BOOK-A-152

Examined by G.H. Cramwell. G.C.

Field Notes
of the
Survey of the
Pine Valley Guide Meridian
in
Townships 42, 41, 40 & 39 South
between
Ranges 15 & 16 West
of the
Salt Lake Meridian
Utah Territory
by
V. C. Bailey
under prime Contract
of Bailey & Burrell
No. 73
dated Sep. 4th 1876

Surveyed April the 5th 7th & 16th 1877

Pine Valley Guide Meridian /
in T. 42 S. Rs. 15 & 16 W. of the Salt Lake Meridian

BOOK-A-152

Chains

Survey commenced April 5th 1897 by F. C. Bailey

Note: Having traced the line between secs 19 & 24 and between secs 13 & 18 and finding the two original 1/4 sec cors. gone or destroyed thereon from the cedar post cor. to secs 19, 24, 25 & 30 I run

North on resurvey line between secs 19 & 24

Var. 16° E.

6.75 S. side of Street bears E & W. in the city of St George

7.95 N. side of same street

15.55 S. side of street bears E. & W.

16.80 N. side of same

18.50 S. side of Avenue bears N. W. & S. E.

BOOK-A-152

Township 39 South R. 16 West



Deer Valley Ranch Mountain

Pine Valley Guide Meridian in

Chains	
20.45	N. side of same
25.00	Foot of hills bears N.W. & S.E. – Leave St. Georges and ascend.
40.00	No trace of original ¼ sec. cor thereof & re-establish it by setting a sandrock 16 × 10 × 6 in 10 in. deep marked ¼ on W. side with mound of stone for ¼ sec. cor.
54.00	Top of Red sandstone bluff bears N.W & S.E
80.00	Intersect old cor. which I find standing in good order. Land S 25 lks cultivated city lots Soil 1st rate timber except fruit trees, grape vines & cedar of Commercial Value.

T. 4
B
Clear
10.
33.
37.
46.
68.
80.

T. 42 S. R. 15 & 16 W. of the S. L. M. 3

BOOK-A-152

Chains

N. on a survey line between secs 13 & 18
Var. 16° E.

10.00 Legge timber
10.50 Descend
33.90 Rocky wash drains N.W.
37.50 " " " S.W.
ascend

46.00 Finding no trace of original cor. thereon I re-establish it by setting Sandstone 18 x 12 x 12 in. 12 in. deep marked 1/4 on N. side, with mound of stone for 1/4 sec. cor.
Note: This is the end of former survey

68.00 Top of steep slope
84.00 Set sandstone 30 x 12 x 6 in. 12 in deep notched 2 N. & 4 S., with mound of stone for cor to secs

Pine Valley Guide Meridian . . . in

Chains

7. 12. 13 & 18
Land broken & rocky
Soil 3rd rate
No timber.

North between secs. 7 & 12
Var. 16° E.

40.00 Set Sandstone 18 x 12 x 5 in
12 in deep marked 1/4 m N.
side with summit of stone
for 1/4 sec. cor.

80.00 Set sandstone 30 x 8 x 3 in
21 in. deep notched 1 N.
& 5 L., with mound of ston
for cor to secs 16. 7 & 18
Land broken
Soil 3rd rate
No timber
Some indications of mineral

T. 42 S. R. 15 & 16 W. 6th P. L. Mn.

BOOK-A-152

5

Chains	
	North between secs 1 & 6
	Var 16° E.
7.25	Gulch drains S E.
23.50	" " "
40.00	Pit Sandstone 16 x 9 x 4 in 10 in deep marked 1/4 on N. side with mound of stone for 1/4 sec. cor.
80.00	Last mentioned gulch drains S. W.
80.00	No trace of original cor. thereof re-established same by setting Trachyte 20 x 10 x 6 in. 15 in. deep marked 4 notches on N. S. E & W. edges and mound of stone for cor to Townships 41 & 42 S. R. 15 & 16 W. Land mostly broken & rocky Soil 3rd rate No timber

6 Pine Valley Guide Meridian no

Chains

General Description.

The Tps. S & N. of this line lie in the broken & rocky bluffs & are not surveyable.

Dw T. 4 S. bet. Rs. 15 & 16 W. —

North between secs 31 & 36

Var 16° E.

40.00 Set sandstone 30 x 18 x 6 in 24 in. deep marked 1/4 on W side with mound of stone for 1/4 sec. cor.

80.00 In Sandy flat set Sandstone 14 x 10 x 5 in 9 in. deep notched 5 N & 10 E. and mound of earth from 4 pits each 24 x 12 x 12 in for cor to secs 25 30. 31 & 36

Land broken

N 41

32.0

37.0

11.1

51.

50.

BOOK-A-152

Township *Yuba* **R.** *11 West*



Sierra Valley Land & Lumber Co.

BOOK-A-152

7

N 47 S. betw. Rs 15 & 16 W. of the S.L. Mer.

Chains — Soil 2nd & 3rd rate

No Timber

North between secs 25 & 30

Var. 16° E.

32.00 Gulch drains S.E.

37.00 Foot of second Trachyte Bench bears E & W.

41.00 Marked Stationary Trachyte 36 x 30 x 30 in. above ground 1/4 on W. side and mound of stone for 1/4 sec. cor. on S. slope of trachyte bench.

57.00 Top of bench bears E & W.

61.00 Set trachyte 30 x 14 x 3 in 24 in deep notched + N & S., with mound of stone for cor. to secs 19 24. 25 & 30

Chains	Land mostly broken & rocky Soil 2nd rate No timber
	North between secs 19 & 24 Var. 16° E.
40.00	On Top of low Trachyte Knoll bears E & W. 5 lks dist Trachyte 14 x 10 x 8 in. 9 in. deep marked ¼ on W. side mitte mound of stone for ¼ sec cor.
80.00	Set Trachyte 16 x 6 x 3 in. 18 in deep notched 3 N. & S., mitte mound of stone for cor. to secs 13, 18, 19 & 24
	Land broken Trachyte knob Soil 2nd rate No timber

BOOK-A-152

T. 4 S. Rs 15 & 16 W. of the 9

Chains

North between secs 13 & 18

Var. 16° E.

40.00 Set Trachyte 14 x 8 x 7 in 9 in. deep marked ¼ on W. side, with mound of stone for ¼ sec. cor.

Enters timber

61.50 Wood Road bears E & W.

81.00 Set Trachyte 16 x 10 x 6 in 10 in deep marked 4 notches on E. & 2 on N. edges with mound of stone for cor. to secs 7. 12 13 & 18 from which

A cedar 10 in. dia. bears N 10° E. 40 lks dist. marked S. 7 S. 4 L. R 15 W. B.T.

Land nearly level

Soil 2nd rate

Timber pine & cedar of commercial value on N. 40 chs

Pine Valley Guide Meridian in

Chains	
	North between secs 7 & 12
	Var. 16° E.
37.50	Ravine drains S. E.
46.00	Set trachyte 30 x 16 x 4 in
	2 in deep marked 1/4 on W. sec
	with mound of stone for 1/4
	sec cor.
59.75	Wood Road bears E & W.
61.50	" " " N.W. & S.E.
67.10	Road to Pine Valley " " " "
81.00	On top of low ridge set
	Trachyte 20 x 12 x 12 in. 15 in
	deep notched 1 N. & 5 S., with
	mound of stone for cor to
	secs 1. 6. 7 & 12
	from which
	A cedar 12 in dia bears N 40 E.
	115 lks dist. marked S. 6 T. 41
	S. R 15 W. B. T.
	Land gently rolling

T. 4 S. Intn. R. 15 & 16 W. of the S. L. Mn.

11

Soil 2nd rate
Timber cedar and pine of
commercial value

North between secs 1 & 6
Var. 16° E.

32.10	Enter Trachyte bears N.E. & S.W.
36.00	Leave same bear N.E & S.W.
38.00	Mound bears E. & W.
46.00	Set Trachyte 24 x 12 x 10 in 18 in. deep marked ¼ on W. side, with mound of stone for ¼ sec. cor.
47.50	Old Road bears E & W.
76.00	Descend trachyte bench bears N.E & S.W.
73.00	Enter Danen Valley
80.00	Set Trachyte 18 x 8 x 6 in 12 in deep marked 6 notches

Pine Valley Guide Meridian in

T. 40

on S. E & W. edges for closing cor. to Tps 41 S. R 15 & 16 W. on 8th Standard Parallel South from which

A cedar 9 in. dia bears S 85° E. 180 lks dist. marked S. 6 T. 41 S. R 15 W. B. T.

Land rolling

Soil 2nd rate

Timber cedar & pine of commercial value

April 5th 1877

J. C. Bailey

For general Description see end of Subdivision notes of this Township.

T. 4

T. 40 S. between Rs 15 & 16 W. of the S.L.M.

BOOK No 152 13

Surveyed bet. Rs 15 & 16 W.

April 6th 1877 by J. C. Bailey

Note: As there was no convergency allowed on the 8th Standard Parallel South in running the Guide Line South between Ranges 13 & 14 W. I therefor allow convergency only for two townships in Longitude and two in Latitude which is 2.20 chains.

From the closing cor. to township 41 South Ranges 15 & 16 West I run

West along the 8th Standard Parallel South on S. side sec 31

Var. 16° E.

2.20 Set trachyte 20 x 14 x 5 in 15 inches deep marked 6 notches on N. E & W. edges with monument of stone for Standard Cor to T. 40 S.

R. 15 & 16 W.

		Chains
	from which	60.00
	A cedar 10 in. dia bears N. 83° W.	70.00
	350 lks dist blazed & marked	80.50
	with a notch in the blaze	
	(Timber scribe lost)	
	From this cor 2 mis	
	North between secs 3 & 36	
	Var. 16° E.	
10.00	Along W. slope	
35.00	Ravine drains W.	
40.00	Set trachyte 18 x 16 x 4 in 12 in	
	deep marked ¼ on W. side, with	
	mound of stone for ¼ sec. cor.	
	from which	
	A cedar 5 in. dia bears N 87°	16.10
	W. 85 lks. dist marked ¼	21.00
	S. B. T.	40.00
42.50	Top of ledge bears S 87 &	
	S. E.	

T. 40 S. Range. R. 15 ½ W. of the S. L. M.

BOOK-A-152

15

Chains	
	Ridge bears E ¼ W.
40.00	Second
80.00	Set Trachyte 15 x 14 x 4 in. 10 in deep notched 5 N. & 5 S. with mound of stone for cor. to secs 25, 30, 31 & 36 from which A cedar 10 in dia bears S 5° E. 54 lks dist marked S 31 T. 40 S. R 15 W. B. T. Land broken Soil 2nd rate Timber Cedar of commercial value

North between secs 25 & 30

Var. 16° E.

16.10	Old Road bears N. E. & S. W.
21.00	Ravine drains S. W.
40.00	Set Trachyte 15 x 6 x 4 in 10 in deep marked ¼ on W. side with mound of stone for.

Tin Valley Guide Meridian in

16

Chains	
	1/4 sec. cor. from which
	A cedar 10 in. dia bears S 30° E.
	150 lks dist. marked 1/4 S. B. T.
41.00	Ravine drains W.
65.00	" " S. W.
75.00	Road bears N. E & S. W.
80.00	Set Trachyte 14 x 8 x 6 in 9 in
	deep notched 4 N & 2 E; with
	mound of stone for cor to
	secs 19 24 25 & 30
	from which
	A cedar 6 in. dia bears N 73 E
	175 lks dist marked S 19 E. 40 L
	R 15 W. B. T.
	Land broken & rocky
	Soil 2nd rate
	Timber cedar of commercial
	value

T. 40

Chains

0.50

14.00

25.00

40.00

70.00

80.00

T. 40 S. betw. R. 15 & 16 W. of the S. L. Mer.

BOOK-A-152

13

Chains	
	North between secs 19 & 24
	Var. 16° E.
0.50	Old Road bears N.E. & S.W.
14.00	Gulch drains S.W.
25.00	Ravine drains S.W.
40.00	Set Trachyte 15 x 10 x 6 in 10 in deep marked 1/4 on W. side with mound of stone for 1/4 sec. cor. from which
	A Juniper 3 in. dia bears N. 2° 45' W. 420 lks dist. marked 1/4 S. B. T.
70.00	Ravine drains S.W.
80.00	Set trachyte 15 x 12 x 12 in. 10 in. deep marked 3 notches on N & S. edges, with mound of stone for cor to secs 13. 18. 19 & 24 from which
	A cedar 12 in. dia bears N. 49 E. 240 lks dist. marked S 18

Pine Valley Guide Meridian in

Chains

T. 40 S R 15 W. B.T.

Land Mostly

Soil 2nd rate

Timber cedar & Juniper of

Commercial value

North between secs 13 & 18

Var. 16° E.

18.50 Ravine drains S.W.

40.00 Set Trachyte 14 x 8 x 6 in 9 in. deep marked 1/4 on W. side, with mound of stone for 1/4 sec. cor. from which

a Juniper 4 in. dia. bears North 12 lks. dist. marked 1/4 S. B.T.

42.60 Ravine drains S.W.

80.00 Set Trachyte 18 x 15 x 8 in 12 in deep notched 2 N. & 4 S., with mound of stone for cor. to secs 7 12. 13 & 18

T. 40

Chains

7.00

40.00

65.0

75.0

80.0

BOOK-A-152

T. 40 S. betw. Rs 15 & 16 W. 4th P. L. On 19

Chains	from which
	A Cedar 10 in. dia bears S 89° E. 325 lks dist. marked S 16 T. 40 S R 15 W. B. T.
	Land rolling & rocky
	Soil 2nd rate
	Timber Cedar & Juniper of commercial value

North between secs 7 & 12
Var. 16° E.

7.00	Gulch drains S. W.
4.00	Set trachyte 14 x 14 x 10 in 9 in deep marked 1/4 on W. side, with mound of stone for 1/4 sec cor.
65.00	Sand Gulch drains S. E.
75.00	" " " S. W.
80.00	Set trachyte 14 x 10 x 6 in 9 in deep marked 1 notch on N. & E. on

Pine 20 Valley Guide Meridian ...

B
T. 4
Chains
8.00

Chains S. edges, with mound of stone for cor. to secs 1, 6 7 & 12

from which

A cedar 13 in. dia S. 50° W. 70 lks dist marked S. 12 T. 40 S. R 16 W. B. T.

Land broken & rocky

Soil 2nd rate

Timber cedar & pine of commercial value

North between secs 1 & 6

Var. 16° E.

8.00 Ravine drains S E.

40.00 Set Trachyte 14 x 16 x 6 in pin deep marked ¼ on W. side, with mound of stone for ¼ sec. cor.

BOOK-A-152

T. 40 S. Subdiv. R. 15 & 16 W. of the S.L. M.

21

Chains
80.00

Set trachyte 14 x 10 x 6 in w 9 in dep marked 6 notches on N. S. E & W. edges with Monument of stone for cor. to Tps. 39 & 40 S. Rgs 15 & 16 W.

From which

A cedar 12 in dia. bears S 5° E 30 lks dist. marked S. 6 T. 40 S. R 16 W. B. T.

A pine 4 in. dia bears N. 10 W. 50 lks dist. marked S 36. T. 39 S R 16 W. B. T.

Land nearly level

Soil 1st rate

Timber cedar & pine of commercial value

April 6th 1877 J. C. Bailey

For General Description see end of Subdivision notes of T. 40 S R 16 W.

Pine Valley Guide Meridian in
In Tps 39 & 40 S. Rs 15 & 16 W.

T. 39 S.

Chains

April 16th 1878 by J. C. Bailey

From the cor. to Tps. 39 & 40
S., Rs 15 & 16 W. to avoid
the mountains I offset West
160 chs thence N. 240 chs
thence E. 160 chs to true line
where I set Granite rock
10 x 9 x 6 in 6 in. deep marked
B notches on N. & S. edges,
with mound of stone for cor
to secs 13, 18. 19 & 24 on
N. slope thence
North between secs 13 & 18
Var. 16° E.

Chains

45.00
65.00
80.00

I. second

14.00 The bottom drains N.
marked stationary Granite
rock 36 x 12 x 12 in. above
ground 1/4 on N. side, with

Chains	
	mound of stone for ¼ sec. cor.
	from which a cedar 8 in. dia bears West 60 lks dist marked ¼ S. B. T.
	Ascend
45.00	Trail bears E & S.
65.00	Along N. slope
80.00	Marked stationary Granite rock 36 x 24 x 12 in above ground, 2 notches on N. & W. on S. edges, with mound of stone for cor. to secs 7, 12 13 & 18 —
	from which
	A Pine 8 in. dia bears N. 10 W. 15 lks dist marked S 12 T. 39 S R 16 W. B T
	Land rolling

Pine Valley Guide Meridian W.

Chains Soil and rate
Timber Pine & Cedar of
commercial value

North between secs 7 & 12
Var 16° E.

5.00 Descend
12.50 Hollow drains N. W.
18.50 Telegraph line bears E & W.
19.00 Road bears E & W.
21.00 Bottom of hollow drains W.
40.00 on S. W. point of Trachyte
Spur set Trachyte 20 x 16 x 5
in. 15 in. dug marked ¼ on W.
side with mound of stone
for ¼ sec. cor.
from which
A cedar 10 in. dia. bears

Chains
59.70
78.50
80.00

BOOK-A-152

T. 39 S. Rs. 15 & 16 W. of the Salt Lake Meridian

25

Chains

N. 60° E 175 lks dist marked
¼ S. B. T.

59.70

Santa Clara River Banks
Channy in placed being inv.
practicable & triangulate
across same and find

71.50

On N. side of banks, the
River runs Nr. 50 lks. wide
in bottom of the rocky gulch

Jeep Road runs E & W.

78.50
80.00

Set Trachyte 18 x 12 x 12 in
Main deep notched 1 N. &
S. E., with mound of
stone for cor to secs
1. 6. 7 & 12

Land rolling
Soil 2nd rate
Timber, cedar & pine
of commercial
value.

Note On account of the broken country to the North I abandon the line here —
April 16th 1877
J. C. Bailey

For Remarks Description see end of Subdivision notes of T. 39 S. R. 16 W.

BOOK-A-152

27

U. S. SURVEYOR GENERAL'S OFFICE.

Salt Lake City, Utah, June 30th *187*7

The foregoing field notes of the survey of the Pine Valley Guide Meridian in Ths. 42, 41, 41½, 39, S.

~~*Township No.*~~ ..... *Ranges No.* 15 & 16 W.

Executed by Bailey & Burrell

Under the first *contract of the* 4th

day of Sept. *187*6, *in the month of*

April *187*7, *having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.*

Nathan Kimball

Surveyor General for Utah.

BOOK-A-152

Township 45 South R. 11 West



Fourth Principal Meridian

BOOK-A-152 1

Examined by C.H. Crowell. 66

33

Field Notes
of the
First Y. North & Boundary
Township 40 South Range 16 West
Salt Lake Meridian
Utah Territory
as surveyed by
F. G. Bailey
under joint contract Bailey & Bennett
No 73. — dated Sept 4th 1876

Survey commenced Apl 9th 1877
" completed " 10th "

West Boundary T. 40 S. R. 16 W.

Chains		Chains
	Apr 9-1877 by T. C. Bailey	
	From the established	
	standard cor. to T. 40 S. R.	
	16 & 17 W.	
	North on range line	
	bet. secs. 31 & 36	4.00
	Va. 16° E.	
40.00	Set sandstone 16×8×7 in	
	11 in. deep marked 1/4 on W.	
	side raised mound of	2.00
	stone for 1/4 sec. cor.	
80.00	Set Trachyte 11×10×5	
	in. deep notched 1 on S.	0.00
	& 5 on N. edge raised mound	0.00
	of stone for cor. to secs. 25. 30.	
	31 & 36 from which	
	A Pine 12 in. dia bears	
	N. 20° E. 45 lks. dist	
	marked T. 40 S. R. 16 W.	
	S. 30. B. T.	

Salt Lake Meridian.

Chains Land broken Soil Sage
Timber Pine & Cedar

North bet. secs 25 & 30
Va. 16° E.

1.00 Set Trachyte 10x10x6 in
6 in deep marked 1/4 on N.
side & raised mound of stone
for 1/4 sec. cor.

2.00 Lean broken rocky brush
center flat runs S.E. & S.W.
lean timber —

0.00 Gulch drains S.W.

0.00 Set Trachyte 18x10x8 in. 12
in. deep notched 1 on N. & E.
on S. edges raised mound
of stone for cor. to secs 19, 24
25 & 30

Sand mostly broken
Soil Sage

West Boundary T. 40. S. R. 16 W. 3rd
Chains Timber Pine & Cedar

North bet secs 19 & 24
Va. 16° E.

40.00 Set Trachyte 16×14×8 in. 11 in. deep marked 1/4 on N. side. Raised mound of stone for 1/4 sec. cor.

80.00 Set Trachyte 14×12×10 in. 9 in. deep notched 3 on N & S. edges Raised mound of stone for cor. to secs. 13, 18, 19 & 24 -
Land level dry & flat No Timber -

North bet. secs. 18 & 19
Va. 16° E.

24.60 Road bears N 77 E.

40.00 Set Red Trachyte 14×12×8

Salt Lake Meridian

Chains 9 in. deep marked 1/4 on N. side
raised mound of stone for
1/4 sec. cor.

4.50 S. slope of extinct volcano
Offset West 10.00 chs. Thence
North 32.50 chs Thence
East 10.00 chs. to
0.00 On true line on N. slope
of volcano set Red
Lava Rock 16x12x10 in.
11 in deep notched 2 on N.
& W sides S. sides raised
mound of stone for cor.
to secs. 7, 12, 13 & 18
Land S. 1/2 level N. 1/2
Volcano slope Soil 2nd rate
No Timber

North bet. secs. 7 & 12
Va. 16.8.

West Boundary T. 40 S. R. 16 W. 38

Chains	
	Descend to
20.00	Foot of volcano slope -
40.00	Pet Trachyte 18×15×10 in. 12 in. deep. marked 4 on W. side trail mound of stone for 4 sec. cor.
55.00	Road to Mountain Lock Brass N.E. 1 S. W.
76.50	Santa Clara River in rocky walls 40 ft. wide runs S. W.
80.00	Mark Trachyte in place 4×2×1 foot above ground 3 notches on S. & W. edges trail mound of stone for cor. Secs. 1. 6. 7 & 12 Sand broken flat 2 Pinus No Timber -

North 1/4 sec. 1 & 6

Salt Lake Meridian

Chains Va. 16°E.

40.00 Set Trachyte 18×12×8 in. 12 in. deep marked 1/4 on N. side. Raised mound of stone for 1/4 sec. cor.

80.00 Set Trachyte 24×16×2 in 18 in. deep Raised mound of stone for cor. to T. 39 & 40 S. R. 16 & 17 W.

Land undulating Soil Sandy

~~Apr 9th T. C. Bailey~~

~~Apr 10th 1877 by T. C. Bailey~~

From the cor. to T. 39 & 40 S. R. 16 & 17 W.

East on random line bet said townships the variation by improved Burt's Solar compass being 16° E. Note: The last

North Boundary T. 40 S. R. 16 W.

Chains 120. chs by offsets as explained in true line)
I find the line to be .5 miles 79 chs & 44 lks. & the falling to be 60 lks. N. of the township cor.
The correction for the true line will therefore be 10 lks. south per mile & the course N. 89° 56' W.
From the cor. to T. 39 & 40. S. R. 15 & 16 W.
N. 89° 56' W. on true line
Lt. secs. 1 & 36
Va. 16° E.

Note: The line in place being impracticable, I offset South 30.00 chs thence West 80.00 chs to a point 30.00 chs S. of

Salt Lake Meridian

chains
80.00 The true cor. falling in steep hills is not set, therefore at the point 30.00 chs. S. of true cor. point set Trachyte 10x12x7 in. 6 in deep marked 1 notch on E & S on N. edges & W. C. Raised mound of stone in Ravine drains N. for witness cor. to secs 1. 2. 35 & 36 Land mountainous Soil Dry Timber Cedar & Pine

---

N. 89° 56' W. on true line bet secs. 2 & 35

Va. 16° E.

From the witness cor. as above described I run West on offset line 40.

North Boundary T. 40. S. R. 16. W.

.00 chs Thence North 30. chs to
40.00 On true line at W. foot
of Ridge bears N.E. 85. lks.
Set Sandstone 1 x 10 x 5 in
6 in deep, marked 1/4 on N.
side & raised mound of
stone for 1/4 sec. cor.
80.00 Set Trachyte 20 x 16 x 6 in. 15
in. deep, notched 2 on E & 4 on
W. edges & raised mound of
stone for cor. to secs. 2. 3. 34 & 35
from which
A Cedar 18 in. dia. bears
N. 2. E. 7 lks. dist. marked
S. 35. T. 39. S. R. 16. W. B. T.
Land broken. Soil & Veg.
Timber Cedar & Pine

N. 89° 56' W. on true line
bet. secs. 3 & 34

chains	
	Va. 16° E.
7.80	Telegraph line bears S. & S.
40.00	Set Trachyte 4 x 2 x 8 in 9 in. deep marked 1/4 on S. side raised mound of stone for 1/4 sec. cor.
30.00	Rocky Canon bears N. 30 W.
80.00	10 chs. South of mouth of canon heads S. & Set Trachyte 16 x 10 x 7 in. 11 in. deep notched 3 on E & W. edges raised mound of stone for cor. to secs. 3, 4, 33 & 34
	Land broken, soil & Data No Timber

N. 89° 56' W. on true line bet. secs. 4 & 33

Va. 16° E.

North Boundary T. 40. S. R. 16. W.

chains		chains
	Along N. slope of Back-ite Bench	
40.00	set Trachyte 22×18×8 in 18 in deep marked ¼ on N. side raised mound of stone for ¼ sec cor.	40.00
55.00	Bear slope trends S. W.	55.00
80.00	set Limestone 16×10×3 in. 11 in deep notched 4 on E & 2 on W. edges raised mound of stone for cor. to secs 4. 5. 32 & 33	80.00
	Land broken hilly & rocky Timber a few cedar & pine	

N. 89° 56' W. on true line bet. secs. 5 & 32

Va. 16° E.

10.00	Road Ruro N. E. & S. W.	25.00
22.50	Top of Trachyte Butte	40.00

R. 16. W. Salt Lake Meridian

chains

40.00 Set Trachyte 16x10x8 in. 11 in. deep marked 1/4 on N. side raised mound of stone for 1/4 sec. cor.

55.00 Santa Clara River in bulch 30 lks wide runs S. W.

80.00 Set Sandstone 16x12x4 in. 11 in. deep notched 5 on E & 1 on W. edges raised mound of stone for cor. to secs. 5, 6, 31 & 32
Found broken Jar & Date Tree & a few Pine & Cedar

N. 89° 56' W. on true line bet. secs. 6 & 31

Va. 16.66

25.00 Wash drains S. E.

40.00 Set Trachyte 15x10x6 in. 10

North Boundary T. 40 S. R. 16.

Chains in dep marked 1/4 cor.
side raised, mound
of stone for 1/4 sec. cor.
53.00 Ridge bears N. & S.
79.44 The cor. to T. 39 & 40 S. R. 16
& 17 W.
Land rolling Soil Rate
No Timber
April 10th 1877 T. C. Bailey

Note: For general Description
& approval see end of
subdivision notes of this
Township —

BOOK A 152

Examined by G. H. Cromwell. 66.

Field Notes
of the
Survey of the
Subdivision lines of
Township 40 South
Range 16 West
of the
Salt Lake Meridian
Utah Territory
by
Bailey & Burrill
under joint contract of
Bailey & Burrill
N. 73
dated Sept. 4th 1876

Survey commenced April 10th 77
" completed " 13th "

BOOK-A-152

Township 40. South **R.** 16 West



Pine Valley Guide Meridian

18.0

7.0

30.5

37.5

40.0

55.00

BOOK-A-152

Subdivision lines of T. 40 S. R 16 W.
Salt Lake Meridian 49

Chains

Survey commenced April 16th
1877 by Maj. Burrill
From the Standard
cor. to secs 35 & 36 on the
8th Standard Parallel South
2 mm
North between secs 35 & 36
Var. 16° E.

Descend

18.00 Foot of hill enter bottom
21.00 Pines cor: 30 lks E. fences
bears N. 7 chs & E 10 chs
36.50 Road bears E & W. bears
Lambs house 4. 50 chs E.
37.50 Enter hills bear E & W
Spring 1.50 chs E.
40.00 Set Sandstone 20 x 12 x 6 in
12 in. deep marked 1/4 on North
with mound of stone for 1/4 sec. cor.
58.00 Ridge bears N.E. & S.W.

Subdivision lines of T. 40 S

Chains
80.00 In mound drains S. W. marked stations
Trachyte 24 x 20 x 20 in 18 in
deep marked 1 notch on E & S edges
with mound of stone for
cor. to secs. 25, 26, 35 & 36

Land rolling
Soil 2nd rate
Timber Pine & Cedar.

East on random line
between secs 25 & 36
Var 16° E.

40.00 Set temporary 1/4 sec. cor.
79.90 Intersect Guide Meridian at
cor to secs 25 & 36
from which
West on true line
between secs 25 & 36
39.95 Set a trachyte 18 x 10 x 9 in
12 in deep marked 1/4 on N.

BOOK-A-152

Chains

side, with mound of stone for 1/4 sec. cor.

79.90 The cor. to secs 25, 26 35 & 36

Land rolling
Soil 2nd rate
Timber cedar.

North between secs 25 & 26
Var. 16° E.

Ascend

10.00 Ridge point bears N E & S W. descend

19.50 Road in hollow runs N E. & S W. ascend

40.00 Set Stone 20 x 10 x 8 in 15 in deep marked 1/4 on W. side, with mound of stone for 1/4 sec. cor.

Subdivision lines of T. 41 S.

Chains	
80.00	Set Trachyte 24x7x6 in 18 in deep notched 1 E & 2 S., with mound of stone for cor. to secs 23 24 25 & 26. Land broken & rocky Soil 2nd rate Timber cedar & juniper.

East on random line between secs 24 & 25 Var. 16° E

40.00	Set temporary 1/4 s.c. cor.
7[illegible].00	Gulch drains S. & W.
7[illegible].00	Road bears S.E. & S. W.
7986	Intersect Guide Meridian at cor to secs 24 & 25 from which West on true line between secs 24 & 25
39.93	Set Trachyte 20x10x6 in 15

R 16 W. Salt Lake Meridian. 5
53
BOOK-A-152

Chains deep marked 1/4 on N. side,
with mound of stone for 1/4
sec. cor.

79.86 The cor. to secs 23 24 25 &
26

Land rolling
Soil 2nd rate
Timber cedar.

North between secs 23 & 24
Var. 16° E.

4.00 Ledge on edge of gulch
bears N.E. & S.W.

40.00 Set trachyte 18 x 14 x 12 in 14 in
deep marked 1/4 on W. side, with
mound of stone for 1/4 sec cor

80.00 Set trachyte 28 x 14 x 10 in 21
in. deep notched 1 E & 3 S., with
mound of stone for cor to secs.

6 54
Subdivision lines of T. 40 S

Chains 13: 14 23 & 24
Land ascending N.
Soil 2nd rate
Timber cedar & Juniper

East on random line
between secs 13 & 24
Var. 16° E.

40.00 Set temporary 1/4 sec. cor.
51.00 Gulch drains S.W.
79.96 Intersect Guide Meridian
16 lks S. of cor to secs
13 & 24
from which
S. 89° 53' W. on true line
between secs 13 & 24
39.98 A Trachyte 20x10x10 ins 15 ins dug
marked 1/4 on N. side, with mound
of stone for 1/4 sec. cor.

R 16 W. Salt Lake Meridian —

BOOK-A-152

Chains

79.96 The cor to secs 13, 14, 23 & 24

Land rolling
Soil 2nd rate
Timber cedar & juniper —

North between secs 13 & 14
Var. 16° E.

4.00 Gulch runs S. W.

40.00 Set trachyte 16 x 12 x 10 in 10 in deep marked 1/4 on W. side with mound of stone for 1/4 sec. cor.

80.00 Set trachyte 16 x 12 x 6 in. 10 in deep notched 1 E & 4 S, with mound of stone for cor. to secs 11, 12, 13 & 14

Land broken Soil 2nd rate
Timber cedar & juniper

---

8 Subdivision lines of T. 4 D S. 56

Chains

East on random line
between secs 12 & 13
Var. 16° E.

40.00 Set temporary 1/4 sec. cor.
47.50 Ravine drains S. Br.
64.00 Gulch " "
80.00 Intersect base Meridian
at cor. to secs 12 & 13
from which
West on true line
between secs 12 & 13
40.00 Set brachyte 30 x 20 x 4 in 2 in
deep marked 1/4 on N. side
with mound of stone for 1/4
sec. cor.
80.00 The cor. to secs. 11. 12, 13 & 14
Land broken
Soil 2nd rate good grass
Timber cedar & junipers

R 16 W. Salt Lake Meridian

57

BOOK-A-152

Chains

North between secs 11 & 12
Var. 16° E.

40.00 Set trachyte 15 x 9 x 4 in 10 in deep marked ¼ on W. side, with mound of stone for ¼ sec. cor.

80.00 Set trachyte 18 x 14 x 8 in 12 in deep notched 1 E & 5 S. with mound of stone for cor to secs 1, 2, 11, 12

Land rolling
Soil 2nd rate
Timber scattering cedar.

East on random line between secs 1 & 12
Var. 16° E.

35.00 Ridge bears N & S.
40.00 Set temporary ¼ sec. cor.

10 58

Subdivision lines of T. 40 S

Chains		Chains
52.00	Descend	52.
70.00	Enter flat	
80.00	Intersect Guide Meridian at cor to secs 1 & 12 from which West on true line between secs 1 & 12	80.00
40.00	Set trachyte 12 x 12 x 6 in 8 in. deep marked 1/4 on N. side with mound of stone for 1/4 sec. cor.	39.40
80.00	The cor. to secs 1. 2. 11 & 12 Land heavy rolling — Soil 2nd rate Timber scattering pine & cedar.	79.40

North on random line between secs 1 & 2
Var. 16° E.

40.00	Set temporary 1/4 sec. cor.

R 16 W. Salt Lake Meridian

BOOK-A-152

Chains

50.00 Foot of ridge N.E. & S.W.

The true cor. to secs 1 & 2 on N. boundary of Tp. not being established thereon at 49.40 chs intersect the Witness cor. 30 chs S. of

80.00 The true cor. bears, from which South on true line between secs 1 & 2

39.40 Set Trachyte 12 x 10 x 5 in 8 ins deep marked 1/4 on W. side with summit of stone for 1/4 sec. cor.

79.40 The cor. to secs 1. 2. 11 & 12

Land rolling.

Soil 2nd rate

Timber scattering Pine & Cedar

April 10th 1877 J. G. Burrill.

April 11th 1877 by J. C. Bailey.

From the Standard Corner to secs 34 & 35 on the

60

Subdivision lines of T 40 S

Chains	8th Standard Parallel South 2 nw
	North between secs 34 & 35
	Var. 16° E.
17.00	Leave lava at foot of Volcano
18.00	Road bears N.W. & S.E.
40.00	Set limestone 14 x 10 x 6 in 9 in. deep marked 1/4 on W. side and mound of earth from 4 pits each 24 x 12 x 12 in for 1/4 sec. cor.
	from which
	John Myers & Geo. Edwards houses bear East 6.25 chs in enclosed field bearing 4 chs N. & 5 chs S. of houses
47.00	Road N.W. & S.E.
62.00	Dry bed of Spring Branch

R 15 W. Salt Lake Meridian

BOOK-A-152

Chains drains S. W.

77.30 Road bears E & W.

78.80 " " N W. & S E.

80.00 Sit trachyte 14 x 12 x 8 in qm
dugs notched 2 E & 1 S, with
mound of stone for cor. to
secs 26, 27, 34 & 35
Land mostly level bottom
Soil 1st rate
No timber

East on random line
between secs 26 & 35
Var. 16 E.

3.00 Road bears N. E & S. W.

3.50 Dry bed of Spring Branch
drains S. W.

7.00 Reservoir 5 chs S.

23.00 Telegraph line at foot of

Subdivision line of T. 40 S.

Chains	
	hills bears N. & S
40.00	Set temporary ¼ sec cor.
53.00	Canon Wash drains S.
56.50	Road bears N. & S.
60.00	S. point of ridge bears N.
65.00	Road bears N.E. & S.W. in canon drains S.W. A spring 6 chs S.W.
80.16	Intersect N & S. line at cor to secs 25, 26, 35 & 36 from which West on true line between secs 26 & 35
40.08	Set Sandstone 16 x 10 x 8 in 10 in. dug mounded ¼ on N. side with mound of stone for ¼ sec. cor
80.16	The cor. to secs 26, 27 34 & 35.

R. 16 W. Salt Lake Meridian 15

BOOK A 152 63

Chains Land mostly rolling
Soil 2nd rate
Timber scattering cedar

North between secs 26 & 27
Var. 16° E.

18.50 Road bears N. E & S. W.

25.00 Enter hills bears N. E & S. W.

32.50 " high bench bears N. E & S. W.

40.00 Set sandstone 16 x 10 x 7 in 10 in deep marked 1/4 on W. side, with mound of stone for 1/4 sec. cor.

80.00 Set sandstone 19 x 10 x 10 in 13 in deep marked 2 notches on E. & S. edges with mound of stone for cor. to secs 22, 23, 26 & 27 from which

A cedar 10 in. dia bears S. 60° W. 7 & 1/2 lks. dist marked

16 64

Subdivision lines of T. 40 S

Chains	S. 27 T. 40 S. R. 16 W. B. T.
	A cedar 5 ins. dia. bears N. 5 W.
	32 lks dist marked S. 27 B. T.
	Land heavy rolling
	Soil 2nd rate
	Timber cedar & pine

East on random line
between secs 23 & 26
Var 16° E.

12.00	Descend
20.00	Enter hollow drains S.
23.50	Telegraph line bears N & S
24.00	Road bears N. & S.
25.10	Spring Branch drains S.
30.00	Ascend rocky slope
40.00	Set temporary 1/4 sec. cor.
74.00	Ravine drains S.W.
80.36	Intersect N. & S. line at

R 16 W. Salt Lake Meridian

BOOK-A-152

Chains cor. to secs 23, 24, 25 & 26
from which
West on a true line
between secs 23 & 26
40.18 Set sandstone 13 x 10 x 9 in 8 in
deep marked 1/4 on N. side, with
mound of stone for 1/4 sec. cor
80.36 Pine cor. to secs 22, 23, 26 & 27
Land heavy rolling
Soil 2nd rate
Timber scattering cedar
& pine

North between secs 22 & 23
Var. 16° E.
7.00 Hollow drains E.
11.00 Ridge runs E & W.
40.00 Set sandstone 11 & 10 x 6 in
8 in. deep marked 1/4 on W. side

Subdivision line of T. 40 S

Chains	with mound of stone for
	1/4 sec. cor.
80.00	Trachyte 16 x 10 x 8 in 10 in
	deep notched 2 E & 3 S. with
	mound of stone for cor to
	secs 14, 15, 22 & 23
	from which
	A cedar 4 in. dia bears N 85 E
	14 lks distant marked B. T.
	T 40 S R 16 W.
	Land rolling
	Soil red rocky
	Timber pine & cedar

East on random line
between secs 14 & 23
Var. 16 E.

4.80	Telegraph line bears NW & SE.
23.50	Ravine drains S. W.

R 16 W. Salt Lake Meridian

BOOK-A-152

Chains

37.50 North of Gulch bears N.E.

40.00 Set temporary 1/4 sec. cor.

44.50 Ravine drains S.

60.00 Gulch drains S.W.

80.00 Intersect S. & N. line at cor. to secs 13, 14, 23 & 24 from which West on true line between secs 14 & 23

40.00 Set trachyte 18 x 12 x 6 in 12 in deep, marked 1/4 on N. side, with mound of stone for 1/4 sec. cor.

80.00 The cor. to secs 14. 15. 22 & 23

Land broken & rocky

Soil red rate

Timber cedar & pine

North between secs 14 & 15

Var. 16° E.

Subdivision lines of T. 40 S

Chains	
17.40	Telegraph line bears N.W. & S.E.
40.00	Set trachyte 11×10×5 in 8 in. deep marked 1/4 on W. side, with mound of stone for 1/4 sec. cor.
80.00	Set trachyte 14×10×6 in 9 in deep marked 2 notches on E. & 4 on S. edges, with mound of stone for cor to secs 10, 11 14 & 15
	Sand rolling
	Soil red Gate
	Timber scattering cedar & pine

East on random line between secs 11 & 14

Var. 16° E.

40.00	Set temporary 1/4 sec. cor.
59.00	Gulch drains S.
80.40	Intersect N. & S. line at

R 16 W. Salt Lake Meridian 21

BOOK-A-152 69

Chains cor to secs 11 12 13 & 14
from which
West on true line
between secs 11 & 14
40.20 Set Trachyte 10 x 10 x 7 in 6 in
dup marked 1/4 on N. side, with
mound of stone for 1/4 sec. cor.
80.40 The cor to secs 10 11 14 & 15
Land gently East slope
Soil 1st rate
Cedar Timber & Juniper

North between secs 10 & 11
Var. 16° E.
40.00 Set trachyte 16 x 10 x 8 in 10 in
dup, marked 1/4 on W. side
with mound of stone for 1/4
sec. cor.
80.00 Set trachyte 14 x 12 x 8 in. 9 in

22 10

Subdivision lines of T. 40 S.

Chains	
	deps marked 2 notches on E. & 5 on S. edges, with mound of stone for cor to secs 2, 3, 10 & 11 from which
	a cedar 5 in dia bears N. 5° E. 20 lks distant marked S 2 T. 40 S. R 16 W. B. T.
	a cedar 7 in dia bears S 10° E 62 lks dist. marked S. 11 B. T.
	Land mostly level
	Soil 1st rate
	Timber cedar, pine & juniper

East on random line between secs 2 & 11 Var 16 E.

Ascend

40.00	Set temporary ¼ sec. cor.
80.00	Intersect N & S. line at

BOOK-A-152

R. 16 W. Salt Lake Meridian 1911

Chains Cor. to secs 1, 2, 11 & 12
from which
West on true line
between secs 2 & 11

40.00 Set trachyte 14 x 12 x 6 in. 9 in.
deep marked 1/4 on W. side, with
mound of stone for 1/4 sec. cor.

80.00 The cor. to secs 2, 3, 10 & 11
Land ascending E.
Pine 2nd rate
Timber scattering cedar & pine

North on random line
between secs 2 & 3
Var. 16° E.

40.00 Set temporary 1/4 sec. cor.
45.00 Trachyte Gulch drains N. W.
70.00 " " " West
79.30 Intersect N. Boundary of T. 2 S.

24 72

Subdivision lines of T. 40 S.

Chains

at cor. to secs 2 & 3

from which

South on true line

between secs 2 & 3

39.30 Set Trachyte 15 x 10 x 7 in 10 in. deep marked 1/4 on W. side, with mound of stone for 1/4 sec. cor.

79.30 The cor. to secs 2, 3 10 & 11

Land rolling

Soil 2nd rate

Timber scattering pine & cedar.

April 11th 1877 F. C. Bailey

April 11th by J. G. Burrill

From the Standard cor. to secs 33 & 34 on the 8th Standard Parallel South

I run

North between secs 33 & 34

Var. 16 E.

R 16. W. Salt Lake Meridian

BOOK-A-152

73

Chains

On account of chgs off set 7.50 chs E. thence N. 40.00 chs thence W. 7.50 chs to

40.00 On line in place set Sandstone 16×12×5 in 10 in deep marked 1/4 on W. side, with mound of stone for 1/4 sec. cor.

76.00 Road bears N. W. & S. E.

80.00 Set sandstone 20×20×8 in 15 in deep notched 3 E & 1 S., with mound of earth raised from 4 pits each 24×12×12 in for cor. to secs 27, 28 33 & 34 Land on line broken Soil 2nd rate Timber pine & cedar.

East on random line between secs 27 & 34 Var. 16° E.

Subdivision lines of T. 40 S. 14

Chains	
40.00	On W. slope of low ridge at temporary ¼ sec. cor.
57.00	Ridge bears N.W. & S.E.
70.50	Road " " "
78.10	" " " "
80.12	Intersect North & South line at cor. to secs 26, 27, 34 & 35 from which
	West on true line between secs 27 & 34
46.06	Set sandstone 14 x 8 x 6 in 9 in. deep marked ¼ on N. side with mound of stone for ¼ sec cor.
80.12	The cor to secs 27, 28, 33 & 34.
	Land mostly level
	Soil 1st rate
	No timber

R 16 W. Salt Lake Meridian 27

BOOK-A-152

Chains

North between secs 27 & 28
Var. 16° E.

8.00 Road bears E & W.

10.00 Accnd bears E & W

40.00 On W. point of ridge set sand stone 12 x 12 x 7 in. 8 in. deep marked ¼ on W. side, with mound of stone for ¼ sec. cor.

68.00 Trail bears N. E & S. W. in Birch draw S. W.

80.00 Set limestone 18 x 12 x 8 in 12 in. deep notched 3 E & 2 S. with mound of stone for cor to secs 21, 22 27 & 28 from which

A cedar 6 in. dia bears N 10 E 20 lks dist marked S 22 S 40 S R 16 W. B. T.

Land rolling

16

Subdivision lines of T. 46 S.

Chains	
	Soil 2nd rate
	Timber Pine & Cedar.

East on random line
between secs 22 & 27
Var. 16° E.

9.75	Gulch drains S. W.
11.25	Trail Road bears N.E & S.W.
33.25	Same bears N.W. & S.E.
	in hollow drains N. W.
40.00	Set temporary ¼ sec. cor.
58.00	Trail bears N. & S.
80.17	Intersect N & S. line 10 lks
	N. of cor. to secs 22 23 26 & 27
	from which
	N. 89° 56' W. on true line
	between secs 22 & 27
40.08	Set sandstone 18 x 12 x 10 in
	12 in deep marked ¼ on N. side

R 16 W. Salt Lake Meridian

Chains

with mound of earth ston
pros 4 pits each 24 x 12 x 12 in
for 1/4 sec. cor.

80.17 The cor to secs 21 22 27 28

Land undulating
Soil 1st rate
Timber pine & cedar

North between secs 21 22

Var. 16° E.

25.00 Gulch drains W.

36.00 " " S.W.

46.00 Set trachyte 16 x 12 x 8 ins 10 ins
deep marked 1/4 on W. side with
mound of stone for 1/4 sec cor

74.00 Descend

80.00 Set sandstone 16 x 10 x 7 ins 10 ins
deep notched 3 E & S. with mou
of stone for cor to secs 15.16. 21 22

Subdivision lines of T. 40 S.

Chains	Soil 2nd rate Timber Pine & Cedar.
	East on meadow line between secs 22 & 27 Var. 16° E.
9.75	Gulch drains S. W.
11.25	Trail Road bears N.E & S.W.
33.25	Same bears N.W. & S.E.
	in hollow drains N. W.
40.00	Set temporary ¼ sec. cor.
58.60	Trail bears N. & S.
80.17	Intersect N & S. line 10 lks N. of cor. to secs 22 23 26 & 27 from which N. 89° 56' W. on true line between secs 22 & 27
40.08	Set sandstone 18 x 12 x 10 in 12 in dep marked ¼ on N. side

R 16 W. Salt Lake Meridian

T 7 N

Chains

with mound of earth thrown
from 4 pits each 24 x 12 x 12 in
for 1/4 sec. cor.

80.17 The cor to secs 21 22 27 28

Land undulating
Soil 1st rate
Timber pine & cedar

North between secs 21 22

Var. 16° E.

25.00 Gulch drains W.

36.00 " " S.W.

46.00 Set brachyte 16 x 12 x 8 in 10 in
deep marked 1/4 on W. side with
mound of stone for 1/4 sec cor

74.00 Descend

80.00 Set sandstone 16 x 10 x 7 in 10 in
deep notched 3 E & S. with mound
of stone for cor to secs 15 16 21 22

32 Subdivision lines of T. 40 S. 80

Chains secs 9, 10, 15 & 16.
Land rolling
Soil red mte
No timber

East on random line
between secs 10 & 15
Var 16° E.

40.00 On top of S. end of trachyte ridge set temporary 1/4 sec. cor.

64.10 Telegraph line bears N. & S.

80.10 Intersect N. & S. line at cor to secs 10, 11, 14 & 15 from which
West on true line
between secs 10 & 15

40.03 Marked stationary Trachyte 30 x 20 x 15 in. above ground

R. 16 W. Salt Lake Meridian 83

Chains

marked
¼ on N. side, with mound of stone for ¼ sec. cor.

80.00 The cor to secs 9, 10 15 & 16
Land gently N. W. slope
Soil 1st rate
Timber cedar & Juniper

North between secs 9 & 10
Var. 16° E.

21.00 Enter drain W.

40.00 Set trachyte 13 x 10 x 6 in 8 in deep marked ¼ on W. side with mound of stone for ¼ sec. cor.

80.00 Set trachyte 13 x 10 x 6 in 8 in deep marked 3 notches on E & 5 on S. edges, with mound of stone for cor to secs 3, 4 9 & 10

34 87

Subdivision lines of T. 40 S

Chains	
	Land mostly level
	Soil 1st rate
	Timber pine & cedar

East on random line
between secs 3 & 10
Var. 16° E.

40.00	Set temporary 1/4 sec. cor.
68.50	Telegraph line bears N & S.
80.76	Intersect N. & S. line at cor to 2. 3, 10 & 11

from which
West on true line
between secs 3 & 10

40.38	Set trachyte 16 x 12 x 6 in 10 in deep marked 1/4 on N. side, with mound of stone for 1/4 sec cor.
80.76	The cor. to secs 3, 4

R 16 W. Salt Lake Meridian

Chains 9 & 10
Land mostly gentle W. slop
Soil 1st rate
Timber scattering cedar

North on random line
between secs 3 & 4
Var. 16° E.

40.00 Set temporary 1/4 sec. cor.
49.28 Intersect N. boundary of T.
at cor to secs 3 & 4
from which
South on true line
between secs 3 & 4
39.28 Set bracketed 16 x 16 x 5 in 10 in
deep marked 1/4 on W. side,
with mound of stone for 1/4
sec cor.
49.28 The cor to secs 3, 4, 9 & 10

36 84

Subdivision lines of T. 40 S

Chains

Land mostly sloping N.W.
Soil 1st rate
Timber scattering cedar.
April 11th 1877, J. G. Burrill

April 12th 1877 by T. C. Bailey
From Standard cor.
to secs 32 & 33 on 8th
Standard Parallel South
& new
North bet. sec. secs 32 & 33
Var. 16° E.

40.00 Set Trachyte 14×10×7 in gin.
dep marked ¼ on W. side
with mound of stone for ¼ sec. cor.

80.00 Set sandstone 16×12×8 in
10 in dep notched 4 E & 4 S.,
with mound of stone for
cor. to secs 28, 29,
33 & 32

Range 16 W. - Salt Lake Meridian

Chains from which

A Pine 14 in. dia bears
S 40 E 20 lks dist marked
S. 33 T. 40 S. R 16 W. B T
A Pine 5 in. dia. bears N 30° E
marked S 28 B.T.
Land broken & rocky
Soil 2nd rate
Timber cedar & pine

East on standard line
between secs 28 & 33
Var. 16° E.

2.00 Ravine drains N.
27.50 " " "
40.00 Set temporary 1/4 sec. cor
5/.00 Leave broken ground bea
N. W. & S. E.
74.80 Road bears N. W & S E

Subdivision lines of T 40 S

Chains	
80.00	Intersect N & S. line at cor to secs 27, 28 33 & 34 from which West on true line between secs 28 & 33
40.00	Set sandstone 20 x 16 x 5 in. 15 in deep marked 1/4 on W. side with mound of dirt for 1/4 sec. cor.
80.00	The cor to secs 28, 29 32 & 33 Land E 1/2 level Soil 1st rate W. 1/2 broken Soil 2nd rate Timber pine & cedar.

North between secs 28 & 29
Var. 16° E.

17.00	N. point between 2 gulches heading S E & S W.
32.25	Gulch drains N. 10 E.

R 16 W. Salt Lake Meridian

Chains	
40.00	Set Sandstone 16 × 10 × 4 in 10 in. deep marked 1/4 on W. side with mound of stone for 1/4 Sec. Cor from which
	A pine 14 in dia bears N. 45 W. 36 lks dist. marked 1/4 S. B. T. on bench
62.00	Leave bench enter flat bears N. W. & S E.
64.00	Road bears N. W & S E.
80.00	Trachyte 20 × 12 × 10 in 15 in deep notched 4 E & 2 S, with mound of stone for cor to Secs 20 21 28 & 29 from which
	A cedar 14 in. dia bears N. 75° E 65 lks dist marked S. 21 T 4 S R 16 W. B.T.
	Land mostly rolling & broken

Subdivision lines of T. 40 S.

Chains	Soil and note
	Timber Pine & Cedar
	East on a random line between secs 21 & 28 Var 16° E
8.00	Wash drains N.W.
11.50	Road bears N.W. & S.E.
30.75	" " N. & S.
40.00	Set Temporary Qr. sec. cor.
77.50	Foot of hills bear N & S.
80.40	Intersect N. & S. line 15 lks S. of cor to secs 21, 22 27 & 28
	from which S 89° 54' W. on true line between secs 21 & 28
40.20	Set Limestone 14 x 10 x 6 in. 9 in. deep marked 1/4 on N. side

R 16 W. Salt Lake Meridian.

BOOK-A-152

87

Chains

with mound of stone for 1/4 sec. cor. from which

A cedar 6 in dia bears South 10 1/2 lks. dist marked 1/4 S. B. T.

$0.40 The cor to secs 20, 21, 28 & 29

Land mostly level

Soil 1st rate

Timber scattering pine and cedar

North between secs 20 & 21

Var. 16° E.

13.00 Wash drains N. W.

17.40 Road bears N. W. & S. E.

40.00 Set trachyte 20 x 12 x 10 in 15 in. deep marked 1/4 on W. side with mound of stone for 1/4 sec. cor.

41.00 Pine Valley Road bears

Subdivision lines of T. 40 S.

Chains	N. W. & S. E.
54.00	Road bears N. 10° W. & S 10° E.
80.00	Set Schist rock 12 x 7 x 7 in 8 in. deep notched 4 E & 3 S., with mound of stone for cor. to secs 16. 17. 20 & 21
	Land mostly level
	Soil 1st rate
	Timber scattering cedar & pine

East on abandoned line between secs 16 & 21
Var. 16° E.

12.00	Lone Butte
19.00	Hollow drains N.
30.00	Lone Butte
40.00	Set temporary 1/4 sec cor.
65.50	Road bears N. E & S W.
69.80	Bottom of hollow drains

R. 16 W. Salt Lake Meridian 1913

BOOK-A-152

Chains	
	S. W.
80.46	Intersect N. & S. line at cor. to secs 15, 16, 21 & 22 from which West on true line between secs 16 & 21
40.20	Set sandstone 16 x 10 x 4 in 10 in deep marked 1/4 on N. side with mound of stone for 1/4 sec. cor.
80.40	The cor to secs 16, 17, 20 & 21 Land broken Soil 2nd rate Timber Cedar

North between secs 16 & 17
Var. 16° E.

5.00	Road bears N. E & S. W.
40.00	Set sandstone 12 x 10 x 6 in.

Subdivision lines of T. 40 S

	Chains 8 in. deep marked ¼ on W. side with mound of stone for ¼ sec. cor.	Chains
80.00	Set trachyte 12 x 10 x 8 in. 8 in deep notched 4 E & S. with mound of stone for cor to secs 8, 9, 16 & 17.	40.10
	Land mostly level	80.20
	Soil 1st rate	
	Timber scattering cedar	

East on random line between secs 9 & 16
Var. 16° E.

25.20	Old Road bears N.E & S.W.	25.00
34.00	Ascend	
40.00	Set temporary ¼ sec. cor.	31.00
80.20	Intersect N & S line at cor. to secs 9, 10, 15 & 16	40.00

R 16 W. Salt Lake Meridian

BOOK-A-152

	Chains	from which
		West on true line
		between secs 9 & 16
	40.10	Set trachyte 20 x 15 x 8 in 15 in deep marked 1/4 on N. side with mound of stone for 1/4 sec. cor.
	80.20	The cor to secs 8 9 16 & 17 Land gentle W. slope Soil 2nd rate Timber scattering pine & cedar
		North between secs 8 & 9 Var. 16° E.
	25.00	Foot of trachyte bench bears E & W.
	31.00	Enter flat bench
	40.00	Set trachyte 10 x 10 x 6 in 6 in deep marked 1/4 on W. side

Subdivision lines of T. 40 S R.

Chains		Chains
	with mound of stone for 1/4 sec. cor.	66.50
68.00	Descend hill E & W.	80.70
80.00	Set Sandstone 16 x 12 x 5 in 10 in. deep notched 4 E & 5 S., with mound of stone for cor. to secs 4, 5, 8 & 9	
	Land mostly rolling	40.35
	Soil 2nd rate	
	No timber	
		80.70

East on random line between secs 4 & 9
Var: 16° E.

Along N. slope Trachyte bench

40.00	Set temporary 1/4 sec. cor	
57.00	Descend N.E. slope of bench	10.00

R. 16 W. Salt Lake Meridian

BOOK-A-152

95

Chains

66.50 Old Road bears N. & S. in hollow drains S ascend

80.70 Intersect N. S. line at cor. to secs 3 4 9 & 10

from which

West on true line between secs 4 & 9

40.35 Set sandstone 16 x 7 x 5 in ground in deep marked 1/4 on N. side with mound of stone for 1/4 sec. cor.

80.70 The cor to secs 4. 5. 8 & 9

Land mostly broken

Soil 2nd rate

Timber scattering pine & cedar

North on random line between secs 4 & 5

Var. 16 E.

10.00 Fort of trachyte bench

Subdivision lines of T. 40 S

Chains

40.00 Set temporary 1/4 sec. cor.

47.00 Road bears E. & W.

62.50 Enter trachyte point

70.00 Leave same bears E & W.

79.20 Intersect N. Boundary of Tp.
at cor. to secs 4 & 5
from which
South 80 links line
between secs 4 & 5.

39.20 Set sandstone 16 x 10 x 8 ins
16 in dep marked 1/4 on W.
side with summit of stone
for 1/4 sec. cor.

79.20 The cor to secs 4 5 8 & 9
Land rolling
Soil red Sate
Timber scattering pine
& cedar
April 12th 1877 T. C. Bailey

R.

Chains

40.00

80.00

R. 16 W. Salt Lake Meridian

BOOK-A-152

97

Chains

April 12th 1877 by J. G. Burkett

From the Standard Cor. to secs 31 & 32 on the 8th Standard Parallel South

2 mm

North between secs 31 & 32

Var. 16° E.

40.00 Set trachyte 12 x 10 x 6 in 8 in deep marked 1/4 on W. side with mound of stone for 1/4 sec. cor.

80.00 Set trachyte 14 x 10 x 9 in 9 in deep notched 5 on E & 1 on S edges; with mound of stone for cor to secs 29, 30, 31 & 32

Land broken & rocky

Soil 2nd rate

Timber cedar & pine

Subdivision line of T. 40 S

Chains	
	East on random line between secs 29 & 32
	Var. 16° E.
40.00	Set temporary ¼ sec. cor.
66.00	Gulch drains N.E
80.44	Intersect N. & S. line at cor. to secs 28 & 29, 32 & 33 from which
	West on true line between secs 29 & 32
40.22	Set trachyte 15 x 11 x 7 in 10 in. deep marked ¼ on N. side with mound of stone for ¼ sec. cor.
80.44	The cor. to secs. 29, 30, 31 & 32
	Land broken
	Soil 2nd rate
	Timber Pine & cedar

R 16 W. Salt Lake Meridian

BOOK A-152

Chains

West on random line
between secs 30 & 31
Var. 16° E.

40.00 Set temporary ¼ sec. cor.

80.00 Intersect W. Boundary of
Tp. at cor to secs 30 & 31
from which
East on true line
between secs 30 & 31

40.00 Set brichyte 11×9×5 in 7 in
deep marked ¼ on W. side
with mound of stone
for ¼ sec cor

80.00 The cor to secs 29, 30,
31 & 32
Land broken & rocky
Soil poor and wet.
Timber pine & cedar

57 Subdivision lines of T. 40 S

Chains

North between secs 29 & 30
Var. 16° E.

40.00 Set trachyte 12 x 10 x 6 in 8 in deep marked ¼ s on W. side, with mound of stone for ¼ sec. cor.

80.00 Set trachyte 12 x 10 x 6 in 8 in deep notched 5 E. & 2 S., with mound of stone for cor to secs 19. 20. 29 & 30

Land rolling & rocky
Soil red & stiff
Timber pine & cedar.

East on random line
between secs 20 & 29
Var. 16 E.

40.00 Set temporary ¼ sec. cor.

57.00 Enter flat stone broken [illegible]

Chains	
62.25	Road bears N.W. & S.E.
79.96	Intersect N. & S. line at cor to secs 20, 21, 28 & 29 from which West on true line between secs 20 & 29
39.98	Set trachyte 12 x 12 x 7 in 8 in deep marked 1/4 on N side with mound of stone for 1/4 sec. cor.
79.96	The cor. to secs 19. 20. 29 & 30 Land mostly broken Soil very rocky Timber pine & cedar

West on random line between secs 19 & 30
Var 16° E.

40.00	Set temporary 1/4 sec. cor.
54.00	Wash in deep canon

5-4 Subdivision lines of T. 40 S 10 W

Chains	
	drains S. W.
63.50	S. point of ridge bears N.
66.75	Enter flat
80.00	Intersect W. Boundary of Tp. at cor to secs 19 & 30 from which East in true line between secs 19 & 30
40.00	Set sandstone 10 x 10 x 6 in 6 in. deep marked 1/4 on N. side with mound of stone for 1/4 sec. cor.
80.00	The cor. to secs 19. 20. 29 & 30 Land mostly broken Soil 2nd rate Timber cedar & pine

North between secs 19 & 20
Var 16° E.

R

Chains	
30.00	
40.00	
65.00	
80.00	

R 16 W. Salt Lake Meridian

BOOK-A-152

Chains	
30.00	Wash in deep cañon drains S.W.
40.00	Set trachyte 14 x 12 x 10 in 9 in deep marked 1/4 on N. side, with mound of stone for 1/4 sec. cor.
62.00	Road at foot of bench bears N.W. & S.E.
80.00	Set trachyte 16 x 10 x 8 in 10 in deep notched 5 E. & 3 S, with mound of stone for cor to secs 17, 18, 19 & 20 from which A cedar 4 in dia. bears S.80 W. 15 lks dist marked S 19 T. 40 S R 16 W. B.T. Land mostly broken Soil 2nd rate Timber, fine cedar

Subdivision lines of T. 40 S

Chains		Chains
	East on meridian line between secs 17 & 20 Var 16° E.	
40.00	Set temporary ¼ sec. cor.	
57.50	Road bears N.W. & S.E.	
76.20	" " N.E & S.W.	
80.00	Intersect N. & S. line at cor to secs 16. 17 20 & 21	13.50
	from which	24.50
	West on true line	35.50
	between secs 17 & 20	40.00
40.00	Deposited small trachyte	58.40
	marked with a cross (~~+~~ X) in	61.00
	mound of earth raised from	79.90
	4 pits each 24 x 12 x 12 in	
	for ¼ sec cor	
80.00	The cor to secs 17. 18.	
	19 & 20	
	Land mostly level	

R 16 W. Salt Lake Meridian

BOOK-A-152

Chains	
	Soil 1st rate
	No timber
	April 13th 1877 J. G. Burrill
	April 13th 1877 by T. C. Bailey
	West on random line
	between secs 18 & 19
	Var. 16° E.
13.50	Road at foot of rocky
	bench bears N W & S E.
24.50	Enter grassy glade down N.
35.50	Leave same
40.00	Set temporary ¼ sec. cor.
58.40	Descend high rocky bluff bears N & S
61.00	Enter flat
79.90	Intersect W. Boundary of
	Tp. 20 S. R. 16 W. 4 cor to
	secs 18 & 19
	from which
	N 89° 57' E on true line
	between secs 18 & 19

5-8 106

Subdivision lines of T. 40 S

Chains		
39.90	Set sandstone 20 x 8 x 5 in 15 in. deep marked 1/4 on N. side with mound of stone. for 1/4 sec cor.	
79.90	The cor. to secs 17, 18 19 & 20	
	Land nearly level	
	Soil 1st rate	
	Timber Cedar & Pine	

North between secs 17 & 18

Var. 16° E.

		8.20
		15.00
		22.00
40.00	Set trachyte 14 x 9 x 7 in 9 in deep marked 1/4 on N. side with mound of stone for 1/4 sec cor.	40.00
		80.00
80.00	Set trachyte 14 x 8 x 6 in 9 in deep notched 5 E & 4 S, with mound of stone	40.00

BOOK-A-152

R 16 W. Salt Lake Meridian 1877

Chains for cor to secs 7, 8 17 & 18

Land nearly level

Soil 1st rate

No timber

East on random line between secs 8 & 17 Var. 16° E.

8.20	Road bears N.W. & S.E.
15.00	Foot of hill bears N.W. & S.E.
22.00	Ravine gully
40.00	Set temporary 1/4 sec cor.
80.00	Intersect N. & S. line at cor to secs 8 9 16 & 17 from which West on true line between secs 8 & 17
40.00	Set charred cedar post

60 Subdivision lines of T. 40 S.

Chains	
	48 x 4 x 4 in. M in deep marks, 1/4 on N side and mixed mound of earth from 4 pits each 24 x 12 x 12 in for 1/4 sec cor.
80.00	The cor to secs 7. 8. 17 & 18
	Land mostly level
	Soil 1st rate
	Timber scattering cedar on E 1/2

39.80

79.80

West on random line between secs 7 & 18
Var 16° E.

5.00	Enter trachyte bench bears N.W. & S.
40.00	Set temporary 1/4 sec. cor.
53.00	Ascend steep extinct

15.50

5006-A-152

R 16 W. Salt Lake Meridian 10 S.

Chains	
	Down steep slope
70.00	Top of knoll
79.80	Intersect W. Boundary of Townships at cor to secs 7 & 18 from which
	East on true line between secs 7 & 18
39.80	Marked Stationary Porphyry 36 x 2 4 x 14 in above ground 14 on N. side; and mound of stone for 1/4 sec. cor.
79.80	The cor. to secs 7. 8. 17 & 18
	Land very broken
	Soil 3rd rate
	No timber

North between secs 7 & 8

Var. 16° E

15.50 Road to Pine Valley

62 110

Subdivision lines of T. 4 o S R 1

Chains		
	bears N.W. & S.E.	
26.00	Ledge bears N.W & S.E.	
40.00	Set trachyte 15 x 10 x 8 in 10 in dep marked 1/4 on W. side with mound of stone for 1/4 sec. cr.	
55.00	Bend in old Road bears N.W. & S.W.	21.30
60.00	W. point of ledge descend	
64.00	Same old Road bears N.E & S.W.	30.00
		40.00
65.50	Pine Valley Road bears N.E. & S.W. enters flat	47.00
80.00	Set limestone 16 x 11 x 4 in 10 in dep marked 5 notches on E & S. edges, with mound of stone for cor to secs 5. 6, 7 & 8.	80.16
	Land S 40 chs - rolling	40.05
	Balance level flat	
	Soil 2nd rate	

R 16 W. Salt Lake Meridian

No timber.

East on random line
between secs 5 & 8
Var. 16° E.

21.30 Pine Valley Road bears N.E & S.W. Record

30.00 N. point of ledge

40.00 In mine drains N. to temporary 1/4 sec. cor.

47.00 Ledge bears N.E. & S.

80.10 Intersect N. & S. line at cor to secs 4. 5. 8 & 9 from which

West on true line
between secs 5 & 8

40.05 Set trachyte 3" x 2" x 1 foot 2 feet due S. marked 1/4 on N. side, with mound of stone

Chains		Chains
	for ¼ sec. cor.	
80.10	The cor to secs 5, 6, 7 & 8	
	Land mostly level	39.80
	Soil Vgd rate	
	Timber Cedar & pine on E½	
		79.80
	West on random line between secs 6 & 7 Var 16° E.	
30.00	Foot of N. slope of "Big Hill"	
38.00	Road to Gunlock bears N.W. & S.E.	
40.00	Set temporary ¼ sec cor	
65.00	Santa Clara River 50 lks wide runs S.W.	2.05
79.80	Intersect W. boundary of Tp at cor to secs 6 & 7 from which	30.00
		40.00

R 16 W Salt Lake Meridian

BOOK-A-152

Chains

East on true line between secs 6 & 7

39.80 Set trachyte 14 x 10 x 8 in 9 in. deep marked 1/4 on N. side, with mound of stone for 1/4 sec. cor.

79.80 The cor. to secs 5. 6 7 & 8

Land mostly level
Soil 1st rate
No timber

North on random line between secs 5 & 6
Var. 16° E.

2.05 Road bears E & W.

30.00 Ridge bears E & W.

40.00 Set temporary 1/4 sec. cor.

Subdivision lines of T. 40 S R.

Chains
61.50 Santa Clara River 30 lks wide 2 feet deep Banks 50 feet high runs S.W.

80.00 Intersect N. Boundary of Sp. at cor to secs 5 & 6 from which

South on true line between secs 5 & 6

40.00 Set old trachyte 16 x 8 x 5 in 10 in. deep marked 1/4 on W. side with summit of stone for 1/4 sec. cor.

80.00 The cor to secs 5, 6 7 & 8.

Land broken except South 30 chs Soil 2nd rate Timber cedar & pine in middle

April 13th 1877 T. C. Bailey

BOOK-A-152

R. 16 W. Salt Lake Meridian

1156

General Description

This township embraces the North part of Panoche Valley & adjacent timbered hunches.

The Santa Clara River runs through the N. W. part and several Spring Branches through the S. E. part Secs. 35 & 36 contain the Panoche Settlements The lands are all agriculture.

T. C. Bailey
U.S. Dep. Sur.

118

BOOK-A-152

U. S. SURVEYOR GENERAL'S OFFICE.

Salt Lake City, Utah, June 30 *187*7

The foregoing field notes of the survey of the N. & W. boundary & subdivision lines of *Township No.* 40 S. *Range No.* 16 W. *Executed by* Bailey & Burrill *Under* their Jan'y *contract of the* 4th *day of* Sept *187*6, *in the month of* April *187*7, *having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.*

Wm. Kimball

Surveyor General for Utah.

FFICE.

187

of th

s of

W.

ill

th

onth of

tically

nd ex-

nd the

ved.

Utah.

BOOK-A-152 -3

121

Examined by C. H. Cromwell & C.

Field Notes

of

The Survey of the

South Boundary

Township No 2 S. Range 1 W. Utah.

of

The Salt Lake Meridian,

Utah Territory.

By

J. C. Bailey

Under joint Contract of Bailey & Bamb

No 73 dated Sept 2 1876

Surveyed April 12 1877.

Salt Lake Meridian. 25

Yards. Survey commenced April 15th 1874.

By J. B. Bailey,

From the cor. to Tps. 29 & 30 S.,
R. 1 & 2 W. Salt Lake Mer.,
North one mile
thence East, 1 to 30,
Cor. 16 E.

11,00 Set marble 20x30x15 in.
12 in. deep, sunk 1/4 in. N.
side & mine mound on stone
for 1/4 Sec. Cor.

58,50 Pits bear N. E. 1/2 W.

65,50 " " S.W. Mound.

78,00 Foot of Hills.

80,00 Set Granite boulder, 15 x 10
x 10 in., 10 in. in., notched 1
on E. & 5 on W. edges for Cor.
to Secs. 12, 13, 24 & 25, from which,
Aspen 6 in. dia. bears
N. 40 E. 6.8 lks. dist. marked,

24

4th Concession Tp. of S. Kelly

Chains,

S. 36, T. 39 S. R. 17 W. 3rd P.M.
Land broken & rocky,
Soil, 2nd rate,
Timber, Cedar, cedars,

Work on Land Lots
Between Sec. 2 & 35,
Con. 4th E.

No. gets, 16 ins. over 10 ft.
wide runs S. W. road in
Creek, (Ascends)
Ridge drains N. W. & S. E.
Set trachyte 16 x 10 x 6 ins.
Hew, deep, notched 12 ins. in
side, & round mouths of
stones, for 4th Con.
Ravine drains S.
Set trachyte 20 x 10 x 6 ins.
15 in. deep, notched 2 ins.

BOOK-A-152

Chains, E & W on N. edges, and mounds of stones for Cor. to Secs. 2, 3, 34 & 35,

Land broken.

Soil 2nd rate,

Timber, Scattering Cedar,

April 18th, 1844,

J. C. Bailey

U. S. Dep. Surveyor.

Note;

For Genl. Description & Approval see end of Subdivision Notes of this Dk.

Chair

BOOK-A-152

Examined by C.M. Cranmell C.C.

137

Plan

Field Notes
of the
Survey of the
subdivision lines of
Township 40 South
Range 1 West
of the
Salt Lake Meridian
Utah Territory
by
Bailey & Burrill
under contract of
Bailey & Burrill No 3
dated September 4th 1876

Survey commenced April 13th/77
" completed " 14. "

BOOK-A-152

Township 11[illegible] South **R.** 17, West



BOOK-A-152

Subdivisional line of T. 40 S. R. 17 W.

Salt Lake Meridian 129

Survey commenced April 13th 1877 by J. G. Burrill.

The true boundary between Sec. 25 & 26 on E. boundary of Township 8 runs West on true line between Secs. 25 & 36 var. 16° E.

76.00 Cactus drains N.W.

40.00 Set Trachyte 11 x 11 x 4 in. 8 in. deep marked 1/4 Sec. N. side, with mound of stone for 1/4 Sec. Cor.

56.00 Ridge runs N. & S.

80.00 Cañon next 10 Chs. drains N.W. Set Trachyte 12 x 10 x 6 in. 8 in. deep notched 1 E. & S. Edges with mound of stone for Cor to Secs. 25, 26, 35 & 36

Subdivision lines of T. 40 S. | R. 1

Chains	Land very broken & rocky	Chains
	Soil 2nd rate	
	Timber Cedar, Juniper & pine	
		Sec 80
	North between secs 25 & 26	40.00
	Var 16° E.	40.75
	Descend	80.10
25.00	Gully at 1rst & hills down W.	
40.00	Set trachyte 24 x 12 x 10 in, 18 in	
	deep marked 4 mm - W. sec 26, with	
	mound of stone for 4 cor.	
80.00	Set trachyte 16 x 12 x 10 in 18 in	40.00
	deep notched 1 E & 2 S, with	
	mound of stone for cor to secs	
	23. 24. 25 & 26	80.10
	Land broken & rocky	
	Soil 2nd rate	
	Timber scattering Cedar &	
	Juniper —	

R. 1 W. Salt Lake Meridian

Mean	End on second line between secs 24 & 25 Lat. 16° E.
3.82	Trail runs NW & SE.
40.00	Set temporary 4 sec. cor.
76.75	Trail leaves N & S.
80.10	Intersect E. boundary of T. at cor. to secs 24 & 25 from which
	West on a true line between secs 24 & 25
40.03	Set boxwork 12 x 8 x 6 in. 8 in. deep marked 4 on N. side, with mound of stone for 4 sec. cor.
80.10	The cor. to secs 23, 24, 25 & 26 Found level. Soil 1st rate. No timber

Cable Survey Line of 3.7 40 3

Rain	North between sec. 13 & 24 Var. 16° E.	Chain 46.00 80.00
32.00	a grade station driven S.W.	
46.00	Set Trachyte 16 x 8 x 4 in. 6 in. deep marked + on Top, with Nail & Stone for Witness.	
60.00	Rail road S.W. & S.E.	46.00
80.00	Set Trachyte 20 x 16 x 10 in 15 in. deep notched 1 E., 2 W., with Nail & Stone for Wit. to secs 13, 14, 23 & 24 Land mostly level Soil 1st Rate No timber	80.00
	East on a random line between secs 13 & 24 Var. 16° E.	
38.50	Trachyte, Pile on line	14.00

C. T. & P. Salt Lake Meridian

Chains	
40.00	Set temporary 1/4 sec. cor.
80.00	Intersect E. boundary of T. 16 N. R. 2 E. cor to secs 13 & 24
	from which
	N 89° 53' W. on true line between secs 13 & 24.
40.00	Set Buchyd 16 x 8 x 4 in 10 in. deep marked 1/4 sec No 13, with mound of stone for 1/4 sec. cor.
80.00	S. 1/4 cor to secs 13. 14. 23 & 24.
	from which well, cave bear 1st pine No timber.
	North between secs 13 & 14 Var. 16° E.
14.00	Bottom drains P.W.

Subdivision lines of T. 40 S.

Chains		Chains
40.00	Prop. mon. cor. N. ¼ cor. B.	26.7
40.00	Set Stone 5 x 4 x 5 in. Cor.	
	stone marked ¼ on W. side, with	40.0
	Mound of stone for ¼ sec. cor.	40.0
43.83	Land mon. & ¼ cor.	80.1
45.50	" " E. & ¼ cor. to sections	
80.00	Set Stone 28 x 18 x 18 in. 24	
	in. deep, bedded 18 in. N. & 14 in. E.,	
	with mound of stone for cor	
	to secs. 11, 12, 13 & 14	40.0
	Land broken & rocky	
	Soil Loam	
	No timber	
		80.1

East on a random line
between secs 12 & 13
Var 16° E.

T. 12 N. Salt Lake Meridian

Chains	
26.75	Road to Timber bears N. & E.
40.00	Set temporary 1/4 sec. cor.
63.00	Creek
80.16	Intersect E. boundary of T. at cor to secs 12 & 13 from which (Pine 20" brs Pine between secs 12 & 13
40.08	Set brch'd 16 x 10 x 8 in. 10 in. deep marked 1/4 N. side, north mound of stone for 1/4 sec. cor.
80.16	The cor to secs 11 12 13 & 14 Land broken & rocky. Good red soil No timber

Subdivisional lines of T. 40 S.

		Chain 4-50
N.B.	North between secs 11 & 12	79.9
	Var. 16° E.	
W.C.	Santa Clara River 50 lks wide runs S.W. in deep gulch	
M.C.	Set triangle 15 x 12 x 7 ins 12 ins. above marked 4 sides, with mound of stone & dec. cor	30.0
S.C.	Set triangle 12 x 15 x 10 ins 15 ins. deep marked 1/4 S 5 E. with mound of stone for cor. to secs 1, 2, 11 & 12	79.9
	Land nearly level	
	Soil 1st rate	
	No Timber	

Said cor. is meander line between secs 1 & 12 Var. 16° E. 30.0

Chains

4.00 Set Limestone 4 sec. Cor.

79.90 Thence E. and boundary of T.
10 N. R. 2 W. to sec. 1 & 12
from which
S 89° 56' W. on true line
between secs 1 & 12

39.95 Set Limestone 18 x 17 x 11 in.
in deep mounds 4 ons N. side
with mound of stone for 4 sec. cor.

79.90 To cor. to secs 1, 2, 11 & 12

Large undulating
Soil 2nd rate
No timber

North on a random line
between secs 1 & 2
Var. 16° E.

30.00 Edge of bluff, bear N E & SW.
Recrossed

Subdivision lines, T. 6 S., R. 40 E.

Chains	
40.00	E. Quarter sec. cor.
47.50	Fence at 1.50 E. and W.
2.32	W. R. Cross Tie bears N. 2 E.
0.66	Ditch runs S. W. Fence on S. side of it
8.00	Ditch runs S. E.
80.20	Intersect N. boundary of T. 6 S. at cor. to secs. 1 & 12, brass, which South on brass line between secs. 1 & 12
40.20	Planted bracketed in place 3 x 2 x 1 set above ground 1/4 on W. side, south mound of stone for 1/4 sec. cor.
80.20	The cor. to secs. 1, 12, 11 & 12 Land & Lot brass

40.

80.

T. 2 N. Salt Lake Meridian

Soil 2nd rate
N & East & Creek bottom
Soil 1st rate
Timber Cottonwood & Cedar
Survey 13th 1877 J. G. Burrill

April 14th 1877 by
T. C. Bailey
Ran the Cor to
secs. 22, 23, 26 & 27
2nd rund
West on true line
between secs 22 & 27
Var. 16° E.

40.00 Set bracketed 11 x 11 x 5 in 8 in
deep marked 1/4 on N. side,
with mound of stone for
1/4 sec. Cor.

80.00 Set bracketed 10 x 9 x 6 in

Subdivision lines of T. 40 S.

Chains	40 links deep notches E & W, North Mound of stone for Cor to secs 22, 23, 26 & 27 Found marble Lead Pile 1st rate No timber
	North between secs 22 & 23 Var. 16° E.
40.00	Set trachyte 16 x 10 x 6 in. 10 in. deep marked 1/4 on W side, North Mound of stone for 1/4 sec. cor.
66.00	Edge of bluffs descend—
74.00	Foot " "
80.00	Set trachyte 20 x 15 x 10 in 15 in deep notches E & W, with Mound of stone for cor to secs 14, 15, 22 & 23

Chain

56.

66.

80.

0004-A-152

N. M. P. Salt Lake Meridian

Chains	Land worked Soil Red sand Timber Juniper cedar
	East on a random line between secs 14 & 23 Var. 16° E. Line in place with improvements 2 offset North 10 lks thence up a gulch East 50.00 lks thence South 10 lks to
50.00	run true line 10 lks East
80.12	of gulch drains N.W. Bruff's corner N.W. 1/4 Sec intersect N. & S. line 16 lks S. of cor to secs 13, 14, 23 & 24 from which S. 89° 53' W. on true line between secs 14 & 23

Subdivision lines of S. 40 E.

30.00	Edge of timber. Course N. W. & S. E. Set iron pipe 20 x 10 x 8 in., 5 in. deep marked 1/4 M. C. on N. side, with mound of stone for witness 1/4 sec. cor. Thence with the West line to	40.00
34.12	Sec. cor. to secs. 14, 15, 22 & 23. Land rocky. Soil 2nd rate. Timber, some cedar.	
	North between secs 14 & 15. Var. 16° E.	58.00
16.00	Wm. Barnes House 3 chs W., Field S. & W. of the house.	65.00
20.00	Ridge Spur bears S. & W.	70.00
		80.00

E. & W. Salt Lake Meridian

Chains
28.50 Santa Clara River 50 lks wide runs S.W., clear fresh & cold water. Mica & black sand plentiful - mountains & timber. Second

40.00 Set Conglomerate sandstone 20 x 14 x 6 ins 15 ins deep marked 1/4 on W. side, with mound of stone for 1/4 sec. cor. The Santa Clara River 6.00 lks East runs S.

53.00 Sandstone ledge bears N.E. & S.W. Second

65.00 Road bears N.E. & S.W.

70.00 W. Adkins two houses 60 about 1/2 chs.

80.00 Set Trachyte 18 - 10 x 9 ins 12 ins deep notched 2 E.B.

Subdivision lines of s. 4 S. R 2 W.

Runs	4 S., with mon. N. 40 W. for cor. to secs 10, 11, 14 & 15	Chains 7,80
	Land broken & stony Cultivated in bottoms Other line is 1st rate Oak Timber	39.90
	East on random line between secs 11 & 14 Var. 16° E.	7,80
80.00	Santa Clara River 50 lks wide runs S. W.	
40.00	Set temporary 1/4 sec. cor. Junction of the Dec. gal- lic creek & Santa Clara River N. 7 lks.	
65.00	Santa Clara River 50 lks wide runs N. W.	40.00
7.00	Santa Clara River runs S.	

E. 7 W. Salt Lake Meridian

Chains

79.80 Undersd. S. & L. line
35 lks N. 4 cor to sec 11,
12, 13 & 14 from which
N. 89° 45' W. on true line
between secs 11 & 14

39.90 Set Encinyte 15 x 10 x 5 in 10
in deep marked 1/4 on N. side,
with mound of stone for 1/4 sec
cor.

79.80 The cor to secs 10, 11, 14 & 15
Land broken & rocky
Soil 2nd rate
No timber.

North between secs 10 & 11
Var 16° E.
Along E slope

40.75 Set Encinyte 15 x 10 x 4 in. 10 in
deep marked 1/4 on W. side, with

Chains		Chains
80.00	Mound of Stone for ¼ sec. cor.	
	Set sandstone 16 x 12 x 12 in. 16	
	in. logs notched E & S, with	40.00
	mound of stone for cor. to secs. 2, 3, 10 & 11	
	Land broken & slopes	
	Soil 2nd rate	80.00
	Timber some cedar.	

East on a random line
between secs. 2 & 11
Var. 16° E.

Descend

40.00	Set temporary ¼ sec. cor.	
45.00	Meander creek 10 lks. wide	
	runs S.W. Ascend	
55.00	Top of bluffs bear N.E. & S.W.	
80.10	Intersect N. & S. line at	40.00
	cor. to secs. 1, 2, 11 & 12	
	from which	

T. 14 N. Salt Lake Meridian

Chains

West on true line
between secs 2 & 11

4.00 Set sandstone 16 x 12 x 9 in. 10 in
deep marked ¼ on N side, with
mound of stone for ¼ sec. cor.

80.00 Pit cor. to secs 2, 3, 10 & 11
Grass worked
Soil red sandy No timber
Note Abandon line here

From cor to secs 22, 23
26 & 27 N run
West on true line between secs 22
& 27 Var 16° E.

4.00 Set sandstone 16 x 11 x 9 in, 10 in.
deep marked ¼ on N side, with
mound of stone for ¼ sec. cor.

Subdivision lines of T. 6 S.

Chains		Chains
0.00	Cor. of 4 sec. 1 & 2	40.00
	East 19 chs. thence	
	West 19 chs. to	
85.00	Set Stone witness Cor. 14 B.T.	45.00
	19 chs. north of true Cor. where	59.00
	a marked Cruchyte in place	
	1 x 1 x 1 foot above ground 3 cu. links	
	on E. & W. lines on S. edge W. C.	74.00
	with mound of stone for witness	80.00
	Cor. to secs. 1, 2, 11 & 12	
	Land broken & rocky	
	Soil & vegetable. No timber	

North between secs. 1 & 2.
Var. 16° E.

19.00	Witness Cor.	
21.00	Santa Clara River 50 lks wide runs S.W.	10.00
23.50	Road runs N.E. & S.W.	21.00
24.00	Ditch runs S.W.	23.00

T. 1 N. R. 6 E. Salt Lake Meridian.

Chains	
40.00	Set sandstone 16 x 9 x 6 in. 10 in. deep marked ¼ on W. side with mound of stone for ¼ sec. cor.
45.00	Descend
75.00	Cor. of fences bear N 20 E. & S 40 E. 2.5 lks. East Road on outside of fence, field on inside
75.00	Descend to
80.00	Set Sandstone 16 x 10 x 8 in, 10 in. deep notched 3 E. & S., with mound of stone for cor. to secs 15, 16, 21 & 22. Land broken. Soil 2nd rate. No timber. Various cultivations.

East on random line between secs 15 & 22. Var. 16° E.

10.00	Descend
21.00	Road bears N E & S W at foot of hills
23.00	Wash drains S E.

Subdivision lines of T. 40 S. R.

Chains		Chains
2.50	Fence runs N & S. east bank	
36.50	" " NE & SW bank "	
40.00	Set Temporary ¼ sec. cor.	
50.00	Santa Cruz River 30 lks wide runs SW.	
70.00	Road runs NE. & SW.	
80.00	Intersect N & S line at cor to secs.	
	14, 15, 22 & 23 bears which	
	West on a true line	
	between secs 15 & 22	
40.00	Set rock boulder 16 x 15 x 7 ins. 16 ins.	
	deep marked 40 on N side with mound	
	of stone for ¼ sec. cor.	
80.00	The cor to secs 15 & 16, 21 & 22	40.00
	in mid mostly level bottom	
	Soil 1st rate — No timber	
	Note Abandon line here.	

	From cor to secs 21, 22, 27
	& 28 2 ins.

R. 17 W. Salt Lake Meridian

Chains

South between Secs 27 & 28
Var. 16° E.

The line being impracticable in place
2 mds from the witness cor. 19 chs
N. & true cor. W. & E. offset line
20 chs. thence South 19 chs to hard
2 mark trachyte in place 3 x 2 x 1 for above
ground 3 notches S & E. I. W.C. with mound
of stone for witness cor to secs 21, 22,
27 & 28. Continue S. on the
line to 40 chs thence East
5 chs to

40.00 the true line at trachyte 15 x 10
x 4 in 10 in deep marked 1/4 cor W side,
with mound of stone for 1/4 sec cor
Note. Abandon line here.

Land broken ... 2 nd rate
No timber

Subdivision lines of s. 40 S. [illegible]

Chains		Chains
	West on true line between Secs 27 & 28 Var. 16° E.	47.00
2.00	Witness cor set in mound of stone	5-79.50
	South between Secs 27 & 28	
20.50	Santa Clara River N. 60° W.	60.00
31.00	Fence runs N.E. & S.W.	80.00
4.00	H Mound stone N. 5 chs	
35.50	Fence runs N.W. & S.E.	
37.00	Ditch runs S.W.	
40.00	Set sandstone 8 x 7 x 8 in Wm dug marked 40 on N side with mound of stone for 4 cor. cor	
45.50	Road runs NE & SW which is the N. end of Main Street in the town of Sunbrook runs S 89° W. & N 5° E. some 4 or 5 houses on either side of the street	3400
46.50	Ascend	

Range 17 W. Gila and Salt River Meridian

Chains	
47.00	Cañon runs S.E.
59.50	Top of hill from which Point of Rocks bears S. 38 W. about 20 chs. dist. Sorghum Mill at intersection of ditch 2 chs SW of the house
66.00	Road bears N.W. & S.E.
80.00	E. Cañon 20 x 12 x 7 in. 15 in. deep marked 4. E. & 2. S., with mound of stone for cor to secs 20, 21, 28, 29
	Land mostly part cultivated fields & orchards. Soil 1st rate. Balance hilly & rocky. Soil 2nd rate. No timber.

South between secs 28 & 29

Var. 16° E.

34.00	Ditch runs S.W., Gravel hills bears N.E. & S.W.

Subdivision lines of 1409 N.

Lines
39.50

Santa Clara River 50 chs wide runs SW.

46.00 One set bank of river SE (Mark Boulder 18 x 14 x 9 ins 13 ins deep marked 1/4 on N. side, with mound of stone for 1/4 cor.
Water Abundant Lines here.
Land mostly hilly Soil 2nd Rate
(No timber
April 14th 1877, T. C. Bailey

General Description

The surveyed lands in this Tp. embrace the settlements along the Santa Clara River and the bench land East of the River although there are some strong indications of mineral and

R. 7 W. Salt Lake Meridian

The "Lost Silver Lode" is said to be in the N. W. ¼ of Sec. 14 yet finding nothing definite I return all as agricultural

T. C. Bailey
U. S. Dep. Surv.

156

U. S. S

Salt L

The for

North

Townshi

Executed

Under

day of

Apr

examine

planatio

surveys

BOOK-A-152

57

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, June 6th 1877

The foregoing field notes of the survey of the West Boundary & Subdivisions *Township No.* 4 South *Range No.* 1 West *Executed by* Bailey & Burrill *Under* Joint- *contract of the* 4th *day of* September 1876, *in the month of* April 1877, *having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.*

Paul Kimball

Surveyor General for Utah.

BOOK-A-152

Township [illegible] **R.** [illegible]



BOOK-A-152

Township 41 South **R.** 6 West



BOOK-A-152

157

5th Examined by C. H. Cranwell C. C.

Field Notes
of the
Subdivisions of
Townships 1 South Range 1 West
Salt Lake Meridian
Utah Territory
as surveyed by
Bailey W Lassin
under joint contract Bailey & Burrill
No. 78 dated Sept 6th 1876

Survey commenced March 13th 1877

" Completed " " "

Subdivisions of Sec. 4, T. 6 S., R. 1 W.

Chains	
	Mar 13th 1877 by J. H. Brooks
	As the whole of this south
	boundary is prob. run thru-
	fare from the cor. to sec. 32 33
	on the North Boundary
	North bet. secs. 32 & 33
	Va. 15° 30' E.
3.00	Ascend. g. t. & stone
10.00	Top of last point of hill
	Descend.
15.00	Foot of grade
29.70	Paria River bottom wide runs S.E.
30.00	Road bears N. 5° W. & S. 5° E.
40.00	Set Sandstone 22 x 14 x 8 in. 15
	in. deep marked 1/4 on W.
	side raised mound of stone
	for 1/4 sec. cor. from which
	A Cottonwood 24 in. dia.
	bears N. 10° E. 80 lks. dist. blazed

Chains	
	Chai
77.	
80.	

Salt Lake Meridian

Chains

77.00 | 80.00

Fr S. B. T.

Thence along W. slope of Bluffs.

Gulch draws W.

Mark Sandstone in place 3x notches 1½ x 1 foot Cabow ground 4 on E8. 1 on S. side & mound of stone for Cor. Secs. 28. 29. 32 & 33 from which

A Cottonwood 20 ins. dia. bears N. 89° 30' W. 330 lks. dist. Marked S. 29. T. 4 S. R. 1 W. B. T.

Landing River bottom, Level Soil, Poplar, Timber a few Cottonwoods

---

It being impracticable to run E & the line west crossing the river bottom I run West on true line

Subdivision Sec. 5. T. 12 S. R. 1 W.

Chain Sec. Acres 299.32.

Var. 15° 30' E.

3.29 Foot of Bluff bears N & E.

9.50 Pacific Rim 30 lks. wide runs S.

18.36 Road bears N & E.

20.00 Wash drains S.

30.00 Foot of Bluff bears N & E.

40.00 Same cor. falling in Bluff is not set, therefore set a stone 20 lks. S. & Sandstone 20 × 14 × 3 ins. 16 ins. deep marked 5 m. S. 5 W. C. & raised a mound of stone for witness 5 acres, cor. from which A Cottonwood 10 ins. dia. bears S. 89. W. 66 lks. dist. marked 5 S. B. T.

Note: I abandon line here. Land mostly level, fair to Timber — as from Cottonwoods —

Chains

Township cor. S.E. 29. 32933
North 80.00 chs. 28929
West 15°. 30. E.
The line, in place being impracticable, Offset West 4.00 chs. Thence North on offset line 80.00 chs. to

40.00 Point 4.00 chs. West of Township cor. where I set Standstone 15×11×5 ins. 12 ins. deep marked, 1/4 on N. side & W.C. Raised mound of stone for witness 1/4 sec. cor.

Continue on offset line to 80.00 chs. thence East 4.00 chs. to

80.00 On true line Set Slate stone 18×8×3 ins. 12 ins. deep notched 1/4 on E. & 2 on S. edges raised mound of stone for cor. Sec. 20. 21. 28. 29 on N. slope of Gray Bluffs.

Subdivision Survey T. 4 N., R. 1 W.

Chains	Found iron pin and stone, Corner to	Links
	Sections 1, 2, 11 and 12, T. 4 N., R. 1 W.	

The lines run on this Survey impracticable therefrom Distances North Lat. acc. 20721 Va. 15° 30' E.

15.00	Points 18.00 chs. East of S. point of Sharp Rocky Ridge -	
25.00	Gap in ridge 10.00 chs. N.	
40.00	Set Sandstone 18x6x6 in. 12 in. deep marked S 4 on N. side & raised a mound. Pointers for S. 1/4 cor.	
43.00	Wash drains E. W.	
46.00	" " " " junction 5.00 chs. N.	6.5
58.50	Ridge trees N. 50 E. & S. 20 W.	
68.00	Wash drains N. W.	16.
71.00	Small Ridge trees E & W.	
75.80	Road in, 2 cottonwood, cañon trees N.E.	40.

Salt Lake Meridian

Chains	
80.00	Set White Sandstone 18"x4"x6" in 12" in. deep notched to E & W on S. edge & raised mound of earth from which pits each 24"x12"x12" in. for cor. Bears. 16 & 17. 20 & 21
	Land mostly prairie along line, in bottom land - Soil 1st rate
	No Timber - Coal in Ridge -
	The line east being impracticable I run
	North Lat. Dec. 16 & 17
	Var. 15° 30' E.
6.50	Cottonwood, Brush 18 ins. wide runs S. W.
16.00	Foot of White Sandstone Bluffs bears N. E. & S. W.
40.00	Line cor. falling in rocky bluffs

Specifications Part of Sec. 1. Pr.

Chainage not exact Theodolite 16.00
chs. I Set. Pickets & Standstone 24x
12x6 ins. 18 in. deep marked upon
Pickets W.W.C. Mainsprung & Monument
Monuments & witnesses pl. accd. on
sketch. I abandon line here -
Land S/F Sand, Soil, bottom
Soil, Bale Balance part, 2d
Rate. No Timber -

So Construct line 80.0
pl. accd. 16821
Sur. S. 30. E.
Peculiar, being impracticable
in place therefore from the
witness on 1600 chs. N. of sec. to
accd. 16.17.20821 I run East
on offset line 35.00 chs. to a
point 16.00 chs. N. 45.00 chs. West of

Salt Lake Meridian

Chains

40.00 The bear. cor. falling in Bluffs is not set, therefore at this point 30.00 chs. N. of bear. cor. I set a sandstone 18x10x4 in. 12 in. deep, notched 3 on E & S. edges & W. C. mixed & rammed & stone for witness cor. Bears. 16. 16. 21 22 —

Land broken & rocky on line in bottom land - Bank Bats -

Subdivision D. 41. L. 12. 1. 9.

Chains No Timbers

North bet. secs. 15 & 16
Va. 15° 30' E.

From witness cor. 30.00 chs. N. of
tree, cor. D offset W. 10.00 chs. 10.0
Thence N. on offset line 5.00
chs. to 16.3
80.00 Point 10.00 chs. West of tree cor. 18.3
where I set Sandstone 24x13x3 in 30.0
18 in. deep, notched 3 on E. & 4 on S. edges
VV.C. 32.8
Marked, mound & pit on for wit-
ness cor. Secs. 9. 10. 15 & 16. 40.0

Note: The pit & cor. falling in bluffs
is not set.

Land on line rocky & broken—
Bowl— Hill 3 Dale—
In bottom level, Hill 1 Dale
No Timber—

Salt Lake Meridian

Chains The line past, being impracticable Down
West on True Line
Bet. 20 & 30 N. 9 W. 16
Mn. 15° 30' E.

10.00 Witness cor. all found S. Ridge containing Coal, bears N.E. 75 W.

16.30 Wash drains N.W.

18.50 Saddle Rock, Ridge bears N.E. 75 W.

30.00 Road bears N.E. 75 W.

32.80 Cottonwood, Brush 4 links wide runs S.W.

40.00 Set Standstone 24 x 6 x 6 in. 18 in. deep marked 1/4 on N. side & raised mound. Stone for 1/4 sec. cor. at foot of White Ridge bears N.E. 75 W. from which A Cottonwood 8 in. dia. bears S. 88 E. 52 5 links dist. marked 1/4 S. B.T.

Subdivision Sec. 6, T. 1 S., R. 2 W.

Containing Sand and Gravel Bottom

Soil, Sandy. Surface

Note: Abandoned Pine Bear

North bet. secs. 7 & 18
Var. 15° 30' E.

The line in place being impracticable I offset East 10.00 chs. to wood bluffs, thence North on offset line & note the topography thereon.

13.60	Wash draws N. 75° W.
18.20	" " "
23.00	" " W.
26.00	" " S. W.
26.20	Bank bars N. E. & S. W.
40.00	Thence East 2.90 chs. to Point 7/10 chs. West of Point
40.00	Thence to where I mark a White

Salt Lake Meridian

Chains Standstone. Needle 150 feet high
1/4 S.W.C. on E. face raise a
mound of stone for witness
1/4 occ. cor. from which
A Pine 10 in. dia. bears N. 10. W.
65 lks. dist.
A Pine 8 in. dia. bears S. 10. W. 50
lks. dist. both trees marked
1/4 S.W.C. B.T.
These are the only pines in
the neighborhood —
Continue north on offset line
10.00 chs. W. of true line
45.50 Creek lks. under pines S.W.
46.20 Road bears N.E. & S.W.
54.80 Fence bears N. 70. W. & S. 70. E.
Across canon drains
60.00 Thos Smiths Ranch 12.00
chs. W. at mouth of Mud-

Subdivision T. 24 S. R. 1 W.

Barry Canon —

71.00 To point thence

East 10.00 chs. to

71.00 Pacific line, thence North

with said line to

80.00 Set standstone 16x12x10 in. 11

in. deep mounded with earth

from pits, each 24x12x12 in. for

cor. to secs. 3. 4. 9 & 10.

Land on line broken & rocky —

Soil 3rd rate —

In bottom land — Soil 1st rate —

No Timber —

As this line east will strike

the bluffs in less than 80.00 chs

I run

East on true line —

Salt Lake Meridian

Chains	
	Lat. Decr. 30.10
	Va. 15° 30' E.
5.00	Tmbr of Needle Ledge, bears N & S, breaks off 20 links N.
11.50	Foot of Boat Ledge, bears N & S. Sand bottom.
110.00	Timber falling in rocky bluffs is not set thereon at 11.50 chs. I mark Sandstone in place 4 x 2 x 1½ feet above ground ¼ W.C. on N. side I raise mound of stone for witness ¼ acorn.
Note:	I abandon line here — Sand in bottom, level — Soil 1st rate — No Timber —

As the line next will strike the bluffs in left I run 80.00 chs.

Subdivision Mon. S. M. T. R.

Chains | Bearings & Distances | Chains

Commence at cor. Secs. 4 & 9, Twp. 1 South Range 1 East on line between Secs. 4 & 9 Mon. No. 3 Bears N. 89° E. 40 links distant

Run S. 89° E. 80.00 chs. to Mon. No. 4 on S. B. of Sec. 4 & 9 Twp. 1 S. R. 1 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 5 on S. B. of Sec. 3 & 4 Twp. 1 S. R. 1 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 6 on S. B. of Sec. 3 & 2 Twp. 1 S. R. 1 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 7 on S. B. of Sec. 2 & 1 Twp. 1 S. R. 1 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 8 on S. B. of Sec. 1 Twp. 1 S. R. 1 E. M. and on W. B. of Sec. 6 Twp. 1 S. R. 2 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 9 on S. B. of Sec. 6 & 5 Twp. 1 S. R. 2 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 10 on S. B. of Sec. 5 & 4 Twp. 1 S. R. 2 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 11 on S. B. of Sec. 4 & 3 Twp. 1 S. R. 2 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 12 on S. B. of Sec. 3 & 2 Twp. 1 S. R. 2 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 13 on S. B. of Sec. 2 & 1 Twp. 1 S. R. 2 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 14 on S. B. of Sec. 1 Twp. 1 S. R. 2 E. M. and on W. B. of Sec. 6 Twp. 1 S. R. 3 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 15 on S. B. of Sec. 6 & 5 Twp. 1 S. R. 3 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 16 on S. B. of Sec. 5 & 4 Twp. 1 S. R. 3 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 17 on S. B. of Sec. 4 & 3 Twp. 1 S. R. 3 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 18 on S. B. of Sec. 3 & 2 Twp. 1 S. R. 3 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 19 on S. B. of Sec. 2 & 1 Twp. 1 S. R. 3 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 20 on S. B. of Sec. 1 Twp. 1 S. R. 3 E. M. and on W. B. of Sec. 6 Twp. 1 S. R. 4 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 21 on S. B. of Sec. 6 & 5 Twp. 1 S. R. 4 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 22 on S. B. of Sec. 5 & 4 Twp. 1 S. R. 4 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 23 on S. B. of Sec. 4 & 3 Twp. 1 S. R. 4 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 24 on S. B. of Sec. 3 & 2 Twp. 1 S. R. 4 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 25 on S. B. of Sec. 2 & 1 Twp. 1 S. R. 4 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 26 on S. B. of Sec. 1 Twp. 1 S. R. 4 E. M. and on W. B. of Sec. 6 Twp. 1 S. R. 5 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 27 on S. B. of Sec. 6 & 5 Twp. 1 S. R. 5 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 28 on S. B. of Sec. 5 & 4 Twp. 1 S. R. 5 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 29 on S. B. of Sec. 4 & 3 Twp. 1 S. R. 5 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 30 on S. B. of Sec. 3 & 2 Twp. 1 S. R. 5 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 31 on S. B. of Sec. 2 & 1 Twp. 1 S. R. 5 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 32 on S. B. of Sec. 1 Twp. 1 S. R. 5 E. M. and on W. B. of Sec. 6 Twp. 1 S. R. 6 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 33 on S. B. of Sec. 6 & 5 Twp. 1 S. R. 6 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 34 on S. B. of Sec. 5 & 4 Twp. 1 S. R. 6 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 35 on S. B. of Sec. 4 & 3 Twp. 1 S. R. 6 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 36 on S. B. of Sec. 3 & 2 Twp. 1 S. R. 6 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 37 on S. B. of Sec. 2 & 1 Twp. 1 S. R. 6 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 38 on S. B. of Sec. 1 Twp. 1 S. R. 6 E. M. and on W. B. of Sec. 6 Twp. 1 S. R. 7 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 39 on S. B. of Sec. 6 & 5 Twp. 1 S. R. 7 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 40 on S. B. of Sec. 5 & 4 Twp. 1 S. R. 7 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 41 on S. B. of Sec. 4 & 3 Twp. 1 S. R. 7 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 42 on S. B. of Sec. 3 & 2 Twp. 1 S. R. 7 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 43 on S. B. of Sec. 2 & 1 Twp. 1 S. R. 7 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 44 on S. B. of Sec. 1 Twp. 1 S. R. 7 E. M. and on W. B. of Sec. 6 Twp. 1 S. R. 8 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 45 on S. B. of Sec. 6 & 5 Twp. 1 S. R. 8 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 46 on S. B. of Sec. 5 & 4 Twp. 1 S. R. 8 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 47 on S. B. of Sec. 4 & 3 Twp. 1 S. R. 8 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 48 on S. B. of Sec. 3 & 2 Twp. 1 S. R. 8 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 49 on S. B. of Sec. 2 & 1 Twp. 1 S. R. 8 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 50 on S. B. of Sec. 1 Twp. 1 S. R. 8 E. M. and on W. B. of Sec. 6 Twp. 1 S. R. 9 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 51 on S. B. of Sec. 6 & 5 Twp. 1 S. R. 9 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 52 on S. B. of Sec. 5 & 4 Twp. 1 S. R. 9 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 53 on S. B. of Sec. 4 & 3 Twp. 1 S. R. 9 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 54 on S. B. of Sec. 3 & 2 Twp. 1 S. R. 9 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 55 on S. B. of Sec. 2 & 1 Twp. 1 S. R. 9 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 56 on S. B. of Sec. 1 Twp. 1 S. R. 9 E. M. and on W. B. of Sec. 6 Twp. 1 S. R. 10 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 57 on S. B. of Sec. 6 & 5 Twp. 1 S. R. 10 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 58 on S. B. of Sec. 5 & 4 Twp. 1 S. R. 10 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 59 on S. B. of Sec. 4 & 3 Twp. 1 S. R. 10 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 60 on S. B. of Sec. 3 & 2 Twp. 1 S. R. 10 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 61 on S. B. of Sec. 2 & 1 Twp. 1 S. R. 10 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 62 on S. B. of Sec. 1 Twp. 1 S. R. 10 E. M. and on W. B. of Sec. 6 Twp. 1 S. R. 11 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 63 on S. B. of Sec. 6 & 5 Twp. 1 S. R. 11 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 64 on S. B. of Sec. 5 & 4 Twp. 1 S. R. 11 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 65 on S. B. of Sec. 4 & 3 Twp. 1 S. R. 11 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 66 on S. B. of Sec. 3 & 2 Twp. 1 S. R. 11 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 67 on S. B. of Sec. 2 & 1 Twp. 1 S. R. 11 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 68 on S. B. of Sec. 1 Twp. 1 S. R. 11 E. M. and on W. B. of Sec. 6 Twp. 1 S. R. 12 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 69 on S. B. of Sec. 6 & 5 Twp. 1 S. R. 12 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 70 on S. B. of Sec. 5 & 4 Twp. 1 S. R. 12 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 71 on S. B. of Sec. 4 & 3 Twp. 1 S. R. 12 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 72 on S. B. of Sec. 3 & 2 Twp. 1 S. R. 12 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 73 on S. B. of Sec. 2 & 1 Twp. 1 S. R. 12 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 74 on S. B. of Sec. 1 Twp. 1 S. R. 12 E. M. and on W. B. of Sec. 6 Twp. 1 S. R. 13 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 75 on S. B. of Sec. 6 & 5 Twp. 1 S. R. 13 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 76 on S. B. of Sec. 5 & 4 Twp. 1 S. R. 13 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 77 on S. B. of Sec. 4 & 3 Twp. 1 S. R. 13 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 78 on S. B. of Sec. 3 & 2 Twp. 1 S. R. 13 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 79 on S. B. of Sec. 2 & 1 Twp. 1 S. R. 13 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 80 on S. B. of Sec. 1 Twp. 1 S. R. 13 E. M. and on W. B. of Sec. 6 Twp. 1 S. R. 14 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 81 on S. B. of Sec. 6 & 5 Twp. 1 S. R. 14 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 82 on S. B. of Sec. 5 & 4 Twp. 1 S. R. 14 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 83 on S. B. of Sec. 4 & 3 Twp. 1 S. R. 14 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 84 on S. B. of Sec. 3 & 2 Twp. 1 S. R. 14 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 85 on S. B. of Sec. 2 & 1 Twp. 1 S. R. 14 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 86 on S. B. of Sec. 1 Twp. 1 S. R. 14 E. M. and on W. B. of Sec. 6 Twp. 1 S. R. 15 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 87 on S. B. of Sec. 6 & 5 Twp. 1 S. R. 15 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 88 on S. B. of Sec. 5 & 4 Twp. 1 S. R. 15 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 89 on S. B. of Sec. 4 & 3 Twp. 1 S. R. 15 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 90 on S. B. of Sec. 3 & 2 Twp. 1 S. R. 15 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 91 on S. B. of Sec. 2 & 1 Twp. 1 S. R. 15 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 92 on S. B. of Sec. 1 Twp. 1 S. R. 15 E. M. and on W. B. of Sec. 6 Twp. 1 S. R. 16 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 93 on S. B. of Sec. 6 & 5 Twp. 1 S. R. 16 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 94 on S. B. of Sec. 5 & 4 Twp. 1 S. R. 16 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 95 on S. B. of Sec. 4 & 3 Twp. 1 S. R. 16 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 96 on S. B. of Sec. 3 & 2 Twp. 1 S. R. 16 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 97 on S. B. of Sec. 2 & 1 Twp. 1 S. R. 16 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 98 on S. B. of Sec. 1 Twp. 1 S. R. 16 E. M. and on W. B. of Sec. 6 Twp. 1 S. R. 17 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 99 on S. B. of Sec. 6 & 5 Twp. 1 S. R. 17 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 100 on S. B. of Sec. 5 & 4 Twp. 1 S. R. 17 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 101 on S. B. of Sec. 4 & 3 Twp. 1 S. R. 17 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 102 on S. B. of Sec. 3 & 2 Twp. 1 S. R. 17 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 103 on S. B. of Sec. 2 & 1 Twp. 1 S. R. 17 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 104 on S. B. of Sec. 1 Twp. 1 S. R. 17 E. M. and on W. B. of Sec. 6 Twp. 1 S. R. 18 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 105 on S. B. of Sec. 6 & 5 Twp. 1 S. R. 18 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 106 on S. B. of Sec. 5 & 4 Twp. 1 S. R. 18 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 107 on S. B. of Sec. 4 & 3 Twp. 1 S. R. 18 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 108 on S. B. of Sec. 3 & 2 Twp. 1 S. R. 18 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 109 on S. B. of Sec. 2 & 1 Twp. 1 S. R. 18 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 110 on S. B. of Sec. 1 Twp. 1 S. R. 18 E. M. and on W. B. of Sec. 6 Twp. 1 S. R. 19 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 111 on S. B. of Sec. 6 & 5 Twp. 1 S. R. 19 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 112 on S. B. of Sec. 5 & 4 Twp. 1 S. R. 19 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 113 on S. B. of Sec. 4 & 3 Twp. 1 S. R. 19 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 114 on S. B. of Sec. 3 & 2 Twp. 1 S. R. 19 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 115 on S. B. of Sec. 2 & 1 Twp. 1 S. R. 19 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 116 on S. B. of Sec. 1 Twp. 1 S. R. 19 E. M. and on W. B. of Sec. 6 Twp. 1 S. R. 20 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 117 on S. B. of Sec. 6 & 5 Twp. 1 S. R. 20 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 118 on S. B. of Sec. 5 & 4 Twp. 1 S. R. 20 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 119 on S. B. of Sec. 4 & 3 Twp. 1 S. R. 20 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 120 on S. B. of Sec. 3 & 2 Twp. 1 S. R. 20 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 121 on S. B. of Sec. 2 & 1 Twp. 1 S. R. 20 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 122 on S. B. of Sec. 1 Twp. 1 S. R. 20 E. M. and on W. B. of Sec. 6 Twp. 1 S. R. 21 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 123 on S. B. of Sec. 6 & 5 Twp. 1 S. R. 21 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 124 on S. B. of Sec. 5 & 4 Twp. 1 S. R. 21 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 125 on S. B. of Sec. 4 & 3 Twp. 1 S. R. 21 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 126 on S. B. of Sec. 3 & 2 Twp. 1 S. R. 21 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 127 on S. B. of Sec. 2 & 1 Twp. 1 S. R. 21 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 128 on S. B. of Sec. 1 Twp. 1 S. R. 21 E. M. and on W. B. of Sec. 6 Twp. 1 S. R. 22 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 129 on S. B. of Sec. 6 & 5 Twp. 1 S. R. 22 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 130 on S. B. of Sec. 5 & 4 Twp. 1 S. R. 22 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 131 on S. B. of Sec. 4 & 3 Twp. 1 S. R. 22 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 132 on S. B. of Sec. 3 & 2 Twp. 1 S. R. 22 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 133 on S. B. of Sec. 2 & 1 Twp. 1 S. R. 22 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 134 on S. B. of Sec. 1 Twp. 1 S. R. 22 E. M. and on W. B. of Sec. 6 Twp. 1 S. R. 23 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 135 on S. B. of Sec. 6 & 5 Twp. 1 S. R. 23 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 136 on S. B. of Sec. 5 & 4 Twp. 1 S. R. 23 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 137 on S. B. of Sec. 4 & 3 Twp. 1 S. R. 23 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 138 on S. B. of Sec. 3 & 2 Twp. 1 S. R. 23 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 139 on S. B. of Sec. 2 & 1 Twp. 1 S. R. 23 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 140 on S. B. of Sec. 1 Twp. 1 S. R. 23 E. M. and on W. B. of Sec. 6 Twp. 1 S. R. 24 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 141 on S. B. of Sec. 6 & 5 Twp. 1 S. R. 24 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 142 on S. B. of Sec. 5 & 4 Twp. 1 S. R. 24 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 143 on S. B. of Sec. 4 & 3 Twp. 1 S. R. 24 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 144 on S. B. of Sec. 3 & 2 Twp. 1 S. R. 24 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 145 on S. B. of Sec. 2 & 1 Twp. 1 S. R. 24 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 146 on S. B. of Sec. 1 Twp. 1 S. R. 24 E. M. and on W. B. of Sec. 6 Twp. 1 S. R. 25 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 147 on S. B. of Sec. 6 & 5 Twp. 1 S. R. 25 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 148 on S. B. of Sec. 5 & 4 Twp. 1 S. R. 25 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 149 on S. B. of Sec. 4 & 3 Twp. 1 S. R. 25 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 150 on S. B. of Sec. 3 & 2 Twp. 1 S. R. 25 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 151 on S. B. of Sec. 2 & 1 Twp. 1 S. R. 25 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 152 on S. B. of Sec. 1 Twp. 1 S. R. 25 E. M. and on W. B. of Sec. 6 Twp. 1 S. R. 26 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 153 on S. B. of Sec. 6 & 5 Twp. 1 S. R. 26 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 154 on S. B. of Sec. 5 & 4 Twp. 1 S. R. 26 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 155 on S. B. of Sec. 4 & 3 Twp. 1 S. R. 26 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 156 on S. B. of Sec. 3 & 2 Twp. 1 S. R. 26 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 157 on S. B. of Sec. 2 & 1 Twp. 1 S. R. 26 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 158 on S. B. of Sec. 1 Twp. 1 S. R. 26 E. M. and on W. B. of Sec. 6 Twp. 1 S. R. 27 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 159 on S. B. of Sec. 6 & 5 Twp. 1 S. R. 27 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 160 on S. B. of Sec. 5 & 4 Twp. 1 S. R. 27 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 161 on S. B. of Sec. 4 & 3 Twp. 1 S. R. 27 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 162 on S. B. of Sec. 3 & 2 Twp. 1 S. R. 27 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 163 on S. B. of Sec. 2 & 1 Twp. 1 S. R. 27 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 164 on S. B. of Sec. 1 Twp. 1 S. R. 27 E. M. and on W. B. of Sec. 6 Twp. 1 S. R. 28 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 165 on S. B. of Sec. 6 & 5 Twp. 1 S. R. 28 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 166 on S. B. of Sec. 5 & 4 Twp. 1 S. R. 28 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 167 on S. B. of Sec. 4 & 3 Twp. 1 S. R. 28 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 168 on S. B. of Sec. 3 & 2 Twp. 1 S. R. 28 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 169 on S. B. of Sec. 2 & 1 Twp. 1 S. R. 28 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 170 on S. B. of Sec. 1 Twp. 1 S. R. 28 E. M. and on W. B. of Sec. 6 Twp. 1 S. R. 29 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 171 on S. B. of Sec. 6 & 5 Twp. 1 S. R. 29 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 172 on S. B. of Sec. 5 & 4 Twp. 1 S. R. 29 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 173 on S. B. of Sec. 4 & 3 Twp. 1 S. R. 29 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 174 on S. B. of Sec. 3 & 2 Twp. 1 S. R. 29 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 175 on S. B. of Sec. 2 & 1 Twp. 1 S. R. 29 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 176 on S. B. of Sec. 1 Twp. 1 S. R. 29 E. M. and on W. B. of Sec. 6 Twp. 1 S. R. 30 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 177 on S. B. of Sec. 6 & 5 Twp. 1 S. R. 30 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 178 on S. B. of Sec. 5 & 4 Twp. 1 S. R. 30 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 179 on S. B. of Sec. 4 & 3 Twp. 1 S. R. 30 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 180 on S. B. of Sec. 3 & 2 Twp. 1 S. R. 30 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 181 on S. B. of Sec. 2 & 1 Twp. 1 S. R. 30 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 182 on S. B. of Sec. 1 Twp. 1 S. R. 30 E. M. and on W. B. of Sec. 6 Twp. 1 S. R. 31 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 183 on S. B. of Sec. 6 & 5 Twp. 1 S. R. 31 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 184 on S. B. of Sec. 5 & 4 Twp. 1 S. R. 31 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 185 on S. B. of Sec. 4 & 3 Twp. 1 S. R. 31 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 186 on S. B. of Sec. 3 & 2 Twp. 1 S. R. 31 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 187 on S. B. of Sec. 2 & 1 Twp. 1 S. R. 31 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 188 on S. B. of Sec. 1 Twp. 1 S. R. 31 E. M. and on W. B. of Sec. 6 Twp. 1 S. R. 32 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 189 on S. B. of Sec. 6 & 5 Twp. 1 S. R. 32 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 190 on S. B. of Sec. 5 & 4 Twp. 1 S. R. 32 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 191 on S. B. of Sec. 4 & 3 Twp. 1 S. R. 32 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 192 on S. B. of Sec. 3 & 2 Twp. 1 S. R. 32 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 193 on S. B. of Sec. 2 & 1 Twp. 1 S. R. 32 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 194 on S. B. of Sec. 1 Twp. 1 S. R. 32 E. M. and on W. B. of Sec. 6 Twp. 1 S. R. 33 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 195 on S. B. of Sec. 6 & 5 Twp. 1 S. R. 33 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 196 on S. B. of Sec. 5 & 4 Twp. 1 S. R. 33 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 197 on S. B. of Sec. 4 & 3 Twp. 1 S. R. 33 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 198 on S. B. of Sec. 3 & 2 Twp. 1 S. R. 33 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 199 on S. B. of Sec. 2 & 1 Twp. 1 S. R. 33 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 200 on S. B. of Sec. 1 Twp. 1 S. R. 33 E. M. and on W. B. of Sec. 6 Twp. 1 S. R. 34 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 201 on S. B. of Sec. 6 & 5 Twp. 1 S. R. 34 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 202 on S. B. of Sec. 5 & 4 Twp. 1 S. R. 34 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 203 on S. B. of Sec. 4 & 3 Twp. 1 S. R. 34 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 204 on S. B. of Sec. 3 & 2 Twp. 1 S. R. 34 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 205 on S. B. of Sec. 2 & 1 Twp. 1 S. R. 34 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 206 on S. B. of Sec. 1 Twp. 1 S. R. 34 E. M. and on W. B. of Sec. 6 Twp. 1 S. R. 35 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 207 on S. B. of Sec. 6 & 5 Twp. 1 S. R. 35 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 208 on S. B. of Sec. 5 & 4 Twp. 1 S. R. 35 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 209 on S. B. of Sec. 4 & 3 Twp. 1 S. R. 35 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 210 on S. B. of Sec. 3 & 2 Twp. 1 S. R. 35 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 211 on S. B. of Sec. 2 & 1 Twp. 1 S. R. 35 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 212 on S. B. of Sec. 1 Twp. 1 S. R. 35 E. M. and on W. B. of Sec. 6 Twp. 1 S. R. 36 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 213 on S. B. of Sec. 6 & 5 Twp. 1 S. R. 36 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 214 on S. B. of Sec. 5 & 4 Twp. 1 S. R. 36 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 215 on S. B. of Sec. 4 & 3 Twp. 1 S. R. 36 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 216 on S. B. of Sec. 3 & 2 Twp. 1 S. R. 36 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 217 on S. B. of Sec. 2 & 1 Twp. 1 S. R. 36 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 218 on S. B. of Sec. 1 Twp. 1 S. R. 36 E. M. and on W. B. of Sec. 6 Twp. 1 S. R. 37 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 219 on S. B. of Sec. 6 & 5 Twp. 1 S. R. 37 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 220 on S. B. of Sec. 5 & 4 Twp. 1 S. R. 37 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 221 on S. B. of Sec. 4 & 3 Twp. 1 S. R. 37 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 222 on S. B. of Sec. 3 & 2 Twp. 1 S. R. 37 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 223 on S. B. of Sec. 2 & 1 Twp. 1 S. R. 37 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 224 on S. B. of Sec. 1 Twp. 1 S. R. 37 E. M. and on W. B. of Sec. 6 Twp. 1 S. R. 38 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 225 on S. B. of Sec. 6 & 5 Twp. 1 S. R. 38 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 226 on S. B. of Sec. 5 & 4 Twp. 1 S. R. 38 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 227 on S. B. of Sec. 4 & 3 Twp. 1 S. R. 38 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 228 on S. B. of Sec. 3 & 2 Twp. 1 S. R. 38 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 229 on S. B. of Sec. 2 & 1 Twp. 1 S. R. 38 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 230 on S. B. of Sec. 1 Twp. 1 S. R. 38 E. M. and on W. B. of Sec. 6 Twp. 1 S. R. 39 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 231 on S. B. of Sec. 6 & 5 Twp. 1 S. R. 39 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 232 on S. B. of Sec. 5 & 4 Twp. 1 S. R. 39 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 233 on S. B. of Sec. 4 & 3 Twp. 1 S. R. 39 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 234 on S. B. of Sec. 3 & 2 Twp. 1 S. R. 39 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 235 on S. B. of Sec. 2 & 1 Twp. 1 S. R. 39 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 236 on S. B. of Sec. 1 Twp. 1 S. R. 39 E. M. and on W. B. of Sec. 6 Twp. 1 S. R. 40 E. M.

Run S. 89° E. 80.00 chs. to Mon. No. 237 on S. B. of Sec. 6 & 5 Twp. 1 S. R. 40 E. M.

Run S. 89° E. 80.00 chs. to Mon.

Ref. to Lake Meridian

Drains From the corner S.E. cor. S.4. 9810
North 66.00 n. 3814
Va. 15° 30. E.
The line, being impracticable
in place. Thence
N. 16° E. due (s) the topography
thereon.

6.50	Wash drains N.
18.00	" " "
25.50	" " S.N.
40.50	" " "
41.61	To a point. Thence

West 9.00 chs. to a point 2.47 chs.
East of
40.00 Thence, where set a sand-
stone 15x10x5 in. 10 in. deep marked
1/4 on N. side W.V.C. Raised mound
of stone for witness 1/4 cor. bears from
which

Subdivision of Sec. 18, T. 22 N.

Chains	A Cottonwood 12 ins. dia. brs N. 20. W. C. N. 76 lks. dist. marked, ¼ S. B. T. Portique N. 16° E. on former line	Lks
59.00	Wash drains N.	
1.50	" " "	
3.22	To a point on 8th Standard Parallel South 23.94 chs. East of Starting point. Thence N. 0 15.00 chs. to a point 8.94 chs. West of	
50.00	True closing cor. falling in bluffs is not set, therefore at the point 8.94 chs. East of true cor. I set Sandstone 30 x 16 x 5 ins. 20 ins. deep, notched 6 on S. 3 on E. & N. adze'd W. C. I raised a mound of stone for witness closing cor. 15 secs. 38 ½ from which A Pine 14 ins. dia. brs N. 70. E. 80 lks dist. marked S. 34. 7.40. S. R. 1. B. W.	8.9 13. 23. 25. 27. 40.

Mt. of 6th Principal Meridian

20.	4chains	C. B.T.
		Sand on line, broken rocky
		Ant 2 Pals — Intersections
		Land Ant 5 Pals —
		No Timber —
		Mar 13th 1877 J. W. Berrill
		Mar 13th 1877 T. C. Bailey
		East on true line
		on 8th Standard Parallel North
		on S. side sec 34
		Va. 15° 30' E.
16	8.94	Iron witness cor.
S.	13.00	Brick & ks. wide runs S.
	23.00	Ash in foot of Saddle Ledge
	25.00	Ash drains N.N.E. 5 lks thence N.
	27.50	Foot of Coal Ridge bears N.E. & S.W.
		Leave Bottom
	40.00	Timber falling in bluffs to W.

Subdivisions T.14 S. R.1. W.

Chains

Note:

Chain

1.50

6.50

20.00

21.00

33.00

40.00

50.00

80.00

Set Thereon at 2.50

Set Stone 18x10x8 in. 10 in. deep marked from N. side 1 W.C. Raised mound of stone for witness trees. -

I abandon line here - This mile should be returned in a separate book but I have to here as I can't do desired & formed much easier than if returned any other way - Land in the bottom Level Soil Rate - No Timber.

From the cor. Bears 20.20.25 W 29 Links

West on true line Bears 20 W 29

Salt Lake Meridian

Chains	Tp. 15 S. R. 30 E.
	Descend.
1.50	Foot of Bluffs, enter bottom, bears N & S.
6.50	Paria River 50 lks. wide runs S.
20.70	" " " " " " " N. E.
21.50	Road bears N & S.
33.50	Paria River 50 lks. wide runs S.
40.00	Set Sandstone 16 x 10 x 5 in. 11 in. deep, marked ⅄ on N. side & raised mound of stone for ⅄ reed, cor. from which A Cottonwood 36 in. dia. bears S. 75 E. 120 lks. dist. marked ⅄ S. B. T.
50.00	Foot of Bluffs on N. side of Bottom, bears N. E & S. N.
80.00	Intersection falling into bluffs is not set, therefore at 50.00 chs.

151

Subdivision Twp 1. S. R. 1. W.

Chains	
	N.E. Planted Stone, 18 x 8 x 8 ins, 12 ins. deep, marked Scribed Iron E. W.S. edges. W.C. Raised mound of stone for cor. to secs. 19. 20. 29 & 30
	Land mostly level, bottom Soil, Sandy.
	Timber - a few Cottonwood.

North pt. secs. 19 & 20
Ma. 15°. 30. E.
Bee Line is in place Mining impracticable therefore pursued the meanders cor. 30.00 chs. east of this true cor. Run N. 15°. E. noting the topography thereon. -

35.00	Road, bears N-W.
39.50	Parias River 50 lks. wide runs S.E.

Chains

Salt Lake Meridian

Chains	40.00	Point on left bank of Rain & 12 lks N. of the Discovery Monument of the "Blue Ledge Mine" claimed & located by J.P. McMangrum. 1500 feet by 300 feet, north of the discovery monument the Witness bears N. 10 E. is about 20 feet distant 65 certain cedar — From this point J.P. McMangrum's Cabin bears S. 50 E. about 30.00 chs. dist. South point of Bluff to Sierra Bottom and Paria canons bears S.E. 150 lks dist. Thence N. 47° 30' W.
	24.75	chs — Thence N. 24. W.
	23.00	" Thence N. 59. W.
	6.08	" Thence West

Subdivisions T. 4 S. R. 1 W.

Chains	
	600 chs to
80.00	On true line mark Sandstone in place 4×3×2½ feet above ground 50 links and 730 links S. side of road mound of stone for corner 17.18.19.20
	Sand 5/8 in bottom. Loam Soil 1st Rate — 3/8 in the "Narrows" Soil Sandy 2nd Rate No Timber —
	East on random lines Set. post, 1720
	West 15.30 S.
2.00	Rain River 50 lks wide runs S.
3.00	Road bears N & S.
7.50	East side of "Narrows" 4 foot of massive fine Sandstone

Salt Lake Meridian

Chains	
	Bluffs bears N. W. & S. E. Mark N. face of Sandstone, Ledge 1/4 W.C. & raised mound of stone for witness 1/4 sec. cor.
	I now return to a point 2.12 ch. South of the "Blue Ledge Discovery Monument which point lying N 3.19 chs. & W 32 ~~65~~ 17 chs. E. of the cor. from which I started.
	Thence East on offset line ~~29.82~~ 30.38 chs. Thence North 43.19 chs. to
69.50	On true line, Thence East on true line 10.50 chs. to
80.00	The cor. to secs. 16. 17. 20 & 21 from which Mist on true line bears N.E. sec. 17 & 20
10.50	At foot of White Bluffs

185

Subdivision S.W. S. W. S. W.

Chains	Bear. N.E. D.S. W. on W. side of Cottonwood Brush & Hackberries S.W. where I set Standstone 15x10x4 in. 10 in. deep marked ¼ on N. side I W.C. & raised mound of stone for witness ¼ sec. cor.
40.00	Thence sec. cor. falling in bluffs in rock -
72.50	Witness cor. at grove, East
80.00	The cor. to sec. 17, 18, 19, 20 Land middle part rock, bluffs - Balance bottom land fine, Soil Sandy No Timber -

---

Meander line Missouri River

Va. 15° 30' E.

\+ I offset North 7.50 chs.

BOOK-A-152

Salt Lake Meridian

Chains	
	Thence N. 45° W. 31.83 chs. Thence
	West on offset line 5,50 chs.
	Thence South 30.00 chs. to
80.00	Intersect West boundary of
	Township 8 North Range 8
	West from which
	East on true line
	Sec. Cor. 18 & 19
	North on offset line 30.00 chs
	Thence East 5,50 chs. Thence
	S. 45° E. 31.83 chs. to
7.50	On true line Thence East to
80.00	The cor. Secs. 17. 18. 19 & 20
	The 1/4 sec. cor. falling in this
	Bluffs is not set -
	Land, rocky bluffs
	Soil Rate
	No Timber -

Subdivision T. 4 S. R. 1 W.

Chains	North bet. secs. 1 & 12
	Var. 15° 30' E.
4.00	Road bears N. W. & S. E.
7.50	On left bank of Paria River 50 lks. wide runs S. E. & foot of bluffs bears N. W & S. E. Mark a sandstone in place 15 x 10 x 3 feet in ground 1/4 W.C. Raised mound & pits for witness & dug. Thence N. 45° W. 31.83 chs. Thence North on offset line 50.00 chs. Thence East 1.04 chs. to a point on foot of Bluff facing west & bearing N. W. & S. E. & 2.46 chs. West of
50.00	The true cor. which falling in rocky bluff is not set. Therefore at the above

Salt Lake Meridian

Stone. Found Stone, mound of stones for witness, cor. to sec. 7. S. 1918

Note: The fd. sec. cor. falling in Bluffs is not set. Sandstone & broken Soil, 3 Pts. No Pimbs.

The lines East & North are impracticable, therefore Drum Post on random lines Ast. Dec. 7 & 8

Va. 15° 30' E.

21.46 The witness cor. Record- 40.00 Corner falling on steep hill side, could not be permanently established

Subdivisions for S. ½ 34 29 N

Chains	Thence from A.	Chains
45.50	Post. of a Bluff set. Quartz-	69.00
	ite rock. 3 x 8 x 6 in. 15 in. high	
	marked ¼ sec. 34 29 N. C. &	80.00
	raised mound of stone for	
	witness, bears. &c.	
50.55	Point from which the N.E.	
	cor. of the North & Block on E.	
	side of Main St in the	34.45
	Town of Paris bears South	
	6.84 chs. dist. The blocks	40.00
	are about 5.00 chs square	
	The streets 1.00 ch. wide	
	The town contains about	58.54
	50 inhabitants.	
51.55	Ditch runs S.E.	80.00
52.50	Road bears N.W. & S.E.	
53.00	Corn burr Mill 50 lks. S.	
54.00	Enter cultivated field	

Salt Lake Meridian

6chains	Brs W. N. W. S. Co. (no fence)
69.00	Pasture River 50 lks. wide runs S. W.
80.00	Intersect west boundary of Township at the cor. Secs. 7 & 18 from which Boston Triangle Mt. bears, 1918
34.45	The W. Meas. cor. all going west.
40.00	The ¼ sec. cor. falling in the steep hill side is not set.
58.54	The witness cor. set going S. bears W. 1918
80.00	The cor. joint to Secs. 7. 8. 17. 18 Land W½ part level Soil 1st Rate - Balance rocky bluffs, Soil 3rd Rate

140/2
A

Subdivision T. 41 S. R. 7 E. M.

Chains N. Timber -
* Sup next page -
Note: On account of heavy
Bluffs & Inundation this
fractional township
Jan 13th 1877 T. C. Bailey

General Description
The lands in the surveyed
portion of this township
are bounded on the Southern
along the Sevier River
& Cottonwood Creek & the
Town of Paris in section
18. & the Settlement of Jas.
M. Mangrum in sec. 20
There is some Alum
in the foot hills around
the Town on either side

of the matter.

I return the following as Coal Land.

The E½ of S.W.¼ Sec. 33.
" " " N.W. " " 21.
" S.E.¼ & E½ of N.E.¼ Sec 16.
" N.W.¼ of Sec. 10.
The E½ of S.W.¼ Sec. 3.

The balance are agricultural lands

T. C. Bailey
U. S. Dep. Surveyor

---

* East on true line
bet. secs 6 & 7
Va 15° 30' E.
From the ¼ sec. cor. bet secs 6 & 7
on N. Boundary I offset east 20.
chs thence N. 40 chs. to point on

Subdivisions T. 41 S. R. 1 W.

2 chains	true line set Sandstone 16 x 10 x 6 in. 11 in. deep marked / notch on N. & S. edges & raised mound of stone W. C. / for witness cor. to sec 1. 6. 7 & 12
	Thence East on true line to
40.00	set Sandstone 18 x 12 x 6 in 12 in deep marked 1/4 on N. side raised mound of stone for 1/4 sec. cor.

BOOK-A-152

193.

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, June 21st 1877

The foregoing field notes of the survey of the Subdivisions of

Township No. 41 S. Range No. 1 West

Executed by Bailey & Russell

Under Joint contract of the 4th

day of Sept 1876, in the month of

March 1877, having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

Nathan Kimball

Surveyor General for Utah.

BOOK-A-152

6d Examined by C. H. Cramwell. C. C.

Field Notes
of the Survey
of the
East & West
Boundary
of Township 4 South Range 2 West
Salt Lake Meridian
Utah Territory
as surveyed by
J. C. Bailey
under Joint Contract Bailey & Burnett
No. 78 — dated Sept 4th 1876

Survey commenced Nov. 7th 1877
" completed " 9th "

57

East Boundary T. 44 N. R. 5 W.

Chains	Viands ~~&~~ Bldg by J. C. Bailey	Cha
	Same Sec. Co. T. 45 N. R. 5 W.	40.0
	1933 N. Span	
	North on range lines	
	Ret. Dec. 31 1936	80.
	Var. 15° 30' E.	
	Mon. about 20 chs N. of bluff	
110.00	Set Standstone 15x10x4 ins 16 ins deep marked 1/4 on N. side	
	raised mound of earth from 4 pits each 2.6 x 1.2 x 1 ft for 1/4 sec. cor.	
80.00	Set Standstone 18x10x4 ins 12 ins deep notched 1 on S. 8 on E. edge	
	raised mound of stones for cor.	
	Dec. Co. 30. 8 1936	40.0
	Frank M. Hoffman Pioneer Station	
	No Timber	
		40.0

North bet. Secs. 29 & 30

Salt Lake Meridian

Chains	
	Va. 15° 30' E.
40.00	Pet Sandstone 18×10×4 ins 12 ins deep marked 1/4 on W. side & raised mound of stone for 1/4 sec cor
80.00	Pet Sandstone 18×11×3 ins 12 ins deep notched 2 on S. & on W. edges raised mound of stone for cor to secs 13 24 19 & 18
	Land W. slope - Soil & Rock - No Timber

North bet. secs 19 & 24
Va. 15° 30' E.
Along foot of Bluffs
40.00 Pet Sandstone 16×10×3 ins 11 ins deep marked 1/4 on W. side & raised mound of stone for 1/4 sec cor.
80.00 Pet Sandstone 18×10×3 ins 12 ins deep notched 3 on W. & S. edges & raised

100

East Boundary T. 41 S. R. 2 W.

Chains	
	mound of stone for cor. to sec.
	13. 18. 19 & 24.
	Land, broken rocky.
	Soil, Sage &c. No Timber.

North bet. secs. 13 & 18
Va. 15° 30' E.

2.00	Wash drains E.
2.70	Road bears S.W.
5.00	Wide Wash drains E.
20.00	Wash " "
28.50	Deep Gulch drains E.
40.00	Set Sandstone 28 x 12 x 7 ins. 21 ins.
	descended from N. side &
	raised mound of stone for 1/4
	sec. cor. at foot of hills on N.
	side of Gulch Winds N. W.
	about 40 chs. dist. Thence
	along broken Basin hills

M. Salt Lake Meridian.

	Chains	sloping E.
	80.00	Set Pt. in mound of stone 1.4 x 3 ins. x 12 ins. deep, notched, 2 on N. side, on N. edge, raised mound of stone for cor. Secs. 7, 12, 13 & 18. from which Aspen 4 ins. dia. bears N. 15 E. 100 links dist., marked S. 7. T. 41. S. R. 1. W. B. T. — Aspen 7 ins. dia. bears N. 65 W. 112 links dist. marked S. 12. T. 41. S. R. 2. W. B. T. — Land broken, Alum Gulch Ords. & Dale — No Timber. —
		North Vt. Secs. 7 & 12 Var. 15° 30' E.
	9.00	Pair Aspen 5 ins. dia. runs S. E.

East Boundary, T. 41 S. R. 2 W.

Chains	
10.00	Stone Mon., S.E. S. ps. thence East across the valley - enters field
14.00	Cross Ditch 50 lks wide pass S.W.
15.50	" " " " " " " S.E.
35.00	Ditch cross S.E. Road on N. side of ditch, Cane field.
40.00	P.S. Sandstone 16x14x10 ins 11 ins above mound of stone for 1/4 sec. cor., from which A Cottonwood 10 in. dia. bears S. 20 W. 55 lks. dist. A Cottonwood 14 in dia bears S. 7 W. 176 lks. dist., both trees marked 1/4 S. B. I.
42.00	Foot of Bluff bears N. 77 E.
80.00	The true cor. falling in Bluff is not set thereon at 12.00 chs. set Sandstone

Salt Lake Meridian

Claim, 8 x 6 x 3 ins. 2 in. deep, notched
3 on S. W. side to edge, D. W. C. mound of stone for witness
cor. to sec. 5, 16. R. 12 E. —
Land S. & rocky, level —
cultivated fields —
Soil, Sandy —
No Timber —
No Water Nearby
Soil Sandy —
No Timber —

Note: I abandon this here —
May 7th 1877 T. Carl Bailey
U. S. Dep Surveyor

Mile 20 Corners of T. 41 S. R. 2 W.
S. L. M.

From the established cor
to Townships 41 & 42 S. Range
2 & 3 W. 2 miles
North astron dec. 31 ½ 30'
Var. 15° 30' E

4.00 Post 4 rod blazed bear S & W
Set sandstone 16 x 10 x 7 in. 10 in
deep marked 1/4 on W. side, with
mounds of stone for 1/4 sec cor.
Note: Abandons line here
Land level
Soil 1st rate
Timber Cedars.
March 4th 1874.

T. C. Bailey
U. S. Dep. Surveyor

For general description & approval see end of subdivision notes of this township.

BOOK-A-152 7 205

Field Notes

of the

One mile of 8th Standard South and Subdivisions of

Township South Range 2 West

Salt Lake Meridian

Utah Territory

as surveyed by

Bailey & Burrill

under joint contract Bailey & Burrill

No. 13 - dated Sept 21st 1876

Survey commenced Mar 8th 1877

" completed " 9th "

BOOK-A-152

Township 11. South R. 2. West
of Standard Principal Meridian.



Salt Lake Meridian

Chains Timber & Cedar

East
Ch. accs. 25.736
Va. 15° 30. E.

20.00 Edge of Bluff, bears N.E. N.
40.00 Ch. temp. for accs. cor.
40.00 Road bears N.E.
79.90 Intersect east boundary of Township 1 No. S. of cor. B accs. 25.736 from which S. 89° 53. W. on true line Ch. accs. 25.736
39.95 Set Sandstone 15 x 10 x 4 ins 10 ins deep marked from N. side raised mound of stone for temp. cor.
79.90 The cor. B accs. 25.26.35.36
Land Office Salt Lake Date

Subdivision T. 44 S. R. 2. W.

Brain Elmer scattering Cedar

North 1/4 sec. 25 T. 3. 6

W. 1/2 80. 8.

10.00 Marino drain S. E.

17.00 " " E.

100.00 N. E. Sandstone 24 x 14 x 2 in

1 in. deep marked Jno. M.

with 2 rain and 2 round Gates

for 2 sec. Cor.

80.00 N. E. Sandstone 36 x 3 1/2 x 4 in 27

in. deep Notched with 2 T 2 in S.

only 2 rain and 2 round Gates

for cor. Bees 23. 24. 25 T 26

Land broken, Soil Dark

Elmer Cedar

Land on random line

1/4 sec. 24 T 26

Salt Lake Meridian

Chains	
	Va. 15° 30' E.
34.00	Radian Stone drains N. E.
40.00	Set temp. for meander.
80.06	Intersect past boundary of Township 35 S. R. 10 W. S. of cor. to secs. 24 & 25 from which S. 89° 15' W. one link dist. secs. 24 & 25
160.03	Set Sandstone 18x10x4 in 12 in deep marked for M. on N. side with mound of stone for j.o. cor.
80.06	The cor. to secs. 23-24-25 & 26 Sand & Boulder clay hills Soil Dunes, Timber-Cedar
	North dist. secs. 23 & 24 Va. 15° 30' E.
40.00	Set Sandstone 12x12x4 in 6 in deep marked for M. on N. side

Subdivision T. 11 S. R. 2. W.

Chains	Raised mound of stone for ¼ sec. cor.
56.00	Road to Tuscumbia &c.
12.00	Marsh chains E.
15.00	Foot of Bluffs, east side of mouth of Indian head R.
60.00	Trees for falling in Bluff in notch 6, thence at 75. links set Sycamore 16×10× 4 ins. 1½ in deep marked W.C. ¼ ¼ sec. 6 N 30 W. S. edge to mound mound of stone for cor. to sec. 13. T. 11 S. R. 2 W. 24 —
	Land fractional Claim Settled April 3rd 1846 — No Timber —

East on random lines
Lt. 11 chs. 13 L. 2 c.
Va. 15°. 30. E.

Salt Lake Meridian

Chains	
	From witness cor. Drum East on offset line 20.00 chs thence N. 3.00 chs to
	cor. on true line
22.00	Rock drains N. E.
31.00	" " S. E.
40.00	Set temp. 1/4 sec. cor.
53.00	Rock drains N. E. & road bears N. E. & S. W.
72.10	Intersect east boundary of township 1 S. of cor. bears 13924 from which S. 89° 53' W. on true line Dist. 13924
40.05	Set sandstone 16 x 10 x 4 ins 11 ins deep marked 1/4 on N. side & raised mound of stone for 1/4 sec. cor. at foot of bluffs bearing nearly E & W.

5/2

Subdivisions 7.14. S. R 2. W.

Chains
80.10

The cor. to secs. 13. 14. 23 & 24
Sand, broken Soil & Pts.
N. Dan Tree. —

The line returns secs. 13 & 24
being impracticable I go to
the cor. to secs. 12 & 13 on the
east boundary of the township
from
Post on true line
Int. secs. 12 & 13
Va. 15°. 30'. E.

5.00
10.00

Foot of Bluffs bears N & S.
Iron corner falling in
Bluffs is not set there
from at 5.00 chs. set stone
stone 20 x 8 x 6 on 15 in deep
marked W. C. 1/4 on N. side &
raised mound of stone

Salt Lake Meridian

Chains for witness ¼ sec. cor.

Note: I abandon line here.
Sand broken clay hills
Soil Sandy - No Timber -

West on true line
bet. secs. 1 & 12
Va. 1° 30' E.
from E. ¼ sec. cor. bet. secs 1 & 12
N. 68° 30' W. 46.00 chs. thence
North 23.14 chs. to true line
thence East 1.80 chs. to point at
31.00 On true line at foot of bluffs
on the side of Gulch drains N.
where I set Sandstone 20x8x
6 in 1½ in deep marked W.C.

Subdivisions T. 4 S. R. 2 W. Sa

Chains	Mole hole 5 on S. & 1 on N. edges raised mound of stone for witness corner. No. 16. 7 1/2 ✓
40.00	Set Sandstone 20 x 2 x 4 ins. 5 in ground marked 1/4 on N. side raised mound of stone for 1/4 sec. cor.
40.00	Gulch drains S. W.
51.00	Paria River 50 links wide runs S. E.
65.00	Road bears N & S.
65.50	Fence bears N & S. enter field
73.25	Foot of bluffs on W. side of Bottom & field.
80.00	The true cor. falling in bluff 40.0 is not set. Therefore at 73.25 chs. I mark Red Sandstone in place 4 x 2 1/2 x 1 foot above ground W.C. Mole hole 1 on S & 5 on S. edges ✓ raised mound of

Salt Lake Meridian

stone for witness, cor. bears S. 2. W. 1.0 ch. dist.
Land mostly level.
Soil, clay & sand. No Timber.

As the line north will strike the bluffs in less than 80.00 chs Drum South, bet. secs. 11 & 12
Va. 15° 30' E.
From this witness cor. South on offset line along E. slope of bluffs 40.00 chs. to point 6.75 chs. east of
40.00 The true cor. point falling in bluffs is not set therefor at the point above reached I set a sandstone 16 x 10 x 4 in 11 in. deep, marked 1/4 on N. side & W.C. raised mound of stone

916.

Subdivision, T. 1 S. R. 2 W.

Chains for witness pt. as per cor.

Note. I abandon line here -
Land E. slope of Bluff.
Soil 3rd rate - No Timber -

From Witness cor. N. 71 W.
Set Stone Mound
Lt. acc. 1 E.
Va. 15° 30' E.
From this witness cor. to Sec
13. 1 1 S 1 2
Run North 20. West
19.74 chs to
18.49 On true line
30.00 Fence, brs E & W. Lean field
A. F. Smithson's cabin brs
S. E. 5.00 chs. dist.
40.00 Corner falling in Paria
River which runs E. 9 offset

Salt Lake Meridian

Chains West 8.15 chs. where I set
Sandstone 14×13×9 in 9 in deep
marked ¼ on N. side W.C.M.
raised mound of stone for
witness ¼ sec. cor. from which
A Cottonwood 10 in. dia. bears
N. 30° W. 100 lks. dist.
A Cedar 3 in. dia. bears S. 35° W.
20 lks. dist. both trees marked
¼ S. W. C. B. T.
Thence North on offset line
20.00 chs. to point 20.00 chs
South & 8.15 chs west of
80.00 The point for true cor. which
falling in bluff is not set
thereon at the point reached
on the offset line I set
Sandstone 30×24×15 in 20 in
deep marked W.C. notched

Subdivision T. 4 N. R. 2 W.

Chain

[illegible]

1.42 Ch. [illegible]

A Ballonwood 12 ins. dia. brass

S.S.W. 152 lks. dist. marked

S. 2. T. 4 N. S. R. 2 W. W.C. B.T.

Sand mostly, sand bottom — 2.74

Pd. 1.42 Vale, No Timber —

2.92

8th Standard South — 40.00

Set. pcs 29.35

Var. 15° 30' E.

From the witness cor. last — 4.E.16

set as above I run West

14.30 chs. thence north on

offset line 20.00 chs. to point

on 8th Standard South a — 52.4

22.46 Entrance line 40 feet of

Bluffs bearing N. 75 E. — 80.00

BOOK-A-152

Chains	where I set a Red Sandstone 4×3×2 feet marked S.C. 1 rock on E. 5 on N. 6 on S. edges with mound of rock piled around it for closing witness cor. Witness N 2
2.74.5	Pass a Barrow bears wide pass S.W. Roads N.
29.25	Road bears N. & S.
40.00	Finding an error in the tally on this offset to this 1/4 sec. cor. was set, at
46.10	A Sandstone 17×10×7 in 11 inches marked 1/4 on N. side & mound mound of stone for 1/4 sec. cor.
52.45	Foot of bluffs on W. side & bottom bears N. W & S. E.
60.00	The true cor. falling in

770

Subdivision of U.S. R.L.M.

Note:

Chain and Tally Book of Survey of Subdivision of Township No. 32 North of Range No. 3 East of the Boise Meridian, Idaho, Surveyed by W. C. Dashiell, Deputy U.S. Surveyor, under Contract No. 2, dated May 1st, 1877.

Commencing at the Corner to Sections 1, 2, 11 & 12, T. 32 N., R. 3 E., B.M., from which a Standard Stone 3" x 2" x 16" bears North 40.0 links distant, and a Pine 12" diameter bears S. 40° W. 53.0 links distant, and a Pine 8" diameter bears S. 80° W. 80.0 links distant, and a Pine 8" diameter bears N. 80° E. 80.0 links distant, and a Pine 8" diameter bears S. 80° E. 80.0 links distant, and a Pine 8" diameter bears N. 80° W. 80

Salt Lake Meridian.

Chains of Kaniksu Span
North bet. secs. 34 & 35
Ra. 15° 30. E.

40.00 Set Sandstone 20x7x5 ins
inscribed with N. with
raised mound of earth from
which a cedar 24 ins in dia
bears N. 53. W. 72 lks. dist
S. 27. W. 1 L. S. R. 2 W. B. T.
Land undulating - Soil
Dale. Timber Cedar on S 1/2

Subdivision No. 1 S. 02. 2. W.

Chains	East on land on line
	bet. secs. 26 & 35
	Va. 15. 50. E.
30.00	Ridge, mars. N. E. & S. W.
110.00	Red Sandstone Rock cor.
80.10	Intersect N. & S. line of
	W. S. Sec. bet. secs. 26 & 35
	from which
	S. 89° 53. W. on line, line
	bet. secs. 26 & 35
210.05	Pt. Sandstone 15 x 10 x 4 in.
	10 links from mound of
	stone for 1/4 sec. cor.
80.10	Thence Rock secs. 26. 27. 34 & 35
	Sand, broken, pits & Tats
	Timber- Cedar-

North bet. secs. 26 & 27

Salt Lake Meridian

Chains	
	Tw. 15°. 30. E.
14.00	Wash drains N. E.
31.00	W. d. bears N. E. 8 S. W.
46.00	Set Sandstone 16×9×4 ins 11 ins deep marked 4 on N. side raised mound of stones for 4 corner.
47.00	Wash drains N. E.
80.00	Set Sandstone 14×10×4 ins 9 ins deep notched 2 on E & S. edges raised mound of stones for COR Bears. 22.23.26 W.
	Land broken clay hills fair 2° rate - No Timber

Last on random line
Set. Bears. 28 W 26

Tw. 14°. 30. E.

16.00	Wash drain N. E.

Subdivision 2.4.1.S.8E.2.W.

Chains		
31.00	Road bears N.E. 2 S. W.	Chain
40.00	Set Temp. 1/4 sec. cor.	
80.01	Intersect N bdy. Lim 36	56.0
	Chn. S. 8 sec., 6 secs. 23726	80.0
	from which	
	S. 89° 45' W. on true line	
	Set. secs. 23726	
40.02	Set Sandstone 14x8x6 in	
	pile depressed 1/2 cu.	
	N. side & mixed around	
	Rotten for 1/4 sec. cor.	
70.01	Chain in 8 secs. 22.23.26.27	
	Land broken, clay hills	
	Soil Dark, No Timber	

	North Set. secs. 22923	40.0
	W. 15° 30' E.	60.0
40.00	Set Sandstone 5 in x 9 in	
	10 in deep mounded 1/4 cu	

Salt Lake Meridian

Chains | Ft. Oaks & raised mound of stone for Ist. cor.

56.00 | Wash drains E.

80.00 | Set Sandstone 17x10x7 in. 11 in. deep, notched 2 on E & 3 on S. edges & raised mound of stone for cor. B.C. on. Ts. 15, 22 & 23 R. 3 E.

Lands broken & hay hills Soil, Dale.

Timber scattering pedar

East on random line Ist. Secs. 14 & 23 Tps. 15, 30, E.

Many ponds & close of bluffs

40.00 | Set Stone, 4 cor. on.

60.00 | South point of Bluff - Offset south 5.00 chs. thence East 20.00 chs. to witness cor. 5.00 chs

Sec. 4 Twp. 5 S. R. 2 W.

Chains	
	South.
80.00	Thence East 80.00 chains
	Pine and Oak
	First quality land
	Lots 1 2 3 & 4
40.00	Red Sandstone 14 x 9 x 6 in. Qtz. deeply impacted, 4 on 4 sides & raised mound of stone for each corner.
80.00	Thence East 80.00 chains
	Sandy broken clay hills
	Soil 2nd rate
	Timber pine, cedar,

Note: On account of the Bluffs the line could not be run & is unmeasurable.

Area Thence East 39.84

Salt Lake Co. Recorded

Chains on the south boundary of the Tramway Drain
North E. 2 acres, 33 x 334
Sec. 16. 30. E.

6.00 Pond Brass N.E. 9 S. W.

40.00 Set 6 Standstones 12 x 12 x 6 in Sec. for corner marked on W. side & faced on round of stone for corner.

40.00 Brass Chains N. & E.

78.50 " " E.

80.00 Dig Pit & Plant Cedar Post Notched 3 on E & 1 on S. edges 48 x 12 x 12 in 2 ins. above ground mound of earth from pits each 24 x 12 x 12 ins for cor. 2 acres. 27.28.33.34 from which Cedar 20 ins. dia. bears S. 30. W. 28 lks. dist. marked S.33 T.4 S. R. 2. W. S.L.

Sab. Forenoon Sch. A. M. 2. Pr.

Chairs B. Cedar Sim. Rec. Chairs No. 85. Chairs
Pr. 68 Chr. Christ. Comm. Cedar 25.
P. T.
Rand. Brothers, Cap. Hill
Foil, 3 Rails.
Timber Cedar.

Easton Random Sins,
Ch. Acco. 2 Pr. 31.
Ps. 15. 30. 8.

12.50 Chairs No. 8.
40.00 Pet Lamps, Upper. Cor.
40.00 " " Wash drains No. 8.
53.00 Trunk " " " 10.00
5.15 Board to Carriage, Chairs No. 8. P. S. M.
2.50 Wash drains No. 8.
70.00 Interior No. 8 P. S. Limestone
Cor. Chairs. 16. 2 Pr. 34936 47.00
Front Cor. 80.00

Salt Lake Meridian

Obains Northern Line
Sec. 2, T 3 S.
40.00 N. E. Corner Section,
18 x 12 x 3 in. deep, marked
Stone, Mound of
Stones 2 ft. West.
80.00 [illegible] Sec. 2, T. 28. S. R 3 W.
Range Northern Utah Hills
[illegible]
Timber Cedar

Sec. 2, T. 28 S.
R. 15. 30. E.
40.00 Cor. Sandstone, 16 x 10 x 4 in. 11
in deep, marked 1/4 on N.
side, Mound of Stones
1 ft. West.
49.50 Creek, drains N. E.
80.00 Cor. Sandstone, 16 x 10 x 8 in. 11

Sec. 6 Twp. 54 R. 8 W. 2 M.

	Chains in a straight line 30 on 6 72 on	Chains
	S. edge of raised mound of	79.86
	stone from cor. No. 22 2 1928	
	Land Northerly bay lakes	
	No. 2 Dak.	
	Timber. Cedar	
	East on random line	
	Int. cor. 2282	40.00
	Va. 15° 30' E.	
21.00	Wash drains N. E.	
40.00	Set temp. St. cor.	
79.86	Intersect N 85 chs. 35 lks.	44.00
	S. of cor. No. 2282 from which	30.00
	S. 89° 45' W. on true line	80.00
	Int. cor. 2282	
39.93	Set Sandstone 18 x 10 x 6 in	
	12 in deep mound St. on N.	
	side of raised mound of	

Salt Lake Meridian

Chains stone for ¼ sec. cor.

79.86 Thence W. on sec. 21, 22, 27, 28.

Land small clay hills

Soil, 2 Yards

Timber - Cedar -

North, W. on sec. 21 & 22

Var. 16° 30' E.

40.00 Set, sandstone, 16 x 8 x 8 in. ½ in.

deep Mounds, on N. side &

scribed mound stone for ¼

sec. cor.

44.00 Wash drain N. E.

70.00 W.

80.00 Iron post & bluff, pass E. on.

Set sandstone, 16 x 11 x 9 in. ½ in.

deep mounds on E. & S. edges

scribed mound stone for cor.

to sec. 15, 16, 21 & 22.

Land small clay hills -

Subdivision Sec 1. S. R. 2. W.

Chains

Chains for 2nd Ln:
Chamber. Reduce
Mar 8th 1877 J. Cr Bennett.

Notes

Mar 9th 1877 J. Cr Bailey.
Cashin & Sandercock
Sub. decs. of 1922
Vin. S. 30. E.
Along Northern post of bluffs
40.00 to Stone P. Incr. cor.
79.80 Intersect S. 88 Links & Lks
S. of cor to decs. 1922 from which 40.00
S. 89° 53' W. on true line
Sub. decs. 1922
39.90 Set standstone 4x12x4 in the
ground, 4 on N. side
Raised mound of stone for 4
decs. cor.
7.50 Thence to decs. S. 16. 2 1922

Salt Lake Meridian

Chains Land: Iron Ken
Coal: Fire Clay
Timber: Cedar
Notes: I abandon Mines here

From the cor. to secs. 32 33 28 33 on the south boundary of this Township
North Bt. secs. 32 33
Va. 15° 30' E.
13.00 Set Road Brass N. E. 95. N.
40.00 Set Sandstone 6x8x6 Saw 11 in deep marked 1/4 on N. side & raised mound of stone for 1/4 section from which
Cedar 6 in dia brass S. 75. E. 65. Mrs. dist. marked 1/4 S. B. T.
To wood Mounts Town I

234

Subdivisions T. 4 S. R. 2 W.

Chains

20.00 Offset, east 20.00 chs. Thence north on offset line 40.00 chs to point 20.00 chs East of the True cor. point which falling in brakes this cor. is not set, therefore at this point reached I set a piece of hypsum 8"x14"x4" 4in 12in deep marked W.C. 4 notches on E & W sides and mound of stone for cor. Bears 28.29.32 E 33 Land broken Soil Dark Timber Cedar

Chains

East on random line
Set. accs. 28 33
Va. 15.20.E.

Witness tree
Pointer

Salt Lake Meridian

Chains	
15.00	Pine & Cedars N. E.
20.00	Pointers cor.
40.00	Set Temp. Mound cor.
70.00	Intersect C. & N. S. Lines & cor.
	Bears. 28 & 33 from w. ends
	Fruit on three lines
	Mts. bears. 28 & 33
40.00	Set Cedar Post (charred) marked 1/4 on N. sides 48 links & 4 links W. under Mound of stone for 1/4 sec. cor.
70.00	Pine cor. bears. 28. 29. 32 & 33
	Land broken clay hills
	Soil & Rate
	Timber, Cedar

North 80 chs. bears. 28 & 29
Var. 15° 30' E.
From cor. Pointers cor. North 20.
00 chs. Pine bears West 20.00 chs

Sur Elevation, Tel. S. Ry. 2 Tr.

Chains	Estate, Line, where Data	Elev
	Sandstone, 16 x 10 x 4 in., in	
	deep marked W.C.D. ¼ on	
	N. side Trained mound &	30.0
	stone for witness cor. Dec.	40.0
	28 & 29. 32 933 -	80.0
40.00	Rel. Sandstone 16 x 12 x 4	
	in 11 in deep, marked ¼ on	
	N. side Trained mound &	
	stone for ¼ sec. cor.	40.0
52.00	Wash drains E.	
80.00	Rel Sandstone 16 x 10 x 4 in 11	
	in deep, marked 1 on E 2 on	
	S. side Trained mound &	80.0
	stone, for sec. Dec. 20. 21. 28 & 29	
	Sand, Brown Rocky	
	Soil 2 Feet	
	Timber Cedar -	

Sixth Principal Meridian

Chains — Exterior Boundaries

Blk. 1, 2, 21 & 28

Lat. 15° 30.6,

30.00 Township No. 8,

40.00 Subdivision of sections,

80.10 Intersects N. & S. line 35 lks. E.

of cor. to secs. 21 & 28 from which

S. 89° 45' W. 80 lks. a white pine

blaze, 6 ins. diam.

40.05 Set stone 16 x 12 x 4 ins.

inscribed as in field notes, with

mound of stones.

80.10 Passes E. & W. cor. to secs. 20, 21, 28 & 29

Land is rolling prairie

and 2nd-rate timber land.

North 1/4 sec. cor. to secs. 20 & 21

Lat. 15° 30.6.

238

Subdivision No 15. 1922. M

Drains

40.00 Pits Sandstone 8 x 11 x 6 in. 80.16

in deep for radial Drain 22

pits to be commenced & dug

for Inspector.

40.00 Wash drains S.E. 40.08

10.00 Pit, Sandstone 8 x 10 x 4 in.

12 in deep for notched drain &

4 Sand bags & raised mound

of clay for one Drain No. 17 80.16

20721 near foot of bluff

Boring E & S.W.

Sandstone Quarry

Coal 3 Miles. No Timber

Note:

East main drainage line

Plt. No. 16721

Va. 15° 30° E.

40.00 Pit Temp. for Drain. cor.

57.00 Wash drains S.E.

Salt Lake Meridian

Township

80.16 Intersect N.S.L. with W. bdy. S. of cor. B. secs. 16 & 21 from which S. 89° 53' W. 80.16 chs. Set cor. 16 & 21

40.08 Set Sandstone 17 x 9 x 6 ins. in ground marked from which Pine 12 ins. diam. bears N. 30° E. 40 links dist. Pine 6 ins. diam. bears S. 30° W. 40 links dist. for 1/4 sec. cor.

80.16 The cor. B. secs. 16, 17, 20 & 21 Sandstone 20 x 10 x 6 ins. Mound of Stones. Pits 3 ft. sq. Timber Cedar.

Note: The land further north is unsurveyable & I abandon it here.

From the cor. B. secs. 31 & 32 on south boundary of the Township

North 80.16 chs. to cor. 31 & 32

Subdivisions T. 4 S. R. 2 W.

Chains	
	Pt. 15°. 30 E.
30.00	Foot of Bluffs bear E & W. a scant
40.00	Mound. falling in bluffs is not
	set. the reference 30. L. Post
	Sandstone 4 x 10 x 24. 7 ins deep
	marked XV. S. 4 on W. side
	raised mound of stone for
	witness tree.
Note:	Owing to the Red Bluff
	Subdivision the further
	survey of this Township
	Land Notes were lost by
	fire. Date
	Timber - Post Oak &
	Marg. 57 J. C. Bailey

General Description.

A portion of the
surveyed lands in this

Salt Lake Meridian

Township lies in the bottom of the Paria River in secs. 1, 2, 11 & 12 where there is a settlement & the lands are under cultivation —

Returns 5 1/2 secs 13 as Alum land —

The balance of the lands lie on the bench west of Paria River — Timber Cedar —

The lands are agricultural —

T. C. Bailey
U. S. Dep. Surveyor

BOOK-A-152

U. S. SURVEYOR GENERAL'S OFFICE.

Salt Lake City, Utah, June 21" 1877

The foregoing field notes of the survey of

East & West Boundary & Subdivisions,
& one mile 6th Standard South,

Township No. 4 1 S *Range No.* 2 W

Executed by Bailey & Russell

Under Joint *contract of the* 4"

day of Sept 1876, *in the month of*

March 1877, *having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.*

Nathan Kimball

Surveyor General for Utah.

BOOK-A-152

Examined by C. H. Cranwell. G. G.

Field Notes
of the
Survey of the
Subdivision lines of
Township 41 South
Range 4½ West
of
Salt Lake Meridian
Utah Territory —
by
J. C. Bailey
U. S. Dep. Surveyor.
under joint contract No 71
of Bailey & Burnie
Dated Sept. 4th 1876.

Surveyed Dec. 27th & 28th 1876.

BOOK-A-152

Township N. Rock R. 11 W. 5th P.M.



BOOK-A-152

Subdivision lines of T. 4 S. R 4½ W.
Salt Lake Meridian — 247

Survey commenced
Dec. 27th 1876
by J. C. Bailey

Note: See explanation of Range "4½" West in Note at end of mile on South side sec 32, 7th Standard South Range 4 West

As it is impracticable to survey the south & east portions of this township 2 begin at the established cor to secs 13, 18, 19 & 24 on the West boundary of the township & run
East on true line between secs 18 & 19
Var. 16° E.

Chains		Chain
39.16	(Allowing for convergency) Set sandstone 15 x 10 x 5 in. 10 in. deep marked 1/4 on N. side & raised mound of earth from 4 pits each 24 x 12 x 12 in. for 1/4 sec. cor.	
79.16	Set Sandstone 12 x 8 x 6 in. 8 in deep marked 5 notches on E & 3 on S. edges & raised mound of earth from 4 pits each 24 x 12 x 12 in for cor. to secs 17, 18, 19 & 20 from which	40.00
	A cedar 8 in dia bears S. 1 W. 25 lks dist. marked S 19 T 41 S. R. 4½ W. B.T.	
	A pine 12 in dia bears S 30 E. 60 lks dist. marked S. 20 B.T.	50.00 80.00
	Land undulating	
	Soil 2nd rate	

R 4 1/2 W. Salt Lake Meridian

Chains | Timber Pine & cedar

East on true line
betw secs 17 & 20
Var. 16° E.

40.00 | Set sandstone 16 x 10 x 4 in
11 in deep marked 1/4 on N.
side & raised mound of
stones for 1/4 sec. cor.
from which
A cedar 14 in. dia bears
N. 85° W 50 lks dist.
A Pine 9 in. dia bears
S. 87° E 55 lks dist.
Both trees marked 1/4 S.B.T.

50.00 | Bottom of cañon drains S.W.

80.00 | Set sandstone 15 x 10 x 5 in
10 in deep marked 4 notches
on E & 3 on S edges &

Subdivision lines of T. 41 S. R

Chains	raised mound of stones for cor to secs 16. 17, 20 & 21. Land undulating Soil 2nd rate Timber scattering pine & cedar.	Chains
	East on random line between secs 16 & 21 Var. 16° E.	
40.00	Set chamfered cedar post 48 x 3 x 3 in 12 in deep marked 1/4 on N. side in mound of earth raised from 4 pits each 24 x 12 x 12 in for 1/4 sec. cor.	40.0
80.00	Set chamfered post 48 x 4 x 4 in 12 in deep marked 3 notches on S & E edges in mound	80.0

R 4½ W. Salt Lake Meridian

Chains of earth raised from 4 pits each 24 x 12 x 12 in for cor. to secs 15, 16 21 & 22
Land undulating
Soil 2nd rate
Timber scattering pine & cedar.

North betw secs 15 & 16
Var. 16° E.

40.00 Set cedar post 48 x 3 x 3 in 12 in. deep marked ¼ on W. side, in mound of earth raised from 4 pits each 24 x 12 x 12 in for ¼ sec. cor.

80.00 Set cedar post 48 x 4 x 4 in 12 in. deep marked 3 notches on E & 4 on S. edges, in mound of earth raised from 4 pits

Subdivision lines of T. 41 S. R

Chains	
	each 24 x 12 x 12 in for cor. to secs 9, 10, 15 & 16.
	Land undulating
	Soil 2nd rate
	Timber scattering pine & cedars

North betw. secs 9 & 10
Var. 16° E.

40.00	Set cedar post 48 x 3 x 3 in 12 in deep marked 1/4 on W. side, in mound of earth raised from 4 pits each 24 x 12 x 12 in for 1/4 sec. cor.
80.00	Set limestone 18 x 15 x 2 in. 12 in deep marked 3 notches on E & 5 on S. edges & raised a mound of earth from 4 pits each 24 x 12 x 12 in for cor. to

R 4½ W. Salt Lake Meridian

Chains secs 3, 4, 9 & 10 pmw which
X cedar 7 in. dia bears N.
22 W. 60 lks. dist marked
S. 4. T 41 S. R 4½ W. B.T.
X cedar 5 in dia bears
S. 10° E. 57 lks dist marked
S 10° B. T. —
Land undulating
Soil 2nd rate.
Timber scattering pine &
cedar.

North on true line
between secs 3 & 4
Var. 16° E.

26.00 Ravine drains W.
40.00 Set limestone 14 × 12 × 3 in
9 in. deep marked ¼ on
W. side (no pits) for ¼ sec cor.

Subdivisional lines of T. 41 S.

Chains

from which

A pine 8 in. dia bears
N. 45° W. 56 lks dist
Pine 8 in. dia bears East
32 lks. dist.
Both trees marked 1/4 S. B. T.

80.00 Intersect 8th Standard North
8.96 chs E. of Standard cor.
to secs. 33 & 34 where I set,
on N. point of Gypsum hill,
a piece of Gypsum 18 x 12 x
3 in. 12 in deep notched 3
on E. & W. & 6 on S. edges &
mixed mound of Gypsum
for closing cor to secs 3 & 4.

from which

A Pine 12 in. dia. bears S 45 W.
35 lks. dist. marked S. 4 B. T.
A Pine 12 in. dia. bears S 35 E.
40 lks dist marked S 3, T 41 S,

R 4½ W. Salt Lake Meridian

Chains R 4½ W. B.T.

Land broken

Soil 2nd rate

Timber thick cedar & pine

From the cor. to secs

16, 17, 20 & 21 2 mw

North betw. secs 16 & 17

Var. 16° E.

35.00 Cairn near head draws S.W.

40.00 Set limestone 18 × 8 × 5 in

12 in. deep marked 1/4 on

W. side & raised mound of

stones for 1/4 sec. cor. from which

A cedar 12 in. dia. bears

N. 87° W. 14 lks. dist.

A cedar 14 in dia bears

S 10° W 10 lks dist.

Both trees marked 1/4 S. B.T.

Subdivision lines of T. 41 S. R 4

Chains	
65.00	Tops of Rock Bluff bears E & W
80.00	Set sandstone 24 x 14 x 5 in 16 in deep notched 4 on E & S. edges & raised mound of stones for cor to secs 8, 9, 16 & 17 from which:
	a cedar 6 in. dia. bears S 25° E 15 lks dist marked S 16 B.T.
	a Pine 10 in dia bears N. 80 W. 100 lks dist marked S. 8 T. 41 S. R 4½ W. B.T.
	Land broken
	Soil 2nd rate
	Timber pine & cedar

East on random line between secs 9 & 16
Var. 16° E.

0.50	Ravine drains N. W.

R 4½ W. Salt Lake Meridian

357

Chains	
40.00	Set temp. 1/4 sec. cor.
80.10	Intersect N. & S. line 7 lks S. of cor. to secs. 9, 10, 15 & 16 from which
	S. 89° 57' W. on true line between secs 9 & 16
40.05	Set cedar post 48 x 4 x 4 in 12 in deep marked 1/4 on N. side in mound of earth raised from 4 pits each 24 x 12 x 12 in for 1/4 sec. cor.
80.10	The cor. to secs 8, 9, 16 & 17.
	Land broken
	Soil 2nd rate
	Timber pine & cedar

North betw. secs 8 & 9
Var. 16° E.

0.50	Ravine drains N. W.

Subdivision lines of T. 41 S

Chains	
13.00	Rocky bluff bears E & W. descend
20.00	Bottom of flat mine drains S W.
35.00	Ridge bears N. W. & S. E.
40.00	Set sandstone 15 x 10 x 7 in 10 in deep marked 1/4 on W. side, with mound of stones for 1/4 sec. cor from which A pine 5 in dia bears S. 75 W. 85 lks dist marked 1/4 S. B.T.
80.00	Set sandstone 14 x 12 x 8 in. 9 in deep notched 4 on E & 5 on S. edges & raised mound of earth from 4 pits each 24 x 12 x 12 in for cor to secs. 4, 5, 8 & 9
	Land broken
	Soil 2nd rate
	Timber Pine & Cedar

Dec 27th 1876

R 4½ W. Salt Lake Meridian

Chains	
	Dec. 28th 1876
	East on random line
	between secs 4 & 9
	Var. 16° E.
30.00	Ridge bears N.W. & S.E.
34.00	Wash drains N.W.
40.00	Set temporary ¼ sec. cor.
45.20	Ravine drains N.W.
	Ascend —
53.00	Top of sandstone bluff bears N. & S.
60.00	Ravine drains N.W.
65.00	" " "
71.00	" " "
74.00	Top of main ridge bears N. & S. —
80.00	Intersect N. & S. line at cor to secs 3. 4. 9 & 10 from which

Subdivision lines of T. 41 S.

Chains	
	West on true line between secs 4 & 9
40.00	Set sandstone 16 x 10 x 5 in. 11 in. deep marked 1/4 on N. side (no pits) for 1/4 sec. cor. from which A cedar 6 in. dia. bears S. 60 E. 8 links dist. A cedar 5 in. dia. bears N. 20 W. 35 links dist. Both trees marked 1/4 S. B. T.
80.00	The cor. to secs 4, 5, 8 & 9 Land broken Soil 2nd rate Timber pine & cedar.

North on true line between secs 4 & 5
Var. 16° E.

R 4½ W. Salt Lake Meridian

Chains

40.00 Deposited a small stone marked with a cross (+) in mound of earth raised from 4 pits each 24 x 12 x 12 in for ¼ sec. cor.

47.00 Ridge bears E & W.

80.10 Intersect 8th Standard South 8.96 chs east of standard cor to secs 32 & 33 whence 2 set Limestone 24 x 16 x 6 16 in deep notched 4 on E. & 2 on W. & 6 on S. edges & raised mound of earth from 3 pits (E. W. & S) each 24 x 12 x 12 in. for closing cor. to secs 4 & 5.

Land rolling

Soil 2nd rate

Timber a few cedar.

Subdivision lines of T. 41 S.

Chains

From the cor. to
secs 17, 18, 19 & 20
2 mds
North betw secs 17 & 18
Var. 16° E.

40.00 Set sandstone 12 x 8 x 5 in
8 in. deep marked 1/4 on
W. side & mixed mound
of earth from 4 pits each
24 x 12 x 12 in for 1/4 sec
cor.

58.00 Head of moving drains
W.

75.00 Ridge bears E & W. descend

80.00 Set limestone 18 x 10 x 2 in
12 in deep notched 5 on E &
4 on S. edges and mixed
mound of stone for cor to
secs. 7, 8, 17 & 18 from which

R 4½ W. Salt Lake Meridian

Chains

A pine 10 in. dia. bears N. 45° E., 35 lks dist marked S 8 T 4 S. R. 4½ W. B. T. Pine 18 in. dia bears S. 45 W. 55 lks dist marked S. 18 B. T.

Land rolling

Soil 2nd rate Sandy

Timber pine & cedar.

East on random line between secs 8 & 17

Var. 16° E.

40.00 Set temp. ¼ sec. cor.

80.00 Intersect N. & S. line at cor. to secs. 8, 9, 16 & 17 from which

West on true line between secs 8 & 17

40.00 Set sandstone 15 x 10 x 5 in

Subdivision lines 18 of T. 41 S. 26 E. R.

Chains		Chains
	10 in. deep marked 1/4 on N. side & mixed mound of earth from 4 pits each 24 x 12 x 12 in. for 1/4 sec. cor	
80.00	The cor. to secs 7, 8, 17 & 18	33.00
	Land undulating	
	Soil 2nd rate	
	Timber pine & cedar.	

West on random line
between secs 7 & 18 — 79.06
Var. 16° E

10.00	Ravine drains S. W.
30.00	East side of canon drains
	South 2 mon offset
	North 40.00 chs thence
	West 17.00 chs thence
	South 40.00 chs to
47.00	On W. side of same cañon
79.06	Intersect West boundary — 4.00

R. 4½ W. Salt Lake Meridian

Chains	of townships at the cor to secs 7 & 18 from which East on true line between secs 7 & 18
33.00	Set sandstone 14 x 8 x 4 in 9 in deep marked ¼ M.C. on N. side & mixed mound of stones for Witness ¼ sec cor. Note: True cor. point falling in cannon cannot be established. ~~on line~~
79.06	The cor. to secs 7, 8, 17 & 18 Land broken & rocky. Soil 2nd rate Timber pine & cedar

North between secs 7 & 8
Var. 16° E.

4.00	Ravine drains S.W.

Subdivision Lines of T. 41 S.

Chains		Chains
35.50	Ravine drains N.W.	
40.00	Set sandstone 16 x 12 x 2 in. 11 in. deep marked 1/4 on N. side & mixed mound of stones for 1/4 sec. cor. on W. slope from which a pine 18 in. dia bears N. 20 W 60 links dist. A pine 20 in. dia. bears S. 30° E 50 lks dist. Both trees marked 1/4 S. B.T.	40.00
60.00	Descend to	44.00
75.00	Ravine drains west	47.00
80.00	Set limestone 30 x 14 x 2 in. on bed rock notched S & W E & S. edges in mound of stones for cor. to secs 5, 6, 7 & 8	50.00
		80.10
	from which	

R 4½ W Salt Lake Meridian

Chains A cedar 15 in. dia. bears
N. 12° E. 40 lks dist. marked
S. 5 T. 41 S. R 4½ W. B. T.
Land broken
Soil 2nd rate
Timber pine & cedar

East on random line
between secs 5 & 8
Var. 16° E.

40.00 Set temp. ¼ sec cor.
44.00 S. W. point of ridge
47.00 Ravine drains S. W.
57.00 Same " N. W.
80.10 Intersect N. & S. line 7 lks
South of cor to secs 4, 5,
8 & 9
from which

Subdivision lines of T. 41 S.

Chains		Chains
	S. 89° 57' W. on true line between secs 5 & 8	26.00
40.05	Set limestone 14 x 10 x 4 in 9 in deep marked 1/4 on N. side & raised mound of stones for 1/4 sec cor.	40.00 78.88
80.10	The cor. to secs 5, 6, 7 & 8 Land rolling Soil 2nd rate Timber a few cedars	38.88

West on true line between secs 6 & 7
Var. 16° E.

6.00	Brook runs S. W. and Enters meadow.	
17.00	Cabin bears N. 20 chs. dist.	78.88
19.00	Road bears N. & S.	

R 4½ W. Salt Lake Meridian 269

Chains	Leave Meadow
26.00	N.E. point of ridge
40.00	Set stone 1/4 sec. cor.
78.88	Intersect W. boundary of township at the cor. to secs 6 & 7 from which East on true line between secs 6 & 7.
38.88	Set limestone 18 x 12 x 5 in 12 in. deep marked 1/4 on N. side & raised mound of stone for 1/4 sec. cor. from which Cedar 10 in. dia bears N. 5 E. 44 lks. dist. marked 1/4 S. B. T.
78.88	The cor. to sections 5, 6, 7 & 8

Subdivision lines of T. 41 S. 370 24

BOO

Chains

Land broken
Soil 1st & 2nd rate
Timber a few cedars & pines

North on true line
between secs 5 & 6
Var. 16° E.

4.00 Enter meadow bears N. E & S. W.

12.00 Leave same

21.00 Fence bears S E & N. W. enter field.

40.00 Set limestone 20 x 14 x 12 in. 14 in deep marked 1/4 on W. side & raised mound of stones for 1/4 sec cor from which

40.10

41.2

73.70

R 4½ W. Salt Lake Meridian

J. M. Lee's house bears
N. 75° E 470 lks dist.
James M. Clarks house bears
S. 82 W. 310 lks dist.
A Pine stump bears
S. 46° W. 400 lks dist.
Simms Clarks house bears
S. 76½° E. 8.50 chs dist
David Lee's house bears
S. 84 E 8.65 chs dist
John Clarks house bears
N. 85 E. 9.14 chs. dist. —
This embraced the
settlement of
"Skunpuk" or Clarkston
40.10 Fence S. side of lane
bears E & W.
41.25 Fence on N. side of lane.
73.70 Fence bears N. W. & S. E

Subdivision Lines of T. 41 S. — R

Chains
80.00

Intersect 8th Standard
south 8.96 chs E. of
Standard cor to secs.
31 & 32, when 2 set
limestone 14 x 8 x 8 ins
9 ins deep notched 5 on E,
1 on W. & 6 on S. edges
& mixed mound of
stones for closing cor
to secs. 5 & 6
Land mostly level
fields
Soil 1st rate
No timber
Dec 28th 1876
T. C. Bailey

BOOK-A-152

R 4½ W. Salt Lake Meridian

T 23 S

General Description

The lands surveyed in this township embrace a portion of the "Skim-Pah Valley" and the settlement of that name.

The lands are agricultural.

The country rock is sandstone probably overlying coal.

J. C. Bailey—
U.S. Dep. Surveyor.

BOO

U. S.

Salt

The

Towns

Execu

Under

day of

exami

planat

survey

BOOK-A-152

270

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, April 3rd *187*7

The foregoing field notes of the survey of the Subdivision lines of *Township No.* 41 S. *Range No.* 4½ E *Executed by* J. C. Bailey, *Under his* first *contract of the* 4th *day of* September *1876, in the month of* December *1876, having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.*

Nathan Kimball

Surveyor General for Utah.

13 BOOK-A-152

Examined by D.H. Craine F.C.B.

S.M.R. 279

Field notes
of the Survey
of
The East Boundary of
Township 41 South,
Range 5 West,
of the
Salt Lake Meridian
Utah Territory
By,
F.C. Bailey, Under
Joint Contract of
Bailey & Burgess
U.S. Dep. Surveyors,
No. 77
Dated Sept. 4th 1896.

Surveyed Dec. 26, 1896

BOOK-A-152

Township 11 South R. 5 West



Cor. Bounding T. 41 S. R. 5 W.

chains Dec. 26th 1896 by T. C.
Bailey.
Note: See Explanation of
4 1/2 W, in note at end
of Sec. 32, T 35 S. R. 4
W. 7th standard South.
From the Standard cor,
to T. 40 S. R. 4 1/2 & 5 W,
I run East along the
8th standard South
10,08 For convergency of Meridians, to a point where I
set a charred cedar
post, 48 x 4 x 4, 12 in. deep
Marked 6 notches on E. W,
& S. Edges, in mound of
Earth, raised from 3 pits,
Each 24 x 12 x 12 in, E. W. &
South of post, for closing
cor, to Township 41 S. R. 4 1/2 & 5 W,

East Boundary T. 44 S. R.

from which Corner on South bears Sec. 1/16 Var. 16° E.

30.05	Road to Long Valley bears E. & W.	
110.00	Set a piece of Gypsum 18 x 12 x 3, 12 in. deep, marked 1/4 on N. side, for 1/4 sec. cor. (40 rods) from which A Cedar 15 in. dia, bears N 45 E. 200 links dist	
	" " 4 " " " S 53 W. 136 "	
	Both trees marked 1/4 S. B.T.	
	Thence along E. foot of Gypsum hills,	
62.00	Head of wash drains E.	
70.00	Ravine drains E.	
79.00	Near head of ravine drains E.	
80.00	Set a piece of Gypsum 16 x 8 x 7, 11 in. deep notched I on N. & S on S. Edges, and raised mound of Gypsum	1.00 33.00 40.00

BOOK
5 We

5 West, Salt Lake Meridian.

For cor. to Secs. 1. 6. 7 & 12. from which
A cedar 8 in. dia. bears N. 1 E. 40
links dist, marked T. 41 S. R. 4½
W. S. 6 — B. T.
A pine 20 in. dia, bears S. 65 W.
50 links, dist, marked R. 5 W. S. 6. B. T.
A pine 16 in. dia, bears S. 88 W,
65 links, dist, marked S. 12. B. T.
A cedar 20 in. dia, bears S. 1 E. 14
links dist, marked S. 7 B. T.
Land rolling.
Soil 1st & 2d rate.
Timber scattering pine & cedar.

South between Secs, 7 & 12
Var. 16° E.

1.00	East point of hill,
33.00	Ranie draws N. E.
40.00	Set charred cedar post
	48 x 3 x 3, 12 in. deep, marked

East Boundary T 41 S. R.

1/4 on N. side, and deposited a small stone, marked with a cross(+) along side of post for 1/4 sec. cor. from which, A cedar 8 in. dia, bears S. 80 E 45 links dist.
A pine 9 in. dia. bears N. 80 E. 55 links, dist. Both trees, marked 1/4 S. 13 T.

75.00 Ridge bears E & W.

80.00 Set Sandstone 13 x 8 x 6, 9 in 40.00 deep, notched 2 notches on N. & 4 on S. Edges, for cor, to secs. 7, 12, 13 & 18. from which A cedar 6 in. dia. bears N. 65 36 links dist, marked T. 41 S. R. 4 1/2 W. S. 7. 13 T.
A cedar 8 in. dia, bears S. 65 W. 50 links, dist, marked S. 13, 13 T. 42.00

R. 5 W. Salt Lake Meridian

A cedar 5 in. dia, brs S.80 E.
37 links, dist. marked S.18.B.T.
A cedar 8 in. dia. brs N.1 W. 48
links dist, marked S. 12 B.T.
Land broken,
Soil 2d rate - Sandy.
Timber cedar & pine

South between Secs. 13 & 18
Var. 16° E.

40.00 Set Sandstone 16 x 8 x 3, 11 in.
deep, marked ¼ on N. side,
and raised mound of stones
for ¼ Sec. Cor. from which
A Pine 4 in. dia, brs S. 60 W.
90 links dist,
A Pine 8 in. dia. brs N. 80 E.
60 links dist, Both trees
marked ¼ S. B.
42.00 Edge of Sandstone bluff

2586 6

East Boundary T. 41 S. R.

300 feet high, bears N.E. & S.W.

47.00 Foot of Same,

48.00 Road in bottom of Cañon S.W.

55.00 Skum-Ah Brook runs S.W.

57.00 Foot of Bluff on S.E. side of Cañon,

68.00 Top of Same.

80.00 Set Sandstone 16×10×4, 11in. deep marked 3 notches on N & S. edges, and raised a mound of stones, for cor. to Secs. 13, 18, 19 & 24,

Land broken.

Soil 2d rate.

Timber, cedar & pine.

Note: On account of the white cliffs to the south I abandon the line here.

Dec. 26th 1876 T. C. Bailey

BOOK-A-152

287

U. S. SURVEYOR GENERAL'S OFFICE.

Salt Lake City, Utah, April 3 1877

The foregoing field notes of the survey of the East Boundary of *Township No.* 41 S. *Range No.* 5 W. *Executed by* T. C. Bailey, *Under his* joint *contract of the* 4th *day of* September *1876, in the month of* December *1876, having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.*

Nathan Kimball

Surveyor General for Utah.

288

BOOK-A

W. Sal

For

and ap

of Su

this

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, 187

The foregoing field notes of the survey of

Township No. Range No.

Executed by

Under

day of 187 , in the month of

187 , having been critically examined, the necessary corrections made and approved, the said field notes, and the surveys they describe, are hereby approved.

Surveyor General for Utah.

BOOK-A-152

N. Salt Lake Meridian 2E

For General Description and Approval, See End of Subdivision notes of this Township.

BOOK-A-152

9a

Examined & ed. H. Brantley C. C.

Field Notes

of the survey of
the subdivisions of
Township 41 South Range 5 West
Salt Lake Meridian
as surveyed by
Bailey & Burrill
under their joint contract
No 71. dated Sept 4th 1876.

Survey commenced Dec 26. 1876
" completed Dec 30th 1876

Subdivisions T. 24 S., R. 5 W.

Chains

As it is impracticable on account of the mountains to survey the south part of this township from the cor. to secs 7. 12. 13 & 18 on east boundary of township I run West on true line between secs 12 & 13 Va. 16° E.

40.00 Set Limestone 10 x 10 x 7 in 6 in deep marked ¼ on N. side & raised mound of stones for ¼ sec. cor.

67.50 Top of slope descend

74.65 Road bears N & S.

76.20 Wash drains S. ascend

80.00 Marked sandstone in place 4 x 3 x 2 ft above ground notch on E & W sides S. edges raised

Sec

Chain

12.0

40.0

Note

BOOK-A-152 2

Salt Lake Meridian 270

Chains mound of stones for cor. to secs 11, 12, 13 & 14

Land rolling Soil 2nd rate
Timber scattering Cedars

South 1/2 mile secs 13 & 14

Va. 16° E.

12.00 Birch trees S. E. & N. W.

40.00 Set Sandstone 14 x 11 x 5 in 9 in deep marked + on N. side and raised mound of earth from 4 pits each 24 x 12 x 12 in for 4 secs. cor.

Land broken Soil 2nd rate
No Timber

Note: I abandon line here

From the cor. to secs 11, 12, 13 & 14 I run

North 1/2 mile secs 11 & 12

Va. 16° E.

294

Subdivisions 1 & 4 S. 12 E. 5 M.

Chains	
2.50	Wash in small hollow drains E.
10.00	Foot of sandstone ledge 30 ft high
11.50	Wash bears S. 30 E.
12.00	Road " " & N. 20 W.
29.00	Foot of Ridge, bears hollow
32.00	Limestone ledge 15 ft high bears E & W.
33.50	Top of Ridge point extends 3.50 chs N.
39.00	Foot of Ridge
40.00	Set sandstone 18 x 7 x 5 in 12 in deep marked + on N. side & raised mound of stone for 1/4 sec. cor.
50.50	Wash in hollow drains S. W.
54.00	Road " " bears E & S. W.
80.00	Set Limestone 16 x 7 x 8 in 10 in deep marked 1 notch on E & S on S. edges raised mound of earth from 4 pits each 24 x 12 x 12 in for cor. bocs 1. 2. 11 & 12
	Land undulating fair soil Timber scattering cedars

Sa

Chains

8.20

39.0

40.0

69.5

80.9

40.4

80.9

Salt Lake Meridian

chains East on random line
returns pecs 1 & 2
Var. 16° E.

8.20 Road bears N.E. & S.W. in hollow
drains S.W.

39.00 Point of Ridge extends from S.E.

40.00 Set temporary ¼ sec. cor.

69.50 Head of flat hollow drains
N.E. & W. into Plateau hills

80.90 Intersect east boundary of town-
ship 10 lks N. of cor. to secs. 1. 6.
7. 12 from which
N. 89° 36' W. on true line
returns pecs 1 & 2

40.45 Down charred Cedar stake
4 & 4 x 4 in 2 in deep marked
¼ S. raised mound of earth
from pits each 24 x 2 x 12 in for 4 sec. cors.

80.90 The cor. to secs. 1. 2. 11 & 12
Land rolling Soil & Rate.

Subdivisions T. 41 S. R. 5 W.

Chains & Timber scattering Pine

North on true line
Returns pass 1 82
Va. 16° 0' E.

38.80 Road bears E & W.

40.00 Set Sandstone Metate
14 x 8 x 4 in 9 in deep, marked
+ on N. side & raised mound
of stones for 1/4 sec. cor.

77.50 Gully, drains S. W.

79.64 Intersect 8th standard
Parallel North 8.96 chs E. of
standard cor. to secs 35 & 36
where I
Set Trachyte 18 x 12 x 8 in 12
in deep marked notch on
E & S on N. & on S. edges & C. C.
for closing cor. to secs 1 & 2
Land level & Fair Table

Salt Lake Meridian

Chains

No Timber

Dec 26th 1876 by J. C. Bailey

Dec 27th 1876 by J. Geo. Burrill

Set on true line

between secs 11 & 14

Va. 16° E.

25.00 Hash drains N. E.

25.50 Head of hollow drains N. 75° E.

33.00 Enter Plateau.

40.00 Set Sandstone 14 x 8 x 5 in 9 in deep marked + on N. side raised mound of stones for 4 sec cor from which

Cedar 12 in dia bears S. 15° E. 25 lks dist.

Cedar 10 in dia bears N. 45° W. 5 lks dist both trees marked 1/4 S. B. T.

80.00 Down Charred Cedar Post 4 & 4 x 4 in 12 in deep marked 2 notches on E & 4 on S. edges raised

Subdivisions T. 41 S. R. 5 W.

Chains mound of earth from 4 pits each 24 x 12 x 12 in for cor. trees 10, 11, 14, & 15 from which Cedar 4 in dia bears S. 30 E. 73 lks dist marked T. 41 S. R. 5. W. S. 14. B. T.

Land mostly level, Soil, Yate, Timber Cedar & Pine

As the north part of the township was not run on account of the mountains I run South between secs 14 & 15 Var. 16° 00 E.

40.00 Pit Sandstone 12 x 10 x 8 in & in deep marked T. on W. side raised mound of earth from 4 pits each 24 x 12 x 12 in for 4 dec. cor.

40.00

BOOK-A-152

Salt Lake Meridian 299

Chains

80.00 Pet Sandstone 14×10×6 in 9 in deep marked 2 notches on E. & W. on S. edge & raised mound of earth from pits each 24×12×12 in for cor. bees 14, 15, 22 & 23

Land slope facing N.

Pine & Cedar

Timber scattering

As the line will strike rock, mark pin less than 8 chs Dpm

East on true line

Return pits 14 & 23

Va. 16° E.

40.00 Pet Sandstone 15×9×9 in 9 in deep marked ± on N. side raised mound of earth from pits each 24×12×12 in for ± sec. cor.

300

Subdivisions T. 41 S. R. 5. W.

Chains		
	Note: I abandon line here	
	Land sloping N.	
	Soil 2nd rate.	
	Timber scattering cedars	140.
	At the line will reach rock	
	Breaks in less than 80 chs	
	I run	
	West on true line	
	between secs 15 & 22	
	Va. 16° 0' E.	80.
40.00	Set Sandstone 12 x 8 x 7 in 8	
	in deep marked ¼ on N.	
	side & raised mound of	
	earth from 4 pits each 24 x	
	12 x 12 in for ¼ sec. cor.	
	Note: I abandon line here	
	Land nearly level	
	Soil 2nd rate	
	Timber scattering cedars	

Salt Lake Meridian

Chains

From the cor. to secs 10. 11. 14 & 15
North 1/2 mile secs 10 & 11
Va. 16° 00' E.

140.00 Set Sandstone 18 x 16 x 8 in 12 in deep marked ¼ on W. side raised mound of stone for ¼ sec cor. from which the top of lone sugar loaf hill bears N 50 E. 12 chs dist. - Said hill being 15 chs dia. at base.

80.00 Set Limestone 14 x 8 x 5 in 9 in deep marked 2 notches on E & S ons. edges raised mound of earth from 4 pits each 24 x 12 x 12 in for cor. to secs 2. 3. 10 & 11
Land undulating soil 1st rate Good grass - No Timber

Easton random line
1/2 mile secs 2 & 11

Subdivisions T. 41, S. of R. 5 E.

Chains	Va. 16 cv. E.
16.50	Road bears N. W & S. E.
23.00	Enter Lava Bench bears N. W & S. E.
25.50	& Break in Lava Bench
28.00	Bear pine
40.00	Set temporary ¼ sec. cor.
65.00	Gully drains S. bear bench
80.10	Intersect N. & S. line 20 lks N. of cor. to secs 1, 2, 11 & 12 from which N. 89° 51' W. on true line between secs 2 & 11
40.05	Set Trachyte 14 x 9 x 5 in 9 in deep marked ¼ on N. side raised mound of stone for ¼ sec. cor.
80.10	The cor. to secs 2, 3, 10 & 11 Land level fair Data to Timber

Salt Lake Meridian

Chains North on true line

Returns secs 2 & 3

Va. 16° 00' E.

18.00 Road to Johnsons bears S. 7 W. S. E.

37.00 " " " Skumpah " E & W.

40.00 Set Lava stone 14 x 10 x 5 in 9 in deep marked + on W. side raised mound of earth from 4 pits each 24 x 12 x 12 in for 4 acc. cor.

40.12 Wash in hollow drains E.

77.52 Enter Lava Rd bears E & W.

79.48 Intersect 8th Standard Parallel South 8.96 chs E. of standard cor. to secs 34 & 35 where I s

Set Trachyte 15 x 8 x 6 in 10 in deep marked 2 notches on E. 4 on W. 6 on S. edges & s. c. & raised mound of lava

304 18

Subdivisions T. 41 S. of B. & M.

Chains for closing contracts.

2 & 3.

Land level

Soil 2d rate

No Timber

Dr. 27th J. G. Burrill

BOOK-A-152

Salt Lake Meridian

Chains Dec 28th 1876 by J. H. Purrill
On account of brakes South
1 run
West on true line
Return secs 10 & 15
Va. 16° 0' E.

40.00 Set Sandstone 14×8×7 in 9 in
deep marked + on N. side and
raised mound ~~of~~ of
stone for + Dec. Cor.

80.00 Pit Charred Oak Post 48×
4×4 in 24 in deep marked 3
notches on E. & 4 on S. edges & raised
mound of earth from 4 pits each
24×12×12 in for Cor. to secs 9. 10. 15 & 16
Sand level
Dirt & Rock
No Timber

North Return secs 15 & 16

Subdivisions T. 41, S. 8 R. 5. W.

Chains Va. 16°00'. E.

33.00 Descend

40.00 Bottom of Ravine drains S.E.
Set Gypsum 10x8x7 in 6 in
deep marked + on W. side
raised mound of
Gypsum for + dec cor.

80.00 Set Trachyte 11x9x6 in 6 in
deep marked 3 notches on
E & S. edges raised mound
of stone for cor. B dec 15.16.1922
Land rolling Dir 2 Rate
Timber scattering Cedar

North Returns dec 21 1922
Va. 16°00'. E.

40.00 Set Sandstone 11x11x5 in 7
in deep marked + on W. side
raised mound South from
4 pits each 14x12x2 in for + dec cor.

BOOK-A-152

Salt Lake Meridian

Engine

Note: I abandon line here
Land broken, Pits & Rate
& timber scattering Cedar

From the cor. to secs 9.10.15 &
16 I run
North 81 rods to sec 9 & 10
Va. 16° W. E.

40.00 Drove an Oak stake (charred)
4 8 × 4 × 4 in 12 in deep marked
$\frac{S}{4}$ on N. side 1 in mound
of earth from 4 pits each 2 × 1 2
× 1 2 in for ¼ sec. cor.

80.00 Deposited Bois du vic in
mound of earth raised
from 4 pits each 2 4 × 1 2 × 1 2 in
& drove charred cedar stake
4 8 × 4 × 4 in 12 in deep marked
3 notches on E. & S. on S. edges in
S. E. pit for cor. to sec 3. 4. 9 & 10

Subdivisions T. 41 S. R. 5 W. 308 17

Chains Land rolling part State
In Dinkey

East on random line
Return recs 3 & 10
Va. 16° W. E.
Gentle descent
40.00 Set temporary ¼ sec. cor.
80.18 Intersect N & S. line 22
Wes N. of cor. 6 recs 2. 3. 10 & 11
from which
N. 89° W. on true line
Return recs 3 & 10
40.09 Set charred cedar stake
4 x 4 x 4 in 12 in deep marked
¼ S on N. side trained mound
of earth from pits each 24 x
12 x 12 in for ¼ sec. cor.
80.18 The cor. to recs 3. 4. 9 & 10
Land gentle descent E.

Salt Lake Meridian

Plains Port Pate. N Timbr

North on true line
Returns secs 3 & 4
Va. 16.00 E.
Gentle descent
22.75 Wash drains E.
24.30 Road bars E & W
26.80 Main Wash drains E.
40.00 Raised mound of earth
pomt & pits each 24 x 12 x 12
in & iron charred cedar
stake in mound.
4 8 x 3 x 3 in 12 in deep
marked 1/4 S. for 1/4 sec. cor.
50.00 Gentle ascent
79.45 Intersect 8th Standard
Parallel south 8.90 chs E. of
standard cor. to secs 33 & 34
where I set
charred cedar post

Subdivisions T. 41 S. R. 5 W.

Chains 48 × 4 × 4 in 24 in deep
marked 3 notches on E&
W. edges & on S. & P.C. for
closing cor. Dec. 3 & 4
Land almost level
Soil, Slate. No Timber

On account of Brooks S.
Drum
West on true line
Returned as 1682.
Va. 16° 00' E.

40.00 Set Charred Cedar Post
48 × 4 × 4 in 12 in deep marked
¼ S. on N. side in mound of
earth raised from 4 pits
each 24 × 12 × 12 in for 40 ac. cor. 80.00

43.00 Ridge bears N. W. & S. E.

80.00 Set Limestone 15 × 10 × 8 in
10 in deep marked 4 notches

Salt Lake Meridian

chains on E. & S. edges & raised
mound of earth from 4 pits
each 24 x 12 x 12 in for cor. Dec
16. 17. 20 & 21
Land rolling Soil Rate
Timber scattering Cedar
Dec 28th 1876 J. H. Burrill

Dec 29th 1876 by J. H. Burrill
South Returns Secs 20 & 21
Va. 16° 0' E.

40.00 Pet Charred Cedar Post
4 ft x 4 x 4 in 1 2 in deep marked
15.
4 on W. side & raised mound
of earth from 4 pits each 24 x 12
x 12 in for 4 Sec. Cor.

80.00 Pet Charred Cedar Post
4 ft x 4 x 4 in 12 in deep marked
4 notches on E & S. edges in
mound of earth from 4

317 DV

Subdivisions T. 41 S. R. 5 W.

Chains	Pits each 24×12×12 in for cor	Chains
	to secs 20, 21, 28 & 29	
	Land slightly rolling	
	Soil Talus	
	Timber scattering Cedar	18.0
		40.0
	Return B cor. to secs 16, 17.	80.0
	20 & 21 N.	
	North Return secs 16 & 17	
	Va. 16.00 E.	
40.00	Drove Charred Cedar stake	
	48×3×3 in 12 in deep marked	40.0
	1/4 S. on W. side in mound of earth	
	from pits each 24×12×12 in for 1/4 sec.	
80.00	Set Gypsum 12×12×5 in 8 in	
	deep marked 4 notches on E &	80.0
	S. edges & raised mound of Gyp	
	sum for cor. to secs 8, 9, 16 & 17	
	Land undulating, Soil Talus	
	Timber scattering scrub Cedar	

Salt Lake Meridian

Chains East on random line
Returns pass 9 8 1 6
Va 16.00 E.

Ascend

18.00 Top of Ridge bears N 8 W.

40.00 Set temporary ¼ sec. cor.

80.19 Intersect N & S. line 30 lks
N. of cor. bet 9.10.1816
from which
N. 89° 47' W. on true line
Returns pass 9 8 1 6

40.10 Set Charred Cedar Post
marked ¼ S. on N. side
4 8 x 4 x 4 in 12 in deep, mound
mound of earth from pits
each 24 x 12 x 12 in for ¼ sec. cor.

80.19 The cor. bet 8.9.1817
Land rolling fair Soil
Timber scattering cedar

North Returns pass 8 8 9

314 23

Subdivisions 7, 4, 1, S. 12. S. W.

Chains	Va. 16° 00'. E.	Chains
14.00	Ridge runs E & N descend	0.1
40.00	Pet Charred Cedar Post marked + S. on N. side 48×12×12 in 12 in deep Mound of earth from 4 pits each 24×12×12 in for 4 sec cor.	13.0
		31.0
		35.0
		40.
50.00	Ridge runs N E & S W.	55.0
60.00	" " " "	80.0
80.00	Pet Limestone 14×10×10 in qin deep marked 4 notches on E & S on S. edges raised Mound of earth from 4 pits each 24×12×12 in for cor. 4 sec 4.5.8 E 9 Land undulating Arid State No Timber	48.0
	East on random line returns pace 4 E 9 Va. 16° 00'. E.	80.0

Salt Lake Meridian

Chains	
0.10	Bottom of hollow drains S.E. ascend
13.00	Ridge bears N.E. & S.W.
31.00	" " N & S.
35.00	Ravine drains N.E.
40.00	Set temporary ¼ sec cor.
55.00	Ridge bears N.W. & S.E.
80.09	Intersect N & S. line 16 lks N. of cor. to secs 3.4.9 & 10 from which N. 89° 46' W. on true line 4 trees secs 4 & 9
48.05	Set Limestone 16 x 10 x 8 in 10 in deep marked ¼ on N. side & raised mound of stone for ¼ sec. cor. on W. slope of Ridge bears N & S.
80.09	The cor. to secs 4. 5. 8 & 9 Found rolling. Oak & Yellow Pine scattering Cedar & Pine

Subdivisions T. 44 S. R. 5 W.

Chains	
	North on true line between secs 4 & 5 Va. 16° E.
21.00	Road bears E & W. pr hollow drains E.
40.00	Set Limestone 16 x 10 x 8 in 10 in deep marked + on W. side & raised mound of earth from 4 pits each 24 x 12 x 12 in for 4 cor. cor.
79.25	Intersect 8th Standard Parallel South. 8.94 chs E of Standard cor to secs 32 & 33 where I set Redsandstone 12 x 8 x 7 in 8 in deep marked 4 notches on E & 2 on W. & 6 on S. edges & C. C. raised mound of stone for closing cor to secs 4 & 5.

Cha

40.0

80.0

Salt Lake Meridian

Chains Land rolling, Soil 2d Rate
Timbr. scattering Pin & Cedar

Return to cor. to secs 20. 21. 28
& 29 & on account of brake S.
I run
West on true line
Return secs 20 & 29
Va. 16° v. E.

40.00 Set Sandstone 12 x 10 x 6 in 8 in
deep marked 1/4 on N. side
raised mound of stone for 1/4 cor.

80.00 Set Sandstone 13 x 9 x 5 in 8 in
deep marked 5 notches on
E & 2 on S. edges raised
mound of stones for cor. to
secs 19. 20. 29 & 30
Land undulating, Soil 3d Rate
Timbr scattering Cedar

3.18. 29
Subdivisions T. 41, S. R. 5. W.

Chains. North Returns secs 19 & 20

Va. 16° 00'. E.

40.00 Set Sandstone 13×8×6 in 8 in deep marked ¼ on W. side raised mound of stone for ¼ sec. cor.

65.00 Descend

80.00 Set Sandstone 20×8×3 in 15 in deep marked 5 notches on E. & S. edges for cor. to secs. 17. 18. 19 & 20.

Land undulating. Soil Fair Timber scattering Cedar

Dec 29th 1876. J. G. Burrill

Dec 30th 1876 by J. G. Burrill

East on random line

Returns secs 17 & 20

Va. 16° 00' E.

Ascend

Salt Lake Mer. Survey

chains

15.00 Enter Plateau bars N.E. & S.W.

40.00 Set temporary 1/4 sec. cor.

80.40 Intersect N. & S. line at cor. to secs 16. 17. 20 & 21 from which

West on true line

Return secs 17 & 20

40.20 Set Sandstone 14 x 8 x 5 in 9 in deep marked 1/4 on N. side raised mound of stone for 1/4 sec. cor.

80.40 The cor. to secs 17. 18. 1920

Sand undulating Dirt 1st rate Timber scattering Cedar

North on random line

Return secs 18 & 19

Va. 16° 0'. E.

33.00 E. Fork of Ruby bears N. & S.

40.00 Set temporary 1/4 sec. cor.

50.00 Ridge bears N. & S.

Subdivisions T. 41 S. R. 5 W.

Chains		
61.00	Ravine drains S. E.	
68.00	Ridge Point Pass S. E.	
74.00	Ravine drains S. E.	
78.60	Intersect Guide Merid.	
	run 34 lks N. of cor. b secs.	80.00
	18 & 19 from which	
	N. 89° 45. E on true line	
	return secs 18 & 19	
38.60	Set Sandstone 10 x 8 x 8 in	
	6 in deep marked ¼ on N.	
	side raised mound of	
	earth from pits each	
	24 x 12 x 12 in for ¼ sec. cor.	
78.60	The cor. b secs 17. 18. 19 & 20.	
	Land broken, Soil Rich	
	Timber scattering Cedar	

	37.00
North between secs 18 & 19	40.00
Va. 16° E.	79.99

40.00 Set charred Cedar

Salt Lake Meridian

Chains Post 4 8 x 12 x 12 in 12 in deep
marked 4 on N. side raised
mound of earth from 4 pits
each 24 x 12 x 12 in for 4 sec. cor.
8.00 Set Gypsum 14 x 10 x 4 in
9 in deep marked S notches
on E & 4 on S. edges raised
mound of earth from 4 pits
each 24 x 12 x 12 in for cor. to secs
T. 8. 1 7 & 18
Land level. Dri & Pate
No Timber.

East on random line
to turn secs 8 & 17
Va. 16 cor. E.

37.00 Enter Plateau, leave rolling ground
40.00 Set temporary 1/4 sec. cor.
79.90 Intersect N. S. line 23 lks
N. of cor. to secs 8. 9. 16 & 17

394 B.C.

Subdivisions T. 4 N., R. 3 W.

Chains from which

N. 89° 50' W. on true line

Return pecs 8 & 7

39.90 Chained. Cedar

Post 48 x 4 x 4 w/ 3 in deep

marked ¼ S. on N. side &

raised mound of earth

from 4 pits each 24 x 12 x 12

in for ¼ sec. cor.

79.90 The cor. to secs 7, 8, 17 & 18

Sand plateau

Soil, dry gate

Timber scattering Cedar

West on random line

Return secs 7 & 18.

Va. 16° 00' E.

22.00 E. Fork Juniper Canon

drains E. heads N.W.

40.00 Set temporary ¼ sec. cor.

Chains

45.00

77.90

37.90

77.90

24.00

BOOK-A-152

Salt Lake Meridian

Chains

10 chs S. of head of E. fork of Little Bannon

45.00 Ridge bears N & S.

77.90 Intersect Guide Merid-ian at cor. to secs 7 & 18 from which East on true line Returns secs 7 & 18

37.90 Set Sandstone 13 x 7 x 6 in 9 in deep marked 1/4 on S. side Raised Mound of earth 4 pits each 24 x 12 x 12 in for 1/4 sec. cor.

77.90 The cor. to secs 7, 8, 17 & 18 Sandrolling Soil Fair Timber scattering pine & cedar

---

North Returns secs 7 & 8 Va. 16° 00' E.

24.00 Top of Gypsum Hill

Subdivisions 27.4 33 7.41.S.R.5.W. Hal

Chains		Chains
40.00	Set Gypsum 4×4×7×6 in g in deep marked 4 on N. side raised mound of Gypsum for 4 sec. cor.	25.00
50.00	Ridge bears E & W.	35.00
65.00	Road bears E & W.	
80.00	Set Sandstone 18×8×6 in 8 in deep marked S notches on E & S. edges raised mound of earth from 4 pits each 24×12×12 in for cor. Brass S. 6. 7 8	38.24
		40.00
		45.00
		72.50
	from which	80.00
	A Pine 12 in dia bears N. 5. E. 36 lks dist. marked 7.41.S.R.5.W.S.S, B.T.	
	A Pine 15 in dia bears N. 89. W. 30 lks dist marked S.6.B.T.	40.00
	Land rolling fair Soil Sandy	
	Timber scattering Cedar	

Salt Lake Meridian

Chains East on random line
Return pecs S & S
Va. 16° 00' E.

25.00 Head of prairie drains E
35.00 Mouth of same
38.24 Road to Pony Valley bears N.E. & S.W.
40.00 In hollow drains N.E.
Set temporary 1/4 sec. cor.
45.00 Ridge bears N.E & S.W.
72.50 " " N & S.
80.00 Intersect N & S. line 26 lks N. of cor to secs 4, 5, 8 & 9 from which
N. 89° 53' W. on true line
Return pecs S & S
40.00 Set Gypsum 14 x 8 x 6 in 9 in deep marked 4 on N. side raised mound of earth from 4 pits each

Subdivisions T. 24 S. R. 5 W. 396 35 BOO

Chains	24×12×12 in for ¼ sec. cor.	Chains	c
80.00	The cor. to secs 5.6.7.8		12
	Sandstone, Pits 2 dak	77.76	7
	Timber scattering		
	Cedar & Pine		
	Set on random line		
	bearing secs 6 & 7		
	Va. 16° E.		
39.00	Ridge bears N & S.	40.00	
40.00	Set temporary ¼ sec. cor.		9
	Road 5 chs S. bears E & W.		
77.76	Intersect South side Merid-		
	ian 80 lks N. of cor. to secs		1/4
	6 & 7 from which	78.00	
	N. 89° 26' E. on true line	79.20	
	bearing secs 6 & 7		
37.76	Set Sandstone 18×12×9		
	in 12 in deep, marked ¼		
	on N. side traiond mound		

R. 5. W. Salt Lake Meridian

chains of earth from 4 pits each 24 x 12 x 12 in for 4 sec. cor.

7.76 The cor. to secs 5. 6. 7 & 8 Land rolling, soil 2nd rate Timber scattering Pine & Cedar

---

North on true line between secs 5 & 6 Var. 16° E.

40.00 Set Sandstone 14 x 10 x 6 in 9 in deep marked 1/4 on W. side raised mound of earth from 4 pits each 24 x 12 x 12 in for 1/4 sec. cor.

68.00 Hollow drains S. E.

79.20 Intersect 8th Standard Parallel North 9.14 chs E. of standard cor. to secs 31 & 32 Where I set Charred Cedar Post

4 8 x 4 x 4 in 12 in deep
marked S notches on E. &
W. 6 on S. edges T.C. for clo
sing cor. 6 secs 3 & 6. in pate
of Oak Brush -
Land broken, Ariz Dat
Timber scattering Cedar &
Dec 30th 1876 J. G. Burrill

General Description

The land in this township
is good grazing land & as coa
is found in the one adjoinin
formation bring simila
it is presumed there is coa
in this township. Return
all as coal land except
the following which are
returned as by resurv
N. W. 1/4 of S. W 1/4. S. 8 - N. E. 1/4

Salt Lake Meridian

of Sec 7.- S.E. 1/4 of N.W. 1/4 - S 1/2 of N.E. 1/4 - E 1/2 of S.W. 1/4 & the S.E. 1/4 of Sec 12 - E 1/2 of N.W. 1/4 - & N.E. 1/4 Sec 13 Lots 1 & 2, S 1/2 of N.E. 1/4 & S.E. 1/4 Sec 1.

330

U. S. S

Salt L

The fo

Subd

Townsh

Execut

Under

day of

Dec

exami

plana

surve

331

BOOK-A-152

U. S. SURVEYOR GENERAL'S OFFICE.

Salt Lake City, Utah, April 3rd 1877

The foregoing field notes of the survey of the Subdivision lines of

Township No. 41 S *Range No.* 5 East

Executed by Bailey & Burrell

Under this joint *contract of the* 4

day of September *1876, in the month of* December *1876, having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.*

Nathan Kimball

Surveyor General for Utah.

BOOK-A-152

Township 41 South **R.** 6 West



BOOK-A-152

Township 41 South **R.** 6 West



BOOK-A-152

Examined by J. H. Cardwell 1st. 6.

Field Notes,

of

the Survey of the Subdivision lines

of,

Township 41 S. Range 6 West,

of,

the Salt Lake Meridian,

Utah Territory

By,

T. C. Bailey & J. G. Burrill,

Under their Joint Contract,

No. 71.

Dated Sept. 4th 1876.

Survey Commenced Dec. 30th 1876.

Survey Completed. Jany 1st 1877.

Township 41 S. R. 6 West



BOOK-A-152

Subdivisions of Sec. 4 T. 41 S. R. 6 W. 351
Salt Lake Meridian

chains,

December 30th 1876,

By. T. C. Bailey

Note,

It being impracticable on account of the broken nature of the ground to survey the Southern portion of this township, I began at the Cor. to Secs. 13 & 24, on the Panguitch & Kanab State Road,

West on true line between Secs. 13, & 24,

Var. 16° E.

31,00 Descend,

34,50 Ravine drains S. W. 20 chs, then S. E.

44,00 Set Limestone 14×10×5 ins, 9 in. deep, marked 1/4 on N. side, traced mound

1
7
12
5
13
1
24
6
25
36

1936 2

Subdivisions 2, 11, 1 S. R. 6 W.

Chains		Chains
23,00	Pof of slope	
53,50	Ravine drains S,	96,
78,50	" " S.W.	"
80,00	Set Limestone 20x10x6in 10in. deep, noteched 1 on E & S, edges, & raised mound of stones for Cor. to Secs. 13, 14, 23 & 24, Land undulating Soil 2nd rate, Timber, Scattering Cedars,	80,

South between Secs, 23 & 24
Var, 16° E.

4,00	Ravine drains S.E,
40,00	In hollow drains S.E Set Limestone 12x8x6in, 8in. deep, meseled 1/4 on

BOOK-A-152 (5) 207

Jackrabbit Meridian

Chains	
	W, side, mound of stones for 1/4 Sec, Cor,
76,00	Head of W, fork of Guide Canon drains S. E,
80,00	Set chained Oak stake 48, X4X4 in, 24 in, deep, notched 1 on E, & 2 on S, edges mound of Earth from 4 pits each 24X12X12 ins for Cor, to Secs 23, 24, 25 & 26,
	Land broken
	Soil Gravelly,
	Timber, burned Cedar Pine & Oak,

Note; The line East entering impassable breaks in less than 80,00 Chs, Drum, East on true line

Subdivisions Sec. 24 T. 6 N. R. 6 W.

Chains, between Secs. 24 & 25,
Var. 16° E.

10.00 East fork of Guide
Canon bears S. E.,

40.00 Set Charred Cedar post
4"x4"x4' 24" deep,
marked 1/4 on N. side of
mound of earth
from 4 pits each 24"x12"x
12", for 1/4 Sec. Cor.
Note: I abandon this here,
Land broken,
Soil 2nd rate,
Timber, brush cedar pine & oak.

Return to the Cor. to Secs.
13, 14, 23 & 24 & run,
North between Secs. 13 & 14,
Var. 16° E.

BOOK-A-152

Salt Lake Meridian 3 S 3 W

Chains
40,00 Set limestone 18x10x5 in, 12 in, deep, marked 1/4 on S, side & raised mound of earth from 4 pits each 24x12x12 in, for 1/4 Sec, Cor,

8,00 Set Shaved Oak stake 48x4x4 in, 24 in, deep notched 1 on E, & 4 on S, edges & raised mound of earth from 4 pits each 24x12x12 in, for Cor, to Secs, 11, 12, 13 & 14

Land level,
Soil Pirate,
Timber,

East on random line between Secs, 12 & 13,
Var, 16° E,

6,50 Meets drains N. E,

340 6

Subdivisions 2f. 4, T. 8 S. R. 6 W.

Chains	
10,00	Rolled drains N. W.
4,00	Set temporary 1/4 Sec. Cor,
79,60	Intersect Guide Meridian 95 lks. N. of Cor. to Secs, 7, 12, 13 & 18, from which, N. 89° 19, W. on true line between Secs, 12 & 13,
39,80	Set Gypsum 13x12x6 in, 9in. deep, marked 1/4 on N. side of raised mound of earth from 4 pits, each 24x12x12 in, for 1/4 Sec. Cor,
79,60	The cor. to Secs, 11, 12, 13 & 14, Land undulating Soil Pt rate, No Timber,

---

North between Secs, 11 & 12, Run, 16 Ch.

Chains
40,00

Salt Lake Meridian

Chains, 40,00	Set charred cedar post 4/8x4x4 ins, 24 ins, above, marked 1/4 on N. side & raised mound of earth from 4 pits each 24x12x12 ins, for 1/4 Sec. Cor.
80,00	Set limestone 18x12x3 ins, 12 ins. above ground, notched 1 on E, & 5 on S, edges & raised mound of earth from 4 pits each 24x12x12 ins, for Cor. to Secs. 1, 2, 11 & 12,
	Land undulating,
	Soil 1st rate
	No timber,

East on random line between Secs. 1 & 12,

Var. 16° E.

Subdivisions 9, 4, 8 S. R. 6 W.

Chains.	
40,00	Set temporary 1/4 Sec. Cor.
78,00	Road to Long Valley bears N. W. & S. E.
80,00	Intersect Guide Meridian at Cor. to Secs. 1 & 12, from which, West on true line between Secs. 1 & 12,
4,00	Set Sandstone 12 x 10 x 8 ins. 8 ins. deep, marked 1/4 on N. side, & raised mound of earth from 4 pits each 2 x 12 x 12 ins. for 1/4 Sec. Cor.
8,00	The Cor. to Secs. 1, 2, 11 & 12, Land rolling Soil Private, No Timber.

Chains

6,0

24,

44,

49,

Chains	
	North on true line between Secs, 1 & 2.
	Var, 16° E,
6,00	Wash draws N,
24,00	Ridge bears E. & W,
	Set Sandstone 16×12×24 in, 10 in, deep, marked 1/4 on N, side, & raised mound of earth from 4 pits, each 24×12×12 in, for 1/4 Sec, Cor,
44,00	Long Valley road bears N. 70° E,
79,30	Intersect Std. Standard North 11,45 chs, East of Standard Cor, to Secs, 35 & 36, where I set a Sandstone 18×12×4 in, 12 in, deep, notched 1 on E, 5 on W, & C on S. edges, & C.C, for closing Corner to Secs, 1 & 2,

344 10

Subdivisions Ty. 41 S. R. 6 W.

Chains

Land rolling
Soil 2nd rate,
No Timber.

From the Cor. to Secs. 23,
24, 25 & 26, down,
West on true line
between Secs, 25 & 26,
Van 16° E,

40,00 Set charred Oak post, 4 x
4 x 4 in, 24 in. deep, marked
1/4 on N. side & raised
mound of Earth from 4
pits, each 24 x 12 x 12 in for
1/4 Sec. Cor,

80,00 Set Charred Oak post, 4 x
4 x 4 in, 24 in. deep, notched
2 on E. & S. edges, & raised
mound of Earth from 4 pits
each 24 x 12 x 12 in, for Cor. to

30,0

40,0

Salt Lake Meridian

Chains

Secs, 22, 23, 26, & 27,
Land undulating,
Soil 1st rate,
No Timber,

South between Secs, 26 & 27,
Twp. 16° E.,

30,00 Rock knobs,

40,00 Falling in knobs at 30, chs.
Set Charred Oak stake 48
x 4 x 4 in, 24 in, deep marked
1/4 M. C, on N, side raised
mound of earth from 4 pits
24 x 12 x 12 in, for Witness 1/4
Sec. Cor,
Note; I abandon line here,
Land level,
Soil 2nd rate,
No Timber,

Chains, Line West reaching Canon breaks in less than 80 chs,
I run,
West on true line
between Secs, 22 & 24,
Var, 16° E,
30,50 Canon breaks,
40,00 Point for 1/4 Sec Cor, falling in rocky breaks cannot be established therefore at, 30.00 chs, Set charred Cedar post, 48 x 4 x 4 in, 24 in. deep, marked 1/4 S. 40,00
W.C, & raised mound of earth from 4 pits each 24 x 12 x 12 in, for witness 1/4 Sec, Cor,
Note; I abandon line here, 42,
Land level, 44,
Pine Ridge, 80,

Salt Lake Meridian 13 347

Chains | Timber, scattering Cedar,
December, 30th 1874,
T. C. Bailey.

January 1st 1875,
By J. G. Bimble,
From the Cor. to Secs, 22, 23,
26, & 27, T 1 N,
North between Secs,
22 & 23,
Var, 16° E,

24,00 Set limestone 24 x 10 x 4 in,
Pits, dug, marked 1/4 on
N. side & raised mound
of earth from 4 pits, each
24 x 12 x 12 in, for 1/4 Sec, Cor,
42,50 Head of hollow drains N, W,
94,00 Hollow drains W,
80,00 Set limestone 20 x 6 x 5 in,

15 in. deep, notched 2 on E, & 3 on S, edges & ranid mound of earth from 4 pits Each 24×12×12 in. for Cor, to Secs, 14, 15, 22, & 23, Land undulating, Soil Sandy, Timber, Scattering Cedars. Chains, 4,30 80,59

East on random line between Secs, 14 & 23, Var. 16° E,

40,00 Set temporary 1/4 Sec. Cor,
65,00 Leave plateau,
76,34 Ravine Draws S. E,
80,59 Intersect N. & S. line 33 lks, S. of Cor, to Secs, 13, 14, 23 & 24, from which,
S. 89° 46' W. on true line 40,00

Chains,	
	between Secs, 14 & 23,
4,30	Set limestone 26,x5x5 in, 18 in, deep, marked 1/4 on N, side & raised mound of earth from 4 pits each 24x12x12 in, for 1/4 Sec, Cor,
80,54	The cor, to Secs, ~~13, 14, 23 & 24~~ 14. 15. 22 & 23, Land mostly level, Soil Sandy, No Timber,

It being impossible to establish the cor, to Secs, 15, 16, 21 & 22, from the South, Iron, West on true line between Secs, 15 & 22, Van, 16° E,

40,00	Set Sandstone 11x8x4 in,

Subdivisions of T. 41 S. R. 6 W.

Chains	Dees, marked 1/4 on N. side	Chains
	mound of earth	
	from 4 pits each 24 x 12 x 12	
	in, for 1/4 Sec. Cor,	
80,00	Set Charred Oak post,	
	48 x 4 x 4 in, 24 in, deep,	80,00
	notched 3 on E. & S. edges,	
	mound of earth	
	from 4 pits, each 24 x 12 x 12	
	in, for Cor, to Secs, 15, 16, 21, & 22,	
	Land slightly undulating,	
	Soil 1st rate,	
	Timber, Scattering Cedars,	
	From the Cor, to Secs, 14, 15	
	22, & 23, Drain,	
	North between Secs, 14 & 15,	34,2
	Var, 16° E,	40,00
40,00	Set Charred Oak stake,	45,2

Salt Lake Meridian.

Chains 4 8x4x4 in, 24 in dep marked 1/4 on N. side raised Mound of earth from 4 pits each 24x12x12 in, for 1/4 Sec. Cor,

80,00 Set charred Oak post, 4 8x4x4 in, 24 in. dep, notched 2 on E, & 4 on S, edges for Cor, to Secs, 10, 11, 14, & 15,

Land undulating,
Soil Sandy,
Timber, Scattering Cedars,

Bart on random line between Secs, 11 & 14
Var, 16° E,

34,25 Ridge bears N. & S,
40,00 Set temporary 1/4 Sec, Cor,
45,25 Ravine bears N. W.

Subdivisions Tp. 41 S. R. 6 W.

Chains.		Chains
74.15	Ridge bears N. & S.,	
80.65	Intersect N. & S line 54 lks, E. of Cor. to Secs. 11, 12, 13, & 14	40.00
	from which,	
	S. 89° 37' W. on true line between Secs. 11 & 14,	
40.33	Set sandstone 14 x 10 x 6 in., 9 in. deep, marked 1/4 on S. side, raised mound of earth	
	from 4 pits, each 24 x 12 x 12 in.	
	for 1/4 Sec. Cor.,	
80.65	The Cor. to Secs. 10, 11, 14, & 15,	
	Land rolling,	
	Soil 2nd rate,	
	No Timber,	

Note, The line West reaching Canon breaks miles than 80.00 chs. Iron, West on true line

40.00

Salt Lake Meridian

Chains, between Secs, 10 & 15,
Var, 16° E,

40,00 Set Sandstone 10x8x4 ins,
Chs, deep, marked 1/4 on N,
pile of rocks mound of
stone for 1/4 Sec, Cor,
Note, I abandon line here,
Land nearly level
Soil Private,
No Timber,

From the Cor, to Secs, 10, 11,
14 & 15, I run,
North between Secs, 10 & 11,
Var, 16° E,

40,00 Set charred cedar post,
4 8x4x4 ins, 24 ins, deep, marked
1/4 S, on N, side of raised
mound of earth from 4 pits

Subdivisions of Sec. 4 T. 6 N.

Chains, each 24×12×12 ins, for ¼ Sec, Cor,

Do, do Sandstone 20×12×8 ins, 10 ins, deep, notched 2 on E, & S on W, edges, & raised mound of earth from 4 pits, each 24×12×12 ins, for Cor, to Secs, 2, 3, 10 & 11,

Land undulating,

Soil 1st rate,

do timber,

Each on random line between Secs, 2 & 11,

Var, 16° E,

40,00 Set temporary ¼ Sec, Cor,

Do, 04 Intersect N, & S, line 21 lks, S, of Cor, to Secs, 1, 2, 11 & 12, from which,

Chains,

40,04

Do, 04

39,20

40,00

Chains, S, 89° 42' W, on true line
between Secs. 2 & 11,
40.04 Set limestone 15 x 8 x 5 in,
10 in, deep, marked 1/4 on
N, side & raised mound of
stones, for 1/4 Sec, Cor,
80.07 The Cor, to Secs, 2. 3. 10 & 11,
Lund level,
Ord ground,
No, timber,

North on true line
between Secs, 2 & 3,
Var, 16° E,
39.25 Hollow Arans N.E,
40.00 Set limestone 15 x 11 x 8 in,
10 in, deep, marked 1/4 on
N, side, raised mound
of stone for 1/4 Sec, Cor,

Chains
52,50 Hollow draws N.W.
70,00 Descend,
75,50 Enter Kanab Creek bottom
bears N.E. & S.W.
76,80 Kanab Creek runs S.W.
80,00 Intersect 8th Standard
Parallel South, 11.20 chs.
E. of Standard Cor. to Secs.
34 & 35, where Set,
Sandstone 14×12×24 in.
Pit, dep, notched 2 on
E, 4 on W, & 6 on S. edges,
& C.C. for closing Cor. to
Secs. 2 & 3,
Land mostly level,
Soil 1st rate,
Timber, scattering Cedar,
Note: The portion lying
West of Kanab Creek
Canon, I leave unsurveyed

Sacramento Meridian

on account of the extreme severity of the weather,

January 1st 1894,

J. G. Burrill,

General Description

The surveyed portion of this Twp, consists of fine grazing lands, The Township North Containing coal, & similar rock formations obtaining here, it is presumable that the whole of the Township contains coal measure, although no outcroppings were observed during the progress of the Survey, the faces being mostly covered by debris,

I therefore return all as coal land. J. G. Burrill

358 24

as examined

J. G. Burrill,

U. S. Deputy Surveyor,

BOOK-A-152

337

U. S. SURVEYOR GENERAL'S OFFICE.

Salt Lake City, Utah, April 3rd *187*7

The foregoing field notes of the survey of the Subdivision Lines of *Township No.* 4 S. *Range No.* 6 W. *Executed by* Bailey & Burrell *Under* their Joint *contract of the* 4 *day of* September *187*6, *in the month of* Dec & Jany *187*6-7, *having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.*

Nathan Kimball

Surveyor General for Utah.

BOOK-A-152

16 Box C/K C

12, 5

Descriptive Lots Made

Examined by C. H. Cramwell. C. C.

Field Notes

of

The Survey of the,

Long Valley Guide Meridian,

in,

Township 41 S. Ranges 7 & 8 West,

of

The Salt Lake Meridian

Utah Territory,

By,

T. C. Bailey,

Under Joint Contract of Bailey & Burrill.

No 71,

dated Sept 4th 1896,

Survey Commenced, Dec 29th 1896,

Survey Completed Dec. 29th 1896,

50

BOOK-A-152

Township [illegible] R. [illegible]



BOOK-A-152



BOOK-A-152

Long Valley Guide Meridian, West
Of. 41 S. Cor. Rs. 7 & 8 W. S. L. M.

Surveyed Dec, 29th 1876,
By T. C. Bailey.

From the Standard Cor,
to Of. 40 S, Rs. 7 & 8 W, set
by me today, I run,
East, 16, 80 chs for convergency
of Meridian to a point on
the 8th Standard South,
where I set a Sand stone
20 x 14 x 5 in, 15 in, deep, marked
6 notches on the E, W, & S, edges,
Mound of stones
for closing cor, to T. 41, S, R,
7 & 8 W, from which,
A pine 12 in, dia, bears S.
60 W, 40 lks, dist, marked
S, 1 T. 41, S. R 8 W, B. T,
A pine 8 in, dia, bears S. 30 E,
45 lks, dist, marked S. 6.
R. 7 W. B. T. Thence,

Long Valley Guide Meridian W. 41 S.

Chains	
	Sec's bet. Secs, 1 & 6, in T. 41 S. R. 7 & 8 W, Var. 16° E,
20,00	Descend S. E. slope
25,00	Enter flat bears N.E. & S.W.
30,50	Road bears S.W. & N.E.
31,00	Leave flat & ascend N.W. slope
40,00	On Nest slope of hills, Set Sandstone 24×11×6 ins, 18 ins, deep, marked 1/4 on W. side & raised mound of stones for 1/4 Sec. Cor. from which, A double pine 15 in. dia, bears N. 10 W, 60 lks, dist, marked 1/4 S. B.T.
60,00	Indications of coal, Low hills & Enter flat, bears N.W. & S.E.
70,00	Road bears N.W. & S.E.
74,00	Muddy Creek. 10 lks. wide

Bet. Rs. 7 & 8 W. Salt Lake Meridian,

Chains runs S. E.,

75,50 Same creek runs S. W.,

78,50 " " " S. E.,

80,00 Set sandstone 15 x 15 x 2 in., 10 in. deep, marked 1 notch on N. & S. on E. edges and mound of stones for Cor. to Secs. 1, 6, 7 & 12, from which,

A Cottonwood 15 in. dia., bears N. 12 E. 25 lks. dist., marked S. 6 T. 4 1 S., R. 7 W. S. L.

Land broken & level flat,

Soil 1st & 2nd Rate,

Timber pine & cedar, of

Commercial Value,

South bet. Secs. 7 & 12,

Var. 16° E.

Long Valley Guide Meridian, Ts. 41 S.

Chains The line being impracticable in place, I offset East, 20 chs, thence South on Offset line, 80,00 chs, thence West 20,00 chs, to

80,00 On true line where I set Sandstone 16x10x5 in, 11 in, deep, marked 2 notches on N, & 4 on S, edges, & mound of stone for cr, to secs, 7, 12, 13 & 18, near top of Red ridge bears N, & S, from which,

Aspen 10 in, dia, bears S 15 E, 30 lks, dist, marked S, 18, T. 41 S, R, 7 W, B.T,

Aspen 8 in, dia, bears N. 65 E, 60 lks, dist, marked S, W, B.T,

Land broken & hilly,

Twp. Rs. 7 & 8 W. Salt Lake Meridian.

Chaining Soil 2nd rate,
Timber, Pine & Cedar of
Commercial Value,
Note, The ¼ Sec. Cor. falling
in broken hills is not
established

South bet. Secs. 13, & 18,
Var. 16° E,
The line being impracticable
in place, Offset East
34.76 chs, thence South on
Offset line, which, passing
through cultivated field,
I note the topography thereon,
0.50 chs, Road N.W. & S.E,
3.00 " Fence bears N.W. & S.E,
Enter cultivated field,
34.00 chs, Muddy creek 10 lks

Long Valley Guide Meridian N. 41 S.

Chains, wide rivers S, E, of stone bears West about 2.00 chs dist, [illegible]

4,00 chs, Center of Sec, 18, and 4,00 chs West of East foot of Gypsum hills, at West edge of field bears N.W. & S.E.

55,00 chs, Leave field & Enter Gypsum hills, bears N.W. & S.E. 8,00 to point on line between Secs, 18 & 19 thence West, 34,76 chs, to,

8,00 on true line, Set sandstone 15 x 10 x 5½ in, 10 in, deep, marked 3 notches on N & S, edges, & raised mound of stones for Cor to Secs, 13, 18, 19 & 24,

Chains,

bet. Rs. 7 & 8 W. Salt Lake Meridian

Chains, Land on true line broken & hilly, Soil 2nd rate, Timber pine & cedar of Commercial Value,

Land on Offset line N. 55 chs, Cultivated fields, Soil 1st rate, Balance hilly, Soil 2nd rate,

---

South bet. Secs. 19 & 24, Var. 16° E,

The line being impracticable in place, I offset East, 34.76 chs, thence South on Offset line & note topography thereon,

8,00 chs, County road S. W,
10,00 " " " S. E,
10,50 " E, point of Gypsum hills,
11.00 " County road S. W,
12,00 Muddy creek rocks,

Long Valley Salt Lake Meridian. T. 41 S.

chains, wide runs S.W.,
Enter field, bank
of creek forms the fence,
18.50, Chs, Rio Virgin 20 lks
wide runs S. W.,
25,00 " Wash draws W.,
31.00 " Dry Creek bed S.W.,
57.00 " West slope of bluff
bare field,
63,00 " Wash draws S. W.,
75,00 " Corner, thence
West, 3.76, to true
line on West boundary. Thence
South, 5.00 chs to
80,00 Set piece of Gypsum 14 x
10 x 5 in, Qtz, dec, marked
4 notches on N. & 2 on S.
edges, & raised mound of
stones, for Cor. to Secs, 19, 24,
25, & 30, in small flat,

BOOK-A-152

Tp. 4 S. R. 7 & 8 W. Salt Lake Meridian

Adams, Note; The 1/4 Sec. Cor. falling in the broken bluffs, is not established,

The line further South is impracticable,

Dec. 29th 1876,

T. C. Bailey,

General Description,

T. 4 S. R. 8 W. is broken & unfit for Cultivation,

T. 4 S. R. 7 W. will be, described at end of Sub, div. notes of that Dp,

---

37X

U. S

Sc

Th

L

Tow

Exe

Uno

day

A

exa

pla

sur

375

BOOK-A-15

U. S. SURVEYOR GENERAL'S OFFICE.

Salt Lake City, Utah, April 3 1877

The foregoing field notes of the survey of Long Valley Guide Meridian

Township No. 41 S. *Ranges No.* 7 & 8 W.

Executed by J. C. Bailey

Under his final contract of the 4th

day of September 187 6, *in the month of*

Dec. 187 6, *having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.*

Graham Kimball

Surveyor General for Utah.



BOOK-A-152

Examined by C. H. Lindsell C. C.

Field Notes,

of

The Survey of the,

Subdivision lines

of,

Township 41 South, Range 7 West,

of

The Salt Lake Meridian

Utah Territory.

By F. C. Bailey,

Under Joint Contract of Bailey & Daniels

No. 41,

dated Sept 4th 1896.

Survey Commenced Dec, 30th 1896

" Completed January 1st 1897

BOOK-A-152

Township 41 South **R.** 7 West



BOOK A-152

Subdivisions of T. 4 S. R. 7 West,
Salt Lake Meridian. 346

Chains, December 30th 1876,
By J. C. Bailey,
From the Standard Cor. to Secs,
34 & 35, Run, East, S. N.
13,44, To Iron Pin on S. Standard
South, to allow for Convergency
of Meridian, where I set Long
Sandstone 15x10x6 ins, 10 ins, Line
deep, marked 2 Notches on E, Bet,
& on S, 04 on W, edges, for N
Closing Cor. to Secs, 2 & 3, T. 4 S, of
R. 4 W, Thence, Cor,
South bet. Secs. 2 & 3,
Var. 16° E, 30
9,00 Raise Irons N. W, W. C.
40,00 Set Sandstone 14x10x4 ins, imp=
9 ins. deep, marked 1/4 on W, 45'
side, & raised mound of Ls,
Stones for 1/4 Sec. Cor,
Note: Abandon line here, D

353/4

2

Subdivisions T. 41 S. R. 4 W.

Chains Land broken,
Soil 2nd rate,
Timber, Pine & Cedar,

To Allow for convergency of Meridians, at a point 13,44 Chs, E., of the Standard Cor, point to Secs, 33 & 34 on the 8th Standard South, Set a Sandstone 16x12x5 in, 11 in, deep, marked 3 notches on E & W, & 6 on Sides, for closing Cor, to Secs, 3 & 4, T. 41 S, R. 4 W, from which, Acottonwood 30 in. dia, bears S. 35 W, 80 Lks. dist, marked S, 4, S, 41, S, R, 4

BOOK-A-152

13

554½

Salt Lake Meridian,

Chains

N, B.T, thence Down,
Sects bet. Secs. 3 & 4,
Van, 16° E,

1,50 Rio Virgen, 15 lks. wide runs S.W,
3,50 County road bears N.E, & S.W,
9,50 Small wash drains S.W,
10,00 Foot of bluff on E. side of long
Valley, bears N.E, & S.W, where
I set a Sandstone 24 & 15 & 8 ins,
18 ins, deep, marked 1/4 M.C, on
N. side & raised mound of
stones for Witness 1/4 Sec, Cor,
from which,
Cedar 14 ins, dia, bears S. 30
W, 55 lks, dist, marked 1/4 M.C,
B.T,
The line in place becoming impr-
acticable, I run run S, 46, 45'
W, 10.2,06 chs, to point 40 chs,
S, & W 4.27 chs, West of the

2383 3/4 4

Subdivision Sec. 4, T. 5 S. R. 4 W.

Chains, above Witness Cor, which latitude of 0.0 chs, added to 10 chs, the distance run from the closing to the Witness Cor, on true line gives,

Set a, 0.0 Point for true Cor, to Secs, 3, 4, ~~10.00~~ 10.01, which falling in the rocky bluffs, is not established

Land on true line broken & rocky,

Soil 2nd rate,

Timber Pine & Cedar,

The Township line runs through the Center of King Valley, on which the soil is 1st rate, Cultivated fields,

Chains

69.

B

%

Salt Lake Meridian

Chains.

West on true line bet.
Secs, 4 & 9
Var, 16° E.

69.27 Point reached by measuring East, 5,00 chs, from the intersection of the traverse line in Sec, 4, with the line bet. Secs, 4 & 9, where I set a Sandstone 18x11x4 ins, 12 ins, deep, marked 1/4 M. C, on N, side ▽ raised mound of stones for witness 1/4 Sec. Cor, from which, Cedar 5 ins, dia, bears East, 6 lks, dist, marked 1/4 S, W. C, B. T, At this point, 20 lks West of ditch runs S, enter cultivated field at foot of hills bears N, & S,
75.94 Rio Virgen 15 lks wide

Subdivisions Sec. 4, T. 8 S., R. 7 W.

Chains, 15 in. deep, runs S.,

80,00 Set Sandstone 28 x 14 x 3 ins
2 ins. deep, marked 5 Notches
on S. & 4 on E. edges, & raised
mound of earth from 4
pits, each 24 x 12 x 12 ins, for
Cor. to Secs. 4, 5, 8 & 9,
Land E. 40 chs broken,
Soil 2nd rate,
Balance, level prairie,
Soil 1st rate,
Timber, pine & cedar on E. part,

North on true line 1 ch,
Secs. 4 & 5,
Var. 16° E.,

5,50 Ditch runs S. E.,
28,00 " " S. W.,

Salt Lake Meridian

Chains	
30,20	County Road bears S. W. & N. E.
	& leave field,
40,00	Set Sandstone 12x10x4 in, 8 in,
	deep, marked 1/4 on W. side, &
	raised mound of stones for 1/4
	Sec. Cor, from which,
	A cedar, (double) 5 in. dia, bears
	N. 15° E, 28 lks. dist, marked
	1/4. S. B. T. at foot of hills, bears
	N. E, & S. W. to avoid which I offset
	E, 20,00 chs. to point, from which
	the S. W. cor. of Orderville
	Dining hall, bears N. 45, E,
	22,40 chs. dist, from which Cor,
	of the hall, I take the following
	Notes,
	The S. W. cor. of "Head Quarters,"
	House bears S, 46° E, 300 lks,
	Carpenter Shop, School House,
	Blacksmith Shop, Weaving

Subdivisions of 4 South Range 7

Rooms, &c. all under one roof, bears E, 480 lks, on E, side of street, bears N. & S, — N. side of street 375 lks, S, bears E. & W.; S. E. corner of row of dwellings bears S, 62 ½, 220 lks.; East side of the West street, 311 lks. dist, bears N. & S.; South side of Middle street 556 lks, North bears E. & W. dividing the two blocks, Embracing the town of Orderville, with a population of 350 All living under & by the rules of the "United Order," a religious branch of Mormons, organized under the Auspices of the Church of Jesus Christ of Latter Day Saints,

BOOK-A-152

N. Salt Lake Meridian

Claims, Howard O. Spencer & Bateman H. Williams are the headmen, From the point 20 chs E. of the 1/4 Sec. Cor. I run N. on Offset line 30 Chs, to a pint 10 chs, South & 20 chs East of Point on 8th Standard Parallel South, 13.44 chs. E. of pint for Standard Cor, to Secs, 32 & 33. T. 40 S, R. 4 W, where the closing Cor. to Secs, 4 & 5, T. 41 S, R. 4 W falling in the rocky bluff is not established, therefore at the point 24.00 chs. E. & 10 chs S, of pint for the closing Cor, I set sandstone 22 x 14 x 5 in 16 in. deep, marked 4 notches on E, 2 on W, & 6 in Sedges, W.B. for witness Closing

80.00

388 10

Subdivisions of 41 S. R. 7 W.

Cor. to Secs. 4 & 5, T. 41 S., R. 7 W., on N. side of Ravine, drains S.E., from which Cor. Cedar, 3 in. dia. bears S. 20 E., 45 lks; dist. marked S. 4 B.T.

Cedar 9 in. dia. bears S. 3 W., 95 lks. dist marked S. 4 T. 41 S. R. 7 W. B.T.

Land S½, level, 1st rate, N½ broken hills, 2nd 2nd rate,

Timber, Scattering Pino Cedar,

From the Cor. to Secs. 4, 5, 8 & 9, Iron. [illegible]

BOOK-A-152

Tuolumne Meridian,

South on true line
bet. Secs. 8 & 9,
Var. 16° E,

Do avoid the hills Offset
West, 40 chs, thence South,
on Offset line & gives topography,
in Sec. 8,

28,00 chs, Road bears S. E. & N. W.
& bears fixed,
28,50 " Ditch drains S. E.
30,00 " Top of E point of ridge,
35,25 " County road bears
N. E. & S. W.
35,50 " Fence bears N. E. & S. W.
Enter fixed,
37,50 " J. M. Reeds house
bears W. 250 lks. dist,
40,00 " Center of Sec. 8,
44,50 " Ditch drains S. W.
45,00 " Wm Jolleys house

3/10 12

Subdivision N. 41 S. R. 7 W.

in "Fiddlers Green,"

Char

bears N. 85 W. about 6.

Chs. dist. Ref. Jolleys

House bears S. 77. W

about 6. chs. dist. on W.

side of County road,

Saw Mill bears S. 30 W.

60.00 Chs. Rio Virgen 15 lks. wide

runs S.W.

6.50 chs. Ditch drains S.W.

71.00 " Road bears N.E. & S.W.

73.00 " Same ditch drains S.E.

75.00 " Wash drains S.W.

80.00 " To point from which

Saw Mill, bears N. 57 W.

thence East.

40.00 " to,

80.00 Mark Sandstone to place

4 x 2 x 1 ft above ground, 4

Notches on E. & S. edges.

Salt Lake Meridian.

Chains, raised mound of stones for Cor. to Secs. 8, 9, 16 & 17, from which, Juniper Tree, dia bears S. 45 E. 70 lks. dist, marked S. 16. T. 41 S. R. 7 W. B. T.,
Cedar Tree, dia. bears N. 75 E. 60 lks. dist, marked S. 9 B. T. Coal Vein bears N. E. about 10. lks dist. on bank of a ravine, drains N. W.
Land on this line broken & hilly. Soil Dry rate with Juniper & cedar timber.
Land on the Offset line Cultivated fields,
Soil 1st rate,
No timber,
Note; The 1/4 Sec. Cor. falling in the hills is not established.

Subdivisions 2p. 41, S. R. 7 W.

Chains

East on true line bet.
Secs. 9 & 16.
Var. 16° E.

6,00 Ravine drains N. W.

40,00 Set Sandstone 15x10x5 in,
10 in. deep, marked 1/4 on
N. side & raised mound
Stones for 1/4 Sec. Cor.
Land broken, Dry Gulch,
Timber, Pine & Cedar,
Note: I abandon the
line here.

South bet. Secs. 16 & 17.
Var. 16° E.

40,00 Set Sandstone 15x10x4 in,
10 in. deep, marked 1/4 on N.

BOOK-A-152

15 398

Fairbanks Meridian

Chains, pcds, raised mound of stones for 1/4 Sec. Cor,

80,00 Set Sandstone 16x17x4 in, 11 in, deep, marked 4 notches on E, & 3 on S, edges, raised mound of stones, for Cor, to Secs, 16. 17. 20 & 21,

Land broken,
Soil 2nd rate,
Timber, Pine & Cedar,

Azimuth true line Set,
Secs. 17 & 20,
Var. 16° E.

40,00 Set Sandstone 20x10x5 in, 15 in. deep marked 1/4 on N. side, & raised mound of stones for 1/4 Sec. Cor.

3/4 16

Subdivisions of T. 41 S. R. 7 W.

~~Chains~~ ~~50,00~~	Rush in Ravine bears S. W.	Char
50,00	Same " " " N. W.	
58,50	" " " " S. W.	
71,25	Ridge bears N. E. & S. W.	
80,00	Near foot of bluff bears N. E. & S. W. Set Sandstone 16x10x4 in. 11 in. deep, marked Notches on E. & W. sides, raised mound of stones, for Cor. to Secs. 17, 18, 19 & 20, from which, A cedar 20 in. dia. bears N. 30 E. 128 lks. dist. marked S. 19, T. 41, S. R. 7 W. B.T.	80,

---

South bet. Secs. 19 & 20.
Var. 16° E.

BOOK-A-152

Salt Lake Meridian

	Chains,	Down the broken hills Offset West 40 chs. to Spirit thence South, on Offset line,
	80,00	80,00 chs. to Spirit on line bet, Secs. 19, & 30, thence East 40,00 chs. to Set Sandstone 15"x4"x6" in, 10 in, deep, marked 3 Notches on E, & 2 on S. Edges mound of stones for Cor, to Secs, 19, 20, 29 & 30,
		Land broken, Soil 2nd rate, Timber, Pine & Cedar,
		Note, The 1/4 Sec. Cor, falling in the hills is not established,
		Dec. 30th 1876.

356 18

Subdivision No. 41 S. R. 7 W.

Chains,	January 1st 1896 –	Chains
	First random line	
	Set Secs 19 & 30,	
	Var. 16° E,	
35,00	Ravine bears N. W.	
40,00	Set temporary 1/4 Sec. Cor,	77,84
60,00	Foot of hills Enter flat,	
69,00	Virgin River runs S,	
73,00	County road bears N. & S,	
77.84	Intersect Guide Meridian	
	7 lks. N. of Cor, to Secs, 19, & 30,	
	from which,	
	A, 89° 45' E, on true line	
	Set, Secs, 19 & 30,	
3.84,	Mark a limestone 4 x 2 1/2 x 1 1/2 ft, above ground,	
	1/4 on N, side, & raised a	
	mound of stones for 1/4 Sec,	
	Cor, from which,	
	Cedar 9in, dia, bears	2,00

BOOK-A-152

Salt Lake Meridian

Sums	S. 50 W. 6 chs. dist., Cedar 5 ins. dia. brs. N. 15 E. 4 links dist., Both trees marked 1/4 S. B. T.
77.84	The Cor. to Secs. 19, 20, 29 & 30, Land broken on E. 3/4. Set 2nd Corr. to, Winter Line & Cedar, W. 1/2 20 chs. level, Set 1st Corr. to, Set Timber,

---

From the Cor. to Secs. 17, 18, 19 & 20, Run, West on random line bet. Secs. 18 & 19, Var. 16° E.,

2.00	Ditch drains S. W. into field,

3 8 20

Subdivisions Sec. 41 S. R. 4 W.

Chains.		Chains.
5,00	Rio Virgen 20 lks. wide, runs S. W.	
30,00	Muddy creek 10 lks. wide runs S. W. -	77,80
34,00	Pence bears N. E. & S. W. hard fired,	
35,00	County road bears N. E. & S. W. Ascend Gypsum hills,	
40,00	Set Temporary 1/4 Sec. Cor. on E. slope of bluffs,	
60,00	Enter Rainie drains S. W.	
77,80	Intersect Guide Meridian at the Cor. to Secs. 18 & 19 from which,	
	East on true line bet. Secs. 18 & 19,	1,00
		1 1,00
37,80	Set a piece of Gypsum 16x10x6 in. 11 in. deep, marked 1/4 on N. side & mound of stones for 1/4 Sec. Cor.	19,0
		27,9
		2 8,90

BOOK-A-152

Salt Lake Meridian

Chains, from which,

Aspen Tree, dia, bears S. 30 E.
50 lks, dist, marked 1/4 S. B.T.,

77,80 The Cor, to Secs, 14, 18, 19, & 20,
Lands E½, cultivated fields,
Soil 1st rate, W½, broken
& rocky, Soil 2nd rate,
Timber, Scattering Cedar & pine
on W½,

North bet. Secs. 14 & 18,
Var. 16° E,

1,00 Ditch drains S. W.
1,00 Wash drains S. W.
19,00 Rio Virgen runs S. W.
27,90 S. side street bears S. 48½ E.
Enter, Mt. Carmel,
28,90 N. side street bears S. 48½ E.

400 22

Subdivisions T. 41 S. R. 7 W.

Chains.	
3 1,85	S. side street bears S. 42½ W.
3 3,95	N. " " " " " "
3 8,90	S. " " " " 48½ E.
3 9,85	N. " " " " " "
40,00	In S. Cor. of Silas Hoyt's lot, Set Sandstone 2" x 14" x 8" in. 15 in. deep, marked ¼ on W. side & raised around of stones for ¼ Sec. Cor.
6,00	Foot of Alum hills bear N.E. & S.W. to avoid which I offset East 20,00 chs. to point, thence N. on offset line 5,50 chs. South side of the North street in Mt. Carmel bears S. 48½ E.
6,50	chs. N. side of same street.
9,00	" Alum mine 5 chs W. & N.E. end of Main St. S. 42½ W. 100 lks. dist.

8 0,

Salt Lake Meridian

10,00 chs, County road N.E. & S.W,
12,75 " E, point of Alum hills,
13,50 " Ditch runs S.W,
20,00 " to point on line
bet, Secs, 8 & 17, 20,00 chs. E of,
the point for cor, to Secs, 7, 8,
17, & 18, which falling on the
broken rocky hills is not
established, therefore at the
point 20,00 chs, E, of the Sec,
Cor, point, I set pond stone
28 x 20 x 8 ins, 20 ins, deep, marked
5 notches on E, & 4 on S, edges
W.C, & raised mound of
stones for Witness Cor, to Secs,
7, 8, 17 & 18,
Land S. 3/4 cultivated fields
& town lots, N. 20 chs, Alum hills,
No Timber, except an occ. scrub
Pine & cedar,

80,00

406 24

Subdivisions 2 & 11 S. R. 7 W.

East on random line bet,
Secs, 8 & 17,
Var, 16° E,
From Witness Cor, running the
distance back to the true Cor,
point,

		40,00
		80,00
21,50	Ditch runs S. W. at foot of	
	Alum hills, bears N. E. & S. W.	
24,00	County road bears N. E. & S. W. &	
	enters plowed land,	
29,00	Rio Virgen runs S. W.	
33,00	Road bears N. & S.	
38,50	Wash drains S. W.	
40,00	Set temporary 1/4 Sec. Cor,	
48,70	Road bears N. & S. Ascend,	
60,00	Top of ridge bears N. & S.	
80,00	Intersect N. & S. line at the	
	Cor, to Secs, 8, 9, 16 & 17, from	
	which,	

West on true line bet,

Salt Lake Meridian,

Secs, 8 & 14,

40,00 Set limestone 20 x 18 x 4 in, 13 in, deep, marked 1/4 on N. side, raised mound of stones for 1/4 Sec, Cor,

80,00 The Corner to Secs, 4, 8, 14, & 18, Land Center 30 chs, level, Cultivated fields, Soil 1st rate, Bal. hilly, 2nd rate, Timber, Scattering pine & cedar,

---

West on random line bet, Secs, 4 & 18,

Var, 16° E,

From the Witness Cor, on line bet, Secs, 8 & 14, I offset South 24,00 chs, to Avoid the rocky hills, thence W, on

Subdivisions Sec. 46 S. R. 4 W.

Chains on Offset line 60,00 chs, thence
N, 24,00 chs, to,
4,00 On true line at N, side of
hills, Set Temporary 1/4
Sec, Cor, from which, a mine
of Bituminous coal bears
N.W, about 20, chs dish,
4,30 Road bears N, W, & S, E,
4,05 Fence bears N, W, & S, E, & Enter
field,
54,00 Fence S, W, & N, E, leave field,
58,00 Muddy creek 10 lks. wide
runs, S, E,
75,00 Ascend,
77,76, Intersect Guide Meridian
7, lks. N, of Cor. to Secs, 7 & 18
from which,
which was not leaved N, 89° 57' W, on true line
Set, Secs. 7, & 18,
3,7,76 Set quartz stone 24 x 14 x 9 ins,

BOOK-A-152

Salt Lake Meridian,

Chains, 18 in. deep, marked 1/4 on N. side, ∨ raised mound of stones for 1/4 Sec. Cor,

47.76, The cor. point to Secs. 7, 8, 17, ∨ 18, Land 35 chs, ∨. part level, Soil 1st rate, No timber, Bal. hilly, 2nd rate, Timber, pine ∨ cedar,

---

North bet. Secs. 7, ∨ 8, Var. 16° E,

To avoid the hills Offset E. 40.00 chs, thence N. on Offset line, 80.00 chs, thence W. 40.00 chs, to

80.00 Top of ridge bears N. & S. Set Sandstone 20×12×10 ins, 15 in. deep, marked 5 notches on E.

406

28

Subdivisions 9, 40, S. R. 4 W.

o S, edges, traced mound	28,4
of stones for cor, to Secs, 5, 6,	39,0
7, & 8, from which,	
Spruce 9in, dia, bears N, 55	40,0
W, 30 lks, dist, marked S,	48,3
6, T, 41, S, R, 4 W, B.T.	
Spruce 8in, dia, bears S, 40 W,	52,0
75, lks, dist, marked S, 7, B.T.	55,0
Note; The 1/4 cor, falling	60,2
in the hills is not established,	61,0
Land on true line broken	
hills, Grd 2nd rate,	62,5
Timber, Spruce & Cedar,	80,0

East on random line
Set, Secs. 5 & 8,
Var. 16° E,
Descend,

40,0

Salt Lake Meridian.

Chains,	
28,40,	Road on W. side of ditch S.W. & enters plowed land.
39,00	Ditch drains S.W.
46,00	Set temporary ¼ Sec. Cor,
48,50	Road bears N.W. & S.E. over plowed land,
54,00	Low ridge bears N. & S.
55,00	Road bears S.W. & N.E. Enterfield.
60,25	County road bears N.E. & S.W.
61,00	Ditch drains S.W. enters plowed land,
62,50	Ditch drains S.E.
80,00	Intersect N. & S. line at the Cor. to Secs. 4. 5. 8 & 9. from which,
	Witness tree bears, Secs. 5 & 8,
40,00	Set Sandstone 20 x 18 x 3 in. 15 in. deep, marked ¼ on N. side & raised mound

408 30

Subdivisions N. 4° S. R. 7 W.

	of earth from 4 pits, each 24×12×12 in, for 1/4 Sec Cor,	Stan 58,0 71,0 76,0
80,00	The cor to Secs, 5, 6, 7, 8, Land mostly Cultivated fields, Soil 1st rate, Timber, Cedar & pine on N. 30 chs,	97.7
		37.7
	West on random line 1/4 Secs. Cor, Var, 16° E,	77.7
	Descend,	
4,00,	Post of ridge bears N. & S,	
7,50,	Road bears S.E & N.W,	
29,50,	" " " "	
40,00	Set temporary 1/4 Sec Cor,	
53,00	Ridge bears N.W, & S.E,	

Sixth Principal Meridian.

Chains

58,00 Coal indications

71,00 Road bears N. & S.

76,00 Muddy Creek, 10 lks. wide, runs S.,

77.76, Intersect Guide Meridian at the Cor. to Secs. 6 & 7, from which,

East on true line 16 lks. Secs. 6 & 7,

37.76 Set Sandstone 18 x 11 x 4 in., 12 in. deep, marked 1/4 on N. side, & raised mound of stones for 1/4 Sec. Cor.

77.76, The Cor. to Secs. 5, 6, 7 & 8,

Land broken

Do 2nd rate.

Timber, Cedar & Pine.

410 32

Subdivisions of 41 S. R. 4 W.

Chains,

North gr. true line bet.
Secs, 5 & 6,
Var, 16° E,

10,00 Descend along E. slope
34,00 Port of hill bears E, & W,
outer flat,
37.50, Road bears N. W. & S. E,
40,00 Set Sandstone 16x12x4 in,
1 in, dup, marked 1/4 on
W. side & raised mound
of stones for 1/4 Sec, Cor,
46,00 Dry Creek bed drains S. E,
bears flat & Ascend,
82,00 On S, slope of bare Sand
hill, Intersect 8th Stan=
dard, South, 13,44 chs,
E, of Standard Cr, to Secs,
31 & 32, T, 40 S, R, 4 W,
where I set a sandstone

Salt Lake Meridian,

18 x 5 x 3 in, 12 in. deep, marked 5 notches on E, 1 on N, & 6 on S, edges, for Closing Cor. to Secs 5 & 6, T, 41 S, R, 4 W.

Land broken, Soil 2nd, Date,

Timber, Scattering pine & Cedars,

January 1st 1897

F. C. Bailey,

General Description,

The Surveyed portion of this Township embraces the S. W. portion of Long Valley which is all under Cultivation. It Contains the towns of Orderville, Mt. Carmel, & the Settlement at Fiddlers Green. The lands lying in the hills are returned

as Mineral and are designated as follows, Viz:

Coal Land

Lots 1, 2 & 3, & S. ½ of N. ½	Sec.	3,
Lot 4, & S ½ of S. E ¼	"	4.
Lots, 1, 2, 3 & 4, & S. ½ of N ½ & N. W. ¼ of S. E ¼ & S. W. ¼ of S. W ¼	"	5,
" 1, 2, 3, 4, 5 & 6, S. E. ¼ of N. W ¼ S. W. ¼ of N. E. ¼, W ½ & S. E. ¼ of S. E ¼ & E ½ of S. W. ¼.	"	6,
The E. ½ ~~of~~ the E ½ of N. W. ¼ & N. E. ¼ of S. W ¼	"	7.
The W ½ of N ½	"	8.
" E ½ of N. W. ¼ & S. W ¼	"	9
" N. W. ¼	"	16,
" E ½ N. E. ¼ & S. E. ¼	"	17
" E ½ of S. E ¼	"	19
" N. W. ¼	"	20

BOOK-A-152 35 ~ 413

Alum

The N 1/2 of N.W. 1/4 of N.W. 1/4	Sec.	17.
" N.E. 1/4 of N.E. 1/4	"	18.

Gypsum

The S. 1/2 of Lot 1, Lots 2, 3 & 4, the S.W. 1/4 of S.E. 1/4 of N.W. 1/4 & E 1/2 of S.W. 1/4	"	18.
Lot 1, the E 1/2 of lots 2 & 3, & the N. 1/2 of N.E. 1/4 of N.W. 1/4	"	19

F. C. Bailey
U. S. Dep. Surveyor.

" "

3,
4,
5,
6,
7,
8,
9
16,
17
19
20.

U. S

Sa

The

Town

Execu

Under

day of

Dec

exami

planat

survey

415

BOOK-A-152

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, April 3rd 187 7

The foregoing field notes of the survey of the Subdivision Lines of *Township No.* 41 S. *Range No.* 7 W. *Executed by* S. L. Bailey *Under his* Said *contract of the* 4th *day of* September 1876, *in the month of* Dec + Jany 1876+7 *having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.*

Frank Kimball

Surveyor General for Utah.

BOOK-A-152

13 419

Examined by C. H. Cranwell. C.G.

Field Notes
of the
Survey of the
Subdivision lines
of
Township 41 South
Range 10 West
of the
Salt Lake Meridian
Utah Territory
by
J. G. Burrill
under print contract of
Bailey & Burrill
No. 73 dated Sep. 4th 1876.

Survey commenced March 27. 77
" completed " " "

91

BOOK-A-152

Township 11 North **R.** 10 West



BOOK-A-152

Subdivisional lines of T. 41 S. R. 10 W.
Salt Lake Meridian 471

Survey commenced March
29th 1877 by J. G. Burrill
Note. The N E, N W & S E
portions of this Tp. laid in
Mountains and cannot be surveyed
thereon & mud
North between secs 31 & 32
Var. 13° E.
Lines in place being impracticable on account of
mountains & begin at the
initial cor to secs 31 & 32
on S. boundary being 10 chs
E. of true cor. point and
measure 15 chains E. thence
N 5 chs. N. thence N 59° E.
26 chs thence N. 14 3/4° E 40 chs
thence North 7.93 chs
thence West 18.47 chains

Subdivision lines of T. 4 S.

Miles
81.33

to a point 39.00 chs East of The true cor. point where I set sandstone 28 x 20 x 7 in 21 in deep notched 5 E. & 1 S. marked B. C. and mound of stone for witness cor. to secs 29, 30, 31 & 32

Note: The 1/4 sec cor falling in bluff is not set.

Land in line in place Mountainous in bottom Levee Soil in bottom 1st rate Timber pine & cedars in mountains

---

Note: The cor to secs 28, 29, 32 & 33 not being set. I run

East on true line between secs 29 & 32

Var. 16° E.

R 10 W. Salt Lake Meridian

Chains	
39.00	The witness cor to secs 29, 30, 31 & 32 On steep slope of mountain facing E.
42.00	Marked stationary sandstone 24 x 18 x 8 in above ground 1/4 cor N. side & mound of stone for 1/4 sec. cor.
44.50	Wash drain S.
52.50	Ridge bears N & S
57.47	Enter flat
73.47	S. E. cor. of E. 80 acres homed.
79.70	Road bears N & S.
85.00	Set sandstone 16 x 12 x 6 in 10 in deep notched 4 E & 1 S, with mound of stone for cor. to secs 28. 29 32 & 33
	Land mostly level
	Soil 1st rate
	Timber pine & cedar in mountains

Subdivision lines of T. 41 S. R. 10

South between secs 32 & 33

Var 16° E.

1.00	Ditch drain S.W.	
4.50	" " "	
4.60	Fence bears N.E. & S.W. being extension of S.W. side of Street in Springdale Settlement, which extends S 62½ W. 27 chs consisting of 3 horses and 2 steers distributed on both sides of street	
10.00	Fence bears N.E. & S.W.	
14.50	North bank of Rio Virgin 60 lks wide 12 min deep runs S.W.	4.50
40.00	Falls in bluffs cannot be set thereon at 20 chs marked A sandstone in place 12 x 8 x 3 feet above ground ¼ on W.	7.50 14.00

R. 10 W. Salt Lake Meridian

Chains	pits and mound a mound of stone for witness ¼ sec. cor.
	Note: Abandon line here.
	Land level
	Soil 1st rate
	Timber cedar & pine
	on mountains.
	Note: The cor. to secs 27, 28, 33 & 34 not being set thereon I run
	East on true line between secs 28 & 33
	(Var. 16° E.
4.50	Pitch runs S. W.
7.50	Wash runs S. E.
16.00	North fork of Rio Virgin 100 lks wide 1½ in deep runs S. W.
	at foot of mountains bear N & S

Subdivision lines of T. 41 S.

Chains	
40.00	Sabine on mountains can be set thereon at 12 chs Pit sandstone 12 x 12 x 4 ins 8 ins deep marked 1/4 W. C on N. side and mound of stone for witness 24 x 24 x cir. Note Meander line here: Sand rock in bottom Soil 1st rate Timber cedar & pine in mountains.
	North between secs 28 & 29. Var 16° E.
0.32	Road bears N E & S W.
4.00	Wash drains S E.
40.00	On top of W. end of low ridge marked sandstone in place 6 x 4 x 1 feet above ground 1/4 ex

BOOK A, 152

T. 10 N. Salt Lake Meridian —

Spacing	
	W. Line & mixed mound of stone for 1/4 sec. cor.
76.52	Foot of mountains
0.75	Hills in mountains Cannot set thereon at 76.52 chs set a stone 18 x 12 x 10 ins 12 ins in ground marked 4 notches on E. & W. sides & cross and W. C, mixed mound of stones for cor. to secs 22, 21, 28 & 29.
	Land mostly level
	Soil 1st rate
	Timber cedar & pine in Mountains —

Note: The cor. to secs 22, 23, 26 & 27 not being set thereon

Z. Reed

Subdivision lines of Sec 4 / T.

East on true line between secs 21 & 28 Var 16° E.

46.60

Line in place impracticable on account of mountains therefore from the witness cor 23.50 chains E. to cor. print of secs 20. 21. 28 & 29 & measure East 40 chs thence North 23.50 chs. to

40.00 Cor line in place at foot of mountains set sandstone 11 x 10 x 5 in 7 in deep marked 1/4 in stone and raised mound of stone for 1/4 sec. cor.

41.00 Road bears N.E. & S.W.

45.60 North fork of Rio Virgin 100 lks wide 12 in. deep runs S.W.

68.

61.

40.0

BOOK-A-152

46.00	Red logs N.E. & S.W. enter Calcium Land
64.25	Pits at foot of hills runs S.W.
68.75	Ridge point runs N.
81.75	Set Sandstone 16 x 10 x 4 in 10 in deep notched 3 E. & 2 S., with mound of stone for cor to Secs 21, 22, 27 & 28 Land level in bottom Soil 1st rate Timber pine & cedars in mountains

South between Secs 27 & 28
Var. 16° E.

Record

40.00	On N.W. slope set a Sandstone 10 x 10 x 6 in 6 in deep

Subdivision lines of S. T. 4. S. R. E.

Ch.

Marked 14 on Dr. tree and raised mound of stone for 1/4 sec. cor.

Note: Abandon line here

Land mountainous

Soil poor rate

Timber scattering pine & cedar

21.00

Note: The cor to secs 22, 23, 26 & 27 not being set 2 rods

East on true line between secs 22 & 27

Var. 16° E.

42.00

Chained

46.00

40.00 Set sandstone 11 x 9 x 6 in 7 in deep marked 1/4 on N. side, with mound of stone for 1/4 sec. cor.

80.00

BOOK-A-152

S. L. M. Salt Lake Meridian

Note: Abandoned line here.
Land mountainous
Soil 2nd rate
Timber scattering cedar
and pine —

North between secs 21 & 22
Var. 16° E.

21.00 North fork Rio Virgin 150 lks
wide 10 in deep runs S.W.

46.00 Set sandstone 14 x 10 x 6 in
9 in deep marked 1/4 on W.
side, with mound of stone
for 1/4 sec. cor.

42.00 Road bears N.E. & S.W.

46.00 Foot of mountains bears
N.E. & S.W.

80.00 Drive charred cedar post
4 ft x 4 x 4 in notched 3 on E. & S.
Edges,

Subdivision lines T. 7 S. R. 4 W. S.B.M.

12 in. days in mound of earth raised from 4 Pits each 24 x 12 x 12 in for Cor to secs 15, 16 21 & 22.

Note: On account of the mountainous & abandoned Survey (now).

Land in both Land, Soil 1st rate,

No Timber.

March 29th 1877 J. G. Burrill

General Description.

The surveyed portion of this Township embraces the bottoms of the N. fork of the Rio Virgen mostly in a high state of cultivation as

12 W. Salt Lake Meridian

vineyards, orchards and
lucerne fields. In sec. 32
is the settlement of Spring=
dale containing about 100
inhabitants. The entire
all the lands as agricultural.

J. G. Burrill
U. S. Dep. Surv.

BOOK-A-152

435

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, June 30th 1877

The foregoing field notes of the survey of

Subdivisional Lines

Township No. 41 S. *Range No.* 10 W.

Executed by Bailey & Burrill

Under their *contract of the* 4th

day of Sept 1876, *in the month of*

March 1877, *having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.*

Nathan Kimball

Surveyor General for Utah.



BOOK-A-152

Examined by C.H. Cranwell. C.C.

(Plotted & Corrected)

437

Field Notes

of

The Survey of the Subdivision lines

of

T. 41 S. R 11 W.

of

The Salt Lake Meridian

Utah Territory

By

J. G. Burrill

Under Joint Contract of Bailey & Burrill

No. 73 dated Sept. 4th 1876.

Survey commenced, March 26th 1877.

" Completed " 26th 1877.

BOOK-A-152

Township [illegible] **R.** [illegible]



Subdivisions. Tp. 41 S. R. 11 W.

Chains, Note. The East & Central portions of this Township not being Surveyed on Account of Mountains therefor from the Cor. to Secs. 33 & 34, on South boundary Sec. North between Secs. 33 & 34

Var. 16° E.

15,00 Foot of Tracky to Bluff bears E. & W.

40,00 Falling in Bluffs, noted therefore at 15, Chs set a Tracky to 20×12×4 ins. 15 ins. deep, marked 1/4 S.C. on W. side, & raised mound of stones for Witness 1/4 Sec. Cor.

Note. I abandon line here, Land level in bottom, Soil 1st rate.

4,18

4,78

7,00

7,50

8,00

8,51

40,00

BOOK-A-152

Salt Lake Meridian,

No timber,

From the Cor. to Secs, 32. & 33,
on S. boundary of T.,
North between Secs, 32 & 33,
Var. 16° E.

4,18 Rio Virgen, 60 lks. wide 2
feet deep, runs S. W.

4,78 Enter cultivated land,

7,00 Leave same, fence bears E. & W.

7,10 Road bears E. & W.

8,00 Telegraph line bears E. & W.

8,50 Foot of Trachyte bluff
bears N.W. & S.E.

40,00 Falling in bluff, no rock,
therefore at 8,50 chs, marked
a Stationary Trachyte, 5 x 5 x
4 feet above ground, 1/4 M.
on W. side, & mound

Subdivisions Tp. 41 S. R. 11 W.

of stones for Witness 1/4 Sec. Cor.

Note Abandon. line here

Land in bottom level,
Soil 1st rate,
No timber,

From the Cor. to Secs. 31 & 32, on the S. boundary of Tp., North between Secs. 31 & 32.
Var. 16° E.

20,00 West point of low bluff bears E. 3 chs.

38,25 River bluff bears N.W. & S.E.

40,00 Set Sandstone 14x12x6 ins. Pits. dug, marked 1/4 on W. side & raised mound of stones for 1/4 Sec. Cor.

42.24 Rio Virgin 186 lks. wide

18 in, deep, runs N. W.
44,19 Enters cultivated land,
53.60 Foot of Trachyte bluff
bears N.W. & S.E,
80,00 Falling in bluff, notch,
therefore at, 53.60 chs, Set
a trachyte, 18x12x8 in, 12
in, deep, marked 5 notches
on E, & 1 on S. edges, & W.C.
for, Witness Cor. to Secs,
29, 30, 31, & 32,
Land mostly level,
Soil in bottom 1st rate,
No timber,

Mak on random line
between Secs, 30 & 31,
Var. 16° E,
Line in place, impracticable,

Subdivisions, Tp. 41 S. R. 11 W.

Chains		Chains
	Therefore, from the Witness Cor, 26.40 chs, S. of the Cor, limit to Secs, 29. 30, 31 & 32, South, 32 chs; thence East 51 chs; thence N 63° 45' W. 11 chs; ~~thence N. 63° 45' W. 10,11 chs; thence~~	41,8 42,0 42.7 48,1
thence	N. 54° W. 8,00 chs; thence N. 81° W. 10 chs; thence N. 56° W. 10 chs; thence W. 4,00 chs; (the last three Courses falling in the Settlement of Duncans Retreat, Containing a population of about 125, with 16 houses as plotted) thence N. 10 chs. to	70, 80,0 40,0
38,00	On line in place at fork of Trachyte bluffs, bears N.W. & S.E.,	80,0
40,00	Set tempering ¼ Sec. Cor,	
41,00	Road bears N.W. & S.E,	
	Telegraph line bears N.W. & S.E.	

Chains.	
41,80	Stone Wall bears N.W. & S.E.
42,00	River bluff bears N.W. & S.E.
42.78	Rio Virgin 325 lks. wide runs N.W.
48,10	Road & ditch bears N.W. Enter bench,
70,00	Gulch drains N.
80,00	Intersect W. boundary of Sec. at Cor. to Secs. 30 & 31, from which, East on true line between Sections 30 & 31,
40,00	Set trachy to 13x12x10 in. 9 in. deep, marked 1/4 on N. side, with mound of stones for 1/4 Sec. Cor.
80,00	The Cor. point to Secs. 29, 30, 31 & 32. Also Witness by marking a stationary trachyte 3x2x2 feet above

Subdivisions, T. 41 S. R. 11 W.

Chains

40,00

Chains, ground, & noticed on E. & 1 on S. edges, with mound of stones, 38,00 chs. N. of true Cor. Point Land W 1/2, level, E 1/2 in bluffs, Soil mostly 2nd rate, No timber,

---

Note; As the Cor. to Secs. 5, 6, 7 & 8, is not set, therefore from the Cor. to Secs. 6 & 7, on the West boundary of the T., I run, Each on true line between Secs. 6 & 7, Var. 16° E,

10,00 Foot of very steep slope, bears N.E. & S.W.

Sacramento Meridian, 669

Chains, 40,00

Inaccessible, therefore at 10 chs. Set trachyte 16 x 10 x 4 ins, 11 ins, deep, marked 1/4 S.C, on N. side, & raised mound of stones for Witness 1/4 Sec, Cor,

Note; Abandon line here, Land mostly mountainous, Soil 2nd rate, No Timber,

---

Note; As the Cor. to Secs, 5, 6, 7 & 8 is not set, therefore from the established closing Cor, to Secs, 5 & 6, on the 8th Standard Parallel, South, forming the South Boundary of this Dp, I run, South ~~on true lines~~ returns

Subdivisions, Sec. 41 S. R. 11 W.

Chains	
	Secs, S & E,
	Var. 16° E.
0,90	Arrito Creek 30 lks, wide,
	10 in, deep, runs S, W,
1,40	Fence bears E, & W, enter
	Orchard & Cultivated land,
7,90	Stone Wall, bears N, 80 W,
	& S, 80 E, enter Bench land,
12,00	Fork of Mountains,
40,00	Falls in Mountains,
	Not set, therefore, at 16,39
	chs, on N, W slope of Moun=
	tains, marked a Stationary
	Sandstone 12 x 8 x 8 ft, abm
	Ground ¼ W. C, on W, side,
	& raised mound of stones,
	for Witness ¼ Sec, Cor,
	Note; Abandon line here,
	Land level bottom & bench,
	Soil 2d rate,

Chains

30°44'

40,00

Chains No Timber,

Note; As the Cor. to Secs. 4. 5. 8 & 9 is not set, therefore from the established Witness closing S. 80 W, Cor, to Secs, 4 & 5, on the 8th Standard Parallel South, & N, boundary of this Dp, I run,

South ~~a true~~ ~~line~~ between Secs, 4 & 5,

Var, 16° E,

Note; The Running of this line being impracticable on account of Mountains I measure a base, 32.70 chs, W, from said witness corner, from which a flag in line, bears S. 30° 44' E, making, from cor, Where I set a Trachyte,

S. chs. W. of true cor. of 4 & 5, on the 8th Standard

W.T. Secs. 4 & 5

S 30° 44' E

4,00

Subdivisions, T. 41 S. R. 11 W.

16×12×7 in., 11 in. deep, marked
¼ on W side, & raised mound
of stones for ¼ Sec. Cor.
Note: I abandon further
Survey here,
Land mountainous,
Soil 2nd rate,
Timber, Pine, & Cedar,

General Description

The Surveyed portions of this
T., principally embrace the
bottoms of North Creek & the
Rio Virgin, Sec. 5 contains
Millville Settlement, with a
population of about 50 souls,
Sec. 6 a portion of Mountain
Dell, Sec. 31 the Settlement

451

BOOK-A-152

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, June 30 *187*7

The foregoing field notes of the survey of Subdivisions Sixth of *Township No.* 4 S *Range No.* 1 W *Executed by* Bailey & Burrill *Under* Supplemental *contract of the* 4 *day of* Sept *187*6, *in the month of* March *187*7, *having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.*

Nathan Kimball

Surveyor General for Utah.

BOOK-A-152

Sack Lake Meridian,

of Dunc ans Retreat, more particularly described in the field notes, The lands are agricultural, ~~mostly~~ under cultivation,

March 26th 1877. J. G. Bursell
U. S. Dep. Sur.

BOOK-A-152

Examined by C. H. Cranwell, S. C.

Field Notes,

of

the Survey of the

South & East Boundaries

of

Tp. 41 S. R. 12 W,

of the Salt Lake Meridian

Utah Territory,

By,

F. C. Bailey

Under Joint Contract of Bailey & Bamill

No 73 dated Sept 4th 1876

Survey Commenced, March 21st 1877

" Completed " 21st 1877

BOOK-A-152

Township [illegible] **R.** [illegible]



South Boundary 2p. 41 S. R. 12 W.

Chains		Chains
	March 21st 1877,	
	By, F. C. Bailey	
	Note; As the S. E Cor. of this	
	2p. is not set, therefore from	41,50
	the established corner to	
	2ps. 41 & 42 S, Rs. 12 & 13 W,	77,0
	I run,	
	East on true line between	80,00
	Secs, 6 & 31,	
	Var. 16° E,	
40,00	Set white Tufa, 12 x 8 x 5 in;	
	9 in. deep, marked 1/4 on N.	
	side, & raised mound of	
	Tufa, for 1/4 Sec. Cor,	
	Note;	
	As no convergency was	
	allowed in the Survey of	
	the 2ps. N. & W. of this,	
	therefore to make Surveys	
	correspond, & permit a	

Salt Lake Meridian,

Chains	
	future connection, Omit the usual allowance, for emergency here,
41,50	Road to Workmans bears N.E. & S.W.
77,00	Hood road bears N.E. & S.W. & Wash drains N.E.
80,00	Set Sandstone 16x10x9 in., 11 in. deep, notched 3 on E. & 1 on S. edges, & raised mound of stones for Cor. to Secs. 5, 6, 31 & 32,
	Land level,
	Soil 1st rate,
	No Timber,

East on true line between Secs. 5 & 32,

Var. 16° E.

South Boundary of T. 41 S. R. 12 W.

Chains.		Chains.
25,00	Wash drains N. & Road bears N. & S.	
31,00	Wash drains N.	
33,50	" " N. W.	40
41,00	Set Soapstone 18 x 10 x 4 ins, 12 ins. deep, marked 1/4 on N. side, & raised mound of stones for 1/4 Sec. Cor.	
45,00	Large Canon wash, drains N. W.	45
81,00	On W. edge of bluffs, at mouth of small Canon, Set a Soap stone 36, 12 x 4 x 3 ins, 2½ ins. deep, notched 4 on E. & 2 on W. edges, & raised mound of soap stone for Cor. to Secs. 4. 5, 32, & 33.	55, 80

Land Broken.
Soil 2nd rate,
No Timber.

Salt Lake Meridian.

	Chains,	
		East on true line between Secs. 4 & 33. Var. 16° E,
	40,00	Enters S. W. point of lone bluffs. Set Soapstone, 42 x 20 x 3 in, 31 in, deep, marked 1/4 on N. side D raised mound of Soap Stone for 1/4 Sec. Cor,
	47,50	2 lks of point bears N.E. & S.W.
	55,00	Enter bench flat, bears N.E. & S.W;
	80,00	Set Soapstone 16 x 14 x 5 in, 11 in, deep, notched 3 on E. & W, edges, for Cor. to Secs, 3. 4. 33. & 34.
		Land broken, Soil 2nd rate, No timber,

South boundary Tp. 41 S. R. 12 W.

Chains.	
	East on true line between Sees. 3 & 34.
	Var. 16° E.
40,00	At foot of high bluffs, bears N. E & S. W. Set Limestone 13 x 7 x 6 in. 9 in. deep, marked 1/4 on N. side, & raised mound of stones for 1/4 Sec. Cor, Notes; Further chaining on line in place being impracticable I offset 24 chs. N, thence 40 chs. E, to a point 24 chs, N. of.
80,00	Where I set a Limestone 13 x 8 x 6 in, 9 in. deep, marked 2 notches on E. & 4 on W. edges, & W. C. & raised mound of stones for Witness Cor. to Sees, 2, 3, 34 & 35.

40.0

80,0

Land E/r Mountains,
Soil 2nd " rate,
W/r level. Soil 1st " rate,
No timber,

East on true line between
Secs. 2 & 35
Var. 16° E.
Note; Line in place impracticable therefore from the Witness Corner, 2400 chs,
N. of the Cor, point to Secs,
34 & 35, on S. boundary Run,
East on Offset line 40 chs. to
40.00. set Sandstone 15 x 10 x 4, 12 in. deep marked
1/4 M. C. on N. side, and raised mound
of stones for witness 1/4 sec. cor. 24, chs. N. of
true cor.—Continue E. 80 chs, thence
South 9 chs, to point 15 chs. N. of
80,00 Where I set a Sandstone
13 x 7 x 7 in. 9 in. deep, marked
1 Notch on E. & S. on W. edges

South Boundary Tp. 41 S. R. 12 W.

Chains	▽ W.C. ▽ raised mound of Stones for Witness Corner to Secs, 1, 2, 35 ▽ 36,	Chains 40.0
	Note: 40. chs. falling in Bluff, the 1/4 Sec. Cor. is not Set,	80.0
	Land broken,	
	Soil 2nd rate,	
	No Timber,	

East on the line between Secs, 1 ▽ 36,

Var. 16° E.

Note:

Line in place impracticable, therefore from the Witness Corner, 15 chs. N. of the Cor. found, to Secs 1, 2, 35, ▽ 36, I run E. on offset line 40 chs to

Salt Lake Meridian,

Chains

400

80,000

Set Sandstone 15x10x4, 10 in. above marked 1/4 S. C. on, W. Scribed & raised mound of stone for future 1/4 Sec. Cor. 15 chs. W. of True Cor. Point, Thence continue E. to 80 chs. to Point 15 chs. W. of the True Point for the 1/4 Cor. but the nature of the ground rendered the setting of a witness Cor. impracticable, therefore I measure on E. 25 chs. further thence S. 15 chs. to Point 25 chs. S. of Where I set a Gypsum, of 2x12x6 in. 15 in. deep, notched 6 on N. S. E & W. edges, marked W.C., & raised mound of Gypsum for Witness Corner to Tps. 41 & 42 S. Rs. 11 & 12 W.

Note, 40 chs. falling in true Bluff, the 1/4 Sec. Cor. is not set.

Land broken,

Soil 3rd rate,

No Timber,

East Boundary Tp. 41 S. R. 12 W.

Chains		Chains
	North between Secs. 31 & 36,	
	Var. 16° E.	
	Note, Line in place being impracticable, therefore from the Witness Corner, 25 chs. E. of the Cor, point, to Tps. 41 & 42 S, Rs. 11 & 12 W, I run, On offset line N. 68 chs, W. 25 chs, to a point 28 chs, N, of,	6,0
		14,5
40,00	On line in place at foot of bluff, bears N. W & S.E, where I set a Sandstone 14 x 9 x 7 in, 9 in, deep, marked 1/4 M.C, on N, side & raised mound of stones for Witness 1/4 Sec, Cor,	19,5
		29,7
		38,1
		40,0
80,00	Set Sandstone 24 x 16 x 4 in, 18 in, deep, notched 1 on S, & 5 on N, edges, for Cor, to	

Salt Lake Meridian.

W.		
36,	Chains,	Secs, 25, 30, 31, & 36,
		Land broken,
ing		Sec 2nd rate,
ne		Not timber,
er,		
h,		
2 W,		North between Secs. 25 & 30,
68 ch		Var. 16° E.
ks,	6,00	Enter bottom bears N.W. & S.E.
	14,50	Road bears N.W. & S.E.
t	19,50	Fence " " "
E,		Enter cultivated land,
e	29,70	Fence bears E. & W,
ked		bars cultivated land,
ab	38,10	Rio. Virgin 2 links, wide,
ness		runs W,
	40,00	Set trachyte 25 x 12 x 6 in,
		19 in, deep, marked 1/4 on
		W, side, & raised mound
		of stones for 1/4 Sec, Cor,
to		

East Boundary 24. 41 S. R. 12 W.

Chains.	
41,90	Ditch runs N.W.,
42,50	Road, a Telegraph line bears N.W. & S.E., about off trachyte bluffs.
80,00	Falling in bluffs is not set, therefore at 45 chs, marked a stationary trachyte 4×2×½ ft. above ground, 4 notches on N, & 2 on S. edges, & W.C. & raised mound of stones for Witness Corner. to Sees, 19, 24, 25 & 31,

Land mostly level,
Soil 1st rate,
No timber,

Note; I abandon line at this point, & proceed to the Witness Cor. to Sees. 7, 12, 1318, 80,00

Salt Lake Meridian,

established in Sub-dividing
this 2p., Viz;

A Stationary Sandstone
24 x 18 x 18 in, above ground,
marked 2 Notches on N, &
4 on S, edges & W.C", &
mound of stones, & run,
North between Sees. 7 & 12,
Var. 16° E,
Note: Line in place being
impracticable, therefore
from the Witness Corner,
31,60 chs, N, of the Cor. Joint
to Sees, 7, 12, 13 & 18 Inum,
On offset line N. 40 chs,
thence E. 11,60 chs, thence
N. 40 chs, (~~thence E. 11,60 chs,~~
~~thence N. 40 chs,~~) thence E,
20 chs, to,

13 18, 80,00 On line in place, Set tracky te

East Boundary Sec. 4 T. 8 S. R. 22 E.

		Chains
Chains,	20×10×2 in. 15 in. deep, notched 1 on N. & 5 on S. edges, & raised mound of stones, for Cor. to Secs. 1, 6, 7, & 12,	6,00
	Land in bottom level.	6,25
	Soil 1st rate,	6,60
	No timber,	7,75
		11,80
		12,80
Note; The 1/4 sec. Cor. falling in Mountains is not set.		14,00
		15,00
		15,50
	North between Secs. 1 & 6,	17,00
	Var. 16° E.	18,50
0.65	Brick House in Mountain Dell, Settlement, bears N. 9 3/4° W. White house bears N. 16 3/4° W. Adobe House bears N. 14 3/4° W. Frame house bears N. 5° E. Barn bears N. 10 1/4° E.	19,0
		21,1
		22,7

Sacramento Meridian

Chains	
6,00	Enter bottom bears N.E, & S.W,
6,25	Ditch runs S.W.
6,60	Fence bears S.W. enter orchard,
7,75	Fence " N.W & S.E.
11,80	" " " "
12,80	Ditch runs N.E.
14,00	Fence bears N.W & S.E.
15,00	Wine cellar on line,
15,50	Brick Kiln 0.20 chs. E,
17,00	Ditch runs S.W.
18,50	Fence Corner 5 links W
19,00	Ditch runs N.E.
20,00	Foot of hill bears W.
22,75	Top of same, at this point, Brick house bears S. 8° W, White House bears S. 16¼° W, Adobe House bears S. 8¼° W, A frame house

East Boundary T. 4 S. R. 12 W.

Chains	
	S. 8° E. Bam bears S. 10° E.
24,50	Witch on Side hill runs S. W.
24,80	Leave hills,
26,00	North Creek 20 lks. wide, runs S. W. road bears N. & S.
26,50	Fence bears N. E. & S. W. Enter cultivated land.
34,00	Leave same - enter hills,
35,00	Stone Wall, bears N. W.
40,00	Set Sandstone 13 x 13 x 10 in. 9 in. deep, marked 1/4 on W. side, & raised mound of stones for 1/4 Sec. Cor.
40,20	Wash. drains S. E.
80,00	The closing Cor. on 8th Standard Parallel South, falling in high mountains can not be set, therefore at 46.20 chs. marked a

Sackatoo Meridian,

Chains	Stationary Sand Stone 10 x 5 x 6 Ft. above ground, 6 notches on S. E. & W. Edges, & W. C. C. raised mound of stones, for Witness Closing Corner to Tps. 41 S. Rs. 11 & 12 W. Land broken except in Flat. Soil 1st & 2nd rate, No timber, March 21st 1877. T. C. Bailey
Note;	For General Description & approval see end of Sub. Div. notes of This Tp.

BC

BOOK-A-152

Examined by C. H. Cranwell C/C.

Field Notes,

of

The Survey of the Subdivision lines,

of

Tp. 41 S. R. 12 W.

of

The Salt Lake Meridian

Utah Territory

By,

Bailey Burrill

No. 43 dated Sept. 4th 1876.

Survey Commenced Mch 22d 1877

" Completed " 23d "

BOO

Chair

15;

4 11,

93

8 11,

BOOK-A-152

Subdivisions T. 41 S. R. 12 W.
Salt Lake Meridian

Chains.	
	March 22d 1877.
	By. J. G. Burrill.
	From the Witness Corner to Secs. 35 & 36, on S. boundary Arch between Secs, 35 & 36, Var. 16° E.
15,00	The Witness Corner at foot of bluffs. bears N. 1/4 E.
40,00	Set Gypsum 12 x 8 x 8 in. 9 in. deep, marked 1/4 on St. side & raised mound of Gypsum for 1/4 Sec. Cor.
73,00	Deep Gulch wash drains N. E.
80,00	Set Sandstone 20 x 12 x 8 in, 15 in. deep, notched 1 on E. & 1 on S. edges, & raised mound of stones for Cor. to Secs. 25, 26, 35 & 36.

Subdivisions. Tp. 41 S. R. 12 W.

Chains,	
	Land mostly broken,
	Soil 2nd rate,
	No Timber,
	East on random line
	between Sees. 25 & 36,
	Var. 16° E,
6,00	Rush drains N.E,
13,00	" " N,
37,00	" " N.E,
40,00	At foot of bluffs brass
	N.E. & S.W. Set temporary
	1/4 Sec. Cor. thence Offset
	20 chs. N, thence 40 chs.
	E, thence 20 chs. S. to;
80,00	Intersect E. boundary
	of Tp. at Cor. to Sees. 25-
	& 36. from which,
	West on true line with

Salt Lake Meridian 729

Chains Offsets. between
Secs. 25 & 36.

40,00 Set Gypsum, 16x12x4
ins, 11in, deep, marked
1/4 on N. side, & raised
Mound of Gypsum for
1/4 Sec. Cor.

80,00 The Cor. to Secs, 25. 26. 35 & 36,
Sand broken.
Soil 2nd rate,
No timber,

Arch between Secs. 25 & 26.
Var. 16° E.

13,00 Wash drains N.E.

25,00 " " "

26,50 Same " " N.W.

29,50 " " " N.E.

40,00 Set Sandstone 24x10x7in.

480

Subdivisions 2 & 4, 41 S., R. 12 W.

Chains	18 in. deep, marked 1/4 on W. side, & raised mound of stones for 1/4 Sec. Cor,	Chains
49,00	Old Fence bears N. 28° W. 1750 chs. dist,	
51,20	Rio Virgin 50 lks. wide 18 in. deep, runs N. W. bare bench,	
55.75	Fence bears E & W. Enter Cultivated land,	10,
65,00	Fence on S. side of Ditch runs W. enter hills,	11.
66,00	Telegraph line bears E.-W.	
67,00	Road bears E. & W.	8
75,00	Gulch drains S. W.	
80,00	Set a trachyte 20x8x6 in, 15 in. deep, notched 1 on E. & 2 on S. edges, & raised mound of stones fr. Cor, to Secs. 23. 24. 25 & 26,	4

Salt Lake Meridian,

	Chains,	Land mostly level. Soil 1st rate, Timber,
		East on random line between Secs. 24 & 25 Var. 16° E. Descend,
	10,00	Ravine drains S.W.
	14,50	Foot of precipitous trachyte bluff. Offset 35 chs. S. 65 50 W. chs E. to
	81,10	Intersect E. boundary of T. at Witness Corner. 35 chs. S. of cor. point to Secs. 24 & 25, from which, West on true line with Offsets between Secs. 24 & 25, Falling in bluffs cannot
	40,00	

Subdivisions 2n. 41 S. R. 12 W.

Chains, Set sch. therefore at, 65,50 Chs.
on trig line
Chs, Set a trachyte 18x12x10
in, 12 in. deep. marked
1/4 M. C. on N. side, D
raised mound of stones
for Witness 1/4 Sec. Cor.
80,00 The Cor. to Secs. 23. 24. 25 & 26,
Land broken,
Soil 2nd rate,
No timber,

North between Secs. 23 & 24
Var. 16° E.

40.00 To avoid bluffs, I offset 20 chs. W. thence N.
Set Boulder 15x14x10.-10 in. deep, marked
1/4 M. C. on W. side & raised mound of stones for Wit-
ness 1/4 sec. cor. 20. chs. W. of the cor. point.
Continue N. to ——

—— 80 chs. thence E. 20 chs. to
80,00 where I set a trachyte
18x10x8 in, 12 in. deep,

Salt Lake Meridian.

	Chains, Notched 1 on E. & 3 on S. edges, & raised mound of stones for Cor. to Secs. 13, 14. 23 & 24.
	Land in place Mountainous
	Soil 3rd rate,
	No timber,
	Note; The true 1/4 Sec. Cor. Not set.

Note; The Cor. to Secs. 13 & 24 on E. boundary not being Sch. therefore I run,

E. on true line between Secs. 13 & 24, Var. 16° E.

1,00	Creek bluff bears N. & S.
12,50	Foot of high bluff. bears N. & S.
40,00	Falls in bluff, Cannot

Subdivisions. 9 R. 41 E. R. 12 W.

Chains

Chains be set, therefore at 12,50 chs. marked a trachyte in place, 5 x 3 x 2 ft, above ground, 1/4 W.C. on N. side, raised mound of stones for Witness 1/4 Sec. Cor, Note; I abandon line here,

Land undulating,
Soil 1st & 2nd rate,
No timber,

North between Secs. 13 & 14,
Var. 16° E,

1,00 North Creek runs S,
5,00 Leave Creek bed,
8,50 Fence bears E. & W.
9,00 " " N. 15 W.
18,50 Ditch runs S.W.

Cha
19.
21,
25,
28,
41
49
51,
81

Salt Lake Meridian.

Chains	
19.25	Fence bears E. & W.
20.00	Mouth of wash. Leads N.W.
25.75	Road bears N.E. & S.W.
28.50	Enter hills, bear N.E. & S.W.
40.00	Set Gypsum 20×12×2 in. 15 in. deep, marked 1/4 on W. side raised mound of Gypsum for 1/4 Sec. Cor.
49.75	Wash drains S.E.
51.50	S.E. point of steep hill, between two Cañons heading N.W.
80.00	Falls in bluffs, not set, therefore at 51.50 chs, set Gypsum 16×12×4 in. 11 in. deep, marked 1 notch on E. & two S. edges & W.C. & raised mound of Gypsum for Witness Corner

406

Subdivisions. Tp. 41 S. R. 12 W.

Chains to Secs. 11. 12. 13 & 14,
Land broken,
Soil 1st rate,
No timber.

Note; The Cor. to Secs. 12 & 13, on E. boundary of Tp. not being set therefore Irun,
East on true line between Secs. 12 & 13, Var. 16° E.,
Note; Line in place impracticable, therefore from Witness Cor. 28.50 chs. S. of Cor. Sought, to Secs. 11. 12. 13 & 14. I offset East, 20 chs, thence N. 28.50 chs, to 20.00 On line in place at foot

BOOK-A-152

Salt Lake Meridian.

Chains	
	of hills, where I set a Sandstone 20 x 6 x 5 in, 15 in, deep, marked 1 notch on E, & 4 on S. Edges, & W.C. & raised mound of stones for Witness Corner to Secs, 11, 12, 13, & 14, thence E, on line in place,
26,75	Red water ditch runs S. W.
29,10	Road bears N.E. & S.W.
29,70,	North Creek 60 lks. wide runs S. W.
35.80	Fence bears N.E. & S.W.
38,00	Enter hills. bear N.E. & S.W. Ascend.
40,00	Marked a Stationary Trachyte, 36 x 24 x 18 in. above ground 1/4 on N. Side, & raised mound of stones for 1/4 Sec. Cor.

Subdivisions Tp. 4 S. R. 12 W.

Chains.	
48,40	On top of ridge. bears N.W. & S.E.
80,00	Falls on Stub Mountain side & cannot be set, therefore at 48.40 chs. marked a Stationary Sandstone 24x18x18 in. above ground 2 notches on N. & 4 on S. Edges. W.C. for Witness Corner to Sees. 12 & 13, on East Boundary of Tp. Land broken. Soil 1st & 3rd rate, No timber,
	Note; Discontinue Survey North on this line.

Note; The cor. to Sees. 1. 2. 11 & 12 not being

Salt Lake Meridian.

Chains set, therefore from the Cor. to Sec. 1 T 12. on the East Boundary.

West on true line between Sec. 1 T 12. Var. 16° E.

6.20 Trail bears N. & S.

9.10 Road " " "

Enter flat.

9.20 Ditch runs S.

9.25 Fence bears N. & S. enter cultivated land.

12.50 Fence bears N.E. & S.W. leave cultivated land,

14.80 North Creek. 40 lks. wide, 10 in. deep. runs S.

20.00 Foot of hill bears N.E. & S.W.

40.00 In. Mountains, Not set, therefore at. 20 chs. Set Sandstone 16 x 10 x 4 in.

49°

Subdivisions of Sec. 24 T. 41 S. R. 12 W.

Chains. 11 in. deep, marked 1/4
W.C. on N. side, raised
mound of stones. for
Witness 1/4 Sec. Cor.
Note: Abandon line
here,
Land mostly level.
Soil 1st rate,
No Timber.
March 22d 1877 J.G. Burrill.

March 22d 1877 by T.C. Bailey
From the Witness Corner
to Secs. 34 & 35, on the
S. & E. Boundary.
North between
Secs. 34 & 35,
Var. 16° E.
24.00 The Witness Corner at
fork of bluffs bears
E. & S.W.

BOOK A-152

Salt Lake Meridian.

Chains 40,00	Set Limestone 12 x 9 x 4 in, 8 in, deep, marked 1/4 on N, side & raised mound of stones for 1/4 Sec. Cor.
65 11 0	Rock Gulch, drains N,
	15 E,
66,00	On S, side of ledge, Set a Limestone 28 x 16 x 3 in, 21 in deep, notched 2 on E. & 1 on S, edges & raised mound of stones for Cor. to Secs. 26, 27, 34, & 35,
	Land mostly broken.
	Soil 2nd rate,
	No Timber.

East on random line between Secs. 26, & 35.

Subdivisions, Sec. 4, T. 8 S. R. 12 W.

Chains	Var. 16° E.
2,11	Bottom of wash drains N. 15 E. Ascend,
8,50	Enter brush. Road bears N. & S.
12,00	Wash drains N,
37,00	" " "
40,00	Set temporary 1/4 Sec. Cor,
80,00	Intersect N. & S. line at Cor. to Secs. 25, 26, 35 & 36, from which,
	Ak. on true line between Secs, 26. & 35,
40,00	Set Slate stone 20 x 10 x 2, in. 15 in deep, marked 1/4 on N. side & mound of stones for 1/4 Sec. Cor,
8,11,11	The Cor. to Secs, 26, 27. 34, & 35,

Duck Lake Meridian.

Chains	Land broken.
	Soil 2nd rate,
	Timber.

North between
Secs. 26 & 27,
Var. 16° E.

5,00	Road bears N.E. & S.W.
24,00	Enter Wash breaks drain N.E.
35,00	Leave same.
40,00	Set Limestone 18 x 12 x 3 in, 12 in. deep, marked 1/4 on W. side mound of stones for 1/4 Sec. Cor.
67,00	Bench bluff. bears E. & W. descend.
69,50	Trail bears N.W. & S.E.

Subdivisions. Tp. 41 S. R. 12 W.

Chains		Chains
7 11,11	Foot of bluff bears E. & W.	
8 11,11	Set Limestone 14 x 8 x 5 in. 9 in deep, ~~Notched~~ 2 on E. & S. edges & raised mound of stones for Cor. to Secs. 22. 23. 26. & 27.	24,11 47.5 53.4
	Land mostly level, Soil 1st rate, No Timber,	54,11 54.5
		80,00
	East on random line between Secs. 23 & 26, Var. 16° E.	
15,00	Road bears N.W. & S.E.	24,4
25,11	River bluff bears N.W. & S.E. enter Rio Virgen 200 lks. wide. runs N.	
27,00	Fence on E. bank of river bears N. & S. enter	8 11,1

Salt Lake Meridian

Chains	cultivated fields,
24,11 11	Set temporary 1/4 Sec. Cor.
47,50	Ditch runs N.W.
53,40	Stone Wall. bears N.W. & S.E.
54,11 11	Road bears N.W. & S.E.
54,50	Telegraph line bears N.W. & S.E. enter Trachyte bench.
80,00	Intersect N. & S. line at Cor. to Secs. 23. 24. 25 & 26, from which, Meander true line between Secs. 23. & 26,
4,4 11	Set Limestone 20 x 8 x 4 in., 15 in. deep, marked 1/4 on N. side & raised mound of stones for 1/4 Sec. Cor.
8,11 11	The Cor. to Secs. 22. 23. 26. & 27.

Subdivisions. T. 41 S. R. 12 W.

Chains. Land mostly level,
Soil 1st rate,
No timber.

North between Secs. 22 & 23.
Var. 16° E.

5,25 Road bears E. & W.
6,00 " " N. 80. E.
7,00 Telegraph line bears E. & W.
10,80 The Eastern of two adobe houses in line, Enter field,
20,50 Fence bears E. & W. bear field.
23,25 Rio Virgin 75 lks. wide, runs S. W.
25,00 Mouth of short hollow. heads N. 10° W.
33,30 Road bears N.E. & S.W.
A Line Kiln bears N. W.
250 chs. dist.

BOOK-A-152

Salt Lake Meridian

T. 7 N.

Chains	
40.00	Set Sandstone 13x11x6 in., 9 in. desc. marked 1/4 on E. side & raised mound of stones for 1/4 Sec. Cor.
46.75	Road bears N.E & S.W.
	in hollow drains S.W.
80.00	Set Sandstone 14x10x5 in., 10 in. desc. notched 2 on E. & 3 on S. edges, & raised mound of stones for Cor. to Secs. 14. 15. 22. & 23.
	Land undulating,
	Soil 1st rate,
	No Timber,

East on random line
Between Secs. 14 & 23,
Var. 16° E.

5.60	Wash drains S.

Subdivisions T. 41 S. R. 12 W.

Chains.	
28,50	Wash drains S.E.
37,00	Head of wash drains S.E.
40,00	Set temporary 1/4 Sec. Cor.
42.50	Descend,
50,75	Trail bears N.W. & S.E.
	in. hollow, drains S.E.
55,00	Leave hollow,
56,55	Road bears N.E. & S.W.
75,85	" " N. & S.
78,50	North creek 150 lks. wide
	runs S.
80,00	On E. bank of North
	Creek, Intersect N. & S. line
	at Cor. to Secs. 13. 14. 23. & 24.
	from which,
	West on true line
	between Secs. 14 & 23,
40,00	Set Sandstone 24 x 13 x 2 in.
	18 in. deep, marked 1/4 on
	N. side & raised mound

Chains

80,

25,

41,

61.

81,

Salt Lake Meridian

Chains	
	Stones for 1/4 Sec. Cor.
80,00	The Cor. to Secs, 14. 15. 22 & 23,
	Land undulating,
	Soil 1st rate,
	No Timber.

	North between Secs, 14 & 15,
	Var. 16° E.
25,00	Wash drains S.E.
40,00	Set Sandstone 12x8x6in.
	9 in. deep, marked 1/4 on
	W. side, & raised mound
	Stones for 1/4 Sec. Cor.
61,00	Foot of bluffs bears E. & W.
80,00	In bluffs, not set, therefore
	at 61,00 chs. Set a Conglom-
	erate rock, 14x8x7in.
	10 in. deep, marked 2
	notches on E. & 4 on S.

Subdivisions. Sec. 41 S. R. 12 W.

		Chains
Chains,	edges & W.C. for Witness Cor. to Secs. 10. 11. 14. & 15, Land undulating Soil 1st rate, Not timber,	80.24
	East on random line between Secs. ~~11.~~ & 14 & ~~15~~ Var. 16° E. Note; Line in place impracticable. Offset 28.50 chs. S. thence E. 80.24 chs. to,	30.00
80.24	Intersect N. & S line at W.C 28.50 chs. S. of cor. point to Secs. 11. 12. 13 & 14 from which,	35.00
	West on true line with Offsets, between Secs. ~~11.~~ & 14 & ~~15~~	40.00
40.12	Set Soapstone 24 x 16 x 12, 18 in. deep marked 1/4 W.C. on N. side & raised mound of stones for Witness 1/4 Sec. cor. 28.50 chs. S. of the cor. Point.	45.00

Sacramento Meridian.

Chains.	
80,24	The Cor. to Secs. 10, 11, 14, & 15;
	Land broken.
	Soil 2nd rate.
	Mn timber.
	March 22d 1877. F. C. Bailey.
	" 23d 1877 by J. G. Burrell
	Note; Abandon line North,
	From the Cor. to Secs. 33,
	& 34, on S. boundary.
	North between Secs.
	33 & 34.
	Var. 16° E.
30,00	Enter E. point of low bluff,
	bears N.E. & S.W.
35,00	Top. of same bears, N.E. & S.W.
40,00	Set Soapstone 5" x 8" x 3 in.
	36 in. deep, marked 1/4 on
	W. side, & raised mound
	of stones for 1/4 Sec. Cor.
45,00	Enter flat.

Subdivision. 2 ℄. 4 S. R. 12 W.

Chains.	
53,00	Road bears E & W,
80,00	Set Shale rock, 2 ft 4 in 2 in, 18 in. deep, notched 3 on E, & 1 on S. edges & raised mound of stones for Cor. to Secs, 2 ℄. 28, 33. & 34.
	Land nearly level,
	Soil 1st rate,
	No timber,

	East on random line between Secs. 2 ℄. & 34.
	Var. 16° E.
8,00	Gulch drains N. E.
13,00	Ridge bears N. E. & S. W.
18,00	Gulch drains N.
21,00	" " "
30,00	" " "
41,00	Set temporary 1/4 Sec. Cor.
54,00	Gulch drains N. E.

Salt Lake Meridian,

Chains.	
75,00	Road bears N.E. & S.W.
80,20	Intersect N. & S. line at Cor. to Secs. 26, 27, 34 & 35, from which,
	West on true line between Secs. 27 & 34,
40,00	Set Dolomite 20x10x6 in. 15 in. deep, marked 1/4 on N. side & raised mound of stones for 1/4 Sec. Cor. on S.E. side of road
80,20	The Cor. to Secs. 27, 28, 33 & 34. Land nearly level. Soil Private, No timber.

North between Secs. 27 & 28

Var. 16° E.

24,00	Leave high bank, Descend,
25,00	Enter flat, bears E. & W.

Subdivisions of T. 41 S. R. 12 W.

Chains.		Chains.
40,00	Set Sandstone 20×10×5 in. 15 in. deep, marked 1/4 on W. side, & raised mound of stones for 1/4 Sec. Cor,	Chain
63,60	Road bears E. & W. Enter bottom,	
64,40	Fence bears E. & W. enter cultivated land,	
72,40	Fence bears E. & W. leave cultivated land,	
76,00	Rio Virgen, 12 in. deep, runs W.	
79.95.	Leave same. Fence bears E. & W. enter Cultivated land,	
80,00	Set Slate rock, 26.×8×5 in, 18 in. deep, notched 3 on E. & 2 on S. edges; & raised mound of stones for Cor. to Secs. 21, 22, 27, & 28. Land mostly level.	12,5 14,0 20,0 25,0

BOOK-A-152

505

Salt Lake Meridian

Chains	Soil 1st rate, No timber,
	East on random line between Secs. 22 & 27, Var. 16° E.
	Note; The line in place being impracticable on account of deep river bend, I therefore cause a flag to be set on Extreme East edge of Water, Then run N. 69° E. 8,50 thence S. 56 1/4° E, 5,50 Chs, which by Calculation gives,
12,52	To flag on line,
14,00	Fence bears N.W. & S.E.
20,75	" " N.E. & S.W.
25,75	Ditch on edge of bench runs N.W.

Subdivisions of T. 41 S. R. 12 W.

Chains.		Chains.
29.50	Fence bears N.W. & S.E.,	66,00
32,10	Road " N. & S.,	66,40
32.20	Mathews house, bears	68.20
	S. 30. E. 2,00 chs,	69.50
40,00	Set temporary 1/4 Sec. Cor.	70,50
44,03	East side of street	71,00
	Enter Virgin City,	
45,40	Fence bears N.E. & S.W.	74,00
48,46	Division fence bears N. & S.	
51,90	W. side of street fence	80,00
	bears N. & S.	
52,95	East side of street fence	
	bears N. & S.	
55,95	Fence bears N. & S.	
57.50	" " "	40,00
60,64	" " "	
63,00	" " (Crosses division	
	Lines in Virgin City.)	
64.60	Mill race runs S.W.	80,00
65,40	Road bears N. & S.	

BOOK-A-152

Salt Lake Meridian

Chains,	
66,00	Road bears N. & S.
66,40	Rio Virgin, 15 m. deep, runs S.
68,20	Across same
69,50	Road bears N.E. & S.W.
70,50	" " " "
71,00	E. branch of Rio. Virgin 100 lks. wide, runs S.W.
74,00	Fork of bench hills bear N.E. & S.W.
80,00	Intersect N. & S. line at Cor. to Secs. 22, 23, 26, & 27, from which, West on true line returns Secs. 22 & 27.
40,00	Set Sandstone 14 x 10 x 4 in., 10 in. deep, marked 1/4 on N. side, & raised mound of stones for 1/4 Sec. Cor.
80,00	The Cor. to Secs. 21, 22, 27 & 28. Land mostly level &

Subdivisions. Sec. 4, T. 1 S. R. 12 W.

Chains,

Chains, under cultivation,
Soil 1st rate,
No Timber,
8 11,00

Surv. between Secs. 21, & 22,
Var. 16° E,

1,50 State bluff, 50 ft. high
bears N.E, & S.W, bears
Cultivated land,

17,25 Telegraph line bears
N.W, & S.E,

17,50 Road bears N.W. & S.E.

24,25 " " E, & W,

40,00 Set Lava rock 15 x 8 x 6 in,
10 in. deep, marked 1/4 on
W, side, & raised Mound
of stones for 1/4 Sec. Cor,

55,00 Foot of bluff debris
bears E, & W.

Note;

Chains,
80,00 Falls in bluff, not set,
Therefore at 55,00 chs, Set
Sandstone 24 x 10 x 5 in, 9
in, deep, marked 3 notches
on E, & S, edges, & W.C, &
raised mound of stones
for Witness Cor, to Secs,
15, 16, 21 & 22,
Land mostly level,
Soil 1st rate,
No timber,

East on random line between Secs, 15 & 22,
Var, 16° E,

Note; Line in place impracticable, therefore
from the Witness Corner, 25 chs, S, of
Cor, Joint, to Secs, 15, 16, 21 & 22, I run,
on offset lines E, 69.16 chs, thence
N, 25 chs, to—

Subdivisions Sec. 21 T. 12 N.

Chains.		Chains.
69,16	Auline in place at foot of bluff, debris, bears N.W. & S.W.	
80,16	Intersect N. & S. line at Cor. to Secs. 14. 15, 22 & 23, from which, West with Offsets on true line between Secs. 15 & 22,	41,11
41,08	Falling in bluffs Cannot be set therefore at 11 chs. Set Sandstone 20 x 6 x 2 in. 15 in. deep marked 1/4 N.C. on N. side for Witness to Sec. Cor. raised mound of stone	69,2
80,16	The Cor. point to Secs. 15, 16, 21 & 22, Land undulating & broken, Soil 1st rate, No timber Note: Abandon Survey north.	80,11

From the Cor. to Secs. 32 & 33, on S. Boundary, North between Secs. 32 & 33,

Salt Lake Meridian,

Chains,

Var. 16° E.

Note; Line in place impracticable, therefore I offset, W. 20 chs, thence North, 50 chs, thence E. 20 chs, to a point on line 10 chs. N. of,

40,00 Where I set a Sandstone 16x10x 5 in, 11 in, deep, marked 1/4 M.C. on W. side & raised mound of stones for. Witness 1/4 Sec. Cor.

69,25 Mark drains N.E.,

80,00 Set Sandstone 12x9x5 in, 8 in. deep, notched 4 on E, & 1 on S. edges, & raised mound of stones for Cor. to Secs. 28, 29, 32 & 33,

Land broken,

Soil 3rd rate,

No timber,

Earth w/ random line between

512

Subdivisions. T. 41 S. R. 12 W.

	Chains, Sees, 28 & 33,
	Var. 16° E,
0.50,	Wash drains N.W.
7.50	Foot of broken bluffs, bears
	N.E, & S.W. thence Offset N, 30 chs,
	thence E, 72.60 chs, thence S, 30 chs, to
80.10,	Intersect N. & S. line at Cor. to
	Sees, 27, 28, 33 & 34, from which,
	West on true line with Offsets
	between Sees, 28 & 33,
40.50	Falls in broken ground cannot
	be set, therefore at, 72.60 chs,
	on true line
	Set Sandstone 12 x 10 x 5 in, 8 in,
	deep, marked 1/4 W.C. on N. side,
	Trench mound of stones for
	Witness 1/4 Sec. Cor,
80.10,	The Cor, to Sees, 28, 29, 32, & 33,
	Land mostly broken,
	Soil 2nd rate,
	Timber,

Salt Lake Meridian,

Chains,	North between Secs. 28 & 29.
	Var. 16° E.
6,50	Wash drains N.W.
15,00	Road bears N.E. & S.W.
40,00	Set Sandstone 12×9×5 in, 8 in. deep, marked 1/4, on W. side & raised mound of stones for 1/4 Sec. Cor.
61,00	Gulch drains N.W.
80,00	Set Sandstone 15×7×6 in, 10 in. deep, notched 4 on E. & 2 on S. edges, & raised mound of stones for Cor. to Secs. 20. 21, 28 & 29.
	Land broken,
	Soil 2nd rate,
	No timber.

Subdivisions, 2/ 41 S. R. 12 W.

Chains,	East on random line between Secs, 21, & 28, Var. 16° E.	
	Note; It being impracticable to chain line in place on account of river brake, I cause a flag to be set in line on E. side of same which from a Base, 1/2 mile S, bears N, 45 E, which would give distance to flag,	40,11
41,00	Where I left temporary 1/4 Sec, Cr, about 17 chs. E. of the river.	80,22
46,50	Rock Wash drains S,	
55,50	" " " S. E,	
77,00	Enter river bottom,	
78,50	Fence bears N, & S, enter Cultivated land,	
80,22	Intersect N, & S. line at	

Jack Lake Meridian.

Cor, to Secs, 21, 22, 27, & 28,
from which,
West on true line
Returns Secs, 21 & 28,
40,11 Set Black Lava rock, 16,
x 10 x 5 in, 12 in, deep, marked
1/4 on N. side & raised mound
of stones for 1/4 Sec. Cor,
80,22 The Cor, to Secs, 20, 21, 28 & 29,
Land broken,
Soil 2nd rate,
Not timber.

North Returns Secs. 20 & 21,
Var, 16° E,
Note; Chaining being impracticable
on account of river breaks,
I cause a stay to be set
on N. side of breaks, another

	on N side of brs ake,	Clair
	From last flag, I measure	
	North 23 chs, & E, 15 chs,	
	to first flag, =	
23,00	On line in place, 10 chs. N. of	
32,75	Road bears E, & N,	
36,00	Telegraph line bears E. & W,	
40,00	Set Limestone 5+ x 8 x 5 in	
	24 in, deep, marked 1/4 on,	
	N, side & raised mound	
	of stones for 1/4 Sec, Cor,	
55,00	S'ort of bluff, bears E, & N,	
80,00	On bluffs, not set,	80,00
	Therefore at 55,00 chs,	
	Set Gypsum, 14 x 12 x 4 in,	
	10 in, deep, marked. 4	
	notches on E, & 3 on S, edges,	
	& N. C. for Witness Cor,	
	to Secs, 16, 17, 20, & 21,	40,00
	Land mostly broken,	

Salt Lake Meridian

Chains

Soil 2d rate,
No timber,

East on random line
between Secs. 16 & 21,
Var. 16° E,

Note; Line in place impracticable, Therefore from Witness Corner 25 chs, S, of corner found, to Secs. 16, 17, 20 & 21, I run E, on Offset line to,

80,00 Intersect N. & S. line at Witness Cor, 25 chs, S, of the Cor. found, to Secs. 15, 16, 21, & 22, from which,

Set on true line (Offset) between Secs. 16 & 21,

64,00 Set piece of Gypsum 18 x 17 x 14. 12 in. deep marked 1/4 M.C. on S. side & raised mound of stone for witness 1/4 sec. cor. 25. chs. South of true cor. point.

Subdivisions. Tp. 41 S. R. 12 W.

Chains.	
80,00	The Cor. post to Secs. 16, 17, 20, & 21,
	Land broken,
	Soil 2nd rate,
	No timber,
	Note; Discontinue further Survey North,
	March 23d 1877 J. G. Burrill
	March 23d 1877 by T. C. Bailey From the Cor. to Secs 31 & 32 on S. Boundary,
	North returns Sections 31 & 32
	Var. 16° E.
5,80	Road bears N.E. & S.W.
	to Nash drains N.E.
32,10	Nash drains N.W.
40,00	Set Limestone 14 x 8 x 5 ins, 10 ins. deep, marked 1/4 on N. side & raised mound of stones for 1/4 Sec. Cor.

Sackakie Meridian

Chains	
52,00	Road bears N.E. & S.W.
80,00	Set Sandstone 26×12×2 ins, 18 ins, deep, notched 5 on E. & 1 on S. edges & raised mound of stones for Cor. to Secs, 29, 30, 31 & 32,
	Land mostly level,
	Soil 1st rate,
	No timber,

	East on random line between Secs, 29 & 32,
	Var, 16° E,
25,00	Gulch wash drains N.E,
411,00	Set temporary ¼ Sec, Cor,
42,20	Road bears N.E. & S.W,
80,13	Intersect N. & S. line at Cor, to Secs, 28, 29, 32 & 33, from which,

570

Subdivisions 2N. 41 S. R. 12 W.

Chains	
	West on true line between Secs. 29 & 32,
40.07	Set Limestone 20 x 20 x 2 in. 15 in. deep, marked 1/4 on N. side & raised mound of stones for 1/4 Sec. Cor.
80.13	The Cor. to Secs. 29, 30, 31 & 32.
	Land mostly level.
	Soil 1st rate,
	No Timber.

	West on random line between Secs. 30 & 31, Var. 16° E.
2.10	Wash drains N.E.
40.00	Set Temporary 1/4 Sec. Cor. thence Offset to avoid broken ground S. 30 chs, thence W. 40.16 chs. to

Salt Lake Meridian

Chains	
80,16	Intersect St. Boundary of T., at Witness Corner 30 chs, S. of Cor, Limb to Secs 30 & 31, from which, East on true line with Offsets, between Secs, 30 & 31,
40,16	On line in place, Set Limestone 30,x16x2 in, 20 in, deep, marked 1/4 on N. side, & raised mound of stones for 1/4 Sec, Cor,
80,16	The Cor, to Secs, 29, 30, 31 & 32, Land broken, Soil 2nd rate, No Timber

North between Secs, 29 & 31
Var. 16° E.

Subdivisions, 2, 41 S. R. 12 W.

Chains	
2,75	Mark drains N.E.
40,00	Set Limestone 14 x 7 x 6 in., 9 in. deep, marked 1/4 on N. side, & raised mound of stones for 1/4 Sec. Cor.,
55,00	Rivr breaks bear E. & W. Measure a base 10 chs. E. from which a flag on line on N. side of breaks, bears N. 35° 55' W. the calculation gives distance 13.80 chs=
68,80	To flag on N. side of river breaks, 46 chs. N. of River,
80,00	Set Limestone 16 x 12 x 3 in., 12 in. deep, notched 5 on E. & 2 on S. edges & raised mound of stones for Cor. to Secs. 19. 20, 29 & 30.
	Land mostly level,
	Soil 1st rate

Sackbake Meridian.

Chains.	No Timber
	East on random line between Secs. 20 & 29, Var. 16° E,
12,00	Bend of river breaks, bears N. & S.
35,50	Across same,
40,00	Set temporary 1/4 Sec. Cor,
49,50	Small crack in river breaks,
65,00	Flagpoint established in running North, between Secs. 21 & 21, 15 chs. W. of
80,00	Intersect N. & S. line at Cor. to Secs, 20, 21, 28 & 29, from which,
	W. on true line between Secs. 20 & 29,
4,00	Set Bachyte 13 x 8 x 4 in,

Subdivisions Tp. 41 S. R. 12 W.

Chains		Chains
	9 in deep, marked 1/4 on	
	N. side & raised mound	
	of stones for 1/4 Sec. Cor.,	
80.00	The Cor. to Secs. 19. 20, 29 & 30,	
	Land broken,	40.12
	Soil 2nd rate,	
	No timber,	80.12

	With random line	
	between Secs. 19 & 30,	
	Var. 16° E.	
	Note: The line in place	
	impracticable on account	38.00
	of broken ground & river	40.00
	breaks, I therefore offset	
	N. 3.04 chs. thence W. 80.12	
	chs. to,	
80.12	Intersect N. boundary of	59.5
	Tp. at Witness Cor. 3.04 chs.	59.5
		60.00

Chains

N. of the cor. Smith, to Secs.
19, & 30, from which,
E, on true line with offsets
between Secs. 19 & 30,
Set Trachyte 16 x 10 x 9. in. deep
40.12 marked 1/4 N. C. on N. side & raised
mound of stones for witness 1/4 Sec. cor.
37.94 Chs. N. of the cor. point.—
80.12 The cor. to Secs. 19, 20. 29 & 30.
Land broken,
Soil 3rd rate,
No timber.

North between Secs. 19 & 20,
Var. 16° E.
38.00 Road bears N.W. & S.E.
40.00 Set Gypsum 14 x 8 x 5 in. 9 in.
deep, marked 1/4 on N. side
& raised mound of Gypsum
for 1/4 Sec. Cor.
57.50 Trail bears E. & W.
59.50 Telegraph line bears N.E. & S.W.
64.00 Foot of bluff bears E. & W.

Subdivisions of Sec. 4, T. 8 S., R. 12 E.

Chains		
8.11.10	In bluffs not set, thence at 60.00 chs, Set a Limestone 14 x 8 x 5 in., 9 in. deep, marked 5 notches on E. & 3 on S. edges & W.C. & raised mound of stones for Witness Cor. to Secs. 17, 18, 19 & 20. Land nearly level, Soil 1st rate, No timber.	40.32 / 80.63
	East on random line between Secs. 17 & 20, Var. 16° E., Note: Line in place impracticable, therefore Offset S. 25 chs, thence E. 80.63 chs. to Intersect N. & S. line at Witness Corner, 25 chs. S.	40.00 / 60.80
80.63.		

BOOK-A-152

Salt Lake Meridian,

of Cor. point to Secs. 16, 17, 20 & 21,

from which

West on true line with offsets

between Secs. 17 & 21,

40.32 Set Limestone 18 x 9 x 6, 12 in. dep marked ¼ M.C. on S. side, & raised mound of stones for witness ¼ Sec. cor. 25.00 chs. E. of true cor. point.

81,63 The Cor. to Secs. 17, 18, 19 & 20,

Land broken,

Soil 2nd rate,

No Timber,

West on random line

between Secs. 18 & 19,

Var. 16° E.

On account of broken ground

offset 20 chs. S, thence W.

40 chs. thence N. 20 chs. to

40,00 On line, in place. Set

temporary ¼ Sec. Cor.

60,50 Road bears N.W. & S.E.

Subdivision of Sec. 4, T. 8 S., R. 12 W.

Chains	
67,00	Telegraph line bears N.W. & S.E.
80,00	Intersect N. Boundary of Sec., at Cor. to Secs. 18 & 19, from which, East on true line between Secs. 18 & 19,
40,00	Set Sandstone 14 x 9 x 6 in., 9 in. deep, marked 1/4 on N. side, & raised mound of stones for 1/4 Sec. Cor.
80,00	The Cor. to Secs. 17, 18, 19 & 20, Land mostly level, Soil 2nd rate, No timber.

Note: On account of the red bluffs to the N. I abandon the survey here.

BOOK A-152

Salt Lake Meridian

679

General Description.

The Surveyed portions of this Township embrace the bottoms of North Creek, & the Rio Virgen & the adjacent benches. The Settlement of Virgin city, lies partly in Secs 22 & 27, & has a population of about 200, Mountain Dell, another small Settlement lies mostly in the S.E. cor. of Sec. 1, March 23d 1877. F. G. Bailey U. S. Deputy Surveyor.

BOOK-A-152

U. S. SURVEYOR GENERAL'S OFFICE.

Salt Lake City, Utah, June 6th 1877

The foregoing field notes of the survey of

S & E. Boundaries & Subdivisions

Township No. 41 S *Range No.* 12 W

Executed by Bailey & Burrill

Under joint *contract of the* 4th

day of Sept *187*6*, in the month of*

March *187*7*, having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.*

Chauncey Kimball

Surveyor General for Utah.