OK-A-162

R:

Filed January 29th 1880

Examined by T. C. Bailey

Compared by O.C.L. and F.L.d.G.

FIELD NOTES

OF

THE SURVEY OF THE

Exterior

of Township No. 7 S., Range No. 20 E.

of the Salt Lake Meridian in Utah Territory.

BY

Augustus D. Gunn

U. S. DEPUTY SURVEYOR,

Under his Contract No. 92

dated June 13. 1879

Survey commenced Oct. 20 1879.

Survey completed " " 1879.

OK-A-162

R:

Filed January 29th 1880

Examined by T. C. Bailey

Compared by O.C.L. and F.L.d.G.

FIELD NOTES

OF

THE SURVEY OF THE

Exterior

of Township No. 7 S., Range No. 20 E.

of the Salt Lake Meridian in Utah Territory.

BY

Augustus D. Gunn

U. S. DEPUTY SURVEYOR,

Under his Contract No. 92

dated June 13. 1879

Survey commenced Oct. 20 1879.

Survey completed " " 1879.

BLANK
PAGE

North Boundary Tp. 7 S. R 20 E

Sand, broken
Soil 2nd & 3rd rate,
No Timber
Augmented on 80 chs.

West on true line bet. Sec.
2 and 35.
Va 16° 30' E.

4.00 Leave bad lands, enter bench
5.50 Road bears N.E. & S.W.
40.00 Set Sand Stone 21 x 12 x 7.
15 in deep, marked 1/4 on
N. side with Stone mound
for 1/4 Sec Cor. ... 35
80.00 Set Sand Stone 19 x 10 x 6,
12 in deep; marked 2 Notches on
E. and 4 on West edges, with
Stone mound for Cor to Sec.
2. 3. 34 and 35

Salt Lake Meridian 4

Land mostly level bench
Soil 1st rate
No Timber

West on true line bet.
Sec.s 3 and 34.
Var 16° 30' E.

8.60	Wash drains S.
21.00	" " S.E.
40.00	Set Sand Stone 14 x 10 x 4 9 in deep, marked 1/4 on N. Side with Stone mound, for 1/4 Sec cor.
80.00	Set Sand Stone 25. x 13 x 11 18 in deep, marked 3 Notches on E. & W. edges, with Stone mound for Cor to Sec.s 3. 4. 33 & 34.

Land level. Soil 1st rate;
No Timber

North Boundary Tp. 9 S. R 20 E

West on true line
bet. Sec. 11 and 33,
Va 16° 30' E.

39.25 Wash drains S.E.

40.00 Set sand stone 16×10×7
11 in deep, marked 1/4 on
N. side with stone mound
for 1/4 Sec. cor.

80.00 Set sand stone 30×20×6
20 in deep, marked 4 Notches
on E. and 2 on W. edges, with
stone mound for cor to Sec.
4.5.32. & 33
Land - bench.
Soil, 1st rate
No Timber

Salt Lake Meridian

West on true line bet.
Secs. 5 and 32.
Va 16° 30' E.

40.00 deposited small sand
stone marked with a cross (4)
in ug. mound of earth
and pits for 1/4 sec cor.
63.50 Descend into Hollow
71.00 Ascend from "
80.00 Set sand stone 15×10×6, 10
in deep, marked 5 Notches
on E. and 1 on W. edges,
with stone mound for cor to
Secs. 5. 6. 31. & 32.
Land mostly good bench;
Soil 1 & 3rd rates
No Timber

BOOK-A-162

North Boundary Tp 7 S. R 20 E.

West, on true line, bet.
Secs. 6 & 31.
Va 16° 30' E.

7.00 Descend
20.00 Enter flat.
40.00 Set Sand Stone 36 × 20 × 4. 24 in deep, marked 1/4 on N. side with stone mound for 1/4 Sec.
59.00 Wash drains S.W.
77.50 (Allowing for Convergency of Meridian) Set Sand Stone 36. × 12. × 8. 24 in deep, marked 6 Notches on N. S. E & W. edges with regulation mound and pits for Cor to Tps. 6 & 7 S. R. 19 and 20 E.
Land broken bench;
Soil 1st & 2nd rate
No Timber

BOO

West.

~~40.00~~
23.00
40.00
80.00

West. Boundary Tp 7 S. R 20 E.

From the cor to Tps 6 & 7 S.
R. 19 & 20 E. I run
South bet Sec.s 1 and 6.
Va 16° 30' E.

~~40.00~~
23.00 Wash drains S.W.
40.00 Set charred cottonwood post. 4 x 4 in 4 ft long, 2 ft deep, marked 1/4 on W. side with reg. mound & pits for 1/4 sec cor.

80.00 Set charred cottonwood post. 4 x 4 in 4 ft. long, 2 ft deep, marked on Notch on N. and 5 on S. edges with Reg mound and pits for cor to Sec.s 1. 6. 7 and 12.

Land level bench;
Soil, 12 rate;
No Timber

South bet. Sec 7 & 12 Va 16° 30' E.

West Boundary Tp. 7 S. R 20 E.

40.00 Set charred Cottonwood post 4 x 4 in. 4 ft long, 2 ft deep, marked 1/4 on W. edges, with reg. mound and pits for 1/4 Sec. cor

80.00 Set charred cottonwood post 4 x 4 in. 4 ft long, 2 ft deep, marked 2 Notches on N. and 4 on S. edges with Reg. mound and pits for cor to Sec. 7. 12. 13 & 18, Land level;

Soil, 1st rate;

No Timber

South bet. Sec. 13 & 18

Va 16.30 E.

40.00 Set charred cottonwood post 4 x 4 in. 4 ft long, 2 ft deep, marked 1/4 S. on W. Sides with

Salt Lake Meridian

Reg. mound and pits for ¼ Sec. cor.

60.00 Wash drains S.W.

80.00 Set charred cottonwood post 4 x 4 in. 4 ft. long, 2 ft. deep, marked Tetafcheson N & S. edges with Reg. mound and pits for cor. 4 Sec.s 13. 18. 19 and 24.

Land level;

Soil, 12 Strata;

No Timber.

South bet. Sec.s 19 & 24

Vol. 30 C.

40.00 Deposited 1 Pint Pebbles in reg. mound & pits for ¼ Sec. cor.

56.00 Road bears N.W. & S.E.

62.50 Intersect N.E. boundary of Uintah Ind. Reservation

77 BOOK-A-162

West Boundary Tp. 7 S. R 20 E.

At a point N. 23° W. 27.25 chs. dist.
from mile Cor. No. 6.
Where I set a chaud cottonwood
post 4x4 in. 4 ft long, 2 ft deep
marked C.C. with reg. mound and
pits for closing Cor. to fractional
Sec. 19 & 24.
Land level,
Soil 1st rate,
No Timber
Oct. 30th 1879

Note for General Description
see Subdivisions of this Tp.
A. D. Ferron
Dep. Surveyor

BOOK-A-162

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, Feb 24 1880

The foregoing field notes of the survey of the

Exterior boundaries of

Township No 7 S. *Range No* 20 E.

of the Salt Lake Meridian, Utah Territory,

Executed by A. D. Ferron

Under joint *contract No* 92

of the 13th *day of* June 1879.

in the month of Oct. 1879.

having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.

Frdc. Salomon

U. S. Surveyor General for Utah.

BOOK-A-162
R: 1880. 162

13

Filed 187 .

Examined by T. C. Bailey

Compared by D. E. S. & T. L. A. Gorliaski

FIELD NOTES

OF

THE SURVEY OF THE

Subdivisions

of Township No. 7 S. , Range No. 20 E.

of the Salt Lake Meridian in Utah Territory.

BY

A. D. Ferron

U. S. DEPUTY SURVEYOR,

Under his Contract No. 92

dated June 13th 1879.

Survey commenced Oct. 21 1879.

Survey completed " 27 1879.

Book 162

Exterior Boundaries and Subdivisions

Township 7 S. R. 20 E.

	7	6	5	4	3	2
8	6 / 71	5 / 54	4 / 44	3 / 35	2 / 25	1
	70	68	57	43	34	24
8	7 / 68	8 / 53	9 / 43	10 / 33	11 / 23	12
	67	66	51	42	31	21
9	18 / 65	17 / 51	16 / 41	15 / 31	14 / 20	13
	64	63	50	40	30	19
10	19 / 62	20 / 49	21 / 39	22 / 29	23 / 18	24
	61	60	48	38	28	17
	30 / 59	29 / 47	28 / 37	27 / 27	26 / 16	25
	58	56	46	37	26	15
	31 / 55	32 / 45	33 / 36	34 / 26	35 / 14	36

Meanders 72-74

BOOK-A-162

Subs Tp 7 S., R. 20 E. S.L. Mer'd.

Survey commenced Oct 21. 1879.
by A. D. Peterson.
From the established Cor.
to Secs. 35 & 36 on the S. Boundary
of the Tp. & run
North between Secs. 35 & 36
Var. 16° 30' E.

40.00 Set Sandstone 14x10x8, 9 in. deep
marked 1/4 on N. side, with
regulation mound of earth
and pits for 1/4 Sec. Cor.

80.00 Set Limestone 12x12x5, 8 in.
deep, marked 1 notch on S.
& E. edges with stone
mound for Cor. to Sec.
25, 26, 35 & 36.

Land Bench
Soil 1st rate
No Timber

Subs Tp 7 S. R 20 E

	East on random Line between Secs. 25 + 36
	Var. 16° 30' E.
36.00	Wash drains N. W.
40.00	Set temp. 1/4 Sec. Cor.
48.00	Descend Green Ke. Bluff
80.86	Intersect E. Boundary of Tp. 92 Chs. S. of Cor. to Sec 25 + 36. From which S. 89° 23' W. on true line between Secs. 25 + 36.
40.43	Set Cobble stone 12 x 9 x 6, 8 deep, marked 1/4 on N. e with stone mound for 1/4 Sec. Cor.
80.86	The Cor. to Secs. 25, 26, 35 +
	Land Bench + Bluff Breaks.
	Soil 2nd rate
	No Timber

S. ...

	Au...
	No...
26.00	Ho...
39.00	"
40.00	Se...
	8 en...
	se...
	1...
60.50	He...
	7...
80.00	De...
	ar...
	Co...
	Pi...
	ar...
	mo...
	Co...

T. L. Merrill.

Remembered on 32.86 ch.

North between Sec. 25 & 26
Var. 16° 30' E.

26.00 Hollow drains S. W.

39.00 " " " "

40.00 Set Cobble stone 12 x 9 x 6, 8 in. deep, marked 1/4 on W. side with stone mound for 1/4 Sec. Cor.

60.50 Head of Hollow drains N. 70° E.

80.00 Deposited 1/2 Gal. Bois du vac and drove a charred cottonwood stake in S. E. Pit, marked 2 notches on S. and 1 on E. edges with seg. mound of earth and pits for Cor. to Secs. 23, 24, 25 & 26

Subs. Tp 7 S., R 20 E.

Land Broker Bench
Soil 2nd rate
No Timber

East on random line
between Secs. 24 & 25
Var. 16° 30' E.

24.00	Descend Green R. Break
24.50	Right Bank of Green R. 4 ft. deep runs S. E.
33.68	Left Bank of Green R
40.00	Set temp. 1/4 Sec. Cor.
60.00	Enter Bench
80.60	Intersect E. Boundary of Tp. 62 lks. S. of Cor. to Secs. 24 & 25. From which S. 89° 33' W. on true line between Secs. 24 & 25.
40.30	Set charred Cotton wood Post 4 x 4 in, 4 ft. long, 2 ft

S.

4632

55.50

80.60

S. L. Meridian

Deep, marked 1/4 S. on N. side with regulation mound of Earth and pits for 1/4 Sec. Cor.

4.32 Set Charred Cotton wood Post, 4x4 in. 4 ft. long, 2 ft. deep marked M. C. for Meander Cor. to fractional Sec. 24 & 25.

5.50 Set Charred Cottonwood Post, 4x4 in. 4 ft. long, 2 ft. deep marked M. C. for Meander Cor. to fractional Sec. 24 & 25.

80.60 The Cor. to Sec. 23, 24, 25 & 26.

Land level & level
Soil 1st rate
No Timber

North between Sec. 23 & 24
Var. 16° 30' E.

Subs Tp 7 S. R. 20 E.

40.00	Set charred Cottonwood Post 4x4 in., 4 ft. long, 2 ft. deep on 1/4 S. on W. side for with regulation mound of earth & Pits for 1/4 Sec. Cor.	40.00 53.00 80.00
80.00	Set Sandstone 10x10x6, 7 in. deep, marked 3 notches on S. and 1 on E. edges with regulation mound of earth and Pits for Cor. to Secs. 13, 14, 23 & 24.	40.00
	Land level Soil 1st rate No Timber	80.00
	East on random line between Secs. 13 & 24 Var. 16° 30' E.	
28.00	Enter Hollow	25.00

S. L. Meridian

40.00	In main Wash, drains S.E. set temp. 1/4 Sec. Cor.
53.00	Leave Flat
80.00	Intersect E Boundary of Tp. for Cor. to Secs. 13 & 24 From which West on true line between Secs. 13 & 24.
40.00	Set Sandstone 24x14x4, 16 in. deep, marked 1/4 on N. side with stone mound for 1/4 Sec. Cor.
80.00	The Cor. to Secs. 13, 14, 23 & 24. Land level Soil 1st rate No Timber.
	North between Secs. 13 & 14 Var. 16° 30' E.
25.00	Enter Flat.

Subs. Tp 9 S. R 30 E

36.75	Wash drains S. E.
40.00	Set Sandstone 18x12x6, 12 in. deep marked 1/4 on W. side with stone mound for 1/4 Sec. Cor.
43.30	Ascend.
80.00	Set Sandstone 12x10x6, 8 in. deep, marked 4 notches on S. and 1 on E. edges with regulation mound of earth & pits for Cor. to Secs 11, 12, 13 & 14
	Land Broken and rolling Bench
	Soil 1st & 3rd rate
	No Timber

East on random line
Set Secs. 12 & 13
Var 16°30' E.

42.00	Set temp 1/4 Sec. cor.

S. L. Meridian

56.50 Gulch Arus. S
68.25 Wash " S. E.
80.40 Int E. Boundary of
Tp 10 lks N of cor.
to Secs. 12 and 13
from which
N. 89° 5' 4" W on
true line bet Secs. 12 & 13
40.20 Set Cobble stone 14 x 10 x 4,
9 in. deep, marked 1/4
on N side, with reg.
mound of earth and pits
for 1/4 Sec. cor
80.40 The cor. to Secs.
11. 12. 13 & 14
Land rolling Bench
Soil 1st rate
No Timber

Subs Tp 7 S. R 20 E

North bet Secs. 11 & 12
Var 16° 30' E.

5.00 Upper Bench
40.00 Deposit 1/2 Gal. Bois du vac. with reg. mound of earth and pits for 1/4 Sec. cor.
80.00 Set Cobble stone 12x8x6 8 in. deep marked 5 notches on S and 1 on E edges with stone mound for cor to Secs. 1, 2, 11 & 12
Land rolling Bench
Soil 1st rate
No Timber

East on random line bet Secs 1 & 12
Var 16° 30' E.

25.00
40.00
44.00
49.00
75.00
80.55
40.27
80.55

S. L. Meridian

25.00 Leave Bench, enter Bad land hills

40.00 Set temp 1/4 Sec. cor

44.00 Main Gulch drns. N. E.

49.00 Head of Gulch drns. N

75.00 Gulch drns N. N.

80.55. Int. E Boundary of Tp 21 lks N. of cor. to Secs 1 and 12 from which N. 89° 57' W on true line bet. Secs. 1 & 12

40.27 Set Sandstone 30 x 10 x 8 20 in. deep, marked 1/4 on N side with stone mound for 1/4 Sec. cor.

80.55. The cor to Secs. 1. 2. 11. & 12.

Land Mostly Bad lands

Soil 3rd rate

No Timber

Augmented on 55.55 ch's

Subdiv 7 S. R 20 E.

North on random line
bet Secs 1 & 2
Var 16° 30' E.

20.50 Leave Bench, enter Bad lands
40.00 Set Temp. 1/4 Sec. cor.
47.50 Leave Bad lands enter Bench
76.50 Enter " "
80.00 Int N. Boundary of Tp.
at cor. to Secs. 1 & 2
From which
South on true line
bet. Secs 1 & 2.
40.00 Set Sandstone 20 x 12 x 8
13 in. deep, marked 1/4 on
West side, with stone mound
for 1/4 Sec. cor.
80.00 The cor. to Secs. 1. 2. 11 & 12
Land broken Bench
and Balands
Soil 1st and 3rd rate

S. L. Meridian

No Timber

Augmented on 41. chi.

Oct 21, 1879

North bet Secs 34 & 35

Var 16° 30' E.

40.00 Deposit 1/2 Gal Boiss du vac in reg mound of earth and pits for 1/4 Sec. cor.

80.00 Set Sandstone 20 x 6 x 4 15 in. deep marked 1 notch on S and 2 on E E edges for cor to Secs 26. 27. 34 and 35

Land Bench

Soil 1st rate

No Timber

East on random line bet. Secs. 26 and 35

Var 16° 30' E

Subdivd. R 30 E.

28.70 Wagon road bns. N. W. & S. E.
40.00 Int. temp. 1/4 Sec. cor.
55.00 Hollow drns. N. W.
80.30 Int. Rand S. line
at cor to Secs. 25. 26.
35 & 36 from which
Weston tow line
bears Secs. 26 & 35
40.15 Deposit 1 Gal. Bois du
vac. with reg. mound &
earth and Gilt for 1/4 Sec. cor.
80.30 The cor. to Secs 26. 27.
34 and 35
Land broken Bench
Soil 1st rate
No Timber

North bet. Secs. 26. & 27
Var 16° 30' E.
40.00 Deposit 1 Qt. of pebbles

80.00

2.50
40.00
80.20

S. L. Meridian

in reg. mound of earth
and pits, for 1/4 Sec. cor.
80.00 Set Cobblestone 12 x 8 x 6,
8 in, deep marked 2
notches on Sand E Edges
for cor. to Secs. 22. 23.
26. & 27.
Land rolling Bench
Soil 1st rate
No Timber

East on random line
bet. Secs. 23 and 26.
Var 16° 30' E.
2.50 Road bra N & S.
40.00 Set temp 1/4 Sec. cor.
80.20 Int N & S line at cor.
to Secs 23. 24. 25 and 26. from which
West on true line, bet Secs.
23 and 26.

Subs Tp 9 S. R. 20 E.

40.10	Deposit 1 Qt. of pebbles in reg. mound of earth and pits, for 1/4 Sec. cor	
80.20	The cor to Secs. 22. 23. 26 & 27	
	Land level Soil 1st rate No Timber	
		40.00
	North bet. Secs. 22 & 23 Var 16° 30' E.	80.14
39.00	Road Sears N. W. & S. E.	
40.00	Deposit 1 Qt. of pebbles with regulation mound of earth and pits for 1/4 Sec. Cor.	40.07
80.00	Set Sandstone 15"x10"x6", 10 in. deep marked 3 Notches on S and 2 on E edges with regulation mound of earth & Pits, ~~marked 3 notches on S. & 2 on E. edges~~	80.14

BOOK

Sal

Salt Lake Meridian

for Cor. to Secs. 14, 15, 22 & 23
Land level
Soil 1st rate
No Timber

East on random line
between Secs. 14 & 23
Var. 16° 30' E.

40.00 Set temp. 1/4 Sec. Cor.
80.14 Intersect N. and S. line at Cor. to Secs.
13, 14, 23 & 24 From which
West on true line between
Secs. 14 & 23.
40.07 Set Sandstone 14 X 12 X 12,
9 in. deep, with regulation
mound of earth & Pits,
marked 1/4 on N. side
for 1/4 Sec. Cor.
80.14 The Cor. to Sec. 14, 15, 22 & 23
Land rolling Bench

Sub Tp 7 S. R 20 C. | Sa

	Soil 1st rate	
	No Timber	1.00
	North between Secs. 14 & 15	2.00
	Var. 16° 30' E.	3.00
40.00	Deposit small stone,	15.00
	marked with a cross (+)	37.00
	with regulation mound	40.00
	of Earth & Pits for 1/4 Sec Cor.	64.25
77.50	Wash, in hollow, drains E.	80.10
80.00	Set Cobble stone 20 X 14, 10	
	15 in. deep, marked 4	
	notches on S. and 2 on E.	
	edges, with stone mound	
	for Cor. to Secs. 10, 11, 14 & 15.	40.05
	Land Bench	
	Soil 1st rate	
	No Timber	
		80.10
	East on random line	
	between Secs. 11 & 14	

Salt Lake Meridian

Var. 16° 30' E.

1.00	Wash, in Bottom, drains N. E.
2.00	Wash, in Bottom drains S. E.
3.00	" " " " N. E
15.00	Small Hollow " " "
37.00	Large Main Gulch " S. E
40.00	Set temp. 1/4 Sec. Cor.
64.25	Hollow drains S. E.
80.10	Intersect N. & S. line 24 lbs. N. of Cor. to Secs. 11.12. 13 Gm 14. From which North 89°50' W. on true line between Secs. 11 & 14.
40.05	Set Sandstone 14 x 8 x 6, 9 in. deep, marked 1/4 on N. side with stone mound for 1/4 Sec. Cor.
80.10	The Cor. to Secs. 10. 11. 14 & 15.

Sand mostly level

Sub. Tp 7 L. R 20 E

Soil 1st rate
No Timber.

North between Secs. 10 + 11
Var. 16°30' E.

15.00	Leave Bench. Enter Bad Lands	11.00
		40.00
19.50	Wash drains E.	80.22
40.00	Set Sandstone 18 x 8 x 4, 12 in. deep, marked 1/4 on W. side with stone mound for 1/4 Sec. Cor.	
80.00	Set Sandstone 38 x 14 x 6, 25 in. deep, marked 5 notches on S. + 2 on E. edges with mound of stones for Cor. to Secs. 2, 3, 10 + 11	40.11
		80.22

Land level & Broken
Soil 1st + 3rd rate
No Timber

S. L. Meridian

Segmented on 65 Chs

East on random line
between Sec. 2 & 11
Var. 16° 30 E.

11.00	Gulch drains S.
40.00	Set temp. 1/4 Sec. Cor.
80.22	Intersect N. & S. line 18
	Chs. N. of Cor. to Sec. 1.2.11 & 12
	From which
	N. 89° 52' W. on true line
	between Sec. 2 & 11.
40.11	Set Sandstone 26 x 9 x 5;
	17 in. deep, marked 1/4 on N.
	side with stone mound
	for 1/4 Sec. Cor.
80.22	The Cor. to Sec. 2.3.10 & 11

Land level Bench
Soil 1st rate
No Timber

Subs Tp 7 S. R 90 E

	North ~~between~~ on random line between Secs. 2 & 3 Var. 16° 30' E.	
5.00	Wash drains S. E.	
11.10	Road bears N. E & S. W.	
40.00	Set temp. 1/4 Sec. Cor.	40.00
49.00	Leave Bad Land. Enter Bench	
80.23	Intersect N. Boundary of Tp. 20 lks. W. of Cor. to Secs. 2 & 3 From which S. 0° 9' W on true line between Secs. 2 & 3	80.00
40.23	Set Sandstone 20"x15"x6", 15 in. deep, marked 1/4 on W. side with stone mound for 1/4 Sec. Cor.	
80.23	The Cor. to Secs. 2, 3, 10 & 11. Land Broken Bad Lands, & Bench. Soil 1st & 3rd rate	

Salt Lake Meridian

No Timber
Augmented on 49 Chs.
Oct. 22nd 1879

North bet. Secs. 33 & 34
Var 16° 30' E.

40.00 Deposit 1/2 Gal Bois du vac with reg. mound of earth and pits, for 1/4 Sec. cor.

80.00 Set charred Cottonwood post 4" x 4", 4 ft. long 2 ft. deep, marked 1 notch on S and 3 on E edges with reg. mound of earth and pits for cor. to Secs 27, 28, 33 & 34

Land Bench
Soil 1st rate
No Timber

Int. Tp 7 S. R 30 E.

	East on random line bet Secs. 27 & 34 Var 16°30' E	80.00
40.00	Set temp. 1/4 Sec. cor.	
80.00	Int N & S. line at cor to Secs. 27 & 34 from which West on true line bet Secs 27 & 34.	
40.00	Deposit 1 Gal Bois du vac in reg. mound of earth and pits for 1/4 Sec cor.	
80.00	The cor to Secs. 27. 28. 33 & 34 Land Bench Soil 2nd rate No Timber.	40.00
		80.00
	North bet. Secs. 27 & 28 Var 16°30' E.	
40.00	Deposit 1/2 Gal. Bois du vac in reg. mound of earth	

and pits for 1/4 Sec. cor.
80.00 Set Cobblestone 12 x 8 x 6
8 in. deep, marked 2 notches
on S and 3 on E edges,
with reg. mound and
pits for cor. to Secs.
21. 22. 27 & 28
Land Bench
Soil 1st rate
No Timber

East on random line
bet. Secs. 22 & 27
Var 16° 30' E.
40.00 Set temp. 1/4 Sec. cor.
80.00 Set N. & S. line at cor.
to Secs. 22. 23. 26 & 27
From which
West on true line
bet Secs. 22 & 27

Subs Tp 7 S. R 20 E

Sa

40.00 Deposit 1 Qt. of pebbles in reg. mound of earth and pits for 1/4 Sec. cor.

80.00 The cor. to Secs. 21. 22. 27 & 28

Land level

Soil 1st rate

No Timber.

37.50

40.00

North bet. Secs. 21 & 22

Var 16° 30 E.

60.00

69.50

40.00 Deposit 1 Qt. of pebbles in reg. mound of earth and pits, for 1/4 Sec. cor.

79.85

80.00 Set Cobble stone 12 x 8 x 7 8 in. deep, marked 3 notches on S and E. edges with reg. mound of earth and pits for cor. to Secs. 15. 16. 21 & 22

39.92

Land level

79.85

Salt Lake Meridian

Soil 1st rate
No Timber

East on random line
bet Secs. 15 & 22
Var 16° 30' E.

37.58 Enter high Bench
40.00 Set temp. 1/4 Sec. cor.
60.00 Enter lower Bench
69.50 Road brs. N & S.
79.85 Int. N & S. line 36
lks. N of cor. to Secs. 14
15. 22. and 23. from which
N 89° 45' W on true
line bet. Secs. 15 & 22
39.92 Set Cobble stone 1/2 x 12 x 10
11 in. deep, marked 1/4 on
N. side with stone
mound for 1/4 Sec. cor.
79.85 The cor. to Secs. 15. 16.

Subs Tp 7 S. R 20 E.

21 & 22
Land level
Soil 1st rate
No Timber

North bet. Secs. 15 & 16
Var 16° 30' E.

40.00 Deposit 1 Qt. of pebbles in reg. mound of earth and pits for 1/4 Sec. cor. Bench brs. N. W. & S. E.

80.00 Set cobble stone 15 X 10 X 8 10 in. deep, marked 4 notches on S and 3 on E. edges, with reg. mound of earth & pits for cor. to Secs. 9. 10. 15 & 16.

Land level
Soil 1st rate
No Timber

BOOK
S. L

38.25
40.00
52.20
72.50
80.06
40.03
80.06

S. L. Meridian

East on random line
bet. Secs. 10 & 15
Var 16°30' E.

38.25 Shallow hollow drns. S.E.
40.00 Set temp 1/4 Sec. cor.
52.20 Road brs. N & S.
72.50 Wash in hollow drns E.
80.06 Int. N & S. line 35
Lks. S. of cor to Secs
10 & 15 from which
S 89°45' W on true
line, bet. Secs. 10 & 15
40.03 Set Cobble stone 13 x 10 x 9
9 in. deep, marked 1/4 on
N. side, with stone mound
for 1/4 Sec. cor.
80.06 The cor. to Secs 9. 10. 15. 16
Land level
Soil 1st rate
No Timber

Tubs Tp 7 S. R 30 E.

	North bet Secs. 9 & 10	40.00
	Var 16° 30' E	48.00
40.00	Set Sandstone 12 x 9 x 7	58.00
	8 in. deep, marked 1/4 on	73.50
	W side, with Stone mound	80.00
	for 1/4 Sec. cor.	
79.00	Gully drns. N. E.	
80.00	Set Sandstone 12 x 8 x 6	
	8 in. deep, marked 5	40.00
	notches on S and 3 on E. edges	
	with mound of stones for	
	cor. to Secs. 3. 4. 9 & 10	
	Land level	80.00
	Soil 1st rate	
	No Timber.	

	East on random line	
	bet. Secs. 3 & 10	
	Var 16° 30' E.	
1.00	Small hollow drns. N. E.	

Salt Lake Meridian

40.00	Set temp 1/4 Sec. cor.
48.00	Wash drns. N. E.
58.00 / 73.50	Road brs. N. E. & S. W.
80.00	Int. N and S. line at cor. to Secs. 3 & 10, from which West on true line bet. Secs. 3 and 10.
40.00	Set Sandstone 24 x 14 x 4 18 in. deep, marked 1/4 on N side, with stone mound for 1/4 Sec. cor.
80.00	The cor. to Secs. 3. 4. 9 & 10

Land level

Soil 1st rate

No Timber

North on random line bet. Secs. 3 & 4

Var 16° 30' E

Subs Tp 7 S. R 20 E. S.

40.00 Set temp. 1/4 Sec. cor.
80.46 Int. N. Boundary of Tp. 42.30
17 lks. E of cor. to Secs 3 & 4 80.00
from which
S. 0°.07' E on true line
bet Secs. 3 & 4
40.46 Set Sandstone 12 x 10 x 8
8 in. deep, marked 1/4 on
W side with reg. mound
and pits for 1/4 Sec. cor.
80.46 The cor. to Secs. 3. 4. 9 & 10
Land level Bench
Soil 1st rate
No Timber
Oct 23. 1879 40.00
North bet Secs. 32 & 33 80.20
Var. 16° 30' E
40.00 Set Sandstone 14 x 10 x 8
8 in. deep, marked 1/4 on W
side with stone mound

S. L. Meridian

for 1/4 Sec. cor

42.30 Road brs. N. W. & S. E.

80.00 Set Sandstone 18 x 12 x 5
12 in deep marked 1 notch
on the S. and 4 on E edges
with stone mound for cor.
to Secs. 28. 29. & 33
Land level
Soil 1st rate
No Timber

East on random line
bet. Secs. 28 & 33
Var 16° 30' E

40.00 Set temp. 1/4 Sec. cor.

80.20 Int. N & S line 22 lks.
S. of cor. to Secs. 28 & 33
from which
S. 89° 51' W on true
line bet. Secs. 28 & 33

Subs Tp 9 S. R 20 E

40.10 Deposit 3 small stones one marked with cross (+) in. reg. mound and pits for 1/4 Sec. cor.

80.20 The cor. to Secs. 28. 29. 32 & 33

Land level

Soil 1st rate

No Timber.

North bet. Secs. 28 & 29

Var. 16° 30' E.

40.00 Set charred Cottonwood post 4" x 4" 4 ft. long 2 ft. deep, marked 1/4 Sow W side, with reg. mound and pits for 1/4 Sec. cor.

80.00 Set Cobble stone 10 x 10 x 6 6 in. deep, marked 2 notches on S and 4 on E edges,

with reg. mound and
pits for ~~cor~~ 16 Secs.
20. 21. 28 and 29
Land level
Soil 1st rate
No Timber

East on random line
bet. Secs. 21 & 28
Var 16° 30' E.

40.00 Set temp 1/4 Sec. cor.
80.00 Int. N and S. line at
cor. to Secs. 21 & 28 from which
West on true line, bet,
Secs. 21 and 28.
40.00 Deposit small cobble-
stone 6" x 6" x 3". marked
with cross (+) in reg.
mound of earth and
pits for 1/4 Sec. cor

Sub. Dist. R. 20 E.

80.00 The cor. to Secs. 20.21.28 and 29.
Land level
Soil 1st rate
No Timber

North bet. Secs. 20 & 21
Var 16° 30' E.

40.00 Set Cobble stone 16 X 4 X 6 marked 1/4 on W side, with reg. mound and pits for 1/4 Sec. cor.

80.00 Set Quartzite 10 X 8 X 7, 7 in. deep, marked with 3 notches on S and on E. edges with reg. mound and pits for cor to Secs. 16.17. 20. & 21
Land level
Soil 1st rate

Sa

40.00

80.20

40.10

80.20

BOOK-A-162

Salt Lake Meridian

No Timber.

East on random line
bet. Secs. 16 & 21
Var 16° 30' E.

40.00 Set temp. 1/4 Sec. cor.

80.20 Int. N and S line at
cor to Secs. 15.16.21. and 22. from which
West on true line bet
Secs. 16 & 21

40.10 Set cobble stone 18 X 14 X 12
12 in. deep, marked 1/4 on
N side, with reg. mound
and pits for 1/4 Sec. cor.

80.20 The cor. to Secs. 16.17.20 & 21
Land level
Soil, 2nd rate
No Timber

Subs Tp 7 S., R 20 E.

North bet. Secs. 16 & 17
Var. 16° 30' E.

40.00 Deposit 1 Qt. pebbles with
reg. mound and pits.
for 1/4 Sec. cor.

53.00 Wash drus. S. W.

60.00 " " " "

80.00 Set Sandstone 18 x 8 x 8
12 in. deep marked 4 notches
on S and 4 on E edges
with reg. mound and pits
for cor to Secs. 8. 9. 16 & 17
Land level
Soil 1st rate
No Timber.

East on a random line
bet. Secs. 9 & 16
Var 16° 30' E

16.75 Wash drus. S. W.

BOOK
S.

23.50 4

40.00 4

44.00

80.00

40.00

80.00

S. L. Meridian

23.50 Sandstone Ledge 5 ft high
brs. N & S. ascend Bench
brs. N. W & S. E.
40.00 Set temp. 1/4 Sec. cor.
44.00 Small hollow drns. S. W.
80.00 Int. N & S. line at cor.
to Secs. 9. 10. 15. & 16.
from which
West on true line
bet. Secs. 9 & 16.
40.00 Set Cobble rock 14 x 10 x 6.
9 in. deep marked 1/4 on
N side with stone mound
for 1/4 Sec. cor.
80.00 The cor. to Secs. 8. 9. 16 & 17
Land level
Soil 1st rate
No Timber

Sub & Tp 7 S. R. 20 E.

North bet. Secs. 8 & 9
Var. 16° 30' E.

25.00 Enter Leigher Bench
bns. N. W. & S. E.

40.00 Set Cobble stone 12 x 9 x 5
8 in. deep, marked 4
on W side, with reg.
mound of earth and pits
for 1/4 Sec. cor.

80.00 Set Sand stone 18 x 8 x 8,
12 in. deep, marked,
5 notches on S and 4 on E
edges, with reg. mound of
and pits, for cor. to Secs
4. 5. 8 & 9.

Land level
Soil 1st rate
No Timber

S. L. Meridian

East on a random line
bet. Secs. 4 & 9
Var 16° 30' E.

40.00 Set temp. 1/4 Sec. cor.
80.00 Int. N and S. line as nor
to Secs. 4 & 9 from which
West on true line
bet. Secs. 4 & 9
40.00 Deposit 1/2 Gal Bois du vau
in reg. mound and pits
for 1/4 Sec. cor.
80.00 The cor. to Secs. 4, 5, 8 & 9
Land level
Soil 1st rate
No Timber

North on random line
bet. Secs 4 & 5
Var 16° 30' E.
40.00 Set temp. 1/4 Sec. cor.

Sub Tp 7 S. R 20 E

80.14 Int. N. Boundary of
Tp. at cor. to Secs. 4 & 5
from which
South on true line
bet. Secs. 4 & 5
40.14 Deposit 1/2 Gal. Bois du val
in reg. mound and pits
for 1/4 Sec. cor.
80.14 The cor. to Secs. 4. 5. 8 & 9
at Land level
Soil 1st rate
No Timber.
Oct 24. 1879

North bet. Secs. 31 & 32
Var 16° 30' E.
21.50 Wash drus S. E.
25.00 " " " "
40.00 Set Sandstone 14 x 12 x 4
9 in. deep, marked 1/4 on
W side, with reg. mound

P. L. Meridian

and pits for 1/4 Sec. cor.

48.00 Wash drns. East

53.00 " " S. E.

71.00 " " " "

80.00 Set charred cottonwood post 4"x4" 4 ft long 2 ft. deep marked 1 north on S and 5 on E edges with reg. mound and pits for cor. to Secs. 29. 30. 31 & 32

Land Bench

Soil 1st rate

No Timber

East on random line bet. Secs. 29 & 32

Var. 16° 30' E.

16.00 Wash drns. S. E.

40.00 Set temp 1/4 Sec. cor.

43.00 Wash drns. S. E.

Subs Op 7 S. R 20 E.

48.00 Road dirs. N. W. & S. E.
80.28 Int. N. and S. line of
Tp. 34 lks. N of cor.
to Secs. 28. 29. 32. and 33.
from which
N. 89° 45' W on True line
bet Secs. 29 & 32.
40.14 Set Sandstone 12 x 10 x 8
8 in deep, marked 1/4
on N side with stone
mound for 1/4 Sec. cor.
80.28 The cor. to Secs. 29. 30. 31 & 32
Land level
Soil 1st rate
No Timber

Note: as the cor. to Secs.
30 and 31 on W. Boundary
of Tp falls in Uintah Indian
Reservation, I run

BOOK-A-162

Salt Lake Meridian

West on true line
bet Secs. 30 & 31
Var 16° 30' E.

16.15 Ascend
27.00 Enter flat
37.80 Int. N. E. Boundary
of Uintah Reservation
lks. S. 23° E from
5th mile cor. where I set
a charred Cottonwood
post 4"x4" 4 ft. long
2 ft. deep marked
C. C. with reg. mound
and pits for closing cor.
to fractional Secs. 30 & 31
Land level
Soil 2nd rate
No Timber

Subs Tp 7 S. R 20 E

North bet. Secs. 29 & 3

Var 16° 30' E

22.00 Wash drus. S. E.

40.00 Deposit 6 small stones 1 marked with cross (+) in reg. mound and pits for 1/4 Sec. cor.

49.00 Road bra. N. W. & S. E.

80.00 Set charred Cottonwood post 4" x 4" 4 ft. long 2 ft. deep marked 2 notches on S and 5 on E edges with reg. mound and pits for cor. to Secs. 19. 20. 29 & 30

Land Bench

Soil 1st rate

No Timber

Salt Lake Meridian

East on random line
bet. Secs. 20 & 29
Var 16° 30' E

40.00 Set temp 1/4 Sec. cor.
79.96 Int N & S. line 22
lks. S of cor. to Secs. 20.
21. 28 and 29 from which
S. 89° 30' W on true
line bet Secs. 20 & 29
39.98 Set charred cottonwood
post 4" x 4" 4 ft. long.
2 ft. deep, marked 1/4 S
on N side with reg.
mound and pits for
1/4 Sec cor.
79.96 The cor to Secs. 19. 20. 29 & 30
Land level
Soil 1st rate
No Timber

Subdivid. R. 20 E.

Note: The cor to Secs. 19 & 30 on W. Boundary falling in Indian Reservation therefore I run West on true line bet Secs 19 & 30

Var 16° 30' E.

39.75 Road bears N. W. & S. E.

40.00 Deposit 2 boxes in reg. mound and pits for 1/4 Sec. cor.

70.57 On N point of low ridge int. N. E. Boundary of Uintah Indian Reservation at a point 8.30 chns. N. 23° W of mile cor No 6. where I set cobble stone 2½" x 2½" x 8" 8 in deep marked C. C. with reg. mound and pits for closing

S. L. Meridian

cor. to fractional Secs.
19 & 30
Land level
Soil 1st rate
No timber

North lat. Secs. 19 & 20
Var 16° 30' E.

40.00 Set Sandstone 12X10X5-
8 in. deep, marked 1/4 on
W side, with reg. mound
and pits for 1/4 Sec. cor.

80.00 Set charred bottom wood
post 4"X4" 4 ft. long
2 ft. deep, marked
3 notches on S and 5 on
E edges with reg.
mound and pits for
cor. to Secs 17, 18, 19 & 20
Land level

Subs Tp 70 South R 20 E.

Soil 1st rate
No Timber.

East on random line
bet Secs. 17 & 20
Var 16° 30' E.

40.00 Set temp 1/4 Sec. cor.
80.18 Int. N & S. line 20
lks. S. of cor. to Secs.
17 & 20 from which
S. 89° 51' W on true
line bet. Secs. 17 & 20
40.09 Set charred Cottonwood
post 4" x 4" 4 ft. Long
2 ft. deep marked 1/4 S.
on N side, with reg.
mound and pits
for 1/4 Sec cor.
80.18 The cor to Secs.
17. 18. 19 & 20

S. L. Meridian

Land level
Soil 1st rate
No Timber.

West on random line
bet Secs. 18 & 19
Var 16°30' E.

40.00 Set temp. 1/4 Sec. cor.

78.82 Inst. W. Boundary of
Tp. 33 lks. S. of cor.
to Secs. 18 & 19 from which
S. 89°46' E. on true
line bet Secs. 18 & 19

38.82 Set charred Cottonwood
post 4" x 4" 4 ft. long
2 ft. deep marked 1/4 S
on N side, with reg
mound and pits for
1/4 Sec. cor.

78.82 The cor. to Secs. 17, 18, 19 & 20

Subdivided R 20 E.

Land level
Soil 1st rate
No Timber

North bet. Secs. 17 & 8
Var 16° 30' E

53.00 Wash drus. West
40.00 Deposit 1 Qt. of pebbles
in reg. mound of earth
and pits for 1/4 Sec. cor
80.00 Set charred cottonwood
post 4"x4" 4 ft. long.
2 ft. deep, marked 4
notches on S and 3 on
E edges, with reg.
mound and pits
for cor to Secs 7.8.
17 and 18.
Land level
Soil 1st rate

40.00
80.22

40.11

80.22

S. L. Meridian

No Timber.

East on random line
bet. Secs. 8 & 17
Var 16° 30' E

40.00 Set temp 1/4 Sec. cor.
80.22 Int. N & S. line 2 links
S of cor to Secs. 16 & 17
from which
S 89° 45' W on true
line bet. Secs. 8 & 17
40.11 Set charred Cottonwood
post 4"x4" 4 ft. long
2 ft. deep marked 1/4 Sec
N side with reg. mound
and pits for 1/4 Sec cor
80.22 The cor. to Secs. 7, 8,
17 & 18
Land level
Soil 1st rate

Subs Tp 7 S. R 20 E.

No Timber.

West on random line
bet. Secs 7 & 18
Var 16° 30' E

40.00 Set temp. 1/4 Sec cor.
41.00 Wash drms. S. W.
78.00 Int. W. Boundary of
Tp at cor. to Secs 7 & 18
from which
East on true line bas
Secs. 7 & 18
38.00 Set charred cottonwood
post 4"x4" 4 ft. long
2 ft. deep marked 1/4 S
on N side with reg. mound
of earth and pits for 1/4
Sec. cor.
7800 The cor to Secs. 7, 8, 17
and 18

S.

2

40.00

80.00

S. L. Meridian

Land level
Soil 1st rate
No Timber
Oct. 25, 1879

North bet. Secs 7 & 8
Var 16° 30' E

40.00 Deposit 1 Qt of pebbles in reg. mound and pits for 1/4 Sec. cor

80.00 Set Cobble Stone 12 X 8 X 6 8 in deep marked on notches on S and E edges with reg. mound and pits for cor. to Secs. 5, 6, 7 & 8

Land level
Soil 1st rate
No Timber.

East on randomline bet Secs. 5 & 8

Int. Gp. 7 S. R. 20 E.

Var 16° 30' E.

25.00 Enter higher Bench
bns N. W. & S. E.

40.00 Set temp 1/4 Sec.
cor.

80.00 Int. N & S. line at
cor to Secs. 4. 5. & 8 & 9
from which
West on true line
bet Secs. 5 & 8.

40.00 Deposit 1 Qt. of pebbles
in reg. mound and
pits for 1/4 Sec. cor.

80.00 The cor to Secs. 5. 6.
7 & 8.

Land level
Soil 1st rate
No Timber

Sa

9.00
40.00
46.75
77.90

37.90

77.90

Salt Lake Meridian

West on random line
bet. Secs. 6 & 7
Var 16° 30' E

9.00 Wash drns. S. W.
40.00 Set temp. 1/4 Sec. cor.
46.75 Wash drns. S. E.
77.90 Int. W. Boundary
of Tp at cor to Secs
6 & 7 from which
East on true line
bet Secs. 6 & 7
37.90 Set charred cottonwood
post 4" x 4" 4 ft. long
2 ft. deep, marked 1/4 S.
on N side with reg
mound and pits for
1/4 Sec. cor.
77.90 The cor. to Sec 5. 6. 7 & 8
Land level
Soil 1st rate

Subs Tp 7 S. R 20 E.

No Timber

North on random line bet Secs. 5 & 6
Var 16° 30' E

5.50 Wash drws. S. W.
40.00 Set temp 1/4 Sec. cor.
60.00 Point of higher Bench
73.00 Enter higher Bench
80.20 Int. N Boundary of Tp. at cor. to Secs. 5 & 6. from which
South on true line bet. Secs. 5 & 6.
40.20 Set cobble stone 16 x 8 x 5 11 in. deep marked 1/4 on W side with stone mound for 1/4 Sec. cor.
80.20 The cor. to Secs. 5. 6. 7 & 8

S. L. Meridian

Land level
Soil 1st rate
No Timber

Meanders of Green River
in Tp 7 South, Range 20 East.

Right Bank

Beginning at the meander Cor
to fractional Secs 19 & 24, 46 chs
North of Cor to Secs 24 & 25 on E.
Boundary of Tp and right bank
of Green River Down meander
down stream

In Sec. 24 Va 16°30' E.

S. 82°30' W. 22.20 chs
S. 53°45' W. 34.60 "
S 11°30' W. 23.00 " Thence
79.80

In Sec. 25.

S. 22°30' E. 31.00 chs.
S. 80°00' E. 44.40 " to the
75.40
Meander Cor 43 chs N. of the

Sub & Tp 7 S. R. 20 E.

Cor to Sec. 25 and 36.
On the E. Boundary of the Tp.

Left Bank

From the Meander Cor 33 chs N. of Cor to Sec. 24 & 25 on E. Boundary of T. and left Bank of Green River Thence

In Sec. 24.

N. 89°45' W. 13.00 chs
S. 57°30' W. 29.00 "
S. 27° W. 19.50 " Thence
61 50

In Sec. 25.

S. 35° E. 21 chs.
S. 86°45' E 34.30 "
55 30

Land on both sides good bottoms covered with brush
Soil Wrak
Timber a few Cottonwood
Augmented on 30 [illegible], 32 chs.

Oct. 27, 1879

BOOK-A-162

S. L. (Meridian)

General Description

This Tp. contains some excellent bottoms on the west side of Green River. The soil is mostly of good quality, and can be irrigated from Green River but at less expense from the Uintah River on account of its having more fall than Green River. A bend of the last named river falls in Sec. 24 & 25, which contain about 100 acres of willow grass bottoms. The N.E. part of the Tp. is somewhat broken by bad land washes.

A. D. Perron
U.S. Sub. Surveyor.

BOOK-A-162

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, Febry 24 *18* 80

The foregoing field notes of the survey of the

Subdivisions of

Township No 7 S. *Range No* 20 E

of the Salt Lake Meridian, Utah Territory,

Executed by A. D. Ferron

Under print *contract No* 92

of the 13th *day of* June *1879,*

in the month of Oct. *1879*

having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.

Ira Salomon

U. S. Surveyor General for Utah.

OOK-A-162
R: 1880.

Filed Jany 21st 1880

Examined by T. C. Bailey

Compared by T. C. Bailey

FIELD NOTES

OF

THE SURVEY OF THE

Subdivision Lines

of Township No. 7 South Range No. 21 East

of the Salt Lake Meridian in Utah Territory.

BY

E. Buettner

U. S. DEPUTY SURVEYOR,

Under his Contract No. 921

dated June 13th 1879

Survey commenced October 23rd 1879

Survey completed " 30th 1879

Book 162

Exteriors and Subdivisions

Township 7 S. **R.** 21 E

174 175 176 178 179 180

6	149	5	126	4	112	3	100	2	88	1
147		146		125		111		99		87
7	144	8	124	9	110	10	98	11	86	12
143		141		123		108		97		85
18	140	17	122	16	108	15	96	14	84	13
139		137		120		107		95		83
19	136	20	114	21	106	22	94	23	81	24
135		134		117		105		93		80
30	132	29	116	28	104	27	92	26	79	25
131		129		114		103		91		78
31	128	32	113	33	102	34	90	35	77	36

172 171 170 169 168 167

Meanders 151-163

BOOK-A-162

Subs. Tp. 7 S. R 21 East.

Survey commenced Oct. 23rd 1879

By. E. Buettner

From the cor. to Secs. 35 & 36 on South Boundary of Tp. North bet. Secs. 35 and 36

Var 16° 30' E

25.00 Wash in Broad hollow drns. S. W.

40.00 Set sandstone 14 x 12 x 4 9 in deep, marked 1/4 on W side, with stone mound for 1/4 Sec. cor.

48.50 Hollow drns. S. W.

58.00 Ridge brs. N. E. and S. W.

65.00 Hollow drns. S. W.

80.00 Set charred Cottonwood post 4" x 4" 4 ft. long, 2 ft. deep marked with 1 notch on S and 1 on E edges, and stone mound for cor. to

Subdivisions Tp. 7 S. R 21 E. of the

Secs. 25. 26. 35 and 36.
Land high broken Upland
Soil 3rd rate
No Timber
augmented on 80.00 chns.—

East on random line bet
Secs. 25 and 36
Var 16° 30' E

12.50	Hollow drns. S. W.
20.75	Ridge brs. N. E. and S. W.
29.00	Hollow drns. S. W.
40.00	Set temp. 1/4 Sec. cor.
80.18	Int. E. Boundary of Tp at cor to Secs. 25 and 36 from which
	West on true line bet Secs. 25 and 36
41.09	Set Sand stone 18 x 12 x 3

Salt Lake Meridian

12 in. deep, marked 1/4 on N side with stone mound for 1/4 Sec. cor.

80.18 The cor. to Secs. 25, 26, 35 & 36.
Land broken upland
Soil 3rd rate
No Timber
augmented on 80.18 chns.

North bet Secs. 25 & 26
Var 16° 30' E.

28.00 Enter broken ground
40.00 Set Sandstone 18 X 18 X 3
12 in. deep
marked 1/4 on W side with stone mound for 1/4 Sec. cor.
41.00 Head of hollow drns. N. E.
80.00 Set Sandstone 16 X 13 X 5, 10 in. deep, marked 2 notches on S

Subdivisions Tp. 7 S. R 21 E.

and on E. edges, with
reg. mound of earth and
pits, for cor. to Secs 23
24. 25 and 26.
Land broken and level
Soil 2nd and 1st rate
No Timber
Augmented on 42.00 chns.

East on random line
bet Secs. 24 and 25
Var 16°30' E.

21.00 Hollow drus. N. E.
35.00 " " N. W.
40.00 Set temp 1/4 Sec. cor.
68.00 Wash drus, N. W.
80.12 Int. E Boundary of Tp.
16 lks. N of cor. to Secs 24 & 25
from which

of the Salt Lake Meridian

North 89°52' W bet.
Secs. 24 and 25

40.06 Set charred Cottonwood
post 4" x 4" 4 ft. long
2 ft. deep marked 1/4 Sec.
N side with stone mound
for 1/4 Sec. cor.

80.12 The cor. to Secs. 23. 24
25 and 26
Land Broken
Soil 2nd rate
No Timber
augmented on 80.12 chus

North bet. Secs. 23 and 24
Var 16°30' E

4.50 Hollow drus. West.
16.50 " " "
20.50 " " "

Subdivisions Tp. 7 S. R. 2 & E.

37.00	Hollow drus. West	
40.00	Set Sandstone 24 x 18 x 5 18 in deep, marked 1/4 on W side, with reg. mound and pits for 1/4 Sec. cor.	40.00
68.00	Hollow drus. West leave broken ground, enter Bench	80.22
80.00	Set charred cottonwood post 4" x 4" 4 ft. long 2 ft. deep marked with 3 notches on S and on E edges with reg. mound and pits for cor. to Secs. B. 14. 23 & 24	40.00
	Land mostly broken soil 2nd rate	80.22
	No Timber	
	Augmented on 80.00	

East on random line

of the Salt Lake Meridian

bet. Secs. 13 & 24

Var 16° 30' E

40.00 Set temp 1/4 Sec. cor

80.22 Int. E. Boundary of Tp 22 Cks. S of Secs. 13 & 24 from which S. 89° 57' W on true line bet Secs 13 and 24

40.11 Set charred Cottonwood post ~~with~~ 4" x 4" 4 ft. long 2 ft. deep, marked 1/4 S on N side with reg mound and pits

80.22 The cor. to Secs. 13. 14. 23 and 24

Land level

Soil 1st rate

No Timber

Subdivisions Tp. 7 S. R 21 E.

North bet. Secs. 13 & 14
Var 16° 30' E.

25.60 Wash drns. West.

40.00 Set charred bottomwood post 4"x4" 4 ft. long, 2 ft. deep, marked 1/4 on N side, with neg. mound and pits for 1/4 Sec. cor.

80.00 Set charred bottomwood post 4"x4" 4 ft. long, 2 ft. deep, marked 1/4 notches on S and E on E, edges, with stone mound for cor to Secs. 11, 12, 13 and 14

Land gently rolling
Soil fertile
No timber

BOOK-

of the

40.00

79.90

39.95

79.90

of the Salt Lake Meridian

East on random line
bet. Secs. 12 and 13
Var. 16° 30' E.

40.00 Set temp. 1/4 Sec. cor.
79.90 Int. E. Boundary of Tp.
42 lks. South of cor. to
Secs. 12 and 13 from which
A. 89° 42' W. on true
line bet. Secs. 12 and 13
39.95 Sandstone 16 x 7 x 9
10 in. deep, marked 1/4 on
West side with reg. mound
and pits for 1/4 Sec. cor
79.90 The cor. to Secs. 11, 12
13 and 14.

Land level
Soil 1st rate
No Timber

Subdivisions Tp. 7 S. R 21 E. of

North bet Secs. 11 & 12

Var 16° 30' E.

40.00	Set Sandstone 11 x 8 x 7 6 in. deep, marked 1/4 on N side, with reg. mound and pits for 1/4 Sec. cor.	1.25
		5.70
		25.00
78.80	Wash drus. S. W.	40.00
80.00	Set Sandstone 24 x 14 x 3 18 in deep, marked 5 notches on Sand 1 on E, edges with reg. mound and pits for. cor. to Secs. 1. 2. 11 and 12.	71.00
		80.00
	Land level	40.00
	Soil 1st rate	
	No Timber	
		80.00

the Salt Lake Meridian

East on random line
bet. Secs. 1 and 12
Var. 16° 30' E.

1.25 Wash drus. S. W.
5.70 Same wash drus. N. W.
25.00 Point of low sandstone
ridge brs. N. E.
40.00 Set temp. 1/4 Sec. cor
71.00 Wash drus. S. W.
80.00 Int. E. Boundary of
Tp. at cor. to Secs. 1 & 12
from which
West on true line bet
Secs. 1 and 12
40.00 Set Sandstone 18 x 8 x 4
12 in. deep, marked
1/4 on N side with stone
mound for 1/4 Sec. cor
80.00 The cor. to Secs. 1. 2. 11. and 12
Land level

Subdivision Tp. 7 N. R. 21 E.

Sol. 1st rate
No Finder

	North on random line bet. Secs. 1 and 12 Var 16°30' E	30.19
34.00	Enter Sandstone bluffs	
4.00	Set temp. 1/4 Sec. cor.	
79.81	Left Bank of Green River 7 ft. deep runs West	
71.79	Right Bank of Green River	40.00
80.00	Int. N. Boundary of Tp. at cor. to Secs. 1 and 2 from which South on true line bet. Secs. 1 and 2	80.00
8.21	Set charred Cottonwood post 4" x 4" 4 ft. long	

of the Salt Lake Meridian

2 ft. deep, marked M. C.
with reg. mound and
pits for Meander Cor
of fractional Sec. 1 & 2.

30.19 Set charred cedar wood
post 4"x4" 4 ft. long
2 ft. deep, marked
M. C. with reg. mound
and pits for Meander
Cor. to fractional
Secs. 1 and 2.

40.00 Set sandstone 12x10x
9. 8 in deep, quarried
1/4 on W side with
stone mound for 1/4
Sec. cor.

80.00 The cor. to Secs. 1. 2. 11 & 12
Land mostly level
Soil 1st quality

Thos Fowler

Subdivisions Tp. 7 S. R 21 E

North bet. Secs.
34 and 35

Var 16° 30' E.

40.00 Set Sandstone 16x10x4
11 in. deep, marked ¼
on West with stone
mound for ¼ Sec. cor.

74.00 Enter Bench
Trav Bad lands

80.00 Set Sandstone 12x7x7
8 in. deep, marked 1 north
on Sand 2 on E. Edges
with stone mound for
cor. to Secs. 26. 27. 34 & 35
Land mostly broken
and rocky.

Soil 3rd rate
No Timber

Augmented on 74.00 chns.

October 23rd 1879

20.00
40.00
45.00
80.60

40.30

80.60

of the Salt Lake Meridian

East on random line
bet Secs. 26 and 35
Var 16° 30' E.

20.00 Enter Bad land Break
40.00 Set temp. 1/4 Sec. cor.
45.00 Leave Bad land break
80.60 Int. N and S. line 43 lks
N. of cor. to Secs. 25. 26.
35 and 36 from which
N. 89° 42' W. on true
line bet Secs. 26 and 35
40.30 Set sand stone 11 X 10 X 6
6 in. deep marked 1/4 on
N side, with stone mound
for 1/4 Sec. cor.
80.60 The cor. to Secs. 26. 27.
34 and 35.
Land level and broken
Soil 1st and 3rd rate
No Timber

Subdivisions Tp. 7 S. R 21 E.

Augmented on 23.60. chns

North bet Secs. 26 & 27
Var 16° 30' E.

24.00 Wash drus. N.W.
40.00 Set Sandstone 18 x 6 x 5
12 in. deep, marked
1/4 on W side, with
stone mound for 1/4
Sec. cor.
62.00 Wash drus. N.E.
80.00 Set charred Cottonwood
post 4" x 4", 4 ft. long
2 ft. deep, marked 2
notches on Sand E edges
with reg. mound and
pits for cor. to Secs.
22. 23. 26. & 27
Land level

of the

9.00
31.50
34.50
40.00
80.16
40.08

BOOK-A-162

of the Salt Lake Meridian

Soil 2nd rate
No Timber.

East on random line
bet. Secs. 23 and 26
Var 16° 30' E.

9.00 Wash dries North
31.50 " " "
34.50 Sandstone ledge bra.
N and S. Enter broken ground
40.00 Set temp 1/4 Sec. cor.
80.16 Int. N and S. line 3 chs
N of cor. to Secs 23. 24
23 and 26. from which
N 89° 44' W an true
line bet Secs. 23 & 26.
41.08 Set Sandstone 16 X 8 X 3
in. deep, marked 1/4
on N side with stone

Subdivisions Tp. 7 S. R 21 E.

mound for 1/4 Sec. cor

80.16 The cor. to Secs. 22. 23.
26 and 27
Land broken and level
Soil 3rd and 1st rate
No Timber
Augmented on 45.56 chns.

North bet. Secs.
22 and 23
Var 16°30' E.

26.00 Wash drus. West
40.00 Set Sandstone 18 x 8 x 4
12 in. deep, marked 1/4
on W side with reg.
mound and pits, for
1/4 Sec. cor.
62.50 Hollow drus. West
80.00 Set charred Cottonwood

of the Salt Lake Meridian

post 4"x4" 4 ft. long
2 ft. deep, marked 3
notches on S and 2 on
E edges with reg. mound
and pits for cor. to Secs.
14. 15. 22. and 23.
Land level
Soil, 1st rate
No Timber.

East on random line
bet Secs. 14 and 23
Var 16° 30' E.

40.00 Set temp. 1/4 Sec. cor
44.00 Enter Broken ground
80.14 Int. N and S. line 49
lks. N. of cor. to Secs.
13. 14. 23 and 24
from which

Subdivisions Tp. 7 S. R 21 E.

N. 89°39' W on true line bet Secs. 14 and 23

40.07 Deposit 1 Qr. of pebbles in reg. mound of earth and pits for 1/4 Sec. cor.

80.14 Pile cor. to Secs. 14, 15, 22 and 23. Land nearly level Soil poor rate No Timber.

North bet. Secs. 14 & 15 Var. 16°30' E.

8.25 Wash drns. West

40.00 Deposit 1 Qr. of pebbles in reg. mound of earth and pits for 1/4 Sec. cor.

74.50 Wash drns. S. W.

80.00 Set charred aspen post

BOOK

of the

17.00

40.00

80.00

40.00

of the Salt Lake Meridian

4'x4' 4 ft. long 2 ft. deep
marked 4 notches on Sand
2 on E. edges with reg.
mound and pits for cor.
to Secs. 10. 11. 14. and 15
Land level
Soil 1st rate
No timber.

East on random line
bet Secs. 11 and 14
Var 16°30' E.
17.00 Wash dmo S.W.
40.00 Set temp. 1/4 Sec. cor.
80.00 Set N. and S. line at cor.
to Secs. 11. 12. 13 and 14
from which
Weston true line
bet Secs. 11 and 14
40.00 Set charred stake & cottonwood

post 4" x 4" 4 ft. long
2 ft. deep marked 1/4 S
on N side with reg. mound
and pits for 1/4 Sec. cor.
80.00 NE cor. to Secs. 10.11.14 & 15
Land level
Soil 1st rate
No Timber.

North bet. Secs. 10 & 11
Var. 16°30' E 1.50
40.00 Set sandstone 12 x 10 x 7
8 in. deep, marked 1/4 on
W side, with reg. mound
and pits for 1/4 Sec. cor. 80.20
78.10 Wash drns. S. W.
80.00 Set sandstone 14 x 7 x 6.
9 in. deep, marked
5 notches on S. and 2 on 40.10

21E of the Salt Lake Meridian

E edges, with reg. mound and pits for cor to Secs 2. 3. 10 and 11

Land level

Soil 1st rate

No Timber

East on random line bet Secs 2 and 11

Var 16° 30' E

1.50 Wash drus. S. W.

40.00 Set temp. 1/4 Sec. cor.

80.20 Int. N. and S. line at cor. to Secs. 1. 2. 11 and 12. from which

West on true line bet Secs. 2 and 11

40.10 Set Sandstone 14 x 9 x 7 8 in. deep, marked 1/4 on

N side, with reg. mound and pits for 1/4 Sec. cor. 80.00

80.20 The cor. to Secs. 2. 3. 10 and 11

Land level

Soil 1st rate 8.21

No Timber.

North on random line bet. Secs. 2 and 3

Var 16° 30' E. 40.00

40.00 Set temp 1/4 Sec. cor.

71.79 Left Bank of Green River 4 ft. deep rus. N. E.

Meas. Offset West 15.43 chns 80.00

Meas. North 8.21 "

Meander corner 15.43 chns. West of cor. point which falls in River making the connection

of the Salt Lake Meridian

80.00 Intersect N. Boundary of Tp. at cor. point to Secs. 2 and 3. from which South bet. Secs. 2 & 3

8.21 Set charred Cottonwood post 4"x4" 4 ft. long 2 ft. deep marked M. C. with orig. mound and pits for Meander Cor. to fractional Secs. 2 and 3

40.00 Set sandstone 16x8x4, 11 in. deep, marked 1/4 S on W side with stone mound for 1/4 Sec. cor.

80.00 The cor to Secs. 2, 3, 10 and 11.

Land level
Soil 1st rate
No Timber

Subdivisions Tp. 7 S. R 21 E.

North bet. Secs. 33 & 34

Var 16°30' E

40.00 Set Sandstone 10 x 10 x 6, 6 in. deep, marked ¼ on W side with stone mound for ¼ Sec. cor.

45.00 Enter flat.

54.00 Ascend in Breaks.

80.00 Set sandstone 16 x 10 x 5 11 in. deep, marked 1 north on S and 3 on E edges with stone mound for cor. to Secs. 27, 28, 33 and 34

Land sandstone breaks

Soil 3rd rate

No Timber

Augmented on 7.10 chns.

of the

E

40.00

75.00

79.48

39.76

79.48

of the Salt Lake Meridian

East on random line
bet. Secs. 27 and 34
Var. 6° 30' E.

40.00 Set temp. 1/4 Sec. cor.
75.00 Enter Birch
79.48 Int. N and S. line 46. lks.
N of cor. to Secs. 26. 27. 34
and 35 from which
N 89° 40' W on true
line bet. Secs. 27 and 34
39.76 Set Sandstone 10 x 9 x 6,
6 in deep marked 1/4 on
N side with stone mound
for 1/4 Sec. cor.
79.48 The cor. to Secs. 27. 28. 33
and 34

Land heavy Brush
Soil 3rd rate
No Timber

Augmented on 75.00 chns.
October 24th 1879

Subdivisions Tp. 78 R. 21 E.

	North bet. Secs. 27 and 28 Var 16°30' E.	31.75
40.00	Set Sandstone 10x10x7	40.00
	6 in. deep, marked 1/4 on	55.00
	W side with stone mound	59.25
	for 1/4 Sec. cor.	70.50
48.00	Enter Bench	80.04
80.00	Set Sandstone 12x8x6,	
	8 in. deep, marked 2 notches	
	on S and 3 on E edges with	
	stone mound for cor. to	
	Secs. 21. 22. 27. 28	40.02
	Land broken and level	
	Soil 3rd and 1st rate	
	No Timber	
	Augmented on 48.00 chns.	80.04

East on random line
bet. Secs. 22 and 27

of the Salt Lake Meridian

Var 16°30' E.

31.75 Wash drns. N. W.
40.00 Set temp 1/4 Sec. cor.
55.00 Wash drns. N. E.
59.25 " " North
70.50 " " "
80.04 Int N and S. line 10 lks
South of cor. to Secs. 22. 23
26 and 27 from which
S. 89°56' W on true line
bet. Secs. 22 and 27
40.02 Set sandstone 18 x 10 x 8
12 in. deep, marked 1/4 on
N. side with stone mound
for 1/4 Sec. cor.
80.04 The cor to Secs. 21. 22.
27. and 28
Land level
Soil 1st rate
No Timber

Subdivisions Tp. 7 S. R. 21 E.

North bet. Secs. 21 & 22
Var 16° 30' E.

9.00	Wash drus. N. W.	
40.00	Set Sandstone 12 x 10 x 6. 8 in. deep, marked 1/4 on W side with stone mound for 1/4 Sec. cor.	40.00
		79.20
60.00	Wash drus. N. W.	
78.50	" " " "	
80.00	Set Sandstone 12 x 8 x 6, 8 in. deep, marked 3 notches on S and E edges with reg. mound and pits for cor. to Secs. 15, 16, 21 and 22.	39.60
		79.20

Land level
Soil 1st rate
No Timber

BOOK-A
of the

of the Salt Lake Meridian

East on random line
bet. Secs. 15 and 22
Var. 16° 30' E.

40.00 Set temp. 1/4 Sec. cor.
79.20 Int. N and S. line 47 lks.
S. of cor. to Secs. 14. 15.
22 and 23 from which
S. 89° 40' W on true
line bet Secs. 15 and 22
39.60 Deposit 1 Qt. pebbles in
reg. mound and pits
for 1/4 Sec. cor.
79.20 The cor. to Secs. 15. 16
21 and 22

Land level
Soil 1st rate
No Timber

Subdivisions Tp. 7 S. R 21 E.

	North bet Secs. 15 and 16 Var 16°30' E	18.00
		36.00
7.00	Wash drus. S. W.	40.00
40.00	Deposit 1 Qt of pebbles in reg mound of earth and pits for 1/4 Sec. cor.	42.00
		65.50
		72.00
80.00	Set Cobblestone 12 x 9 x 6 8 in. deep marked 4 on the on Sandson E edge with reg. mound and pits for cor. to Secs. 9, 10, 15 and 16	79.80
	Land gently rolling Soil sandy No Timber	39.90
	East on random line bet Secs. 10 and 15 Var 16°30' E.	79.80

Of the Salt Lake Meridian

18.00	Wash drns S. W.
36.00	" " South
40.00	Set temp 1/4 Sec cor.
42.00	Wash drns. North
65.50	Same " " S. W.
72.00	Detatched Bench slope
79.80	Int. N and S. line at cor to Secs. 10. 11. 14 and 15 from which West on true line bet Secs. 10 and 15
39.90	Set Sandstone 20 x 10 x 3 16 in. deep, marked 1/4 on N side with reg. mound and pits for 1/4 Sec. cor.
79.80	The cor. to Secs. 9. 10. 15 and 16.

Land level

Soil 1st rate

Subdivisions Tp. 7 S. R 21 E. of the

No Timber.

	North bet. Secs. 9 & 10	34.00
	Var 16°30' E	40.00
39.50	Bench brs. E and W.	79.90
40.00	Set Sandstone 14 x 8 x 8, 9 in. deep, marked 1/4 on W side with stone mound for 1/4 Sec. cor.	
80.00	Set charred bottomwood post, 4" x 4" 4 ft. long 2 ft deep, marked 5 notches on 2 and 3 on E edges, with orig. mound and pits for cor. to Secs. 3, 4, 9 and 10.	39.95
		79.90
	Land nearly level	
	Soil 1st Rate	
	No Timber	

of the Salt Lake Meridian

East on random line
bet Secs 3 and 10
Var 16°30' E

34.00 Wash drus. S.E.
40.00 Set temp. 1/4 Sec. cor.
79.90 Int. N and S. line
15 lks. S. of cor. to Secs.
2. 3. 10. and 11 from
which S 89°53' W
on true line bet Secs.
3 and 10
39.95 Set sandstone 12 x 9 x 6.
8 in. deep, marked 1/4
on N side, with stone
mound for 1/4 Sec. cor.
79.90 The cor. to Secs. 3. 4.
9 and 10
Land level
Soil 1st rate
No Timber

Subdivisions Tp. 7 S. R 21 E.

	North on random line bet. Secs. 3 and 4 Var 16° 30' E.	22.50
40.00	Set temp 1/4 Sec. cor.	40.00
80.00	Int. N. Boundary of Tp. at cor. to Secs. 3 and 4 from which South on true line bet. Secs. 3 and 4	42.50
40.00	Set charred Cottonwood post 4" x 4" 4 ft. long, 2 ft. deep, marked 1/4 S on W side, with reg. mound and pits for 1/4 Sec. cor.	53.00
80.00	The cor to Secs. 3, 4, 9 and 10.	

Land level
Soil 1st rate
No Timber

of the Salt Lake Meridian

North bet. Secs. 32 and 33
Var 16° 30' E.

22.50 Enter heavy undergrowth

40.00 Set charred Cottonwood post 4"x4" 4 ft. long 2 ft. deep marked 1/4 S on W side with reg. mound and pits for 1/4 Sec. cor.

42.50 Wash drus. West

53.00 Left Bank of Green River 4 ft. deep rus S. W.
Set charred Cottonwood post 4"x4" 4 ft. long 2 ft deep, marked M. C. with reg. mound and pits for Meander Cor. to fractional Secs. 32 and 33
Thence offset East 5.33 chns
North 27.00 "
to a point 5.33 chns E. of

Subdivisions Tp. 7 S. R 21 E. of the

80.00	(true cor. point falls in River) where I set a charred Cottonwood post 4" x 4" 4 ft. long 2 ft. deep marked M.C. with reg. mound and pits for Meander Cor. to fractional Secs. 28 and 33 on Left Bank of Green River Land level Soil 1st rate No Timber Heavy undergrowth on 57.50 chns. augmented on 57.50. chns.—	5.33 15.00 40.00 80.48 40.24 80.48

East on random line
bet Secs. 28 and 33
Var 16° 30' E

of the Salt Lake Meridian

5.33 Meander Cor.
15.00 Enter Bad lands
40.00 Set temp 1/4 Sec. cor.
80.48 Pass N, and S, line 29 lks
N, of cor. to Secs. 27, 28,
33 and 34 from which
N. 89°48' W. on true
line bet Secs. 28 and 33
80.24 Set Sandstone 12x8x7
8 in. deep, marked 1/4 on
N side with stone mound
for 1/4 Sec. cor.
80.48 The cor. point to Secs.
28. 29. 32 and 33
Land mostly Broken
Soil 3rd rate
No Timber
Augmented on 65.48 chns.

Subdivisions Tp. 7 S. R21 E.

North bet. Secs. 28 and 29

Var 16° 30' E.

Note as the line falls in River therefore from a point 15.00 chns. E of cor point to Secs. 28. 29. 32. and 33 I offset North 50.50 chns. West 15.00 " to

50.00 on line in place on Left Bank of Green River where I set charred Cottonwood post 4" x 4" 4 ft. long 2 ft. deep marked M. C. with reg. mound and gits for Meander cor. to fractional Secs. 28 and 29

50.00 Enter Ledge point brs. E & W.

of the

61.00

68.75

72.75

80.00

of the Salt Lake Meridian

61.00 Leave same
68.75 Wash drns. West
72.75 " " S.W.
80.00 Set Sandstone 36x10x4
20 in. deep, marked 2 notches
on S and 4 on E. edges,
with stone mound for cor.
to Secs. 20. 21. 28. and 29
Land mostly level Bottom
Soil 1st rate
No Timber
Heavy undergrowth
augmented on 80.00 chns.
Note: The 1/4 Sec. cor. falls
in River and is not set.
October 25th 1879

East on random line
bet Secs. 21 & 28
Var 16° 30' E

Subdivisions Tp. 7 S. R 21 E.

9.00	Wash drns. N. W.
19.00	Sandstone Ledge 10 ft. high
	bns N. & S. Enter Bad lands.
22.50	Wash drns. N. W.
32.00	" " " "
40.00	Set temp. 1/4 Sec. cor.
53.50	Enter level Bench
66.25	Wash drns. North
76.25	" " "
79.82	Int. N. and S. line 76 lks.
	N of cor. to Secs. 21. 22.
	27 and 28 from which
	N 8 90 27 W on true line
	bet Secs. 21 and 28.
39.91	Set Sandstone 22 x 11 x 7,
	16 in. deep, marked 1/4 on
	N side, with stone mound
	for 1/4 Sec. cor.
79.82	The cor. to Secs. 20. 21. 28
	and 29

of the Salt Lake Meridian

Land level Bench, Bottom and Breaks
Soil 1st and 3rd rates
No Timber
Heavy undergrowth on Bottom
Augmented on 53.50 chns.

North bet. Secs. 20 and 21
Var 16° 30' E.

3.00 Wash drus. West
7.50 Lone Sandstone Pillar bears W. 65 lks. distant
16.00 Wash drus. S. W.
22.00 Enter Breaks
35.00 Leave same, enter Bench
40.00 Set Sandstone 10 x 10 x 6, 6 in. deep, marked 1/4 on W side, with reg. mound and pits for

Subdivisions Tp. 7 S. R 21 E.

1/4 Sec. cor.
Descend into hollow
80.00 In South side of hollow
set Sandstone 20 x 12 x 12, 12
in deep, marked 3 notches
on S and 4 on E edges, with
stone mound for cor to
Secs. 16. 17. 20 and 21.
Land level bench, bottom
and Breaks
Soil 1st and 3rd rate
No Timber
Heavy undergrowth on bottom
augmented on 35.00 chns. —

East on random line
Cut Secs. 16 and 21
Var 16° 30' E
12.00 Enter Bench

of the Salt Lake Meridian

40.00 Set temp 1/4 Sec. cor.
43.00 Wash drus. North
Enter lower flat.
62.00 Wash drus. S. W.
74.50 " " " " [illegible] SE.
79.60 Int N and S. line, 90 lks. N. of cor. to Secs. 15. 16. 21. and 22 from which
N 89°21' W. on true line bet. Secs. 16 and 21
39.80 Cobble stone 15 x 10 x 6, 10 in deep, marked 1/4 on N side, with stone mound for 1/4 Sec. cor
79.60 The cor. to Secs. 16. 17 20 and 21.
Land rolling Bench
Soil 1st Rate
No Timber

Subdivisions Tp. 7 S. R 21 E.

North bet. Secs. 16 and 17
Var 16° 30' E.

5.00 Wash drains S.W.
17.00 Enter Bench
40.00 Set charred Cottonwood post 4" x 4" 4 ft. long 2 ft. deep marked 1/4 S on W side with stone mound for 1/4 Sec. cor.
51.00 Enter lower flat
63.00 Wash drns. West.
71.00 Wash drns. S. W.
80.00 Set charred Cottonwood post 4" x 4" 4 ft. long 2 ft. deep, marked 4 notches on S and E. edges with reg mound and pits for. cor. to Secs. 8. 9. 16 and 17.
Land level
Soil 1st rate

of the Salt Lake Meridian

No timber.

East on random line
bet Secs. 9 and 16
Var 16°30' E.

13.00 Wash drus. S. W.
7.00 Set temp. 1/4 Sec. cor
80.00 Int. N and S. line, at cor.
to Secs. 9. 10. 15 and 16
from which
West on true line
bet. Secs. 9 and 16
4.00 Set charred Cottonwood
post 4" x 4" 4 ft. long
2 ft. dep, marked 1/4 S
on N side with reg.
mound and pits for
1/4 Sec. cor.
8.00 The cor to Secs. 8. 9. 16

Subdivisions Tp. 7 S. R 21 E.

and 17.

Land level
Soil 1st rate
No Timber.

North bet Secs. 8 and 9
Var 16° 30' E.

5.00 Enter Bench
40.00 Set charred Cottonwood post 4" x 4" 4 ft. long, 2 ft. deep, marked 1/4 S. on W side, with reg. mound and pits for 1/4 Sec. cor.
43.50 Hollow drus. S. W.
80.00 Set charred Cottonwood post 4" x 4" 4 ft. long 2 ft. deep, marked 5 notches on S and 4 on

of the Salt Lake Meridian

E edge with org mound
of earth and pits for
Cor to Secs. 4. 5. 8. and 9
Land mostly level
Soil 1st rate
No timber

East on random line
bet Secs. 4 and 9
Var 16°30' E.

40.00 set temp. 1/4 Sec. cor.
80.20 Int. N and S. line, at cor.
to Secs. 3. 4. 9 and 10
from which
Watson true line bet
Secs 4 and 9
40.10 set stone 12 x 10 x 5
8 in dep, marked 1/4 on
N side with org mound

Subdivisions Tp. 7 S. R 21 E.

and pits for 1/4 Sec. cor.

80.20 The cor. to Secs. 4. 5. 8 & 9

Land level

Soil 1st rate

No Timber

North on random line

bet. Secs. 4 and 5

Var 16° 30' E.

39.00 Hollow drus. West.

40.00 Set temp. 1/4 Sec. cor.

51.75 Left Bank of Green River

4 ft. deep rus. West

59.50 Right Bank of Green River

80.00 Int. N. Boundary of Tp at cor. to Secs. 4 and 5

from which

South on true line

of the Salt Lake Meridian

Lot Secs. 4 and 5

On right bank of Green River

20.50 Set charred Cottonwood post 4" x 4", 4 ft. long, 2 ft. deep, marked M. C. with stg. mound and pits, for Meander cor. to fractional Secs. 4 and 5

On left bank of Green River

28.25 Set charred Cottonwood post 4" x 4" 4 ft. long 2 ft. deep, marked M. C. with stg. mound and pits for Meander cor. to fractional Secs. 4 and 5

40.00 Set standstone 16 x 9 x 5 in. in deep, marked 1/4 on W. side with stg. mound and pits for 1/4 Sec. cor.

80.00 The cor. to Secs. 4, 5, 8 and 9

Land level

Soil pt. rate

Subdivisions Tp. 7 S. R 21 E. of the

No Timber

North bet. Secs. 31 and 32
Var. 16°30' E

8.50 Leave undergrowth

40.00 Set charred Cottonwood post
4" x 4" 4 ft. long 2 ft. deep
marked 1/4 S on W side
with reg. mound and pits
for 1/4 Sec. cor.

70.00 Leave meadow. Enter sagebrush

80.00 Set charred Cottonwood post
4" x 4" 4 ft. long, 2 ft. deep
marked 1 notch on S and
5 on East edges. with
reg. mound and pits
for cor. to Secs. 29. 30
31 and 32.
Land level

Salt Lake Meridian

Soil 1st rate
No Timber
Ally needed on 8.50 chns.

East on random line
bet. Secs. 29 and 32
Var 16° 30' E

5.00 Enter Meadow
48.00 Set temp. 1/4 Sec. cor
45.00 Enter Heavy undergrowth
70.20 Right Bank of Green River 4 ft. deep rus. S.W.
Note: The cor to Secs. 28. 29. 32 & 33 falling in River I therefore connect with the meander cor to Secs. 28 and 33 5.33 chs. E. of said cor point on left bank of River by triangulation; find its course

Subdivisions: Tp. 7 S. R 2 E.

to be due East. 15.13 chns
distant which would
make connection with
cor. point as follows.

80.00 Int. N. and S. line at
cor. point to Secs. 28.29.
32 and 33. from which
West on true line bet
Secs. 29 and 32)

40.00 Set charred hollowwood
post 4" x 4", 4 ft. long
2 ft. deep, marked 1/4 Sec
N side, with reg. mound
and pits, for 1/4 Sec. cor.

80.00 N.E. cor. to Secs. 29. 30. 31 and
32)

Land level
Soil 1st rate
No timber
Heavy undergrowth on 25.20 chns

of the Salt Lake Meridian

augmented on 25.20 chns.

West on random line
bet. Secs. 30 and 31
Var 16°30' E.

40.00 Set temp. 1/4 Sec. cor.
48.00 Enter Bad land Break
63.50 Hollow draw south
78.40 Int. W. Boundary of Tp.
19 lks. S. of cor. to Secs. 30 & 31
from which
S. 89°52' E on line
bet. Secs. 30 and 31
38.40 Set Cobble stone 13 x 8 x 6 8
in deep marked 1/4 on N side
with stone mound for
1/4 Sec. cor.
78.40 The cor to Secs. 29. 30. 31 & 32
Land level and broken

Subdivisions Tp. 7 S. R 21 E.

Soil 1st and 3rd rate
No Timber
Augmented on 34.40 chns.

North bet. Secs. 29 and 30
Var 16°30'

40.00 Set charred Cottonwood post 4"x4" 4 ft. long, 2 ft. deep, marked 1/4 S on W side, with reg. mound and pits for 1/4 Sec. cor

46.00 Right Bank of Green River, 4 ft. deep rod East Set charred Cottonwood post 4"x4" 4 ft. long 2 ft. deep, marked M. C. with reg. mound and pits for Meander cor to fractional Secs. 29 and 30 ascertained by triangu=

of the Salt Lake Meridian

lation distance across River to be 13.00 chns.

59.00 Left Bank of Green River set charred Cottonwood post 4" x 4" 4 ft. long 2 ft. deep marked M.C. with reg. mound and pits for Meander Cor. to fractional Secs. 29 & 30

80.00 Set charred Cottonwood post 4" x 4", 4 ft. long 2 ft. deep, marked 2 notches on S and S on E. edges, with reg. mound and pits for cor to Secs. 19, 20, 29 and 30.

Land level
Soil 1st rate
No Timber
October 27th 1879

Subdivisions Tp. 7 S. R 21 E.

East on random line
bet. Secs. 20 and 29
Var 16°30' E

40.00 Set temp. 1/4 Sec. cor. & [illegible]
[illegible] brush
68.00 Wash drns. South
71.50 " " "
75.00 Leave Brush
80.20 Int. N and S. line at cor to Secs.
20. 21. 28 and 29 from which
West on true line
bet Secs. 20 and 29
40.00 Set sandstone 24 x 8 x 4
18 in deep marked 1/4 on
N. side, with stone mound
for 1/4 Sec. cor.
80.20 The cor. to Secs. 19. 20. 29 & 3
Land level
Soil 1st rate
No Timber

BOOK-A-162

of the Salt Lake Meridian

West on random line
bet. Secs. 19 and 30
Var 16°30' E

20.00 Leave Meadow
40.00 Set temp. 1/4 Sec. cor.
78.90 Int. W. Boundary of Tp.
22 N. R 5 E. cor. to Secs.
19 and 30 from which
N 89°57' E on true line
bet. Secs. 19 and 30.
38.90 Set charred Willow wood
post 4" x 4" 4 ft. long, 2 ft.
deep, marked 1/4 Sec N side
with reg. mound and pits
for 1/4 Sec. cor.
78.90 The cor to Secs. 19, 20, 29
and 30

Land level
Soil st. rate
No Timber

Subdivisions Tp. 7 S. R. 21 E.

North bet. Secs. 19 and 20

Var 16° 30' E.

40.00 Set bobble stone, 4 x 10 x 4, 9 in. deep, marked 1/4 on N side, with stone mound for 1/4 Sec. cor.

43.00 Left Bank of Green River Set charred Cottonwood post 4" x 4" 4 ft. long 2 ft. deep marked M. C. with reg. mound and pits for Meander Cor. to fractional Secs. 19 and 20. ascertained by triangulation distance across Green River to be 13.00 chains

58.00 Right bank of Green River 4 ft. deep. Set charred Cottonwood post 4" x 4" 4 ft. long

of the Salt Lake Meridian

2 ft. deep marked M. C.
with reg. mound and
pits for Meander Cor.
to fractional Secs. 19 & 20
20.00 Set Cobble stone 12 x 8 x 6,
8 in. deep, marked 3 notches
on S and 5 on E. edges with
reg. mound and pits for
cor. to Secs. 17, 18, 19 and 20
Land level
Soil 1st rate
No Timber

East on random line
bet. Secs. 19 and 20
Var 16° 30' E.
16.00 Right Bank of Green
River 4 ft. deep on South
Set charred Cottonwood post

Subdivisions Tp. 7 S. R 21 E.

4" x 4" 4 ft. long, 2 ft.
deep, marked M. C. with
reg. mound and pits
for Meander cor. to
fractional Secs. 12 and 20
Ascertained by triangula-
tion distances across River
to be 14.70 chns.

30.70 Left Bank of Green
River set Sandstone
12 x 12 x 4, marked M. C.
with stone mound for
Meander cor. to fractional
Secs. 17 and 20

40.00 Set temp. 1/4 Sec. cor.
60.00 Wash chns. S. W.
80.00 Int N. and S. line at cor.
to Secs. 16. 17. 20 and 21
from which
West on true line
bet Secs. 17 and 20

of the Salt Lake Meridian

40.00 Set Sandstone 12 x 8 x 6, marked 1/4 on N side, with reg. mound and pits for 1/4 Sec. cor.

80.00 The cor to Secs. 17, 18, 19 & 20
Land level
soil 1st rate
No timber

West on random line
bet. Secs. 18 and 19
Var 16° 30' E.

20.00 Mosby's Cabin. brs. S. 27°
20' W

40.00 Set temp. 1/4 Sec. cor
from which Mosby's Cabin
brs. S. 27° E

78.80 Int. W. Boundary of Tp. at
cor. to Secs. 18 and 19

Subdivisions Tp. 7 S. R 21 E.

from which
East on true line bet
Secs. 18 and 19

38.80 Set charred Cottonwood post
4" x 4" 4 ft. long 2 ft. deep
marked 1/4 on N side, with
reg. mound and pits
for 1/4 Sec. cor.

78.80 The cor. to Secs. 17. 18. 19
and 20
Land level
Soil 1st rate
Geo Tinker.

North bet. Secs. 17 and 18
Var 16° 30' E.

40.00 Set cobble stone 12 x 8 x 6
8 in. deep marked 1/4 on
N. side, with reg.

of the Salt Lake Meridian

mound and pits for
1/4 Sec. cor.
80.00 set stone 18 x 18 x 5
15 in deep, marked 4
notches on E and 5 on E
edges, with stone mound
for cor to Secs. 7, 8, 17
and 18
Land level
soil 1st rate
No Timber

East on random line
bet. Secs. 18 and 17
Var 16° 30' E.
4.60 Right Bank of Green
River 4 ft. deep run South
ascertained by triangu
lation distance across

Subdivisions Tp. 7 S. R 21 E.

River 19. 40. chns.

24.00 Left Bank of Green River.

40.00 Set temp 1/4 Sec. cor. Wash drus. S. W.

71.00 " " " "

80.00 Int. N and S. line at cor. to Secs. 8. 9. 16 and 17 from which West on true line bet. Secs. 8 and 17

40.00 Set Sandstone 10 x 8 x 7, 6 in. deep, marked 1/4 on N side with stone mound for 1/4 Sec. cor.

56.00 Set Sandstone 20 x 12 x 5 15 in. deep, marked M. with reg. mound and pits for Meander Cor. to fractional Secs. 8 and 17

of the S

75.40 Se

pos

2 f

pit

pit

to f

80.00 Th

18

L

We

l

15.00 a

29.00 H

32.00

40.00 Se

of the Salt Lake Meridian

75.40 Set charred Cotton wood post 4"x4" 4 ft. long 2 ft. deep, marked M. C. with reg. mound and pits for Meander Cor. to fractional Secs. 8 and 17

80.00 The cor to Secs 7, 8, 17 and 18

Land level
Soil 1st rate
No Timber

West on random line
bet Secs. 7 and 18
Var 16°30' E.

15.00 ascend

29.00 Hollow drus. South

32.00 " " "

40.00 Set temp. 1/4 Sec. cor

Subdivisions Tp. 7 S. R 21 E.

77.80 Int West Boundary of Tp. at cor. to Secs. 7 & 18 from which
East on true line bet Secs. 7 and 18
37.80 Set Sand stone 12 x 10 x 4, marked 14 on N side with stone around for 1/4 Sec. cor.
77.80 The cor. to Secs. 7. 8. 17 and 18
Land undulating soil 2nd rate
No Timber

North bet Secs. 7 and 8
Var 16° 30' E.
40.00 Set charred cottonwood post 4" x 4" 4 ft. Coz 2

of the Salt Lake Meridian

2 ft. deep, marked 1/4 S on
W side with reg mound
and pits for 1/4 Sec. cor.

42.00 Right Bank of Green
River 4 ft. deep rus. S. E.
Set charred Cottonwood
post 4" x 4" 4 ft. long
2 ft. deep, marked M. C.
with reg. mound and
pits for Meander Cor.
to fractional Secs 7 & 8
ascertained by triangulation distance
across River to be
14.00 chns.

56.00 Left Bank of Green River
Marked Sta. Sandstone
4 x 3 x 2 ft. above ground
M. C. for Meander
Cor. to fractional Secs 7 & 8

Subdivisions Tp. 7 S. R 21 E.

80.00	Set Sandstone 14 x 12 x 4
	9 in. deep, marked 5 notches
	on Sand E. edges, with
	reg. mound and pits
	for cor. to Secs. 5. 6. 7 & 8
	Land level
	Soil 1st rate
	No Timber
	East on random line
	bet. Secs. 5 & 8
	Var 16° 30' E
40.00	Set temp. 1/4 Sec. cor.
60.00	Enter Bench
80.00	Int. N. and S. line 42 lks.
	S. of cor. to Secs. 4. 5. 8 & 9
	from which
	S. 89° 42' W on true
	line bet. Secs. 5 and 8

of the

40.00	Se
	9 in
	N
	a
80.00	9
	L
	N
11.50	L
	4 f
	as
	di
	le
36.00	Ru
	4
	Ru

of the Salt Lake Meridian

40.00	Set Sandstone 14 x 7 x 7, 9 in. deep marked 1/4 on N side with reg. mound and pits for 1/4 Sec. cor.
80.00	The cor to Secs. 5. 6. 7 & 8 Land level Soil 1st rate No Timber
	West on ~~true~~ random line bet. Secs. 6 and 7 Var 16° 30' E.
11.50	Left Bank of Green River 4 ft. deep rus. S. E. ascertained by triangulation distance across River to be 24.50 chns.
36.00	Right Bank of Green River formed by Bluffs.

Subdivisions Tp. 7 S. R 21 E.

150 ft. Leigh

40.00 Set temp. 1/4 Sec. cor.

77.25 Int W. Boundary of Tp. at cor. to Secs. 6 & 7 from which

East on true line bet. Secs. 6 and 7.

37.25 Set sandstone 14 x 10 x 5 9 in deep marked 1/4 on N side, with stone mound for 1/4 Sec. cor.

41.25 Set sandstone 18 x 12 x 12, 12 in. deep marked M. C. with stone mound for Meander cor. to fractional Secs. 6 and 7

65.75 Set sandstone 12 x 12 x 4 8 in deep marked M. C. with stone mound for Meander cor. to fractional

BOOK-A-162

of the Salt Lake Meridian

Secs. 6 and 7

77.25 The cor to Secs. 5. 6. 7 and 8.
Land nearly level
Soil 1st rate
No Timber.

North on random line
bet. Secs. 7 and 6
Var 16° 30' E.

0.80 Wash dry West
6.50 Hollow dry. West
22.00 Enter Bottom
40.00 Set temp 1/4 Sec. cor.
52.00 Left Bank of Green River
runs West - ascertained
by triangulation distance
across river to be 7.50 chns.
59.50 Right Bank of Green River
73.00 Arrived

Subdivisions Tp. 7 S. R 21 E.

77.00 Ridge point brs. E. and W.

80.00 Int. N. Boundary of Tp. at cor to Secs. 5 and 6. from which S. on true line bet. Secs. 5 and 6.

20.50 Set charred Cottonwood post 4" x 4" 4 ft. long 2 ft. deep, marked M. C. with reg. mound and pits for Meander cor. to fractional Secs. 5 and 6

28.00 Set Cobble stone 12 x 10 x 6 8 in. deep marked M. C. with stone mound for Meander cor to fraction Secs. 5 and 6.

40.00 Set Sand stone 13 x 8 x 5 9 in. deep, marked 1/4 on W side with stone mound for 1/4 Sec. cor

the Salt Lake Meridian

80.00 The cor to Secs. 5, 6, 7 and 8
Land mostly level
Soil Gravelly
No Timber
October 28th 1879

Meanders of the Right
Bank of Green River
From the Meander Cor. 6.55
chns. East of cor. to Secs. 1 & 2
on N. Boundary of Tp. on
Right Bank of Green River
I. Meander down stream
Ln. Sec. 1
Var 16°30' E
S. 44° W. 12.30 chns. to
Meander cor. to fractional
Secs. 1 and 2 Lower
Ln Sec. 2
S 44° W 2.00 chns.

Meanders Tp. 7 S. R 21 E

S. 72° 30' W 23.20 chns.
N. 75° W 25.00 "
N. 33° 15' W 19.50 " to
67.70
Meander cor. 14.92 chns East
of cor. joint to Secs. 2 and 3 on
North Boundary of Tp.

From Meander cor. 2.00 chns
East of cor. to Secs 4 and 5
on N. Boundary of Tp. on
Right Bank of Green River
I Meandered down Stream
In Sec. 4.
S 10° E. 7.50 chns.
S 4° 30' W 10.00 "
S 38° 45' W 4.00 " to
1.50
Meander cor. bet. Secs. 4 and 5
Thence in Sec. 5.
S 65° W 2.60 chns.
West 4.00 "
6.60

BOOK-A-162

of the Salt Lake Meridian

N. 79°30' W	15.00 chns.
N. 85° W	7.00 "
S 84° W	26.00 "
West	24.00 "
N 77° W	2.12 " to

Meander cor. bet. Secs 5 and 6. Thence

In Sec. 6.

N. 79° W	15.00 chns.
N 15°45' E	6.00 "
N. 78° W	17.00 "
S. 33° W	16.50 "
S. 16°15' W	10.00 "
S 3°45' W.	12.00 "
S 9°30' E	36.75 " to

Meander cor. bet. Secs 6 and 7. Thence on

Sec. 7.

South 17° E	21.00 chns.
S 69° E	20.00 "
	41.00

Meanders. Tp. 7 S. R 21 E. of the

S. 47° E. 16.00 chns. to
Meander cor. bet. Secs. 7 & 8.
Thence in Sec. 8.
South 6° 15' E 42.25 chns
to Meander cor. bet. Secs.
8 and 17. Thence
In Sec. 17
South 46.00 chns.
S. 18° 30' E. 36.00 "
to Meander cor. bet
Secs. 17 and 20. Thence
In Sec. 20.
S 18° W 16.00 chns.
S 58° 30' W 13.00 "
Meander cor. bet Secs.
19 and 20 thence in Sec
19.
S. 60° W 8.00 chns.
S 72° 30' W 15.00 "
S. 83° 30' W 21.00 "
25.00

Salt Lake Meridian

West 25.00 chns.
S. 84°30' W 11.80. " to
Meander cor. 46. chns. North
of cor. to Secs. 19 & 30
on W. Boundary of Tp.

From Meander cor. 43.50 N.
of cor. to Secs. 30 and 31 on
W. Boundary of Tp. on Right
Bank of Green River I
meander down stream

In Sec. 30

N. 79°30' E. 38.00 chns.
East 8.00 "
S. 70° E 21.00 "
N. 78°30' E 13.70 " to
Meander cor. bet. Secs.
29 and 30 Thence

In Sec. 29

N. 78°30' E. 25.00 chns

Meanders Tp. 7 S. R 21 E. of the Salt

S 83° E	34.00 chns.	
S 42° 30' E.	22.00 "	
S 3° 30' E	2.60 "	
S 25° W	10.00 "	G
	1-09.60	

Meander cor. bet. Secs. 29 and 32 Thence

In Sec. 32.

S. 22° W.	15.00 chns.	
S 25° 30' W	17.00 "	
S 34° 15' W	13.00 "	
S 29° 15' W	30.00 "	
S 39° W	17.80 "	G
	1-12.80	

Meander cor. 24.20 chns. East of cor. to Secs. 31 & 32 on South Boundary of Tp.

October 29th 1879

of the Salt Lake Meridian

Meanders of the left Bank of Green River.

Beginning at the Meander Cor. 25.25 chns. East of cor. point to Secs. 1 and 2 on the North Boundary of Tp. I meandered down stream

In Sec. 1

Var 16°30' E

S. 28° W	16.00 chns.
S 48° W.	24.00 " to
	40.00

Meander cor. bet. Secs. 1 & 2

Thence in Sec. 2

S. 81° W	14.80 chns.
West	27.00 "
N. 70° 30' W	17.00 "
N. 50° W	29.00 "
	104.80

to Meander cor bet. Secs 2 and 3. Thence

In Sec. 3

Meanders Tp. 7 S. R 21 E.

N. 62° W. 16.50 chns.
Meander cor. 64.57 chns.
East of cor. 6 Secs. 3 and 4
on N. Boundary of Tp.

From the Meander cor.
8.00 chns. East of cor. 6 Secs.
4 and 5 on N. Boundary of
Tp. on Left Bank of Green
River I meander down
Stream In Sec. 4.

S. 20° E 4.00 chns
S. 1° 45' W 15.00 "
S 30° W 10.00 "
S 78° W 4.00 "
33.00
Meander cor. bet. Secs. 4 & 5
Thence in Sec 5
N. 86° W. 21.00 chns
S. 80° W 15.00 "
West 38.00 "
74.00

The Salt Lake Meridian

N. 78° W 6.50 chns.
to Meander cor. bet
Secs. 5 and 6. Thence
In Sec. 6
N. 79° W. 14.00 chns.
S 80° W 13.00 "
S 23° W 6.00 "
S 21° E 45.00 "
S 14° E 5.00 "
to Meander cor. bet. Secs
6 and 7
Thence In Sec. 7
S 25°30' E 26.60 chns.
to Meander cor. bet
Secs. 7 and 8 Thence
In Sec. 8
S. 50° E 14.00 chns.
S 26° E. 17.00 "
S. 18° E. 32.20 "
to Meander cor. bet. Secs.

Meanders, Tp. 7 S. R 21 E of M.

8 and 17. Thence

In Sec. 17

S. 30° W 47.00 chns.
S 15° E 21.50 "
S 13° E 15.60 "
to Meander cor. bet. Secs.
17 and 20 Thence

In Sec. 20.

S 90 W 21.00 chns.
S 31° W 9.00 "
S 72°30' W 22.80 "
to Meander cor. bet.
Secs. 19 and 20 Thence

In Sec. 19.

S. 67° W. 29.00 chns.
N 85°30' W 16.00 "
West 36.90 "
to Meander cor. 33.00 chns.
North of cor. to Secs. 18 and
30. on W. Boundary of

Salt

Salt Lake Meridian

T. 7 N.

From the Meander cor. 61.00 chns North of the cor to Secs. 30 and 31 on the West boundary of T. 7 N. and left bank of Green River I meander down stream

In Sec. 30.

N. 81° 45' E.	72.00 chns.
S 72° E	31.00 "
N. 77° 45' E	8.00 " to

Meander cor. bet. Secs. 29 and 30 Thence

In Sec. 29

N. 75° 45' E.	27.00 chns.
S 81° 15' E.	33.00 "
S 64° 00' E	23.50 " to

Meander cor bet Secs 28 and 29

Meanders Tp. 7 S. R 21 E

Thence in Sec. 28

S. 51° 45' E. 8.00 chns.

S 10° E 30.00 "

S 21° E. 17.20 " to

Meander cor. bet. Secs.

28 and 33. Thence

In Sec. 33.

S. 11° W 27.50 chns.

to Meander cor. bet Secs.

32 and 33. Thence

In Sec. 32.

S. 18° 45' W. 18.00 chns

S 33° 30' W 32.00 "

S 54 00 W 16.00 "

66.00

to Meander cor. 43.68 chns

E. of cor. to Secs. 31 and 32

on South Boundary of Tp.

Land on both sides of River

is mostly good Bottom

Soil 1st rate

BOOK-A-162

of the Salt Lake Meridian

Timber scattered small groves of sweet Cottonwoods Heavey undergroth of Willows, Sweet Brier Hawthorne and Bullberry.

Augmented meanders on 23 Miles 79.20 chs.

October 30th 1879

General Description

This Tp. embraces some first class Bottoms along Green Riv and adjacent Benches.

The Bottoms are subject to overflow at some seasons. the Benches can mostly be irrigated from Green River and contain good soil with the exception of the breaks, ~~in dec.~~

Our settlement has been made in Sec. 19 and various claims exist in Secs. 29, 30, 31, and 32.

E. Buettner
U. S. Dep. Surveyor

BOOK-A-162

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, Febry 24/1880

The foregoing field notes of the survey of the

Subdivision and Meander lines of

Township No 7 S. *Range No* 21 E.

of the Salt Lake Meridian, Utah Territory,

Executed by E. Buettner

Under joint *contract No* 92

of the 13th *day of* June *1879.*

in the month of Oct. *1879*

having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.

Jno. Salisbury

U. S. Surveyor General for Utah.

BOOK-A-162
R: 1880. 162 / 166

Filed Jany 21st 1880

Examined by F. C. Bailey

Compared by F. C. Bailey

FIELD NOTES

OF

THE SURVEY OF THE

Exteriors

of Township No. 7 South Range No. 21 East

of the Salt Lake Meridian in Utah Territory.

BY

E. Breitmer

U. S. DEPUTY SURVEYOR,

Under his grant Contract No. 221

dated June 13th 1879.

Survey commenced October 22nd 1879.

Survey completed " " 1879.

East Boundary Tp. 7 S. R 21 East

Survey commenced Oct. 22nd 1879
by E. Buettner.
From the corner to Tps. 7 and
8 S R. 21 and 22 E
North bet. Secs. 31 and 36
Var 16° 30' E.

1.50 Hollow drus. S. W.
15.00 Enter Bench
29.50 Bottom of broad hollow drus.
S. W.
38.00 Enter Bench
40.00 Set sandstone 18 x 8 x 3, 12 in.
deep marked 1/4 on W. side
with reg. mound and pits
for 1/4 Sec. cor.
73.00 Wash drus. West
0.00 Set charred Cottonwood post
4" x 4" 4 ft. long, 2 ft. deep
marked 5 notches on N and
1 on South edges with reg.

East Boundary Tp. 7 S. R 21 E. of

mound and pits, for cor.
to Secs. 25. 30. 35 & 36
Land South ½ Broken
North ½ level
Soil 1st and 3rd rate
No Timber
Augmented over 38.00 chns.

North bet Secs. 25 and 30
Var 16° 30' E.

40.00 Set Sandstone 18 x 6 x 4,
12 in. deep, marked ¼ on
W side, with stone mound
for ¼ Sec. cor.
45.00 Descend into Breaks
47.00 Head of Gulch drns. N.
80.00 Set Sandstone 24 x 14 x 9,
18 in. deep, marked 4 on
North and 2 on S Edges

Salt Lake Meridian

with stone mound for cor
to Secs. 19. 24. 25 and 30
Land level Bench and
Breaks
Soil 1st and 3rd rate
Timber a few Cedar
Ang mented on 35.00 chns.

North bet. Secs. 19 & 24
Var 16°30' E.

11.50 Gulch drns West
36.00 " " "
40.00 Set Sandstone 18 x 6 x 5,
12 in. deep marked 1/4
on W side, with stone
mound for 1/4 Sec. cor,
73.00 Enter level Bench
80.00 Set Sandstone 12 x 10 x 5
8 in. deep, marked 3 notches

East Boundary Tp. 7S. R21E

on N and S edges with
reg. mound of earth
and pits for cor. to
Secs. 13, 18, 19 and 24
Land Broken on 73.00 chns.
Soil 2nd rate
No Timber
augmented on 73.00 chns

North bet. Secs. 13 & 18
Var 16°30' E

34.00 Wash drns. West
40.00 Set Sandstone 10 x 8 x 6,
6 in. deep, marked 1/4 on
W side, with reg. mound
and pits for 1/4 Sec. cor.
80.00 Set Sandstone 22 x 7 x 4
16 in. deep marked 2
notches on N and 4 on

of the Salt Lake Meridian

S. Edges, with stone mound
for cor. to Secs. 7, 12, 13 & 18
Land rolling
Soil 1st rate
No Timber

North bet. Secs. 7 & 12
Var 16° 30' E

$3.00 Wash drus. West.
$5.00 Set Sandstone 12 x 8 x 6,
8 in. deep marked 1/4 on
W side, with reg. mound
and pits for 1/4 Sec. cor.
$0.00 Set Sandstone 15 x 10 x 5,
10 in. deep, marked 1 notch
on N and 5 on S. Edges
with reg. mound and pits
for cor. to Secs. 1. 6. 7 & 12
Land level

East Boundary Tp 7 S. R 21 E

Soil 1st rate
No Timber.

North bet Secs 4 & 5
Var 16° 30' E

7.00 Leave Bench, descend into br
40.00 Set Sandstone 14 x 8 x 6
10 in. deep, marked 1/4 on
W side, with stone mound
for 1/4 Sec. cor.
63.00 Gulch drns N. E.
80.00 On S. side of deep Gulch drns
N. W. Set Sandstone 15 x 8
10 in. deep, marked 6 notches
on N. S. E and W edges
with stone mound for
Cor. to Tps. 6 and 7 S. R.
26 and 27 E.
Land heavy Breaks

BOOK-A-162

Soil 3rd rate

No Timber

augmented on 73.00 chns.

North Boundary of Tp.
7 S. R 21 E.

From the cor. to Tps. 7 and
8 S. R. 21 and 22 E.
I run
West on random line
between said Tps. setting
temporary 1/2 mile and
mile cor. I find the line
to be 5 miles 77 chns
and 60 lks. and the
falling 80 ~~falling~~ links South
The correction will therefore
be 14 lks. S. per mile

North Boundary Tp. 7 S. R 21 E

From the cor. to Tps.
6 and 7 South R. 20 and 21 E.
Grum
South 89°57' E.
on true line bet. Secs. 6 & 31
Var 16° 30' E

27.00 Enter Green River Breaks.
37.60 Set Sandstone 20x11x7.
15 in. deep, marked 1/4
on N side with stone mound
for 1/4 Sec. cor.
44.50 Gulch wash drns. N. E.
49.00 " " " North
77.60 Set Sandstone 20x12x5
15 in. deep, marked 1/4 north
on E and on W. edges
with stone mound for
cor. to Secs. 5. 6. 31 & 32
Land mostly Broken
Soil good rate

of the Salt Lake Meridian

No Timber

Acq. rented on 53.00 chns.

S. 89° 54' E on true line
bet Secs. 5 and 32
Var 16° 30' E.

24.00 Enter Brush and Bottom.

35.08 Right Bank of Green River
thence along said bank

40.00 Set charred Cottonwood post
4" x 4" 4 ft. long 2 ft. deep
marked 1/4 S on N. side
with reg. mound and pits
for 1/4 Sec. cor.

68.40 Leave Green River Bank
River runs N. E.

80.00 Set charred Cottonwood post
4" x 4" 4 ft. long, 2 ft.
deep, marked 2 notches on

North Boundary Tp. 7 S. R 21 E

W. and 4 on E, Edges,
with reg. mound and
pits for cor. to Secs 4, 5
32. and 33.
Land mostly Bottom
Soil 1st rate
No Timber.
Heavy undergrowth in
Bottom
augmented on 80.00 [illegible]

S. 89° 54' E on true line
bet. Secs. 4 and 33
Var 16° 30' E.

2.00 Right Bank of Green Ru
4 ft. deep. rus. South
Set Sandstone 12 X 10 X 8,
8 in deep marked M.C.
with stone mound for

BOOK-A-162

Meander Cor. to fractional
Secs. 4 and 33
8.00 Left bank of Green River
Bluff 100 ft. high
Set Sandstone 12 x 3 x 8
8 in. deep, marked M. C.
with stone mound for
Meander Cor. to fractional
Secs. 4 and 33.
40.00 Set Sandstone 12 x 8 x 6,
8 in deep marked 1/4 on
N. side, with stone mound
for 1/4 Sec. cor.
80.00 Set Sandstone 12 x 10 x 10
8 in deep marked 3 notches
on E and W edges with
stone mound for cor.
to Secs. 3. 4. 33 and 34
Land high rolling Bench
Soil 2nd rate

North Boundary Tp. 7 S. R 21 E.

No Timber.

S. 89°54' E on true line, bet. Secs. 3 and 34

Var 16°30' E.

40.00 Set Sandstone 12 x 10 x 5 8 in deep, marked 1/4 on N side with stone mound for 1/4 Sec. cor. at foot of ridge bns. S. E.

64.57 ~~Right~~ Left Bank of Green River 4 ft. deep rns. S. E. Set Sandstone 20 x 8 x 6 15 in. deep marked M. C. with stone mound for Meander cor. to fractional Secs. 3 and 34 and Witness to Cor. point of Secs. 2 and 3

of the Salt Lake Meridian

80.00 Falls in River not set
Land high rolling Bench
Soil 2nd rate
No Timber.

East on true line
bet. Secs. 2 and 35
Var 16° 30' E.
Note: From the Witness
Cor. 15. 43 chns. W. of
cor. point to Secs. 2. 3.
34 and 35 I ascertained
by triangulation distance
across River to be 30.35
chains.

14.92 ~~Left~~ Right Bank of Green River
Set charred Cottonwood post
4" x 4" 4 ft. long, 2 ft. deep
marked M. C. with reg.

North Boundary Tp. 7 S. R 21 E

mound and pits for
Meander cor. to fractional
Secs. 2 and 35
40.00 Set sandstone 18 x 18 x 8
6 in. deep, marked 1/4 on
N side with stone mound
for 1/4 Sec. cor
80.00 Set sandstone 19 x 8 x 8
12 in. deep, marked 1/4 north
on E and S on W. edges
with stone mound for
cor. to Secs. 1. 2. 35 &
36.
Land rolling Bench
Soil 2nd rate
No Timber

S. 89.54 E on true
line bet Secs. 1 & 36

of the S

6.35

25.25

40.00

of the Salt Lake Meridian

Var 16° 30' E.

6.25 Set sandstone 20x18x3
15 in. deep, marked
M. C. ~~[illegible]~~ With stone
mound for Meander Cor
to Fractional Secs. 4 & 36.
on Right Bank of
Green River bears S.W.
ascertained by triangu-
lation distance across
River to be 18.70 chns.

25.25 Set sandstone 14x10x4
9 in. deep, marked M. C.
with stone mound for
Meander Cor. to Fraction-
al Secs 1 and 36.
on Left Bank of
Green River

40.00 Set sandstone 11x10x6
6 in. deep, marked [illegible] on

BOOK-A-162

1882

North Boundary Tp 7 S. R 21 E

N. side, with stone mound for 1/4 Sec. cor

80.00 The cor. to Shs. 6 and 7

p. R. 21 and 22 E.

Land rolling Bench

Soil 3rd rate

No Timber.

Note: For General Description see end of Subdivisions of this Tp.

October 22nd 1879

E. Buellner

U. S. Dep. Sur.

of the

BOOK-A-162

153

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, Febry 24 1880

The foregoing field notes of the survey of the

Exterior Boundaries of

Township No 7 S. *Range No* 21 E.

of the Salt Lake Meridian, Utah Territory,

Executed by E. Buettner

Under priv *contract No* 92

of the 13th *day of* June 1879

in the month of Oct. 1879

having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.

Frde. Salomon

U. S. Surveyor General for Utah.

BOCK-A-162

R: Orkiep 1880 (162) 184

Filed Jany 20th 1880.

J.H.C. Examined by T. C. Bailey

Compared by " " "

FIELD NOTES

OF

THE SURVEY OF THE

Exteriors

of Township No. 8 South, Range No. 21 East

of the Salt Lake Meridian in Utah Territory.

BY

E. Buettner

U. S. DEPUTY SURVEYOR,

Under his joint Contract No. 92

dated June 13th 1879.

Survey commenced October 13th 1879.

Survey completed October 14th 1879.

South Boundary Tp. 8 S. R 21 E.

Survey commenced Oct. 13. By E. Baethner

Note: The S. E. cor. of this Tp. not being established therefore, from the cor. to Tps. 8 & 9 S. R. 20 & 21 E. on the Green River Guide Meridian, I run East on true line bet Secs. 6 & 31

Var 16° 30' E

8.00 Flat top of Bad land hill
24.00 Descend
28.75 Enter flat
38.80 allowing for. Conver. of Meridian set Sandstone 18 X 12 X 8; 12 in. deep marked 1/4 on N. side with reg. mound and pits for 1/4 Sec. cor.
47.50 Road brs. N. W. & S. E.
77.15 " " N. & S.

South Boundary Tp. 8 S. R 21 E

77.80 Right Bank of White River
Runs South, 150 chns. wide 4 ft. deep
78.80 Falls in River not set
Therefore at 77.80 chns.
I set charred Cottonwood
post 4"x4", 4 ft. long, 2 ft
deep, marked 5 notches on
E and 1 on W edges and
W. C. with reg. mound and pits for Witness Cor.
to Secs. 5. 6. 31 & 32.
Land broken and level
Soil 1st and 2nd rate
No Timber
Heavy brush in Bottom
Augmented on 78.80 chns.

East on true line
bet Secs. 5 & 32
Var 16° 30' E

of the Salt Lake Meridian

Note: as the line crosses White River a number of times, said River being a swift stream, about 150 lks. wide and 4 ft. deep, carrying a large amount of quicksand rendering its crossing at most points impracticable, therefore from the Witness Cor. 100 lks. West of cor. point to Secs. 5, 6, 31 & 32, I offset North 6.50 chns. thence East 41.00 chns. thence South 6.50 chns. to

40.00 on line in place

Set charred Cottonwood post 4"x4" 4 ft. long, 2 ft. deep marked 1/4 S on N. side, with rg. mound of earth and pits

South Boundary Tp. 8 S. R21 E

for 1/4 Sec. cor.
Note: For reasons given at
beginning of line, I again
offset North 6.50 chns.
East 40.00 chns
South 6.50 " to
80.00 in place on S.E. edge of
Bad land hill, marked
Stationary Sandstone
18 X 10 X 10 in. above grou
with a cross, and 4 notches
on E. and 2 notches on
limbs of same. (+)
mound and pits impracti
able, for cor. to Secs.
4. 5. 32 and 33.
Land mostly level Bottom
Soil 2nd rate
Heavy undergrowth
No Timber

BOCK-A-162

of the Salt Lake Meridian

augmented on 30.00 chs.

East on true line bet Secs
4 & 33.

Var 16°30' E.

1.50 Darling's house bears S.75°30' W
8.50 chs. distant

40.00 Set charred cottonwood post
4"x4", 4 ft. long 2 ft. deep
marked 1/4 S. on N. side
with reg. mound of earth and
pits for 1/4 Sec. cor.

80.00 Set charred cottonwood post
4"x4" 4 ft. long, 2 ft. deep
marked 3 notches on E and
Wedges, with reg. mound
of earth and pits, for cor. to
Secs. 3. 4. 33 and 34.

Land level

South Boundary Tp. 8 S. R. 21 E

Soil 1st rate
Heavy undergrowth
No Timber
augmented on 80 chns

East on true line
bet. Secs. 30-34
Var 16° 30'

26.00 Old bed of River brs. N.E. & S.
35.00 " " " " N.W. & S.
40.00 Set charred Cottonwood post 4"x4" 4 ft. long, 2 ft. deep marked 1/4 S. on N side with reg. mound and pits for 1/4 Sec. cor.
42.25 Road brs. N.W. and S.E.
60.30 Wash drns. S.W.
80.00 Set charred Cottonwood post 4"x4" 4 ft. long

of the Salt Lake Meridian

2 ft. deep, marked 2 notches on E and 4 on W edges, with reg. mound and pits for cor. to Secs. 2, 3, 34 & 35 from which G. Remington's cabins and settlements bear S. 36° E. 10 chns. dist.

Land level

Soil 1st rate

No Timber

Heavy undergrowth

Augmented on S. 50.00 chns.

East on true line

bet Secs. 2 & 35

Var 16°30' E.

40.00 Set charred hollowwood post 4"x4" 4 ft. long 2 ft. deep marked 1/4 Sec N. side

South Boundary Tp. 8 S. R 21 E of the

with reg. mound of earth
and pits, for 1/4 Sec. cor.
62.00 A Cottonwood 10' diameter
71.00 Right Bank of White River
1.50 chs. wide, 5 ft. deep, rus S.W.
being impossible to cross I
offset North 2.50 chns.
thence East 9.00 chns.
to a point 2.50 chns. North
of true cor. point (which
falls in overflowed land
and cannot be established)
where I set a charred
Cottonwood post 4" x 4", 4 ft
long, 2 ft. deep, marked
1 notch on E. and 5 on W. edge
and W. C. for Witness Cor.
to Secs. 1. 2. 35. and 36.
Land level Bottom
Soil 1st rate
No Timber

Salt Lake Meridian

Heavy undergrowth
Augmented on 80.00 chns

East on true line
bet Secs. 1 & 36
Var 16° 30' E.
From Witness Cor. 2.50
Chns. North of true cor point
to Secs. 1.2. 35 and 36.
I offset East 10.25 chns.
thence South 2.50 chns. to
10.25 on Right Bank of White
River rns. N. W. 6 ft. deep 1.60 chns. wide
19.25 Wash drns. S. W.
40.00 Set charred Cottonwood post
4"x4" 4 ft. long, 2 ft. deep
marked 1/4 Sow N side
with reg. mound and pits
for 1/4 Sec. cor.

South Boundary Tp. 8 S. R 21 E.

80.00 Set charred Cottonwood post 4" x 4" 4 ft. long, 2 ft. dep, Marked 6 notches N. S. E and W. edges, with reg. mound and pits, for cor to Tps. 8 and 9 South R 21 & 22 E.

Land level Bottom

Soil 1st rate

No Timber

Heavy undergrowth

Mg marked on 80.00 chns.

Oct. 13th 1879

East

21.00

32.00

37.50

40.00

43.00

80.00

BOOK-A-162

East Boundary Tp. 8 S. R. 21 E.

From the cor. to Tps. 8 & 9 S.
R. 21 and 22 E. I run
North between Secs. 31 & 36
Var 16°30' E

21.00 Leave undergrowth enter
broken hills

32.00 Top.

37.50 Descend

40.00 Set bolbla stone 13x10x4
8 in. deep marked 1/4 on W
side with stone mound
for 1/4 Sec. cor.

43.00 Enter flat

80.00 Set Sandstone 12x8x6,
8 in. deep, marked 5 notches
on N and 1 on S. edges,
with reg. mound and pits
for cor to Secs. 25. 30.
31 and 36.

Land mostly level

East Boundary Tp. 8 S. R. 21 E of the

Soil 1st rate
No Timber
Heavy undergrowth on 21 chns.
Augmented on 43.00 chns

North bet. Secs. 25 & 30 — 40.00
Var. 16° 30' E
40.00 Set Quartz 16 X 11 X 5
10 in. deep marked 1/4 on
West with stone mound
for 1/4 Sec. cor. — 50.00
80.00 Deposit 1 Qt. of pebbles in — 80.00
reg. mound of earth and
pits and drove reg.
bottonwood stake, marked
2 notches on S and E on N
edge in S. E. pits, for
cor. to Secs. 19. 24. 25 & 30
Land level

BOOK-A-162

of the Salt Lake Meridian

Soil 1st rate

No Timber.

North bet. Secs 19 & 24

Var. 16° 30' E

40.00 Set charred Cottonwood post 4" x 4" 4 ft. long 2 ft. deep marked 1/4 S on W side with seg. mound and pits for 1/4 Sec. cor.

50.00 Wash dries S. W.

80.00 Set charred Cottonwood post 4" x 4" 4 ft. long 2 ft. deep, marked 3 notches on N and S. edges with seg. mound of earth and pits for cor. to Secs. 13, 18, 19 and 24.

Land gently North slope

East Boundary Tp. 8 S. R 21 E

Soil 1st rate

No Timber.

North bet. Secs. 13 & 18

Var 16° 30' E.

40.00 Set charred Cottonwood post 4" x 4' 4 ft. long, 2 ft. deep marked 1/4 S on W side, with reg. mound and pits for 1/4 Sec. cor.

80.00 Set Sandstone 20" x 14" x 4' 15 in. deep marked 2 notches on N and 4 on S. edges with reg. mound of earth and pits for cor. to Secs. 7. 12. 13 and 18

Land gentle N. slope

Soil 1st rate

No Timber

of the Salt Lake Meridian

North bet. Secs. 7 and 12

Var 16° 30' E

40.00 Set charred Cottonwood post 4"x4", 4 ft. long, 2 ft. deep marked 1/4 S on W side, with rg. mound and pits, for 1/4 Sec. cor.

78.50 Enter Bad land hills bear N. E. and S. W.

80.00 Set Sandstone 12x12x10 8 in. deep marked 1 notch on N and 5 on S. edges, with rg. mound and pits for cor. to Secs. 1. 6. 7. & 12

Land mostly level

Soil 1st rate

No Timber

North bet Secs 1 & 6

Var 16° 30' E

2.00

East Boundary Tp. 8 S. R. 21 East

34.00	Gulch drus. S. W.
40.00	Set Sandstone 20 x 14 x 5 15 in. deep marked 1/4 on W side with stone mound for 1/4 Sec. cor.
50.50	Same Gulch drus. S. E.
60.20	" " " S. E.
79.00	Enter flat
80.00	Set Sandstone 24 x 8 x 8 18 in. deep, marked 6 notches on N. S. E. and W edges with stone mound for cor. to Tps 7 and 8 S. R. 21 and 22 E.

Land Mountainous
Soil 3rd rate
No Timber

Augmented on 79. chns.

BOOK-A-162

North Boundary Tp. 8. S. R. 21 E.

From the cor. to Tps. 7 and 8 South R. 21 and 22 E.

I run West on random line bet said Tps. setting temp. corners every 40 and 80 chns. at 5 miles 78 chns and 20 lks. I intersect the Green River Guide Meridian 108 lks. N of cor. to Tps. 7 and 8 S. R 20 & 21 E. The correction for the true line will therefore be 18 lks. S. per mile

From the cor. to Tps. 7 and 8 South R. 20 and 21 E.

South 89° 52' E on true line bet Secs. 6 & 31

Var. 16° 30' E.

38.20 Set charred Cottonwood post

North Boundary Tp 8 S. R 21 E of the

4"x4" 4 ft. long, 2 ft. deep
marked 1/4 S. on N side
with reg. mound and pits
for 1/4 Sec. cor.

59.20 Enter undergrowth

78.20 Set charred Cottonwood post
4"x4" 4 ft. long, 2 ft. deep
marked 5 notches on E
and 1 on W edges, with
reg mound and pits for
cor to Secs. 5. 6. 31 & 32

Land level Bottom
Soil 1st rate
No Timber.

Undergrowth on 19 chns.
Augmented on 19.00 chns.

South 89° 52' E on true line
bet Secs. 5 and 32

24.20
40.00
43.68
50.00
65.00
80.00

Salt Lake Meridian

Var 16° 30' E.

24.20 Right Bank of Green River
Banks, 4 ft. high, slow current,
4 ft. deep, rus. S. W. Set charred
cottonwood post 4"x4" 4 ft. long 2 ft. deep for M. C.
ascertained by triangulation
distance across River to be
19.48 chns.

40.00 falls in River not set

43.68 Left Bank of Green River
Set charred Cottonwood post 4"x4"
4 ft. long 2 ft. deep, marked
M. C. for Meander cor.
to fractional Secs. 5 and 32

50.00 Enter Cottonwood Timber
and undergrowth

65.00 Leave Timber

80.00 In heavy undergrowth
Set Sandstone 14 x 8 x 5
9 in. deep, marked 4 notches
on E and 2 on W. edges

North Boundary Tp. 8 S. R. 21 E

	with reg. mound and pits	
	for cor to Secs. 4, 5, 32 & 33.	
	Land level Bottom	
	Soil 1st rate	
	Timber Cottonwoods along	
	E Bank of river	
	Heavy undergrowth on 60.52	
	Chains	
	Augmented on 60.52 chains	
	South 89° 52' E on true line	
	bet Secs. 4 and 33	
	Var 16° 30' E	
27.00	Enter Gypsum hills leave brush	32.50
40.00	Set Sandstone 12 X 8 X 6, 8 in	40.00
	deep marked 1/4 on N side	
	with reg mound and pits	
	for 1/4 Sec. cor.	
80.00	Set Sandstone 14 X 8 X 5	80.00

21 E of the Salt Lake Meridian

its		9 in. deep, marked with
2 9.33		3 notches on E and W edges
		for cor to Secs. 3, 4, 33 & 34
		Land Mountainous and level
y		Soil 1st and 3rd rates
		No Timber
on) 60.50		Heavy undergrowth on 27.00
		chns.
ains		augmented on 80 chns. —
ue line		South 89°52' E. on true
		line bet Secs. 3 & 34
°30' E		Var 16°30' E
eave brush	32.50	Wash drus S. W.
8 in	40.00	Set Sandstone 12 x 10 x 6,
de		8 in. deep, marked 1/4 on N. side
ts		with reg. mound and pits
		for 1/4 Sec. cor.
5	80.00	Set Sandstone 15 x 10 x 7,

North Boundary Tp. 8 S. R 21 E

10 in deep marked 2 notches on E and 4 on Wedges with reg mound and pits for cor to Secs. 2. 3. 34 & 35

Land Mountainous

Soil 3rd rate

No Timber

Augmented on 80 chns

South 89°52' E. on true line bet. Secs. 2 & 35

Var 16°30' E

40.00 Set Sandstone 16 x 8 x 4, 11 in. deep marked 1/4 on N side with reg mound and pits for 1/4 Sec. cor.

78.00 Enter flat Ravine

80.00 on east side of Ravine Set Sandstone 12 x 7 x 7, 8 in deep, marked 1 notch on E

of the Salt Lake Meridian

and 5 on W edges with reg. mound and pits for cor. to Secs. 1. 2. 35. and 36

Land Mountainous

Soil 3rd rate

No Timber

Augmented on 78.00 chns.

South 89°52' E on true line bet. Secs. 1 & 36

Var 16°30' E.

40.00 Set sandstone 15 x 11 x 4, 10 in. deep marked 1/4 on N side, with stone mound for 1/4 sec cor.

45.00 Wash drns. S. W.

65.00 " " " "

80.00 The cor to Tps. 7 and 8 S. R. 21 and 22 E.

208 BOOK-A-162

North Boundary Tp 8 S. R. 21 E.

Land Broken

Soil 3rd rate

No Timber

Oct. 14th 1879

Note: For General Descript[illegible] see and Subdivision Notes of This Township.

E. Buettner

U. S. Dep. Surveyor

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, Febry 24 1880

The foregoing field notes of the survey of the

Exterior Boundaries of

Township No 8 S *Range No* 21

of the Salt Lake Meridian, Utah Territory,

Executed by E. Buettner

Under joint *contract No* 92

of the 13th *day of* June *1879.*

in the month of Oct *1879*

having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.

Frde. Salomon

U. S. Surveyor General for Utah.

BOOK-A-162
R: 162
2101

Filed 187 .

Examined by

Compared by O. E. S. & F. L. A. G.

FIELD NOTES

OF

THE SURVEY OF THE

Subdivision Lines

of Township No. 8 South, Range No. 21 East

of the Salt Lake Meridian in Utah Territory.

BY

E. Buettner

U. S. DEPUTY SURVEYOR, S

Under ~~his~~ joint Contract No. 92

dated June 18th 1879.

Survey commenced October 15th 1879.

Survey completed October 25th 1879.

Book 162

Extensions and Subdivision Lines

Township 8 S. **R.** 21 East

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

BOOK-A-162

Subd. Tp. 8 S. R. 21 E. Salt Lake Meridian

Survey commenced Oct. 15th 1899

by C. Buttner

Witness cor. 2.50 chns N of

from the cor. to Secs. 35 & 36 on

South Boundary of Tp. North

Det. Secs. 35 & 36

Var 16°30' E.

20.00 Leave flat and heavy Brush,

35.00 W. point of high Bench

42.00 Set Sandstone 10x10x6, 6in

deep, marked 1/4 on W side

with reg. mound of earth

and pile for 1/4 Sec. cor.

57.00 Wash dms. S. W.

65.00 Ascend

70.00 Low Ridge, Cros. E. & W.

72.00 Enter flat.

80.00 Set Cobblestone 16x10x8, 11in.

deep marked 1 notch on S. and E. edges

with stone Mound for cor. to Secs.

25. 26. 35 & 36.

Subs. Tp. 8 S. R. 21 E. of the

Land rolling
Soil 1st & 2nd rate
No Timber.

augmented on 2000 chns.

East on random line bet Secs
25 & 36.
Var 16°30' E.

3.00 Ascend
17.00 Enter flat. brs. N. W. & S. E.
35.00 Wash drns. S. W.
40.00 Set temp 1/4 Sec. cor.
80.04 Int. E. Boundary of Tp. 60
lks. S. of cor. to Secs. 25 & 36
from which S. 89°39' W
on true line bet Secs.
25 & 36
40.02 Set sandstone 15 x 8 x 5,
10 in deep marked 1/4 on
N. side reg. mound of ea

Salt

and
80.04 Th
L

No

12.50 N
40.00 Set
ma
reg
for
80.00 Se
9 in
on
cor.
L

Salt Lake Meridian

and pits for 1/4 Sec. cor.

80.04 The cor to Secs. 25. 26. 35 & 36

Land mostly level

Soil 1st rate

No Timber.

North bet Secs. 25 & 26.

Var 16° 30' E.

12.50 W. point of hill.

40.00 Set Sandstone 13 x 7 x 6, 8 in. deep marked 1/4 on W side, with reg. mound of earth & pits for 1/4 Sec. cor.

80.00 Set Sandstone 14 x 12 x 4. 9 in deep marked 2 notches on S and 1 on E edges. for cor. to Secs. 23. 24. 25 & 26

Land mostly level

Soil 1st rate

219

Subs Tp 8 S. R. 21 E of Ch

No Timber

East on randomline bet
Secs. 24 & 25
Var 16° 30' E

40.00 Set temp 1/4. Sec. cor
80.10 Wash drns S. W
80.20 Int. E. Boundary of Tp. at
cor. to Secs. 24 & 25. from
W on true line bet Secs. 24 &
40.10 Deposit 1/2 Gal. Bois du vac
in reg. mound of earth and
pits for 1/4 Sec. cor.
80.20 The cor. to Secs. 23. 24. 25 &
Land level
Soil 1st rate
No Timber

BOOK-A-162

Salt Lake Meridian

North bet. Secs. 23 & 24

Var 16° 30' E

40.00 Set charred Cottonwood post 4"x4". 4 ft. long 2 ft. deep, marked 1/4 Sec W side with reg. mound of earth and pits for 1/4 Sec. cor.

80.00 Set charred Cottonwood post 4"x4" 4 ft. long 2 ft. deep, marked 3 notches on N and 1 on E edges, with reg. mound of earth & pits for cor to Secs. 13. 14. 23 & 24.

Land level

Soil not rich

No Timber

216

Subd. Tp. 8 S. R. 21 E. of the

Eastern meridian line bet

Secs 13 & 24

Var 16° 30' E.

34.50 Wash drns. South

40.00 Set temp. 1/4 Sec. cor.

45.00 Wash drns. South

64.00 " " "

80.16 Int. E. Boundary of Tp. 21

Rks. S. of cor. to Secs 13 & 24

from which S. 89° 57' W.

on true line bet Secs. 13 & 24

40.08 Deposit 1/2 pt. of pebbles,

in reg. mound of earth & pit

for 1/4 Sec. cor.

80.16 The cor. to Secs. 13. 14. 23 & 24

Land level

Soil 1st rate

No Timber

40.00

80.00

2.00

BOOK-A-162

Salt Lake Meridian

North bet Secs. 13 & 14

Var. 16° 30' E.

40.00 Set Sandstone 12 x 8 x 6.
8 in. deep, marked 1/4 on
W side with reg mound
of earth and pits for 1/4 Sec. Cor.

80.00 Set Sandstone 20 x 4 x 4 16
in deep marked 4 notches
on Land on E edges for
cor to Secs 11, 12, 13 & 14

Land Level

Soil 1st rate

No Timber

Excation random line bet
Secs. 12 & 13.

Var 16° 30' E

2.00 Enter wash dry. N.W.
Leads E.

Subs. Tp. 8 S. R. 21 E. of the

19.00 Leave Dam

40.00 Set temp. 1/4 Sec. cor.

80.00 Intersect E. Boundary of Tp.
at cor. to Secs. 12 & 13.
from which W. on true line
bet Secs. 12 & 13.

40.00 Deposit 12 pt. of pebbles on
reg. mound of earth and pits
for 1/4 Sec. cor.

80.00 The cor to Secs. 11. 12. 13 & 14.
Land level
Soil 1st rate
No Timber

North bet. Secs. 11 & 12

4.00 Wash drains N.W.) Var 16° 30' E

40.00 Set charred cottonwood
post 4" x 4" 4 ft. long
2 ft. deep. marked 1/4 S. on

Wside, with reg. mound of earth and pits, for 1/4 Sec. cor.

4.00 Wash drus. S.W.

8.00 Set Sandstone 16 x 8 x 5, 11 in. deep, marked 5 notches on Sand 1 on E edges, with reg mound of earth and pits for cor. to Secs. 1. 2. 11. & 12

Land gently rolling

Soil 1st rate

No Timber.

East on random line let Secs. 1 & 12

Var 16°30' E

40.00 Set temp. 1/4 Sec. cor.

45.00 Wash drus. S.W. enter Bad lands.

8026 Int. E. Boundary of Tp

Subs. Tp. 8 S. R 21 E. of the

18 lks. S. of cor. to Secs 1 & 12. from which S. 89 W. on true line bet. Secs. 1 & 12

40.13 Set Sandstone 10 x 8 x 7, 6 in deep, marked 1/4 on N. side with reg. mound of earth and pits for 1/4 Sec. cor

80.26 The cor. to Secs. 1, 2. 11 & 12

Land level and broken

Soil 1st rate

No Timber

Augmented on 35.26 chns

North on random line bet Secs. 1 & 2.

Var 16° 30' E

9.00 Wash drns. S. W.

29.00 " " " "

40.00 Set temp 1/4 Sec. cor.

65.00 Ascend Bench

Salt Lake Meridian

80.30 Int. N. Boundary of Tp. 22 lks. W. of cor. to Secs. 1 & 2. from which [illegible] S. 0° 09' W. on town line bet Secs. 1 & 2.

40.30 Set Sandstone 18 x 12 x 4, 12 in. deep, marked 1/4 on W. side with sig. mound of earth and pits for 1/4 Sec. cor.

80.31 The cor. to Secs. 1. 2. 11. & 12. Land mostly level

Soil Sandy

No Timber

October 15th 1879

North bet. Secs. 34 & 35 — Var 16° 31' E.

30.00 Leave Bottom and heavy brush

40.00 Set Sandstone 12 x 12 x 5

Subs. Tp. 8 S. R. 21 E of the

8 in. deep, marked 1/4 on W side
with stone mound for 1/4 Sec. cor.
80.00 Set charred cottonwood post
4"x4" 4 ft long 2 ft. deep
marked with 1 notch on Sand
2 on E. edges with reg.
mound of earth and pits for
cor to Secs. 26. 27. 34 & 35.
Land level Bench and Bottom
Soil 1st rate
No Timber
Augmented on 30. chns.

East on random line bet
Secs. 26 & 35
Var 16° 30' E.
30.00 Enter flat.
40.00 Set temp. 1/4 Sec. cor.
27.00 Wash drus. South
62.00 " " "

Salt Lake Meridian

79.92 Int. N. and S. line, 19 lks
S. of cor. to Secs. 25. 26. 35 & 36
from which
S. 89°52' W on true line
bet Secs. 26. & 35.

39.96 Set sandstone 16 x 10 x 8 in
deep, marked 1/4 on N. side
with sig. mound of earth
and pits for 1/4 sec. cor.

79.92 The cor. to Secs. 26. 27. 34 & 35
Land mostly level
Soil 1st rate
No Timber

North bet. Secs 26 & 27
Var 16°30' E

40.00 Deposit 1 Gal Bois du vac
in sig mound of earth & pits
for 1/4 Sec. cor.

Subs. Tp. 8 S. R. 21 E. of the

80.00 Set charred Cottonwood post 4"x4" 4 ft. long 2 ft. deep, marked 2 notches on S and 2 on E. edges with stg. mound of earth and pits for cor's Secs. 22. 23. 26 & 27

Land level Bench

Soil 1st rate

No Timber

East on random line bet. Secs. 23 & 26

Var 16° 30' E.

34.00 Wash down S. E.

40.00 Set Temp 1/4 Sec. cor.

80.00 Set H a S. line at cor to Secs. 23. 24. 25 & 26. from which West on true line bet Secs. 23 & 26.

40.00 Deposit 1 pint of pebbles

Su

80.00 Th

40.00

80.00

Salt Lake Meridian

in reg. mound of earth & pits
for 1/4 Sec. cor.

80.00 The cor to Secs. 22. 23. 26 & 27
Land level
Soil 1st rate
No Timber

North bet Secs. 22 & 23
Var 16°30' E.

40.00 Set charred Cottonwood
post 4"x4" 4 ft. long,
2 ft. deep marked 1/4 S on
W side with reg mound
of earth and pits for 1/4 Sec. Cor.

80.00 Set charred Cottonwood post
4"x4" 4 ft. long 2 ft. deep
marked 3 notches on S and
2 on E. edges with reg
mound of earth and pits

276

Subs. Tp. 8 S. R 21 E. of the

for Cor. to Secs. 14, 15 22 & 23

Land level

Soil 1st rate

No Timber.

East on random line bet Secs. 14 & 23

Var. 16° 30' E

5.50 Wash drus South

40.00 Set temp. 1/4 Sec. cor

80.00 Int. N. & S. line at. cor to Secs. 13. 14. 23 & 24, from which W. on true line bet Secs 14 & 23.

40.00 Set charred Cottonwood post 4" x 4" 4 ft. long 2 ft deep marked 1/4 S. on N. side with reg. mound of Earth and pits for 1/4 Sec. cor

Salt Lake Meridian

80.00 The cor. to Secs. 14, 15, 22 & 23
Land level
Soil 1st rate
No Timber.

North bet Secs. 14 & 15
Var 16° 30' E.

27.50 Mark drns. S. W.
40.00 Set charred cottonwood post
4" x 4" 4 ft. long. 2 ft. deep
marked 14 S on W side, with
reg mound of earth and pits
for 14 Sec. cor.
80.00 Set charred cottonwood post
4" x 4" 4 ft. long. 2 ft. deep
marked 4 notches on S and
2 on E. edges. with reg
mound of earth and pits
for cor to Secs. 10, 11, 14 & 15

Subs. Tp. 8 S. R. 21 E. of the

Land level
Soil 1st rate
No Timber.

East on random line
bet Secs. 11 & 14.
Var 16°30' E

35.00 Wash drns. S. W.
40.00 Set temp. 1/4 Sec. cor.
60.00 Wash drns. S. W.
80.16 Int N & S line, 36 lks.
N. of cor. to Secs. 11. 12. 13 & 14
from which N. 89°45' W on
true line bet Secs. 11 & 14
40.08 Set Sandstone 14 x 7 x 3, 9
in deep. marked 1/4 on
W side, with reg. mound
of earth and pits for 1/4 Sec. cor.
80.16 The cor. to Secs. 10. 11. 14 & 15

Salt Lake Meridian

Land gently rolling
Soil fair
No Timber.

North bet Secs. 10 & 11
Var 16°30' E

40.00 Set Sandstone 12 X 12 X 4, 8 in. deep, marked 1/4 on West, with reg. mound of earth and pits, for 1/4 Sec. cor

50.00 Wash drns. S. W.

63.00 " " " "

71.50 " " " "

80.00 Set Sandstone 14 X 7 X 6, 9 in. deep marked 3 notches on S and 2 on E edges, with reg mound of earth and pits for cor to Secs. 2 & 3. 10 & 11

Subs. Tp. 8 S. R. 21 E. 5th

Land gently rolling
Soil 1st rate
No Timber

East on random line bet
Secs. 2 & 11.
Var 16° 30' E

25.00 Wash drus S. W.
40.00 Set temp 1/4 Sec. cor.
45.00 Wash drus S. W.
74.00 Head of wash drus S. W.
80.20 Int. N. & S. line at cor
to Secs. 1. 2. 11 & 12. from wh
Wow true line bet Secs.
2 & 11
42.10 Set Sandstone 10 x 8 x 6. 6in
deep marked 1/4 on N. side
with seg. mound of earth
and pits for 1/4 Sec. cor.

Sal

80.20

7.50
36.50
40.00
55.00
80.20

40.20

Salt Lake Meridian

80.20 The cor to Secs. 2.3. 10. & 11
Land gently rolling
Soil 1st rate
No Timber.

North on random line
bet. Secs. 2 & 3
Var 16°30' E

7.50 Wash drus. W.
36.50 " " "
40.00 Set temp. 1/4 Sec. cor.
55.00 Wash drus. W. Enter Gypsum hills
80.20 Int. N. Boundary of Tp.
at cor to Secs. 2 & 3. from which
S. on true line bet Secs.
2 & 3.
40.20 Set Sandstone 18 x 6 x 4,
12 in. deep, with reg.
mound of earth and pits

Subs. Tp. 8 S. R. 21 E. of the

marked 1/4 on W side
for 1/4 Sec. cor.

80.20 The cor. to Secs. 2. 3. 10. 11
Land gently rolling
Soil 1st rate
No Timber
augmented on 25.20 chns Oct. 16th 1879

North bet Secs. 33 & 34
Var 16° 30' E.

28.00 Road brs. E & W
30.00 Leave Bottom and heavy brush
33.50 Wash drns. S. W.
40.00 Set cobble stone 12 x 8 x 6,
8 in. deep marked 1/4 on W side
with Stone mound, for 1/4
Sec. cor.
43.00 Wash drns S. W.
80.00 Set charred cottonwood post
4" x 4" 4 ft. long 2 ft. deep

Salt Lake Meridian

marked 1 notch S and 3
on E edges, with reg.
mound of earth and pits
for cor. to Secs. 27. 28. 33
and 34

Land mostly level
Soil 1st rate
No Timber.

augmented on 30 inches

East on random line bet
Secs. 27 & 34

Var 16° 30' E

40.00 Set temp. 1/4 Sec. cor.
79.80 Int. N. & S. line 17 lks
Sol. cor. to Secs. 26. 27. 34 & 35
from which
S. 89° 52' W on true line
bet Secs. 27 & 34
39.90 Deposit 1 Gal Bois du vac

2 3

Subs. Tp. 8 S. R 21 E. of the

in reg. mound of earth and
pits for 1/4 Sec. cor.

79.80 The cor. to Secs. 27. 28. 33. & 34
Land level
Soil 1st rate
No Timber.

North bet Secs. 27 & 28
Var 16° 30' E.

40.00 Deposit 1 Qt. of pebbles in
reg mound of earth and pits
for 1/4 Sec. cor.

80.00 Set Sandstone 11 X 10 X 5
6 in deep, marked 2 notches
on S and 3 on E edges, with
reg mound of earth and pits
for cor to Secs. 21. 22. 27
and 28
Land level

Salt Lake Meridian

Soil 1st rate
No Timber

East on random line bet.
Secs. 22 & 27
Var 16° 31' E

40.00 Set temp. 1/4 Sec. cor
80.10 Int. N. & S. line 19 lks
S. of cor to Secs. 22. 23. 26 & 27
from which S. 89° 52' W
on true line
bet Secs. 22 & 27.

41.15 Deposit 1/2 Gal Bois du vac
with reg. mound of earth
and pits for 1/4 Sec. cor.

80.10 The cor to Secs. 21. 22. 27 &
28

Land Bench
Soil 1st rate
No Timber

Sales Tp. 8 S. R. 21 E. of the

North bet Secs. 21 & 22

Var 16° 30' E

40.00 Set charred Cottonwood post
4" x 4" 4 ft long 2 ft. deep
marked 1/4 on W. side
for 1/4 Sec. cor. with reg.
mound of earth and pits.

57.00 Wash drus. S. W.

80.00 Set charred Cottonwood post
4" x 4" 4 ft long 2 ft. deep
marked 3 notches on Sand
E edges with reg. mound
of earth and pits, for cor.
to Secs. 15. 16. 21 & 22

Land level Bench
Soil 1st rate
No Timber

East on random line

BOOK-A-162

Salt Lake Meridian

Set Secs. 15 & 22

Var 16°30' E.

5.00 Wash down S.

19.50 " " S. W.

40.00 Set temp. 1/4 Sec. cor.

79.86 Int. N & S. line 36 lks

N. of cor to Secs. 14 & 15.

22 & 23 from which

N 89°45' W on true

line bet. Secs 15 & 22

39.93 Set Sandstone 12X10X5

8 in. deep marked 1/4 on

N side with reg. mound

of earth and pits for

1/4 Sec. cor.

79.86 The cor. to Secs. 15. 16. 21 & 22

Land level

Soil 1st rate

No Timber

Subs. Tp. 8 S. R 21 E. of the

North bet. Secs 15 & 16

Var. 16° 30' E

31.00 Wash drus. S. W.

40.00 Deposit 1 Qt. of pebbles in reg. mound of earth and pits for 1/4 Sec. cor.

80.00 Set charred Cottonwood post 4" x 4". 4 ft. long 2 ft. deep marked & notches on S and 3 on E edges, with reg. mound of earth and pits, for cor. to Secs. 9. 10. 15 & 16

Land gently rolling

Soil 1st rate

No Timber

East on random line bet Secs 10 & 15

Var 16° 30' E

Salt Lake Meridian

40.00	Set temp. 1/4 Sec. cor.
77.50	Wash drus S.W.
80.12	Int. N & S line 15 lks S. of cor to Secs. 10. 11. 14 & 15 from which S 89°54' W on true line bet Secs. 10 & 15
41.06	Set Sandstone 10 x 10 x 5 6 in deep, marked 1/4 on N side, with reg. mound of earth and pits for 1/4 Sec. cor.
80.12	The cor to Secs 9. 10. 15 & 16

Land gently rolling
Soil 1st rate
No Timber

North bet Secs. 9 & 10
Var 16°30'E

Subs. Tp. 8 S. R. 21 E. of the

25.00	Wash drus. S. W.
40.00	Set charred Cottonwood 4"x4" 4 ft. long 2 ft. deep, marked 1/4 S on W. side, with reg mound of earth and pits for 1/4 Sec. cor.
80.00	Set charred Cottonwood post 4"x4" 4 ft. long 2 ft deep marked 5 notches on S and 3 on E edges, with reg mound of earth and pits for cor. to Secs. 3. 4. 9. & 10

Land slightly rolling
Soil 1st rate
No Timber.

East on random line
bet Secs. 3 & 10
Var 16° 30' E

Salt

40.00	
80.22	
40.11	
80.22	
3.00	

Salt Lake Meridian

40.00	Set temp. 1/4 Sec. cor.
80.22	Int. N & S line 38 lks. N of cor. to Secs. 2. 3. 10 & 11 from which N. 89° 44' W on true line bet secs 3 & 10.
40.11	Deposit 1 Qt. of pebbles in reg. mound of earth and pits for 1/4 Sec. cor.
80.22	The cor to Secs. 3. 4. 9 & 10

Land mostly level
Soil 1st rate
No Timber

North on random line bet Secs. 3 & 4
Var 16° 30' E

3.00	Wash drus W.

Subs. Tp. 8 S. R. 21 E. of the

40.00 Set temp 1/4 Sec. cor.
52.00 Wash drus. W. enter Gypsum hills
79.96 Int W. Boundary of Tp.
at cor to Secs. 3 & 4, from
which
South on true line
bet Secs. 3 & 4
39.96 Set charred cottonwood post
4" x 4", 4 ft. long, 2 ft. deep
marked 1/4 Sow W side
with reg mound of earth
and pits for 1/4 Sec. cor.
79.96 The cor to Secs. 3. 4. 9 & 10
Land slightly rolling
Soil 1st rate
No Timber.
augmented on 27.96 chns
Oct. 17th 1879

North bet Secs. 32 & 33
Var 16° 30' E
24.75 Road at foot of Bench bre E & W

Salt Lake Meridian

40.00 in Wash drw W. set
Sandstone 12 x 9 x 5 8 in
deep, marked 1/4 on W side
with reg. mound of earth
and pits for 1/4 Sec. cor.
57.55 Wash drw. W.
80.00 Set charred Cottonwood
post 4" x 4" 4 ft. long. 2 ft.
deep, marked 1 notch on
S and 4 on E edges. with
reg mound of earth and
pits for cor to Secs.
28. 29. 32. & 33.
Land mostly level
Soil 1st & 3rd rate
No Timber

East on random line
set Secs. 28 & 33

Subs. Tp. 8 S. R. 21 E. of the

Var 16° 30' E

40.00 Set temp 1/4 Sec. cor

80.32 Int N & S. line at cor to Secs. 27. 28. 33 & 34 from which

West on true line

bet Secs. 28 & 33

40.16 Deposit 1 Qt. of jebbles in reg. mound of earth and pits, for 1/4 Sec. cor.

80.32 The cor. to Secs. 28. 29. 32 & 33.

Land level

Soil 1st rate

No Timber

North bet Secs. 28 & 29

Var 16° 30' E.

40.00 Deposit 1 Qt of jebbles

Salt Lake Meridian

in reg. mound of earth
and pits for 1/4 Sec. cor.

80.00 Set Cobble stone 12 x 10 x 6
8 in. deep, marked 2 notches
on S and 4 on E edges,
with stone mound for
cor to Secs. 20. 21. 28 & 29

Land level

Soil 1st rate

No Timber

East on random line
bet Secs. 21 & 28

Var 16° 30' E

2.20 Hollow drus N. W.
5.00 lks into flat.

40.00 Set temp. 1/4 Sec. cor.

80.12 Int. N & S line 1 & lks
N. of cor. to Secs. 21. 22

246

Subs. Tp. 8. S. R. 21. E. of the

27 & 28 from which
N 89° 54' W on true line
bet Secs. 21 & 28

40.06 Deposit 1 Gal Bois du vac
in reg. mound of earth
and pits for 1/4 Sec. cor.

80.12 The cor. to Secs. 20. 21. 28 & 29
Land level
Soil 1st rate
No Timber

North bet. Secs. 20 & 21
Var 16° 30' E

2.00 mouth of gulch
40.00 Deposit 1 Qt of pebbles in
reg. mound of earth and pits
for 1/4 Sec. cor.
46.00 Wash draws West
80.00 Set charred cottonwood post
4" x 4" 4 ft. long 2 ft
deep, marked 3 notches

Salt Lake Meridian

on S and 4 on E, edges
with reg. mound of earth
and pits for cor. to Secs.
16, 17, 20 & 21
Land level
Soil 2nd rate
No Timber

East on random line
bet Secs. 16 & 21
Var 16° 30' E
4.00 Set temp. 1/4 Sec. cor.
79.92 Int. N & S. line at cor
to Secs. 15, 16, 21 & 22.
from which
West on true line
bet Secs. 16 & 21
39.96 Deposit 1 Qt of pebbles
in reg. mound of earth

Subs. Tp. 8 S. R. 21 E. of the

and pits for 1/4 Sec. cor.

79.92 The cor. to Secs. 16. 17. 20 and 21.

Land level

Soil 1st rate

No Timber

North bet Secs. 16 & 17

Var 16° 30' E

13.50 Wash drus. W

40.00 Deposit 1 Qt. of pebbles in reg. mound of earth and pits for 1/4 Sec. cor

80.00 Set charred Cottonwood post 4" x 4" 4 ft. long 2 ft. deep. marked 4 notches on Sand E edges, with reg. mound of earth and pits for cor. to Secs.

Salt Lake Meridian

8. 9. 16. & 17

Land level

Soil 1st rate

No timber

East on random line

bet Secs. 9 & 16.

Var 16°30' E

4.00 Set temp. 1/4 Sec. cor.

80.08 Int. N & S line at cor

to Secs. 9, 10, 15 & 16

from which

West on true line bet

Secs. 9 & 16

40.04 Set sandstone 12 x 8 x 6

8 in. deep, marked 1/4 on

N side, with reg. mound

of earth and pits, for

1/4 Sec. cor.

Subs. Tp. 8 S. R. 21 E. of the

80.08 The cor. to Secs. 8. 9. 16 &
17

Land level
Soil 1st rate
No Timber

North bet Secs. 8 & 9
Var 16° 30' E.

19.20 Wash drns. S. W.

40.00 Deposit 1 Qt. of pebbles
in reg. mound of earth
and pits for 1/4 Sec. cor.

80.00 Set charred Cottonwood
post 4" x 4" 4 ft. long
2 ft. deep, marked 1/4
notches on Qand & on E
Edges with reg. mound
of earth and pits for cor
to Secs. 4. 5. 8 & 9

BOO

Subs.

40.00

80.12

40.06

80.12

BOOK-A-162

Salt Lake Meridian

Land gently rolling
Soil 1st rate
No Timber

East on random line
bet. Secs. 4 & 9
Var 16° 30' E

40.00 Set temp 1/4 Sec. cor.
80.12 Int. N. & S. line 23 lks
S. of cor to Secs. 3. 4. 9 & 10
from which
S. 89° 55' W on true line
bet. Secs. 4 & 9
40.06 Set Sandstone 18 x 6 x 4,
12 in. deep marked 1/4
on N side, with neg.
mound of earth and pits
for 1/4 Sec. cor
80.12 The cor to Secs. 4. 5. 8. & 9

Suls. Tp. 8 S. R. 21 E. of the

Land level
Soil 1st rate
No Timber

North on random line
bet Secs. 4 & 5
Var 16°30' E

4.50 Wash drus S. W.
40.00 Set temp. 1/4 Sec. cor.
44.25 Wash drus. W
80.16 Int. N. Boundary of
Tp. 24 lks. W. of cor. to
Secs. 4 & 5 from which
S. 0°10' W. on true line
bet Secs. 4 & 5
40.16 Deposit 1 Qt. of pebbles
in reg. mound of earth
and pits, for 1/4 Sec. cor.
80.16 The cor. to Secs. 4. 5. 8 & 9

Salt

1.00
39.25
40.00

BOOK-A-162

Salt Lake Meridian

Land level
Soil 1st rate
No Timber
October 18th 1879

North bet. Secs. 31 & 32
Var 16° 30' E.
From the Witness cor. 100
lks. W. of cor. point to
Secs. 31 & 32, I offset
North 2.64 chs.
East 1.00 ch. to
1.00 on line in place. North
bank of White River
125 lks wide, 2 ft. deep
mo. South.
39.25 Road at foot of Bluff
bns. E & W. lear heavy
brush.
40.00 Deposit small sandstone

Subs. Tp. 8 S. R. 21 E. of the

6 x 4 x 3 in. marked with a cross (+) in reg. mound of earth and pits for 1/4 sec. cor.

80.00 Set Sandstone 12 x 7 x 7, 8 in. deep, marked 1 notch on S and 5 on E edges, with reg. mound of earth and pits for cor to Secs. 27. 30. 31 & 32

Land level

Soil 1st rate

No Timber

augmented on 39.55. chns.

East on random line bet Secs. 29 & 32

Var 16° 30' E

40.00 Set temp. 1/4 Sec. cor

Salt L

80.00 I

to

J

M

S

40.00 D

in

an

80.00 The

31.

W

C

40.00 L

50.10 R

Salt Lake Meridian

80.00 Int. N & S. line at cor.
to Secs. 28. 29. 32 & 33
From which
West on true line bet
Secs. 29 & 32
40.00 Deposit 1 bal Bois du vac
in reg. mound of earth
and pits, for 1/4 Sec. cor
80.00 The cor. to Secs. 29. 30.
31. & 32
Land level
Soil, sandy
No Timber

West on random line
bet Secs. 30 & 31
Var 16° 30' E
40.00 Set temp 1/4 Sec. cor
50.10 Road bes. N & S.

Subs. Tp. 8 S. R. 21 E of the

78.70 Int. W. Boundary of Tp.
at cor. to Secs. 30 & 31
from which
East on true line
bet. Secs. 30 & 31
38.70 Set Sand stone 14 x 8 x 5
9 in. deep, marked 1/4
on N. side with reg.
mound and pits, for
1/4 Sec. cor.
78.70 The cor to Secs. 29. 31.
31 & 32

Land gently rolling
Soil 1st rate
No Timber

North bet. Secs. 29 & 30
Var 16° 30' E
40.00 Deposit 1 Gal Bois du rde

Salt

in

50.75 Fr
80.00 Se

12

2

E

m

co

3

E

b

14.00 R
40.00 S
60.00 E

Salt Lake Meridian

in reg. mound and pits
for 1/4 Sec. cor.
50.75 Road bro. N.E. & West.
90.00 Set Sandstone 18 x 13 x 3
12 in deep, marked
2 notches on Sandstone
E edges, with reg.
mound and pits for
cor. to Secs. 19. 20. 29
30.
Land level
Soil 1st rate
No Timber

East on random line
bet. Secs. 20, 29
Var 16° 30' E
14.00 Road bro. North & South
40.00 Set temp. 1/4 Sec. cor.
60.00 Enter N. slope of higher

Subdivs. T. 8 S. R. 21 E. of the

Bench

80.30 Intp N & S. line 16 lks.
E. of cor. to Secs. 20. 21.
28 & 29. from which
S. 89° 59' W. on true line
bet. Secs. 20 & 29

40.15 Deposit small Cobble
stone 4 x 4 x 4 in. marked
with cross (+) in reg.
mound of ~~earth~~ and pits
for 1/4 Sec. cor.

80.30 The cor. to Secs. 19. 20.
29 & 30

Land mostly level
Soil 1st rate
No Timber

West on random line
bet Secs. 19 & 30

Salt Lake Meridian

Var 16° 30' E.

32.50 Enter Gypsium hills bear N & S.

40.00 Set temp. 1/4 Sec. cor.

58.50 Gulch drns. North, ~~Ascend~~

78.56 Int. W. Boundary of Tp. at cor. to Secs 19 & 30 from which ...

East on true line bet Secs. 19 & 30

38.56 Set Sandstone 24 X 8 X 4 17 in. deep, marked 1/4 on N. side, with reg. mound and pits for 1/4 Sec. cor.

78.56 The cor. to Secs. 19. 20. 29 & 30.

Land W. 1/2 broken Gypsium hills. E 1/2 flat

Soil 2nd and 1st rate

260

Subs. Tp. & S. R. 21 E of the

No Timber.

Augmented on 40.06 chns

North bet. Secs. 19 & 20

Var 16° 30' E.

40.00 Deposit 1 At. of pebbles in reg. mound and pits for 1/4 Sec. cor.

63.50 Wash drus. S. W.

72.20 Road bro E. & W.

80.00 Set Sandstone 13 x 9 x 6 9 in. deep, marked 3 Notches on Sand 5 on E edges with reg. mound and pits for cor. to Secs. 17. 18. 19 & 20.

Land level

Soil 1st rate

Salt Lake Meridian

No Timber

	East on random line bet. Secs. 17 & 20
	Var 16° 30' E.
23.00	Wash drus. S. W.
31.00	Same " " N. W.
40.00	Set temp. 1/4 Sec. cor.
71.00	Same Wash drus S. W.
80.24	Int. N. and S. line at cor. to Secs. 16. 17. 20 & 21, from which West on true line bet Secs. 17 & 20
40.12	Set Sandstone 16 x 13 x 3 11 in. deep, marked 1/4 on N. side with reg. mound and pits for 1/4 Sec. cor.
80.24	The cor to Secs. 17. 18. 19

Subs. Tp. 8 S. R. 21 E. of the

and 20

Land level Bench
Soil 1st rate
No Timber

West on random line
bet. Secs. 18 & 19
Var 16° 30'

39.75 Road bears N.W. & S.E.
40.00 Set temp. 1/4 Sec. cor.
78.75 Int. W. Boundary of Tp.
10 lks. N. of cor. to Secs.
18 & 19. From which
N 89° 56 E on true line
bet. Secs. 18 & 19
38.75 Set Sandstone 10 x 10 x 6
6 in. deep, marked 1/4 on
N. side, with reg. mound
of earth and pits for
1/4 Sec. cor.

Salt Lake Meridian

78.75 The cor. to Secs. 17. 18. 19 and 20.

Land level

Soil 1st rate

No timber

North bet Secs. 17 & 18

Var 16° 30' E.

40.00 Set Sandstone 12 x 10 x 4 8 in deep, marked 1/4 on W. side with reg. mound and pits for 1/4 Sec. cor

60.60 Wash drus S. W.

80.00 Set Sandstone 10 x 9 x 6 6 in. deep marked 4 notches on Sandstone edges, with reg. mound and pits, for cor to Secs

Subs. Tp. 8 S. R. 21 E. of the

7. 8. 17 & 18.

Land level

Soil 1st rate

No Timber

East on random line

bet Secs. 8 & 17

Var 16°30' E

41.00 Set temp. 1/4 Sec. cor

41.50 Wash drus S. W.

79.90 Int. N & S. line

22 lks. N. of cor. to Secs.

8. 9. 16. & 17 from which

N 89°51' W. on true

line bet Secs. 8 & 17

39.95 Set Sandstone 9 x 8 x 8

6 in. deep, marked 1/4 on

N. side with reg. mound

of earth and pits

Salt Lake Meridian

For 1/4 Sec. cor.

79.90 The cor. to Secs. 7.8.17 & 18

Land level

Soil 1st rate.

No Timber

October 20th 1879

West on random line bet. Secs. 7 & 18

Var 16°30' E.

40.00 Set temp 1/4 Sec. cor

78.70 Pnt. W. Boundary of Tp. 42 lks S. of cor. to Secs 7 & 18. from which S. 89°42' E on true line bet. Secs. 7 & 18

38.70 Deposit 1 Qt of pebbles in reg. mound of earth and pits for 1/4 Sec. cor

78.70 The cor. to Secs. 7.8.17 & 18

Subs. Tp. 8 S. R. 21 E. of the

Land level
Soil 1st rate
No Timber

North bet. Secs. 7 & 8
Var 16° 30' E.

27.40 Wash down. S. W.

40.00 Deposit 1 Qt. of Pebbles in reg. mound of earth and pits, for 1/4 Sec. cor.

80.00 Set charred Cottonwood post 4" x 4" 4 ft. long 2 ft. deep, marked 5 notches on S. and E. edges with reg. mound and pits for cor to Secs 5. 6. 7 & 8.

Land level
Soil 1st rate

Subs

No

Eas
bet

40.00 Set

75.25 W

80.24 Ins
N.
fro
on
5 q

40.12 Dep
in
and

80.24 The

Salt Lake Meridian

No Timber

East on random line
bet Secs. 5 & 8
Var 16° 30' E

40.00 Set temp 1/4 Sec. cor.
75.25 Wash drus. S. W.
80.24 Int. N & S. line 43 lks
N. of cor. to Secs. 4. 5. 8 & 9.
from which N. 89° 42' W
on true line bet Secs
5 & 8.
40.12 Deposit 1 Qt. of pebbles
in reg. mound of earth
and pits for 1/4 Sec. cor.
80.24 The cor to Secs. 5. 6. 7 & 8

Land level
Soil 1st rate
No Timber

Subd. Tp. 8 S. R. 21 E. S.L.M.

West on random line
bet Secs. 6 & 7
Var 16°30'E

40.00 Set temp 1/4 Sec. cor
45.00 Thomas Bingham's cabin bears
South 10 lks. distant.
78.50 Inst. W. Boundary of Tp.
19 lks N of cor. to Secs.
6 & 7 from which
N. 89° 52' E. on true
line bet. Secs. 6 & 7
38.50 Set charred cottonwood
post 4"x4" 4 ft. long
2 ft. deep, marked 1/4
on N. side with reg.
mound of earth and
pits, for 1/4 Sec. cor.
78.50 The cor. to Secs. 5. 6. 7.
and 8.
Land level

Salt Lake Meridian

Soil 1st rate
Timber a few cottonwoods
on West end.

North on random line
bet Secs. 5 & 6
Var 16°30' E.

40.00 Set temp 1/4 Sec. cor
40.00 On left Bank of Green
River, Banks 4 ft. high.
Slow current.
Set Boulder 12 x 9 x 5
marked M. C. with
stone mound for
Meander cor. to
fractional Secs. 5 & 6.
54.00 South side of small Island
bns. West 25 chns. and East
6. chns.

270

Subs. Tp. 8 S. R. 21 E. of the

58.25 North side of Island

62.00 Right Bank of Green

River 4 ft. deep rus. West.

Marked Cottonwood stump

5 in. diameter 2 ft. high

M. C. for Meander Cor.

to fractional Secs. 5 & 6.

80.00 Int. N. Boundary of Tp.

at cor to Secs. 5 & 6

from which

South on true line

bet. Secs. 5 & 6.

40.00 Set Sandstone 12 x 10 x 6

8 in. deep marked 1/4 on

W. side with reg. mouns

and pits, for 1/4 Sec. cor.

80.00 The cor. to Secs. 5. 6. 7 & 8

Land level Bottom

Soil 1st rate

Timber Cottonwoods

Salt Lake Meridian

along River.

October 21st 1879

(Note. See Meanders after General Description [illegible] —)

General Description

This Tp. embraces Bottoms along Green River, and adjacent Benches, also a small portion of the White River Bottoms. With the exception of a portion of Sections 19 and 30, the whole Tp. can be irrigated from either Green or White River. Settlements have been made along Green and White River by parties

who claim portions of the land in the South and West parts of this Tp.

E. Buettner
Dep. Sur.

BOOK-A-162

Meanders of Green River
in Tp. 8 S. R. 21 E.
Meanders of right Bank
beginning at the Meander Cor
38.50 chns. N. of cor. to Secs.
1. 6. 7 and 12 on W. Boundary
of Tp 9 meander up stream
as follows: in Sec. 6.

N. 79°30' E	24.00 chns
S. 88°00' E	36.00 "
N. 87°00' E	19.00 "
In Sec. 5	79.00
N. 82°30' E	17.00 chns
N. 27°00' E	17.00 "
	33.00

Meanders of Left Bank of
Green River
Beginning at the Meander Cor
to fractional Secs. 5 and 32

274

Heavy undergrowth and Augmented on 3 Miles 14.80 chs.

October 21st 1879. E. Buettner U. S. Dep. Sur.

on North Boundary of Tp.
I meander down stream
as follows.

In Sec. 5

S. 30° 30' W.	28° 00 chs
S. 54° 30' W	13.00 "
S. 69° 00' W	20.30 "
	61.00

Thence in Sec. 6

S. 69° 30' W	6.00 chs
S. 76° 00' W	3.00 "
N. 81° 45' W	8.00 "
N. 54° 30' W	4.50 "
N. 77° 00' W	15.50 "
S. 83° 30' W	21.50 "
S 86° 00' W	22.00 "
	100.50

to Meander Cor on West
Boundary of Tp.

Land on both sides of River
first class Bottom
Soil 1st rate. Timber scattering Cotton

BOOK-A-162

235

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, Feby 24 1880

The foregoing field notes of the survey of the

Subdivisions of

Township No 8 S, *Range No* 21 E,

of the Salt Lake Meridian, Utah Territory,

Executed by E. Buttner

Under Joint *contract No* 92

of the 13 *day of* July 1879

in the month of Oct. 1879,

having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.

Jno. Salisbury

U. S. Surveyor General for Utah.

BOOK-A-162

R: 1880. 162 276

Filed January 29th 1880.

Examined by P. C. Bailey

Compared by O. E. S. F. L. A. G.

FIELD NOTES

OF

THE SURVEY OF THE

Exteriors

of Township No. 8 South, Range No. 20 East

of the Salt Lake Meridian in Utah Territory.

BY

A. D. Ferron

U. S. DEPUTY SURVEYOR,

Under ~~his~~ point Contract No. 92

dated June 13th 1879.

Survey commenced Oct 15 1879.

Survey completed " " 1879.

BOOK-A-162

South Boundary Tp. 8 S. R 20 E.

Survey commenced Oct 15/79
by A. D. Fenn

Note: The S. W. cor. of this Tp. falls in the Uintah Indian Reserve. Therefore from the cor. to Tps. 8 and 9 S. R 20 and 21 E. on the Green River Guide Meridian I run Westerly true line bet Secs. 1 and 36

Var. 16° 30' E.

4.00 White River 150 lks. wide 3 ft. deep runs N. W.

10.00 White River 150 lks. wide 3 ft. deep runs S. E.

15.00 White River 150 lks. wide 3 ft. deep runs N. W.

40.00 Set charred Cottonwood Post 4" x 4" 4 ft. long

South Boundary Op. 8th Rec'd

2 ft. deep, marked 1/4 S on N side, with reg. mound and pits, for 1/4 Sec. cor.

46.00 Touch South side of Bend of White River

80.00 Set charred Cottonwood stake 4"x4" 4 ft. long 2 ft. deep, marked 1 notch on E and 5 on Wedges with reg. mound and pits, for cor. to Secs. 1. 2. 35 and 36.

Land level

Soil 1st rate

Timber a few Cottonwoods along river heavy under-growth

Augmented on 80.00 chain

S. L. Meridian

West on true line bet
Secs. 2 and 35
Var 16° 30' E

4.00 Set charred Cottonwood
post 4" x 4" 4 ft. long
2 ft. deep, marked 1/4 S
on N side with reg.
mound of earth and pits
for 1/4 Sec. cor.

8.00 Set charred Cottonwood
post 4" x 4" 4 ft. long
2 ft. deep marked
2 notches on E and 4 on
W. edges with reg.
mound and pits for
cor to Secs. 2. 3. 34 and
35

Land level
Soil 1st rate
No Timber. Heavy undergrowth

South Boundary Tp. S. Rec. E.

Augmented on 80.00 chns.—

West on true line
bet secs. 3 and 34
Var 16°30' E.

41.00 Set charred Cottonwood post 4" x 4" 4 ft. long. 2 ft. deep marked 1/4 S on N. side, with reg mound and pits for 1/4 sec. cor.

78.30 White River 2.20 chns. wide 4 ft. deep runs South

80.00 falls in River can not be set, therefore at a point 50 lks. W of true cor point set charred Cotton wood post 4" x 4" 4 ft

long, 2 ft. deep marked
3 notches on E and W
Edges and W. C. for
Witness Cor. to Secs.
3, 4, 33 and 34
Land level
Soil 1st rate
No Timber. Heavy
undergrowth
Augmented on 80.00 chns.

West on true line bet.
Secs. 4 and 33.
Var 16°30' E.

0.50 Witness cor.
40.00 Set charred Cottonwood
post 4" x 4" 4 ft. long
2 ft. deep, marked
1/4 S on N. side, with

South Boundary T. 18 S. R. 20 E.

reg. mound and pits
for 1/4 Sec. cor.

74.00 Left Bank of Green
River set charred
Cottonwood post 4" X 4"
4 ft. long. 2 ft. deep
marked M. C. for
Meander Cor. to
fractional Secs. 4 and 33

80.00 Falls in River cannot
be set. Therefore at
a point 86. lks. West
of true cor. point on
East shore of small
Island in Green River
Set charred Cottonwood
post 4" X 4" 4 ft. long
2 ft. deep, marked
4 notches on E and D
on W edges, and W. C.

with reg. mound and pits for Witness Cor. to Secs. 4. 5. 32 and 33.
Land level
Soil 1st rate
Timber a few Cotton = woods on River.
Heavy under growth
Augmented on 80.00 chns. —

Note: Green River here forming E. Boundary of Reserve. I abandon line.

North Boundary
Tp. 8 S. R 20 East.
Note: The N.W. cor. of Tp. falls in Reserve, therefore from the cor to Tps. 7 and 8 S. R 20 and

North Boundary Tp. 8 S. R 20 E

21 E. I run
West on true line bet
Secs. 1 and 36
Var 16° 30' E

40.00 Set charred Cottonwood post
4" x 4" 4 ft. long 2 ft. deep,
marked 1/4 S on N side
with reg. mound and pits
for 1/4 Sec. cor.

50.00 Leave Bottom ascend

67.00 Enter Bench

80.00 Set charred Cottonwood post
4" x 4" 4 ft. long. 2 ft.
deep marked 1 notch on
E and 5 on W. edges with
reg mound and pits, for
cor to Secs. 1. 2. 35 & 36
Land mostly level
Soil 1st rate
No Timber

Salt Lake Meridian

West on true line bet.
Secs. 2 and 35
Var 16° 30' E

38.50 Road bears N.W. and S.E.
40.00 Deposit 1 Qt of pebbles
in reg. mound of earth and
pits for 1/4 Sec. cor.
80.00 Set charred cottonwood
post 4" x 4" 4 ft. long
2 ft. deep, marked 2
notches on E and 4 on
W. edges, with reg. mound
and pits for cor to Secs.
2. 3. 34 and 35.
Land level Bench
Soil 1st rate
No Timber.

West on true line bet
Secs 3 and 34

North Boundary Tp 8 S. R 20 E

Var 16° 30' E.

40.00 Set charred Cottonwood post 4"x4" 4 ft. long. 2 ft. deep, marked 1/4 S on N side with reg mound and pits for 1/4 Sec. cor.

80.00 Set charred Cottonwood post 4"x4" 4 ft. long. 2 ft. deep, marked 3 notches on E and W edges with reg. mound and pits for cor to Secs. 3. 4. 33 and 34

Land level

Soil 1st rate

No Timber

West on true line bet Secs. 4 and 33

Var 16° 30' E

Sal

40.00 D

in

an

46.00 K

80.00 S

p

2

4

35.00

Salt Lake Meridian

40.00 Deposit 1 Gal Bois du vac in reg. mound of earth and pits for 1/4 Sec. cor.

46.00 Road bra. N. W. and S. E.

80.00 Set charred cottonwood post 4" X 4", 4 ft. long 2 ft. deep, marked 4 notches on E and 2 on W. edges with reg. mound and pits for cor to Secs. 4. 5. 32 & 33.

Land level
Soil 1st rate
No Timber

West on true line bet Secs. 5 and 32
Var 16° 30' E.

35.00 Wash drus South

North Boundary Tp. 8 S. R. 20 E.

40.00 Set charred Cottonwood post 4"x4", 4 ft. long 2 ft. deep marked 1/4 Sow N side, with reg. mound and pits for 1/4 Sec. cor.

50.00 Set charred Cottonwood post 4"x4". 4 ft. long 2 ft deep marked 5 on E. and 1 on W. Edges, with reg. mound and pits for cor. to Secs. 5. 6. 31 and 32.

Land level

Soil 1st rate

No Timber

Westow true line
Bet Secs. 6 and 31
Var 16° 30' E

3.70 Int. N. Boundary of
Uintah Indian Reserve
at a point S. 25° E. from
the 4th mile cor. 13.90.
chns. distant, where I
set a charred Cottonwood
post 4" x 4" 4 ft. long
2 ft. deep, marked C. C.
for closing cor. to fracti-
onal Secs. 6 and 31.
Land level
Soil 1st rate
No Timber
Oct 15. 1819
Note: For General
Description see end
of Subdivisions of this Tp.
A. D. Fenn. dep. Mr

BOOK-A-162

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, Febry 24 1880

The foregoing field notes of the survey of the

Exterior Boundaries of

Township No 8 S. *Range No* 20 E.

of the Salt Lake Meridian, Utah Territory,

Executed by A. D. Ferne

Under print *contract No* 92

of the 13 *day of* June *1879,*

in the month of Oct. *1879*

having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.

Frd. Salomon

U. S. Surveyor General for Utah.

BOOK-A-162

R: 1880 (162) copied 291

Filed Jany 29th 1880

Examined by T. C. Bailey

Compared by T. C. Bailey

FIELD NOTES

OF

THE SURVEY OF THE

Subdivisions

of Township No. 8 S., Range No. 20 E

of the Salt Lake Meridian in Utah Territory.

BY

Ferron & Buettner

U. S. DEPUTY SURVEYOR,

Under Joint Contract No. 92

dated June 13 1879.

Survey commenced Oct 16th 1879.

Survey completed Nov. 19 1879

Book 162

Extensions and Subdivision Lines

Township 8 S. R. 20 E.

289 287 286 285 285 284

6 342 5 341 4 331 3 318 2 305 1

339 338 338 317 303

7 8 337 9 329 10 316 11 302 12

336 334 328 314 301

18 17 335 16 327 15 313 14 300 13

327 325 312 298

19 20 21 324 22 311 23 297 24

323 322 310 295

30 29 28 323 27 309 26 294 25

320 308 293

31 32 333 33 319 34 307 35 292 36

281 280 279 277

Subs. Tp. 8 S. R. 20 East.

Survey commenced Oct 16. 79
By A. D. Finn
From the cor. to Secs. 35 and 36.
North bet. Secs. 35 and 36
Var 16° 30' E

27.40 South Bank of White River 150 lks. wide 6 ft. deep rns. West.
37.00 Road. Crs. N. W. and S. E.
39.00 Enter Bench. Leave Brush
40.00 Set charred Cottonwood, post 4" x 4", 4 ft. long. 2 ft. deep marked 1/4 S on W side with reg. mound and pits for 1/4 Sec. cor.
80.00 Set Sandstone 24 x 8 x 5, 18 in. deep marked 1 notch on S and E edges with stone mound for Corner to Secs ——

Subdivisions

25. 26. 35 and 36
Land mostly level
Soil 1st rate
No Timber
Heavy undergrowth on 39 chns.
Augmented on 39.00 chns.

East on random line
let Secs. 25 and 36.
Var 16° 30' E.

3.50 Wash drus. South
18.50 " " "
25.00 " " "
33.00 Top of lone low Butte
40.00 Set Sandstone 18 X 6 X 6,
12 in. deep, marked 1/4
on N side with reg. mom
and pits for 1/4 Sec. cor.
80.00 Int E Boundary of Tp

T. 8 S. R 20 E.

22 Ch. N. of cor. to Secs.
25 and 36, from which
N. 89° 57' W. on true
line bet. Secs. 25 and 36.
40.00 set Sand stone 18 x 6 x 6
12 in. deep, marked 1/4 on
N side, with reg. mound
and pits for 1/4 Sec. cor.
80.00 N. cor. to Secs. 25. 26. 35
and 36.
Land gently rolling
Soil 1st rate
No timber.

North bet. Secs. 25 & 26
Var 16° 30' E.
25.00 Enter Gypsum hills
40.00 Set charred cottonwood
post 4" x 4" 4 ft. long 2 ft.

Subdivisions

deep, marked 1/4 S on
on W. side, with reg.
mound and pits for
1/4 Sec. cor.

80.00 Set charred Cottonwood
post 4" x 4" 4 ft long
2 ft. deep marked 2
notches on S and 1 on E
Edges, with reg. mound
and pits for cor. to
Secs. 23. 24. 25 & 26
Land broken and level
Soil mostly Gypsum
No Timber.
Augmented on 55.00 chns.

East on random line
bet Secs. 24 and 25
Var 16° 30' E

Tp 8 S. R 20 E.

18.00 Gulch drus. North
35.00 " " N. W.
40.00 Set temp. 1/4 Sec. cor.
80.20 Int E. Boundary of Tp.
20 lks. S. of cor. to Secs.
24 and 25 from which
S. 89° 51' W. on true
line bet. Secs. 24 and 25
40.10 Marked Stationary sand-
stone 2 x 2 x 4 ft. above
ground 1/4 on N. side
with stone mound for
1/4 Sec. cor.
80.20 The cor. to Secs. 23. 24. 25 &
26.

Land broken
Soil 2nd rate
No Timber

Augmented on 80.20 chns.

Subdivisions Tp 8 S. Rev

North bet Secs. 23 & 24
Var 16° 30' E

38.50 Ridge Crs. N. E. & S. W.

40.00 Set Boulder 12 x 10 x 6, 8 in deep marked 1/4 on W. side with reg. mound and pits for 1/4 Sec. cor.

60.00 Leave broken hills

64.60 Road Crs. N. E. and S. W.

78.50 Left Bank of Green River 4 ft. deep rus. S. W.
Set charred Cottonwood post 4" x 4" 4 ft. long 2 ft. deep marked M. C. ~~forth~~ reg mound and pits, for Meander cor. to fractional Secs. 23 and 24.

80.00 Falls in River not set.
Land broken hills and

Sal

0.50

Salt Lake Meridian

Bottom
Soil 3rd and 1st rate
No Timber
augmented on 60.00 chns.

East on random line
bet. Secs. 13 and 24
Var 16°30' E.
From the meander cor.
1.58 chns. South of cor point
to Secs. 13. 14. 23. and 24
I offset East .50 lks
North 1.50 chns. to
0.50 Right Bank of Green
River set charred
cottonwood post 4" x 4"
4 ft. long 2 ft. deep
marked M.C. with reg
mound and pits for

Subdivisions: Tp 8 S. R 20 E.

Meander cor. to fractional
Secs. 13 and 24.
40.00 Set temp 1/4 Sec. cor.
80.00 Int. E. Boundary of Tp
at cor. to Secs. 13 and 24
from which West on
true line bet Secs 13 & 24
40.00 Set Sandstone 12 x 12 x 6
8 in. deep, marked 1/4
on N. side with reg.
mound and pits
for 1/4 Sec. cor.
80.00 The cor. point to Secs.
13. 14. 23 and 24.
Land level
Soil 1st rate
No Timber.

Salt Lake Meridian

North bet. Secs. 13 & 14.
Var 16°30' E.
From the Meander Cor.
to fractional Secs. 13 & 24
" 50 lks. E. of cor. point
to Secs. 13, 14, 23 and 24
I offset on account of
River East 19.50 chns.
North 80.00 chns.
West 13.60 " to
a point 6.40 chns E. of
Stone where I set a charred
Cottonwood post 4" x 4"
4 ft. long 2 ft. deep,
Mounted M. C. with reg.
recorded and pits for
Meander cor. to fractional
Secs. 12 and 13.
on Left Bank of Green
River

Subs Tp 8 S. R 20 E

Note: The 1/4 Secs. falling in Green River is not set.
Land East of line level
Soil 1st rate
No Timber.
Heavy undergrowth
Avg. rated on 70.00 chns.

East on random line
bet Secs. 12 and 13
Var 16° 30' E.
From Meander cor. to
fractional Secs. 12 & 13
~~5.13~~ 6.40 chns. E. of cor point
to Secs. 11. 12. 13 and 14.
~~5.13~~ 6.40 Said Meander cor.
45.00 1st temp. 1/4 Sec. cor.
79.88 Int. E. Boundary of Tp.
34 lks. S. of cor. to Secs 12

S. L. Meridian

and 13. from which
S. 89°45' W. on true line
bet. Sec.s 12 & 13.

39.94 Set chained Cottonwood post
4x4 in, 4 ft long, 2 ft deep, marked
1/4 S. on N. side, with reg. mound
and pits for 1/4 Sec. Cor.

79.88 The Cor point to Sec.s 11.12.13 & 14
Land level, soil rehate
No timber

North bet. Sec.s 11 & 12
Var 16° 30' E.

From a point 10 chs E. of Cor point
to Sec.s 11.12.13 & 14 (On account of
River) Chain North (on offset)
39.50 chs then West. 10 chs

39.50 Left bank of Green River set
Chained Cottonwood post 4x4 in
4 ft long, 2 ft deep, marked M. C.
with reg. mound & pits for Meander Cor.

Subs Tp 8 S. R 20 E.

40.00 Set chained cottonwood post 4x4 in 4 ft long 2 ft deep Marked 1/4 S. on W. side with reg. mound and pits for 1/4 sec cor.

76.50 Left Bank of Gunn River set chained cottonwood post 4x4 in 4 ft long, 2 ft deep, marked M.C. ~~for~~ with reg. mound and pits for meander cor.

80.00 falls in River, not set. Land level soil 1 strata No Timber. Heavy underg. with

Augmented in 80.00 chs.

East on random line bet Sec. 1 & 12

Vall. 30 E.

On account of river offset E. 1.50 chs. N. 3.50 to

1.50 Left Bank of Gunn River

S. L. Meridian

Set charred Cottonwood post 4x4in, 4ft. long, 2ft deep, marked M.C. with regulation mound and pits for meander Cor. to fractional secs. 1 & 12

40.00 Set temp. 1/4 Sec. cor.

80.16 Int. E Boundary of Tp. at cor. to Secs. 1 and 12 from which ~~#~~

West on true line

Set Secs. 1 and 12

40.08 Set charred Cottonwood post 4"x4" 4 ft. long 2 ft. deep, marked 1/4 Sou N side, with reg mound and pits for 1/4 Sec. cor.

80.16 The cor point to ~~fractional~~ Secs. 1. 2. 11 and 12

Land level

Soil 1st rate

Subs Tp 8 S. R 70 E

No Timber.

North on random line
bet. Secs. 1 and 2
Var 16°30' E
From a point 11.00 chns. West of
cor. point to Secs. 1. 2. 11 and 12
I offset North 29.00 chns
East 11.00 " to
29.00 on line in place on Right
Bank of Green River
Set charred Cottonwood post
4" x 4" 4 ft. long 2 ft. deep
marked M. C. with reg.
mound and pits for
Meander cor. to fractional
Secs. 1 and 2.
40.00 Set temp 1/4 Sec. cor.
A Cabin brs. S 66°45' E.

Salt Lake Meridian

8 chns. distant.
ascend.
60.00 Enter Bench
80.00 Int. N. Boundary of Tp.
at cor. to Secs. 1 and 2.
from which
South on true line bet
Secs. 1 and 2.
40.00 Set Sandstone 14 x 12 x 8,
9 in. deep, marked 1/4
on W side with stone
mound for 1/4 Sec. cor.
80.00 The cor. to Secs. 1, 2, 11 & 12
Land Broken and level
Soil 3rd and 1st rate
No Timber.
augmented on ~~69.00~~ 40.00 chns.

Subs Tp 8 S. R 20 E

North bet. Secs 34 and 35
Var 16° 30' E.

27.00 Euler Brush
32.25 White River 150 lks wide
3 ft. deep run. West.
40.00 On S. side of Road bears N W & SE
Set chained cottonwood post 4 x 4
in 4 ft long 2 ft deep, marked
1/4 S. on W. side with reg. mound
and pits for 1/4 sec cor.
65.00 Enter bench leave bench
80.00 Set Sand Stone 12 x 8 x 6, 8 in
Deep, marked one Notch on S. and
2 on E. edge with reg. mound
and pits for cor to Secs. 26. 27
34 & 35.
Land level bottom & bench
Soil 1st rate
No Timber heavy undergrowth
Augmented on 38 chs.

S. L. Meridian

East on random line bet.
Sec^s. 26 & 35
N 16° 30' E.

33.75 Hollow drains S.
40.00 Set temp. 1/4 sec Cor.
71.75 Wash drains S.
80.00 Int. A & B line at cor to Sec^s.
25. 26. 35 & 36 from which
West on line between
Sec^s. 26 & 35
40.00 Set Sand stone 14×10×4. 9 in
deep, marked 1/4 on N. side
with stone mound for 1/4 sec cor.
80.00 The cor to Sec^s. 26. 27. 34 & 35,
Land, level bench;
Soil Strata
No Timber
Oct. 16. 1879

Subs Tp 8 S. R 30 E

North bet Sec. 26 & 27
Va 16° 30' E.

28.00 Hollow drains N.W.
31.80 " " W.
40.00 Set Cobblestone 12×10×5 —
Pin dup. marked 1/4 on W.
Side with reg. mound and
pits for 1/4 sec cor
55.00 Hollow drains W.
60.50 Enter bottoms
62.00 Road from ashley to White
River bears N.E. & S.W.
80.00 Set Sand stone 24×10×6,
Pin dup. marked 2 Notches
On S. and E. edges with reg.
mound and pits for corts Sec.
22. 23. 26 & 27.
Land level bench & bottom
Soil Wheat
No Timber.

13.00
22.00
40.00
80.40
40.20
80.40

S. L. Meridian

Easton random line
bet sec. 23 & 26.
Va 16° 30' E.

13.00 Road bears N.E. & W.
ascend.

22.00 Enter Gypsum Hills

40.00 Set temp. 1/4 sec cor

80.40 Int. N. & S. line at Cor. Sec.
23. 24. 25 & 26 from which
Weston Sunline bet. Sec.
23 and 26.

40.20 Set Placed Cottonwood post
4x4 in. 4 ft long, 2 ft deep.
marked 1/4 on N. side
with reg. mound & pits
for 1/4 sec cor.

80.40 The Cor. Sec. 22. 23. 26. & 27
Land broken
Soil Erdrate
No Timber

Augmented on 67.40 chs.

Lab. Tp 8 S. R 20 E

North bet. Sec. 22 & 23
Va 16° 30' E.

32.50 Left Bank of Green River
4 ft dup. Set. charred cotton
wood post 4 x 4 in. 4 ft long. 2 ft
dup. marked M. C. for Meander
Cor.

40.00 Fallin River not set.

46.50 Right bank of Green River
Set. charred cottonwood post
4 x 4 in 4 ft long 2 ft dup.
marked M. C. with reg. mound
and pits for Meander Cor.

80.00 Set charred cottonwood post
4 x 4 in. 4 ft long. 2 ft dup.
marked 3 Notches on S. & 2 on E.
edges with reg mound & pits
for corts sec. 14. 15. 22 & 23

Land level Soil 1st rate
No Timber

22.00
40.00
68.33.
80.00
11.67
40.00

S. L. Meridian

Easton random line bet.
Sec. 14 and 23
V a 16° 30' E.

22.00 Enter Heavy brush.
40.00 Set temp. 1/4 sec cor.
68.33. Right bank of Green River
Note as the mile cor falls in
River, I triangulate to the M. C.
on E. Bank of River and find
its distance to be 12.17 chs. making
the connection
80.00 Int. N. & S. line at cor point to
Sec. 13. 14. 23 & 24. from which
West on true line bet. Sec. 14 & 23
11.67 Set chained cottonwood post. 4 x 4 in
4 ft long 2 ft deep marked M. C.
with reg. mound & pits
for meander cor.
40.00 Set chained cottonwood post
4 x 4 in 4 ft long. 2 ft deep.

313 Subs Tp 8 S. R 20 E

marked 1/4 on E. side, with
reg. mound & pits for 1/4 sec cor.
80.00 Mi. cor. to secs. 14, 15, 22 & 23.
Land, level bottom;
Soil, Rhate;
No Timber
Heavy brush on 58 chs.
Augmented on 58 chs.

North bet. secs. 14 & 15.
M 16° 30' E
40.00 Set chained Cottonwood post 4x4
in. 4 ft long, 2 ft deep, marked
1/4 on W. side with reg. mound
and pits for 1/4 sec cor.
45.00 Enter Cottonwoods
57.00 leave Same
78.00 Road bears N.W. & S.E.
80.00 Set. chained Cottonwood post
4x4 in 4 ft long, 2 ft deep,

BOOK-A-

I. L. Meridian.

BOOK-A-162

marked 4 Notches on S. and
2 on E. edges with reg.
mound and pits for Cor.
to Sec^s. 10.11.14 & 15
Land level
Soil Mixte
Timber Cottonwoods on 12 chs
Augmented on 12 chs.

East on random line bet.
Sec^s. 11 and 14
Va 16° 30' E.

40.00 Set temp. 1/4 sec. cor.
52.00 Road bears N & S.
59.00 Enter Cottonwoods
70.50 Right bank of Green River
Note: as the mile cor. falls in
River, I triangulate to Meander
Cor. on E. bank in line 15.90 chs
distant.

making the Connection

80.00 Int. N. & S. line at Cor point to Sec. 11.12.13 & 14 from which West on true line bet. Sec. 11 and 14.

9.50 Set chaued Cottonwood post 4x4 in. 4 ft. long 2 ft dup, marked M. C. for Meander Cor.

40.00 Set chaued Cottonwood post 4x4 in. 4 ft long 2 ft dup marked 1/4 on North side with reg. mound and pits for 1/4 Sec Cor

80.00 The Cor to Sec. 10. 11. 14 & 15 Land level

Soil Strata

Timber Cottonwoods on 11.50 chs

Augmented on 11.50 chs

S. L. Meridian

North bet. sec.s 10 & 11

Va 16° 30' E.

14.00 Ascend broken bench slope

40.00 Set Cobble stone 12×12 18, 8 in deep, marked 1/4 on W. side with pitone mound for 1/4 sec. cor.

41.00 Enter bench

80.00 Chained Cottonwood post 4×4 in 4 ft long 2 ft deep marked 5 Notches on S. and 2 on E. edges with reg. mound and pits for Cor to sec.s 2. 3. 10 & 11.

Land mostly level

Soil 1st & 2nd rate

No Timber

Augmented on 27.00 chs

BOOK-A-162

East on random line
bet. sec.s 2 and 11
M 16° 30' E

33.40 Road bears N & S.
35.00 Descend on broken bench slope
40.00 Set temp. 1/4 sec cor.
69.00 Right bank of Green River
Note: as the mile cor falls
in Green River I triangulate
to the Meander Cor on E. bank
in line 12.50 chs. dist. making
Connection
80.00 Int. N. & S line at cor point
to sec.s 1. 2. 11 & 12 from which
West on true line bet. sec.s 2 & 11
11.00 Set sand stone 16×11×5, 11 in dep. marked M.C. with
40.00 Set. sand stone 18×12×8, 12
in dep. marked 1/4 on W. side
with stone mound for 1/4 sec cor
80.00 The cor to sec.s 2. 3. 10 & 11
Land, level & broken,
stone mound for Meander Cor.

S. L. Meridian

Soil 1st & 3rd rate
No Timber
Augmented on 34 chs.

North on random line
bet. Sec.s 2 & 3.
Vas 16° 30' E.

4.00 Set temp. 1/4 sec cor
79.40 Int. N. Boundary of Tp. at
Corts Sec.s 2 and 3. from which
South on true line
bet. Sec.s 2 & 3.
39.40 Set Chained Cottonwood
post 4 x 4 in, 4 ft long,
2 ft deep, marked 1/4 S.
on W. side with reg. mound
and pits for 1/4 sec cor
79.40 The corts Sec.s 2. 3. 10 & 11
Land level,

BOOK-A-162

Soil, 1st rate;
No Timber.

North bet secs. 33 & 34
Va 16° 30' E.

From Witness Cor. 50 lks west of
Cor point offset N. 5.00 chs then E.
50 lks to.

5.00 White River 2.20 chs wide 4 ft
deep. runs S. Thence in bench

40.00 Set chained Cottonwood post
4x4 in 4 ft long. 2 ft deep, marked
1/4 S. on W. side with Reg. mound and
pit for 1/4 sec cor.

~~47.00 Enter Cottonwood~~

73.75 Left Bank of Green River
Set chained Cottonwood post 4x4
in. 4 ft long. 2 ft deep.
marked M. C. for meander

80.00

10.00

20.85

I. L. Meridian

Cor.

80.00 Fallen River not set;
Land level bottom;
Soil, 1st rate;
Not timber
Brush and heavy [illegible]
Augmented at 75 ch.

East on random line bet.
Secs 27 & 34
Va 16° 30' E.
From Meander Cor 6.25 chs S. of
Cor point to secs. 27, 28, 33 & 34 I offset
East. 10 chs, North 6.25 chs to.
10.00 Left Bank of Green River
Set chained Cottonwood post, 4×4
in, 4 ft long 2 ft deep, marked
M. C. with reg. mound & pits
for Meander Cor.
20.85 Fence bears N.W. & S.E.

321 Pubs Tp 8 S. R 20 E

BOOK A-162

25.00 Poppers Cabin bear N. 41° E.
" Stable & Corral " N 55 3/4° E.
29.75 Road bears N.E. & S.E.
35.00 Poppers Ranch Cabin bear N 25 1/4° W.
" Stable & Corral " N 17 3/4° W.
40.00 Set temp. 1/4 sec. cor.
60.00 Ascend on bench.
80.18 Ent. N. & S. line at cor to sec.
26. 27. 34 & 35 from which
Weston tree line bet sec.
27 & 34
40.09 Set Cobble Stone 15 × 8 × 6
10 in deep marked 1/4 on
N. side with Stone mound
for 1/4 sec cor.
80.18 The cor to sec. 27. 28.
33 & 34
Land level bottom & bench
Soil 1 Strata
No Timber

Note: As the line bet. Sec.s 27 & 28 falls mostly on the Ind. Reservation therefor from cor to Sec.s 22. 23. 26 & 27 West on true line bet. sec 22 & 27

Va 16° 30' E.

40.00 Set Chained Cottonwood post 4×4 in, 4 ft long, 2 ft deep, marked 1/4 S. on N. side with Reg. mound and pits for 1/4 sec cor.

42.00 Enter heavy brush.

80.00 Set chained Cottonwood post 4×4 in, 4 ft long, 2 ft deep, marked 2 Notches on S. and 3 on E. edges, with Reg. mound and pits for Cor to Sec.s 21. 22. 27 & 28

Land level;

Soil 1st rate, No Timber

Heavy brush & Augmented on [illegible]

BOOK-A-162

South bet. sec. 27 & 28

Va 16°30' E

1.67 Left Bank of Green River
Set chained Cottonwood post
4x4 in 4 ft long, 2 ft deep in
reg. mound & pits marked
M. C. for Meander Cor.
Note: Balance of line falls
on Reservation. —
Land. level; soil 1st rate;
No Timber

West on true line bet.
sec. 21. & 28.

1.50 Left Bank of Green
River set chained Cotton-
wood post 4x4 in, 4 ft
long, 2 ft deep, marked
M. C. with reg. mound

BOOK-A-162

and pits for Meander Cor.
Note: Balance of line falls on
Reservation ——
Land level;
Soil, Wrate;
No Timber.
Oct 17th 1879

North bet Sec. 21 & 22
Vat 6° 30' E.

21.66 Left Bank of Green River
Set chained Cottonwood post, 4 x 4 in
4 ft long 2 ft dup, marks M.C.
with Reg. mound & pits for
Meander Cor. Thence triangulate
to flag on N. side of river 33.34 chs
dist.

55.00 Right Bank of Green River
Set chained Cottonwood post
4 x 4 in, 4 ft long, 2 ft dup,

325 Subs Tp 8 S. R 20 E

marked M. C. with reg. mound
and pits for Meander Cor.
57.00 Ascend
66.00 Enter bench.
80.00 Set chained cottonwood post 4x4
in. 4 ft long, 2 ft deep, marks
3 notches on S. & E. edges, with
reg. mound and pits for Cor
to Secs. 15, 16, 21 & 22.
Land level bottom &
bench, Soil Strata
No Timber
Heavy underwrath on bottom
14.00 Augmented on 66 chs.
Note: 40 chs falls in river not set.

East on random line bet.
Secs. 15 & 22.
Vat 6° 30' E.

BOOK-A-162

5.75 Corral 2.70 chs dia.
22.00 Descend from bench
28.00 Enter bottom
40.00 Set temp ¼ sec. cor.
80.22 Int. N & S. line 34 lks S. of cor to Sec.s 14. 15. 22 & 23, from which S. 89° 45' W. on true line bet. Sec. 15 & 22
40.11 Set charred cottonwood post 4x4 in 4 ft long 2 ft deep, marked ¼ on N. side with Reg. mound & pits for ¼ sec cor.
80.22 The cor to Sec.s 15. 16. 21 & 22
Land level;
Soil 1st rate;
No Timber

Note: The line bet Sec.s 16 & 21. falling partly in Reserve Therefor Crum.

32 Subs Tp 8 S. R 20 E

BOOK-A-162

West on true line
bet sec. 16 & 21.
Va 16° 30' E.

40.00 Set chased Cottonwood post
4x4 in 4 ft long 2 ft dup,
marked 1/4 Lower N. Side with
reg. mound & pits for 1/4 Sec cor
49.00 Ascend
61.81 Int. Reservation boundary
at a point S 23° E. 37.60 chs dist.
Set a chased Cottonwood post 4x4 in
4 ft long 2 ft dup. marked C.C.
with reg. mound & pits for Closing
Cor to Fract. Sec. 16 & 21.
Land mostly level;
Soil Strata;
No Timber.

✓

North bet sec. 15 & 16
Va 16° 30' E.

40.00 Set charred cottonwood post, 4x4 in 4 ft long, 2 ft. deep, marked 1/4 Sec. W. side with reg. mound & pits for 1/4 sec cor.

80.00 Set. chared cottonwood post 4x4 in 4 ft long 2 ft deep, marked 4 Notches on S. and 3 on E. edges with reg. mound and pits for cor to Sec.s 9. 10. 15 & 16.

Land level bench,
Soil 1st rate,
No Timber.

East on random line
bet Sec.s 10 & 15
Va 1630 E.

20.00 Descend on broken slope of bench
40.00 Set temp. 1/4 sec cor.
64.50 Enter bottom
77.40 Road bears N.W. & S.E.

Subs Tp 8 S. R 20 E

80.12 Int. N & S. line 20 lk. S. of Cor to sec. 10.11.14 & 15 from which S. 89° 51' W. on true line bet. sec. 15 & 22.

40.06 Set. Sand stone 10 x 10 x 6, 6 in deep, marked 1/4 on W. side with stone mound for 1/4 sec cor

80.12 The cor to sec. 9.10.15 & 16 Land, broken bench slope, Soil Quadrate; No Timber.

North bet sec. 9 & 10 Va 16° 30' E.

14.65 Hollow drains E.

40.00 dep. 1 Pint pebbles in reg. mound & pits for 1/4 sec cor

47.15 Hollow drains E.

80.00 Set charred Cottonwood post 4 x 4 in 4 ft long

S. L. Meridian

2 ft. dup. marked 5 Notches on S. and 3 on E. edges with Stone mound for cor to Secs. 3. 4. 9 & 10.

Land level;
Soil Whole
No Timber

East on random line bet Secs. 3 & 10
Va 16° 30' E.

14.00 Road bears N.W. & S.E.
31.00 Hollow drains S.E.
40.00 Set temp. 1/4 Sec cor
79.80 Int. N & S. line 22 lks N. of cor to Secs. 2. 3. 10 & 11 from which N. 89° 51' W. on true line bet. Secs. 3 & 10
39.90 Set. chained Cottonwood post 4x4 in, 4 ft long, 2 ft dup.

331 Subs Tp. 8 S. R. 20 E.

marker 1/4 on N. side with
reg. mound and pits for 1/4 sec cor
79.80 The cor to sec. 3. 4. 9 & 10
Land level,
Soil 1st rate
No timber

North on random line
bet sec. 3 & 4
Va 16° 30' E.
17.00 Road bears N.W. & S.E.
35.00 Hollow drains S.E.
40.00 Set temp. 1/4 sec cor
80.19 Inst. N. B. of Tp. 25 lks W.
of cor to sec. 3 & 4 from which
S 0° 11' W. on true line bet sec.
3 and 4.
40.19 Set sand stone 10x10x6, 6 in
deep. marker 1/4 on W side

(See 2d Page forward)

BOOK-A-162

North bet. Secs. 32 & 33

Var. 16° 30' E.

From Meander cor. on Left Bank of Green River 6 chs. East of cor. point to Secs. 32 & 33 on S. Boundary I offset North 12. chns. West 6.00 chns to

12.00 Left Bank of Green River Set charred bottomwood post 4"x4" 4 ft. long 2 ft. deep marked M. C. with reg. mound of earth and pits for Meander cor. to Fractional Secs. 32 & 33.

40.00 Set charred bottomwood post 4"x4" 4 ft. long. 2 ft. deep marked 1/4 S. on W. side with reg. mound of earth and pits for 1/4 Sec. cor.

Subs. Tp. 8 S. R 20 E.

51.00 Left Bank of Green River
set charred Cottonwood post
4" x 4"; 4 ft. long 2 ft. deep
marked M. C. with reg.
mound of earth and pits
for Meander cor. to
fractional Secs. 32 & 33
Abandon further Survey
of this line on account of
Uintah Indian Reservation
Land level
Soil 1st rate
Timber a few scattering
Cottonwoods.
Heavey undergrowth

Augmented on 51.00 chns

BOOK-A-162

with reg. mound and pits for 1/4 sec cor.

80.19 The cor to sec. 3. 4. 9 & 10
Land, level;
Soil, 1st rate
No Timber

x

From cor to sec 9. 10. 15 & 16
West on true line bet. sec. 9 & 16
va 16°30' E.

40.00 Set chained Cottonwood post 4x4 in 4 ft long 2 ft deep, marked 1/4 on N. side with Reg. mound & pits for 1/4 sec cor

48.00 Ascend

80.00 Set Boulder 12x10x7, 8 in deep, marked 4 Notches on S. and E. edges with stone mound for cor to sec. 8. 9. 16 & 17.

Land mostly level;
Soil 1 strata
No Timber

South bet Sec. 16 & 17
Va 16° 30' E

37.00 Intersect Boundary line of Uintah Indian Reservation at a point N 23° W. 9.15 chs dist - from Mile Cor No 1.
where I set
A chained Cottonwood post 4 x 4 in 4 ft long, 2 ft deep, marked C.C. with Reg. mound and pits for Closing cor to fractional Sec. 16 and 17.

S. L. Meridian 336

Land rolling
Soil 1st rate
No Timber

West on true line
bet Sec. 8 & 17.
Va 16° 30' E.

15.70 Intersect Boundary line of Uintah Indian Reservation, at a point S. 23° E. 29.70 chs dist from Mile Cor. No 2. where set a charred cottonwood post. 4x4 in, 4 ft. long, 2 ft. dup marked C.C., with regulation mound and pits for closing Cor to fractional Sec. 8 & 17.

33 7 Sub. Tp 8 S. R 20 E

BOOK-A-162

Land, rolling;
Soil, 1st rate
No Timber

North bet. Sec. 8 & 9
N 16° 30' E.

13.00 Enter bench
40.00 Set chained cottonwood post. 4 x 4 in. 4 ft. long, 2 ft. deep, marked 1/4 on W. side, with regulation mound and pit for 1/4 sec cor
62.00 Wash drains E.
80.00 Set. chained cottonwood post, 4 x 4 in, 4 ft long, 2 ft deep, marked 5 Notches on S. and 4 on E. edges with reg.

J. L. M

mo
Cor
Lan

Ea
be

34.00 S
40.00 S
80.20 S
S
fo
S.
be
40.00 Se
pr
2 f

mound and pits, for
cor to secs. 4, 5, 8 & 9
Land, level bench,
Soil Indrate,
No Timber

East on random line
bet. secs. 4 & 9
Va 16° 30' E.

34.00 Wash drains S.E.
40.00 Set temp. 1/4 sec cor
80.20 Int. N & S. line, 18 lks
S of cor to secs. 3, 4, 9 & 10
from which
S. 89° 52' W. on true line
bet. secs. 4 and 9.
40.00 Set charred Cottonwood
post 4 x 4 in, 4 ft long
2 ft deep marked.

Subs Tp 8 S. R 20 E.

E

1/4 S. on N. side with reg. mound and pits for 1/4 sec cor.

80.20 The corts Secs. 4.5.8 & 9 Land level;
Soil Mixte;
No Timber,

West on true line between Secs. 5 and 8
Va 16° 30' E.

40.00 Set charred Cottonwood post, 4 x 4 in, 4 ft long, 2 ft deep, marked 1/4 S. on N. side with regulation mound and pits for 1/4 sec cor.

49.70 Intersect Boundary line of the Minitak

Indian Reservation at a point S.23°E 20.80 chs dist from Mile Cor No. 3. where I set a charred Cottonwood post 4x4 in. 4 ft long, 2 ft deep, marked C.C. with regulation mound and pits for closing Cor to fractional Secs. 5 & 8.

Land, level;
Soil, 1st rate;
No Timber.

North on Random line bet. Secs. 4 & 5
Va 16° 30' E.
40.00 Set temp. 1/4 sec cor

34 Subs Tp 8 S. R 20 E.

BOOK-A-162

57.00 Wash drains E.E.

79.65 Intersect N. boundary of Tp. at Cor to Sec.s 4 and 5, from which South on line line, bet. Sec.s 4 and 5.

39.65 Set chained cottonwood post 4x4 in 4 ft long, 2 ft deep, marked 1/4 S. on W. side, with regulation mound and pits for 1/4 Sec cor

79.65 The Cor to Sec.s 4.5.8 & 9

Land, level bench;

Soil 1st rate

No Timber

x

S. L. Meridian

342

Note: On acct of Reserve Trun from the Cor to Secs. 5 and 6. on N. boundary of Tp. South on true line between Secs. 5 & 6.

Va 16° 30' E.

70 Intersect Boundary line of Uintah Indian Reservation at a point S. 23° E. 22.40 chs dist. from Mile Cor No. 4, where I set a Charred cottonwood post 4 x 4 in 4 ft long, 2 ft deep, marked C.C. with u.g. mound and pits for closing Cor to fractional Secs. 5 & 6.

Land level

Soil Vt rate

No Timber

Oct 18th 1879. A. D. Fenon dep Sur.

34 Subs Tp 8 S. R 20 E

BOOK-A-162

Meanders of Green River
Right Bank.

Nov. 18th 1879 by E. Brettner
From the Meander Cor.
to Sec. 1 & 12 on Right Bank
of Green River, and East
Boundary of Tp. Sum

In Sec. 1

50.09 S. 82 °W. ~~35~~ chs.
X
35.00 S. 57 3/4 W. ~~30.70~~ " Thence
1-05-09 65.70

In Sec 2.

S. 48 1/2 °W. 4 chs.
S. 32 1/2 °W. 8.50 "
S. 13 3/4 °W. 10.10 "
S. 8 1/4 °W. 8.00 "
South 0.83 " Thence
33.33

In Section 11.

S. 28 3/4 °W. 22.80 chs.
S. 19 1/4 °E. 42.40 "
S. 4 1/2 °W. 20.00 " Thence
1-05-20

BOOK-A-16

S. 8 1/2
S. 1 1/2
S. 6°
S 11°
S. 12° W
S. 44° W
S. 65 3/4
S. 64 1/4
S 73°
S. 57
S. 78
S. 78
N 67
N 85
N 88
N 86
N 89

S. L. Meridian 344

BOOK-A-162

In Sec 14.

S. 8½° E. 20.22 chs
S. 1½° W. 20.00 "
S. 6° W. 34.20 "
S 11° W. 6.12 " Thence ...

1-00 [illegible]

In Sec. 23.

S. 12° W. 3.00 chs.
S. 44° W. 17.00 "
S. 65¾ W. 3.50 "
S. 64¼ W. 10.50 "
S 73° W. 16.00.
S. 57¼ W. 5.00.
S. 78° W. 24.30 " Thence

76.30

In Sec 22

S. 78° W. 10.50 chs.
N 67¼° W. 22.00 "
N 85¾° W 3.50 "
N 88° W 2.00 "
N 86¼° W 21.00
N 89° W 5.00

64-00

S. 89° W. 8.00 chs.
S. 75 3/4 W 4.00 "
S 82° W. 4.50 "
N 66 3/4 W. 2.33 " Thence
18-83
In Sec 21.
S. 33° W. 20.00 chs.
S. 9° W. 9.70 "
29.70
To Boundary Cor on Uintah Indian Reservation on right bank of Green River
Nov 18th 1879

Left Bank.

Beginning at the Meander Cor to Secs. 1 & 6 on E. Boundary of T and left Bank of River Comm
In Sec 1
S. 86° W. 6.50 chs.
S. 77 1/4 W. 12.50 "
S. 82° W. 3.00 "
S. 71 1/2 W. 9.00 "
31.00

P. L. Meridian

S. 76 3/4 W. 7.50 chs.
S. 25 1/4 W. 19.00 "
S. 61 1/2° W. 5.00 "
S. 37 1/2 W. 24.50.
S. 26 1/2° W. 15.70 Thence
On Dec. 12. Sec. 2?
S. 23° W. 3.85 chs. Thence
On Dec. 11
S. 23° W. 11.65 chs.
S. 2° W. 10.00 "
S. 14 1/2° E. 12.00 "
S. 21 3/4 E. 5.14 " Thence
On Dec 12
S. 21 3/4 E. 17.36 chs.
South 23.50 " Thence
On Dec 13.
S. 44 1/2° E. 4.00 chs
S. 34 3/4 E. 4.00 "
S. 15° E. 5.00 "
S. 19 1/2° E. 15.00 "
S. 46 3/4 W. 6.00 "
34.00

Subs Tp 8 S. R 20 E.

347

BOOK-A-162

S. 9 1/4° W. 15.50 chs.
S. 4 3/4° W. 31.00 "
S. 54 3/4 W 5.50 "
West 2.00 " Thence
54.00

In sec. 24.

S 14° W. 2.10 chs. Thence

In sec. 23.

S. 14° W. 1.96 "
S. 39 1/2 W. 26.00 "
S. 81° W. 6.00 "
S. 58° W. 8.00 "
S. 59° W. 20.00 "
S. 55 3/4 W. 15.00 "
S. 68 1/2° W. 8.00 "
West 9.00 "
N. 51 1/4° W. 5.42 " Thence
10.38

In sec. 22.

West 7.00 chs.
N 73 3/4° W. 20.00 "
West 11.00 "
N. 74 3/4° W. 14.50
52.50

S. L. Meridian 348

S 65 3/4 W. 6.50 chs.
S 67 1/2 W. 18.50 "
S 29° W. 12.00 " Thence
37.00
On Dec. 21.
S. 29° W. 15.00 chs.
S 19 1/4 E. 3.00 "
S 42 1/4 E. 7.75 " Thence
25.75
On Dec 28
S 42° E. 2.24 chs. Thence
On Dec. 27
S 42° E. 3.76 chs.
S 51 3/4 E 5.00 "
S 85° E. 2.00 "
S 81 1/4 E. 7.00 "
S 61 1/2 E 9.00 "
S. 37 1/4° E. 20.50 "
S. 12 1/2° E. 18.50 "
S. 5 3/4° E. 7.00 "
S 32° W 19.50 "
S. 69° W. 12.50 "
S 57 1/4° W. 7.00 "
1-4-76

BOOK-A-162

Subs Tp 8 S. R 20 E. S. L. Mer

349

S. 82° W. 2.53 chs. Thence

In Sec. 34.

S. 56 1/4° W.	10.50 chs.	
S. 64° W.	1.40 "	Thence

In Sec. 33.

S. 56 3/4° W.	9.00 chs	
S. 78 1/2° W.	15.00 "	
N. 83 1/2° W.	12.00 "	
N. 80° W.	7.50 "	
N. 65° W.	9.00 "	
S. 63 1/2° W.	21.00 "	
S. 52 3/4° W.	14.00 "	
S. 5° W.	3.50 "	Thence

In Sec. 32.

S. 14 1/4° W.	3.78 chs	
S. 26 3/4° W	2.35 "	
S. 35 1/4° W.	2.10 "	
S. 17 3/4° W	2.15 "	
West	0.15 "	
S. 10 1/2° W.	4.77 "	
S. 11 3/4° E.	20.50	
S. 9° E.	4.80	Thence

In Sec 33.

S. 25 3/4 E.	13.50 chs.	to Meander

Corto Sec. 4 & 33 on S. Boundary of Tp. and Left Bank of Green River.

Nov: 19th 1879

General Description

The Land embraced in this Tp. Consists of first-class bottoms along Green River and adjacent benches. They can all be readily irrigated and are mostly claimed by people who have been deterred from entering on their lands on acct of the prevailing Indian Troubles. Settlements have been made in Sec. 1, 14, 27, 34 & 33. [illegible]

E. Buttner Dep. Sur.

Land on both sides of River fond bottom
Coil, 1st rate,
Timber from fur w. Towards
Mangamdugrowth
Augmented on 15.04.06.

Nov. 19th 1879

BOOK-A-16

plo
ma
for
M
Ex
ad
fo
25
Tp
Tp
Tp
Tp
Tp

BOOK-A-162

LIST OF NAMES.

A list of the names of the individuals employed to assist in running, measuring or marking the lines and corners described in the foregoing Field Notes of ~~the~~

Meridian, Standard, Exterior, and Subdivision lines adjoining and embracing the following Tp's: Tp. 5 S. R 24 & 25 E. Tp. 4 S. R 22 E. Tp. 3 S. R 20 E Tp. 4 S. R. 21 E. Tp. 3 S. R 19 E. Tp's 6. 7 and 8 S. R. 20 E. Tp's 6. 7 and 8 S. R 21 E. Tp. 10 S. R. 18. 19 and 20 E. Tp. 9 S. R 19 and 20 E

BOOK-A-162

showing the respective capacities in which they acted.

Daniel W. Beard

Thomas Cornwell Chainman.

Joseph F. Remington Chainman.

Rodney B. Remington Flagman.

Richard Waldschmidt Axeman.

BOOK-A-162

LIST OF NAMES.

A list of the names of the individuals employed to assist in running, measuring or marking the lines and corners described in the foregoing Field Notes of ~~the~~

Meridian, Standard, Exterior, and Subdivision lines adjoining and embracing the following Tp's: Tp. 5 S. R 24 & 25 E. Tp. 4 S. R 22 E. Tp. 3 S. R 20 E. Tp. 4 S. R. 21 E. Tp. 3 S. R 19 E. Tp's 6. 7 and 8 S. R. 20 E. Tp's 6. 7 and 8 S. R 21 E. Tp. 10 S. R. 18. 19 and 20 E. Tp. 9 S. R 19 and 20 E

BOOK-A-162

BOO

and that said Surveys

have been in all respects, to the best of our knowledge and belief, well and faithfully surveyed, and the boundary monuments planted according to the instructions furnished by the Surveyor General. Daniel H Beard

Thomas Cornwell Chainman.

Joseph F Remington Chainman.

Rodney B Remington Flagman.

Richard Waldschmidt Axeman.

Subscribed and sworn to by the above named persons, before me, a Deputy Surveyor for Utah Ty. , [redacted]

~~of~~ , [redacted]erritory

~~of Utah~~, this 19th day of Nov. 1879

A. D. Fenon

U.S. deputy Surveyor

BOOK-A-162

I, Ernst Buettner

U. S. Deputy Surveyor, do solemnly swear that in pursuance of a contract with

Frd. Salomon

Surveyor General of the public lands of the United States in the Territory of Utah, bearing date the 13th day of June 1879, and in strict conformity to the laws of the United States, the Manual of Surveying Instructions, and the instructions furnished by the said Surveyor General, I have faithfully surveyed the Meridian, Standard, Exterior and Subdivision lines, adjoining and embracing the following tps:

Tp. 5 S. R 24 and 25 E
Tp. 4 S. R 22 E.
Tp. 3 S. R 20 E
Tp 4 S. R 21 E.
Tp 3 S. R 19 E

BOOK-A-162

BOO

Tps 6. 7 and 8 S. R 20 E.
" " " " " " " 21 E.
Tp 10 S. R. 18. 19 and 20 E.
Tp 9. S. R 19 and 20 E

In the Territory aforesaid, and do furt

solemnly swear that the foregoing are the t

and original Field Notes of such survey.

E. Buettner
U. S. Deputy Surveyor.

Subscribed by the said E. B

U. S. Deputy Surve

and sworn to before me, a Notary

Public *for*

county of Salt Lake *in the Terri*

of Utah, this 15 *day of* January 18

Edward Michaels
Notary Public
Salt Lake Co

BOOK-A-162

3259

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, Febry 24 1880

The foregoing field notes of the survey of the

Subdivision And Meanders of fractional

Township No 8 S. *Range No* 20 E.

of the Salt Lake Meridian, Utah Territory,

Executed by Ferron & Buettner

Under joint *contract No* 92

of the 13th *day of* June 1879

in the month of Oct. & Nov 1879

having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.

Jno. Salisbury

U. S. Surveyor General for Utah.

BOOK-A-162
R: 1880 (162) 357

Filed Feb. 17th 1880

Examined by F. G. Bailey

Compared by F. G. Bailey

FIELD NOTES

OF

THE SURVEY OF THE

West. Boundary

of Township No. 9 South, Range No. 19 East.

of the Salt Lake Meridian in Utah Territory.

BY

A. D. Vernon

U. S. DEPUTY SURVEYOR,

Under his Contract No. 92

dated June 13. 1879

Survey commenced Nov. 4th 1879.

Survey completed " " 1879.

Book 162

West Boundary

Township 9 S. **R.** 19 E

3.17	6	5	4	3	2	1
3.16	7	8	9	10	11	12
3.15	18	17	16	15	14	13
3.14	19	20	21	22	23	24
3.13	30	29	28	27	26	25
3.12	31	32	33	34	35	36

West boundary Tp. 9. S. R. 19. E.

BOOK-A-162

S. L. Meridian

Survey Commenced Nov. Oct 4 1879

By A. D. Perron

From the Cor. to Sps 9 & 10 S.

R. 18 and 19. E. Trun

Nor. bet Sec. 31 and 36.

Var. 16° 30' E.

4.50	Rocky gulch drains E.
15.00	Head of hollow " N.E.
34.60	Trail bears NE & SW.
40.00	Set sand stone 10 x 10 x 6. 10 in. deep marked 1/4 on W side with stone mound for 1/4 sec. Cor.
41.25	Hollow drains N.E.
57.00	" " " "
66.00	" " " "
80.00	Set sand stone 40 x 10 x 6, 20 in. deep marked 5 notches on N & 1 on S edges. with stone mound for Cor to sec. 25, 30, 31 & 36. Land broken.

West boundary T/p 9.S. R-19 E

Soil 3d rate

No Timber

Augmented on 80 Chs.

North bet. Sec's 25 and 30

Var. 16° 30' E.

0.75	Hollow drains S E
26.00	" " " "
40.00	Set sand stone 20 x 5 x 5. 15 in. deep marked 1/4 on W side with stone mound for 1/4 sec. Cor.
66.50	Sand stone ledge breaks 20 ft high bears E & W
74.00	Ledge ridge bears E and W
80.00	On solid sand stone ledge Marked as follows:- ‡, with stone Mound for Cor to sec. 19. 24, 25 and 30.

Land Very broken & rocky

BOOK-A-162

S. L. Meridian

Soil 3d rate
No Timber
Augmented on 80 Ch's

North bet Sec's 19 & 24
Var 16° 30' E.

26.15 Hollow drains S.E.

40.00 Set sand stone 20 x 10 x 10 - 15 in deep, marked 1/4 on W side with stone mound for 1/4 sec. Cor.

76.60 Trail bears N.W. and S.E.

80.00 Set sand stone 16 x 16 x 5 10 in deep. Marked 3 notches on N and S. Edges with stone mound for Cor. to Sec's 13 - 18 - 19 and 24

Land Broken plateau
Soil 3rd rate, rocky
No Timber
Augmented on 80 Ch's

West boundary Tp 9 S R. 19. E.
North bet Sec 13 and 18
Var. 16° 30' E.

35.50 Hollow drains E.
40.00 Set sandstone 12 × 10 × 6
8 in deep, Marked 1/4 on
W side with stone mound
for 1/4 sec. Cor.
45.00 Trail bears NW and S.E.
51.50 Hollow drains N.E.
58.00 " " " "
63.10 Trail bears NW and S.E.
80.00 Set sand stone 22 × 14 × 4
16 in deep. Marked 2 Notch
on N and 4 on S. Edges
With stone mound for
Cor. to secs 7. 12. 13 & 18
Land Very broken
Soil 3d rate
No Timber
Augmented on 80 Chs

S. L. Meridian

North bet. secs 7 and 12
Var 16° 30' East.

16.25	Trail bears NW and S.E.
23.25	" " " " "
40.00	Set sand stone 24 x 12 x 4 18 in deep. Marked 1/4 on W side with stone mound for 1/4 sec. Cor.
44.00	S.E. point of bench bears NW and S.E.
66.00	Enter hollow drains S.E.
73.25	Leave same
80.00	Set trachyte 22 x 10 x 10. 16 in. deep marked 1 notch on N and 5 on S. Edges with stone mound for Cor to Secs 1-6-7 and 12

Land broken.
Soil 3 drate
No Timber

Augmented 8 a 80 chs

BOOK-A-162

West Boundary T'p 9 S. R 19 E

North bet. Sec 1 and 6

Var. 16° 30' E.

5.00	Hollow drains E.
22.00	Enter wash hollow drains E
23.25	Leave same
40.00	Set sand stone 30 x 10 x 4
	20 in. deep marked 1/4 on
	W. side with stone mound
	for 1/4 sec Cor.
43.00	Ridge bears NW and SE
51.50	A sand stone boulder
	20 ft dia.
53.00	Ridge bears NE and SW.
80.00	Set Cobble stone 16 x 10 x 8 10 in deep
	Marked 6 notches on N. S. E. W edges with
	stone mound for Cor to T'ps 8 & 9 S.
	Range 18 and 19 E.

Land broken and ridgy

Soil 3d rate

No Timber

Augmented [illegible] 80 Chs.

Nov. 4th 1879

S. L. Meridian

General description:—
The t'ps adjoining this line Consist for the most part of high broken terra-Mauvais, unsuitable for Agricultural purposes, there are some signs of Coal, gypsum, iron, and Asphaltum but not sufficiently pronounced to justify subdividing.

A. D. Ferron

Note The t'p Not failing mostly in the Uintah Indian Reservation I abandoned further Survey North

BOOK-A-162

LIST OF NAMES.

A list of the names of the individuals employed to assist in running, measuring or marking the lines and corners described in the foregoing Field Notes of ~~the~~

Meridian, Standard, Exterior and Subdivision lines adjoining and embracing the following Tp's:

Tp. 5 S. R 24 & 25 E.
" 4 S. R 22 E.
" 3 S. R 20 E. Tp. 4 S. R 21 E.
Tp. 3 S. R 19 E. Tp's 6. 7. & 8 S. R 20 E. Tp's. 6. 7 & 8 S. R 21 E.
Tp. 10 S. R's. 18. 19 & 20 E.
Tp. 9 S. R. 19 & 20 E.

showing the respective capacities in which they acted.

Otto E. Salomon, Compassman
Charles C. Bingham, Chainman.
William H. Beddshaw, Chainman.
Alfred H. Westover Flagman.
Thomas Bingham, Jr. Axeman.

BOOK-A-162

in which

rman.

nman.

nman.

gman.

eman.

We hereby certify that we have assisted

Augustus A. Fenon

U. S. Deputy Surveyor in surveying the

Meridian, Standard, Exterior and Subdivision lines, adjoining and embracing the following

Tps: Tp. 5 S. R 24 & 25 E.
Tp. 4 S. R 22 E Tp. 3 S. R 20 E
Tp. 4 S. R 21 E. Tp. 3 S. R 19 E.
Tp's. 6. 7 and 8 S. R. 20 E.
Tp's. 6. 7 and 8 S R 21 E.
Tp. 10 S. R. 18. 19 and 20 E
Tp. 9 S. R. 19 and 20 E.

BOOK-A-

and that said Townships have been in all respects, to the best of our knowledge and belief, well and faithfully surveyed, and the boundary monuments planted according to the instructions furnished by the Surveyor General. Otto E. Solomon Compassman

Charles R Bingham Chainman

William H. Bradshaw Chainman.

Alfred C White Flagman.

Thomas Bingham Jr Axeman.

Subscribed and sworn to by the above named persons, before me, a Dep Surveyor, for the ~~County~~ ~~of~~ _____, ~~in the~~ Territory of Utah, this 5th day of Nov. 1879

A. D. Simon

U. S. Dep. Surveyor.

BOOK-A-162

I, Augustus L. Ferron

U. S. Deputy Surveyor, do solemnly swear that in pursuance of a contract with

Fred. Salomon

Surveyor General of the public lands of the United States in the Territory of Utah, bearing date the 13th day of June 1879, and in strict conformity to the laws of the United States, the Manual of Surveying Instructions, and the instructions furnished by the said Surveyor General, I have faithfully surveyed the, Meridian, Standard, Exterior and Subdivision lines adjoining and embracing the following Tp's. – Tp. 5 S. R. 24 & 25 E. Tp. 4 S. R. 22 E. Tp. 3 S. R 20 E. Tp 4 S. R. 21 E. Tp. 3 S. R 19 E. Tp's 6. 7. & 8 S. R 20 E Tps. 6. 7 & 8 S. R 21 E Tp. 10 S. R 18 19 & 20 E. Tp. 9 S. R 19 & 20 E

BOOK-A

In the Territory aforesaid, and do furt

solemnly swear that the foregoing are the t

and original Field Notes of such survey.

Augustus S. Gunn

U. S. Deputy Surveyor.

Subscribed by the said

Augustus S. Gunn *U. S. Deputy Surve*

and sworn to before me, a Notary

Public *for*

county of Salt Lake *in the Terri*

of Utah, this 15 *day of* January *1*

Edward Michaels

Notary Public

Salt Lake County

BOOK-A-162

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, Febry 24 1880

The foregoing field notes of the survey of the

West boundary of

Township No 9 S. *Range No* 10 E

of the Salt Lake Meridian, Utah Territory,

Executed by A. D. Ferron

Under first *contract No* 92

of the 18th *day of* June 1879

in the month of Nov. 1879

having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.

Fred. Salomon

U. S. Surveyor General for Utah.

BOOK-A-162
R: 188 (62) Copied 360

Filed Feb. 17th 1882.

Examined by J. C. Bailey

Compared by " " "

FIELD NOTES

OF

THE SURVEY OF THE

West Boundary

of Township No. 9 South, Range No. 20 East

of the Salt Lake Meridian in Utah Territory.

BY

A. H. Ferron

U. S. DEPUTY SURVEYOR,

Under his Contract No. 92

dated June 13 1879

Survey commenced Nov 14 1879.

Survey completed " " 1879.

Book 162.

West Boundary

Township 9 S R. 20 E.

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

BOOK-A-162

West Boundary Tp. 9 S., R 20 E.

Survey commenced Nov 1st. 79
by A. D. Ferron
From the established Cor to Tps 9 & 10
S., R 19 & 20 E. Irun
North bet. Sec.s 31 and 36.
Var 6° 30' E.

7.00 Hollow drains N.W.
20.00 " " "
40.00 Set Sandstone 24 x 10 x 3, 15 in.
deep, marked 1/4 on W. side
with Stone mound for 1/4 Sec. Cor.
45.00 Wash drains E.
50.00 Marked Stationary Sand Stone
5 x 1 x 1 ft. above ground, 5 Notches
on N. and 1 on S. edges, with
Stone mound for cor to Sec.s 25. 30. 31 & 36
Land, broken plateau;
Soil, Strata;
No Timber
Segmented on 80 chs.

West Boundary Tp 9 S. R 20 E.

North bet Sec. 25 and 30.

Va. 16°30' E.

0.50 Enter flat basin, enter heavy b

29.50 Wash drains N.E.

33.50 Leave basin, leave brush.

40.00 Set sand stone 16×10×6, 11 in deep, marked 4 on N. side, with stone mound for ¼ sec cor.

56.50 Hollow drains N.E.

74.75 " " N.W.

80.00 Set sand stone 14×10×8, 9 in deep, marked 4 Notches on N. and 2 on S. edges, with stone mound, for cor to sec. 19, 24, 25 and 30.

Land, mostly broken

Soil 3rd rat 5 Ultrate

No timber

Heavy brush on 33 chs.

Augmented on 80 chs.

BOOK-A-162

S. L. Meridian

North bet. Sec.s 19 and 24.

Vat 6°30' E.

2.00	Enter Willow Ank bottoms and Heavy brush
2.50	Ridge bears E & W.
33.00	Dry bed of Willow Ank drains N.W.
40.00	Set chained cottonwood post 4×4 in. 4 ft. long, 2 ft deep, marked 1/4 on W. side with reg. mound and pits for 1/4 Sec. Cor.
48.50	Ascend, leave brush.
75.00	Hollow drains W.
80.00	Set Sand Stone 24×10×6, 18 in deep, marked 3 notches on N. and S. edges, with Stone mound, for Cor to Sec.s 13. 18. 19 and 24.

Land broken plateau and bottom

West Boundary Tp. 9 [illegible]

Soil 1st and 3rd [illegible]
No Timber
Augmented on 80 chs.

North bet. Sec. 13 & 18
Va 16° 30' E.

0.50 Hollow drains S.W.
35.00 " " "
40.00 Set Sand stone 20 x 10 x 6, 15 in. deep, marked 4 on St. [illegible] with stone mound for [illegible]
80.00 Set Cobble stone 10 x 10 x 6, [illegible] deep, marked 2 Notches on N. and 4 on S. edges, with stone mound for Cor. to Sec. 7, 12, 13 and 18.
Land broken, Soil 2nd [illegible]
No Timber
Augmented on 80 chs. —

BOOK-A-162

S. L. Thomson

In the bet. sec.s 7 and 12
Ca 16° 30' E.

10.00 Deposited small stone marked
with a cross (+) in reg mound
of earth and pits for ¼ sec. cor.
from which
G. Snyder's Cabin bear. S 7/4 20' W.

10.00 Enter Green River bottom,
10.00 set charred aspen post
4 x 4 in 4 ft long, 2 ft. deep,
marked 1 Notch on et. and 5 on
sides for Cor to Sec.s 1.6. 7 & 12
Lined broken & level bottom
Soil 2 & 1 Strata
Dr Timber
Augmented on 50 ch.

West boundary Tp. 9 S., R. 20

North bet. Sec.s 1 and 6

Cal. 6° 30' E.

Enter a [illegible] grove & thick brush

40.00 Set charred cottonwood post 4×4 in., 4 ft. long, 2 ft. deep, marked 1/6 S. on W. side, with reg. mound and pits for 1/4 sec. cor.

65.30 Left bank of Green River set charred cottonwood post 4×4 in., 4 ft. long, 2 ft. deep, marked M.C., with regulat. mound and pits for Meander Cor.

Note: The River being the boundary of the Uintah Indian Reservation I abandon line here.

Land good bottom;

Soil, Shale;

Timber Cottonwood

Augmented on 65.30 chs

Nov. 14. 1879

BOOK-A-162

J. L. Meridian

General Description

This Tp. embraces portions of the Green River bottoms and adjacent bench land. The South & East parts consist principally of broken bed lands containing coal & asphaltum.

A. D. Gerron

Dep. Sur.

BOOK-A-162

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, Feby 24 1880

The foregoing field notes of the survey of the

West Boundary of

Township No 9 S. *Range No* 20 E.

of the Salt Lake Meridian, Utah Territory,

Executed by A. D. Ferron

Under joint *contract No* 92

of the 13th *day of* June *18*79

in the month of Nov. *18*79

having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.

Fred. Salsbury

U. S. Surveyor General for Utah.

BOOK-A-162
R:1880 (162)
(Copied)
569

Filed Feb. 18th 1880

Examined by F. C. B.

Compared by F. C. Bailey

FIELD NOTES

OF

THE SURVEY OF THE

West Boundary

of Township No. 10 S., Range No. 19 E.

of the Salt Lake Meridian in Utah Territory.

BY

A. D. Ferron

U. S. DEPUTY SURVEYOR,

Under his Contract No. 92

dated June 13 1879.

Survey commenced Nov. 3 1879.

Survey completed " 1879.

Journal

Book 162

West Boundary

Township 10 S. **R.** 19 E.

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

West boundary Tp 10 S R 19 E.
OOK-A-162
370
G. S. L. Meridian

Survey Commenced Nov. 3. 1879
By A. D. Ferron

From the standard Cor. to Tps
10. S R 18 and 19 E on the second
standard parallel S. established
by me. Trun N. between Secs.
31 and 36 Var. 16° 30' E.

08.00 Gulch drains N.W.

40.00 Set sand stone 13 × 7 × 6 - 8 in deep
marked 1/4 on W. side with stone
mound for 1/4 Sec. Cor.

69.00 Gulch drains N.W.

0.00 Set sand stone 10 × 10 × 6 - 6 in deep
marked 5 Notches on N and 1 on
S. Edges with stone mound for
Cor to Secs. 25. 30 - 31 and 36.

Land broken plateau

Soil 2d rate

No timber

Augmented on 80 Chs

West boundary Tp 10 S. R 19 E

North bet. Sec's 25 and 30
Var. 16° 30' E.

40.00 Set sand stone 12 × 9 × 7 - 8 deep Marked 1/4 on W side with stone mound for 1/4 sec. Cor.

49.50 Gulch drains N.W.

71.00 Enter Green River bottoms on heavy undergrowth.

78.50 Left bank of Green River 4 ft deep runs S.W. set Charred Cottonwood post. 4 × 4 in, 4 ft long, 2 ft deep marked m.c. with reg mound and pits for meander Cor.

80.00 Falls in river not set.

Land Mostly very broken plate
Soil 2d rate
Timber - A few Cottonwoods on riv

Augmented on 80 Ch

BOOK-A-162

North between Secs. 19 and 24
Var. 16° 30' E

From the meander Cor. 1.50 ch's S of Cor. point to Sec's 19-24-25 and 30. I triangulate across river and find the distance to be 6.75 ch's. Therefore

5.25
25.00 right bank Green River set Charred Cottonwood post 4x4 in, 4 ft long, 2 ft deep, marked M.C. with reg. mound & pits for meander Cor.

9.00 Leave bottom and undergrowth.

6.50 Chaining becoming impracticable on account of heavy sand stone breaks. I offset E. 40 ch's Thence N. 52 ch's. Thence N 20° 30' W. 12.28 ch's to a point 34.70 ch's E. of:-

80.00 where I set a Green Sand stone

West boundary Tp 10.5. R 19

16×9×6, 10 in deep marked
3 notches on N. and S. Edges
and W.C. with stone mound
for witness Cor. to Secs 13.1
19 and 24.

Note The 1/4 sec. Cor point falling
in impracticable breaks is
Not established.

Land - on offset line mostly
bottom.

Soil 2d rate, and 1st rate

Timber a few Cottonwoods along
heavy undergrowth of willows
hawthorns and briers.

Augmented on 80 Ch's

North bet Secs 13 and 18
Var. 16° 30' E.
From witness Cor. 34.70 Ch's
of Cor. point to sec 13-18-19

BOOK-A-162

Salt Lake Meridian

24, I run

N. 20° 30' W. 15 Ch's

N 32° 30' W. 24 Ch's

N. 11° 30' W. 33 Ch's

N 20. 45' W 14.30 Ch's

to a point; 4.90 Ch's E. of ⊥

0.00 Where I set a sand stone

18 × 16 × 10 – 12 in. deep. Marked

2 notches on N, and 4 on S. Edges

and W. C. for witness Cor. to

Sec. 7 - 12 - 13 and 18. On edge

of Green River where I erected

a stone mound 4 ft. high.

ote The 1/4 Sec. Cor point falling

in impracticable breaks

is not Established

Land along of set line good bottom

Soil 1st rate

Timber a few Cottonwoods. heavy

Undergrowth of Willows

West Boundary Tp 10 S R 19

Hawthorn & briers

Augmented on 80 Ch

North bet. Sec 7 and 12

Var 16° 30' E.

From Witness Cor. 4.90 Ch's

E. of cor. point to Sec. 7-12

13 and 18 - I run

N	20° 45'	W.	11 Ch's
N.	7° 30'	W.	10 "
N	5°	E	12 Ch's
N	18° 30	E.	11.50 "
N	33°	E	22 "

North 18.97 Ch's. To a point

16.21 Chs E. of :-

80.00 Where I set a schale ro

16 x 8 x 4, 10 in deep, Marke

1 Notch on N. and 5 on

edges and W. C. for Witness

Cor. to Secs 1, 6, 7 and 12

Salt

Note The

imp

is

La

Good

Tim

Unde

& b

Au

Nor

Fro

E.

7 a

Off

Sa

4.5

9.5

BOOK-A-162

Salt Lake Meridian

Note The 1/4 Sec. Cor point falls in impracticable breaks and is not established

Land along Offset line mostly Good bottom

Soil 1st rate.

Timber a few Cottonwood, heavy Undergrowth of Willows, hawthorns & briers

Augmented on 80 Ch's

North between Secs. 1 and 6

Var. 16° 30' E.

From Witness Cor. 16.21 Ch's E. of Cor point to Sec 1-6. 7 and 12 I run north on Offset line taking notes on said line as follows:—

4.50	Hollow drains S.W.
9.50	Ridge bears NE and S.W.

BOOK-A-162

West Boundary Tp 10 S R 19-6

14.00	Hollow drains S.W.
21.00	" " N.W.
26.00	" " S.W.
43.50	Trail bears NW and SE
46.00	To a point thence

West 16.21 Ch's to

46.00 on line in place Whe
I set a schale rock 20 x 5
15 in deep. Marked 1/4 W. C.
for witness 1/4 sec. Cor. Thence
North on line in place.

52.00 Hollow drains N.E.

58.00 Trail bears NW and S.E.

60.00 Hollow drains E.

80.00 Set sand stone 20 x 16 x 14 - 15 in deep.
Marked notches on N.S.E.W. Edges with stone
Mound, for Cor to tps 9 and 10 S R 18 and 19
Land very broken, - Soil 3d rate - No timber,

Augmented on 80 Ch's Nov. 3 1877

General description - The tps adjoining this line contain very
arable land, and show no signs of minerals

A. D. Ferron Dep'y

Salt Lake Meridian

BOOK-A-162

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, Febry 24 1880

The foregoing field notes of the survey of the

West Boundary of

Township No 10 S. *Range No* 19 E.

of the Salt Lake Meridian, Utah Territory,

Executed by A. D. Ferrow

Under joint *contract No* 92

of the 13th *day of* June 1879

in the month of Nov. 1879

having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.

Fred. Salsbury

U. S. Surveyor General for Utah.

BOOK-A-162

Copied (162) 379

R: 1880.

Filed Feb. 19th 1880.

Examined by F. C. Bailey

Compared by O. C. S. and F. L. a. G.

FIELD NOTES

OF

THE SURVEY OF THE

Exterior Boundaries

of Township No. 10 S., Range No. 20 E.

of the Salt Lake Meridian in Utah Territory.

BY

Augustus D. Dixon

U. S. DEPUTY SURVEYOR,

Under his Joint Contract No. 92

dated June 13. 1879.

Survey commenced Oct. 30. 1879.

Survey completed " 30. 1879.

Book 162 BOOK-A-162

Exterior Boundaries

Township 10 S **R.** 20 E.

	390	389	388	387	386	385
384	6	5	4	3	2	1
383	7	8	9	10	11	12
382	18	17	16	15	14	13
381	19	20	21	22	23	24
380	30	29	28	27	26	25
379	31	32	33	34	35	36

BOOK-A-162

West Boundary Tp 10 S. R. 20 E.

Survey commenced Oct 3rd by [illegible]

From the Stand. Cor. to Tp. 10 S.,

R. 19 and 20 E. established by me.

From North Cut. Sec. 31 & 36.

Va 16.30 E.

18.00 Hollow drains N.E.

28.00 " " "

40.00 " " " Set Sand

Stone 12 x 10 x 5, 8 in. deep.

marked 1/4 on W. side, with

Stone mound for 1/4 sec cor.

49.00 Gulch drains N.W.

58.50 " " "

79.40 Same " " N.E.

80.00 Set Sand Stone 14 x 14 x 13, 9 in.

deep, marked 5 Notches on N. and

one on S. edges, with Stone mound for

cor. to Sec. 25, 30, 31 and 36.

Land, broken plateau

Soil 3rd rate.

Ver Timber

Augmented on 80 chs.

West Boundary Tp. 18 S., R. 20 E.

	North bet. Sec. 25 & 30.	6.50
	Va 16° 30' E.	28.00
26.50	Hollow drains N.E.	40.00
38.00	" " "	
40.00	Set Sand Stone 20×12×3, 15 in.	
	deep, marked 1/4 on W. side, with	57.25
	Stone mound for 1/4 Sec. Cor.	80.00
60.00	Gulch drains N.W.	
66.50	Ridge bears E & W.	
80.00	Set Sand Stone 14×10×4, 9 in.	
	deep, marked 1/4 Notch on N. and 1/4	
	on S. edges, with Stone mound for	
	Cor. to Sec. 19, 24, 25 and 30.	
	Land, broken rocky plateau;	
	Soil, 3rd rate.	
	No Timber	
	Augmented on 80 chs.	
		17.50
	North bet. Sec. 19 and 24.	29.00
	Va 16° 30' E.	40.00

BOOK-A-162

6.50 Gulch drains N.W.

28.00 Gulch " E.

40.00 Set sand stone 12×8×8, 8 in dup. marked 1/4 on W. side, with stone mound, for 1/4 sec. cor.

57.25 Gulch drains N.W.

80.00 Set sand stone 16×8×5, 11 in dup. marked 3 notches on N. and S. edges with stone mound, for cor. to Sec.s 13.18.19 and 24.

Land, broken rocky plateau;

Soil, 3rd. rate;

No Timber

Augmented on 80 chs.

North bet. Sec.s 13 & 18

Va 16°30' E.

17.50 Wash drains N.E.

29.00 Hollow " E.

40.00 Set sandstone 24×14×6, 18 in.

West boundary Tp 10 S. R 20 E

	[illegible] marked 1/4 on W. side, with stone mound, for 1/4 sec.	53.35
		70.00
52.00	Ridge bears N.E. & S.E.	73.50
65.00	Gulch drains N.E.	80.00
79.00	" " E.	
80.00	Set sand stone 14 x 10 x 6, 9 in. deep, marked 2 notches on N. and 4 on S. edges, with stone mound for corto Sec.s 7.12.13 and 18. Land, broken plateau; Soil, 3rd class; No Timber; Augmented on 80 chs.	
	North bet. Sec.s 7 and 12 (Va 16° 30' E.	17.00
		30.00
33.50	Hollow drains N.E.	36.00
40.00	Set sand stone 14 x 8 x 6, 9 in. deep, marked 1/4 on W. side, with stone mound for 1/4 sec.	40.00

BOOK-A-162

T. L. Meridian

53.35	Rocky Gulch drains N.E.
70.00	W. point of Ridge, bears E.
73.30	Wash in hollow drains N.W.
80.00	Set Sand Stone 16×10×6, 11 in. deep, marked one Notch on N. and 5 on E. edges, with Stone mound for Cor. to Secs. 1, 6, 7 and 12.
	Land, broken plateau; Soil, 3rd rate;
	Un Timber
	Augmented on 80 chs.

North bet. Secs. 1 and 6.

Va 16° 30' E.

17.00	Wash in hollow drains N.W.
20.00	Ridge bears E & W.
36.00	Hollow drains W.
40.00	Set Sand Stone 40×16×4, 20 in. deep, marked 1/4 on W. side with Stone mound for 1/4 sec. Cor.

West Boundary Tp. 10 S. R. 20 E.

52.00	Ridge bears N.W. and S.E.	
60.00	Hollow drains N.W.	
80.00	Sandstone 30x14x4, 20 in. deep, marked C. Hatcheson N.S.E.W.	
	Edges for cor. to Tps 9 & 10 S., R. 19 and 20 E.	40.00
	Land, broken plateau;	
	Soil, 3rd rate;	
	No Timber.	41.25
	Augmented on 80 chs.	73.00
	Oct. 30. 1879.	80.00

North Boundary Tp. 10 S., R. 20 E.

From the cor. to Tps 9 & 10 S., R. 19 & 20 E.
Time E. on random line, setting temporary 1/2 mile and mile, cors.
At 5 miles 78 chs and 90 lks, I intersect the Green River Guide Meridian 110 lks N. of cor. to Tps 9 & 10 S. R. 20 & 21 E.
The correction for the true line will therefore be 1873 lks S. pr. mile.

BOCK-A-162

North Boundary Tp 10 S., R 20 E.

From the cor. to Tps. 9 & 10 S., R 20 and 21 E. Sum

N 89° 52 W. on true line bet. secs. 1 & 36.

Va 16° 30' E.

40.00 Set Sand Stone 13 x 7 x 6, 8 in. deep, marked ¼ on N. side, with stone mound for ¼ sector.

41.75 Hollow drains N.W.

43.00 Hollow drains N.E.

80.00 Set Sand Stone 14 x 8 x 5, 9 in. deep, marked one Notch on E. and 5 on W. edges, with Stone mound for cor. to Secs. 1. 2. 35 & 36.

Land, broken plateau;

Soil 3rd rate,

No Timber

Augmented on 80 chs.

N 89° 52' W. on true line bet. Secs. 2 & 35

Va 16° 30' E.

387 BOOK-A-162

North Boundary Tp 10 S. R 20 E

5.00	Hollow, drains N.W.	
9.50	Same " " S.W.	
19.00	" " " N.W.	70.00
40.00	Set Sand stone 14 x 10 x 4, 9 in. deep, marked 1/4 on N. side with stone mound for 1/4 sec cor.	80.00
52.50	Hollow drains N.W.	
80.00	Set Sand stone 18 x 10 x 3, 12 in. deep, marked 2 Nat Chison E. and 4 on W. edges with stone mound for Cor to Sec. 2.3.34 & 35. Land, broken plateau; Soil, 3rd. rate; No Timber Augmented on 80 chs.	15.50
	N. 89° 52' Wentworth line, Sec. 3 & 34. Va 16° 30' E.	30.00
9.50	Hollow drains N.	39.25
33.00	Willow Creek Road bears N & S.	40.00
40.00	Set Sand stone 17 x 12 x 3, 11 in. deep	

S. L. Meridian

marked 1/4 on N. side, with stone mound for 1/4 sec cor.

70.00 Hollow drains N.

80.00 Set sand stone 16×9×5, 11 in. deep, marked 3 Notches on E & W. edges with stone mound for cor to sec. 3.4. 33 & 34

Land, broken plateau;

Soil, Indrate;

No Timber.

Augmented on 80 chs. —

N 89° 52' Wontrue line bet. Sec. 4 & 33.

Va 16° 30' E.

15.50 Hollow drains N.E.

30.00 " " N.

39.25 " " "

40.00 Set sand stone 16×9×6, 11 in deep, marked 1/4 on N. side, with stone mound for 1/4 sec. cor.

North Boundary Tp. 10 S. R. 20 E. | North

51.00	Hollow drains N.	80.00
61.60	" " "	
80.00	Set Sand Stone 14 x 9 x 5, 9 in. dup.	
	marked 4 Notches on E. & W. edges	
	with stone mound for cor. to Sec.	
	4.5.32 and 33.	
	Land, Coker plateau	
	Soil 3rd rate	
	No Timber	
	Augmented on 80 chs.	
	N. 89°52' W. on cor. line bet. Sec. 5 & 32	
	Va 16°30' E.	69.00
40.00	Set Sand Stone 18 x 10 x 4, 12 in. dup.	
	marked 4 on N. side with stone mound	40.00
	for 4 Sec. cor.	
45.75	Hollow drains N.W.	
61.00	Perp. Sand Stone Bluff 100 ft high	78.90
66.00	Enter Willow Creek bottom near	
	mouth of of small Cañon head N.E.	
78.00	Dry bed of Willow Creek drain	

BOCK-A-162

North Boundary Tp 10 S., R. 20 E.

80.00 Set sand stone 14×10×6, 9 in dup, marked 5 Notches on E & on W. edges, with stone mound for cor to Sec.s 5 & 6. 31 and 32.
Land, broken plateau and bottom;
Soil, 3rd & 1st rate
No Timber
Augmented on 66 chs. —

N. 89° 52' W. on true line bet. Sec.s 6 and 31. Va 16° 30' E.

99.00 leave bottom enter broken plateau.

40.00 Set sand stone 10×10×6, 6 in dup, marked 4 on N. side with stone mound for 1/4 sec cor.

48.90 The cor to Tps. 9 & 10 S., R. 20 & 21 E.
Land, broken plateau & bottom —

Soil 3rd rate

No Timber

Augmented on 49.90 chs.
Oct 31st 1879

General Description

The land embraced by these boundaries is only partly agricultural viz: the bottoms along Willow Creek. The balance consists of bad lands containing coal, asphaltum & mineral wax.

A. G. Ferron, dep. sur.

BOOK-A-162 392

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, Febry 24 1880

The foregoing field notes of the survey of the

West & North boundaries of

Township No 10 S. *Range No* 20 E

of the Salt Lake Meridian, Utah Territory,

Executed by A. D. Ferron

Under joint *contract No* 92

of the 13 *day of* June 1879

in the month of Oct. 1879

having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.

Fred. Salomon

U. S. Surveyor General for Utah.

BOOK-A-162
B: (462) Copied 393

Filed 187 .

H. C. Examined by J. C. B.

Compared by O. E. S. F. G.

FIELD NOTES

OF

THE SURVEY OF THE

Ind. Standard Parallel South (and offsets)

~~of Township No.~~ through , Range No. 18, 19 & 20 E.

of the Salt Lake Meridian in Utah Territory.

BY

A. D. Ferron

U. S. DEPUTY SURVEYOR,

Under his Contract No. 92

dated June 13th 1879

Survey commenced Oct. 10. 1879.

Survey completed " 11 1879.

Book 162 BOOK-A-162

2nd Standard Parallel South and Offsets.

~~Township~~ through R. 18 E.

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

394 395 396 397

Stand. Par. S., Range 18. East.

OOK-A-162

Survey Commenced Oct. 10. 1879
by A. J. Tucson
Co. on the Witness Cor. 9. 10 [illegible]
of Cor. point to Sec. 26. 27. 34 & 35
Established by me last season
on an offset to the 2nd. Standard
Parallel S. Crum
East. bet. Sec. 27 & 34
Va 6° 30' E.

[illegible]19 Mag. per Cor on Right Bank of Green River
Note on acct of Green River, I
chain a base North 5 chs. from
which a flag on E. Bank of
Green River bears S. 53° E.
distance across River 6.63 chs.

[illegible]6.82 Left Bank of Green River
Set. Chaud Cottonwood post 4 x 4 in
4 ft. long, 2 ft. dup, marked M. C. with reg.
[illegible] and pits for Meander Cor.

[illegible]000 Set Chaud Cottonwood post
4 x 4 in. 4 ft. long, 2 ft. dup,

393 Offset for
Second Stand Par. S. R 18 E

BOOK-A-162

marked 3 Napkins on E.
and one on S. edges for Cor
to Sec. 26. 27. 34 and 35
Land good bottom
Soil 12 ft. ate
No Timber
Heavy underpinned
Augmented on 9.81 Chs.

Note. The ground permitting
I now again the 2nd Stand.
Parallel S. by running
South bet. Sec. 34 & 35
Vat 6° 30' E

4000 Set charred bottom wood
post, 4 x 4 in. 4 ft. long,
2 ft. dup, marked 1/4 on W. Ma
with reg. mound and pit

BOOK-A-162

Second Stand. Par. S. R. 18

for 1/4 Sec Cor.

[illegible] Set chained Cottonwood post 4 x 4 in 4 ft long, 2 ft deep, marked 2 Notches on E. 4 on W. 6 on N. on S. C. on S. Sides with [illegible] mound of earth and pits [illegible] for Cor to Sec. 34 and 35.

Land level; #

Soil 1st rate;

Timber a few Cottonwoods

Heavy undergrowth

Augmented on 80 ch's.

Thence on 2nd Stand Par. South.

East on S. side Sec 35.

[illegible] leave Bottoms

[illegible] Gulch drains N.

[illegible] Set chained Cottonwood post.

[illegible] Gulch drains N.

[illegible] Set chained Cottonwood post 4 x 4 in, 4 ft long.

Ind. Stand. Pac. T. R. 18 E.

Ind. Sta

BOOK-A-162

Left dip marked one
Notch on E. 5 on W. Six on
and P.C. on S. side, with
reg. mound and pits for cor
to Sec. 35. and 36.

Land, mostly broken
high Plateau;
Soil, 2nd rate
Timber, a few
Cottonwood on River with
heavy underpinnings.
Augmented on 80 chs.

East on S. side Sec. 36.
Va 16° 30' E.

22.30 Gulch drains N.W.
40.00 Set Sand stone 11×10×9 bu
dup. marked 4 on N. side
with stone mound for 1/4 sec

44.80 Su
61.00
80.00 S
dup
and
Stone
Tp
Lan
Ag
Th
18.50
37.20
40.00

Ind. Stand. Pap. I. R. 19

BOOK A 162

44.80 Gulch drains N.E.

61.00 " " N.W.

80.00 Lt Sand Stone 15×10×8–10 in

dip, marked 6 Notches on N.E.

and W. Side and S.C. with

Stone mound for Stand. Cor. to

Tp. 10 S., R. 18 & 19 E.

Land, broken plateau;

Soil Gudrate;

No Timber;

Augmented on 80 ch.

Thence:

Through Range 19 East.

East on S. Side Sec. 31

Va 16°30' E

18.50 Gulch drains N.E.

37.20 " " "

40.00 Lt Sand Stone 20×10×10,

Book 162 BOOK-A-162

and Standard Parallel South
and Offsets

Township Through R. 19 East

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36
398	399	400	401	402	404

15 in. deep, marked 1/4 on N. side with stone mound, for 1/4 Sec. Cor.

54.25 Gulch drains N.
64.75 " " N.W.
80.00 Set chained cottonwood post 4 x 4 in. 4 ft. long 2 feet deep marked 6 Notches on N. 5 on E. on W. & S.C. on S. Sides with legular mound and pits for Land.
Cor. to Sec. Hand 32
Land broken plateau
Soil 3rd rate
Cottonwood
Augmented on 80 ch.

East on S. Side Sec. 32
Va 16° 30' E.
7.25 Gulch drains N.E.

11.00 Sec
deep
1/4
51.40 Gu
80.00 Se
bi
on
on
fr
4.00 S
11.00

Salt Lake Meridian

BOOK A 162

11.00 Set Sand Stone 12 x 9 x 6, 8 in. deep, marked 4 on N. side, with Stone mound for 1/4 sec cor.

51.40 Gulch drains N.W.

80.00 Set Sand stone, 11 x 10 x 9, 6 in deep, marked 6 Notches on N. 4 on E., 2 on W. and S.C. on S. side with Stone mound for stand cor to Sec. 32 & 33.

Land high broken plateau

Soil Indrate

No Timber

Augmented on 80 chs

East on S. side sec 33

Va. 16°30' E.

4.00 Gulch drains N.W.

11.00 " " N.E.

2nd Stand. Par. S. R. 17

40,00	Set chased cottonwood pr. 4 x 4 in. 4 ft long, 2 ft deep marked 1/4 Sol. N. Side [illegible] Stone mound for 1/4 Sec. cor.	10,00	40
		34,00	
		40,00	Mar
			5 x 3
			N.
			1/4
80,00	Set chased cottonwood post 4 x 4 in. 4 ft long, 3 ft deep marked 3 Notches on E. & W. on N. and S. C. on S. Side with regulation mound and pits for Stand. Cor. to Sec. 33 & 34. Land high, broken plateau Soil Ist rate Mr Trimber Augmented on 80 chs	61,00	3
		80,00	Set
			Dup
			Hon
			with
			to
	Cast on S. Side Sec. 34, Va 16.30 E.		
1,50	A Boulder 30 ft. dia.		
2,00	Hollow drains N.	5,00	

BOOK-A-162

Salt Lake Mid[illegible]

10.00	Hollow deaves A.
34.00	" " A. W.
40.00	Marked Stationary sand stone, 5×3×2 ft above ground, 1/4 on N. side with Stone mound, for 1/4 sec cor.
61.00	3 point of sand stone ridge
80.00	Set sand stone 14×10×4, 9 in deep, marked 6 Notches on N. 4 on E. 2 on W. and S. C. on S. side with stone mound for Stand cor. to Sec. 34 and 35

Land, high, broken plateau, Soil 3rd rate; No timber; Ingrounded on 80 chs.

East on S. side Sec 35.
Va 16° 30' E.

5.00	S. point Ridge, bearing

Ind. Stand. Par. S. Rig E.

16.75	Hollow drains N.W.
40.00	Set Sand Stone 12×10×5, 8
	deep, marked 1/4 on N. Side
	with Stone mound for 1/4 Sec
41.40	Hollow drains N.W.
52.75	" " N.
79.75	" " N.W.
80.00	Set Sand Stone 48×18×4
	2 ft deep, marked 6 Notches
	on S. 1 on E. 5 on W. and S.
	on S. Side, with Stone mound
	for Stand. Cor. to Sec. 35 & 36
	Land High, broken plateau
	Soil 3rd rate;
	No Timber
	Augmented on 80 chs.

BO

Salt

	O
25.00	As
32.00	A
36.60	Ele
40.00	S
	in
	Sa
	1/4
65.50	
73.00	
80.00	S
	1
	o
	n
	1/
	2

Salt Lake Meridian

Easton S. Side Sec. 36.
Va 16° 30' E.

25.00	Ascend
32.00	Ridge bears N & S.
36.60	Enter plateau.
40.00	Set. Sandstone 20 x 10 x 6, 15 in dup, marked 1/4 on N. Side, with Stone mound for 1/4 Sec. Cor.
65.50	Wash Hollow drains N.E.
73.00	" " "
80.00	Set. Sand stone 24 x 20 x 4, 15 in dup, marked 6 Notches on N. E & W. and S.C. on S. Side, with Stone mound, for Stand. Cor. to Tps. 10 S. R 19 & 20 E.

Land high, broken plateau,
Soil 3rd rate
Ur T. in br
Augmented on 80 chs.
Oct. 10. 1879

Lord Stand Par. S. R. 20 E.

Thence in Range 20 East

East on S. Side Sec. 31.

Var 6° 30' E.

Note: As the line East falls into the Willow Creek Breaks rendering chaining impracticable, I measure — bars North 20 chs and 30 chs. and South 30 chs, from which a flag set in line across breaks bears: S. 86° 16' E. S. 84° 25' E., and N. 84° 26' E. respectively. making distance as calculated: 307 chs = 3 M. + 67 chs.

40.00 falls in Triangulation. Not set.

80.00 " " " "

Land broken ledge masses

Soil Erd rate

Ad Timber

40.00

80.00

40.00

80.00

Book 162 BOOK-A-162

2nd Standard Parallel South

~~Township~~ Through R. 20 E.

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36
405	406	406	407	408	409

BOOK-A-162

Augmented on 80 chs.

Easton S. Side Sec 31
Va 16° 30' E.

40.00 falls in foregoing triangulation, not set,

80.00 falls in triangulation not set.

Sand broken sand
Stone ledge breaks,
Soil 3rd rate
No Timber

Augmented on 80 chs.

Easton S. Side Sec 33.
Va 16° 30' E.

40.00 falls in foregoing triangulation not set.

80.00 falls in triangulation

Ind. Stand. Par. S. R. 20 E.

Notes:

Sand, broken Sand

Stone Bluffs:

Soil, 3rd rate;

no Timber

Segmented on 80 chs.

Eastern S. Side Sec 34.

Va 16° 30' E.

40.00 falls in Foregoing Triangulation

Not Set.

67.00 Flag point triangulation to

Set Sand Stone 14 x 8 x 5, 9 in dup,

marked 1/4 W. C. on N. Side

with Stone mound for witness

1/4 Sec cor.

75.00 Gulch drains S.W.

80.00 Set Sand Stone 36 x 12 x 4, 20

in dup, marked 2 Notches

on

and

Sta

3

Au

6.50

16.50

40.

53.00

80.00

Sand

4;

ber

ulation

in dup

side

ribun

20.

ches

on E., 4 on W., 6 on N.,
and S.C. on S. side,
with Stone mound for
Stand. Cor. to Sec. 3 and
35.

Land broken plateau
Soil Erdrote
No Timber
Augmented 80 ch.

East on S. side Sec. 35
Va 16° 30' E.

6.50 Hollow drains N.W.
16.50 " " "
40.00 Set Sand Stone 12 x 12 x 4, 8 in
deep, marked 1/4 on N. side,
with Stone mound,
for 1/4 sec cor.
53.00 Hollow drains N.W.
80.00 Set Sand Stone

Ind Stand Par. S.R. 20 E.

16 x 8 x 6, 11 in dup
marked 6 Natchison N.
1 on E, 5 on W. and
S.C. on S. sides with
Stone mound for Stand
Cor to Sec. 35 and 36.
Land broken plateau
Soil 3rd rate
No Timber
Augmented on 80 chs.

Eastern S. side of
Sec. 36.
Va 16° 30' E.

5.00	Hollow drains N.
14.40	" " N.E.
37.00	" " N.W.
40.00	Set Sand Stone 10 x 10 x 7
	6 in. dup, marked 1/4

S. L. Meridian

on N. Side, with Stone
mound for 1/4 Sec. Cor.
50,00 Walker drains S.W.
80.00 Set Sand Stone 20×10×6
15 in dep, marked 6 Sot-
-ches on N. E. & W. ~~edge~~
and S. C. on S. Side,
with Stone mound
for Standard Cor
4 Tps. 10 S., R 20 & 21 E.
Land, broken plateau,
Soil Zoo rate,
No Timber
Augmented on 80 chs.
Oct 11th 1879.
~~A. D. Green dep. Inc.~~

Note. This point offering
a convenient place for
the Green River Guide

Second Stand. Par. S., R. 3 E.

Meridian, and the land further East not being immediately available, I abandon the 2nd Stand Par. S. here and proceed to Among the Green River Guide Meridian.

General Description

The land along the whole extent of the 2nd Standard Parallel South here surveyed is of a mountainous character covered with fine bunch grass without timber and not available for anything but grazing purposes at the present time (1879)

There are numerous indi-

cations of the existence
of bed of coal, asphaltum
and mineral wax,
but the great scarcity of
water did not permit
us to make any explorations
for these substances.

A. D. Fenon.

Asp. Sur.

BOOK-A-162

4/3

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, Feb 24 1880

The foregoing field notes of the survey of the

2nd Standard Parallel S.
and offset, through Rs 18, 19 and 20 E.

~~Township No~~ ~~Range No~~

of the Salt Lake Meridian, Utah Territory,

Executed by A. D. Ferron

Under his Joint contract No 92

of the 13th *day of* June 1879.

in the month of October 1879

having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.

Frd. Salomon

U. S. Surveyor General for Utah.

BOOK-A-162

R: 1880. (162) 414

Copied

Filed Jany 16th 1880.

Examined by T. C. Bailey

Compared by T. C. Bailey

FIELD NOTES

OF

THE SURVEY OF THE

First Standard Parallel South

~~of Township No.~~ through, Range No. 2 & 5 E

of the Salt Lake Meridian in Utah Territory.

BY

E. Bielenski

U. S. DEPUTY SURVEYOR,

Under his Contract No. 92

dated June 13th 1879.

Survey commenced Sept 30th 1879.

Survey completed Oct 12th 1879.

Book 162 BOOK-A-162

First Standard Par. South

~~Township~~ through R. 24 E.

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36
415	417	418	419	420	421

BOOK-A-162

Standard Parallel S. R. 24 E. 5th

Survey Commenced Sept 30/79

By E. Baeltner

U. S. Deputy Surveyor.

From the Corner to Sec. 5 & 1

R 23 & 24 E, established last season by A. D. Ferson Sig.

Sandstone 20x8x7in. P&M.

~~[illegible]~~

agreeing with the description furnished me by the Office

I run

E on S side of Sec 31

Va 16° 30' E

In Cedars

.75 Leave Cedars enter Sandstone breaks

.50 Top of Perpendicular Bluff bears N & S

.00 At foot of Bluffs; Marked

Standard Parallel S R 24

	Sandstone 4 x 8 x 12 above ground - mark 1/4 on N side with stone mound for 1/4 sec cor
55.60	Dry bed of Cliff Creek 2 Chs in Canon, drains North.
70.00	Enter Swamp & heavy Hardwood
75.50	Leave same, ascend
78.00	Central White River Indian Trail bears N & S E.
80.00	Set sandstone 12 x 10 x 6, 8 in marked 1 notch on W. & 5 on & 6 on N edges & S.C. for Stone Cor to secs 31 - 32
	From which
	J Edwards Cabin & Sulphur Spring bear N 60 E 12 Chs dist.
	A Mineral Spring bs N 60° E 20 Chs
	Land: Broken Lot
	Soil: 3rd rate

BOOK-A-162

	Am
	Augr
	E, o
0.50	Spring
	deep
0.00	Set C
	Mar
	Mou
	Sch
2.00	Enter
8.00	Enter
	Cea
0.00	Set
	15 in
	on W
	& S C

OCK 162

Timber; Cedars on N. end
Augmented on 80 chains.

E. on S. side sec. 32
Va. 16° 30' E.

.50 Spring branch 3 lks. wide 6 in
deep. runs S.W.

.00 Set limestone 15 + 12 + 3 10 in deep
marked ¼ on N side with
mound of earth from 3
pits 24 + 12 + 12 for ¼ sec. cor.

.00 Enter Cedar ridge bis N. S.

.00 Enter hollow drains S.W.
leave scattering Cedar.

.00 Set sandstone 20 + 15 + 12
15 in deep marked 2 notches
on W. on E. and 6 on N. edges
+ S.C. with stone mound for

Standard Parallel

Standard Cor to Secs 32 & 33
Land, (Mountainous)
Soil 2nd & 3rd Rates
Timber, Scattering, Cedar
Augmented on 80 chains

E, on S side of Sec 33
Va, No 30 E,

1.45	Leave hollow,
40.00	Set Sandstone 30 x 24 x 1
	20 in deep marked 1/4 on N
	side with stone mound
	for 1/4 Sec cor; in deep
	hollow drains S.
50.00	Ridge bears N & S.
52.00	Hollow, drains S
71.00	" " "
80.00	On N side of hollow dra
	Set Sandstone 15 x 10 x 5 10

Oct. 24 E. S. L. Dr

OCT. 1 182

deep marked 3 inches on
E & W & 6 on N edges & S.C.
with stone mound for stand
Cor to Secs. 33 & 34.
Land; Mountainous.
Soil 2nd & 3rd Calcs
Timber, Scattering Cedar & pine
Augmented on 80 Chains

E. on S side of Sec 34
Vee 16° 30' E.

5.00	Ascend
3.00	Ridge bears N & S
7.80	Birch Creek 2 lks wide 6 in
	deep, in deep hollow runs S
1.50	Ridge bears N & S
7.50	Foot of Ridge enter Cedars
10.00	Set Sandstone 12 x 10 x 8, 8 in
	deep marked from N side

Standard Parallel

	with Line Ground for
	In Sec. [illegible]
51.50	Wash drain.
59.00	" " "
77.50	" " "
80.00	Set Grey Sandstone 15 + 15 + 5.00
	10 in deep marked [illegible] 0.00
	on E and 2 on D and [illegible] 2.00
	D edges + S C with [illegible] 0.00
	Ground for Standard [illegible]
	to Secs 34 & 35
	Land Mountainous
	Soil 3rd Rate
	Timber Scattering Cedar
	Augmented on 80 chai
	E on Side Sec 35
	Ca 16° 30' E
4.50	Wash drain. S W

0.50	Dash drains S.W.
0.00	Set Landstone 24 x 12 x 6. 18 in deep marked from N. side with Stone mounted for M. Sec. Cor.
5.00	Dash drains S.W.
0.00	" " "
2.00	" " "
0.00	Set Landstone 18 x 12 x 6, 12 in deep marked 5 mtrks on W. 1 on E & 6 on N edges & S.C. with Stone mounted for Standard Cor. & Lies 35 & 36.
	Land: Mountainous. Soil: 3rd Date. Timber: Scattering Cedar. Augmented on 80 chai

Standard Parallel

E on S side Sec 36

Va 16° 30' E

13.00 Dark drains S

25.50 " " "

40.00 Sec Sandstone 24+10+6 ft

in deep marked from N

side with Stone mound

for 1/4 Sec cor

33.00 Dark drains S

71.50 A Cone Sandstone 30' high 30' d

80.00 Sec Sandstone 20+12+10 ft

in deep marked 6 witches

on N E & W sides & S C, with

Stone mound for Standard

Cor to to Tps 5 S R 24 & 25 E

Turn which

A Cedar 12 in dia bis N 15° W 11 Ft

" " 12 " " N 45° E 12

" " 6 " " S 75° W 26

All marked according to Instructions

BOOK-A-162

OOK-A-162

Land: Broken
Soil: 2nd Rate
Timber: Cedar & pine
Augmented on 8 chains

Sept 30th 1879

General Description

The Ip Lot of Land [illegible]
high plateau suitable for
Varying purposes
The Ip South embraces part
of dug up and Cliff Creek
Valleys; also some timber-
lands which should be
subdivided

Standard Parallel N.R. 22

BOOK-A-162

	E. on S side Sec 31		
	Sec 16° 30' E	.50	
14.00	Gulch drains S	3.50	
39.00	" " "	0.00	Set
40.00	Set sandstone 20 + 18 + 6		Sec
	15 in deep marked 1/4 in		Sec
	A side with stone mou		Sec
	for 1/4 Sec cor	6.20	
73.00	Cedar timber	5.00	
80.00	Set sandstone 12 + 10 + 6	0.00	Set
	8 in deep marked 1 North		on
	on E + 5 on W + 6 on N side		Wa
	and S O for Stand Cor		+
	Sec 31 + 32		32
	Land Broken + rocky		
	Soil 3rd rate		
	Timber Cedar + pine		
	Augmented on 80 chain		

Book 162 BOOK-A-162

1st Standard Parallel South

~~Township~~ Through R. 25 E.

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36
424	425	426	427	428	429

OOK-A-162

...tte ... R. 25. E. ... S L Dr

E on S side Sec 32

Va 16° 30' E

...50 Gulch drains S

3.50 " " "

0.00 Set Sandstone 18+12+6, 12 in deep marked ¼ on N side with stone mound for ¼ Sec cor.

6.20 Gulch drains S

5.00 " " "

0.00 Set Sandstone 20+20+8, 15 in deep, marked 2 notches on W and 4 on E + 6 on N sides + SC for Standard Cor & Secs 32 + 33

Land, broken Mountainous Soil 1st 2nd rates

Timber, Scattering Cedar

Augmented on 80 chains

Standard Parallel

E. on S side Sec 33

Sec 16° 30' E.

37.20 Gulch drain

40.00 Set Sandstone 20 + 12 +

15 in deep marked 1/4

N side with stone mon

for 1/4 sec cor 5.00

44.00 Enter Cedar ridge, lo 0.00

& rocky bear N & S

53.00 Top of ridge bear N

57.20 Foot of same; Gulch dr

69.00 Cedar ridge bear N & 2.50

71.50 Gulch drain. S.W. 2.50

80.00 Set Grey Sandstone 12 + 10 9.50

8 in deep marked 3 sides 2.00

on E & W & on N sides & S 5.00

for Standard Cor to Sec

33 D 34

Land; Broken

Soil; 2 & 3 Sales

BOOK-A-162

OCK-..-162

Timber Dwarf Cedar
Augmented on 80 Chains

E. on S side Sec 34
Va 16° 30' E

Cedar Ridge bro N E & S W.
Marked Stationary Sandstone
24" x 20" x 10" - Above ground - 1/4
on N side for 1/4 sec cor
(with stone mound).
Gulch drains S
Sand Stone 25 ft high
Gulch drains S W.
Ceare Cedars
Set sandstone 14 x 8 x 6, 6
in deep marked 4 notches
on N. 2 on E & 6 on N sides
& S C with mound of earth
from 3 pits 24 x 12 x 12 for

Standard Parallel N 25

Standard Cor to Secs
34 & 35
Land Mountainous
Soil 3rd Rate
Timber & Oatlein Cedar
Augmented on 80 Ch

E. on S side Sec 35
Vu 16° 30' E.

5.50	Enter Cedar Hills
26.80	Gulch drains
35.00	Sandstone 120 ft high
40.00	Set Sandstone 14 x 6 x 5
	Qu deep marked 1/4 on
	S side with Mound of
	earth from 3 pits 24 x 12
	for 1/4 Sec cor
43.00	Leave Cedars
59.20	Wash drains

BOOK-A-162

	Wash drains S
6.00	Euler Cedars
6.00	Coarse Cedars
0.00	Set sandstone 14 + 12 + 4
	9 in deep marked 1 notch
	on W 5 on E + 6 on N sides
	+ S C with mound of
	earth from 3 pits 24
	+ 12 + 12 fr Standard on
	Tees 35 & 36
	Land Mountainous
	Soil, 1 + 2 Dale,
	Timber Scattering Cedar
	Augmented on 80 chains

E on S side Sec 36
Sta 16° 30' E

8.80	Wash drains S W
19.00	Gulch " "

BOOK-A-162

R: (162) 433

Filed 187 .

Examined by T. C. Bailey

Compared by O. E. S. and F. L. A. G.

FIELD NOTES

OF

THE SURVEY OF THE

Green River Grid Meridian

of Township No. 6, 7, 8, 9 & 10, Range No. 20 & 21 E.

of the Salt Lake Meridian in Utah Territory.

BY

A. D. Ferron

U. S. DEPUTY SURVEYOR,

Under his Contract Joint No. 92

dated June 13th 1879.

Survey commenced Oct 11th, 1879.

Survey completed " 14th. 1879.

1 Standard Parallel S R 25

23.50	Camp Creek 3 Chs wid
	Oil deep Runs S W in deep
	hollow.
35.70	Bear Ears & Blue Mountain
	Bail bears N E & S W.
40.00	Cedar Sandstone 12+10+4, 8
	deep marked ¼ on N
	with Stone mound for
	¼ Sec cor.
41.00	Cubes Cedars; thence al
	½ foot of Cedar ridge
	A Gulch drains N 2 Chs the
	W. heads E.
62.50	Cave Gulch heads S E
80.00	Ridge bears N 50° W.
	Cedar Sandstone 15+12+4 N
	deep marked 10 cor Ctrs
	on N E & W sides + S E with
	Stone mound for cor to
	Tps 5 S R 25+26 E.

BOOK-A-162

A Ceda
dist
(Ho
Ima
Ceda
The
Ind
The
Ch
Cau
Air

BOOK 1-162

from which

A Cedar 10 in dia bs N 45 E 10 lks dist marked according to instructions (No other trees suitable for marking)

Land, Mountainous

Soil, 2nd Rate

Timber, Scattering Cedar

Augmented on 80 chains

Oct. 12th 1879

General Description

The Lp N of this line falls in unavailable high plateau. The Lp S embraces part of Elk Valley & some timber lands and should be subdivided

E Buettner

Blank

Page

Green River Guide Meridian
BOOK-A-162 Tps. 10 S. R 20 & 21 E.

Oct. 11th 1879

Survey commenced by A. D. Ferron

From the Stand. Cor to Tps. 10 S., R 20 & 21 E., established by me this day. Trim North bet. Sect. 31 and 36. Va 16°30' E.

40.00 Set Sand Stone 16 x 12 x 6, 11 in deep, marked 1/4 on W. side, with Stone mound, for 1/4 sec cor.

67.00 No Clear drains N. W.

77.00 " " N. E.

80.00 Set Sand Stone 17 x 11 x 7, 11 in. deep, marked 5 Notches on N. and 1 on S. edges, with Stone mound for Cor to Sec. 25, 30, 31 and 36.

Land broken plateau

BOOK-A-162 Book 162

Green River Guide Mer

Township 10 S. let R. 20 & 4 E.

6	5	4	3	2	1	437
7	8	9	10	11	12	438
18	17	16	15	14	13	437
19	20	21	22	23	24	436
30	29	28	27	26	25	435
31	32	33	34	35	36	434

Green River Guide Meridian

Soil, 3rd rate;

No Timber

Augmented on 80 chs

North bet. Secs. 25 & 30

Ca 16°30' E

13.00 Hollow drains N.W.

33.75 " " N. E.

40.00 Set Sand Stone 14 x 8 x 8, 9 in

deep, marked 4 on W. side

with Stone mound for 7 Sec.

54.00 Hollow drains N.W.

61.00 " " N. E.

80.00 Set Sand Stone 18 x 8 x 6, 12

in deep, marked 4 Notches

on N. and 2 on S. edge, with

Stone mound for Cor. to Secs. 19, 24

25 and 30.

Land, broken plateau;

Soil, 2nd rate;

BOCK-A-162

Tr. 10 S., Lat. R. 20 & 21 E. 436

No Timber

Augmented on 80 chs.

North bet. Sec.s 19 and 24.

[illegible] 16°30' E.

17.50 Hollow drains N.E.

29.00 " " E.

[illegible]00 deposited small cobble stone, marked with cross (+) in reg. mound and pits, for 1/4 sec. cor.

33.00 Hollow drains N.E. fork, heading S.W. & S.E.

80.00 Set. sand stone 18 x 12 x 4, 12 in deep, marked 3 Notches on S. and E. edges, with reg. mound and pits for Cor. to Sec.s 13, 18, 19 & 24.

Land broken plateau;

Soil, 2nd rate;

No Timber;

BOOK-A-162

Augmented on 80 chs.

North bet. Secs. 13 & 18
Ca 16° 30' 6.

22.00 Hollow drains N.W.
110.00 Set sand stone 14 x 7 x 6.
Pin deep, marked 1/4 on N. side
with peg. mound and pits
for 1/4 sec. cor.
54.50 Wash drains N.W.
80.00 Set. Set sand stone 12 x 10 x 6
Pin deep, marked 2 Notches
S. and 1 on S. edge with
peg. mound and pits for cor.
to Secs. 7, 12, 13 & 18.
Land, broken plateau;
Soil, 2nd rate
No timber

Augmented on 80 chs.

Spec. S., bet. R. 20 & 21. E.

North bet. Sec.s 7 and 12,
Va. 16° 30' E.

30.75 Hollow drains West.
35.00 Hot of sand stone ledges
bears N.E. & S.W.
38.50 Top of same
40.00 Set sand stone 20 x 12 x 6,
15 in. deep, marked on W.
side, with stone mound
for ¼ Sec. 100.
61.00 Hollow drains N.W.
70.00 " " W.
80.00 Set sand stone 18 x 6 x 4,
14 in. deep, marked, which
on N. and S. edges, with
Reg. mound and pits for
Cor. 4 Sec.s 1. 6. 7 & 12.
Land broken plateau;
Soil, 2nd rate;
No timber
Augmented on 80 ch.

Green River Guide Meridian

BOOK-A 162

North Lat. 30 S. 1 and 6.

Var. 6° 30' E.

13.00 Hollow drains N.E.

40.00 Set Sand Stone 26 x 12 x 15, 18 in deep, marked 1/4 on W. side, with stone mound first see cor.

41.00 Hollow drains N.W.

80.00 Set Sand Stone 24 x 12 x 15 18 in deep, marked 6 Notch on N. S. E. and W. edges, with peg. mound and pits, for cor. to Tps. 9 & 10 S. R. 20 & 21 E.

Land broken plateau

Soil 2nd rate

No Timber

Augmented on 80 chs.

Oct 11th 1879

BOOK-

Tp. 10 S.

BOOK-A 162

Tps 10 S., R. 20 and 21 6.

General Description

The land on both sides of this line consists of broken, uplands unsuitable for cultivation.

There are good indications of coal, asphaltum and Mineral wax along the entire line.

Green River Guide Meridian

North bet. Sec. 31 & 36
in 16°30' E.

40.00 Set sand stone 20 × 12 × 6, 15 in. deep, marked 1/4 on W. side with stone mound for 1/4 sec. cor.

119.75 Hollow drains N.W.

80.00 Set sand stone 18 × 6 × 5, 12 in. deep, marked 5 Nos. on N. and 1 on S. edges, with reg. mound and pits for Cor. to Sec. 25, 30, 31 and 36.

Land broken plateau, Soil 1st rate

No timber

Augmented on 80 chs.

North bet. Sec. 25 and 30.
in 16°30' E.

40.00 Hollow drains N.E. Set,

BOOK-A-162

Green River Guide Meridian

Township 9 S. bet **R.** 20 & 21 E.

6	5	4	3	2	1	4-4-5
7	8	9	10	11	12	4-4-
18	17	16	15	14	13	4-4-3
19	20	21	22	23	24	4-4-2
30	29	28	27	26	25	4-4-
31	32	33	34	35	36	4-4-

BOOK-A-162

Sp. 9 S., R. 20 & 21 E.

Sand stone 16×10×4, 11 in. deep, marked 4 on W. side, with stone mound, for ¼ sec. cor.

70.00 Gulch drains N.E.

80.00 Set sand stone 22×10×5, 17 in. deep, marked 4 Notches on N. and 2 on S. edges with stone mound, for Cor. to Sec.s 19. 24. 25 and 30.

Land, broken plateau;
Soil Erd rate;
No Timber;
Augmented on 80 ch's.

North bet. Sec.s 19 and 24
to 6° 30' E.

5.00 Hollow drains N.W.

10.00 Set sand stone 20×6×5

Green River Trade at Vidian

15 in. d. p. marked 1/4 on
W. side, with Stone mound,
for 1/4 sec. cor.

61.50 Gulch drains N.W.

78.50 " " "

80.00 marked stationary & and Stone
48 × 30 × 30 in above ground 3 Notches
on N. & S. edges with Stone mound
for Cor to Sec. 13. 18. 19 & 24,
Land, broken plateau;
Soil 3rd rate
No Timber
Augmented on 80 chs

North bet. Sec. 13 & 18
1 a 16° 20' E.

15.00 Gulch drains N.W.

26.00 " " W.

44.00 Set Sand Stone 13 × 8 × 6

BOOK-A-162

Gin-dup, marked 1/4 on
N. side, with Stone mound
for 1/4 sec cor.

7.00 Rocky reef bears E. & W.

80.00 Set Sand stone 22 x 12 x 10,
Gin dup, marked 2 Notches
on N. and 4 on S. edges, with
Stone mound for Cor to
Sec. 7. 12. 13 and 18.
Land broken plateau;
Soil, 3rd rate;
No Timber
Augmented on 80 chs.

North Cut. Sec. 7 & 12
Va 16° 30' E.

2.00 Gulch drains N.W.

7.00 " " W.

40.00 Set Sand Stone 14 x 10 x 8

Green River Guide Meridian

Gindup, marked 4 on W. side
with stone mound for 1/4 sec.
75.00 Enter White River bottom
80.00 Set sand stone 14 x 12 x 5, 9
in dup, marked 5 Notches
on S. and 1 on N. edges,
with reg. mound and pits
for Cor. Sec. 1. 6. 7 and 12
Land, mostly broken plateau
Soil Indicate
No Timber
Augmented on 75 chs.

North bet. Sec. 1 and 6.
Va 16° 30' E.
17.00 Wash drains E.
40.00 Foot of bad land Hill
Set sand stone 26 x 12 x 16, 18
in dup, marked 1/4 on W.

Tp. 9 S. R 20 & 21 E.

Side with Stone mound,
for 1/4 Sec. cor.

11.50 Top of Still bear Eg W.

50.00 Foot of Same, enter feat.

70.00 White River 75 lks wide 4 ft deep
pure W.

72.75 White River 75 lks wide 4 ft deep,
pure E.

76.75 White River 75 lks wide 4 ft deep
pure W. Ground

80.00 Marked Stationary Sand
Stone 24 x 20 x 18 in. above
ground, marked C Notches on N. S.
E & W. edges with Stone
mound for cor to Tps
8 and 9 S. R 20 and 21 E.
Land, mostly bottom;
Soil Intrate
No Timber
Augmented on 10 chs.

Green River Guide Meridian

General Description

Most of the land on both sides of this line consists of high, broken plateau, The breakthrow indications of coal and asphaltum - The land is only valuable for its mineral contents

Tp 8

0.90

4000

45.50

58.50

60.00

BOOK-A-162

North bet. Sec.s 31 and 36.
Va 16° 30' E.

0.90 Enter flat.

4.00 Set chained cottonwood post, 4×4 in., 4 ft long, 2 ft. deep, marked 1/4 S. on W. side, with reg. mound and pits, for 1/4 sec. cor.

43.50 Road bears E. & W.

58.50 Enter high bench.

80.00 Set Sandstone 16×10×3, 11 in deep, marked 5 Notches on N. and 1 on S. edges, with reg. mound and pits for cor to Sec.s 25, 30, 31 and 36.

Land mostly level
Soil 1 strata

W. Trimber

North bet. Sec.s 25 and 30
Va 16° 30' E.

BOOK-A-162 Book 162

New River Guide Meridian

Township 8 S. let **R.** 20 & 21 E

6	5	4	3	2	1	452
7	8	9	10	11	12	451
18	17	16	15	14	13	450
19	20	21	22	23	24	449
30	29	28	27	26	25	448
31	32	33	34	35	36	447

449

Gunn River Principal Meridian

11.10	Walk diverse E.E.
35.00	Ascend
40.00	Set Sand Stone 18×8×3 12 in deep, marked 1/4 on W. side with Stone mound for 1/4 Sec Cor.
80.00	Set Sand Stone 12×12×10 8 in. deep, marked 1 Notches on N. and 2 on S. edges with Stone mound for Cor to Secs. 19, 24, 25 and 30. Land broken & level Soil 2nd rate Cor Timber Augmented on 45 chs
	North bet. Secs. 19 and 24. Va 16.30' E.
10.50	Gulch drains N.E.

BOOK

Tp 6

11.00	
35.00	
40.00	
80.00	
80.00	
16.20	
80.00	

BOOK-A-162

Tp 8 S. Bet. R. 2 [illegible]

14.00	Gulch drains N.E.
25.00	Enter Queen River flat.
40.00	Set Sand Stone 18 x 14 x 3, 12 in deep, marked 1 on W. Side with reg. mound and pits for ½ sec cor.
80.00	
80.00	Set Sand Stone 14 x 14 x 3 9 in. deep, marked 3 Natchuan N. and S. edges with reg. mound and pits for cor to Sec. 13. 18. 19 and 24.
	Land, level and broken; Soil, 1st and 3rd rate; No Timber
	Augmented on 25 chs.
	North bet. Sec. 13 and 18 Va. 16° 30' E.
16.20	Road bears E & W.
40.00	Set 4 mud [illegible] post

Tp. 45 [illegible] Green River Guide Meridian

4x4 in. 4 ft. long, 2 ft. deep, marked 1/4 S. on W. side, with reg. mound and pits for 1/4 Sec. Cor.

10.00 Set charred cottonwood post, 4x4 in. 4 ft. long, 2 ft. deep, marked 2 Notchson N. and 4 on S. edges with reg. mound and pits for cor. to Sec. 7, 12, 13 and 18. Land, level;

Soil 1st rate;

No Timber.

North bet. Sec. 7 and 12

Va 6°30' E.

20.00 Joe Jackson's Cabin bears W. 6 ch. dist.

40.00 Set charred cottonwood post 4x4 in. 4 ft. long, 2 ft. deep, marked 1/4 S. on W. side with

Sp. 8 S, bet. [illegible]

reg. mound and pits for
1/4 sec. cor.

45.00 Dave Bingham's Cabin, bear
East 40 lks. dist.

52.00 Enter Cottonwood grove

80.00 Set charred cottonwood post.
4 x 4 in. 4 ft. long. 2 ft. deep. marked
One notch on N. and 5 on S. edges
with reg. mound and pits
for cor. to Sec.s 1, 6, 7 and 12.

from which:

A cottonwood 12 in. dia. bear. [illegible] E. 53 lk. dist.
" " 14 " " " N. 58° W. 104 " "
" " 11 " " " S. 36° 30' W. 83 " "

all marked according to instructions
land level;

Soil, pt. rate;

No timber;

North bet. Sec.s 1 and 6.
Va 16° 30' E.

Green River Guide Meridian

33.00	Enter heavy brush.	
40.00	Set charred cottonwood post 4x4 in. 4 ft long, 2 ft deep, marked M.C. on W. side with reg. mound and pits for Cor.	
41.00	Set charred cottonwood post 4x4 in. 4 ft long, 2 ft deep, marked M.C. with reg. mound and pits for Meander Cor. on left bank of Green River 4 ft deep, mar. S.W.	
53.38	Set charred Cottonwood post 4x4 in. 4 ft long, 2 ft deep marked M.C. With reg. mound and pits for Meander Cor. on right bank of Green River	
80.00	Set grey sandstone 24x8x8 - 18 in deep marked 6 notches on N. S.E. E. & W. Edges with stone mound for Cor to townships 7 & 8 south. R. 20 & 21 E. A	

Land good bottom.

BOOK

Sp. 6 T.

"Note"

	25.00 L
	40.00 L
	45.00
	57.00
	59.00
	80.00

BOOK-A-162

Tp. 8 S. bet. R. 20 & 21 E. 454

Soil first rate

No Timber

Heavy undergrowth

Augmented on 45 chs.

"Note" For general description see Subdivisions of adjacent twps. October 13th, 1879

Tp. 7 S. bet. R. 20 & 21 E.

North bet. Sec. 31 and 36.

Va. 1.30 E.

25.00 Leave medow. Enter bench.

40.00 Deposited 1 qt of pebbles in reg. mound of earth and pits for 1/4 sec. cor.

45.00 Wash drains S. E.

57.00 Sand stone ledge bears E & W

59.50 Enter badland breaks

80.00 Set sand stone 36 x 24 x 12 - 20 in deep. Marked 5 Notches on N. and

BOOK-A-162 Box R 162

Green River Guide Meridian

Township 7 S. bet **R.** 20 & 21 E.

6	5	4	3	2	1	460
7	8	9	10	11	12	459
18	17	16	15	14	13	458
19	20	21	22	23	24	457
30	29	28	27	26	25	456
31	32	33	34	35	36	454

BOOK-A-162

1 on S. edge with stone
Mound for Cor. to Secs 25, 30,
31 & 36.
Land mostly level.
Soil 1st & 3d rate.
No timber
Augmented on 20.50 Ch.

North bet. Secs 25 and 30
To 16° 30' E.

40.00 Set sand stone 12 x 8 x 6, 8 in
deep. Marked 1/4 on W side
with stone mound for 1/4 Sec. Cor.

43.50 Right bank Green River 1 ft
deep runs E. Set Charred
Cottonwood post 4 x 4 in
1 ft long, 2 ft deep. Marked
M. C. with reg. mound & pits
for Meander Cor.

BOOK-A-1

61.00

80.00

Ascertained by triangulation
dist. across river to be
17.50 chs.

61.00 Left bank of Green River
Set charred Cottonwood post
4 x 4 in. 4 ft long, 2 ft deep
Marked "M. C" with reg. mound
and pits for Meander Cor.

80.00 Set charred Cottonwood
Posts 4 x 4 in, 4 ft long, 2 ft
deep. Marked 4 Notches on
N and 2 on S. Edges
with reg. mound & pits for
Cor to Secs. 19, 24, 25, and 30.

Land broken & rocky
Soil 3d rate
No timber
Augmented on 20 chs.

Green River Guide Meridian

North bet Sec's 19 and 24
Va. 16° 30' E.

33.00 Left bank Green River
4 ft deep. Sums W. set
Charred Cottonwood post.
4 x 4 in: 4 ft long, 2 ft deep
Marked M. C. with reg. Mound
and pits for meander Cor.
Ascertained by triangulation
dist. across River to be
13 chs.

46.00 Right bank of Green River
Set Charred Cottonwood
post. 4 x 4 in. 4 ft long
2 ft deep. Marked M. C.
with reg. Mound and pits
for Meander Cor.

80.00 Set Cobble stone 12 x 10 x 6
8 in deep, marked 3 notches on
N and S. edges with reg.

Tp 7

Note

6.00
20.00
40.00
65.25
80.00

BOOK-A-162 Tp 7 S. R 20 and 21. E 4618

Meridian
and 24
River
set
post.
ft deep
g. Mound
Cor.
gulation
tobe
River
od
long
N. C.
pits
10 + 6
ches on
g.

Mound and pits for Corto
Secs. 13, 18, 19, & 24

Note The 1/4 sec. Cor. falling in
River is not set.
Land broken and rocky
Soil 3d rate
No timber
Augmented on 80 Chs

N. bet Sec's 13 & 18
Va. 16° 30' E.

6.00 Hoclow drains East.
20.00 " " S. E.
40.00 Deposited 1 quart of pebbles
in reg. mound of earth and
pits for 1/4 sec. Cor.
65.25 Wash drains S. E
80.00 Set sand stone 10 + 10 + 8
2 Notches on N & 4 on S edges
6 in deep marked ~~[illegible]~~
with stone mound for Cor. Sec

Green River Guide Meridian

BOOK-A-162

7, 12, 13 and 18.

Land broken

Soil 2d rate

No timber

Augmented on 80 Chs

N. between Secs 7 and 12

Va. 16° 30' E.

18.00 Hollow drains N.E.

40.00 Set cobble stone 11 + 9 + 9, 6 in deep marked 1/4 on W. side with stone mound 1/4 sec. Cor.

70.00 Hollow drains N.W.

80.00 Set sand stone 14 + 10 + 8 9 in deep. marked 1 notch on N + 5 on S. Edges, with stone mound for Cor. see 1.6. 7. and 12.

Land broken

Soil 2d rate

Tp 7 S. R 20 and 21 E

BOOK-A-162

No Timber

Augmented on 80 Chs

N. bet. Sec's 1 & 6

Va 16° 30' E.

15.00 Hollow drains N.E.

27.50 Ridge bears N.E. and S.W.

40.00 Marked Stationary Stand Stone, 5 x 5 x 2 ft above Ground 1/4 on W. side with stone mound for 1/4 sec Cor.

80.00 Set Charred Cottonwood post 4 x 4 in, 4 ft long, 2 ft deep. Marked 6 notches on N. S. E. W. edges with reg. mound & pits for Cor to tps 6 & 7 so. range 20 & 21 E.

Land broken

Green River Guide Meridian

Soil 3d rate
No timber
Augmented on 80 Chs

Note For General Description
See Subdivisions of
Adjoining Tps

Tp. 6 S. bet. R. 20 & 21 E.

North bet. Secs. 31 and 36.
Va 16° 30' E.

17.00	Decend.
27.50	North East point of ridge
30.00	Enter flat.
36.50	Wash drains N.E.
39.50	" " N.W.
40.00	Set sand stone 14 x 12 x 6, 9 in deep. Marked 1/4 on W. side with stone Mound for 1/4 Sec. Cor.
41.25	Wash drains N.E.
42.50	Road bears N.W. and S.E.

Tp 6

80.00	Ge
	dec
	10
	fo
	C
	A
6.50	
10.25	M
17.00	
21.50	
28.00	
34.00	
40.00	
	d
	e

BOOK-A-162 Book 162.

Green River Guide Meridian

Township 68 Ser. R. 20 and 21 E.

6	5	4	3	2	1	466
7	8	9	10	11	12	465
18	17	16	15	14	13	464
19	20	21	22	23	24	463
30	29	28	27	26	25	462
31	32	33	34	35	36	461

BOOK-A-162

Tp 6 S R. 20 and 21 E.

80.00 Set sand stone 36 x 20 x 10 - 2ft deep. Marked 5 notches on N & 1 on S Edge, with stone mound for Cor. to Sec. 25, 30, 31 & 36.

Land level & Broken

Soil 1st and 3d rate

No timber

(Augmented on 30 Chs)

North bet Sec 25 and 30

Va. 16° 30' E.

6.00 Ascend

10.25 Wash drains S. E.

17.00 " " " "

21.50 " " " "

28.00 Ridge bears N.W and S.E.

34.00 Hollow drains S.E.

40.00 Set sand stone 12 x 5 x 6 - 8in deep. Marked 1/4 on W. side with stone mound for 1/4 Sec. Cor

Green River Guide Meridian

45.00 Wash in broad hollow drains E.
58.00 " drains S. E., leave hollow
76.50 Ledge ridge bears E & W
80.00 Set sand stone 13 x 8 x 7, 8 in deep marked 4 notches on N and 2 on S Edges, with stone mound for Cor. to sec. 19, 24, 25, and 30.

Land broken
Soil 3d rate
No timber
Augmented on 7/4 59 [illegible]

North bet. Secs 19 and 24
Va. 16° 30' E.

3.50 Enter hollow
13.40 Wash drains - E.
17.50 Leave hollow
31.00 Hollow drains. E.
40.00 Set sand stone 24 x 16 x 12

Tp 6 S. R. 20 and 21 E.

	18 in deep. Marked 1/4 on w side with stone mound for 1/4 Sec. Cor.
63.00	Hollow drains E.
80.00	Set sand stone 20 x 10 x 5 15 in. deep, Marked 3 notches on N and S. Edges with stone Mound for Cor to Secs. 13, 18, 19 & 24
	Land broken
	Soil 2d and 3d rate
	No timber
	Augmented on 80 Chs
	North bet. Secs. 13 and 18
	Var. 16° 30' E.
5.00	Hollow drains — E.
15.50	Road bears N.W. and S.E.
	Enter broad hollow
27.00	Leave hollow
40.00	Set sand stone 14 x 10 x 6 — 9 in

Green River Guide Meridi

✓	deep. marked 1/4 on W side with stone mound for 1/4 Sec. Cor.
74.00	Ridge bears NW and SE
80.00	Set sandstone 14 + 8 + 8, 9 in deep. marked 2 notches on N and 4 on S Edges, with stone mound ~~for~~ for Cor to Secs. 7-12-13 and 18.

Land broken

Soil 3d rate

No timber

Augmented on 80 Chs

North bet Secs. 7 and 12

Var. 16° 30' E

15.00	Sand stone ledge. 75 ft high bears E and W.
21.00	Wash drains S.W
38.50	Sand stone ledge 10 ft high bears E+W
40.00	Set sand stone 24 × 16 × 10

Tp

	18 m
	side
	Sec
53.00	Ho
75.00	
80.00	On
	as fo
	for
	A
	C
13.00	H.
28.00	
40.00	Se
	de
	W
	C

Tp C. S. R. 20 and 21 E
466

		18 in deep. Marked 1/4 on W. side with stone mound for 1/4 Sec. Cor.
	53.00	Hollow drains S. E.
	75.00	" " S. E.
	80.00	On sand stone Croppings. marked as follows:— 1 6 / 12 7 with stone mound for Cor 10 sec. 1. 6. 7 and 12.

Land broken
Soil 2d rate.
No timber
Augmented on 80 Chs.

North bet. Secs. 1 and 6
Var. 16° 30' E

	13.00	Hollow drains S. E.
	28.00	" " " "
	40.00	Set sand stone 16 x 12 x 8 11 in. deep marked 1/4 on W side with stone mound for 1/4 sec. Cor.

Green River Guide Men

45.00 Hollow drains S.E.

63.70 Intersect 1st standard par

S. 9.20 Chs E. of Standard

Cor. to Secs. 31 and 36

Aps 5 S R. 20 and 21 E.

where I set a sand stone

24 x 14 x 10, 18 inc. deep

Marked 6 notches on S.E.

W. sides and C.C. with

stone mound for Closing Cor.

to Secs. 1 and 6 Aps 6 S.

R. 20 & 21 E.

Land broken

Soil 3d rate

No timber

Augmented on 63.70 Chs

October 14th, 187

Note For general description see

Subdivisions of adjoining

Aps A.D. Ferrow

Dep'y Sur.

BOOK A 162 Tp E S. R- 20 and 21 E 468

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, Febry 24 1880

The foregoing field notes of the survey of the

Green River Guide Meridian

through *Townships No* 6. 7. 8. 9. & 10 *Range No* 20 & 21 E

of the Salt Lake Meridian, Utah Territory,

Executed by A. D. Ferron

Under his joint *contract No* 92

of the 13th *day of* June 1879

in the month of October 1879

having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.

Fred. Salomon

U. S. Surveyor General for Utah.

by T. C. Bailey O.K. 469

R: 1880 (162) Copied

Filed Sept 17th 1879.

Examined by T. C. Bailey

Compared by " " "

FIELD NOTES

OF

THE SURVEY OF THE

Segregated Agricultural lands in sections 3. 4 & 10

of Township No. 4 S. , Range No. 4 W.

of the Salt Lake Meridian in Utah Territory.

BY

Adolphe Jessen

U. S. DEPUTY SURVEYOR,

Under his Contract No. 94

dated August 25th 1879.

Survey commenced September 10th 1879

Survey completed September 11th 1879

See Comm. letter of Nov. 1 [illegible] Bailey [illegible]
[illegible] Bailey [illegible]

Book 162 BOOK-A-162

Seggregated Agricultural Lands

Township 4 S R. 4 W

6	5	4 472	3	2	1
			473		
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

OOK-A-162

FOR CHAINMAN.

We Chance McKendricks

and Thomas McLeod

do solemnly swear that we will faithfully execute the duties of chain carriers; that we will level the chain upon uneven ground, and plumb the tally pins, whether by sticking or dropping the same; that we will report the true distance to all notable objects, and the true length of all lines that we asssist in measuring, to the best of our skill and ability,

Chance McKendricks
Thomas McLeod

Subscribed and sworn to before me this 10th day of September 1879

Adolphe Jessen
U. S. Dep. Surveyor

BOOK-A-162

FOR FLAGMAN.

I, D. W. Reuck

do solemnly swear that I will well and truly perform the duties of flagman, according to instructions given me, and to the best of my skill and ability.

D. W. Reuck

Subscribed and sworn to before me this 10th *day of* September 1879

Adolphe Jensen
U. S. Dep. Surveyor

BOOK-A-162

FOR AXEMAN

I, George Gee

do solemnly swear that I will well and truly perform the duties of axeman, according to instructions given me, and to the best of my skill and ability.

George Gee

Subscribed and sworn to before me this 10th *day of* September 1879

Adolphe Jussen
U. S. Dep Surveyor

1470 BOOK-A-162

Segregated survey in secs 3, 10. Sp. 4

Survey commenced
September 18th 187

Note:

This survey intend
to embrace the agricultu
land in the narrow botto
of Settlement Canyon
presents special difficul
in the way of segregati
the mineral land from
the agriculture -

The large
Mining District of "Rust
Valley" with its numero
rich mines of Lead and
Silver is situated mainly
~~in~~ in secs. 17. 18. 19. 20
21. 28. 29 & 30 of this Town
ships and the Mountains
forming Settlement

BOOK-A-162

Canyon are said to show strong indications of Mineral Deposits -

Therefore in accordance with section 2330 Revised Statutes of the United States I proceed to survey in Ten acre lots the agricultural lands in & around the bottom of said canyon thereby Segregating the Mineral lands from the agricultural.

From the cor. to Secs 3 & 4 on N. Bound. of Tp. established by myself under my surveying contract No. 91

I rmd

472 BOOK-A-162

Aggregated Survey in sec. 4

Chains South bet. secs 3 & 4
Va. 17° 30' E.

4.50 Leave cultivated land,
Fence bears E. & W.

5.00 Assume hills bear N.W. &

10.00 Set Quartzite 14 x 9 x 6 in 9 in
deep marked with a cross
(+) on top with a stone mound for southeast co
of lot 1. in sec. 4

Land S. 5.00 chs. mountain
balance level field -
Soil 1st & 2nd rate
Timber heavy oak brush
on hill sides -

West on S. side lot 1
Va. 17° 30' E.

10.00 Set limestone 15 x 13 x 5 in
10 in deep marked with a
cross (+) on top, and mou

BOOK-A-162

BOOK-A-162

chains stone for S. W. cor. lot 1. sec. 4 -
Land mountainous on 10.00 chs -
Soil 2nd rate -
Timber Oak brush -

North on W. side lot 1.
Va. 17° 30' E
Descend.
10.00 Intersect N. Bound. of Tp. 10.00 chs. W. of cor. to secs. 3 & 4 where I set Quartsite 15 x 9 x 6 in 10 in deep marked with a cross (+) on top, and mound of stone for N. W. cor. lot 1 sec 4
Land mountainous on 10.00 chs
Soil 2nd rate - Timber oak brush

Segregated survey in sec. 3

chains

From the establishe
S.E. cor. of lot 1 in sec 3.
on line between secs 3 & 4
2 mm

East on S. side lot 1 (in sec
Va. 17°30' E.

Descend mountains

5.00 Fence bears N.E. & S.W.
enter bottom & field -

7.00 Mill Race runs Northwesterly

8.50 Settlement Creek 10 lks
wide 8 in deep runs Northerly

10.00 Set sandstone 9x8x6 in
5 in deep marked with a
cross (+) on Top, and stone
mound for S.E. cor. lot 1.
sec. 3.00 -

Land W. 5.00 chs mountain
ous -

Soil 1st & 2nd rate -

T. 4 S.
BOOK-A-1

BOOK-A-162

T. 4 S. R 4 W. S. L. Mer.

Timber heavy oak & maple brush in places

North on E. side lot 1.
Va. 17° 30' E.

1.00 Leave field, Fence bears N. W. & S E. –

1.25 Road bears N. W. & S E.

1.50 Ascend hills

5.50 Descend

7.50 Enter gulch drains W.

10.00 Intersect N. Boundary of Township 10.00 chs E. of cor. to secs 3 & 4 where I set a sandstone 14×12×7 in 9 in deep marked with a cross (+) on Top and stonemound for N. E cor to lot 1 in sec 3.

Land 8.50 chs mountainous –

Segregation Survey in sec. 3 -

Chains Soil 1st & 2nd rate -

Timber Oak, brush

From the establishe 10.00

S. W. corner to Lot 1 in sec

and S.E. cor. lot 1 in sec 4 2 m

South on W. side lot 2 sec

and on line bet. secs. 3 & 4.

Va. 17° 30' E

Descend.

3.50 Deep gulch draining W.

10.00 Set limestone 14 x 9 x 5 in

9 in. deep marked with a

cross (+) on top, and stone

mound for S.W. cor. lot 2

in sec. 3 -

Land 10.00 chs mountainous

Soil 2nd rate

Timber heavy Oak brush

Chains

0.50

4.00

6.75

T. 4 S. R 4 W. S. L. Mer.

BOOK-A-162

Chains East on S. side lot 2

Va. 17° 30' E

Descend

10.00 At foot of hills marked stationary Quartzite 3 x 2 x 2 ft. above ground with a cross (+) on top and raised a mound of stone for S.E. Cor. lot 2 sec. 3

Land 10.00 chs mountainous

Soil 2nd rate -

Oak Brush.

North on E. side lot 2

Va. 17° 30' E.

0.50 Fence bears N.W. & SE.; Enter field -

4.00 Mill Race runs N.W.

6.75 Settlement Creek 10 lks wide 8 in deep runs N.W. erly

Segregated survey in section

chains	
10.00	The E. cor. to lots 1 & 2 se
	Land nearly level.
	Soil 1st rate. —
	Oak brush in pla
	East on N. side lot 3
	Var 17° 30' E
0.50	leave field, Fence bears N.W.
0.70	Road bears N.W. & S.E.
0.75	Ascend hills
3.40	Rocky Point bears 1.00 ch. S.
	descend
5.00	Gulch drains S.W. ascend
10.00	Set limestone 16 x 14 x 8 in. 11 i
	deep marked with a cross (+) o
	top, and stone mound for
	N. E. cor. lot 3. sec. 3.
	Land E. 9.25 chs mou
	amons —
	Soil 1st & 2nd ra

Blank

Page

BOOK-A-162

432

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, Febry 24 1880

The foregoing field notes of the survey of the

1st Standard Parallel S.

Through *Range No,* 24 & 25 E

of the Salt Lake Meridian, Utah Territory,

Executed by E. Buettner

Under joint *contract No* 92

of the 13th *day of* June 1879

in the month of Oct 1879

having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.

Fred. Salomon

U. S. Surveyor General for Utah.

BOOK-A-162

T. 4 S. R. 4 W. S. L. Mer.

Timber oak brush

South on E. side lot 3.
Va. 17°30' E.

Ascend
2.00 Descend
9.90 Gulch drains N.
10.00 Set sandstone 12x7x6 in
8 in deep marked with a cross
(+) on top, and stone mound
for S.E. cor. lot 3 in sec. 3.
Land 10.00 chs mountainous
Soil 2nd rate.
Oak brush.

West on S. side lot 3
Va. 17°30' E

0.25 Small gulch drains westerly.
3.00 Foot of hills; Road bears N.W.
& S.E.

Segregated survey in section 3

Chains	
3.50	Fence bears N.W. & S.E., enter field.
6.50	Settlement Creek 10 lks wi[illegible] 8 in. deep runs N.Wearly
8.50	Mill Race runs N.W.
9.75	Fence bears N.W. & S.E., leave field.
10.00	The S. cor. to lots 2 & 3 sec 3
	Land E 3.00 ch mountainous
	Soil mostly 1st rate
	Brush in places -

From established S.E. cor. lot 3.

South on E. side lot 4.

Va. 17°30'E

Ascend

1.75	Descend S.W. slope
10.00	Set Quartzite 12 x 10 x 7 in 8 in deep marked with a cross (+) on top, and stone mound for S.E. cor lot 4 sec 3.

T. 4 S. R. 4 W. S. L. Mer-

chains Land 10.00 chs mountainous
Soil 2nd rate.
Oak brush.

West on S. line lot 4
Va. 17° 30' E.

0.35 Leave hill, Road bears N.W. & S.E.
0.50 Fence bears N.W. & S.E.
enter field.
3.20 Settlement Creek 10 lks wide 8 in.
deep runs N.W.
6.00 fence bears N.W. & S.E. -
leave field.
7.50 Ascend hills
10.00 Set sandstone 14 x 10 x 7 in. 9 in.
deep marked with a cross (+)
on top, and stone mound
for S.W. cor. lot 4 sec. 3.
Land 2.50 chs mountainous
Soil mostly 1st rate.

Segregated Survey in Section 3.

Timber Oak brush

North on W. side lot 4

Va. 17°30' E.

along E. slope of hill

10.00 The cor to lots 2, 3 & 4 sec 3.

Land 10.00 chs. mountainous

Soil 2nd rate -

Oak brush.

From the established S.W.

cor lot 4 sec 3 I run

South on W. side lot 5

Va. 17° 30. E.

3.00 Gulch drains E.

10.00 Set sandstone 12x9x6 in 8 in

deep marked with a cross (+)

on top, and stonemound for

S.W. cor. lot 5 sec. 3.

Land Mountainous on 10.00 chs.

BOOK-A

1.00

10.00

BOOK-A-162

S. 4 S. R 4 W. S. L. Mer

Soil 2nd rate -
Oak brush -

East on S. side lot 5
Va. 17° 30' E.

1.00 Descend in small gulch drains E.

5.00 Foot of hill, Fence bears N & S., enter field -

8.00 Settlement Creek 10 lks wide 7 in deep runs northerly

10.00 Set Quartzite 20 x 16 x 9 in 15 in deep marked with a cross (+) on top for S.E. cor lot 5 sec. 3. Land W. 5.40 chs mountainous
Soil 1st & 2nd rate -
Oak & Maple brush.

North on E. side lot 5
Va. 17° 30' E

Segregated survey in Section 3

Chains
3.10 "Left Hand Fork Creek" 8 lks wide in deep runs W.

7.00 leave field, fence bears N.W. &

8.50 Road bears N.W. & S.E.

10.00 The E. cor. to lots 4 & 5 sec 3.

Land mostly level.

Soil 1st rate.

Oak brush

East on N. side ~~Sec.~~ Lot 6

Va. 17° 30' E.

Ascend hills

10.00 Set Quartzite 14x9x6 in ground marked with a cross (+) on top, and stonemound for N.E cor. lot 6 sec. 3.

Land 10.00 chs mountainous

Soil 2nd rate

Brush in places

Chains

2.00

5.50

7.50

10.00

T. 4 S. R 4 W. S. L. Mer.

chains	South on E. side lot 6
	Va. 17°30'E
2.00	Descend S. slope.
5.50	Enter left hand fork Canyon
6.00	Road in same bears E & W.
7.50	Left hand fork Creek 8 lks wide 4 in deep runs W., ascend
10.00	On Top of Ridge bears W. set Sandstone 18 x 8 x 5 in 12 in deep marked with a cross +/- on top, and stone mound for S.E. cor. lot 6 sec. 3.
	Note: From this cor. surface croppings of big Iron ledge bears N. 76°30'E about 35 chs dist.
	Land 10.00 chs. mountainous
	Soil 2nd rate
	Oak brush

Segregated survey in section 3.

chains	West on S. side lot 6
	Va. 17°30' E
	Descend W. slope
5.00	Foot of hills, enter bottom
7.00	Road bears N.erly & S.erly
7.20	Fence " " "
	enter field –
10.00	The S. cor. to lots 5 & 6 sec. 3
	Land E. 5.00 chs Mountainous
	Soil 1st & 2nd rate –
	Oak brush –
	South on W. side lot 7
	Va. 17°30' E.
3.00	Settlement Creek 10 lks wide
	6 in deep runs N.W.erly
6.75	Leave field, Fence bears NW. & SE.
7.00	Ascend hills
10.00	Set sandstone 24 x 12 x 6 in 18 in
	deep marked with a cross (+)

on top, and stonemound
for S.W. cor lot 7 sec 3.
Land mountainous on 3rd chs
Soil 1st & 2nd rate.
Oak brush –

East on S. side lot 7
Va. 17° 30' E.

Descend
2.00 Foot of hills
2.05 Fence bears N.W. & S.E., enter field
2.85 Reach Spring bears South
60 lks dist –
6.20 Settlement Creek 10 lks wide
5 in deep runs N.W. erly
6.75 leave field, Fence bears N. & S.
7.00 Road bears N. & S., ascend hills
10.00 Set Quartzite 18 x 12 x 7 in 12 in
deep marked with a cross (+)
on top, and stonemound

Segregated survey in section 3

Chains	
	for S.E. cor. lot 7 sec. 3
	Land 5 on chs mountainous -
	Soil 1st & 2nd rate -
	Oak brush -
	North on E. side lot 7
	Va. 17° 30' E.
	Ascend S.W. slope
8.50	Small gulch drains W.
10.00	The E. cor. lots 6 & 7 sec 3.
	Land 10 chs mountainous
	Soil 2nd rate -
	Oak brush -
	From the established S.W.
	cor. lot 5 sec 3
	South on W. side lot 8
	Va. 17° 30 E.
0.50	Small gulch drains W
10.00	Set limestone 13 x 8 x 5 in

T. 4 S. R 4 W. S.L. Mer.

chains 8 in deep marked with a cross (+) on top, and stone mound for S.W. cor lot 9 sec. 3 —

Land 10.00 chs mountainous

Fair 2nd rate

Oak & Maple brush

East on S. side lot 8

Va. 17°30' E

Descend

10.00 The S. cor to lots 7 & 8 sec 3

Land 10.00 chs mountainous

Fair 2nd rate

Oak & Maple brush

From the established cor. to lots 7. 8 & 9

South on W. side lot 9

Va 17°30' E

Segregated survey in Sec. 3.

Chains	
4.50	Gulch drains E.
7.50	do do.
10.00	Set Quartzite 12 x 7 x 5 in 8 in dup marked with a cross (+) on top, and stone mound for S.W. cor. lot 9 sec 3
	Land 10.00 chs mountainous
	Soil 2nd rate
	Oak brush.

East on S. side lot 9

Va. 17° 30' E

Descend

5.00	Foot of hill, enter bottom
7.50	Settlement 10 lks wide 5 in dup runs N.W. Ely
9.50	Road bears N. x S.
10.00	Set sandstone 14 x 8 x 7 in 9 in dup marked with a cross (+) on top, and stone mound for

T. 4 S. R 4 W. S. L. Mer

BOOK-A-162

Chains S.E. cor. lot 9 sec 3
Land 5.00 chs. mountainous.
Soil 1st & 2nd rate.
Oak brush.

North on E. side lot 9
Va. 17°30'E
ascend S.W. slope
10.00 The E. cor to lots 7 & 9 sec 3
Land 10.00 chs mountainous
Soil 2nd rate
No timber —
September 10th 1879 —

September 11th 1879
From the established S.W. cor. to lot 9
South on W. side lot 10
Va. 17°30'E
5.00 ~~Gulch drains E.~~

Segregation Survey in section 3

Chains

5.00 Gulch drains E.

10.00 Set Quartzite 14x10x5 in 9 in dep
marked with a cross (+) on top
and stone mound for S.W.
cor. lot 10 sec. 3.
Land 10.00 chs mountainous
Soil 2nd rate -
Oak brush -

East on S. side lot 10
Va. 17° 30' E.

Ground

5.50 Foot of hills, enter bottom

7.75 Settlement Creek 10 lks wide
5 in. dep runs N.W.

9.00 Road bears N.W. & S.E.

10.00 Set blue limestone 12x11x4
8 in dep marked with a cross
on top, pile stone mound

BOOK-A-162

T. 4 S. R 4 W. S. L. Mer.

Chains for S.E. cor lot 10 sec 3
Land 5.50 chs mountainous
Soil 1st & 2nd rate
Oak brush

North on E. side lot 10
Va. 17° 30' E.
Ascend gulch S.W. slope
10.00 The E. cor. lots 9 & 10 sec 3
land undulating
Soil 1st rate
No timber

From the established S.W. cor.
lot 10 sec 3
South on W. side lot 11.
Va. 17° 30' E
7.50 Gulch drains E.
10.00 Intersect line bet secs 3 & 10
20 W. of ¼ sec cor. point on

Segregated survey in sec 3.

Chains	
	Quartzite 13x10x5in 8in deep marked with a cross (+) on top and stone mound for S.W. cor. lot 11, sec 3.
	Land 10.00 chs mountainous
	Soil 2nd rate
	Oak brush
	East on S. side lot 11 and on sec. line bet. secs 3 & 10
	Va. 17° 30' E.
	Descend steep E slope
6.75	Foot of hill, enter bottom
9.25	Settlement Creek 10 lks wide 5in deep runs N.
9.75	Road bears N. & S.
10.00	At a point 10 chs W. of ¼ sec cor. point set limestone 13x8x8 in 8in deep marked with a cross (+) on top, and stonemound for S.E. cor

T. 4 S. R 4 W. S. L. Mer.

Lot 11 sec 3.
Land W. 6.75 chs mountainous
Soil 1st & 2nd rate
Oak brush.

North on E. side lot 11
Va. 17° 30' E
Along level flat
10.00 The cor. to lots 10. 11. & 12 sec 3
Land level.
Soil 1st rate.
No Timber.

East on N. side lot 12
Va. 17° 30' E.
1.00 Ascend steep W. slope
6.00 to Quartzite 13 x 9 x 5 in 8 in dep
marked with a cross (+) on top,
and stone mound for N.E. cor.
Lot 12, sec. 3.

Segregation survey in sec 3

Land 10.00 ch mountainous
Soil 2nd rate
Oak brush

South on E. sign lot 12
Va. 17° 30' E.

7.00 Deep gulch drains N.
10.00 The 1/4 sec cor. point on sec line bet. secs 3 & 10 - Set blue limestone 16x10x4 in 11 in deep marked 1/4 on S. side with Monumental for 1/4 sec. cor. & SE. cor. lot 12 sec 3
Land 10.00 chs mountainous
Soil 2nd & 3rd rate
Oak brush

West on S. side lot 12
and on sec. line bet secs 3 & 10
Va. 17° 30' E

Chains
8.00
10.00

T 4 S R 4 W. S.L. Mer.

Chains	Descend steep W. slope
8.00	Foot of hills, enter bottom
10.00	The S. cor. betn lots 11 & 12 in sec 3
	Land 8.00 chs mountainous
	Soil 1st & 2nd rate
	Oak brush

Segregated Survey in sec 10 T. 4

Chains		Chains
	From S. cor. to lots 11	1.00
	& 12 in sec. 3 on line bet secs	1.50
	3 & 10. ten chs W. of ¼ sec. cor	10.00
	2 mon	
	South on W. side lot 1	
	Va. 17° 30' E	
2.00	Road bears N. 10° W. & S. 10 E	
6.50	Settlement Cr. R 12 lks wide	
	5 in deep runs N. W.	
8.75	same runs N. E.	
10.00	Set limestone 10 x 10 x 4 in	
	10 in deep marked with a	
	Cross (+) on top and stone	5.00
	mound for S.W. cor lot 1 sec 10	10.00
	Land undulating	
	Soil 1st rate	
	No timber	
	East on S. side lot 1	
	Va. 17° 30' E	

T. 4 S. R. 4 W. S. L. Mer.

Chains	
1.00	Road bears N. & S.
1.50	Ascend steep W. slope
10.00	Set Quartzite 14x9x5 in 9 in deep marked with a cross (+) on top, and stone mound for SE cor lot 1 sec 10
	Land 8.50 chs mountainous
	Soil 1st & 2nd rate
	Oak brush

North on E. line lot 1

Va. 17° 30' E

5.00	Gulch drains W.
10.00	The ¼ sec. cor. bet secs 3 & 10
	Land 10.00 chs mountainous
	Soil 2nd rate
	Oak brush

From S.W. cor lot 11 in sec 3

Segregated survey in section

Chains	South on W. side lot 2
	Va. 17°30' E
	Along E. slope
10.00	Set Quartzite 14×9×5 in deep marked with a cross on top, and stone mound S.W. Cor. lot 2 sec 10
	Land 10.00 chs mountainous
	Soil 2nd rate
	Oak brush
	East on S. side lot 2
	Va. 17°30' E
	Descend E. slope
6.75	Foot of hills, enter bott
8.65	Settlement Creek 10 lks wid 5 in deep runs N.E.
10.00	The S. Cor. to lots 1 & 2 in sec
	Land W. 6.75 chs mountainous
	Soil 1st & 2nd ra

T. 4 S

ains

Sou

00 Roa

00 Set

deep

on

for.

La

We

.40 Ro

.75 Se

5 in

.50 A

.00 Se

BOOK-A-162

T. 4 S. R 4 W. S. L. Mer

Oak brush

South on E. side lot 3
Va. 17°30' E
Road bears SW. & N. E.
Set Quartzite 13 x 9 x 6 in. 9 in
deep marked with a cross (+)
on top, and stonemound
for S.E. cor. lot 3. sec 10
Land level
Soil 1st rate
No timber —

West on S. side lot 3
Va. 17°30' E
Road bears NE. & S.
Settlement Creek 10 lks wide
5 in deep runs NE.
Ascend hill
Set limestone 15 x 7 x 4 in.

Seggregated survey in section

10 in. deep marked with a cross (+) on top, and stonemound for SW. cor lot 3 in sec. 10 -

Land W. 7.50 chs mountainous -

Soil 1st & 2nd rate

Oak brush -

North on W. side lot 3

Va. 17° 30' E

Along E. slope

10.00 The W. cor to lots 2 & 3 in sec. 10

Land mountainous 10.00 chs

Soil 2nd rate -

Oak brush -

September 11th 1879

Adolphe Jessen

U. S. Dep. Surveyor

BOOK-A-162

T. 4 S. R 4 W. S.L. Mer.

Note:

The bottom of the canyon becomes narrow at this point and so undulating as to be scarcely fit for cultivation. I therefore abandon further survey here —

BOO

General Description

This survey embraces the agricultural lands in sections 3, 4 & 10 T. 4 S. R. 4 W. S. L. Mer. situated in Settlement Canyon; the bottom of which is mostly in a high state of cultivation producing magnificent crops of lucerne & wheat without irrigation, the soil being very rich deep and (mostly

The mineral land in

BOOK-A-162

the surrounding
mountains I have
aimed to exclude –

Adolphe Jessen
U. S. Dep Surveyor

Blank

Page

BOOK-A-162 **LIST OF NAMES.** 59

A list of the names of the individuals employed to assist in running, measuring or marking the lines and corners described in the foregoing Field Notes of the

Segregated survey in sections 3 4 & 10 T. 4 S R 4 W. S. L. Meridian

508 BOOK-A-162

showing the respective capacities in which they acted.

Chance McKendrick Chainman.
Thomas McLeod Chainman.
D. W. Rench Flagman.
George Gee Axeman.

BOOK-A-162

in which

inman.

inman.

gman.

veman.

We hereby certify that we have assisted

Adolph Jesse

U. S. Deputy Surveyor in surveying

Segregated agricultural lands in sections 3.4 & 10 T.4 S. R.4 W. S.L. Mer

and that said lands

been in all respects, to the best of our knowledge and belief, well and faithfully surveyed, and the boundary monuments planted according to the instructions furnished by the Surveyor General.

Chance McKendrick Chainman.
Thomas McLeod Chainman.
D. W. Reich Flagman.
George Gee Axeman.

Subscribed and sworn to by the above named persons, before me, a U. S. Deputy Surveyor, for the ~~County~~ District of Utah, in the Territory of Utah, this 11th day of September 1879

Adolphe Jessen
U. S. Dep Surveyor

BOOK-A-I62

511

I, Adolphe Jessen

U. S. Deputy Surveyor, do solemnly swear that in pursuance of a contract with

Fred Salomon

Surveyor General of the public lands of the United States in the Territory of Utah, bearing date the 25th day of August 1879 and in strict conformity to the laws of the United States, the Manual of Surveying Instructions, and the instructions furnished by the said Surveyor General, I have faithfully surveyed the Segregated agricultural lands in sections 3.4 & 10 T. 4 S. R 4 W. S.L. Mer

In the Territory aforesaid, and do fu
solemnly swear that the foregoing are the
and original Field Notes of such survey.

Adolphe Jessen
U. S. Deputy Surveyo

Subscribed by the said Adolphe
Jessen U. S. Deputy Sur
and sworn to before me, a Notary
Public for
county of Salt Lake in the Terri
of Utah, this 17th day of September 18

Thomas C. Baily
Notary Public

U.S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, Oct 28 1879

The foregoing field notes of the survey of the Seggregated sub-division lines in

Township No 4 S. *Range No* 4 W.

of the Salt Lake Meridian, Utah Territory,

Executed by Adolphe Jessen

Under his *contract No* 94

of the 25th *day of* Augt. 1879

in the month of September 1879

having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.

Fred. Salomon

U. S. Surveyor General for Utah.