BLANK PAGE

Book 168 No. 1

R. 1881 BOOK-A-168 Copied

Filed Filed July 21st 1880.

July 21. Examined by T. C. Bailey

1880. Compared by " " "

Corrections to be made — Bailey

FIELD NOTES

OF

THE SURVEY OF THE

3d Standard Parallel South

~~of Township No.~~ through, Ranges No. 10. 11. 12. 13. 14. 15. 16. 17. 18. 19 & 26. West of the Salt Lake Meridian in Utah Territory.

BY

Joseph Gorlinski

U. S. DEPUTY SURVEYOR,

Under his Contract No. 93

dated June 3d 1879.

Survey commenced May 3d 1880.

Survey completed May 13th 1880.

53 1 184
261
57 12 185
249
49 13 186
248
7 24 187
242
25
36

BOOK-A-168

Township 15 S **R.** 10 W.



Township 15



BOOK-A-168

2

FOR CHAINMAN.

We Frank Gorlinski

and Robert Gorlinski

do solemnly swear that we will faithfully execute the duties of chain carriers; that we will level the chain upon uneven ground, and plumb the tally pins, whether by sticking or dropping the same; that we will report the true distance to all notable objects, and the true length of all lines that we asssist in measuring, to the best of our skill and ability,

Frank Gorlinski

Robt Gorlinski

Subscribed and sworn to before me this 29th *day of* April *1880*

Jno A. Bailey

Notary Public

BOOK-A-168 FOR FLAGMAN.

I, Theodore Sims

do solemnly swear that I will well and truly perform the duties of flagman, according to instructions given me, and to the best of my skill and ability.

Theodore Sims

Subscribed and sworn to before me this 29th day of April 1880

Jno A. Bailey
Notary Public

BOOK-A-168

FOR AXEMAN

I, Joseph Turner,

do solemnly swear that I will well and truly perform the duties of axeman, according to instructions given me, and to the best of my skill and ability.

Joseph Turner

Subscribed and sworn to before me this 29th *day of* April *1880*

Jno A. Bailey
Notary Public.
P. C.

3d Standard Parallel South between Tps 15 and 16 S. in Range 10 W.

Chs. Begin at the corner to Townships 15 and 16 South in Ranges 9 and 10 West. The stone standing and agrees with the description furnished me by the office, viz:
"Porphyry stone 24x12x8 in. in mound of stones."

Thence West on a true line along the South Boundary of ~~Township 15 South in~~ section 36.

Variation 16° 12' East.

13.80 To post, the closing corner to Township 16 South, between ranges 9 and 10 West established by former surveys.

40.00 Set a grey sand stone 14x8x4 in. 9 in. in the ground, marked 1/4. on the North side in mound of

6 3d Standard Parallel South
between T. 15 and 16 S. in R. 10 W.

Chs. of earth mkd 3 pits each 24 x 12 x 12 in. for 1/4 Sec. cor.

80.00 Set a sand stone 15 x 8 in. 10 in. deep. marked 1 north the east and 5 notches on the west edges in mound of earth mkd 3 pits each 24 x 12 x 12 for Standard corner to sections 35-36.

Bench land. Soil 2nd rate no timber. —

West on a true line, along the south boundary of Sec. 36. Var. 16° 12' E.

4.50 dry wash 150 links wide course S W

40.00 Set a lava stone 17 x 10 x 4 in

3d. Standard Parallel South
between Ts. 15 and 16 S. in R. 10 W.

Bks. 11 in. deep marked 1/4 on the north, in mound of earth mix 3 pits, each 24 X 12 X 12 in. for 1/4 sec. cor.

40.00. same Wash drains N.W.

66.00 same Wash drains N.W.

77.50 bears of same Wash draining S.W.

80.00 Set a sand stone 14 X 8 X 6 in. 9 in. deep. marked 2 notches on the east and 4 on the west edges. mix 3 pits each 24 X 12 X 12 in in mound of earth for standard corner to sections 34 and 35.

Bench land. Soil 2nd rate.
No timber.--

8 3rd Standard Parallel South
T. 15 S. R. 10 West.

Chains West on a true line
along the South boundary
of Section 34.
Var. 16° 12' East.

32.00 N. Rollow 300 links wide
~~bears NNW and~~ drains S.E.

40.00 Set a sandstone 15 X 10 X 10
in. 10 in. deep. marked 1/4 on
the north side in mound of
earth with 3 pits each 24 X 12
X 12 in. for 1/4 sec. cor.

46.00 Gully 50 links wide ~~bears NNW~~ drains
~~and~~ S.E.

55.00 dry bed 100 links wide drains ~~bears NNW~~ S.E.

80.00 Set a sandstone 16 X 11 X 7 in.
10 in. deep marked 3 notches on the
east and west edges in mound
of earth with 3 pits each 24 X 12 X 12
in. for standard corner to sections 33 & 34.
Broken land and foot hills
Soil 3rd rate. - No timber -

3rd Standard Parallel South
T. 15 S. R. 10 W.

BOOK-A-168

Chs. West on a true line along the south boundary of section 33.
Var. 16° 12' E.

20.50 A mark 100 links wide, ~~down~~ drains ~~A hill~~ ~~and~~ SE.

40.00 Set a grey sand stone 13X11X4 in. 8 in. deep, marked 1/4 on the north side in mound of earth from 3 pits, each 24X12X12 in. for 1/4 sec. cor.

80.00 Set a grey sand stone 14X8X9 in. 9 in. deep, marked 4 notches on the east, and 2 notches on the west edge in mound of earth from 3 pits each 24X12X12 in. for standard corner to sections 32 and 33.

Bottom right bench land
Soil 3d rate No timber.

3d Standard Parallel South
T. 15 S. R 10 W.

Bfs. West on a true line, along the south boundary of sec. 32.

Va. 16° 12' E

3.00 Old Road bears North 85° E.

20.00 East of Detroit Range of Mountains bearing Northerly and Southerly and haller 2 chs wide.

4000 Set a sand stone 12 x 10 x 4 in. 8 in. deep. marked 1/4 on the north side mit 3 pits each 24 x 12 x 12 in. in mound of earth and stone for 1/4 sec. cor.

4350 Ravine 30 chs wide, ~~drains North~~ Bfs.

80.00 Set a sand stone. 16 x 8 x 8 in 10 in. deep. marked 5 notches on the east and 1 notch on the west edges. in mound of stone, for corner to sections 31 and 32. Pits impracticable.

Mountainous rocky land, on 60 chains East and high bench. Soil 3d rate. No timber.

3d S
T. 1

Bfs

4000

55.00

80.00

BOOK-A-168

3d Standard Parallel South
T. 15 S. R 10 W.

Chs. West on a true line, along the south boundary of section 31
No. 16 12 E.

4000. Set a sand stone 13 X 8 X 8 in 8 in deep, marked 1/4 on the north side in mound of earth, from 3 pits each 24 X 12 X 12 in for 1/4 sec. cor.

55.00 Ravine 500 ch wide, ~~1 drain NE~~ ~~and~~ SW.

80.00 Set a sand stone 20 X 10 X 6 in 15 in deep, in mound of stone and earth, marked 6 notches on the north, east and west edges, ~~for~~ stand'd cor. ~~between~~ Sec. 15 ~~and~~ 16 T. 15 S. Ranges 10 and 11 W.

Pits impracticable on 80 chains
Rock mountainous ~~land~~.

Soil 3d rate. No timber

May 3d 1880

12 3rd Standard Parallel South
T. 15 S. R 10 W.

General description
The land North on South
of this Standard through
the Range. as far as can be
seen consist mostly of high
bench, and foot hills; the
west and being covered
by high mountain range.
It is not adapted for cultiv-
ation. except for grazing
purposes.
No timber or mineral.

3rd St
between P
Bbls.
4000
50.00
7400
8000

3d Standard Parallel South
to 1st C. T. 15 and 16 S. in R. 11 West.

BOOK-A-168

Bks. West on a true line along the
south boundary of township 15
S. ~~the~~ Sec. 36.

Variation 16° 15' East.

40.00 Set a lime stone 12 X 10 X 5 in.
8 in. deep in mound of earth, marked
1/4 on the north side with 3 pits each
24 X 12 X 12 in. for 1/4 sec. cor.

50.00 A gully, ~~bears NE & and~~ drains SW

74.00 A gully, ~~bears NE and~~ drains S.

80.00 Set a grey sand stone 14 X 14 X 12
in. in mound of earth, 9 in. deep,
marked 1 notch on the east and
5 notches on the west, with 3 pits,
each 24 X 12 X 12 in. standard for corner
to sections 25 and 36.

Mountainous land, on 80 chains Soil
3d rate, rocky and covered
with undergrowth of sagebrush
No timber.

BOOK-A-168

Township 15 S. R. 11 W.

1	6	5	4	3	2	1
12	7	8	9	10	11	12
13	18	17	16	15	14	13
24	19	20	21	22	23	24
25	30	29	28	27	26	25
36	31	32	33	34	35	36
3	18	17	16	15	14	13

3d Standard Parallel South.
T. 15 S. Range 11 West.

Chs. West on a true line. ~~along~~ the south boundary of section 35.

Variation 16° 15' E.

6.00 head of ravine bearing N.E.

13.50 Summit of mountains bears N. & S.

36.00 head of gulch bearing S.W.

40.00 Set a sand stone 14 X 10 X 4 in. 9 in. deep. marked 1/4 on the north side in mound of earth from 3 pits each 24 X 12 X 12 in for 1/4 sec. cor. on top of ridge bearing N.E. - S.W.

64.00 Ravine, ~~bears N.E. and~~ drains S.W.

71.00 top of ridge bears N. and S.

78.00 Ravine, ~~bears N.E. and~~ drains S.E.

80.00 Set a sand stone 18 X 10 X 8 in. 12 in. deep, marked 2 notches on the east and 4 on the west edges. in mound of earth from 3 pits. each 24 X 12 X 12 in for standard cor. to sections 34 and 35.

Mountainous land. Soil 3rd rate. no timber on 80 chains.

3d Sta
T. 15

Chs.

2306

4000

4350

4800

5350

7500

8000

3d Standard Parallel South
T. 15 S. Range 11 West.

BOOK-A-168

Chs. West on a true line, along the South boundary of sec. 34.
Variation 16° 15' E.
2306 Head of gulch bearing S.W.
4000 Set a sand stone 13 X 10 X 5 in. 8 in. deep, marked 1/4 on the north side, in mound of earth, from 3 pits each 24 X 12 X 12 in. for 1/4 sec. cor.
4350 Gully, ~~bears N.E. and~~ drains S.W. and enters cedars
4800 top of ridge bears N.E. and S.W.
5350 A hollow 250 links wide, ~~bears N.E.~~ drains S.W.
7500 top of ridge bears N.E. and S.W.
8000 Set a sand stone 16 X 8 X 5 in. 10 in. deep, marked 3 notches on the east and west edges, in mound of earth from 3 pits, each 24 X 12 X 12 in. for standard corner to sections 33 and 34.

Mountainous land on 80 chains Soil rocky 3d rate. West half covered with scattered cedars—

16 3rd Standard Parallel South
T 15 S. Range 11 West.

Obs. West on a true line along the south boundary of section 33.
Variation 16° 15' East.

10.00 A hollow 150 links wide, drains N. & W.

40.00 Set a sand stone 16 X 12 X 5 in. 10 in. deep, marked 1/4 on the north side, in mound of earth and stone from 3 pits each 24 X 12 X 12 in. for 1/4 sec. cor.

42.75 A Gully, drains S.

65.00 A gully, drains S.E.

80.00 Set a grey sand stone 16 X 10 X 6 in. 10 in. deep, marked 4 notches on the east and 2 notches on the west edges, in mound of earth and stone, with 3 pits each 24 X 12 X 12 in. for cor. to sections 32 and 33. Post standard

Mountainous rocky land, on 80 chains covered with scattered cedars.
Soil 3rd rate.—

3d St
T.
Obs.
150
1050
2000
4000
7050
7850
8000

3d Standard Parallel South. 17
T. 15 S. R. 11 W.

Chs. West on a true line along the south boundary of section 32
Variation 16° 15' E.

1.50 Wash 50 links wide, drains S.

10.50 top of round hill bearing N. & S.

20.00 leave mountainous and enter bench land bearing N. and S.

40.00 Set a sand stone 14 X 12 X 10 in. 9 in. deep. marked 1/4 on the north side in mound of earth and stone, with 3 pits, each 24 X 12 X 12 in. for 1/4 sec. cor.

70.50 Gully, drains S.

78.50 Gully, drains S.

80.00 Set a sand stone 12 X 14 X 10 in. 8 in. deep, marked 5 notches on the east and 1 notch on the west in mound of earth, with 3 pits, each 24 X 12 X 12 in. for standard cor. to sections 31 and 32
Mountainous on 20 chains. — Balance Bench land. Soil sandy, 3d rate
No timber.

18 3d Standard Parallel South
T. 15 S. Range 11 West.

3d S.P.

Chains West on a true line, along the
south boundary of Sec. 31
Township 16 South 15 East
40.00 Set a sand stone 12X8X7 in.
8 in. deep, marked 1/4 on the north
side, in mound of earth, from 3
pits each 24X12X12 in. for 1/4 sec. cor.
80.00 Set a lime stone 18X12X6 in. 12 in.
deep, marked 6 notches on the north,
east and west edges in mound
of stone and earth, with 3 pits, each
36X18X18 in. for standard corner to Tps 15
~~and 16~~ Ranges 11 and 12 W.
Bench land, Soil 2nd rate
No timber.

Whs. 4.50 40.00 80.00

General description

Most of land along this standard
is high, and mountainous, unfit for
cultivation, - partly timbered, is suit-
able for grazing. No mineral found

3d Standard Parallel South
T. 15 S. Range 12 West.

60 lks. West on a true line, along the south boundary of sec. 36.
Variation 16° 15' East.

4.50 dry bed 20 links wide drain ~~running~~ ~~16° E~~ ~~and~~ S. 10 W.

40.00 Set a sand stone 12 x 10 x 5 in 8 in. deep. marked 1/4 on the north side, in mound of earth with 3 pits, each 24 x 12 x 12 in for 1/4 sec. cor.

80.00 Set a sand stone 11 x 10 x 6 in 7 in. deep marked 1 notch on the east and 5 notches on the west edges, in mound of earth with 3 pits each 24 x 12 x 12 in. for standard corner to sections 35 and 36.

Rolling valley land. Soil 2nd rate. No timber.
May 4th 1880.

BOOK-A-168

Township 15 S **R.** 12 W

6	5	4	3	2	1	6	5				
7	8	9	10	11	12	7	8				
18	17	16	15	14	13	18	17				
19	20	21	22	23	24	19	20				
30	29	28	27	26	25	30	29				
31	32	33	34	35	36	31	32				
24	25	22	21	20	19	31	30				

3d Standard Parallel South
T. 15 S. R. 12 W.

Chs. West on a true line, along the south boundary of sec. 35
Var. 16° 15' E.

20.00 Level valley land bearing N. & S.

40.00 Set a sand stone 12 X 8 X 6 in. 8 in. deep, marked 1/4 on the west side, in mound of earth, with 4 pits each 24 X 12 X 12 in. for 1/4 sec. cor.

41.50 dry creek bed 20 links wide, ~~bears~~ drains ~~NW and~~ SE.

45.50 dry creek bed 30 links wide, ~~bears~~ drains ~~N. and W.~~

80.00 Set a sand stone 12 X 8 X 6 in 8 in. deep in mound of earth from 3 pits each 24 X 12 X 12 in, marked 2 notches on the east and 4 notches on the west edges for Standard corner to sections 34 and 35

Level land. Soil 1st rate
No timber. —

3d S
T.

Chs.

40.00

50.00

80.00

3d Standard Parallel South
T. 15 S. R 12 W.

6hs. West ~~on a true line~~, along the south boundary of sec. 34
Var. 16° 15' E.

40.00 Set a charred cedar post 4 x 4 in. ogmas 4 feet long in mound of earth marked 1/4 S. on the north side with 3 pits each 24 x 12 x 12 in. for 1/4 sec. cor.

50.00 Leave level and enter gently rising valley bearing N and S.

80.00 Set a limestone 14 x 10 x 6 in. 9 in. deep, in mound of earth marked 3 notches on the east and west, with 3 pits each 24 x 12 x 12 in. for standard corner to sections 33 and 34.

Valley land. Soil 1st rate.
No timber.

3rd Standard Parallel South
T. 15 S. R. 12 W.

Chs. West on a true line, along the south boundary of sec. 33.
Var. 16° 15' E.

21.50 Wash 25 links wide, drains NE ~~& W.~~

40.00 Set a limestone 15 X 10 X 6 in. 10 in. deep in mound of earth, marked 1/4 on the north side, with 3 pits each 24 X 12 X 12 in. for 1/4 sec. cor.

46.15 Road from Detroit Mines to Grassie's Springs bears NE and S.W. and enters bench lands.

80.00 Set a Lime stone 15 X 12 X 8 in. 10 in. deep, marked 4 notches on the east, and 2 notches on the west edges in mound of earth from 3 pits, each 24 X 12 X 12 in. for standard corner to sections 32 and 33.

Bench land. Soil 2 in. rocky. No timber

Chs.
40.00
43.85
55.10
80.00

3d Standard Parallel South 33

T. 15 S. R 12 W.

60 Chs. West on a true line, along the south boundary of section 32
Va. 16° 15' E.

40.00 Set a lime stone 18 X 12 X 12 in. 12 in deep. marked 1/4 on the north side in mound of earth. from 3 pits each 24 X 12 X 12 in. for 1/4 sec. cor. in gully, ~~draining~~ NE ~~and SW~~.

43.85. Old Road bears NE. and SW.

55.10. Gully, ~~draining~~ bears NE ~~and SW~~.

80.00 Set a Lime stone 12 X 12 X 8 in. 8 in. deep. marked 3 notches on the east and 1 notch on the west edges. in mound of earth and stone. with 3 pits each 24 X 12 X 12 in. for ~~standard~~ cor. to sections 31 and 32.

Rocky level land. Soil 3d rate No timber.

3rd Standard Parallel South
T. 15 S. R. 12 W.

Chs. West on a true line along the south boundary of section 31.

Va. 16° 15' E

21.50 A Gully ~~drains~~ NE ~~and SW~~ and foot of Whitelope Mountains bearing Northerly and Southerly

30.30 A Gully ~~drains~~ NE ~~and SW~~.

40.00 Set a lime stone 18 X 10 X 8 in. 12 in deep. marked 1/4 on the N. side. in mound of stone and earth. with 4 pits each 24 X 12 X 12 in for 1/4 sec. cor.

76.55 Gully ~~drains~~ NE ~~and SW~~

80.00 Set a lime stone 13 X 12 X 7 in. 8 in deep. in mound of stone. marked 6 notches on the N. E & W edges. for standard cor. to Ts. 15 ~~and~~ S. R. 12 and 13 W.

Pits impracticable.

Mountainous rocky land on 58.59 chains. Cut and high bench. Soil 3rd rate. No timber

BOOK-A-168

3d Standard Par'l. T. 15 S. R. 12 W.

General description
The land along the portion
of the Standard line consist
of bench and valley land
which extends Northward from
Sevier Lake. West end is
mountainous and rocky -
The soil in the valley is first
rate and adapted for cultiv-
ation; bench and mountain-
ous land fit only for grazing
purposes - No timber
or mineral.

May 5th 1880

V

3d Standard Parallel South
T. 15 S. - R. 13 W.

Chs.	West on a true line, along the south boundary of section 36.	Chs.
	Va. 16° 18' E.	6.00
40.00	Set a lime stone 12x12x5 in. 8 in. deep, mound of stone for 1/4 sec. cor. Pits impracticable.	31.75
		40.00
43.50	Gully ~~drain~~ drain, NE. ~~and Slp.~~	
80.00	Set a lime stone 14x10x6 in. 9 in. deep, in mound of stone and earth, marked 1 notch on the east and 5 notches on the west edges for standard cor. to sections 35 and 36. Pits impracticable	80.00
	Mountainous rocky land on 80 chs. unfit for cultivation. - No timber. -	

BOOK-A-168

wnship 15 S R. 13 W

1	6	5	4	3	2	1
12	7	8	9	10	11	12
13	18	17	16	15	14	13
24	19	20	21	22	23	24
25	30	29	28	27	26	25
36	31	32	33	34	35	36
49	31	30	29	28	27	26

3d Standard Parallel South
T. 15 S. R. 13 W

Chs. West on a true line along the south boundary of section 35
Variation 16° 18' E.

6.00 Ravine drains NW & SE.

31.75 same ravine, drains NE & SW.

40.00 Set a limestone 16 X 10 X 8 in 10 in. deep, marked 1/4 on the north side in mound of stone and earth with 3 pits each 24 X 12 X 12 in. for 1/4 sec. cor.; from which a cedar 6 in. dia. bears N. 55° W. 63 links distant

80.00 Set a limestone 17 X 9 X 7 in. 11 in. deep, marked 2 notches on the east and 4 notches on the west edges. in mound of stone and earth for standard cor. common to sections 34 and 35; from which a cedar 8 in. dia bears N 60° W. 64 links distant Site impracticable — high mountainous land on 80 chs. Timber cedars. Surveying 3d rate. —

3d Standard Parallel South
T. 16 S. R. 13. W.

Chs. West on a true line, along the south boundary of section 34. Variation 16° 18' E.

5.00 Ravine ~~bears~~ drains N.W. ~~and dies~~

40.00 Set a lime stone 19 X 12 X 10 in. 14 in. deep, marked 1/4 on the west side in mound of stone and earth, for 1/4 sec. cor.; from which a cedar tree 12 in. dia. bears S. 45° W. 66 links distant.— Pits impracticable.

80.00 Set a lime stone 29 X 18 X 9 in. 19 in. deep, marked 3 notches on the east and west edges, in mound of stone and earth, for standard corner to sections 33 and 34; from which a cedar 8 in. dia. bears N. 70 W. 21 links ~~and~~ a cedar 12 in. dia. bears S. 55° W. 23 links distant.

X High mountainous land, on 80 chain Stiff rocky 3d rate.— Timber thick cedars and Pinon Pine.—

Chs.
11.00
40.00
47.50
78.00
80.00

3rd Standard Parallel South
T. 15 S. R. 13 W.

Book-A-168

Chs. West on a true line, along the south boundary of section 33.
Va. 16° 18' E.

11.00 head of deep gulch bearing N E.

40.00 Pinyon Pine tree 7 in. dia. marked 1/4 S. on the north side, as monument for 1/4 sec. cor. - Pits impracticable.

47.60 Top of high ridge bears N E and S W.

78.00 deep ravine heads S W. bears N E.

80.00 Set a lime stone 15 X 15 X 6 in. 10 in. deep. marked 4 notches on the east and 2 notches on the west edges in mound of stone and earth, for standard Cor. to sections 32 and 33; from which bear:

A Cedar 6 in dia. S 38° E. 42 links
A Cedar 12 in. dia. S 50 W. 37 links,
and A Pinyon Pine 12 in. dia. N 40° E. 18 links distant. ~~Pits impracticable~~ on 80 chains

High rocky mountainous land.
Timber, thick Cedars and Pinyon Pine.

3d Standard Parallel South
T. 15. S. R 18 W.

Chs. West on a true line, along the south boundary of sec. 32.
No. 16° 18' E.

25.00 head of rocky gulch ~~draw~~ draw NE.

40.00 Pinyon Pine 16 in. dia. marked 1/4 S on the north side on monument for 1/4 cor. sec.
Pits impracticable.—

66.00. Point of highest summit of Antelope mountains on the precipice facing on the west, bearing Northerly and Southerly from which A~~n~~ round peak bears S. 13° W. 9.50 chs. distant.—

80.00. Set a lime rock 30 X 12 X 12 in 20 in. deep, in mound of stone and earth, for ~~Standard~~ corner to sections 31 and 32, on the West side of the summit at the foot of steep precipice, which corner is marked 5 notches on the east and 2 on the west edge.
Pits impracticable.— on 80 chs.
High rocky mountainous land.—
Timber Cedars and Pinyon Pine.
Soil 3d rate

Chs.
22.00
40.00
68.00
80.00

3rd Standard Parallel South 31

T. 15 S. R 13 W.

Chs. West on a true line along the south boundary of section 31.
Va. 16° 18' E.

22.00 Deep gulch, drains N.W. ~~and E.~~.

40.00 Set a lime rock 18 X 10 X 10 in 12 in deep. marked 1/4 on the north side in mound of rock and earth. for 1/4 sec. cor. - Pits impracticable -

68.00 Leave cedars and enter rocky gulch ~~bearing~~ draining Northerly ~~and Southerly~~

80.00 Set a fine stone 20 X 10 X 8 in 14 in. deep, in mound of stone and earth with 3 pits each 36 X 18 X 18 in. marked 6 notches on the North, East and West edges. for standard corner to T. 15 S. ~~with~~ Ranges 13 and 14 West.

On 80 chains High mountainous land. Timber Cedars Soil rocky. 3rd rate -

May 6th 1880.

32 3rd Standard Parallel South
T. 15 S. R. 13 E.

General Description.

The land along this portion of the Standard is entirely covered by high rocky range of mountains, unfit for cultivation, but well adapted for grazing purposes.—
Timber consisting of cedar and Pinyon Pine is found in abundance all through the mountains, with scattered springs and plenty bunch grass.
No mineral found.

Chains
40.00
58.50
80.00

BOOK-A-168

3d Standard Parallel South
T. 15 S. R. 14 W.

Chains West on a true line along the south boundary of section 36.

Va. 16° 22' E.

40.00 Set a lime stone 16 X 12 X 4 in. 10 in. deep, marked 1/4 on the north side, in mound of stone and earth with 3 pits each 24 X 12 X 12 in for 1/4 sec. cor.

58.50 Gully 75 links wide, drains NW

80.00 Set a lime stone 15 X 10 X 5 in. 10 in deep, marked 1 notch on the east side in mound of earth and 5 notches on the west edge, with 3 pits, each 24 X 12 X 12 in for Standard Cor. to sections 35 and 36 — at the foot of bench land bearing N 45 E. and leave Antelope mountains on 89 chains Mountainous rocky, land 3d rate. No timber —

BOOK-A-168

Township [illegible] **R.** [illegible]

[illegible]	6	5	4	3	2	1	6	5	
[illegible]	7	8	9	10	11	12	7	8	
[illegible]	18	17	16	15	14	13	18	17	
[illegible]	19	20	21	22	23	24	19	20	
[illegible]	30	29	28	27	26	25	30	29	
[illegible]	31	32	33	34	35	36	31	32	
	[illegible]								

3d Standard Parallel North
T. 15 S. R. 14 W.

Chs. West on a true line, along the south boundary of sec. 35.
Va. 16° 22' E.

34.50 Wash 100 links wide ~~down~~ NE ~~of Hk~~.

40.00 Set a limestone 15 X 10 X 4 in 20 in. deep, marked 1/4 on the north side in mound of stone and earth with 3 pits each 24 X 12 X 12 in. for 1/4 sec. cor.

65.00 Leave bend, enter brook valley sandy land, bearing N. and E.

80.00 Set a sand stone 12 X 8 X 6 in. 8 in. deep, marked 2 notches on the east and 4 notches on the West edges with 3 pits, each 24 X 12 X 12 in. in mound of earth for Standard corner to sec. tions 34 and 35.

Brush land. - East 1/4 valley
Soil 2nd and 3d rate.
No timber. -

3d S
T. 15
BOOK
Chs.
40.00
52.50
80.00

3d Standard Parallel South

T. 15 S. R. 14 W.

BOOK-A-168

Cho. West on a true line, along the south boundary of sec. 34.

Va. 16° 22' E.

40.00 Set a sand stone 12 X 8 X 5 in. 8 in. deep, marked 1/4 on the north side in mound of earth, from 3 pits each 24 X 12 X 12 in. for 1/4 sec. cor.

52.50 Flat alkali soil with greasewood bears N. and S.

80.00 Set a grey sand stone 12 X 10 X 5 in. 8 in. deep, marked 3 notches on the east and west edges in mound of earth, from 3 pits each 24 X 12 X 12 in. for ~~standard~~ corner to sections 33 and 34.

East half sandy, West half alkali soil. - 3d rate

No timber -

Chs. West on a true line, along the south boundary of sec. 33
Var. 16° 22' E.

40.00 Set a sand stone 18 X 7 X 6 in. 8 in. deep, marked 1/4 on the north side in mound of earth, with 3 pits each 24 X 12 X 12 in. for 1/4 sec. cor.

80.00 Set a sand stone 12 X 9 X 4 in. 8 in. deep, marked 4 notches on the east and 2 notches on the west edges, in mound of earth with 3 pits each 24 X 12 X 12 in. for Standard corner to sections 32 and 33.

Land rolling land with gravel soil 3d rate.—
No timber.

May 7th 1880.

3d Standard Parallel South
T. 15 S. R 14 W.

Chs. West on a true line, along the south boundary of sec. 32
Var. 16° 22' E.

40.00 Set a lime stone 12 X 8 X 6 in. 8 in. deep, marked 1/4 on the north side in mound of earth, with 3 pits each 24 X 12 X 12 in. for 1/4 sec. cor.

80.00 Set a sand stone 18 X 8 X 6 in. 8 in. deep, marked 5 notches on the east and 1 notch on the west edges in mound of earth, with 3 pits each 24 X 12 X 12 in. for Standard corner to sections 31 and 32.

Low alkali land, with grease wood mounds
Soil 3d rate. No timber.

West on a true line, along the south boundary of section 31.

3d Standard Parallel South
T. 15 S. R 14 W.

Chs.	Variation 16° 22' E.	Chs.
40.00	Set a limestone 13 X 8 X 7 in. 8 in deep marked 1/4 on the north side with mound of earth and 3 pits each 24 X 12 X 12 in. W for 1/4 sec. cor.	40.00
80.00	Set a limestone 18 X 8 X 6 in. 12 in. deep. marked 6 notches on the North, East and West edges. in mound of stone and earth with 3 pits — each 36 X 18 X 18 in. W for corner ~~between~~ to T. 15 ~~and 16~~ S. Ranges 14 and 15. W.	58.50 80.00
	Low alkali land. Soil 3d rate. No timber —	

General Description.

The land along this portion of the Standard is bench on the East and low alkali soil on the West, unfit for cultivation. commonly called "White Valley" — No mineral or timber —

3rd Standard Parallel South

T. 15 S. R. 15 W.

BOOK-A-168

Chs. West on a true line, along the south boundary of sec. 36.

Var. 16° 25' E.

40.00 Set a limestone 11X8X7 in. 7 in. deep, marked 1/4 on the north side, in mound of earth, from 3 pits each 24X12X12 in. for 1/4 sec. cor.

58.50 Leave alkali, enter level valley bearing N. and S.

80.00 Set a limestone 13X8X5 in. 8 in. deep, marked 1 notch on the east and 6 notches on the west edges in mound of earth from 3 pits each 24X12X12 in. for Standard corner to sections 35 and 36.—

3/4 mile on the east bar alkali. 1/4 mile on the west level valley land. Soil 3rd and 2nd rate.—No timber—

BOOK-A-168

wnship 15 S. R. 15 W.

1	6	5	4	3	2	1
12	7	8	9	10	11	12
13	18	17	16	15	14	13
24	19	20	21	22	23	24
25	30	29	28	27	26	25
36	31	32	33	34	35	36
1	53	111	116	113	111	110	50

3d Standard Parallel South
T. 15 S. R 15 W.

BOOK A
T. 1

Chs.	West on a true line, along the south boundary of section 35 Va. 16° 25' E	Chs.
23.75	Old Road bears N & S.	6.50
40.00	Set a lime stone 10 X 8 X 7 in. 6 in deep marked 1/4 on the north side, in mound of earth, with 3 pits each 24 X 12 X 12 in. for 1/4 sec. cor.	40.00
45.00	foot of mountain range bears N & S.	
59.25	Ravine drains N.E. ~~and Lake~~	51.50
71.00	top of ridge bears N & S.	80.00
79.00	Ravine drains N.W. ~~and E.~~	
80.00	Set a lime stone 19 X 12 X 8 in. 14 in. deep, marked 2 notches on the East and 4 notches on the west edges in mound of earth and stone for Standard Corner to sections 34 and 35.	
	Pits impracticable.	
	East half valley land. Soil 2nd rate ~~West half~~ rocky and mountainous, on 35.00 chs.	
	Soil 3d. rate. No timber.	

BOOK A-168

Standard Parallel South

T. 15 S. R 15 W

Chs. West on a true line, along the south boundary of section 34.

Va. 16° 25' E.—

6.50. Rollor mountainous land bearing Northerly and Southerly

40.00 Set a limestone 13 X 7 X 6 in. 8 in. deep. marked 1/4 on the north side, in mound of earth, with 3 pits each 24 X 12 X 12 in. for 1/4 sec. cor.

51.50 Ravine 25 links wide, chains NE

80.00 Set a blackrock 11 X 10 X 6 in. 7 in. deep. marked 3 notches on the east and west edges. in mound of earth with 3 pits each 24 X 12 X 12 in. for Standard Corner to sections 33 and 34.

Land on 80 chains Ridge and rocky mountainous with rollors and gullys. Soil 3d rate.

No timber—

3d Standard Parallel South
T. 15 S. R. 15 W.

Chs. West on a true line, along the south boundary of sec. 33.
Var. 16° 25' E.

40.00 Set a limestone 12 X 10 X 6 in. 8 in. deep, marked ¼ on the west side in mound of earth, with 3 pits, each 24 X 12 X 12 in. for ¼ sec. cor.

68.00 Ravine 100 lks wide ~~bearing~~ ~~S.~~

80.00 Set a limestone 14 X 10 X 8 in. 9 in. deep, marked 4 notches on the east and 2 on the west edges in mound of stone and earth, with 3 pits each 24 X 12 X 12 in. for standard, corner to sections 32 and 33.

Ridge and rocky mountainous land with hollows and ravines. Soil 3d rate.
No timber —
Mountainous on 80 chains.

Chs.

1.25

16.25

21.75

40.00

68.00

80.00

3rd Standard Parallel South 43
T. 15 S. R 15 W

Bkr: West on a true line, along the south boundary of sec. 32.
Var. 16.25 E.

1.25 White burnt lime knoll 50 links on the north of line

16.25 Summit of the ridge bears N & S.

21.75 head of ravine bearing S.W.

40.00 Set a lime stone 12 X 8 X 6 in. 8 in. deep, marked 1/4 on the north side in mound of earth, with 3 pits each 24 X 12 X 12 in. for 1/4 sec. cor.

68.00 Leave mountains. enter valley bearing Northerly and Southerly

80.00 Set a lime stone 14 X 8 X 5 in. 9 in. deep, marked 5 notches on the east and 1 notch on the west side edges. in mound of earth with 3 pits each 24 X 12 X 12 in. for Standard corner to sections 31 and 32.

Mountainous rocky land on 68.00 chains Soil 3rd rate.
West end valley. 2nd rate. No timber.

3rd Standard Parallel South
T. 15 S. R. 15 W

BOOK A-3
T. 15

Chs. West on a true line, along the south boundary of sec. 31.
W. 16.25 Ch.

40.00 Set a lime stone 12 X 8 X 6 in. 8 in deep, marked 1/4 on the north side in mound of earth, with 3 pits each 24 X 12 X 12 in. for 1/4 sec. cor.

80.00 Set a lime stone 15 X 10 X 8 in. 10 in. deep, in mound of stone and earth from 3 pits, each 36 X 18 X 18 in. — marked 6 notches on the North, East and West edges, for standard corner ~~to~~ to Township 15 ~~and 16~~ S. R. 15 & 16 W.

Level land. Soil 1st rate
No timber. —
May 8th 1880

General description

The land along this portion of the Standard, consist partly of mountainous and partly of valley lands, of the 3d & 2nd qualities. No mineral or timber —

Chs.

34.70

40.00

68.00

80.00

3rd Standard Parallel South
T. 15 S. R. 16 W.

Chs. West on a true line, along the south boundary of sec. 36.
Var. 16° 25' E.

34.70 Rush Spring and Trout Creek road bears NW. and SE.

40.00 Set a lime stone 15 X 12 X 8 in. 10 in. deep, marked 1/4 on the north side with 3 pits each 24 X 12 X 12 in. and mound of earth for 1/4 sec. cor.

68.00 Enter sand hills and foot of mountains bearing N. & E.

80.00 Set a lime stone 15 X 10 X 5 in. 10 in. deep, marked 1 with 4 notches on the west edges, in mound of earth with 3 pits, each 24 X 12 X 12 in. for ~~standard~~ cor. to sections 35 and 36.

West over sandy and mountainous ozs 12.00 chains. Soil 3d rate. East part in the valley. Soil 1st rate. No timber

BOOK-A-168

Township 15 S **R.** 16 W

6	5	4	3	2	1	6	5
7	8	9	10	11	12	7	8
18	17	16	15	14	13	18	17
19	20	21	22	23	24	19	20
30	29	28	27	26	25	30	29
31	32	33	34	35	36	31	32
50	49	48	47	46	45	57	56

3d Standard Parallel South
T. 15 S. R 16 W.

Chs. West on a true line, along the south boundary of Sec. 35
Var. 16° 25' E.

40.00 Set a lime stone 11 X 8 X 7 in. 7 in. deep. marked 1/4 on the north side in mound of earth and stone, with 3 pits each 24 X 12 X 12 in. for 1/4 sec. cor.

53.50. Summit of the ridge bears N. & S.

60.00 leave mountains. & enter valley bearing NW and SE.

80.00 Set a lime stone 10 X 8 X 7 in. 6 in. deep. marked 2 notches on the east and 4 on the west edges. in mound of earth. from 3 pits each 24 X 12 X 12 in. for Standard corner to sections 34 and 35.

60 Chains
~~3/4 mile~~, on the east. mountainous
1/4 mile on the west level valley land.
No timber. Soil 3d and 2d rate.

BOOK A 168

Standard Parallel South
T. 16 S. R. 16 W.

Chs. West on a true line
along the south boundary of
Sec. 34.

Ch. 16.25 E.

40.00 Set a lime stone 12 X 10 X 5 in. 8 in.
deep, marked 1/4 on the north
side, in mound of earth, from
4 pits each 24 X 12 X 12 in. for 1/4
sec. cor.

60.00 Leave Bench Land bearing N. & S.
72.50 Road 30 links wide, ~~leave~~ drain ~~60~~ E.
80.00 Set a lime stone 15 X 10 X 4 in. 10
in. deep, marked 3 notches on the
east and west edges in mound of
earth and stone, from 3 pits each
24 X 12 X 12 in. for Standard corner Sections
33 and 34

River valley 1st rate,
West and bench land 3d
rate. No timber.

3d Standard Parallel South
T. 15 S. R. 16 W.

Chs. West on a true line, along the south boundary of section 33

Va. 16° 25' E.

10.00 leave mark 2 ~~training~~ ~~trees~~ and E.

27.35 Old road bears NW and SE.

35.00 Foot of Snake valley Mountains bears Northerly and Southerly

40.00 Set a limestone 12 X 8 X 6 in. 8 in. deep, marked 1/4 on the north side in mound of stone. Pit 1/4 cor. on line impracticable

80.00 Set a limestone 16 X 12 X 6 in. 10 in deep, marked 4 notches on the east and 2 on the west edge, in mound of earth and stone with 3 pits each 24 X 12 X 12 in. for corner to sections 32 and 33. Standard

Bench and Mountainous land on 45.00 Chs.

Sec. 3d rods No timber

Chs.

34.00

40.00

46.75

67.50

80.00

BOOK A-168

Standard Parallel South
T. 15 S. R. 16 W.

Chs. West on a true line, along the south boundary of sec. 32.
Va. 16° 25' E.

34.00 Gully drains S.

40.00 Set a lime stone 13 X 10 X 8 in. 8 in. deep, marked 1/4 on the north side in mound of stone, for 1/4 sec. cor. Pits impracticable.

46.75 Gulch, drains SE.

67.50 same Gulch drains E

80.00 Set a lime stone 17 X 10 X 8 in. 11 in. deep, in mound of stone, marked 5 notches on the east and 1 notch on the west edge, Standard for cor. to secs. 31 and 32
Pits impracticable.

Mountainous rocky land, one 80 chains
Soil 3d rate. No timber.

50 3d Standard Parallel South
T. 15 S. R 16 W.

80 chs. West on a true line, along the south boundary of sec 31.
Vo. 16° 25' E.
8.00 A gulch ~~leads~~ draining NE. ~~and SW.~~
18.50 Enter gulch 100 links wide, ~~leading~~ draining ~~NW~~ and SE.
24.50 Leave the same, ~~leaving~~ ~~NW and~~ draining SE.
34.50 Ravine ~~leads~~ draining NE. ~~and SW.~~
40.00 Set a limestone 14 x 12 x 5 in. 9 in. deep, marked 1/4 on the N. side in mound of rock. No 1/4 sec. cor. Pits impracticable.
62.00 Top of mountain bears NE. and SW.
66.00 Ravine ~~leads~~ draining NE. ~~and SW.~~
80.00 Set a quartzite rock 16 x 12 x 10 in 10 in. deep, marked 6 notches on the N. and W. edges for corner to Tps. 15 ~~and 16~~ Ranges 16 and 17 W. in mound of stone
Pits impracticable.
on 80 chs.
Rocky mountainous land.
Soil 3d rate. Timber scattered cedar.

80 chs.

BOOK A-168

3rd Standard Parallel South

T. 15 S. R 16 W

Bhs.

General description

The quality of land along this portion of the Standard, consist of small valleys surrounded by various chain of mountains - with 2nd rate soil - It is more adapted for grazing than farming purposes. There being no water on the land - and no mineral or timber. - Mountains are very rocky and in limestone formation - with few scattered cedars. -

3rd Standard Parallel South
T. 15 S. R. 17 W.

Chs. West on a true line, along the south boundary of section 36.
Variation 16° 27' E.

2.50 Top of ridge bears NW and SE

8.50 Hollow 500 links wide drains 36.

46.00 Set a limestone 22 X 14 X 5 in. 15 in. deep marked 1/4 on the north side in mound of rock for 1/4 sec. cor. Pits impassable.—

51.25 Top of high knoll on the ridge bearing southerly.

66.00 dry creek bed 50 links wide mit cedars ~~bears W~~ drains NE.

80.00 Set a sand stone 14 X 10 X 10 in. in. deep, marked 1 notch on the east and 5 notches on the west edges in mound of rock. Pits impracticable Standard for cor. run to sections 35 and 36.
Can 80 chains
Mountainous rocky land.
Soil 3rd rate. Timber scattered cedars.—

BOOK-A-168

wnship 15 S. R. 11 W.

1	6	5	4	3	2	1
12	7	8	9	10	11	12
13	18	17	16	15	14	13
24	19	20	21	22	23	24
25	30	29	28	27	26	25
36	31	32	33	34	35	36
165	57	56	55	54	53	52

3rd Standard Parallel South
T 15 S. R 17 W

Bks. West on a true line along the south boundary of section 35
Variation 16° 27' E.

5.50 a Gully ~~bears~~ ~~NW and~~ drains SE. and enters ridge with cedars.

40.00 Set a limestone 15 X 10 X 5 in. 10 in. deep, marked 1/4 on the west side, in mound of rock. for 1/4 S. corner. - Pits impracticable.

80.00 Set a limestone 15 X 10 X 8 in. 10 in. deep, marked 2 notches on the east and 4 on the west edges. in mound of rock and earth. Pits impracticable for Standard corner to sections 34 and 35

on 80. chains
Mountainous rocky land.
Soil 3rd rate. Timber cedars.
May 10th 1880.

3d Standard Parallel South
T. 15 S. Range 17 W.

Chs. West on a true line, along the south boundary of section 34.
Var. 16° 27' E..

11.60 High summit of the mountains bearing NW. and SE.

26.00 A Gulch, drain NW. ~~and SE.~~

40.00 Set a lime stone 13X8X6 in. 8 in deep. marked 1/4 on the north side in mound of stone and earth with 3 pits each 24X12X12 ~~in~~ for 1/4 sec. cor.

52.00 Ravine, drains NW. ~~and SE.~~

64.60 Ravine, drains NW. ~~and SE.~~

71.50 same ravine, drains ~~NE and~~ SW.

73.50 same ravine, drains NW. ~~and SE.~~

80.00 Set a sand stone 16X10X4 in 10 in deep marked 3 notches on the east and west edges with 3 pits each 24X12X12 in. mound of stone and earth. for Standard corner to sections 33 and 34.
on 80 chs
Land mountainous, 3 rods - with cedars.

40.00

67.50

75.00

80.00

3d Standard Parallel South
T. 15 S. Range 17. West.

Chs. West on a true line, along the south boundary of section 33.
Var. 16° 27' E.

40.00 Set a sand stone 19 X 8 X 6 in. 14 in. deep, marked 1/4 on the north side in mound of earth and stone with 3 pits each 24 X 12 X 12 in. for 1/4 sec. cor.

67.50 Summit of the mountain bears N. & S.

75.00 Limestone ledge bears N. & S.

80.00 Set a limestone 18 X 12 X 10 in. 12 in. deep, marked 4 notches on the east and 2 on the west edge in mound of stone. Pits impracticable for Standard corner to sections 32 and 33; from which a cedar 14 in. dia. bears N. 37° W. 48 links distant.

on 80 chains
Land rocky and mountainous;
Timber scattered cedars. Soil 3d rate.

3d Standard Parallel South
T. 15 S. R 17 W.

Chs. West on a true line, along the south boundary of section 32.
Va. 16° 27' E.

6.50 Head of deep gulch, ~~running~~ draining S W.

40.00 Set a limestone 12 X 10 X 6 in. 8 in. deep, marked 1/4 on the north side in mound of rocks. Pits impractical. For 1/4 sec. cor.

66.00 A hollow 350 links wide ~~to S~~ drains S.

80.00 Set a limestone 14 X 10 X 5 in. 9 in. deep, in mound of stone and earth, with 3 pits, each 24 X 12 X 12 in. marked 5 notches on the east and 1 notch on the west edge. For Standard corner to sections 31 and 32.

Land mountainous and rocky on 80. chains
3d rate. Timber for scattering cedars.—

Chs.

2.00

8.00

34.75

40.00

45.00

64.50

80.00

3rd Standard Parallel South
T. 15 S. - R. 17 W.

Chs. West on a true line, along the south boundary of section 31.
Va. 16° 27' E.

2.00 A gully 50 links wide, ~~bears NE and~~ drains SW

8.00 A hollow 4.00 chs wide, ~~bears NW~~ drains SE.

34.75 Top of ridge bears NW. and SE.

40.00 Set a limestone 16 X 10 X 5 in. 10 in. deep. marked 1/4 on the north side, in mound of stone and earth, with 3 pits each 24 X 12 X 12 in. for 1/4 sec. cor.

45.00 A hollow 3.00 chs wide, ~~bears NW and~~ drains SE. and end of cedars.—

64.50 top of mountain bears NW and SE.

80.00 Set a limestone 20 X 12 X 8 in. 15 in. deep. marked 6 notches on the North, East and West edges, in mound of rock and earth, with 3 pits each 36, X 18 X 18 in. for corner to T. 15 ~~and 16~~ S. Rs. 17 and 18 W. Standard (on 80 chain) Soil Land mountainous, 3rd rate. No timber except few scattered cedars.—

3d Standard Parallel South
T. 15 S. R 17 W

General description
The land on both sides of this portion of the standard line is high and mountainous, broken by deep gulches and ravines. The formation is limestone. — Portion of this land is overgrown by cedars. Soil 3d rate unfit for cultivation, except for grazing purposes —
No mineral found. —

3d S
T. 15

Bho.

20.50
39.00
40.00

60.00
76.00
80.00

3d Standard Parallel South
T. 15 S. R. 18 W.

Chs. West on a true line along the south boundary of section 36.
Var. 16° 28' E.

20.50 Enter ravine, bearing W. course W.

39.00 Leave same ravine, bearing S.W.

40.00 Set a limestone 15 X 8 X 10 in. 10 in. deep. marked 1/4 on the north side, in mound of stone and earth, with 3 pits. each 24 X 12 X 12 in. for 1/4 sec. cor.

60.00 Ravine 100 links wide, bearing W.

76.00 A knoll on top of the ridge bearing NE.

80.00 Set a limestone 12 X 10 X 6 in. 8 in. deep. marked 1 notch on the east. and 5 notches on the west edge. with 3 pits each 24 X 12 X 12 in. for Standard corner to sections 35 and 36.

on 80 chains
Land Mountainous and rocky;
Soil 3d rate.— No timber —
May 11th 1880.

BOOK-A-168

Township 15 S. R. 18 W.

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36
64	63	62	61	60	59

BOOK-

nship 15 S.

6	5	4
7	8	9
18	17	16
19	20	21
30	29	28
31	32	33
64	63	62

60 3d Standard Parallel South
T. 15 S. R 18 W.

Chs. West on a true line, along the south boundary of section 35
Va. 16° 28' E.

5.00 Leave mountains and enter Salt marsh Valley, bearing N.W. and S.E.

39.80 A Trail bears N.E. and S.W.

40.00 Set a limestone 11 x 8 x 7 in. 7 in. deep. marked 1/4 on the north side. in mound of earth. with 3 pits each 24 x 12 x 12 in. for 1/4 sec. cor.

80.00 Set a limestone 13 x 7 x 6 in. 8 in. deep. marked 2 notches on the east and 4 notches on the west edges. in mound of earth. from 3 pits each 24 x 12 x 12 in. for Standard corner to sections 34 and 35.

Mountainous on 5.00 chains.

Balance Gently rolling valley land.
Soil 2nd rate. No timber —
East end in the mountains. —

BOOK-A-
3d St
T.

Chs.

40.00

42.00

5355

80.00

3rd Standard Parallel South 61
T. 15 S. R 18 W

80 West on a true line, along the South boundary of Sec. 34.
Va. 16° 28' E.

42.00 Set a limestone 12 X 7 X 7 in. 8 in. deep. marked 1/4 on the N. side in mound of stone and earth with 3 pits each 24 X 12 X 12 in. for 1/16 sec. cor.

42.00 Ravine 150 links wide, ~~drains~~ ~~And~~ SW

53.55 Trail bears NE. and SW.

80.00 Set a limestone 12 X 8 X 6 in 8 in. deep. marked 3 notches on the east and west edges in mound of earth. from 3 pits each 24 X 12 X 12 in. for Standard corner to sections 33 and 34.

Valley Land. Soil 2nd rate
No timber.

3rd Standard Parallel South
T. 15 S. R 18 W.

Chs. West on a true line, along the south boundary of section 33.
N. 16° 28' E.
23.40 Wood 30 links wide, ~~across~~ drains
40.00 Set a limestone 15X10X8 in. 10 in. deep, marked 1/4 on the north side, in mound of earth, from 3 pits each 24X12X12 in. for 1/4 sec. cor.
59.40 Road bears NW and SE
80.00 Set a limestone 14X8X6 in. 7 in. deep, marked 4 notches on the east and 2 on the west edges in mound of earth, from 3 pits each 24X12X12 in. for Standard corner to sections 32 and 33

Valley land. Soil 2nd rate
No timber.

BOOK A. 1

Chs.
40.00
68.00
80.00

Standard Parallel South
T. 15 S. R. 18 W.

Chs. West on a true line, along the south boundary of sec. 32.
N. 16° 28' E.

40.00 Set a lime stone 13 X 9 X 6 in. 8 in deep, marked 1/4 on the north side in mound of earth, from 3 pits each 24 X 12 X 12 in. for 1/4 sec. cor.

68.00 Enter Salt marsh meander mile 30 chs South, draining fresh water springs. Northerly, ~~East~~ ~~Southerly~~.

80.00 Set a lime stone 12 X 8 X 6 in 8 in deep, in mound of stone and earth, from 3 pits each 24 X 12 X 12 in. marked 5 notches on the east and 1 notch on the west edges for Standard corner to sections 31 and 32.

Valley land Soil 2nd rate.
~~West~~ and. West end Salt Marsh mile fresh water springs. No timber.

3rd Standard Parallel South
T. 15 S. - R. 18 W.

16th.

16th.

West on a true line along the south boundary of sec. 31.
Va. 16° 28' E

14.00 From a stone meander bears NW. and SE. with Springs running NW.

31.25 Set Gulf Water Lake bears Northerly and S.

40.00 Set a lime stone 13 X 8 X 6 in. 8 in deep, marked 1/4 on the north side, in mound of earth from 3 pits each 24 X 12 X 12 in. for 1/4 sec. cor. in dry bottom of the Lake

5850. across the Lake which bears Northerly about 4 miles and S.E. about 1/2 mile distance, and Enter meander

8000 Set a lime stone 24 X 12 X 12 in. 16 in deep, marked 6 notches on the north, east and west edges, in mound of stone and earth, from 3 pits each 30 X 18 X 18 in. for corner to Tr. 15 S. R. 18 W. 19th Salt marsh and meander land, partly covered with Alkali bottoms of the Lake. Soil 2nd and 3rd rate. Timber.

Jr. Standard Parallel South
T. 15 S. = R. 18 E.

Ch's.

General description

The first mile on the east along this portion of the Standard is mountainous. - 2nd 3d and 4th bench and valley land. Soil 2nd rate balance level, partly valley - salt marsh and meadow land with fresh water springs. well adapted for grazing purposes. This Line crosses the Southern end of Little Salt Water Lake, which extends Northerly for about 4. miles in length and 2 miles in width. - The Salt gathered in this Lake, is extensively used by Nevada Mining Co. for milling and reduction of silver ores.

No timber or mineral except salt. -

3rd Standard Parallel South
T. 15 S. R 19 W.

Chs. West on a true line, along the south boundary of sec. 36.
Va. 16° 30' E.

23.00. Fresh water spring 150 links wide runs N.E heads S.W.

40.00 Set a limestone 14 X 10 X 6 in. 9 in. deep. marked 1/4 on the north side in mound of earth. pawn 3 pits each 24 X 12 X 12 in. for 1/4 sec. cor.

80.00. Set a limestone 13 X 12 X 8 in. 8 in. deep. marked 1 notch on the east and 5 notches on the west edges. in mound of earth pawn 3 pits each 24 X 12 X 12 in. for Standard corner to sections 35 and 36.

First rate meadow land.
No timber.

BOOK-A

BOOK-A-168

nship 15 S. R. 19 W

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36
71	70	69	68	67	66

1 12 13 24 25 36

54

The Standard Parallel South
T. 15 S. R 19 W

80 chs. West on a true line, along the south boundary of sec. 35.
Va. 15° 30' E.

28.00 Leave meadow, enter level greasewood valley bearing North and South

40.00 Set a limestone 14 X 10 X 6 in 9 in deep. marked 1/4 on the north side in mound of earth, from 3 pits each 24 X 12 X 12 in. for 1/4 sec. cor.

61.50 Willow on meadow Springs head S.W. run N E.

78.50 Leave springs & meadows, and enter valley bearing N E and S W.

80.00 Set a limestone 13 X 8 X 6 in 8 in. deep, marked 2 notches on the east and 4 notches on the west edges in mound of earth, from 3 pits each 24 X 12 X 12 in for Standard corner sections 34 and 35

Meadow and valley land
Soil 1st rate.

3rd Standard Parallel South
T. 15 S. R 19 W.

0 hrs.	West on a true line, along the south boundary of sec. 34.
	Va. 16° 30' E.
40.00	Set a limestone 11 X 8 X 6 in. 7 in. deep, marked 1/4 on the north side, in mound of earth from 3 pits each 24 X 12 X 12 in. for 1/4 sec. cor.
63.50	Road bears N 0° E and S E.
80.00	Set a limestone 14 X 8 X 5 in. 9 in. deep, marked 3 notches on the east and west edges, in mound of earth from 3 pits each 24 X 12 X 12 in. for Standard corner to sections 33 and 34.
	Level grassy wood valley land Soil 1st rate.

3rd St. Par.
T. 15 S.

0 hrs. W
the

1.50 A
W
29.90 Set
37.00 Be
40.00 Set
m
of
Ge
ha
a
8
53.75 L
75.00 Le
4
79.75
80.00

3rd Standard Parallel South 69

T. 15 S. R. 19 W.

6 chs.	West on a true line, along the south boundary of sec. 33. Va. 16° 30' E.
1.50	A Road to Miller's Ranche bears NW. and SE.
29.90	Spring Creek 15 links wide runs S.E.
37.00	Cultivated field bears NW & SE.
40.00	Set a lime stone 17 X 10 X 10 in 11 in deep marked 1/4 on the north side in mound of earth, from 3 pits each 24 X 12 X 12 in for 1/4 sec. cor. from which Miller's house bears N 50 W. about 15.00 chs distant and Smith's house bears S. 40° W. about 25.00 chs distant.
53.75	A Road bears N. and S.
75.00	Leave field & Enter valley bearing NW. and S.E.
79.75	A Road bears NW and SE.
80.00	Set a lime rock 16 X 10 X 8 in. 10 in. deep, marked 4 notches on the

To 3d Standard Parallel South
T. 15 S. R. 19 W.

Chs. east and 2 notches on the west edges, in mound of earth from 3 pits each 24 X 12 X 12 in. for corner to sections 32 and 33.

Valley and cultivated level land Soil 1st rate. No timber.

West on a true line, along the south boundary of sec. 32
Va. 16° 30' E.

16.85 Water ditch bears NW and SE.

40.00 Set a limestone 14 X 8 X 6 in. 9 in. deep, marked 1/4 on the north side, in mound of earth from 3 pits each 24 X 12 X 12 in. for 1/4 sec. cor.

51.50 deep Wash 50 links wide.

3rd Standard Parallel South
T. 15 S. R 19 W.

Obs. ~~bears~~ drains NE. ~~and Ells~~ from which point Murphy's house bears Northerly about 30 chs. distant— and enter bench land bearing NE + SW.

80.00 Set a limestone 18 X 14 X 9 in. 12 in. deep, marked 5 notches on the east and 1 notch on the west edges in mound of earth, from 3 pits, each 24 X 12 X 12 in. for Standard Corner to secs. 31 and 32.

Valley and bench land. Soil 2nd rate. No timber—

West on a true line, along the south boundary of sec. 31.

Va. 16° 30' E.

40.00 Set a limestone 12 X 10 X 8 in.

3d Standard Parallel South
T. 15 S. R. 19 W.

Chs. in. deep, marked 1/4 on the north side, in mound of earth, from 3 pits each 24 X 12 X 12 in. for 1/4 sec. cor.

80.00 Set a lime stone 18 X 12 X 10 in. 12 in deep, marked 6 notches on the north East and West edges, in mound of stone and earth, with 3 pits each 24 X 12 X 12 in. for Standard corner to township 15 South, Ranges 19 and 20 West; from which bears head of Warm Springs bears Northerly about 20.00 chs distant at the foot of a high peak leaning Northerly.

Bench land. Soil 2nd rate No timber.

General description.

There is a large portion of good farming and meadow land along this portion of the Standard line, and it should be subdivided.

No mineral or timber.

Standard Parallel South
T. 15 S. R 20 W

Sho. West on a true line, along the south boundary of sec. 36.
Va. 16° 30' E.

21.16. Intersected the boundary line between Utah and Nevada;
South 60.30 chains, from 129th mile corner on said boundary.
No 130th mile corner found.—
where I set a limestone 16X10 X8 in. 10 in. deep, in mound of rock and earth with 3 pits, each 24 X 12 X 12 in. marked C. C. U. on the east and N. on the West side with 6 notches on the South and North edges. and I posted on the east to fractional sec. 36.
for Closing Corner, ~~between Tps 15~~ and 16 S. in Range 20 W ~~in Sec 36~~

Bench gravelly land. Soil 3d rate. No timber.
May 13th 1880.

BOOK-A-168

Township 15 S **R.** 20 W

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

194 3d Standard Parallel South
T. 15 S. R 20 W.

General description.
The land along this portion
of the standard is gravely
and partly mountainous being
unfit for cultivation. —
No mineral or timber.

Joseph Gorlinski
U.S. Dep. Surveyor.

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, Aug 14 1880

The foregoing field notes of the survey of the

3d Standard Parallel South

~~*Township No*~~ through *Range No,* 10.11.12.13.14 15.16.17.18.19 & 20 W.
of the Salt Lake Meridian, Utah Territory,

Executed by Joseph Gorlinski

Under his *contract No* 93

of the 3 *day of* June 1879.

in the month of May 1880,

having been critically examined. the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.

Jde. Salomon.

U. S. Surveyor General for Utah.

Copied

BOOK A. 168

Book 168 No. 2 96

Filed July 21st 1880.

Examined by F. C. Bailey

Compared by F. C. Bailey

FIELD NOTES

OF

THE SURVEY OF THE

2nd Guide Meridian, West,
from 3d to 2d Standard Par's.
~~of Township No.~~ between, Ranges No. 14 & 15 W.

of the Salt Lake Meridian in Utah Territory.

BY

Joseph Gorlinski

U. S. DEPUTY SURVEYOR,

Under his Contract No. 93

dated June 3d 1879

Survey commenced May 15th 1880.

Survey completed May 20th 1880

2nd Guide Meridian West
T. 15 S. Rs. 14 and 15 W.

lks. Begin at the Standard Corner ~~between~~ to Tps. 15 ~~and 16~~ S. Rs. 14 + 15 W. on 3rd Standard Parallel South, previously established,

Thence

North on a true line bet. Secs. 31 + 36.

Var. 16° 32' E.

.00 Set Limestone, 11 x 7 x 7 in., 8 in. deep, in mound of Earth, marked 1/4 on W. Side, with 4 pits, each 24 x 12 x 12 for 1/4 sec. cor.

.00 Set Limestone, 12 x 8 x 7 in., 8 in. deep, in mound of Earth, marked 1 notch on S. + 5 notches on N. Edges, with 4 pits each 24 x 12 x 12 in., for cor. to secs. 25, 30, 31 + 36.

lchs. Alkali flat with Grea... lchs.

wood mounds.

Soil 3rd Rate. No Timbe...

North on true line
between secs. 25 + 30.
Va. 16° 32' E.

40.00 Set Limestone, 10 x 8 x 7 in. 7.50
6 in. deep, in mound of
Earth, marked 1/4 on N.
Side, with 4 pits, each 24 29.50
x 12 x 12, for 1/4 Sec. cor. 40.00

80.00 Set Limestone, 10 x 7 x 7...
6 in. deep, in mound of
Earth, marked 2 notches
on S. + 4 notches on N. ...
ges, with 4 pits, Each 2... 80.00
x 12 x 12, for corner to

2nd Guide Meridian West

BOOK-A-168

T. 15 S. Rs. 14 + 15 W.

lks. Secs. 19, 24, 25 + 30.
Alkali flat with grease-
wood mounds. —
Soil 3rd rate. No Timber.

North on a true line
between Secs. 19 + 24
Va. 16° 32' E.

7.50 Leave Alkali. Enter level
valley, bearing NE. + SW.

29.50 Wash, 25 lks. wide, drains NE

40.00 Set Limestone, 10 x 8 x 6 in.
6 in. deep, in mound of
earth, marked 1/4 on W.
side, with 4 pits, each 24
x 12 x 12 ins, for 1/4 Sec. Cor.

80.00 Set white Sandstone, 12 x 8 x 6
in. 8 in. deep, in mound

chs.		chs.
	of earth, marked 3 no...	
	on S + 3 notches on N. ed...	80.00
	with 4 pits, each 24 x 12 x 12...	
	for cor. to Secs. 13, 18, 19 + 2...	
	Land, level covered with...	
	Grass wood.	
	Soil 2nd rate. No Timber...	
	North on a true line	
	between Secs. 13 + 18	
	Va. 16° 32' E.	
40.00	Set Limestone, 12 x 8 x 6...	
	8 in. deep, in mound of...	
	Earth, marked 1/4 on W...	
	side, with 4 pits, each...	
	24 x 12 x 12 in, for 1/4 Sec. Cor...	40.00
46.50	Wash 10 lks. wide, ~~Land~~ drain...	
	NE ~~Still~~ Enter Alka...	

2nd Guide Meridian West
T. 15. S. Rs. 14 + 15 W.

BOOK-A-168

chs. Witness trees, Bears. NW + SE.

80.00 Set Limestone, 14 x 7 x 5 in. 9 in. deep, in mound of earth, marked 4 notches on S. + 2 notches on N. edges, with 4 pits, each 24 x 12 x 12, for cor. to secs. 7. 12. 13 + 18.

Land alkali with greasewood.

Soil 3rd rate. No Timber.

North on a true line between secs. 7 + 12

Va. 16° 32' E.

40.00 Set Limestone, 11 x 8 x 6 in. 7 in. deep, in mound of earth, marked 1/4 on W.

2nd Guide Meridian West
Tp. 15 S. Rs. 14 + 15 W.

chs.		chs.
	sides, with 4 pits, each 24 X 12 X 12 in. for 1/4 sec.	
80.00	Set Limestone, 12 X 8 X 7 8 in. deep, in mound of Earth, marked 5 notches on S. + 1 notch on N. edge with 4 pits, each 24 X 12 X 1 for cor. to secs. 1. 6. 7 + 12	80.00
	Sand Alkali with grease wood.	
	Soil 3rd rate. No Timber	

North on a true line between secs. 1 + 6.

Va. 16° 32' E.

40.00	Set Limestone, 13 X 6 X 4 8 in. deep, in mound of earth, marked 1/4 on E.	

2nd Guide Meridian West
BOOK-A-168
Tps. 15 S. Rs. 14 + 15 W.

chs.

Side, mth 4 pits, each 24 x 12 x 12 in, for 1/4 Sec. cor.

80.00 Set Red Sandstone, 14 x 6 x 5, 9 in. deep, in mound of earth + stone, marked 6 notches on the N. S. & + W. edges, mth 4 pits, each 24 x 12 x 12 in, for cor. to Tps. 14 + 15 S. Rs. 14 + 15 W.

Land alkali, covered with Greasewood.

Soil 3rd rate. No Timber.

General Description

Nearly all land along this portion of the Meridian is alkali + unfit for cultivation. No mineral or timber.

2nd Guide Meridian West
Tp. 14. S. Rs. 14 + 15 W.

chs.		chs.
	North on a true line between Secs. 31 + 36. Va. 16° 32' E	
20.00	Leave, alkali flat. Enter level valley, bears NE. + SW.	40.00
40.00	Set Limestone, 12 x 6 x 7 8 in. deep, in mound of earth, marked 1/4 on W. side, with 4 pits, each 24 x 12 x 12, for 1/4 Sec. Cor.	
80.00	Set Limestone, 13 x 8 x 5, 8 in. deep, in mound of earth + stone, marked 1 notch on S. and 5 notches on N. edges, with 4 pits, each 24 x 12 x 12 in. for Cor. to Secs 25. 30. 31 + 36.	53.00 80.00
	Land, level valley with greasewood + shadscale. Soil 2nd rate, No Timber	

BOOK-A-168

Township 111 S. **R.** 14 W

90	6	5	4	3	2	1
89	7	8	9	10	11	12
84	18	17	16	15	14	13
86	19	20	21	22	23	24
85	30	29	28	27	26	25
84	31	32	33	34	35	36

BOOK-

nship 13 S

6	5	4	
7	8	9	
18	17	16	
19	20	21	
30	29	2	
31	32	3	

2nd Guide Meridian West—
Tp. 14 S. Rs. 14 + 15 W.

chs.	
	North on a true line between Secs. 25 + 30. Ta. 16.32' E.
40.00	Set Conglomerate, 12 x 10 x 5 in. 8 in. deep, in mound of earth + stone, marked 1/4 on W. side, with 4 pits, each 24 x 12 x 12, for 1/4 Sec. corner.
53.00	Wash, ~~Lodraun~~ NE ~~Lake~~
80.00	Set Limestone, 12 x 6 x 8 in. 8 in. deep, in mound of earth + stone, marked 2 notches on S. + 4 on N. edges, with 4 pits, each 24 x 12 x 12 in. for corner to Secs. 19. 24. 25 + 30.
	From this corner mountains with iron

chs. indications, bearing N. + S. lie about 3/4 mile West.

Land, level valley mtl. grasswood + shadscale.

Soil 2nd rate. No Timber

North on a true line between Secs. 19 + 24.

Va. 16° 32' E.

40.00 Set Limestone, 11 x 8 x 7 in. 7 in. deep, in mound of Earth + stone, marked 1/4 on W. side, with 4 pits, each 24 x 12 x 12, for 1/4 Sec. Cor.

55.00 Wash, 20 lks. wide, ~~Land~~ NE ~~* Xxx~~.

58.50 Wash 25 lks. wide, ~~Land~~

chs. 7
8.00 8
E
3
n
T
n

29.75
40.00

2nd Guide Meridian West
BOOK-A-168
T. 14 S. Rs. 14 & 15 W.

chs.	
	NE & ~~[illegible]~~.
80.00	Set limestone, 12 x 8 x 5 in. 8 in. deep, in mound of earth & stone, marked 3 notches on N & S edges with 4 pits, each 24 x 12 x 12 in. for cor. to Secs. 13. 18. 19 & 24. Sand gravelly; gently rising. Soil 2nd rate; No Timber. May 15th 1880.
	North on a true line between secs. 13 & 18. Va. 16° 32' E.
29.75	Wash, 25 lks. wide, ~~[illegible]~~ S. E.
40.00	Set limestone, 12 x 8 x 6 in, 8 in. deep, in mound of stone & earth, marked 1/4

2nd Guide Meridian West
Tp. 14. S. Rs. 14 & 15 W.

BOOK-A

chs.		chs.
	on W. side, with 4 pits, each 24x12x12 in, for 1/4 sec. corner.	
67.50	Dry creek, 50 lks. wide, ~~[illegible]~~ drains S E.	40.00
75.50	Branch of same creek runs S E.	
80.00	Limestone, 15x8x6 in, 10 in. deep, in mound of earth & stone, marked 4 notches on S. & 2 notches on N. edges, with 4 pits, each 24x12x12 in. for corner to secs. 7. 12. 13 & 18.	80.00
	Land, valley with grease wood.	
	Soil 1st rate. No Timber	

2nd Guide Meridian West

BOOK-A 168

Tp. 14. S. Rs. 14 & 15 W.

chs. North on a true line between Secs. 7 + 12.

Va. 16° 32' E.

40.00 Set Limestone, 16 X 8 X 5 in. 10 in. deep, in mound of earth + stone, marked 1/4 on W. side, with 4 pits, each 24 X 12 X 12 in. for 1/4 Sec. Cor.

80.00 Set Limestone, 14 X 12 X 5 in. 9 in. deep, in mound of earth + stone, marked 5 notches on S. + 1 on N. edges, with 4 pits, each 24 X 12 X 12 in for cor. to secs. 1. 6. 7 + 12.

Beech land

Soil 2nd rate No Timber.

9th 2nd Guide Meridian West
Tp. 14. S. Rs. 14 + 15. W.

chs.	
	North on a true line between Secs. 1 + 6. Va. 16° 32' E.
10.00	Edge of bluff bears NE & SW
22.00	" " " " NW + SE
30.00	" " " " SW. + NE
40.00	Set limestone, 14 x 10 x 8 in. 9 in. deep, in mound of earth + stone, marked 1/4 on W. side, with 4 pits, each 24 x 12 x 12 in. for 1/4 Sec. Cor.
42.75	Wash ~~Stream~~ NW ~~SE~~ Enter Mountainous land
55.00	Gulch ~~Stream~~ SW
72.10	" "
80.00	Limestone, 16 x 10 x 6 in. 10 in. deep, in mound of earth + stone, marked 6 notched on N. S. E + W

2nd
Tp.

chs.

Range

of the

chs. edges, with 4 pits, each 24 x 12 x 12 in. for corner to Tps. 13 + 14 S. Rs. 14 + 15 West, from which S. end of Fish Spr. Range bears Easterly about 2 mile distant.

First 1/2 mile, beuch: one 37.25 chains
Second, mountainous,
Soil 2nd + 3rd rate.
No Timber

General Description

The land along this portion of the Meridian is mostly in the valley + adapted for cultivation, except a little in the north which is mountainous + has no mineral or Timber
Soil 2nd + 3rd rate.

2nd Guide Meridian West
Tp. 13. S. Rs. 14 + 15 W.

2nd
BOOK A
Tp.

Chs.		Chs.
	North on a true line between secs. 31 + 36. Va. 16° 32' E.	
1.00	Gulch, ~~bears NE~~ drains SW	
11.50	Ravine " " " "	
15.00	Leave ravine.	
29.50	Gulch, ~~bears NE~~ drains SW.	
40.00	Set limestone, 15 x 8 x 6 in. 10 in. deep, in mound of stone, marked 1/4 on W. side, with 4 pits, each 24 x 12 x 12 in. for 1/4 Sec. Cor.	2.25 10.50 15.00
60.00	Wash 50 lks wide, head NE. bears SW.	40.00
66.75	Dry bed, 100 lks wide, ~~bears~~ drains ~~SE~~ SW.	
80.00	Limestone, 20 x 10 x 8 in. 15 in. deep, in mound of stone, marked 1 noted	42.25 54.50

BOOK-A-168

nship 13 S R. 14 W.

1	6	5	4	3	2	1
12	7	8	9	10	11	12
13	18	17	16	15	14	13
24	19	20	21	22	23	24
25	30	29	28	27	26	25
36	31	32	33	34	35	36

2nd Guide Meridian West
BOOK-A-168
Tp. 13. S. Rs. 14 + 15. W.

Chd. on S. + 5 notches on N. edges for cor. to Secs. 25. 30. 31 + 36
Said, mountainous
on 80. chains —
Soil 3rd rate. No Timber —

North on a true line
between Secs. 25 + 30.
Va. 16° 32' E.

2.25 Wash, 25 lks. wide, drains SW
10.50 " 50 " " " " "
15.00 Gulch 25 " " " " "
40.00 Set limestone, 13 x 10 x 5 in.
8 in. deep, in mound of
stone + earth, marked 1/4
on W. side, with 4 pits, each
24 x 12 x 12 in. for 1/4 Sec. Cor.
42.25 Dry creek bed, drains SW.
54.50 Wash 50 lks. wide. " "

942nd Guide Meridian West
Tp. 13 S. Rs. 14 & 15 W.

chs.		chs.
59.50	Hollow, 250 lks wide, drains S.W.	
63.00	" " " "	
74.00	Gulch, drains SW.	
80.00	Set Limestone, 20x12x8 in. 15 in. deep, in mound of stone, marked 2 notches on S. & 4 notches on N. edges, with 4 pits, each 24x12x12 ins. for cor. to secs. 19. 24. 25 & 30. Land mountainous Soil 3rd rate. No Timber.	60.75 80.00

North on a true line between Secs. 19 & 24
Va. 16° 38' E.

40.00	Limestone 15x10x7 in. 12 in.	4.00

chs. deep, in mound of stone,
marked 1/4 on W. side,
with 4 pits, each 24 x 12 x 12,
for 1/4 Sec. Cor.

60.75 Dry bed, 75 lks. wide, drains SW

80.00 Set limestone, 15 x 10 x 10 in.
10 in. deep, in mound of
stone, marked 3 notches
on N + S. edges, with 4
pits, each 24 x 12 x 12 in.
for Cor. to Secs. 13. 18. 19 + 24
on 80 chains
Land, mountainous
Soil 3rd rate. No Timber.
May 17th 1880.

North on a true line
between Secs. 13 + 18.
Va. 16° 32' E.

4.00 Rocky wash in gulch, 2.00

2nd Guide Meridian West

Tp. 13 S. Rs. 14 + 15 W.

Chs.		Chs.
	lks. mds, ~~drains~~ SW.	
40.00	Set Sandstone, 14 x 9 x 8 in. 9 in. deep, in mound of stone, marked 1/4 on W. side, with 4 pits, each 24 x 12 x 12 in. for 1/4 Sec. Cor.	32.00
		40.00
78.00	Rocky wash in gulch, 200 lks. wide, ~~Land~~ drains SW.	
80.00	Set Limestone, 16 x 8 x 7 in. 10 in. deep, in mound of earth + stone, marked 4 notches on S. + 2 on N. edges, with 4 pits, each 24 x 12 x 12 in. for Cor. to Sec 8. T. 12. R. 13 + 18	48.00
		80.00
	Land. mountainous + rocky on 80 chains	
	Soil 3rd rate, no timber.	

2nd Guide Meridian West
BOOK-A-168
Up. 13. S. Rs. 14. & 15. W.

chs.	
	North on a true line between Secs. 7 & 12 Va. 16° 32' E.
32.00	Wash, 30 lks wide, ~~Virginia~~ ~~[illegible]~~ W.
40.00	Set limestone, 14 X 8 X 8 in. 9 in deep, in mound of stone, marked 1/4 on W. side, with 4 pits, each 24 X 12 X 12 in. for 1/4 Sec. Cor.
48.00	Gulley, 100 lks wide, ~~Virgin~~ ~~[illegible]~~ W.
80.00	Limestone, 14 X 10 X 8 in, 10 in deep, in mound of stone, marked 5 notches on S. & 1 on N. edges, with 4 pits, each 24 X 12 X 12 in for Cor. to Sect. 1. 6. 7. & 12 Land, mountainous on 80 chains

98 2nd Guide Meridian West
T. 13 S. Rs. 14 + 15 W.

2nd
BOOK-A
p. 7

Soil 3rd rate
Scrub cedars

North on a true line
between secs. 1 + 6.
Va. 16° 32' E.

9.50 Dry creek bed, 50 lks. wide
heads NE runs SW.

15.00 Dry rocky bed, 150 lks wide
~~[illegible] drains~~ SW.

40.00 Set Limestone, 15 x 8 x 7 in.
10 in. deep, in mound of
stone, marked 1/4 on W.
side, with 4 pits, each 24
x 12 x 12 in, for 1/4 sec. Cor.

80.00 Set limestone, 16 x 12 x 9 in.
10 in. deep, in mound of stone
marked 6 notches on the

chs.

chs. N. S. E + W. edges, with 4 pits, each 24 x 12 x 12 in, for cor. to Tps. 12 + 13 S. Rs. 14 + 15 W. on 80 chains

Land, mountainous,
Soil 3rd rate. Scrub cedars

General Description

The land along this portion of the Meridian is mountainous and in places rocky, it is non-mineral bearing + unfit for cultivation

The soil is 3rd rate.

There are a few scattered scrub cedars.

Summit of Fish Springs Mountains bears Easterly about 1¾ mile distant from N. end of this Meridian. —

2nd Guide Meridian West
100 Tp. 12. S. Rs. 14 + 15 W.

2nd G
BOOK-A-
Tp. 1

chs.		chs.
	North on a true line between Secs. 31 + 36 Va. 16° 32' E.	
40.00	Set limestone, 14 x 10 x 8 in. 10 in. deep, in mound of stone, marked /4 on W. side, with 4 pits, each 24 x 12 x 12 in. for /4 sec. Cor.	27.50
		40.00
75.00	Gulch, ~~Lime Ec~~ drains W.	
80.00	Set limestone, 14 x 10 x 8 in, 10 in deep, in mound of stone, marked 1 notch on S. + 5 notches on N. edges, pits impracticable, for Corner to Secs. 25. 30. 31 + 36	44.00
		"
		57.00
		63.25
	Land, mountainous on 80 chs.	80.00
	Soil 3rd rate	
	Timber, scattered cedars.	
	May 18th 1880.	

BOOK-A-168

Township 13 S. **R.** 14 W.

105	6	5	4	3	2	1
104	7	8	9	10	11	12
103	18	17	16	15	14	13
102	19	20	21	22	23	24
101	30	29	28	27	26	25
100	31	32	33	34	35	36

BOOK-A

ship 11 S. R

6	5	4	
7	8	9	
18	17	16	
19	20	21	
30	29	28	
31	32	33	

2nd Guide Meridian West 26
Bet. 12. S. Rs. 14 & 15 W. 101

chs.	North on a true line between Secs. 25 & 30. Va. 16° 32' E.
27.50	Dry trench 50 lks. wide, ~~drains~~ ~~E & W.~~
40.00	Set limestone, 14 x 6 x 8 in. 10 in. deep, in mound of stone & earth, marked 1/4 on W. side, with 4 pits, ~~each~~ 24 x 12 x 12 in. for 1/4 Sec. Cor.
44.00	Wash, ~~E & W.~~ drain
"	Foot of ridge bears E & W.
57.00	Ravine ~~E & W~~ drains
63.25	Top of ridge, bears E & W.
80.00	Set limestone, 14 x 8 x 6 in. 10 in deep, in mound of earth & stone, marked 2 notches on S. & 4 on N. edges with 4 pits, each 24 x 12 x 12 in.

2nd Guide Meridian West
Tp. 12. S. Rs. 14 + 15 W.

Chs	
	for cor. to Secs. 19. 24. 25 + 30.
	Land, mountainous
	Soil 3rd rate
	Timber, scattered Cedars.

North on a true line
between Secs 19 + 24.
Va. 16° 32' E.

17.75	Ravine bears E. & W. drains
25.00	Dry bed, runs E. & W.
40.00	Set limestone, 12 x 10 x 9 in. 8 in. deep, in mound of earth + stone, marked 1/4 on W. side, with 4 pits, each 24 x 12 x 12 in. for 1/4 sec. cor.
	This corner is in a Ravine, draining NW.
44.80	Gulch ~~bears~~ drains W.

2nd
BOOK-A-1
Tp. 1

Chs.	
63.75	
80.00	
	10
38.00	
40.00	

2nd Guide Meridian West
105
Tp. 12. S. bet. Rs. 14 + 15 W.

Chs.	
63.75	Wash, 100 lks wide, ~~bet. E + W.~~
80.00	Set limestone, 14 X 8 X 5 in. 10 in. deep, in mound of stone, marked 3 notches on N + S edges, pits impracticable, for cor. to Sect. 13. 18. 19 + 24. —
	Sand, mountainous, on 80 chains
	Soil 3rd. rate
	Timber, Scrub Cedars.

North on a true line between Sects. 13 + 18.
Va. 16° 32' E.

38.00	Dry brd, ~~[illegible]~~ drains NW ~~[illegible]~~.
40.00	Set a limestone, 17 X 10 X 9 in. 12 in. deep, in mound of

#2 164

2nd Guide Meridian West
Tp. 12. S. bet. Rs. 14 & 15 W.

Chs.	
	Earth & stone, marked 1/4 on W. side, pits impracticable for 1/4 sec. cor.
54.00	Dry bed ~~Leads E & W.~~ drains W.
60.00	Top of bluff bears NW & SE.
80.00	Set limestone, 14 x 12 x 6 in, on side of bluffs, 9 in deep, in mound of stone, marked 4 notches on S. & 2 notches on N. edges, (pits impracticable) for cor. to Secs. 7. 12. 13 & 18.
	Sand, mountainous. on 80 chains
	Soil 3rd. rate
	Timber, scrub cedars.

North on a true line
between Secs. 7 & 12
Va. 16° 32' E.

2nd G
BOOK-A-1
Tp. 1

Chs.
40.00
80.00

2nd Guide Meridian West
BOOK A-168
Tp. 12 S. bet. Rs. 14 + 15 W.

chs.

40.00 Set limestone, 15 x 8 x 7 in. 10 in. deep, in mound of stone, marked 1/4 on W. side, pits impracticable, for 1/4 Sec. Cor.

80.00 Set limestone, 16 x 12 x 8 in. 10 in. deep, in mound of stone, marked 5 notches on S + 1 notch on W. edges, pits impracticable, for Cor. to Secs. 1. 6. 7 + 12. on 80 chains
Said, mountainous.
Soil, 3rd rate
Timber, Scrub Cedars.

North on a true line between Secs. 1 + 6.

37 2nd Guide Meridian West
106 Tp. 12 S. bet. Rs. 14 & 15 W

chs.	Va. 16° 32' E.
14.75	Foot of Rocky, high ridge bears NW & SE.
24.50	Ravine ~~E & W~~ drains W.
38.50	" " "
40.00	Set a limestone, 14 x 8 x 6 in. 10 in. deep, in mound of Stones, marked 1/4 on W. side pits impracticable, for 1/4 sec. cor.
50.50	Deep gulch, ~~E & W~~ drains W.
67.00	Summit of mountains, bear NW & SE.
80.00	Set a limestone, 20 x 12 x 10 in. 15 in. deep, in mound of Stone, marked 6 notches on N. S. E & W edges, pits impracticable, for corner to Tps. 11 and 12 S. Rs. 14 and 15 W.
	Land, mountainous & rocky. on 80 chains. —

2nd
BOOK A-1
Tp. 12

BOOK-A-168

2nd Guide Meridian West
T. 12. S. Sect. R. 14 & 15 W.

37
107

Chs. Soil 3rd. rate
Timber, scrub cedars.
May 19th 1880

General Description

The land along this portion of the Meridian is mountainous & rocky, with scattered cedars.

The Soil is of a 3rd. rate quality & unfit for cultivation. There are no known minerals.

The Timber is cedars.

North end of Flint Springs Mountains bears N.E. about 1 mile distant from N. end of this Meridian

2nd Guide Meridian West
Tp. 11. S. Rs. 14 + 15 W.

chs.		chs.
	North on a true line between Secs. 31 + 36 Va. 16° 32' E.	
12.50	Top of high black Peak	20.00
26.50	deep hollow, drains W.	
40.00	Set limestone, 15 x 10 x 8 in. 10 in deep, in mound of stone, marked 1/4 on W. side, pits impracticable, for 1/4 sec. cor.	40.00
80.00	Set limestone, 18 x 8 x 8 in 12 in. deep, in mound of stone, marked 1 notch on S + 5 notches on N. edges, pits impracticable, for cor. to Secs. 25. 30. 31 + 36	(7) 54.75 80.00
	Land, mountainous 80 acres	
	Soil 3rd rate	
	Timber, cedars.	

BOOK-A-168

ship 11 S. R. 14 W.

1	6	5	4	3	2	1
12	7	8	9	10	11	12
13	18	17	16	15	14	13
24	19	20	21	22	23	24
25	30	29	28	27	26	25
36	31	32	33	34	35	36

2nd Guide Meridian West 109

Mp. 11. S. — bet. Rs. 14 + 15 W.

chs.

North on a true line between Secs. 25 + 30.
Va. 16° 32' E.

20.00 Top of knoll on mountain slope, bearing NE + SW.

40.00 Set Sandstone, 14x10x4 in., 10 in. deep, in mound of stone, marked 1/4 on W. side, pit impracticable, for 1/4 Sec. Cor.

54.75 Gulley, drain SW.

80.00 Set Sandstone, 20x10x10 in. 15 in. deep, in mound of stone, marked 2 notches on S. + 4 notches on N. edges, pits impracticable, for Cor. to Secs. 19 24 25 + 30.
80 chains
Land, mountainous.
Soil, 3rd rate.
Timber, scattering cedars.

2nd Guide Meridian West (56) 111
T. 1 N. S. bet. Rs. 14 & 15 W.

chs. For cor. to Secs. 13. 18. 19 & 24.
Mountainous on 7.50 Chains
Balance Bench & valley land
Soil 2nd rate
greasewood, undergrowth
No Timber.

North on a true line
between Secs. 13 & 18
T. 16° 32' E.

40.00 Set limestone, 14 X 7 X 6 ins.
10 in deep, in mound of
earth & stone, marked
1/4 on W. side, with 4 pits
each 24 X 12 X 12 in. for
1/4 Sec. Cor.

60.00 Overland road from Salt
Lake City to California
bears N. 45° W.

2nd Guide Meridian West
110 T. 1 p. U.S. bet. Rs. 14 + 15 W.

chs.	
	North on a true line bet. Secs. 19 + 24.
	Va. 16° 32' E.
6.75	Gulley, bears ~~NE + SW~~ drain
7.50	Gently sloping bench. and leave mouth of intermittent stream.
40.00	Set limestone, 13 X 8 X 6 in. 8 in. deep, in mound of stone + earth, marked 1/4 on W. side, with 4 pits, each 24 X 12 X 12 in. for 1/4 Sec. Cor.
45.00	Enter level valley land, bears NE + SW.
75.00	Enter greasewood flat, bears NE + SW.
80.00	Set limestone, 15 X 14 X 4 in. 10 in. deep, in mound of stone + earth, marked 3 notches on N + S. edges, with 4 pits, each 24 X 12 X 12 in.

2nd Guide
BOOK-A-1
1 p. 11

chs.	
	bal
	balance.
40.00	
80.00	

2nd Guide Meridian West (St) 111
T. 1 N. S. bet. Rs. 14 & 15 W.

chs. For cor. to Secs. 13. 18. 19 & 24.
Mountainous on 7.50 Chains
balance Bench & valley land
Soil 2nd rate
greasewood, undergrowth
No Timber.

North on a true line
between Secs. 13 & 18
Va. 16° 32' E.

40.00 Set limestone, 14 X 7 X 6 ins.
10 in deep, in mound of
earth & stone, marked
1/4 on W. side, with 4 pits
each 24 X 12 X 12 in. for
1/4 Sec. Cor.

60.00 Overland road from Salt
Lake City to California
bears NE & SW.

3rd Guide Meridian West
Tp. 11. S. bet. Rs. 14 + 15 W.

chs.		chs.
66.98	Telegraph line, bears NE & SW.	35.00
80.00	Set limestone, 14 x 8 x 6 in. 10 in. deep, in mound of earth + stone, marked 4 notches on S. and 2 notches on N. edges, with 4 pits, each 24 x 12 x 12 in. for cor. to Secs. 7. 12. 13 + 18. Valley land Soil 2nd rate greenwood, undergrowth, No timber.	40.00
		80.00

North on a true line between secs. bet. Secs. 7 + 12 Tn. 16° 32' E.,

2nd Guide
BOOK-A-16
Tp. 11.

S.
De
Se
10 i
ca
Se
24
Co
Se
8 c
ea
on
m
fo

2nd Guide Meridian West 113

Bet. 11. S. bet. Rs. 14 + 15 W.

chs.	
35.00	S. margin of American Desert, bears NE + SW.
40.00	Set limestone 15 X 10 X 5 in. 10 in. deep, in mound of earth, marked 1/4 on W. side, with 4 pits each 24 X 12 X 12 in. for 1/4 sec. cor.
80.00	Set limestone 13 X 8 X 6 in. 8 in deep, in mound of earth, marked 5 notches on S. + 1 notch on N. edges, with 4 pits, each 24 X 12 X 12 in, for cor. to secs. 1. 6. 7 + 12

Alkali, desert land.
Soil 3rd rate
No Timber.

chs. North on a true line between sections 1 + 6.
Va. 16° 32' E.

40.00 Set sandstone, 12 x 10 x 5 in. 8 in. deep, in mound of earth, marked 1/4 on W. side, with 4 pits, each 24 x 12 x 12 in, for 1/4 sec. cor.

80.00 To a point, 1 mile distant

95.75 dry slough bears NE + SW.

122.16 Intersect 2nd Standard Parallel South 37.08 chs. West from Standard corner to Township 10 ~~North~~ South between Rs. 14 + 15 West, where I set a quartzite stone, 17 x 10 x 6 in, 12 in deep, marked C. C. with 6 notches on S. E and W. edges, in

2nd Guide Meridian West 46 115
Tp. 11. S. bet. Rs. 14 + 15 W.

chs. mound of earth + stone,
from 3 pits, each 24 x 12 x
12 in. for closing corner
of 2nd Guide Meridian
West with 2nd Standard
Parallel South in Tp. 11. S.
between Rs. 14 + 15 W.

Alkali, desert land
Soil 3rd rate
No. timber.
May 20th 1880.

General Description

The land along this por-
tion of the Meridian is
on the first 2 miles, moun-
tainous + rocky, unfit for

2nd Guide Meridian West
Tp. 11. S. Rs. 14 + 15 W.

BOOK-A-

chs. cultivation, & the balance consists of bench, valley & alkali land having soils of 2nd & 3rd qualities. Northern end is covered by Great American Desert. There is neither mineral or timber, except some scattered cedars on the South end.

Joseph Gorlinski
U.S. deputy surveyor.

BOOK-A-168

117

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, Aug 14 1880

The foregoing field notes of the survey of the

2d Guide Meridian West, from the 3d to the 2d standard Parallel South

~~Township No~~ between Ranges No 14 & 15 W.

of the Salt Lake Meridian, Utah Territory,

Executed by Joseph Gorecki

Under his *contract No* 93

of the 3d *day of* June 1879,

in the month of May 1880,

having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.

Jno. Salmon.

U. S. Surveyor General for Utah.

BOOK-A-168
R.: 1884

Copied Book 168 R. 3

118

Filed July 21st 1880

Examined by F. C. Bailey

Compared by F. C. Bailey

FIELD NOTES

OF

THE SURVEY OF THE

4th Standard Parallel S.

of Township ~~No.~~ through, Ranges No. 9. 10. 11. 12
& part of 13 West.
of the Salt Lake Meridian in Utah Territory.

BY

Joseph Gorlinski

U. S. DEPUTY SURVEYOR,

Under his Contract No. 93.

dated June 3d 1879.

Survey commenced May 24th 1880.

Survey completed May 31st 1880.

BOOK-A-168

Township 20 S. **R.** 9 W



Township 20

4th Standard Parallel South
T. 20 S. - R. 9 W. 119

Chs. Begin at the post the es- 15
tablished corner to Townships
20 ~~2~~ S. R^s 8 and 9 W.

The post standing as agrees
with the description furnished
me by the office viz:
"Post in mound"

Thence
West on true line along
the S. boundary of Sec. 36
Var. 16° 15' E.

40.00 Set a quartzite stone 16×12×10 in.
10 in. deep marked 1/4 on N. side
in mound of earth, with 3 pits
each 24×12×12 in. for 1/4 Sec. Cor.
41.50 bench bears N.E. and S.W.
76.90 old road bears N.E. and S.W.
80.00 Set a Flint stone 11×8×5 in. 7 in.
deep marked 1 notch on E. and 5 on

Chs.	W. edges in mound of earth with 3 pits each 24×12×12 in. for Standard Cor. to Secs. 35 and 36. Land Rolling; Soil 2nd rate No timber.	Chs.
	West on true line along S. boundary of Sec. 35 Var. 16° 15' E.	23.45
40.00	Set Sand Stone 15×10×6 in. 10 in. deep marked 1/4 on N. side in mound of earth with 3 pits each 24×12×12 in. for 1/4 Sec. Cor.	40.00
		50.00
80.00	Set Sand Stone 14×10×6 in. 10 in. deep marked 2 notches on E. and 4 on W. edges in mound of earth with 3 pits each 24	72.00
		80.00

4th Standard Parallel South
20 L. R. 9 W.

Chs. x12x12 in. for corner to Secs 34 & 35
Gently rolling valley land; Soil
2nd rate; No timber.

West on true line along S.
boundary of Sec. 34.
Var. 16° 15' E.

23.45 wash, ~~drain N.E.~~ S.W. 10 links
wide, enter bench

40.00 Set sand stone 12x8x6 in. 8 in.
deep marked 1/4 on N. side in
mound of earth, with 3 pits each
24x12x12 in for 1/4 Sec. Cor.

50.00 foot of Beaver Range Mountains
bear N.E. and S.W.

72.00 top of ridge bears N.E. and S.W.

80.00 Set a Quartzite stone 12x10x4
in. 8 in. deep marked 3 notches

Fifth Standard Parallel South
T. 20 S. R 9 W.

Chs.		Chs.
Chs.	on E. and W. edges in mound of earth, with 3 pits each 24×12×12 in. for Standard cor. to secs 33 and 34.	54.50
		64.50
		80.00
	East half bench land; West half Mountainous and covered with undergrowth & Soil rocky and 3rd-rate. No timber. on 30.00 chains	

West on true line along S. boundary of Sec. 33
Var. 16° 15' E.

4.00	Ravine heads N.W. bears S.E.	
40.00	Set a Quartzite stone 14×7×6 in. 10 in. deep marked 1/4 on N. side in mound of earth with 3 pits each 24×12×12 in. for 1/4 Sec. cor.	11.00
		40.00

4th Standard Parallel South
T. 20 S. R. 9 W.

Chs.	
54.50	Ravine heads S.W. bears N.E.
64.50	Top of ridge bears N.E. & S.W.
80.00	Set a Quartzite stone 14×10×8 in. 10 in. deep marked 4 notches on E. & 2 on W. edges in mound of earth with 3 pits each 24×12×12 in. for Cor. to Secs. 32 & 33. Land mountainous & soil 3rd rate; No timber.

West on true line along S. boundary of Sec. 32.
Var. 16° 15' E.

11.00	Hollow and valley land bears North & South; leave mountains
40.00	Set Sandstone 14×6×5 in. 10 in. deep, marked 1/4 on N. side

F 4th Standard Parallel South
T. 20 S. R. 9 W.

4th

Chs

in mound of earth with
3 pits each 24×12×12 in.
for 1/4 Sec. cor.

44.00 old road bears N.W. and S.E. 52.50

80.00 Set red sandstone 12×10×5 74.50
in. 8 in. deep, marked 5 notches
on E. and 1 on W. edges in 76.00
mound of earth with 3 pits
each 24×12×12 in. for Standard cor
to Sect. 31 and 32 Mountainous 11 chs
Balance Valley and hollowland; Soil 80.00
2nd rate; No timber

West on true line along
S. boundary of Sec. 31.
Var. 16° 15' E.

40.00 Set sandstone 15×15×6 in.
10 in. deep, marked 1/4 on N.

4th Standard Parallel South
T. 20 S. R. 9 W.

WYA-A-168

Chs. Sided in mound of earth with
3 pits each 24×12×12 in. for
1/4 Sec. cor.

52.50 Wash 20 links wide drain N.E. & S.W.

74.50 Same wash ~~drain~~ ~~N.W.~~ & S.E.

76.00 Same wash drain N.E. & ~~S.W.~~
& foot of mountains bearing N.E.
and S.

80.00 Set Quartzite stone 24×10×5 in.
18 in. deep, marked 6 notched on
N.E. & W. edges, in mound of
stone & earth with 3 pits each
36×18×18 in. for Standard Corner to
Dn. 20. S. Ranges 9 & 10
West.

On 4.00 chs.
~~Rolling~~ Mountainous land.
Balance Rolling.
Soil 2nd rate No timber.

May. 24th 1880.

4th Standard Parallel South
T. 20 S. R. 9 W.

4th

Cls.

General Description

First 2 1/2 miles on the East along this Standard consist of valley and bench land; Soil 2nd rate; balance mountainous and hollow land; Soil 3rd rate; Not adapted for cultivation, but suitable for grazing purposes.	21,00
	32.00
	40,00
	46,50
	80,00
No timber, and no mineral found.	

4th Standard Parallel South
20 S. R 10 W.

127

Ss. West on true line along S. boundary of Sec. 36.
Var. 16° 15' E.

21,00 Top of ridge bears N.W. and S.E.

32.00 Ravine heads N.W. bears S.E.

40,00 Set a Quartzite stone 18×10×6 in. 12 in. deep, marked 1/4 on N. side in mound of earth with 3 pits each 24×12×12 in. for 1/4 Sec. cor.

46,50 Summit bears N.E. and S.W.

80,00 Set Quartzite 22×12×6 in. 16 in. deep. marked 1 notch on E. and 5 on W. edges in mound of earth with 3 pits each 24×12×12 in. for Corner to Secs 35 and 36.

Land mountainous on Southern Soil Stony; Thick cedar timber.

BOOK-A-168

Township 20 S **R.** 10 W.



1284 th Standard Parallel South
T. 20 S. R 10 W.

4 th
BOOK A-

Chs.		Chs.
	West on true line along S. boundary of Sec. 35 Var. 16° 15' E.	
19.50	Across summit bears N. E. and S. W.	10,00
40,00	Set Quartzite stone 15x12x8 in. 10 in. deep, marked 1/4 on N. side in mound of earth, with 3 pits each 24x12x12 in. for 1/4 Sec. Cor.	22,00
		27,00
		40,00
43.50	Deep ravine heads N. E. bears S. W.	
55,50	Top of ridge bears N. W. and S. E.	
80,00	Set Sand Stone 14x10x6 in. 10 in. deep, marked 2 notches on E. and W. edges in mound of earth with 3 pits each 24x12x12 in. for Standard Cor. to Secs. 34 and 35 on 80 chains. Land mountainous N. Soil 3rd rate; Thick Cedar timber.	53,50
		71,50
		80,00

4th Standard Parallel South
BUUM-A-168 T. 20 S. R. 10 W.

Chs.	
	West on true line along S. boundary of Sec. 34. Var. 16° 15' E.
10,00	Hollow ~~bears N.E.~~ drains S.W.
22,00	Across hollow ~~bears N.E.~~ drainage S.W.
27,00	Top of ridge bearing N.E.
40,00	Set Quartzite Stone 17×9×5 in. 11 in. deep, marked 1/4 on N. side, in mound of earth with 3 pits each 24×12×12 in. for 1/4 Sec. Cor.
53,50	Gulch 30 links wide heads N.E. bears S.W.
71,50	Top of ridge bearing N.E.
80,00	Set Quartzite Stone 18×12×10 in. 12 in. deep, marked 3 notches on E. and W. edges, in mound of earth with 3 pits each 24×12×12 in. for Standard Cor. to Secs 33 and 34.

130 4th Standard Parallel South
T. 20 S. R. 10 W.

4th P
Lou. R

Chs. Land Mountainous and rocky on 80 chains
Soil 3rd rate; Timber Scattering Cedars. Chs. 80,00

West on true line along S. boundary of Sec. 33
Var. 16° 15' E. Bilan

15.75 Wash, ~~beats~~ drains N.W. ~~S.E.~~

25.00 Wash 30 links wide bars N.W. and ~~S.E.~~ beaver dam on pt. beginning N.W. and S.E.

40.00 Set a Quartzite stone 16x10x4 ins. 10 ins. deep marked 1/4 on N. side, in mound of earth, with 3 pits each 24x12x12 ins. for 1/4 Sec. Cor. 1.50 40,0

51.00 Wash, ~~beats~~ drains N.W. ~~S.E.~~

61.00 Old road bears N.W. and S.E. and enters valley

4th Standard Parallel South
BOOK A-168 20 L. R. 10. W.

Chs.

80,00 Set Quartzite stone 16×10×8 in. 10 in. deep, marked 4 notched on E. and 2 on W. edges, in mound of earth with 3 pits each 24×12×12 in. for Standard Cor. to Sections 32 and 33. Mountainous on 25.00 chains Bitanu Level bench land; Soil 2nd rate; No timber.

West on true line along S. boundary of Sec. 32, Var. 16° 15' E.

1.50 Wash 25 links wide, drain N. W. and S. E.

40,00 Set a Limestone 13×10×5 in. 8 in. deep, marked 1/4 on N. side, in mound of earth, with 3 pits each 24×12×12 in. for 1/4 Sec. Cor.

134 th Standard Parallel South
T. 20 S. R 10 W.

Chs. 80.00 Set a quartzite stone 17×7×7 in. 11 in. deep, marked 5 notches on E. and 1 on W. edges, in mound of earth, with 3 pits each 24×12×12 in, for ~~Sixteenth~~ Cor. to Secs. 31 and 32.

Rolling valley land; (Soil 2nd rate); No timber.

West on true line along S. boundary of Sec. 31

Var. 16° 15' E.

15.25 Wash 25 links wide, ~~Chains~~ N. & S. ~~E & W~~

40.00 Set Grey Sandstone 16×12×8 in. 10 in. deep, marked 1/4 on N. side, in mound of earth, with 3 pits each 24×12×12 in. for 1/4 Sec. Cor.

Chs. 40.00

Chs. 47.00

80.00

4th Standard Parallel South
T. 20 S. R 10 W.

BOOK-A-168

Chs.
47.00 Dry margin on the East side of Revier Lake bearing N.E. and S.W. and enter dry bed of the Lake.

80.00 To a point at corner bet. Tps. 20 and 21 S. Rs. 10 and 11 W. in a mry bed of the Lake from which East 33 chains I have set a purple Sand-Stone 18×10×8 in. 12 in. deep in mound of stones, marked W.C. with 6 notches on the N.E. and W. edges for Witness Corner bet. Tps. 20 and 21 S. Rs. 10 and 11 W. on the East margin of dry bed of Revier Lake

East half level valley; Soil 2nd rate; No timber. West end in the dry bed of Revier Lake with

4th 134 Standard Parallel South
T. 20 S. R. 10 W.

BOOK-A-
Chs.

many bottoms; Alkali and Saline soil, No timber

May 25th 1880.

General Description

The land along this portion of the Standard in the 1st, 2nd, 3rd and a portion of the 4th mile is mountainous and rocky. On the West end covered with dry bed of Recien Lake; balance bench and valley land; Soil 2nd and 3rd rate. No timber or mineral.

30.00
40.00

80.00

Offset for 4th Standard Parallel S.
Through T. 20 S. R. 10 W.

BOOK-A-168

Chs. It being impracticable to continue the 4th Standard Parallel through Devils Lake and miry bottoms of the same I returned to the Standard corner bet. Secs. 33 and 34. on said Standard in T. 20 S. R. 10 W. previously established from which I run:

North bet. Secs. 33 and 34 on offset subdivision line
Var. 16° 15' E.

30.00 Leave mound pits and enter bench land bearing N. E.

40.00 Set sand stone 13 x 8 x 5 in. 8 in. deep marked 1/4 on W. side in mound of earth, with 4 pits each 24 x 12 x 12 in. for 1/4 Sec. Cor.

80.00 Set sand stone 12 x 9 x 7 in. 8 in. deep marked 1 notch

136 Offset for 4th Standard Parallel
Through T. 20 S. R. 10 W.

Chs. on S and 3 on E. edges, in mounds of earth with 4 pits each 24×12×12 in. for cor to Secs. 27, 28, 33 and 34. Beech land; soil 3rd rate No timber.

Mountains are 30.00 chains

North on true line bet. Secs. 27 and 28

Var. 16° 15' E.

9.25 Wash drains N.E. & S.W. and enter Sandy Soil.

40.00 Set Sand Stone 10×9×6 in 6 in. deep marked 1/4 on W. side, in mound of earth, with 4 pits each 24×12×12 in. for 1/4 Sec. cor.

55.00 Gully 5 links wide drains N.W.

Chs. 80.00
73.00
80.00
40.0

Off Set for 4th Standard Parallel South
Through T. 28 S. R 10 W.

Chs.

BOOK A-6 168

73.00 Leave beach and enter valley bearing N. E. and E. W.

80.00 Set Quartzite Stone 12 x 4 x 6 in. 8 in. deep, marked 2 notches on S and 3 on E edges in mound of earth, with 4 pits each 24 x 12 x 12 in. for Cor. to Sec. 21. 22. 27 and 28. Rolling sandy land; Soil 3rd rate; No timber.

North on true line
bet. Sec. 21 and 22
Var. 16° 15' E.

40.00 Set sandstone 12 x 10 x 5 in. 8 in. deep, marked 1/4 on W. side, in mound of earth, with 4 pits each 24 x 12 x 12 in. for 1/4 Sec. Cor.

Off Set for 4th Standard Parallel S
through T. 20 S. R 10 W.

Chs.
80.00 Set Sand Stone 14 x 8 x 5 in. 10 in deep, marked 3 notched on S. and E. edges, in mound of earth, with 4 pits each 24 x 12 x 12 in. for Cor. to Sec. 15, 16, 21 and 22.

Land level; Soil 2nd rate; No timber.

North on true line
bet. Secs. 15 and 16
Var. 16° 15' E.

40.00 Set Sand Stone 14 x 10 x 4 in. 10 in. deep, marked 1/4 on W. side, in mound of earth, with 4 pits each 24 x 12 x 12 in. for 1/4 Sec. Cor.

46.00 Greasewood and alkali flat bearing N.E. and S.W.

Off Set for 4th Standard Parallel S.
Through T. 20 S. R. 10 W.

Ch. BOOK A-168

80.00 Set Sand Stone 12×8×5 in.
4 in. deep, marked 4 notched
on S. and E on E. edges, in
mound of earth, with 4 pits
each 24×12×12 in. for cor.
to Sec's. 9. 10. 15 and 16.
Greasewood and Alkali flat;
Soil 3rd rate; No timber,
Small Lake to the West
about 3½ mile distant.

North on true line
bet. Sec's. 9 and 10
Var. 16° 15' E.

40.00 Set Cobble Stone 11×9×6 in.
8 in. deep, marked 1/4 on
W. side, in mound of earth,
with 4 pits each 24×12×12 in.
for 1/4 Sec cor.

14 Off Set for 4th Standard Parallel S. Through T. 20 S. R 10 W.

Chs.		Chs.
60.00	Dry Slough 30 links wide, bears N. W. and S. E. and enters river bottom.	22,50
74.00	Willows N. W. and S. E.	25,50
80.00	Set Sand Stone 14×10×8 in. 10 in. deep, marked 5 notches on S. and 3 on E. edges, in mound of earth, with 4 pits each 24×12×12 in. for Cor. to Secs. 3. 4. 9 and 10. South 3/4 alkali and Greasewood, North 1/4 bottom river sand, No timber.	40,00
		80,00

North on true line between Secs. 3 and 4
Var. 16° 15' E.

19.00 Left bank of Rogue River, which runs W. N. W.

Off Set for 4th Standard Parallel
through T. 20 S. R 10 W.

Chs.	
22,50	Right bank of Bevier River mile heads N.E. runs S.W.
25,50	Leave bottom, and enter valley land bearing N.E. and S.W.
40,00	Set a Conglomerate Stone 11 x 8 x 6 in. 8 in. deep, marked 1/4 on W. side in mound of earth with 4 pits each 2 x 12 x 12 in. for 1/4 Sec. Cor.
80,00	Set a Conglomerate Stone 13 x 8 x 7 in. 8 in. deep, marked 3 notches on E and W. edges, in mound of earth, with 4 pits each 2 x 12 x 12 in. for corner to Secs. 3, 4, 33 and 34, and Off Set corner for the 4th Stand. and Parallel South on the North boundary of T. 20 S. R. 10 W.

~~May 20th 1882~~

Off Set for 4th Standard Parallel & North boundary of T. 20 S. R 10 W.

Chs. South end bottom land; balance valley land; Soil 1st and 2nd rate No timber.

May 26. 1880

Thence;

West on a true line bet. Sec. 4 and 33 — 40,00

Var. 16° 15' E.

40.00 Set a Conglomerate Stone 13 x 8 x 5 in. 8 in. deep, marked 1/4 on N. side in mound of earth with 4 pits each 24 x 12 x 12 in. for 1/4 Sec. cor. — 66.00

80.00 Set a Conglomerate Stone 15 x 8 x 4 in, 10 in. deep, marked 4 notches on E. and 2 on W. edge in mound of earth with 4 pits each 24 x 12 x 12 in. for corner to Secs. 4. 5. 32 and 33, — 80.00

Off Set for North

Chs.

BOOK-A-168

Off Set for 4th Standard Parallel S.
North boundary of T. 20 S. R. 10 W.

Chs.

Lowland; Soil 2nd rate;
No timber.

BOOK-A-168

West on true line
bet. Secs. 5 and 32
Var. 16° 15' E.

40.00 Set a Conglomerate Stone 13x
8x6 in. 8 in. deep, marked 1/4
on N. side, in mound of earth
with 4 pits each 24x12x12 in.
for 1/4 Sec. Cor.

66.00 Granite Spring road, bears N.W.
and S.E.

80.00 Set a Conglomerate Stone 18x
8x4 in. 12 in. deep, marked
5 notches on E. and 1 on W. edge
in mound of earth with 4 pits
each 24x12x12 in. for Cor. to Secs.
5. 6. 31 and 32.

Off Set for 4th Standard Parallel S.
14 H North boundary of T. 20 S. R. 10 W.
Chs.
Low land; Soil 2nd rate, No timber.

West on true line
bet. Secs. 6 and 31
Var. 16° 15' E.

40.00 Set a Conglomerate Stone 14 x 10 x 4 in. 5 in. deep, marked 1/4 on N. side in mound of earth with 4 pits each 24 x 12 x 12 in. for 1/4 Sec. Cor.
Allowing 2 for convergency of Meridians

79.41 Set a Conglomerate Stone 18 x 8 x 6 in. 12 in. deep, marked 6 notches on N. S. E. and W. edges, in mound of earth, with 4 pits each 36 x 18 x 18 in. for Cor. to Tps. 19 and 20 S. Rs. 10 and 11 W.
Low land; Soil 2nd rate; No timber.

Off Set for 4th Standard Parallel S. 1145
North boundary T. 20 S. R. 10 W.

BOOK-A-168

General Description

This Twp. contains some alkali lands bordering on Sevier Lake, and some bottom lands along Sevier River adapted for cultivation. The last approach by land to Sevier River is from the Western end of this boundary in a Southerly direction about half mile distant; from which the banks of the river are impassable and covered with deep miry alkali for about 3 miles distance S. W. to its sink at Sevier Lake.

146 Off Set for 4th Standard Parallel
North boundary of T. 20 S. R. 11 E.

Chs. West on true line
bet. Secs. 1 and 36
Var. 16° 20' E.

39.00 Alkali flat along northern edge of Deoria Lake bears N.W. and S.E.

40,00 Set a Conglomerate Stone 13x10x4 in. 8 in. deep, marked 1/4 on N. side in mound of earth, with 4 pits each 24x12x12 in. for 1/4 Sec. Cor.

73.50 Dry Slough bears S. E. 1/2 E. head N. 10° W.

80.00 Set a Conglomerate Stone 18x14x5 in. 12 in. deep, marked 1 Notch on E. and 5 on W. edges in mound of earth, with 4 pits each 24x12x12 in. for corner to Secs. 1. 2 35 and 36.
Land alkali flats; Soil 3rd rate
No timber.

Off Set
North
Chs.
BOOK-A-
40,00
80,00

BOOK-A-168

Township 20 S. **R.** 11 W.

151 150 149 148 147 146

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Township

158

159 6

160 7

161 18

162 19

163 30

164 31

165

Offset for 4th Standard Parallel S. 14
North boundary T. 20 S. R. 11 W.

Ord.

West on true line
bet. Secs. 2 and 35
Var. 16° 20' E.

40,00 Set a Conglomerate Stone 14x10
x4 in. 10 in. deep, marked 1/4
on N. side in mound of earth
with 4 pits each 24x12x12 in.
for 1/4 Sec. Cor.

80,00 Set a Conglomerate Stone 15x10
x4 in. 10 in. deep, marked 2
notches on E. and 4 on W. edges
in mound of earth with 4 pits
each 24x12x12 in. for Cor. to
Secs. 2. 3. 34 and 35.
Low alkali flats; Soil 3rd
rate; No timber.

BOOK-A-168

Off Set for 4th Standard Parallel N
North boundary of T. 20 S. R. 11 W.

Chs. West on true line
bet. Secs. 3 and 34
Var. 16° 20' E.

40.00 Set Conglomerate Stone 16x10x3 in. deep, marked 1/4 on N. side in mound of earth, with 4 pits each 24x12x12 in. for 1/4 Section corner.

80,00 Set Conglomerate stone 14x8x4 in. 9 in. deep, marked 3 notches on E. and W. edges, in mound of earth, with 4 pits each 24x12x12 in. for corner to Secs. 3. 4. 33 and 34.
Alkali and Greasewood flats;
Soil 3rd rate; No timber.

Chs.

37,00

40,00

80,00

Off set for 4th Standard Parallel S.
North boundary T. 20 S. R 11 W.

Chs. West on true line
BOOK-A-168 bet. Secs. 4 and 33
Var. 16° 20' E.

37,00 Leave alkali flat, enter valley bearing N.E. and S.W.

40,00 Set Conglomerate Stone 11x9 x5 in. 7 in. deep, marked 1/4 on N. side, in mound of earth, with 4 pits each 24x12x12 in. for 1/4 Sec. cor.

80,00 Set Conglomerate Stone 16x10x5 10 in. deep, marked 4 notches on E. and 2 on W. edges, in mound of earth, with 4 pits each 24x12x12 in. for corner to Secs. 4. 5. 32 and 33.

East 1/2 alkali; West 1/2 valley, Soil 2nd and 3rd rate; No timber.

May 27th 1880.

Off Set for 4th Standard Parallel North
North boundary of T. 20 S. R. 11 W.

Chs. West on true line
bet. Sec. 5 and 32
Var. 16° 20' E.

40,00 Set Conglomerate stone 16x10x
10 in. 5 in. deep, marked 1/4
on N. side in mound of earth
with 4 pits each 24x12x12 in.
for 1/4 Sec. cor.

80,00 Set Conglomerate stone 13x8x6
in. 8 in. deep, marked 5 notches
on E. and 1 on W. edges, in
mound of earth, with 4 pits
each 24x12x12 in. for cor. to Secs.
5. 6. 31 and 32.
Level valley land; Soil 2nd
rate; No timber.

Off Set
North

Chs.

BOOK-A-1

8.50 G
15.15
40,00 (
(
(
(
79.41 (
(
(
(

Off Set for 4th Standard Parallel
North boundary T. 20 S. R 11 W.

Chs. West on true line
bet. Sec. 6 and 31
Var. 16° 20' E.

BOOK-A-168

8.50 Dry bed 10 links wide bra. S. heads N.

15.15 " " " " " " " " "

40.00 Set Conglomerate Stone 13×4×5 in. 8 in. deep, marked 1/4 on N. side, in mound of earth, with 4 pits each 24×12×12 in. for 1/4 Sec. cor. (allowing for convergency)

79.41 Set Conglomerate Stone 16×10×5 in. 10 in. deep, marked 6 notches on N. S. E. and W. edges, in mound of earth and stones, with 4 pits each 36×18×18 in. for cor. to Tps. 19 and 20 S. Rs. 11 and 12 W. Level valley land; soil 2nd rate. No timber.

55
154 Offset for 4th Standard Parallel
North boundary of T. 20 S. R. 11 E.

General Description

The land south of this boundary
is covered with alkali and
Sevier Lake on the North it
Consists of level valley, no
mineral, No timber.

Offset
North

Chs.

BOOK-

40,00

80,00

"Offset for 4th Standard Parallel S.
North boundary T. 20 S. R. 12 W.

Chs. West on true line
bet. Secs. 1 and 36.

BOOK-A-168

Var. 16° 20' E.

40,00 Set Conglomerate Stone 12x8x6 in. 8 in. deep, marked 1/4 on N. side in mound of earth with 4 pits each 24x12x12 in. for 1/4 Sec. Cor.

80,00 Set Limestone 15x10x4 in. 10 in. deep, marked 1 notch on E. and 5 on W. edges, in mound of earth, with 4 pits each 24x12x12 in. for Cor. to Secs. 1. 2. 35. and 36.

Rolling valley land; Soil 2nd rate; No timber.

BOOK-A-168

Township 20 S **R.** 12 W.

159	6	5	4	3	2	1
160	7	8	9	10	11	12
161	18	17	16	15	14	13
162	19	20	21	22	23	24
163	30	29	28	27	26	25
164	31	32	33	34	35	36

Offset for 4th Standard Parallel North boundary T. 20 S. R. 12 E.

Chs. West on true line bet. Sec. 2 and 35 Var. 16° 20' E.

13.00 Mark 30 links wide ~~drain~~ N.

40.00 Set Limestone 12×8×6 in. 8 in. deep marked 1/4 on N. side, in mound of earth, with 4 pits each 24×12×12 in. for 1/4 Sec. Cor.

80.00 Set Limestone 15×10×4 in. 10 in. deep, marked 2 notches on E. and 4 on N. edge, in mound of earth and with 4 pits each 24×12×12 in. for Cor. to Sec. 2. 3. 34 and 35.

Land sandy and brushy; Soil 2nd and 3rd rate; No timber.

Offset f... North...

Chs.

BOOK-A-

8.50

40.00

80.00

Offset for 4th Standard Parallel South
North boundary T. 20 S. R. 12 W.

Chs. West on true line
bet. Sects. 3 and 34
BOOK-A-168
Var. 16° 15' E.

8.50 Wash 20 links wide, ~~bearing~~ drain W. ~~and~~ S. E.

40.00 Set Limestone 14 × 8 × 5 in. 9 in. deep, marked 1/4 on N. side, in mound of earth, with 4 pits each 24 × 12 × 12 in. for 1/4 Section Corner.

80.00 Set Limestone 12 × 10 × 6 in. 8 in deep, marked 3 notches on E. and W. edges, in mound of earth, with 4 pits each 24 × 12 × 12 in. for Cor. to Sects. 3, 4, 33 and 34. Land Sandy and brushed; Soil 2nd and 3rd rate; No timber.

Offset for 4th Standard Parallel South
North boundary of T. 20 S. R. 12 E.

Chs.		Chs.
	West on true line between Secs. 4 and 33 Var. 16° 20' E.	
40,00	Set Limestone 13×9×5 in. 8 in deep, marked 1/4 on N. side in mound of earth, with 4 pits each 24×12×12 in. for 1/4 Sec. Cor.	8.00 32,50 40,00
65,00	Bench sloped N. and E.	
80,00	Set Limestone 14×8×5 in 10 in deep, marked 4 notches on E. and 2 on N. edges, in mound of earth, with 4 pits each 24×12×12 in. for Cor. to Sections 4. 5. 32 and 33.	80,00

Bench land; Soil 2nd rate;
No timber.

Off set for 4th Standard Parallel S.
North boundary T. 20 S. R. 12 W.

Ch. West on true line
between Secs. 5 and 32
Var. 16° 20' E.

BOOK-A-168

18.00 Gully 100 links wide, ~~bears N.W.~~ drains S.E.

32.50 " 50 " " " " "

40.00 Set Limestone 16x11x6 ins. 10 ins deep, marked 1/4 on N. side ins. mound of earth, with 4 pits each 24x12x12 ins. for 1/4 Sec. Cor.

80.00 Set Limestone 18x12x6 ins. 12 ins. deep, marked 5 notches on E. and 1 on W. edge ins mound of earth, with 4 pits each 24x12x12 ins. for Cor. to Secs. 5. 6. 31 and 32.

Land broken bench;
Soil 2nd rate; No timber;

Off Set for 4th Standard Parallel South
North boundary T. 20 S. R. 12 W.

Chs

West on true line
bet. Secs. 6 and 31.
Var. 16° 20' E.

40.00 Set Limestone 15×10×5 ins. 10 ins.
deep, marked 1/4 on N. side, in
mound of earth with 4 pits each
24×12×12 ins. for 1/4 Sec. cor.
Allowing for convergency of Meridians
79.41 Set Limestone 18×12×6 ins. 12 ins.
deep, marked 6 notches on N. &
E. and N. edges in mound of
earth, with 4 pits each 36×18
×18 ins. for cor. to Secs. 19 and
20 S. R. 12 and 13 W.

Bench land; Soil 2nd rate
No timber.

From this cor. Antelope Mountain
bears Westerly about 1/2 mile distant.

May 28th 1880.

Off Set
2nd Guia

Chs.

BOOK-A-168

4.50
11.00
40.00
80.00

Offset for 4th Standard Parallel South and 2nd Guide Meridian West, Westboundary T. 20 S. R 12 W.

BOOK-A-168

Chs.	
	From corner to Townships 19, and 20 S. R^rs 12 and 13 West; I run South on true line along W. boundary of Sec. 6. Var. 16° 20' E.
4.50	Wash ~~Limestone 4 Pt.~~ drain R. E.
11.00	Across Lane " " "
40.00	Set Limestone 16×12×6 in. 10 in. deep, marked 1/4 on W. side, in mound of earth with 4 pits each 24×12×12 in. for 1/4 Sec. Cor.
80.00	Set Limestone 14×12×5 in. 9 in. deep, marked 1 notch on N. and 5 on S. edges, in mound of earth, with 4 pits each 24×12×12 in. for corner to Secs. 6. 7. 1 and 12 Rolling valley land; Soil 2nd rate; No timber.

160 Offset for 4th Standard Parallel South to 2nd Guide Meridian West, West boundary T. 20 S. R. 12 W.

Chs.		Offset fo Guide Me Chs.
	South on a true line along W. boundary of Sec. 7. Var. 16° 20' E.	2 BOOK-A-
10.00	Wash 25 links wide, ~~drains N. & W.~~ ~~and~~ S.E.	
22.25	Wash 30 links wide, ~~drains N. & W.~~ ~~and~~ S.E. from this point a lone cedar 10 in. dia, bears E. about 2.00 chains distant	18.50
40.00	Set Limestone 14 x 8 x 4 in. 9 in. deep, marked 1/4 on N. side in mound of earth with 4 pits each 24 x 12 x 12 in. for 1/4 Sec. Cor.	31.00 40.00
57.50	Old road bears N.W. and S.E.	54.75
80.00	Set Conglomerate stone 18 x 6 x 4 in. 12 in. deep, marked 2 notches on N. and 4 on E. edges in mound of earth with 4 pits each 24 x 12 x 12 in. for corner to Secs 12. 13. 7 and 18.	80.00

Offset for 4th Standard Parallel South and 2nd Guide Meridian West, West boundary T. 20 S. R 12 W.

Chs. Rolling gravelly valley land; Soil 2nd rate; No timber.

BOOK-A-168

South on true line along W. boundary of Sec. 18.
Var. 16° 20' E.

18.50 Old road (same) bears S. and N.E.

31.00 " " " North and S.W.

40.00 Set a Limestone 12×10×6 in. 8 in. deep, marked 1/4 on W. side, in mound of earth, with 4 pits each 24×12×12 in. for 1/4 Sec. corner.

54.75 Gully bears N.E. and S.W. and same old road bears N.W. and S.E.

80.00 Set Conglomerate Stone 18×14×5 in. 12 in. deep marked 3 notched on N. and S. edges in mound of earth, with 4 pits each 24×12×12 in. for cor. to Secs. 18. 19. 13 and 24

475
162

Offset for 4th Standard Parallel South, and 2nd Guide Meridian West, N. boundary T. 20 S.

Offset
Meridia

Chs. Rolling valley land; soil 2nd rate; No timber.

Chs.

BOOK

✓

South on true line along W. boundary of Sec. 19.
Var. 16° 20' E.

11.00 Post of ridge E. and W. 40,00

14.00 Pos of Rane " "

25.00 Valley E. and W.

40.00 Set Limestone 14 x 5 x 4 in. 9 in. deep, marked 1/4 on W. side in mound of earth with 4 pits each 24 x 12 x 12 in. for 1/4 Sec. cor. 80,00

54.00 Wash 3 links wide, ~~bears N.W.~~ drains S.E.

66.00 " " " " " " "

80.00 Set Limestone 12 x 6 x 4 in. 8 in. deep, marked 4 notched on N. and 2 on S. edges, in mound of earth

Offset for 4th Stand. Par. South, and 2nd Guide Meridian W. West boundary T. 20 S. R 12 W.

Chs. Rolling valley land; Soil 2nd rate; No timber.

BOOK-A-168

South on true line along W. boundary of Sec. 30 Var. 16° 20' E.

40,00 Set Limestone 12×6×5 ins. 8 ins. deep, marked 1/4 on W. side, in mound of earth, with 4 pits each 24×12×12 ins. for 1/4 Sec. Cor.

80,00 Set Limestone 14×7×6 ins. 9 ins. deep, marked 5 notched on N. and 1 on S. edges, in mound of earth with 4 pits each 24×12×12 ins. for corner to Secs. 25. 30, 31 and 36.

Rolling valley land; Soil 2nd rate; No timber.

Offset for 4th Stand. Par. S. and 2nd Guide Meridian W. West boundary T. 20 S. R. 12 W.

Chs. South on true line along W. boundary of Sec. 31.
Var. 16° 20' E.

1.50 Bench Slope N.E. and S.W. and enter Coal valley.

40.00 Set Limestone 10 x 9 x 8 in. 6 in. deep, marked 1/4 on W. side in mound of earth, with 4 pits each 24 x 12 x 12 in. for 1/4 Section Corner.

40.50 Dry creek bed, drains E. and W.

73.90 Ravine ~~[illegible]~~, drains S.E.

80.00 Set a Limestone 18 x 11 x 10 in. 12 in. deep, marked 6 notches on N. S. E. and W. edges, in mound of stones and earth with 4 pits each 36 x 18 x 18 in. for standard corner to Townships 20 ~~[illegible]~~ S. R. 12 and 13 W. on 4th Stand. Par. South.
Rolling valley land; Soil 2nd rate; No timber.
May 29th 1880.

4th (illegible) South

Chs.

35.00

40.00

80.00

BOOK-A-168

4th Standard Parallel South
South boundary T. 20 S. R. 13 West

BOOK-A-168

Chs. | From Standard Corner to Townships 20 ~~and 21~~ S. R^s 12 and 13 West

I run:

West on true line along S. boundary of Sec. 36

Var 16° 20' E.

35,00 Foot of Antelope Mountain bear N. E. and S. W.

40.00 Set a Limestone 12 x 8 x 6 ins. 8 ins. deep, marked 1/4 on N. side in mound of earth with 3 pits each 24 x 12 x 12 ins. for 1/4 Sec. Cor.

80,00 Set Limestone 15 x 8 x 6 ins. 10 ins. deep, marked 1 notch on E, and 5 on N. edges in mound of earth with 3 pits each 24 x 12 x 12 ins for Standard Cor. to Secs. 35 and 36

East 1/2 level valley land; Soil 2nd rate on 45.00 chains

West 1/2 Mountainous; Soil 3rd rate

No timber.

BOOK-A-168

Township 20 S. **R.** 23 W.



Township



166

4th Standard Parallel South
Southbound ary T. 20 S. R. 13 W.

4th, S
Sout

From this corner I find it impracticable to continue any further the Standard during this season of the year, on account of high and rocky range of mountains, and scarcity of water.

Chs.

DOUBLE

40.00

80.00

4th Standard Parallel South
South boundary T. 20 S. R. 12 W.

Chs. Returning to the corner to Tps. 20 and 21 S. Rs. 12 and 13 West. I run:

BOOK A-168

East on true line along S. boundary of Sec. 31 Var 16° 20' E.

40.00 Set Limestone 12 x 9 x 5 in. 8 in. deep, marked 1/4 on N. side in mound of earth with 3 pits each 24 x 12 x 12 in. for 1/4 Sec. Cor.

80.00 Set Limestone 13 x 9 x 9 in. 8 in. deep - marked 1 notch on N. and 5 on E. edges in mound of earth with 3 pits each 24 x 12 x 12 in. for Standard Cor. to Secs 31 and 32

Level valley land; Soil 2nd rate; No timber.

F 168

4th Standard Parallel South
South boundary T. 20 S. R. 12 W.

BOOK-

Chs. East on true line along
S. boundary of Sec. 32.
Var 16° 20' E

BOOK-A-168

40.00 Near dry margin of Sevier
Lake, which bears N. and S. Set
a Limestone 12 x 10 x 6 in. 8 in.
deep, marked 1/4 on N. side in
mound of earth with 3 pits each
24 x 12 x 12 in. for 1/4 Sec. Cor.

Level valley land; Soil 2nd
rate; No timber.

May 31st 1880.

Joseph Gorlinski
deputy surveyor.

BOOK-A-168

169

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, Aug 14 *1880*

The foregoing field notes of the survey of the

4th Standard Parallel S.

~~*Township No*~~ *through* *Range No* 9. 10. 11. 12

& a part of 13 East

of the Salt Lake Meridian, Utah Territory,

Executed by Joseph Gerlinski

Under his *contract No* 93

of the 3 *day of* June *1879*

in the month of May *1880,*

having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.

Fred. Salsbury.

U. S. Surveyor General for Utah.

BOOK-A-168 Book 168

R: 1851

170

Filed 187 .

Examined by J. H. Cauke

Compared by F. C. Bailey

FIELD NOTES

OF

THE SURVEY OF THE

Guide Meridian Extension & Subdivisions

of Township No. 6 S., *Range No.* 25 E.,

of the Salt Lake Meridian in Utah Territory.

BY

A. D. Ferron

U. S. DEPUTY SURVEYOR,

Under his Contract No. 95, Ext. of Cont. 92

dated June 12th 1880.

Survey commenced 21st Nov. 1879.

Survey completed 29th " 1879.

BOOK-A-168

FOR CHAINMAN.

We Chas C. R. Bingham
and William N. Bradshaw,
do solemnly swear that we will faithfully execute the duties of chain carriers; that we will level the chain upon uneven ground, and plumb the tally pins, whether by sticking or dropping the same; that we will report the true distance to all notable objects, and the true length of all lines that we asssist in measuring, to the best of our skill and ability,

(Signed) Charles C. R. Bingham
William N. Bradshaw.

Subscribed and sworn to before me this 2nd day of Oct. 1879

A. D. Terrell
U. S. Dep. Surveyor

BCCR-A-168

172

FOR FLAGMAN.

I, Alfred N. Westover

do solemnly swear that I will well and truly perform the duties of flagman, according to instructions given me, and to the best of my skill and ability.

(Signed) Alfred N. Westover

Subscribed and sworn to before me this 2nd *day of* October 1879

A. D. Perron

Dep. Surveyor.

BOOK-A-168 — 173

FOR AXEMAN

I, Thomas Brigham Jr.
do solemnly swear that I will well and truly perform the duties of axeman, according to instructions given me, and to the best of my skill and ability.

Signed / Thomas Brigham Jr.

Subscribed and sworn to before me this 2nd day of October 1879

A. D. Perron
Dep Surveyor.

BOOK-A-168

Township 6 S **R.** 25 E



Ute Meridian
East Boundary Twp 6. S. R 25 6

BUyR-A-1
East

Survey Commenced Nov 21, 18

From the Standard Cor.

To Twp's 5 & 6 S. R. 25 & 26 E.

I measured W. 9 chs; (Being 7.00

the Calculated Convergence 3.00

of Meridians according to 58.15

Connection made) Set 2 d 63.70

x 1 at Stand. Par. by guide

Meridian Set. R. 20 x 21 E.

Where I set Sand Stone

14 x 10 x 8, q'n deep Marked

6 Notches on E- W- x S. Edges

and C.C. with Stone Mound for Closing

Cor. to Twp's 5 & 6 S. Rs 25 x 26

From which I run S on a

true line Set. Deg 176

Var. 16° 30' E.

5.10 Wash runs W Est.

23.70 (According to a forementioned 12.65

Connection) Set Sand stone 27.50

Salt L. Meridian

12 x 8 x 6 - 8 in deep, marked
1/4 on W. side with stone mound
for 1/4 Sec. Cor.

27.00 Wash drains S.W.

37.00 Deep Gulch drains S.W.

58.75 Deep gulch drains S.W.

63.70 Set Grey Sand Stone
14 x 12 x 6 - 9 in deep, Marked
1 notch on N and 5 on S.
edges with stone mound
for Cor. to Sec's. 1-6-7 & 12

Land Mountainous
Soil 3d rate.
Timber Scattering Cedar
Mountainous on 8 Chs

S. bet Sec's 7 & 12
Var. 16° 30' E.

12.65 Deep Hollow drains S.W.

27.50 " " " "

E. Bndry Twp 6 S. R 20 E

37.50 Deep hollow drains Sec—

40.00 Set Sand Stone, 12 x 9 x 5, 8 in. deep Marked 1/4 on W Side, with Stone Mound for 1/4 Sec. Cor.

55.00 Deep Gulch drains Sec.

70.20 " " " "

80.00 Set Sand Stone 12 x 8 x 7, 8 in. deep, Marked 2 Notches on N x 4 on S. Edges with Stone Mound for Cor. to Sec's 7-12-13 & 18.

Land Broken, Mountainous

Soil 2d rate

Timber, Scattering dwarf Cedars

Mountainous on 80.00 Ch's

S. Set Secs 13 & 18

Var. 16° 30' E.

5.00 Gulch drains Sec.

BOOK A

40.00 A

M

16

1/4

N

O

55.00 S

75.00 C

80.00 C

40.00 At foot of perpendicular wall Set Conglomerate 16 x 6 x 6 - 11 in deep marked 1/4 on N side, with stone Mound for 1/4 Sec. Cor. Thence on flat.

55.00 Cliff Creek 10 lks wide 1 ft deep runs W.

75.00 Enter hills

80.00 On top of ridge Cr's N.W. & S.E. Set Sand Stone 20 x 10 x 4 - 15 in. deep. Marked 3 notches on N and E. edges with Stone Mound for Cor. to Sec's 13 - 18 - 19 & 24

Land Mountainous & Level

Soil 3d & 1st rate

Timber Scattering Pine

on No. 40.00 Ch's

Mountainous on 5.00 Chs.

Boundary Twp 6 S R 25 E

S. bet Secs 19 & 24
Var 16° 30' E.

6.50 Enter flat.

40.00 Set Sandstone 14 x 10 x 5
Qin deep, marked 1/4 on
N. side with Stone Mound
for 1/4 Sec. Cor.

80.00 Set Sand Stone 14 x 12 x 8
Qin. deep. Marked 4 Notches
on N and 2 on E. Edges
with stone mound, for
Cor to Secs 19-24, 25 & 30.

Land Mostly Level
Soil 1st rate
No Timber
Mountainous on 6.50 Chs

S. bet. Secs 25 & 30 18.00
Var 16° 30' E. 38.00
32.00 Uintah & White River Trail 40.00

BOOK-A-168

S. L. Meridian

Bear N.W. & E.

40.00 Set Sand Stone 12 x 10 x 6.
8 in deep, marked 1/4 on W.
Side, with reg. mound & pit
for 1/4 Sec. Cor.

51.15 Dry bed of Creek Runs N.W.

80.00 Set Sand Stone, 12 x 10 x 7.
8 in deep marked 5 Notches
on N & 1 on S. Edges with
Reg. mound & pits for Cor. to
Sec's 25 - 30 - 31 & 36.
Land Level
Soil 1st rate
No Timber

S. Set Sec's 31 & 36.
Var 16° 30' E

18.00 Wash Drains N.W.
38.00 " " " "

Trail 40.00 Set Sand Stone 14 x 10 x 5

9 ins. deep. marked 1/4
N side with stone mou
for 1/4 Sec. Cor.
75.00 Enter ridge Brs NW & S
80.00 Set sand stone 30 x 12 x 7
20. ins deep marked 6 north
on N. S. E & W. edges with
stone mound - 6 ft high
6 feet base for Cor to
Twps 6 and 7 S R. 25 & 26 E 5.00
Land level on 75 chs. 10.00
Soil 1st rate 24.40
No Timber 40.00
Mountainous on 5 chs.
Nov. 21 1899

R L

Descriptions of this mile is omitted

115.00
60.15
80.00

EWR-A-168

South Boundary Twp 6. S. R 25 E.

Notes:—

The S.W. Cor. of this Twp
Not being established
therefore from the Cor.
to Twps 6 & 7 S. R 25 & 26
E. I run
W. on true line Set Sec's
1 & 36.
Var. 16° 30' E.

5.00 Ridge bts NW- & S.E

10.00 Enter Oak.

24.40 Wash drains N.W.

40.00 Set sand stone 12 x 8 x 6.
8 in. deep marked 1/4 on
N. side with stone mound
for 1/4 Sec. Cor.

45.00 Wash drains N.W.

60.15 " " " "

80.00 Set sand stone 14 x 6 x 6.
9 in deep marked 1/4 Notches
on E & 5 on W Edges.

A Boundary Twp 6 N R 26 E

With Stone Mound for
Cor. to Secs 1-2-35 & 36.
Land mostly level
Soil 1st rate
No Timber
Mountainous on 15.00 Chs

West on true line bet Secs 2 & 35
Var. 16° 30' E.

27.75 Enter Mountains

40.00 Set Sand Stone 13 x 9 x 6
9 in deep. Marked 1/4 on N
side with Stone Mound
for 1/4 Sec. Cor.

80.00 Set Sand Stone 11 x 8 x 8.
7 in. deep. Marked — 2 Notches
on E x 4 on W. Edges
with Stone Mound
for Cor to Secs 2-3-34 & 35
Land Mostly Mountainous

BLM-A-168

2d Meridian

Soil 2d & 1st rate

Timber, Scattering Dwarf Ce d
Mountainous on 52.25 Chs

Note:-

On account of unavailable
Mountains I Abandoned
further Survey H.

Nov 22nd 1879

West Boundary Twp 6. S. R 25 E.

Notes:

The S.W. Cor of this Twp
Not being established
(therefore) from the
Standard Cor. to Twps 84.00
5 S. R 24 & 25 E.
I measured N. 6.00 Chs
(Convergency of Meridians)
Where I set a Sand Stone
12 x 9 x 5 8 in deep, Marked
6 Notches on E. & N &
Edges and C. C. with
Stone Mound for Closing
Corner to Twps 6 S. R
24 & 25 E. from which
Run
S. 66 1 Secs 18 & 19
Var. 16° 30' E.
24.00 (According to Connection
Mentioned at beginning of

DUPLICATE

21.50

34.00

BOOK-A-168

Township 6 S. **R.** 24 E.



S. L. Meridian

East Boundary) Set Sand Stone 15 x 7 x 7 - 9 in deep Marked 1/4 on N side, with Stone mound for 1/4 Sec. Cor.

84.00 Set Sand Stone, 11 x 9 x 9 in deep Marked 1 Notch on N and 5 on S edges with Stone mound for Cor. to Sec's 1 - 6 - 7 x 12

Land) Mountainous
Soil 2d rate
No Timber.
Mountainous on 6 4.00 Chs

Set Sec's 7 x 12
Var 16° 30' E.

21.50 Wash drains E.

Enter Flat.

34.00 Uintah & White River trail Bro's E & W.

N. Boundary Tp's 6 & R 20 E

40.00	Set Sand Stone 15×10×[illegible]	
	10 in. deep, marked 1/4 on	
	N. side, with stone	80.00
	Mound for 1/4 Sec. Cor	
80.00	Set Sand Stone 20×12×10	
	15 in. deep, marked 2	
	Notches on N and 4 on S.	
	sides with stone mound	
	for Cor. to Sec's 7-12-13×18	
	Land Mostly Level	
	Soil 1st rate	
	No Timber	
	Mountainous on 21.50 Chs	
		27.00
	E. bet. Sec's 13×18	
	Var 16° 30' E.	32.00
13.95	Wash Drains W.	11.00
32.00	" " S.W.	
40.00	Set Sand Stone 16×7×5	
	11 in deep, marked 1/4 on	

W. side work stone Mound
for 1/4 Sec. Cor.
No.00 Set Sand Stone
10 x 9 x 6. 6 in deep, marked
3 on N & S. Edges with
Rig. Mound & pits for Cor.
No Sec's 13-18-19 & 24.
Land level.
Soil 1st rate
No Timber

S. bet Sec's 19 & 24
Var 16° 30' E.
2.00 Deep Gulch formed by Cliff
Creek (dry) drains W.
32.00 Enter Mountains
11.00 Set Sand Stone 10 x 9 x 7
6 in deep marked 1/4 on
W. side with Stone
Mound for 1/4 Sec. Cor.

1881 N. Boundary Twp 6 & R 25 E
6th Meridian

80.00 Set Land Stone 13 x 7 x 7
9 in deep. Marked 4 Notches
on N and 2 on S. Edges
with Reg. Mound & pits
for Cor. to Secs 19 - 24 - 25
& 30.

Land Mountainous & Covered
with Soil 3d & 1st rate
No Timber
Mountainous on 48.00 Chs

Note! —
On account of unavoidable
Mountains I abandoned
Survey South, from this
Point

Nov. 22nd 1879

Subs Surv. T. 5 S. R. 26 E

No Cor Sec 35 & 36.

Var 16° 30' E.

1450	Wash drains NW.	
40.00	Set Iron Stone 18 x 8 x 6	18.50
	12 in. deep marked 1/4	27.50
	on W. side with reg.	35.00
	Mound & pits for 1/4 Sec Cor.	115.50
44.90	Wash drains NW.	55.70
80.00	Set sand Stone 20 x 10 x	80.32
	5 — 15 in. deep marked	
	1 Notch on S. & E edges	
	Work stone mound for	
	Cor to Sec's 25 26 35 & 36	40.16
	Land level	
	Soil 2d rate	
	No Timber	
	Indications of Iron & Coal	80.32
	along line	

S. L. Meridian

, 190

E. on random line bet
Sec's 25 & 36.
Var 16° 30' E.

& 8 & 6	18.50	Enter ridge
1/4	27.50	Top of ridge & brs NW & SE.
g'	35.00	Enter flat.
Sec Cor.	115.50	Mash drains NW.
	55.70	" " " "
0 x 10 x	80.32	Int. E. boundary of Twp
ked		At Cor to Sec's 25 & 36.
dges		from which west on true line
for		bet Sec. 25 & 36.
& 36	40.16	Set sand stone 10 x 8 x 7
		6 in deep marked 1/4 on
		N side with reg. mound
		& pits for 1/4 Sec. Cor.
al	80.32	The Cor to Sec's 25-26-35
		& 36.

Land level & Mountainous
Soil 1st & 3d rate
Mountainous on 16.50 Chs

Sub's Twp 6 S R. 25 E

N. bet Secs. 25 & 26

Var 16° 30' E.

36.00 Leave flat

40.00 Set sand stone 36 x 12 x 6 33.80

2 ft. deep marked 1/4 on N. 40.00

side, with reg. mound & 80.15

pits for 1/4 Sec. Cor.

50.00 Ridge bears N.W. and S.E.

57.50 Enter flat.

68.00 Dry bed of Jones's Creek.

Drains N.W. 40.07

80.00 Set sand stone 12 x 8 x 6.

Ten deep marked 2 notches

on S. and 1 on E. edge

with reg. mound & pits 80.15

for Cor to Secs 23-24-25 & 26

Land level & Mountainous

Soil 1st & 2d rate

No Timber

Mountainous on 21.50 Chs

6th Meridian

E. on random line bet Secs
24 & 25
Var 16° 30' E.

33.80 Trail bears NW. and SE
40.00 Set Temp. 1/4 Sec. Cor.
80.15 Int. East bdry of Twp
40 lks N of Cor. to Secs
24 & 25. from which
N. 89° 51' W. on true
line bet Secs 24 & 25
40.07 Set Sand Stone 10 x 8 x 8
6 in deep, marked 1/4 on
N side with reg. mound
& pits for 1/4 Sec. Cor.
80.15 The Cor. to Secs 23-24-
25 & 26.

Land level
Soil 1st rate
No Timber

1st
1903 Subs Twp 6 S R 25 E.

N. (Bet Sec's 23 & 24
Var 16° 30' E.

22.00 Trail Cr's NW. & S.E.
110.00 Set Sand Stone, 8 x 8 x 8 11.00
6 in deep, marked 1/4 on W. 7.00
side, with Stone Mound 80.10
for 1/4 Sec. Cor.
65.00 Leave flat.
80.00 Set Sand Stone 11 x 12 x 3 11.05
9 in deep marked 3 notches
on S- and 1 on E edge
With Stone Mound for
Cor. to Sec's 13-14-23 & 24
Land mostly level
Soil 1st rate
No timber 80.10
Mountainous on 1500 ch

East on Random line (Bet Sec's
13 & 24

6th Principal Meridian

Var. 16° 30' E.

Along the ridge

28.00 Enter & Cor

11.00 Set Temp'y 1/4 sec Cor.

77.00 Enter ridge Brs NW & SE

80.10 Int. E. bndry of Twp

at Cor to Secs 13 & 24

from which West on

true line Set. Secs

13 & 24.

11.05 Set Charred Cedar post

4 x 4 in. 11 ft. long 2 ft. dug

Marked 1/4 S. on N side

with reg. mound & pits

for 1/4 Sec. Cor.

80.10 The Cor to Secs 13-14

23 & 24.

Land level & Mountainous

Soil 1st & 3rd rate

No Timber

Mountainous on 31.10 Ch's

E6
195

Sub's Twp 6 S R 2 E

N Bet. Sec's 13 & 14
Var 16° 30' E.

3.50 Enter Flat.

26.70 Cliff Creek 10 Lks wide, 15 in deep runs West. 3.00 21.00

11.00 Set Sand Stone, 10 x 10 x 7 in deep — Marked 1/4 on W side with Stone Mound for 1/4 Sec. Cor. 11.00 67.00 79.85

80.00 Set Sand Stone 15 x 8 x 6 in. deep marked 11 Notches on S and 1 on E edges with Stone Mound for Cor to Sec's 11-12-13 & 14 39.92

Land Level (mostly)
Soil 1st rate
No Timber
Mountainous on 3.50 Ch's 79.85

BOOK A-168 196

E. of L. Meridian

E. on random line bet sec
12 & 13
Var. 16° 30' E.

30.00	Enter Mountains
21.00	Wash Hollow Drains S.W.
40.00	Set Temp. 1/4 sec. Cor.
44.00	Hollow drains S.W.
67.00	" " "
79.85	Int. E. bndry of Tp. 20 N.

N. of Cor. to sec's 12 & 13
from which N. 89° 51' W. on true line bet sec's 12 & 13.

39.92 Set Sand Stone 12 x 8 x 7 8 in. deep marked 1/4 on N side with stone mound for 1/4 sec. Cor.

79.85 The Cor. to sec's 11-12-13 & 14
Land mostly mountainous
Soil 3d rate
No Timber
Mountainous on 79.85 Chs

Nov. 24 th 1879

Subs Twp 6 S R 25 E

BOOK A

N. Set Secs 11 x 12
Var 16° 30' E.

7.00 Enter Mountains
25.00 Wash drains W.
35.00 " " "
40.00 Set sand Stone 16 x 12 x 8
11 in deep, marked 1/4 on
W. side, with reg. mound
& pits for 1/4 Sec. Cor.
59.00 Ridge Brs E & W.
75.65 Wash in hollow drains N.
80.00 Set Sand Stone 12 x 10 x 5
8 in deep marked 5 notches
on S' and 1 on E. Edges
with Stone mound for Cor.
to Sec's 1-2-11 x 12
Land mostly mountainous
Soil 2d rate
No Timber
Mountainous on 73.00 Chs

8.20
10.00
21.00
40.00
80.00
40.00
80.00

E. on random line bet.
Sec's 1 & 12
Var 16° 30' E.

8.20 Steep Ascent
10.00 Gulch Leads N. ~~Land~~ Sand Wash Gulch
on Gulch from E.
21.00 Leave Gulch Ascend
40.00 Set 2 mps. 1/4 Sec. Cor.
80.00 Int. E. bndry of Twp 16 N.
of Cor to Sec's 1 & 12
from which N 89° 53 W
on true line bet Secs 1 & 12
40.00 Set Sand Stone 12 x 9 x 6
8 in. deep marked 1/4 on N
side with Stone Mound
for 1/4 Sec. Cor.
80.00 The Cor to Sec's 1-2-11 & 12.

Land Mountainous
Soil 2d rate
Timber - Scattering dwarf Cedar.
Mountainous on 80.00 Chs

Subs Twp 6 S R 2 W

N. on true line bet Secs 1 & 2
Var. 16° 30' E.

28.00 Ridge Trs E & W.

32.00 Snake River trail Trs N.E. & S.W. — Enter flat

40.00 Set sand Stone 12 x 8 x 7 8 in deep marked 1/4 on W side with reg. Mound & pits for 1/4 Sec. Cor.

42.00 Camp Creek Gulch drains W Leave flat

47.00 Hollow drains S.W.

64.50 Int. 1st Stand. Par. S. 9.10 Chs W. of Standard Cor to Secs 35 & 36. Where I set Sand Stone 15 x 10 x 6 — 10 in deep marked 1 Notch on E. S on W & 6 on S. Edges and C C for Closing Cors.

40.00

80.00

to Sec's 1 & 2.
Land Mountainous
Soil 2d rate
No Timber
Mountainous on 65.50 Ch's

March 6th Sec's 34 & 35
Var 16° 30' E.

H0.00 Set Sandstone 10 x 10 x 7
6 in deep marked 1/4 on W
side with stone mound
for 1/4 Sec. Cor.

80.00 Set Sand Stone 11 x 11 x 6
6 in deep marked 1 notch
on S. and 2 on E. Edges
with Stone mound for Co. to
Sec's 26 - 27 - 34 & 35.
Land Mountainous
Soil 2d rate
No Timber
Mountainous on 80.00 Ch's

Sabi Twp 6 S R 25 E.

E. on random line bet
Sec's 26 & 35
Var. 16° 30' E.

27.50 Enter float
34.00 Wash drains N.
40.00 Set Temp. 1/4 Sec. Cor.
80.10 Int. N & S line at Cor.
to Sec's 25-26-35 & 36
from which W on true
line bet Sec's 26 & 35
40.05 Set Sand Stone 12 x 8 x 6
8 in deep marked 1/4 on
N side with Stone mound
for 1/4 Sec. Cor.
80.10 The Cor to Sec's 26-27-34 & 35
Land level & Mountainous
Soil 1st & 3d rate
No Timber
Mountainous on 27.50 Ch's

E. B. & L. Meridian

N bet Sec's 26 & 27
Var 16° 30' E.

40.00 Set Charred Cedar post
4 x 4 ins. 4 ft. long. 2 ft.
deep, marked 1/4 S. on
W. side with reg. mound
& pits for 1/4 Sec. Cor.

80.00 Set Sand Stone 13 x 7 x 7
9 ins. deep marked 2
Notches on S. and E. edges
with stone mound for
Cor. to Sec's 22 23 26 & 27

Land broken Mountains
Soil 2d rate
No Timber
Mountainous on 80 Chs

E. on random line bet Sec's
23 & 26.
Var 16° 30' E

54
203

Subs Twp 6 S R 25 E

14.00 Enter flat.
25.00 Wash drains N.
32.00 Enter Ridge
40.00 Set Twp 1/4 Sec Cor
49.00 Enter flat.
63.00 Dry bed of Jones's Creek
drains N.W.
80.14 Int. N & S. line 22 Ch. S of
Cor. to Secs 23-24-25 & 26
from which S. 89° 51' W.
on true line bet Secs 23 & 26.
40.00 Set Charred Cedar Post.
4 x 4 x 18 in - 4 ft long - 2 ft deep
Marked 1/4 S on N side
with reg. mound & pits
for 1/4 Sec. Cor.
80.14 The Cor to Secs 22 23-26 & 27
Land level & Mountainous
Soil 1st & 2d rate.
No Timber.
Mountainous ow 31.00 Chs

J. C. Mulville
VERNAL, UTAH

THE STATE OF UTAH
STATE ROAD COMMISSION
SALT LAKE CITY

Nov. 21st. 1932

COMMISSION
HENRY H. BLOOD, CHAIRMAN
W. J. PARKER, MEMBER
PRESTON G. PETERSON, MEMBER
AGNES MCNEIL, SECRETARY
H. S. KERR, CHIEF ENGINEER

Sketch Showing Description of Witness Corners for the S. 1/4 Corner Stone Of Section 23 T. 6 S. R. 25 E. Witness Corners are 1"x30" Pipe.

1/4 Corner Stone is under a 25ft fill 6.5 ft. North of Centerline at Station 248+50 F.A.P. 96-D Utah U.S. 40



6th Meridian

N. Set Sec's 22 & 23
Var 16° 30' E

22.00 Enter flat.

40.00 Set Sand Stone 9 x 7 x 5
6 in deep, marked 1/4 on N
side with reg. mound & pit
for 1/4 sec. Cor.

69.50 Trail bears NW & E

80.00 Set Sand Stone 10 x 10 x 7
6 in deep - marked 3 notches
on S. and 2 on E. Edge
with reg. mound & pit - for
Cor to secs 14-15-22 & 23

Land mostly level
Soil 2d rate
No Timber
Mountainous on 2200 Ch

E. on random line bet Sec's 14 & 23
Var 16° - 30' E

15.00 Walk drains NW

Subs Twp 6 S. R. 25 E.

37.50	Enter ridge	
40.00	Set Temp. 1/4 Sec Cor.	40.00
80.16	Int N & S. line at Cor to Sec's 13-14-23 & 24 from which N. on true line Set Sec's 14 & 23	80.00
40.08	Set Sand Stone 12 x 8 x 7 8 in deep marked 1/4 on N side with Stone Mound for 1/4 Sec. Cor.	
80.16	The Cor. to Sec's 14-15-22 & 23 Land Mountainous & level Soil 3d & 1st rate No Timber Mountainous on 42.66 Chs	

Nov. 25. 1879

	N. Set Sec's 14 & 15	40.00
	Var. 16° 30' E.	80.12
5.40	Cuff Creek 10 Lks wide	

BOOK-A-168

5 E

G. L. Meridian

12 in deep runs N.

40.00 Set Sand Stone 14 x 10 x 6
9 in deep Marked 1/4 on
N. side with Stone
Mound for 1/4 Sec. Cor.

80.00 Set. Sand Stone 12 x 7 x 7
8 in deep (Illegible) marked 1 on S.
and 2 on E Edge & with
Stone Mound for Cor
to Secs 10-11-14 & 15

Land level
Soil 1st rate
No timber

E, on random line bet Secs
11 and 14
Var 16° 30' E

40.00 Set Temp. 1/4 Sec. Cor.
80.12 Intd. N & S line 35 lks S of
Cor to Secs 11-12-13 & 14

38
20

Subs Twp 6 S R. 20 E.

B00

	From which S. 89° W 51.00	
	on true line bet.	62.00
	Secs 11 & 14	73.00
40.06	Set Sand stone 16 x 8 x 4	80.00
	11 in deep marked 1/4 on	
	N side with stone	
	Mound for 1/4 Sec Cor	
80.12	The Cor to Secs 10-11-14	
	& 15	
	Land Level.	
	Soil 1st rate	
	No Timber.	
	N. bet Secs 10 & 11	
	Vas 160 30' E	
39.00	Camp Creek (dry) runs SW.	
40.00	Set Sand Stone, 11 x 10 x 5	16.00
	6 in deep marked 1/4 on W	23.00
	side with stone Mound	38.00
	for 1/4 Sec. Cor	40.00

51.00 Leave flat
62.00 Ridge bts E. & W
73.00 Gulch wash drains N.W.
80.00 Set Sand Stone 20 x 7 x 7
15 in deep marked S
Notches on S. 20 on E.
edges with Stone Mound
for Cor to Sec's 2-3-10 & 11
Land Mostly level
Soil 1st rate
No Timber
Mountainous on 29.00 Chs

E. on random line bet
Sec's 2 & 11
Var 16° 30' E
160.00 Enter flat.
230.00 Wash drains S.E.
380.00 " " "
400.00 Set Temp. 1/4 Sec Cor

209 Subs Twp 6 S. R. 20 E.

43.75 Wash drains S
59.00 Same Wash drains NW,
66.00 Wash drains SW
74.00 Enter Mountains
79.94 Int. N & S. line at Cor to Sec. 1-2-11 & 12. from Which West on true line Bet sec-2 & 11
39.97 Set. Sand stone 10 x 10 x 8 - 6 in deep Marked 1/4 on N side with stone Mound for 1/4 Sec. Cor.
79.94 The Cor. to Sec's 2-3-10 & 11
Land Mostly level
Soil 1st rate
No Timber
Mountainous on 27.94 Chs

N. Bet Sec's 2 & 3
Var 16° 30' E

book D. 2

120 0
21.00
31.00
40.00
64.20

S. L. Meridian

12.00	Ridge bears NE & SW
21.00	Trail " " " "
31.00	Gulch wash drains S.W.
40.00	Set Sandstone 11 x 9 x 7 6 in deep. Marked 1/4 on N. side, with stones Mound for 1/4 Sec. Cor.
64.20	Int. 1st Stan'd. Par. S. 9.18 Chs W. of Stan'd Cor. to Secs 34 & 35 - Where I set a Sandstone 12 x 7 x 7, 8 in deep Marked 2 Notches on E. & on W. & 6 on S. edges and C. C. for Closing Corner to Sec. 2 & 3

Land Mountainous
Soil 3d rate
Timber Scattering dwarf Cedar
Mountainous on 64.20 Chs

Sub's Twp. 6 S R. 25 E.

Notes:

The Southwest Cor. of this Twp not being Surveyed Distances from the Cor. to Sec's 22. 23-26 & 27 Run West on True line Sec's 22 & 27

Var. 16° 30' E.

22.00 Set Sulak drain N. E.

40.00 Set Sand stone 10 x 10 + 8 - 6 in deep. marked 1/4 on N side, with Stone Mound for 1/4 Sec. Cor.

80.00 Set Sand Stone 11 x 9 x 9 6 in deep. Marked 2 Notches on S. & 3 on E Edges with Stone Mound for Cor to Sec's

27.00

40.00

BOOK-A-168

21-22-27 & 28

Land Broken Mountainous
Soil 3rd rate
Timber Scattering Cedar
Mountainous on 80.00 chs

West on true line bet Secs 21 & 28
Var 16° 30' E.

27.00 Gulch drains NE
40.00 Set Chiseled X Cedar
Post 4 x 4 in - 4 ft long
2 ft. deep, Marked 1/4 S
on W side, with brs.
Mound & pits for 1/4 Sec
Cor.

80.00 Set Sand Stone 14 x 8 x
6 in. deep Marked 1/4
Notch on S & E on
Edges, with Stone Mound
for Cor. to Secs 20-21-28 & 29

~~##~~
213 Subs Twp 6 S. R. 25 E.

Land broken Mountains
Soil 2d rate
No Timber
Mountainous on 80 Chs

W. on true line bet Secs 28 & 29
Var 16° 30' E

26.75 Sulch drains N.W.
40.00 Set sandstone 16 x 9 x 5 11 in. deep, marked 1/4 on N. side with stone Mound for 1/4 Sec Cor.
80.00 Set Sand Stone 10 x 8 x 6 in. deep, marked 2 Notches on S. & S on E edges with stone Mound for Cor to Secs 19-20-29 & 30.

Land Heavy Mountains
Soil 3d rate

S. L. Meridian

Timber Scattering Cedar Mountains on 8.00 Chs

N. on random line bet. Sec's 19 & 30.
Var 16° 30' E.

40.00 Set temp. 1/4 Sec. Cor.
48.50 Gulch drains N.
79.20 Int. W. boundary of Twp 42 Rks N. of Cor. to Sec's 19 & 30. From which N. 89 1/2 E. On true line bet Sec's 19 & 30.
3.20 Set sandstone 14 x 7 x 7 in deep marked 1/4 on N side, with stone Mound for 1/4 Sec Cor.
3.20 The Cor. to Sec's 19-20-29 & 30 Land high Mountains

Dubois Twp 6 S R. 20 E

Soil 2d rate
No Timber
Mountainous 7 7.20 Chs
Nov. 26. 1880
N. Bet. Sec's 21 & 22
Var 16° 30' E.

40.00 Set sand Stone 13 x 8 x 7
9 in. deep, Marked 1/4
on N. side with stone
Mound for 1/4 Sec. Cor.
43.00 Gulch drains N.E.
75.50 Enter flat.
79.00 Dry bed of Cliff Creek
runs W.
80.00 Set sand Stone 16 x 7 x 5
11 in. deep, marked
3 notches on S. and E.
edges with stone
Mound for Cor. to Sec's
15-16-21 & 22.

BOOK

S. L. Meridian

Land Mostly Mountains
Soil 3rd rate
No Timber
Mountainous on 75.50 Chs

E. on random line Set Secs
15 & 22
Var 16° 30' E.

29.00 Dry bed of Cliff Creek
Runs S. E. 6.00 Chs
Thence W.

40.00 Set temp. 1/4 Sec. Cor.
62.50 Trail Crs NW & SE.
80.20 Int N & S line 21 Chs
N of Cor. to Secs 14-15-
22 & 23 from which
N. 89° 50' W. on true
line Set Secs 15 & 22
40.10 Set Sand Stone 14"x8"
6 - 9 in deep. Marked

217 Subs Twp 6. S. R. 20 E. S. 2

1/4 on N side, W & L $0.00
Stone mound for 1/4 Sec
Cor.

$0.20 The Cor. to Secs 15-16-21
& 22
Land Level
Soil 1st rate
Timber — a few Cottonwood
on Creek —

N. bet Secs 15 & 16.
Var. 16° 30' E.

3.10 Camp Creek (dry) runs S.W.
24.50 Wash drains S.W. $0.00
37.50 Trail Ocean NW & E. $0.50
110.00 Set Sand Stone 12 x 8 $0.00
x 7 — 8 in deep Marked $0.50
1/4 on W side W & L
Stone mound for
1/4 Sec. Cor

80.00 Set Sand stone 16 x 8 x 6 - 11 in deep, Marked H Notches on S & E Edges, with Mound & pits for Cor. to Secs. - 9 - 10 - 15 & 16.

Land Level.

Dob 1st rate

Number.

Cor. on random line bet Secs. 10 & 15 -

Var 16° 30' E.

8.00 Wash drains S.

38.50 Temp. rock Md. (Cor.) S.W.

40.00 Set Temp. 1/4 Sec Cor

20.50 Int. N & S line at Cor to Secs 10 - 11 - 14 & 15 -

from which W. on true line. Set Secs 10 & 15

50
219

Subs Twp 2 S. R 25 E

40.25 Deposited a small Sandstone marked with Cross (+) in Reg. mound of earth & pits for 1/4 Sec Cor

80.50 The Cor to Sec's 9-10-15-16

Land level

Soil 1st rate

No timber

N. bet Sec's 9 & 10

Var. 16° - 30' E.

40.00 Set sand stone 12 x 12 x 16 Sin. deep marked 1/4 on W. side with reg. Mound of Earth & pits for 1/4 Sec. Cor.

47.00 Wash drains S.E.

55.00 Trail bears N.E. & S.W.

Enter Mountains

S. L. Meridian

Ft 220

20.00 Set Sand Stone 20 x 7 x 4
15 in. deep. Marked
5 Notches on S. & 3 on E
Edges With Reg mound
of Earth & pits for Cor to
Sec's 3-4-9 & 10.
Land Mostly level
Soil 1st rate
No Timber
Mountainous on 2 or 3 Chs

East on land on line 6 Chs.
Sec's 3 & 10.
Var 16° 30' E

10.00 Wash in Gulch Drains S. E.
3.00 Trail bears N.E. & S.W.
16.50 Hollow drains S.
2.00 Ridge bears N & S.
8.00 Gulch Wash drains S.
20.00 Set Temp. 1/4 Sec. Cor

Ft.
22

Subs Twp 6 S R 25 E

BOOK

47.00 Wash drains S.W.

52.00 Ridge bears N.E. & S.W.

56.00 Enter flat. 3.50

60.00 Wash drains N.W. 40.00

Leave flat.

80.00 Int N. & S. line 43 lks
N. of Cor. to secs 2-3-10 & 11
from which N 89° 45' W 63.90
On true line bet secs
3 & 10.

40.00 Set Sandstone 10 x 8 x 7,
6 in deep, marked 1/4
on N side, with
stone mounds for 1/4
Sec. Cor.

80.00 The Cor. to secs 3, 4, 9, & 10
Land Mostly Mountains
Soil 2d rate
No Timber
Mountainous on 60.00 Chs

4 L Meridian

N. on true line bet Secs 3 & 4
Var 16° 30' E.

3.50 Gulch wash drains S.E.

4.00 Set sand stone. 10 x 8 x 7
6 in. deep, marked 1/4
on N. side with stone
Mound for 1/4 Sec. Cor.

63.90 Int. 1st Stand Par. S. 9.12
Chs W. of Stand Cor to
Secs. 33 & 34 where I
set a sand stone 12 x 8 x 7
6 in deep marked 3 notches
on E & W. & 6 on S. Edges
and C. C. with stone
Mound for Closing Cor.
to Secs 3 & 4

Land Mountainous
Soil 3rd rate
No Timber
Mountainous on 63.90 Chs

Subs Twp 6 S R. 25 E

BOOK-A

N. bet Secs 20 & 21
Var 16° 30' E.

40.00	Set Sand Stone 10×10×6 in. deep marked 1/4 on W. side with reg. mound & pit, for 1/4 Sec. Cor.	12.75
16.00	Gulch drains N.W.	5.50
30.00	Enter flat	41.00
15.00	Dry bed of Cliff Creek drains S.W.	55.00
80.00	Set Sand Stone 12×10×6 in. deep marked 3 Notches on S & 3 on E edges with reg. mound & pits for Cor to Secs 16-17-20 & 21	65.50
		14.40
		0.60
		40.30
	Land mostly Mountainous	
	Soil 3rd rate	
	No Timber	
	Mountainous on 13.00 Chs	0.60

J. L. Mendenhall

E. on random line bet Sec's 16 & 21
Var 16° 30' E.
12.15 Dry bed of Cliff Creek
Drains S.W.
5.50 Same drains N.W.
24.50 Wash drain S.
40.00 Set Temp 1/4 Sec Cor
55.00 Dry bed of Cliff Creek
Drains S.W.
65.50 Same drains N.W.
94.40 Wash drains S.W.
0.60 Int. N & S. line at Cor.
to Sec's 15-16-21 & 22
From which W. on true
line bet Sec's 16 & 21
10.30 Set Sand Stone 10×9×6.
6 in deep marked 1/4
on N. side w/ stone
Mound for 1/4 Sec. Cor.
20.60 The Cor to Sec's 16-17-20 & 21

T. 22 S.

Dak's Fork 6s R 25 E

Land level
Soil 1st rate
No Timber Nov 27. 80

N. 6 et Sec. 16 & 17
Var. 16° 30' E

+10.00 Set Sand Stone 12 x 9 x 6,
8 in. deep, Marked 1/4 on
W. side, with stone mound
for 1/4 Sec. Cor.

41.00 Wash drains S.W.
Leave flat.

8.00 Set lime stone 14 x 8 x 6
9in deep. marked 4 notch
on S. & E. edges with
stone mound for cor to
Sec's 8-9-16 & 17

Land Mostly level
Soil 2d rate
No Timber
Mountainous on 39.00 Chs

11.00
1.50
37.00
10.00
39.00 —
9.90
39.95 —
9.90

S. L. Meridian

On random line bet Sec's 9 & 16.

Var 16° 30' E.

11.00 Meadow drains S.

1.50 Trail bears N.W. & S.E.

37.00 Sulah Wash drains S.

40.00 Set temp. 1/4 Sec. Cor.

39.00 — Enter flat —

19.90 Int North & South line 90 lks S of Cor. to Secs 9-10-15 & 16. From which S. 89° 00' West on true line bet Sec's 9 & 16.

39.95 Set Sand Stone 14 x 10 x 5 in deep marked 1/4 on N. side with Brg. Mound & pits for 1/4 Sec Cor.

19.90 The Cor to Secs 8-9-16 & 17 Land mostly Mountains

FB
22

Subs Dwp 6. s R20 E

Soil 2d rate
No Timber
Mountainous on 6 9.00 chs

No. 6 et Sec's 8 v 9
Var 16° 30' E

20.00	Uintah & White River trail bears NW & SE.	1400
40.00	Set sand stone 10x9x6	4000
40.00	6 in deep marked 1/4 on W. side with stone Mound for 1/4 Sec. Cor.	0.12
62.00	Ridge bears NW & SE.	
80.00	Set sandstone 20x12x6 - 15 in. deep Marked notches on S & E on E. Edges with reg. Mound & pits for Cor. to Sec's 4-5-8 & 9	0.06
		0.12

Land Mountains

BOOK-A-168

S. L. Meridian

Soil 2d rate
No Timber
Mountainous on 8000 Chs

E on random line bet Sec 4 & 9
Var 16° 30' E

1400 Gulch Wash drains E
4000 Set temp. 1/4 Sec. Cor.
50.00 Gulch wash drains E
20.12 Int N & S line 22 Lks
N. of Cor. to Secs 3-4-9-10
from which N. 89° 51'
W. on true line bet Secs
4 & 9
40.06 Set Sand Stone 12 x 10 x 6.
8 in deep, marked 1/4
on N. side with reg. Mound
& Pits for 1/4 Sec. Cor.
20.12 The Cor. to Secs 4-5-8-9

Land Mountains

Subs Twp 6 S. R 25 E.

Soil 2d rate
No Timber
Mountainous on 8 0. 12 Chs

N. on true line Cor Secs 4 & 5
For 160 30' E

40.00 Set Sand Stone 18 x 8 x 8
5 in deep, marked 1/4 on it 40.00
N side, with Stone
Mound for 1/4 Sec Cor'
53.00 Gulch was h drains S. E.
63.82 Instr 1st Stand. Par S. 41.00
9.14 Chs N of Stand Cor. 92.00
to Secs 32 & 33 - where 68.00
I Set Sand Stone 10 x 6 x 4 11.00
6 in deep marked ⊕ 90.00
Notches on S. & on E. &
2 on N. edges, with
Stone mound for Closing
Cor to Secs 4 & 5.

BOOK-A-168

Ut. 230

S. L. Meridian

Land Mountains
Soil 2d rate
No Timber
Mountainous on 63.82 Chs

N. Cor Sec's 19 & 20.
Var - 16° 30' E.

40.00 Set Sand Stone 10 x 8 x 8
6 in deep, Marked 1/4
on N. Side - with Stone
Mound for 1/4 Sec Cor

41.00 Gulch drains N.W.
E.
Enter Flat.

68.00 Dry bed of Cliff Creek drains W

71.00 Wash drains S.W.

70.00 Set Sand Stone 16 x 12 x 12
11 in. deep, Marked 3 Notches
on S x S on E. Edges
with reg. Mound of Earth
& pit for Cor. to Secs. 17-18-19 & 20

Subs Twp 6 S. R. 20 E

Land) Mostly Mountains
Soil 2d rate
No Timber
Mountainous on 62.00 Ch's

E. on random line bet Sec's 1 & 20
Var 16° 30' E.

7.00	Gulch drains S.W.	39.00
40.00	Set temp 1/4 Sec. Cor.	40.00
58.50	Wash drains S.W.	77.30
68.00	" " " "	
80.40	Sm't N & S line at Cor.	
	to Sec's 16 & 17. 20 & 21 from	
	which W on true line	37.30
	bet. Sec's 17 & 20	
40.20	Set sand stone 10 x 8 x 4	
	6 in. deep marked 1/4 on	
	N. side with reg. Mound	77.30
	& bit for 1/4 Sec Cor.	
80.40	The Cor to Sec's 17-18-19 & 20	

BOOK-A-168

Salt L. Meridian

Land level

Soil 1st rate

No Timber.

W. on random line bet. Sec's 18 & 19.

Var 16° 30' E.

39.00 Mark Drains S.W.

40.00 Set 1 emp. 1/4 Sec. Cor.

77.30 Int. W. boundary of Twp. at Cor. to Sec's 18 & 19 from which E. on a true line bet Sec 18 & 19.

37.30 Set Sand Stone 14 x 9 x 7 in deep, Marked 1/4 on N. side with Reg. Mound & pits for 1/4 Sec. Cor.

77.30 The Cor. to Secs 17-18-19 & 20.

Land level

Soil 1st rate

No Timber

Subs Twp 6 S R 25 E

North bet Secs 17 & 18
Var 16° 30' E

40.00 Set Sand Stone 11 x 8 x 6
6 in deep, mkd. 1/4 on E
side, with reg. mound &
pits for 1/4 Sec. Cor.

50.25 Deep wash drains N.W.

65.00 Small drain N.W.

77.00 Bones " " S.E.

80.00 Set Sand Stone 18 x 14 x 8
12 ins deep Marked at notch
on S & E edges
with reg. mound & pits
for Cor. to Secs 7-8-17 & 18
Land Level
Soil 1st rate
No Timber

E. on random line bet Secs 8 & 17
Var 16° 30' E

18.00
10.00
51.00
76.50
80.10
40.05
40.10
0.50

L. L. Meredeen

18.00 Wash drains A.W.

+8.00 Pet. temp. 1/4 Sec. Cor

51.00 Enter mountains

76.50 Wash in hollow drains S.

80.10 Int. N. & W. line 19 lks E of
Cor. to Sec's 8 & 9. 16 & 17
from which S. 89° 52' W
outline Pet. Secs 8 & 17

40.05 Set sand stone 14 x 8 x 5, q'ds
Mark'd 1/4 on N. side with
reg. Mound & pit. for 1/4 Sec. Cor

90.10 The Cor. to Sec's 7-8-17 & 18
Land Mostly level
Soil 1st rate
No Timber
Mountainous on 29.10 Ch's

N. on random line bet Sec's 17 & 18
Var 16° 30' E

0.50 Wash drains E.

64
235 Sub. Twp 6 S R 25 E

35.50 Wash draws S.

40.00 Set Temp. 1/4 Sec. Cor.

45.00 Wash draws SW

77.50 Int. W. Bndry of Twp at Cor. to Secs 7 & 18 from which E. on true line Set. Secs 7 & 18

80.00

37.50 Set Sandstone 16 x 9 x 7 in deep marked 1/4 on W. side with stone mound for 1/4 Sec Cor.

77.50 The Cor to Sec's 7-8-17 & 18

Land level

Soil 1st rate

No Timber Nov 18. 79

N. Set Sec's 7 & 8

Var 16° 30' E

38.50 White River & Uintah trail bears E and W

14.00

S. L. Meridian

40.00 Set Sand Stone 12 x 10 x 6 Dis dup, marked 1/4 on Cor. Side with reg. mound and pits for 1/4 Sec. Cor.

75.00 Wash drains S.E.

80.00 Set Sand Stone 14 x 12 x 4 9 in dup, marked 5 notches on S & E. edges, with reg. mound and pits for Cor 4 Sec's 5. 6. 7 & 8.

Land level;
Soil Shale;
No Timber.

E. on random line bet. Sec's 5 & 8
Var 16 30' E.

14.00 Wash drains S.E.

Subs. Twp. 6 S. R 25 E.

20.00 Enter ridge bears N & S.
25.50 Top of Ridge
34.00 Enter Flat.
40.00 Set temp. 1/4 sec cor.
56.25 Wash drains S.
70.00 Enter Mountains.
80.00 Ent. N & S. line at cor. to sec! 4. 5. 8 & 9 from which West on true line bet. sec! 5 and 8.
40.00 Set sand 10 x 8 x 7. 6 in. deep, marked 1/4 on N. Side, with stone mound for 1/4 sec. cor,
80.00 Pit cor 4 sec! 5. 6. 7 & 8
Land leveling mountainous
Soil 1st & 2nd rate.
No Timber.
Mountainous on 24.00 chs.

2.10
36.00
40.00
66.50
77.10
37.10
77.10

On random line bet.
Sec.ˢ 6 and 7,
Var 16° 30' E.

2.10 Wash drains S.E. enters ridge
36.00 Enter flat.
40.00 Set temp. 1/4 Sec. Cor,
86.50 Wash drains S.W. enters mountains
47.10 S.W. boundary of Twp, 26
Lks, N. of cor. to Secˢ 6 & 7:
from which N. 89° 49' E.
on true line bet. Secˢ 6 & 7.
37.10 Set Sand Stone 12×10×8, 8in.
deep, marked 1/4 on N.
side, with pg. mound &
pits for 1/4 Sec Cor.
47.10 The cor to Secˢ 5. 6. 7 and 8
Land level & mountainous;
Soil 2nd & 3rd rate;
No Timber
Mountains on 54.50 chs.

237

Sibis Twp. 6 S., R 25 E.

North on true line bet. Secs P. 576
Va 16. 30' E.

3.00 Enter Mountains
40.00 Set Sand Stone 10×9×6, 6 in.
dup, marked 1/4 on W. Side
with pg. mounds pits for
1/4 Sec. Cor.
53.00 Gulch drains E.
63.80 Ent. 1st Stand. Par. S. 9.40 ch.
W. of Stand. Cor. to Sec. 31 & 32
When Set a Sand Stone
12×10×5, 8 in dup. marked 5
Notches on E., 1 on W. & 6 on S. edg
and C.C. for closing Cor to Sec. 576.
Land mostly mountains;
Soil Indurate;
No Timber
Mountainous on 60.80 chs
Nov 29. 80

BOOK-A-168

L. Meridian

#138

General Description

The Land embraced in this Township, consists of the Valley along Cliff Creek, a Mountain Stream which at ordinary seasons furnishes sufficient water for irrigation. There are numerous other small Streams running into this creek, which, on account of the extraordinary drouth prevailing at time of survey, contained water only at their extreme fountain heads.

The Soil is of first rate quality. The S.E. portion of this Township, contains

BOOK

~~# 2~~ ~~#~~ 239

Sec

Good indications of
Coal; the S.W. par
falls in unavailable
mountains, and is not
surveyed.

R. D. Perron
Deputy Surveyor.

T. 1
No.

5 "
6 "

BOOK-A-168

42
240

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, August 11th *1880*

The foregoing field notes of the survey of the

Guide meridian, fractional S & W, boundaries & Subdivisions,

Township No 6 S *Range No* 25 E,

of the Salt Lake Meridian, Utah Territory,

Executed by A. D. Ferrin

Under his *contract No* 95 - Ext. of Cont. 92

of the 12 *day of* June *1880,*

in the month of Nov. *1879*

having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.

Jno. Salomon.

U. S. Surveyor General for Utah.

BOOK-A-168 (Book K 168)
R: 1881.

241

Filed 1880.

Examined by John H. Campe C.D.

Compared by F. C. Bailey

FIELD NOTES

OF

THE SURVEY OF THE

Subdivision lines

of Township No. 6 South, Range No. 24 East

of the Salt Lake Meridian in Utah Territory.

BY

O. G. Ferron.

U. S. DEPUTY SURVEYOR,

Under his Contract No. 96. Ext: of Cont: 92.

dated June 12th, 1880.

Survey commenced dec 2d 1880.

Survey completed " 7th 1880.

Subs Tp 6 S R 24

Survey Commenced: Dec 2d 18

Note- The S part of this Tp falls in and Cedar hills And is not Surveyed. Therefore the established Cor. to secs 19, 25 & 30 I run West on true line through the Tp according the instructions of the Office

West on true line bet Secs 24 & 25 Va 16° 30' E.

40.00 On E foot of Low hill Set Sand Stone 12x9x6, 8 in deep, marked on N side with stone mound for 1/4 Sec. Cor.

54.00 Enter Flat.

80.00 Set Sand Stone 13x9x6, 8 in deep, marked 2 on S and 1 on E edges, with stone mound Cor to Secs 23-24-25 & 26.

BOOK-A-1

Salt

Le

West

1600 Lea

4000 Set

Mar

For

8000 Set

Mar

reg.

26 &

Moun

Salt Lake Meridian

Land Mostly level.

Soil 1st rate

No Timber

West on true line bet Secs 23 & 26

Va 16° 30' E.

6.00 Leaves flat enters mountains

40.00 Set Sand Stone 16 × 12 × 12, 11 in. deep

Marked 1/4 on N side with Stone Mound

for 1/4 sec. Cor.

80.00 Set Sand Stone 14 × 10 × 4, 9 in deep

Marked 2 Notches on S and E edges, with

reg. mound and pits for Cor. to secs 22-23

26 & 27

Land Mostly Mountainous

Soil 3d rate

No Timber

Mountainous on 6 Chs

Subs 2 N 6 W 24 E

West on true line bet Secs 22 & 27
Var 16° 30' E.

40.00 Set sand stone 10 x 10 x 9 - 6 in deep
Marked 1/4 on N side with stone Mound
for 1/4 Sec. Cor.

53.00 Gulch drains N

80.00 Set sand stone 10 x 9 x 8 - 6 in deep
Marked 2 Notches on S and 3 on
sides, with stone Mound for Cor.
Secs 21-22-27 & 28

Land broken Mountainous
Soil 3d rate.
No timber
Mountainous on So Side

West on true line bet Secs 21 & 2
Var. 16° 30' E.

9.00 Gulch drains N E.

4000 Set sand stone 18 x 8 x 4, 12 inch

Salt Lake Meridian

Marked 1/4 on N side, with reg mound & pits for 1/4 Sec. Cor.

80 0 0 Set Sand Stone 12 x 12 x 6 - 8 in deep

Marked 2 Notches on S, and 4 on E edges

With reg. Mound & pits for Cor. to Sec's

20. 21-28 & 29.

Land Mountainous

Soil 2d rate

No Timber

Mountainous on do Ch's

West on true line Set Sec 20 & 29

Va. 16° 30' E.

40.00 Set Sand Stone 10 x 8 x 6 - 6 in deep

Marked 1/4 on N side with reg.

Mound & pits for 1/4 Sec. Cor.

57.00 Gulch drains N.W.

80.00 Set Sand Stone 12 x 9 x 5 —

8 in deep marked 2 Notches.

Subs Tp 6 S R 24 E.

ow S and it ow E edges with
Stone Mound for Cor to Secs 19.
20 - 29 & 30.
Land Mountainous
Soil 2d rate
No Timber
Mountainous ow & o Chs

West on true line bet Secs 19 & 30 40.00
Ja. 16° 30' E.
21.00 Enter float
40.00 Set Sand Stone 11 x 8 x 4 6 in
deep. Marked 1/4 on N side 57.00
with S.M. for 1/4 Sec. Cor
77 40 Allowing for Convergency of Mer 80.00
Set Sand Stone 13 x 9 x 4 9 in
deep, Marked 4 Notches on 1
and 2 on S edges with Bg
Mds & pits for Cor to Secs 19-24

Salt
25
L
C
M
N
Se
15
with
Cor.
Sa
inde
Set
3 No
reg.
23 and

Salt Lake Meridian

25 and 30 on W bndry of Tp
Land Mostly level.
Soil 1st rate
No Timber
Mountainous on 21 Chs.
Dec 1. 1879

North bet Secs 23 & 24.
Var 16° 30' E.

40.00 Set sand stone 20 x 12 x 4 -
15 in deep. Marked 1/4 on W side
with reg. mound & pits for 1/4 Sec.
Cor.

57.00 Sand stone ledge, bears N W x S E Good
indications of Coal.

80.00 Set sand stone 20 x 6 x 4 - 15 in deep
3 Notches on S. and 1 on E. edges with
reg. Mound & pits for Cor to Secs 13 14
23 and 24 -
Land level.
Soil 1st rate
No Timber

Subs Tp 6 S. R 24 E.

East on random line between Secs 18 & 19
Va. 16° 30' E.

40.00 Set temp. 1/4 Sec. Cor.
50.50 Dry bed of Cliff Creek bears N.W.
79.84 Int E Boundary of Tp at Cor to Secs 13 & 24 from which
West on true line bet Secs 13 & 24
39.92 Set Charred Cedar post 4 x 4 in, 4 ft long 2 ft. dug with reg. mound & pits for 1/4 Sec. Cor.:
79.84 The Cor. to Secs 13-14-23 & 24.

Land level.
Soil 1st rate
No timber

Salt Lake Meridian

North bet. Secs 13 & 14

Va. 16° 30' E.

[illegible]4.00 Cliff Creek Gulch drains N.W.

40.00 Set Sand Stone 10 x 10 x 8 - 6 in. deep. marked 1/4 on W. side with reg. Mound & pits for 1/4 Sec. Cor.;

80.00 Set Sand Stone 12 x 9 x 6 - 8 in deep, Marked 4 Notches on S. and 2 on E. edges. with reg. Mound & pits for Cor. to Secs. 11 - 12 - 13 & 14.

Land level.

Soil 1st rate.

No Timber

East on random line bet Secs 12 & 13.

Var. 16° 30' E.

1000 Enter heavy rolling hills

Subs Tp 6 S. R 24 E

35.00 Leave Rame

40.00 Set Temp. 1/4 Sec. Cor.

45.00 Wash Drains S.

80.20 Int. & Boundary of Tp 3rd Lks N of Cor to Secs 12 & 13 from which N 89° 45' W on true line bet Secs 12 & 13

40.10 Set sand Stone 12 x 10 x 6 - 8 in deep Marked 1/4 on N side with reg Mound & pits for 1/4 Sec. Cor.

80.20 The Cor to Sec's 11, 12, 13 & 14

Land level & rolling

Soil 1st rate

Timber Scattering Cedars on hills

Mountainous on 25.00 Ch

BOOK-A-

Sec

No

15.00 Na

19.50 Wh

30.00 LO

40.00 Se

dee

Wi

Se

Se

dee

And

Mou

11 &

BOOK-A-168

Salt Lake Meridian

North Bet Secs 11 & 12
Va. 16° 30' E.

15.00 Wash drains W.

19.50 White River trail bears E & W

30.00 Deep Wash drns W.

40.00 Set Sand Stone 13 + 9 + 5 = 9 in deep marked 1/4 on W side with reg. Mound & pits for 1/4 Sec. Cor.

70.00 Set Sand Stone 14 x 8 x 8 - 9 in deep. Marked 5 Notches on S. and 1 on E edges with reg. Mound & pits for Cor. to Secs 1, 2, 11 & 12.

Land level.
Soil 1st rate
No timber

Sub's Tp 6 S R 24 E

East on random line bet Sec's 1 & 12.
Var 16° 30' E.

21.00	Wash drains S
33.00	" " "
40.00	Set Temp 1/4 Sec. Cor
52.00	Wash drains S.
74.50	" " "
	Enter hills
80.18	Int E Boundary of Tp at Cor. to Sec. 1 & 12 from which. West on true line bet. Sec's 1 & 12
40.09	Set sand stone 21 x 14 x 8 — 15 in deep marked 1/4 on N side with reg. Mound & pits for 1/4 Sec. Cor.
80.18	The Cor. to Sec's 1-2-11 & 12

Land mostly level.
Soil 1st rate.
No Timber
Mountainous on 5.50 Chs

BOOK-A-168

Salt Lake Meridian

North Controlling line Bet Secs 1 & 2
Va. 16° 30' E.

28.00 Enter Mountains

4.00 Set Sand Stone 14 x 8 x 8 — 9 in. deep, Marked 1/4 S. on W side with S. M for 1/4 Sec. Cor.

64.10 Init 1st Stand. Par. South
6.30 Chs West of Stand. Cor.
to Secs 35 & 36 — Where I set
a Sand Stone 15 x 6 x 6 — 10 in.
deep. Marked 1 Notch on E.
3 on N and 6 on S. edges. and
C.C. with S.M. for closing
Cor to Secs 1 & 2
Land Mountainous & Level
Soil 3rd & 1st rate
No timber
Mountainous on 36.17 Chs.

Subs Tp 6 S R 24 E

North. bet Secs 22 & 23.
Var 16° 30' E.

40.00 Set Sand Stone 18 x 9 x 4 — 12 in deep. marked 1/4 on W Side with S. M. for 1/4 Sec Cor.

12.50 Enter Teal.

80.00 Set Sand Stone 16 x 8 x 5 — 11 in. deep marked 3 Notches on S and 2 on E edges with S. M. for Cor to Secs 14, 15, 22 & 23.

Land Mostly Mountainous
Soil 3rd rate
No Timber
Mountain down 12.50 Ch.

East on Random line bet Secs 14 &
Var 16° 30' E.

40.00 Set Comp 1/4 Sec. Cor.

Salt Lake Meridian

80.10 Inst. N. and S. lines 12 lks N of Cor to Sec's 13, 14, 23 & 24 from Which N. 89° 55' W on true line Bet Sec's 14 & 23

40.05 Set Sand Stone 12 x 10 x 6-8 in deep. Marked 1/4 on W side with S.M. for 1/4 Sec. Cor.

80.10 The Cor. to Sec's 14-15-22 & 23

Land level.

Soil 1st rate.

No Timber

Dec. 3. 1879

Mon'l Bet. Sec's 14 & 15

Var 16°. 30' E.

40.00 Set Sand Stone 12 x 12 x 4-8 in deep. Marked 1/4 on W side with Reg. Mound & pit for 1/4 Sec. Cor.

0.75 Cliff Creek Gulch - 2 Chs wide dry N.W.

Subs T.p 6 S R. 24 E

8.00 Set Chamfered Cedar post 4" x 14" 4 ft long 2 ft deep. Marked - 14 Notches on S. and 2 on E. edges with Reg. Mound of pits for Cor. to Secs 10-11-14 & 15.

Land level.

Soil 1st rate

No Timber

East on random line Set Secs 11 & 14 Va. 16° 30' E.

6.00 West drain. A.W.

40.00 Set temp. 1/4 Sec. Cor.

80.18 Ent N and S line at Cor to Secs 11-12-13 & 14 from which West on true line Set Secs 11 & 14

40.09 Se
dee
(W
1/4
80.18 The

No

23.50 Tr
32.00 E.
40.00. Se
dee
reg
80.00 Se
Di
on

Salt Lake Meridian

40.09 Set Sand Stone 14 x 10 x 6 - 9 in deep. Marked 1/4 on N side With reg. Mound & pits for 1/4 Sec. Cor.

30.18 The Cor. to Sec's 10-11-14 & 15

Land level.

Soil 1st rate.

No Timber

Mon'd Set. Secs 10 & 11

Var. 16° 30' E.

23.50 Trail bears E. and W.

35.00 Enter Mountains

40.00. Set Sand Stone 12 x 8 x 8 - 8 in. deep. Marked 1/4 on W side with reg. Mound & pits for 1/4 Sec. Cor.

50.00 Set Sand Stone 12 x 12 x 8. 8 in. deep. marked 5 Notches on S. and 2 on E edges

Subd 1 p 6 s R 24 E

With reg. Mound & pits for
Cor. to Secs 2 - 3 - 10 & 11.
Land mostly Mountainous
Soil 1st rate
No Timber
Mountains on N & S Sides

Set on random line bet Secs 2 & 11
Va 16° 30' E.

19.00	Enter flat	15.00
27.00	Mark drains S	4.00
40.00	Set Temp. 1/4 Sec. Cor.	10.00
80.12	Int N and S lines, 42 lks N of Cor to Secs 1 - 2 - 11 & 12. from which N 89° 42' W. on true line bet Secs 2 & 11	54.50
40.06	Set sandstone 24 x 15 x 12 18 ins. deep. marked 1/4 on N side with reg - Mound & pits	8.00 3.74

BOOK-A-168

Salt Lake Meridian

for 1/4 Sec. Cor.

80.12 The Cor. to Sec's 2-3-10×11

Land mostly level)

Soil 1st rate

No Timber

Mountainous on 19 Chains.

North on true line Sec Secs 2 & 3.

Var 16° 30' E.

15.00 Enter flat.

4.00 Wash drains N.W.

10.00 Set Sand stone 10×10×8

6 in deep. marked 1/4 on it

Side with Stone mound for

1/4 Sec. Cor.

54.50 Ledge Ridge-Bears N.E. & S.W.

58.00 Wash in Hollow Drains S.W.

63.74 Intd 1st Stan. Par. South 5.90 Chs

W. of Stand. Cor to Sec. 34 & 35

Sub's Tp 6 R 24 E

Where I set Sand Stone
10 x 9 x 8 - 6 in deep Marked
2 Notches on E. & on W. and
6 on S. edges and C. C.
for Closing Cor. to Secs 2 & 3
Land Mountainous and Level
Soil 2d & 1st rate
No Timber
Mountainous on 2d. & 2d Chs.

Work Set Secs 21 & 22
Var. 16° 30' E.

15.00 Gulch drains N. E.
40.00 Set Sand Stone 13 x 7 x 7 - 7 in deep marked 1/4 on W side with S. M. for 1/4 Sec. Cor.
80.00 Set Sand Stone 14 x 8 x 8 - 9 in deep. marked 3 notches on S. and E. edges with Sm. for

40.00
79.00
79.80
39.90
79.80

Salt Lake Meridian

Cor. to Sec's 15-16-21 & 22.
Land Mountainous
Soil 1st rate
No Timber
Mountainous on So Sides

Course random line Bet Sec 15 & 22
Var 16° 30' E.

40.00 Set 1 emp 1/4 Sec. Cor.
79.00 Enter Flat.
79.80 Int N & S line 18 lks S of Cor to Sec's 14-15-22 & 23 from which ^ S 89° 52' W On true line Bet. Sec. 15 & 22.
39.90 Set sand stone 12 x 9 x 7 8 in. deep. marked 1/4 on N side with B. M. for 1/4 Sec. Cor.
79.80 The Cor. to Sec's 15-16-21 & 22.

Subs Tp 6. R-24 E

Land Mostly Mountains
Soil 2d rate.
No Timber
Mountainous on 5 q Chs

North Bet. Sec. 15 & 16.
Var 16° 30' E.

40.00 Set Sand Stone 18 x 8 x 4 - 12 deep marked 1/4 on W Side W
S. M. for 1/4 Sec. Cor.

45.00 Enter Creek

80.00 Set Stamped Cedar Post 4" x 4" x 4 ft Cong, 2 ft deep; Marked 1/4 Not Chs on S and 3 on E edges with Mound & pit for Cor to Sec's 9 10. 15 & 16.

Land Broken & level.
Soil 3d & 1st rate

BOOK-A-168

Salt Lake Meridian

No Timber

Mountainous on 4-5 Chs

East on random line bet Secs 10 & 15

Var. 16° 30' E.

4.00 Set temp. 1/4 Sec. Cor.

4.10 Cliff Creek Gulch — 2 Chains W

Drains N.W.

80.12 Int N and S lines 22 Chs N of Cor to Secs 10-11-14 & 15 (from which N 89° 51' W. on true line bet Secs 10 and 15

4.06 Set Charred Cedar post 4 x 4 in. 4 ft long — 2 ft deep Marked 1/4 S on N. side with rg. mound & pits for 1/4 Sec Cor.

80.12 The Cor. to Secs 9-10-15 & 16.

Land level

Soil 1st rate

No Timber Dec. 1899

Secs Tp 6 S. R 24 E.

North bet. Secs 9 & 10
Va. 16° 30' E.

28.00 Cliff Creek Gulch 2 chs W
Drains W

40.00 On S side of trail Bears
E & W, Set Sand Stone 12 x 8 x
8 in. deep Marked 1/4 on W
With reg. Mound & pit for 1/4 Sec

80.00 Set Sand Stone 14 x 8 x 8 — 9 in
deep Marked 6 notches on S
3 on E. edges with reg. Mound
& pit for Cor. to Secs 3-4-9 & 10
Land Level.
Soil 1st rate.
No Timber

East on Random line bet Secs 3 &
Va. 16° 30' E.

3.00 Dry bed of Birch Creek Drains S

40.00
73.40
74.50
80.16
40.08
80.16
17.00
2.00

Salt Lake Meridian

40.00 Set temp 1/4 Sec. Cor.
73.40 Wash drains S.
74.50 Enter hills
80.16 Int N & S line at Cor to Secs.
2-3-10 & 11 from which
W. 0 w true line Bet Secs. 3 & 10
40.08 Set Sand Stone 20 x 5 x 6 - 15 in
deep Marked 1/4 on N side with
A.M. for 1/4 Sec. Cor.
80.16 The Cor to Secs 3, 11, 9 & 10 -
Land Mostly Level.
Soil 1st rate
No Timber
Mountainous 5.66 Chs

North true line Bet Secs 3 & 4
Var 16° 30' E.
17.00 Leave flat. Ledge ridges bro E and W.
32.00 Foot of Main Mountains

Subs Tp 6 S R 24 E

40.00 Set Sand stone 16 x 8 x 6 –
10 in deep. Marked T 4 on W
side with S.M. for T 4 Sec
Cor.

63.40 Int. 1st Stand Par. S. 5.86 Chs
W. of Stand. Cor. to Sec's 33 &
34 Where I set Sand Stone
14 x 12 x 10 – 9 in. deep, Marked
3 Notches on E & W. 6 to the
S. and C.C. for Closing Cor
to Sec's 3 & 4.

Land mostly Mountains.
Soil 2d rate.
No Timber
Mountainous on 46.40 Chs

North Set Sec's 20 & 21
Var. 16° 30' E.

40.00 Set Sand Stone 18 x 12 x 6 –

12

COOK-A-168

Salt Lake Meridian

12 in. deep; Marked 1/4 on W side with S. M for 1/4 Sec. Cor.

80.00 Set Sand Stone 12 x 9 x 6 - 8 in deep. Marked 3 notches on S and 4 on E edges. with S. M. for Cor. to sec's 16-17-20 & 21

Land Mountains

Soil 3d rate

No Timber

Mountainous ow do Cho.

East on random line bet. Sec 16 & 21.

Var 16° 30' E.

40.00 Set Temp. 1/4 Sec. Cor.

79.94 Int. N and S. line 21 Chs

N of Cor. to Sec's 15-16-21 & 22

From which North 89° 51' W. on true line bet. Sec's 16 and 21

Dubs T. 6 S. R 24 E

39.97 Set Sandstone 12 x 9 x 7 – 8 in deep Marked 1/4 on N Side with Stone Mound for 1/4 Sec Cor..

79.94 The Cor to Secs 16 – 17 – 20 & 21

Land Mountains

Soils 2d rate

No Timber

Mountainous on 79.94 Chs

North Set Secs 16 & 17

Va. 16° 30' E.

19.00 Enter flat.

40.00 Set Sand Stone 14 x 10 x 8 – 8 in. deep, Marked 1/4 on W Side with S. M for 1/4 Sec Cor.

80.00 Set Sandstone 10 x 8 x 7 – 6 in. deep Marked 4 Notches on S. and E edges with

40.00

69.00

80.00

40.00

BOOK-A-168

Salt Lake Meridian

S. M. for Cor. to Sec's 8-9-16 & 17

Land Mostly level
Soil 1st rate
No Timber
Mountainous on 19 Ch's

Easton random line Set Sec's 9 & 16.
Va. 16° 30' E.

40.00 Set temp. 1/4 Sec. Cor.
69.00 Wash Drains N W.
80.00 Int. N & S line at Cor. to Sec's 9-10-15 & 16 from which N on true line Set Sec's 9 & 16.
40.00 Set Charred Cedar post. 4 x 4 - 4 ft long, 2 ft deep. Marked 1/4 S. on W side With Reg. Mound & Pits for 1/4 Sec Cor.

Subs Tp 6 S R 24 E

8000 The Coz. to Secs 8-9-16-& 17.
Land level.
Soil 1st rate
No Timber

North bet. Secs 8 & 9.
Va. 16° 30' E.

40.00 Set Sand Stone 16 x 9 x 5 11 in. deep Marked 1/4 on N side, with L.M. for 1/4 Sec Co

62.00 Cliff Creek Gulch. 3.50 Chs wide Drains N.W.

69.50 White River trail Crs N.W. & S.E.

72.50 Leave bottom, Ascend

80.00 Set sandstone 18 x 12 x 6 - 12 in. deep, Mound 5 Notches on S and E on East edges with Stone Mound for Co. to Secs. 4, 5, 8, & 9.

Land Mostly level.
Soil 2d rate
No Timber
Mountainous on 7.50 Chs

Sub

0.70
39.50
40.00
57.75
80.20
80.10
80.20

BOOK-A-168

Salt Lake Meridian

East on random line bet Secs 4 & 9
Var 16° 30' E.

0.70 Sand stone ledge S

39.50 Wash drains S

40.00 Set temp. 1/4 Sec. Cor.

57.75 Wash drains S.

80.20 Int. N & S line at Cor to Secs 3-4-9 & 10, from which W on a true line bet Secs 4 & 9

40.10 Set sand stone 14 x 8 x 8 - 9 in deep. Marked 1/4 on N. side with S. M. for 1/4 Sec. Cor.

80.20 The Cor. to Secs 4-5-8 & 9.

Land level.

Soil 2d rate

No Timber

Dec. 5, 1879

Subs: Tp. 6 S R 24 E

North on true line. Set Lec 4 &
Var 16° 30' E.

20.00 Sand Stone ledge bears N. E. 26.00
40.00 Set Sand Stone 10 x 8 x 7 - 6 in 40.00
deep. Marked 1/4 on W side
with S. M. for 1/4 Sec. Cor.
Leave Peak. 10.00
59.00 Wash hollow drain SW.
63.80 Int. 1st stand. par. S - 6.20 Chs
W. of Stand. Cor to Secs 32 & 33.
Where I set Sand Stone 12 x 8 x 6.
6 in deep. Marked + Notches on 6
2 on W. 6 on S Edges and C.C.
for Closing Cor. to Secs 4 & 5
Land mostly level
Soil 1st rate
No Timber
Mountainous on 23.80 Chs

BOOK
Salt
No
E
On l
Se
dep
wi
Se
dep
und
L.
20
M
E
40.00 Se

Salt Lake Meridian

North bet. Secs 19 and 20.

Var. 16° 30' E.

Enter flat

26.00 Set sand stone 10 x 8 x 7 - 6 in deep; Marked 1/4 on N side with Stone Mound for 1/4 Sec. Cor.

80.00 Set sand stone 12 x 9 x 7 - 8 in deep. Marked S & notches on S. and E on E. edge with L. M for Cor to Secs 17 - 18 - 19 & 20.

Land Mostly level.

Soil 1st rate

No Tim.

Mountainous. 26.00 Chs

East on random line bet Secs 17 & 20

Var 16° 30' E.

40.00 Set Temp 1/4 Sec. Cor.

Subs Tp 6 s R. 24 E

44.00 Level flat.

80.00 Int. N & S line at Cor to Secs 16, 17, 20 & 21 from which
N on true line bet Secs 17 &
20

40.00 Set Charred Ced post
4 x 4 in. 4 ft long - 2 ft. deep
Marked 1/4 S. on W side, with
req. Mound & pits for 1/4 Sec.
Cor.

80.00 The Cor to Secs 17-18-19 & 20
Land level & Mountains
Soil 1st & 3d rate
No Timber
Mountainous on 360 chs

West on random line bet Secs 18 & 19
Var 16° 30' E.

40.00 Set temp 1/4 Sec. Cor.

59.00 Lev
76.98 Int
24
from
true
76.98 Set
deep
wi
76.98 The
M
No
40.00 S
m
&

Salt Lake Meridian

59.00 Leaves flat.

76.98 Int. W Boundary of Tp.
2nd Lk N of Cor to Secs 18 & 19
from which N 89° 30' E on
true line Set Secs 18 & 19.

76.98 Set Sandstone 16 x 9 x 7 - 11 in
deep. Marked 1/4 on N side
with A. M. for 1/4 Sec Cor.

76.98 The Cor to Secs 17-18-19 & 20
Land mostly level.
Soil 1st rate.
No Timber
Mountainous 17, 98 Chs

North bet Secs 17 & 18
Va. 16° 30' E.

40.00 Set Sand Stone 11 x 8 x 7 - 6 in deep
Marked 1/4 on N side with reg. Mound
& pits for 1/4 Sec. Cor.

Subs T. 6 S. R. 24 E.

46.00	Leave Flat
80.00	Set Charred Cedar Post 4×4 in., 4 ft long, 2 ft deep. Marked + Notches on S and S on E. edges with reg. Mound + pits. for Cor to Sec. 7-8-17-+18.
	Land level + Mountainous
	Soil 1st + 2d rate
	No Timber
	Mountainous on 3rd & 4th Subs

East on random line Bet. Secs 8 + 17. Var. 16° 30' E.

40.00	Set temp 1/4 Sec. Cor.
38.00	Enter Flat
80.10	Int. N and S line at Cor to Secs 8-9-16+17 from which

BOOK-A-168

Salt Lake Meridian

N on true line bet Secs 8 & 17

40.05 Set Sandstone 12 x 10 x 5 —
8 in. deep N ¼ on N side
marked
with reg. mound & pits for ¼ Sec
Cor.

20.10 The Cor to Secs 7-8-17 & 18
Land Mostly Mountains
Soil 2d rate
No Timber
Mountainous on S & W Bks

West on random line bet Secs 7 & 18
Var 16° 30' E.

40.00 Set temp ¼ Sec Cor
62.00 Gulch Drains N
77.20 Int. N - boundary of Ty. 41 Bks
N. of Cor to Secs 7 & 18 - from
Which N 89° 42' E on true
line bet Secs 7 & 18

Subs Tp 6 o R 24 E.

3720 Set Sand Stone 11 x 10 x 7 - 6 in deep Marked 1/4 on N side with Stone Mound for 1/4 Sec Cor.

7720 The Cor. to Secs 7-8-17+18
Land Mountains
Soil 2d rate
No Timber
Mountainous on 7.20 Chs

North bet Secs 7+8
Var 16.° 30 E.

3200 Enter Flat

4000 Set Sand Stone 12 x 10 x 6 - 8 in deep. Marked 1/4 on N side with reg. Mound & pits for 1/4 Sec. Cor.

4200 Wash drains NE.

4900 Trail bears E & W.

BOOK-A

BOOK-A-168

Salt Lake Meridian

40.00 Level flat.

20.00 Set sand Stone 10 x 9 x 7 - 6 in deep. Marked 5 Notches on S and E edges with Stone Mound, for Cor to Secs 5-6-7 and 8.

Sand Mountains & Level Soil 2d & 1st rate.

No Timber

Mountainous on N & W Chs

East on random line Bet Secs 5 & 8

Var 16° 30' E.

25.00 Enter Flat.

32.50 Wash drains N

39.90 White River trail bears N.E. and S.W.

40.00 Set temp. 1/4 Sec. Cor.

41.00 Cliff Creek Gulch drains N.W.

Subs Tp 6 s R 24 E.

80.00 Int. N and S lines at Cor to Secs 4-5-8 & 9. from which W on true line bet Secs 5 and 8

40.00 Set Sand Stone 15 x 10 x 4 10 in. deep Marked 1/4 on N side with stone mound for 1/4 Sec. Cor.

80.00 The Cor to Secs 5-6-7 & 8

Land mostly level

Soil 1st rate

No Timber

Mountains on 25.00 Chs

Dec. 6. 1879

West on random line bet.

Secs 6 & 7

Var 16° 30' E.

40.00 Set temp 1/4 Sec. Cor.

77.50 Int. N bound'y of Twp 20 N. of Cor to Secs 6 & 7 from

Salt Lake Meridian

Which N 89° 51' E on true
line bet Secs 6 and 7
3750 Set sand stone 11 x 9 x 6.
6 in deep. Marked 1/4 on N
Side with stone mound for
1/4 Sec. Cor.
7750 The Cor. to Secs 5-6-7 & 8
Land Mountains.
Soil 2d rate.
No Timber
Mountainous on 77.50 Chs

North true line bet
Secs 5 and 6.
Var. 16° 30' E.
2380 Enter flat.
33.20. Cliff Creek Gulch 2 Chs Wide
Drains NW.
4000 Set sand stone 14 x 12 x 6.

Subs Tp 6 S R 24 E.

BOOK-

9 in. deep. Marked 1/4 on W side with Stone Mound for 1/4 Sec. Cor.

52.50 Enter Swamp.

64.00 Int 1st Stand. Par S. 6 chs W. of Stand. Cor. to secs 31 & 32. Where I set Sand Stone 20x16 in. - 15 in. deep Marked 5 Notches on E. and 6. 6. on S Edges with Stone Mound ~~and C. C.~~ for Closing Cor to Sec 5 & 6.

Land mostly level.

Soil 1st rate.

No Timber

Mountainous 23.80 Chs

Dec. 7. 1879

BOOK-A-168

Salt Lake Meridian

General description

The surveyed part of this Township embraces a portion of Cliff Creek Valley. At ordinary seasons there is more than enough water in Cliff Creek to irrigate the land surveyed, but owing to extreme drought, the bed ~~of the bed~~ of the Creek was dry at the time of Survey. The Valley contains 1st Class Soil, and is situated on the Main trail between the Uintah and White River Agencies.

A D Perron
Dep Surveyor

BOOK-A-168

3811.

LIST OF NAMES.

A list of the names of the individuals employed to assist in running, measuring or marking the lines and corners described in the foregoing Field Notes of the

Guide Meridian, Exterior and Subdivision Lines embracing Tps 6 S., R. 2 E and 2 S., 2 E, Salt Lake Meridian, Utah Ty.

showing the respective capacities in whi
they acted.

Charles C. A. Bingham — *Chainman.*
William H Bradshaw — *Chainman.*
Alfred H Westover — *Flagman.*
Thomas Bingham Jr. — *Axeman.*

BOOK-A-168

We hereby certify that we have assisted

A. L. Perron

U. S. Deputy Surveyor in surveying the

Uinta Meridian, Exterior and Subdivision Lines embracing Pts 6 S. R. 2 E and 25 E., Salt Lake Meridian, Utah 93.

s in whi

hainman.

hainman.

Flagman.

Axeman.

287

and that said Townships have been in all respects, to the best of our knowledge and belief, well and faithfully surveyed, and the boundary monuments planted according to the instructions furnished by the Surveyor General.

(Signed) Charles C. R. Bingham Chainman.
William H Bradshaw Chainman.
Alfred H. Watrous Flagman.
Thomas Bingham Jr. Axeman.

Subscribed and sworn to by the above named persons, before me, a Dep'y Surveyor, for the ~~County~~ of ~~in the~~ Territory of Utah, this 10th day of December 1879

A. D. Ferron
Dep. Surveyor.

BOOK-A-168

I, A. G. Ferron

U. S. Deputy Surveyor, do solemnly swear that in pursuance of a contract with Fred. Salomon Surveyor General of the public lands of the United States in the Territory of Utah, bearing date the 12th day of June 1880, being an extension of Contract No. 92. and in strict conformity to the laws of the United States, the Manual of Surveying Instructions, and the instructions furnished by the said Surveyor General, I have faithfully surveyed the Guid Meridian Eastern and Subdivision Lines embracing Pt. 6 S. R. 2 E & 25 E. of the Salt Lake Meridian

U. S

S

Tow

of th

Exe

Und

of th

in th

hav

corr

field

her

In the Territory aforesaid, and do fur

solemnly swear that the foregoing are the

and original Field Notes of such survey.

A. D. Glenn

U. S. Deputy Surveyor

Subscribed by the said A. D. Glenn

U. S. Deputy Surv

and sworn to before me, a Notary

Public *for*

county of Salt Lake *in the Terri*

of Utah, this 10th *day of* August 1

Edward R. Wiggins

Notary Public.

BOOK-A-168

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, August 11 1880

The foregoing field notes of the survey of the

Subdivision lines

of

Township No 6 South *Range No* 2 East

of the Salt Lake Meridian, Utah Territory,

Executed by A. G. Ferron

Under his *contract No* 95; Ext of 92

of the 12th. *day of* June *1880,*

in the month of Dec. *18*79,

having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.

Fred. Salsbury

U. S. Surveyor General for Utah.

BOOK-A-168 (Book 168)
R: 1881.

291

Filed 1880.

Examined by John H. Crampe C.D.

Compared by T. C. Bailey

FIELD NOTES

OF

THE SURVEY OF THE

Exterior lines

of Township No. 6 South, Range No. 2 East

of the Salt Lake Meridian in Utah Territory.

BY

O. G. Ferron

U. S. DEPUTY SURVEYOR,

Under his Contract No. 95; Ext: of Cont: 92.

dated June 12th, 1880.

Survey commenced Dec. 2nd 1880.

Survey completed " " 1880.

Exterior Lines Tp 6 S R 24 E

Survey Commenced Dec 2nd

From the established Cor to Sec
19, 24, 25 and 30 on West Boundary 40.00
of Tp Drum

North Bet Secs 19 and 24
Va. 16° 30' E.

40.00 Set Charred Cedar post 4 x 4 in 80.00
4 ft long, 2 ft deep marked 1/4 S
on W side with regulation Mound
of earth and pits for 1/4 Sec. Cor.

59.00 Enters Broken Mountains.

80.00 Set Sand Stone 11 x 10 x 10 - 6 in deep
Marked 3 Notches on N and S Edges
with Stone Mound for 1/4 Sec. Cor
Land S 3/4 Flat. N 1/4 Mountainous
Soil 1st and 3d rates.
No Timber
Mountainous on 21 Chs

BOOK A-

Sec

No

Set
for
on
of E
Set
long
on
reg.
Cor.
L

Mo

Salt Lake Meridian

North Bet. Secs 13 & 18

Var. 16° 30' E

40.00 Set Charred Cedar post 4"x4"x4 ft long 2ft deep, marked 1/4 S on W side with reg. Mounds of earth & pits for 1/4 Sec. Cor.

80.00 Set Charred Cedar post 4"x4"x4 ft long, 2ft deep, marked 2 notches on N and 4 on S edges with reg. Mounds of earth & pits for Cor. to Secs 7. 12 - 13 & 18.

Land Broken Mountains

Soil 2d rate

Timber Scattering Cedar

Mountainous 80 Chs

291 Exh Tp 6 S. R 24 E

BOOK-A

Sect

North bet Secs 7 & 12
Va. 16° 30' E.

2400. Deep broad hollow Drains E 40.00 Set
40 00 Set Chained Cedar post, 4 x 4 Mar
4 ft long, 2 ft deep, marked 1/4 Moun
on W side, with reg. mound & Pit 20 In
Pit for 1/4 Sec. Cor. 3 Ch
7000 White River Trail bears NW & SE Pos
in Hollow drains S.E. set
8000 Set Sand Stone 10 x 10 x 8, 1/16 in deep
deep; Marked 1 Notch on N & Mon
S on S edges with stone Mound
for Cor: to Secs 1-6-7 & 12
Land Broken Mountains
Soil 3d rate
No timber
Mountainous on 80 Chs

BOOK-A-168

Salt Lake Meridian

North Bet. Secs 1 & 6.
Va 16° 30' E

40.00 Set Sand Stone 11 x 9 x 6, 6 in deep
Marked 1/4 on W side, with stone
Mound for 1/4 Sec. Cor.

0.20 Intersect 1st Stand. Pas. S
3 Chs W of Stand. Cor to Secs 31 & 36
Tps 5 S R 23 & 24 E when S
Set a Sand Stone 11 x 10 x 8, 6 in
deep, marked 6 notches on S. E.
& W sides & C. C. with stone
Mound for Closing Cor to Secs 1 & 6.

Land Mountainous
Soil 3d rate
No Timber
Mountainous on 6 & 20 Chs.

Dec. 2nd 1879

BOOK-A-168

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, August 11th *1880*

The foregoing field notes of the survey of the

Exterior lines of

Township No 6 South *Range No* 24 East

of the Salt Lake Meridian, Utah Territory,

Executed by A. Q. Ferron

Under his *contract No* 95; Ext of 92

of the 12th *day of* June *1880,*

in the month of Dec. *1879,*

having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.

Fred. Salsbury.

U. S. Surveyor General for Utah.