Vol 175. BOOK-A-175
R: 1882

Filed 187 .

Examined by J.H. Campbell & B. Gorlinski

Compared by E. Michaels & E. Salomon

FIELD NOTES

OF

THE SURVEY OF THE

North Boundary

of Township No. Dey S, Range No. 11 W.

of the Salt Lake Meridian in Utah Territory.

BY

S. C. Bailey

U. S. DEPUTY SURVEYOR,

Under his Contract No. 102,

dated May 2nd 1881

Survey commenced Aug 9. 1881

Survey completed " " 1881

Vol 175. BOOK-A-175
R: 1882

Filed 187 .

Examined by J.H. Campbell & B. Gorlinski

Compared by E. Michaels & E. Salomon

FIELD NOTES

OF

THE SURVEY OF THE

North Boundary

of Township No. Dey S, Range No. 11 W.

of the Salt Lake Meridian in Utah Territory.

BY

S. C. Bailey

U. S. DEPUTY SURVEYOR,

Under his Contract No. 102,

dated May 2nd 1881

Survey commenced Aug 9. 1881

Survey completed " " 1881

BOOK-A-175

/

Township 27 S. R. 11 W.

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

BOOK-A-175

North boundary T. 27 S. R. 11 W.

Survey commenced Aug. 7th 1884, with a Burts improved Solar compass.

From the cor. to Tps. 26 & 27 S. R. 11 & 12 W, set by me on the 4th inst, I run East on a random line between Tps. 26 & 27 S. R. 11 W, setting temporary corners at 40 & 80 chs, and at 6 miles, 1 chain and 70 links I intersect the East boundary of the township at the cor. to ~~secs.~~ Tps. 26 & 27 S. R. 10 & 11 W, —.

From the above cor, which

North Boundary T. 3 N. R. 11 W. 2

Stone is a Trachyte 21 x 9 x 9 in,
with pits and mound, set
by me, on this survey as
the re-established corner
to said Sec's, I run
West on a true line
Mer. Sec. 1836
Var. 15° 30' E.

9.00 Indian Trail bears N 45 E.

40.00 set Sandstone 14 x 12 x 6 in.
mk. in. in the ground for
1/4 sec. cor. marked 1/4 on
N side, dug pits 18 x 18 x
12 in. E & W. of stone 5 ft
dist, & raised mound of
Earth 1 ft. high 5 ft.
base alongside.

80.00 Trachyte 16 x 10 x 5 in. 11 in
in the ground, for cor. to
Secs. 1. 2. 35 T36. Marked

BOOK-A-175

R. 11 W. S. L. Mi.

I notch on E. & S. on N.
edges, dug pits 18x18x12
sup. mi each section 5 ft.
ft. dist, & raised a mound
of earth 2 ft. high 4 ft.
base alongside.
Land level flat.
Soil 1st rate.
Timber.
White stage brush on so. sec.

Set on the line
bet. Sec. 2 & 35
Var. 15 30' E.

Found Set charred cedar post
3 ft. long 3 in. square, 1 in.
in the ground for 1/4
Sec. cor. Marked 1/4 S. on

South boundary T. 2 S. R. 11 W.

chains N. side, dug pits 18×18×12 ins. E & W. of post, 5½ ft. dist, and raised a mound of earth 1½ ft. high 4 ft. base around post.

$1.00 Set charred cedar post 4 ft. long 4 ins. square 12 ins. in the ground for cor. to secs. 2. 3. 34 & 35, marked T. 2 S. S. 35 on N.
R. 11 W. S. 2 " SE.
T. 2 S. S. 3 " SW. and S. 34 on N. & W. faces, with 2 notches on E & 4 on W. Edges, dug pits 18×18×12 ins. in each section, 5½ ft. dist, and raised a mound of earth 2 ft. high, 4 ft. base along scale.

9.00

30.00

110.00

BOOK-A-175

R. 11 N. S. & M.

Land level Sage brush
Flat.
Soil 1st rate.
No timber.
Brush on 80 chs.

"

Mst on true line
bet. Secs. 3 & 34
Var. 15° 30' E.

9.00 Road from Frisco to Black Rock Springs bears S E & N W.

30.00 Leave white sage flat & enter dense artimesia.

40.00 Set Quartzite stone 14 x 12 x 10 ins. 10 ins. in the ground for Y sec. on marked Y on S. side; dug pits 18 x 18 x 12 ins. E & W. of stone

Post Boundary T. 27 S. R. 11 W. S.

1 chains	5½ ft. dist. & raised a mound of earth 1½ ft. high 3½ ft. base alongside. Ascend Gently.	4.50	chains
80.00	Set a Quartzite 18×14×13 ins. 1 ins. in the ground for cor. to secs. 3. 4, 33 & 34. Marked 3 notches on E & W Edges; drug pits 18×18×12 ins. in each sec. 5½ ft. dist. & raised mound of earth 2 ft. high 4½ ft. base alongside.	41.00	
	Land sloping East.	11.50	
	Soil 1st rate.	6.00	
	No timber.	40.00	
	Trees at intervals brush on N. & W. sides,		
	White sage on S. & to E. Post,		

W. S. Line.

chains Met on true line
bet. Secs. 4 & 33.
Var. 15°30' E.

4.50 Road bears NW & SE.

4.00 Set Quartzite stone 14 x 8 x 8 ins, 10 lks. in the ground for 1/4 sec. cor. marked 1/4 on N. side; dug pits 18 x 18 x 18 ins. E. & W. of stone 5 1/2 ft. dist, & raised mound of earth 1 1/2 ft. high 3 1/2 ft. base along side.

4.50 Road bears NW, ascend flat hills.

6.00 Ranch drains SE.

8.00 Set a Speckled Limestone 15 x 9 x 8 ins. 10 lks. in the ground for cor. to Secs. 4, 5, 32 & 33, marked 4 notches on E. & 2 on N. side,

North boundary T. 2 N. R. 11 W.

6 chains and passed a mound of stones alongside.	
Land E. & gently rocky.	
W. & mountainous—	58.00
Soil 2d rate,	79.00
No timber,	80.00
Dense sagebrush and rocks.	

"

Met on true line
bet. Secs. 5 & 32
Var. 15° 30' E.

2.00 Ravine drains SE. mound
26.00 Top of hill bears SE.
37.50 Ravine drains "
40.00 set Quartzite 14 x 10 x 10 ins,
10 ins. in the ground for
¼ sec. cor. Marked ¼ on
N. side, & raised a

BOOK-A-175

W. S. L. M.

Mound of stones along=
side— Ascend S. Slope
of hill.

58.00 Ranie draws S.

79.00 " " "

8.00 set Quartzite 16×10×9
ins. well in the ground
for cor. to secs. 5, 6, 31, 32,
marked 6 notches on E. &
W. on west edges, & raised
a mound of stones along=
side.
Land mountainous.
Soil 2d rate.
A few cedars.

West on true line
bet. secs. 6 & 31.

North Boundary T. 24 S. R. 1 W. S.

Chains Var. 15°30' E.

Ascending S E slope.

40.00 Set Quartzite 16 x 12 x 6 in. 11 ins. in the ground for 1/4 sec. cor. marked 1/4 on N. side, & raised mound of stones alongside.

81.70 The cor. to Tps. 26 & 24 S. R. 11 & 12 W. Mt. Diablo: a Limestone 16 x 6 x 6 in. properly marked with stone mound along side, and two cedar bearing trees as follows:

Cedar 12 ins. dia. bears N 70 W. 100 links

" " " " " S 40 W. 100 " both properly marked.

Land Mountainous Soil 2d rate.

Timber scattering cedars.

Aug. 7th 1881.

"

BOOK-A-175

N. S. L. M.

General Description

The land in this T. is generally 1st rate, except the part in the mountains in the centre, and in the N.W. corner—
There is a settlement on the line of the Rail Road and one at the old Hickory mine near the centre of the T.
The whole can be subdivided.

T. C. Bailey
U. S. Dep. Surv.

BOOK-A-175

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, October 5th *1881*

The foregoing field notes of the survey of the

North boundary of

Township No 27 S. *Range No* 11 W.

of the Salt Lake Meridian, Utah Territory,

Executed by T. C. Bailey

Under his *contract No* 162

of the 2nd *day of* May *188*1.

in the month of Augt. *188*1.

having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.

Fred. Salsbury

U. S. Surveyor General for Utah.

BOOK-A-175

R: 1882

5

Filed 187 .

Examined by J. N. Lamps & B. Goslinski

Compared by E. Michales & E. Salomon

FIELD NOTES

OF

THE SURVEY OF THE

South, & North & Re-survey of W. boundaries of Township No. 21 S., Range No. 12 W.

of the Salt Lake Meridian in Utah Territory.

BY

P. C. Bailey

U. S. DEPUTY SURVEYOR,

Under his Contract No. 17

dated May 2nd 1881

Survey commenced August 8 1881

Survey completed " 9 1881

BOOK-A-175

2

Township 27 S. R. 12 W.



BOOK-A-175

South boundary T. 27 S. R. 12 W.

Survey commenced Aug. 8th 1881, by a Burt's improved solar compass, which I tested on the meridian and found correct.

From the Trachyte stone 36 x 12 x 6 ins, with pits & mound, being the cor. to Tps. 27 & 28 S. R. 11 & 12 W. I run a

Met on random line

between said

townships in Range 12 W,

Var. is 30° E,

Setting temporary corners at 40 & 80 chs, and at 6 miles 7 chains & 35 links I intersect west boundary of the township 20 links S. of the cor. to

South boundary T. 29 S. R. 12 W.

Tps. 28 & 29 S. R. 12 W. 3 M.
Viz: A granite 14 x 14 x 18 in.
Marked 6 notches on N. S. E & W. edges with mound of earth thrown around the corner from the boundary
From the above cor. I run
S. 89° 59' E. on a true line bet. secs. 6 & 31, Tur. 18° 30' E.
42.35 Reach Arauis R.C.
47.35 Set a limestone stone 14 x 14 x 10 ins. 10 lbs. in the ground for ¼ sec. cor. Marked ¼ on N. side, dug pits 18 x 18 x 12 in. E & W. of stone 5½ ft. dist. & raised mound of earth 1½ ft. high 3½ ft. base elongated.
79.00 I saw timber & under heavy sage brush
87.35 On hill bears N. W. S. bet

40.00

BOOK-A-175

12 M. S. L. 315

a Trachyte 15 x 12 x 8 in. 10 in in the ground for cor. to Secs. 5. 6. 31 & 32, marked X 5 notches on E & 1 on N. Edges, & raised a mound of stones along side.
Land broken.
Soil 2d rate.
Timber cedars on 79. chs.
Dense sage brush on 8.35 Chains.

—— " ——

S. 89° 57' E. on a true line bet. Secs 5 & 32
Run 15.36 Chs.

40.00 Set Limestone 14 x 12 x 8 ins, 10 ins. in the ground, for

South boundary T. 24 y S. R. 1

chains	¼ sec. cor. Marked ¼ on S. side, dug pits 18×18×12 in. E & W. of stone 5 ½ ft. dist. & raised mound of Earth 1½ ft. high, 3½ ft. base alongside.	chains
		25.00
		39.50
		40.00
72.08	Telegraph Line bears N & S.	
80.00	Set a Trachyte stone 15×12×12 ins. 10 ins. in the ground for cor. to secs. 4, 5, 32 & 33, marked 4 notches on E. & 2 on N. edges; dug pits 18×18×12 ins. in each sec. 5 ½ ft. dist. & raised a mound of earth 2 ft. high 4½ ft. base alongside.	
		59.00
		65.65
		77.00
		80.00
	Land broken bench soil 2d class.	
	No timber	
	Dense sage brush on Socho.	

BOOK-A-175

R. 12 W. S. L. M.

chains	S. 89° 59' E. on a true line bet. Secs. 4 & 33.
25.00	Head of hollow drains &c.
39.50	Diverted from Bench
40.00	Set a Trachyte stone 16 x 11 x 10 ins. 11 ins. in the ground for 1/4 sec. cor. marked 1/4 on N. side, dug pits 18 x 18 x 12 ins. E & W. of stone 5 1/2 ft. dist, Traced a mound of earth 1 1/2 ft. high 3 1/2 ft. base alongside. Enter broad hollow drains &c.
59.00	Road bears N. & W.
65.65	Road to Shamutee bears S. & E.
77.00	Leave the hollow drains S. E.
80.00	Set a Trachyte stone 14 x 10 x 4 ins. 10 ins in the ground for cor. to secs. 3. 4. 33 & 34, marked 3 Notches

South boundary T. 2 y S. R. 1

Mounds on E & W. Edges, dug pits 18 x 18 x 12 in. in each sec. 6 1/2 ft. dist. & raised a mound of earth 2 ft. high by 3 1/2 ft. base alongside. 67.00
Land rolling bench 77.00
Soil 1st rate. 85.00
No timber.
Dense sage brush on sec.

N. 89° 59' E. on a true line between Secs. 3 & 34
Var. 15° 30' E.
40.00 Set Limestone 15 x 12 x 6 ins 10 in. in the ground for 1/4 Sec. cor. Marked 1/4 M.
Pile, dug pits 18 x 18 x 12 ins, E & W. of stone 6 1/2

BOOK-A-175

R. 12 W. S. L. M.

ft. dist. & raised a mound of earth 1½ ft. high, 3½ ft. base along side, on N. point of ridge.

6" 00 Hollow drains N.W.

" 7.00 Wash " "

8.00 Set Trachyte stone 14×12×6 ins. rough, in the ground for cor. to secs. 2. 3. 34 & 35, marked 2 notches on E & N. Edges, drag pits 18×18×12 ins. in each sec.

~~Stone~~ 5½ ft. dist. & raised a mound of earth 2 ft. high 4½ ft. base alongside.

Laid broken bench rail, 2d sale,

N Inner

Sage brush 80 chs.

"

South Boundary T. 24 S.

20

S. 89°59' E. on a true line
bet. Secs. 2 & 35
Var. 15 30' E.

40.00 On N. point of ridge, set a hackmatack 8 x 12 x 12 ins, 12 ins, in the ground for 1/4 sec. cor. Marked 1/4 on N. side, & raised a mound of stones alng. side,

80.00 Set Tamarack stone 24 x 12 x 8 ins. 18 ins, in the ground for cor. to secs. 1, 2, 35 & 36, Marked 1 notch on E & S on N. Edges & raised a mound of stones alongside.
Land broken bench.
Soil 2d rate.
No timber. Sage brush & cho-

2.00
40.00
80.00

BOOK-A-175

R. 12 W. S. L. M.

S. 89° 59' East on true line
bet. Secs 1 & 36
Dist. 153.0 ch.

2.00 Enter Sage brush flat. Wks.

4.00 Set Trachyte stone 14 x 12 x 6 ins. 10 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on N. side, dug pits 18 x 18 x 12 ins, E & W. of stone 5 1/2 ft. dist, & raised a mound of earth 1 1/2 ft. high & 5 ft. base alongside.

8.00 The Cor. to Tps. 2 & 3 S. R. 11 & 12 W. described in the beginning of these notes.

Sand Bench & flat.
Soil 1st rate.
Timber—Sagebrush &c. chs.

11

BOOK-A-075

Re-survey 2-2

West boundary T. 27 S. R. 12 W.

olhs Survey commenced Aug. 8th 1881,

Note:

Having formerly run a random line along the South boundary of this township and at 6 miles I made search for the old corner to T. 27 & 28 S. R. 12 & 13 W, but was unable to find it; I therefore run a blank line North and at a distance of 3 miles I found the old Limestone 12 x 12 x 10 ins, with mound of stones, which was pointed out to me by E. Buettner & U. S.

deputy Mineral surveyor
dec'd cor. to secs. 13, 18, 19,
24, 5 chains west of
my line— From this
corner I run the line
south; at 40 chs, I
find the old sandstone
lying loose upon the
ground 2.35 links west
of my line,
At 80 chs, I find no
trace of old corner.
At 1½ miles I find
the old stone standing
50 lks west of my line,
At 2 miles I find the
old stone cor. standing
2.35 chs. west of my line
At 2½ miles I find no
trace of old corner,

BOOK-A-175

and at 3 miles I found the old granite stone 14×14×12 ins, lying loose 2.35 links west of my line, and found fresh trace of the old Earth mound, by which I was enabled to identify this as the old corner point, altho' it is 7.35 chains west of its true position —

Finding the line in the above emergency I deem it necessary to resurvey it, in order to reestablish the old corners, and to properly mark the true point for the

Re-survey

West boundary T. 27 S. R 12 E. 25

Chains		Chains
	Pp. Cor. 6 miles north;	
	Thence from the	
	above described corner,	
	after ~~adding~~ re-setting	
	the same in the old	
	mound, which is	
	ground for re-established	
	corner to T. 27 & 28 S. R.	41.10
	12 & 13 E. and adding	45.00
	pits 24 x 18 x 12 in, length	8.00
	north and south on each line S. E.	
	& W. of stone 6 ft. east,	
	& raised a mound of	
	Earth 2½ ft. high 5 ft.	
	base alongside, I run	
	North on a Re-survey	
	line bet. Secs. 31 & 36	
	Var. 15° 50' E.	
	by cedar timber	
2.80	Wash drains S E.	
40.00	to tree of old corner	

BOOK-A-175

N. S. L. M. 26

Chains Set a Slate Rock 14 x 12 x 10 ins. 10 ins. in the ground for re-established 1/4 sec. cor, marked 1/4 on N. side & raised mound of stones along side.

41.10 Rash drains East.

45.00 Leave cedars

8.00 Find old lava rock 12 x 10 x 6 ins, with mound of stones on line. Lined rolling nuts, soil 2d rate. Cedars on 45 chs,

N. 2°38' E. on re-survey line bet. secs. 25 & 30

Var. 15° 30' E

Re-survey

West boundary T. 2 N., R. 2 E.

4.50	Ridge bears E & W.	57.75
20.25	Wash drains E.	
30.00	Top of divide bears E & W.	70.00
40.00	Find the old Lava Rock 14 x 10 x 8 ins, standing with stone mound, properly marked -- Note: Although this corner is out of line I cannot move it into its proper place as the Tp. on the west has been subdivided. As I failed to find the Sec. cor. on the line going south, but found the stone for the 1/4 cor. bet. Secs. 19 & 24 thereon I change my course (as I am now 185 links east of said 1/4 Sec. cor.) to N. 1° 19' W.	80.00

BOOK-A-175

12 W. S. L. M.

57.75 Road bears S E, in a hollow drains S E.

70.00 West side of knoll.

80.00 Find no trace of old cor. I set a Trachyte stone 18 x 18 x 8 in. 12 ins, in the ground for cor. to secs. 19. 24. 25 & 30, marked 2 notches on S. & E. edges & mound of stones alongside. Land mountainous. Soil 2d rate. No timber.

"

At 1° 19' W. on N. survey line bet. secs. 19 & 24 Var. 15° 50' E.

Re-survey

West boundary T. 3 S., R. 1 W.

8.00 West slope of knoll

25.00 Wash drains N.

40.00 Fnd old sandstone chiseled cor, & remains of stone mound, I re-set same a Sandstone 10 x 8 x 4 in. 7 ins. in the ground for 1/4 sec. cor. marked 1/4 on N. side & raised a mound of stones alongside.

45 I am now 2.35 links N. of cor. to secs. 13. 18. 19 & 24

I now change my course and run N. 3° 22' E. so as to intersect at the sec. cor. as found on the retraced line.

43.00 Wash drains E.

48.00 Top of knoll

60.90 Utah Central R.R. bears N. 85 E.

62.55 Road bears N. & S.

80.00 Fnd old Limestone 12 x 12 x 10 ins, with stone mound,

N. S. & M.

Marked 3 notches on N & S. Edges. Note: This corner seemed to be out of place, but on account of the subdivisions on the west, and the land having been entered as the Fresco townsite immediately joining this line on the west, I cannot move it.
Land mountainous.
Soil & rate.
No timber.

"

I now change my course and run North on N=S survey line

Re-survey

West boundary T. 21 S. R. 12 E.

Chains bet. Secs. 13 & 18

Var. 15° 50' E.

18.50 Road E & W. A house bears S W. 100 lks. dist.

30.00 Road E & W.

40.00 Find no trace of old Cor: I set a sandstone 14 x 10 x 6 ins. 10 ins. in the ground for W. established 1/4 sec. Cor. marked 1/4 on W. side dug pits 18 x 18 x 12 ins. W. & S. of stone 5 1/2 ft. dist & raised mound of earth 1 1/2 ft. high, 3 1/2 ft. base alongside.

56.00 Road bears N & S W.

80.00 Find no trace of old Cor. I set a Red Sandstone 16 x 6 x 6 ins. 11 ins. in the ground for W. established

20.00

40.00

12

W. S. L. M.

corner to secs. 7, 12, 13 & 18, marked 2 notches on N. & from S. Edges, & dug pits 18 x 18 x 12 ins. in each sec. 5 1/2 ft. dist, & raised mound of earth 2 ft. high 4 1/2 ft. base along side. Land rolling foot hills—
Soil & rate.
Timber scattering cedar.
(End of N = survey.)

North bet. secs. 7 & 12
Var. 15° 50' E.

20.00 Ranie drains E.
40.00 set a Dorphony stone 14 x 10 x 6 ins. ins. in the ground for 1/4 sec. cor. marked

West boundary S. 2½ L.

chains
¼ on W. side, & mixed
a mound of stone along
side, from which
A pine 4in. dia. bears 45 E. 12
lks. dist. marked ¼ S. B. T.
40.50 small Range drains S. E.
41.00 Carbonate Mine Hoisting
works bears N. 71° E. about
40 chs dist.
71.00 Road bears S E & N W.
80.00 Set Quartzite 18 x 12 x 4in,
12 ins. in the ground for
cor. to secs. 1. 6. 7 & 12, marked 2.00
1 notch on N. & S on S. Edges 5.50
~~Raised~~ dug pits 18 x 18, 9.50
12 in. in each sec. 5½ ft.
dist, & raised mound
of earth 2 ft. high 4½ ft.
base alongside, from which 31.00
A Cedar 7in. dia. bears S. 35° E. 84 links 38.50

BOOK-A-175

R. 12 W.

Marked T. 2 y S. R. 12 W.
S. y. B. T.
Cedar 6 in. dia. bears N 55 W. 45 lks
Marked T. 2 y S. R. 13 W. S 1, B. T.
Land rolling foothills.
Soil 2d rate.
Timber cedars.

"

North bet. secs 1 & 6
Var. 15° 30' E.

	2.00	Same road bears NE.
	5.50	" " " NW.
	9.50	" " " N in Ravine drains SE. Charcoal Kilns bear N 70 W. about 1/2 chs. dist, in Sage Ravine.
	31.00	Top of East Spur.
	38.50	Road in Ravine S. E.

West boundary T. 2 y. S. R.

40.00 Set a Sandstone 18x10x4 ins. 12 ins. in the ground for 1/4 sec. cor. Marked 1/4 on N. side & raised mound of stones alongside, from which Cedar 6 in. dia. bears N. 75° W. 12 lks. " " 6 " " " " 180 E. 44 " Both trees marked 1/4 S.B.T.

76.00 Ranie drains S.E.

80.00 on S. slope of mountain. Set Sandstone 18x10x10 ins. 12 ins. in the ground for cor. to T. 26 & 2 y. S. R. 12 & 13 W. Marked 6 notches on N.E. & W. Edges, & raised mound of stones alongside, from which Cedar 24 in. dia. bears S 35° E. 25 lks. Marked T. 2 y. S. R. 12 W. S 6. B. T.

BOOK-A-175

12 W. S.L. M. 96

A Pine 4in. dia. bears S 70 W. 4 lks.
Marked T. 27 S. R. 13 W. S. B. T.
Cedar 14in. dia. bears N. 55 W. 32 lks.
Marked T. 26 S. R. 13 W. S 36. B. T.
Cedar 20in's. dia. bears N 35 E. 44 lks.
Marked T. 26 S. R. 12 W. S 31. B. T.
Land Mountainous
Soil 2d rate
Timber cedar.
Aug 8th 1881.

"

North boundary T. 25 S. R. 12 W.

Aug. 9th 1881

Beginning at the corner to T. 26 & 25 S. R. 11 & 12 W. viz: A limestone 16 × 6 × 6 in. 11 lks. in the ground, with stone mound from which a cedar 12 ins. in dia. bears N. 70 W. 100 lks. A cedar 1 in. dia. bears S. 70 W. 100 lks. 5.00 35.00 41.00

I run

West on a random line Var. 15° 50' E. between T. 26 & 25 S. R. 12 W., setting temporary corners at every 40 & 80 chs, and at 6 miles & 1 chain I intersect the cor. to T. 26, 25 & S. R 12 & 13 W. (described on the preceding page,) 53.00

12 N. S. L. M.

60 links north.
From the above cor. I run
S 89° 56' E. on a true line
Ref. Trees. 6 & 8
Var. 15° 50' E.

5.00 Knoll; direct

25.00 Ravine drains E. Ends N.

44.00 In same ravine, set a Porphyry 14 x 8 x 6 ins, mix. in the ground for 1/4 sec. cor. marked 1/4 on N. side from which
Accepted dia. bears S. 45 W. 20 lks.
Cedar 16 in. dia. bears S 35 W. 40 lks. Both marked 1/4 S. B. T.
And leave ravine.

53.00 Road bears N & S.

North boundary T. 2 y S. R. 12

$1.00	Set Porphyry stone 20x10,	19.00
	mis. 14 mis, in the ground	34.00
	for cor. to secs. 5. 6. 31 & 32,	40.00
	marked 5 notches on E & W	
	on N. Edges & raised a	
	mound of stones along	
	side; from which	
	A cedar 10 ins. dia. brs. N. 45 W. 15 lks.	
	Marked T. 26 S. R. 12 W. S. 31. B. T.	
	A cedar 10 in. dia. bears S 10 W. 12 lks.	
	Marked T. 27 S. R. 12 W. S 6. B. T.	
	Land East slope of mts.	80.00
	soil 2d rate,	
	Cedar timber	

11

N. 89° 56' E. on true line
bet. secs. 5 & 32
Var 16° 0' E.

BOOK-A-175

R. 52 W. S. L. Mer.

19.00 Road bears N W & S E.

34.00 " " " N E.

40.00 Set Sandstone 15 H x 8 ins. mins. in the ground for 1/4 Sec. cor. marked 1/4 X on N. side & raised a mound of stones alongside from which
A cedar 6 ins. dia. bears S. 80 E. 20 lks.
" " 6 " " " S 30 W. 18 "
Both trees marked 1/4 S. B. J.

80.00 Set Sandstone 18 x 10 x 10 ins. 12 ins. in the ground, for corner to Secs. 4. 5. 32 & 33, Marked 2 notches on W & N edges raised mound of stone alongside. from which
A cedar 8 ins. dia. brs. N 35 E. 55 lks
Marked T. 26 S R 12 W. S. 33. B. T.
A cedar 12 ins. dia. brs. S 10 W, 108 lks.

North Boundary T. 2 ½ S. R. 12 W. | ½ W.

Marked T. 2½ S. R. 12 W. S. 5. B. T.
Land for hills.
Soil 2d rate.
Timber cedar.

N. 89° 34' E. Met. Secs. 4933.
Var. 15° 30' E.

40.00 Set Flint stone 18×14×8 ins.
12 ins. in the ground for ¼
Sec. cor. marked ¼ in N.
side, from which
A cedar 6 in. dia. brs. N. 70 W. 80 lks. 22.00 Re
" " ½ " " " S. 15 E. 54 "
Both trees marked ¼ S. B. T. 40.00 Se
70.00 Leave cedars & foot hills
bearing N. & S. Entersage bu
80.00 Set flint stone 14×13×6 ins.
10 ins. in the ground, for cor

R. 12 W. S. L. M.

marked 5 notches on 64 Pines
to Secs. 3, 4, 33 & 34 Aug pits
18 X 18 X 12 ins. in each sec.
6½ ft. dist, & mound of
mound of earth 2 ft. high
4½ ft. base alongside.
Sand gutter E. slope
soil 1st rate.
Cedars on N. 70 chs.

"

N. 89° 56' E. On true line
bet. Secs. 3 & 34
Dan. 15° 50' E.

80 lks. 22.00 Road from Frisco to Coal Kilns
bears N. & S.
14 " 40.00 Set Sandstone 14 X 10 X 6 ins.
I. B. T. 10 ins. in the ground for
hills ¼ sec. cor. Mar. R. & ¼ on
N. Rod, Aug pits 18 X 18
X 12 ins. E & W. of line

North Boundary T. 2 y S. R.

5½ ft. dist, & raised mound
of earth 1½ ft. high 3½ ft.
base alongside.

68.50 Road from Frisco bears N. W.

80.00 Set Flint Stone 16 x 8 x 8
ins, in the ground for
cor. to secs. 2. 3. 34 & 35.
Marked ~~B C~~ 2 notches
on E & W edges, dug
pits 18 x 18 x 18 ins. in each
section, 5½ ft. dist, &
raised mound of earth
2 ft. high 4½ ft. base
alongside.
Land level
Soil 1st rate.
Timber
Dense Sage brush on sec.

11

BOOK-A-175

[6.—FINAL OATH OF UNITED STATES DEPUTY SURVEYOR.]

I, Thomas C. Bailey
United States deputy surveyor, do solemnly swear that in pursuance of instructions received from Fred. Salamon
United States surveyor general for Utah, bearing date of the 27th day of May, 1881, I have well, faithfully, and truly, in my own proper person, and in strict conformity with the instructions furnished by the United States surveyor general for Utah, the surveying manual, and the laws of the United States, surveyed all those parts or portions of Mendon, standard, township and subdivision lines under my contract No. 102 dated May 27, 1881, as surveyed and returned up to this date, situated South and West
of the Salt Lake base and meridian in the Territory of Utah, as are represented in the foregoing field notes as having been surveyed by me and under my directions; and I do further solemnly swear that all the corners of said survey have been established and perpetuated in strict accordance with the surveying manual, printed instructions, the special written instructions of the United States surveyor general for Utah, and in the specific man-

ner described in the field notes, and that the foregoing are the **TRUE** *field notes of such survey; and, should any fraud be detected, I will suffer the penalty of perjury, under the provisions of an act of Congress, approved August 8, 1846.*

Thomas C. Bailey

United States Deputy Surveyor.

Subscribed and sworn to before me this 22

day of Sept. *1881.*

Jno A. Bailey

Notary Public

BOOK-A-175

57

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, Oct 7th 1881

The foregoing field notes of the survey of the

South & North & re-survey of
~~South~~ West boundaries

Township No 2 S. *Range No* 12 W.

of the Salt Lake Meridian, Utah Territory,

Executed by F. C. Bailey

Under his *contract No* 102

of the 2 *day of* May *1881,*

in the month of Aug't. *1881,*

having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.

J. H. Salomons

U. S. Surveyor General for Utah.

BOOK-A-175

R: 1881 Survey of Township [illegible]

Filed Sept. 14. 1881.

Examined by John H. Compton & R. Gorlinski

Compared by E. Salomon & E. Michaelis

FIELD NOTES

OF and Re-Survey

THE SURVEY OF THE

West, North & East Boundaries

of Township No. 28 S. , Range No. 10 W.

of the Salt Lake Meridian in Utah Territory.

BY

T. C. Bailey

U. S. DEPUTY SURVEYOR,

Under his Contract No. 102

dated May 27th 1881.

Survey commenced July 27 1881

Survey completed " 28 1881

BOOK-A-175

3

Township 28. S. R. 10. W.



BOOK-A-175

Re-Survey

West boundary T. 28 S. R. 10 W.

On the night of July 26, 1881, I took an observation on the star Polaris, in accordance with instructions contained in the Manual of Surveys, and drove pickets on the line thus established. Survey commenced July 29, 1881, with a Burt's improved Solar Compass. Before commencing the survey, I took my compass on the line established last night and found it correct.

Note:

Having made search for the cor. to T. 29 & 28 S. R. 10 & 11 W, and also for

Re-Survey

53

West boundary T. 28 S. R. 20 W.

BOOK-A-

Chains		
	the old corners on the North boundary of this Tp, and being unable to find traces enough to fully identify any of them, I therefore find it necessary to Re-survey the West & North boundaries, and commence at the cor. to Tps. 28 & 29 S. R. 10 & 11 W, which is a charred cedar post in mound of earth, with pits, re-established by me yesterday, as view North on Re-Survey line bet. secs. 31 & 36, Var. 15° 30' E.	8 0.45
4.80	Road bears NW & SE.	
23.80	" " E & W,	
40.30	Find faint traces of old mound	

but no post, 45 links East of my line; I re-establish the cor, at the old mound by setting a Trachyte stone 24×14×4 in., 18 in. in the ground for ¼ Sec. cor. marked ¼ on W. side & dug pits 18×18×12 in., N.W.S. of stone 5½ ft. dist. & mixed mound of earth 1½ ft. high 5½ ft base alongside.

I now change my course to N. 0 1/2 E. and measure on bet. Secs. 31 & 36

8 0.45 Find faint trace of old corner mound when I set a Trachyte stone 20×12×8 in. 14 in in the ground for cor. to Secs. 25, 30, 31 & 36, marked 5 notches on N.E. & W. edges, dug pits

Re-Survey

West boundary of S. 28 S.R. 10 W.

Chains	18 x 18 x 12 in. ins each Sec. 5½ ft. dist, and raised Mound of earth 2 ft. high 4½ ft. base alongside. Land level— Soil 1st rate Ash timber.	
	——— " ———	
	North on Re Survey line bet. Secs. 25 & 30 Var. 15° 30' E.	
40.90	Found slight trace of old Mound Where I set a Trachyte stone 15 x 6 x 4 in. 10 ins. in the ground for ¼ Sec. cor. Marked ¼ on N. side, dug pits 18 x 18 x 12 ins. N & S of Stone 5½ ft dist, & raised Mound of	

BOOK-A

S. L.

Chains Ea

bra

79.40 Re

81.80 Fo

br

Fr

18

to

4

E

1

2

3

0

BOOK-A-175

	Earth 1½ ft. high 3½ ft base alongside.
19.40	Road bears NW & SE.
21.80	Faint trace of old mound but no post, when dec'd Trachyte lime 24 x 8 x 6 in. 18 in. in the ground for cor. to Secs. 19. 24. 25 & 30. Marked 4 notches on E. & W. on S. Edges, dug pits 18 x 18 x 12 in. in each Sec, 5½ ft. distant raised mound of earth 2 ft. high 4½ ft. base alongside.
	Land level—
	Soil 1st rate.
	No timber.

Re-Survey.

West boundary T. 28 S., R. 12 W.

Chains	
	N. 0.14' E. on Re-survey line bet. Secs. 19 & 24 Var. 15° 30' E.,
28.00	Near N.W. corner of Bingham House in the settlement of "Horse Shoe Bend" - Road passes N&S in front of the house, most of which are several houses.
30.00	S.W. corner of stable and corral.
31.00	Road bears NE & SW.
37.00	Beaver River runs NW. 75 links
40.00	to tree of ocd cor. Set a Trachyte stone 20x12x6 in., 14 in. in the ground for 1/4 sec. cor. Marked 1/4 on W. side & dug pits 18x18x12 in., N.& of stone 5½ ft. dist. & mound of earth 1½ ft. high

S. 6 W. 12 W. S. L. M.

N. 89° 56' E. on true line
bet. Secs. 2 & 35
Var. 15° 50' E.
3.00 Road bears N. & S.
10.00 Set Limestone 14 x 12 x 8 ins.
-0
-3
mks. on the ground for ¼ sec. cor. marked ¼
on N. side, & mound of stones along
side
12.25 Road nr. hollow S.W.
9.00 Set Sandstone stone 16 x 10 x
4 ins. above ground for cor. to secs. 1, 2, 35 & 36
marked 1 notch on E. & 5
on N. Edges, & mound of stone along side,
from which
A cedar 5 in. dia. bears N. 50 E. 30 lks.
marked T. 26 S. R. 12 W. S. 36. B. T.

Fork Township T. 24 S. R. 12

Chains

Acedar 5 ins. dia. brs. S 80 W. 40 lks
Marked T. 24 S. R 12 W. S. 2. B. T. 50.00
Land mostly level.
Sold 1st Sale.
At timber.
Dense sage brush on so chs

"

N. 89° 30' E. on true line
Ref. Rec. 1736
Var. 15° 30' E.

Acres.

40.00 In Sodon drains S W. set
a Granite stone 14 x 8 x 6
ins. in the ground for
1/4 sec. cor. Marked 1/4
on N. side & mixed a
mound of stones along
side, from which
Acedar 12 ins. dia brs. N 40° E. 50 l

BOOK-A-175

Marked W. S. B. T.
Top of mountains discovered
Robbed bears N. & S. in hollow.
The corner to T. 26 & 27 S.
R. 11 & 12 W. described at
the beginning of the random
line.
Land mountainous
Soil 2d rate.
Scattering cedars.
Aug. 9th 1881.

"

General Description
The lands in this Tp. are
generally 2d rate. The town
of Carbonate is situated
near the west boundary.
The Tp. can be subdivided.

T. C. Bailey
U. S. Dep. Surv.

BOOK-A-175

[4.—LIST OF NAMES.]

A list of the names of the individuals employed by Thomas C. Bailey *United States deputy surveyer, to assist in running, measuring, and marking the lines and corners described in the foregoing field notes of the survey of* Meridian, Standard, Townships and Subdivision lines *under contract No. 102, dated* May 27th, 1881 as returned up to date; situated South and west *of the Salt Lake base and meridian in the Territory of Utah, showing the respective capacities in which they acted.*

Frank Garlinski, Compassman.
William Forsyth, Chainman.
George W. Gardner, Chainman.
Adolph Meisel, Chainman.
George Burk, Chainman.
Oliver Hellstrand, Axeman.
James Christiansen, Axeman.
Charles Edwards, Flagman.
Richard T. Higbee Axmen.

BOOK-A-175 48

[5.—FINAL OATHS OF ASSISTANTS.]

48

We hereby certify that we assisted Thomas C. Bailey United States deputy surveyor, in surveying all those parts or portions of the Meridian, Standard, township, & subdivision lines under Contract No. 102, dated May 27th 1881, as returned up to date, situated South & West of the Salt Lake base and meridian in the Territory of Utah, as are represented in the foregoing field notes as having been surveyed by him and under his direction; and that said survey has been in all respects, to the best of our knowledge and belief, well and faithfully surveyed, and the corner monuments established according to the instructions furnished by the United States surveyor-general for Utah.

Frank Gorlinski, Compassman.
William Forsyth, Chainman.
Geo W Gardner, Chainman.
Adolph Meisel, Chainman.
George Brock, Chainman.
Oliver his x Helebrant, Axeman.
Peter his x Christensen, Axeman.
Charles D Edwards, Flagman.
Richard J. Higbee, Axeman.

Test: Frank Gorlinski

Subscribed and sworn to before me this 9th day of Nov, 1881,

Thomas C. Bailey
U. S. Dept. Sur.

BOOK-A-175

10 W. S. L. M.

3½ ft. base alongside.
80.00 At this point I find no
trace of old corner, but
find some pieces of cedar
fence stakes stuck in the
ground but no marks
upon them—I set a
charred cedar post 4 ft. long
4 in. square 12 in. in the
ground for cor. to Secs. 13.18
19 & 24, marked
T. 28 S. S. 18 on E.
R. 10 W. S. 19 on SE.
S. 24 on SW. and
S. 13 on NW. faces with 3
notches on NE & edges, dug
pits 18 × 18 × 12 in. in each
section 5½ ft. dist. & raised
mound of earth 2 ft. high
4½ ft. base alongside post.

Re-Survey 1859

West Boundary T. 28 S. R 10 W.

Chains		
	Land level	
	Soil 1st rate	
	No Timber	
	"	
	N 0° 15' E. on Re-Survey line	
	Set. Sec. 13 & 18.	
	Var. 15° 30' E.	
3.05	Beaver River (bend) runs SW.	
	Thence in River to	
4.50	River head to East, leave it.	
34.10	Road bears NE & SW.	
40.00	At Stone of old cor. Set a	
	Trachyte Stone 15 x 12 x 10 in.	
	10 in. in the ground for W 1/4	
	Sec. cor. Marked W 1/4 on S.	
	side; dug pits 18 x 18 x 12 in.	
	W of Stone 5 1/2 ft. dist.,	
	& raised Mound of Earth	

BOOK-

BOOK-A-175

U. L. L. M. Co

1½ ft. high 3½ ft. base along its sides

78.00 Ra. Utah central Rail Road track bears E ver.

80.00 Find trace of old Mound, then I set a Trachyte Stone 15 x 9 x 6 in. ins. in the ground for cor. to secs. 7, 12, 13 & 18. Marked 2 Notches on N & W S. Edges, dug pits 18 x 18 x 12 in. in each sec. 5½ ft. dist. & raised Mound of earth 2 ft. high 4½ ft. base alongside. Land level—
Soil 1st rate,
No Timber.

Re-Survey

West boundary T. 28 S. R. 10 W.

BOOK S. 2

Chains	
	At 0.17 E. on Re-survey line bet. secs. 7 & 12 Var. 15° 30' E.
40.50	Found slight trace of old mound and the Post lying loose on the ground nearby covered up — Set a Trachyte 15 x 9 x 8 ins. 10 ins. in the ground for 1/4 Sec. Cor. Marked 1/4 on N. side & dug pits 18 x 18 x 12 in. 4 lbs of stone 5 1/2 ft. dist. & raised mound of earth 1 1/2 ft. high 3 1/2 ft. base alongside.
41.00	Road bears E & W.
80.69	Found trace of old mound — Set a Trachyte stone 15 x 10 x 9 ins. 10 ins. in the ground for Cor. to secs. 1. 6. 7 & 12, Marked 1 Pits

S. 2 4

40.24

Chains on N. & S. on S. Edges; dug pits 18×18×12 in. in each Sec. 5½ ft. distt. & mound of earth 2 ft. high 4½ ft. base alongside.
Land level.
Soil 1st rate.
No Timber.
Milford is situated 1 mile East in Secs. 5. 6. 7 & 8.
"

N. 0.14 E. on Re-survey line bet. Secs. 1 & 6,
Dan 15.30 E
S. 2 4 Road to Frisco bears NW.
40.2 4 Find ~~Iron~~ Remains of old chopped
¼ cor. & post lying line
Same distance away — Inset Stone 12 in. deep in old Mound, for ¼ Sec. cor.

Re-Survey

West boundary T. 28 S. R. 10 W.

BOOK S. X

chains	Marked 1/4 S. on W. side, dug pits 18 x 18 x 12 in. N.E. of post 5 1/2 ft. dist. & raised mound of earth 2 ft. high, 3 1/2 ft. base along side.	chains
80	50	Here I find the old post lying about 100 links N.W. & a faint trace of the old mound. I re-set the same with the old mound 12 in. in the ground, for cor. to T. 29 & 28 S. R. 10 & 11 W. properly marked, dug pits 24 x 18 x 12 in N.E. S. & W. lying in a line, 6 feet distant, & raised mound of earth 2 1/2 ft. high 5 1/2 ft. base around post.	(Note)
		Land level,	15.00
			20.30
			23.00
			29.00

S. L. Mc 64

chains Sold 1st rate,
No timber.

" "

Note: In order to fully identify the corner on the North boundary I found it necessary to retrace the same,

" "

From the cor. to S. 24 & 25 S.,
R. 10 & 11 W. I run
East on Re-survey line
bet. Secs. 6 & 31
Var. 15° 30' E.

15.00 Ridge bears N. S.
20.30 Edge of Bench, Descend
23.00 East of "
29.00 Road to "Rocky" A. M.

Re-Survey 1854

North Boundary T. 28 S. R 10

BOOK-

R. 10. W

40.34 Found old corner nearly obliterated— set charred cedar post 3 ft. long, 3 in. square, 12 in. in the ground for 1/4 sec. cor. marked 1/4 S. on E. face, dug pits 18×18×12 in. Elm. of post 5½ ft. dist. Raised mound of earth 2 ft. high 3½ ft. base around the post.

Chains

40.32

80.60 Found trace of old mound, & the old charred cedar post lying 100 links west; set the same in the old hole 12 in. in the ground for cor. to secs. 5. 6. 31 & 32, properly marked, dug pits 18×18×12 ins. in each sec. 5½ ft. dist. Raised mound of earth 2 ft. high 4 ft. Base around post.

BOOK-A-175

R. 10. W. S. L. M.

Chains

Sand Rolling
Soil 1st rate
No timber.

———"———

East on Re-survey line
bet. Secs. 5 & 32
Var. 15° E.

40.32 Find base of old mound
and stone lying same
50 links N. Set same
in old mound viz:
"Sand Stone 6 x 8 x 5 ins, 10 ins
in the ground for 1/4 sec.
cor. marked 1/4 on S.
side, and dug pits
18 x 18 x 12 ins. E & W. of
same 5 ft. dist. & A
raised mound of earth

Re-Survey

North Boundary T. 28 S., R. 2

Chains	1½ feet high 3½ ft. base alongside.	
45.00	Utah Central R. Road bears N. W.	
54.20	Road bears N. W.	
55.21	Fence bears " " Inter field and meadow bottom	
66.50	Marsh bears N. W.	
70.50	Leave Same " "	
80.33	Old cor. mound on line; the old cedar post & found. Lying 12 lks N.E.	2.40
	which I mark in the old mound 12 in. in the ground	3.00
	for cor. to secs. 4, 5, 32 & 33, properly marked, dug pits 18 x 18 x 12 ins. in each	4.30
	section, 5½ ft. dist. & raised mound of earth 2 ft. high & 7½ ft. base	11.09
		29.10
		40.17

BOOK-A-175

10 M. S. L. Sec. 65

Ammd post.
Land level
Soil 1st rate.
No timber.

East on Re-survey line
bet. Secs. 4 & 33.
Var. 15° 30' E.

2.40 Beaver River 40 links wide
runs N.

3.00 Leave field & Meadow &
cross fence bears W.S.

4.30 Slough 100 lks wide bears
N.W.

11.09 Road bears S.E. & N.W.

29.10 Saree River bottom under
brush bears W.S.

40.17 To base of old cor.

Re-Survey 62

North Boundary T. 28 S. R. 10 W.

Chains Set Stone 16×8×6 in. 11 in. in the ground for 1/4 sec. cor. Marked 1/4 on N. side; dug pits 18×18×12 in. E & W. of stone 5 1/2 ft. dist, & raised a mound of earth 1 1/2 ft high 3 1/2 ft. base alongside.

80.35 Found old mound & the old charred cedar post lying 10 links N. & re-set stake in the old mound, 12 in. the ground for cor. to Sec. 3. 4. 33 & 34, properly marked, dug pits 18×18×12 in. in each section 5 1/2 ft. dist, & raised a mound of earth 2 ft. high 4 1/2 ft. base around post. Sand River Bottom & 40.30

BOOK-A-175

10.11. S.L.M.

Beech-
Soil 1st rate.
No timber.

East on Re-survey line
bet. Secs. 3 & 34
Var. 15° 30' E.

40.30 Find slight Trace of
old Mound, & charred
charred cedar post
lying N. & S. on the line
the same in charred
Mound 12 in. in the ground
Marked 1/4 S. on N. side,
for 1/4 sec. cor. dug pits
18 x 18 x 12 in., E & W. of
post 8 ft. dist. & raised
Mound of earth 1 ft

Re-Survey

North Boundary T. 2 S. R. 1 W. 71

BOOK-A

101

Chains high, 3 1/2 ft. base armed th
post.

17.00 Leave Lower Bench & Accen

80.30 Old Corner Mound on
line; I find the old chamo
cedar post lying 15 links
N.W. I re-set Same in
the old Mound 1 link in
the ground for cor. to sec.
2. 3. 34 & 35. Property Marke
Aug Pits 18 x 18 x 12 in. in
Each Sec. 5 1/2 ft. dist. &
raised Mound of earth
2 ft. high 4 1/2 ft. base
armed post.
Land Bench—
Soil 1st rate.
Timber

3400

(End of Re-survey)
July 25th 1881.

BOOK-A-175

July 28, 1881

Bro:

I leave the north boundary line for the present, and go to the cor. to T. 28 & 29 S. R. 9 & 10 W, (which was set two days since, & therefore I deem it useless to repeat the description here) and run

North bet. Secs. 31 & 36

Var. 15 30' E.

Descend

3400 on the Gp. cor. is difficult of access; for convenience of the future explorer, at this point I set a Granite 20x10x6 ins 18 ins. in the ground

East boundary 73 T. 28 S. R 10

Chains		Chains
	for Witness cor. to T. 28 & 29 S. R. 9 & 10 W. Marked 6 notches on N. E. S. W. Edges, with the letters W. C. & mixed a mound of stones alongside.	
37.00	Small drains west	
40.00	set Trachyte stone 16 x 10 x 6 in. 11 in. in the ground, for 1/4 sec. cor. Marked 1/4 on N. side & raised mound of stones alongside.	10.00
		28.00
		35.50
50.00	Ridge bears E & W.	40.00
58.70	" " " " "	
80.00	Set Mark a cross (X) on a Stationery Trachyte Rock 6 x 4 x 3 ft. above ground for cor. to secs. 25. 30. 31 & 36. Marked 5 notches on N & 1 on S. Edges, & raised a	

S. L. M 74

Chains	Mound of stone alongside.
	Land Mountainous
	Soil 2d rate.
	No timber
	" "
	North Var. Des. 25 W 30
	Var. 15° 30' E.
10.00	Foot of descent entering ravine.
28.00	Wash drains N.W.
35.50	" " "
40.00	Set Trachyte stone 15 x 10 x 5 in. 10 in. in the ground, for 1/4 Sec. cor. Marked 1/4 on N. side, & raised mound of stones alongside, from which
	A cedar 12 in. dia. bears West 55 lks, Marked 1/4 S B. T.

East Boundary T. 28 S. R. 10 W.

8.00	set Trachyte stone 20 x 8 x 6 in. 14 in. in the ground for cor. to secs. 19. 24. 25 & 30, Mkd 4 notches on N & E on S. Edges & raised mound of stones alongside, from which A Cedar 14 in. dia. bears S 70 W. 3 links Marked T. 28 S. R 10 W. S. 25 B. T.	40.00
	A Cedar 10 in. dia bears N. 29½° E. 32 lks Marked T. 28 S. R 9 W. S. 19 B. T.	8.00
	Land broken bench Soil 1st & 2d rate. Scattering cedar & pinon.	
	"	
	North bet. sec. 19 & 24 Var. 15°30' E.	
1.90	Wash draws N W.	
26.00	" " West.	

BOOK-A-175

L. R. 10 M. L. L. Mi.

40.00	Set Trachyte 18 x 12 x 5½ in. 12 in. in the ground for ¼ sec. cor. Marked ¼ on N. side, dug pits 18 x 18 x 12 in. N & S of stone 5½ ft. dist. & banked mound of earth 1½ ft. high 3½ ft base alongside.
8.00	Set Trachyte stone 24 x 12 x 8 ins. 18 in. in the ground for cor. to secs. 13, 18, 19 & 24 Marked 3 notches on N & S. Edges; dug pits 18 x 18 x 12 in. in each sec. 5½ ft. dist, & banked mound of Earth 2 ft. high, 4½ ft. base alongside.

East Omudan T. 28 S. R 10 W

Chains		Chains
	North bet. secs. 19 & 24 Var 15° 30' E.	
18,00	Road bears N & S.	
22,00	Broad wash drains N.	
40,00	Set charred cedar post 3 ft. long 3 in. square 1 in in the ground marked 1/4 S. on W. side, dug pits 18 x 18 in. N. & S. of post 5 1/2 ft dist, & raised mound of Earth 1 1/2 ft. high, 3 1/2 ft base around post.	10.00 17.50
63,00	Leave cedars N & S.	40.00
80,00	Set Trachyte 16 x 8 x 5 in. 11 ins. in the ground, for cor. to secs. 13, 18, 19 & 24, marked 3 notches on N & S Edges, dug pits 18 x 18 in. in each sec, 5 1/2 ft. dist, & raised a mound of Earth 2 ft	

BOOK-A-175

S. L. M.

chains high, 4½ ft. base along=
side.
Land broken.
Soil 1st rate.
Cedars on 63 chains.

〃 〃

North bet. secs. 13 & 18
Var. 15° 30' E.

10.00 Wash drains SW.
17.50 〃 〃 〃 Enter brush.
40.00 Set Trachyte 15 x 8 x 4 ins,
10 ins. in the ground for ¼
sec. cor. Marked ¼ on
N. side, dug pits 18 x 18 x
12 ins. Mds of stone 5½ ft.
dist & mound
of earth 1½ ft. high 3½
ft base alongside.

East Boundary T. 28 S. R 10 W

80.00 Set charred cedar post 4 ft. long 4 ins. square, 12 ins. in the ground for cor. to secs. 7, 12, 13 & 18. Marked T. 28 S. S. 7 on NE. R 9 W. S. 18 " S E. R 10 W. S. 13 " S W. and S 12 on N W. faces, with 2 notches on N & W sides. dug pits 18 x 18 x 12 ins. in each sec. 5½ ft. dist. mound of earth 2 ft. high 4½ ft. base around post. Land rolling brush. Soil 1st rate. No timber Dense Artimesia brush on 62.50 chs.

1,90
2 60.00
40.00
80.00

BOOK-A-175

R 10 W S. L. M.

North bet. Secs. 7 & 12
Var. 15° 30' E.

1.90 Wash drains N. W.

2 600 " " " "

40.00 set Trachyte stone 18 x 12 x 6 ins. 12 in. in the ground for 1/4 sec. cor. marked 1/4 on N. side, dug pits 18 x 18 x 12 in. N & S of stone 5 1/2 ft. dist. & banked mound of earth 1 1/2 ft. high, 3 1/2 ft. base along side.

8.00 set Trachyte 24 x 12 x 8 in 18 in. in the ground, for cor. to Secs. 1. 6. 7 & 12, marked 1 notch on E. & 5 on S. Edges, dug pits 18 x 18 x 12 in. on each sec. 5 1/2 ft. dist. & banked mound of Earth

East boundary T 28 S R 10 W.

2 ft. high - 4½ ft. base alder
side.
Land rolling
Soil 1st rate
No timber.
Dense Arbutus & brush
on both sides.

North bet. Secs 1 & 6.
Var. 18°30' E.

1.75 Wash in hollow drains S.E.
22.00 Road bears S.E.
40.00 Set Quartzite stone 14 x 8 x 6
in. 10 in. in the ground
for ¼ sec. cor. Marked ¼
on N. side, dug pits 18 x
18 x 12 in. N & S of stone
5½ ft. dist. & mound

BOOK-A-175

10m S. L. M. &c

Chains Mound of earth 1½ ft high, 3½ ft. base along side.

$1.50 Bush Anchors N.

$0.00 set Trachyte 24×12×6 in. 18in. in the ground, for cor. to Tps. 29 & 28 S. R 9 & 10 W. Marked 6 notches on N. E. S. & W. edges, dug pits 24×18×12 in. length = nine on each line N. E. S & W of stone 6 ft. dist, & raised mound of earth 2½ ft. high, 5½ ft. base along side.

Land Rolling
Soil 1st rate.
No Timber—
Dense Artemisia bush on surface.

North boundary T. 28 S., R. 10 W.

83

chains

From the cor. to T. 29 & 28 S., R. 9 & 10 W., I run West on Random line and at one mile and 79 chains, I intersect the cor. to secs. 2, 3, 34 & 35, from which I run East on true line bet. secs. 2 & 35 - Var. 15° 30' E. in Brush

39.50 (Bearing tree distance), set Trachyte 20 x 10 x 6 in., 14 in. in the ground, for 1/4 sec. cor. marked 1/4 on N. side, dug pits 18 x 18 x 14 in., 6 cu. ft. of stone 5 k ft. dist. & raised mound of earth 1 1/2 ft. high 3 1/2 ft. base alongside.

79.00 Set

BOOK-A-175

10 N. S.L.M. 84

79.00 Set Trachyte 18x12x6 ins. 12 ins. in the ground for cor. to secs. 1, 2, 35 R6 marked 1 Notches east & on N. Edges, dug pits 18x18x12 ins. in each sec. 5 1/2 ft. dist, & raised a mound of earth 2 ft. high, 4 1/2 ft. base along side.

Land rolling,
Soil 1st rate.
No timber—
Some sage brush on hgts

"

East on true line
bet. secs. 1 & 36
Var. 15 30' E.

North boundary T. 28 S R. 10

Chains

40.00 East set Limestone 15 x 12 x 5 in. 10 in. in the ground, for 1/4 sec. cor. marked 1/4 on S. side & raised mound of stone alongside.

80.00 The cor. to Tps. 29 & 28 S. R. 9 & 10 W. set today & thereon the description of which I deem useless to repeat here.

Land rolling -
Soil 1st rate.
No timber
Dense sage brush on both sides.

11

BOOK-A-175

T. 10 N. R. 2 W. M.

General Description

One half of this Township lis already subdivided on the west, the balance can be also.

The township in Range 2 W. lies in the Granite Mountains.

July 28th 1881.

F. C. Bailey
U. S. Depy. Surv.

BOOK-A-175

87

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, Oct 7th 1887

The foregoing field notes of the survey of the and Re-survey

West, North & East Boundaries

of

Township No 28 S *Range No* 10 W.

of the Salt Lake Meridian, Utah Territory,

Executed by F. C. Bailey

Under his *contract No* 102

of the 2nd *day of* May 188/,

in the month of July 188/,

having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.

Fred. Salomon

U. S. Surveyor General for Utah.

BOOK-A-175
R: 1883

Filed *187 .*

Examined by J. H. Campfer & H. Gorlinske

Compared by E. Salomon & S. Nichales

FIELD NOTES

OF

THE SURVEY OF THE

and Re-Survey

North Boundary

of Township No. 28 S. , *Range No.* 11 W.

of the Salt Lake Meridian in Utah Territory.

BY

T. C. Bailey

U. S. DEPUTY SURVEYOR,

Under his Contract No. 102

dated May 2nd *187*8.

Survey commenced Aug 5, *187*8.

Survey completed " " *187*8.

BOOK-A-175

4

Township 28 S. **R.** 11 W.



BOX-A-175

Re-Survey 88

North boundary T. 28 S. R. 11 W.

Survey commenced Aug 5th 1884, with a Burt's improved Solar compass, which I have tested on the meridian & found correct.

From the corner to T. 27 & 28 S. R. 11 & 12 W, set by me on the 3d inst, viz: A Fir tree 36 x 12 x 6 in, properly marked, with pits & mound, bears East on a random line between T. 27 & 28 S R 11 W, and at 2½ links I make search for the old stone corner, and at 2.80 chs. East I find the old Grey sandstone properly marked for the cor. lying loose upon the ground, with no indications of having

Re-Survey
In the Boundary of T. 2 & 8 S.

or pits. At this stone
deemed to be out of plumb
I continue East on the
random line, searching
for the old corners at every
40. & 80. chs, of which I find
Saints trees now and then
but not sufficient to
enable me to fully iden-
tify the old corner points
and at 6 miles 2 chs. &
20 lks, I intersect the
East boundary of the
township 18 lks South of
the re-established post
corn to T. 2 & 3 S. R 10 E
W Ms set by me on this
survey —
From the above corner
I run

BOOK-A-1

BOOK-A-175

E. 11 M. S. Line.

Runs S. 89° 59' W. on a line
N- survey line
bet. Secs. 1 & 36
Var. 15° 30' E.

40.00 Find joint mound, and die cedar post lying down-
I m- set stone in ord
mound 12 in, in the ground
for 4 sides, cor. marked 1/4
S. on E. side, dug pits
18 x 18 x 12 in. E & W. of post
5 1/2 ft. dist, & mounds
mound of earth 1 1/2 ft.
high, 3 1/2 ft. base around
post.

55.29 Road bears NW & SE.

80.00 Find joint mound, but no post I
re-establish the corner by

Re-survey of
North Boundary No 28 S.R.11

Chains	Setting a Trachyte stone 18×6×4 ins, 12 ins in the ground for cor. to sec. 1, 25 & 36, Marked 1 notch on E, & 5 on N. Edges, dug pits 18×18×12 ins, in each sec, 5½ ft. dist, & raised a mound of earth 2 ft. high 4½ ft. base along sec. do.	
	Land level mostly, with a slight slope to the E.	
	Soil 1st rate.	
	No timber.	
	S. 89° 59' W. on re-survey line	
	Ref. Trees. as 935	
	Var. 15° 30' E.	

BOOK-A

M.	L.
2.00	St
22.50	T
28.00	Cr
38.00	La
40.00	A
	Sur
	3
	12
	Sec
	A
	12
	2a
	1
	m
	a
	a
5100	A
	D
	x
	fo

BOOK-A-175

W. L. M. 92

2.00 Slight ridge bears N.E.
22.50 Ranine draws S.E.
28.00 Utah Central R.R. bears N.W.
38.00 Low ridge bears S.E. & N.W.
40.00 A tree of old cor. I set a charred cedar post 3 feet long, 3 ins. square 12 ins. in the ground for 1/4 sec. cor. marked 1/4 S. on N. side, dug pits 18×18×12 ins. E. & W. of post, & raised mound of earth 1½ ft. high, 3½ ft. base around post; from which a house bears N. 84°20' E. about 5 chs. dist.
80.00 A tree of old cor. I set a Cedar stone 16×10×4 ins, 11 ins. in the ground for my established cor. to

Re-survey

93

North Lonsdale, T. 2 S. R 11 W.

chains Secs. 2. 3. 34 & 35, marked 2 notches on E, & 4 on N. Edges, dug pits 18×18×12 ins. in each Sec. 5½ ft. dist. & raised mound of earth 2 ft. high 4½ ft. base along side.

Land rolling beech & oak sandy, 2d rate, Ash timber.

"

S. 89° 59' W. on Re survey line bet. Secs. 3 & 34

Var. 15° 30' E.

25.5 Wash drains N.W.,

40.00 Trees of old mound, and old charred cedar post lying down, nearly covered

R 11 W. S. L. M. 94

over mth earth & brush.
In-set same in the
old mound, 12 in. in the
ground for re-established
1/4 sec. cor. marked 1/4 S.
on S. side; dug pits 18x
18x12 in, E & W. of post 5 1/2
ft. dist, & raised mound
of earth 1 1/2 ft. high 3 1/2 ft
base around post.

76.70 Wash drains N W.

80.00 cannot find old stone cor.
Re-establish same by
setting a Sandstone 15x6x6
ins. 10 ins. in the ground
for cor. to sec. 3. 4. 33 & 34,
Marked 3 notches on E & S
W. edges; dug pits 18x8x
12 in. in Each sec. 5 1/2 ft.
dist, & raised a mound

Re survey 1895

North boundary T. 28 S., R. 11 W.

Chains	of each 2 ft. high, 4½ feet base, alongside. Sand beach, slopes S.E. Soil 2d rate. No timber.	Chains
	"	
	S. 89° 57' W. on re-survey line bet. secs. 4 & 33 Var. 15° 30' E.	47.50
15.50	Wash drains N.W.	60.00
33.00	" " N.W.	62.70
40.00	I now find, that the old stone, mentioned on the road on line, lies close to the point now marked. Inset the same on line viz: A Gray Sandstone 16/12/4 ins, rais'd in the ground, for	70.00
		77.50
		80.00

BOOK-A-175

W. L. M. 26

	Chains	re-established ¼ Lee. cor. Marked ¼ on it. Side; dug pits 18×18×12 in. E & N. of stone 5 ½ ft. dist & raised a mound of earth 1½ ft. high 3½ ft base alongside.
		Note:
		End of old survey.
	47.50	Road bears NW & SE.
	60.00	On NW point of ridge.
	62.70	Gulch drains NE: heads 3 chs. to W. Ascend
	70.00	Top of low divide bears W.
	77.00	Descend
	80.00	On N. slope, set Stadyte 24×18×10 in. 18 in. in the ground for cor. to secs. 4. 5. 32 & 33, marked 4 notches on E & 2 on W. edges;

North boundary T. 28 S. R. 11 W.

Chains

raised a mound of stones alongside.

Land beech on 47.80 chs.

Bal broken - to 62nd mile.

No timber.

Dense sage brush on the N. 40 chs.

Chains
62.30
80.00

S 89° 9' W. on true line
Var. 15° 30' E.

3.00 Intersect.

31.05 Road to Shamrock bears N.

39.00 Wash drains N.

40.00 Set Trachyte 24 x 12 x 4 in. 18 in the ground, for 1/4 sec. cor. Marked 1/4 on N. side, & raised mound of stones

L. R. & W. R. R. Co. 28

Chains alongside.
62.30 Wash drains N.E.
80.00 Set Trachyte 16×14×6 in.
11 in. in the ground, for
Cor. to Secs. 5, 6, 31 & 32,
Marked 5 notches on E. &
1 on W. edges; dug pits
18×18×12 in. in each sec.
6½ ft. dist, & raised a
mound of earth 2 ft.
high, 4½ ft. broad along=
side.
Land sage brush flat.
Soil 1st rate.
No timber.
Dense sage brush on adobe.

"

BOOK-A-17

North boundary T. 28 S. R. 11 W.

1 Chains S. 89° 59' W. on the line bet. secs. 6 & 31, Var. 15° 30' E.,

30.00 Hackm drains N

40.00 set Stachyle 14 1/2 x 6 cm. mound, in the ground for sec. cor. Marked 1/4 on N side, dug pits 18 x 18 x N & S of stone 6 1/2 ft. dist. Raised mound of earth 1 1/2 ft. high 3 1/2 ft. base along side.

82.20 The established cor. to T. 29 & 28 S. R. 11 W. 2 M. set by me on the 3d inst. and thereon I think it useless to repeat here.

Land Sage flat,
Soil 1st rate,
No timber.

BOOK-A-175

T 8 S. R. 11 W. S. L. M.

Dense Daze timber on 82 rods.
Augt. 5 1881.

"

General Description

The eastern part of this township has been subdivided. The western part lies mostly in the mountains, but can be subdivided, as the mountains are generally rolling, and contain lead and silver.

F. M. Bailey
U. S. Dep. Surv.

BOOK-A-175

121

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, Oct 7th 1881

The foregoing field notes of the survey of the And Mc Survey

North Boundary

Township No 28 S. *Range No* 11 W

of the Salt Lake Meridian, Utah Territory,

Executed by P. C. Bailey

Under his *contract No* 162

of the 27 *day of* May 1881,

in the month of Aug. 1881,

having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.

Fred. Salmon

U. S. Surveyor General for Utah.

BOOK-A-175

8

R: 1881 [illegible]

Filed Sept. 7th. 1881.

Examined by J.H. Camp & R. Goslinski

Compared by E. Michaels & E. Salomon

FIELD NOTES

OF

THE SURVEY OF THE and Re-Survey

South, East & North boundaries

of Township No. 29 S., Range No. 10 W.

of the Salt Lake Meridian in Utah Territory.

BY

F. C. Bailey

U. S. DEPUTY SURVEYOR,

Under his Contract No. 102

dated May 24th 1881

Survey commenced July 23d 1881.

Survey completed " 26th 1881.

BOOK-A-175

9

Township 30 S. **R.** 9 W.



BOOK-A-175

South Boundary T. 29 S. R. 10 W.

Lines

Survey commenced July 25th 1881, by Burts improved solar compass, which I find in proper adjustment.

On 5 miles of this line have been surveyed some years since, thence from the cor. to T. 29 & 30 S. R. 9 & 10 W. set yesterday by myself, the discription of which I deem it useless to repeat here, I run West on random line bet. T 29 & 30 S. R. 10 W. and at 80 chs. I make search for the old cor, but not finding it, I continue West, searching

South

~~South~~ boundary T. 29 S. R. 10 W.

at every 40 & 80 chs, for the
old corners, none of which
I can find marked plain
enough for identification,
until I reach the west
boundary of the Township
when, at 5 miles, 78 chs
& 50 links, I intersect the
South of the cor. to T. 29
30 S. R 10 W. W. where I
find the old post lying
down, near the remains
of the old mound & pit
which I am satisfied is
the old original corner,
which I re-establish by
setting the old charred cedar post
4½ ft. long 4 in. square, 12
in the ground, properly
marked - dug new pits

Chains
5.00
40.00

BOOK-A-175

10 N. L. L. 9 W.

Chains 24×18×12 in. lengthwise on each line N. S. E & W. of Post 6 ft. dist. & raised Mound of earth 2½ ft high, 5 ft. base around post—

From this cor. I run East on Re-survey line bet. Secs. 6 & 31 Var. 15 45' E.

5.00 Trail bears N. & S.

40.00 Find faint Traces of old Mound & pits, and the old post lying some distance away, which I re-set 12 ins. in the ground for ¼ sec. cor. Marked ¼ S. on N. face, dug pits 18×18×4 ins E & W of post 5½ ft. dist, & raised Mound of earth 1½ feet high, 3½ ft. base around post.

Re-survey 105

South Boundary T. 29 S. R. 10. E

80.00 Found faint traces of old mound & pits & old post lying loose some distance north — which I re-set 12 in. in the ground for cor: to secs. 5, 6, 31 & 32. properly marked, dug, pits 18 x 18 x 12 in. in each sec. 5½ ft. dist. & raised mound of earth 2 ft. high 4½ ft. base around post.

Land level valley — soil 1st rate.

No timber.

40.00 Fd

63.6[illegible]

80.00

East on re-survey line bet. secs. 5 & 32

Var. 15° 45' E

40.00 Faid faint traces of old mound & pits & the ed charred cedar post lying upon the ground 5 cho. N. which I re-set in the old mound, 12 in. in the ground for 1/4 sec. cor. marked 1/4 S on N. side; dug pits 18×18 ×12 ins. E & W. of ~~Stone~~ Post 5 1/2 ft. dist. & raised mound of earth 1 1/2 ft. high 3 1/2 ft. base around post.

63.64 Trail bears N W & S E.

80.00 Faid faint traces of old mound & pits & old post nearly covered with Earth; I re-set same, ~~at~~ in the old mound 12 in. in the ground for cor. to secs 4, 5, 32 & 33, properly marked,

Re-Survey

South Boundary T. 29 S. R. 10 W.

Chains dug pits 18×18×12 ins. in Each section, 5½ ft. dist. & raised mound of earth 2 ft. high 4½ ft. base around post. Land level—
soil 1st rate.
No timber.

East on Re-Survey line bet. Secs. 4 & 33.
Var. 15° 35' E.

40.00 Find faint trace of old mound, and old charred cedar post lying in the brush some distance away, which I reset in old mound 12 ins. in the ground for 1/4 sec. cor. Marked 1/4 S.

BOOK-A-1

S. L.

Chains on

12
ft.
of
bas
80.00 Fa
old
ea
hal
12
12
old
ma
in
mo
bas
La

Chains on N. side; dug pits 18×18×12 ins. E & W. of post 5½ ft. dist, & raised mound of earth 1½ ft. high 3½ ft. base around post.

80.00 Find faint traces of old mound, & old charred cedar post lying near by half covered up, which I re-set in the old mound, 12 ins. deep, for cor. to Secs. 3, 4, 33 & 34, formerly marked, dug pits 18×18×12 ins in each sec. 5½ ft. dist & raised mound of Earth 2 ft. high 4½ ft. base, around post.
Land level.
Soil 1st rate.
No timber.

Re-Survey

South boundary T. 29 S. R. 10 W.

Chains	
	East on Re-survey line bet. Secs. 3 & 34 Var. 15° 30' E.
40.00	Found faint traces of old mound, and thereon charred cedar post lying in the brush near by which I re-set 12 in. deep in the old mound, marked 1/4 S. on N. side for 1/4 sec. cor. dug pits 18 x 18 x 12 in. E & W. of Post 5 ft. dist. & raised mound of earth 1½ ft. high, 3½ ft. base around the post.
66.70	Road to Milford bears NW & SE.
76.00	Beaver River (Dry) drains N.
80.00	Found faint traces of the

BOOK-A-175

Chains old mound, and old charred cedar post partly buried in the soil, which I reset in old mound, 1½ cu. in the mound for Cor. to secs. 2. 3. 34. & 35. properly marked; dug pits 18×18×12 ins. in each section, 5¼ ft. dist, & raised mound of earth 2 ft. high, 4¼ ft. base, around post.
Land level
soil 1st rate.
No timber.

East on Re-survey line
bet. secs. 2 & 35
Var. 15° 30' E.

Re-Survey—

South Boundary T. 36 S. R. 10 W

7.00 Road to Milford bears N.

15.00 Fort of Bench bears N.W. & S.E.

25.00 Ravine bears S.W.

40.00 Find faint traces of old mound & post lying on the ground in the brush, which I re-set 12 in deep in old mound, Marked 1/4 S. on E. side for 1/4 Sec. cor. dug pits 18×18×12 in. E. & W. of post 5½ ft. dist, & raised mound of Earth 1½ ft. high 8½ ft. base around post.

80.00 Find old corner stone thrown over, partly buried with earth & hidden by the brush, which I re-set viz: ~~A white sandstone 24×12×8~~ 2½ in. 10 ins. in the ground ~~Bearing~~ for Cor. to secs. 1. 2. 35 & 36, Marked 1 Notch on E. & S on N. Edge, dug pits 18×18×12 in. in

18.25
39.45

Each sec. 5½ ft. dist. & raised mound of earth 2 ft. high 4½ ft. base alng side.
Land mostly level.
Soil 1st rate.
No Timber.
(End of Re-survey)

According to the closing on the boundary line West, the bearing from the above cor. to the ¼ cor. is S. 89° 34' E. 78.90 chs. Therefor I run on that course

East. Decs. 1836

Var. 15° 30' E.

18.25 Road bears NW & SE. Enter brush.
39.45 (Deviding the Error) Set a Granite Rock 14 x 10 x 6 ins. 10 ins

South Boundary T. 29 S. R. 10 W.

in the ground for 1/4 sec. cor.
Marked 1/4 on N. side & Raised
a mound of Stone alongside.
73.90 Hazelen drains South
78.90 the Cor. to T. 29 & 30 S. R. 9 & 10 W.
Land rolling bench.
Soil 1st rate—
No timber—
Heavy brush on 6.75 chs.
July 28th 1881.

10 W. S

Claims

Note: B

0.00

40.00

6.00

8.00

BOOK-A-175

10 W. S. L. Mer.

Chains

East Boundary T. 29 S. R 10 W.

Note: By examination I find that the 1/4 sec. cor. bet. Secs. 19 & 24 bears north 2 1/2 miles, I therefore run a meridian line North, bet. Sec. 31 & 36.

Var. 15° 30' E.

0.00 In brush.

40.00 Set Blue Flint Stone 16 x 6 x 4 ins. in the ground for 1/4 sec. cor. Marked 1/4 on N. side for 1/4 sec. cor. & raised a mound of stones alongside,

61.00 Hollow Drains W.

80.00 Set Sandstone 16 x 6 x 4 in, ins. in the ground for cor. to Secs. 25, 30, 31 & 36. Marked 5 notches on N & W Sides, dug pits 18 x 18 x 12 ins. in each Sec. 5 1/2 ft. dist. & raised mound of earth 2 ft. high 4 1/2 ft. base alongside.

East Boundary T. 29 S. R. 15 E.

Land broken
soil 1st rate
Heavy Artemesia brush
on 8 chs.

North bet. secs. 20 & 30
Var. 15° 30' E.

12.00 Enter Rocky drains SW.
22.00 Leave " head SE.
24.25 Road bears N 60 W.
25.00 Lincoln town bears S 60 E
about 1 1/4 miles dist.
40.00 Enter foot hills & cedars -
Set Sandstone 15 x 8 x 5 in.
10 in. in the ground for 1/4
sec. cor. Marked 1/4 on W.
side, Aug pits 18 x 8 x 12 in.
W 8. of stone 5 1/2 ft. dist.

BOOK-A
10 W.
Chains
65.00
70.25
80.00

10 N. R. 2 W. 6th Pm.

Chains | Y raised mound of Earth 1½ ft. high, 3½ ft. base along side.

65.00 | Wash drains SW.

70.25 | " " "

80.00 | The old cor. seems to be destroyed. Set Sandstone 16 × 6 × 5½ in., 11 in. in the ground for re-established cor to secs. 19, 24, 25 & 30, Marked 4 notches on N. & S. Edges, drug pits 18 × 18 × 12 in., in each sec. 5½ ft. dist, & raised a mound of earth 2 ft. high 4½ ft. base alongside.
Land hilly
Soil 1st rate.
Cedars on 40 chs.

East Boundary T. 29 S. R 10 W.

Chains

North on Re-Survey line
bet. Secs. 19 & 24
Var. 15° 30' E.

10.00 Road bears N.E. & S.W.

29.50 " " " " " "

40.00 Found oak cor. standing Viz:
"A Blue Limestone 14 x 10 x 6 ins,
for 1/4 sec. cor. marked 1/4
on N. side & raised mound
of stones along side; Alder mks.

68.84 Present Road 50 links West.

81.00 Found oak cor. Viz: Limestone
14 x 12 x 10 ins. for cor. to Secs
13. 18. 19 & 24, marked 3 notches
on W. & S. Edges, with mound
of stone along side, from
which a spring bears S 20 E. 10 lks.
A spring & Stones bears S. 55° W.
about 50 lks.

11.00

50.00

BOOK-A
S. L.

Land broken—
soil 2d rate.
Timber Cedar.
(Leave Re-survey line)

North bet. Secs. 13 & 18.
Var. 15°30' E.
Mound Mountains

14.00 Set a Lava Rock 20×12×4in.,
14in. in the ground for 1/4
Sec. Cor. Marked 1/4 on N.
side ~~for 1/4 Sec. Cor.~~ and
raised mound of Stones
alongside.

8.00 S.P. a Limestone 18×6×4in.,
12in. in the ground for Cor.
to Secs. 7, 12, 13 & 18, and Raised
Var. Red 2 notches West 4 on S Edge
a Mound of Stones alongside
from which the Cor. mine

BOOK-A

East Boundary Twp 29 S. R 10 W. S. L.

chains

is situated about 60 chs. N.W. with house N.W. of mine about 20 chs. & adjoining in a gulch N.E. of the house. Land mountainous Soil 2d rate. Some scattering cedars. 80.00

North bet. decs. 7 & 12
Var. 15°30' E.

20.00 Ridge Pos bears S.W. & N.
40.00 set Limestone 15 x 10 x 5 ins.
10 ins. deep for ¼ sec. cor.
marked ¼ on W. side
Raised Mound of stones
alongside. 40.00
60.00 Bottom of Such drain on W.
Ascend—

BOOK-A-175

N. S. Line. 120

80.00 set Limestone 15 x 12 x 9 in. 10 in. in the ground for Cor. to secs. 1, 6, 7 & 12. Marked 1 notch on N & S on S. edges & raised mound of stone along side.

Land Mountainous.
Soil 2d rate.
A few cedar.
Indications of mineral.

North bet. secs. 1 & 6
Var. 15° 30' E.

40.00 set Limestone 15 x 10 x 5 in. 10 in. in the ground for 1/4 sec. cor. Marked 1/4 on N. side & raised mound of stones along side.

BOOK-A

80.00	On Top of Mountain Ridge bears E & W. Set Limestone 18 x 9 x 9 in. 12 in. in the ground for cor. to T.S.S. 28 & 29 S. R 9 & 10 W. Marked 6 notches on N. E. S & W. edges & raised mound of stone along side. Land Mountainous. Soil & rate Indications of Mineral— & few cedars.	Chains

BOOK-A-175

Chains

North Boundary T. 29 S. R. 10 W.

From the cor. to T. 28 & 29 S. R. 9 & 10 W. I run West on a random line setting temporary corners at 40 & 80 chs. and at 3 miles I search for the old cor. to secs. 3. 4. 33 & 34, and finding no trace of it, I continue West, to the 4th mile when I find faint trace of the the old corner 50 links south; at the 5th mile I also find faint trace of the original corner,

(Re-Survey).

North boundary T. 29 S. R. 10 W

25 links South, and at 6 miles I intersect at the corner to T. 28 & 29 S. R. 10 & 11 W. which is a charred cedar post lying down near the old mound - I re-set the same in the mound 11 in. in the ground, properly marked, dug new pits 24 x 18 x 12 in. lengthwise on each line N. E. S. & W. of Post 6 feet dist & raised mound of Earth 2½ ft. high 5 foot base around Post. 40.00

Judging from the fault traces of the old corners on or near the random 58.00 65.75

BOOK-A-175

line, that the old line bears 25 links south per mile, therefore I run

S. 89°50' E. on Re-Survey line bet. Secs. 6 & 31 / Var. 15°30' E.

40.00 Find slight remains of old mound - set a Trachyte stone 18 x 10 x 8 in., 12 in. in the ground for 1/4 sec. cor. marked 1/4 on N. side & dug pits 18 x 18 x 12 in. E & W. of ~~post~~ stone & raised mound of Earth 1 1/2 ft. high 3 1/2 ft. base along side.

58.00 Road bears N & S.

65.75 Irrigating ditch bears N E.

Re-Survey
North Boundary T. 29 S. R 10

BOOK-

		N.	S.
6	8.00 Old Road bears E & W.	5.00	
8	0.00 Find trace of old mound,		
	when I set a trachyte stone	23.70	
	24 x 12 x 10 in. 18 in. in the	37.34	
	ground for cor. to secs. 5, 6,	40.00	
	31 & 32. Marked 5 notches		
	on E & W on N. edges &		
	dug pits 18 x 18 x 12 in. in		
	each sec. 5 ft. dist. &		
	raised mound of earth		
	2 ft. high 4 ft. east base		
	alongside.		
	Land level Valley.		
	Soil 1st rate.		
	No timber.		
	July 25th 1881		
		42.10	
	July 26th 1881	71.70	
	S. 89° 50' E. on Re-Survey	80.00	
	line bet. secs. 5 & 32		

BOOK-A-175

5.00 Beaver River 75 links wide runs NE.

23.70 Ditch drains NE.

37.34 Road bears N & S.

40.00 Find faint trace of old corner mound - when I set Trachyte stone 20 x 8 x 8 in., 15 in. in the ground for 1/4 sec. cor. Marked 1/4 on N. side. Dug pits 18 x 18 x 12 in. E & W. of stone 3 1/2 feet distant, & raised a mound of earth 1 1/2 ft. high, 3 1/2 ft base along side.

42.10 Road N W & S E.

71.70 " " "

80.00 Find mounds of old mound & the post, lying

Re-survey

North boundary T. 29 S. R. 10 W.

	Chains
Chains in the brush nearly covered up — I meet the post, along side of a small Trachyte Stone, 12 li. in the ground for cor. to secs. 4, 5, 32 & 33. Properly marked, dug pits 18 x 18 x 12 in. in each section 5½ feet dist, & raised mound of Earth 2 ft. high 4½ ft. base around post & stone — the small stone is marked 4 notches on E. & 2 on W. edges.	40.00
Land level.	64.50
Soil 1st rate.	80.00
No timber	

S. L. M.

Chains

South 89°50' E. on Re-survey line, bet. Secs. 4 & 33.
Var. 15° 30' E.

4.00 Find remains of old corner, where I set Sandstone 18 x 6 x 3 in., 12 in. in the ground for 1/4 sec. cor. marked 1/4 on N. side; dug pits 18 x 18 x 12 in., Encr. of stone 5 1/2 ft. dist., & raised a mound of earth along side

6.50 Road bears N. & S.

80.00 Find remains of old mound, where I set a trachyte stone 15 x 8 x 6 in., 10 in. in the ground, for cor. to Secs. 3, 4, 33 & 34, marked 3 Notches on E & W. edges, dug pits

North boundary T. 29 S. R 10

Chains 18 x 18 x 12 in. in each sec. 5 l/2 ft. dist, & mixed a mound of earth 2 ft. high 4 l/2 ft base along side.
Land level—
Soil 1st rate.
No timber.
(End of Re-survey)

16.35
24.60
41.00

According to the bearing of the Random & retraced lines I am now 78 links south of the cor. to T. 28 & 29 S. R 9 & 10 W. therefore I run
N. 89° 50' E. on a true line bet. secs. 3 & 34

68.50
74.75
78.00
80.00

R 10 W. S. L. M.

Var. 15° 30' E.

In dense sage brush

16.35 Road bears N-S.

24.60 " " " " "

40.00 set Trachyte stone 8 x 10 x 8 in. 12 in. in the ground for 1/4 sec. cor. Marked 1/4 on N. side, dug pits 18 x 18 x 12 in. E. & W. of stone & raised mound of earth 1½ ft high 8½ ft. base alongside. Ds Ascend

68.50 Wash drains N. to S.

74.75 Wash drains " "

78.00 Road bears NE & SW.

80.00 set Trachyte 15 x 10 x 5 in. 10 in. in the ground, for cor. to sec. 2, 3, 34 & 35 Marked 2 notches on E.

North boundary T. 29 S. R

Y4 on N. Edges ~~for Cor~~
& raised mound of
stones alongside.
Land gently sloping N.
Soil 1st rate.
No timber

N. 89° 50' E. bet. Secs 2 & 35
Var. 15° 30' E. by Brush
Euler & calling cedars
33.97 Cedar tree 6 in. dia. on line
40.00 set Limestone 14 x 10 x 6 in.
10 in. in the ground for 1/4
Sec. Cor. Mar. Red 1/4 on N.
side & raised a mound
of stones alongside,
from which
A cedar 4 in. dia. bears S 40 W

45.00
67.00
80.00

W. M. S.L.M.

15 links dist. marked
¼ S.B.T.

45.00 small wash drains N.

67.00 " " "

Ascend mountains

80.00 set Trachyte 20×8×6 in.
14 in. in the ground, for
cor. to secs. 1. 2. 35 & 36.
Marked 1 Notch on E.
& 5 on W. Edges, from
which

A cedar 4 in. dia. bears S 65° W. 15 links
Marked T. 29 S. R 10 W. S. 2 B.T.

A cedar 12 in. dia. bears S. 70° E. 15 links,
Marked T. 29 S. R 10 W. S. 1 B.T.

A cedar 5 in. dia. bears N 60 E. 35 lks
Marked T. 28 S. R. 10 W. S 36. B. T.

A cedar 10 in. dia. bears N. 30° W. 125 lks
Marked T. 28 S. R 10 W. S. 35. B. T.

Land broken & rocky.

North boundary T. 29 S.

Chains Soil 2d rate.
Timber, cedars.

" "

N. 89° 50' E. on true line
bet. Secs. 1936
Var. 15° 30' E.
Found monument
4.00 set Limestone 15 x 10 x 5
iron. dep. for ¼ sec. co
marked ¼ on N. side
raised mound of stones
alongside.
8.00 The cor. to Townships 28
29 S. R. 9 & 10 W. which
is described before in
this book, and therefore
I deem it, tautology
to repeat it here.

BOOK-A-175

T. 10 N. R. 2 W.

Land Mensuration.

Soil 2nd rate - rocky.

Timber scattering cedar.

General Description

This township is partly subdivided - the balance can be also.

T 29 S. R. 9 W lies in the granite Range of mountains & cannot be subdivided without great labor & expense.

July 26th 1881.

F. C. Bailey
U. S. Deputy
Surveyor.

BOOK-A-175

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, Oct 9th 1881

The foregoing field notes of the survey of the & Re-survey

South, East & North boundaries of

Township No 2 S *Range No* 10 W.

of the Salt Lake Meridian, Utah Territory,

Executed by F. C. Bailey

Under his *contract No* 102

of the 29th *day of* May 1881

in the month of July 1881

having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.

Fred Salsbury

U. S. Surveyor General for Utah.

BOOK A 175

R: 1882

Filed 187 .

Examined by John H. Cowper, B. Gorlinski

Compared by E. Solomon, E. Michaelis

FIELD NOTES

OF

THE SURVEY OF THE and Re-Survey

North boundary

of Township No. 2 S , Range No. 11 W.

of the Salt Lake Meridian in Utah Territory.

BY

F. M. Bailey

U. S. DEPUTY SURVEYOR,

Under his Contract No. 102

dated May 2 1881.

Survey commenced Aug 2 1881

Survey completed " 10 " 1881

6

BOOK-A-175

Township 29 S. **R.** 11 W.

145 147 142 141 139 137

6	152 151 5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

BOOK-A-175 Re-Survey
36
North Boundary T. 29 S. R. 11 W.

Commenced Aug 2d 1881
by a Burts improved solar
compass, which being tested
on my meridian line I
find correct.

Note:

Having made
search for the corner to
T. 28 & 29 S. R. 11 & 12 W, and
being unable to find
it, I therefore find it
necessary to retrace
Either the Guide line
in T. 29 S. be. R. 11 & 12 W.
or the N. boundary of
T. 29 S. R. 11 W. in order
to find the said corner,
As only a portion of
the said North Boundary
of T. 29 S. R. 11 W. has been

Re-survey

North Boundary T.29 S. R.1 E. S. L.

37

chains established I decided
to retrace the portion
already run in 1870, and
complete the remainder
of the line West.

I begin at the established
corner to T.28 & 29 S. R 10 & 11
re-established by me on this
Survey Viz: A charred cedar
post 4 ft. long 4 ins. Square
run in the ground, properly
marked, with pits and
mound.

West on a ~~line~~ Re-survey line
bet. Secs. 1 & 36
Var. 15° 30' E.

40.24 Find & mark trace of old,
mound, and old Post
lying down; I re-set

S. L. Mc.

Mains Same in old mound, 12 ins in the ground for 1/4 Sec. cor. marked 1/4 S. on N. side, Chg. Pits 18 x 18 x 12 ins E & W. of post 5½ ft. dist. & raised mound of Earth 1½ ft. high 3½ ft. base around post.

C/S Said old corner post lying on the mound. Re-set Same in the mound 12 ins in the ground for cor. to Sec. 1, 2, 35 & 36, Chg. pits 18 x 18 x 12 ins. in each Sec, 5½ ft. dist. & raised a mound of earth 2 ft. high 4½ ft. base around post. Land level. Pine 1st rate. Timber.

Re-Survey.

North Meridian T. 29 S., R. 11 E.

chains	
	Met on re-survey line
Ck. Lees. 2 W 85
Var. 15° 30' E.
1.00	Rock drains N.
30.50	Road bears S.W & S. 6. Bellin
dog's house bears S. 25° W. abt.
2 chs. dist. Corral 4 chs,
S.E. of house; enter meadow d
40.26	Find fence & trees of pits, bu
no post. Re-establish the
cor. by setting a Trachyte
stone 15 x 15 x 6 ins. 10 ins in
the ground for 1/4 Sec. cor
marked 1/4 on E. side;
dug pits 18 x 18 x 12 in S.
W. of stone 6 1/2 feet di
& mixed mound of ea
1 1/2 ft. high, 3 1/2 ft. base
alongside.
67.75	Road bears NW & S.

S. L. M

30.48	Fen
Re-
reta
12 x
for
mar
4 m
18 x
feet
mon
4 1/2
Lan
desi
Sta
Sole
Spa
in
dre
of

BOOK-A-175

S. L. M. 140

0.48 Faint trace of old mound.
Re-establish the corner by
setting a Trachyte stone 15 x
12 x 10 ins. 10 ins. in the ground
for cor. to sections 2. 3. 34 & 35.
Marked 2 notches on E & S
4 on N. Edges, dug pits 18 x
18 x 12 ins. in each dec. 5 ½
feet distt. and raised a
mound of earth 2 ft. high,
4 ½ ft. base alongside.
Land level
soil 1st rate.
No timber.
Note: The sand and
spring branches mentioned
in the old notes are all
dried up at this season
of the year.

"

Re-survey

North Boundary T. 29 S. R. 11 W. S. L.

chains West on re-survey line
bet. Secs. 3 & 34
Var. 15° 30' E.

7.65 Road bears NW & SE.

17.00 Leave meadow, bears N & S.

40.10 Remains of old mound = I re-establish cor. by setting a Trachyte stone 15 x 10 x 4 in. 10 in. in the ground for 1/4 Sec. Cor. Marked 1/4 on N. side aug. hole 18 x 18 x 12 in. E & W. of stone 6 ft. dist, & raised a mound of Earth 1 1/2 ft. high, 3 1/2 ft. base alongside,

48.00 Ridge 10 ft. high, bears N & S,

50.15 Telegraph line bears NW & SE

61.20 Road bears NW & SE,

74.60 " " NE & SW.

80.20 Find remains of old corner with post lying down—

BOOK-A-175

R. 11 W. S. L. M. 143

I re-set the old charred cedar post in the mound 12 ft. in the ground for Cor. to secs. 3. 4. 33 & 34, properly marked; dug pits 18 & 18 ins. in each sec. 6 ft. dist. & raised mound of earth 2 ft. high 4 ft. base around post.

Land generally level—
Soil 1st rate—
Grassland & grass.
No Timber.

—— " ——

West on re-survey line
bet. secs. 4 & 33
Var. 15° 30' E.
Road bears N & S.

Re-survey

North boundary T. 29 S., R. 11 W.

12.50	A small ridge bears N. & S.
13.00	Road bears N.W. & S.E.
15.00	Old remains of Trny Sweet twig marks bears S. 75° W. at 10 chs. dist.
24.50	Road bears N.W. & S.E.
26.50	" " N. & S.
31.00	" " N.W. & S.E.
37.00	" " " " "
40.28	Find faint trace of old mound; the old charred cedar post lying 30 links north — I re-set same in the old mound, 12 ins. in the ground for 1/4 sec. cor. marked 1/4 S on N. side, dug pits 18 x 18 x 12 ins. E. & W. of post 5 1/2 ft. dist, & raised mound of earth 1 1/2 ft. high 3 1/2 ft. base

BOOK-A-

Chains	Al
60.28	N
72.00	N
80.59	Fa
	&
	by
	Ir
	by
	15
	Gr
	4.
	by
	24
	Edg
	ru
	&
	2f
	Ra
	La
	par

BOOK-A-175

W. S. L. Mine

Drains also around post.
60.28 Ascend gradually
72.00 Bush drains N.E.
80.89 Faint trace of old mound
& find the old post
lying 100 links north=
Re-establish the cor.
by setting a Trachyte stone
15 x 12 x 8 in. 10 in. in the
ground for cor. to sec. 4.
4.5.32 & 33. (& set the post
by side of the stone) - marked
2 notches on E & W on west
edges, dug pits 18 x 18 x 12 in.
in each sec. 5 ft. dist,
& raised mound of earth
2 ft. high 4 ft. base, along
side.
Land east part level; West
part sloping east.

North boundary T. 29 S., R. 11 E.

1454

chains Soil 2d rate.
No timber.
(End of mile survey)
"

I now run West on a
blank line, bet. secs.
5 & 32, 6 & 31, and at 1 mile
79. chs & 80 links, after diligent
search, I found charcoal cor,
stone, nearly covered over,
but standing N.E. Red
sandstone 15 x 7 x 7 ins, (formerly marked)
which I add a mound
of stone alongside & run
East on a true line
bet. secs. 6 & 31
Var. 15° 30' E.
Descend S.E. Slope
33.00 Foot of slope, Road bears to S.

34.00 Se
10,
1/4
On
18
5/4
Mo
3/2
71.50 R
79.80 Se
Upo
to
5 m
Ch
die
Mo
4/4
La
Ba
Mo

BOOK-A-175

W. S. L. M. '46

39.80 Set a Trachyte 15 x 10 x 5 in, 10 ins. in the ground for 1/4 sec. cor. marked 1/4 on N. side, drs pits 18 x 18 x 12 in. E & W. of stone 5 1/2 ft. dist, & raised a mound of earth 1 1/2 ft. high, 3 1/2 ft. base alongside.

72.50 Road bears N.W. & S.E.

79.80 Set Limestone 16 x 6 x 6 in. 11 in. in the ground for cor. to secs. 5. 6. 31 & 32, marked 5 notches on E. & 1 on W. edges. drs pits 18 x 18 x 12 in, in each section 6 1/2 ft. dist, & raised mound of earth 2 ft. high 4 1/2 ft. base alongside. Land W. to Chr. Mountainous Bal= East slope, covered with sage brush.

North boundary T. 29 S. R

Soil Dale.
to timber.

East on this line
bet. secs. 5 & 32
Dan. 15 30' E.

11.00 Nash drains SE.

40.00 set Flint stone 18 x 8 x
4 in, 10 ins. in the ground
for N sec. cor. marked I X
on N. side; dug pits 18
18 x 12 in, Cor. of stone
5/2 feet dist. & dug pit
1/2 ft. high, 3/2 ft. base
alongside

4.50 Nash drains SE,

80.00 the corner to secs. 4. 5.
32 & 33. which I set this

BOOK-A-175

day, and therefore deem
it useless to repeat
the description here.
Land sloping East.
Soil 2d rate.
Timber.
Vegetation on same.
Aug. 2 1881.

11

General Description

This township has all been subdivided except part of Secs. 5 & 6. It now contains several settlers.

F. C. Bailey
U. S. Dep. Surv.

BOOK-A-175

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, Oct 9th *188*1

The foregoing field notes of the survey and Resurvey of the

North Boundary

Township No 2 S *Range No* 1 W.

of the Salt Lake Meridian, Utah Territory,

Executed by J. C. Bailey

Under his contract No 102

of the 2 *day of* May *188*1,

in the month of Aug. *188*1,

having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.

Fred. Salsbury

U. S. Surveyor General for Utah.

BOOK-A-175

R: 1882

Filed Sept. 9th. 1881.

Examined by John H. Kemper & R. Gerlinsky

Compared by L. Salomon & C. Michaelis

FIELD NOTES

OF

THE SURVEY OF THE

6th Standard Parallel South

between

Township No. 30 & 31 S. Ranges No. 7. & 21 W.

of the Salt Lake Meridian in Utah Territory.

BY

F. C. Bailey

U. S. DEPUTY SURVEYOR,

Under his Contract No. 102

dated May 2nd 1881.

Survey commenced July 14th 1881.

Survey completed " 16th 1881.

Subdivision of T. 29 S. R. 11 W.

Note: As all of this township is surveyed except a portion of secs 5 & 6, I deem it advisable while I am on the ground running the north boundary to finish up the survey of said sections, therefore I begin Aug 2d 1881, at the cor. to secs. 5. 6, 31 & 32. on the North boundary viz: A Limestone 16 x 6 x 6 in, marked 5 notches on E & W sides, with pits & mound, set by me today, and run South on a random line bet. secs. 5 & 6 Var 15° 30' E.

Additional Subdivisions of T. 29 S. R 15 E

Chains

40.00 Cannot find old cor. & set temp. 1/4 sec. cor.

81.98 Find remains of old mound & old charred cedar post lying down = on line. R = set same in old mound, 1 link in the mound for cor. to secs. 5. 6. 7 & 8, properly marked, dug pits 18 x 18 x 12 ins. in Each sect, 5½ ft. dist, & raised mound of earth 2 ft. high 4½ ft. base around the post. Thence North on a true line between secs. 5 & 6 Var 15° 30' E

8.50 Wash drains S.E.

40.00 Find the old stone thrown over, partly covered up. I R = set same viz: A Blue

BOOK-A-175

R 1 W. T 3 S. L. M.

Limestone 24×12×6 in., 18 in.
in the ground for 1/4 sec.
cor marked 1/4 on W. side,
Dug pits 18×18×12 in, N & S
of stone, & raised a
mound of earth 1½ ft.
high 3½ ft. base alongside.
81.98 To the cor. to secs. 5. 6. 31 & 32
Land nearly level
soil 2d rate -
Sage brush on 80 chs.
Aug 2d 1881.

"

General Description
is given in the notes
of the survey of the
North boundary.

T. C. Bailey
U. S. Dep. Surv.

BOOK-A-175

R: 1882

Filed Sept. 9th. 1881.

Examined by John H. Kemper & R. Gerlinsky

Compared by L. Salomon & C. Michaelis

FIELD NOTES

OF

THE SURVEY OF THE

6th Standard Parallel South

between

Township No. 30 & 31 S. Ranges No. 7. & 21 W.

of the Salt Lake Meridian in Utah Territory.

BY

F. C. Bailey

U. S. DEPUTY SURVEYOR,

Under his Contract No. 102

dated May 2nd 1881.

Survey commenced July 14th 1881.

Survey completed " 16th 1881.

BOOK-A-175

7

Township 30. S. **R.** 7. W.



BOOK-A-175

8

Township 30 S. **R.** 8 W



BOOK-A-175

9

Township 30 S. **R.** 9 W.



BOOK-A-175

10

Township 30 S. **R.** 10 W.



BOOK-A-175

11

Township 31. S. **R.** 8. E.



BOOK-A-175

12

Township 31 S. **R.** 9 W.



13

BOOK-A-175

Township 31 S. R. 10 W.



Names and duties of Assistan

"

Frank Gorlinsk. Compassman
William Forsyth, Chainman
George W. Gardner, "
Adolph Meisel "
George Burk "
Olivier Helebrant Axeman
James Christensen "
Charles A. Edwards " & Flagman
Richard R. Higbee " "

BOOK-A-175

[1.—PRELIMINARY OATH OF COMPASSMAN.]

I, Frank Gorlinski '56

do solemly swear that I will well and truly perform the duties of compassman, according to instructions given me, and to the best of my skill and ability, in the survey ~~of the~~ Meridian, Base, Standard, Guide meridian, township, subdivision & lines under contract No 102 dated May 2nd 1888 with J. C. Bailey U. S. Dept. Surveyor lying South, and West

of the Salt Lake base and meridian in the Territory of Utah.

Frank Gorlinski

Compassman.

Subscribed and sworn to before me this 14th day of July 1888

F. Constance O'Connor

Notary Public

[2.—PRELIMINARY OATH OF CHAINMEN.]

We, William Forsyth, George W. Gardner 157
and Adolph Meisel, George Burk
do solemnly swear that we will well and faithfully execute the duties of chain carriers; that we will level the chain upon even and uneven ground and plumb the tally pins, either by sticking or dropping the same; that we will report the true distance to all notable objects, and the true length of all lines that we assist in measuring, to the best of our skill and ability, and in accordance with instructions given us, in the survey ~~of the~~ under contract No. 102, dated May 27th 1881 with J. C. Bailey U.S. Dept. Surveyor of the Meridian, Base, Standard, Guide Meridian, Township Subdivision lines, lying South and West of the Salt Lake base and meridian in the Territory of Utah.

William Forsyth Chainman.
George W. Gardner Chainman.
Adolph Meisel Chainman.
George Burk Chainman.

Subscribed and sworn to before me this 14th day of July 1881

F. M. Lutesinger
Notary Public

[3.—PRELIMINARY OATH OF AXEMEN.]

1538

We, Oliver Helebrandt

and James Christensen

do solemnly swear that we will well and truly perform the duties of axemen, in the establishment of corners and other duties, according to instructions given us, and to the best of our skill and ability, in the survey ~~of~~ under contract No. 102 dated May 27th 1881 with J. C. Bailey U. S. Deputy Surveyor of the Meridian Base Standard & Guide Meridian Townships & Subdivision Lines, lying South and West

of the Salt Lake base and meridian in the Territory of Utah.

Witness: his
Oliver x Helebrandt, Axeman.
mark
Frank Gorlicki, James Christensen, Axeman.

Subscribed and sworn to before me this 14th day of July 1881

F. Whiteside-Clawson
Notary Public

[3.—PRELIMINARY OATH OF AXEMEN.]

We, Charles A. Edwards 159
and Richard J. Higbee
do solemly swear that we will well and truly perform the duties of axemen, in the establishment of corners and other duties, according to instructions given us, and to the best of our skill and ability, in the survey ~~of~~ under contract No. 162, dated May 27th 1881 with J. C. Bailey, U. S. Deputy Surveyor, of the Meridian Base, Standard ~~and~~ Guide Meridian lines, lying South and West

of the Salt Lake base and meridian in the Territory of Utah.

Charles A. Edwards, Axeman.

Richard J. Higbee, Axeman.

Subscribed and sworn to before me this 14th day of July 1881

F. Whiteside-O'Connor
Notary Public

BOOK-A-175

Re-Survey of the Sixth Standard Parallel South

Range 7 West, Salt Lake Mer.

On the night of July 15th 1881 I took an observation on the star Polaris, in accordance with instructions contained in the Manual of Surveys, and drew sketches on the line, thus established

Survey commenced July 16th 1881, with a Burt's improved Solar Compass.

Before commencing this survey I tested my compass on the line established last night, and found it correct, Giving latitude 38° 10' N. for this line.

Being unable to find and identify any of the

Re-Survey of the 6th Standard Parallel South

Chains Old corners in this range,
I thereon begin at the Stand.
and Corner to Tps 30 & 31 Ranges
6 & 7 W. which is a Grey
Sandstone, 24 x 12 x 8 ins. Mar[ked]
6 notches on N. & W. Edges, &
from which
A cedar 12 ins. dia. bears N. 63¼° E. 175 lks.
" " 6 " " " S. 58¾° E. 180 "
A nut Pine 6 " " " N. 73¾° W. 307 "
Thence I run
West on a re-survey line
on the South side of Sec. 36.
Var. 15° 30' E.
6.00 Foot of bluff bears N. & W.
17.50 Dry Bed drains S.W.
18.00 Foot of bluff bears S.W. & N.
40.00 Find Old Corner Stone lying
down, which is a Grey Sand
Stone 20 x 15 x 10 ins. which I re-

Chains set
I re
from
& ce
" Pi
Mar
80.00 Gre
Five
as
re-s
from
5,00
estab
desc
A ce
" Sa
" Ce
" Pi
which
tion

BOOK-A-175

Range 7 West. S. L. M.

Chains set 5 ins. in the ground, marked
1/4 on N. side for 1/4 Sec. cor.
from which
A cedar 6 ins. dia. bears S 72 1/2° W. 28 lks.
" Pine 4 " " " N 7 1/4° E. 35 "
Marked 1/4 S. B. T.

80.00 Grey Sandstone 17 x 12 x 6 ins. Iron
knocked over, which I identify
as the old corner stone, and
reset the same 12 ins. in the
ground, marked 1 notch on E. &
5 on W. Edges, with S. C. for re-
established standard cor. to
Secs. 35 & 36: from which
A cedar 9 ins. dia. bears S. 47 3/4° E. 48 lks. dist.
" Pine 5 " " bears N 22° E. 48 " "
" Cedar 4 " " " S 67 W. 59 " "
" Pine 5 " " " N 29 1/4 W. 195 " "
which agrees with the descrip-
tion furnished me by the office

Re-Survey of the 16th Standard S. Range 4

Chains

Land partly broken & level.
Soil 1st rate.
A few cedars.

West on a Re-Survey line along S. side of Sec. 35.
Var. 15°30' E.

36.50 Road from Sawmill to Beaver Lake, Colby, bears N. & S.

38.30 Telegraph line " N & S.

40.00 I find chiseled corner standard 12x10x8 in. thereon, which I re-set 12 in. in the ground, marked ¼ on N. side for re- is a blazed ¼ Sec. cor. from this A pine 8 in. dia. bears S 3°E. 124 lks. dist. A cedar 4" " " N 3½° W. 176 " " Marked ¼ S. B. T. Corner is in a Ravine drains S.W.

80.00 I find the old corner Grey

BOOK-A-175

Range 4 W., S. E. M.

Chains Sandstone 16 x 8 x 6 in. thrown over, which I m. set 11 in. deep, marked 2 notches on E. & 4 on W. edges S.C. for Re-established Standard Cor. to Sec. 34 & 35. from which
A cedar 6 in. diam. bears N. 53¾° E. 32 lks. dist.
" Pine 4 " " " S. 36° E. 45 " "
" Cedar 4 " " " S 31¼ W. 35 " "
" Pine 3 " " " N 70½° W. 37½ "
The marks on the trees are partly covered by new growth, and therefore cannot be fully read, but the trees and bearings are, agree with the description furnished by the office.
Land Rolling.
Soil 2nd rate.
Timber, Scattering cedar.

1657

Re Survey of the 6th Standard Parall

Chains West on N. Survey line
along South side Sec. 34
Var. 15°30' E.

40.00 I find standing the old Grey Sand
stone 18×12×6 in. for 1/4 Sec. Cor.
Marked 1/4 on N. side, from which
A Pine 8 in. dia. bears N. 55½° E. 34 Lks. dist
" Cedar 10 " " " N 55½° W. 20 " "
Marked 1/4 S.B.T.

47.00 Ridge bears S.

62.50 Ravine " S.

80.00 I find the old Red Sandstone
20×10×6 in, Marked 5 Notches on
E & W. Edges S.C. Standing in
place, from which
A Cedar 4 in. dia. bears N. 50½° W. 7 Lks. dist
" " 5 " " " N 37¾° W. 46 " "
" " 8 " " " N 12° E 33 " "
" " 12 " " " N 50° E. 89 " "
The marks cannot all be read,

BOOK-A-

South, R.

Chains

40.00

40.00

80.00

BOOK-A-175

South, R. 7 W. S. L. M.

Lines but the lines, stone &c agree with the description of the original standard corner to secs. 33 & 34.

Land rolling.

Soil 2d rate.

Timber, Scattering cedars.

West, on Re-Survey, land along South side Sec. 33

Var. 15° 30' E. (mean)

40.00 Finds the old 1/4 sec. corner; Red Sand-Stone 17 x 12 x 8 in. Marked 1/4 on N. side, Standing in place, from which

A cedar 6 in. dia. bears North 36 lks. dist.

" " 5 " " " S 42 3/4° W. 27 " "

Marked 1/4 S.B.S.

80.00 Finds the old standard cor. to secs. 32 & 33; Standing = A Red Sandstone 18 x 12 x 10 in. Marked 4 notches on E.

Re Survey 6th Standard Parallel South R.

Chains

1/2 on W. Edges & S.C. from which
A Pine qui. dia. bears N 72° W. 20 lks. dist
" " 6 " " " S 83¼° W. 42 " "
" Cedar 5 " " " N 80° E. 12 " "
" " 6 " " " S 43° E. 23 " "
As the corner is fully identified
I deem it useless to repeat the
Marks on the trees.
Land rolling East slope.
Soil 2d rate.
Timber scattering cedars.

West on Re. Survey line along
South side Sec. 32
Var. 15° 30' E.

4.50 Deep Gulch, bears S.E. Indications
of Iron.

32.50 Summit of high sharp mountain
Ridge, bears S.W. & N.E.

40.00 I find the old ¼ corner Grey

BOOK-A-175

South R. 7 W. 68 S. L. Mr.

Chains Sandstone 17 x 13 x 4 in. marked
1/4 on N. side, standing on N.
slope of hill; dug pits 18 x 18 x 12
ins. E & W. of stone 5 1/2 feet dist,
and raised a mound of earth
1 1/2 feet high 3 1/2 feet base, along
side.

Note: At this point the old
line was abandoned by the
former survey; I therefore
continue West with my own
line, descending.

55.00 Ranie drains S.W.

65.00 Top of Ridge N.W. & S.W.

80.00 Set Sandstone 24 x 10 x 7 in. 18 ins.
in the ground, for standard
cor. to secs. 31 & 32, marked S.C.
with 5 notches on E. & 1 on W.
edges, and raised a mound
of stone along side.

6th Standard South

Chains	Land Monuments Soil 2d rate. No timber.
	West along S. side sec. 31. Var. 15°30' E.
	Gentle N.W. slope
25.00	Foot of " " "
25.00	Ascend S. slope of Butte
40.00	Set Sandstone 24 x 10 x 9 ins. 10 in. in the ground marked 1/4 on N. face for 1/4 sec. cor. with S.C. and raised a mound of stones along side
	Descend to
74.00	Flat bottom drains S.
80.00	Set Granite 24 x 10 x 10 ins. 18 in. in the ground, for standard cor. to Tps. 30 S. R. 7 & 8 W. Marked S.C. with 6 notches on N. & W. Edges, and raised a mound

BOOK-A-175

R. 7 W. S. L. 1881.

chains of stone alongside.
Land mountainous
Soil 2d rate.
No timber.
Thursday July 14th 1881

In R. 8 W. July 15th 1881.
Westerly & Sections 36. Var. 15° 30' E.
Along divide

16.00 Enter cedar on N & W.

40.00 Set Granite 15 x 10 x 8 ins. 10 ins. in the ground marked S. C. 1/4 on N. side for standard 1/4 sec. cor. and raised a mound of stone alongside.

10.00 Ravine runs N. W.

52.00 Road bears NW & SE.
Along E. slope

80.00 Set Granite 15 x 11 x 9 ins 10 ins. in the ground for standard cor. to secs. 35 & 36, Marked S. C. mile 1 notch on E. & S on W. edge

6th Standard Parallel South

chains and raised a mound of stones
alng side.
Land high mountains divide
Soil 2d rate.
A few scattering cedars.

West along S. side Sec. 35
Var. 5° 30' E.

17.00 Ravine drains NW.
35.00 Ridge bears NW & SE.
40.00 Post of Ridge - Set Granite 18x10
6 ins. 12 in. in the ground marked
S.C. 1/4 on N. side for standard
1/4 Sec. cor. & raised mound of
stone alongside. No present-
able to mark.
59.00 Ravine drains NW.
Along N. slope of divide
80.00 Set Trachyte 14 x 9 x 8 ins. 12 in.
in the ground, for standard

R. 8 W. S. L. Mt.

Chains Cor. to Secs 34 & 35 — Marked
S.C. with 2 notches on E. & W. Edges, and raised mound
of stone along side.
No suitable trees to mark.
Land N. slope of Mountain divide
Soil 2d rate.
Timber cedar & Pinon Pine.

West along S. Side Sec 34
Var. 15° 30' E.
Along N. slope of divide
40.00 Set Trachyte 15 x 8 x 8 ins. 10 in.
in the ground Marked S.C. 1/4
on N. side for Standard 1/4 Sec.
Cor. and raised mound of
stones along side—
No suitable trees to mark.
50.00 Ranie drains N.
80.00 On Ridge bears N.W. Set a

6th Standard parallel S.

Chains Grande 16 x 10 x 8 lks. 11 li. in the ground for standard cor. to secs 33 & 34, marked S.C. with 3 notches on the E & W. Edges, and raised a mound of stone alongside. Land N. slope of hts.
~~Land~~ 2d rate.
Timber, cedar & Pinion Pine.

West along S. side Sec. 33
Var. 15° 30' E.
Descend to
35.00 Ravine trends NE.
4 0.00 set Tachy co 30 x 26 x 20 lks. 20 li. in the ground marked S.C. 1/4 for standard 1/4 Sec. cor. & raised mound of stone along side
45.00 Ridge bears NE & SW.
50.00 Road in Hollow N E.

chains
55.00
65.00
73.50
80.00
12.50
25.00
30.50
40.00

BOOK-A-175

R. 8 W. S.L.M. 74

chains
55.00 Ridge bears N.S.

65.00 Wash drains S.

73.50 Ridge bears N.S.

80.00 Set Trachyte 16x14x12 ins. 11 in. deep for standard Cor. to Secs. 32 & 33, marked S.C. with 4 notches on E. & W. on N. Edges and raised a mound of stone along side. As trees in distance Land Mountainous.
Soil 2d rate.
Timber scattering cedar.

West on S. Side Sec. 32
Var. 15° 30' E.

12.50 Gulch drains S.

25.00 Ridge S.E. & S.W.

30.50 Gulch drains S.E.

40.00 Mark a stationary Trachyte Rock 5 feet ogram a bare ground

6th Standard Parallel South

Chains marked with a cross at the corner post & S.C. 1/4 on N. side for Standard 1/4 sec. cor. & raised a mound of stones alongside.
along S & slope,
65.50 Head of creek; drains SE
80.00 Set trachyte 18 x 18 x 18 ins. 12 in in the ground for standard cor. to secs. 31 & 32, Thence Set S.C. with 5 notches on E & W on N. Edges & raised a mound of stones alongside. 10 trees at hand
Land Mountainous
Soil 2d rate.
Timber scattering cedar, Pine & Mahogany.

West along the S. Side sec. 31
Var. 15° 30' E.

Chains
16.00
29.50
40.00
46.50
61.00
80.00

R. 8 W. S. L. M.

Chains	
	Ascend
16.00	Divide bears S. 15 chs. then N W.
29.50	Gulch drains S.
40.00	Set Trachyte 30×25×10 ins. 20 in. in the ground Marked S C 8/4 on N. side & raised mound of stones along side for 1/4 bg. cor.
46.50	Ridge bears N W. & S E.
61.00	Head of wash drains S E.
	Ascend
80.00	Set Sandstone 20×12×6 in. 15 in. in the ground for standard corner to Township 30 S. R. 8 & 9 W. Marked S C. with 6 notches on N. E. & W. Edges and raised a mound of stones along side 5 feet distant.
	No trees suitable to mark.
	Land mountainous
	Soil 2d rate = Cedar, Pine & Mahogany.

6th Standard Parallel S.

In Range 9 West.

Chains I took the latitude yesterday at noon, and found it to be N. 38° 10'.

West along the S. Side Sec. 36
Var. 15° 30' E.

Ascend

10.00 Ridge N. & S.

30.00 Wash drains S.

40.00 On East slope, marked a stationery Granite Rock 5 feet square above ground S. C. & 1/4 on N. Side, for stand'd 1/4 Sec. cor. & raised a mound of stone alongside, marked a (X) cross at the corner joint, on the rock.

Ascend to

56.00 Top of main Mts. bears N. W. & S. E.

60.50 Descend to

BOOK-A

R. 9 W.

76.00 T

80.00 K

K

gr

a

S.

5

N

3

M

T

La

S

T

W

4.00 R

30.00 M

40.00 Se

R. 9 W. S. L. M.

7600 Hollow drains S.

8000 Mark a stationary volcanic Rock 40×40×40 ins, above ground, with a cross (X) at the corner point, & S.C. with 1 notch on E & 5 notches on W. Edges, for standard cor. to Secs. 35 & 36. and raised a mound of stone alongside. Trees too rough to mark. Land mountainous Soil 2d rate. Timber scattering cedars.

West along S. side Sec. 35 Var. 15°30' E.

400 Ridge bears N. & S. descend

3000 Wash drains S. ascend,

4000 Set Granite 14×12×6 ins

6th Standard South

Chains
10 lks. in the ground, marked S.C. & 1/4 on N. side for stand= ard 1/4 Sec. cor. & raised a mound of stone along side.
43.50 Top of Ridge N.W. & S.E.
76.00 Gulch drains S.
80.00 Set Volcanic Rock 18 x 10 x 6 ins. 12 ins. in the ground for Standard Cor. to secs. 34 & 35, marked S.C. with 2 notches on E. and 4 on W. Edges, and raised mound of stone alongside. No trees near. Land mountainous Soil 2d rate. Timber Cedar, & mountain mahogany.

BOOK-A
R. 9

Chains
4.00
5.50
13.50
40.00
43.50
48.50
74.00
80.00

BOOK-A-175

R. 9 W. S. L. M.

Chains	West along S. Side Sec. 38 / Var. 15° 30' E.
4.00	Enter heavy growth of cedar timber bears N. & S.
5.50	Ridge bears N. & S.
13.50	Gulch drains S.
40.00	Set Wasatch Rock 18 x 14 x 12 ins. 12 in. deep, marked S.C. 1/4 on N. Side, for standard 1/4 Sec. cor. from which 8" cedar 12 in. dia. bears N. 10 E. 12 lks. " " " " " " " S 45 W. 21 " marked 1/4 S. B. T.
43.50	Ridge bears NW. & SE.
48.50	Trachyte ledge " " "
74.00	Wash drains S, leave heavy cedar timber, ascend.
80.00	Set Granite 16 x 10 x 7 ins. 11 in. deep for standard cor. to Secs. 33 & 34, Marked

6th Standard Parallel S.

chains S.C. with 3 notches on E. & W. Edges, and raised mound of stone alongside No tree in distance fit to mark.
Land Mountainous.
Soil 2d rate,
Timber, Cedar on 76 chs.

West along the S. Side 83.
Var. 15° 30' E.

5.00 Ridge bears N 77 E. Ascend.
30.00 Road in Valley, S E.
40.00 S.E. Mamie Rock 36 x 30 x 16 ins. 24 ins. in the ground Marked S.C. and 1/4 on N. side for Stand. and 1/4 Sec. cor. on raised a mound of stone alongside. No Trees in distance.
Ascend to

BOOK-A
R. 9
45.00 A
53.00 M
57.80
68.50 R
80.10 Le
13
an
S.C.
2.
a
No
to
La
Se
Ta
1.00 Ma
38.00 Ri

R. 9 W. 182

45.00 Ridge bears N.W.S.

53.00 Wash drains N.

57.80 " " "

68.50 Ridge bears N.W. & S.E. descend

80.10 Set Volcanic Rock 20×16×4 ins. 13 in. in the ground for standard cor. to secs. 32 & 33, marked S.C. with 4 notches on E and 2 on West edges & raised a mound of stones alongside. No trees in distance suitable to mark.

Land Mountainous.

Soil 2° rate.

Timber Scattering cedars.

West along S. side Sec. 32

Var. 15° 30' E.

1.00 Wash drains N. Jr.

38.00 Ridge bears N.W. & S.E. descend

6th Standard Parallel S.

40.00	On W. side of hill; Set a Conglomerate Rock 14×10×10 ins. in the ground Marked S.C. & 1/4 on N. side for Standard 1/4 Sec. cor. and raised Mound of Stone alongside—	Chains
	A Cedar 4 in. Dia. bears N45°E. 2 links marked 1/4 S.B.M.	3.50
42.50	Bank drains N.	16.00
51.50	Ridge bears NW & SE.	40.00
60.00	Bank drains N.	
77.00	Bois Brule Spring bears SW about 12 chs.	
80.00	Set Volcanic Rock 15×10×10 ins. deep for Standard cor. to secs. 31 & 32 Marked S.C. with 5 notches on E & 1 on W. edges, and raised a Mound of Stone along side.	42.50
	Ete Trees at Stand.	50.00
	Land Monuments	80.00

BOOK-A-175

R. 9 W. S. L. Mt.

Chains Soil & Rate.

Timber scattering cedar.

West along the S. side sec. 31.

Var. 15°30' E.

3.50 Wash drains SW.

16.00 " " " , ascend.

40.00 Set Volcanic Stone 24×14×12 ins. 18 in. in the ground marked S.C. & 1/4 on N. side for standard 1/4 sec. cor. and raised mound of stone alongside As here convenient to mark.

42.50 Spur of Ridge bears N W.

50.00 Wash drains N.

80.00 Set Volcanic stone 21×13×11 ins. 14 ins in the ground, for standard corner to Secs. 30 & 31 T. 9 N R. 10 W. Marked S.C. with six notches on N. E. & W. Edges, and raised

6th Standard Parallel South 85m R. 10

Chains. a mound of stones alongside,
No Trees near enough to mark.
Land Mountainous—
Soil 2d rate.
Timber Scattering cedar.
July 15th 1881

BOOK-A-175

South

gside,
mark.

dar.
81

R. 10 W. S. L. Mer.

In Range 10 W.
July 16th 1881

As a part of the line in this range has been surveyed, I therefore met on a random line on the South boundary of the Tp. in this range, setting temporary corners at every 40 & 80 chs, and at 6 miles 1 chain & 17 links I intersect the Range line between 10 & 11 W. 1.16 links E. of the standard cor. to T. 30 S. R. 10 & 11 W.

Now, as the standard line has been originally run 6 miles East, I therefore run East from the above corner, which is a Red Sand-stone 20 x 15 x 14 ins. in mound

Re-Survey 6th Standard Parallel S. 1881 — R. 10.

Chains

of Stones,-which agrees with the description furnished me by the office,-on a re-survey line along S. side Sec. 31.

Var. 15° 30' E

32.00 Ravine bears N. W.

40.00 Fnid the old 1/4 cor: A Red Sandstone 19 x 10 x 4 ins. lying down I re-set the Same 12 ins. in the ground; Mark S.C. on the stone in addition to the old 1/4 on the N. side, for re-established 1/4 Sec. Cor. & raised Mound of Stones along side.

52.00 Ridge bears N W & S E.

73.50 Ravine drains N.

80.00 Fnid the old corner Standing Viz: Red Sandstone 17 x 10 x 8 ins. 11 in. in the ground marked S.C. with 5 Notches on E & W

Chains

40.00

80.00

BOOK-A-175

R. 10W. S.L.M.

Chains N. Edge, for standard cor. to secs. 31 & 32, I raise a mound of stone alongside. Land Rolling — Soil 2d rate. No timber.

East on Re-Survey line along S. side sec. 32. Var. 15° 30' E.

40.00 Find the old cor. standing viz: Red Sandstone 18×10×8 ins. 12 ins. deep, marked S C 1/4 on N. side for standard 1/4 sec. cor. I raise a mound of stone along side.

80.00 Find old corner standing. viz: Grey Sandstone 20×6×4 ins. about 15 ins. in the ground, marked S.C. & 4 notches on E, & 2 on W.

Re-Survey = 6th Standard S.

Chains Edges for old Standard
Cor. to Secs. 32 & 33. I add a
mound of stones alongside
Land Poliris.
Soil 2d rate.
No timber.

East on Re-Survey line
along S. side Sec. 33,
Var. 15° 30' E.

40.00 Find old ¼ stone & mound
Re-set the same, viz: Red
Sandstone 16×12×6 ins, 11 ins,
in the ground, for re-established
Standard ¼ Sec. Cor, marked
S.C. ¼ on N. side, & raised
mound of stones alongside

53.80 Wash drains N. W.

66.00 Ridge bears N.

80.00 Find old corner standing:

Chains Ed

Ea

40.00 Fi
Re
11 ins,
¼
on
Ma

BOOK-A-175

T. 1 S., R. 10 W., S. L. M.

Chains Viz: Red Sandstone 18×10×8 ins. about 12 ins. in the ground, for Standard cor. to secs. 33 & 34, marked S.C. with 3 notches on E & W. Edges; I added a mound of stones along side. Land Rolling Much Soil 1st rate. No timber.

East on Re-survey line along S. side sec. 34, Var. 15° 30' E.

40.00 Found old cor. standing; Viz: Grey Standstone 17×12×5 ins. about 11 ins. in the ground, for Standard 1/4 sec. cor. marked S.C. 1/4 on N. side; I added a mound of stones alongside,

65.00 Marsh drains N.

Re-survey 6th Standard S. R. 6 W.

77.40 Road to Pawnee from Miamisville bears N & S.

80.00 Find old corner standing: Dig. Black lava stone 26×12×12+ ins, about 18 ins. in the ground for standard cor. to Secs. 34 & 35 Marked S.C. with 2 notches on E. & W. edges. I dug pits 18×18×12 in. N. E. & W. of corner 5½ ft. distant & mound a mound of earth 2 feet high 4½ feet base alongside. Land Rolling brush. Soil 1st rate. Timber. (End of re-survey

Note: From the above corner, my temporary stake bears N. 1.16 chs. and the standard Corner to Tps. 30 S. R. 9 & 10 W.

13.00 Ga
33.00 Ri
40.58 Dr
40.80 Pas
67.50 Ri
81.17 Se

therefore, bears N. 89°35' E.
2 miles 1 chain & 17 links,

I now run
N. 89°35' E. along S. side
of Sec. 35, (in order to save
setting a double corner)
Var. 15°30' E.

13.00 Ascend.
33.00 Ridge bears N & S.
40.58 Note:
Dividing the error of 117 links
in this mile) Set Volcanic stone
14×12×10 ins. 10 in. in the ground
for standard 1/4 Sec. cor. Marked
S.C. & 1/4 on N. side & Raised
Mound of stone alongside.
Ascend
40.80 Wash drains N. Ascend 11 lks.
57.50 Ridge bears N & S.
61.17 See above note: Set Volcanic Rock
24×8×8 ins. 18 in. in the ground

6th Standard Parallel S. R. 10 W.

Chains for standard cor. to sec. 35 & 36. Marked S.C. with notches on E. & S. on N. Edges, and raised mound of stone alongside.
Mountains on 40.37 chs.
Soil 3d rate.
No timber —

N. 89° 35' E. along the S. side sec. 36.
Var. 15° 30' E.

Ascend
20.00 Spur of mtn. bears N.
20.00 Rock drains N. Ascend
40.00 set sandstone 15 x 12 x 6 ins. 10 ins. in the ground, for standard 1/4 sec. cor. Marked S.C. 1/4 on N. side, & raised mound of stone alongside.

BOOK-A-175

R. 10 W. S. L. M. 1884

57.00 Ridge bears N.W.S.
71.50 Wash drains S.W. ascend
80.00 Intersect my corner to T. 30 S.
R. 9 & 10 W. ~~which~~ & set yester-
day the description of
which I deem useless to
repeat here.
Land mountainous.
Soil 3d rate.
Timber a few cedars on E/r.
~~Monday~~ July 16th 1881.

General Description
The line runs generally
along the divide of Mountains
between beaver and Paroman
Valleys.
The townships N. & S. of
the line, in the several
ranges, lie partly in the

mountains & partly in the foot hills, containing a good deal of timber and indications of mineral. They can all be subdivided by putting forth proper effort.

F. C. Bailey
U. S. Dep. Surv.

BOOK-A-175

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, Oct 9th *1881.*

The foregoing field notes of the survey and re-survey of the

6th Standard Parallel South

in Ranges 7. 8. 9. & 10 W.

Township No 30 S. ~~*Range No*~~

of the Salt Lake Meridian, Utah Territory,

Executed by S. C. Bailey

Under his *contract No* 102

of the 2ny *day of* May *1881,*

in the month of July *1881,*

having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.

Fred Salsbury

U. S. Surveyor General for Utah.

BOOK-A-175

R: 1872

Filed Sept. 11th. 1881.

Examined by J. H. Camp & R. Garlinski

Compared by E. Nichols & E. Salomon.

FIELD NOTES

OF

THE SURVEY OF THE

3 West Boundary

of Township No. 30 S., Range No. 7 W.

of the Salt Lake Meridian in Utah Territory.

BY

F. C. Bailey

U. S. DEPUTY SURVEYOR,

Under his Contract No. 102,

dated May 29th 1881

Survey commenced July 18th 1881

Survey completed " 18th 1881.

BOOK-A-175

West Boundary T. 30 S. R. 7 W.

On the night of July 17, 1881, I took an observation of the star Polaris in accordance with instructions contained in the Manual of Surveys and drove pickets on the line thus established.

Survey commenced July 18th 1881 with a Burt's improved solar compass.

Before commencing this survey I test my compass on the line established last night.

I begin at the standard corner to T. 30 S. R. 7 W. S. B. which is a Granite Stone 24 x 10 x 10 in. Marked

BOOK-A-17

West Boundary T. 30 N. R. 8 W.

Chains: S.C. with 6 notches on E. & W. edges, with a mound of stones alongside.
Having previously run a blank line between the above corner & the cor. to T. 29 & R. 7 & 8 W. I know the bearing and length of the line to be North six miles.
Therefore I run
North on a true line between Secs. 31 & 36
Var. 15° 30' E.

5.00 Divide bears E. & S/W
Descend slowly for the next 3 miles pick & calling each
110.00 Set Granite stone 13 x 8 x 3½ ins, in the ground, marked ¼ on W. sides for ¼ sec. cor.

BOOK-A-175

T. 30 R. 8 W. S. L. M.

and raised mound of
stone alongside
0.000 Set Granite 15 x 10 x 8 ins.
10 ins. in the ground, for
cor. to secs. 25, 30, 31 & 36.
Marked 5 notches on N. & 1 on S. edge &
& raised mound of stone
alongside.
Land Mountainous-
Soil, 2d rate.
Timber, Scattering cedars.

North bet. Secs. 25 & 30
Var. 15° 30' E.
4.000 Set Granite 14 x 8 x 4 ins.
10 ins. deep for 1/4 sec. cor.
marked 1/4 on N. side &
raised a mound of stone
alongside.
0.00 Set Granite 12 x 12 x 6 ins,

West boundary T. 30 S. R. 7 E.

Chains

Cor. to Secs. 19. 24. 20 & 30. Marked 4 notches on 4 faces S. edge
and raised Mound of Stones alongside, from which 8.75
Cedar 5 in. dia. bears S. 5° E 8 links 0.00
Marked T. 30 S. R. 7 W. S. 19. B.T.
Cedar 4 in. dia. bears S. 9° E 10 lks.
marked T. 30 S. R. 7 W. Sec. 30 B.T.
Land Mountainous —
Soil 2d rate.
Timber Scattering Cedar.

North bet. Secs. 19 & 24
Var. 15° 30' E.

40.00 Set granite 14 x 10 x 5 in.
10 in. in the ground for
1/4 sec. cor. Marked 1/4
on W. side, from which

BOOK-A-175

R. 7 E., S. L. M.

Chains A cedar 18 in. dia. bears S. 30 E. 60 lks
marked ¼ S. B. T. at foot
of mountains bearing E. & W.
68.75 Road N. & S.
60.00 Set Granite 13 × 12 × 10 ins,
qui. deep for cor. to Sees.
7 & 8, 13 × 18. 1924. Marked
3 notches on N. & 3 on S. edges
& dug pits 18 × 18 × 12 in.
in each Sec, 5½ ft. dist,
& raised mound of earth
2 ft. high 5½ feet base
alongside, from which
A cedar 3 in. dia. bears S 30 E. 40 lks
marked T. 3 S. R 7 E. S. 19 B. T.
Land mountainous on S.
40.00 chs.
Balance hilly -
Soil 2d rate.
Timber, scattering cedar.

West Boundary T. 30 S. R. 7 E.

Chains

North bet. Secs. 13 & 18
Var. 15° 30' E.

6.75 Road bears E & W.
8.90 " " N & S.
40.00 Set Granite 14 x 9 x 4 in. 10 in. deep for 1/4 sec. cor. Marked 1/4 on W. side & raised mound of stones alongside.
80.00 Set Granite 14 x 10 x 6 in. 10 in the ground for cor. to Secs. 7, 12, 13 & 18 marked 2 notches on cor. & on S. Edges & raised mound of stones alongside. Land cedar hills, Sloping N. Soil 2nd rate. Timber cedar & Pinon Pine.

Chains

Nor

40.00 Set

Qua
Mon
pits
stor
mus
feet

7.00 Roa
.00 Set

mi
to s
not
& o
alon
Lan
Soil
Tim

BOOK-A-175

R. 7 W. 2° S. L. M.

Chains

North bet. Secs. 7 & 12
Var. 15° 30' E.

41.00 Set Granite 13 x 10 x 6 in.
2 in. deep, for 1/4 Sec. cor
marked 1/4 on N. side; dug
pits 18 x 18 x 12 in. N & S of
stone 5 1/2 feet distant, &
raised mound of stone 1 1/2
feet high 3 1/2 feet base. alongside

47.00 Road bears N E & S W.

50.00 Set Granite 14 x 10 x 4 in.
min. die thro gmnd, for cor.
to Secs. 1. 6. 7 & 12, marked 1
notch on E, & 5 on S. Edges,
& raised mound of stones
alongside.
Land hilly.
Soil 2d rate.
Timber, scattering cedar

West boundary T. 30 S. R. 7 W.

Chains

North between Secs. 1 & 6
Var. 15° 30' E.

6.00 Enter Hollow drains N.W.
20.00 Leave scattering cedars.
20.00 " Hollow drains N.W.
40.00 Set Granite 13 x 9 x 6 in. qui. in the ground for 1/4 sec. cor. marked 1/4 on W. side & mixed mound of stones alongside.
57.00 Leave foot hills & enter sage brush & grasswood in valley bears E. & W.
80.00 Intersect north boundary at the established cor. to T. 29 & 30 S. R. 7 & 8 W. which is ~~a Locust~~ blue line Stone 20 x 8 x 6 in. chiseled over: I on se the same, 18 in. in the grou

BOOK-A-175

touch ups the 6 notches on
N. E. S & W. edges, & dug pits
24 x 18 x 12 in. Lengthwise on
Each line N. S. E. W. of Stone
6 ft. dist. & raised a mound
of each 2½ feet high 5 ft
base a square.
Land hilly & level.
Soil 2d rate.
Timber, scattering cedars on 20. chs
Sage brush & greasewood on 23. "
Total 43. "

July 18th 1881

General Description

The South part of both of the townships on the E. & W. of this line falls in the mountains, which divide Beaver from Parowan Valley. The Balance of the townships lie in Beaver Valley but contain no known settlements. They can be subdivided.

T. C. Bailey
U. S. Dep. Surv.

BOOK-A-175

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, Oct 7th 1881

The foregoing field notes of the survey of the

West Boundary of

Township No 30 S *Range No* 7 W.

of the Salt Lake Meridian, Utah Territory,

Executed by F. C. Bailey

Under his *contract No* 102

of the 27 *day of* May 1881,

in the month of July 1881,

having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.

Fd. Salsbury

U. S. Surveyor General for Utah.

BOOK-A-175

R: 1882

Filed Sept. 11. 1881.

Examined by John H. Camp & R. Gerlinski

Compared by E. Salomon & E. Michaelis

FIELD NOTES

OF

THE SURVEY OF THE

West & Re-Survey of the North Boundaries of

of Township No. 30 S., Range No. 8 W.,

of the Salt Lake Meridian in Utah Territory.

BY

F. C. Bailey

U. S. DEPUTY SURVEYOR,

Under his Contract No. 102

dated May 24th 1881.

Survey commenced July 19th 1881

Survey completed " 20th 1881

BOOK-A-175

206

Re-Survey of St. Boundary of
T. 30 S. R. 8 W. S. L. Mr.

In order to determine & identify the Township corners originally established on this line, I find it necessary to retrace it, as the point shown me for the cor. to Secs. 7 & 30. T. 30 S. R. 7 & 8 W. could not be well identified as the old corner, the stone being thrown over & probably out of place; Therefore after adjusting my compass to the meridian, I commenced the survey July 19th 1881, and run a blank line West from the above corner point, to the cor. to T. 29 S

Re-Survey of S. Boundary

T. S.

Chains

T30 S. R. 8 & 9 W, which I
find standing viz: A Greysand
stone 17 x 8 x 8 ins, about 11 ins,
in the ground, marked 6 notches
on N. E. S W. Edges, to which I
added pits 24 x 18 x 12 ins, lengthwise
on each line N. S. E W.
of stone 6 ft. dist: & raised
mound of earth 2½ ft.
high 5 ft. base along side.
I find some of the old
corners standing, the bearing
of the old line agrees with
my own, and the length
of the line is 6 miles, ——
—— which exactly
—— agrees with the
orginal measurement.
I now, from the above cor.
run East on a true, line

40.00

80.00

Re-survey

of S. 30 S. R. 8 W. S. L. M.

Chains

Cert. Secs. 6 & 31

Var. 15° 30' E.

40.00 Find old Cor. Stone chiseled over which I now set Veg: At Greysand dune 17 x 8 x 6 ins, 9 ins & in the ground for 1/4 sec. Cor. & dug pits 18 x 18 x 12 ins. E & W of Stone 5 1/2 ft. dist, & raised mound of earth 1 1/2 ft. high, 3 1/2 feet base along=side.

80.00 Find old corner to secs. 5 & 6. S. 31 W. standing Veg: A Black Cava 20 x 14 x 6 ins. 14 ins. in the ground marked 5 notches on E. & 1 on N. Edges and dug pits 18 x 18 x 12 ins, in each Section 3 1/2 feet distant & raised a mound of earth 2 ft. high 4 1/2 ft. base along side,

Re-Survey of N Boundary 209

Chains Land rolling valley
soil 1st rate.
No timber.

East on Re-survey line
bet. Secs. 6 & 32
Var 15° 30' E.

13.55 Road bears NE & SW.
40.00 Find old 1/4 cor. Stone
Standing 12" Sandstone 15 x 12 x 4
div. about 9 ii. in the ground
marked marked 1/4 on N. Side
& I added pits 18 x 18 x 18 ins,
E & W. of Stone 5 1/2 feet dist,
& raised mound of earth
1 1/2 ft. high 8 1/2 feet base
alongside.
53.28 Wash drains N & S
75.78 Road bears NW & SE.
80.00 Find old cor. Gone-Iron=

1.50
4.50
40.00

T30. S. R. 8 W. 2nd S. E. Mer.

Establish Corner by setting a Granite Stone 15 x 10 x 4 ins. 10 ins. in the ground for Marked 4 notches on E & W2 on N. sides Cor. to Secs. 4, 5, 32 & 33, X X

Raised a mound of Stone along side.

Land rolling Valley

Soil 1st rate.

No timber.

East on Resurvey line bet. Secs. 4 & 33

Var. 15° 30' E.

Enter Hollow drains S.W.

12.50 Bush in Hollow

4.50 Leave hollow head S. E. Black

40.00 Find old corner & Land

18 x 9 x 7 ins. about 10 ins. in

N. Boundary T. 30 S. R. 8 W.

Chains the ground for ¼ Sec. cor.
Marked ¼ on N. side & raised
Mound of stones along side.
44.90 Enter Hollow drains N. W.
49.70 Leave " heads S E. 17.50
65.50 Road bears N W & S E 19.25
74.65 Wash drains N W. 40.00
80.00 Old corner stone viz: A Black Alaw
17 x 10 x 5 ins, thrown over: Re-
set the stone 10 ins. in the
ground for Cor. to Secs. 3. 4.
33 & 34 marked 3 notches on
E & W. Edges & raised Mound 80.00
of stones alongside.
Land rolling Valley
Soil 1st rate.
No Timber.

BOOK-A-175

S. L. M. 212

East on Re-survey line
bet. 3 & 4
Var. 15° 30' E.

17.50 Road bears N. W. & S. E.

19.25 Wash Drains N. W.

40.00 Corner stone lying down—
Re-set Same as Found 20 x
10 x 8 in. qui. in the ground
for 1/4 sec. cor. marked 1/4
on north side & mound of stones alongside.

80.00 Old cor. stone viz: A brown sandstone
16 x 10 x 4 in. thrown over—
Re-set Same qui. in the
ground for cor. to secs.
2, 3, 34 & 35, marked 2 notches
on E & W edges, & raised
mound of stone along side.
Land Rolling Valley,

Re-survey

243

A. Boundary S. 30 S.R. 8 W.

Chains Soil 1st rate.

No timber.

East on Re-survey line

bet. secs. 2 & 35

Var. 15 30' E.

2.50 Brush drains N W.

17.10 Def. Hemlock 6 inch bears.

N. 15° W. about 60 lks,

N 15° E. 16° E. about 40 lks.

24.00 Brush drains N.

24.25 Road bears N & S.

35.00 " " N E & S W.

40.00 Found old corner stone in

place 8/5; (Sandstone 16 x 6 x 4 in.

mas for 1/4 sec. cor. no Rod 1/4

on N. side, deg pits 18 x 18 x

12 in. N & E & W. of stone 5/2

S. L. M. 214

chains ft. dist. & raised ground of Earth 1½ ft. high 3½ ft. base alongside. from which Bartons Guest mill bears N 15° E. 40 chs. about.

Two Old stone standing bg: a Red Sandstone 17 × 10 × 5 in. Marked 1 Notch on E & W sides on N. Edges for cor. to recs. 1.2.55 V 36 to which S. dug pits 18 × 18 × 12 in. in Each Dist. 5½ ft. dist. & raised ground of Earth 2 ft. high 4½ ft. base alongside.

Land Rolling Valley Soil Loam.

No Timber

Reserve

N. boundary T. 30 S. R. 8 W.

BOOK

Chains

East on N. survey line
bet. Secs. 1 & 36.
Var. 15° 30' E.

10.50 Road bears S.E. & N.W. in deep wash drains N.E.

40.00 Find old cor. stone standing, viz: 4 sandstones about 17 x 8 x 6 ins, for 1/4 sec. cor. marked W on N. side & dug pits 18 x 18 x 12 in. E. & W. of stone 5 1/2 feet dist. & raised a mound of stone Earth 1 1/2 feet high, 3 1/2 ft. base alongside. from which Jos. Morris house bears N. 5° E. about 30 chs. dist.

42.20 Trail bears N.E. & S.W.

70.95 Road bears N.W. & S.E.

80.00 To the Blue Lime Stone 20 x

8 x 6 ins, lying loose on the ground, as mentioned in the beginning, which I now find to be at the corner point. I re-set the same 18 ins. in the ground for Cor. to S. 29 & 30 S. R. 7 & 8 W. marked 6 notches nt. E. & W. Edges, dug pits 24 x 18 x 12 ins, crowning on line, N. S. E. W. of stone 6 ft. dist, & raised a mound of earth 2½ feet high 5 ft. base alongside. Land Rolling Valley soil 1st rate.

Timber.

Beaver River runs along N., north of line from 40 to 80 chs. distant.

July 19 day 1881.

West boundary of T. 30 S., R. 8 W.

chains

July 20th 1881.

From the Standard corner to ~~xxxx~~ T. 30 S. R. 8 & 9 W. (which was set by me the other day, and therefore I deem it useless to repeat the description here) I run North on a Random line along the West boundary of T. 30 S., R. 8 W., setting temporary corners at 40.00 & 80. chains, and at 80.50 miles 6 links W. of cor. I intersect the cor. to T. 29 & 30 S. R. 8 & 9 W.

From the above cor. I run S. 0° 8' W. on a true line bet. secs. 1 & 6

2.00
35.25
44.00

81.00

BOOK-A-175

S. L. M. 216

Var. 15° 30' E.

2.00 Iron drains set E.

35.25 " " " "

40.00 Set Limestone 15×10×6 in. 10 in in the ground for 1/4 sec. cor. Marked 1/4 on N. side X raised mound of stones alongside.

81.00 Set Trachyte stone 15×14×11 in, 10 in in the ground for cor. to secs. 1. 6. 7 & 12, Marked 1 notch on N & S on S. Edges & raised mound of stone alongside.

Land Sage brush flat & Valley.

Soil 2nd rate.

No timber — Sage brush only.

West Boundary of T. 30 S. R. 8 W. of S.

Chains		Chains
	South 8 W. on a true line	
	bet. Secs. 7 & 12	
	Var. 15° 30' E.	
40.00	Set Trachyte 13 x 10 x 8 ins. 9 in.	
	in the ground for 1/4 sec. cor.	
	Mt. Red 1/4 on N. side. Brs.	
	mound of stones alongside,	1.00
53.00	Enter timber & leave flat, ascend	
57.00	Enter marsh, drains N.	
63.00	Leave same heads E.	
80.00	Trachyte stone 15 x 12 x 16 ins.	
	min. in the ground for	76.50
	cor. to secs. 7, 12, 13 & 18, marked	80.00
	2 notches on E. & W. edges.	
	Brs. E. mound of stones	
	alongside.	
	Land mountainous & large flat.	
	Soil Scrub.	
	Timber scattering cedar & pine	

R. 8 W. S. Lake. 320

chains on S. 25 chs. Bal. dense sage brush & greasewood.

S. 0°8' W. on true line
Dist. Recs. 13 & 18
Var. 15°30' E.

40.00 Set a Granite Stone 15 x 12 x 4 in. 9 in. in the ground for 1/4 Sec. cor. Marked 1/4 on W. side, & raised a mound of stones ~~for~~ alongside.

76.50 Top of Knoll - descend

8.00 Set Trachyte 36 x 30 x 30 in. 24 in. in the ground for cor. to Secs. 13. 18. 1924, ~~Raised~~ Marked 3 notches on E. & S Edges & raised Mound of Stone alongside.

Land Mountainous

West boundary T. 30 S. R. 8 W. &

Chains	Soil 2d rate. Timber & scattering cedar.	Chain
	S. 0° 8' W. on a true line bet. secs. 19 & 24 Var. 15° 30' E.	
0.50	Wash drains N.	
22.00	Top of Knoll—	
30.00	Head of hollow drains E.	
36.00	ascend—	
40.00	set Trachyte 13 x 12 x 9 ins. 9 ins. in the ground for W. cor. Marked 1/4 on N. side X raised mound of stones alongside.	21.0 400.0
68.00	Wash drains N.	
80.00	Top of Ridge bears N. & W. Set Trachyte 24 x 8 x 6 ins. 18 ins.	

BOOK-A-175

W. S. L. Mr. 2 2 2

Chains

Marked y notches on N. & E. on S. Edge of me. the ground, & raised mound of stone alongside.
Land Mountainous.
Soil & rock
Timber & scattering cedars

S. 0°8' W. on true line
bet. Secs. 25 & 30
Var. 15°30' E.
Descend to
Wash drains NE. thence
along W. slope of grassy ridge,
21.00 Set Trachyte 14×10×8 in. conc.
in the ground for 1/4 sec. cor.
Marked 1/4 on W. side, from
40.00 which
A cedar 6 in. dia. bears N 50° E. 15 links.
" Pine 6 " " " N 55 W. 40 "

W. boundary T. 30 S. R. 8 W.

Chains	
	Marked T. S. B. T. Enter hollow drains westerly
53.00	Head of same, drains South.
72.00	Top of Knoll.
80.00	In Rock slide, set a Granite stone 20×12×10 ins. 14 ins. in the rocks for cor. to secs. 25, 30, 31 & 36, marked S notches on E. & W. sides, and raised mound of stones adjoining, from which a cedar 8 in. dia. bears N. 33° E. 15 links. Marked T. 30 S. R. 8 W. S. 30 B. T. A cedar 6 in. dia. bears S. 20° W. 40 links. Marked T. 30 S. R. 9 W. S. 36. B. T.
	Land mountainous
	soil 2nd rate.
	Timber & cat deny cedar

Chains	
30	
32.0	
40.0	
55.	
63.	
72.	
76.	
80	

W.

	Chains	
		S. 0°8' W. on true line bet. Secs. 31 & 36 Var. 15°30' E.
	3.00	Hollow drains NE.
	32.50	Top of Divide bears E & W.
	40.00	set Granite 13 x 12 x 8 in. qui. in the ground for 1/4 Sec. cor. marked 1/4 on W. side & raised mound of stone alongside.
	55.00	Bottom of mud basin.
	63.50	Top of Knoll
	72.00	Wash drains E.
	76.00	Top of Knoll.
	80.00	The standard cor. to T. 30 S., R. 8 W. Land Mountainous Soil 2d rate. Timber, some cedars.

General Description.

The north part of this Town-
ship lies in Beaver Valley
& the S. part in the
timbered Mountains —
There are no known set-
lements in it, but a
party is about to make
a desert entry of some
of the land in the
N.E. corner — It can be
all subdivided.

July 20th 1881.

C. C. Bailey
U.S. Dep. Sur.

BOOK-A-175

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, Oct 7th *1881.*

The foregoing field notes of the survey of the

West & Re-Survey of the North Boundaries of

Township No 8 S *Range No* 8 W.

of the Salt Lake Meridian, Utah Territory,

Executed by F. M. Bailey

Under his *contract No* 102

of the 2nd *day of* May *1881,*

in the month of July *1881,*

having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.

Fred Salsbury

U. S. Surveyor General for Utah.

BOOK-A-175
R: 1882

Filed Sept. 16. 1881.

Examined by John H. Evans & R. Gorlinski

Compared by E. Salomon & E. Michaelis

FIELD NOTES

OF

THE SURVEY OF THE

West & South Boundaries

of Township No. 30 S., Range No. 9 W.

of the Salt Lake Meridian in Utah Territory.

BY

P. C. Bailey

U. S. DEPUTY SURVEYOR,

Under his Contract No. 102

dated May 24th 1881.

Survey commenced July 21st 1881

Survey completed " 22d 1881.

BOOK-A-175

East Boundary T. 30 S. R. 9 W.

Plains

Survey commenced July 21, 1881, with a Burt's improved Solar Compass, which agrees with the meridian obtained from an observation on the star Polaris,

From the established corner to secs. 7, 12, 13 & 18, T. 30 S. R. 9 & 10 W.

Viz: "A grey sandstone 17" x 7" x 5" in.
"marked 2 notches on the N.
"& W. edges,
which agrees with the description furnished by the Office, I run
South on a Blank line along the W. boundaries of secs. 18. 19. 30 & 31, and at four miles I intersect

West boundary of T. 30 R. 9 W.

Chains		
	the 6th Standard Parallel	4.50 To
	South at the Standard	7.70 Iron
	Cor. to T. 30 S. R. 9 & 10 W. M.	0.00 Sto
	now established by me	mi
	three days since, and	m
	thereby I deem it unnecessary	for
	to describe the same	cor
	here, from which I run	of
	North Var. 15°30' E.	20
	Ascend	do
40.00	set Granite 24x12x12 in.,	Bo
	18 in. in the ground for	Sto
	1/4 Sec. cor. marked 1/4	
	on N. side & raised a	
	mound of stones alongside	
43.00	Top of Ridge E & W.	1.90 Iron
46.50	Descend to	8.00 To
60.00	Head of Arroyo N.	11.25 Iron

BOOK-A-175

R. 9 W. S. L. M.

4.50 Top of Knoll; Enter cedar trees.
7.70 Wash drains S.W.
10.00 Granite 12x12x12 ins. 8 ins in the ground, marked 5 notches on N. & W. on S. Edges for cor. to secs. 29. 30. 31 & 36. and raised a mound of stones alongside.
Land, 40 chs. Inundations- Soil 2d rate.
Balance Rolling- Soil 2d rate. Scattering cedar on 14.50 chs.

North between secs. 25 & 30
Var. 15° 30' E.

1.90 Wash drains S.W.
8.00 Top of Spur bears S.W.
11.25 Wash drains S.W.

West boundary T. 30 S. R. 9 W.

14.00	Top of spur of Ridge bear	chains
	Error.	
16.50	Wash drains N. heads E. 5. cr	
24.00	West point of Knoll.	
30.50	Wash drains N.	
40.00	Set Granite 20×12×5 ins. 14	
	in the ground for 1/4 sec. cor	
	Marked 1/4 on N. side &	
	raised mound stone along	
	side, from which	
	Cedar 12 in. diam. bears N 40° 30' E	
	23 links dist. Marked 1/4	
	S. B. T.	
52.50	Wash drains N.	
66.00	Leave cedar timber	
65.30	Wash drains NE.	
75.00	Top of Knoll.	4.00
80.00	Set Trachyte stone 16×12×12	15.00
	ins. 10 in. in the ground	40.00
	for cor. to secs. 19. 24. 25 & 30.	

9 W. S. L. Sn. 231

chains

Marked 4 notches on ℄ 2
on S. Edges, and raised a
mound of stones alongside.
from which
A Cedar 16 in. dia. bears N 59½ E. 15 lks,
marked T. 30 S. R. 9 W. S. 19. B. T,
Cedar 16 in. dia. N 73° W. 31 links,
Marked T 30 S. R. 10 W. S. 24. B. T,
Land mountainous—
Rec'd 2d date.
Cedar on S. 65 chs.

North Ref. 1924
Var. 15° 30' E.

4.00 Road bears N E & W
15.00 West slope of Knoll
40.00 Set Granite 14 × 10 × 9 ins.
10 ins. in the ground for

West boundary T. 30 S. R. 9 W. 6

Chains		Chains
	1/4 sec. cor. marked 1/4 on N. side, dig pits 18x18x1 ins. N & S of stone 5 1/2 feet distant, and raised a mound of earth 1 1/2 ft. high 3 1/2 ft. base alongside	22.25
		30.00
		34.00
75.50	Road bears N W & W.	40.00
80.00	Set Granite 16x12x4 ins, 11 in. in the ground, for cor. To dep. 13.18.19 & 24, mark 3 notches on N. & S. edges & dig pits 18x18x12 in. in each sec. 5 1/2 ft. dist. and raised mound of earth 2 ft. high 4 1/2 ft. base alongside.	43.00
		52.50
		58.50
	Land Mountainous	80.00
	Soil 2d rate	
	No timber.	

BOOK-A-175

R. 9 W. S. L. M. 233

	Chains
	North bet. Secs. 13 & 18.
	Var. 15° 30' E.
2	2.25 Brush drains N.W.
3	0.00 Spur of Ridge, N.W.
3	4.00 Brush drains W.
4	0.00 Set Granite 16x12x8 ins, 10 ins. in the ground for 1/4 Sec. cor. Marked 1/4 on W. side & mound of Stones alng side.
4	3.00 Spur of Ridge bears S & W.
5	2.50 Brush drains W.
5	8.50 W. Point of Ridge.
8	0.00 To the established cor. to Secs. 7, 12, 13 & 18. Land rolling & broken. Soil 2d rate. Heavy cedar brush on W. chs

BOOK

Re-survey bet. Secs. 7 & 12. of N. Com

Chains

North on Re-survey line
bet. Secs. 7 & 12
Var. 15°30' E. 49.80

40.00 Cobble stone 16 x 8 x 6 in. which 51.00
I identify as the old ¼ cor. 52.00
Standing 32 links West of 53.00
my line, (which stone was 54.00
found west 21 feet by some
one, as I am informed by seve 56.10
of the citizens of Minersville) but
as the N.E. & E. of this line 76.10
on both sides of the 80.00
the settlers have made
their entries, I let the
stone stand where I find
it, & continue North
on my own Re-survey line.
41.50 the E. street in Minersville
bears E & W. - The East side

W. Sunday T. 30 S. R. 9 W. 2. Mer

of the East strut of the
Tree, bears N.W.S. about 10
links West of my line.
49.80 Irrigating ditch drains N.
51.00 House 75 links E.
52.00 Strut bears E & W.
53.00 House " E. about 100 lks.
54.00 Baker's House bears N. about
10 links.
56.10 Beaver River 70 lks. wide
runs N.
76.10 Road bears E & W.
80.00 Find old cor. standing by:
Cobble stone 20 x 6 x 5 in.
for cor. to secs. 1, 6, 7 & 12,
marked 1 notch on N. & S. on
S. Edges, & mound
of stones alongside.
Land, mostly in Meadows
fit for cultivation

250

236

West boundary T. 30 S. R. 9 W

Chains	
	Soil 1st rate.
	No timber.
	Leave Resurvey & run North bet. secs. 1 & 6 Var. 15° 30' E.
0.00	Enter brush.
16.50	Road bears N & S.
20.00	Enter Hoelow head N.E.
40.00	Set sandstone 14 x 10 x 6 in. 10 ins. in the ground for 1/4 Sec. cor. Marked 1/4 on N. side, & raised mound of stone alongside.
45.00	Leave Hoelow, drains N.W.
60.00	Wash drains S.W.
80.00	Set Sandstone 15 x 6 x 5 in. 10 in. in the ground for cor. to T. 29 & 30 S., R. 9 & 10 W. Marked 6 Notches on N.E.

N - S. L. Mt. 237

S. Mt. Edges, dug pits 24 x 18 x 12 in. lengthwise on each line N. S. E. & W. of stone 6 ft. dist, and buried mound of earth 2½ ft. high, 5 ft base alongside.
Land sloping south.
Soil 1st rate.
Heavy sage brush on ridges.

July 21st 1881

North boundary T. 30 S. R.

chains	
	July 22d 1881.
	From the corner to T. 29 & 30
	S. R. 9 & 10 W. I run East
	on a random line, setting
	temporary half mile & mile corners at
	40. & 80. chains, and at
	6 miles I intersect the
	Established corner to T. 29 &
	30 S. R. 8 & 9 W. viz: a
	"Agency sandstone" 7 x 8 x 8 in. marked
	6 notches on each edge, with
	pits 24 x 18 x 12 in. length =
	rise on each line N. E. S. &
	W. of stone 6 feet dist. with
	mound of earth the reqd=
	ired size, along side.
	From the cor. to Townships
	29 & 30 S. R. 8 & 9 W. I run
	West on a true (reserved) line

BO

chains
15.5
31.9
33.3
40.0
42.4
49.8
49.9
55.
59.

W. S. L. M. 239

Chains	
	Set. Reco. 1836
	Var. 15°30' E.
15.50	Wash drains N.W.
31.90	Road bears N.E.
33.30	Enter fried fence N.E. & S.W.
40.00	Set Granite 15 x 8 x 6 in. 10 in. in the ground for 1/4 Sec Cor. Marked 1/4 on N. side, dug pits 18 x 18 x 12 ins. E & W. on line 5 1/2 ft dist, & raised mound of earth 1 1/2 ft. high 3 1/2 ft. base alongside. No trace of old corner.
	End of Reservoir.
42.40	Beaver River 30 links wide runs S.W.
49.80	Leave fried fence N.E.
49.90	Road bears N.E.
55.35	Wash drains S.W.
59.20	Geo. Chaffin's House bears S 10° E. 10 chs.

North boundary 240 L. 30 S. R. 9 W.

Chains		
	David Reese House bears	0.65
	N. 75 E. 8 chs.	21.00
60.90	Road bears N.W.	
80.00	Set Lava stone 15 × 8 × 6 ins,	
	10 ins. in the ground, for	40.00
	cor. to secs. 1. 2. 35 & 36.	
	marked 1 / notch on E. & S. on	
	br. Edges & raised mound	
	of stones alongside.	
	Land sloping East.	48.50
	Soil 1st & 2d rate.	80.00
	No timber.	
	Heavy sage brush, except	
	on the 16.50 chains in feed.	

"

West on true line
bet. secs. 2 & 35
Var. 15° 30' E

N. S. L. S. M. 241

0.65	Wash in Hollow drains S.W.
21.00	Telegraph line bears N.W. & leave rolling valley & ascend Mountains N.W. & N.
40.00	Set Lava Stone 20 x 8 x 8 ins, 14 ins. in the ground for 1/4 sec. cor. Marked 1/4 on N. side & raised Mound of Stones alongside.
48.50	Enter cedars
80.00	Set Lava Stone 16 x 7 x 4 ins, 11 ins. in the ground, for Marked 2 notches on E & W on sides cor. to 2 secs. 2. 3. 34 & 35 & raised Mound of Stones alongside and 5 Q. chs. Mountainous,
	Bal. rolling Valley —
	Land 2d rate.
	Cedars on 48.50 chs

North Boundary T. 30 S., R.

Chains

West on true line
bet. secs. 3 & 34
Var. 15° 30' E.

40.00 Volcanic Rock) 30 x 18 x 12 in.
20 in. in the ground, for
1/4 sec. cor. marked 1/4
on N. side. & raised a
mound of stone alongside,
from which a large
Lava Rock bears S. 10
links dist. along S. slope—
66.50 Road bears NW. dist.
a Hollow drains NW.
80.00 Set Sandstone 24 x 6 x 6 in.
18 in. in the ground for cor.
to secs. 3. 4. 33 & 34 marked
3. notches on E & W. edges
& raised mound of stone
alongside.

BOOK 92.

40.00

79.00
80.00

BOOK-A-175

T. 2 N. R. 2 W.

Land Mountainous —
Soil 2nd rate.
Timber, scattering cedar.

Mst on true line
bet. Secs. 4 & 33
Var. 15° 30' E.
Over South slope of mountain
Set Granite 16 x 06 x 4 ins.
11 ins. in the ground, for
¼ Sec. cor. Marked 1/4 on
N. side & raised Mound
of stone alongside.
Road bears N & S.
Set Flintstone 24 x 12 x 10 ins.
18 ins. in the ground for cor.
to Secs. 4, 5, 32 & 33. Marked 4
Notches on E. & 2 on W. Edges.
& raised Mound of stone alongside.

40.00
79.00
80.00

South boundary T. 30 S. R. 2 W. 9 M.

Chains Soil, 2d rate. Land mountainous

Timber - scattering cedar.

"

West on the line
bet. Secs. 5 & 32
Var. 15° 30' E.

25.50 Road bears NW & in a
hollow which drains S.

40.00 Set Sandstone 40 x 14 x 12
ins. ins in rocky place,
for ¼ sec. cor. Marked
¼ on E. side & raised
a mound of stone around
the corner. to support the
stone.

80.00 Leave mountains & enter
Valley, bears NW. - leave
cedars. Set Sandstone

7.90
15.92
40.00

9 M. S.L. Mines

15 x 9 x 6 in. 10 in. in the ground for cor. to secs. 5.6.31 & 36. Marked 5 Notches on E. & W. on N. Edges, dug pits 18 x 18 x 12 in. in each sec. 5½ ft. dist. & mound of earth 2 ft. high 4½ ft. base alongside. Land mountainous Soil & rock. Timber scattering cedar.

"

Met on true line bet. secs. 6 & 31 (Var. 15° E)

Cedar grove.

7.90 Creek draining S.W.

15.92 Road bears N. & S.

40.00 Red Sandstone 14 x 10 x 5 in.

North boundary of T. 30 S. R. 9 W.

Chains 10 mi. in the ground for 1/4 sec. cor. Marked 1/4 on N. side, dug pits 18×18×12 in. E & W. of stone 5½ ft. dist. & raised mound of Earth 1½ ft. high 5½ ft. base alongside.

50.00 Rock drains South.

58.45 Road bears NE & SW.

60.00 Hollow drains S.

80.00 The cor. to T. 29 & 30 S. R. 9 & 10 W.

Land rolling —
Soil 2d rate.
No timber.
Mean pace on 80 chs.
July 22d 1851

BOOK-A-175

for ¼
n cr.
/18 /
½ ft.
d of
½ ft.
e.
r.
S. R.
s.
85/

Gen'l Survey of T. 6 N. R. 2 W.

General Description.

The N. & S. portions of this Tp. lie in the mountains; the middle part, through which flows Beaver River, contains some settlements & can be subdivided.

T. C. Bailey
U. S. Dep. Surv.

S. L. M. 253

63.00 Top of Ridge bro. N.E.
70.00 Radius drains N.E.
80.00 Set a Trachyte stone 18 x 15 x 12 in. 12 in. in the ground for cor to Secs. 23, 24, 25 & 26, marked with 2 notches on Sand 1 on E. edges. and raised a mound of stone alongside.
Land High broken Mountains.
Soil 3rd rate
Scattering cedar.

East on a random line bet. Secs. 24 & 25
Var. 15° 30' E.
9.00 Radius drains N. 1/4 Sec. Cor.
40.00 Set Comp. 1/4 Sec. Cor.
66.00 Radius drains N.E.
80.20 Int. Le cor. to Secs.

Subdivisions T. 30 S., R. 9 W.

24 & 25 on the East
Bd. of the Tp. which is
a Trachyte stone 24x8x6 in.
with a stone mound
from which
West on a true line
bet. Secs. 24 & 25.
40.10 Set a Trachyte stone
23x16x10 in. 15 in. in the
ground, for 1/4 Sec. cor.
marked 1/4 on N. side,
and raised a stone mound
alongside.
80.20 The Cor. to Secs. 23. 24.
25 & 26.
Land high broken Mountains
Soil 3rd rate.
Scattering cedars.

BOOK-A-175

S. L. M.

North bet. Secs. 23 & 24

Var. 15° 30' E.

40.00 in gage trench Set a Trachyte stone 20 X 15 X 12 ins. 12 in. in the ground, for 1/4 Sec. Cor. marked 1/4 on W. face, and raised a stone-mound alongside.

53.00 Track dirs. N. E.

~~Found Cedar Pointer~~

8.00 Set a Trachyte stone 20 X 14 X 14 ins. 12 in. in the ground, for cor. to Secs. 13. 14. 23 & 24. marked with 3 notches on Sand 1 on E. edge, and raised a mound of stone alongside, from which a Cedar 12 in. in diameter brs. N. 43¼° E. 57 lks. distant

Subdivisions T. 30 S. R. 9 W.

marked T. 30 S. R. 9 W.	
S. 13. B. T.	
A cedar 10 in. in dia. brs.	
S 25½° W. 10 lks. dist.	20.00
marked T. 30 S. R 9 W.	
S. 23 B. T.	33.00
A cedar 12 in. in dia. brs.	40.00
N. 14° W. 22 lks. dist.	50.00
marked T. 30 S. R. 9 W.	80.12
S. 14. B. T.	
A cedar 8 in. dia. brs. S. 2¼°	
E. 6 lks. dist. marked	
T. 30 S. R. 9 W. S. 24 B. T.	
Land Mountainous.	
Soil 3rd rate	
Oak and sage brush on	
80. chs.	40.
Cedars scattering.	

S. L. M. 251

East on a random line
bet. Secs. 13 & 24
Var. 15° 30' E.

20.00 Ravine drns. N. E.
Leave Timber enter brush.
33.00 Top of Ridge N E & S W.
40.00 Set temp. 1/4 Sec. cor.
50.00 Ravine drns. N. E.
80.12 Intersect the E. Bd. of
the Tp. at the cor.
to Secs. 13 & 24, which is
a Trachyte 36 x 30 x 30 in
with a mound of stone.
From which
West on a true line
bet. Secs. 13 & 24
40.06 Set a Trachyte 18 x 12 x 8 in
12 in. in the ground
for 1/4 Sec. cor. marked
1/4 on N. side and raised

Subdivisions T. 30 S., R. 9 W.

chains a mound of stone along side.

80.12 The cor. to secs. 13, 14, 23 & 24

Land Mountainous
Soil 3rd rate.
Timber Cedars. on 20. chs.
Brush Oak & Sage Brush on 60. chs.

North bet. secs. 13 & 14
Var. 15° 30' E.
Descend

34.00 enter timber.
40.00 set Trachyte 17 x 12 x 8 ins. mins. in the ground for 1/4 sec. cor. marked 1/4 on

BOOK A-15

S. L. M. 201

Chains W. side [illegible] & raised mound of stone along side, at foot of mountains.

57.00 Ridge bears N.W. & S.E.,

65.00 Wash drains N.W.

75.00 Ridge bears N.W. & S.E.,

80.00 * Land mountains.

Soil 2d rate.

Cedar timber on N. 46. chs.

* Set Stone hub 20×12×8 ins. 15 ins in the ground for cor. to secs. 11, 12, 13 & 14, marked 1 notch on E. & 4 on S. W. edge & raised mound of stone alongside.

East on random line bet. secs. 12 & 13

Var. 15° 30' E.

1.50 Wash Drains N.E.

8.50 Ridge bears N. & S.

12.00 Wash drains NE

3.00 Ridge bears NE, & SW.

Subdivision T. 30. S. R. 9 W.

39.25 Wash drain N.

40.00 set temp. 1/4 sec. cor. on ridge bears N & W.

41.00 Wash drain N.W. 1 chain

58.50 Ridge bears W.S.

77.90 Wash drain N.

80.29 Intersect East boundary of the Tp. 40 lks. N. of the cor. to secs. 12 & 13. Thence a Trachyte stone 15x12x10 ins. with stone mound, from which

N. 89° W. on true line bet. secs. 12 & 13,

40.15 set Burnt Sandstone 20x20x12 ins. 15 ins. in the ground for 1/4 sec. cor. Marked 1/4 on N. side, & mound stones adjacent.

17.80

20.00

21.00

27.00

40.00

80.00

S. L. Mr. 261

80.29 The cor. to secs. 11, 12, 13 & 14,
Land Mound,
Soil 2d rate.
Scattering cedars.

"

Mark Met. Dec. 1912
Var. 15° 30' E.
Leave timber Eng. some Branch.
17.80 Mark draws W.
20.00 Ridge, bears N W & E.
21.00 Enter hollow draws N W.
27.00 Leave " " "
40.00 Set Iron pipe stone 24 x 20 x
12 ins. 18 ins. in the ground
for 1/4 sec. cor. marked 1/4 on
W. side & mound stone S
Alone Almond.
80.00 (old obs. 29 Dec. not found)
Set Bl. stone 16 x 12 x 10
ins. 11 ins. in the ground

Subdivision T. 30 S., R. 9 W.

Chains for cor. to secs. 1, 2, 11 & 12,
Marked / notch on E. & on S. Edges & raised
mound of stone & ranged
Land sloping North,
Soil 2d rate.
Dense sage brush & such
Timber.

East on random line
bet. secs. 1 & 12
Var. 15° 30' E.

20.00 Brush drains N.W.
40.00 Set Quarter ¼ Sec. cor.
80.50 Intersect East boundary
of the Tp. 30 S. R. 9 W. of the cor. to secs. 1 & 12, which
is a Trachyte stone 15 x 14 x
11 ins. mile stone mound

Chains

10.25

80.50

BUOY-A-175

S. L. M.

Chains from which
N. 89° 30' W. on true line
bet. secs. 1 & 12

40.25 set Land Stone 16 x 10 x 10 ins
11 mks. in the ground for
1/4 sec. cor. marked 1/4 on W.
side, dug pits 18 x 18 x 12 ins,
E. & W. of stone 5 ft. dist,
Mounds formed of Earth
1 ft. high 3 ft. base
alongside.

80.50 The cor. to secs. 1. 2. 11 & 12,
Land Marks level.
Soil 1st class.
Dense Sage Brush 80 chs.
Timber.

Subdivision T 30 S. R 4

Chains North, between secs. 1 & 2
Var. 15° 30' E.

23.00 Road bears N W & S E.
30.00 Road " N E & S W.
40.00 set bush. 1/4 sec. cor.
41.00 Beaver River 50 Links wide
Runs N.
48.70 Fence bears S E & N W.
51.80 Same " " N E & S W.
60.00 Road from Minersville
to Beaver city bears N W & S E.
61.25 Gen. C. Chafin's House
bears N 75° E. about 30 chs.
and enter foot hills.
71.25 Hollow drains S E
81.25 In Same " " S W. Entered
N. boundary of the [illegible]
at the cor. to secs. 1 & 2,
which is a Lava stone
15 x 8 x 6 ins, mkd mound

M. S. L. M.

chains of stone, from which
North on true line
bet. secs. 1 & 2

41.25 Set Volcanic stone 12 x 12 x
10 ins. 8 ins. in the ground
for 1/4 sec. cor. Marked 1/4
on W. side, & dug pits
18 x 18 x 12 ins
N.E. & S. of stone 5 ft. dist.
& mound of earth
1 1/2 ft. high 3 1/2 ft. base
alongside.

81.25 The cor. to secs. 1. 2. 11 & 12,
Land mostly level.
Soil 1st rate.
Dense sage brush on 81.25 chs,
No timber.
Oct. 10th 1881.

Subdivisions T. 30 S., R. 9 W.

chains

Oct 11th 1884

From the Stan cor. to secs. 34 & 35, on the north boundary of the Township, on Std. Standard Line, which is a Volcanic Rock 18×10×6 ins with mound of stone along side, bears

North bet. secs. 34 & 35

Var. 15° 30' E.

20.00 Rains drains S.E.

40.00 set Trachyte stone 18×12×10 ins. 12 ins. in the ground for 1/4 sec. cor. marked 1/4 on N. side & raised mound of stone alongside.

70.00 Divide bears N.W. & S.E.

80.00 set Trachyte stone 17×15 1/2 ins. 11 ins. in the ground for cor. to secs. 26 & 27. 34 & 35, marked 2 notches on E.

chains a

40.00

59.00

79.90

BOOK-A-175

S. L. M.

Chains on 1 on S. Edgls. & raised
mound of Surveyors
style.
Land Mountainous
Soil 2d rate,
Scattering cedars

East on random line
bet. secs. 26 & 35
Var. 15° 30' E.
through scattering cedars.
40.00 set trees. ¼ sec. cor.
59.00 Ravine draws N.
79.90 Intersect N. & S. line 14 lks
S. of cor. to secs. 25. 26.
35 & 36, from which
S. 89° 54' W. on true line
bet. secs. 26 & 35

Subdivisions T. 30 S. R. 9 W.

39.95 set Trachyte stone 18 x 12 x 6 ins. 12 ins. in the ground for 1/4 sec. cor. marked 1/4 on S. side & raised a mound of stone along side.

79.90 The cor. to secs. 26. 27. 34 & 35 —

Land Mountains, Soil 2d rate, Scattering cedars.

"

Same bet. secs. 26 & 27 Var. 15° 30' E.

40.00 set Trachyte stone 14 x 11 x 4 ins. 10 ins. in the ground for 1/4 sec. cor. marked 1/4 on N. side & raised

BOOK A 175

S. L. M.

chains Mound of stone alongside
45.00 Ravine drains N.E.
75.00 Ravine " " "
80.00 On N. side of main Ravine
drains N. set a Granite
20 x 14 x 10 ins. 15 ins. in
the ground for cor. to
secs. 22, 23, 26 & 27, marked
2 notches on E & W. edges &
mound of stone
alongside, from which
a pine 10 ins. dia. bears N. 10 E. 30 lks.
Marked T 30 S. R. 9 W. S. 23. B. T.
Land mountainous,
Soil & Sale.
Scattering cedar & Pine timber

11

Subdivisions T 30 S. R. 9 W.

chains		
	East on random line bet. secs. 23 & 26. Var. 15° 30 E.	
5.00	Ravine trends NE.	
20.00	Ridge bears NE & SW.	
30.00	Ravine trends NE	
40.00	set 1 inch I. pipe, sec. cor.	
79.94	Intersect N.S. line 1 lk. S. of cor. to secs. 23 & 24, 25 & 26, from which S. 89° 30' W. one inch bet. secs. 23 & 26	40.00
87.97	set Standstone stone 24 x 16 x 12 ins., 18 ins. in the ground for 1/4 sec. cor. marked X on N. side & raised mound of stone along side.	53.50 76.50 80.00
79.94	The cor. to secs. 25, 23, 26 & 27, Land Monuments,	

BOOK
S.
chains

BOOK-A-175

S. L. Mk. 2/

Chains Soil 2d rate.

Scattering cedar & Pine

"

North bet. Secs. 22 & 23
Var. 15°30' E.

Descend,

4000 set Granite 16×10×6 ins,
11 ins. in the ground for
1/4 sec. cor. marked 1/4 on
N. side, & buried mound
of stone alongside.

53.50 Ranges chains N.

76.50 " " "

80.00 On E. Point of hill; set a
Granite 16×12×6 ins. 11 ins,
in the ground, for cor. to
Secs. 14, 15, 22 & 23, marked
2 notches on E. & 3 on S. edges

Subdivisions T 30 S., R. 9 W.

Chains Traced Mound of stone
Amgoide.
Land Monuments,
Set 2d Date.
Scattering cedars & pine

"

East on random line
bet. secs. 14 & 23.
Var: 15° 30' E.

Descend

10.00 Ravine crosses.
40.00 set bears. & sec. cor.
49.00 Ravine crosses N.
62.00 Ridge bears N. 85 W.
77.92 Intersect N. & S. line 21
links S. of cor. to secs. 13,
14, 23 & 24, from which
S. 89° 57' W. on line

BOOK-

S. L.

Chains

39.96

77.92

4.50

33.25

BOOK-A-175

S. L. M. 273

Chains bet. secs. 14 & 23,

39.96 set Granite 14 x 12 x 6 ins
10 ins. in the ground
for 1/4 sec. cor. marked
1/4 on N. side & raised
mound of stone along
side.

79.92 The cor. to secs. 14, 15, 22 & 23,
Land Mountains,
Soil 2d rate.
Timber Keating
cedar & Pitch pine

North bet. secs. 14 & 15
Var. 15° 30' E.
Descend

4.50 Hollow drains SE.
33.25 Wood Road in hollow NE.

Subdivisions T. 30. S. R. 9 W.

40.00 Set Granite 12 x 10 x 4 ins, 8 ins. in the ground for 1/4 sec. cor. Marked 1/4 on N. side & mound of stone along side.

80.00 Set Volcanic Rock 24 x 20 x 10 ins. 18 ins. in the ground for cor. to secs. 10, 11, 14 & 15, Marked 2 notches on E & W sides, edges & mound of stone along side.

Found Monuments, Lojl & Dale.

A few cedars.

"

BOOK-

S. L.

Chains

5.00
13.00
26.00
34.00
35.50
40.00
47.50
55.00
60.00
65.00
75.00
80.00

40.00

BOOK-A-175

S. L. Mrs.

Chains East on random line
bet. secs. 11 & 14
Var. 15° 30' E.

6.00 Ridge bears N & W
13.00 Wash draws N.
26.00 Ridge bears N & W.
34.00 Inter Wash draws E.
35.50 Leave " " NE.
41.00 set stone, 1/4 sec. cor.
47.50 Ridge bears N & W.
55.00 Wash draws N.
60.00 Ridge bears N E & W.
65.00 Road in Wash N W.
75.00 Ridge bears N W & E.
80.00 Intersect N & S line
at the cor. to secs. 11, 12, 13
& 14 from which
Brass on true line
bet. secs 11 & 14
40.00 Set Stone 20 x 12 x 8

Subdivisions of Sec. 30 S.R. 9W

	chains mks. 15 lks. in the ground for ¼ sec. cor. marked ¼ on N. side, & raised mound of stone along side.	43.00
80.00	The cor. to secs. 19, 24, 25, 30, Land mountainous, soil 2d rate. Pine cedars.	44.00
	"	50.50
	North bet. secs. 19 & 24 Var. 15° 30' E	62.25
~~1000~~	Descend,	64.00
10.00	Pine mountains & cedars, Enter Beaver Cañon E & W. & dense brush,	80.00
40.00	set set volcanic stone 14×10×6 ins. 10 ins in	

S. L. M. 21

the ground for 1/4 sec. cor. marked 1/4 on W. side, & raised mound of stone alongside.

43.00 Road E & W.

44.00 Barnes' stable bears S 1/4° 30' E.

50.50 Barnes' Mable bears S 64° 30' E, His house is about 1 ch. S.E. of stable. N.W. cor. of his field bears N. 28° 30' E. about 20 chs. distant.

62.25 Beaver River runs N. 50 lks. wide

64.00 Road to Beavercity E. Leave canon & enter hills.

80.00 on N. slope of Lava Mts: set Lava stone 24 x 16 x 12 ins., 18 ins. in the ground for cor. to secs.

Subdivisions Tp. 38 S. R. 9 W.

Chains	2.3.10 41, Marked B Notches on E & S on S. Edges & raised Mound of Stone alongside.	40.00
	Land Mountainous, Soil 2d rate.	42.00
	A few cedars on S. 10 chs.	50.20
	brush on 70 chs.	65.25
		78.50
		80.20
		40.10
	East on a random line bet. Secs. 2 & 11 Var. 15° 30' E	
	Ascending	
9.00	To N Lava Mountain	
32.00	Foot N same N & S.	
33.50	Road N.E. & S.W.	
37.50	Beaver River 50 lks. wide 4 ft. deep runs S.W.	8.2
	Enter field	

40.00 42.00	Set temp. 1/4 Sec. Cor. Rocks, Ford Injs. S. about 20.00 lks.
50.25	Road N. E. and S. W.
65.25	Wash S. W.
78.50	Same Wash N. W.
80.20	Intersect N & S. line at cor. to Secs. 1. 2. 11 & 12 from which West on a true line bet. Secs 2 & 11
40.10	Set a Volcanic rock 12 x 10 x 6. ins. 9 in. in the ground, for 1/4 Sec. Cor. marked 1/4 on N side, dug pits 18 x 18 x 12 ins E & W. of stone, 5 1/2 ft. dist. and raised Mound of Earth 1 1/2 ft. high 3 1/2 ft. base along side. From which
8.2	a log cabin bears S. 50 W 2.50 chs. distant

Subdivisions Tp. 38 S. R. 9

Wm J. Jones house
brs. S. 12° E. about 12 lks. dist
Jones corral brs. S 25° E.
about 13 chains distant.

80.20 The cor. to Secs. 2, 3, 10 & 11. 40.30

Land rolling hills
Soil 1st and 2nd rate
Dense Sagebrush ow
80.20 chs. — 80.30

North on a random line
bet. Secs 2 & 3
Var 15° 30' E.

1.00 Hollow drns. S. E.
22.00 Telegraph line brs. N. & S. W.
40.00 Set temp. 1/4 Sec. cor
80.30 Intersect the North Boun-
dary of the Tp. at cor to
Secs 2 & 3, which is a

R. 9 W. 2d S. L. M.

Lava stone 16 x 7 x 4 in
in mound of stones
from which
South on true line
bet. Secs. 2 & 3
40.30 Set a Lava stone 16 x 12 x 9 in.
12 in. in the ground for
1/4 Sec. Cor. marked 1/4 on W. side
and raised
a mound of stone alongside
80.30 The Cor. to Secs. 2. 3. 10 & 11
Land Mountainous.
Soil 2nd rate, rocky
Scattering Cedars.
Oct. 11th 1881

Oct. 12th 1881
From the cor. to Secs.
33 & 34 on the South
being also Sixth Standard North
Boundary of the Township

which is a Granite
stone 16x10x7 ins. with
a stone mound alongside
I saw
North Lat Secs. 33 & 34
Var. 15° 30' E.

38.00 Wash S. M.
40.00 Set a Trachyte rock 18x14x11
ins. 12 in. in the ground
~~mound~~ 1/4 Secs ~~cor~~ s
marked 1/4 on W. side
and raised a mound of
stone alongside. 12.00

80.00 Set a Trachyte rock 20.00
17x14x7 ins. 13 ins. in the 32.00
ground for cor. to Secs. 40.00
27. 28. 33 & 34. marked 60.00
with 1 notch on the South 80.12
and 3 on the East edges. and
raised a mound of stone
alongside.

R. 9 W. S. L. M.

Land Mountainous.
Soil 3rd rate
Heavey undergrowth of
Oak & Sage brush
Scattering Cedars. ow 80.00 chs.

East on a random line
bet. Secs. 27 & 34
Var. 15° 30' E.

12.00	Wash drns. South
20.00	Ridge brs. N. & S.
32.00	Wash drns. S. W.
40.00	set temp. 1/4 Sec. cor.
60.00	Divide brs. N. W. & S. E.
80.12	Intersect N. & S. line 21 Mls.

P. of cor. to Secs. 26, 27, 34 and 35. from which
S. 89° 30' W.

Subdivisions 28th T. 30 S.

on a true line West Secs.
27 & 34.

4.00 Set a Trachyte rock 8
15 x 15 x 12 ins. 10 ins. in the
ground, for 1/4 Sec. Cor.
marked 1/4 on N. face. ~~with~~
and raised a mound of
stone alongside.

80.12 The Cor. to Secs. 27. 28.
33 & 34.
Land Mountainous.
Soil 3rd Rate
Heavy Oak & Sage brush.
Scattering Timber.

30.00
7.00

80.00

BOOK A 175

R. 9 W. S. 22 N. M.

North Cor. Secs. 27 & 28

Var. 15° 30' E

30.00 Divide N. W. & S. E.

7.00 Set a Trachyte rock 23 x 13 x 10 ins. 16 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on W. side and raised a mound of stone along side

8.00 Set a Granite rock 14 x 14 x 6 ins - 7 ins in the ground for Cor to Secs. 21, 22, 27 & 28 marked 2 notches on S & 3 on E. edges and raised a mound of stone alongside from which

a Cedar 6 in. dia. brs. N. 75° E. 30 lks. dist. marked T. 30 S. R 9 W. S. 22 B. T.

Subdivisions Tp. 30 S. R. 9 W.

chains	
	No other trees within distance. Land Mountainous Soil 3rd rate Timber scattering Cedars and Pinons.
	East on random line bet. Secs. 22 & 27 Var. 15° 30' E.
7.50	Hollow drains S. E.
37.00	" " " "
40.00	Set temp. 1/4 Sec. cor. at head of large hollow drains S. E.
58.00	Rocky Ledge bears N. W. & S. E.
65.00	" " " "

S. L. M. 28

chains	parallel with the 1st one.
	Descend to
80.00	Intersect N & S line at
	the cor. to secs. 22.23,
	26 & 27, from which
	Mst on true line
	bet. secs. 22 & 27
40.00	set Volcanic stone 10x10x
	10 ins. 7 ins. in the ground
	for 1/4 sec. cor. marked
	1/4 on N. side & raised
	mound of stone along
	side.
80.00	The cor. to secs. 21.22, 27 & 28
	Land mountainous.
	Soil 2d rate.
	Cedar & Pine

"

Subdivisions S. 30 S. R. 9 W.

chains

Iron bet. secs. 2/1132
Var. 15° 30' E.

35.00 Head of hollow draw on S. slope of hill; set
40.00 white stone 18 x 12 x 10 ins.
12 ins. in the ground for
1/4 sec. cor. marked 1/4 on
W. side of mound
of stone alongside, from
which
Cedar 12 ins. dia. brs. N 25° W. 30 lks.
marked 1/4 S. B. T.

51.00 Bald rocky hill bears
E & W.

80.00 Near top of high hill
on W. slope. Set a
Quartzite stone 18 x 16 x
10 ins. 12 ins. in the ground
for cor. to secs. 15,
16. 21 & 22, marked 3

20.00

S. L. M. 28

Notches on E and S. edges and raised a Mound of stone alongside, from which a Price 18 ins. dia. brs. N. 30° W. 50 lks. Marked T. 30 S. R 9 W. S. 16 B. T.

a Price 12 ins. dia. brs. S. 80° W. 50 lks. Marked T. 30 S. R 9 W. S. 21 B. T.

Land Mountainous.

Soil 2nd rate

Scattering Cedar & Pine

East on random line

Var. Secs. 15 & 22.

Var 15° 30' E.

20.00 To S. Flathill, N. & S.

Subdivisions T. 29 S. R. 9 W.

		Chains
40.00	Set temp. ¼ Sec. Cor.	
45.00	Hollow drains N.E.	
65.00	Head of Hollow drains N.E.	
80.04	Intersect N. & S. line of W.	22.50
	of the Cor. to Secs. 14. 15.	40.00
	22 & 23 from which	
	a. S 89° 57' W. 40 links true line	
	Cor. Secs. 15. 9 22.	
40.02	Set Granite 15 x 10 x 10 ins.	
	10 ins. in the ground for ¼	
	Sec. Cor. Marked ¼ on N. side	
	and mixed a Mound of stone	
	alongside).	
80.04	Cor. to Secs. 15. 16.	52.75
	21 & 22.	55.00
	Land Mountainous	69.50
	Soil 2nd rate	80.00
	Cedar Timber	

BOOK-A-175

S. L. M. 2 11

Chains Arch bet. Secs. 15 & 16
Var. 15° 30' E.
Descend.

22.50 Head of large Hollow drains N.W.
40.00 On N. slope of hill, set Granite 14 x 14 x 8 ins. 10 ins. in the ground for 1/4 sec. cor. marked 1/4 on N. side & raised mound of stone alongside from which Cedar 6 ins. dia. brs. N. 25 E. 15 lks. marked 1/4 S. B. T.
52.75 Hollow drains N.
55.00 E. Point of rocky hill.
69.50 Leave cedars.
70.00 On Ridge bears NW. set Volcanic stone 20 x 20 x 10 ins. 15 ins. in the ground for cor. to Secs. 9. 10. 15 & 16

Subdivision T. 30 S. R. 9 W.

Chains Marked 3 notches on E. & W.	39.00
on S. Edges & raised a	40.00
mound of Stone alongside,	55.50
Land Mountainous	64.50
Soil 2d rate.	80.00
Timber cedar as noted.	
"	
East on random line	40.00
bet. secs. 10 & 15	
Var. 15° 30' E.	
3.00 Brush drains N.	
6.50 Ridge bears N. & S.	
8.00 Brush drains N.	80.00
11.00 Ridge bears N. & S.	
15.00 Brush drains N.	
21.50 Ridge bears N. & S.	
25.00 Brush drains N.	
29.50 Ridge bears N. & S.	

BOOK-A-175

S. L. M.

39.00 Mark drains N. W.
40.00 Set temp: 1/4 sec. cor.
53.50 Ridge bears N. W. & S. E.
64.50 Ravine drains N.
80.00 Intersect W. S. line at the cor. to secs. 10. 11. 14 & 15, from which
Wet on true line bet. secs. 10 & 15
40.00 Set Standstone stone 20 x 12 x 8 ins. 15 ins. in the ground for 1/4 sec. cor. marked 1/4 on N. side, & mound of stone alongside
80.00 The cor. to secs. 9. 10. 15 & 16, Land mountains
Soil 2d rate.
No timber

Subdivisions T 30. S. R. 9

chains. North bet. secs. 9 & 10 chains
Var. 15° 30' E.

Descend

3 6.00 Leave Mountains & enter bottom & down range brush.

4 0.00 Set Limestone 12 x 10 x 6 ins. 8 ins. in the ground for ¼ sec. cor. Marked ¼ on W. side & mound a mound of stone along side.

4 3.03 S. Bank of Beaver River, runs W. 60 lks wide.

4 3.63 N. Bank of same. Res Reservoir bears S. 85 W. about 13 chs.

4 6.00 Road to Beaver city E & W.

4 7.00 Telegraph bears E & W. & leave Bottom & ascend 33.50

8 0.00 Set Limestone stone 14 x 10 x 37.00

S. L. M. 1-95

chains 10 lks. 10 lks. in the ground, for cor. to secs. 3, 4, 9 & 10, marked 3 notches on E. & S on S. Edges & mound mound of stone & ditch, from which A cedar 14 ins. dia. bears N. 15 E. 20 lks. Marked T 30 S. R. 9 W. S. 3. B. T.

Land mountainous, Soil & rate. Dense sage brush on 44 chs. No timber

East on random line bet. secs. 3 & 10 Var. 15° 30' E.

33.50 Station drains S.

37.50 Road Road bears N. & S.

Subdivisions T 30 S. R 9 W.

40.00	set temp. 1/4 sec. cor.	chains
42.50	Wash drains S.	
43.50	Telegraph line bears N 85 W.	
75.00	Holcom drains S. a creek	15.00
80.00	Intersect N.S. line at	40.00
	the cor. to secs. 2. 3. 9 & 10	
	from which	80.50
	Iron on true line	
	bet. secs. 3 & 10	
40.00	set Granite 8 x 12 x 10 ins,	
	12 ins. in the ground	
	for 1/4 sec. cor. Marked	
	1/4 on N. side, & raised	
	mound of stone along	
	side.	40.50
80.00	The cor. to secs. 3. 4. 9 & 10	
	Land Mountains,	
	Soil 2nd rate.	
	Timber	
	"	80.50

W. S. L. M.

chains North on random line
bet. secs. 3 & 4,
Var. 15° 15' E.

15.00 Stake in drains S. W.

40.00 set temp. 1/4 sec. cor. on
small circle bears N. & W.

80.50 Intersect S. boundary
of the Sp. 14 lks. W. of
the cor. to secs. 3 & 4,
which is a Limestone
2 x 6 x 5 ins. with stone
mound, from which
S. 0° 6' W. on true line
bet. secs. 3 & 4

40.50 set Granite 16 x 8 x 6 ins.
11 ins. in the ground for
1/4 sec. cor. marked 1/4 on
W. side & raised mound
of stone alongside.

80.50 The cor. to secs. 3, 4, 9 & 10.

Subdivisions of T 30 S., R. 9 W. S.

Chains	
	Land Mountainous
	Soil 2d. rate.
	Av Timber
	Oct. 12th 1881
	"
	43.00
	Oct. 13th 1881
	56.00
	80.00
	From the cor. to Secs. 32 & 33 on the South Boundary of the Tp. which is a Volcanic rock 20 x 16 x 4 ins. with a mound of stone along side & runs North Meb. Secs. 32 & 33
	Var. 15° 30' E.
	Ascend
10.00	Ridge bears N. W.
20.00	Wash down West
40.00	Opens Trachyte rock

W. S. L. M. 22

22 X 12 X 7 ins. 14 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on W side and raised a stone mound alongside.

43.00 Top of Ridge brs. E & W.

56.00 Mesh drns. West

8.00 Set a Trachyte rock R 20 X 12 X 9 ins. 14 ins. in the ground for cor. to 5 Secs. 28. 29. 32 & 33. marked with 1 notch on the South and 4 notches on the East edges with stone mound alongside.

Land Mountainous
Soil 3rd rate
Scattering Cedars.

Subdivisions Tp. 30 S R 9 W.

East on a random line
bet. Secs. 28 & 33
Var. 15° 30' E.

24.00 Wash drns. S. W.
40.00 Set temp. 1/4 Sec. Cor.
55.00 Top of Ridge bns. N. E. & S. W.
79.80 Intersect the N & S line
at cor. to Secs. 27. 28. 33 & 34 16.00
Ground which 33.00
West on a true line 40.00
bet. Secs. 28 & 33
39.90 Set a Trachyte rock
18 X 12 X 12 ins. 12 ins. in
the ground for 1/4 Sec. cor.
marked 1/4 on N. side 52.00
with a mound of stone 60.00
alongside. 80.00
79.80 The cor. to Secs. 28. 29
[illegible] 33.

S. L. N. 301

		Land Mountainous
		Soil 3rd rate
		Scattering Cedars.
		North bet. Secs. 28 & 29
		Var. 15° 30' E.
33 & 34	16.00	Wash drains West
	33.00	Top of Rocky Ridge
	40.00	Set a Trachyte 22 x 17 x 9
		ins. 14 ins. in the ground
		for 1/4 Secs. cor. marked
		1/4 on N. side, with
		stone mound alongside
		Ravine drns. N. W.
	52.00	Top of Ridge drns. N. W.
	60.00	Set a Trachyte 25 x 20 x
	80.00	20 ins. 16 ins. in the
		ground for cor. to Secs.

Subdivisions Tp. 30 S. R 9 W.

BOOK-

Sec. 20. 21. 28 & 29.
marked with 2 notches
on the S. and E ow the
E. edges with a low
mound alongside.
Land Mountainous
Soil 3rd rate
Scattering Cedars.

40.07

"

80.15

East on a random
line bet. Secs. 21 & 28.
Var. 15° 30' E.

10.00 Mark drns. N. W.
40.00 Set temp. 1/4 Sec. Cor.
80.15 Intersect the N & S. line
Set 6 lks. N. of Cor. to

T. 2 N. R. 3 W.

Secs. 21, 22, 27 & 28

from which

N. 89° 45' W. on a true line bet. Secs. 21 & 28

40.07 Set a Trachyte 17 x 15 x 11 ins 13 ins. in the ground, for 1/4 Sec. cor. marked 1/4 on the N. side, and raised a mound of stone along side.

80.15 A.L. cor. to Secs. 20, 21, 28 and 29

Land Mountainous

Soil 3rd rate

Scattering Cedars

Subdivisions T. 3 S. R 9 W

North bet. Secs. 20 & 21

Var. 15° 30' E.

10.00 Gulch drains N. W.

4.00 Top of Ridge bro. N. W.

Set Trachyte 15 x 12 x 10 ins. 11 ins in the ground for 1/4 Sec. cor. marked 1/4 on W side, and raised a mound of stone alongside

53.00 Gulch drains N. 30.00

56.00 Leave same drns N. E. 40.00

7.00 " " N. W. 80.30

8.00 Set a Trachyte 25 x 10 x 12 ins. 16 ins in the ground for cor to Secs 16, 17, 20 & 21 marked with 3 notches on the S. and for the E 40.15 edges, and raised a stone mound alongside

S. L. M.

Land Mountainous
Soil 3rd rate
Scattering Cedars

East on random line
bet. Secs. 16 & 21
Var 15° 30' E.

30.00 Wash drns. N. W.

40.00 Set temp. 1/4 Sec. cor.

80.30 Intersect N & S line 20
Chs. S of cor. to Secs.
15, 16, 21 & 22 from which
S. 89° 57' W on true line
bet. Secs. 16 & 21

40.15 Set Trachyte 17 x 12 x 10 ins
12 ins. in the ground for
1/4 Sec. Cor. marked
1/4 on N. side and raised

Subdivisions Tp. 30 S. R 9 W.

Chains		
	a mound of stone alongside	
80.30	The cor to Secs. 16. 17. 20 & 21	
	Land Mountainous	53.00
	Soil 3rd rate	
	Scattering Cedars.	80.00
	North bet. Secs. 16 & 17	
	Var. 15° 30' E.	
23.00	Top of Ridge bears N. W.	
40.00	in Gulch bears N. W.	
	Set Trachyte 18 x 12 x 10 ins.	
	12 ins. in the ground, for	
	1/4 Sec. Cor, marked same	
	1/4 on W face, and raised	
	a mound of stone alongside	
	from which	
	A Cedar 12 ins. in. dia.	14.20
	bears N. 16 1/4° E. 18 lks. dist	19.00
	A Cedar 10 ins. dia bears	35.00

S. 17½° W. 23 lks. dist.
Both marked 1 + S. B. T.

53.00 Top of Ridge
Lead Cedars.

80.00 Set Mahyle 20 x 12 x 4 ins
1 + ins. in the ground,
for cor. to Secs. 8. 9. 16 + 17
and raised a mound of
stone along side.
Land Mountainous
Soil 3rd rate
Cedars on ~~3~~ 3 chs.
(53)

East on random line
bet. Secs. 9 + 16.
Var 13° 30' E.

14.20 Top of Ridge brs. N + S.
19.00 Gulch dms. N. E.
35.00 Top of Ridge brs. N + S.

Sub-divisions Tp. 30 S. R 9 W.

39.75	Gulch dries N. E.	
40.00	Set temp. 1/4 Sec. cor.	
41.50	Top of Ridge bns. N. & S.	
54.50	Main Gulch dries North	
65.00	Top of Ridge bns. N & S.	
75.00	Wash dries. North	
80.12	Intersect N & S. line at cor to Secs. 9. 10. 15 & 16. from which Western trav line bet Secs. 9 & 16.	26.81 30.00 31.00
40.06.	Set a Volcanic rock 16 x 12 x 10 ins. 12 ins. in the ground, for 1/4 Sec. cor. marked 1/4 on N side, and raised a mound of stone alongside	35.00 40.00
80.12	The cor. to Secs. 8. 9. 16 & 17 Land Mountainous	

BOOK-A-175

S. L. M.

Soil 3rd rate
No timber.

North bet. Secs. 8 & 9
Var. 15° 30' E.

28.81	Fence brs. N. W. (Cave Mountains)
30.00	Corral and shed brs. East 1 ch. dist.
31.50	John Reed's house brs. East 2.50 chs dist.
35.00	Beaver Creek 50 lks. wide 2 ft. deep runs S. W.
40.00	Set Trachyte 20 x 20 x 12 ins. 14 ins. in the ground, for 1/4 Sec. Cor. marked 1/4 on W. side, and raised a mound of stone alongside

Subdivisions Tp. 30 S R 9 W.

46.25	Fence lies S. W.	
40.50	Road lies E & W.	
	Ascend	
42.00	Telegraph Line lies E & W.	15.00
78.00	Top of Butte.	19.75
80.00	Set Flint 14 x 8 x 6 ins.	40.00
	10 ins. in the ground for	41.50
	Cor. to Secs. 4. 5. 8 & 9	72.50
	Mark Red Knotches on S.	
	and for E. edges and	79.80
	raised a mound of stone	
	alongside.	
	Land Mountainous (60.3) 46.31 chs on	
	Soil 1st and 3rd rate	
	Timber.	39.90
		79.80

East on random line
bet. Secs. 4 & 9
Var. 15° 30' E.

15.00 Hollow drns. S. W.
19.75 Ledge of Granite rock N & S.
40.00 Set temp. 1/4 Sec. Cor.
41.50 Hollow drns. S. E.
72.50 — and Wash drns. S. W.
Road in wash N. E. & S. W.
79.80 Intersect N. & S. line
at Cor. to Secs. 3. 4. 9 & 10
from which
West 80 rds line bet
Secs. 4 & 9
39.90 Set Trachyte 14 X 10 X 10 ins.
10 ins. in ground, for 1/4
Sec. Cor. marked 1/4 on
N side, and raised a
mound of stone alongside
79.80 The Cor. to Secs. 4. 5.

Subdivisions T. 30 S. R 9 W.

8 & 9.
Land Mountainous.
Soil 2nd rate rocky
a few scattering Cedars

40.65

North on a random line
bet. Secs. 4 & 5
Var. 15° 30' E.

80.65

25.00 Small hollow drns. S. W.
40.00 Set temp. 1/4 Sec. Cor.
67.00 Hollow drns. S. W.
80.65 Intersect the North
Boundary of the Township
24 x 12 x 10 blaze stone 2.4 links W. of Cor. to Secs. 4 & 5, 9 with stone mound.
from which
South on true line
bet. Secs. 4 & 5

S. L. M.

80.65 Set Granite 20 x 12 x 12 ins. 14 ins. in the ground, for 1/4 Sec. Cor. marked Same 1/4 on W side. and raised a mound of stone alongside.

80.65 The Cor. to Secs. 4. 5. 8. & 9. Land Mountainous Soil Slate Scattering Cedars.

Oct. 13th 1881

Oct. 14th 1881

From the Cor. to Secs. 31 & 32 on the South Boundary of the Township which is a Volcanic rock 15 x 10 x 10 ins. with a

	mound of stone along side	
	from which I saw	
	North bet. Secs. 31 & 32	
	Var. 15° 30' E	
35.00	Wash drns. N. W.	
40.00	Set a Trachyte 12 x 12 x 10 ins.	
	9 ins. in the ground, for	
	1/4 Sec. cor. marked 1/4 on	
	W. face and raised a mound	
	of stone along side.	8.00
61.50	Head of Hollow drns. West	30.00
78.75	Top of Mountain bnrs. E & W.	34.00
80.00	Set a Trachyte 24 x 18 x 12	40.00
	ins. 16 ins. in the ground	48.00
	for cor. to Secs. 29. 30. 31 & 32	80.12
	marked with 1 notch on	
	the S. and 5 on the E. edges.	
	and raised a mound of stone	
	along side.	
	Land Mountainous	

Soil 3rd rate.
Scattering Cedars.

East on a random line
bet. Secs. 29 & 32
Var. 15° 30' E.

8.00 Wash drns. N. W.
30.00 Point of Ridge brs. N.
34.00 Head of Hollow drns. N.
40.00 Set temp. 1/4 Sec. cor.
48.00 Top of Ridge
80.12 Intersect N. & S. line 18 lks.
S. of cor. to Secs. 28. 29.
32 & 33. From which
cor. S. 89° 45' W. one
tree line bet. Secs.
29 & 32

40.06 Set a Volcanic rock 16x15x
10 ins. 12 ins in the ground
for 1/4 Sec. Cor. marked
1/4 on N side, and raised 4.50
a mound of stone alongside 21.00
from which 37.00
a Cedar 8 ins. in dia. brs. 40.00
N. 42 1/4° E. 25 lks. distant 53.00
a Cedar 18 ins. in dia. brs. 80.10
S. 31° W. 43 lks distant
Both marked 1/4 S. B. T.

80.12 The Cor. to Secs.
29. 30. 31 & 32.
Land Mountainous
Soil 3rd rate
Scattering Cedars

40.10

West on a random line
bet. Secs. 30 & 31
Var. 15° 30' E.

4.50 Toz. of Ridge brs. N. W.
21.00 Wash dries. N. W.
37.00 Toz. of Ridge & joint brs. N.
40.00 Set Temp. 1/4 Sec. Cor.
53.00 Wash dries. North
80.10 Intersect the West Boundary
of the Tp. 15 N. R. 9 W. of the
Cor. to Secs. 30 & 31
which is a [redacted] Granite
12 x 12 x 12 ins. with a stone
mound alongside from
which I run
N. 89° 54' E on true
line bet. Secs. 30 & 31
40.10 Set a Trachyte 20 x 14 x 12 ins.
14 ins. in the ground,
for 1/4 Sec. Cor. mar Red

	1/4 on N. side and raised	65.00
	a mound of stone alongside.	80.00
80.10	The Cor. to Secs. 29. 30. 31 & 32	
	Land Mountainous	
	Soil 3rd Rate.	
	Scattering Cedars	
	"	
	North bet. Secs. 29 & 30	
	Var. 15°30' E.	
27.00	Hollow and Road brs. N. W.	
36.50	Top of Ridge brs. N. W.	
40.00	Set Trachyte 18 x 10 x 10 ins.	
	12 ins in the ground	
	for 1/4 Sec. Cor. marked	
	1/4 on W side, and raised	
	a stone mound alongside.	
50.00	Wash draw. N. W.	

65.00
80.00

To 7 Ridge brs. E & W.
at Trachyte 18 x 12 x 4 ins.
12 ins in the ground,
for cor. to Secs. 19. 20.
29 and 30. marked
with 2 notches on the
S. and 3 on the E. edges.
From which
a cedar 6 ins. dia. brs.
N. 10° W. 40 lks. distant
marked T. 30 S. R. 9 W.
S. 19 B. T.
a cedar 12 ins. dia. brs.
N. 45° E. 30 lks. distant.
Marked T. 30 S. R. 9 W. S. 20 B.T.
a cedar 12 ins. dia. brs.
S. 16¼° W. 10 lks. distant
Marked T. 30 S. R. 9 W. S. 30 B.T.
a cedar 10 ins. dia brs
S. 18½° E. 8 lks. distant

Subdivisions T. 30 S. R. 9 W.

Chains		Chains
	mar Red T. 30 S. R. 9 W. S. 29 B.T.	
	Land Mountainous.	
	Soil 3rd rate rocky	
	Scattering Cedars.	
		79.90
	"	
	East on a random line	
	bet. Secs. 20 & 29	
	Var. 13° 30' E.	
2.00	Leave cedars.	
20.00	Enter "	
40.00	Set temp. 1/4 sec. cor.	
79.90	Intersect N. & S. line 14 lks.	
	S. of cor. to secs. 20. 21. 28 &	23.00
	29. from which	40.00
		50.00
		63.00
	S. 89° 54' W. on true line	
	bet. secs. 20 & 29	79.80
39.95	Set Trachyte stone 16 x 12 x	

S. L. M.

	Chains	10 lks. 11 mks. in the ground for 1/4 sec. cor. Marked 1/4 on N. side & raised a mound of stone along side.
	79.90	The cor. to secs. 19. 20. 29 & 30, Land Monuments, Soil & rate. Scattering cedars on 61.90 chs.
		"
		Mstr on random line bet. secs. 19 & 30 Var. 15° 30' E.
	23.00	Wash drains S W.
	40.00 50.00 63.00	Set temp: 1/4 sec. cor. Leave Timber Wash drns. N. E.
	79.80	Intersect the West Boundary of the Tp. 20 Ks. S. of cor

to Secs. 19 & 30 which is 79.80
a Trachyte 16 x 12 x 12 ins.
with a mound of stone along side
from which
a Cedar 16 ins. dia. bears S 57½° E.
15 lks. distant
a Cedar 16 ins. dia. bears N. 73° W.
31 lks. distant.
from which Corner
S 89° 52' E on true line
bet. Secs. 19 & 30
3.980 set a Trachyte 20 x 12 x 12 ins. 5.00
13 ins. in the ground, 20.00
for ¼ Sec. cor. marked 33.00
¼ on N. side, from which 37.00
a Cedar 14 ins. dia. brs. 40.00
S. 88° W. 60 lks. distant
a Cedar 14 ins dia. brs.
N 4° E. 12 lks. distant
Both marked ¼ S. B. 9.

	79.80	The cor. to Secs. 19. 20. 29 and 30.
		Land heavy rolling Soil 2nd rate
		Cedars on 50.00 chs.
		11
		North bet. Secs. 19 & 20 Var. 15° 30' E.
	5.00	Wash drns. West
	20.00	Top of Ridge brs. N. W.
	33.00	Wash drns. N. W.
	37.00	Ridge brs N. W.
	40.00	Set Trachyte 18 x 12 x 10 ins. 12 ins. in the ground, for 1/4 Sec. Cor. marked 1/4 on W. side and raised a mound of stone alongside

Chains		
	No trees near cor.	
45.00	Wash drns. N. W.	
62.00	Head of Hollow drns. W.	
72.50	Top of Ridge Leave Cedars.	12.00
80.00	Set a Trachyte 22 x 11 x 7 ins.	18.00
	14 ins. in the ground,	25.00
	for cor. to Secs. 17, 18, 19 & 20	40.00
	marked with 3 notches	70.00
	on the E. and 3 on the	80.15
	E. edges and raised a	
	Stone mound alongside	
	Land Mountainous.	
	Soil 3rd rate rocky	40.07
	Scattering Cedars. on 72.50 ds.	

East on a random
line bet. Secs. 17 & 20
Var. 15° 30' E.

W.
dars.
nis.
y
17 & 20
tes
the
d
ride
ky
do.

12.00 Wash drns. S. W.
18.00 Top of Ridge bears N. E.
25.07 Wash drns. S. W.
40.00 Set Temp. 1/4 Sec. Cor.
70.00 Wash drns. N. W.
80.15 Intersect N. & S. line at
cor. to Secs. 16, 17, 20 & 21
from which West 20
True line bet. Secs. 17 & 20
40.07 Set Trachyte 20 x 12 x 10 ins.
13 ins. in ground, for
1/4 Sec. Cor. from which
a Cedar 8 ins. dia. bears
N. 10° W. 23 lks. distant
a Cedar 12 ins. dia. bears
S. 40° E. 50 lks. distant
Both marked 1/4 S. B. T.

80.15	The cor. to Secs. 17. 18. 19 & 20	72.00
	Land Mountainous	79.60
	Soil 3rd rate	
	Scattering Cedars	
		39.60
	West on a random line	
	bet. Secs. 18 & 19	
	Var 15° 30' E.	79.60
6.00	Point of Ridge bears S.W.	
18.00	Wash draw. S.W.	
28.00	Rocky point of Ridge bears S.W.	
33.00	Head of hollow draw W.	
40.00	Set temp. 1/4 Sec. cor.	
43.00	Wash draw W.	
58.00	Top of Ridge bears S.W.	

BOOK-A-175

72.00	Wash drns. S. W.
79.60	Intersect the West Boundary of the Pp. 43 Lks. N. of Cor. to Secs. 18 & 19 which is a Granite 16 x 12 x 4 ins. with M & P. from which I run N 89° 42' E on true line bet. Secs. 18 & 19
39.60	Set Trachyte 18 x 10 x 10 ins. 12 ins. in the ground marked 1/4 Sec. Cor. N. side for 1/4 Sec. Cor. and raised a mound of stone alongside.
79.60	The Cor. to Secs. 17. 18. 19 and 20.

Land Mountainous and rolling

Soil 3rd rate

Dense Sage & Oak brush

North Lat. Secs. 17 & 18

Var. 15°30' E.

28.00	Wash drns. S. W.	
40.00	Set Volcanic rock 20 x 12 x 4 ins. 13 ins. in the ground for 1/4 Sec. cor. marked 1/4 on W side and raised a mound of stone alongside.	
53.00	Top of Ridge brs. S. W.	
72.00	Road in Wash brs. West	15.50
75.00	Point of Ridge brs. S. W.	27.00
97.00	Wash drns. S. W.	33.00
80.00	Set a Trachyte 18 x 18 x 12 ins.	40.00
	12 ins. in the ground, for	48.50
	cor. to Secs. 7, 8, 17 & 18.	55.00
	marked with 4 notches	65.00
	on the S. and 3 on the E.	74.50
	edges and raised a mound	80.00
	of stone alongside.	

Land Mountainous
Soil 3rd rate
No timber

East on a random line
bet. Secs. 8 & 17
Var. 15° 30' E.

15.50	Wash drns. N. W.
27.00	Top of Knoll
33.00	Wash drns. S. W.
40.00	Set temp. 1/4 Sec. Cor.
48.50	Top of Divide bears N & S.
55.00	Gulch drns. East
65.00	Leave same drns. N. Ea
74.50	Top of Ridge
80.00	Intersect N & S. line at cor. to Secs. 8. 9. 16 & 17. From which I run

Chains.		
	West on true line	40.00
	bet. Secs. 8 & 17	48.25
40.00	Volcanic rock 20x12x12 ins,	58.50
	13 ins. in the ground, for	80.00
	1/4 Sec. Cor. marked 1/4	
	on N side, and raised a	
	mound of stone alongside.	
80.00	The Cor. to Secs. 7, 8, 17 & 18	
	Land Mountainous	
	Soil 3rd rate	
	No Timber.	40.00

a

	West on random line	
	bet. Secs 7 & 18	80.00
	Var 15° 30' E.	
15.00	Top of Ridge Trees N. & S.	
23.50	Wash Trees N. & S.	

S. L. M.

40.00 Set temp ¼ Sec. Cor.

48.25 Track drains N W.

58.50 " " "

80.00 Intersect West boundary of the Sp. at the cor. to Secs. 7 & 18, which is a Gray Sandstone 17 x 7 x 5 ins, from which East on the line bet. Secs. 7 & 18

40.00 Set Quartzite stone 18 x 10 x 8 ins. 12 ins. in the ground for ¼ sec. cor. marked ¼ on N. side & raised mound of stone along side.

8.00 The cor. to Secs. 7, 8, 17 & 18, Land Immediately, Soil 2d rate. No Timber

Subdivisions T. 30 S. R. 9 W.

chains		chains
	Stock let. sec. 7 & 8	
	Var. 15.30 E.	65.60
6.00	Nash drains N W.	70.00
5.50	Ridge bears N W & E	71.50
9.50	Nash drains W.	
25.50	Ridge E & W.	75.00
23.50	Ranie drains W. 1 ch. Thick	80.00
32.00	Ridge E & W.	
40.00	On W. slope of Ridge; set a Sandstone 24 x 20 x 10 ins. 18 ins. in the ground for 1/4 sec. cor. Marked 1/4 on W. side & mound of stone alongside, from which	
	Cedar 10 ins. dia. bears S. 47 1/2° W. 97 lks. Marked 1/4 S. B. J.	
64.40	Lepre valley South bank of Miniswild Reservoir, made by damming the Beaver River; a	

BOOK-A-175

S. L. M.

chains	Bridge bears N. about 10 lks,
65.60	N. side of Reservoir, chains W.
70.00	Telegraph line bears E. & W.
71.50	Road to Beaver City & Illinois-
	ville bears E & W.
75.00	Mt. Point of Ridge -
80.00	Set Limestone 20 x 10 x 6 ins,
	15 ins, in the ground for
	cor. to secs. 5. 6. 7 & 8,
	Marked 5 Notches on E. & S.
	Edges & rough mound of
	stone alongside,
	Land Immaterial,
	Soil & Date.
	Timber.

Subdivision T. 30 S. R 9 E

4 chains	East on random line	75.00
	Cor. Sec. 5 & 8	80.00
	Var. 15° 30' E.	
	Ascend	
2.06	Rocky ledge bears N & S.	
12.50	S. Point of rocky ridge. Old	
	Summit Mine Prospect	40.00
8	Dump bears N 70 E. 10 chs.	
	Old stone Brewery bears S.	
	25° E. Descend S. slope.	
33.50	Same Brewery bears S 28°	
	30' W. West end of Rees	80.00
	field bears S 26° E.	
39.25	Road to Lime Kiln N & S.	
41.00	In hollow drains S. set temp.	
	¼ sec. cor.	
50.00	small Ravine drains SW.	
55.00	West End of Rees field	
	bears S. 2 W.	
59.00	Wood road in hollow SW	

R 9W

S. L. M.

line 75.00 Station Mound S.W.
5 80.00 Intersect N.S. line at
E. the cor. to Secs. 4, 5, 8 & 9
from which
Mat on the line
bet. Secs. 5 & 8
Ash Sunstone 14 x 10 x 6 ins.
Sect 40.00 10 ins. in the ground for
chs. W. Sec. cor. Marked 14 on
ars S. N. side & mound
Sec 28 of Stone alongside.
28 The cor. to Secs. 5, 6, 7 & 8.
ces 80.00 Land Monuments
Soil & rock.
N.S. No Timber.
temp
"
SW.
ied
SW

Subdivisions T 30 S. R 9 W

Chains		Chains
4.	West on random line bet. Secs. 6 & 7, Var. 15° 30' E.	40.25
	Descend.	
30.00	Road bears N W & S E, at foot of hill, & enter Valley & Sage Brush.	
8 4.25	Wash drains SE.	
26.50	" " "	79.50
35.25	" " " S.	
39.25	Fluid oed & stone -	
41.50	S. point of small hill	
78.00	Road to Lincoln N & S.	
79.50	Intersect west boundary of the T. 30 S., South of the cor. to secs. 6 & 7, which is a Cobble stone 20 x 6 x 5 ins. from which (in order to reach the old & true cor.) I run	

BOOK-A-175

S. L. M.

Chains	S. 87° 39' E. on true survey line bet. Secs. 6 & 7,
40.25	To the old ¼ sec. cor., which is a Blue Limestone 24 × 12 × 6 ins.
	I now run East on true line 39.25 chains to
79.50	The cor. to secs. 5, 6, 7 & 8, Land Mostly rolling valley, soil 2d rate. Dense Sage brush on 76.50 chs.
	Set Meander.

Subdivisions T. 30 S. R 9 W.

4 Chains		North on random	80.65
		bet. secs. 5 & 6,	
		Var. 15° 30' E.	
20.00		Small hollow drains SW.	
40.00		Set temp. 1/4 sec. cor.	
60.00		Hollow drains SW.	
80.65		Intersect N. boundary of	
&		the Sp. 25 lks. W. of the	
		cor. to secs. 5 & 6, whence	
		a Sandstone 15 x 9 x 6 ins,	
		mkd. Pits & Mound, bears	
		which	
		S. 0° W. N. on true line	
		bet. secs. 5 & 6.	
90.65		Set Granite 20 x 15 x 6 ins,	
		15 ins. in the ground for	
		1/4 sec. cor. Marked 1/4 on	
		N. side & raised a	
		Mound of stone along	
		side.	

BOOK-A-175

S. L. M.

80.65

The cor. to Secs. 5, 6, 7 & 8
Land Mountains,
Salt Lake,
Territory.
Oct. 11th 1881.

"

BOOK

General Description

This township contains some good farming land in Beaver Canon, in which there are several settlements. The balance of the Tp. lies in the mountains covered with cedar & Pinon pine timber. In tp the W ½ of Sec. 5 is Mineral land containing silver.

T. C. Bailey
U. S. Dep. Surv.

248

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, Oct 4th 1881.

The foregoing field notes of the survey of the

West & North Boundaries

of

Township No 30 S. Range No 9 W.

of the Salt Lake Meridian, Utah Territory,

Executed by F. C. Bailey

Under his contract No 102

of the 24 day of May 1881,

in the month of July 1881,

having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.

Fred. Salomon

U. S. Surveyor General for Utah.

BOOK-A-1/5

13

352

R: 1882.

Filed 187 .

Examined by John H. Campe.

Compared by F. Linton & Ed. Michaelis

FIELD NOTES

OF

THE SURVEY OF THE

Additional

Subdivisions

of Township No. 30 S., Range No. 9 W

26

of the Salt Lake Meridian in Utah Territory.

BY

J. C. Bailey

U. S. DEPUTY SURVEYOR,

Under his Contract No. 102

dated May 27th 1881.

Survey commenced October 10th 1881.

Survey completed October 14th 1881.

Subdivisions 130 S.R. 9 W.

Note.— Having run the Exterior Boundaries of this Township under my regular Contract No. 10 last July I deem it useless to put the Government to the expense of retracing those lines.—

Survey commenced Oct. 10th 1881, with a Burts Solar Compass which I tested on a Meridian obtained from an observation on the Star Polaris, and found correct.

Begin at the Stone Cor. to Secs. 35 and 36, on the South Boundary of the Tp, which is the 6th Stan. South which is a Stationary Vulcanic rock 40 x 40 x 40 in. with a stone-mound.

Subdivision T 30 S. R. 9 W.

From which
North bet. Secs. 35 & 36
Var. 15° 30' E.

29.00 Top of Ridge N W & S E
40.00 Set a Trachyte rock 13 x 12 x 10 in. 9 in. in the ground for 1/4 Sec. Cor. marked 1/4 on W side and raised a mound of stone along side.
45.00 Wash drains N E.
80.00 Set a Trachyte rock 18 x 15 x 10 in. 12 in. in the ground, for Cor. to Secs. 25. 26. 35 & 36. marked 1 notch on E and S edges and raised a mound of stone along side.

Land Mountainous
Soil 3rd rate
Heavy Oak brush.
Scattering cedars.

6.00
40.00
56.00
80.00
40.00

BOOK-A-175

S. L. Mt.

East on random line
bet. Secs. 25 & 36
Var. 15° 30' E.

6.00 Head of hollow drns N. E.

40.00 Set Comp. ¼ Sec. Cor.

56.00 Ravine drs. N E.

80.00 Intersect E. Bd. of the Tp.
at the cor. to Secs. 25 & 36
which is a Granite stone
20 x 12 x 10 in. with a stone
mound. from which
A Cedar 14 in. dia. brs. N. 33° 15'
E. 15 lks. distant
A Cedar 16 in. dia. brs. S. 20° W.
40 lks. distant. both properly
marked.]
from which
West on a true line
bet. Secs. 25 & 36.

40.00 Set a Trachyte stone
18 x 15 x 10 in. 12 in. in the

Subdivisions T. 30 S. R. 9W

ground, for 1/4 Sec. cor. marked 1/4 on N. side, and raised a mound of stone along side.

80.00 The cor. to Secs. 25. 26. 35 & 36.

Land Mountainous
Soil 3rd rate
Scattering cedars.

North bet. Secs. 25 & 26.
Var. 15° 30' E.

5.00 Top of ridge brs. N. E.

20.00 Ravine drns. N. E.

40.00 Set a Trachyte stone 20 x 12 x 10 in. 13 in. in the ground for 1/4 Sec. cor. mar 1/4 on W. face, and raised a stone mound along side.

3741

A list of the names of the individuals employed by T. C. Bailey United States deputy surveyer, to assist in running, measuring, and marking the lines and corners described in the foregoing field notes of the survey of subdivision lines of Tps. 7 & 8 S. R. 14 & 15 W. - 37 S. R. 15 & 16 W & 18 W. 36 S. R. 18 W & 30 S. R. 9 W.

of the Salt Lake base and meridian in the Territory of Utah, showing the respective capacities in which they acted.

Frank Gorlinski, Compassman.

George Burk, Chainman.

Williams Billingsley, Chainman.

Benjamin Banks, Chainman.

Edwin Minchey, Chainman.

George Epps, Axeman.

Frank Roberts, Axeman. and

....., Flagman.

BOOK-A-175 358

[5.—FINAL OATHS OF ASSISTANTS.]

We hereby certify that we assisted T. C. Bailey United States deputy surveyor, in surveying all those parts or portions of the Subdivisions of Tps. 38 S. R. 14 & 15 W. & 37 S. R. 15. 16. 17 & 18 W. & 36 S. R. 18 W. & 30 S. R. 9 W.

of the Salt Lake base and meridian in the Territory of Utah, as are represented in the foregoing field notes as having been surveyed by him and under his direction; and that said survey has been in all respects, to the best of our knowledge and belief, well and faithfully surveyed, and the corner monuments established according to the instructions furnished by the United States surveyor-general for Utah.

Frank Gorlinski, Compassman.

Geo. Geo Beck, Chainman.

Wm Wm Bullock, Flagman.

Benjamin Bangs, Chainman.

Nelson Mundey, Chainman.

....., Axeman.

George Eppe, Axeman.

Peter Frank Roberts, Flagman. and Axeman

Subscribed and sworn to before me this 15th day of Oct. 1881

Wm Wood

Justice of the Peace

in and for Minersville Precinct

Beaver Co. Utah.

BOOK-A-175

[6.—FINAL OATH OF UNITED STATES DEPUTY SURVEYOR] 359

I, F. C. Bailey 3rd, United States deputy surveyor, do solemnly swear that in pursuance of instructions received from Fred. Salamun United States surveyor general for Utah, bearing date of the 27th day of May, 188/, I have well, faithfully, and truly, in my own proper person, and in strict conformity with the instructions furnished by the United States surveyor general for Utah, the surveying manual, and the laws of the United States, surveyed all those parts or portions of the subdivision lines of Townships 38 S. R. 14 & 15 W. 37 S. R. 15. 16. 17 & 18 W. 36 S. R. 18 W. & 30 S. R. 9 W.

of the Salt Lake base and meridian in the Territory of Utah, as are represented in the foregoing field notes as having been surveyed by me and under my directions; and I do further solemnly swear that all the corners of said survey have been established and perpetuated in strict accordance with the surveying manual, printed instructions, the special written instructions of the United States surveyor general for Utah, and in the specific man-

ner described in the field notes, and that the fore-
going are the TRUE field notes of such survey,
and, should any fraud be detected, I will suffer
the penalty of perjury, under the provisions of an
act of Congress, approved August 8, 1846.

Thomas C. Bailey
United States Deputy Surveyor

Subscribed and sworn to before me this 11
day of Dec. 1881

Edward Michaelis
U.S. Surv. Gen

3 x 5

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, March 15, 1882

The foregoing field notes of the survey of the

Additional Subdivisions

Township No 30 S. Range No 9 W.

of the Salt Lake Meridian, Utah Territory,

Executed by J. C. Bailey

Under his contract No 102

of the 27th day of May 1881,

in the month of October 1881,

having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.

Fred. Saltzer

U. S. Surveyor General for Utah

581.

BOOK-A-175
R: 1882

362

Filed 187 .

Examined by A. Gorlinski

Compared by A. Gorlinski & E. Archadis

FIELD NOTES

OF

THE SURVEY OF THE

and Re-Survey

East & Survey of West boundaries

of Township No. 31 S., *Range No.* 8 W.,

of the Salt Lake Meridian in Utah Territory.

BY

P. C. Bailey

U. S. DEPUTY SURVEYOR,

Under his Contract No. 102

dated May 29th 1881.

Survey commenced Aug 11th 1881.

Survey completed " 14th 1881.

BOOK-A, 175

Re-Survey of a portion of East Boundary T. 31 S. R. 8 W.

363

Note:

I commence the survey on Augt. 11th 1881 with a Burts improved Solar compass, tested this morning & found correct- As two miles of this line have been previously run, I run a blank line North from the Cor. to T. 31 32 S. R. 7 8 W, (re-established by me ~~yesterday~~ today in the re-survey of 3½ miles of the Range line south of said corner,) and find no old corners standing on the said two miles of old survey, I therefore find it necessary to re-survey the same, and begin at the said

Re-survey
East boundary T. 31 S. R. 8 W.

chains

Township cor. to T. 31 & 32 S.
R. 7 & 8 W. and run
North on a re-survey line
bet. Secs. 31 & 36
Var. 15° 35' E.

40.00 Old stone lying loose 15 links
West of line; I re-set same
on line viz: A conglomerate
stone 12 x 10 x 5 ins. 8 ins. in the
ground for re-established
1/4 sec. cor. Marked 1/4 on
W. side, dug pits. 18 x 18 x
12 ins, N & S. of stone 5 1/2 ft.
dist. & raised Mound of
Earth 1 1/2 ft. high 3 1/2 ft.
base alongside.

80.00 Old stone not found;
Set Lava rock 14 x 12 x 8 ins,
10 in. in the ground, for
re-established cor. to secs

32.0

40.0

59.5

25 30, 3 / 936, Marked 5 Notches,
on Aff 4 on South Edges, & raised Mound of stone alongside.
Land level — Soil 1st rate,
Sage brush undergrowth.

"

North on Re-survey line
bet. Secs. 25 & 30
Var. 15° 35' E.

32.00 Foot of Mountains bears N & W,
Entire scattering cedars & Aspens

40.00 Old stone not found — Set
a standstone, 14 x 12 x 6 ins,
10 ins, in the ground for
¼ Sec. cor. Marked ¼ on
N. side & raised Mound
of stones alongside, from which
a Pine 12 ins. dia. bears N. 75° W. 30 lks,
Marked ¼ S. B. T.

59.50 Gulch drains E.

Re-survey 1870.

East boundary T. 31 S., R. 8 W.

		East chains
80.00	Old stone not found. Set a granite stone 15 x 10 x 10 ins, 10 ins. in the ground for re-established cor. to secs. 19, 24, 25 & 30, marked 4 notches on N. & 2 on S. Edges & raised mound of stones alongside, in hollow drains &c. Land Mountains on 48 chs Soil 2d rate.	
	Timber scattering cedars on N. 48 chs.	
	Note. End of Re-survey.	
	"	

24.5
40.0
74.0
80.0

New Survey
East Boundary T. 31 S. R 8 W. S.L.M.

Chains	
	North on true line bet. Secs. 19 & 24 Var. 15° 35' E
24.50	Hollow 5 lks wide, drains NE.
40.00	Set Granite stone 14 x 10 x 8 ins. 10 ins. in the ground for 1/4 Sec. cor. Marked 1/4 on N. side, & raised Mound of Stones alongside.
74.00	Middle of Hollow drains NW.
80.00	Mark a Stationery Lava Rock 4 x 2 x 2 ft. above ground, for cor. to secs. 13, 18, 19 & 24, Marked with a cross at corner point, and with 3 notches on N & E Edges & raised a Mound of Stone alongside on N. Side of hollow. Land Mts. Soil 2d rate.

East boundary T. 31 S R 8 W.

Chains Timber Cedar & Pitch Pine.

"

North bet. Secs. 13 & 18
Var. 15° 35' E.

40.00 Set Granite stone 14 x 10 x 8 ins. 10 ins. in the ground for 1/4 Sec. cor. Marked 1/4 M W side & raised a mound of stone alongside.

53.00 Enter small valley ins Mts. bears E & W.

62.75 Wash drains S E,

80.00 Set Granite 14 x 8 x 6 ins. 10 ins. in the ground for cor. to Secs. 7, 12, 13 & 18, Marked 2 notches on N. & 1/4 on S. Edges, & raised a mound of stone alongside.

40.00

80.00

BOOK-A-175

S. L. M. 358

Land mountainous on 53. chs.
Soil 2d rate.
Bal. Rolling valley—
Scattering cedars & Pitch pine.

"

North on true line
bet. Secs. 7 & 12
Var. 15° 35' E.

40.00 Set Sandstone 14 x 7 x 6 ins,
10 ins. in the ground for
1/4 sec. cor. Marked 1/4 on
W. side, dug pits 18 x 18 x 12 ins
N & S of stone 5 1/2 ft. dist, &
raised mound of Earth
1/3 ft. high 5 1/2 ft. base along
side.

80.00 Set Sandstone 14 x 6 x 5 ins,
10 ins in the ground, for cor.

East boundary T31 S. R. 8 W.

Chains to Secs. 1, 6, 7 & 12, marked
1 notch on N. & S on South
edges, dug pits 18×18×12
ins, in each sec. 5½ feet
dist, & raised mound of
earth 2 ft. high 4½ ft. base
alongside. 58.00
Land Rolling Valley 85.60
soil 2d rate.
Timber scattering cedars
& Piñon Pine.

"

North bet on the line
bet. Secs. 1 & 6
Var. 15° 35' E.

31.50 Small rock S.W.
40.00 Set Sandstone 14×8×5 ins,
10 ins, in the ground, for

S. L. M.

1/4 Sec. cor. Marked 1/4 on N. side, dug pits 18x18x12 ins, N&S of stone 5 1/2 ft. dist, & raised Mound of Earth 1 1/2 ft. high 3 1/2 ft. base, alongside.

58.00 Leave Valley bears E & W. Azm

85.60 Intersect 6th standard Parallel South 23.27 chs West, of the standard cor. to T. 30 S., R. 7 & 8 W. which is a "Granite Rock 24x10x10 ins, with mound of stone alongside". Set a Granite stone 15x7x7 ins. ins. deep for standard closing corner to T. 31 S., R. 7 & 8 W., Marked C.C. with 6 notches on S. E & W. edges with mound of stone alongside.

Land Mts, on N. 22. chs.

372

Balance swelling Valley –
Soil 2d rate.
Timber Scattering cedar.
Aug 11th 1881.

"

Chains

750

750

38.75

40.00

West Boundary T. 31 S.

R. 8 W. S.L.M.

Chains

Survey commenced Aug. 14th 1881, by a Burts improved solar compass which I previously tested on my meridian pickets & found correct.

7.50 I begin at the estab lished cor. to T. 31 & 32 S., R. 8 & 9 W., set by me on the 12th inst, and run North bet. Secs. 31 & 36 Var. 15° 30' E.

7.50 Hollow drains S.E.

38.75 " " N.W.

40.00 Set Granite 14 x 10 x 6 ins, 10 ins. in the ground for 14 sec. cor. Marked 14 on

West boundary T. 31 S. R. 8 W.

Chains	on W. side, mich. mound of stone alongside.	Chains
	From which	
	A Pine 14 ins. dia. bears N 80 E. 55 lks.	34.50
	Marked "T. 8. R. 8."	40.00
56.25	Road bears NW. W.C., in a hollow drains SW.	
56.50	Bank in same " "	
80.00	W.C. side of small hollow drains S.C., set a Granite 15 x 6 x 6 ins., ramis, in the ground for cor. to secs. 25, 30, 31 & 36	43.00
	Marked 5 notches on N. & W. on S. Edges & raised Mound of Stone alongside.	55.50
		65.50
		80.00
	Land Mountainous Soil 2d rate, Timber Cedar & Pine,	

Mains	North bet. Secs. 25 & 30, Tan. 15° 30' E.
	Scribed.
34.50	Leave cedars N & W,
40.00	set Lava stone 14×10×8 ins, 10 ins. in the ground for 1/4 sec. cor. Marked 1/4 on N. side & scribed a mound of stones along side.
43.00	Large Lava Rock on line,
55.50	Lava ledge E & W.
65.50	Top of high Mt divide E & W. under rolling grass hills.
80.00	set Granite 14×8×6 ins, 10 ins. in the ground for cor. to Secs. 19, 24, 25 & 30, Marked 4 notches on N. & 2 on S. Edges & scribed mound of stone alongside.

West Boundary T. 31 S R 8 W

chains	Earth 1½ ft. high 3½ ft base along side.	32.00 40.00
43.00	Shallow drains NE.	
80.00	Set Granite 14 × 8 × 6 ins. 10 ins. in the ground for cor. to secs. 7, 12, 13 & 18, Marked 2 notches on N. & E on S. edges	55.50
	dug pits 18 × 18 × 12 ins, in	
	Each sec. 5½ ft. dist. &	68.50
	raised mound of earth 2 ft.	80.00
	high 4½ ft. base alongside.	
	Land rolling hills on top	
	of mountains.	
	Soil 2d rate.	
	No timber — Sage brush.	

Witness Cor. Secs. 7 & 12
Var 15° 30' E.

1.50	Shallow drains NE

BOOK-A-175

S. L. Mr.

32.00 Hallow drains N

40.00 Set Granite stone 14 x 8 x 6 ins, 10 ins. in the ground for ¼ sec. cor. Marked ¼ on N. side, & raised Mound of stone alongside

55.50 Hallow drains N. Crown S. Slope of rocky Mt.

68.50 Top of Same bears N & S.

80.00 Set Granite 18 x 11 x 8 ins, 12 ins. in the ground for cor. to secs. 1. 6. 7 & 12 Marked 1 notch on N. & 5 on S. Edges, & raised Mound of stones alongside

Land Mountains & Rolling hills

Soil 2d rate.

Cedar & Pine on South Slope of Mt.

West boundary T. 31 S., R. 8 W. S.

North bet. Secs. 1 & 6
Var. 15° 30' E.

19.75 Hollow drains E.
25.00 Enter cedars bear E & W.
35.00 Leave same N. & S.
141.90 Set Granite stone 16 x 8 x 5 ins.
11 ins. in the ground,
for 1/4 sec. cor. Marked
1/4 on W. side, & raised
mound of stones along
side.
54.50 Enter oak brush on side of
hollow.
56.50 Leave same bears E & W.
59.50 Hollow drains S.E.
87.39 Intersect 6th standard
parallel South 19.50 chs.
West of standard cor. to
T. 30 S. R. 8 W. for cor. set a

N. S. L. M.

Granite stone 18 x 10 x 10 ins
12 ins. in the ground for
standard
Closing corner to T. 31 S. R.
8 & 9 W. Marked C. C, with
6 notches on E. & W. Edges,
& raised Mound of stone
alongside.
Land Mountainous -
Soil 2d rate.
Some cedars, pine & Mah-
ogany.

Aug 14th 1881

"

BOOK-A-175

366

General Description

The townships lying East of this line has been ~~thoroughly~~ partly subdivided— The one lying on the west lies in the foot hills & mountains dividing the Beaver & Panvan valleys. It contains cedar & Piñon pine timber, and one settlement at "Pow Wow" Spring near the center of the township. It can all be subdivided but will require more labor & time than is usually required in the subdivision of an average T.p. of land.

J. C. Bailey
U. S. Dep. Sur.

BOOK-A-175

367

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, Dec. 19th 1881

The foregoing field notes of the survey and re-survey *of the*

East, & Survey of the West boundaries of

Township No 31 S. *Range No* 8 W.

of the Salt Lake Meridian, Utah Territory,

Executed by J. C. Bailey

Under his *contract No* 102

of the 2nd *day of* May 1881,

in the month of Aug 1881,

having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.

Jd. Salomon

U. S. Surveyor General for Utah.

BOOK-A-175 15 384

R. 1882

Filed 187 .

Examined by R. Gorlinski

Compared by R. Gorlinski & E. Michaelis

FIELD NOTES

OF

THE SURVEY OF THE

South & West Boundaries

28 *of Township No.* 3 S. , *Range No.* 9 W.

of the Salt Lake Meridian in Utah Territory.

BY

T. C. Bailey

U. S. DEPUTY SURVEYOR,

Under his Contract No. 102

dated May 29th 1881.

Survey commenced Aug 15th 1881.

Survey completed " " 1881.

Squith

Boundary T. 31 S. R. 9 W.

Survey commenced Augs. 1881 by a Burts improved solar compass, which I tested on my meridian line, and found correct.

I begin at the cor. to Tps. 31 & 32 S. R. 9 & 10 W. Viz: A Granite 24 x 14 x 4 ins, with mound of stones & run

East on a random line between said townships setting temporary corners at 40 & 80 chs and at 5 miles 1 chain 88 links I intersect the East boundary of the township 70 links south of the cor. to Tps 31 &

South Boundary T. 31 S. R. 9 W.

32 S. R. 8 & 9 W, the		
corrected mile thereon	12.00	
be for the true line 11 2/3	20.00	
links N. & 1.88 E. per	24.00	
mile, and the course	35.00	
S. 89. 55' W.	40.00	
From the Township cor. to		
T. 31 & 32 S. R. 8 & 9 W. Viz:		
A Granite stone 20 x 8 x 6		
ins, from which		
A Pine 4 ins. dia. brs. S 20 W. 20 lks		
" " 12 " " " S 78 E. 40 "		
" " 18 " " " N 12 W. 45 "		
" Cedar 8 " " " S. 60 E. 25 "	50.80	
all properly marked,	65.00	
I run	69.80	
S. 89° 55' W. on the line	72.00	
bet. secs.	79.00	
1736,	80.00	
Var. 15° 35' E.		

W. S. L. M. 3rd

		Descend in cedars.
	12.00	Wash drains E.
1 1/3	20.00	Top of Knoll.
	27.00	Wash drains S E.
	35.00	Top of Knoll
	40.00	On N. slope set a Trachyte
		stone 15 x 12 x 6 ins., 10 ins.
		in the ground for 1/4
		cor. marked 1/4
		on N. side, from which
		A Piñon 20 ins. dia. bears S 25 E. 20 lks
		" " 30 " " " S 85 E. 40 lks.
		Both trees marked 1/4 S. B. T.
	50.80	Wash drains S W. Ascend
	65.00	Top of Ridge point, descend,
	69.80	Wash drains S E. ascend
	72.00	Top of Ridge point.
	79.00	Wash drains S E. ascend
	80.00	Set Trachyte stone 18 x 12 x 8
		ins. 12 ins. in the ground

South Boundary T. 31 S. R. 9 W.

for cor. to secs. 1, 2, 35 & 36	20.00
Marked 1 notch on E & W sides, Edges, & raised mound of stones alongside, from which	40.00
A Pinon 8 ins. dia. brs. S 10½ E. 50 lks.	
Marked T. 32 S. R. 9 W. S. 1 B. T.	
A cedar 12 ins. dia. brs. S 71½ W. 20 lks.	
Marked T. 32 S. R. 9 W. S. 2 B. T.	
A Cedar 8 ins. dia. brs. N 43¼ W. 50 lks.	40.50
Marked T. 31 S. R. 9 W. S. 35, B. T.	45.50
Land Mountainous —	59.00
Soil 2d rate,	
Cedar & Pine timber.	67.50
	73.50
	80.00
S. 89° 55' W. on a true line bet. secs. 2 & 35 —	
Leave timber	
Cors. 15° 35' E.	
10.00 Ridge point — descend.	

9 M. S. L. M. 372

20.00 Wash drains N.

40.00 Head of hollow drains N.W. Set Trachyte stone 15×8× 7 ins. 10 ins. in the ground for 1/4 secs. cor. Marked 1/4 on N. side, & mound of stones alongside. Ascend.

40.50 Top of Divide N.W.S. descend.

45.50 Wash S.W.

59.00 Top of high mountains N.W.S. Descend.

67.50 Wash drains S.W. Ascend

73.50 Top of Ridge, Descend

80.00 Head of hollow drains N.W. Set Trachyte stone 16×10×4 ins. 11 ins in the ground for Cor. to secs. 2.3.34 & 35. Marked 2 notches on E.

South Boundary T. 31 S. R. 9 W.

chains and 4 on N. Edge of a raised mound of stones alongside.
Land Mountainous
Soil 2d rate.
No timber. 80.00

"

S. 89° 55' W. on a true line
Dec. Reco. 8 W 34.
Var. 15° 55' E.

2.50 Ascend
4.00 Top of divide, Descend
4.50 Enter cedars.
17.50 Foot of hill
40.00 Set Quarter 15 x 8 x 7 ins.
10 ins. in the ground
for 1/4 sec. cor. marked
1/4 on N. side from

R. 9W. S.L.M. 334

which
A cedar 10 ins dia. brs. N 50 E. 20 lks.
" " 14 " " " S 30 W. 10 "
Both trees marked 1/4 S. B. T.
Ascend on S. side of Ridge
80.00 On S. slope = Set a
Trachyte stone 16 x 12 x 8 ins.
11 ins. in the ground for
Cor. to secs. 3, 4, 33 & 34,
Marked 3 notches on E &
W. Edges from which
A cedar 16 ins. dia. brs. S 10 E. 70 lks
Marked T 32 S. R. 9 W. S 3. B. T.
A cedar 12 ins. dia. brs. S 80 W. 15 lks
Marked T. 32 S. R 9 W. S. 4. B. T.
A cedar 10 ins. dia. brs. N 5 W. 40 lks
Marked T 31 S. R. 9 W. S. 33. B. T.
A cedar 16 ins. dia. brs. N. 42 1/4 E. 33 lks
Marked T. 31 S. R. 9 W. S. 34 B. T.
Land mountainous,

South Boundary T. 31 S. R. 9 W.

375

Chains Soil 2d rate.
Timber Cedar & Pine.

80.00

S. 89°55' W. on true line
bet. Secs. 4 & 33
Var. 15°35' E.

25.00 Brush drains NW. at foot of hills. Leave timber & enter dense sage brush.

4.00 Set Touchy to stone 4 x 10 x 6 ins. for 1/4 sec. cor. Marked 1/4 on N. side, dug pits 18 x 18 x 12 ins. & NW. of stone 5 1/2 ft. dist, & raised a mound of ~~stone~~ earth 1 1/2 ft. high 3 1/2 ft. base alongside.

66.00 Brush drains NW.

BOOK-A-175

qtr. S. L. M.

80.00 Set Trachyte stone 18 x 12 x 4 ins. 12 ins. in the ground for cor. to secs. 4, 5, 32 & 33. Marked 4 notches on E & 2 on W. Edges, dug pits 18 x 18 x 12 ins. in each sec. 5 ft. dist. Mound of earth 2 ft high 4½ ft base along side.
Land mountainous & rolling brush.
So E 2d rate.
Cedar & pine on E. 25 chs.
Bal. desert sage brush

"

Smith Boundary T31 S. R. 9 W.

chains S. 89°55' W. on true line between Secs. 6 & 32 Var. 15°35' E.

8.50 Road from Dawson to Minersville via Cane Springs.

40.00 Set Trachyte stone 14 x 11 x 10 ins. 10 ins. in the ground for 1/4 sec. cor. Marked 1/4 on S. side & raised mound of stone alongside.

55.00 Rock drains S. & W.

67.50 " " " W. 9.50

80.00 Set Trachyte Stone 14 x 10 x 7 ins. 10 ins. in the ground for cor. to Secs. 5. 6. 31 & 32. Marked 5 Notches on E. & W. sides, & on S. Edges, drive pits 18 x 18 x 12 ins. in each. 170.00

9 W. S.L. M.

Sec. 5 ft. dist, & dug pits 2 raised mound of Earth 2 ft. high 4 ft. base, alongside. Land rolling bench soil 1st rate. Dense sage brush.

"

S. 89°55' W. on a true line bet. Secs. E. 1/4 Var. 15°35' E.

9.50 Wash drains S.W.

1/0.00 Set Porphyte stone 14 x 11 x 10 ins. 10 ins. in the ground for 1/4 sec. cor. Marked 1/4 on N. side & raised mound of stone along side.

38

West boundary T. 31 S R 9 W

ni the gmnd for ~~Town~~ cor
to secs. 25. 30. 31 & 36. Marked
1 Notch on S. & on N. Edges
& raised mound of stones
alongside.
Land Broken brush
Soil 2d rate.
Dense sage brush.
No timber

"

North bet. Secs. 25 & 30
Var. 15° 30' E.

8.00 Descend on N. slope of Bench
40.00 on N. slope set Trachyte
stone 14 x 12 x 12 ins. 10 ins.
ni the gmnd, for 1/4
Sec. cor. Marked 1/4 ~~Sec~~
on N. side, & raised a
mound of stone alongside.

44.50
60.00
80.00
11.00

S. L. M. 382

44.50 Bash drains S.E., ascend
60.00 Top of Beech brush N.W.S.E.
80.00 On East slope: set a
Trachyte stone 14x12x4
ins. 10 ins. in the ground
for cor. to secs. 19, 24, 25 & 30
Marked 4 notches on N.
& 2 on S. Edges, & raised
mound of stone along
side.
Land rolling -
Soil 2d rate.
Dense sage brush.
No Timber.

North bet. Secs. 19 & 24
Var. 15°30' E.

11.00 Bash drains S.E.

West Boundary T. 31 S. R 9W

23.00 Top of Beech bears N W & S E.
40.00 Hollow drains S E. set Trachyte stone 16 x 10 x 4 ins. 11 ins. in the ground for 1/4 sec. cor. Marked 1/4 on N. side & raised mound of stone alongside.
54.00 Top of Beech brs. N W & S E
65.00 Wash drains S E. at foot of mountains ascend.
80.00 Set Trachyte stone 30 x 10 x 10 ins. 21 ins. in the ground for cor. to secs. 13. 18. 19 & 24 marked 3 notches on N & S. edges & raised mound of stone alongside

40.00
65.00
75.00
80.00

Heavy rolling bench. Land 2nd rate. No timber Dense sage brush undergrowth.

"

S. L. M.

North bet. Secs. 13 & 18
Var. 15° 30' E.
Scattering cedars.

40.00 Mark a stationery Trachyte rock 48 x 30 x 25 ins. above ground for ¼ sec. cor., marked with a cross (+) at the corner point, & ¼ on N. side, & raised a mound of stone alongside.

65.00 Top of ridge E & W. Descend

75.00 Ravine drains West.

80.00 Set Trachyte 17 x 15 x 10 ins. 11 ins. in the ground for cor. to secs. 7, 12, 13 & 18, marked 2 notches on N & S. Edges, & raised mound of stone alongside.

Land Mountains.

West Boundary T. 31 S. R. 9 W. 385

BOOK S.

Chains		
	Soil 2d rate. Scattering cedars along line.—	7.00
	"	8.00
	North bet. Secs. 7 & 12 Var. 15° 30' E.	
10.00	Top of Ridge brs. N.W. & E.	
18.00	Descend	
35.00	Head of Hollow drains S.E. and ascend.	
40.00	Mark a Stationery Trachyte Rock 20 x 10 x 10 ins. above ground for 1/4 Sec. cor. Marked 1/4 on N. side & a cross (+) at the corner point, & raised mound of stone along side.	

BOOK-A-175

7000 Top of Mountain divide
bears E & W. Descend
8000 Marked stationary trachyte
rock 24 x 12 x 10 ins. above
ground for cor. to secs.
1. 6. 7 & 12, Marked Notch
on N. & S. Edges, &
a cross (+) on corner point
& mound of stone
alongside.
Land Mountainous.
Soil 2d rate.
Sage brush and scattering
cedar timber.

BOOK-

West boundary T. 31 S., R. 9 W. S.

Chains North bet. secs. 1 & 6

Var. 15° 30' E.

4.00 Set Trachyte 16 x 9 x 4 ins. 11 ins. in the ground for 1/4 sec. cor. marked 1/4 on W. side & raised mound of stone alongside.

6.00 Foot of mountains bears E. W.

84.25 Intersect 6th standard

Parallel S. 18 chs. West of the standard cor. to T. 30 S., R. 9 W. 10 Mls, which is a "Volcanic stone 21 x 13 x 11 ins. with mound of stone"—

Set Trachyte stone 14 x 10 x 7 ins. 16 ins. in the ground for, standard closing cor. to T. 31 S. R. 9 & 10 W. marked C. C. with 6 notches on E. S. & W. edges with mound of stone

B. S. L. M. 3 R 6

almgrede.
Land Mountainous.
Soil 2d rate
Scattering cedar timber.
Aug. 15th 1881.

"

General Description

The lands in this township are mostly mountainous ~~country~~ covered with scattering cedar & pine timber. There are some general indications of minerals.

Bear grass springs are situated about in sec. 6 & Big Maple springs are about in sec. 4, as nearly as can be located, as they could not be seen from either line. The township can be subdivided.

570

T. C. Bailey
U. S. Dep. Surv.

BOOK-A-175 391 408

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, Dec. 19th 1881

The foregoing field notes of the survey of the

South & West Boundaries

of

Township No 31 S. *Range No* 9 W.

of the Salt Lake Meridian, Utah Territory,

Executed by D. C. Bailey

Under his *contract No* 102

of the 2nd *day of* May 188 1,

in the month of Augt. 188 1,

having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.

Edw. Salomon.

U. S. Surveyor General for Utah.

BOOK-A-175
R: 1882

Filed 187 .

Examined by R. Gorlinski

Compared by R. Gorlinski & E. Mohaley

FIELD NOTES

OF

THE SURVEY OF THE

South & West Boundaries

of Township No. 31 S. , Range No. 10 W.

of the Salt Lake Meridian in Utah Territory.

BY

T. C. Bailey

U. S. DEPUTY SURVEYOR,

Under his Contract No. 102

dated May 24th 1881.

Survey commenced Aug 17 1881.

Survey completed " " 1881.

BOOK-A-175

South 392 Bounday T. 31 S. R 10 W.

Survey commenced Aug. 17th 1881, with a Burts improved solar compass, which I test on my meridian, Pickets and find correct.

From the Trachyte stone 18 x 14 x 10 ins. with stone mound, the cor. to T. 31 & 32, S. R 9 & 10 W. I run East on a random line between said Tps. in R. 10 W. setting temporary corners at 40 & 80 chs. and at 5 miles. 79 chs. & 70 links, I intersect the East Bounday of the townships at the Trachyte Stone 24 x 14 x 4 ins. with stone mound, The correction for the line

995

South Boundary T. 31 S. R. 10 W.

chains link will therefore be
30 links west per mile
and the course West.

From the above described
cor. to T. 31 & 32 S. R. 9 & 10
W, I run
West on the line
bet. Secs. 1 & 36
Var. 15° 35' E,

11,00 Stationary Trachyte Rock
36 x 25 x 12 ins. above ground
for 1/4 sec. cor. marked 1/4
on W. side, with a cross
(X) at corner point, &
raised mound of stone
alongside,

42,00 Rock drains S.

65,00 Hollow " S.E.

80,00 Set Trachyte 36 x 15 x 8 ins

11.00
20.00
36.00
40.00

BOOK-A-175

Cor. S. L. Sec.

24 lks. in the ground,
for cor. to Secs. 1, 2, 35 & 36,
Marked 1 with on E. & 5 on
N. edges, & raised mound
of stone alongside.
Land broken Bench.
Soil 2d rate.
Dense sage brush, good
grass — No timber.

"

Meas. on the line
bet. Secs. 2 & 35.
Var. 15° 35' E.

11.00 Top of Ridge NW & SE.
20.00 Wash draws S.E.
36.00 Top of Knoll.
40.00 Set Trachyte 30 x 10 x 10 ins
22 lks. in the ground, for

South Boundary T. 31 S. R. 16

Chains ¼ sec. cor. Marked ¼ on N. side & mound of stones alongside.

54.00 Rush drains SE. 13.00

70.00 Top of Knoll 33.83

80.00 Set Trachyte stone 20×12× 40.00
10 ins. 14 ins. in the ground
for cor. to secs. 2, 3, 34, 35,
Marked 2 notches on E,
& ¼ on N. edges & mound
mound of stones alongside. 70.50

Land Mundane
Soil 2d rate.
Dense sage brush & good
grass — to mouth.

BOOK-A-175

R. 10 E. S. L. M.

West on the line
bet. Secs. 3 & 34
Var. 15° 35' E.

13.00 Top of a spur Ridge N & S.
33.83 Road to Minnisville S W.
40.00 Set Trachyte stone 15 x 8 x
6 ins. 10 ins. in the ground
for ¼ sec. cor. marked ¼
on N. side, & mound a
mound of stone along side.
70.50 Wash drains S E.
77.10 Top of Ridge bears N & S.
80.00 Set trachyte stone 14 x
12 x 6 ins. 10 ins. in the
ground for cor. to secs.
3. 4. 33 & 34, marked
3 notches on E. & W. edges
& mound mound of
stone along side.
Land Broken Bush & hills.

South Boundary T. 31 S. R. 10 W.

Chains		
	Soil 2d rate.	66.00
	Dense sage brush, wood	8.00
	grass — No timber.	
	"	
	Iron on true line	
	bet. Secs. 4 & 33,	
	Var. 15° 25' E.	
3.00	Wash drains S E,	
15.00	Top of Ridge, S E,	
24.00	Hollow drains "	
40.00	on top of Ridge, set	
	limestone 15 x 12 x 6 ins.	
	10 ins. in the ground	
	for the sec. cor. Marked	
	1/4 on N. side & raised	
	a mound of stone	5.00
	alongside.	31.50
49.00	Hollow drains S E,	38.50

W. S. L. M. 378

66.00 Top of Ridge S.E. & N.W.
80.00 Set Trachyte stone 16 x 12 x 10 ins. 11 ins. in the ground for cor. to secs. 4, 5, 32 & 33, Marked 4 notches on E. & W. edges, & raised mound of stone alongside.

Land Mountainous,
Soil 2d rate.
Dense Sage. No timber.

Meas on true line
bet. Secs. 5 & 32
Var. 15° 35' E.

5.00 Wash drains S.E.
31.50 Top of Ridge bears S.E. & N.W.
38.50 Wash drains N. across

South boundary T. 3 S., R. 10 W.

40.00	Set Trachyte 18×18×10 ins., 12 ins. in the ground for ¼ sec. cor. Marked ¼ on N. side, & raised a mound of stone alongside.	Chains
55.00	Top of ridge bears N.&S.	28.00
80.00	In hollow drains S.E.,	35.00
	Set Porphyry stone 15×10×7 ins., 8 ins. in the ground for cor. to secs. 5, 6, 31 & 32, Marked 5 notches on E. & W. edges, & raised mound of stone alongside.	40.00
	Land Mountainous,	45.00
	Soil 2d rate,	55.00
	No timber.	63.00
		69.00
		79.74

21

BOOK-A-175

W. S.L. M.

Chains West on true line
bet. Secs. 6 & 31.
Var. 15° 35' E.
Ascend on N. side of hollow
drains N.
28.00 Same hollow drains at W.
35.00 Top of Divide bears NW. & SE.
40.00 Wash drains N W. Set a
Sandstone 14 x 12 x 10 ins,
10 ins. in the ground for
1/4 sec. cor. Marked 1/4 on
N. side, & raised a
mound of stones alongside,
45.00 Ascend.
55.00 Top of Ridge N W & S E
63.00 Wash drains N.
64.00 Top of divide, bears NW & SE.
79.70 To the Trachyte stone 18 x
14 x 10 ins. with stone
Mound, the cor. to S. 31

Claims

and 32 S. R. 10 W 11 W.
Land Mountainous,
Soil 2d rate.
No timber.

22.00
30.00
40.00

60.00
70.00
80.00

West Boundary T. 31 S. R. 10 W.

Chains. From the Trachyte stone 18 x 14 x 10 ins. with stone mound the cor. to T. 31 & 32 S. R. 10 & 11 W. Runs North bet. secs. 31 & 36 Var. 15° 35' E.

22.00 Ridge bears SE & NW.

30.00 Wash drains SE.

40.00 Set Trachyte stone 15 x 9 x 8 ins. 10 ins. in the ground for 1/4 sec. cor. marked 1/4 S. R. on N. side, & raised mound of stone alongside.

60.00 Ridge bears SE & NW.

70.00 Ranie drains SE.

80.00 Set Trachyte 14 x 12 x 10 ins. 10 ins. in the ground, for cor to secs. 25, 30, 31 & 36, Marked 1 notch on S & W N. edges, & raised mound of ~~stone~~

BOOK-A-

421

Inst Boundary T. 31 S. R 10 W. S. L

Stones stone alongside.
Land mountainous.
Soil 2d rate.
No timber.

"

North bet. Secs. 25 & 30
Var 15° 35' E.

30.00 Ranie drains E.
110.00 set Quartzite 16 x 12 x 9 ins.
11 ins. in the ground for
¼ sec. cor. marked ¼.
on N. side, & raised a
mound of stone along
side.
60.00 Ridge bears S E & N W.
70.00 Ranie drains S E.
80.00 Set Quartzite stone 15 x 9 x
8 ins. 11 ins. in the ground

20.00
40.00

S. L. Sn.

for cor. to Secs. 19, 24, 25 & 30, Marked 4 notches on N. & E. on S. Edges, & raised Mound of Stones alongside.
Land Mountainous
Soil 2d rate.
No Timber.

North Dist. Secs. 19 & 24
Va. 15° 35' E.

Ascend, enter Cedars.
20.00 Ridge bears N & S.
40.00 Hollow drains N, set a Pinchyte stone 16 x 14 x 8 ins, 11 ins. in the ground for 1/4 Sec. cor. Marked 1/4 on N. side, & raised Mound of Stone along side.

BOOK

West boundary T. 31 S. R. 10 W. S. 2

50,00	East Point of ridge,	Chains.
80,00	Set Trachyte 16x11x8 ins. 11 ins. in the ground for cor. to Secs. 13, 18, 19 & 24, Marked 3 notches on N & S. Edges, & raised a mound of R. Fox Stone adjacent. Land Mountainous Soil 2d rate, Scattering cedars	45.00 65.00 80.00

North bet. Secs. 13 & 18
Var. 15° 35' E.

10,00	Rains drains SE.
15.00	Ridge bears SE & W.
40.00	Set Trachyte 14x12x11 ins. 10 ins. in the ground for

BOOK-A-175

S. L. M.

Chains. 1/4 sec. cor. marked 1/4 on N. side & raised a mound of stones alongside.

45.00 Ranie bears N.

65.00 Ridge bears N. & S.W.

80.00 Set Trachyte stone 17 x 11 x 8 ins., 11 ins. in the ground for cor. to secs. 7, 12, 13 & 18, marked 4 notches on S. & 2 on E. Edges, & raised a mound of stones alongside. Land Mountainous Soil, 2d rate scattering cedars.

East boundary T. 31 S. R 10 W. S. 2

~~181~~ North bet. Secs. 7 & 12
Var. 15° 35' E.

1800 Knoll —

4000 Set Trachyte 14 x 13 x 9 ins. mrs. N 40 W 4 ins. in the ground, for 1/4 Sec. cor. marked 1/4 on N. side, & raised a mound of stone alongside. 14.00

4900 Dash drains N. 4.00

5500 Ridge bears N 60 W,

7500 Ranne drains N,

8000 Set Trachyte stone 15 x 10 x 8 ins. 10 ins in the ground for cor. to Secs. 1, 6, 7 & 12, marked 1 notch on E. & W sides & S edges, & raised a mound of stone alongside. 76.00 82.50

S. L. M.

Land Mountaineers
Ark 2d rate.
Scattering cedars.

North between Secs. 1 & 6
Var. 15° 35' E.

14.00 Raine drains N.

40.00 Set Trachyte stone 16 x 10
x 9 ins. 11 ins. in the
ground, for 1/4 sec. cor.
Marked 1/4 S. on N. side,
Pound mound of
stones alongside.

76.00 Ridge bears N 40° E

82.30 Intersect 6th standard
Parallel S. 14.50 chs. N.
of the Red Sandstone 20 x
15 x 14 ins. the standard

Cor. to ~~Sec~~. T.p. 30 S.R. 10 & 11 W. Set Trachyte Stone 16 x 14 x 12 ins. for 11 ins in the ground for Standard closing cor. to ~~Sec~~. T.ps. 31 S.R. 10 & 11 W. Marked 6. notches on S. E & W. Edges, with C.C, & mound of stones along side.

Land Mountainous
Soil 2nd Rate.
Scattering cedar.

Aug. 17th 1881.

N. S.L.Dn. 40

General Description

The lands in this township consist of mountains & foot hills mostly covered with cedar timber and good grass.

The Soil is 2d rate.

This township & the one in Range 11 W. can be subdivided.

F. C. Bailey
U. S. Dep. Surv.

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, Dec. 17th. 1881

The foregoing field notes of the survey of the

South & West Boundaries of

Township No 31 S. Range No 10 W.

of the Salt Lake Meridian, Utah Territory,

Executed by F. C. Bailey

Under his contract No 102

of the 2nd day of ~~Aug~~ May 1881,

in the month of Aug 1881,

having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.

Jno. Salsbury

U. S. Surveyor General for Utah.