BOOK-A-197

ORT: 1884

188

mined by John H. Caupke

scribed by E. Michaelis

pared by C. S. & Ed. Michaelis

FIELD NOTES

Re-Survey

OF THE SURVEY OF THE

By. H. N. R. W. and

Survey of the

E. By. N. N. R. 14 W.

OF

Township No

No

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Henry Fitzhugh

U. S. Deputy Surveyor,

nder his Contract No. 116

d July 16 1883

ey commenced October 1 1883

y completed 11 1 1883

BOOK-A-197

ORT: 1884

188

mined by John H. Caupke

scribed by E. Michaelis

pared by C. S. & Ed. Michaelis

FIELD NOTES

Re-Survey

OF THE SURVEY OF THE

By. H. N. R. W. and

Survey of the

E. By. N. N. R. 14 W.

OF

Township No

No

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Henry Fitzhugh

U. S. Deputy Surveyor,

nder his Contract No. 116

d July 16 1883

ey commenced October 1 1883

y completed 11 1 1883

BOOK-A-197

Township 11 North R. 14 West

6	5	4	3	2	1	10
7	8	9	10	11	12	15
18	17	16	15	14	13	14
19	20	21	22	23	24	14
30	29	28	27	26	25	12
31	32	33	34	35	36	11
1	3	4	6	8	9	

BOOK-A-197 1

Re-Survey —

S. Bdy. T. 11 N. R. 14 W. S. L. M.

Chains Before Commencing this Survey I took an observation of the star Polaris and find the Variation of the Needle to be 18° E. Upon testing my Transit on the line which agrees with the notes of the old survey

Survey Commenced with a Gurley Transit October 1. 1883

From the Cor. to Tps. 10 & 11 N. Rs. 14 & 15 W. on the Grid. Meridian which is a Conglomerate 24x20x20 ins marked B notches on N. S. E. & W. sides & Regulation Mound & Pits & Mon

East on Re-survey line Bet. Secs. 6 & 31

Ogr. degree of the Grid. E. Note Not Very Able often

9 2

Re-Survey of Sec. 7 T. 11 N.

Chains		Chains	
	diligent search to find & identify this Cor. to Secs 10 & 11 N.S R.S. 13 W 4 D. Otherwise necessary for me to make a 2½ deviation of this line -		
40.00	No trace of Cor. Set Witness Cor.		
	I then continue East to		
2.68	find old Cor. standing		
	I then return to		
4.68	Set quartzite 20×14×10 ins.	15	40.00
	ins. in the ground for N.E.		
	Established 1/4 Sec. Cor. mark-		
	ed 1/4 on N. face, dug pits	25.00	
	& placed stones		
	& placed mound of earth		
	& gravel	40.00	
1.68	find old Cor. standing, where		
	is a pine stake 12×2½×2 ins.		
	at the S.E. pit × properly		
	marked for Cor. to Secs. 5.		
	31 & 32. I opened old		
	mound & which was		
	remain from Regulation	0.00	

R. 14 W. S. L. M.

Miles
Land level
Line 1st date
Underbrush under growth on 80.68 chs.

Set on re-survey line
Sec. 1 & 2
N 18° 10' E.

Set Stone & old Cor.
Set Temporary Cor.
Thence East 40
Find old Cor. Stone dug
& Trees of old Mound
Stone Return to
Set Granite 12x8x8 inc.
Stone in the ground for
re-established Sec. Cor.
Marked 1/4 on E. from dug
Regulation Pits & Pits
Regulation Mound of Earth
Complete
Find old Cor. which is a

Re-Survey of Bg. T. 11 S.

Chains	Pine Stake 24×2×2 ins. Prob. Cor. Sec. 4 Pine Stake 24×2×2 ins. Prob. Cor. Sec. 5 Pine Stake 24×2×2 ins. Prob. Cor. Sec. 32 & 33 Pine Stake 24×2×2 ins. Prob. Cor. Sec. 4 &

BOOK-A-197

R. 14 W. S. L. Co.

Set Temporary Cor.
Thence East 80.00
Find old stake & stones down
Faces of old mound
Stones taken to
Set Conglomerate 33 x 10 x 4 ins
Do ins. in the ground for re-
establishment 1/4 Sec. Cor. Mark-
ed 1/4 on E face, dug reg-
ulation pits & raised reg-
ulation mound of earth
complete
Check drains S.
Ridge bears N.E. & S.W.
Check drains S.E.
Find old stake & stones down
& decayed & Faces of old
mound - Set Sine & Sine
10 x 8 x 5 ins - 10 ins. in the
ground for re-established
Cor. to Secs. 3, 4, 33 & 34, Mark-
ed 3 notches on E & W. edges
and Sunk old mound
from regulation pits

Re-Surveyed By D. M. R.

Chains

Land rolling & Mountainous
Pine & Hard Wood
Dense Age Growth
Growth on 27.00 Chs.
Mountainous on 53.00 Chs
Augmented on 8.00 Chs.

East on re-survey line
Bet. Secs. 34 & 4
Va 18.10 E.

2.00 Enter Flat Beech & Pine
Dense Age Growth under growth
4.00 to Race of old Cr.
Set Temporary Cr.
Thence East 8.00
to Race of old Cr.
Set temporary Cr.
Thence East along S. side of
Sec. 35-5
4.00 to Race of old Cr.
Set temporary Cr.
8.00 Ford old Cr. Standing
I Iron Pipe to

Chains

4.00 Set
Set
re-
Dense
Growth
Set
Mountainous
2.00 Enter
8.00 to
Set
15 Pine
Flat
34
on
Age
Set
Along
Set
Set
Ford
Standing
Iron

BOOK-A-197

R. 14 E. T. L. & M.

40.00 Set Stone & Pile 12x8x4 ins & ins. in the ground, for re-established 1/4 Sec. Cor. Marked 1/4 on N. face, dug Regulation Pits & raised Regulation Mound of Earth Alongside

Mountains bear N.E. & S.W.

40.00 No Trace of old Cor. Set Stone & Pile 27x9x5 ins. 15 ins. in the ground for re-established Cor. to Secs. 2, 3, 34 & 35 Marked & Notches on N. & E. Edges. Dug Regulation Pits & raised Regulation Mound of Earth Alongside

Land Mountainous & flat Soil 1st & 2nd rate Dense Age Brush & under-growth on 40. chs. Mountains on 40. chs. Augmented on 200 chs.

Re-Survey of By. T. 11 N.

Chains	
	East on Re-survey line Bet. Secs. 2 & 35 Var 18° 10' E.
15.00	Leave Meanders. Cedar Flat Bears Cor. X Base Page Brush underbrush
40.00	No trace of old Cor. Set Stone & mound 3x3x6 ins. 9 ins. in the ground for re-established 11 X Sec. Cor. Mound 11 X on N. face, dug pit alongside & 16 X faced by relation mound of earth
80.00	Find old Cor. which is a stone State properly marked standing in open prairie for Cor. to Secs. 1, 2, 35 & 36 X Traces of old mound - I erected mound from relations
	Land Meanders & flat Base 1st & 2nd Base Same Page Brush underbrush on 65.00 chs.

Chains

BOOK-A-197

R. 14 W. S. L. M.

Mountains on 10.00 chs.
Aggregation on 80.00 "

Easterly re-survey line
Bet. Secs. 1 & 36
Va 18.10 E.

No trace of old Cor.
Set Temporary Cor.
Thence East 80.00
Find old Cor.
1 Pine Pointed
Set Charred Pine Stake 3 ft
long 3 ins. Square, 12 ins. in
the ground for re-established
1/4 Sec. Cor. Marked 1/4 on
S. face, dug regulation
Pits & raised regulation
Mound of earth & stone
Find old Cor. which is a
Pine Stake 24 x 4 x 3 ins. Properly
Marked, Stones down &
Displaced. Traces of
old Mound remaining

10 Re-Survey

S. By. T. 11 N. R. 14 E. — S. L. M.

Acres

Same name from Sec 2
Adelia Fields & drive old
stake in S.E. Cor. 12 ins.
deep for Re-established
Cor. Sec 10 & 11 N. Rs. 13
& 14 E.

Land rolling
Soil Loam & Gravelly
Wood Oak Elm & underg
growth in 80.00 chs

80.00

C Bet. R. 11 & 12 R. 14 & 15 W. S. L. Mt.

Chains From the Cor. to Sps. 10 & 11 N. Rs. 13 & 14 W. Var. 18° 10' E. Established by me during this survey & one Limb on a Blaze line Trees Bears. Var 18° 10' E. and at 6 miles 77.57 chs. Intersect Township line 12.50 Chains W. of the Cor. to Sps 11 & 12 N. Rs. 13 & 14 W. Which I find & identify after diligent search. I set Limb Pits & Stone Corrs to the Cor. to Sps. 10 & 11 N. Rs 13 & 14 W. & run Northon the line Bet. Secs. 31 & 36. Var 18° 10' E.

100 At 5 links W. the 16 x 4 x 4 ins. 11 ins. in the ground for 1/4 Sec. Cor. Marked 1/4 on W. face, dug Pits at the Corner & Mixed Mound adopted

12

E ½ Sec. 7 T. 11 N. R. 14 W.

Claims

80.00 Set Stone Mon 12x8x7 ins
8 ins. in the ground for
to Secs. 25, 30, 31 & 36, Mar
ed 1 notch on S. & W
on N. edges, dug up and
pits & mound Irregular
mound alongside
Land rolling
Soil 1st qlty - Sandy
Dense Kage & brush and
growth on 80.00 Acs

Northwestline Set
Secs. 25 & 30
W 18 links E

15.00 Corner high broken Mountain
bears N.W. & S.E.
~~Scattering Cedars~~
Kage dense Kage & brush

4.00 Set Stone 16x6x6 - ins
11 ins. in the ground for
1/4 sec. Cor. Marked 1/4 on
W. face, dug up Irregular

Lands

5.00
6.00
7.00
5.00

BOOK-A-197 13

S. L. Co.

Pits & mound regulation
Mound of earth alongside
Ridge bears N.W. & S.E.
Adjoining drains S.E.
Ridge bears N.W. & S.E.
Set Stone 22 x 10 x 9 ins -
15 ins. in the ground for
Cor. to secs. 19, 24, 25 & 30
marked 2 notches on S.
& E. edges. Day reg=
ulation pits & mound reg=
ulation mound of earth
alongside
Land rolling & mountainous
Soil 2nd rate
Timber on 65.00 chs.
Dense Age brush under=
growth on 15.00 chs.
Augmented on 8.00 chs.

Gate in the line
Bet. secs. 19 & 24
Var 18.0 10' E.

E/By. D.W.N.R. 4th Dr.

Chains
4000 Act Sine & Tne 14×9×4 ins -
10 ins. in the ground for 1/4
Sec. Cor. Marked 1/4 on Dr.
face, dry Regulation
pits & raised Regulation
mound of earth alongside
8000 Act Sine & Tne 10×8×7 ins - 6
ins. in the ground for Cor.
to Secs. 13, 18, 19, & by Mark
ed B Notches on N. & S.
edges, dry Regulation
pits & raised Regulation
mound of earth alongside
Land & mountainous
Soil 3rd Class.
Mountainous on 8000 ch

North on the line
Bet. Secs. 13 & 18
Va 18.10 E.
1900 Ash in hollow drains N
4000 Act Sine & Tne 24×4×0 in
16 ins. in the ground for 1/

L. L. M.

Sec. Cor. marked 1/4 on Br. Face, dug regulation pits & raised regulation mound of earth alongside

Set Stone 18x8x8 ins - 12 ins. in the ground for Cor. to Secs. 7, 12, 13 & 18 marked + notches on S. & E. edges, dug regulation pits & raised regulation mound of earth alongside

Land Mountainous
Soil 2nd rate
Mountainous 80.00 Chs.

North on Meridian
Between 7 & 12
Var 18° 10' E

Set granite 26x7x5 ins - 18 ins. in the ground, for 1/4 Sec. Cor. marked 1/4 on Br. Face, dug regulation pits & raised regu-

E. By. P. M. R. 14 Yr.

Chains | Cabin mound of earth
| alongside
8.00 | On N. W. point of ridge
| Set Spike tree 20×12×12 ins
| 18 ins ins the ground, for
| Cor. to Secs. 1, 6, 7 & 12, Mark
| ed S notches on S. & 1 Notch
| on N. edges. Any depression
| Pits & Mounds of
| Cabin mound of earth
| aforesaid
| Land Mountains
| Dale & Coast
| Mountains in 8.00 Ch

| North to the line
| Set Secs. 1 & 6
| Va 18.10 E.
0.00 | Cutts Valley bears E. &
| & Aug. Dge Smoke
40.00 | Set Spike tree 10×10×7 ins
| 10 ins. in the ground, for
| 1/4 Sec. Cor. Marked 1/4 on

Chains
77.07

S. L. Cor

Chains

77.87

W. face, dug regulation
Pits & Mound Regulation
Mound of earth alongside
Intersects Township lines
12.00 Chains N. of Cor. to
Shs. 11 & 12 N. Rs. 13 & 14 W.
Note. The Connection from
this Cor. with the Guide
Meridian is 9.87 chs.
long & 1 ch. S., which
accounts for my falling
at this point & for other
points in this line, con-
verging more & more as I
the differences -
Where I set a Charred Pine
Post 4 ft. long 4 ins. Square
12 ins. in the ground for
Accessible Cor. to Shs 11 N. Rs.
13 & 14 W. Marked 6 notches
on S. & W. edges, with
S. 11 N. R. 14 W. on S. W. and
S. 6. R. 13 W. on S. E. sides
And D. C. Dug Pits a-

18

E. by T. 11 N. R. 14 W. S. L. M.

Chains

Ten pits & mound of stone
at each corner mound of earth
& stone pits
Land mountainous Valley
land 1st & 2nd rate.
Mountainous 10. Chs.
Average thickness under
growth on 67.50 chs.
Aggregated on 77.50 chs.

October 1. 1883

General Description

This township embraces
some good farming land
& some cedar timber.
It affords fine water
power for stock.

Henry Lippich
U.S. Dep. Surveyor.

U. S. SURV

Salt L

The fo

Surve

Township No

Executed by

Under

day of

Octob

amined, the ne

the said field

hereby approve

BOOK-A-197

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, February 15th 1884.

The foregoing field notes of the survey and Resurvey of the

S. Bdy. T. 11 N. R. 14 W. Resurvey of 6th Mer.

Township No. T. 11 N. Range No. R. 14 W.

Executed by Henry Fitzhugh

Under Sec. No. 116 contract of the 16th

day of July 1883, in the month of

October 1883, having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.

J. H. Salomon

U. S. Surveyor General for Utah.

BOOK-A-197

10 6

REPORT: 1884

Filed 188

Examined by John H. Campbell

Transcribed by E. M. Michaelis

Compared by John A. Mitchell & E. M. Michaelis

FIELD NOTES

OF THE SURVEY OF THE Resurvey

North Boundary

OF

Township No 11 North

Range No 15 West

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Henry Fitzgerald

U. S. Deputy Surveyor,

Under his Contract No. 116

Dated July 16 1883

Survey commenced Sept. 20 1883

Survey completed " 20 1883

V

BOOK-A-197

Township 11 North R. 15 West

	24	26	27	21	21	19
47	6	5	4	3	2	1
45	7	8	9	10	11	12
44	18	17	16	15	14	13
43	19	20	21	22	23	24
42	30	29	28	27	26	25
40	31	32	33	34	35	36
	29	31	32	34	35	36

BOOK-A-197 19

Re-Survey

N. Bdy. T. 11 N. R. 15 W. S.L.M.

Chains Survey Commenced with a Gurley Transit Sept. 20. 1883

Note-

Being unable after diligent search to find the established Cor. to Secs. 3, 4, 33 & 34 I find it necessary to make a re-survey of this line as far as run. in order to make Connection between the Guide Meridian, and the Cor. to Tps. 11 & 12 N. Rs. 15 & 16 W. set by me during this survey, thereon

From the Cor. to Tps. 11 & 12 N. Rs. 14 & 15 W. on the Guide Meridian which is a cedar post, mound according to instructions with my blazed & scribed sides.

Run

West on N. survey line Bet. Secs. 1 & 36

Ld= 18.10 C.

Through Dense Sage brush

N. Bk.

Re-Survey T. 11 N. R. 15 W.

Chains	
40.00	Fnd old cor. standing, which is an Aspen post properly marked for 1/4 Sec. Cor. I renew old mound from regulation pits.
18.00	W. fork Arauco R.
80.00	Fnd old Cor. which is an Aspen post of regulation size Aspen post thrown down & misplaced, & being properly marked. I re-set same 12 ins. deep in old mound of which traces remain for re-established Cor. to Secs. 1, 2, 35 & 36 and renew old mound from regulation pits. Land level Soil 1st rate - Sandy Loam Sage brush, under growth on 80.00 chs.
	West on re-survey line Bet. Secs. 2 & 35 Va 18.10 E.

Chains	
40.00	Fn
	is
	m
	Fn
80.00	Fn
	Co
	Si
	Fo
	Co
	Op
	Fn
	Fn
	Fn

BOOK-A-197 21

S. L. M.

	Stone
40.00	Find old Cor. standing, which is an Aspen post, properly marked for 1/4 Sec. Cor. I mon. all around from Regulation pits.
80.00	Find old Cor, which is an Aspen post of Regulation size stone down, it being properly marked - S. 25 E. 12 lks. dug in old mound of which pace re- for re-establishing Cor. to Secs 2, 3, 34 & 35 mean - I mon. old mound from Regulation pits Loud Level Soil 1st rate - sandy Dense sage brush under growth on 80.00 chs.
	West on previous line Bet. Secs 34 & 35 Var 18° 10' E.
40.00	Find old Cor. stone down & decayed with traces of old mound

22

Re-Survey

N. Bdy. T. 11 N. R. 15 W. - S. L. M.

Chains	Set Stone 12x10x5 ins. 8 ins. in the ground for re-established 1/4 Sec. Cor. marked 1/4 on N. face and Brs. W'd old Mound from Regulation Pits
45.00	Track drains S.
50.00	Enter dense cedars
	Clear dense sage brush
80.00	Find old cor. which is a Stone Post Properly Marked for Cor. to Secs. 3, 4, 33 & 34, Stand in Mound of earth & stone - I Dig new old Mound from Regulation Pits
	Land Rolling
	Soil 1st rate.
	Dense sage brush under-growth on 50.00 Chs.
	Heavily timbered on 30. over
	Augmented on 80.00 Chs
	End of Re-Survey

N. By. T. 11 N. R. 15 W. S. L. M.

Mains

From the Cor. to Secs. 3. 4, 33 & 34 which is a Pine Post in Mound of Earth & Stone Marked T. 12 N. on N.E. R. 15 W. on S.W. S. 33 on N.W. and S. 3 on S.E. faces, with 3 notches on E. & W. edges. I run West on a Random line Bet. Tps. 11 & 12 N. R. 15 W. the Variation of my Transit being 18° 10' East - I set Temporary half-mile & mile Cors. at each 40 and 80 chs. and find the line to be, from starting point, 2 miles - 79 chains and 28 links and the falling to be 41 links S. of the Cor. to Tps. 11 & 12 N. Rs. 15 & 16 W. The correction for the true line will therefore be 1 37/3 chs. S. for mile and its course will be

24

N. By. T. 11 N. R. 15 W.

Chains	S. 89° 54' E.
	From the cor. to Sec. 11 & 12 N. R. 15 & 16 W. set by me during this survey I run
	S. 89° 54' E. on a true line Bet Secs. 6 & 31 over mountains Va. 18.10 E.
26.50	Track drains S. E.
	Leave mountains.
	Enter rolling brush & dense cedar
39.28	Set Sandstone 13 x 12 x 8 ins. 10 ins. in the ground, for 1/4 Sec. Cor. marked 1/4 on N. face, and Stone pits & Burned Regulation mound of earth alongside
	From which a cedar 14 ins. diam. bears S. 11° E. 150 lks. dist. Marked 1/4 S. B. T.
49.00	Track in hollow drains S. E.

Chains	
53.50	
66.00	
79.28	

S. L. M.

Links	
53.50	Road in same bears N.W. 1/4 E.
66.00	Trash in same bears S.E.
79.28	Ln trash drains S.E.
	Set Stone 13×8×8 ins. 10 ins. in the ground, for Cr. to Secs. 5, 6, 31 & 32, Marked 1 notch on E. & S. notches on E. edges, Dug Regulation Pits & Raised Regulation Mound of earth alongside Same a Pitch
	A cedar 24 ins. diam. bears S. 25° W. 110 lks. dist. Marked T. 11 N. R. 15 W. S. C. B. T.
	A cedar 8 ins. diam. bears N. 45° W. 32 lks. dist. Marked T. 12 N. R. 15 W. S. 31. B. T.
	Land rolling & mountainous
	1st & 2nd rate
	Mountains on 26.50 chs.
	Heavily timbered ~~timber~~ on 52.78 chs.
	Dug mounds on 79.28 chs

N. By. T. 11 N. R. 15 W.

Chains	S. 89° 54' E. on true line Bet. Secs. 5 & 32 Va 18° 10 E.	Chains	N. A S. N. L & &
40.00	Set Quartz 14x8x5 ins - 10 ins in the ground for 1/4 Sec. Cor. marked 1/4 on N. face, dug Regulation pits & mound Regulation mound of earth alongside. From which A cedar 8 ins. diam. bears S. 50 E. 16 lks. dist Marked 1/4 S. B. T.		S.
76.60	Fork Stone S.	39.00	
80.00	Set Pine Stone 19x10x6 ins - 12 ins in the ground for Cor. to Secs. 4, 5, 32 & 33, Marked 2 notches on W & N on E. edges, dug Regulation pits & mound Regulation mound of Earth alongside From which A cedar 6 ins. diam. bears N. 17° W. 33 lks. dist. Marked	40.00	Set ins Cor. dug mound Fr A N. A S.

BOOK-A-197 27

S. L. C.

Chains

T. 12 N. R. 15 W. S. 32. B. T.
A cedar 11 ins. diam. bears,
S. 47° W. 49 lks. dist. Marked
T. 11 N. R. 15 W. S. 5 B. T.
Land rolling
Soil 1st class
Heavily timbered with woods

S. 89° 57' E. on true line
18 Ch. Sec's 4 & 33
Var 18° 10' E.

39.00 Stake in hollow drains S. E.
40.00 Set Stone 18 x 8 x 8 ins - 12
ins. in the ground for 1/4 Sec.
Cor. Marked 1/4 on N. face,
Dug Regulation Pits & Mound
Regulation Mound of earth
Alongside
From which
A cedar 6 ins. diam bears
N. 16 1/4° E. 59 lks. dist.
A cedar 7 ins. diam. bears
S. 83° W. 16 lks. dist.

28

N. By. T. 11 S. R. 15 W. S. L. M.

Chains	
	Both Banks of S. C. R.
5.00	Kash Arroyo S. E.
80.00	The Cr. to Secs. 3, 4, 33 & 34
	Land rolling
	Soil 1st & 2nd rate
	Heavily timbered on Sec. 4
	Sept. 20. 1883

General Description

For general description see end of Subdivisional notes of Tp. 11 S. R. 15 W.

Henry Fitzhugh
U.S. Dep. Surveyor.

U. S. SURVE

Salt Lak

The foreg

Township No.

Executed by

Under

day of

Sept

amined, the nece

the said field

hereby approved

BOOK-A-197

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, February 15th 1884

The foregoing field notes of the survey of the

North Body

Township No. 11 S. *Range No.* 15 W.

Executed by Henry Fightmaster

Under his No. 116 *contract of the* 16th

day of July *1883, in the month of*

Sept. *1883, having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

Fred Salomon

U. S. Surveyor General for Utah.

BOOK-A-197

16

REPORT: 1884

Filed 188

Examined by John H. Dampe.

Transcribed by E. Michaelis

Compared by .....

FIELD NOTES

OF THE SURVEY OF THE

South Boundary

OF

Township No 11 N

Range No 15 W

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

H. C. Fitzhugh

U. S. Deputy Surveyor,

Under his Contract No. 116

Dated July 16th 1883

Survey commenced October 8 1883

Survey completed " 8 1883

Re-Survey S. By. T. 11 N. R. 15 W.

Chains

Survey Commenced with a Gurley Transit October 8. 1883

Note. a number of the Cor. on this line being destroyed before making the subdivision of this Tp. I find it necessary to make a resurvey of said line, following the course of same. Therefore I run the Cor. to Tps. 10 & 11 N. Rs. 15 & 16 W. & re-establish by me during this survey

I run

N. 89° 55' E. on resurvey line Bet. Secs. 6 & 31 through dense Cedar brush

15.00 Center Cedar hills bear N.W. & S.E.

27.00 Ridge bears N.W. & S.E.

Re. Survey of Bdy. Lines

Reference

41.34 Found old post thrown down & decayed with four notches of old mound &.
Set sand stone 20x8x7 ins. - 10 ins. in the ground for re-established 1/4 Sec. Cor. Marked 1/4 on N. face & dug a mound of stone alongside

45.00 Enter rolling brush bears NE. & SW. & dense page brush undergrowth

58.50 Spring branch in hollow drains SE. Spring 120 lks. N. of SE.

78.00 Enter hollow drains SE.

81.34 Found old Cor. standing which is a sand stone 10x18x11 ins. above ground properly marked for Cor to Secs. 5, 6, 31 & 32. with a mound of stone alongside

Sand hilly & rolling
Soil 1st & 3rd Rate
Heavily timbered on 30 chs.

BOOK-A-197

31

R. 15 E. S. L. M.

Drains Drain dug S. 89° W. in growth on S. 34 chs. Augmented N. 34 chs.

N. 89° 55 E. on Survey line Bet. Secs. 5 & 32

Var. 18° 10' E.

2.50 Leave hollow drains S.E.

4.00 Find old Cor. which is a pine post, stump down with marks nearly obliterated 2 pr. Mark & pr. set same 12 ins. deep in old mound of which Bacs remain for re-established 1/4 Sec. Cor. & erect old mound from regulation pits.

4.50 Cross Drain S.E.

5.20 Old Emigrant Road bears N.E. & S.W.

8.00 Find old Cor. which is a pine post of regulation size. Stump down & Miss placed & marks

Re. Survey of Bg. T. 11 N.

Chains

Marks effaced - & re-
Sank Fe ins in the grou
in old mound, of which
Traces remain for re-es
tablished Cor. to Secs. 4. 5,
32 & 33 marked
S. 11 W. on N.E.
B.T. S. 32 on N.W.
B. T. O W. on S.W. and
B.T. S. 4 on S.E. with 2
notches on W & 4 on E.
edges. & Stones old mou
from pits of Regulation
Size

Land rolling
Soil 1st rate
Dense Age Bush
under growth on Boo

N. 89° 55' E. on Reservoy line
Bet. Secs. 4 & 33
Lks 18.10 E.
4.00 Found Old Cor. whic

Chains

Bo

T. 1

is
Sa
& Re
& re
the
of
for
Cor.
Sec
Found
Fou
Mi
Sa
me
gro
wh
for
Se
Old
to

BOOK-A-197

T. 15 N. R. 1 W. 2nd P.M.

is a fine sort of vegetation size, timber down & marks nearly obliterated & no set stone 12 ins. in the ground in old mound of which traces remain for re-established 1/4 Sec. Cor. Marked 1/4 S. on N. face and mound old mound Pits

80.00 Mid Sec. Cor. Timber down & misplaced - No set stone, at bring Property marked 12 ins in the ground in old mound of which traces remain for re-established Cor. to Secs. 3, 4, 33 & 34. & mound old mound from vegetation Pits

Land level
Soil 1st Qlty Sandy
Dense growth brush under growth on 80.00 Chs.

BOOK A

Re-Survey of Sec. 34 T. 11 N. R.

Chains. N 89° 55' E. on N. Survey bounds of Sec. 3 & 34. Dec. 1870.

3000 Enter Mud Creek bottom bears N.W. & S.E.

4000 Find old Cor. stone down & decayed & set Chiseled pine post 3 ft. long 3 ins. square 12 ins. in the ground in old mound of which faint traces remain for 1/4 Sec. Cor. Marked 1/4 S. on N. face, and stone old mound from regulation pits re-established

4450 Muddy Creek, dry bed, drains S.E.

4650 Leave Muddy Creek bottom Enter bench bears N.W. & S.E.

6350 Road bears N.E. & S.W.

8000 Find old Cor. stone down & misplaced. & reset same, which is a pine post of regulation size

BOOK A-1 35.

R. 15 W. S. L. M.

& properly marked, 12 ins.
in the ground in old
mound, of which traces
remain for re-establish-
ed Cor. to Secs. 2, 3, 34 & 35.
I drew old mound from
regulation pits.
Land level & bottom
soil 1st rate.
Dense day & brush under-
growth in 80.00 chs.

N. 89° 05' E. on resurvey line
Bet. Secs. 2 & 35
Dist 18.08.
40.00 Found old Cor. which is a
pine post of regulation
size & properly marked
Burnt down & misplac-
ed - & re-set same 12 ins.
in the ground in old mound
of which traces remain
for re-established by Sec.

Re Survey S.B. T. 11 N.

Chains		Links
	Cor. I mound'd mound from regulation pits	78.00
50.00	Entered Indian Camp bears N.E. & S.W.	33.00
61.50	Leave same bears N.E. 18	40.00
80.00	Find old Cor. which is a pine post properly marked, standing for Cor to Secs. 1, 2, 35 & 36, & Cor = mound'd from regulation pits.	
	Land Bench April 18th 1872 Hardly Dense Sage brush and grown on 80.00 chs.	64.50
		7.00
		8.00
	N. 89° 55' E. on Survey line Bet. Secs. 1 & 36	
	Dec 18° 10' E.	
17.00	Leave bench. Enter Mountains bear N. 5.	

37

E. 10 N. L. M.

Chains	
78.00	Rocky ridge bears N.S.
33.00	Door Mountains.
	Enter rolling brush bears N.S. & cedar timber.
40.00	Find oak stake, which is a pine post property marked for 1/4 sec. Cor., standing a mound old mound from degulation pits & bears a cedar 10 ins. diam, which bears S. 40° E. 30 lks. dist. 1/4 S. B. T.
64.50	Small quick drains S.E.
7.00	Pass cedar timber
	Enter dense page brush
8.00	Find Cor. which is a door post with conglomerate rock standing Stamped.
	Standing property marked for Cor. to Sec. 10 & 11 N. Rs. 1 & 2 W. with mound & pits in good condition
	Land brush & Mountains
	Sail 1st & 4th Date
	Mountains on 16.00 chs.

38 Re-Survey

S.B. 9 11 N. R. 10 W. S.L.M.

Chas. Henry Tinsley 37.00 Chs.
Dense sage brush under-
growth 27.00 Chs.
Augmented 8.00 Chs.
October 8. 1883

General Description

See General Description
See end of Subdivision
Notes of T. 11 N. R. 15 W.

Henry Fitzpatrick
U.S. Dep. Surveyor

A list
ployed by
United Sta
ning, mea
corners des
the survey
Survey
Tract
1883
of the Salt
tory of Uta
in which th

BOOK-A-197

[4—LIST OF NAMES.]

A list of the names of the individuals employed by Henry Fitzhugh *United States deputy surveyor, to assist in running, measuring, and marking the lines and corners described in the foregoing field notes of the survey of* the Standard Meridian Township & subdivision lines ~~[illegible]~~ surveyed under Contract No. 116 dated June 16 1883. Howard Nebeker Resp

of the Salt Lake base and meridian in the Territory of Utah, showing the respective capacities in which they acted.

....., *Compassman.*
Charles A Fine, *Chainman.*
James Lee, *Chainman.*
Joseph Lee, *Chainman.*
Isaac Douglas, *Chainman.*
George M. Smith, *Axeman.*
John Lee, *Axeman.*
....., *Flagman.*

BOOK A 197

[5.—FINAL OATHS OF ASSISTANTS.]

We hereby certify that we assisted Henry Fitzhugh *United States deputy surveyor, in surveying all those parts or portions of the* Standard, Meridian, Township, and Subdivision Lines, under Contract No. 16, dated June 16. 1883 *of the Salt Lake base and meridian in the Territory of Utah, as are represented in the foregoing field notes as having been surveyed by him and under his direction; and that said survey has been in all respects, to the best of our knowledge and belief, well and faithfully surveyed, and the corner monuments established according to the instructions furnished by the United States surveyor-general for Utah.*

, *Compassman.*

Charles D. Lee, *Chainman.*

James Lee, *Chainman.*

Joseph Lee, *Chainman.*

David Douglass, *Chainman.*

George M. Smith, *Axeman.*

John Lee, *Axeman.*

, *Flagman.*

Subscribed and sworn to before me this 9th *day of* October 1883

Henry Fitzhugh

U.S. Deputy Surveyor.

BOOK-A-197

[6.—FINAL OATH OF UNITED STATES DEPUTY SURVEYOR.]

I, Henry Fehlings

United States deputy surveyor, do solemnly swear that in pursuance of instructions received from Fred. Salmon United States surveyor-general for Utah, bearing date of the 16th day of July, 1883, I have well, faithfully, and truly, in my own proper person, and in strict conformity with the instructions furnished by the United States surveyor-general for Utah, the surveying manual and the laws of the United States, surveyed all those parts or portions of the Standard, Meridian, Township & Subdivision lines ~~&~~ surveyed under Contract No. 116 dated June 16. 1883 - Situate North & East

of Salt Lake base and meredian in the Territory of Utah, as are represented in the foregoing field notes as having been surveyed by me and under my directions; and I do further solemnly swear that all the corners of said survey have been established and perpetuated in strict accordance with the surveying manual, printed instructions, the special written instructions of the United States surveyor-general for Utah, and in the specific man-

ner described in the field notes, and that the foregoing are the TRUE *field notes of such survey; and, should any fraud be detected, I will suffer the penalty of perjury, under the provisions of an act of Congress, approved August 8, 1846.*

Henry J. B. Lynch

United States Deputy Surveyor

Subscribed and sworn to before me this 29th *day of* January *1884*

Edward Michaelis

Notary Public

BOOK-A-197

Salt Lake City U.T.
Dec. 1st 1883

Hon: Jos. Salmon
U.S. Surveyor General
Salt Lake City U.T.

Sir:

I have the honor to state that in the performance of my contract No. 116 of July 16. 1883, it was unknown and impracticable to have the oaths administered to my assistants on account of distance and the time and expense I would have incurred in finding such officer and taking my oath before him. I therefore, administered the oaths as provided for under such circumstances.

Very Respectfully
Henry Tibbetts
U.S. Dep. Surveyor

BOOK-A-197

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, February 15th 1884

The foregoing field notes of the survey of the

North boundary

Township No. 11 North *Range No.* 15 West

Executed by Henry Fitzhugh

Under his *contract* No 116 *of the* 16th

day of July 1883, *in the month of*

October 1883 *having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

Ed Salomon

U. S. Surveyor General for Utah.

BOOK-A-197

12

REPORT: 1884

Filed 188

Examined by John H. Caney.

Transcribed by J. W. Hickok

Compared by Hickock & Mitchell

FIELD NOTES

OF THE SURVEY OF THE

West Boundary

OF

Township No 11 N

Range No 15 W

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

J. C. Fitch

U. S. Deputy Surveyor,

Under his Contract No. 16

Dated July 16th 1883

Survey commenced September 19 1883

Survey completed 4 19 1883

40

BOOK-A-197

West Boundary T. 11 N. R. 15 W

On the night of Sept. 18. 1883
I took R and observation on the
Star Polaris on its Eastern
Elongation to determine the
true Meridian, and drove
pickets on the line thus Es=
tablished and find the var.
to be 18° E.

Survey commenced Sept. 19. 1883
With a Gurley Transit
Before commencing this
survey I test my Instrument
on the line established
last night and find it
correct.

From the cor. to Tps. 10 &
11 N. R's. 15 & 16 W set by sun
I run
North bet. Secs. 31 & 36
Va. 18° E.
5.00 High Ridge bears N. W. & S. E.
2.50 Deep Gulch bears S. E.

West Boundary Tp 11 N. R 15 W

chs.	
	Ascend steeper hills.
3.50	Gulch runs S.E.
40.00	Set Quartzite 30 x 14 x 4 in. 24 in in ground for 1/4 Sec. cor. marked 1/4 on W face with stone mound alongside.
45.00	Ridge runs N.E. & S.W.
55.00	Gulch runs S.W.
62.00	" "
70.00	S.W. point of ridge, thence along rocky N. slope to
81.00	Set Quartzite 20 x 8 x 6. in 15 in in ground, for cor. to Secs. 25. 30. 31 & 36. marked with 1 notch on S and 5 on N edges, with stone mound alongside.

Land Mountainous
Soil 2nd & 3rd rate
few scattering Cedars
Mountainous as far as 80 chs.

Salt

chs.	
	Ascend
20.00	Set
40.00	Set
	in
	mk
	st
56.50	Ri
70.00	Ga
81.00	m
	18
	wi
	4
	co
	w
	a
	Sca
	M
	Jor
11.00	De
20.50	Ro

BOOK-A-197 42

Salt Lake Meridian

chs.	
	North bet. Secs. 25 & 30
	Va. 18° E.
2.00	Descend
4.00	Set Quartzite 18×7×6 in. 12 in. in ground, for 1/4 Sec. cor. marked 1/4 on W face, with stone mound alongside.
56.50	Deep Gulch drns. N.E.
70.00	Gulch drns. E. ascend
80.00	marked a Stationary Limestone 18×8×4 in. above ground with 2 notches on S and 4 on N. Edges, and with a (+) cross on exact cor. pt. with stone mound alongside. Land Mountainous Soil 4th rate, rocky Scattering cedars and sage brush Mountainous on 80 chs.

North bet. Secs. 19 & 24
Va. 18° E.

11.00	Deep Gulch drns. S.E.
20.50	Ridge brs. N.E. & S.W.

Salt Lake Meridian

Chs	
25.00	Gulch drns. S.E.
29.00	Main Ridge brs. N.E. & S.W. Dr
40.00	Set Quartz Ltr 14×8×6 in. 10 in. in ground for 1/4 Sec. cor. marked 1/4 on W. face with stone mound alongside
65.00	Gulch drns. N.E.
80.00	Sm Gulch drns. N.E. Set Limestone 18×8×8 in. 12 in. in ground for cor. to Secs. 13. 18. 19 & 24 marked with 3 notches on N & E edges with stone mound alongside. A Cedar 6 in. dia. brs. N. 26° E. 70 lks. dist. marked T. 11 N. R. 15 W. S. 18 B.T. Cedar 7 in. dia. brs. N. 80° W 60 lks. distant marked T. 11 N. R. 16 W. S. 13 B.T. No other trees near Land Mountainous Soil 2nd & 4th rate Scattering Cedars Mountainous on 80 chs.

West

Chs.	
	Iron
40.00	Set
	3 f
	in
	Co
	Ja
	M
	and
	Cor
	arc
	Ce
49.00	S. E
	Hor
	N. 5
	W 4
	cor
	Cal
72.00	Cul
	T. 12
	Lea
80.00	Set
	4 in
	in

West Boundary T. 11 N. R. 15 W

chs. North bet. Secs. 13 & 18
Va. 10° E.

40.00 Set charred Cedar post
3 ft. long, 3 in. square, 12 in.
in the ground for 1/4 Sec.
Cor. marked 1/4 S. on W.
face, dug pits 18 x 18 x 12 in
N & S. of post 5½ ft. dist.
and raised a mound of
earth 1½ ft. high 3½ ft. base
around post

40.00 Enter valley brs. N. W. &
S. E. and dense sage brush
Henry Losees house brs.
N. 52½° E. Outhouse brs. N
5° 45' E. Stackyard and
corrall brs. N. 50° 30' E.
Cattle corrall brs. N. 31½° E.

72.00 Enter meadow. Dry Bed
of Birch Creek brs. N. E.
Leave sage brush Undergrowth

8.00 Set charred Pine post
4 in. square, 4 ft. long, 12
in. in the ground for

Salt Lake Meridian

chs.

Cor. to Secs. 7, 12, 13 & 18
marked T. 11 N. R. 7 ow N. E
R. 15 W S. 18 ow S. E.
R. 16 W S. 13 ow S. W
S. 12 ow N. W Jacks, with
4 notches ow Sand 2 ow N
Edges. dug pits 18 x 18 x 12 in
Thread Sec. 5½ ft. disch
and raised a mound of earth
2 ft. high 4½ ft. base arou
post.
Land Mtns and Valley
Soil 2nd and 1st rate
Brush Undergrowth ow 23.0
Mountainous ow 49.0
Augmentos on 72.0

North bet. Secs. 7 & 12
Va. 18° E.

1.00 Fence brs. S. E. & N. W
2.00 Road brs. S. E. & N. W
16.00 Mud creek (Dry Bed) dous. S.
Leave Meadow. Enter dense
Sage & rabbit brush undergro

West

chs.
16.00 No
Ent
40.00 Sec
bou
gla
Ou
du
D.
cas
1½
pos
8.00 Le
10
to
wit
ou
an
and
La
Dru
No

BOOK-A-197 46

West Boundary Tp. 11 N. R. 15 W

chs
Road brs. N. W. & S. E.
Enter Bench brs. N. W. & S. E.
4.00 Set charred cedar post 3 ft. long 3 in. square 12 in. in ground for 1/4 Sec. cor marked 1/4 S on W. face dug pits 18 x 18 x 12 in. N & S. of post 5 1/2 ft. dist. raised mound of earth 1 1/2 ft. high 2 1/2 ft. base around post.
8.00 Set Quartzite 15 x 10 x 3 in. 10 in. in ground for cor. to Secs. 1, 6, 7 & 12, marked with 5 notches on S. and 1 on N faces, with regulation pits and mound of earth alongside.
Land valley & Bench
soil 2d rate
Brush Undergrowth on 6.00.

North bet Secs. 1 & 6
Va. 18 E.

47

Salt Lake Meridian

Chs.	
7.50	Enter scattering cedars
32.00	in Low rolling hills
	brs. N. W. & S. E.
40.00	Set Quartzite 18 x 14 x 6
	12 in. in ground for 1/4
	Sec. cor. marked 11 on
	W. face with stone
	mound alongside
52.50	Head of Gulch brs. S. W
65.00	Ridge brs. E & W
80.00	Set Quartzite 24 x 12 x 6 in
	18 in. in ground, for cor.
	to Secs. 11 & 12 N. R. 15 W
	marked with 6 notches
	on N. S. E & W edges with
	regulation M & P. alongside
	Land Brush and hilly
	Soil 2nd & 3rd rate
	Scattering cedars.
	Dense Undergrowth on 80 ch

September 19. 1888

For General Description see end of Subdivisional lines of this Tp

Henry Fitzhugh
U. S. Dep. Surv.

U. S. SURVEY

Salt Lak

The foreg

Township No.

Executed by

Under

day of

Septem

amined. the nec

the said field

hereby approved

BOOK-A-197

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, February 15th 1884.

The foregoing field notes of the survey of the

West Boundary.

Township No. 11. N. *Range No.* 15. W.

Executed by Henry Fitzhugh

Under his Noll contract of the 16th

day of July 1883, *in the month of*

September 1883, *having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

Fred Salomon

U. S. Surveyor General for Utah.

BOOK-A-197

1/2

REPORT: 1884

Filed 188

Examined by John W. Campbell

Transcribed by [illegible]

Compared by [illegible]

FIELD NOTES

OF THE SURVEY OF THE

South West and North Boundaries

OF

Township No 11 North

Range No 16 West

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Henry Fitzhugh

U. S. Deputy Surveyor,

Under his Contract No. 116

Dated July 16th 1883

Survey commenced Sept 17 1883

Survey completed " 18 1883

BOOK-A-197

Township 11 North R. 16 West



BOOK-A-197 48

South Boundary Tp. 11 N. R. 16 W.

Chs. Survey commenced Sept. 17. 1883 with W Gurley Transit.

Before commencing this survey I took an observation on the Star. Polaris on its Eastern Elongation, in order to determine the correct variation of the needle and find it to be 18° E. Drove pickets on the line thus established and test my instrument and same and find it correct.

From the cor to Tps. 10 & 11 N. R. 15 & 16 W reestablished by me during this survey I run West on a random line between said Townships the var. of my Transit being 18° E. & set temporary half mile and mile corners at each 40 and 80 chs and find the Township line to be

Salt Lake Meridian South

Chs. 5 miles 77 chs and 50 lks. long, and the falling to be 1.30 lks. N. of the cor. to Tps. 10 & 11 N. R. 15 & 16 W. The correction for the true line will therefore be 2 1/3 lks. S. ~~and 2.50 lks E.~~ per mile and its course will be N. 89° 51' E.

From the cor. to Tps. 10 & 11 N. R. 16 & 17 W. which is established by me during this survey.

I run N 89° 57' E. on a true line bet. Secs. 6 & 31

Va. 18° E.

37.50 Set Limestone 17 x 7 x 4 in 12 in in ground for 1/4 Sec. cor. marked 1/4 on N face with regulation pits and

lks. mu
62.50 K
72.00 bo
77.50 Set
8 mi
to S
wit
ow
mu
Mon
N. 8
be
99.00 Ob
Iro
4.00 Ou
Lim
10 in
cor.
with

South Boundary T. 11 N. R. 16 W.

lks. mound of earth alongside
62.50 Ridge Dns. N.E. & S.W.
72.00 Gulch dns. N.E.
77.50 Set Limestone 12 x 6 x 6 in.
8 in. in ground for Cor
to Secs. 5. 6. 31 & 32 marked
with 5 notches on E and 1
on W. Edges with stone
mound alongside
Land Mountainous
Soil 3rd rate
Mountainous on 77.50 chs.

N. 89° 57' E on true line
Meh. Secs. 5 & 32
Va. 18 E.
39.00 Old road bears N.E. & S.W.
Sw Gulch dns. N.E.
42.00 On rocky bluff set
Limestone 15 x 13 x 4 in.
10 in. in ground for 1/4 Sec.
Cor. marked 1/4 on N face
with stone mound alongside

Salt Lake Meridian

6 lks. 22.00	Gulch drns. N.E.
77.50	" " "
80.00	Set Limestone 15 x 10 x 4 in. 10 in. in ground for cor. to Secs. 4 & 5, 32 & 33 marked with 4 notches on E and 2 on W. edges with stone mound alongside.
	Land Mountainous Soil 3rd rate Mountainous on 80 chs

N. 89° 57' E. on true line bet. Secs. 4 & 33

Va. 18° E.

26.70	Rose Bud Creek 6 lks. wide 3 in. deep runs S.E. in Gulch drns. S.E.
28.00	Road in Gulch bears N.W. & S.E.
	Gulch drns. S.E.
39.50	Gulch drns. S.
40.00	Set Limestone 24 x 7 x 6 in

South

6 lks.	18
	cor
	with
80.00	Le
	10
	to
	with
	N. E
	pits
	alon
	Sec
	Ma
	N. 8
	bet
40.00	Le
	in
	14
	on
	pits

South Boundary Tp. 11 N. R. 16 W.

lks. 18 in. in ground for 1/4 Sec. cor. marked 1/4 on N face, with stone mound alongside.

80.00 Set Limestone 15x8x6 in. 10 in. in ground for cor. to Secs. 3, 4, 33 & 34 marked with 3 notches on E. and 3 on N. edges, with regulation pits and mound of earth alongside.

Land Mountainous
~~Soil~~ 3rd rate

Pen scattering cedars
Mountainous on 80 chs

N 89° 57' E. on true line
bet. Secs. 3 & 34

Va. 18° E.

40.00 Set State Stone 13x8x3 in. 8 in. in ground for 1/4 Sec. cor. marked 1/4 on N face with regulation pits and mound of earth

Salt Lake Meridian

chs.	alongside
5.00	Gulch dams. S.E.
62.50	" " "
8.00	Set Slate 15 x 8 x 4 in. 10 in in ground for cor. to Secs 2. 3. 34 & 35 marked with 2 notches on E and 4 on W. Edges with stone mound alongside
	a Cedar 13 in. dia brs. S. 27 130 lks. distant marked T 10 N. R. 16 W. S. 3. B. T.
	No other trees within distance
	Land Mountainous Soil 1st & 3rd rate Few scattering Cedars Mountainous on 8 chs.

N. 89° 57' E. on true line bet. Secs. 2 & 35

Va. 18° E.

8.25 Prospect Cor N. 50 lks. dis

10.00 " " " "

chs
15.50
38.00
40.00
42.50
63.00
78.00
80.00

BOOK A-197

524

South Boundary T. 11 N. R 16 W.

chs	
15.50	Gulch drns. N.
38.00	
40.00	Set Limestone 15 X 14 X 5 in. 10 in. in ground for 1/4 Sec. cor. marked 1/4 on N face with stone mound alongside.
	a cedar 14 in. dia. brs. N 63° E. 42 lks. dist.
	No other trees near.
57.50	Ridge brs. N.E. & S.W.
63.00	Dry Gulch drns. N.E.
74.00	High Ridge brs. N.E. & S.W.
80.00	Set Limestone 16 X 13 X 5 in. 10 in. in ground for cor. to Secs. 1. 2. 35 & 36. marked with 1 notch on E and S on W. edges, with stone mound alongside. no suitable trees for marking near the corner.
	Land Mountainous Soil & rate rocky Scattering cedars

8 55

Salt Lake Meridian

Chs.	Mountainous on 8 chs.
	N. 88° 57 E. on true line bet. Secs. 1 & 36
	Va. 18 E.
33.50	Gulch dms. S.
40.00	Set Limestone 16 x 7 x 3 in 25.00
	10 in. in ground for 1/4 Sec 40.00
	Cor. marked 1/4 on N. face
	from which a
	Cedar 5 in. dia. brs. S. 59° W. 31 lks. dist
	" 8 " " N. 42° E. 20 " "
	Both marked 1/4 S. B. T.
57.00	Gulch dms S. E. 46.00
69.00	Road brs. N. W. and S. E. 66.50
	in Gulch dms. S. E. 80.00
80.00	The Cor. to Tps. 10 & 11 N.
	R. 15 & 16 W.
	Land Mountainous
	Soil 4th rate rocky
	few & scattering Cedars
	Mountainous on 8 chs
	September 17. 188

BOOK-A-197

56 9

West Boundary T. 11 N. R. 16 E.

Survey Continued Sept. 18. 1883

from the cor. to Secs. 10 & 11 N. R. 16 & 17 W

Set by me on this survey I run North a true line bet. Secs. 31 & 36

Va. 18° E.

Hollow drns. E.

Set Quartzite 18 X 10 X 9 in. 12 in. in ground for 1/4 Sec. cor. marked 1/4 on W. face with regulation pits and mound of earth alongside.

46.00 Gulch drns. S. E.

66.50

Set Quartzite 20 X 10 X 7 in. 15 in. in ground for cor to Secs. 25 & 30 31 & 36, marked with 1 notch on E. and 5 on N. edges. with Stone mound alongside.

Land Mountainous:

Soil 1st & 3rd rate

10 517

Salt Lake Meridian

lchs.		lchs.
	Good grass Mountainous and rocky	
	North bet. Secs. 25 & 30 Va. 18° E.	
11.00	Ridge trs. N.W. & S.E.	
30.00	Gulch runs S.E.	
40.00	Set Limestone 14x13x7 in. 9 in. in ground for 1/4 Sec. cor. marked 1/4 on W face with stone mound alongside.	9.00
		17.75
		34.00
		40.00
42.50	Ascend steep broken mountains	
68.50	Gulch runs S.E.	
78.00	High Ridge trs. N.W. & S.E.	45.00
80.00	On N. slope of high ridge Set Limestone 22x13x7 in 18 in. in ground for cor. to Secs. 19, 24, 25 & 30 marked with 2 notches on S. and 4 on N edges with stone mound alongside	66.50
		80.00

West Boundary Tp. 11 N. R 16 W

lks. Land Mountainous
Soil 3rd & 4th rate
Few scattering Pines on N 1/2
Mountainous on So ds.

North bet. Secs. 19 & 24
Va. 18° E.

9.00 Dry Gulch dms. E.
17.75 Ridge bns. N.E. & S.W.
34.00 Gulch dms. N.E.
40.00 Set Limestone 24 x 9 x 8 in.
18 in. in ground, for 1/4
Sec. cor. marked 1/4 on
W face with stone mound
alongside
45.00 Ridge bns. N.E. & S.W.
66.50 Gulch dms S.E.
80.00 Set Limestone 19 x 10 x 10
in. 12 in. in ground
for cor. to Secs. 13, 18, 19
& 24. marked with 3
notches on N & 3 on S.
Edges, with stone mound
alongside

12 T9

Salt Lake Meridian

Lks.		Lks.
	Land Mountainous Soil 4th rate rocky few scattering pines Mountainous 80 ch	
	North bet. Secs. 13 & 18 Va. 18 Ch	
4.00	Ridge trs. N.W. & S.E.	
15.00	Gulch dms. N.E.	
26.00	Junction of Ridges trs N.E. N.W. & S.W	10.00
27.50	Head of Gulch dms. N.	25.00
40.00	Set Limestone 18 x 16 x 8 12 in. in ground for 1/4 Sec. cor. marked 1/4 on W. face with stone mou alongside	4.00
60.00	Ridge trs. N.E. & S.W	50.00
73.00	Gulch dms. N.E.	62.50
80.00	Set Limestone 32 x 14 5 in. 24 in. in ground for cor. to Sec. 7, 12, 13 & 18 marked with	73.00 8.00

BOOK-A-197

60

13

West Boundary Tp. 11 N. R. 16 W

lchs. 4 notches on S. and 2 on N. Edges, with Stone mound alongside.
Loud mountainous
Soil 3rd & 4th rate
Some Quaking asp
Mountainous 80 chs.

North lch. Secs. 7 & 12
Va. 18° E.

10.00 Ridge brs. N. W. & S. E.
25.00 Gulch drns. S. E.
40.00 Set Limestone 14 X 13 X 7 in. 10 in. in ground, for 1/4 Sec. cor. marked 1/4 on W face with Stone mound alongside.
50.00 Ridge brs. N. W. & S. E.
62.50 Deep Gulch drns. S. E.
73.00 Ridge brs. N. W. & S. E.
80.00 Set Granite 19 X 10 X 9 in. 12 in. in ground for cor. to Secs. 1. 6. 7 & 12, marked

Salt Lake Meridian West

lchs. with 5 notches on S and
low N edges with Stones
mound alongside
Land Mountainous
Soil 3rd sals
few Quaking asp
Mountainous on Sochs

North lch. Secs. 19 & 20
Va. 18° E.

5.00 Deep Gulch runs N.E.
24.00 Ridge lrs. E & W
40.00 In deep Gulch runs N.E.
set Granite 13 X 13 X 9 in
8 in. in ground, for 1/4
Sec. cor. marked 1/4 on
W. face, with Stones mound
alongside.
60.00 High ridge lrs. N. E. & S.
80.00 set Granite 27 X 13 X 12 in
20 in. in ground for
cor. to Tps. 11 & 12 N. R. 16 &
17 W. marked with 6 notch

BOOK-A-197

62

West Boundary of T. 11 N. R. 16 W.

chs on N. S. & W. edges with Stone mound bldg aide

Land Intns.
Soil 3rd & 4th rate
Mountainous on 80 chs.

North Boundary Tp. 11 N. R. 16 West

lchs. From the cor. to Tps. 11 & 12 lchs.
N. Rs 16 & 17 W. I run
East on a meadow line
between said Tps, the
variation of my Transit
being 18° E. I set temp
half mile and mile corner
at every 40 and 80 chs. and
find the Township line to be 5 miles 76 chs. & 83 lks
long, and the falling to
be 98 lks North of the
cor to Tps. 11 & 12 North
Rs 15 & 16 W. The
correction for the true line
will therefore be 16⅔ lks
E. and 3.7 chs. West per
mile, and its course
will be N. 89° 53' W. 1 mile.
From the cor to Tps. 11 & 12
N. R. 15 & 16 W. set by
me during this survey
I run

30.25

BOOK-A

BOOK-A-197

North Boundary Tp. 11 N. R. 16 W.

N. 89° 53 W on d Lmrs bet. Secs. 1 & 36.
Va. 18 ° E.

30.25 Leave high broken Cedar hills
Enter rolling bunch bx. N & S.
& dense sage brush & Shad
scale undergrowth.
Road bms. N. E. & S. W
" " N & S.

Set Quartzite 18 x 8 x 6 in.
12 in. in ground for 1/4
Sec. cor. marked 1/4 on
N. face, with regulation
pits and mound of earth
alongside.

Hollow dms. S. W
Road bms. N. W. & S. E.

Set Quartzite 13 x 8 x 4 in
8 in. in ground for cor.
to Secs. 1. 2. 35 & 36.
marked with 1 notch on E
and 5 on W. edges. with
regulation pits and
mound of earth alongside

Salt Lake Meridian

chs | chs

Land rolling
Soil 1st rate gravelly
Timber Underbrush & growth 4/
Mountainous 3/
Augmented on 8000 chs.

North 89° 53 W on true line bet. Secs. 2 & 35
Va. 18 E.

28.50 Enter Hollow dry S.E.
32.00 Wash dry S.E. Leave Hollow.
4.00 Set Quartzite 14 x 8 x 7 in 4.00
9 in. in ground for 1/4 Sec. Cor. marked 1/4 on N. face with pits and mound of earth alongside.
62.50 Gully dry S.E.
76.00 " " "
80.00 Set Quartzite 17 x 8 x 4 in 80.00
12 in. in ground for Cor to Secs. 2. 3. 34 & 35 mar with 2 notches on E and

1.50
22.00
3.00

North Boundary Tp. 11 N. R 16 W

Lakes Run W. edges with
Mour mound alongside
Land rolling
Soil 1st & 2nd rate
Dense Undergrowth on Rods

N 89° 53' W on true line
bet. Secs. 3 & 34
Vg. 18° E.

1.50 Gulch drns. S.E.
22.00 " " "
40.00 Set Quartzite 15x6x6 in.
10 in. in ground for 1/4
Sec. cor. marked 1/4 on N
face with reg. pits and
mound of earth alongside
5300 Wash fringed with willows
drns. S.E.
80.00 Set Quartzite 14x8x4 in.
9 in. in ground for cor.
to Secs. 3. 4. 33 & 34
marked with 3 notches
on E and 3 on W edges

Salt Lake Meridian North

lks	with rec. pits and mound of earth along side. Land rolling Soil 1st rate gravelly Brush Undergrowth and Sec.	lks.	mo E a Stor Lan Do Sec Dru Mo co
	N 89° 53' W on true line Bet. Secs. 4 & 33 Va. 18° E.		N. 8 bet
16.00	Leave rolling Bench & brush undergrowth and Ascend steep hills br. Rp		
28.50	Gulch brs. S. E.	21.50	Sec
40.00	Set Granite 24 x 13 x 3 in. 18 in. in ground for 1/4 Sec. Cor. marked 1/4 on N. face with Stone mound along side.	39.00 40.00	Set 12 in Cor. with
80.00	On high rocky ridge brs. S. E. & N. W. Set Granite 22 x 9 x 8 in. 16 in. in ground for Cor. to Secs. 4, 5, 32 & 33	60.00 68.50 80.00	Sec Rid in Set 18 in

North Boundary Tp. 11 N. R 16 W.

lks. marked with 4 notches on E and 2 on W. edges, with stone mound alongside. Land rolling & hilly. Soil 1st rate rocky few scattering cedars brush Undergrowth on 15 chs Mountainous on 65 chs
Augmented on 80.00 chs.

N. 89° 53' W on true line
Ref. Secs. 5 & 32
Va. 18° E.

2.50 Deep Gulch brs. S. E.
39.00 High Ridge brs. N. W. & S. E.
40.00 Set Granite 18 x 18 x 7 in. 12 in in ground, for 1/4 Sec. Cor. marked 1/4 on N face with stone mound alongside
60.00 Deep Gulch brs. S. E.
68.50 Ridge brs. N. W. & S. E.
80.00 in deep basin brs. S. E. Set Granite 25 x 8 x 8 in. 18 in in ground, for cor. to

Salt Lake Meridian North Bo

lchs. Secs. 5. 6. 31 & 32 marke
with 1 notch ow W and 5
on E. edges with stone
mound alongside.
Land mountainous
Soil stony rocky
Few scattering cedars
Mountainous ow 80. ch

N. 89° 53' W ow true line
bet. Secs. 6 & 31
Va. 18° E.

1.50 Birch creek in canon
5 lks. wide & in. deep runs
26.00 Ridge bro. N. W. & S. E.
40.00 In deep Gulch drns. S.
bet granite 15 X 10 X 10 in
10 in. in ground for 1/4 Sec
cor. marked 1/4 ow W. fac
with stone mound alon
sides.
68.50 High Ridge bro. N. E. & S. W.
76.83 Sec cor. to 4 ps. 11 & 12 N.

BOOK-A-197

70

North Boundary T. 11 N. R. 16 W.

Rs. 16 & 17 W.

Land mountainous.
Soil & rock rocky
some Quaking ash
Mountainous on 76.83 ds

September 18. 1883

Note: For General Description see end of Subdivisions of this Township.

Henry Fitzhugh
W. Deputy Surveyor

BOOK-A-197

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, February 15th *1884.*

The foregoing field notes of the survey of the South, West and North boundaries

Township No. 11 North *Range No.* 16 West

Executed by Henry Fitzhugh

Under his *contract* No. 116 *of the* 16th

day of July *1883, in the month of*

September *1883, having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

Jos. Salomon

U. S. Surveyor General for Utah.

BOOK-A-197

15

REPORT: 1884

Filed 188

Examined by John W. Campbell

Transcribed by E. Michaelis

Compared by .....

FIELD NOTES

re

OF THE SURVEY OF THE

South boundary

OF

Township No 12 North

Range No 13 West

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Henry Fitzhugh

U. S. Deputy Surveyor,

Under his Contract No. 116

Dated July 16th 1883

Survey commenced October 3 1883

Survey completed 4 12 1884

BOOK-A-197

Township 12 North R. 13 West



BOOK-A-197

Re-Survey 71

S. Bdy. T. 12 N. R. 13 W. S. L. M.

Line From the Cor. To Tps 10 & 11 N. Rs. 12 & 13 W. Set by me during this Survey I run N. on a blank line and at 6 distance of 6 miles I being unable to find the Cor. to Tps. 11 & 12 N. Rs. 12 & 13 W. I set a temporary corner K. In order to determine the Connection & make a Resurvey of the T. line Bet. Tps. 11 & 12 N. R. 13 W.

Re Survey Commenced with a Party Trans- October 3. 1883

Re-Survey of Twp. No. 12

Chains	From the Cor. to Secs. 11 & 12 N. 88 W. 13.74 lks. found a stone identified by me, which is a large Cottonwood Post 4 ins. in diameter set mound of earth properly marked I run East on the North line Sec. 6 & 31
	S. 88° 10' E.
40.00	Through dense cane brake Cedar 18 ins. bears N. 45 W. 1 link from dense cane brake
	No trace of old Cor.
	Set Temporary Cor.
80.00	No trace of old Cor.
	Set Temporary Cor.
	I then continue East on the North side of Sec. 32 & Set Temporary Cor. at 40 Chs. and at 80.20 find old Cor. Stone Dam, Set

Re-

BOOK-A-197 — of 53

R. 13 W. S. L. Co.

Chains enough of old mound remaining to identify the position of old Cor. & then return to temporary 1/4 Sec. Cor. on S. side of Sec. 30. & at.

40.05 Set Charred Aspen post 3 ft. long 3 ins. square, 12 ins. in the ground for re-established 1/4 Sec. Cor. marked 1/4 S. on E. face, dug Regulation Pits & raised Regulation mound of earth around post.

80.10 Leave Mead on W. Cañon drain Wash drains S.E. & Sagebrush Nursery no trace of old Cor. Set Hachyte 5 x 8 x 7 ins. 10 ins. in the ground, for re-established Cor. to secs. 5, 6, 31 & 32, marked 1 notch on N. edge & 5 notches on E. edges, dug Regulation Pits & raised Regulation

Re-Survey S. Bdy. T. 12 N.

Chains Mound of earth alongside
Land flat
Soil 1st Class.
Dense Growth of brush under-
growth in 40.00 Chs.

East on Re-survey line
Set Secs. 5 & 32
Va 18° 10' E.

13.50 Road bears N.W. & S.E.
15.75 Old Cabin On line
26.00 Fence bears N & S.
40.05 Pursuing No trace of old c
Set Aspen (Chmd) post 3 ft.
long 3 ins. square 12 ins. a
the ground for 1/4 Sec. Cor.
marked 1/4 S. on N. face,
Acc of regulation pits &
Mound of regulation mound
of earth alongside
49.00 Fence bears N.W. & S.E.
52.50 Road bears N.W. & S.E.
80.10 Find old Cor. stone mon

BOOK-A-197 — 75

R. 13 W. S. L. M.

decayed, but sufficient of old mound remaining to fully identify the true position of old Cor. I set for W. Cor. Chained aspen post 4 ft. long 4 ins. square 12 ins. in the ground in old mound for re-established Cor. to Secs. 4, 5, 32 & 33, marked S. 33 T. 1 N. R. 1 W. S. 32 T. 1 N. R. 1 W. S. 4 T. 1 S. R. 1 W. S. 5 on S. W. with 2 notches on N. & 4 notches on E. edges. Dug excavation pits & formed regulation mound around post.

Land level
Soil 1st qual. Sandy
Drift Gravel Brush under-
growth mostly 10 chs.

Re-Survey S. Bn. T. 12 N. R

Mains East on Re-survey line.
Bet Secs. 4 & 33
Dist 18.10 L.

Stone Fnd Old Cor. Thrown down
& decayed
Set Charred Birch post
3 ft. long 3 ins. Square
12 ins. in the ground, in old
mound of which sufficient
remains to identify the true
position of old cor. from
Re-established 1/4 Sec. Cor
marked 1/4 S. on N. face, in
regulation pits & raised
regulation mound of
earth around post

Stone Fnd Old Cor. which is a
Cottonwood Stake Scorpion
by Marked, thrown down,
I Re-Set same 12 ins. in
the ground in old mound,
of which sufficient Re
mains to identify the
true position of old cor.

Mains Fr
to
Re

Ea
Be

Fn
Co
Re
I 6
in
Be
Sta
Old
Re
Re

6.75 C

BOOK-A-197 = 77

R. 13 W. S. L. M.

Mains For W.C. - established Cor. to Secs. 3, 4, 33 & 34, T. found and mound from regulation pits -
Land flat
Soil, Sandy
Some Deg. brush under growth on 8000 Acs

East on W.C. - Survey line
Bet. Secs. 3 & 34
Var 18° 10' E.

4000 Found Cor. which is a Cottonwood stake with marks nearly effaced, stone down 1 ft. Set stone 12 ins. deep in old mound, of which stones remain, for W.C. - established 1/4 Sec. Cor. marked 1/4 S. on N. face & W. - recorded old mound from regulation pits.

6.75 - Old Road Bears N. & S.

BOOK-A-

Re-Survey S. Bg. T. 12 N. R.

Returns

80.00 Fnd acd cr, which is a Cottonwood Stake Prop'r ly marked, thrown down & misplaced, I Re-set same 12 ins. dep in old mound, of which Brass Bracket, for Re-established Cor. & Secs. 2, 3, 34 & 35 I removed Mound from Irrigation Ditch.

Land Rolling
Soil 1st rate Sandy
Drift Gravel Brush and Grass Growth on 80.00 Acs.

East on Re-survey line Bet. Secs 2 & 35
Lks 18.10 E.

40.00 Fnd acd cr, which is a Cottonwood Stake Properly marked thrown down & misplaced, I Re-set same 12 ins dep in old

R. 13 W. S. L. M.

mound of which bears
S. 89° E. Cor. I found
Old Mound from Regu-
lation pits.
Unity Annex S.
77.50 Find Old Cor. which is a
80.00 Cottonwood Post properly
Marked, Thrown down &
misplaced. I Re-set
Same 12 ins. deep in old
mound, of which bears
S. 89° E. Cor. to Secs. 1, 2, 35 & 36.
I found old mound from
Regulation pits.
Land Rolling
Soil 1st Qual. Sandy
Dense Growth Sagebrush under-
growth in Sec. Cor.

BOOK-A

S. Bx

Re-Survey T. 12 N. R. 13 W.

Chains	
	East on Re-survey line Bet. Secs. 1 & 36. Var. 18.° 10' E.
1.00	Mark trees S.
25.00	Meadow, in bottom bears S. 60 dia wide
	Set Witness Corner S.
40.00	Ind'd Stake Stone Pile which is a Cottonwood Stake Property marked Fr 1/4 Sec. Cor. & Re-mound and pits.
42.00	Mark trees S. W.
53.25	Old Emigrant Road bears N.W. & S.E.
80.00	Ind'd Cor, which is a Rocky Stone 30x15x9 ins. Stones down & properly marked, & Re-set Same 20 ins. deep in old Mound of which Saint Stones remain, for Re-established Cor. to Shs. 11 & 12 N. Rs. 12 & 13 W. & Mound Old &

BOOK-A-197

81

T. L. M.

Mound from Regulation
Pts.
Sand Valley
Dail 1st rate Sandy
Dense Dyer brush under-
growth on 79.50 Chs.
October 3. 1883

General Description

For General Discription
see end of Subdivision
notes of Tps. 22 N. R. 13 W.
Henry Fishbaugh
U.S. Dep. Surveyor

BOOK-A-197

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, February 15th 1884

The foregoing field notes of the re *survey of the*
South boundary
Township No. 12 North *Range No.* 13 West
Executed by Henry Fitzhugh
Under his No 116 *contract of the* 16th
day of July 1883, *in the month of*
October 1883, *having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

Jno Salomon

U. S. Surveyor General for Utah.

016 BOOK-A-197 V 10

REPORT: 1884

Filed 188

Examined by John H. Caupe

Transcribed by E Michaelis

Compared by .....

FIELD NOTES

and resurvey

OF THE SURVEY OF THE

Third Standard Parallel North

R. 15. West and survey of 3d

Stand. Par. North R. 16 West

OF

Township No .....

Range No .....

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Henry Fitzhugh

U.S. Deputy Surveyor,

Under his Contract No. 116

Dated July 16th 1883.

Survey commenced Sept. 26 1883

Survey completed " 27 1883

V

BOOK-A-197

Township 12 South R. 15 West

	91	90	88	86	85	83
108	6	5	4	3	2	1
108	7	8	9	10	11	12
106	18	17	16	15	14	13
105	19	20	21	22	23	24
104	30	29	28	27	26	25
103	31	32	33	34	35	36

BOOK-A-197

Rec- Survey 12

3rd Standard Par. N. R. 15 W.

Plains

On the night of Sept. 25. 1883
I took an observation
of the Star Polaris on its
Eastern Elongation, and
drove pickets on the line
thus established

Survey Commenced Sept.
26. 1883 with a Gurley Transit
Before commencing this
survey I test my Tran-
sit on the line previous-
ly established and find
the variation of the Needle
to be 18° 0' E. which agrees
with the field notes of
this line.
I begin at the Standard

Re-Survey 3rd Standa

Chains

Cor. to Tps. 13 North
14 & 15 W. on the Uni
Meridian which is
Cedar Post Mins. bears
set in the ground & properly
Mkd. by direction Surveyor
Re-Survey Line
W. on S. By Sec. 36
Re 18 & 19
through dense
Note.

Not being able of
diligent search, to f
and identify the 1/4
Cor. on S. side of Se
32 I find it nece
to make Re-Survey
this line to that
4.00 Find old Cor., which
Cedar Post properly m
for Standard 1/4 Sec. Cor.
Standing S.

BOOK-A

Wallu

BOOK-A-197 = 884

Gerallet M. R. 15 W. S. L. M.

ins and pits being obliterated I erected the same
v find acc Cor. thereon down
& decayed and enough
of old mound remaining
to identify the true locus
of the Cor. I set Cedar post
4 ft. long 4 ins. square 2
ft. in the ground for re-
established Standard Cor. to Secs
25 & 36, marked.
T. 13 N. R. 15 W. S. C. on M.
S. 36 on E. and
S. 35 on W. faces. with
1 notch on E. and 5 on
W faces. Made regula-
tion pits with mound of
earth alongside.
Land Rolling

Re-Survey 2nd Standard vacated

Chains	Soil 1st sort Gravelly, Dense sage brush cov. Origin. set on 8000 Chs.	Chains	
	N. on re-survey line on S. side of Sec. 35 T. 2 S. R. 1 E.		
4.00	Found old Cor. stones down & decayed. Set Chained Cedar post 3 ft. long 3 ins. square in the ground for re-est. lished Standard 1/4 Sec. Cor. Mound 1/4 S. on N. face, with pits & dug Reg. lation pits and mound of earth alongside		
8.00	Found old Cor. stones down 4.00 with mound Literally ft. record - S. re-set		

Nortt. R. 15 W. S. L. M.

Which is a Cedar Post
5 ft. long 4 ins. square
properly marked, 24
ins in the ground for
re-established Standard
Cor to Secs. 34 & 35.
I mean the Mound of Stones
Sand rolling
Soil / St Pats Gravelly
Dense Sage Brush under
growth on 80.00 chs.

West on Re-survey line on
S. side of Sec. 34
18.10 E.

Find old Cor. stones down
and so small that I
deem it advisable to Set

Re-Survey 3rd Standard Parallel North

Chains		Chains	
	Another - Set Chained Cedar Post 8 ft. long 3 ins. square 12 ins. in the ground for re-established Standard 1/4 Sec. Cor. Marked 1/4 S. on N face with S.C. Acid mounds and pits of which traces were found.		
48.50	Creek drains S.	20.50	
8.00	Mid Cr. which is dry standing but not marked 40.00		
	x no mounds or pits.		
	I mark S.C. with 3 notches on E & W edges for re-established Standard Cor. to Secs. 2 & 3 & 34. Dug pits	43.50	
	Latin pits and raised mound of earth alongside		
	Land rolling	49.50	

...alled North R. 15 W. S. L. M.

...d Cedar Hands	Axle 1st & 2nd posts
...dgman	Bears Dogs Trees under=
...for	brush on 8000 Acs.
...edars	
...1/4 S.	
...ward	West on Re-Survey line on
...f which	S. side of Sec. 33
	T. 18. N. R. 10. E.
20.50	Creek S. W.
...and 81.00	Creek S. W.
...man 4.00	Find old cor. which is a
...ts.	Cedar post, standing and
...ver=	properly marked for stand=
...ed Cor	ard 1/4 Sec. Cor. & mound
	Mound & pits
...f Reg 3.50	Creek Drains S. W.
...ed Mo	Enter Broken, rough Mountain
	Lean dense Dogs Trees
49.50	Road Lean N. W. & S.

Re-Survey 3rd Standard Parall

Chains		Chains
5.30	Does Corner 6 lks. N&E	
	lies. deep mine S.E.	
80.00	Said Cor. which is a Mariz	
	Stone 9x14x4 ins. above gr	6.50
	Standing and mounded an	40.00
	Without mound or pits.	
	I Mark S.C. with 4 notch	
	on E & W on N. edges for	
	Re-established Standar	
	Cor. to Secs 32 & 33, and	
	raised a mound of ston	
	alongside	
	Land high, rolling & Mountai	
	Soil 2nd & 3rd rate	57.50
	Dense Sage brush under	
	growth on 43.50 chs.	70.00
	Mountainous on 36.50	80.00
	Augmented on 80.00 chs	

Canal — Mark R. 15 N. S. L. M.

nide	Chains	West on N. Survey line on
E.		S. side of Sec. 32
Granite		[illegible] 1810 E.
ers gr	6.50	Road bears N.W. Found
ked an	0.00	Stone, Broken clear Quartz Mountain
hills.		Found old Cor. Standing, Which
notch		is a granite Stone firmly
es for		set in the ground, and properly
adian		marked with mound of
and		Stone alongside for Standard
t Stn		1/4 Sec. Cor.
		End of Resurvey
		beginning of Survey
mountain		
ats	7.50	High ridge bears S.E. thence
undred		along Summit to
chs.	0.00	Same ridge bears N.W.
	0.00	Set granite 21×6×3 ins. 15
Pchs		ins. in the ground for Stand=
		ard Cor. to Secs. 31 & 32
		Marked S.C. Mk. 1 notch

3rd Standard Parallel

Chains

West and 5 on E. edge
and raised a mound of
stone alongside
Land Mountainous
Soil 2nd & 4th Qts. Rocky
Tim. Scat. Cedars
Mountainous on 8.00 Ch.

West on S. Side of Sec. 31
& Cor. 18. & 19

Through dense Cedars.
30.00 Scarce dense Cedars.
4.00 In creek drains S.
Set Mastzite 14×14×4 ins-
9 ins. in the ground for
Standard 1/4 Sec. Cor.
Marked S.C. 1/4 on N. face
and raised a mound of

Chains
8.00

BOOK-A-

BOOK-A-197 — 92

R. 15. W. L. L. M.

Stone alongside

Set granite 19×4×7 ins. 12 ins
in the ground for Standard
Cor. to T. 13 N. R. 15 & 16 W.
Marked S. C. with 6 notches
on N. E. & W. faces, and
buried a mound of stone
alongside.

Land Mountainous
Soil 4th Rate Rocky
Some Cedars on 30 chs.
Mountainous on W. "

General Description
Part of the land on the South
side of this line has been
subdivided. The land on
the N. side is mostly

3rd Standard Parallel North

93 R. 15 W. 5th P. M.

Chains	high Broken mountains unfit for cultivation with the exception of some good land among Rocks	Chains	
	Sept. 26. 1883	7.00	
		4.00	
		32.00	
		4.00	
		16.00	
		.00	

BOOK-A-191

3rd Standard Corner North

Range 16 W. S. L. M. 1884

Survey Commenced Sept. 27. 1883

Chains. From the Cor. to T. 16 & 17 N. Rs.
16 & 17 W. established by
me during this survey
I run
West on S. bdy of Sec. 36
18.10 L.

7.00 Gulch Drains S.

1.00 High ridge bears N.E. & S.W.

37.00 Deep gulch drains N.E.

40.00 Set quartzite 18 x 2 x 4 ins. 12
ins in the ground for Stand=
ard 1/4 Sec. Cor. Marked 1/4 S. C.
on N. face, and piled a
mound of stone around
Entire high basin N.W. & S.W.

46.00 Gulch Drains N.E.

50.00 Set quartzite 16 x 9 x 4 ins - 10
ins. in the ground, for Stand=
ard Cor. to Secs. 35 & 36.

BOOK-A-197

Township 12 North R. 16 West

100	99	98	96	95	94
6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

3rd Standard Parallel North

Chains

Marked notch E and S
~~notches~~ on N. edges
Obtained a mound of stone
surveyed
Land Mountainous
Soil 1st & 3rd rate.
No timber
Mountainous on West

Chains

80.00

West on S. side of Sec. 36
Dec 18° 10' E.

33.00 Road N. & S.

40.00 Set quartzite 19x4x3 ins 1½
ins in the ground for 1/4 1/4 Sec. Cor.
and 1/4 Sec. Cor. Marked
S. C. on N. face and

BOOK-A-127

96

R. 16 W. S. L. M.

Chains
80.00 a Mound of stone and pits
Set quartzite 27×5×4 ins-18
ins. in the ground for Stand=
ard Cor. to Secs. 34 & 35,
Marked 2 Notches on E. and
4 notches on W. edges with
S. S. and found a Mound
of stone near said
Land high Mountains
Soil Hard Rocky
No timber
Mountainous on South.

West and South sides of Sec. 34
Var 18.10 E.

12.00 High ridge runs N.E. & S.W.
36.50 Deep gneck drains N.E.
40.00 Set quartzite 23×11×6 ins-15

3rd Standard Parallel North

Chains in. s. in the ground for
Standard ¼ Sec. Cor. Mark
¼ on N. face with S.C
and found a mound of
Stone alongside
58.00 Gulch drains &
70.00 High divide Ens. E. &
Ascend.
80.00 At head of gulch drains N
Set quartzite 20×5×4 ins. 146.50
ins. in the ground for Stan 80.00
and Cor. to Secs. 33 & 4,
Marked S.C. with Bowche
on E. & W. edges and pits
a mound of Stone alongsid
Land high Mountains
Soil 2nd rate.
Fine Bunch grass.
Mountains N 80.00 ch

Chains

12.00
0.00

R. 16 W. S. L. M.

Trans West on S. Bdy. Sec. 28
Dec 18° 10' E

High ridge bears N. W. & S. E.

Set Stone 25×8×2 ins. 15 ins. in the ground, for Stand-ard 1/4 Sec. Cor. marked 1/4 with S. C. on N. face and raised a mound of stone alongside.

Gulch Trans N. W.

Set granite 20×6×4 ins - 15 ins in the ground for Stand-ard Cor. to Secs. 32 & 33, Marked 4 notches on E. and 2 on W. edges with S. C and raised a mound of stone alongside.

Land Mountainous
Soil 2nd Class

3rd Standard Parallel North

Chains		Chains	
	Fine Buckgrass		
	Mountains on S.		
	West on S. side of Sec 3		
	Var. 18° 10' E.		
14.00	Creek Course N.W.		
25.00	Creek " N.		
40.00	Set quartzite 20×12×3 ins.		
	15 ins in the ground for		
	Standard 1/4 Sec Cor. Mar-		
	ked 1/4 on N. face with S.		
	and raised a mound of		
	stone and ashes		
46.25	Junction Creek 7 lks. wide	32.00	
	6 ins. deep runs N.W. in	40.00	
	Creek -		
	Course.		
80.00	Set Quartzite 16×12×3 ins. 10 ins		
	in the ground for Standard		

BOOK-A-197 = 100

R. 16. W. S. L. M.

Trans Cor. to Secs. 31 & 32 marked
5 notches on E. and 1 notch
on W. edges with S.C.
and raised a mound of
stone all sides
Land Limitations
Soil 1st & 4th Rate
Fine grass
Limitations on do. chs.

West mid. pts of Sec. 31
Ld 1810 E

3.00 Creek drains S.E.
4.00 Set granite 17x8x6 ins. 12
ins in the ground, for
Standard 1/4 Sec. Cor. Mark
ed 1/4 on W. face with S.C.
and raised a mound of

3rd Standard Parallel North

Chains		Links
6300	Stone alongside Gulch drains S.E.	
8000	Set Stone 12×9×6 ins. 15 ins. in the ground, for Standard Cor. to S. 16 & Cs. 16 & 17 West, marked 6 notches on N. & W. edg with S.C. and raised a mound of stone alongsid	
	Land Mountainous.	
	Sol 1st & 4th rate	
	Fine grass	
	Mountainous on 8000 ch	
	Sept. 27. 1883	

Note. It was my intention to make the connection between this line fro the East and the Stan

R. 16 W. S. L. M.

ains dard from the West.
but owing to a severe
snow storm which lasted
3 days and covered the
intervening mountains,
which are very high & broken,
with snow to such a depth
~~that~~ it was impossible

General Description
The Township on the S. side
of this line is mostly high
broken Mountains. That
on the East embraces part
of Jumpkin Valley in
which there are some
settlements - This Township
Planed by Subdivided
Henry Pittsburgh
U. S. Dep. Surveyor.

BOOK-A-197

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, February 15th 1884

The foregoing field notes of the survey of the 3rd and resurvey
Standard Parallel North R. 15 West and survey
of 3d Standard Parallel North R. 16 West

Township No. — *Range No.* —

Executed by Henry Fitzhugh

Under his *contract* No. 116 *of the* 16th

day of July *1883., in the month of*

September *1883., having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

Fred Salomon

U. S. Surveyor General for Utah.

BOOK-A-197 — 103

11

17

REPORT 1884

Filed 188

Examined by John K Campbell

Transcribed by Jim A Mitchell

Compared by .....

FIELD NOTES

OF THE SURVEY OF THE

West Boundary

Township No 12 North

Range No 15 West

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Henry Fitzhugh

U.S. Deputy Surveyor,

Under his Contract No. 166

Dated June 16 1883

Survey commenced September 25 1883

Survey completed 4 1883

BOOK-A-197 — 103

W. By. J. 12 N. R. 15 W. S. L. M.

Chains

Survey Commenced with a Gurley Transit & set stone 25.8 [illegible]

From this Cor. to Twps 11 & 12 N. Rs. 15 & 16 W set by me during this survey I note

Notes Bet. Secs. 31 & 36. Var 18° 10' E.

12.50 Enter rolling brush bears E & W. & dense sage brush undergrowth scoria broken cedar Mountains

36.00 Road bears S. E. & N. W.

40.00 Set quartzite 20 x 8 x 3 ins. 16 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on W. face, day regulation pits & stone regulation mound alongside

80.00 Set quartzite 13 x 8 x 5 ins. 10 ins. in the ground for Cor. to Secs. 25, 30, 31 & 36, marked 1 notch on S. & 5 notches on N. edges, day regulation

W. Bg. T. 12 N. R. 15 W.

Chains | Hills & raised regulation mound alongside Sand mountains & brush Sec 1st & 3rd nats. Mountains on 12.50 chs. Dense sage brush under growth on 67.50 chains. Augmented on 80.00 chs.

North brt. secs. 25 & 30 Var 18° 10' E

40.00 Set Stone 24x6x14 ins. 16 ins. in the ground for 1/4 sec Cor. Scribed 1 & on W. face, dug regulation pits & raised regulation mound alongside

60.00 Eden Traversed hills bear E & W. & scattering cedars Dense sage brush

80.00 Set quartzite 14x11x5 ins. 10 ins. in the ground for Cor. to secs. 19, 24, 25 & 30

Chains | Mo... H... du... Sta... alo... L... S... N... D... G... A...

10.00 Sea... Eas... N.W... Dr... Set... ins... Sec...

S. L. M.

Trees marked 2 notches on S. & 4 notches on N. edges, dug regulation pits & raised regulation mound alongside

Land mountainous & brush

Soil 18" + 32" bats

Mountainous 15.00 chs.

Dense sage brush undergrowth on 65.00 chs.

Easy rolling on 20.00 chs.

North Bet. Secs. 19 & 24

Va 18.10 E.

10.00 Lava broken mountainous

Easy rolling brush bears N.W. & S.E. X

Dense sage brush

40.00 Set quartzite 8x6x4 ins. 12 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on N.

W. Bg. T. 12 N. R. 15 W.

Chains		Links
	Face, dug regulation pits & mound & regulation mound alongside	
67.50	Road bears E & W.	67.00
80.00	Set quartzite 15 x 8 x 7 ins - 10 ins. in the ground for Cor. to Secs. 13, 18, 19 & 24 mark'd 3 notches on N. & S. edges dug regulation pits & mound regulation mound of earth alongside	67.00
	Land mountainous & brush Soil 1st & 3rd rate Mountainous on 10.00 chs. Dense sagebrush, undergrowth on 70.00 chs. Augmented on 80.00 chs.	78.50
		80.00
	North bet. Secs. 13 & 18 on 18.00 E.	
80.00	Set quartzite 17 x 9 x 6 ins - 12 ins. in the ground for 1/4 Sec. Cor. Marked 1 x on W.	

BOOK-A-197 - 107

S. L. Mc.

Lens	face, dug regulation pits & paired regulation mound of earth alongside
60.00	Ascend broken rocky mountains bear E & W.
	Scour sage brush undergrowth
67.00	Ridge bears E & W.
78.50	Gulch drains W.
80.00	Set quartzite 13x8x5 ins - 10 ins. in the ground for Cor. to Secs. 7, 12, 1378, marked + notches on S. & E on N. edges & paired a mound of stone alongside
	Land mountainous & brush
	Soil light & dry
	Mountainous 20.00 chs.
	Dense sage brush undergrowth 50.00 chs.
	Augmented 10.00 chs.

Mark Bet. Secs. 7 & 12
Va 18.10 E.

Y. By. T. 17 N. R. 15 W.

Chains	
40.00	Marked Stationary Mound Boulder 8 × 2½ × 1½ ft. above ground 1/4 on W. face for 1/4 Sec. Cor. & passed a mound of stone alongside & a (+) cross
40.00	High ridge bears E. & W. Descend
80.00	Set quartzite 23×6×4 ins. - 17 ins. in the ground for Cor. to Secs. 1, 6, 7 & 12, marked 5 notches on S. & 1 notch on N. edges & passed a mound of stone alongside
	Land Mountainous
	Soil Hard & rocky
	Mountainous on 80.00 Chs.

North Bet. Secs. 1 & 6

Va 18.10 W.

40.00	Set quartzite 24 × 3 × 5 - ins 16 ins. in the ground for 1/4 Sec. Cor. Marked 1/4 on

Chains	
61.00	W. of
61.50	E. Ba
80.25	Set 13 Set 15 ins ing W. S. & Ba alo

S. L. M.

Land W. face x mound
of Stone alongside
61.00 Wash in ditch gulch drains
E.
61.00 Rail in same gulch bears
E & W.
Record
80.21 Intersect 3rd Standard
parallel North 1 chs. E.
of Standard Cor. to Ps.
13 N. Rs. 15 & 16 W. Mound
set Quartzite 20×18×12 ins.
15 ins. in the ground for clos-
ing Cor. to T. 12 N. Rs. 15 & 16
W. Mound S. notches on
S. & W. edges with C.C.
& pound a mound of stone
alongside

Land mountainous
Soil 40 Rocky
Mountains in 80.21 chs.

September 28. 1883

110

W. By. T. 12 N. R. 15 W. S. L. M.

Remarks	General Description
	There is some good farming land & cedar timber on this tp. The Eastern half has already been subdivided

Henry Fitzhugh
U.S. Dep. Surveyor

U. S. SUR

Salt L

The f

We

Township N

Executed by

Under W

day of

Dep. S

amined, the

the said fie

hereby appro

BOOK-A-197

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, February 15th 1884.

The foregoing field notes of the survey of the West Boundary

Township No. 12 N. *Range No.* 15 W.

Executed by Henry Fitzhugh

Under His No. 116 *contract of the* 16th

day of June 1883, *in the month of*

September 1883 *having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

Fred Salomon

U. S. Surveyor General for Utah.

Second Description Recorded

18 BOOK-A-197

REPORT: 1884

Filed 188

Examined by John A. Campbell

Transcribed by E. Michaelis

Compared by .....

FIELD NOTES

OF THE SURVEY OF THE

South boundary

OF

Township No 12 North

Range No 17 West

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Henry Fitzhugh

U. S. Deputy Surveyor,

Under his Contract No. 116

Dated July 16th 1883.

Survey commenced Septembers 21 1883

Survey completed " 21 1883

BOOK-A-197

Township 12 South R. 17 West



BOOK-A-197

South Boundary Tp. 12 N. R 17 W

Survey commenced
Sept. 21. 1883
With a Burley Transit
On the night of Sept. 20 83
I took an observation of
the Star Polaris on its
eastern elongation in order
to establish the true
Meridian, and drove pickets
on the line thus established

Before commencing this
Survey I test my Transit
on the line established
last night and find it
correct.

From the cor. to Tps. 11 & 12 N.
Rs. 17 & 18 W. which is a
White Quartz 16 x 12 x 12 in
firmly set in ground, marked
with 6 notches on N. S. E & W
Edges with reg. mound & pits
I run East on a random line

South Boundary Tp. 12 N. R 17 W

lks		lks.
lks	Met. Tps. 11 & 12 N. R. 17 W.	40.00
	the var. of my Transit being	
	18° E. I set temporary half	
	mile and mile corners	
	at each 40 and 80 chs. and	
	find the Township line	
	to be 5 miles 77 lks and	5.77.00
	58 lks. long and the fallin	
	to be 1.80 lks. N. of the cor	8.00
	to Tps. 10 & 11 N. R. 16 & 17 W	
	The correction for the	
	true line will therefo	
	be 2.50 chs. W pr. mile an	
	30 lks. S. pr. mile and its	
	course will be N. 89° 47'	
	From the cor. to Tps. 11 &	
	N. R.s 16 & 17 W. set by an	
	I run	
	N. 89° 47' W on a true	
	line Met. Brs. 14 36	
	Va. 18° E	
2.00	Main clear creek Mea	11.00
	bear. Ups.	

Salt Lake Meridian

40.00 Set Limestone 26x7x4 in. 18 in. in ground for 1/4 Sec. cor. marked 1/4 on N face, with stone mound alongside.

Pine Creek in Canon 6 lks. wide 1 ft. deep runs N.W.

8.00 Set Limestone 15x8x8 in 10 in. in ground, for Cor. to Secs. 1 & 2, 35 & 36, marked with 1 notch on E and 5 on W. edges with stone mound alongside

Land very broken Mtns. Soil 2nd & 4th rate Mountainous on 80 chs

North 89° 47' W on true line bet Secs. 2 & 35

Va. 18° E.

11.00 High rocky Ridge runs N & S.

South Boundary Tp. 12 N. R. 17 W

chs.	
40.00	Set Limestone 20 x 10 x 7 in. 15 in. in ground, for 1/4 Sec. cor. marked 1/4 on E face with Stone mound alongside.
48.00	Gulch Drns. S. W
80.00	Set Limestone 23 x 13 x 8 in. 18 in. in ground, for cor to Secs. 2. 3. 34 & 35. marked with 2 notches on E and & on W. Edges with Stone mound alongside.
	Land Mtns. Soil 2nd & 4th rate Mtns Timbered Soil
	N. 89° 41' W. on true line bet. Secs. 3 & 34 Va. 18° E.
34.00	Ridge Drs. N. E. & S. W
40.00	Set Limestone 17 x 9 x 6 in. 12 in. in ground, for 1/4

Salt Lake Meridian

	Sec. cor. 1 with regulation mound of earth and Pits alongside. marked 1/4 on N. face
6.00	Drilled drus S. W.
8.00	Limestone 19 x 8 x 8 in. 14 in. in ground for cor. to Secs. 3, 4, 33 & 34 marked with 3 notches on E and W. edges with reg. pits and mound of earth alongside.

Land Mtns.
Soil 1st rate
Good grass
Mountainous on 80 chs

N 89° 47' W. on a true line bet. Secs. 4 & 33
Va. 18° E.

8.00	Ridge brs. N. W. & S. E. Second high Mtns.
4.00	Dry Gulch drus N. W. set Granite 18 x 8 x 3 in. 12 in. in

6 116

South Boundary Tp. 12 N. R 17 W.

chs.		chs
	ground for 1/4 Sec. Cor.	10.00
	marked 1/4 on N face with	33.50
	2 Eq. pitts and mound of	40.00
	Earth alongside	
73.00	Ridge bears N. E. & S. W.	
	Enter scattering Cedars	
80.00	Set Sandstone 15 X 8 X 5 in	
	10 in. in ground for cor	
	to Secs. 4. 5. 32 & 33. mar	48.00
	with + notches on E and	62.00
	2 on W. edges, North Eq.	80.00
	pitts and mound of Earth	
	alongside. From which	
	Cedar 7 in dia bears S. 7° E. 6 lks. d	
	marked T. 11 N. R. 17 W. S. 4 B. T.	
	No other trees near.	
	Land Nitus	
	Soil 1st rate	
	Mountainous and Rocks	

N. 89 1/4 W. on a true line
bet. Secs. 5 & 32
Va. 18 Lks

Salt Lake Meridian

chs
10.00 Broad hollow drns N. W.
33.50 Ridge brs. N. W. & S. E.
40.00 Set Limestone 13 x 7 x 7 in.
8 in. in ground for 1/4 Sec.
Cor marked 1/4 on N face
Cedar 7 in. dia. brs. S. 50° W 15 lks.
" 13 " " " N. 70° E. 20 "
Both marked 1/4 S.B.T.
48.00 Gulch drns. N. W.
62.00 Ridge brs. N. W. & S. E.
80.00 Set Quartzite 18 x 7 x 7 in. 7 in.
in ground, for cor. to Secs.
5, 6, 31 & 32 marked with
5 notches on E and on W. edges
with reg. pits and mound
of earth alongside
Land Mtns.
Soil 2nd rate
Fine grass
Mountainous on 80. chs.

N. 89° 47' W on a true
line bet. Secs. 6 & 31

8

118

South Bd. Tp. 12 N. R. 17 W.

Chs.	Va. 16° E.
40.00	Set Limestone 12x8x7 in. 8 in. in ground for 1/4 Sec. cor. marked 1/4 S on N face with reg. pits and mound of earth alongside
5.00	Road bro. N. E. & S. W.
	Enters Swallow drs. S. W. & Aims Log Br.
7.00	Wash drs. S. W.
7.50	The cor. to Tps. 11 & 12 N. R. 17 & 18 W.
	Land Mtns.
	Soil 2nd rate
	Fine grass scattering tree
	Mountainous and [illegible]

Surveyed from the 1st day of September to the 21st inclusive 1881

For General description see subdivisions of this Township.

Henry Flaherty
U.S. Dep. Surveyor

U. S. SURVE

Salt Lak

The foreg

Township No.

Executed by

Under

day of

Depu

amined. the nece

the said field n

hereby approved.

BOOK-A-197

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, February 15th 1884.

The foregoing field notes of the survey of the South boundary

Township No. 12 North *Range No.* 17 West

Executed by Henry Fitzhugh

Under his *contract* under date of the 16th *day of* July *1883, in the month of* September *1883, having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

Fred Salomon

U. S. Surveyor General for Utah.

BOOK-A-197

REPORT: 1884

Filed 188

Examined by John McCampbell

Transcribed by L. W. Hickok

Compared by C. S. & L. W. H.

FIELD NOTES

OF THE SURVEY OF THE

West Body

OF

Township No 12 North

Range No 17 West

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Henry Fitzhugh

U. S. Deputy Surveyor,

Under his Contract No. 116

Dated May 16 1883

Survey commenced Sept. 29 1883

Survey completed " 29 1883

BOOK-A-197

Co. Bdy. S. 12 N. R. 17 W.

Lands S. L. M.

Survey Commenced with a
Gurley transit September 29. 1883
from the Cor. to Sec. 11 & 12 N.
Rs. 16 & 17 W. established by
the during this survey
Mound 18 Set Sec. 31 & 36
Var 18° 10' E.
Alm E. slope of high ridge to
4.00 Set Granite 18x10x8 ins. 12 ins
in the ground for 11 & Sec. Cor.
marked 11 on W. face & paired
a Mound of Stone alongside
5.00 Dap gneck draws NE
9.00 Cut high ridge bears NE & SW
Set Limestone 22x9x5 ins.
5 ins. in the ground for Cor.
to Secs. 25, 30, 31 & 36, mark-
ed 1 notch on S. & 5 notches
on N. edges, & paired a
Mound of Stone alongside
Land high & mountainous

120

E. By. T. 12 N. R. 7 W.

Chains		Chains
	Coal Hill Quartz-Rocky	
	to Finder	
	Mountainous on 800 Acs.	
	North Bet Secs. 25 & 30	
	T. 13 N. R. 7 W.	
37.00	Cairn trans N E	
40.00	Set Granite 20×10×9 ins - 15 ins	
	in the ground for 1/4 Sec. Cor	
	marked 1/4 on W. face & Pine	
	a mound of stone alongside	
	from which	
	A pine tree 20 ins. diam. bears	2.50
	N 70° 30' E. 63 lks. dist.	40.00
	marked 14 S. B. T.	
80.00	Set Granite 16×9×8 - ins - 1	
	ins. in the ground for	
	Cor. to Secs. 19, 24, 25 & 30	
	marked 2 notches on S & E	
	N. edges & Pine a mound	
	of stone alongside	
	from which	
	A pine tree 27 ins. diam bears	3.00

S. L. & M.

Items

S. 32° E. 93 lks. dist.
Marked S. 1/2 N. R. 16 W. S. 30 B.T.
A pine tree 10 ins. diam. bears
N. 30° 15' E. 29 lks. dist.
Marked S. 19. B. T. T. R. N. R. 16 W.
Land hilly & mountainous
Soil & rock poor & rocky
Some scattering pine timber
Mountainous on 8000 Acs.

North Bdy. Secs. 19 & 24.
Var. 18° 10' E.

Hills ridge bears N. E. & S. W.
At granite 17 x 8 x 8 ins. 1 x
ins in the ground for 1/4 Sec.
Cor. marked 1/4 on E. face &
raised a mound of stone
alongside
from which
A pine tree 19 ins. diam. bears
N. 38° W. 47 lks. dist.
Marked 1/4 S. B. T.
Deep gulch drains N. E.

E. By. T. 12 N. R. 17 W.

Chains
15.00 Deep gulch drains E.
80.00 Set granite 24×9×8 ins. 18 ins. in the ground for Cor. to Secs. 13, 18, 19 & 24, marked 3 notches on N. & S. edges. & raised a mound of stone alongside
Land high mountains
Soil thin rocky
Some scattering pines
Mountainous on 80.00 chs.

North Bet. Secs. 13 & 18. 80 chs.

22.00 Junction of ridges bear N.W., S.E. & N.E.
40.00 N. deep gulch drains E.
Set granite 17×17×6 ins. 12 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on N. face & raised a mound of stone alongside
59.00 Ridge bears N.W. & S.E.

Chains
80.00 De
ins
Se
No
& 8
alo
6
Jun
1.00 Dee
42.50 High
40.00 Set
ins.
Cor.
Sec
alon
Fro
Ap
N. #

S. L. M.

Chains

80.00 Set granite 21×10×7 ins-15 ins. in the ground for Cr. to Secs. 7, 12, 1308, marked + notches on S. & E. edges. & raised a mound of stone alongside E.

Land high mountains
Soil Mt. Lake rocky
No timber
Mountains on 80.00 Chs.

North Bet. Secs 7 & 12
Lat 18° 10' E.

1.00 Deep creek draws S.E.
12.50 High ridge bears N.W. & S.E.
40.00 Set granite 26×17×4 ins-16 ins. in the ground for 1/4 Sec. Cr. marked 1/4 on E. face & raised a mound of stone alongside E.
From which
Aspens 17 ins. diam. bears N. 47° W. 24 lks. dist.

E. B. T. 12 N. R. 17 W.

Chains	
	A pine tree 9 ins. diam. bears S. 12° E. 85 lks. dist. Post marked 1/4 S. B. T.
4.50	Gneiss rock bears E. W.
	Second ridge E. & W.
8.00	Ridge bears E. & W.
	Set Stone Stone 19 x 13 x 6 ins. 12 ins. in the ground for Cor. to Secs. 16. 17 & 12 Quarter Sec. Notches on S. & W. notch on N. edges & mound of stone alongside from which A pine tree 18 ins. diam. bears N. 69° W. 57 lks. dist. Marked T. 12 N. R. 17 W. 1/4 B. T.
	Land high mountainous soil of slate rocky some scattering pine timber Mountains on 8.00 Chs.

North Bet. Secs. 16, 17 & 18. 10 E.

Chains	
23.00	
40.00	
72.00	
81.20	

L. L. & C.

Miles	
23.00	Levee ridge bears N.W.
40.00	Au Aux Sable Creek bears S.E. & Set Granite 17x8x8 ins. - 12 ins in the ground for 1/4 Sec Cor. Marked 1/4 on W. face, & raised a mound of stone alongside
72.00	Hill ridge bears N.W. & S.E.
81.20	Intersect 3rd Standard and Parallel North 2.30 Chs. E. of Standard Cor. to T. 13 N. R. 16 & 17 W. Where I set Lime stone 16x10x8 ins - 10 ins. in the ground for Closing Cor. to T. 12 N. Rs. 16 & 17 W. Marked 6 notches on S. E. & W. edges with C.C. & raised a mound of stone alongside
	Land high Mountainous
	Soil Slate-rocky
	Timber
	Mountainous on 81.20 Chs

September 29. 1883

126

E By. T. 12 S. R. 17 W. S. L. M.

Chains

General Description

The land embraced in this Township is mountainous. There is some good pine timber. It is well watered & affords fine summer range for stock.

Henry Fitzhugh
U.S. Dep. Surveyor

U. S. SURV

Salt L

The for

Co

Township No.

Executed by

Under his

day of Ju

Septem

amined, the nec

the said field

hereby approved

BOOK-A-197

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, February 15th 1884.

The foregoing field notes of the survey of the East Body

Township No. 12 N. *Range No.* 17 W.

Executed by Henry Fitzhugh

Under Sur No. 116 *contract of the* 16th

day of July 1883, *in the month of*

September 1883, *having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

Fred Salomon

U. S. Surveyor General for Utah.

BOOK-A-197

REPORT: 1884

Filed 188

Examined by John H. Campe.

Transcribed by John A. Mitchell

Compared by

FIELD NOTES

OF THE SURVEY OF THE

3rd Standard Parallel North

OF

~~Township No~~ Through

Range No 18 West.

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Henry Pitchugh.

U. S. Deputy Surveyor,

Under his Contract No. 116

Dated June 16 1883

Survey commenced September 24 1883

Survey completed " 24 1883

BOOK-A-197

Township 12 North R. 18 West

~~128~~	129	130	131	132	~~134~~	X
6	5	4	3	2	1	142
7	8	9	10	11	12	141
18	17	16	15	14	13	140
19	20	21	22	23	24	138
30	29	28	27	26	25	137
31	32	33	34	35	36	136

3rd Stand. Parallel N. R. 18 W.

Chs, On the night of Sept 23 1883 took an observation of the Star Polaris at its Eastern Elongation in order to determine the Correct Variation of the needle and find it to be 18° 00' E,

---

Survey Commenced Sept. 24. 1883

Before Commencing this Survey I test my transit on the line established last night and find it Correct.

I begin at the Standard Corner to Tps. 13. N. Ranges 18 & 19 West. on the Guide Meridian, which is a limestone about 4 x 12 x 12 ins. above ground, with Bronze Cap: Capped Quarter Sec. Corner Posts

32d Stand Parallel North. Range

Chs.		Chs.	
	Thence 1 gun East on S. side of Sec. 31. Va. 18° E.		
3,00	Deep Gulch bears N.		
3,50	High divide bears S.W. & E.		
4,00	Set a Shale rock 24x6x5 ins, 14 ins, in the ground for Standard 1/4 Sec. Cor. marked 1/4 on N. face with S.C. and raised a mound of stone alongside.	4,00	Head
		18,00	Deser
			bear
		40,00	Set
			ins,
			1/4 S
60,50	Head of Gulch bears S.E. & N.		N.
73,00	Spring bears S. 19° 20' W. 14 Chs. dist.		Mon
	Spring bears S. 30 Chs. dist.	52,00	Head
80,00	Set Limestone 17x12x4 ins, 11 ins, in the ground for Standard Corner to Secs, 31 & 32, marked S.C. with 5 notches on E. & 1 notch on W. edges, and raised a Mound of stone alongside.	80,00	Set
			ins, ins
			Cor. to
			S.C.
			2 ins
			X 18 X
			Stone
			raise
	Land, High broken Mountain Soil, 3rd & 4th rate, rocky		2 ft.

Range 18 West.

	chs.	Fine grass for grazing, Mountainous on So. chs,
		Carbon S. side Sec, 32, Va. 18° 00' E,
	4,00	Head of Gulch drains S.W,
	18,00	Descend from high divide, bears N. & S,
	40,00	Set limestone 20 x 11 x 8 ins, 13 ins, in the ground for Standard 1/4 Sec Cor, marked 1/4 S.C, on N. face, and raised a Mound of stone alongside
	52,00	Head of gulch drains S.E,
	80,00	Set a limestone 20 x 10 x 8 ins, 15 ins, in the ground for Standard Cor. to Secs, 32 & 33, marked S.C. with 4 Notches on E and 2 on W. edges, dug pits 18 x 18 x 12 ins, N.E. & W. of stone 5 1/2 ft. distant and raised a Mound of earth 2 ft. high 4 1/2 ft. base

3rd Stand. Parallel North.

Chs.	Alongside, Land high broken Mountains, Soil, 1st & 3rd rate, Fine grass for grazing. Mountainous on 80. chs.	
	Easton S. Boundary Dec. 38, Va. 18°00' E.	
27,50	Head of Gulch, drains S.E.	
35,00	High ridge bears N.W. & S.E.	
40,00	In small gulch drains S. Set a limestone 13×7×7 ins, 9 ins, in the ground for Stand. 1/4 Sec. Cor, Marked 1/4 S.C. on N. face, dug pits 18×18 & 12 ins, E. & W. of stone 5½ ft, distant, and raised a Mound of earth 1½ ft. high 3½ ft. base alongside.	40,00
80,00	In grassy hollow drains S.E. Set limestone 15×10×5 ins, 10 ins in the ground for Standard Cor. to Secs. 33 & 34. Marked	67,00 / 1,00

BOOK-A-197

Range 18 West.

with 3 notches on E. & W. edges with S.C. dug pits 18×18×12 in, 5½ ft. dist, and raised a mound of earth 2 ft. high, 4½ ft. base alongside, Land, Mountainous Soil, 1st & 2nd rate, Fine grass for grazing, Mountainous on 80.00 Chs.

East on South side Sec 34 va. 1800 E,

40.00 Set limestone 13×9×6 in, 8 in. in the ground for Standard 1/4 Sec. Cor. Marked 1/4 S.C. on N. face, dug pits. 18×18×12 in E. & W. of stone 5½ ft. dist, and raised a mound of earth 1½ ft. high, 3½ ft. base alongside,

67.00 Ridge bears N.W. & S.E.

1.00 In small meadow bears N.W. & S.E. Set Quartz 12×8

3rd Stand. Parallel North.

Chs.	X 8 in. 8 in. in the ground for Standard Cor. to Secs. 34 & 35 marked 2 Notches on E. & W. edges, with S.C. dug pits 18 x 18 x 12 in. N.E. & N.W. of Stone. 5 1/2 feet dist. and raised a mound of earth 2 ft. high, 4 1/2 ft. base, alongside, Land Mountainous Soil. 1st rate, Fine grass for grazing, Mountainous on 80. Chs.

East on South Side Sec. 35
Va. 18° 00' E.

17.00	Enter grassy hollow, drains S.
19.00	North fork of Goose Creek 9 Lks. wide, 7 ft. deep, runs S.E.
33.00	Leave hollow, Enter Mountain bear N.W. & S.E.
40.00	Set Shale 25 x 18 x 3 in. 15 in. in the ground for Standard

Range 18 West,

1/4 Sec. Cor. marked 1/4 S.C.
on N. face, dug pits 18x18x12 in.
E. & W. of stone 5½ ft. dist. and
raised a Mound of earth 1½
ft. high, 3½ ft. base alongside,
4,50 Ridge bears N.W. & S.E.
6,50 Creek in grassy Hollow 6 lks.
wide 4 in. deep, runs S.W.
8,00 Set Quartzite 19x7x6 in, 12 in.
in the ground for Standard
Cor. to Secs. 25 & 36, marked
1 Notch on E. & 5 on W. edges,
with S.C. dug pits 18x18x12
in, N.E. & W. of stone, and
raised a Mound of earth
2 ft. high 4½ ft. base
alongside,
Land Mostly Mountainous.
Soil, 1st & 2nd rate,
Fine grass for Grazing,
Mountainous on 64. Chs,

1324

3rd Stand. Parallel North.

Chs.	
	Eaton South Side Sec. 36, Va. 18° 00' E.
23,00	Ridge bears N.E. & S.W.
29,00	Wash in hollow drains S.W.
	Ascend steep Mountains.
40,00	Set limestone 19 x 10 x 5 in. 12 in. in the ground for Standard 1/4 Sec. Cor. marked 1/4 S.C on N. face, dug pits 18 x 18 x 12 in. E. & W. of stone 5 1/2 ft. dist. and raised a Mound of earth 1 1/2 feet high. 3 1/2 ft. base alongside.
56,50	High ridge bears N. & S.
67,50	Deep gulch drains S.
77,00	Ridge bears N.W. & S.E. Descend,
80,00	Set limestone 18 x 8 x 5 in. 12 in. in the ground for Standard Cor. to Tps. 13 N. Ranges 17 & 18 West, marked S.C. with 6 Notches on N.E. & W. edges, dug pits. 24 x 18 x 12 in. Cross line on each line N.E. & W. of stone, 6 ft. dist. and raised

Range 18 West.

Chs, a mound of earth 2½ ft. high,
5 ft. base alongside,
Land Mountainous.
Soil. 1st & 3rd rate,
Fine grass for grazing,
Mountainous on 80. Chs,
Sept. 24. 1883

Note; For General Description
see Subdivisional Notes of
T. 12 N. R. 18 W,

Henry Fitzhugh,
Dep. Surveyor

BOOK-A-197

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, February 15th 1884.

The foregoing field notes of the survey of the

3rd Stand. Parallel North.

~~Township~~ *No.* Through *Range No.* 18 West

Executed by Henry Pitzhugh.

Under Sup Inst'ns *contract of the* 16th

day of June *188*3 *in the month of*

September *188*3, *having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

J. H. Salomon

U. S. Surveyor General for Utah.

BOOK-A-197

24

REPORT: 1884

Filed 188

Examined by John H. Camp.

Transcribed by I. C. Hickok.

Compared by Hickok & Mitchell.

FIELD NOTES

OF THE SURVEY OF THE

East Boundary.

OF

Township No 12 North.

Range No 18 West.

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Henry Fitzhugh.

U. S. Deputy Surveyor,

Under his Contract No. 116.

Dated July 16th 1883.

Survey commenced Sept Number 25 1883.

Survey completed " " 1883.

BOOK-A-197 — 136

East Boundary T. 12 N. R. 18 W. E.

lks. Survey commenced with a Surley Transit. Sept. 25. 1883

From the cor. to Tps. 11 & 12 N. R. 17 & 18 W. which is a white Quartz 6 x 12 x 12 ins. firmly set marked with 6 notches from which a B.O. Ridge pine 12 ins. diam. bears North 60 E. - Sec. 31 & 36 Va. 18 E.

4.50 Leave hollow Enter Gutes Road bears N. E. & S. W.

Enter scattering Cedars

20.00 Wash runs S. W.

30.00 Ridge bears S. E. & N. W.

40.00 Set Limestone 20 x 11 x 4 ins. 5 ins. in ground for 1/4 Sec. cor. marked on W. face with regulation pits and mound of Earth alongside

50.00 Hollow runs N. W.

58.00 Ridge runs N. W. & S. E.

75.00 Road in Gulch runs S. W.

80.00 Set Quartzite 12 x 8 x 7 ins. 4 ins. in ground for cor to Secs.

East Boundary Tp. 12 N. R 18 W

chs.	25. 30. 31 & 36 marked with	chs	
	1 notch on E and S on N Edges		
	with stone mound alongside	68.00	
	Cedar 9 in. dia. brs. N. 10 W. 3 lks. dist	69.20	
	marked T. 12 N. R. 18. W. S. 25 B. T.		
	Cedar 7 in. dia. brs. S. 56° E 20 lks. dist		
	marked T. 12 N. R 17 W. S. 31 B. T.	80.00	
	No other trees at hand		
	Land Mtns.		
	Soil 2nd rate rocky		
	& scattering Cedars & good grass		
	Mountainous on 80 chs		

North bet. Secs. 25 & 30
Va. 18 E.

10.00	Ridge brs. N. E. & S. W.	
40.00	Lst Quartzite 15 x 8 x 4 in. 10 in	
	in ground, for 1/4 Sec. cor.	
	marked 1/4 on W. face, with	
	pits. ditto and mound of earth	
	alongside.	
	Cedar 10 in dia. brs. N. 5° W 40 lks	2.00
	Marked 1/4 S. B. T.	

Salt Lake Meridian

no other tree suitable for marking at land.
Road brs. N. W. & S. E.
68.00 Enter Hollow Pine Creek 6.20
10 lks. wide 5 in deep runs. W
Fence brs. W. 20 chs.
80.00 Set Quartz 20 x 9 x 6 in. 15 in in ground for cor. to Secs. 19. 24 25 & 30 marked with 2 notches on land & on N. Edges with pits and mound of earth alongside.
Ross Worthington's house brs. S. 70° W
Land Mtns.
Soil 2nd and 1st rate
Scattering Cedars & grass
Mountainous on 80 chs

North bet. Secs. 19 & 24
Va. 18° E.
3.00 Leave hollow, Enter Cedar Hills brs. S. E. & S. W

East Boundary Tp. 12 N. R. 1 W.

chs.	
40.00	Set Quartz 18 x 5 x 5 in. 12 in. in ground for 1/4 Sec. cor. marked 1/4 on W. face, w from which a Cedar 12 in. dia. brs. N. 84° E. 30 lks. distant Cedar 9 in. dia. brs. N. 49° W 15 lks. dist. Both marked 1/4 S. B. & M.
52.50	Leave heavy Cedars & timber Enter Grouse Creek Bottom and Grouse Sage brush. brs. S. W.
55.00	Road trd. E & W
57.50	Middle Fork Creek 6 lks. wide 6 in. deep runs S. W. 20 chs. to Junction with Grouse Creek
80.00	Set Quartz 20 x 8 x 8 in. 15 in. in ground for cor. to Secs. 13. 18. 19 & 24 marked with 3 notches on N. & S. Edges, with regulation pits and mound of earth along said E.

BOOK-A-197 = 1420

Salt Lake Meridian

1847

	chs.	S. E. cor. of meadow bears N. 55° W 4.50 chs. dist. Land Mtns & Flat Soil 2nd & 1st rate Heavy Timber cedars on 52.50 Dense Undergrowth on 27.50 Mountain ore on 52.50 Magnetic variation on 2000 chs.
		North bet. 2 secs. 13 & 18 Va. 18° E.
	40.00	Set Quartz 20 x 8 x 7 in. 15 in. in ground for 1/4 sec. cor. marked 1/4 on W face, with excavation, pits and mound of earth alongside.
	60.00	David Thomas House bears N. 63° W Stable bears N. 53 3/4° W Corral bet. house & stable Stack Yard N of stable
	80.00	Set Quartz 17 x 8 x 7 in. 12 in. in ground for cor to Secs. 7, 12, 13 & 18. marked

1141

East Boundary T. 12 N. R 16 W

chs.		chs.
	with 4 notches on S and	
	low N edges & Mdr	
	Irrigable Unsurveyed Pas	
	Land adjoining	7,600
	soil poor Rate	80,000
	Brush Undergrowth on 80	

North bet. Secs 7 & 12
Va. 1806

16.00	Road brs. N.E. & S.W.	
33.25	Grouse Creek 15 lks. wide	
	2 ft. in. deep runs S.W. about	
	30 chs. to Junction with	
	North Fork of Grouse Creek	
38.00	Road brs N.E. & S.W.	
	Leave Grouse Creek bottom	
	& Brush Sage brush	
	Ascend. Enter scattering	4,000
	Cedars.	
40.00	Set Quartzite 18 x 12 x 7 in	
	12 in. in Ground for 14	
	pre. cor. marked 14 on	
	N. face, with Stone mound	
	alongside	

BOOK-A-197 = 142

Salt Lake Meridian

chs. W Corrall brs. N. 30° E. 85 chs. distant.
Ridge brs E & W
Cw Johnson brs N
Set Quartzite 17 x 4 x 4 in 12 in. in Ground for cor to Secs 1, 6, 7 & 12. marked with 5 notches on S and 1 on N Edges with Stone mound alongside.
Land rolling & Hilly
Soil 1st & 2nd rate
Timber Undergrowth on 38. chs
Mountainous on 42. chs
Augmented on 80.00 chs.

North bet. Secs 1 & 6
Ga. 18° E.
40.00 Set Quartz 10 x 8 x 6 in. 6 in in Ground for 1/4 Sec. cor. marked 1/4 on W. face with notches and mound of Earth alongside. Ascend higher Mountains

East Boundary Tp. 12 N. R. 18 W

chs.	
7350	On top of high Knoll Intersects 3rd Standard Par. N. 2.75 chs. W. of Standard, cor. to Tps. 12 & 13 N. R. 17 & 18 W. quartz & Lime stone 23 x 8 in. 18 in. in ground for closing cor. to Tp. 11 N. R. 17 & 18 W. marked with 6 notches on N. E. & W. Edg. E and b.t. with Regulation pits and mound of Earth alongside Land First rate Soil 1st & 2nd rate scattering Cedars fine grass Mountainous & Hilly Sept. 25. 1883
End of	For Sec Description & Subdivisions lines of this Township

Henry Fitzhugh
U. S. Deputy Surveyor

U. S. SURV

Salt La

The for

East

Township No.

Executed by

Under

day of

Sept.

amined. the nec

the said field

hereby approved

BOOK-A-197

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, February 15th 1884.

The foregoing field notes of the survey of the

East Boundary

Township No. 12. N. *Range No.* 18 W.

Executed by Henry Fitzhugh.

Under his No. 16 *contract of the* 16th

day of July *1883, in the month of*

Sept. *1883, having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

Fred Salomon

U. S. Surveyor General for Utah.

BOOK-A-197

1/10

REPORT: 1884

Filed October 23rd 1883.

Examined by John H. Dauphe

Transcribed by (William Koeber)

Compared by O.E.S. & L.W.H.

FIELD NOTES

OF THE SURVEY OF THE

East boundary

OF

Township No 13 South

Range No 1 East

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Augustus D. Ferron

U. S. Deputy Surveyor,

Under his Contract No. 117.

Dated July 5th 1883.

Survey commenced September 21st 1883

Survey completed September 21st 1883.

BOOK-A-197

Township 13 South R. 1 East

6	5	4 182	3 171	2 160	1 146		
		194	180	170	159		
7	8 192	9 179	10 169	11 158	12 147		
		191	178	168	157		
18	17 190	16 177	15 167	14 156	13		
203	202	189	177	165	155		
19 201	20 188	21 176	22 165	23 154	24		
200	199	186	175	164	153		
30 198	29 185	28 174	27 163	26 152	25		
197	196	184	173	162	151		
31 195	32 183	33 172	34 161	35 150	36 145		

BOOK-A-197

[L.—PRELIMINARY OATH OF COMPASSMAN.]

William Kaeber

nnly swear that I will well and truly per-
he duties of compassman, according to
tions given me, and to the best of my skill
ility, in the survey of the Eastern
Subdivision Lines of
to 13 & 14 S. in Range
1 East,

Salt Lake base and meridian in the Terri-
Utah.

William Kaeber, Compassman.

ribed and sworn to before me this 3rd
lay of Sept. 1883.

W. D. Turner

U.S. Dep Surv.

BOOK-A-197

[2.—PRELIMINARY OATH OF CHAINMEN.]

We, Olof Larsen
and Harry Pitchforth
solemnly swear that we will well and faithfully execute the duties of chain carriers; that will level the chain upon even and unon ground and plumb the tally pins, either by cking or dropping the same; that we will port the true distance to all notable objects, and true length of all lines that we assist in easuring, to the best of our skill and ability, nd in accordance with instructions given us, the survey of the additional
xterior and subdivision lines
in Tps. 13 & 14 South of Range
10 East
the Salt Lake base and meridian in the Territory of Utah.

Olof Larsen, Chainman.
Harry Pitchforth, Chainman.
....., Chainman.
....., Chainman.

ubscribed and sworn to before me this 3rd
day of Sept 1883.

R. D. Terry
U.S. Dep. Sur.

BOOK-A-197

[3.—PRELIMINARY OATH OF AXEMEN.]

We, I. James W. Jarrett

nd .....

solemnly swear that we will well and truly per-
rm the duties of axemen, in the establishment
corners and other duties, according to instruc-
ons given us, and to the best of our skill and
ility, in the survey of the Exterior
Subdivisional lines of
Tps No 13 & 14 South Range
No 1 East

f the Salt Lake base and meridian in the Terri-
ory of Utah.

James W Jarrett, Axeman.

....., Axeman.

ubscribed and sworn to before me this 3rd
day of Sept, 188 4

N. D. Green

U. S. Dep. Sur.

BOOK-A-197

Earthworks
Ft. #3. S. R. 1 E.

Survey commenced Septbr 21.
(finished)

BOOK-A-19

East boundary Tp. 13 S.

Survey commenced. April 21.83 with a Burt's improved Solar compass. My special i
from the Surveyor general for the survey
this Tp. ordered me to extend the survey of this T
in accordance with the existing prior survey, bo
in alignment & distances. In retracing the o
Labadie in last year. Took pains to reu
up all the existing old cor. in final val
and after a great deal of labor deter
the claiming to be true measurment but
of lines to be N. 10 W. or in other words that
lines of the old survey were run with a var
of 17½° E. instead of 16½° E. with lat
is the true variation.
The new surveys were therefore m
in accordance with the facts fou

.00.

8.00

.00

East
From
set by

set
the g
1/4 on
mon
Gulo
set
the g
& 36
Son
mon
Lan
Soil
No
Man

BOOK-A-197

East boundary Tp. 13 S. R 1 E.

From the cor. to Tps. 13 & 14 S. R 1 & 2 E.
Set by me during this survey Down
North betw. 31 & 36.
Var. 17½° E.

.00. Set sandstone 12×8×6 in 8 in in the ground for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside.

8.00 Gulch drains S. W.

.00 Set sandstone 18×12×10 in 12 in in the ground for cor. to secs. 25. 30. 31 & 36 marked 5 notches on S. and W. edges and raised a stone mound alongside.

Land mountains.

Soil Grate.

No timber.

Mountainous desert

undergrowth cov 80 chs.

East boundary

Note. On account of bluff 250 high very broken and inaccessi abandon the line here. Then proceed to the cor. to Tps 12, 13 S. R. 1 & 2 E. formerly set by me from which I run

South betw. secs 1 & 6
Var. 17½° E.

8.00	Enter Salt Creek canyon
8.00	Salt Creek 25 lks wide 1½ deep runs S.
12.00	Wagon road W. & E. Telegraph line, E.
12.30	Sanpete Valley R. R. bears N. W. & E.
13.10	Telegraph line bears N. W. & E.
19.00	Ascend
40.00	Witness oak cor, set gypsum 10×6, 6 in the ground for ¼ sec. cor. mea 6.00 in ¼ on W face and raised a stone mound alo Thence offset West 6.00 chs. thence South 40 chs. to a point 6 chs N of 80.00. where I set 2 iron 6.00

BOOK-A-197

Sp. T3. S. R 1E.

14×10×6 i for W.C. to secs. 1. 6. 7 & 12.
marked / notch on 4 & 5 on S. edges
and W.C. and raised a stone
mound alongside.
Land. mountains
Soil State.
No timber.
Heavy mountains & dense
undergrowth on 80 chs.

South betw. secs. 1 and 12
Var. 17½ E.
From Witness 6 chs. W. & cor. point
to secs. 1. 6 & 12. Same South on
offset line 40 chs. thence East 6 chs 50
in place, set hinestone 12×6×6
8 i in the ground for 1/4 sec. cor. marked
1/4 on W. face and raised a stone mound
alongside.
Gulch drains N. W.

148

East boundary Pt. 13 S. R.

8000 Set limestone 16×10×7 in. in the ground for cor. to secs. 7 & 12, 13, 18 marked 2 notches on stand'g on S edges and raised a stone mound alongside.

Land mountainous

Soil Grate.

Timber. some scatt. cedars.

Mountainous descent undergrowth on rocks.

Note. On account of high broken inaccessible bluff I abandon line here.

(Note. For general description see subdivisions of this Pt.)

Augustus D. Person

U. S. Dep. Surv.

U. S. SURV

Salt L

The f

Township N

Executed by

Under In

day of

Sept.

amined. th

the said

hereby ap

BOOK-A-197

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, November 5th *1883*

The foregoing field notes of the survey of the

East boundary

Township No. 13 South *Range No.* 1 E

Executed by Augustus G. Ferron

Under No 117 *contract of the* 5th

day of July *1883, in the month of*

September *1883, having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

Jede Saloman

U. S. Surveyor General for Utah.

BOOK-A-197

REPORT: 1884.

Filed October 28th 1883.

Examined by John H. Campbell

Transcribed by (William Koeber)

Compared by O.E.S + L.W.H.

FIELD NOTES

OF THE SURVEY OF THE

Subdivisions

OF

Township No 13 South

Range No 1 East

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Augustus D. Ferron

U. S. Deputy Surveyor,

Under his Contract No. 117.

Dated July 5th 1883

Survey commenced September 22 1883

Survey completed October 5 1883.

BOOK-A-197

=149

Subdivisions Sp. 13. S. R 1 E

Survey commenced: Septr 22, 83
with a Burt's improved Solar
Compass

By especial instructions from the
Surveyor general for the survey
of this Sp. ordered me to extend
the survey of this Sp. in accordance
with the existing prior survey,
both in alignment and distances.
In retracing the Salt Lake Meridian
last year Stock grains to hunt
up all the existing old survey
cor in Jual Valley, and after
a great deal of labor, determined
the chaining to be true measurement
but all the N. & S. lines to be 1° 10'
W. or in other words, that the
lines of the old survey was run
with 17 1/2° E. variation, instead
of 16 1/2° E. which latter is the
true variation.

The new surveys was therefore
made in accordance with the
facts found.

Subdivisions Tp. 13 S. R. 1

From the cor. to secs. 35 and 3
the S. boundary of this Tp.
set by me Nov
North betw. secs. 35 and
Var. 17 1/2° E.

Descend.

40.00 Set a sandstone 14×10×6
in the ground for 1/4 sec. c
marked 1/4 on W. face and r
a stone mound alongside

43.50 Bottom of Gardeners cany
drains N. W.

60.00 Gulch drains S. W.

80.00 Set a granite 10×8×7 in 6
ground for cor. to secs. 25,
36 marked with 1 notche
S & E edges and raised a s
mound alongside.
Land. Mountains
Soil 2nd. rate.
No timber
Mountainous & dense
undergrowth on 80 ch

BOOK-A-197

divisions Tp. 13. S. R. 16

East on random line
betw. secs. 25 and 36
Var. 17½° E.

Set temporary 1/4 sec. cor.
Intersect E. boundary of the
Tp. at cor. to secs. 25 & 36, set
by me from which I run
West on true line
betw. secs. 25 and 36
with same var.

Set a sandstone 16×8×5 in. 12 in.
in the ground for 1/4 sec. cor.
marked 1/4 on N face and raise
a stone mound alongside.
Enter hollow drains N.
Leave same, ascend.
The cor. to secs. 25. 26. 35 & 36
Land. Mountainous
Soil 2nd rate
No timber.
Mountainous & dense
undergrowth on S. 60 chs.

Subdivisions Tp. 13. S. R. 1

North betw. secs. 25 & 2
Var. 17½° E.

8.60 Gulch drains N. W.

11.75 Road in gulch bears N W. and

30.50 Spring branch in hollow 3 lks w
4 ins deep runs S. W.

40.00 Set sandstone 14×10×6 in 16
in the ground, for 1/4 sec cor.
marked 1/4 on W. face and
raised a stone mound alon
side.

70.00 Hollow drains S. W.

80.00 Set sandstone. 16×8×7 in 6 in
in the ground for cor. to secs
23. 24. 25 & 26 marked with
2 notches on Sand ton Edges
and raised a stone mound
alongside

Land. mountainous
Soil. 2nd rate.
No timber.
Mountainous & dense
undergrowth on 80 chs.

26.00
16.00

BOOK-A-197

Subdivisions Tp. 13. S. R. 1 E.

Note.
The E. boundary not being established I run
East on true line
betw. secs. 24 & 25.
Var. 17½° E
Gulch drains N. W.
Ridge bears N. W & S. E. set
sandstone 10 × 8 × 6 in 6 in in
the ground for 1/4 sec. cor.
marked 1/4 on N face and
raised a stone mound along
side.
Note. On account of high
impassible rocky bluff 10 chs.
east of this point I abandon
line here.
Land mountains.
Soil 3rd rate.
No timber.
Mountainous & dense
undergrowth on 40 chs.
Sept. 22-83.

BOOK-A-

Subdivisions Tp. 13 S. R 1

Subdivis

North betw. secs. 23 & 24
Var. 17 1/2° E.

19.00 Road bears N E & S W.

26.00 Hollow drains S. W.

40.00 Set sandstone 10 x 8 x 7 in 6 in in the ground for 1/4 sec. cor. marked 1/4 on N. face and raised a stone mound alongside.

45.00 Gulch drains S. W.

75.40 Ridge bears E & W.

86.00 Bottom of gulch dr. N. W. set limestone 18 x 8 x 5 in 12 ins in the ground for cor. to secs. 13. 14. 23 & 24 marked with 3 notches on S. and 1 notch on E edges and raised a stone mound alongside

Land mountainous
Soil 2nd rate.
No timber.
Mountainous and dense undergrowth on 80 ch

Note
bein
6

Ri
Can
Set
8 ins
sec.
face
alon
Note.
prop
10 ch
line
Lan
Soi
No
Mo
u

BOOK-A-197

155

Subdivisions Tp. 13 S. R 16 E

Note. The E. boundary not being established I run East on true line betw. secs. 13 and 24. Var. 17 1/2° E.

Ridge bears N. W. & S. E.

Canyon drains N. W.

Set sandstone 12×8×6 in 8 ins in the ground for 1/4 sec. cor. marked 1/4 on N. face and raised a stone mound alongside.

Note. On account of inaccessible perpendicular bluffs about 10 chs. E of this point, I abandon line here.

Land. Mountainous.

Soil 2nd. rate

No timber.

Mountainous & dense undergrowth on 46 chs.

Subdivisions Sp. 13 S. R. 1 E.

North betw. secs. 13 and 14
Var. 17 1/2° E.

6.50	W. point of ridge	
14.75	Gulch draws N. W.	4.00
28.00	" " "	30.00
40.00	Set granite 18 x 15 x 12 in. 14 in. in the ground for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alo side.	
41.50	Ridge bears N. W. & S. E.	3.50
70.00	Gulch dr. N. W.	10.00
75.50	Small gulch dr. S. W.	5.00.
80.00	Set granite 14 x 8 x 6 in. 10 in. in the ground for cor. to secs. 12. 13 & 14 marked with 4 notch on 2 and 1 on Edges and raised a stone mound alongs	40.00
	Land. mountainous	3.00
	Soil 2nd rate.	12.00
	No timber.	20.00
	Mountainous & dense undergrowth on 80 ch	

Subdivisions Sp. 13 S. R 1. E.

East on random line
betn. secs. 12 & 13.
Var. 17½° E.

40.00 Set temp. ¼ sec. cor.

40.00 Intersect East boundary of Sp. at cor. to secs. 12 & 13. formerly set by me from which I run

West on true line
betn. secs. 12 & 13.
with same var.

3.50 Hollow drains N. E.

10.00 Ridge bears N. W. & S. E.

0.00. Head of spring branch bears S. 8 chs.

40.00 Set sandstone 14 x 8 x 5 in. in the ground for ¼ sec. cor. marked ¼ on S. face and raised a stone mound along side.

3.00 Ditch runs N. W.

4.90 Gulch drains N.

0.00 The cor. to secs. 11, 12, 13 & 14.
Land mountainous.
Soil 1st. & 2nd rate.
No timber
Mountainous & dense undergrowth on 8 chs.

Sept. 24 83.

Subdivisions Sec. 13 T. 8 S. R. 5 E.

North between secs 11 and 12

Var 17½° E

15.00 Gulch dr. S. W.

15.00 Ditch bears S. W.

40.00 Set granite 10×8×7. 6 ins in ground for 1/4 sec. cor. mark 1/4 on W. face, raised a stone mound alongside.

43.50 Gulch dr. S. W. Prices Ranch bears S. 85° W. 12.50 dist.

63.50 Gulch drains W.

76.50 Ridge bears S W & S E.

80.00 Set sandstone 12×8×6 ins in the ground for cor. to secs 1. 2. 11 & 12. marked with 5 nicks on sand & on E. edge and raised a stone mound alongside.

Land Mountainous
Soil 2nd rate.
Timber, few cedars
Mountainous & dense undergrowth on 80 ch

40.00 Se

14.20 Se
Cor
6 ch
cor

6.20 Ju
Sp.
sec
ru
sp

00 The
of g
per

2.50 Gu

0.10 Se
gro
1/4 c
sto

2.50 Gul

0.50

0.20 The

BUCK-A-197 = 159

T. R. Subdivisions Tp. 13 S. R. 1 E.

	East on a random line betw. secs. 1 and 12 Var. 17½° E.
40.00	Set temporary ¼ sec. cor.
14.20	S on a point 21 lks. N. of Witness Corner to secs. 1 and 12. Being 6 chs. west of corner point the connection will therefore be
40.20	Intersect E. boundary of Tp. 21 lks. N. of cor. point to secs. 1 & 12 ~~formerly set by me~~ from which I run
	N 89° 51' W on true line betw. secs. 1 and 12. with same var.
80.00	The Witness Cor. on W. side of gulch 200 ft deep with perpendicular sides drains N.
1.50	Gulch dr. N. W.
0.10	Set slate 10 x 8 x ¾ in ¾ in in the ground for ¼ sec. cor. marked ¼ on N. face and raised a stone mound along side.
2.50	Gulch drains N. W.
0.50	" " "
4.20	The cor. to secs. 1, 2, 11 & 12.

Land. mountainous
Soil 2nd rate
Timber scattering cedars.
Mountainous & dense
undergrowth on 80.2

North on random line
betw. secs. 1 and 2
Var. 17 1/2° E.

39.80 To a point 40 lks. West of
1/4 sec. cor. bet. secs. 1 & 2.
formerly established by m
being a sandstone 12 × 8 × 6
firmly set in the ground
marked 1/4 on W. face, and
erected stone mound
alongside. from which
run
S. 0° 34' W. on true line
betw. secs. 1 & 2.
with same var.

11.00 Leave Salt creek canyon, a
15.00 Gulch drains to W.
39.80 The cor. to secs. 1. 2. 11 and 1
Land. mountainous

5.50
40.00
40.50
4.50
1.00

Subdivisions Tp. 13 S. R. 16 E.

Soil 2nd rate
Timber. scattering cedars.
Mountainous & dense
undergrowth on 39.80 ch.
Lgth 25.83.

From the cor. to secs. 34 & 35 on
the S. boundary of the Tp. formerly
set by me Grun
North betw. secs. 34 & 35
Var. 17½° E.
Gulch drains W.
In hollow draining W. set granite
12×8×6 in. 8 ins in the ground for 1/4
sec. cor. marked 1/4 on W. face &
raised a stone mound along side.
Road bears E & W. Ascend
Enter gulch drains W.
Set granite 14×12×8 in. 9 ins in
the ground for cor. to secs. 26. 27.
34 & 35 marked with 1 notch on
S. and 2 on E edges and raised a
stone mound alongside.
Land. mountainous
Soil. 2nd rate.

Subdivisions Tp. 13 S. R. 1 E.

No timber.
Mountainous & dense
undergrowth on 80 chs.

East on random line
betw. secs. 26 & 35
Var. 17 1/2° E.

40.00 Set temporary 1/4 sec. cor.
80.00 Intersect N. & S. line at cor
to secs. 25. 26. 35 & 36. from w. in
Sum
West on true line
betw. secs. 26 & 35
with same var.

6.50 Ridge bears N. W. & S. E.
31.10 Gulch drains S. W.
40.00 Set granit. 10 x 8 x 8 in. in
ground for 1/4 sec. cor. marked
1/4 on N. face and raised a stone
mound alongside.
42.50 Enter flat top of mountain.
55.00 Descend
63.00 Enter canyon flat
80.00 The cor. to secs. 26. 27. 34 & 35

Land mountainous
Soil 2nd rate

8.00
9.00
13.50
35.50
39.00
40.00
44.00
58.60
79.40
80.00

1. E. Subdivisions Tp. 13 S. R. 1 E.

No timber.
Mountainous and dense
undergrowth on 80 lks.

North betw. secs. 26 and 27
Var. 17 1/2° E.

8.00 Rpos bears E & W.
9.00 Leave gulch dr. W.
13.50 Enter flat bears N.E. & S. W.
35.50 Wash drains S. W.
39.00 Road bears N E & S. W.
40.00 Set granite 14×6×6 in 9 in in the ground for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside.
44.00 Wash drains S. W.
58.60 Road, bears N. E. & S. W.
79.40 Gulch drains S. W.
80.00 On N. side of same gulch set granite 12×8×8 in 7 ins in the ground for cor. to secs. 22. 23. 26 & 27 marked with 2 notches on S. and E edges and raised a stone mound along side.

Land. mountainous
Soil 2nd rate

No timber
Mountainous & dense
undergrowth on. 80 lks. 4.50
25.00

East on random line
betw. secs. 23 & 26
Var. 17 1/2° E. 40.00
40.00 Set temporary 1/4 sec. cor.
79.90 Intersect N. & S. line 55 lks W
of cor. to secs. 23. 24. 25 & 26. 80.00
from which I run
N. 89° 36' W. on true line
betw. secs. 23 & 26
with same var.
39.95 Set granite 14 x 8 x 6 ins in
the ground for 1/4 sec. cor. mar
1/4 on N face and raised a stone
mound alongside.
59.90 Road bears S. W. & N. E.
73.00 Road bears N. & S.
79.90 The cor. to secs. 22. 23. 26 & 27
Land. mountainous
Soil 2nd rate.
No timber.
Mountainous & dense 0.00

1 E. Subdivisions Tp. 13 S. R 1 E.

North betw. secs. 22 and 23
Var. 17½° E.

Chs. 4.50 Leave flat, ascend
25.00 Ridge bears E. & S. W.
Road bears N. W. & S E.
40.00 Set granit. 10×8×8 in 6 in in the ground for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside., Enter little valley
80.00 Set granite 14×10×6 ins in the ground for cor. to secs. 14. 15. 22 & 23. marked with 3 notches on S and 2 on E edges and raised a stone mound alongside.
Land, mountainous & valley
Soil 1st & 2nd rate.
No timber.
Dense under growth on W dn.

East on random line
betw. secs. 14 and 23
Var. 17½° E.

0.00 Set temporary 1/4 sec. cor.

Subdivisions Tp. 13 S. R 1 E.

80.15	Intersected N. & S. line 20 lks. W. of cor. to secs. 13. 14. 23 & 24, from which I run N. 89° 57' W. on true line betw. secs. 14 and 23. with same va.
4.50	Hollow draius N.
13.20	Hollow " N.
22.00	Hollow " N.
40.07	Set granite 15 x 14 x 8 in in the ground for 1/4 sec. cor. mark 1/4 on W face and raised a stone mound alongside.
42.00	Ridge bears N. W. & S. E.
48.75	Gulch draius N. W.
70.00	Gulch draius N. W.
75.00	Ridge bears N W. & S.E.
78.00	Enter little valley
80.15	The cor. to secs. 14. 15. 22 & 23 Land mountainous Soil 2nd rate. No timber. Mountainous & dense undergrowth on 80.15 chs.

3.00	
14.00	
24.50	
40.00	
42.75	
58.50	
74.00	
96.00	

Subdivisions Tp. 13 S. R. 1 E.

North betw. secs. 14 and 15.
Var. 17½° E.

3.00 Leave Valley
14.00 Ridge bears N. W. & S. E.
24.50 Gulch dr. N. W.
40.00 On S. side of gulch set trachyte 14×10×6 in. 9 in in the ground for 1/4 sec. cor. marked with 1/4 on W. face and raised a stone mound alongside.
42.75 Gulch drains W.
58.50 Road bears S. W. & E. E.
74.00 Ridge bears S. W. & E.
96.00 Set granite 24×14×8 in. 18 in in the ground for cor. to secs. 10. 11. 14 & 15. marked with 4 notches on S and 2 notches on E edges. and raised a stone mound alongside.
Land mountainous.
Soil 2nd rate.
No timber.
Mountainous & dense undergrowth on 96 ch.

Subdivisions Tp. 13 S. R. 1 E.

East on random line
betn. secs. 11 and 14.
Var. 17 1/2° E.

40.00 Set temporary 1/4 sec. cor.

80.25 Intersect N. & S. line 20 lks. S. of cor. to secs. 11. 12. 13 & 14, from which Trun
S. 89° 51' W on true line
betn. secs. 11 and 14
with same va.

6.50 Gulch drains N. W.

11.50 Hollow drains N.

16.00 Ridge bears N. & S.

32.50 Hollow drains S.

40.12 Set slate 12 x 10 x 5 - 8 in in the ground for 1/4 sec. cor. marked 1/4 on N. face and raised a stone mound alongside.

67.50 Canyon drains N. accend.

80.25 The cor. to secs. 10. 11. 14 & 15.
Land mountainous.
Soil 2nd rate.
No timber.
Mountainous & dense
undergrowth on 80.25
Septr 27. 83.

14.00
17.00
22.50
31.50
34.65
39.50
40.00
56.50
52.00
58.00
80.00

Subdivisions Tp. 13 S. R 1 E.

North betw. secs. 10 & 11
Var. 17 1/2° E.

14.00 Canyon draws W.
17.00 Gulch draws S. W.
22.50 Spur ridge bears N. E.
31.50 Gulch heads N. E.
34.65 " " E.
39.50 Ridge bears N. E.
40.00 Set sandstone 14 x 7 x 6 in. gm in the ground for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside.
46.50 Gulch draws W.
52.00 Head of gulch draws S. W.
58.00 ~~ridge bears E. W.~~
80.00 Set trachyte 12 x 8 x 6 in. 8 in in the ground for cor. to secs. 2. 3. 10 & 11. marked with 5 notches on S. and 2 on E. edges and raised a stone mound alongside.

Land mountainous.
Soil 2nd rate.
Timber scattering cedars
Mountainous & dense
undergrowth on 80 chs.

Subdivisions Sp. 13 S. R. 1 E.

East on random line
betw. secs. 2 and 11
Var. 17½° E.

40.00	Set temp ¼ sec. cor.	40.00
80.00	Intersect N. & S. line 30 lks. N. of cor. to secs. 1. 2. 11 & 12. from which I saw N. 89° 47 W. on true line betw. secs. 2 and 11 with same va.	80.00
		5.70
		15.00
4.00	Ridge bears N. W. & S. E.	28.50
18.50	Gulch draws N. W.	21.00
20.45	Road bears N. & S.	22.25
22.00	Gulch draws N. E.	24.35
35.00	Ridge bears N. E. & S. W.	35.50
40.00	Set granite 24×20×15. 18 in in the ground for ¼ sec. cor. marked ¼ on N. face and raised a stone mound alongside.	35.80
		36.80
		40.00
72.00	Gulch draws N. E.	
80.00	The cor. to secs. 2. 3. 10 & 11.	53.50
		60.00
	Land Mountainous	62.00
	Soil 2nd rate.	74.00
		79.00
		80.00
	Timber scattering cedars Mountainous & dense undergrowth on 80 chs.	

Subdivisions Sp 13 S. R 1 E.

North random line
betw. secs. 2 and 3.
Var 17½° E.

40.00 For finding the old cor. set temp. 1/4 sec. cor.
30.00 Intersect N. boundary of Sp. Folks E. of cor.
to secs. 2 & 3, formerly set by me, from which I run
S. 0° 30' E on true line
betw. secs. 2 and 3 with same var.
5.70 Road bears S W & E.
15.00 Fence
28.50 Gulch drains S W.
21.00 Enter Salt Creek Canyon
22.25 Canyon road bears E & W.
24.35 Telegraph line bears E & W.
25.50 Railroad bears E & W.
25.80 Telegraph line
26.80 Salt Creek 40 lks wide 18 ins deep runs W.
40.00 Set trachyte 15 x 8 x 5, 10 ins in the ground for 1/4 sec. cor. marked 1/4 on W. face & raised a stone mound alongside
across
53.50 Spur ridge bears N E & S W.
60.00 Enter hollow dr. E.
62.00 leave same
74.00 Ridge bears S W & E
79.00 Gully or Drain N E.
80.00 Set cor to secs. 2. 3. 10 & 11
Land level & mountainous
soil 2nd rate.
no timber.
Brush underground with on 80 chs.

From the cor to secs. 33 and 34 on
boundary of the Tp. formerly set by me
Run
North betn secs. 33 & 34 — 40.00
Var. 17½ E — 80.00
5.30 Road bears NE & SW.
40.00 Set granite 14×8×6 in. Gin the
ground for ¼ sec. cor. marked
¼ on W face and raised a stone
mound alongside.
44.50 Wash drains S. W. — 15.00
49.00 " " " — 38.90
59.00 Road bears S & W & E. — 40.00
64.00 Bottom of gulch drains S. W.
76.35 Road bears E & W
80.00 In gulch dr. S. W. set standard
14×8×6. g in in the ground for cor. to — 69.00
secs. 27. 28. 33 & 34. marked with — 80.00
I notch on S and 3 notches on E
edges and raised a stone mound
alongside.
Land rolling
Soil 1st rate.
No timber
Some underbrush on SW

Subdivisions Sec. 13. T. R. 1E.

East on random line
betw. secs. 27 and 34
Var. 17½° E.

40.00 Set temp 1/4 sec. cor.
80.00 Intersect N & S. line at cor. to secs. 26. 27. 34 & 35. from which Trees
West on true line
betw. secs. 27 and 34
with same var.
15.00 Leave mouth of ~~flat~~ canyon flat
38.90 Road bears N E & S W.
40.00 Set granite 10×10×5 ± 6in in the ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound along side.
69.00 Enter gulch head S. E.
80.00 Pre cor. to secs. 27. 28. 33 & 34
Land. rolling
Soil 1st & 2nd rate.
No timber.
Dense undergrowth on Hoko.

Subdivisions Tp. 13. S. R. 16.

North betw. secs. 27 and 28

Var. 17½° E.

	Leave		
2.50	Gulch dx. S. W.		
33.50	" " N. W.	40.00	
40.00	Set granite 16×10×4 in. 10 in in the ground for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside.	80.40	
70.00	Gulch drains W.		
80.00	Set granite 14×8×6 in. 9 in in the ground for cor. to secs. 21. 22. 27 & 28 marked with 2 notches on S. and 3 on E. edges and raised a stone mound alongside.	40.20	
		44.50	
		60.80	
	Land. mountainous	80.40	
	Soil 2nd rate.		
	Timber scattering cedars		
	Mountainous & dense		
	undergrowth on 80 lks.		

R. 16. Subdivisions Sp. 13 c. R. 16.

East on random line
betw. secs. 22 and 27
Var. 17 1/2° E.

40.00 Set temporary 1/4 sec. cor.

80.40 Intersect N. & S. line 40 lks.
S. of cor. to secs. 22. 23. 26 & 27
from which I run
S. 89° 43' W. on true line
betw. secs. 22 and 27
with same va.

40.20 Set sandstone 15 x 14 x 5± 10± in the ground for 1/4 sec. cor. marked with 1/4 on N face & raised a stone mound alongside.

44.50 Recced from flat

60.80 Gulch draws S.

80.40 The cor. to secs. 21. 22. 27 & 28
Land. rolling
Soil 2nd rate.
No timber
Brush undergrowth
on 80. 40 chs
Sept 29. 83.

Subdivisions Sp. 13 S. R. 16 Sub

North betw. secs. 21 and 22.
Var. 17 1/2° E

4.50 Gulch drains S. W.
40.00 Set granite 14 x 8 x 6 in. 9 in in the ground for 1/4 sec. cor. 16.50
marked 1/4 on W. face and rais 23.50
a stone mound alongside. 36.00
44.50 Ridge bears N E & S. W. 46.15
80.00 Set granite 12 x 10 x 6 in. 8 in in the ground for cor. to secs. 15. 16. 21 & 22 marked with 3 notches on S & E edges and raised a stone 45.50
mound alongside. 54.00
Land mountainous 67.00
Soil 2nd rate. 80.30
Timber scattering cedars.
Dense undergrowth
on 80 chs.

East on random line
betw. secs. 15 and 22.
Var. 17 1/2° E.

40.00 Set temporary 1/4 sec. cor.
80.30 Intersect N & S. line 45 lks. S. of 4.50
cor. to secs. 14. 15. 22 & 23 from which 33.00

BOOK-A-197

177

Subdivisions Tp. 13 S. R. 16.

From

S. 89° 41' W on true line
between secs. 15 & 22
with same va.

16.50 Leave Valley

23.50 Road bears N & S.

36.00 Ridge bears N E & S W.

40.15 Set quartzite 18×10×8 in. 12 in in the ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

45.50 Gulch drains S W.

54.00 Top of round hill 400 ft high

67.00 Gulch drains N.

80.30 The cor. to secs. 15. 16. 21 & 22.

Land. Mountainous
Soil 1st & 2nd rate.
No timber.
Mountainous & dense
undergrowth on 80.30 chs.

North betw. secs. 15 and 16.
Var. 17 1/2° E.

4.50 Gulch 15 ft deep drains N W.

33.00 " 75 " " S W

Subdivisions Tp. 13. S. R 16

40.00	Set granite 14×8×6″ 9″ in the ground for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside.	40.00
44.50	Gulch dr. N. W.	
59.50	Road in gulch ~~dr~~ S. W.	
73.50	" " " W.	
80.00	Set granite 24×10×8″ 18″ in the ground for cor. to secs. 9. 10. 15 & 16. marked with 4 notches on S. and 3 on E. edges and raised a stone mound alongside.	63.00 70.00 80.00
	Land. mountainous Soil 2nd rate. Timber. scattering cedars Mountainous & dense undergrowth on 80 lks.	
	East on random line betw. secs. 10 and 15 Var. 17 1/2° E.	35.00 40.00
40.00	Set temp 1/4 sec. cor.	
80.00	Intersect N. & S. line at cor. to secs. 10. 11. 14 & 15 from which I run West on true line	40.80

betw. secs. 10 and 15.
with same va.

40.00 At head of gulch set trachyte 12×8×7 in the ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

Thence in gulch

63.00 Leave gulch dr. S. W.

70.00 Head of gulch dr. S.

80.00 The cor. to secs. 9. 10. 15 & 16.
Land mountainous
Soil 2nd rate.
Timber. few cedars.
Mountainous & dense
undergrowth on 80 chs.
Bells 1. 83

North betw. secs. 9 and 10
Var. 17 1/2° E.

35.00 N. W. point of ridge

40.00 Set sandstone 15×10×4 10 in the ground for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside.

40.80 Road in canyon bears N. W.

Subdivisions Sec. 13. T. R. 1E.

48.50	N. W. point of ridge		
52.50	Road in small canyon bears N.W.		
57.00	Canyon 350 ft. deep dr. W.	0.75	
73.00	N. W. point of ridge	23.00	
75.50	small gulch drains S. W.	25.00	
80.00	no trace of old cor. to be found	33.50	
	set at foot of mountains bears	39.95	
	E & S.W. sandstone 16 x 10 x 8		
	12 ins in the ground for cor. to secs.		
	3. 4. 9 & 10. marked with 5 notches		
	on S. and 3 on Edges, and raised	47.00	
	a stone mound alongside.	58.75	
	Land. mountainous	62.00	
	Soil 2nd rate.	72.50	
	No timber.	76.00	
	Heavy mountains on 80 chs.	79.90	
	East on random line		
	betw. secs. 3 and 10.		
	Var. 17½° E.		
40.00	Set temp. ¼ sec. cor.		
79.90	Intersect N. & S. line 30 lks N.		
	of cor. to secs. 2. 3. 10 & 11. from which		
	I run		
	N. 89° 47' W. on true line		

Subdivisions Tp 13 S. R 1E.

betw secs. 3 and 10
with same var.

0.75. Gulch drains S.E, enters cedars
23.00 Leave cedars
25.00 Ridge bears N & S.
33.50 Hollow dr. S.
39.95 Deposited Stake 8x5x3, in 12in deep in the ground for 1/4 sec. cor. marked 1/4 and raised a mound of stones over it.
47.00 Gulch drains S. W.
58.75 Trail in gulch bears S W.
62.00 Spur ridge bears N & S.
72.50 Gulch drains S. W.
76.00 Ridge bears NW & S.E
79.90 Pk cor. to secs. 3. 4. 9 & 10.
Land mountainous
Soil 2nd & 3rd rate.
Timber. Few cedars
Mountainous & dense
undergrowth on 79.90 chs.

Subdivisions Sp. 13 S. R. 16

Subd

	North on random line	
	betw. secs. 3 and 4.	48.77
	Var 17½° E.	48.95
40.00	To trace of old cor. set temp. ¼ sec	49.90
80.13	Intersect N. boundary of Sp. at co	50.23
	to secs. 3 & 4 formerly set by me	50.36
	from which 3" pine	57.50
	South on true line	
	betw. secs. 3 and 4.	67.10
	with same var.	
	Note. On account of obstacles in line	80.13
	Offset 2 chs. W.	
2.10.	Fence bears E & W.	
2.15.	Ditch runs W.	
3.82.	Fence bears E & W.	
10.65	" " "	
10.73	Ditch runs W.	
13.88	" " "	
26.77	Fence bears E & W.	
28.26	" corner 44 lks. W.	
33.00	Wash drains W. thence in same	
38.00	Leave same	
40.13	Offset 2 chs E. on true line	
	Set sandstone 16×12×8"	
	10 in. in the ground for	40.00
	¼ sec. cor. marked ¼	
	on W face and raised a stone	

S. R 16 | Subdivisions Sp. 13 S. R. 16 E.

mound alongside.

48.77 Fence bears E & W.

48.95 Telegraph line "

49.90 San Pete Valley R. R. bears E & W.

50.23 Telegraph line " "

50.36 Fence bears E & W.

57.50 Salt creek 30 lks wide 12 ins deep runs W.

67.10 Junction of 2 roads bears N E. W. & S W.

80.13 The cor. to secs. 3. 4. 9 & 10.
Land. level
Soil 1st rate.
No timber.
Mostly under cultivation.
Octr 2. 83

From the cor. to secs. 32 and 33 on the S. boundary of the Sp. formerly run & set by me I run North betw. secs. 32 and 33
Var. 17½ ° E.

40.00 No trace of old cor. set cobble 14×8×6. ins in the ground, for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside.

Subdivisions Sp. 13 S. R 1 E.

40.65	Wash drains W
49.50	" " S. W.
56.00	" " "
68.60	Ditch runs S. W
69.00	Wash drains W.
80.00	No trace of old cor. set quartzite 16×12×6 in 12 in in the ground for cor. to secs. 28. 29. 32 & 33 marked with 1 notch on S. and 4 on E edges and raised a mound stones alongside
	Land level.
	Soil 1st rate.
	No timber.
	Dense black sage brush on 80 ch.
	East on random line bet'n. secs. 28 and 33 Var. 17½° E.
32.00	No trace of old cor.
40.00	Set scup W for sec. cor.
80.36	Intersect N. & S. line at cor. to secs. 27. 28. 33 & 34 from which I run
	West on true line bet'n. secs. 28 and 33

BOOK-A-

Subdivis

1.50	N.
2.50	Set Co
20.00	Em
40.18	Set in ma ran cir
46.00	Ro
80.36	Sh La So No De
4.35	Wa
6.25	Em
18.00	Wa
31.00	Gu
36.75	Re
38.00	No
40.00	Se

Subdivisions Tp. 13 S. R. 1 E.

with sauce va,

1.50 N. slope of gravel knoll
2.50 leave Canyon dr. S. W.
20.00 Enter flat
40.18 Set quartzite 19×14×12 : 12 in in the ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.
46.00 Road bears N. 80° W.
80.36 The cor. to secs. 28. 29 32 & 33
Land. rolling & level
Soil. 1st & 2nd rate
No timber.
Dense brush on 80. 36 chs.

North betw. secs. 28 and 29
Var. 17 1/2° E.

4.35 Wood road bears E & W.
6.25 Enter cedars, ascend
18.00 Wash drains W.
31.00 Gulch 150 ft deep drains W.
36.75 Ridge bears E & W. leave cedars
38.00 No trace of old corner.
40.00 Set sandstone 14×12×8 in

Subdivisions Tp. 13 S. R. 1 E.

	10 ins in the ground for 1/4 sec. cor. marked 1/4 on W. face & raised a stone mound alongside.
40.25	Gulch dr. W.
47.00	" " W.
60.40	" 150 ft. deep drains W.
67.00	" 150 " " " W.
70.00	Ridge bears E & W.
72.50	Head of canyon dr. N. W.
79.00	Canyon drains N
80.00	Set granite 20 x 14 x 12 : 14 ins in the ground for cor. to secs. 20. 21. 28 & 29. marked with 2 notches on S. and 4 on E edges and raised a stone mound alongside.
	Land rolling hills.
	Soil 2nd rate.
	Timber. scattering cedars.
	Mountainous on E sides.

East on random line
between secs. 21 and 28.
Var. 17½° E.

40.00	Set temporary 1/4 sec. cor.
80.00	Intersect N. & S. line at cor.

1.25	to
18.50	Sa
23.70	Gu
27.50	R
37.50	Gu
40.00	G
	in
	ma
	ra
53.60	R
55.50	Gu
62.75	
71.00	R
80.00	Th
	L
	S
	T
	C

Subdivisions Tp. 19 S. R. 1 E.

	to secs. 21. 22. 27 & 28. from which Iron West on true line bet. secs. 21 & 28 with same var.
1.25	Gulch drains S.
18.50	Point of cedars on ridge sloping S.
23.70	Gulch drains S.
27.50	Ridge bears N & S.
37.50	Gulch drains S.
40.00	Set trachyte 20×12×12 in. 15 ins in the ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound along side.
53.60	Road in canyon bears N. W.
55.50	Gulch drains N.
62.75	" " N.
71.00	Ridge bears N & S.
80.00	The cor. to secs. 20. 21. 28 & 29 Land mountainous. Soil 2nd rate. Timber scattering cedars. Mountainous & dense undergrowth on all sides. Oct. 3. 83.

Subdivisions Tp. 13 S. R. 1 E.

North betw. secs. 20 and 21
Var. 17½° E.

3.00 Gulch dr. W.
24.65 Road bears N. W. & S. E.
25.50 Canyon drains N. W.
40.00 At foot of hills set granite 18 x 12 x 8 in. 12 in. in the ground for 1/4 sec. cor. marked 1/4 on W face & raised a stone mound alongside.
44.25 Gulch drains W.
46.00 No trace of old cor. to be found.
61.50 Wash drains W.
66.55 " " W.
" " W.
78.20 No trace of old cor.
80.00 Set Quartzite 18 x 14 x 12 in. 12 in. in the ground for cor. to secs. 16, 20 & 21, marked with 3 notches on S. and 4 on E. edges and raised a stone mound alongside.
Land. mountainous & valley.
Soil 1st. & 2nd rate.
Timber. scattering cedars.
Dense brush on hills.

Subdivis...

25.00 No...
40.00 Set...
80.00 Set...
to ...
Set...

2.50 R...
11.50 Gu...
19.00 Le...
26.50 N. ...
36.00 Se...
40.00 Se...
in ...
ma...
rai...
43.50 Ro...
48.00 N. ...
58.35 Wa...
80.00 The...
La...
So...

R. 1 E. Subdivisions Sp. 13 S. R. 1 E.

0 and 21

E.

nite

ns for
face &
gzine.

found.

12in 12in
secs. 16 &
notches
and
along ridge
s. & valley
.
dars.
ches.

East on random line
betw. secs. 16 and 21
Var. 17 1/2° E.

25.00 No trace of old cor.
40.00 Set temporary 1/4 sec. cor.
80.00 Intersect N. & S. line at cor.
to secs. 15. 16. 21 & 22 from which
I run

West on true line
betw. secs. 16 and 21
Var. 17 1/2° E.

2.50 Ridge bears N. & S.
11.50 Gulch drains N.
19.00 Head of gulch drains N. W.
26.50 N. point of ridge 950 ft. high
36.00 Trail bears N. W.
40.00 Set trachyte 22 x 20 x 12in 16in
in the ground for 1/4 sec. cor.
marked 1/4 on N face and
raised a stone mound along side.
43.50 Road in canyon dr. N. W.
48.00 N. W. point of ridge. Enter valley
58.35 Wash from hollow heads S. E.
80.00 The cor. to secs. 16. 17. 20 & 21.
Land mountainous & level.
Soil 2nd rate.

1900

Subdivisions Tp. 13 S. R. 1 E.

Timber scattering cedars.
Mountainous on 60 chs. & slem
undergrowth on 80 chs.

North betw. 16 and 17
Var. 17½° E.

26.50 Wash draws W.

36.00 W.

40.00 Set quartzite 18×12×8 : 12in in the ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.

50.50 Road bears N. W & S.E.

67.20 Main road to Yreka bears N & S. Leave brush.

80.00 Set quartzite 16×12×10 : 12in in the ground for cor. to sec. 8. 9. 16 & 17. marked with 4 notches on S & E. edges and raised a stone mound alongside.

Land. Level.
Soil 1st rate
No timber
Dense underg rowth on 67.20

40.00 Set
80.00 Set

R. 1 E. Subdivisions Sec. 13 T. R. 1 E.

East on random line
between secs. 9 and 16.
Var. 17 1/2° E.
No trace of old cor.
40.00 Set temporary 1/4 sec. cor.
80.00 Intersect N. & S. line 50 lks E.
of cor. to secs. 9. 10. 15 & 16, from
which I run
N. 89° 39' W on true line.
between secs. 9 and 16.
with agonic var.
No trace of old monument
3.00 Enter valley bears N & E.
30.00 Road bears N. W & S. E.
83.50 Set granite 14 x 10 x 6 in 9 in
40.00 in the ground for 1/4 sec. cor.
marked 1/4 on N face & raised
a stone mound alongside.
49.50 Road bears N W & S. E.
65.00 Road " " "
78.90 Co. Road " W & S.
80.00 The cor. to secs. 8. 9. 16 & 17
Land. level & mountainous
Soil 1st & 2nd rate
Timber. scattering cedars.
Dense undergrowth on
80 chs.

Subdivisions Tp. 19 S. R. 1 E.

Subdivis.

Note. Having established the cor. to secs. 4. 5. 8 & 9 from the original field notes of the old survey & set sandstone 14 x 12 x 4 in 8 ins in the ground, marked with 5 notches on S and 4 on E edges, raised a stone mound along side. Therefore from the cor. to secs. 8. 9. 16 & 17 Run

North on random line
betw. secs. 8 & 9
Var. 17 1/2° E.

40.00 No trace of old cor set temporary 1/4 sec. cor.

80.23 Intersect the cor. to secs. 4. 5. 8 & 9 from which Run

South on true line
betw. secs. 8 and 9
with same var.

Note. On account of obstacles in line S offset 5 lks. E. to center of Main street in the town Neph[i] taking notes on same.

2.95 Street corner bears E & W.
9.50 " " " "
10.96 " " " "
17.43 " " " "

18.80 Stree
25.43 "
26.88 "
32.55 "
34.55 "
40.11 Offse
lks.
set
in
ma
rai
sid
57.12 Fen
60.05 N.
65.26 S.
80.23 the
La
So
Not
La

BOOK A-197 — 193

R. 1 E. Subdivisions Tp. 13 S. R. 1 E.

the cor. to	18. 80	Street corner bears E & W.
rical fie	25. 43	" " " "
t sandst	26. 88	" " " "
t, marke	32. 55	" " " "
& edge,	34. 55	" " " "
g size.	40. 11	Offset 5 lks. W. to true line at 85. lks. fence bears E & S. thence set sandstone 12 x 7 x 6 in 8 in in the ground for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside.
secs. 8. 9.		
e		
temporary		
	50. 12	Fence cor. 75 lks. W. of line
4. 5. 8 & 9 pr	60. 05	N. E. corner of fence & field
	65. 26	S. E. " " " & "
	86. 23	The cor. to secs. 8. 9. 16 & 17
		Land. Level.
		Soil 1st. rate.
		No timber.
		Land mostly under cultivation.
ailes in		
ter of		
Nephi		
E.		
& W.		
"		
"		
"		

	East on random line	49.23	Corn
	betw. secs. 4 and 9.	57.16	"
	Var. 17 1/2° E.	57.70	"
5.00	On account of obstacles in	59.20	"
	line I offset 3.50 South	5.75	"
	thence E. taking notes on same	7.25	"
	line.	13.73	"
40.00	Set temporary 1/4 sec. cor. witness	16.00	Rhea
80.00	Intersect N. & S. line 30 lks S. of		Lau
	cor. to secs. 3. 4. 9 & 10. from which		Sou
	I run		No
	S. 89° 47' W on true line		Lau
	betw. secs. 4 and 9.		
	with same var.		
1.50	Wash draws N. W.		
14.80	Road bears S. E & N. W.		Fro
19.90	Fence bears N & S. Enter field		on th
29.88	Ditch heads N. E. runs S.		fro
30.93	Enter field under cultiv.		
40.00	Set a quartzite 20 x 14 x 10 ins.		
	14 ins. in the ground for	19.25	Hall
	1/4 sec. cor. marked 1/4 on	22.50	Ditc
	face and raised a stone	29.50	Fenc
	mound alongside.	40.00	Set
41.68	Leave field		in
43.00	Corner of Street bears N & S.		cor

BOOK-A-197 — 1961

R. 1 E.

Subdivisions of T. 13 S. R. 1 E.

line

acles in

l

n same

or. to sec

30 lks S. of

n which

e

.

l. W.

nter field

ues S.

tio.

14 x 10 in

ed for

1/4 on

stance

ide.

rs N & S.

49.23	Corner of street bears N & S
51.16	" " "
57.70	" " "
59.20	" " "
5.75	" " "
47.25	" " "
13.73	" " "
40.00	Mean. to secs. 4. 5. 8. 9.
	Land level.
	Soil 1st rate.
	No timber
	Land worthy under cultivation.
	Octr 4. 83
	From the cor. to secs. 31 & 32 on the S. boundary of this T. formerly reset by me North 40 lks. secs 31 & 32 Var. 17 1/2° E.
49.25	Hollow dr. N. W.
22.50	Ditch drains W.
39.50	Fence cor. 30 lks. E.
40.00	Set trachyte 16 x 8 x 6 in 1 ft in the ground, for 1/4 sec. cor. marked 1/4 on W

BOOK-A-19

face and raised a stone mo
alongside. W traced for cor.
40.75 Ditch drains W.
42.00 Entry deane brush
62.00 Lead same.
80.00 Set trachyte 18×18×8 in. 12 in
in the ground for cor. to secs.
29. 30. 31 & 32. marked with 1
notch on S. and S on E edges
and raised a stone mound
alongside. W traced for cor.
Field level.
Soil 1st rate
No timber
Deane brush on 20 chs.

East on random line
betw. secs. 29 and 32
Var. 14½° E.
40.00 Set temp. ¼ sec. cor. W traced for
80.12 Intersect W. S. line 5 lks N.
cor. to secs. 28. 29. 32 & 33 from
which I mark
N. 89° 58' W. on true line
betw. secs. 29 & 32
with same var

22.00 West
39.20 Rod
40.06 Set
gran
on N.
mou
51.00 Lea
80.12 Set
Lac
Sou
Not
Di

40.00 Set
79.90 Int
at c
me

1.40 War
1.76 "

S. L. R. Subdivisions Tp. 13 S. R. 1 E.

	...ne and ...st cor.
	...i 12 li... ...to secs. ...with ... ...edges ...ound ...st cor.
	...hs.
	...line
	...d 32
	...Meridian ...Lake N. ... 33 from
	...ne line
	...2
22.00	Wash 30 ft. deep dr. N. W.
39.20	Rod bears N & S.
40.06	Set Quartzite 20×14×10 in. 15 in. in the ground for 1/4 sec. cor. marked 1/4 on N. face and raised a stone mound alongside.
57.00	Leave brush
80.12	Sec cor. to secs. 29. 30. 31 & 32. Land. Level. Soil. 1st rate Timber. Dense brush on 5 chs.
	West on random line betw. secs. 30 and 31. Var. 17 1/2° E.
40.00	Set temp. 1/4 sec. cor. Meander corner
79.90	Intersect Salt Lake Meridian at cor. to secs. 30 & 31 reset by me from which I run East on true line betw. secs. 30 and 31. with same var.
1.40	Wash dr N. W.
1.50	" " "

BOOK-A-197

Subdivisions Tp. 93 S. R. 1 E

39.90 Set trachyte 14×9×4 in ground for 1/4 sec. cor. marked on N. face and raised a stone mound alongside.

74.15 Road bears N & S.

79.90 Pine cor. to secs. 29. 30. 31 & 32.
Land. level
Soil 1st rate.
No timber
Grass on 79.90 chs.

North 80 chs. secs. 29 and 30
Var. 17½° E.

No trace of older corner

40.00 Set trachyte 12×8×6 in ground for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside.

62.00 Road bears N E & S. W.

80.00 Set trachyte 18×10×8 in the ground for cor. to secs. 19, 29, 30, marked with 2 notches on S. and 5 notches on Edges and raised a stone mound alongside. No trace of older cor.
Land. Level

R.1 E. Subdivisions Tp. 13 S. R. 1 E.

	Soil 1st rate.
	No timber
	Dense undergrowth on 40 chs.
	East on random line
	betw. secs. 20 and 29
	Var. 17½° E.
0.00	Set temporary ¼ sec. cor. to trace of old cr.
4.00	Intersect N. & S. line 5 lks. W. of c. cr. to secs. 20. 21. 28 & 29. from which Spurs.
	N. 89° 58' W. on true line
	betw. secs. 20 and 29.
	With same va.
0.10	Gulch drains N.
11.00	" " N. W.
29.00	Leave foothills
29.78	Road N. W. & S. E.
40.00	Set quartzite 20 + 10 + 10 + 15 ins. in the ground for ¼ sec. cor. marked ¼ on N. face and raised a stone mound alongside.
11.75	Old Levan Road
56.30	Wash drains N.
70.20	Road bears N. & S.

200

Subdivisions Tp. 13 S. R. 1 E

77.00	Wash draws N.
80.00	The cor. to secs. 19. 20. 29 & 30.
	Land. Level & mountainous
	Soil 1st & 2nd rate
	Timber scattering cedars.
	Dense undergrowth on 80 ch.
	West on random line
	betw. secs. 19 and 30.
	Var. 17½° E
40.00	Set temporary ¼ sec. cor. No trace of old
79.97	Intersect Salt Lake Meridian
	at cor. to secs. 19 & 30, reset by
	me from which I saw
	East on true line
	betw. secs. 19 & 30
	with same var.
8.72	Telegraph line bears N E & S W.
9.25	Rail Road " "
39.97	Set cobble 10 x 8 x 8 in 6 in in the
	ground for ¼ sec. cor. marked
	on N. face and raised a stone
	mound alongside.
30.00	Road bears N E & S W Center bears
79.97	The cor. to secs. 19. 20. 29 & 30

40.00	Set
40.65	Road
48.90	Rail
49.45	Teleg
80.00	Set

Subdivisions Sp. 13 S. R 1 E.

Land level
Soil 1st rate
No timber
Dense brush on 29.97 chs.

North betw. secs. 19 and 20
Var. 17½° E.

40.00 Set trachyte 14×11×7 in. in the ground for 1/4 sec. cor. marked 1/4 on W. face & raised a stone mound alongside. No trace of old cor.

40.65 Road bears N E & S W.

48.90 Railroad bears N. & Utah Central

49.45 Telegraph line bears N. & S.

80.00 Set trachyte 14×8×5 in. in the ground for cor. to secs. 17. 18. 19. 20 marked with 3 notches on each of 5 on E edges and raised a stone mound alongside. No trace of old cor.

Land level.
Soil 1st rate.
No timber.
Dense artemisia undergrowth on 80 chs.

Subdivisions Tp. 13 S. R

East on random line
betw. secs. 17 and 20
Var. 17 1/2° E.

40.00	Set temporary 1/4 sec. cor.
80.00	Intersect R. & S. line at cor. secs. 16. 17. 20 & 21 from which

West on true line
betw. secs. 17 and 20
With same var.

10.00	Wash drains N.
13.40	Canyon Road bears N. W. &
22.70	Junction of 2 roads bears N
39.30	Rail Road bears N E & S. W.
40.00	Telegraph line " "
40.05	Set trachyte 12×8×6 in. 8 ins. in ground for 1/4 sec. cor. mark on N. face and raised a stone mound alongside.
61.70	Wash dr. N.
75.50	" " N.
80.00	The cor. to secs. 17. 18. 19 & 20 Land. level. Soil 1st rate. No timber. Dense artemisia undergrowth on 80 ch

BOOK-A-

Subdivi

We

	My tra
00	Set
04	Inte
	at co
	from
	E.
04	Set
	grou
	1/4 co
	stan
90	Pits
31	Wa
04	The
	La
	So
	Ve

Subdivisions Sp. 13 S. R. 1 E.

West on random line
betw secs. 18 and 19.
Var 17 1/2 E.

My trace of old cor.

00 Set temporary 1/4 sec. cor.

04 Intersect Salt Lake Meridian
at cor. to secs. 18 & 19. reset by me.
from which I run
East on true line
betw. secs. 18 and 19
with same var.

04 Set trachyte 12 x 8 x 7 ins in the
ground for 1/4 sec. cor. marked
1/4 on N. face and raised a
stone mound alongside.

90 Ditch heads S. W.

31 Wash draws N.

04 The cor. to secs. 17. 18. 19. 20
Land. level.
Soil 1st. rate.
No timber.

Vol. F. 83.

General Description.

The additional land surveyed embraces the W. slope of the Nebo [illegible] of the Wasatch Mountains, consisting of steep foothill ridges and intervening vales. The soil is rich though rocky, it is mostly suitable for dairy farming, and many claims have lately been made in it for that purpose.

The applicants improvements are situated in Sec. 11. and consist of several cabins, corrals, considerable fencing & ditch making and about 15 acres of land under cultivation.

Augustus L. D. Ferron
U. S. Dep. Surv

BOOK-A-197

JOHA

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah. November 5th *1883*

The foregoing field notes of the survey of the Subdivisions

Township No. 13 South *Range No.* 1 East

Executed by Augustus D. Ferron

Under No 17 *contract of the* 5th

day of July *1883, in the months of* Sept. & Oct. *1883, having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

Fred Dalton

U. S. Surveyor General for Utah.

BOOK-A-197

REPORT: 1884

Filed October 24th, 1883

Examined by John H. Caulfield

Transcribed by L. W. Hickok

Compared by C. E. D. & L. W. H.

FIELD NOTES

OF THE SURVEY OF THE

North, South & East boundaries

OF

Township No 14 South

Range No 1 East

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Augustus D. Ferron

U. S. Deputy Surveyor,

Under his Contract No. 117.

Dated July 5th, 1883

Survey commenced September 3rd 1883

Survey completed September 5th 1883

V

BOOK-A-197

Township 14 South R. 1 East



ANTS:

ompassma
ainman.
ainman.
hainman.
hainman.
veman.
xeman.
lagman.

Survey Commenced:- Sept. 3rd 1883.
With a Burt's improved Solar Compass
My special instructions from the
Surveyor General for the Survey of
this Township ordered me to extend
the Survey of this Th. in accordance
with the existing prior Survey,
both in alignment and distances.
On retracing the Salt Lake
Meridian last year Stark pains to
hunt up all the existing old Cors
in Juab Valley; and, after a
great deal of labor determined
the Chaining to be true measurement
but all the Mag. Courses to be N. 1° W.
or in other words that the lines of
the old Survey were run with 17°30' E.
Variation, instead of 16°30' E. Var.
which latter is the true variation.
The new Surveys were therefore
made in accordance with the
facts found.—

South Boundary T. 14 S. R. 1 E.

Same cor to Secs. 32 & 33. on S. boundary of this T. formerly by me Surv.;

East on true line bet Secs 4 & 33, 50.00 Ravine
Var 17½° E. 9.00 "
Mound 5.00
17.50 Ridge bears N. & S. 4.00 Set
40.00 Set Sand Stone 14×7×7, 9 in. in the ground for 1/4 Sec cor, marked 1/4 on N. face & Stone mound alongside. Bottom of old cor. the ground
45.50 Bottom of ditch Ravine dug
68.50 " " " " 9.50 Ravine
80.00 Set Sand Stone 24×8×8, 18 in. in the ground for cor to Secs. 3. 4. 33 & 34, marked 3 Notches on E. & W. edges, and raised a Stone mound alongside. 2.00 " 10.00 Set 12 in ground Cor to Secs marked 4 on E face & a Stone mound alongside
Land, Mountains;
Soil, Sandy;
Timber, Some Scatt. pine & oak
Heavy mountains & dense undergrowth
on S. & W.

East on 3 & 34
Ravine
"
Set
the ground
marked
raised
along
Ravine
"
Set
12 in
Cor to
marked
4 on E
a Stone
Land
Heavy
dense

...l. Rs 6. ...outh Boundary Tp. 14 S., Rs 6.

...33. on ...formerly 2...

East on line bet. Secs 2—
3 & 34
Ca 17.20 ch.

...t Sec^r 4,5...7.50 Ravine drains N.
9.00 " " "
35.00 " " "
...0.00 Set Flint 10 x 10 x 6, 6 in. in the ground, for 1/4 Sec. Cor., marked 1/4 on N. face and raised a stone mound alongside.

...in. in the gr... N. face S... ...d Cor. ...ns drain...
" 9.50 Ravine drains N.
...8 in. in the ... 2.00 " " "
...0.00 Set limestone 18 x 8 x 5, 12 in in the ground for Cor to Secs 2, 3, 34 & 35, marked 2 Notches on E. & W. edges, and raised a stone mound alongside.

...ains & ... ...dge prod...

Low Mountains;
Soil, Red Gravel;
No Timber
Heavy mountains and dense undergrowth in 40 chs.

South Boundary Tp. 14 S. R 1. E.

South bou

East on line bet. Secs
2 and 35,
Var 17 1/2° E.

7.00 Ravine drains N. E.
36.50 Ridge cañon drains N.
39.25 Chicken Creek 15 lks wid
14 lks dep drains N. W.
40.00 Set granite 14 x 8 x 5. 9 in
in the ground, for 1/4 Sec.
marked 1/4 S. Sec
raised a stone mound alon
side.
42.30 Road bears N. W. & S.
44.00 Arroyo
57.00 Gulch drains S. E.
61.00 Ridge bears N. W. & S.
78.80 Hollow drains S.
80.00 Set granite 20 x 8 x 6,
in. in the ground,
to Sec. 1. 2, 35 & 36. ma
Station E. & on W.
and raised a stone
mound alongside
Land Heavy Timbe
Soil, Sandrock,
Pine Timber

North
undu

East
Sec

Hollo
four
mark
for 1/4
raised
S.W. po
in 4.
20 x 15
cor. to
and rai
Level.
Soil
Timb
Heavy
mix

South boundary Sp. 14 S. R 1. E.

Mountainous & dense
undergrowth 80 chs

East on true line bet.
Sec. 1 and 36,
Ran 17 1/2° E.

Hollow draws S.E.
foot of bluff
marked s all'd ledge of sandst.
for 1/4 sec. cor. 14 sec. north &
raised stone mound alongside.
S.W. point of high bluff
on N. slope of cañon set sandst.
20 x 15 x 5 in. 5 in in the ground for
cor. to Sp. 14 & 15 S. R 1 & 2 E.
marked 6 notches on N. S. E & W edges
and raised stone mound alongside.
Rocky mountains.
Soil 3rate.
Timber, some cedars & pines.
Heavy mountains & thick
undergrowth on 80 chs.
Sept. 3/83.

BOOK-A-197

East boundary Tp. 1 [illegible] 1. E.

From the cor. to Tps 1 & 2
R. 1 & 2 E. formerly set by me
run N. betw. secs. 31 & 36
Var. 17½° E.

Note. On account of bluffs
offset West 30 chs. thence
50 chs. thence East 10 chs. to
point 20 chs West of

80.00 set a sandstone 11x10x6.
in the ground for cor. to secs
25. 30. 31 & 36 marked 5 notch
on 4 and 1 on Edges & W. C. 80.00
and raised a stone mound
alongside.

Note. The 1/4 sec. cor. falls in the
bluffs and is not set.
Land. high bluffs.
Soil 3rd rate.
No timber.

Heavy mountains on 80

North betw. secs. 25 and
Var. 17½° E.

From Witness cor. 20 chs. W. of
cor. point to secs. 25. 30. 31
& 36 & offset North 10 chs

80.00

thence
(Note.
to reach
secs
ground
of land
for.
being
W. of
ground
to a po
where
4 x 3 i
1/4 sec.
W. for
mound
on off
8. 00 a
in plac
Witness
sec. 19
4 notch
and o
Land.
Soil.
Timber

Tp. 14 S. 1. E. Salt Lake Meridian

Tp 14 S 1 E
set by me
cs. 31 & 36
7½° E.
x of bluffs
chs. thence
et 10 chs. to
et of
11 x 10 x 6.
Witness
cor. to sec
ked 5 notch
dges & W. C.
tone mound
falls in mou
t set.
ffs

ries on 80

ecs. 25 and
½° E.
20 chs. W. of
cs. 25. 30. 3
orth 10 chs

thence East 11, 50 chs.
(Note. It being still impossible to reach the line I here set a sandstone 14 x 8 x 6 : 9 in in the ground marked 5 notches on N and 1 on S. edges and W. C. for W. C. to secs. 25. 30. 31 & 36. bearing 10 chs north and 8, 50 chs. W. of true cor. point.) thence I run on offset North 30 chs to a point 8, 50 chs. west of where I set a sandstone 14 x 4 x 3 : 9 in in the ground for W. 1/4 sec. cor. marked 1/4 W C on W. face and raised a stone mound alongside, thence on offset North 40 chs., East 8. 50 chs. to 0.00
in place, set granite 20 x 8 x 12 - 15 in in the ground for cor. to sec. 19. 24. 25 & 30 marked 4 notches on N & E on S edges and raised a stone mound alongside. Land. very broken, mountainous & hilly. Soil. 3rd rate.
Timber. Open cedars.
Mountain mahogany, cedar, undergrowth on hills

East boundary T. 7 N. R. 9 W.

North 60 recs. 19 g 24

Var 17½° E.

Mon. On account of broken ... set
S. offset West 20 lks. thence N. ...
40 lks. to a point 20 lks west ... sec. ...
40.00 set sandstone 12×8×7,8 in ... stone
ground for 1/4 W.C. marked ... Sn. acc
W.C. on W. face ... North
raised a stone mound ... 1.00 in pl
alongside. thence No. ... for ...
on same offset line 40 lks. ... and 20
East 20 lks. to ... East
80.00 in place set sandstone 2 ... S.
4×5. 16 in. in the ground, for ... Sec
to recs. 13. 18. 19 & 24. marked ... Mo
3 notches on N & E edges and
raised a stone mound alongside.
From which
Quaken tree bears N. 45° W. 16 lks dist ... 1.00 Pine
marked T. 14 S. R. 16. S. 12 B. T. ... 1.00 Cot
No other trees within limits. ... 1.00 sec
Land mountainous. ... gro
Soil Grate. ... W.C.
Timber some aspen. ... 1.75 Spr
Mountainous & descends ... 1.00 Sec
on 80 ... Cor
Sept. 4th 1883. ... mon

T. 19 S. R. 1 E.

North bet 13 & 18.
Var 17½° E.

Set sandstone 11×10×8 in 6 in the ground for 1/4 sec. cor. marked 1/4 on W face and raised stone mound alongside.

On account of bluff offset West 10 chs. thence North 40 chs. thence East 10 chs. to in place set sandst. 16×11×10 in 12 in the ground for cor. to secs. 7, 12, 13 & 18. marked with 4 notches and 2 on W edges and raised a stone mound alongside.

Land broken hig hbluffs
Soil 3rate.
Timber cedar & aspen
Mountain ground under growth of Hkr.

North bet. sec. 7 & 12.
Var. 17½° E.

Ridge bears NE & SW.
Gulch draw W.
set sandstone 11×9×8 in 6 in the ground for 1/4 sec. cor. marked 1 notch on W face and raised a stone mound alongside
Gulch draw W.
In gulch dr. NW. set sandst. 11×11×10 6 in in the ground for cor. to secs. 1, 6, 7 & 12. marked 1 notch on 4 E & W edges and raised a stone mound alongside

214

East boundary Tp. 14. S. R 1 E. Northbo

Land mountains.
Soil 3rd rate.
Timber pine aspens.
Mountains dense undergrowth o

North bet. secs. 1 & 6
Cor. 17 links E.

40.00 Set sandstone 16×14×6 in. 10 in the g
for 1/4 sec. cor. marked 1/4 on W. face
raised a stone mound alongside.
60.00 high ridge bears NE. & SW.
80.00. On south side of cañon set trachyte
×6, 18 in in the ground for cor. to Tps. 13
R 1 & 2 E. marked 6 notches on
E & W edges and raised a stone mou
alongside.
Land mountains.
Soil 3rd rate.
Timber: pine, mill aspen
Mountains dense undergro
on West.

16.20
1.00
7.50
4.00
4.00

Fro
by
betw
cor
inte
for
Cor

Pas
set
for 1/4
rais
asce
Gu
set
for
two
rais
Lan
Soi
Tim
Mou

BOOK-A-197

215

North boundary Tp 14 S. R 16 E.

From the cor. to Tp. 13 & 14 S. R 15 & 16 E. set by me Trav. West on random line between said Tps. set temp. 1/2 mile cor. every 40 & 80 chs. and at 3 miles I intersect the cor. to secs. 3. 4. 33 & 34 formerly set by me from which Trav. East on true line between secs. 3 & 34 Var. 17 1/2 E.

6.20 Ash drains SW.

5.00 set granite 14 x 12 x 6. 8 in the ground for 1/4 sec. cor. marked 1/4 on N. face and raised a stone mound alongside. 1 stone from old cor.

accord

4.50 Gulch drains S. SW.

4.00 set granite 10 x 8 x 5 6 in the ground for cor. to secs. 2. 3. 34 & 35 marked two notches on E. & W edges and raised a stone mound alongside. 1 stone from old cor.

Land mountains

Soil Good.

Timber scattering cedar.

Mountains & dense undergrowth on Spurs

North boundary

East on true line
betw. secs. 2 & 35.
Var 17½° E.

27.25 Gulch drains N.W.
40.00 Set trachyte 30×20×15. 20in in the ground for ¼ sec. cor. marked ¼ on N face and raised a stone mound along side. Notch on old
80.00 Set granite 14×8×6. 9in in the ground for cor. to secs. 1. 2. 35 & 36 marked with 10 cuts E and 5 on W edges and raised a stone mound along side. Notch on old
Land mountains.
Soil Grats.
Watered.
Mountains & down and on
on 80 chs.

East on true line
betw. secs. 1 & 36.
Var 17½° E.

3.50 Gulch drains N.
16.50 " " "
20.00 " " "
40.00 Set sandstone 24×20×4in 18in in ground for ¼ sec. cor. marked

BOOK-A-

Pr. 1

on N
mou
1.00 Ridg
1.00 The co
Lan
Lan
Trin
Mou

Not.
For
Sch

BOOK-A-197 - 217

T. 14 S. R. 1 E.

on N face and raised stone mound alongside.

1. on Ridge leads NW & SE

1. on Rec cor. to Sps. 13 & 14 S. R 1 & 2 E.

Land mountainous

Soil Coarse

Timber. few cypress.

Mountainous & denuncunder=

Jonathan Cohn.

Sept. 5th 1883.

Note.

For general description see Subdivisions of this Sp.

Augustus D. Person

U. S. Dep. Surv.

BOOK-A-197

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, November 5th *1883*

The foregoing field notes of the survey of the

North, South and East boundaries

Township No. 14 South *Range No.* 1 East

Executed by Augustus D. Ferron

Under No 117 *contract of the* 5th

day of July *1883, in the month of*

September *1883, having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

Fred Salomon

U. S. Surveyor General for Utah.

BOOK-A-197

REPORT: 1884.

Filed October 22nd 1883

Examined by John H. Campbell

Transcribed by Edw. M. Shaeb

Compared by C E S & C W H.

FIELD NOTES

OF THE SURVEY ~~OF THE~~

and resurveys of

Subdivisions

OF

Township No 14 South

Range No 1 East

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Augustus D. Ferron

U. S. Deputy Surveyor,

Under his Contract No. 117.

Dated July 5th, 1883.

Survey commenced September 6th, 1883.

Survey completed September 20th, 1883.

BOOK-A-197 - 218

divisions Tp. 14 S., R. 1 E

Survey commenced: Sept 6th 1883.
with a Burt's improved Solar
Compass

My special instructions from the
surveyor general for the survey of
this Tp. ordered me to extend the
survey of this Tp. in accordance
with the existing prior survey,
both in alignment and distance.
In retracing the Salt Lake Meridian
last year I took pains to hunt
up all the existing old survey
cor. in Juab Valley, and after
a great deal of labor, determined
the chaining to be true measurement,
but all the N. & S. lines to be N 1° W.
or in other words, that the lines of
the old survey ~~were~~ run (more) with 17°
30' E. variation, instead of 16° 30' E.,
which latter is the true variation.
The new surveys ~~were~~ (must) therefore
must be in accordance with the
facts found.

Subdivisions Tp. 14. S. R 1

	I commenced at the cor. to secs 35 & 36 on the S. boundary of the Tp. formerly set by me, from which I run	
	North betw. secs. 35 & 36	40.00
	Var. 17° 30' E.	60.00
21.00	Deep hollow drains S. E.	
40.00	Set a limestone 26×12×8 in. 20 ins in the ground for 1/4 sec. cor. mon 1/4 on W. face and raised a stone mound alongside.	80.00
41.00	Enter flat top ridge & sagebrush bears N E & S W.	
52.50	Leave same & descend.	20.00
54.00	Hollow drains S. W.	
58.50	Enter flat top ridge	36.00
80.00	Set a granit 14×10×6 in. 8 ins in the ground for cor. to secs. 25. 26. 35 & 36 marked with 1 notch on S & E edges and raised a stone mound alongside.	40.00
		56.50
	Land. Mountainous.	72.50
	Soil 3rd & 1st rate	80.00
	No timber	
	Dense underbrush on 60 Chs.	

S. R 1 Subdivisions Tp. 14 S. R. 1 E.

	East on a random line betw. Secs. 25 & 36. Var. 17½° E.
40.00	Set a temporary ¼ sec cor.
60.00	To a point 36 lks. S of Witness cor. the connection with corner point will therefore be
80.00	Intersect East boundary of the Tp. 40 lks. S. of the corner point to secs. 25 & 36 from which true S. 89° 43' W on true line betw. secs. 25 & 36. with same var.
20.00	The Witness corner set by me. ascend.
36.00	Enter rolling mountain top
40.00	Set a granit 14 x 8 x 6 ± 10 ins in the ground, for ¼ sec. cor. marked with ¼ on N. face and raised a stone mound along side.
56.50	Gulch draines N. E.
72.50	" " "
80.00	The cor. to secs. 25. 26. 35 & 36 Land mountains Soil. 3rd rate Timber. scattering pines & cedars

Mountainous & dense artemisia undergrowth on 80

North betw. Secs. 25 & 26
Var. 17½° E.

12.00 Leave rolling flat & sagebrush
18.00 Enter pigeon creek canyon dr. d.
22.00 Pigeon Creek 10 lks wide 2 lks. deep runs S. W.
37.50 Wash drains S. W.
40.00 Set a sandstone 14×8×4 in. 6 in in the ground for ¼ Sec. cor. marked ¼ on W. face and raised a stone mound alongside.
48.50 Leave hollow drains S.
76.25 Enter gulch drains S. E.
80.00 In gulch set sandstone 20×15 15 ins in the ground, for cor. to secs. 24. 25 & 26 marked with 2 notches on S. & E. edges. and raised a stone mound alongside.
Land. mountains & level
Soil. 1st & 3rd rate
Timber. few cottonwoods on Creek
Dense underbrush on 80 Ch.

40.00 Set
40.30 In
Tp.
set

8.50 Gul
15.00 Des
23.50 Hol
40.15 Set
gro
on
alo
78.00 Ent
80.30 The
Las
Sou
Sin
D

Subdivisions Sp. 14 T. R 1 E.

East on random line
betw. secs. 24 & 25.
Var. 17½° E.

40.00 Set temporary 1/4 sec. cor.
40.30 Intersect E. boundary of the Sp. at cor. to secs. 24 & 25 formerly set by me from which I run
West on true line
betw. secs. 24 & 25
with same var.
8.50 Gulch drains S. E.
15.00 Descend
33.50 Hollow drains S.
40.15 Set a quartz 12×8×4 ins. 8 ins in the ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.
78.00 Enter gulch
80.30 The cor to secs. 23. 24. 25 & 26
Land. mountains.
Soil. 2nd rate.
Timber - scattering cedars & pines.
Dense underbrush on 80.30 Chs.
Sept 6. 1883.

BOOK-A-1

Subdivisions Tp. 14 S. R. 1 E. Subdivisi

North betw. secs. 23 and 24
Var. 17½° E.

Ascend

37.00 Enter rolling top of mountain

40.00 Set a limestone 14×10×6 in. 8 in. in ground for 1/4 sec. cor. marked 1/4 W. face and raised a stone mound alongside. 4.50 31.00 40.20

56.00 Descend

80.00 Set a sandstone 34×24×16 in. 20 in. in the ground for cor to secs. 13. 14 23 & 24 marked with 3 notches on E. 1 notch on E edges and raised a stone mound alongside. 42.00 71.00 80.40

Land. mountainous
Soil. 2nd rate
No timber
Dense undergrowth on 80 Chs.

East on random line
betw. secs. 13 and 24
Var. 17½° E.

40.00 Set temporary 1/4 sec. cor. 14.00 40.00

80.40 Intersect E. boundary of Tp 30 & of cor. to secs 13 & 24 formerly

R. 1 Subdivisions Sp. 14 S. R. 1 E.

124		set byrne from which Sxun S. 89.°47' W. on true line betw. secs. 13 & 24 with sam var.
Tain		
Sins in	4.50	Descend from bluff, leave aspen
ked 1/4	31.00	Gulch draius S.
mound	40.20	Set a sandstone 14 x 12 x 4 in 8 ins in the ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone m mound alongside.
16 in 20 ins		
cs. 13. 14	42.00	S. point of ridge
es on E	71.00	Hollow draius E. W.
d a stone	80.40	The cor. to secs. 13. 14. 23 & 24. Land. mountains Soil 2nd rate Timber. aspen Mountainous & dense undergrowth on 80. 40 Chs.
40 Chs.		
line		North betw. secs. 13 & 14 Var. 17 1/2° E.
4		
	14.00	Gulch draius N. W.
	40.00	Set a granit 14 x 10 x 6 ins 8 ins in the ground for 1/4 sec. cor. m arked 1/4 on W face, & raised a stone mound alongside.
2 t/p 30		
nerly		

Subdivisions Tp. 14 S. R. 7

Subdivisi

58.00 Gulch draws N.E.

80.00 Set a sandstone 14×10×8 ins. g
in the ground for cor. to secs. 11,
13 & 14 marked with 4 notches
S. and 1 notch on E edges and
raised a stone mound alongside

Land. mountains
Soil. 2nd. rate.
No timber
Dense underbrush on 80 lks.

East on a random line
betw. secs. 12 and 13
Var. 17½° E.

40.00 Set a temporary ¼ sec. cor.
80.60 Intersect E. boundary 25 lks
S. of cor. to secs. 12 & 13. formerly
set by me from which I run
S. 89.30' W. on true line
betw. secs. 12 and 13
with same var.

Ascend
15.00 Top of bluff bears N E & S W.
40.30 Set a sandstone 14×8×6 ins g
in the ground, for ¼ sec. cor. mark

42.00
64.00
70.25
70.70
72.40
74.15
80.60

4.00
5.50
6.00
7.50
16.00

¼ on
mou
Desc
Enter
Roa
Ditch
Four
leave
Sprin
runs
The co
Land
Soil
Timb
Dem
Desc
Enter
Ditch
Four
Roa
Leav

Subdivisions Sec. 14 T. R. 1 E.

	1/4 on N. face, and raised a stone mound alongside.
42.00	Descend
64.00	Enter canyon draius N.W.
70.25	Road bears N.W. & S.E.
70.70	Ditch runs N.W.
72.40	Fourmiles Creek dry, draius N.W.
	leave canyon, ascend.
74.15	Spring branch 2 lks wide 2 ins deep runs N.
80.60	Rec cor. to secs. 11. 12. 13 & 14.
	Land. mountains
	Soil. 3rd rate
	Timber. few cottonwoods on creek scattering cedars on mountains
	Dense underbrush on 80. 60 chs.
	Sept. 7. 1883.
	North betw. 11 & 12 Var. 17½° E
	Descend.
4.00	Enter canyon draius N. W.
5.50	Ditch runs N. W.
6.00	Fourmile creek dry draius N.W.
7.50	Road bears N. W. & S. E.
16.00	Leave canyon, ascend

Subdivisions Sec. 14 T. R. 1

Subdivi

30.00	Gulch draius S. W.		
40.00	Set a sandstone 10×6×6 in. 6 in in the ground, for 1/4 sec. cor marked 1/4 on W. face and raised a stone mound alongside.	4.00	
		4.80	
43.50	Gulch draius S. W.		
51.00	" " " .		
56.00	S. W. point of ridge. Colvin Cabin bears S. 71° 30' W. 2.5 Chs. dist.		
72.00	Enter hollow draius S. W.	1.00	
74.25	Stream water 1 lks wide 2 ins deep runs S.	8.00	
75.50	Wood Road bears N E & S. W.	4.40	
78.30	Stream of water 2 lks wide 2 ins deep runs S. W.		
80.00	Set granit 24×12×6 in 18 ins in the ground for cor. to secs. 1. 2. 11 & 12. marked with 5 notches on S and 1 notch on E edges & raised a stone mound alongside.	1.00	
		2.00	
		9.60	
	Land mountainous	4.80	
	Soil 2nd rate.		
	Timber. few cottonwoods on Creek		
	Mountainous and thick undergrowth on 80 Chs.		

R. 1 E. Subdivisions Tp. 14 S. R. 1 E.

	East on a random line
	betw. secs. 1 & 12.
	Var. 17 1/2° E.
	Set temporary 1/4 sec. cor.
	Intersect E. boundary of Tp.
	at cor. to secs. 1 and 12. formerly
	set by me from which I run
	West on true line
	betw. secs. 1 and 12.
	with same va.
	Gulch draius h.
	" " h. E.
	Set trachyte 14 x 10 x 6 ins in
	the ground for 1/4 sec. cor. marked
	1/4 on h face and raised a stone
	mound alongside.
	Ridge bears h E & I. W.
	Enter canyon
	h. fork of fourmile creek 5 lks
	wide 4 ins. deep runs I. W.
	The cor. to secs 1. 2. 11 & 12.
	Land. mountains.
	Soil 2nd rate.
	Timber.
	Mountainous & dense under-
	brush on 80. 80 Chs.

BOOK-A-

Subdivisions Tp. 14 S. R. 1 E.

Subdivis

North on random line
betw. secs. 1 and 2.
Var. 17 1/2° E.

40.00 Set temporary 1/4 sec. cor.

79.80 Intersect N. boundary of Tp.
40 lks. E. of cor. to secs. 1 & 2. former
set by me, from which Brus
S. 0. 1/2 E. on a true line
with same var.
Ascend.

18.00 Top of ridge bears E & W.

39.80 Set a sandstone 12 x 10 x 5 in 8 in
the ground for 1/4 sec. cor. marke
1/4 on W. face and raised a stone
mound alongside.

68.00 Enter Solon draius S. W.

79.80 The cor. to secs. 1. 2. 11 & 12.
Land mountainous.
Soil 2nd rate.
No timber.
Mountainous & dense
underbrush on 79.80 Ch.

From
the
set b

Desc
Enter
21.50
Chicka
8.32
runs
Roa
29.20
Ascen
33.00
Set b
40.00
the gr
with
a ston
Flat
57.00
Desc
63.00
Enter
73.00
drai
Tra
74.10
Pigeo
75.75
runs
Set a
40.00
in the
26 &
S. and

R 1 E. Subdivisions Th. 14 S. R. 1 E.

From the cor. to secs. 34 & 35 on the S. boundary of the Tp. formerly set by me I run

North betw. secs. 34 & 35
Var. 17½° E.

Descend.

21.50 Enter canyon drains N. W.

28.32 Chicken Creek 10 lks wide 5 ins deep runs W.

29.20 Road bears E & W.

33.00 Ascend

40.00 Set limestone 12 x 5 x 4 ins 8 ins in the ground for 1/4 sec. cor. marked with 1/4 on W. face and raised a stone mound alongside.

57.00 Flat top ridge 250 ft. high bears E & W.

63.00 Descend

73.00 Enter pigeon creek canyon drains W.

74.10 Trail bears E & W.

75.75 Pigeon Creek 8 lks wide 3 ins deep runs W. ascend

80.00 Set a limestone 14 x 10 x 4 ins 8 ins in the ground, for cor to secs. 34, 35 26 & 27 marked with 1 notch on S. and 2 notches on E. edges and

	raised a stone mound alon	60.00	Pigeon
	side.		deep
	Land. mountains	60.60	The san
	Soil 2nd rate	63.10	The san
	Timber scattering cedars	68.50	Leave
	Mountainous & dense	80.15	Reco
	undergrowth on 80 Chs.		Land.
	Sept. 8 & 1883.		Soil.
			Timbe
			Moun
	East on a random line		
	betw. secs. 26 & 35		
	Var. 17½° E.		
40.00	Set a temporary ¼ sec. cor.		
80.75	Intersect N. & S. line 19 lks. E. of		
	cor. to secs. 25. 26. 35 & 36. from	20.00	Gulch d
	which I run	26.00	"
	S. 89.° 52' W. on true line betw.	40.00	Set a lim
	with same var.		ground
25.50	Hollow drains N.E.		on W. fa
32.50	Descend		along s
40.08	Set a lime stone 14×6×6 ins. in	44.00	Hollow
	the ground for ¼ sec. cor. mark	56.20	"
	¼ on N. face and raised a stone	56.25	"
	mound alongside.	62.00	"
59.25	Enter canyon drains S.W.	74.00	"
	Trail bears N.E. & S.W.	80.00	Set gra

R. 1[illegible] Subdivisions Tp. 14 S. R. 16

o abou	80.00	Pigeon Creek 15 lks. wide 5 ins. deep runs S. W.
	80.60	The same runs E.
	83.10	The same " S. W.
ars	88.50	Leave canyon, ascend
ase	80.15	Rec. cor. to secs. 26. 27. 34 & 35.
chs.		Land. mountains
d 1883.		Soil. 3rd rate
		Timber. scattering cedars
line		Mountainous on 80.15 chs.
		North betw. 26 & 27
		Var. 17½° E
cor.		
ks. S. of		
from	20.00	Gulch draws E.
	26.00	" " E.
line between	40.00	Set a limestone 12×10×5 ins in the ground for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside.
6 ins. grits	44.00	Hollow 100 ft. deep draws N. E.
marked	56.20	" " " " "
stone	56.25	" " " " E.
	62.00	" " " " "
S. W.	74.00	" " " " S. E.
	80.00	Set granit 14×8×6 ins grits in the.

	in the ground, for cor to secs. 22. 23.		mou
	& 27 marked with 2 notches on Sa		Alpine
	E edges and raised a stone mound		dist.
	alongside.	61.50	Hollo
	Land mountains	80.40	The c
	Soil: 2nd rate		Land.
	No timber.		Soil
	Mountainous and dense		Shru
	underbrush on 80 Chs.		Mo
			un
	East on random line		
	betw. secs. 23 and 26		
	Var. 17 1/2° E.		
40.00	Set temporary 1/4 sec. cor.	39.25	Gul
80.40	Intersect N. & S. line at cor. to sec	40.00	stati
	23. 24. 25 & 26 from which 6 run		for.
	West on a true line		on W
	betw. secs. 23 and 26		mou
	with same var.	58.00	Hollo
2.00	Leave gulch drains S. E.	80.00	Set
23.00	Gulch drains S.		in th
35.00	" " S.		14. 15.
40.20	Set sandstone 14 x 8 x 3 ins. Qcis in		notch
	the ground for 1/4 sec. cor. marked		on E
	1/4 on N face, and raised a ston		mou

. R1 Subdivisions Sec. 14 S. R1 E.

. 22. 23.
s on S.
mound

e
ks.

e
6

cor. to sec
& run

S. E.

. Gun in
mark
a stone

mound alongside, from which
Alpine 7 lks diam. bears N. 65° E. 30 lks.
dist. marked 1/4 S. B. T.

61.50 Hollow drains S.

80.40 The cor. to secs. 22. 23. 26 & 27
Land. mountains
Soil 2nd rate
Timber scattering cedars
Mountainous & dense
undergrowth on 61.40 Chs

North bet'n. secs. 22 & 23.
Var. 17½° E

39.25 Gulch drains W.

40.00 Stationary Quartz 30 x 26 x 18 ins.
for 1/4 sec. cor. marked 1/4
on W face and raised a stone
mound alongside

58.00 Hollow 150 lks deep drains S. W.

80.00 Set sandstone 15 x 14 x 3 ins 10 ins
in the ground, for cor. to secs.
14. 15. 22 & 23, marked with 3
notches on S. and 2 notches
on E edges, and raised a stone
mound alongside.

Subdivisions Tp. 14 S. R. 1

	Land. mountainous	40.00
	Soil. 2nd rate	
	Timber. scattering cedars.	
	Mountainous &	
	dense underg rowth on 80	
	East on random line	
	betw. secs. 14 and 23	
	Var. 17 1/2° E.	10.00
40.00	Set a temporary 1/4 sec. cor.	19.00
80.00	Intersect N. & S. line at cor. to	35.00
	secs. 13. 14. 23 & 24 from which	40.00
	I run	
	West on true line	
	betw. secs. 14 and 23	
	with same var.	57.00
14.80	Enter round basin	68.00
21.00	Leave same	~~50~~
36.45	Cedar 20 ins. diam.	80.00
40.00	Set a sandstone 22×10×10 ins 16 ins in	
	ground for 1/4 sec. cor. marked 1/4	
	on N. face and raised a stone mou	
	alongside.	
40.25	Gulch draws S.	
57.00	" " S.	

Subdivisions Sp. 14 T. R 1 E.

40.00	The cor. to secs. 14. 15. 22 & 23
	Land. mountainous
	Soil. 2nd rate.
	No timber.
	Dense underbrush on 80 Chs.
	Sept. 10. 1883.
	North betw. 14 and 15.
	Var. 17½° E.
10.00	Enter gulch draius S. W.
19.00	leave same
35.00	Gulch draius S. W.
40.00	Set a granite 12 × 8 × 6 ins 8 ins in the ground for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside.
57.00	Gulch draius S. W.
68.00	" " S. W.
~~80.00~~	~~Enter~~ gulch draius S. W.
80.00	Set a sandstone 10 × 10 × 4 ins. 6 in the ground for cor. to secs. 10. 11. 14 & 15. marked with 4 notches on land 2 notches on Edges and raised a stone mound alongside.
	Land. mountains

Subdivisions Tp. 14 S. R. 4 W.

Soil. 2nd rate
Timber. scattering cedars.
Mountainous & dense
undergrowth on S. lines.

East on random line
betw. secs. 11 & 14
Var. 17½° E

40.00 Set temporary 1/4 sec. cor.
80.40 Intersect W. & S. line 2 lks
S. of cor. to secs. 11. 12. 13 & 14.
from which I run
S. 89° 48' W. on true line
betw. secs. 11 & 14
with same va.
40.20 Set a sandstone 12 x 8 x 6 in 8 in
in the ground for 1/4 sec. cor.
marked 1/4 on E. face and
raised a stone mound alongside.
50.50 Top of ridge bears NE & SW.
72.00 Gulch trains S. W.
80.40 Pine cor. to secs. 10. 11. 14 & 15
Land. mountains
Soil. 2nd rate

3.00 &
14.75
40.00
57.00
59.30
61.50
62.00
80.00

Subdivisions Tp. 14 S. R 1 E.

Timber. scattering cedars
Dense underbrush on 80. 40 lks.

North betw. 10 and 11
Var. 17 1/2° E

3.00 cedar 24 ins. diam.
14.75 Saddle of ridge bears N E & S W.
40.00 Set a sandstone 18 x 8 x 4 - 12 ins in the ground for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside.
57.00 Enter canyon. Drains N. W.
59.30 Four mile creek 4 lks wide 3 ins. deep runs N. W.
61.50 Road bears E & W.
62.00 Leave canyon ascend
80.00 Set a sandstone 14 x 10 x 6 ins 8 ins in the ground for cor. to secs 2. 3. 10 & 11 marked with 5 notches on East 2 notches on E edges and raised a stone mound. along side from which a cedar 14 ins diam. bears N 30° W. 30 lks dist. marked T. 14 S. R. 1. E. S. 3. B. T.

Subdivisions Sp. 14 S. R 1 E.

Land. mountainous
Soil. 2nd rate.
Timber. scattering cedars.
Mountainous & dense
undergrowth on 80 Chs.

East on random line
betw. secs. 2 and 11
Var. 17 1/2° E.

40.00	Set temporary 1/4 sec. cor.	40.00
80.27	Intersect N. & S. line 31 lks W. of cor. to secs. 1. 2. 11 & 12. from which I run	79.90
	S. 89° 47' W. on true line betw. secs. 2 and 11 with same var.	
4.00	Leave hollow drains S. W.	2.30
29.75	Gulch drains S. W.	16.50
40.13	Set a granit 10 x 8 x 6 in. 6 ins in the ground for 1/4 sec. cor. mark 1/4 on N face and raised a stone mound alongside.	29.00 39.00 39.90
59.00	Top of ridge bears N & S.	
77.00	Gulch drains S.	
80.27	The cor. to secs. 2. 3. 10 & 11	

Subdivisions Sp. 14 S. R. 1 E.

R. 1 E.

	Land. mountains Soil 2nd rate. Timber. Mountainous & dense underbrush from 80.27 chs.
	North on random line betn. Secs. 2 and 3 Var. 17½° E.
40.00	Set temporary 1/4 sec. cor.
79.90	Intersect N. boundary of Sp. at cor. to secs. 2 and 3 formerly set by me from which I run.
	South on true line with same var.
2.30	Top of ridge bears S. 17½ E.
16.50	Gulch drains N. W.
29.00	" " "
39.00	Top of high ridge bears E. & W.
39.90	Set a sandstone 10 × 8 × 6 ins in the ground for 1/4 sec. cor. marked with 1/4 on W. face and raised a stone mound alongside.

BOOK-A-1

Subdivisions Tp. 14 S. R. 16

79.90	Thecor. to secs. 2. 3. 10 & 11. Land. mountainous Soil. 2nd rate. Timber scattering cedars. Dense undergrowth on 79.9 Sept. 11. 1883.
	From the cor. to secs. 33 & 34 on the S. boundary of the formerly set by me Dec. North betw. secs. 33 & 34 Var. 17½ E
36.50	Enter canyon draining W.
38.50	Road bears E & W.
40.00	Set a post 3 ft. long, 3 ins square with chamfered stake 12 ins in the ground, for ¼ sec. cor. marked ¼ S. on W. face, dug pits, 18 + 12 ins N & S. of post 5½ ft. di and raised a mound of earth 1½ ft. high, 3½ ft. base around
40.25	Chicken creek 15 lks. wide 4 in deep runs W.

43.50	Lan
52.00	Soi
70.00	Ent
72.00	Pig
	deep
75.00	Dec
40.00	Set
	in th
	27. 2
	Iron
	E. &
	mou
	whe
	a pine
	dist.
	Lan
	Soi
	Tim
	Den
40.00	Set a
50.00	Ente

Subdivisions Pr. 14 T. R. 1 E.

43.50	Leave canyon
52.00	Top of ridge bears E. & W.
70.00	Enter Pigeon Creek canyon
72.00	Pigeon creek 5 lks wide 4 ins deep runs N. W.
75.00	Ascend
86.00	Set limestone 14 × 6 × 4 ins 8 ins in the ground for cor. to secs. 27. 28. 33 & 34 marked with 1 notch on land 3 notches on E. edges. and raised a stone mound alongside from which a pine 10 ins diam bears N 89° E. 52 lks. dist. marked T. 14 S. R. 1 E. S. 27. B. T. Land mountainous. Soil. 2nd rate. Timber scattering cedars. Dense undergrowth on 80 Ch.
	East on random line betw. secs. 27 and 34 Var. 17 1/2° E.
46.00	Set a temporary 1/4 sec. cor.
50.00	Intersect W. & S. line 35 lks N.

Subdivisions Tp. 14 S. R 1 E.

	of cor. to secs 26. 27. 34 & 35. from which Trees
	S. 89° 45 W on true line betw. secs. 27 & 34 with same ve.
5.00	Top of ridge bears N & S.
22.50	Gulch draies S.
30.50	" " S.
40.00	Set limestone 12 x 7 x 3 in 8 in in the ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.
80.00	The cor. to secs. 27. 28. 33 & 34 Land. mountains. Soil. 2nd rate. Timber. scattering cedars. Bunch underbrush on 80.00
	North betw. Secs. 27 & 28 Var. 17 1/2° E.
	Ascend
19.00	Top of ridge bears E & W.
40.00	Set a. sandstone 14 x 8 x 5 in in the ground for 1/4 sec. cor. marked 1/4 on W face and

BOOK-A

Subdiv

	rai
41.00	Gu
58.00	Ri
80.00	Set
	in
	21.
	2 no
	on
	mo
	Lan
	So
	Tr
	M
40.00	Set
80.10	Int
	S. of
	pro
	S.
6.25	Hol

Subdivisions Tp. 14 S. R 1 E.

raised a stone mound alongside.

41.00 Gulch 75 ft. deep drains N. 80° W.

58.00 Ridge 100 ft. high bears E & W.

80.00 Set a limestone 12×6×4 in Sais in the ground for cor. to secs. 21. 22. 27 & 28 marked with 2 notches on S and 3 notches on E edges and raised a stone mound alongside.

Land very broken
Soil 3rd rate
Timber scattering cedars.
Mountainous on 81 Chs.

East. on random line
betw. secs. 22 & 27
Var. 17½° E.

40.00 Set temporary ¼ sec. cor.

80.10 Intersect N. & S. line 40 chs. S. of cor. to secs. 22. 23. 26 & 27 from which I run
S. 89° 43' W on true line
betw. secs. 22 & 27
with same va.

6.25 Hollow drains N. W.

Subdivisions Tp. 14 S. R. 1 E.

Subdivi

12.25	Hollow draius N.	45.00	Jun
22.00	Top of ridge bears N. W. &		N E
40.05	Set limestone 12×6×4 ins in the ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.	65.00	Ri
		80.00	Set 10 ins secs. with and side
57.00	Gulch draius N.		
78.25	" " N.		
80.10	The cor to secs. 21. 22. 27 & 28 Land. Mountainous Soil. 2nd rate. Timber. scattering cedars. Dense underbrush on 80.		Acca mar Lan Soil Tim Mou
	Sept 12. 1883.		
	North betw. 21 & 22 Var. 17 1/2° E.		E
5.00	Bottom of Pine canyon 200 ft. deep draius W.	40.00	Set
23.00	Peak 200 ft. high.	80.55	Inte S. of fram
40.00	Set limestone 12×8×6 ins in the ground, for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside.		S.

Subdivisions Tp. 14 S. R. 1 E.

45.00 Junction of 2 gulches, head N E & S E & run W.
65.00 Ridge bears E & W.
80.00 Set a sandstone 15 x 10 x 5 in. 10 ins in the ground for cor. to secs. 15. 16. 21 & 22, marked with 3 notches on land E. edge, and raised a stone mound alongside. from which
A cedar 15 ins diam. bears N 60° W. 10 lks
marked T. 14 S. R 1 E. S. 16. B. T.
Land. mountainous
Soil 1st & 2nd rate
Timber. scattering cedars.
Mountainous on 81 Chs.

East on random line
betw. secs. 15 & 22
Var. 17 1/2° E.

40.00 Set temporary 1/4 sec. cor.
80.55 Intersect N. & S. line 27 lks.
E. of cor. to secs. 14. 15. 22 & 23
from which I saw
S. 8 & 9. 48' W. on true line
betw. secs. 15 and 22
with same va

Subdivisions Tp. 14 S. R. 1 E.

7.50	Canyon drains S. W.	80.00
40.27	Set a sandstone 12×8×6 ins. 8 ins in the ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.	
51.00	Ridge bears N. W & S. E.	
70.00	Gulch 150 ft. deep drains N. W.	
73.00	Ridge bears N. W. & S. E.	
75.50	Gulch 75 ft. deep drains N. W.	
80.55	The cor. to secs. 15. 16. 21 & 22. Land. mountainous. Soil 2nd rate. Timber. scattering cedars. Dense undergrowth on 80.55 ch.	
	North betn. secs. 15 and 16. Var. 17 1/2° E.	40.00
		80.00
17.00	Gulch drains S. W.	
22.00	" " S. W.	
40.00	Set a granit 16×10×8 ins. 12 ins in the ground, for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside.	0.50
40.15	Wood road bears S. W & N. E.	

R. 1 E. | Subdivisions Tp. 14 S. R. 1 E.

W.	
× 6 ins. 8 ins	
sec. cor	
and	
s along	
E.	
s N. W.	
E.	
ins N. W.	
1922.	
ves.	
ders.	
on 80.55 chs.	
5 Lks 16.	40.00 Set a temporary 1/4 sec. cor.
	80.00 Intersect N. & S. line 10 lks. S. of cor. to secs. 10. 11. 14 & 15. from which Sun S. 89° 56 W. on true line betw. secs. 10 & 15 with same var.
12 ins in	
r. marked	
stone	
	0.50 Leave gulch 200 ft deep drains S. W.
N. E.	

80.00 Set trachyte 24 × 16 × 12 ins. 16 ins in the ground for cor. to secs. 9. 10. 15 & 16. marked with 4 notches on S and 3 notches on E. edges and raised a stone mound alongside, from which a cedar 10 ins diam bears N 55° E. 35 lks. dist. marked T. 14 S. R. 1 E. S. 10. B. T. Land. mountainous. Soil. 2nd. rate. Timber scattering cedars. Dense undergrowth on 80 chs.

East on random line betw. secs. 10 & 15. Var. 17½° E.

BOOK-A

Subdivisions Sp. 14 S. R. 1 E.

18.50	Top of ridge bears N & S.
40.00	Set a quartz 12×8×6 ins. 8 ins. in the ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.
48.50	Hollow drains S.
64.32	A cedar 24 ins. diam.
64.00	Gulch dr. S. W.
80.00	The cor. to secs. 9. 10. 15 & 16. Land. mountainous Soil. 3rd rate. Timber scattering cedars. Dense undergrowth on Sec. Sept. 13. 1883.
	North betw. secs. 9 and 10 Var. 17½° E.
4.00	Top of ridge bears E & W.
33.50	Gulch drains N. W.
40.00	Set granite 12×8×6 ins. 8 ins in the ground for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside.
43.50	Hollow drains S. W.
79.00	Enter gulch

80.00	S
	g
	n
	3.
	n
	a. c
	m
	L
	S
	En
40.00	Se
80.20	En
	2.
	on
21.50	Gu
40.10	En
	gr
	for

Subdivisions Sp. 14 S. R 1 E.

80.00 Set granit 14×10×8 ins 9 ins in the ground for cor. to secs. 3. 4. 9. & 10. marked with 5 notches on S and 3 on E edges and raised a stone mound alongside from which a cedar 12 ins diam. bears S. 5° W. 10 lks. marked B.T. 14 S. R. 1 E. S. 9. B. T.
Land. mountains.
Soil. 2nd rate.
Timber scattering cedars.
Dense undergrowth on 80 lks

East on random line
betw. secs. 3 & 10
Var. 16° 12" E.

40.00 Set temporary 1/4 sec. cor.
80.20 Intersect N. & S. line at cor. to secs. 2. 3. 10 & 11 from which 5 ins West on true line

betw. secs. 3 & 10
with same va.

2.50 Gulch drains S.
40.10 Enter canyon dr. N. W. set a granit 10×10×4 ins. 6 ins in the ground for 1/4 sec. cor. marked 1/4 on N.

Subdivisions Sec. 14 T. 8 R. 1 E.

	face and raised a stone mound alongside.
54.20	Four miles Creek 4 lks wide & runs N.W.
57.00	Road bears N. W. & S.E.
58.00	ascend.
74.50	Gulch draws N. W.
79.90	" " N. W. E.
80.20	Sec cor. to secs. 3. 4. 9 & 10.
	Land: mountains.
	Soil 2nd rate.
	Timber. scattering cedars.
	Dense underbrush on 80.20 chs

North betw. secs. 3 & 4
Var. 17½° E.

40.00	Set a temporary ¼ sec. cor.
80.40	Intersect North boundary 35 lks E. of cor. to secs. 3 & 4 from which I run
	S. 0. 15. E on true line betw secs 3 & 4 with same var.
4.00	Wash draws S. W.
30.00	Leave sagebrush flat
40.40	Set a granit 16×10×4 is 6 ins in

Subdiv

	gr
	¼
	m
49.00	Ge
53.50	Fo
66.00	En
68.75	Fo
	4 in
69.50	R
71.00	Le
80.40	Sec
	Le
	Fo
	En
	E
	Fr
	on
	Fou
	Des
9.50	Ge
14.00	

R 1 E. Subdivisions Sp. 14 S. R. 1 E.

ground for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside.

49.00 Gulch drains W.

53.50 Top of ridge bears E & W.

66.00 Enter canyon

68.75 Four mile creek 5 lks. wide 4 ins. deep runs W.

69.50 Road bears E & W.

71.00 Leave canyon bears E & W.

80.40 The cor. to secs. 3. 4. 9 & 10.

Land. mountains

Soil 2nd rate.

Timber. scattering cedars.

Dense undergrowth on 80.40 chs.

From the cor. to secs. 32 & 33 on the S. boundary of the Sp. formerly set by me

North betw. Secs. 32 & 33

Var. 17 1/2° E.

Descend

9.50 Gulch drains W.

14.00 " " W.

Subdivisions Tp. 14 S. R. 1 E.

32.00	Gulch draines W.		
40.00	Set trachyte 14×10×6 ins in the ground for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside.	40.00	
		80.20	
44.10	Enter valley bears N E S. W.		
45.00	Ditch runs S. W.		
48.00	Chicken Creek in gulch 10 lks w 3 ins. deep runs N. W.	6.52	
49.30	Hill road runs N. W.	6.50	
49.40	Hill bears N 55° 40 W. 5 Chs. dist.	10.00	
54.00	Road bears E & W.		
80.00	Set a slate 10×8×6 ins 6 ins in the ground for cor. to secs. 28. 29. 32 & 33 marked with 1 notch on 2 and 4 Edges and raised a stone mound alongside.	10.20	
		11.50	
		40.10	
	Land. Level & Mountains. Soil 1st & 2nd rate.		
	Timber scattering cedars	52.90	
	Mountainous on 44.10 Chs and dense artemisia undergrowth on 35.90 Chs.	73.50	
		80.20	
	Sept. 14. 1883.		

Subdivisions Sp. 14 S. R. 1 E.

East on random line
betw. secs. 28 & 33.
Var. 17 1/2° E.

40.00 Set a temporary 1/4 sec. cor.

80.20 Intersect N. & S. line 45 lks
S. to secs. 27. 28. 33. 34.
S. of cor. from which Trun
S. 89° 41' W. on true line
betw. secs. 28 & 33.
with same va.

0.52 Cedar 14 ins. diam.

6.50 Enter pigeon Cr. canyon.

10.00 Pigeon Creek 10 lks wide 4 ins
deep runs N. W.

10.20 Trail bears N. W. & S. E.

11.50 Leave canyon bears N. & S. E.

40.10 Set limestone 12 x 8 x 4 & 8 ins
in the ground for 1/4 sec. cor.
marked 1/4 on N. face and
raised a stone mound along-
side.

52.90 Top of ridge bears N. W. & S. E.

73.50 Enter valley bears N. E. & S. W.

80.20 The cor. to secs. 28. 29. 32 & 33.
Land. mountainous & level.
Soil. 2nd. & 1st. rate.
Timber scattering cedar.
Dense artemisia undergrowth
on 80.20 chs

Subdivisions No. 14 T. 8 R. 1 E.

North betw. secs. 28 and 29
Var. 17½° E.

2.90	Road bears E & W.	19.20
9.00	Pigeon creek 10 lks. wide 4 ins deep	33.50
40.00	Set slate 15×12×4 ins 10 ins in the ground for 1/4 sec. cor. marked on W face and raised stone mound alongside.	40.15
80.00	Set Limestone 12×6×5 ins in the ground for cor. to secs. 20. 21. 28 & 29. marked with 2 notches on land 4 on E edge and raised a stone mound alongside.	80.30
	Land. Level.	
	Soil. 1st rate.	
	Dense artemisia and sagebrush on 80 lks.	
	East on random line	6.20
	betw. secs. 21 and 28	17.50
	Var. 17½° E.	23.00
40.00	Set temporary 1/4 sec. cor.	40.00
80.30	Intersect N & S C. L. line 23 lks. S. of cor. to secs. 21. 22. 27 & 28 from which I run	
	S. 89° 30 W on true line.	46.10

Subdivisions Tp. 14 S. R 1 E.

betw. Secs. 21 & 28
with same var.

19.20 A cedar 24 ins.
33.50 Enter valley bears NE & SW.
40.15 Set limestone 10×6×6 in 6 ins in the ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.
80.30 Rec cor. to secs. 20. 21. 28 & 29.
Land. Level & mountains.
Soil 1st & 2nd rate.
Timber. scattering cedars.
Mountainous & dense artemisia undergrowth on 80.30 chs.

North betw. secs. 20 & 21
Var. 17½° E.

6.20 Road bears E & W.
17.50 Wash drains S. W.
23.00 " " S. W.
40.00 Set a sandstone 14×6×5 in. 9 ins in the ground for 1/4 sec. cor. marked 1/4 on W. face & raised a stone mound alongside.
46.10 Road bears E & W.

Subdivisions Tp. 14 S. R. 1 E.

46.50	Wash drains W.
53.50	" " S. W.
56.10	Enter cedars N. W. & S. E.
73.50	Leave same
80.00	Set a sandstone 20×10×6 in 15 in the ground for cor to secs. 16. 17. 20 & 21 marked with 3 notches on S. and 4 on E edges and raise a stone mound alongside.
	Land. rolling
	Soil 1st rate.
	Timber scattering cedars.
	Dense artemisia undergrowth
	on 80 Chs.
	Sept. 15. 1883.
	East on random line
	betw. secs. 16 and 21
	Var. 17½° E.
40.00	Set a temporary ¼ sec. cor.
80.40	Intersect N. & S. line 27 lks. S. of cor. to secs. 15. 16. 21 & 22 from which Trees
	S. 8 g. 48 W. an true line
	betw. secs 16 and 21
	with same va

BOOK-A

Subdi

1.30	F
4.50	
20.00	
40.20	S
	in
	m
	a s
45.80	W
58.50	L
68.50	E
80.40	R
	L
	S
	T
	M
	m
12.50	E.
40.00	Set
	gra
	¼ o
	m
9.50	W.

Subdivisions Tp. 14 S. R. 1 E.

0.30	Hollow drain N.W.
4.50	" " N.
20.00	" " N.
40.20	Set a sandstone 22×20×12in 15in in the ground for 1/4 sec. cor. marked 1/4 on N. face and raised a stone mound alongside.
45.80	Wood Road in hollow dr. N.W.
58.50	Low ridge bears N.W. & S.E.
68.50	Enter valley bears N & S.
80.40	The cor. to secs. 16. 17. 20. & 21 Land. Mountainous & level. Soil 2nd & 1st rate. Timber scattering cedars. Mountainous & dense underbrush on 68.50 Chs.

North betn. 16 and 17
West 17 1/2 0 E.

12.50	E. edge of cedar grove
40.00	Set quartz 22×20×10in 15in in the ground for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside.
49.50	W. point of cedar grove.

Subdivisions Tp. 14 S. R 1 E.

80.00	Set a sandstone 15×10×6 ins 10 ins in the ground for cor. to secs. 8. 9. 16 & 17 marked with 4 notches on E. and E edges and raised a stone mound alongside.	61.70
		80.23
	Land. rolling	
	Soil 1st rate.	
	Timber scattering cedars.	
	Dense artemisia undergrowth on 80 Chs.	
		1.50
		33.75
	East on a random line betw. secs. 9 and 16.	40.00
	Var. 19 1/2° E.	
40.00	Set temporary 1/4 sec. cor.	
80.23	Intersect N. S. line at cor. to secs. 9 and 10. 15 & 16. from which True	80.00
	West on true line betw. secs. 9 and 16 with same on.	
40.12	Ên gulch set quartz 16×10×4 ins 10 ins in the ground, for 1/4 sec. cor. marked 1/4 on N. face and raised a stone mound alongside	
57.50	Enter Valley bears NE & S. W.	

BOOK-A-197 = 260

Subdivisions Tp. 14 S. R. 1 E.

61.70 Road bears N W S E.

80.23 The cor. to secs. 8. 9. 16 & 17.
Land. rolling & level.
Soil 1st & 2nd rate.
Timber. scattering cedars.
Dense artemisia undergrowth
on 80.23 Chs.

North betw. secs. 8 and 9
Var. 17 1/2° E.

1.50 Road bears N E & S E.

33.75 " " N. W. & S. E.

40.00 Set limestone 12 x 8 x 6 in. 5 in in the ground for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside.

80.00 No trace of old corner to be found
Set quartz 18 x 12 x 12 in 12 in in the ground for cor. to secs. 4. 5. 8 & 9. marked with 5 notches on East 4 notches on E. edges and raised a stone mound alongside.
Land. gently rolling
Soil. 1st. Rate.
Timber. scattering cedars.
Dense artemisia undergrowth on
80. Chs.

Subdivisions Tp. 14 S. R 1 E.

East on random line
betn. secs. 4 and 9.
Var. 17½° E.

40.00 Set temporary ¼ sec. cor.
80.00 Intersect N. S. line at cor.
to secs. 3, 4, 9 & 10 from which
Trees West on true line
betn. secs. 4 and 9
with same va.
1.00 Leave gulch
15.00 Gulch drains N.
25.50 Enter valley bears N & S.
40.00 Set a granit 30 × 20 × 10 in. 20 in.
in the ground for ¼ sec. cor.
marked ¼ on N face and
raised a stone mound alongs
61.25 Road bears N & S.
80.00 The cor. to secs. 4. 5. 8 & 9.
Land mountainous & level.
Soil 1st & 3rd rate.
Timber scattering cedar.
Dense ~~under brush~~ astem
undergrowth on 80 chs.

BOOK-A
Subdivi
Set
Int
at
mo
Ro
Fen
Gu
Dit
Roa
hou
Four
set
the g
¼ on
mou
Fenc
Race
40.27
42.00
80.37
The c
Lan
Soil,

Subdivisions Sp. 14 S. R 1 E.

North on random line
betw. secs. 4 and 5.
Var. 17½° E.

40.00 Set temporary ¼ sec. cor.
80.37 Intersect N. boundary of Sp.
at cor. to secs. 4 & 5. reset by
me from which I run
South on true line.
betw. secs. 4 and 5.
with same va.
0.22. Road bears N. W. & E.
0.89 Fence bears E & W. enter Gulch Land
15.15 Gulch draws W.
25.15 Ditch flows W.
25.22 Road bears E & W. Broadhead's
house 15 chs. east
26.40 Four mile creek dry draws W.
40.00 Set granite 14 × 12 × 6 in 8 ins in
the ground for ¼ sec. cor. marked
¼ on W. face and raised a stone
mound alongside.
40.27 Fence bears E & W. leave Gulch Land
42.00 Race track bears E & W.
80.37 The cor. to secs. 4. 5. 8 & 9.
Land. Level.
Soil. 1 rate.

Subdivisions Tp. 14 S. R. 1 E.

Subdiv

No timber.
Dense artemisia undergrowth
on 40.19 Chs.
Sept. 17th 1883.

From the cor. to secs. 31 & 32 on
S. boundary of the Tp. re-establ.
by me. Thence
North bet'w. secs. 31 & 32.
Var. 17½° E.

23.70	Road bears N ¼ S.E.
26.50	Hollow drains S.W.
36.50	Road bears E & W.
37.10	Ditch runs S.W.
38.75	Gulch drains S. 70° W.
40.00	No trace of old corner to be found
set sandstone 10×8×7. 6 in in the
ground for ¼ sec. cor. marked
1/4 on W. face and raised a stone
mound alongside.
40.40	Fence bears N & S. W. enter cultivated land
49.84	" " E & W. leave "
50.45	Road bears E & W.
51.50	Ditch runs W.
51.95	A house 3 chs. east of line.
59.95	Ditch runs W

61.00	E
63.50	S
65.00	C
74.93	S
80.00	N
40.00	N
77.00	"
80.00	En

Subdivisions Tp. 14 S. R. 1 E.

61.00 Enter cultiv. land bears E & W.
63.50 Leave same.
65.00 Road bears E & W.
74.93 Fence bears E & W. Enter Cultd Land
86.00 No trace of old corner, set sandstone 16×12×8 a 12 ins in the ground for cor. to secs. 29. 30. 31 & 32. marked with 1 notch on Sand 5 notches on E edges and raised a stone mound alongside.
Land. Level.
Soil 1st rate.
No timber.

East on random line
betw. secs. 29 and 32.
Var. 17½° E.

40.00 No trace of old cor. set temp. 1/4 sec. cor.
77.00 " " " " "
86.00 Intersect N. & S. line 37 lks S. of cor. to secs. 28. 29. 32 & 33 from which I run
S. 89. 44 W. on true line
betw. secs. 29 and 32.

Subdivisions Tp. 14 S. R 1 E.

4.00	Road bears N W & E.	80.08
40.00	Set slate 12×8×6 in. 8 ins in the ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound along side.	80.08
70.20	Road bears S E & N W	
71.15	Fence bears N & S.	
80.00	The cor. to secs. 29. 30. 31 & 32.	
	Land level.	11.27
	Soil 1st. rate.	19.50
	No timber.	20.20
	Dense artemisia undergrowth on 71.15 chs.	18.54
		26.80
		40.00
	West on random line betw. secs. 30 and 31 Var. 17½ E.	
	The line passing through the town of Levan, with many houses in its way, I offset N. 1 E. & 1 street 3.19 chs. thence W. on offset line, at	44.70 53.00 60.70 68.40 76.00 80.08
40.00	3.19 chs. south, no trace of old cor. to be found, set temp. 1/4 sec. cor. thence W on offset at	

R 1 E. | Subdivisions Tp. 14 S. R. 1 E.

80.08 481 Chs. south to corner
The connection will therefore be.
80.08 Intersect Salt Lake Meridian 62 lks.
N. of cor. to secs. 30 & 31 reset by me,
from which I run on offset as before
N. 89° 34' E. on true line
betw. secs. 30 & 31
with same va.
11.27 Leave field, fence bears N. & S.
13.50 Center of street 150 lks. wide bears N. & S.
20.20 " " " 180 " " " "
28.54 " " " 184 " " " "
36.80 " " " 150 " " " "
40.08 319 chs. S., set on public square in Levan
a sandstone 24 x 18 x 18, 16 ins in the ground for
1/4 sec. cor. marked 1/4 on N. face and raised a
stone mound alongside, then along on offset.
44.70 Center of street 145 lks. wide. Bears N. & S.
53.00 Center of street 153 " " " "
60.70 " " " 140 " " " " "
68.40 " " " 190 " " " " "
76.00 Leave town of Levan.
80.08 The cor. to secs. 29. 30. 31 & 32.
Land. level.
Soil. 1st rate.
Timber.

Subdivisions Tp. 14 S. R. 1 E.

North betw. secs. 29 and 30.
Var. 17½° E.

1.19	Fence bears E & W.	
1.26	Ditch bears E & W.	40.00
3.31	Road bears S. W & N.E.	
11.65	House 75 lks. west of line	62.00
14.75	Ditch runs S. W.	80.00
16.85	" " "	
40.00	No trace of old cor. to be found, set a sandstone 14×10×8 in. 8 ins in the ground for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside.	13.40
80.00	No trace of old cor. to be found, set a sandstone 16×10×8 in. 12 ins in the ground, together with the old box stake which was found lying in bush close by, for cor. to secs. 19. 20. 29 & 30. marked with 2 notches on S. and 5 notches on E edges and raised a stone mound alongside.	40.00
		66.00
		69.40
		80.00
	Land level.	
	Soil 1st rate.	
	No timber	
	Fence artemisia underground	

on 78.87 Chs.

R. 1 E. | Subdivisions Tp. 14 S. R. 1 E

	East on random line
	betw. secs. 20 and 29
	Var. 17½° E.
40.00	No trace of old cor. to be found, set
	temporary ¼ sec. cor.
62.00	No trace of old cor. to be found
80.00	Intersect N. & S. line at cor.
	to secs. 20. 21. 28 & 29. from
	which I run
	West on true line
	betw. secs. 20 and 29
	with same va.
13.40	Road bears N.E. & S.W.
40.00	Set a sandstone 10×8×6 in. 6 in
	in the ground for ¼ sec. cor.
	marked ¼ on N face and
	raised a stone mound alongside.
66.00	Wash 7 ft. deep drains N.W.
69.40	" 2 " " " N.W.
80.00	The cor. to secs. 19. 20. 29 & 30.
	Land. level
	Soil Slate
	No timber
	Dense artemisia
	undergrowth 30 Rds.

Subdivisions Tp. 14 S. R. 1

West on random line
betw. secs. 19 and 30.
Var. 17½° E

40.00 No trace of old cor. to be found
temporary ¼ sec. cor.

80.15 Intersect Salt Lake Meridian
34 lks. N. of cor. to secs. 19 & 30
reestablished by me from which
I run

N. 89.° 45° E on true line
betw. secs. 19 and 30.
with same va.

40.15 Set sandstone 16×10×4± 12 ins in
the ground for ¼ sec. cor. mark
¼ on N face and raised a stone
mound alongside

45.34 Fence bears N & S. leave the field,
Co. Road on east side of fence

49.00 House 3.50 Chs. north of line.

80.15. The cor. to secs. 19. 20. 29 & 30.
Land. Level.
Soil. 1 rate.
No timber.
Dense artemisia undergrowth
on 34.66 Chs.

Sept. 18. 1883.

Subdi

8.35 Ya
18.25
20.20 Ro
28.80
40.00 No
sam
gra
1/4
ma
80.00 No
a gr
gra
mar
5 on
mar
Lan
Soi
No
Di

BOOK-A-197

Subdivisions Sec. 14 T. R 1 E

North betwn. secs. 19 and 20

Var. 17 1/2° E

8.35 Wash 7 ft. deep drains N. W.

18.25 " 7" " " N. W.

20.20 Road bears E & W.

28.80 " " E & W.

40.00 No trace of old cor. to be found, set sandstone 14 x 10 x 6 in gr in the ground for 1/4 sec. cor. marked 1/4 on N. face and raised a stone mound alongside.

80.00 No trace of old cor. to be found set a granit 14 x 10 x 8 in 10 ins in the ground for cor. to secs. 17. 18. 19 & 20 marked with 3 notches on S. & S on Edges and raised a stone mound alongside.

Land. level.

Soil 1st rate.

No timber.

Bêche artemisia undergrowth on 80 chs.

Subdivisions Tp. 14 S. R 16.

East on random line
betw. secs. 17 and 20.
Var. 17 1/2 E.

40.00 No trace of old cor. to be found, set a temporary 1/4 sec. cor.

71.00 No trace of old cor. to be found.

80.10 Intersect N & S. line at cor. to secs. 16. 17. 20 & 21 from which I run West on true line betw. secs. 17 and 20 with same var.

40.05 Set limestone 10 x 6 x 4 in. 6 in in the ground for 1/4 sec. cor. marked 1/4 on N face and raise a stone mound alongside.

46.50 Road bears S. W & E.

80.10 The cor. to secs 17. 18. 19 & 20.
Land level
Soil 1st rate.
No timber.
Dense artemisia undergrowth on 80.10 chs.

Subdivisions Tp. 14 S. R 16 E.

West on random line
betw. secs. 18 & 19.
Var. 17½° E.

40.00 No trace of old cor. to be found
set a temporary ¼ sec. cor.

80.22 Intersect Salt Lake Meridian
14 lks N. of cor. to secs. 18 & 19.
reestablished by me from
which I run
W. 89° 54' E on a true line
betw. secs. 18 & 19
with same va.

40.22 Set limestone 12 x 6 x 4 in 8 cm
in a mound for ¼ sec. cor.
marked with ¼ on N face, &
raised a stone mound along side.

57.50 Co. Road bears N & S.

66.65 Road bears N & S.

80.22 The cor. to secs. 17. 18. 19 & 20.
Land. Level.
Soil 1st rate.
No timber.
Some artemisia and cedar
growth on 80. 22 Chs.

Subdivisions Tp. 14 S. R. 18

	North betw. secs. 17 and 18. Var. 17 1/2° E.	79.45
40.00	No trace of old cor. to be found, set sandstone 12×8×6 ins 8 ins in the ground for 1/4 sec. cor. mark 1/4 on W face and raised a stone mound alongside.	39.73
80.00	No trace of old cor. to be found set granite 14×10×4 ins 9 ins in the ground for cor. to secs. 7. 8. 17 & 18. marked with 4 notches on S & W 5 notches on E edges and raised a stone mound alongside. Land level. Soil Skate. No timber. Dense artemisia undergrowth on 80.00 chs.	79.45
	East on random line betw. 8 and 17. Var. 17 1/2° E.	40.00
40.00	No trace of old cor. to be found set a temporary 1/4 sec. cor.	80.12
14.00	No trace of old cor. to be found.	

BOOK-A-197 = 274

Subdivisions Tp. 14 S. R. 16

79.45 Intersect N. & S. line at cor. to secs. 8. 9. 16 & 17. from which I run

West on true line between secs. 8 and 17

with same var.

39.73 Set granite 10 x 8 x 5 ± 6 in in the ground for 1/4 sec. cor. marked 1/4 on E. face and raised a stone mound alongside.

79.45 The cor. to secs. 7. 8. 17 & 18.

Land. level.

Soil 1st rate.

No timber.

Dense artemisia undergrowth on 79.45 Chs.

West on random line between secs. 7 and 18.

Var. 17½° E.

40.00 No trace of old cor. to be found, set a temporary 1/4 sec. cor.

80.12 Intersect Salt Lake Meridian at cor. to secs. 7 & 18, reset by me from which I run

Subdivisions Tp. 14 S. R 1 E.

East on true line
betw secs. 7 & 18.
with same va.

40.12 Set granit 10×6×4 6in in the ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

57.35 Road bears N & S.

77.25 " " "

80.12 No cor. to secs. 7. 8. 17 & 18.
Land. level.
Soil 1st rate
No timber.

Sept. 19. 1883.

North betw. secs. 7 & 8
Var. 17½° E.

37.55 Road bears N.E. & S.W.

40.00 No trace of old cor. to be found, set granit 10×8×6in 6in in the ground for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside

80.00 No trace of old cor. to be found set cobble 15×12×12in 10in in the ground for cor. to secs. 5. 6. 7 & 8. marked with 5 notches on S & E edges and raised

11.60
35.00
40.05
80.10

Subdivisions Sec. 14 T. R 1 E.

a stone mound alongside.
Land. Level
Soil 1st rate.
No timber

East on random line
betw. Secs. 5 and 8
Var. 17½° E.

40.00 No trace of old cor. to be found, set temporary sec. cor.

80.10 Intersect N. & S. line at cor. to secs. 4. 5. 8 & 9. from which I run

West on true line
betw. secs. 5 and 8
with same va.

11.60 Road bears S E & N W.

35.00 Leave sagebrush enter Grassland

40.05 Deposited cobble 4 in diam, for 1/4 sec. corner, marked 1/4 and raised a stone mound over it.

80.10 The cor. to secs. 5. 6. 7. 8.
Land. Level.
Soil 1st rate.
No timber
Dense artemisia undergrowth

Subdivisions Tp. 14 S. R. 1

West on random line
betw. secs. 6 and 7
Var. 17½° E.

40.00 No trace of old cor. to be found, temporary 1/4 sec. cor.

80.04 Intersect Salt Lake Meridian 19 lks. S. of cor. to secs. 6 & 7. rest by me from which I run S. 89° 42' E. on true line betw. secs. 6 and 7 with same va.

40.04 Deposited Quartz Hinc diem 12 in ground for 1/4 sec. cor. marked 1/4 raised a stone mound over it.

61.50 Road bears N & S.

80.04 Pre cor to secs. 5. 6. 7 & 8.
Land: Level
Soil 1st rate.
No timber.

North on random line
betw. secs. 5 and 6.
Var. 17½° E.

40.00 No trace of old cor. to be found, set temp. 1/4 sec. cor.

Divisions Tp. 14 S. R. 1 E.

Intersect N. boundary of Tp. at cor. to secs. 5 & 6 from which I run
South on true line
betw. secs. 5 & 6.
with same on.
Set cobble 12 x 10 x 8. 8 ins in the ground for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside.
The cor. to secs. 5. 6. 7 & 8.
Land. level
Soil 1st rate.
No timber.

Sept. 20/83.

General Description.

The additional land surveyed in this Tp. embraces the valleys along Chicken creek, Pigeon creek & four mile creek and the mountains adjacent there

te. The greater part is mount
Much can be cultivated witho
irrigation. The valleys are
mostly all claimed.
The applicant's improvemen
are situated in Secs. 4 & 11 an
consist of considerable fencin
road making, a house and
land under cultivation.

Respectfully
A. D. Perron
U. S. Dep. Surv

A list of th
ployed by Au
United States
ning, measuri
corners descri
the survey of
subdivis
13 and 14

of the Salt La
tory of Utah,
in which they
Hill
O
Ha
Jam

BOOK-A-197

[4.—LIST OF NAMES.]

A list of the names of the individuals employed by Augustus D. Ferron *United States deputy surveyor, to assist in running, measuring, and marking the lines and corners described in the foregoing field notes of the survey of* the Exterior and subdivision lines of Tps. No. 13 and 14 S. Range No 1 East

of the Salt Lake base and meridian in the Territory of Utah, showing the respective capacities in which they acted.

William Hoeber, *Compassman.*
Olof Larsen, *Chainman.*
Harry Pitchforth, *Chainman.*
....., *Chainman.*
....., *Chainman.*
James N Jarrett, *Axeman.*
....., *Axeman.*
....., *Flagman.*

BOOK-A-197

[5.—FINAL OATHS OF ASSISTANTS.]

We hereby certify that we assisted Augustus J Treon United States deputy surveyor in surveying all those parts or portions of the Tps No 6, 13 & 14 S. of Range No 1 East,

of the Salt Lake base and meridian in the Territory of Utah, as are represented in the foregoing field notes as having been surveyed by him and under his direction; and that said survey has been in all respects, to the best of our knowledge and belief, well and faithfully surveyed, and the corner monuments established according to the instructions furnished by the United States surveyor-general for Utah.

William Roeber, Compassman.
Olof Larsen, Chainman.
Harry Pitchforth, Chainman.
....., Chainman.
....., Chainman.
James W Jarrett, Axeman.
....., Axeman.
....., Flagman.

Subscribed and sworn to before me this 6th day of October 1883.

A J Treon
U S Deputy Surv.

BOOK-A-197

[6.—FINAL OATH OF UNITED STATES DEPUTY SURVEYOR.]

I, Augustus Gibson,
United States deputy surveyor, do solemnly swear that in pursuance of instructions received from Fred. Salmon
United States surveyor general for Utah, bearing date of the 5th day of July, 1883, I have well, faithfully, and truly, in my own proper person, and in strict conformity with the instructions furnished by the United States surveyor general for Utah, the surveying manual, and the laws of the United States, surveyed all those parts or portions of the Exterior Subdivision Lines of Tps No 13 & 14 South, of Range No 1 East,

.....

.....

.....of the Salt Lake base and meridian in the Territory of Utah, as are represented in the foregoing field notes as having been surveyed by me and under my directions; and I do further solemnly swear that all the corners of said survey have been established and perpetuated in strict accordance with the surveying manual, printed instructions, the special written instructions of the United States surveyor general for Utah, and in the specific man-

ner described in the field notes, and that the foregoing are the **TRUE** *field notes of such survey; and, should any fraud be detected, I will suffer the penalty of perjury, under the provisions of an act of Congress, approved August 8, 1846.*

Augustus D. Thurm

United States Deputy Surveyor.

Subscribed and sworn to before me this 5th *day of* November *1883.*

Edward Michaelis

Notary Public

U. S. SURV

Salt L

The fo

resur

Township N

Executed by

Under Ju

day of

Septem

amined. the

the said fie

hereby appr

BOOK-A-197

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, November 5th, 1883

The foregoing field notes of the survey ~~of the~~ and resurvey of Subdivisions *Township No.* 1 South *Range No.* 1 East *Executed by* Augustus G. Ferron *Under* No 117. *contract of the* 5th *day of* July *1883, in the month of* September, *1883, having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

Fred Salomon

U. S. Surveyor General for Utah.

BOOK-A-197

REPORT: 1884

Filed September 28 1883

Examined by John W Campe

Transcribed by L W Nickok

Compared by O E Salsbury & L W Nickok

FIELD NOTES

OF THE SURVEY OF THE

South and East

boundaries

OF

Township No 26 South

Range No 1 East

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Augustus D Ferron

U. S. Deputy Surveyor,

Under his Contract No. 117

Dated July 5th, 1883.

Survey commenced August 14. 1883

Survey completed August 20. 1883.

BOOK A-197

Township 26 South R. 16 East



BOOK A-197

[1.—PRELIMINARY OATH OF COMPASSMAN.]

I, George Marchbank

do solemly swear that I will well and truly perform the duties of compassman, according to instructions given me, and to the best of my skill and ability, in the survey of the Exteriors and Subdivisions of Tps 26 South, in Ranges 1 and 2 East,

of the Salt Lake base and meridian in the Territory of Utah.

George Marchbank

Compassman.

Subscribed and sworn to before me this 14th *day of* August *188*6

A D Tenor

U. S. dep. Sur.

BOOK-A-197

[2.—PRELIMINARY OATH OF CHAINMEN.]

We, Olof Larsen

and Enoch Jorgensen

do solemnly swear that we will well and faithfully execute the duties of chain carriers; that we will level the chain upon even and uneven ground and plum the tally pins, either by sticking or dropping the same; that we will report the true distance to all notable objects, and the true length of all lines that we assist in measuring, to the best of our skill and ability, and in accordance with instructions given us, in the survey of the Exteriors and Subdivisions of Sps 26 South in Ranges 1 and 2 East

of the Salt Lake base and meridian in the Territory of Utah.

Olof Larsen, Chainman.

Enoch Jorgens, Chainman.

....., Chainman.

....., Chainman.

Subscribed and sworn to before me this 14th day of August 1883.

A. D. Lyon

U.S. Deputy Surv.

BOOK-A-19

[3.—PRELIMINARY OATH OF AXEMEN.]

We, R. H. Thompson

and .....

do solemly swear that we will well and truly perform the duties of axemen, in the establishment of corners and other duties, according to instructions given us, and to the best of our skill and ability, in the survey of Exteriors and subdivisions of Tp. 26 South in Ranges No 1 and 2 E.

of the Salt Lake base and meridian in the Territory of Utah.

R. H. Thompson, Axeman.

....., Axeman.

Subscribed and sworn to before me this 11th day of August 1883.

A. D. Gunn

U. S. Dep. Surv.

BOOK-A-197 - 280

South Boundary Tp. 26 S. R. 1 E.

Survey commenced: August 14th 1883
The instrument used is a Gurley Solar compass, examined and approved by the U. S. Surv. Gen. office, which was tested frequently on a meridian obtained by an observation of Polaris made for that purpose.
I begin at the cor. to Tps. 26 & 27 S. R 1 & 1 W. on the Salt Lake Principal Meridian which is a Granite stone 24"x12"x8" marked S. L. M. and 6 notches and N. P. & Wedges with stone mound from which Iron East on true line, the S. E. cor. of this Tp. not being established.

East on True line
betw. secs. 6 & 31
Var. 16° 30' E.

Ascend.

7.60 Allowing for convergency of Meridian set sandstone 16x10x5 ins, 11 ins in the ground for 1/4 sec. cor. marked 1/4 on N. face and raised a stone mound 1 foot

10.10 Ridge bears N & S.

South Boundary Tp. 26 S.

~~48.00~~	Hollow drains S.
70.90	Road bears N W & S E.
77.60	Set sandstone 16×8×6 in the ground, for cor. to secs 5. 6. 31 & 32 marked 1 noth Wand S on E edges and ra a stone mound alongs Land. mountainous Soil 2nd rate. Timber pen. cedars. Mountainous & dense undergrowth on 77. 6

East on true line
betw. secs. 5 and 32
Var. 16° 30' E

8.00	access
37.00	Ridge bears N & S.
40.00	Set sandstone 16×8×7 in ground for 1/4 sec. cor. m 1/4 on N. face and raised stone mound alongsi
42.00	Hollow drains E.
63.00	Ridge bears N & S.
65.00	Hollow drains E.

BOOK-A-197 282

North Boundary Tp. 26 S. R. 1 E.

Top of main ridge bears
N & S. set sandstone 16×16×
12 ins 12 ins in the ground for
cor. to secs. 4. 5. 32 & 33. marked
with 4 notches on E and 2 on
Wedges and raised a stone
mound alongside.
Land. mountainous
Soil 2nd rate
No timber.
Heavy mountains on West

East on true line
Intersects the 33
Var. 16° 30' E.

Recess
Set a sandstone 14×12×6 ins
ins in the ground for 1/4 sec.
cor. marked 1/4 on N. face
and raised a stone mound
alongside.
Hollow drains S.
Set sandstone 22×6×6 ins
14 ins in the ground for cor.
to secs. 3. 4. 33 & 34 marked

South Boundary Sp. 26. South Bou

with 3 notches on E & W sides
and raised a stone mound
alongside.
Land mountainous
Soil 2nd rate.
Timber a few aspen.
Heavy mountains on So

East on true line
betw. secs. 34 & 35
Var. 16° 30' E.

27.00 Hollow drains S. accum 1.60
40.00 Set sandstone 16x8x8 in 11
in the ground for 1/4 sec. cor 16.00
marked 1/4 on N. face and 40.00
raised a stone mound alo
side.
45.00 Ridge bears N & S.
53.00 Hollow drains N. W. 78.00
58.00 Enter table mountain 80.00
dense artemisia undergr
80.00 Set sandstone 14x12x4 in
9 ins in the ground for cor
to secs. 2. 3. 34 & 35 marke
with 4 notches on W. and
2 on Edges and raised

Sp. 26. South Boundary Sp. 26 S. R. 1 E.

a stone mound alongside.
Land. mountainous
Soil 2nd rate.
Timber pin aspen
Mountainous & dense
undergrowth on 80 chs.
August 14 A.D. 1883

East on true line
betw. secs. 2 and 35.
Var. 16° 30' E.

3 large clumps of rocks
descend

Road N. W. & S. E.

Set a sandstone 30 x 20 x 20 in.
20 ins in the ground for 1/4 sec. cor.
marked 1/4 on N. face and raised
a stone mound alongside.

Road bears N. E. & S. W.

Set sandstone 22 x 16 x 8 in.
15 ins in the ground for cor.
to secs. 1. 2. 35 & 36. marked
with 1 notches E and 5 on
W. edges and raised a stone
mound alongside.

Land broken table mountains

BOOK-A-19

South Boundary Tp. 26 S. R. East Bou

Soil 2nd rate.
Timber few aspen
Dense undergrowth on 80

East on true line
betw. secs. 1 and 36
Var. 16° 30' E.

3.00 Access
40.00 Set sandstone 30×20×20 in. in the ground for 1/4 sec. cor. marked 1/4 on N. face & raised a stone mound alongs
50.00 Hollow drains S.
73.53 " " S.
80.00 On boulder point set sandsto 20×14×6, 15 in in the ground for cor. to Tps. 26 & 27 S. R. 1 & 2 E. marked 6 notches on N. S. E & Wedges and ra a stone mound alongside.
Land mountainous
Soil 2nd rate
Timber, few scattering aspen
Heavy Mountains on 80 chs.

August 15th 1883.

From
set by
c

3.00 Stoc
40.00 Set
in th
1/4 on
mou
52.50 Ent
62.90 Abo
per
Eur
Set
mar
×2 f
Sa
cor
a st
The
set
this
flag
the
77.
80.00 Set

BOOK-A-197 = 286

6 S. R. East Boundary Tp. 26. S. R. 1 E.

From the cor. to Tp. 26 & 27 S. R. 1 & 2 E.
set by me during this survey I run
North betw. secs. 31 & 36.
Var. 16° 30' E.

3.00 Steep ascend.

14.00 Set sandstone 20×20×6. in
in the ground for 1/4 sec. cor. marked
1/4 on W. face and raised a stone
mound alongside.

52.50 Enter mountain Top.

62.90 Abrupt descend ledge of
perpendicular rocks.
Further chaining being impossible,
I leave a flag at this point, also
marked a stationary boulder 2×2
×2 ft. above ground, one notch on
East and South Edges. W. C. for Witness
cor to secs. 25. 30. 31 & 36 and raised
a stone mound alongside.
Thence ~~around~~ mound to a flag, previously
set by me in meadow N. from
this point, and triangulate to
flag on top of mountain, making
the distance betw. the two flags
77.00 chs.

80.00 Falling in said triangulation
is not set

East Boundary Sp. 26 S. R. 1 E.

Land mountainous
Soil 2nd rate.
Timber, some pine & aspen
Heavy Mountains and
dense undergrowth on S

North betw. secs. 25 & 30
Var. 16° 30' E.

From flag in triangulation
in meadow I measure back S
27 chs. which brings me to
32.90 on this line. - Foot of mountain
Enter meadow & willows.
40.00 Set Trachyte 14×10×8 in. in the
ground for 1/4 sec. cor. marked
1/4 on W. face and raised a stone
mound alongside.
42.57 Slough at head of Fish Lake
46.90 across same.
66.00 Leave willowy meadow &
Enter dense sage brush flat.
80.00 Set granite 22×20×12, 15 in. in th
ground for cor. to secs. 19. 24. 25 & 30
marked with 4 notches on N and
2 on E edges, and raised a stone
mound alongside.

17.50
22.00
24.50
27.00
40.00
70.00

S. B.; East Boundary Tp. 26 S. R. 1 E.

	Land: in part mountains, meadow & artemisia flat.
	Soil 1st & 2nd rate
	Timber Pine & aspen
	Heavy mountains on 32.90 chs.
	Dense undergrowth " 47.10 "
	Total 80. 00 chs.
	North betw. secs. 19 and 24.
	Var. 16° 30' E.
17.50	Road bears N E & S W.
32.00	same " N.
34.50	leave same " N. E. 3 chs. to Lake
37.00	Thompson Creek 5 lks wide 5 ins deep
	runs S E. 2.50 chs to Lake thence
	Enter dense willows
40.00	Set granite 22×22×12 15 in
	in the ground for 1/4 sec. cor.
	marked 1/4 on W. face & raised
	a stone mound along side.
	from which
	an aspen 5 ins diam bears N 85° E. 5 lks dist.
	" " 4 " " " S. 25° W. 19 " "
	both marked 1/4 S. B. T.
	ascend mountains.
70.00	Gulch drains E.

East Boundary Tp. 26. S. R. East Bo

80.00	Set conglomerate 24×20×10 in the ground for cor. to secs. 13 18. 19 & 24. marked with 3 notches N & S. edges & raised a stone mou alongside.	16.00	Set g for co notch stone Land Soil Timb Hea
	Land. mountainous & artemisia		
	Soil 1st & 2nd rate.		
	Timber. few pine & aspen.		
	Heavy Mountains on 40 chs.		
	Dense artemisia " 40.		
	Total 80.00 ch August 18/83	40.00	Set g for 1/4 a sto
	North betw. secs. 13 and 18 Var. 16° 30' E.		
13.00	Gulch drains E.	15.00	Dens
30.00	Ridge spur bears E & W.	15.00	Holl
35.00	Canyon drains E.	6.00.	Set g
40.00	Set plate 24×14×5. 18 in in the ground for 1/4 sec. cor. marked 1/4 on W. face & raised a stone mound alongside.		for cor. Ton S. Land Soil Timb He
51.50	Lone pine 5 in diam.		
52.50	Ridge bears 4 W & S.E.		
57.50	Canyon 275 ft. deep dr. S. E.		
63.00	Enter top of mountains		
71.00	Clump of pines		

BOOK-A-197

...S. R. East Boundary Tp. 26 S. R. 1 E.

20×10×16.00 Set granite 24×20×12 in 20 in in the ground
to secs. 1 for cor. to secs. 7. 12. 13 & 18. marked with 2
3 notches notches on N & W on S. edges, & raised a
ine mou stone mound alongside.
Land. mountainous
artemisia Soil 2nd rate.
Timber. scattering pine & aspen.
Heavy Mountains on S. bdy.
spen.
40 chs.
40 "
80.00
4/8/83
40.00 Set granit 18×18×12 in 12 in in the ground
3 and 18 for 1/4 sec. cor. marked 1/4 on W. face & raised
a stone mound alongside.
15.00 Descend
W. 15.00 Hollow drains E. ascend
0.00. Set granite 24×20×10 in 20 in in the ground
in in the for cor. to secs. 1. 6. 7 & 12. marked with 1 notch on N.
marked 5 on S. edges & raised a stone mound alongside.
stone Land. mountainous
Soil 2nd rate.
Timber, few pine & aspen.
Heavy Mountains on S. bdy.

S. E.

North betw. secs. 7 and 12.
Var. 16° 30' E.

East Boundary Tp. 26 S. R. 1 East

North betw. secs. 1 and 6.
Var. 16° 50' E.

16.00 Top of slope
26.50 Head of deep canyon drains N.
40.00 Set slate 23×16×5 15 ins in the ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mo along sive.
41.75 Canyon drains SE.
73.75 Intersect 5th Standard Par. S. 15, 83 chs. E of Standard Cor. to Tps. 25 S. R 1 & 2 E. being a Trachyte stone 25"×14"×4" marked 6 notches on N. E and W. edges where I set a granite 16×12×10 ins in the ground for a closing cor. to Tp. 26 S. R 1 & 2 E. marke with 6 notches on S. E. & W edges and raised a stone mound along sive.

Land mountainous
Soil 2nd rate.
Timber scattering pine & aspe
Heavy Mountains on E. 75

August 29/83

BOOK-A-197 - 292

East Boundary Tp. 26 S. R 1 E.

Note: The above connection corresponds with my connection made two days previous with the cor. to Tps. 26 & 27 S. R. 2 & 3 E.

To further satisfy myself I rechained several miles of the Standard line and ascertained that each mile was from 2.00 to 3.00 chs. short, which shortness the connection indicates.

Note: For general description see subdivisions of this township

Respectfully
A. B. Perron
U. S. Dep. Surv

BOOK-A-197

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, November 5th 1883.
SB July 26. 1884

The foregoing field notes of the survey of the South and East boundaries

Township No. 26 South *Range No.* 1 East

Executed by Augustus G. Feiren

Under No. 117 *contract of the* 5th

day of July *1883, in the month of*

August *1883, having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

Edw Saloman

U. S. Surveyor General for Utah.

BOOK-A-197

REPORT: 1884

Filed September 28, 1883

Examined by Johnson Campbell

Transcribed by Edward Michaelis

Compared by O.E.S. & L.W.H.

FIELD NOTES

OF THE SURVEY OF THE

Subdivisions

of the Fractional

OF

Township No 26 South

Range No 1 East

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Augustus D. Ferron

U. S. Deputy Surveyor,

Under his Contract No. 217.

Dated July 5th 1883.

Survey commenced August 21 1883

Survey completed August 23 1883.

BOOK A-197 - 293 -

Subdivisions Sp. 26 S. R. 1 E.

Survey commenced: Aug. 21/83
with a Gurleys improved
Solar Compass.
I commence at the cor. to secs. 35 & 36 on the S. boundary of the Sp. formerly set by me & run
North betw. Secs. 35 and 36.
Var. 16° 30' E.

6.50 Descend
6.00 Enter flat
4.00 Set trachyte 18×12×10in 12 in in the ground for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside.
3.65 Road bears N E & S W.
4.00 Set granite 30×25×10, 20 in in the ground for cor. to secs. 25. 26. 35 & 36 marked with 1 notch on S & E edges and raised a stone mound alongside.
Land, mostly flat, some mountainous
Soil 1st & 2nd rate.
Timber some pines.
Mts. Mountainous on 36, 00 chs.

Subdivisions Tp. 26 S. R. 1 E.

East on random line
betw. secs. 25 and 36
Var. 16° 30' E.

40.00 Set temporary 1/4 sec. cor.
Then offset S. 7.10 chs., E 40.80 chs
to a point 35 lks. N. of Witness
to secs. 25 and 36, set during the
survey. The intersection will
therefore be

80.80 Intersect E. boundary of Tp.
35 lks. N. of cor. point to secs. 24.00
36 from which I run
N. 89° 45' W. on true line
betw. secs. 25 and 36
with same var.

40.40 Set granite 22x20x12 in. 15 in. in the
ground, for 1/4 sec. cor. marked
1/4 on N face and raised a stone
mound alongside.

49.00 Enter bottom land.

79.70 Wagon road bears N E & S W.

80.80 The cor. to secs. 25. 26. 35 & 36.
Land. mostly mountainous.
Soil 2nd rate.
Timber. scattering aspen & pine
High Mountainous on 49 chs.

BOOK-A

Subdivisio

N

.75 Accr
2.00 Ente
4.00 Leave
6.00 Set
grou
1/4 on
mou
large
24.00 Mark
+3 ft.
2 mou
raise
for cor.
Aspen
mark
Aspen
mark
Land
Soil.
Timb
Hea

BOOK-A-197 2951

Subdivisions Tp. 26 S. R. 1 E.

North betw. secs. 25 and 26.
Var. 16° 30' E.

.75 Ascend mountains.
2.00 Enter dense aspen timber
4.00 Leave same.
4.00 Set granite 30x25x20 in. 20 in in the ground for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside, from which large red boulder bears N 10° E. 22 lks dist. Marked stationary trachyte 3x3 +3 ft. above ground with a cross, 2 notches on S. E. top on E limb +, and raised a stone mound alongside.
4.00 For cor. to secs. 23. 24. 25 & 26, from which 8 in aspen 6 ins diam. bears N. 85° E. 4 lks dist. marked T. 26. S. R. 1 E. S. 24. B. T.
An aspen 4 ins. diam bears N. 15° W. 22 lks dist. marked T. 26. S. R. 1 E. S. 25. B. T.
Land mountainous
Soil. 2nd rate.
Timber. some aspen.
Heavy Mountains on W. & S.

Subdivisions Tp. 26. S. R. 1 E.

East on random line
betw. secs. 24 and 25.
Var. 16° 30' E.

40.00 Set temporary 1/4 sec. cor.
80.20 Intersect the E. boundary of T
at cor. to secs. 24 & 25. set by m
from which Trees
West on true line
betw. secs. 24 and 25.
with same var.
8.00 Road bears N E & S. W.
13.50 Enter aspen accum
19.00 Leave "
35.00 Enter " (Russell)
40.00 Marked stationary trachyte
x 3 ft. above ground 1/4 on N. fa
for 1/4 sec. cor. and raised a stone
mound alongside.
80.20 The cor. to secs. 23. 24. 25 & 26.
Land mountainous
Soil 2nd rate.
Timber. aspen & pines.
Heavy mountains & dens
undergrowth on 80. 20 chs.

BOOK-A-

Subdivis

Accu
Set t
grou
on W.
alon
Anasp
10 lks
Anasp
18. lks.
Set t
grou
mark
1 on E.
mou
Lan
Soil
Tim
Hea

BOOK-A-197

Subdivisions Tp. 26 S. R. 1 E.

North betw. secs. 23 and 24
Var. 16° 30' E.

Ascend

6.00 Set trachyte 12×8×6 in 8 in in the ground for 1/4 sec. cor. marked 1/4 on W. face & raised a stone mound alongside, from which
A aspen 4 in diam. bears N 50° E. 10 lks dist.
An aspen 2 in diam bears S. 15° W. 18 lks dist. both marked 1/4 S. B. T.

11.00 Set trachyte 26×18×10. 18 in in the ground for cor to secs. 13. 14. 23 & 24. marked with 3 notches on S. and 1 on E. edges. and raised a stone mound alongside.

Land. mountainous
Soil 2nd rate.
Timber. aspen
Heavy mountains on S & W.

Subdivisions Tp. 26 S. R. 1

East on random line
betw. secs. 13 and 24
Var. 16° 30' E.

40.00 Set temporary 1/4 sec. cor.

80.60 Intersect E. boundary of Tp.
21 lks. S. of cor. to secs. 13 & 24, from which Trees
S. 89° 51' W. on true line
betw. secs. 13 and 24
with same var.
Descend

30.00 Flat ridge bears N & S.

34.00 Diescend.

40.30 Set granite 20 x 8 x 4. 15 in in the ground for 1/4 sec. cor. marked 1/4 on N. face and raised a stone mound alongside.

64.00 Canyon 500 ft. deep drains S.

80.60 The cor. to secs. 13. 14. 23 & 24.
Land. mountainous
Soil 2nd rate.
Timber, aspen & pine
Heavy Mountains on 80.60
Aug. 21. A. 1883.

Note. On account of unavailable mou
Labandon survey N.

BOOK-A-19

Subdivis

Fron
the S.
me

Desc
Hollo
Roa
Holl
Set
the gr
1/4 on
mou
Roa
"
Holl
Set
the g
35 m
2 on
mou
Lan
Soi
Tim
He

Subdivisions Tp. 26 S. R. 1 E.

From the cor. to secs. 34 & 35 on the S. boundary of this tp. run

North betw. secs. 34 & 35.

Var. 16° 30' E.

8.00 Descend from bluff

8.00 Hollow drains N. W.

8.50 Road bears N. W. & S. E.

5.00 Hollow drains S. W.

4.00 Set granite 22×20×6 : 15 in in the ground for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside.

46.50 Road bears N. W. & S. E.

9.75 " " E. & W.

3.00 Hollow drains S. 10° E.

30.00 Set granite 30×30×20 : 20 in in the ground for cor. to secs. 26. 27. 34 & 35 marked with 1 notch on S. and 2 on E. edges and raised a stone mound alongside.

Land mountainous.

Soil 2nd rate.

Timber: scattering aspen & pine.

Heavy mountains on S. &

BOOK-A-19

Subdivisions Sec. 26 T. 8 R. 1

East on random line
betw. secs. 26 and 35.
Var. 16° 30' E.

40.00 Set temporary 1/4 sec. cor.

80.40 Intersect N. & S. line 29 lks. E.
of cor. to secs. 25. 26. 35 & 36. from
which Srun
S. 89° 48' W on true line
betw. secs. 26 and 35.
with same var.

40.00 Ascend

32.50 Ridge bears N. & S.

40.20 Set granite 12x12x12 ins in the
ground for 1/4 sec. cor. marked
on N. face & raised a stone mo
alongside.

80.40 The cor. to secs. 26. 27. 34 & 35.
Land. mountainous
Soil. 2nd rate.
Timber. scattering aspens.
Heavy mountains and
dense undergrowth an
80.40 chs.

Subdivisi

N

6.25 Hol
40.00 Mar
18x10-
cor.
rais
57.50 Ri
65.00 Ho
80.00 Set
in th
22.
2 no
rais
sid
La
So
Sa
Ye

BOOK-A-197

Subdivisions Tp. 26 S. R. 1 E.

North betw. secs. 26 and 27
Var. 16° 30' E.

16.25 Hollon draius W.

16.00 Marked stationary trachyte 24×18×10 in above ground for 1/4 sec. cor. marked 1/4 on W. face & raised a stone mound alongs.

57.50 Ridge bears E & W.

15.00 Hollon draius S. W.

16.00 Set a trachyte 18×12×8 in 12 in in the ground for cor. to secs. 22. 23. 26 & 27. marked with 2 notches on S & E. edges and raised a stone mound alongside.

Land mountainous.
Soil. 2nd rate.
Timber. scattering small aspen
Heavy Mountains on S & W.

Subdivisions Tp. 26 S. R 1

East on random line
betw. secs. 23 and 26
Var. 16° 30' E.

40.00 Set temporary 1/4 sec. cor.
80.80 Intersect N. & S. line 34 lks.
of cor. to secs. 23 & 26. from
which Trees
S. 89° 45' W. on true line
betw. secs. 23 & 26.
with same var.
34.50 Ridge bears N & S.
40.40 marked stationary trachyte
10 x 4 x 2 ft. above ground for 1/4
sec. cor. 1/4 on N. face and
a stone mound alongside.
80.80 The cor. to secs. 22. 23. 26. 27.
Land mountainous.
Soil 2nd rate.
Timber. small aspens.
Heavy Mountains on
80.80 chs.

BOOK-A-1

Subdivi

40.00 Set
gra
1/4 on
ma
40.00 Set
15 li
secs.
with
edge
mo
La
10.00
Se
Tr
He
C
40.00 Set
44.80 Tr
of c

S. R. Subdivisions Pp. 26 S. R. 1 E.

North betw. secs. 22 and 23
Var. 16° 30' E.

40.00 Set brachyte 10×10×6 in 6 cm in the ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.

40.00 Set petrified wood 20×10×6 in 15 cm in the ground for cor. to secs. 14. 15. 22 & 23 marked with 3 notches on S and 2 on E. edges and raised a stone mound alongside.

Land. mountainous about 10.000 feet above sea level.
Soil 2nd rate.
Timber. small aspen
Heavy Mountains on West.

East on random line
betw. secs. 14 and 23.
Var. 16° 30' E.

40.00 Set temp. 1/4 sec. cor.

40.30 Intersect N & S. line 36 lks W. of cor. to secs. 13. 14. 23 & 24. from

which Trun
N. 89° 54' W on true line
betw. secs. 14 and 23
with same var.

33.00 Low pine 20 ins diam.

40.15 Set volcanic rock 18×18×10 40.00
12 in in the ground for 1/4 sec
cor. marked 1/4 on N. face
and raised a stone mound
alongside. 4.00

80.30 The cor. to secs. 14. 15. 22 & 23. 40.00
Land. mountainous
Soil 2nd & 1st rate.
Timber. scattering small pine
Heavy mountains on. 80. 20
August 22/83.

Note.
On account of impassable
bluffs Salmon line N.

Subdivisions Tp. 26 S. R. 1 E.

From the cor. to secs. 33 & 34 on the S. boundary of this Tp. set by me I run

North betw. secs. 33 and 34.

Var. 16° 30' E.

Set trachyte 16 x 10 x 6 - 12 in the ground for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside.

Hollow drains S. Pf.

Set trachyte 18 x 12 x 8 - 12 in in the ground for cor. to secs. 27. 28. 33 & 34. marked with 1 notch on S. and 3 on E edges. and raised a stone mound alongside.

Land: broken table mountains

Soil 1 rate.

No timber.

Heavy mountains and dense artemisia undergrowth on 80 acs.

Subdivisions Tp. 26 S. R. 1 E.

	East on random line
	betw. secs. 27 and 34
	Var: 16° 30' E.
40.00	Set temporary 1/4 sec. cor.
80.60	Intersect W'g S. line 30 lks.
	S. of cor. to secs. 26. 27. 34 & 35.
	from which I run
	S. 89° 47. W. on true line
	betw. secs. 27 and 34
	with same var.
13.00	Small aspen grove.
26.00	Head of hollow drains S. E.
32.00	Road bears N. W'g S. E.
40.30	Set trachyte 14x12x6: g.s. in the ground for 1/4 sec. cor. marked 1/4 on N. face and raised a stone mound alongside.
80.60	The cor. to secs. 27. 28. 33 & 34
	Land. mountainous
	Soil 2nd rate.
	Timber. small scattering aspen
	Heavy mountains at 80.60

40.28 An
25.15 In
4.00 Se
g.s
1/4
m
40.00 Se
in
22.
on
ra
si
La
Jo
ho
H
4.00 Se
9.90 In

Subdivisions Sp. 26 T. R. 1 E.

North betw. secs. 27 and 28.
Var. 16° 30' E.

40.28 An aspen 30 in Diam.
35.15 In hollow drains W. road.
40.00 Set trachyte 20 x 6 x 6, 15 in in the ground for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside.
40.00 Set trachyte 26 x 12 x 5 in 18 in in the ground for cor. to secs. 21. 22. 27 & 28 marked with 2 notches on S and 3 on E edges, and raised a stone mound alongside.
Land very broken W. slope.
Soil 2nd rate.
No timber.
Heavy mountains on S & W.

East on random line
betw. secs. 22 and 27
Var. 16° 30' E.

40.00 Set temporary 1/4 sec. cor.
39.90 Intersect N. & S. line 18 lks S.

Subdivisions Tp. 26 S. R. 1

BOOK-A-

	S. of cor. to sec. 22. & 23. 26 & 27.
	from which Trees
	S. 89° 52' W. on true line.
	betw. secs. 22 & 27.
	with same cor.
15.00	Decease
39.95	Set trachyte 14 x 10 x 6 in. 9 in. in the ground for 1/4 sec. cor. marked 1/4 on N. face and raised a stone mound alongside.
56.00	Canyon 300 ft. deep drains S.
79.90	The cor. to secs. 21. 22. 27 & 28.
	Land. mountainous
	Soil 2nd rate.
	Timber small aspen
	Heavy mountains on 79.
	Aug. 23rd 1883.
	Note. On account of unavoid mountains I abandon furth survey of this Township.

and land

BOOK-A-197

Subdivisions Tp. 26. S. R. 1 E.

2

General Description.

The surveyed portion of this Tp. embraces a portion of the Main fish lake Mountains, and a nice flat lying in Secs. 25. 35 & 36. Said flat is suitable for cultivation. The mountains contain some good timber, though very scattering.

The applicants improvements consists of road making and a cabin, mostly all situated in the N E 1/4 of sec. 25. and the S.E. 1/4 of sec 24.

August 1883. A. G. Simon U.S. Deputy Surveyor.

Note. This Tp. is surveyed under part of the deposit made for Township 26 S. R. 2 E. by A. G. Allred — it being found at the time of survey that the land desired to embrace were situated partly in Tp. 26 S. R. 1 E. (Mr. Peter Anderson

who made the additional deposit, I found living in the Township. His improvements in S.E.¼ Sec. 24, consist of a log cabin, and some ditches and dams, constructed to make available a few acres of meadow land which lies only in this Township

August H. L. Farnsworth
U.S. Dep. Surv.

Note: The parenthetical part of last note was added July 21st 1884.

U. S. SURVEY

Salt Lak

The foreg

Township No.

Executed by

Under

day of

August

amined, the nec

the said field

hereby approved

BOOK-A-197

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah. November 5th 1883.
July 26, 1884

The foregoing field notes of the survey of the Subdivisions of the fractional

Township No. 26 South *Range No.* 1 East

Executed by Augustus D. Ferron

Under No 117 *contract of the* 5th

day of July *1883, in the month of* August *1883, having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

Ed Solomon

U. S. Surveyor General for Utah.

BOOK-A-197

REPORT: 1884.

Filed ..... September 18, 1883.

Examined by ..... James A Carter

Transcribed by ..... E.J.

Compared by ..... O.E.J. & L.W.H.

FIELD NOTES

OF THE SURVEY OF THE

South

boundary

OF

Township No 26 South

Range No 2 East

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Augustus D Ferron

U. S. Deputy Surveyor,

Under his Contract No. 117.

Dated ..... July 5th, 1883.

Survey commenced ..... August 16, 1883.

Survey completed ..... August 17, 1883.

BOOK-A-197 : 311

South Boundary Tp. 26 S. R. 2. E.

Survey commenced Aug 16/83
The instrument used is a
Gurley solar compass.
I commence at the cor. to Tps.
26 & 27 S. R 1 & 2 E. set by me
and run East on a random line
betw. said Tps.
The Var. of my compass being
16° 30' E.
I set temporary 1/2 mile & Mile cors
every 40 & 80 chs. and find the
Tp. line to be 5 miles & 51 chs. long
and the falling E be 21 lks. S.
of cor. to Tps. 26 & 27 S. R. 2 & 3
E. on the Fremont Valley Ente
Meridian established by Messrs.
Bailey & Burried in 1876.
The correction for my true line
will therefore be 3 1/2 lks. N. & 29 chs.
West per mile and its course
S. 89° 59' W.
Note. This connection being so
much "out" I took the pains
to look up thoroughly the discrepancy
First. I personally, with my
compassman Mr. G. Marshbank

South Boundary Tp. 26 S. R. 2 [illegible] South Bou

rechained the line from cor
to cor. and found it correct
I then ran the Range line
in township 26 S. R. 2 E. 80
E. and intersect the 5th Stan
Par. S. at about 1/2 the dis
of the "out". I then carefu
rechained several miles on th
Standard line and found the
all to be "short". ranging fro
2,00 to 3 Chains.
Having thus determined the
real state of the case I let
work stand, after making
the necessary correction of
my random line.—
From the cor. to Tp. 26 & 27 S. 00
R. 2 & 3 E. which is a Sandstone
stone 20"x14"x10", marked 6 notches on N.
& E. & Wedges with stone monument 4 ft bac
4 ft high — Bearing trees standing. — 6.50
Thence
N. 89° 59' W. on a true line 6.00
betw. secs. 1 & 36
Var. 16° 30' E.
40.00 Set petrified pine stone 24"x12"

20 ins
cor. m
a ston
Set
grou
36 m
5 on
Land
Soil
Cim
Hou

S.

Ente
Set
the g
1/4 on
mou
Leave
Ente
Set
the g
mar
edge

...l. R. 2 ...outh Boundary Tp. 26 S. R. 2 E.

...on cor
...orrect
...e line
...26 E. 1
...5th Stan
...the dist
...careful
...es on th
...ound the
...ing fro
...ed the
...e Set
...making
...tion of
...6. 00
...36 & 27 S. 00
...Trachyte
...lies on N.
...ns & 5 bas
...ning. — 6. 50
6. 00
...ne line 6. 00
...36
...E.
...24 x 12 x 6

20 ins in the ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

Set Granite 23 x 20 x 26 in 15 in in the ground for cor. to secs. 1. 2. 35 & 36 marked with 1 notch on E and 5 on W edges, and raised a stone mound alongside.

Land. mountains

Soil 2nd rate.

Timber. scattering pine & aspen Mountainous 80 Chs.

S. 89° 59' W. on true line betw. secs. 2 and 35.

Var. 16° 30' E.

Enter hollow drains S. E.

Set granite 30 x 30 x 6 in 20 ins in the ground for 1/4 sec. cor. marked 1/4 on N. face and raised a stone mound alongside.

Leave former hollow, ascend

Enter flat, sloping gently S. E.

Set granite 29 x 20 x 20 in 20 ins in the ground for cor. to secs. 2. 3. 34 & 35 marked with 2 notches on E & 4 on W. edges and raised a stone mound

South Boundary Tp. 26 S. R. South Bo

	along side.	
	Land. Mountains	
	Soil 2nd rate.	
	Timber. scattering pine & cedar	6.00
	Mountainous on 80 Chs.	9.00
	August 15/83.	0.00
	S. 89° 59' W on true line	
	betw. secs. 3 & 34	
	Var. 16° 30' E.	
1.00	Descend	
9.00	Gulch drains S.E.	
40.00	Set granite 20×20×8 in. 15 ins in	
	ground for 1/4 sec. cor. marked	
	1/4 on N. face and raised a stone	
	mound alongside.	
46.00	Enter hollow drains S.E.	
80.00	Set granite 22×20×12 in. 16 ins in	
	ground for cor. to secs. 3. 4. 33	
	marked with 3 notches on E & W	
	edges and raised a stone mound	
	alongside.	
	Land. mountains	
	Soil 2nd rate.	
	Timber. scattering cedars & pine	
	Mountainous on 80 Chs	

S. S

4.00	Ascen
9.00	Enter
0.00	Set
	the gr
	1/4 on
	moun
	On asp
	like dis
4.00	Desc
6.00	foot
2.50	Road
6.00	Hol
4.00	Set
	the g
	32 & 33
	Land
	stone
	Land
	Soil
	Timb
	Mou

BOOK-A-197

= 3151

6 S. R. South Boundary Tp. 26 S. R. 2 E.

S. 89° 59' W. on true line
between secs. 4 and 33
Var. 16° 30' E.

e & cedar 1.00 Ascend
Lks. 9.00 Enter flat top of hill
5/83. 0.00 Set granit 26 x 20 x 12 & 20 ins in
the ground for 1/4 sec. cor. marked
1/4 on N. face and raised a stone
mound alongside from which
an aspen 4 ins diam. bears N 45° W. 15
lks dist. marked 1/4 S. B. T.
4.00 Descend
15 ins in 6.00 foot of slope
marked 2.50 Road bears Rt & L
d a ston 6.00 Hollow drains L
1.00 Set trachyte 16 x 10 x 10 & 10 ins in
the ground for cor. to secs. 4. 5.
32 & 33 marked with 4 notches on
E and 2 on W edges and raised a
stone mound alongside.
Land. mountains.
Soil. 2nd rate.
Timber scattering pine & aspen
Mountainous on 80 lks

ne line
34
s.

16 ins in
s. 3. 4. 33
s on Eg
tone mo

pers & pin

316

South Boundary Dp. 26 S. R. 2 E.

S. 89° 59' W. on true line
betw. secs. 5 & 32
Var. 16° 30' E.

35.00 Hollow drains NE.

40.00 Set trachyte 16×10×10in 12in in the ground for 1/4 sec. cor. mar 1/4 on N. face and raised a stone mound alongside.

51.00 Ridge bears N W & S E.

76.00 Hollow drains S. E.

80.00 On ridge bears N W & S E. marked stationary trachyte 36×36×36in. above ground, with 5 notches on E and 1 on edges for cor to secs. 5. 6. 31 & 32 and raised a stone mound alongside.

Land. Mountains.
Soil. 2nd rate.
Timber. scattering pines & aspen
Mountainous 80 chs.

4.00 Enter
4.00 Desc
7.00 Hollow
1.50
7.50 Desc
16.00 Set
in the
mar
a sto
Holl
1.00
51.00 The c
Lan
Soi
Tim

Mou

Note
For
sec
town
Range

BOOK-A-197

South Boundary Tp. 26 S. R. 2 E.

S. 89° 59' W. on true line
Meas. recs. 6 & 31
Var. 16° 30' E.

4.00 Enter flat ridge
Recess from flat
7.00 Hollow drains S. ascend.
Flat ridge bears
N. & S.
7.50 Recess from same
10.00 Set trachyte 14 x 7 x 6 in. 10 in.
in the ground for 1/4 sec. cor.
marked 1/4 on N. face and drains
a stone mound alongside.
1.00 Hollow drains S.
51.00 The cor. to Tps. 26 & 27 S. R. 1 & 2 E.
Land mountainous.
Soil 2nd. rate.
Timber scattering cedars,
pine & aspen.
Mountainous on S. Bdy.

August 17/83.

Note

For general description
see Subdivisions of this
Township.

Respectfully D. Ferron
U. S. Dep. Surv.

BOOK-A-197

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, November 5th *1883.*

The foregoing field notes of the survey of the South boundary

Township No. 16 South *Range No.* 2 East

Executed by Augustus G. Ferron

Under No 117 *contract of the* 5th

day of July *1883, in the month of* August *1883, having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

Edw Solomon

U. S. Surveyor General for Utah.

REPORT: 1884

BOOK-A-197

Filed September 28 1883

Examined by John A Campbell

Transcribed by William Koeber

Compared by C.E.S. & L.W.H.C.

FIELD NOTES

OF THE SURVEY OF THE

Subdivisions

And

Meanders of Fish Lake

OF

Township No 26 South

Range No 2 East

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Augustus D. Farrow

U. S. Deputy Surveyor,

Under his Contract No. 117

Dated July 5th, 1883.

Survey commenced August 24, 1883.

Survey completed September 1 1883.

V

BOOK-A-197

Township 26 South R. 2 East



BOOK-A-197

Subdivisions Tp. 26 S. R. 2. E.

Survey commenced Aug 24/83
with a Gurley Solar compass.
Note. The eastern part of this Tp.
is unavailable on account being
so far from water, and is on that
account not surveyed.
Therefore from the cor. to secs. 32 & 33
33 on the S. boundary of this Tp.
formerly set by me I run
North betw. secs. 32 and 33
Var. 16° 30' E.

9.00 Enter aspens
4.00 Hollow drains N. E.
4.00 Ridge bears E & W.
5.00 Hollow dr. S. 80° E. leave timber
ascend
8.30 Road bears N W & S. E.
1.00 Set trachyte 28×18×10 : 20 in the
ground for 1/4 sec. cor. marked 1/4
on W. face and raised a stone
mound alongside.
4.00 Enter Table Mountains, aspen & pines
5.00 Descend into deep canyon
1.00 Set a trachyte 14×10×8 : 9 in the
ground for cor. to secs. 28. 29. 32 & 33 marked
with 1 notch on S. and 4 on E. edges.

Subdivisions Tp. 26 S. R. 2 E. Subdivis

and raised a stone mound Sour 1.00 Enter
from which leave
An aspen 4 ins diam bears N. 70° E. 6 lks d 1.00 Set
marked T. 26 S. R. 2 E. S. 28 B. T. for co
An aspen 4 ins diam bears N. 40° W. 5 lks. dis with
marked T. 26. S. R. 2 E. S. 29 B. T. raised
An aspen 5 ins. diam bears S. 60° W. 12 lks. d Lacu
marked T. 26. S. R. 2 E. S. 32. B. T. Soil
Land. Mountainous Timb
Soil 3rd rate. Moun
Timber, aspen & pine. un
Mountainous & dense
undergrowth on 80 chs.

4.50 Dear

North betw. secs. 28 and 29 2.50 Ledg
Var. 16° 30' E. 2.00 On st

17.00 Carry on 500 ft. deep drains E. 15 5 ins di
then S. E. and ra

40.00 Set trachyte 16 x 10 x 10 ins 12 ins in the side
ground for 1/4 sec. cor. marked 1/4 Abalsam
W. face and raised a stone mound distan
alongside from which 4.50 On S.
An aspen 16 ins diam. bears S. 50° E. 32 lks statio
marked 1/4 S. B. T. groun

45.00 Carry on 500 ft deep drains S. E. secs. 2

BOOK-A-197 — 320

R. 2 ... subdivisions Sp. 26 S. R. 2 E.

Enter rolling, plateau Lake ridge, leave timber, a gap in plateau 15 chs W.

Set trachyte 16×9×5 in 12 in in the ground for cor. to secs. 20. 21. 28, 29 marked with 2 notches on S. and 4 on E. edges, & raised a stone mound alongside.

Land. Mountainous.

Soil 2nd rate.

Timber. Aspen & pine.

Mountainous & dense undergrowth on 80 chs.

North betw. secs. 20 and 21 Var. 16° 30' E.

Descend from "Lake ridge"

Ledge croppings 50 ft. high.

On steep slope, marked an aspen 5 ins diam. for 1/4 sec. cor. ~~4~~ on W. face and raised a stone mound alongside from which

a balsam 6 in diam bears N. 30° W. 10 lks. distant marked 1/4 S. B. T.

On S. E. of Fishlake, marked stationary trachyte 5×2×1 ft. above ground for Meander Cor. to fractional secs. 20 & 21 ~~X~~ M. C. and raised a

stone mound alongside.
Land. Mountainous.
Soil. 3rd rate.
Timber. Pines & aspens
Heavy Mountains on 64 chs.
Aug 24/8 .00

From the cor. to secs. 20 & 2
28 & 29
West on true line
betw. secs. 20 and 29 .50
Var 16° 30' E. .00

15.00 Decr.
*56.75 Set trachyte 15x10x6 in. 10 in in the ground for. Meander Cor. to fractional secs. 20 & 29, marked M. C and raised stone mound alongsi
Land. Mountainous
Soil 3 rate.
Timber. cedar & pines
Mountainous & dense
under growth on 56.75 ch

*40.00 Set trachyte 12x8x6 in. 8 in. in the ground, f
1/4 sec. cor. marked 1/4 on N. face & raise
a stone mound alongside.

From
on S.
me

Asce
Marke
3 x 1 fe
1/4 on
mou
No tr
Ente
Set
the g
mar
edges
along
in asp
dist.
All the
& ide
Lan
Soil
Tim
Hea
de

Subdivisions Tp. 26 S. R 2 E.

From the cor. to secs. 31 and 32
on S. boundary of Tp. set by
me Run North between secs. 31 & 32
Var. 16° 30' E.
Ascend in scattering pines.
Marked stationary trachyte, 4x
3x1 ft. above ground for 1/4 sec.
1/4 on W. face and raised a stone
mound alongside.
No trees within limits.
Enter aspen plateau
Set trachyte 24x20x8 in 15 ins in
the ground for cor. to secs. 29. 30. 31 & 32
marked with 1 notch on S and 5 on E.
edges and raised a stone mound
alongside. from which
An aspen 6 ins diam bears S. 70° E. 50 lks
dist. marked T. 26. S. R. 2. E. S 32. B.T.
All the other trees in limits are burned
& dead.
Land Mountainous
Soil 3rd rate.
Timber: aspen (dead).
Heavy Mountainous and
dense undergrowth on both.

Subdivisions Sp. 26 S. R.

East on random line
between secs. 29 and 32.
Var. 16° 30' E.

40.00 Set temporary 1/4 sec. cor.
79.80 Intersect N. & S. line, 22 lks.
of cor. to secs. 29 & 32. from which
I run
N. 89° 51' W. on true line
between secs. 29 and 32
with same va.
Ascend.
19.00 Enter rolling plateau
39.90 Set sandstone 11 x 11 x 6 in 6 in.
the ground for 1/4 sec. cor. mark
1/4 on N. face and raised a stone
mound alongside.
65.00 Gulch drains S. E.
79.80 Pre. cor. to secs. 29. 30. 31 & 32.
Land. Mountainous.
Soil. 2nd rate.
Timber, pines & aspens.
Mountainous and
dense undergrowth on 79.

BOOK-A-

Subdivis

We

1.00 Steep
chs. th
42 lk
on W.
ine to
The c
1.40 Inte
of co
whi
N.

1.40 The
is
9.00 Gul
1.40 The
Lan
Soi
Tim

Heav
Un

Subdivisions Tp. 26 S. R. 2 E.

West on random line
betw. secs. 30 and 31
Var. 16° 30' E.

4.00 Steep rocky descent, offset S. 17.10 chs. thence W. 27.40 chs. to a point 42 lks. N. of W. C. to secs. 30 & 31 on W. boundary of Tp. set by me 18 chs. S. of true corner point. The connection will therefore be.

1.40 Intersect W. B. of Tp. 42 lks N. of cor. point to secs. 30 & 31 from which I run

N. 89° 32' E. on true line
betw. secs. 30 and 31
with same var.

1.40 The 1/4 sec. cor. point is inaccessible is not set.

9.00 Gulch drains S. W.

1.40 The cor to secs. 29. 30. 31 and 32.

Land. Mountainous
Soil 2nd rate
Timber. aspen & pine.

Heavy Mountains & dense
undergrowth on 57.40 chs.

Subdivisions Tp. 26 S. R 2

Subdivisi

North betro. secs 29 and 30

Var. 16° 30' E.

35.00 Deccend into fishlake basi

40.00 Set trachyte 24×24×6 in 18 in
the ground for 1/4 sec. cor. mark 3.00
1/4 on W. face and raised a ston
mound alongside.

60.60 Edge of Fish Lake set trach
26×18×10 in 18 in the ground for
Meander Cor. to fractional secs. 2
30. marked M. C. and raise
a stone mound alongside.
Land Mountainous.
Soil 3 rate
Timber pines & aspens.
Mountainous and dens
undergrowth on 60.60 ch Note: To comp

Note. The cor. secs. 19. 20. 29. &
fallsin ishlake. - there
from the cor. to secs. 19 & 30 on West
boundary of Tp. set by me, Sur
East on true line
betro. secs. 19 and 30.
Var. 16° 30' E.

10.80 Allowing for convergency set

trach
for
N. fa
mou
Edge
24×
mea
secs.
and
alon
Lan
Soil
No t
Dec

secs.
Mea
fou
Fish

61.12 Chs.

Subdivisions Ph. 26 S. R 2 E.

trachyte 10×10×6 in. 6 in. in the ground for 1/4 sec. cor. marked 1/4 on N. face and raised a stone mound along side.

3.00 Edge of fishlake, set trachyte 24×14×10 in. 18 in. in the ground for meander cor. to fractional secs. 19 & 30 marked M. C. and raised a stone mound alongside.

Land. Level valley
Soil 1st rate
No timber.
Dense artemisia undergrowth

on 13.00 chs.
Aug. 25th 1883.

Note: To comply with Manual of Instructions —
From Meander cor. to fract. secs. 19 & 30 Triangulate to the Meander cor. betw. secs. 20 & 29. and find the distance ~~to be~~ across Fishlake, to be
91.12 chs. and the course N. 89° 42' E.

Subdivisions Tp. 26 S. R. 2

Note: the cor. to secs. 17, 18, 19 & 20 falls in Fish Lake, therefo from the cor. to secs. 18 & 19 on W. boundary of Tp. set by me Thence

East on true line betw. secs. 18 and 19 Var. 16° 30' E.

Descend

10.60 Allowing for convergency set trachyte 10 x 9 x 8 in. 7 in. in the gr for 1/4 sec. cor. marked 1/4 on N. face and raised a stone mou along side.

33.75 Road bears N E & S W. N. W. edge of fish lake set tra 16 x 12 x 5 in. 10 ins. in the ground f meander cor. to fractional secs 18 & 19. marked M. C. and raised a stone mound alon side from which

An aspen 14 ins. diam bears N. 80 W. 30 lks. d marked T. 26 S. R 2 E. S. 18 M C. B. T.

An aspen 4 ins diam bears S. 60 W. 19 lks. d marked T. 26 S. R 2. E. S. 19 M C B. T.

Land, mountainous

Subdivisi

So
Sur
Mon
un

Note
betw
flag
Nor
from
back
29 3
116.
Nor
secs.
poin
Ther
bear
grou
to fr
M. C
alon
An aspe
distan

Subdivisions Tp. 26 S. R 2 E.

Soil 3rd rate.
Timber, aspens & pines
Mountainous and dense
undergrowth on 33.75 chs.

Note. From the Meander cor.
betw. secs. 29 and 30, I have a
flag set on edge of fishlake
North. To comply with manual of instructions
from said flag Triangulate
back to meander cor. betw. secs.
29 & 30. and make the distance
116.90 chs. which is 17.50. chs.
North of the corner point to
secs. 17. 18. 19 & 20, which cor.
point falls in fishlake.
There marked a trachyte
boulder 36 x 30 x 30 ins above the
ground for meander cor.
to fractional secs. 17 & 18. with
M. C. and raised a stone mound
alongside, from which
an aspen 12 ins diam bears N 17° E. 20 lks
distant marked M. C. sec. 17. B. T.

Subdivisions Sp. 26 S. R. 2E

Subdivisi

From M. C. 17.50 lks. N. of corn
point to secs. 17. 18. 19 & 20 T. run
North betw. secs. 17 and 18.
Var. 16° 30' E.

1.00 Spring branch 3 lks. wide 4
deep runs S. E.

5.50 Small aspen grove.

12.00 Road bears E & S. W.

20.00 Forked pine 20 ins diam. on S for
of Twin Creek 20 lks. wide 10 in
deep runs E.

20.50 N. fork Twin creek 10 lks wide
deep runs E.

27.50 Small aspen grove.

42.50 Set granite 20 x 14 x 6 in. 15 in. in th
ground for 1/4 sec. cor. marked 1/
on W. face and raised a stone mo
alongside.

28.40 A boulder 8 ft. diam.

62.50 Set a trachyte 16 x 12 x 8 in. 10 in. in
ground for cor. to secs. 7. 8. 17 & 18
marked with 4 notches on S. an
E. on E. edges and raised a ston
mound alongside, from wh
An aspen 4 ins diam. N 50° W. 17 lks. dist
marked S. 26. S. R. 2 E. S. 7. 8. T.

A pine 5
marked
Land
Soil
Timbe
Mounta

Note:
S. 9. 16 &
Therefo
7. 8. 17 &
Eas
be

Leave
Small
trachyt
for 1/4
face a
along
An aspe
"
both s
Road

Subdivisions Sp. 26 S. R 2 E.

Spruce 5 ins diam bears S. 10° E. 22 lks dist.
marked T. 26. S. R. 2 E. S. 17. B. T.
Land S. E. slope of mountain.
Soil 2nd rate.
Timber. pines & aspen
Mountainous & dense undergrowth.
on 62.50 chs.
August 27/83

Note: The corner point to secs.
S. 9. 16 & 17 falls in his blake.
Therefore from the cor. to secs.
T. 8. 17 & 18 S run
East on true line
betw. secs. 8 and 17
Var. 16° 30' E.
Leave timber.
In small grove of aspen set
trachyte 16 x 12 x 10, 12 ins in the ground
for 1/4 sec. cor. marked 1/4 on E.
face and raised a stone mound
alongside, from which
An aspen 4 ins diam bears N. 30 W. 8 lks dist
" " 2 " " " S. 40 E 7 " "
both marked 1/4 S. B. T.
Road bears N E & S W.

Subdivisions Tp. 26 S. R. 2 E.

53.80 On N. W. edge of Fish Lake set trachyte 18×12×12 in in the ground for Meander cor. to fractional secs. 8 & 17 marked 1/4 C. and raised a stone mound alongside from which an aspen 8 ins diam bears S. 54 1/2° W. 50 lks. dist. marked T. 26 S. R. 2 E. S 17 1/4 C. B.

Land. Mountainous

Soil 2nd rate. 8.00

Timber. Pine & aspen. 9.00

Heavy mountains & dense undergrowth on 53.80 ac.

To comply with Manual of Instructions 9.00

Note: From the Meander cor. to fractional secs. 20 & 21 I cause 9.00 a flag to be set North across fish lake. From said flag I triangulate to the said M. C. to fractional secs. 20 & 21 and find the distance to be 117 lks. being 21 lks. E. of corner point to secs. 8. 9. 16 & 17 where I set trachyte 16×8×7 1/2 in in the ground, for meander cor to fractional sec

8 & 9 m
stone

From
of cor.

Ascen
Road
Set t
grou
1/4 on
mou
Ridg
Desce
Set t
grou
mark
on E
mou
an aspe
mark
an aspe
mark

Subdivisions Tp. 26 S. R. 2 E.

S. 9. marked M. C. and raised a stone mound alongside.

From the meander cor. 2 chs. N. of cor. to secs. 8. 9. 16 & 17 T. 26 S. R. 2 E.
North betw. secs. 8 & 9
Var. 16° 30' E.

Ascend
Road bears N. E. & S. W.
Set trachyte 16 x 10 x 8 in. in the ground for 1/4 sec. cor. marked 1/4 on W. face & raised a stone mound alongside.
Ridge bears N 60° W. & S. 60° E.
Descend.
Set trachyte 16 x 10 x 10 - 12 in. in the ground for cor. to secs. 4. 5. 8 & 9. marked with 5 notches on East 4 on Edges and raised a stone mound alongside, from which an aspen 4 in. diam. bears N. 30° W. 13 lks. dist. marked T. 26. S. R. 2 E. S. 5. B. T.
An aspen 3 in. diam. bears S. 55° E. 19 lks. dist. marked T. 26. S. R. 2 E. S. 9. B. T.

BOOK-A-197

Land mountainous.
Soil 1st. rate.
Timber, pine & cedars
Heavy Mountains and dens
undergrowth on 5 & chs.
Aug 28/83.

Note. The cor. to secs. 3. 4. 9. & 10. n
being established in regular
course from S. boundary.
Therefore from cor. to secs. 4. 5
& 9. I run
East on true line
betw. secs. 4 and 9
Var. 16° 30 E. in 1883

6.20 Creek bed, dry draining E. 70°
32.50 Leave aspen, thence in thick br
40.00 Set trachyte 16 x 12 x 10. 12 ins
the ground for 1/4 sec. cor.
marked 1/4 on N. face
and raised stone mound
alongside.
67.00 Old Road bears N. & S. & enter
artemisia flat.
80.00 Set trachyte 10 x 10 x 6 ins in 5 m

in the
3. 4. 9.
on S
raise
along
Land
Soil
Timb
Mou
Den

Note.
follo
tabli
to sec

8.00 Roa
9.50 N.
Trach
for
secs.
rais
alon

in the ground for cor. to secs. 3. 4. 9 & 10. marked with 5 notches on S and 3 on E. edges and raised a stone mound alongside.
Land. Mountainous & flat
Soil 2nd rate.
Timber, small aspen & pine
Mountainous on 6 chs.
Dense undergrowth, 13 "
Total. 80 chs.

Note. The cor. to secs. 9. 10. 15 & 16 falling in Lake is not established therefore from cor. to secs. 3. 4. 9 & 10 Run South between secs. 9 and 10.
Var. 16° 30' E.

8.00 Road bears S.E. & S.W.
9.50 N.W. edge of Fish lake set Trachyte 12 x 8 x 6. 8 in in the ground for meander cor to fractional secs. 9 & 10 marked M. C. & raised a stone mound alongside.

Subdivisions of Sec. 26. T. 2 R. 2

Land. Level
Soil 1st rate.
No timber.
Dense artemisia undergrowth
on 39.50 chs.

Note: The cor. to secs. 2. 3. 10 & 11
not being set. Run from
cor. to secs. 3. 4. 9 & 10
East on true line
betn. secs. 3 & 10.
Var. 16° 30' E

4.25 Road bears N & S.
9.50 Edge of fish lake set trachy.
11 x 8 x 6. in the ground for N. cor. to fractional secs. 3 & 10 marked 1/4. C. and raised a stone mound alongside. then triangulate across lake & find distance to be 27.90 chs. therefore at.
37.40 On E. side of Lake marked stationary trachyte 15 x 6 x with a cross (+) 2 ft. above ground 1/4. C. for meander cor to fractional sec 3 & 10 and raised a stone mound

40.00 Set a Stone marked S 1/4 and

Set 4 x 4 x 2.3.10 x 11 a Mound of Land

Soil

Mountain

North

Set a Stone marked 1/4 Cor. Sec. 3 & 10 Bears N. 53.00 Distance 42.35 to Pin. 3 marked S Stone mound where Set for Cor 6 Notches Stone mound Land Timber Mountain

BOOK-A-197

336

S. R. 2 Subdivisions 5, 26 S., R. 2 E.

40.00 Set a Trachyte 10×10×6, 6 in. in the ground for 1/4 Sec. cor. marked 1/4 on N. Jaw, and raised stone mound alongside stand Hesp Mountain SE

Set a Trachyte 11×9×6 min 6 in. in the ground for cor to Secs 2. 3. 10 & 11, marked 5 Notches on S. & 2 on E. edges, and raised a stone mound alongside.

Land Mountains & timber;

Soil 3rd & 4th rate;

Timber some aspen & pine on E. 1/2,

Mountainous, & dense undergrowth on 53.10 chs

North on true line Mar. Dec. 29 1/2 E.

Var 16° 30' E.

40.00 Set Trachyte 11×10×5, 6 in. in the ground for 1/4 Sec. cor. marked 1/4 on W. Jaw, and raised a stone mound alongside

53.00 Gulch drains S.W.

42.35 Enters at 5th Stand Par. L, 50 lks W. of Stand. Cor to Secs. 34 & 35, which is a Trachyte 16×10×8. Jointly set marked S.C. & 6 Notches on E. 4 on W. & 2 on E. edges with stone mound alongside, 2 Bearing trees standing. whence Set a Trachyte 10×9×8, 6 in. in the ground for closing Cor to Secs. 2 & 3. marked C.C. and 6 Notches on E. 4 on W. & 2 on E. edges and raised a stone mound alongside.

Land Hesp W. Slope, Soil 3rd rate;

Timber, burnt pine & aspen;

Mountainous & dense undergrowth on 73.35 chs

Subdivisions Sec. 26. T. 2 E.

Section line East bet Secs 25 & 26.
On 26. 30. C.

19.00 Road bears N.W. & S.E.

26.50 Edge of Lake, Set Trachyte 12x12x10, 8on in ground for meander Cor. to Grad. Sec. 25 & 26. 40. —
marked M. C. raised a stone mound alongside
Thence Triangulate across bay in Lake and pro
distance to be 40.25 chs. which makes

66.75 To Edge of Lake, Set Trachyte 12x12x10, 8on 13.20
in the ground for meander cor to grad. Sec.
marked M. C. and raised a stone mound alongside

72.25 N. side of road bears N.E. & S.W. Intersect 50
Stand. Bar. L. 2.00 chs W. of Standard to Sec 35
which is a Trachyte 10x10x18, setting Set mo
L.C. & 6 Witness mound E. & W. edge with Stone mo
on top Set a Trachyte 12x12x24, Scribed in the grou
for closing cor to Sec 25 & 26, marked C.
& Notches on E. & W. sides, and raise
a Stone mound alongside.
Level, mostly all level,
Soil, red rock,
No Timber
Some artemisia & Willow & Dogwo
on 32.00 chs.

August 29/83.

Subdivi
Nor
Dep
N.E.
Set
Set
an
bdi
Sne
chi
which
Set m
alon
on L
L.C.
Whe
bin,
to
on
and
bdi
Sou
Mounta
73.

Subdivisions T. 26 S. R 2 E.

North on true line last Sec. 4 & 5
Var 16° 30' E.

4.70 Dry bed of Creek in Cañon chains
N.E. across on Broken Mountain Slope
Set Trachyte 14 x 12 x 10 Ins in the ground
for Sec Cor. marked 1/4 on E. face,
and raised a Stone mound along-
side.

73.20 Intersect S. & Stand. Par. L. 5.50
chs W. of Stand. Cor. to Sec. 32 & 33.
which is a Trachyte 14 x 10 x 4 Ins. long
Set in the ground & Stone mound
alongside marked with 4 notches
on E. 2 on W. & 6 on N. edges and
I. C. — 3 bearing trees Standing,
Brass Capped Trachyte 16 x 10 x 8 Ins.
Ins. in the ground for closing Cor
to Sec 4 & 5, marked 4 notches
on E. 2 on W. & 6 on N. edges I. C.
and raised a Stone mound along
side. —

Land Mountainous,
Soil Sandy,
Timber Small aspen,
Mountain on & along meridian
73.20 chs. —

Subdivisions R.230., & 2 C.

Meande

Fr. with the cor.t Sec.r 7. 8. 17 & 18 Surv.
Weston random line last Sec.r 7 & 1
var 16° 30' E.

40.00	Set Temp. 1/4 Sec. cor.	
50.60	Intersect N. boundary of 9 ps, at cor.t Sec.r 7 & 18, previously set by me from which Surv.r East on true line last Sec.r 7 & 18 with same var.	40 3/4 W.
3.50	Enter burnt Timber	39 3/4 W.
10.60	Set Trachyte 18×12×10, 12 in. in ground for 1/4 Sec cor. marked 1/4 on N. face, and raised a stone mound alongside,	35 W. 39 1/2 W. 48 1/2 W.
20.00	Intersect from Mountain	37 1/2 W.
24.00	Descend from ledge 50 ps high	50 W
30.60	" " " " " "	
50.60	Cor.r to Sec.s 7. 8. 17 & 18. Land, Mountainous, Soil 2nd rate, Timber pine & aspen mostly burnt Mountainous & down and gorse on 50.60 chs.	

August 30 & 1883.

50° W.
48 1/4° W.
54° W.

Me
Sur
var
con
frac
Sr

Lan
Soi
Tim
Sr

BOOK-A-197 = 340

Meanders Tp. 26 S. R. 2 E.

Meanders of fishlake Tp. 26 S. R 2 E.
Survey commenced Aug. 30 1883
with a Gurleys improved Solar
compass at the meander cor to
fractional secs. 20 & 21.
Thence S run with meanders
in sec. 20.
Var: 16° 30' E.

40 3/4 W.	11.40 chs.	
39 3/4 W.	8.39	"
35 W.	19.30	"
39 1/2 W.	19.50	"
48 1/2 W.	9.20	"
37 1/2 W.	3.70	"
50 W	14.00	" to meander cor fractional secs. 20 & 29.

Land. Foot of steep slope
Soil. 2nd. rate.
Timber. Aspens & pines.
Dense underg rowth 85.49 chs

Thence in sec. 29.
Var: 16° 30' E.

50° W.	5.20 chs.	
48 1/4° W.	14.00	"
54° W.	5.60	"

Meanders Sec. 26. T. R. 2 E.

S. 44¼° W.	1.60 chs.
S. 53¾ W.	4.40 " To meander cor. to fractions secs. 29 & 30.
	Land: bottom & steep slope
	Soil. 2nd rate.
	Timber. aspens & pine.
	Dense undergrowth on 30. 80

Fence in sec. 30.
Var. 16° 30' E.

S. 70° W.	9.50 chs. ✓
S. 52° W.	3.70 " ✓
S. 23° W.	2.30 " ✓
S. 44° W.	6.75 " ✓
S. 22½° W.	2.75 " ✓
S 50¼ W.	4.25 " ✓
S 45° W.	6.00 " ✓
S. 67° W.	2.70 " ✓
S. 71¼° W.	6.00 " ✓
S. 81½ W.	5.00 ✓ " To a point R. H. Thompson's cabin bears S 63°
N. 70° W.	8.50 ✓ " Enter meadow, runs back 4 chs. To a point-Pane cabin bears S 11½° E
N. 57° W	4.40 "
N. 26° E.	14.00 ✓ " at 2.00 chs enter Slough at head of Lake
	" " 6.00 " leave Lake.
N. 68½° E.	0.75 ✓ "
N 24¾ E.	2.00 ✓

BOOK A-3

Mean

6¾ E.
19¾ E.
6° E.
26¼° E.
6¼° E.

La

So

Tim

BOOK A-197 = 342

Meanders Sp. 26. T. R 2E

6 3/4 E.	3.00 chs. ✓
19 3/4 E.	7.00 " ✓
6° E.	2.61 " ✓
26 1/4° E.	2.63 " ✓ Leave meadow
6 1/4° E.	10.10 " ✓ To meander cor. to fractional secs. 19 & 30.

Land. foot of mountains. and meadow.

Soil: 1st. and 2nd rate.

Timber, some pines & aspens

Dense underbrush

on 53.45 chs.

August 30 A 1883

Meanders. Tp. 26 S. R 2 E.

Fence in sec. 19.
Var. 16° 30 E.

N. 2¼ E.	13.25 chs.	
N. 6¾° W.	6.90 "	
N. 20¼° W.	5.00 "	
N. 38½° W.	7.25 "	
N. 31½° W.	6.00 "	
N. 14½° W.	5.10 "	At. 3.10. Road. At. 3.30, creek, & enter timb
N. 19° E.	5.80 "	
N. 30¼° E.	5.50 "	
N. 46¾° E.	12.72 "	
N. 71° E.	6.00 "	
N. 41½° E.	5.82 "	
N. 64½° E.	2.14 "	
N. 7¼° E.	2.58 "	
N. 24¾ E.	6.50 "	
N. 40° E.	3.50 "	
N. 26° E.	1.83 "	To meander cor to fractional secs. 18 & 19

Land level brush
Soil 1st rate.
Timber, aspens & pines on 52.3

Deuse undergrowth on 95.

35½° E.	4
45° E.	20
52° E.	8.
42½° E.	8.
63¾° E.	6.
17¾° E.	6.
8¼° E.	2.
48° E.	5.
45° E.	5.
42° E.	9.

BOOK-A-197

344

R. 2 E. Meanders Tp. 26 S. R. 2 E.

Thence in Sec. 18.

Var. 16° 30' E.

35½° E. ✓ 4.00 chs. To a rock in edge of water fractional

45° E. ✓ 20.00 " To meander cor of secs.

17, 18.

Land bottom of slope

Soil. 1st rate.

Timber aspens.

Dense undergrowth on 24.00 chs.

Thence in Sec. 17

Var. 16° 30' E.

52° E. ✓ 8.00 chs. At 1.75 Mouth of small creek

" 4.50. " " " "

" 7.00. " " " "

42½° E. ✓ 8.40 " "

63¾° E. ✓ 6.75 ✓ " At 0.75 Mouth of creek

" 4.50 " " South Twin creek

Allred cabin bears W. 37½° W.

" 6.75 same " " W. 61° W.

mouth of North Twin Creek

17¾° E. ✓ 6.00 ✓ " At 3.50 Wagon road leaves Lake

8¼° E. ✓ 2.75 ✓ "

48° E. 5.25 "

45° E. 5.50 "

42° E. 9.80 "

Meanders Tp. 26. S. R. 2 E.

BOOK-A-19

Meander

N. 44¾° E.	10.00 chs.	
N. 24¾° E.	5.70 "	
N. 45¾° E.	2.17 "	
N. 22½° E.	7.00 "	
N. 40 E.	6.15 "	To meander cor. to fracl. secs. 8 & 17.

Land. bottom of slope
Soil 1st rate.
Timber. Some aspens.
Dense undergrowth on 83.50

Thence in Sec. 8.
Var. 16° 30' E.

N. 65½° E.	14.00 chs.	
N. 61¼° E.	8.00 "	
N. 29 E.	13.00 "	To meander cor. to fractional secs. 8 & 9.

Land. gentle S. E. slope.
Soil. 1st rate.
Timber. Some aspens
Dense undergrowth on 35.

Meander

43° E.	10.
ast	15.
78¼° E.	17.
84½° E	11.
75½° E.	11.
65½° E.	9
45¾° E.	14

Lan
Soi
Tim
D

73½° E. 15.
46¼° E. 4.
34¼° E. 4.
11° W. 10.
23½° W. 4.
86° W. 11.
15° E. 6.
19° E. 8.

BOOK-A-197

346

R. 2 E. Meanders Tp. 26 S. R. 2 E.

Thence in Sec. 9.
Var. 16° 30' E.

43° E. 10.00 chs. to Bowery, leave timber
East 15.00 "
to fracl. 78¼° E. 17.60 "
84½° E 11.50 "
75½° E. 11.50 "
65½° E. 9.00 "
45¾° E. 14.00 " Enter meadow, to meander
on 83.50 cor. to fractional secs. 9 & 10.
Land. mostly artemisia flat.
Soil. 1st rate.
Timber. aspens on 10 chs.
Dense undergrowth on 83.50 chs.

Thence in Sec. 10
Var. 16° 30' E.

to fractions
73½° E. 15.20 chs.
46¼° E. 4.00 "
34¼° E. 4.50 "
Lon 35. 11° W. 10.00 "
43½° W. 4.50 "
86° W. 11.00 "
15° E. 6.00 "
19° E. 8.00 " Leave meadow to

Meanders Tp. 26 S. R. 2 E.

	meander cor. to fractional secs. 3 & 10.	30 3/4° W. 14
		38 1/2° E. 2
	Land. mostly meadow.	
	Soil. 1st rate.	
	No timber.	
	August 31st 1883	
	Fence Sec. 3.	
	Var. 16° 30' E.	
North	4.00 chs.	
N. 24° E.	3.90 "	
N. 18 1/2° W.	12.00 "	
N. 36 1/2° W.	7.25 "	
N. 53 1/2° W.	3.00 " to meander cor. to fractional secs. 3 & 4.	41 1/2° E. 15.
	Land. level	41 1/2° E. 35.
	Soil. 1st rate	27 1/2° E. 4.
	No timber.	29° W. 1.
	Dense undergrowth on 30.1	26 1/2° W. 2.
		41° W. 3.
		23 1/2° W. 2.
	Fence Sec. 4	19 3/4° W. 4.
	Var. 16° 30' E	34 1/2° W. 4.
N. 53 1/2 W.	9.00 chs.	18 1/2° W. 3.
N. 69 1/2 W.	3.00 "	4 1/2° W. 2.

BOOK A-197

348

R. 2 E. Meanders Tp. 26 S. R. 2 E.

al secs.

low.

ed 1883

to fract'l

on 30.10

30 3/4° W. 14.00 chs.

38 1/2° E. 28.00 " Borgendon's ranch bears N. 25° 30' E. 3 Enter meadow, i. meander cor. to fractional secs. 3 & 4.

Land. level.
Soil. Sandy
No timber
Dense undergrowth on 54.50 chs.

Thence Sec. 3.
Var. 16° 30' E.

12.00 chs.

71 1/2° E. 15.00 "

41 1/2° E. 35.70 " Outlet of fish lake 6 0 chs wide

27 1/2° E. 4.00 " leave meadow & enter timber. 2 ft. deep, runs N.

29° W. 1.27 "

26 1/2° W. 2.50 "

41° W. 3.25 "

23 1/2° W. 2.50 "

19 3/4° W. 4.78 "

24 1/2° W. 4.20 "

18 1/2° W. 3.50 "

6 1/2° W. 2.50 "

349

Meanders Tp. 26. S. R. 2 E.

N. 38 1/2° W.	5. 30. chs.
N. 3. ° E.	5. 30 .

To meander cor. to
fractional secs. 3 & 10.
Land. level & foot of mount.
Soil. 1st & 2nd rate.
Timber, pines & aspen on 3d. 10 chs.
Dense undergrowth on 3d. 10 chs.
Sept 12th 1883.

Note. The balance of this Tp. is not surveyed, on account of falling in impracticable and unavailable mountains.

BOOK-A-197

R. 2 E.

to
s. 3 & 10.
...

39. 10 th.
... 39. 10 ...
& 3.

Tp. is
st. of Salt
available

General Description.

The surveyed part of this Tp. embraces some meadow and timber lands along Fish Lake which is a beautifull sheet of water, situated on top of the Wasatch mountains at an elevation of 8500 ft. above sea-level.

The applicants improvements are situated on Twin creeks in secs. 17 & 18 and consist of a well built log house, road making etc. There is also a cabin, corral & considerable fencing in sec. 30. The land is suitable for dairy farming.

A. D. Ferron
U. S. Dep. Surv.

BOOK-A-197

[4.—LIST OF NAMES.]

A list of the names of the individuals employed by M. D. Tenney *United States deputy surveyer, to assist in running, measuring, and marking the lines and corners described in the foregoing field notes of the survey of* Extension and Subdivisions of Tps 26 South in Ranges 16 & 2 East *of the Salt Lake base and meridian in the Territory of Utah, showing the respective capacities in which they acted.*

George Markbank, Compassman.

Olof Larsen, Chainman.

Enoch Jorgensen, Chainman.

....., Chainman.

....., Chainman.

R. H. Thompson, Axeman.

....., Axeman.

....., Flagman.

BOOK-A-197

[5.—FINAL OATHS OF ASSISTANTS.]

We hereby certify that we assisted Augustus D. Ferron *United States deputy surveyor, in surveying all those parts or portions of the* Exterior and Subdivision Lines of Tp. 26 S. Ranges 1 and 2 East

of the Salt Lake base and meridian in the Territory of Utah, as are represented in the foregoing field notes as having been surveyed by him and under his direction; and that said survey has been in all respects, to the best of our knowledge and belief, well and faithfully surveyed, and the corner monuments established according to the instructions furnished by the United States surveyor-general for Utah.

George Marshbank, Compassman.

Olof Larsen, Chainman.

Enoch Jorgenson, Chainman.

....., Chainman.

....., Chainman.

R. L. Thompson, Axeman.

....., Axeman.

....., Flagman.

Subscribed and sworn to before me this 14th *day of* Sept. 1883

A. D. Ferron

U.S. Dep Surv

BOOK-A-197

[6.—FINAL OATH OF UNITED STATES DEPUTY SURVEYOR.]

I, Augustus D. Timon

United States deputy surveyor, do solemnly swear that in pursuance of instructions received from Ind. Solomon

United States surveyor general for Utah, bearing date of the 5 th day of July, 1883, I have well, faithfully, and truly, in my own proper person, and in strict conformity with the instructions furnished by the United States surveyor general for Utah, the surveying manual, and the laws of the United States, surveyed all those parts or portions of Sections and Subdivisions of Tps No 26 South, in Ranges No 1 & 2 East

of the Salt Lake base and meridian in the Territory of Utah, as are represented in the foregoing field notes as having been surveyed by me and under my directions; and I do further solemnly swear that all the corners of said survey have been established and perpetuated in strict accordance with the surveying manual, printed instructions, the special written instructions of the United States surveyor general for Utah, and in the specific man-

ner described in the field notes, and that the foregoing are the **TRUE** *field notes of such survey; and, should any fraud be detected, I will suffer the penalty of perjury, under the provisions of an act of Congress, approved August 8, 1846.*

Augustus D. Gunn

United States Deputy Surveyor.

Subscribed and sworn to before me this 5th *day of* November *1883.*

Edward Mitchell

Notary Public

U. S. SURVE

Salt Lak

The fore

Divisions

Township No.

Executed by

Under Dep

day of

August

amined, the nec

the said field

hereby approve

BOOK-A-197

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, November 5th, 1883

The foregoing field notes of the survey of the Subdivisions & Meanders of Fish-Lake *Township No.* 26 South *Range No.* 2 East *Executed by* Augustus G. Ferron *Under* No 117 *contract of the* 5th *day of* July *1883., in the month of* August *1883., having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

Jno Caldwell

U. S. Surveyor General for Utah.

BOOK-A-197

REPORT: 1884.

Filed September 28, 1883.

Examined by Jos. St. Cowie.

Transcribed by L. W. Hickok.

Compared by O. E. & S. W. 26

FIELD NOTES

OF THE SURVEY OF THE

West and South

boundaries

OF

Township No 29 South

Range No 4 East

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Augustus D. Ferrow

U. S. Deputy Surveyor,

Under his Contract No. 117

Dated July 5th 1883.

Survey commenced July 26. 1883.

Survey completed July 28. 1883.

BOOK-A-197

[1—PRELIMINARY OATH OF COMPESSMAN.]

I, William Koeber

do solemnly swear that I will well and truly perform the duties of compassmen, according to instructions given me, and to the best of my skill and ability, in the survey of the Exteriors and Subdivisions of Tp 29 South, in Range 4 East

of the Salt Lake base and meridian in the Territory of Utah.

William Koeber, Compassman.

Subscribed and sworn to before me this 26th day of July 1883

A. D. Simon
U. S. dep. Surv.

BOOK-A-197

[2.--PRELIMINARY OATHS OF CHAINMEN.]

We James Heath

and W. Burgess,

do solemnly swear that we will well and faithfully execute the duties of chain carriers; that we will level the chain upon even and uneven ground and plumb the tally pins, either by sticking or dropping the same; that we will report the true distance to all notable objects, and the true length of all lines that we assist in measuring, to the best of our skill and ability, and in accordance with instructions given us, in the survey of the Exterior and Subdivisions of T. 29 South in Range No. 4 East

of the Salt Lake base and meridian in the Territory of Utah.

James Heath, Chainman.

W. Burgess, Chainman.

....., Chainman.

....., Chainman.

Subscribed and sworn to before me this 26th day of July 1883.

A. D. Lyman

U. S. Dep. Sur.

BOOK-A-197

[3.—PRELIMINARY OATH OF AXEMEN.]

We, G. W. Carroll

and .....

do solemly swear that we will well and truly perform the duties of axemen, in the establishment of corners and other duties, according to instructions given us, and to the best of our skill and ability, in the survey of Extension and Subdivisions of Sp 29 d. R 4 E

of the Salt Lake base and meridian in the Territory of Utah.

G. W. Carroll, Axeman.

....., Axeman.

Subscribed and sworn to before me this 26th day of July 1883

A. D. Timm

U. S. Dep. Sur.

BOOK-A-197 = 357

West Boundary Tp. 29 S. R. 4 E.

Survey commenced: July 26 A 1883.
with a Gurley solar compass.
From the cor. to secs. 7. 12. 13 & 18 on
W. boundary of Tp. 29 S. R. 4 E.
being a Sand Stone 20×20×5 in. 15 in. in the
ground, marked 2 Notches on N. & E. edges
with stone mound alongside.
Surv. South, on resurvey line between secs. 13 and 18.
Var. 15° 45' E.

7.20 Leave Fremont Valley, ascend
6.00 Gulch draining W.
26.00 W. point of spur ridge
40.00 Set a slate 10×8×6 in. 7 ins in the
ground for 1/4 sec. cor. marked 1/4 on
W. face and raised a stone mound
alongside from which
A pine 6 ins diam 45° E. 16 lks dist.
marked 1/4 S. B. T.
No trace of old cor. Ridge runs Easterly.
50.25 Gulch draining S. W.
59.00 " " "
80.00 In gulch draining S. W. set sand-
stone 16×12×4 in. 12 ins in the ground
for cor. to secs. 13. 18. 19 & 24 marked
with 3 notches on N. & E. edges
and raised a stone mound along-
side, from which

West Boundary Tp. 29 S.

		A pine 12 ins diam. bears N. 85° W.
	2.	dist. marked T. 29 S. R. 13 E. S. 1/4
		Land mostly heavy mo
		Soil 3rd rate.
		Timber pen cedars.
		Heavy mountains & dens
		undergrowth on 80 ac
		South betw. Secs. 19 &
		Var. 15° 45' E.
9.50		Enter Salt Creek cany on
16.50		Salt creek 2 lks wide 3 ins de
		runs N. W. acmd
40.00		Set gypsum 24 x 8 x 4 ins 16
		in the ground for 1/4 sec. c
		marked 1/4 on W. face and
		a stone mound alongside
50.20		N. W. spur of ridge.
80.00		Set a granite 14 x 10 x 8 ins 16
		in the ground for cor. to
		19. 24. 25 & 30. marked with
		notches on N and 2 notches
		Sedges and raised a stone
		alongside.
		Land mountains

...t Boundary Tp. 29 S. R 4 E.

Soil 3rd rate
Timber. scattering pines & cedars.
Heavy mountains & dense
undergrowth on 80 chs.

South betw. secs. 25 & 30
Var. 15° 45' E.
Gulch draws N. W. ascend
Set trachyte 20 x 10 x 8 in 14 in
in the ground for 1/4 sec. cor.
marked 1/4 on W. face and
raised a stone mound
alongside, from which
A pine 20 in diam bears N. 82° E.
37 lks dist. marked 1/4 S. B. T.
Descend
Set trachyte 24 x 10 x 6 in 18 in
in the ground for cor. to secs.
25. 30. 31 & 36 marked with 5
notches on N and W edges
and raised a stone mound
alongside.
Land. mountains
Soil 3rd rate.
Timber, few pines

West Boundary. Sp. 29 S. R

	Mountainous and dense undergrowth on 80 lks.
	South betw. Secs. 31 & 36 Var. 15° 45' E.
7.00	Wood road bears N. W & S. E.
8.30	Government creek 10 lks wide 6 ins deep runs N. W. in hollow.
9.00	Ascend.
30.50	Government creek 10 lks wide 4 ins deep runs N.E. in hollow
37.30	Head of Government creek 25 lks W. of line.
40.00	Granit 14×10×7 in 10 ins in the ground for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside.
71.00	Ridge bears N E & S. W.
80.00	Set granit 15×10×8 in 10 ins in the ground for cor. to Sps 29 & 30 S. R 3 & 4 E. marked with 6 notches on N, S, E & W edges from which A pine 9 ins diam. bears S. 15° E. 26 links dist. marked S 30 S. R4E. S.6. B.T.

BOOK-A-197

West boundary T. 29 S. R. 4 E.

A pine 3 in diam: bears N 33° W.
2 lks dist: marked T 29 S. R. 3 E.
S. 36 B. T.

Land mountainous
Timber, Yew Cedars
Soil, 2nd rate
Heavy mountainous and
dense underbrush Dou 80.00 chs.

July 26th, 1883

Augustus G. Ferrow.
U. S. Dep: Surveyor.

BOOK-A-197

South Boundary Tp. 29 S. R. 4 E.

From the cor. to Tps. 29 & 30 S. R. 3 & 4 E. run East on random line betw. said Tps. setting temporary 1/2 mile & Mile cors. every 40 & 80 chs. I find the line to be 6 Miles 1 chs. 45 lks. long and the falling to be 9 & lks. N. of corner point to Tp. 29 & 30 S. R. 4 & 5 E.

The correction for the same line will therefore be 15½ lks S. & 1.45 chs. E. pr. mile. and it's course N. 89° 54' W.

From the Witness corner, 50 lks N. of corner point to Tp. 29 & 30 S. R. 4 & 5 E. formerly set by me I run S. 50 lks. to corner point then

N. 89° 53' W. on true line
betw. secs. 1 and 36
Var. 15° 39' E.

8.50 Sandstone bluff ridge bears N E & S W.
4.00 falls on round soft sandstone ledge too soft to mark, therefore 4.37 chs. West from corner point set sandstone 14 x 10 x 4. 10 ins in the ground for 1/4 sec. cor. marked 1/4. W. C. on N face & raised a stone mound alongside.

217

South boundary Tp. 29 S. R 4 East

45.00 Descend, perpendicular ledges.

47.50 Wash dr. N & E into Donkey Creek

51.50 Bluff ridge bears N E & S W.

58.00 Gulch drains N. W.

65.70 Gulch drains N. W.

80.00 Set sandstone 14 x 10 x 6 in 8 in in the ground for cor. to secs. 1, 2, 35 & 36. marked with 1 notch on E and 3 notches on W. edges and raised a stone mound alongside.

Lava. Mountains

Soil 1st & 2nd rate.

Timber. some pine & cedar

Mountainous & some underg south on S

N. 89° 53' W on true line

betw. secs. 2 and 35

Var. 15° 45' E.

4.75 Gulch drains N.

40.00 Set granite 16 x 12 x 6 in 12 in in ground for 1/4 sec cor. marked 1/4 on N face and raised a stone mound alongside from which a pine 15 in diam bears S. 45° W. 52 links marked 1/4 S. B. T.

5.10 R. a

15.00 Gul

4.00 Set

the g

35 m

and 4

stone

dred

dist. n

Lan

Soil

Timb

Heav

E

N. 8

4.55 Spr

deep

Gul

2.50

40.00 Set

grou

1/4 on

mou

T. R 4 | South Boundary Tp. 29 S. R 4 E.

ledges.	5.10
ley Cree	5.00
& W.	4.00
6 & 8 in	
secs. 1. 2	
oth on	
and	
along	
e	
cedar	
oth on 80	
line	
5	
	4.55
	2.50
mou	4.00
W. 52 lks	

Red beans N 2 lks E.
Gulch drains N.
Set granite 18 x 10 x 3 in 12 in in the ground for cor. to secs. 2. 3. 34 & 35 marked with 2 notches on E and 4 on W edges and raised a stone mound alongside, from which Oregon pine 4 in diam bears N 9° E. 60 lks dist. marked T. 29 S. R 4 E. S. 35. B T.
Land mountainous.
Soil 2nd rate
Timber. some pine & cedars
Heavy Mountains & dense undergrowth on 80 chs.

N. 89° 53' W. on true line betw. secs. 3 and 34
Var. 15.45° E
Spring branch 2 lks wide 4 ins. deep runs N. E.
Gulch drains N. E.
Set granit 12 x 8 x 6 in 8 in in the ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside

South Boundary Tp. 29 S. R

80.00 On ridge bears N E & S W sc
granite 14 x 8 x 6 in 10 ins in the
ground for cor. to secs. 3. 4. 33 & 34
marked with 3 notches on E
edges and raised a stone mo
along side.
Land. Mountainous.
Soil 2nd rate
Timber. some pine & cedar
Heavy Mountains & dense
undergrowth on 80 chs.
July 27th 1883.

N. 89° 53' W on true line 10.50
betw. secs. 4 and 33
Var. 15° 45' E. 21.50
Descend. 16.00
42.60 Spring in gulch runs N.
31.50 Gulch drains N. E.
40.00 Set granite 20 x 10 x 6 in 15 in in
ground for 1/4 sec. cor. mark 41.90
1/4 on N. face and raised a stone 43.50
mound along side. 75.00
60.50 Gulch drains N. 79.00
80.00 Set sandstone 16 x 10 x 5 in 10 in
the ground for cor. to secs. 4. 5. 33 86.00

South Bo

mar
and
a sta
Lan
Soil
Tim
Hea

N.

Spru
deep
Bea
Set
the g
1/4 on
mou
a pin
Gul
Spru
Mai
Tim
Set

BOOK-A-197

South Boundary Tp. 29 S. R. 4 E.

marked with 4 notches on E. and 2 on Wedges. and raised a stone mound along side.
Land. Mountainous
Soil 2nd rate.
Timber. scattering pine.
Heavy Mountains and dense undergrowth on Sides.

N. 89° 53' W. on town line betw. secs. 5 and 32.
Var. 16° 12' E.

10.50 Spring branch 15 lks. wide 4 in deep runs N. in gulch.
1.50 Ravine dr. N. E.
16.00 Set a granite 12×8×6 in 8 in in the ground for 1/4 sec. cor. marked 1/4 on N. face and raised a stone mound along side.
1.90 A pine 24 in diam.
43.50 Gulch dr. N. W.
75.00 Pond 10 ft. diam. bears N. 25 lks
9.00 Main Mulberry Creek 10 lks wide 5 ins. deep runs N. E. in gulch
86.00 Set granite 15×10×8 in 16 in

South Boundary Tp. 29 S. R.

South bo

in the ground for cor. to secs.
5. 6. 31 & 32. marked with 5 on
on E and 1 on W edges and
raised a stone mound alongs
from which
An aspen 10 in diam bears N. 15° E. 15 l
dis taut marked T. 29 S. R 4 E. S. 32 B.
an aspen 15 in diam bears S. 21° E 29
dist. marked T. 30 S. R 4 E. S. 5. B. T.
Land. Mountains
Soil 2nd rate.
Timber. Pines, cedars & aspen
Heavy mountains & dense
Undergrowth on 80 chs.

N. 89° 53' W. on true lin
betw. secs. 6 and 31.
Var. 16° 12' E.

15.50 Spring branch 5 lks wide 3 in d
runs N. W in gulch.
26.10 S. point of small pond
40.00 In gulch drains S E. set gra
12 x 8 x 6 i 8 in in the ground f
1/4 sec. cor. marked + on N.
face and raised a stone

mo
Ri
Gu
The
E.
Lan
Soi
Tim
Hea
m

Vote
For
sec
tow
Co

BOOK-A-197

South boundary Tp. 29 S. R 4 E.

mound along river.
Ridge bears N & S.
Gulch drains N. E.
The cor. to Tps 29 & 30 S. R. 3 & 4 E.
Land. Mountains
Soil. 2nd rate.
Timber. some pine & cedars
Heavy mountains & dense undergrowth on 31. 45 chs.

July 28th. 1883.

Vote.

For general description see Subdivisions of this township.

Augustus A. Ferrow
U. S. Dep Surv

BOOK-A-197

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, November 5th *1883.*

The foregoing field notes of the survey of the West and South boundaries *Township No.* 29 South *Range No.* 4 East *Executed by* Augustus D. Ferron *Under* his *contract of the* 5th *day of* July *1883, in the month of* July *1883, having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

Edw. Salisbury

U. S. Surveyor General for Utah.

BOOK-A-197

REPORT: 1884.

Filed September 28, 1883

Examined by John H. Cauke.

Transcribed by William Koeber

Compared by O.E.S. & S. W. H.

FIELD NOTES

OF THE SURVEY OF THE

Subdivisions

OF

Township No 29 South

Range No 4 East

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Augustus D. Ferron

U. S. Deputy Surveyor,

Under his Contract No. 117

Dated July 5th, 1883.

Survey commenced July 30, 1883.

Survey completed August 11, 1883.

BOOK-A-197

Township 29 South *R.* 4 East



BOOK-A-197 - 363

Subdivisions T. 2 S. R. 4 E.

Survey commenced July 30 th 1883.
with a Burts improved solar compass.
From the cor. to Secs. 35 & 36 on the
south boundary of the township
formerly set by me I run
North bet. secs. 35 & 36
Var. 15° 45' E.

4.50 Gulch dr. N. W.

4.75 Gulch dr. N. E.

6.00 Set a granit 14 x 10 x 6 ins. 10 ins in the
ground for 1/4 sec. cor. marked
1/4 on W. face and raised a stone
mound alongside, from which
A pine 6 ins diam. S 45° E. 6 lks dist.
marked 1/4 sec. B. T.
A. cedar 20 ins diam. bears S. 45° W. 9 lks
dist. marked 1/4 S. B. T.

45.00 Gulch dr. N. E.

80.00 Set a granit 12 x 6 x 4 ins. 8 ins in the
ground, for cor. to secs. 25. 26. 35 &
36, marked with 1 notch on S & E.
edges and raised a stone mound
alongside, from which
A pine 7 ins diam. bears S. 9 W. 2 9 lks
dist. marked T. 2 S. R. 4 E. S. 35 B. T.
A pine 9 ins diam. bears N. 11 W. 33 lks

dist. marked S. 29 S. R 4 E. S. 46. B.
two other trees within limits
land. mountainous
Soil. 2nd rate
Timber. Cedars & pines.
Dense undergrowth var. 80 Chs.

East on a random line
bet secs. 25 and 36
Var. 16° 12' E.

40.00 Set temporary 1/4 sec. cor.
80.40 Intersect East boundary of the
40 lks. S of cor. to secs. 25 & 36. forme
set by me from which I run
S. 39. 43 W. on a true line
bet secs. 25 and 36
17.40 Donkey Creek, dry, drains N.
29.00 Enter lower flat bears N E.
40.20 Set trachyte 12 x 6 x 4 ins. 8 ins in
ground, for 1/4 sec. cor. marked 1/4 on
face and raised a stone mound
alongside
No trees within limits
51.50 Enter cedars bearing N. W. & S. E.
57.50 Wash dr. N E.

.50 leave
.40 The co
Land
Soil
Timbe
dense

Ch
Descend
.00 Post
.00 Set
the g
1/4 on
mou
.50 Enter
.90 Was
.00 Set
in the
25 & 2
Land
stone
No tre
Land.
Soil.
Timbe

BOOK-A-197

Subdivisions Sec. 29 T. R. 4 E

leave flat bears N.W. & S.E.

.40 The cor. to secs. 25. 26. 35 & 36.

Land. mountainous and level

Soil 1st & 3rd rate

Timber. Cedars and pines.

dense undergrowth on 80. 40 Chs.

North bet. secs. 25 and 26

Var. 16° 12' E.

Descend

.00 Foot of slope

.00 Set trachyte 24 × 12 × 6 ins. 18 ins in the ground for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside.

.50 Enter timber bears E & W.

.00 Wash drains N. E. Leave Timber

.00 Set sandstone 12 × 10 × 6 ins 8 ins. in the ground for cor. to secs. 23. 24 25 & 26 marked with 1 notches on S. and 1 on E. Edges and raised a stone mound alongside.

No trees within limits.

Land. mostly level

Soil. 2nd rate

Timber. scattering cedars & pines

Subdivisions Sec. 29 T. R. 4 E

Dense artemisia undergr
on 81.00 Chs.

East on a random line
bet. Secs. 24 and 25
Var. 15° 45' E.

40.00 Set temporary 1/4 sec. cor.

80.70 Intersect East boundary of Sec
S. of cor. to secs. 24 & 25 former
by me, from which I run
S. 89. 45 W. on a true line be
Secs. 24 and 25

40.35 Set trachyte 12 x 8 x 8 ins. 8 ins in
for 1/4 sec. cor. marked 1/4 on E. f
raised a stone mound alongsi

76.90 Road bears S. E & N. W.

76.95 Wash drains N. E.

80.70 Sec. cor. to secs. 23. 24. 25 and 26.
Land. rolling
Soil. 1st & 2nd rate.
Timber. scattering cedars.
Dense artemisia undergrowth

80.70 Chs.

July 30 A 18

Subdivisions

No

Enter
Road
Wash
Road
Wash
Leave
Cedar
Set tr
groun
1/4 on
mou
Hollo
Top
Set t
groun
mark
1 in Stak
mou
Land
Soil.
Timbe
Dense

BOOK-A-197

Divisions Tp. 29 S. R. 4 E

North bet. Secs. 23 and 24
Var. 15° 45' E.

Enter hollow
Road bears N.W. & S.E.
Wash 7 ft. deep drains N.E.
Road bears N.E. & S.W.
Wash 9 ft. deep drains N.E.
Leave hollow drains N.E. and Enter Cedars.
Set trachyte 12 x 6 x 4 ins. 8 ins in the ground for 1/4 Sec. Cor. marked with 1/4 on W. face and raised a stone mound alongside.
Hollow drains N.E.
Top of ascend.
Set trachyte 15 x 10 x 6 ins. 12 ins in the ground for cor. to Secs. 13. 14. 23 and 24 marked with 3 notches on S and 1 notch on E. edges, and raised a mound of stones alongside.
Land: level and mountainous
Soil. 1st and 2nd rate.
Timber. scattering cedars & pines.
Dense artemisia undergrowth on
80.00 Ch.

Subdivisions Sec. 29 T. 4 S. R. 4 E

	East on a random line bet. secs. 13 and 24 Var. 15° 45' E.
40.00	Set temporary 1/4 sec. cor.
80.20	Intersect E. boundary of Tp. 25 Rs. S. of cor. to secs. 13 & 24 formerly set by me from which I run S. 89. 49 W. on a true line betw. secs. 13 and 24
25.00	Descend
37.00	Fremont River 40 lks. wide 4 ft. deep runs S. E.
40.70	Set trachyte 15 x 15 x 6 ins. 10 ins in the ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside
40.50	Leave riverbottom
49.50	Road bears N & S.
55.00	Enter high bench bears N E & S W.
67.25	Gulch draining N.E.
79.50	Top of bench bears N E & S W.
80.20	Sec cor. to secs. 13. 14. 23 & 24. Land level and mountainous Soil 1st and 2nd rate Timber scattering cedars. Dense undergrowth on 80.20 Chs.

Subdivisio

16.50	Desc
32.70	Ente
40.00	Set grou an W. alon
47.22	Willo
53.30	Leav
54.50	Ente
55.00	Fren runs
61.50	Lea
80.00	Set gro ma with a st Lan Soil Vot Dens

Subdivisions Sec. 29 T. R. 4 E.

North betw. secs. 13 and 14.
Var. 15° 45' E.

16.50 Descend bears E & N.

32.70 Enter lower bench

40.00 Set trachyte 14×10×6 ins. 10 ins in the ground for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside

47.22 Willmer's Cabin bears N. 64° E. 10 Chs. dist.

53.30 Leave bench N. W. & S. E.

54.50 Enter bottom

55.00 Fremont River 40 lks wide 4 ft. deep runs N E, heads N. W.

61.50 Leave river bottom bears N W & S E.

80.00 Set trachyte 20×8×6 ins. 15 ins in the ground for cor. to secs. 11. 12. 13 & 14. marked with 4 notches on S. and with 1 notch on E. edges and raised a stone mound alongside.

Land. level

Soil. 1st and 2nd rate.

No timber.

Dense artemisia undergrowth on

80 Chs.

Subdivisions Tp. 29 S. R. 4 E.

East on a random line
betw. Secs. 12 and 13.
Var. 15° 45 E.

40.00 Set temporary 1/4 sec. cor.

80.00 Intersect E. boundary of Tp. 5 lk. S. of cor. to secs. 12 & 13 formerly set by me, from which I run
S. 89° 58' W. on a true line
betw. Secs. 12 and 13.

40.00 Set trachyte 16 x 12 x 6 ins. 12 ins. in the ground for 1/4 sec. cor. marked 1/4 on E face and raised a stone mound alongside.

57.50 Enter cedars.

69.50 Leave the same Road bears N. W. & S. E.

80.00 The cor. to secs. 11. 12. 13 and 14.
Land level
Soil 1st rate
Timber, cedars.
Dense artemisia undergrowth
on 80.00 Chs.

July 31st 1883.

Subdivisio

16.00 Roa
40.00 Set
grou
on
alon
5.85 Roa
0.00 Set
grou
ma
and
raise
Lan
Soil
Ve
Dec

40.00 Set
79.82 Int
cor
by

BOOK-A-197

Subdivisions Tp. 29 S. R. 4 E

North betw. Secs. 11 & 12
Var. 15° 45' E.

16.00 Road N. W. & S.E.

40.00 Set trachyte 12×6×4 ins 8 ins in the ground, for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside.

5.85 Road bears S. W. & N.E.

21.00 Set trachyte 18×10×8 ins 12 ins in the ground for cor. to secs. 1. 2. 11 & 12 marked with 5 notches on S. and 1 notch on E. edges. and raised a stone mound alongside.

Land. level.
Soil 1st rate.
No timber.
Dense artemisia undergrowth on
80. or Chs.

East on a random line
betw. Secs. 1 & 12
Var. 15° 45' E.

40.00 Set temporary 1/4 sec. cor.

79.82 Intersect E. boundary of Tp. at cor. to secs. 1 & 12. formerly set by me from which I run

Subdivisions Tp. 29 S. R. 4 E.

West on a true line
betw. secs. 1 & 12.

5.00 Enter higher bench bears S. E.

39.91 Set a trachyte 10 × 8 × 8 ins 6 ins in the ground for 1/4 sec. cor. marked on W. face and raised a stone mound alongside.

63.10 Road bears S. W. & N. E.

79.82 The cor. to secs. 1. 2. 11 and 12.
Land level
Soil 1st rate
Timber scattering cedars.
Dense artemisia undergrowth on
79.82 Chs.

North on a random line
betw. secs. 1 and 2.
Var. 15° 45' E.

40.00 Set temp. 1/4 sec. cor.

80.10 Intersect N. boundary of Tp. at cor. to secs. 1 and 2 formerly set by me from which Trun
South on true line
betw. secs. 1 and 2.

5.00 Wash in hollow draines S. E., gradually ascend

20.00 Top of
27.00 foot
36.50 Enter
40.10 Set
grou
W. fa
along
A. pin
de
A. pe
de
52.00 Bro
deep
79.82 The
Lan
Soi
Tim
Dens

Subdivise

BOOK-A-197

Subdivisions Th. 29 N. R 4 E

20.00	Top of bluff 150 ft. high bears N W & S E.
27.00	foot of same, Enter hollow drains S E
36.50	Enter bench bears N W & S E.
40.10	Set limestone 18 x 6 x 5 ins. 12 ins in the ground for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside from which A. pine 4 ins diam. bears N 60° W. 23 lks. dist. marked 1/4 S. B. T. A. pine 5 ins. diam. bears N 70° E. 35 lks. dist. marked 1/4 S. B. T.
52.00	Brown's Creek 10 lks. wide, 10 ins. deep runs S. E. in hollow.
80.10	The cor. to secs. 1. 2. 11 & 12. Land. mostly level bench. Soil. 3rd rate. Timber. scattering cedars. dense undergrowth on 80.10 ch.

August 12th. 1883.

Subdivisions Tp. 29 S. R. 4 E.

From the cor. to secs. 34 & 35 on the S. boundary of the Tp. formerly set by me I run

North bet secs. 34 and 35.

Var. 15° 45' E.

Descend

15.00 Gulch draws N. E.

27.25 Road bears S. E & N. W.

40.00 Set a sandstone 24×10×4 ins 18 ins in the ground for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside from which a pine 15 ins diam. bears S. 39. E. 42 lks. dist. marked 1/4 S. B. T. — 40.00

80.60 — 7.50

No other trees within limits. — 17.00

80.00 Set a granit 20×10×6 ins, 15 ins in the ground for cor. to secs. 26. 27. 34 & 35 marked with 1 notch on S and 2 notches on E edges and raised a stone mound alongside from which — 40.30

A pine 20 ins diam. bears N. 85° E. 21 lks dist. marked T. 29 S. R. 4 E. S. 26. B. T. — 75.00

A pine 15 ins diam. bears N. 77° W. 34 lks dist. marked Tp. 29 S. R 4 E. S. 27. B. T. — 84.60

No other trees within limits

Land. mountainous

Subdivisions of Sec. 29 & R. 4 E

Soil 3rd rate.
Timber. cedars & pine
Dense undergrowth on 80 chs.

East on a random line
betw. secs. 26 & w 35
Var. 15° 45' E.

40.00 Set a temporary 1/4 Sec. cor.
80.60 Intersect N. & S. line 49 lks. S. of cor. to secs. 25. 26. 35 & 36 from which I run S. 89° 39' W on a true line betw secs. 26 & w 35
7.50 S of of cedar ridge bears N E & S W.
17.00 Gulch draius N. E.
40.30 Set a trachyte 14 x 6 x 4 in 10 ins in the ground for 1/4 Sec. cor. marked 1/4 on N face and raised a mound of stones alongside.
75.00 Canyon draius N. W.
80.60 Pine cor. to secs. 26. 27. 34 & w 35
Land. mountainous.
Soil. 2nd rate.
Timber. scattering cedars & pines.
Thick undergrowth on 80.60 chs.

3 M

Subdivisions Sp. 29 S. R. 4 E.

North betn. secs. 26 and 27
Var. 15° 45 E.

Descend.

6.05	East fork of canyon heads S. E.		
8.90	Enter main canyon draius N.		
25.70	Wash draius N. E.		
29.10	Road bears N E & S W.		
31.25	the same bears N W & S E.		
32.40	Wash draius N. W.		
33.50	leave canyon ~~bears~~ draius N. W. & ~~S E.~~	40.00	Set
38.50	Top of spur of sandstone bluff 200 ft. high bears N. W & S.E.	80.40	Ente to secs. cor.
40.00	Set a sandstone 24×12×6 ins 18 ins in the ground for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mou alongside.	3.50	En
		13.50	Lea
43.00	Enter rolling bench N E & S W.	35.00	Wa
43.50	Wash 7 ft. deep draius N.E.	40.20	Set
50.00	Road bears N E & S W.		gro
57.00	N.E. spur of sandstone bluff bears S W & N E. leave timber.		on alo
67.50	Road bears N W & S E.	80.40	The
80.00	Set trachyte 12×8×6 ins 8 ins in the gro for cor. to secs. 22. 23. 27 and 28, marke with 2 notches on S. and E. edges and raised a stone mound alongside.		Lar Sou Tim Dea

BOOK-A-197

Land. mountainous and level.
Soil. 3rd & 1st rate
Timber. pines & cedars
Deuse artemisia undergrowth
on 80 Chs.

East on a random line
betn secs. 23 and 26
Var. 16° 12' E.

40.00 Set temporary 1/4 sec. cor.
80.40 Intersect N. & S. line 2 lks. S. of cor. from which
to secs. 23. 24. 25. 26
I. bears
S. 89. 49 W. on a true line
betn. secs. 23 and 26
3.50 Enter cedars bearing N & S.
13.50 Leave the same
35.00 Wash drains N. E.
40.20 Set a trachyte 15 x 8 x 6 ins 10 ins in the ground for 1/4 sec. cor. marked 1/4 on N. face and raised a stone mound alongside.
80.40 The cor. to secs. 22. 23. 26 and 27.
Land. level
Soil 1st and 2nd rate.
Timber. cedars & pine
Deuse artemisia undergrowth on 80.40 Chs.

Subdivisions Tp. 29 S. R. 4 E.

North betn. secs. 22 & 23
Var. 16° 24' E.

21.10 Wash 2 ft. deep draws N.E. cas
34.50 small ridge bears S.W. & N.E.
40.00 Set granit 14×8×6 ins 8 ins in the gro
for 1/4 sec. cor. marked 1/4 on W. fa
and raised a stone mound alongs
from which
Spruce 12 ins diam. bears N. 45° W. 45
dist. marked 1/4 S. B. T.
no other trees within limits.
Principles by manual
62.10 Enter lower bench bears N.E. & S.W.
80.00 Set trachyte 16×12×6 ins 12 ins in the
ground for cor. to secs 14. 15. 22 and 23
marked with 3 notches on S and
2 notches on E edges and raised a
stone mound alongside.
Land mostly level.
Soil 1st and 2nd rate.
Timber, scattering cedars.
Dense artemisia undergrowth on

80.00 Chs.

August 2nd 1883.

40.00 Set
80.25 Inte
to s
S. ra
c
1.20 Lea
23.50 En
40.13 Set
gro
1/4
m
64.00 Acr
74.00 En
80.25 Re
La
So
Ti
2

Subdivisions Tp. 20 S. R. 4 E.

	East on a random line betw. secs. 14 and 23. Var. 16° 24' E.
40.00	Set temporary 1/4 secs. cor.
80.25	Intersect N. & S. line 6 lks. S. of cor. to secs. 13. 14. 23 & 24 from which S. run S. 89° 56' W. on a true line betw. secs. 14 and 23.
1.20	Leave cedars bearing S E & N W.
23.50	Enter cedars
40.13	Set granit 18 x 8 x 6 ins. 12 ins in the ground for 1/4 sec. corner, marked 1/4 on N face and raised a stone mound alongside.
69.00	Across bench, descend
74.00	Enter lower bench bears N E & S W.
80.25	The cor. to secs. 14. 15. 22 and 23.
	Land. mountainous.
	Soil. 3rd rate
	Timber. cedars.
	Dense undergrowth on 80.25 chs.

Subdivisions Tp. 29 S. R 4 E.

	North betw. Secs. 14 and 15 Var. 16. 30 E.	80. 00
6.60	E. bend of Wash 30 ft. deep	
27.75	Wash draws N.E.	
40. 00	Set granit 10 x 10 x 10 in. 6 ins in the ground for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside.	40. 00
45.00	Wash 30 ft. deep dr. N. E.	
45.60	Waste ditch runs N.E.	45. 00
75.25	Road bears N W & S E.	46. 50
80. 00	Set trachyte 15 x 10 x 4 in. 10 ins in the ground for cor. to secs. 10. 11. 14 and 15 marked with 4 notches on S and 2 on E edges and raised a stone mound alongside.	50. 50
	Land. rolling	80. 00
	Soil 1st & 2nd. rate	
	No timber	
	Thick undergrowth on 80. Chs.	
	East on a random line betw. Secs. 11 and 14 Var. 16° 30' E	26. 00
		30. 50
40.00	Set temporary 1/4 sec. cor.	

Subdivisions Tp. 29 S. R 4 E.

80.00	Intersect N. & S. line at cor. to secs. 11. 12. 13 & 14. from which I run West on a true line betw. secs. 11 & 14.
40.00	Set trachyte 15 x 12 x 4 ins. 12 ins in the ground for 1/4 sec. cor. marked 1/4 on N. face and raised a stone mound alongside.
45.00	River bottom bears N W & S E.
46.50	Fremant River 40 lks wide. 4 ft. deep runs S E. near Ford. —
50.50	Leave bottom bears N W & S E.
80.00	The cor. to secs. 10. 11. 14 & 15. Land. level and rolling Soil 1st rate No timber Dense artemisia undergrowth on 80 Chs.

North betw. secs. 10 & 11 Var. 16° 30' E.

26.00	Enter bottom bears N W & S E.
30.50	Fremant River 40 lks wide 3 ft. deep runs N E.

Subdivisions Tp. 29 S. R. 4 E.

39.00	Fremont River 40 lks wide, 4 ft. deep runs S. W.	
40.00	Set trachyte 30 x 20 x 10 in. 24 ins in the ground, for 1/4 sec. cor. mark 1/4 on W. face and raised a stone mound alongside.	0.80 20.00
53.00	Fremont River 40 lks wide 2 ft deep runs S. E.	40.10
62.00	Leave bottom N. W. & S. E.	
80.00	Set sandstone 20 x 10 x 4 in. 14 ins in the ground, for cor. to secs 2, 3, 10 and 11 marked with 5 notches on S and 2 notches on E edges and raised a stone mound alongside.	57.50 57.25 79.25 80.20

Land mostly level.
Soil 1st and 2nd rate
No timber.
Dense artemisia undergrowth and

East on a random line
bet. secs. 2 and 11.
Var. 16° 30' E.

40.00	Set temporary 1/4 sec. cor.	
80.20	Intersect N. & S. line at cor. to	

BOOK-A-197

R. 4 E. Subdivisions Tp. 29 S. R. 4 E.

secs. 1. 2. 11 and 12. from which I run

West on a true line
between secs. 2 and 11.

9.80	Road bears N. & S.
20.00	Leave trachyte bench bears N. W. & S. E.
40.10	Set trachyte 18 x 16 x 12 in. 12 ins in the ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.
57.50	Wash drains S.
57.25	" " S. E.
79.25	" " S.
80.20	The cor. to secs. 2. 3. 10 and 11.

Land mostly level.
Soil 3rd rate
No timber
Dense undergrowth on 80.20 Chs

August 3rd. 1883.

Note

The line between secs. 2 and 3 falling in inaccessible and unavailable bluff is not established.

Subdivisions Tp. 29 S. R. 4 E.

From the cor. to secs. 33 and 34 on the S. boundary of the Tp. formerly set by me I run North bet. 33 and 34. Var. 15° 45' E.

	Descend.	40.00
3.50	Enter timber	80.70
40.00	In gulch drains NE. set granite 20×10×8 ins 15 ins in the ground for 1/4 Sec. cor. marked 1/4 on W. face and raised a stone mound alongside, from which	17.25
	A pine 40 ins diam. bears N. 45° W.	18.50
	37 lks dist. marked 1/4 S. B. T.	19.45
	A. pine 25 ins diam bears N. 33° E.	21.50
	14 lks. dist. marked 1/4 S. B. T.	40.35
65.40	Gulch drains NE.	
80.00	Set a sandstone 14×8×4 ins 10 ins in the ground for cor. to secs. 27. 28. 33 and 34 marked with 1 notch	74.50
	on S and 3 notches on E edges and	80.70
	raised a stone mound alongside	
	No trees within limits.	
	Land mountainous	
	Soil. 2nd rate.	
	Timber. Cedars & pines.	

BOOK-A-197

Dense undergrowth on 80 Chs.

East on a random line
betw. Secs. 27 and 34
Var. 15° 45' E.

40.00 Set temporary 1/4 sec. cor.

40.70 Intersect N. & S. line 55 Lks. S. of cor. to secs. 26. 27. 34 & 35 from which I run
S. 89° 37' W. on a true line
betw. Secs. 27 and 34

17.25 Enter canyon bears N.E. & S.W.

18.50 Wash drains N.E.

19.45 Road bears N.E. & S.W.

21.50 Leave canyon

40.35 Set trachyte 10 x 10 x 8 ins 6 ins in the ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

74.50 Gulch drains N.E.

80.70 Stone cor. to secs 27. 28. 33 & 34
Land. mountainous.
Soil Stony
Timber. scattering cedars & pines.
Dense undergrowth on 80.70 Chs.

Subdivisions Sec. 29 T. 2 R. 4 E.

North bet. Secs 27 and 28
Var. 15° 45' E.

37.50 Gulch draius N.E.
40.00 Set trachyte 16×12×6 in 12 ins in the ground for 1/4 sec. cor. mark 1/4 on W. face and raised a stone mound alongside.
47.50
80.40
51.50 Gulch draius N.E.
67.50 Enter hollow draius N.E.
67.90 Wash dr. N.E.
80.00 Set trachyte 12×8×6 ins 8 ins in the ground for cor. to secs. 21. 22. 27 & 28 marked with 2 notches on S. and 3 notches on E edges and raised a stone mound alongside
10.30
23.90
32.70
Land. mountainous
Soil. 2nd rate
Timber. scattering cedars.
Thick undergrowth on 40 Chs.
65.00
80.40

East on a random line
betw. Secs. 22 and 27
Var. 15° 45' E.

22.50 Inaccessible bluffs renders chaining on line impracticable

Subdivisions Tp. 29 S. R. 4 E.

	offset N. 15 Chs., E 25 Chs., and S 15 Chs. to
47.50	in line where I set a temp. 1/4 sec. Witness cor.
80.40	Intersect N. & S. line at cor. to secs. 22. 23. 26 and 27 from which I run West on true line betw. secs. 22 and 27
10.30	Road N.W. & S.E.
23.90	Wash drains N.W.
32.70	7.50 chs E of cor point Set sandstone 30 x 15 x 10 in 20 in in the ground for 1/4 sec. Witness cor. marked 1/4 W.C. on N face and raised a stone mound alongside, then offset as before around bluff
65.00	Was'h drains N.E.
80.40	The cor. to secs. 21. 22. 27 and 28. Land. level and mountainous Soil 3rd and 1st rate. Timber. scattering cedars. Dense undergrowth on 80.40 chs.

August 4th 1883.

Subdivisions Tp. 29 S. R. 4 E.

	North betw. secs. 21 and 22		
	Var. 16° 18' E.		
2.25	Road bears N E & S W.		
3.80	Wash 9 ft. deep drains N E.		
15.00	Ascend.		
19.00	Top of ridge bears N W & S E.		
24.00	Descend		
37.50	Pine 24 ins diam.	40.00	se
40.00	Set a sandstone 20 x 15 x 8 ins. 15 ins	80.36	S
	in the ground for 1/4 sec. cor. mark		o
	1/4 on W. face and raised a stone mou		mo
	alongside. from which		
	A pine 30 ins diam. bears S. 87° W. 25 lks		
	dist. marked 1/4 S. B. T.	2.00	
	No other trees within limits.	18.60	
53.00	Enter flat bears N W & S E.	27.30	
60.90	Road bears S E & N W.	40.18	
65.15	Sandstone ledge bears N E & S E.		
73.55	Enter field bears E & W.		1/4
80.00	Set a sandstone 14 x 10 x 6 ins 8 ins in		
	the ground for cor. to secs 15. 16. 21 & 22	61.50	
here	marked with 3 notches on S and		
	E edges and raised a stone	74	
	mound alongside.	74.90	
	Lands. level and mountainous	78.60	
	Soil. 1st and 3rd rate	80.36	

BOOK-A-197

Subdivisions Sp. 29 S. R 4 E.

Timber: scattering cedars
Dense artemisia undergrowth
on 80. Chs.

East on a random line
bet. Secs. 15 and 22
Var. 16° 30' E.

40.00 Set temporary 1/4 sec. cor.

80.36 Intersect N. & S. line 37 lks E. of cor. to secs. 14. 15. 22 and 23 from which I run
S. 89° 44' W. on a true line
betw. secs. 15 and 22

2.00 Wash drains N.E. 30 ft deep

18.60 " " " 30 " "

27.30 " " " 30 " "

40.18 Set sandstone 15 x 6 x 4 ins 12 ins in the ground for 1/4 sec. cor. marked 1/4 on N. face and raised a stone mound alongside.

61.50 Enter field bears N & E.

74.90 Leave field bears N.E. & S.W.

78.60 Enter " " N.W. & S.E.

80.36 The cor. to secs. 15. 16. 21 and 22

Subdivisions Sec. 29 T. 2 R. 4 E.

Land rolling
Soil 1st rate
No timber
Dense artemisia undergrowth

North betw. 15 and 16
Var. 16° 45' E.

2.90	branch of bullberry Creek 4 lks wide 3 ins deep runs NE.		
8.00	Leave field bears SE & NW.	40.00	Se
16.60	Enter " " "	80.00	Sec
23.52	leave " " "		to
32.25	Road bears NE & SW.		
38.50	Branch of bullberry Creek 3 lks wide 3 ins deep runs NE.	15.00	Se
40.00	Set a trachyte 10×8×4 ins 6 ins in the ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.	30.50 40.00	E S th 1/4
49.67	Road bears NE & SW.		
80.00	Set a trachyte 10×8×4 ins. 6 ins in the ground for cor. to secs. 9. 10. 15 and 16 marked with 4 notches on Sec 3 notches on Edges & raised a stone mound alongside.	56.70 80.00	C C S C C S

BOOK-A-197

P 4 E. Subdivisions Tp. 29 S. R 4 E.

	Land. rolling
	Soil. 1st rate.
	Timber scattering cedars
	Dense artemisia undergrowth
	on 80 lks.
	East on a random line
	bet. secs. 10 and 15
	Var. 16° 30' E.
40.00	Set a temporary 1/4 sec. cor.
80.00	Intersect N. & S. line at cor.
	to secs. 10. 11. 14 & 15 from which
	Iron Post on a true line
	betw. secs. 10 and 15.
15.00	Road W & S. E.
30.50	Enter higher bench bears S. E. 1/4 W.
40.00	Set trachyte 14 x 8 x 6 ins. 8 ins in
	the ground for 1/4 sec. cor. marked
	1/4 on N face and raised a stone
	mound along side.
56.10	Bullberry Creek dry. drains N. E.
80.00	Meander to secs. 9. 10. 15 & 16.
	Land. rolling
	Soil 1st. rate
	Timber. scattering cedars.
	Dense undergrowth on 80 lks.

Subdivisions Tp. 29 S. R. 4

	North betn secs 9 and 10	40.00
	Var. 16° 30 E.	80.00
13.50	Enter lower bench bears N W &	
15.50	Road bears N W. S.E.	
40.00	Set a trachyte 12×12×6 ins 8 ins in the ground for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside.	2.50
		4.90
		1.40
64.50	Road bears N W & S E.	32.50
75.00	Enter bottom bears N E & S W.	
80.00	Set a trachyte 14×12×10 ins 8 ins in the ground for cor to secs. 3 4 9 and 10 marked with 5 notches on S and 3 notches on E edges and raised a stone mound alongside.	39.00
		40.00
	Land. rolling	
	Soil. 1st & 2nd rate	
	Timber: scattering cedars.	
	Dense undergrowth on 80 chs.	51.00
		58.50
	East on a random line betn. Secs. 3 and 10.	
	Var. 16° 30 E.	80.00

Subdivisions Sp. 29 S. R. 4 E.

40.00	Set temporary 1/4 sec. cor.
80.00	Intersect R. g S. line at cor. to secs. 2. 3. 10 & 11. from which Trees West on a true line betw secs. 3 & 10 &
2.50	Wash drains S.
4.90	" " S.E.
1.40	" " "
32.50	Mus. Joy Cabin bears S. 45° 30 W. 20 Chs. dist.
39.00	Wash drains S.
40.00	Set sandstone 18×12×10 in 12 ins in the ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside from which A pine 5 ins. diam bears N. 65° W. 10 Lks dist. marked 1/4 S. B. T. no other trees within limits
51.00	Gulch drains S.
58.50	The Fremont River running along line, Soffset N 2.50 Chs. thence West 2.50 Chs. thence South 2.50 Chs. to
80.00	The cor. to secs. 3. 4. 9 & 10

Subdivisions. Tp. 29 S. R. 4 E

Land mostly south foothills of bluff.
Soil 3 rate.
Timber, scattering cedars
Mountainous on SO cor.
August 6th 1883.

	21.50
	40.00

Note

The line between Secs. 3 & 4 falling in unavailable and inaccessible bluffs is not established

	44.30
	54.00
	62.50
	80.00

.4 E. Subdivisions Tp. 29 S. R. 4 E.

oothills

ans

0 chs.

83.

3 & 4

e and

at set

From the cor. to Secs. 32 and 33 on the South boundary of the Tp. formerly, set by me Trun

North betw. Secs. 32 & 33.

Var. 16° 10' E.

21.50 Descend

40.00 Set a trachyte 10 x 8 x 6 ins 7 ins in the ground for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside from which

A pine 15 ins diam bears S. 17° E. 33 lks. dist. marked 1/4 S. B T.

44.30 Gulch draius N E.

54.00 Top of ridge bears N E & S W.

62.50 Gulch 150 ft. deep draius N W.

80.00 Set trachyte 15 x 10 x 6 ins 10 ins in the ground for cor. to secs. 28. 29. 32 & 33 marked with 1 notch on S and 4 notches on E edges and raised a stone mound alongside.

Land very mountainous

Soil 3rd rate

Timber. scattering cedars & pines

Subdivisions Tp. 29 S. R. 46

Dense artemisia undergrowth on 80 Chs.

East on random line
betw. Secs. 28 & 33.
Var. 16° 10 E.

40.00 Set temp. 1/4 sec. cor.
80.40 Intersect N. S. line 54 lks W. of cor. to secs. 27. 28. 33 & 34. from which Trees N. 89° 37 W. on true line betw. Secs. 28 & 33
10.00 Gulch draius N.E.
40.20 Set a trachyte 10 x 6 x 8 ins 6 ins in the ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside
80.40 The cor. to secs. 28. 29. 32 & 33.
Land. mountainous
Soil 2nd rate.
Timber. scattering cedars.
Dense artemisia undergrowth on 80.40 Chs.

0.50
12.10
37.60
38.00
40.00
80.00

BOOK-A-197

297

Subdivisions Tp. 29 S. R 4 E.

North betw. secs. 28 & 29
Var. 16° 1/2 E.

11.50 Pine 6 ins diam. in hollow
12.10 Spring branch 2 lks wide runs N.E.
37.60 Same Spring branch runs N. W.
38.00 The same runs N E.
40.00 Set a trachyte 20 x 10 x 4 ins 15 ins. in the ground for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside from which a pine 12 ins diam. bears N. 65° E 51 lks distant marked 1/4 S. B. T. no other trees within bar limits.
80.00 Set a slate 14 x 10 x 2 ins 8 ins in the ground for cor. to secs. 20. 21. 28 and 29, marked with 2 notches on said 4 on E edges and raised a stone mound alongside.

Land. mountainous
Soil. 2nd rate.
Timber, scattering cedar & pine
Dense undergrowth on 80 lks.

Subdivisions Sec. 29 T. R4

East on a random line
betw. secs. 21 and 28.
Var. 16° 1/2 E.

		17.50
40.00	Set temporary 1/4 sec. cor.	18.50
80.00	Intersect W. & S. line 15 lks. N. of cor. to secs. 21. 22. 27 & 28. from which I run N 89° 54 W. on a true line bet secs. 21 and 28.	31.20
		40.00
7.50	Road bears W. & E.	
15.00	leave road bears N. W. ascend.	52.00
40.00	Set a trachyte 15 x 6 x 6 ins. 10 ins in the ground for 1/4 sec. cor. mark 1/4 on N. face and raised a stone mound alongside.	65.00
		71.00
		80.00
75.00	Hollow drains E. & E.	
80.00	The cor. to secs. 20. 21. 28 & 29. Land. level Soil. 2nd. rate Timber scattering cedars. Dense undergrowth on 80 lks	

August 7th 1883.

BOOK-A-197

399

Subdivisions T. 29 S. R. 4 E.

North bet secs. 20 & 21
Var. 16° 12' E.

17.50 Enter hollow drains N.E.

18.50 Wash 7 ft. deep drains N.E.

31.20 Ascend.

40.00 Small gulch drains S.E. set sandstone 14 x 10 x 6 in 8 ins in the ground for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside.

52.00 Top ridge bears E & W.

65.00 Descend.

71.00 Enter flat

80.00 Set a sandstone 12 x 10 x 6 in 8 ins in the ground for cor. to secs. 16, 17, 20 & 21. marked with 3 notches on S. and 4 notches on E. edges and raised a stone mound alongside, from which a pine 12 ins. diam. bears S. 85 W. 60 lks dist. marked T. 29 S. R 4 E. S. 20 B.T.

Land. mountainous & rolling

Soil. 1st & 2nd rate.

Timber. scattering cedars

Dense artemisia undergrowth

on 80 Chs.

Subdivisions Tp. 29 S. R. 4 E.

	East on a random line bet'w. secs. 16 and 21 Var. 16° 30' E.		
40.00	Set temporary 1/4 sec. cor.		
80.10	Intersect N. & S. line at cor. to secs. 15. 16. 21 & 22 from which I run		
	West on a true line bet'w. secs. 16 and 21	1.50	
11.60	Leave field bears N. & S.	17.85	
21.90	Road bears N.W. & S.E.	18.90	
25.25	Enter field bears N. & S.		
35.00	Leave " "	19.50	
35.75	Ditch runs S.E.	40.00	
36.10	" " "		
40.05	Set a sandstone 12 x 8 x 6 ins 8 ins in the ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.		
50.00	West most cabin in Settlement bears N. 34° E. 18 lks dist	52.00	
	S.E. most " " " " N. 65 1/4 E. 28 " "	77.25	
52.25	Ditch runs S.E.	80.00	
67.30	Wash drains S.E.		
73.00	N. point of spur.		
80.10	The cor. to secs. 16. 17. 20 & 21. Land. level & rolling		

BOOK-A-197

2401

Subdivisions Sec. 29 T. N. R. 4 E.

Soil 1st 3rd rate.
Timber. scattering cedars.
Dense artemisia undergrowth
on. 58.75 Chs.

North betw. 16 & 17
Var. 16° 30' E

1.50 Wash draius N.E.
17.85 Road bears N.W. & S.E.
18.90 Bullberry Creek 4 lks wide, 6 ins deep runs N.E.
19.50 Ascend.
40.00 Set a granit 24×10×10 ins 18 ins in the ground, for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside from which a pine 7 ins diam. bears N 45° W. 30 lks dist. marked 1/4 S. B. T.
52.00 Top of bluff bears N.E. & S.W.
77.25 Gulch 150 ft. deep draius N.W.
80.00 Set a sandstone 10×10×6 ins, 6 ins in the ground for cor. to secs. 8. 9. 16 & 17 marked with 4 notches on N and E. edges and raised a stone mound alongside.

Subdivisions Tp. 29 S. R 46

	Land. mountainous Soil. 3rd rate. Timber. scattering cedars.	
	Mountainous ab 80 Chs.	
	East on a random line betw. Secs. 9 and 16. Var. 16° 30' E.	5.50 10.00 20.00
40.00	Set temporary 1/4 sec. cor.	40.00
80.10	Intersect N. & S. line at cor. to secs. 9. 10. 15 and 16 from which I run (on a true line)	
	West betw. secs. 9 and 16	50.36
35.40	Road bears S.E. & N.W.	56.00
40.05	Set trachyte 15 x 10 x 6 in 10 in in the ground for 1/4 sec. cor. marked with 1/4 on W. face and raised a stone mound alongside.	60.90 77.90 80.00
47.50	Road bears S.E & N.W.	
59.00	Ascend	
64.00	Top of ridge bears S.E & N.W.	
80.10	The cor. to secs. 8. 9. 16 & 17 Land. mountainous & rolling Soil 1st & 2nd rate. Timber scattering cedars.	

Dense artemisia undergrowth on 80. 10 Chs.

North betw. Secs. 8 & 9
Var. 16° 30' E.

5.50	Descend bears S.E & N.W.
10.00	Enter Coverbench
20.00	Wash in hollow drains N.E.
40.00	Set a trachyte 12×12×12 in 8 in in the ground for 1/4 sec cor. marked 1/4 on W. face and raised a stone mound alongside.
50.36	Road bears S.E & N.W.
56.00	Enter Riverbottom N.E & S.W.
60.90	Road bears N.E & S.W.
77.90	Fremont River 50 lks. wide 4 ft. deep flows N.E.
80.00	Set a sandstone 18×10×8 in 14 in in the ground for cor. to Secs. 4. 5. 8 & 9. marked with 5 notches on S. and 4 notches on E edges and raised a stone mound alongside.

Land. level & mountainous
Soil 1st & 3rd rate

BOOK-A

	Timber. scattering cedars	
	Dense artemisia undergrowth	73. 50
	on 80 Chs.	
		76. 63
	East on random line	
	betw. secs. 4 and 9	
	Var. 16° 30' E.	
		80. 00
40. 00	Set temporary 1/4 sec. cor.	
80. 00	Intersect N. & S. line at cor.	
	to secs. 3. 4. 9 & 10. from which	
	I run	
	West on true line	
	betw. secs. 4 and 9	
1. 20	Fremont River 40 lks wide 2 ft deep	
	flows N.	
13. 50	Gulch draius S.	
16. 90	R. bank of fremont river 40 lks wide	
	2 ft. deep	
24. 00	Fremont Riv. 50 lks. wide 2 ft deep runs S.E.	
28. 00	The same 40 " " 2 " " " N.	
31. 00	The same 45 " " 2 " " " S.E.	
36. 90	Road bears N.E & S.W.	
40. 00	Set a trachyte 16 x 10 x 8 in 12 ins in the	
	ground for 1/4 sec. cor. marked 1/4	
	on N. face and raised a stone	

BOOK-A-197

4051

Subdivisions Sec. 29 T. R. 4 E

	mound along side.
13. 50	Fremont river 40 lks. wide 3 ft deep heads W. flows N.E.
16. 63	leave the same 40 lks wide 2 ft deep heads S. W.
80. 00	The cor. to secs. 4. 5. 8 & 9 Land. mostly broken bench Soil 3rate Timber. scattering cedars. Brush underbrush on 80 Chs.

August 8 A 1883.

Note.

The line between secs. 4 & 5 falling in inaccessible bluffs is not established.

Subdivisions Tp. 29 S. R. 4 E.

From the cor. to secs. 31 & 32 on the south boundary of the Tp. formerly set by me I run

North betw. secs. 31 & 32 — 40.00

Var. 16° 12' E. — 80.40

Descend.

40.00 Set a trachyte 14 x 10 x 6 ins 8 ins in the ground for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside.

45.00 Enter thick timber — 17.50

52.50 Dup. Gulch drains N.E. — 24.40

80.00 Set a granit 10 x 8 x 6 ins 6 ins in the ground for cor. to secs. 29, 30, 31 & 32. marked with 1 notch on S. and 5 notches on E edges and raised a stone mound alongside — 28.25

from which — 39.70

A pine 15 ins diam. bears N. 88° E. 55 lks dist. marked T. 29 S. R. 4 E. S 29 B. T. — 40.20

Land. mountainous. — 80.40

Soil. 2nd rate

Timber. pine & cedars.

Mountainous on 80 Chs.

BOOK-A-197

Subdivisions Tp. 29 S. R 4 E.

East on a random line
betw. secs. 29 and 32.
Var. 16° E.

40.00 Set a temporary 1/4 sec. cor.
80 40 Intersect N. & S. line at cor. to secs. 28. 29. 32 & 33 from which I run West on true line
betw. secs. 29 and 32
17.50 Gulch drains N. W.
24.40 3.55 chs. south lake, 2 chs diam.
28.25 Gulch drains W. W.
39.70 Bulberry Creek 5 lks wide 1 ft deep runs N. E. in deep Cañon
40.20 Set a trachyte 14 x 10 x 8 in 10 ins in the ground, for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.
80.40 The cor. to secs 29. 30. 31 and 32.
Land. mountains.
Soil 2nd rate
Timber. cedars & pines
Mountainous on 80. 40 chs

Subdivisions Sp. 29 S. R 4 E.

West on a random line
betw. secs. 30 & 31.
Var. 16° 12' E

40.00 Set a temporary 1/4 sec. cor.

80.55 Intersect West boundary of Sp. at cor. to secs. 30 & 31 formerly set by me from which I run

East on true line
betw. secs. 30 & 31

Ascend

7.50 Mountain top bears N W & S E.

37.10 Road bears N & S.

40.55 Set trachyte 14 x 8 x 6 ins 10 ins in the ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside. bears S W & S E on Ridge

57.00 Ingulch spring branch 5 links wide 3 ins deep. runs N E.

80.55 The cor. to secs. 29. 30. 31 & 32

Land. Mountains.
Soil. 2nd rate.
Timber, scattering cedars.
Mountainous on 80.55 chs

2.50 B
10.50 Le
11.90 De
40.00 Set
in
m
rai
70.00 En
73.70 En
74.55 B
de
75.00 Le
81.00 Se
gr
30
an
ra
al
La
S
C

BOOK-A-197

Subdivisions Tp. 29 S. R. 4 E.

North betw. secs. 29 and 30
Var. 16° 30' E.

2.50	Bottom of ravine 200 ft deep N. E.
10.50	Leave thick timber
11.90	Descend N. W. & S. E.
40.00	Set a trachyte 24 x 12 x 8 ins 18 ins in the ground for 1/4 sec. cor. marked with 1/4 on W face and raised a stone mound alongside.
70.00	Enter thick timber N. W. & S. E.
73.70	Enter canyon bears N W. & S. E.
74.55	Bullberry Creek 5 lks. wide 8 ins. deep runs N. W.
75.00	Leave canyon.
80.00	Set a granite 14 x 10 x 6 ins 8 ins in the ground for cor. to secs. 19. 20. 29 & 30 marked with 2 notches on S. and 5 notches on E. edges and raised a mound of stones alongside.

Land. Mountainous
Soil. 3rd rate.
Timber scattering cedar & pine
Dense undergrowth on
20 chs

Subdivisions Sec. 29 & R 4 E

East on a random line
betw. secs. 20 and 29
Var. 16° 30 E.

40.00	Set a temporary 1/4 sec. cor.
79.60	Intersect N & S. line 30 lks E. at cor. to secs. 20. 21. 28 & 29 from which I run S. 89° 57 W. on a true line betw. secs. 20 and 29
	Ascend.
14.50	Gulch drains N E.
37.50	Top of ridge bears N. W. & S. E.
39.80	Set a trachyte 10 x 8 x 6 in. 6 ins in the ground for 1/4 sec. cor. mark 1/4 on N face and raised a stone mound alongside from which a pine & juniper bears N 65° W. 27 lks. marked 1/4 S. B. T.
	Then along N. side of canyon.
79.60	The cor. to secs. 19. 20. 29 & 30.
	Land. Mountainous
	Soil 2nd. rate
	Timber, scattering cedars & pine
	Dense undergrowth on 79.60

August 9th 1883

40.00	Set
80.60	Inte
	37 l
	for
	wh
40.60	Set
	the
	1/4
	m
45.00	R
60.89	A
71.25	En
72.90	Be
	dec
74.00	Co
80.60	Th
	La
	So
	Ti
	D

BOOK-A-197

Subdivisions Tp. 29 S. R 14 E.

West on random line
betn. secs. 19 and 30
Var. 16° 30' E.

40.00 Set a temporary 1/4 sec. cor.
80.60 Intersect Westboundary of Tp.
37 lks. S. of cor. to secs. 19 & 30
formerly set by me, from
which I run
S. 89. 44 E. on true line
betn. secs. 19 and 30.
40.60 Set granite 24 x 12 x 6 ins 18 ins in
the ground for 1/4 sec. cor. marked
1/4 on N face and raised a stone
mound alongside.
45.00 Ridge N E & S W.
60.89 A pine 20 ins. diam
71.25 Enter canyon
72.90 Bullberry Creek 4 lks. wide 6 ins
deep runs N. E
74.00 Ascend.
80.60 The cor. to secs. 19. 20. 29 & 30.
Land: mountainous
Soil 3rd rate
Timber scattering cedars & pine
Dense undergrowth on 80.60 Ch.

Subdivisions Sp. 29 S. R. 4 E.

North betw. secs. 19 and 20
Var. 16° 30' E.

12.50	Enter canyon
15.00	Bullberry Creek 4 lks wide 10 ins deep runs N.E.
17.70	Road bears S. W. & N. E.
37.00	Ascend
40.00	Set a trachyte 15×12×6 ins 10 ins in the ground for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside.
49.50	Gulch drains S. E.
80.00	Set a trachyte 24×20×10 ins 18 ins in the ground for cor. to secs. 17, 18, 19 & 20 marked with 3 notches on S and 5 notches on E edges and raised a stone mound alongside.

Land. mountainous
Soil. 3rd rate
Timber. scattering pines & cedars
Dense undergrowth on all lks.

40.00	
80.70	
3.50	
15.00	
22.50	
24.25	
24.50	
25.50	
40.35	
80.70	

BOOK-A-197

413

Subdivisions Tp. 29 S. R 4 E.

East on randomline
betw. secs. 17 and 20
Var. 16° 30' E.

40.00 Set a temporary 1/4 sec. cor.

80.70 Intersect N. & S. line 24 lks. N. of cor. to secs. 16. 17. 20 & 21 from which I run

N 89° 50' West on true line
betw. secs. 17 and 20

3.50 Ascend bears N. & S.

15.00 N. E. spur of ridge

22.50 Enter canyon bears N E & S. W.

24.25 Road bears N E & S. W.

24.50 Bullberry Cr. 4 lks. wide 10 ins deep runs N E.

25.50 Ascend

40.35 Set a sandstone 14 x 6 x 6 ± 9 ins in the ground for 1/4 sec. cor. marked 1/4 on N. face and raised a stone mound alongside from which a pine 9 ins diam bears N. 65° W. 46 lks. dist. marked 1/4 S. B. T.

80.70 The cor. to secs. 17. 18. 19 & 20.
Land. mountainous.
Soil 1st & 2nd rate
Timber. scattering cedars

Subdivisions Tp. 29 S. R 4 E

Dense artemisia undergrowth on 80 Chs.

West on a random line
betw. secs. 18 and 19
Var. 16° 30 E.

40.00 Set temporary 1/4 sec. cor.

80.40 Intersect W. boundary of Tp. at cor. to secs. 18 and 19 formerly set by me, from which I run

East on true line
betw. secs. 18 and 19

Ascend

40.40 On ridge bears N E & S E set sandst. 14 x 10 x 6 in. in the ground for 1/4 sec. cor. marked 1/4 on N face & raised a stone mound alongside

80.40 The cor. to secs. 17, 18, 19 & 20.

Land mountainous.
Soil 3rd rate.
Timber scattering cedars.
Dense undergrowth on 80. 40 Chs.

29.00
36.50
40.00
53.50
80.00
40.00

BOOK-A-197

Subdivisions Sec. 29 T. 2 N. R. 4 E.

North betw. secs. 17 and 18
Var. 15° 30 E.

Record

29.00 Top of slope bears N E g. S. Pf.

36.50 Gulch drains N.E.

40.00 Marked ledge of sandstone, for 1/4 sec. cor. 1/4 facing the W. and raised a stone mound alongside.

53.50 Ridge bears N E g S. Pf.

80.00 Set a trachyte 14 x 10 x 8 in. 10 in in the ground for cor. to secs. 7, 8, 17 & 18 marked with 4 notches on S. and E. on E edges and raised a stone mound alongside.

Land mountains
S. L. 3rd rate.
Timber scattering cedars & pines.
Brush artemisia under-growth on 80 chs.

August 10th 1883.

East on random line
betw. secs. 8 and 17.
Var. 16° 30' E.

40.00 Set temporary 1/4 sec cor.

Subdivisions Tp. 24 S. R 4 E

80.15	Intersect N. & S. line at cor. to secs. 8. 9. 16 & 17. from which Sun West on true line betw. secs. 8 and 17.
4.50	Gulch draines N W, ascend
18.00	Top of bluff
30.00	Descend
35.00	Gulch draines N E.
40.07	Set a trachyte 14×8×6 in 10 ins in the ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.
52.00	Ridge bears N E & S W.
80.15	The cor. to secs. 7. 8. 17 & 18. Land. Mountains Soil 2nd rate. Timber. scattering cedar & pine Dense artemisia undergrowth on 80.15 Chs.

West on a random line betw. 7 and 18. Var. 16° 30 E.

40.00	Set temporary 1/4 sec cor.

Subdivi

40.30	Int
	38
	wh
	Sun
	2 Na
	Stone
	fro
7.50	lea
24.30	Gu
37.50	
40.30	Set
	the
	1/4
	m
	a
49.50	Gu
80.30	The
	La
	So
	Tim
	Di

Subdivisions Tp. 29 S. R. 4 E.

40.30	Intersect West boundary of Tp. 38 lks. S. of cor. to secs. 7 & 18 which is a sandstone 20 × 20 × 5 firmly set in the ground, marked 2 Notches on N. & 4 on E. edges, with stone mound alongside. — from which Spruce S. 89. 44 E. on true line betw. secs. 7 and 18
7.50	leave Rabbit Valley, ascend
24.30	Gulch draines S. W.
37.50	" " "
40.30	Set trachyte 15 × 10 × 8 in 10 ins in the ground for 1/4 sec. cor. marked 1/4 on N. face and raised a stone mound along side from which a pine 10 ins diam bears N 38° W 17 lks dist. marked 1/4 S. B. T.
49.50	Gulch draines N.
60.30	The cor. to secs. 7. & 17 & 18. Land. mostly mountains Soil. 3rd Rate. Timber. scattering cedars Dense undergrowth on 60.30 Ch.

Subdivisions Tp. 29 S. R. 4 E

North betw. secs. 7 and 8.
Var. 16° 30' E.

Ascend

16.00 Rid. bears E & W.

26.00 Gulch draws N.W.

40.00 In gulch draws N.W. set trachyte 36 x 20 x 10 in. 24 ins in the ground, for 1/4 sec. cor. marked 1/4 on W. pc and raised a stone mound alongside.

48.50 Enter bottoms.

58.15 Road bears E & W.

62.95 Enter cultivated land

70.00 leave same

80.00 Set sandstone 16 x 8 x 5 ins 12 ins in the ground for cor. to secs. 5. 6. 7 & 8 marked with 5 notches on land E. edges and raised a stone mound alongside.

Land. mountainous & level
Soil. 2nd & 1st rate.
Timber. scattering cedars on mound
Mountainous on 48.50 chs.

40.00

80.00

40.00

52.00

79.30

80.00

BOOK-A-197

Subdivisions Tp. 29 S. R. 4 E.

East on a random line
betw. secs. 5 and 8.
Var. 16° 30' E.

40.00 Set a temporary 1/4 sec. cor.

80.00 Intersect N. & S. line at cor. to secs. 4. 5. 8 & 9 from which I run

West on true line
betw. secs. 5 and 8.

Along broken slope of bluff

40.00 Set a sandstone 18 x 10 x 7 in. 12 ins. in the ground for 1/4 sec. cor. marked 1/4 on N. face and raised a stone mound alongside.

52.00 Enter flat bears N. W. & S. E.

79.30 ~~Fragment River 66 lks. wide 2 ft. deep N. & S.~~

80.00 The cor. to secs. 5. 6. 7 & 8.

Land. mostly broken bluffs

Soil. 3rd rate.

No timber.

Mountainous on 52 chs.

Dense undergrowth on 28 chs.

Subdivisions Tp. 29 S. R 4 E.

West on random line
betw secs. 6 & 7.
Var. 16° 30 E.

40.00 Set temporary 1/4 sec. cor.

30.40 N & S ect W. boundary of Tp.
28 lks. south of cor. to secs. 6,
which is a Trachyte 12x10x10, firmly set
in the ground, marked one Notch on N.
or S. edges with pits and mound
from which Trees
S. 89. 48 E on true line
betw. secs. 6 & 7.

7.00 Enter field bears N & S.

12.75 Leave same

20.75 Road bears N W & S. E.

25.00 Wash drains S. E.

29.00 Leave Rabbit Valley, ascend.

40.40 Set a trachyte 40x20x10 in. 20 in
in the ground for 1/4 sec. cor. marked
1/4 on N. face and raised a stone
mound alongside.

63.00 Enter flat

79.50 Fremont River 50 lks. wide 2 ft. deep
heads S. W.

80.40 The cor. to secs. 5. 6. 7 & 8.
Land. level & mountains

Subdivis

Sou
No
De

40.00 Set
80.00 Int
at
set
m

21.50 Ri
40.00 Set
in
m
sa
sti

62.00 Top
dee
Gen

BOOK-A-197

Subdivisions Tp. 29 S. R. 4 E.

Soil. 1st & 3rd rate
No timber.
Dense artemisia undergrowth
on 7th 60 Chs.

North on random line
betw. secs. 5 & 6.
Var. 16° 30' E.

40.00 Set temporary 1/4 sec. cor.

80.00 Intersect N. boundary of Tp.
at cor. to secs. 5 & 6. formerly
set by me from which I
run

South on true line

21.50 Ridge Spur 150 ft high bears E & W.

40.00 Set a sandstone 14 x 10 x 8 in
in the ground for 1/4 sec. cor.
marked 1/4 on W. face and
raised a stone mound along-
side.

62.00 Top of bluff 250 ft high, perpendicular
descend.

George W. Carrol house bears
S. 37 3/4 E. 30 Chs. dist.

G. C. Carrol house bears
S. 34° E. 35 Chs. dist.

Subdivisions Tp. 29 S. R. 4 E.

	Heath's Mill bears S. 37 3/4 W. 37 Chs. dist.
68.00	foot of bluff E enter Dense undergrowth on bottom
69.00	2 pine 10 in diam.
79.40	Fremont River 50 lks wide 6 ft deep runs S. E.
80.00	The cor. to Secs. 5. 6. 7. & 8. Land mostly mountains Soil 3rd & 4th rate. Timber a few scattering cedar Mountainous & Dense undergrowth on 80 Chs.

August 11th 1883.

Gener

This
vall
or
por
vall
Riv
stre
sett
par
par
15.
The
The
mi
of
gra
per
lan
by

Au

BOOK-A-197 423

General Description

This Tp. embraces a small valley lying S. E. of Fremont or Rabbit Valley and a small portion of the last named valley. It is watered by Fremont River and several smaller streams. There is a small settlement of about a dozen families in sec. 16. whose farming lands lie in secs. 15. 16. 21 & 22.
There is a grist mill in sec 7.
The applicants improvements are mostly in sec. 7 & 8 and consist of a log house, stable and granary, also a corral and considerable fencing. He has considerable land under cultivation, irrigated by a canal from Fremont River.

Augustus A. F. Ferron
U. S. Dep. Surv

BOOK-A-147

[4.—LIST OF NAMES.]

A list of the names of the individuals employed by A. D. Perron *United States deputy surveyer, to assist in running, measuring, and marking the lines and corners described in the foregoing field notes of the survey of* the Extensions and Subdivisions of T. 1 S. R. 4 E.

of the Salt Lake base and meridian in the Territory of Utah, showing the respective capacities in which they acted.

William Kayser, *Compassman.*

James Leatt, *Chainman.*

W. Burgess, *Chainman.*

....., *Chainman.*

....., *Chainman.*

C. F. Carroll, *Axeman.*

....., *Axeman.*

....., *Flagman.*

BOOK-A-197

[5.—FINAL OATHS OF ASSISTANTS.]

We hereby certify that we assisted Augustus D. Ferron *United States deputy surveyor, in surveying all those parts or portions of the* Exteriors and subdivisions of Tp. 29 S. R. 4 E.

of the Salt Lake base and meridian in the Territory of Utah, as are represented in the foregoing field notes as having been surveyed by him and under his direction; and that said survey has been in all respects, to the best of our knowledge and belief, well and faithfully surveyed, and the corner monuments established according to the instructions furnished by the United States surveyor-general for Utah.

William Rader, **Compassman.**

James Heath, **Chainman.**

W. Burgess, **Chainman.**

....., **Chainman.**

....., **Chainman.**

E. H. Cossett, **Axeman.**

....., **Axeman.**

....., **Flagman.**

Subscribed and sworn to before me this 11th *day of* August *188*3.

A. D. Ferron

U. S. Dep. Surv.

BOOK-A-197

[6.—FINAL OATH OF UNITED STATES DEPUTY SURVEYOR]

I, Augustus D. Simon, United States deputy surveyor, do solemnly swear that in pursuance of instructions received from Ed. Solomon, United States surveyor general for Utah, bearing date of the 5th day of July, 1883, I have well, faithfully, and truly, in my own proper person, and in strict conformity with the instructions furnished by the United States surveyor general for Utah, the surveying manual, and the laws of the United States, surveyed all those parts or portions of Extensions and Subdivisions of T. 29 S. R 4 E.

of the Salt Lake base and meridian in the Territory of Utah, as are represented in the foregoing field notes as having been surveyed by me and under my directions; and I do further solemnly swear that all the corners of said survey have been established and perpetuated in strict accordance with the surveying manual, printed instructions, the special written instructions of the United States surveyor general for Utah, and in the specific man-

ner described in the field notes, and that the foregoing are the **TRUE** *field notes of such survey; and, should any fraud be detected, I will suffer the penalty of perjury, under the provisions of an act of Congress, approved August 8, 1846.*

Augustus D Gunn

United States Deputy Surveyor.

Subscribed and sworn to before me this 5th *day of* November *1883.*

Edward Michaelis

Notary Public

B

U. S. SURVEY

Salt Lake

The foreg

Township No.

Executed by

Under No

day of

July 2nd

amined, the nece

the said field

hereby approved

BOOK-A-197

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, November 5th, *1883.*

The foregoing field notes of the survey of the

Subdivisions

Township No. 29 South *Range No.* 4 East

Executed by Augustus G. Ferron

Under No 117 *contract of the* 5th

day of July *1883, in the months of*

July and August *1883, having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

Fred Salsbury

U. S. Surveyor General for Utah.

BOOK-A-197

1/2

REPORT: 1884

Filed 188

Examined by .....

Transcribed by .....

Compared by J. A. Mitchell & L. M. Hickocks

FIELD NOTES

& Re-survey

OF THE SURVEY OF THE

North and West boundaries and
survey of South & East boundaries

OF

Township No 9 South

Range No 3 East

OF THE

SALT LAKE MERIDIAN.

IN

UTAH TERRITORY,

AS SURVEYED BY

Ernst H. Kesse

U. S. Deputy Surveyor,

Under his Contract No. 118

Dated July 5 1883

Survey commenced Sept 25 1883

Survey completed Nov. 1st 1883.

V

BOOK-A-197

Township 9 South R. 3 East



[2.--PRELIMINARY OATHS OF CHAINMEN.]

We Joseph Kerr, Jacob Hatfield, Joseph Adamson and Albert Babcock

do solemnly swear that we will well and faithfully execute the duties of chain carriers; that we will level the chain upon even and uneven ground and plumb the tally pins, either by sticking or dropping the same; that we will report the true distance to all notable objects, and the true length of all lines that we assist in measuring, to the best of our skill and ability, and in accordance with instructions given us, in the survey of the Guide Meridian, Standard, Exterior Subdivisions of Tps 9 S. Rs 3 & 4 E and Tp 10 S R 3 East

of the Salt Lake base and meridian in the Territory of Utah.

Joseph Kerr, Chainman.

[illegible], Chainman.

Joseph Adamson, Chainman.

Albert Babcock, Chainman.

Subscribed and sworn to before me this 23rd day of September 1883

E. A. Bless

U. S. Dep. Surveyor

BOOK-A-197

[3—PRELIMINARY OATH OF AXEMEN.]

I, James Angus

and

do solemnly swear that we will well and truly perform the duties of axemen, in the establishment of corners, and other duties, according to instructions given us, and to the best of our skill and ability, in the survey of the Guide Meridian Standard, Exteriors & Subd. of Tps 1 & 2 N. R 3 E & Tp 10 S. R 3 E

of the Salt Lake base and meridian in the Territory of Utah.

James Angus, Axeman.

, Axeman.

Subscribed and sworn to before me this 23 day of September 1883

E. A. Ross

U. S. Dep. Surveyor

BOOK-A-197

[3 — PRELIMINARY OATH OF AXEMEN.]

I/We, John T. Moore

~~and~~

do solemnly swear that we will well and truly perform the duties of axemen, in the establishment of corners, and other duties, according to instructions given us, and to the best of our skill and ability, in the survey of the Guide Meridian, Standard, Exteriors & subdivisions of Tps 9 South Rs 3 & 4 East & T 10 S Rs 3 East

of the Salt Lake base and meridian in the Territory of Utah.

John T. Moore, Axeman.

~~, Axeman.~~

Subscribed and sworn to before me this 23rd day of September 1883

E.W. Ross

U.S. Dep Surveyor

BOOK-A-197

[1—PRELIMINARY OATH OF ~~COMPASSMAN~~ Flagman.]

I, F. M. Gordon

do solemnly swear that I will well and truly perform the duties of ~~compassmen~~ Flagman, according to instructions given me, and to the best of my skill and ability, in the survey of the Guide Meridian Standard, Exterior & Subdivisions of Tps 9 S. Rs 3 & 4 East & Tps. 10 S. R 3 East

of the Salt Lake base and meridian in the Territory of Utah.

F. M. Gordon, ~~Compassman~~ Flagman.

Subscribed and sworn to before me this 23d day of September 1883.

[illegible]

U. S. Dep. Surv.

BOOK-A-197 424 1

North boundary T. 9 S. R 3 E.

Survey commenced Sept 25/83. with a Gurley Solar compass. Note. Begin at a point which was shown me by various parties living on the ground as being the cor. to secs. 26, 25, 32, 33 on T. 8 S. R 3 E. where I found a cedar st. 14 x 10 x 4 in without marks. From this I run South one mile and 20 ct 2 miles and 20 lks. to the cor. to Tps. 8 & 9 S. R 2 & 3 E. which I found marked with 6 notches on N. & E. sides being a sandstone 14 x 10 x 8 in. To further perpetuate this point I here set a cotton wood post 4 ft. long 4 in square for cor. to secs. 1. 6. 31, 36. marked with 6 notches on N. & E. sides, dug pits 2 ft 18 x 12 in. in each sec. and raised a mound of earth 2 1/2 ft high. 5 ft. here around it.

4251

North boundary

From the cor. to Secs.
T. R. 2 & 3 E. thus es
by me from East
on true ~~magnetic~~ line
between Secs 6 & 5
Var. 16° 40' E.

9.42 Road to E. Colton house bears
28.00 Ditch drs. westerly
40.00 Set cobblestone 12 x 8 x 6 i
the ground for 1/4 sec. cor. m
1/4 on N face and raised a st
mound alongside Mitra
45.50 Road bears N W & S E.
48.50 " " "
47.00 Ditch drs N W.
80.00 Witness pit cor. set cobbl
14 x 10 x 4, 9 i in the ground
cor. to secs. 5. 6. 31 & 32 mar
with 5 notches on E and 1
edges and raised a stone m
alongside.
Land. gently rolling
Soil N W Fair
Timber
Trees and growth on 80.

BOOK-A

BOOK-A-197 426

T. 9 S. R. 3 E.

Eastern Oregon
Base on true line
Intro. secs. 5 and 32
Var. 16° 40' E.
Road bears N ½ p. 16.
Ditch drained
Cedar stake 13 x 10 x 8. 8 in
the ground for ¼ sec. cor. marked
W on N face and raised a stone
mound alongside No trace of old
cor.
Old Road bears N ½ p. 16.
Salem canal 10 lks, wide runs S. ½ p.
Road bears W ½ p. W.
Second high bench bears W ½ p. W.
No trace of old cor. set limestone
12 x 8 x 5 8 in in the ground for
cor. to secs. 4. 5. 32 & 33 marked
with 4 notches on E & end 2 on W
edges and raised a stone mound
alongside.
Land mostly rolling bench
Soil. 1st rate.
No timber
Remeasured north on 32. Chs.
Septr. 25th 83

427

North boundary

BOOK A.

Note. On the ~~north~~ right to Sept. 8
Taken observation of Polaris
and find my instrument
in good adjustment giving
a variation 16° 40' E.

resurvey
Easterly true line
between secs. 4 & 33
Var. 16° 40' E

	Along N. side of high mountain	26. 00	Descend
40 00	to trace of old Cor. set stone	28. 00	Comm
	16 x 8 x 4, 12 in the ground, for		mon
	1/4 sec. cor. marked 1/4 on	40. 00	to tra
	and raised a stone mound		16 x 8
	alongside.		1/4 sec.
57. 00	End of old survey, no trace of		Spru
	old Cor.	53. 00	Spru
75. 00	Descend into Wells cañon down		Spru
	northerly	58. 00	Witn
78 00	Pine trees 2 in Sp. 8 in.	61. 00	Spru
80. 00	Set sandstone 12 x 8 x 5, 9 in in the		mon
	ground for Cor. to sec. 3 & 4, 33 & 34 mi	69. 00	"
	with 3 notches on E & W. edges and rais		mon
	a stone mound alongside.	91. 00	On ro
	Land mountainous		stone

BOOK A-197

T. 9 S. R. 3 E.

Sail. 2nd rate.
All timber.
Mountainous & dense
undergrowth 80 chs.

East on this line
bttn. secs. 3 & 5 ±
Var. 16° E.

26.00 Descend
28.00 Commence recovery of old line
run from the E. but no trace of old cor.
6.00 No trace of old cor. set sandstone
16 × 8 × 4. 12 ± in the ground for
¼ sec. cor. marked ¼ cor. 4 pits
& pointed stone mound alongside.
53.00 Spanish fork creek 40 lks wide
& 4 feet deep. Runs N. W.
58.00 Ditch 15 lks wide runs N. W.
61.00 Spanish fork Creek 75 lks wide 2 feet deep &
runs N. W.
66.00 " " " "
runs N. W.
80.00 On road embankment set stone
stone 20 × 16 × 4 ins, 8 ins in the

North boundary

ground for cor. to secs 2. 3. 34 & 35
marked with 2 notches on E and W sides and raised a stone mound alongside.
Rky. hilly mountainous
Soil 1st Rate.
No timber.
Dense undergrowth Willows.

Survey
East on true line
Retro. sec. 2 and 35
Var. 16° 40' E.

00.50 Road bears N.W. & S.E.
1.50 Denver & Rio Grande R.R. bears N.W. & S.E.
2.00 Rocky Grade access steep mountain
35.00 Gulch draining S.W.
40.00 Witness old cor. set stone 18 x 10 x 8, in the ground for 1/4 sec. cor. marked 1/4 on 4 faces raised a stone mound alongside.
45.00 Ridge bears N.E. & S.W. descend
55.00 Gulch draining S.W. ascend
61.00 Intersect old survey cor.
80.00 Set a stone 15 x 11 x 5, in the ground for cor to secs. 1. 2. 35 & 36 marked with 1 notch on E and 5 on W faces stone mound alongside

BOOK-A-197

Sept. 1902

Sand. high rocky mountains on 78 1/4
Soil Lind rate.
Timber.
Dense undergrowth 80 chs.

Note. Unaccount of inaccessible mountains Sabaudon line here.

Sept 4th. 26th 83.

431

Westhaven day Sp.

From the cor. to Sps. & 9 Ch. R
E. reestablished by me Jan
on resurvey
South Returned Ch. 81
Var. 16° 45' E.

4.00 Road bears N. W.
6.00 " " "
8.50 " " E & W.
22.00 Ditch drains W.
29.30 Enter narrow field extends E. 1 ch.
to Ditch
31.50 Leave field enter high bench
40.00 Found cobblestone 17×10×6
lying on ground marked 1/4
which I reset 11. deep for 1/4 M
cor. marked 1/4 on W face.
dug pits 18×18×12. N & S. 5 1/2 ft dist
raised a mound of earth 1 1/2 ft high
2 ft base along line.
58.30 Road bears E & W.
59.00 Ditch drains W.
66.80 Enter small field bears E & W
72.00 Leave field road bears E & W
Enter oak brush
76.90 Road bears E & W.
80.00 Set lime stone 16×10×10. 18 in

BOOK-A-

South

in th
J & B.
N 2
pits
5 1/2
of ear
Lar
Sa
No
Ba
7.00 Ditch
10.35 Sal
18.00 A co
19.00 Roa
22.00 "
36.60 "
40.00 Fou
wh
a co
4 in

BOOK-A-197

South R. 3 East.

in the ground for cor. to secs. 1. 6.
7 12. marked with 1 notch on
N and S sides and dug
pits 18 x 18 x 12 in. in each dir.
5 1/2 ft. dist. and raised a mound
of earth 2 ft high 4 1/2 ft. base along road
At Witness of old Cor.
Land. Level
Soil. 2nd rate.
Timber.
Pine undergrowth 12. 10 in.

South ~~ketu~~ on resurvey Land 12 X
Var 16° 45' E.

7.00 Ditch runs W.
15.35 Salem ditch 20 ft wide runs E. W. Enters higher bank
18.00 A corner on E side of line
19.00 Road bears N W & S E.
22.00 " " " "
26.60 " " E & W.
40.00 Found point of original cor.
which I perpetuate by setting
a cottonwood post whence point
of intersection 3 ft. long, 2" in in the

West boundary

ground for 1/4 sec. cor. marked 1/4 S on W face, 4 dug pits 18×18×12 N & S. 5 1/2 ft dist. and raised a mound of earth 1 1/2 ft high 3 1/2 ft base around

42.06 Road bears W. & E.

80.00 Enter high rolling bench

80.00 No trace of old Cor. yet observed. 4 ins square 4 ft long. cottonwood post 12 ins in the ground for cor to secs. 7. 12. 13 & 18 marked with 2 notches N & S on S. edge, dug pits 18×18×12 ins in each section 5 1/2 ft. dist. raised a mound of earth 2 ft high & 4 ft base around it also marked T 9 S R 2 E. S 7 on N S 18 on E

Land. Level

Soil 2nd rate.

No timber.

Dense undergrowth on 80 ch

X

South bet. secs. 13 & 18 on boundary

Var. 16° 45' E.

40.00 No trace of old cor. set charred oak post 3 ins diam. 3 ft long for 1/4 sec. cor. marked 1/4 W face, dug pits 18×18×12

H 254

T. 9 S. R 3 E.

W. ¼ S 5 1/2 dist. & raised a mound of stone 1½ ft. high 3½ ft. at base around it.

53.50 Road bears N ½ pt E.

57.50 " " W ½ S E.

75.00 Access

80.00 Witness cor. set cobble stone 15 x 7 x 5 in. in the ground for cor. to sec. 13. 18. 19. 24 marked with 3 notches on S. edge and raised a stone mound alongside. Land high rolling brush Soil & rocks. No timber. Down undergrowth on 80 ch.

South bet. secs. 19 and 24 Var. 16.° E

80.00 No trees or bearings, set a standstone 12 x 9 x 5 in. in the ground for ¼ sec. cor. marked ¼ on W. face & raised a stone mound alongside. End of old survey.

80.00 Set hard stone 12 x 12 x 4 in. in the ground for cor to secs. 19. 24. 25 & 30. marked

12 Weathaunday 1885

with 4 notches on 4 and 2 on
2 edges and raised a stone
mound alongside.
Land. mountains
Soil 2nd rate.
No timber.
Mountains p down under snow
on 81 chs.

South betw. secs. 25 p 30.
Var. 16° 45' E.

40.00 Road bears. E p N.
set sandstone 18 x 14 x 8, 12 in
the ground for 14 sec cn marked
W on W face dug pits 18 x 18 x 12 in
Up d. 5 1/2 ft dist. and raised a
mound of earth 1 ft high
3 1/2 feet bar alongside it.
60.00 Ascend steep mountain side.
80.00 Set sandstone 17 x 10 x 4 in 12 in in the
ground for cn to secs. 25. 30. 31 p 36
marked with 5 notches, and on 2 edges
and raised a stone mound alongside
Land. mountains
Soil. 2nd rate.

BOOK-A-197

Mt. 9, S. R 96

Mt Number.

Mountainous, adjacent underground workings on 80 Ls.

Note. On account of unavailable mountain abandon line here.

Septbr. 29th 83.

East boundary T. 9

Beginning at the cor. to secs
1. 6. 7 & 12. Established by me
from Subdivision Line
being a limestone 18 x 9 x 6 ins.
set in the ground, marked 1/4
on N & S sides, with stone
mound alongside. I saw
South 10 links to
Var. 16. 40' E.

Descend
18.00 Ascend
22.00 Descend
40.00 Set sandstone 15 x 12 x 6 ins.
in the ground for sec. cor. marked
1/4 on W face and raised a stone
mound alongside.
Enter cañon
74.00 Cañon road bears N. W. & S. E.
76.00 D. & R. G. R. R. bears N. W. & S.
76.50 Enter Hyram L. Sterling's field
86.00 Set sandstone 18 x 12 x 6 ins. 12
in the ground for cor. to secs.
1. 12. 13 & 18 marked "R" as before
N. & S. sides and raised a
stone mound alongside.
Land. Mountainous level

South R. 3 East

Soil. 2nd & 1st rate.
No timber.
Mountainous & clean underwood
on 76.50 chs.

South bdrs. secs. 13 & 18.
Var. 16° 40 E.
Clear field, Spanish fork creek
50 lks wide 2 fks deep runs N.W.
ascend steep mountains.
Ridge bears. E & W. descend
Set standstone 16 x 8 x 4. 11 in in ground for 1/4 sec. Cor. marked
1/4 on W face and raised a stone
mound alongside. ascend.
Set standstone 20 x 10 x 5 in
15 in in the ground for cor to secs
13. 18. 19. 24 marked with
3 notches on S edge and
raised a stone mound along-
side.
Land mostly mountainous,
Soil. 2nd rate.
No Timber.

439

Mountainous ground
underbrush 75 cts.
Septr. 27th 83.

Note. On account of mountains Abandoned here.

Note. For general description see Subdivisions of this.
F.

Ernst H. Hess
U. S. Dep. Surv.

Grou
East

27.00 Fork
rugo
4.00 Set
grou
1/4 ou
mou
6.00 Set
the gro
mark
Wedg
alway
L
S
6
Dis

Note.
inacc
line
For
of this

BOOK-A-197 440 216

South Boundary Tp 9 S R 3 E

From the cor to Tps 9 & 10 S R 3 E
East 1 mile
West on true line
bet Secs 1 & 36
Var 16° 40' E
27.00 Fork of crab creek 5 lks wide
runs S E
40.00 Set limestone 14 x 10 x 8, 9 in in
ground for 1/4 Sec corner marked
1/4 on N face and raised a
mound of stones alongside
80.00 Set limestone 29 x 12 x 6, 20 in. in
the ground for cor to Secs 35 & 36
marked with 1 notch on E & 5 on
W edges and raised a stone mound
alongside
Land high Mountainous
Soil 2nd rate
No timber
Dense undergrowth on 80 chs.
Nov. 1st 1883

Note: On account of high ~~mountains~~
inaccessible Mountains I abandon
line here

For Gen'l description see subdivision
of this Tp.

Ernest H. Hease
U. S. Dep Surveyor.

BOOK-A-197

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, February 4th 1884.

The foregoing field notes of the survey and re-survey of the North & West Bounds. & Survey of South & East Bounds.

Township No. 9. South Range No. 3. East

Executed by Ernest N. Hesse.

Under 118 contract of the Fifth

day of July 1883, in the months of

Sept & Nov 1883, having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.

Fra Salomon

U. S. Surveyor General for Utah.

BOOK-A-197

REPORT: 1884

Filed 188

Examined by .....

Transcribed by E Mickaelis

Compared by J. A McKinnon & E Mickaelis

FIELD NOTES

OF THE SURVEY OF THE

Subdivisions of the Fractional

OF

Township No 9 South

Range No 3 East

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Ernest H. Heese

U. S. Deputy Surveyor,

Under his Contract No. 115

Dated July 5th 1883

Survey commenced Septr 27th 1883

Survey completed October 5 1883

BOOK-A-197

1441

Subdivision T. 9 S. R 3 E.

Survey commenced Sept 27. 83

From the cor. to secs. 1 & 2 on S. boundary of this T. previously set by me I run

South 80 rds. to 1/4 s.

Var. 16° 40' E.

Reserved

N. on Set limestone 18 x 12 x 5. Pile of stone on ground for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside.

E. on Set limestone 28 x 10 x 8. Pile of stone on ground for cor. to secs. 1. 2. 11 & 12. marked with 5 notches on S. and 1 on E edges and raised a stone mound alongside.

Land. Steep mountains.

Soil 2nd rate.

No timber.

Brush under growth in places.

Subdivisions Sp. of S. & R.

Note The Eastboundary of this
not being run
East on true line
betw. secs. 1 & 12.
Var. 16°.40' E.

Ascend.

40.00 Set sandstone 24×5×3. 18 in
the ground for 1/4 sec. cor. ma
1/2 on N. face and raised a stan
mound alongside.

80.00 Set limestone 18×9×6. 12
in the ground for cor. to secs.
1. 6. & 12. marked with 1 notch
on 4 and 5 on edges and ra
a stone mound alongside.
Laid. mountainous
Soil 2nd rate
No timber.
Done underground on 8th

Sept. 27th 83

From the cor. to secs. 1. 2. 11 &
previously established South
South betw. secs. 11 &
Var. 16°.40' E.

Subdivis

2.00 Rece
4.00 D. S
4.50 Qua
6.00 Spa
2 pi
40.00 Set
in th
mak
a sta
46.00 Rece
60.00 Lay
80.00 Set
in th
12. 13
on 4
a sta
Lai
Sa
On
Dec

Ea

BOOK-A-197

443

Subdivisions Sec. 1 T 23 E

2.00 Descend of bench
4.00 S. & R. G. R. W. bears N 44° E.
4.50 Road
6.00 Spanish fork Creek bears
2 poles runs N. W. ascend
4.00 Set sandstone 20×10×8. 15 a
in the ground for 1/4 sec. cor.
marked 1/4 on W. face and raised
a stone mound alongside.
46.00 Descend
60.00 Large pine gulch down S. E.
80.00 Set limestone 25×12×6. 20 a
in the ground for cor. to secs. 11.
12. 13 & 14 marked with 4 notches
on S and 1 on E edge and raised
a stone mound alongside.
Large mountains
Said 2nd date
No timber
Dense undergrowth on Hills.

East on meridian line
betw. secs. 12 & 13.
Var. 16° 40' E

Subdivisions T. 9 S. R. 3 E.

40.00 Set temp. 1/4 sec. cor.
80.00 Intersect East boundary of
Sp. at cor. to secs. 12 & 13 T. 9 S.
sect by me from which
run
West on true line
bet'n secs. 12 & 13
with same var.
10.00 Reach field enter dense undergrowth
12.00 Spanish Fork Creek 50 lks wide 2
deep runs N. W. accord
40.00 Set limestone 2 x 4 x 10. 18 ins
in the ground for 1/4 sec. cor.
marked 1/4 on N face and rais
a stone mound alongside.
48.00 enter Valley
50.00 Road runs NE & SW
56.50 Wash draws NE. in Pole Cañon
58.00 Road in Pole Cañon runs NE & SW
65.00 Dense pine & cedar draws S.
80.00 The cor. to secs. 11. 12. 13 & 14.
Land mountainous
Soil 2nd & 3rd rate
No timber.
Some undergrowth [illegible]

BOOK-A

Subdivisi

Note.
On ac
unu
chan

From
on Ea
sect

40.00 Set s
in the
mar
rais
Land
Soil
No
Ben

Note.
On ac
mou
pine

BOOK-A-197

Subdivisions T. 9 S., R. 9 E.

Note.

On account of inaccessible & unavailable mountains & abandon. Survey South.

From the cor. to secs. 13 & 24 on East boundary formerly noted by me I run West on true line between secs. 13 & 24 Var 16° 40' E.

40.00 Set standstone 17 x 9 x 6" in the ground for 1/4 sec cor. marked 1/4 cor. S. pass and raised a stone mound also Land mountainous & Soil 2nd rate. No timber Bearings & distances to

Note. Oct 1st 83.

On account of unavailable mountains Abandon survey here.

Subdivision of S. of G. L. R. 3 W.

From the cor. to secs. 1. 2. 35 & 12
from
West on true line
betw secs. 2 & 11
Var. 16° 40' E.

3.00 Record of bench
5.50 S. to R. G. R. R. bears N. 44° E.
6.50 Cajon Road " "
8.00 Spanish fork Creek 50 lks wide
2 ft deep runs N. W.
13.00 Record
40.00 Set limestone 20×2×12 in
in the ground for 1/4 sec. cor.
marked 1/4 on W. face and
raised a stone mound alongside
30.00 Set limestone 16×9×8 in
the ground for cor to secs. 2. 3. 10 & 11
marked with 3 notches on W.
and 2 on E. edges and raised
a stone mound alongside
Land mountainous
Soil 2nd rate
No timber.
Down underbrush on hills

Subdivision

Nor
to

24.00 ~~Set to~~
0.00 Set to
40.00 Intersec
30 lks
previ
which
c

8.00 Spanish
deep
20.00 Record
40.00 Set li
ground
on W.
along
80.00 Set cor
Land
Soil
De

BOOK-A-197

Subdivisions T. 9 S. R. 3 E.

North on meridian
between secs. 2 & 3.
Var. 16° 40' E.

~~24.00 Top of Ledge.~~
0.00 Set stone, 1/4 sec. cor. W. bears 30 lks. dist.
80.00 Intersect N. boundary of T.
30 lks. W. of cor. to secs. 2 & 3
previously set by me from
which I run
S. 0° 15' W. on true line
between secs. 2 & 3
with same var.
8.00 Spanish fork Creek 75 lks. wide. 4 ft.
deep runs N. W.
20.00 Recross
40.00 Set hinestone 14 x 8 x 3 in. in the
ground for 1/4 sec. cor. marked 1/4
on W face, raised a stone mound
alongside.
80.00 N. cor. to secs. 2. 3. 10 & 11.
Land mountainous & level.
Soil 2nd rate.
Pine, underbrush on Hills

Subdivisions Pr. 9 S. R 3 E

West on true line
betw. secs. 3 and 10
Var 16° 40' E.

40.00 Set sandstone 19 x 13 x 3, 12 in
the ground for 1/4 sec. cor. mark
1/4 on N. face and raised a stone
mound along side.

80.00 Set sandstone 16 x 13 x 5 in. 12 in
in the ground for cor to secs. 3, 4,
9, 10 marked with 5 notches
on said 3 on E edge and ra
a stone mound along side.
Land. High broken mounta
Soil Stony
No timber.
Bears underbrush on 80 ch

Oct. 2nd 83.

North on random line
betw. secs. 3 & 4
Var. 16° 40' E.

40.00 Set temp 1/4 sec cor.
79.80 Intersect N. boundary of Tp.
25 chs W of cor. to secs. 3, 4, 9,
formerly set by me from

BOOK-A-

Subdivi

which

Rock

Road

Set bo
in the
1/4 on
mou

Road

Arro

The c
Land
Soil
No t
Bear

Pos

Smal

Set b
in the

BOOK-A-197

Subdivisions T. 9 S. R. 3 E.

which runs
S 0° 11' W on true line
betw. secs. 3 & 4
with same var.

10.00 Rocky Spur of Mountains.
20.00 Road in Snells Cañon dr. N. W.
29.80 Set limestone 18 x 12 x 3. 12 in
in the ground for 1/4 sec cor. marked
1/4 on W face and raised a stone
mound alongside.
58.00 Road in Snells cañon bs. NE.
Agent.
79.80 Pit cor. to secs. 3. 4. 9 & 10.
Land. mountainous.
Soil. 2nd rate
No timber,
Scrub underbrush on T. 9 S.

West on true line
betw secs. 4 & 9
Var 16° E.

22.00 Snells canon drains NE. Road
40.00 Set limestone 20 x 11 x 4. 15 in
in the ground for 1/4 sec. cor.

Subdivisions T. 9 S. R. 3 E.

marked 1/4 on N. face and rais
a stone mound alongside.
80.00 Set limestone 20 x 10 x 5 - 15
in the ground for cor. to secs.
9. 5. 8 & 9 marked with 5
notches on S. and 4 on E. edg
and raised a stone mound alongs
Land mountainous
Soil 2nd rate
No timber
Bears underbrush on 80 ac

North on random line
between secs. 4 & 5.
Var. 16° 40' E.

40.00 Set stone 1/4 sec. cor.
52.00 Ash 12 ins. dia. bears
79.90 Intersect N. boundary of
T. 15 Nor. R 4 W. cor. to secs. 4
previously set by me from
which I run

West on true line
between secs. 4 & 5
with same var.

Record

BOOK

Subdivisi

2000 Ente
39.90 Set
the
14 or
along
50.00 Pit
79.90 Pit
Lar
Soi
No
Bea

Pro
on E
pre

5.00 Roa
31.50 "
40.00 Mar
2 x 1
on

BOOK-A-197 451

Subdivisions Sp. 9 T. 2 S. R 3 E.

20.00 Enter bench
39.90 Set limestone 15×8×3 in 10 in in the ground for 1/4 sec. cor marked 1/4 on W face, raised a stone mound alongside.
30.00 Ridge bears NE & SW.
79.90 Set cor to sec. 4. 5. 8 & 9
Land mountainous.
Soil 2nd rate.
No timber.
Course undergrowth 79.90 Ch.

Oct. 3rd 83.

From the cor. to secs. 19 & 30 on the boundary of this Sp. previously set by me I run East on true line between secs. 19 & 30 Var. 16° 45° E.

5.00 Road bears N & S.
31.50 " " NW & SE.
40.00 Marked stationary and set a stone 2×1×1 ft above ground mark X on N face. for 1/4 sec. cor.

Subdivisions Sec. 9 T. 9 S. R. 3

and raised a stone mound
alongside.

57.00 Record

20.00 Set said stone 14 x 12 x 2 in
8 ins in the ground for cor. to secs
19. 20. 29 & 30 marked south
notches on land S on E edge
and raised a stone mound
alongside.
Land. mountainous.
Soil. 2nd rate.
No timber.
Dense brush on both

East on true line
bet. secs. 20 & 29
Var. 16° 45' E.

20.00 Top of ridge.

40.00 Set said stone 20 x 11 x 5 & 15 ins
in the ground for 1/4 sec cor
marked 1/4 on S face and
raised a stone mound alongside
Land. mountainous

BOOK-A-197 465

Subdivisions Sec. 9. T. 23 S. R. 3 E.

Said 2nd rate.
No timber.
Dense undergrowth on hills

Note. On account of unavailable mountains Sabaudon survey here.

From the cor. to secs. 9 & 10
29 & 30 set by same
North bet. secs. 9 & 10
Var. 16° 45' E.

40.00 No trace of old cor, set limestone 15 x 18 x 3. 10 in the ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound along side. entire re-survey

80.00 not found Old cor set & said stone 14 x 12 x 2. 9 in in the ground for cor. to secs. 9, 10, 15, 16 & 29 & 30 marked with 3 notches on S. and E on E edges and raised a stone mound alongside.

Race. West slope of mountains

Sail 2nd rate.
No timber.
Dense underbrush on 80ch

40.00

Note. The cor. to secs. 16, 17, 20, 21
not set. Survey
East on true line.
Astron. secs. 17 & 20
Var. 16° 45' E.

40.00 No trace of old cor. set limeston
17 × 6 × 4 in. 10 in. in the ground fo
1/4 sec. cor. marked 1/4 on S
and raised a stone mound
alongside.
Rolling mountainous
Sail. 2nd rate.
No timber.
Dense underbrush on 40

80.35

Note. On account of mountains
mountains Abandon
further survey East.

40.35

61.00
76.00
80.35

BOOK-A-197

Subdivisions T. 9 S. R. 3 E.

West on random line
bet. secs. 18 & 19
Var. 16° 45' E.

40.00 No trace of old cor. set temp.
1/4 sec. cor.

80.35 Intersect W. boundary of
Tp. 2 lks S. of cor. to secs. 18 & 19
from which I run
S. 89° 51' E. on true line
bet. secs. 18 & 19
with same var.

40.35 Set oak post 3 ft. long 3 ins. sq.
for 1/4 sec. cor. marked 1/4 S. dug
pits 18 x 18 x 12 ins. E & W. 5 1/2 lks
dist. and raised a mound of
earth 1 1/2 ft. high and 3 1/2 ft.
base around it

61.00 Road bears N. E & S. W.

76.00 Spring branch 5 lks wide flow. N.W.

80.35 Set cor. to secs. 17. 18. 19 & 20
Lays mountainous
Soil 2nd rate.

Witness:
Bears underbrush on 80.35 lks
Oath 53

Subdivisions Sp. 9 T. 8 R. 5 E.

North [illegible] Secs. 17 & 18
Var. 16° 45' E.

13.00 Road bears NE.
14.00 Spring branch 4 links wide runs S. W.
23.00 Road bears NW & SE.
25.50 " " W.
29.00 " " NW & SE.
40.00 No trace of old cor. set limestone
12 x 2 x 6 in. marked 1/4 S on W. face
in the ground for 1/4 sec. cor. Pits 18 x 18 x
in depth N & S. 5 1/2 ft dist. and
raised a mound of earth
1 1/2 ft high, 3 1/2 ft at base above
side
60.00 Road to Waterman bears NW
79.00 Creek 10 links wide 4 in deep runs SW
80.00 No trace of old cor. set limestone
14 x 8 x 6 in 9 in the ground for
cor. to secs. 7, 8, 17 & 18 marked
with 4 notches on S. and 5 on
Edges and raised a stone
mound alongside.
Land mountainous
Soil 2nd rate.
No timber.
Pence underbrush 80 ch

BOOK-A-197

Subdivisions Sp. 9 S. R. 8 E.

Note. Meas. to secs. 8, 9, 16 & 17 not set from
removed
East on true line
betw. secs. 8 & 17.
Var 16° 45' E.

4.00 Posted.

40.00 Outline of old cor. set various
16 x 14 x 8 in. 12 in in the ground for
1/4 sec. cor. marked 1/4 on N. face
and witness stone mound
alongside.
Laid mountainous.
Soil Grade.
No timber.
Dense undergrowth on Hdth.

Note.
On account of high
inaccessible mountains
I abandon further survey
here.

Subdivisions Tp. 9 S. R3

Ex survey

West on said ann line
betw. secs. 7 & 18
Var. 16° 45' E.

40.00 No trace of old cor. set temp
1/4 sec. cor.

80.40 Intersect West boundary of
Tp. 15 lks S. of cor to secs.
7 & 18 formerly set by me
from which Sam
S. 89° 54' E. on true line
betw secs. 7 & 18
with same var.

21.50 Enter gulch drains N. W.

28.00 Leave same

30.00 Enter same " "

35.00 Leave same

40.40 Set a blazed cottonwood post
3 ft. long 3 ins sq. for 1/4 sec.
cor. marked 1/4 S. on N. face
Dug pits 18 x 18 x 12. Ep W. 3 1/2 ft
dist. and raised a mound of earth
1 1/2 ft high & 3 1/2 ft. at base
around it.

44.20 Ditch runs N.

57.00 Road leaves N. W. & E.

Subdivi

68.50 R
70.50
80.00 Pre
80.40 The
La
Sa
Ne
Dec

40.00 Set
Stan
for
face
also

80.00 Set
in
of
Dug
Cou
a m
4 1/2
Le

BOOK-A-197

4 519

Subdivisions Sec. 9 T. 8 R. 3 E.

68.50 Road bears N. & E.
70.50 " on N. & E.
80.00 Creek 5 lks. wide runs N.
80.40 The cor. to secs. 7. 8. 17 & 18.
Land mountainous
Soil 2nd rate.
No timber.
Bears N. 80. 40 lks.

North betw. secs. 7 & 8
Gar. 16 links E.

70.00 My trace of old cor.
Set in bears oak brush a lime-
stone 15 x 10 x 3 in. 9 in in the ground
for 1/4 sec. cor. marked 1/4 S. 7.
face and raised a stone mound
alongside.

80.00 My trace of old cor.
Set a sandstone 20 x 6 x 4 in 15 in
in the ground for cor. to secs. 5. 6. 7.
& 8. marked with 5 notches on S. & E.
Edges, dug pits 18 x 18 x 12 in each
secs. 5 1/2 ft. distant, and raised
a mound of earth 2 ft. high and
4 1/2 ft. at base alongside.
Land very broken foothills

Subdivisions P. & S.R.S.

Sail 3rd rate.
No timber.
Dense undergrowth 80.30

East on reserve
land on true line
between secs. 5 & 8
Var. 16° 45' E.

38.00 Re trace of old cor. set temp.
40.00 1/4 sec. cor.
80.30 Intersect N. & S. line at cor to secs. 4. 5. 8 & 9. from which Tree
West on true line
between secs. 5 & 8
with same var.
40.16 Set Pine stake 16 x 8 x 5 ~~10~~ in the ground for 1/4 sec. cor. & raised stone mound alongside. marked 1/4 on N face.
65.00 Enter lower flat
80.30 Re cor to secs. 5. 6. 7 & 8
Land mountainous & heavy
Sail 2nd & 1st rate.
No timber.
Dense undergrowth 80.30

BOOK-A-

Subdi

4000 No
1/4 sec
79.86 Inte
15 lk
set
23.00 Rec
28.00 Sal
31.00 "
79.86 On
7 in
140
alo
43.00 Sal
47.86 Ent
50.00
58.00
72.30 Re
79.86 Re
La
S

BOOK-A-197 461

Subdivision Sec. 9 T. 8 S. R. 36 E.

West on random line
retro secs. 6 & 7.
Var. 16° 45' E.

4000 No trace of old cor. set temp
1/4 sec. cor.

79.86 Intersect W. boundary of Sec
15 lks N. of cor. to secs. 6 & 7
as by me from which I run
N. 89° 54' E on true line
retro. secs. 6 & 7.
With same var.

23.00 Creek, bench

28.00 Salem ditch bears NE leave brush

32.00 " " " SE

39.86 On road set collection corner 12 x 8 x 6 X
pit in the ground for 1/4 sec. cor. marked
1 on W face, raised stone mound
adjacent.

43.00. Salem ditch 20 lks wide bears NE
47.86 Enter brush " " " SE
56.00 " " " " NE

58.00 " " " " NE

72.30 Road bears NE & SW.

79.86 Rec. cor. to secs. 5. 6. 7 & 8.
Lava. broken bench
Soil and grass rock

Subdivisions T. 9 S. R. 8 E.

No timber.
Dense undergrowth on 60 ch.

North on random course
betw secs. 5 & 6
Var. 16° 45' E

40.00 In trace of old cor. set temp ¼ sec. cor.

80.00 Intersect N. boundary of T. 9 S. R. 8 E. W. of cor to secs. 5 & 6 set by me from which I run
S. 0° 6' W on true line
betw secs. 5 and 6
with same var.

2.00 Ditch runs W.
7.00 " " "
12.50 Road bears N. W. & E.
20.50 Road bears N. W. & E. a cabin bears E. 15 ch. enter field leave N.
X 26.50 Ditch E & W.
X 35.50 Leave field enter dense brush
40.00 Set standard 12 x 9 x 6 : 8 ds in the ground for ¼ sec cor.

BOOK-

Subdivi

mark
18 x 18
raise
high

42.20 Road
50.50 Leav
51.50 Road
52.50 A fe
68.00 Ditch
73.28 Lake
W.
76.20 Road
80.00 The
D
D

Dun

BOOK-A-197

Subdivisions Tp 9 S. R. 3 E.

marked 1/4 on W face, dug pits
18 x 18 x 12 in N & S. 5 1/2 ft. dist and
raised a mound of earth 1 1/2 ft
high and 3 1/2 ft at base alongside

42.20 Road bs. S 75° E enter field
50.50 Leave field enter dense brush
51.50 Road bears N 75° E
52.50 A field W of hwy
68.00 Ditch runs E, leave field.
73.28 Salem ditch 20 lks wide runs
W.
76.20 Road bears S 75° E
80.00 Cor to Sec 5, 6, 7 & 8.
Land gravel bench
Soil 2nd & and 1st rate
No timber
Dense undergrowth on 56.70 chs.

Oct 5th 1883.

BOOK-A-197

464

General Description.

Most of this Township embraces very high and almost inaccessible Mountains. The main Cañon through which the Denver & Rio Grande Railway passes (narrow Guage) has rich soil. There is no timber on the portion surveyed, but dwarf pine and oak brush, as also a heavy growth of willows along the water courses

Applicants for survey are H. L Sterling and Lewis Edwards who have a joint farm consisting of fenced fields 2 housed stable corral ditches of over $600 in value Said improvements are situated on the S E ¼ of Sec 12 Lovendahls Saw Mill is located on the S W ¼ of same Section

Pole canon has no living
Stream.
The resurveyed portion of the
Tp is high bench land covered
with dense sage and oak brush
Settlers are L Colton on NW
1/4 Sec 6
W. Lewis on NW 1/4 Sec 5
Thos Cloward on S 1/2 Sec 6
Water Canon has a small
stream of water.

Ernest H. Hesse
U. S. Dep. Surveyor

BOOK-A-197

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, February 4th *1884*

The foregoing field notes of the survey of the Subdivisions of the fractional *Township No.* 9 South *Range No.* 3 East *Executed by* Ernest H. Peace *Under* 118 *contract of the* 5th *day of* July *1883, in the month of* Sept & October *1883, having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

Fra Salomon

U. S. Surveyor General for Utah.

BOOK-A-197

REPORT: 1884

Filed 188

Examined by .....

Transcribed by Jno. A Mitchell

Compared by Jno. A Mitchell & L.N. Hicks

FIELD NOTES

OF THE SURVEY OF THE

Guide Meridian

(East Boundary)

OF

Township No 9 South between

Range No 4 & 5 East

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Ernst H. Hesse

U. S. Deputy Surveyor,

Under his Contract No. 118

Dated July 5th 1883

Survey commenced Oct 9th 1883

Survey completed Oct 9th 1883

BOOK-A-197

Township 9 South R. 4 East

6	5	4	3	2	1	469
7	8	9	10	11	12	468
18	17	16	15	14	13	467
19	20	21	22	23	24	466
30	29	28	27	26	25	465
31	32	33	34	35	36	464

X65 Guide Meridian
East boundary Tps 9 & R 4 E

Survey commenced Oct 9th 1855
From the cor to Tps 9 & 10 S. R 4 E
previously set by me, I run
North betw. Secs 31 & 36
Var 16° 40 E

21.00 Ridge bs E & W.

40.00 Set limestone 19 x 11 x 4. 13 in in the ground for 1/4 sec cor marked 1/4 on W face & raised a stone mound alongside.

80.00 marked stationary boulder, at foot of mountains 3 x 2 x 2 ft. above ground with 5 notches on N & on S. edges for corner to secs 25 & 30, 31, & 36 and raised a stone mound alongside.

Land mountainous
Soil 2nd rate
No timber
Dense underbrush on 80 chs.

North betw. secs 25 & 30
Var 16° 40' E

1.00 Soldiers Creek 70 lks wide runs W

9.70 D & R G. R W. bs E & W.

Gunde Meridian

East boundary Sec 9 T. 8 R 4 E.

12.00 Road E. & W. along fence.

20.00 Creek

40.00 Set flint 30×18×5: 20i in the ground for 1/4 sec. cor. marked 1/4 on W face raised a stone mound alongside

30.00 Set lime stone 20×8×5: 14s in the ground for cor to secs. 10. 24. 25 & 9. marked with 4 notches on S and E. edges and raised a stone mound alongside. Land mountainous level. Soil. 2nd & 1st rate. Timber. Jun. cedars. Mountainous & dense underbrush on 6 chs.

North betw. secs. 10. & 9.
Var. 16° 40' E.

21.00 Ridge runs E & W.

46.00 Set lime stone 12×8×5: S in the ground for 1/4 sec. cor. marked 1/4 on W face raised a stone mound alongside.

51.00 Ridge runs E & W.

68.00 " " W & E.

80.00 Set sandstone 18×16×16 in 12 in the ground

467 Guide Meridian
East boundary. T. 9 S. R. 4 East

for cor to secs. 13. 18. 19 & 24 mar
with 3 notches on 4 sides & 3
raised a stone mound
alongside.
Land High Mountains
Soil red rock
Timber sc. cedars
Mountainous & dense
undergrowth on S. boundary

North 80 links
Var 16° E.

24.00 Ridge bears NW & SE.
40.00 Set iron stone 15 x 12 x 8 in. 9 in
in the ground for 1/4 sec. cor.
marked 1/4 on W. face & raised a
stone mound alongside.
51.00 Ridge bears E & W.
30.00 Set flint 18 x 11 x 6 in. 12 in. in the
ground for cor to secs. 7. 12. 13 & 18
marked with 4 notches on sides
2 on Bedges and raised a stone
mound alongside.
Land Mountainous

BOOK-A-19

Ute Meridian 4.68 W.

East boundary of Tp. 9 S. R 4 E.

Soil. 2nd rate
Timber.
Mountainous & dense
undergrowth on Slope.

North bet sec 7 & 12
On 16.40. E.

40.00 Set a cedar stake 19 x 13 x 4 in 18 in in the ground for 1/4 sec cor. marked 1/4 on W face & raised a stone mound alongside.

60.00 Ridge bears W

80.00 Set limestone 24 x 6 x 6 18 in in the ground for cor to secs 1. 6. 7 & 12 marked with 5 notches on East & on W face raised a stone mound alongside.

East mountainous.
Soil 2nd rate.
Timber.
Mountainous & dense
undergrowth on Slopes.

469. Guide Meridian
East boundary, T. 9 S., R. 4 E.

North bdy. sec. 1, T. 6
Var. 16° 20' E.

0.50 Radius drains N.W.

40.00 Set sandstone 15"x9"x3"; 9" in the ground for 1/4 sec. cor. marked 1/4 on W. face and raised a stone mound alongside.

45.00 Ridge bears N. W. & S. E.

80.00 Set limestone 24"x8"x4"; 18" in the ground for cor. to Tps. 8 & 9 S., R. 4 & 5 E. marked with 4 notches on N. & E. edges and raised a stone mound alongside.

Exter. mountainous
Soil 2nd rate,
No timber,
Mountainous & dense
undergrowth on 80th's.

Oct 9th 1883

For Genl description see sub-divisional surveys.

Ernst H. Hesse
U. S. Dep. Surveyor

U. S. SURVE

Salt La

The fore

Guid

Township No.

Executed by

Under 11

day of

Octo

amined, the ne

the said field

hereby approv

BOOK-A-197

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, February 4th *1884.*

The foregoing field notes of the survey of the Ute Meridian (E. boundary)

Township No. 9 South *Range No.* 4 & 5 East

Executed by Ernest H. Hesse

Under 118 *contract of the* 5th

day of July *1883, in the month of* October *1883, having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

Fred Salomon

U. S. Surveyor General for Utah.