BOOK-A-201

REPORT: 1884

Filed 188

Examined by .....

Transcribed by John A. Mitchell

Compared by John A. Mitchell & E. Michaelis

FIELD NOTES

OF THE SURVEY & Resurvey OF THE

South & the survey of the East and the resurvey of the Northboundaries.

OF

Township No 13 South

Range No West

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Edward W. Kocher

U. S. Deputy Surveyor,

Under his Contract No. 122

Dated Dec 4 *1883*

Survey commenced Jan 1 *188*4

Survey completed Jan 19 *188*4.

BOOK-A-201

[2.—PRELIMINARY OATHS OF CHAINMEN.]

We, Olof Larsen

and Harry Pitchforth

do solemnly swear that we will well and faithfully execute the duties of chain carriers; that we will level the chain upon even and uneven ground and plumb the tally pins, either by sticking or dropping the same; that we will report the true distance to all notable objects, and the true length of all lines that we assist in measuring, to the best of our skill and ability, and in accordance with instructions given us, in the survey of the Exterior and Subdivisions of Tp. No. 12 South, of Range 1 West

of the Salt Lake base and meridian in the Territory of Utah.

Olof Larsen, Chainman.

Harry Pitchforth Chainman.

, Chainman.

, Chainman.

Subscribed and sworn to before me this 14th day of January 1884

Edward L. Foster

Clerk & Surv

BOOK-A-201

[PRELIMINARY OATH OF AXEMEN.]

We, Olof Larsen, and
and Harry Pitchforth
do solemnly swear that we will well and truly perform the duties of axemen, in the establishment of corners, and other duties, according to instructions given us, and to the best of our skill and ability, in the survey of
Exterior and Subdivisions
of Tp. No. 13 South, in Range No. 11.

of the Salt Lake base and meridian in the Territory of Utah.

Olof Larsen, Axeman.
Harry Pitchforth, Axeman.

Subscribed and sworn to before me this 14th
day of January 1884

[illegible]
U.S. Deputy Surveyor

BOOK-A-201

Township 13 South R. 18 West

	58		59		60		61				
59	6	63	5	34	4	23	3	11	2		1
	62		46		33		22				
56	7	45	8	32	9	21	10	10	11		12
	45		44		31		20				
55	18	43	17	30	16	19	15	9	14		13
	42		41		29		18				
54	19	40	20	28	21	17	22	9	23		24
	39		38		27		16				
53	30	37	29	26	28	15	27	8	26		25
	34		35		25		14		7		5
52	31	35	32	24	33	13	34	6	35	4	36
	51		50		49		48		47		2

BOOK-A-201

REPORT: 1884

Filed 188

Examined by .....

Transcribed by E. Michaelis

Compared by J. A. Mitchell & E. Michaelis

FIELD NOTES

OF THE SURVEY OF THE

Fractional Lotton of the East Boundary

OF

Township No 24 South,

Range No 4 & 5 West.

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Edward W. Kaeber

U. S. Deputy Surveyor,

Under his Contract No. 122

Dated Dec. 4th 1883

Survey commenced Jany 9th 1884

Survey completed " " 1884

V

BOOK-A-20166

East Boundary T. 24 S. R. 4½ W.

Before commencing this survey I tested my compass on a meridian observation on the star Polaris, and found it in proper adjustment.

Commenced the survey Jany 9th 1884 with a Burts improved solar compass.

From the cor. to ~~xxxx~~ Secs 24 & 25 S. R. 4 & 4½ West, which is a granite 16 x 12 x 10 ins. with a stone mound drum

Mech bet. Decs. 31 & 36
Var. 16° E.

3.60 Robert Parker's cabin & correll bears N. 76° 15' E. about 18.50 chs.

13.00 Rose Creek 3 links wide runs S E.

22.50 N. side of Ridge
32.50 Cross creek 3 links wide runs
NW. in hollow.
34.50 Same creek runs SE.
40.00 Set Granite 30 x 18 x 5 ins, 20 ins
in the ground for 1/4 Sec. cor
Marked 14 on N. face &
placed a mound of stones
alongside.
43.50 Ridge bears NW. & SE. SE. cor.
of Frazier's Corrall bears S. 75°45' W.
about 20 chains; Large elm
in heavy bunch of aspens N.
of the corrall, Enter aspens.
53.50 Indian Creek 3 links wide
runs SE. in hollow, and
leave aspens; Elsinore
house bears S. 82°31' W. 6 chains
a corrall SE. of the house.
63.50 Gully draws SE.
74.00 Ridge bears SE & NW.
80.00 Set a Granite 20 x 8 x 7 ins
5 ins. in the ground for
for cor. to Secs. 25.30.19 &
36, Marked 5 notches on

BOOK-A-201

at & 1 on both edges &
raised a mound of
stone along it.
Land mountainous 80. chs.
Soil 2d rate.
Dense undergrowth.
Aspen timber as note B.

North bet. secs. 20 & 30
Var. 16° E.

6.00 Gully drains S.E.
12.00 Ridge bears N.E. & S.W. and enter aspens.
19.00 Fence S. side of Grouse Corrall
20.00 Enter swampy ground in corrall, and leave aspens.
21.50 Gooseberry Creek 3 lks. wide runs S.E.
22.50 Large spring 2.75 chs. W. just out side of the corrall, which is the supposed source of Gooseberry Creek.
23.50 Leave corrall, and swampy ground,

33.00 Ridge bears E & W.
38.00 Elder aspens.
40.00 Set Granite 20x8x14 ins. 15 ins. in the ground for 1/4 sec. cor. Marked 1/4 on W. face, and from which Wallaspen 4 ins. diam. bears N 22° E. 36 lks
" " 6 " " " N 3° W. 30 "
Both trees marked 1/4 S. B. T.
60.00 Spring 50 links W. drains NW.
63.00 Spring 25 links E. drains NW.
77.25 Spring Branch hollow, drains NW. A spring in hollow 3 chs. S. E. Large aspens.
80.00 Spring at 60° E. about 8 chs. drains W. — Set Granite 12x12x8 ins. 8 ins. in the ground for cor. to secs. 19, 24, 25 & 30 Marked 4 notches on N. & E. on S. Edges, and raised a mound of stone alongside. Land Mountainous on 80 chs.
Soil 1st rate.
Dense oak underwood.

BOOK-A-201

East Boundary T. 24 S. R 4½ W

taken timber as noted.

Arch bet. secs. 19 & 24
Var. 16° E.

5.26 Water mus N. from spring 6 chains E. of line.

20.00 Ridge bears NE & SW.

40.00 Set Granite 15 x 10 x 8 ins, 10 ins. in the ground for 1/4 sec. cor. marked 1/4 on N. face and raised around of stone alongside –

Land Meandered on 40 chs soil 2d rate.

Dense undergrowth

No timber.

Note:

The line further north is impracticable.

— " — Jany 9th 1884

Note:

For general description see end of subdivision notes.

Edward F. Kocher
U. S. Deput. Surv.

BOOK-A-201

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, April 8 *1884.*

The foregoing field notes of the survey of the

fractional portion of the East Boundary

Township No. 24 S. *Range No.* 4½ W

Executed by Edward W. Kocher No. 122

Under his *contract of the* 4th

day of Dec. *1883, in the month of*

January *1884, having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

Fred Salsbury

U. S. Surveyor General for Utah.

BOOK A-201

4

REPORT: 1224

Filed 188

Examined by .....

Transcribed by E. Michaelis

Compared by J. A. Mitchell & E. Michaelis

FIELD NOTES

OF THE SURVEY OF THE

Subdivisions

of the

fractional

~~Tp~~

Township No 24 South

Range No 4½ West

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Edward W. Hoeber

U. S. Deputy Surveyor,

Under his Contract No. 122.

Dated December 4th 1883.

Survey commenced January 10th 1884

Survey completed January 12th 1884.

BOOK-A-201

Township 24 South R. 4½ West

6		5		4		3		2		1	
7		8		9		10		11		12	
18		17		16		15		14		13	
19		20		21		22		23		24	70
		101		93		87		81		76	
30	99	29	92	28	86	27	80	26	75	25	68
98		96		90		84		79		73	
31	96	32	89	33	83	34	78	35	72	36	66

BOOK-A-201

Subdivisions T. 24 S. R. 11½ W.

I test my compass on the meridian and find it correct.

Survey commenced Jany 10. 1884 with a Burts improved solar compass,

Township cor. to secs. 35 & 36 on the south boundary of this township which is a Granite 16x6x5 ins. with stone mound I run

Arch bet. secs. 35 & 36

Chains. Var. 16° E.

4.00 Ridge bears NE & SW.

7.00 Gulch draws SW.

10.00 On top of Ridge bears NE & SW, set a Granite 20x14x12 ins, 15 ins. in the ground for ¼ sec. cor. marked ¼ on W. face, and raised a mound of stone alongside.

16.00 Gulch draws W.

18.00 On E. side of hollow draws SW. set

Subdivisions Tp. 24 S R 4 1/2

a Granite 30x12x12 ins. 20 ins. in the ground for cor. to secs. 25. 26. 35 & 36 Marked 1 notch on E & S. edges, and raised a mound of stone along side,

on 80. chs.

Land mountainous, soil 2d rate.
Dense undergrowth.
No Timber.

East on Random line bet. secs. 25 & 36
var. 16° E.

40.00	set temp. 1/4 sec. cor.
79.90	Intersect east boundary of the Tp. at the cor. to secs. 25, 30, 31 & 36, which is a Granite 20 x 8 x 7 ins. with stone mound, from which West on a true line bet. secs. 25 & 36

BOOK-A-201

With same Var.
6.00 Ridge bears NW & SE.
10.00 SE. cor. of a corrall bears N. 50° W. about 15 chains; a cabin and two springs W. of the corrall.
Indian Creek.
19.50 Cross drains SE. Enter aspens
39.95 Set Granite 36 x 20 x 10 ins, 2 ins. in the ground for 1/4 sec. cor. marked 1/4 on N. face and from which
Aspen 6 ins. dia. bears S. 60° 30' W. 50 lks.
" " 4 " " " N. 10° 30' E. 100 "
Both trees marked 1/4 S. B. T.
55.00 Leave aspens.
60.50 Ridge SW & NE.
65.00 Head of hollow trends SW,
70.00 Ridge bears SW & NE.
79.90 The cor. to secs. 25, 26, 35 & 36
Land Mountainous on 79.90 chs.
Soil 1st rate.
Dense undergrowth.
Timber as noted.

75

Subdivisions Tp. 24 S. R. 4½ E.

Notch bet. secs. 25 & 26
Var. 16° E.

4.00 Gulch drains S.W. Enter Aspen
20.00 Top of divide bears E & W.
Descend
40.00 Set Granite 14 x 9 x 5 ins,
9 ins. in the ground for
¼ sec. cor. marked 1/4 on
W. face ~~for ¼ sec. cor.~~ and
from which
An Aspen 3 ins. dia. bears S. 45° E. 10 lks
" " 3 " " " S. 21° W. 6 "
Both trees marked ¼ S. B. T.
43.00 Gulch drains S.W.
48.50 Ridge bears S.W. & S.E.
60.00 Gulch drains S.W. & leave
Aspens.
80.00 On W. slope; set a Granite
15 x 11 x 9 ins. 10 ins. in the
ground for cor. to secs.
23, 24, 25 & 26, marked 1
Notch on E. & 2 on S. Edges
and raised a mound of
stone alongside.
Land Mountainous on 80. chs

BOOK

Subdivi

Se
De
Tu

Ea

40.00 set
80.00 Gul
che
sees
is
mu
ref
Mo

1.50 Spru
3.50 Gul
19.50 Spru
aug
35.50 Spr
40.00 set

Subdivisions T. 24 S. R. 4½ W.

Soil 1st & 3d rate.
Dense undergrowth,
Timber Aspen on 56 chs.

East on random line
bet. Secs. 24 & 25
Var. 16° E.

40.00 set temp. ¼ sec. cor.
800.0 Intersect E. boundary of the Tp. at the cor. to Secs. 19, 24, 25 & 30, which is a boulder 12x12x8 ins, with stone mound, from which
West on true line
bet. Secs. 24 & 25
Var. 16° E.

1.50 Spring branch in hollow 3 chs. wide nearly N.
3.50 Fully aspen timber
19.50 Spring branch in hollow 3 chs. wide, and leave aspen timber
35.50 Open Ridge bears N. & S.
40.00 set Trachytic Rock 15x6x6 ins.

Subdivisions T. 24 S. R. 4½ W.

10 lks. in the ground for
¼ sec. cor. marked 1/4 on
N. face, and raised a
mound of stone alongside

43.00 Enter small cove

60.00 Spring branch 3 chs. wide in gulch
runs N. Leave the cove,

76.00 Ridge bears NW & SE.

80.00 The cor. to secs. 23, 24, 25 &
26.

Land mountainous 0 in 80 chs.
Soil 1st & 3d rate.
Dense undergrowth,
Timber aspen as wood.

"

Note: On account of the
mountains I abandon the
survey further North.
January 10. 1884

4

Lues

Fom
on the
Rhi
lks.
I ra
N

3.00 Inter
35.00 Leav
40.00 set
lks.
sec.
face
of t
Jam
and
along
the
60.00 Cab
69.00 Leav
Acc
80.00 Set
18 lks
cor. t
mar
on S

Lues Lake Meridian

From the cor. to secs. 3 4 33 35
on the south boundary of the township
which is a Granite 16x9x8
ins. with stone mound
I run
North bet. secs. 3 4 33 35
Var. 16° E.
3.00 Enter timber.
35.00 Leave " — Hollow drains E.
40.00 set Granite 15x10x10 ins. 10
ins. in the ground for 1/4
sec. cor. marked 1/4 on W.
face, and raised a mound
of stone alongside. from which
James A. Ross' Ranche, Cabins
and corrals bear East
about 12 chs. as shown on
the plat. Enter flat.
60.00 Corral E. about 11 chs.
69.00 Leave flat bears N & S W. &
Ascend. Cabin E. about 14 chs.
80.00 Set Sandstone 20x24x12 ins.
18 ins. in the ground for
cor. to secs. 26. 27. 34 & 35,
marked 2 notches on E. &
on S. Edges, and raised

Subdivisions T. 24 S. R. 4 1/2 W.

a mound of stone along side; Spring bears S. 50° E. 17 chs.
Land mountainous on 57. chs.
Soil 1st & 2d rate.
Dense undergrowth on 80.00
Timber aspen on 32 chains

"

East on random line
bet. Secs. 26 & 35
Var. 16° E.

40.00 set temp. 1/4 sec. cor.
80.20 Intersect S. line 7 links
S. of cor. to Secs. 25, 26, 35 & 36
from which
S. 89° 57' W. on true line
bet. Secs. 26 & 35
with same Var.

3.00 Trail in hollow drains SW.
7.00 Enter Aspens.
13.00 Leave " — Ridge bears N. & S. W.
20.00 Enter "
35.00 Leave "
46.10 Head of Hollow drains N. 5 chs.

Subdivisions T. 24 S. R. 4½ W.

Thence N, set a Granite 20×20×6 ins. 15 ins. in the ground for ¼ sec. cor. marked ¼ on N face & raised a mound of stone alongside.

57.00 Hollow trends S.

15.00 Ridge bears NE & SW.

9.20 The cor. to secs. 26, 27, 34 & 35,

Land mostly mountainous sq. 80.20 chs.
soil 2nd rate.
Dense undergrowth.
Aspen timber as noted.

North bet. secs. 26 & 27
Var. 16° E.

30.00 Divide bears E & W.

40.00 Set Granite 18×12×6 ins. 12 ins. in the ground for ¼ sec. cor. marked ¼ on W. face, and raised a mound of stone along side.

Subdivisions T. 24 S. R 4½ W.

52.50 Inlet drains N.W.
72.00 Ridge bears N.W. & S.E.
80.00 Set Granite 15×10×6 ins.
10 ins. in the ground
for cor. to secs. 22, 23, 26 &
27, marked 2 notches
on E. & S. Edges, and
raised a mound of stone
alongside.
Land mountainous on 80. ch.
Soil 2d rate.
Dense undergrowth,
No timber.

East on a random line
bet. secs. 23 & 26
Var. 16° E.
40.00 Set temp. ¼ sec. cor.
80.40 Intersect N. & S. line 21 links
N. of cor. to secs. 23, 24, 25 & 26
from which
N. 89° 51' W. on true line
bet. secs. 23 & 26

BOOK-A-201

S. L. Lib.

With same var.
17.50 Gulch draws NW.
22.50 Ridge bears NW. & SE.
40.20 set Granite 14x10x8 ins.
9 ins. in the ground for
1/4 sec. cor. marked ¼
on N. face, and raised
a mound of stone alongside.
42.10 Gulch draws NW.
58.00 Ridge bears NW & SE.
80.40 The cor. to secs. 22.23.26 & 27.
Land mountainous on 80.40 chs.
Soil 2d rate.
Dense undergrowth
No timber.

Note: On account of the mountainous country I abandon the line further north.

Subdivisions T. 24 S. R. 4½ W.

Temporary cor. to secs. 33 & 34, on the south boundary of the township which is a branch 30 x 18 x 10 ins. with stone mound. Line run to cor. between secs. 33 & 34, var. 16° E.

2.00 Wash drains W.

35.00 Entry timber.

40.00 On Ridge bears N. & S. set a branch 17 x 12 x 11 ins. 11 ins. in the ground for ¼ sec. cor. marked ¼ on W. face ~~fs~~ and raised a mound of stone along side found which

8.00 an aspen 6 ins. dia. bears N. 63° E. 7 lks.

" " 8 " " " South ½ "

Both trees marked ¼ S. B. T.

8.00 Marked an aspen tree 6 ins dia. for cor. to secs. 27, 28, 33 & 34, with 3 notches on E. & 1 on S. sides, from which

an aspen 8 ins. dia. bears N. 20° W. 6 lks.

" " 8 " " " N 5° E 4 "

" " 4 " " " S. 6½° W. 11 "

" " 10 " " " S 10¼° E. 9 "

All the trees marked with the proper sec. T. & R.

Subdivisions T. 24 S. R. 4½ W.

Land mountainous poor.
Soil 1st & 2d rate.
Timber aspen on 4/5 chs.

East on random line
bet. secs. 27 & 34
Var. 16° E.

40.00 set temp. ¼ sec. cor.
20.00 Intersect N. & S. line at
the cor. to secs. 26. 27. 34 &
35, from which
West on true line
bet. secs. 27 & 34
with same Var.

1.00 Enter aspens.
4.00 Ridge bears N. & S. W. & leave aspens
17.00 Hollow drains S. W.
24.00 Ridge bears N. W. & S. E.

Subdivisions T. 24 S. R. 4½ W.

110.00 set Granite 48×48×30 ins. 36 ins. in the ground for ¼ sec. cor. marked on N. face, and raised a mound of stone along side.

48.00 Enter aspens.

80.00 The cor. to secs. 27, 28, 33 & 34.

Land Miscellaneous 92.80

Soil 2d rate.

Dense undergrowth and aspen timber as noted

BOOK A 201 86

Lucs Lake Meridian.

North bet. Secs. 27 & 28
Var. 16° E.

10.00 Leave aspens.

12.00 Cummings corrall & cabins
West of line as located on
map.

25.00 Top of W. slope.

40.00 Set Granite 10x10x8 ins.
10 ins. in the ground for
1/4 sec. cor. marked 1/4
on N. face & raised a
mound of stone along
side.

50.00 Gulch drains W.

60.00 Ridge bears E & W.

70.00 Set Granite 14x10x6 ins.
9 ins. in the ground for
cor. to secs. 21, 22, 27 & 28. —
Marked 3 notches on E.
& 2 on S. Edges, and raised

Subdivisions Sp. 24 S. R. 4 1/2 W.

a mound of stone
alongside.
Land mountainous 80 ch.
Soil 2d rate.
No timber.
Dense Undergrowth.

"

East on a random line
bet. secs. 22 & 27
Var. 16° E.

40.00 set temp. 1/4 sec. cor.
79.86 intersect N. & S. line 14 links
N. of cor. to secs. 22.23.26 & 27
from which
N 89° 54' W. on true line
bet. secs. 22 & 27
with same var.
16.50 Ridge bears N W & S E

BOOK A-201

Lake Lake Meridian

79.50 Creek draws NW.
79.93 Set Granite 18 x 11 x 4 ins.
12 ins. in the ground
for 1/4 sec. Cor. marked
1/4 on N. face, and
raised a mound of
stone alongside.
75.00 Ridge bears NW & SE.
79.86 The cor. to secs. 21, 22, 27 & 28.
Land mountainous
Soil 2d rate.
No timber.
Dense undergrowth.
Jany. 11. 1884

Note: I abandon the line
north on account of the
mountains.

79.86 chs.

Subdivisions T. 24 S. R. 4 E.

Temp. Glass cor. to secs. 32
on the South boundary of the Township
& 33, which is a mound
18 x 10 x 10 ins. with stone
mound 3 ins
North bet. secs. 32 & 33
Var. 16° E.

39.00 Enter aspens.

40.00 set Granite 19 x 19 x 10 ins
14 ins. in the ground for
1/4 sec. cor. marked 1/4 on
W. face & from which
An Aspen 6 ins. dia. bears N. 14° W. 6 lks
" " 7 " " " S. 43° E. 10 "
Both trees marked 1/4 S. B. T.

55.00 Ridge bears N.W. & S.E.

75.00 Leave aspen.

80.00 In Nolton's Cañon 3m.
Omnes Corral N.W. 5 chs: set a
Granite 36 x 36 x 6 ins, 27 ins.
in the ground for cor. to
secs. 28. 29. 32 & 33, marked

Salt Lake Meridian.

4 notches on E. & W. sides, and raised a mound of stone along side,

Land mountainous, rocky & of no value.

Timber aspen as noted.

Dense undergrowth on 80 chs.

East on a random line bet. secs. 28 & 33 Var. 16° E.

40.00 set temp. 1/4 sec. cor

80.10 Intersect N. & S. line 7 lks N. of cor. to secs. 27, 28, 33 & 34, from which

N. 89° 57' W. on true line

Subdivisions T. 24 S. R. 4½ W.

bet. Secs. 28 & 33
with same Var.

7.65 Wash drains N.
30.00 Leave aspen timber.
40.05 Set Granite 20×15×8 ins.
15 ins. in the ground for
¼ sec. cor. marked ¼ on
N. face, and raised a
mound of stone along
side.
48.00 Head of hollow drains N.
50.00 Top of Mountain bears N.W.S.
55.00 Road bears N.W.S.
65.00 Enter aspens.
76.00 Leave "
81.10 In hollow drains NW. The
cor. to Secs. 28. 29. 32 & 33.
Land mountainous on 80.10
Soil 2d rate.
Aspen timber on 41 chs.

Subdivisions T. 29 S. R 4½ W.

North bet. Secs. 28 & 29.
Var. 16° E.
over W. slope of mountain.

4000 set Granite 14×10×8 ins
qrs. in the ground
for ¼ sec. cor. marked
¼ on W. face, and raised
a mound of stone along
side.

5000 set Granite 15×11×9 ins,
10 ins. in the ground for
cor. to secs. 20. 21. 28 & 29.
marked 4 notches on E.
& 2 on S. Edges, and
raised a mound of
stone alongside.
Land mountainous 80 chs.
Soil 2d rate.
No timber.
Dense undergrowth.

Subdivision Tp. 24 S R 4½ W.

East on a random line
bet. secs. 21 & 28
Var. 16° E.

40.00 set temp. ¼ sec. cor.
80.30 Intersect N.&S. line
10 links N. of cor. to secs.
21, 22, 27 & 28, from which
N. 89° 56' W. on true line
bet. secs. 21 & 28
with same var.
30.00 Ridge bears NW & SE
40.15 set Granite 11 x 11 x 7 in
projs. in the ground for
¼ sec. cor. marked ¼
on N. face; and raised
a mound of stone alongside
62.00 Gulch drains NW.
80.30 The cor. to secs. 20, 21, 28 & 29
Land Impenetrable on 80.30 ch.
Soil 2d rate.

BOOK A-201

(Red Lake) Meridian

to Timber.
Dense Undergrowth.

Note:
The line further north is impracticable.

Subdivisions T. 24 S. R. 4 W.

From the cor. to Secs. on the south boundary of the Tp.
Secs. 31 & 32, which is
a Granite 24 x 24 x 6 in.
with stone mound, Drum
North bet. Secs. 31 & 32
Var. 16° E.

Descend

40.00 set Granite 12 x 12 x 9
ins. 8 ins in the ground
for 1/4 sec. cor. marked 1/4
on W. face, and raised
a mound of stone along
side.

41.50 Kunk Creek 3 lks. wide
runs N. Crane's cabin &
spring up the creek about
8 chs. Corral North of
same.

60.00 Ridge bears N. & S.

80.00 set a Granite 16 x 10 x 8 ins

Subdivisions T. 24 S. R. 4½ W.

10 lks. in the ground
for cor. to secs. 29, 30, 31 &
32, marked 5 notches
on E. & W. edges, and
raised a mound of
stone alongside.
Land Regulations good.
Soil 2d & 1st rate.
Timber.
Dense Undergrowth.

East on a random line
bet. secs. 29 & 32
Var. 16° E.
40.00 set temp. ¼ sec. cor.
80.16 Intersect N. & S. line 7
links S. of cor. to secs. 28,
29, 32 & 33. from which

S. 89°57' W. on the line
bet. Secs. 29 & 32
with same Var.

8.00 Land Spring Holler drains
SE.

25.00 Ridge bears N W & S E.

40.08 set Granite 12 x 11 x 10
ins. 8 ins. in the gro
for ¼ sec. cor. marked
+ on t. face, and
raised a mound of
stone alongside.

59.00 Ridge bears N & S W.

80.16 The cor. to secs. 29. 30. 31
& 32,

Land mountainous
Soil 2d. rate.
No timber,
Dense underwood.

80.16 chs.

Salt Lake Meridian.

West on a random line
bet. Secs. 30 & 31
Var. 16° E.

40.00 Set temp. 1/4 Sec. Cor.

39.50 Intersect N. boundary of
the Tp. 50 links N. of the
cor. to Secs. 25.30.31 & 36,
which is a Granite 40 x
30 x 4 ins. with mound
of stone, from which
N. 89° 39' E. on a true line
bet. Secs. 30 & 31
with same var.

39.50 Set Granite 13 x 12 x 9 ins.
8 ins. in the ground for
1/4 Sec. Cor. marked 1/4
on N. face & raised a
mound of stone along
side.

Subdivisions T. 27 S. R. 4½

15.50 Ledge drains S.
62.50 Ridge bears N & S.
79.50 the cor. to secs. 29. 30. 31 & 32,

Land mountainous
Soil 2d. rate.
No timber,
Dense undergrowth

North bet. secs. 29 & 30
Var. 16° E.
22.40 Ridge bears NE & SW.
40.00 set Granite 14×10×8 in
quis. in the ground
for ¼ sec. cor. marked
¼ on W. face, and
raised a mound of
stone alongside,

Subdivisions T. 14 S. R. 4½ W.

49.60 Gulch drains N.
68.50 Ridge leans N.W. & S.E.
80.00 Set a Granite 15 x 10 x 5 ins. 10 ins. in the ground for cor to secs. 19, 20, 29 & 30, marked 5 notches on E. & 2 on S. Edges, and said a mound of stone already.

Land mound on sec line 2d rate, No timber Dense under growth.

on 74.50 chs

on 80.00

Subdivisions T. 24 S. R. 4 1/2 W.

East on a random line
bet. secs. 20 & 29
Var. 16° E.

40.00 Set temp. 1/4 sec. cor.
79.88 Tal. west N. & S. line 21 lks
N. of the cor. to secs. 20, 21,
28 & 29, from which
N. 89° 51' W. on true line
bet. secs. 20 & 29
with same var.
24.00 Gulch passing W.
39.94 Set Granite 13 x 11 x 9 ins.
8 ins. in the ground
for 1/4 sec. cor. marked
4 on N. face, and
raised a mound of
stone alongside,
44.00 Ridge bearing W. & E.
54.30 Gulch drains N. W.
79.88 The cor. to secs. 19, 20, 29 & 30.

Land mountainous, pr. 78

BOOK A-201

Salt Lake Meridian

Seal 2d Sale.
October,
Dense undergrowth,
Jany 12, 1884

Note: On account of the mountains I abandon further survey of this Township.

General Description

The surveyed portion of this township is mountainous, and contains plenty of cedar, pine and aspen timber, and excellent water; and is a fine summer range for stock there being sufficient grass for that purpose. The soil is generally first rate. There are settlements in sees, 32, 28, 35, 25 & 36, among which is James A. Rose the applicant for the survey, whose improvements consist of four cabins built of logs, two corrals, and some large waterring troughs situated in the S.W.¼ of the

SW¼ & SW¼ of NW¼ Sec. 35.
The cabin and corrall lying north of these improvements in the same section, probably belong to him also, but this could not be definitely determined.
The numerous springs and streams are running with pure cold water.
There are no indications of mineral.

Edward W. Kveler
U.S. Depy. Surveyor.

BOOK-A-201

[4—LIST OF NAMES.]

A list of the names of the individuals employed by Edward W. Kocher *United States deputy surveyor, to assist in running, measuring, and marking the lines and corners described in the foregoing field notes of the survey of* the exteriors and subdivision lines in Tps. 24 & 25 S. R. 4 1/2 W.

of the Salt Lake base and meridian in the Territory of Utah, showing the respective capacities in which they acted.

	Compassman.
Anthony Whatcott	*Chainman.*
James H. Day	*Chainman.*
	Chainman.
	Chainman.
Joseph Haadee	*Axeman.*
Marion W. Lott	*Axeman, and Flagman,*

BOOK-A-201

[5.—FINAL OATHS OF ASSISTANTS.]

We hereby certify that we assisted Edward W. Koeber United States deputy surveyor, in surveying all those parts or portions of the Exterior and subdivision lines of Tps. 24 & 25 S. R. 4 1/2 W.

of the Salt Lake base and meridian in the Territory of Utah, as are represented in the foregoing field notes as having been surveyed by him and under his direction; and that said survey has been in all respects, to the best of our knowledge and belief, well and faithfully surveyed, and the corner monuments established according to the instructions furnished by the United States surveyor-general for Utah.

....., Compassman.

Anthony Walker, Chainman.

James H. Day, Chainman.

....., Chainman.

....., Chainman.

[illegible], Axeman.

Marion W. Lott, Axeman. and

....., Flagman.

Subscribed and sworn to before me this 12th day of January 1884

Edward W. Koeber

U. S. Dep. Surv.

BOOK-A-201

[5.—FINAL OATHS OF ASSISTANTS.]

We hereby certify that we assisted Edward W. Roeber United States deputy surveyor, in surveying all those parts or portions of the Exterior and subdivision lines of Tps. 24 & 25 S. R. 4 1/2 W.

of the Salt Lake base and meridian in the Territory of Utah, as are represented in the foregoing field notes as having been surveyed by him and under his direction; and that said survey has been in all respects, to the best of our knowledge and belief, well and faithfully surveyed, and the corner monuments established according to the instructions furnished by the United States surveyor-general for Utah.

, Compassman.

Anthony H. Hale, Chainman.

James H. Day, Chainman.

, Chainman.

, Chainman.

, Axeman.

Marion W. Lott, Axeman. and

, Flagman.

Subscribed and sworn to before me this 12th day of January 1884

Edward W. Roeber

U. S. Dep. Surv.

ner described in the field notes, and that the foregoing are the **TRUE** field notes of such survey; and, should any fraud be detected, I will [illegible] the penalty of perjury, under the provisions of an act of Congress, approved August 8, 1846.

Edward W. Hocker

United States Deputy Surveyor.

Subscribed and sworn to before me this 17th day of January 1884

Jno. A. Bailey,

Notary Public

BOOK-A-201

S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, April 8 *1884.*

The foregoing field notes of the survey of the Subdivisions of the fractional *Township No.* 24 South *Range No.* 4½ West *Executed by* Edward F. Kocher *Under* his *contract* No. 122 *of the* 4th *day of* December *1883., in the month of* January *1884., having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

Fred Salomon

U. S. Surveyor General for Utah.

BOOK-A-201

3

REPORT: 1884

Filed 188

Examined by .....

Transcribed by E Michaelis

Compared by J A Michael & E Michaelis

FIELD NOTES

OF THE SURVEY OF THE

North, and Five Miles of the East Boundaries, and Re-survey of 1 Mile of East Boundary

OF

Township No 25 South

Range No 4 1/2 W.

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Edward W. Koeber

U. S. Deputy Surveyor,

Under his Contract No. 122

Dated Dec. 4th 1883

Survey commenced Dec. 25th 1883

Survey completed " 29 188

BOOK-A-201

[3 PRELIMINARY OATH OF AXEMEN.]

We, Joseph Hadden

and Marion W. Lott

do solemnly swear that we will well and truly perform the duties of axemen, in the establishment of corners, and other duties, according to instructions given us, and to the best of our skill and ability, in the survey of the exterior and subdivision lines of T. 24 & 25 S. R. 4½ W.

of the Salt Lake base and meridian in the Territory of Utah.

Joseph Hadden, Axeman.

Marion W. Lott, Axeman.

Subscribed and sworn to before me this 27th day of Dec. 1883

Edward W. Roder
U. S. Dep. Sur.

BOOK-A-201

[2.—PRELIMINARY OATH OF CHAINMEN.]

We, Anthony Whatcott

and James H. Day

do solemnly swear that we will well and faithfully execute the duties of chain carriers; that we will level the chain upon even and uneven ground and plum the tally pins, either by sticking or dropping the same; that we will report the true distance to all notable objects, and the true length of all lines that we assist in measuring, to the best of our skill and ability, and in accordance with instructions given us, in the survey of the Exterior and subdivision lines of Tps. 24 & 25 S. R. 4 1/2 W.

of the Salt Lake base and meridian in the Territory of Utah.

Anthony Whatcott, Chainman.

James H. Day, Chainman.

, Chainman.

, Chainman.

Subscribed and sworn to before me this 27th day of Dec 1883

Edward W. Fisher

U. S. Deputy Surv

BOOK-A-201

East Boundary T. 25 S. R. 4½ W.

Note:

See the note at the beginning of the field notes of the survey of the 5th Standard Parallel South in Range 4½ W, which fully explains the cause and creation of this fractional numbered range, and which has been accepted and approved.

Befor commencing this survey an observation on the star Polaris is taken, and the meridian line determined, on which I test my compass and find it in adjustment.

Survey commenced December 28th 1883, with a Burts improved solar compass.

106 Re-Survey of
East Boundary T. 25 S. R. 4½ W.

chains I begin at the establish
standard cor. to T. 25 S. R.
4 & 4½ W, which is a
Granite Rock 25 x 20 x 20
ins, marked S.C, with sy
notches on the N. E. & W.
Edges, with a mound of
stone alongside,
Thence, on a Re-Survey
line, I run
North between Secs. 31 & 36
Var. 17° E.
1.80 Gulch drains W.
6.80 Ridge bears N E & S W.
16.80 Top of Bluffs " " "; descend
26.80 Find the old witness cor. sto
chiseled over, which is a
Trachyte Rock 15 x 7 x 7 ins,
properly marked — I reset
same 10 ins. in the ground
and rebuild the mound
of stone alongside.
From this point John S. Lott's
cabin, and field — —
bears N. 63° W. 20 chains dist.

BOOK-
La

35.00 Cle
can
mi
36.40 Roc
36.80 I fi
dis
I ns
gro
for
sec.
mon
40.00 The
the
set
tea
Cha
pro
set
wit
W.
whi
gu
44.00 To
of
80.00 Fi

Lucs Lake Meridian

35.00 Clear Creek in bottom of Cañon, runs East; 20 lks wide

36.40 Road bears E & W.

36.80 I find the old witness ¼ sec. stone displaced, which is a limestone I reset same 9. ins, in the ground properly marked for re-established witness ¼ sec. cor. and rebuild the mound of stone alongside.

40.00 The ¼ sec. point falling in the bluffs, the cor. is not set, and chaining impracticable, I therefore at 36.80 chains, Run East 7.20 chains from which point a flag, set in line North of the witness ¼ sec. cor. bears N. 45° W. which gives 7.20 chains, which being added to 36.80 gives the distance on line as

44.00 To top of bluffs on N. side of the Cañon –

80.00 Find the old stone standing

which is a Limestone 15x8x7 inc, properly marked for cor. to secs. 25, 30. 31 & 36, and rebuild the stone named alongside.

Land mountainous on 80 chs.

Soil 3d rate.

No Timber.

— End of Re-Survey —

East Ban

chains

Nor

18.50 Lea

23.00 Gap

one

St.

36.50 Bas

40.00 Set

inc,

1/4 s

N. f

A Pin

A ced

each

Ale

80.00 On

Set

ins.

cor.

4 n

edge

of s

A ced

mark

Lan

East Boundary T. 25 S. R. 4 1/2 W.

chains

North bet. secs. 25 & 30
Var. 17° E.

18.50 Ridge bears N.E. & S.W.

23.00 Gap at head of two gulches one drains N.E. the other S.W.

36.50 Wash in hollow drains S.E.

40.00 Set Pudding stone 17x8x4 ins, 11 ins. in the ground for 1/4 sec. cor. marked 1/4 on N. face, from which
A Pinion 9 ins. dia. bears S. 30 W. 26 lks.
A cedar 9 " " " N. 88 E. 21 "
each marked 1/4 S 13 T.
Attempted along E.E. slope

80.00 On East slope of mountain set a Pudding stone 15x6x5 ins. 10 ins. in the ground for cor. to secs. 19, 24, 25 & 30, marked 4 notches on N. & E. on South edges, and raised a mound of stone along side from which
A cedar 9 ins. dia. bears S. 43° E. 30 lks
marked S. 30. T. 25 S. R. 4 W. B.T.
Land mountainous, on 80. chs.

East boundary T. 25 S. R. 4

Soil 3d rate - rocky.
A few cedars and pinions.

—"—

Arch bet. Secs. 19 & 24.
Var. 17° E.

5.00 Ridge bears E & W.
7.50 Gulch drains E.
13.00 " " "
23.00 " " "
29.50 Junction of Gulches heading N E & S W. draining E.
34.00 S. E. point of ridge.
37.00 Gulch drains S E.
40.00 set Shale Rock 20 x 7 x 5 ins. 15 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on W. face, from which
A Pinion 5 ins. dia. bears N 55° E. 35 lks
" " 6" " " N. 23° W. 55 "
Both trees marked 1/4 S. B. T.
45.00 South point of ridge
50.00 Gulch drains S W.
56.00 East point of ridge.

BOOK A-201

Salt Lake Meridian

58.50 Gulch drains S.E.
64.30 " " S.W.
80.00 Set a Granite 18x14x11 ins, 12 ins. in the ground for cor. to secs. 13. 18. 19 & 24, marked 3 Notches on N. & S. Edges ~~for cor. to secs.~~ from which A Pinus Quis. dis. bears S. 70°E. 30 lks.
" " 5 " " " N. 10°W. 22 "
" " 12 " " " S. 89°W. 50 "
" " 6 " " " N. 8°E. 48 "
Trees all marked with the proper Tp. R. and Section.
Land Mountainous on 80chs.
Soil 3rd rate - rocky.
A few cedar & Pinus.

"

Note to Secs. 13 & 18
Var. 17° E.

1.00 Ridge bears E. & W.
10.50 Gulch drains E.
30.00 Flat top ridge bears S.E. & N.W.
40.00 Set Trachyte 20x15x6 ins. 15 ins.

East bdy. T. 25 S. R. 4½ W.

in the ground for ¼ sec. cor.
Marked ¼ on W. face, and
raised a mound of stones
alongside.

42.50 Gulch drains E.

53.00 " " "

70.00 Ridge bears SE & NW.

80.00 Set Granite 13x7x6 ins.
8 ins. in the ground for cor.
to secs. 7, 12, 13 & 18. Marked
2 notches on E. & 4 on S.
Edges, and raised mound
of stone alongside.
Land Mountainous & rocky
Soil & rocky.
No timber.

North bet. secs. 7 & 12
Var. 17° E.

7.50 Gulch drains SE.

31.50 Ridge bears SE & NW

35.00 Gulch drains E.

40.00 Set Trachyte 18x10x5 ins.

BOOK A-201

East Boundary T. 26 S. R. 4 & 5 W.

12 ins. in the ground for
1/4 sec. cor. marked 1/4 on
N. face, and raised a
mound of stone alongside.
14.00 Ridge bears 1 E & 1 W, thence
descend to
80.00 Set Trachyte 18 x 7 x 6 ins,
12 ins. in the ground
for cor. to secs. 1, 6, 7 & 12
marked 1 notch on E. & 5
on S. Edges, and raised
a mound of stone alongside.
Land Mountainous & rocky.
Soil 3d rate — rocky.
Dense oak brush.

Arch bet. secs. 1 & 6
Var. 17° E.
10.50 Deep Gulch drains N.
34.00 Deep Gulch " E; Spring
30 links E. drains E.
40.00 Set Trachyte 18 x 10 x 8 ins. 12
ins. in the ground for 1/4 sec.

East bay. S. 25 L. & R. 4½ W.

Cor. marked 4 on W. face & raised a mound of stones alongside.

5.00 Ridge bears E. & W.

75.00 Creek crossing E.

8.00 set Granite 16×12×10 in. in the ground for cor. to Sec. 24 & 25. S. R. 4 & 4½ W. marked 6 notches on N. E. & W. edge and raised a mound of stone alongside.

Land mountainous and soil 3d rate. Mostly heavy oak brush.

Dec. 28th 1883.

BOOK-A

Anch

3.00 Le

BOOK-A-201

North Boundary T. 26 S. R. 4½ W.

From the corner to Tps 24 & 25 S. R. 4 & 4½ W, I run West on a random line between said Townships, the variation of my compass being 17° E, setting temporary corners at 40 & 80 chains, and at 3 miles 79 chains & 60 links I intersect the W. boundary of the Tp. 150 links N. of the township cor. The true bearing of the true line will therefore be N. 89° 49' E. and the correction 28 links S. per mile.

From the cor. to Tps. 24 & 26 S. R. 4½ & 5 W, which is a Granite 30 x 15 x 4 ins. with stone mound, I run
N. 89° 49' E. bet. Sec. 6 & 31
Var. 17° E.

3.00 Leave gulch drains S.W. and leave timber.

Northbdy. Tp. 25 S. R. 4½ W.

34.00 Skunk Creek 4 links wide
drains NW.

39.60 set Granite 20 x 17 x 10 ins, 15 ins.
in the ground for ¼ sec. cor,
marked ¼ on S. face, and
raised a mound of stone
alongside.

57.00 Ditch drains NW.

79.60 Set, on top of Ridge bears
N & S, a Granite 24 x 24 x 6
ins. 18 ins. in the ground
for cor. to secs. 5, 6, 31 & 32
marked 5 notches on E. & W
on N. Edges and raised a
mound of stone alongside.
Land & Monuments on 79.60 chs
soil, 1st & 3d rate.
No timber except cedar & pine
on N. 3 chains.
Dense oak brush.

BOOK-A-201

Salt Lake Meridian.

Arch S 89 49' E. on line bet. secs. 5 & 32.

Var. 19° E

12.00 Spring 150 lks. N. drains E.

17.25 Hollow drains S.

16.00 Ridge bears SE & NW.

20.30 Wash drains SE.

14.00 Set Granite 24 x 15 x 7 ins. 18 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on E. face, mound raised & mound of stone alongside

14.00 Ridge bears NW. & SE.

16.30 Gulch drains NW.

20.00 Set Granite 18 x 10 x 10 ins. 12 ins. in the ground for Cor. to secs. 4. 5. 32 & 33. marked 4 notches on E. & 2 on W. edges, and raised a mound of stone alongside.

Land mountainous & 80 chs.

Soil 3d rate.

Dense undergrowth —

No timber.

North bdy. T. 25 S. R. 4½ W.

N. 89°49' E. on true line
bet. Secs. 4 & 33
Var. 19° E.

5.00 Ridge bears. 1 E x 1 N.
30.00 Wash drains S.W.
40.00 Set Sandstone 17 x 15 x 15 ins.
11 ins. in the ground for
¼ sec. cor. Marked ¼ x on
E. face, and raised a
mound of stone around
65.00 Wash drains S.W.
80.00 Set Granite 30 x 18 x 10 ins. 20 ins.
in the ground for cor. to sec.
3, 4, 33 & 34, Marked 3 notches
on E & W. edges, and raised
a mound of stone around
Land Mountains are so cho-
ked 3° rails.
Dense undergrowth and
some aspen.

BOOK A

Sa

N. 8

10.00 Re
29.00 No
40.00 Se
in
cor.
ac
24
50.00 Re
68.00 Se
80.00 Set
in
2. 3
on
rai
alm
La
S
N
Sa

Salt Lake Meridian.

N. 89°49' E. on true line
bet. Secs. 3 & 34
Var. 17° E.

10.00 Ridge bears N. & S.
29.00 Node draws S.
40.00 Set Granite 14 x 12 x 5 ins. 10 ins.
in the ground for 1/4 sec.
cor. marked 1/4 on E. face,
and raised a mound of
stone alongside.
50.00 Ridge bears N. & S.
68.00 Gulch draws S.
80.00 Set granite 16 x 9 x 5 ins. 10 ins.
in the ground for cor. to secs.
2. 3. 34 & 35, marked 2 notches
on E. & 4 on N. Edges, and
raised a mound of stone
alongside.
Land mountainous on 80 chs.
Soil 3rd rate.
Heavy undergrowth and
some aspen timber.

North boundary Sp. 25. S.R 4/27.

N. 89°49' E. on a true line
bet. secs. 27 & 35
Var. 17° E.

1.00 Ridge, bears N. & S.
6.00 Deep hollow drains SE.
30.00 Ridge bears NW & SE.
40.00 In flat hollow drains S. set a
Granite 18 x 13 x 7 ins. 10 ins. in
the ground for 1/4 sec. cor.
Marked 1/4 on S. face & raised
a mound of stone alongside.
55.00 Low Ridge bears NW & SE.
68.00 Hollow drains NW.
76.50 Ridge bears NW & NE.
80.00 Set Granite 16 x 6 x 5 ins. 10 ins.
in the ground for cor. to secs.
12. 33 & 34, Marked 1 Notch
on E. and 3 on W. Edges, &
raised a mound of stone
alongside.
Land undulating or rocky.
Soil 2nd rate.
Scattering aspen, and heavy
underbrush.

BOOK-A-201

Salt Lake Meridian

N. 89°49' E. on true line
bet. Secs. 1 & 36
Var. 17° E.

25.00 Flat hollow drains S.E. & trail in same.

38.00 Ridge bears N.W. & S.E.

40.00 Set Trachyte 12 x 10 x 4 ins. 8 ins in the ground for 1/4 sec. cor. marked 1/4 on N. face from which

Aulespen 7 ins. dia. bears S 72° E. 24 links
" " 2 1/2 " " " N 40° W. 15 "
Both trees marked 1/4 S. B. T.

55.50 Gulch drains S.E.

58.00 Ridge bears N.W. & S.E.

70.00 Gulch drains N.

74.50 Ridge bears N.E. & S.W.

80.00 The cor. to Tps. 2 & 25 S. R. 4 X 4 1/2 W.

Land Monuments on
80 chains
Soil 3d rate.
Scattering quaking asp
and Dense undergrowth.

Note:
For General Description
see end of Subdivision
notes.

Edward W. Kucker
U. S. Deputy Surveyor

BOOK-A-201

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, April 2 *1884.*

The foregoing field notes of the survey of the South 5 miles of the East boundaries, and resurvey of 1 mile of the East boundary

Township No. 25 South *Range No.* 4½ W.

Executed by Edward W. Kaeber

Under his *contract* No. 122 *of the* 4th *day of* December *1883, in the month of* December *1883, having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

Fred Salomon

U. S. Surveyor General for Utah.

BOOK-A-201

6

REPORT: 1884

Filed 188

Examined by .....

Transcribed by Michaelis

Compared by J. A. Mitchell & E. Michaelis

FIELD NOTES

OF THE SURVEY OF THE

Subdivision lines

OF

Township No 25 South

Range No 4½ West

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Edward H. Kloeber

U. S. Deputy Surveyor,

Under his Contract No. 122

Dated December 1883

Survey commenced Dec. 31st 1883

Survey completed Jan 8th 188X

BOOK-A-201

Township 25 South R. 4½ West

115	117	118	119	120	121
6 189	5 170	4 158	3 146	2 134	1 113
187	186	169	157	145	132
7 183	8 168	9 156	10 144	11 132	12 112
184	183	167	155	143	131
18 182	17 166	16 154	15 142	14 130	13 114
181	180	165	153	141	129
19 179	20 164	21 152	22 140	23 128	24 115
177	176	163	151	139	127
30 175	29 162	28 150	27 137	26 126	25 108
174	173	161	149	136	125
31 172	32 160	33 148	34 135	35 123	36 106

BOOK A 201

Subdivisions of T. 25 S. R. 4 1/2 W.

Note:

See the note at the beginning of the field notes of the East boundary of this township.

Before commencing the subdivision of this tp, I tested my compass on my meridian, and find it correct.

Survey commenced Dec. 31st 1883, with a Burt's improved solar compass.

From the established stand and cor. to sec. 35 & 36, which is a Trachyte Rock 36 x 36 x 12 ins, with stone mound and 3 bearing trees, I run North bet. sec. 35 & 36

Var. 17° E.

In Gulch drains N.W.

Subdivision Tp. 25 S. R 4½ W. S.L.M.

30.00 Bluff on S. side of Cañon E&W
35.00 Clear Creek 16 links wide runs E.
and Road on S. side of Creek
between E & W. Skinners House and field East of house E. 32 chs.
40.00 Set Limestone 30x12x8 ins. 2 cubic inches ground for ¼ sec. cor. marked ¼ on N. face, and raised a mound of stone along side. Ascend
42.00 Top of rocky bluffs, E&W.
80.00 Set Limestone 15x10x8 ins. 10 ins. in the ground for cor. to secs. 25. 26. 35 & 36, marked 1 notch on S. & E. edges, and raised mound of stone alongside.
Land mountainous, or rocky
Soil 3d rate.
No timber.

Subdiv

Ea

40.00 Se

80.26 Sub
che
25
Lim
San
Dr
M

18.00 Lim
40.13 On
Lim
in c
Mark
ouv
along
60.00 Set
80.26 Th
Lan
Sou

Subdivisions Tp. 25 S. R. 4½ W S.L.M.

East on a random line between secs. 25 & 36
Var. 17° E.

40.00 set temp. ¼ sec. cor.

40.26 Intersect East boundary of the Tp. at the cor. to secs. 25, 30, 31 & 36, which is a Limestone 15 x 8 x 7 ins with stone mound, from which I run

West on true line between secs. 25 & 36.
with some Var.

18.00 Reach S. W.

40.13 On SW point of Ridge, set a Limestone 18 x 10 x 6 ins. 12 ins in the ground for ¼ sec. cor. Marked ¼ on N face, and raised a mound of stone alongside.

60.00 Reach Drain SW.

80.26 The cor. to secs. 25, 30, 31 & 36, on bd. 24 chs. land broken and timbered.
Soil 3rd qlty. rocky.
No Timber.

Subdivisions Tp. 25 S. R. 4½ W. S.L.M.

North bet. secs. 25 & 36
Var. 17° E.

2500 Ridge bears SW & NE.

4000 Set Limestone 15 x 12 x 9 ins. 10 ins. in the ground for ¼ sec. cor. marked ¼ on N. face, and raised a mound of stone alongside.

5300 Gulch draws SW.

8000 Set Granite 17 x 12 x 10 ins. 11 ins. in the ground for cor. to secs. 23, 24, 25 & 26, marked 1 notch on E. & 2 on S. Edges, & raised a mound of stone alongside.

Land Mountainous & Rocky on 80 chs.
Soil 3d rate –
Timber –

— —

Subdivisions T. 25 S. R. 4 1/2 W. S.L.M.

East on a random line
bet. secs. 24 & 25
Var. 17° E.

~~10.00 Box Culvert drains SE.~~

40.00 set temp. 1/4 sec. cor.

80.30 Quarre at E. boundary of the Tp.
7 links S. of cor. to secs. 19, 24, 25
30, from which I run
S. 87° 15' W. on true line
bet. secs. 24 & 25
with same var.

Observed

10.00 Ridge bears SW & NE.

40.15 Ridge " S. set Granite
15 x 10 x 9 ins. 10 ins. in the
ground for 1/4 sec. cor. marked
1/4 on N. face, and raised a
mound of stone alongside.

70.00 Box Culvert drains SE.

80.30 The cor. to secs. 23, 24, 25 & 26
on 80.30 chs.
Land mountainous & Rocky

Soil 3d rate -

No timber -

Subdivision Tp. 25 S. R. 4½ W. S.L.M.

North bet. secs. 23 & 24
Var. 17° E.

5.00 Box Cotton drains S.E.
10.00 Ridge bears E & W.
30.00 Gulch drains W.
40.00 Ridge bears SW & NE - set a Granite 20x15x8 ins. 15 ins. in the ground for ¼ sec. cor. marked ¼ on W. face and raised a mound of stone alongside.
43.00 Enter gulch drains SW. head North.
52.50 Leave the gulch -
58.00 Ridge bears NE & SW.
74.00 Gulch drains SW.
80.00 set Granite 40x20x10 ins. 26 ins. in the ground for cor. to secs. 13. 14. 23 & 24, marked 1 Notch on E. & 3 on S. Edges and raised a mound of stone alongside.

Land Mountainous & rocky on 80 chs.
Soil 3d rate.
No timber -

BOOK-A-201

Subdivisions Tp. 20 S. R. 4 1/2 W. S.L.M.

East on a random line
bet. secs. 18 & 24
bar. 17°E.

40.00 set temp. 1/4 sec. cor.

80.32 Intersect East boundary of the Tp. 28 links South of the cor. to secs. 13.18.19 & 24, which is a Granite 18 x 14 x 11 ins. with stone mound, from which
S. 89°48' W. on a true line
bet. secs. 19 & 24.
bar. same bar.

30.00 Ridge bears S 17 W. 15

40.16 set Granite 15 x 9 x 6 ins. 10 ins. in the ground for 1/4 sec. cor. marked 1/4 on N. side, & raised a mound of stone alongside.

75.00 Gulch drains SW.

80.32 The cor. to secs. 13.14.23 & 24 on 80.32 chs.
Land mountainous & Rocky
soil 3° rate.
Dense undergrowth.
etc timber.

Subdivision T. 25 S. R. 4½ W. S.L.M.

Arch bet. secs. 13 & 14
Var. 19° E.

33.50 Divide bears N & S.

40.00 set Granite 24 x 24 x 8 ins. 18 inches in the ground for ¼ sec. cor. marked ¼ on N. face, and raised a mound of stone along side.

60.20 Gulch draws S.

78.00 Ridge bears S.W. & S.E.

80.00 set Granite 20 x 15 x 10 ins. 15 inches in the ground for cor. to secs. 11, 12, 13 & 14, marked 1 notch on E. & two on S. Edges, and raised mound of stone along side.

Land between mountains on 80.00 chs. soil 3d rate.

Dense in virgin rock.

No. 2. over.

Subdivision Tp. 25 S. R. 4½ W. S.L.M.

East on a random line
bet. secs. 12 & 13
Var. 17° E.

40.00 set temp. ¼ sec. cor.
0.20 Intersect E. boundary of the
Tp. 14 chs. S. of the cor. to secs.
7, 12, 13 & 18, which is a blaze
13 x 7 x 6 ins. with stone mound,
from which
S. 89° 54' W. on true line
bet. secs. 12 & 13.
with same Var.
0.10 On Ridge bears S. & N. set a
Granite 18 x 12 x 4 ins. 12 ins.
in the ground, for ¼ sec. cor.
marked ¼ on N. face, and
raised a mound of stone
alongside.
15.00 Ridge bears NE & SW.
0.20 The cor. to secs. 11, 12, 13 & 14,
Land rocky mountainous on 80.20 chs
soil 3d Rate.
Dense undergrowth
No timber.

Subdivis. Sp. 25 S.R. 4½

Arch bet. secs. 11 & 12
Var. 17° E.

20.00 Creek draws S.W.

40.00 set Granite 18×15×10 ins. 12 ins. in the ground for ¼ sec. cor. Marked ¼ on W. face, and raised mound of stones alongside.

73.00 Ridge bears NE & SW.

80.00 set Granite 20×17×12 ins. 15 ins. in the ground for cor. to secs. 1, 2, 11 & 12, marked ¼ on West or E. & S on S. Edge and raised mound of stones alongside.

Land Mountainous 80 chs.
Soil 3d rate.
Dense undergrowth.
No timber.

Dec. 31. 1883

BOOK-A-201

Salt Lake Meridian

East on a random line
bet. Secs. 1 & 12
Var. 17° E.

40.00 set temp. 1/4 sec. cor.

80.26 Intersect E. boundary of the
Tp. 7 lks. south of the cor.
to secs. 1, 6, 7 & 12, which is a
Trachyte 18 x 7 x 6 ins. with sine
mound, from which
S. 89° 57' W. on true line
bet. Secs. 1 & 12
with same Var.

10.00 Gulch or riv. NE.

35.00 Ridge bears NW & SE.

40.13 set Granite 15 x 10 x 8 ins. 10
ins. in the ground for 1/4
sec. cor. marked 1/4 on N.
face, and raised a mound
of stones alongside

75.00 Ridge bears NE & SW.

80.26 The cor. to secs. 1, 2, 11 & 12,
Land Mountainous on 80.26 chs
Soil 3d rate.
Dense undergrowth —
No timber —

Subdivisions Tp. 25 S. R. 4½ W. S.L.M.

North on a meandered line
bet. Secs. 1 & 2.
Var. 17° E.

40.00 Set temp. 1/4 Sec. Cor.
30.00 Intersect the N. boundary
of the Sp. at the cor. to
Secs. 1 & 2, 35 & 36, on which is
a Granite 16 x 6 x 5 ins.
with stone mound,
from which
Search on a true line
bet. Secs 1 & 2
with same Var.
20.00 Track drains E.
36.00 Ridge bears E & W.
40.10 Set Granite 25 x 15 x 12 ins. 18
ins. in the ground for 1/4
Sec. Cor. marked 1/4 on N.
face, and raised a mound
of stone alongside.
47.50 Ditch drains SE
57.00 Ridge bears SE & NW
66.50 Ditch drains NW.
80.10 The cor. to Secs. 1, 2, 11 & 12
Land mountainous on 80.10 chs.
Sol. 3d Sec. Dunsmuir approved
Wylinder.

Subdivision T. 25 S. R. 4½ W.

From the standard cor. to secs. 34 & 35, which is a limestone 16×12×10 ins, with a mound of stone, I run North bet. secs. 34 & 35
Var. 17° E.
along W. slope to
Top of bluffs on S. side
2.00 of Cañon: Ascend to
29.75 Clear Creek 15 lks. wide
heads NW. runs NE. and E. end of
32.00 cabin E. about 35 chs. with
field as shown on the plat:
36.25 Road, bears E. & W. ascend
40.00 Set chalk stone 18×8×6 ins. 12
ins. in the ground for ¼
sec. cor. marked ¼ on W. face
and raised a mound of
stone alongside.
50.00 Top of bluffs.
58.50 Gulch draws SE.
65.50 Gully " SW.
75.00 " " "
78.73 Bluff 50 ft. high. bears E & W.

Subdivisions Tp. 25 S. R. 4½ W. S.L.M.

80.00 Set Chalk Stone 20×5×5 ins. 15 ins. in the ground for cor. to secs. 26. 27. 34 & 35, marked 2 notches on E. and 1 on S. Edges, and raised a mound of stone alongside. Land Mountainous on 80 chs. Soil rocky; 3d rate. Dense undergrowth on 43.70 chs. N. part.

No timber.

East on random line bet. secs. 26 & 35 Var. 17° E.

40.00 set temp. ¼ sec. cor.

80.00 Intersect N. & S. line 4 links N. of cor. to secs. 25. 26. 35 & 36, from which

N. 89° 57' W. on true line bet. secs. 26 & 35 with same var.

30.00 Descend.

Subdivi

40.00 set

ins. i

cor. t

and

stone

45.00 Cross

ing

65.00 S.E.

80.00 The

Lan

Soil

Dens

No

Nor

0.00 Inter

15.00 Set

33.50 Desc

40.00 State

2×1

¼ sec

N. fa

mou

BOOK A 201

Subdivisions Tp. 25 S. R. 4½ W. S.L.M.

40.00 set Sandstone 15 x 10 x 8 ins. 10 ins. in the ground for ¼ sec. cor. marked ¼ on N. face and raised a mound of stone alongside.

45.00 Creek 5 links wide runs S. in Bx Canon.

65.00 SE. point of bluffs.

80.00 The cor. to secs. 26, 27, 34 & 35. Land monumented on so. chs. Soil 3d. rate. Dense undergrowth. No timber.

North bet. secs. 26 & 27
Var. 17° E.

0.00 Enter cedars

15.00 Gulch draining SW.

33.50 Descend.

40.00 Stationary chalk Rock 2½ x 2 x 1 ft. above ground for ¼ sec. cor. marked ¼ on N. face, and raised a mound of stone alongside. mph. across

Subdivisions T. 25 S. R. 4½ W. S.L.M.

44.00 Gulch drains S.E. and enter small Cove, and leave cedars.

77.00 Leave Cove and enter timber

80.00 Set chalkstone 20×8×8 ins. 15 ins. in the ground, for cor. to secs. 22.23.26 & 27, marked 2 notches on E. & W. edges, and raised a pyramid of stone alongside, pyramid & cedar 18 in. dia. bears S. 20° E. 20 lks.
" " 20 " " " N 88° W. 30 "
Both trees marked with the proper T. R. & Section.
Land mountainous on 80. chs. Soil 3d rate. Rocky
Timber cedar & pinion on 67 chains.

BOOK-A-201

Subdivision Tp. 25 S. R. 4½ W. S.L.M.

East on random line
bet. Secs. 23 & 26
Var. 17° E.

40.00 set temp. ¼ Sec. cor.

80.10 Intersect N. & S. line 9 lks. N. of cor. to secs. 23, 24, 25 & 26 from which
N. 89° 56' W. on true line
bet. Secs. 23 & 26
with same Var.

20.00 Ridge bears S.E. & N.W.

40.05 On Edge of bluff; set Limestone 18 x 10 x 8 ins. 12 ins. in the ground for ¼ Sec. cor. marked ¼ on N. face and raised a mound of stone alongside.

50.00 Creek 5 lks. wide runs S.E. in Box Canon.

73.00 Ascend ledge — and enter timber.

80.10 The cor. to secs. 22, 23, 26 & 27
Land mountainous on 80.10 chs.
Soil rocky: 3d rate.
Dense undergrowth.

Subdivisions S. 25 S. R. 4 W.

Cedar timber, on W. & cho.

"

North bet. Secs. 22 & 23
Var. 17° E.

6.50 S.E. point of Ridge
10.00 Bluffs — Descend
21.50 Cross 5 links wide, runs S.E. in Box Cañon.
26.00 Leave Cañon & ascend.
37.00 Low Ridge bears SE. & NW.
40.00 set Granite 14×10×4 ins. 10 ins in the ground for 1/4 sec. cor. marked 1/4 on W. face, from which A Pinus quis. dia. bears S15°E. 30 links
" " 15 " " " N51°W. 47 " Both trees marked 1/4 S.B.T.
64.50 Ridge bears NE & SW.
80.00 set Granite 20×20×4 ins. 15 ins. in the ground for cor. to secs. 14, 15, 22 & 23. marked 2 notches on E. & 3 on S. edges and raised a mound of stones alongside, from which

BOOK-A-2

A Pin
" "
" Cedar
Tree
forks
sectio
Lar
N.
Pinu

East

40.00 set
80.22 Inter
N. of
from
N. 8

A seg
22.00 Pi
De

BOOK-A-201

East Lake Meridian

A Pine 14 ins. dia. bears N 30° E. 25 lks.
" " 14 " " " S. 38° W. 45 "
" Cedar 24 " " " N. 17° W. 40 "
Trees all marked with the
proper township, Range &
section.
Land Mountainous on 80. chs.
Soil 3rd rate. Rocky
Timber, Cedar and Pine.
January 2nd 1884

"

East on random line
bet. Secs. 14 & 23
Var. 17° E.
40.00 set temp. 1/4 sec. cor.
80.22 Intersect N. & S. line 18 links
N. of cor. to secs. 13. 14. 23 & 24
from which
N. 89° 52' W. on true line
bet. Secs. 14 & 23.
with same Var.
Ascend to
22.00 Ridge bears N. & S.
Descend to

Subdivisions Sp. 25 S. R. 4½ W. S.L.M.

40.11 set Granite 15 x 9 x 8 ins. 10 ins. in the ground for ¼ sec. cor. marked ¼ on E. face, and raised a mound of stone alongside.

45.00 Gulch draws S.E.

55.50 Ridge bears N.E. & S.W.

65.00 Gulch draws S.W.

77.00 Ridge bears N. & S.

80.22 The cor. to secs. 14, 15, 22 & 23.

Land mountainous, on 80.22 ch.

Soil rocky – 3d rate.

Dense undergrowth.

No timber.

"

North bet. secs. 14 & 15

Var. 17° E.

5.00 Leave timber on Ridge bears S.E. & N.

25.00 Enter high Plateau N.W. & S.E.

40.00 set granite 20 x 12 x 4 ins. 15 ins. in the ground for ¼ sec. cor. marked ¼ on W. face, and

Subdivisions T. 25 S. R. 4 1/2 W.

raised a mound of stone alongside,

45.50 Descend from Plateau

61.50 Head of hollow drains SE.

75.00 " " " SW.

80.00 Set Granite 20x8x5 ins. 15 ins. in the ground for cor. to secs. 10. 11. 14 & 15, Marked 2 notches on E. & 4 on S. Edges, and raised mound of stone along side.

Land mountainous, on 80. chs.

Soil 3rd rate - rocky.

Dense undergrowth.

No timber.

East on a random line bet. secs. 11 & 14

Var. 17° E.

40.00 set temp. 1/4 sec. cor.

80.06 Intersect N. & S. line 21 links S. of cor. to secs. 11. 12. 13 & 14, from which

N. 39° 51' W. on true line

Subdivisions Tp. 25 S. R. 4½ W. S. L.

bet. Secs. 11 & 14
with same Var.

40.03 In bulch drains SW. set a Granite 20 x 9 x 8 ins. 15 ins in the ground for ¼ Sec. cor. Marked ¼ on E. face and raised a mound of stone alongside.

49.00 Ridge bears SE & NW.

59.00 bulch drains SE.

80.06 The cor. to secs. 10, 11, 14 & 15.
Land Mountainous on 80.06 chs.
Soil 3d rate - rocky -
Dense undergrowth -
No timber.

North bet. Secs. 10 & 11
Var. 17° E.
Over high plateau -

40.00 set Granite 15 x 8 x 6 ins. 10 ins. in the ground for ¼ Sec. cor. Marked ¼ on N. face, and raised a

Subdivisions Tp. 25 S. R. 9½ W. S.L.M.

mound of stone alongside,
51.00 Leave Plateau bears S.E. & N.W.
56.00 Gully drains S.E.
80.00 Set Granite 20x14x4 ins. 15 ins. in the ground for cor. to secs. 2.3.10 & 11, marked 2 notches on E. & 5 on S. Edges and raised a mound of stone alongside.
Land, Mountain Plateau-
Soil 2 rate.
Dense undergrowth on 80. chs.
No timber.

East on a random line
bet. secs. 2 & 11
Var. 17° E.
40.00 set temp. ¼ sec. cor.
80.12 Intersect N. & S. line 14 lks.
South of the cor. to secs. 1.2.11 & 12
from which
S. 89°.54' W. on true line
bet. secs. 2 & 11

Subdivisions T. 25 S. R. 4½ W. S.L.M.

with same Var.

18.00 Leech drains S.W.

40.06 set Granite 15×14×9 sis. 10 ins. in the ground for ¼ sec. cor. marked ¼ on N. face, and raised a mound of stone along side.

60.00 Ridge bears N. & S.

75.00 Wash in hollow drains S.E.

80.12 The cor. to secs. 2, 3, 10 & 11.

Land mountainous on 80.12 chs.

Soil 3rd rate. Rocky—

Dense undergrowth

No timber.

North on a random line bet. secs. 2 & 3.

Var. 17° E.

40.00 set temp. ¼ sec. cor.

80.40 Intersect North boundary of the township 14 links W. of the cor. to secs. 2, 3, 34 & 35, which

BOOK-A-201

Subdivisions T. 25 S. R. 4½ W.

is a Granite 16 x 9 x 5 ins.
with Stone mound, from which
S. 0.06 W on a true line
bet. secs. 2 & 3
with same bar.

~~20.00 Gully drains E.~~
~~23.50 Leave hollow.~~
Along top of Spur all Ridge to
6.00 Descend S point of Ridge.
10.00 Head of Gulch drains S E.
20.00 Enter Cove Hollow drains S E.
28.00 Leave " " " "
40.40 set Granite 25 x 13 x 10 ins. 18 ins
in the ground for ¼ sec. cor.
marked ¼ on W. face & raised
a mound of stone alongside.
46.50 Enter Sandy hollow.
60.00 Gully drains E.
80.40 The cor. to secs. 2. 3. 10 & 11
Land mountainous on 80.40 chs.
Soil 3d rate.
Dense undergrowth.
No Timber.

Subdivisions T. 25 S. R. 4½ W. S.L.M.

From the standard cor.
to secs. 33 & 34, which is
a Limestone 30 x 20 x 10 ins.
with stone mound, I run
North bet. secs. 33 & 34
Var. 17° E.

Descend, to
10.00 Cooper field bears N & NW.
15.00 Robinson's House about 15 chs
19.00 Road bears N & NW. & leave
field — Cultivated land along
South side of the Road E & W.
as shown on the plat.
20.00 Clear Creek 15 lks. Mid opposite
35.00 Ascend; leave Cañon — entry notes.
40.00 Set Granite 14 x 8 x 5 ins. gu
in the ground for ¼ sec. cor.
Marked ¼ on W. face & said
a mound of stone alongside
50.00 Gulch drains SE.
76.00 Gulch " "
80.00 Set Trachyte 18 x 8 x 5 ins. 12 in
in the ground for cor. to secs.
27, 28, 33 & 34, Marked 3 Sections

Subdivisions T. 25 S. R. 4½ W. S.L.M.

on E. & W. S. Edges, and raised a mound of stone alongside.
Land Mountainous 55 chs.
Soil 1st rate in the Cañon, balance 3rd rate: rocky.
Dense mullergrass except in the fields, on 55 chs.
No timber.

East on random line
bet. Secs. 24 & 34
Var. 17° E.

40.00	set temp. 1/4 sec. cor.
79.90	intersect N. & S. line 9 links S. of cor. to secs. 26, 27, 34 & 35 from which
	S. 89° 56' W. on a true line bet. Secs. 24 & 34 with same Var.
20.00	Gulch drains S. E. leave timber.
35.00	" " " "
39.95	set Trachyte stone 15 x 9 x 6 ins. 10 ins. in the ground

Subdivisions Tp. 25 S. R. 4½ W. S.L.M.

for ¼ sec. cor. marked ¼ on N. face, and raised a mound of stone alongside & refer as bars.

7.00 Gulch drains &c.

79.90 The cor. to secs. 27, 28, 33 & 34, Land mountainous on 77.40 chs. Soil rocky; 3d rate. Dense undergrowth, and cedar timber as noted.

Arch bet. secs. 27 & 28
Var. 17° E.

7.00 Gulch drains &c.

40.00 set Granite 13×8×6 ins. 8 ins. in the ground for ¼ sec. cor. marked ¼ on N. face and raised a mound of stone alongside,

44.50 Deep Gulch drains &c.

67.50 " " " " "

80.00 set a Volcanic Rock 13×9×6 ins (8 ins in ground) for cor. to secs. 21, 22, 27 & 28

Subdivisions T. 25 S. R. 4½ W.

marked 3 notches on E, and 2 on S. Edges, and raised a mound of stone alongside. Land mountainous on 80 chs. Soil 3d rate - rocky. Timber cedar & Pinon.

Jany 3 1884

East and random line bet. secs. 22 & 27 Var. 17° E.

40.00 set temp. ¼ sec. cor.

80.18 Intersect N. & S. line 14 links S. of cor. to secs. 22, 23, 26 & 27, from which S. 89°54' W. on true line bet. secs. 22 & 27 with same var.

7.00 Rocky bluffs bear SW & NE.

40.09 On Ridge " SE & NW. set a Granite stone 15 x 11 x 9 ins, 10 ins. in the ground for ¼ sec. cor. marked ¼ on N. face, and raised a mound

Subdivisions Tp. 25 S. R. 4½ W. S.L.M.

of stone alongside.
66.50 Gulch drains S.E.
80.18 The cor. to secs. 21, 22, 27 & 28;
Land mountainous on 80.18 Ch.
Soil 3d rate rocky.
Timber cedar & pinion.

Arch bet. secs. 21 & 22
Var. 17° E.
15.00 Ridge bears N.W. & S.E.
16.50 Gulch drains S.E.
40.00 Set Volcanic Rock 13 x 8 x 5 ins.
8 ins. in the ground for
¼ sec. cor. marked ¼ on W.
face, and raised a mound
of stone along side.
50.00 Ridge bears S.E. & N.W.
68.00 Gulch drains E.
80.00 Set Granite 17 x 8 x 8 ins. 11
ins. in the ground for cor.
to secs. 15, 16, 21 & 22; marked
3 notches on E. & S. Edges, &
raised a mound of stone

Subdivisions Tp. 25 S. R. 4½ W. S.L.M.

alongside.
Land mountainous 80 chs.
Soil 3rd rate - rocky
Timber Cedar and Pinon

East on random line
bet. Secs. 15 & 22
Var. 17° E.
14.00 set temp. ¼ sec. cor.
79.88 Intersect N.S. line 21 links
South of cor. to secs. 14.15.22 & 23
from which
S. 89° 51' W. on true line
bet. Secs. 15 & 22
with same var.
6.00 Gulch drains S.W.
15.00 Ridge bears N. & S.W.
20.00 Gulch drains S.W.
27.00 Ridge bears N. & S.
39.94 In box Cairn drains S.E. set
Granite 15 x 13 x 6 ins. 10 ins.
in the ground for ¼ sec. cor.
marked ¼ on N. face and

Subdivision of T. 25 S. R. 4½ W. S.L.M.

raised a mound of stone
alongside. — Along S. E. slope
79.88 the cor. to secs. 15. 16. 21 & 22.
Land mountainous on 79.88 chs.
Soil 3d rate — rocky.
Timber Cedar & Pinon.

North bet. secs. 15 & 16
Var 17° E.
Leave timber & enter brush &
ascend.
40.00 set Granite 30×12×10 ins. 20
ins. in the ground for ¼
sec. cor. marked ¼ on W. face
and raised a mound of
stone along side.
70.00 Enter Plateau —
80.00 set a Granite 18×9×5 ins. 12
ins. in the ground for cor. to
secs. 9. 10. 15 & 16. Marked 3
notches on E. & 4 on S. Edges
and raised mound of
stone alongside.

BOOK-A-201

Subdivisions T. 25 S. R. 4½ W.

Land mountainous 80 chs
Soil 3d rate —
Dense oak brush undergrowth.

East on random line bet
secs. 10 & 15
Var. 17° E.
40.00 set temp. ¼ sec. cor.
80.00 Intersect N. & S. line 14 links
S. of cor. to secs. 10, 11, 14 & 15,
from which
S. 89° 54' W. on true line
bet. secs. 10 & 15
with same bar.
[illegible]00 Ridge bears SW & NE.
[illegible]0.00 Deep gulch draws SW.
[illegible]0.00 set trachyte stone 15 x 10 x 5 ins.
10 ins. in the ground for
¼ sec. cor. marked ¼ on N.
face, and raised a mound
of stone alongside.
[illegible]0.00 S. E. point of high ridge,
[illegible]6.50 Gulch draws SE.

Subdivision Tp. 25 S. R. 4½ W. S.L.M.

Ascend to
79.80 Enter plateau.
80.00 The cor. to secs. 9, 10, 15 & 16,
Land meandered 80 chs.
Soil 3d rate.
Dense undergrowth.
No timber.

North bet. secs. 9 & 10
Var. 17° E.
40.00 set Granite 15 x 13 x 7 ins.,
10 ins. in the ground for 1/4
sec. cor. marked 1/4 on N. fa
and raised a mound of
stone alongside.
50.00 Leave plateau & enter a
broad hollow drains S. E.
80.00 set Granite 12 x 8 x 6 ins. stu
in the ground for cor. to sec
3, 4, 9 & 10, marked 3 notches
on E. & 5 on S. edges, and
raised a mound of stone
alongside.

Subd
Lan
Do
Den
Sma

East

40.00 set
79.86 Inte
S. of
rah
S. 89

17.00 Lea
39.93 set
in
Mar
rais
alon
50.00 Rid
70.00 Was

Subdivisions T. 25 S. R. 4½ W. S.L.M.

Land rolling and broken -
Soil 2nd rate.
Dense undergrowth on 80 chs and
some aspen trees.

East on a random line
bet. secs. 3 & 10.
Var. 17° E.

40.00 set temp. ¼ sec. cor.
79.86 Intersect N. & S. line 40 links
S. of cor. to secs. 2, 3, 10 & 11, from
which,
S. 89° 43' W. on true line
bet. secs. 3 & 10
with same var.
17.00 Leave hollow & ascend
39.93 set Granite 18 x 16 x 4 ins. 12 ins
in the ground for ¼ sec. cor.
Marked ¼ on N. face and
raised a mound of stone
alongside.
50.00 Ridge bears N. & S.
70.00 Wash drains S.E. Enter hollow.

Subdivisions Tp. 25 S. R. 4½ W. S.L.M.

79.86 The cor. to secs. 3, 4, ~~10~~ 9 & 10 & 11.
Land mountainous on 79.86 chs.
Soil 2d rate.
Dense undergrowth.

—"—

Search on a random line
bet. secs. 3 & 4.
Var. 17° E.

~~30.00~~ Leave the bottom.
40.00 set temp. ¼ sec. cor.
80.60 Intersect N. boundary 21 lks
West of the cor. to secs. 3, 4, 33
& 34 which is a Granite 30 x
18 x 10 ins. with stone mound,
from which
S.0. 9° W. on true line
bet. secs. 3 & 4.
with same var.
12.00 Ridge bears SW & NE.
20.00 Enter broad flat below SW.
35.00 Leave same S.E.
40.60 set Granite 22 x 17 x 6 ins.
15 ins. in the ground for

BOOK A-201

Subdivisions T. 25 S. R. 4½ W.

¼ sec. cor. marked ¼ on
W. face, and raised a
mound of stone alongside.
50.00 Inter Sande hollow, S W.
80.60 The cor. to secs. 3.4. 9 & 10.
Land mountainous.
Soil 2d rate.
Dense undergrowth on 80.60
chs.
No timber.

January 4th 1894

Subdivisions T. 25. S. R. 4 1/2 W. S. L. M.

From the standard cor. to
Secs. 32 & 33, which is a
Limestone 18x15x7 ins. 12 in
in the ground for with
stone mound, I run
North bet. Secs. 32 & 33
Var. 17° E.

17.00 Gulch drains N.
34.10 Clear Creek 15 lks. wide runs E.
35.10 Road bears E. & W.
40.00 set Limestone 15x11x7 ins.
10 ins. in the ground for
1/4 sec. cor. marked 1/4 on
N. face ~~for~~ and raised
a mound of stone alongside
47.50 Top of bluffs on N. side of Cañon
65.00 Ridge bears SW & NE.
66.00 Gulch drains SW.
80.00 Stationary Granite boulder
3x2x2 ft. above ground for
cor. to Secs. 28. 29. 32 & 33, marked
with a cross & 4 notches on E. Edge, and
1 on South edge, and raised
a mound of stone alongside.

BOOK-A-201

Subdivisions Tp. 25 S. R. 4½ W. S.L.M.

Land Mountainous & rocky
Soil 3rd rate.
Dense undergrowth on 80 chs.
No timber.

East on random line
bet. secs. 28 & 33
Var. 17° E.

40.00 set temp. ¼ sec. cor.
80.46 Intersect N.S. line 21 links
south of cor. to secs. 27.28.33 & 34
from which
S. 89° 51' W. on true line
bet. secs. 28 & 33
with same var.
4.00 bunch drains S.E.
40.23 set boulder 18 x 11 x 7 ins.
12 ins. in the ground for
¼ sec. cor. marked ¼ on
N. face, and raised a
mound of stone alongside.
73.00 S.E. point of Ridge.
80.46 The cor. to secs. 28.29.32 & 33

Subdivisions T. 25 S. R. 41 W. 6th P.M.

Land mountainous
Soil 3d rate.
Dense undergrowth, on
80.46 chs.
N. bounder

North bet. secs. 28 & 29
Var. 17° E.

10.00 Ridge bears SE & NW.
20.00 Wash draws SE, and a spring in same abut 150 lks. SE.
40.00 set Granite 18 x 8 x 7 ins. 10 ins. in the ground for 1/4 sec. cor. marked 1/4 on N. face, and raised a mound of stone along side.
46.00 Gulch draws E.
80.50 set Granite 17 x 17 x 10 ins. 11 ins. in the ground for cor. to secs. 20, 21, 28 & 29 marked 4 notches on E. & 2 on S. edges, and raised a mound

Subdivisions T. 25 S. R. 4 1/2 W.

of stone alongside.
Land undulations on 80 chs.
Soil 3d rate.
Dense undergrowth.
No timber.

East on random line
bet. Secs. 2/728
Var. 14° E.
40.00 set trip. 1/4 sec. cor.
80.12 Intersect N.&S. line 14 lks
S. of cor. to secs. 21, 22, 2/728,
from which
S. 89°54' W. on true line
bet. Secs. 21 & 28
with same Var.
15.00 Branch drains S.W.
35.00 Ridge bears S.W. & N.E.
40.06 set hackyte 18x12x6 ins.
12 ins. in the ground for
1/4 sec. cor. marked 1/4 on
N. face and raised a
mound of stone alongside.

Subdivisions T. 25 S. R. 4½ W. S.L.

60.00 Gulch drains S.E.
80.12 The cor. to secs. 20.21.28 & 29
Land mountainous poor soil 3d rate. 80.12 chs.
Dense underbrush
Timber.

North bet. secs. 20 & 21
Var. 17° E.
5.00 E. point of hill.
23.50 Ravine drains S.E.
40.00 On top of mountain bears E. & W. Set Granite 20 x 20 x 10 ins. 15 ins. in the ground for ¼ sec cor. marked ¼ on N face and raised a mound of stone alongside.
52.00 Gulch drains W.
80.00 Set Granite 17 x 15 x 9 ins. 11 ins. in the ground for cor. to secs. 16.17.20 & 21 Marked 4 notches on

B006-A-201

son S. Edge, and raised
a mound of stone along
side.
Land mountainous rocks.
Soil 3° rate on S. ½;
" 1st " on N ½.
Dense undergrowth.
No timber.

"

East on random line
bet. secs. 16 & 21
Var. 19° E.

40.00 set tries, ¼ sec. cor.
80.44 Intersect N. & S. line 16 links
S. of cor. to secs. 15. 16. 21 & 22
from which
S. 89° 53' W. on true line
bet. secs. 16 & 21
with same Var.
along S. E. slope to
16.00 Gulch drains S. E.
25.00 Ridge bears NW & SE.
40.22 set Granite 18 x 11 x 9 ins.

Subdivisions T. 25 S. R. 4 W. S.L.M.

12 mis. in the ground for 1/4 sec. cor. marked 1/4 on N. face and raised a mound of stone alongside.

72.00 Top of mountain bears NW & SE.

80.44 The cor. to secs. 16, 17, 20 & 21, Land mountains on 80.44 ch.s. Soil 1st & 3d rate. Dense undergrowth. No timber.

"

North bet. secs. 16 & 17
Var. 14° E.

5.00 Head of hollow, drains W.

70.00 Top of mountain bears NW & SE.

35.00 Nash drains S.E.

40.00 On Ridge bears SE & NW; set Granite 40 x 20 x 20 ins. 30 ins. in the ground for 1/4 sec. cor. marked 1/4 on N. face and raised a mound of stone alongside.

Subdivisions Tp. 25 S. R. 4½ W. S.L.M.

15.00 Enter hollow drains S.E.
5.00 Leave " " "
5.00 Ridge bears S.E. & N.W.
0.00 set granite 20x20x10 ins.
16 ins. in the ground for
cor. to secs. 8. 9. 16 & 17, marked
4 notches on E. & S. Edges,
and raised a mound of
stone alongside.
Land undulating on 80. chs.
Soil 1st rate.
Dense undergrowth,
No timber.

East on a random line
bet. secs. 9 & 16.
Var. 17° E.
40.00 set temp. ¼ sec. cor.
80.32 Intersect N. & S. line 9
links S. of cor. to secs.
9. 10. 15 & 16, from which
S 89° 56' W. on true line
bet. secs. 9 & 16

Subdivisions No. 25 S. R. 4 W. S.B.M.

with same var.
Over high mountain
plateau.

40.16 set Granite 15 x 10 x 5 ins.
10 ins. in the ground for
1/4 sec. cor. marked 1/4
on W. face, and raised
a mound of stone
alongside.

80.32 The cor. to secs. 8, 9, 16 & 17
Land mountainous
soil 1st rate, grassy
Dense under growth
on 80.32 chs.
No timber.

North bet. secs. 8 & 9
Var. 17° E

3.50 wash drains W. thence
over high mountain
plateau.

40.00 set granite 36 x 30 x 20 ins.
27 ins. in the ground
for 1/4 sec. cor. marked
1/4 on W. face, and raised

BOOK-A-201

Subdivisions T. 25 S. R. 4½ W. S.L.M.

mound of stone along side.

80.00 ~~the~~ set Granite 18x16 x9 ins. 12 ins. in the ground for cor. to secs. 4.5, 8 & 9, marked 4 & 5 on E. & 5 on S. Edges, and raised mound of stone alongside.

Land mountainous.
Soil 1st rate.
Dense undergrowth
on 80. chs.
Timber.

"

East on random line
bet. secs. 4 & 9
Var. 17° E.

40.00 set temp. ¼ sec. cor.

80.46 Intersect N. & S. line 32 lks S. of cor. to secs. 3, 4, 9 & 10, from which
S 89° 46' W. on true line
bet. secs. 4 & 9.

Subdivisions Tp. 25 S. R. 4½ W. S. L. M.

with same var.

20.00 Leave hollow drains S.E.

29.00 Ridge bears N. & S.W.

40.23 set Trachyte 18x8x4 ins., 12 ins. in the ground for ¼ sec. cor. marked ¼ on face, and raised a mound of stone along side.

75.00 Gulch drains W.

80.46 The cor. to secs. 4, 5, 8 & 9, Land very high rolling, soil 1st & 3d rate. Dense undergrowth on 80.46 ch. some aspens.

"

North on a random line bet. secs. 4 & 5 Var. 17° E.

40.00 set temp. ¼ sec. cor.

80.70 Intersect the north boundary 13¼ links, W. of the cor. to secs. 4, 5, 32 & 33, which is a

Subdivisions Tp. 25 S. R. 4½ W. S.L.M.

Granite 18×10×10 ins,
with stone mound from
which
S.0.6 W. on true line
bet. Secs. 4 & 5
with same var.

70.00 Top of Mountain bears E & W.

40.70 ~~Lxx~~ Lizzie Boulder 5
×5×5 ft, above ground
for 1/4 sec. cor. marked 1/4
on W. face and cross
and raised
a mound of stone along
side,

75.00 Pole Creek Canon draws N.W.

80.70 The cor. to Secs. 4, 5, 8 & 9,
Land Mountainous on 80.70 chs.
Soil 3d rate.
Dense undergrowth,
No timber.
January 5. 1884.

Subdivisions T. 25 S. R. 4½ W. S.L.M.

From the Stat. cor. to sec. 31 & 32 (which is a limestone 6 inches above ground with 4 bearing trees standing and properly marked) I saw:

North bet. secs. 31 & 32
Var. 17° E.

Descend

36.00 To Edge of bluffs on S. side of canon, large timber

37.25 W.T.R. G.R.R. & W. trade bears S.E. & N.W.

38.00 Clear Creek 15 lks. wide runs S.E. heads S.W.

38.50 Road bears E. & W.; Ascend

40.00 set Granite 15 x 6 x 6 ins. 10 ins. in the ground for sec. cor. marked 1/4 on N. face & I raised a mound of stone along side.

80.00 Granite 17 x 8 x 6 ins. 11 ins. in the ground for cor. to secs. 29, 30, 31 & 32, marked 5 notches on E. & 1 on S. edges, and raised a mound of stone along side.

Land meandered on 80 chains.

Subdiv

De
Ba
D
Ce

Ea

40.00 set
79.96 Inte
the
& 33
N

Ove

39.98 set
10 in
1/4 o
N.
a 1/4
side

43.00 S.M

Subdivisions Sp. 25 S. R. 17 W. S.B.M.

Soil 1st rate in canon,
Balance 3d rate & rocky.
Dense undergrowth,
Cedar timber on 36. chs.

—"—

East on a random line
bet. secs. 29 & 32
Var. 17° E.
40.00 set temp. 1/4 sec. cor.,
79.96 intersect N. & S. line at
the cor. to secs. 28, 29, 32
& 33, from which
West on true line
bet. secs 29 & 32
with same Var.
Over broken ledges & rocks
3.98 set Granite 15 x 10 x 5 ins.,
10 ins. in the ground for
1/4 sec. cor. Marked 1/4 on
N. face, and raised
a mound of stone along
side,
43.00 S. to point of Ridge.

Subdivision No. 25 S. R. 4½ W. S. & M.

55.00 Lunch drains S.W.
65.00 Low ridge bears S.W. & N.
73.00 Lunch drains S.W.
79.96 The cor. to secs. 29.30.31 & 36 on 79.96 ch.
Land mountainous
Soil 3d rate, rocky
Dense underwood

No timber.

"

Mstr a random line
bet. secs. 30 & 31
Var. 17° E.
40.00 set temp. ¼ sec. cor.
79.90 The intersect the mst boundary
7 links S. of the cor. to secs. 25, 30.31 & 36, which is a Granite
30×12×4 ins. with stone mound
from which
S. 89° 57' E. on a true line
bet. secs. 30 & 31
with same Var.
35.00 Deer Creek 3 lks wide runs

Subdivisi

in V
9.40 set t
ins
sec.
face
of st
63.00 Ridg
79.90 The
Lam
Soi
Den
A f

Am

Asce
26.00 Red
40.00 set
ins.
¼ sec
W. fa
A Pum
Aceda

14 BOOK A-201

Subdivisions Sec. 25 T. R. 4½ W. G. & S. R. M.

in Upper Cook Canon.

9.40 set Granite 15×10×6 ins. 10 ins in the ground for 1/4 sec. cor. marked 1/4 on N face and raised a mound of stone alongside. Ascend.

6.00 Ridge SW & N. Descend to

19.90 the cor. to secs. 29. 30. 31 & 32

Land mountainous on 79.90 chs.

Soil 3d rate.

Dense undergrowth.

A few cedar.

North bet. secs. 29 & 30

Var. 17° E.

Ascend SE. Slope of mountain

26.00 Ridge bears N. & S.

40.00 set Granite 20×12×8 ins. 15 ins. in the ground for 1/4 sec. cor. marked 4 on W. face, and from which

A Pine 8 ins. dia. bears S 50° W. 20 lks.

A Cedar 5 " " " S 40 E. 22 "

Subdivisions Tp. 25 S. R. 4½ W. 2d M.

Both trees marked 1/4 S.B.C.

42.40 Inch drains SW.

58.00 Cedar ridge bears N & SW,

80.00 Set granite 19x12x6 ins. 12 ins. in the ground for cor. to secs. 19, 20, 29 & 30, from which a Pine 4 ins. dia. bears S. 10° W. 30 l.
A Cedar 6 " " " S. 88° E. 7 "
" " 4 " " " N 40 E. 4 "
" " 5 " " " S. 46° W. 80 "
Trees all marked with the proper Tp. & R, and section.
Land very broken & mountainous
Soil 3d rate. gn 80. cho.
Timber cedar & pine.

East on random line
bet. secs. 20 & 29
Var. 17° E.

40.00 set temp. 1/4 sec. cor.

80.04 Intersect N. & S. line 14 links S. of cor. to secs. 20, 21, 28 & 29 from which

BOOK-A-201

Subdivision T. 25 S. R. 4½ W. S. L. M.

S. 89°54' W. on a true line
bet. secs. 20 & 29
with same var.

40.02 In gulch drains SE. set a
Granite 15 x 10 x 8 ins. 10 ins
in the ground for ¼ sec.
cor. marked 4 on N. face
and raised a mound of
stone alongside,

60.00 Ridge bears SE & NW.

80.04 The cor. to secs. 19. 20. 29 & 30,
Land Mountainous, 80.04 chs.
Soil 3d rate.
Cedar Timber on N. 8 chs.
Dense undergrowth.

—"—

Meet on a random line
bet. secs. 19 & 30,
var. 17° E.

40.00 set temp. ¼ sec. cor.

79.86 Intersect the West boundary
14 links S. of the cor. to secs.
19. 24. 25 & 30, which is a

Subdivision of T. 25 S. R. 4½ W. G. & S. R.

Trachyte 14×12×9 ins. 9 ins. in the ground with stone mound, from which S. 89° 54' E. on true line bet. secs. 19 & 30 with same bar.

13.00 ~~Extra~~ Lead timber & plate on ascend.

38.76 ~~Hare~~ Pole Creek 6 ins. wide runs S. in canon.

76.30 Gulch draws SW. & enters hanging

39.86 set Trachyte 15×10×5 ins. 16 ins. in the ground for ¼ sec. cor. marked ¼ on N. face, and raised a mound of stone alongside.

76.30 Gulch draws SW. & enters hanging

79.86 The cor. to secs. 19, 20, 29 & 30.

Land mountainous on 79.86 chs.

Soil 3d rate.

Dense underbrush cedar timber as note.

BOOK A-201

Subdivisions T. 25 S. R. 4½ W. W.M.

North bet. secs. 19 & 20
Var. 17° E.

4.00 Gulch drains SW.
8.00 Leave timber.
30.00 High Ridge bears N. & S.
36.00 Gulch Drains SW.
40.00 set Granite 20×10×8 ins. 15 ins. in the ground for ¼ sec. cor. marked ¼ on W. face, and raised a mound of stone alongside.
56.00 Gulch drains SW. thence along W. slope of high Plateau.
80.00 set granite 20×12×8 ins. 15 ins. in the ground for cor. to secs. 17. 18. 19 & 20, marked 5 notches on E. & 3 on S. edges and raised a mound of stone alongside, from which a cedar 6 ins. dia. bears N. 30° E. 3 links dist, marked S. 17. T. 25 S. R. 4½ W. B. T.

Land mountainous on so. chs. Soil 3d rate. Dense under growth = Cedar on S. 8 chs.

Subdivision Tp. 25 S. R. 4½ W. S.L.M.

East on a random line
bet. secs. 17 & 20
Var. 17° E.

40.00 set temp. ¼ sec. cor.
79.92 Intersect N. & S. line 21 links
south of cor. to secs. 16. 17. 20 & 21
from which
S. 89° 51' W. on true line
bet. secs. 17 & 20
with same Var.
15.00 Enter flat holler drains S.
and enter plateau
25.00 Leave " " " " "
39.96 ~~40.00~~ set Granite 18 x 12 x 6 ins. 12 in
in the ground for ¼ sec. cor.
Marked ¼ on N. face, X
raised a mound of stone
alongside.
71.00 Descend from Plateau.
79.92 The cor. to secs. 17, 18, 19 & 20.
Land mountainous ~~80.00~~
Soil 3d rate.
Dense undergrowth
79.92
No timber.

Jany 7. 84

Subdivisions T. 25 S. R. 41 W. 2 P.M.

West on a random line
bet. secs. 18 & 19
Var. 17° E.

40.00 set temp. 1/4 sec. cor.
39.78 Intersect N. boundary of the Tp. 26 links S. of the cor. to secs. 13. 18. 19. & 24, which is a Trachyte 15 x 11 x 9 ins, with stone mound from which
S. 89° 49' E." on true line
bet. secs. 18 & 19
with same Var.
7.00 Gulch drains SE. Leave timber.
20.00 Ridge bears NW. & SE.; Descend
36.30 Pole Creek 10 lks. wide runs S. in canon.
39.78 Set trachyte 15 x 12 x 9 ins, 10 ins. in the ground for 1/4 sec. cor. Marked 4 on N. face, and raised a mound of stone alongside.
Ascend to
72.50 Plateau bears N & S.
79.78 The cor. to secs. 17, 18, 19 & 20,

Subdivision T. 25 S. R. 4½ W. S.L.M.

Land monumented
Soil 3d rate. 79.78 chs.
Dense under growth.
Cedar on W. 7 chs.

"

Arch bet. secs. 17 & 18
Var. 17° E.

3.50 Flat hollow drains N.W.
4.50 Leave " & ascend to
10.00 Euler plateau E & W.
27.00 Small flat hollow drains N.W.
33.50 Gulch drains W.
40.00 set Granite 20×16×8 ins. 15 ins. in the ground for ¼ sec. cor. marked 4 on W. face and raised a mound of stone alongside.
57.50 Leave plateau. descend to
70.00 Deep Gulch drains W. Good
75.50 Granite ledge 175 ft high
80.00 set Granite 18×10×5 ins. 12 ins. in the ground for cor. to secs. 7, 8, 17 & 18, marked 5

Subdivis

Note
and
stone
Leave
Do
Dep
80. chs.

Eas

40.00 set
39.90 & le
S. of
plan
S. 89°

15.00 Hol
39.95 Set
ins.
sec.
face

Subdivision T. 25 S. R. 4½ E. G.&S.R.M.

notches on E. & W. sides and raised a mound of stone alongside.

Land Meandered.
Soil & rock - rocky.
Dense undergrowth, on
80 chs. No timber.

"

East on a random line
bet. secs. 8 & 17
Var. 17° E.

40.00 set temp. 1/4 sec. cor.
79.90 & intersect N. & S. line 7 lks.
S. of the cor. to secs. 8, 9, 16 & 17
pts. which
S. 89°36' W. on a true line
bet. secs. 8 & 17
with same Var.
15.00 Hollow drains S.
39.95 Set Granite 19x12x10 ins., 12
ins. in the ground for 1/4
sec. cor. marked 1/4 on E.
face & raised a mound of stone

Subdivision Tp. 25 S. R. 4½ W. S.L.M.

almost dry,
55.00 Gulch drains SW,
79.70 The cor. to secs. 7, 8, 17 & 18,
Land mountainous on
Soil 3d rate. 79.70 chs.
Dense undergrowth.
No timber,

Met on random line
bet. secs. 7 & 18
Var. 17° E.
40.00 set temp. ¼ sec. cor.
79.70 Intersect Met boundary
of the Tp. 14 links S. of the
cor. to secs. 7, 12, 13 & 18, which
is a Granite 24 x 15 x 7 ins
with stone mound, pmdpts
S. 89° 54' E. on a true line
bet. secs. 7 & 18
with same Var.
6.00 Gulch drains SE.
20.00 Ridge bears NW. Descend
30.10 Dole Creek 10 lks wide, runs N
& leave timber.

BOOK-A-201

Subdivisions T. 35 S. R. 4½ W. S.L.M.

39.70 On E. side of Cañon drains S.
set Trachyte 18 x 11 x 4 ins., 12
ins. in the ground for
¼ sec. cor. marked ¼ on
N. face, and raised a
mound of stone alongside.
68.00 Enter plateau.
79.70 The cor. to secs. 7, 8, 17 & 18,
Land Mountainous on 79.70 chs.
Soil 1st & 3d rate.
Dense undergrowth.
Cedar timber on W. 30.10 chs.

North bet. secs. 7 & 8
Var. 17° E.
Over mountain plateau.
40.00 set Granite 30 x 20 x 6 ins.
20 ins. in the ground
for ¼ sec. cor. marked ¼
on W. face, and raised
a mound of stone along
side.
65.00 Head of hollow drains S.W.

Subdivisions T. 25 S. R. 4½ W. S.L.M.

8000 Set Granite 27 x 12 x 8 ins.
18 ins. in the ground for
cor. to secs. 5. 6. 7 & 8, marked
5 notches on E. & S. Edges
and raised a mound of
stone alongside.
Land high mountain Plateau
soil 2d & 1st rate.
Dense undergrowth on
Timber.

(80.00)

East on random line
bet. Secs. 5 & 8.
Var. 17° E.
40.00 Set temp. ¼ Sec. cor.
79.86 Intersect N & S. line 40 lks.
S. of cor. to secs. 4. 5. 8 & 9
from which
S. 59° 43' W. on true line
bet. secs. 5 & 8
with same var.
Over high rolling mountain
plateau.

Subdivisions Tp. 26 S. R. 4½ W. G.&S.M.

39.93 set Granite 15 x 9 x 8 ins.,
10 ins. in the ground for
¼ Sec. cor. Marked ¼ on
N. face, and raised a
mound of stone along
side.

39.80 The cor. to secs. 5.6.7 & 8.,
Land high mountain
plateau.
Soil 1st. rate.
Dense undergrowth on
no timber.

on 80 chs.

on 79.86 chs.

"

Met on a random line
bet. secs. 6 & 7
Var. 17° E.

40.00 set temp. ¼ sec. cor.
79.60 Intersect W. boundary of
the Tp. 40 links S. of
the cor. to secs. 1.6.7 & 12
which is a Granite 20 x
12 x 8 ins. with stone
mound from which

Subdivisions T. 25 S. R. 4½ W. S.L.M.

S. 89° 43' E. on a true line
bet. secs. 6 & 7
with same var.

3.00 Knoll on line.
13.00 Spur Ridge bears S 75° W
25.00 Pole creek 12 lks. wide, runs
near junction of canons,
39.60 Set Granite 16 x 9 x 8 in
10 ins. in the ground for
¼ sec. Cor. marked ¼ on
N. face and raised a
mound of stone alongside
Ascend
60.00 Entir plateau bears S 6° W
79.60 The cor. to secs. 5, 6, 7 & 8
Land mountainous on 79.
Soil 1st & 3rd rate.
Dense undergrowth,
No timber.

BOOK-A-201

Subdivisions T. 25 S. R. 41 E. M. D. M.

Mich on a random line
bet. Secs. 5 & 6.
Var. 1½° E.

40.00 set Temp. ¼ Sec. cor,
80.60 Intersect the N. boundary
of the Tp. 7 links W. of
the cor. to secs. 5.6.31 & 32
which is a Granite 24x
24 x 6 ins. with stone
mound, from which
S.0.3' W. on true line
bet. secs. 5 & 6.
With Same Variation.
17.50 Leave flat top Ridge & des=
cend.
26.50 Granite ledge 60 ft. high.
40.60 set Granite 25 x 9 x 7 ins.
18 ins. in the ground for
¼ sec. cor. Marked ¼ on
W. face and raised a
mound of stone along
side.
49.00 Dole creek 60 lks. wide, runs
SW. Ascend
58.50 Granite ledge 150 ft. high.

Subdivisions T. 25 S. R. 4½ W. S.L.M.

74.50 Granite ledge 50 ft. high and utter plateau

80.60 The cor. to secs. 5, 6, 7 & 8

Land mountainous

Soil 2nd rate

Dense undergrowth to higher.

January 8th 1884

80.60 CHS.

BOOK A 201

General Description

The lands in this township consist chiefly of mountains except in clear creek canon, the soil being first and second rate. There is some cedar and pinon pine timber in the mountainous portion. Dole Creek runs south through the west tier of sections, and clear creek runs east through the south tier of sections.

The Denver & Rio Grande Rail Road Company have a portion of their road bed graded in Secs. 31 & 32.

There are over 100 acres cultivated by five settlers along clear creek, among which

BOOK A

is the applicant for survey
John S. Lotto, whose improvements consist of a log house 16x32 feet, 120 rods of fencing 150 rods of ditching and about 20 acres in his cultivated field, with stable and out house.

These improvements are situated in the N½ of the SE¼ & SE¼ of the NE¼ of section 36.

There are no indications of minerals.

Edward W. Kooke
U.S. Deputy Surveyor

BOOK A-201

A list of the names of the individuals employed by Edward W. Roeber *United States deputy surveyor, to assist in running, measuring, and marking the lines and corners described in the foregoing field notes of the survey of* the Exterior and Subdivisions of Tp. 13 South R. 1 West.

of the Salt Lake base and meridian in the Territory of Utah, showing the respective capacities in which they acted.

....., *Compassman.*
Olof Larson, *Chainman.*
Harry Pitchfork, *Chainman.*
....., *Chainman.*
....., *Chainman.*
Olof Larson, *Axeman.*
Harry Pitchfork, *Axeman.*
....., *Flagman.*

BOOK A-201

[5. FINAL OATHS OF ASSISTANTS.]

We hereby certify that we assisted Edward W. Roeber United States deputy surveyor in surveying all those parts or portions of the exterior and subdivision of Tp. No. 13 S., R. 1 W. Salt Lake

of the Salt Lake base and meridian in the Territory of Utah, as are represented in the foregoing field notes as having been surveyed by him, and under his direction; and that said survey has been in all respects, to the best of our knowledge and belief, well and faithfully surveyed, and the corner monuments established according to the instructions furnished by the United States surveyor-general for Utah.

, Compassman.

C. W. Larsen, Chainman.

Harry Pitchforth, Chainman.

, Chainman.

, Chainman.

, Axeman.

, Axeman.

, Flagman.

Subscribed and sworn to before me this 25 day of January 1884

[illegible]

[illegible]

BOOK-A-201

[6.—FINAL OATH OF UNITED STATES DEPUTY SURVEYOR.]

I, Edward H. Hocker

United States deputy surveyor, do solemnly swear that in pursuance of instructions received from Fred. Solomon

United States surveyor-general for Utah, bearing date of the 4 day of Decbr., 1883, I have well, faithfully, and truly, in my own proper person, and in strict conformity with the instructions furnished by the United States surveyor-general for Utah, the surveying manual and the laws of the United States, surveyed all those parts or portions of Exteriors and Subdivisions Tp. 13 S. R. 1 W.

of Salt Lake base and meredian in the Territory of Utah, as are represented in the foregoing field notes as having been surveyed by me and under my directions; and I do further solemnly swear that all the corners of said survey have been established and perpetuated in strict accordance with the surveying manual, printed instructions, the special written instructions of the United States surveyor-general for Utah, and in the specific man-

ner described in the field notes, and that the foregoing are the **TRUE** *field notes of such survey; and, should any fraud be detected, I will suffer the penalty of perjury, under the provisions of an act of Congress, approved August 8, 1846.*

Edward W. Kocher

United States Deputy Surveyor

Subscribed and sworn to before me this 3 *day of* April *188*4

Edward Michael

Notary Public

BOOK

U. S. SURVEY

Salt Lak

The foreg

Township No.

Executed by

Under

day of

amined. the neces

the said field n

hereby approved.

BOOK A-201

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, April 8 1884

The foregoing field notes of the survey of the

Subdivisions

Township No. 25 S *Range No.* 4½ W.

Executed by Edward H. Roeber

Under his *contract* No. 122 *of the* 4th

day of December 1883, *in the months of*

Nov & January 1883 & 1884, *having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

Fred Salomon

U. S. Surveyor General for Utah.

BOOK-A-201

REPORT: 1884

Filed 188

Examined by .....

Transcribed by E. Michaelis.

Compared by Wilkinson & Michaelis

FIELD NOTES

OF THE re SURVEY OF THE

Subdivisions of fractional.

Township No 13 South

Range No 3 West

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Shadrach M. Richardson.

U. S. Deputy Surveyor,

Under his Contract No. 123.

Dated December 19th 1883.

Survey commenced February 8th 1884

Survey completed " " 1884

[2. PRELIMINARY OATHS OF CHAINMEN.]

We T. H. Gavin, J. A. Montague J. E. Beckstrom and W. M. Loyd.

do solemnly swear that we will well and faithfully execute the duties of chain carriers; that we will level the chain upon even and uneven ground and plumb the tally pins, either by sticking or dropping the same; that we will report the true distance to all notable objects, and the true length of all lines that we assist in measuring, to the best of our skill and ability, and in accordance with instructions given us, in the survey of the townships and section lines in townships 13, 14 and 19 south, range 3 west and townships 35 and 36 south, range 7 west

of the Salt Lake base and meridian in the Territory of Utah.

T. H. Gavin, Chainman.

J. A. Montague, Chainman.

J. E. Beckstrom, Chainman.

W. M. Loyd, Chainman.

Subscribed and sworn to before me this 1st day of February 1884.

Ernst Salomon
Notary Public

BOOK-A-201

[3 – PRELIMINARY OATH OF AXEMEN.]

We, Peter Petersen

and Moroni A. Brown

do solemnly swear that we will well and truly perform the duties of axemen, in the establishment of corners, and other duties, according to instructions given us, and to the best of our skill and ability, in the survey of township and section lines in townships 13, 14 and 15 south, range 3 west and townships 35 and 36 south, range 7 west

of the Salt Lake base and meridian in the Territory of Utah.

[illegible], Axeman.

Moroni A Browne, Axeman.

Subscribed and sworn to before me this 1st day of February 1884.

Ernst Salomon
Notary Public

BOOK-A-201

Township 13 South R. 3 West

6	5	4	3	2	1	
7	8	9	10	11	12	
18	17	16	15	14	13	
19	20	21	22	23	24	
197	198	199	200			
194 30	29	28	27 201	26	25	
				203		
195 31	32	33	34	35 204	36	

West Boundary T 13 S. R 3 W. S. L. M.

Chs. Survey commenced Feb. 7/84.
The instrument used in the survey of this contract is a Burts improved solar transit being examined by the U. S. Surveyor Generals office and found in proper adjustment.
Note.

In accordance with instructions received from the U. S. Surveyor General, accompanying this contract, I complete the west boundary of T 13 S. R 3 W, thus establishing the N W corner of Tp. 14 S. R 3 W.

Having retraced a portion of the west boundary of T 13 S R 3 W I find the corner to sec's. 19. 24, 25 & 30 to be standing therefore from this corner which is a limestone firmly set in the ground and properly marked, after renewing

West Boundary T 13 S

Chs. mound of stone I run south on a true freeway line bet. sec's 25 and 30.

Var. 15°30' E.

Through undergrowth.

23.00 Wash in hollow drains W.

27.00 Enter cedars.

40.00 No trace of old corner. set lime stone 16 X 10 X 6 ins. 11 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.

A cedar 7 ins. diam. bears N 40 lks dist. marked 1/4 S. B.T.

No other tree within limits.

40.50 Hollow drains N.E.

80.00 Set lime stone 15 X 9 X 5 ins. 1[illegible] ins. in ground for cor. to sec[illegible] 25. 30. 31 & 36 marked 5 notches [illegible] N and 1 on S edges and raised a stone mound alongside

A nut pine 7 ins. diam bears S 60° W 12 lks dist. marked T 13 S R 4 W. S 36 B.T.

R 3

Chs No

La

N

N

D

8 0.0

T

mil

So

12.50 Ho

20.00 Ri

32.50 H

40.00 Se

10 in

mark

raise

55.00 Ri

80.00 Se

10 in

Tp's

W

R 3 W. S. L. M.

Chs No other tree within limits.
Land rolling mountains.
Soil 3rd rate.
Scattering timber on 5300 chs.
Dense undergrowth on
80.00 chs.
The first 40.00 chs. of this
mile is a reservoy.

South bet. secs. 31 and 36.
Var. 15° 30' E.

12.50 Hollow drains N.
20.00 Ridge bears E and W.
32.50 Hollow drains N E.
40.00 Set lime stone 15 x 8 x 6 ins.
10 ins. in ground for 1/4 sec. cor.
marked 1/4 on W face and
raised a stone mound alongside.
55.00 Ridge bears N E and S. W.
80.00 Set lime stone 15 x 8 x 6 ins.
10 ins. in ground for cor. to
Tps. 13 and 14 S. Rs. 3 and 4
W marked 6 notches on each

BOOK-A-201

Township 13 South R. 3 West

6	5	4	3	2	1	
7	8	9	10	11	12	
18	17	16	15	14	13	
19	20	21	22	23	24	
197	198	199	200			
194 30	29	28	27 201	26	25	
				203		
195 31	32	33	34	35 204	36	

BOOK-A-201

Resurvey Subd. T 13 S. R 3 W. S L. M.

chs. Note.

To comply with the special instructions received from the U. S. Surveyor Genl. for the survey of the North Bound. of T 14 S. R 3 W I find it necessary to resurvey some of the subdivision lines of T 13 S. R 3 W in order to properly reestablish a point on the south boundary of T 13 S. R 3 W, where after careful search I am unable to find a corner standing.

Therefore from the cor. to secs. 19. 24. 25 and 30 on the west boundary of the Tp. previously reestablished by me I run East on a true resurvey line bet. secs. 19 and 30

Var. 15° 30' E.

33.00 Hollow drains N W.

39.00 Old cor. thrown down,

Resurvey Subdivisions T. 13 S.

Chs. reset same a lime stone 24 X 15 X 10 ins. 16 ins. in ground for ¼ sec. cor. marked ¼ on N face and raised a stone mound alongside.

79.70 The cor. to sec's. 19. 20. 29 & 30 found standing, firmly set in the ground and properly marked, renewed mound of stone.

Land rolling.

Soil 3rd rate.

Dense undergrowth on 79.70 chs.

East on a true resurvey line bet. sec's. 20 & 29

Var. 15° 30' E.

4.00 Ridge bears N E and S W

17.50 Hollow drains N E.

40.00 No trace of old cor. set lime stone 14 X 9 X 4 ins. 10 ins. in ground for ¼ sec. cor.

R 3

Chs. ma
pit
of
80.00 O
rese
16 X
for
ma
on
rai
and
S
O
D
gro

Ea
lin

5.00 Asce

10.50 Top

15.00 Foo

40.00 No

R 3 W. S. L. M.

Chs. marked 4 on N face, dug pitts and raised a mound of earth and stone alongside.

80.00 Old cor. thrown down reset same a lime stone 16 X 14 X 12 ins. 11 ins. in ground for cor. to secs. 20. 21. 28 & 29 marked 4 notches on E and 2 on S edges, dug pitts and raised a mound of earth and stone alongside.

Land rolling.

Soil 3rd rate.

Dense artemesia under growth on 80.00 chs.

East on a true resurvey line bet. secs. 21 and 28.

Var. 15° 30' E.

5.00 Ascend.

10.50 Top of hill bears N and S.

15.00 Foot of hill " " "

40.00 No trace of old cor. set

Subdivisions T 13 S

Chs. sandstone 14 x 12 x 8 ins. 10 ins
in ground for 1/4 sec. cor.
marked 1/4 on N face and raised
a stone mound alongside.
73.00 Leave undergrowth.
80.00 No trace of old cor. set
lime stone 14 x 9 x 4 ins. 10 ins
in ground for cor. to secs.
21. 22. 27 & 28 marked 3 notch
on E and 2 on S edges. dug
pitts and raised a mound
of earth and stone alongside.
Land rolling.
Soil 3rd rate.
Dense undergrowth on
73.00 chs.

East on a true resurvey
line bet. secs. 22 and 27.
Var. 15° 30' E.
3.50 Road bears N.W. and S.E.
40.00 Old cor. thrown down, reset
same a sand stone 16 x 8 x 8
ins. 11 ins. in ground for 1/4

R 3

Cha sec. c
dug
mound
along
70.00 Entering
80.00 No tr
grani
in gr
22. 23
notches
dug
mound
alongs
S
S
D
10.00 c

Sout
line

4.00 Road
10.00 Ascen
11.50 Ridge

R 3 W. S. L. M.

Chs. sec. cor. marked 1/4 on N face dug pits and raised a mound of earth and stone alongside

70.00 Entry undergrowth

80.00 No trace of old cor. set a granite 14 x 10 x 10 ins. 10 ins. in ground for cor. to secs. 22, 23, 26 & 27. marked 2 notches on E and 2 on Sdges dug pits and raised a mound of earth and stone alongside.

Land rolling.

Soil 3 rate.

Dense undergrowth on 10.00 chs.

South on a true resurvey line bet. 26 and 27

Var. 15° 30' E.

14.00 Road bears N E and S W.

20.00 Ascend.

21.50 Ridge bears N E and S W.

Resurvey Subdivisions T 13 S

Chs.	
38.00	Hollow drains N.E.
40.00	No trace of old cor. set line stone 16X10X5 ins 11 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside
45.60	Ridge bears N E and S W.
57.00	Hollow drains N.E.
65.00	Ascent bears N E and S W.
80.00	No trace of old cor. set line stone 14X10X5 ins. 10 ins in ground for cor. to secs. 26, 27, 34 and 35 marked 2 notches on E and 1 on S edges and raised a stone mound alongside.

Land mountainous.

Soil 3rd rate.

Mountainous on 60.00 chs.

Dense undergrowth on 80.00 chs.

R 3

Chs.	
	Ea line
	Desc
20.00	Foot
40.00	No stone grou 1/4 on stone
80.00	No line ins. secs. 1 not and alon

La

Sa

M

De

R 3 W. S. L. M.

Chs. East on a true resurvey line bet. sec's. 26 and 35.
Var. 15° 30' E.
Descend.
20.00 Foot of mountain. bears N.W. & S.E.
40.00 No trace of old cor. set lime stone 15 X 10 X 8 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.
80.00 No trace of old cor. set. lime stone 16 X 12 X 10 ins 11 ins. in ground for cor. to sec's. 25. 26. 35 and 36 marked 1 notches on E and S edges and raised a stone mound alongside.
Land rolling and mountainous.
Soil 3rd rate.
Mountainous on 20.00 chs.
Dense undergrowth on 80.00 chs.

Resurvey Subd. T 13 S

chs. South on a true resurvey line bet. sec's. 35 and 36.
Var. 15° 30' E.

1.00 Leave undergrowth.

39.00 Enter "

40.00 No trace of old cor. set lime stone 14 X 10 X 6 ins. 10 ins. in ground for ¼ sec. cor. marked ¼ on W face and raised a stone mound alongside.

64.50 Road bears NE and SW.

80.00 No trace of old cor. set lime stone 15 X 9 X 4 ins. 10 ins in ground for cor. to sec's. 1. 2. 35 and 36 marked 1 notch on E and 5 on W edges and raised a stone mound alongside.

Land rolling.
Soil 3 rd rate.
Dense undergrowth on 42.00 chs.

Feb. 8, 1884.

R 3 W. S. L. M.

General Description.

This line runs mostly along the foot of mountains, over land partly good for agricultural purposes.

It affords good grazing.

U. S. Dep. Surveyor.

BOOK-A-201

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, June 28th 1884

The foregoing field notes of the survey resurvey *of the* fractional West Boundary

Township No. 13 S *Range No.* 3 W

Executed by Shadrach M. Richardson

Under his *contract* no 123 *of the* 19th *day of* December 1883, *in the month of* Feb. 1884, *having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

Frd Salomon

U. S. Surveyor General for Utah.

BOOK-A-201

3

REPORT: 1884

Filed 188

Examined by J. H. C.

Transcribed by E. Michaelis

Compared by A. Rinsow & Michaelis

FIELD NOTES

OF THE SURVEY OF THE

West, North, South and East Boundaries

OF

Township No 14 South

Range No 3 West.

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Shadrach M. Richardson.

U. S. Deputy Surveyor,

Under his Contract No. 123

Dated December 19 th 1883.

Survey commenced February 9 th 1884.

Survey completed " 11 th 1884

BOOK-A-201

West Boundary T 14 S. R 3 W.

chs Survey commenced Feb 9/84.

From the cor. to Tps. 13 and 14 S. Rs 3 and 4 W previously set by me I run south on a random line because the S W. cor. of the Tp. is set, setting temp. half mile and mile corners at each 40.00 and 80.00 chs.

I find the distance to be 5 miles 69.08 chs. and the falling to be 13.20 chs. E of the cor. to Tps. 14 and 15 S. Rs. 3 and 4 W.

The falling being greater than is allowed by the instructions I run north on a true line from the cor. to ~~Tps~~. 14 and 15 S. Rs. 3 and 4 W. bet secs. 31 and 36.

N. Var. 16° 30' E.

this corner is a granite friendy set in the ground and properly marked.

West Boundary T 14 S.

Chs.	
15.00	Ascend
40.00	On ridge bears N W and S. set flint stone 16x10x9 ins. 11 ins. in ground for 1/4 sec. co marked 1/4 on N face and raised stone mound alongside.
50.00	Foot of ridge.
71.00	Wash drains S.E.
80.00	Set sand stone 19x10x4 ins. 13 ins. in ground for cor to secs. 25. 30. 31 and 36 marked 5 notches on N and 1 on S edges and raised a stone mound alongside.

Land rolling mountains.
Soil 4th rate
Dense artemisia undergrowth on 80.00 chs.

North on a true line bet secs 25 and 30.

Var. 16° 30' E.

Through dense undergrowth.

R 3

Chs.	
15.00	Des
39.00	En
40.00	Se
	12
	cor
	wh
	bea
	dra
	1/4 S.
61.00	Ri
70.00	Hi
78.50	R
80.00	Se
	14
	sec
	4
	edge
	mou
	A
	N 83
	R 3
	N
	to

R 3 W. S. L. M.

Chs.
15.00 Descent bears N W and S.E.
39.00 Enter cedars leave undergrowth.
40.00 Set line stone 18X12X10 ins.
12 ins. in ground for 1/4 sec.
cor. marked 1/4 on W face from
which A cedar 12 ins. diam.
bears E 10 lks dist.
A cedar 9 lks dist 8 ins.
diam. bears W. each marked
1/4 S. B. T.
61.00 Ridge bears S.E.
70.00 Head of canon drains S.E.
78.50 Ridge bears S E and N W.
80.00 Set line stone 20X12X10 ins.
14 ins. in ground for cor. to
sec's. 19. 24. 25 and 30 marked
4 notches on N and 2 on S
edges and raised a stone
mound alongside.
A nut pine 10 ins. diam. bears
N 85° E 10 lks dist. marked T14S
R 3 W S. 19. B.T.
No other tree large enough
to mark

West Boundary T 14 S

Chs. Land mountainous
Soil 4th rate.
Dense undergrowth on 39.00 chs.
Heavily timbered on 41.00 chs.

North bet. secs. 19 and 24.
Var. 16° 30' E.

37.00 Ridge bears S E.

4.00 Set lime stone 15 x 10 x 7 ins. 10 ins. in ground for ¼ sec. cor. marked ¼ on W face from which
A pine 9 ins. diam. bears S 30° E 10 lks dist.
A pine 8 ins. diam. bears N 10° W 32 lks dist each marked ¼ S. B. T.

60.00 Leave cedars.

78.00 Canon drains S W.

8.00 Set lime stone 19 x 12 x 8 ins. 13 ins. in ground for cor. to secs. 13. 18. 19 and 24 marked 3 notches on N and S edges and raised a stone mound alongside.

BOOK-A-201

R 3 W. S. L. M.

cho Land mountainous.
Soil 4th rate.
Heavily timbered on 60.00 chs.
High Mountains on 8.00 chs. —

North bet. secs. 13 and 18
Var. 16° 30' E.
27.00 Ridge bears E and W. mtn
undergrowth.
34.00 Ravine drains W.
40.00 Set line stone 14 X 12 X 6 ins.
10 ins. in ground for 1/4 sec. cor
marked 4 on W face and raised a
stone mound alongside.
57.00 Ridge bears W and N.E.
80.00 Set line stone 14 X 12 X 5 ins. 10
ins. in ground for cor. to secs.
7. 12. 13 X 18 marked 2 notches on N
and 4 on S edges and raised a
stone mound alongside.
Land mountainous.
Soil 4th rate.
Dense undergrowth on 33.00 chs
High Mountains on 8.00 chs. —

West Boundary. T. 14 S.

Chs. North bet. sec's. 7 and 12
Var. 16° 30' E.
Through dense undergrowth.
23.50 Ravine drains N.
30.00 Ridge bears E and W.
35.00 Trail in ravine bears N E & S.
40.00 Set lime stone 13X10X10 ins. 10 ins. in ground for 1/4 sec. cor. mark 1/4 on N face and raised a stone mound alongside.
80.00 Set lime stone 17X10X7 ins. 12 ins. in ground for cor. to sec's. 1. 6. 7 and 12 marked 1 notch on N and 5 on S edge and raised a stone mound alongside.

A nut pine 9 ins. diam. bears S 80° E 7 lks dist. marked T14 S. R 3 W S. 7 B.T.

No other tree within limits.

Land mountainous.

Soil 4 th rate.

Dense undergrowth on 80.00 chs.

R 3 W.

Chs. No

3.50 Ridge
10.00 Head
19.00 Rid
30.00 Rav
37.00 Rid
40.00 Set
in g
1/4 on
mou
45.00 Ravi
69.08 Inter
Tp. 1
Tp. 1
at p
line
in g
to T
mark
edge
stone
La
Sa
Dec

R 3 W. S. L. M.

Chs	North bet. secs. 1 and 6 Var. 16° 30' E.
3.00	Ridge bears E and W.
10.00	Head of canon drains N.E.
19.00	Ridge bears N E and S W.
30.00	Ravine Drains N.E.
37.00	Ridge bears N E & S W.
40.00	Set lime stone 15 X 10 X 5 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.
45.00	Ravine drains N.E.
69.08	Intersect north boundary of Tp. 13. 20 chs. west of cor. to Tps. 13 and 14 S. R's. 3 and 4 W. at point of intersection set lime stone 16 X 10 X 7 ins. 11 ins. in ground for closing cor. to Tps. 13 and 14 S. R's. 3 & 4 W marked 6 notches on E. S & W edges and C.C. and raised a stone mound alongside.

Land mountainous.
Soil 4 th rate
Dense undergrowth on 69.08 chs.

North Boundary T 14 S

Chs. From the cor. to Tps. 13 & 14 S. R's 3 and 4 W. previously established by me I run east on a random line to the cor. of sec's. 1. 2. 35 & 36 resestablished by me

Var. 16° 30' E.

I set temp. half mile and mile corners at each 4000 and 8000 chs, and find the distance to be 4 miles 79.03 chs, the following 90 lks North of cor. to sec's. 1. 2. 35 & 36, the correction for the true line will therefore 18 lks South & 97 lks West per mile and its course will be North 89° 0' 12" West.

From the cor. to sec's. 1. 2. 35 and 36, I run N 89° 32' W on a true line on the S side of sec 35

Var. 16° 30' E.

40.00 Set flint stone 18 x 14 x 4 ins. 12 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound along side

69.00 Ridge bears S E.

R 3

Chs.
71.50 Rovn
80.00 Set
10 ins.
sec's. 3
mart
on W
mown
L
D
D
80.00 c

N 89
bet.

10.00 Ridg
27.50 Rov
40.00 Set
ins.
marke
a sto
50.00 Ridg
55.50 Rav

BOOK-A-201

R 3 W. S. L. M.

chs.
71.50 Ravine drains S E.
80.00 Set lime stone 15 X 9 X 4 ins. 10 ins. in ground for cor. to sec's. 34 and 35, 2 and 3 marked 2 notches on E and 4 on W edges and raised a stone mound alongside.

Land rolling mountains
Soil 3rd rate.
Dense undergrowth on 80.00 chs.

N 89° 52' W on a true line bet. sec's. 3 and 34.
Var. 16° 30' E.

10.00 Ridge bears S.E.
27.00 Ravine drains S.E.
40.00 Set limestone 16 X 9 X 5 ins. 11 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.
50.00 Ridge bears S.E.
55.50 Ravine drains S E.

North Boundary T 14 S

Chs
70.00 Ridge bears S.E.
80.00 Set line stone 17 X 10 X 4 ins. 11 ins. in ground for cor. to secs. 3. 4. 33 and 34 marked 3 notches on E and W edges and raised a stone mound alongside
Land mountainous.
Soil 4th rate.
Mountainous and dense undergrowth on 80.00 chs.

N 89° 52' W on a true line bet. secs. 4 and 33.
Var. 16° 30' E.

10.20 Ravine drains S.E.
23.00 Ridge bears S W.
32.00 Ravine drains S W.
40.00 Set line stone 15 X 10 X 4 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.
50.00 Ridge bears S W.

R 3

Chs.
80.00 Set
ins.
secs.
notc
edges
mou
L
S
N
un

N
line

17.00 Desc
40.00 Set
10 ins
cor.
rais
alon
60.00 Hol
71.50 Rid
80.00 Set

R 3 W. S. L. M.

Chs.
80.00 Set lime stone 15 x 8 x 6 ins. 10 ins. in ground for cor. to secs. 4. 5. 32 x 33 marked 4 notches on E and 2 on W edges and raised a stone mound alongside.

Land mountainous.

Soil 4th rate.

Mountainous and dense undergrowth on 80.00 chs.

N 89° 52' W on a true line bet. secs. 5 and 32.

Var. 16° 30' E.

17.00 Descent bears S.W.

40.00 Set sandstone 14 x 8 x 4 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

46.00 Hollow drains N W.

71.50 Ridge bears S. E.

80.00 Set lime stone 14 x 10 x 5 ins.

North Boundary T 14 S

chs 10 ins. in ground for cor. to secs. 5, 6, 31 and 32 marked 5 notches on E and 1 on W edges and raised a stone mound alongside.

Land rolling and broken.
Soil 3rd rate.
Dense undergrowth on 80.00 chs.

N 89°52' W on a true line bet. secs. 6 and 31
Var. 16°30' E.

6.00 hollow drains N.
40.00 Set line stone 14 x 8 x 5 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.
45.00 Ridge bears N and S.
56.00 Hollow drains N
68.00 Ridge ~~bears~~ bears N and S.
79.00 Ravine drains N. E.

BOOK-A-201

R 3

chs.
79.03 The co
Rs. 3
La
S
De
79.03

From
35 an
bound
east
line

26.50 Trail
40.00 No tr
line
in gr
mark
raised
along
68.50 Wash
71.00 Road

R 3 W. S. L. M.

chs.
79.03 The cor. to Tps. 13 and 14 S.
Rs. 3 and 4 W.
Land rolling and broken
Soil 3rd rate.
Dense undergrowth on
79.03 chs.
February 9/84.

From the cor. to secs 1. 2.
35 and 36 on the north
boundary of the Tp. I run
east on a true resurvey
line bet. secs 1 and 36.
Var. 16° 30' E.

26.50 Trail bears N W and S E.
40.00 No trace of old cor. set a
lime stone 18 X 9 X 9 ins. 13 ins.
in ground for 1/4 sec. cor.
marked 1/4 on N face and
raised a stone mound
alongside.
68.50 Wash drains S E.
71.00 Road bears N W and S E.

North Boundary T14S. R. 3 W.

Chs.
8000 No trace of old cor. set a sandstone 16x10x10 ins. 11 ins. in ground for cor. to Tps 13 and 14 S. Rs. 2 and 3 W marked 6 notches on each edge and raised a stone mound alongside.

Land rolling.

Soil 2nd rate.

Dense artemesia under growth on 8000 chs.

BOOK-A-20

South B

Chs.	
	T
	and
	is a
	grou
	I ru
	bet
	Thr
.75	Roo
23.50	Wa
36.00	Ro
39.40	All
	meri
	14 x 14
	for
	N fo
	mo
51.00	Uta
56.35	Ser
63.50	"
68.25	"
69.50	Ca
69.60	Asc
73.50	Ric

3 W.
set a
s. 11 ins.
Tps
3 W
ach
tone
ncler

South Boundary T 14 S. R 3 W.

Chs. From the cor. to Tp. 14 and 15 S. Rs. 3 and 4 W which is a granite firmly set in the ground and properly marked I run east on a true line bet. sec's. 6 and 31

Var. 16°30' E.

Through dense undergrowth.

.75 Road bears N E.

23.50 Wash drains S.

36.00 Road bears N E.

39.40 Allowing for convergancy of meridians Set lime stone 14 X 10 X 6 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

51.00 Utah Central R. R. bears N E.

56.35 Sevier river 75 lks wide flows S

63.50 " " " " " N

68.25 " " " " " S

69.50 Canal drains S. W.

69.60 Ascent bears N E.

73.50 Ridge bears N E & S W

South Boundary T 14 S

Chs.
79.40 Set granite 34 X 10 X 8 ins. 24 ins. in ground for cor. to sec's. 5. 6. 31 and 32 marked 5 notches on E and 1 on W edge and raised a stone mound alongside.

Land rolling.

Soil 2nd & 3rd. rate.

Dense undergrowth on 79.40 ch

East on a true line bet. sec's. 5 and 32

Var. 16° 30' E.

1.25 Ravine drains N.
29.50 Ridge bears N and S.
35.00 Ravine drains N.
37.00 Small ridge bears N & S.
38.50 Ravine drains N.
40.00 Set flint stone 19 X 10 X 6 ins. 13 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside
60.00 Ridge bears N and S.
79.50 Canon drains N.

R 3 W

Chs.
0.00 Set
12 ins.
sec's.
notc
edgel
moun
La
S
S
line.
De
80.00

Eas
sec's.

32.00 Ridg
40.00 Set
11 ins.
mark
raise
alon
44.00 Rav

R 3 W. S. L. M.

Chs.
80.00 Set line stone 18x14x5 ins. 12 ins. in ground for cor. to sec's. 4. 5. 32 & 33 marked 4 notches on E and 2 on W edges and raised a stone mound alongside.

Land mountainous.

Soil 4th rate.

Scattering cedars along line.

Dense undergrowth on 80.00 chs.

East on a true line bet. sec's. 4 and 33.

Var. 16° 30' E.

32.00 Ridge bears N and S.

40.00 Set line stone 16x12x7 ins. 11 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

44.00 Ravine drains N.

South Boundary T14 S

chs.	
50.00	Ridge bears N and S.
55.00	Ravine drains N W.
57.00	Ridge bears N and S.
62.25	Ravine drains N.
80.00	Set granite stone 14x10x7 ins. 10 ins. in ground for cor. to sec's. 3. 4. 33 and 34 marked 3 notches on E and W edges and raised a stone mound alongside.

Land mountainous.

Soil rocky 3rd and 4th rate.

Scattering timber along line.

Dense artemesia undergrowth on 80.00 chs.

Mountainous on 80.00 chs.

East on a true line bet sec's. 3 and 34.

Var. 16°30' E.

R 3 W. S.L.M.

Chains

1.50 Ridge bears N. W.

4.00 indications of minerals. prospect 2 chs S. of line

10.00 Mine monument of the "Juneau" located by H. M. Wheeler and G. C. Elmer 750 ft N and 750 ft S. of line.

19.50 Ravine drains N. W.

26.00 Ridge bears N x S

27.00 Enter scrub cedars

40.00 Set iron stone 34" x 10" x 8", 22 ins in the ground, for 1/4 sec. cor, marked 1/4 on N. face and raised a mound of stone along side

56.00 ravine drains S. 70° E.

57.00 Leave cedars

80.00 Set granite stone 14" x 12" x 6", 9 ins in ground for cor: to secs: 2, 3, 34 & 35, marked with 2 notches on the E and 4 notches

South Boundary T. 14 S.

chains on W edges and raised a mound of stone alongside.

Land mountainous
Soil rocky; 4th rate
Scrub cedars on 30.00 chs
High Mountains and dense undergrowth on 80.00 chs

East betw. Secs 2 and 35
Var 16° 30' E.

35.00 Cesgeux bears N & S.
40.00 Set granite 14"x10"x6", 10 ins in ground for 1/4 Sec. Cor. marked 1/4 on N face and raised a mound of stone alongside
60.00 Dense undergrowth enter white sage
80.00 Set sandstone 15"x12"x6" 10 ins in ground for Cor. to Secs 1, 2, 35 & 36 marked with 1 notch on E and 5 notches on W edges and raised a stonemound alongside
Land rolling
Soil 3rd rate
White sage brush on 20.00 chains
Dense undergrowth on 60.00 chains

BOOK-A-201

R 3 W.

chs.	East
	W
.50	Road
2.00	Trail
27.00	Ridge
40.00	Set g in gro mon a stone
50.50	U. S.
52.60	Seve flows
57.00	Leave
60.00	Road
66.50	"
80.00	Set g ground S. R. notches a stone
	Lo
	So
	Der

BOOK-A-201

R 3 W. S. L. M.

ch. East bet. sec's. 1 and 36.
Var. 16° 30' E.

.50 Road bears N. W.

2.00 Trail in hollow, drains N.

27.00 Ridge bears N and S.

40.00 Set granite 14 x 10 x 6 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

50.50 U. C. R. R bears N W.

52.60 Sevier Riv. 1.00 ch. wide flows N. W.

57.00 Leave white sage, enter undergrowth.

60.00 Road bears N. W.

66.50 " " N. E.

80.00 Set granite 16 x 12 x 10 ins. 11 ins in ground for cor. to Tps 14 and 15 S. Rs. 2 and 3 W. marked 6 notches on each edge and raised a stone mound alongside.

Land rolling
Soil 2nd & 3rd rate.
Dense undergrowth on 23.00 chs.

February 10, 1884.

East Boundary T 14 S

chs. Note.

Knowing from the closing of the west boundary that the east boundary will fall outside the limit for correction I therefore run it north on a true line from the corner to Tps. 14 and 15 S. R's. 2 and 3 W just established by me but sees 31 & 36

Var. 16° 30' E.

27.00 Road in hollow bears S. W.

40.00 Set granite 16X14X7 ins. 11 ins. in ground for 1/4 sec. cor. mon. 1/4 on W face and raised a stone mound alongside.

41.50 Ridge bears S. W.

63.50 Hollow drains S W

80.00 On ridge bears S W set sand stone 16X10X8 ins. 11 ins. in ground for cor. to sec's. 25. 30. 31 & 36 marked 5 notches on N and 10 S edges and raised a stone mound alongside.

R 3 W

chs. Lar
Dar
Dense

North

20.00 Ravin
33.00 Ridg
40.00 Set f
in gr
1/4 on
mou
43.50 Rav
57.00 Ridg
75.00 Ravn
80.00 Set
in gr
24.25
N and
a ston
A
S 25°
S. R 3

R 3 W. S. L. M.

chs. Land mountainous.
Soil 3 rd rate.
Dense undergrowth on 80.00 chs.

North bet. secs. 25 and 30.
Var. 16° 30' E.

20.00 Ravine drains S W.
33.00 Ridge bears S W.
40.00 Set flint stone 15 X 9 X 7 ins. 10 ins in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.
43.50 Ravine drains S W.
57.00 Ridge bears S W.
73.00 Ravine drains S W.
80.00 Set granite 18 X 14 X 12 ins. 12 ins. in ground for cor. to secs. 19 24. 25 & 30 marked 4 notches on N and 2 on S edges and raised a stone mound alongside.

A cedar 14 ins diam bears S 25° W 15 lks dist. marked T 14 S. R 3 W. S 25. B. T.

East Boundary T14 S

Chs. No other tree within limits.
Land mountainous.
Soil 4th rate.
Mountainous and dense
undergrowth on 80.00 chs.

North bet. secs. 19 and 24.
Var. 16° 30' E.

20.00 Ridge bears S W.
31.00 Trail in hollow, drains S W.
40.00 Set granite 14 x 10 x 7 ins. 10 ins.
in ground for 1/4 sec. cor. mark
1/4 on W face and raised a stone
mound alongside.
51.50 Ridge bears E and W.
69.00 Ravine drains W.
77.00 " " S. W.
80.00 Set granite 20 x 15 x 6 ins. 13 ins.
ground for cor. to secs. 13. 18. 19 x 24
marked 3 notches on N and S
edges and raised a stone mound alongside
Land mountainous,
Soil 3rd rate.
Mountainous & dense undergrowth
on 80.00 chs.

R 3 W

Chs. North

14.00 Ravine
23.00 Ridge
35.00 Ravine
40.00 Set
in gr
1/4 on
stone
43.50 Ridge
48.00 Ravine
55.50 Ridge
64.50 Ravine
80.00 Set
10 ins.
secs.
notch
edges
alone
L
Sa
De
mou

R 3 W. S. L. M.

Chs. North bet. secs. 13 and 18
Var. 16°30' E.

14.00 Ravine drains W.
23.00 Ridge bears W
35.00 Ravine drains W.
40.00 Set sand stone 16 X 10 X 6 ins. 11 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.
43.50 Ridge bears E & W.
48.00 Ravine drains W.
53.50 Ridge bears N W.
64.50 Ravine drains W.
80.00 Set lime stone 15 X 11 X 6 ins. 10 ins. in ground for cor. to secs. 7. 12. 13 & 18 marked 2 notches on N and 4 on S edges and raised a stone mound alongside.

Land mountainous.
Soil 4th rate.
Dense undergrowth and mountainous on 8000 chs.

East Boundary T 14 S

Chs. North bet. sec's. 7 and 12
Var. 16° 30' E.

3.50 Ridge bears E & W.

35.00 Foot of mountain bears N E &

40.00 Set line stone 14 X 12 X 6 ins. 10 ins. in ground for 1/4 sec. c marked 1/4 on W face and raised a stone mound alongside.

41.50 Wash drains W.

51.25 Wash " S W.

58.60 Road bears S W.

70.00 Ascent, bears S. W.

80.00 Set line stone 14 X 10 X 10 ins. 10 in ground for cor to sec's. 1. 6. 7 & 12 marked 1 notch on N and 5 on S edges and raised a stone mound alongside.

Land level and mountainous.

Soil 2nd & 4th rate.

Mountainous on 37.00 chs.

Dense undergrowth on 80.00 chs.

BOOK-A-207

R 3

Chs. North

40.00 Set
11 ins.
mark
raised
along

55.00 Desce

67.80 Inter
towns
corne
R's. 2
intersec
24 X 12
for c
13 and
mar
edges
stone
Lan
S
De
67.80

BOOK-A-201

R 3 W. S. L. M.

Chs. North bet secs. 1 and 6.
Var. 16° 30' E.

40.00 Set lime stone 16 X 9 X 7 ins., 11 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.

55.00 Descend bears S W.

67.80 Intersect N boundary of township 14. 45 west of the corner to Tps. 13 and 14 S. Rs. 2 and 3 W. At point of intersection set granite 24 X 12 X 10 ins. 16 ins. in ground for closing corner to Tps. 13 and 14 S. Rs. 2 and 3 W. marked 6 notches on E. & W edges and 6 6. and raised a stone mound alongside.

Land rolling.
Soil 3rd rate.
Dense undergrowth on 67.80 chs.

February 11. 1884

Note,

For general description see subdivision notes of this township.

U. S. Dep. Surveyor.

BOOK

U. S. SURVE

Salt Lak

The foreg

W. N.

Township No.

Executed by

Under hi

day of Dec

February

amined, the nec

the said field

hereby approve

BOOK-A-201

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, June 28th 1884

The foregoing field notes of the survey of the

N. N. S & E Boundaries

Township No. 14 S *Range No.* 3 W

Executed by Shadrach M. Richardson.

Under his *contract* No 123 *of the* 19th

day of December 1883, *in the month of*

February 1884, *having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

Fred Salomon

U. S. Surveyor General for Utah.

BOOK-A-201

REPORT: 1884

Filed 188

Examined by J. H. G.

Transcribed by E. Michaelis

Compared by Atkinson & Michaelis

FIELD NOTES

OF THE SURVEY OF THE

Subdivisions

OF

Township No 14 South

Range No 3 West

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Shadrach M. Richardson

U. S. Deputy Surveyor,

Under his Contract No. 123.

Dated December 19th 1883.

Survey commenced February 12th 1884.

Survey completed " 17th 1884.

V

BOOK-A-201

Township 14 South R. 3 West

217	216	215	214	213	218
212 6 294	5 277	4 266	3 255	2 244	1 232
293	292	276	265	254	243
211 7 291	8 275	9 264	10 253	11 242	12 233
290	289	274	263	252	241
210 18 288	17 273	16 262	15 251	14 240	13 234
287	286	272	261	250	239
209 19 285	20 271	21 260	22 249	23 238	24 229
284	283	270	259	248	237
208 30 282	29 269	28 258	27 247	26 236	25 228
280	279	268	257	246	235
206 31 278	32 267	33 256	34 245	35 234	36 227
220	221	222	223	225	226

BOOK-A-201

Subdivisions T 14 S. R 3 W. S.L.M.

Chs. Survey commenced Feb. 12/84
From the cor. to sec's.
35 and 36 on the S boundary
of the Tp. previously set by
me I run North on a true
line bet. sec's. 35 and 36.
Var. 16°30' E.

20.00 Ridge bears E and W.

35.00 Enter river bottom.

40.00 Set sandstone 18 X 10 X 7 ins.
12 ins. in ground for 1/4 sec.
cor. marked 1/4 on W face and
raised a stone mound alongside.

45.00 Sevier river 100 lks wide
flows N. W.

80.00 Set a granite 16 X 10 X 6 ins.
11 ins. in ground for cor. to
sec's. 25. 26. 35 and 36 marked
1 notches on E and 1 on S edges
and raised a stone mound
alongside.

Land nearly level
Soil 2nd rate.
Dense undergrowth on 80.00 chs.

Subdivisions T 14 S.

Chs. East on a random line bet. sec's. 25 and 36.

Var. 16° 30' E.

~~40.00 Set [illegible] 1/4 sec. cor.~~

77.40 Intersect E Bound. of Tp. at cor. to sec's. 25 and 36, from which I run W on a true line bet. sec's. 25 and 36, with same Var.

39.95. In hollow drains S. set. gronil 14X12X7 ins. 10 ins in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

67.50 Road bears N W and S E.

72.00 Slough " " " "

74.40 Utah Central R. R. bears. N W & S E

79.90 The cor. to sec's. 25. 26. 35 & 36.

Land rolling.

Soil 2 nd rate.

Dense artemesia undergrow

on 79.90 chs.

R 3

Chs. North

8.00 Road

18.00 "

36.00 "

39.00 Road

40.00 Set g ground 1/4 on N mound

40.25 U. C.

80.00 Set 10 in sec's. 1 not edges mou La S D grou

BOOK-A-201

R 3 W. S. L. M.

Chs. North bet secs. 25 and 26.
Var. 16°30' E.

8.00 Bend of river.

18.00 " " "

36.00 " " "

39.00 Road bears N W and S E

40.00 Set granite 14 X 4 X 6 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.

40.25 U. C. R. R. bears N W and S E.

80.00 Set flint stone 15 X 7 X 6 ins. 10 ins. in ground for cor. to secs. 23. 24. 25 X 26 marked 1 notch on E and 2 on S edges and raised a stone mound alongside.

Land level

Soil 2nd rate

Dense artemesia undergrowth on 80.00 chs.

Subdivisions T 14 S

Chs. East on a random line bet
secs. 24 and 25
Var. 16° 30' E.

40.00 Set temp. 1/4 sec. cor.

79.85 Intersect E. Bound of Tp.
10 lks N of cor. to secs. 24 &
25 from which I run N 89° 56'
on a true line bet. secs. 24 & 25
with same Var.

20.00 Ridge bears N E and S W.

26.00 Rovind drains S W.

37.00 Ridge bears N E and S W.

39.92 Set granite 14 x 10 x 9 ins. 10 ins.
in ground for 1/4 sec. cor. mark
1/4 on N face and raised a
stone mound alongside.

33.50 Hollow drains S.

79.85 The cor. to secs. 23. 24. 25 & 26

Land rolling mountains.
Soil 3rd rate.
Dense artemesia undergrow
on 79.85 chs

R 3 W. S. L. M.

Chs. North bet. sec's. 23 and 24
Var. 16° 30' E.

30.00 Wash drains S.E.

40.00 Set flint stone 14x10x6 ins 10 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.

50.00 Ridge bears N.E. & S.W.

74.50 Wash drains W.

80.00 Set lime stone 14x10x7 ins. 10 ins. in ground for cor. to sec's. 13. 14. 23 and 24 marked 1 notch on E and 3 on S edges and raised a stone mound alongside.

Land rolling.

Soil 2nd and 3rd rate.

Dense undergrowth on 80.00 chs.

Subdivisions T14 S

Chs. East on a random line bet. sec's. 13 and 24
Var. 16° 30' E.

40.00 Set temp. 1/4 sec. cor.

79.85 Intersect E bound. of Tp. at cor. to sec's. 13 and 24 from which I run west on a true line bet. sec's. 13 and 24 with same Var.

22.50 Ravine drains N W.

37.50 Ridge bears N. W. & S. E.

39.92 Set granite 13 x 9 x 5 ins. 9 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

60.00 Wash drains S W.

76.00 Trail bears N & S.

79.85 The cor. to sec's. 13. 14. 23 & 24.

Land rolling.
Soil 3rd rate.
Dense undergrowth on
79.85 chs.

BOOK-A-201

R 3 W. S. L. M.

Chs. North bet. sec's. 13 & 14.
Var. 16° 30' E.

11.00 Wash drains S W.

20.00 Road bears N E & S W.

34.00 Ridge bears E and W.

40.00 Set flint stone 18 X 12 X 9 ins. 12 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.

60.00 Ridge bears E and W.

76.00 Hollow drains N E.

80.00 Set lime stone 17 X 10 X 8 ins. 12 ins. in ground for cor. to sec's. 11 12. 13 & 14 marked 1 notch on E and 4 on S edges and raised a stone mound alongside.

Land rolling.

Soil 2 nd rate.

Dense undergrowth on 80.00 chs.

Subdivisions T 14 S

Chs. East on a random line bet. secs. 12 and 13.

Var. 16° 30' E.

40.00 Set temp. 1/4 sec. cor.

80.15 Intersect E Bound. of Tp. 23 lks W of cor. to secs. 12 & 13 from which I run N 89° 50' W on a true line bet secs. 12 & 13 with same Var.

29.00 Foot of mountain bears N E & S W

34.00 Wash drains S W.

38.50 Road bears N E. & S W.

40.07 Set granite 19 X 12 X 7 ins. 13 ins in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside

45.00 Ascend.

52.00 Ridge bears N W & S.E.

62.00 Hollow drains S.E.

70.00 Ridge bears N W and S.E.

77.00 Hollow drains S.W.

80.15 The cor. to secs. 11. 12. 13. & 14.

Land mountainous.

Soil 2 nd & 4 th rate

Dense undergrowth on 80.15 chs.

R 3

Chs. Nor

3.50 Hol

10.00 Rid

15.00 Ho

39.00 Ri

40.00 Set

in g

mor

a st

55.00 Ho

75.00 Ri

80.00 Set

in g

1. 2.

on

rais

alo

L

S

N

und

R 3 W. S. L. M.

Chs.	North bet. secs. 11 and 12 Var. 16°30' E.
3.50	Hollow drains S.E.
10.00	Ridge bears S.E. & N.W.
15.00	Hollow drains S.E.
39.00	Ridge bears S.E.
40.00	Set granite 16 X 14 X 9 ins. 11 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.
55.00	Hollow drains E.
75.00	Ridge bears E and W.
80.00	Set. granite 15 X 11 X 8 ins. 10 ins. in ground for cor. to secs. 1. 2. 11 and 12 marked 1 notch on E and 5 on S edges and raised a stone mound alongside.

Land mountainous.

Soil 3rd rate.

Mountainous and dense undergrowth on 80.00 chs.

Subdivisions T 14 S

Chs. East on a random line bet. sec's. 1 and 12
Var. 16° 30' E.

40.00 Set temp. ¼ sec. cor.

80.00 Intersect E boundary of Tp. 16 lks N of cor. to sec's. 1 and 12 from which I run N 89° 53' on a true line bet sec's. 1 and 12 with same Var.

40.00 Set gray granite 18 X 12 X 7 in 12 ins. in ground for ¼ sec. cor. marked ¼ on N face and raised a stone mound alongside

80.00 The cor. to sec's. 1. 2. 11 and 12.

Land rolling.
Soil 2nd and 4th rate
Dense undergrowth on 80.00 chs.

BOOK-A-201

R 3 W. S. L. M.

Chs. North on a true line bet. secs. 1 and 2.

Var. 16° 30' E.

7.50 Hollow drains E.

40.00 Set sand stone 15 x 8 x 5 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.

68.00 Intersect N boundary of Tp. 14.25 chs. west of the cor. to secs. 1. 2. 35. & 36. at point of intersection set sand stone 14 x 10 x 8 ins 10 ins in ground for closing cor. to secs. 1 and 2 marked C.C. with 1 notch on E and 5 on W edges and raised a stone mound alongside.

Land rolling.

Soil 3rd rate.

Dense undergrowth on 68.00 chs.

February 13. 1884

Subdivisions T 14 S

Chs.	From the cor. to sec's. 34 & 35 on the S Bound. of the Tp. I run north bet. sec's. 34 & 35
	Var. 16° 30' E.
15.00	Ridge bears N.W. & S.E.
25.00	Ravine drains S.E.
37.00	Ridge bears N.W. & S.E.
40.00	Set granite 17 X 12 X 6 ins. 13 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside
50.00	Ravine drains S.E.
80.00	Set flint stone 14 X 11 X 7 ins. 10 ins. in ground for cor. to sec's. 26. 27. 34 and 35 marked 2 notches on E and 1 on S edges and raised a stone mound alongside.
	Land mountainous
	Soil 4 th rate.
	Dense undergrowth and mountainous on 80.00 chs.

R 3

Chs.	Eas sec's.
40.00	Set
80.16	Inte S of from on a with
3.00	Sev N.W
13.00	Leav
19.00	Roa
36.00	Rid
40.08	Set 10 in mort a st
45.00	Wash
80.16	The c La S De 80.16

R 3 W. S. L. M.

Chs. East on a random line bet. sec's. 26 and 35

Var. 16° 30' E.

40.00 Set temp. 1/4 sec. cor.

80.16 Intersect N & S line 19 lks S of cor. to sec's. 25. 26. 35 & 36. from which I run S 89°52' W on a true line bet. sec's. 26 & 35 with same Var.

3.00 Sevier river 50 lks wide flows N.W.

13.00 Leave river bottom

19.00 Road bears N.W.

35.00 Ridge bears N and S.

40.08 Set flint stone 14 x 10 x 7 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

45.00 Wash in hollow drains N.E.

80.16 The cor. to sec's. 26. 27. 34 & 35

Land mountainous.

Soil 1st & 3rd rate.

Dense undergrowth on

80.16 chs.

Subdivisions T 14 S

Chs. North bet secs. 26 and 27
Var. 16° 30' E.

10.00 Ridge bears E and W.

40.00 Set granite 17x10x9 ins. 12 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.

49.00 Ravine trains S E.

55.00 Ridge bears S.W. and N.E.

80.00 Set granite 30 x 18 x 10 ins. 20 ins. in ground for cor. to secs. 22. 23. 26 and 27 marked 2 notches on E and S edges and raised a stone mound alongside.

Land mountainous
Soil 4th rate,
Mountainous and dense undergrowth on 8000 ch

Chs. Ea
bet

40.00 Set
80.60 Inl
cor.
from
true

27.50 U. t
30.00 Rea
35.00 Dev
N. W

40.30 Set
12 in
mor
a sto

48.50 Dev
60.75 "
80.60 The
L
S
D
80. 6

BOOK-A-201 R-48

R 3 W. S. L. M.

Chs. East on a random line bet. secs. 23 and 26.
Var. 16° 30' E.

40.00 Set temp. 1/4 sec. cor.

80.60 Intersect N and S line at cor. to secs. 23, 24, 25 & 26. from which I run west on a true line with same Var.

27.50 U. P. R. R. bears N. W. & S. E.

30.00 Road N. W. & S. E.

35.00 Devier Riv. 150 lks wide flows N. W.

40.30 Set sandstone 18 x 10 x 10 ins. 12 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound along side.

48.50 Devier Riv. 100 lks wide flows S.

60.75 " " 75 lks " " N

80.60 The cor. to secs. 22. 23. 26 & 27.

Land mostly level.

Soil 2nd rate.

Dense undergrowth on 80.60 chs.

Subdivisions T 14 S

Chs.	
	North bet. secs. 22 & 23. Var. 16° 30' E.
10.00	Ridge bears E & W.
11.40	Sevier River. 120 lks wide flows N
14.25	Road bears E & W.
16.75	U. C. R.R. bears E & W.
31.00	Road bears N E & S W.
40.00	Set limestone 14 X 10 X 8 ins 10 in in ground for 1/4 sec. cor. mkd 1/4 on W face and raised a stone mound alongside.
80.00	Set line stone 18 X 14 X 7 ins. 12 ins. in ground for cor. to secs. 14, 15, 22 & 23 marked 2 notches on E and 3 on S edges and raised a stone mound alongside.

Land rolling
S. 2nd rate
Dense undergrowth on 80.00 chs.

R 3 W. S. L. M.

Chs.

East on a random line bet. sec's. 14 and 23.

Var. 16° 30' E.

40.00 Set temp. 1/4 sec. cor.

80.10 Intersect N and S line 18 lks N of cor. to sec's. 13. 14. 23. & 24 from which I run N 89° 52' W on a true line bet. sec's. 14 & 23 with same Var.

7.50 Wash in hollow drains S.

10.00 Road bears S W and N E.

40.05 Set a granite 14x10x5 ins 10 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

60.00 Ridge bears N and S.

80.10 The cor. to sec's 14. 15. 22 & 23.

Land rolling and broken

Soil 2nd & 4th rate.

Dense undergrowth on 80.10 chs.

Subdivisions T 14 S

Chs. North bet. sec's. 14 and 15
Var. 16° 30' E.

22.00 Hollow drains S W.

40.00 Set limestone 14 x 9 x 7 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.

43.00 Enter broad hollow. bears N E & S W.

62.00 Road bears N E & S W.

75.00 Leave hollow

80.00 Set lime stone 15 x 10 x 6 ins. 10 ins. in ground for cor. to sec's. 10. 11. 14 and 15 marked 2 notches on E and 4 on Sedges and raised a stone mound alongside.

Land rolling.

Soil 3rd rate.

Dense undergrowth on 8000 chs.

Scattering timber along line.

BOOK-A-201

R 3 W. S. L. M.

Chs. East on a random line bet. secs. 11 and 14.
Var. 16° 30' E.

40.00 Set temp. 1/4 sec. cor.

80.00 Intersect N and S line, 31 lks N of cor. to secs. 11, 12, 13 & 14, from which I run N 89° 47' W on a true line bet. secs. 11 & 14 with same Var.

4.00 Ridge bears S W & N. E.

40.00 Set gray granite 16 X 12 X 8 ins. 11 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside. A cedar 8 ins. diam. bears S 5° E 40 lks dist. marked 1/4 S. B. T. No other tree within limits.

78.50 Road bears S & N. W.

80.00 The cor. to secs. 10, 11, 14 & 15

Land rolling.
Soil 3rd rate.
Dense undergrowth and scattering timber on 80.00 chs.

Subdivisions T 14 S

Chs. North bet secs. 10 and 11
Var. 16°30' E.

6.50 Road bears N W and S.E.

40.00 Set lime stone 16X12X7 ins. 11 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.

43.00 Ridge bears N E & S W.

52.50 Hollow drains S.W.

80.00 Set lime stone 15X11X9 ins, 10 ins. in ground for cor. to secs. 2. 3. 10 & 11 marked 2 notches on E and 5 on S edges and raised a stone mound alongside.

Land rolling
Soil 3rd rate.
Scattering timber and dense undergrowth on 80.00 chs.

R

Chs. Ec
sec

40.00 Si

80.15 Int
N o
wh
a t
wi

19.00 Ri

30.00 Ro

39.00 Ri

40.07 Se
12
cor
rai
C
20 t
N

55.00 Ro

80.15 Th

Dec

R 3 W. S. L. M.

Chs. East on a random line bet. sec's. 2 and 11

Var. 16° 30' E.

40.00 Set temp. 1/4 sec. cor.

80.15 Intersect N and S line 10 lks N of cor. to sec's 1. 2. 11 & 12 from which I run N 89° 56' W on a true line bet. sec's 2 & 11 with same Var.

19.00 Ridge bears N. W. & S. E.

30.00 Ravine drains S. E.

39.00 Ridge bears S E & N W.

40.07 Set lime stone 18 X 8 X 6 ins, 12 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside

A cedar 7 ins. diam bears N 20 lks dist. marked 1/4 S. B. T.

No other tree within limits.

55.00 Ravine drains S E.

80.15 The cor. to sec's. 2, 3. 10 & 11

Land rolling.

Soil 4th rate.

Dense undergrowth on 80.15 chs.

Subdivisions T 14 S

Chs. North on a true line bet. secs. 2 and 3.

Var. 16° 30' E.

20.00 Ridge bears N.W. & S.E.

30.00 Ravine drains E.

40.00 Set line stone 14 X 8 X 7 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.

50.00 Ridge Bears N.W. and S.E.

61.00 Ravine drains S.E.

68.20 Intersect N boundary of Tp. 14. 15 chs. west of the cor. to secs. 2. 3. 34 & 35. At point of intersection set sandstone 16 X 12 X 11 ins. 11 ins. in ground for closing cor. to secs. 2 and 3 marked 2 notches on E and 4 on W edges and CC and raised a stone mound alongside.

Land rolling.

Soil 3rd rate

Dense undergrowth on 68.20 chs.

BOOK-A-201

R 3 W. S. L. M.

Chs. From the cor. to secs. 33 & 34 on the S. Bound of the Tp. I run north bet. secs. 33 & 34

Var. 16° 30' E.

4.00 Ridge bears N W & S.E.

35.00 Foot of mountain bears S.E. & N.W.

40.00 Set lime stone 15 x 10 x 9 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.

65.00 Ridge bears E and W.

80.00 Set granite 15 x 10 x 7 ins. 10 ins. in ground for cor. to secs. 27. 28. 33 & 34 marked 3 notches on E and 1 on S edges and raised a stone mound alongside.

Land mountainous.

Soil 4th rate.

Mountainous and dense undergrowth on 80.00 chs.

Subdivisions T 14 S

Chs. East on a random line bet. secs. 27 and 34.

Var. 16° 30' E.

40.00 Set temp. 1/4 sec. cor.

80.00 Intersect N and S line 28 Chs. N of cor. to secs. 26. 27. 34 & 35 from which I run N 89° 48' W on a true line bet. secs. 27 & 34 with same Var.

4.00 Ravine drains S.

12.50 Ridge bears N E & S W.

34.50 Ravine drains N. W.

45.00 Set granite 15 X 12 X 8 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside

63.50 Ridge bears N. W & S. E.

80.00 The cor. to secs. 27. 28. 33 & 34

Land mountainous.

Soil 4 th rate.

Mountainous and dense undergrowth on 8.00 chs.

February 14, 1884

R 3

Chs. North

5.00 Ridge

19.60 Road

32.00 Ridg

40.00 Set in gro 1/4 on N mou

43.25 Road

57.00 Devi

62.50 U. S.

68.00 Road

80.00 Set g ground and 2 and 3 stone

Lan

Sa

Den

80.00

BOOK-A-201

R 3 W S. L. M.

Chs. North bet. sec's. 27 and 28.
Var. 16° 30' E.

5.00 Ridge bears N E and S W.

19.60 Road bears N E and S W.

32.00 Ridge bears N E & S W.

40.00 Set sand stone 14x10x5 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.

43.25 Road bears N E and S W.

57.00 Devil's Riv. 150 lks wide flows W

62.50 U. P. R.R. bears E & W.

68.00 Road bears E & W.

80.00 Set granite 15x10x7 ins. 10 ins. in ground for cor. to sec's. 21. 22. 27 and 28 marked 3 notches on E and 2 on S edges and raised a stone mound alongside.

Land rolling.
Soil 2nd rate.
Dense undergrowth on 80.00 chs.

2 Dig.

Subdivisions T 14 S

Chs. East on a random line bet. sec's. 22 and 27.

Var. 16° 30' E.

40.00 Set temp. 1/4 sec. cor.

80.00 Intersect N and S line 14 l/s N of cor. to sec's. 22. 23. 26 & 27 from which I run N 89° 54' W on a true line bet. sec's. 22 & 27 with same Var.

5.00 Ridge bears N and S.

25.50 Road bears N E and S W.

29.50 Wash drains N. W.

34.75 Devier Riv. 75 l/s wide flow S.

40.00 Set nine stone 14 x 8 x 6 ins 10 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

59.50 U. C. R.R. bears S W & N. E.

60.00 Road bears N E & S W.

77.50 Road " N W & S E.

80.00 The cor. to sec's. 21. 22. 27 & 28.

Land rolling.

Soil 2nd & 4th rate.

Dense undergrowth on 80.00 chs.

R 3 W. S. L. M.

Chs. North bet. sec's. 21 and 22
Var. 16° 30' E.

.75 Road bears N W x S E.

36.00 Hollow drains S. E.

40.00 Set lime stone 14x10x4 ins.
10 ins. in ground for 1/4 sec. cor.
marked 1/4 on W face and raised
a stone mound alongside.

62.00 Road bears S. E. x N. W.

80.00 Set sand stone 15x10x7 ins.
10 ins. in ground for cor. to sec's.
15. 16. 21 & 22 marked 3 notches
on E and S edges and raised
a stone mound alongside.

Land level
Soil 2 nd rate.
Dense undergrowth on
80.00 chs.

Subdivisions T 14 S

Chs. East on a random line bet secs. 15 and 22
Var. 16° 30' E.

40.00 Set temp. 1/4 sec. cor.

79.60 Intersect N and S line at cor. to secs. 14. 15. 22 & 23. from which Trav West on a True line bet secs. 15 & 22 with same Var.

12.00 Road bears N and S.

13.50 Wash drains S.N.

28.00 " " S.

39.80 Set line stone 14x10x10 ins. 10 ins in ground for 1/4 sec. cor., marked 1/4 on N face and raised a stone mound alongside.

79.60 The cor. to secs. 15. 16. 21 and 22
Land rolling.
Soil 2 nd & 4 th rate.
Dense undergrowth on 79.60 chs.

R 3

Chs. Nort

22.00 Hol

40.00 Set
11 ins
cor.
raised

45.00 Rid

70.00 Rou

80.00 Set
13 in
secs
nole
edges
mo

S
7
una

BOOK-A-201

R 3 W. S. L. M.

Chs. North bet. sec's. 15 and 16.
Var. 16° 30' E.

22.00 Hollow drains S. E.

40.00 Set sandstone 16 x 12 x 7 ins. 11 ins. in ground for 1/4 sec. cor. marked 4 on W face and raised a stone mound alongside.

45.00 Ridge bears N W & S E.

70.00 Ravine drains S E.

80.00 Set lime stone 19 x 12 x 7 ins. 13 ins. in ground for cor. to sec's. 9. 10. 15 & 16 marked 3 notches on E and 4 on S edges and raised a stone mound alongside.

Land mountainous.
Soil 3 rd rate.
Mountainous and dense undergrowth on 80.00 chs.

Subdivisions T. 14 S.

Chs. East on a random line bet. secs. 10 and 15.

Var. 16° 30' E.

40.00 Set temp. 1/4 sec. cor.

80.20 Intersect N and S line 35 ch. N of cor. to secs. 10. 11. 14 & 15 from which I run N 89° 45' on a true line bet. secs. 10 & 15 with some Var.

35.00 Canon drains S E.

40.10 Set lime stone 17 x 9 x 6 ins. 11 in ground for 1/4 sec cor. mark 1/4 on N face and raised a stone mound alongside.

80.20 The cor. to secs. 9. 10. 15 & 16.

Land rolling.

Soil 3rd rate.

Scattering timber and dense undergrowth on 80.20 ch.

R 3

Chs. Nor

4.00 Ridg

25.00 Rov

35.00 Ridg

40.00 Set

10 in

cor.

rais

51.50 Rav

74.00 Ri

80.00 Set

14 in

secs.

note

and

alon

und

BOOK-A-201

R 3 W S. L. M.

Chs. North bet. sec's. 9 and 10
Var. 16° 30' E.

4.00 Ridge bears E & W.

25.00 Ravine drains S W.

35.00 Ridge bears N W & S E.

40.00 Set line stone 14 X 11 X 7 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.

51.50 Ravine drains E.

74.00 Ridge bears S E and N. W.

80.00 Set line stone 20 X 12 X 10 ins. 14 ins. in ground for cor. to sec's. 3. 4. 9 and 10 marked 3 notches on E and 5 on S edges and raised a stone mound alongside.

Land mountainous.

Soil 4th rate.

Scattering timber on line.

Mountainous and dense undergrowth on 80.00 chs.

Subdivisions T 14 S

Chs.	
	East on a random line bet. sec's. 3 and 10. Var. 16° 30' E.
40.00	Set temp. 1/4 sec. cor.
80.10	Intersect N and S line 14 l/s N of cor. to sec's. 2. 3. 10 & 11 from which I run N 89° 54' W on a true line bet. sec's. 3 & 10 with same Var.
7.00	Ridge bears N.W. & S.E.
30.00	Ravine drains S.E.
40.05	Set line stone 19 X 10 X 6 ins. 13 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside
60.00	Ridge bears N W & S.E.
74.00	Ravine drains S.E.
80.10	The cor. to sec's. 3. 4. 9 & 10.

Land mountainous.
Soil 4 th rate.
Scattering timber on 80.10 chs.
Mountainous and dense undergrowth on 80.10 chs.

R 3

Chs.	
5.00	Ravin
20.00	Ridge
39.75	Ravin
40.00	Set 11 ins mort raised
68.40	Inter 13.90 3.4.3 terse 12 X 8 for c mort on E a st

Land

Soil

Scattering

Mountainous

unde

R 3 W. S. L. M.

Chs. North bet. sec's. 3 and 4
Var. 16° 30' E.

5.00 Ravine drains S E.

20.00 Ridge bears S E & N. W.

39.75 Ravine drains S W.

40.00 Set line stone 16 X 10 X 8 ins. 11 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.

68.40 Intersect N bound of Tp. 13.90 chs. W of the cor. to sec's. 3. 4. 33 & 34. At point of intersection set sand stone 12 X 8 X 8 ins. 8 ins. in ground for closing cor. to sec's. 3 & 4 marked C. C. with 3 notches on E and W edges and raised a stone mound alongside.

Land mountainous.

Soil 4th rate.

Timber along line.

Mountainous and dense undergrowth on 68.40 chs.

Subdivisions T 14 S

chs.	From the cor. to sec's. 32 & 33 on the S Bound of the Tp. I run N on a true line bet. sec's. 32 & 33.
	Var. 16° 30' E.
40.00	Set line stone 15 x 10 x 7 ins. 10 ins. in ground for 1/4 sec. cor. marked 4 on W face and raised a stone mound alongside
41.00	Ridge bears N E & S W.
46.00	Foot of ridge.
63.75	Road bears N. E. & S. W.
74.00	U. C. R. R. bears N. E. & S. W.
80.00	Set blue line stone 16 x 12 x 7 ins. 11 ins. in ground for cor. to sec's. 28, 29, 32 & 33 marked 4 notches on E and 1 on S edges and raised a stone mound alongside.
	Land broken & mountainous.
	Soil 2nd & 4th rate.
	Dense undergrowth on
80.00 chs.	

R.

chs.	Eas sec
40.00	Set
80.14	Tul cor. from true with
6.00	Rid
11.25	Roa
23.50	Rid
40.07	Set in mor raise
53.75	Roa
77.75	Ur
80.14	The L S D 80.

R. W. S. L. M.

Chs. East on a random line bet. sec's. 28 and 33.

Var. 16° 30' E.

40.00 Set temp. 1/4 sec. cor.

80.14 Intersect N and S line at cor. to sec's. 27. 28. 33 & 34 from which I run west on a true line bet. sec's. 28 & 33. with same Var.

6.00 Ridge bears N.E. & S.W.

11.25 Road in hollow drains S.W. & N.E.

23.50 Ridge bears N.E. & S.W.

40.07 Set granite 16 x 10 x 6 ins. 11 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

53.75 Road bears N.E. & S.W.

77.75 Ut. C.A.R. bears. N.E. & S.W.

80.14 The cor. to sec's. 28. 29. 32 & 33.

Land rolling.

Soil 2nd & 4th rate.

Dense undergrowth on 80.14 chs.

Subdivisions T 14 S

Chs.	
	North bet. secs. 28 and 29. Var. 16° 30' E.
5.10	Sevier River. 90 lks wide flows W
16.00	Road bears N.E. x S.W.
40.00	Set flint stone 14 x 10 x 6 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.
66.75	Road & fence, road bears E x W fence bears S.E. & N.W.
75.00	Ridge bears N.W. & S.E.
80.00	Set lime stone 24 x 10 x 6 ins. 16 ins. in ground for cor. to secs. 20. 21. 28 and 29. marked 4 notches on E and 2 on S edges and raised a stone mound alongside.

Land rolling.
Soil 3rd rate.
Scattering timber along line.
Dense undergrowth on 80.00 chs.

R 3

Chs.	
	Eas secs.
40.00	Set
80.00	Inte N of from on a with
40.00	Set 10 ins cor. raised
80.00	The and
	on E

BOOK-A-201

R 3 W. S. L. M.

Chs. East on a random line bet. secs. 21 and 28.

Var. 16° 30' E

40.00 Set temp. 1/4 sec. cor.

80.00 Intersect N and S. line 10 chs N of cor. to secs. 21. 22. 27 & 28 from which I run N 89° 36' W on a true line bet. secs. 21 & 28 with same Var.

40.00 Set lime stone 14 X 10 X 8 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound along S.

80.00 The cor. to secs. 20. 21. 28 and 29.

Land rolling.

Soil 3rd rate.

Dense undergrowth on 8.00 chs.

Feb. 15, 1884

Subdivisions T 14 S

Chs. North bet. secs. 20 and 21
Var. 16° 30' E.

25.00 Ridge bears N W & S. E.

40.00 Set line stone 38 X 18 X 12 ins
27 ins. in ground for 1/4 sec.
cor. marked 1/4 on W face
and raised a stone mound
alongside.

70.00 Trail in canon, drains S E.

80.00 Set line stone 18 X 10 X 6 ins
12 ins. in ground for cor.
to secs. 16. 17. 20. & 21 marked
4 notches on E and 3 on S
edges and raised a stone
mound alongside.

Land mountainous.
Soil 4 th rate.
Mountainous and
dense undergrowth on
80.00 chs.

R 3

Chs. Ea
bet

40.00 Set

79.70 Int
cks
22,
N 8
bet.
sam

25.00 Roa

30.00 Ca

34.95 Set
13 in
mar
rais
alon

79.90 The

und

R 3 W. S. L. M.

Chs. East on a random line bet. secs. 16 and 21.
Var. 16° 30' E.

40.00 Set temp. 1/4 sec. cor.

79.70 Intersect N and S line 11 lks N of cor. to secs. 15, 16, 21 & 22, from which I run N 89° 55' W on a true line bet. secs. 16 and 21. with same Var.

25.00 Road bears N W and S E.

30.00 Canon drains S E

34.95 Set line stone 19 x 10 x 7 ins. 13 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

79.90 The cor. to secs. 16. 17. 20 & 21

Land mountainous.

Soil 4 th rate.

Mountainous and dense undergrowth on 79.90 chs.

2/3

Subdivisions T 14 S

Chs. North bet. secs. 16 and 17.
Var. 16° 30' E

22.50 Ridge bears E and W.

40.00 Set lime stone 13 x 11 x 6 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside

45.00 Canon drains E.

80.00 Set lime stone 15 x 9 x 7 ins. 10 ins. in ground for cor. to secs. 8. 9. 16 & 17 marked 4 notches on E and 4 on S edges and raised a stone mound alongside.

Land mountainous.
Soil 4th rate.
Timber scattering.
Mountainous and dense undergrowth on 80.00 chs.

BOOK-A-201

R 3 W. S. L. M.

Chs. East on a random line bet. secs. 9 and 16.
Var. 16° 30' E.

40.00 Set temp. 1/4 sec. cor.

79.75 Intersect N & S line 18 lks S of cor. to secs. 9.10. 15 & 16 from which I run S 89° 52' W on a true line bet. secs. 9 & 16 with same Var.

34.00 Ravine drains S.E.

39.87 Set flint stone 18 x 9 x 6 ins. 12 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

53.00 Ridge bears N Ward S E.

79.75 The cor. to secs. 8. 9. 16 & 17

Land mountainous.

Soil 4th rate.

Mountainous and dense undergrowth on 79.75 chs.

Subdivisions T14 S

chs.	
	North bet. secs. 8 and 9. Var. 16° 30' E.
22.00	Ridge bears N W and S. E.
40.00	Set lime stone 16x10x7 ins. 11 ins. in ground for 1/4 sec cor. marked 1/4 on W face and raised a stone mound alongside
45.00	Trail in canon, drains S.
65.00	Ridge bears N.E. x S.W.
80.00	Set lime stone 18x10x6 ins. 12 ins. in ground for cor. to secs. 4. 5. 8 x 9. marked 4 notches on E and 5 on S edges and raised a stone mound alongside.

Land mountainous.
Soil 4th rate.
Timber scattering.
Mountainous and dense undergrowth on 80.00 chs.

R 3

chs.	
	E bec
40.00	Set
80.00	Ine cor wh tru wit
10.00	Ri
35.00	Ca
40.00	Se 11 in cor and alon
60.00	Ri
80.00	The

und

R 3 W. S. L. M.

Chs. East on a random line bet. Secs. 4 and 9.

Var. 16°30' E.

40.00 Set temp. 1/4 sec. cor.

80.00 Intersect N and S line at cor. to secs. 3. 4. 9 & 10 from which I run west on a true line bet. secs. 4 and 9 with same Var.

10.00 Ridge bears N W & S E.

35.00 Canon drains S E.

40.00 Set lime stone 16x4x8 ins. 11 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside

60.00 Ridge bears N E & S W.

80.00 The cor. to secs. 4. 5. 8 & 9.

Land mountainous.

Soil 4th rate.

Mountainous and dense undergrowth on 80.00 chs.

Subdivisions T14 S

Chs. North on a true line bet. secs. 4 and 5.. Va. 16° 30' E.

4.00 Ravine drains W.

20.00 Ridge bears E and W.

40.00 Set line stone 17 X 12 X 6 ins. 12 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.

68.60 Intersect N. Bound of Twp. 13.75 chs. W of the cor. to secs. 4. 5. 32 & 33. At point of intersection set sand stone 16 X 12 X 11 ins. 11 ins. in ground for closing cor. to secs. 4 & 5, marked C.C. with 4 notches on E and 2 on W edges and raised a stone mound alongside.

Land rolling.

Soil 3rd rate.

Timber scattering.

Dense undergrowth on 68.60 chs.

R 3

Chs. Fro
32 o
Tp.
line

Jam
R 3

15.00 Foo
21.75 Sw
22.40 U. C.
29.50 Road
40.00 Set
ins.
cor.
rais
along
50.50 Road
55.00 Rid
80.00 Set
10 ins
secs.
notc
and
along

R 3 W. S. L. M.

chs.	From the cor. to sec's. 31 & 32 on the S. Bound. of the Tp. I run north on a true line bet. sec's. 31 and 32
	Var. 16° 30' E.
	James R. Roe's house bears N 37° E about 30.00 chs. dist.
13.00	Foot of mountain.
21.75	Sevier Riv. 75 lks wide flows N.W.
22.40	U. C. R. R. bears E & W.
29.50	Road bears N. W. & S. E.
40.00	Set granite 18x10x6 ins. 12 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.
50.50	Road bears N E & S W.
63.00	Ridge bears N E & S W.
80.00	Set lime stone 14x9x7 ins. 10 ins. in ground for cor. to sec's. 29, 30, 31 & 32 marked 5 notches on E and 1 on S edges and raised a stone mound alongside.

Subdivisions T 14 S.

Chs. Cedar 8 ins. diam. bears N 85° E 15 lks dist. marked T 14 S. R 3 W S. 29 B.T.
No other tree within limits
Land rolling.
Soil 2nd & 3rd rate.
Timber scattering.
Dense undergrowth on 80.00 chs.

East on a random line bet. secs. 29 and 32.
Var. 16° 30' E.

[illegible].00 Set temp. 1/4 sec. cor.
80.00 Intersect N and S line. 15 lks N of cor. to secs. 28. 29. 32 & 33 from which I run N 89° 54' W on a true line bet. secs. 29 and 32 with same Var.
8.00 Road bears N E & S W.
20.00 Ridge bears N E & S W.
27.50 Sevier River 100 lks wide flows S
40.00 Set flint stone 14 x 7 x 6 ins. 10 ins. in ground for 1/4 sec. cor. marked

Chs. 1/4 on
mou
47.50 Ridge
51.50 Rovm
60.00 Wash
76.00 Wast
80.00 The
Lar
Su
S
line.
N
80.00
D
growth

Wes
bet.

40.00 Set
80.10 Inter
at co
which

R 3 W. S. L. M.

Chs. ¼ on N face and raised a stone mound alongside.
47.50 Ridge bears N.W. and S.E.
57.50 Rovine drains S.E.
60.00 Wash drains S.
76.00 Wash " S.E.
80.00 The cor. to sec's. 29. 30. 31 & 32.
Land mountainous.
Soil 4th rate.
Scattering timber on line.
Mountainous on 80.00 chs.
Dense artemesia under growth on 80.00 chs.

West on a random line bet. sec's. 30 and 31
Var. 16° 30' E.
40.00 Set temp. ¼ sec cor.
80.10 Intersect W. Bound of Tp. at cor. to sec's. 30 & 31, from which I run east on a true

Subdivisions T 14 S

Chs.	
	line bet. sec's. 30 and 31 with same Var.
20.00	Ridge bears SW & NE.
40.10	Set line stone 17 X 10 X 7 ins 12 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.
42.50	Wash drains S.
64.75	" " "
80.10	The cor. to sec's. 29. 30. 31 & 32

Land rolling and broken.

Soil rocky, 3rd and 4th rate.

Scattering cedars along line.

Dense undergrowth on 80.10 chs.

R 3 W. S. L. M.

chs. North bet. secs. 29 and 30.
Var. 16° 30' E.

37.50 Ridge bears N W and S.E.

40.00 Set line stone 15x10x7 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.

55.00 Canon drains S E.

80.00 Set line stone 19x10x6 ins. 13 ins in ground for cor. to secs. 19. 20. 29 and 30 marked 5 notches on E and 2 on S edges and raised a stone mound alongside.

Land mountainous.
Soil 4th rate.
Mountainous and dense undergrowth on 80.00 chs.

Subdivisions T 14 S

Chs. East on a random line bet. sec's. 20 and 29.
Var. 16° 30' E.

40.00 Set temp. ¼ sec. cor.

80.10 Intersect N and S line 10 lks N of cor. to sec's. 20. 21. 28 & 29 from which I run N 89° 56' W on a true line bet. sec's. 20 & 29 with same Var.

10.00 Ridge bears N W & S E.

35.00 Canon drains S E.

40.05 Set lime stone 18 X 10 X 7 ins 12 ins. in ground for ¼ sec. cor. marked ¼ on N face and raised a stone mound alongside

72.50 Ridge bears N W and S E.

80.10 The cor. to sec's. 19. 20. 29 & 30

Land mountainous.
Soil 4th rate.
Mountainous and dense undergrowth on 80.10 chs.
February 16. 1884.

R 3

Chs. West sec's

40.00 Set

79.80 Int cor. which line with

14.00 Can

25.00 Ri

39.80 Set 12 in mar a st

45.00 Tra

79.80 The L S T N und

BOOK-A-201 287

R 3 W. S. L. M.

Chs. West on a random line bet. sec's. 19 and 30.

Var. 16° 30' E.

40.00 Set temp. ¼ sec. cor.

79.80 Intersect W bound. of Tp. at cor. to sec's. 19 and 30 from which I run East on a true line bet. sec's. 19 and 30. with same Var.

14.00. Canon drain S.E.

26.00 Ridge bears S.E. & N.W.

39.80 Set line stone 17 X 11 X 4 ins. 12 ins. in ground for ¼ sec. cor. marked ¼ on N face and raised a stone mound alongside.

45.00 Trail in canon, drain S.E.

79.80 The cor. to sec's. 19. 20. 29 & 30.

Land mountainous.

Soil 4th rate.

Timber scattering.

Mountainous and dense undergrowth on 79.80 Chs.

Subdivisions T14S

Chs. North bet. sec's. 19 and 20
Var. 16°30' E.

12.00 Ridge bears N W and S.E.

38.00 Canon drains S.E.

40.00 Set flint stone 17X10X7 ins 12 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside

63.00 Ridge bears S E & N W.

80.00 Set flint stone 19X10X6 ins. 13 ins. in ground for cor. to sec's. 17, 18, 19 & 20 marked 5 notches on E and 3 on S edges and raised a stone mound alongside.

Land mountainous.

Soil 4th rate.

Mountainous and dense undergrowth on 80.00 chs.

R 3 W. S. L. M.

chs.	East on a random line bet. secs. 17 and 20.
	Var. 16° 30' E.
40.00	Set temp. 1/4 sec. cor.
80.00	Intersect N and S line 18 l/s N of cor. to sec's. 16. 17. 20 & 21 from which I run N 89° 52' W on a true line bet. secs. 17 & 20. with same Var.
5.00	Ridge bears N. W. and S. E
40.00	In canon drains S E set sandstone 14 X 10 X 6 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.
80.00	The Cor. to sec's 17. 18. 19 and 20.
	Land mountainous.
	Soil 4th rate
	Mountainous and dense under growth on Pavo cho

Subdivisions T 14 S

Chs. West on a random line bet. secs. 18 and 19.

Var. 16° 30' E.

40.00 Set temp. 1/4 sec. cor.

79.70 Intersect W Bound of Tp. 14 l'ks S of cor. to secs. 18 & 19 from which I run S 89° 54' E on a true line bet. secs. 18 & 19 with same Var.

2.00 Ridge bears N E & S W.

9.00 Canon drains S. W.

20.00 Ridge bears N and S.

39.70 Set lime stone 14 X 10 X 6 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

79.70 The cor. to secs. 17. 18. 19 & 20.

Land mountainous,
Soil 4th rate.
Mountains and dense undergrowth on 79.70 chs.

(R 3

Chs. Nor

25.00 Can

40.00 Set

10 ins

mar

rais

60.00 (Rid

80.00 Set

11 ins

secs.

note

edges

mou

Le

So

T

N

unde

BOOK-A-201

R 3 W. S. L. M.

Chs North bet. secs. 17 and 18.
Var. 16° 30' E.

25.00 Canon drains S E.

40.00 Set lime stone 15 x 9 x 6 ins.
10 ins. in ground for 1/4 sec. cor.
marked 1/4 on W face and
raised a stone mound alongside

50.00 Ridge bears N W & S E.

80.00 Set lime stone 16 x 10 x 7 ins.
11 ins. in ground for cor. to
secs. 7. 8. 17 & 18 marked 5
notches on E and 4 on S
edges and raised a stone
mound alongside.

Land mountainous.
Soil 4 th rate.
Timber scattering.
Mountainous and dense
undergrowth on 80.00 chs.

Subdivisions T14S

Chs. East on a random line bet. secs. 8 and 17.
Var. 16°30' E.

40.00 Set temp. 1/4 sec. cor.

79.80 Intersect N and S line 21 lks N of cor. to secs. 8. 9. 16 & 17 from which I run N 89°57' W on a true line bet. secs. 8 & 17 with same Var.

5.00 Canon drains S.

15.00 Ridge bears N and S.

35.00 Canon drains SE.

37.90 Set flint stone 16 x 9 x 6 ins 11 ins. in ground for 1/4 sec. cor marked 1/4 on N face and raised a stone mound alongside.

79.80 The cor. to secs. 7. 8. 17 & 18

Land mountainous.

Soil 4th rate.

Mountainous and dense undergrowth on 79.80 Chs

BOOK-A-201

R 3 W. S. L. M.

Chs. West on a random line bet. sec's. 7 and 18.

Var. 16° 30' E.

40.00 Set temp. 1/4 sec. cor.

80.15 Intersect N bound. of Tp. 25 lks S of cor. to sec's. 7 & 18 from which I run S 89° 49' E on a true line bet. sec's. 7 & 18 with same Var.

35.00 Ridge bears NE & SW.

40.15 Set lime stone 15 X 12 X 6 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

80.15 The cor. to sec's. 7. 8. 17 & 18

Land mountainous.

Soil 4th rate.

Mountainous and dense undergrowth on 80.15 chs.

Scattering cedars.

Subdivisions T14S

Chs. North bet. secs. 7 and 8.
Var. 16° 30' E.

34.00 Canon drains S.E.

40.00 Set flint stone 17x12x12 in
12 ins. in ground for 1/4 sec cor.
marked 1/4 on W face and
raised a stone mound alongside

60.00 (Ridge bears N E and S E.

80.00 Set lime stone 16x9x9 ins.
11 ins. in ground for cor. to
secs. 5. 6. 7 & 8 marked 5
notches on E and S edges and
raised a stone mound
alongside.

Land mountainous,
Soil 4th rate.
Timber, scattering.
Mountainous and dense
underwrowth on 80.00 chs.

R 3 W

Chs. East
bet.

40.00 set

79.85 Inter
cor. to
from
a bru
with

27.50 Cano

39.92 Set
13 ins
cor.
raised

60.00 Ridge

79.85 The
Lou
So
High Mo
underw

R 3 W. S. L. M.

Chs. East on a random line bet. sec's. 5 and 8.
Var. 16° 30' E.

40.00 set temp 1/4 sec. cor.

79.85 Intersect N and S line at cor. to secs. 4, 5, 8 and 9. from which I run west on a true line bet. sec's 5 and 8. with same Var.

27.50 Canon draws S W.

39.92 Set lime stone 17 X 9 X 8 ins. 13 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

60.00 Ridge bears N E & S W.

79.85 The cor. to sec's. 5, 6, 7 & 8.
Land mountainous.
Soil 4th rate.
High Mountains and undergrowth on 79.85 chs.

Subdivisions T 14 S

Chs. West on a random line bet. sec's. 6 and 7.
Var. 16° 30' E.

40.00 Set temp. 1/4 sec. cor.

80.10 Intersect West Bound of Tp. 30 Lks S of cor. to sec's. 6 & 7 from which Drum S 89° 47' E on a true line bet. sec's. 6 & 7 with same Var.

15.00 Ravine drains N.E.

30.00 Ridge bears N E & S W.

35.00 Ravine drains N.E.

40.10 Set lime stone 19X10X7 ins. 13 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

45.00 Ridge bears N E & S W.

55.00 Ravine drains N E.

80.10 The cor. to sec's. 5. 6. 7 & 8.

Land mountainous.

Soil 3rd rate.

Grass on line.

High Mountains on 80.10 chs.

BOOK-A-201

R 3 W. S. L. M.

Chs. North on a true line bet. secs. 5 and 6.

Var. 16° 30' E.

10.00 Enter dense sage brush.

30.00 Hollow draws N.E

40.00 Set line stone 17X10X6 ins. 12 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.

55.00 Ridge bears N E & S W.

58.85 Intersect N boundary of Tp. 13.50 chs. W of cor. to secs. 5. 6. 31 and 32. At point of intersection set sand stone 18X12X12 ins 12 ins. in ground for closing cor. to secs. 5 & 6 marked CC with 3 notches on E and 1 on W edges and raised a stone mound alongside.

Land descending north.

Soil 3rd rate.

Dense undergrowth on

58.85 chs.

Feb. 17. 1884.

Subdivisions T 14 S

General Description.

This township is mostly mountainous, covered with dense undergrowth and some scattering timber.

It contains good grazing land and some good agricultural land.

The Sevier Riv. flows through the southern part of the Tp.

The Utah Central R.R. also runs through the southern part.

There is a house in the S E ¼ of sec. 26.

The applicant for survey ~~Tom~~ James A. Ross has his improvements in sec. 32 on the Sevier river.

They consist of a cultivated field of about 100 acres, a house and barn.

The railroad section house is located in the

BOOK-A

R 3

N W

U.

BOOK-A-201

R 3 W. S. L. M.

N W ¼ of Sec. 36.

U. S. Dep. Surveyor.

BOOK-A-201

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, June 28th 1884

The foregoing field notes of the survey of the

Subdivisions

Township No. 14 S *Range No.* 3 W

Executed by Shadrach M Richardson

Under his *contract* no 123 *of the* 19th

day of December 1883, *in the month of*

February 1884, *having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

Fred Salomon

U. S. Surveyor General for Utah.

BOOK-A-201

REPORT: 1884

Filed 188

Examined by .....

Transcribed by Jno. A. Mitchell

Compared by Atherson & Mitchell

FIELD NOTES

OF THE re SURVEY OF THE

West and North boundaries and survey of the East boundary

OF

Township No 19 South

Range No 3 West

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Shadrach M. Richardson,

U. S. Deputy Surveyor,

Under his Contract No. 123

Dated December 19 th. 1883

Survey commenced February 18 th 1884

Survey completed " 20 th 1884

V

NAMES AND DUTIES OF ASSISTANTS:

.....*Compassman*

.....*Chainman.*

Chainman.

.....*Chainman.*

.....*Chainman.*

.....*Axeman.*

.....*Axeman.*

.....*Flagman.*

BOOK-A-20

Resurvey Wa

Survey

T

the accu

a Bur

Transit,

approved

Generals

B

survey T

instrume

on the

observat

and

adjust

Fro

19 and

which

set in

properly

a true

sec. 3

Throug

underg

BOOK-A-201

Resurvey West Bound. T19 S. R. 3 W.

Survey commenced Feb. 18/84

The instrument used in the survey of this contract is a Burts improved Solar Transit, being examined and approved by the U. S. Surveyor Generals Office.

Before commencing this survey I again test my instrument by an observation on the star Polaris and an observation for latitude and find it to be in perfect adjustment.

From the corner to Tps. 19 and 20 S. Rgs. 3 and 4 W which is a quartz stone firmly set in the ground and properly marked I run N. on a true resurvey line between secs. 31 and 36.

Var. 16° 35' E

Through dense sage brush undergrowth.

Resurvey West Boundary T 19 S

Chs.
23.00 Ditch drains S.W.
40.00 No trace of old corner, set limestone 16 x 10 x 5 ins. 11 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside
45.00 Road bears N.E. and S.W.
63.00 Ravine bears E and W.
80.00 No trace of old cor. set sand stone 14 x 12 x 6 ins. 10 ins. in ground for cor. to secs. 25, 30, 31 and 36 marked 5 notches on N and 1 on S edges and raised a stone mound alongside.

Land level
Soil sandy, 2nd rate
No timber
Dense undergrowth on

8000 chs.

BOOK-A-2

R 39

Chs. Nor

40.00 Old
sand
10 ins
cor.
dug
mound
along
66.50 Ridge
80.00 Fine
firmly
and
mound
L
D
D
8000

BOOK-A-201

R 3 W. S. L. M.

chs. North on a resurvey line
bet. secs. 25 and 30
Var. 16° 35' E.

40.00 Old cor. destroyed, set
sand stone 14 X 12 X 4 ins.
10 ins in ground for 1/4 sec.
cor. marked 1/4 on N face,
dug pitts and raised a
mound of earth and stone
alongside.

66.50 Ridge bears E and W

80.00 Find old cor. a lime stone
firmly set in the ground
and properly marked. I renew
mound and pitts.

Land rolling.

Soil 2 nd rate

Dense undergrowth on
8000 chs.

Resurvey West Boundary T19S

Chs. North on a resurvey line bet. secs. 19 and 24
Var. 16° 35' E.

16.25 Road bears S W and N E.
21.25 Telegraph line bears S W & N E.
27.50 Road bears S.W.
40.00 No trace of old cor. set granite 16x10x6 ins. 11 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.
54.00 Wash drains W.
61.00 " " S.W.
70.00 Road bears S.W.
80.00 No trace of old cor. set sand stone 19 X12 X7 ins. 13 ins. in ground for cor. to secs. 13. 18. 19 and 24 marked with 3 notches on N and S edges and raised a stone mound alongside.
Land rolling.
Soil 2nd rate.
Dense undergrowth on 80.00 chs.

R 3

Chs. North
bet

20.00 Enter
40.00 Find
prinly
and f
mound
a ced
East
No ot
80.00 No tr
sand
in gro
7. 12. 1
2 notc
edges
mour
a
N 45°
T19S.
No ot
Land
Soil
S cat
Dense

R. 3 W. S. L. M.

chs. North on a resurvey line
bet. sec's. 13 and 18
Var. 16° 35' E.

20.00 Enter scattering cedars.

40.00 Find old cor. a sandstone
firmly set in the ground
and properly marked. I renew
mound of stone and mark
a cedar 12 ins. diam. bearing
East 25 lks dist. T 14 S. B. T.
No other tree within limits.

80.00 No trace of old cor. set
sand stone 17 x 12 x 8 ins. 12 ins.
in ground for cor. to sec's.
7. 12. 13 and 18 marked with
2 notches on N and 4 on S
edges and raised a stone
mound alongside.

a cedar 10 ins. diam. bears
N 45° W 15 lks dist. marked.
T 14 S. R 4 W. S 12 B. T.
No other tree within limits.
Land rolling.
Soil 2nd rate.
Scattering timber on 60.00 chs
Dense undergrowth on 80.00

Resurvey West Bound. T19S.

chs. North on a resurvey line bet. secs. 7 and 12
Var. 16°35' E.

35.00 Ridge bears E and W.

40.00 Find old cor. a sand stone firmly set in the ground and properly marked. I renew mound of stone.

80.00 No trace of old cor. set sand stone 15 x 10 x 8 ins. 10 in in ground for cor. to secs. 1. 6. 7 and 12 marked 1 north on N and 5 on S edges and raised a stone mound alongside.

Land rolling.
Soil 3rd rate.
Timber scattering.
Dense undergrowth on 80.00 chs.

R. 3

chs. Nort
bet

2.00 Rav
7.00 Ridg
14.00 Rav
in r
40.00 No
sand
ins.
cor.
and
along
A
bears
marke
No
limi
80.00 Fi
down
stone
the g
18 a
4 W

T 19 S. R. 3 W. S. L. M.

chs. North on a resurvey line bet. sec's. 1 and 6.

Var. 16° 35' E.

2.00 Ravine drains W.

7.00 Ridge bears E and W.

14.00 Ravine drains W. road in ravine bears E and W.

40.00 No trace of old cor. set sand stone 14 X 10 X 8 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.

A cedar 9 ins. diam. bears S 44° E 20 lks dist marked 1/4 S. B. T.

No other tree within limits.

80.00 Find old cor. thrown down, reset same, a lime-stone 12 X 10 X 6 ins. 8 ins. in the ground for cor. to Tps. 18 and 19 S Ranges 3 and 4 West marked with 6

notches on each edge and raised a mound of stone alongside.

Land rolling.
Soil 3rd rate.
Timber scattering.
Dense undergrowth on 80.00 chs

Feb. 18/84

Note. Having retraced the line before resurveying it, I found most of the corners destroyed, and resurveyed it on account of the subdivisions closing on it.

For the same reason the North boundary of this Tp. was resurveyed.

For general description see subdivision notes of this Township.

chs. From
and 19
recently
I run
line b

Throug
9.50 Cedar
marked
29.10 Road
40.00 Old
same
ins. 11
sec. co
and r
alongs
A c
S 20
80.00 No t
line st
in gro
5. 6. 31
on E a
raised a

BOOK-A-201

Resurvey North Boundary T 19 S R 3 W.

chs. From the corner to Tps. 18 and 19 S. Rgs. 3 and 4 W recently reestablished by me I run east on a true resurvey line bet secs. 6 and 31

Var. 16° 30' E.

Through dense sagebrush.

9.50 Cedar tree 20 lks S of line, marked same.

29.10 Road bears N W and S.E.

40.00 Old cor. thrown down, reset same a quartz stone 16 x 12 x 4 ins. 11 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

A cedar 5 ins. diam. bears S 20 lks. dist. marked 1/4 S.B.T.

80.00 No trace of old cor, set limestone 12 x 10 x 2 ins. 8 ins. in ground for cor. to secs. 5, 6, 31 & 32 marked 5 notches on E and 1 on W edges and raised a stone mound alongside.

Resurvey North Bound. T 19 S

Chs. Land rolling.
Soil 2nd rate.
Dense undergrowth on 80.00 ch
Timber scattering.

East on a true resurvey line
bet. sec's. 5 and 32
Var. 16° 30' E.

4.40 Cedar, 24 ins. diam on line, marked same.

40.00 Old cor. thrown down, reset same a quartz stone 24 x 10 x 6 ins. 16 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a mound of stone alongside.

64.50 Road bears N and S.

80.00 Old cor. thrown down, reset same a limestone 12 x 9 x 6 ins. 8 ins. in ground for cor. to sec's. 4. 5. 32 & 33 marked 4 notches on E and 2 on W edges and

R 3 W.

chs. raised
along

80.00 c

East
line

Throu
No
lime
in gr
marke
raised
side.
No t
blue
8 ins.
to se
with
edges

40.00

80.00

chs. raised a stone mound alongside.

Land rolling.

Soil 2nd rate

Dense undergrowth on 80.00 chs.

East on a true resurvey line bet. secs. 4 and 33

Var. 16° 30' E.

Through dense sage brush.

40.00 No trace of old cor. set limestone 15 X 10 X 6 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound along-side.

80.00 No trace of old cor. set blue limestone 12 X 10 X 6 ins. 8 ins. in ground for cor. to secs. 3, 4, 33 & 34 marked with 3 notches on E and W edges and raised a stone

Resurvey North Boundary T19S

Chs. mound alongside.
Land rolling.
Soil 2nd rate.
Dense undergrowth on
80.00 chs.

East on a true resurvey line
bet. sec's. 3 and 34
Var. 16°30' E.
Through dense sage and oak
undergrowth.

7.50 Road and Deseret telegraph
line bears N. E. and S. W.

40.00 Find old cor. standing, a
quartz stone firmly set in the
ground and properly marked,
raised a stone mound
alongside.

80.00 No trace of old cor. set
quartzite 18 X 10 X 6 ins. 12 ins.
in ground for cor. to sec's.
2. 3. 34 and 35 marked 2
notches on E and 4 on W

BOOK-A-2

R. 3

Chs. edges
mou

80.00 c

East
bet.

Throu
Road
"
No t
blue
14 ins.
cor. r
raised
along
80.00 Find
firmly
and p
mou

R. 3 W. S. L. M.

chs. edges and raised a stone mound alongside
Land rolling
Soil 2nd rate
Dense undergrowth on
80.00 chs.

East on a true resurvey line bet. secs. 2 and 35
Var. 16° 30' E.
Through dense undergrowth.
6.50 Road bears N.E. and S.W.
20.00 " " N.W. " S.E.
40.00 No trace of old cor. set blue lime stone 20 x 10 x 8 ins. 14 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.
80.00 Find old cor. a quartzite firmly set in the ground and properly marked, I renew mound of stone.

Resurvey North B and T 19 S

chs. Land rolling.
Soil 2nd rate
Dense undergrowth on
80.00 chs.

East on a true resurvey line
bet. sec's. 1 and 36
Var. 16°30' E.

40.00 Find old cor. thrown down, reset
same a lime stone 24x18x12
ins. 16 ins. in ground for 1/4
sec. cor. marked 1/4 on N face
and raised a stone mound
alongside.

46.30 Ascend

80.00 Old cor. thrown down. reset
same a quartzite 24 x 20 x 10 ins
16 ins. in ground for cor. to
Tps. 18 and 19 S. Rgs. 2 and
3 W marked with 6 notches
on each edge and raised a
stone mound alongside.

BOOK-A-20

R 3

chs. Land
Soil
Dens
chs.

Note.
see s
this

BOOK-A-201 310

R 3 W. S. L. M.

chs. Land rolling.
Soil 2 nd rate.
Dense undergrowth on 8000
chs.

Feb. 19/84

Note. For general description
see subdivision notes of
this township.

East Boundary T. 19 S.

Note. The N.E. and S.E. corners of this Township being set, I find it necessary to run a random line between these corners, correcting back on a true line.

From the corner to Tps. 19 and 20 S. Rgs. 2 and 3 W which is a blue lime stone firmly set in the ground marked with 6 notches on each edge with stone mound alongside, I run North on a random line between Rgs. 2 and 3 W to the cor. of Tps. 18 and 19 S. Rgs. 2 and 3 W, previously reestablished by me.

The variation of my instrument is 16° 30' E.

I find the distance to be 5 miles 79.80 chs and the falling to be 2.40 chs. W.

The correction for the true

BOOK-A-201

chs. line will therefore be East 40 lks per mile and the course will be S 0° 17' W

From the corner to Tps. 18 and 19 S. Rgs. 2 and 3 W previously reestablished by me I run S 0° 17' W on a true line between secs. 1 and 6.

Var. 16° 30' E.

Through dense sage and oak undergrowth.

39.80 Set sandstone 14 x 12 x 8 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.

45.00 Ridge bears E and W.

79.80 Set sandstone 18 x 12 x 3 ins. 12 ins. in ground for cor. to secs. 1. 6. 7 and 12 marked 1 notch on N and 5 on S edges and raised a stone mound alongside.

Land rolling.

Soil 2nd rate.

Dense undergrowth on 79.80 chs.

East Boundary T19S

chs. S 0°17' W on a true line bet. sec's. 7 and 12
Var. 16° 30' E.

40.00 Set sandstone 14 x 9 x 7 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.

80.00 Set sandstone 14 x 12 x 7 ins 10 ins. in ground for cor. to sec's. 7, 12, 13 and 18 marked 2 notches on N and 4 on S edges and raised a stone mound alongside.

Land rolling.

Soil 2nd rate.

Dense undergrowth on 80.00 chs.

S 0°17' W on a true line bet. sec's. 13 and 18
Var. 16° 30' E.

Through dense sage brush.

t. 3

chs.
1.00 Road
2.00 S pr
flow
Ascc
40.00 Set
ins.
mark
raised
alon
80.00 Set
11 ins
sec's.
3 not
and r
alon

80.00 c

S 0°
sec

BOOK-A-201

T. 3 N. S. L. M.

Chs.
1.00 Road bears E and N.
2.00 Spring branch 2 chs wide flows N
Ascend
40.00 Set granite 14 x 10 x 6 ins 10 ins. in ground for 1/4 sec. cor marked 1/4 on N face and raised a stone mound alongside
80.00 Set sand stone 16 x 12 x 7 ins. 11 ins in ground for cor. to secs. 13. 18. 19 and 24 marked 3 notches on N and S edges and raised a stone mound alongside.

Land rolling and broken.
Soil 2nd rate.
Dense undergrowth on 80.00 chs.

S 0°17' W on a true line bet. secs. 19 and 24
Var. 16° 30' E

East Boundary T. 19 S.

Chs.	
10.00	Ravine with wash drains N.W.
40.00	Set sand stone 18 x 9 x 4 ins. 12 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.
51.00	Wash in hollow drains S.W.
80.00	Set sand stone 20 x 10 x 6 ins. 14 ins. in ground for cor. to sec's. 19. 24. 25 & 30 marked 4 notches on N and 2 on S edges and raised a stone mound alongside.

Land rolling.
Soil 2nd rate
Dense undergrowth on 80.00 chs.

S 0° 17' W on a true line between sec's 25 and 30
Var. 16° 30' E.
Through dense undergrowth

R 3

Chs	
21.60	Ravine
36.00	Wash
40.00	Set
72.50	Ridge
80.00	Set

BOOK-A-201

R 3 W. S. L. M.

Chs.	
21.60	Spring branch 2 lks wide in ravine trains W.
36.00	Wash in hollow drains W.
40.00	Set granite 15 X 10 X 6 ins. 10 ins in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.
72.50	Ridge bears N W
80.00	Set lime stone 16 X 12 X 7 ins. 11 ins. in ground for cor. to secs. 25, 30, 31 and 36 marked 5 notches on N and 1 on S edges and raised a mound of stone alongside.

Land rolling and broken
Soil 3rd rate.
Dense undergrowth on 80.00 chs.

S 0° 17' W on a true line bet. secs. 31 and 36.
Var. 16° 30' E.

317

East Bound. T 19 S. R. 3 W. S L. M

Chs.
40.00 Set lime stone, 7 X 10 X 8 ins. 12 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside

80.00 The cor. to Tps. 19 and 20 Rgs. 2 and 3 W.

Land rolling.

Soil 3rd rate.

Dense undergrowth on 80.00 chs.

Feb. 20th. 1854

Note. For general description see subdivision notes of the township.

U. S. Dep. Surveyor.

BOOK-A

U. S. SURVEYO

Salt Lake C

The foregoin

N bound a

Township No.

Executed by Sh

Under No. 1

day of Decem

February

amined, the necessar

the said field note

hereby approved.

BOOK-A-201

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, June 28th *188*4.

The foregoing field notes of the re *survey of the* W & N bound and survey of E bound,

Township No. 19 S *Range No.* 3 W

Executed by Shadrach M. Richardson

Under No. 123 *contract of the* 19th *day of* December *188*3, *in the month of* February *188*4, *having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

Fred Salomon

U. S. Surveyor General for Utah.

BOOK-A-201

6

REPORT: 1884

Filed 188

Examined by .....

Transcribed by E Michaelis

Compared by Allerson & Michaelis

FIELD NOTES

OF THE SURVEY & resurvey OF THE

Subdivisions

OF

Township No 19 South

Range No 3 West

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Shadrach M. Richardson

U. S. Deputy Surveyor,

Under his Contract No. 123

Dated December 19th 1883

Survey commenced February 21st 1884

Survey completed " 27th 188

BOOK-A-201

Township 19 South R. 3 West

304	305	306	307	308	309
302 6 377	5 361	4 350	3 339	2 328	1 312
376	375	360	349	338	327
301 7 374	8 359	9 348	10 337	11 326	12 313
373	372	358	347	336	325
300 18 371	17 357	16 346	15 335	14 324	13 314
370	369	356	345	334	323
299 19 368	20 355	21 344	22 333	23 322	24 315
367	366	354	343	332	321
298 30 365	29 353	28 342	27 331	26 320	25 317
364	363	352	341	330	319
296 31 362	32 351	33 340	34 329	35 318	36 316

Subdivisions T 19 S R. 3 W. S L M.

chs. Survey commenced. Feb. 2/84

Before commencing this survey I test my instrument by an observation on the star Polaris and an observation for latitude and find it to be in perfect adjustment.

This survey is executed with a Burts improved Solar Compass.

From the corner to sec's. 35 and 36 on the S boundary of the Tp. which is a sand stone firmly set in the ground marked with 1 notch on E and 5 on W edges with mound of stone alongside, I run north between sec's. 35 and 36.

Var. 16° 30' E.

Through dense sage brush.

40.00 Set limestone 17 X 12 X 7 ins. 12 ins. in ground for 1/4 Sec. cor. B. marked 1/4 on W face and raised a

Subdivisions T 19 S

chs. stone mound alongside
80.00 Set lime stone 14 x 10 x 7 ins.
10 ins. in ground for cor. to
sec's. 25, 26, 35 & 36 marked
1 notch on E and S edges
and raised a stone mound
alongside
Land rolling
Soil 2nd and 3rd rate
Dense undergrowth on 80.00

East on a random line bet
sec's. 25 and 36.
Var. 16° 30' E.
40.00 Set temp. ¼ sec. cor.
79.50 Intersect East boundary of Tp
20 lks N of cor. to sec's. 25 and
36, from which I run
N 89° 51' W on a true line
bet. sec's 25 and 36.
Var. 16° 30' E.
Through dense sage brush
9.00 Wash in hollow drains N W

R 3

chs.
39.90 Set
12 in
mon
rais
alon
61.75 Ca
66.50 Roo
68.00 As
79.80 The

79.8

No

Thr
12.00 Sec
13.50 Roo
26.00 Was
40.00 Se
10 in
Cor.
raised
63.00 Was

R. 3 W. S. L. M.

chs.
39.90 Set limestone 18X16X10 ins. 12 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.
61.75 Cairon drains N.
66.50 Road bears N and S.
68.00 Ascend.
79.80 The cor. to sec's. 25, 26, 35 & 36.
Land rolling & broken.
Soil 2nd & 4th rate.
Dense undergrowth on 79.80 chs.

North bet. sec's. 25 & 26.
Var. 16° 30' E.
Through dense sage brush.
12.00 Descend
13.50 Road bears N. W. & S. E.
26.00 Wash in ravine drains N W.
40.00 Set sand stone 16 X 10 X 7 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.
63.00 Wash in ravine drains N W

Subdivisions T 19 S

Chs.
76.00 Wash in canon drains W.
80.00 Set sandstone 18 X 12 X 8 ins.
12 ins. in ground for cor. to
sec's. 23, 24, 25 & 26 marked
1 notch on E and 2 on S
edges and raised a stone
mound alongside.
Land rolling and broken
Soil 4th rate.
Cause undergrowth on 80.00 ch

East on a random line
bet. sec's. 24 and 25.
Var. 16° 30' E.
40.00 Set temp. 1/4 sec. cor.
80.10 Intersect E bound of Tp.
15 lks N of cor to sec's. 24 &
25 from which I run
N 89° 54' W on a true line
bet. sec's. 24 and 25
Var. 16° 30' E.
4.50 Ridge bears N and S. descend
33.50 Foot of Mt. bears N E & S W.
38.00 Wash in hollow drains S W.

BOOK-A

R 3

Chs.
40.05 Set
11 ins.
mark
raised
80.10 The
and
S
D

Nor

Throu
oak
40.00 Set
13 ins
cor.
and
alon
80.00 Set
11 ins
sec's.
note

R. 3 W. S. L. M.

chs.
40.05 Set lime stone 16 X 12 X 7 ins. 11 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.
80.10 The corner to sec's 23. 24. 25 and 26.

Land rolling and broken.
Soil 2nd & 3rd rate.
Dense undergrowth on 80.10 chs.

North bet. sec's. 23 and 24
Var. 16° 30' E.

Through dense artemesia and oak undergrowth.
40.00 Set sandstone 19 X 8 X 6 ins. 13 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.
80.00 Set lime stone 16 X 13 X 5 ins. 11 ins. in ground for cor. to sec's. 13. 14. 23 & 24 marked 1 notch on E and 3 on S

Subdivisions T 19 S

Chs. edges and raised a stone mound alongside.
Land rolling.
Soil 3rd rate.
Dense undergrowth on
8000 chs.

East on a random line bet. sec's. 13 and 24
Var. 16° 30' E.

40.00 Set temp. 1/4 sec. cor.
80.15 Intersect E bound. of Tp. 21 Rs N of cor. to sec's. 13 and 24 from which I run N. 89° 51' W on a true line bet. sec's. 13 and 24
Var. 16° 30' E.
5.00 Wash in hollow drains N.
40.07 Set limestone 30 X 12 X 7 ins. 20 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

R 3 T

Chs.
55.00 Was
74.50 "
80.15 The
Lan
Soil
Dens
80.1

N

Throu
19.00 Was
40.00 Set
13 ins
cor.
raise
68.00 Ros
70.00 Was
76.50 Was
80.00 Set
13 ins
sec's.
notch

R 3 W. S L. M.

chs.	
55.00	Wash in Ravine drains N.
74.50	" " " " N W.
80.15	The cor. to secs. 13. 14. 23 & 24
	Land rolling & broken
	Soil 3rd rate.
	Dense undergrowth on
	80.15 chs.

North bet. secs. 13 and 14
Var. 16° 30' E.

Through dense sage brush

19.00	Wash in hollow drains N.W
40.00	Set lime stone 17 X 10 X 8 ins.
	13 ins. in ground for 1/4 sec.
	cor. marked 1/4 on W face and
	raised a stone mound alongside.
68.00	Road bears E and S W.
70.00	Wash in cañon drains W.
76.50	Wash in hollow " S W.
80.00	Set lime stone 19 X 15 X 4 ins.
	13 ins. in ground for cor. to
	secs. 11. 12. 13 & 14 marked 1
	notch on E and 4 on S edges

Subdivisions T 19 S

Chs. and raised a stone mound alongside

Land rolling and broken

Soil 4 th rate.

Dense undergrowth on

80.00 chs.

East on a random line bet. secs. 12 and 13

Var. 16° 30' E.

40.00 Set temp. 1/4 sec. cor.

79.90 Intersect E bound. of Tp. 10 lks S of cor. to secs. 12 and 13 from which I run S 89° 56' on a true line bet. secs. 12 and 13

Var. 16° 30' E.

39.45 Set sand stone 15X11X7 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

77.00 Wash in hollow drains S N.

R 3 W. S L M.

chs.
79.90 The cor. to sec's. 11, 12, 13 and 14
Land rolling.
Soil 4 th. rate.
Dense undergrowth on
79.90 chs.

North bet. sec's. 11 and 12
Var. 16° 30' E.
Throug dense arlemesia and
oak undergrowth.
40.00 Set lime stone 15 X 10 X 6 ins.
10 ins. in ground for 1/4 sec.
cor. marked 1/4 on N face
and raised a stone mound
alongside.
60.00 Ravine drains N W.
80.00 Set lime stone 15 X 10 X 7 ins.
10 ins. in ground for cor. to
sec's. 1. 2. 11 & 12 marked 1
notch on East and 5 on S
edges and raised a stone
mound alongside.
Land rolling

Subdivisions T 19 S

chs. Soil 4 th rate
Dense undergrowth on
80.00 chs.

East on a random line
bet. secs. 1 and 12
Var. 16° 30' E.

40.00 Set temp. 1/4 Sec. cor.
80.20 Intersect E bound. of Tp.
30 lks N of cor. to secs.
1 and 12 from which I
run N 89°47' W on a true
line bet. secs. 1 and 12
Var. 16° 30' E.
35.00 Descend.
40.10 Set sand stone 16X12X7 ins.
11 ins. in ground for 1/4 sec.
cor. marked 1/4 on N face and
raised a stone mound
alongside.
69.00 Wash in hollow drains N W.
80.20 The cor. to secs. 1. 2. 11 & 12.
Land rolling

BOOK-A-201

L. 3 W. S. L. M.

Chs. Soil 3rd rate.
Dense undergrowth on
80.20 Chs.

Feb. 21/84.

North on a random line
bet. sec's 1 and 2
Var. 16° 30' E.

40.00 Set temp. 1/4 sec. cor.
79.90 Intersect N boundary of Tp.
at cor. to sec's 1 and 2
from which I run S on
a true line bet. secs.
1 and 2
Var. 16° 30' E.

39.90 Set limestone 18 X 12 X 6 ins.
12 ins. in ground for 1/4 sec.
cor. marked 1/4 on W face
and raised a stone mound
alongside.

50.00 Wash in hollow trains N W.

79.90 The cor. to sec's. 1. 2. 11 & 12.
Land rolling.
Soil 3rd rate.
Dense undergrowth on 79.90 chs.

BOOK-A-2

Subdivisions T 19 S

Chs. From the cor. to secs. 34 and 35 on the S bound of the township which is a sandstone firmly set in the ground and properly marked I run north bet. secs. 34 and 35.

Var. 16° 30' E.

Through dense undergrowth

19.50 Wash in ravine drains S.W.

39.00 Ridge bears E and W.

40.00 Set lime stone 15 x 9 x 4 ins. 10 ins. in ground for 1/4 sec. cor marked 1/4 on W face and raised a stone mound alongside.

73.00 Wash in Cañon drains N.W.

80.00 Set lime stone 20 x 14 x 10 ins. 14 ins. in ground for cor. to secs. 26, 27, 34 & 35 marked 2 notches on E and 1 on S edges and raised a stone mound alongside.

Land mountainous.

R 3

chs. Soil
Dense
Mou

East
secs. 2

40.00 Set
80.15 Interse
N of
from
on a
with
17.00 S bra
in co
18.00 Road
40.07 Set
10 ins
cor. m
raised
along
65.00 Ridg
80.15 The

R 3 W. S L. M.

chs. Soil 4th rate.
Dense undergrowth on 8.00 chs.
Mountainous on 8.00 chs.

East on a random line bet. sec's. 26 and 35
Var. 16°30' E.

40.00 Set temp. 1/4 sec. cor.
80.15 Intersect N and S line 20 lks N of cor. to sec's 25, 26, 35 & 36 from which I run N 89°51' W on a true line bet. sec's 26 & 35 with same Var.
17.00 Spring branch 3 lks wide in canon drains N
18.00 Road bears N.
40.07 Set lime stone 14 x 12 x 6 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.
65.00 Ridge bears N.W. & S.E.
80.15 The cor. to sec's 26, 27, 34 & 35

Subdivisions T 19 S

chs. Land mountainous.
Soil 4th rate.
Mountainous on 80.15 chs.
Dense undergrowth on 80.50

North bet. secs. 26 and 27
Var. 16° 30' E.
Through sage and oak under growth.

23.00 Ridge bears N.W. & S.E.

40.00 Set line stone 16x10x8 ins. 11 ins in ground for ¼ sec. cor. marked 4 on N face and raised a stone mound alongside.

14.50 Road bears E and W.

80.00 Set flint stone 16x12x7 ins. 11 ins in ground for cor. to secs. 22, 23, 26 & 27 marked 2 notches on E and S edges and raised a stone mound alongside.

Land rolling and mountainous
Soil 3rd rate.
Dense undergrowth on 80.00 chs.

R. 3 W. S. L. M.

cho. East on a random line bet. sec's. 23 and 26

Var. 16° 30' E.

40.00 Set temp. ¼ sec. cor.

80.18 Intersect N and S line 30 lks N of cor. to sec's. 23, 24, 25 & 26 from which I run N 89° 47' W on a true line bet. sec's. 23 & 26 west same Var.

40.09 Set sand stone 17 x 10 x 7 ins. 12 ins. in ground for ¼ sec. cor. marked ¼ on N face and raised a stone mound alongside.

50.00 Road bears N. W. & S. E. in hollow.

52.00 Wash in hollow drains N. W.

80.18 The cor. to sec's. 22, 23, 26 & 27

Land rolling.

Soil 3rd rate.

Dense sage and oak brush undergrowth on 80.18 chs.

Subdivisions T 19 S

Chs.	
	North et. sec's. 22 and 23. Var. 16° 30' E.
	Through dense sage and oak undergrowth.
5.00	Road in cañon drains N.
35.00	Ridge bears E and W.
40.00	Set lime stone 14 x 8 x 6 ins. 10 ins in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.
50.00	Wash in cañon drains W.
80.00	Set. lime stone 15 x 12 x 7 ins. 10 ins. in ground for cor. to sec's. 14. 15. 22 & 23 marked 2 notches on E and 3 on S edges and raised a stone mound alongside.
	Land broken and mountainous.
	Soil 3rd and 4th rate.
	Mountainous on 80.00 chs.
	Dense undergrowth on 80.00 chs.

R 3 W. S L M.

Chs. East on a random line
bet. sec's. 14 and 23.
Var. 16° 30' E.

40.00 Set Temp. 1/4 sec. cor.

79.85 Intersect N and S line 10 lks
N of cor. to sec's. 13. 14. 23 & 24
from which I run N 89° 56' W
on a true line bet. sec's 14 & 23.
Var. 16° 30' E.
Through dense undergrowth.

11.00 Ridge bears N. W.

39.92 Set lime stone 17 x 9 x 6 ins.
12 ins. in ground for 1/4 sec.
cor. marked 1/4 on N face and
raised a stone mound
alongside.

57.00 Wash in hollow drains N.

79.85 The cor. to sec's. 14. 15. 22. & 23
Land mountainous.
Soil 3rd rate.
Mountainous on 79.85 chs.
Dense undergrowth on 79.85 chs.

Subdivisions T 19 S

Chs. North on a true line bet. secs. 14 and 15
Var. 16°30' E.
Throug dense sage brush
31.00 Road bears S.W. & N.E.
35.00 Wash in cañon trains S.W.
40.00 Set lime stone 15 x 10 x 6 ins. 10 ins. in ground for ¼ sec. cor. marked ¼ on N face and raised a stone mound alongside.
55.00 Enter cedars.
80.00 Set lime stone 30 x 10 x 7 ins. 23 ins in ground for cor. to secs. 10, 11, 14 & 15 marked 2 notches on E and 4 on S edge and raised a stone mound alongside.
Land rolling & broken
Soil 3rd rate.
Scattering timber on 25.00
Dense undergrowth on 80.00 ch
Feb. 22/84

BOOK-A-201

R. 3 W. S. L. M.

chs. East on a random line bet. secs. 11 and 14
Var. 16° 30' E.

40.00 Set temp. 1/4 sec. cor.

79.80 Intersect N and S line 16 lks N of cor. to secs. 11. 12. 13 & 14 from which I run N 89° 53' W on a true line bet. secs. 11 and 14 with same Var. Through dense undergrowth.

39.90 Set lime stone 19 x 14 x 7 ins. 13 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound along side.

60.00 Enter cedars.

70.50 Ridge bears N. E. & S. W.

79.80 The cor. to secs. 10. 11. 14 & 15

Land rolling mountains.

Soil 3rd rate.

Scattering timber on 19.80 chs.

Dense undergrowth on 79.80 chs.

Subdivision 7 19 S

Chs. North bet. secs. 10 and 11
Var. 16° 30' E.

Through scattering cedars and dense undergrowth.

4.00 Wash in Canon drains S. N.

29.00 Leave cedars.

40.00 Set flint stone 16 x 7 x 6 ins. 11 ins. in ground for 1/4 sec. cor. marked 4 on N face and raised a stone mound alongside.

48.00 Ridge bears E and W.

71.00 Head of ravine drains N.

80.00 Set lime stone 30 x 10 x 5 ins. 22 ins. in ground for cor. to secs. 2. 3. 10 & 11 marked 2 notches on E and 5 on S edges and raised a stone mound alongside.

Land mountainous.

Soil 3rd rate.

Scattering timber on 2400 chs.

Mountainous on 8000 chs.

Dense under growth on 8000 chs.

Chs Eas
be

40.00 Set

79.80 Inter
S of
from
on a
n
Thro

14.25 Trail
Cano

32.50 Ri

39.90 Set
14 in
cor.
and
along

51.00 Rid

79.80 The
L
S
N
De

R 3 W S L M.

chs.	East on a random line bet. sec's. 2 and 11 Var. 16° 30' E.
40.00	Set temp. 1/4 sec. cor.
79.80	Intersect N and S line 20 lk. D of cor. to sec's. 1, 2, 11 & 12 from which I run S 89° 51' W on a true line bet. sec's. 2 & 11 with same Var.
	Throug sage and oak undergrowth.
14.25	Trail in cañon bears N.
	Canon drains N.
32.50	Ridge bears N. W.
39.90	Set lime stone 20 x 12 x 8 ins. 14 ins. in ground for 1/4 sec. cor. marked 1/4 on N face. and raised a stone mound alongside.
51.00	Ridge bears S & N.
79.80	The cor. to sec's. 2, 3, 10 & 11
	Land mountainous.
	Soil 3rd rate.
	Mountainous on 79.8. chs.
	Dense undergrowth on 79.80 chs.

Subdivisions T 19 S.

chs.	North on a random line bet. secs. 2 and 3
	Var. 16° 30' E.
40.00	Set temp. 1/4 sec. cor.
79.85	Intersect N boundary of Tp. at cor. to secs. 2 and 3 previously reset by me, from which I run S on a true line bet. secs. 2 and 3. with same Var.
35.00	Wash in canon drains N.W.
39.85	Set lime stone 14X10X6 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.
45.00	Ridge trends N.W. & S.E.
79.85	The cor. to secs. 2.3.10 & 11.
	Land mountainous.
	Soil 4th rate.
	Dense undergrowth on 79.85 chs.

R. 3 W. S. L. M.

chs.	From the cor. to sec's. 33 & 34 on the S boundary of the Tp. which is a sandstone firmly set in the ground and properly marked I run N on a true line bet. sec's. 33 & 34
	Var. 16° 30' E.
	Through dense sage and oak undergrowth.
7.50	Ravine drains W.
22.50	Ridge bears E and W.
38.00	Ravine with wash drains W.
40.00	Set flint stone 20 x 12 x 4 ins. 14 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.
48.00	Ridge bears E and W.
71.00	Wash in ravine drains W.
80.00	Set lime stone 16 x 10 x 6 ins. 11 ins. in ground for cor. to sec's. 27, 28, 33 & 34 marked 3 notches on E and 1 on S edges. and raised a stone mound alongside
	Land mountainous.

Subdivisions T 19 S

Chs. Soil 3 rd. rate.
Mountainous on 8000 chs.
Dense undergrowth on 8000

East on a random line
bet. sec's. 27 and 34
Var. 16°30' E.

40.00 Set temp. 1/4 sec. cor.
80.25 Intersect N and S line at cor
to sec's. 26. 27. 34 & 35 from
which I run West on a true li
bet. sec's 27 and 34 with same Var
Through dense undergrowth.
1.00 Wash in ravine drains N. W.
31.50 Ridge bears N W & S.E.
40.12 Set lime stone 18 X 7 X 4 ins.
12 ins. in ground for 1/4 sec. cor.
marked 1/4 on N face and raised
stone mound alongside.
80.25 The cor. to sec's 27. 28, 33 & 34.
Land broken & mountainous.
Soil 3 rd rate.
Dense undergrowth on 8 0.25 ch

R 3

Chs. Nor
Throu
40.00 Set
10 ins.
mark
raised
48.50 Wash
74.00 Road
80.00 Set
ins. 1
cor.
mark
2 on
stone
La
S
De
oak

R 3 W. S. L. M.

Chs. North bet. sec's 27 and 28.
Var. 16° 30' E.
Through dense undergrowth.
40.00 Set lime stone 15 X 10 X 7 ins.
10 ins. in ground for 1/4 sec. cor.
marked 1/4 on N face and
raised a stone mound alongside.
48.50 Wash in ravine drains W.
74.00 Road bears E and S. W.
80.00 Set blue lime stone 16 X 10 X 7
ins. 11 ins. in ground for
cor. to sec's. 21. 22. 27 & 28
marked 3 notches on E and
2 on S edges and raised a
stone mound alongside.
Land rolling and broken.
Soil 3rd and 4th rate
Dense artemesia and
oak undergrowth on 80.00 chs.

Subdivisions T 19 S

Chs. East on a random line bet. sec's. 22 and 27.
Var. 16° 30' E.

40.00 Set temp. 1/4 sec. cor.

80.16 Intersect N and S line 14 lks S of cor. to sec's. 22. 23. 26 & 27 from which I run S 89° 54 on a true line bet. sec's. 22 & 27 with same Var.

32.80 Creek 7 lks wide 5 ins. deep. flows N W.

40.08 Set sand stone 14 X 10 X 6 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

80.16 The cor. to sec's. 21. 22. 27 & 28

Land rolling.

Soil 3rd rate.

Dense undergrowth on 80.16 chs.

BOOK-A-201

L. 3 W. S. L. M.

Chs. North bet. secs. 21 and 22
Var. 16° 30' E.
Through dense sage brush.
5.50 Wild Goose Cr. 5 lks wide 6 ins.
deep. flows S. W.
13.00 Road bears S W & N. E.
35.00 " " " "
40.00 Set lime stone 14 x 12 x 6 ins.
10 ins. in ground for 1/4 sec.
cor. marked 1/4 on W face and
raised a stone mound alongside.
80.00 Set sand stone 15 x 13 x 6 ins.
10 ins. in ground for cor. to
secs. 15, 16, 21 & 22 marked
3 notches on E and S edges
and raised a stone mound
alongside.
Land rolling.
Soil 3rd rate.
Dense undergrowth on
80.00 chs.

Subdivisions T. 19 S.

Chs. East on a random line bet. sec's. 15 and 22
Var. 16° 30' E.

40.00 Set temp. 1/4 sec. cor.

80.05 Intersect N and S line 13 ch's N of of cor. to sec's. 14. 15. 22 & 23 from which I run N 89° 54' W on a true line bet. sec's. 15 & 22 with same Var.

32.00 Road bears N E & S W.

40.02 Set lime stone 14x10x8 ins. 10 ins. in ground for 1/4 sec. cor. marked '40 on N face and raised a stone mound alongside

57.00 Road bears N W. & S E.

72.00 Wash drains N W.

80.05 The cor. to sec's. 15. 16. 21 & 22
Land rolling.
Soil 2 nd and 4 th rate
Dense undergrowth on 80.05 ch
From cor. David R. Stevens field bears S 61° E.
Feb. 23/84

R.

Chs. Nor
Throu
2.00 Was
16.75 Roa
22.00 En
22.75 Was
40.00 Set
in gr
1/4 on
mou
E. 15 l
No o
80.00 Set
10 ins.
sec's.
notch
and r
A ce
30 in
15 B.
No

R. 3 W. S. L. M.

ch. North bet. sec's. 15 and 16.
Var. 16° 30' E.
Through dense sage brush.
2.00 Wash drains N.
16.75 Road bears N W & S E.
22.00 Enter cedars.
22.75 Wash drains N.
40.00 Set lime stone 14 X 12 X 7 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.
A cedar 17 ins. diam. bears. - E. 15 lks dist. marked 1/4 S.B.T.
No other tree within limits.
80.00 Set sand stone 14 X 10 X 7 ins. 10 ins. in ground for cor. to sec's. 9. 10. 15 & 16 marked 3 notches on E and 4 on S edges and raised a stone mound alongside.
A cedar 16 ins. diam. bears S 70° E 30 lks dist. marked T 4 S. R 3 W S 15 B.T.
No other tree within limits.
Land rolling

Subdivision T 9 S

Chs. Soil 3rd. rate
Scattering timber on 58.00 chs
Dense undergrowth on 8.00 chs

East on a random line bet
secs 10 and 15
Var. 16° 30' E.

40.00 Set temp. 1/4 sec. cor.
80.10 Intersect N and S line at cor
to secs. 10. 11. 14 & 15 from which
I run West on a true line betw
10 and 15, with same Var.
Through timber and undergrow
2.00 Wash in ravine drains S N
16.00 Leave Cedars.
40.05 Set lime stone 18 X 15 X 6 ins. 12 ins
in ground for 1/4 sec. cor. marked
1/4 on N face and raised a
stone mound alongside.
A cedar 18 ins. diam. bears S
20° W 25 lks dist marked 1/4 S B. T
No other tree within limits.
80.10 The cor. to secs. 9. 10. 15 & 16

R. 3 W. S. L. M.

Chs. Land rolling.
Soil 3rd rate.
Scattering timber on 16.00 chs.
Dense undergrowth on 80.10 chs.

North bet. secs. 9 and 10
Var. 16°30' E.

13.50 Trail bears N. E. & S. W.
34.00 Leave cedars.
40.00 Set lime stone 14 x 10 x 6 ins.
10 ins. in ground for 1/4 sec. cor.
marked 1/4 on W face and raised
a stone mound alongside.
72.00 Ridge bears E & W.
80.00 Set lime stone 14 x 10 x 6 ins.
10 ins. in ground for cor. to secs.
3, 4, 9 and 10 marked 3 notches
on E and 5 on S edges and raised
a stone mound alongside.
Land rolling.
Soil 3rd rate.
Scattering timber on 34.00 chs.
Dense undergrowth on 80.00 chs.

Subdivisions T 19 S

Chs.	
	East on a random line bet. secs. 3 and 10
	Var. 16° 30' E.
40.00	Set temp. 1/4 sec. cor.
79.60	Intersect N and S line 16 chs. N of cor. to secs. 2 3. 10 & 11 from which I run N 89° 53' W on a true line bet. secs. 3 and 10 with same Var.
35.50	Wash in hollow trains N. W.
39.80	Set sand stone 14 x 10 x 6 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside
75.00	Wash in hollow trains N. W.
77.60	The cor. to secs. 3. 4. 9 and 10
	Land rolling
	Soil 3rd rate.
	Timber scattering.
	Dense undergrowth on 79.60 chs.

R

Chs.	
	Nor bet
40.00	Set
80.14	Inte 17 ch from on a
	Thro unde
6.50	Road line
15.50	Road
40.14	Set 11 ins mon a sto
77.1	Was
80.11	The

BOOK-A-201 250

R 3 W. S L. M.

	chs.	North on a random line bet. sec's. 3 and 4 Var. 16° 30' E.
	40.00	Set temp. 1/4 sec. cor.
	80.14	Intersect N bound of Tp. 17 lks E of cor to sec's. 3 & 4 from which I run S 0° 7' E on a true line with same Var.
		Throug dense sage and oak undergrowth.
	6.50	Road and Deseret telegraph line bears S W & N.E.
	15.50	Road bears E and W.
	40.14	Set lime stone 16 x 12 x 7 ins. 11 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.
	77.1	Wash in hollow drains W.
	80.11	The cor to sec's. 3. 4. 9 & 10.

Land rolling.
Soil 2nd rate.
Dense undergrowth on 80.14 chs.

Subdivisions T 19 S

Chs. From the corner to secs. 32 & 33 on the S bound. of the Tp. which is a blue limestone firmly set in the ground and properly marked with mound of stone alongside I run N bet. secs 32 and 33

Var. 16° 30' E.

Through dense sage and juniper brush.

4.00 Enter cedars.

40.00 Set lime stone 16 X 12 X 7 ins. 11 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised stone mound alongside

A cedar 7 ins. diam. bears S 5° W 50 lks dist. marked 1/4 S.B.T.

No other tree within limits

48.50 Road bears W.

60.00 Leave cedars.

80.00 Set lime stone 14 X 10 X 6 ins. 10 ins. in ground for cor. to secs 28. 29. 32 & 33 marked 4 notch on E and 1 on S edges and

BOOK-A-201

R 3 W. S. L. M.

Chs. raised a stone mound alongside.
Land rolling.
Soil 3rd rate.
Scattering timber on 56.00 chs.
Dense undergrowth on 80.00 chs.

East on a random line bet. sec's. 28 and 33.
Var. 16° 30' E.

40.00 Set temp. 1/4 sec. cor.

80.00 Intersect N & S line at cor. to sec's. 27, 28, 33 & 34 from which I run W on a true line with some Var.

40.00 Set line stone 14 X 10 X 7 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

80.00 The cor. to sec's. 28, 29, 32 & 33
Land rolling.
Soil 3rd rate.
Dense undergrowth on 80.00 chs.

Subdivisions T 19 S

Chs.	
	North bet. sec's. 28 and 29. Var. 16° 30' E.
	Through dense sage brush.
39.50	Road bears N.E. & S.W.
40.00	Set lime stone 14 X 10 X 6 ins. 10 ins. in ground for 1/4 sec. cor. marked 40 on W face and raised a stone mound alongside
78.80	Water ditch 4 ft. wide 7 ins. deep. flows S.W.
79.25	Road bears N E and S W.
80.00	Set sand stone 18 X 10 X 6 ins. 12 ins in ground for cor. to sec's 20. 21. 28 & 29 marked 4 notches on E and 2 on S edges and raised a stone mound alongside.
	Land rolling.
	Soil 3rd and 4th rate
	Dense undergrowth on 80.00 chs.

Chs.	
	E bet
40.00	S
80.04	I
	N o
	fro
	on a
	Thr
	bru
40.02	S
	14
	ma
	ra
78.75	Wat
79.00	R
80.04	Th
	L
	S
	D
	u

1884

R 3 W S L M.

Chs.	East on a random line bet. sec's. 21 and 28. Var. 16° 30' E.
40.00	Set imp. 1/4 sec. cor.
80.04	Intersect N and S line 19 Chs N of cor. to sec's. 21, 22, 27 & 28 from which I run N 89° 52' W on a true line with same Var. Through dense sage and oak brush.
40.02	Set sand stone 20 x 10 x 6 ins. 14 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.
78.75	Water Ditch 4 lks. wide flows S.W.
79.00	Road bears N E and S. W.
80.04	The cor. to sec's. 20, 21, 28 & 29
	Land rolling.
	Soil 3rd and 4th rate.
	Dense oak and sage brush undergrowth on 80.04 chs.
	Feb. 24/84

Subdivisions T 19 S

Chs. North bet. secs. 20 and 21
Var 16° 30' E
Through dense sage brush.
12.00 Wash drains W.
40.00 Set sand stone 14 X 10 x 7 ins.
10 ins. in ground for 4 sec cor
marked 4 on W face and raised
a stone mound alongside.
54.00 Wash drains W.
80.00 Set sand stone 16 X 12 x 7 ins.
11 ins. in ground for cor. to
secs 16. 17. 20 & 21 marked 4
notches on E and 3 on S sides
and raised a stone mound
alongside.
Land nearly level.
Soil 3rd rate.
Dense undergrowth
on 8000 chs.

R 3 W. S. L. M.

Chs. East on a random line bet. sec's. 16 and 21.
Var. 16° 30' E.

40.00 Set temp. 1/4 sec. cor.

80.12 Intersect N and S line at cor. to sec's 15. 16. 21 and 22 from which I run W on a true line with same Var.

40.06 Set granite 17 X 14 X 6 ins. 11 ins. in ground for 1/4 sec. cor marked 1/4 on N face and raised a stone mound alongside.

80.12 The corner to sec's. 16. 17 20 and 21.

Land rolling.
Soil 3rd and 4th rate.
Dense undergrowth on 80.12 chs.

Subdivisions T. 19 S.

Chs.	
	North bet. sec's. 16 and 17
	Var. 16° 30' E.
	Through dense sage and oak brush undergrowth
8.00	Enter thin scattering cedars.
30.00	Leave cedars.
40.00	Set sand stone 15 X 10 X 7 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside
41.00	Wash drains W.
51.00	Road bears E and W.
64.50	Wash drains W.
80.00	Set granite 16 X 12 X 8 ins. 11 ins. in ground for corner to sec's. 8. 9. 16 & 17 marked 4 notches on E and 4 on S edges and raised a stone mound alongside
	Land rolling.
	Soil 3rd & 4th rate.
	Scattering timber on 22 wsch
	Dense undergrowth on

80.00 chs.

BOOK-A-2

R

Chs.	
	Eas
	sec's
40.00	Set
80.80	Inter
	N of
	from
	on a
	Thro
10.00	Leav
	N E
20.00	Hold
40.40	Set
	ins
	mark
	raise
	along
68.75	Roa
80.80	The
	L
	S
	S
	De

BOOK-A-201

R 3 W. S. L. M.

Chs. East on a random line bet. secs. 9 and 16

Var. 16° 30' E.

40.00 Set temp. 1/4 sec. cor.

80.80 Intersect N and S line 27 lks N of cor. to secs. 9. 10. 15 & 16 from which I run N 89° 48' W on a true line with some Var. Through cedars and undergrowth.

10.00 Leave cedars. Road bears N E and S. W.

20.00 Hollow drains S. W.

40.40 Set lime stone 14 X 10 X 6 ins. 10 ins in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

68.75 Road bears N W & S E.

80.80 The cor. to secs. 8. 9. 16 & 17

Land rolling.

Soil 3rd rate.

Scattering timber on 10.00 chs.

Dense undergrowth on 80.80 chs.

Subdivisions T 19 S

chs.	
	North bet. secs. 8 and 9
	Var. 16° 30' E.
	Through dense oak and sage undergrowth.
27.00	Road varo N. E. and S. W.
40.00	Set lime stone 14 x 9 x 6 ins. 10 in. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.
60.25	Road and Deseret telegraph line bear N E and S W.
71.00	Wash drains S W.
80.00	Set sand stone 13 x 10 x 8 ins. 10 ins. in ground for cor. to secs. 4. 5. 8 and 9 marked 4 on E and 5 on S edges. and raised a stone mound alongside
	Land rolling.
	Soil 2nd rate.
	Dense undergrowth on 80.00 chs.

BOOK-A

chs.	
	Ec
	be
40.00	Set
80.40	Int
	cor.
	whe
	line
	sar
40.20	Se
	10 in
	ma
	rais
	alo
61.00	Ro
	bear
64.80	Wa
80.40	The

BOOK-A-201

R 3 W. S. L. M.

Chs. East on a random line bet. secs. 4 and 9
Var. 16° 30' E.

40.00 Set temp. ¼ sec. cor.

80.40 Intersect N and S line at cor. to secs. 3. 4. 9 and 10 from which I run West on a true line bet. secs. 4 an 9 with same Var.

40.20 Set sand stone 15 x 13 x 6 ins. 10 ins. in ground for ¼ sec. cor. marked ¼ on N face and raised a stone mound alongside.

61.00 Road and telegraph line bear N E and S W.

64.80 Wash drains S W.

80.40 The cor. to secs. 4. 5. 8 and 9

Land rolling.
Soil 3rd and 4th rate.
Dense sage and oak brush undergrowth on 80. 40 chs.

Subdivisions T 19 S

Chs. North on a random line bet. sec's. 4 and 5.
Var. 16° 30' E.

40.00 Set temp. 1/4 sec. cor.

79.30 Intersect N boundary line 35 Chs W of cor. to sec's. 4 and 5 from which I run S 0° 15' W on a true line bet. sec's 4 & 5 with same Var.
Through dense undergrowth.

39.30 Set lime stone 16 X 12 X 3 ins. 11 ins. in ground for 1/4 sec. cor. marked 4 on W face and raised a stone mound alongside.

72.30 Wash in hollow drains S. W.

76.50 Road bears N E and N W.

79.30 The cor. to sec's. 4. 5. 8 & 9.
Land rolling.
Soil 3rd rate.
Dense artemesia undergrowth on 79.30 chs.

Feb. 25/84.

R. 3 W. S. L. M.

Chs. From the cor. to sec's. 31 & 32 on the S boundary of the Tp. which is a blue lime stone firmly set in the ground and properly marked I run North on a true line bet. sec's. 31 and 32

Var. 16° 30' E.

Through dense sage and oak undergrowth.

10.00 Hill bears E and W.

40.00 Set lime stone 14 X 10 X 6 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.

80.00 Set flint stone 15 X 10 X 6 ins 10 ins. in ground for cor. to sec's. 29. 30. 31 and 32 marked 5 notches on E and 1 on S edges and raised a stone mound alongside.

Land rolling.

Soil 3rd rate.

Dense undergrowth on 80.00 chs.

Subdivisions T 19 S

Chs. East on a random line
bet. secs. 29 and 32
Var. 16° 30' E.

40.00 Set temp. 1/4 sec. cor.

80.08 Intersect N and S line at cor.
to secs. 28. 29. 32 & 33 from
which I run West on a true
line bet. secs. 29 and 32
with same Var.
Through dense oak and sage
undergrowth.

40.04 Set flint stone 17 X 12 X 3 ins.
11 ins. in ground for 1/4 sec.
cor. marked 1/4 on N face and
raised a stone mound
alongside.

80.08 The corner to secs. 29. 30
31 & 32

Land rolling.
Soil 3rd and 4th rate
Dense undergrowth on
80.08 Chs.

R 3 W. S.L.M.

Chs.	West on a random line bet. sec's. 30 and 31 Var. 16° 30' E. Through dense sage brush.
40.00	set temp. 1/4 sec. cor.
80.00	Intersect W bound. of Tp. at cor. to sec's. 30 and 31 from which I run East on a true line with same Var.
	resurvey
	Vis trace of old corner
40.00	Set lime stone 15 X 10 X 7 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside
	end of resurvey
64.00	Ridge bears N and S.
67.50	Wash drains S. W.
68.25	Road bears N.E. & S.W.
68.35	Water ditch drains S. W.
72.50	Road bears S.W. & N.E.
80.00	The cor. to sec's. 29, 30, 31 & 32
	Land rolling.
	Soil 2nd rate.
	Dense undergrowth on 80.00 chs.

Subdivision T. 19 S.

Chs. North bet. sec's. 29 and 30.
Var. 16°30' E.

Throug dense artemesia undergrow

5.50 Road bears N.E. and S.W.

12.00 Ditch 4 ft. wide 7 in. deep.
drains S.W.

12.50 Road bears S.W. & N.E.

40.00 Set line stone 14 X 10 X 8 ins.
14 ins. in ground for 1/4 sec.
cor. marked 1/4 on W face and
raised a stone mound alongsid

45.00 Ridge bears E and W.

80.00 No trace of old corner
Set stone 14 X 12 X 6 ins.
10 ins. in ground for cor. to
sec's. 19. 20. 29 & 30 marked 5
notches on E and 2 on S edges
and raised a stone mound
alongside.

Land rolling & broken.
Soil 3rd rate.
Dense artemesia under
growth on 80.00 chs.

BOOK-A-

R

Chs. Ea
bet

40.00 Set

80.10 Int
N of
from
on a
wit
Throu
brus

40.05 Set
14 in
cor.
and
alon

78.00 Des

80.10 The

80.10

BOOK-A-201

R 3 W S L M.

Chs. East on a random line bet. sec's. 20 and 29
Var. 16° 30' E.

40.00 Set temp. ¼ sec. cor.

80.10 Intersect N and S line 31 lks N of cor. to sec's. 20. 21. 28 & 29 from which I run N 89° 47' W on a true line bet. sec's. 20 & 29 with same Var.
Throug dense oak and sage brush undergrowth.

40.05 Set sand stone 20 X 14 X 6 ins. 14 ins. in ground for ¼ sec. cor. marked ¼ on N face and raised a stone mound alongside.

78.00 Descend

80.10 The cor. to sec's. 19. 20. 29 & 30.
Land rolling.
Soil 3rd rate.
Dense undergrowth on 80.10 chs.

367

Subdivisions T 19 S

Chs. West on a random resurvey line bet. secs. 19 and 30
Var. 16° 30' E.

— 40.00 " " set.
temp. 1/4 sec. cor.

80.00 Intersect N bound of Tp. 10 chs N of cor. to secs. 19 & 30 previously reestablished by me from which I run N 89° 55' E on a true resurvey line bet. secs. 19 and 30 with some Var.

— 40.00 No trace of old cor. Set sand stone 14 x 12 x 7 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

60.00 Ridge bears N and S.

80.00 The corner to secs. 19. 20. 29 & 30. End of resurvey.
Land rolling and broken.
Soil 3rd rate.
Dense undergrowth on 80.00 chs.

BOOK-A-

R 3

Chs. No

Thro

30.00 Ro

32.00 Wa
No b

40.00 " Set
" 12 i
cor.
raise
Erec

55.00 " O

80.00 Set
10 ins
17. 1
note
and
along
A c
S 11
R 3
N

Dens

BOOK-A-201

R 3 W. S. L. M.

Chs. North on resurvey bet. secs. 19 and 20.
Var. 16° 30' E.
Through dense artemisia undergrowth.
30.00 Road bears E and W.
32.00 Wash drains W.
40.00 No trace of old corner on resurvey
Set sand stone 16 X 11 X 7 ins.
" 12 ins. in ground for 1/4 sec.
cor. marked 1/4 on W face and
raises a stone mound alongside.
50.00 End of resurvey
Cedars.
" 80.00 Set sand stone 14 X 12 X 7 ins.
10 ins. in ground for cor. to secs.
17. 18. 19 and 20 marked 5
notches on E and 3 on S edges
and raised a stone mound
alongside.
A cedar 12 ins. diam. bears
S 41° W 11 lks dist. marked T 19 S
R 3 W S. 19 B T.
No other tree within limits.
Land rolling.
Soil 3rd rate.
Scattering cedars on 25 chs.
Dense undergrowth on 80.00 chs.

Subdivision T 19 S

Chs. East on a random line bet. sec's. 17 and 20

Var. 16°30' E.

40.00 Set temp. 1/4 sec. cor.

80.06 Intersect N and S line 21 chs N of cor. to sec's. 16.17.20 & 21 from which I run N 89°51' W on a true line bet. sec's 17 & 20 with same Var.

Through dense sage brush.

40.03 Set sand stone 14 X 12 X 6 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

44.00 En - timber.

80.06 The c - to sec's. 17.18.19 & 20

Land rolling.

Soil 3rd rate.

Cedars on 36.06 chs.

Dense undergrowth on 80.06 chs.

Feb. 26/84.

R 3

Chs. We

sec's

40.00

1/4 se

80.00 Int

at

whi

true

18 an

Thro

18.50 Roa

30.50 Was

40.00 Set

14 ins

cor.

and

along

43.00 Was

46.50 Deser

47.10 Road

47.50 Ent

52.25 Roa

80.00 The

R 3 W. S L. M.

Chs. West on a random line bet. sec's. 18 and 19

Var. 16° 30' E.

40.00 set temp. -

¼ sec. cor.

80.00 Intersect W bound. of Tp. at cor. to sec's. 18 and 19 from which I run East on a true resurvey line bet sec's. 18 and 19 with some Var. Through dense undergrowth.

18.50 Road bears N. E. and S. W.

30.50 Wash in hollow drains S. W.

40.00 Notched old corner Dig solid stone 20 X 18 X 10 ins. 14 ins. in ground for ¼ sec. cor. marked ¼ on N face and raised a stone mound alongside. End of resurvey.

43.00 Wash drains S. W.

46.50 Deseret telegraph line bears N. E. & S. W.

47.10 Road bears N. E. and S. W.

47.50 Enter cedars.

52.25 Road bears N. E. and S. W.

80.00 The cor. to sec's. 17. 18. 19 & 20.

Subdivisions T19S

chs. Land rolling.
Soil 2nd and 3rd rate.
Timber on 32.50 chs.
Dense undergrowth on 80.00 chs.

North bet. secs. 17 and 18
Var. 16° 30' E.
Through undergrowth and scattering cedars.

3.00 Leave timber.

25.50 Road bears N.E. and S.W.

38.00 Deseret telegraph line bears N.E. and S.W.

40.00 Set lime stone 15 X 10 X 6 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.

64.00 Road bears N.E. and S.W.

65.00 Wash drains S.W.

80.00 Set sand stone 14 X 9 X 6 ins. 10 ins. in ground for cor. to secs. 7, 8, 17 & 18 marked 5 notches on E and 4 on S edges and raised a stone mound alongside.

R 3 W. S. L. M.

chs. Land rolling.
Soil 3rd rate.
Timber on 3 chs.
Dense undergrowth on 8.00 chs.

East on a random line
bet. sec's. 8 and 17
Var. 16° 30' E.

40.00 I t temp. 1/4 sec. cor.
82.18 Intersect N & S line 31 chs N of cor. to sec's. 8. 9. 16 & 17 from which I run N 89° 47' W on a true line bet. sec's. 8 & 17 with same Var.
Through dense undergrowth.
27.00 Road bears N. E and S. W.
40.09 Set sand stone 19 X 14 X 6 ins. 13 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.
46.50 Road bears N. E. and S. W.
47.00 Deseret telegraph line

Subdivisions T 19 S

Chs.	
	bears N E and S W.
67.50	Wash in hollow drains S W.
80.18	The cor. to sec's. 7. 8. 17 & 18
	Land rolling.
	Soil 3rd and 4th rate.
	Dense undergrowth on 80.18 chs

West on a random line bet. sec's. 7 and 18

Var. 16° 30' E.

40.00	Set temp. 1/4 sec. cor.
80.10	Intersect W bound. of Tp. 10 l'ks N of cor. to sec's. 7 & 8 from which I run N 89° 56' E on a true line with same Var.
	Through dense undergrowth.
6.00	Ravine drains S E.
12.00	Ridge bears N and S.
40.10	Set sand stone 18 x 10 x 7 ins. 13 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

R

Chs.	
80.10	The
	on

No

	Thr
	un
40.00	Set
	in
	1/4 on
	a ce
	ma
	with
50.00	Was
75.00	Ri
80.00	S t
	in
	8 m
	edge
	alon

R 3 W. S. L. M.

chs.
80.10 The cor. to sec's. 7. 8. 17 and 18
Land rolling.
Soil 3rd rate.
Dense undergrowth
on 80.10 chs.

North bet. sec's. 7 and 8
Var. 16° 30' E.
Throughsage and oak brush
undergrowth.

40.00 Set sand stone 18 x 14 x 12 ins. 12 ins.
in ground for 1/4 sec. cor. marked
1/4 on W face & raised a stone mound alongside.
A cedar 7 ins. diam. bears E 15 lks. dist.
marked 1/4 S. B. T. No other tree
within limits.

50.00 Wash in ravine drains S. W.

75.00 Ridge bears S. W. & N. E.

80.00 Set lime stone 18 x 14 x 12 ins. 12 ins.
in ground for cor. to sec's. 5. 6. 7 &
8 marked 5 notches on E and S
edges and raised a stone mound
alongside.

Subdivisions T 19 S

Chs. Land rolling.
Soil 3rd and 4th rate.
Timber scattering.
Dense undergrowth on 8000 ch

East on a random line bet. sec's. 5 and 8
Var. 16° 30' E.

40.00 Set temp. 1/4 sec. cor.

80.12 Intersect N and S line 17 lks N of cor. to sec's. 4. 5. 8 & 9 from which I run N 89° 53' W on a true line, with same Var. Through dense sage brush.

14.00 Wash drains S. W.

20.00 Ascend.

40.06 Set line stone 15 X 12 X 7 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

80.12 The cor. to sec's. 5. 6. 7 & 8.
Land ascending west.
Soil 3rd rate.
Dense undergrowth on 80.12 ch

R. 3

Chs. We
be

40.00 Set
80.00 Inte
10 lks
from
a bu
with
Throu
Asce

40.00 Set
10 ins
cor.
raised

49.50 Ridg
80.00 The
Le
S
M
De

BOOK-A-201

R. 3 W. S.L.M.

Chs. West on a random line
bet. secs. 6 and 7
Var. 16° 30' E.

40.00 Set temp. 1/4 sec. cor.

80.00 Intersect W bound. of township.
10 lks N of cor. to secs. 6 and 7,
from which I run N 89° 56' E on
a true line bet. secs. 6 and 7
with same Var.
Through artemesia undergrowth.
Ascend.

40.00 Set sand stone 14 X 10 X 8 ins.
10 ins. in ground for 1/4 sec.
cor. marked 1/4 on N face and
raised a stone mound alongside.

49.50 Ridge bears N and S. descend.

80.00 The cor. to secs. 5. 6. 7 & 8.
Land mountainous.
Soil 4 th rate.
Mountainous on 80.00 chs.
Dense undergrowth on 80.00 chs.

Subdivisions T 19 S

Chs. North on a random line bet. sec's 5 and 6
Var. 16° 30' E.

40.00 Set temp. 1/4 sec. cor.

80.05 Intersect N bound. of Tp. at cor. to sec's. 5 and 6. from which I run S on a true line with same Var. Through dense sage brush and scattering cedars.

22.00 Road bears N W and S. E.

40.05 Set sand stone 14 X 8 X 6 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.

80.05 The cor. to sec's. 5. 6. 7 and 8.
Land rolling.
Soil 2nd and 3rd rate.
Timber scattering.
Dense undergrowth on 80.05 chs.

Feb. 27/84.

BOOK-A-201

R 3 W. S. L. M.

General Description.

The applicant for the survey of this township is David R. Stevens. His improvements are situated is sec. 22. They consist of a field under cultivation, a house, barn, corral, fencing and ditching.

There is a spring in the NE quarter of sec. 22 and one in the NE quarter of sec. 27 called "Wild Goose Spring".

The eastern and north-western portions of this Tp. are mountainous and broken, affording however good range for stock.

The central and south western portions are comparatively level. The land when irrigated can be used for agricultural purposes.

U. S. Dep. Surveyor.

BOOK-A-201

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, June 28th 1884

The foregoing field notes of the survey reservoy of the Subdivisions

Township No. 19 S *Range No.* 3 W

Executed by Shadrach M Richardson

Under No. 123 *contract of the* 19 th *day of* December 1883, *in the month of* February 1884, *having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

Fred Salomon

U. S. Surveyor General for Utah.

BOOK-A-201 379

REPORT: 1884

Filed 188

Examined by .....

Transcribed by Henry R M Atkinson

Compared by Atkinson & Michaelis

FIELD NOTES

OF THE re SURVEY OF THE

East boundary and survey of the West and North boundaries

OF

Township No 35 South

Range No 7 West

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Shadrach M. Richardson.

U. S. Deputy Surveyor,

Under his Contract No. 123.

Dated December 19th. 1883.

Survey commenced March 17th 1884

Survey completed " 19th 1884.

BOOK-A-201 379-A

Resurvey East Bound T35S R7W.

Chs. Note. Having retraced the east boundary of this Tp. I find a number of the corners destroyed, therefore consider it necessary to resurvey this line as I must close the subdivisions upon it.

Survey commenced March 17/84.

From the standard corner to Tp. 35 S. Rgs 6 and 7 W which is a granite firmly set in the ground and properly marked with stone mound alongside. I run North on a true resurvey line bet sec's. 31 and 36

Var. 15° 30' E

Through timber.

8.00 Ridge bears E and W.

15.00 Ravine drains W.

40.00 Find old cor. a granite, firmly set in the ground and properly marked with bearing trees standing.

Resurvey East Bound. T 35 S

chs.
76.00 Ridge bears S. E.
80.00 Find old cor. standing, a volcanic rock firmly set in the ground and properly marked with bearing trees standing.

Land mountainous.
Soil 2nd rate.
Mountainous on 80.00 chs.
Heavily timbered on 80.00 ch

North on a true resurvey line bet. secs. 25 and 30
Var. 15° 30' E.
Through pine timber.
30.00 Ravine drains S W.
31.00 Ridge bears S W and N. E.
40.00 Old stone thrown down, reset same a granite 18 x 16 x 14 ins. 12 ins. in ground for 1/4 sec. cor. marked 1/4 on W face. Old bearing trees standing.

R 7

chs.
48.00 Ro
62.50 H
64.50 R
80.00 N
gr
in
19.
4
dg
no
bea
wi

N
lin

Thr
5.00 Pa

R 7 W. S. L. M.

chs.	
48.00	Road bears N E and S W.
62.50	Hollow drains N. E.
64.50	Ridge bears N E and S W.
80.00	No trace of old cor. set granite 16 x 10 x 6 ins. 11 ins. in ground for cor. to secs. 19. 24. 25 and 30 marked 4 notches on N and 2 on S edges and raised a stone mound alongside. Three bearing trees standing, agree with description.

No other tree within limits.
Land mountainous.
Is 3rd rate.
Heavily timbered on 80.00 chs.
Mountainous on 80.00 chs.

North on a true resurvey line bet. secs. 19 and 24
Var. 15° 30' E.
Through pine timber

5.00	Pangnitch Cr. 16 lks wide runs E

Resurvey East Bound T35S

Chs.	
35.00	Road in hollow bears E and W.
40.00	Old cor. thrown down, result same, a granite 15 X 14 X 9 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound along side.
	An aspen 6 ins. diam. bears N 30° E 17 lks dist.
	An aspen 5 ins. diam. bears N 10° W 23 lks dist, each marked 1/4 S.B.T.
44.00	Ridge bears E and W.
50.50	Leave timber enter meadow fence bears E and W.
55.00	Creek 4 lks wide runs E.
58.00	" 15 " " " "
72.00	Leave meadow, enter field fence bears E and W.
78.80	Leave field, fence bears E and W. Enter undergrowth.
80.00	No trace of old corner set sandstone 14 X 10 X 8 ins. 10 ins in ground for cor to secs. 13, 18, 19 and 24 marked

R 7 W S L M.

	Ch.	3 notches on N and S edges and raised a stone mound alongside.
		Land level and mountainous Soil 1st and 3rd rate.
		Mountainous on 50.50 chs
		Heavily timbered on 30.50 chs.
		Dense undergrowth on 1.20 chs.
		Augmented on 51.70 chs.
		North on a true reservey line bet. sec's. 13 and 18
		Var. 15°30' E.
		Through dense undergrowth.
	34.50	Ridge bears E and W.
	40.00	No trace of old cor. set sandstone 16 x 9 x 8 ins. 11 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.
	59.00	Ravine drains S E.
	65.00	Ridge bears S E and N W.
	80.00	No trace of old cor. set

Resurvey East Bound. T35S

Chs sandstone 14X10x6 ins 10 ins. in ground for cor. to sec's. 7, 12, 13 & 18 marked 2 notches on N and 4 on S edges and raised a stone mound alongside.
Land rolling mountain.
S 1st rate.
Dense undergrowth on 80.00 ch

North on a true resurvey line bet. secs. 7 and 12
Var. 15° 30' E.

10.00 Wash in hollow drains S E.

40.00 No trace of old cor. set sandstone 14 X 10 X 6 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.

70.00 Ridge bears S E and N. W.

80.00 Old cor. thrown down. reset same a sand stone 18 X 10 X 10 ins 12 ins. in ground for cor. to

R 7 W. S. L. M.

chs secs. 1. 6. 7 and 12 marked 1 notch on N and 5 on S edges and raised a stone mound alongside.

Land rolling bench
Soil 1st rate.
Grass along line.
Dense undergrowth on 80.00 chs.

North on a true resurvey line bet. secs. 1 and 6.
Var. 15° 30' E.
Through dense undergrowth.

20.00 Road bears S E & N W.

20.50 Spring branch 6 lks wide runs S E.

40.00 No trace of old cor. set granite 16 x 10 x 7 ins. 11 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raisld a stone mound along side.

Resurvey E Bound. T35S R 7 W.

Chs.
80.00 Old corner thrown down. reset some a granite 15x10x10 ins. 10 ins. in ground for cor. to Tps. 34 and 35 S. Rgs. 6 and 7 W. marked 6 notches on each edge and raised a stone mound alongside.

Land rolling.

Soil 2nd rate.

Dense undergrowth on 80.00 chs.

March 17/84

Note. For general description see subdivision notes of this Township.

BOOK-A-201

West Boundary T35 S. R 7 W. S.L.M.

Chs. Note.

The N.W. cor. of T35 S R 7 W and S E cor. of T34 S R 8 W being about 1 mile apart as is shown by the connection made of the 7th. S Stand. Par. S, therefore I run the west bound. on a true line.

From the S Stand. cor. to Tp. 35 S. Rgs. 7 and 8 W which is a volcanic rock firmly set in the ground and properly marked with 3 bearing trees standing I run north on a true line bet. sec's. 31 and 36.

Var. 15° 30' E.

Through pine and fir timber and undergrowth.

26.00 Spring branch 4 lks wide drains N.E.

27.50 Spring branch 3 lks wide drains N.E.

40.00 Set volcanic stone 15 X 10 X 7 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.

West Boundary T 35 S

chs.	a quakingasp 8 ins. diam. bears E 17 lks dist.
	a quakingasp 9 ins. diam. bears S 52° E 18 lks dist. each marked 1/4 S.B.T.
44.75	Road bears S. E. & N. W.
49.25	Creek in cañon 7 lks wide flows S.E.
55.50	Road bears S E and N W. Ascend.
80.00	Set volcanic stone 18 X 10 X 6 ins 12 ins in ground for cor. to secs. 25. 30. 31 and 36 marked 5 notches on N and 1 on S edges and raised a stone mound alongside.
	a red cedar 20 ins. diam bears S 65° W 13 lks dist.
	a cedar 15 ins. diam. bears N 13° E 26 lks dist. each marked with the proper Tp. Rg & Sec.
	Land mountainous.
	Soil 1st and 4th rate.
	Heavily timbered on 80.00 chs.
	Dense undergrowth on 80.00

BOOK-A-201

R 7 W. S. L. M.

Cha North bet. sec's. 25 and 30
Var. 15° 30' E.
Through timber and undergrowth.
6.00 Mountain bears N. W. & S. E.
40.00 Set volcanic stone 15 X 8 X 6 ins.
10 ins. in ground for 1/4 sec. cor.
marked 1/4 on W face
An aspen tree 6 ins. diam.
bears N 45° E 15 lks dist
A quakingasp. 7 ins. diam.
bears S 44° W 12 lks dist,
each marked 1/4 S. B. T.
65.70 Head of ravine drains S. E.
80.00 Set volcanic stone 14 X 10 X 6
ins. 10 ins. in ground for cor. to
sec's. 19, 24, 25 and 30 marked
4 notches on N and 2 on S
edges and raised a stone
mound alongside.
Timber too small to mark.
Land mountainous.
Soil 3rd rate.
Heavily timbered and
dense undergrowth on 80.00 chs.

West Boundary T35 S

Chs.	
	North bet. secs. 19 and 24
	Var. 15° 30' E.
	Through undergrowth and
	small scrubby timber.
9.00	Ridge bears S. E. and N. W.
40.00	Set volcanic stone 16 X 10 X 6 ins.
	11 ins. in ground for 1/4 sec. cor.
	marked 1/4 on W face and raised
	a stone mound alongside.
45.75	Head of ravine drains S. E.
60.10	Ridge bears S. E. and N. W.
80.00	Set volcanic stone 24 X 15 X 6
	ins. 16 ins. in ground for cor. to
	secs. 13. 18. 19 and 24 marked 3
	notches on N and S edges and
	raised a stone mound alongside
	Timber too small to mark.
	Land mountainous
	Soil 4th rate.
	Heavily timbered will small
	scrubby timber on 80.00 chs.
	Dense undergrowth and
	mountainous on 80.00 chs.

BOOK-A-201

R 7 W. S.L.M.

Chs North bet. sec's. 13 and 18
Var. 15° 30' E.
Through timber and undergrowth.
32.50 Ridge bears N.E. and S.W.
40.00 Set volcanic stone 15 X 10 X 4 ins.
10 ins. in ground for 1/4 sec. cor.
marked 1/4 on W face and raised a
stone mound alongside.
A balsam 5 ins. diam. bears
W 7 lks dist.
A balsam 8 ins. diam. bears
S 80° E. 15 lks dist. each marked
1/4 S.B.T.
55.00 Foot of hill, enter into valley.
and meadow. Leave timber and undergrowth
80.00 Set volcanic stone 14 X 11 X 6 ins.
10 ins. in ground for cor. to sec's.
7, 12, 13 & 18 marked 2 notches on
N and 4 on S edges and raised a
stone mound alongside.
Timber too small to mark.
Land level and mountainous.
Soil 1st and 4th rate.
Mountainous on 55.00 chs.
Dense undergrowth on 55.00 chs.

West Boundary T35 S

chs. From cor. a house bears N 15° 30' E about 15 chs. Corral bears N 8° E, of hou

North bet. sec's. 7 and 12
Var. 15° 30' E.

Through meadow.

25.00 Ascend, leave meadow enter undergrowth.

34.00 Ridge bears E and W. descend

40.00 Foot of hill set volcanic stone 16 X 10 X 5 ins. 11 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.

A pond bears S 45° E. 10 chs. dis

80.00 Set volcanic stone 18 X 12 X 8 ins 12 ins. in ground for cor. to sec's. 1. 6. 7 & 12 marked 1 notch on N and 5 on S edges and raised a stone mound alongside.

Land level and rolling.
Soil 1st and 3rd rate.

R 7

chs. De
a

No

Thr
8.00 E
13.50 S
flo
22.00 As
35.00 Ri
40.00 Set
ins
cor.
A
bear
C
bear
1/4 S
52.50 Ho
80.00 A
at
T3

R. 7 W. S. L. M.

chs. Dense undergrowth on 35.00 chs.
A house bears N 47° E

North bet secs. 1 and 6
Var. 15° 30' E.
Through undergrowth
8.00 Enter timber.
13.50 Spring branch 3 lks wide flows E.
22.00 Ascend.
35.00 Ridge bears N E and S. W.
40.00 Set volcanic stone 14 X 12 X 6 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on W face,
A balsam 12 ins. diam. bears E 20 lks dist.
A quakingasp 10 ins. diam. bears W 15 lks each marked 1/4 S. B. T.
52.50 Hollow drains S. E.
80.00 A quakingasp bre 8 ins. diam at cor. marked
T 34 S S 31 on N. E.

N. Bound. T35S R7W. S.L.M.

T35S. S1 on SW.
R7W S6 on SE
R8W S36 on NW and raised a stone mound alongside.

Land rolling.
Soil 2nd rate.
Scattering timber on 72.00 chs.
Dense undergrowth on 8.00 chs.
March 18/84.

Note:
For general description see subdivision notes of this township.

North

Chs. Fr
35 S
reset
a ra
Tp's.
and
4000

I fi
5 mi
follu
Nori
The
line
and
F
34 an
previo
N
line l

Throu
timbe
22.00 Leave

S.L.M. North Bound. T35S. R7W.

nd

72.00 ch.
8000 ch

iption
of

Chs. From the cor. to Tps. 34 & 35 S. Rgs. 6 and 7 W, previously reset by me I run West on a random line bet. said Tps. setting temp. half mile and mile corners at each 4000 and 8000 chs.

Var. 15° 30' E.

I find the dist to be 5 miles 79.90 chs and the falling to be 2.80 chs North.

The course for the true line will therefore be N 89° 40' E. and the correction 46⅔ lks S

From the cor. to Tps. 34 and 35 S. Rgs. 7 and 8 W previously set by me I run N 89° 40' E on a true line bet. secs. 6 and 31

Var. 15° 30' E.

Through undergrowth and timber.

22.00 Leave timber.

North Boundary T 35 S

Chs.	
39.90	Set volcanic stone 24 x 9 x 7 ins. 16 ins. in ground for 1/4 sec cor. marked 1/4 on N face and raised a stone mound alongside. Enter timber.
	A balsam 11 ins. diam. bears N 89° W 8 lks dist. marked 1/4 S.
	No other tree within limits.
40.90	Road bears N and S.
48.75	Ridge bears N. W. and S. E.
74.80	Ravine drains S. E.
79.90	Set volcanic stone 15 x 12 x 4 ins. 10 ins. in ground for cor to secs. 5. 6. 31 & 32 marked 5 notches on E and 1 on W edges and raised a stone mound alongside.
	A quakingasp tree 10 ins. diam. bears S 10° W 25 lks dist.
	A quakingasp 12 ins. diam. bears N 60° W 50 lks dist.
	each marked with the proper Tp. Rg. and Sec.
	No other tree within limits

R 7

Chs.	
	2
	C
	T
	De
	N
	sec
	Th
8.50	Rid
20.50	Rai
39.00	Rai
40.00	Set
	ins.
	1/4 se
	N fo
	of st
50.00	Rid
61.00	Rai
80.00	Set
	13 in
	sec's.
	notch

R 7 W. S. L. M.

Chs. Land rolling.
Soil 2nd rate.
Timber on 62.00 chs.
Dense undergrowth on 79.90 chs.

N 89° 40' E on a true line bet. sec's. 5 and 32.
Var. 15° 30' E.
Through timber and undergrowth.

8.50 Ridge bears S. leave timber.
20.50 Ravine drains. S.
39.00 Ravine drains S. E.
40.00 Set volcanic stone 18 x 10 x 6 ins. 12 ins. in the ground for 1/4 sec. cor. marked 1/4 on N face and raised a mound of stone alongside.
50.00 Ridge bears S. E. and N. W.
61.00 Ravine drains S. E.
80.00 Set volcanic stone 19 x 9 x 7 ins. 13 ins. in ground for cor. to sec's. 4. 5. 32 & 33 marked 4 notches on E and 2 on W edge

North Boundary T 35 S

Chs. and raised a stone mound alongside.

Land mountainous.

Soil 4 th rate.

Timber on 8.50 chs.

Dense undergrowth on 80.00 chs.

N 89° 40' E on a true line bet. sec's. 4 and 33.

Var. 15° 30' E.

Through dense undergrowth.

35.00 Ravine drains N E. enter timber

40.00 Set volcanic stone 16 x 12 x 7 ins. 11 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

A balsam 10 ins. diam. bears N 5° W 15 lks. dist. marked 1/4 S B T

No other tree within limits.

53.00 Leave timber.

80.00 Set volcanic stone 15 x 10 x 6 ins.

R 7 W. S L. M.

Chs. 10 ins. in ground for cor. to secs. 3. 4. 33 & 34 marked 3 notches on E and W edges and raised a stone mound alongside.

Land rolling.
Soil 1st and 3rd rate.
Grass along line.
Timber on 18.00 chs.
Dense undergrowth on 80.00 chs.

N 89°40' E on a true line bet. secs. 3 and 34
Var 15° 30' E.
Through undergrowth.

40.00 Set a quartzite 18 x 10 x 4 ins. 12 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

72.00 Road in hollow bears N W & S E.

80.00 Set a volcanic rock 34 x 15 x 6 ins 10 ins. in ground for cor. to

North Boundary T35 S

Chs. secs. 2, 3, 34 and 35 marked 2 notches on E and 4 on W edges and raised a stone mound alongside.

Land rolling.

Soil 1st rate.

Timber scattering.

Dense undergrowth on 80.00 ch.

N 89°40' E on a true line bet. secs. 2 and 35

Var. 15°30' E.

Through undergrowth.

3.50 Ridge bears N and S.

28.50 Dodds Cr. 10 lks wide flow S.

40.00 Set a conglomerate stone 18 X 12 X 8 ins. 12 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

42.50 Branch of Dodds Cr. 5 lks wide flows S.W.

60.00 Ridge bears S and N.

BOOK-A

R

ch.

70.00 Ho

80.00 S

8 in

cor

1 n

edge

n

S

D

80

N

t

Thr

35.00 Sp

40.00 Se

4 in

1/4 se

face

mo

63.30 Ro

BOOK-A-201

R 7 W. S L. M.

chs.
70.00 Hollow trains S.
80.00 Set a volcanic stone 20x12x 8 ins. 14 ins. in ground for cor. to sec's. 1. 2. 35 & 36 marked 1 notch on E and 5 on W edges and raised a stone mound alongside.

Land rolling.
Soil 1st rate.
Dense undergrowth on 80.00 chs.

N 89° 40' E on a true line bet. sec's. 1 and 36.
Var. 15° 30' E.
Through undergrowth.
35.00 Spur of ridge, bears N.
40.00 Set a volcanic stone 20x10x 4 ins. 14 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.
63.30 Road bears N W and S E. descend

402

N. Bound. T 35 S. R 7 W.

Chs.	
64.00	Creek 13 lks wide flows S E in canon.
80.00	The cor. to Tps 34 and 35 S Rgs. 6 and 7 W.

Land rolling.
Soil 1st and 4th rate.
Dense undergrowth on 80.00 chs.

March 1884.

Note.
For general description see subdivision notes of this township.

U. S. Dep. Surveyor.

BOOK

U. S. SURVEY

Salt Lak

The foreg

E. W. a

Township No.

Executed by S

Under No. 1

day of Decem

March

amined, the neces

the said field n

hereby approved.

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, June 28th 1884

The foregoing field notes of the survey resurvey *of the*

E. W and N boundaries

Township No. 35 S *Range No.* 7 W

Executed by Shadrach M. Richardson.

Under No. 123 *contract of the* 19th

day of December 1883, *in the month of*

March 1884, *having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

Fred Salomon

U. S. Surveyor General for Utah.

6.8 BOOK-A-201

REPORT: 1884

Filed 188

Examined by .....

Transcribed by Henry R M Atkinson

Compared by R Atkinson & Michaelis

FIELD NOTES

OF THE SURVEY OF THE

Subdivision and Meanders of Panguitch Lake

OF

Township No 35 South

Range No 7 West

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Shadrach M. Richardson.

U. S. Deputy Surveyor,

Under his Contract No. 12 3.

Dated December 19th 1883.

Survey commenced March 20th 1884

Survey completed March 27th 1884

V

BOOK-A-201

Township 35 South R. 7 West

395	397	398	399	400	401

393	6	466	5	449	4	438	3	427	2	415	1 385

465	464	448	437	426	414

392	7	463	8	447	9	436	10	425	11	413	12 384

462	461	446	435	424	412

391	18	460	17	445	16	434	15	422	14	411	13 383

459	458	444	433	421	409

390	19	457	20	443	21	432	22	420	23	408	24 382

456	455	442	431	419	407

389	30	454	29	441	28	430	27	418	26	406	25 381

453	452	440	429	417	405

387	31	450	32	439	33	428	34	416	35	403	36 379

BOOK-A-201

Subdivisions T 35 S. R. 7 W. S.L.M.

chs. Survey commenced. March 20/84. with a Burts improved Solar Compass.

Before commencing this survey I test my instrument by an observation on the star Polaris and find it in perfect adjustment.

From the standard cor. to sec's. 35 and 36 I run north on a true line bet. sec's. 35 and 36.

Var. 15° 45' E.

The standard cor. to sec's. 35 and 36 is a granite firmly set in the ground and properly marked, with a mound of stone alongside.

15.28 Ridge bears E and W.

25.30 Abrupt descent.

40.00 Set volcanic rock 22x10x6 ins 15 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound

Subdivisions T 35 S.

Chs. alongside.

A long leafed pine 20 ins diam bears N 70° E. 25 lks dist.

A long leafed pine 15 ins. diam bears N 73°15' W 30 lks dist. each marked 1/4 S.B.T.

64.10 Ravine drains N.E.

73.75 Canon drains E.

80.00 Set volcanic rock 18x10x8 ins 12 ins. in ground for cor. to secs. 25.26.35 & 36 marked 1 notch on E and S edges

A long leafed pine 14 ins. diam. bears N 45° W 70 lks di

A long leafed pine 30 ins. diam, bears N 38° W 70 lks dist.

An aspen 6 ins. diam. bear S 48°30' W 53 lks dist. each marked with the proper Tp. Rg and Sec.

No other tree within limits raised a stone mound alongside.

Land rolling.-

BOOK-A-201

R 7 W. S. L. M.

Chs. Soil 1st rate.
Heavily timbered on 8.00 chs.

East on a random line
bet. sec's. 25 and 36.
Var. 15° 30' E.

40.00 Set temp. 1/4 sec. cor.

80.10 Intersect E bound of Tp. at cor. to sec's. 25 and 36. from which I run W on a true line bet. sec's 25 and 36.
Var. 15° 30' E.
Through timber and undergrowth.

14.40 Rocky wash drains N.

40.05 Set sand stone 15X10X6 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside. from which
An aspen 3 ins. diam. bears N 48° 30' W marked 1/4 S.B.T.
A long leafed pine 24 ins. diam. bears S 46½ W 197 lks dist.

Subdivisions T 35 S

Chs. marked ¼ S.B.T.
66.00 Ravine drains N. E.
71.00 Ridge bears N and S.
80.10 The cor. to secs. 25. 26. 35 & 36.
Land mountainous.
Soil 1st and 3rd rate.
Heavily timbered on 80.10 chs.
Dense undergrowth on 80.10 chs.

North E. E. sec. 35 and 26.
Var. 15° 30' E.
Through scattering timber and dense undergrowth.
32.40 Panguitch Cr. 19 lks wide flows E.
37.40 Leave timber.
37.90 Ravine drains S.E. ascend.
40.00 Set volcanic rock 18 X 16 X 8 ins. 12 ins. in ground for ¼ sec. cor. marked ¼ on W face and raised a stone mound alongside.
55.50 Top of bench

R 7 W. S. L. M.

chs.
79.30 Road from Panguitch to Panguitch Lake bears E & W.

80.00 Set volcanic rock 20x14x8 ins. 14 ins. in ground for cor. to sec's. 23. 24. 25 & 26. marked 1 notch on E and 2 on S edges and raised a stone mound alongside.

Land rolling.
Soil 2nd and 4th rate.
Timber on 37.40 chs.
Dense undergrowth on 80 ch.

East on a random line bet. sec's. 24 and 25.
Var. 15° 30' E.

40.00 Set temp. 1/4 sec. cor.

80.13 Intersect E bound. of Tp. 70 lks S of cor. to sec's. 24 & 25 from which I run S 89° 30' W on a true line bet. sec's. 24 and 25.
Var. 15° 30' E.
with same var.

Subdivisions T35S

Chs.	
10.00	Ridge bears N and S.
17.00	Wash draws N.
26.70	Panguitch cr. 14 wide draws N
29.00	Road bears N and S.
40.07	Set sandstone 20 x 8 x 8 ins. 15 ins. in ground for 1/4 sec cor. marked 1/4 on N face and raised a stone mound alongside.
58.80	Ridge bears NW and SE
80.15	The corner to sec's. 23. 24. 25 26.

Land rolling mountains.
Soil 2nd rate.
Dense sage and mountain rush undergrowth on 80.15 chs.

North bet. sec's. 23 and 24
Var. 15°30' E.
Through dense undergrowth.

18.20	Bench bears S.E. & N.W.
32.30	Leave bench, descend.

BOOK

R.

Chs.	
40.00	S
	14
	co
	ra
	al
50.50	R
56.00	R
62.00	
75.70	R
80.00	S
	30
	for
	m
	on
	sto
	8 o
	E
	b

R. 7 W. S. L. M.

Chs.	
40.00	Set sandstone 20 X 14 X 14 ins 14 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.
50.50	Ravine drains E.
56.00	Ridge bears E and W.
62.00	Ravine drains E.
75.70	Ridge bears E and W.
80.00	Set volcanic rock 30 X 18 X 12 ins. 12 ins. in ground for cor. to sec's. 13. 14. 23 & 24 marked 1 notch on E and 3 on S edges and raised a stone mound alongside.

Land mountainous.
Soil 3rd and 4th rate.
Dense undergrowth on 80.00 chs.

East on a random line bet. sec's. 13 and 24
Var. 15° 30' E.

Subdivisions T35 S

chs.
40.00 Set temp. 1/4 sec. cor.
80.14 Intersect E bound. of Tp.
at cor. to sec's. 13 and 24
from which I run West on
a true line bet. sec's.
13 and 24 with same Var.
Through undergrowth.
5.30 Leave undergrowth, enter
field, fence bears N W & S E.
21.90 Leave field, fence bears N and
S. enter artemesia undergrowth
39.40 Dodds Cr. 14 lks wide flows S
40.07 Set volcanic rock 18 x 12 x 7 in
12 ins. in ground for 1/4 sec. cor
marked 1/4 on N face and
raised a stone mound
alongside.
41.20 Fence bears N. W. and S. E.
41.40 Road " " "
42.00 Ascend.
80.14 The cor. to sec's. 13. 14. 23 & 24
Land level and mountainous
Soil 1st and 3rd rate.
Dense undergrowth on 80.14c

R 7 W. S. L. M.

Chs. North bet. sec's. 13 and 14
Var. 15° 30' E.
Through dense undergrowth.
22.20 Rocky ravine drains E.
35.30 Ridge bears E and W.
40.00 Set volcanic rock 18 X 12 X 10 ins. 12 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.
65.00 Ridge bears E and W.
78.50 Cr. 10 lks wide flows S. E.
80.00 Set volcanic rock 16 X 12 X 6 ins. 11 ins. in ground for cor. to sec's. 11. 12. 13 & 14. marked 1 notch on E and 4 on S edges and raised a stone mound alongside.

Land mountainous
Soil 4th rate rocky.
Dense undergrowth on
80.00 ch.

Subdivisions T 35 S

Chs. East on a random line bet. sec's. 12 and 13
Var. 15° 30' E.

40.00 Set temp. 1/4 sec. cor.

80.80 Intersect E bound. of Tp. 42 lks S of cor. to sec's. 12 and 13 from which I run S 89° 42' W on a true line bet. sec's. 12 & 13 with some Var.
Through dense undergrowth.

29.50 Ridge bears N. E. and S. W.

40.40 Set volcanic rock 14 x 12 x 8 in 10 ins in ground for 1/4 sec cor marked 1/4 on N face and raised a stone mound alongside.

44.30 Wash draws S.

46.50 Ridge bears N and S.

75.00 Descend abruptly.

79.50 Dodds Cr. 10 lks wide draws S. E.

80.80 The cor. to sec's. 11. 12. 13 & 14
Land mountainous.
Soil 2nd and 4th rate.
Dense undergrowth on 80.80 chs.

R

Chs.

.80 Do

10.10 Us

15.50 Ra

39.55 Ru

40.00 Se

ins.

sec.

and

alon

60.00 Wa

80.00 Set

ins.

to

1 m

edge

mo

La

S

De

on 8

R 7 W S L M.

		North bet. secs. 11 and 12
		Var. 15° 30' E.
		Through dense sage brush.
	.80	Dodds Cr. 10 lks wide drains S. E.
	10.10	Ascend.
	15.50	Ravine drains W.
	39.55	Ridge bears E and W.
	40.00	Set volcanic rock 30 x 14 x 12 ins. 20 ins. in ground for 1/4 sec. cor. marked 4 on W face and raised a stone mound alongside.
	60.00	Wash drains W.
	80.00	Set volcanic rock 15 x 12 x 8 ins. 10 ins. in ground for cor. to secs. 1, 2, 11 and 12 marked 1 notch on E and 3 on S edges and raised a stone mound alongside.

Land rolling and mountainous
Soil 2nd and 4th rate.
Dense artemesia undergrowth on 80.00 chs.

Subdivisions T35 S

Chs East on a random line.
bet. sec's. 1 and 12
Var. 15° 30' E.

40.00 Set temp. 1/4 sec. cor.

80.00 Intersect E bound. of Tp. at cor. to sec's. 1 and 12, from which I run West on a true line bet. sec's. 1 and 12 with same Var.
Through dense artemesia undergro

12.50 Ridge bears N and S.

18 40 Ravine drains S.

40.00 Set volcanic stone 24x24x10 ins. 18 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

41.00 Ridge bears N and S.

52.30 Ravine drains S.

62.50 Ridge bears N and S.

80.00 The cor. to sec's. 1. 2. 11 & 12
Land mountainous.
Soil 3rd rate.
Mountainous and dense undergrowth on 80.00 chs.

Chs.
40.00
80.80
40.80
67.00
80.80

BOOK-A-201 : 4151

R 7 W. S. L. M.

Chs. North on a random line bet. secs. 1 and 2.

Var. 15° 30' E.

40.00 Set temp. 1/4 sec. cor.

80.80 Intersect North bound. of Tp. 70 l/rs E of cor. to secs 1 and 2 from which I run S 0° 31' E on a true line bet. secs. 1 and 2 with same Var.

40.80 Set volcanic rock 20 X 12 X 10 ins. 14 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.

67.00 Ridge bears E and W.

80.80 The cor. to secs 1. 2. 11 & 12

Land rolling & mountainous.

Soil 2nd & 4th rate.

Dense artemesia undergrowth on 80. 80 chs.

March 20/84.

Subdivision, T 35 S

Chs. From the standard cor. to sec's. 34 and 35 which is a volcanic rock firmly set in the ground and properly marked I run north on a true line bet. sec's. 34 and 35.

Var. 15° 30' E.

Through timber and undergrowth

5.00 Ravine drains N. E.

20.00 Leave timber.

25.00 Foot of mountain bears N. E.

36.50 Road bears N. W. and S. E.

40.00 Set volcanic rock 38 X 12 X 8 in. 26 ins. in ground for 1/4 sec. c. s. marked 1/4 on N face and raised a stone mound alongside

55.00 Panguitch Cr. 30 lks wide dr. E.

60.00 Ascend.

62.25 Top of hill cours E. and N.

68.40 Road bears N. E. and S. W.

70.20 " " " "

80.00 Set volcanic rock 15 X 10 X 7 in. 10 ins. in ground for cor. to sec's 26. 27. 34 & 35 marked 2

BOOK-A-201

R 7 W. S. L. M.

Chs. notches on E and 1 on S edges and raised a stone mound alongside.

Land rolling mountains.

Soil 1st and 2nd. rate.

Timber on 200 chs.

Dense undergrowth on 80 chs.

Church's house bears S 14° E. 25.00 chs. dist.

Reynols house bears S 41° W. 25.00 chs. dist.

East on a random line bet. sec's. 26 and 35

Var. 15° 30' E.

40.00 Set temp. 1/4 sec. cor.

79.30 Intersect N and S line 50 chs S of cor. to sec's. 25, 26, 35 & 36, from which I run S 89° 38' W on a true line bet. sec's. 26 & 35, with same Var.

25.00 North end of pond.

79.65 Set volcanic stone 18 x 14 x 6 ins.

Subdivisions T 35 S.

Chs. 12 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside

46.50 Pauguitch Cr. drains N. E. 14 lks wide.

61.65 Road bears N and S.

79.30 The cor. to sec's. 26. 27. 34 & 35

Land rolling.

Soil 1 st and 4 th rate.

Dense undergrowth on 79.30 ch

North bet. sec's. 26 and 27

Var. 15° 30' E.

Through dense sage and greasewood undergrowth.

2.00 Ridge bears E and W.

37.00 Ridge " " "

40.00 Set volcanic rock 20 x 10 x 8 ins. 15 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.

50.50 Ravine drains S. E.

80.00 Set volcanic rock 20 x 10 x 8

chs ins. 15 ins. in ground for
cor. to sec's. 22. 23. 26 & 27
marked 2 notches on E and
S edges and raised a stone
mound alongside.
Land mountainous.
Soil 3rd and 4th rate.
Mountainous on 8000 chs.
Dense undergrowth on
8000 chs.

East on a random line
bet. sec's. 23 and 26.
Var. 15° 30' E.

40.00 Set temp. 1/4 sec. cor.
79.50 Intersect N and S line 45 lks
S of the cor. to sec's. 23. 24. 25
and 26, from which I run
S 89° 41' W on a true line
bet sec's. 23 and 26
with some Var.
Through dense undergrowth.
36.35 Ridge bears N and S.

Subdivisions T 35 S

chs.
39.75 Set volcanic rock 14x8x7 in
10 ins. in ground for 1/4 sec.
cor. marked 1/4 on N face
and raised a stone mound
alongside.
40.85 wash drains S.
51.40 Road bears N and S.
53.60 Ravine drains S.
79.50 The cor. to sec's. 22.23.26 x 27
Land mountainous.
Soil 2nd and 4th rate.
Mountains on 79.50 chs
Dense undergrowth on
79.50 chs.

North bet. sec's. 22 and 23.
Var. 15° 30' E.
Through dense undergrowth.
36.20 Wash drains E.
40.00 Set volcanic rock 20x18x7
15 ins. in ground for 1/4 sec.
cor. marked 1/4 on W face
and raised a stone mound

Subdivisions T 35 S

Chs. Through dense undergrowth.
2.30 Ridge bears N and S.
13.10 Ravine drains N.
39.80 Set volcanic rock 14 x 8 x 8 in
10 ins. in ground for 1/4 sec.
cor. marked 1/4 on N face
and raised a stone mound
alongside.
77.50 Wash drains S.
79.60 The cor. to sec's. 14. 15. 22 & 23
Land mountainous.
Soil 2nd and 4th rate.
Scattering timber along
line.
Dense undergrowth
on 79.60 chs.
Mountainous on 79.60 chs

North bet sec's. 14 and 15
Var. 15°30' E.
25.50 Head of brood hollow drains E.
37.50 Ridge bears N E and S W.
40.00 Set black lava stone 24 x 12 x

Chs
43.00
78.00
80.00

Subdivisions T 35 S

Chs. Through dense undergrowth.
2.30 Ridge bears N and S.
13.10 Ravine drains N.
39.80 Set volcanic rock 14 x 8 x 8 in
10 ins. in ground for 1/4 sec.
cor. marked 1/4 on N face
and raised a stone mound
alongside.
77.50 Wash drains S.
79.60 The cor. to sec's. 14. 15. 22 x 23
Land mountainous.
Soil 2nd and 4th rate.
Scattering timber along
line.
Dense undergrowth
on 79.60 chs.
Mountainous on 79.60 chs

North bet. sec's. 14 and 15
Var. 15° 30' E.
25.50 Head of brood hollow drains E.
37.50 Ridge bears N E and S W.
40.00 Set black lava stone 24 x 12 x

R 7 W. S. L. M.

Chs ins. 16 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.

A balsam 18 ins. diam. bears N 35° E 2.18 chs dist marked 1/4 S B.T.

No other tree within limits.

45.00 Enter heavy timber

78.00 Leave " "

80.00 Set red lava stone 16 X 10 X 6 ins. 11 ins. in ground for cor. to sec's. 10. 11. 14 & 15 marked 2 notches on E and 4 on S edges and raised a stone mound alongside.

An aspen 3 ins. diam. bears S 75½° E 30 lks dist.

An aspen 8 ins. diam. bears S 65° W 72 lks dist.

An aspen 3 ins. diam. bears N 82° W 3.35 chs dist. each marked with the propr. Tp. Rge. Sec.

Land rolling.

Soil 1st rate.

Heavily timbered on 33.00 chs

Dense undergrowth on 80.00 chs.

Subdivisions T35 S

Chs. East on a random line bet. sec. 11 and 14.

Var. 13° 30' E.

40.00 Set temp. 1/4 sec. cor.

79.50 Intersect N and S line 25 lks N of cor. to sec's. 11. 12. 13 & 14 from which I run N 89° 49' W on a true line bet. sec's 11 & 14 with same Var.

Through dense undergrowth.

4.00 Canon bears N

25.00 Ridge bears N and S.

39.75 Set lava stone 18 x 10 x 4 ins. 12 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound along side an aspen 5 ins. diam. bears N 77 W 68 lks dist. marked 1/4 S. B. T. No other tree within limits.

52.00 Canon drains N 70° E.

59.00 Ridge bears N and S.

65.00 Canon drains S. E.

79.50 The cor. to sec's. 10. 11. 14 & 15

Land rolling.
Soil 1st rate.
Decrease undergrowth on 79.50

R 7 W. S. L. M.

Chs North bet. sec's. 10 and 11
Var. 13° 30' E.
Through undergrowth.
13.50 Canon drains E.
40.00 Set volcanic rock 18 x 10 x 8 ins.
12 ins. in ground for 1/4 sec.
cor. marked 1/4 on N face and
raised a stonemound alongside.
Ridge bears E and N.
65.00 Dodds Cr., in canon, 20 ft.
wide 15 ins. deep flows E.
80.00 Set volcanic rock 20 x 12 x 10 ins.
14 ins. in ground for cor. to
sec's. 2. 3. 10 and 11 marked 2
notches on E and 5 on S
edges and raised a stone
mound alongside.
Land mountainous.
Soil 2nd and 4th rate.
Scattering timber on
line.
Dense undergrowth on
80.00 chs.

March 21/84

Subdivisions T 35 S

Chs. East on a random line bet. sec's. 2 and 11
Var. 15° 30' E.

40.00 Set temp ¼ sec. cor.

79.80 Intersect N and S line 10 lks N of cor. to sec's. 1. 2. 11 & 12 from which I run N 89° 56' W on a true line bet. sec's. 2 & 11 with same Var.
Through dense undergrowth.

39.90 Set volcanic rock 18 X 12 X 10 ins. 12 ins in ground for ¼ sec. cor. marked ¼ on N face and raised a stone mound alongside.

53.00 Creek 10 lks wide, in canon flows S.

79.80 The cor. to sec's. 2. 3. 10 & 11.
Land mountainous.
Soil 2nd and 4th. rate.
Dense undergrowth on 79.80 chs.

BOOK-A-201

R 7 W. S. L. M.

Chs. North on a random line bet. sec's. 2 and 3.

Var. 15° 30' E.

40.00 Set temp. 1/4 sec. cor.

80.27 Intersect N bound of Tp. at cor. to sec's 2 and 3 from which I run S on a true line bet. sec's 2 and 3, with same Var. Through dense undergrowth. Descend

20.00 Bottom of flat

40.27 Set volcanic rock 22 x 18 x 7 ins. 15 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.

53.00 Wash drains E.

76.00 Ridge bears E and W.

80.27 The cor. to sec's. 2. 3. 10 & 11

Land mountainous.

Soil 1st and 3rd rate.

Dense undergrowth on

80. 27 Chs.

Subdivisions T 35 S

Chs. From the meander cor. to fractional section 33 & 34 which is a stationary boulder properly marked with stone mound alongside I run north bet. sec's. 33 and 34
Var. 15° 30' E.
The meander cor. is 18.85 chs. N of the true corner point which falls in the lake.

24.00 Road bears N W and S E.
28.00 " " N.E. " S.W.
39.00 Ridge bears E and W.
40.00 Set lava stone 15 X 10 X 6 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.
49.50 Road bears S.E. and N.W.
59.60 Hollow drains S.E. thence S.
80.00 Which is 61.15 chs. North of meander cor. set volcanic rock 18 X 10 X 7 ins. 12 ins. in ground for cor. to sec's. 27. 28. 33 & 34 marked 3 notches on E and 1

R 7 W S.L.M.

Chs. on S edges and raised a stone mound alongside.

Land rolling.

Soil 2nd rate

Dense sage brush undergrowth on 61.15 chs.

East on a random line bet. sec's. 27 and 34

Var. 15° 30' E.

40.00 Set temp. 1/4 sec. cor.

80.00 Intersect N and S line at cor. to sec's. 26, 27, 34 and 35 from which I run west on a true line bet. sec's. 27 and 34 with some Var.

13.10 Creek 10 lks wide 14 ins. deep flows S.E.

39.50 Wash drains S E.

40.00 Set volcanic rock 14 X 10 X 6 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

71.00 Ridge bears N W & S E.

80.00 The cor. to sec's. 27, 28, 33 & 34

Subdivisions T35 S

Chs. Land rolling.
Soil 3rd rate gravel.
Dense undergrowth on 8000 chs.

North bet. secs. 27 and 28
Var. 15° 30' E.
Through dense sage brush.
2.50 Ridge bears E and N.
29.50 Road bears S.E. and N.W.
40.00 S&V Volcanic stone 18 X 13 X 10 ins.
12 ins. in ground for 1/4 sec.
cor. marked 1/4 on N face and
raised a stone mound alongside.
49.50 Hollow drains S E.
56.50 Ridge bears S E & N W.
7' 0 Creek 8 ft. wide in cañon flows S E
80. Set volcanic stone 20 X 12 X 6 ins. 14
ins. in ground for cor. to secs. 21. 22
27 and 28 marked 3 notches on E
and 2 on S edges and raised a
stone mound alongside.
Land rolling.
Soil 4th rate.
Dense undergrowth on 8000 ch

R 7 W. S. L. M.

Chs East on a random line bet. sec's. 22 and 27

Var. 15°30' E.

40.00 Set temp. 1/4 sec. cor.

80.00 Intersect N and S line 10 lks S of cor. to sec's. 22. 23. 26 & 27 from which I run S 89°36' W on a true line bet. sec's. 22 and 27 with same var.

Through dense sage brush.

9.70 Ravine drains S. E.

17.50 Ridge bears S. E. & N. W.

37.70 Ravine drains S E.

40.00 Set volcanic rock 14 x 10 x 6 ins. 10 ins in ground for 1/4 sec cor. marked 1/4 on N face and raised a stone mound alongside.

52.50 Ridge bears S. E. & N W.

78.50 Hollow drains S.

80.00 The cor. to sec's 21. 22. 27 & 28.

Land rolling.

Soil 3rd & 4th rate.

Dense undergrowth on

80.00 chs.

Subdivisions T35S

Chs. North bet. sec's. 21 and 22
Var. 15°30' E.
Through scattering timber.

7.50 Ravine drains S.E.

25.00 Ridge bears E and W.

40.00 Set volcanic stone 18X12 x 7 ins 12 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.

40.15 Nash in hollow drains S.W.

60.00 Ridge bears E and W.

70.00 Hollow drains S.E.

80.00 Set volcanic stone 16X12 x 6 ins 11 ins. in ground for cor. to sec's. 15. 16. 21 and 22 marked 3 notches on E and S edges and raised a stone mound alongside.

Land rolling.
Soil rocky. 4th rate.
Scattering timber along line
Dense undergrowth on 80.00 chs.

BOOK-A-201 433

R 7 W. S.L.M.

Chs. East on a random line bet. sec's. 15 and 22

Var. 15° 30' E.

40.00 Set temp. 1/4 sec. cor.

80.10 Intersect N and S line 10 lks S of cor. to sec's. 14. 15. 22 & 23 from which I run S 89° 56' W on a true line bet. sec's. 15 and 22 with same Var.

Through dense sage brush.

4.00 Hollow drains S E.

17.00 Ridge bears S E and N.W.

39.00 Wash in hollow drains E.

40.05 Set gray sandstone 24x10x6 ins. 16 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

67.50 Ridge bears N W and S E.

80.10 The cor. to sec's. 15. 16. 21 & 22.

Land mountainous.

Soil 2nd and 4th rate.

Dense undergrowth and mountainous on 80.10 chs.

Subdivision T35S

Chs. North bet. secs. 15 and 16
Var. 15° 30' E.
Through dense sage brush.
20.00 Ridge bears S W and N E.
31.50 Hollow drains W 5 chs. thence S.
40.00 Set volcanic rock 24 X 15 X 14 ins. 16 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.
50.00 Top of hill.
80.00 Set volcanic stone 20 X 12 X 10 ins. 13 ins. in ground for cor. to secs. 9. 10. 15 and 16 marked 3 notches on E and 4 on S edges and raised a stone mound alongside.
Land rolling.
Soil 1st and 4th rate.
Dense undergrowth on 80.00 chs.
March 22/84

BOOK-A-201

4351

R 7 W. S. L. M.

Chs. East on a random line bet. sec's. 10 and 13
Var. 15° 30' E.

40.00 Set temp. 1/4 sec. cor.

80.08 Intersect N and S line 15 lks S of cor. to sec's. 10. 11. 14 & 15 from which I run S 89° 54' W on a true line bet. sec's. 10 and 15, with same Var. Through dense undergrowth.

40.04 Set volcanic rock 16 x 10 x 8 ins. 11 ins in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

80.08 The cor. to sec's. 9. 10. 15 & 16

Land rolling.

Soil 2nd rate.

Scattering timber along line.

Dense undergrowth on 80.08 chs.

Subdivisions T 35 S

Chs. North bet. sec's. 9 and 10
Var. 15° 30' E.
Through dense undergrowth.
7.50 Hollow drains E.
35.00 Ridge bears E and W.
40.00 Set volcanic rock 14 x 8 x 6 ins. 10 ins. in ground for 1/4 sec. cor. marked "4 on W face and raised a stone mound alongside.
66.00 Wash drains E.
80.00 Set volcanic rock 18 x 16 x 14 ins. 12 ins. in ground for cor. to sec's. 3. 4. 9 and 10. marked 3 notches on E and 5 on S edges and raised a stone mound alongside.
Land rolling mountains.
Soil 3rd rate.
Dense undergrowth on 80.00 chs.

R 7 W. S. L. M.

Chs. East on a random line bet. sec's. 3 and 10
Var. 15° 30' E.

40.00 Set temp. 1/4 sec. cor.

80.00 Intersect N and S line 21 lks N of cor. to sec's. 2, 3, 10 & 11 from which I run N 89° 51' W on a true line bet. sec's. 3 & 10 with same Var.
Through dense sage brush.

11.00 Ridge bears N and S.

22.50 Trail bears S.

23.00 Wash in ravine drains S.

35.00 Ridge bears N and S.

40.00 Set volcanic rock 36 x 18 x 9 ins 27 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

80.00 The cor. to sec's. 3, 4, 9 & 10
Land rolling mountains.
Soil 2nd and 4th. rate.
Dense undergrowth on 80.00 chs.

Subdivisions T 35 N

Chs. North bet. sec's. 3 and 4 on a random line.

Var. 15° 30'

40.00 Set temp. ¼ sec. cor.

80.90 Intersect N boundary of Tp. 80 lks W of cor. to sec's 3 and 4 from which I run S 0° 34' W on a true line bet. sec's 3 & 4 with same Var.

40.90 On ridge bears E & W set volcanic rock 20 x 18 x 8 ins. 15 ins. in ground for ¼ sec. cor. marked ¼ on W face and raised a stone mound alongside.

77.50 Ridge bears E and W.

80.90 The cor. to sec's. 3. 4. 9. & 10

Land mountainous.

Soil 1st and 2nd rate.

Grass along line.

Dense undergrowth on 80.90 chs.

BOOK-A-201

R 7 W. S. L. M.

Chs. From the standard corner to sec's. 32 & 33 which is a volcanic rock firmly set in the ground and properly marked with mound of stone alongside, I run North bet. sec's 32 & 33.

Var. 15° 30' E.

10.00 Enter undergrowth.

15.00 Wood bears E & W.

22.50 Leave undergrowth enter meadow fence bears N E and S W.

Epson's house bears N 87° 15' E. 20 chs.

26.00 Leave meadow, enter undergrowth Ascend.

34.50 Top of hill fence bears S E.

40.00 Set Volcanic rock 19 x 18 x 7 ins. 14 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.

75.50 Foot of ridge.

80.00 Set volcanic stone 19 x 12 x 8 ins. 14 ins. in ground for cor. to sec's. 28. 29. 32 & 33 marked 4 notches on E and 1 on S edges

Subdivisions T 35 S

Chs and raised a stone mound alongside.
Land rolling.
Soil 1st rate
Dense undergrowth on 66.50 chs.

East on a random line bet. secs. 28 and 33.
Var. 15°30' E.

40.00 Set temp. 1/4 sec. cor.
80.10 Intersect N and S line 30 N of cor. to secs. 27, 28, 33 & 34 from which I run N 89°47' on a true line bet. secs. 28 & 33 with same Var.
Through dense undergrowth.
15.60 Hollow drains S E.
40.05 Set volcanic stone 24 x 14 x 8 in 16 ins. in ground for 1/4 sec. co marked 1/4 on N face and raised a stone mound alongside.
55.30 Road bears S E and N W.
70.00 Road " S and N E.

BOOK-A-201

R 7 W. S. L. M.

Chs.
78.50 Creek 6 lks wide, 6 ins. deep, drains E.
80.10 The cor. to secs. 28. 29. 32 & 33.
Land rolling.
Soil 3 rd. rate.
Dense undergrowth on 80.10 chs

North bet. secs. 28 and 29
Var. 15° 30' E.
36.00 Top of bluff bears S E & N. W.
40.00 Set volcanic stone 14 x 10 x 6 ins.
10 ins. in ground for 1/4 sec. cor.
marked 1/4 on W face and raised a
stone mound alongside.
68.00 Creek in Canon. 5 lks wide flows S E.
80.00 Set volcanic stone 14 x 13 x 7 ins.
10 ins. in ground for cor. to secs. 20. 21,
28 & 29. marked 4 notches on E and
2 on S edges and raised a stone
mound alongside.
A quaking asp 6 ins. diam.
bears N 70° E. 20 lks dist. marked,
T 35 S. R 7 W S 21. B.T.
Land rolling.
Soil 3 rd rate.
Dense undergrowth on 80.00 chs.

Subdivisions T 35 S

Chs.	
	East on a random line bet. secs. 21 and 28
	Var. 15° 30' E.
40.00	Set temp 1/4 sec. cor.
80.20	Intersect N and S line at cor. to secs. 21, 22, 27 and 28. from which I run west on a true line bet. secs. 21 and 28 with same Var.
11.00	Ridge bears N.W. & S.E.
40.10	Set volcanic stone 14x10x6 ins. 10 ins in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.
67.12	Ravine with Cr. 5 lks wide flows E.
74.00	Ridge bears S.E. & N.W.
80.20	The cor. to secs. 20, 21, 28 & 29

Land rolling and mountainous
Soil 4th rate.
Dense undergrowth on 80.20 chs.

BOOK-A-201

R 7 W. S. L. M.

Chs. North bet. sec's. 20 and 21
Var. 15° 30' E.

14.50 Ridge bears S.E. and N.W.

40.00 In ravine drains N E set volcanic rock 10x8x7 ins. 7 ins. in ground for 1/4 sec. cor. marked 4 on W face and raised a stone mound alongside.

45.00 Ridge bears E and W.

51.00 Ravine drains S E.

71.00 Ridge bears S E and N W.

80.00 Set volcanic rock 18x10x5 ins. 12 ins. in ground for cor. to sec's. 16. 17. 20 x 21 marked 4 notches on E and 3 on S edges and raised a stone mound alongside

Land mountainous.
Soil 4 th rate.
Mountainous on 8000 chs.
Dense undergrowth on 8000 chs.

March 24/84

Subdivisions T 35 S

Chs. East on a random line bet. secs. 16 and 21

Var. 15° 30' E.

40.00 Set temp. 1/4 sec. cor.

80.15 Intersect N and S line 10 lks W of cor. to secs. 15. 16. 21 & 22 from which I run S 89° 36' W on a true line bet. secs. 16 & 21 with same Var.

14.00 Ridge bears N and S.

22.00 Ravine drains S.

40.08 Set volcanic rock 18 x 14 x 6 ins. 12 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

44.00 Ridge bears N and S.

63.50 Ravine drains S.

80.15 The cor. to secs. 16. 17. 20 & 21

Land Mountainous.

Soil 4th rate.

Mountainous and dense undergrowth on 80.15 chs.

Chs. No

Thro

19.00 Cre

32.00 Ri

37.00 He

40.00 Set

10 in

mor

raise

51.00 Rav

65.00 Rid

80.00 Set

in gr

mark

and r

a

N

a gu

N 75

bears

mark

La

Sa

mount

80.00

BOOK-A-201 4445

R 7 W. S. L. M.

Chs. North bet. secs. 16 and 17
Var. 15° 30' E.

Through undergrowth.

19.00 Creek 4 lks wide 3 ins. deep. drs E.

32.00 Ridge bears E and W.

37.00 Head of hollow drains E.

40.00 Set volcanic rock 14 X 10 X 6 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.

51.00 Ravine drains E.

65.00 Ridge bears E and W.

80.00 Set sand stone 14 X 10 X 8 ins. 10 ins. in ground for cor. to secs. 8. 9. 16 & 17 marked 4 notches on E and S edges and raised a stone mound alongside.

A pine 4 ft. diam. bears N 20° E 30 lks dist.

A quakingasp 13 ins. diam. bears N 75° W 50 lks dist.

A quakingasp 8 ins. diam. bears S 75° E. 30 lks dist each marked with the proper Tp. Rg & Sec.

Land mountainous.

Soil 4th rate.

Mountainous & dense undergrowth on 80.00 chs.

LHG

Subdivisions T 35 S

Chs.	East on a random line bet. sec's. 9 and 16. Var. 16° 30' E.
40.00	Set temp. 1/4 sec. cor.
79.80	Intersect N and S line 10 lks N of cor. to sec's. 9. 10. 15 & 16 from which I run N 89° 56' W on a true line bet. sec's. 9 and 16 with same Var.
	Through dense undergrowth.
10.00	Ridge bears N and S.
23.00	Ravine drains S.E.
39.90	Set volcanic stone 15 x 10 x 7 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.
41.00	Ridge bears S 5° E.
72.50	Canon drains S 5° E.
79.80	The cor. to sec's. 8. 9. 16 & 17.
	Land mountainous.
	Soil 4th rate.
	Dense undergrowth on 79.80 chs.

BOOK-A-201

R 7 W. S. L. M.

Chs. North bet. sec's. 8 and 9.
Var. 15° 30' E.
Through dense artemisia undergrowth.
40.00 Set volcanic stone 15 X 10 X 4 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.
42.00 Enter timber, ascend.
70.00 Ridge bears N.
74.00 Leave timber.
75.00 Head of hollow drains N.
80.00 Set volcanic rock 18 X 12 X 6 ins. 12 ins. in ground for cor. to sec's. 4. 5. 8 and 9 marked 4 notches on E and 5 on S edges and raised a stone mound alongside.
Land rolling & mountainous.
Soil 3rd and 4th rate.
Timber on 32.00 chs.
Dense undergrowth on 80.00 chs.

Subdivisions T 35 S

Chs. East on a random line bet. sec's. 4 and 9.

Var. 15° 30' E.

40.00 Set temp. ¼ sec. cor.

80.00 Intersect N and S line 21 ½ N of cor. to sec's. 3. 4. 9 & 10 from which I run N 89° 57' W on a true line bet. sec's 4 and 9 with same Var.

Through dense undergrowth.

13.00 Hollow drains S. E.

22.00 Small ridge bears S E & N W.

40.00 Set volcanic stone 16 X 10 X 7 ins. 11 ins. in ground for ¼ sec. cor. marked ¼ on N face and raised a stone mound alongside

50.00 Ascend.

74.00 Ridge bears N and S.

80.00 The cor. to sec's. 4. 5. 8 & 9.

Land mountainous.

Soil 3rd and 4th rate.

Mountainous and dense undergrowth on 80.00 chs.

BOOK-A-201 449

R 7 W. S. L. M.

Chs. North on a random line bet. secs. 4 and 5

Var. 15° 30' E.

40.00 Set temp. 1/4 sec. cor.

80.80 Intersect N bound. of Tp. 70 S. W of cor. to secs. 4 and 5 from which I run S 0° 30' W on a true line bet. secs. 4 and 5 with same Var.

5.00 Ravine drains S.E.

10.00 Ridge bears S E and N. W.

20.00 Head of cañon drains S.E.

40.80 Set volcanic stone 16 X 10 X 8 ins. 11 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.

50.00 Ridge bears N W and S. E.

80.80 The cor. to secs. 4. 5. 8 & 9.

Land mountainous.

Soil 4th rate.

Trees Undergrowth and mountainous on 80.80 chs.

Subdivisions T 35 S

Chs. From the standard corner to sec's. 31 and 32 which is a volcanic stone firmly set in the ground and properly marked with stone mound alongside. Trav. north on sec's. 31 and 32

Var. 15°30' E.

.50 Small hollow drains E.
5.00 Ridge bears S.E. & N.W.
14.00 Corrall 75 lks wide.
16.25 Road bears N.W. and S. 2.00 chs thence S.E. Hollow drains E.
18.00 Corrall 85 lks wide of line.
18.75 House bears W. 1.00 ch. dist.
23.00 Ridge bears E. and W.
26.50 Foot of ridge.
29.26 Creek 9 lks wide 7 ins. deep in cañon flows S.E.
30.50 Ditch flows S.E.
31.00 Road bears S.E. & N.W. ascend
40.00 Set lava stone 17 x 12 x 4 ins. 12 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound

Ch.
38.00
70.00
80.00

BOOK-A-201 451

R 7 W. S. L. M.

Chs. alongside.

A pine 10 ins. diam bears S 5° W 15 lks dist, marked ¼ S B.T.

No other tree within limits

38.00 Ridge bears E and W.

70.00 Enter undergrowth.

80.00 Set volcanic stone 36 X 13 X 7 ins. 27 ins. in ground for cor. to secs 29, 30, 31 and 32 marked with 5 notches on E and 1 on S edges and raised a stone mound alongside.

A pine 14 ins. diam. bears N 33° E 50 lks dist marked T 35 S. R 7 W S 29 B.T.

No other tree within limits.

Land mount among

Soil 1st and 4th rate.

Timber scattering.

Dens Undergrowth o. 10.00 chs.

Mgh Mountains on 8 0.00 chs.

Subdivisions T 35 S

Chs. East on a random line bet. secs. 29 and 32
Var. 13° 30' E.

40.00 Set temp. 1/4 sec. cor.

79.90 Intersect N and S line 16 lks N of cor. to secs. 28, 29, 32 & 33 from which I run N 89° 53' W on a true line bet. secs. 29 & 32 with same Var.

5.00 Ascend.

31.00 Ridge bears N and S.

39.45 Set volcanic stone 24 x 14 x 7 ins. 16 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound along.

45.00 Descend.

79.90 The cor. to secs. 29, 30, 31 & 32

Land mountainous.

Soil 3rd rate.

Scattering timber along line.

Mountainous and dense undergrowth on 79.90 chs.

March 25/84

BOOK-A-201 483

R 7 W. S. L. M.

Chs. West on a random line bet. sec's. 30 and 31.

Var. 13° 30' E.

40.00 Set temp. 1/4 sec. cor.

80.00 Intersect N bound. of Tp. at cor. to sec's. 30 and 31 previously set by me, from which I run East on a true line bet. sec's 30 and 31 with some Var.

20.00 Ridge bears S.E. & N.W.

40.00 Set volcanic stone 14 x 12 x 6 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside

42.50 Creek 7 lks wide 4 ins. deep in cañon drains S.E.

45.00 Road bears N.W. & S.E.

50.00 Spring branch 3 lks wide flows S.

60.00 Ridge bears N & S.

80.00 The cor. to sec's. 29, 30, 31 & 32

Land mountainous.

Soil 4 th rate.

Mountainous and dense undergrowth on 8 0.00 chs.

454

Subdivisions T 33 S.

Chs. North bet. secs. 29 and 30.
Var. 15° 30' E.

36.00 Ridge bears N. W. and S. E.

40.00 Set volcanic stone 14 X 10 X 6 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.

47.50 Enter timber.

80.00 Set volcanic rock 13 X 13 X 8 ins. 9 ins. in ground for cor. to secs. 19. 20. 29 and 30 marked 3 notches on E and 2 on S edge and raised a stone mound alongside.

A quaking asp 6 ins. diam. bears N 70° E 20 lks dist.

A quaking asp 8 ins. diam. bears N 5° W 40 lks dist, each marked with the proper Tp. Rg & Sec.

No other tree within limits.

Land mountainous.

Soil 2nd & 4th rate.

Timber on 32.50 chs.

Mountainous and dense undergrowth on 80.00 chs.

BOOK-A-201 455

R. 7 W. S. L. M.

Chs. East on a random line bet. secs. 20 and 29.
Var. 15° 30' E.

40.00 Set temp. 1/4 sec. cor.

80.20 Intersect N and S line 40 lks N of the cor. to secs. 20. 21. 28 & 29 from which I run N 89° 43' W on a true line bet. secs. 20 and 29 with same Var.

20.00 Road in hollow bears N and S.

39.00 Ascend enter timber.

40.10 Set lava stone 18 x 12 x 7 ins. 12 ins. in ground for 1/4 sec. cor. marked 4 on N face and raised a stone mound alongside. A pine 24 ins. diam. bears N, 10 lks dist. marked 1/4 S.B.T.

43.00 Ridge bears S E & N W.

46.00 Canon with creek 7 lks wide 8 ins. deep flows S.E.

60.00 West bank of deep rocky canon.

80.20 The cor. to secs. 19. 20. 29 and 30.

Land rough and broken.
Soil 4th. rate.
Timber on 41.20 chs.
Mountainous & dense undergrowth on 80.20 chs.

4 P G

Subdivisions T35 S

Chs. West on a random line bet. sec's. 19 and 30.
Var. 13°30' E.

40.00 Set temp. 1/4 sec. cor.

79.70 Intersect N bound of Tp. 30 lks S of cor. to sec's. 19 and 30 from which I run S 89°47' E on a true line bet. sec's. 19 and 30 with same Var.

25.00 Ravine drains S.

39.70 Set a lava stone 17 x 9 x 6 ins. 12 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside a quakingasp. 6 ins. diam. bears N 45° E. 7 lks dist. marked 1/4 S 29. No other tree within limits.

48.00 Ridge bears N W & S E.

58.50 Ravine drains N W.

65.00 Ridge bears N W x S E.

79.70 The cor. to sec's. 19, 20, 29 & 30.

Land mountainous.

Soil 3rd and 4th rate.

Mountainous and dense undergrowth on 79.70 chs.

BOOK-A-201 4519

R 7 W. S. L. M.

Chs. North bet. secs. 19 and 20
Var. 15° 30' E.

22.50 Ridge bears E and W.

23.00 Ravine drains S.E.

35.00 Ridge bears S E & N.W.

40.00 Set lava stone 15 X 10 X 7 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.

48.00 Canon drains S E. ascend.

66.00 Top of bluff.

80.00 Set volcanic stone 19 X 12 X 12 ins 13 ins. in ground for cor. to secs. 17. 18. 19 & 20 marked 5 notches on E and 3 on S edges and raised a stone mound alongside.

A pine 20 ins. diam. bears S 35° W 25 lks dist. marked T35S R7W S19 B.T.

No other tree within limits.

Land mountainous.

Soil 4th rate.

Timber scattering.

Mountainous and dense undergrowth on 80.00 chs.

Subdivisions T 35 S

Chs. East on a random line bet. sec's. 17 and 20.

Var. 15° 30' E.

40.00 Set temp. 1/4 sec. cor.

79.80 Intersect N and S line at cor. to sec's. 16. 17. 20 and 21 from which I run West on a true line bet. sec's. 17 and 20 with same Var.

16.15 Ridge bears S.E. and N.W.

39.90 Set volcanic rock 15 X 10 X 4 ins 10 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside

41.00 Hollow drains S.E.

73.00 Road bears N W and S.E.

79.80 The cor. to sec's. 17. 18. 19 & 20.

Land rocky and broken

Soil 4th. rate.

Dense undergrowth on 79.80 chs.

R

Chs. We
bet

40.00 Se

79.70 In
lis
fro
on
18 a

24.00 Ro

34.00 Ri

39.70 Set
11 in
mo
rais

64.00 Ed

65.25 Cre
gorg

72.00 Al

79.70 The
S
S
N
unde

BOOK-A-201 4519

R 7 W. S. L. M.

Chs. West on a random line bet. sec's. 18 and 19
Var. 15° 30' E.

40.00 Set temp. 1/4 sec. cor.

79.70 Intersect W bound of Tp. 65 lks N of cor. to sec's 18 and 19 from which I run N 89° 32' E on a true line bet. sec's 18 and 19 with same Var.

24.00 Ravine drains S E.

34.00 Ridge bears N W and S.E.

39.70 Set volcanic stone 16 X 10 X 7 ins. 11 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

64.00 Edge of deep rocky gorge

65.25 Creek 10 lks wide 6 ins. deep in gorge drains S.E.

72.00 Bluff bears S E & N. W.

79.70 The cor. to sec's. 17. 18. 19 & 20

Land mountainous.

Soil 4th rate.

Mountainous and dense undergrowth on 79.70 chs

Subdivisions T 35 S

Chs. North bet. secs. 17 and 18
Var. 15° 30' E.

14.50 Road bears N. W. and S. E.

35.00 Ridge bears " " "

40.00 Set lava stone 14 X 14 X 8 ins.
10 ins. in ground for 1/4 sec. cor
marked 1/4 on W face and
raised a stone mound alongside
A quakingasp 5 ins. diam.
bears N 10° E 20 lks dist. marked 1/4 S B.
No other tree within limits

45.00 Hollow drains W.

65.00 Ridge bears E and W.

80.00 Set lava stone 14 X 10 X 6 ins. 10 ins
in the ground for cor. to secs.
7. 8. 17 & 18 marked 5 notches on E
and 4 on S edges and raised a
stone mound alongside.
A balsam 9 ins. diam. bears S 85° E
12 lks dist.
A balsam 7 ins. diam. bears
S 43° W 14 lks dist. each
marked with the proper Tp. & Rge.
No other tree within limits.

BOOK-A-201 1461

R 7 W. S. L. M.

Chs. Land mountainous.
Soil 3rd and 4th rate.
Scattering timber on line.
Mountainous and dense
undergrowth on 80.00 chs.

East on a random line bet.
sec's. 8 and 17.
Var. 15° 30' E.

40.00 Set temp. ¼ sec. cor.

80.60 Intersect N and S line 10 lks. N
of cor. to sec's. 8. 9. 16 and 17 from
which I run N 89° 56' W on a true
line bet. sec's. 8 & 17 with some Var.

20.00 Ridge bears N and S.

34.40 Ravine drains S.

40.30 Set volcanic stone 17 x 13 x 5 ins.
12 ins. in ground for ¼ sec. cor.
marked ¼ on N face and raised a
stone mound alongside.

80.60 The cor. to sec's. 7. 8. 17 & 18.
Land rolling and mountainous.
Soil 3rd rate.
Dense undergrowth on 80.60 chs.

Subdivisions T 35 S

Chs. West on a random line bet. secs. 7 and 18.

Var. 15° 30.

40.00 Set temp. 1/4 sec. cor.

79.85 Intersect N bound of Tp at cor. to secs. 7 and 18 from which Trees East on a true line bet. secs. 7 and 18 with some Cor.

11.00 Ridge bears N. W. & S. E.

34.50 Road bears " "

39.85 Set lava stone 14x9x4 ins. 10 in. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

Aquoking asp. 7 ins. diam. bears N 5° W 12 lks dist. marked 1/4 S B T.

45.00 Descend.

45.30 West end of pond about 3.00 chs S of line.

56.80 E end of pond, south of line.

79.85 The corner to secs. 7. 8. 17 & 18

Land level and mountainous.

Soil 1st and 4th rate.

Dense undergrowth on 79.85 ch

R 7 W. S. L. M.

Chs. North bet. secs. 7 and 8
Var. 15° 30' E.

18.00 Ravine drains W.

40.00 Set lava stone 24 x 13 x 9 ins. 6 ins. in ground for ¼ sec. cor. marked ¼ on W face and raised a stone mound alongside. A house bears S 34° W

45.00 Ridge bears E and W.

63.00 Ravine drains S. E.

78.25 Ridge bears S E and N. W.

80.00 Set lava stone 40 x 10 x 7 ins. 30 ins. in ground for cor. to secs. 5. 6. 7 and 8 marked 5 notches on E and S edges and raised a stone mound alongside

Land mountainous.

Soil 4 th rate.

Scattering timber on line

Mountainous and dense undergrowth on 80 acres

Subdivisions T35S

Chs. East on a random line bet. secs 5 and 8

Var 13°30' E

40.00 Set temp. ¼ sec. cor.

80.10 Intersect N and S line 7 lks north of cor. to secs. 4.5.8 & 9. from which I run N 89° 57' W on a true line bet. secs. 5 and 8 with same Var.

16.00 Cañon. trains NW.

40.05 Set volcanic stone 18 X 12 X 8 in 12 ins. in ground for ¼ sec. cor. marked ¼ on N face and raised a stone mound alongside.

A quaking asp. 5 ins. diam. bears N 83° W 23 lks dist. marked ¼ S

45.75 Spring branch 5 lks wide in Cañon trains S.

80.10 The cor. to secs. 5.6.7 & 8.

Land mountainous.

Soil 3rd rate.

Mountainous and dense undergrowth on 80.10 chs.

R

Chs. We bet

40.00 S.

79.80 In at c whe true with

12.00 Ha

21.00

38.00 Ro

39.80 Set o w mart a sto Spru

42.00 Ascé

50.00 T of

60.00 Rovi

79.80 The L Sa

Mount grow

BOOK-A-201

A list of the names of the individuals employed by Shadrach M. Richardson *United States deputy surveyor, to assist in running, measuring, and marking the lines and corners described in the foregoing field notes of the survey of* township and section lines in Townships 13, 14 and 19 south, range 3 west and townships 35 and 36 south, range 7 west

of the Salt Lake base and meridian in the Territory of Utah, showing the respective capacities in which they acted.

———, *Compassman.*
F. M. Gavin, *Chainman.*
J. A. Montague, *Chainman.*
P. J. Beckstrom, *Chainman.*
W. M. Lloyd, *Chainman.*
Peter Peterson, *Axeman.*
Moroni A. Brown, *Axeman.*
———, *Flagman.*

BOOK-A-201

[15. FINAL OATHS OF ASSISTANTS.]

We hereby certify that we assisted Shadrach M. Richardson United States deputy surveyor, in surveying all those parts or portions of the townships and sections lines in townships 13, 14 and 19 south, range 3 west and townships 35 and 36 south range 7 west

of the Salt Lake base and meridian in the Territory of Utah, as are represented in the foregoing field notes as having been surveyed by him, and under his direction; and that said survey has been in all respects, to the best of our knowledge and belief, well and faithfully surveyed, and the corner monuments established according to the instructions furnished by the United States surveyor-general for Utah.

_____, Compassman.

F. M. Gavin, Chainman.

J. A. Montagy, Chainman.

J. E. Bickstrom, Chainman.

W. M. Lloyd, Chainman.

Peter Petersen, Axeman.

Moroni A. Brown, Axeman.

_____, Flagman.

Subscribed and sworn to before me this 30th day of March 1884.

Ernst Salomon

Notary Public

BOOK-A-201

[6.—FINAL OATH OF UNITED STATES DEPUTY SURVEYOR.]

I, Shadrach M. Richardson United States deputy surveyor, do solemnly swear that in pursuance of instructions received from Fred. Falconer United States surveyor-general for Utah, bearing date of the 19th day of December, 1883, I have well, faithfully, and truly, in my own proper person, and in strict conformity with the instructions furnished by the United States surveyor-general for Utah, the surveying manual and the laws of the United States, surveyed all those parts or portions of townships and subdivision lines in townships 13, 14 and 19 south, range 3 west and townships 35 and 36 south, range 7 west

of Salt Lake base and meredian in the Territory of Utah, as are represented in the foregoing field notes as having been surveyed by me and under my directions; and I do further solemnly swear that all the corners of said survey have been established and perpetuated in strict accordance with the surveying manual, printed instructions, the special written instructions of the United States surveyor-general for Utah, and in the specific man-

ner described in the field notes, and that the foregoing are the TRUE field notes of such survey; and, should any fraud be detected, I will suffer the penalty of perjury, under the provisions of an act of Congress, approved August 8, 1846.

Shadrach M. Richardso

United States Deputy Surveyor.

Subscribed and sworn to before me this 30th day of March 1884.

Ernst Salomon

Notary Pub

5

BO

U. S. SUR

Salt L

The fo

Based u

Township N

Executed by

Under Re

day of Dec

amined, the n

the said field

hereby approv

BOOK-A-201 470-A

East Boundary T36 S. R 7 W.

Chs. Survey Commenced March 4/84
From the corner to Tps 36 and 37 S. Rs. 6 and 7 W which is a sandstone firmly set in the ground and properly marked I run north on a true line bet. secs 31 and 36.
Var. 15° 20' E.
Through timber.

40.00 Set a lime stone 20 x 12 x 8 ins. 14 ins. in ground for 1/4 sec. cor. marked 1/4 on W face, from which
A pine 6 ins. diam. bears S 70° E 20 lks dist.
A pine 8 ins. diam. bears N 60° W 70 lks dist. each marked 1/4 S. B. T.

60.00 Trail bears E and W.

80.00 Set lime stone 14 x 10 x 6 ins. 10 ins. in ground for corner to secs. 25. 30. 31 and 36 marked 5 notches on N and 1

East Boundary T 36 S

Chs. on S edges, from which
A pine 30 ins. diam. bears
S 10° E 1.30 chs. dist.
A pine 10 ins. diam. bears
S 45° W 2.00 chs. dist.
A pine 8 ins. diam. bears
N 47° W 1.46 chs. dist.
A pine 12 ins. diam. bears
N 25° E 70 lks dist, each
marked with the proper Tp.
Rg and Sec.
Land rolling.
Soil 2nd rate
Heavily timbered on 80.00 ch

North bet. secs. 25 and 30.
Var. 15° 20' E.

Throug heavy pine timber.

5.90 Road bears N E and S W.
20.00 Ascend abruptly.
32.00 Ridge bears S W and N E.
40.00 Set lime stone 16 x 10 x 6 ins.
11 ins. in ground for 1/4 sec. cor.

East Boundary T 36 S

Chs. Soil 2 nd. rate.
Heavily timbered on 80.00 chs.

North bet. sec's. 19 and 24.
Var. 15° 20' E.

40.00 Set lava stone 20 x 12 x 8 ins. 14 ins. in ground for 1/4 sec. cor. marked 1/4 on W face.

A pine 40 ins. diam. bears N 53° E 57 lks dist.

A pine 60 ins. diam. bears N 32° W 145 lks dist. each marked 1/4 S B.T.

60.00 Descend abruptly.

65.50 Hollow drains N.E.

70.00 Ridge bears N E. and S.W.

80.00 Set gray lime stone 16 x 10 x 6 ins 11 ins. in ground for cor. to sec's. 13. 18. 19 and 24 marked 3 notches on N and S edges.

A pine 14 ins. diam. bears N 45° E. 40 lks dist.

A pine 6 ins. diam. bears

BOOK-A-201 474

R 7 W. S. L. M.

Chs. S 16° E 110 lks dist.
A pine 8 ins. diam. bears
N 82° W 52 lks dist.
A pine 18 ins. diam. bears
S 75° W 60 lks dist each
marked with the proper Tp.
Rg and Sec.
Land plateau and rolling.
Soil 1st and 2nd rate.
Heavily timbered on 8000 chs.

North bet. secs. 13 and 18
Var. 15° 20' E.
Through heavy timber.
22.00 Ravine drains E.
28.00 Ridge bears E and W.
38.00 Abrupt Descent.
40.00 Set sandstone 14 x 10 x 8 ins.
10 ins. in ground for 1/4 sec.
cor. marked 1/4 on W face
A pine 6 ins. diam. bears
S 85° E 1.80 chs. dist.
A pine 8 ins. diam bears

East Boundary T36 S

Chs. N 45° W 20 lks dist. each marked 1/4 S. B.T.

4 4.50 Trail in canon bears E & W

7.00 Ridge bears E and W.

8.00 Set a lava stone 15 x 8 x 4 ins 10 ins in ground for cor. to secs. 7. 12. 13 and 18 marked 2 notches on N and 4 on S edges

A pine 30 ins. diam. bears S 86° W 55 lks dist.

A pine 18 ins. diam. bears S 25 1/2° W 2. 14 chs. dist.

A pine 4 ins diam. bears N 10° E 20 lks dist.

A pine 8 ins. diam. bears N 39° W 1.70 chs. dist each marked with the proper Tp Rg and Sec.

Land mountainous

Soil 3rd rate

Mountainous and heavily timbered on 8.00 chs.

R 7 W S L. M.

Chs. North bet. sec's. 7 and 12
Var. 15° 20' E.
Through heavy timber.
40.00 Set sand stone 15 x 12 x 3 ins.
10 ins. in ground for 1/4 sec.
cor. marked 1/4 on W face.
A pine 30 ins. diam. bears
N 78° E 20 lks dist.
A pine 36 ins. diam. bears
S 75° W 48 lks dist. each
marked 1/4 S. B. T.
51.00 Leave timber
56.00 Road from Panguitch lake
to Mammoth Cr. bears S.E.
70.00 Ascend.
80.00 Set lava stone 16 x 10 x 6 ins.
11 ins. in ground for cor. to
sec's. 1. 6. 7 & 12 marked 1 notch
on N and 5 on S edges and
raised a stone mound alongside.
Land rolling and mountainous.
Soil 2nd rate.
Heavily timbered on 50.00 chs.
Mountainous on 10.00 chs.

East Boundary T 36 S. R. 7 W. S.L.M.

Chs. North bet. secs. 1 and 6.
Var. 15°20' E.

12.50 Enter timber.

17.83 Trail in pass bears E and W.

40.00 Set flint stone 16 X 8 X 6 ins. 11 ins. in ground for 1/4 sec. cor. marked 1/4 on W face, from which
A pine 14 ins. diam. bears N 50° E 150 lks dist.
A mut pine 5 ins. diam bears N 85° W 100 lks dist each marked 1/4 S.B.T.

60.00 Ravine drains S.W.

65.00 Leave timber.

84.56 Intersect 7th. Stand. Par. S.
14.40 chs East of the standard cor to Tp. 35 S Rs. 6 and 7 W.
at point of intersection set sandstone 14 X 10 X 4 ins. 10 ins. in ground for closing cor. to Tp. 36 S. Rs. 6 and 7 W. marked CC with 6 notches on E. S & W edges and raised a stone mound alongside.

Chs. La
S
S
Hcaag
1 M

BOOK-A-201

Chs. Land mountainous.
Soil 3rd rate.
Scattering timber on 52.50 chs.
Nearly Mountainous on 84.56 chs.
March 4/84

South Boundary T 36 S

Chs. From the corner to Tps 36 and 37 S. Rs. 6 and 7 W I run west on a random line betw said Tps. to the corner of Tps. 36 and 37 S. Rs. 7 and 8 W setting temp. half mile and mile corners at 40.00 and 80.00 chs.

Var. 15°20' E.

I find the distance to be 5 miles 78.30 chs. and the falling to be 2.70 chs. north. The correction for the true line will therefore be .45 chs south per mile and the course will be N 89°41' E.

From the corner to Tps. 36 and 37 S. Rs. 7 and 8 W which is a sandstone firmly set in the ground and properly marked I run N 89°41' E on a true line bet. secs 6 and 31

Chs.
5.00
20.00
38.00
38.30
42.00
44.40
78.30

R 7 W. S. L. M.

chs. Var. 15° 20' E.

5.00 Spring branch 4 lks. wide in hollow drains N E.

20.00 Ridge bears N E and S.W.

38.00 Ravine drains N.E.

38.30 Set lava stone 15 x 10 x 4 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on N face, from which

An aspen 4 ins. diam. bears N 20° W 25 lks dist.

An aspen 3 ins. diam. bears S 50° W 60 lks dist. each marked 1/4 S. B. T.

42.00 Ridge bears N E and S.W.

44.40 A pine, marked same.

78.30 Set lava stone 14 x 10 x 7 ins. 10 ins in ground for cor. to sec's. 5. 6. 31 and 32 marked 5 notches on E and 1 on W edges, from which

An aspen 7 ins. diam. bears N 12° E 40 lks dist.

An aspen 6 ins. diam. bears N 7° W 55 lks dist.

An aspen 3 ins. diam. bears

South Boundary T36 S

Chs. S 19° W 30 lks dist
An aspen 3 ins. diam.
bears S 35° E 35 lks dist. each
marked with the proper
Tp. Rg. and sec.
Land mountainous.
Soil 2nd rate.
Heavily timbered and
mountainous on 78.30 chs.

N 89° 41' E on a true line
bet. secs. 5 and 32
Var. 15° 20' E.

8.20 Mammoth creek 30 lks wide
10 ins. deep. flows S.E.

12.50 Ridge bears S.E. and N.W.

20.00 Hollow drains S.E.

40.00 Set lava stone 15x10x10 ins.
10 ins. in ground for 1/4 sec.
cor. marked 1/4 on N face
A pine 36 ins. diam. bears
N 15 lks dist
A pine 24 ins. diam. bears

R 7 W. S. L. M.

chs. S 61°30' E 65 lks dist. each marked ¼ S. B.T.

52.00 Ravine drains S.

70.77 A pine, blazed same.

72.00 Ridge bears S. and N.

78.25 Head of ravine drains S E.

80.00 Set sand stone 15 x 10 x 4 ins. 10 ins. in ground for corner to secs. 4. 5. 32 & 33 marked 4 notches on E and 2 on W edges, from which

A pine 16 ins. diam. bears S 35° W 50 lks dist.

A cedar 9 ins. diam. bears N 80° W 55 lks dist.

A cedar 6 ins diam. bears N 15° E 10 lks dist.

A cedar 5 ins. diam. bears S. 30 E 35 lks dist. each marked with the proper Tp. Rg and Sec.

Land mountainous.

Soil 3 rd rate.

Heavily timbered & mountainous on 80.00 chs.

South Boundary T36 S

Chs. N 89°41' E on a true line bet. secs. 4 and 33.

Var. 15°20' E.

18.50 Ridge bears N and S.

26.00 Trail bears S.E. & N.W.

31.50 A pine, blazed same.

39.50 Ravine drains S.E.

40.00 Set lava stone 19 X 14 X 9 ins. 13 ins. in ground for 1/4 sec. cor. marked 1/4 on N face

A pine 14 ins. diam. bears S 25° E 80 lks dist.

A pine 15 ins diam. bears N 45° E 15 lks dist. each marked 1/4 S.B.T.

68.75 Ridge bears N and S.

80.00 Set volcanic stone 19 X 12 X 8 ins 13 ins. in ground for cor. to secs. 3. 4. 33 X 34 marked 3 notches on E and W edges.

A pine 10 ins. diam. bears N 45° W 10 lks dist.

A pine 14 ins. diam. bears N 45° E 10 lks dist.

BOOK-A-201

R 7 W. S. L. M.

Ch. A cedar 7 ins. diam. bears S 30° E 50 lks dist.
A cedar 6 ins. diam. bears S 10° W 10 lks dist. each marked with the proper Tp. Rg. and Sec.
Land mountainous.
Soil 3rd rate.
Heavily timbered and mountainous on 8000 chs.

N 89° 41' E on a true line bet. secs. 3 and 34.
Var. 15° 20' E.

.25 Small ravine drains S.
14.55 A pine, blazed same.
17.00 Point of ridge bears S.
40.00 Set lava stone 16 X 10 X 9 ins. 11 ins. in ground for 1/4 sec. cor. marked 1/4 on N face
A pine 30 ins. diam. bears N 3° W 60 lks dist.
A pine 16 ins. diam. bears

485

South Boundary T 36 S

Chs. N 30° E 75 lks dist. each marked ¼ S. B. T.

8.00 Set lava stone 20×14×10 ins 14 ins. in ground for cor. to sec's 2. 3. 34 and 35 marked 2 notches on E and 4 on W edges, from which

A pine 24 ins. diam. bears N 2° W 2.18 chs. dist.

A pine 30 ins. diam. bears N 50° E 3.12 chs. dist.

A pine 16 ins. diam. bears S. 30° W. 78 lks dist. each marked with the proper Tp. Rg and Sec.

No other tree within limits raised a stone mound observed

Land rolling and mountainous

Soil 3rd rate.

Heavily timbered on 8.00 chs.

BOOK-A-201

R 7 W. S. L. M.

Ch. N 89° 41' E on a true line
bet. secs 2 and 35
Var: 15° 20' E.

2.00 Trail bears S 85° E.

4.00 Set lava stone 24X14X10 ins.
16 ins. in ground for 1/4 sec.
cor. marked 1/4 on N face
A cedar 3 ins. diam. bears
S 60° W 60 lks dist.
A cedar 4 ins diam. bears
N 30° E 50 lks dist. each
marked 1/4 S. B. T.

8.00 Set lava stone 18X10X10 ins.
12 ins. in ground for cor.
to secs. 1. 2. 35 and 36 marked
1 notch on E and 5 on W
edges and raised a stone
mound alongside.
Timber too small to
work.
Land broken.
Soil third rate.
Heavily timbered with
small scrubby timber on 8.00 ch.

South Boundary T36 S

Chs. N 89°41' E on a true line bet. sec's. 1 and 36.

Var. 15°20' E.

4.50 Road bears N W & S E.

7.20 " " " "

29.50 " " N and S.

31.00 Wash drains S.

34.75 Road bears N E and S.W.

40.00 Set sand stone 14X10 X7 ins. 10 ins in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.

50.00 Ridge bears N and S.

53.25 A pine marked same.

65.50 Road bears N and S.

72.50 Road " N E and S W.

80.00 The cor. to ~~Tow~~ townships 36 and 37 south, ranges 6 and 7 W.

Land nearly level

Soil 1st and 2nd rate.

Heavily timbered with

BOOK-A-201

R 7 W. S. L. M.

small scrubby timber on 8000 chs, too small to mark.

March 1907

West Boundary T 36 S

Chs. From the cor. to Tps. 36 and 37 S. Rs. 7 and 8 W. which is a sand stone firmly set in the ground and properly marked I run North on a true line between secs. 31 and 36.

Var. 15° 30' E.

Through timber.

32.00 A pine blazed same.

40.00 Set lava stone 14x10x6 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on W face

An aspen 9 ins. diam. bears S 86° E 50 lks dist.

A pine 3 ins. diam bears N 5° W 4 lks dist each marked 1/4 S. B. T.

41.00 Head of ravine drains N.E.

43.00 Ridge bears N. E. and S. W.

44.00 Mammoth creek. 25 lks wide 9 ins. deep. drains S. E.

45.00 Trail bears N. W. & S. E.

√ 80.00 Set lava stone 16x12x9 ins.

R 7 W. S. L. M.

Chs. 11 ins. in ground for cor. to sec's. 25. 30. 31 and 36 marked 5 notches on N and 1 on S edges, from which

An aspen 5 ins. diam. bears N 37° E 90 lks dist.

An aspen 6 ins. diam. bears S 45° E 2.25 chs. dist.

An aspen 7 ins. diam. bears S 35° W 1.95 chs. dist. each marked with the proper Tp. Rg. and Sec.

No other tree within limits raised a stone mound alongside.

Land mountainous.

Soil 3rd rate.

Heavily timbered and mountainous on 8.00 chs.

West Boundary T 36 S

Chs North bet. secs. 25 and 30
Var. 15° 30' E.
Through timber.

40.00 Set line stone 15 x 10 x 5 ins
10 ins. in ground for 1/4 sec.
cor. marked 1/4 on N face.
A pine 16 ins. diam bears
S 40° E. 55 lks dist.
A pine 36 ins. diam bears
S 45° W 60 lks dist. each
marked 1/4 S. B. T.

80.00 Set a lava stone 14 x 12 x 8
ins 10 ins. in ground for
cor. to secs. 19. 24 x 25 x 30
marked 4 notches on N and
2 on S edges from which
An aspen 6 ins. diam. bears
N 24° W 1.15 chs. dist.
An aspen 5 ins. diam. bears
S 30° W 1.04 chs dist.
An aspen 3 ins diam. bears
N 57° 30' E 1.40 chs. dist.
An aspen 5 ins. diam. bears
S 35° E 2.10 chs. dist.

R 7 W

chs. eac
propo

No

11.60 A p
39.00 Top o
40.00 Set
11 ins
mark
an
N

S 5
mar
50.00 Des
60.00 Roc
79.00 Des
80.00 Set
ins

R 7 W. S. L. M.

chs. each marked with the proper Tp. Rg and sec.
Land rolling.
Soil 2nd rate.
Heavily timbered on 8000 chs.

North bet. sec's. 19 and 24
Var. 15° 30' E.

11.60 A pine 20 ins. diam, blazed same.
39.00 Top of mountain 2000 ft high.
40.00 Set a lava stone 16 X 10 X 10 ins 11 ins in ground for 1/4 sec. cor. marked 1/4 on W face from which an aspen 5 ins. diam. bears N 45° W 1.60 chs. dist.
An aspen 5 ins. diam. bears S 57½° E 96 lks dist. each marked 1/4 S. B. T.
50.00 Descend abruptly.
60.00 Rocky gorge drains E.
79.00 Descend abruptly.
80.00 Set volcanic rock 18 X 12 X 5 ins 12 ins. in ground for

493

West Boundary T 36 S

Chs cor. to secs. 13. 18. 19 and 24
marked 3 notches on N and
S edges from which
An aspen 6 ins. diam. bears
N 30° W 38 l'ks dist.
An aspen 3 ins. diam. bears
N 80° E 31 l'ks dist.
An aspen 3 ins. diam. bears
S 15° E 14 l'ks dist.
An aspen 4 ins. diam. bears
S. 38° W 10 l'ks dist. each
marked with the proper
Tp. Rg and Sec.
Land mountainous.
Soil 2nd rate.
Mountainous and
heavily timbered on 8.00 chs

North between secs. 13 & 18
Var. 15° 30' E.

7.50 Spur of ridge bears W.
11.00 Rocky gulch drains N. E.
25.50 Ridge descends E.

BOOK-A-201 494

R 7 W. S. L. M.

Chs
40.00 Set a volcanic stone 14 X 10 X 6 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on W face

An aspen 4 ins. diam. bears N 60° W 90 lks dist.

An aspen 5 ins. diam bears S 70° E 79 lks dist. each marked 1/4 S. B. T.

71.00 Spring branch 10 lks wide flows E about 1.50 chs and forms a lake about 1½ acres

78.00 Ridge bears E and W.

80.00 Set a lava stone 15 X 11 X 6 ins. 10 ins. in ground for corner to secs. 7, 12, 13 and 18 marked 2 notches on N and 4 on S edges from which

A pine 46 ins. diam. bears N 25° E 26 lks. dist.

An aspen 7 ins. diam. bears N 60° E 2.56 chs dist.

An aspen 8 ins. diam. bears S 56° E 1.18 chs. dist.

An aspen 4 ins diam.

West Boundary T 36 S

chs. bears S 46½° W 1.65 chs. dist.
each marked with the
proper Tp. Rg and Sec.
Land rolling and broken.
Soil 4th rate.
Heavily timbered on 80.00 ch

North bet. secs. 7 and 12
Var. 15° 30' E.

22.00 Spring branch 5 lks wide
flows S. E.
23.50 Road bears E and W.
34.50 Creek runs E 15 lks wide.
40.00 Set volcanic stone 18 X 12 X
10 ins 12 ins. in ground for
¼ sec. cor. marked ¼ on W
face from which
An aspen 7 ins. diam.
bears S 89° E 20 lks dist.
An aspen 2 ins. diam.
bears N 79° W 15 lks dist
each marked ¼ S. B.T.
72.70 A perpendicular cliff

(R

chs. 4
79.00 J
80.00 C
15
to
1
ed
ne
bea
bea
bea
loc
per
N

BOOK-A-201

R 7 W. S. L. M.

Chs. 40 ft. high.
79.00 Hollow drains E.
80.00 Set lava stone 20 x 14 x 6 ins. 15 ins. in ground for cor. to secs. 1. 6. 7 and 12 marked 1 notch on N and 5 on S edges and raised a stone mound alongside.

An aspen 6 ins. diam. bears S 38° W 2.14 chs. dist.

An aspen 6 ins. diam. bears S 46½° E 2.63 chs. dist.

An aspen 5 ins. diam. bears N 35° E 2.64 chs. dist. each marked with the proper Tp. Rg and Sec.

No other tree within limits.

Land rolling mountains.

Soil 2nd and 4th rate.

Heavily timbered on 80.00 chs.

West Boundary T 36 S

Chs. North between secs. 1 and 6.
Var. 15°30' E.

5.00 Ridge bears N. E. & S W.

25.00 Hollow drains E.

30.00 Canon drains E. spring 5.00 chs. east of line.

35.00 A ledge of rock bears E & W.

40.00 Set a lava stone 14X10X8 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on W face
An aspen 8 ins. diam. bears S 45° W 1.15 chs. dist.
An aspen 5 ins. diam. bears S 25° E 2.60 chs. dist. each marked 1/4 S B.T.

54.00 Top of mountain about 1800 ft. above lake bears S.

83.78 Intersect 7th. Stand. Par. South 13.20 chs. east of standard cor. to Tp. 35 S Rs. 7 and 8 W. at point of intersection set a lava stone 16 X 10 X 3 ins. 11 ins. in ground for closing corner

BOOK-A-201

R 7 W. S. L. M.

chs. to Tp. 36 S. Rs. 7 and 8 W. marked C.C. with 6 notches on E. S + W edges from whcd. an aspen 3 ins. diam. bears S 86° W 100 lks dist.

An aspen 3 ins. diam bears S 78° E 70 lks dist.

A pine 13 ins. diam. bears N 6° E 30 lks dist. each marked with the proper Tp. Rg and Sec.

Land mountainous.

Soil 2 nd and 4 th rate.

Heavily timbered on

83.78 chs.

March 6/84

Note.

For general description see subdivision notes of this township.

U. S. Dep. Surveyor.

BOOK-A-201

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, June 28th 1884

The foregoing field notes of the survey of the

E. & W. Boundaries

Township No. 36 S *Range No.* 7 W

Executed by Shadrach M. Richardson

Under his *contract* No 123 *of the* 19th

day of December 1883, *in the month of*

March 1884, *having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

Fred Salomon

U. S. Surveyor General for Utah.

BOOK-A-201

REPORT: 1884

Filed 188

Examined by .....

Transcribed by E M Chalis

Compared by C H Kerrison & E M Chalis

FIELD NOTES

OF THE SURVEY OF THE

Subdivisions and Meanders of Panguitch Lake

OF

Township No 36 South

Range No 7 West

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Shadrach M. Richardson

U. S. Deputy Surveyor,

Under his Contract No. 123.

Dated December 19 th. 1883.

Survey commenced March 7 th 1884.

Survey completed " 14 th 1884.

V

BOOK-A-201

Township 36 South *R.* 7 West

497	6	569	5	549	4	538	3	527	2	512	1	471
	568		566		548		537		526		511
495	7	565	8	546	9	536	10	525	11	510	12	476
	563		562				535		524		509
493	18	561	17	545	16		15	522	14	507	13	474
	560		559						521		506
492	19	558	20	544	21	534	22	520	23	504	24	473
	557		556		543		533		518		503
491	30	554	29	542	28	531	27	517	26	502	25	471
	553		552		541		530		516		500
489	31	550	32	540	33	529	34	514	35	499	36	476
	479		481		483		484		486		487

BOOK-A-201

Subdivisions T36 S. R7 W.

Chs. Survey commenced March 7/84
From the corner to sec's.
35 and 36 on the south
boundary of the Tp. previously
set by me I run north
on a true line between
sec's. 35 and 36.
Var. 15°45' E.

3.25 Road bears N W x S E.
8.30 Wash drains S.E.
9.50 Road bears N W x S.E.
14.00 Foot of hill, enter valley.
40.00 Set sandstone 16 X 10 X 10 ins.
11 ins. in ground for 1/4 sec.
cor. marked 1/4 on W face
A pine 14 ins. diam. bears
S 45° W 6 lks dist.
A pine 10 ins. diam. bears
N 45° E 11 lks dist, each
marked 1/4 S. B. T.
46.00 Ascend
68.00 Road bears S.W. x N. E.
80.00 Set sand stone 16 X 14 X 9 ins.
11 ins. in ground for cor. to

Subdivisions T 36 S

Chs. secs. 25. 26. 35 & 36 marked
1 notch on E and S edges
a pine 13 ins. diam. bea
N 45° E 14 lks dist.
a pine 24 ins. diam. bea
S 6° E 40 lks dist.
a pine 26 ins. diam. bear
S 70° W 60 lks dist.
a cedar 8 ins. diam. bear
N 45° W 45 lks dist. each
marked with the proper
Tp. Rg. and sec.
Land rolling
Soil 2nd rate.
Heavily timbered on
8000 chs.

East on a random line
bet. secs 25 and 36.
Var. 15°30' E.

4000 Set temp. 1/4 sec. cor
80.10 Intersect E boundary of Tp
at cor. to secs. 25 and 36

R

Chs. fro
a t
w
8.00 Ru
24.50 R
40.00 Se
10
cor
an
al
T
58.00 Ro
62.00 "
72.00 R
80.10 Th
36.
de
8

BOOK-A-201

R 7 N. S. L. M.

Chs. from which I run west on a true line bet. secs. 25 & 36 with same Cor.

8.00 Road bears N. E. and S. W.

24.50 Ridge bears N and S.

40.05 Set a sandstone 14 X 10 X 5 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside

Trees too small to mark.

58.00 Road in canon bears N W.

62.00 " " same " " "

72.00 Ridge bears N & S.

80.10 The cor. to secs. 25. 26. 35 & 36.

Land mountainous.

Soil 1st and 3rd rate.

Mountainous and dense scrubby timber on 80.10 chs.

Subdivisions T 36 S

Chs. North bet. secs. 25 & 26.
Var. 15°30' E.

5.00 Stone edges
10.00 Ridge bears S E & N W.
22.00 Head of hollow undrained drains S E
25.00 Ridge bears S E & N W.
40.00 Set sand stone 16 x 10 x 7 ins
11 ins. in ground for 1/4 sec.
cor. marked 1/4 on W face
A pine 18 ins. diam bears
E 6 lks dist.
A pine 5 ins. diam bears
S 60° W 15 lks dist. each
marked 1/4 S. B. T.
47.50 Canon drains S. E.
80.00 Set lime stone 40 x 12 x 6 ins
30 ins. in ground for corner
to secs. 23. 24. 25 & 26.
marked 1 notch on E and
2 on S edges, from which
a pine 6 ins. diam. bears
S 20° E 36 lks dist. marked
T36 S. R. 7 W. S. 25 B.T.
No other tree large enough
to mark.

R. 7 W. S. L. M.

Chs. raised a stone mound alongside.

Land mountainous.

Soil 3rd rate.

High mountainous and timber on 80.00 chs.

East on a random line between secs 24 x 25

Var. 15°30' E.

40.00 Set temp ¼ sec. cor.

80.00 Intersect E bound. of Tp. 10 lks N of cor. to secs. 24 and 25 from which I run N 89°56' W on a true line bet secs 24 x 25 with same Var.

Through timber.

25.00 Descend abruptly.

31.00 Ravine drains N.

36.00 Ridge bears N & S.

40.00 Set a lime stone 16 x 10 x 8 ins 11 ins. in ground for

Subdivisions T 36 S

Chs. 1/4 sec. cor. marked 1/4 on ~~E~~ W face ~~E~~

47.80 Wash in hollow drains S.

Ascend.

80.00 The corner to secs. 23. 24. 25 & 26.

Land rolling.

Soil 1st & 3rd rate.

Heavily timbered on 80.00 chs.

~~Note. The bearing trees of the 1/4 sec. cor. are~~

~~E~~ A pine bears N 80° W 3 ins. diam. 20 lks dist.

A pine 8 ins diam. bears S 80° W 25 lks dist. each marked 1/4 S. B. T.

North between secs. 23 & 24.

Var. 15° 30' E.

31.00 A pine, blazed same.

40.00 Set lime stone 14 x 10 x 5 in 9 ins. in ground for 1/4 sec.

R 7 W. S. L. M.

Chs. cor. marked 1/4 on W face
A pine 7 ins. diam. bears
S 65° E 70 lks dist.
A pine 10 ins. diam. bears
N 70° W 60 lks dist. each
marked 1/4 S B T.
63.40 Ravine with trail bears
N E & S W. drains N E.
79.00 Ridge bears E & W.
80.00 Set volcanic rock 16 x 12 x 7
ins. 11 ins. in ground for cor.
to secs. 13. 14. 23. & 24.
marked 1 notch on E & 3 on S
edges from which
A pine 36 ins. diam bears
S 72° W 122 lks dist.
An aspen 5 ins. diam. bears
S 85° E 106 lks dist
An aspen 7 ins diam. bears
N 21° E 143 lks dist.
A quaking asp. 7 ins. diam. bears
S 45° W. 83 lks dist. each
marked with the proper
Tp. Rg and Sec.

Subdivisions T 36 S.

Chs. Land rolling.
Soil 2 nd rate.
Heavily timbered on 80.00 ch

East on a random line
bet. 13 and 24.
Var. 15° 30' E.

40.00 Set temp. ¼ Sec. cor.
80.20 Intersect E. bound of Tp.
20 lks N of cor. to secs. 13 &
14, from which I run
N 89°51' W on a true line
bet. secs. 13 and 24
with same Var.
26.00 Ravine drains S.
40.00 Set lime stone 16 x 10 x 4 ins
11 ins. in ground for ¼ sec.
cor. marked ¼ on N face
A pine 27 ins. diam. bears
N 64 lks dist.
A pine 20 ins. diam. bear
S 10° W 78 lks dist. each
marked ¼ S. B. T.

R 7 W. S. L. M.

Chs. 70.00 Trail in canon drains N

80.20 The corner to sec's. 13 14. 23 & 24

Land mountainous.

Soil 2nd rate.

Mountainous and heavily timbered on 80.20 chs.

North bet. sec's. 13 & 14

Var. 15° 30' E.

5.00 Trail bears E and W.

6.00 Bottom of ravine drains E.

10.00 A pine blazed same.

34.50 Canon with trail drains E.

A house and corral bears S 36° E

40.00 Set lava stone 15 X 10 X 9 ins. 10 ins in ground for 1/4 sec. cor. marked 1/4 on W face from which

A pine 24 ins. diam. bears S 40° W 25 lks dist.

A pine 16 ins. diam. bears.

Subdivisions T 36 S.

Chs. N 15° E 35 lks dist. each marked ¼ S. B. T.

66.50 Ridge E & W.

72.50 Road bears N. E.

80.00 Set lime stone 14 x 10 x 8 ins 11 ins. in ground for corner to secs. 11. 12. 13 & 14 marked 1 notch on E and 4 on S edges

A pine 5 ins. diam. bears N 20° W 30 lks dist.

A pine 3 ins. diam. bears N 80° E 100 lks dist.

A pine 18 ins. diam. bears S 75° E. 100 lks dist.

A pine 20 ins. diam. bears S 45° W 120 lks dist. each marked with the proper Tp. Rg and Sec.

Land rolling & broken. M

Soil 2nd rate.

Mountainous and heavy timber on 80.00 chs.

R

Chs.

40.00 Se

79.30 Sp

12.00 R

39.65 S

67.00 Tr

75.00 R

79.00 Ro

79.30 The

R 7 W. S. L. M.

Chs. East on a random line bet. secs. 12 & 13.

Var. 15° 30' E.

40.00 Set temp. 1/4 sec. cor.

79.30 Intersect the E. boundary of Tp. 50 lks N of corner to secs. 12 & 13 from which I run N 89° 39' W on a true line bet. secs. 12 and 13 with same Var.

12.00 Ridge bears N E & S W.

39.65 Set a lime stone 14 x 8 x 3 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on N face

A pine 20 ins. diam. bears N 18° E 20 lks dist.

A pine 15 ins. diam. bears S 2° E 31 lks dist. each marked 1/4 S. B. T.

67.00 Trail, course S.E. & N W.

75.00 Ridge bears N E & S W.

79.00 Road in canon bears N E and S.W.

79.30 The cor. to secs. 11. 12. 13 & 14

Land mountainous

Subdivisions T 36 S

chs. Soil 2nd x 3rd rate.
Mountainous and heavily timbered on 79.30 chs.

North bet. secs. 11 and 12
Var. 15°30' E.

23.00 A pine, blazed same
40.00 Set a sand stone 15 x 12 x 3 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on W face from which
A pine 14 ins. diam. bears N 85° W 10 lks dist.
A pine 16 ins. diam. bears S 70° E 50 lks. dist. each marked 1/4 S. B. T.
44.00 Trail bears N. and S.
55.60 A pine, blazed same.
80.00 Set granite 16 x 10 x 3 ins. 11 ins. in ground for cor. to secs. 1, 2, 11 & 12 marked 1 notch on E and 5 on S edges from which a pine 36 ins. diam. bears S 48° E 125 lks dist.

R 7 W. S. L. M.

Chs. A pine 12 ins. diam. bears N 30° W 135 lks dist, each marked with the proper Tp. Rg and Sec.
No other tree convenient to mark, raised a stone mound alongside.
Land rolling.
Soil 2nd rate.
Heavily timbered on
8000 chs.

East on a random bet. sec's. 1 and 12
Var. 15°30' E.

40.00 Set temp. ¼ Sec. cor.
80.05 Intersect E bound. at cor. to sec's 1 and 12, from which I run west on a true line bet. sec's. 1 and 12 with same Var.
15.00 Foot of hill, course N. & S.E.
33.50 Road bears N.W. & S.E.

5/2

Subdivisions T 36 S

Chs.
36.00 Ascend.

40.02 Set granite 22 x 16 x 2 ins. 14 ins. in ground for 1/4 sec. cor. marked 1/4 on N face

A pine 24 ins. diam. bears S 76° W 50 lks dist.

A pine 30 ins. diam. bears N 18° W 50 lks dist. each marked 1/4 S. B. T.

65.00 Hollow drains N. with trail

80.05 The cor. to secs. 1. 2. 11 & 12

Land rolling.

Soil 2nd rate.

Heavily timbered with small scrubby timber on 80.05 chs.

North on a true line bet secs. 1 and 2

Var. 15° 30' E.

28.72 A pine, blazed same.

40.00 Set quartzite 18 x 12 x 6 ins. 12 ins. in ground for

R 7 W. S. L. M.

Chs. 1/4 sec. cor. marked 1/4 on W face and raised a mound of earth and stone alongside.

47.00 Road bears N W x S E.

57.10 " " " "

70.00 Foot of mountain. Ascend.

75.00 Wash drains S W.

84.10 Intersect 7th standard parallel south 13.60 chs. East of cor. to sec's. 35 & 36. At point of intersection set a sand stone 20 x 10 x 6 ins. 14 ins. in ground for closing corner to sec's. 1 and 2 marked C.C. with 1 notch on E and 5 on W edges

A nut pine 10 ins. diam. bears S 31° W 125 lks dist.

A cedar 12 ins. diam. bears S 11° E 120 lks dist. each marked with the proper Tp. Rg and Sec.

No other tree convenient.

Subdivisions T 36 S

Chs. to mark, raised a stone mound alongside.

Land rolling.

Soil 1st & 2nd rate.

Timber scattering.

March 1784.

From the corner to sec's. 34 & 35 on the S boundary of the Tp. previously set by me I run north on a true line bet. sec's. 34 and 35

Var. 15° 30' E.

.50 Trail bears N W & S E. ascend

18.00 Abrupt ascent.

27.75 Top of ridge bears S E & N W

40.00 Set a black lava stone 14 x 4 x 4 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on W face from which

A pine 8 ins. diam. bears S 88° E 180 lks dist.

A pine 4 ins. diam. bears

BOOK-A-201

R 7 W. S. L. M.

Chs. N 78° W 30 lks dist. each marked ¼ S. B.T..

58.50 Trail bears S.E. x N.W.

66.00 Divide between hollows bears S E x N W, divide bears S W x N.E.

70.00 Wash drains W.

80.00 Set a lime stone 16 x 12 x 10 ins. 11 ins. in ground for corner to secs. 26. 27. 34 x 35. marked 2 notches on E and 1 on S edges from which

A pine 10 ins. diam. bears N 56° E 48 lks dist.

A pine 16 ins. diam. bears N 60° E 35 lks dist.

A pine 12 ins. diam. bears S 31° 30' E 200 lks dist.

A pine 12 ins. diam. bears S 26° W 230 lks dist. each marked with the proper Tp. Rg and Sec.

Land rolling mountains.

Soil 3rd rate.

Subdivisions T 36 S

Chs. Heavily timbered on 80.00 chs.

East on a random line bet. sec's. 26 and 35.
Var. 15° 30' E.

40.00 Set temp. ¼ sec. cor.

80.30 Intersect N and S line at cor. to sec's. 25. 26. 35 x 36 from which I run west on a true line bet. sec's. 26 x 35 with same Var.

10.00 Ridge bears N W & S E.

19.50 Trail in canon bears S. E.

40.15 Set sandstone 15 x 10 x 8 ins. 10 ins. in ground for ¼ sec. cor. marked ¼ on N face and raised a stone mound along

A pine 10 ins. diam. bears N 50° W 100 lks. dist.

A spruce 7 ins. diam. bears S 70° W 63 lks. dist. each marked ¼ S. B. T.

70.75 Ridge bears N W & S. E.

R 7 W. S. L. M.

chs.
80.30 The cor. to secs. 26. 27. 34 x 35.

Land mountainous.
Soil 3rd rate.
Mountainous and heavily timbered on 80.30 chs.

North bet. secs. 26 and 27.
Var. 15° 30' E.

15.00 Ridge bears N W & S.E.

40.00 Set lime stone 16 x 10 x 5 ins. 11 ins in ground for 1/4 sec. cor. marked 1/4 on W face, from which a pine 10 ins. diam. bears S 45° W 100 lks dist.

A pine 15 ins. diam. bears S 65° E 112 lks dist. each marked 1/4 S. B. T.

50.00 Ascend.

79.50 Wash in hollow drains S.E.

80.00 Set a lime stone 20 x 12 x 10 ins. 14 ins in ground for cor. to secs. 22. 23. 26 & 27 marked

Subdivisions T 36 S

Chs. with 2 notches on E and S edges from which

a pine 6 ins. diam. bears S 54° E 100 lks dist.

a pine 30 ins diam bears S 60° W 35 lks dist.

a pine 28 ins. diam. bears N 35° W 112 lks dist.

a pine 28 ins. diam bears N 15° E 18 lks dist. each marked with the proper Tp. Rg and Sec.

Land mountainous.

Soil 3rd rate.

Heavily timbered on 8000 chs.

East on a random line bet. secs. 23 and 26

Var. 15°30' E.

40.00 Set temp. 1/4 sec. cor.

79.90 Intersect N and S line 10 lks N of cor. to secs. 23. 24.

R 7

Chs. 25 ris lin wit D

7.50 To

12.20 Tr

15.80 Re

39.95 Se 10 cor

S 3

N 8 ma

48.50 Ri

71.00 Ho

79.90 Th 27.

79.

R 7 W S. L. M.

Chs. 25 and 26 from which I run N 89° 56' W on a true line bet. secs. 23 and 26. with some Var.

Descend.

7.50 Foot of abrupt descent.

12.20 Trail bears N and S.

16.80 Road in canon bears N & S.

39.95 Set lime stone 14 x 12 x 6 ins. 10 ins in ground for 1/4 sec. cor. marked 1/4 on N face

A pine 8 ins. diam. bears S 35° E 50 lks dist.

A pine 30 ins. diam bears N 8° E 60 lks dist. each marked 1/4 S. B. T.

48.50 Ridge bears N. and S.

71.00 Hollow drains S.

79.90 The cor. to secs. 22. 23. 26 & 27.

Land rolling mountains.

Soil 2nd rate.

Heavily timbered on 79.90 chs.

Subdivisions T 36 S

Chs. North bet. secs. 22 & 23.
Var. 15° 30' E.

20.00 Ridge bears N W & S E.

27.60 Hollow drains S. E.

40.00 Set a gray lime stone 14 x 10 x 8 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on W face from which a pine 40 ins. diam. bears N 78° W 31 lks dist.

A pine 12 ins. diam. bears N 60° E 61 lks dist. each marked 1/4 S. B. T.

80.00 Set a volcanic rock 16 x 12 x 7 ins 11 ins. in ground for cor. to secs. 14. 15. 22 & 23 marked 2 notches on E and 3 on S edges from which

A pine 36 ins. diam. bears S 72° W 122 lks dist.

An aspen 5 ins. diam. bears S 85° W 106 lks dist.

An aspen 40 ins. diam. bears N 21° E 143. lks.

A quaking asp. 7 ins. diam.

BOOK-A-201 521

R 7 W. S. L. M.

Chs bears S 45° W 83 lks dist.
each marked with the proper
Tp. Rg and Sec.
Land rolling mountains.
Soil 2nd rate.
Heavily timbered on
80.00 chs.

East on a random line
bet. sec's. 14 and 23.
Var. 15° 30' E.

40.00 Set temp. 1/4 sec. cor.
80.00 Intersect N and S line at
cor. to sec's. 13. 14. 23 & 24. from
which I run west on a true
line bet. sec's. 14 and 23
with same var.
15.00 Ridge bears N. E. and S. W.
38.00 Head of ravine drains N. E.
40.00 Set line stone 18 x 10 x 8 ins.
13 ins. in ground for 1/4 sec.
cor. marked 1/4 on N face from
which a pine 14 ins. diam.

Subdivisions T 36 S.

Chs bears S 50° E 83 lks dist
a quaking asp 7 ins. diam.
bears N 10° W 48 lks dist.
each marked 1/4 S.B.T.

41.50 Spring branch 2 lks wide flows
N.E. Birch spring bears S W
about 5.00 chs.

42.30 Trail bears N E & S W.

80.00 The cor. to secs. 14, 15, 22 & 23
Land rolling mountains.
Soil 2nd rate.
Heavily timbered on 80.00 chs

North bet. secs. 14 and 15
Var. 13° 30' E.

40.00 Set a lime stone 14 x 10 x 3 ins
10 ins. in ground for 1/4 sec.
cor. marked 1/4 on N face
from which a pine 4 ins. diam
bears N 79° E 40 lks dist.
a pine 4 ins diam. bears
S 70° W 38 lks dist. each
marked 1/4 S.B.T.

R. 7 W. S. L. M.

chs.
56.80 Trail in canon bears S E & N W.
80.00 Set volcanic stone 40 x 40 x 30 30 ins. in mound of stone for cor. to secs. 10. 11. 14 & 15 marked 2 notches on E and 4 on S edges and raised a stone mound alongside.

An aspen 8 ins. diam. bears S 50° W 220 lks dist.

An aspen 5 ins. diam. bears S 6 1/2 E 211 lks dist

An aspen 7 ins. diam. bears N 30 W 83 lks dist each marked with the proper Tp. Rg and Sec.

No other tree within limits.

Land rolling mountains

Soil 3rd rate.

Heavily timbered on

80.00 chs.

Subdivisions T 36 S

Chs.	
	East on a random line bet. sec's. 11 and 14
	Var. 15° 30' E.
40.00	Set temp. ¼ sec. cor.
79.75	Intersect N and S line 31 lks N of cor. to sec's. 11. 12. 13 & 14 from which I run N 89° 47' on a true line bet. sec's. 11 and 14.
	Var. 15° 30' E.
30.00	Ridge bears N and S.
39.87	Set a lava stone 16 x 10 x 3 ins 11 ins. in ground for ¼ sec. cor. marked ¼ on N face and raised a stone mound alongside.
	An aspen 5 ins. diam. bears N 30° E 115 lks dist
	A pine 8 ins. diam. bears S. 15° W 32 lks dist. each marked ¼ S. B. T.
60.00	Descent, bears N W & S E.
77.75	The corner to sec's. 10. 11. 14 15

BOOK-A-201

R 7 W. S. L. M.

Chs. Land broken mountains.
Soil 4th rate.
Heavily timbered on 79.75 chs.

North bet. sec's. 10 and 11
Var. 15° 30' E.

8.00 Ascend abruptly.

40.00 Set a lava stone 20 x 12 x 3 ins. 14 ins. in the ground for 1/4 sec. cor. marked 1/4 on W face from which a pine 6 ins. diam. bears S 75° W 210 lks dist.

A pine 14 ins. diam. bears S 88 E 47 lks dist. each marked 1/4 S. B. T.

46.00 A pine 24 ins. diam. blazed.

80.00 Set a lava stone 20 x 12 x 10 ins. 14 ins. in ground for cor. to sec's. 2. 3. 10 and 11 marked 2 notches on E and 3 on S edges

A pine 30 ins. diam. bears S 75° W 65 lks dist.

A pine 5 ins. diam. bears.

Subdivisions T 36 S.

Chs.	
	S 35° E 70 lks dist.
	a pine 24 ins. diam. bears N 40° W 55 lks dist.
	a pine 36 ins. diam. bears N 30° E 60 lks dist. each marked with the proper Tp. Rg and Sec.
	Land rolling mountains.
	Soil 3rd rate.
	Heavily timbered on 8.00 chs.

East on a random line bet. secs. 2 and 11

Var. 15° 30' E.

40.00	Set temp. ¼ sec. cor.
80.10	Intersect N and S line 15 lks north of cor. to secs. 1. 2. 11 & 12 from which I run N 89° 54' W on a true line bet. secs. 2 & 11 with some Var.
12.60	Trail bears N and S.
40.05	Set lava stone 14 x 10 x 7 ins. 10 ins in ground for ¼ sec. cor.

R 7 W. S. L. M.

cha. marked ¼ on N face from which
A pine 36 ins. diam. bears
S 50° W 25 lks dist.
A pine 4 ins. diam. bears
N 45° E 30 lks dist. each
marked ¼ S. B. T.
43.70 A pine, blazed same.
64.00 Ridge bears N. W. & S. E.
80.10 The cor. to sec's. 2, 3, 10 & 11
Land broken & mountainous.
Soil 2 nd & 4 th rate.
Heavily timbered on 80.10 chs.

North bet. sec's. 2 and 3.
Var. 15° 30' E.
10.00 Ridge bears N. W. & S. E.
16.00 Trail in hollow bears E & W.
40.00 Set lava stone 14 x 10 x 7 ins. 10 ins
in ground for ¼ sec. cor. marked
¼ on W face from which
An aspen 4 ins. diam. bears
W 12 lks dist.
An aspen 4 ins. diam. bears.

Subdivisions T 36 S

Chs. E 35 lks dist. each marked
1/4 S.B.T.

42.50 Ridge bears E and W.

84.85 Intersect 7th Stand. Par. S.
14.30 chs. E of the standard
cor. to sec's. 34 & 35. T 35 S. R 7
W. At point of intersection
set lava stone 16 x 10 x 9 ins.
11 ins in ground for closing
cor. to sec's. 2 and 3 marked
C.C. with 2 notches on E and
4 on W edges from which

A pine 13 ins. diam. bears
S 33° E 95 lks dist.

A pine 20 ins. diam. bears
S 43° W 15 lks dist.

A pine 14 ins. diam. bears
N 65° W 60 lks dist.

A pine 36 ins. diam.
bears N 25° E 30 lks dist.
each marked with the
proper Tp. Rg and Sec

Land mountainous and broken
Soil 4th rate.

R 7

Chs. H

30.00 Ridg

40.00 Set

10 in

mark

A

S. 3

A

N. 4

mark

60.00 Dea

64.00 Holl

80.00 Set

16 ins

sec's.

R 7 W. S. L. M.

chs. Heavily timbered on 84.85 chs.
March 8th. 1884.

From the corner to secs.
33 & 34 on the S boundary of
the Tp. previously established
by me I runs north on a true
line bet. secs. 33 and 34.
Var. 15° 30' E.

30.00 Ridge bears W & S E.

40.00 Set sandstone 14 x 10 x 8 ins.
10 ins. in ground for 1/4 sec. cor.
marked 1/4 on W face from which
A pine 12 ins. diam. bears.
S. 30° E 16 lks dist.
A pine 15 ins. diam. bears.
N. 41° W 35 lks dist. each
marked 1/4 S. B. T.

60.00 Descend.

64.00 Hollow drains S E.

80.00 Set a sand stone 24 x 8 x 10 ins.
16 ins in ground for cor. to
secs. 27. 28. 33 & 34. marked

530

Subdivisions T 36 S.

Chs. 3 notches on E and 1 on S edge
A pine 8 ins. diam. bears
N 10° E 65 lks dist.
A pine 16 ins. diam. bears
N 70° W 61 lks dist.
A pine 14 ins diam. bears
S 45° W 100 lks dist.
A pine 6 ins. diam. bears
S 20° E 104 lks, each marked
with the proper Tp. Rg & Sec.
Land mountainous.
Soil 3rd rate.
Mountainous and heavily
timbered on 8 00 chs

East on a random line
bet. secs. 27 & 34.
Var. 13° 30' E
40.00 Set temp 1/4 sec cor
80.15 Intersect N and S line 17 lks
N of cor. to secs. 26, 27, 34 & 35
from which I run N 89° 53' W
on a true line bet. secs.
27 and 34

BOO

R

Chs
1.00
23.00
31.00
40.07
64.50
80.15
30.00
40.00

R 7 W. S. L. M.

Chs. with same Var.
1.00 Descend.
23.00 Wash in hollow drains S.
31.00 Ledge of rock bears N & S.
40.07 Set a quartzite 20 x 12 x 3 ins.
14 ins. in ground for 1/4 sec. cor.
marked 1/4 on N face from which.
A pine 8 ins. drain. bears
N 37° E 85 lks dist.
A pine 26 ins. drain. bears
S 56° W 111 lks dist. each
marked 1/4 S.B.T.
64.50 Ascend.
80.15 The cor. to secs. 27. 28. 33 & 34.
Land rolling mountains
Soil 1st and 4th rate.
Heavily timbered on 80. 15 chs.

North bet. secs. 27 and 28.
Var. 15° 30' E.
3.00 Ridge bears N E and S W.
40.00 Set sandstone 16 x 10 x 6 ins.
11 ins. in ground for 1/4 sec. cor.

Subdivisions T 36 S

Chs. marked ¼ on W face from which
a pine 19 ins. diam. bears.
N 15° W 72 lks dist.
a pine 12 ins. diam. bears
S 62° E. 43 lks dist. each
marked ¼ S. B. T.
47.00 Ridge bears N W & S E.
80.00 Set a brichyte 16x10x8 ins.
11 ins in ground for cor.
to secs. 21. 22. 27 & 28 marked
3 notches on E and 2 on S
edges and raised a stone
mound along side.
a pine 13 ins. diam. bears
N 30° W marked T 36 S. R 7 W.
S 21. B.T.
No other tree large enough
to mark.
Land mountainous
Soil 3rd rate.
Mountains one and heavily
timbered on 8000 chs.

R

Chs.
be
4000 S
80.20 T
N
fro
on
we
4.00 Tho
11.00 R
15.00 H
36.00 R
40.1 Set
10 i
mar
N 3
a
S 2
mar
54.25 Tra
80.20 The
L
S

R 7 W. S. L. M.

Chs. East on a random line
bet. sec's. 22 and 27
Var. 15° 30' E.
40.00 Set temp 1/4 sec cor
80.20 Intersect N and S line 13 lks
N of cor. to sec's. 22. 23. 26 & 27
from which I run N 89° 54' W
on a true line bet. sec's. 22 & 27
with same Var.
4.00 Hollow with wash drains S.E.
11.00 Ridge bears N and S.
15.00 Head of hollow drains S.W.
36.00 Ridge bears N & S.
40.10 Set a lime stone 14 x 10 x 4 ins.
10 ins. in ground for 1/4 sec. cor.
marked 1/4 on N face from which
A fir 3 ins. diam bears
N 5° E 36 lks dist.
A fir 4 ins. diam. bears
S 20° E 25 lks dist. each
marked 1/4 S. B. T.
54.25 Trail in hollow bears N & S.
80.20 The cor. to sec's. 21. 22. 27 & 28
Land mountainous.
Soil 3 rd rate.

Subdivisions T 36 S

Chs. High Mountains and timbered on 80.20 chs.

North bet. sec's. 21 and 22
Var. 15° 30' E.

19.00 Hollow drains S.E.

40.00 A pine 6 ins. diam. marked ¼ S on N face from which A pine 4 ins. diam. bears N 39° E 12 lks dist.

A pine 8 ins. diam. bears N 45° W 14 lks dist. each marked ¼ S.B.T.

55.00 Ravine drains S.E.

67.00 Ridge bears N W and S E.

80.00 Set sand stone 16 X 11 X 10 ins. 11 ins. in ground for cor. to sec's. 15. 16. 21 and 22 marked 3 notches on E and S edges and raised a stone mound alongside.

Timber too small to mark.

Land mountainous.

R 7 W. S. L. M.

Chs Soil 2nd & 3rd rate. Mountainous and heavily timbered with small timber on 8000 chs.

Note.

It being impossible to run the lines bet. secs. 15 and 22 and bet. secs. 15 and 16 on account of very broken mountains, I run west on a true line from the cor. to secs. 10. 11. 14 and 15 bet. secs 10 and 15

Var. 15° 30' E.

10.00 Ridge bears N and S.

25.00 Trail in hollow bears N 70° SE.

40.00 Set a lava rock 14 x 8 x 4 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside

55.00 Ridge bears N and S.

60.00 Gulch drains N W.

Subdivisions T 36 S.

Chs
72.50 Ridge bears N. and S.
80.00 Set a lava stone 20x10x6 ins 14 ins in ground for cor. to secs. 9.10. 15 & 16 marked 3 notches on E and 4 on S edges and raised a stone mound alongside.

Land mountainous.
Soil 4th rate.
High Mountains on 8.00 chs.

North bet. secs. 9 and 10
Var. 15° 30' E.

16.80 Trail in canon bears E & W
30.00 Ridge bears N E & S W.
40.00 Set lava stone 14x10x8 ins 10 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.
70.00 Abrupt descent bears N W & S
74.50 Trail bears N W & S.E.
80.00 Set lava stone 16x12x7 ins.

Chs. 11 ins. in ground for cor. to sec's. 3. 4. 9 and 10 marked 3 notches on E and 5 on S edges

A pine 30 ins. diam. bears N 35° W 23 lks dist.

A pine 36 ins. diam. bears N 10° E 30 lks dist.

A pine 24 ins. diam. bears S 70° E. 60 lks dist.

A pine 26 ins. diam. bears S 83° W 90 lks dist each marked with the proper Tp. Rg and Sec.

Land mountainous.

Soil 3 rd rate.

High Mountains on 8000 chs.

East on a random line bet. sec's. 3 and 10

Var. 15° 30' E.

4000 Set temp 1/4 sec cor

79.40 Intersect N and S line at cor. to sec's. 2. 3. 10 and 11 from which I run west on

Subdivisions T 36 S

Chs.	
	a true line bet. secs. 3 & 10 with same Var.
4.00	Ridge bears N and S.
39.95	Set lava stone 15 x 12 x 8 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on N face from which a pine 14 ins. diam. bears N 75° W 30 lks dist.
	a pine 36 ins. diam. bears S 65 lks dist. each marked 1/4 S. B. T.
40.40	Hollow drains N.
71.50	Ridge bears N W and S. E.
79.90	The cor. to secs. 3. 4. 9 & 10.
	Land mountainous.
	Soil 4 th rate.
	Mountainous and heavily timbered on 79.90 chs.

North bet. secs. 3 and 4
Var. 15° 30' E.

5.50	Ridge bears N W & S E
11.70	Road bears " "

BOOK-A-201

R 7 W. S. L. M.

chs.	
20.50	Leave timber
26.50	Hollow drains W.
33.25	Ridge bears E & W.
40.00	Set quartzite 15 X 12 X 8 ins. 10 ins. in ground for 1/4 Sec. Cor. marked 1/4 on W face and raised a stone mound alongside.
42.65	Road bears E & W.
43.00	South bank of Pangnitch lake set quartzite 17 X 12 X 7 ins. 12 ins. in ground for meander corner to fractional sections 3 and 4 marked M.C. and raised a stone mound alongside.

Land mountainous.
Soil 2nd & 4th rate.
Timber on 20.50 chs.

High Mountains on 43.00 chs.

March 10th 1884.

Subdivisions T 36 S.

Chs. From the corner to sec's. 32 & 33 on the S bound. of the Tp. previously established by me I run north on a true line bet. sec's. 32 & 33,

Var. 13°30' E.

35.00 Ridge bears N W & S E.

40.00 Set lava stone 18x12x9 ins. 13 ins. in ground for ¼ sec. cor. marked ¼ on W face, from which a pine 13 ins. diam. bears N 3° E 31 lks dist.

a pine 8 ins. diam. bears S. 41° W 18 lks dist. each marked ¼ S. B. T.

80.00 Set a lava stone 16x12x8 ins. 11 ins. in ground for cor. to sec's. 28. 29. 32 & 33 marked 4 notches on E and 1 on S edges from which a cedar 4 ins. diam. bears N 30° W 60 lks dist.

an aspen 4 ins. diam. bears S 47° W 318 lks dist.

a cedar 5 ins. diam. bears

R 7 N. S. L. M.

Cha S. 32° E. 78 lks dist each marked with the proper Off. Rg and Sec.
No other tree within limits raised a stone mound alongside.
Land very broken mountains.
Soil 4th rate.
Mountainous and heavily timbered on 80.00 chs.

East on a random line bet. secs. 28 and 33.
Var. 15° 30' E.

40.00 Set temp. ¼ sec. cor.
80.00 Intersect N and S line. 14 lks N of cor. to secs. 27, 28, 33 & 34 from which I run N 89° 54' W on a true line bet. secs. 28 and 33 with same Var.
8.00 Ridge bears N and S.
15.00 Ravine drains S E.

Subdivisions T 36 S

Chs.
40.00 Set a lava stone 14 x 14 x 10 ins.
10 ins. in ground for 1/4 sec. cor.
marked 1/4 on N face from which
A cedar 28 ins. diam. bears
N 25° W 35 lks dist.
A cedar 4 ins. diam. bears
S 5° W 113 lks dist each marked
1/4 S B T.
A cedar on a bare knoll
bears N 25° W.
80.00 The cor. to sec's. 28. 29. 32 & 33.
Land very broken.
Soil 4th rate.
Mountainous and heavily
timbered on 80.00 chs.

North bet. sec's. 28 and 29.
Var. 15° 30' E.

40.00 Set lava rock 24 x 12 x 12 ins.
16 ins. in ground for 1/4 sec. cor.
marked 1/4 on W face and raised
a stone mound alongside.
80.00 Set lava rock 30 x 16 x 10 ins.
20 ins. in ground for cor. to

BOOK-A-201 543

R 7 W. S. L. M.

Chs. secs. 20. 21. 28 and 29. marked 4 notches on E and 2 on S edges and raised a stone mound alongside.

Land, lava bed.

Soil 4th rate.

Timber scattering.

East on a random line bet. secs. 21 and 28.

Var. 15° 30' E.

40.00 Set temp. ¼ sec. cor.

80.10 Intersect N and S line 23 lks S of cor. to secs. 21. 22. 27 & 28 from which I run S 89° 30' W on a true line bet. secs. 21 & 28 with same Var.

80.00 Ridge bears N W & S E.

80.05 Set sandstone 14 x 8 x 8 ins. 10 ins. in ground for ¼ sec. cor. marked ¼ on N face from which a cedar 8 ins. diam. bear N 3° E 41 lks dist.

Subdivisions T 36 S

Chs. A cedar 9 ins. diam. bears S 35° W 13 lks dist. each marked 1/4 S. B. T.

80.10 The cor. to secs. 20. 21. 28 & 29

Land very broken mountains

Soil 4th rate.

Heavy Mountains on 80.10 chs.

North bet secs. 20 and 21

Var. 15° 30' E.

30.00 Canon drains E.

40.00 Set sandstone 18 x 12 x 12 ins 12 ins. in ground for 1/4 sec. cor. marked 1/4 on W face from which A pine 6 ins. diam. bears N 43° W 62 lks dist.

A pine 5 ins. diam. bears S 31° E 19 lks dist. each marked 1/4 S. B. T.

50.00 Ridge bears E and W.

80.00 Set volcanic rock 24 x 12 x 1 ins. 16 ins. ground for cor. to secs. 16. 17. 20. & 21 marked

R 7 W. S. L. M.

chs. 4 notches on E and 3 on S edges and raised a stone mound alongside.

Timber too small to mark.

Land mountainous.

Soil 4th rate.

Mountainous and heavily timbered with small scrubby timber on 8.00 chs.

Note.

It being impossable to run east between secs. 16 and 21 on account of very broken and inaccessible mountains - I run north bet. secs. 16 and 17

Var. 13° 30' E.

2.00 Ascend.

19.50 Ridge bears E and W.

40.00 Set volcanic stone 18 x 12 x 7 ins. 12 ins. in ground for 1/4 sec. cor. marked 1/4 on W face

Subdivisions T 36 S

Chs. and raised a stone mound alongside.

80.00 Set volcanic stone 20 X 18 X 12 ins. 15 ins. in ground for cor to sec's. 8. 9. 16 & 17 marked 4 notches on E and 4 on S edges and raised a stone mound alongside.

Land very broken.

Soil 4th rate.

High Mountains on 80.00 chs.

Note.

On account of broken inaccessable and unavailable mountains the line bet. sec's. 9 and 16 is not run, I therefore run north bet. sec's. 8 and 9

Var. 15° 30' E.

1.00 Enter timber

10.00 Descend.

40.00 Set volcanic stone 18 X 12 X 12 ins 12 ins in ground for 1/4 sec.

R 7

Chs. cor.
whe
bear
a
bear
1/4 S.
32.00 S pr
flow
70.00 Rid
80.00 Set
in g
5. 8
on E
which
bear
a
N 6
a
bears
a
S 50
mor
Rg
L

BOOK-A-201 547

R 7 W. S. L. M.

Chs. cor. marked ¼ on W face from which a quaking asp 4 ins. diam. bears W 20 lks dist.

A quaking asp 12 ins. diam. bears E 40 lks dist. each marked ¼ S. B. T.

52.00 Spring branch 2 lks wide flows W.

70.00 Ridge bears E and W.

80.00 Set a line stone 16 x 6 x 6 ins. 11 ins. in ground for cor. to sec's. 4, 5, 8 and 9 marked 4 notches on E and 5 on S edges from which An aspen 8 ins. diam. bears S 40° W 168 lks dist.

An aspen 8 ins. diam. bears N 67° W 360 lks dist.

An aspen 9 ins. diam. bears N 23½° E 171 lks dist.

An aspen 3 ins. diam. bears S 50° E 160 lks dist. each marked with the proper Tp. Rg and Sec.

Land mountainous.

Subdivisions T 36 S

Chs. Soil 2nd rate.
Heavily timbered on 79.00 ch

East on a random line
bet. sec's. 4 and 9
Var. 15° 30' E
40.00 Left temp. 1/4 sec. cor.
80.20 Intersect N and S line 25 lks
N of cor. to sec's. 3. 4. 9 & 10
from which I run N 89° 49'
on a true line bet. sec's 4 & 9
with Same Var.
9.04 Trail bears N W and S.E.
13.50 Ascend.
20.00 Ridge bears N and S.
29.00 Foot of ridge
40.10 Set Sand stone 26 x 14 x 3 ins.
17 ins. in ground for 1/4 sec. cor.
marked 1/4 on N face from which
A pine 16 ins. in diam. bears
S 30° E 26 lks dist.
A pine 9 ins. diam. bears
N 45° W 61 lks dist. each
marked 1/4 S.B.T.
A house bears S 7° 30' W

R 7

Chs. abo
ab
42.10 Sp
N
43.80 De
43.90 Ro
72.20 Ro
76.30 "
80.20 The
H

No
2.50 Fo
6.00 Ro
19.20
40.00 Se
10 i
mor
ran

BOOK-A-201

R 7 W. S. L. M.

chs. about 12 chs. dist.
A house bears S 31½° W
about 16 chs. dist.
42.10 Spring branch 3 lks wide flows N.
43.80 Ditch flows N.
43.90 Road bears N and S.
72.20 Road bears N.W. & S.E.
76.30 " " " "
80.20 The cor. to sec's. 4. 5. 8 and 9.
Land rolling.
Soil 1st & 4th rate.
Heavily timbered on 80.20 chs.

North bet. sec's. 4 and 5.
Var. 15° 30' E.
2.50 Foot of mountain.
6.00 Road bears N.W. & S.E.
19.20 " " N E & S W.
40.00 Set volcanic stone 15 x 12 x 10 ins.
10 ins. in ground for ¼ sec. cor.
marked 4 on W face and
raised a stone mound
alongside.

Subdivisions T36 S

Chs.
57.20 Creek 15 l'ks wide flows E
81.00 West bank of Panguitch lake
set a block lava stone 18x10x
8 ins. 12 ins. in ground for
meander corner to fractional
sections 4 and 5 marked M.C.
and raised a stone mound
alongside.

Land rolling.
Soil 1st rate.
March 11 th 1884.

From the cor. to sec's. 31 and
32 on the S bound. of the
Tp. previously set by me 9
run north bet. sec's. 31 and 32
Var. 15° 30' E.

5.00 Trail bears N W and S. E.
7.00 Mammoth Ck 25 links wide ds S.E.
35.25 Hollow drains S W.
40.00 Set granite stone 18x11x3 ins.
12 ins. in ground for 1/4 sec. cor.
marked 1/4 on W face and raised
a stone mound alongside.

R 7

Chs.
61.00
80.00

BOOK-A-201 257

R 7 W. S. L. M.

Chs. A pine 36 ins. diam. bears W 55 l'ks dist.

A pine 8 ins. diam. bears N 36° E 12 l'ks dist. each marked 1/4 S. B. T.

61.00 Ridge bears N W and S E.

80.00 Set a sand stone 30 x 10 x 8 ins. 20 ins. in ground for cor. to sec's. 29. 30. 31. and 32 marked 5 notches on E and 1 on S edges from which

A pine 26 ins. diam. bears S 75° E 8 l'ks dist.

A pine 9 ins. diam. bears S 40° W 50 l'ks dist.

A pine 7 ins. diam. bears N 45° W 55 l'ks dist.

A pine 10 ins. diam. bears N 7° E 30 l'ks dist each marked with the proper Tp. Rg and Sec.

Land broken.

Soil 1st and 4th rate.

Heavily timbered on

80.00 chs.

Subdivisions T 36 S.

Chs. East on a random line bet. secs. 29 and 32
Var. 15° 30' E.

40.00 Set temp 1/4 sec. cor

79.60 Intersect N and S line 23 lks N of cor. to secs. 28. 29. 32 & 33 from which I run N 89° 30' W on a true line bet. secs. 29 and 32 with same Var.

4.50 Ridge bears N and S.

7.50 Hollow drains S E.

21.50 Ridge bears N and S.

33.00 Hollow drains N. E.

36.50 Ridge bears N and S.

39.80 Set a black lava stone 30 x 24 x 14 ins 20 ins. in ground for 1/4 s. cor. marked 1/4 on N face from which a pine 8 ins. diam. bears S 3° W 26 lks dist.
A pine 4 ins. diam. bears N 6° W 19 lks dist. each marked 1/4 S. B. T.

44.23 Hollow drains S E.

60.00 Ridge bears N and S.

R 7 W. S. L. M.

chs.
73.00 Canon drains N W.
79.60 The cor. to sec's 29, 30, 31 & 32
Land mountainous.
Soil 2nd and 3rd rate.
Mountainous and heavily
timbered on 79.60 chs.

West on a random line
bet. sec's. 30 and 31
Var. 13° 30' E.

40.00 Set temp. 1/4 sec. cor.
80.60 Intersect N bound of Tp.
1.40 chs S of cor. to secs. 30 & 31
from which I run S 89° E on
a true line bet. sec's. 30 & 31
with same Var.
5.00 Ridge bears N and S.
16.70 Wash drains S.
35.00 Trail bears N and S.
40.60 Set a sand stone 14 X 10 X 10 ins.
10 ins. in ground for 1/4 sec. cor.
marked 1/4 on N face from which
a pine 10 ins. diam. bears

Subdivisions T 36 S.

Chs N 31° W 30 lks dist.
A pine 5 ins. diam bears
S 32° E 14 lks dist each
marked ¼ S. B. T.
66.00 Ascend.
74.00 Ridge bears N. W. and S. E.
80.60 The cor. to secs. 29. 30. 31 & 32
Land rolling mountains.
Soil 2 nd rate.
Heavily timbered on 80. 60 chs

North bet. secs. 29 and 30
Var. 15° 30' E.
20.00 Basin drains N.
40.00 On ridge bears E + W set a
sand stone 16X10X9 ins. 11 ins. in
ground for ¼ sec. cor. marked
¼ on W face from which
A pine 10 ins diam. bears
E 30 lks dist.
An aspen 7 ins. diam. bears
N. 50 lks dist. each marked
¼ S. B. T.
60.00 Ravine drains SW

R 7 W. S. L. M.

Chs.
64.50 Ridge bears E & W.
71.90 Trail in hollow bears N E & S W.
78.00 Ridge bears E and W.
80.00 Set lava stone 16x14x6 ins. 11 ins. in ground for cor. to sec's. 19. 20. 29 and 30 marked 5 notches on E and 2 on S edges from which
W pine 24 ins. diam. bears S 45° W 50 lks dist.
An aspen 7 ins diam bears N 30° W 30 lks dist.
An aspen 3 ins. diam. bears N 10° E 28 lks dist.
An aspen 3 ins diam bears S 40° E 10 lks dist each marked with the proper Tp. Rg and Sec.
Land mountainous.
Soil 1st and 4th rate.
Mountainous and heavily timbered on 80.00 chs.

Subdivisions T 36 S

Chs. East on a random line
bet secs. 20 and 29.
Var. 13° 30' E.

40.00 Set temp 1/4 sec. cor.

80.60 Intersect N and S line,
75 lks N of cor. to secs. 20, 21
28 and 29 from which I run
N 89°28' W on a true line
bet. secs. 20 and 29
with same Var.

40.30 Set volcanic rock 18 x 12 x 10
ins. 12 ins in ground for 1/4 sec.
cor. marked 1/4 on N face and
raised a stone mound alongside

52.00 Enter timber.

74.50 Trail bears N and S ft.

80.60 The cor. to secs 19, 20, 29 & 30
Land broken.
Soil 2nd and 4th rate.
Heavily timbered on
28.60 Chs.

R

Chs. N
b

40.00 S.

80.90 T.
33
30
E
19
w
T
40.40 S.
12
fro
be

N
1/4

72.00 T.

80.90 Th

Jem

BOOK-A-201 537

R 7 W. S. L. M.

Cha West on a random line
bet. sec's. 19 and 30
Var. 15° 30' E.

40.00 Set temp. 1/4 Sec. cor.

80.90 Intersect N bound. of Tp.
33 lks S of cor. to sec's. 19 and
30 from which I run S 89° 46'
E on a true line bet. sec's.
19 and 30
with same Var.
Throug timber and undergrowth.

40.40 Set lime stone 18 X 12 X 12 ins.
12 ins. in ground for 1/4 sec. cor.
from which a pine 9 ins. diam.
bears S 30° E 14 lks dist.
A pine 14 ins. diam. bears
N 24 lks dist. each marked
1/4 S. B. T.

72.00 Trail bears N. E. & S. W.

80.90 The cor. to sec's. 19. 20. 29 & 30.
Land rolling
Soil 2nd rate.
Heavily timbered and
dense undergrowth on 80.90 chs.

Subdivisions T 36 S

Chs. North bet. secs. 19 and 20.
Var. 15° 30' E.

5.00 Hollow drains N.E.

14.00 Trail bears N E & S W.

30.00 Ridge bears N W and S.E.

32.40 A pine, blazed same

36.50 Trail bears N W and S.E.

40.00 Set lava stone 16 x 12 x 7 ins. 11 ins. in ground for ¼ sec. cor. marked ¼ on W face from which

An aspen 5 ins. diam. bears S 45° E 25 lks dist.

An aspen 6 ins. diam. bears N 80° W 25 lks dist. each marked ¼ S. B. T.

80.00 Set a lava stone 16 x 4 x 9 ins. 11 ins in ground for cor. to secs. 17. 18. 19 and 20 marked 5 notches on E and 3 on S edges from which

An aspen 8 ins. diam. bears S 30° E 55 lks dist.

An aspen 7 ins. diam. bears N 40° W 76 lks dist. each marked with the proper Tp. Rge.

R 7 W. S. L. M.

Chs. No other tree within limits, raised a stone mound alongside
Land rolling lava bed
Soil 4th rate
Timber scattering on 80.00 chs.

East on a random line bet. secs. 17 and 20
Var. 15° 30' E

40.00 Set temp. 1/4 sec. cor.
80.60 Intersect N and S line 40 lks N of cor. to secs. 16. 17. 20 & 21 from which I run N 89° 43' W on a true line bet. secs 17 and 20 with same Var.
44.30 Set volcanic rock 30 x 18 x 12 ins 20 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.
41.75 Trail in canon bears N W.
75.00 Enter timber.
80.60 The cor. to secs 17. 18. 19 & 20.

Subdivisions T 36 S

Chs. Land broken
Soil 4th rate.
Heavily timbered on 5.60 chs.

West on a random line
bet. sec's. 18 and 19
Var. 15° 30' E.

40.00 Set temp. ¼ Sec. cor.

80.85 Intersect W boundary of Tp.
at cor. to sec's. 18 and 19 from
which I run E on a true
line bet. sec's. 18 and 19
with same Var.

35.00 Ridge bears N W and S.E.

40.85 Set sandstone 14x10x10 ins.
10 ins. in ground for ¼ sec. cor.
marked ¼ on N face from which
a pine 7 ins. diam. bears.
N 30° W 16 l'ks dist.
a pine 17 ins. diam. bears
S 19 l'ks dist each marked
¼ S.B.T.

60.00 Trail bears N and S.

BOOK-A-201 561

R 7 W. S. L. M.

Chs.
80.85 The cor. to sec's. 17. 18. 19 and 20.
Land broken mountains.
Soil 3rd rate.
Heavily timbered on 80.85 chs.

North bet. sec's. 17 and 18
Through Var. 15° 30' E.
Undergrowth.
40.00 Set lava stone 15 X 10 X 6 ins.
10 ins. in ground for 1/4 sec. cor.
marked 1/4 on W face and raised
a stone mound alongside.
An aspen 5 ins. diam. bears
N 55° 30' E 18 lks dist.
An aspen 7 ins. diam. bears
S 16° W 96 lks dist. each marked
1/4 S.B.T.
62.80 Trail bears N W and S.E.
80.00 Set a lime stone 15 X 10 X 9 ins.
10 ins. in ground for cor. to sec's.
7. 8. 17 and 18 marked 5 notches
on E and 4 on S edges from which
A pine 9 ins. diam. bears.
S 31° E 114 lks dist. marked

Subdivisions T 36 S

Chs. T36S. R 7W. S. 17 B.T.
No other tree convenient to mark raised a stone mound alongside.
Land nearly level
Soil 2nd and 3rd rate.
Dense undergrowth on
80.00 chs.

East on a random line bet. sec's. 8 and 17
Var. 15°30' E.
40.00 Set temp. 1/4 Sec. Cor.
80.30 Intersect N and S line 43 lks S of cor. to sec's. 8. 9. 16 & 17 from which I run S 89°42' W on a true line bet. sec's. 8 and 17 with same Var.
35.00 Descend, enter timber.
40.15 Set volcanic rock 16 x 14 x 10 ins. 11 ins. in ground for 1/4 sec. cor. marked 1/4 on N face from which a quadringasp 7 ins. drow.

R 7 W. S. L. M.

Chs. bears N 75 lks dist.
A quotingasp 6 ins. diam.
bears S 10° W 132 lks dist.
each marked 1/4 S.B.T.

51.00 Ridge bears N and S. leave timber.

80.30 The cor. to secs. 7. 8. 17 and 18
Land mountainous.
Soil 2 nd and 4 th rate.
Heavily timbered on 16.00 chs.
Heavy " Mountains on 80.30 chs.
March 12. 1884.

West on a random line
bet. secs. 7 and 18
Var. 15° 30' E.

40.00 Set temp. 1/4 sec. cor.

80.90 Intersect W boundary of
Tp. 10 lks S of cor. to secs
7 and 18. from which I run
S 87° 56' E on a true line bet.
secs. 7 and 18
with same Var.

Subdivisions T36 S

chs.	
20.00	Leave timber.
22.32	Fence bears N W and S E. enter meadow
39.20	Fence bears N 1°30' W, leave meadow
40.90	Set a charred post 4 ins. square 12 ins. in ground marked ¼ S on N face, dug pitts and raised a mound of earth and stone around post. Samuel Henries house bears N 31° E about 20.00 chs. dist.
64.00	Road bears N and S.
66.50	Creek 25 lks wide flows N.
70.50	Road bears N and S.
80.90	The cor. to secs. 7. 8. 17 and 18 Land level. Soil 1st rate. Heavily timbered on 20.00 chs.

Chs.	
10.00	
15.00	
18.50	
31.50	
40.00	
46.90	
54.00	
56.05	
75.00	
77.50	
80.00	

R 7 W. S. L. M.

Chs. North bet. sec's. 7 and 8.
Var. 15° 30' E.

10.00 Ascend.
15.00 Enter timber.
18.50 Ridge bears N E & S. W.
31.50 Road bears N E & S W.
40.00 Set quartzite 15 x 10 x 4 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on W face from which
A pine 36 ins. diam. bears S 40° W 10 lks dist.
A pine 4 ins. diam. bears S 45° E 60 lks dist. each marked 1/4 S. B. T.
46.90 Creek 20 lks wide flows N E.
54.00 Ridge bears S.E. and N.W.
56.05 Wash drains S.E.
75.00 Ridge bears N E and S W.
77.50 Hollow drains S.W.
80.00 Set lava stone 18 x 8 x 8 ins. 12 ins in ground for cor. to sec's. 5. 6. 7 and 8 marked 5 notches on E and 5 on S edges from which

Subdivisions T 36 S

chs. A pine 24 ins. diam. bears S 35° W 60 lks dist.

A pine 10 ins. diam. bears N 45° 30' W 70 lks dist

A pine 12 ins. diam. bears N 35° E 90 lks dist.

A pine 26 ins. diam. bears S 77° 30' E 100 lks dist. each marked with the proper Tp Rg and Sec.

Land mountainous.

Soil 1st and 3rd rate.

Heavily timbered on 65.00 chs.

Heavy mountains on 70.00 chs.

East on a random line bet. secs. 5 and 8

Var. 15° 30' E.

40.00 Set temp. 1/4 sec. cor.

80.70 Intersect N and S line 18 lks N of cor. to secs. 4. 5. 8 and 9 from which I run N 89° 52' W on a true line bet. secs. 5 & 8

R 7 W. S. L. M.

chs. with same Var.
8.50 Leave timber.
16.60 Road bears N W and S E.
32.50 Enter timber.
35.00 Ridge bears N E and S. W.
40.35 Set flint stone 14x10x4 ins. 10 ins in ground for 1/4 sec. cor. marked 4 on N face, from which
A pine 20 ins. diam. bears N 40° E 50 lks dist.
A pine 14 ins. diam. bears S 37 lks dist. each marked 1/4 S.B.T.
40.70 Road bears N E and S W.
46.00 Descend abruptly.
48.70 Blue spring Cr. 20 lks wide flows N E.
72.00 Ridge bears N E and S W.
80.70 The cor. to sec's. 5. 6. 7 & 8.
Land mountainous.
Soil 2nd rate.
Heavily timbered on 56.70 chs.
Heavy Mountains on 80.70 chs.

Subdivisions T36S

Chs. West on a random line bet. sec's. 6 and 7
Var. 15°30' E.

40.00 Set temp. ¼ Sec. Cor.

80.10 Intersect W boundary of Tp. 33 N of cor. to sec's. 6 and 7 from which I run N 89°46' E on a true line bet. sec's. 6 & 7 with same Var.

25.00 Ridge bears N W and S E.

40.10 Set a granite 16x10x4 ins. 11 ins. in ground for ¼ sec. cor. mark ¼ on N face from which
An aspen 5 ins. diam. bears S 45° E 15 lks dist.
An aspen 5 ins. diam. bears N 80° E 10 lks dist. each marked ¼ S. B. T.

49.00 Road, in hollow, drains S.E.

70.00 Ridge bears N E and S W.

80.10 The cor. to sec's. 5. 6. 7 & 8
Land mountainous.
Soil 2nd rate.
Mountainous and heavily timbered on 80.10 chs.

BOOK-A-201

569

R 7 W. S. L. M.

Chs. North bet. secs. 5 and 6
Var. 15° 30' E.

5.40 Ridge bears E and S W.

34.10 Head of ravine drains N. E.

40.00 Set lava stone 14X10X8 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on W face from which a pine 20 ins. diam. bears N 45° E 10 l'ks dist.
A pine 3 ins. diam. bears S 11° W 30 l'ks dist. each marked 1/4 S. B. T.

69.00 Leave timber.

81.30 Road bears N W and S. E.

83.90 Intersect 7th stand. Par. S. 14.05 chs. E of standar. Cor. to secs. 31 and 32. T 35 S. R 7 W. At point of intersection set lime stone 14X14X10 ins 10 ins. in ground for closing corner to secs. 5 and 6. marked CC with 5 notches on E and 1 on W edges and raised a stone mound alongside.

570

Subdivisions T 36 S. R 7 W. S.L.M.

Chs. Land rolling mountains.
Soil 1st and 3rd rate.
Heavily timbered on 69.00 chs.
March 13th. 1884.

BOOK-A-201

S.L.M.

Meanders of Pauguitch Lake T36S. R 7W.

Chs. I begin at the meander cor. to fractional sections 5 and 32 on the 7th Stand Par. S. and run

S 53°30' E 5.20 chs.

to the meander cor. to fractional sections 4 and 5 thence in sec. 4

Var. 15°30' E.

S 12°30' E	15.00 chs.
S 43¼ E	16.50 "
N 16°45' E	9.00 "
S 20° E	5.50 "
N 76°30' E	3.56 "
N 40° E	3.00 "
S 55° E	1.60 "
S 20° W	5.00 "
S 50°30' W	2.50 "
S 4°45' E	9.20 "
S 84° E	9.50 "
N 67½° E	7.25 "
S 81° E	18.00 "
N 75° E	6.70 "
S 85° E	10.90 "

...00 chs.
...84.

572

Meanders of Panguitch Lake

Chs. S 67¼° E 5.40 chs. to the meander cor. to fract. sections. 3 and 4.

Thence in Sec. 3.

Var. 15° 30' E.

N 83° E 19.50 chs.

N 41° E 16.17 "

N 13° E 15.00 "

N 12° W 13.50 " to meander corner of fractional sections 3 and 34 on the Seventh Stand. Par. S.

Land along lake level. Soil 1st Rate

Dense willow undergrowth.

on 2nd 37 chs 98 lks

March 14, 1884

BOOK-A-201 573

T 36 S. R 7 W. S. L. M.

General Description.

The southern portion of this Tp. is mostly mountainous and broken, having little agricultural land.

It is covered with an excellent growth of timber.

The land around Panguitch lake is good agricultural land

The applicant for the survey of this township Mr. Samuel Henrie has improvements in secs. 7 and 18, consisting of a meadow, house, barns and stock yard.

There is a cultivated field and a large meadow is sec. 5, belonging to Messrs. Prince, Imley and Paddock, there is also a meadow is section 4 belonging to Mr. Montague.

5174

Parts of the township is well watered and affords good grazing.

U. S. Dep. Surveyor.

575

BOOK-A-201

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, June 28th 1887

The foregoing field notes of the survey of the .....

Subdivisions & Meanders of Panguitch Lake.

Township No. 36 S *Range No.* 7 W.

Executed by Shadrach M. Richardson

Under his *contract* no 123 *of the* 19th

day of December 1883, *in the month of*

March 1884, *having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

Fred Salomon

U. S. Surveyor General for Utah.

Subdivisions T 35 S

Chs.		Chs.
	East on a random line bet. secs. 5 and 8	
	Var. 15° 30' E.	
40.00	Set temp. 1/4 sec. cor.	40.00
80.10	Intersect N and S line 7 lks north of cor. to secs. 4. 5. 8 & 9. from which I run N 89° 57' W on a true line bet. secs. 5 and 8 with same Var.	79.80
16.00	Cañon, drains N.W.	12.00
40.05	Set volcanic stone 18 x 12 x 8 ins. 12 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside.	21.00
		38.00
		39.80
	A quaking asp. 5 ins. diam. bears N 83° W 23 lks dist. marked 1/4 S	
45.75	Spring branch 5 lks wide in Cañon drains S.	42.00
80.10	The cor. to secs. 3. 6. 7 & 8.	50.00
	Land mountainous.	60.00
	Soil 3rd rate.	79.80
	Mountainous and dense undergrowth on 80.10 chs.	

BOOK-A-201 #65

R 7 W. S. L. M.

Chs.	
	West on a random line bet. secs. 6 and 7.
	Var. 15° 30' E.
40.00	Set temp. 1/4 sec. cor.
79.80	Intersect West bound. of Tp. at cor. to secs. 6 and 7 from which I run East on a true line bet. secs. 6 and 7 with same Var.
12.00	Wash drains S.
21.00	" " "
38.00	Road bears N and S.
39.80	Set volcanic stone 15 x 12 x 7 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on N face and raised a stone mound alongside. Spring bears S W about 5 chs.
42.00	Ascend.
50.00	Top of ridge bears S.W. & N.E.
60.00	Ravine drains S W.
79.80	The cor. to secs. 5. 6. 7 & 8.

Land mountainous.

Soil 1st and 3rd rate.

Mountainous and dense under-growth on 79.80 chs.

Subdivisions T 35 S

Chs.	
	North on a random line bet. sec's. 5 and 6. Var. 15° 30' E.
40.00	Set temp. 1/4 sec. cor.
80.75	Intersect N bound of Tp. 60 lks E of cor. to sec's. 5 and 6 from which I run S 0° 26' E on a true line bet. sec's. 5 and 6 with same Var.
3.00	Rovine drains S. E.
13.00	Ridge bears S. E. & N. W.
23.50	Spring broad 10 lks wide in canon. drains E.
40.75	Set lava stone 15 x 10 x 8 ins. 10 ins. in ground for 1/4 sec. cor. marked 1/4 on W face and raised a stone mound alongside.
45.00	Ridge bears E and W.
67.00	Trail in rovine bears E & W.
80.75	The cor. to Sec's. 5. 6. 7 and 8. Land mountainous. Soil 2nd and 4th rate. Mountainous on 80.75 chs. Scattering timber and dense undergrowth on 80.75 chs. March 26/84.

BOOK-A-201

R 7 W. S. L. M.

Cha. Meanders of Pauguitch Lake
T 35 S. R 7 W S. L. M.

I begin at the meander cor. to fractional sections 3 and 34 on the south boundary of the Tp. which is a volcanic stone firmly set in the ground and properly marked and run the meanders in sec. 34.

Var. 15° 30' E.

N 32° W	7.50 chs.
N 43° 45' W	2.50 "
N 38° 15' W	3.00 "
N 2° 45' W	3.00 "
N 17° W	3.50 "
N 6° 30' W	2.90 "
N 12° E	6.00 "
N 32° 30' W	5.00 "

N 86° W 1.50 Pauguitch Cr. 15 lks wide flows N E. thence on same course to 17.00 chs.

N 73° 30' W	9.00 chs.
S 11° 30' W	8.50 chs.

Meanders of Paugnitch Lake

S 21° 31' E 7.00 chs.
N 87° 30' W 8.80 " to
meander cor. to fractional
sections 33 & 34 which is
a stationary boulder properly
marked.

Land level.
Soil 1st rate.

Thence in sec. 33.
Var. 15° 30' E.
N 85° W. 13.50 chs.
S 56° W. 23.00 chs.
N 36° W 15.50 chs.
S 71° W 18.00 "
S 39° W 18.20 " to
meander corner to fractional
sections 4 and 33 which
is a sandstone firmly set
in the ground and properly
marked.

Land level
Soil 1st rate.
Fence with wounds generally found 2m 11chs 90lks
March 27th. 1884.

BOOK
935

More formation marked on subdivision plat

BOOK-A-201

469

T35 S. R 7 W. S. L. M.

General Description.

This township consists largely of mountain ridgs.

It contains good agricultural and grazing land and is well watered

The applicant for survey Mr. George Dodds has improvements in secs. 13 & 24, then consist of a cultivated field meadow and houses.

Mr. Epson's improvements are situated in section 33 on Pangnitch lake.

There are ranches in sections 31, 34 and 35.

U. S. Dep. Surveyor.

More information wanted about this lake

469 E

BOOK-A-201

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, June 28th 1884

The foregoing field notes of the survey of the Subdivisions & Meanders of Pauguitch Lake

Township No. 35 S Range No. 7 W

Executed by Shadrach M Richardson.

Under No. 123 contract of the 19th

day of December 1883, in the month of March 1884, having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.

Fred Salomon

U. S. Surveyor General for Utah.

BOOK-A-201

9

470

REPORT: 1884

Filed 188

Examined by .....

Transcribed by E. Michaelis

Compared by A. Kirson & Michaelis

FIELD NOTES

OF THE SURVEY OF THE

East, South & West boundaries

OF

Township No 36 South.

Range No 7 West

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Shadrach M. Richardson

U. S. Deputy Surveyor,

Under his Contract No. 123.

Dated December 19th 1883

Survey commenced March 4th 1884

Survey completed " 6th 1884

V

BOOK-A-201

472

R 7 W. S. L. M.

chs.	
	marked ¼ on W face
	A pine 5 ins. diam bears N 88° W 35 lks dist.
	A pine 5 ins. diam bears N 20° E 66 lks dist. each marked ¼ S. B. T.
50.00	Hollow drains S.W. ascend
77.00	Top of abrupt ascent
80.00	Set a lime stone 14 X 10 X 8 ins. 10 ins. in ground for corner to secs. 19. 24. 25 and 35 marked 4 notches on N and 2 on S edges.
	A pine 11 ins. diam. bears N 15° E 48 lks dist.
	A pine 16 ins diam. bears N 63° W 130 lks dist.
	A pine 6 ins. diam bears S 17° W. 80 lks dist.
	A pine 4 ins. diam bears S 62° E 38 lks dist. each marked with the proper Tp. Rg. and Sec.
	Land rolling mountains.