BOO

REPORT: 15

Filed

Examined by

Transcribed by

Compared by

F

OF TH

Poung

Township No

Range No 5

SALT

Shea

Under his

Dated Dec

Survey comm

Survey comp

BOOK-A-203

1

REPORT: 1885

Filed 188

Examined by John H. Cooper

Transcribed by H. H. Atkinson

Compared by O. E. Salomon & H. Atkinson

FIELD NOTES

OF THE Re SURVEY OF THE

Panguitch and Kanab Guide Meridian

OF

Township No 39 South

Range No 5 & 6 W

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Shadrach M. Richardson

U. S. Deputy Surveyor,

Under his Contract No. 123

Dated December 19th 1883

Survey commenced May 24 1884

Survey completed May 24 1884

NAMES AND DUTIES OF ASSISTANTS:

Compassman.

Chainman.

Chainman.

Chainman.

Chainman.

Axeman.

Axeman.

Flagman.

BOOK-

We Richa

John E Coo

do solemnly s

fully execute t

we will level

even ground a

sticking or d

report the true

the true lengt

measuring, to

and in accord

in the survey

T.

of the Salt Lak

tory of Utah.

Richa

Ev

John

O.

Subscribed and

day of Ma

[2.—PRELIMINARY OATHS OF CHAINMEN.]

We Richard Keal, E. V. Haney, John E. Cook and Oscar Swanger do solemnly swear that we will well and faithfully execute the duties of chain carriers; that we will level the chain upon even and uneven ground and plumb the tally pins, either by sticking or dropping the same; that we will report the true distance to all notable objects, and the true length of all lines that we assist in measuring, to the best of our skill and ability, and in accordance with instructions given us, in the survey of ~~the~~ T. 39 S. R. 6 W.

of the Salt Lake base and meridian in the Territory of Utah.

Richard his X mark Keal, Chainman.
E. V. Haney, Chainman.
John E. Cook, Chainman.
Oscar Swanger, Chainman.

Subscribed and sworn to before me this 24th day of May, 1884

Ernst Salomon
Notary Public

Blank

Page

Blank

Page

Resurvey Sanguitch & Kanab
Guide Meridian T39S bet Rs 5 & 6 W

Survey commenced May 24th 1884
From the corner to Tps 38 & 39
S Rs 5 & 6 W, I run South on
a random line bet said Rs
The variation of my compass
being 15° 20' E, I set temporary
half mile & mile corners at
each 40 & 80 chs and find
the line to be 6m 01ch 4lks long
and the falling to be 11 lks E
of the Cor to Tps 39 & 40 South
Rs 5 & 6 W, The correction for
the true line will therefore
be 17 links North per mile
and its course will be
practically the same. As most of
the corners were not to be found I commence
From the corner to Tps 39
& 40 S, Rs 5 & 6 W which is a
sandstone 18 x 12 x 8 ins firmly
set in the ground and
properly marked I run
North on a true resurvey
line bet secs 31 & 36

Reservoir Sanguitch & Kanab

Guide Meridian T39S bet Rs 5 & 6 W

with same va

40,00 Find old corner, a sandstone 10"x10"x6" above ground, marked 1/4 on W face, with stone mound alongside

69,30 Hollow dims W

80,00 Found old corner lying down reset same a sandstone 18"x12"x3" 12" in the ground for cor to sec 25, 30, 31 & 36 marked 5 notches on N & 1 on Sedges, Dug pits 24x12x12 ins in each sec 5 1/2 ft dist and raised a mound of earth 2 ft high 4 1/2 ft base alongside

From which

A cedar 5" in diam bears N 5° W 39 lks dist marked S 25 T39S R6W B T

A cedar 10" in diam bears N 40° E, 50 lks dist marked S 30 T39S R5W B T

No other free within limits

Land rolling

Resurvey Tanguitch & Kanab

Guide Meridian T39S bet Rs 5 & 6 W

Soil 1st rate
Heavy timber cedars on
80.00 chs

North on a true resurvey
line bet secs 25 & 30
Var 15° 20' E

40.00 No trace of old corner, Set a
sandstone 14" x 12" x 7. 10" in
the ground for 1/4 sec cor, marked
1/4 on W face and raised a
mound of stone alongside
from which
A Cedar 20" in diam
bears N 55° E 29 lks dist
marked 1/4 S B T

61.00 Trail in hollow drns NW
72.50 Road bears E & W
75.00 Wash in hollow drains W
80.00 No trace of old corner, Set a
Sandstone 20 x 10 x 6 ins 15"
in the ground for cor to secs
19, 24, 25 & 30, marked 4
Notches on N & 2 on Sedges

Resurvey
Panguitch & Kanab Guide
Meridian T39 S bet Rs 5 & 6 W

and raised a mound
of stone alongside
from which
A cedar 17" in diam
bears N 49° E 83 lks dist
marked S 19 T39 S R5 W
B T
A cedar 6" ins in diam
bears S 80° E 39 lks dist
marked S 30 B T
No other tree within
limits
Land undulating
cedar bench
Soil 2nd rate
Heavy Timber cedars
on 80.00 chs

North on a true resurvey
line bet secs 19 & 24
Var 15° 20' E
40.00 No trace of old corner, Set
a sandstone 12 x 8 x 5 ins
8 ins in the ground for

BOOK-
Resurvey
Guide M

1/4 sec
& rai
along
A
bear
S
80.00 No
a sa
15" in
Secs
notch
raised
along
No
lin
La
So
Hc
80.
North
line
40.00 Foun

Resurvey Pauguitch & Kanab
Guide Meridian T39S, Rs 5 & 6 W

1/4 sec cor marked 1/4 on W face
& raised a stone mound
alongside, from which
A cedar 12" in diam
bears S 65° E marked 1/4
S B T 35 lks dist other trees too
small to mark

80,00 No trace of old corner, Set
a sandstone 20 x 12 x 6 ins
15" in the ground for cor to
Secs 13, 18, 19 & 24 marked 3
notches on N & S edges and
raised a mound of stone
alongside
No suitable bearing trees within
limits
Land level
Soil 1st rate
Heavy timber Cedars on
80,00 Chs

North on a true resurvey
line bet secs 13 & 18
Var 15° 20' E

40,00 Found old corner, lying

Reservoir Paugnitch & Kanab Reservoir
Guide Meridian T39 S bet. Rs 5 & 6 W Guide

down, reset same a sandstone
10×10×6 ins 6 ins in the ground
for 1/4 sec cor, marked 1/4 on
W face & raised a mound of
stone alongside
42.50 Road bears E & W
52.00 Fence " E & W
80.00 Found old corner lying down
reset same a sandstone
11"×10", 5" 7 ins in the ground
for cor to secs 7, 12, 13 & 18
marked 2 notches on N
and 4 on Sedges, Deg
pits 24×12×12 in each
Sec 5 1/2 ft dist and raised
a mound of earth 2 ft high
4 1/2 ft base alongside
Land level
Soil 1st Brake
No timber

North on a true reservoir
line feet secs 7 & 12
Var 15° 20' E

40.00 Fo
res
20"
for
W
N
ra
1/2
43.50 Fe
N
oth
A
19
53.30 A
re
73.50 Se
74.50
80.00 No
Sa
in
1.6.
on
ra
al

Resurvey Taugnetch & Kanab
Guide Meridian T39 S, bet Rs 5 & 6 W

40.00 Found old corner overthrown reset same a sandstone 20"x6"x5" 14" in the ground for 1/4 sec cor, marked 1/4 on W face dug pits 18x18x12 in N & S of stone 5 1/2 ft dist and raised a mound of earth 1 1/2 ft high 3 1/2 ft base alongside

43.50 Fence corner on line bears N 70° W about 15 chs and the other N 35° E about 20 chs Robinsons house bears N E 19 chs dist

53.30 Kanab creek 10 lks wide runs S W

73.50 Fence bears S 55° E

74.50 " " S 54° E

80.00 No trace of old corner, set a sandstone 15x8x6 ins 10 ins in the ground for cor to secs 1, 6, 7 & 12 marked 5 notches on S and 1 on N edges and raised a stone mound alongside

Reservoir Panguitch & Kanab
Guide Meridian T 39 S bet Rs 5 & 6 W

Land level pasture
Soil 1st rate
No timber

North on a true reservoir line bet secs 1 & 6
Var 15° 20' E

1,50 Fence bears N 50° E & S 50° W
3,50 Road bears E & W
40,00 Old corner thrown down reset same a sandstone 18x10x6 ins 12 ins in the ground for 1/4 sec cor marked 1/4 on W face and raised a stone mound alongside
80,00 Found corner standing which is a conglomerate rock 5 15x10x8 above the ground. The corner to Tps 38 & 39 S, R 5 & 6 W, marked 6 notches on N S E & Wedges with a stone mound alongside

Land rolling
Soil 1st rate
No timber

May 24th 1884

General Description

See Subdivisions
Mudrach M. Richardson
U.S. Dep. Surveyor

Blank

Page

BOOK-A-203

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah. Feby 21 1885

The foregoing field notes of the survey of the Panguitch & Kanab Guide Meridian

Township No. 39 S *Range No.* 5 & 6 W

Executed by Shadrach M Richardson

Under his *contract* No 123 *of the* 19th

day of December 1883, *in the month of* May 1884, *having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

Fred Salomon

U. S. Surveyor General for Utah.

Blank

Page

BOOK-A-203

REPORT: 1885 19

Filed 188

Examined by .....

Transcribed by M. Atkinson

Compared by O. E. S. & M. A.

FIELD NOTES

OF THE SURVEY OF THE

North boundary

OF

Township No. 39 South

Range No. 6 West

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Shadrach M. Richardson

U. S. Deputy Surveyor,

Under his Contract No. 123.

Dated December 19. 1883

Survey commenced May 23d 1884

Survey completed May 23d 1884

NAMES AND DUTIES OF ASSISTANTS.

..... *Compassman.*

..... *Chainman.*

..... *Chainman.*

..... *Chainman.*

..... *Chainman.*

..... *Axeman.*

..... *Axeman.*

..... *Flagman.*

BOOK

North

From
S. R
a ra
sai
of m
I se
and
40 a
the
5 m
and
S. o
R.P.
the
be
per
roil

Su
188
Fr
5 & 6.
15 x
th

BOOK-A-205

North B'dy T. 39. S. R. 6 W. G. & S. R.

From the cor. to Tps. 38 and 39. S. Rs. 6 & 7 W. I run East on a random line between said townships the variation of my compass being 15° 20' E. I set temporary half mile and mile corners at each 40 and 80 chains and find the township line to be 5 miles 78 chs. 50 lks long and the falling to be 40 lks S. of the cor. to Tps. 38 & 39 S. Rs. 5 & 6 W. The correction for the true line will therefore be 6 2/3 lks S. and 1.50 lks W. per mile and its course will be S. 89° 57' W.

Survey commenced May 23d 1884.

From the cor. to Tps. 38 & 39. S. Rs. 5 & 6. W. which is a conglomerate stone 15x10x8 ins firmly set in the ground marked

2.

North Bdy T. 39 S. R. 6 W.

6 notched on N. S. & W. edges with a mound of stone alongside. Thence S. 89° 54' W. on a true line betw. secs. 1 & 36,

Va. 15° 20' E

15.00 Ridge descends S.

22.50 Ravine drs. S.

23.00 Enter cedar & pine timber, Leave dense sagebrush.

33.00 Ridge descends S.

40.00 Set sandstone 26 x 20 x 14 ins 20 ins in the ground for 1/4 sec. cor. marked 1/4 on N. face from which a cedar 9 ins diam. brs. N. 65° W. 40 lks. dist. marked 1/4 S. B. T. No other tree within limits, therefore raised a mound of stone alongside.

50.50 Canon drs S.

75.00 Ridge descends S. W.

80.00 Set sandstone 14 x 10 x 7, 9 in ground for cor. to secs. 1. 2. 35 & 36, marked

BOOK-A-203

Lake Lake Meridian.

1 notch on E & 5 notches on
W. edges, from which
a pine 14 ins in dia, bears S. 45° E.
30 lks dist marked.
T. 39 S. R. 6 W. S. 1 B. T.
a pine 10 ins in diam. bears
S. 85° W. 40 lks, dist, marked
T. 39. S. R. 6 W. S. 2 B. T.
No other tree within limits.
Land, mountainous & broken.
Soil, rock & gravel 3rd & 4th rate.
Heavy timber cedar & pine 57.00 chs
Dense undergrowth oak and
sagebrush on 23.00 chs.
Augmented on 80.00 chs

S. 89° 57' W. on a true line betw.
secs. 2 & 35
Va. 15° 20' E

15.00 Leave pine timber, enter dense sagebrush
40.00 Set sandstone 14 x 8 x 6 ins 9 ins
in the ground for 1/4 sec. cor.
marked 1/4 on N. face and
raised a mound of

North Bdy T. 39. S. R. 6 W.

stone alongside.

72.50 Trail in cañon brs. S. 30° W.

80.00 Set sandstone 14 x 10 x 4 ins 9 ins in the ground for cor. to secs. 2. 3. 34 & 35, marked 2 notches on E & 4 notches on W. edges and raised a mound of stone alongside.

Land, mountainous & broken.

Soil, rock & land 2d & 4th rate.

Heavy timber pines on 15.00 chs.

Dense undergrowth oak brush on 65.00 chs.

Augmented on 80.00 chs.

S. 89° 57' W. on a true line betw secs. 3 & 34

Va. 15° 20' E.

18.50 Road from Panguitch to Upper Kanab brs N.W. & S.E.

40.00 Set sandstone 14 x 6 x 6 ins, 9 ins in the ground for 1/4 sec. cor. marked 1/4 on N. face and raised a mound of stone alongside.

Chains

47.00

55.75

71.00

80.00

BOOK-A-203

Salt Lake Meridian

Chains	
47.00	Enter scattering Pine timber.
	Ridge trends N.
55.75	Ravine trs. N. W.
77.00	Ridge trends N.
80.00	Set Sandstone 14 x 12 x 7 ins. 9 ins. in the ground, for cor. to secs. 3. 4. 33 & 34 marked 3 notches on E. and 3 ~~notches on~~ W. ridges. from which
	A pine 14 ins. in diam. bears S. 81° W. 8 lks. dist. marked. T. 39. S. R. 6 W. S. 4. B. T.
	A pine 8 ins. in diam. bears S. 45° E. 12 lks. dist. marked T. 38 S. R. 6 W. S. 34. B. T.
	A pine 13 ins. in diam. bears S. 60° E. 15 lks. dist. marked T. 39 S. R. 6 W. S. 3. B. T.
	~~as~~ other tree convenient to mark ~~therefore~~ raised a mound of earth ~~and~~ stone alongside.
	Land rolling and broken.

6 N. boundry T39 S. R. 6 W.

Chains	Soil, rock and gravel 2nd & 4th rate.
	Scattering Pine timber on 33.00 chs.
Dense	Undergrowth ~~is~~ Oak brush on 80.00 chs.
	S. 89°57 W. on a true line bet. secs. 4 & 33.
	Va. 15°20 E.
3.00	Leave scattering pines
7.26	Cañon drs. N. E.
11.50	Road brs. N. E. & S. W.
	Enter scattering timber.
14.00	Corral 2.00 chains S. of line.
40.00	Set Volcanic stone 14 x 12 x 6 ins. 9 ins. in the ground for 1/4 sec. cor. marked 1/4 on N. face. no tree convenient to mark therefore raised a mound of earth and stone alongside.
41.50	Ridge descends N. E.

BOOK-A-203

Salt Lake Meridian.

Chains	
47.50	Canyon drs. N.
66.50	Ridge course N. W. & S. E.
68.70	Ravine drs. S.
66.00	Ridge descends S.
79.50	Scarce Timber.
80.00	Set volanic Stone 15x12x7 ins 10 ins. in the ground for cor to secs. 4. 5. 32 & 33. marked 4 notches on E. and 2 notches on W. edges. from which a pine 16 ins in diam. bears S. 45° E. 80 lks. dist. marked B.T. 32 S. B. 6 W. S. 4. B. T. no other tree within limit therefore raised a mound of earth and stone along side.

Land mountainous & broken.
Soil, Rock. 4th rate.
Scattering Pine timber on 71.00 chs.

Mountains on 80.00 chs.

Chains	Var 15° 20' E
40.00	Set temp 1/4 sec cor
80.10	Intersect E boundary of Tp 50 lks N of cor to secs 7, 12, 13 & 18 re-established by me under present contract, I adjust my chain to agree with former survey and run N 89° 39' W on a true line Var 15° 20' E
20.00	Kanab Creek (dry) drains S.
20.50	Fence N & S.
21.00	Road N & S ascend
23.50	Enter dense oak and sage brush with scattered cedars
40.12	No trace of old corner, Set a gray sandstone 18x14x12 ins 12 ins in the ground, marked 1/4 on N face for re-established 1/4 sec cor and raised a mound of stone alongside

BOOK-

Subdivi

Chains	
76.00	Ho
	Lea
80.25	The
	S
	Soi
	He
	4.00
	De
	& oa
	No
20.00	Le
40.00	No
	lin
	the
	ma
	pit
	5 1/2
	mi
	3 1/2
67.70	Co
	to

Salt Lake Meridian.

9 ins in the ground for cor. to secs. 5.6.31 & 32, marked 5 notches on E. and 1 on W. edges, from which a pine 12" dia. brs. N. 31° W. 50 lks. dist, marked T. 38 S. R 6 W. S 31 & B.T. a pine 16 ins dia. brs. S. 60° E 15 lks dist marked T. 39 S. R. 6 W. S. 5 B. T. No other tree within limit raised a mound of stone alongside.

Land, mountainous & broken.
Soil, rocks 4th rate.
Heavy timber pines on 73.50 chs
Mountain on 80.00 chs.

S. 89° 57' W. on a true line betw secs. 6 & 31.

Va. 15° 20' E.

Ravine drs S. Trail in cañon brs. N. & S.

17.50 Ridge descends S E.
22.20 Cañon drs. S E.
23.00 Board brs N W. & S E.
40.00 Ridge descends S W.

10. North Bdy T. 39 S. R. 6 W.

Set sandstone 14x10x8 ins, 9 ins in the ground for 1/4 sec. cor. marked 1/4 on W. face,
from which
a pine 8 ins dia. bears N. 10° E 8 lks dist, marked 1/4 S.B.
a pine 9 ins dia. bears S. 40° W. 15 lks dist. marked 1/4 S.B.
55.00 Cañon bears S.W.
78.00 Cor. to Tps. 38 & 39 S. Rs. 6 & 7 W. which is a limestone 6x14x6 ins firmly set in the ground marked 6 notches on N. S. E & W. edges with four bearing trees in the position and with marks as reported in the field notes establishing said corner.
Land mountainous and broken.
Soil, rocky & barren
Heavy timber, pines & cedars on 78.00 chs
Mountainous on 78.00 chs
May 23. 1884.

BOOK-A-203

11.

Salt Lake Meridian.

General Description
of subdivisions.

Shadrach M. Richardson
U. S. Deps. Surveyor

Blank

Page

BOOK-A-203 33

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, February 21 *1885.*

The foregoing field notes of the survey of the North Boundary

Township No. 39 South *Range No.* 6 West.

Executed by Shadrach M. Richardson

Under Contract No. 123 *of the* 19th

day of December *1882, in the month of*

May *1884, having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

Fred Lalomas

U. S. Surveyor General for Utah.

Blank

Page

BOOK-A-203

OK

35

REPORT: 1885

Filed 188

Examined by .....

Transcribed by Henry R. McAtkinson

Compared by H. Atkinson & E. Michaelis

FIELD NOTES

OF THE SURVEY OF THE

Subdivisions

OF

Township No 39 South

Range No 6 West

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Shadrach M. Richardson

U. S. Deputy Surveyor,

Under his Contract No. 123

Dated December 19th 1883

Survey commenced May 24th 1884

Survey completed May 31st 1884

BOOK-A-203

Panguitch and Kanab Guide Meridian

Township 39 S. R. 6 W.

29		28		26		24		23		22
6	122	5	99	4	83	3	68	2	52	1
121		119		97		82		66		50
7	118	8	96	9	79	10	64	11	49	12
117		115		93		78		63		47
18	113	17	91	16	77	15	61	14	46	13
112		110		90		75		60		44
19	108	20	89	21	74	22	59	23	43	24
107		105		87		73		57		42
30	104	29	86	28	72	27	56	26	40	25
102		101		85		70		55		39
31	100	32	84	33	69	34	54	35	38	36

Panguitch and Kanab Guide Meridian

8

Subdivision T39 S.R.6 W S L M

Preliminary to commencing this survey I run west on a blank line on south boundary of Sec. 36 and at 39.90 chs. found the 1/4 sec. cor. and at 80.03 chs. found the Sec. cor. ~~and at~~ My compass will therefore run the same line as the exterior boundaries and the chaining practically agrees.

Survey commenced with Saurt's improved Solar Compass May 24" 1884 I commenced at the cor to sec 1, 2, 35 and 36 on the South boundary which is a Sandstone 15 x 8 x 5 8 in in the ground with one notch on east 5 on west edge and mound of stones alongside.

Subdivisions T 39. S R 6 W. S L M.

Chains	Thence Trun	Sub. Chains
	Northern resurvey line bet. Secs. 35 & 36 Var 15° 20' East	
4.00	Ravine drains W.	
6.50	Trail bears [illegible]	
10.00	Enter scattering timber	
20.00	Ridge descends W	
40.00	Found corner a sandstone 12 x 9 x 4 ins. marked 1/4 on W face lying on ground reset [illegible] ins. in the ground for reestablished 1/4 Sec. cor and raised a mound of earth stone & longside	
40.10	Ravine drains W	40.00
50.00	Ridge descends W. Leaves timber	
55.00	Enter oak and sagebrush flat	80.20
63.00	Dry bed of Kanab Creek dro. S. 10° W	
66.75	Road bears N. 75° E and S. 75° W.	
71.75	Road bears S 10 W and N 10° E	
[illegible]	Cor. down Set limestone 14 x 8 x 4, 9 ins in the ground	

Sub. T 39 S. R. 6 W. S. L. M.

Chains For re-established cor to secs. 25 & 26, 35 & 36 marked 1 notch on S and 1 on E edges and raised a mound of stone alongside
Sand, level N. 25.00 chs
Broken S. 55.00 chs
Soil 1" & 2" rate
Scattering timber on 40.00 chs
Dense undergrowth of oak and sage brush on 25.00 chs.

East on a random resurvey line bet secs. 25 & 36
Var. 15° 20' E

40.00 No trace of old corner Set Temporary ¼ Sec. Cor.

80.20 Intersect east boundary of Tp 30 lks N of Cor. to secs 25, 30, 31 & 36 reestablished by me under present contract
I adjust my chain to agree with former survey

Subdivision T 39 S R 6 W S L W

	and run N 89° 47 W on a true line between Sec. 25 & 36 with same Var.
23.00	Trail in canyon drain N.W. ascend
45.00	Set Gray sandstone 16x10x4, 11 ins in ground for [illegible] 1/4 Sec. cor marked 1/4 on N. face and raised a mound of stone alongside
62.00	Ridge bears N.
64.00	Enter oak and sagebrush flat
75.00	Dry bed Kanab Creek drains S 40° W
77.00	Road bears N
80.00	The cor to secs 25, 30 31 & 36
	Sand Level and broken Soil 2nd rate
	Timber scattering cedars.
	Dense undergrowth oak and sage brush on 16.00 chs
	North bet secs 25 & 26
	Var 15° 20' E
16.00	Foot of hill leave dense oak

Subdivision T 39 S R 6 W. S L M

hains and sage
1.10 Enter scattering cedar
0.00 Found a lava stone 18x10x5
marked 1/4 on W face lying
on ground reset same
11 in deep for reestablished
1/4 and raised a mound
of stone alongside
7.50 Ridge descends S.
From this point a house
and corral bears N 44° E
3.00 Enter dense oak and sage brush
0.00 Corner down. Set a lava stone
19x12x3 in 11 ins in the ground
marked 2 notches on Sand
1 on E edges for reestablished
cor to secs 23.24, 25 & 26 and
raised a mound of stone
alongside
No bearing tree to be found
Sand level and mountain
Soil 1st and 2nd rate
Mountains on 64.00 chs
Timber. scattering cedars
Dense oak and sagebrush

Subdivision T 39 S. R 6 W S L M

Chains undergrowth on 23.00 cha
Augmented on 8000 chains
East on a random line
bet secs 24 and 25
Var 15° 20' E

40.00 Set temp 1/4 sec cor
80.10 Intersect E boundary of Tp
42 lks N of the cor to secs 19,
24, 25 & 30 reestablished
by me under present
contract
Tradjust my chain to
agree with former survey
and run
N 89° 42' W on a true
line bet. secs. 24 & 25
Var 15° 20' E

9.00 Enter hollow.
25.00 Road bears N W & S E
28.00 Fence bears N & S
30.00 Winslow's house bears 1.20 c
40.05 No trace of old corner, Set
a sandstone 14x10x6 in 9 ins
in the ground marked
1/4 on N face for reestablishe

Subdi
Chains
45.00
48.00
55.00
51.00
66.00
80.10
40.00

Subdivisions, T39 SR 6W S S M

Chains	1/4 sec cor and raised a mound of stone alongside
45.00	Fence bears NE & SW
48.00	Dry bed of Kanab crk. dra S 10 W
50.00	Road to Kanab bears NE & SW
51.00	Cabin 3 chs. South Silershouse bears S 15° 3 E 14 chs
66.00	Ascend enter dense oak and sagebrush
80.10	The cor to secs 23, 24, 25 & 26

Land Rolling
Soil 1st & 2nd rate
Timber scattering cedars
Dense undergrowth oak and sage on 14. 10 chs

North on a true resurvey line bet secs 23 & 24 [illegible] 15° 20' E

40.00	No trace of old corner set sandstone 15 x 10 x 3 ins 10 ins in the ground for 1/4 sec cor marked 1/4 on W face and raised a mound of stone alongside

Subdivision T 29 S R 6 W S L M

Chains		Chains
80.00	No trace of old corner or bearing trees. Set a limestone 16"x8"x8" 11" in the ground for cor. to secs 13, 14, 23 & 24 marked 1 notch on E and Cor. Sedges, dug pits 18, 18 x 12 ins in each sec 5½ ft. dist and raised a mound of earth 1½ ft high 3½ ft base alongside	
	Soil 1st & 2nd rate	4.00
	Land level and rolling	12.00
	Timber scattering cedars and pines	16.00
	Dense undergrowth of oak and sage brush on 80.00 chs	19.00
		25.00
		32.00
		45.59
	East on a random line bet secs 13 and 24 Var 15° 20' E	
4.00	Set Temp ¼ sec cor	45.00
80.19	Intersect E boundary Lp 60 lks N of cor to secs. 13, 19	80.19

Subdivision T 29 S. R 6 W S L M

Chains	18 & 24 re-established by me under present contract I adjust my chains to agree with former survey and run N. 89° 34' W on a true line bet. secs 13 & 24 Var 15° 20' E
4.00	Wash drains S W
12.00	Kanab creek drains S W dry
16.00	Road bears N. E & S. W
19.00	ascent
25.00	ridge bears S.
32.00	hollow drains S.
40.59	No trace of old corner Set gray sandstone 16 x 8 x 2 in. 19 ins in the ground marked 1/4 on N. d.c. for re-established 1/4 sec cor and raised a mound of stone alongside
45.00	Ascend Entered [illegible] oak and sagebrush
80.19	The cor to secs 13, 14, 23 &

Chains v 24

Land Rolling
Soil 2nd v 3rd rate
Timber scattering cedars
and pines
Dense undergrowth, oak
and sage on 35, 19 chs

North bet sec 13 v 14
Var 15, 20 E

31,00 Wash drains S. E
39,00 Round hill
40,00 No trace of old corner
Set sandstone 14 x 6 x 2
9 ins in the ground for
1/4 sec cor, marked
1/4 on N face and
raised a mound of
stone along side
55,00 Leave oak brush, enter
heavy cedars
84,00 Corner down reset
sandstone

BOOK-A-203

Subdivision T 39 S R 6 W S L M

Chains 16 x 10 x 6 ins 11 ins in the ground for cor to secs 11, 12, 13 & 14 marked 4 notches S. and 1 on E edge from which

A cedar 14 ins. diam bears S 58° W 30 lks dist. marked T 39 S R 6 W, S 14 B T

A cedar 9 in diam bears S 65° E 86 lks dist marked T 39 S R 6 W S 13 B T

A cedar 40 ins diam bears N 15° W 2.50 lks dist marked T 39 S R 6 W, S 11 B T

No other trees convenient to mark

Land nearly level

Soil 1st 2nd & 3rd rate

Heavy timber, cedars on 2500 chs

Dense undergrowth oak and sage brush on 55.00

Augmented on 8000 chains

East on a random line bet Secs 12 & 13

BOOK-A-205

Subdivisions T39 SR 6W S L M

Chains	
76.00	Hollow drains S enter heavy cedars
80.25	The cor. to secs. 11, 12, 13, & 14 Sand level & broken Soil 2nd and 3rd rate Heavy timber, cedars on 4.00 chains Dense undergrowth, sage & oak brush on 56.75 chains May 24th 1884
	North between Secs. 11 & 12 Var 15° 20' E
24.00	Leave heavy cedar timber
40.00	No trace of old corner, Set limestone 14 x 9 x 7 in 9 ins in the ground for 1/4 sec cor marked 1/4 on W face, dug pits 18 x 18 x 12 ins N & S of stone 5 1/2 ft dist and raised a mound of earth 1 1/2 ft high 3 1/2 ft base alongside
67.70	Cut off road from ranch to upper Kanab bears W E &

Subdivisions T 39 S. R 6 W. S L M

Chains	
78.00	Road from Ranch to Up per Kanab bears S E & N W leave heavy oak brush
80.00	Set bluish sandstone 16 x 9 x 5 ins 11 ins. in the ground for cor to secs 1, 2, 11 & 12 marked 1 notch on E and 5 on S edges and raised a mound of earth stone alongside
	Land rolling hills
	Soil 2nd rate
	Heavy timber cedars on 20.00 chains
	Dense undergrowth oak brush on 7300 chs.
	East on a random line bet. secs 1 and 12
	Var 15° 20' E
40.00	Set temp 1/4 sec cor
80.45	Intersect E boundary of Tp 79 lks S of cor to secs 1, 6, 7 & 12 re-established by me

Subdivisions T39SR6W 2Lm

under present contract
I adjust my chain to
agree with former sur-
vey and run
S.89°26' W on a true line
bet secs 1 & 12
Var 15° 20' E.

2.00 fence bears N & S.
6.00 Road bears N & S
7.00 House bears 2 chs N.
11.00 Road bears NE. & SW.
12.00 Wash drains S leaves potatoe patch
12.50 Fence N & S leave field
15.20 Road from Woolley's to Land N and S.
Enter dense oak and sage brush
26.00 Pass timber ridge, descends S about 20 chs
31.00 Hollow drains S
35.00 Ridge bears N and S.
41.22 No trace of old corner. Set sandstone 36"x20"x2", 27" in the ground for 1/4 Sec cor

Subdivisions T 39 S R 6 W, S L M

Chains	
	marked 1/4 on N face from which a pine
	a pine 10" in diam bears N 37° W 60 lks dist
	A pine 20" diam bears N S ~~37° W 60 lks dist~~ 85° W 90 lks dist each marked 1/4 S B T.
50.00	Descend Leave timber
63.00	Leave dense oak and sagebrush
80.45	The cor to secs 1, 6, 7 & 12
	Land nearly level
	Soil 2nd & 3rd rate
	Heavy timber, pines on 24.50 chs
	Dense undergrowth oak on 49.80 chs
	North on random line bet. secs. 1 and 2
	Var 15° 20' E

Subdivisi

Chains	
41.00	Set
61.25	Int
	Tp.
	35 &
	Iry
	S
5.00	Ria
41.25	No
	Set
	11 in
	1/4 s
	W fa
	mo
	side
	no
	ma
50.00	Lea
	oak
3.00	Lea
1.25	Cor
	He

Subdivisions T 39 S R 6 W. S L M

Chains	
41.00	Set temp 1/4 sec cor
81.25	Intersect N boundary of Tp. 1 ch E of cor to secs 35 & 36, 1 & 2 from which I run
	So 43' E bet. secs. 1 & 2
	Var. 15° 20' E
5.00	Ridge bears N E & S W
11.25	No trace of old corner Set limestone 16 x 8 x 8 ins 11 ins in the ground for 1/4 sec cor marked 1/4 on W face and raised a mound of stone alongside at foot of mountain no tree convenient to mark
50.00	Leave timber enter dense oak brush
53.00	Leave dense oak brush
71.25	Cor to secs. 1, 2, 11 & 12
	Land rolling
	Soil 1st and 3rd rate
	Heavy timber, pine on 50.00 chs

BOOK-A

Subdivisions T 39 S, R 6 W S L M

Chains	
	Dense undergrowth, oak brush on 3.00 chs
	Augmented on 53.00 chains
	From the cor to secs 2, 3, 34 & 35 which is a sandstone 5 x 12 x 4 in. above ground properly marked stone mound alongside and one bearing tree I run
	North bet. secs 34 & 35.
	Var 15° 20' E
2.00	Ascend
7.50	Leave cedars, enter oak brush
34.00	Top of low ridge E & W
40.00	Cor down, Set limestone 16 x 14 x 3 ins, 11 ins in the ground for re-established 1/4 sec. cor marked 1/4 on W face and raised a mound of earth and stone alongside
69.30	A cedar 12 in in diam
80.00	Corner down, Reset same a sandstone 18 x 12 x 4 ins

Subdivisi

Chains	
	12 in
	cor
	mar
	2 in
	a m
	side
	Sou
	Hea
	on
	Scar
	pine
	Oak
	72.
	Au
	Eab
	bet
	Desce
40.00	Set
79.80	Inte
	N of
	& 35

Subdivision T39 S R 6 W S L M

Chains 12 ins in the ground for cor to secs 26, 27, 34 & 35, marked 1 Notch on S. and 2 on Edges and raised a mound of stone along side.

Land rolling Mountains
Soil 1st & 2nd Rate
Heavy Timber, Cedar & Pine on 7.50 chs
Scatt. timber cedars and pine on 72.50
Dense undergrowth Oak and sarvis berry on 72.50 chains
Augmented on 80.00 chains
East on a random line bet Secs 26 & 35
Var 15° 20' E
Descend mountain
40.00 Set temp 1/4 sec cor
79.80 Intersect N and S line 74 chs N of the cor to secs 25, 26, 34 & 35
I adjust my chain

Subdivisions T39 S R 6 W S L M

Chains	to agree with former survey and run N 87° 28' W on a true line
	bet secs 26 & 35
	Var 15° 20' E
25.00	Ascend
40.00	Found corner laying down Reset same, a sandstone 22" & 6" x 6" 18 ins. in the ground for re-established 1/4 sec cor marked 1/4 on N face and raised a mound of stone alongside
	No bearing tree
80.00	The cor to secs 26, 27, 34 & 35
	Land mountainous
	Mountainous on 55.00 ch
	Scatt timber cedars & Pine
	Dense undergrowth sag & oak brush on 80.00 chs
	Soil 3rd Rate
	North between secs 26 & 2
	Var 15° 20' E
30.00	Wash in Cañon drains S E
40.00	No trace of old corner, Se

Subdivisions T 39 S R 6 W S.B.

sandstone 14 x 10 x 6 ins 9 ins in the ground for 1/4 sec. cor. marked 1/4 on W face and raised a mound of stone alongside

55.00 A hollow drains S W

60.00 Same hollow drains S E

80.00 No trace of old corner. Set limestone 18 x 14 x 6 ins. 12 ins in the ground, for cor to secs 22, 23, 26 & 27, marked 2 notches on E & S edges and raised a mound of stone alongside

Land rolling mountains

Soil 2nd & 3rd rate

Scatt timber cedars & pine

Dense undergrowth sage & oak brush on 80.00 chains

East on a random line bet secs 23 & 26

Var 15° 20' E

Subdivisions T39S R6W S.L.

Chains	
40.00	Set temp 1/4 sec cor
80.00	Intersect N & S line 30 lks N of the cor to secs 23, 24, 25 & 27 from which
	Trees
	N 9° 17' W on a bi[illegible] line bet secs 23 & 26
	Var 15° 20' E
10.00	Leave scattering cedar
14.00	Cañon drains S. E.
20.00	Enter scrub cedar
22.50	Ridge descends N
[illegible]	Leave cedar
40.00	Found old corner down reset same, a sandstone 18x10x4 12 ins in the ground for 1/4 sec cor marked 1/4 on N face and raised a mound of stone a longside
80.00	The cor to secs 22, 23, 26 & 27
	Land nearly level
	Soil 2nd Rate

Subdivisio

Chains	
	Scatt
	and
	Dens
	and
	North
[illegible]	Hollo
16.00	Enter
31.00	Ridg
35.00	Leave
40.00	Sear
	corne
	one,
	7 in 1
	for 1/4
	on N
	moun
45.25	Head
	Ceda
65.00	Leave
80.00	No tra
	Sand
	in th
	secs
	mar

Subdivisions T39SR6W S L M

Chains Scattering timber, pines and scrub cedar on 24.00 chs
Dense undergrowth oak and sagebrush on 80.00 chains
North bet secs 22 & 23
Var 15° 20' E
[illegible].00 Hollow drains E
16.00 Enter scrub cedar
31.00 Ridge descends E
35.00 Leave cedar
40.00 Searched diligently for corner failed to find one, Set sandstone 16x10x7 in 11 ins in the ground for 1/4 sec cor marked 1/4 on W face and raised a mound of stone alongside
45.25 Head of cañon drs SE. Enter Cedar
65.00 Leave cedar
80.00 No trace of old corner, Set Sandstone 15x10x7 10 ins in the ground for cor to secs 14 & 15 22 & 23 marked 2 notches on

Subdivision T 39 S R 6 W S L M

Chains	
	on E & 3 on S. edges and raised a mound of stone alongside
	Land rolling & broken Soil sandy 2nd Rate Timber scatt cedars on 38.75 chs.
	Dense undergrowth oak and sagebrush and sarvis-berry on 80 chains.
	East on a random line bet secs 14 & 23
	Var 15° 20' E
	Descend mountain
40.00	Set temp 1/4 sec cor
80.19	Intersect N & S line 42 lks S of cor to secs 13, 14, 23, &
	Thence I run
	S 89° 42' W on a true line bet secs 14 & 23
	Var 15° 20' E

Subdivisi

Chains	
40.09	No tr
	Set
	9 ins
	re-es
	mark
	raise
	alon
80.19	Corn
	La
	S
	Scat
	Dens
	and
	North
40.00	No tr
	Set
	ins
	sec c
	W fac
	of st
	of m
46.50	Ente

Subdivisions T 39 S R 6 W S L M

Chains	
40.09	No trace of old corner Set lime stone 14 x 9 x 7 ins 9 ins in the ground for re-established 1/4 sec cor, marked 1/4 on N face and raised a mound of stone alongside
80.19	Corner to secs 14, 15, 22 & 23 Land mountainous Soil 2nd 3rd Rate Scattering timber, cedars Dense undergrowth sage and oak brush on 80.19
	North bet secs. 14 & 15 Var 15° 20' E
41.00	No trace of old corner, Set sandstone 14" x 10" x 6" 9 ins in the ground for 1/4 sec cor marked 1/4 on W face and raised a mound of stone alongside at foot of mountain N.E & S.W
46.50	Enter heavy pine timber

Subdivisions T39 SR 6W S 1 m

Chains	
65.00	Ridge bears N E
72.00	Ravine drains N W.
74.50	Ridge descends N W
80.00	No trace of old corner
	Set limestone 16 x 10 x 7
	11 ins in the ground for cor
	to secs 10.11.14 & 15 marked
	4 notches S and 2 on E
	edges from which
	A pine tree 30 ins in diam
	bears N 46° E 40 lks dist
	Marked T39 S R 6 W S11 B T
	A pine tree 4 ins diam
	bears S 54° E 20 lks dist
	Marked T39 SR6W, S14 B T
	A pine tree 5 ins diam bears
	N 57 W, 60 lks dist marked
	T 39 SR 6W, S 10 B T
	A pine tree 24 in diam bears
	S 82° W 65 lks dist marked
	T 39 S R 6W, S 15 B T
	Land mountainous & broke
	Soil sandy & rocky
	" 2" & 4" rate

Subdivi

Chains	
	Hea
	cha
	Den
	& sa
	Eas
40.00	Set
80.17	Inf
	S of
	13 &
	S 8
	bet
20.00	J W
	3 00
25.00	Lea
40.08	No
	Se
	x 4
	for

BOOK-A-203

Subdivisions T 39 S R 6 W. S L M

Chains Heavy Limber pines on 33.50 chains
Dense undergrowth oak & sage brush on 80.00 chs
May 26th 1884

East on a random line bet secs 11 and 14
Var 15° 20' E

40.00 Set temp 1/4 sec cor
80.17 Intersect N & S line 80 lks S of the cor to secs 11, 12, 13 & 14
Thence I run
S 89.26 W on a true line bet secs 11 & 14
Var 15° 20' E

20.00 J W Semons coal mine 300 lks S of line
25.00 Leave dense oak and sage brush
40.08 No trace of old corner
Set a limestone 14 X 10 X 4 ins 9 ins in the ground for 1/4 sec cor, marked

Subdivisions T39 SR6W S.S.M.

Chains	
	1/4 on N face from which A cedar 8 ins. in diam bears S 46° W. 70 lks dist marked 1/4 S B T
55.00	Enter pine, scrub cedar & dense undergrowth at foot of precipitous ridge Ascend, more gradual
78.50	Divide bet Kanab and Long Valley Creeks, bears N 20 E and descend
80.17	The cor to secs 10, 11, 14 and 15 Land rolling Mountain Soil 1st rate Scatt Timber, Pine & Scrub Cedar Dense undergrowth sage and oak brush on 50.17 chains
	North bet secs 10 & 11 Var 15° 20' E
20.00	Leave scattering timber
30.00	Foot of hill, Enter land gently sloping N.

BOOK

Subd

Chains	
	Lea
55.50	Roa
	ch
41.00	Se
	in
	m
	ra
	al
57.60	Fo
	W
	En
66.75	Ri
76.00	Ho
80.00	Se
	9
	co
	5
	an
	st
	Sc
	sc
	D

Subdivisions T 39 S R 6 W S L M

Chains	
	Leave dense oak and sage brush
5.50	Road bears S W and N E 2.50 chains Thence North
40.00	Set limestone 16 x 8 x 8 ins 11 ins in the ground for 1/4 sec cor marked 1/4 on W face and raised a mound of stone alongside
57.60	Forks of road bears N 30° W N 80° W & S 80° E
	Enter dense oak brush
66.75	Ridge descends W
76.00	Hollow drains S W
80.00	Set sandstone 14 x 10 x 5 ins 9 ins in the ground for cor to secs 2. 3. 10 & 11 marked 5 Notches S and 2 E edges and raised a mound of stone alongside
	Land gently rolling
	Soil 2nd rate
	Scatt Timber Pine & scrub cedars
	Dense undergrowth oak

Subdivisions T 39 S R 6 W. S L M

Chains	
	and sagebrush on 52.40 chains
	East on a random line bet secs 2 and 11
	Var 15° 20' E
40.00	Set temp 1/4 sec cor
80.20	Intersect N & S line, 50 lks N of the cor to secs 1, 2, 11 & 12
	Thence I run N 89° 39 W on a true line bet secs 2 & 11
	with same Var
12.50	Road from Ranch to Upper Kanab N W & S E
	Enter oak brush
18.50	Ascend, Enter heavy timber
	Leave oak brush flat
36.00	Steep ridge N & S.
40.00	No trace of old corner
40.10	Set sandstone 6x12x8 ins 11 ins in the ground for 1/4 sec cor marked 1/4 on N face from which

BOOK-A-203

Subdivisions T 39 S R 6 W S L M

Chains	a pine 15 ins in diam bears N 46° 30' E 1.13 chs dist marked 1/4 S B T
	A pine 12 ins in diam bears S 17° 30' E, 89 lks marked 1/4 S B T
41.00	Leave heavy timber
	Enter oak brush
45.80	Wash in cañon drains S E.
47.10	Road from Ranch to Upper Kanab in canyon bearing S W.
	Cañon drains S 10° W
56.50	Ridge N W & S E
76.00	Hollow drains N W.
80.20	The cor to secs 2. 3. 10 & 11
	Land level & rolling
	Soil 1st & 2nd rate
	Heavy Pine timber on 22.50 chs
	Dense undergrowth oak brush on 45.20 chs
	Augmented on 67.70 chs

Subdivisions T39 S R6 W. S L M

	North on a random line bet secs 2 & 3
	Var 15°.20' E
40.00	Set temp 1/4 sec cor
80.70	Intersect N B dy of Tp 76 lks E of cor to secs 2.3.34 & 35
	Thence Trun
	S 0°32' E on a true line bet secs 2 & 3
	with same Va
7.50	Spring in corrall bears E 2.50 chs
40.70	Set Limestone 16"x10"x6" 11" in the ground for 1/4 sec cor marked 1/4 on W face and raised a mound of stone alongside
43.50	Trail bears NW & SE

Subdivisions T39S, R6W, S L M

48.50 Foot of ridge, Leave flat
53.00 Mid spring, bears N 21° E
62.50 Ridge descends W about 7 chs
74.70 Swail drain W
78.50 Ridge bears E & W
80.70 The cor to secs 23, 10 & 11
Land Rolling
Soil 2nd & 3rd rate
Dense undergrowth, oak
& Sage brush on 80.70 chs

North from cor to secs 33 & 34 which is a sandstone 5×12×4" above ground, properly marked with stone mound alongside. A cedar 23 ins diam bears S 26° E 80 lks dist marked T 40 S R 6 W S 2 B T
Var 15° 20' E

20.00 Ravine drains S.
40.00 Sch limestone 16×12×4 ins 11 ins in the ground for 1/4 sec cor, marked 1/4 on W face from which
A pine 10 ins in diam, bears S 10' E, 45 lks dist, marked 1/4 S B T
A cedar 12 ins in diam

Subdivision T39 S R6 W S L M

	bears S 30° W, 60 lks dist	
	marked 1/4 S B T	
41.50	Wash drains E	15.00
65.00	Ridge descends E	27.50
80.00	Set Limestone 20x18x6 ins 15'	
	in in the ground, for cor to secs	
	27, 28, 33 & 34 marked 1 notch	32.00
	S and 3 on E edges and raised	40.30
	a mound of earth and	
	stone alongside	
	Land, Mountainous	
	Soil, 1st & 2nd rate - - -	
	Scattering pine & cedar	
	Dense undergrowth, oak	
	and Sarvisberry on 80 chs	
	East on a random line	46.5
	bet secs 27 & 34	54.5
	Var 15° 20' E	60.0
40.00	Set temp 1/4 sec cor	78.5
80.60	Intersect N & S line 40 lk	80.6
	S of the cor to secs 26, 27, 34 & 35	
	Thence I run	
	S 89° 43' W on a true line	

Subdivision T39S R6W, SLM

bet secs 27 & 34
with same Var
15.00 Enter timber
27.50 Ridge descends N, Leave
dense and enter scattering
timber
32.00 Wash drns N E
40.30 Set limestone 16x14x2 ins
11 ins in the ground for 1/4
sec cor, marked 1/4 on N face
from which
A cedar 12 ins diam bears
S 37°30' W, 130 lks dist
A pine 10 ins in diam bears
N 50° W 75 lks dist each
marked 1/4 S B T
46.50 Ravine drs S
54.50 Ravine " N
60.00 Low ridge bears N & S
78.50 Leave pine and cedars
80.60 The cor to secs 27, 28, 33 & 34
Land rolling mountain
Soil 1st and 2d rate
Pine, cedar, oak and

Subdivision T39 S R6 W.

Sub

Sarvisberry
Dense undergrowth in
80,60 ch

North lat sec 27 and 28
Var 15° 20' E

20,00	Enter timber	
22,18	Ravine drains E	
38,00	Leave timber	
40,00	Set limestone 16x10x10 ins 11 ins in the ground for 1/4 sec Cor, marked 1/4 on W face and raised a mound of earth and stone alongside	40,00 79,50
47,00	Ridge descends E	
50,00	Head of wide canyon drs W	
80,00	Set a sandstone 22x12x4 ins 17 ins in the ground for Cor to secs 21, 22, 27 & 28 marked 2 notches S and 3 on E edges and raised a mound of earth and stone alongside	12,90 39,75
	Land mountain ridges	74,60 79,50

Subdivision T39 S R6 W S L M

Soil 1st & 2nd rate
Sarvisberry, pine & cedar
on 18 chs
Dense undergrowth sage
on 80.00 chs

East on a random line
bet secs 22 & 27
Var 15° 20' E

40.00 Set temp 1/4 sec cor
79.50 Intersect N & S line 30 lk
N of cor to secs 22, 23, 26 &
27. Thence Trun
N 89° 47' W on a true line
bet secs 22 & 27
with same Var
12.90 Cattle trail N E & S W
39.75 Set limestone 18 x 12 x 4 ins
12 ins in the ground for 1/4
sec cor, marked 1/4 on N
face and raised a mound
of earth and stone alongside
74.60 Ridge descends S
79.50 The cor to secs 21, 22, 27 & 28

Sieldersvie T39S R1W SLM

Land rolling mountain,
Soil 1st 2nd rate
Dense undergrowth,
Sage, on 79,50 chs

North bet secs 21 and 22
Var 15° 20 E

10,50 Ridge descends N W
20,00 Ravine drains W heads S E.
Enter scattering timber
40,00 Set limestone 18"x12"x12", 12"
in ground for 1/4 sec cor marked
1/4 on W face and raised a
mound of stone along side
41,00 Ridge descends W
63,50 Ravine drs W
80,00 On ridge bearing W set
limestone 24x20x15 ins
18 ins in the ground for
cor to secs 15, 16, 21 & 22
marked Trotches on S and
Trotches on E edges from
which
A pine pin in diam

40,00
79,80

BOOK-A-203

Subdivision T39S R6W S2N

bears N14°W 75' lks dist
marked T39S R6W S16 BT
A pine 24 ins in diam
bears N76°E 118 lks dist
marked T39S R6W S15 BT
A pine 28 ins in diam
bears S12°E 80 lks dist marked
T39S R6W S22 BT
A pine 14" diam bears S79°
W 120 lks dist marked
T39S R6W S21 BT

Land Mountainous
Soil 1st and 3rd rate
Cutting Pine, Cedars, oak and
Sarvisberry on 60 chs
Dense undergrowth on
80.00 chs

East on a random line
bet secs 15 and 22
Var 15°, 20' E
40.00 Sch temp 1/4 sec Cor
79.80 Intersect N & S line 15 lks
N of Cor to secs 14, 15, 21 & 22

Subdivision T39 S R 6 W S L M

	Thence Trim
	N 89° 54' W on a true line
	bet secs 15 & 22
	with same var
22,50	Foot of mountain, Leave flat
25,00	Point of ridge descends S
	about 4 chs
31,00	Ravine des S E heads
	N W about 10 chs
39,90	Set limestone 24 x 12 x 6
	24 ins in the ground for
	1/4 sec cor, marked 1/4 on N
	face and raised a mound
	of earth and stone alongside
42,00	Ridge N & S
60,00	Enter timber (Scattering)
69,00	Spur ridge descends N
79,80	The cor to secs 15, 16, 21 & 22
	Land high & mountainous
	Soil 1st & 2d rate
Scattering	Pine cedar & sarvisberry
	on 19,80 chs
	Dense undergrowth, sage
	& greasewood on 79,80 chs
	May 27th 1884

Subdivision T39 S, R6W, S.L.M.

North bet secs 15 & 16
Var 15°20' E

2000 Wash in ravine drs W
35,00 Ridge descends W
40,00 Set Limestone 18 x 10 x 6 ins 12 ins in the ground for 1/4 sec cor marked 1/4 on W face from which
A pine 30" in diam bears N 89° E 80 lks dist marked 1/4 S B T
A pine 36 ins in diam bears S 89° W 130 lks dist marked 1/4 S B T
4800 Wash in ravine drs W
5350 Ridge descends W
65,00 Ravine drns W, heads E about 10 chs
8000 Set limestone 16 x 10 x 6 11 ins in the ground for cor to secs 9, 10, 15 & 16 marked 4 notches on S and W on E edges & raised a mound of earth and stone alongside

Subdivision T39S. R6W. S.L.M.

Corner of R.G. Jolley's field
bears N 40° E about 5 ch
dist
No trees within limits
Land high & mountains
Soil 1st and 3rd rate
Dense undergrowth
on 80.00 ch.

Eastern a random line
bet secs 10 & 15
Var 15°.20' E
40.00 Sch temp 1/4 sec cor
80.80 Intersect N & S lines 80 lk
N of the corner to secs 10, 11,
14 & 15. Thence Frun
N 89°.26' W on a true line
bet secs 10 & 15
with same var
11.80 Ravine 80 ft below corner
drains N
14.80 Ridge 60 ft above hollow
descends N
40.40 Sch sandstone 14 x 10 x 6 ins

Subdiv

9"
Cor
fro
C
2
C
I
m
51.00 Spr
60.80 Tra
S E
68.30 20 c
71.80 Hol
80.80 The
d
s
o
No
6.50 Fen
Ear
15.20 Fen
Enter

BOOK-A-203

Subdivision T39S R6W S.B.M.

9" in the ground for 1/4 sec
Cor marked 1/4 on N face
from which
A pine 8" in diam bears S
28 W 100 lks dist
A pine 20 ins diam bears
N 13 1/2° E 172 lks dist, each
marked 1/4 S B T

51.00 Spur of ridge N W & S E
60.80 Trail in Levanger canyon
S E & N W
65.30 20 chs North to Levanger House
71.80 Hollow-down N W
80.80 The corner to secs 9, 10, 15 & 16
Land rolling mountains
Soil 2nd rate
Heavily timbered, pine,
on 80.80 chs

North bet secs 9 and 10
Var 15° 20' E
6.50 Fence N E & S W, Leave timber
Enter field
15.20 Fence N E & S W leave field
Enter dense sage brush

Subdivision T39S, R6W, S.L.M.

15,50	Road N E & S W
16,50	Enter timber
25,20	Ridge N W & S E
40,00	Set sandstone 18 x 8 x 6 ins 12 ins in the ground for 1/4 sec cor, marked 1/4 on W face from which
	A pine 24 ins in diam bears S 79° E 80 lks dist
	A pine 26 ins in diam bears S 31° W 78 lks dist each marked 1/4 S B T
57,00	Canyon dro S E
59,00	Leave timber at abrupt ascent
64,00	Ridge bears E & W 500 ft above hollow
70,00	Enter timber and dense oak
80,00	Set limestone 14 x 12 x 4 ins 9 ins in the ground for cor to secs 3, 4, 9 & 10 m marked 5 notches S and 3 m E edges from which
	A pine 20 ins in diam bears N 15½° W, 2 chs dist

Subd

Bear

E

40,00 Se

7,30 Li

No

Th

Subdivisions T39S R6W S 2

marked T39S R6W S4 BT
A pine 16" in diam bears N
50° E 1.17 chs dist marked
T39S R6W S3 BT
A pine 16 ins in diam bears
S 60½° E 1.07 chs dist marked
T39S R6W S10 BT
A pine 26" in diam bears S
31½° W 1.70 chs dist marked
T39S R6W S9 BT
Land rolling mountains
Soil 2nd rate
Heavy Timber on 59.00 chs Pine & oak
Dense undergrowth age
on 71.30 chs
~~May 24 [illegible]~~
East on a random line
Lat secs 3 & 10
Var 15°, 20' E
41.00 Set temp ¼ sec cor
[illegible].30 Intersect N & S line 80 lks
N of cor to secs 2, 3, 10 & 11
Thence I run
N 89° 26' W on a true

Subdivision T 39 S. R 6 W S L M

	line bet secs 3 & 10 with same var
1.50	Ridge N E & S W
19.00	Enter mud Spring Valley bears N E & S W
23.00	Road from Nanab and Arizona to Panguitch bears N & S
30.00	Leave Valley
39.15	Set a gray sandstone 16x10x5 ins 11 ins in the ground for 1/4 sec cor, marked 1/4 on N face and raised a mound of earth and stone alongside
44.30	Enter pinetimber
79.30	The cor to secs 3, 4, 9 & 10. Land rolling mountains Soil 1st and 2nd rate Heavy pinetimber on 35 chs Dense undergrowth Sage on 79.30 chs

Subd

	c
40.00	V
80.96	L
	1/3
	c
	l
17.50	Sp
35.00	L
	Re
40.96	Se
	11
	Cor
	fr
	c
	c
	c
	c
	c
51.00	Re

Subdivisions T39S R6W S.E.M.

North on a random line
bet secs 3 & 4
Var 15° 20' E

40.00 Set temp 1/4 sec cor
80.96 Intersect N boundary
of Tp 84 lks E of the cor to secs
3, 4, 33 & 34, Thence from
S 0° 36' E on a true line
bet secs 3 & 4
with same var
17.50 Spur ridge descends W
35.00 Hollow drns W 150 ft below
ridge
40.96 Set sandstone 16 x 10 x 8 ins
11 ins in the ground for 1/4 sec
cor marked 1/4 on W face
from which
A pine 10 ins in diam
bears N 75° W
A pine 4 ins in diam
bears S 86° E, 1.08 chs
dist, each marked 1/4
S B T
51.00 Ridge descends E

Subdivisions T39S, R6W, S.L.M.

70,00	Hollow dry W
80,96	The corner to secs 3, 4, 9 & 10.
	Land rolling mountain Soil 2nd Rate Dearly Timber Pine on 80,96 chs.
	North from corner to Secs 32 & 33
	which is a sandstone 6x13x2 in above ground properly marked with mound of earth & stone alongside
	Var 15° 20' E
40,00	Set sandstone 16x14x3 in 11 ins in the ground for 1/4 sec cor, marked 1/4 on W face and raised a mound of earth and stone alongside
50,00	Rocky ridge descends N W
67,50	Ravine drains N W
73,50	Rocky point descends W
74,00	Enter scattering Cedar
80,00	Set lava stone 16x14x4 in 11 ins in the ground for cor

Subdivisions T39S R6W S.B.

to Secs 28, 29, 32 & 33.
marked 4 notches E &
1 on S edges, from which
a Cedar tree 9 ins in
diam bears S 83° E 25
lks dist marked T39S
R6W S33 B.T.
Land mountainous & broken
Soil 4th rate
Dense undergrowth oak
& sage on 80,00 chs

East on a random line
bet secs 28 & 33
Var 15° 20' E
40,00 Set temp 1/4 sec cor
80,40 Intersect N & S line
30 lks S of the cor to Secs
27, 28, 33 & 34 Thence from
S 89° 47' W on a true line
bet secs 28 & 33
with same Var
40,20 Set limestone 14"x12"x4"
9 ins in the ground for

Subdivisions T39S R6W S L M

	1/4 Sec cor marked 1/4 on N face and raised a mound of earth and stone alongside
48.50	Ridge bears N E & S W
51.00	Trail " N W & S E
80.40	The corner to secs 28, 29, 32 & 33
	Land mountainous
	Soil 3rd rate
	Dense undergrowth
	Sage brush on 80.40 chs
	North bet secs 28 & 29
	Var 15° 20' E
24.00	Hollow dens N 20° E
30.00	Enter scattering timber
40.00	Set limestone 15 x 8 x 8 ins 10 ins in the ground for 1/4 Sec cor marked 1/4 on W face from which
	A pine tree 34" in diam bears N 7° E 55 lks dist marked 1/4 S B T
	No other tree convenient to mark

Subdivisions T39S, R6W,

65.00	Enter broad open hollow
	Leave timber & brush
72.00	Trail bears S E & N W
79.50	Hollow drains W Enter brush
80.00	Set limestone 15"x10"x8 in
	10 ins in the ground for
	cor to secs 20, 21, 28 & 29
	marked 4 notches on E
	and 2 on S edges from which
	A pine tree 30 ins in diam
	bears N 34° 30' E 2 chs dist
	marked T39S, R6W, S21 B.T.
	An old house of Roundy's
	bears N 70° 30' E
	Land level & mountainous
	Soil 1st and 2d rch
	Scattering timber on
	35 chs
	Dense undergrowth
	oak brush on 65.00 chs
	East on a random line
	bet secs 21 & 28
	Var 15° 20' E

Subdivisions T39S R6W, S.L.M.

40.00	Set temp 1/4 sec cor
80.30	Intersect N & S line 49 lks N of the corner to secs 21, 22, 27 & 28, thence from N 89° 39' W on a true line bet secs 21 & 28 with same var
40.15	Set limestone 20x10x4 in 15 in in the ground for 1/4 sec cor marked 1/4 on N face and raised a mound of earth and stone alongside
44.00	Ridge descends N W Leave scattering cedar
49.00	Foot of hill
51.50	Trail bears S 75° E N 75° W
80.30	The cor to secs 20, 21, 28 & 29 Land gently rolling Soil 1st and 2nd rate Scattering cedars on 44 00 chs Dense undergrowth sage brush on 80.30 chs May 29th 1884

Subdivisions T39S R6W, S2M

North bet secs 20 & 21
Var 15°20'E

4,00 Trail bears N 70° W and S 70° E
10,00 Foot of hill, Enter dense Timber Pine & cedar
27,00 Ridge descends N W
34,00 Hollow drns S 60° W
40,00 Set limestone 14 x 9 x 6 ins 9 ins in the ground for 1/4 sec cor marked 1/4 on W face from which
A pine tree 6 ins in diam bears N 40° E 12 lks dist marked 1/4 S B T.
A cedar tree 4" in diam bears S 45° W 50 lks dist marked 1/4 S B T
55,00 Ridge descends S 65° W
68,40 Ravine bears N W
72,25 Ridge descends W
75,75 Ravine drs S 60° W
80,00 Set limestone 15 x 10 x 9 ins 10 ins in the ground for cor to secs 16, 17, 20 & 21 marked

Subdivision T39 S R6 W S L M

4 notches on E and 3 on S
edges from which
A pine tree 20 in in diam
bears S 74° W 55 lks dist
marked T39 S R6 W S20 B.T. 40,10
A pine tree 18 in in diam
bears N 76° 30' W 70 lks dist
marked T39 S R6 W S17 B.T.
A pine tree 6 in in diam
bears N 14° E 1,25 chs dist 80,20
marked T39 S R6 W S16 B.T.
Land mountainous &
broken
Soil 1st & 3rd rate
Timber Pine & Cedar on 70 chs
Dense undergrowth
sage brush & oak on 80 chs

6,00
Eastern a random line 13,30
bet secs 16 & 21 26,50
Var 15° 20' E 29,00
40,00 Set temp 1/4 sec cor 40,00
80,20 Intersect N & S line 77 lks
N of the cor to secs 15, 16, 21 & 22

Subdivision T39S R6W S.L.M.

Thence Trun
N 89° 27' W on a true line
bet secs 16 & 21
with same Var
40.10 Set grayssandstone 15'x9x3
ins 10 ins in the ground for
1/4 sec cor, marked 1/4 on N
face and raised a mound
of earth and stone alongside
80.20 The corner to secs 16 17, 20 & 21
Land nearly level
Soil 1st and 2d rate
Dense undergrowth
Sage & oak brush on 80.20 ch

North bet secs 16 & 17
Var 15° 20' E
6.00 Ridge descends S 60° W
13.30 Ravine drs S 80° W
26.50 Ridge descends S 80 W
29.00 Descend
40.00 Set a limestone 14x9x8 ins
9" ins the ground for 1/4 sec cor
marked 1/4 on W face from

Subdivisions T39S, R6W, S.L.M. | Sub

which
A pine tree 14" in diam
bears N 66°45' E 55 lks dist
A pine tree 24 in diam
bears S 29°45' W, 50 lks dist
each marked 1/4 S B T
A house bears S 57°30' W
16 lks wide 5" deep
50.00 Long Valley Creek runs S W
51.75 Road to Panguitch, and brush
fence S W & N E
70.00 J H Miles house, E 6 chs,
P O E 11 chs
76.00 Spur Ridge E & W
79.50 J H Leamans garden fence
E & W
80.00 Set limestone 18 x 12 x 4 ins
12 ins in the ground for
cor to Lees 8, 9, 16 & 17 marked
4 notches on E and 4 on S
edges, and raised a mound
of stone alongside
A pine 20" in diam
bears N 53 1/2 E, 2.19 chs dist
marked T39S. R6W S9 B T

40.00
79.60

Subdivisions T39S R6W, S L M

A pine 12" diam bears
N 39°75' W, 1.85 chs dist
marked T39S, R6W, S8 B T
A Pine 14" in diam bears
S 30°30' W 1.50 chs dist
marked T39S, R6W, S17 B T
No other tree convenient
to mark
Land rolling brush
Soil 2d & 3d rate
Timber scattering
Bence underground sage
brush. ... 80.00 chs

East on a random line
bet secs 9 and 16
Var 15°20' E
40.00 Set temp 1/4 sec cor
79.60 Intersect N & S line 42
lks S of the cor to secs 9, 10, 15
& 16, Thence From
S 89°42' W on a true line
bet secs 9 & 16.
with same Var

Subdivision T39S, R6W, S L M

4.30	Trail in mouth of hollow	
	Leave timber	48.4
5.00	R G Jolley's fence bears N 75°	51.7
	E and S 75° W. Enter	59.5
	Cultivated field	62.5
17.40	Leave field, bears N 80° E	65.7
	and S 80° W	
28.00	Road from Upper Kanab	
	to Long valley, bears N 80° E	
	S 80° W.	
30.00	Ascend enter sage & oak	
	brush	
34.00	Point of spur ridge S W 3 chs	
39.80	Set limestone 16 x 10 x 6 ins	69.50
	11 ins in the ground, for 1/4 sec	
	Cor, marked 1/4 on N face	
	from which a pine tree	70.00
	16" in diam bears N 16½° E	
	1.50 chs dist marked 1/4 S B T	79.60
	R G Jolley's house bears S 68°	
	30' W, Barn bears S 65° W	
	Reservoir bears S 50° W	
	about 8 chs dist	
46.00	Road bears S 80° W a[illegible]	

Subdivisions T39S. R6W. S.L.M.

N 80° E, Leave sage & oak brush
48.40 Cor of Jolley field bears S 80 W
51.75 Ditch runs S
59.50 fence bears N 80° W
62.50 Long Valley Creek runs S W (10 lks wide 6" deep)
65.75 Fence bears N & S, Enter field and leave mill yard
Jno Seaman's steam saw mill bears S about 2 chs
House is about 50 lks S of mill
School House about 300 lks N.W. and barn is about 300 lks W of mill.
69.50 Road from Long Valley to Panguitch bears N & S
Enter oak brush
70.00 J.W. Seaman's barn bears S 2 chs dist
79.60 The cor to secs 8.9.16 & 17
Land gently rolling
Soil 1st rate
Timber on 4.30 chs
Dense undergrowth, sage & oak brush on 16.00 chs
augmented on 20.30 chs
May 2 6th 8 [illegible]

Subdivision T39 S R6W, S L M

	North bet secs 8 and 9	
	Var 15° 20' E	
3,50	Log road in Cañon bears E & W	
20,00	3,50 chs E stable & corral & 5 chs E. R G Jolley's Mill Pond at head of Long Valley Creek	
24,00	4 Chs E, William Wilkerson's house and S end of J W Semain's fenced field	
40,00	Set limestone 14x12x6 ins 9" in the ground marked 1/4 on W face from which A pine 20 ins in diam bears S 89° W 37 lks dist A pine tree 6" in diam bears N 80° E, 15 lks dist each marked 1/4 S B T	
40,50	Ridge descends E	
60,50	Canyon drains E	
72,50	Ridge 60 ft above canyon bears E	
77,50	Road in Canyon bears E	
80,00	Set limestone 18"x12"x6"	40,00

Subdivisions T39S R6W S2M

12" in the ground for cor to
secs 4, 5, 8 & 9 marked
4 notches on E and 5 on S
edges from which
A pine 22 ins in diam bears
S 56½° W 62 lks dist
marked T39S R6W S8BT
A pine tree 24 ins in diam
bears S 60¾° E, 2 chs dist
marked T39S R6W S9BT
A pine 20 ins in diam
bears N 59° W 68 lks dist
marked T39S R6W S5BT
A pine 26 ins in diam
bears N 60° E 56 lks dist
marked T39S R6W S4BT
Land rolling mountains
Soil 2nd rate
Heavy Timber, pine 80,00 chs

East on a random line
bet secs 4 & 9
Var 15° 20' E
40,00 Set temp ¼ sec cor

Subdivisions T3 S, R6 W, S2 M

80,60	Intersect N & S line 35 lks
	N of the cor to secs 34, 9 & 10
	Thence Trees
	N 89°45' W on a true
	line bet secs 4 & 9
	with same var
1,00	Ridge about 600 ft above
	Canon bears N & S
27,00	Descend Enter timber
40,30	Set a limestone 16 x 10 x 8 ins
	10 ins in the ground for 1/4
	sec cor, marked 1/4 on N face
	from which
	A pine 40 ins in diam
	bears S 56° W 3,10 chs dist
	A pine 20" diam bears
	N 22° E, 1,80 chs dist each
	marked 1/4 S B T
55,00	Mouth of Clark Canyon
	Leave pine timber
62,50	Road bears N & S
63,00	Wash drns S
73,60	Road up left hand canyon
	bears N E & S W

Subdivision T39 S. R6 W. S.L.M.

Foot of mountains, Enter timber and leave Canyon
80,60 The cor to secs 4, 5, 8 & 9
Land rolling mountains
Soil 2nd rate
Heavy Timber pine on 35,40 chs
Dense undergrowth sage and oak brush on 80,60 chs

North on a random line bet secs 4 & 5
Var 15°, 20' E
40,00 Set temp 1/4 sec cor
80,90 Intersect N boundary 80 lks E of the cor to secs 4, 5, 32 & 33, Thence I run S 0° 34' E on a true line bet secs 4 and 5 with same Var
12,00 Wash in Canon drains E
20,00 Road bears N 10 W and S 10° E
40,90 Set a limestone 18 x 12 x 6 12 ins in the ground for 1/4

Subdivisions T3 S R6 W. S.L.M. | Subd

	sec cor marked 1/4 on W face from which	
	A pine 18 ins in diam bears N 88° W, 70 lks dist	
	A pine 30 ins in diam bears S 80° E 2,50 chs dist each marked 1/4 S B T	40,20
60,00	Right hand fork of cañon	57,00
	Ascend	72,50
75,00	Aspen ridge bears E & W	80,00
80,90	The cor to secs 4, 5, 8 & 9	
	Land rolling mountains	
	Soil 1st and 2nd rate	
	Heavy Timber Pine on	
	80,90 chs	
	North from corner to secs 31 and 32 which is a sandstone 6x10x6 above ground, properly marked stone mound alongside & 2 bearing trees	
	Var 15°,20' E	
37,00	Ridge descends N W	
	Either timber	
40,00	Set limestone 15x10x0 ins	40,00

Subdivisions T39S, R6W, SLM

10 ins in the ground for 1/4 sec cor marked 1/4 on W face from which
A pine tree 7 ins diam bears S37°W, 25 lks dist marked 1/4 SBT

40.20 Ravine drains E
57.00 Ridge descends E
72.50 Leave scattering Tumbi
80.00 Set sandstone 18x18x2 ins 12 ins in the ground for Cor to secs 29, 30, 31 & 32 marked 6 notches E and 1 on Sedges and raised a mound of stone alongside
Land, mountainous
Soil 1st rate
Scattering timber on 35.50 chs
Dense undergrowth
oak and sage brush on 80 chs

East on a random line
bet secs 29 & 32
Var 15°20' E

40.00 Set temp 1/4 [illegible]

Subdivisions T39 S R6 W S L M

79.90 Intersect N & S line 30 lks
S of the cor to sec 28, 29, 32 &
33 Thence Trun
S 89° 47' W on a true line
bet secs 29 & 32
with same Var
7.00 Hollow drains N 80° W
39.95 Set lava stone 14 x 10 x 8
ins quinn the ground for
1/4 sec cor, marked 1/4 on N
face and raised a mound
of stone alongside
55.00 Foot of Mountain
Lava dense underwrth
67.24 Enter cultivated land
79.90 The cor to secs 29, 30, 31 & 32
Land level & mountainous
Soil 2nd and 4th rate
Dense underwrth
oak & sagebrush on 67.24 chs

West on a random line
bet secs 30 & 31
Var 15° 20' E
40.00 Set turn 1/4 sec cor

Subdi

80.24

13.50
40.24

48.00

48.30
73.45

74.70

80.24

Subdivisions T39S, R6W, SLM

80.24	Intersect W boundary of Tp 91 lks N of the cor to sec's 25, 30, 31 & 36 which is sand stone 5x15x6' above ground, properly marked, with mound of earth & stone Thence I run N 89°21' E on a true line bet sec's 30 & 31 earth same var
13.50	Local attraction 4°30' W
40.24	Set lava stone 16x12x8 ins 11 ins in the ground for 1/4 sec cor marked 1/4 on N face and raised a mound of earth and stone along side
48.00	Table land, Local attraction 3°45' E
48.30	Foot of ledge 30 ft high
73.45	Enter Meadow Descend hill
74.70	Leave Meadow Enter Cultivated land
80.24	The cor to sec 29, 30, 31 & 36

Subdivision T39 S R E W S L M | Sub

	Land level & Mountainous	80,00
	Soil 1st & 4th rate	
	Dense undergrowth oak	
	& sagebrush on 73.45 chs	
	Noth bet secs 29 & 30	
	Var 15°.20' E	
65	Bottom of hollow drs W	
13,00	Trail bears N W & S E	
	Enter scattering timber	
40,00	Set sandstone 14 x 10 x 6 in	
	9" in the ground for 1/4 sec	
	Cor marked 1/4 on W face	
	from which	
	A pine tree 36 in in diam	
	bears N 45° E 65 lks dist	
	marked 1/4 S B T	40,00
47,00	Leave timber and undergrowth	78,00
51,00	Descend into Long valley narrows	
56,25	Bottom of hill, Enter nearly	
	level land	
58,70	Creek 10 lks wide, 8 in deep	
	drns S 50° W	
78,40	Road bears N E & S W	1,00

Subdivisions T39S R6W SLM

8000 Set limestone 18x14x4 ins 12" in the ground for cor to secs 19, 20, 29, & 30 marked 5' notches on E & 2 on S edges and raised a mound of earth and stone alongside
Land mountainous
Soil 3rd rate
Scattering Timber on 34 chs
Dense undergrowth, Oak brush and well w'on 47 chs
May 30th 84
E Easton a random line bet secs 20 & 29
Var 15°20' E
4000 Set temp 1/4 sec cor
7800 Intersect N & S line 50 lks N of the cor to secs 20, 21, 28 & 29 Thence Trun N 89°39' W on a true line bet secs 20 & 29 with same var
1.00 Wash in hollow drs N 67 W

Subdivision T39 S R6 W S L M

10.00	trail bears N W & S E	
20.00	Foot of hill enter timber	
25.00	Ridge descends N W	
38.50	Hollow drains N	
39.80	Set flint stone 16 x 10 x 8 in	
	11 ins in the ground for 1/4	
	sec cor marked 1/4 on N	40.00
	face from which	80.17
	A pine tree 6 ins in diam	
	bears S 69° E 40 lks dist	
	A pine tree 24 ins in diam	
	bears N 54° W 30 lks dist	
	each marked 1/4 S B T	
56.00	Ridge descends N & S	
68.80	Trail bears N & S Foot of mountain	
71.50	Leave pine Enter Willows	
72.90	Long valley creek 20 lks wide	9.00
	drains S	16.00
77.50	Spring branch 20 lks wide drs E Leave Willows	
78.10	Road in Canyon drs S	20.60
78.60	The cor lotses 19, 20, 29 & 30	
	Land Level & broken	
	Soil 1st & 3d rate	27.20
	Timber pine on 51.50 chs	
	Willows on 7.10 chs	

Subdivisions T39 S R64 S L M

Dense undergrowth, sage brush in 78,60 chs

West on a random line bet secs 19 & 30
Var 13° 20' E

40,00 Set temp 1/4 sec cor
80,17 Intersect W boundary of Tp 43 lks S of the cor to secs 19, 24, 25 & 30 which is a sandstone 6x10x6 above ground, properly marked with 4 bearing trees
Thence from
S 89° 42' E on a true line bet secs 19 & 30
with same Var
9,00 Enter timber
16,00 Low ridge descends S
20,60 About 2000 ft below sec cor
Road from Glendale to Kanab on side hill bears SE & NW
27,20 Same road in Canyon bears S House bears N 3 chs, Spring bear N 3,50 chs

Subdivision T39 S R 6 W, S L M

38.50 Leave Long valley
40.17 Set sandstone 18 x 12 x 5 ins 12" in the ground for 1/4 sec Cor marked 1/4 on N free from echeck
A pine 9 ins in diam bears N 40° E 40 lks dist
A balsam 4 ins in diam bears S 63° W, 1.60 chs dist each marked 1/4 S B T
80.17 The corner to secs 19, 20, 29 & 30
Land Mountainous
Soil 1st & 3d rate
Timber, pine on 71.17 chs
Dense undergrowth, Sage brush on 80.17 chs

North bet secs 19 & 20
Var 15°, 20' E
5.00 Enter scattering Timber
10.70 A pine 25 in dia
19.00 Mouth of ravine drains E
39.50 Ridge descends E

Subdivision T39 S. R6W. S L M

40.00 Set limestone 15x10x3 ins 10 ins in the ground for 1/4 sec cor marked 1/4 on W face, from which

A pine tree 12 ins in diam bears S 70° E 60 lks dist marked 1/4 S B T

No other tree convenient to mark

Wm Roundy's house & barn bears S 65° 30' E about 25 chs dist

59.50 Ravine dis S 70° E

80.00 Set limestone 16x12x4 ins 11 ins in the ground for cor to secs 17, 18, 19 & 20 marked 5 notches on E and 3 on S edges from which

A pine tree 24 ins in diam bears S 45° W 55 lks dist marked T39 S R6W S 19 B T

A red pine tree 30 ins in diam bears N 56° W 50 lks dist marked T39 S. R6W S 18 B T

Subdivision T39S, R6W, S20M

	A pine tree 24 in in diam bears S45° E, 25 lks dist marked T39S, R6W, S20 B T	26.50
	A pine tree 20 in in diam bears N29° E 12 lks dist marked T39S, R6W, S17 B T	24.70
	Land Mountainous & Broken Soil 2nd rate	29.00
	Timber Scattering pine 75 lks	31.50
	Remainder growth on 80 chs	34.37
		36.00
		40.12
	East on a random line bet secs 17 and 20 Var 15° 20' E	
40.00	Set limestone 1/4 sec cor	
80.25	Intersect N & S line 56 lks S of the cor to secs 16, 17, 20 & 21	
	Thence from	41.00
	S 89° 36' W on a true line	42.50
	bet secs 17 and 20	59.25
	with same Var	66.50
5.00	Head of Ravine dry S 25° W	70.50
25.00	Ridge descends S 25° W	80.25

BOOK-A-203

Subdivisions T39 S. R 6 W. S L M

26.50 Foot of hill. Leave timber
26.70 Long valley creek, 5 lks wide
12 ins deep dirs S 22 W,
Enter plowed land
27.00 Leave plowed land
31.50 Fence bears N 27° E, S 37° W
Leave Graham Mt Donalds Meadow
34.37 Road bears S 27 W & N 27 E
36.00 Enter timber
40.12 Set flint stone 16 x 10 x 7 ins
11 ins in the ground for 1/4 sec
cor, marked 1/4 on N face from
which
A pine tree 24 ins in diam
bears S 82° E 175 lks dist
A pine tree 7 ins in diam
bears S 79° W 100 lks dist, each
marked 1/4 S B T
41.00 Ridge descends S E
42.50 Ravine drns S E
59.25 Ridge descends S E
66.50 Ravine drns S E
70.50 Ridge descends S 20 E
80.25 The Cor to Secs 17, 18, 19 & 20

Subdivision T39 S R6 W S L M

	Land rolling & Broken	
	Soil 1st and 2nd rate	
	Timber on 73.75 chs	
	Dense undergrowth	
	sagebrush on 80.25 chs	49.90
		60.70
	West on a random line	68.00
	bet secs 18 & 19	77.25
	Var 15°.20' E	79.75
40.00	Set temp 1/4 sec cor	
79.75	Intersect W boundary of Tp	
	1/4 lks N of the cor to secs 13, 18, 19	
	& 24 which is a white limestone 5	
	x10x5 in above ground properly marked	
	and 4 bearing trees.	
	Thence Trun	
	N 89°28' E on a true	
	line bet secs 18 & 19	
	with same var	17.50
15.00	Ridge N 20° W and S 20° E	29.00
32.50	Cannon dis S	
39.75	Set lava stone, 18"x12"x7" 13" in	40.00
	the ground for 1/4 sec cor marked	
	1/4 on N face from which	
	a pine tree 7" diam bar	

Subdivisions T39S R6W SLM

S 45° W, 3 olks dist
A Nut pine tree 8 ins in
diam, bears N 50° E 50 lks
dist, each marked 1/4 S B T
49.90 Ridge descends S E.
60.70 Ravine drns S. 50° E.
68.00 Ridge descends S 35° E
77.25 Ravine drns S 80 E
79.75 The cor to secs 17, 18, 19 & 20
Land Mountain Ridges
Soil 1st and 2nd rate
Oak brush on 49.90 chs
Dense undergrowth
Sage brush on 79.75 chs

North bet secs 17 & 18
Var 15° 20' E
17.50 Ridge descends W
29.00 Head of Canon heads S 10° W
15 chs and drns S 35° E
40.00 Set limestone 15 x 8 x 7 ins 10 in
in the ground for 1/4 sec cor
marked 1/4 on W face from
which

Subdivisions T39S R6W S L M

A pine tree 9 ins in diam
bears S 30° E 10 lks dist.
A pine tree 30 ins in diam
bears N 45° W 50 lks dist
each marked 1/4 S B T

52.00 Enterbrush
56.75 Ridge, course N W & S E
65.10 A pine 30 in dia
80.00 Head of Cañon drs S 60° E
Set limestone 17 x 12 x 8 ins
12 ins in the ground for
Cor to Secs, 7, 8, 17 & 18 marked
5 notches on E and 4 on
Ledges, from which
A pine tree 14 ins in diam
bears S 63° 30' W 135 lks
dist marked
T39S, R6W, S18 B T,
A pine tree 18 ins in diam
bears N 61° W 35 lks dist
marked
T39S, R6W, S7 B T
A pine tree 20 ins in
diam bears N 20° E

Subd

55
40.00 Sy
79.80 Inc
S of
S 8
be
V
31.50 Rec
39.90 Set

BOOK-A-203

Subdivisions T39S, R6W, S2M

55 lks dist marked
T39S, R6W, S8BT
A pine tree 16 in in diam
bears S25°E 160 lks dist
marked
T39S R6W, S17BT
Land Mountainous
Soil 3rd rate
Dense undergrowth, sage
brush on 28 chs
Heavy timber on 80.00 chs

East on a random line
bet secs 8 & 17
Var 15°20'E
40.00 Set temp 1/4 sec cor
79.80 Intersect N & S line 98 lks
S of the cor to secs 8, 9, 16 & 17.
Thence I run
S 89°18' W on a true line
bet secs 8 & 17 with same
Var
31.50 Ridge descends S E
39.90 Set lime stone 16 x 10 x 4

Subdivisions T39 S. R6 W. S.L.M.

	11 ins in the ground for 1/4 sec cor, marked 1/4 on N face from which
	A pine tree 16 ins in diam bears S 10° W 110 lks dist
	A pine tree 15 ins in diam bears N 70 W west 35 lks dist each marked 1/4 S B T
45,25	Ravine drns S 5° E
49,00	Ridge descends S E
54,45	Ravine drns S 55° E
54,60	Road bears S 55° W and N 55° E
62,30	Edge of basin
65,00	Bottom of basin 150 lks in Circumference
68,00	Edge of basin
74,40	A pine 16 in dia
79,80	The cor Rotecs 7, 8, 17 & 18
	Land Mountainous
	Soil 3rd rate
	Scattering timber on 79,80 ch

Sub

40,00	
80,80	
12,00	
34,50	
40,80	

BOOK-A-203

Subdivision T 39 S R 6 W S L M

Dense undergrowth sage brush on 79,80 chs

West on a random line bet secs 7 & 18
Var 15° 20' E

40,00 Set temp 1/4 sec cor
80,80 Intersect W boundary of Tp 84 lkg N of the cor to secs 7, 12 13 & 18 which is a sandstone 6x6x5 in above ground properly marked & 4 bearing trees
Thence Trees
N 89° 24' E on a true line bet secs 7 & 18
with same Var
12,00 Ridge descends S
24,50 Ravine drains SW
40,80 Set limestone 15"x12"x9", 10" in the ground for 1/4 sec cor marked 1/4 on N face from which
A pine tree 24 ins in diam bears S 50° W, 30 lks dist
A pine tree 5 ins in diam

Subdivisions T39 S R6 W S & M

bears N 60° E 50 lks dist
each marked 1/4 S B T
52,50 Ridge N 5° E and S 20° W
80,80 The cor to secs 7, 8, 17 & 18
Land mountainous
Soil 2nd rate
Tenx underground sage
and oak brush on 80,80 chs

North bet secs 7 and 8
Var 15° 20' E
39,00 Ridge bears S W & N E
Enter underground
40,00 Set limestone 17 x 14 x 8 in 12
in ground for 1/4 sec cor
marked 1/4 on W face from
which
A pine tree 16 in in diam
bears S 73° W 8 lks dist
A pine tree 17 in in diam
bears N 25° W 30 lks dist
each marked 1/4 S B T
80,00 Set a limestone 18 x 17 x 3 in
12 in in the ground for cor

Subdivision T39S R6W S.L.M.

to Secs 5, 6, 7 & 8 marked
5 notches in E & S edges
from which
A pine tree 6 ins in diam
bears S 73° W 147 lks dist
marked T39S, R6W, S7BT
A pine tree 8 ins in diam
bears N 38° W 142 lks dist
marked T39S, R6W, S6BT
A pine tree 9 ins in diam
bears N 62° 30' E 215 chs
dist marked T39S, R6W, S5BT
No other tree convenient
to mark
Land mountainous
Soil 3rd rate
Heavy pine timber on 80 chs
Dense underground oak
and sarvisbury brush
on 41 chs
Augmented on 80 chs
East on a random line
bet secs 5 and 8
Var. 15° 20' E

Subdivisions T39 S R6 W S L M

		Sub
40.00	Sch temp 1/4 sec cor	
79.46	Intersect North and South line 50 lks N of the cor to secs 4, 5, 8 & 9 Thence I run N 89°39' W on a true line bet secs 5 and 8 with same var	
31.00	Ridge N & S Thence along rolling bench	40.00 80.45
39.73	Sch flint stone 16 x 10 x 8 ins 11 ins in the ground, for 1/4 sec cor, marked 1/4 on N face from which A pine tree 7" in diam bears S 40° E 80 lks dist A pine tree 18" in diam bears N 75° 30' W 1.10 chs dist each marked 1/4 S B T	13.55 15.70
75.00	Ravine drns S E	
79.46	The cor to secs 5, 6, 7 & 8 Land Mountainous and rolling plateau Soil 2nd & 3rd rk	17.70 40.45

Subdivisions T39S R6W S.L.M.

Dense undergrowth
sage & sarvisberry brush
on 79.46 chs.
Heavy pine timber on 79.46 chs
West on a random line
bet secs 6 & 7
Var 15° 20' E
40.00 Set temp 1/4 sec cor
80.45 Intersect W boundary 75
lks N of the cor to secs 1
6, 7, & 12 which is a sandstone 8 x 10
& stone mound alongside
x 6" above ground, properly marked B heavy trees,
Thence Trun
N 89° 28' E on a true line
bet secs 6 & 7
with same var
13.55 Wash in Canyon drs S 5 chs
to Main Canyon
15.70 Road to Saw Mill in
Canyon 5 chs wide drs SW
17.70 Ridge decends abruptly NE
40.45 Set flint stone 24 x 12 x 4 ins
19" in the ground for 1/4 sec
Cor, marked 1/4 on N face

Subdivision T 39 S R 6 W S L M

from which
A pine tree 10 ins in dia
bears N 11° W, 15 lks dist
A pine tree 20 ins in diam
bears S 47° E, 38 lks dist each
marked 1/4 S B T

46.00 Ravine drs W
76.00 Decend
80.45 The Cor to secs 5, 6, 7 & 8
Land Mountainous
Soil 3rd rak
Timber, pine on 80.45 chs
Dense undergrowth
sage & oak brush on 80.45
chs.

North on a random
line bet secs 5 & 6
Var 15° 20' E
40.00 Set temp 1/4 sec cor
81.15 Intersect N boundary of
Tp 85 lks E of the cor to
secs 5, 6, 31 & 32
Thence Trun

BOOK-A-203

Subdivisions T39S R6W. S L M

S 0° 36' E on a true line
bet secs 5 & 6
with same Var
18.50 Ravine descends W
41.15 Set lime stone 15 x 12 x 7
10 ins in the ground for 1/4 sec
cor, marked 1/4 on W face
from which
A pine tree 4 ins in diam
bears S 86° W 14 lks dist
A pine tree 8 ins in diam
bears N 45° E 30 lks dist
each marked 1/4 S B T
45.00 Ridge descends S W
46.60 Ravine drains W
47.15 The cor to secs 5, 6, 7 & 8
Land mountainous
Soil 3rd rate
Heavy pine timber on 81.15 chs
Dense undergrowth oak
sarvesberry & choke cherry
bush on 81.15 chs

May 31st 87.

Subdivisions T39 S R6 W SL4 Sub.

BOOK-A-203

Sub. T. 39 S. R. 6 W. Salt Lake Mer.

General Description

This township contains a variety of land consisting of mountains hills and narrow valleys and the soil ranges from rock to rich loam composed of decayed vegitation

The soil of the bottom lands along the Kanab Cr. and Chiquo or Long Valley Cr. and the low benches is generaly rich sandy loam capable of producing abundant crops without irrigation.

The soil of the remaining portions of the township except the abrupt and precipitous mountains can nearly all be classed as first & second rate and is covered with an abundant growth of Wild oats and other

rich and nutritious grasses it is pastured extensively by Cattle Sheep and horses. Is heavily timbered with pine timber There is a settlement in Secs. 9 and 16 with post office saw mill, shingle mill school house &c John H. Miles the applicant is living with his family in sec 16 [illegible]

The land along the Kanab Cr. is highly cultivated as farms meadows and gardens and there are a number of settlers along the Cr.

There is Coal of excellent quallity discovered in Sec 15.

Shadrach M Richardson
U. S. Deputy Surveyor

15 X 15 feet and has a barn corrals &c and a field fenced ~~25 acres of land &c~~ and about 25 acres highly cultivated as a farm and meadow land

Blank

Page

BOOK-A-203

14—LIST OF NAMES.]

A list of the names of the individuals employed by Shadrach M. Richardson *United States deputy surveyor, to assist in running, measuring, and marking the lines and corners described in the foregoing field notes of the survey of* Township 39 S. R. 6 W.

of the Salt Lake base and meridian in the Territory of Utah, showing the respective capacities in which they acted.

	Compassman.
Richard Heel	*Chainman.*
E. V. Haney	*Chainman.*
John E. Cook	*Chainman.*
Oscar Lovanger	*Chainman.*
Moroni O. Brown	*Axeman.*
John H. Miles	*Axeman.*
Lewis W. Wilson	*Flagman.*

Blank

Page

[5.—FINAL OATHS OF ASSISTANTS.]

We hereby certify that we assisted Shadrach M. Richardson United States deputy surveyor, in surveying all those parts or portions of the Exterior and Subdivision of township 39 South, range 6 west

of the Salt Lake base and meridian in the Territory of Utah, as are represented in the foregoing field notes as having been surveyed by him and under his direction; and that said survey has been in all respects, to the best of our knowledge and belief, well and faithfully surveyed, and the corner monuments established according to the instructions furnished by the United States surveyor-general for Utah.

, Compassman.

his mark Richard X Keel, Chainman.

Ev Hamy, Chainman.

John E Cook, Chainman.

Oak Lovomyk, Chainman.

Moroni A. Brown, Axeman.

John H. Miles, Axeman.

his mark Levi W. X Wilson, Flagman.

Subscribed and sworn to before me this 31st day of May 1884

Ernst Salomon
Notary Public

Blank

Page

BOOK-A-203

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, Feby 21 *1885*

The foregoing field notes of the survey of the Subdivisions

Township No. 39 S *Range No.* 6 W

Executed by Shadrach M Richardson

Under his *contract of the* 19th

day of December *1883, in the month of*

May *1884, having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

Fred Salomon

U. S. Surveyor General for Utah.

Blank

Page

BOOK-A-203

1/11

135

REPORT: 1885

Filed 188

Examined by John H. Campe

Transcribed by Henry J. McAtkinson

Compared by O.E.S. & H.R.M.A.

FIELD NOTES

OF THE SURVEY OF THE

East Boundary and

Re-Survey of the

West Boundary

OF

Township No 9 North

Range No 13 West

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Henry Fitzhugh

U. S. Deputy Surveyor,

Under his Contract No. 124

Dated March 19 1884

Survey commenced May 14 1884

Survey completed " " 1884

Re-Survey 144

W. By. Tp. 9 N. R 13 W. S L M.

Chains	
80.00	Regulation Mound & Pits
	Find Cor. standing, as set by
	me under Contract No. 116
	during the present month,
	for Cor. to Tps. 8 & 9 N. Rs.
	13 & 14 W
	Land Alkali flat
	Soil 4th rate
	Some scat. Shadscale

~~General Description.~~

~~For General Description~~
~~See end of subdivisional~~
~~Notes of T. 9 N. R. 13 W.~~
~~Henry Fitzhugh~~
~~U.S. Deputy Surveyor~~

E By. T. 9 N. R. 13 W. S L M

Chains From the Cor. to Tps. 8 & 9 N. Rs. 12 & 13 W. on the 2nd Standard Parallel North set by me under Contract No. 116 during the present month I run

North on random line Bet. Said Tps. setting Temporary half mile & mile Cors. at each 40 & 80 Chs. The Va of my transit being 18° 10' E. At 5 miles and 79 chains I intersect the North boundary of the township 190 Sks. E. of the Cor. to Tps. 9 & 10 N. Rs. 12 & 13 W. The Correction for the true line will therefore be N. 0° 13' W.

From the Cor. to Tps. 8 & 9 N. Rs. 12 & 13 W.

I run

North 0° 13' W. on true line

E. By. Tp. 9 N. R. 13 W.

Chains	
	Bet Secs. 31 & 36.
	Vr 18° 10' E.
0.40	Gully drains N.W.
21.50	" " W.
29.60	" " W.
40.00	Set Flint 12 x 8 x 6 ins - 8 ins in the ground for 1/4 Sec. Cor. marked 1/4 on W. face and made regulation mound & pits
73.00	Gully drains W.
80.00	Set Flint 16 x 10 x 10 ins - 10 ins. in the ground for Cor. to Secs. 25, 30, 31 & 36, marked 1 notch on S. & 5 notches on N. edges and made regulation mound & pits.
	Land rolling bench
	Soil 1st rate
	Dense sage brush & shadscale undergrowth on 80.00 chs.
	North 0° 13' W. on true line
	Bet. Secs. 25 & 30.

Chains
24.50
40.00
59.25
80.00
40.0

S. L. M.

Chains

Va 18°10' E

24.50 Gully drains N.W.

40.00 Set Flint 12×7×6 ins - 8 ins. in the ground for 1/4 Sec. Cor. Marked 1/4 on W. face and made regulation mound & pits

59.25 Gully drains N.W.

80.00 Set Flint 14×12×6 ins - 10 ins. in the ground for Cor. to Secs. 19, 24, 25 & 30, Marked 2 Notches on S. & 4 on N. edges and made regulation mound & pits.

Sand bench

Soil 1st rate.

Dense sage brush & shadscale

Undergrowth on 80.00 chs

North 0°13' W. on true line Bet. Secs. 19 & 24

Va 18°10' E.

40.00 Set Limestone 16×10×10 ins. 10 ins. in the ground for 1/4 Sec

E. By. T. 9 N. R. 13 W.

Chains		Chains
	Cor. marked 1/4 on W. face and made regulation mound & pits.	76.20
43.50	Wash drains N.W.	80.00
64.50	" " "	
69.50	" " "	
80.00	Set Limestone 15×9×5 ins - 10 ins. in the ground for Cor. to Secs. 13, 18, 19 & 24, marked 3 notches on N. & S. edges and made regulation mound & pits	
	Land bench	
	Soil 1st rate	
	Dense sage brush & Greasewood underground on 80.00 chs.	
		25.0
	N. 0° 8' 3" W. on true line Bet. Secs. 13 & 18	30.10
	Va 18° 10' E.	40.0
~~0.0~~	Enter flat bears E. & W.	
40.00	Set Limestone 12×8×6 ins - 8 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on W. face, and	59.20

S. L. M

Chains	Made regulation mound & pits
76.25	Wash drains N.W.
80.00	Set Volcanic Rock 12×10×5 ins. 8 ins. in the ground for Cor. to Secs. 7, 12, 13 & 18 marked 4 notches on S. & 2 on N. edges and made regulation mound & pits
	Land flat
	Soil 1st rate
	Dense Sage brush & shadscale undergrowth on 80.00 chs.
	N. 0° 13' W. on true line Bet. Secs. 7 & 12 Va 18° 10' E.
25.00	Wash drains N.W.
30.10	" " W.
40.00	Set Limestone 12×8×8 ins - 8 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on W. face and made regulation mound & pits.
59.25	Wash drains W.

E By. Tp 9. N. R. 13 W

Chains		Chains
80.00	Set Volcanic Rock 13×9×9 ins 11 ins. in the ground for Cor. to Secs. 1, 6, 7 & 12 marked 5 notches on S. & 1 notch on N. edges and made regulation mound & pits.	
	Land flat	
	Soil 1st rate	
	Dense Sage brush & Greasewood	
	Undergrowth on 80.00 chs.	
	N. 0° - 13' W. On true line	
	Bet Secs. 1 & 6	
	Va 18° 10' E.	
40.00	Set Volcanic Rock 15×12×6 ins - 10 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on W. face and made regulation mound & pits	
74.25	Wash drains S.W.	
79.00	The Cor. to Tps. 9 & 10 N. Rs. 12 & 13 W.	
	Land flat	
	Soil 1st rate.	

BOOK-A-203

S. L. M.

Chains Dense Sage brush & shadscale
Undergrowth on 79.00 chs.
May 14. 1884

General Description
For general description
see end of Subdivisional
Notes of Tp. 9. N. R. 13 W.
Henry Fitzhugh
U.S. Deputy Surveyor.

Blank

Page

BOOK-A-203

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah. October 11th 1884

The foregoing field notes of the survey of the East and resurvey of the West boundary *Township No.* 9 North *Range No.* 13 West *Executed by* Henry Fitzhugh *Under* No 124 *contract of the* 19th *day of* March 1884, *in the month of* May 1884, *having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

Fred Salomon

U. S. Surveyor General for Utah.

Blank

Page

BOOK A-203 1885

5

155

REPORT: 1885

Filed 188

Examined by John H. Campe

Transcribed by E. Michaelis

Compared by Atkinson & Michaelis

FIELD NOTES

OF THE SURVEY OF THE

Subdivision Lines

OF

Township No 9 North

Range No 13 West

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Henry Fitzhugh

U. S. Deputy Surveyor,

Under his Contract No. 124

Dated March 19 1884

Survey commenced May 15th 1884

Survey completed " 21st 1884

BOOK-A-203

Township 9 N. R. 13 W.

138	6	214	5	199	4	188	3	178	2	166	1	150
	213		212		198		187		177		165	
139	7	211	8	197	9	186	10	176	11	164	12	149
	210		209		196		185		175		163	
140	18	208	17	195	16	185	15	174	14	162	13	148
	207		206		194		184		173		161	
141	19	205	20	193	21	183	22	172	23	161	24	147
	204		203		192		182		171		160	
142	30	203	29	191	28	181	27	170	26	159	25	146
	202		201		190		180		169		158	
143	31	200	32	189	33	179	34	168	35	157	36	145

Subs. T. 9 N. R. 13 W. S. L. M.

Chains	
	Survey commenced May 15, 1884 with a Burts improved Solar Compass
	From the Cor. to Secs. , 35, & 36 on the 2nd Standard Parallel North set by me during the present month under Contract No. 116
	I run North Bet. Secs. 35 & 36 Va 18°10' E.
40.00	Set charred pine post 3 ft. long 3 ins. square 12 ins. in the ground for 1/4 Sec. Cor. marked 1/4 S. on W. face, and made regulation mound & pits
80.00	Set Volcanic rock 16 x 8 x 5 ins. 10 ins. in the ground for Cor. to Secs. 25, 26, 35 & 36, marked 1 notch on S & E. edges, and made regulation mound & pits.

Subdivisions T. 9 N.

Chains

Sand level
Soil 1st rate
Dense sage brush & greasewood
undergrowth on 80.00 chs.

East on random line
Bet. Secs. 25 & 36
Va 18° 10' E.

40.00 Set temporary 1/4 Sec. Cor.
80.14 Intersect E. Bry. of Township
48 lks. N. of Cor. to Secs. 25,
30, 31 & 36 set by me dur-
ing this survey
Thence I run
N. 89° 42' W. on true line
Bet. Secs. 25 & 36.
With same Va

40.07 Set charred pine post 3 ft.
long 3 ins. square, 12 ins.
in the ground for 1/4 Sec.
Cor. Marked 1/4 S. on N. face
and made regulation
mound of pits
80.14 The Cor. to Secs. 25, 26, 35 & 36

R. 13 W - S. L. M

Chain	
	Land bench Soil 1st rate Dense sage brush & Greasewood Undergrowth on 80.14 chs.
	North Bet. Secs. 25 & 26 Va 18° 10' E
40.00	Set Volcanic rock 15 x 12 x 5 ins. 10 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on W. face and made regulation mound & pits
64.00	Levee bench Enter flat bears E & W
80.00	Set Volcanic rock 36 x 12 x 8 ins 27 ins. in the ground for Cor. to Secs. 23, 24, 25 & 26, marked 2 notches on S. & 1 notch on E. edges and made regu- lation mound & pits.
	Land bench & flat Soil 1st rate Dense sage brush & Greasewood Undergrowth on 80.00 chs.

Subdivisions - T. 9 N

Chains	East on random line
	Bet Secs. 24 & 25
	Lat 18° 10' E.
40.00	Set Temporary 1/4 Sec. Cor.
50.30	Intersect E. Bdy. of Township
	51 Rds. N. of cor. to Secs.
	19, 24, 25 & 30 set by me
	during this Survey
	Thence Same
	N. 89° 38' W. on the line
	Bet. Secs. 24 & 25
	With same Lat
40.15	Set Redwood post 3 ft. long
	3 ins. square, 12 ins. in the
	ground for 1/4 Sec. Cor.
	marked 1/4 S. on N. face and
	made regulation mound & pits
72.55	Place brush
	Entry flat bears N.E. & S.W.
80.30	The line to Secs. 23, 24, 25 & 26
	Land brush & flat
	Soil 1st Rate
	Dense sage brush & greasewood
	undergrowth on 80.30 chs

R. 13. W. L. L. M

Chains	
	North Bet. Secs. 23 & 24 Va 18°.10' E.
33.50	Wash drains N.W.
40.00	Set Volcanic rock 20×12×10 ins. 15 ins in the ground for 1/4 Sec. Cor. Marked 1/4 on W. face & made regulation mound & pits
77.50	Wash drains N.W.
80.00	Set Volcanic rock 30×12×8 ins. 22 ins. in the ground for Cor to Secs. 13, 14, 23 & 24 marked 3 notches on S. & 1 on E. edges & made regulation mound & pits
	Land flat
	Soil 1st rate
	Dense sage brush & Greasewood undergrowth on 8000 chs.
	East on a random line Bet. Secs. 13 & 24 - Va 18°.10' E -
40.00	Set Temporary 1/4 Sec. Cor.
79.90	Intersect E. Bry. of Township 36 Rs. S. of Cor. to Secs. 13, 14, 23 & 24. Set by me during this survey

Subdivisions T. 9 N.

Chains	
	Thence I run
	S. 89° 45' W. on true line Bet. Secs 13 & 24 with same Va
2.40	Leave bench
	Enter flat bears N.E. & S.W.
39.95	Set Charred Redwood post 3 ft. long 3 ins. square, 12 ins. in the ground for 1/4 Sec. Cor. marked 1/4 S. on N. face, and made regulation mound & pits.
79.90	The Cor. to Secs 13, 14, 23 & 24
	Land bench & flat
	Soil 1st rate
	Dense Sage brush & Greasewood
	Undergrowth on 79.90 chs
	North Bet. Secs. 13 & 14
	Va 18° 10' E
4.00	Wash drains N.W.
10.00	" " "
40.00	Set charred redwood post 3 ft. long 3 ins. square, 12 ins. in the ground for 1/4 Sec. Cor. marked 1/4 S. on W. face

R. 13 W. S. L. M.

Chains and made regulation
mound & pits.
80.00 Set Volcanic rock 27 x 16 x 8 ins.
20 ins. in the ground for Cor.
to Secs. 11, 12, 13 & 14, marked
4 notches on S. & 1 notch on E.
edges and made regulation
mound & pits
Sand flat
Soil 1st rate
Dense sage brush & Greasewood
under growth on 80.00 chs.

East on random line
Bet. Secs. 12 & 13
Va 18°.10 E
40.00 Set Temporary 1/4 Sec. Cor.
80.20 Intersect E. By. of Township
47 Rls. N. of Cor. to Secs. 11, 12,
13 & 14 set by me during
this survey
Thence from
N. 89° 40' W. on true line
Bet. Secs. 12 & 13

Subdivisions T. 9 N

Chains	With same Va
26.60	Wash drains S.W.
28.60	" " N.W.
40.10	Set Pine post 3 ft. long 3 ins square, 12 ins. in the ground for 1/4 Sec. Cor. marked 1/4 S. on N. face and made regulation mound & pits.
80.20	The Cor. to Secs. 11, 12, 13 & 14 Pond flat Soil 1st rate Dense sage brush & Greasewood Underwrowth on 80.20 Chs.

North Bet. Secs. 11 & 12
Va 18°.10' E.

10.25	Wash drains S.W.
25.75	" " "
40.00	Set charred redwood post 3 ft. long 3 ins. square - 12 ins. in the ground for 1/4 Sec. Cor. marked 1/4 S. on W. face and made regula=

R. 13 W. S. L. M

Chains	
	tion mound & pits
78.00	Wash drains S. W.
80.00	Set charred Redwood post 4 ft. long 4 ins. square, 12 ins. in the ground for Cor. to Secs. 1, 2, 11 & 12, marked T. 9 N. on N. E. R. 13 W. on S. E. S. 11 on S. W. and S. 2 on N. W faces with 5 notches on S. & 1 notch on E. edges and made regulation mound & pits.
	Sand flat
	Soil 1st rate
	Dense sage brush & Greasewood undergrowth on 80.00 chs.
	East on random line
	Bet. Secs. 1 & 12
	Vn 18° 10' E.
40.00	Set temporary 1/4 Sec. Cor.
79.67	Intersect E. Bry. of Township 48 Sks. S. of Cor. to Secs. 1, 6,

Subdivisions T. 9 N.

Chains	11 & 12 set by me during this survey
	Thence I run
	S. 89° 39' W. on true line
	Bet. Secs. 1 & 12
	With same Do
39.83	Set Charred Pine post 3 ft. long 3 ins. square, 12 ins. in the ground for 1/4 Sec. Cor. Marked 1/4 S. on N. face and made regulation mound & pits
69.70	Wash drains S. W.
75.50	" " "
79.67	The Cor. to Secs. 1, 2, 11 & 12
	Sand flat
	Soil 1st rate
	Dense sage brush & Greasewood undergrowth on 79.67. Chs.
	North on random line
	Bet. Secs. 1 & 2
	Do 18° 10' E.
40.00	Set Temporary 1/4 Sec. Cor.

R. 13 W. - S. L. M.

Chains	
79.66	Intersect N. By. of Township 61 Rs. E. of Cor. to Secs. 1, 2, 35 & 36 re-established by me during this survey
	Thence I run
	S. 0°-26' E. on true line
	Bet. Secs. 1 & 2
	With same Va
39.66	Set Charred redwood post 3 ft. long 3 ins. square, 2 ins. in the ground for 1/4 Sec. Cor. Marked 1/4 S. on W. face & made regulation mound & pits
63.40	Wash arains S.W.
70.00	" "
79.66	the Cor. to "Secs." 1, 2, 11 & 12
	Sand flat
	Soil 1st rate
	Dense sage brush & Greasewood undergrowth on 79.66 chs.

May 15. 1884

Subdivisions T. 9 N

Chains	From the Cor. to Secs. 34 & 35 on the 2nd Standard Parallel North - Set by me during the present month under Contract No. 116	Chains
	Iron	
	North Bet. Secs. 34 & 35	
	Dn 18°.10' E	
	Through sage brush & Greasewood	
40.00	Set Charred redwood post 3 ft. long 3 ins. square, 12 ins. in the ground for 1/4 Sec. Cor. marked 1/4 S. on W. face and made regulation mound & pits	40.00 80.2
80.00	Set Charred redwood post 4 ft. long 4 ins. square, 12 ins. in the ground for Cor. to Secs. 26, 27, 34 & 35, marked T. 9 N. on N.E. R. 13 W. on S.E. S. 34 on S.W. S. 27 on N.W. with 1 notch on S. & 2 notches on E. edges, and made	40.00 80.2

R. 13 W. - S. L. M.

Chains	regulation mound & pits
	Land bench
	Soil 1st rate
	Dense Sage brush & Greasewood
	Undergrowth on 80.00 chs.
	East on random line
	Bet. Secs. 26 & 35
	Va 18°.10' E.
40.00	Set Temporary 1/4 Sec. Cor.
80.27	Intersect N. & S. line 16 Sks.
	N. of Cor. to Secs. 25, 26, 35 & 36
	Thence I run
	N. 89° 53' W. on true line
	Bet. Secs. 26 & 35
	With same Va
40.23	Set Volcanic rock 30 x 12 x 12
	ins. 22 ins. in the ground for
	1/4 Sec. Cor. marked 1/4 on N.
	face and made regulation
	mound & pits.
80.27	The Cor. to Secs. 26, 27, 34 & 35
	Land bench
	Soil 1st rate

Subdivisions T. 9 N

Chains	Dense sage brush & shadscale undergrowth on 80.27 Chs.
	North Bet. Secs. 26 & 27 Vn 18.10 E
18.80	Wash drains S.W.
40.00	Set Cobble stone 12 x 8 x 8 ins - 8 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on N. face and made regulation. Mound & pits
65.00	Leave bench
	Enter flat bears E & W.
80.00	Set Charred redwood post 4 ft. long 4 ins. square, 12 ins in the ground for Cor. to Secs. 22, 23, 26 & 27 marked. T. 9 N. on N.E. R. 13 W. " S.E. S. 27 on S.W. S. 22 on N.W. faces with 2 notches on S & E edges and made regulation mound & pits.

R. 13 W. - S. L. M.

Chains	
	Land bench & flat Soil 1st rate Dense sage brush & Greasewood Undergrowth on 80.00 chs.
	East on random line Bet. Secs. 23 & 26 Va 18°.10' E
40.00	Set Temporary 1/4 Sec. Cor.
80.00	Intersect N & S. line 15 Rks. N. of Cor. to Secs. 23, 24, 25 & 26 Thence I run N. 89° 54' W. on true line Bet. Secs. 23 & 26 with same Va ~~18°.10' E~~
40.00	Set Charred redwood post 3 ft. long 3 ins. square 12 ins. in the ground for 1/4 Sec. Cor. marked 1/4 S. on N. face and made regulation mound & pits
43.00	Wash drains N. W.
58.00	" " "
71.50	" " "

Subdivisions - T. 9 N.

Chains	
80.00	The Cor. to Secs. 22, 23, 26 & 27
	Land flat
	Soil 1st rate
	Dense Sage brush & Greasewood
	Undergrowth on 80.00 Chs.
	North Bet. Secs. 22 & 23
	Va 18°.10' E
40.00	Set Charred Pine post 3 ft.
	long 3 ins. square, 12 ins. in
	the ground for 1/4 Sec. Cor.
	marked 1/4 S. on W. face
	and made regulation
	mound & pits
41.25	Wash drains N.W.
67.75	" " W.
80.00	Set charred redwood post 4 ft.
	long 4 ins. square, 12 ins. in
	the ground for Cor. to Secs.
	14, 15, 22 & 23, marked.
	T. 9. N. on N.E.
	R. 13 W. " S.E.
	S. 22 on S. W. and
	S. 15 on N.W. faces

BOOK-A-205

R. 13 W. — S. L. M.

	With 3 notches on S. & 2 on E.
	edges, and made regulation mound & pits
	Land level
	Soil 1st rate
	Dense sage brush & greasewood
	Undergrowth on 8000 chs.
	East on random line
	Bet. Secs 14 & 23
	Va 18° 10' E
40.00	Set temporary 1/4 Sec. Cor.
79.68	Intersect N. & S. line 21 8 Rs.
	S. of Cor. to Secs. 13, 14, 23 & 24
	Thence Imm
	S. 89° 51' W. on true line
	Bet. Secs. 14 & 23
	With same Va
3.00	Wash arams N. W.
5.50	" " "
32.00	" " "
39.84	Set charred redwood post 3 ft. long 3 ins. square, 12 ins. in the ground for 1/4 Sec. Cor.

Subdivisions T. 9 N

Chains	
	Marked 1/4 S. on N. face and made regulation mound & pits
79.68	The Cor. to Secs. 14, 15, 22 & 2
	Sand flat
	Soil 1st rate
	Dense sage brush & shadrea underground on 79.68 chs
	North Bet Secs. 14 & 15 Va 18°10' E.
8.25	Wash drains S.W.
28.50	" " "
40.00	Set charred redwood post 3 ft. long 3 ins. square, 12 ins. in the ground for 1/4 Sec. Cor. marked 1/4 S. on W. face, and made regulation mound & pits
80.00	Set charred pine post 4 ft. long 4 ins. square, 12 ins. in the ground for Cor. to Secs. 10, 11, 14 & 15, marked T. 9 N. on N.E.

R. 1

Chains	
	With E. ... tion Land, dense ... on ...
	Ea...
40.00	Set
79.83	Int... of C... Thu... S. 8...
9.00	Was...
29.00	"
37.00	"
39.91	Set ... long ... grou... 1/4 S.

R. 13 W. S. L. M.

Chains	
	R. 13 W. on S.E.
	S. 15 on S.W. and
	S. 10 on N.W. faces
	With 4 notches on S & 2 on
	E. edges and made regulation mound & pits
	Land, flat. soil, 1st rate
	Dense sagebrush & greasewood undergrowth on 80. chs.
	East on random line
	Bet. Secs. 11 & 14
	Vra 18°.10' E.
4.00	Set Temporary 1/4 Sec. Cor.
79.83	Intersect N & S. line 20 Hks. S.
	of Cor. to Secs. 11. 12, 13 & 14
	Thence I run
	S. 89°.51' W. on true line
	Bet. Secs. 11 & 14
	With same Dra
9.00	Wash drains S.W.
29.00	" " "
37.00	" " "
39.91	Set charred redwood post 3 ft.
	long 3 ins. square 12 ins. in the
	ground for 1/4 Sec. Cor. marked
	1/4 S. on N. face, and

Subdivisions T. 9 N.

Chains	Made regulation Mound & pits
79.83	The Cor. to Secs. 10, 11, 14 & 15
	Land flat
	Soil 1st rate
	Dense sage brush & Greasewood
	undergrowth on 79.83 Chs
	North Bet. Secs. 10 & 11
	Va 18°10' E
16.00	Wash drains S.W.
36.25	" " W.
40.00	Set charred redwood post 3 ft.
	long 3 ins square, 12 ins. in
	the ground for 1/4 Sec. Cor.
	Marked 1/4 S. on W. face
	and made regulation
	mound & pits
48.50	Wash drains W.
62.00	Wash drains S.W.
80.00	Set sandstone 20 x 8 x 5 ins - 15
	ins. in the ground for Cor.
	to Secs. 2, 3, 10 & 11. marked
	5 notches on S. & 2 on E.
	edges, and made regulation

BOOK

R.

Chains	Mo
	Dr
	un
	Eas
40.00	Set
80.15	Int
	Of C
	Thr
	N. 8
8.25	W
40.07	Set
	len
	the
	Ma
	an
	Mo
80.15	The

R. 13 W. S. L. M.

Chain	Mound & pits.
	Sand flat
	Soil 1st rate
	Dense Sage brush & Greasewood
	Underground on 8000 Chs.
	East on random line
	Bet. Secs. 2 & 11
	Va 18° 10' E
40.00	Set Temporary 1/4 Sec. Cor.
80.15	Intersect N. & S. line 14 8 Ks. N.
	Of Cor. to Secs. 1, 2, 11 & 12
	Thence Inn
	N. 89° 54' W. on true line
	Bet. Secs. 2 & 11
	With same Va
8.25	Wash arains S W
40.07	Set Charred Pine post 3 ft.
	long 3 ins. square, 12 ins. in
	the ground for 1/4 Sec. Cor.
	Marked 1/4 S. on N. face
	and made regulation
	Mound & pits
80.15	The Cor. to Secs. 2, 3, 10 & 11

Subdivisions T. 9 N.

Chains	Land flat Soil 1st rate Dense sage brush & shadscale Undergrowth on 80.15 chs.
	North on random line Bet. Secs. 2 & 3 Va 18°.10' E
40.00	Set Temporary 1/4 Sec. Cor.
79.55	Intersect N. By. of Township 42 Rks. E. of Cor. to Secs. 2, 3, 34 & 35 re-established by me during this survey Thence I run S. 0° 12' E. on true line Bet. Secs. 2 & 3 With same Va
39.55	Set Redwood (charred) stake 3 ft. long 3 ins. square, 12 ins. in the ground for 1/4 Sec. Cor. marked 1/4 S. on W. face and made regulation mound & pits
79.55	The Cor. to Secs. 2, 3, 10 & 11

R. 13 W - S. L. M

Chaix	Land flat Soil 1st rate Dense sage brush & Greasewood Undergrowth on 79.55 chs May 16. 1884
	From the Cor. to Secs. 33 & 34 on the 2nd Standard Parallel North - set by me during this month, under Contract No. 116 I run North Bet. Secs. 33 & 34 Va 18.10 E
	Through dense sage brush & Greasewood
31.00	Wash drains N.E.
38.00	Same wash drains N.W.
40.00	Set Volcanic rock 16 x 12 x 4 ins 10 ins in the ground for 1/4 Sec. Cor. Marked 1/4 on W. face and made regulation Mound & pits
80.00	Set Sinistone 16 x 8 x 4 ins. 10

Subdivisions T. 9 N.

Chains	
80.00	Intersect N. & S. line 22 lks. S. of Cor. to Secs. 10, 11, 14 & 15 thence same S. 89° 51' W. on the line Bet. Secs. 10 & 15 With same Va
20.60	Wash drains S. W.
36.75	" " "
40.00	Set Charred Redwood post 3 ft. long 6 in. square, 12 in. in the ground for 1/4 Sec. Cor. marked 1/4 S. on N. face and made regulation mound & pits
55.00	Wash drains S. W.
67.25	" " "
71.50	" " "
80.00	The Cor. to Secs. 9, 10, 15 & 16 Sand flat Soil 1st rate Dense sage brush & shadscale undergrowth on 80.00 chs.

North Bet. Secs. 9 & 10
Va 18° 10' E.

Chains	
40.00	
57.25	
61.50	
80.00	
40.00	
80.20	

Subdivisions T. 9 N

Chains	
	ins. in the ground for Cor to Secs. 27, 28, 33 & 34 marked 1 notch on S. & 3 notches on E. Edges and made regulation mound & pits.
	Land flat
	Soil 1st rate
	Dense sage brush & Greasewood undergrowth on 80.00 chs
	East on random line
	Bet. Secs. 27 & 34
	Va 18.10 E.
40.00	Set temporary 1/4 Sec. Cor.
79.88	Intersect N. & S. line 26 8 Ks. S. of Cor. to Secs. 27, 28, 33 & 34
	Thence I run
	S. 89° 49' W. on true line
	Bet. Secs. 27 & 34
	With same Va
30.00	Wash arains N. W.
39.94	Set Conglomerate 12 & 8 & 6 ins. 8 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on N. face

R. 1

Chains	
	an
	ma
79.88	The
	Dru
	und
	Nor
40.00	Set
	in
	ma
	ma
64.25	Wa
66.00	Wa
80.00	Set
	15 in
	Sec
	2
	edg
	Ma

R. 13 W. – S. L. M.

Grants	and made regulation mound & pits
79.88	The Cor. to Secs. 27, 28, 33 & 34
	Land flat
	Soil 1st rate
	Dense sage brush & Greasewood undergrowth on 79.88 chs.
	North Bet. Secs. 27 & 28
	Va 18°.10' E.
40.00	Set Priest one 12 x 12 x 4 ins. 8 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on W. face and made regulation mound & pits
64.25	Wash arains S.W.
66.00	Wash arains S.W.
80.00	Set Volcanic rock 20 x 6 x 4 ins 15 ins. in the ground for Cor. to Secs. 21, 22, 27 & 28, marked 2 notches on S. & 3 on E. edges and made regulation mound & pits
	Land bench
	Soil 1st rate

Subdivisions T. 9 N

Chains	Dense sage brush & Greasewood Undergrowth on 80.00 Chs.	Chains
	East on random line	
	Bet. Secs. 22 & 27	18.00
	Va 18° 10' E	23.00
40.00	Set Temporary 1/4 Sec. Cor.	
79.58	Intersect N. & S. line 25 Mi. S.	36.00
	of Cor. to Secs. 22, 23, 26 & 27	40.00
	Thence Iron	
	S. 89° 49' W. on true line	
	Bet. Secs. 22 & 27	
	With same Va	
39.79	Set Charred Pine post. 3 ft. long	80.00
	3 ins. square, 12 ins. in the	
	ground for 1/4 Sec. Cor. marked	
	1/4 S. on N. face & Made regu-	
	lation mound & pits.	
51.60	Leave flat	
	Entre Bench bears N.W. & S.E.	
79.58	The Cor. to Secs. 21, 22, 27 & 28	
	Sand flat & bench	
	Soil 1st rate	
	Dense sage brush & Greasewood	

R. 13 W. S. L. M.

Chains	undergrowth on 79.58 chs.
	North Bet. Secs. 21 & 22 Vn 18° 10' E
18.00	Volcanic Knoll
23.00	Leave bench
	Enter flat bears N.W. & S.E.
36.00	Wash drains S.W.
40.00	Set Volcanic rock 15×12×8 ins 10 ins. in the ground for 1/4 Sec. Cor. Marked 1/4 on W. face and made regulation mound & pits
80.00	Set Volcanic rock 15×13×3 ins 10 ins. in the ground for Cor. to Secs. 15, 16, 21 & 22, marked 3 notches on S. & E. edges and made regulation mound & pits
	Land bench & flat
	Soil 1st rate
	Dense sage brush & Greasewood undergrowth on 80.00 chs.

Subdivisions T. 9 N.

Chains	
	East on random line
	Bet. Secs. 15 & 22
	Va 18° 10' E
40.00	Set Temporary 1/4 Sec. Cor.
80.00	Intersect N & S. line 10 Rks. N.
	of Cor. to Secs. 14, 15, 22 & 23
	Thence Iron
	N. 89° 56' W on true line
	Bet. Secs. 15 & 22
	With same Va
18.75	Wash drains S.
23.00	" " S.W.
40.00	Set Charred redwood post 3 ft.
	long 3 ins. & square, 12 ins. in
	the ground for 1/4 Sec. Cor.
	marked 1/4 S. on N. face and
	made regulation mound & pits
53.10	Wash drains S.E.
57.50	Bend of wash heads N. drains N.E.
59.00	Wash drains S.
80.00	The Cor. to Secs. 15, 16, 21 & 22
	Sand flat
	Soil 1st rate
	Dense sage brush & shadscale
	Undergrowth on 8000 Chs.

K.

Chains	
	N.
19.25	[illegible]
40.00	[illegible]
	[illegible]
	[illegible]
	[illegible]
45.00	[illegible]
67.90	
80.00	[illegible]
	12
	Se[illegible]
	no[illegible]
	a[illegible]
	[illegible]
	[illegible]
	[illegible]
	E[illegible]
40.00	[illegible]

R. 13 W. - S. L. M

Chains	North Bet. Secs. 15 & 16 Va 18°.10' E
19.25	Wash drains S.E.
40.00	Set Limestone 12×8×6 ins - 8 ins in the ground for 1/4 Sec. Cor. marked 1/4 on W. face and made regulation mound & pits
45.00	Wash drains S.E.
67.90	" " "
80.00	Set Volcanic rock 18×8×6 ins - 12 ins. in the ground for Cor. to Secs. 9, 10, 15 & 16, marked 4 notches on S. & 3 on E. edges and made regulation mound & pits
	Land flat Soil 1st rate Dense Sage brush & Greasewood Undergrowth on 80.00 Chs.
	East on random line Bet. Secs. 10 & 15 Va 18°-10' E.
40.00	Set Temporary 1/4 Sec. Cor.

R. 13 W. - S. L. M.

Chains	
40.00	Set Prime stone 12 x 9 x 6 ins - 8 ins in the ground for 1/4 Sec Cor. marked 1/4 on W. face and made regulation mound & pits
57.25	Wash drains S.E.
61.50	Wash " "
80.00	Set Volcanic stone 20 x 20 x 8 ins - 15 ins in the ground for Cor. to Secs. 3, 4, 9 & 10, marked 5 notches on S. & 3 on E. edges and made regulation mound & pits.

Land flat

Soil 1st rate

Dense sage brush & shadscale undergrowth on 80.00 Chs.

East on random line

Bet. Secs. 3 & 10

Va 18° 10' E

40.00	Set Temporary 1/4 Sec. Cor.
80.20	Intersect N.S. line 30 Lks. S. of Cor. to Secs. 2, 3, 10 & 11

Thence I run

Subdivisions T. 9 N.

Chains	
	S. 89° 47' W. on true line Bet. Secs. 3 & 10 With same Va
40.10	Set Limestone 12×10×8 ins - 8 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on N. face and made regulation mound & pits.
80.20	The Cor. to Secs. 3. 4. 9 & 10 Land flat Soil 1st rate Dense sage brush & Greasewood undergrowth on 80.20 chs.
	North on random line Bet. Secs. 3 & 4 Va 18° 10' E.
40.00	Set Temporary 1/4 Sec. Cor.
79.30	Intersect N. Bry. of Township 26 Rs. W. of Cor. to Secs. 3, 4, 33 & 34 Thence I run
	S. 0° 11' W. on true line Bet. Secs. 3 & 4 With same Va

BOOK-A-203

R. 13 W. S. L. M.

Chains	
39.30	Set Limestone 12×8×6 ins. 8 ins. in the ground for 1/4 Sec. Cor. Marked 1/4 on W. side and made regulation mound & pits
79.30	The Cor. to Secs. 3, 4, 9 & 10
	Land flat
	Soil 1st rate
	Dense Sage brush & Greasewood Undergrowth on 79.30 chs.
	— May 17. 1884
	From the Cor. to Secs 32 & 33 on the 2nd Standard Parallel North set by me during the present month under contract No. 116
	I run
	North Bet. Secs. 32 & 33
	Va 18°10' E.
	Over alkali flat.
40.00	Set charred pine post 3 ft. long 3 ins. square, 12 ins. in the ground for 1/4 Sec. Cor.

Subdivisions T. 9. N.

Chains	
	Marked 1/4 S. on W. face and made regulation mound & pits
73.50	Leave Alkali flat.
	Enter dense sage brush & Greasewood
80.00	Set Lime stone 17 x 10 x 8 ins - 12 ins. in the ground for Cor. to Secs. 28, 29, 32 & 33, marked 1 notch on S. & 4 notches on E. edges and made regulation mound & pits.
	Land mostly alkali flat Soil 4th & 1st rate
	Dense sage brush & Greasewood undergrowth on 6.50 chs.
	East on random line Bet. Secs. 28 & 33 Va 18.10' E.
40.00	Set Temporary 1/4 Sec. Cor.
79.49	Intersect N. & S. line 32 Ms. N. of Cor. to Secs. 27, 28, 33 & 34
	Thence I run
	N. 89° 46' W. on true line

R. 13 W. S. L. M

Chains	
	Bet. Secs. 28 & 33
	With Same Va.
19.50	Wash drains S.E.
32.50	Leave bench
	Enter flat bears N.O.S.
39.74	Set charred pine post 3 ft. long 3 ins. square, 12 ins. in the ground for 1/4 Sec. Cor. marked 1/4 S. on N. face, and made regulation mound & pits
79.49	The Cor. to Secs. 28, 29, 32 & 33
	Land flat & bench
	Soil 1st rate
	Dense sage brush & Greasewood Undergrowth on 79.49 chs.
	North Bet. Secs. 28 & 29
	Va 18° 10' E.
40.00	Set Volcanic rock 16 x 8 x 5 ins - 10 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on W. face and made regulation mound & pits
43.00	Wash drains N.W.

Subdivision T. 9 N.

Chains		Chains
62.90	Wash drains N.W.	
80.00	Set Pine Stone 30×16×12 ins. 12 ins. in the ground for Cor. to Secs. 20, 21, 28 & 29, marked 2 notches on S. & 4 on E. edges and made regulation mound & pits	45.0
	Land flat	51.4
	Soil 1st rate	80.4
	Dense Sage brush & Greasewood undergrowth on 80.00 chs.	
	East on random line Bet. Secs. 21 & 28 Va 18° 10' E	
40.00	Set Temporary 1/4 Sec. Cor.	40.00
80.43	Intersect N & S. line 15 Rks S. of Cor to Secs. 21, 22, 27 & 28 Thence from S. 89° 56' W. on true line Bet. Secs. 21 & 28 With same Va	80.0
40.21	In quick drains S. Set Charred pine post 3 ft.	

R. 13 W. S. L. M

Chains	Long 3 ins. square, 12 ins. in the ground for 1/4 Sec. Cor. marked 1/4 S. on N. face and made regulation mound & pits
45.00	Four ridge bears N.W. & S.E.
51.40	Leave bench
	Enter flat bears N.W. & S.E.
80.43	The Cor. to Secs. 20, 21, 28 & 29
	Sand bench & flat
	Soil 1st rate
	Dense sage brush & Greasewood underground on 80.43 chs.
	North Bet. Secs. 20 & 21
	Va 18°10' E
40.00	Set sand stone 14×10×5 ins - 10 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on W. face and made regulation mound & pits
80.00	Set Volcanic rock 22×10×8 ins 15 ins. in the ground for Cor. to Secs. 16, 17, 20 & 21, marked 3 notches on S. & 4 on E. edges and made regulation

Subdivisions. T. 9 N

Chains	Dense sage brush & grease wood underprooth on 80.00 chs.
	East on random line
	Bet. Secs. 9 & 16
	Va 18°.10' E
40.00	Set Temporary 1/4 Sec. Cor.
79.75	Intersect N.d.S. line 40 8 Ks. N.
	of Cor. to Secs. 9.10.15 & 16
	Thence I run
	N. 89.43' W. on true line
	Bet. Secs. 9 & 16
	With same Va
10.50	Wash drains S.W.
39.87	Set Lime stone 12 x 8 x 7 ins - 8 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on N. face and made regulation mound & pits.
57.25	Leave flat
	Enter bench bears N.W. & S.E.
79.75	The Cor. to Secs. 8.9.16 & 17
	Land flat & bench

R. 13 W. S.L.M

Chains	
	Soil 1st rate
	Dense sage brush & Greasewood
	Undergrowth on 79.75 Chs
	North Bet. Secs. 8 & 9
	Va 18°.10' E
12.00	Leave bench
	Enter flat bears N.W. & S.E
40.00	Set Volcanic rock 19×9×4 ins -
	12 ins. in the ground for 1/4
	Sec. Cor. marked 1/4 on W. face
	& made regulation mound & pits
43.75	Wash drains S.E.
75.00	" " "
80.00	Set Conglomerate 14×6×6 ins 10
	ins. in the ground for Cor. to
	Secs. 4, 5, 8 & 9, marked 5
	Notches on S. & 4 on E.
	edges and made regula-
	tion mound & pits
	Sand bench & flat
	Soil 1st rate
	Dense sage brush & Greasewood
	Undergrowth on 80.00 Chs.

Subdivisions T. 9 N

Chains	
	East on random line
	Bet. Secs. 4 & 9
	Va 18°10' E
40.00	Set Temporary 1/4 Sec. Cor.
79.68	Intersect N.&S. line 16 Ms. S.
	of Cor. to Secs. 4, 5, 8 & 9.
	Thence I run
	S. 89°53' W. on true line
	Bet. Secs. 4 & 9
	With same Va
39.84	Set Charred redwood post 3 ft.
	long 3 ins. square, 12 ins. in
	the ground for 1/4 Sec. Cor.
	Marked 1/4 S. on N. face and
	made regulation mound & pits
52.20	Wash drains S.E.
67.00	" " "
75.10	" " "
77.70	" " "
79.68	The Cor. to Secs. 4, 5, 8 & 9.
	Sand flat
	Soil 1st rate
	Dense sage brush & Greasewood
	undergrowth on 79.68 Chs

R. 13 W. S. L. M.

Chains	North on random line
	Bet. Secs. 4 & 5
	Va 18° 10' E
40.00	Set Temporary 1/4 Sec. Cor.
79.40	Intersect N.o.S. line 30 8ks. W. of Cor. to Secs. 4, 5, 32 & 33 re-established by me during this survey
	Thence I run
	S. 0° 13' W on true line
	Bet. Secs. 4 & 5
	With same Va
7.40	Wash drains S.E.
15.00	Leave bench
	Enter flat bears N.E. & S.W.
39.40	Set Volcanic rock 16 x 10 x 8 ins 10 ins. in the ground for 1/4 Sec. Cor. Marked 1/4 on W. face and made regulation mound & pits
47.40	Wash drains S.E.
57.60	" " "
77.50	" " "
79.40	The Cor. to Secs. 4, 5, 8 & 9
	Land flat & bench

Subdivisions T. 9 N

Chains	
	Soil 1st rate
	Dense sage brush & shadscale
	Undergrowth on 79.40 chs.
	May 19. 1884
	From the Cor. to Secs. 31 & 32
	on the 2nd Standard Parallel
	North Set by me during the
	present month under contract
	no. 116
	I run
	North Bet. Secs. 31 & 32
	Va 18°.10' E
40.00	Set charred Redwood post 3 ft.
	long 3 ins. square, 12 ins. in
	the ground for 1/4 Sec. Cor.
	marked 1/4 S. on W. face, and
	made regulation mound & pits
54.50	Wash drains S. W.
80.00	Set Lime stone 16 & 9 & 5 ins - 10
	ins. in the ground for Cor. to
	Secs. 29, 30, 31 & 32 marked 1 notch
	on S. and 5 notches on E.

R. 13 W. - S. L. M

Chains	edges and made regulation mound & pits
	Land alkali flat
	Soil 4th rate
	Some scattering Greasewood
	East on random line
	Bet. Secs. 29 & 32
	Va 18° 10' E
40.00	Set Temporary 1/4 Sec. Cor.
80.00	Intersect N.o S. line 27 Hs. N. of Cor. to Secs. 28, 29, 32 & 33
	Thence Imm
	N. 89° 48' W. on true line
	Bet. Secs. 29 & 32
	Va 18° 10' E.
7.00	Leave sage brush & Greasewood
	Enter Alkali flat or Arm of Great American Desert bears N.W. & S.E.
40.00	Set Lime stone 13 x 8 x 7 ins - 8 ins in the ground for 1/4 Sec. Cor. marked 1/4 on N. face, and made regulation mound & pits

Subdivisions T. 9 N

Chains	
80.00	The Cor. to Secs. 29. 30, 31 & 32
	Land mostly alkali flat
	Soil 1st & 4th rate
	Dense sage brush & Greasewood
	undergrowth on 7.00 Chs.
	West on random line
	Bet. Secs. 30 & 31
	Va 18°10' E.
40.00	Set Temporary 1/4 Sec. Cor.
80.27	Intersect W. By. of Township
	18 Sks. N. of Cor. to Secs. 25. 30
	31 & 36 reestablished by me during this Survey
	Thence Sum
	N. 89°52' E. on true line
	Bet. Secs. 30 & 31.
	Va 18°10' E
40.27	Set Charred pine post. 3 ft.
	long 3 ins. Square, 12 ins. in the
	ground for 1/4 Sec. Cor. marked
	1/4 S. on N. face, and made
	regulation mound & pits
80.27	The Cor. to Secs. 29. 30. 31 & 32
	Land alkali flat.

BOOK-A-203

R. 13 W. S. L. M.

Chains	
	Soil 4th rate
	Some scattering greasewood
	North Bet Secs. 29 & 30
	Va 18°10' E
4000	Set Limestone 12 x 8 x 8 ins - 8 ins in the ground for 1/4 Sec. Cor. marked 1/4 on W. face, and made regulation mound & pits
8000	Set Limestone 15 x 9 x 8 ins - 10 ins. in the ground for Cor. to Secs. 19. 20, 29 & 30, marked 2 notches on S & 5 on E. edges, and made regulation mound & pits
	Land Alkali flat
	Soil 4th rate
	Some Scattering greasewood
	East on random line
	Bet. Secs. 20 & 29
	Va 18°10' E.
4000	Set Temporary 1/4 Sec. Cor.
8010	Intersect N. & S. line 23 Sks. N.

Subdivisions T. 9. N.

		Chains
Chains	of Cor. to Secs. 20, 21, 28 & 29	80.32
	thence Sam	
	N. 89° 50' W. on true line	
	Bet. Secs. 20 & 29	
	Va 18° 10' E.	
40.05	Set charred pine post 3 ft.	
	long 3 ins. square, 12 ins. in	
	the ground for 1/4 Sec. Cor.	
	marked 1/4 on N. face, and	40.32
	made regulation mound & pits	
7.00	Scrub sage brush & greasewood	
	Enter alkali flat or arm of	
	Great American Desert Tract.	
	N. & S.	80.32
80.10	The Cor. to Secs. 19, 20, 29 & 30	
	Sand flat	
	Soil 1st & 4th rate	
	Dense sage brush & greasewood	
	underwoods on 70.00 chs.	
	West on random line	7.25
	Bet. Secs. 19 & 30	19.00
	Va 18° 10' E.	4.00
4.00	Set temporary 1/4 Sec. Cor.	

BOOK-A-205

R. 13 W. S. L. M.

Chains

80.32 Intersect W. By. of Township
29 Ms. R. of Cor. to Secs. 19, 24,
25 & 30, re-established by me during this
survey

Thence Same
N. 89° 48' E. on True line
Bet. Secs. 19 & 30
Va 18° 10' E.

40.32 Set Charred Pine post 3 ft. long
3 ins. square, 12 ins. in the
ground for 1/4 Sec. Cor. marked
1/4 S. on N. face, and made
reflections mound & pits.

80.32 The lev. to Secs. 19, 20, 29 & 30
Land alkali flat
Soil 4th rate
Some scattering greasewood

North Bet. Secs. 19 & 20
Va 18° 10' E

7.25 Stake arrives N.W.
19.50 " " "
40.00 Set Sandstone 13 x 8 x 6 ins - 8 ins.
in the ground for 1/4 Sec. Cor.

Subdivisions T. 9 N.

Chains		Chains
	Marked 1/4 on W. face and made regulation mound & pits	39.90
55.00	Leave Alkali flat	
	Enter Greasewood & sage brush	
80.00	Set Quartzite 18×6×6 ins - 12 ins. in the ground for Cor. to Secs. 17, 18, 19 & 20, marked 3 notches on S. & 5 on E. edges and made regulation mound & pits	45.30
		71.40
		79.80
	Land mostly alkali flat	
	Soil 4th & 1st rate	
	Dense sage brush & Greasewood	
	Undergrowth on 25.00 chs.	
	East on random line	
	Bet. Secs. 17 & 20	40.00
	Va 18°10' E.	80.4
40.00	Set Temporary 1/4 Sec. Cor.	
79.80	Intersect N & S. line 24 Rs. N. of Cor. to Secs. 16, 17, 20 & 21	
	Thence S mn	
	N. 89°50' W. on true line	
	Bet. Secs. 17 & 20	

R. 13 W. S. L. M.

Chains	
	Va 18° 10' E.
39.90	Set Limestone 14x10x6 ins - 10 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on N. face and made regulation Mound & pits
45.30	Wash drains S.
71.40	" " S.E.
79.80	The Cor. to Secs. 17. 18. 19 & 20
	Land flat
	Soil 1st rate
	Dense Sage brush & Greasewood underground on 79.80 Chs.
	West on random line
	Bet. Secs. 18 & 19
	Va 18° 10' E
40.00	Set Temporary 1/4 Sec. Cor.
80.40	Intersect West Bn. of Township 44 8 Rs. N. of Cor. to Secs 13. 18. 19. & 24 re-established by me during this Survey
	Thence I run
	N. 89° 41' E. on true line
	Bet. Secs. 18 & 19

Subdivisions T. 9 N

Chains		Chai
	Va 18°10'E	
5.00	Lower alkali flat - Enter sagebrush & Greasewood	
40.40	Set Charred pine post, 3 ft. long 3 ins. square 12 ins. in the ground for 1/4 Sec. Cor. marked 1/4 S on N. face, and made regulation mound & pits.	
51.40	Wash drains S.W.	
66.35	" " "	
80.40	The Cor. to Secs. 17, 18, 19 & 20	
	Sand flat	
	Soil 1st & 4th rate	
	Dense sagebrush & Greasewood undergrowth on 75.40 Chs.	
	— May 20. 1884	
	North Bet. Secs. 17 & 18	
	Va 18°10'E	40
40.00	Set Charred pine post 3 ft. long 3 ins. square, 12 ins. in the ground for 1/4 Sec. Cor, marked 1/4 S on W. face and made regulation mound & pits	80.
80.00	Set charred redwood post 4 ft. long 4 ins. square, 12 ins. in the ground for Cor. to Secs.	40.

R. 13 W - S. L. M.

Chains 7, 8, 17 & 18, marked
T. 9. N. on N.E.
R. 13 W on S.E.
S. 18 on S.W. and
S 7. on N.W. with 4 notches
on S. & 5 on E. edges. and
Made regulation mound & pits
Land flat
Soil 1st rate
Dense sage brush & shadscale
Undergrowth on 80.00 chs.

East on random line
Bet. Secs. 8 & 17
Va 18° 10' E.

40.00 Set Temporary 1/4 Sec. Cor.
80.44 Intersect N. & S. line 32 Rks. S.
of Cor. to Secs. 8, 9, 16 & 17
Thence Iron
S. 89° 46' W. on true line
Bet. Secs. 8 & 17
Va 18° 10' E.

40.22 Set Limestone 10 x 9 x 6 ins. 7
ins. in the ground for 1/4 Sec.
Cor. marked 1/4 on N. face, and

Subdivisions T. 9 N.

Chains	Made regulation mound & pits
75.80	Wash drains S.E.
80.44	The Cor to Secs. 7, 8, 17 & 18
	Land bench
	Soil 1st rate
	Dense sage brush & shadscale undergrowth on 80.44 chs.
	West on random line
	Bet. Secs. 7 & 18
	Va 18°10' E
40.00	Set temporary 1/4 Sec. Cor.
80.57	Intersect W. By. of Township 20 Rks. S. of Cor. to Secs. 7, 12, 13 & 18 re-established by me during this survey
	Thence I run
	S. 89°51' E. on true line
	Bet. Secs. 7 & 18
	Va 18°10' E.
38.00	Wash drains S.W.
40.57	Set Conglomerate 20 x 13 x 7 ins 15 ins. in the ground for 1/4 Sec. Cor. Marked 1/4 on N. face and

Chain
64.2
80.5
28.5
40.0
80.0

BOOK-A-203

R. 13 W. - S. L. M.

Chains	
	Made regulation mound & pits
64.25	Wash drains S.
80.57	The Cor. to Secs. 7, 8, 17 & 18
	Land bench
	Soil 1st rate
	Dense sage brush & shadscale
	undergrowth on 80.57 chs.
	North Bet. Secs. 7 & 8
	Va 18° 10' E.
28.50	Wash drains S.E.
40.00	Set charred pine post 3 ft. long
	3 ins. square 12 ins. in the
	ground for 1/4 Sec. Cor. marked
	1/4 S. on W. face, and made
	regulation mound & pits
80.00	Set charred redwood post 4 ft.
	long 4 ins. square 12 ins. in
	the ground for Cor. to Secs. 5, 6,
	7 & 8 marked
	T. 9 N. on N.E.
	R. 13 W. on S.E.
	S. 7 on on S.W. and
	S. 6 on N.W. With 5 notches

Subdivisions T. 9 N

Chains		Chains
	on S. & E. edges and made	
	Vegetation mound & pits	
	Land bench	
	Soil 1st rate	
	Dense sage brush & shadscale	79.76
	Undergrowth on 80.00 Chs.	
	East on random line	
	Bet. Secs. 5 & 8	
	Va 18°10' E	
40.00	Set Temporary 1/4 Sec. Cor.	
79.76	Intersect N. & S. line 328 Rs. N. of	
	Cor. to Secs. 4, 5, 8 & 9	
	Thence Iron	40.00
	N. 89°46' W. on true line	80.53
	Bet. Secs. 5 & 8	
	Va 18°10' E.	
6.50	Wash drains S. E.	
15.00	" " "	
23.00	" " "	
27.00	" " "	40.00
33.50	Leave flat	40.53
	Enter bench bears N. W. & S. E.	
39.88	Set Charred redwood post 3 ft.	

R. 13 W. - S. L. M.

Chains long 3 ins. square 12 ins. in the ground for 1/4 Sec. Cor, marked 1/4 S. on N. face and made regulation mound & pits

79.76 The Cor. to Secs. 5, 6, 7 & 8,
Land flat & bench
Soil 1st rate
Dense sage brush & shadscale
leader growth on 79.76 Chs.

West on random line
Bet. Secs. 6 & 7
Va 18° 10' E.

40.00 Set Temporary 1/4 Sec. Cor.
80.53 Intersect W. By. of Township
31 Rks. N. of Cor. to Secs. 1, 6, 7 & 12
N. established by me during this survey
Thence S. now
N. 89° 47' E on true line
Bet. Secs. 6 & 7
Va 18° 10' E

40.00 Wash drains S. W.
40.53 Set Charred redwood post 3 ft. long 3 ins. square 12 ins. in the ground for 1/4 Sec. Cor.

Subdivision T. 9 N.

Chains		Chains
	Marked 1/4 S. on N. face, and made regulation mound & pits	40.00
58.50	Wash drains S. W.	60.00
66.00	" " S. E.	
80.53	The Cor. to Secs. 5, 6, 7 & 8	79.50
	Sand bench	
	Soil 1st rate	
	Dense sage brush & shadscale undergrowth on 80.53 chs.	
	North on random line	
	Bet. Secs. 5 & 6	
	Va 18°10' E.	
40.00	Set Temporary 1/4 Sec. Cor.	
79.50	Intersect N. Bry. of Township 18 8 Ks. W. of Cor. to Secs. 5, 6, 31 & 32 re-established by me during this Survey	
	Thence L run	
	S. 0°8' W. on true line	
	Bet. Secs. 5 & 6	
	Va 18°10' E.	
39.50	Set Limestone 15 x 12 x 4 ins - 10 ins in the ground for 1/4 Sec. Cor. Marked 1/4 on W. face, and made regulation mound & pits	

BOOK-A-203

R. 13 W. S. L. M

Chains	
45.00	Wash drains S.W.
60.00	Bend of previous Wash heads N.W. drains S.W.
79.50	The Cor. to Secs. 5, 6, 7 & 8

Land bench
Soil 1st rate
Dense sage brush & shadscale
Undergrowth on 79.50 chs.
May 21. 1884

General Description

The land embraced in this township is flat & bench and Alkali flat in the S.W. Corner. It is covered with a fine growth of shadscale, white sage & California Clover, affording fine Winter range for stock - it is now extensively used as such for sheep.
It is believed that artesian

216 Subdivisions
T. 9 N. R. 13 W. - S. L. M.

Wells judiciously sunk would furnish water for agricultural purposes. The soil being first rate and its nearness to the Central Pacific railroad, in that county, would render it desirable for settlement.

Henry Fitzhugh
U.S. Deputy Surveyor.

BOOK-A-203

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah October 11 1884

The foregoing field notes of the survey of the Subdivisions

Township No. 9 North *Range No.* 13 West

Executed by Henry Fitzhugh

Under No 124 *contract of the* 19th

day of March 1884, *in the month of*

May 1884, *having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

Fred Salomon

U. S. Surveyor General for Utah.

Blank

Page

BOOK-A-203

1885

2

219

REPORT: 1885

Filed 188

Examined by John H. Campe.

Transcribed by Henry R. M. Atkinson

Compared by O.E.S. H.R.M.A.

FIELD NOTES

OF THE SURVEY OF THE

East Boundary of

OF

Township No 9 North

Range No 16 West

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Henry Fitzhugh

U. S. Deputy Surveyor,

Under his Contract No. 124

Dated March 19th 1884

Survey commenced June 25th 1884

Survey completed " " 1884

NAMES AND DUTIES OF ASSISTANTS:

.....*Compassman.*

.....*Chainman.*

.....*Chainman.*

.....*Chainman.*

.....*Chainman.*

.....*Axeman.*

.....*Axeman.*

.....*Flagman.*

Re-Survey -221

E. By. Ltr. 9 N. R. 16 W. - S. L. M.

Obs. Note

Before subdividing T. 9 N. R. 16 W. I find it necessary to re-survey the East By. as some of the corners are doubtless lost or destroyed having been set for so long a time.

On the night of June 24th 1884 I took an observation of the Star Polaris and established a meridian in accordance with instructions contained in the manual of surveys.

Survey commenced with a Gurley transit June 25th 1884

Before commencing this survey I test my instrument in the meridian previously established & find it to be correct.

From the Cor. to T 9 N Rs. 15 & 16 W. on the 2nd Standard

Re-survey E By. 7. 9 W.

Chs.	Parallel North which is a Pine Post 3½ ft. above ground 4×6 ins. ~~square~~, properly marked, and pits & mound alongside. I run North on reservey line Bet. Secs 31 & 36 Vn 18°10' E.	Chs. 8.50
40.00	Find old Cor. a pine post standing 2 feet above ground properly, marked for ¼ Sec. Cor. I renew old mound from regulation pits.	40.00
75.10	Telegraph line bears N.E. & S.W.	
76.20	Central Pacific rail road track bears, N.E. & S.W.	80.00
76.80	Telegraph line bears N.E. & S.W.	
77.50	Road bears N.E. & S.W.	
80.00	Find old Cor. a pine post 3 ft. above ground standing, properly marked for Cor. to Secs. 25. 30, 31 & 36. I renew old mound from regulation pits. Land flat Soil 1st rate	

R 16 W - S. L. M

Chs. Dense sage brush & shads cale undergrowth on 80.00 Chs.

North on re-survey line
Bet. Secs. 25 & 30
Dia 18° 10' E.

8.50 Wash drains S.E.
40.00 Find old cor. a pine post. standing in old mound for 1/4 Sec. Cor. the marks being nearly effaced I renew same & also old mound from regulation pits
80.00 Find old cor. (a pine post.) thrown down, but sufficient of old mound remaining to fully identify the true position of old Cor. I re-set old post in old mound, it being properly marked for re-established Cor to Secs. 19. 24, 25 & 30. I renew old mound from regulation pits
Sand flat
Soil 1st rate

Re-Survey E Bx, 7. 9 W.

Chs.		Chs.
	Dense Sage brush & shadscale undergrowth on 80.00 chs	
	North on re-survey line Bet. Secs 19 & 24 Va 18° 10' E.	
40.00	Find old Cor. thrown down (which is a pine post,) but sufficient of old mound remaining to fully identify the true position of old Cor. Reset old post in old mound, it being properly marked for re-established 1/4 Sec. Cor. I renew old mound from regulation pits	8.00 12.00 40.00
71.40	Old road bears N.E. & S.W.	65.00
80.00	Find old Cor. standing, which is a pine post 2½ ft. above ground, properly marked for Cor. to Secs 13, 18, 19 & 24. I renew old mound from regulation pits	80.00
	Sand flat.	

R. 16 W. S. L. M.

Chs.	Soil 1st rate Dense sage brush & shadscale undergrowth on 80.00 chs.
	North on re-survey line Bet. Secs. 13 & 18 Va 18° 10' E.
8.00	Wash drains S. E.
12.00	Road bears N. E. & S. W.
40.00	Find old Cor. (a pine post) Standing 2 ft. above ground, in old mound, properly marked for 1/4 Sec. Cor. I re-new old mound from regulation pits
65.00	Leave bottom. Ascend falling brush bears. E. & W.
80.00	Find old Cor. A pine post. 2 1/2 ft. above ground, standing in old mound, properly marked, for Cor. to Secs. 7. 12 13 & 18. I renew old mound from regulation pits.

Re-survey E By. T. 9 N.

Chs.		Chs.
	Land flat & brush Soil 1st rate Dense sage brush & shad scale underground on 80.00 Chs.	
	North on re-survey line Bet. Secs. 7 & 12 Va 18° 10' E.	30.00
30.30	Road from Terrace to Grouse Creek bears E & W.	40.00
40.00	Find old Cor. (a pine post) standing 2 ft. above ground, properly marked for 1/4 Sec. Cor. I re-new old mound from regulation pits.	
59.50	Gully drains S.E.	
79.00	" " "	
80.00	Find old Cor. (a pine post) standing 2 ft. above ground in old mound properly marked for Cor. to Secs. 1, 6, 7 & 12 I renew old mound from regulation pits.	57.00
	Land rolling	80.00

R. 16 W. S. L. M.

Chs. Soil 1st & 3rd rate
Dense sage brush & shadscale
undergrowth on 8000 Chs.

North on reservoy line
Bet. Secs. 1 & 6
Va 18° 10' E.

3000 Wash drains E.
4000 Find old Cor. (a pine post
thrown down, but enough of
old mound remaining to fully
identify the true position of
old Cor. I re-set old post
in old mound, it being properly
marked for 1/4 Sec. Cor. & rerun
old mound from regulation
pits
5700 Leave rolling ground. &
Enter Valley bears N.W. & S.E.
8000 Find old Cor. standing, a
pine post 4 ins. square in
mound of earth & properly
marked for Cor. to S. 9 & 10
N. Rs. 15 & 16 W. The same

Re-Survey 228

E. By T. 9 N. - R. 16 W. - S. L. M.

Chs. having been re-established by me under Contract No. 116.

Land high rolling & flat

Soil 2nd & 1st rate

Dense sage brush & shadscale undergrowth on 8000 Chs.

June 25, 188

General Description.

For general Description see end of subdivision lines of Tps. 9 N. R.S. 15 & 16 W.

Henry Fitzhugh

U.S. Deputy Surveyor

BOOK-A-203

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, October 11th 1884

The foregoing field notes of the re *survey of the* East Boundary of

Township No. 9 North *Range No.* 16 West

Executed by Henry Lifthugh

Under Lis No. 124 *contract of the* 19th

day of March 1884, *in the month of*

June 1884, *having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

Fred Salomon

U. S. Surveyor General for Utah.

Blank

Page

BOOK-A-203

231

1885

REPORT: 1885

Filed 188

Examined by John H. Dampe

Transcribed by Henry R. McAtkinson

Compared by O.E.S. & H.R.M.A.

FIELD NOTES

OF THE SURVEY OF THE

Fractional Subdivision Lines

OF

Township No 9 North

Range No 16 West

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Henry Fitzhugh

U. S. Deputy Surveyor,

Under his Contract No. 124

Dated March 19th 1884

Survey commenced June 26th 1884

Survey completed " 28th 1884

BOOK-A-203

Township 9 N R. 16 W.

6	5	4	260	3	253	2	2142	1
				258		252		241
7	8	9	257	10	251	11	240	12
				255		250		239
18	17	16		15	2149	14	238	13
						248		237
19	20	21		22	247	23	237	24
						246		236
30	29	28		27	2146	26	235	25
						245		234
31	32	33		34	2441	35	233	36

Subs. T. 9 N. R. 16 W. - S. L. M.

Chd.	Survey commenced June 26th 1884 with a gurley transit -
	From the Cor. to Secs. 35 & 36 on the 2nd Standard Parallel North which is a Limestone 12x8x5 ins, firmly set in the ground, marked S.C. with 1 notch on E. and 5 notches on W. edges and pits & mound alongside & run -
	North Bet. Secs. 35 & 36 Va 18° 10' E.
34.80	Telegraph line bears N.E. & S.W.
35.70	Central Pacific Rail road track bears N.E. & S.W.
36.30	Telegraph line bears N.E. & S.W.
36.75	Road bears N.E. & S.W.
40.00	Set Limestone 12x10x6 ins - 8 ins in the ground for 1/4 Sec. Cor. marked 1/4 on W. face and made regulation mound & pits
80.00	Set Granite 17x8x5 ins - 11 ins -

Subdivisions T. 9. N.

Chs.	
	in the ground for Cor. to Sec. 25, 26, 35 & 36, marked 1 notch on S. & E. edges, and made regulation mound & pits.
	Land flat
	Soil 1st rate
	Dense sage brush & shadscale undergrowth on 80.00 Chs.
	East on random line
	Bet. Secs. 25 & 36
	Va 18° 10' E.
40.00	Set Temporary 1/4 Sec. Cor.
80.20	Intersect E. By. of Township 26 Ks. N. of Cor. to Secs. 25, 30, 31 & 36 reestablished by me during this survey.
	Thence I am
	N. 89° 49' W. on true line
	Bet. Secs. 25 & 36
	Va 18° 10' E.
40.10	Set Granite 18 x 12 x 4 ins. - 1 2 ins. the ground for 1/4 Sec.

R. 10 W. — S. L. M.

Cor. marked 1/4 on N. face and made regulation mound & pits

80.20 The Cor. to Secs. 25, 26, 35 & 36.
Land flat
Soil 1st rate
Dense sage brush & shadscale
undergrowth on 80.20 chs.

North Bet. Secs. 25 & 26
Va 18° 10' E.

30.00 Road crossing N.S. & S.W.

40.00 Set Volcanic stone 18x10x6 ins.
12 ins. in the ground for 1/4 Sec.
Cor. marked 1/4 on W. face and
made regulation mound & pits

62.50 Wash crossing S.E.

80.00 Set Sandstone 16x12x8 ins - 10
ins. in the ground for Cor. to
Secs. 23, 24, 25 & 26, marked 2
notches on S. & 1 notch on E.
edges and made regulation
mound & pits
Land flat
Soil 1st rate.

Subdivisions L. J. N.

Chs.		Chs.
	Dense sage brush & shadscale under growth on 80.00 chs.	
	East on random line Bet. Secs. 24 & 25 Va 18° 10' E.	40.00
40.00	Set Temporary 1/4 Sec. Cor.	
80.31	Intersect E. By. of Township 10 Mls. S. of Cor. to Secs. 19. 24. 25 & 30, reestablished by me during this Survey.	80.00
	Thence L'mm S. 89° 56' W. on true line Bet. Secs. 24 & 25 With same Va	
40.15	Set Limestone 20×16×10 ins - 15 ins - in the ground for 1/4 Sec. Cor. marked 1/4 on N. face, and made regulation mound & pits	
43.00	Road bears N.E. & S.W.	
80.31	The Cor. to Secs. 23, 24, 25 & 26 Land flat Soil 1st rate	40.00
	Dense sage brush & shadscale	79.5[illegible]

R. 16 W. - S. L. M.

Chs.	undergrowth on 80.31 chs.
	North Bet. Secs. 23 & 24 Va 18° 10' E.
1000	Set Volcanic Stone 15 x 12 x 6 ins - 10 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on W. face, and made regulation mound & pits.
8000	Set Limestone 20 x 15 x 13 ins - 15 ins. in the ground for Cor. to Secs. 13, 14, 23 & 24, marked 3 notches on S. & 1 notch on E. edges, and made regulation mound & pits
	Land flat
	Soil 1st rate
	Dense Sage brush undergrowth on 8000 chs
	East on random line Bet. Secs. 13 & 24 Va 18° 10' E.
4000	Set Temporary 1/4 Sec. Cor.
79.58	Intersect E. Bdy. of Township

Subdivisions T 9 N

Chs.		Chs.
	37 8 Ks. S. of Cor. to Secs. 13. 18. 19 & 24, re-established by me during this survey	60.00
	Thence Sum	80.00
	S. 89° 44' W. on true line	
	Bet. Secs. 13 & 24	
	With same Va	
26.50	Gulch drains S. E.	
39.79	Set Granite 19 x 12 x 6 ins - 12 ins in the ground for 1/4 Sec. Cor. marked 1/4 on N. face, and made regulation mound & pits.	
79.58	The Cor. to Secs. 13. 14. 23 & 24	
	Pond rolling brush	
	Soil 1st rate	
	Dense sage brush undergrowth on 79.58 Chs.	
		40.00
		79.80
	North Bet. Secs. 13 & 14	
	Va 18° 10' E.	
5.90	Road bears E & W.	
40.00	Set Granite 14 x 10 x 4 ins - 10 ins in the ground for 1/4 Sec. Cor. marked 1/4 on N. face, and	

R. 16 W. - S. L. M.

Chs.	
	Made regulation mound & pits.
60.00	It ash in hollow drains S.E.
80.00	Set Granite 18 x 12 x 9 ins - 12 ins. in the ground for Cor. to Secs. 11, 12, 13 & 14, marked 4 notches on S. & 1 notch on E. edges and made regulation mound & pits -
	Land rolling
	Soil 1st rate
	Dense sage brush undergrowth on 80.00 chs
	East on random line
	Bet. Secs. 12 & 13
	Va 18° 10' E.
40.00	Set Temporary 1/4 Sec. Cor.
79.80	Intersect E. By. of Township 29 Ms. N. of Cor. to Secs. 7, 12, 13 & 18 re-established by me during this survey
	Thence I run
	N. 89° 48' W. on true line
	Bet. Secs. 12 & 13

Subdivision T. 9 N.

Chs.	With same Va	Chs.
39.90	Set Granite 24×6×6 ins - 16 in in the ground for 1/4 Sec. Cor. marked 1/4 on N. face, and made regulation mound & pits	43.50
78.80	Wash drains S.E.	57.00
79.80	The Cor. to Secs. 11, 12, 13 & 14 Land rolling Soil 1st rate Dense sage brush undergrowth on 79.80 Chs	80.00
	North Bet. Secs. 11 & 12 Va 18° 10' E.	
5.00	Wash drains S.E.	
17.00	Previous Wash drains S.W.	
31.00	Road from Grouse Creek to Terrace bears N.W. & S.E.	
34.00	Bend of previous Wash heads N.E. drains S.E.	40.00
40.00	Set Granite 13×12×8 ins - 8 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on W. face, and made regulation mound & pits.	80.13

R. 16 W. S. L. M.

Chs.	
43.50	Previous Wash drains S.E. heads N.
57.00	" " heads N.W.
	Enter mountains bear N.W. & S.E.
	Leave dense sage brush
80.00	Set Granite 20×12×10 ins – 15 ins. in the ground for Cor. to Secs. 1, 2, 11 & 12, marked 5 notches on S. & 1 notch on E. edges, and made regulation mound & pits
	Land rolling & Mountainous
	Soil 1st & 3rd rate
	Dense sage brush undergrowth on 57.00 chs.
	High Mountainous on 23.00 chs.
	Augmented on 80.00 "
	June 26 1894
	East on random line
	Bet. Secs. 1 & 12
	Va 18° 10' E.
40.00	Set Temporary 1/4 Sec. Cor.
80.13	Intersect E. Bry. of Township 16 Rs. N. of Cor. to Secs. 1, 6, 7 & 12 re-established by me during this Survey –

Subdivisions T. 9 N.

Chs.	
	Thence Iron
	N. 89° 53' W. on true line
	Bet. Secs. 1 & 12
	With same Va
2.00	Gulch drains S.E.
30.00	" " N.E.
40.07	Set Granite 20 x 12 x 10 ins - 15 ins. in the ground for 1/4 Sec. Cor. Marked 1/4 on N. face, and made regulation mound & pits.
49.00	Gulch drains N.E.
64.00	Hollow drains S.E.
78.50	Ridge bears N.O.S.
80.13	The Cor. to Secs. 1, 2, 11 & 12
	Sand Mountainous
	Soil 3rd rate.
	High Mountains on 80.13 Chs.
	North on random line
	Bet. Secs. 1 & 2
	Va 18° 10' E.
40.00	Set Temporary 1/4 Sec. Cor.
79.88	Intersect N. Bry. of Township
	30 Lks. W. of Cor. to Secs. 1, 2, 35

R. 16 W — S. L. M.

Chs. + 36. Which is Granite 5 x 9 x 5 ins above ground properly marked and mound & pits alongside
Thence I run
S. 0° - 13' W. on true line
Bet. Secs. 1 & 2
With same Co.
39.88 Set Granite 12 x 9 x 7 ins - 8 ins in the ground for 1/4 Sec. Cor. marked 1/4 on W. face, and made regulation mound & pits.
67.00 Ridge bears E. & W.
79.88 The Cor. to Secs. 1, 2, 11 & 12
Sand mountainous
Soil 4th rate
High Mountains on 79.88 Chs.

Subdivisions L. G. N.

Chs.		Chs.
	From the Cor. to Secs. ~~2, 3~~ 34 & 35 on the 2nd Standard Parallel North which is a Quartz Stone 4×9×8 ins above ground properly marked & mound & pits alongside & run	40.00
	North Bet. Secs. 34 & 35 Va 18° 10' E.	80.15
40.00	Set Limestone 16×12×6 ins – 10 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on W. face, and made regulation mound & pits	22.90
71.00	Leave flat & sage brush	40.07
	Enter Mountains bear N.E. & S.W.	
80.00	Set Limestone 20×15×12 ins – 15 ins. in the ground for Cor. to Secs. 26, 27, 34 & 35, marked 1 notch on S & 2 notches on E. edges, and made regulation mound & pits.	62.50
	Land Flat & Mountains	80.15
	Soil 1st & 3rd rate.	
	Dense sage brush undergrowth on 71.00 chs.	
	High Mountains on 9.00 chs.	
	Augmented on 80.00 chs –	

R. 16 W. S. L. M.

Chs.	East on random line
	Bet. Secs. 26 & 35
	Va 18° 10' E.
40.00	Set Temporary 1/4 Sec. Cor.
80.15	Intersect N. & S. line 10 Hks. S. of
	Cor. to Secs. 25, 26, 35 & 36
	Thence I run
	S. 89° 56' W. on true line
	Bet. Secs. 26 & 35
	With same Va
22.90	Road bears N.W. & S.E.
40.07	Set Granite 20×12×9 ins - 15 ins.
	in the ground for 1/4 Sec. Cor.
	Marked 1/4 on N. face, and made
	regulation Mound & pits
62.50	Enter Mountains bear N. & S.
	Leave flat & sage brush
80.15	The Cor. to Secs. 26, 27, 34 & 35
	Land flat & Mountains
	Soil 1st & 3rd rate
	Dense sage brush & thadscale
	undergrowth on 62.50 Chs.
	High Mountains on 17.65 Chs.
	Augm. ended on 80.15 Chs

Subdivisions T. 9 N.

Chs.	North Bet. Secs. 26 & 27 Va 18° 10' E.
40.00	Set Limestone 18 x 12 x 9 ins - 12 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on W. face, and made regulation mound & pits.
48.50	Ridge bears N.E. & S.W.
61.00	Hollow drains N.E.
80.00	Set Limestone 15 x 13 x 8 ins - 10 ins. in the ground for Cor. to Secs. 22, 23, 26 & 27 marked 2 notches on S & E. edges, and made regulation mound & pits
	Land mountains
	Soil 3d & 4th rate
	High mountains on 80.00 chs.
	East on random line
	Bet. Secs. 23 & 26 Va 18° 10' E.
40.00	Set Temporary 1/4 Sec. Cor.
79.84	Intersect N. & S. line 22 Rks. N. of Cor. to Secs 23, 24, 25 & 26
	Thence I run

R. 16 W. - S. L. M.

Chs.	
	N. 89° 51' W. on true line
	Bet. Secs. 23 & 26
	With same Va
39.92	Set Limestone 12x10x7 ins - 8 ins in the ground for 1/4 Sec. Cor. marked 1/4 on N. face and made regulation mound & pits.
52.50	Leave flat & sage brush
	Enter Mountains bear N.E. & S.W.
79.84	The Cor. to Secs. 22, 23, 26 & 27
	Land flat & Mountains
	Soil 1st & 4th rate
	Dense sage brush undergrowth on 52.50 Chs.
	High Mountains on 27, 34 Chs.
	Augmented on 79.84 Chs
	North Bet. Secs. 22 & 23
	Va 18° 10' E.
36.75	Gulch drains N.E.
39.00	" " "
40.00	Set Limestone 18x12x6 ins - 12 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on W. face, and

Subdivisions T. 9 N.

Chs.		Chs.
60.00	Made regulation Mound & pits Gulch drains N.E.	58.00
80.00	Set Limestone 15×12×7 ins - 10 ins. in the ground for Cor. to Secs. 14, 15, 22 & 23, marked 3 notches on S. & 2 on E. edges and made regulation Mound & pits	80.00
	Land mountainous	
	Soil 4th rate	
	High mountains on 80.00 Chs.	
	East on random line Bet. Secs. 14 & 23 Va 18° 10' E.	
40.00	Set Temporary 1/4 Sec. Cor.	8.50
80.00	Intersect N.D.S. line at Cor to Secs. 13, 14, 23 & 24	70.00
	Thence I run	
	West on true line Bet. Secs 14 & 23 With same Va	
23.75	Hollow drains S.	
40.00	Set Limestone 16×13×6 ins - 10 ins in the ground for 1/4 Sec. Cor. marked 1/4 on N. face, and made	

R. 16 W. S. L. M.

Chs.	Regulation Mound & pits
58.00	Hollow drains S.E.
	Leave bench & sage brush
	Enter Mountains bear N.E.
80.00	The Cor. to Secs 14, 15, 22 & 23
	Land bench & Mountains
	Soil 1st & 4th rate.
	Dense sage brush undergrowth
	on 58.00 chs.
	High mountains on 22.00 chs.
	Augmented on 80.00 chs.
	North Bet. Secs. 14 & 15
	Va 18° 10' E.
8.50	Road bears E. & W.
20.00	At foot of inaccessible
	Granite bluff
	Set Granite 18 x 17 x 8 ins - 12 ins
	in the ground for witness 1/4
	Sec. Cor. marked 1/4 W.C. on
	W. face, and raised mound
	of stone alongside
	Thence I offset E. 15.00 chs.
	Thence N. 60.00 chs.

Subdivisions T. 9 N.

Chs.	Thence W. 15. chs on true line	39.97
	Where I set Granite 16×13×7	
	ins - 10 ins in the ground for	
	Cor. to Secs. 10, 11, 14 & 15 marked	
	4 notches on S. & 2 on E. edges	45.00
	and made regulation mound	79.94
	and pits	
	Land mountainous	
	Soil 4th rate - rocky	
	Few scattering cedars.	
	High mountains on 80.00 Chs.	
	East on random line	
	Bet. Secs. 11 & 14	5.0
	Va 18° 10' E.	16.0
40.00	Set Temporary 1/4 Sec. Cor.	40.0
79.94	Intersect N. & S. line 5 Ks. S. of	
	Cor. to Secs. 11, 12, 13 & 14	
	Thence I run	
	S. 89° 58' W. on true line	
	Bet. Secs. 11 & 14	47.
	With same Va	
8.50	Wash in hollow drains S.E.	57.
23.00	Granite ridge bears N.W. & S.E.	71.

R. 16 W. — S. L. M.

Chs.	
39.97	Set Granite 14×10×9 ins. - 10 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on N. face, and made regulation mound & pits
45.00	Road bears N.W. & S.E.
79.94	The Cor. to Secs. 10. 11. 14 & 15 Land rolling Soil 1st & 4th rate Dense sage brush undergrowth on 79.94 chs — June 27. 1884
	North Bet. Secs. 10 & 11 Va 18° 10' E.
5.00	Road bears N.E. & S.W.
16.00	Gulch drains E.
40.00	On top of Granite ridge bears N.W. & S.E. Set Granite 24×8×10 ins. - 18 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on W. face, and made regulation mound & pits.
47.00	Enter hollow drains S.E. × sage brush
57.00	Wash drains S.E.
71.20	Road from Terrace to Grouse

Subdivisions [illegible]

Chs.	
	Creek bears N.W. & S.E.
71.75	Wash drains S.E.
80.00	Set Limestone 16×14×10 ins - 10 ins. in the ground for Cor. to Secs. 2, 3, 10 & 11, marked 5 notches on S. & 2 on E. edges and made regulation mound & pits
	Land Mountains & Hollow
	Soil 4th & 1st rate
	Dense sage brush undergrowth on 33.00 Chs.
	High Mountains on 47.00 Chs.
	Hay mounted on 80.00 Chs
	East on random line Bet. Secs. 2 & 11 Va 18° 10' E.
40.00	Set Temporary 1/4 Sec. Cor.
79.88	Intersect N. & S. line 32 Rks. S. of Cor. to Secs 1, 2, 11 & 12
	Thence I run
	S. 89° 46' W. on true line Bet. Secs. 2 & 11
	With same Va

Chs.	
2.50	W
17.50	R
28.00	Ent
39.94	S
	E
	Gra
	gr
	re
	H
	Sk
45.00	W
50.00	R
55.00	H
63.00	R
78.50	S
	E
79.88	W
	D
	o
	H
	N
	I

R. 16 W. S. L. M.

Chs.	
2.50	Wash in hollow drains S.
17.50	Ridge bears N. E. & S. W.
28.00	Enter hollow drains S. & sage brush
39.94	Leave hollow & sage brush.
	Enter Mountains bear N. & S. Set Granite 16 x 14 x 13 ins - 10 ins in the ground for 1/4 Sec. Cor. Marked 1/4 on N. face, and made regulation mound & pits - from which Cedar 17 ins. diam. bears N. 13° W. 28 Lks. dist. marked 1/4 S. B. S.
45.00	Wash drains S. E.
50.00	Ridge bears N. & S.
55.00	Hollow drains S.
63.00	Ridge bears N. & S.
78.50	Leave mountains bear N. & S. Enter hollow & sage brush
79.88	The Cor. to Secs. 2, 3, 10 & 11

Land mountains & hollow.
Soil 4th & 1st rate -
Dense sage brush undergrowth on 13.32 chs.
High Mountains on 66.56 chs.
Augmented on 79.88 chs

North on random line
Bet. Secs. 2 & 3
Dn 18° 10' E.

Subdivisions T. 9 N.

Chs.	
40.00	Set Temporary 1/4 Sec. Cor.
79.70	Intersect N. By. of Township 35
	Lks. W. of cor. to Secs. 2, 3, 34 & 35
	which is a limestone 5×10×8 ins
	above ground properly marked &
	mound & pits alongside
	Thence I run
	S. 0° 15' W. on true line Bet. Secs. 2 & 3
	With same Va
16.00	Enter mountains - Leave bench
	bears N.E. & S.W. and sage brush
39.70	Set Granite 32×8×4 ins - 24 ins
	in the ground for 1/4 Sec. Cor. marked
	1/4 on W. face, and made regula-
	tion mound & pits
76.00	Leave mountains
	Enter hollow bears N.W. & S.E.
	and sage brush
79.70	The Cor. to Secs 2, 3, 10 & 11
	Land mountains & bench
	Soil 1st & 4th rate
	Dense sage brush undergrowth
	on 19.70 chs

R. 16 W. L. M.

Chs. High mountains on 60.00 chs.
Augmented on 79.70 chs.

Note.
The line South of Sec
10 is falling in high broken
mountains I find it impract-
icable to run
I therefore from Cor to Secs 10, 11, 14 & 15
run West on this line bet. Secs. 10 & 15
Va 18° 10' E.

9.25 – Road bears N.E. & S.W.
18.80 – Spring branch in gulch
drains N.E. Entry Cedar & pine
23.50 Granite bowlder
26.00 Old Cabin on line
37.50 Ash drains N.E.
44.00 Set granite 16×12×7 ins – 10 ins
in the ground for 1/4 Sec. Cor.
marked 1/4 on N. face, and
made regulation Mound & Pits.
From which
Pine Tree 8 ins. dia. bears

Subdivisions T. 9 N

Chs.	N. 35 lks. dist
	A Cedar Tree 4 ins. diam. bears
	S. 23° W. 52 lks. dist.
	Both marked 1/4 S. B.T.
63.00	Gulch drains N.E.
76.00	" " "
80.00	Set Limestone 16×14×9 ins - 10 ins
	in the ground for Cor. to Secs.
	9, 10, 15 & 16, marked 4 notches
	on S & 3 on E. edges, and
	raised a mound of stone
	alongside
	From which
	A Cedar Tree 6 ins. diam. bears
	S. 45° W. 35 lks. dist. marked
	S. 16. T. 9. N. R. 16 W. B.T.
	A Cedar Tree 4 ins. diam. bears
	S. ~~21~~° E. 24 lks. dist. marked
	S. 15. B.T.
	A Cedar Tree 7 ins. diam. bears
	N. 61° E. 43 lks. dist. marked
	S. 10 B.T.
	Land Mountains
	Soil 3d rate
	Cedar & pine Timber on 61.20 Chs.

BOOK-A-203

R. 16 W. S. L. M.

Chs. High mountains on 8.00 Chs

North Bet. Secs. 9 & 10
Dec. 18° 10' E.

13.00 Ridge trees E. & W.
30.50 Creek drains E.
40.00 Set Sandstone 18x10x7 ins. 12 ins. in the ground for 1/4 Sec. Cor. Marked 1/4 in W. face, and raised a mound of stone alongside.
From which
A Cedar 5 ins. diam. bears N. 30° W. 26 lks. dist. Marked 1/4 S. B.
44.75 Creek drains N.E.
45.15 " " S.E.
80.00 Set Sandstone 20x12x7 ins. 15 ins. in the ground for Cor. to Secs. 3, 4, 9 & 10, marked 5 notches on S. & 3 on E. edges and raised a mound of stone alongside.
From which
A cedar 6 ins. diam. bears N. 70° W.

Subdivisions T. 9 N.

Chs.	36 Ms. dist marked S. 4 B.T.	Ch
	A Cedar Gins. diam. bears S. 14°	21.0
	W. 56 Ms. dist marked S. 9.	31.0
	T. 9 N. R. 16 W. B.T.	40.1
	Sand Mountains	
	Soil 2nd & 4th rate	
	Cedar & Pine Timber	
	High Mountains on 80.00 Chs.	
	East on random line	
	Bet. Secs. 3 & 10	62.
	Va 18° 10' E.	80.2
40.00	Set Temporary 1/4 Sec. Cor.	
80.00	Intersect N. & S. line 29 Ms. N.	
	of Cor. to Secs. 2, 3, 10 & 11	
	Thence Dam	
	N. 89° 48' W. on true line	
	Bet. Secs. 3 & 10	
	With same Va	
2.00	Wash drains S.E.	
5.00	Road from Terrace to Grouse	
	Creek bears N.W. & S.E.	
	Sewer hollow & sage brush	
	Enter Mountains bear N.W. & S.E.	
	& Cedar Timber	

BOOK-A-203

R. 11 W. — S. L. M.

Chs.	
24.00	Granite ridge bears N.W. & S.E.
31.00	Brush in hollow drains N.E.
40.10	Set Sandstone 20x18x6 ins. 15 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on N face, and made regulation Mound & pits.
	From which
	Cedar 5 ins. diam. bears S. 47° W. 2 lks. dist.
	Cedar 15 ins. diam. bears N. 7° 30' W. 20 lks. dist. both marked 1/4 S. B. T.
62.25	Spring drains N.E.
80.20	The Cor. to Secs. 3, 4, 9 & 10
	Land Mountainous
	Soil 3d x 4th rates
	Cedar timber on 75.20 Chs.
	Dense sage brush Undergrowth on 5.00 Chs.
	High mountains on 75.20 Chs
	Hogbacked on 80.20 Chs

Subdivisions T. 9 N.

Chs.	
	North on random line Bet. Secs. 3 & 4
	Va 18° 10' E.
40.00	Set Temporary 1/4 Sec. Cor.
79.30	Intersect N. By. of Township 46 Mts. W. of Cor. to Secs. 3, 4, 33 & 34 Which is a quartzite 5x10x6 in above ground, properly marked & mound & pits alongside Thence I run
	S 0° 20' W. on true line Bet. Secs. 3 & 4
	Va 18° 10' E.
25.00	Sloor bench bears N.W. & S.E. Enter hollow drains S.E.
39.30	Set Limestone 22x18x12 ins 15 ins in the ground for 1/4 Sec. Cor. marked 1/4 on W. face, and made regulation mound & pits.
48.50	Wash in hollow drains S.E.
50.50	Road from Terrace to Grouse Creek bears N.W. & S.E. Sloor hollow & sage brush Enter Mountains bears N.W. & S.E.
76.50	Junction of gulches head S.W. drain N.E.

BOO

Chs. 79.30

R. H. W. — S. L. M.

Chs. 79.30 The Cor. to Secs. 3, 4, 9 & 10
Land bench & mountains
Sice 1st & 4th rates
Dense sage brush undergrowth
on 50.50 Chs.
High Mountains on 28.80 Chs.
Augmented on 79.30 Chs.
June 28. 1884

General Description

The land embraced in this fractional township is flat & mountainous
There is a spring in Sec. 15 -
The Central Pacific railroad runs through Secs. 35 & 36
By boring artesian wells a sufficient supply of water might be obtained for agricultural purposes in the southern portion
The township affords

Good Minister Range for Stock -

Henry Fitzhugh
U.S. Dep. Surveyor

BOO

We
Henry
surveyo
of the S
R14W, T
T9N, R13
R13W &
of the S
tory of
field no
under
been in
and bel
corner
instruc
surveyo

U
Ste

S

Subscri
day of

We hereby certify that we assisted Henry Fitzhugh United States deputy surveyor, in surveying re-surveying all those parts or portions of the Subdivisional lines of Tps 9, 10 & 11 N, R 13 W, T 11 N R 14 W, Tps 10 & 11 N R 16 W & Fract T 9 N, R 16 W & E & W Bdy, T 9 N, R 13 W, S & W Bdys T 10 N, R 13 W, N Bdy T 11 N R 13 W & E Bdy, Tp 9 N, R 16 W

of the Salt Lake base and meridian in the Territory of Utah, as are represented in the foregoing field notes as having been surveyed by him, and under his direction; and that said survey has been in all respects, to the best of our knowledge and belief, well and faithfully surveyed, and the corner monuments established according to the instructions furnished by the United States surveyor-general for Utah.

Ernst Salomon, Compassman.

Walter L. Whately, Chainman.

Stewart M. Caucate, Chainman.

....., Chainman.

....., Chainman.

David R. Sinclair, Axeman.

Samuel J. his x mark Cook, Axeman.

Stewart M. Cauca, Flagman.

Witness

Subscribed and sworn to before me this 30th day of June 1884

Henry Fitzhugh
U.S. Dep. Surveyor

Blank

Page

[6.—FINAL OATH OF UNITED STATES DEPUTY SURVEYOR.]

I, Harry Fitzhugh United States deputy surveyor, do solemnly swear that in pursuance of instructions received from Ed. Salomon United States surveyor-general for Utah, bearing date of the 19th day of March, 1884 I have well, faithfully, and truly, in my own proper person, and in strict conformity with the instructions furnished by the United States surveyor-general for Utah, the surveying manual and the laws of the United States, surveyed & re-surveyed all those parts or portions of the Subdivision lines of Tps. 9 10 & 11 N. R. 13 W. - T. 11 N. R. 14 W. - Tps. 10 & 11 N. R. 16 W. & Back T. 9 N. R. 16 W. and E. & W. Bdys. T. 9 N. R. R. 13 W. N. By. T. 11 N. R. 13 W. & E. By. Tp. 9 N. R. 16 W.

of Salt Lake base and meridian in the Territory of Utah, as are represented in the foregoing field notes as having been surveyed by me and under my directions; and I do further solemnly swear that all the corners of said survey have been established and perpetuated in strict accordance with the surveying manual, printed instructions, the special written instructions of the United States surveyor-general for Utah, and in the specific man-

ner described in the field notes, and that the foregoing are the TRUE *field notes of such survey; and, should any fraud be detected, I will suffer the penalty of perjury, under the provisions of an act of Congress, approved August 8, 1846.*

Harry Fitzhugh

United States Deputy Surveyor.

Subscribed and sworn to before me this 30th *day of* August *1884.*

Edward Michaelis

Notary Public

BOOK-A-203

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, October 11th 1884

The foregoing field notes of the survey of the Fractional Subdivisions

Township No. 9 North *Range No.* 16 West

Executed by Henry Fitzhugh

Under Ins No. 124 *contract of the* 19th

day of March 1884, *in the month of* June 1884, *having been critically examined, the necessary corrections and explanations made; the said field notes, and the surveys they describe are hereby approved.*

Fred Salomon

U. S. Surveyor General for Utah.

Blank

Page

BOOK-A-203

1885

269

REPORT: 1885

Filed 188

Examined by John H. Dampe

Transcribed by J. Michaelis

Compared by O.E.J. + E.M.

FIELD NOTES

OF THE SURVEY OF THE

East, South & West Boundaries

OF

Township No 10 North

Range No 13 West

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Henry Fitzhugh

U. S. Deputy Surveyor,

Under his Contract No. 124

Dated March 19 1884

Survey commenced May 3 1884

Survey completed May 5 1884

NAMES AND DUTIES OF ASSISTANTS:

..... *Compassman.*

..... *Chainman.*

..... *Chainman.*

..... *Chainman.*

..... *Chainman.*

..... *Axeman.*

..... *Axeman.*

..... *Flagman.*

I,
do sol
form
instru
and a
line
R. 14
Tp. 9
N. R
13 M
Tp. 9

of the
tory of

Subscr
d

[1.—PRELIMINARY OATH OF COMPASSMAN.]

I, Ernst Salomon

do solemnly swear that I will well and truly perform the duties of compassman, according to instructions given me, and to the best of my skill and ability, in the survey and resurvey of the subdivision lines of Tps. 9, 10 & 11 N. R. 13 W — T. 11 N. R. 14 W — Tps. 10 & 11 N. R. 16 W — & Fract. Tp. 9 N. R. 16 W — and E. & W. Bdys. T. 9 N. R. 13 W — S. E. & W. Bdys. T. 10 N. R. 13 W — N. Bn. Tp. 11 N — R. 13 W & E. Bn. Tp. 9 N. R. 16 W

of the Salt Lake base and meridian in the Territory of Utah.

Ernst Salomon, Compassman.

Subscribed and sworn to before me this 3rd day of May 1884

Henry Pittsburgh
U. S. D. L. Surveyor

Blank

Page

[2.—PRELIMINARY OATHS OF CHAINMEN.]

We, Stewart M. Pancake

and Walter L. Whately

do solemnly swear that we will well and faithfully execute the duties of chain carriers; that we will level the chain upon even and uneven ground and plumb the tally pins, either by sticking or dropping the same; that we will report the true distance to all notable objects, and the true length of all lines that we assist in measuring, to the best of our skill and ability, and in accordance with instructions given us, in the survey and resurvey of the Subdivision lines of Tps. 9, 10 & 11 N. R. 13 W. T. 11 N. R. 14 W. Tps. 10 & 11 N. R. 16 W. & Fract. T. 9 N. R. 16 W. and E. & W. Bdys. T. 9 N. R. 13 W. S. E. & W. Bdys. T. 10 N. R. 13 W. N. Bdy. T. 11 N. R. 13 W. E. Bdy. Tp. 9 N. R. 16 W. of the Salt Lake base and meridian in the Territory of Utah.

Stewart M. Pancake, Chainman.

Walter L. Whately, Chainman.

....., Chainman.

....., Chainman.

Subscribed and sworn to before me this 3rd day of May 1884

Henry Elzinga
U.S. Dep. Surveyor

Blank

Page

[3.—PRELIMINARY OATH OF AXEMEN.]

We, Samuel J. Cook

and David R. Sinclair

do solemnly swear that we will well and truly perform the duties of axemen, in the establishment of corners and other duties, according to instructions given us, and to the best of our skill and ability, in the survey and resurvey of the Subdivision lines of Tps. 9, 10 & 11 N. R. 13 W. T. 11 N. R. 14 W. Tps. 10 & 11 N. R. 16 W. & Tract T. 9 N. R. 16 W. End E. & W. Bdys. T. 9 N. R. 13 W. S. E. & W. Bdys. T. 10 N. R. 13 W. N. By. Tp. 11 N. R. 13 W. & E. By. Tp. 9 N. R. 16 W.

of the Salt Lake base and meridian in the Territory of Utah.

his witness. E Salomon

Samuel J. Cook, Axeman.

mark

David R. Sinclair, Axeman.

Subscribed and sworn to before me this 3rd day of May 1884

Henry Fitzhugh

U.S. Dep. Surveyor

Re-Survey

By Tp. 10 N. R. 13 W. S L M

On the night of May 2nd 1884 took an observation of the star Polaris, in accordance with instructions contained in the manual of surveys, and drove picketts on the line thus established

Survey Commenced May 3rd 1884 with a gurley transit

Before commencing this survey I test my transit on the line established last night and find the variation of the needle to be 18° 10' E

I begin at the Cor. to Tps. 10 & 11 N. Rs. 12 & 13 W. which is a pine stake 23 x 3 x 3 ins. properly marked and reset by me under Contract No 116

Re-Survey E. By T. 10 N.

Chains	Thence I run
	South on re-survey line Bet. Secs. N C. Va 1870' E.
40.00	No trace of old Cor. Set Temporary 1/4 Sec Cor. I then continue S. to
77.50	Find old stake (24×3×3 ins pine) thrown down & traces of old mound. I re-mark & re-set same in S.E. pit after removing old mound & pits. I then return and at
37.50	Set volcanic rock 24×10×4 ins 15 ins. in the ground for 1/4 Sec. Cor. Marked 1/4 on W. face and made regulation mound & pits
53.00	Leave bottom bears N.W. & S.E.
67.00	Enter high bench bears. N.W. & S.E
77.50	Re-set old stake, which is a pine 24×3×3 ins & re-

N. R. 13 W. - S. L. M.

Chains | Mark same for re-established Cor. to Secs. 1, 6, 7 & 12
Land bottom & bench
Soil 1st rate - sandy
Dense sage brush & grease-wood undergrowth on 77.50 chs.

South on re-survey line
Bet. Secs. 7 & 12
Va 18°10' E.

40.00 No trace of old Cor.
Set Temporary Cor.
80.00 Find Add Cor. Standing
I then return to
40.00 Set Lime-stone 20 x 18 x 5 ins
15 ins. in the ground for
re-established 1/4 Sec. Cor.
Marked 1/4 on W. face and
Made regulation mound
& pits
80.00 Find old Cor standing pro-
perly marked (a pine post
22 x 3 x 2 ins) above ground
I renew old mound from

Re-Survey E. By. T. 10 N.

Chains	old pits of which traces remain for re-established Cor. to Secs. 7, 12, 13 & 18
	Land brush
	Soil 1st rate
	Dense sage brush & grease wood undergrowth on 80.00 chs.
	South on re-survey line Bet. Secs. 13 & 18 Vn 18°10' E.
4.00	Descend
15.00	Enter flat bears E & W.
20.50	Road bears N.W. & S.E.
30.70	Telegraph line bears N.W. & S.E.
32.20	Central Pacific Rail road track bears N.W. & S.E.
33.60	Telegraph line bears N.W. & S.E.
40.00	No trace of old Cor.
	I then run S. to
80.00	Find old Cor. standing
	I then return to
40.00	Set Lime stone 13 x 6 x 5 ins

R. 13 W. — S. L. Ind.

Chains 9 ins. in the ground for re-established 1/4 Sec. Cor. marked 1/4 on W. face & made regulation mound & pits

80.00 Find old Cor. standing (a pine post 2 x 2 x 12 ins above ground) properly marked I renew old mound from pits of which traces remain for re-established Cor. to Secs. 13, 18, 19 & 24

Land flat

Soil 1st rate - sandy

Dense sage brush & Greasewood undergrowth on 80.00 Chs.

South on re-survey line Bet. Secs. 19 & 24

Ca 18.°10' E.

40.00 No trace of old Cor.

Set temporary Cor.

80.00 Find old Cor. standing

I then return to

Re-Survey - E By T. 10 N.

Chains	
4.00	Set Lime stone 10x10x6 ins - 6 ins. in the ground for re-established 1/4 Sec. Cor. Marked 1/4 on W. face & made regulation mound & pits.
6.30	Wash drains S.E.
8.00	Find old Cor. standing (a pine stake 2x2, 12 ins. above ground properly marked I re-new old mound from pits of which traces re-main for re-established Cor. to Secs. 19, 24, 25 & 30
	Land flat
	Soil 1st rate.
	Dense sage brush & Grease = wood undergrowth on 8.00 chs.
	South on re-Survey line Bet. Secs. 25 & 30
	Va 18°.10' E
4.00	No trace of old Cor. Set Temporary Cor.

R. B. W. S. L. M.

Chains

80.00 Find old stake standing
Then return to
40.00 Set Pine-Stone 12x10x6 ins-
8 ins. in the ground for re-
established 1/4 Sec. Cor. mark-
ed 1/4 on W. face & made
regulation mound & pits
60.00 Wash drains S.W.
80.00 Find old Cor. standing (a
pine post 2x3x12 ins above?
ground properly marked
for Cor. to Secs. 25, 30, 31 & 36
I renew old mound from
pits of which faint traces
re-main

Land flat
Soil 1st rate
Dense sage brush & Greasewood
undergrowth on 8.00 chs.

South on re-survey line
Bet. Secs. 31 & 36
Dn 18.10 E
20.00 Wash drains S.W.

Re-Survey - E By T. 10 N.

Chain		Chain
40.00	No trace of old Cor.	
	Set temporary Cor	
54.40	Wash drains S W	
80.00	Find old Cor. thrown down	
	I then return to	
40.00	Set Lime stone 10×7×7 ins	
	6 ins in the ground for re=	
	established 1/4 Sec. Cor. mark	
	ed 1/4 on W. face and	
	made regulation mound	
	& pits	
80.00	Find old Cor. (a pine stake)	
	thrown down & decayed	
	& faint traces of old mound	
	I set Quartzite 24×10×4 ins -	
	15 ins in the ground in	
	old mound, Marked 6	
	notches on N. S. E & W.	
	Edges and raised a	
	mound of earth alongside	
	from pits of regulation	
	size for Cor. to Tps. 9 &	
	10 N. Rs. 12 & 13 W	
	Land flat	
	Soil 1st rate	

R. 13 W. S. L. M.

Chains

Dense sage brush & shadscale underground on 8000 Chs.

General Description
The land on each side of this line is brush & flat, covered with sage brush & in places shad=scale affording fine winter range for stock
Henry Fitzhugh
U.S. Dep. Surveyor.

Blank

Page

S. By. Tp. 10 N. R. 13 W. S.L.M.

Note-
many of the old Cors. being destroyed & obliterated as I intend to subdivide T. 10 N. R. 13 W. I find it necessary to make re-survey of E. S. & W. Bdys of said Tp. Therefore

From the Cor. to Tps. 9 & 10 N. Rs. 12 & 13 W. re-established by me during this survey

I run
West on re-survey line
Bet Secs. 1 & 36
Va 18°10' E.

40.00 No trace of old Cor.
80.00 Find old Cor. thrown down
I then return to
40.00 Set Limestone 20 x 10 x 8 ins - 15 ins. in the ground for re-established 1/4 Sec. Cor. Marked 1/4 on N. face and made regulation mound

Re-Survey S By. T. 10 N.

Chains		Cha
	and pits,	
72.50	Wash drains S W.	
80.00	Find old Cor. which is a pine stake 24×3×3 ins. thrown down & traces of old mound I renew old mound from pits of regulation size & remark & drive old stake in S.E. pit for re-established Cor. to Secs. 1, 2, 35 & 36	8
	Land flat	
	Sail 1st rate	
	Dense sage brush & greasewood underground on 80.00 chs.	
	West on re-survey line Bet. Secs. 2 & 35 Dn 18.10' E.	
40.00	No trace of old Cor.	4
80.00	Find old Cor.	
	I then return to	8
40.00	Set Limestone 14×9×5 ins	

R. 13 W. - S. L. M.

Chains 10 ins. in the ground for re-established 1/4 Sec. Cor. marked 1/4 on N. face and made regulation mound & pits

80.00 Find old Cor. which is a pine post. 24 x 2 x 2 ins. thrown down - I reset old mound of which traces remain from regulation pits & re-mark & drive old stake in S.E. pit for re-established Cor. to Secs. 2, 3, 34 & 35

Sand flat

Soil 1st rate

Dense sagebrush & Greasewood undergrowth on 80.00 Chs

West on re-Survey line
Bet Secs. 3 & 34
Va 18°.10' E

40.00 No trace of old Cor.
Set Temporary Cor.

80.00 Find old Cor.
I then return to

Re-Survey S. By. Tp. 10 N

Chains		Chains
40.00	Set Limestone 10×8×8 ins 6 ins. in the ground for re-established 1/4 Sec. Cor. marked 1/4 on N. face, and made regulation mound & pits.	80.00
		40.00
80.00	Find old Cor thrown down & traces of old mound. I remove old mound from regulation pits I drive old stake (a pine 24×3×3 ins properly marked) in S.E. pit for re-established Cor. to Secs. 3, 4, 33 & 34	
	Land flat	80.00
	Soil 1st rate	
	Dense sage brush & shadscale undergrowth on 80.00 chs.	
	West on re-Survey line Bet Secs. 4 & 33 Dn 18.10 E	
7.00	Wash drains S.W.	40.00
40.00	No trace of old Cor.	80.00

R. 13 W. S. L. M.

Chains Set Temporary Cor.
80.00 Find old Cor.
I then return to
40.00 Set Sandstone 12x8x6 ins - 8 ins. in the ground for re-established 1/4 Sec. Cor, marked 1/4 on N. face, and made regulation mound & pits.
80.00 Find old Cor. Standing (a pine post 12x2x2 ins above ground properly marked)
I remove old mound from regulation pits for Cor. to Secs. 4, 5, 32 & 33
Land flat
Soil 1st rate
Dense sage brush & shadscale undergrowth on 80.00 Chs.

West on re-Survey line
Bet. Secs. 5 & 32
Va 18°10' E.

40.00 No trace of old Cor.
80.00 Find old Cor.

Re-Survey S. Bdy. T. 10 N.

Chain	I then return to
40.00	Set Limestone 12×10×8 ins-8 ins. in the ground for re-established 1/4 Sec. Cor. marked 1/4 on N. face, and made regulation mound & pits.
62.50	Wash drains S. W.
80.00	Find old cor. (a pine post) standing properly marked for Cor. to Secs. 5, 6, 31 & 32. I renew old mound of which traces remain from regulation pits

Land level
Soil 1st rate
Dense sage brush & shadscale undergrowth on 80.00 chs.

West on re-survey line
Bet. Secs. 6 & 31
Dn 18.10' E.

40.00	No trace of old cor. set temporary cor

R. 13 W. - S. L. M.

Chain
79.75 - Find old Cor.
I then return to.
40.00 Set Limestone 10x8x8 ins - 6 ins. in the ground for re-established 1/4 Sec. Cor. marked 1/4 on N. face x made regulation mound & pits
57.00 Wash drains S.
79.75 - Find old Cor. (a pine post standing properly marked for Cor. to Tps. 9 & 10 N. Rs. 13 & 14 W. - I renew old mound from regulation pits
Land flat
Soil 1st rate
Dense sage brush & shadscale undergrowth on 79.75 Chs.
May 3d 1884

~~General Description~~

~~For General Description See end of subdivision notes of~~

Blank

Page

T. 9 N. R. 10 N. - R. 13 W. S.B.M.

From the Cor. to Trs. 9 & 10 N.
Rs. 13 & 14 W. re-established
by me during this survey
I run
North on Re-Survey line
Bet. Secs. 31 & 36
Va 18° 10' E.

22.50 Road bears N.E. & S.W.
40.00 No trace of old Cor.
Set Temporary Cor.
80.00 Identify old Cor.
I then return to
40.00 Set volcanic rock 16 x 10 x 6 ins.
" 10 ins. in the ground for re-
established 1/4 Sec. Cor. mark-
ed 1/4 on W. face and raised
a mound of stone alongside
70.25 Wash drains S.E.
77.60 Telegraph line bears N.E. & S.W.
78.00 Central Pacific rail road
track bears N.E. & S.W.
78.50 Telegraph line bears N.E. & S.W.
80.00 Find old stake thrown down
& decayed with sufficient
of old mound remaining

Re-Survey W. By T. 10 N.

Chains	
	to identify the true locus of old Cor.
	I set Lime stone 30×20×12 ins 22 ins. in the ground for re-established Cor. to Secs. 25, 30, 31 & 36, marked 1 notch on S & 5 notches on N. edges and made regulation mound & pits.
	Land flat
	Soil 1st rate
	Dense sage brush & shadscale undergrowth on 80.00 Chs.
	North on re-Survey line Bet. Secs. 25 & 30 Va 18° 10' E.
35.70	Wash drains S. W.
40.00	No trace of old Cor.
	Set Temporary Cor.
80.00	Identify old Cor.
	I then return to
40.00	Set Conglomerate 16×8×6 ins. 10 ins. in the ground for re-

R. 13 W. S. L. M.

Chains re-established 1/4 Sec. Cor. marked 1/4 on W. face and made regulation mound and pits.

80.00 Find old Cor (a pine stake 24×2×2 ins lying by the side of old mound - I re=new old mound from regulation pits and re=mark & drive old stake in S.E. Pit for re-established Cor. to Secs. 19, 24, 25 & 30

Land rolling brush

Soil 1st rate

Dense sage brush & Greasewood undergrowth on 80.00 chs.

North on re-Survey line Bet. Secs. 19 & 24

Va 18° 10' E

19.00 Wash drains S.W.

32.15 Ascend hills bear N.E. & S.W.

40.00 No trace of old Cor.

Set temporary Cor.

Re-Survey W. Bg. L. 10 N.

	Chains	
Ch	76.00	Top of hill bear N.E. & S.W.
	80.00	Leaving old Cor.
		I turn return to
	40.00	Set Pine stake 20×1½×1½ ins
		15 ins. in the ground for re-established ¼ Sec. Cor. mark-ed ¼ on W. face and raise a mound of stone alongside
	80.00	Find cedar a pine stake 24×3×2 ins lying on the ground by the side of old mound – I remove old mound from regulation pits, and re-mark and drive old stake in S.E. pit for re-established Cor. to Secs. 13, 18, 19 & 24
		Land high rolling bunch Soil 1st & 2nd rate.
		Dense sage brush & shadscale undergrowth on 80.00 chs.
		North on re-survey line Bet. Secs. 13 & 18

R. 13 W - S. L. M

Va 18° 10' E.

Chains	
40.00	No trace of old cor. Set Temporary Cor.
80.00	Identify old Cor. I then return to
40.00	Set Limestone 30 x 24 x 16 ins. 22 ins. in the ground for re-established 1/4 Sec. Cor. Marked 1/4 on W. face, and raised a mound of stone alongside -
58.90	Wash drains S.E.
80.00	Find old cor. a pine stake 24 x 2 x 2 ins. lying on the ground by old mound - I renew old mound from regulation pits and remark and ~~re~~ drive old stake in S.E. pit for re-established Cor. to Secs. 7, 12, 13 & 18. Land high rolling bench Soil 1st & 2nd rate. Dense sage brush & Greasewood undergrowth on 80.00 chs.

Re-Survey W. Bry T. 10 N.

North on Re-Survey line
Bet. Secs. 7 & 12
Va 18.10 E

37.50 Enter hills bear N.E. & S.W.
40.00 No trace of old Cor.
Set Temporary Cor.
80.00 Identify old Cor.
I then return to
40.00 Set Martzite 16×10×8 ins - 10
ins. in the ground for re-
established 1/4 Sec. Cor.
marked 1/4 on W. face and
made regulation mound and
pits
45.00 Gulch drains S.W.
60.00 " " "
69.50 " " "
80.00 Find old Cor. a pine stake
thrown down & broken & lying
by the side of old mound.
I set Limestone 24×10×10 ins
18 ins. in the ground for
re-established Cor. to Secs.
1, 6, 7 & 12, marked 5 notches
on S. & 1 notch on N. edges.

R. 13 W. S. L. M.

chains	and renewed old mound from regulation pits. Land hilly Soil 2nd rate. Dense Sage brush & Greasewood Undergrowth on 80.00 chs.
	North on re-Survey line Bet. Secs. 1 & 6 Va 18° 10' E.
12.50	Gulch drains S.W.
30.70 40.00	Gulch No trace of old Cor. Set Temporary Cor.
79.70	Identify old Cor. Then return to
40.00	Set Cedar post 3 ft. long 3 ins. square 12 ins. in the ground for 1/4 Sec. Cor. Marked 1/4 S. on W. face and made regulation mound and pits.
79.70	Find old Cor. standing

Re-Survey

302

W. By. T. 10 N R 13 W - S. L. M.

Chains | Properly marked for Cor. to Tps. 10 & 11 N. Rs. 13 & 14 W. -
This Cor. was re-established by me under Contract No. 116

Land hilly
Soil 1st & 3rd rate
Dense sage brush & Greasewood undergrowth on 79.70 chs.
May 5, 1884

General Description

For general Description See end of Subdivision Notes of Tp. 10 N. R. 13 W.
Henry Fitzhugh
U.S. Deputy Surveyor

BOOK-A-203

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, October 11th *1884*

The foregoing field notes of the re *survey of the* South, East and West boundaries

Township No. 10 North *Range No.* 13 West

Executed by Henry Fitzhugh

Under No 124 *contract of the* 19th *day of* March *1884, in the month of* May *1884, having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

Fred Salomon

U. S. Surveyor General for Utah.

Blank

Page

BOOK-A-203 305 1000

REPORT: 1885

Filed ..... 188.

Examined by John H. Dampe

Transcribed by E. Michaelis

Compared by H. Salomon & E. Michaelis

FIELD NOTES

OF THE SURVEY OF THE

Subdivisions

OF

Township No 10 N.

Range No 13 W.

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Henry Fitzhugh

U.S. Deputy Surveyor,

Under his Contract No. 124

Dated March 19th 1884

Survey commenced May 6 1884

Survey completed " 13 1884

BOOK-A-203

Township 10 N. R. 13 W.

383	6	382	5	381	4	380	3	379	2	378	1
377	7	376	8	375	9	374	10	373	11	372	12
371	18	370	17	369	16	368	15	367	14	366	13
365	19	364	20	363	21	362	22	361	23	360	24
359	30	358	29	357	28	356	27	355	26	354	25
353	31	352	32	351	33	350	34	349	35	348	36

BOOK-A-203

Subdivisions Tp. 10 N R 13 W.

Survey commenced
May 6th 1884 with
a Burts improved Solar
Compass.
From the cor to Secs. 1. 2
35 & 36 on the S. Bd. of the Tp.
re-established by me during
this survey I run
North lat. Secs. 35 & 36
Va. 18°10' E.

40.00 Set Volcanic rock 12x8x6 in
8 in. in ground for 1/4 Sec.
cor. marked 1/4 on W face
dug pits 18X18X12 in.
W & S of cor. raised mound
of earth 1 1/2 ft. high 3 1/2 ft
base alongside

80.00 Set charred cedar post 4 ft.
long 4 in. square, 12 in. in
the ground, for cor. to Secs.

of the Salt Lake Meridian

chains 25. 26. 35 & 36. marked with 1 notch on S and 1 on E. edges. [illegible]
T. 10 N. S. 25 on N. E.
R 13 W S. 26 on N. W
S. 35 on S. W and
S 36 on S. E faces dug pits 18×18×12 in. in each sec. 5½ ft. dist. and raised a mound of earth 2 ft high 4½ ft. base alongside.
Land level
Soil 1st rate
Dense sage brush and shadscale, undergrowth on 80 chs.

East on a random line bet. Secs. 25 & 36
Va. 18° 10' E.

Tow

301
3
300
3
298 1
37
297 19
37
296 30
36
295 31
29

Subdivisions Tp. 10 N. R 13 W

chs.	
40.00	Set temp 1/4 Sec. cor.
80.09	Int Int E. Bd of Tp. 13 lks. N of the cor. to Secs. 25. 30. 31 & 36. from which Trees N 89° 54' W on true line bet. Secs. 25 & 36 with same va.
40.05	Set Limestone 16 X 12 X 8 in 10 in. in ground, for 1/4 Sec cor. marked 1/4 on N. face dug pits 18 X 18 X 12 in. E & W of cor. 5 1/2 ft. dist raised mound of earth 1 1/2 ft. high 3 1/2 ft. base alongside.
57.50	Wash drus. S. E.
80.09	The cor. to Secs. 25. 26. 35 & 36 Land level

of the Salt Lake Meridian

Chains	
	Soil 1st rate
	Dense Sage brush and shadscale undergrowth on 80.09 chs
	North bet. Secs. 25 & 26
	Va. 18°10' E.
4.00	Set flint stone 14 x 10 x 10 in 9 in. in ground, for 1/4 sec. cor. marked 1/4 on W face, dug pits 18 x 18 x 12 in N & S. of line 5 1/2 ft. dist. raised mound of earth 1 1/2 ft. high 3 1/2 ft. base alongside
80.00	Set flint stone 40 x 28 x 12 in 30 in. in ground for cor to Secs. 23. 24. 25 & 26. marked, with 2 notches on S and 1 on E. edges dug pits 18 x 18 x 12 in. in each sec. 5 1/2 ft. dist. and

Subdivisions Tp. 10 N. R 13 W

chains	raised a mound of earth 2 ft. high 4½ ft. base alongside
	Land level
	Soil 1st & 2nd rate
	Dense sagebrush and shadscale undergrowth on 80. chs.
	East on a random line bet. Secs. 24 & 25
	Va. 18°10' E.
40.00	Set temp 1/4 Sec. cor
80.10	Int E. Bd of Tp. 27 lks. S. of cor. to Secs. 19. 24. 25 & 30, from which S. 89° 48' W on true line bet. Secs. 24 & 25
	with same va.
40.05	Set Conglomerate rock

of the Salt Lake Meridian

chs	
	18 X 12 X 6 in. 12 in. in ground for 1/4 Sec. cor. marked 1/4 on N face dug pits 18 X 18 X 12 in. E & W. of stone raised a mound of earth 1 1/2 ft high 3 1/2 ft. base alongside
80.10	The cor to Secs. 23. 24 25 & 26.
	Land level
	Soil 1st rate
	Dense sagebrush and greasewood underground on 80.10 chs.
	North bet. Secs. 23 & 24
	Va. 18°10' E.
40.00	Set volcanic rock 20 X 16 X 8 in. 15 in. in ground, for 1/4 Sec. cor. marked 1/4 on W. face, dug pits 18 X 18 X 12

Subdivisions Tp. 10 N. R 13 W

chns	in. N. & S. of cor. 5½ ft. dist. and raised mound of earth 1½ ft. high 3½ ft. base alongside.
71.25	Telegraph line brs. N.E. & S.W.
72.30	Central Pacific R.R. brs. N. E. & S. W.
73.15	Telegraph line brs. N.E. & S.W.
80.00	Set Limestone 21 x 10 x 8 in. 15 in. in ground for cor. to secs. 13. 14. 23 & 24 marked with 3 notches on S. and 1 on E. edges, dug regulation pits and raised mound of earth alongside.
	Land level
	Soil 2nd rate
	Dense sage brush and shadscale undergrowth on 80.00 chs

of the Salt Lake Meridian

Ward.

Subdivisions Tp. 10 N. R 13 W

chns.	East on a random line bet. Secs. 13 & 24
	Va. 18°10' E.
40.00	Set temp. 1/4 Sec. cor
79.91	Int E. Bd. of Tp. 26 lks. N. of reestablished cor. to Secs. 13. 18. 19 & 24 from which I run N. 89°49' W on true line bet. Secs. 13 & 24
39.95	with same va
39.95	set Limestone 10 x 10 x 8 in 8 in. in ground for 1/4 Sec. cor. marked 1/4 on N. face dug reg. pits and raised mound of earth alongside
58.20	Telegraph line brs. N. E & S. W
69.00	Central Pacific R. R. brs N. E & S. W
70.10	Telegraph line brs. N. E & S. W
79.91	The cor to Secs. 13. 14. 23 & 24
79.91	

of the Salt Lake Meridian

chns. Land Bench
Soil 1st rate
Dense sage brush and shad-
scale undergrowth on 79.91 chs.

North bet. Secs. 13 & 14
Va. 18°10' E

2.50 Road brs N.E. & S.W.
20.00 Wash drns. S.E.
21.50 " " "
40.00 Set Limestone 30 x 24 x 13 in.
23 in. in ground for 1/4
Sec. Cor. marked 1/4 on W.
face dug regulation pits
and raised mound of earth
alongside.
42.50 Foot of Mtns. bear N.E. & S.W.
Ascend Leave dense undergrowth
80.00 Set Quartzite 24 x 12 x 10 in

Subd. T. 10 N. 13 W

chas. 18 in in ground, for cor to
Secs 11. 12. 13 & 14 marked
with 4 notches on S and on
E. edge raised mound
of stone alongside.
Land Bench & Mtns.
Soil 2nd & 3rd rate
Dense sage brush & shadscale
undergrowth on 42.50 chs.
High Mountains on 37.50 chs
Augmented on 80.00 chs

East on a random line
bet. Secs. 12 & 13
Va. 18° 0' E.
40.00 set temp 1/4 Sec. cor.
79.75 Int E. Bd. of Tp. 36 lks N
& re established cor to Secs
11. 12. 13 & 18 from which
N. 89° 45' W on true line

of the Salt Lake Meri

chus. bet. Secs. 12 & 13
north same va
39.87 Set Volcanic rock 16x10x6 in
12 in in ground for 1/4 Sec. cor.
marked 1/4 on N. face raised
mound of stone alongside
50.25 Leave high Bench & dense
Undergrowth Ascend
79.75 The cor. to Secs. 11, 12, 13 & 14
Land high bench & Mtns.
Soil 2nd & 4th rate
Dense sagebrush and shad
scale undergrowth on 50.25
High Mountains on 29.50
Augmented on 79.75

North bet. Secs 11 & 12
Va. 18° 15' E.
Note: On account of high
rocky inaccessable Mountains

Subs. Tp. 10 N. R 13 W

chns.	
	I offset East 19.00 chs thence North on offset line
	Ascend
17.00	Enter high Plateau N.E & S.W
35.00	Descend Leave Plateau
40.00	Set Lime stone 12 x 8 x 8 in 8 in. in ground for Witness 1/4 Sec. cor. marked W. C. 1/4 on W face raised stone mound alongside
57.50	Gulch drns. E. Enter high rolling bench ~~bars~~ N & S and dense sage brush undergrowth
60.00	thence West 19. chs. to point on true line thence North to
80.00	Set Volcanic rock 15 x 8 x 7 in. 10 in. in ground, for cor.

of the Salt Lake Mer.

chns		to Secs 1. 2. 11 & 12. marked with 5 notches on S and 1 on E. edges, and raised Mound of stone alongside Land Mtns. & Bench Soil 3rd & 1st rate
50		Dense Sagebrush undergrowth on 20.50 chs
79.		High Mountains on 59.50 chs Augmented on 80 chs
		East on random line bet. Secs. 1 & 12 Va. 18°10' E
	40.00	Set Temp. 1/4 Sec. cor
	79.88	Int. E. Bd. of Tp. 45 lks N. of ctra re-established cor. to Secs. 1. 6. 7 & 12 from which N. 89°41' W. on true line

BOOK-A-203

Subs. Tp. 18 N. R 13 W.

bet. Secs. 1 & 12

with same va.

39.94 Set Limestone 10x10x6 in
6 in. in ground for 1/4 Sec.
cor. marked 1/4 on N face
dug reg. pits and raised
mound of earth alongside

79.88 The cor. to Secs. 1. 2. 11 & 12

Land high rolling Bench
Soil 1st rate

Dense Sage brush undergrowth
on 79.88 chs.

North on a random line
bet. Secs. 1 & 2

Va. 18° 18' E

4.00 Set temp 1/4 Sec. cor
78.00 Intersect N. Bd. of Tp. 48
lks. W. of cor. to Secs. 1. 2.
35 & 36 which is a limestone 4x8
x6 ins. above ground properly mark-
ed & mound & pits alongside.

of the Salt Lake Mer.

Chns.

Ground which I run S 0° 20' W
on true line bet. Secs. 1 & 2.
with same va.

38.00 Set Limestone 20 x 15 x 6 in
15 in. in ground, for 1/4 Sec.
Cor. marked 1/4 on W. face
dug reg. pits and raised
mound of earth along side

78.00 The cor. to Secs. 1, 2, 11 & 12
Land high rolling Bench
Soil 1st rate
Dense sage brush undergrowth
on 78.00 ch.

May 6. 1884

From the cor. to Secs. 2 & 3
34 & 35 on the S. Bd.
of the Tp. re-established by me
during this survey I run

BOOK-A-203

Sub's Tp. 10 N. R. 15 W

chus. North bet. Secs. 34 & 35

Va. 18° 10' E.

4,00 Deposited quartz pebbles 12 in. in ground, for 1/4 Sec. cor. dug pits 18 X 18 X 12 in. N & S. of cor point 5 1/2 ft. distant and raised mound of earth 1 1/2 ft. high 3 1/2 ft. base over it in N. pits drove a charred stake 2 ft. long 2 in. square, 12 in. in ground, marked 1/4 S on W. face.

8000 Set a bobel stone 16 X 10 X 10 in. 10 in. in ground, for cor. to Secs. 26, 27, 34 & 35, marked with 1 notch on S and 2 on E. Edges. dug orig. pits and raised mound of earth alongside

Land level

of the Salt Lake Mer.

Chns.	Chns.	Soil 1st rate
		Dense Sage brush undergrowth on 80 chs.
38.00		East on random line bet. Secs. 26 & 35 Va. 18°10' E.
	40.00	Set temp. 1/4 Sec. cor.
	80.00	Intersect N & S. line at cor to Secs. 25. 26. 35 & 36.
78.00		from which I run West on a true line bet. Secs 26 & 35 with same va.
	20.50	Wash drns. S. E.
	40.00	Set Limestone 24 x 22 x 4 in 18 in. in ground, for 1/4 Sec. cor. marked 1/4 on N. face deg reg. pits and raised mound of earth along side

48 [illegible]

Subs Tp. 18 N. R 13 W

62.75 Wash drns. S.E.
80.00 The cor. to Secs. 26. 27.
34 & 35
Land Level
Soil 1st rate
Brush sagebrush undergrowth
on 80.00 chs.

North bet. Secs. 26 & 27
Va. 18° 10' E.
35.00 Wash drns. S.E.
4.00 Set Limestone 12 X 9 X 6 in.
8 in. in ground for 1/4 Sec.
cor. marked 1/4 on W. face
dug reg. pits and raised
mound of earth alongside
62.00 Wash drns. S.E.
80.00 Set Limestone 22 X 10 X 4 in.
16 in. in ground for cor. to

of the Salt Lake Mer.

Chns.

Secs. 22. 23. 26 & 27 marked
with 2 notches on S and 2 on
E. edges, dug pits and raised
mound of earth alongside
38.00 Land level Bench
Soil 1st rate
Brush sagebrush undergrowth
on 80. chs.

78.00 East on random line
bet. Secs. 23 & 26
Va. 18°, 0' E.
40.00 Set temp 1/4 Sec. cor
80.00 Int N & S. line 20 lks. N of
cor. to Secs. 23. 24. 25 & 26,
from which I run
N. 89° 51' W. on true line
bet. Secs. 23 & 26
with same va

Subs. Tp. 10 N, R 13 W.

chs.	
19.00	Wash drain S.E.
42.00	Set volcanic rock 30x30x 8 in. 23 in. in ground, for 1/4 Sec. cor. marked 1/4 on N face dug req pits and raised mound of earth alongside
67.00	Wash drain S.E.
80.00	The cor. to Secs. 22.23 26 & 27
	Land level
	Soil Pr rate
	Dense sagebrush undergrowth on 80 chs.
	North bet. Secs. 22 & 23 Va. 18° 0' E.
9.30	Telegraph line bears N.E. & S.W
10.10	Central Pacific R.R. " " " "
12.05	Telegraph Line bears " " " "

of the Salt Lake mer

chns.	
18.30	Road brs. N. E. & S. W.
40.00	Set Limestone 16 x 10 x 6 in. 10 in. in ground, for 1/4 Sec. Cor. marked 1/4 on W. face dug reg Pits and raised mound of earth alongside
45.00	Leave bench and dense undergrowth. Enter Mtns bear N. E. & S. W.
75.25	Gulch drns. S. E.
80.00	Set Sandstone 24 x 12 x 10 in 18 in. in ground for cor to Secs. 14. 15. 22 & 23, marked with 3 notches on S and 2 on E. edges and raised mound of stone alongside
	Land Bench and Mtns.
	Soil 2nd & 3rd rate
	Dense undergrowth (sage brush) on 45 chs.

Sub

chns.	
	Ma
	Ca
	E
	Ea
	be
40.00	g
80.19	In
	to
	wi
	b
3.00	R
40.09	Se
	12
	co
	ra
60.00	L
	be
75.00	

Subs. Tp. 10 N. R 13 W

chns.	High Mountains ... 35.00
	Augmented on 80.00 chs
	East on random line
	bet. Secs. 14 & 23
	Va. 18°15' E
40.00	Set temp 1/4 Sec. cor.
80.19	Int. N & S. line 30 lks. N. of cor
	to Secs. 13. 14. 23 & 24 from
	which N. 89°47' W on true line
	bet. Secs. 14 & 23
	with same va.
3.00	Road brs N.E. & S.W
40.09	Set Limestone 18 x 10 x 6 in.
	12 in. in ground, for 1/4 Sec
	cor. marked 1/4 on N face
	raised a mound of stone alongside
60.00	Leave dense undergrowth &
	bench and Ascend Mtns.
75.00	Gulch drns. S.E.

of the Salt Lake Mer

80.19	The cor. to Secs. 14. 15. 22 & 23	
	Land level Bench & Mtns.	
	Soil 1st & 3rd rate	
	Dense sagebrush undergrowth	
	on 60. chs.	
	High Mtns. on 20.19 chs	
	Augmented on 80.19 chs	
	North bet. Secs. 14 & 15	
	Va. 18°10' E.	
0.75	Ravine drns. S. E.	
40.00	Set Conglomerate 30 x 10 x 8 in	
	23 in. in ground, for 1/4 Sec.	
	cor. marked 1/4 on W. face	
	raised Stone mound alongside	
45.00	Gulch drns. S. E.	
65.00	" " " "	
80.00	Set Limestone 12 x 12 x 10 in	
	8 in. in ground for cor.	
	to Secs. 10. 11. 14 & 15	

Subs. Tp. 10 N. R 13 W

-23	Chs.	marked with 4 notches on S and 2 on E. edges raised mound of stone alongside
		Land Mountainous
		Soil 3rd rate
		High Mountains & sage brush on 80 chs.
		East on random line bet. Secs 11 & 14
		Va. 18° 10' E.
	40.00	Set temp 1/4 Sec. cor
	80.00	Int N & S. line, 12 lks. N. of cor. to Secs. 11. 12. 13 & 14 from which I run N 89° 55' W. on true line bet. Secs. 11 & 14
		with same va
	10.00	Gulch drus. S. W
	25.00	" " "

of the Salt Lake Mer

chns.	
35.50	Junction of Gulches read N. W. and N. E. drn. S. E.
40.00	Set Conglomerate 20 x 8 x 8 in. 15 in. in ground, for 1/4 sec. cor. marked 1/4 on N face raised mound of stone alongside.
48.50	High Ridge brs. N & S.
55.00	Deep Gulch drns. S. E.
60.00	Ridge brs. N & S.
65.75	Deep Gulch drns. S.
79.00	Deep Gulch " S. W.
80.00	The cor to secs. 10. 11. 14. & 15

Land Mtns.
Soil 4th rate rocky
High broken Mountains
on 80.00 chs.

Subs. Tp. 10 N. R 13 W

chns. North bet. Secs. 10 & 11
Va. 18° 10' E.

15.00 Ravine drns. S. W

33.50 " " "

37.00 Top of Ridge brs E & W

40.00 Set Limestone 18 X 12 X 8 in.
12 in. in ground for 1/4
Sec. cor. marked 1/4 on W
face raised mound of
stone alongside

52.50 Top of Ridge brs. N. E. & W.

65.00 Ravine drns N. W.

80.00 Set Limestone 14 X 10 X 10 in
9 in. in ground, for cor. to
Secs. 2. 3. 10 & 11 marked
with 5 notches on S and 2
on E. edge, raised mound
of stone alongside

Land Mtns.
Soil 3rd rate

of the Salt Lake Mer.

High Mountains on 80.00 80.00

East on random line
bet. Secs. 2 & 11
Va. 18°10' E.

40.00 Set temp 1/4 Sec. cor
79.37 Intersect N & S. line, 56 lks
N. of cor to Secs. 1. 2. 11 & 12
from which
N. 89°36' W. on true line
bet. Secs. 2 & 11
with same va.

39.68 Leave Bench & dense
undergrowth ascend Mtns
bear N.W. & S.E.
Set Limestone 17 x 8 x 5 in.
12 in. in ground, for 1/4 Sec
cor. marked 1/4 on N face
Dug orig. pits & raised mound

BOOK-A-205

Subs Tp. 10 N. R 13 W

Chs	
	of earth alongside
65.00	Ridge brs. N.W. & S.E.
79.37	The cor. to Secs. 2. 3. 10 & 11
	Land Bench & Mtns.
	Soil 1st & 4th rate
	Dense sagebrush under-
	growth on 39.68 chs.
	Mountainous on 39.69 chs.
	Augmented on 79.37 chs
	North on random line
	bet. Secs. 2 & 3
	Va. 18°10' E.
40.00	Set temp. 1/4 Sec. cor.
78.40	Int. N. Bd. of Tp. 20 lks. W
	of cor. to Secs. 2. 3. 34 & 35
	which is an aspen post 2 ft. 4 x 4 ins
	above ground properly marked & mound
	& pits alongside
	from which S. 0° 9' W on true
	line bet. Secs. 2 & 3
	with same va.
36.40	Gulch drns. N.E. foot of Mtns.
	br. N.W. & S.E. Lower Bench & Dense undergrowth

of the Salt Lake Meridian

Chs	Chus. 38.40	Set Limestone 12x10x8 in. 8 in in ground, for 1/4 Sec. cor. marked 1/4 on W. face dug reg. pits and raised mound of earth alongside
38	72.00	Gulch drus. N. E.
	78.40	The cor. to Secs. 2. 3. 10 & 11
		Land Mtns. & Bench
		Soil 2nd & 1st rate
78.		High Mountains on 42.00 chs.
		Dense undergrowth sage brush and
		shadscale on 36.40 chs
		augmented in 78.40
		May 7. 1884
		From the re-established cor. to Secs. 3. 4. 33 & 34 on the S. Bd. of the Tp. I run North bet. Secs. 33 & 34
		Va. 18°10' E
		Through Dense sage brush

Subs Tp. 10 N. R 13 W

Chs. and Shadscale undergrowth
20.00 Leave Flat. Cors. N.W. & S.E
Enter Bench
40.00 Set volcanic rock 12 X 10 X 8 in.
8 in in ground, for 1/4 Sec. cor.
marked 1/4 on W face, dug reg pits
& raised mound of earth alongside
~~40.50~~ Gully drain S.E.
80.00 Set cobble stone 18 X 10 X 10 in. 12 in.
in ground, for cor. to Secs.
27. 28. 33 & 34 marked with 1 notch
on S. and 3 on E. edges, dug reg.
pits and raised mound of
earth alongside
Land level Bench & flat
Soil 1st rate
Dense Sage brush and
Shadscale undergrowth on 80 chs

of the Salt Lake Meridian

	chs.	East on a random line between Secs. 27 & 34 Va. 18° 10' E.
	40.00	Set temp ¼ Sec. cor.
	80.00	Intersect N & S. line 12 lks N of cor. to Secs. 26. 27. 34 & 35 from which N 89° 55' W on true line bet. Secs. 27 & 34 with same Va.
	39.40	Wash drain S.
	40.00	Set Sandstone 18 x 8 x 6 in 12 in. in ground for ¼ Sec. cor. marked ¼ on N face deep reg pits and raised mound of earth alongside
	57.90	Gully drains S. E.
	80.00	The cor to Secs. 27. 28. 33 & 34

Subs. T. 10 N. R 13 W

chs. Land level Bench
Soil 1st rate
Dense sagebrush and
shadical undergrowth
on 80.00 chs.

North bet. Secs. 27 & 28
Va. 18° 10' E.

36.75 Gulch drns. S.E.
40.00 Set Volcanic rock 22x10x8 in
15 in. in ground for 1/4 Sec.
cor. marked 1/4 on W face
dug regulation pits and
raised mound of earth
alongside
69.19 Telegraph line brs. N.E. & S.W.
69.95 Central Pacific R.R. brs.
N.E. & S.W.
70.75 Telegraph line brs. N.E. & S.W.

of the Salt Lake Meridian

C	chns. 80.00	Set Sandstone 20 x 12 x 10 in. 15 in. in ground for cor to Secs. 21. 22. 27 & 28. marked with 2 notches on
3		Sand 3 on E. edges, dug reg. pits and raised mound of earth alongside
		Land level bench
		Soil 1st rate
7		Dense sage brush and shadscale undergrowth on 80
		East on random line
		Bet. Secs. 22 & 27
		Va. 18°10' E.
	40.00	Set temp 1/4 Sec. cor
	80.10	Int. N & S. line 10 lks. S of cor. to Secs. 22. 23. 26 & 27 from which

Subs. T. 10 N. R 13 W

chs.	
	S. 89°56' W on true line bet. Secs. 22 & 27 with same va
15.60	Telegraph line brs. N. E & S. W
18.10	Central Pacific R. R brs. N. E & S. W.
20.00	Telegraph line brs. N. E & S. W.
37.50	Shelly drus. S. W
40.05	Set Sandstone 15 x 10 x 6 in. 10 in. in ground for 1/4 Sec. cor. marked 1/4 on N face raised mound of stone alongside.
40.25	Shelly drus. S
55.10	" " S. E.
80.10	The cor. to Secs. 21. 22. 27 & 28

Land Bench
Soil 1st rate
Drused sage brush and shad-scale undergrowth on 80.10 chs.

of the Salt Lake Meridian

Ch	chns.	North bet. Secs. 21 & 22
		Va. 18°10' E.
	9.80	Road bns. E & W
	29.50	Wash drns. S.E.
3	40.00	Set conglomerate rock
		30x14x12 in. 22 in. in
		ground for 1/4 Sec. cor.
		marked 1/4 on W face, dug
		orientation pits and raised
78		mound of earth alongside
	64.00	Gully drns. S.W.
	78.00	Wash drains S.W.
	80.00	At head of Gulch drns S.W.
		Set Limestone 18x10x10 in.
		12 in. in ground, for
		cor. to Secs. 15. 16. 21 & 22
		marked with 3 notches on
		S. and 3 on E. edges, dug
		orig. pits and raised mound
		of earth alongside
		Land high Bench

Lubs Tp. 15 N. R 13 W

chs. Soil 1st & 3rd rate
Dense sagebrush and shad-
scale undergrowth on 80. chs.

East on random line
bet. Secs. 15 & 22
Va. 18°15' E.
40.00 Set temp 1/4 Sec. cor.
19.78 Int. N & S. line 10 lks. S.
of cor. to Secs. 14, 15, 22 &
23 from which
S. 89°56' W on true line
bet. Secs. 15 & 22
with same va.
3.00 High rocky ridge N & S.
40.00 Set Quartzite 24 x 5 x 8 in
18 in. in ground for 1/4 Sec
cor. marked 1/4 on N. face
raised mound of stone along
side.

of the Salt Lake Meridian

	chns. 64.00	foot of Mtns. Enter rolling bench and dense sage brush & shadscale undergrowth.
	75.25	Wash drns. S. W
	78.28	" " " "
	79.70	The cor. to Secs. 15. 16 21 & 22
		Land Mountainous & Bend Soil 4th & 2nd rate
		High Mountains on 64.00
		Dense sage & shadscale undergrowth on 15.70
		Augmented on 79.70 chs
		North bet. Secs. 15 & 16 Va. 18° 15' E.
	40.00	set Limestone 15" x 8 x 8 in. 10 in. in ground for 1/4 Sec. cor. marked 1/4 on W. face, dug reg. pits and raised

Subs Tp. 10 N. R. 13 W

Chns.	mound of earth alongside
80.00	set Limestone 12 x 12 x 8 in.
	8 in. in ground for cor.
	to Secs. 9. 10. 15 & 16.
	marked with 4 notches on
	Sand 3 on E. edges, dug
	reg. pits and raised
	mound of earth alongside
	Land high Bench
	Soil 1st rate
	Dense sagebrush & shadscale
	undergrowth on 80 chs.
	East on random line
	bet. Secs. 10 & 15
	Va. 18° 10' E.
40.00	set temp. 1/4 Sec. cor.
79.40	Int. N & S. line 60 lks.
	S. of cor. to Secs. 10. 11

of the Salt Lake Meridian

Chos. 14 & 15 found which
S. 89°34' W on true line
bet. Secs. 10 & 15
with same va
5.00 High Ridge N. E & S. W.
16.00 Gulch drns. S. W
23.00 same " " N. "
26.30 " " " S. W
28.00 " " " N. W
35.00 N.E. point of ridge brs. S. W
39.70 Set Limestone 15 X 12 X 8 in.
10 in. in ground, for 1/4 Sec.
Cor. marked 1/4 on N face
raised mound of stone
alongside.
Foot of Mtns. Enter high
Bench & dense undergrowth
79.40 The cor. to Secs. 9, 10, 15 & 16
Land Mountainous Bench
Soil 4th & 5th rate

Subs T 10 N R 13 W

Chus. High Mountains on 39.70 chs
Dense sage brush and shad-
scale undergrowth 39.70
augmented on 79.40 chs
May 8. 1884

North bet. Secs. 9 & 10
Va. 18° 10' E.

40.00 Set Conglomerate stone 16x10x8
in. 10 in. in ground, for
1/4 Sec. cor. marked 1/4 on
W face dug reg. pits
and raised mound of
Earth alongside.

64.00 Leave Bench & dense
undergrowth. Ascend
high Mtns. bear E & W

80.00 Set Granite 20x12x8 in.
15 in. in ground for cor.
to Secs. 3. 4. 9 & 10. marked
with 5 notches on S and 3

of the Salt Lake Meridian

Ch	chns	on E. edges, dug reg. pits and raised mound of earth alongside
		Land Bench and Intus Soil 1st rate
3		Hig Mountains on 16 chs. Dense Sagebrush & shadscale undergrowth on 64 chs. Augmented on 80.00 chs
7		East on random line bet. secs. 3 & 10 Va. 18°10' E
	40.00 80.61	Set temp. 1/4 sec. cor Int. N & S. line 19 lks. N of cor. to secs. 2. 3. 10 & 11 from which N 89°52' W. on true line bet. secs. 3 & 10 with same va

Subs. T 10 N R 13 W

Chos. 12.10	Gulch drus. N.E.
30.00	" " "
32.75	Ravine drus. N.E.
40.30	Set Limestone 16x8x6 in. 10 in. in ground, for 1/4 sec. cor. marked 1/4 on N face, dug. reg. pits and raised mound of earth alongside.
47.50	Top of Ridge S.E & NW
55.00	Gulch drus. S.W
80.61	The cor. to secs. 3. 4. 9 & 10
	Land Mountainous
	Soil 3rd rate
	Scattering Cedars sage and greasewood
	High Mountains on 80.61
	North on a random line bet. secs 3 & 4

of the Salt Lake Meridian

Chns	
	Var. 18° 10' E
40.00	Set temp 1/4 Sec. cor.
78.75	Int N. Boundary of Tp 52 lks. W of cor to Secs. 3. 4. 33 & 34 which is a limestone 6×13×7 ins. above ground properly marked & mound of stone alongside from which I run S. 0° 22' W on true line bet. Secs. 3 & 4 with same va
38.75	Set Limestone 17×8×5 in 12 in. in ground for 1/4 sec. cor. marked 1/4 on W face, raised mound of stone alongside
46.00	Top of Ridge brs. N. W. & S. E.
68.75	Gulch drns. S W
78.75	The cor. to Secs. 3. 4. 9 & 10
	Land Mountainous.
	Soil 2nd rate

Subs. Tp. 10 N R 13 W

Chus. scattering cedars & under-growth
High Mountains on 78.75

From the re established cor. to Secs. 4. 5. 32 & 33 on the South Boundary of the Township I run
North bet. Secs. 32 & 33
Va. 18° 10' E.
Through dense undergrowth

40.00 Set Limestone 12 X 8 X 4 in 8 in. in ground, for 1/4 Sec. cor marked 1/4 on W face, dug reg. pits and raised mound of earth alongside

80.00 Set Limestone 18 X 12 X 6 in 12 in. in ground, for cor. to Secs. 28. 29. 32 & 33 marked

Of the Salt Lake Meridian

Ch	chus	with 1 notch on S and 4 on E. edges. dug reg pits and raised mound of earth alongside.
3		Land gently rolling Soil 1st rate Dense sage brush and shad-scale undergrowth on 80 ch
7		East on a random line bet. Secs. 28 & 33 Va. 18°10' E.
	40.00	Set temp 1/4 Sec. cor
	80.22	Intersect N & S. line 37 lks S. of cor. to Secs. 27. 28. 33 & 34 from which S. 89°44' W. on true line bet. Secs. 28 & 33 with same va

Subs. Tp. 10 N R 13 W

Chns.	
15.30	Gully drus. S.E.
40.11	Set Flint stone 12 x 10 x 6 in. 8 in. in ground, for 1/4 Sec. cor. marked 1/4 on N face, dug reg. pits and raised mound of earth alongside
40.60	Gully drus. S.E.
49.00	" " South
80.22	The cor. to Secs. 28. 29. 32 & 33
	Land level Bench
	Soil 1st rate
	Dense sagebrush and shad-scale undergrowth on 80.22

North bet. Secs. 28 & 29

Va. 18°10' E

33.90	Telegraph line brs. N.W. & S.E.
34.78	Central Pacific R.R. " " " "

of the Salt Lake Meridian

chns.	
35.56	Telegraph line brs. N.W. & S.E.
40.00	set Limestone 10 X 10 X 6 in. 10 in. in ground, for 1/4 Sec. cor. marked 1/4 on W face dug reg. pits and raised mound of earth along side
42.50	Road brs. E & W
53.50	Gully trns. S.E.
80.00	set Limestone 18 X 12 X 6 in. 12 in. in ground, for cor to Secs. 20, 21, 28 & 29 marked with 2 notches on land 1/4 on E. edge dug reg. pits and raised mound of earth along side.

Land gently rolling
Soil 1st rate
Brush sage brush and shadscale
undergrowth on 80. chs.

Lubs. T. 10 N. R. 13 W.

	Chus.	East on a random line bet. Secs. 21 & 28 Va. 18°10' E.
	2.00	Set temp. 1/4 Sec. cor.
	79.35	S. at. N & S. line 60 lks. N. of cor. to Secs. 21. 22. 27 & 28. from which N. 89° 34' W on true line bet Secs. 21 & 28 with Same va.
	16.50	Wash drns. S. W
	3.00	Road brs. N. E & S. W
	39.67	Set cobble stone 12 x 12 x 8 in 8 in. in ground, for 1/4 Sec. cor. marked 1/4 on N face dug reg. pits and raised mound of earth alongside
	79.35	The cor. to Secs. 20. 21. 28 & 29.

Land Bench

of the Salt Lake Meridian

Chus.	Soil 1st rate
	Dense sage brush and shad-scale undergrowth on 79.35 d.
	North bet. Secs. 20 & 21
	Va. 18° 10' E
40.00	Set volcanic rock 18 x 12 x 4 in. 12 in. in ground for 1/4 sec. cor. marked 1/4 on W face dug reg. pits and raised mound of earth alongside.
43.50	Old Indian Antelope corrall brs. S.E. & N.W.
73.50	Same brs. S.E. & N.W.
75.50	Gully drns. S.E.
80.00	Set Limestone 18 x 10 x 10 in 12 in. in ground, for cor to Secs. 16. 17. 20 & 21 marked with 3 notches on

Subs. Tp 10 N. R 13 W

chns. Sand 4 on E. edges, dug
reg. pits and raised
mound of earth along side.
Land level Bench
Soil 1st rate
Dense sage brush and shadscale
undergrowth on 80 chs.

East on random line
bet. Secs. 16 & 21
Va. 18°10' E.
4000 Set temp. 1/4 Sec. cor
79.58 Pnt. N & S. line 33 lks. N
of cor. to Secs. 15.16.21 & 22
from which
N 89°46' W. on true line
bet. Secs. 16 & 21
with same va
15.00 Wash drns. S.W.

Of the Salt Lake Meridian

chns.
39.79 Set Limestone 12x8x6 in
8 in. in ground for 1/4 Sec. cor
marked 1/4 on W face dug
reg. pits and raised mound
of earth alongside
46.00 Wash drns. S.E.
79.58 The cor. to Secs. 16, 17, 20 & 21
Land Bench
Soil 1st rate
Dense sage brush and shad-
scale undergrowth on 79.58

North bet Secs. 16 & 17
Va. 18° 10' E.
24.00 Gully drns. S.E. ascend
rolling Bench
40.00 Set Cobblestone 18x8x6 in.
12 in. in ground for 1/4 Sec.
Cor. marked 1/4 on W face

Subs. T 10 N R 13 W

chus	dug reg. pits and raised mound of earth alongside
46.00	Old Indian Antelope corrale brs. S. E & N. W
55.00	Same brs. S. E. & N. W
80.00	Set charred Cedar post 4 ft. long 4 in square 12 in. in ground for cor. to Secs. 8. 9. 16 & 17. marked w T. 10 N. S 9 on N. E. R 13 W S. 16 on S. E. S. 8 on N. W S. 17 on S. W faces with 4 notches on S and 4 on E Edges. dug reg pits and raised mound of earth around post
	Land Bench
	Soil 1st rate
	Dense sage brush & shadscale undergrowth on 80 chs.

of the Salt Lake Meridian

East on random line
bet. Secs. 9 & 16
Va. 18°10' E.

~~40.00~~ Set temp 1/4 Sec. cor.

79.68 Int. N & S line 21 lks. S. of
cor. to Secs. 9. 10. 15 & 16,
from which
S. 89°51' W on true line
bet. Secs. 9 & 16
with same va.

39.84 Deposited quart of pebbles
at cor. point 12 in. in ground for 1/4 Sec. cor. dug pits
18 X 18 X 12 in. E & W cor. pt.
5 1/2 ft dist raised mound
of earth over same in E pits
drove charred cedar stake
2 ft. long 2 in. sq. 12 in in
ground, marked 1/4 S on
N face.

79.68 The cor. to Secs. 8. 9. 16 & 17

Subs. T. 10 N R 13 W

chus. Land Bench
Soil 1st rate
Dense sage brush & shadscale
undergrowth on 79.68.
May 9. 1884

North bet. Secs. 8 & 9
Va. 18 ft E

40.00 Set Sandstone 30 X 12 X 4 in
22 in. in ground for 1/4 sec
cor. marked 1/4 on W. face
dug reg. pits and raised
mound of earth alongside
77.50 Wash drus. S.E.
80.00 Set Limestone 16 X 12 X 12 in.
10 in. in ground, for cor. to
secs. 4. 5. 8 & 9, marked w
with 5 notches on S and
4 on E. edges, dug reg.
pits & raised mound of earth

of the Salt Lake Mer.

chus.	alongside
	Land rolling Bench
	Soil 1st rate
	Dense sagebrush & shadscale
	undergrowth on 80 chs
	East on a random line
	bet. Secs. 4 & 9
	Va. 18° 10' E.
40.00	Set temp 1/4 Sec. cor
80.00	Int. N & S. line 7 lks. N. of cor
	to Secs. 3. 4. 9 & 10 from which
	N 89° 57' W on true line, bet
	Secs. 4 & 9
	with same va.
8.00	Gulch drns. S W
35.00	Foot of Mtns. S.E. & N.W. Enter Bench
	& Dense undergrowth
40.00	Set Charred Cedar post

Subs. Tp. 10 N R 13 W

Chus. 3 ft. long 3 in. square, 12 in in ground, for 1/4 sec. cor marked 1/4 S on N face, dug reg. pits and raised mound of earth around post

65.00 Gulch drns. S. E.

80.00 The cor. to Secs. 4. 5. 8 & 9

Land Mtns. & Bench

Soil 1st rate

Dense Sagebrush & shadscale undergrowth on 45.00 chs.

High Mountains on 35.00 "

Augmented on 80.00 chs

North on random line bet. Secs. 4 & 5

Va. 18° 10' E.

40.00 Set temp. 1/4 Sec. cor.

79.00 Int N. Bd. of Tp. 13 lks. E. of cor. to Secs. 4. 5. 32 & 33

of the Salt Lake Meridian

	Chus.	which is a limestone 5x10x6 ins above ground, properly marked & mound & pits alongside — from which S. 0° 6' E. on true bet Secs 4 & 5. with same va.
	19.00	Gulch drns. S. E.
	39.00	Set Limestone 12x8x6 in 8. in. in ground for 1/4 Sec. cor. marked 1/4 on W. face dug reg pits raised mound of earth along side
	54.25	Gulch drns. S. E.
	65.25	" " "
?	74.00	" " "
	79.00	The cor. to Secs. 4. 5. 8 & 9 Land mountainous. Soil 1st & 2nd rate Scattering Cedars. Dense Sagebrush & Shadscale undergrowth on 79 chs.

Subs. T. 10 N. R. 13 W.

chns. From the cor. to Secs. 5. 6. 31 & 32 on the South Bd of the Tp. re-established by me during this survey I run
North bet. Secs. 31 & 32
Va. 18° 10' E
Though dense sage brush & shadscale undergrowth
70.00 Set Limestone 18 X 12 X 10 in. 12 in. in ground for 1/4 Sec. cor. marked 1/4 on W face dug pits reg. and raised mound of earth alongside
60.10 Gully drns. S.E.
80.00 Set Limestone 20 X 13 X 5 in. 15 in. in ground, for cor. to Secs. 29. 30. 31 & 32 marked with 4 notch on E and 1/4 on S. edges, dug reg.

of the Salt Lake Meridian

Chns. pits and raised mound of earth alongside.
Land rolling
Soil 1st rate
Dense sagebrush & shadscale undergrowth on 80 chs.

East on random line bet. Secs. 29 & 32
Va. 18°10' E.
40.00 Set temp. 1/4 Sec. cor.
79.88 Set. N & S. line 15 lks. W of cor. to Secs. 28, 29, 32 & 33 from which
N 89°54' W on true line bet. Secs. 29 & 32
with same val
39.94 Set volcanic rock 16x10x8 in. 10 in. in ground, for

Meridian

Subs. Tp. 10 N. R 13 W

ound

Chns. 1/4 Sec. cor. marked 1/4 on N face, dug reg pits and raised mound of earth alongside.

shadscale 77.30 Wash drns. S. E.

80 chs. 79.88 The cor. to Secs. 29, 30 31 & 32

Land Bench

Soil 1st rate

line Dense sagebrush & shadscale undergrowth on 79.88 chs.

10' E.

or.

lks. N

32 & 33

West on a random line bet. Secs. 30 & 31

Va. 18°10' E.

true line

40.00 Set temp 1/4 Sec. cor.

e va 79.58 Int W. Bd. of Tp. 30 lks.

16x10x8 N. of re-established cor. to Secs. 25. 30. 31 & 36.

for

of the Salt Lake Meridian

chs.	
	from which
	N 89° 47' E on true line
	bet. Secs. 30 & 31
	with same va.
5.70	Telegraph line lrs. N.E. & S.W.
6.50	Central Pacific R.R. . . . .
7.50	Telegraph line . . . . .
39.58	Set Flint stone 12 X 10 X 8 in
	8 in. in ground, for 1/4 Sec. cor.
	marked 1/4 on N face, dug
	reg. pits and raised mound
	of earth alongside
47.10	Wash drns. S.E.
69.00	Road lrs. N.E. & S.W
79.58	The cor. to Secs. 29, 30
	31 & 32
	Land Bench
	Soil 1st rate
	Dense sage brush & shadscale
	undergrowth on 79.58

Tuls. Tp. 10 N. R 13 W

Chns.	North bet. Secs. 29 & 30
	Va. 18°10' E.
	Section house (Mattie) brs.
	N. 56°30' E.
	House brs. N 58° E.
	" " 55° E.
4.35	Road brs. N. E. & S. W
11.85	" " E & W
14.30	Telegraph line E & W
14.90	Central Pac. R.R. " "
15.70	Telegraph line " "
4.00	Set Limestone 15 x 8 x 4 in
	10 in. in ground, for 1/4 Sec.
	cor. marked 1/4 on W. face
	dug 8 sq. pits and raised
	mound of earth alongside
8.00	Set Limestone 20 x 13 x 5 in.
	15 in. in ground, for cor. to
	Secs. 19, 20, 29 & 30, marked
	with 2 notches on S and 5 on

of the Salt Lake Meridian

Chns. E. edges, dug reg. pits and raised mound of earth alongside, from which Section house at Mathis brs. S. 27° E.
House brs. S. 29° 30' E.
" " S. 26° E.
Land Bench
Soil 1st rate
Dense sagebrush & shadscale undergrowth on 80 chs.

East on random line bet. Secs. 20 & 29
Va. 18° 10' E.
40.00 Set temp. 1/4 Sec. cor.
80.16 Int N & S. line 14 lks. N of cor to Secs. 20. 21. 28 & 29 from which

Subs T 10 N R 13 W

Chns	N. 89° 54' W on true line bet Secs. 20 & 29 with same va
30.00	Deep wash drns. S.E.
40.08	Set Limestone 16 x 10 x 8 in. 10 in. in ground for 1/4 Sec. cor. marked 1/4 on N face, dug reg. pits and raised mound of earth alongside.
80.16	The cor. to Secs. 19, 20, 29 & 30
	Land Bench
	Soil 1st rate
	Dense sage brush & shad-scale undergrowth on 80.16

West on random line bet. Secs. 19 & 30
Va. 18° 10' E.

of the Salt Lake Meridian

Chs.	
40.00	Set temp 1/4 Sec. cor.
79.15	Int. W. Boundary of Tp. 27 lks. N of cor. to Secs. 19, 24, 25 & 30 re-established by me from which N 89° 48' E on true line bet. Secs. 19 & 30 with same va.
39.19	Set charred cedar post 3 ft. long 3 in. square, 12 in. in ground for 1/4 Sec. cor. marked 1/4 S on N face dug reg. pits and raised mound of earth around post
56.65	Wash drus. S.
62.15	" "
79.19	The cor. to Secs. 19, 20, 29 & 30.

of the Salt Lake Meridian

Chus. Land Bench
Soil 1st rate
Dense sagebrush & shad=
scale undergrowth on 79.69
May 10. 1884

North lat. Secs. 19 & 20
Va. 18° 10' E

40.00 Set Limestone 14 x 12 x 8
in. 10 in. in ground, for
1/4 sec. cor. marked 1/4 on
W face, dug reg. pits &
raised mound of earth
alongside.

80.00 Set Limestone 14 x 12 x
4 in. 10 in. in ground,
for cor. to Secs. 17, 18, 19 &
20, marked with 3 notches
on S and 5 on E. edges,
dug reg pits & raised

of the Salt Lake Meridian

6	chns.	mound of earth along side
		Land level Bench
		Soil 1st rate
		Dense Sagebrush & shad-
3		scale undergrowth on 80ch
		East on random line
		bet Secs. 17 & 20
		Va. 18°10' E.
7	4.00	Set temp 1/4 Sec. cor
	80.30	Int N & S. line at cor.
		to Secs. 16, 17, 20 & 21,
		from which
		West on true line bet
		Secs. 17 & 20
		with same va.
	30.25	Wash drns. S. E.
	40.15	Set Cobble stone 14X12X12
		in. 10 in. in ground for.

Subs. T 1 S N. R 13 W

ridian	chs.	1/4 Sec. cor. marked 1/4 on N face, dug reg. pits & raised mound of earth along side.
long side	42.25	Wash drus. S. E.
h	57.00	" " " "
shad	71.30	" " " "
t on 8 ochs	80.30	The cor to Secs. 17. 18. 19 & 20.
line		Land level Bench Soil 1st rate
8°10' E.		Dense Sage brush & shad-scale underg rowth on 80.30
cor		
t cor.		
,		
bet		West on random line bet. Secs. 18 & 19
ne va		Va. 18°10' E.
4X12X12	40.00	Set temp 1/4 Sec. cor.
for.	78.72	Int W. Bd. of Tp. 19 lks.

of the Salt Lake Meridian

chs.		I. of re-established cor to Secs. 13. 18. 19 & 24, from which S. 89° 52' E on true line bet. Secs. 18 & 19 with same va.
	31.00	Wash drns. S. W
	38.72	set volcanic rock 16x14x8 in. 10 in. in ground, for 1/4 Sec. cor. marked 1/4 on N face, dug reg. pits and raised mound of earth alongside
	58.50	Wash drns. S. W
	70.60	" " "
	78.[illegible]	The cor. to Secs. 17. 18. 19 & 20. Land level Bench Soil 1st rate Dense sagebrush & shad=

Subs T 10 N R 13 W

chs.	Scale undergrowth on 78.12 Chs.
	North bet. Secs. 17 & 18 Va. 18° 10' E.
11.10	Wash drns. S. E.
40.00	Set Limestone 18 X 10 X 6 in. 12 in. in ground, for 1/4 sec. cor. marked 1/4 on W. face, dug reg. pits and raised mound of earth alongside
80.00	Set Limestone 18 X 10 X 8 in. 12 in. in ground for cor to Secs. 7, 8, 17 & 18, marked with 4 notches on S and 5 on E. edges, dug reg. pits and raised mound of earth alongside
	Land level Bench

Of the Salt Lake Meridian

chs.	
	Soil 1st rate
	Dense sage brush & shad-scale undergrowth on 80 chs.
	East on random line bet. Secs. 8 & 17
	Va. 18° 10' E.
40.00	Set temp. 1/4 Sec. cor.
80.42	Int N & S. Line, 15 lks. S. of cor. to Secs. 8, 9, 16 & 17 from which
	S 89° 54' W on true line bet. Secs. 8 & 17
	with same va.
31.40	Gulch trns. S.E.
40.21	Set Limestone 12 x 10 x 6 in. 8 in. in ground for 1/4 Sec. cor. marked 1/4 on N face dug reg pits & raised mound

Subs. T. 10 N R 13 W

chs.	Earth alongside
47.80	Ridge brs. N & S.
80.42	The cor to Secs. 7. 8. 17 & 18
	Land mostly level
	Soil 1st rate
	Dense sage brush & shad-
	scale under growth on 80.42

	West on random line
	bet. Secs. 7 & 18
	Va. 18°10' E.
40.00	Set temp 1/4 Sec. cor.
78.64	Int W. Bd. of Tp. 40 lks.
	S. of re-established cor. to Secs. 7. 12. 13 & 18, from which
	S. 89°43 E. on true line
	bet. Secs. 7 & 18
	with same va

of the Salt Lake Meridian

Chs.	
32.50	Wash drws. S.
39.90	
38.64	Set Cedar post (charred) 3 ft. long 3 in square 12 in. in ground, for 1/4 Sec. cor. marked 1/4 S on N face, dug reg pits and raised mound of earth alongside.
78.64	The cor. to Secs. 7. 8. 17 & 18. Land level Bench Soil 1st rate Dense Sage brush & shad-scale undergrowth on 78.64 chs.

May. 12 1884

North bet. Secs. 7 & 8
Va. 18° 18' E.

15.50	Leave Bench & dense sage

Subs. Tp. 10 N R 13 W

chs. brush & shadscale undergrowth
Enter high Mtns. br. N.W. & S.E.
40.00 Set Limestone 30 x 20 x 6 in
23 in. in ground, for 1/4
sec. cor. marked 1/4 on
W face, dug reg. pits &
raised mound of earth
alongside
45.00 Gulch drains S.W.
61.50
80.00 Set Limestone 30 x 10 x 10 in.
23 in. in ground, for cor.
to secs. 5. 6. 7 & 8 marked
with 5 notches on S & E
edges, dug reg. pits and
raised mound of earth
alongside.
Land Bench & Mountainous
Soil 1st & 3rd rate
Dense sage brush & shadscale
undergrowth on 15.50 chs.
High Mountains on 64.50 chs.
Augmented on 80.00 chs

of the Salt Lake Meridian

Chs	chs.	
		East on random line bet. Secs. 5 & 8
		Va. 18°10' E.
	40.00	Set temp. 1/4 Sec. cor.
38.	79.83	Int. N & S. line 42 lks. N of cor. to Secs. 4, 5, 8 & 9
		from which
		N 89°42' W on true line bet. Secs. 5 & 8
78.		north same va.
	20.00	Leave Bank & underground
		Enter High mountains
	39.91	Set Limestone 12 X 8 X 4 in. 8 in. in ground, for 1/4 Sec. cor. marked 1/4 on N face raised mound of stone alongside
	57.30	Gulch dries. S. W
	69.30	" " " "
	79.83	The cor. to Secs. 5, 6, 7 & 8

Subs. T. 10 N R 13 W

Land Bench & Mountainous
Soil 1st & 3rd rate
Dense Sagebrush & shad-
scale undergrowth on 20.00
High Mountains on 59.83
Augmented on 79.83

West on random line
bet. Secs. 6 & 7
Va. 18° 10' E.
40.00 Set temp 1/4 Sec. cor.
78.52 Int. W. Bd. of Tp. 35 lks.
S. of re-established cor.
to Secs. 1. 6. 7 & 12 from
which
S. 89° 45' E. on true line
bet. Secs. 6 & 7
with same va.
10.25 Gulch Irus. S. W. Leave

of the Salt Lake Meridian

Ch	chs.	Bend & dense undergrowth
		Ascend High Mountains
		br. N. W. & S. E.
	28.00	Pulled drus. S. W
38		Set volcanic rock 12x8x6.
		in. 8 in. in ground for
		1/4 Sec. cor. marked 1/4 on
		N face, raised mound of
		stone along side.
78.	7.50	Pulled drus. S. W
		The cor. to Secs. 5. 6. 7 & 8
		Land mostly mountains
		Soil 3rd rate
		Dense sage brush & shadscale
		undergrowth on 10.25
		High Mountains on 68.27
		Augmented in 78.52
		North on random line
		bet. Secs. 5 & 6

Subs. T. 18 N. R 13 W.

chs	
	Va. 18° 10' E.
40.00	Set temp 1/4 Sec. cor.
79.50	Int N. Boundary of Tp.
	18 lks. W of cor. to Secs.
	5. 6. 31 & 32 } which is a Limestone 4x 8x7 ins. above ground properly marked & mound & pits along side
	from which
	S 0° 8' W on true line
	bet. Secs. 5 & 6
	with same va
39.50	Set Limestone 16x12x10 in.
	10 in. in ground, for 1/4 Sec. cor.
	marked 1/4 on W. face, raised
	mound of stone alongside
47.00	Gulch drns. N. E.
79.50	The cor to Secs. 5. 6. 7 & 8 12
	Land Mountainous
	Soil 3rd rate
	High Mountains on 79.50
	May 13. 1884
Date	

General Description

Ch

The land embraced in this township is mostly level, with some mountain in the N. & N.E. portions. The land for the most part is covered with a growth of shadscale & white sage, affording fine winter range for stock. It is now very extensively used as a winter range for sheep. The Central Pacific Rail Road runs N.E. & S.W. nearly through its centre. Mathews section station is situated in Section 29

38.

78.

Henry Fitzhugh
U.S. Dep. Surveyor

BOOK-A-205

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, October 1 1884.

The foregoing field notes of the survey of the Subdivisions

Township No. 10 North Range No. 13 West.

Executed by Henry Fitzhugh No. 124

Under his contract of the 19. day of March 1884, in the month of May 1884, having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.

Fred Salomon

U. S. Surveyor General for Utah.

Blank

Page

BOOK A-200 1000

388

REPORT: 1885

Filed 188

Examined by John H. Campbell

Transcribed by E. Michaelis

Compared by H. A. Atkinson & E. Michaelis

FIELD NOTES

OF THE SURVEY OF THE

Subdivision lines

OF

Township No 10 North

Range No 16 West

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Henry Fitzhugh

U. S. Deputy Surveyor,

Under his Contract No. 124

Dated March 19th 1884

Survey commenced June 18th 1884

Survey completed " 24 " 1884

BOOK-A-203

Township 10 N. R. 16 W.

6 450	5 434	4 422	3 411	2 400	1
449	448	433	421	410	399
7 447	8 432	9 420	10 409	11 398	12
446	445	431	419	408	397
18 444	17 430	16 418	15 407	14 396	13
443	441	429	417	406	395
19 440	20 428	21 416	22 405	23 394	24
439	438	427	415	405	393
30 437	29 426	28 414	27 404	26 392	25
436	436	425	413	403	391
31 435	32 424	33 412	34 402	35 390	36

Subdivisions 390 N. R. 1 6 W.
S. L. M.

Chs. Before commencing this Survey I took an observation of the Star Polaris on the night of June 17th 1884, and established a meridian in accordance with instructions contained in the manual of of surveys on the following morning I test my instrument & find it correct.

Survey commenced with a Brunt Improved Solar Compass June 18th 1884

From the Cor. to Secs. 1, 2, 35 & 36 which is a Granite 5×9×5 ins above ground properly marked, and mound of stone alongside —

From

North Bet. Secs. 35 & 36

Var. 18° 10' E.

18.00 Gulch drains E.

31.50 " "

40.00 Set Volcanic rock 18×12×10 ins 12 ins in the ground for 1/4 Sec.

Subdivisions T. 10 N.

Chs.	Chs.	Cor. marked 1/4 on W. face & made regulation mound & pits
	57.00	Creek drains E.
	80.00	Set limestone 7 x 9 x 5 ins - 12 ins. in the ground for Cor. to Secs. 25, 26, 35, 36 marked 1 notch on S. & E. edges, and made regulation mound & pits
38.		Land hilly
		Soil 3rd rate
78.0		Some scattering cedars
		Dense sage brush undergrowth on 80.00 Chs
		East on random line
		Bet. Secs. 25 & 36
		Lo 18°10' E.
	4.00	Set temporary 1/4 Sec. Cor.
	80.28	Intersect E. By. of township 30 Sks. N. of Cor. to Secs. 25, 30, 31 & 36. ~~which is~~ re-established by me during this survey
		Thence Iowa

Chs.	
	N. 89° 47' W. on true line
	Bet. Secs. 25 & 36
	With same Va
40.14	Set Granite 20×12×3 ins. 15 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on N. face, and made regulation mound & pits
70.00	Leave flat.
	Enter hills bear N. & S.
80.28	The Cor. to Secs. 25, 26, 35 & 36
	Land flat & hilly
	Soil 1st & 2nd rate
	Dense sage brush undergrowth on 80.28 chs.
	North Bet. Secs. 25 & 26
	Va 18° 10' E.
18.50	Wash drains E.
	Leave hills. Enter bench bears E. & W.
22.00	Road bears E. & W.
40.00	Set Limestone 10×8×6 ins. 7 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on W. face, and made regulation mound & pits.

Subdivisions T. 10 N.

Chs.	
48.25	Old Emigrant Road bears N.E. & S.
61.00	Wash drains E.
69.00	" " "
78.00	" " "
80.00	At Marty 18 x 12 x 7 ins - 12 ins in the ground for Cor. to Secs. 23, 24, 25 & 26, marked 2 notches on S. & 1 notch on E. edges & made regulation Mound & pits
	Sand hilly & brush
	Soil 2nd & 1st rate
	Dense sage brush undergrowth on 80.00 chs.
	East on random line
	Bet. Secs. 24 & 25
	Va 18° 10' E.
40.00	Set Temporary 1/4 Sec. Cor.
80.40	Intersect E. By. of Township 40 Rks. N. of Cor. to Secs. 19, 24, 25 & 30 ~~which is~~ re-established by me during this Survey
	Thence Jim

R. 16 W. - S. L. M.

Chs.	
	N. 89° 43' W. on true line.
	Bet. Secs. 24 & 25
	With same Va
40.20	Set Limestone 15 x 11 x 9 ins - 10 ins in the ground for 1/4 Sec. Cor. marked 1/4 on N. face, and made regulation mound & pits.
58.00	Old Emigrant Road bears N.E. & S.W.
80.40	The Cor. to Secs 23, 24, 25 & 26
	Land bench
	Soil 1st rate
	Dense sage brush undergrowth on 80.40 Chs.
	North Bet. Secs. 23 & 24
	Va 18° 10' E.
12.00	Hollow drains E
18.50	" " S.E.
38.75	Gully drains S.E.
40.00	Set Limestone 17 x 8 x 5 ins - 12 ins in the ground for 1/4 Sec. Cor. marked 1/4 on W. face, and made regulation mound & pits
47.50	Hollow drains S.E.

Subdivisions T. 10 N.

Chs.	
80.00	Set Limestone 22 x 8 x 3 ins - 15 ins. in the ground for Cor. to Secs. 13, 14, 23 & 24, marked 3 notches on S & 1 notch on E. edges, and made regulation Mound & pits
	Land Bench
	Soil 1st rate
	Dense sage brush underground on 80.00 Chs
	East on random line
	Bet. Secs. 13 & 24
	Va 18° 10' E
40.00	Set Temporary 1/4 Sec. Cor.
80.27	Intersect E. By. of Township 28 Chs. N. of Cor. to Secs. 13. 18. 19 & 24 which is re-established by me during this survey
	Thence Town
	N. 89° 48' W. on true line
	Bet. Secs. 13 & 24
	Va, 18° 10' E.

R. 16 W. – S. L. M.

Chs.	
32.75	Old Emigrant Road bears N.E. & S.W.
40.13	Set Martzite 10×10×6 ins – 7 ins in the ground for 1/4 Sec. Cor. marked 1/4 on N. face, and made regulation mound & pits.
47.75	Spring on line
65.25	Wash drains S.E.
80.27	the Cor. to Secs. 13, 14, 23 & 24
	Land bench
	Soil 1st rate
	Dense sage brush undergrowth on 80.27 chs.

North Bet. Secs. 13 & 14
Va 18° 10' E.

40.00	Set Martzite 14×12×4 ins – 10 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on W. face, and made regulation mound & pits
72.50	Wash drains S.E.
	Enter Mountains bear E & W.
	Leave bench & sage brush.
80.00	Set Martzite 48×30×8 ins – 24 ins. in the ground for Cor. to

Subdivisions T. 10 N.

Chs.		Secs. 11, 12, 13 & 14 marked 4 notches on S. & 1 on E. edges and made regulation mound & filled Sand bench & Mountainous Sale 1st & 3rd rate.
38.		Dense sage brush undergrowth on 72.50 Chs. Mountainous on 7.50 Chs. Augmented on 8.00 Chs.
78.0		East on random line Bet. Secs. 12 & 13 Va 18° 10' E.
	40.00	Set Temporary 1/4 Sec. Cor.
	79.40	Intersect E. By. of Township 19 Ms. N. of Cor. to Secs. 7, 12, 13 & 18 which is re-established by me during this survey
		Thence Inn N. 89° 52' W. on true line Bet. Secs. 12 & 13 With same Va
	19.00	Wood road bears N.W. & S.E.

R. 16 W. – S. L. M.

Chs.	
33.30	Wash drains S.E.
39.70	Set Quartzite 16×10×6 ins – 10 ins in the ground for 1/4 Sec. Cor. Marked 1/4 on N. face and made regulation mound & pits.
59.40	Leave bench & sage brush Enter Mountains bear N. & S.
78.00	Quartzite ridge bears N.W. & S.E.
79.41	The Cor. to Secs. 11, 12, 13 & 14 Land bench & Mountains Soil 1st & 3rd rate Dense sage brush under growth on 59.40 chs. Mountainous on 20.01 chs. Augmented on 79.41 chs.
	North Bet. Secs. 11 & 12 Va 18° 10' E.
5.00	Rocky ridge bears N.W. & S.E.
28.50	Leave Mountains Enter bench bears N.W. & S.E. and dense sage brush
40.00	Set Limestone 16×12×8 ins – 10 ins in the ground for 1/4 Sec. Cor.

Subdivisions T. 10 N.

Chs.	
	Marked 1/4 on W. face, and made regulation mound & pits.
60.50	Gulch drains N.E.
68.75	Spring bears. S. 84° 30' E. 38.00 Chs. dist.
72.00	Enter Rose Bud Creek bottom bears. N. W. & S.E.
77.00	Road bears N.W. & S.E.
79.60	Rose Bud Cr. dry bed runs S.E.
80.00	Set limestone 21 x 11 x 10 ins - 15 ins. in the ground for Cor. to Secs. 1, 2, 11 & 12, marked 5 notches on S. & 1 notch on E. edges, and made regulation mound & pits
	Land Mountains & bench
	Soil 3rd & 1st rate
	Dense sage brush undergrowth on 51.50 Chs.
	Mountainous on 28.50 Chs.
	Augmented on 80.00 Chs.

East on random line
Bet. Secs. 1 & 12
Va 18° 10' E.

R. 16 W. – S. L. M.

Chs.	
4.00	Set Temporary 1/4 Sec. Cor.
80.37	Intersect E. Bn. of Township 20 Ns.
	N. of Cor. to Secs. 1, 6, 7, & 12
	Which is re-established
	by me during this Survey,
	Thence Inn
	N. 89°51' W. on true line
	Bet. Secs. 1 & 12
	With same Va.
10.18	Set Limestone 24 x 18 x 10 ins. - 15
	ins. in the ground for 1/4 Sec. Cor.
	marked 1/4 on N. face, and made
	regulation mound & pits.
71.00	Canal runs S.E.
79.50	Enter Rose Bud Creek bottom
	bears N.W. & S.E.
80.37	The Cor. to Secs. 1, 2, 11 & 12
	Sand bench
	Soil 1st rate
	Dense sage brush undergrowth
	on 80.37 Chs.
	North on random line
	Bet. Secs. 1 & 2

Subdivisions T. 10 N.

Chs.	Va 18° 10' E.	Chs.
40.00	Set Temporary 1/4 Sec. Cor.	
80.48	Intersect N. By. of Township 51 Mls. E. of Cor. to Secs. 1, 2, 35 & 36. which is a Limestone 6x13x5 ins. above ground, properly marked and mound of stone alongside	
	Thence Same	
	S. 0° 22' E. on true line	
	Bet. Secs. 1 & 2	
	With same Va	
30.45	High ridge bears N.E. & S.W.	
40.48	Set Limestone 18x12x8 ins - 12 ins in the ground for 1/4 Sec. Cor. marked 1/4 on N. face, and made regulation mound & pits	40.0
75.75	Canal runs S.E.	
78.40	Enter Rose Bud Creek bottom bears N.W. & S.E. & sage brush	67.5
	Leave mountains.	80.0
80.48	The Cor. to Secs. 1, 2, 11 & 12	
	Land mostly mountainous	
	Soil 1st & 5th rate	
	Mountainous on 78.40 chs.	
	Dense sage brush underground	

R. 16 W - S. L. M.

Chs.	on 2.08 Chs.
	Augm entered on 80.48 Chs.
	June 18th 1884
	From the Cor. to Secs. 2, 3. 34 & 35 on the S. By. of Township Which is a Limestone 5x10x8 ins above ground, properly marked, and mound & pits alongside —
	Town
	North Bet. Secs. 34 & 35
	Va 18°10' E.
40.00	Set Charred Cedar Post 3 ft. long 3 ins. Square 12 ins. in the ground for 1/4 Sec. Cor. marked 1/4 S. on W. face and made regulation mound & pits
67.50	Wash drains E.
80.00	Set Limestone 20x10x4 ins - 15 ins in the ground for Cor. to Secs. 26, 27, 34 & 35, marked 1 notch on S. & 2 notches on E. edges, and made regulation mound & pits
	Land bench.

Subdivisions T. 10 N.

Chs.	
	Soil 1st rate Dense Sage brush under growth on 80.00 Chs.
	East on random line Bet. Secs. 26 & 35 Vn 18° 10' E.
40.00	Set Temporary 1/4 Sec. Cor.
79.88	Intersect N & S. line 25 Ms. N. of Cor. to Secs. 25, 26. 35 & 36 Thence Same N. 89° 49' W. on true line Bet. Secs. 26 & 35 With same Va
39.94	Set Limestone 20 x 18 x 10 ins. 15 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on N. face, and made regulation mound & pits
71.75	Prove hills, Wash drains N.E. Enter rolling bench bears N.E. & S.W.
79.88	The Cor. to Secs. 26, 27. 34 & 35 Land bench & hilly Soil 1st & 3rd rate

R. 16 W. - S. L. M.

Chs. Dense sage brush undergrowth on 79.88 Chs.

North Bet. Secs. 26 & 27
Va 18° 10' E.

12.75 Wash drains N.E.
15.25 Old Emigrant road bears N.E. & S.W.
38.00 Wash drains N.E.
40.00 Set Limestone 15×10×8 ins. 10 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on W. face, and made regulation mound & pits
46.00 Road bears N.W. & S.E.
62.00 Wash drains N.E.
70.00 Hollow drains S.E.
80.00 Set Marbrite 16×15×5 ins. 10 ins. in the ground for Cor. to Secs. 22, 23, 26 & 27, marked 2 notches on S. & E. edges, and made regulation mound & pits.
Land rolling bench
Soil 1st rate
Dense sage brush undergrowth on 80.00 Chs

Subdivisions T. 10 N.

Chs.	
	East on random line Bet. Secs. 23 & 26 Va 18°10' E.
40.00	Set Temporary 1/4 Sec. Cor.
80.16	Intersect N. & S. line 40 Chs. N. of Cor. to Secs. 23, 24, 25 & 26. Thence Sun N. 89° 43' W. on true line Bet. Secs. 23 & 26 With same Va
40.08	Set Limestone 12 x 8 x 7 ins - 8 ins in the ground for 1/4 Sec. Cor. marked 1/4 on N. face, and made regulation mound & pits.
48.50	Hollow drains S.E
80.16	The Cor. to Secs. 22, 23, 26 & 27 Land rolling bench Soil 1st rate Dense sage brush undergrowth on 80.16 Chs
	North Bet. Secs. 22 & 23 Va 18°10' E.
40.00	Set Limestone 17 x 10 x 7 ins - 11

BOOK A

R. 1

Chs.	
	ins. Cor. ma mad
80.00	Set S in th 14, 15, on s mad Land roll Soil, 1 Dense
	Eas
40.00	Set
80.00	Intr Secs Thm We
35.50	Gre
40.00	Set in mar reg
80.00	The

R. 16 W – S. L. M

Chs.	ins. in the ground for 1/4 Sec. Cor. marked 1/4 on W. face, and made regulation mound & pits
80.00	Set Limestone 20×6×6 ins – 14 ins. in the ground for Cor. to Secs. 14, 15, 22 & 23, marked 3 notches on S. & 2 on E. edges, and made regulation mound & pits
	Land rolling bench. Soil, 1st rate. Dense sagebrush on 80.00 chs;
	East on random line Bet. Secs. 14 & 23 Va 18° 10' E.
40.00	Set Temporary 1/4 Sec. Cor.
80.00	Intersect N. & S. line at Cor. to Secs. 13, 14, 23 & 24
	Thence Iowa
	West on true line Bet. Secs. 14 & 23 With same Va
35.50	Gulley drains S.E.
40.00	Set Quartzite 15×8×5 ins – 10 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on N. face, and made regulation mound & pits
80.00	The Cor. to Secs. 14, 15, 22 & 23

Subdivisions T. 10 N.

Chs.	
	Land rolling bench Soil 1st rate Dense sage brush undergrowth on 80.00 Chs.
	North Bet. Secs. 14 & 15 Dn 18° 10' E.
40.00	Set Volcanic rock 18×10×10 ins. 12 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on N. face and made regulation mound & pits
55.00	Creek drains N.E.
	Leave rolling bench & sage brush Enter mountains bear N.E. & S.W.
80.00	Set Limestone 16×6×5 ins. - 10 ins. in the ground for Cor. to Secs. 10, 11, 14 & 15, marked 4 notches on S. & 2 on E. edges, and made regulation mound & pits.
	Land rolling & mountains Soil 1st & 4th rate Dense sage brush undergrowth on 55.00 Chs. Mountainous on 25.00 Chs.

R.

Ang

Ed
Cas

40.00	Set
80.00	Int
	to S
	Thu
	S. 8
33.50	Gr
40.00	Set
	ins.
	Cor.
	ma
47.00	Gr
65.00	Ri
65.00	Gr
80.00	The
	Mo

R. 16 W. — S. L. M.

Augmented on 80.00 chs.

East on random line
Bet. Secs. 11. & 14
Va 18° 10' E.

40.00 Set temporary 1/4 Sec. Cor.
80.00 Intersect N. & S. line 30 Rks. S. of cor.
to Secs. 11, 12, 13 & 14
Thence Iron
S. 89° 47' W. on the line
With same Va

33.50 Gulch drains S.
40.00 Set Quartzite 37 x 23 x 7 ins - 24
ins. in the ground for 1/4 Sec.
Cor. marked 1/4 on N. face, and
made regulation mound & pits
47.00 Gulch drains S. E.
65.00 Ridge bears N. & S.
65.00 Gulch drains S.
80.00 The Cor. to Secs. 10, 11, 14 & 15
Land Mountainous
Soil 4th rate rocky
Mountainous on 80.00 chs.

Subdivisions T. 10 N.

Chs.	North Bet. Secs. 10 & 11 Va 18° 10' E.
12.50	High ridge bears E. & W.
19.00	Gulch drains E.
23.00	Head of gulch drains S.E.
30.50	Gulch drains N.E.
40.00	Set Limestone 24 x 12 x 6 ins. 15 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on W. face, and made regulation mound & pits.
40.75	Ridge bears E. & W.
52.50	Gulch drains N.E.
69.50	Gulch drains N.E.
	Leave Mountains. Enter sage brush & rolling bench bears N.W. & S.E.
80.00	Set Limestone 15 x 8 x 5 ins. 10 ins. in the ground for Cor. to Secs. 2. 3. 10 & 11, marked 5 notches on S. & 2 on E. edges. and made regulation mound & pits
	Land Mountainous & bench Soil 4th & 1st rate
	Dense sage brush undergrowth on 10.50 Chs.
	Mountainous on 69.50 Chs.

R. 16

Chs.	Aug
	Eas
40.00	Set
80.10	Inte of Cor Thence N. 89
0.50	Ros
3.75	Roa
16.00	Leav Entr
23.00	Gul
37.00	Gul
40.05	Set ins. Cor. m mad from Acc. 27° E.

R. 16 W. S. L. M.

Chs.	Augmented on 80.00 Chs. June 19. 1884
	East on random line Bet. Secs. 2 & 11 Va 18° 10' E.
40.00	Set Temporary 1/4 Sec. Cor.
80.10	Intersect N. & S. line. 15 Lks. N. of Cor. to Secs. 1, 2. 11 & 12
	Thence Sum
	N. 89° 54' W. on true line With same Va
0.50	Rose Bud Creek dry bed runs S.E.
3.75	Road bears N.W. & S.E.
16.00	Leave bottom
	Enter rolling bench bears N.W. & S.E.
23.00	Gully drains N.E.
37.00	Gully " N.
40.05	Set Limestone 21 x 8 x 7 ins - 15 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on N. face, and made regulation mound & pits from which
	A cedar 10 ins. diam. bears S. 27° E. 96 Lks. dist, marked

Subdivisions T. 10 N.

Chs.	
	1/4 S. B.T.
58.50	Creek drains N.E.
80.10	The Cor. to Secs. 2, 3, 10 & 11
	Land mostly bench
	Soil 1st rate
	Dense sage brush underground
	on 80.10 chs.
	North on random line
	Bet. Secs. 2 & 3
	Va 18° 10' E.
40.00	Set temporary 1/4 Sec. Cor.
80.13	Intersect N. Bdy. of Township 42
	Lks. W. of Cor. to Secs. 2, 3, 34 & 35
	Which is a slate stone 5 x 8 x 4 ins.
	above ground, properly marked, and
	mound of stone alongside —
	Thence Sum
	S. 0° 18' W. on true line
	Bet. Secs. 2 & 3
	Va 18° 10' E.
30.00	Reservoir bears W. about 30 chs.
	dist. Enter bench bears N.W. & S.E.
40.13	Set Volcanic rock 18 x 10 x 8 ins.

R. 16 W. — S. L. M.

Sec.	12 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on W. face, and made regulation mound & pits
51.60	Enter bottom bears N.W. & S.E.
52.00	Rose Bud Creek 6 Lks. wide 4 ins deep runs S.E.
56.00	Road bears N.W. & S.E.
57.00	Leave bottom.
	Enter bench bears N.W. & S.E.
67.50	Gully drains N.E.
80.13	The Cor. to Secs. 2, 3, 10 & 11
	Land hilly & bench
	Soil 2nd & 1st rate
	Dense sap brush under growth on 80.13 chs.

From the Cor. to Secs. 3, 4, 33 & 34 on the S. By. of Township which is a Marty 5 x 10 x 6 ins. above ground, properly marked & mound & pits alongside —

I run

North Bet. Secs. 33 & 34

Subdivisions T. 10 N.

Chs.	
	Va 18° 10' E.
29.00	Old Emigrant road bears N.E. & S.W.
40.00	Set Limestone 20×8×6 ins - 15 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on W. face, and made regulation mound & pits
55.00	Gulch drains E.
80.00	Set Limestone 16×10×8 ins - 10 ins. in the ground for Cor. to Secs. 27, 28, 33 & 34, marked 1 notch on S. & 3 notches on E. edges, and made regulation mound & pits.
	Land bench
	Soil 1st rate
	Dense sage brush undergrowth on 80.00 chs.
	East on random line
	Bet. Secs. 27 & 34
	Va 18° 10' E.
40.00	Set Temporary 1/4 Sec. Cor.
79.90	Intersect N. & S. line To 8 Hs. N.

R. 16 W. - S. L. M.

Chs. of Cor. to Secs. 26, 27, 34 & 35
thence I run
N. 89° 51' W. on true line
Bet. Secs. 27 & 34
With same Va
29.75 Old Emigrant road bears N.E. & S.W.
39.95 Set Sandstone 14 x 10 x 10 ins - 10 ins.
in the ground for 1/4 Sec. Cor.
marked 1/4 on N. face, and made
regulation mound & pits.
A cedar 16 ins. diam. bears. S. 30½° E.
140 lks. dist
A cedar 8 ins. diam. bears. N. 14½°
W. 30 lks. dist.
both marked 1/4 S. B. T.
79.90 The Cor. to Secs. 27, 28, 33 & 34
Sand bench
Soil 1st rate
Some scattering cedars
Dense sap brush undergrowth
on 79.90 chs.

North Bet. Secs. 27 & 28
Va 18° 10' E.

Subdivisions T. 10 N.

Chs.	
3.50	Wash drains E.
16.00	" " "
28.00	" " "
38.00	" " S.E.
40.00	Set Granite 12×8×7 ins - 8 ins in the ground for 1/4 Sec. Cor. marked 1/4 on W. face, and made regulation mound & pits
62.00	Wash drains E.
77.00	Hollow drains S.E.
80.00	Set Limestone 24×7×6 ins - 15 ins in the ground for Cor. to Secs. 21, 22, 27 & 28, marked 2 notches on S. & 3 on E. edges, and made regulation mound & pits
	Land bench
	Soil 1st rate
	Dense sage brush undergrowth on 80.00 chs.
	East on random line
	Bet. Secs. 22 & 27
	Vn 18° 10' E.
40.00	Set Temporary 1/4 Sec. Cor.

BOOK

R.

Chs.	
79.73	Int
	Cor.
	Thu
	N. d
17.50	Ho
39.86	Se
	in
	ma
	ng
41.00	Hol
60.50	Ra
79.73	The
	Ja
	S
	Dun
	on
	Nor
9.00	Ra
33.00	W
40.00	Set

R. 16 W – S. L. M.

Chs.	
79.73	Intersect N. & S. line 20 Mls. N. of Cor. to Secs. 22, 23, 27 & 28
	Thence Same
	N. 89°51' W. on true line
	Bet. Secs. 22 & 27
	With same Va
17.50	Hollow drains S.E.
39.86	Set Limestone 13×10×4 ins – 8 ins – in the ground for 1/4 Sec. Cor. marked 1/4 on N. face, and made regulation mound & pits.
41.00	Hollow drains S.E.
60.50	Road bears N.W. & S.E.
79.73	The Cor. to Secs. 21, 22, 27 & 28
	Found brush
	Soil 1st rate
	Dense sage brush sandy growth on 79.73 Chs.
	North Bet. Secs. 21 & 22
	Va 18°10' E.
9.00	Road bears E. & W.
33.00	Wash drains S.E.
40.00	Set Limestone 16×12×10 ins – 10

Subdivisions T. 10 N.

Chs.	
	ins. in the ground for 1/4 Sec. Cor. marked 1/4 on W. face, and made regulation mound & pits.
	Leave bench & sage brush
	Enter mountains bear N.W. & S.E.
73.00	Ridge bears N.W. & S.E.
80.00	Set Limestone 20x6x6 ins - 15 ins in the ground for Cor. to Secs. 15, 16, 21 & 22, marked 1/4 on W. face and made regulation mound & pits
	Land bench & mountains
	Soil 1st & 3rd rate
	Dense shadscale & sage brush
	undergrowth on 40.00 chs.
	mountainous on 40.00
	Augmented on 80.00 chs.
	East on random line
	Bet. Secs. 15 & 22.
	Va 18°10' E.
40.00	Set Temporary 1/4 Sec. Cor.
79.90	Intersect N & S. line 16 Hks. N. of Cor. to Secs. 14, 15, 22 & 23

R. 16 W – S. L. M.

Chs.	
	Thence Imm
	N. 89° 53' W. on true line
	Bet. Secs. 15 & 22
	With same Va
39.95	Set Limestone 16×12×4 ins – 10 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on N. face, and made regulation mound & pits
64.90	Floor bench & sage brush
	Center mountains bear N.W. & S.E.
79.90	The Cor. to Secs. 15, 16, 21 & 22
	Sand bench & mountains
	Soil 1st & 4th rate
	Dense sage brush & shadscale undergrowth on 64.90 Chs.
	mountainous on 15.00 "
	Augmented on 79.90 Chs.
	North Bet. Secs. 15 & 16
	Va 18° 10' E.
7.50	Gulch drains N.E.
34.00	Center flat bears E. & W. & Sage brush
40.00	Set Slate 36×12×8 ins – 24 ins

Subdivisions T. 10 N.

Chs.	
	in the ground for 1/4 Sec. Cor.
	marked 1/4 on W. face, and
	made regulation mound & pits
77.50	Wash Arains S.E.
80.00	Set Limestone 20×12×10 ins-15
	ins. in the ground for Cor. to Secs.
	9. 10, 15 & 16, marked 4 notches
	on S. & 3 on E. edges, and
	made regulation mound & pits
	Land mountainous & flat
	Soil 1st & 4th rate
	Dense sage brush undergrowth
	on 46.00 Chs.
	Mountainous on 34.00 Chs.
	Augmented on 80.00 Chs. June 20th 1884
	East on random line
	Bet. Secs 10 & 15
	Va 18°10' E.
40.00	Set Temporary 1/4 Sec. Cor.
79.76	Intersect N. & S. line 30 Rks. N. of
	Cor. to Secs. 10, 11, 14 & 15
	Thence Same
	N. 89°47' W. on true line
	Bet. Secs. 10 & 15

BOOK-A

R.

Chs.	
	Wit
9.00	Rid
19.00	Gri
26.00	"
39.88	Set
	the
	ed
	Ref
56.50	Cont
	Au
79.76	The
	Den
	on
	Mo
	Au
	No
6.50	Wa
	Gr
	Ju
39.00	Ri

R. 16 W. — S. L. M.

Chs.	
	With same Va
9.00	Ridge bears N.W. & S.E.
19.00	Gulch drains S.
26.00	" " "
39.88	Set Slate 12×10×6 ins - 8 ins - in the ground for 1/4 Sec. Cor. marked 1/4 on R. face, and made regulation mound & pits
56.50	Center flat bears N.W. & S.E. & dense sage brush
79.76	The Cor. to Secs. 9. 10. 15 & 16 Sand mountainous & flat Soil 1st & 4th rate Dense sage brush undergrowth on 23.26 chs. Mountainous on 56.50 chs. Aug. marked on 79.76 chs.
	North Bet. Secs. 9 & 10 Va 18° 10' E.
6.50	Wash drains S.E. Ground mountains bear N.W. & S.E. Dense sage brush
39.00	Ridge bears N.W. & S.E.

Subdivisions T. 10 N.

Chs.	
40.00	Set Slate 25×20×12 ins - 15 in in the ground for 1/4 Sec. Cor. marked 1/4 on W. face and made regulation mound & pits
73.00	Gulch drains S.E.
80.00	Set Limestone 16×12×8 ins. 10 ins. in the ground for Cor. to Secs. 3, 4, 9 & 10, marked 5 notches on S. & 3 on E. edges, and made regulation mound & pits
	Land mountainous & flat
	Soil 4th & 1st rate
	Dense sage brush underground on 6.50 Chs.
	Mountainous on 73.50 Chs.
	Augmented on 80.00 Chs.
	East on random line
	Bet. Secs. 3 & 10
	Va 18° 10' E.
40.00	Set Temporary 1/4 Sec. Cor.
79.83	Intersect N & S. line 19 8 Ks. S. of Cor. to Secs. 2, 3, 10 & 11
	Thence Dom

BOOK-

R. 4

Chs.	
	S. 89
10.50	Was
39.91	Set
	in th
	mark
	regul
57.00	Ent
	Lan
79.83	The
	Lan
	S
	Dense
	on 5
	Mon
	Aug
	Nort
40.00	Set
80.41	Inter
	28 8 K
	& 34

R. 14 W. — S. L. M.

Chs.	S. 89° 52' W. on true line
	Bet. Secs. 3 & 10
	With same Va
10.50	Wash drain N.
39.91	Set Limestone 12 x 12 x 5 ins - 8 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on N. face, and made regulation mound & pits.
57.00	Enter Mountains bear N.W. & S.E. Leave bench & sage brush
79.83	The Cor. to Secs. 3, 4, 9 & 10 Land bench & Mountains Soil 1st & 4th rate
	Dense sage brush undergrowth on 57.00 Chs.
	Mountainous on 22.83 Chs.
	Augmented on 79.83 Chs.
	North on random line Bet. Secs. 3 & 4 Va 18° 10' E.
40.00	Set Temporary 1/4 Sec. Cor.
80.41	Intersect North By. of Township 28 Rks. E. of Cor. to Secs. 3, 4, 33 & 34 which is a Limestone

Subdivisions T. 10 N.

Chs.	
	5×8×6 ins. above ground, properly marked and mound & pits alongside.
	Thence I run
	S. 0° 12' E. on true line
	Bet. Secs. 3 & 4
	Va 18° 10' E.
29.00	Road in hollow bears N.W. & S.E.
	Hollow drains S.E.
29.50	Rose Bud Creek 78 lks. wide 12 ins. deep runs S.E. in same Hollow
40.41	Set Limestone 24, × 12 × 6 ins - 18 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on It. face, and made regulation mound & pits
42.40	Ridge bears N.W. & S.E.
77.00	Gulch drains S.E.
80.41	The Cor. to Secs. 3, 4, 9 & 10
	Land Mountainous
	Soil 3rd & 4th rate
	Mountainous on 80.41 chs.

BOOK-A

R. 16 [illegible]

Chs.	
	From [illegible]
	32 & 3[illegible]
	of [illegible]
	Martzite
	marked [illegible]
	I [illegible]
	Nor[illegible]
39.50	Gully
40.00	Set [illegible]
	15 ins. [illegible]
	Sec. Co[illegible]
	and [illegible]
	& pits.
57.50	Gully
63.00	"
80.00	Set [illegible]
	ins. in [illegible]
	Secs. [illegible]
	Notch [illegible]
	E. edge [illegible]
	mounta[illegible]
	La[illegible]
	Soil [illegible]
	Dens[illegible]

BOOK-A-203

424

R. 16 W. — S. L. M.

Chs. From the Cor. to Secs. 4. 5. 32 & 33 on the South By. of Township which is a Martzite 5 x 8 x 6 ins. above ground, properly marked & mound & pits alongside — I run

North Bet. Secs. 32 & 33
Va 18° 10' E.

39.50 Gully drains N.E.

40.00 Set Sandstone 20 x 18 x 12 ins. 15 ins. in the ground for 1/4 Sec. Cor. Marked 1/4 on W. face and made regulation mound & pits.

57.50 Gully drains S.E.

63.00 " "

80.00 Set Slate 18 x 6 x 5 ins - 12 ins. in the ground for Cor. to Secs. 28, 29. 32 & 33. marked 1 Notch on S & 4 notches on E. edges and made regulation mound & pits.

Land rolling
Soil 1st rate
Dense Sage brush & shadscale

Subdivisions T. 10 N.

Chs.	
	undergrowth on 8.00 Chs.
	East on random line Bet. Secs. 28 & 33 Va 18° 10' E.
4.00	Set Temporary ¼ Sec. Cor.
8.00	Intersect N. & S. line 28 Chs. N. of Cor. to Secs. 27. 28. 33 & 34 Thence I run N. 89° 48' W. on true line Bet. Secs. 28 & 33 With same Va
4.00	Set Limestone 14 x 8 x 6 ins. 10 ins. in the ground for ¼ Sec. Cor. marked ¼ on N. face, and made regulation Mound & pits
8.00	The Cor. to Secs. 28, 29. 32 & 33 Land rolling Soil 1st rate Dense Sage brush & shadscale undergrowth on 8.00 Chs.

R. 16

Chs.	North
4.00	Set Sl ins. in Sec. Cor. and N Mound
7.00	Wash Ascend Leave
8.00	Set Im ins. in Secs. 2 notch and & pits Lan Soil Dense undergr Mount Ang n

R. 16 W. — S. O. M.

Chs.	North Bet. Secs. 28 & 29 Va 18° 10' E.
4.00	Set Slate 14 x 12 x 5 ins - 10 ins. in the ground for 1/4 Sec. Cor. Marked 1/4 on W. face and made regulation mound & pits.
7.00	Wash Arains S.E. Ascend Mountains bear N.W. & S.E. Leave Sage brush & shadscale
8.00	Set Martzite 20 x 16 x 10 ins - 15 ins. in the ground for Cor. to Secs. 20, 21, 28 & 29, marked 2 notches on S. & 4 on E. edges and made regulation mound & pits
	Land rolling & mountains Soil 1st & 3rd rate
	Dense Sage brush & shadscale
	Underwrowth on 7.00 Chs.
	Mountainous on 10.00 "
	Augmented on 8.00 "

Subdivisions T. 10 N.

Chs.	
	East on random line Bet. Secs. 21 & 28 Va 18° 10' E.
40.00	Set Temporary 1/4 Sec. Cor.
80.31	Intersect N & S line 43 Rks. S. of Cor. to Secs. 21, 22, 27 & 28 Thence I run S. 89° 42' W on true line Bet. Secs. 21 & 28 Va 18° 10' E
5.50	Deep hollow drains S.E.
40.15	Set Limestone 15 x 11 x 6 ins. 10 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on N. face and made regulation Mound & pits
67.50	Enter Mountains bear N.W. & S.E. Cover sage brush & shadscale
75.00	Ridge bears N.W. & S.E.
80.31	The Cor. to Secs. 20, 21, 28 & 29 Land bench & mountains Soil 1st & 3rd rate Dense sage brush & shadscale underground on 67.50 Chs. Mountainous on 12.81 " Augmented on 80.31 "

R. 16

Chs.	North
5.00	Ridge
12.50	Ravi
24.00	Ridge Cabin
32.00	Road Greek
40.00	Set ins. in Cor. Ma made No sinti
46.50	Hollow
51.50	Shaft.
60.00	Ridge
63.50	Ravine
80.00	On Set Lim ins. in Secs. 16 Notch & Mad Lan

BOOK-A-203

R. 16 W. - S. L. M.

Chs.	North Bet. Secs. 20 & 21 Va 18° 10' E.
5.00	Ridge bears N.W. & S.E.
12.50	Ravine drains S.E.
24.00	Ridge bears N.W. & S.E.
	Cabin bears N. 70° 30' E.
	" " N. 23° 45' E.
32.00	Road in gulch bears N.W. & S.E.
	Gulch drains S.E.
40.00	Set Limestone 18 x 12 x 5 ins. - 12 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on W. face, and made regulation Mound & pits
	No suitable trees for marking
46.50	Hollow drains S.E.
51.50	Shaft. 2.50 Chs. East
60.00	Ridge bears N.E. & S.W.
63.50	Ravine drains S.W.
80.00	On ridge bears N.W. & S.E.
	Set Limestone 14 x 10 x 6 ins. - 10 ins. in the ground for Cor. to Secs. 16, 17, 20 & 21, marked 3 notches on S. & 4 on E. edges & made regulation Mound & pits
	Land Mountainous -

Subdivisions T. 10 N

Chs.	
	Soil 4th rate rocky
	Few scattering cedars.
	Mountainous on 80.00 Chs.
	East on random line
	Bet. Secs. 16 & 21
	Va 18° 10' E.
40.00	Set Temporary 1/4 Sec. Cor.
79.41	Intersect N & S. line 23 Hks. N.
	of Cor. to Secs. 15, 16, 21 & 22
	Thence Same
	N. 89° 50' W. on true line
	Bet. Secs. 16 & 21
	With same Va
9.00	Gulley drains N.
39.70	Set Limestone 19 x 7 x 4 ins - 13 ins.
	in the ground for 1/4 Sec. Cor.
	marked 1/4 on N. face, and
	made regulation mound & pits
	from which
	A cedar 7 ins. diam. bears S. 30° E.
	82 Hks. dist. marked 1/4 S. B. L.
64.50	Ridge bears N.W. & S.E.
73.00	Gulch drains S.E.
77.00	Ridge bears N.E. & S.W.

BOOK-A-2

R. 1

Chs.	
79.41	The Co
	Fau
	So
	Few
	Mount
	North
0.00	Cabin
	Shaft
	32 C
	Shaf
	33 Ch
14.00	Shaf
24.00	Gulc
40.00	Set S
	in th
	Marke
	regul
71.50	Ridge
80.00	Set S
	ins.
	Secs.

R. 16 W. - S. L. M.

Chs.	
79.41	The Cor. to Secs. 16, 17, 20 & 21
	Land Mountainous.
	Soil 4th rate
	Few scattering Cedars
	Mountainous on 79.41 Chs.
	North Bet. Secs. 16 & 17
	Va 18° 10' E.
0.00	Cabin bears S. 25° E.
	" " S. 14° E.
	Shaft bears S. 18° 30' E. about 32 Chs. dist
	Shaft bears S. 9° E. about 33 Chs. dist
14.00	Shaft bears E. 10 Chs. dist.
24.00	Gulch drains E.
40.00	Set Slate 22 x 10 x 4 ins - 15 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on W. face, and made regulation mound & pits
71.50	Ridge bears N.E. & S.W.
80.00	Set Limestone 14 x 12 x 4 ins - 10 ins. in the ground for Cor. to Secs. 8, 9, 16 & 17, marked 4

Subdivisions T. 10 N.

Chs.	
	Notches on S. & E. edges and made regulation mound & pits
	Land mountainous
	Sixe 3rd rate
	Mountainous on 80.00 Chs.
	June 21st 1884
	East on random line
	Bet. Secs. 9 & 16
	Va 18° 10' E.
40.00	Set Temporary 1/4 Sec. Cor.
80.30	Intersect N. & S. line 25 Hs. N. of Cor. to Secs. 9. 10. 15 & 16
	Thence Down
	N. 89° 49' W. on true line
	Bet. Secs. 9 & 16
	Va 18° 10' E.
32.50	Wash drains S. E.
40.15	At foot of mountains
	bear N. W. & S. E.
	Leave Sage brush & shadscale
	Set Quartz 20 x 12 x 10 ins - 15 ins in the ground for 1/4 Sec. Cor. marked 1/4 on N. face, and made regulation mound & pits

R. 16

Chs.	
80.30	The Cor.
	Land
	Soi
	Dense
	underg
	Mount
	Augm
	North
4.00	Creek
40.00	Set Co
	ins.
	Cor. M
	made
80.00	Set Sa
	ins.
	Secs. 4
	on S.
	made
	La
	&
	Mou

R. 16 W - S. L. M.

Chs.
80.30 The Cor. to Secs. 8, 9, 16 & 17.
Land Mountainous & flat.
Soil 4th & 1st rate
Dense Sage brush & shadscale
undergrowth on 40.15 chs.
Mountainous on 40.15 "
Augmented on 80.30 "

North Bet. Secs. 8 & 9.
Va 18° 10' E.
4.00 Creek drains S.E.
40.00 Set Conglomerate 12 x 6 x 5 ins - 8
ins. in the ground for 1/4 Sec.
Cor. marked 1/4 on W. face, and
made regulation Mound & pits
80.00 Set Sandstone 42 x 18 x 10 ins - 30
ins. in the ground for Cor. to
Secs. 4, 5, 8 & 9, marked 5 notches
on S. & 4 on E. edges, and
made regulation Mound & pits
Land Mountainous
Soil 3rd rate
Mountainous on 80.00 chs

Subdivisions T. 10 N.

Chs.	East on random line
	Bet. Secs. 4 & 9
	Va 18° 10' E.
40.00	Set Temporary 1/4 Sec. Cor.
79.60	Intersect N & S. line 10 Rks. N.
	of Cor. to Secs. 3, 4, 9 & 10
	Thence I run
	N. 89° 56' W. on true line
	Bet. Secs 4 & 9.
	With same Va
38.50	Ridge bears N.W. & S.E.
39.80	Set Volcanic Stone 12 x 8 x 7 ins. 8
	ins. in the ground for 1/4 Sec. Cor
	Marked 1/4 on N. face, and made
	regulation Mound & pits
48.50	Gulch drains N.W.
64.50	" "
70.00	Ridge bears N.W. & S.E.
79.60	The Cor. to Secs. 4, 5, 8 & 9
	Land Mountainous
	Soil 4th rate
	Mountainous on 79.60 chs

R. 14 E.

Chs.	North
40.00	Set T
80.62	Intersec
	29 Rks
	& 33,
	ins above
	Thence
	S. 0°
	Secs. 4 & 5
	W
40.62	Set
	in the
	Marked
	regula
45.50	Gulch
56.60	"
80.62	The
	Land
	So
	Mount

R. 14 W. — S. L. M.

Chs. North on random line
Bet. Secs. 4 & 5
Va 18° 10' E.

40.00 Set Temporary 1/4 Sec. Cor.
80.62 Intersect N. By. of Township
29 Rks. W. of Cor. to Secs. 4, 5, 32
& 33, which is a Limestone 5x10x4
ins above ground, properly marked and
stone mound alongside
Thence I run
S. 0° 12' W. on true line bet.
Secs. 4 & 5
With same Va

40.62 Set Limestone 13x9x5 ins - 8 ins.
in the ground for 1/4 Sec. Cor.
marked 1/4 on W. face, and made
regulation mound & pits.
45.50 Gulch drains NE
56.60 " " NE
80.62 The Cor. to Secs. 4, 5, 8 & 9.
Sand mound ainons
Soil 3rd rate
Mountainous on 80.62 Chs.

Subdivisions T. 10 N.

Chs.	
	From the Cor. to Secs. 5, 6, 31 & 32 on the S. Bry. of Township which is a Quartz 7×9×6 ins, above ground, properly marked and mound of stone alongside —
	I run
	North Bet. Secs. 31 & 32 Va 18° 10' E.
00.25	Road from Terrace to Ground Creek in hollow drains S.E.
38.00	Wash drains N.E.
40.00	Set Granite 18×8×6 ins - 12 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on W. face and made regulation mound & pits
80.00	Set Granite 30×12×6 ins. 20 ins in the ground for Cor. to Secs. 29, 30, 31 & 32, marked 1 notch on S. & 5 notches on E. edges, and made regulation mound & pits.
	Land rolling
	Soil 1st rate
	Dense sage brush undergrowth on 80.00 chs.

R. 16

Chs.	
	East Be
40.00	Set Gr
80.00	Intersect of Cor. Thence N. 89° B
17.00	Grea
40.00	Set G in th marke regula
80.00	The C La S Few S Dense under
	Wes

R. 16 W - S. L. M

Chs. East on random line
Bet. Secs. 29 & 32
Va 18° 10' E.

4.00 Set Temporary 1/4 Sec. Cor.
80.00 Intersect N. & S. line 32 Rds. N.
of Cor. to Secs. 28, 29, 32 & 33
Thence Iron
N. 89° 46' W. on true line
Bet. Secs. 29 & 32
Va 18° 10' E.

17.00 Grassy drains S. E.
40.00 Set Granite 16 x 7 x 5 ins - 10 ins.
in the ground for 1/4 Sec. Cor.
marked 1/4 on N. face and made
regulation Mound & pits.
80.00 The Cor. to Secs. 29, 30, 31 & 32
Land rolling
Soil 1st rate
Few scattering cedars
Dense sage brush & shadscale
undergrowth on 80.00 Chs.

West on random line
Bet. Secs. 30 & 31

Subdivisions T. 10 N

Chs.	Va 18° 15' E.
40.00	Set Temporary 1/4 Sec. Cor.
78.50	Intersect W. Bry. of Township 38 Rks. N. of Cor. to Secs. 25. 30, 31 & 36 which is a Granite 7 x 13 x 5 ins. above ground, properly marked and mound & pits alongside
	Thence from N. 89° 44' E. on true line Bet. Secs. 30 & 31 With same Va
38.50	Set Granite 12 x 9 x 6 ins - 8 ins in the ground for 1/4 Sec. Cor. marked 1/4 on W. face, and made regulation mound & pits
78.50	The Cor. to Secs. 29. 30, 31 & 32 Land rolling Soil 1st rate Dense sage brush undergrowth on 78.50 Chs.
	North Bet. Secs. 29 & 30 Va 18° 10' E.
22.10	Hollow drains E.
25.65	Old road bears N.W. & S.E.

BOOK-A-2

R. 16

Chs.	
40.00	Set Gr in the marked regula
80.00	Set Sim in the 19. 20, on S. made
	Lan Dense on 80
	East
40.00	Set T
79.68	Intrese of Cor. Thence N. 89°

R. 16 W. S. L. M.

Chs.
4.00 Set Granite 15×8×6 ins - 10 ins in the ground for 1/4 Sec. Cor. Marked 1/4 on W. face, and made regulation mound & pits.

8.00 Set Limestone 18×10×10 ins - 12 ins. in the ground for Cor. to Secs. 19, 20, 29 & 30, marked 2 notches on S. & 5 on E. edges and made regulation mound & pits
Land rolling. Soil 1st rate
Dense sage brush undergrowth on 80.00 Chs.

East on random line
Bet. Secs. 20 & 29
Va 18° 10' E.

4.00 Set Temporary 1/4 Sec. Cor.
79.68 Intersect N. & S. line 33 Rks. N. of Cor. to Secs. 20, 21, 28 & 29
Thence I run
N. 89° 46' W. on true line
Bet. Secs. 20 & 29
With same Va

Subdivisions T. 10 N.

Chs.	
12.00	Hollow drains S.E.
39.84	Set Limestone 16×8×5 ins - 10 ins. in the ground for 1/4 Sec Cor. marked 1/4 on N. face and made regulation mound & pits.
52.50	Ridge bears N & S
60.00	Enter rolling bench bears N & and dense sage brush
79.68	The Cor. to Secs. 19. 20, 29 & 30 Land Mountainous & rolling Soil 4th & 1st rate
	Dense sage brush underground on 19.68 Chs.
	Mountainous on 60.00 Chs.
	Augmented on 79.68 Chs
	West on random line Bet. Secs. 19 & 30 Va 18° 10' E.
40.00	Set Temporary 1/4 Sec. Cor.
78.00	Intersect It. By. of Township 16 Rks. S. of Cor. to Secs. 19. 24 25 & 30 which is a Black

BOOK-A-

R. 16

Chs.	
	Flint 5×7× marked &
	Thence S. 89°
	B
20.00	Leave Enter sage
38.00	Set Li in the marke regular
78.00	The Co Land Soil Dense on 58 Mount Augm
	North

BOOK-A-203

R. 16 W - S. L. M

Chs. Flint 5x7x6 ins. above ground, properly marked & mound of stone along side
Thence I. Mn
S. 89° 53' E. on true line
Bet. Secs. 19 & 30
With same Va

20.00 Leave mountains.
Enter rolling bench & dense sage brush

38.00 Set Limestone 18x10x7 ins - 12 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on N. face, and made regulation mound & pits.

78.00 The Cor. to Secs. 19. 20. 29 & 30
Land rolling & Mountainous
Soil 1st & 3rd rate
Dense sage brush underground on 58.00 chs.
Mountainous on 20.00 chs.
Augmented on 78.00 chs
June 23d 1884

North Bet. Secs. 19 & 20
Va 18° 10' E.

Subdivisions T. 10 N.

Chs.	
16.40	Wash drains S.E.
40.00	Set Granite 12×6×6 ins - 8 in in the ground for 1/4 Sec. Cor. Marked 1/4 on W. face, and made regulation Mound & pits.
72.75	Gully drains S.E.
80.00	Set Marty 30×16×12 ins - 20 ins. in the ground for Cor. to Secs. 17, 18, 19 & 20, marked 3 notches on S. & 5 on E. edges and made regulation Mound & pits
	Land rolling
	Soil 1st rate
	Dense sage brush undergrowth on 80.00 Chs
	East on random line
	Bet. Secs. 17 & 20
	Va 18° 10' E.
40.00	Set Temporary 1/4 Sec. Cor.
80.15	Intersect N. & S. line 29 8 Ks N. of Cor. to Secs. 16. 17. 20 & 21
	Thence I run -

BOOK-A-2

R. 16

Chs.	
	N. 89° 4
17.50	Ridge
23.50	Gulch
30.00	"
38.00	"
40.07	Set Gr ins. in t marked regular
65.00	Hollow Leave & rolli
80.15	The Co Land Soi
	Dense on 15. Mound Augm
	West

R. 16 W. - S. L. M.

Chs.	
	N. 89° 48' W. on the line
	Bet. Secs. 17 & 20
	With same Cor.
17.50	Ridge bears N.W. & S.E.
23.50	Gulch drains S.
30.00	" " S.E.
38.00	" " S.W.
40.07	Set Limestone 12×8×6 ins. - 8 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on N. face, and made regulation mound & pits.
65.00	Hollow drains S.
	Leave mountains - Enter sage brush & rolling bench
80.15	The Cor. to Secs. 17. 18. 19 & 20
	Land mountainous & rolling
	Soil 1st & 4th rate
	Dense sage brush underground on 15.15 Chs.
	Mountainous on 65.00 Chs.
	Augmented on 80.15 Chs.

West on random line

Subdivisions T. 10 N.

Chs.	
	Bet. Secs. 18 & 19
	Va 18°10' E.
40.00	Set Temporary 1/4 Sec. Cor.
78.20	Intersect W. By. of Township
	48 Sks. N. of Cor. to Secs. 13. 18. 19
	& 24 which is a Limestone 6x12x
	ins. above ground, properly marked
	& mound of stone along side
	Thence [illegible]
	N. 87°40' E. on true line
	Bet. Secs. 18 & 19
	With same Va
35.00	Leave Mountains bear N & S
	Enter rolling brush & sage brush
38.20	Set Limestone 17x12x8 ins. 13
	ins. in the ground for 1/4 Sec.
	Cor. marked 1/4 on N. face, and
	made regulation mound & pits.
56.00	Gulch drains S.E.
65.00	" " S.E.
78.20	The Cor. to Secs. 17, 18, 19 & 20
	Land Mountainous & rolling
	Soil 4th & 1st rate
	Dense sage brush undergrowth
	on 43.20 Chs.

BOOK-A-20

R. 16

Chs.	
	Mounta
	Augmen
	North
27.00	Gulch
37.00	"
40.00	Set Sa
	in the
	marke
	regula
52.85	Road
	Hollow
80.00	Set
	ins.
	Secs.
	on S.
	made
	L
	S
	Dense
	on 80.

R. 16 W. S. L. M.

Chs. Mountainous on 35.00 Chs.
Augmented on 78.20 chs.

North Bet. Secs. 17 & 18
Va 18° 10' E.

27.00 Gulch drains E.
37.00 " " S.E.
40.00 Set Sandstone 12 x 8 x 7 ins. - 8 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on W. face, and made regulation mound & pits.
52.85 Road in hollow bears N.W. & S.E.
Hollow drains S.E.
80.00 Set Granite 20 x 14 x 12 ins. - 15 ins. in the ground for Cor. to Secs. 7, 8, 17 & 18, marked 4 notches on S. & 5 on E. edges, and made regulation mound & pits
Land rolling
Soil 1st rate
Dense sage brush undergrowth on 80.00 chs.

Subdivisions T. 10 N.

Chs.	
	East on random line
	Bet. Secs. 8 & 17
	Va 18°10' E.
40.00	Set Temporary 1/4 Sec. Cor.
80.14	Intersect N & S. line 17 Rks. S. of
	Cor. to Secs. 8, 9, 16 & 17
	Thence I run
	S. 89°53' W. on true line
	Bet. Secs. 8 & 17
	With same Va
35.00	Ridge bears N.W. & S.E.
40.07	Set Limestone 12 x 10 x 5 ins. 8
	ins. in the ground for 1/4 Sec.
	Cor. marked 1/4 on N. face, and
	made regulation mound & pits
40.50	Hollow drains N.
	Leave Mountains bear N. & S.
	Enter rolling bench & sage brush
80.14	The Cor. to Secs. 7, 8, 17 & 18
	Land rolling & Mountains
	Soil 1st & 3rd rate
	Dense sage brush undergrowth
	on 39.64 Chs.
	Mountainous on 40.50 Chs.

BOOK-A-20

R. 16

Chs.	
	Augm
	West
40.00	Set Te
77.60	Intersec
	42 Rks.
	& 18 Whi
	ins. prop
	stone
	Thence
	N. 89°
30.00	Leave
	Enter
37.60	Set S
	the gr
	1/4 on
	teen
77.60	The C
	Land
	Se

R. 16 W. — S. L. M.

Chs. Augmented on 80. 14 Chs.

West on random line
Bet. Secs. 7 & 18
Va 18° 10' E.

40.00 Set Temporary 1/4 Sec. Cor.
77.60 Intersect W. By. of Township
42 Sks. N. of Cor. to Secs. 7, 12, 13
& 18 Which is a Limestone above ground 15x10x6 ins.
ins. properly marked, and mound of
stone alongside
Thence Trim
N. 89° 42' E. on true line
Bet. Secs. 7 & 18
With same Va

30.00 Leave Mountains bear N. & S.
Enter rolling bench & sage brush.
37.60 Set Slate 13x8x5 ins. 8 ins. in
the ground for 1/4 Sec. Cor. marked
1/4 on N. face, and made regula-
tion mound & pits
77.60 The Cor. to Secs. 7, 8, 17 & 18
Land rolling & Mountainous
Soil 1st & 3rd rate

Subdivisions T. 10 N.

Chs.	
	Dense sage brush undergrowth on 47.60 Chs.
	Mountainous on 30.00 Chs.
	Augmented on 77.60 Chs.
	North Bet. Secs. 7 & 8 Va 18° 10' E.
5.50	Flat Hollow drains N.E.
40.00	Set Limestone 20×12×10 ins. 15 ins. in the ground for 1/4 Sec. Cor. Marked 1/4 on W. face, and made regulation mound & pits
80.00	Set Sandstone 40×12×3 ins. 30 ins. in the ground for Cor. to Secs. 5, 6, 7 & 8, marked 5 notches on S. & E. edges, and made regulation mound & pits.
	Land rolling
	Soil 1st rate
	Dense sage brush undergrowth on 80.00 Chs.

BOOK-A-20

R. 16

Chs.	
	East
40.00	Set
80.00	Intersec
	of Cor.
	Thence
	N. 89°
34.00	Ridge
40.00	Set
	ins.
	Mark
	regula
73.70	Wagon
	Hollo
	Leave
	Enter
80.00	The Co
	Lan
	Soi
	Dense
	on 6.

R. 16 W. - S. L. M.

Chs.	
	East on random line
	Bet. Secs. 5 & 8
	Va 18° 10' E.
4.00	Set Temporary 1/4 Sec. Cor.
8.00	Intersect N. & S. line 25 Mls. N.
	of Cor. to Secs. 4, 5, 8 & 9
	Thence Same
	N. 89° 49' W. on true line
	Bet. Secs. 5 & 8
	With same Va
34.00	Ridge bears N.E. & S.W.
40.00	Set Sandstone 40 x 20 x 13 ins. 30 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on N. face, and made regulation Mound & pits.
73.70	Wagon road in hollow bears N.E. & S.W.
	Hollow drains N.E.
	Leave Mountains.
	Enter rolling land & sage brush
80.00	The Cor. to Secs. 5, 6, 7 & 8
	Land mountainous & rolling
	Soil 1st & 3rd rate
	Dense sage brush undergrowth on 6.30 Chs.

Subdivisions T. 10 N.

Chs.	
	Mountainous on 73.70 Chs.
	Augmented on 80.00 Chs.
	West on random line
	Bet. Secs. 6 & 7
	Va 18° 10' E.
40.00	Set Temporary 1/4 Sec. Cor
77.70	Intersect W. By. of Township
	18 Rks. S. of Cor. to Secs. 1, 6, 7 &
	12 which is a Limestone 6 x 8 x 6 ins
	above ground, properly marked, and
	mound of stone alongside in
	Thence S. run
	S. 89° 52' E. on true line
	Bet. Secs. 6 & 7
	With same Va
22.50	Leave mountains
	Enters rolling land & sage brush
37.70	Set Limestone 12 x 8 x 5 ins - 8 ins.
	in the ground for 1/4 Sec. Cor.
	marked 1/4 on N. face, and made
	regulation mound & pits
52.00	Wash drains N.E.
67.00	" " N.E.

R. 16

Chs.	
77.70	The C
	Lan
	So
	Dens
	on 5
	Mon
	Augm
	North
40.00	Set
80.39	Intr
	16 Rk
	& 32
	above
	mound
	Then
	S.O.
39.50	Gu
40.39	Set
	in

R. 16 W. – S. L. M.

Chs.
77.70 The Cor. to Secs. 5, 6, 7 & 8
Land rolling & Mountainous
Soil 1st & 3rd rate
Dense Sage brush underground
on 55.20 Chs.
Mountainous on 22.50 Chs.
Augmented on 77.70 Chs.

North on random line
Bet. Secs. 5 & 6
Va 18° 10' E.
40.00 Set Temporary 1/4 Sec. Cor.
80.39 Intersect N. By. of Township
16 Rs. E. of Cor. to Secs. 5, 6, 31
& 32 which is a Limestone 4x6x6 ins.
above ground, properly marked, and
mound of stone along side
Thence Iron
S. 0° 7' E. on true line
Bet. Secs. 5 & 6
With same Va
39.50 Gulch drains S. E.
40.39 Set Slate 20x8x4 ins – 15 ins.
in the ground for 1/4 Sec. Cor.

Subdivisions T. 10 N.

Chs.	
	Marked ¼ on W. face, and made regulation mound & pits.
68.00	Creek drains S.E.
80.39	The Cor. to Secs. 5, 6, 7 & 8
	Land rolling
	Soil 1st rate
	Dense sage brush undergrowth on 80.39 Chs

June 24. 1884

General Description.

The land embraced in this township is mostly rolling bench with mountains in the Northern portion - There is some fine bottom land along Rose Bud Creek, a fine stream of pure water running through the North Eastern part of the town.

R. 16

Chs.	
	Ship
	The
	Supp
	at Te
	Pacif
	iron
	In
	Cabin
	dug
	eval,
	but
	now
	There
	12 & 1
	The
	Sang

R. 16 W. L. L. M.

Obs. Ship.
The resavoir in Sec. 3.
supplies the water used
at Terrace on the Central
Pacific Railroad through
iron pipes.
In Sec. 21 there are two
Cabins and some Shafts
dug in prospecting for min-
eral, as also in Sec. 16
but apparently abandoned
now.
There are springs in Secs.
12 & 13.
The Township affords fine
range for stock.
Henry Fitzhugh
U.S. Deputy Surveyor

BOOK-A-203

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, October 11th 1884.

The foregoing field notes of the survey of the Subdivisions

Township No. 10 N. *Range No.* 16 W

Executed by Henry Fitzhugh No. 124

Under his *contract of the* 19th

day of March 1884, *in the month of*

June 1884, *having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.*

Fred Salomon

U. S. Surveyor General for Utah.

BOOK-A-203

9

REPORT: 1885 456

Filed July 30 1884

Examined by John H. Campe

Transcribed by Henry R. McAdkinson

Compared by E. S. R. M. A.

FIELD NOTES

OF THE SURVEY OF THE

Subdivision Lines

OF

Township No 11 North

Range No 13 West

OF THE

SALT LAKE MERIDIAN

IN

UTAH TERRITORY,

AS SURVEYED BY

Henry Fitzhugh

U. S. Deputy Surveyor,

Under his Contract No. 124

Dated March 19 1884

Survey commenced May 22nd 1884

Survey completed " 29th 1884

BOOK-A-203

Township 11 N R. 13 W.

6	527	5	510	4	499	3	487	2	474	1	
	526		525		509		497		486		472
7	524	8	508	9	496	10	485	11	471	12	
	523		522		507		495		484		469
18	521	17	506	16	494	15	483	14	467	13	
	520		519		505		493		481		466
19	518	20	504	21	492	22	480	23	465	24	
	517		516		503		491		479		463
30	515	29	502	28	490	27	478	26	461	25	
	514		513		501		489		477		460
31	512	32	500	33	488	34	476	35	458	36	

Subs. Tp. 11 N. R. 13 W

Chns. Survey commenced May 22nd 1884 with a Burts Improved Solar Compass.

From the cor. to Secs 1. 2. 35 & 36. on the South Boundary of the Tp. which is a Lime=stone 5 in above ground marked with 1 notch on E and 5 on W. edges, with pits and mound of earth along=side I run

North bet. Secs. 35 & 36
Va. 18° 10' E.

Through dense sage brush
40.00 Set charred cedar post 3 ft long 3 in. square, 12 in. in ground, for 1/4 sec. cor. marked 1/4 S on W face. dug ~~reg.~~ pits and raised

of the Salt Lake Meridian

Chs.	reg. mound of earth around post.
	Leave Bench and enter Dove creek valley brs. N.W. & S.E.
80.00	Set charred spruce post 4 ft. long 4 in. square, 2 ft. in ground for cor to Secs. 25, 26, 35 & 36 marked with 1 notch on S and 1 on E. Edges, and T 11 N. S. 25 on N.E. R 13 W S 36 on S.E. S 26 on N.W. S 35 on S.W. faces.
	dug reg. pits and raised 6 reg. mound of earth around post.
	Land Bluff & valley soil 1st rate

Subs. T. 11 N. R. 13 W.

Chs. Dense sagebrush undergrowth on 80. chs.

East on random line
bet. Secs. 25 & 36
Va. 18°15' E.

4.00 Set temp. 1/4 Sec. cor
80.22 Int E. Bd. of T. 27 Ks,
N. & cor. to Secs. 25. 30
31 & 36. which I find standing
and agrees with description
furnished me. viz: a
Trachyte 4 in above ground
properly marked, with reg
pits and mound of earth
alongside. from which
N. 89° 47 W. bw true line
bet. Secs. 25 & 36
with same Va.

Of the Salt Lake Meridian

chns	
10.00	Dove Creek 5 lks wide 4 in. deep rns. S.E.
40.11	Set Spruce post (charred) 3 ft. long 3 in. square 12 in. in ground, for 1/4 Sec. cor. marked 1/4 S on N face, dug reg pits and raised reg. mound of earth alongside
80.22	The cor. to Secs. 25. 26. 35 & 36.
	Land level
	Soil 1st rate
	Dense Sage brush undergrowth on 80.22 chs.
	North bet. Secs. 25 & 26
	Va. 18°10' E.
40.00	Set charred Spruce post

BOOK-

Sub

chs.	
	3 ft.
	in g
	ma
	dug
	reg
	Sid
80.00	Set
	4 ft.
	in g
	23. 2
	T 11
	R 13
	S: 2
	S 26
	1 no
	dug
	reg
	Sid
	S

Subs. T. 11 N. R. 13 W.

ch. 3 ft. long 3 in square 12 in in ground for 1/4 Sec. cor marked 1/4 S on W face, dug reg. pits and raised reg. mound of earth along side.

Do. Set charred Quakingasp post 4 ft. long 4 in. square, 2 ft. in ground, for cor. to Sec. 23, 24, 25 & 26. marked
T 11 N. S. 24 on N. E.
R 13 W S. 25 on S. E.
S. 23 on N. W
S 26 on S. W faces, and 1 notch on E and 2 on S. edges. dug reg. pits and raised reg. mound of earth along side.

Land level valley
Soil 1st rate

Of the Salt Lake Meridian

chns	Dense sagebrush under-growth on 80. chs.
	East on random line bet. Secs. 24 & 25
	Va. 18° 10' E.
40.00	Set temp. 1/4 Sec. cor.
80.43	Int. E. Bd. of Tp. 14 lks. N. of cor. to Secs. 24 & 25, which I find standing, and which agrees with description furnished me, viz: Trachyte 5 in. above ground properly marked and with reg. pits and mound of earth along side from which I run
	N. 89° 54' W on true line bet. Secs. 24 & 25
	with same va

BOOK

Jul

chs. 33.40	G
40.21	Se
	10
	1/4
	N.
	va
	Ea
54.00	To
	N.
58.00	Fo
64.25	K
67.08	D
	6
80.43	Th
	La
	L
	De
	on

Subs. T. 10 N R 13 W

chs.	
33.40	Gulch drus. S.W
40.21	Set volcanic rock 22 x 10 x 10 in. 16 in. in ground, for 1/4 sec. cor. marked 1/4 on N face, dug reg. pits and raised reg. mound of earth alongside. ascend
54.00	Top of volcanic Bench lrs. N. & S.
58.00	Foot of same lrs. S.E & N.W.
64.25	Road to Ambery lrs. N & S.
67.08	Dove Creek 5 lks. wide 6 in. deep rns. S.
80.43	The cor. to Secs. 23. 24. 25 & 26
	Land mostly level Bench
	Soil 2nd & 3rd rate
	Dense sagebrush undergrowth on 80.43 chs.

of the Salt Lake Meridian

chs.	
	North bet. Secs. 23 & 24
	Va. 18° 10' E.
38.00	Wash drains E
40.00	Set charred Cedar post 3 ft long 3 in. square, 12 in. in ground, for 1/4 Sec. cor. marked 1/4 S on W face, dug reg. pits and raised reg mound of earth alongside
43.50	Dove Creek 4 lks. wide 10 in deep rns. S.E.
64.00	Road to Ouray lrs. N.W. & S.E.
80.00	Set Trachyte 25 x 9 x 7. 18 in. in ground, for cor. to Secs. 13. 14. 23 & 24 marked with 3 notches on S and 1 on E. edges, dug reg. pits and raised reg. mound of earth alongside.

Sub

chs.	
	L
	S
	Dens
	and
	on
	E
	bet
40.00	Se
80.29	I
	N
	wh
	abo
	ma
	and
	Fro
	N 8
	bet

Subs. T. 11 N. R 13 W

chs. Land level
Soil 1st rate
Dense sage & rabbit brush
and greasewood undergrowth
on 80.00 chs.

East on random line
bet. Secs. 13 & 24
Va. 18° 10' E.
40.00 Set temp. 1/4 Sec. Cor.
80.29 Int E. Bd. of Tp. 34 lks.
N of cor. to Secs. 13 & 24
which is a Trachyte, 5 in
above ground, properly
marked, with reg. pits
and mound of earth alongside
From which I run
N 89° 45' W. on true line
bet. Secs. 13 & 24

of the Salt Lake Meridian

chs.		
		with same va.
3) 69.29	11.00	Leave bottom Ascend
2) 69.79	16.50	Enter high bench lvs. N & S.
1) 40.14		Set Volcanic rock 19x10x9 12 in. in ground, for 1/4 Sec. cor. marked 1/4 on N face, dug reg. pits and raised reg. mound of earth alongside.
80.29		The cor. to Secs. 13. 14. 23 & 24
		Land bottom and Bench soil 1st rate
		Dense sage brush & shad-scale undergrowth on 80.29 chs
		North bet. Secs. 13 & 14 Va. 18°10' E.
3.50		Road to Ombey lvs.

of the

chs.	
	N.
34.50	Roa
	N.
40.00	Set
	19 in
	Sec
	W f
	and
	of E
65.40	Cl
	N. 4
	Cl
80.00	Set
	21 in
	to S
	ma
	Sam
	reg
	in
	Co

of the Salt Lake Meridian

chs. N. E. & S. W.

34.50 Road to Ouray bro.

N. W. & S. E.

40.00 Set Trachyte 26 X 12 X 8 in. 19 in. in ground, for 1/4 Sec. cor. marked 1/4 on W face, dug reg pits and raised reg mound of earth alongside

65.40 Clarks corrall bears N. 79° 30' W.

Clarks House bro. N. 72° W

80.00 Set Trachyte 30 X 12 X 6 in. 21 in. in ground for cor. to Secs. 11, 12, 13 & 14. marked with 4 notches on S and on E. edges, dug reg. pits & raised reg. mound of earth alongside corrall bro. S. 58° 30' W.

of the Salt Lake Meridian

chs. Clarks house brs. S. 63°15' W
Land level valley
Soil 1st rate
Dense sage & rabbit
brush undergrowth on
80. chs.

East on random line
bet. Secs. 12 & 13
Va. 18° 10' E.

40.00 Set temp. 1/4 Sec. cor.
80.60 Int E. Bd of Tp. 42 lks.
N. of cor. to Secs. 12 & 13
which is a Trachyte firmly
set in ground properly
marked, and with reg.
pits and mound of earth
alongside. from which
N. 89° 42' W on true

Subs. T. 11 N. R. 3 W

line bet. Secs. 12 & 13
with same va.

40.30 Set charred cedar post
3 ft. long 3 in square, 12 in
in ground, for 1/4 Sec. cor.
marked 1/4 S on N face, dug
reg. pits and raised reg.
mound of earth around
post.

66.50 Leave Bench bro. N & S.
Enter valley

80.00 The cor. to Secs. 11, 12.
13 & 14

Land Bench & valley
Soil 1st rate

Dense sagebrush undergrowth
on 80.00 chs.

May 22nd 1884

of the Salt Lake Meridian

chs.	
	North bet. Secs. 11 & 12
	Va. 18°10' E.
13.65	Road to Kelton lrs. N.E. & S.W.
29.00	Enter Bench lrs. E & W.
40.00	Set Trachyte 22 x 10 x 6 in. 16 in. in ground for 1/4 sec. cor. marked 1/4 on W face, dug reg. pits and raised reg. mound of earth alongside.
50.50	Enter grassy hollow drns. S.W.
70.00	Leave hollow, enter Bench lrs. N.E. & S.W.
77.00	Small Gulch drns. S.E.
80.00	Set Trachyte 22 x 10 x 8 in 16 in. in ground for cor. to Secs. 1. 2. 11 & 12 marked with 1 notch on

BOOK-

Sub

E
re
re
ac
L
p
Den
gr

E
b

40.00 S
80.69 d
63
1 &
sto
fr
m

Subs. T. 10 N. R 13 W

E & 5 on S. Edges. dug
reg. pits and raised
reg. mound of earth
alongside
Land valley & bench
soil 1st rate
Dense sagebrush under=
growth on 80.00 chs.

East on random line
bet. Secs. 1 & 12
Va. 18° 10' E.
4.00 Set temp. 1/4 Sec. cor.
80.69 Int E. Boundary of Tp.
63 lks. N. of cor. to Secs.
1 & 12, which is a Lime=
stone 6 in above ground
firmly set & properly
marked and with reg.

Of the Salt Lake Meridian

Chs.	
	pits and mound of earth alongside from which N 89° 33' W on true line bet. Secs. 1 & 12
33.19	Road to Kelton crs. N.E. & S.W. with same va.
40.35	Set Limestone 16 x 12 x 6 in. 10 in. in ground, for 1/4 Sec cor. marked 1/4 on N side, with reg. pits and reg mound of earth alongside
54.10	Gulch drns. S.W
65.10	Leave bench crs. N.E. & S.W
	Enter hollow drns. S.W
68.50	Spring branch 15 lks. wide 2 in. deep drns. S.W
69.10	Leave hollow drns. S.W
80.69	The cor. to Secs. 1. 2. 11 & 12
	Land bench & to
	Soil Pt rate
	Dense sage brush under growth on 80.69 chs.

Subdiv

Chs.	
	Note
	A
	prov
	Com
	with
	my
	Hill
	the
	ins
	I m
	in
	lin
	No
20.00	Em
27.50	Sw
	Em
34.00	W
40.00	Set
	in

Subdivisions T. 11 N. R. 13 W. - S. L. M.

Chs. Note:
Knowing from connections previously made by the E. & W. boundaries of this Township with the N. Boundary under my Contract No. 116. That I will fall West outside of the limit for connecting instead of random lines. I run the last miles North in this Tp. North on true lines — Therefore North on true line
Bet. Secs. 1 & 2
Va 18°.10' E.

20.00 Enter grassy hollow drains S.E.
27.50 Leave same
Enter bench
34.00 Wash drains S.W.
40.00 Set brachyte 16 x 8 x 6 ins. 10 ins. in the ground for 1/4

Subdivisions T. 11 N.

Chs.	
	Sec. Cor. marked 1/4 on W. face and made regulation mound & pits.
59.20	Road bears E & W.
	Foot of volcanic butte.
65.00	Top of W. end of same bears E.
73.20	Foot of same.
	Old Emigrant road bears E & W.
79.30	Intersect N. Bdy. of Township 14.24 Chs. W. of Cor. to Secs. 35 & 36. where I set Trachyte 22 x 10 x 8 ins. - 15 ins. in the ground for closing Cor. to Secs. 1 & 2, marked 6 notches on S. 1 notch on E. & 5 notches on W. edges, with C. G. and made regulation mound & pits
	Land bench
	Soil 1st rate
	Dense sage brush undergrowth

BOOK-A

R. 1

Chs.	
	on
	Tom
	35
	Whic
	ins.
	prop
	mon
	Im
35.00	Wa
40.00	Set
	ins
	Cor.
	ma
80.00	Set
	in
	on
	an

R. 13 W. - S. L. M.

Chs. on 79.30 chs.

From the Cor. to Secs. 2, 3, 34 & 35 on the S. By. of Township Which is an aspen post 4 ins. square & 2 ft. above ground properly marked, and with mound & pits alongside —

Iron

North Bet. Secs. 34 & 35
Va 18.° 10' E

35.00 Wash drains E.

40.00 Set Limestone 14 x 10 x 6 ins. 10 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on W. face and made regulation mound & pits

80.00 Set Limestone 14 x 12 x 6 ins 10 ins in the ground, marked 1 notch on S. & 2 notches on E. edges and made regulation

Subdivisions T. 11 N.

Chs.	
	Mound & pits.
	Land flat
	Soil 1st rate
	Dense sage brush undergrowth
	on 80.00 Chs.
	East on random line
	Bet. Secs. 26 & 35
	Va 18° 10' E
40.00	Set Temporary 1/4 Sec. Cor
79.58	Intersect N. & S. line 33 Rks. N. of
	Cor. to Secs. 25, 26, 35 & 36
	Thence I run
	N. 89° 46' W. on true line
	Bet. Secs. 26 & 35
	With same Va
39.79	Set Sandstone 12 x 8 x 6 ins. 8
	ins. in the ground for 1/4
	Sec. Cor. marked 1/4 on N.
	face and made regulation

R. 13 W. - S. L. M.

Chs.	
	Mound & pits
48.10	Wash drains S.E.
79.58	The Cor. to Secs. 26, 27, 34 & 35
	Land flat
	Soil 1st rate
	Dense sage brush undergrowth
	on 79.58 chs.
	North Bet. Secs. 26 & 27
	Va 18° 10' E.
2.00	Wash drains N.E.
40.00	Set charred Spruce post 3 ft.
	long 3 ins. Square, 12 ins. in
	the ground for 1/4 Sec. Cor.
	marked 1/4 S. on W. face and
	made refutation Mound & pits
55.00	Wash drains S.E.
75.00	Ridge bears S.E. & N.W.
80.00	Set Limestone 14 x 10 x 8 ins. 10
	ins. in the ground for Cor.

Subdivisions T. 11 N.

Chs.	
	to Secs. 22, 23, 26 & 27, marked 2 notches on S. & E. edges, and made regulation mound & pits
	Land bench
	Soil 1st rate
	Dense Sage brush undergrowth on 80.00 Chs.
	East on random line
	Bet. Secs. 23 & 26
	Va 18° 10' E.
40.00	Set temporary 1/4 Sec. Cor.
79.31	Intersect N. & S. line. To 8 hrs. N. of Cor. to Secs. 23, 24, 25 & 26
	Thence I run
	N. 89° 51' W. on true line
	Bet. Secs 23 & 26
	Va 18° 10' E.
39.65	Set Charred Hickory post 3 ft.

BOOK-

R. 1

Chs.	
	Con
	the
	Mai
	Nea
50.00	W
79.31	The
	Dn
	un
	N
7.00	W
21.00	"
38.00	"
40.00	Set
	in
	Sec
	No

R. 13 W - S. L. M.

Chs.	Long 3 ins. square, 12 ins. in the ground for 1/4 Sec Cor. Marked 1/4 S. on N. face and made regulation mound & pits
50.00	Wash arains N.E.
79.31	The Cor. to Secs. 22, 23, 26 & 27
	Sand bench
	Soil 1st rate
	Dense sage brush & Greasewood undergrowth on 79.31 chs.
	North Bet. Secs. 22 & 23
	Va 18°10' E
7.00	Wash arains S.E.
21.00	" " "
38.00	" " "
40.00	Set Sandstone 18 x 10 x 6 ins. - 12 ins. in the ground for Cor. to Secs. 14, 15, 22 & 23, Marked 3 notches on S. & 2 on E. edges.

Subdivisions T. 11 N.

Chs.	
	and made regulation mound & pits.
80.00	Set Charred Spruce post 4 ft. long 4 ins. square, 12 ins. in the ground for Cor. to Secs. 14, 15, 22 & 23, marked
	T. 11 N. on N.E.
	R. 13 W. on S.E.
	S. 22 on S.W. and
	S. 15 on N.W. faces with 3 notches
	on S. & 2 on E. edges and
	made regulation mound & pits
	Land Bench
	Soil 1st rate
	Dense sage brush & Greasewood
	undergrowth on 80.00 chs.
	East on random line
	Bet. Secs. 14 & 23
	Va 18°10' E.

R. 13

Chs.	
40.00	Set
80.30	Int
	Cor.
	S. 8
13.75	Ra
	Ma
15.00	Dov
	Sm
18.80	Sec
29.00	Em
40.15	Set
	3 in
	for
	face
	M.
47.10	W.
48.80	n
74.30	
80.30	Th
	Dr

R. 13 W. - S. L. M.

Chs.	
40.00	Set Temporary 1/4 Sec. Cor.
80.30	Intersect N. & S. line 22 8 Ks. S. of Cor. to Secs. 13. 14, 23 & 24
	Thence Iron
	S. 89° 51' W. on true line
	Bet. Secs. 14 & 23
	With same Va
13.75	Road bears N. & S. Enter meadow - Leave sage brush
15.00	Dove Creek 6 8 Ks. wide 3 ins. deep runs S.
18.80	Leave meadow. Enter sage brush
29.00	Enter bench bears N. & S.
40.15	Set charred Aspen post 3 ft. long 3 ins. square, 12 ins. in the ground for 1/4 Sec. Cor. marked 1/4 S. on N. face and made regulation mound & pits
47.10	Wash drains S.E.
48.80	" "
74.30	" " N.E.
80.30	The Cor. to Secs. 14, 15, 22 & 23
	Land flat & bench
	Soil 1st rate
	Dense sage brush underground

Subdivisions T. 11 N.

Chs.	
	on 75.25 chs.
	North Bet. Secs. 14 & 15
	Va 18°10' E.
17.00	Wash drains E.
24.00	" " S.E.
40.00	Set Trachyte 14×8×6 ins - 10 ins. in the ground for 1/4 Sec. Cor. Marked 1/4 on W face, and made regulation mound & pits
71.50	Wash drains E.
80.00	Set Trachyte 16×10×4 ins - 10 ins. in the ground for Cor. to Secs. 10, 11, 14 & 15, Marked 4 notches on S. & 2 on E. edges and made regulation mound & pits.
	Land bench
	Soil 1st rate
	Dense sage brush & Greasewood undergrowth on 80.00 chs.

R. 13 W. S. L. M.

Chs.	
	East on random line Bet. Secs. 11 & 14. Va 18° 10' E.
40.00	Set Temporary 1/4 Sec. Cor.
79.80	Intersect N. & S. line 21 8 Ks N. of Cor. to Secs. 11, 12, 13 & 14 Thence S. run N. 89° 51' W. on true line Bet. Secs 11 & 14 With same Va
7.50	Road to Kelton bears N.E. & S.W.
21.00	Road to Ombey bears N. & S.
35.00	Enter Meadow bears N.W. & S.E.
37.00	Leave sage brush Dove Creek 20 Ks. wide 12 ins. deep runs S.E.
39.90	Set Charred Spruce post 3 ft. long 3 ins. square 12 ins. in the ground for 1/4 Sec. Cor. marked 1/4 S. on N. face, and made regulation mound & pits
46.50	Branch of Dove Creek 5 Ks. wide 15 ins. deep runs S.E.
51.75	Leave meadow, Enter sage brush
55.50	Grassy Slough bears N.W. & S.E.
78.00	Enter bench bears N.W. & S.E.

Subdivisions T. 11 N.

Chs.	
79.80	The Cor to Secs. 10, 11, 14 & 15
	Sand flat & bench
	Soil 1st rate
	Dense Sage brush undergrowth
	on 63.05 chs
	— May 23d 1884
	North Bet. Secs. 10 & 11
	Va 18.10 E
4.00	Enter bottom bears N.W. & S.E.
33.00	Irrigation ditch drains S.E.
36.00	Enter Meadow bears N.W. & S.E.
	Leave Sage brush
39.00	Dove Creek 4 Hs. wide 10 ins.
	deep runs S.E.
40.00	Leave Meadow. Enter Sage brush
	Set Wachy to 18 x 8 x 4 ins - 12 ins
	in the ground for 1/4 Sec. Cor.
	marked 1/4 on W. face, and
	made regulation mound & pits
45.00	Road to Ombey bears E & W.
50.00	Ascend
57.50	Enter high bench bears E & W.
80.00	Set Wachy to 20 x 10 x 7 ins - 15
	ins. in the ground for Cor. to

R. 13 W. S. L. M.

Chs	Secs. 2, 3, 10 & 11, marked 5 notches on S. & 2 on E. edges, and made regulation mound & pits.
	Land flat & bench
	Soil 1st rate.
	Dense sage brush undergrowth on 76.00 Chs
	East on random line
	Bet. Secs. 2 & 11
	Va 18° 10' E
40.00	Set temporary 1/4 Sec. Cor.
80.16	Intersect N. & S. line. 12 Rs. N. of Cor. to Secs. 1, 2, 11 & 12
	Thence Iron
	N. 89° 55' W. on true line
	Bet. Secs. 2 & 11
	With same Va
40.08	Set Limestone 20 x 8 x 8 ins. - 15 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on N. face, and made regulation mound & pits
72.00	Road bears N. E. & S. W.

Subdivisions. T. 11 N.

Chs.	
80.16	The Cor. to Secs. 2, 3, 10 & 11
	Land Bench
	Soil 1st rate
	Dense Sage Brush & Greasewood
	undergrowth on 80.16 Chs.
	Knowing from previous con=
	nections that I will fall
	West outside of Closing dis=
	tance, I run
	North on true line
	Bet. Secs. 2 & 3
	Vo 18°10' E
40.00	Set Trachyte 16×8×6 ins - 10 ins
	in the ground for 1/4 Sec. Cor.
	marked 1/4 on W. face, and
	made regulation Mound & pits
59.00	Old Emigrant road bears E & W.
78.23	Intersect N. By. of Township
	14.65 Chs. W. of Cor. to Secs.
	34 & 35, where I set
	Trachyte 22×7×6 ins - 15 ins.
	in the ground for Closing
	Cor. to Secs. 2 & 3, marked

R. 13 W. S. L. M.

chs. 6 notches on S. 2 on E. & 4 on W. edges, with C. C. and made regulation mound & pits
Land bench
Soil 1st rate
Dense Sage brush & Greasewood underground on 78.23 chs

From the Cor. to Secs. 3, 4, 33 & 34 on the S. By. of Township which is a limestone 6 x 13 x 7 ins above ground properly marked & with mound & pits along side.
I run
North Bet. Secs. 33 & 34
Va. 18° 10' E.

28.00 Gulch drains N.E.

40.00 Set Limestone 14 x 8 x 6 ins. 10 ins. in the ground for 1/4 sec. cor. marked 1/4 on W. face and made regulation mound & pits

Subdivisions T. 11 N.

Chs.	
58.00	Gulch Avaine N.E.
73.00	" " "
80.00	Set Limestone 17×10×6 ins - 11 ins. in the ground for Cor. to Secs. 27, 28, 33 & 34, marked 1 notch on S. & 3 notches on E. edges, and made regulation mound & pits. Land E. Slope Cedar Mountain Soil 3rd rate.
High	Mountainous on 80.00 Chs.
	East on random line Bet. Secs. 27 & 34 Va. 18°, 0' E.
40.00	Set Temporary 1/4 Sec. Cor.
80.00	Intersect N. & S. line 21 Chs. N. of Cor. to Secs. 26, 27, 34 & 35 Thence Inner N. 89°51' W on true line Bet. Secs. 27 & 34 With Same Va.
40.00	Set Limestone 22×12×6 ins - 15 ins. in the ground for 1/4 Sec. Cor.

R. 13 W. S. L. M.

Chs.	Marked 1/4 on N. face, and made regulation mound & pits
60.00	Pivot bench & sage brush
	Enter mountains bear N.E. & S.W.
80.00	The Cor. to Secs. 27, 28, 33 & 34
	Land bench & Mountainous
	Soil 1st & 3rd rate
	Dense sage brush undergrowth on 60.00 Chs.
High	Mountainous on 20.00 Chs.
	Augmented on 80.00 Chs
	North Bet. Secs. 27 & 28
	Va 18° 10' E.
40.00	Set Cobble stone 12 x 10 x 6 ins - 8 ins. in the ground for 1/4 Sec. Cor.
	Marked 1/4 on W. face, and made regulation mound & pits
47.50	Gulch drains E.
80.00	Set Shale 14 x 8 x 6 ins - 10 ins.

Subdivisions T. 11 N.

Chs.	
	for cor. to secs. 21, 22, 27 & 28
	in the ground, marked 2
	notches on S. & 3 on E. edges.
	and made regulation
	mound & pits.
	Land Mts
	Soil 3rd rate
High	Mountainous on 80.00 Chs.
	East on random line
	Bet. Secs. 22 & 27
	Va 18° 10' E.
40.00	Set Temporary 1/4 Sec. Cor.
80.13	Intersect N. & S. line 29 Rks. S.
	of Cor. to Secs. 22, 23, 26 & 27
	Thence Snin
	S. 89° 48' W. on true line
	Bet. Secs. 22 & 27
	Va 18° & 10' E.
10.00	Ravine drains N.E.
30.00	" " S.E.

R. 13 W. S. L. M.

Chs.	
40.06	Set charred Cedar post 3 ft. long 3 ins. Square 12 ins. in the ground for 1/4 Sec. Cor. marked 1/4 S. on N. face, and made regulation mound & pits.
80.13	The Cor. to Secs. 21. 22. 27 & 28
	Land Mountainous
	Soil 3rd rate
High	Mountainous on 80.13 Chs
	North Bet. Secs. 21 & 22
	Va 18° 10' E.
13.50	High ridge bears N.W. & S.E.
40.00	Set Limestone 16 x 10 x 8 ins. 10 ins. in the ground for 1/4 Sec. Cor. marked 1/4 S. on N. face, and made regulation mound & pits
52.00	Gulch drains E.
80.00	Set Shale 19 x 10 x 4 ins - 12 ins in the ground for Cor. to Secs.

Subdivisions T. 11 N.

Chs.	15, 16, 21 & 22, marked 3 notches on S. & E. edges and made regulation Mound & pits	
	Land Mountainous	
	Soil 3rd rate	
High	Mountainous on 80.00 Chs.	
	East on random line	
	Bet. Secs. 15 & 22	
	Va 18° 10' E.	
40.00	Set Temporary 1/4 Sec. Cor.	
80.10	Intersect N. & S. line 65 Hs. N. of Cor. to Secs. 14, 15, 22 & 23	
	Thence from	
	N. 89° 32' W. on true line	
	Bet. Secs. 15 & 22	
	With same Va	
40.05	Set Spruce post (Charred) 3 ft. long 3 ins. square, 12 ins. in the ground for 1/4 Sec. Cor.	

BOOK-A-203

R. 13 W. - S. L. M.

Chs.	Marked 1/4 S. on N. face and made regulation mound & pits
49.00	Wash drains N.E.
60.10	Enter mountains bear N.W. & S.E.
	Leave sage brush
80.10	The leav. to Secs. 15, 16, 21 & 22
	Land & bench & mountainous
	Soil 1st & 3rd rate
	Dense sage brush undergrowth on 60.10 chs.
High	Mountainous on 20.00 chs
	Augmented on 80.10 chs
	May 24th 1884
	North Bet. Secs. 15 & 16
	Dn 18 10 E.
33.00	Leave mountains bear N.W. & S.E.
	Enter bench & sage brush
40.00	Set charred cedar post 3 ft. long 3 ins. square, 12 ins. in the ground, for 1/4 Sec. Cor. marked

Subdivisions T. 11 N.

Chs.	1/4 S. on W. face, and made regulation mound & pits
80.00	Set charred cedar post 4 ft. long 4 ins. square, 12 ins. in the ground for Cor. to Secs. 9, 10, 15 & 16, marked T. 11 N. R. 13 W. on N.E. S. 15 on S.E. S. 16 on S.W. and S. 9 on N.W. with 4 notches on S. and 3 on E. edges and made regulation mound & pits.
	High mountains on 33.00 chs.
	Dense underwrowth on 47.00 ch
	Augmented on 80.00 "
	Cast on random line
	Bet. Secs. 10 & 15
	Va 18° 10' E.
40.00	Set temporary 1/4 Sec. Cor.
79.93	Intersect N & S. line 40 Sks. S. of Cor. to Secs. 10, 11, 14 & 15

R. 13 W. S. L. M

Chs. Thence Dun
S. 89°43 W. on true line
Bet. Secs 10 & 15
With same Va
39.96 Set charred Spruce post 3 ft.
long 3 ins. square, 12 ins in
the ground for 1/4 Sec. Cor.
Marked 1/4 S. on N. face and
made regulation mound & pits
48.00 Wash drains S.E.
79.93 The Cor. to Secs. 9, 10, 15 & 16
Sand bench
Soil 1st rate
Dense sage brush underground
on 79.93 Chs.

North Bet. Secs. 9 & 10
Va 18°10' E.
4.00 Set charred Cedar post 3 ft.
long 3 ins. square, 12 ins. in

Subdivisions T. 11 N.

Chs.	
	the ground for 1/4 Sec. Cor. Marked 1/4 S. on N. face and made regulation mound & pits
50.00	Wash Arains S.E.
75.50	Enter bottom & meadow
	Leave sage brush
80.00	Set Quartzite 20×8×6 ins - 15 ins in the ground for Cor. to Secs. 3, 4, 9 & 10, marked 5 notches on S. & 3 on E. edges, and made regulation mound & pits.
	Land bench & bottom
	Soil 1st rate.
	Dense sage brush under growth on 75.50 chs.
	East on random line
	Bet. Secs. 3 & 10
	Va 18°10' E.
40.00	Set Temporary 1/4 Sec. Cor.

R. 13 W. S. L. M

Chs	
80.16	Intersect N. & S. line 27 8 lks. N. of Cor. to Secs. 3.4, 9 & 10
	Thence Iron
	N. 89° 48' W. on true line
	Bet. Secs. 3 & 10
	With same Va
23.00	Wash drains S.W.
25.00	" " S.
33.00	Descend
40.08	Set Limestone 14 x 8 x 6 ins - 10 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on N. face and made regulation mound & pits
54.00	Road in Canon bears. N.W. & S.E.
55.00	Dove Creek 20 ins. wide 24 ins. deep runs. S.E.
56.00	Spring 7 lks. N. of line
64.00	" 125 " " " "
	Enter bottom & Meadow
	Leave Sage brush
80.16	The Cor. to Secs. 3.4.9 & 10
	Land bench & bottom
	Soil 1st rate
	Dense Sage brush undergrowth on 64.00 Chs

Subdivisions T. 11 N.

Chs.	
	Knowing from previous connections that I will fall West outside of the limit for connecting —
	Iron
	North on true line Bet. Secs. 3 & 4
	Dec 18° 10' E.
13.60	Dove Creek 12 Sks. wide 10 ins. deep runs S.E.
15.00	Road bears N.W. & S.E.
	Leave Meadow. Enter Sage brush
18.00	Enter bench bears N.W. & S.E.
40.00	Set limestone 14 x 8 x 4 ins - 10 ins in the ground for 1/4 Sec. Cor. marked 1/4 on W. face and made regulation mound & pits
49.00	Old Emigrant road bears N.E. & S.W.
78.10	Intersect N. By. of Township 14.60 Chs. W. of Cor. to Secs. 33 & 34 where I set
	Limestone 20 x 8 x 4 ins. 15 ins. in the ground for Closing Cor. to Secs. 3 & 4, marked 6 notches on S. & 3 on E. & W. edges with C. C. and made

R. 13 W. – S. L. M.

Chs.	regulation mound & pits Sand bench & bottom Soil 1st rate Dense sage brush undergrowth on 63.10 Chs
	From the Cor. to Secs. 4, 5, 32 & 33 on the S. By. of Township Which is a Limestone 5×10×6 ins above ground properly marked with mound & pits along side Iron
	North bet. Secs. 32 & 33 Va 18° 10' E.
30.00	High ridge bears N.E. & S.W.
40.00	Set Limestone 16×12×8 ins. 10 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on W. face and made regulation mound & pits
51.50	Gulch drains N.E.
63.00	Ridge bears N.E. & S.W.
80.00	Set Conglomerate 18×6×4 ins. 12 ins. in the ground for Cor. to

Subdivisions T. 11 N.

Chs.		Chs.	R.
	Secs. 28, 29, 32 & 33, marked 1 notch on S. & 4 notches on E. edges, and made regulation mound & pits.	55.23	G
		61.75	R
		71.70	G
		76.20	
	Land Mountainous	79.73	
	Soil 4th rate		
?	Mountainous on 80.00 chs.		
	East on random line		
	Bet. Secs. 28 & 33		
	Va 18° 10' E.		
40.00	Set Temporary 1/4 Sec. Cor.	1.50	
79.73	Intersect N. & S. line 19 8 Ns. S. of	9.00	
	Cor. to Secs. 27, 28, 33 & 34	29.00	
	Thence I run	34.00	
	S. 89° 52' W. on true line	39.00	
	Bet. Secs. 28 & 33	40.00	
	Va 18° 10' E.		
28.00	Gulch drains N.E.		
39.86	Set. Shale 20 x 12 x 4 ins. 15 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on N. face and made regulation mound & pits	60.00	
40.00	Gulch drains N.E.	80.00	

BOOK-A-203

R. 13 W. S. L. M.

Chs.	
55.23	Gulch drains N.E.
61.75	Ridge bears N.E. & S.W.
71.70	Gulch drains N.E.
76.20	" " "
79.73	The Cor. to Secs. 28, 29, 32 & 33
	Land Mountainous
	Soil 1st rate
	Mountainous on 79.73 Chs ?
	North Bet. Secs. 28 & 29
	Va 18° 10' E.
1.50	Gulch drains N.E.
9.00	" " "
29.00	" " "
34.00	" " "
39.00	" " "
40.00	Set Shale 14×10×5 ins - 10 ins in the ground for 1/4 Sec. Cor. marked 1/4 on W. face, and made regulation mound & pits
60.00	Leave Mountains
	Enter Gulch bears N.W. & S.E. & Sage brush
80.00	Set Limestone 14×10×6 ins - 10

Subdivisions T. 11 N.

Chs.	
	ins. in the ground for Cor. to Secs. 20, 21, 28 & 29, marked 2 notches on S. & 4 on E. edges and made regulation mound & pits.
	Land Mountainous & bench Soil 4th & 3rd rate
	Mountainous on 60.00 Chs. Dense sage brush under-growth on 20.00 Chs. Augmented on 80.00 Chs. May 26th 1884
	East on random line Bet. Secs. 21 & 28 Va 18°10' E.
40.00	Set Temporary 1/4 Sec. Cor.
80.42	Intersect N. & S. line 32 Rks. S. of Cor. to Secs. 21, 22, 27 & 28 Thence L run
	S. 89°46' W. on true line Bet. Secs. 21 & 28 With same Va
10.00	Ridge bears N. & S.
19.00	Creek drains S.E.

BOOK-

R.

Chs.	
23.00	Re
40.21	Set
	ins
	Cor
	M
45.00	Ea
	N.
80.42	The
	M
	Dr
	G
	N
40.00	Se
	in
	Co
	m
53.50	W
80.00	S

R. 13 W. - S. L. M.

Chs.	
23.00	Ridge bears N.W. & S.E.
40.21	Set Conglomerate 18×9×7 ins. 12 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on N. face and made regulation mound & pits
45.00	Enter high bench bears N.W. & S.E. & sage brush
80.42	The Cor. to Secs. 20, 21, 28 & 29 Land Mountainous & bench Soil 4th & 1st rate Mountainous on 45.00 Chs. Dense sage brush under growth on 35.42 Chs. Augmented on 80.42 Chs

North Bet. Secs. 20 & 21
Va 18°10' E.

40.00	Set Limestone 18×8×4 ins. 12 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on N. face and made regulation mound & pits
53.50	Wash drains S.E.
80.00	Set Limestone 16×10×6 ins. 10

Subdivisions T. 11 N.

Chs.	
	ins. in the ground for Cor. to Secs. 16. 17. 20 & 21 marked 3 notches on S. & 4 on E. edges, and made regulation mound & pits
	Land high bench
	Soil 2nd rate
	Dense sage brush under-growth on 80.00 Chs
	East on random line
	Bet. Secs. 16 & 21
	Va 18° 10' E
40.00	Set Temporary 1/4 Sec. Cor.
79.50	Intersect N & S. line 10 Rks. S. of Cor. to Secs. 15. 16, 21 & 22
	Thence I run
	S. 89° 56' W. on true line
	Bet. Secs. 16 & 21
	Va 18° 10' E.
20.50	High ridge bears N.W. & S.E.
39.75	Set Charred Balsam post 3 ft. long 3 ins. square, 12 ins. in

R. 13 W. S. L. M.

Chs.	
	the ground for 1/4 Sec. Cor. marked 1/4 S. on N. face and made regulation mound & pits
41.50	Raine drains S.E.
52.00	Enter high bench bears N.W. & S.E. & sage brush
79.50	The Cor. to Secs. 16. 17. 20 & 21 Sand Mountainous & bench Soil 1st & 3rd rate Mountainous on 52.00 chs. ? Dense sage brush underground on 27.50 chs. Augmented on 79.50 chs
	North Bet. Secs. 16 & 17 Va 18.10 E.
4.00	Enter Mountains bear E. & W. Leave sage brush
8.00	Gulch drains S.E.
36.00	Ridge bears N.E. & S.W.
40.00	Set Limestone 16 x 10 x 8 ins. 10 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on W. face

Subdivisions T. 11 N.

Chs.	
	and made regulation mound & pits.
44.00	Creek drains W.
49.00	Ridge bears E. & W.
70.00	Enter flat bears E. & W. & sage brush
80.00	Set Limestone 18×8×8 ins. - 12 ins. in the ground for Cor. to Secs. 8, 9, 16 & 17 marked 4 notches on S. & E. edges and made regulation mound & pits.
	Sand Mountainous & bench Soil 3rd & 4th rate
?	Mountainous on 66.00 Chs.
	Dense sage brush undergrowth on 14 Chs.
	Augmented on 80.00 Chs.
	East on random line Bet. Secs. 9 & 16 Va 18°10' E.
40.00	Set Temporary 1/4 Sec. Cor.
79.63	Intersect N. & S. line 28 Chs. S. of

BOOK-A-203

R. 13 W. – S. L. M.

Chs.	Cor. to Secs. 9. 10. 15 & 16
	Thence I run
	S. 89° 48' W. on true line
	Bet. Secs. 9 & 16
	With same Va
39.81	Set Charred Spruce post 3 ft. long 3 ins. square, 12 ins. in the ground, for 1/4 Sec. Cor. marked 1/4 S. on N. face and made regulation mound & pits.
75.50	S. W. point of ridge bears N. E.
79.63	The Cor. to Secs. 8, 9. 16 & 17
	Land rolling bench
	Soil 1st & 2nd rate
	Dense sage brush undergrowth on 79.63 Chs
	North Bet. Secs. 8 & 9
	Va 18° 10' E.
27.00	Wash drains N. E.
32.00	" " S. E.
40.00	Set Limestone 16 & 8 & 7 ins. 10 ins. in the ground for 1/4 Sec. Cor.

Subdivisions T. 11 N.

Chs.	
	Marked 1/4 on W. face and made regulation mound & pits
80.00	Set Limestone 20×12×8 ins - 15 ins. in the ground for Cor. to Secs. 4, 5, 8 & 9, marked 5 notches on S. & 4 on E. edges and made regulation mound & pits.
	Land rolling bench Soil 2nd rate
	Dense sage brush under = growth on 80.00 chs.
	East on random line Bet. Secs. 4 & 9 Va 18° 10' E.
40.00	Set temporary 1/4 Sec. Cor.
80.30	Intersect N. & S. line 32 Rks. N. of Cor. to Secs. 3, 4, 9 & 10
	Thence I run
	N. 89° 46' W. on true line Bet. Secs. 4 & 9 With same Va

R. 13 W — S. L. M

Chs.	
1.00	Spring bears N. 40 Rs. dist
6.80	Leave bottom & meadow
	Enter bench bears N.W. & S.E.
	& sage brush
27.00	Wash drains N.E.
40.15	Set Martzite 18x6x6 ins. 12
	ins in the ground for 1/4 Sec.
	Cor. Marked 1/4 on N face and
	made regulation mound & pits
80.30	the Cor. to Secs. 4, 5, 8 & 9
	Land bottom & bench
	Soil 1st rate
	Dense sage brush underground
	on 73.50 Chs.

Knowing from previous connections that I will face West outside of the limit for connecting

I run

North on true line

Bet. Secs. 4 & 5

Subdivisions T. 11 N.

Chs.	Jan 18 1883
23.75	Gulch drains N.W.
33.25	Fence bears N.W. & S.E.
	Enter meadow
	Leave rolling bench & sage brush
40.00	Shirley's House bears N. 22° 30' E.
	His barn bears N. 20° 00' E.
	Set charred spruce pot 3 ft.
	long 3 ins square, 12 ins. in
	the ground for 1/4 Sec. Cor.
	marked 1/4 S on W face, and
	made regulation mound & pits
47.25	Dove Creek 15 Lks. wide 15 ins
	deep runs S.E.
47.30	Spring on line
55.00	S.W. Cor. of Corral 40 Lks. East
63.25	Road bears N.W. & S.E.
69.50	Fence bears N.W. & S.E.
	Leave meadow
70.75	Road bears N.W. & S.E.
	Enter sage brush
77.75	Shirley's house bears S. 15° 30' E.
	His barn bears S. 13° 45' E.
	Intersect N. Bry. of Township
	14.75 chs. N. of Cor. to Secs.

R. 13 W. - S. L. M.

Chs. 32 & 33, where I set
Charred Spruce post 4 ft. long
4 ins. square, 12 ins. in the
ground for closing cor. to Secs.
4 & 5, marked
T. 11 N. R 13 W. on S.E. and
S. 5 on S.W. with 6 notches on
S. 4 on E. & 2 on W. edges with
C.C. and made regulation
mound & pits.
Land rolling bench & bottom
Soil 2nd & 1st rate
Dense sage brush undergrowth
on 40.25 Chs
May 27th 1884

From the Cor. to Secs. 5.6 31 & 32
on the S. Br. of Township
which is a Limestone 6 x 8 x 7 ins
above ground properly marked
& with mound & pits alongside
Iron
North Bet. Secs 31 & 32

Subdivisions T. 11 N.

Chs.	Va 18° 10' E
40.00	Set Limestone 14×10×6 ins. 10 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on W. face, and made regulation mound & pits.
50.00	Enter hollow drains N.W. and Sage brush
60.00	Enter mountains, Grove sage brush
77.00	Raine drains S.W.
80.00	Set Charred Cedar post 4 ft. long 4 ins. square, 12 ins. in the ground, marked 1 notch on S & 5 notches on E. edges and made regulation mound & pits
	Land mostly mountainous Soil 2nd & 4th rate
	Dense sage brush under growth on 10.00 chs.
High	Mountains on 70.00 chs. Augmented on 80.00 chs.
	East on random line Bet. Secs. 29 & 32

R. 13 W - S. L. M

Chs | Va 18° 10' E
40.00 | Set Temporary 1/4 Sec. Cor.
80.30 | Intersect N. & S. line 26 8 Ks. S. of Cor. to Secs. 28, 29, 32 & 33
Thence S mn
S. 89° 49' W. on true line
Bet. Secs. 29 & 32
With same Va
4.30 | Gulch drains N.E.
28.25 | Ridge bears N. & S.
40.15 | Set Limestone 16 x 8 x 4 ins - 10 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on N. face and made regulation Mound & pits
42.00 | Gulch drains S.W.
80.30 | The Cor. to Secs. 29, 30, 31 & 32
Land mountainous
Soil 4th rate
High Mountains on 80.30 chs.

West on random line
Bet. Secs. 30 & 31
Va 18° 10' E.

Subdivisions T. 11 N.

Chs.	
40.00	Set Temporary 1/4 Sec. Cor.
79.00	Intersect W. Bry. of Township
	48 Sks. N. of Cor. to Secs. 25, 30
	31 & 36 Which is a Sandstone 4x8x7
	ins above ground properly marked & mound & pits along side
	Thence Run
	N. 89° 39' E. on true line
	Bet. Secs. 30 & 31
	With same Va
39.00	Set Slate 12x10x5 ins - 8 ins
	in the ground for 1/4 Sec. Cor.
	Marked 1/4 on N. face, and
	made regulation Mound & pits
46.50	Raime drains S.W.
79.00	The Cor. to Secs. 29, 30, 31 & 32
	Sand Mountainous
	Soil 4th rate
?	Mountainous on 79.00 Chs
	North Bet. Secs. 29 & 30
	Va 18° 10' 8.
31.50	Raime drains S.W.
40.00	High ridge bears E.&W.

BOOK-A

R.

Chs.	
	Set
	in
	Mo
	Mo
70.00	Ra
80.00	Set
	15
	Sec
	M
	a
	&
	W
	E
40.00	S
80.39	S
	Co
	S

R. 13 W. - S. L. M.

Chs. Set Slate 20×10×8 ins - 15 ins. in the ground for 1/4 Sec Cor. marked 1/4 on W. face, and made regulation mound & pits

7.00 Ravine drains N.E.

8.00 Set Conglomerate 20×10×7 ins 15 ins. in the ground for Cor. to Secs. 19. 20, 29 & 30. marked 2 notches on S. & 5 on E. edges and made regulation mound & pits

Land mountainous
Soil 4th rate
Mountainous on 8.00 Chs

East on random line
Bet. Secs. 20 & 29
Va 18°10' E.

4.00 Set Temporary 1/4 Sec. Cor.

8.39 Intersect N. & S. line 40 Rks. S. of Cor. to Secs. 20. 21, 28 & 29
Thence I run
S. 89°43' W. on true line
Bet. Secs. 20 & 29

Subdivisions T. 4 N.

Chs.	With same Va
20.30	Leave high bench & sage brush. Enter Mountains bear N.W. & S.E.
35.25	Ravine drains N.E.
40.19	Set Charred Cedar post 3 ft. long 3 ins. square, 12 ins. in the ground for 1/4 Sec. Cor. marked 1/4 S. on N. face and made regulation mound & pits
49.30	High ridge bears N.E. & S.W.
75.00	Ravine drains N.E.
80.39	The Cor. to Secs. 19, 20, 29 & 30
	Sand Mountainous
	Soil 4th rate
?	Mountainous on 80.39 chs
	West on random line
	Bet. Secs. 19 & 30
	Va 18° 10' E.
40.00	Set Temporary 1/4 Sec. Cor.
79.22	Intersect W. By. of Township 21 Ks. S. of Cor. to Secs. 19, 24, 25 & 30 which is limestone 7 x 10 x 9 ins. above ground, properly marked with pits & mound accordingly

R. 13 W - S. L. M

Chs Thence I run
S. 89° 51' E on true line
Blt. Secs. 19 & 30
With same Va

19.00 Raine drains N.
39.22 Set. Limestone 18 x 10 x 4 ins - 12 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on N. face, and made regulation mound & pits
57.25 High ridge bears S.E. & N.W.
79.22 The Cor. to Secs. 19. 20, 29 & 30
Land mountainous
Sixth 4th rate
Mountainous on 79.22 chs

North Blt. Secs. 19 & 20
Va 18.10' E.

12.00 Creek drains N.E.
40.00 Set Limestone 18 x 8 x 4 ins, 12 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on N. face and made regulation mound & pits
41.50 High ridge bears N.E. & S.W.
49.75 Deep raine drains N.E.

Subdivisions T. 11 N.

Chs.	
53.50	High ridge bears N.E. & S.W.
64.00	Greek drains N.E.
73.00	" " S.E.
80.00	Set Conglomerate 18 x 16 x 7 ins - 12 ins. in the ground for Cor. to Secs. 17. 18. 19 & 20, marked 3 notches on S. & 5 on E. edges, and made regulation mound & pits
	Land Mountainous
	Soil 4th rate
	Mountainous on 80.00 Chs.
	East on random line
	Bet. Secs. 17 & 20
	Va 18°. 10' E.
40.00	Set Temporary 1/4 Sec. Cor.
80.00	Intersect N. & S. line 13 Chs. S. of Cor. to Secs. 16. 17. 20 & 21
	Thence I run
	S. 89°. 54' W. on true line
	Bet. Secs. 17 & 20
	With same Va
40.00	Set Charred Balsam post 3 ft. long 3 ins square, 12 ins. in

R. 13 W. S. L. M.

Chs.	the ground for 1/4 Sec. Cor. marked 1/4 S. on N. face, and made regulation mound & pits
48.00	Raine Arains S.E. Enter mountains. Grove sage brush
73.00	Ridge bears N. & S.
80.00	The Cor to Secs. 17, 18, 19 & 20 Land Mountainous & brush Soil 1st & 3rd rate Mountainous on 32.00 Chs. Dense sage brush undergrowth on 48.00 Chs. Augmented on 80.00 chs
	West on random line Bet. Secs. 18 & 19 Va 18° 10' E.
40.00	Set temporary 1/4 Sec. Cor.
78.75	Intersect W. Bry. of Township 38 Sts N. of Cor. to Secs. 13, 18, 19 & 24 which is a limestone 4 & 8 & 7 ins above ground Thence Town properly marked N. 89° 44' E. on true line with same Va
16.75	Ridge bears N. & S.

Subdivisions T. 11 N.

Chs.	
30.50	Gulch drains S.E.
38.75	Set Conglomerate 18×12×7 ins. 12 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on N. face and made regulation mound & pits
44.25	Gulch drains S.
51.25	" " S.
68.50	" " S.E.
73.75	Ridge bears N.W. & S.E.
78.75	The Cor. to Secs. 17.18.19 & 20
	Land mountainous
	Soil 4th rate
	Mountainous on 78.75 chs
	May 28th 1884
	North Blt. Secs. 17 & 18
	Vn 18° 10' E.
5.00	Gulch drains S.E.
11.50	Ridge bears N.W. & S.E.
21.50	Lower Mountains. Eastern high bench bears E. & W. & sage brush
40.00	Set Conglomerate 12×8×6 ins 8 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on W. face and made regulation mound & pits.

R. 13 W. S. L. M.

Chs
80.00 Set Limestone 18 x 7 x 5 ins. 12 ins. in the ground for Cor. to Secs. 7. 8. 17 & 18. Marked 4 notches on S. and 5 on E. edges and made regulation mound & pits.

Land Mountainous & bench
Soil 3rd & 4th rate
Dense sage brush undergrowth on 58.50 Chs.
Mountainous on 21.50 Chs.
Augmented on 80.00 Chs

East on random line
Bet. Secs 8 & 17
Va 18° 10' E.

40.00 Set Temporary 1/4 Sec. Cor.
80.11 Intersect N. & S. line 20 Rks. N. of Cor. to Secs. 8, 9. 16 & 17.
Thence Iron
N. 89° 51' W. on line
Bet. Secs 8 & 17
With same Va

24.00 Wash drains N

Subdivisions T. 11 N.

Chs.	
40.05	Set Limestone 19×15×8 ins - 12 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on N. face and made regulation mound & pits
53.00	Enter rolling hills bear N.E. & S.W.
73.00	Ridge bears N.E. & S.E.
80.11	The Cor. to Secs. 7, 8, 17 & 18
	Land bench & hilly
	Soil 1st & 3rd rate
	Dense sage brush undergrowth on 80.11 chs.
	West on random line
	Bet. Secs. 7 & 18
	Va 18°10' E.
40.00	Set Temporary 1/4 Sec. Cor.
78.80	Intersect N. By. of Township 42 Ms. S. of Cor. to Secs. 7, 12, 13 & 18 which is a Limestone 6×8×8 ins. above ground, properly marked & mound & pits along side
	Thence Inn
	S. 89°42' E. on true line
	Bet. Secs. 7 & 18
	With same Va

R.

Chs.	
28.80	Ri
38.80	Se
	ins.
	ma
	Re
43.50	W
70.30	W
78.80	The
	M
	No
12.00	Ri
33.00	S
	be
40.00	Se
	Co
	th
	m
	m
47.25	W
65.00	O

R. 18 W. – S. L. M.

chs.	
28.80	Ridge bears N. & S.
38.80	Set limestone 14 x 12 x 7 ins. – 10 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on N. face, and made regulation mound & pits.
43.50	Good road bears N. & S.
70.30	Wash drains S.E.
78.80	The Cor. to Secs. 7. 8. 17. & 18
	Land Mountains
	Soil 4th rate
	Mountains on 78.80 chs

North Bet. Secs. 7 & 8
Var. 18° 10' E.

12.00	Ridge bears N.E. & S.W.
33.00	Snow hills. Enter bench bears N.E. & S.W.
40.00	Set Charred Aspen post 8 ft. long 3 ins. square, 12 ins. in the ground for 1/4 Sec. Cor. marked 1/4 S. on W. face, and made regulation mound & pits
47.25	Wash drains N.E.
65.00	Old road bears N.E. & S.W.

Subdivisions T. 11 N.

Chs.	
80.00	Set Limestone 22×2×6 ins. 15 ins. in the ground for Cor. to Secs. 5, 6, 7 & 8, marked 5 notches on S. & E. edges, and made regulation mound & pits
	Land hilly & bench
	Soil 3rd & 1st rate
	Dense sage brush undergrowth on 80.00 Chs.
	East on random line
	Bet. Secs. 5 & 8
	Va 18° 10' E.
40.00	Set Temporary 1/4 Sec. Cor.
80.23	Intersect N. & S. line 33 8 Ks. S. of Cor. to Secs. 4, 5, 8 & 9
	Thence Sun
	S. 89° 46' W. on true line
	Bet. Secs. 5 & 8
	With same Va
27.00	Enter Lower bench bears. N.E. & S.W.
40.11	Set Limestone 20×10×7 ins. 15 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on N. face, and

R. 13 W. - S. L. M.

Chs.	Made regulation mound & pits
80.23	The Cor. to Secs. 5, 6, 7 & 8.
	Sand bench
	Soil 1st rate
	Dense sage brush underground
	on 80.23 Chs.
	West on random line
	Bet. Secs. 6 & 7
	Va 18° 10' E.
4.00	Set temporary 1/4 Sec. Cor.
78.60	Intersect N. Bdy. of Township
	238 Lks. N. of Cor. to Secs. 1, 6,
	7 & 12 which is a limestone 7 x 12 x 12 ins. above ground, properly marked & with mound & pits alongside
	Thence Sum
	N. 89° 50' E. on true line
	Bet. Secs. 6 & 7
	Va 18° 10' E.
5.50	Wash arains N.
10.70	" " "
38.60	Set limestone 20 x 10 x 10 ins - 15 ins. in the ground for 1/4 Sec Cor. marked 1/4 on N. face and

Subdivisions T. 11 N.

Chs.	
	Made regulation Mound & pits
68.00	Wash drains N.
73.25	" " "
78.60	The Cor. to Secs. 5, 6, 7 & 8
	Land bench
	Soil 1st rate
	Dense sage brush undergrowth on 78.60 Chs
	Knowing from previous connections that I will fall West outside of the limit for connecting
	Town
	North on true line
	Bet. Secs. 5 & 6
	Va 18° 10' E.
40.00	Set Charred aspen post 3 ft. long 3 ins. square, 12 ins. in the ground for 1/4 Sec. Cor. Marked 1/4 S. on W. face and made regulation

R. B. W. — S. L. M.

Chs.	Mound & pits
78.35	Intersect N. By. of Township
	14.30 Chs. W. of Cor. to Secs.
	31 & 32 where I set.
	Charred Hemlock post 4 ft. long
	4 ins. square, 12 ins. in
	the ground for closing Cor. to Secs.
	5 & 6. Marked
	T. 11 N. R. 13 W. on S.E. and
	S. 6 on S.W. faces with 6
	notches on S. 5 on E. & 1 on
	W. edges with C.C. and
	made regulation mound
	& pits
	Land flat
	Soil 1st rate
	Dense sage brush & greasewood
	undergrowth on 78.35 Chs.
	May 29th 1884

General Description

About three fourths of this Township is bench & bottom land, the remaining fourth being mountainous and in the S.W. corner there is a good growth of White Sage, and Shadscale affording fine Winter Range for Stock.

Dove Creek runs South Easterly nearly through the entire township - at this season of the year it affords an abundant supply of Water. There is some fine meadow land principally in Secs. 4, 5, 11 & 14 from which a quantity of hay is cut annually. Clark has a log house and stock corral in Sec. 14 and Shurley a house barn and corral in Sec. 4

At Shirley's place there is a fine meadow inclosed by about two miles of fencing
There are springs in Sect. 3 & 10

Henry Fitzhugh
U. S. Deputy Surveyor

BOOK-A-205

U. S. SURVEYOR GENERAL'S OFFICE,

Salt Lake City, Utah, October 11th 1884

The foregoing field notes of the survey of the Subdivision Series

Township No. 11 North Range No. 13 West

Executed by Henry Fitzhugh

Under his contract of the 19th day of March 1884, in the month of May 1884, having been critically examined, the necessary corrections and explanations made, the said field notes, and the surveys they describe are hereby approved.

Fred Salomon

U. S. Surveyor General for Utah.