

**Volume**

**#**

**R0556**



# INDEX DIAGRAM

Township 12 SOUTH, Range 17 WEST

	30	27	28	27	27	26	
	81	81	80	80	80	80	
19	• 78	• 65	• 56	• 48	• 39	• 25	
	78	77	64	56	47	38	
19	• 76	• 64	• 55	• 46	• 37	• 24	
	75	74	63	54	46	36	
18	• 73	• 62	• 53	• 45	• 36	• 23	
	73	72	61	53	44	35	
16	• 71	• 60	• 52	• 43	• 34	• 22	
	70	69	60	51	42	33	
15	• 69	• 59	• 50	• 41	• 33	• 21	
	68	67	58	50	41	32	
14	• 66	• 57	• 49	• 40	• 31	• 20	
	66	57	49	40	31	20	

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES

Of the ..... Meridian,

In the State of .....

EXECUTED BY

Under special instructions dated ....., 19....., which provided  
for the surveys included under Group No. ...., approved .....  
and assignment instructions dated ....., 19.....

Survey commenced ....., 19.....

Survey completed ....., 19.....

2A

# INDEX DIAGRAM

Township 19 SOUTH, Range 6 WEST  
 141 141

139	140	127	120	112	106	99
138	138	126	119	112	105	
137	137	126	119	111	104	97
136	136	125	118	111	104	
137	135	125	117	110	103	96
134	133	124	117	109	103	
135	133	123	116	109	102	95
132	131	123	116	108	101	
133	130	122	115	108	101	94
129	128	121	114	107	100	
130	128	121	113	106	100	93
93	92	91	91	90	89	

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

# FIELD NOTES

Of the ..... Meridian,

in the State of .....

EXECUTED BY

Under special instructions dated ....., 19....., which provided  
for the surveys included under Group No. ...., approved .....  
and assignment instructions dated ....., 19.....

Survey commenced ....., 19.....

Survey completed ....., 19.....

3A

## INDEX DIAGRAM

Township 19 SOUTH, Range 7 WEST

	160	160	159	158	157	157
	196	189	182	175	168	156
	197	197	185	181	174	167
7		188	181	173	167	155
		195	187	180	173	166
18		186	179	172	165	154
		194	186	179	172	165
19		185	178	171	164	154
		193	184	177	171	163
30		192	184	177	170	162
		191	183	176	169	162
31		182	175	168	161	152
		149	149	150	151	

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

# FIELD NOTES

Of the ..... Meridian,

in the State of .....

EXECUTED BY

Under special instructions dated ....., 19....., which provided

for the surveys included under Group No. ...., approved .....

and assignment instructions dated ....., 19.....

Survey commenced ....., 19.....

Survey completed ....., 19.....

# INDEX DIAGRAM

Township 19 SOUTH, Range 8 WEST

213	261	251	244	236	226	220
261	260	251	243	235	227	263
212	259	250	242	234	228	263
259	258	249	242	233	263	18
210	258	248	241	232	213	18
257	257	248	240	232	225	262
209	256	247	240	231	224	262
256	255	246	239	231	223	
208	254	246	238	230	222	262
253	253	245	237	229	222	220
206	252	244	236	228	221	219
213	214	215	216	217	218	

5  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

# FIELD NOTES

Of the ..... Meridian,

In the State of .....

EXECUTED BY

Under special instructions dated ....., 19....., which provided  
for the surveys included under Group No. ...., approved .....  
and assignment instructions dated ....., 19.....

Survey commenced ....., 19.....

Survey completed ....., 19.....

# INDEX DIAGRAM

Township 19 SOUTH, Range 19 WEST

292	291	290	290	289	288
282 • 321 • 314 • 309 • 304 • 298 • 288					
321	320	314	309	303	298
280 • 320 • 313 • 308 • 303 • 297 • 286					
320	319	313	308	302	297
279 • 319 • 313 • 307 • 302 • 296 • 285					
318	318	312	307	301	295
278 • 317 • 312 • 306 • 301 • 295 • 284					
317	317	311	306	300	294
277 • 316 • 311 • 305 • 300 • 293 • 283					
316	315	310	305	299	293
276 • 315 • 310 • 304 • 299 • 292 • 283					
275	274	273	272	271	270

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

# FIELD NOTES

Of the ..... Meridian,

in the State of .....

EXECUTED BY

Under special instructions dated ....., 19....., which provided

for the surveys included under Group No. ...., approved .....

and assignment instructions dated ....., 19.....

Survey commenced ....., 19.....

Survey completed ....., 19.....

47

# INDEX DIAGRAM

NEVADA  
UTAH

Township 19 SOUTH, Range 20 West

						330
6	5	4	3	2	1	336
						335
7	8	9	10	11	12	335
						334
13	17	16	15	14	13	334
						332
19	20	21	22	23	24	333
						331
29	28	28	27	26	25	332
						M.P. 153 . 330
31	32	33	34	35	36	331
						M.P. 154 . 329

GPO 886119

328

M.P. 155 .

7

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

# FIELD NOTES

Of the ..... Meridian,

in the State of .....

EXECUTED BY

Under special instructions dated ....., 19....., which provided

for the surveys included under Group No. ...., approved .....

and assignment instructions dated ....., 19.....

Survey commenced ....., 19.....

Survey completed ....., 19.....

# INDEX DIAGRAM

Township 20 SOUTH , Range 8 WEST

355	393	384	376	369	363	347
<del>393</del>	<del>392</del>	<del>383</del>	<del>376</del>	<del>369</del>	<del>362</del>	
354	392	383	375	368	361	346
<del>391</del>	<del>391</del>	<del>382</del>	<del>374</del>	<del>367</del>	<del>361</del>	
352	390	381	374	367	360	345
<del>390</del>	<del>389</del>	<del>381</del>	<del>373</del>	<del>366</del>	<del>359</del>	
351	388	380	372	366	359	344
<del>388</del>	<del>387</del>	<del>379</del>	<del>372</del>	<del>365</del>	<del>358</del>	
349	387	378	371	364	357	344
<del>386</del>	<del>386</del>	<del>378</del>	<del>371</del>	<del>364</del>	<del>357</del>	
348	385	377	370	363	356	343



81

# INDEX DIAGRAM

Township 23 SOUTH, Range 1 WEST

6	5	4	3	2	1
7	8	9	10	11	12
13	17	16	15	14	13
19	20	21	22	23	24
29	29	28	27	26	25
				406	403
31	32	33	34	405	35
					402
					36
					400

SALT LAKE MERIDIAN

9  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

# FIELD NOTES

Of the \_\_\_\_\_ Meridian,

the State of \_\_\_\_\_

EXECUTED BY

Under special instructions dated \_\_\_\_\_, 19\_\_\_\_, which provided

for the surveys included under Group No. \_\_\_\_\_, approved \_\_\_\_\_

and assignment instructions dated \_\_\_\_\_, 19\_\_\_\_

Survey commenced \_\_\_\_\_, 19\_\_\_\_

Survey completed \_\_\_\_\_, 19\_\_\_\_

1A

# INDEX DIAGRAM

Township 23 SOUTH, Range 2 West

		415	4	3	2	1
	419	416				
	420					
414	421	418	9	10	11	12
	417					
	13	17	16	15	14	13
	19	20	21	22	23	24
	29	28	28	27	26	25
	31	32	33	34	35	36



OK

# INDEX DIAGRAM

Township 24 SOUTH , Range 1 WEST.....

				431	432
6	7	8	9	10 438	11 430
					437
12	13	14	15	16 436	17 429
					436
18	19	20	21	22 435	23 428
					434
24	25	26	27	28	29
30	31	32	33	34	35
36	37	38	39	40	41



11A

# INDEX DIAGRAM

Township 27 SOUTH, Range 13 WEST

	520	519	519	518	518	517
448	• 477 •	516 •	514 •	496 •	482 •	1
	477	476	513	512	495	481
447	7 475 •	465 •	511 •	494 •	479 •	12
	475	474	510	509	492	458
447	18 473 •	463 •	508 •	490 •	457 •	13
	472	472	507	505	489	455
446	19 471 •	462 •	504 •	488 •	454 •	24
	470	469	503	502	487	453
445	20 468 •	460 •	501 •	486 •	452 •	25
	468	467	500	499	485	451
444	31 466 •	459 •	498 •	484 •	449 •	26

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT



# FIELD NOTES

OF THE

DEPENDENT RESURVEY

WILLOW SPRINGS GUIDE MERIDIAN, THROUGH T<sub>s.</sub> 12 S., BETWEEN

R<sub>s.</sub> 17 AND 18 W., THE NORTH AND EAST BOUNDARIES AND SUBDIVISION

OF

T. 12 S., R. 17 W.

Of the Salt Lake Meridian,

the State of Utah

EXECUTED BY

Elliot Bird, Cadastral Engineer

Under special instructions dated May 1, 1950, which provided

for the surveys included under Group No. 374, approved May 9, 1950

and assignment instructions dated May 25, 1950.

Survey commenced July 5, 1950.

Survey completed September 8, 1950.

# INDEX DIAGRAM

Township 12 South, Range 17 West

		17	16	15	14	14	13					
		68	68	67	67	67	67					
6	6	65	5	52	4	43	3	35	2	26	1	12
	65		64		51		43		34		25	
6	7	63	8	51	9	42	10	33	11	24	12	11
	62		61		50		41		33		23	
5	18	60	17	49	16	40	15	32	14	23	18	10
	60		59		48		40		31		22	
3	19	58	20	47	21	39	22	30	23	21	24	9
	57		56		47		38		29		20	
2	20	56	29	46	28	37	27	28	26	20	25	8
	55		54		45		37		28		19	
1	31	53	32	44	33	36	34	27	35	18	36	7

851

**T. 12 S., R. 17 W.**

The history of the surveys of T. 12 S., R. 17 W., Salt Lake Meridian, Utah, is as follows.

The west boundary or Willow Spring Guide Meridian, was surveyed by T.C. Bailey in 1882 and resurveyed by A.J. Stookey in 1899. The north mile of this boundary was retraced by J.W. Dougall in 1915. The north boundary was surveyed by T.C. Bailey in 1882 and resurveyed by A.J. Stookey in 1899. The south boundary was surveyed by A.J. Stookey in 1899 and resurveyed by J.W. Dougall in 1915. The east boundary and subdivisional lines were surveyed by A.J. Stookey in 1899.

The resurvey was made at the request of the Bureau of Land Management.

Preliminary to the resurvey of the lines of the original surveys, retracements were made of all the lines except those of the south boundary and search is made for all corners and other calls of the record. Identified corners are remonumented in their original positions, lost corners are reestablished and remonumented at proportionate positions based upon the original record. The retracement data are thoroughly verified and only the true line field notes are given herein.

The survey was executed with a Buff and Buff light mountain transit serial number 18003, constructed in accordance with the standard specifications of the Bureau of Land Management. The instrument was in good condition, having been placed in satisfactory adjustment prior to beginning the survey. The instrument was tested and checked frequently during the course of the survey. Measurements are made on the slope with Chicago steel tapes, eight chains in length, graduated every link for the first 100 links and thereafter at intervals of 10 links. The vertical angle of each measurement was ascertained by a clinometer when necessary. Only the horizontal equivalents of the measurements are entered in the field note record. The tape was compared to a standard.

The directions of the lines were determined by deflection angles from true meridians determined by hour angle observations made upon line during the progress of the work.

The geographic position of the southeast corner of the township as computed from ties to United States Coast and Geodetic Survey triangulation station "Ibapah" located in sec. 31, T. 11 S., R. 13 W., is as follows.

Latitude  $39^{\circ}43'30''$  N. Longitude  $113^{\circ}42'$  W.

The mean magnetic declination was found to be  $17^{\circ}30'$  E.

Due to an extra supply of three inch survey posts by the department at numerous places the three inch posts were set for corner monuments in lieu of the one and two inch posts.

**DEPENDENT RESURVEY**  
**WILLOW SPRINGS GUIDE MERIDIAN, Ts. 12 S., Rs. 17 AND 18 W.**

Reestablishment of surveys executed by  
T.C. Bailey, Deputy Surveyor, in 1882  
and resurveyed by A.J. Stookey, Deputy  
Surveyor, in 1899.

The cor. of Ts. 12 and 13 S., Rs. 17 and 18 W., is marked by an iron post, 3 ins. in diam., set, marked, and witnessed as described in the official record.

DEPENDENT RESURVEY  
WILLOW SPRINGS GUIDE MERIDIAN, Ts. 12 S., Rs. 17 AND 18 W.

Chains

Thence, from said cor.

N.  $0^{\circ}03'$  E., bet. secs. 31 and 36.Over rolling bench land, through medium dense short undergrowth; ascend 30 ft. over general SE. slope to the  $\frac{1}{4}$  sec. cor.

25.60 Wash, 70 lks. wide, 5 ft. deep, drains SE.

40.14 The  $\frac{1}{4}$  sec. cor. of secs. 31 and 36, which is marked by a granite stone, 20 x 16 x 10 ins., firmly set, marked  $\frac{1}{4}$  on W. face.

At the cor. point:

Set an iron post, 3 ft. long, 3 ins. in diam., 27 ins. in the ground, with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ \hline S36 \quad | \quad S31 \\ \hline 1950 \end{array}$$

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

N.  $0^{\circ}13'$  W., beginning new measurement.

Ascend 60 ft. over general SE. slope to the sec. cor.

40.16 The cor. of secs. 25, 30, 31, and 36, which is marked by a granite stone, 12 x 10 x 8 ins., firmly set, marked 1 notch on S. edge and 5 notches on N. edge.

At the cor. point:

Set an iron post, 3 ft. long, 3 ins. in diam., 18 ins. in the ground to solid rock and in a mound of stone, 5 ft. base,  $1\frac{1}{2}$  ft. high, with brass cap marked
$$\begin{array}{c} T12S \\ R18W \quad R17W \\ S25 \quad | \quad S30 \\ \hline S36 \quad | \quad S31 \\ \hline 1950 \end{array}$$

Reset the stone cor. monument alongside the iron post.

Land, rolling.

Soil, sand and clay.

No timber; undergrowth of shadscale, sage, rabbit, and black brush, and greasewood.

N.  $0^{\circ}17'$  W., bet. secs. 25 and 30.Over rolling bench land through medium dense short undergrowth; ascend 100 ft. over general SE. slope to the  $\frac{1}{4}$  sec. cor.

4.70 Wash, 40 lks. wide, 4 ft. deep, drains SE.

8.60 Wash, 60 lks. wide, 4 ft. deep, drains SE.

## DEPENDENT SURVEY

WILLOW SPRINGS GUIDE MERIDIAN, T<sub>s</sub>. 12 S., R<sub>s</sub>. 17 and 18 W.

Chains

16.70 Wash, 30 lks. wide, 4 ft. deep, drains SE.

22.40 Wash, 60 lks. wide, 5 ft. deep, drains SE.

33.20 Unimproved road, bears E. and W.

34.50 Base of gradual ascent over S. rim of bench, bears E. and W.

40.14 The  $\frac{1}{4}$  sec. cor. of secs. 25 and 30, which is marked by a granite stone, 20 x 10 x 8 ins., firmly set, marked  $\frac{1}{4}$  on W. face.

At the cor. point:

Set an iron post, 3 ft. long, 3 ins. in diam., 27 ins. in the ground, with brass cap marked

$$\frac{1}{4}$$

S25	S30
-----	-----

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

N. 0°15' W., beginning new measurement.

Ascend 120 ft. over general SE. slope to the sec. cor.

4.00 Top of S. rim of bench, bears NE. and SW.

11.10 Shallow draw, drains SE.

30.50 Top of S. rim of Granite Creek, bears E. and W.

36.70 Dry channel of Granite Creek, 40 lks. wide, 4 ft. deep, drains E.

40.25 The cor. of secs. 19, 24, 25, and 30, which is marked by a granite stone, 10 x 8 x 6 ins., firmly set, marked 2 notches on S. edge and 4 notches on N. edge.

At the cor. point:

Set an iron post, 3 ft. long, 3 ins. in diam., 27 ins. in the ground, with brass cap marked

T12S	
R18W	R17W
S24	S19
S25	S30

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

Land, rolling.

Soil, deep sand and clay.

No timber; undergrowth of shadscale, sagey black, and rabbit brush, and greasewood.

N. 0°56' W., bet. secs. 19 and 24.

DEPENDENT RESURVEY  
WILLOW SPRINGS GUIDE MERIDIAN, T<sub>s</sub>. 12 S., R<sub>s</sub>. 17 AND 18 W.


Chains

Over rolling bench land, through medium dense short undergrowth; ascend 120 ft. over general SE. slope to the sec. cor.

- 6.00 Top of N. rim of Granite Creek, bears NE. and SW.; thence over bench.
- 15.30 Top of N. rim of bench, bears NE. and SW.
- 17.30 Wash, 40 lks. wide, 5 ft. deep, drains NE.
- 26.60 Shallow draw, drains NE.
- 37.30 Unimproved road, bears E. and W.
- 40.23 The  $\frac{1}{4}$  sec. cor. of secs. 19 and 24, which is marked by a granite stone, 20 x 10 x 8 ins., firmly set, marked  $\frac{1}{4}$  on W. face.

At the cor. point:

Set an iron post, 3 ft. long, 3 ins. in diam., 27 ins. in the ground, with brass cap marked



Reset the stone cor. monument alongside the iron post and raise a small mound around same.


N. 0°03' E., beginning new measurement.

Ascend 80 ft. over general SE. slope to the sec. cor.

- 5.50 Low rise, bears E. and W.
- 18.00 Wash, 20 lks. wide, 4 ft. deep, drains NE.
- 23.50 Shallow draw, drains SE.
- 35.30 Wash, 20 lks. wide, 4 ft. deep, drains SE.
- 40.27 The cor. of secs. 13, 18, 19, and 24, which is marked by a granite stone, 20 x 19 x 12 ins., firmly set, marked 3 notches on N. and S. edges.

At the cor. point:

Set an iron post, 3 ft. long, 3 ins. in diam., 27 ins. in the ground, with brass cap marked



1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

Land, rolling.

Soil, deep sand and clay.

No timber; undergrowth of shadscale, black, sage, and rabbit brush, and greasewood.

DEPENDENT RESURVEY

W. 81 WILLOW SPRINGS GUIDE MERIDIAN, T<sub>s</sub>. 12 S., R<sub>s</sub>. 17 AND 18 W.

N. 0°15' E., bet. secs. 13 and 18.

Over rolling land, through medium dense short undergrowth; ascend 60 ft. over general SE. slope to the  $\frac{1}{4}$  sec. cor.


24.00 Wash, 150 lks. wide, 6 ft. deep, drains SE.

35.20 Unimproved road, bears NW. and SE.

40.15 The  $\frac{1}{4}$  sec. cor. of secs. 13 and 18, which is marked by a granite stone, 18 x 12 x 8 ins., firmly set, marked  $\frac{1}{4}$  on W. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked



Reset the stone cor. monument alongside the iron post and raise a mound of stone, 4 ft. base, 9 ins. high, around same.

N. 0°10' E., beginning new measurement.

Ascend 90 ft. over general SE. slope to the sec. cor.

2.50 Wash, 20 lks. wide, 5 ft. deep, drains S. 80° E.

9.70 Unimproved road, bears E. and W.

14.70 Concrete pipe line which diverts the water from Granite Creek, flows E.


15.80 Unimproved road, bears NW. to a ranch and SE. to the County road.

25.40 Shallow draw, drains E.

40.12 The cor. of secs. 7, 12, 13, and 18, which is marked by a granite stone, 18 x 12 x 8 ins., firmly set, marked 4 grooves on S. face and 2 grooves on N. face.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked



Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

Land, rolling.

Soil, deep clay, gravel, and sand.

No timber; undergrowth of shadscale, greasewood, sage, black, and rabbit brush.

DEPENDENT RESURVEY  
WILLOW SPRINGS GUIDE MERIDIAN, T<sub>s</sub>. 12 S., R<sub>s</sub>. 17 AND 18 W.

Chains

N. 0°05' W., bet. secs. 7 and 12.

Over rolling bench land, through medium dense short undergrowth; ascend 60 ft. over general SE. slope to the  $\frac{1}{4}$  sec. cor.

40.16

The  $\frac{1}{4}$  sec. cor. of secs. 7 and 12, which is marked by a granite stone, 16 x 8 x 8 ins., firmly set, marked  $\frac{1}{4}$  on W. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 ins. in diam., 27 ins. in the ground, with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ S12 \mid S7 \\ 1950 \end{array}$$

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

N. 0°06' W., beginning new measurement.

Ascend 60 ft. over general SE. slope to the sec. cor.

15.20

Wash, 40 lks. wide, 4 ft. deep, drains SE.

25.60

Shallow draw, drains SE.

32.50

Shallow draw, drains NE.

40.16

The cor. of secs. 1, 6, 7, and 12, which is marked by a granite stone, 14 x 10 x 8 ins., firmly set, marked 5 notches on S. edge and 1 notch on N. edge.

At the cor. point:

Set an iron post, 3 ft. long, 3 ins. in diam., 27 ins. in the ground, with brass cap marked

$$\begin{array}{c} T12S \\ R18W \mid R17W \\ S1 \mid S6 \\ \hline S12 \mid S7 \\ 1950 \end{array}$$

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

Land, rolling.

Soil, deep clay, gravel, and sand.

No timber; undergrowth of shadscale, sage, black, and rabbit brush.

N. 0°01' E., bet. secs. 1 and 6.

Over rolling bench land, through medium dense short undergrowth; ascend 70 ft. over general SE. slope to the  $\frac{1}{4}$  sec. cor.

11.30

Wash, 40 lks. wide, 4 ft. deep, drains S. 80° E.

## DEPENDENT RESURVEY

WILLOW SPRINGS GUIDE MERIDIAN, Ts. 12 S., Rs. 17 AND 18 W.

Chain

- 23.30 Shallow draw, drains S. 80° E.  
 29.30 Shallow draw, drains E.  
 31.00 Shallow draw, drains E.  
 35.40 Shallow draw, drains E.  
 40.22 The  $\frac{1}{4}$  sec. cor. of secs. 1 and 6, which is marked by a granite stone, 15 x 8 x 6 ins., firmly set, marked  $\frac{1}{4}$  on W. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$$\frac{1}{4}$$

S1	S6
----	----

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

N. 0°20' W., beginning new measurement.

- 7.60 Shallow draw, drains E.  
 18.00 Low spur, slopes NE.  
 23.00 Base of ascent of 220 ft. over SE. slope of broken, ledgy, mountainous land; enter scattered juniper and pinon timber, bears NE. and SW.  
 43.80 Rocky gulch, drains SE.  
 47.50 Top of ascent on rocky spur, slopes E.; descend 70 ft. to cor.  
 53.04 The cor. of Ts. 11 and 12 S., R. 17 W., which is marked by an iron post, 3 ins. in diam., set, marked, and witnessed as described in the official record.

Land, rolling bench on S. south; broken and mountainous on N. portion.

Soil, gravel, clay, and sand.

Timber, scattered juniper and pinon on N. portion of mile; undergrowth of shadscale, greasewood, sage, black, and rabbit brush.

DEPENDENT RESURVEY OF EAST BOUNDARY, T. 12 S., R. 17 W.

Reestablishment of surveys executed  
 by A.J. Stookey, Deputy Surveyor,  
 in 1899.

The cor. of Ts. 12 and 13 S., Rs. 16 and 17 W., is marked by an iron post, 3 ins. in diam., set, marked, and witnessed, as described in the official record.

Thence, from the above cor.

N. 0°05' W., bet. secs. 31 and 36.

## DEPENDENT RESURVEY OF EAST BOUNDARY, T. 12 S., R. 17 W.

Chains

Over rolling bench land., through medium dense short undergrowth.

39.75

The  $\frac{1}{4}$  sec. cor. of secs. 1 and 36, which is marked by a volcanic stone, 20 x 10 x 8 ins., firmly set, marked  $\frac{1}{4}$  on W. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ \text{S36} \mid \text{S31} \end{array}$$

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

N. 0°02' W., beginning new measurement.

Continue over rolling bench land.

39.44

The cor. of secs. 25, 30, 31, and 36, which is marked by a cobble stone, 18 x 10 x 10 ins., firmly set, marked 1 groove on S. face and 5 grooves on N. face.

At the cor. point, on low sandy rise, bears E. and W.

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked

$$\begin{array}{c} \text{T12S} \\ \text{R17W} \mid \text{R16W} \\ \text{S25} \mid \text{S30} \end{array}$$

$$\text{S36} \mid \text{S31}$$

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

Land, rolling.

Soil, deep sand and clay loam.

No timber; undergrowth of shadscale, sage, rabbit, and black brush.

N. 0°03' W., bet. secs. 25 and 30.

Over rolling desert land, through medium dense short undergrowth.

40.51

The  $\frac{1}{4}$  sec. cor. of secs. 25 and 30, which is marked by a cobble stone, 12 x 10 x 6 ins., firmly set, marked  $\frac{1}{4}$  on W. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ \text{S25} \mid \text{S30} \end{array}$$

1950

## DEPENDENT RESURVEY OF EAST BOUNDARY, T. 12 S., R. 17 W.

Chains

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

N. 0°03' W., beginning new measurement.

Continue over rolling desert land.

32.50 Unimproved road, bears NE. to Fish Springs and SW. to Trout Creek.

37.60 Wash, 24 lks. wide, 4 ft. deep, drains W.

40.16 The cor. of secs. 19, 24, 25, and 30, which is marked by a volcanic stone, 18 x 10 x 4 ins., firmly set, marked 2 grooves on S. edge and 4 grooves on N. edge.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked

T128	
R17W	R16W
S24	S19
-----	
S25	S30

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

Land, rolling desert.

Soil, deep sand and clay loam.

No timber; undergrowth of shadscale, greasewood, sage, and black brush.

N. 0°02' W., bet. secs. 19 and 24.

Over rolling desert land, through medium dense short undergrowth.

34.10 Wash, 60 lks. wide, 6 ft. deep, drains NE.

40.20 The  $\frac{1}{2}$  sec. cor. of secs. 19 and 24, which is marked by a volcanic stone, 12 x 8 x 3 ins., firmly set, marked  $\frac{1}{2}$  on W. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$\frac{1}{2}$	
S24	S19

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

N. 0°04' W., beginning new measurement.

Continue over rolling desert land.

## DEPENDENT RESURVEY OF THE EAST BOUNDARY, T. 12 S., R. 17 W.

- Chains  
16.00 Dim unimproved road, bears NE. and SW.
- 29.40 Enter barren clay flat, bears NE. and SW.
- 40.18 The cor. of secs. 13, 18, 19, and 24, which is marked by quartzite stone, 14 x 8 x 6 ins., firmly set, marked 3 grooves on N. and S. face.
- At the cor. point; at NE. edge of barren clay flat, bears SE. and NW.
- Set an iron post, 3 ft. long, 3 ins. in diam., 27 ins. in the ground, with brass cap marked
- |      |      |
|------|------|
| T12S |      |
| R17W | R16W |
| S13  | S18  |
| S24  | S19  |
- 1950
- Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.
- Land, rolling desert.  
Soil, deep clay and sand loam.  
No timber; undergrowth of shadscale, greasewood, sage, and black brush.
- 
- N. 0°03' W., bet. secs. 13 and 18.
- Over rolling desert land, through medium dense short undergrowth.
- 40.16 The  $\frac{1}{4}$  sec. cor. of secs. 13 and 18, which is marked by a quartzite stone, 12 x 10 x 4 ins., firmly set, marked  $\frac{1}{4}$  on W. face.
- At the cor. point:
- Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked
- |               |     |
|---------------|-----|
| $\frac{1}{4}$ |     |
| S13           | S18 |
- 1950
- Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.
- 
- N. 0°03' W., beginning new measurement.
- Continue over rolling desert land.
- 8.90 Wash, 40 lks. wide, 6 ft. deep, drains SW.
- 40.19 The cor. of secs. 7, 12, 13, and 18, which is marked by a quartzite stone, firmly set, marked 4 grooves on S. face and 2 grooves on N. face.
- At the cor. point:
- Set an iron post, 3 ft. long, 3 ins. in diam., 27 ins. in

DEPENDENT RESERVE OF EAST BOUNDARY, T. 12 S., R. 17 W.

Chains  
base 7800

the ground, with brass cap marked

T12S	
R17W	R16W
S12	S7
1950	
S13	S18

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

Land, rolling desert.  
Soil, deep sand and clay loam.  
No timber; undergrowth of shadscale, greasewood, sage, and black brush.

N. 0°03' W., bet. secs. 7 and 12.

Over rolling desert land, through medium dense short undergrowth.

40.22

The  $\frac{1}{4}$  sec. cor. of secs. 7 and 12, which is marked by a quartzite stone, 14 x 6 x 3 ins., firmly set, marked  $\frac{1}{4}$  on W. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$\frac{1}{4}$	
S12	S7
1950	

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

N. 0°03' W., beginning new measurement.

Continue over rolling desert land.

9.40

Shallow draw, drains NE.

24.10

Dim unimproved road, bears SW. and NE.

31.40

Unimproved road, bears NW. and SE.

40.22

The cor. of secs. 1, 6, 7, and 12, which is marked by a quartzite stone, 10 x 10 x 6 ins., firmly set, marked 5 grooves on S. face and 1 groove on N. face.

At the cor. point:

Set an iron post, 3 ft. long, 3 ins. in diam., 27 ins. in the ground, with brass cap marked

T12S	
R17W	R16W
S1	S6
1950	
S12	S7

1950

Chains

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

Land, rolling desert.  
Soil, deep sand and clay loam.  
No timber; undergrowth of shadscale and greasewood, sage, and black brush.

N. 0°03' W., bet. secs. 1 and 6.


Over rolling desert land and sand dunes, through medium dense short undergrowth.

40.19

The 1/4 sec. cor. of secs. 1 and 6, which is marked by a quartzite stone, 16 x 8 x 6 ins., firmly set, marked 1/4 on W. face.

At the cor. point:

Set an iron post, 3 ft. long, 3 ins. in diam., 27 ins. in the ground, with brass cap marked



Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

N. 0°02' W., beginning new measurement.

Continue over rolling desert land.

4.70



County road, graded, bears SE. to Delta, Utah and NW. to Callao, Utah.

55.42

The cor. of Ts. 11 and 12 S., Rs. 16 and 17 W., which is marked by a quartzite stone, 20 x 12 x 10 ins., firmly set, marked 6 grooves on all four faces.

At the cor. point:

Set an iron post, 3 ft. long, 3 ins. in diam., 27 ins. in the ground, with brass cap marked



Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

Land, rolling desert.  
Soil, deep clay and sand loam.  
No timber; undergrowth of sagebrush, shadscale, greasewood, and black brush.

W. T. DEPENDENT RESURVEY OF NORTH BOUNDARY, T. 12 S., R. 17 W.

Chains

Reestablishment of surveys executed by T.C. Bailey, Deputy Surveyor, in 1882 and retraced by A.J. Stockey, Deputy Surveyor, in 1899.

From the cor. of Ts. 11 and 12 S., Rs. 16 and 17 W..

S. 89°42' W., along the S. bdy. of sec. 36, T. 11 S., R. 17 W.

Over rolling desert land, through medium dense short undergrowth.

12.50 Unimproved road, bears N. and S.

36.10 Low sandy ridge, bears NW. and SE.

41.60 The  $\frac{1}{4}$  sec. cor. of sec. 36, which is marked by a cobble stone, 12 x 10 x 6 ins., firmly set, marked  $\frac{1}{4}$  on N. face.

At the cor. point:

Set an iron post, 3 ft. long, 3 ins. in diam., 27 ins. in the ground, with brass cap marked

$\frac{1}{4}$  S36

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

S.89°37' W., beginning new measurement.

Continue over rolling desert land.

6.50 Low ridge, bears NW. and SE.

10.70 Shallow draw, drains SE.

23.40 County road, graded, bears NW. to Callao, Utah and SE. to Delta, Utah.

38.50 The closing cor. of secs. 1 and 2, T. 12 S., R. 17 W.

41.55 The cor. of secs. 35 and 36, which is marked by a quartzite stone, 10 x 8 x 4 ins., firmly set, marked 1 groove on E. face and 5 grooves on W. face.

At the cor. point:

Set an iron post, 3 ft. long, 3 ins. in diam., 27 ins. in the ground, with brass cap marked

T11S | R17W  
S35 | S36

S2

T12S R17W

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

Land, rolling.

Soil, deep sand and clay.

No timber; undergrowth of shadscale, greasewood and sagebrush.

## DEPENDENT RESURVEY OF NORTH BOUNDARY, T. 12 S., R. 17 W.

Chains

S. 89°49' W., along the S. bdy. of sec. 35.

Over rolling bench land, through medium dense short undergrowth.

40.50 Top of NE. rim of bench, bears NW. and SE.

41.78 The  $\frac{1}{4}$  sec. cor. of sec. 35, which is marked by a quartzite stone, 10 x 6 x 4 ins., firmly set, marked  $\frac{1}{4}$  on N. face.

At the cor. point:

Set an iron post, 3 ft. long, 3 ins. in diam., 27 ins. in the ground, with brass cap marked

 $\frac{1}{4}$  S35

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

S. 89°53' W., beginning new measurement.

Continue over rolling bench land.

35.60 The closing cor. of secs. 2 and 3, T. 12 S., R. 17 W.

41.54 The cor. of secs. 34 and 35, which is marked by a quartzite stone, 16 x 8 x 4 ins., firmly set, marked 2 grooves on E. face and 4 grooves on W. face.

At the cor. point:

Set an iron post, 3 ft. long, 3 ins. in diam., 27 ins. in the ground, with brass cap marked

T11S R17W
S34   S35

S3

T12S R17W

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

Land, rolling.

Soil, deep sand and clay loam.

No timber; undergrowth of shadscale, greasewood, sage, and black brush.

S. 89°29' W., along the S. bdy. of sec. 34.

Over rolling bench land, through medium dense short undergrowth.

34.70 Low rise, bears NW. and SE.

41.60 The  $\frac{1}{4}$  sec. cor. of sec. 34, which is marked by a quartzite stone, 10 x 8 x 6 ins., firmly set, marked  $\frac{1}{4}$  on N. face.

At the cor. point:

Set an iron post, 3 ft. long, 3 ins. in diam., 27 ins. in

DEPENDENT RESURVEY OF NORTH BOUNDARY T. 12 S., R. 17 W.

Chain

the ground, with brass cap marked

1/4 S34

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

S. 89°24' W., beginning new measurement.

Continue over rolling bench land.

32.78 The closing cor. of secs. 3 and 4, T. 12 S., R. 17 W.

41.53 The cor. of secs. 33 and 34, which is marked by a quartzite stone, 10 x 8 x 6 ins., firmly set, marked 3 grooves on E. and W. faces.

At the cor. point:

Set an iron post, 3 ft. long, 3 ins. in diam., 27 ins. in the ground, with brass cap marked

T11S R17W  
S33 S34

Sh  
T12S R17W

1950

Reset the stone cor. monument alongside the iron post and raise a mound of stone, 4 ft. base, 9 ins. high, around same.

Land, rolling.

Soil, deep sand and clay loam.

No timber; undergrowth of shadscale, greasewood, sage, and black brush.

S. 89°49' W., along the S. bdy. of sec. 33.

Over rolling bench land, through medium dense short undergrowth; ascend 80 ft. over general E. slope to the 1/4 sec. cor.

32.30 The NE. cor. of a barren clay flat to the SW.

41.48 The 1/4 sec. cor. of sec. 33, which is marked by a quartzite stone, 8 x 6 x 6 ins., firmly set, marked 1/4 on N. face.

At the cor. point:

Set an iron post, 3 ft. Long, 3 ins. in diam., 27 ins. in the ground, with brass cap marked

1/4 S35

1950

Reset the stone cor. monument alongside the iron post and raise a mound of stone, 4 ft. base, 9 ins. high, around the cor. monument.

## DEPENDENT RESURVEY OF THE NORTH BOUNDARY, T. 12 S., R. 17 W.

Chains

Cor. set at the NW. cor. of a barren clay flat which extends S., about 8.00 chs. dist.

S. 89°31' W., beginning new measurement.

Continue over rolling bench land.

- 13.80 The NE. point of bench to the SW., slopes NE.  
 18.90 Large shallow draw, drains NE.  
 21.80 Top of E. rim of bench, bears NE. and SE.; thence over rolling top of higher bench.  
 25.60 Shallow draw, drains S. 80° E.  
 29.87 The closing cor. of secs. 4 and 5, T. 12 S., R. 17 W.  
 30.70 Shallow draw near head, drains S. 80° E.  
 40.73 The cor. of secs. 32 and 33, which is marked by a quartzite stone, firmly set, 16 x 8 x 6 ins., marked 4 grooves on E. face and 2 grooves on W. face.

At the cor. point:

Set an iron post, 3 ft. long, 3 ins. in diam., 27 ins. in the ground, with brass cap marked

T11S R17W	
S32	S33

S5  
T12S R17W

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

Land, rolling.

Soil, deep sand and clay loam.

No timber; undergrowth of shadscale, greasewood, sage, and black brush.

S. 89°45' W., along the S. bdy. of sec. 32.

Over rolling bench land, through medium dense short undergrowth.

- 13.60 Unimproved road, bears NE. and SW.  
 20.30 County road, graded, bears N. to Callao, Ut. and S. to Trout Creek, Ut.  
 41.38 The  $\frac{1}{4}$  sec. cor. of sec. 32, which is marked by a quartzite stone, 10 x 8 x 4 ins., firmly set, marked  $\frac{1}{4}$  on N. face.

At the cor. point:

Set an iron post, 3 ft. long, 3 ins. in diam., 27 ins. in the ground, with brass cap marked.

$\frac{1}{4}$  S32

1950

## DEPENDENT RESURVEY OF NORTH BOUNDARY, T. 12 S., R. 17 W.

Chains

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

S. 89°51' W., beginning new measurement.

Continue over rolling bench land,

28.26 The closing cor. of secs. 5 and 6, T. 12 S., R. 17 W.

35.30 Unimproved road, bears NW. and SE.

40.10 The cor. of secs. 31 and 32, which is marked by a cobble stone, 12 x 12 x 6 ins., firmly set, marked 5 grooves on E. face and 1 groove on W. face.

At the cor. point:

Set an iron post, 3 ft. long, 3 ins. in diam., 27 ins. in the ground, with brass cap marked

T11S	R17W
S31	S32

S6

T12S R17W

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

Land, rolling.

Soil, deep sand and clay loam.

No timber; undergrowth of shadscale, greasewood, sage, and black brush.

N. 89°33' W., along the S. bdy. of sec. 31.

Over rolling bench land, through scattered short undergrowth; ascend 80 ft. over general E. slope to the  $\frac{1}{4}$  sec. cor.

14.10 Dry channel of Cedar Creek, 40 lks. wide, 6 ft. deep, in large draw, drains SE.

38.50 Rocky draw, drains NE.

41.54 Point for the  $\frac{1}{4}$  sec. cor. of sec. 31 at proportionate distance; there is no remaining evidence of the original  $\frac{1}{4}$  sec. cor.

Set an iron post, 3 ft. long, 1 in. in diam., 18 ins. in the ground to solid rock and in a mound of stone, 6 ft. base, 1 $\frac{1}{2}$  ft. high, with brass cap marked

$\frac{1}{4}$  S31

1950

Ascend 230 ft. over general E. slope to the township cor.

42.00 Recross dry channel of Cedar Creek, drains NE.

54.00 Recross bend in dry channel of Cedar Creek, drains S. 80°E. from S. 80° W.

## DEPENDENT RESURVEY OF NORTH BOUNDARY' T. 12 S., R. 17 W.

## Chains

- 77.10 Recross dry channel of Cedar Creek, drains S. 80° E.
- 79.30 Canal, 15 lks. wide, 3 ft. deep, with stream from Cedar Creek, 10 lks. wide, 6 ins. deep, flows S. 70° E.; ascend over rocky E. slope of base of high mountains land to the W.
- 82.50 The cor. of Ts: 11 and 12 S., R. 17 W.
- Land, broken and rolling.  
Soil, shallow clay and sand with a rocky surface.  
Timber, scattered juniper and cottonwood along channel of Cedar Creek; undergrowth of shadscale, greasewood, sage, and black brush.

## DEPENDENT RESURVEY OF SUBDIVISION, T: 12 S., R. 17 W.

Reestablishment of surveys executed by  
A.J. Stookey, Deputy Surveyor, in 1899.

The cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the township, is marked by an iron post, 3 ins. in diam., set, marked, and witnessed as described in the official record.

Thence, from the above cor.

N. 0°06' E., bet. secs. 35 and 36.

Over rolling bench land, through medium dense short undergrowth.

- 39.94 The  $\frac{1}{4}$  sec. cor. of secs. 35 and 36, which is marked by a volcanic stone, 20 x 12 x 4 ins., firmly set, marked  $\frac{1}{4}$  on W. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ \text{S35} \mid \text{S36} \\ 1950 \end{array}$$

Reset the stone cor. monument alongside the iron post and raise a mound of stone, 4 ft. base, 9 ins. high, around same.

N. 0°05' E., beginning new measurement.

Continue over rolling bench land.

- 16.00 Top of NW. rim of bench, 20 ft. high, bears NE. and SW.
- 34.00 Unimproved road, bears NE. to Fish Springs and SW. to Trout Creek.
- 39.92 The cor. of secs. 25, 26, 35, and 36, which is marked by volcanic stone, 18 x 12 x 12 ins., firmly set, marked 1 notch on E. and S. edges.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in

DEPENDENT RESURVEY OF SUBDIVISION, T. 12 S., R. 17 W.

Chains

the ground, with brass cap marked

T12S R17W	
S26	S25
S35	S36

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

Land, rolling.

Soil, deep sand and clay loam.

No timber; undergrowth of shadscale and greasewood, sage, and black brush.

From the cor. of secs. 25, 30, 31, and 36, on the east boundary of the township.

N. 89°24' W., bet. secs. 25 and 36.

Over rolling bench land, through medium dense short undergrowth.

8.90 Shallow draw, drains N.

26.20 Wide shallow draw, drains N.

32.50 Wide shallow draw, drains N.

40.16 The  $\frac{1}{4}$  sec. cor. of secs. 25 and 36, which is marked by a volcanic stone, 12 x 10 x 8 ins., firmly set, marked  $\frac{1}{4}$  on N. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$\frac{1}{4}$	S25
	S36

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

N. 89°27' W., beginning new measurement.

Continue over rolling bench land.

16.00 Shallow draw, drains N.

22.00 Top of NW. rim of low bench, 30 ft. high, bears N. and SW.

24.00 Base of bench, bears N. and SW.

31.50 Unimproved road, bears NE. to Fish Springs and SW. to Trout Creek.

40.04 The cor. of secs. 25, 26, 35, and 36.

Land, rolling.

Soil, deep sand and clay.

No timber; undergrowth of shadscale and black brush.

## DEPENDENT RESURVEY OF SUBDIVISION, T. 12 S., R. 17 W.

Chains

North, bet. secs. 25 and 26.

Over nearly level clay flat through medium dense short undergrowth.

27.80 Enter low sand dunes, bears NE. and SW.

40.14 The  $\frac{1}{4}$  sec. cor. of secs. 25 and 26, which is marked by a volcanic stone, 12 x 10 x 6 ins., firmly set, marked  $\frac{1}{4}$  on W. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$$\frac{1}{4}$$

S26	S25
1950	

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

N. 0°03' E., beginning new measurement.

Continue over low sand dunes.

2.10 Fence, bears N. 36°30' E. and S. 36°30' W.

28.00 Leave sand dunes and enter nearly level clay flat, bears NE. and SW.

40.19 The cor. of secs. 23, 24, 25, and 26, which is marked by a volcanic stone, 16 x 12 x 12 ins., firmly set, marked 2 notches on S. edge and 1 notch on E. edge.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked

T12S	R17W
S23	S24
S26	S25
1950	

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

Land, nearly level clay flat and rolling sand dunes.  
Soil, clay and sand.  
No timber; undergrowth of shadscale, greasewood, and black brush.

From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the township.

N. 89°42' W., bet. secs. 24 and 25.

Over nearly level clay flat through medium dense short undergrowth.

## DEPENDENT RESURVEY OF SUBDIVISION, T. 12 S., R. 17 W.

Chains

- 17.50 Enter barren clay flat, bears NW., about 7.00 chs. dist. and S., about 5.00 chs. dist.
- 25.00 Leave same, bears NE., about 7.00 chs. dist., and SW., about 7.00 chs. dist.; thence over nearly level clay flat through medium dense short undergrowth.
- 40.05 The  $\frac{1}{4}$  sec. cor. of secs. 24 and 25, which is marked by a volcanic stone, 14 x 12 x 6 ins., firmly set, marked  $\frac{1}{4}$  on N. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$$\frac{1}{4} \frac{S24}{S25}$$

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

N. 89°41' W., beginning new measurement.

Continue over nearly level clay flat.

- 12.50 Fence, bears N, 36°30' E., and S. 36°30' W.

- 40.08 The cor. of secs. 23, 24, 25, and 26.

Land, nearly level clay flat.

Soil, deep clay.

No timber; undergrowth of shadscale and greasewood.

N. 0°05' E., bet. secs. 23 and 24.

Over nearly level clay flat through medium dense short undergrowth.

- 34.00 Enter rolling sand hills, bears N. 5° E. and S. 5° W.

- 40.18 The  $\frac{1}{4}$  sec. cor. of secs. 23 and 24, which is marked by a volcanic stone, 18 x 12 x 6 ins., firmly set, marked  $\frac{1}{4}$  on W. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$$\frac{1}{4} \frac{S23}{S24}$$

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

N. 0°03' E., beginning new measurement.

Continue over rolling land.

## DEPENDENT RESURVEY OF SUBDIVISION, T. 12 S., R. 17 W.

Chains

1.80 Unimproved road, bears NE. and SW.

6.20 Unimproved road, bears NE. and SW.

15.90 Fence, bears E. and W.

40.16 The cor. of secs. 13, 14, 23, and 24, which is marked by a volcanic stone, 16 x 12 x 12 ins., firmly set, marked  $\frac{3}{4}$  notches on S. edge and 1 notch on E. edge.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked

T12S	R17W
S14	S13
S23	S24

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

Land, rolling and level.

Soil, deep clay and sand.

No timber; undergrowth of shadscale and greasewood.

From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the township.

N. 89°43' W., bet. secs. 13 and 24.

Over barren clay flat void of vegetation.

40.09 The  $\frac{1}{4}$  sec. cor. of secs. 13 and 24, which is marked by a volcanic stone, 10 x 8 x 6 ins., firmly set, marked  $\frac{1}{4}$  on N. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$\frac{1}{4}$	S13
	S24

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

N. 89°41' W., beginning new measurement.

Continue over barren clay flat.

18.40 Unimproved road, bears NE. and SW.

22.40 Leave barren clay flat and enter rolling sandy land, bears NE. and SW.

40.03 The cor. of secs. 13, 14, 23, and 24.

Land, nearly level clay flat and rolling sandy land.

## DEPARTMENT RESURVEY OF SUBDIVISION, T. 12 S., R. 17 W.

Chains

Soil, deep clay.  
No timber; undergrowth of shadscale and greasewood on W. portion of mile.

N. 0°03' E., bet. secs. 13 and 14.

Over rolling desert land, through medium dense short undergrowth.

15.50 Dim unimproved road, bears NW. and SE.

40.14 The  $\frac{1}{4}$  sec. cor. of secs. 13 and 14, which is marked by a volcanic stone, 16 x 12 x 8 ins., firmly set, marked  $\frac{1}{4}$  on W. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$\frac{1}{4}$   
 S14 | S13  
 1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

N. 0°02' E., beginning new measurement.

Continue over rolling land.

27.20 Base of higher bench to the N., bears NE. and SW.; ascend 90 ft. over general S. slope to the sec. cor.

37.60 Shallow draw, drains E.

40.20 The cor. of secs. 11, 12, 13, and 14, which is marked by a volcanic stone, 12 x 12 x 10 ins., firmly set, marked  $\frac{1}{4}$  notches on S. edge and 1 notch on E. edge.

At the cor. point:

Set an iron post, 3 ft. long,  $\frac{1}{2}$  ins. in diam., 27 ins. in the ground, with brass cap marked

T12S R17W  
 S11 | S12  
 S14 | S13

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

Land, rolling.

Soil, deep sand and clay.

No timber; undergrowth of shadscale and greasewood, sage, and black brush.

From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the township.

DEPENDENT RESURVEY OF SUBDIVISION, T. 12 S., R. 17 W.

Chains

N. 89°44' W., bet. secs. 12 and 13.

Over rolling top of bench through medium dense short undergrowth.

21.80 Road, bears N. and S., at the top of rim of bench, bears NW. and SE.; thence along S. face of bench.

28.40 Shallow draw, drains SE.

32.40 Shallow draw, drains S.

40.05 The 1/4 sec. cor. of secs. 12 and 13, which is marked by a volcanic stone, 12 x 10 x 8 ins., firmly set, marked 1/4 on N. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

S12  
1/4  
S13  
1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

N. 89°45' W., beginning new measurement.

Continue along S. face of bench to the N.

40.01 The cor. of secs. 11, 12, 13, and 14.

Land, rolling.  
Soil, deep sand and clay.  
No timber; undergrowth of shadscale, greasewood, sage, and black brush.

N. 0°02' W., bet. secs. 11 and 12.

Over rolling S. face of bench land, through medium dense short undergrowth; ascend 60 ft. over general S. slope to top of rim of bench.

0.70 Low sandy spur, slopes SE.

7.90 Shallow draw, drains E.

24.40 Dim unimproved road, bears NE. and SW.

33.90 Top of SE. rim of bench, bears NE. and SW.; thence over rolling top of bench.

40.22 The 1/4 sec. cor. of secs. 11 and 12, which is marked by a granite stone, 16 x 14 x 6 ins., firmly set, marked 1/4 on N. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

## DEPENDENT RESURVEY OF SUBDIVISION, T. 12 S., R. 17 W.

Chains

 $\frac{1}{4}$   
 S11 | S12

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

N. 0°01' E., beginning new measurement.

Continue over rolling bench land.

- 2.20 Short shallow draw, drains E.  
 4.80 Short shallow draw, drains E.  
 29.20 Top of NE. rim of bench, bears NW. and SE.; descend 40 ft. to base of bench.  
 32.20 Base of bench, bears NW. and SE.  
 40.15 The cor. of secs. 1, 2, 11, and 12, which is marked by a volcanic stone, 18 x 12 x 8 ins., firmly set, marked 5 notches on S. edge and 1 notch on E. edge.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked

T12S	R17W
S2	S1
S11	S12

1950

Reset the stone cor. monument alongside the iron post and raise a mound of stone, 4 ft. base, 9 ins. high, around same.

Land, rolling.

Soil, deep sand and clay.

No timber; undergrowth of shadscale, greasewood, sage, and black brush.

From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the township.

N. 89°49' W., bet. secs. 1 and 12.

Over rolling bench land, through medium dense short undergrowth.

- 1.30 Low sand rise, bears N. and S.  
 4.40 Unimproved road, bears N. and S.  
 10.40 Unimproved road, bears N. and S.  
 39.97 The  $\frac{1}{4}$  sec. cor. of secs. 1 and 12, which is marked by a cobble stone, 12 x 10 x 8 ins., firmly set, marked  $\frac{1}{4}$  on N. face.

At the cor. point:

## DEPENDENT RESURVEY OF SUBDIVISION, T. 12 S., R. 17 W.

Chains

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$$\frac{1}{4} \frac{S1}{S12}$$

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

N. 89°48' W., beginning new measurement.

Continue over rolling bench land.

40.09 The cor. of secs. 1, 2, 11, and 12.

Land, rolling.

Soil, deep sand and clay.

No timber; undergrowth of shadscale, greasewood, sage, and black brush.

N. 0°05' W., bet. secs. 1 and 2.

Over rolling top of bench land, through medium dense short undergrowth,

40.19 The  $\frac{1}{4}$  sec. cor. of secs. 1 and 2, which is marked by a volcanic stone, 12 x 8 x 6 ins., firmly set, marked  $\frac{1}{4}$  on W. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$$\frac{1}{4} \frac{S2}{S1}$$

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

N. 0°05' W., beginning new measurement.

Continue over rolling bench land.

54.66 The closing cor. of secs. 1 and 2, on the N. bdy. of the township, which is marked by a volcanic stone, 12 x 10 x 8 ins., firmly set, marked 1 notch on E. edge, 5 notches on W. edge, and CC on S. face.

At the cor. point:

Set an iron post, 3 ft. long, 3 ins. in diam., 27 ins. in the ground, with brass cap marked

$$\frac{T11S R17W}{S36}$$

$$\frac{S2}{T12S R17W}$$

C C

1950

DEPENDENT RESURVEY OF SUBDIVISION, T. 12 S., R. 17 W.

Chains

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

From this closing cor., the cor. of secs. 35 and 36, T. 11 S., R. 17 W., bears S. 89°37' W., 3.05 chs. dist.

Land, rolling.

Soil, deep sand and clay.

No timber; undergrowth of shadscale, greasewood, sage, and black brush.

From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the township, which is marked by an iron post, 3 ins. in diam., set, marked, and witnessed, as described in the official record.

N. 0°05' E., bet. secs. 34 and 35.


Over rolling bench land, through medium dense short undergrowth.

20.70 Junction of road from the Sharp's Ranch to the N., with road bearing N. 80° E. to Fish Springs, and S. 80° W. to Trout Creek.

20.75 The SE. cor. of fences bearing N. and W.; thence along fence line at the W. side of road bearing N.

40.05 Point for the 1/4 sec. cor. of secs. 34 and 35 at proportionate distance; there is no remaining evidence of the original 1/4 sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap marked



Set a juniper post, 5 ft. long, 4 ins. in diam., and deposit a lava stone, 10 x 5 x 4 ins., alongside the cor. monument.


Cor. set in fence line bearing N. and S.

58.10 From this point, Sharp's Ranch House, bears West, 3.50 chs. dist.; thence along fence line with cultivated land to the E. and W. of same.

60.70 End of fence from the S. at the junction of fences bearing E. and W.; continue along W. side of road with cultivated land to the E. and W. of same.

80.10 Point for the cor. of secs. 26, 27, 34, and 35, at proportionate distance; there is no remaining evidence of the original sec. cor.

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked



1950

## DEPENDENT RESURVEY OF SUBDIVISION, T. 12 S. R. 17 W.

Chains

Set a pine post, 10 ft. long, 10 ins. in diam., alongside the iron post. Cor. set in alfalfa field at the W. side of road bearing N. and S.

Land, rolling.

Soil, deep clay and sand.

No timber; undergrowth of shadscale and greasewood on uncultivated portion of mile.

From the cor. of secs. 25, 26, 35, and 36.

N.  $89^{\circ}49'$  W., bet. secs. 26 and 35.

Over rolling desert land, through medium dense short undergrowth.

37.70 Fence, bears N. and S.

40.19 The  $\frac{1}{4}$  sec. cor. of secs. 26 and 35, which is marked by a volcanic stone, 12 x 10 x 6 ins., firmly set, marked  $\frac{1}{4}$  on N. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$$\begin{array}{r} S26 \\ \frac{1}{4} \text{---} \\ S35 \end{array}$$

1950

Reset the stone cor. monument with a juniper post, 8 ft. long, 5 ins. in diam., alongside the iron post.

N.  $89^{\circ}39'$  W., beginning new measurement.

Continue over rolling land.

27.00 Fence, bears NE., and SW., 4.00 chs. dist., thence S.; thence across cultivated land.

38.80 Unimproved road, bears N. and S.

40.14 The cor. of secs. 26, 27, 34, and 35.

Land, rolling.

Soil, deep sand and clay.

No timber; undergrowth of shadscale, greasewood, sage, and black brush on uncultivated portion of mile.

North, bet. secs. 26 and 27.

Across cultivated land.

22.50 Leave cultivated land, bears E. and W.; thence over rolling bench land.

24.00 Unimproved road, bears NW. and NE.

34.00 Unimproved road, bears N.  $5^{\circ}$  W. and S.  $5^{\circ}$  E.

40.05 The  $\frac{1}{4}$  sec. cor. of secs. 26 and 27, which is marked by a

## DEPENDENT RESURVEY OF SUBDIVISION, T. 12 S., R. 17 W.

Chains

volcanic stone, 15 ~~15~~ 12 x 4 ins., firmly set, marked  $\frac{1}{4}$  on W. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ \hline S27 \quad | \quad S26 \end{array}$$

1950

Reset the stone cor. monument alongside the iron post and raise a mound of stone 4 ft. base, 9 ins. high around same.

N. 0°02' E., beginning new measurement.

Along gradual W. slope of high spur to the E.

40.16

The cor. of secs. 22, 23, 26, and 27, which is marked by a granite stone, 16 x 12 x 6 ins., firmly set, marked 2 notches on E. and S. edges.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked

$$\begin{array}{c} T12S \quad R17W \\ \hline S22 \quad | \quad S23 \\ \hline S27 \quad | \quad S26 \end{array}$$

1950

Reset the stone cor. monument alongside the iron post and raise a mound of stone, 4 ft. base, 9 ins. high, around same.

Land, rolling.

Soil, deep sand and clay loam.

No timber; undergrowth of shadscale and greasewood.

From the cor. of secs. 23, 24, 25, and 26.

N. 89°47' W., bet. secs. 23 and 26.

Over nearly level clay flat through scattered short undergrowth.

16.00

Leave nearly level clay flat and enter rolling land and medium dense short undergrowth, bears N. and S.

28.70

Unimproved road, bears N. 20° E. and S. 20° W.

40.05

The  $\frac{1}{4}$  sec. cor. of secs. 23 and 26, which is marked by a granite stone, 16 x 10 x 8 ins., firmly set, marked  $\frac{1}{4}$  on N. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

## DEPENDENT RESURVEY OF SUBDIVISION, T. 12 S., R. 17 W.

Chains

S23

 $\frac{1}{4}$   
S26

1950

Reset the stone cor. monument alongside the iron post and raise a mound of stone, 4 ft. base, 9 ins. high, around same.

N. 89°54' W., beginning new measurement.

Continue over rolling land.

- 2.00 Base of high bench to the W., bears N. and S.; ascend 200 ft. over E. slope to top of bench.
- 23.60 Top of E. rim of bench, bears N. and S.; thence over top of bench.
- 29.80 Top of W. rim of bench, bears N. and S.; descend 160 ft. over W. slope to the sec. cor.
- 40.33 The cor. of secs. 22, 23, 26, and 27.

Land, rolling.

Soil, deep clay and sand.

No timber; undergrowth of shadscale, greasewood, sage, and black brush.

N. 0°03' E., bet. secs. 22 and 23.

Along gradual W. slope of rolling land at base of high bench to the E., through medium dense short undergrowth.

- 21.30 Unimproved road, bears N. 5° E. and S. 5° W.
- 27.70 The E. point of a dense bunch of willows to the W.
- 33.90 Recross road, bears NW., and SE., 1.00 chs. dist., thence southerly.
- 40.19 The  $\frac{1}{4}$  sec. cor. of secs. 22 and 23, which is marked by a cobble stone, 12 x 8 x 4 ins., firmly set, marked  $\frac{1}{4}$  on W. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$\frac{1}{4}$   
S22 | S23

1950

Reset the stone cor. monument alongside the iron post and raise a mound of stone, 4 ft. base, 9 ins. high, around same.

Cor. set at the base of high bench to the E., bears N. and S.

N. 0°02' E., beginning new measurement.

DEPENDENT RESURVEY OF SUBDIVISION, T. 12 S., R. 17 W.

Chains

Continue along base of high bench to the E.

14.20 Cove in base of bench to the E., bears East, about 7.00 chs. dist.

19.80 Fence, bears E. and W.

40.18 The cor. of secs. 14, 15, 22, and 23, which is marked by a granite stone, 18 x 14 x 6 ins., firmly set, marked 3 notches on S. edge and 2 notches on E. edge.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked

T12S	R17W
S15	S14
S22	S23

1950

Reset the stone cor. monument alongside the iron post and raise a mound of stone, 4 ft. base, 9 ins. high, around same.

Land, rolling.

Soil, deep sand and clay.

No timber; undergrowth of shadscale, greasewood, sage, and black brush.

From the cor. of secs. 13, 14, 23, and 24.

N. 89°45' W., bet. secs. 14 and 23.

Over rolling bench land, through medium dense short undergrowth; ascend 80 ft. over general SE. slope to the 1/4 sec. cor.

40.17 The 1/4 sec. cor. of secs. 14 and 23, which is marked by a granite stone, 24 x 12 x 6 ins., firmly set, marked 1/4 on N. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

1/4	S14
	S23

1950

Reset the stone cor. monument alongside the iron post and raise a mound of stone, 4 ft. base, 9 ins. high, around same.

N. 89°55' W., beginning new measurement.

Continue over rolling bench land.

5.20 Base of high bench to the W., bears N. and S.; ascend 90 ft. over E. slope to top of bench.

8.00 Shallow draw, drains NE.

DEPENDENT RESURVEY OF SUBDIVISION' T. 12 S., R. 17 W.

Chains

- 13.70 Top of E. rim of bench, bears N. and S.; thence over rolling top of bench.
- 22.80 Unimproved road, bears N. and S.
- 31.20 Top of W. rim of bench, bears N. and S.; descend 140 ft. over steep W. slope to the sec. cor.
- 40.22 The cor. of secs. 14, 15, 22, and 23.  
Land, E. and W. slopes of high bench.  
Soil, deep sand and clay.  
No timber; undergrowth of shadscale, greasewood, sage, and black brush.

N. 0°02' E., bet. secs. 14 and 15.


Over rolling land along base of high bench to the E., through medium dense short undergrowth.

- 30.00 Leave base of bench, bears S. and N. 60° W.; ascend 50 ft. over SW. slope to the 1/4 sec. cor.

- 40.18 The 1/4 sec. cor. of secs. 14 and 15, which is marked by a granite stone, 16 x 12 x 6 ins., firmly set, marked 1/4 on W. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked



Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

N. 0°02' E., beginning new measurement.

Ascend 50 ft. over SW. slope to top of bench.


- 4.60 Top of SW. rim of bench, bears N. 60° W., and S. 60° E., about 15.00 chs. dist., thence southerly; thence over rolling top of bench.

- 16.70 Dim unimproved road, bears N. 60° W. and S. 60° E.

- 40.17 The cor. of secs. 10, 11, 14, and 15, which is marked by a granite stone, 18 x 18 x 6 ins., firmly set, marked 4 notches on S. edge and 2 notches on E. edge.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked



1950

Reset the stone cor. monument alongside the iron post and

W. 1/2 SECTION RESERVE OF SUBDIVISION, T. 12 S., R. 17 W.

Chains

raise a mound of stone, 4 ft. base, 9 ins. high, around same.

Land, rolling.

Soil, sand and clay.

No timber; undergrowth of shadscale, greasewood, sage, and black brush.

From the cor. of secs. 11, 12, 13, and 14.

N. 89°45' W., bet. secs. 11 and 14.

Over rolling desert land, through medium dense short undergrowth.

- 7.80 Shallow draw, drains S.  
 14.00 Shallow draw, drains SE.  
 20.70 Shallow draw, drains S. 20° E.  
 23.80 Shallow draw, drains SE.  
 26.50 Shallow draw, drains SE.  
 40.30 The  $\frac{1}{4}$  sec. cor. of secs. 11 and 14, which is marked by a cobble stone, 16 x 10 x 8 ins., firmly set, marked  $\frac{1}{4}$  on N. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$$\frac{S11}{\frac{1}{4}} \frac{S14}{}$$

1950

Reset the stone cor. monument alongside the iron post and raise a mound of stone, 4 ft. base, 9 ins. high, around same.

N. 89°47' W., beginning new measurement.

Continue over rolling land.

- 20.00 Base of bench to the W., bears NW. and SE.; ascend 40 ft. over NE. slope to top of bench.  
 23.00 Top of NE. rim of bench, bears NW. and SE.; thence over rolling top of bench.  
 40.12 The cor. of secs. 10, 11, 14, and 15.

Land, rolling.

Soil, sand and clay.

No timber; undergrowth of sage and black brush, shadscale, and greasewood.

N. 0°02' E., bet. secs. 10 and 11.

Over rolling top of bench land, through medium dense short undergrowth.

DEPENDENT RESURVEY OF SUBDIVISION T. 12 S., R. 17 W.

Chains


14.40 Dim unimproved road, bears E. and W.

16.20 Shallow draw, drains E., 1.00 chs. dist., thence SE.

40.18 The 1/4 sec. cor. of secs. 10 and 11, which is marked by a cobble stone, 12 x 8 x 8 ins., firmly set, marked 1/4 on W. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked



Reset the stone cor. monument alongside the iron post and raise a mound of stone, 4 ft. base, 9 ins. high, around same.


N. 0°02' E., beginning new measurement.

Continue over rolling bench land.

40.14 The cor. of secs. 2, 3, 10, and 11, which is marked by a cobble stone, 18 x 10 x 10 ins., firmly set, marked 5 notches on S. edge and 2 notches on E. edge.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked



Reset the stone cor. monument alongside the iron post and raise a mound of stone, 4 ft. base, 9 ins. high, around same.

Land, rolling.

Soil, sand and clay.

No timber; undergrowth of shadscale, greasewood, sage, and black brush.

From the cor. of secs. 1, 2, 11, and 12.

N. 89°45' W., bet. secs. 2 and 11.

Over rolling bench land, through medium dense short undergrowth.

3.60 Base of bench to the W., bears N. 20° W. and S. 20° E.; ascend 40 ft. over E. slope to top of bench.

5.60 Top of E. rim of bench, bears N. 20° W. and S. 20° E.; thence over rolling top of bench.

40.21 The 1/4 sec. cor. of secs. 2 and 11, which is marked by a

DEPENDENT RESURVEY OF SUBDIVISION, T. 12 S., R. 17 W.

cobble stone, 12 x 8 x 8 ins., firmly set, marked  $\frac{1}{4}$  on N. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$$\begin{array}{r} S2 \\ \frac{1}{4} \\ \hline S11 \\ 1950 \end{array}$$

Reset the stone cor. monument alongside the iron post and raise a mound of stone, 4 ft. base, 9 ins. high, around same.

N. 89°54' W., beginning new measurement.

Continue over rolling top of bench land.

40.11 The cor. of secs. 2, 3, 10, and 11.

Land, rolling.

Soil, sand and clay.

No timber; undergrowth of shadscale and greasewood, sage, and black brush.

N. 0°04' W., bet. secs. 2 and 3.

Over rolling bench land, through medium dense short undergrowth.

40.17 The  $\frac{1}{4}$  sec. cor. of secs. 2 and 3, which is marked by a granite stone, 18 x 12 x 4 ins., firmly set, marked  $\frac{1}{4}$  on W. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$$\begin{array}{r} \frac{1}{4} \\ S3 \mid S2 \\ 1950 \end{array}$$

Reset the stone cor. monument alongside the iron post, and raise a mound of stone, 4 ft. base, 9 ins. high, around same.

N. 0°08' W., beginning new measurement.

Continue over rolling bench land.

21.80 Top of rim of bench, 40 ft. high, bears NW. and SE.; continue over rolling land.

54.27 The closing cor. of secs. 2 and 3 on the N. bdy. of the township, which is marked by a cobble stone, 20 x 10 x 4 ins., firmly set, marked 2 grooves on E. face, 4 grooves on W. face, and CC on S. face.

DEPENDENT RESURVEY OF SUBDIVISION, T. 12 S., R. 17 W.

Chains

At the cor. point:

Set an iron post, 3 ft. long, 3 ins. in diam., 27 ins. in the ground, with brass cap marked

T11S R17W  
S35

S3	S2
T12S	R17W
C	C

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

From this closing cor., the cor. of secs. 34 and 35, T. 11 S., R. 17 W., bears S. 89°53' W., 5.94 chs. dist.

Land, rolling.

Soil, sand and clay.

No timber; undergrowth of shadscale and greasewood, sage, and black brush.

From the cor. of secs. 33 and 34, on the S. bdy. of the township, which is marked by an iron post, 3 ins. in diam., set, marked, and witnessed, as described in the official record.

N. 0°01' E., bet. secs. 33 and 34.

Over rolling desert land, through medium dense short undergrowth.

40.04

The  $\frac{1}{4}$  sec. cor. of secs. 33 and 34, which is marked by a cobble stone, 15 x 6 x 6 ins., firmly set, marked  $\frac{1}{4}$  on W. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$\frac{1}{4}$   
S33 | S34

1950

Reset the stone cor. monument with a juniper post, 8 ft. long, 4 ins. in diam., alongside the iron post.

N. 0°02' E., beginning new measurement.

Continue over rolling land.

17.80

Dry channel of Granite Creek, 100 lks. wide, 5 ft. deep, drains E.

36.80

Wash, 150 lks. wide, 5 ft. deep, drains E.

40.03

The cor. of secs. 27, 28, 33, and 34, which is marked by a cobble stone, 15 x 8 x 6 ins., firmly set, marked 1 notch on S. edge and 3 notches on E. edge.

At the cor. point:

## DEPENDENT RESURVEY OF SUBDIVISION, T. 12 S., R. 17 W.

Chains

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked

T12S	R17W
S28	S27

S33	S34
-----	-----

1950

Reset the stone cor. monument with a juniper post, 6 ft. long, 8 ins. in diam., alongside the iron post.

Land, rolling.

Soil, sand and clay.

No timber; undergrowth of shadscale, greasewood, sage, rabbit, and black brush.

From the cor. of secs. 26, 27, 34, and 35.

S. 89°51' W., bet. secs. 27 and 34:

Over level alfalfa field.

17.30 Leave alfalfa field and enter dense greasewood, bears N. and S.

40.13 The  $\frac{1}{4}$  sec. cor. of secs. 27 and 34, which is marked by a cobble stone, 12 x 10 x 4 ins., firmly set, marked  $\frac{1}{4}$  on N. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 ins. in diam., 27 ins. in the ground, with brass cap marked

$\frac{1}{4}$	S27
	S34

1950

Reset the stone cor. monument and a juniper post, 8 ft. long, 5 ins. in diam., alongside the iron post.

N. 89°50' W., beginning new measurement.

Continue over nearly level land through dense greasewood.

1.50 Fence, bears N. and S.

40.13 The cor. of secs. 27, 28, 33, and 34.

Land, nearly level.

Soil, deep sandy clay loam.

No timber; undergrowth of dense greasewood.

N. 0°01' E., bet. secs. 27 and 28.

Over nearly level desert land, through medium dense short undergrowth.

40.14 The  $\frac{1}{4}$  sec. cor. of secs. 27 and 28, which is marked by a cobble stone, 14 x 8 x 4 ins., firmly set, marked  $\frac{1}{4}$  on W. face.

## DEPENDENT RESURVEY OF SUBDIVISION, T. 12 S., R. 17 W.

Chains

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$$\frac{1}{4}$$

S28	S27
-----	-----

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

N. 0°01' E., beginning new measurement.

Continue over nearly level desert land.

- 40.13 The cor. of secs. 21, 22, 27, and 28, which is marked by a cobble stone, 12 x 6 x 6 ins., firmly set, marked 2 notches on S. edge and 3 notches on E. edge.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked

T12S, R17W	
S21	S22
S28	S27

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

Land, nearly level desert.

Soil, deep sandy clay.

No timber; undergrowth of greasewood and shadscale.

From the cor. of secs. 22, 23, 26, and 27.

N. 89°58' W., bet. secs. 22 and 27.

Over rolling desert land, through medium dense short undergrowth.

- 2.70 Unimproved road, bears N. and S.
- 4.30 Enter alfalfa field, bears N. and S.
- 8.80 Leave same, bears N. and S.; thence over rolling land.
- 40.16 Point for the  $\frac{1}{4}$  sec. cor. of secs. 22 and 27 at proportionate distance; the original corner monument, a cobble stone, 12 x 8 x 4 ins., lying on the ground out of place, bears West, 25 lks. dist. Cor. monument marked  $\frac{1}{4}$  on bottom face and was in fence line bearing N. and S.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$$\frac{1}{4}$$

S22	S27
-----	-----

1950

## DEPENDENT RESURVEY OF SUBDIVISION, T. 12 S., R. 17 W.

Chains

Reset the stone cor. monument alongside the iron post.

40.40 Fence, bears N. and S.

80.31 The cor. of secs. 21, 22, 27, and 28.

Land, nearly level.

Soil, deep sand and clay.

No timber; undergrowth of shadscale and greasewood, sage, and black brush.

N. 0°01' E., bet. secs. 21 and 22.

Over nearly level desert land, through medium dense short undergrowth.

40.15 The  $\frac{1}{4}$  sec. cor. of secs. 21 and 22, which is marked by a cobble stone, 14 x 6 x 6 ins., firmly set, marked  $\frac{1}{4}$  on W. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ | \\ \text{S21} \quad | \quad \text{S22} \end{array}$$

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

N. 0°01' E., beginning new measurement.

Continue over nearly level land.

33.50 Concrete flume, 10 lks. wide, 2 $\frac{1}{2}$  ft. deep, which carries water from Cedar Creek to Sharp's Ranch, flows S. 45°37'E.

34.40 Unimproved road, bears NW. and SE.

40.12 The cor. of secs. 15, 16, 21, and 22, which is marked by a cobble stone, 12 x 8 x 6 ins., firmly set, marked 3 notches on E. and S. edges.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked

$$\begin{array}{c} \text{T12S, R17W} \\ \text{S16} \quad | \quad \text{S15} \\ \hline \text{S21} \quad | \quad \text{S22} \end{array}$$

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

Land, nearly level desert.

Soil, deep clay and sand.

No timber; undergrowth of shadscale and greasewood.

## DEPENDENT RESURVEY OF SUBDIVISION, T. 12 S., R. 17 W.

## Chains

From the cor. of secs. 14, 15, 22, and 23.

S. 89°55' W., bet. secs. 15 and 22.

Over nearly level desert land, through medium dense short undergrowth.

40.17 The  $\frac{1}{4}$  sec. cor. of secs. 15 and 22, which is marked by a cobble stone, 14 x 12 x 8 ins., firmly set, marked  $\frac{1}{4}$  on N. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$$\frac{1}{4} \begin{array}{l} S15 \\ \hline S22 \end{array}$$

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

N. 89°57' W., beginning new measurement.

Continue over nearly level desert land.

7.20 Dry channel of Cedar Creek, 40 lks. wide, 8 ft. deep, drains SE.

40.16 The cor. of secs. 15, 16, 21, and 22.

Land, nearly level desert.

Soil, deep clay and sand.

No timber; undergrowth of shadscale and greasewood, sage, and black brush.

N. 0°03' W., bet. secs. 15 and 16.

Over rolling desert land, through medium dense short undergrowth.

18.90 Dry channel of Cedar Creek, 150 lks. wide, 20 ft. deep, drains S. 80° E.

40.16 The  $\frac{1}{4}$  sec. cor. of secs. 15 and 16, which is marked by a cobble stone, 14 x 8 x 6 ins., firmly set, marked  $\frac{1}{4}$  on W. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$$\frac{1}{4} \begin{array}{l} S16 \quad | \quad S15 \\ \hline \end{array}$$

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

DEPENDENT RESURVEY OF SUBDIVISION, T. 12 S., R. 17 W.

Chains

N. 0°04' E., beginning new measurement.

Continue over rolling desert land.

16.00 Base of gradual ascent over S. slope of bench to the N., bears E. and W.; ascend 40 ft. to the sec. cor.

31.10 Unimproved road, bears E. and W.

40.15 The cor. of secs. 9, 10, 15, and 16, which is marked by a cobble stone, 12 x 6 x 4 ins., firmly set, marked 4 notches on S. edge and 3 notches on E. edge.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked

T22S	R17W
S9	S10

S16	S15
-----	-----

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

Land, rolling desert.

Soil, deep sand and clay.

No timber; undergrowth of shadscale, greasewood, sage, rabbit, and black brush.

From the cor. of secs. 10, 11, 14, and 15.

S. 89°58' W., bet. secs. 10 and 15.

Over broken and rolling desert land, through medium dense short undergrowth.

38.40 Unimproved road, bears N. 10° E. and SW.

40.18 The 1/4 sec. cor. of secs. 10 and 15, which is marked by a cobble stone, 14 x 10 x 8 ins., firmly set, marked 1/4 on N. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

1/4	S10
-----	-----

S15
-----

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

Cor. set at the base of bench to the NW., bears N. and SW.

N. 89°57' W., beginning new measurement.

Along broken S. slope of bench to the NW.

## DEPENDENT RESURVEY OF SUBDIVISION, T. 12 S., R. 17 W.

## Chains

13.50 Low spur, projects SE., 2.50 chs. dist. to end.

40.20 The cor. of secs. 9, 10, 15, and 16.

Land, rolling.

Soil, deep clay and sand.

No timber; undergrowth of shadscale, greasewood, sage, and black brush.

N. 0°01' W., bet. secs. 9 and 10.

Over broken and rolling desert land, through medium dense short undergrowth; ascend 50 ft. over S. slope to top of bench.

2.20 Top of S. rim of bench, bears N. 80° W. and S. 80° E.; thence over rolling top of bench.

40.18 The  $\frac{1}{2}$  sec. cor. of secs. 9 and 10, which is marked by a cobble stone, 12 x 6 x 4 ins., firmly set, marked  $\frac{1}{4}$  on W. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ | \\ S9 \quad | \quad S10 \\ 1950 \end{array}$$

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

N. 0°02' W., beginning new measurement.

Continue over rolling top of bench land.

20.00 From this point, the center of a clay flat, which is 20.00 chs. long N. and S., and 15.00 chs. wide E. and W., bears West, 20.00 chs. dist.

40.17 The cor. of secs. 3, 4, 9, and 10, which is marked by a cobble stone, 12 x 6 x 6 ins., firmly set, marked 5 notches on S. edge and 3 notches on E. edge.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked

$$\begin{array}{c} T12S \quad R17W \\ S4 \quad | \quad S3 \\ \hline S9 \quad | \quad S10 \\ 1950 \end{array}$$

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

Land, rolling.

Soil, sand and clay.

No timber; undergrowth of shadscale and greasewood.

DEPENDENT RESURVEY OF SUBDIVISION, T. 12 S., R. 17 W.

Chains

From the cor. of secs. 2, 3, 10, and 11.

N. 89°58' W., bet. secs. 3 and 10.

Over rolling desert land, through medium dense short undergrowth.

40.27

The  $\frac{1}{4}$  sec. cor. of secs. 3 and 10, which is marked by a volcanic stone, 16 x 8 x 4 ins., firmly set, marked  $\frac{1}{4}$  on N. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$\frac{1}{4}$   $\frac{S3}{S10}$

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

West, beginning new measurement.

Continue over rolling desert land.

16.70

Base of ascent over E. slope of bench, bears N. and S.; ascend 50 ft. to top of E. rim of bench.

22.20

Top of E. rim of bench, bears N. and S.; thence over rolling top of same.

34.20

Low rise, bears N. and S.

40.19

The cor. of secs. 3, 4, 9, and 10.

Land, rolling desert .

Soil, sand and clay.

No timber; undergrowth of shadscale, greasewood, sage, and black brush.

N. 0°02' W., bet. secs. 3 and 4.

Over rolling desert land, through medium dense short undergrowth.

14.20

From this point, the center of a barren clay flat, about 5.00 chs. in diam., bears SW., about 15.00 chs. dist.

22.90

Top of NE. rim of bench, bears NW. and SE.; descend 80 ft. NE. slope to the  $\frac{1}{4}$  sec. cor.

33.30

Base of bench, bears NW. and SE.; thence over rolling land.

40.30

The  $\frac{1}{4}$  sec. cor. of secs. 3 and 4, which is marked by a volcanic stone, 10 x 8 x 6 ins., firmly set, marked  $\frac{1}{4}$  on W. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

## DEPENDENT RESURVEY OF THE SUBDIVISION, T. 12 S., R. 17 W.

Chains

 $\frac{1}{4}$   
 S4 | S3

1950

Reset the stone cor. monument alongside the iron post and raise a mound of stone, 4 ft. base, 9 ins. high, around same.

N. 0°03' W., beginning new measurement.

Continue over rolling desert land.

53.38

The closing cor. of secs. 3 and 4, on the N. bdy. of the township, which is marked by a cobble stone, 16 x 10 x 6 ins., firmly set, marked 3 notches on E. and W. edges and CC on S. face.

At the cor. point:

Set an iron post, 3 ft. long, 3 ins. in diam., 27 ins. in the ground, with brass cap marked

T11S R17W  
 S34

S4 | S3  
 T12S | R17W  
 C | C

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

From this closing cor., the cor. of secs. 33 and 34, T. 11 S., R. 17 W., bears S. 89°24' W., 8.75 chs. dist.

Land, rolling desert.

Soil, deep sand and clay.

No timber; undergrowth of shadscale, sage, and black brush.

From the cor. of secs. 32 and 33, on the S. bdy. of the township, which is marked by an iron post, 3 ins. in diam., set, marked, and witnessed, as described in the official record.

N. 0°03' E., bet. secs. 32 and 33.

Over rolling bench land, through medium dense short undergrowth.

20.00 Shallow draw, drains S. 80° E.

40.16 The  $\frac{1}{4}$  sec. cor. of secs. 32 and 33, which is marked by a cobble stone, 12 x 6 x 6 ins., firmly set, marked  $\frac{1}{4}$  on W. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

## DEPENDENT RESURVEY OF SUBDIVISION, T. 12 S., R. 17 W.

Chains

$$\frac{1}{4}$$

S32	S33
-----	-----

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

N. 0°01' E., beginning new measurement.

Continue over rolling bench land.

4.30 Shallow draw, drains E.

31.70 Top of S. rim of Granite Creek, bears E. and NW.

40.02 The cor. of secs. 28, 29, 32, and 33, which is marked by a cobble stone, 12 x 10 x 8 ins., firmly set, marked 1 notch on S. edge and 4 notches on E. edge.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked

T12S	R17W
S29	S28

S32	S33
-----	-----

1950

Reset the stone cor. monument alongside the iron post and raise a mound of stone, 4 ft. base, 9 ins. high, around same.

Land, rolling.

Soil, deep sand and clay.

No timber; undergrowth of shadscale, greasewood, sage, black, and rabbit brush.

From the cor. of secs. 27, 28, 33, and 34.

N. 89°54' W., bet. secs. 28 and 33.

Over rolling bench land, through medium dense short undergrowth.

32.80 Wash, 40 lks. wide, 4 ft. deep, drains S. 80° E.

40.10 The  $\frac{1}{4}$  sec. cor. of secs. 28 and 33, which is marked by a sandstone, 12 x 8 x 6 ins., firmly set, marked  $\frac{1}{4}$  on N. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

S28
-----

$$\frac{1}{4}$$

S33
-----

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

## DEPENDENT RESURVEY OF SUBDIVISION, T. 12 S., R. 17 W.

## Chains

N. 89°53' W., beginning new measurement.

Continue over rolling bench land.

- 35.70 Top of N. rim of Granite Creek, bears S. 80° E. and N. 80° W.
- 39.20 Dry channel of Granite Creek, 40 lks. wide, 5 ft. deep, drains SE.
- 40.21 The cor. of secs. 28, 29, 32, and 33.

Land, rolling.

Soil, deep sand and clay.

No timber; undergrowth of shadscale, greasewood, sage, black, and rabbit brush.

N. 0°04' E., bet. secs. 28 and 29.

Over bottom lands of Granite Creek, through dense short undergrowth.

- 3.40 Dry channel of Granite Creek, 40 lks. wide, 5 ft. deep, drains SE. from the NE.
- 8.40 Recross channel of Granite Creek, drains SE.; ascend 30 ft. to N. rim of creek.
- 14.00 Top of N. rim of Granite Creek, bears NW. and SE.
- 40.20 The  $\frac{1}{4}$  sec. cor. of secs. 28 and 29, which is marked by a cobble stone, 14 x 6 x 6 ins., firmly set, marked  $\frac{1}{4}$  on W. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ \hline S29 \quad | \quad S28 \\ 1950 \end{array}$$

Reset the stone cor. monument alongside the iron post and raise a mound of stone, 4 ft. base, 9 ins. high, around same.

N. 0°03' E., beginning new measurement.

Continue over rolling bench land.

- 14.70 Shallow draw, drains E.
- 33.80 Bottom of large main wash, 150 lks. wide, 8 ft. deep, drains E.
- 40.16 The cor. of secs. 20, 21, 28, and 29, which is marked by a cobble stone, 14 x 12 x 6 ins., firmly set, marked 2 notches on S. edge and 4 notches on E. edge.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked

## DEPENDENT RESURVEY OF SUBDIVISION, T. 12 S., R. 17 W.

chains

T12S	R17W
S20	S21
S29	S28

1950

Reset the stone cor. monument alongside the iron post and raise a mound of stone, 4 ft. base, 9 ins. high, around same.

Land, rolling.

Soil, deep sand and clay.

No timber; undergrowth of shadscale, greasewood, sage, black, and rabbit brush.

From the cor. of secs. 21, 22, 27, and 28.

N. 89°43' W., bet. secs. 21 and 28.

Over rolling desert land, through medium dense short undergrowth.

40.18 The  $\frac{1}{4}$  sec. cor. of secs. 21 and 28, which is marked by a cobble stone, 10 x 10 x 8 ins., firmly set, marked  $\frac{1}{4}$  on N. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$\frac{1}{4}$	S21
	S28

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

N. 89°53' W., beginning new measurement.

Continue over rolling bench land.

21.00 Shallow draw, drains SE.

40.13 The cor. of secs. 20, 21, 28, and 29.

Land, rolling.

Soil, deep sand and clay.

No timber; undergrowth of shadscale, greasewood, sage, and black brush.

N. 0°02' W., bet. secs. 20 and 21.

Over rolling desert land, through medium dense short undergrowth.

23.60 Shallow draw, drains SE., 2.00 chs. dist., thence N. 10° E.

40.12 The  $\frac{1}{4}$  sec. cor. of secs. 20 and 21, which is marked by a cobble stone, 16 x 10 x 6 ins., firmly set, marked  $\frac{1}{4}$  on W. face.

DEPENDENT RESURVEY OF SUBDIVISION, T. 12 S., R. 17 W.

Chains

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked



Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.


N. 0°01' W., beginning new measurement.

Continue over rolling bench land.

- 4.70 Shallow draw, drains E.
- 10.90 Shallow draw, drains E.
- 40.21 The cor. of secs. 16, 17, 20, and 21, which is marked by a cobble stone, 14 x 8 x 8 ins., firmly set, marked 3 notches on S. edge and 4 notches on E. edge.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked



Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

Land, rolling.

Soil, deep sand and clay.

No timber; undergrowth of shadscale, greasewood, sage, black, and rabbit brush.

From the cor. of secs. 15, 16, 21, and 22.

N. 89°30' W., bet. secs. 16 and 21.

Over rolling bench land, through medium dense short undergrowth; ascend 50 ft. over general E. slope to the sec. cor.

- 6.10 Unimproved road, bears NW. and SE.
- 6.90 Concrete flume which carries water from Cedar Creek to Sharp's Ranch, 10 lks. wide, 2½ ft. deep, flows S45°37'E.
- 26.40 Wash, 20 lks. wide, 4 ft. deep, drains SE.
- 49.81 The ¼ sec. cor. of secs. 16 and 21, which is marked by a sandstone, 12 x 8 x 4 ins., firmly set, marked ¼ on N. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in

## DEPENDENT RESURVEY OF SUBDIVISION, T. 12 S., R. 17 W.

Chains

the ground, with brass cap marked

$$\frac{1}{4} \frac{S16}{S21}$$

1950

Reset the stone cor. monument alongside the iron post and raise a mound of stone, 4 ft. base, 9 ins. high, around same.

N. 89°58' W., beginning new measurement.

Ascend 50 feet over general E. slope to the sec. cor.

40.47 The cor. of secs. 16, 17, 20, and 21.

Land, rolling.

Soil, deep clay and sand.

No timber; undergrowth of shadscale, greasewood, sage, and black brush.

N. 0°01' W., bet. secs. 16 and 17.

Over rolling bench land, through medium dense short undergrowth.

4.70 Top of low sandy knoll.

17.20 Top of the SE. point of low sandy ridge from the NW.

40.19 The  $\frac{1}{4}$  sec. cor. of secs. 16 and 17, which is marked by a cobble stone, 12 x 10 x 8 ins., firmly set, marked  $\frac{1}{4}$  on W. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$$\frac{1}{4} \frac{S17}{S16}$$

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

North, beginning new measurement.

Continue over rolling desert land.

9.60 Wash, 40 lks. wide, 5 ft. deep, drains E.

26.15 Concrete flume, 10 lks. wide, 2 $\frac{1}{2}$  ft. deep, which carries water from Cedar Creek to Sharp's Ranch, flows S. 66°30' E.

33.40 Unimproved road, bears S. 66°30' E. and N. 66°30' W.

34.50 Unimproved road, bears NE. and W.

36.30 Top of S. rim of Cedar Creek, bears N. 80° W. and S. 80° E.

DEPENDENT RESURVEY OF SUBDIVISION, T. 12 S., R. 17 W.

Chains

38.90 Dry channel of Cedar Creek, 50 lks. wide, 7 ft. deep, drains S. 80° E.

40.15 The cor. of secs. 8, 9, 16, and 17, which is marked by a cobble stone, 14 x 14 x 14 ins., firmly set, marked 4 notches on E. and S. edges.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked

T12S	R17W
S8	S9
S17	S16

1950

Reset the stone cor. monument alongside the iron post and raise a mound of stone, 4 ft. base, 9 ins. high, around same.

Land, rolling.

Soil, deep sand and clay.

No timber; undergrowth of shadscale, greasewood, sage, black, and rabbit brush.

From the cor. of secs. 9, 10, 15, and 16.

N. 89°44' W., bet. secs. 9 and 16.

Along broken S. face of bench land, through medium dense short undergrowth.

10.00 Shallow draw, drains S.

27.00 Base of bench, bears N. 80° W. and S. 80° E.

40.14 The 1/4 sec. cor. of secs. 9 and 16, which is marked by a cobble stone, 14 x 12 x 8 ins., firmly set, marked 1/4 on N. face.

At the cor. point:

Set an iron post, 3/4 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

1/4	S9
	S16

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

N. 89°49' W., beginning new measurement.

Continue over broken bench land.

19.40 Unimproved road, bears N. 80° W. and S. 80° E.

37.00 Shallow draw, drains SE.

38.50 Top of NE. rim of Cedar Creek, bears NW. and SE.

DEPARTMENT RESURVEY OF SUBDIVISION, T. 12 S., R. 17 W.

Chains

40.11 The cor. of secs. 8, 9, 16, and 17.

Land, rolling.

Soil, deep clay and sand.

No timber; undergrowth of shadscale, greasewood, sage, black, and rabbit brush.

N. 0°01' W., bet. secs. 8 and 9.

Over rolling and broken bench land, through medium dense short undergrowth.

2.00 Top of NE. rim of Cedar Creek, bears NW. and SE.

24.00 Base of gradual ascent over SE. slope of bench to the NW. bears E. and W.

40.18 The  $\frac{1}{4}$  sec. cor. of secs. 8 and 9, which is marked by a cobble stone, 12 x 6 x 6 ins., firmly set, marked  $\frac{1}{4}$  on W. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ \hline S8 \mid S9 \\ 1950 \end{array}$$

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

N. 0°01' W., beginning new measurement.

Continue over rolling bench land.

40.17 The cor. of secs. 4, 5, 8, and 9, which is marked by a cobble stone, 12 x 8 x 4 ins., firmly set, marked 5 notches on S. edge and 4 notches on E. edge.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked

$$\begin{array}{c} T12S, R17W \\ \hline S5 \mid S4 \\ \hline S8 \mid S9 \\ 1950 \end{array}$$

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

Land, rolling.

Soil, deep sand and clay.

No timber; undergrowth of shadscale, greasewood, sage, and black brush.

From the cor. of secs. 3, 4, 9, and 10.

## DEPENDENT RESURVEY OF SUBDIVISION, T. 12 S., R. 17 W.

Chains

N. 89°38' W., bet. secs. 4 and 9.

Over rolling bench land, through medium dense short undergrowth.

40.05

The  $\frac{1}{4}$  sec. cor. of secs. 4 and 9, which is marked by a cobble stone, 10 x 8 x 6 ins., firmly set, marked  $\frac{1}{4}$  on N. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$$\frac{S4}{\frac{1}{4}}$$

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

N. 89°56' W., beginning new measurement.

Continue over rolling bench land.

10.30

Shallow draw, drains SW.

11.60

Rim of bench, bears S. and NW.; descend 70 ft. over SW. slope to base of bench.

30.00

Base of bench, bears NW. and SE.

40.13

The cor. of secs. 4, 5, 8, and 9.

Land, rolling.

Soil, deep clay and sand.

No timber; undergrowth of shadscale, greasewood, sage, black, and rabbit brush.

North, bet. secs. 4 and 5.

Over rolling bench land, through medium dense short undergrowth.

8.20

Base of bench to the N., bears E. and W.

19.50

Shallow draw, drains SE.

23.20

Top of S. rim of bench, bears E. and W.

40.19

The  $\frac{1}{4}$  sec. cor. of secs. 4 and 5, which is marked by a cobble stone, 16 x 8 x 6 ins., firmly set, marked  $\frac{1}{4}$  on W. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$$\frac{S5}{\frac{1}{4}} \quad S4$$

1950

## DEPENDENT RESURVEY OF SUBDIVISION, T. 12 S., R. 17 W.

Chains

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

N.  $0^{\circ}02'$  W., beginning new measurement.

Continue over rolling bench land.

45.30 Shallow draw, drains NE..

51.90 Shallow draw, drains S.  $80^{\circ}$  E.

52.89 The closing cor. of secs. 4 and 5, on the N. bdy. of the township, which is marked by a cobble stone, 14 x 10 x 6 ins, firmly set, marked 4 notches on E. edge, 2 notches on W. edge, and CC on S. face.

At the cor. point:

Set an iron post, 3 ft. long, 3 ins. in diam., 27 ins. in the ground, with brass cap marked

T11S R17W  
S33

S5	S4
T12S	R17W
C	C

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

From this closing cor., the cor. of secs. 32 and 33, T. 11 S., R. 17 W., bears S.  $89^{\circ}31'$  W., 10.86 chs. dist.

Land, rolling.

Soil, deep sand and clay.

No timber; undergrowth of shadscale, greasewood, sage, and black brush.

From the cor. of secs. 31 and 32, on the S. bdy. of the township, which is marked by an iron post, 3 ins. in diam., set, marked, and witnessed, as described in the official record.

North, bet. secs. 31 and 32.

Over rolling bench land, through medium dense short undergrowth.

38.80 Unimproved road, bears N.  $60^{\circ}$  W. and S.  $60^{\circ}$  E.

40.13 The  $\frac{1}{4}$  sec. cor. of secs. 31 and 32, which is marked by a cobble stone, 16 x 12 x 8 ins., firmly set, marked  $\frac{1}{4}$  on W. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$\frac{1}{4}$   
S31 | S32

1950

## DEPENDENT RESURVEY OF SUBDIVISION, T. 12 S., R. 17 W.

Chains

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

N. 0°01' W., beginning new measurement.

Continue over rolling bench land.

30.80 Shallow draw, drains E..

37.00 Shallow draw, drains E. .

40.15 The cor. of secs. 29, 30, 31, and 32, which is marked by a cobble stone, 24 x 14 x 10 ins., firmly set, marked 1 notch on S. edge and 5 notches on E. edge.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked

T12S	R17W
S30	S29
S31	S32

1950

Reset the stone cor. monument alongside the iron post and raise a mound of stone, 4 ft. base, 9 ins. high, around same.

Land, rolling.

Soil, sand and clay.

No timber; undergrowth of shadscale, greasewood, sage, and black brush.

From the cor. of secs. 28, 29, 32, and 33.

N. 89°55' W., bet. secs. 29 and 32.

Over rolling bench land, through medium dense short undergrowth; ascend 50 ft. over NE. slope to rim of bench.

20.70 Top of E. rim of bench, bears N. and SW.; thence over top of bench.

40.16 The  $\frac{1}{4}$  sec. cor. of secs. 29 and 32, which is marked by a cobble stone, 14 x 10 x 6 ins., firmly set, marked  $\frac{1}{4}$  on N. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$\frac{1}{4}$	S29
	S32

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

DEPENDENT RESURVEY OF SUBDIVISION' T. 12 S., R. 17 W.

Chains

N. 89°54' W., beginning new measurement.

Continue over rolling bench land.

24.20 Base of ascent of 40 ft. over SE. slope of bench, bears NE. and SW.

33.20 Top of SE. rim of bench, bears NE. and SW.

40.24 The cor. of secs. 29, 30, 31, and 32.

Land, rolling.

Soil, deep sand and clay.

No timber; undergrowth of sage, black, and rabbit brush, shadscale, and greasewood.

From the cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the township.

S. 89°59' E., bet. secs. 30 and 31.

Over rolling bench land, through scattered and medium dense short undergrowth.

6.00 Shallow draw, drains SE.

15.20 Wash, 30 lks. wide, 4 ft. deep, drains SE.

24.00 Wash, 50 lks. wide, 4 ft. deep, drains SE.

33.30 Wash, 50 lks. wide, 3 ft. deep, drains S. 5° W.

38.40 County road, graded, bears N. to Callao and S. to Trout Creek.

53.32 The 1/4 sec. cor. of secs. 30 and 31, which is marked by a cobble stone, 12 x 10 x 8 ins., firmly set, marked 1/4 on N. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

1/4 S30 / S31

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

S. 89°58' E., beginning new measurement.

Continue over rolling bench land.

3.30 Shallow draw, drains S.

39.00 Shallow draw, drains SE.

40.16 The cor. of secs. 29, 30, 31, and 32.

Land, rolling.

Soil, deep sand and clay.

No timber; undergrowth of shadscale, greasewood, sage, and black brush.

DEPENDENT RESURVEY OF SUBDIVISION. T. 12 S., R. 17 W.

Chains


N. 0°01' W., bet. secs. 29 and 30.

Over nearly level clay flat through medium dense short undergrowth.

40.19 The  $\frac{1}{4}$  sec. cor. of secs. 29 and 30, which is marked by a cobble stone, 18 x 12 x 6 ins., firmly set, marked  $\frac{1}{4}$  on W. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked



Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

N. 0°03' W., beginning new measurement.

Continue over nearly level clay flat.

2.60 Top of S. rim of Granite Creek, bears E. and W.; descend 60 ft. over N. slope to channel of creek.

7.90 Dry channel of Granite Creek, drains E., 50 lks. wide and 5 ft. deep; ascend 60 ft. over S. slope to top of N. rim of creek.


15.20 Top of N. rim of Granite Creek, bears E. and W.; thence over rolling bench land.

37.80 Top of S. rim of large wash, bears E. and W.; descend 30 ft. over N. slope to the sec. cor.

46.22 The cor. of secs. 19, 20, 29, and 30, which is marked by a cobble stone, 20 x 12 x 6 ins., firmly set, marked 2 notches on S. edge and 5 notches on E. edge.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked



1950

Reset the stone cor. monument alongside the iron post and raise a mound of stone, 4 ft. base, 9 ins. high, around same.

Land, rolling and nearly level.

Soil, clay and sand.

No timber; undergrowth shadscale and black brush.

From the cor. of secs. 20, 21, 28, and 29.

N. 89°52' W., bet. secs. 20 and 29.

RECORDING RESERVE OF SUBDIVISION, T. 12 S., R. 17 W.

- Chains  
at . 811
- Over rolling bench land, through medium dense short undergrowth.
- 8.60 Large wash in draw, 40 lks. wide, 10 ft. deep, drains S. 80° E.
- 40.30 The  $\frac{1}{4}$  sec. cor. of secs. 20 and 29, which is marked by a cobble stone, 16 x 12 x 8 ins., firmly set, marked  $\frac{1}{4}$  on N. face.
- At the cor. point:
- Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked
- |                   |
|-------------------|
| S20               |
| $\frac{1}{4}$ ——— |
| S29               |
- 1950
- Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.
- 
- N. 89°54' W., beginning new measurement.
- Continue over rolling land.
- 17.20 Top of S. rim of draw, bears NE. and S. 80° W.
- 23.00 Recross large wash in draw, drains N. 80° E.
- 31.20 Top of N. rim of draw, bears N. 85° W. and N. 85° E.
- 38.70 Recross large wash in draw, drains SE.
- 40.19 The cor. of secs. 19, 20, 29, and 30.
- Land, rolling.  
Soil, deep sand and clay.  
No timber; undergrowth of shadscale, greasewood, sage, black, and rabbit brush.
- 
- From the cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the township.
- S. 89°57' E., bet. secs. 19 and 30.
- Over rolling bench land, through medium dense short undergrowth.
- 2.20 Dry channel of Granite Creek, 40 lks. wide, 5 ft. deep, drains NE.
- 6.50 Top of the NW. point of bench to the SE.; thence along N. face of S. rim of creek.
- 27.00 Recross dry channel of Granite Creek, drains SE.
- 44.80 County road, graded, bears N. to Callao and S. to Trout Creek.
- 53.66 The  $\frac{1}{4}$  sec. cor. of secs. 19 and 30, which is marked by a cobble stone, 14 x 8 x 8 ins., firmly set, marked  $\frac{1}{4}$  on N. face.
- At the cor. point:

## DEPENDENT RESURVEY OF SUBDIVISION, T. 12 S., R. 17 W.

Chains Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$$\frac{1}{4} \frac{S19}{S30}$$

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

S. 89°56' E., beginning new measurement.

Continue over rolling desert land.

20.00 Enter bottom of large shallow draw, drains E. from N. 85° W.

32.00 Leave same, drains N. 80° E. from the W.

40.16 The cor. of secs. 19, 20, 29, and 30.

Land, rolling.

Soil, deep sand and clay.

No timber; undergrowth of shadscale, greasewood, sage, black, and rabbit brush.

N. 0°01' W., bet. secs. 19 and 20.

Over rolling desert land, through medium dense short undergrowth.

1.00 Bottom of wide shallow draw, drains E.; ascend 50 ft. over S. slope.

10.00 Top of SE. point of bench, bears N. and W., thence along rim of bench near top.

18.20 Shallow draw, drains SE.

25.00 Shallow draw, drains NE.

27.70 Shallow draw, drains NE.

35.70 Shallow draw, drains E.

40.05 The  $\frac{1}{4}$  sec. cor. of secs. 19 and 20, which is marked by a cobble stone, 14 x 8 x 8 ins., firmly set, marked  $\frac{1}{4}$  on W. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$$\frac{1}{4} \frac{S19}{S20}$$

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

Cor. set on rim of bench, bears N. 5° E. and S.

## DEPENDENT RESURVEY OF SUBDIVISION, T. 12 S., R. 17 W.

Chains

N. 0°01' W., beginning new measurement.

Continue over rolling bench land.

40.14 The cor. of secs. 17, 18, 19, and 20, which is marked by a cobble stone, 20 x 10 x 10 ins., firmly set, marked 3 notches on S. edge and 5 notches on E. edge.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked

T12S	R17W
S18	S17
S19	S20

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

Land, rolling.

Soil, deep clay and sand.

No timber; undergrowth of shadscale, greasewood, sage, black, and rabbit brush.

From the cor. of secs. 16, 17, 20, and 21.

S. 89°58' W., bet. secs. 17 and 20.

Over rolling bench land, through medium dense short undergrowth.

40.33 The  $\frac{1}{4}$  sec. cor. of secs. 17 and 20, which is marked by a cobble stone, 17 x 10 x 10 ins., firmly set, marked  $\frac{1}{4}$  on N. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$\frac{1}{4}$	S17.
	S20

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

N. 89°59' W., beginning new measurement.

Continue over rolling desert land.

17.60 Base of ascent of 70 ft. over E. slope to top of rim of bench, bears N. and S.

27.00 Top of E. rim of bench, bears N. and S.

40.14 The cor. of secs. 17, 18, 19, and 20.

Land, rolling.

Soil, deep sand and clay.

No timber; undergrowth of shadscale, greasewood, sage, black, and rabbit brush.

DEPENDENT RESURVEY OF SUBDIVISION, T. 12 S., R. 17 W.

Chains

From the cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the township.

S. 89°51' E., bet. secs. 18 and 19.

Over rolling bench land, through medium dense short undergrowth.

7.60 Shallow draw, drains S. 20° E.

18.40 Unimproved road on low rise, bears N. 30° W. and S. 30° E.

32.00 Top of E. rim of bench, bears N. and S.; descend 100 ft. over E. slope to the 1/4 sec. cor.

54.18 The 1/4 sec. cor. of secs. 18 and 19, which is marked by a cobble stone, 14 x 10 x 6 ins., firmly set, marked 1/4 on N. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

1/4  $\frac{S18}{S19}$

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

S. 89°48' E., beginning new measurement.

Continue over rolling bench land.

4.70 County road, bears N. 20° E. to Callao and S. 20° W. to Trout Creek.

31.00 Low rise, bears NW. and SE.

40.18 The cor. of secs. 17, 18, 19, and 20.

Land, rolling.

Soil, deep clay and sand.

No timber; undergrowth of shadscale, greasewood, sage, black, and rabbit brush.

N. 0°02' W., bet. secs. 17 and 18.

Over rolling desert land, through medium dense short undergrowth.

7.70 Shallow draw, drains NE., 75 lks. dist. to its junction with next draw.

9.20 Shallow draw, drains SE.

16.70 Draw, 40 ft. deep, drains E.

40.24 The 1/4 sec. cor. of secs. 17 and 18, which is marked by a cobble stone, 16 x 10 x 8 ins., firmly set, marked 1/4 on W. face.

At the cor. point:

DEPENDENT RESURVEY OF SUBDIVISION, T. 12 S., R. 17<sup>W</sup> E.

Chains

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$\frac{1}{2}$   
 S18 | S17  
 1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

N. 0°01' W., beginning new measurement.

Continue over rolling land.

13.50 Shallow draw, drains NE.

28.60 Unimproved road, bears N. 65°E. and S. 72° W.

29.30 Concrete flume, 5 lks. wide, 2 ft. deep, which carries water to Sharp's Ranch, bears N. 65° E. and S. 72° W. From this point, the SE. end of natural reservoir, bears N. 65° E., about 20.00 chs. dist.

40.19 The cor. of secs. 7, 8, 17, and 18, which is marked by a cobble stone, 18 x 10 x 10 ins., firmly set, marked 4 notches on S. edge and 5 notches on E. edge.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked

T12S R17E  
 S7 | SE  
 S18 | S17

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

Land, rolling.

Soil, deep sand and clay.

No timber; undergrowth of shadscale, greasewood, sage, and black brush.

From the cor. of secs. 8, 9, 16, and 17.

N. 89°57' W., bet. secs. 8 and 17.

Over rolling bench land, through medium dense short undergrowth.

1.20 Dry channel of Cedar Creek, 40 lks. wide, 5 ft. deep, drains SE.

3.20 Top of SW. rim of creek channel, bears NW. and SE.

12.80 Junction of unimproved road from the NE. with unimproved road bearing NW. and SE.

21.20 Concrete flume, 5 lks. wide, 2½ ft. deep, flows S. 66½° E.

31.50 Head house to flume from pipe line to the W., bears North, about 5.00 chs. dist.

## DEPENDENT RESURVEY OF SUBDIVISION, T. 12 S., R. 17 W.

Chains	
31.70	Wash, 30 lks. wide, 4 ft. deep, drains S.
40.22	The $\frac{1}{4}$ sec. cor. of secs. 8 and 17, which is marked by a cobble stone, 12 x 10 x 4 ins., firmly set, marked $\frac{1}{4}$ on N. face.  At the cor. point:  Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked  $\begin{array}{r} S8 \\ \frac{1}{4} \text{ ---} \\ S17 \\ \\ 1950 \end{array}$  Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.  <hr/> N. 89°51' W., beginning new measurement.  Ascend 70 ft. over E. slope to top of bench.
18.00	Top of E. rim of bench, bears N. and S.
21.50	Unimproved road, bears NE. and SW.
23.10	Concrete flume, 20 lks. wide, 2 ft. deep, flows NE., about 5.00 chs. dist. to outlet gate on E. edge of Natural reservoir; thence across reservoir.
35.50	Leave reservoir, bears N. and S.
40.24	The cor. of secs. 7, 8, 17, and 18.  Land, rolling. Soil, deep clay and sand. No timber; undergrowth of shadscale and greasewood.
	<hr/> From the cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the township.  S. 89°54' E., bet. secs. 7 and 18.  Descend gradual E. slope of rolling bench land, through medium dense short undergrowth.
13.20	Small draw, drains SE.
15.00	Top of E. rim of bench, bears N. and S.; descend 70 ft. over E. slope to the $\frac{1}{4}$ sec. cor.
37.10	Unimproved road, bears NW. and SE.
41.50	Draw near head, drains NE.
53.84	The $\frac{1}{4}$ sec. cor. of secs. 7 and 18, which is marked by a volcanic stone, 12 x 10 x 8 ins., firmly set, marked $\frac{1}{4}$ on N. face.  At the cor. point:  Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

DEPENDENT RESURVEY OF SUBDIVISION, T. 12 S., R. 17 W.

Chains

$\frac{1}{4}$   $\frac{S7}{S18}$

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

Cor. set at the top of E. rim of bench, bears N. and S.

S. 89°55' E., beginning new measurement.

Descend 70 ft. over general E. slope to the sec. cor.

- 8.00 Base of bench, bears N. and S.; thence over nearly level land.
- 23.40 County road, graded, bears N. to Callao and S. to Trout Creek.
- 40.20 The cor. of secs. 7, 8, 17, and 18.

Land, rolling.

Soil, deep clay and sand.

No timber; undergrowth of shadscale, greasewood, sage, black, and rabbit brush.

North, bet. secs. 7 and 8.

Over nearly level land near W. side of natural reservoir, through medium dense short undergrowth.

- 40.21 The  $\frac{1}{4}$  sec. cor. of secs. 7 and 8, which is marked by a granite stone, 16 x 16 x 14 ins., firmly set, marked  $\frac{1}{4}$  on W. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$\frac{1}{4}$   
S7 | S8  
1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

From the  $\frac{1}{4}$  sec. cor., the NW. cor. of a natural reservoir, bears East, 5.00 chs. dist.

N. 0°01' W., beginning new measurement.

Continue over nearly level land.

- 1.10 Ditch, 10 lks. wide, 2 ft. deep, drains E. to reservoir and bears N. 40° W., 4.00 chs. dist. to end of concrete pipe line from the NW.
- 27.70 County road, graded, bears N. 20° E. to Callao and S. 20° W. to Trout Creek.

DEPENDENT RESURVEY OF SUBDIVISION, T. 12 S., R. 17 W.

Chains

40.13

The cor. of secs. 5, 6, 7, and 8, which is marked by a granite stone, 20 x 12 x 8 ins., firmly set, marked 5 notches on S. and E. edges.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked

T12S	R17W
S6	S5
S7	S8

1950

Reset the stone cor. monument alongside the iron post and raise a mound of stone, 4 ft. base, 9 ins. high, around same.

Land, rolling.

Soil, deep clay and sand.

No timber; undergrowth of shadscale, greasewood, sage, black, and rabbit brush.

From the cor. of secs. 4, 5, 8, and 9.

N. 89°55' W., bet. secs. 5 and 8.

Over rolling bench land, through medium dense short undergrowth.

33.20

Dry channel of Cedar Creek, 60 lks. wide, 6 ft. deep, drains SE.

39.20

Wash, 40 lks. wide, 4 ft. deep, drains SE.

40.31

The 1/4 sec. cor. of secs. 5 and 8, which is marked by a granite stone, 12 x 10 x 8 ins., firmly set, marked 1/4 on N. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

1/4	S5
	S8

1950

Reset the stone cor. monument alongside the iron post and raise a small mound of stone around same.

N. 89°56' W., beginning new measurement.

Ascend 60 ft. over general E. slope of rolling bench land to the sec. cor.

36.00

County road, graded, bears N. 20° E. to Callao and S. 20° W. to Trout Creek.

40.13

The cor. of secs. 5, 6, 7, and 8.

Land, rolling.

## DEPENDENT RESURVEY OF SUBDIVISION, T. 12 S., R. 17 W.

Chains

Soil, deep gravel and sand.  
No timber; undergrowth of shadscale, greasewood, sage,  
black, and rabbit brush.

From the cor. of secs. 1, 6, 7, and 12, on the W. bdy.  
of the township.

S. 89°56' E., bet. secs. 6 and 7.

Over rolling bench land, through medium dense short  
undergrowth; descend 160 ft. over general E. slope to the  
¼ sec. cor.

19.50 Shallow draw, drains NE.

38.30 Concrete flume, 5 lks. wide, 2½ ft. deep, which carries  
water from Cedar Creek to Sharp's ranch, flows SE.; enter  
lower bench land, bears NW. and SE.

53.79 The ¼ sec. cor. of secs. 6 and 7, which is marked by a  
granite stone, 12 x 10 x 10 ins., firmly set, marked ¼ on  
N. face..

At the cor. point:

Set an iron post, ¾ ft. long, 1 in. in diam., 27 ins. in  
the ground, with brass cap marked

$$\frac{S6}{\frac{1}{4}}$$

.S7

1950

Reset the stone cor. monument alongside the iron post and  
raise a small mound of stone around same.

East, beginning new measurement.

Continue over rolling bench land.

15.50 Top of E. rim of bench, bears N. 20° W. and S.; descend  
120 ft. over general E. slope to the sec. cor.

30.00 Base of descent from bench, bears N. and S.

40.29 The cor. of secs. 5, 6, 7, and 8.

Land, rolling.  
Soil, shallow and deep clay and sand.  
No timber; undergrowth of shadscale, greasewood, sage,  
black, and rabbit brush.

N. 0°03' W., bet. secs. 5 and 6.

Over rolling bench land, through medium dense short  
undergrowth.

14.50 Shallow draw, drains NE.

16.00 Unimproved road, bears NW. and SE.

29.40 Wash, 40 lks. wide, 4 ft. deep, drains E. at base of bench,  
bears E. and W.; ascend 60 ft. to top of bench.

## DEPENDENT RESURVEY OF SUBDIVISION, T. 12 S., R. 17 W.

Chains

- 39.50 Top of S. rim of bench, bears NE. and NW.
- 40.94 The  $\frac{1}{4}$  sec. cor. of secs. 5 and 6, which is marked by a cobble stone, 16 x 8 x 8 ins., firmly set, marked  $\frac{1}{4}$  on W. face.
- At the cor. point:
- Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked
- $\frac{1}{4}$   
S6 | S5  
1950
- Reset the stone cor. monument alongside the iron post and raise a mound of stone, 4 ft. base, 9 ins. high, around same.
- 
- N. 0°04' W., beginning new measurement.
- Continue over rolling bench land.
- 10.60 Shallow draw, drains E.
- 19.70 Top of S. rim of Cedar Creek, bears S. 80° E. and N. 80° W.
- 29.30 Dry channel of Cedar Creek, 40 lks. wide, 4 ft. deep, drains S. 80° E.
- 35.70 Top of N. rim of Cedar Creek, bears S. 80° E. and N. 80° W.
- 49.80 Shallow draw, drains S. 80° E.; unimproved road in bottom of same, bears S. 80° E. and N. 80° W.
- 51.65 The closing cor. of secs. 5 and 6 on the N. bdy. of the township, which is marked by a cobble stone, 14 x 6 x 6 ins., firmly set, marked 1 groove on W. face, 5 grooves on E. face, and CC on S. face.
- At the cor. point:
- Set an iron post, 3 ft. long, 3 ins. in diam., 27 ins. in the ground, with brass cap marked
- T11S R17W  
S32  
-----  
S6 | S5  
T12S R17W  
C C  
1950
- Reset the stone cor. monument alongside the iron post and raise a mound of stone, 4 ft. base, 9 ins. high, around same.
- From this closing cor., the cor. of secs. 31 and 32, T. 11 S., R. 17 W., bears S. 89°51' W., 11.84 chs. dist.
- Land, rolling.  
Soil, deep sand and gravel.  
No timber; undergrowth of shadscale, greasewood, sage, rabbit, and black brush.

ESTABLISHMENT OF QUARTER-SECTION CORNERS ON N. BDY., T. 12S., R. 17W.

The point for the N.  $\frac{1}{4}$  sec. cor. of sec. 1 is at midpoint bet. the cor. of T's. 11 and 12 S., Rs. 16 and 17 W., and the closing cor. of secs. 1 and 2.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$\frac{1}{4}$  S1

1950

Raise a small mound of stone around the corner monument.

From this  $\frac{1}{4}$  sec. cor., the  $\frac{1}{4}$  sec. cor. of sec. 36, T. 11 S., R. 17 W., bears S.  $89^{\circ}42'$  W., 1.55 chs. dist.

The point for the N.  $\frac{1}{4}$  sec. cor. of sec. 2 is at midpoint bet. the closing cor. of secs. 1 and 2 and the closing cor. of secs. 2 and 3.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$\frac{1}{4}$  S2

1950

Raise a small mound of stone around the corner monument.

From this  $\frac{1}{4}$  sec. cor., the  $\frac{1}{4}$  sec. cor. of sec. 35, bears S.  $89^{\circ}49'$  W., 4.62 chs. dist.

The point for the N.  $\frac{1}{4}$  sec. cor. of sec. 3 is at midpoint bet. the closing cor. of secs. 2 and 3 and the closing cor. of secs. 3 and 4.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$\frac{1}{4}$  S3

1950

Raise a small mound of stone around the corner monument.

From this  $\frac{1}{4}$  sec. cor., the  $\frac{1}{4}$  sec. cor. of sec. 34, bears S.  $89^{\circ}29'$  W., 7.38 chs. dist.

The point for the N.  $\frac{1}{4}$  sec. cor. of sec. 4 is at midpoint bet. the closing cor. of secs. 3 and 4 and the closing cor. of secs. 4 and 5.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$\frac{1}{4}$  S4

1950

Raise a small mound of stone around the corner monument.

ESTABLISHMENT OF QUARTER-SECTION CORN. ON N. EDY., T. 12 S., R. 17 W.

Chains

From this  $\frac{1}{4}$  sec. cor., the  $\frac{1}{4}$  sec. cor. of sec. 35, bears S.  $89^{\circ}49'$  W., 10.18 chs. dist.

The point for the N.  $\frac{1}{4}$  sec. cor. of sec. 5 is at midpoint bet. the closing cor. of secs. 4 and 5 and the closing cor. of secs. 5 and 6.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$\frac{1}{4}$  S5

1950

Raise a small mound of stone around the corner monument.

From this  $\frac{1}{4}$  sec. cor., the  $\frac{1}{4}$  sec. cor. of sec. 32, bears S.  $89^{\circ}45'$  W., 11.99 chs. dist.

The point for the N.  $\frac{1}{4}$  sec. cor. of sec. 6 is at proportionate distance bet. the closing cor. of secs. 5 and 6 and the cor. of Ts. 11 and 12 S., R. 17 W.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$\frac{1}{4}$  S6

1950

Raise a small mound of stone around the corner monument.

From this  $\frac{1}{4}$  sec. cor., the  $\frac{1}{4}$  sec. cor. of sec. 31, bears N.  $89^{\circ}33'$  W., 13.21 chs. dist.

GENERAL DESCRIPTION OF T. 12 S., R. 17 W.

The land within the boundaries of T. 12 S., R. 17 W., Salt Lake Meridian, Utah, is located at the base of the high rugged Deep Creek Mountains to the west. It consists of a series of rolling and broken benches which slope abruptly to the southeast to a large nearly level clay flat located in the southeast portion of the township.

The elevation of the northwest part of the township is about 5,000 feet above sea level while that at the southeast portion is about 4,500 feet.

The soil in the central southeast portion of the township is a deep clay while that of the remaining portion is a deep loose coarse granite sand. The only portion of the township that is suitable for farming is the clay soil in the southeast portion. Crops cannot be produced without irrigation and the soil of the remainder of the township is so loose and coarse that it is impossible to irrigate it.

Sharp's ranch is located in the central southeast portion of the township. This ranch has about 200 acres of land under cultivation, the main crop being alfalfa. The land is irrigated by the water from Cedar and Granite Creeks. During the early spring months of the year the water from these creeks flows to the ranch through their

## GENERAL DESCRIPTION OF T. 12 S., R. 17 W.

natural channels but about the first of June the water becomes less and when it enters the loose sandy bench lands it sinks and has to be carried through well built concrete pipe lines and flumes to the ranch. About the first of September the water is so low in these two streams that very little of it reaches the ranch.

No timber is found on the township and the undergrowth consists of a medium dense short growth of shadscale, sage, black, and rabbit brush, which affords fair grazing for stock during the winter months of the year.

A graded dirt road enters the township on the south boundary of section 31 and bears northerly about 15 miles to Callao, Utah, and southerly about 6 miles to Trout Creek, Utah. A graded and gravelled road bears southeasterly through section 1, to Delta and Nephi, Utah, and northwesterly to Callao. Numerous other unimproved roads were found throughout the township.

No indications of coal, oil, oil shale, or mineral were found in the township.



CERTIFICATE OF CADASTRAL ENGINEER

I, Elliot Bird, Cadastral Engineer, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 1st day of May 1951 I have ~~surveyed~~ dependently resurveyed the Willow Springs Guide Meridian through Ts. 12 S., between Rs. 17 and 18 W., the north and east boundaries and subdivision of T. 12 S., R. 17 W.,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

February 15, 1951.  
Salt Lake City, Utah.

*Elliot Bird*  
Cadastral Engineer

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,  
Washington, D. C., AUG 26 1952, 19

The foregoing field notes of the ~~survey of dependent resurvey of the Willow Springs~~ Guide Meridian through Ts. 12 S., between Rs. 17 and 18 W., The north and east boundaries and subdivision of T. 12 S., R. 17 W., of the Salt Lake Meridian,

executed by Elliot Bird, Cadastral Engineer

having been critically examined and found correct, are hereby approved.

*Donald Clement*  
Acting Chief, Division of Cadastral Engineering.

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY~~ that the foregoing transcript of the field notes of the above-described surveys in ~~is~~ is a true copy of the original field notes.

Chief, Division of Cadastral Engineering.

RECEIVED  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
SALT LAKE CITY, UTAH



UNITED STATES  
DEPARTMENT OF THE INTERIOR  
~~GENERAL LAND OFFICE~~

Bureau of Land Management

FIELD NOTES

OF THE

INDEPENDENT RESURVEY OF THE GUIDE MERIDIAN, T. 19 S., BETWEEN Rs. 5 AND  
R. 6 W., AND THE NORTH BOUNDARY OF T. 20 S., R. 6 W., AND INDEPENDENT RESURVEY OF  
SUBDIVISION OF T. 19 S., R. 6 W.,

Of the Salt Lake Meridian,

the State of Utah

EXECUTED BY

Elliot Bird, Cadastral Engineer

Andrew Nelson, Cadastral Engineer

Robert C. Yundt, Cadastral Engineer

J.C. Clark, Cadastral Engineer

Under special instructions dated April 7, 1939, which provided  
the surveys included under Group No. 299, bearing the approval of the  
Commissioner of the General Land Office under date of May 25, 1939

Supplemental  
Assignment instructions dated May 29, 1945.

Survey commenced June 23, 1945.

Survey completed July 5, 1945.

# INDEX DIAGRAM.

Township 19 South, Range 6 West  
 53 53

51	6	52	5	39	4	32	3	24	2	18	1	11
	50		50		38		31		24		17	
51	7	49	8	38	9	31	10	23	11	16	12	9
	48		48		37		30		23		16	
49	18	47	17	37	18	29	15	22	14	15	18	8
	46		45		36		29		21		15	
47	19	45	20	35	21	28	22	21	23	14	24	7
	44		43		35		28		20		13	
45	20	42	29	34	28	27	27	20	26	13	25	6
	41		40		33		26		19		12	
42	21	40	32	33	33	25	34	18	35	12	26	5
	5		4		3		3		2		1	

1077

4-679 b

# INDEX DIAGRAM.

Township 19 South, Range 6 West

6	5	4	3	2	1
7	8	9	10	11	12
13	17	16	15	14	13
19	20	21	22	23	24
20	29	28	27	26	25
31	32	33	34	35	36

6-4817

- Lines surveyed by Elliot Bird
- " " " Andrew Nelson
- " " " Robert C. Yundt

**Blank**

**Page**

T. 19 S., R. 6 W.

The boundaries and subdivisional lines of T. 19 S., R. 6 W., Salt Lake Meridian, Utah, were surveyed by Chas. Mogo, in 1857. The returns of this survey on file in this office are copies of the General Land Office plat and field notes bearing date of certification of February 19, 1902 and January 14, 1903. Under date of November 30, 1868, the Surveyor General of Utah, requested information on the status of (among others) the survey of T. 19 S., R. 6 W. The Commissioner's letter in answer dated January 29, 1869, is to the effect that the Mogo surveys were rejected and that future surveys in this area be executed without reference to the Mogo surveys.

The survey was commenced June 23, 1945, and executed by Elliot Bird, Andrew Nelson, Robert C. Yundt, and J. C. Clark, Cadastral Engineers, using Buff and Buff solar transits Nos. 16726, 23831, 18003, and 9797. For full description and tests of the instruments, see that given in the official record of the resurvey of T. 19 S., R. 6 W. of this group.

All azimuth determinations were made by reference to true meridians established by observations made upon Polaris during the progress of the work. The lines of the survey were carried forward by transit lines, taking the mean of direct and reversed sights at each instrument station.

The measurements were made with Lallie steel tapes 5 and 8 chains in length. The tapes were graduated every link for the first 100 links and thereafter at intervals of 10 links. The tapes were tested and found correct, comparison being made with a Lufkin standard steel tape 1 chain in length. The measurements were made on the slope, the vertical angle of each interval determined with clinometers and the slope measurements properly reduced to true horizontal distances which appear in this record.

The geographic position of the southeast corner of the township, is approximately as follows; latitude  $39^{\circ}07' N.$ , and longitude  $112^{\circ}28' W.$

DEPENDENT RESURVEY NORTH BOUNDARY, T. 20 S., R. 6 W.

Reestablishment of surveys executed by Andrew Nelson, Surveyor, in 1934, under Group 255, Utah.

Note; this resurvey was made in order to establish corners for control of the subdivisional surveys in T. 19 S., R. 6 W., and the topography and distance of the boundary were found to agree with that of the official record of the 1934 survey.

The cor. of Ts. 19 and 20 S., Rs. 5 and 6 W., is marked by an iron post, 3 ins. in diam.; firmly set, properly marked and witnessed as described in the official record of the survey of T. 20 S., R. 6 W., Group 255, Utah.

Thence, from the above cor.

N.  $89^{\circ}49' W.$ , along the S. bdy. of sec. 36, T. 19 S. R. 6 W.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of sec. 36.

Set an iron post, 3 ft. long, 1 in. in diam., 10 ins. in the ground to solid rock and in a large mound of stone, with brass cap marked

$\frac{1}{4}$  S36  
1945

Deposit broken glass at the base of the post.

40.265 The original  $\frac{1}{4}$  sec. cor. of sec. 36, which is marked by an iron post, 1 in. in diam., firmly set and properly marked and witnessed as described in the official record of the survey of T. 20 S., R. 6 W. I efface the marks on the brass cap of the cor. monument that pertain to sec. 36, and mark same "AP" for an angle point.

## DEPENDENT RESURVEY NORTH BOUNDARY, T. 20 S., R. 6 W.

Chains

- 42.80 The  $\frac{1}{4}$  sec. cor. of sec. 1, which is marked by an iron post, 1 in. in diam., firmly set, properly marked and witnessed as described in the official record.
- 80.00 Point for the cor. of secs. 35 and 36.  
Set an iron post, 3 ft. long, 2 ins. in diam., 10 ins. in the ground to solid rock and in a large mound of stone, with brass cap marked
- |      |     |
|------|-----|
| T19S | R6W |
| S35  | S36 |
| T20S | R6W |
| S1   |     |
| 1945 |     |
- N. 89°49' W., along the S. bdy. of sec. 35.
- 0.53 The original cor. of secs. 35 and 36, which is marked by an iron post, 2 ins. in diam., firmly set properly marked and witnessed as described in the official record. I efface the marks on the brass cap of the cor. monument that pertain to secs. 35 and 36 and mark same "AP" for an angle point.
- 2.80 The closing cor. of secs. 1 and 2, T. 20 S., R. 6 W., which is marked by an iron post, 2 ins. in diam., firmly set, properly marked and witnessed as described in the official record.
- 40.00 Point for the  $\frac{1}{4}$  sec. cor. of sec. 35.  
Set an iron post, 3 ft. long, 1 in. in diam., 4 ins. in the ground to solid rock and in a large mound of stone, with brass cap marked
- |                   |
|-------------------|
| $\frac{1}{4}$ S35 |
| 1945              |
- Deposit broken glass at the base of the post.
- 40.795 The original  $\frac{1}{4}$  sec. cor. of sec. 35, which is marked by an iron post, 1 in. in diam., firmly set, properly marked and witnessed as described in the official record, of the survey of T. 20 S., R. 6 W. I efface the marks on the brass cap of the cor. monument and mark same "AP" for an angle point.
- 42.825 The  $\frac{1}{4}$  sec. cor. of sec. 2, which is marked by an iron post 1 in. in diam., firmly set, properly marked and witnessed as described in the official record.
- 80.00 Point for the cor. of secs. 34 and 35.  
Set an iron post, 3 ft. long, 2 ins. in diam., 12 ins. in the ground to solid rock and in a large mound of stone, with brass cap marked
- |      |     |
|------|-----|
| T19S | R6W |
| S34  | S35 |
| T20S | R6W |
| S2   |     |
| 1945 |     |
- Deposit broken glass at the base of the post.
- N. 89° 49' W., along the S. bdy. of sec. 34.
- 1.06 The original cor. of secs. 34 and 35, which is marked by an iron post, 2 ins. in diam., firmly set, properly marked and witnessed as described in the official record. I efface the marks on the brass cap of the cor. monument that pertain to secs. 34 and 35 and mark same "AP" for an angle point.

DEPENDENT RESURVEY NORTH BOUNDARY, T. 20 S., R. 6 W.

Chains

- 2.85 The closing cor. of secs. 2 and 3, which is marked by an iron post, 2 ins. in diam., firmly set, properly marked and witnessed as described in the official record.
- 40.00 Point for the  $\frac{1}{4}$  sec. cor. of sec. 34.  
Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground and small mound of stone, with brass cap marked  
 $\frac{1}{4}$  S34  
1945  
Deposit broken glass at the base of the post.
- 41.325 The  $\frac{1}{4}$  sec. cor. originally set for sec. 34, which is marked by an iron post, 1 in. in diam., firmly set, properly marked and witnessed as described in the official record. I efface the marks on the brass cap of the cor. monument that pertain to sec. 34, and mark same "AP" for an angle point.
- 42.875 The  $\frac{1}{4}$  sec. cor. of sec. 3, which is marked by an iron post, 1 in. in diam., firmly set, properly marked and witnessed as described in the official record.
- 80.00 Point for the cor. of secs. 33 and 34.  
Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground and small mound of stone, with brass cap marked  
T19S R6W  
S33 S34  
T20S R6W  
S3  
1945  
Deposit broken glass at the base of the post.

N. 89°49' W., along the S. bdy. of sec. 33.

- 1.59 The original cor. of secs. 33 and 34, which is an iron post, 2 ins. in diam., firmly set, properly marked and witnessed as described in the official record. I efface the marks on the brass cap of the cor. monument and mark same "AP" for an angle point.
- 2.90 The closing cor. of secs. 3 and 4, which is marked by an iron post, 2 ins. in diam., firmly set, properly marked and witnessed as described in the official record.
- 40.00 Point for the  $\frac{1}{4}$  sec. cor. of sec. 33.  
Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground and small mound of stone, with brass cap marked  
 $\frac{1}{4}$  S33  
1945  
Deposit broken glass at the base of the post.
- 41.855 The  $\frac{1}{4}$  sec. cor. originally set for sec. 33, which is marked by an iron post, 1 in. in diam., firmly set, properly marked and witnessed as described in the official record. I efface the marks on the brass cap of the cor. monument and mark same "AP" for an angle point.

DEPENDENT RESURVEY NORTH BOUNDARY, T. 20 S., R. 6 W.

Chains

42.98 The  $\frac{1}{2}$  sec. cor. of sec. 4, which is marked by an iron post, 1 in. in diam., firmly set, properly marked and witnessed as described in the official record.

90.00 Point for the cor. of secs. 32 and 33.

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground and small mound of stone, with brass cap marked

T19S	R6W
S32	S33

T20S R6W  
S4

1945

Deposit broken glass at the base of the post.

N. 89°49' W., along the S. bdy. of sec. 32.

2.12 The original cor. of secs. 32 and 33, which is marked by an iron post, 2 ins. in diam., firmly set, properly marked and witnessed as described in the official record. I efface the marks on the brass cap of the cor. monument and mark same "AP" for an angle point.

3.06 The closing cor. of secs. 4 and 5, which is marked by an iron post, 2 ins. in diam., firmly set, properly marked and witnessed as described in the official record.

40.00 Point for the  $\frac{1}{2}$  sec. cor. of sec. 32.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground and small mound of stone, with brass cap marked

S32

1945

Deposit broken glass at the base of the post.

42.325 The original  $\frac{1}{4}$  sec. cor. of sec. 32, which is marked by an iron post, 1 in. in diam., firmly set, properly marked and witnessed as described in the official record. I efface the marks on the brass cap of the cor. monument and bearing tree and mark same "AP" for an angle point.

42.855 The  $\frac{1}{4}$  sec. cor. sec. 5, which is marked by an iron post, 1 in. in diam., firmly set, properly marked and witnessed as described in the official record.

90.00 Point for the cor. of secs. 31 and 32.

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground and small mound of stone, with brass cap marked

T19S	R6W
S31	S32

S5  
T20S

1945

Deposit broken glass at the base of the post.

## DEPENDENT RESURVEY NORTH BOUNDARY, T. 20 S., R. 6 W.

Chains

N. 89°49' W., along the S. bdy. sec. 31.

2.65 The cor. set for secs. 5, 6, 31, and 32, which is an iron post, 2 ins. in diam., firmly set, properly marked and witnessed as described in the official record. I efface the marks on the brass cap of the cor. monument and bearing tree that pertain to secs. 31 and 32, and cor. now functions for secs. 5 and 6 only.

40.00 Point for the  $\frac{1}{4}$  sec. cor. sec. 31.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground and small mound of stone, with brass cap marked

 $\frac{1}{4}$  S31

1945

Deposit broken glass at the base of post.

42.65 The  $\frac{1}{4}$  sec. cor. sec. 6, which is marked by an iron post, 1 in. in diam., firmly set, properly marked and witnessed as described in the official record.

42.915 The  $\frac{1}{4}$  sec. cor. set for sec. 31, which is marked by an iron post, 1 in. in diam., firmly set, properly marked and witnessed as described in the official record. I efface the marks on the brass cap of the cor. monument and mark same "AP" for an angle point.

83.18 The cor. of Ts. 19 S., Rs. 6 and 7 W., which is marked by an iron post, 3 ins. in diam., firmly set, properly marked and witnessed as described in the official record of the survey of T. 20 S., R. 6 W., Group 255, Utah.

## DEPENDENT RESURVEY GUIDE MERIDIAN, T.19S., BET.Rs.5 AND 6W.

Reestablishment of surveys executed by Julien Bausman, U.S. Deputy Surveyor, in 1869.

From the cor. of Ts. 19 and 20 S., Rs. 5 and 6 W., from which a recently constructed barbed wire fence bears N. 89°49' W. and N. 57° E.

N. 0°08' E., along the W. bdy. of sec. 31, T. 19 S., R. 5 W.

Over slightly rolling land, through medium dense short undergrowth.

40.00 Point for the  $\frac{1}{4}$  sec. cor. sec. 36.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

 $\frac{1}{4}$  S36

1945

Deposit broken glass at the base of the post.

40.83 The  $\frac{1}{4}$  sec. cor. originally set for secs. 31 and 36, which is marked by the original cor. monument, a lava stone, 12 x 6 x 4 ins., loosely set, properly marked and not witnessed. Cor. now will function for the  $\frac{1}{4}$  sec. cor. sec. 31 only.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with the original cor. monument deposited at the base of the post, with brass cap marked

## DEPENDENT RESURVEY GUIDE MERIDIAN, T. 18 S., R. 5 AND 6

Chains

1831

1945

No other accessories available.

Continue on same course beginning new measurement.

39.17 Point for the cor. of secs. 25 and 36.

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked

T19S	T19S
S25	R5W
S36	S31
R6W	

1945

Deposit broken glass at the base of the post.

40.75 The cor. originally set for secs. 25, 30, 31, and 36, which is marked by a decayed juniper post, 3 ft. long, 3 ins. in diam., firmly set in a small mound of earth. No marks remaining on post.

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with the original cor. monument deposited alongside, with brass cap marked

T19S	T19S
R6W	S30
S25	S31
	R5W

1945

Deposit broken glass at the base of the post.

Land, nearly level.

Soil, deep sandy clay; 4th rate.

No timber.

Undergrowth, shadscale, greasewood, and yellow top.

Fair grazing land.

N. 0°08' E., along the W. bdy. of sec. 30.

Over nearly level land with low sand dunes, through medium dense short undergrowth.

8.00 Low sand rise, bears NE. and SW.

38.42 Point for the  $\frac{1}{4}$  sec. cor. sec. 25, which is at a northing of 40.00 chs. from the cor. of secs. 25 and 36.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

 $\frac{1}{4}$  S25

1945

Deposit broken glass at the base of the post.

40.72 The  $\frac{1}{4}$  sec. cor. originally set for secs. 25 and 30, which is marked by the original cor. monument, a decayed juniper post

## DEPENDENT RESURVEY GUIDE MERIDIAN, T. 18 S., BET. Rs. 5 AND 6 W.

Chains

3 ft. long, 3 ins. in diam.; firmly set in mound of earth.  
No marks remaining on post.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in  
the ground, with the original cor. monument buried along-  
side, with brass cap marked

1/4	S30
-----	-----

1945

Deposit broken glass at the base of the post.

Thence:

N. 0°06' E., along the W. bdy. of sec. 30.

32.40 Low sand rise, bears NE. and SW.

35.50 Unimproved road, bears NE. and SW.

37.70 Point for the cor. of secs. 24 and 25, which is at a  
northing of 80.00 chs. from the cor. of secs. 25 and 36.

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in  
the ground, with brass cap marked

T19S	T19S
S24	
	R5W
S25	
R6W	S30

1945

Deposit broken glass at the base of the post.

40.68 Proportionate point for the cor. of secs. 19 and 30, at  
the S. end of barbed wire fence bearing N. and S. No trace  
of the original cor. monument could be found.

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in  
the ground, with brass cap marked

T19S	T19S
	S19
R6W	
	S30
S24	R5W

1945

Deposit broken glass at the base of the post.

Land, nearly level with low sand dunes.

Soil, deep sandy clay; 4th rate.

No timber.

Undergrowth, greasewood, shadscale, and salt weed.

Fair grazing land.

N. 0°06' E., along the W. bdy. of sec. 19.

Over nearly level land, through medium dense short under-  
growth, along barbed wire fence bearing N. and S.

37.02 Point for the 1/4 sec. cor. sec. 24, which is at a northing  
of 40.00 chs. from the cor. of secs. 24 and 25.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in

## DEPENDENT RESURVEY GUIDE MERIDIAN, T. 18 S., BET. R. 5 AND 6 W.

Chains the ground, with brass cap marked

$\frac{1}{4}$  S24 |  
1945

Deposit broken glass at the base of the post.

40.68 The cor. which was originally set for the  $\frac{1}{4}$  sec. cor. secs. 19 and 24, which is marked by the original cor. monument, a juniper post, 3 ft. long, 3 ins. in diam., firmly set in a small mound of earth. No visible marks found on post, which is in fence line bearing N. and S.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with the original cor. monument buried alongside, with brass cap marked

$\frac{1}{4}$  S19  
1945

Deposit broken glass at the base of the post.

Thence; N. 0°11' E., bet. secs, 19 and 24.

17.50 Dim road, bears N. 60° W. and S. 60° E.

36.34 Point for the cor. of secs. 13 and 24, which is at a northing of 80.00 chs. from the cor. of secs. 24 and 25.

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked

T19S	T19S
S13	R5W
S24	S19
R6W	

1945

Deposit broken glass at the base of the post.

40.59 Proportionate point for the cor. of secs. 18 and 19; no trace of the original cor. monument could be found.

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked

T19S	T19S
R6W	S18
S13	S19
	R5W

1945

Deposit broken glass at the base of the post.

Land, nearly level.

Soil, deep sandy clay; 4th rate.

No timber.

Undergrowth, greasewood, shadscale, and salt weed.

Fair grazing land.

N. 0°11' E., along the W. bdy. sec. 18.

Over nearly level land, through medium dense short undergrowth.

## DEPENDENT RESURVEY GUIDE MERIDIAN, T. 18 S., BET. Rs. 5 AND 6 W.

Chains

- 25.80 Low sand dunes, bears E. and W.
- 35.75 Point for the  $\frac{1}{4}$  sec. cor. sec. 13, which is at a northing of 40.00 chs. from the cor. of secs. 13 and 24.  
Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked  
 $\frac{1}{4}$  S13 |  
1945  
Deposit broken glass at the base of the post.
- 40.59 Proportionate point for the  $\frac{1}{4}$  sec. cor. sec. 18; in fence line bearing N. and S.  
Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked  
 $\frac{1}{4}$  S18 |  
1945  
Deposit broken glass at the base of the post.
- 75.75 Point for the cor. of secs. 12 and 13, which is a northing of 80.00 chs. from the cor. of secs. 13 and 24.  
Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked  
T19S T19S  
S12 |  
R5W  
S13 |  
R6W | S18  
1945  
Deposit broken glass at the base of the post.
- 81.18 Proportionate point for the cor. of secs. 7 and 18; no trace of the original cor. monument could be found; in fence line bearing N. and S.  
Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked  
T19S T19S  
R6W | S7  
S12 | S18  
R5W  
1945  
Deposit broken glass at the base of the post.  
Land, nearly level.  
Soil, deep sandy clay; 4th rate.  
No timber.  
Undergrowth, greasewood, shadscale, and salt weed.  
Fair grazing land.


N. 0°11' E., along the W. bdy. sec. 7.

Over nearly level land, through medium dense short undergrowth, along fence line bearing N. and S.

DEPENDENT RESURVEY GUIDE MERIDIAN, T. 18 S., R. 5 AND 6 W.

Chains

15.10 The NW. cor. of fence bearing E. and S.  
 16.60 Enter clay and salt weed basin, bears E. and W.  
 34.57 Point for the  $\frac{1}{4}$  sec. cor. sec. 12, which is a northing of 40.00 chs. from the cor. of secs. 12 and 13.  
 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked




Deposit broken glass at the base of the post.

39.80 Enter barren clay flat and water, bears NW. and SE.

40.59 Proportionate point for the  $\frac{1}{4}$  sec. cor. sec. 7; no trace of the original  $\frac{1}{4}$  sec. cor. could be found; in barren clay flat, in mud and water.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked




Deposit broken glass at the base of the post.

48.60 Leave barren clay flat and mud and water, bears NW. and SE. thence ascend over low rise.

52.60 Low rise, bears NW. and SE.

74.57 Point for the cor. of secs. 1 and 12, which is a northing of 80.00 chs. from the cor. of secs. 12 and 13.

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked




1945

Deposit broken glass at the base of the post.

81.18 The cor. originally set for secs. 1, 6, 7, and 12, which is marked by the original cor. monument, a juniper post, 3 ft. long, 3 ins. in diam., firmly set in a small mound of earth. No visible marks found on post.

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with the original cor. monument buried alongside, with brass cap marked



1945

Deposit broken glass at the base of the post.

## DEPENDENT RESURVEY GUIDE MERIDIAN, T. 18 S., BET. Rs. 5 AND 6 W.

## Chains

Land, nearly level.  
Soil, deep sandy clay; 4th rate.  
No timber.  
Undergrowth, greasewood, shadscale, and salt weed.  
Fair grazing land.

N.  $0^{\circ}14'$  E., along the W. bdy. of sec. 6.

Over nearly level land, through medium dense short undergrowth.

14.20 Old unimproved road, bears S.  $50^{\circ}20'$  E. and N.  $50^{\circ}20'$  W.

21.20 Dim old road, bears NE. and SW.

33.39 Point for the  $\frac{1}{4}$  sec. cor. sec. 1, which is at a northing of 40.00 chs. from the cor. of secs. 1 and 12.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$\frac{1}{4}$  S1 |

1945

Deposit broken glass at the base of the post.

39.85 Proportionate point for the  $\frac{1}{4}$  sec. cor. sec. 6; no trace of the original  $\frac{1}{4}$  sec. cor. could be found.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

|  $\frac{1}{4}$  S6

1945

Deposit broken glass at the base of the post.

Thence over low sand hummocks.

73.39 Point for the cor. of lots 1 and 8, sec. 1, which is at a northing of 80.00 chs. from the cor. of secs. 1 and 12.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

1  
S1— |  
8

1945

Deposit broken glass at the base of the post.

79.69 The cor. of Ts. 18 and 19 S., Rs. 5 and 6 W., which is marked by an iron post, 3 ins. in diam., firmly set, properly marked and witnessed as described in the official record of the resurvey of T. 18 S., R. 6 W., of this group.

Land, nearly level with low sand dunes.  
Soil, deep sandy clay and loose sand; 4th rate.  
No timber.  
Undergrowth, greasewood, shadscale, sagebrush, and weeds.  
Fair grazing land.

INDEPENDENT RESURVEY OF THE  
SUBDIVISION OF T. 19 S., R. 6 W., WASHINGTON

Chains

Note; the survey of T. 19 S., R. 6 W., executed by Chas. Mogo in 1857, was cancelled by letter from the Commissioner of the General Land Office, dated Jan. 29, 1869, and no corners of this survey were found.


From the cor. of secs. 35 and 36, on the S. bdy. of the township, in fence line bearing E. and W.

N. 0°09' E., bet. secs: 35 and 36, parallel to the E. bdy. of the township.

Over nearly level land, through medium dense short undergrowth.

40.00 Point for the  $\frac{1}{4}$  sec. cor. secs. 35 and 36.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked




Deposit broken glass at the base of the post.

52.80 Dim old road, bears NE. and SW.

80.00 Point for the cor. of secs. 25, 26, 35, and 36.

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked



Deposit broken glass at the base of the post.

Land, nearly level.

Soil, deep sandy clay; 4th rate.

No timber.

Undergrowth, greasewood, shadscale, sagebrush, and weeds.

Fair grazing land.

S. 89°49' E., on random line, bet. secs. 25 and 36.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.00 Intersect the E. bdy. of the township, 3 lks. N. of the cor. of secs. 25 and 36.

Thence:

N. 89°48' W., on true line, bet. secs. 25 and 36.

Over nearly level land, through medium dense short undergrowth.

40.00 Point for the  $\frac{1}{4}$  sec. cor. secs. 25 and 36.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
U. S. DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
WASHINGTON, D. C.

825  
826

1945

Deposit broken glass at the base of the post.

85.00 Dim old road, bears N. 20° W. and S. 20° E.

95.00 Dim old road, bears NE. and SW.

80.00 The cor. of secs. 25, 26, 35, and 36.

Land, nearly level.  
Soil, deep sandy clay; 4th rate.  
No timber.  
Undergrowth, greasewood, shadscale, sagebrush, and weeds.  
Fair grazing land.

N. 0°09' E., bet. secs. 25 and 26.

Over nearly level land, through medium dense short undergrowth.

40.00 Point for the 1/4 sec. cor. secs. 25 and 26.

Set an iron post, 1 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked




Deposit broken glass at the base of the post.

47.10 Dim old road, bears N. 60° E. and S. 60° W.

74.80 Dim old road, bears N. 20° W. and S. 20° E.

80.00 Point for the cor. of secs. 23, 24, 25, and 26.

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked



Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor., and deposit glass at the base of the post.

Land, nearly level.  
Soil, deep sandy clay; 4th rate.  
No timber.  
Undergrowth, greasewood, shadscale, sagebrush, and weeds.  
Fair grazing land.

S. 20°12' E., on random line, bet. secs. 24 and 25.

40.00 Set temp. 1/4 sec. cor.

INDEPENDENT RESURVEY OF THE  
SUBDIVISION OF T. 16 S., R. 6 W.

Chains

79.94 Intersect the cor. of secs. 24 and 25, on the E. bdy. of the township.


Thence:

N. 89°48' W., on true line, bet. secs. 24 and 25.

Over nearly level land, through medium dense short undergrowth.

39.97 Point for the  $\frac{1}{4}$  sec. cor. secs. 24 and 25.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked



1945

Raise a mound of stone, 2 ft base,  $1\frac{1}{2}$  ft. high, N. of cor. and deposit broken glass at the base of the post.

61.50 Dim old road, bears N. and S. 10° W.

79.94 The cor. of secs. 23, 24, 25, and 26.

Land, nearly level.

Soil, deep sandy clay; 4th rate.

No timber.

Undergrowth, greasewood, shadscale, sagebrush, and weeds.


Fair grazing land.

N. 0°09' E., bet. secs. 23 and 24.

Over nearly level land, through medium dense short undergrowth.

40.00 Point for the  $\frac{1}{4}$  sec. cor. secs. 23 and 24.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked




1945

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor. and deposit broken glass at the base of the post.

80.00 Point for the cor. of secs. 13, 14, 23, and 24.

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked



1945

Deposit broken glass at the base of the post.

Land, nearly level.

Soil, deep sandy clay; 4th rate.

INDEPENDENT RESURVEY OF THE  
SUBDIVISION OF T. 19 S., R. 6 W.

Chains

No timber.  
Undergrowth, greasewood, shadscale, sagebrush, and weeds.  
Fair grazing land.

S.  $89^{\circ}48'$  E., on random line, bet. secs. 13 and 24.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.90 Intersect the E. bdy. of the township, 2 lks. S. of the  
cor. of secs. 13 and 24.

Thence:

N.  $89^{\circ}49'$  W., on true line, bet. secs. 13 and 24.

Over nearly level land, through medium dense short greasewood and shadscale.

39.95 Point for the  $\frac{1}{4}$  sec. cor. secs. 13 and 24.

Set an iron post,  $\frac{3}{4}$  ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$$\begin{array}{r} S13 \\ \frac{1}{4} \\ \hline S24 \end{array}$$

1945

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor. and deposit broken glass at the base of the post.

61.80 Dim old road, bears NW. and SE.

69.40 Dim old road, bears N.  $10^{\circ}$  W. and S.  $10^{\circ}$  E.

79.90 The cor. of secs. 13, 14, 23, and 24.

Land, nearly level.

Soil, deep sandy clay; 4th rate.

No timber.

Undergrowth, greasewood, shadscale, sagebrush, and weeds.  
Fair grazing land.

N.  $0^{\circ}09'$  E., bet. secs. 13 and 14.

Over nearly level land, through medium dense short undergrowth.

11.70 Dim old road, bears NW. and SE.

40.00 Point for the  $\frac{1}{4}$  sec. cor. secs. 13 and 14.

Set an ironpost,  $\frac{3}{4}$  ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$$\begin{array}{r} \frac{1}{4} \\ S14 \quad | \quad S13 \end{array}$$

1945

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor. and deposit broken glass at the base of the post.

80.00 Point for the cor. of secs. 11, 12, 13, and 14.

INDEPENDENT RESURVEY OF THE  
SUBDIVISION OF T. 19 S., R. 6 W.

Chains

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked

T19S	R6W
S11	S12
S14	S13

1945

Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor. and deposit broken glass at the base of the post.

Land, nearly level.

Soil, deep sandy clay; 4th rate.

No timber.

Undergrowth, greasewood, shadscale, sagebrush, and weeds.

Fair grazing land.

S. 89°49' E., on random line, bet. secs. 12 and 13.

40.00 Set temp. ¼ sec. cor.

80.08 Intersect the E. bdy. of the township, 2 lks. S. of the cor. of secs. 12 and 13.

Thence:

N. 89°50' W., on true line, bet. secs. 12 and 13.

Over nearly level land, through medium dense short undergrowth.

40.04 Point for the ¼ sec. cor. secs. 12 and 13.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

¼	S12
	S13

1945

Raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor. and deposit broken glass at the base of the post.

73.80 Dim old road, bears N. 15° W. and S. 15° E.

80.08 The cor. of secs. 11, 12, 13, and 14.

Land, nearly level.

Soil, deep sandy clay; 4th rate.

No timber.

Undergrowth, greasewood, shadscale, sagebrush, and weeds.

Fair grazing land.

N. 0°09' E., bet. secs. 11 and 12.

Over nearly level land, through medium dense short undergrowth.

23.30 Dim old road, bears N. 20° W. and S. 20° E.

40.00 Point for the ¼ sec. cor. secs. 11 and 12.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in

INDEPENDENT RESURVEY OF THE  
SUBDIVISION OF T. 19 S., R. 6 W.

Chains

the ground, with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ S11 \quad | \quad S12 \end{array}$$

1945

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor. and deposit broken glass at the base of the post.

80.00 Point for the cor. of secs. 1, 2, 11, and 12.

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked

T19S	R6W
S2	S1

S11	S12
-----	-----

1945

Deposit broken glass at the base of the post.

Land, nearly level.

Soil, deep sandy loam; 4th rate.

No timber.

Undergrowth, greasewood, shadscale, sagebrush, and weeds.

Fair grazing land.

S.  $89^{\circ}50'$  E., on random line, bet. secs. 1 and 12.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.96 Intersect the E. bdy. of the township, 9 lks. N. of the cor. of secs. 1 and 12.

Thence:

N.  $89^{\circ}46'$  W., on true line, bet. secs. 1 and 12.

Over nearly level land, through medium dense short undergrowth.

39.98 Point for the  $\frac{1}{4}$  sec. cor. secs. 1 and 12.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$$\begin{array}{c} S1 \\ \frac{1}{4} \text{---} \\ S12 \end{array}$$

1945

Deposit broken glass at the base of the post.

79.96 The cor. of secs. 1, 2, 11, and 12.

Land, nearly level.

Soil, deep sandy clay; 4th rate.

No timber.

Undergrowth, greasewood, shadscale, sagebrush, and weeds.

Fair grazing land.

INDEPENDENT RESURVEY OF THE  
SUBDIVISION OF T. 19 S., R. 6 W.

- Chains N. 0°09' E., on random line, bet. secs. 1 and 2.
- 40.00 Set temp.  $\frac{1}{4}$  sec. cor.
- 80.00 Set temp. lot cor.
- 86.48 Intersect the N. bdy. of the township, 30 lks. E. of the cor. of secs. 1, 2, 35, and 36, which is marked by an iron post, 2 ins. in diam., firmly set, properly marked and witnessed as described in the official record of the resurvey of T. 18 S., R. 6 W., of this group.

Thence:

S. 0°03' E., on true line, bet. secs. 1 and 2.

Over low volcanic outcroppings and low sand dunes, through medium dense short undergrowth.

- 6.48 Point for the cor. of lots 4 and 5 sec. 1, and lots 1 and 8 sec. 2.

Set an iron post, 3 ft. long, 1 in. in diam., 16 ins. in the ground to solid rock and in a large mound of stone, with brass cap marked

$$\begin{array}{c} 1 \quad 4 \\ S2 \quad + \quad S1 \\ 8 \quad 5 \\ 1945 \end{array}$$

Deposit broken glass at the base of the post.

- 46.48 Point for the  $\frac{1}{4}$  sec. cor. of secs. 1 and 2.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ S2 \quad | \quad S1 \\ 1945 \end{array}$$

Raise a mound of stone,  $2\frac{1}{2}$  ft. base, 2 ft. high, W. of cor. and deposit broken glass at the base of the post.

- 81.00 Dim old road, bears N. 20° E. and S. 20° W.

- 86.48 The cor. of secs. 1, 2, 11, and 12.

Land, low volcanic outcroppings and low sand dunes.

Soil, shallow sandy clay; 4th rate.

No timber.

Undergrowth, greasewood, shadscale, sagebrush, and weeds.

Fair grazing land.

From the cor. of secs. 34 and 35, on the S. bdy. of the township.

N. 0°09' E., bet. secs. 34 and 35.

Ascend SE. face of volcanic outcropping, bears NE. and SW.

- 1.00 Top of outcropping, 20 ft. high, bears NE. and SW.; thence over gently rolling land through medium dense short undergrowth.

INDEPENDENT RESURVEY OF THE  
SUBDIVISION OF T. 19 S., R. 6 W.

## Chains

- 4.40 Volcanic outcropping, 10 ft. high, bears NE. and SW.
- 40.00 Point for the  $\frac{1}{4}$  sec. cor. secs. 34 and 35.  
Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked
- $$\begin{array}{c} \frac{1}{4} \\ S34 \mid S35 \\ 1945 \end{array}$$
- Deposit broken glass at the base of the post.
- 72.00 The S. edge of patch of barren sand, bears NE., and SW. about 4.00 chs. dist., thence N. 15° W.
- 80.00 Point for the cor. of secs. 26, 27, 34, and 35, in barren sand.  
Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked
- $$\begin{array}{c} T19S \mid R6W \\ S27 \mid S26 \\ \hline S34 \mid S35 \\ 1945 \end{array}$$
- Deposit broken glass at the base of the post.
- Land, gently rolling.  
Soil, clay and loose sand with rocky outcroppings; 4th rate.  
No timber.  
Undergrowth, greasewood, shadscale, rabbit and sage brush.  
Fair grazing land.
- 
- S. 89°49' E., on random line, bet. secs. 26 and 35.
- 40.00 Set temp.  $\frac{1}{4}$  sec. cor.
- 80.00 Intersect the N. and S. line, 5 lks. S. of the cor. of secs. 25, 26, 35, and 36.  
Thence:
- N. 89°51' W., on true line, bet. secs. 26 and 35.  
Ascend gradual E. slope of gently rolling land, through medium dense short undergrowth.
- 40.00 Point for the  $\frac{1}{4}$  sec. cor. secs. 26 and 35.  
Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked
- $$\begin{array}{c} S26 \\ \frac{1}{4} \mid \\ S35 \\ 1945 \end{array}$$
- Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of cor., and deposit broken glass at the base of the post.
- 74.00 The E. edge of a barren patch of loose sand, bears NW. and

INDEPENDENT RESURVEY OF THE  
SUBDIVISION OF T. 19 S., E. 6 W.

Chains 80.00	<p>The cor. of secs. 26, 27, 34, and 35.</p> <p>Land, gently rolling. Soil, deep sandy clay; 4th rate. No timber. Undergrowth, greasewood, shadscale, sage and rabbit brush. Fair grazing land.</p>						
	<p>N. 0°09' E., bet. secs. 26 and 27.</p> <p>Over barren loose sand.</p>						
3.50	<p>Leave barren loose sand and enter gently rolling land and medium dense undergrowth, bears E. and W.</p>						
14.40	<p>Old unimproved road, bears N. 60° E. and S. 60° W.</p>						
40.00	<p>Point for the <math>\frac{1}{4}</math> sec. cor. secs. 26 and 27, on gradual NE. slope.</p> <p>Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked</p> <div style="text-align: center;"> <math>\frac{1}{4}</math>            S27   S26            1945         </div>						
	<p>Deposit broken glass at the base of the post.</p>						
80.00	<p>Point for the cor. of secs. 22, 23, 26, and 27.</p> <p>Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T19S</td> <td>R6W</td> </tr> <tr> <td>S22</td> <td>S23</td> </tr> <tr> <td>S27</td> <td>S26</td> </tr> </table>           1945         </div>	T19S	R6W	S22	S23	S27	S26
T19S	R6W						
S22	S23						
S27	S26						
	<p>Deposit broken glass at the base of the post.</p> <p>Land, rolling. Soil, deep sandy clay; 4th rate. No timber. Undergrowth, greasewood, shadscale, sage and rabbit brush. Fair grazing land.</p>						
40.00	<p>S. 89°51' E., on random line, bet. secs. 23 and 26.</p> <p>Set temp. <math>\frac{1}{4}</math> sec. cor.</p>						
79.98	<p>Intersect the N. and S. line, 5 lks. S. of the cor. of secs. 23, 24, 25, and 26.</p> <p>Thence:</p> <p>N. 89°53' W., on true line, bet. secs. 23 and 26.</p> <p>Over gently rolling land, through medium dense short undergrowth.</p>						
1.80	<p>Dim old road, bears N. 20° W. and S. 20° E:</p>						

INDEPENDENT RESURVEY OF THE  
SUBDIVISION OF T. 19 S., R. 6 W.

Chains

39.99. Point for the  $\frac{1}{4}$  sec. cor. secs. 23 and 26.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$$\begin{array}{r} \frac{1}{4} \text{ S23} \\ \hline \text{S26} \\ 1945 \end{array}$$

Deposit broken glass at the base of the post.

79.98 The cor. of secs. 22, 23, 26, and 27.

Land, gently rolling.

Soil, deep sandy clay; 4th rate.

No timber.

Undergrowth, greasewood, shadscale, sage, and rabbit brush.

Fair grazing land.

N. 0°09' E., bet. secs. 22 and 23.

Over gently rolling land, through medium dense short undergrowth.

40.00 Point for the  $\frac{1}{4}$  sec. cor. secs. 22 and 23.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$$\begin{array}{r} \frac{1}{4} \\ \text{S22} \mid \text{S23} \\ \hline 1945 \end{array}$$

Deposit broken glass at the base of the post.

80.00 Point for the cor. of secs, 14, 15, 22, and 23.

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked

$$\begin{array}{r} \text{T19S} \mid \text{R6W} \\ \text{S15} \mid \text{S14} \\ \hline \text{S22} \mid \text{S23} \\ 1945 \end{array}$$

Deposit broken glass at the base of the post.

Land, gently rolling.

Soil, deep sandy clay; 4th rate.

No timber.

Undergrowth, greasewood, shadscale, sage, and rabbit brush.

Fair grazing land.

S. 89°53' E., on random line, bet. secs. 14 and 23.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.98 Intersect the cor. of secs. 13, 14, 23, and 24.

Thence:

INDEPENDENT RESURVEY OF THE  
SUBDIVISION OF T. 19 S., R. 6 W.

Chains

N. 89°53' W., on true line, bet. secs. 14 and 23.

Over nearly level land, through medium dense short undergrowth.

39.99 Point for the  $\frac{1}{4}$  sec. cor. secs. 14 and 23.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$$\frac{\frac{1}{4}}{S14}$$

1945

Deposit broken glass at the base of the post.

79.98 The cor. of secs. 14, 15, 22, and 23.

Land, nearly level.

Soil, deep sandy clay; 4th rate.

No timber.

Undergrowth, greasewood, shadscale, sage and rabbit brush.

Fair grazing land.

N. 0°09' E., bet. secs. 14 and 15.

Over gently rolling land, through medium dense short undergrowth.

40.00 Point for the  $\frac{1}{4}$  sec. cor. secs. 14 and 15.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$$\frac{\frac{1}{4}}{S15 \mid S14}$$

1945

Deposit broken glass at the base of the post.

57.80 Dim unimproved road, bears NW. and SE.

80.00 Point for the cor. of secs. 10, 11, 14, and 15.

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked

T19S	R6W
S10	S11
S15	S14

1945

Deposit broken glass at the base of the post.

Land, gently rolling with black lava sand on surface;

Soil, deep clay with sand on surface; 4th rate.

No timber.

Undergrowth, greasewood, shadscale, sage, and rabbit brush.

Fair grazing land.

INDEPENDENT RESURVEY OF THE  
SUBDIVISION OF T. 19 S., R. 6 W.

111

Chains	
40.00	S. 89°53' E., on random line, bet. secs. 11 and 14. Set temp. $\frac{1}{4}$ sec. cor.
79.92	Intersect the cor. of secs. 11, 12, 13, and 14. Thence:
20.00	N. 89°53' W., on true line, bet. secs. 11 and 14. Over rolling land through medium dense short undergrowth. Low volcanic rise, bears N. 80° E. and SW.
39.96	Point for the $\frac{1}{4}$ sec. cor. secs. 11 and 14. Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground and mound of stone, with brass cap marked
	$\begin{array}{r} S11 \\ \frac{1}{4} \cdot \overline{\hspace{1cm}} \\ S14 \\ 1945 \end{array}$
61.50	Deposit a volcanic stone, 10 x 10 x 6 ins., at base of post, marked X. Land becomes more broken, bears NW. and SE.
79.92	The cor. of secs. 10, 11, 14, and 15. Land, rolling with outcroppings of lava. Soil, shallow sandy clay; 4th rate. No timber. Undergrowth, greasewood, shadscale, sage and rabbit brush. Fair grazing land.
15.50	N. 0°09' E., bet. secs. 10 and 11.
20.00	Over rolling land broken by volcanic outcroppings, through medium dense short undergrowth. Dim road, bears N. 80° E. and S. 80° W.
40.00	Enter broken volcanic bench, bears E. and W. Point for the $\frac{1}{4}$ sec. cor. secs. 10 and 11, on top of NW. point of volcanic outcropping.
	Set an iron post, 3 ft. long, 1 in. in diam., in a large mound of stone over a cross cut on the surface rock, with brass cap marked
	$\begin{array}{c} \frac{1}{4} \\   \\ S10 \quad   \quad S11 \\ 1945 \end{array}$
45.00	Base of descent from volcanic outcropping, bears E. and W.; thence over small volcanic outcroppings.
80.00	Point for the cor. of secs. 2, 3, 10, and 11. Set an iron post, 3 ft. long, 2 ins. in diam., 12 ins. in the ground to solid rock and in a large mound of stone, with brass cap marked

INDEPENDENT SURVEY OF THE  
S. 1/4 SECTION OF T. 12 N. R. 6 W.

Contains

49.50 The W. side of low volcanic rise to the E.

64.50 Top of the W. point of volcanic rise.

84.54 The cor. of secs. 3, 4, 9, and 10.

Land, broken volcanic outcroppings.  
Soil, clay with a rocky surface; 4th rate.  
No timber.  
Undergrowth, greasewood, shadscale, sage, and rabbit brush.  
Fair grazing land.

From the cor. of secs. 32 and 33, on the S. bdy. of the township.

N. 0°07' E., bet. secs. 32 and 33.

Over rolling bench land, through medium dense short undergrowth.

27.60 Unimproved road, bears NE. and SW.

40.00 Point for the 1/4 sec. cor. secs. 32 and 33.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked




Deposit a lava stone, 1/2 x 1/2 x 1/2 ins., at base of post, marked X.

71.50 Dis old road, bears NW. and SE.

75.70 Draw, drains SE.; ascend steep SW. slope of spur to the N.

80.00 Point for the cor. of secs. 28, 29, 32, and 33, on steep SW. slope, 120 ft. above draw.

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked



Deposit broken glass at the base of the post.

Land, rolling bench.  
Soil, deep sandy clay; 4th rate.  
Timber, a few scattered juniper.  
Undergrowth, greasewood, shadscale, sage and rabbit brush, yellow top, and weeds.  
Fair grazing land.

S. 89°49' E., on random line, bet. secs. 28 and 33.

40.00 Set temp. 1/4 sec. cor.

INDEPENDENT RESURVEY OF THE  
SUBDIVISION OF T. 19 S., R. 6 W.

## Chains

85.60 Intersect the N. bdy. of the township, 10 lks. E. of the cor. of secs. 2, 3, 34, and 35, which is marked by an iron post, 2 ins. in diam., firmly set, properly marked and witnessed as described in the official record of the resurvey of T. 18 S., R. 6 W., of this group.

Thence:

S. 0°07' E., on true line, bet. secs. 2 and 3.

Over rolling land broken by volcanic outcroppings, through medium dense short undergrowth.

2.60 The SE. point of a barren clay flat to the NW.

5.60 Point for the cor. of lots 4 and 5 sec. 2, and lots 1 and 8 sec. 3.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground and a large mound of stone, with brass cap marked

$$\begin{array}{r|l} 1 & 4 \\ S3 & S2 \\ 8 & 5 \\ \hline & 1945 \end{array}$$

Deposit a lava stone, 6 x 6 x 6 ins., at base of post, marked X.

45.60 Point for the  $\frac{1}{4}$  sec. cor. of secs. 2 and 3.

Set an iron post, 3 ft. long, 1 in. in diam., 20 ins. in the ground to solid rock and in a large mound of stone, with brass cap marked

$$\begin{array}{r|l} \frac{1}{4} & \\ S3 & S2 \\ \hline & 1945 \end{array}$$

Deposit a lava stone, 8 x 8 x 4 ins., at base of post, marked X.

68.60 The NW. edge of a small barren clay flat, about 3.00 chs. in diam.

85.60 The cor. of secs. 2, 3, 10, and 11.

Land, rolling with outcroppings of lava.

Soil, clay with a sandy and rocky surface; 4th rate. No timber.

Undergrowth, greasewood, shadscale, sage, and rabbit brush. Fair grazing land.

From the cor. of secs. 33 and 34, on the S. bdy. of the township.

N. 0°08' E., bet. secs. 33 and 34.


Over rolling bench land, through tall dense sagebrush.

40.00 Point for the  $\frac{1}{4}$  sec. cor. secs. 33 and 34.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

INDEPENDENT RESURVEY OF THE  
SUBDIVISION OF T. 19 S., R. 6 W.


Chains



Deposit broken glass at the base of the post.

- 45.00 Undergrowth becomes short and scattered, bears E. and W.
- 66.00 Unimproved road, bears NE. and SW.
- 80.00 Point for the cor. of secs. 27, 28, 33, and 34.

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground and a large mound of stone, with brass cap marked



Deposit a lava stone, 10 x 6 x 6 ins., at base of post, marked X.

Land, rolling.  
Soil, deep sandy clay; 4th rate.  
No timber.  
Undergrowth, sage and rabbit brush, greasewood, shadscale, yellow top, and weeds.  
Fair grazing land.

S. 89°49' E., on random line, bet. secs. 27 and 34.

- 40.00 Set temp.  $\frac{1}{4}$  sec. cor.

- 79.90 Intersect the cor. of secs. 26, 27, 34, and 35.

Thence:


N. 89°49' W., on true line, bet. secs. 27 and 34.

Ascend gradually over sandy E. slope of bench, through medium dense short undergrowth.

- 15.00 Ascent becomes more gradual, bears N. and S.

- 39.95 Point for the  $\frac{1}{4}$  sec. cor. secs. 27 and 34.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground and small mound of stone, with brass cap marked



1945

Deposit broken glass at the base of the post.

- 45.20 Unimproved road, bears N. 60° E. and S. 60° W.
- 60.00 Undergrowth becomes scattered, bears N. and S.
- 79.90 The cor. of secs. 27, 28, 33, and 34.



INDEPENDENT RESURVEY OF THE  
SUBDIVISION OF T. 19 S., R. 6 W.

Chains S. 89°49' E., on random line, bet. secs., 22, and 27.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.96 Intersect the N. and S. line, 9 lks. N. of the cor. of sec 22, 23, 26, and 27.

Thence:

N. 89°45' W., on true line, bet. secs. 22 and 27.

Ascend gradually over general E. slope of rolling bench land, through medium dense short undergrowth.

39.98 Point for the  $\frac{1}{4}$  sec. cor. of secs. 22 and 27.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

S22
$\frac{1}{4}$
S27

1945

Deposit broken glass at the base of the post.

79.96 The cor. of secs. 21, 22, 27, and 28.

Land, rolling.

Soil, deep sandy clay; 4th rate.

No timber.

Undergrowth, greasewood, shadscale, sage, and rabbit brush

Fair grazing land.

N. 0°08' E., bet. secs. 21 and 22.

Over rolling bench land, through medium dense undergrowth.

10.00 Top of descent to lower bench, bears E. and W.

40.00 Point for the  $\frac{1}{4}$  sec. cor. secs. 21 and 22.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$\frac{1}{4}$
S21   S22

1945

Deposit broken glass at the base of the post.

80.00 Point for the cor. of secs. 15, 16, 21, and 22.

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, and a large mound of stone, with brass cap marked

T19S	R6W
S16	S15
S21	S22

1945

Deposit a lava stone, 8 x 8 x 6 ins., at base of post, marked X.

INDEPENDENT RESURVEY OF THE  
SUBDIVISION OF T. 19 S., R. 6 W.

Chains  
 Land, rolling.  
 Soil, deep sandy clay; 4th rate.  
 No timber.  
 Undergrowth, greasewood, shadscale, sage and rabbit brush,  
 yellow top, and weeds.  
 Fair grazing land.

S. 89°45' E., on random line, bet. secs. 15 and 22.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.00 Intersect the N. and S. line, 2 lks. S. of the cor. of  
secs. 14, 15, 22, and 23.

Thence:

N. 89°46' W., on true line, bet. secs. 15 and 22.

Over rolling bench land, through medium dense short under-  
growth.

40.00 Point for the  $\frac{1}{4}$  sec. cor. secs. 15 and 22.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in  
the ground, with brass cap marked

$\frac{1}{4}$  S15  


---

 S22  
 1945

Deposit a volcanic stone, 18 x 14 x 12 ins., at base of  
post, marked X.

Cor. set in a narrow elongated clay flat, bears N. and S.

80.00 The cor. of secs. 15, 16, 21, and 22.

Land, rolling.  
 Soil, deep clay with a sandy surface; 4th rate.  
 No timber.  
 Undergrowth, greasewood, shadscale, sage and rabbit brush,  
 yellow top, and weeds.  
 Fair grazing land.

N. 0°08' E., bet. secs. 15 and 16.

Over rolling land, through medium dense short undergrowth.

20.30 Old unimproved road, bears N. 60° E. and S. 60° W.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 15 and 16.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in  
the ground and a large mound of stone, with brass cap  
marked

$\frac{1}{4}$   
 S16 | S15  
 1945

Deposit a lava stone, 10 x 10 x 6 ins., at base of post,  
marked X.

INDEPENDENT RESURVEY OF THE  
SUBDIVISION OF T. 19 S., R. 6 W.

Chains

49.00 Barren clay basin, bears NE. for about 15.00 chs. and SW. for about 2 chains.

80.00 Point for the cor. of secs. 9, 10, 15, and 16.  
Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground and small mound of stone, with brass cap marked

T19S	R6W
S9	S10
S16	S15

1945

Deposit broken glass at the base of the post.

Land, rolling with small clay hummocks and sand dunes. Soil, deep clay with a sandy surface; 4th rate. No timber. Undergrowth, greasewood, shadscale, sage and rabbit brush. Fair grazing land.

S. 89°46' E., on random line, bet. secs. 10 and 15.

40.00 Set temp,  $\frac{1}{4}$  sec. cor.

80.02 Intersect the N. and S. line 2 lks. N. of the cor. of secs. 10, 11, 14, and 15.

Thence:

N. 89°45' W., on true line, bet. secs. 10 and 15.

Over rolling land with volcanic outcroppings, through medium dense short undergrowth.

18.90 Unimproved road, bears NE. and SW.

40.01 Point for the  $\frac{1}{4}$  sec. cor. secs. 10 and 15.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground and small mound of stone, with brass cap marked

$\frac{1}{4}$	S10
	S15

1945

Deposit broken glass at the base of the post.

45.00 Enter barren clay flat, bears N. 3.00 chs. and S. 2.00 chs

51.80 Leave same, bears N. 3.00 chs. and S. 2.00 chs.

80.02 The cor. of secs. 9, 10, 15, and 16.

Land, rolling with small lava outcroppings. Soil, deep clay with a sandy surface; 4th rate. No timber. Undergrowth, greasewood, shadscale, sage, and rabbit brush. Fair grazing land.

INDEPENDENT RESURVEY OF THE  
SUBDIVISION OF T. 19 S., R. 6 W.

Chains

N. 0°03' E., bet. secs. 9 and 10.

Over rolling land with lava outcroppings, through medium dense short undergrowth.

38.00 Low sand and rock rise, bears NW. and SE.

40.00 Point for the  $\frac{1}{4}$  sec. cor. secs. 9 and 10, at the S. side of a barren clay flat.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground and a large mound of stone, with brass cap marked

$\frac{1}{4}$   
S9 | S10

1945

Deposit broken glass at the base of the post.

42.00 Leave barren clay flat, bears SE. and SW.

60.00 The W. edge of a circular barren clay flat, about 10.00 chs. in diam.

77.50 The SW. point of a low lava spur from the NE.

80.00 Point for the cor. of secs. 3, 4, 9, and 10.

Set an iron post, 3 ft. long, 2 ins. in diam., in a large mound of stone over a cross cut on the lava surface rock, with brass cap marked

T19S | R6W  
S4 | S3  
S9 | S10

1945

Land, rolling with lava outcroppings.

Soil, clay with a rocky surface; 4th rate.

No timber.

Undergrowth, greasewood, shedscale, sage, and rabbit brush.

Fair grazing land.

S. 89°45' E., on random line, bet. secs. 3 and 10.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.06 Intersect the N. and S. line, 2 lks. S. of the cor. of secs. 2, 3, 10, and 11.

Thence:

N. 89°46' W., on true line, bet. secs. 3 and 10.

Over rolling land with lava outcroppings, through medium dense short undergrowth.

24.10 Dim unimproved road, bears N. 20° E. and S. 20° W.

35.00 The N. side of a circular barren clay basin, which is 15.00 chs. in diam. N. and S., and 10 chs. in diam. E. and W.

40.03 Point for the  $\frac{1}{4}$  sec. cor. secs. 3 and 10.

52  
INDEPENDENT RESURVEY OF THE  
SUBDIVISION OF T. 19 S., R. 6 W.

Chains

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground and mound of stone, with brass cap marked

$\frac{1}{4}$   $\frac{S3}{S10}$

1945

Deposit broken glass at the base of the post.

79.00 Low lava spur, projects SW.

80.06 The cor. of secs. 3, 4, 9, and 10.

Land, rolling with outcroppings of lava.  
Soil, clay and lava; 4th rate.  
No timber.

Undergrowth, greasewood, shadscale, sage, and rabbit brush.  
Fair grazing land.

N. 0°08' W., on random line, bet. secs. 3 and 4.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.00 Set temp. lot cor.

84.54 Intersect the N. bdy. of the township, 5 lks. W. of the cor. of secs. 3, 4, 33, and 34, which is marked by an iron post, 2 ins. in diam., firmly set, properly marked and witnessed as described in the official record of the resurvey of T. 18 S., R. 6 W. of this group.

Thence:

S. 0°06' E., on true line, bet. secs. 3 and 4.

Over gently rolling land, through medium dense short undergrowth.

4.54 Point for the cor. of lots 4 and 5, sec. 3.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground and a large mound of stone, with brass cap marked

$\frac{1}{4}$   $\frac{S4}{S3}$

1945

24.50 Enter low volcanic outcroppings, bears E. and W.

39.50 Low lava rise, bears E. and W.

44.54 Point for the  $\frac{1}{4}$  sec. cor. secs. 3 and 4.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground and a large mound of stone, with brass cap marked

$\frac{1}{4}$   $\frac{S4}{S3}$

1945

Deposit broken glass at the base of the post.

INDEPENDENT SURVEY OF THE  
SUBDIVISION OF T. 23 S., R. 6 E.

CHAINS

53	82
510	511

1945

Deposit a volcanic stone, 10 x 8 x 6 ins., at base of post marked X.

Land, rolling with volcanic outcroppings.  
Soil, shallow sand and clay; 4th rate.  
No timber.  
Undergrowth, greasewood, shadscale, sage, and rabbit brush.  
Fair grazing land.

S. 89°53' E., on random line, bet. secs. 2 and 11.

40.00 Set temp. & sec. cor.

70.00 Intersect the N. and S. line, 9 lks. N. of the cor. of secs. 1, 2, 11, and 12.

Thence:

N. 89°49' W., on true line, bet. secs. 2 and 11.

Over rolling land with lava outcroppings, through medium dense short undergrowth.

4.00 1/2 mi unimproved road, bears N. 20° E. and S. 20° W.

12.00 1/2 mi unimproved road, bears N. 20° W. and S. 20° E.

40.00 Point for the 1/2 sec. cor. secs. 2 and 11.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground and a large mound of stone, with brass cap marked

52
511

1945

Deposit a lava stone, 10 x 6 x 6 ins., at base of post, marked X.

41.00 Top of low lava rim, bears N. and S.

70.00 The cor. of secs. 2, 3, 10, and 11.

Land, rolling with outcroppings of lava.  
Soil, shallow sand and clay, with a rocky surface; 4th rate.  
No timber.

Undergrowth, greasewood, shadscale, sage, and rabbit brush.  
Fair grazing land.

N. 89°09' W., on random-line, bet. secs. 12 and 13.

40.00 Set temp. & sec. cor.

80.00 Set temp. lot cor.

INDEPENDENT RESURVEY OF THE  
SUBDIVISION OF T. 19 S., R. 6 W.

122

Chains

- 79.92 Intersect the N. and S. line, 2 lks. N. of the cor. of secs. 27, 28, 33, and 34.
- Thence:
- N. 89°48' W., on true line, bet. secs. 28 and 33.
- Over nearly level bench land, through medium dense short undergrowth.
- 39.96 Point for the  $\frac{1}{4}$  sec. cor. secs. 28 and 33.
- Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked
- $$\begin{array}{c} S28 \\ \frac{1}{4} \\ \hline S33 \\ 1945 \end{array}$$
- Deposit broken glass at the base of the post.
- 43.30 Dim old road, bears N. 10° W. and S. 10° E.
- 47.80 Dim old road, bears NE. and SW.; ascend gradually along S. slope of spur from Sugar Loaf Butte.
- 75.00 Top of ascent on S. slope of spur, 270 ft. above the  $\frac{1}{4}$  sec. cor.; descend gradual SW. slope.
- 79.92 The cor. of secs. 28, 29, 32, and 33, 30 ft. below top of ascent.
- Land, rolling.  
Soil, deep clay and gravel; 4th rate.  
No timber.  
Undergrowth, greasewood, shadscale, sage and rabbit brush, and yellow top.  
Fair grazing land.
- 
- N. 0°07' E., bet. secs. 28 and 29.
- Ascend SW. slope of rolling land, through medium dense short undergrowth.
- 6.70 Spur, 70 ft. above cor., slopes SE.; descend NE. slope.
- 40.00 Point for the  $\frac{1}{4}$  sec. cor. secs. 28 and 29, at base of descent from spur, bears NW. and SE.
- Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked
- $$\begin{array}{c} \frac{1}{4} \\ S29 \quad | \quad S28 \\ 1945 \end{array}$$
- Deposit broken glass at the base of post.
- Thence descend gradually over rolling bench land.
- 80.00 Point for the cor. of secs. 20, 21, 28, and 29.
- Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked

INDEPENDENT SURVEY OF THE  
SUBDIVISION OF T. 19 S., R. 6 W.

T19S	R6W
S20	S21
S29	S28

1945

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor. and deposit broken glass at the base of the post.

Land, rolling.

Soil, deep clay with a sandy surface; 4th rate.

No timber.

Undergrowth, greasewood, shadscale, sage, and rabbit brush.

Fair grazing land.

S. 89°48' E., on random line, bet. secs. 21 and 29.

40.00 Set temp. 1/4 sec. cor.

80.00 Intersect the N. and S. line, 9 lks. S. of the cor. of secs. 21, 22, 27, and 28.

Thence:

N. 89°52' W., on true line, bet. secs. 21 and 28.

Over gently rolling land, through medium dense short undergrowth.

40.00 Point for the 1/4 sec. cor. secs. 21 and 28.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

S21
1/4
S28

1945

Deposit broken glass at the base of the post.

48.20 Dim old road, bears N. and S.

80.00 The cor. of secs. 20, 21, 28, and 29.

Land, gently rolling.

Soil, deep clay with a sandy surface; 4th rate.

No timber.

Undergrowth, greasewood, shadscale, sage and rabbit brush.

Fair grazing land.

N. 0°07' E., bet. secs. 20 and 21.

Over gently rolling land, through medium dense short undergrowth.

31.50 Old road, bears NE. and SW.

40.00 Point for the 1/4 sec. cor. of secs. 20 and 21.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

Chains

$$\frac{1}{4}$$

S20	S21
1945	

Deposit broken glass at the base of the post.

80.00 Point for the cor. of secs. 16, 17, 20, and 21.

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked

T19S	R6W
S17	S16
S20	S21
1945	

Deposit broken glass at the base of the post.

Land, gently rolling.

Soil, clay with a sandy surface; 4th rate.

No timber.

Undergrowth, greasewood, shadscale, sage, and rabbit brush.

Fair grazing land.

S. 89°52' E., on random line, bet. secs. 16 and 21.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.00 Intersect the N. and S. line, 5 lks. S. of the cor. of secs. 15, 16, 21, and 22.

Thence:

N. 89°54' W., on true line, bet. secs. 16 and 21.

Over nearly level land, through medium dense short undergrowth.

17.70 Unimproved road, bears NE. and SW.

33.80 Enter barren clay flat, bears NW. and SW.

40.00 Point for the  $\frac{1}{4}$  sec. cor. secs. 16 and 21.

Set an ironpost, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

S16
$\frac{1}{4}$
S21

1945

Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, N. of cor., and deposit broken glass at the base of the post.

47.20 Dim old road, bears N. and S.

55.70 Leave barren clay flat, bears N. and SE.

80.00 The cor. of secs. 16, 17, 20, and 21.

Land, nearly level.

Soil, clay with a sandy surface; 4th rate.

No timber.

INDEPENDENT RESURVEY OF THE  
SUBDIVISION OF T. 19 S., R. 6 W.

Chains

Undergrowth, greasewood, shadscale, sage, and rabbit brush.  
Fair grazing land.

N. 0°07' E., bet. secs. 16 and 17.

Over gently rolling land, through medium dense short undergrowth.

40.00 Point for the  $\frac{1}{4}$  sec. cor. secs. 16 and 17.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$$\frac{1}{4}$$

S17	S16
-----	-----

1945

Deposit broken glass at the base of the post.

80.00 Point for the cor. of secs. 8, 9, 16, and 17.

Set an ironpost, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked

T19S	R6W
S8	S9
S17	S16

1945

Deposit broken glass at the base of the post.

Land, gently rolling.

Soil, clay with a sandy surface; 4th rate.

No timber.

Undergrowth, greasewood, shadscale, sage, and rabbit brush.  
Fair grazing land.

S. 89°54' E., on random line, bet. secs. 9 and 16.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.00 Intersect the N. and S. line, 7 lks. S. of the cor. of secs. 9, 10, 15, and 16.

Thence:

N. 89°57' W., on true line, bet. secs. 9 and 16.

Over low rolling sand hills through medium dense short undergrowth.

5.00 Lava break, about 30 ft. high, faces W. and bears N. 20° W. and S. 20° E. about 1.50 chs., thence E.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 9 and 16.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground and mound of stone, with brass cap marked

$$\frac{1}{4}$$

S9	S16
----	-----

1945

INDEPENDENT RESURVEY OF THE  
SUBDIVISION OF T. 19 S., R. 6 W.

126 Chains

Deposit broken glass at the base of the post.

42.90 Dim old road, bears N. and S.

80.00 The cor. of secs. 8, 9, 16, and 17.

Land, rolling.

Soil, clay with a sandy surface; 4th rate.

No timber.

Undergrowth, greasewood, shadscale, sage, and rabbit brush.

Poor grazing land.

N. 0°07' E., bet. secs. 8 and 9.

Over low rolling sand hills, through medium dense undergrowth.

40.00 Point for the  $\frac{1}{4}$  sec. cor. secs. 8 and 9.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$\frac{1}{4}$   
 S8 | S9  
 1945

Deposit broken glass at the base of the post.

50.00 Enter barren mud flat, bears N. 80° E. and S. 80° W.

80.00 Point for the cor. of secs. 4, 5, 8, and 9, at the N. edge of mud flat, bears NW. and N. 80° E.

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked

T19S | R6W  
 S5 | S4  
 S8 | S9  
 1945

Deposit broken glass at the base of the post.

Land, rolling low sand hills and level mud flat.

Soil, deep clay with a sandy surface and wet clay; 4th rate.

No timber.

Undergrowth, greasewood, shadscale and weeds.

Poor grazing land.

S. 89°57' E., on random line, bet. secs. 4 and 9.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.00 Intersect the N. and S. line, 2 lks. N. of the cor. of secs. 3, 4, 9, and 10.

Thence:

N. 89°56' W., on true line, bet. secs. 4 and 9.

Over low rolling sand hills, through medium dense short undergrowth.

INDEPENDENT RESURVEY OF THE  
SUBDIVISION OF T. 19 S., R. 6 W.

Chains

40.00 Point for the  $\frac{1}{4}$  sec. cor. secs. 4 and 9.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$$\begin{array}{c} S4 \\ \frac{1}{4} \text{---} \\ S9 \end{array}$$

1945

Deposit broken glass at the base of the post.

40.50 Dim old road, bears N. and S.

50.00 Enter barren mud flat, bears NE. and SW.

80.00 The cor. of secs. 4, 5, 8, and 9.

Land, low rolling sand hills and barren mud flat.  
Soil, sandy clay and mud; 4th rate.

No timber.

Undergrowth, greasewood, shadscale, and weeds, on E. portion of mile.

Poor grazing land.

N. 0°07' W., on random line, bet. secs. 4 and 5.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

84.16 Intersect the N. bdy. of the township, 19 lks. E. of the cor. of secs. 4, 5, 32, and 33, which is marked by an iron post, 2 ins. in diam., firmly set, properly marked and witnessed as described in the official record of the resurvey of T. 19 S., R. 6 W. of this group.

Thence:

S. 0°15' E., on true line, bet. secs. 4 and 5.

Over gently rolling land, through medium dense short undergrowth.

9.20 Volcanic rise, projects W.

28.20 Volcanic rise, projects W., about 3.00 chs. to end.

44.16 Point for the  $\frac{1}{4}$  sec. cor. secs. 4 and 5.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ S5 \text{ | } S4 \end{array}$$

1945

Deposit broken glass at the base of the post.

54.20 Lava outcropping, projects W., about 5.00 chs. to end.

84.16 The cor. of secs. 4, 5, 8, and 9.

Land, rolling with outcroppings of lava.  
Soil, shallow clay; 4th rate.

No timber.

Undergrowth, shadscale and greasewood.  
Fair grazing land.

INDEPENDENT RESURVEY OF THE  
SUBDIVISION OF T. 19 S., R. 6 W.

Chains	<p>From the cor. of secs. 31 and 32, on the S. bdy. of the township.</p> <p>N. 0°07' E., bet. secs. 31 and 32.</p> <p>Ascend gradual SW. slope of rolling bench land, through medium dense short undergrowth.</p>						
40.00	<p>Point for the <math>\frac{1}{4}</math> sec. cor. secs. 31 and 32, on gradual SW. slope, 210 ft. above sec. cor.</p> <p>Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked</p> <div style="text-align: center;"> <math>\frac{1}{4}</math>  <table border="1" style="margin: auto;"> <tr> <td>S31</td> <td>S32</td> </tr> </table> <p>1945</p> </div> <p>Deposit broken glass at the base of the post.</p> <p>Thence ascend more abrupt SW. slope.</p>	S31	S32				
S31	S32						
48.70	<p>Top of abrupt ascent, bears NW. and SE.; thence ascend gradual SW. slope of high bench.</p>						
65.60	<p>Small draw, drains W.</p>						
80.00	<p>Point for the cor. of secs. 29, 30, 31, and 32.</p> <p>Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked</p> <div style="text-align: center;"> <table border="1" style="margin: auto;"> <tr> <td>T19S</td> <td>R6W</td> </tr> <tr> <td>S30</td> <td>S29</td> </tr> <tr> <td>S31</td> <td>S32</td> </tr> </table> <p>1945</p> </div> <p>Deposit broken glass at the base of the post.</p> <p>Land, rolling, with a general southwesterly exposure and drainage. Soil, deep clay, gravel, and sand; 4th rate. No timber. Undergrowth, greasewood, shadscale, sage and rabbit brush, yellow top, and weeds. Fair grazing land.</p>	T19S	R6W	S30	S29	S31	S32
T19S	R6W						
S30	S29						
S31	S32						
40.00	<p>S. 89°49' E., on random line, bet. secs. 29 and 32.</p> <p>Set temp, <math>\frac{1}{4}</math> sec. cor.</p>						
80.00	<p>Intersect the N. and S. line, 5 lks. N. of the cor. of secs. 28, 29, 32, and 33.</p> <p>Thence:</p> <p>N. 89°47' W., on true line, bet. secs. 29 and 32.</p> <p>Along gradual S. slope of foot hills of Sugar Loaf Butte, through medium dense short undergrowth.</p>						
7.00	<p>Ravine, 50 ft. below cor., drains SE., and forks 2.00 chs. to the NW,</p>						
12.00	<p>Recross fork of ravine, drains NE.; ascend steep E. slope.</p>						

INDEPENDENT RESURVEY OF THE  
SUBDIVISION OF T. 19 S., R. 6 W.

## Chains

- 34.70 Dim old road, bears SW. and **SE**.
- 38.40 Spur from Sugar Loaf Butte, 400 ft. above ravine, projects S.
- 38.44 From this point, the center of a concrete roof to an underground room and the center of a circle, 2.80 chs. in diam., of 20 large and 20 small concrete pillars, bears S. 7°55' W., 13.18 chs. dist. This place is the remains of the construction, to generate electric power from a series of revolving wind mills, but the plant was never completed.
- Thence descend abrupt W. slope.
- 40.00 Point for the  $\frac{1}{4}$  sec. cor. secs. 29 and 32, on abrupt W. slope, 40 ft. below top of spur.
- Set an iron post, 3 ft. long, 1 in. in diam., 10 ins. in the ground to solid rock and in a large mound of stone, with brass cap marked
- $$\frac{1}{4} \frac{S29}{S32}$$
- 1945
- Deposit broken glass at the base of the post.
- 50.00 Base of steep descent from spur, 220 ft. below top, bears N. and S.; thence descend gradually along gradual S. slope.
- 80.00 The cor. of secs. 29, 30, 31, and 32.
- Land, rolling and mountainous.  
Soil, clay, sand, and gravel; 4th rate.  
Timber; a few scattered scrub juniper on portions of mile.  
Undergrowth, shadscale, greasewood, sage, black, and rabbit brush.  
Fair grazing land.
- 
- N. 89°49' W., on true line, bet. secs. 30 and 31.
- Descend gradually over rolling bench land, through medium dense short undergrowth.
- 10.00 Begin abrupt descent over W. slope to lower bench, bears N. and S.
- 21.00 Base of descent, 80 ft. below cor., bears N. and S.; thence over rolling bench land with rocky surface.
- 36.00 Unimproved road, bears SW. about 2.20 chs. to junction with next road and NE. to gravel pit.
- 37.20 Unimproved road, bears N. 20° E. and S. 20° W.
- 40.00 Point for the  $\frac{1}{4}$  sec. cor. secs. 30 and 31.
- Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground and a large mound of stone, with brass cap marked

$$\frac{1}{4} \frac{S30}{S31}$$

1945

INDEPENDENT RESURVEY OF THE  
SUBDIVISION OF T. 19 S., R. 6 W.

Chains

201460


Deposit broken glass at the base of the post.

83.58

Intersect the W. bdy. of the township, S. 0°15' E., 33 lks. dist. from the cor. of secs. 25, 30, 31, and 36, which is marked by an iron post, 2 ins. in diam., firmly set, properly marked and witnessed as described in the official record of the resurvey of T. 19 S., R. 7 W., of this group. I efface the marks on the brass cap of the cor. monument that pertain to sec. 31.

At point of intersection, and point for the closing cor. of secs. 30 and 31.

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground and large mound of stone, with brass cap marked



1945

Deposit a lava stone, 10 x 6 x 6 ins., at base of post, marked X.

Land, rolling.

Soil, clay, sand, and gravel, with a rocky surface; 4th rate.


Timber, a few scattered scrub juniper.

Undergrowth, shadscale, greasewood, sage, black, and rabbit brush.

Fair grazing land.

At mid-point on the W. bdy. of sec. 31, T. 19 S., R. 6 W. and which is the point for the  $\frac{1}{4}$  sec. cor. sec. 31.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked



1945

Deposit broken glass at the base of the post.

From this cor., the  $\frac{1}{4}$  sec. cor. secs. 31 and 36, bears N. 0°15' W., 16 $\frac{1}{2}$  lks. dist. Cor. is marked by an iron post 1 in. in diam., firmly set, properly marked and witnessed as described in the official record of the resurvey of T. 19 S., R. 7 W., of this group. I efface the marks on the brass cap of the cor. monument that pertain to sec. 31.

From the cor. of secs. 29, 30, 31, and 32.

N. 0°07' E., bet. secs. 29 and 30.

Ascend abrupt SW. slope of Sugar Loaf Butte, through medium dense short undergrowth.

17.90

Top of ascent on W. slope of Sugar Loaf Butte, 180 ft. above cor., ascends abruptly to the NE. and descends abruptly to the SW.; descend abrupt N. slope over broken sandstone and lava breaks.

INDEPENDENT RESURVEY OF THE  
SUBDIVISION OF T. 19 S., R. 6 W.

Chains

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 29 and 30, at base of abrupt descent, 210 ft. below top, bears NE. and SW.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$\frac{1}{4}$   
S30 | S29  
1945

Deposit broken glass at the base of the post.

Thence descend gradual N. slope over rolling bench land.

67.50 Unimproved road, bears N. 60° E. and S. 60° W.

80.00 Point for the cor. of secs. 19, 20, 29, and 30.

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked

T19S R6W  
S19 | S20  
-----  
S30 | S29  
1945

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor. Land, rolling and broken. Soil, clay, sand, and rock, with sandstone and lava ledges; 4th rate. No timber. Undergrowth, shadscale, greasewood, sage, black, and rabbit brush. Fair grazing land.

S. 89°47' E., on random line, bet. secs. 20 and 29.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.00 Intersect the cor. of secs. 20, 21, 28, and 29.

Thence:

N. 89°47' W., on true line, bet. secs. 20 and 29.

Over rolling bench land, through medium dense short undergrowth.

40.00 Point for the  $\frac{1}{4}$  sec. cor. secs. 20 and 29.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground and a large mound of stone, with brass cap marked

$\frac{1}{4}$   
S20  
-----  
S29  
1945

Deposit a lavastone, 8 x 6 x 5 ins., at base of the post, marked X.

INDEPENDENT RESURVEY OF THE  
SUBDIVISION OF T. 19 S., R. 6 W.

Chains

52.10 Unimproved road, bears NE. and SW. 00.00

63.00 Enter barren clay flat, bears NE. and SW.

70.00 Leave same, bears NE. and SW.

80.00 The cor. of secs. 19, 20, 29, and 30.

Land, rolling **bench**.  
Soil, deep clay, sand, and gravel; 4th rate.  
No timber.  
Undergrowth, shadscale, greasewood, black, sage, and rabbit brush.  
Fair grazing land.

---

N. 89°49' W., on true line, bet. secs. 19 and 30.

Over rolling bench land, through medium dense short undergrowth.

32.60 Small shallow draw, drains N. 30° E.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 19 and 30.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$$\begin{array}{r} S19 \\ \frac{1}{4} \text{---} \\ S30 \\ 1945 \end{array}$$

Deposit broken glass at the base of the post.

43.50 Top of gradual descent to lower bench, bears NE. and SW.

77.00 Top of gradual descent to lower bench, bears NE. and SW.

84.04 Intersect the W. bdy. of the township, S. 0°16' E., 49 lks. dist. from the cor. of secs. 19, 24, 25, and 30, which is marked by an iron post, 2 ins. in diam., firmly set, properly marked and witnessed as described in the official record of the resurvey of T. 19 S., R. 7 W., of this group. Efface the marks on the brass cap of the cor. monument that pertain to sec. 30.

At point of intersection, and point for the closing cor. of secs. 19 and 30.

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked

$$\begin{array}{r} T19S \quad T19S \\ R7W \quad S19C \\ S25 \quad S30C \\ \quad \quad R6W \\ 1945 \end{array}$$

Deposit broken glass at the base of the post.

Land, rolling.  
Soil, shallow gravel, clay, and sand; 4th rate.  
No timber.  
Undergrowth, shadscale, greasewood, sage, black, and rabbit brush.  
Fair grazing land.

## INDEPENDENT RESURVEY OF THE

SUBDIVISION OF T. 19 S., R. 6 W.

Chains

At mid-point bet. closing cors. on the W. bdy. of sec. 30, T. 19 S., R. 6 W., and which is the point for the  $\frac{1}{4}$  sec. cor. of sec. 30.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ | \\ S30 \end{array}$$

1945

Deposit broken glass at the base of the post.

From this cor., the  $\frac{1}{4}$  sec. cor. of secs. 25 and 30, bears N.  $0^{\circ}16'$  W., 41 lks. dist. Cor. is marked by an iron post, 2 ins. in diam., firmly set, properly marked and witnessed as described in the official record of the resurvey of T. 19 S., R. 7 W. of this group. I efface the marks on the brass cap of the cor. monument that pertain to sec. 30.

From the cor. of secs. 19, 20, 29, and 30.

N.  $0^{\circ}07'$  E., bet. secs. 19 and 20.

Over nearly level land, through medium dense short undergrowth.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 19 and 20.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ | \\ S19 \quad | \quad S20 \end{array}$$

1945

Deposit a volcanic stone, 2 x 3 x 2 ins., at base of post, marked X, also deposit broken glass at the base of the post.

80.00 Point for the cor. of secs. 17, 18, 19, and 20.

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked

$$\begin{array}{c|c} 119S & R6W \\ S16 & S17 \\ \hline S19 & S20 \end{array}$$

1945

Deposit broken glass at the base of the post.

Land, nearly level.

Soil, sandy clay; 4th rate.

No. timber.

Undergrowth, shadscale, greasewood, sage, and rabbit brush. Fair grazing land.

S.  $89^{\circ}47'$  E., on random line, bet. secs. 17 and 20.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.00 Intersect the N. and S. line, 2 lks. N. of the cor. of secs. 16, 17, 20, and 21.

INDEPENDENT RESURVEY OF THE  
SUBDIVISION OF T. 19 S., R. 6 W.

Chains

Thence:

N. 29°46' W., on true line, bet. secs. 17 and 20.

Over nearly level land, through medium dense short undergrowth.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 17 and 20.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

S17  
+-----+  
S20

1945

Deposit broken glass at the base of the post.

50.00 Low rise, bears NW. and S.

60.00 The cor. of secs. 17, 18, 19, and 20.

Land, nearly level.

Soil, deep sandy clay; 4th rate.

No timber.

Undergrowth, shadscale, greasewood, sage, and rabbit brush

Fair grazing land.

N. 20°49' W., on true line, bet. secs. 18 and 19.

Over nearly level land, through medium dense undergrowth.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 18 and 19.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

S18  
+-----+  
S19

1945

Deposit broken glass at the base of the post.

70.21 Intersect the W. bdy. of the township, S. 0°03' E., 83 lks dist. from the cor. of secs. 13, 18, 19, and 24, which is marked by an iron post, 2 ins. in diam., firmly set, properly marked and witnessed as described in the official record of the resurvey of T. 19 S., R. 7 W., of this group. Efface the marks on the brass cap of the corner monument that pertain to sec. 19.

At point of intersection, and point for the closing cor. of secs. 18 and 19.

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked

T19S	T19S
R7W	S18 C
S24	S19 C
	R6W

1945

Deposit broken glass at the base of the post.

INDEPENDENT RESURVEY OF THE

SUBDIVISION OF T. 19 S., R. 6 W.

Chains

Land, nearly level.  
Soil, clay with a loose sandy surface; 4th rate.  
No timber.  
Undergrowth, shadscale, greasewood, sage, and rabbit brush.  
Fair grazing land.

At mid-point bet. closing cors. on the W. bdy. of sec. 19,  
T. 19 S., R. 6 W., and which is the point for the 1/4 sec.  
cor. of sec. 19.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in  
the ground, with brass cap marked

1/4 S19

1945

Deposit broken glass at the base of the post.

From this cor., the 1/4 sec. cor. of secs. 19 and 24, bears  
N. 0°03' W., 66 lks. dist. Cor. is marked by an iron post,  
1 in. in diam., firmly set, properly marked and witnessed  
as described in the official record of the resurvey of  
T. 19 S., R. 7 W., of this group. I efface the marks on the  
brass cap of the cor. monument that pertain to sec. 19.

From the cor. of secs. 17, 18, 19, and 20.

N. 0°07' E., bet. secs. 17 and 18.

Over nearly level land, through medium dense short under-  
growth.

40.00 Point for the 1/4 sec. cor. of secs. 17 and 18.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in  
the ground, with brass cap marked

S18 | S17

1945

Deposit a lava stone, 3 x 3 x 2 ins., at base of post,  
marked X.

80.00 Point for the cor. of secs. 7, 8, 17, and 18.

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in  
the ground, with brass cap marked

T19S | R6W  
S7 | S8

S18 | S17

1945

Deposit a quartzite, 4 x 3 x 2 ins., at base of post,  
marked X.

Land, nearly level.  
Soil, deep clay with a sandy surface; 4th rate.  
No timber.  
Undergrowth, shadscale, greasewood, sage, and rabbit brush.  
Fair grazing land.

## INDEPENDENT RESURVEY OF THE


## SUBDIVISION OF T. 19 S., R. 6 W.

- Chains S. 89°46' E., on random line, bet. secs. 8 and 17.
- 40.00 Set temp.  $\frac{1}{4}$  sec. cor.
- 79.98 Intersect the cor. of secs. 8, 9, 16, and 17.
- Thence:
- N. 89°46' W., on true line, bet. secs. 8 and 17.
- Over nearly level land, through medium dense short undergrowth.
- 39.99 Point for the  $\frac{1}{4}$  sec. cor. of secs. 8 and 17.
- Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked
- $$\begin{array}{r} S8 \\ \frac{1}{4} \text{---} \\ S17 \\ 1945 \end{array}$$
- Deposit broken glass at the base of the post.
- 79.98 The cor. of secs. 7, 8, 17, and 18.
- Land, nearly level.  
Soil, clay with a sandy surface; 4th rate.  
No timber.  
Undergrowth, shadscale and greasewood.  
Poor grazing land.
- 
- N. 89°49' W., on true line, bet. secs. 7 and 18.
- Over nearly level land, through medium dense undergrowth.
- 40.00 Point for the  $\frac{1}{4}$  sec. cor. secs. 7 and 18.
- Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked
- $$\begin{array}{r} S7 \\ \frac{1}{4} \text{---} \\ S18 \\ 1945 \end{array}$$
- Deposit broken glass at the base of the post.
- 84.34 Intersect the W. bdy. of the township, S. 0°03' E., 1.11 chs. dist. from the cor. of secs. 7, 12, 13, and 18, which is marked by an iron post, 2 ins. in diam., firmly set, properly marked and witnessed as described in the official record of the resurvey of T. 19 S., R. 6 W. of this group. Efface the marks on the brass cap of the cor. monument that pertain to sec. 18.
- At point of intersection, and which is the point for the closing cor. of secs. 7 and 18.
- Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked

INDEPENDENT RESURVEY OF THE

SUBDIVISION OF T. 19 S., R. 6 W.

Chains



1945

Deposit broken glass at the base of the post.

Land, nearly level.  
 Soil, clay with a sandy surface; 4th rate.  
 No timber.  
 Undergrowth, shadscale and greasewood.  
 Poor grazing land.

At mid-point bet. closing cors. on the W. bdy. of sec. 18, and which is the point for the 1/4 sec. cor. of sec. 18, T. 19 S., R. 6 W.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked



1945

Deposit broken glass at the base of the post.

From this cor. the 1/4 sec. cor. of secs. 13 and 18, bears N. 0°03' W., 97 lks. dist. Cor. is marked by an iron post, 1 in. in diam., firmly set, properly marked and witnessed as described in the official record of the resurvey of T. 19 S., R. 7 W., of this group. I efface the marks on the brass cap of the cor. monument that pertain to sec. 18.


From the cor. of secs. 7, 8, 17, and 18.

N. 0°07' E., bet. secs. 7 and 8.

Over nearly level land, through medium dense short undergrowth.

40.00 Point for the 1/4 sec. cor. of secs. 7 and 8.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked



1945

Deposit broken glass at the base of the post.

71.00 Enter barren clay and mud flat, bears NW. and E.

80.00 Point for the cor. of secs. 5, 6, 7, and 8.

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked

INDEPENDENT RESURVEY OF THE  
SUBDIVISION OF T. 19 S., R. 6 W.

Chains

T19S	R6W
S6	S5
S7	S8

1945

Deposit broken glass at the base of the post.

Land, nearly level.

Soil, clay with a sandy surface; 4th rate.

No timber.

Undergrowth, shadscale and greasewood on S. 71.00 chs. of mile.

Poor grazing land.

S. 89°46' E., on random line, bet. secs. 5 and 8.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.98 Intersect the N. and S. line, 5 lks. N. of the cor. of secs. 4, 5, 8, and 9.

Thence:

N. 89°44' W., on true line, bet. secs. 5 and 8.

Over barren clay and mud flat.

15.00 Enter a few scattered shadscale, bears NW. and SE.

39.99 Point for the  $\frac{1}{4}$  sec. cor. of secs. 5 and 8.

Set an iron post, 3 ft. long, 1 in. in diam., 2 ins. in the ground to solid rock and in a large mound of stone, with brass cap marked

S5

$\frac{1}{4}$   
S8

1945

Deposit a volcanic stone, 10 x 9 x 5 ins., at base of post, marked X.

78.00 Leave all vegetation and enter barren clay and mud flat, bears NW. and SE.

79.98 The cor. of secs. 5, 6, 7, and 8.

Land, level.

Soil, shallow clay; 4th rate.

No timber.

Undergrowth, a few scattered shadscale.

Poor grazing land.

N. 89°49' W., on true line, bet. secs. 6 and 7.

Over barren clay and mud flat.

27.50 Enter a few scattered shadscale, bears N. and S.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 6 and 7.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

## INDEPENDENT RESURVEY OF THE

SUBDIVISION OF T. 19 S., R. 6 W.

Chairs

$$\begin{array}{r} S6 \\ \frac{1}{4} \\ \hline S7 \end{array}$$

1945

Deposit broken glass at the base of the post.

84.55

Intersect the W. bdy. of the township, S.  $0^{\circ}06'$  E., 1.62 chs. dist. from the cor. of secs. 1, 6, 7, and 12, which is marked by an iron post, 2 ins. in diam., firmly set, properly marked and witnessed as described in the official record of the resurvey of T. 19 S., R. 7 W., of this group. I efface the marks on the brass cap of the cor. monument that pertain to sec. 7.

At point of intersection, which is the point for the closing cor. of secs. 6 and 7.

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked

T19S	T19S
	S6
R7W	C
	S7
S12	R6W

1945

Deposit broken glass at the base of the post.

Land, nearly level.

Soil, shallow clay; 4th rate.

No timber.

Undergrowth, a few scattered shadscales.

Poor grazing land.

At mid-point bet. closing cors. on the W. bdy. of sec. 7, T. 19 S., R. 6 W., and which is the point for the  $\frac{1}{4}$  sec. cor. of sec. 7.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$$\begin{array}{r} \frac{1}{4} \\ | \\ S7 \end{array}$$

1945

Deposit broken glass at the base of the post.

From this cor., the  $\frac{1}{4}$  sec. cor. of secs. 7 and 12, bears N.  $0^{\circ}03'$  W., 1.295 chs. dist. Cor. is marked by an iron post, 1 in. in diam., firmly set, properly marked and witnessed as described in the official record of the resurvey of T. 19 S., R. 7 W., of this group. I efface the marks on the brass cap of the cor. monument that pertain to sec. 7.

At a point on the W. bdy. of sec. 6, T. 19 S., R. 6 W., which is a northing of 40.00 chs. from the closing cor. of secs. 6 and 7, and which is the point for the  $\frac{1}{4}$  sec. cor. of sec. 6.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

SUBDIVISION OF T. 19 S., R. 6 W.

Chains

1/4 S6  
1945

Deposit broken glass at the base of the post.

From this cor., the 1/4 sec. cor. of secs. 1 and 6, bears N. 0°05' W., 1.97 chs. dist. Cor. is marked by an iron post, 1 in. in diam., firmly set, properly marked and witnessed as described in the official record of the resurvey of T. 19 S., R. 7 W., of this group. I efface the marks on the brass cap of the cor. monument that pertain to sec. 6.

From the cor. of secs. 5, 6, 7, and 8.

N. 0°15' W., on true line, bet. secs. 5 and 6.

Over barren clay and mud flat.

2.00 Enter a few scattered shadscale, bears NW. and SE.

40.00 Point for the 1/4 sec. cor. of secs. 5 and 6.

Set an iron post, 3 ft. long, 1 in. in diam., 16 ins. in the ground to solid rock and in a large mound of stone, with brass cap marked

1/4  
S6 | S5  
1945

Deposit a volcanic stone, 8 x 6 x 6 ins., at base of post, marked X.

60.00 Leave all vegetation and enter clay and mud flat, bears NW. and SE.

73.00 Enter salt brush and shadscale, bears NE. and W.

83.22 Intersect the N. bdy. of the township, N. 89°35' E., 55 lks. dist. from the cor. of secs. 31 and 32, T. 18 S., R. 6 W., which is an iron post, 2 ins. in diam., firmly set, properly marked and witnessed as described in the official record of the resurvey of T. 18 S., R. 6 W., of this group.

At point of intersection, which is the point for the closing cor. of secs. 5 and 6.

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, with brass cap marked

T18S R6W  
S32  
-----  
S6 | S5  
T19S | R6W  
C C

1945.

Deposit broken glass at the base of the post.

Land, nearly level.

224

141

INDEPENDENT RESURVEY OF THE

SUBDIVISION OF T. 19 S., R. 6 W.

Chains

Soil, shallow clay with exposed lava; 4th rate.  
No timber.  
Undergrowth, shadscale and salt brush on portions of mile.  
Poor grazing land.

At mid-point on the N. bdy. of sec. 5, bet. the cor. of secs. 4, 5, 32, and 33, and the closing cor. of secs. 5 and 6, and which is the point for the  $\frac{1}{4}$  sec. cor. of sec. 5.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$\frac{1}{4}$  S5

1945

Deposit broken glass at the base of the post.

From this cor., the  $\frac{1}{4}$  sec. cor. of sec. 32, T. 18 S., R. 6 W., bears S.  $89^{\circ}35'$  W.,  $27\frac{1}{2}$  lks. dist. Cor. is marked by an iron post, 1 in. in diam., firmly set, properly marked and witnessed as described in the official record of the resurvey of T. 18 S., R. 6 W., of this group.

At a point on the N. bdy. of sec. 6, T. 19 S., R. 6 W., which is a westing of 40.00 chs. from the closing cor. of secs. 5 and 6, and which is the point for the  $\frac{1}{4}$  sec. cor. of sec. 6.

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, with brass cap marked

$\frac{1}{4}$  S6

1945

Deposit broken glass at the base of the post.

From this cor., the  $\frac{1}{4}$  sec. cor. of sec. 31, T. 18 S., R. 6 W., bears S.  $89^{\circ}30'$  W., 82 lks. dist. Cor. is marked by an iron post, 1 in. in diam., firmly set, properly marked and witnessed as described in the official record of the resurvey of T. 18 S., R. 6 W., of this group

GENERAL DESCRIPTION OF T. 19 S., R. 6 W.

The land within the boundaries of T. 19 S., R. 6 W., Salt Lake Meridian, Utah, is mostly desert and has a general northerly exposure. It is of a volcanic formation and has numerous outcroppings and patches of lava and cinder beds. Most of the township is at an elevation of about 4,700 feet above sea level. The highest point on Sugar Leaf Butte which is a high isolated hill about 300 feet above the remainder of the township, is located in the  $NE\frac{1}{4}SW\frac{1}{4}$  section 29. From the top of this butte, the land slopes abruptly in all directions to the heads of long sloping benches. The north and south slopes of the butte are very rough and broken, and as it is isolated from any other mountainous country, it is gradually being eroded away by the wind. Nearly all of the township at one time was covered with a flow of lava from craters to the south,

## GENERAL DESCRIPTION OF T. 19 S., R. 6 W.

and this lava bed in most places <sup>has</sup> been covered over by soil washed or blown in from the adjacent country. <sup>entirely</sup>

The soil in most places consists of a deep and shallow light colored clay with a sandy top soil, and may be classified as fourth rate. In numerous places, outcroppings of lava appear, and the northwest portion consists of a shallow wet clay.

The only timber in the township, is a few scattered patches of scrub juniper, which has no commercial value.

The entire township except for the barren clay and mud flats, is covered with a medium dense short growth of greasewood, shadscale, sage and rabbit brush, yellow top, and weeds, which affords fair grazing for stock during the winter months of the year.

No portions of the township are suitable for farming and no settlers or improvements were found.

The township contains no water and it is suitable only as a grazing range for stock during the winter. Nearly all parts can be reached by automobile over dim unimproved roads found throughout the township.

The remains of the construction of a series of large wind-mills which were to be used to generate electric power, is located in the NE $\frac{1}{4}$  NW $\frac{1}{4}$  and NW $\frac{1}{4}$  NE $\frac{1}{4}$  sec. 32. The remains of this construction consist of a circle 2.80 chs. in diameter of 20 large concrete pillars, inside of which is a circle 1.40 chs. in diameter of 20 smaller concrete pillars, and in the center of this circle is an underground concrete room about 50 feet long and 30 ft. wide.

About 2 $\frac{1}{4}$  miles of drift fence recently constructed by the Grazing Service, is located along the east boundary of the township, and about 1 $\frac{1}{2}$  miles is located along the south boundary.

No indications of mineral, coal, oil, or oil shale were found.

Due to the local attraction caused by the lava flow, the magnetic declination was not determined.



CERTIFICATE OF SURVEYOR

Elliot Bird, Andrew Nelson, Robert C. Yundt, J.C. Clark, Cadastral Engineers, HEREBY CERTIFY upon honor that,

pursuance of special instructions bearing date of the 7th day of April 1939 supplemental received from the district cadastral engineer for Utah with assignment

instructions dated May 29, 1945 I have surveyed made a dependent resurvey of the Guide Meridian, T. 19 S., Bet. Rs. 5 and 6 W., and the north boundary of T. 20 S., R. 6 W., and an independent resurvey of the subdivision T. 19 S., R. 6 W.,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by me and under my direction, and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Salt Lake City, Utah. Andrew Nelson Cadastral Engineer Robert C. Yundt Cadastral Engineer J.C. Clark Cadastral Engineer

January 31, 1945

CERTIFICATE OF APPROVAL

Bureau of Land Management, Washington, D. C., APR 18 1945

The foregoing field notes of the survey of dependent resurvey of the Guide Meridian T. 19 S., bet. Rs. 5 and 6 W., and the north boundary of T. 20 S., R. 6 W., and independent resurvey of the subdivision of T. 19 S., R. 6 W., of the Salt Lake Meridian, Utah,

executed by Elliot Bird, Andrew Nelson, Robert C. Yundt, and J.C. Clark, under special instructions dated April 7, 1939 supplemental and assignment instructions dated May 29, 1945, having been critically examined, and the necessary corrections made prior to their certification by the engineer, the said field notes, and the survey therein described, are hereby approved.

Carl G. Harrington, Chief, Division of Engineering

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above described surveys is a true copy of the original field notes on file in the public survey office.

Supervisor of Surveys

Book "C"  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GENERAL LAND OFFICE

# FIELD NOTES

OF THE DEPENDENT RESURVEY

EAST BOUNDARY T. 20 S., R. 7 W., THE WEST BOUNDARY T. 19 S., R. 6 W.,  
AND THE NORTH BOUNDARY, THE SUBDIVISIONAL, AND MEANDER LINES, OF  
T. 19 S., R. 7 W.

Of the Salt Lake Meridian,  
the State of Utah

## EXECUTED BY

Elliot Bird, Associate Cadastral Engineer

Andrew Nelson, Assistant Cadastral Engineer

Under special instructions dated April 7, 1939, which provided  
the surveys included under Group No. 299, bearing the approval of the  
Commissioner of the General Land Office under date of May 25, 1939

Supplemental  
assignment instructions dated September 27, 1941.

Survey commenced October 2, 1941.

Survey completed October 17, 1941.

# INDEX DIAGRAM.

*Township* 19 South, *Range* 7 West

		14		13		12		11		11		
6	50	5	43	4	36	3	29	2	22	1		10
51		51	49		43		35		28		21	
7		8	42	9	35	10	27	11	21	12		9
			49		41		34		27		20	
13		13	40	16	33	15	26	14	19	18		8
			43		40		33		26		19	
12	47	20	39	21	32	22	25	23	18	24		8
	47		46		38		31		25		17	
52	46	29	38	28	31	27	24	26	16	25		7
	45		45		37		30		23		16	
31	44	32	36	33	29	34	22	35	15	36		6
1		3		3		4		5				

6-151

1076

## DEPENDENT RESURVEY OF T. 19 S., R. 7 W.

## Chains

The official survey of T. 19 S., R. 7 W., Salt Lake Meridian, Utah, is shown upon plat approved February 26, 1872. All of the exterior, subdivisional and meander lines of this township were surveyed by Julien Bausman, U.S. Deputy Surveyor, in 1871. In 1934, Andrew Nelson, made a dependent resurvey of the east mile of the south boundary. The fractional portions of the west boundary were dependently resurveyed under this Group by Andrew Nelson, in 1940. The following field notes are those of a dependent restoration of the south, east, and north boundaries, and subdivisional lines. The resurvey is a restoration of the original lines in their true original positions according to the identified evidence. Before reconstructing or restoring a corner of the original survey, the lines were retraced, and a search made for evidence of the original corner monuments and other calls of the field notes. After completing the necessary retracements, the rules of proportionate measurement were applied to ascertain the position of each lost corner, and when duly identified or restored, the corner positions were properly re-monumented with the regulation iron survey posts.

The retracement data was submitted to the office for examination and verification, and in order to simplify the record, only the true line notes, referring to the completed resurvey, are supplied herewith.

The resurvey was commenced October 2, 1941, and executed by Elliot Bird and Andrew Nelson, using Buff and Buff transits Nos. 18003 and 16726 respectively. Transits are the property of the General Land Office. The horizontal plate of each instrument is provided with two double verniers placed opposite to each other and reading to single minutes of arc. The instruments are equipped with full vertical circles, each provided with one double vernier reading to single minutes of arc, and solar attachments which were not used on this survey, and no description of them will be given here. The instruments were in good adjustment and were approved for use on this assignment, conditional upon satisfactory field tests, by the district cadastral engineer for Utah, in supplemental assignment instructions dated September 27, 1941. The instruments were tested in the field prior to the commencement of the field work, and found to be free from appreciable error.

All azimuth determinations were made by reference to the true meridian as established by hour angle observations made upon Polaris during the progress of the work. The lines were carried forward as transit lines, taking the mean of direct and reversed sights at each transit point.

The measurements were made with Lallie steel ribbon tapes 5 chains in length. The tapes were graduated every link for the first chain and thereafter at intervals of 10 links. The tapes were tested by comparison with a Lufkin standard steel tape 1 chain in length and found correct. The measurements were made on the slope, the vertical angle of each interval determined by the use of clinometers, and the slope measurements properly reduced to true horizontal equivalents, which appear in these field notes.

The geographic position of the southeast corner of the township is approximately as follows; latitude  $39^{\circ}07'N.$ , and longitude  $112^{\circ}35'W.$

## DEPENDENT RESURVEY OF NORTH BOUNDARY, T. 20 S., R. 7 W.

Reestablishment of surveys executed by  
Julien Bausman, U.S. Deputy Surveyor,  
in 1871.

DEPENDENT RESURVEY OF NORTH BOUNDARY, T. 20 S., R. 7 W.

Chains

October 2, 1941: At the cor. of Ts. 19 and 20 S., Rs. 7 and 8 W., in approximate latitude  $39^{\circ}07'$ , longitude  $112^{\circ}41'$  W.; at a mean time, 9h 32m 51s a.m. My watch which is 22s slow of 105th meridian standard time, determined by comparison with radio signals on this day, I observe Polaris west of the meridian, making four settings, two each with the telescope in direct and reversed position, recording the time of each setting and the horizontal angle eastward from the star to a flag about  $\frac{1}{2}$  mile to the N.

Azimuth of Polaris at time of observation...  $1^{\circ}07.3'$  W.  
 Horizontal angle, star to flag.....  $1^{\circ}18.0'$   
 True bearing to reference flag..... N.  $0^{\circ}10.7'$  E.

Beginning at the remonumented original cor. of Ts. 19 and 20 S., Rs. 7 and 8 W.; an iron post, 3 ins. diam., properly set, marked and witnessed as described in the record of resurvey T. 19 S., R. 8 W., of this Group.

Thence

N.  $89^{\circ}50'$  E., bet. secs. 6 and 31, along N. bdy. of T. 20 S., R. 7 W.

Over level alkali flat, through scattered salt brush.

12.50 Low sand rise, 10 ft. high, bears NW. about 3 chs. to end, and SE. about 4 chs.

10.23 Proportionate distance; no evidence of the original cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked

$$\frac{S31}{\frac{1}{4}}$$

1941

Deposit broken glass at the base of the post.

17.40 Top of low sand rise, extends S. about 3.00 chs. and NW. about 10.00 chs. to end.

17.20 Shallow clay drain, 2.50 chs. wide, drains N.

10.47 The original cor. of secs. 5, 6, 31, and 32; a cedar stake, 2 ft. long, 3 ins. diam., broken off at ground, and having dim scribe marks.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, old stake set alongside, for cor. secs. 5, 6, 31, and 32, with brass cap marked

T19S	R7W
S31	S32
S6	S5
T20S	

1941

No accessories available.

Land, level alkali flat; surface broken by few low sandy rises.

DEPENDENT RESURVEY OF NORTH BOUNDARY, T. 20 S., R. 7 W.

Chains

Soil, heavy wet alkali clay and sandy clay; 4th rate.  
Undergrowth, scattered salt brush.  
Poor grazing.

S. 89°59' E., bet. secs. 5 and 32.

Over level alkali land, through scattered salt brush and grass.

40.30 Proportionate distance; no evidence of the original cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked

S32
$\frac{1}{4}$
S5

1941

Deposit broken glass at the post of the post.

60.45 Barbed wire fence, 6 strands, bears N. 0°15' W., and S. 0°15' E. about  $\frac{1}{4}$  mile to SW. cor., thence easterly; enter heavier salt grass.

80.60 The original cor. of secs. 4, 5, 32, and 33, a cedar stake, 2 ft. long, 3 ins. diam., firmly set, and marked 6 notches on S. and 4 notches on E. edges; unwitnessed.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, old stake set alongside, for cor. of secs. 4, 5, 32, and 33, with brass cap marked

T19S	R7W
S32	S33

S5	S4
T20S	

1941

Deposit broken glass at the base of the post.

Corner set at bend of faint trace of an old ditch, drains W. from the S.

Land; level alkali flat.

Soil, heavy clay on W. portion; sandy clay lying on har-pan on E. portion; 3rd and 4th rates.  
Undergrowth, salt brush and salt grass.  
Fair grazing on E. portion of mile.

N. 89°42' E., bet. secs. 4 and 33.

Over nearly land, through dense salt brush.

36.90 American Telephone & Telegraph transcontinental line, 14 wires, at angle point, bears N. 0°18' E., and S. 34°17' W.

40.00 The original  $\frac{1}{4}$  sec. cor.; a cedar stake, 2 ft. long, 2 ins. diam., firmly set, marked  $\frac{1}{4}$  on N. face; unwitnessed.

At point for cor.

DEPENDENT RESURVEY OF NORTH BOUNDARY, T. 20 S., R. 7 W.

Chains

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old stake set alongside, for  $\frac{1}{4}$  sec. cor., with brass cap marked

S33

$\frac{1}{4}$ .  
S4

1941

Deposit broken glass at base of post, and dig pits, 18 x 18 x 12 ins., E. and W. of post, 3 ft. dist.

Continue on same course, beginning new measurement.

20.00 Low rise, 50 lks. wide, 6 ft. high, bears N. 10° W., and S. 10° E.; the W. end of a dyke from the E., bears S. 10° E., about 8.50 chs. dist.

20.50 Enter wet low land covered with very dense tall salt grass

26.60 Slough, 10 lks. wide, 2 ft. deep, drains N. 10° W.

40.00 The original cor. of secs. 3, 4, 33, and 34; a cedar post 3 ft. long, 5 ins. squared, firmly set, marked 6 notches on S., and 3 notches on E. edges; unwitnessed.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, old cor. set alongside, for cor. of secs. 3, 4, 33 and 34, with brass cap marked

T19S | R7W

S33 | S34

S4 | S3

T20S

1941

Deposit broken glass at the base of the post, and dig pit 18 x 18 x 12 ins., in each sec., 3 ft. dist. from post.

From the cor., a dyke on the N. side of pond, bearing nearly E. and W., bears S., about 6.50 chs. dist.

Land, nearly level.

Soil, wet black clay lying on a shale subsoil; 3rd rate.

Undergrowth, salt grass and salt brush.

Fair grazing.

N. 89°55' E., bet. secs. 3 and 34.

Over level bottom land, through dense tall salt grass.

21.05 Top of earth dyke, 20 ft. wide, 3 ft. high, on W. side of pond, bears N. 2°45' W., and S. 2°45' E. 4.50 chs. dist. to dyke between ponds bearing N. 84° E. and S. 84° W.; thence across pond. Road on dyke, bears same.

40.13 Proportionate point; find no evidence of the  $\frac{1}{4}$  sec. cor., and point falls in pond where it is impossible to set a cor., therefore at a point, S., 2.50 chs. dist. from the true cor. point, on N. edge of dyke between ponds.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for witness cor. to the restored  $\frac{1}{4}$  sec. cor., with

DEPENDENT RESURVEY NORTH BOUNDARY OF, T. 20 S., R. 7 W.

Chains

with brass cap marked

WC  
S34  
S3

1941

Deposit broken glass at the base of the post and place a circle of stone around same.

Contine across pond from true cor. point.

60.15 Six strand barbed wire fence, in pond, bears N. 0°15' W. and S. 0°15' E.; cattle guard over outlet from S. pond to N. pond, bears S., 8.00 chs. dist.

67.60 Dyke on E. side of pond, bears N. 15° W., and S. 32°45' W. 10.30 chs. dist., thence N. 70°45' W.; thence over level alkali flat through scattered salt brush.

80.26 The original cor. of secs. 2, 3, 34, and 35, a decayed juniper post, 3 ft. long, 4 ins. square, firmly set in the ground; no marks remaining on post.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, old cor. deposited alongside, for cor. secs. 2, 3, 34, and 35, with brass cap marked

T19S R7W  
S34 S35  
S3 S2  
T20S

1941

Deposit broken glass at the base of the post, and dig pits 18 x 18 x 12 ins., in each sec., 3 ft. dist. from post.

Land, level.

Soil, wet clay; considerable alkali on E. portion of mile; 4th rate.

Undergrowth, salt grass and brush.

Poor grazing.

N. 89°56' E., bet. secs. 2 and 35.

Over level alkali flat, through scattered salt brush.

1.10 Dim road, bears N. 10° W. and S. 20° E.

6.50 Leave alkali flat, thence across E. point of higher land, bears NE. and S. 20° W.

11.50 Reenter alkali flat, bears NW. and SE.

28.00 Leave flat, enter broken volcanic land, bears N. and SW.; gently ascend entering a few scattered juniper.

40.12 Proportionate distance; no evidence of the original sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored sec. cor., with brass cap marked

DEPENDENT RESURVEY NORTH BOUNDARY OF T. 20 S., R. 7 W.

Chains

S35  
S2  
1941

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of post

80.24 The original remonumented cor. of secs. 1, 2, 35, and 36, an iron post, 2 ins. diam., properly set, marked and witnessed as described in the official record of the completion survey of T. 20 S., R. 7 W., Group No. 255, Ut. in 1934.

Land, level alkali flat on W. portion; low rolling volcanic bench on W. portion; slight W. slope.

Soil, wet alkali clay on flat; rocky with shallow loose sand on bench; 4th rate.

Undergrowth, shadscale, and a few greasewood and salt brush poor grazing.

DEPENDENT RESURVEY WEST BOUNDARY OF T. 19 S., R. 6 W.

Reestablishment of surveys executed by Charles Mogo, U.S. Deputy Surveyor in 1857, and resurveyed by Julien Fausman, U.S. Deputy Surveyor in 1871.

The reestablished original cor. of Ts. 19 S., Rs. 6 and 7 W., is an iron post, 3 ins. diam., properly set, marked and witnessed as described in the official record of the completion survey T. 20 S., R. 6 W., Group No. 255, Utah, in 1934. Note; from this cor., the closing cor. of Ts. 20 S., Rs. 6 and 7 W., bears S. 89°58.6' W., 2.85 chs. dist.

Both corners are at the N. edge of scattered juniper timber. October 1, 1941; at the above township cor., in approximate latitude 39°07' N., longitude 112°39' W., at a mean time of 9h 46m 39s a.m. by my watch which is 22s slow of correct 105th meridian standard time, determined by comparison with radio time signals this day, I observe Polaris west of the meridian, making four settings, two each with the telescope in direct and reversed positions, recording the time of each setting and the horizontal angle westward from star to a flag about 3/4 mile distant.

Azimuth of Polaris at observation ..... 1° 02.6' W.  
Horizontal angle star to flag ..... 88° 56.0'  
True bearing to flag ..... N. 89°58.6' W.

Thence, from the cor. of Ts. 19 S.; Rs. 6 and 7 W.

N. 0°15' W., bet. secs. 31 and 36, along the W. bdy. of T. 19 S., R. 6 W.

Over gently rolling land, through medium dense shadscale undergrowth.

32.20 Unimproved road, bears NE. and SW.

40.14 Proportionate distance; no evidence of the original 1/4 sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored 1/4 sec. cor., with brass cap marked

S36 | S31  
1941

DEPENDENT RESURVEY WEST BOUNDARY OF T. 19 S., R. 6 W.

Chains


Deposit broken glass at the base of the post.

80.28

The **official** cor. of secs. 25, 30, 31, and 36, a cedar stake,  $3\frac{1}{2}$  ft. long, 4 ins. squared, firmly set and having dim scribe marks on two faces; unwitnessed.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, old cor. post deposited alongside, for cor. secs. 25, 30, 31, and 36, with brass cap marked



1941

Place a circle of rock around the post.

Land, gently rolling bench with slight westerly exposure. Soil, loose sand and a few patches of volcanic rock; 2nd rate.

Undergrowth, medium dense shadscale and yellow top.

Timber, a few scattered juniper on S. end of mile.

Fair grazing.

N. 0°16' W., bet. secs. 25 and 30.

Over gently rolling land, through medium dense undergrowth.


30.00

Begin slight descent over general NW. slope.

40.06

Proportionate distance; no evidence of the original  $\frac{1}{4}$  sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked



Deposit broken glass at the base of the post.

50.00

Wide shallow swale, drains NE.

59.00


Low sandy rise, slopes NE.

80.12

The **official** cor. of secs. 19, 24, 25, and 30, a juniper stake, 2 ft. long, 3 ins. diam.; firmly set, marked 2 notches on S. and 4 notches on N. edges; unwitnessed.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, old cor. deposited alongside, for cor. secs. 19, 24, 25, and 30, with brass cap marked



DEPENDENT RESURVEY WEST BOUNDARY OF T. 19 S., R. 6 W.

Chains

Deposit broken glass at the base of post, also place a small circle of stone around post.

1941

Land, gently rolling.

Soil, sandy; 3rd rate.

Undergrowth, greasewood, Brigham tea, shadscale and yellow top.

Fair grazing.

N. 0°03' W., bet. secs. 19 and 24.

Over gently rolling land, through medium dense short undergrowth; gently descend NW. slope.

5.00 Base of slope, thence over land with slight westerly slope

40.15 Proportionate distance; no evidence of the original  $\frac{1}{4}$  sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked

$\frac{1}{4}$   
S24 | S19  
1941

Deposit broken glass at the base of post.

80.30 Proportionate distance; no evidence of the original sec. cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for restored cor. secs. 13, 18, 19, and 24, with brass cap marked

T19S  
R7W | R6W  
S13 | S18  
-----  
S24 | S19  
1941

Deposit broken glass at the base of post.

Land, gently rolling bench.

Soil, loose black volcanic sand; 3rd rate.

Undergrowth, greasewood, shadscale and yellow top.

Fair grazing.

N. 0°03' W., bet. secs. 13 and 18.

Over nearly level land, through medium dense undergrowth.

40.15 Proportionate distance; no evidence of the original  $\frac{1}{4}$  sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked

$\frac{1}{4}$   
S13 | S18  
1941

DEPENDENT RESURVEY WEST BOUNDARY OF T. 19 S., R. 6 W.

Chains

Deposit broken glass at the base of the post.

80.30

Proportionate distance; find no evidence of the original sec. cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for restored cor. secs. 7, 12, 13, and 18, with brass cap marked

T19S	
R7W	R6W
S12	S7
S13	S18

1941

Deposit broken glass at the base of post, and six pits, 18 x 18 x 12 ins., in each sec., 3 ft. dist. from post.

Land, nearly level bench.

Soil, loose black volcanic sand, lying on a hard pan of black shale or sand rock; 3rd rate.

Undergrowth, greasewood and shadscale.

Fair grazing.

N. 0°03' W., bet. secs. 7 and 12.

Over nearly level land, through medium dense undergrowth.

30.00

Leave all undergrowth, thence over barren clay flat, bears NW. and E.

40.15

The official sec. cor., a decayed juniper stake, rotted off at the ground and no marks remaining.

At the cor. point.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, stump of stake deposited alongside, for sec. cor., with brass cap marked

S12	S7
-----	----

1941

Deposit broken glass at the base of the post.

Thence, N. 0°06' W.

40.29

The official sec. cor., a cedar post, 2 1/2 ft. long, 4 ins. squared, firmly set and having dim. scribble marks.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, old post cor. alongside, for cor. secs. 1, 6, 7, and 12, with brass cap marked

T19S	
R7W	R6W
S1	S6
S12	S7

1941

DEPENDENT RESURVEY WEST BOUNDARY OF T. 19 S., R. 6 W.

Chains

Deposit broken glass at the base of the post.

Land, level clay flat and rolling bench land.  
Soil, deep heavy clay and sandy clay; 4th rate.  
Undergrowth, shadscale, Brigham tea, greasewood and yellow  
top on S. portion of mile.  
Poor grazing.

N. 0°05' W., bet. secs. 1 and 6.


Over level barren flat.

14.00 Leave barren flat and enter low sandy rise with scattered undergrowth, bears E. and N. 80° W.

40.35 The official  $\frac{1}{4}$  sec. cor., a decayed juniper stake, 2 $\frac{1}{2}$  ft. long, 3 ins. diam, firmly set in the ground, no marks remaining.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old stake set alongside, for  $\frac{1}{4}$  sec. cor., with brass cap marked




Deposit broken glass at the base of the post.

Thence, N. 0°10' W.

14.50 Leave sandy rise and enter barren clay alkali flat, bears NE. and SW.

40.29 Proportionate distance; find no evidence of the original township cor.

Set an iron post, 3 ft. long, 3 ins. diam., 27 ins. in the ground, for restored cor. of Ts. 18 and 19 S., Rs. 6 and 7 W., with brass cap marked



Deposit broken glass at the base of the post.

From this cor., the original cor. of secs. 5, 6, 31, and 32 on N. bdy. of T. 19 S., R. 6 W., bears N. 89°30' E., 83.66 chs. dist.; The original  $\frac{1}{4}$  sec. cor. secs. 31 and 36, on W. bdy. of T. 18 S., R. 6 W., bears N. 0°26' E., 40.29 chs. dist., and the original cor. of secs. 3, 4, 33, and 34, on the N. bdy. of T. 19 S., R. 7 W., bears N. 89°54' W., 241.62 chs. dist.

Land, level alkali flat and low sandy rise.  
Soil, wet clay and sandy clay; 4th rate.  
Undergrowth, scattered shadscale and salt brush on portion of mile. Poor grazing.

DEPENDENT RESURVEY NORTH BOUNDARY OF: T. 19 S., R. 7 W.

Chains

Reestablishment of surveys executed by  
Julien Bausman, U.S. Deputy Surveyor,  
in 1871.

From the restored cor. Ts. 18 and 19 S., Rs. 6 and 7 W.

N. 89°54' W., bet. secs. 1 and 36, on N. bdy. of T. 19 S.,  
R. 7 W.

Over level alkali mud flat, void of vegetation.

40.27 Proportionate distance; no evidence of the original  
sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the  
ground, for restored sec. cor., with brass cap marked

S36

31

1941

Deposit broken glass at the base of the post.

80.51 Proportionate distance; no evidence of the original sec.  
cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the  
ground, for restored cor. of secs. 1, 2, 5, and 36, with  
brass cap marked

T19S R7W

S35	S36
-----	-----

S2	S1
----	----

T19S

1941

Deposit broken glass at the base of the post.

Land, level alkali mud flat.

Soil, heavy wet sticky clay; 4th rate.

No vegetation.

No grazing.

N. 89°54' W., bet. secs. 2 and 35.

Over level alkali clay flat void of vegetation.

40.27 Proportionate distance; no evidence of the original  
sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the  
ground, for restored sec. cor., with brass cap marked

S35

32

1941

Deposit broken glass at the base of the post.

80.51 Proportionate distance; no evidence of the original sec.  
cor.

DEPENDENT RESURVEY NORTH BOUNDARY OF T. 19 S., R. 7 W.

Chains

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for restored cor. secs. 2, 3, 34, and 35, with brass cap marked

T19S	R7W
S34	S35

S3	S2
----	----

T19S

1941

Deposit broken glass at the base of the post.

Land, level alkali clay flat.  
Soil, heavy wet clay; 4th rate.  
No vegetation.  
No grazing.

N. 89° 41' E., bet. secs. 3 and 34.

Over level alkali clay flat void of vegetation.

20.00 Enter short salt weeds.

20.27 Proportionate distance; no evidence of the original sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored sec. cor., with brass cap marked

S34
S3

1941

Deposit broken glass at the base of the post.

20.54 The original cor. of secs. 3, 4, 33, and 34, a juniper stake, 2 ft. long, 3 ins. diam., squared at top, upon which I find dim scribe marks and 3 notches on two opposite edges.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, old cor. stake set alongside, for cor. secs. 3, 4, 33, and 34, with brass cap marked

T19S	R7W
S33	S34

S3	S3
----	----

T19S

1941

Deposit broken glass at the base of the post.

Land, heavy alkali mud flat.  
Soil, heavy wet clay; 4th rate.  
Undergrowth scattered salt weeds on W. portion of mile.  
Poor grazing.

DEPENDENT RESURVEY NORTH BOUNDARY OF T. 19 S., R. 7 W.

Chains

N. 89°42' W., bet. secs. 4 and 33.

Over level land through scattered weeds.

3.00 Enter salt grass:

14.40 Dim trace of road, bears NW. and SE.

35.00 Leave salt grass and enter medium dense greasewood, bears N. and S.

36.30 Low sand rise, bears N. 30° E. and SW.

38.45 American Telegraph & Telephone transcontinental line, 14 wires, bears N. 0°18' E. and S. 0°18' W.

39.70 Service road, parallel to the above line.

40.26 The original 1/4 sec. cor.; a cedar stake, 2 ft. long, 2 ins. diam., firmly set, marked 1/4 on N. face; unwitnessed.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old cor. stake set alongside, for 1/4 sec. cor., with brass cap marked.

S33  
1/4  
S4

1941

Deposit broken glass at the base of the post.

Thence, N. 89°44' W.

2.70 Old wagon road, bears NW. and SE.

22.00 Old wagon road, bears N. 10° E. and S. 10° W.

40.30 The original cor. of secs. 4, 5, 32, and 33, a cedar stake, 4 ft. long, 4 ins. diam., lying on the ground, marked 4 notches on 1 edge and 2 notches on opposite edge.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, old stake cor. set alongside, for cor. of secs. 4, 5, 32, and 33, with brass cap marked

T18S | R7W  
S32 | S33  
S5 | S4  
T19S

1941

deposit broken glass at the base of the post.

Land, level.

Soil, wet alkali clay and sandy clay; 3rd to 4th rates.

Undergrowth, salt grass and weeds on E. portion of mile; greasewood on W. portion.

Fair grazing.

DEPENDENT RESURVEY NORTH BOUNDARY OF T. 18 S., R. 8 W., Group 207, Ut.

Chains

N. 89°43' W., bet. secs. 5 and 32.  
 Over nearly level land, through medium dense undergrowth.

20.00 Leave medium dense undergrowth, continue through scattered greasewood, salt grass and weeds.

40.17 Proportionate distance; no evidence of the original  $\frac{1}{4}$  sec. cor.  
 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked

S32
S5

1941

Deposit broken glass at the base of the post.

80.34 Proportionate distance; no evidence of the original sec. cor.  
 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for restored cor. secs. 5, 6, 31, and 32, with brass cap marked

T18S	R7W
S31	S32
S6	S5
T19S	

1941

deposit broken glass at the base of the post.

Land, nearly level.  
 Soil, clay and sandy clay; 3rd rate.  
 Undergrowth, greasewood; salt grass and weeds.  
 Fair grazing.

N. 89°43' W., bet. secs. 6 and 31.  
 Over nearly level land, through scattered undergrowth.

5.00 Enter medium dense greasewood undergrowth.

13.00 Old Sevier River channel, 3 chs. wide, 5 ft. deep, drains SE.

27.00 Leave medium dense undergrowth, enter scattered greasewood and shadscale.

40.17 The original remonumented  $\frac{1}{4}$  sec. cor., an iron post, 1 in. diam., properly set, marked and witnessed as described in record of the resurvey of T. 18 S., R. 8 W., Group 207, Ut in 1937.

Thence, N. 89°33' W.

5.30 Dim road; bears N. 30° E. and S. 30° W.

24.05 Telegraph line, 7 wire, parallel to railroad.

25.80 Union Pacific Railroad, single track, bears N. 25°57' E. and S. 25°57' W.

## DEPENDENT RESURVEY NORTH BOUNDARY OF T. 19 S., R. 7 W.

- Chains
- 27.40 Telegraph line, 13 wire, bears same.
- 27.60 Graded road bet. Deseret and Black Rock, parallel to railroad.
- 40.12 The restored cor. of Ts. 18 and 19 S., Rs. 7 and 8 W., an iron post, 3 ins. diam., properly set, marked and witnessed as described in resurvey of T. 18 S., R. 8 W., Group No. 207, Utah, in 1937.
- Land, nearly level; surface broken by sandy rises and small hummocks.  
Soil, heavy clay and sandy clay; 3rd rate.  
Undergrowth, shadscale and greasewood.  
Fair grazing.

## DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 7 W.

Reestablishment of surveys executed by  
Julien Hausman, U.S. Deputy Surveyor,  
in 1871.

From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the township.

N. 0°1.1' W., bet. secs. 35 and 36.

Over gently rolling bench land, with a slight general westerly exposure, through medium dense short undergrowth and a few widely scattered juniper.

- 15.00 The S. edge of small circular clay basin, bears N. and NE.
- 25.00 The N. edge of same, bears SE. and SW.
- 30.00 Leave all but a few scattered juniper to the N. of line.
- 40.25 Proportionate distance; no evidence of position of original cor.; a cedar stake, 2 ft. long, 2 ins. diam., was found lying on the ground.
- Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old stake alongside, for restored 4 sec. cor., with brass cap marked

S35 | S36

1941

Dig pits, 18 x 18 x 12 ins., N. and S. of post, 3 ft. dist., and raise a mound of earth and stone W. of post.

- 46.70 Dim old road, bears NW. and SE.
- 80.50 The original sec. cor., a decayed juniper post, 2 ft. long, 3 ins. diam., lying on top of scattered mound of earth; no marks remaining on post.
- At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to volcanic bedrock and in a mound of stone to top, for cor. secs. 25, 26, 35, and 36, with brass cap marked

Chains

T19S	R7W
S26	S25
S35	S36

1941

Deposit broken glass at the base of the post.

Land, gently rolling bench with slight general westerly slope.  
 Soil, loose sandy clay and patches of volcanic rock outcroppings; 3rd to 4th rates.  
 Undergrowth, shadscale, greasewood, and yellow top.  
 Timber, a few scattered scrub juniper.  
 Fair grazing.

From the original cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the township.

N. 89°55' W., bet. secs. 25 and 36.

Over gently rolling bench land, through short undergrowth.

37.00 Top of flat rise on bench, bears N. and S. 35° E.; begin gradual descent over W. slope of bench.

40.35 The original  $\frac{1}{4}$  sec. cor., a cedar stake, 2 ft. long, 3 in. diam., loosely set and having dim scribe marks; unwitnessed.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam.; 27 ins. in the ground, old stake set alongside, for  $\frac{1}{4}$  sec. cor., with brass cap marked

S25
$\frac{1}{4}$
S36

1941

Deposit broken glass at the base of the post.

Thence, N. 89°59' W.

39.98 The cor. of secs. 25, 26, 35, and 36, 65 ft. below the  $\frac{1}{4}$  sec. cor.

Land, gently rolling bench.  
 Soil, loose sandy clay, and patches of volcanic rock on W. end of mile.  
 Undergrowth, shadscale and yellow top.  
 No timber.  
 Fair grazing.

N. 0°15' W., bet. secs. 25 and 26.

Over rolling bench land, through short undergrowth; along general westerly slope.

15.00 Begin gradual descent over NW. slope of bench.

40.26 The original  $\frac{1}{4}$  sec. cor., a juniper stake, 2 ft. long, 2 ins. diam., loosely set and having dim scribe marks.

At point for cor.



Chains

Deposit broken glass at the base of the post.  
Thence, N. 89°45' W.

15.00 The W. base of bench, thence over nearly level alkali flat, bears NE. and SW.

40.06 The cor. of secs. 23, 24, 25, and 26.

Land, gently rolling bench and level alkali flat.  
Soil, loose sand, wet sandy clay and heavy clay; 3rd rate.  
Undergrowth, shadscale, greasewood and yellow top on bench; scattered salt brush and weeds on flat.  
Fair grazing land on bench.

N. 0°15' W., bet. secs. 23 and 24.

Over nearly level alkali flat, through scattered salt brush

39.72 The original sec. cor., a juniper stake, 2 ft. long, 2 ins. diam., firmly set and having dim scribe marks.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old cor. stake set alongside, for  $\frac{1}{4}$  sec. cor., with brass cap marked

S23	S24
1941	

Deposit broken glass at base of post.

Thence, N. 0°05' W.,

17.10 Dim trace of an old road, bears NW. and SE.

40.46 The original sec. cor., a juniper stake, 2½ ft. long, 3 ins. diam., firmly set, marked 3 notches on S. and 1 notch on E. edges.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, old stake set alongside, for cor. secs. 13, 14, 23, and 24, with brass cap marked

T19S	R7W
S14	S13
S23   S24	
1941	

Deposit broken glass at the base of the post, and dig pit 12 x 12 x 12 ins., in each sec., 3 ft. dist. from post.

Land, nearly level alkali flat.  
Soil, wet sandy clay and heavy clay; 3rd rate.  
Undergrowth, scattered salt brush.  
Poor grazing.

U. S. GEOLOGICAL SURVEY, BUREAU OF MINERAL INVESTIGATION, TULSA DISTRICT, R. 7 W. A.

1.00 Each theodolite on sec. 13, 14, 19, and 24, on the E. side of the township on a bench, sea level 10,000 ft. N. 89°53' W., bet. secs. 13 and 24.


19.50 Over nearly level top of bench, through medium dense short undergrowth.

37.50 Begin gradual descent of 25 ft. over W. slope, bears N. 30° W. and S. 30° E.

40.15 The W. edge of bench, bears N. 20° W. and S. 20° E.; thence over barren alkali flat.

40.15 Proportionate distance; no evidence of the original 1/2 sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored 1/2 sec. cor., with brass cap marked



1941

Deposit broken glass at the base of the post.

78.00 Enter short salt grass and weeds.

80.29 The cor. of secs. 13, 14, 23, and 24.

Land, low bench on E. portion and level alkali flat on W. portion.

Soil, loose black volcanic sand on bench and sandy wet clay on flat; 3rd rate.

Undergrowth, shadeless and greasewood on bench.

Fair grazing on bench.

N. 0°29' W., bet. secs. 13 and 14.

Over level flat with scattered short salt brush and grass.

40.30 The original 1/2 sec. cor., a decayed juniper stake, 2 ft. long, 1/2 in. diam., lying on the ground, no marks remaining.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old stake set alongside, for 1/2 sec. cor., with brass cap marked



1941

Deposit broken glass at the base of the post.

Continue on same course, beginning new measurement.

28.70 Leave alkali flat at the S. edge of bench, bears S. 40° E. and N. 40° W.; ascend broken S. slope, 30 ft.

35.00 Top of bench, bears with base; thence over gently rolling top with black volcanic sand, through dense undergrowth.

DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 7 W.

Chains  
40.30

The original sec. cor., a juniper stake, 3 ft. long, 4 in. diam., firmly set, marked 4 notches on S. and 1 notch on E. edges, and having other dim scribe marks.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, old stake set alongside, for cor. of secs. 11, 12, 13, and 14, with brass cap marked

T19S	R7W
S11	S12
S14	S13

1941

Deposit broken glass at the base of the post.

Land, level alkali flat on S. portion, low bench on N. portion.

Soil, wet alkali clay on flat and loose black sand on bench; 3rd rate.

Undergrowth, scattered salt brush and grass on flat, greasewood and shadscale on bench.

Fair grazing on bench.

From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the township.

N. 89°17' W., bet. secs. 12 and 13.

Over gently rolling sandy bench, through medium dense undergrowth.

33.00

The E. edge of circular barren clay basin.

40.40

The original  $\frac{1}{4}$  sec. cor., a juniper stake, 4 ft. long, 3 ins. diam., lying on the ground and marked  $\frac{1}{4}$  on one face.

At point for cor., on W. edge of clay basin.

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to solid rock and in a large mound of stone to top old stake set alongside; for  $\frac{1}{4}$  sec. cor., with brass cap marked

S12
S13

1941

Thence, S. 89°58' W.

40.45

The cor. of secs. 11, 12, 13, and 14.

Land, gently rolling bench; surface broken by sandy hummocks and interspersed with small clay basins.

Soil, loose black volcanic sand lying on hardpan, and clay ~~3rd rate~~

Undergrowth, greasewood and shadscale.

Fair grazing.

DEPENDENT RESURVEY OF THE SUBDIVISION, T. 19 S., R. 7 W.

Chains

N.  $0^{\circ}10'$  E., bet. secs. 11 and 12.

Over gently rolling bench, through medium dense undergrowth.

40.22 Proportionate distance; no evidence of the original  $\frac{1}{4}$  sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked

S11	S12
-----	-----

1941

Deposit broken glass at the base of the post.

55.00 Dim trace of an old unused road, bears N.  $33^{\circ}$  W. and S.  $33^{\circ}$  E.

56.00 The N. base of bench, bears NE. and SW.; thence over alkali flat with scattered sand rises.

80.44 The original sec. cor., a juniper post, 3 ft. long, 3 ins. diam., lying on the ground, marked 5 notches on one edge.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, old post cor. set alongside, for cor. of secs. 1, 2, 11, and 12, with brass cap marked

T19S	R7W
S2	S1

S11	S12
-----	-----

1941

Deposit broken glass at the base of the post.

Land, rolling bench and nearly level alkali flat, the surface of which is broken by low sand rises.

Soil, loose sand lying on a hardpan on the bench, and wet alkali sandy clay on flat; 3rd rate.

Undergrowth, shadscale, greasewood and salt brush.

Fair grazing on portion of mile.

oooo

From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the township.

N.  $89^{\circ}16'$  W., bet. secs. 1 and 12.

Over level alkali clay flat void of vegetation.

28.00 Enter scattered low sand rises with salt brush and grass.

40.27 The original  $\frac{1}{4}$  sec. cor., a juniper stake, 3 ft. long, 2 ins. diam., firmly set, marks illegible.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old stake cor. set alongside, for  $\frac{1}{4}$  sec. cor., with brass cap marked

DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 7 W.

Chains

S1  
 $\frac{1}{4}$  ———  
 S12

1941

Deposit broken glass at the base of the post.  
 Hence, S. 89°56' W.

10.20 The cor. of secs. 1, 2, 11, and 12.

Land, level alkali clay flat; surface on W. portion broken by low sandy hummocks or rises.  
 Soil, heavy wet clay and sandy clay; 3rd rate.  
 Undergrowth, scattered salt brush and salt grass on W. portion; barren on E. end of mile.  
 Poor grazing.

From the restored cor. of secs. 1, 2, 35, and 36, on the E. bdy. of the township.

S. 0°04' E., bet. secs. 1 and 2.

Over level, barren alkali and mud flat.

10.07 Proportionate distance; no evidence of the original  $\frac{1}{4}$  sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked

$\frac{1}{4}$   
 S2 | S1  
 1941

Deposit broken glass at the base of the post.

60.00 Enter scattered sandy hummocks or rises with scattered salt brush and weeds.

60.36 The cor. of secs. 1, 2, 11, and 12.

Land, level alkali clay flat; surface broken on S. portion by low sandy hummocks or rises.  
 Soil, heavy wet alkali clay and sandy clay; 3rd and 4th rates.  
 Undergrowth, scattered salt brush and weeds on S. portion.  
 Poor grazing.

From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the township.

N. 0°23' W., bet. secs. 34 and 35.

Over level land, through scattered salt brush and salt grass.

60.24 Proportionate distance; no evidence of the original  $\frac{1}{4}$  sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked

DEPENDENT RESURVEY OF THE SUBDIVISION, T. 19 S., R. 7 W.

Chains

$\frac{1}{4}$   
S34 | S35

1941

Deposit broken glass at the base of the post.

72.00 Shallow slough, 1 ch. wide, drains NE.

80.48 The original sec. cor., a cedar stake, 4 ft. long, 4 ins. diam., firmly set, marked 1 notch on S. and 2 notches on E. edges; other scribe marks illegible.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, old stake cor. set alongside, for cor. secs. 26, 27, 34, and 35, with brass cap marked

T19S | R7W  
S27 | S26  
-----  
S34 | S35

1941

Deposit broken glass at the base of the post.

Land, level clay flat.

Soil, heavy clay and sandy clay, saturated with alkali; 3rd rate.

Undergrowth, scattered salt brush and short salt grass and weeds.

Poor grazing.

From the cor. of secs. 25, 26, 35, and 36.

S. 89°55' W., bet. secs. 26 and 35.

Over rolling bench land, through scattered short undergrowth; descend 45 ft. over W. slope of volcanic outcroppings.

6.00 The west base of bench, enter level alkali flat with scattered salt brush, bears N. and S. 20° W.

21.80 Dim trace of old unused road, bears NW. and SE.

40.21 The original  $\frac{1}{4}$  sec. cor., a juniper stake, 3 ft. long, 3 ins. diam., lying on ground, no marks remaining.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old stake cor. set alongside, for  $\frac{1}{4}$  sec. cor., with brass cap marked

S26  
 $\frac{1}{4}$  -----  
S35

1941

Deposit broken glass at the base of the post.

Continue on same course, beginning new measurement.

DEPENDENT RESURVEY OF SUBDIVISION, T. 19N. R. 7W. S. 22

Chains

and 10

- 5.30 A bog spring, 1 ch. in diam., bears N. of line about 1 ch. dist.
- 21.80 Dim trace of old road, bears N. 20° W. and S. 20° E.
- 23.90 Dim trace of old road, bears N. and S.
- 26.80 Slough, 75 lks. wide, drains N.
- 40.24 The cor. of secs. 26, 27, 34, and 35.  
Land, level alkali clay flat except E. 6 chs., which is W. slope of bench.  
Soil, wet clay and sandy clay on flat; rocky and sandy on bench; 3rd and 4th rates.  
Undergrowth, salt brush and salt grass on flat; scattered shadscale on bench.  
Poor grazing.

N. 0°01' E., bet. secs. 26 and 27.

Over nearly level flat, through scattered undergrowth.

- 26.00 Slough, 50 lks. wide, drains N. 10° W.

- 40.24 Proportionate distance; no evidence of the original  $\frac{1}{4}$  sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked

S27	S26
-----	-----

1941

Deposit broken glass at the base of the post, and dig pits 18 x 18 x 12 ins., N. and S. of post, 3 ft. dist.

- 45.00 Dim trace of old road, bears N. 10° W. and S. 10° E.

- 56.00 Dim trace of old road, bears NW. and SE.

- 80.48 Proportionate distance; no evidence of the original sec. cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for restored cor. secs. 22, 23, 26, and 27, with brass cap marked

T19S	R7W
S22	S23

S27	S26
-----	-----

1941

Deposit broken glass at the base of the post.

Land, nearly level flat, the surface of which is broken by small sandy rises on S. end of mile.

Soil, wet heavy clay and sandy clay; 3rd rate.

Undergrowth, very scattered salt brush and salt grass.

Poor grazing.

... ..

DEPENDENT RESURVEY OF THE SUBDIVISION, T. 19 S., R. 7 W.

Chains

From the cor. of secs. 23, 24, 25, and 26.


West, bet. secs. 23 and 26.

Over nearly level flat.

7.00 Enter greasewood and salt brush.

40.07 Proportionate distance; no evidence of the original  $\frac{1}{4}$  sec. cor.

Set an iron post, 3 ft. long, 1 in. diam.; 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked



1941

Deposit broken glass at the base of the post.

42.00 Leave greasewood, continue through very scattered salt brush.

46.20 Dim trace of old road, bears N. 10° E. and S. 10° W.

80.14 The cor. of secs. 22, 23, 26, and 27.

Land, nearly level.

Soil, heavy wet clay and sandy clay; 3rd rate.

Undergrowth, greasewood and salt brush.


Poor grazing.

N. 0°27' W., bet. secs. 22 and 23.

Over nearly level flat, through scattered undergrowth.

40.24 Proportionate distance; no evidence of the original  $\frac{1}{4}$  sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked




1941

Deposit broken glass at the base of the post.

80.48 Proportionate distance; no evidence of the original sec. cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for restored cor. secs. 14, 15, 22, and 23, with brass cap marked



1941

Deposit broken glass at the base of the post.

Land, nearly level flat.

## DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 7 W.

Chains

Soil, sandy clay and wet heavy clay; 3rd rate.  
Undergrowth, scattered short salt brush and salt grass.  
Poor grazing.

From the cor. of secs. 13, 14, 23, and 24.

N. 89°51' W., bet. secs. 14 and 23.

Over level flat, through very scattered salt brush and salt grass.

28.50 Dim trace of old road, bears NW. and SE.

40.31 The original  $\frac{1}{4}$  sec. cor., a juniper stake, 2 ft. long, 2 ins. diam., set in the ground, no marks remaining.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old stake cor. set alongside, for  $\frac{1}{4}$  sec. cor., with brass cap marked

$$\begin{array}{r} S14 \\ \frac{1}{4} \\ \hline S23 \end{array}$$

1941

Deposit broken glass at the base of the post.

Thence, N. 89°42' W.

21.90 Dim trace of old road, bears N. 18° W. and S. 18° E.

40.23 The cor. of secs. 14, 15, 22, and 23:

Land, level flat.

Soil, heavy clay and sandy clay; 3rd rate.  
Undergrowth, very scattered salt brush and salt grass.  
Poor grazing.

N. 0°26' W., bet. secs. 14 and 15.

Over level flat through very scattered short undergrowth.

40.24 Proportionate distance; no evidence of the original  $\frac{1}{4}$  sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked

$$\begin{array}{r} \frac{1}{4} \\ S15 \mid S14 \end{array}$$

1941

Deposit broken glass at the base of the post.

45.60 Dim trace of old road, bears N. 20° W. and S. 20° E.

62.50 Dim trace of old road, bears N. 30° W. and S. 30° E.

80.48 Proportionate distance; no evidence of the original sec. cor.

DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 7 W.

Chains

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for restored cor. secs. 10, 11, 14, and 15, with brass cap marked

T19S	R7W
S10	S11
S15	S14

1941

Deposit broken glass at the base of the post.

Land, level.

Soil, clay and sandy clay, saturated with alkali; 3rd rate. Undergrowth, very scattered salt brush and weeds. Poor grazing.

From the cor. of secs. 11, 12, 13, and 14.

S. 89°35' W., bet. secs. 11 and 14.

Over nearly level top of sandy bench through medium dense greasewood and shadscale.

5.00 The W. edge of bench, 15 ft. below cor., bears NW. and SE.; thence over nearly level flat, the surface of which is broken by hummocks.

20.00 Thence over smooth barren clay flat.

25.00 Enter scattered salt brush.

40.32 The original  $\frac{1}{4}$  sec. cor., a juniper post, 4 ft. long, 2 ins. diam., firmly set, no marks remaining.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old post cor. set alongside, for  $\frac{1}{4}$  sec. cor., with brass cap marked

S11
$\frac{1}{4}$
S14

1941

Deposit broken glass at the base of the post.

Thence, N. 89°17' W.

40.27 The cor. of secs. 10, 11, 14, and 15.

Land, nearly level flat, and low bench on E. end of mile. Soil, sand clay saturated with alkali and salt on the flat; black volcanic sand and cinder on the bench; 3rd rate. Undergrowth, scattered salt brush and weeds on the flat; shadscale and greasewood on the bench. Poor grazing.

N. 0°19' E., bet. secs. 10 and 11.

Over level land, through scattered short undergrowth.


DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S. & R. 7 W.

Chains

221210

40.24 Proportionate distance; no evidence of the original  $\frac{1}{4}$  sec. cor.


Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked



Deposit broken glass at the base of the post.

80.48 Proportionate distance; no evidence of the original sec. cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for restored cor. secs. 2, 3, 10, and 11, with brass cap marked



Deposit broken glass at the base of the post.

Land, level.

Soil, sandy clay saturated with alkali and salt; 3rd rate Undergrowth, very scattered salt brush, weeds and grass. Poor grazing.

From the cor. of secs. 1, 2, 11, and 12.

N.  $89^{\circ}33'$  W., bet. secs. 2 and 11.

Over level flat with scattered hummocks, through salt brush.


10.00 Leave all undergrowth, continue over barren flat.

17.30 Dim trace of old unused road, bears N.  $33^{\circ}$  W. and S.  $33^{\circ}$

40.12 The original  $\frac{1}{4}$  sec. cor., a juniper stake, 4 ft. long, 2 ins. diam., firmly set, no marks remaining.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old stake cor. set alongside, for  $\frac{1}{4}$  sec. cor., with brass cap marked



1941

Deposit broken glass at the base of the post.

Thence, S.  $89^{\circ}50'$  W.

5.00 Enter short salt brush and weeds.

DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 7 W.

Chains  
21.00

Leave same.

40.33

The cor. of secs. 2, 3, 10, and 11.

Land, level flat; scattered hummocks on E. end of mile.  
Soil, wet sandy clay and heavy clay; 4th rate.  
Undergrowth, scattered salt brush and weeds.  
Poor grazing.

From the cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the township.

S. 0°12' E., bet. secs. 2 and 3.

Over level barren clay flat.

40.10

Proportionate distance; no evidence of the original 1/4 sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored 1/4 sec. cor., with brass cap marked

1/4  
S3 | S2  
1941

Deposit broken glass at the base of the post.

80.34

The cor. of secs. 2, 3, 10, and 11.

Land, level clay flat.

Soil, wet clay lying on shale hardpan; 4th rate.  
No vegetation.  
No grazing.

From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the township.

N. 0°12' W., bet. secs. 33 and 34.

Over nearly level land, through dense salt grass.

40.23

Proportionate distance; no evidence of the original 1/4 sec. cor.

Set an iron post, 3 ft. long, 1 in. diam.; 20 ins. in the ground to shale hardpan and in a large mound of stone, for restored 1/4 sec. cor., with brass cap marked

1/4  
S33 | S34  
1941

Deposit broken glass at the base of the post.

80.45

Proportionate distance; no evidence of the original sec. cor.

Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground to shale hardpan and in a large mound of stone, for restored cor. secs. 27, 28, 33, and 34, with brass cap marked

DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 7 W.

Chains

T19S	R7W
S28	S27
S33	S34

1941

Deposit broken glass at the base of post, and dig pits, 18 x 18 x 12 ins., in each sec., 3 ft. dist. from post.

Land, nearly level.  
Soil, black clay and sandy clay, lying on a shale bedrock;  
3rd rate.  
Undergrowth, dense salt grass.  
Fair to good grazing.

From the cor. of secs. 26, 27, 34, and 35.

S. 89°55' W., bet. secs. 27 and 34.

Over nearly level flat through short salt brush.

15.00 Leave nearly all salt brush and enter salt grass.

26.00 Slough, 50 lbs. wide, 1 ft. deep, drains N.

40.00 The original sec. cor., a juniper stake, 3 ft. long, 2 ins. diam., rotted off at the surface, no marks remaining.

At the point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old stake set alongside, for sec. cor., with brass cap marked

S27

S34

1941

Deposit broken glass at the base of the post.

Continue on same course, beginning new measurement.

2.10 A five strand barbed wire fence, bears N. 4°05' W., and S. 4°05' E.; thence through heavier salt grass.

15.00 The E. edge of pond, bears N. 15° W., about 18 chs. dist. to E. end of earth dyke bearing westerly.

Thence across pond.

29.00 The W. side of pond, bears S. 15° E., and N. 15° W. about 12 chs. dist. to W. end of dyke along N. side of pond; thence slight ascent through salt brush to:

34.30 Unimproved road on top of slight rise, bears N. 15° W. and S. 15° E.

40.05 The cor. of secs. 27, 28, 33, and 34.

Land, nearly level.  
Soil, wet clay and sandy clay; 3rd rate.  
Undergrowth, salt grass and salt brush.  
Fair grazing

DEPENDENT RESERVEY OF SUBDIVISION, T. 19 S., R. 7 W.


Chains

N. 0°09' W., bet. secs. 27 and 28.

Over nearly level land, through short salt grass.

- 4.00 Leave nearly all salt grass, continue through salt brush.
- 15.00 Unimproved road, bears N. 15° W. and S. 15° E.
- 30.00 The W. edge of pond, bears N. 10° W. and S. 10° E.; thence across pond.
- 40.23 Proportionate distance; no evidence of the original  $\frac{1}{4}$  sec. cor., which falls in pond; therefore at a point, West, 2.00 chs. dist. from the true cor. point:

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for witness cor. to the restored  $\frac{1}{4}$  sec. cor., with brass cap marked




Raise a small mound of stone around post.

Corner set on W. edge of pond.

Continue from true point for the  $\frac{1}{4}$  sec. cor.

- 73.50 Earth dyke, 20 lks. wide, 3 ft. high, across N. side of pond, bears E. and W.; thence over level grass land.
- 80.45 Proportionate distance; no evidence of the original sec. cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for restored cor. secs. 21, 22, 27, and 28, with brass cap marked



1941

Deposit broken glass at the base of the post.

Land, nearly level.  
 Soil, clay and sandy clay; 3rd rate.  
 Undergrowth, salt brush and salt grass.  
 Fair to poor grazing.

From the cor. of secs. 22, 23, 26, and 27.

S. 89°40' W., bet. secs. 22 and 27.

Over nearly level land, through short salt brush.

- 0.90 Paint trace of old road, bears N. and S.
- 7.20 Dim old road, bears N. 30° W. and S. 30° E.
- 9.30 Slough, 25 lks. wide, 1 ft. deep, drains NW.
- 39.93 The original  $\frac{1}{4}$  sec. cor., a juniper stake, 2 ft. long, 3

DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 7 W.

Chains	<p>ins. diam., firmly set, marked <math>\frac{1}{4}</math> on N. face.</p> <p>At point for cor.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old stake cor. deposited alongside, for <math>\frac{1}{4}</math> sec. cor., with brass cap marked</p> <div style="text-align: center;"> <math display="block">\begin{array}{r} S22 \\ \hline S27 \end{array}</math> <p>1941</p> </div> <p>Deposit broken glass at the base of the post.</p> <p>Thence, N. <math>89^{\circ}53'</math> W.</p> <p>11.00 Leave salt brush and enter dense salt grass.</p> <p>21.00 Six strand barbed wire fence, bears N. <math>0^{\circ}55'</math> W., and S. <math>0^{\circ}55'</math> E.</p> <p>38.10 Stream, 10 lks. wide, 1 ft. deep, flows N. from a pond to the S.</p> <p>40.25 The cor. of secs. 21, 22, 27, and 28.</p> <p>Land, nearly level. Soil, heavy clay and wet sandy clay; 3rd rate. Undergrowth, salt brush and salt grass. Fair grazing.</p> <hr/> <p>N. <math>0^{\circ}33'</math> W., bet. secs. 21 and 22.</p> <p>Over nearly level land, through salt grass.</p> <p>20.40 Six strand barbed wire fence, bears E. and W.; junction of fence from the S. with E. and W. fence, bears W. of line, 3.90 chs. dist.</p> <p>30.00 Shallow slough, 1 ch. wide, drains NW.</p> <p>40.23 Proportionate distance; no evidence of the original <math>\frac{1}{4}</math> sec. cor.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored <math>\frac{1}{4}</math> sec. cor., with brass cap marked</p> <div style="text-align: center;"> <math display="block">\begin{array}{r} \frac{1}{4} \\ S21 \quad   \quad S22 \end{array}</math> <p>1941</p> </div> <p>Deposit broken glass at the base of the post.</p> <p>40.36 The SW. cor. of wire fence bearing N. and E.; bears E. of line, 40 lks. dist.</p> <p>80.45 The original sec. cor., a juniper stake, 3 ft. long, 2 ins. diam., firmly set and having dim scribe marks; cor. set in wire fence line bearing N. and S.</p> <p>At the point for cor.</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with the old stake cor. deposited alongside, for</p>
--------	--

DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 7 W.

Chains

cor. of secs. 15, 16, 21, and 22, with brass cap marked

T19S	R7W
S16	S15
S21	S22

1941

Deposit broken glass at the base of the post.

Land, nearly level.

Soil, heavy wet clay; 3rd rate.

Undergrowth, salt grass and weeds.

Fair grazing.

From the cor. of secs. 14, 15, 22, and 23.

N. 89°52' W., bet. secs. 15 and 22.

Over level land, through short salt weed and salt brush.

0.10 Very dim road, bears N. and S.

33.80 Old road, bears N. 20° W. and S. 20° E.

40.26 The original  $\frac{1}{4}$  sec. cor., a juniper stake, 2 $\frac{1}{2}$  ft. long, 3 ins. diam., firmly set and having dim scribe marks.

At the point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old cor. stake set alongside, for  $\frac{1}{4}$  sec. cor., with brass cap marked

S15
$\frac{1}{4}$
S22

1941

Deposit broken glass at the base of the post.

Thence, S. 89°37' W.

9.30 Slough, 1 ch. wide, drains N. 30° W.; thence through salt grass.

40.11 The cor. of secs. 15, 16, 21, and 22.

Land, level.

Soil, clay; 3rd rate.

Undergrowth, salt brush and salt grass.

Fair to poor grazing.

N. 0°29' W., bet. secs. 15 and 16.

Over nearly level land, through salt grass, along E. side of wire fence parallel to line.

40.49 Proportionate distance; no evidence of the original  $\frac{1}{4}$  sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked

Chains

$\frac{1}{4}$   
 S16 | S15  
 1941

Deposit broken glass at the base of the post.

30.92 Proportionate distance; no evidence of the original sec. cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for restored cor. secs. 9, 10, 15, and 16, with brass cap marked

T19S	R7W
S9	S10
S16   S15	
1941	

Deposit broken glass at the base of the post, and dig pits 18 x 18 x 12 ins., in each sec., 3 ft. dist. from post.

Cor. set. 32 lks. E. of wire fence bearing N. and S.

Land, nearly level.  
 Soil, clay and sandy clay; 3rd rate.  
 Undergrowth, salt grass and salt weed.  
 Fair grazing.

From the cor. of secs. 10, 11, 14, and 15.

N. 89°35' W., bet. secs. 10 and 15.

Over nearly level flat, through scattered salt brush.

10.50 Dim old road, bears N. 15° W. and S. 15° E.

40.20 The original 1/4 sec. cor., a juniper stake, 3 ft. long, 3 ins. diam., squared at the top, firmly set, and having dim scribe marks.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old stake cor. set alongside, for 1/4 sec. cor., with brass cap marked

$\frac{1}{4}$   
 S10  
 ———  
 S15  
 1941

Deposit broken glass at the base of the post.

Thence, N. 89°49' W.

20.30 Low sand rise, bears S. 30° E., and N., 1.50 chs. dist. to end.

23.00 Enter salt grass.

40.17 The cor. of secs. 9, 10, 15 and 16.

Land, nearly level.  
 Soil, clay; 3rd rate.

DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 7 W.

Chains

Undergrowth, salt grass and salt brush.  
 Poor to fair grazing.

N. 0°22' W., bet. secs. 9 and 10.


Over nearly level land, through salt grass; line follows along E. side of wire fence about parallel to line.

40.49

The original  $\frac{1}{4}$  sec. cor., the stump of a juniper post, found in the ground at cor. of fences bearing S. and W.

At the point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old stump of post set alongside, for  $\frac{1}{4}$  sec. cor., with brass cap marked



Deposit broken glass at the base of the post.

Thence, N. 0°07' W.

9.50


Leave salt grass and enter salt brush and weeds.

40.00

The original sec. cor., a juniper post, 2 ft. long, 2 ins. diam., partly burnt, firmly set; no scribe marks remaining

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, old stake cor. deposited alongside, for cor. secs. 3, 4, 9, and 10, with brass cap marked



1941

Deposit broken glass at the base of the post.

Land, nearly level.

Soil, clay and sandy clay; 3rd rate.

Undergrowth, salt grass, salt brush and weeds.

Fair to poor grazing.

From the cor. of secs. 2, 3, 10, and 11.

N. 89°38' W., bet. secs. 3 and 10.

Over nearly level clay flat, through scattered salt weeds.

14.00

Enter salt brush.

38.20

Old road, bears nearly N. and S.

40.54

Proportionate distance; no evidence of the original  $\frac{1}{4}$  sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked

Chains	
	$\frac{S3}{\frac{1}{4}}$ $S10$ <p>1941</p>
	Deposit broken glass at the base of the post.
80.90	Dim road, bears N. and S.
81.08	The cor. of secs. 3, 4, 9, and 10.
	Land, nearly level. Soil, clay; 3rd rate. Undergrowth, short scattered salt brush and weeds. Poor grazing.
	From the cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the township. S. 0°10' W., bet. secs. 3 and 4. Over nearly level clay flat, through scattered salt weeds.
14.30	Old road, bears NW. and SE.
20.00	The NE. cor. of wire fences bearing S. and W., bears W. of line, 40 lks. dist.
40.02	Proportionate distance; no evidence of the original $\frac{1}{4}$ sec. cor.
	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$ $S4   S3$ <p>1941</p>
	Deposit broken glass at the base of the post.
60.00	The SE. cor. of wire fences bearing N. and W., bears W. of line, 10 lks. dist.
70.00	Enter salt grass.
80.03	The cor. of secs. 3, 4, 9, and 10.
	Land, nearly level. Soil, wet clay and sandy clay, saturated with alkali; 3rd rate. Undergrowth, salt brush, weeds, and grass. Poor to fair grazing.
	From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the township. N. 0°20' W., bet. secs. 32 and 33. Over nearly level land, through short salt grass, salt brush and weeds.
40.23	Proportionate distance; no evidence of the original $\frac{1}{4}$ sec. cor.

DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 7 W.

Chains

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked




Deposit broken glass at the base of the post.

80.45

Proportionate distance; no evidence of the original sec. cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for restored cor. secs. 28, 29, 32, and 33, with brass cap marked



Deposit broken glass at the base of the post.

Land, nearly level.  
Soil, sandy clay lying on hardpan; 3rd rate.  
Undergrowth, short salt grass, salt brush and weeds.  
Fair grazing.

From the cor. of secs. 27, 28, 33, and 34.


S. 39°42' W., bet. secs. 28 and 33.

Over nearly level land, through salt grass and salt brush.

40.07

Proportionate distance; no evidence of the original  $\frac{1}{4}$  sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked



1941

Deposit broken glass at the base of the post.

42.35

The American Telephone and Telegraph transcontinental line, 14 wires, bears N. 0°18' E. and S. 0°18' W.; pole No. 5610L, bears to the N. of line, 30 lks. dist.

79.50

Old ditch, 2 ft. wide, 1 ft. deep, drains N. 28° W.

80.15

The cor. of secs. 28, 29, 32, and 33.

Land, nearly level surface broken by small hummocks.  
Soil, dark clay lying on hardpan; 3rd rate.  
Undergrowth, salt grass and salt brush.  
Fair grazing.

DEPENDENT RESURVEY OF THE SUBDIVISION, T. 19 S., R. 7 W.

Chains

N. 0°15' W., bet. secs. 28 and 29.

Over nearly level land, through short salt grass and salt brush.

1.25 Small ditch, 2 lks. wide, drains N. 28° W.

39.90 Six strand barbed wire fence, bears N. 89°40' E., and S. 89°40' W.

40.23 Proportionate distance; no evidence of the original ¼ sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored ¼ sec. cor., with brass cap marked

S29 | S28

1941

Deposit broken glass at the base of the post.

80.45 The original sec. cor., a juniper stake, 2 ft. long, 2 ins squared, firmly set and marked 2 notches on S. and ¼ notch on E. edges.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, old stake cor. deposited alongside, for cor. secs. 20, 21, 22, and 29, with brass cap marked

T19S | R7W  
S20 | S21

S29 | S28

1941

Deposit broken glass at the base of the post.

Land, nearly level.

Soil, clay; 3rd rate.

Undergrowth, salt grass and salt brush.

Fair to poor grazing.

From the cor. of secs. 21, 22, 27, and 28.

S. 89°45' W., bet. secs. 21 and 28.

Over nearly level land, through scattered salt brush and salt grass.

3.60 Six strand barbed wire fence, bears N. and S.

13.90 Dim old road, bears N. 5° W. and S. 5° E.

31.40 Dim old road, bears N. 30° W. and S. 30° E.

40.29 The original ¼ sec. cor., a juniper stake, 2 ft. long, 2 ins. diam.; firmly set and having dim scribe marks.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old stake cor. set alongside, for ¼ sec. cor., with brass cap marked

DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 7 W.

Chains

S21  
1/4 S28

1941

Deposit broken glass at the base of the post.

Thence, S. 89°40' W.

1.70 American Telephone and Telegraph transcontinental line, 14 wires, bears N. 0°18' E. and S. 0°18' W.

40.01 The cor. of secs. 20, 21, 28, and 29.

Land, nearly level.  
Soil, clay; 3rd rate.  
Undergrowth, salt brush and salt grass.  
Fair to poor grazing.

N. 0°25' W., bet. secs. 20 and 21.

Over nearly level land, through short undergrowth.

40.10 The original 1/4 sec. cor., a juniper stake, greatly decayed, 2 ft. long, 2 ins. diam., set in the ground; no marks remaining.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old cor. stake set alongside, for 1/4 sec. cor., with brass cap marked

S20 | S21  
1941

Deposit broken glass at the base of the post.

Thence, N. 0°23' W.

40.33 The original sec. cor., a juniper stake, 2 ft. long, 3 ins. diam., set in the ground; no marks remaining.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, old cor. stake set alongside, for cor. of secs. 16, 17, 20, and 21, with brass cap marked

T19S | R7W  
S17 | S16  
S20 | S21  
1941

Deposit broken glass at the base of the post.

Land, nearly level.  
Soil, clay; 3rd rate.  
Undergrowth, salt brush and salt grass.  
Poor grazing.

DEPENDENT RESURVEY OF SUBDIVISION T. 19 S. R. 7 W.

Chains

enlaro

From the cor. of secs. 15, 16, 21, and 22.

S. 89° 41' W., bet. secs. 16 and 21.

Over nearly level land, through salt grass.

19.60 Blough, 50 lks. wide, drains N.

19.90 Six strand barbed wire fence, bears N. and S.

25.00 Leave salt grass and continue through salt brush.

25.50 Low sandy rise, bears N. and S.

26.00 The original 1/4 sec. cor., a juniper stake, 2 ft. long, 3 ins. diam., firmly set and marked 1/4 on N. face.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old cor. stake set alongside, for 1/4 sec. cor., with brass cap marked

S16  
1/4  
S21

1941

Deposit broken glass at the base of the post.

Continue on same course, beginning new measurement.

0.50 The American Telephone and Telegraph transcontinental line wires, bears N. 0° 18' E. and S. 0° 18' W.

0.80 Low sandy ridge or rise, bears N. and S.

10.00 Old road, bears N. 10° W. and S. 10° E.

11.60 Dirt road, bears N. 30° W. and S. 30° E.

20.00 The cor. of secs. 16, 17, 20, and 21.

Land, nearly level.

Soil, clay and sandy clay; 3rd. rate.

Undergrowth, salt brush and scattered salt grass.

Poor to fair grazing.

N. 0° 27' W., bet. secs. 16 and 17.

Over level flat through scattered salt brush.

13.26 Proportionate distance; no trace of the original 1/4 sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored 1/4 sec. cor., with brass cap marked

S17 | S16  
1941

Deposit broken glass at the base of the post.

DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 7 W.

Chains

80.52 The original sec. cor., a charred juniper post, 3 ft. long, 2 ins. diam., squared at top, set in the ground. No marks visible.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, old cor. stake set alongside, for cor. secs. 8, 9, 16, and 17, with brass cap marked

T19S	R7W
S8	S9

S17	S16
-----	-----

1941

Deposit broken glass at the base of the post.

Land, level.

Soil, wet alkali and sandy clay; 4th rate.

Undergrowth, scattered salt brush about 6 ins. high.

Poor grazing.

From the cor. of secs. 9, 10, 15, and 16.

S. 89°29' W., bet. secs. 9 and 16.

Over nearly level land, through salt grass.

0.30 Old wire fence, bears N. and S.

8.10 Slough, 50 lks. wide, drains N.

20.45 Six strand barbed wire fence, bears N. and S.

27.00 Leave salt grass and enter salt brush and sandy land.

34.37 From this point; the SE. cor. of wire fence inclosing beacon light and building, bears N. of line, 43 lks. dist.; fence extends N. for 1.50 chs. to NE. cor., and thence W. 1.50 chs. to NW. cor.

35.10 Point from which; beacon No. 50 on air route between Salt Lake City, and Los Angeles; bears N. of line 1.20 chs. dist.

35.25 Point from which the SE. cor. of small corrugated building, about 12 x 16 ft., bears N. of line 75 lks. dist.

35.87 Point from which, the SW. cor. of fence inclosing beacon light and building, bears N. of line 41 lks. dist.

38.10 Dim road, bears NW. and S. 10° E.

39.30 American Telephone and Telegraph transcontinental line, 14 wires, bears N. 0°18' E. and S. 0°18' W.

40.16 The original ¼ sec. cor., a juniper stake, 2 ft. long, 2 ins. diam., firmly set; no marks remaining.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old cor. stake set alongside, for ¼ sec. cor., with brass cap marked

Chains

S9

S2.

S16

1941

Deposit broken glass at the base of the post.

Thence, S. 89°20' W.

20.50 Dim road, bears N. 10° W. and S. 10° E.

35.50 Dim road, bears N. and S.

39.70 The cor. of secs. 8, 9, 16, and 17.

and, nearly level.  
Soil, sandy clay and clay; 3rd rate.  
Undergrowth, salt brush and salt grass.  
Poor to fair grazing.

N. 0°13' W., bet. secs. 8 and 9.

Over level flat through scattered salt brush.

26.00 Old road, bears N. 20° W. and S. 20° E.

37.20 Old road, bears E. and W.

39.00 Leave undergrowth and continue over barren flat.

40.29 The original  $\frac{1}{4}$  sec. cor., a juniper stake, greatly decayed  
 $1\frac{1}{2}$  ft. long, 3 ins. diam., firmly set; no marks remaining

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the  
ground, old cor. stake set alongside, for  $\frac{1}{4}$  sec. cor.,  
with brass cap marked

S8 | S9

1941

Deposit broken glass at the base of post, and dig pits,  
18 x 18 x 12 ins., N. and S. of post, 3 ft. dist.

Thence, N. 0°15' W.

11.70 Leave barren flat and enter scattered salt brush.

12.20 Old road, bears N. 5° E. and S. 10° W.

34.70 Enter low sandy rises, bears NE. and W.

40.22 The original sec. cor., a juniper stake, 3 ft. long, 3  
ins. diam., firmly set, marked 5 notches on S. and  
4 notches on E. edges,

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the  
ground, old cor. stake set alongside, for cor. secs. 4, 5,  
8, and 9, with brass cap marked

DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 7 W.

Chains

T19S	R7W
S5	S4
S8	S9

1941

Deposit broken glass at the base of the post.

Land, level flat.

Soil, sandy clay; 3rd rate.

Undergrowth, salt brush on portions of mile.

Poor grazing.

From the cor. of secs. 3, 4, 9, and 10.

S. 89°28' W., bet. secs. 4 and 9.

Over nearly level land, through salt grass.

20.00 Wire fence, bears N. and S.

28.00 Slough, 50 lks. wide, drains N.

38.60 American Telephone and Telegraph transcontinental line, 14 wires, bears N. 0°18' E., and S. 0°18' W.

39.91 The original 1/4 sec. cor., a stump of a juniper post having been burnt, firmly set in the ground; no marks remaining.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old cor. stake set alongside, for 1/4 sec. cor., with brass cap marked

1/4	S4
	S9

1941

Deposit broken glass at the base of the post.

Continue on same course, beginning new measurement.

20.00 Leave salt grass and enter scattered salt brush.

36.60 Old road in bottom of swale or drain, bears N. 20° E. and S. 20° W.

39.89 The cor. of secs. 4, 5, 8, and 9.

Land, nearly level.

Soil, sandy clay; 3rd rate.

Undergrowth, salt grass and salt brush.

Fair to poor grazing.

From the cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the township.

S. 0°26' E., bet. secs. 4 and 5.

Over nearly level land, through medium dense short undergrowth.

DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 7 W.


Chains

acres

21.40 Dlm road, bears E. and W.

40.75 Proportionate distance; no evidence of the original position for the  $\frac{1}{4}$  sec. cor., old cor. stake was found lying on the ground out of place.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old cor. stake set alongside, for  $\frac{1}{4}$  sec. cor., with brass cap marked



Deposit broken glass at the base of the post.

60.00 Low sandy rise, bears NE. and SW.

81.28 The cor. of secs. 4, 5, 8, and 9.

Land, nearly level; surface on S. portion is broken by small sandy rises.  
Soil, sandy clay; 3rd rate.  
Undergrowth, salt brush and scattered greasewood.  
Poor grazing land.

From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the township.


N. 0°03' W., bet. secs. 31 and 32.

Over level alkali flat through scattered salt weed and brush.

40.08 The original  $\frac{1}{4}$  sec. cor., a juniper post, 3 ft. long, 3 ins. diam., firmly set; no marks remaining.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old cor. stake set alongside, for  $\frac{1}{4}$  sec. cor., with brass cap marked



Deposit broken glass at the base of the post.

Continue on same course, beginning new measurement.

40.08 The original sec. cor., a decayed juniper post, rotted off at the ground; no marks remaining.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, old cor. stake set alongside, for cor. of secs. 29, 30, 31, and 32, with brass cap marked

DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 7 W.

Chains

T19S	R7W
S30	S29
S31	S32

1941

Deposit broken glass at the base of the post.

Land, level flat; surface broken by small sandy hummocks. Soil, wet alkali and sandy clay; 3rd rate. Undergrowth, salt weed and salt brush. Poor grazing.

From the cor. of secs. 28, 29, 32, and 33.

S. 89°48' W., bet. secs. 29 and 32.

Over level land, through dense salt grass and weeds.

20.10 Six strand barbed wire fence, bears N. and S.

40.09 Proportionate distance; no evidence of the original 1/4 sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground; for restored 1/4 sec. cor., with brass cap marked

S29
S32

1941

Deposit broken glass at the base of the post.

55.00 Leave salt grass and continue through salt brush and weeds.

80.18 The cor. of secs. 29, 30, 31, and 32.

Land, level; surface broken by small hummocks on portion of mile.

Soil, sandy clay and alkali clay; 3rd rate. Undergrowth, salt grass, salt brush and weeds. Fair to poor grazing.

From the cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the township, an iron post, 2 ins. diam., properly set, marked and witnessed as described in resurvey of T. 19 S., R. 8 W., of this group.

Thence

S. 89°56' E., bet. secs. 30 and 31.

Over level alkali flat, through scattered salt brush and weeds.

11.80 Low sandy rise, bears N. and SE.

39.99 Proportionate distance; no evidence of the original 1/4 sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored 1/4 sec. cor., with brass cap marked

Chains

S30  
 $\frac{1}{4}$  ———  
 S31

1941

Deposit broken glass at the base of the post.

20.13 The cor. of secs. 29, 30, 31, and 32.

Land, level alkali flat; surface broken by few hummocks and low sandy rises.  
 Soil, alkali clay and sandy clay; 3rd to 4th rates.  
 Undergrowth, scattered salt brush and weeds.  
 Poor grazing.

N. 0°03' W., bet. secs. 29 and 30.

Over level alkali flat through scattered salt brush.

40.34 The original  $\frac{1}{4}$  sec. cor., a juniper stake, greatly decayed and rotted off at the ground; no marks remaining.

At point for cor.

Set an iron post,  $\frac{3}{4}$  ft. long, 1 in. diam., 27 ins. in the ground, old cor. stake set alongside, for  $\frac{1}{4}$  sec. cor., with brass cap marked

S30 | S29  
 1941

Deposit broken glass at the base of the post.

Continue on same course, beginning new measurement.

40.12 The original sec. cor., a decayed juniper post, 4 ft. long 3 ins. diam., rotted off at the ground; no marks remaining

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, old cor. stake set alongside, for cor. of secs. 19, 20, 29, and 30, with brass cap marked

T19S | R7W  
 S19 | S20  
 S30 | S29  
 1941

Deposit broken glass at the base of the post.

Land, level alkali flat.  
 Soil, clay and sandy clay; 4th rate.  
 Undergrowth, scattered salt brush and weeds.  
 Poor grazing.

From the cor. of secs. 20, 21, 28, and 29.

S. 89°40' W., bet. secs. 20 and 29.

DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 7 W.

Chains

Over level land, through salt brush.

17.00 Enter salt grass, bears N. and S.

30.00 Leave salt grass and continue through salt brush and weeds.

40.00 The original  $\frac{1}{4}$  sec. cor., a juniper post broken off at the ground, 2 ft. long, 3 in. diam, marked  $\frac{1}{4}$  on one face.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old cor. post set alongside, for  $\frac{1}{4}$  sec. cor., with brass cap marked

S20  
 S29

1941

Deposit broken glass at the base of the post.

Thence, S. 89°53' W.

39.98 The cor. of secs. 19, 20, 29, and 30.

Land, level clay flat.  
 Soil, alkali clay and sandy clay; 3rd rate.  
 Undergrowth, salt brush, weeds and grass.  
 Poor grazing.


West, bet. secs. 19 and 30.

Over level land, through scattered salt brush.

34.55 The original meander cor., a juniper post, 3 ft. long, 3 ins. diam., lying on the ground; no marks remaining.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old cor. post set alongside, for meander cor. of fractional secs. 19 and 30, with brass cap marked



1941

Deposit broken glass at the base of the post.

Note: The original meander cor. was set on the E. bank of a lake which has since dried up; no evidence of any shore line at present time.

Land, level.  
 Soil, alkali clay; 4th rate.  
 Undergrowth, scattered salt brush and weeds.  
 Poor grazing

From the cor. of secs. 19, 20, 29, and 30.

DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S. R. 7 W.


Chains

N. 0°07' E., bet. secs. 19 and 20.  
 Over clay flat, through scattered salt weeds.

40.20 The original  $\frac{1}{4}$  sec. cor., a juniper stake, 3 ft. long, 3 ins. diam., firmly set; no marks remaining.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old stake cor. set alongside, for  $\frac{1}{4}$  sec. cor., with brass cap marked




Deposit broken glass at the base of the post.

Continue on same course, beginning new measurement.

30.15 The original meander cor. a juniper stake, 3 ft. long, 4 ins. diam., firmly set, no marks remaining.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old stake cor. set alongside, for meander cor. fractional secs. 19 and 20, with brass cap marked



Deposit broken glass at the base of the post.

Note: No definite indication of lake shore found.

Land, level.  
 Soil, alkali clay; 4th rate.  
 Undergrowth, scattered salt brush.  
 Poor grazing.

From the cor. of secs. 16, 17, 20, and 21.


West (record course) bet. secs. 17 and 20.

Over level land, through salt weed.

7.00 Enter salt grass, bears N. and S.

40.00 Record distance; no evidence of the original  $\frac{1}{4}$  sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked



1941


Deposit broken glass at the base of the post.

DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 7 W.

Chains

45.00 Leave salt grass, continue through salt weed.

70.00 Record distance; no evidence of the original meander cor.  
 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored meander cor. of fractional secs. 17 and 20, with brass cap marked



1941

Deposit broken glass at the base of the post.

Land, level flat.  
 Soil, alkali clay and sandy clay; 3rd rate.  
 Undergrowth, salt brush, weeds and grass.  
 Poor grazing.

From the cor. of secs. 8, 9, 16, and 17.


S. 89°32' W., bet. secs. 8 and 17.

Over level flat through scattered salt brush.

13.60 The original meander cor., a juniper post, 3½ ft. long, 3 ins. diam., rotted of at ground; faint traces of scribe marks found on post.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old cor. post set alongside, for meander cor. of fractional secs. 8 and 17, with brass cap marked



1941

Deposit broken glass at the base of the post.

Land, level.  
 Soil, alkali clay; 4th rate.  
 Undergrowth, salt brush.  
 Poor grazing.

From the cor. of secs. 4, 5, 8, and 9.

West, bet. secs. 5 and 8.

Over level flat, through scattered salt brush.

38.40 Record distance; no evidence of the original meander cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored meander cor. of fractional secs. 5 and 8, with brass cap marked

Chains

	T19S
M	S5
C	S8
	R7W

1941

Deposit broken glass at the base of the post.

Land, level flat.  
Soil, clay; 3rd rate.  
Undergrowth, salt brush.  
Poor grazing.

From the cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the township.

S. 0°16' E., bet. secs. 5 and 6.

Over nearly level land, through scattered greasewood.

5.00 Leave greasewood; continue through salt brush and weeds.

40.05 The original  $\frac{1}{4}$  sec. cor., a juniper stake, 3 ft. long, 3 ins. diam., firmly set; no marks remaining.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old cor. stake set alongside, for  $\frac{1}{4}$  sec. cor., with brass cap marked

	$\frac{1}{4}$
S6	S5
	1941

Deposit broken glass at the base of the post.

Thence, S. 0°09' E.

17.10 Top of low sandy rise, bears E. and W.

35.50 The original meander cor., a juniper stake, 1 $\frac{1}{2}$  ft. long, 3 ins. diam., firmly set; no marks remaining.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old stake cor. set alongside, for meander cor. of fractional secs. 5 and 6, with brass cap marked

T19S	R7W
S6	S5
MC	
1941	

Deposit broken glass at the base of the post.

Note: This meander cor. was reported as being set on the bank of a salt lake. This lake has since dried up and there is no definite indication of a shore line at present date.

Land, level flat; surface broken by few sandy rises.

## DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 7 W.

Chains

Soil, sandy clay; 3rd rate.  
Undergrowth, scattered salt brush and weeds; a few greasewood on N. end of mile.  
Poor grazing.

## DEPENDENT RESURVEY OF MEANDERS, T. 19 S., R. 7 W.

Reestablishment of surveys executed by  
Julien Bausman, Deputy Surveyor, in 1871.

Note: The lake as shown upon the original plat of this township, dated February 26, 1872, of which the following meanders formed a portion of the W. Tp. bdy., has dried up, and there is no definite shore line. The greater portion of the area which at one time formed the lake, is now covered with a short undergrowth of shadscale, greasewood, salt grass, salt brush and weeds.

From the original remonumented meander cor. of fractional secs. 1 and 6, on the W. bdy. of the township, an iron post, 1 in. diam., properly set, marked and witnessed as described in the resurvey of T. 18 S., R. 8 W., Group No. 207, Utah.

adjusted

Thence with meanders in sec. 6, along N. side of dry lake.

S.  $85^{\circ}14'$  E., 80.82 chs. The original meander cor. of fractional secs. 5 and 6.

Land, level alkali flat.

Soil, clay and sandy clay; 4th rate.

Undergrowth, very scattered salt brush and weeds on portions of line.

Thence in sec. 5.

N.  $87^{\circ}07'$  E., 35.35 chs.

S.  $41^{\circ}09'$  E., 10.45 chs. The restored meander cor. of fractional secs. 5 and 6.

Land, level flat; no definite shore line.

Soil, clay or sandy clay; 4th rate.

Undergrowth, very scattered salt weed or brush.

Thence in sec. 8.

S.  $38^{\circ}57'$  E., 26.32 chs.

S.  $20^{\circ}12'$  E., 43.52 chs. At 24.90 chs., dim road, bears about E. and W.

At 34.50 chs., dim road, bears about E. and W.

S.  $18^{\circ}24'$  W., 20.40 chs. The original meander cor. of fractional secs. 8 and 17.

Land, level flat; no definite shore line.

Soil, alkali sandy clay; 4th rate.

Undergrowth, very scattered salt brush and weeds.

Thence in sec. 17.

S.  $16^{\circ}59'$  W., 42.12 chs.

S.  $47^{\circ}20'$  W., 59.18 chs. The restored meander cor. of fractional secs. 17 and 20.

## DEPENDENT RESURVEY OF MEANDERS, T. 19 S., R. 7 W.

Land, level flat; no defined shore line.  
Soil, alkali clay; 4th rate.  
Undergrowth, very scattered salt brush and weeds.

Thence in sec. 20.

S.  $41^{\circ}33'$  W., 14.01 chs. The original meander cor. of fractional secs. 19 and 20.

Land, level; no defined shore line.  
Soil, clay; 4th rate.  
Undergrowth, short salt weeds.

Thence in sec. 19.

S.  $45^{\circ}51'$  W., 43.16 chs.  
S.  $5^{\circ}17'$  W., 40.47 chs. The original meander cor. of fractional secs. 19 and 30.

Land, level flat; no defined shore line.  
Soil, clay; 4th rate.  
Undergrowth, scattered salt weeds.

Thence in sec. 30.

S.  $30^{\circ}10'$  W., 62.00 chs.  
S.  $53^{\circ}38'$  W., 17.94 chs. The original remonumented meander cor. of fractional secs. 25 and 6th W. bdy. of township, an iron post, 1 in. diam., described in the resurvey of T. 19 S., R. 8 W. of this group.

Land, level flat; no defined shore line.  
Soil, sandy clay; 4th rate.  
Undergrowth, very scattered salt brush and weeds about 6 ins. high.

## GENERAL DESCRIPTION, T. 19 S., R. 7 W.

The land within the boundaries of T. 19 S., R. 7 W., Salt Lake Meridian, Utah, consists of nearly level desert land, which is at an elevation of approximately 4600 feet above sea level. The northeast and northwest portions of the township have very little vegetation, and consist of nearly level clay and alkali flats. The central portion is covered with a dense short growth of salt grass, while the remainder of the township is covered with a scatter to a medium dense growth of salt weeds, greasewood and shadscale. A few scattered scrub juniper trees in the south east portion of section 36, is the only timber found in the township. The extreme east portion of the township consists of a low rolling volcanic bench, and is about 50 feet in elevation above the remainder of the township. This bench is covered with a black volcanic sand, which came from volcanic craters to the southeast of the township. In nearly all places, the township has a general northerly drainage, and considerable water was found in the central south portion. Three large ponds or reservoirs, are located in section 34, the west half of section 27, and the east half of section 28. The water in these ponds or reservoirs, comes from large springs known as "Clear

## GENERAL DESCRIPTION OF T. 19 S., R. 7 W.

"Lake" which are located in the north portion of T. 20 S., R. 7 W. From these ponds or reservoirs, the water flows in a northerly direction through the central portion of the township. The water flows through wide shallow sloughs and swales, irrigating a large area, which is covered with a very dense growth of salt grass, which is about the only vegetation that can be used for the grazing of stock.

The soil on the volcanic bench in the extreme east portion of the township, consists of a shallow loose sand about 12 to 18 inches deep, which is underlain with solid lava. The soil throughout the remainder of the township, consists of a deep light colored heavy clay, the surface of which is covered with alkali. The soil may be classified as third and fourth rates, and contains but very little plant life.

The records of the original survey of this township, which was executed in 1871, reports sections 7 and 18, and portions of sections 5, 6, 8, 17, 20, 19, and 30, as being a salt lake, and the shore line of this lake at that time was meandered. At the time of the resurvey, no indications of this shore line could be found, and the area originally reported as being a lake, is now dry, and in some places covered with vegetation, consisting of salt grass, and salt weed.

The main line of the Union Pacific railroad, from Salt Lake City to Los Angeles, two telegraph lines, and a graded and graveled road from Deseret, Utah to Clear Lake and Black Rock, Utah, bears in a northeasterly and southwesterly direction through the  $\frac{1}{2}$  NW $\frac{1}{4}$  section 6. The American Telephone and Telegraph transcontinental 14 wire line, bears N. 0°18' E., and S. 0°18' W., through the central portions of sections 4, 9, 16, 21, 28, and 33. At a point, West 3.10 chs. distant from the section corner of sections 4 and 33, on the south boundary of the township, is an angle point in this transcontinental line, and from this point, the line bears N. 0°18' E., and S. 34°17' W. Beacon No. 50, on air route between Salt Lake City and Los Angeles, is located in the SW $\frac{1}{4}$  SE $\frac{1}{4}$  section 9. Approximately 10 miles of fencing is located in the central portion of the township. The ponds or reservoirs located in the central south portion, are used for the storage of water for the rearing of fish and wild fowl.

No settlers were living on the township at the time of the survey, and the area covered with salt grass, was being used for a grazing range for stock.

No portions of the township are suitable for farming, due to the great quantities of alkali found in the soil.

During the dry seasons of the year, nearly all portions of the township can be reached by automobile.

The nearest settlement to the township, is Deseret, Utah, located about 6 miles to the north.

No indications of oil, oil shale, coal, or mineral were found.

The mean magnetic declination was found to be 16°30' E.

Blank

Page



Elliot Bird, Associate Cadastral Engineer,  
 We, Andrew Nelson, Assistant Cadastral Engineer  
 xi, ..... , HEREBY CERTIFY upon honor that,

pursuance of special instructions bearing date of the 7th day of April 1939  
 received from the district cadastral engineer for Utah ..... , with assignmen  
 instructions dated September 27, 1941<sup>We</sup> have surveyed made a dependent resurvey o  
 north boundary T. 20 S., R. 7 W., the west boundary T. 19 S., R. 6 W.  
 north boundary, the subdivisional, and meander lines, of T. 19 S., R.

of the Salt Lake Meridian, in the State of Utah ..... , which  
 represented in the foregoing field notes as having been executed by us and under our direction<sup>s</sup>, and that s  
 survey has been made in strict conformity with said instructions, the Manual of Instructions for the Sur  
 of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

March 7, 1942  
 Salt Lake City, Utah.

*Elliot Bird*  
 Associate Cadastral Engineer  
*Andrew Nelson*  
 Assistant Cadastral Engineer

## CERTIFICATE OF APPROVAL

OFFICE OF SUPERVISOR OF SURVEYS,

Denver, Colo., October 31, 1942

The foregoing field notes of the ~~survey of~~ dependent resurvey north boundary,  
 T. 20 S., R. 7 W., the west boundary T. 19 S., R. 6 W., and the north  
 boundary, the subdivisional, and meander lines, of T. 19 S., R. 7 W.  
 Salt Lake Meridian, Utah

executed by Elliot Bird, Associate Cadastral Engineer,  
 Andrew Nelson, Assistant Cadastral Engineer,  
 under special instructions dated April 7, 1939 ..... , supplementa  
 instructions dated September 27, 1941 ..... , having been critically examined, a  
 the necessary corrections made prior to their certification by the engineer, the said field notes, and the surv  
 therein described, are hereby approved.

*[Signature]*  
 Supervisor of Surveys.

~~CERTIFICATE OF TRANSCRIPT~~

I certify that the foregoing transcript of the field notes of the above described surveys in .....  
 is a true copy of the original field notes on file in the public survey office.

*[Signature]*  
 Supervisor of Surveys.

BOOK "A"  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GENERAL LAND OFFICE

# FIELD NOTES

OF THE DEPENDENT RESURVEY

WEST BOUNDARY OF T. 19 S., R. 7 W., WEST BOUNDARY OR SECOND  
GUIDE MERIDIAN WEST, SOUTH BOUNDARY, AND SUBDIVISIONAL LINES  
AND MEANDERS OF T. 19 S., R. 8 W.

Of the Salt Lake Meridian,

the State of Utah

EXECUTED BY

ANDREW NELSON, SURVEYOR

Under special instructions dated April 7, 1939, which provided  
for the surveys included under Group No. 299, bearing the approval of the  
Commissioner of the General Land Office under date of May 25, 1939  
and assignment instructions dated May 9, 1940.

Survey commenced May 17, 1940.

Survey completed June 5, 1940.



## DEPENDENT RESURVEY OF, T. 19 S., R. 8 W.

The official survey of T. 19 S., R. 8 W., Salt Lake Meridian, Utah, is shown on plat approved February 26, 1872. The following field notes are those of a dependent resurvey, or reestablishment of the east, west, and south boundaries, the subdivisional lines, and a portion of the meanders of a salt lake.

The west boundary or Second Guide Meridian West, was surveyed by Julien Bausman in 1871, and resurveyed by George O. Chaney, in 1892. The north boundary was reestablished under the direction, of the General Land Office, in 1938, in the connection with the resurvey of T. 13 S., R. 8 W., Group 207, Utah.

The resurvey is a complete restoration of the original boundaries and subdivisional lines in their true original positions as adjusted to the identified evidence.

Before reconstructing or restoring the corners, the lines of the original survey were retraced, and search was made for evidence of the original corner monuments, their accessories, and other calls of the field notes. When duly identified or restored, the corner positions were remonumented and new accessories taken.

The rules of proportionate measurement were applied in order to ascertain the position of each lost corner, after completing the necessary retracements to connect with the identified corner locations; but not until exhausting every reasonable possibility of finding direct evidence for control of each particular corner.

The retracement data were submitted for office examination and verification. In order to simplify the record, the true line notes only are supplied here, which refer to the completed resurvey.

The resurvey of T. 19 S., R. 8 W., was commenced May 17, 1940, and executed by Andrew Nelson, Surveyor, with Buff and Buff transit No. 16726. The instrument is the property of the General Land Office, and is equipped with a Smith solar attachment and full vertical circle. The horizontal limb has two double verniers placed opposite to each other and reading to single minutes of arc, which is also the least count of the verniers of the latitude and declination arcs and vertical circle. The instrument was approved for use on this survey conditional upon satisfactory field tests, by the district cadastral engineer, for Utah, in assignment instructions dated May 9, 1940.

The solar attachment was not used on this survey, and all controlling meridians were established by hour angle observations made upon Polaris during the progress of the work. The bearings of the lines were deflected from these true meridians by the repetition of angles, and carried forward by transit lines, taking the mean of direct and reversed sights.

The measurements were made with a Lallie steel tape, 5 chains in length which is graduated every link for the first 100 links and thereafter at intervals of 10 links. The tape was tested, comparison being made with a Lufkin standard steel tape 1 chain in length and found correct. The measurements were made on the slope, the vertical angle determined with clinometers in good adjustment, and the slope measurements properly reduced to true horizontal distances which appear in this record.



DEP. RESURVEY 2ND GUIDE MERIDIAN W., T. 19 S., BET. Rs. 8 AND 9 W.

Chains

At the cor. point:

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with the original cor. monument deposited at the base of the post, for  $\frac{1}{4}$  sec. cor. sec. 31, with brass cap marked



1940


raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor. Also deposit the glass of a broken bottle at the base of the post.

Continue on same line, beginning new measurement.

- 9.70 Enter medium dense undergrowth of greasewood, bears E. and W.
- 17.20 Small depression, drains N. 75° W.
- 20.30 Old road, bears N. 70° W. and S. 70° E.
- 24.50 The old channel of Beaver River, 1.20 chs. wide, 10 ft. deep, drains N. 60° W.
- 39.66 The cor. of secs. 25 and 36, a quartzite, 10 x 8 x 5 ins., firmly set, marked 5 notches on SW. edge and 3 notches on NW. edge. Cor. has no accessories.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with the original cor. monument deposited at the base of the post, for cor. secs. 25 and 36, with brass cap marked.




1940

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

- 40.29 The cor. of secs. 30 and 31, a cedar post, 3 ins. diam., 2 1/2 ft. long, upon which I find dim scribed marks. Cor. has no accessories.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with the original cor. monument deposited alongside, for cor. secs. 30 and 31, with brass cap marked



1940

raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.

Chains	
	<p>Land, nearly level desert. Soil, deep clay, 3rd rate. No timber. Undergrowth, .shadscale and greasewood. Fair grazing land.</p>
	<p>N. 0°19' W., along the W. bdy. sec. 30.</p>
	<p>Over nearly level desert land, through scattered short undergrowth.</p>
39.19	<p>The <math>\frac{1}{4}</math> sec. cor. sec. 25, a quartzite, 14 x 12 x 4 ins., firmly set, marked <math>\frac{1}{4}</math> on W. face. Cor. has no accessories</p>
	<p>At the cor. point:</p>
	<p>Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with the original cor. monument deposited at the base of the post, for <math>\frac{1}{4}</math> sec. cor. sec. 25, with brass cap marked</p>
	<p style="text-align: center;"><math>\frac{1}{4}</math> S25   1940</p>
	<p>small mound of stone W. of cor. — <span style="float: right;">raise a</span></p>
40.15	<p>The <math>\frac{1}{4}</math> sec. cor. sec. 30, a cedar post, 3 ins. square, 2<math>\frac{1}{2}</math> ft. long, firmly set. Post is squared on two sides and has no accessories or visible marks.</p>
	<p>At the cor. point:</p>
	<p>Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with the original cor. monument deposited alongside for <math>\frac{1}{4}</math> sec. cor. sec. 30, with brass cap marked</p>
	<p style="text-align: center;"><math>\frac{1}{4}</math> S30 1940</p>
	<p>deposit the glass of a broken bottle and a few rock around the post.</p>
	<p>Thence, N. 0°23' W.</p>
5.00	<p>Wash, 35 lks. wide, 2 ft. deep, drains NW.</p>
34.80	<p>Unimproved road, bears N. 57° W., and S. 57° E.</p>
39.00	<p>Wash, 35 lks. wide, 2 ft. deep, drains N. 75° E.</p>
39.09	<p>The cor. of secs. 24 and 25, a quartzite, 14 x 11 x 6 ins. firmly set, marked 4 notches on N. edge and 6 notches on W., and 2 notches on S. edge. Cor. has no accessories.</p>
	<p>At the cor. point:</p>
	<p>Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with the original cor. monument deposited at the base of the post, for cor. secs. 24 and 25, with brass cap marked</p>

DEP. RESURVEY 2ND GUIDE MERIDIAN W., T. 19 S., BET. Rs. 8 AND 9 W.

Chains

T19S	S30
S24	
S25	
R9W	

1940

No accessories available.

40.38 The cor. of secs. 19 and 30, a quartzite, 20 x 8 x 8 ins., firmly set, marked 4 notches on N. edge, 6 notches on E. edge, and 2 notches on S. edge. Cor. has no accessories.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with the original cor. monument deposited at the base of the post, for cor. secs. 19 and 30. with brass cap marked

S24	T19S
	S19
	S30
	R9W

1940

No accessories available.

Land, nearly level desert.

Soil, deep clay; 3rd rate.

Undergrowth, shadscale and greasewood.

No timber.

Fair grazing land.

N. 0°22' W., along the W. bdy. of sec. 19.

Over nearly level desert land, through scattered short undergrowth.

25.00 Wash, 35 lks. wide, 2 ft. deep, drains NE.

38.76 The  $\frac{1}{4}$  sec. cor. sec. 24, a quartzite, 16 x 15 x 5 ins., firmly set, marked  $\frac{1}{4}$  on W. face. Cor. has no accessories.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with the original cor. monument deposited at the base of the post, for  $\frac{1}{4}$  sec. cor. sec. 24, with brass cap marked

$\frac{1}{4}$ S24
1940

No accessories available.

40.35 The stump of a juniper post, which I take for the  $\frac{1}{4}$  sec. cor. sec. 19. Cor. has no accessories.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with the original cor. monument deposited at the base of the post, for  $\frac{1}{4}$  sec. cor. sec. 19, with brass cap marked

## DEP. RESURVEY 2ND GUIDE MERIDIAN W., T. 19 S., BET. R. 8 AND 9

Chains

1	S19
---	-----

1940

deposit th

glass of a broken bottle and a few stone around the post

Thence, N. 0°18' W.

0.80 An old unused road, bears N. 60° E. and SW.

34.00 Old road, bears N. 80° E. and S. 20° W.

33.42 The cor. of secs. 13 and 24, a quartzite, 18 x 8 x 4 ins firmly set, marked 3 notches on N. and S. edges, and 6 notches on W. edge. Cor. has no accessories.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in t ground, with the original cor. monument deposited at the base of the post, for cor. secs. 13 and 24, with brass c marked

T19S	S19
S13	
S24	
RGW	

1940

deposit th

glass of a broken bottle at the base of the post.

40.28 The cor. of secs. 18 and 19, a juniper post, 3 ft. long, 4 ins. diam., loosely set, upon which I find dim scribe marks. Cor. has no accessories.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in t ground, with the original cor. monument deposited alongs for cor. secs. 18 and 19, with brass cap marked

S13	T19S
	S18
	S19
	R8W

1940

deposit th

glass of a broken bottle at the base of the post.

Land, nearly level desert.

Soil, deep clay.

No timber.

Undergrowth, shadscale and greasewood.

Fair grazing land.

N. 0°22' W., along the W. bdy. sec. 18.

Over gently rolling land, through very scattered short undergrowth.


RESERVE 2ND GUIDE MERIDIAN W., T. 19 S., R. 8 AND 9 W.

Chains

38.05 The 1/4 sec. cor. sec. 13, a quartzite, 14 x 8 x 6 ins., firmly set, marks worn off the cor. stone. Cor. has no accessories.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with the original cor. monument deposited at the base of the post, for 1/4 sec. cor. sec. 13, with brass cap marked




deposit the glass of a broken bottle at the base of the post.

40.21 The 1/4 sec. cor. sec. 18, a juniper post, 3 ft. long, 2 ins. diam., loosely set, upon which I find dir. scribble marks. Cor. has no accessories.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with the original cor. monument deposited alongside the post, for 1/4 sec. cor. sec. 18, with brass cap marked




deposit the glass of a broken bottle at the base of the post.

Thence, N. 0°13' W.

37.99 The cor. of secs. 12 and 13, a quartzite, 18 x 8 x 6 ins., firmly set, marked 2 notches on the N. and E. edges. Cor. has no accessories.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with the original cor. monument deposited at the base of the post, for cor. secs. 12 and 13, with brass cap marked



1940

deposit the glass of a broken bottle at the base of the post.

40.35 The cor. of secs. 7 and 18, an iron post, 2 ins. diam., set, marked, and witnessed, as described in the official record of the survey of T. 18 S., R. 8 W., Group 207, tan.

Land, gently rolling desert.  
Soil, clay and sand; 3rd rate.  
No timber.  
Undergrowth, shadscale and grass.  
Fair grazing land.

Chains


angle 10

N. 0°04' W., along the W. bdy. sec. 7. Over gently rolling desert land, through very scattered short undergrowth.

21.17 The meander cor. of fractional secs. 7 and 12, on the S. shore of a salt lake, as set by George O. Chaney in his resurvey of this boundary in 1992, and which point is the end of his survey. Cor. is a quartzite, 18 x 8 x 5 ins., firmly set, marked MC on N. face. Cor. has no accessories

At the cor. point:

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with the original cor. monument deposited at the base of the post, for meander cor. fractional secs. 12, with brass cap marked




deposit the glass of a broken bottle at the base of the post.

Continue on same line with continuous measurement.

27.90 Leave undergrowth and enter dry lake bed, bears W. and S. 90° E.

40.00 Record distance; find no evidence of the original 1/4 sec. cor. of secs. 7 and 12.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for 1/4 sec. cor. sec. 7, with brass cap marked




deposit the glass of a broken bottle at the base of the post.

Continue across dry bed of lake.

80.00 Record distance; find no trace of the original cor. secs. 1, 6, 7, and 12.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for cor. of secs. 6 and 7, with brass cap marked



deposit the glass of a broken bottle at the base of the post.

Land, level dry bed of lake and rolling desert. Soil, heavy clay; 4th rate. No timber.

Undergrowth, shadscale and grass on portion of mile. Fair grazing land on S. portion of mile.

## DEPT. RESURVEY 2ND. GUIDE MERIDIAN W., T. 19 S., BET. Rs. 8 AND 9 W.

Chains

- N.  $0^{\circ}04'$  W., along the W. bdy. of sec. 6.  
Over level dry bottom of a salt lake bed:
- 2.40 Leave level bottom of dry lake bed and enter rolling desert land, bears E. and W.
- 9.60 Top of low rim, 12 ft. high, bears N.  $35^{\circ}$  E. and S.  $35^{\circ}$  W.
- 18.50 Unimproved road, bears NE. and SW., at base of descent from rim.
- 23.70 Old dry drainage channel, 135 lks. wide, 5 ft. deep, drains SW.
- 33.20 Low rim, 6 ft. high, bears N.  $70^{\circ}$  E. and S.  $70^{\circ}$  W.; enter salt weed and broken bottom of dry lake bed, bears with rim.
- 40.00 Record distance; find no trace of the original  $\frac{1}{4}$  sec. cor. secs. 1 and 6.
- Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for  $\frac{1}{4}$  sec. cor. sec. 6, with brass cap marked

S6

1940

deposit the glass of a broken bottle at the base of the post.

- 40.00 The reestablished cor. of Ts. 18 and 19 S., R. 8 W., an iron post, 3 ins. diam., set, marked, and witnessed, as described in the official record of the resurvey of T. 18 S., R. 8 W., Group 207, Utah.

From this cor., the closing cor. of Ts. 18 and 19 S., R. 9 W., bears N.  $10^{\circ}12'$  E., 4.43 chs. dist.

Land, level bottom of dry lake bed.

Soil, deep heavy clay; 3rd rate.

No timber.

Undergrowth, salt weed and badscale on portions of mile.

Poor grazing land.

## DEPARTMENT RESURVEY SOUTH UTAH, T. 19 S., R. 8 W.

Reestablishment of surveys executed by  
Julien Hausman, U.S. Deputy Surveyor,  
in 1871.

From the cor. of Ts. 19 and 20 S., Rs. 8 and 9 W.

S.  $89^{\circ}40'$  E., bet. secs. 6 and 31.

Over nearly level desert land, through short dense undergrowth.

- 39.77 Proportionate distance; find no trace of the  $\frac{1}{4}$  sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked

S31

S6

1940

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

## DEPENDENT RESURVEY SOUTH BOUNDARY, T. 19 S., R. 8 E.

Chains  
 78.40 Unimproved road, bears NE. and SW.; junction of road from the E., bears SW., about 2,50 chs. dist.  
 80.00 Irrigation ditch, 8 lks. wide, 1½ ft. deep, drains NW.  
 80.32 Proportionate distance; find no trace of the cor. secs. 5, 6, 31, and 32.  
 Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in ground, for cor. secs. 5, 6, 31, and 32, with brass cap marked

T19S	R8W
S31	S32
S6	S5
T20S	

1940

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, nearly level desert.  
 Soil, deep heavy clay; 3rd rate.  
 No timber.  
 Undergrowth, shadscale and greasewood.  
 Fair grazing land.

S. 89°40' E., bet. secs. 5 and 32.

Over nearly level desert land; through dense short undergrowth.

40.55 The ¼ sec. cor. secs. 5 and 32, a juniper post, 4 ins. diam., extending 2 ft. above ground, firmly set, upon which I find dim scribe marks. Cor. has no accessories

At the cor. point:

Set an iron post, 3 ft. long; 1 in. diam., 30 ins. in ground, with the original cor. monument deposited at the base of the post, for ¼ sec. cor., with brass cap marked

¼	S32
—	—
¼	S5

1940

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

Thence, S. 89°45' E.

29.00 Small rise, bears N. and S.

40.39 The cor. of secs. 4, 5, 32, and 33, the stump of a juniper post, set in fence line bearing N. 38° W., S., and E.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in ground, with the original cor. monument deposited at the base of the post, for cor. secs. 4, 5, 32, and 33, with brass cap marked

DEPENDENT RESURVEY SOUTH BOUNDARY, T. 19 S., R. 8 W.

Chains

T19S	R8W
S32	S33
S5	S4
T20S	

1940

mound of stone, 3 ft. base, 2 ft. high, W. of cor. raise a

Land, nearly level desert.  
Soil, deep clay and alkali; 3rd rate.  
No timber.  
Undergrowth, shadscale, and greasewood.  
Fair grazing land.

S. 89°42' E., bet. secs. 4 and 33.

Over nearly level desert land, through medium dense short undergrowth.

Line follows along the N. side of fence bearing easterly.

0.40 Irrigation ditch, 5 lks. wide, drains N. 20° E.

-17.00 Small rise, 5 ft. high, bears N. 10° W., about 10.00 chs. dist to end, and S. 10° E., about 6.00 chs. dist. to end.

40.24 Proportionate distance; find no trace of the 4 sec. cor. secs. 4 and 33.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for 4 sec. cor., with brass cap marked

S33

S4

1940

mound of stone, 3 ft. base, 2 ft. high, N. of cor. raise a

From this cor., the intersection of a barbed wire fence from the W., with fence bearing N. and S., bears S. 0°05' W., 12 lks. dist.

40.55 Irrigation ditch, 15 lks. wide, 2 ft. deep, drains N.

60.00 Irrigation ditch, 8 lks. wide, 1 ft. deep, drains N.

60.50 Unimproved road, bears N. and S.

80.48 The cor. of secs. 3, 4, 33, and 34, a quartzite, 15 x 10 x 6 ins., firmly set, marked 3 notches on E. and W. edges. Parts of a decayed juniper post found at the base of the stone. Cor. has no accessories.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with the original cor. monument deposited at the base of the post, for cor. secs. 3, 4, 33, and 34, with brass cap marked

DEPENDENT RESURVEY SOUTH BOUNDARY, T. 19 S., R. 8 W.

Chains

T19S	R8W
S33	S34
S4	S3
T20S	

acres

1940

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, nearly level desert.

Soil, deep heavy clay; 3rd rate.

No timber.

Undergrowth, shadscale, greasewood, and salt weed.

Fair grazing land.

S. 89°50' E., bet. secs. 3 and 34.

Over nearly level desert land, through medium dense short undergrowth.

16.30 Graded and graveled road, bears N. 18°30' E. to Desert, Utah, and S. 18°30' W., to Blackrock, Utah.

17.50 Irrigation ditch, 10 lks. wide, 1 ft. deep, drains N.

17.60 Fence, bears N. 21° E. and S. 21° W.

17.70 Telegraph line, 13 wires, bears N. 21° E. and S. 21° W.

19.20 Center of track of the Union Pacific Railroad, on curve, bears N. 20° E. and S. 20° W.

20.10 Dm road, bears N. 20° E. and S. 20° W.

20.70 Telegraph line, 9 wires, bears N. 20° E. and S. 20° W.

21.10 Fence, bears N. 20° E. and S. 20° W.

22.30 Unimproved road, bears N. and S.

30.40 Unimproved road, bears N. and S.

40.29 The  $\frac{1}{4}$  sec. cor. secs. 3 and 34, a juniper post, 3 ins. square, extending 2 ft. above ground, firmly set, upon which I find dir scribe marks. Cor. has no accessories.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with the original cor. monument deposited at the base of the post, for  $\frac{1}{4}$  sec. cor., with brass cap marked

S34

S3

1940

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

Thence, S. 89°45' E.

27.90 Dm road, bears N. 30° W. and S. 30° E.

40.31 The cor. of secs. 2, 3, 34, and 35, a juniper post, 3 ft.

DEPENDENT RESURVEY SOUTH BOUNDARY, T. 19 S., R. 8 W.

Chains

long, 3 ins. square, firmly set, upon which I find dim scribe marks. Cor. has no accessories.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with the original cor. monument deposited at the base of the post, for cor. secs. 2, 3, 34, and 35, with brass cap marked

T19S	R8W.
S34	S35
S3	S2
T20S	
1940	

mound of stone, 3 ft. base, 2 ft. high, W. of cor. raise a

Land, nearly level desert.  
Soil, deep heavy clay; 3rd rate.  
No timber.  
Undergrowth, shadscale, greasewood, and salt weed.  
Fair grazing land.

S. 89°45' E., bet. secs. 2 and 35.

Over nearly level desert land, through medium dense short undergrowth.

0.60 Irrigation ditch, 15 lbs. wide, 2 ft. deep, drains N.

29.90 Graded and graveled road, bears S. 61°30' E. to Fillmore, Utah, and N. 61°30' W. to Clear Lake, Utah.

40.28 Proportionate distance; find no trace of the sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for sec. cor., with brass cap marked

S35
S2
1940

mound of stone, 3 ft. base, 2 ft. high, W. of cor. raise a

80.56 The cor. of secs. 1, 2, 35, and 36, a juniper post, 3 ft. long, 3 ins. square, loosely set, marked 6 notches on N. and S. edges, 1 notch on E. and 5 notches on W. edges. Post has dim scribe marks on each face, and has no accessories.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with the original cor. monument deposited at the base of the post, for cor. secs. 1, 2, 35, and 36, with brass cap marked

T19S	R8W
S35	S36
S2	S1
T20S	
1940	

DEPENDENT RESURVEY SOUTH BOUNDARY, T. 19 S., R. 7 W.

Chains

Station

Raise a mound of stone, 3 ft. base, .2 ft. high, W. of cor.

Land, nearly level desert.  
 Soil, deep heavy clay; 3rd rate.  
 Undergrowth, shadscale, greasewood, and salt weed.  
 No timber.  
 Fair grazing land.

S. 89°52' E., bet. secs. 1 and 36.

Over nearly level desert land, through medium dense short undergrowth.

34.70 Old irrigation ditch, drains NW. from S. 22° E.

35.00 Begin gradual descent over E. slope, bears N. and S.

40.31 The 1/4 sec. cor., a juniper post, 2 1/2 ft. long, 3 ins. square loosely set, upon which I find dim scribe marks. Cor. has no accessories.

At the cor. point:

Set an iron post, 3 ft. long, .1 in. diam., 30 ins. in the ground, with the original cor. monument deposited at the base of the post, for 1/4 sec. cor., with brass cap marked

	S36
1/4	-----
	S1

1940

mound of stone, 3 ft. base, 2 ft. high, N. of cor. raise a

Thence, S. 89°59' E.

0.90 Begin short descent over E. slope of low bench, bears N. 20° W. and S. 20° E.

1.30 Ease of descent from bench, bears N. 20° W. and S. 20° E. thence over nearly level land.

40.29 The cor. of Ts. 19 and 20 S., Rs. 7 and 8 W., a lava, 20 x 8 x 8 ins., above ground, firmly set, marked 6 notches on all four edges. Cor. has no accessories.

At the cor. point:

Set an iron post, 3 ft. long, 3 ins. diam., 30 ins. in the ground, with the original cor. monument deposited at the base of the post, for cor. Ts. 19 and 20 S., Rs. 7 and 8 with brass cap marked

T19S	
R8W	R7W
S36	S31
S1	S6
T20S	

1940

glass of a broken bottle at the base of the post. deposit the

DEPENDENT RESURVEY SOUTH BOUNDARY, T. 19 S., R. 8 W.

Chains

Land, nearly level desert.  
Soil, deep heavy clay; 3rd rate.  
No timber.  
Undergrowth, short shadscale, greasewood, and salt weed.  
Fair grazing land.

DEPENDENT RESURVEY WEST BOUNDARY, T. 19 S., R. 7 W.

Reestablishment of surveys executed by  
Julien Bausman, U.S. Deputy Surveyor,  
in 1871.

From the cor. of Ts. 19 and 20 S., Rs. 7 and 8 W.

N. 0°11' E., bet. secs. 31 and 36.

Over nearly level land, through medium dense short undergrowth.

40.20 The  $\frac{1}{4}$  sec. cor., a juniper post, 3 ft. long, 3 ins. square, loosely set, upon which I find dim scribe marks. Cor. has no accessories.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with the original cor. monument deposited at the base of the post, for  $\frac{1}{4}$  sec. cor., with brass cap marked



deposit the


glass of a quart bottle at the base of the post.

Thence, N. 0°09' E.

40.23 The cor. of secs. 25, 30, 31, and 36, a juniper post, 2 ft. long, 3 ins. square, loosely set, upon which I find dim scribe marks. Cor. has no accessories.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with the original cor. monument deposited at the base of the post, for cor. secs. 25, 30, 31, and 36, with brass cap marked



deposit the

glass of a quart bottle at the base of the post.

Land, nearly level desert.  
Soil, deep heavy clay; 3rd rate.  
No timber.  
Undergrowth, short salt grass and salt weed.  
Poor grazing land.

DEPENDENT RESURVEY WEST BOUNDARY, T. 19 S., R. 8 W.


Chains

N. 0°02' E., bet. secs. 25 and 30.  
Over nearly level land, through medium dense short undergrowth.

16.09 The meander cor. of fractional secs. 25 and 30, on the S. side of a dry lake bed, a juniper post, 2 ft. long, 3 ins square, loosely set, upon which I find dim scribe marks. Cor. has no accessories.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with the original cor. monument deposited at the base of the post, for meander cor. fractional secs. 25 and 30, with brass cap marked



deposit the glass of a quart bottle at the base of the post.

Land, nearly level desert.  
Soil, deep heavy clay; 3rd rate.  
No timber.  
Undergrowth, short salt brush and salt weed.  
Poor grazing land.

From the cor. of Ts. 18 and 19 S., Rs. 7 and 8 W., an iron post, 3 ins. diam., set, marked, and witnessed, as described in the official record of the survey of T. 18 S., R. 8 W. Group 207, Utah.

South, bet. secs. 1 and 6.

Over rolling desert land, through scattered short undergrowth.

25.40 Graded and graveled road, bears N. 25°55' E. to Deseret, Utah, and S. 25°55' W., to Clear Lake, Utah.

26.20 Thirteen wire telegraph line, bears with road.

29.60 Center of track of the Union Pacific Railroad, bears N. 25°55' E. and S. 25°55' W.

32.90 Eight wire telegraph line, bears with railroad.

38.90 Old unimproved road, bears NE. and S. 26° W.

40.41 Proportionate distance; find no trace of the 1/4 sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for 1/4 sec. cor., with brass cap marked.



deposit the

## DEPENDENT RESURVEY EAST BOUNDARY, T. 19 S., R. 2 W.

Chains

glass of a quart bottle at the base of the post.

44.50 The old channel of the Sevier River, 1.10 chs. wide, 2 ft. deep, drains SW.

69.36 The meander cor. of fractional secs. 1 and 6, an iron post, 1 in. diam., set, marked, and witnessed, as described in the official record of the survey of T. 18 S., R. 2 W., Group 207, Utah.

Land, rolling desert.

Soil, deep heavy clay; 3rd rate.

Undergrowth, short shadscale, greasewood, salt grass and salt weed.

No timber.

Fair grazing land.

## DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 2 W.

Reestablishment of surveys executed by  
Julien Bausman, U.S. Deputy Surveyor,  
in 1871.

From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the township.

N. 0°15' W., bet. secs. 35 and 36.

Over nearly level desert land, through scattered short undergrowth.

40.33 The  $\frac{1}{4}$  sec. cor. secs. 35 and 36, a juniper post, 2 ft. long, 3 ins. square, loosely set, upon which I find dim scribe marks. Cor. has no accessories.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with the original cor. monument deposited at the base of the post, for  $\frac{1}{4}$  sec. cor., with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ | \\ S35 \quad | \quad S36 \\ | \\ 1940 \end{array}$$

round of stone, 3 ft. base, 2 ft. high, W. of cor. raise a

Thence, N. 0°14' W.

0.40 Old irrigation ditch, 20 lks. wide, 2 ft. deep, drains N. 60° W.

40.31 The cor. of secs. 25, 26, 35, and 36, a juniper post, 3 ft. long, 4 ins. square, firmly set, upon which I find dim scribe marks. Cor. has no accessories.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with the original cor. monument deposited at the base of the post, for cor. secs. 25, 26, 35, and 36, with brass cap marked

DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 8 W.

Chains

T19S	R8W
S26	S25
S35	S36

1940

mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of <sup>raise a</sup> cor.

Land, nearly level desert.  
Soil, deep heavy clay; 3rd rate.  
No timber.  
Undergrowth, short shadscale and greasewood.  
Fair grazing land.

From the cor. of secs. 25, 30, 31, and 36, on the E. bdy of the township.

N.  $89^{\circ}45'$  W., bet. secs. 25 and 36.

Over nearly level desert land, through scattered short undergrowth.

- 1.60 Leave vegetation and enter alkali flat, bears N. and S.
- 39.40 Leave alkali flat and enter vegetation, bears N. and S.
- 40.57 Proportionate distance; find no trace of the  $\frac{1}{4}$  sec. cor.  
Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in th ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked

$\frac{1}{4}$	S25
	S36

1940

broken glass and a quartzite, 12 x 8 x 8 ins., at the ba <sup>deposit</sup> of the post, marked X.

- 45.60 Base of low bench, bears N.  $25^{\circ}$  W. and S.  $25^{\circ}$  E.
- 46.10 Top of E. rim of low bench, bears N.  $25^{\circ}$  W. and S.  $25^{\circ}$  E.
- 81.13 The cor. of secs. 25, 26, 35, and 36.

Land, salt flat and rolling desert.  
Soil, deep heavy clay; 3rd rate.  
No timber.  
Undergrowth, short shadscale and greasewood on portions of mile.  
Poor grazing land.

N.  $0^{\circ}14'$  W., bet. secs. 25 and 26.

Over nearly level desert land, through scattered short undergrowth.


- 40.43 The  $\frac{1}{4}$  sec. cor.. a juniper post, 3 ft. long, 4 ins. squar firmly set, upon which I find dim scribe marks. Cor. has no accessories.

At the cor. point:

DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 8 W.

Chains

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with the original cor. monument deposited at the base of the post, for  $\frac{1}{4}$  sec. cor., with brass cap marked



mound of stone, 3 ft. base, 2 ft. high, W. of cor. raise a


Thence, N. 0°19' W.,

40.52

The cor. of secs. 23, 24, 25, and 26, a juniper post, 3 ft. long, 4 ins. square, upon which I find dim notches and scribe marks. Cor. has no accessories.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins., in the ground, with the original cor. monument deposited at the base of the post, for cor. secs. 23, 24, 25, and 26, with brass cap marked



mound of stone, 3 ft. base, 2 ft. high, W. of cor. raise a

From this cor., the top of a volcanic hill, about 50 ft. high, bears N. 50° W. The S.E. point of same, bears N. 43°15' W., and the N. point of same, bears N. 30°15' W.

Land, nearly level desert.  
Soil, deep heavy clay; 3rd rate.  
No timber.  
Undergrowth, shadscale and greasewood.  
Fair grazing land.

East, bet. secs. 24 and 25.

Over nearly level desert land, through scattered short undergrowth.

18.00

Undergrowth becomes shorter, bears N. and S.

35.50

Top of low rise, 5 ft. high, bears N. 15° W. and S. 15° E.

35.40

Enter salt flat with very scattered short undergrowth, bears N. and S.

38.00

Record course and distance; find no trace of the meander cor. fractional secs. 24 and 25, on the W. side of a dry lake bed.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for meander cor. of fractional secs. 24 and 25, with brass cap marked

DEPENDENT RESURVEY OF SUBDIVISION, E. T. GIBSON, B. M.

Chains

T19S	
S24	
S25	
R8W	

1940

deposit

broken glass and a quartzite, 10 x 8 x 5 ins., at base of post, marked X.

- Land, nearly level desert.
- Soil, deep heavy clay; 3rd rate.
- No timber.
- Undergrowth, shadscale and greasewood.
- Fair grazing land.

From the cor. of secs. 23, 24, 25, and 26.

N. 0°15' W., bet. secs. 23 and 24.

Over nearly level desert land, through scattered short undergrowth of shadscale and greasewood.

2.00 Leave greasewood undergrowth, bears NW. and easterly.

40.42 The sec. cor., a juniper post, 3 ft. long, 3 ins. square, loosely set, upon which I find dim scribe marks. Cor. has no accessories.

At the cor. point:

- Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with the original cor. monument alongside, for  $\frac{1}{4}$  sec. cor., with brass cap marked.

	$\frac{1}{4}$
S23	S24
1940	

deposit

broken glass and a volcanic stone, 8x7x5 ins., at base of post, marked X.

Thence, N. 0°17' W.

1.50 Low rise, 1.20 chs. wide, bears N. 60° W., and S. 60° E., about 3.00 chs. dist. to end.

27.60 Reenter scattered greasewood and shadscale.

40.07 The cor. of secs. 13, 14, 23, and 24, a juniper post, 3 ft. long, 4 ins. square, loosely set, upon which I find dim scribe marks. Cor. has no accessories.

At the cor. point:

- Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with the original cor. monument alongside, for cor. secs. 13, 14, 23, and 24, with brass cap marked.

T19S	R8W
S14	S13
S23	S24

1940

DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 8 W.

Chains

Raise a small mound of stone, W. of cor.

From this cor., the top of SE. point of volcanic hill, bears S. 26° W. The N. point of same bears S. 37° 30' W.

Land, nearly level desert.

Soil, sandy clay and heavy clay; 3rd rate.

No timber.

Undergrowth, shadscale and greasewood.

Fair to poor grazing land.

East, bet. secs. 13 and 24.

Over nearly level alkali flat, through scattered undergrowth, of greasewood and shadscale.

13.00 Leave greasewood and shadscale and enter slat brush,

28.70 Record course and distance; find no trace of the original meander cor.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for meander cor. fractional secs. 13 and 24, with brass cap marked

T19S	
S13	M
S24	C
ROW	

1940

deposit a quartzite, 8 x 7 x 2 ins., at base of post, marked X; also broken glass.

Land, nearly level alkali flat.

Soil, clay and sandy clay; 3rd rate.

No timber.

Undergrowth, greasewood, shadscale, and salt brush.

Fair to poor grazing land.

From the cor. of secs. 13, 14, 23, and 24.

North, bet. secs. 13 and 14.

Over nearly level desert land, through scattered short undergrowth.

40.00 Record distance; find no trace of the 1/4 sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for 1/4 sec. cor., with brass cap marked

S14	S13
-----	-----

1940

deposit broken glass and a quartzite, .10 x 4 x 3 ins., at base of post, marked X.

46.10 Mine wire telegraph line, bears N. 25° 57' E. and S. 25° 57' W.

49.40 Union Pacific Railroad, bet. Salt Lake City, Utah, and

## DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 8 W.

Chains


Los Angeles, Calif., bears N. 25°57' E. and S. 25°57' W.

52.50 Telegraph line, 13 wires, bears with railroad.

53.30 Graded and graveled road, bears with railroad, bet. Dese and Clearlake.

61.00 Record distance; find no trace of the meander cor.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for meander cor. fractional secs. 13 and 14, with brass cap marked



small mound of stone, S. of cor.

raise a

Land, nearly level desert.

Soil, sandy clay with alkali; 3rd rate.

No timber.

Undergrowth, shadscale, greasewood, and salt brush.

Poor grazing land.


From the cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the township, an iron post, 2 ins. diam., set, marked, witnessed, as described in the official record of the survey of T. 18 S., R. 8 W., Group 207, Utah.

S. 0°06' E., bet. secs. 1 and 2.

Over gently rolling top of bench, through scattered short undergrowth.

40.34 Proportionate distance; find no trace of the  $\frac{1}{4}$  sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked



small mound of stone around post.

raise a

65.00 Top of low ridge, bears E. and W.; thence over gradual S. slope.

73.30 Unimproved road, bears N. 60° W. and S. 60° E.

78.80 The S. rim of bench, bears E. and W.; descend 15 ft. over rocky S. face.

80.68 The cor. of secs. 1, 2, 11, and 12, a juniper post, 3 ft. long, 3 ins. diam., lying on ground, upon which I find describe marks. Cor. has no accessories.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in the

DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 9 W.

Chains

ground to solid rock and in a large mound of stone to top, with the original cor. monument alongside post, for cor. secs. 1, 2, 11, and 12, with brass cap marked

T19S	R8W
S2	S1
S11	S12

1940

from which

A point on a lava outcropping, marked X, bears N. 73° W., 16 lks. dist.

Land, rolling bench.  
 Soil, shallow sandy clay and rocky, of a volcanic formation; 3rd to 4th rates.  
 No timber.  
 Undergrowth, short shadscale.  
 Fair grazing land.

East, bet. secs. 1 and 12.

Ascend gradual SW. slope of broken bench, through scattered undergrowth.

2.10 Small rim facing W., bears N. 70° W. and SE.

4.20 Top of ascent on point of bench, 15 ft. above cor., bears S., about 4.00 chs. dist. to end; descend gradually along broken S. slope.

8.40 Dim unimproved road, bears NW. and S. 30° E.

31.60 E. rim of bench, bears N. 20° W. and S. 20° E.; descend.

34.60 Base of bench, bears with top; thence over nearly level flat.

40.00 Record distance; find no trace of the ¼ sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for ¼ sec. cor., with brass cap marked

S1
¼
S12

1940

raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

42.80 Record distance; find no trace of the meander cor.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for meander cor. fractional secs. 1 and 12, with brass cap marked

T19S	/	M
S1	/	C
S12	/	
R8W	/	

1940

raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

INTERMITTENT RESURVEY OF SUBDIVISION, T. 19 S., R. 8 W.

Chains

Land, broken and rolling bench and level clay flat.  
Soil, sandy clay and rocky on bench, alkali and clay on flat; 3rd and 4th rates.  
No timber.  
Undergrowth, shadscale, and a few greasewood and salt br  
Fair to poor grazing land.

from the cor. of secs. 1, 2, 11, and 12.

N. 6°11' E., bet. secs. 11 and 12.

Ascend slight S. slope of rolling land, through short undergrowth.

1.01 Base of bench, bears N. and W.

2.40 Unimproved road, bears N. 80° E. and S. 80° W.

21.00 The reander cor. of fractional secs. 11 and 12, a juniper post, 2½ ft. long, 2 ins. diam., squared on 2 faces, upon which I find dia scribe marks. Cor. is set in small mound of earth.

at the cor. point:

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with the original cor. monument deposited at the base of the post, for reander cor. of fractional secs. 11 and 12, with brass cap marked

T19S | R8W  
S11 | S12

M.C.

1940

round of stone, 2 ft. base, 1½ ft. high, N. of cor. raise a

Land, nearly level desert with a slight S. slope.  
Soil, sand and alkali clay; 3rd rate.  
No timber.  
Undergrowth, shadscale.  
Fair to poor grazing land.

from the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the township.

N. 6°16' E., bet. secs. 34 and 35.

Over nearly level desert land, through short undergrowth

11.01 Graded and gravelled road, bears N. 61°30' W. to Clear Lake and S. 61°30' E. to Fillmore, Utah.

11.37 The sec. cor., a juniper post, 1½ ft. long, 3 ins. dia firmly set, upon which I find dia scribe marks. Cor. has no accessories.

At the cor. point.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with the original cor. monument alongside, for the sec. cor., with brass cap marked

DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 8 W.

Chains

1/4  
S34 | S35  
1940

mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor. raise a  
Thence, N. 0°14' E.

16.90 Old irrigation ditch, 10 lks. wide, 1 ft. deep, drains N. 65° W.

40.33 The cor. of secs. 26, 27, 34, and 35, a juniper post, 2 ft. long, 4 ins. dian., firmly set, marked 1 notch on S. and 2 notches on E. edge, and other dim scribe marks. Cor. has no accessories.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with the original cor. monument alongside, for cor. secs. 26, 27, 34, and 35, with brass cap marked

T19S | R8W  
S27 | S26  
S34 | S35  
1940

mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor. raise a

Land, nearly level desert.  
Soil, alkali clay; 3rd rate.  
No timber.  
Undergrowth, short shadscale and greasewood.  
Fair grazing land.

From the cor. of secs. 25, 26, 35, and 36.

N. 89°47' W., bet. secs. 26 and 35.

Over nearly level land, through short undergrowth.

39.93 Proportionate distance; find no trace of the 1/4 sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for the restored 1/4 sec. cor., with brass cap marked

1/4 S26  
S35  
1940

small mound of stone, N. of cor. raise a

79.86 The cor. of secs. 26, 27, 34, and 35.

Land, nearly level.  
Soil, alkali clay; 3rd rate.  
No timber.  
Undergrowth, shadscale and greasewood.  
Fair grazing land.

## DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 8 W.

## Chains

N.  $0^{\circ}23'$  E., bet. secs. 26 and 27.

Over level land, through short undergrowth.

40.06 The  $\frac{1}{4}$  sec. cor., a juniper post, 2 ft. long, broken off the ground, 2 ins. diam. No marks visible on post, and no accessories found.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with the original cor. monument alongside post, for  $\frac{1}{4}$  sec. cor., with brass cap marked

	$\frac{1}{4}$	
S27		S26
1940		

of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor. raise a mo

Thence, N.  $0^{\circ}15'$  E.

4.00 The N. end of railroad right-of-way fence, bears W., 35 dist.

5.00 Telegraph line, 8 wires, bears parallel to railroad.

5.40 Old unimproved road, bears NE. and SW.

8.40 Center of Union Pacific Railroad track, bears N.  $25^{\circ}57'$  and S.  $25^{\circ}57'$  W.

11.60 Telegraph line, 13 wires, bears parallel to railroad.

12.40 Graded and gravelled road, bears parallel to railroad, bet. Desert and Clear Lake.

24.10 Old unused road, bears N.  $8^{\circ}$  E. and S.  $8^{\circ}$  W.

40.06 The cor. of secs. 22, 23, 26, and 27, a juniper post, broken off at the ground, top portion, 2 ft. long, 4 ins. diam., upon which I find dim scribe marks on all four faces. Cor. has no accessories.

At the cor. point.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with the original cor. monument deposited at the base of the post, for cor. secs. 22, 23, 26, and 27, with brass cap marked

T19S		R8W
S22		S23
S27		S26
1940		

mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor. raise a

Land, nearly level desert.

Soil, sandy and alkali clay; 3rd rate.

No timber.

Undergrowth, shadscale and greasewood.

Fair grazing land.

DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 8 W.

Chains

From the cor. of secs. 23, 24, 25, and 26.

S. 89°37' W., bet. secs. 23 and 26.

Over nearly level land, through short undergrowth.

39.53 Proportionate distance; find no trace of the 1/4 sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for restored 1/4 sec. cor., with brass cap marked

S23

S26

1940

raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

52.20 Dim road, bears NE. and SW.

62.20 Telegraph line, 9 wires, bears parallel to railroad.

63.75 Center of Union Pacific Railroad track, bears N. 25°57' E. and S. 25°57' W.

65.00 Telegraph line, 13 wire, bears parallel to railroad.

65.60 Gravelled road, parallel to railroad.

77.10 Old unused road, bears N. 8° E. and S. 8° W.

79.05 The cor. of secs. 22, 23, 26, and 27.

land, nearly level desert.

Soil, heavy alkali clay; 3rd rate.

No timber.

Undergrowth, short shadscale and greasewood.

Fair grazing land.

N. 1°24' W., bet. secs. 22 and 23.

Over nearly level land, through short undergrowth.

15.00 Leave greasewood and continue through shadscale.

40.45 Proportionate distance; find no trace of the 1/4 sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for 1/4 sec. cor., with brass cap marked

S22

S23

1940

raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

74.00 Leave shadscale and continue through salt brush.

80.89 Proportionate distance; find no trace of the cor. secs. 14, 15, 22, and 23.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for cor. secs. 14, 15, 22, and 23, with brass cap marked

## DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 8 W.

Chains

T19S	RSW
S15	S14
S22	S23

1940

raise a  
mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Land, nearly level desert.

Soil, sand and alkali clay; 3rd rate.

No timber.

Undergrowth, shadscale, greasewood, and salt brush.

Fair to poor grazing land.

From the cor. of secs. 13, 14, 23, and 24.

S.  $89^{\circ}53'$  W., bet. secs. 14 and 23.

Over nearly level desert land, through short undergrowth

22.40 Telegraph line, 3 wires, bears parallel to railroad.

24.00 Center of Union Pacific Railroad track, bears N.  $25^{\circ}57'$   
and S.  $25^{\circ}57'$  W.

25.60 Telegraph line, 13 wires, bears parallel to railroad.

25.90 Gravelled road bet. Desert and Clear Lake, bears parallel  
to railroad.40.32 Proportionate distance; find no trace of the  $\frac{1}{4}$  sec. cor.Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked

S14

S23.

1940

raise a  
mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

65.30 Old unused road, bears N.  $10^{\circ}$  E. and S.  $10^{\circ}$  W.

73.00 Leave shadscale and enter salt brush.

80.64 The cor. of secs. 14, 15, 22, and 23.

Land, nearly level desert.

Soil, sandy alkali clay; 3rd rate.

No timber.

Undergrowth, short shadscale, greasewood, and salt brush

Fair to poor grazing land.

N.  $0^{\circ}31'$  W., bet. secs. 14 and 15.

Over nearly level desert land, through short undergrowth

80.43 Proportionate distance; find an old juniper post lying  
on the ground but no evidence of its original position.

dependent resurvey of subdivision, T. 19 S., R. 3 W.

Chains

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with the original cor. monument alongside, for sec. cor., with brass cap marked

S15 | S14

1940

raise a small mound of stone around the cor. post.

80.86. ~~As three point control~~; find no trace of the cor. secs. 10, 11, 14, and 15.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for cor. secs. 10, 11, 14, and 15, with brass cap marked

T19S | ROW  
S10 | S11

S15 | S14

1940

raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, nearly level desert with surface broken by small sandy hummocks and wind blown rises.

Soil, sandy clay, and heavy alkali clay; 3rd rate.

No timber.

Undergrowth, salt brush and weeds, with a few chadscale.

Fair to poor grazing land.

East, bet. secs. 11 and 14.

Over level alkali flat, through scattered brush.

29.00 Old unused road, bears N. 10° E. and S. 10° W.

30.00 Record distance; find no evidence of the meander cor. fractional secs. 11 and 14, reported as being set on bank of a salt lake bearing NW. and SE.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for meander cor. fractional secs. 11 and 14, with brass cap marked

T19S |  
S11 | M  
S14 | C  
ROW |  
1940

raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, level alkali flat.

Soil, alkali clay and sand; 4th rate.

No timber.

Undergrowth, scattered salt brush, and weeds.

Poor grazing land.

DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 8 W.

Chains

211040

From the cor. of secs. 10, 11, 14, and 15.

N. 0°40' E., bet. secs. 10 and 11.


Over nearly level desert land, through scattered short undergrowth.

8.40 Old drainage canal, 40 lks. wide, 1 ft. deep, drains N. 20° W., for about 10.00 chs., thence southwesterly. Begin slight ascent over southerly slope, entering heavy undergrowth.

10.42 The  $\frac{1}{4}$  sec. cor., a volcanic stone, 18 x 12 x 6 ins., firm set in small mound of stone, marked  $\frac{1}{4}$  on W. face.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with the original cor. monument deposited at the base of the post, for  $\frac{1}{4}$  sec. cor., with brass cap marked



small mound of stone, around post.

raise a

Thence, N. 0°15' W.

0.30 Dim unimproved road at S. base of volcanic bench, bears E. and W.; ascend rocky S. face of bench, 150 ft. to

7.40 Top of S. rim of bench, bears N. 80° E. and S. 80° W.; thence over rolling top of bench.

12.90 Point from which a marl pit, bears E., about 2.00 chs. dist. Pit is 2.00 chs. in diam.


26.00 Small draw, 10 ft. deep, drains E.

30.60 The N. rim of upper bench, bears NW. and SE.; descend 50

33.60 Base of upper bench, bears NW. and SE.; thence over rolling top of lower bench.

40.00 Proportionate distance; find no trace of the cor. secs. 2, 3, 10, and 11.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for cor. secs. 2, 3, 10, and 11, with brass cap marked



round of stone, 2 ft. base, 1½ ft. high, W. of cor.

raise a

Land, nearly flat on S. portion of mile; rolling volcanic bench on NW portion.

Soil, sandy alkali clay on flat; shallow sandy clay on bench, with rock; 3rd to 4th rates.

No timber.

DEPENDENT RESURVEY SUBDIVISION, T. 19 S., R. 8 W.

Chains Undergrowth, shadscale, greasewood, and salt brush.  
Fair grazing land.

---

From the cor. of secs. 1, 2, 11, and 12.  
N. 89°55' W., bet. secs. 2 and 11.  
Over broken general S. face of low volcanic bench, through short undergrowth.

4.60 Low rim of bench, 20 ft. above cor., bears NE. and SW.; thence across top of point of bench.

7.70 Leave top of bench, bears NW. and SE.; thence along general S. face.

20.00 Low rim, faces SE. and bears NE. and SW.; thence across top of bench.

30.00 Leave top of bench, bears NW. and SE.; thence along broken S. slope.

36.50 Unimproved road, bears NW. and SE.

37.40 Dim trace of old road, bears N. 20° E. and S. 20° W.

37.60 Depression on S. slope, 35 ft. below top of bench, drains S.

40.23 Proportionate distance; find no trace of the 1/4 sec. cor.  
Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, and in a mound of stone to top, for 1/4 sec cor., with brass cap marked

S2  
—  
S11

1940

raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

52.70 Rim of bench, 35 ft. above cor., bears northerly, about 10.00 chs. dist., thence SE., and SW.; thence across point of bench.

56.00 Rim facing SW., bears NW. and SE.; thence along general S. face.

63.20 Rim facing SE., bears NE. and SW.; thence over rolling top.

77.40 Shallow draw, course SE.

80.46 The cor. of secs. 2, 3, 10, and 11, 50 ft. above the 1/4 sec. cor.  
Land, rolling and broken; line follows along S. edge and slope of low volcanic bench.  
Soil, rocky with shallow clay; 4th rate.  
No timber.  
Undergrowth, short shadscale.  
Fair grazing land.

## DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 8 W.

Chains

From the cor. of secs. 2 and 3, on the N. bdy. of the township, an iron post, 2 ins. diam., set, marked, and witnessed, as described in the official record of the survey of T. 18 S., R. 8 W., Group 207, Utah.

Thence,

S.  $0^{\circ}29'$  E., bet. secs. 2 and 3.

Over rolling top of volcanic bench, through short undergrowth.

40.35

The  $\frac{1}{4}$  sec. cor., a juniper post, 3 ft. long, 3 ins. diam. squared on two sides, lying on ground, upon which I find dim scribe marks. Cor. has no accessories.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with the original cor. monument deposited at the base of the post, for  $\frac{1}{4}$  sec. cor., with brass cap marked

S3 | S2

1940

raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Thence, S.  $0^{\circ}11'$  W.

13.00

Old unimproved road, bears NW. and SE.

22.00

Old unimproved road, bears N.  $80^{\circ}$  W. and S.  $80^{\circ}$  E.

40.09

The cor. of secs. 2, 3, 10, and 11.

Land, rolling top of bench, with slight general E. slope. Soil, shallow sandy clay; 3rd rate.

No timber.

Undergrowth, shadscale.

Fair grazing land.

From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the township.

N.  $0^{\circ}23'$  W., bet. secs. 33 and 34.

Over nearly level land, through short undergrowth.

13.90

Old irrigation ditch, 5 lks. wide, 2 ft. deep, drains SW.

20.00

Thence along a lane with old wire fences to the E. and W. of line.

39.63

Wire fence on S. side of road, bears E. and W.

40.24

In center of road, bears E. and W., the  $\frac{1}{4}$  sec. cor., a juniper post, 2 ft. long, 3 ins. diam., found set with top flush with the surface of the ground. Cor. has no accessories.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. diam., 36 ins. in the ground, with the original cor. monument deposited alongs

DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 8 W.

Chains

for 1/4 sec. cor., with brass cap marked

1/4	
S33	S34
1940	

broken glass at the base of the post. deposit

From cor., S. 0°23' E., 50 lks. dist., set a volcanic stone, 11 x 9 x 6 ins., in the ground flush with the surface, marked WC on N. face and X on top face, and witnessed by a mound of stone, 2 ft. base, 1 1/2 ft. high W. of stone, for witness cor. to the 1/4 sec. cor.

The true 1/4 sec. cor., is in center of road, well traveled, bearing E. to Clear Lake and W.

From the true 1/4 sec. cor., the chimney on center of Clear Lake station house, bears N. 97°18' E., about 1/2 mile dist. Center of section house on W. side of tracks, bears S. 91°45' E., and the W. gable of house on E. side of tracks, bears S. 90° E.

Continue N. 0°23' W.

0.47 Wire fence on N. side of road, bears E. and W.

40.24 The cor. of secs. 27, 28, 33, and 34, a juniper post, 2 ft. long, 4 ins. diam., marked 1 notch on S. edge. No other marks found on post. Cor. has no accessories.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with the original cor. monument deposited alongside, for cor. secs. 27, 28, 33, and 34, with brass cap marked

T19S R8W	
S28	S27
-----	
S33	S34
1940	

mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor. raise a

Land, nearly level valley.  
Soil, heavy alkali clay; 3rd rate.  
No timber.  
Undergrowth, shadscale and greasewood.  
Fair grazing land.

From the cor. of secs. 26, 27, 34, and 35.

N. 89°56' W., bet. secs. 27 and 34.

Over level land, through short undergrowth.

20.80 Dim road, bears parallel to railroad.

21.30 Right-of-way fence, 5 barbed strands, bears parallel to railroad.

## DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 8 W.

Chains

- 21.40 Telegraph line, 8 wires, bears parallel to railroad.
- 22.30 Center main line of Union Pacific Railroad track, bears N.  $25^{\circ}55'$  E., and S.  $25^{\circ}55'$  W.; side track along E. side of main track, bears northerly about 30.00 chs. dist. to the N. end of same.
- 24.90 Telegraph line, 13 wires, bears parallel to railroad.
- 25.00 Right-of-way fence, bears parallel to railroad.
- 26.70 Graded and gravelled road, bet. Deseret and Clear Lake, bears parallel to railroad.
- 27.80 The E. end of old wire fence from the W., bears S. of 11 20 lks. dist., fence turns to the NE. and bears parallel to the railroad.
- 40.75 Proportionate distance; find no trace of the  $\frac{1}{4}$  sec. cor. Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked

$$\begin{array}{r} S27 \\ \frac{1}{4} \\ \hline S34 \end{array}$$

1940

- raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.
- Cor. set 15 lks. N. of old fence bearing E. and W.
- 61.40 The SW. cor. of old fence bearing N. and E., bears S., 10 lks. dist.
- 81.49 The cor. of secs. 27, 28, 33, and 34.
- Land, nearly level.  
Soil, heavy clay; 3rd rate.  
No timber.  
Undergrowth, greasewood, shadscale, and salt brush.  
Fair grazing land.

N.  $0^{\circ}22'$  W., bet. secs. 27 and 28.

Over nearly level land, through short undergrowth.

- 40.11 The  $\frac{1}{4}$  sec. cor., a juniper post, 4 ft. long, 4 ins. diam. loosely set, upon which I find dim scribe marks. Cor. has no accessories.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with the original cor. monument deposited alongside, for  $\frac{1}{4}$  sec. cor., with brass cap marked

$$\begin{array}{r} \frac{1}{4} \\ S28 \mid S27 \end{array}$$

1940

raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 8 W.

Chains

Cor. set 3 lks. S. of old two strand barbed wire fence, bearing E. and N. 89°40' W.

Thence, N. 0°23' W.

40.11

The cor. of secs. 21, 22, 27, and 28, a juniper post, 2½ ft. long, 3 ins. diam., and squared at top, upon which I find dim scribe marks on all sides. Cor. is firmly set and has no accessories.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with the original cor. monument deposited at the base of the post, for cor. secs. 21, 22, 27, and 28, with brass cap marked

T19S, R8W  
S21 | S22

S23 | S27

1940

raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, nearly level.

Soil, heavy alkali clay; 3rd rate.

No timber.

Undergrowth, greasewood and shadscale.

Fair grazing land.

From the cor. of secs. 22, 23, 26, and 27.

N. 89°40' W., bet. secs. 22 and 27.

Over nearly level flat, through short undergrowth.

40.04

The ¼ sec. cor., a juniper post, 2½ ft. long, 3 ins. diam., squared on two sides, upon which I find dim scribe marks. Post is lying on the ground and has no accessories. The cor. point is determined by fragments of the rotted stump.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with the original cor. monument deposited at the base of the post, for ¼ sec. cor., with brass cap marked

S22

S27

1940

raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

Continue on same line.

24.00

Enter medium dense greasewood.

42.28

The cor. of secs. 21, 22, 27, and 28.

Land, nearly level.

Soil, heavy alkali clay; 3rd rate.

No timber.

Undergrowth, greasewood and shadscale.

Fair grazing land.


Chains

N. 0°01' W., bet. secs. 21 and 22.

Over nearly level land, through medium dense greasewood.

40.56 Proportionate distance; find no trace of the  $\frac{1}{4}$  sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked



raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.


47.40 Low rise, bears NE. and SW.

53.00 Enter dry lake bed void of vegetation, bears NE. and SW. thence across lake bed with wet sticky alkali clay.

01.12 The cor. of secs. 15, 16, 21, and 22, a juniper post, firmly set, 3 ft. long, 4 ins. diam., squared at top and upon which I find discribe marks. Cor. has no accesson

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with the original cor. monument deposited along side, for cor. of secs. 15, 16, 21, and 22, with brass marked



broken glass at the base of the post. deposit

Land, nearly level desert on S. portion of mile; level dry lake bed on N. portion.  
Soil, alkali clay and sandy clay; 3rd and 4th rates.  
No timber.  
Undergrowth, greasewood on S. portion of mile.  
Poor grazing land.

From the cor. of secs. 14, 15, 22, and 23.

N. 89°37' W., bet. secs. 15 and 22.

Over nearly level flat, through scattered undergrowth.

14.60 Low sandy rim, bears NW. and SE.


16.30 Enter dry lake bed, bears NW., and SE. for about 8.00 ch thence westerly.

40.17 Proportionate distance; find no evidence of the true position for the  $\frac{1}{4}$  sec. cor.; an old juniper post lying on ground found considerable distance away.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked

DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 8 W.

Chains



1940

broken glass at the base of post. deposit

Cor. set on wet alkali lake bed.

80.34 The cor. of secs. 15, 16, 21, and 22.

Land, nearly level flat on E. portion of mile, dry lake bed on W. portion.

Soil, wet heavy clay, saturated with alkali and salt on lake bed; sandy clay on E. portion of mile; 3rd and 4th rates.

No timber.

Undergrowth, a few scattered salt brush.


Poor grazing land.

N. 0°16' W., bet. secs. 15 and 16.

Over level bottom of dry lake bed void of vegetation.

40.31 Proportionate distance; find no trace of the 1/4 sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for 1/4 sec. cor., with brass cap marked



1940


broken glass at the base of the post. deposit

76.50 Leave lake bottom and enter sandy clay land and brush, bears E. and W.

80.61 The cor. of secs. 9, 10, 15, and 16, a juniper post, 3 ft. long, 4 ins. diam.; squared at top, upon which I find discribe marks. Cor. is firmly set and has no accessories.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with the original cor. monument deposited alongside, for cor. secs. 9, 10, 15, and 16, with brass cap marked



1940

broken glass at the base of the post. deposit

Land, level lake bottom on S. 76.50 chs. of mile and nearly level desert on N. end of mile.

Soil, wet muddy clay saturated with alkali, and sandy clay; 3rd and 4th rates.

No timber.  
Undergrowth, salt brush on N. end of mile.  
Poor grazing land.

From the cor. of secs. 10, 11, 14, and 15.

N. 89°47' W., bet. secs. 10 and 15.

Over nearly level land, the surface of which is broken by small hummocks and sandy rises, through scattered undergrowth.

15.50 Channel of a drainage canal, 40 lks. wide, 8 ft. deep, drains SW.

39.90 Record distance; find no trace of the  $\frac{1}{4}$  sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked

S10

S15

1940

mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, N. of cor. raise a

79.80 The cor. of secs. 9, 10, 15, and 16.

Land, nearly level desert, slight southern exposure into dry lake to the S. of line; surface broken by small hummocks, sandy rises, and small washes.

Soil, sandy white clay with alkali; 4th rate.  
No timber.

Undergrowth, a few scattered greasewood, shadscale, and brush.

Poor grazing land.

N. 0°04' W., bet. secs. 9 and 10.

Over nearly level desert with a slight southern exposure through short undergrowth.

29.70 Old unimproved road, bears nearly E. and W.

40.35 The  $\frac{1}{4}$  sec. cor., the stump of a juniper post, 10 ins. long, firmly set. The top of post is missing, and cor. has no accessories.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with the stump of the original cor. monument deposited alongside, for  $\frac{1}{4}$  sec. cor., with brass cap marked

S9 | S10

1940

mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, W. of cor. raise a

DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 8 W.

Chains

Thence, N. 0°11' W.


31.10 The S. base of volcanic bench, bears easterly for about 10.00 chs., thence southeasterly, and westerly for about 10.00 chs., thence SW. to W.; ascend steep rocky S. slope, 120 ft.

39.60 Top of S. edge of bench, 160 ft. above the 1/4 sec. cor., bears E. and W.; thence over top of bench.

40.63 The cor. of secs. 3, 4, 9, and 10, which is the center of a deeply embedded mound of stone; no cor. monument could be found.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for cor. secs. 3; 4, 9, and 10, with brass cap marked



1940

raise a mound of stone, 4 ft. base, 3 ft. high, W. of post.

Land, nearly level desert and broken bench.  
Soil, sandy clay and rocky; 3rd to 4th rates.  
No timber.  
Undergrowth, greasewood and shadscale.  
Fair grazing land.

From the cor. of secs. 2, 3, 10, and 11.

N. 89°26' W., bet. secs. 3 and 10.

Over rolling bench land, through short undergrowth.


7.50 The E. base of upper bench, bears NW. and SE.; ascend 75 ft. over broken NE. slope.

12.00 Top of rim on upper bench, bears NW. and SE.; thence over rolling top of bench.

22.20 Dip road, bears N. and S.

40.15 Proportionate distance; find no trace of the 1/4 sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for 1/4 sec. cor., with brass cap marked



1940

raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

61.00 Small swale, drains S., about 2.50 chs. dist. to S. rim of bench.

80.29 The cor. of secs. 3, 4, 9, and 10.

DEPENDENT RESURVEY OF SUBDIVISION T. 18 S., R. 8 W.

Chains

181440

Land, rolling top of bench.  
Soil, shallow sandy clay with rock; 3rd rate.  
No timber.  
Undergrowth, short shadscale.  
Fair grazing land.

01.18


From the cor. of secs. 3 and 4, on the N. bdy. of the township, an iron post, 2 ins. diam., set, marked and witnessed, as described in the official record of the survey of T. 18 S., R. 8 W., Group 207; Utah.

S. 0°12' E., bet. secs. 3 and 4.

Over rolling top of volcanic bench, through short under

40.74 Proportionate distance; find no trace of the  $\frac{1}{4}$  sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked



raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, W. of cor.

81.27 The cor. of secs. 3, 4, 9, and 10.

Land, rolling top of bench.  
Soil, shallow sandy clay, with rock; 3rd rate.  
No timber.  
Undergrowth, shadscale, scattered Brigham tea, and grass  
Fair to good grazing land.

From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the township.


N. 0°36' W., bet. secs. 32 and 33.

Over nearly level land, through medium dense tall grease

12.40 Small ditch, drains NW.; leave nearly all greasewood and continue through salt brush.

40.32 Proportionate distance; find no trace of the  $\frac{1}{4}$  sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked



raise a mound of stone ground the cor. monument and deposit glass at the base of same.

Cor. set in the center of an old unused ditch, 5 lks. wide drains NW., 10 lks. dist.; thence W.

52.90 Old irrigation ditch, 20 lks. wide, 2 ft. deep, drains NW.

U. S. GEOLOGICAL SURVEY, BUREAU OF LANDS, R. 13 W.

Chains

chains

S25	S30
S35	S40

 1939

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the post, and deposit broken glass and the original corner stone at the base of the post.

Land, nearly level desert, sloping to the west. Soil, coarse gravelly clay of granite formation; 3rd rate. Timber, none. Undergrowth, shadeless, match brush and bunch grass. Grazing, fair.

N.0°06'E., on dependent resurvey, between sections 25 and 30.

Over nearly level land, through scant undergrowth, descend 25 ft. along a gentle NW. slope to the 1/4 section corner.

23.20 Swale, drains N.70°W.

40.16 The original 1/4 section corner, a granite stone, 10x8x4 ins., firmly set in the ground, and marked 1/4 on west face.

At the corner point.

Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in the ground, for the 1/4 section corner, with brass cap marked

S25	S30
-----	-----

 1939

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the post, and deposit broken glass and the original corner stone at the base of the post.

Thence

N.0°06'E., with continuous measurement.

Descend 25 ft. to the section corner.

80.28 The original corner of sections 19, 24, 25, and 30, marked by a volcanic stone, 14x12x8, firmly set in the ground, and marked with 2 notches on the south, and 4 notches on north edges, not witnessed.

At the corner point.

Set an iron post, 3 ft. long, 2 ins. diameter, 27 ins. in the ground, for the corner of sections 19, 24, 25, and 30, with brass cap marked

T27S  

R14W	R13W
S24	S19
S25	S30

 1939

Raise a mound of stone, 3 ft. base, 3 ft. high, west of the post, and deposit broken glass and the original corner stone at the base of the post.

## DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 8 W.

Chains

N.  $0^{\circ}10'$  W., bet. secs. 28 and 29.Over nearly <sup>level</sup> land through salt grass.

0.33 Fence along the N. side of lane and road, bears W. and E. 87 lks. dist., thence S.

16.00 Enter scattered greasewood.

40.32 Proportionate distance; find no trace of the  $\frac{1}{4}$  sec. cor.  
Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked

	$\frac{1}{4}$	
S29	S28	
1940		

mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor. raise aFrom this cor., the SW. cor. of fences bearing E. and N. bears S.  $76^{\circ}$  W., 65 lks. dist.

59.90 The NE. cor. of fences bearing S. and W., bears W., about 1.50 chs. dist.

80.64 The cor. of secs. 20, 21, 28, and 29, a juniper post, 3 ft. long, 3 ins. diam., firmly set, upon which I find dim marks. Cor. has no accessories.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with the original cor. monument deposited along for cor. of secs. 20, 21, 28, and 29, with brass cap marked

T19S	R8W
S20	S21
S29	S28
1940	

mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor. raise a

Land, nearly level desert.

Soil, alkali clay; 3rd rate.

No timber.

Undergrowth, greasewood and grass.

Fair grazing land.

From the cor. of secs. 21, 22, 27, and 28.

N.  $89^{\circ}17'$  W., bet. secs. 21 and 28.

Over level land, through scattered greasewood.

13.00 Leave nearly all greasewood, continue through salt brush

40.22 Find no trace of the original point for the  $\frac{1}{4}$  sec. cor. but find an old juniper post lying on the ground out of place. Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with the original cor. monument deposited along

## DEPENDENT RESURVEY OF SUBDIVISION' T. 19 S., R. 8 W.

## Chains

side, for  $\frac{1}{4}$  sec. cor., with brass cap marked

S21

$$\frac{1}{4}$$

S28

1940

raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

46.60 Enter barren lake bed, bears N.  $60^\circ$  E. and S.  $60^\circ$  W.

56.10 Top of sandy clay rise, 4 ft. high, 1.00 ch. wide, extends N.  $30^\circ$  E., about 8.00 chs. dist. to end; continue over lake bed.

60.10 Leave lake bed, bears N.  $30^\circ$  E. and S.  $30^\circ$  W.

68.20 Reenter narrow neck of lake bed, extending S., about 4.00 chs. dist. to S. end.

70.70 Leave lake bed, bears N. and S.

80.44 The cor. of secs. 20, 21, 28, and 29.

Land, level desert and dry lake bed; W. half of mile passes along S. edge of dry lake bed extending northerly.

Soil, sandy clay and wet alkali clay; 3rd and 4th rates.

No timber.

Undergrowth, short salt brush except on lake bed which is barren.

Poor grazing land.

N.  $0^\circ 14'$  W., bet. secs. 20 and 21.

Over nearly level desert through salt brush.

2.10 Enter barren lake bed, bears NE. and SW.; thence across arm of lake bed opening out to the NE.

16.00 Leave same., bears E., and westerly for about 7.00 chs. thence southerly; enter scattered greasewood.

40.24 Proportionate distance; find no trace of the  $\frac{1}{4}$  sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked

S20 | S21

1940

raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

43.00 Enter the SE. edge of salt pond or dry lake bed, bears N.  $20^\circ$  E. and westerly; thence across pond with a salt crust from 1 to 3 ins. thick.

80.48 The cor. of secs. 16, 17, 20, and 21, a charred stump of a juniper post, 2 ft. long, firmly set. No visible marks on post, and no accessories found.

At the cor. point:

DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 8 W.

Chains

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in ground, with the original cor. monument deposited along side post, for cor. secs. 16, 17, 20, and 21, with brass cap marked

T19S	R8W
S17	S16

S20	S21
-----	-----

1940

broken glass at the base of the post.

deposit

Cor. set in salt pond.

Land, level desert and lake beds.  
Soil, sand clay and heavy clay saturated with salt and alkali; 3rd and 4th rates.  
No timber.  
Undergrowth, scattered salt brush and greasewood.  
Poor grazing land.

From the cor. of secs. 15, 16, 21, and 22.

N. 89°44' W., bet. secs. 16 and 21.

Across wet alkali clay lake bed void of vegetation.

40.36 Proportionate distance; find no trace of the  $\frac{1}{4}$  sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked

$\frac{1}{4}$	S16
	S21

1940

volcanic rock, 8 x 6 x 4 ins., at base of post, marked

deposit a

68.30 The W. edge of lake bed, bears N. 10° E. and S. 10° W.; thence overrolling sandy clay rise with scattered shade

71.00 Top of rise bet. lake bed to the E. and a salt pond to the W.; bears N. 15° W. and S. A drainage channel between the two, bears S. of line, about 15 chs. dist.

78.60 The E. edge of salt pond, bears N. 30° W. and S. 10° E.

80.72 The cor. of secs. 16, 17, 20, and 21.

Land, level lake bed and low sandy rise.  
Soil, wet alkali clay and sandy clay; 4th and 3rd rates.  
No timber.  
Undergrowth, scattered shadscale on portion of mile.  
Poor grazing land.

N. 0°28' W., bet. secs. 16 and 17.

Across salt pond with crust from 2 to 3 ins. thick.

3.30 Leave salt pond, bears NW. and SE.; thence over nearly level desert land with scattered salt brush.

## DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 8 W.

## Chains

18.00 Low sandy clay rise, bears W. and SE.

40.26 Proportionate distance; find no trace of the  $\frac{1}{4}$  sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked

S17	S16
-----	-----

1940

mound of stone, 3 ft. base, 2 ft. high, W. of cor. raise a

42.50 Enter lake bed, bears E. and W.

74.00 Leave lake bed, bears NE. and SW.

80.52 Proportionate distance; find no trace of the cor. secs. 8, 9, 16, and 17.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for cor. secs. 8, 9, 16, and 17, with brass cap marked

T19S	R8W
S8	S9

S17	S16
-----	-----

1940

mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor. raise a

Land, lake bed and nearly level desert.

Soil, wet lakali clay and sandy clay; 4th and 3rd rates.

No timber.

Undergrowth, scattered salt brush, shadscale, and greasewood.

Poor grazing land.

From the cor. of secs. 9, 10, 15, and 16.

S. 89°48' W., bet. secs. 9 and 16.

Over nearly level desert land through scattered salt brush.

19.00 Enter lake bed, bears NW., and SE. for about 6.00 chs., thence easterly.

40.50 The  $\frac{1}{4}$  sec. cor., a charred juniper post, 2 ft. long, 2 ins. diam., firmly set. No marks found on post, and cor. has no accessories.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with the original cor. monument deposited at the base of the post, for  $\frac{1}{4}$  sec. cor., with brass cap marked

S9
----

S16
-----

1940

DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 8 W.

Chains

ENCLOSURE

Deposit glass at the base of the post. 100.00

Thence, N. 89°24' W. 13.00

35.50 Leave lake bed, bears NE. and SW.

40.47 The cor. of secs. 8, 9, 16, and 17.

Land, lake bed and nearly level desert.  
Soil, wet alkali clay and sandy clay; 4th and 3rd rates  
No timber.  
Undergrowth, scattered salt brush and a few greasewood.  
Poor grazing land.

N. 0°43' W., bet. secs. 8 and 9.

Over slight S. slope of nearly level desert land, through short undergrowth.

2.20 Unimproved road, bears NE. and SW.

40.26 The  $\frac{1}{4}$  sec. cor., a juniper post, 3 ft. long, 3 ins. dia. lying in a small mound of stone, upon which I find dim describe marks. Cor. has no accessories.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in ground, with the original cor. monument deposited along for  $\frac{1}{4}$  sec. cor., with brass cap marked

	$\frac{1}{4}$	
S8		S9
1940		

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor., and deposit glass at the base of post.

Thence, N. 0°18' W.

38.30 The SW. base of a volcanic bench, bears NW. and SE.

40.57 Proportionate distance: find no trace of the cor. secs. 4, 5, 8, and 9.

Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in ground and in a large mound of stone, for cor. secs. 4, 8, and 9, with brass cap marked

T19S	R8W	
S5		S4
S8		S9
1940		

deposit a volcanic stone, 22 x 12 x 8 ins., at base of post, marked

Land, nearly level desert.  
Soil, sandy clay; rocky at N. end of mile; 3rd rate.  
No timber.  
Undergrowth, scattered greasewood and shadscale.  
Fair grazing land.

DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 8 W.

Chains

From the cor. of secs. 3, 4, 9, and 10.

S. 89°51' W., bet. secs. 4 and 9.


Over rolling top of bench through short undergrowth.

12.30 Shallow swale, drains S., about 4.00 chs. dist. to S. rim of bench.

40.90 The 1/4 sec. cor., a juniper post, 3 ft. long, 3 ins. diam., loosely set, upon which I find dim scribe marks. Cor. has no accessories.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with the original cor. monument deposited alongside, for 1/4 sec. cor., with brass cap marked.



1940

mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor. raise a

Thence, N. 89°33' W.

27.80 The SW. rim of top of bench, bears NW. and SE.; descend steep rocky SW. slope, 190 ft. to

40.53 The cor. of secs. 4, 5, 8, and 9.

Land, rolling top of bench and steep W. slope.

Soil, shallow sand clay on top of bench and rocky on slopes; 4th rate.

No timber.

Undergrowth, shadscale and greasewood.

Good grazing land.

From the cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the township, an iron post, 2 ins. diam., set, marked, and witnessed, as described in the official record of the survey of T. 18 S., R. 8 W., Group No. 207, Utah.


S. 0°05' W., bet. secs. 4 and 5.

Ascend gradual W. slope of rolling bench land, through short undergrowth.

3.00 Small rim of low bench, bears N. 20° E. and S. 20° W.; thence over top of bench.

40.35 Proportionate distance; find no trace of the 1/4 sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 15 ins. in the ground to solid rock and in a large mound of stone, for 1/4 sec. cor., with brass cap marked



1940

volcanic stone, 15 x 8 x 4 ins., at base of post, marked X. deposit a

## DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 8 W.

Chains

64.50 The SW. rim of bench, bears NW. and SE.; descend rocky slope, 190 ft. to

80.92 The cor. of secs. 4, 5, 8, and 9.

Land, rolling top of bench and steep slopes.

Soil, shallow sandy clay and rocky; 3rd and 4th rates.

No timber.

Undergrowth, shadscale, yellow top, and a few greasewood

Fair grazing land.

From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the township.

N. 0°21' W., bet. secs. 31 and 32.

Over nearly level desert land, through medium dense greasewood from 1 to 3 ft. high.

0.20 Old irrigation ditch, 10 lks. wide, drains NW.

1.70 Junction of road from the N. with old unused road bearing NE. and SW.

22.50 The SW. cor. of wire fence bearing N. and E., bears E. line, 30 lks. dist.

40.31 Proportionate distance; find no trace of the  $\frac{1}{4}$  sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked

	$\frac{1}{4}$	
S31		S32
	1940	

raise a small mound of stone around post and deposit glass at the base of same.

From this cor., the junction of fence from the E. with fence bearing N. and S., bears E., 26 lks. dist.

80.62 Proportionate distance; find no trace of the cor. secs. 29, 30, 31, and 32.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in ground, for cor. secs. 29, 30, 31, and 32, with brass cap marked

T19S	R8W.	
S30		S29
S31		S32
	1940	

raise a small mound of stone around the cor. monument and deposit glass at the base of same.

Cor. set at the forks of roads bearing E., N. 30° W., and S. 70° W.

From cor., the SW. cor. of fence bearing E. and N., bears NE., 75 lks. dist., and the NW. cor. of fence bearing E. and S., bears SE., 63 lks. dist.

DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 8 W.

Chains

From cor., an old ditch draining W., bears S., 40 lks. dist.

Land, nearly level.  
Soil, alkali clay; 3rd rate.  
No timber.

Undergrowth, greasewood, and scattered shadscale and rabbit brush.  
Fair grazing land.

From the cor. of secs. 28, 29, 32, and 33.

N. 89°45' W., bet. secs. 29 and 32.

Over nearly level land, through scattered short undergrowth, along road in lane bearing westerly from the S.

35.00 Top of slight rise, bears N., about 2.00 chs. dist. to the S. base of a volcanic butte.

40.29 Proportionate distance; find no trace of the 1/4 sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for 1/4 sec. cor., with brass cap marked

1/4 S29  
S32  
1940

round of stone, 2 ft. base, 1 1/2 ft. high, N. of post, and deposit glass at the base of same. raise a

From this cor., the E. and W. fence on N. side of lane, bears N., 35 lks. dist., and the E. and W. fence on S. side of lane, bears S., 55 lks. dist. The W. edge of top of butte, bears N. 2° E., about 10.00 chs. dist.

80.59 The cor. of secs. 29, 30, 31, and 32.

Land, nearly level.  
Soil, heavy clay; rocky surface on central portion of mile; 3rd rate.  
No timber.  
Undergrowth, greasewood, shadscale, and salt brush.  
Fair grazing land.

From the cor. of secs. 30 and 31, on the W. bdy. of the township.

S. 89°41' E., bet. secs. 30 and 31.

Over nearly level desert through dense short undergrowth.

40.02 Proportionate distance; find no trace of the 1/4 sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for 1/4 sec. cor., with brass cap marked

1/4 S30  
S31  
1940

DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 8 W.

- Chains Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of and deposit glass at the base of same.
- From this cor., the SW. cor. of an old wire fence, bearing E. and N., bears N.  $70^{\circ}$  E., 78 lks. dist.
- 60.70 The SE. cor. of fence bearing N. and W., bears N., 40 lks. dist.
- 79.50 Ditch, 30 lks. wide, drains NW.
- 80.40 The cor. of secs. 29, 30, 31, and 32.
- Land, nearly level.  
Soil, heavy clay; 3rd rate.  
No timber.  
Undergrowth, greasewood, rabbit brush, and shadscale.  
Fair grazing land.

N.  $0^{\circ}26'$  E., bet. secs. 29 and 30.

Over nearly level land through dense short undergrowth. Line follows along W. side of fence bearing nearly parallel to line.

- 19.90 The NW. cor. of fences bearing E. and S., bears E., about 40 lks. dist.
- 40.31 The  $\frac{1}{4}$  sec. cor., a juniper post,  $2\frac{1}{2}$  ft. long, 3 ins. diameter, squared on two sides, firmly set, and no visible marks remaining on post. Cor. had no accessories.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in ground, with the original cor. monument deposited along for  $\frac{1}{4}$  sec. cor., with brass cap marked

	$\frac{1}{4}$	
S30		S29
1940		

raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Thence, N.  $0^{\circ}11'$  W.

- 31.70 Leave nearly all greasewood and continue through shadscale.
- 40.20 The cor. of secs. 19, 20, 29, and 30, a juniper post, 3 ft. long, 2 ins. diam., squared at top and upon which I find dim scribe marks. Cor. has no accessories.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in ground, with the original cor. monument deposited along for cor. secs. 19, 20, 29, and 30, with brass cap marked

T19S	R8W	
.S19		.S20
S30		S29
1940		

raise a

DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 8 W.

Chains

mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.  
Land, nearly level desert.  
Soil, heavy alkali clay; 3rd rate.  
No timber.  
Undergrowth, greasewood and shadscale.  
Fair grazing land.

From the cor. of secs. 20, 21, 28, and 29.

N. 89°49' W., bet. secs. 20 and 29...

Over nearly level land, through scattered salt brush.

- 1.00 Enter arm of dry lake bed, bears NE. and SW.
- 4.10 Leave same, bears N., and S. for about 6.00 chs. dist., thence NE; thence over desert land through scattered shadscale.
- 15.80 Dim trace of road, bears NW. and S. 10° E.
- 40.10 Proportionate distance; find no trace of the 1/4 sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for 1/4 sec. cor., with brass cap marked

$$\begin{array}{r} S20 \\ \frac{1}{4} \\ \hline S29 \\ 1940 \end{array}$$

raise a mound of stone, 3 ft. base, 1 1/2 ft. high, N. of cor.

- 80.19 The cor. of secs. 19, 20, 29, and 30.

Land, nearly level.  
Soil, clay and sand; 3rd rate.  
No timber.  
Undergrowth, shadscale and salt brush.  
Fair grazing land.

From the cor. of secs. 19 and 30, on the W. bdy. of the township.

S. 89°41' E., bet. secs. 19 and 30.

Over level desert land through undergrowth of greasewood.

- 4.50 Leave greasewood and enter shadscale.
- 40.41 Proportionate distance; find no trace of the 1/4 sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for 1/4 sec. cor., with brass cap marked

$$\begin{array}{r} S19 \\ \frac{1}{4} \\ \hline S30 \\ 1940 \end{array}$$

raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

DEPENDENT RESURVEY OF SUBDIVISION, T. 19S., R. 18W.

Chains

and

71.70 Dim old road, bears NE. and SW.

81.02 The cor. of secs. 19, 20, 29, and 30.

Land, level desert.  
Soil, clay and sandy clay; 3dr rate.  
No timber.  
Undergrowth, shadscale and greasewood.  
Fair grazing land.

N. 0°32' W., bet. secs. 19 and 20.

Over nearly level land through short undergrowth.

13.50 Dim old road, bears NW. and SE.

17.30 Dim old road, bears N. 20° E. and S. 20° W.

40.52 The  $\frac{1}{4}$  sec. cor., a juniper post, 2 ft. long, 3 ins. square, loosely set, upon which I find dim scribe marks. Cor. has no accessories.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with the original cor. monument deposited alongside for  $\frac{1}{4}$  sec. cor., with brass cap marked

	$\frac{1}{4}$	
S19		S20
1940		

raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Thence, N. 0°24' W.

32.50 Old wagon road, bears NE. and S. 70° W.

40.29 The cor. of secs. 17, 18, 19, and 20, a juniper post, 3 ft. long, 4 ins. square, firmly set, upon which I find dim scribe marks. Cor. has no accessories.

At the cor. point:

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with the original cor. monument deposited alongside for cor. secs. 17, 18, 19, and 20, with brass cap marked

T19S		R8W
S18		S17
S19		S20
1940		

deposit glass at the base of the post.

Land, nearly level desert.  
Soil, heavy alkali clay; 3rd rate.  
No timber.  
Undergrowth, shadscale.  
Fair grazing land.

DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 8 W.

Chains

From the cor. of secs. 16, 17, 20, and 21.

N. 89°34' W., bet. secs. 17 and 20.

Across dry lake or salt pond, with salt crust from about 3 to 4 inches thick.

23.50 The W. edge of dry lake or salt pond, bears S., and N. about 6.00 chs. dist., thence NW; thence over nearly level desert land with short undergrowth.

40.26 Proportionate distance; find no trace of the 1/4 sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for 1/4 sec. cor., with brass cap marked

S17

1/4           
S20

1940

raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

40.70 Dim road, bears N. and S. 10° E.

58.80 Dim road, bears N. 20° E. and S. 20° W.

72.70 Wagon road, bears NE. and SW.

80.52 The cor. of secs. 17, 18, 19, and 20.

Land, nearly level desert and lake bed.  
Soil, heavy clay, sandy clay, and wet clay saturated with salt; 3rd and 4th rates.  
No timber.  
Undergrowth, shadscale on portion of mile.  
Fair grazing land.

From the cor. of secs. 13 and 19, on the W. bdy. of the township.

S. 89°49' E., bet. secs. 18 and 19.

Over nearly level desert land through patches of grass and shadscale.

12.00 Enter medium dense greasewood and shadscale.

15.50 Wagon road, bears NE. and SW.

23.20 Wash, 40 lks. wide, 3 ft. deep, drains N.

40.27 Proportionate distance; find no trace of the 1/4 sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for 1/4 sec. cor., with brass cap marked

S18

1/4           
S19

1940

raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

80.79 The cor. of secs. 17, 18, 19, and 20.

DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 8 W.

Chains

Land, nearly level.  
Soil, sandy clay; 3rd rate.  
No timber.  
Undergrowth, shadscale, greasewood, and grass.  
Fair grazing land.


N. 0°32' W., bet. secs. 17 and 18.

Over nearly level desert land, through scattered underg

27.50 Wagon road, bears N. 60° E. and S. 60° W.

39.60 Top of low rise along S. side of lake bed, bears N. 80°  
and S. 80° E.; descend gradually towards edge of lake be

40.39 Proportionate distance; find no trace of the  $\frac{1}{4}$  sec. cor  
Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in t  
ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked




raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, W. of cor., and deposit glass at the base of post.

43.00 Enter S. edge of dry lake bed void of vegetation; thin crust of alkali and salt over portions of surface.

80.78 Proportionate distance; find no trace of the cor. secs. 7, 8, 17, and 18.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in t ground, for cor. secs. 7, 8, 17, and 18, with brass cap marked



deposit glass at the base of the post.

Land, nearly level desert and dry lake bed.  
Soil, sandy clay and wet heavy clay; 3rd and 4th rates.  
No timber.  
Undergrowth, shadscale on portion of mile.  
Fair grazing land on portion of mile.

From the cor. of secs. 8, 9, 16, and 17.

N. 89°26' W., bet. secs. 8 and 17.

Over nearly level desert land through short undergrowth.

1.70 Wagon road, bears NE. and SW.

15.80 Old road, bears N. and S.

DEPENDENT RESERVE OF SUBDIVISION, T. 19 S., R. 8 W.

Chains

- 17.10 Bank, 12 ft. high, on E. side of dry lake bed, bears N. 10° W. and S. 10° E.
- 20.40 Enter dry lake bed void of vegetation, bears with bank.
- 40.31 Proportionate distance; find no trace of the 1/4 sec. cor.  
Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for 1/4 sec. cor., with brass cap marked

S8  
 1/4  
 S17

1940

deposit glass at the base of the post.

- 80.61 The cor. of secs. 7, 8, 17, and 18.  
Land, nearly level desert and dry lake bed.  
Soil, sandy clay and wet heavy clay; 3rd and 4th rates.  
No timber.  
Undergrowth, shadscale.  
Fair grazing land on E. portion of mile.

From the cor. of secs. 7 and 18, on the W. bdy. of the township.

East, bet. secs. 7 and 18.

Over nearly level desert land, through medium dense short undergrowth.

- 32.10 Wash, 30 lks. wide, 2 ft. deep, drains NW. from the S.
- 40.09 Proportionate distance; find no trace of the 1/4 sec. cor.  
Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for 1/4 sec. cor., with brass cap marked

S7  
 1/4  
 S18

1940

raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

- 65.80 Enter dry bed of old lake void of vegetation, bears NW. and SE.

- 80.48 The cor. of secs. 7, 8, 17, and 18.  
Land, nearly level desert and dry bed of lake.  
Soil, sandy clay and wet heavy clay saturated with alkali; 3rd and 4th rates.  
No timber.  
Fair grazing land.

N. 0°32' W., bet. secs. 7 and 8.

Across dry bed of lake void of vegetation.

DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 8 W.

Chains

40.39

Proportionate distance; find no trace of the  $\frac{1}{4}$  sec. cor.  
Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked

$\frac{1}{4}$   
S7 | S8  
1940

deposit

glass at the base of the post.

80.78

Proportionate distance; find no trace of the cor. secs.  
5, 6, 7, and 8.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the  
ground, for cor. secs. 5, 6, 7, and 8, with brass cap marked

T19S | R8W  
S6 | S5  
S7 | S8  
1940

raise a

mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor., and  
deposit glass at the base of post.

Land, level bed of old lake.  
Soil, wet alkali clay; 4th rate.  
No timber.  
No vegetation.  
Poor grazing land.

From the cor. of secs. 4, 5, 8, and 9.

N.  $89^{\circ}46'$  W., bet. secs. 5 and 8.

Descend gradual SW. slope of bench.

0.50

Base of rocky volcanic bench, bears NW. and SE.; thence  
over nearly level desert land, through short undergrowth

25.20

Dim road, bears NW. and S.  $10^{\circ}$  E.

35.50

Top of slight sandy rise, bears NW. and SE.

40.46

The  $\frac{1}{4}$  sec. cor., a juniper post, 3 ft. long, 4 ins. diam.  
loosely set, upon which I find dim scribe marks. Cor. has  
no accessories.

At the cor. point:

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the  
ground, with the original cor. monument deposited alongside  
for  $\frac{1}{4}$  sec. cor., with brass cap marked

S5  
 $\frac{1}{4}$   
S8

1940

deposit

glass at the base of the post.

DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 8 W.

Chains

Thence, N. 89°07' W.

13.00 Enter dry lake bed void of vegetation, bears NW. and SE.

40.16 The cor. of secs. 5, 6, 7, and 8.

Land, nearly level desert and lake bed.

Soil, sandy clay and heavy wet clay; 3rd and 4th rates.

No timber.

Undergrowth, shadscale.

Fair grazing land.

From the cor. of secs. 6 and 7, on the W. bdy. of the township:

N. 89°30' E., bet. secs. 6 and 7.

Across bed of dry lake void of vegetation.

39.77 Proportionate distance; find no trace of the 1/4 sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for 1/4 sec. cor., with brass cap marked

S6  
1/4

S7

1940

raise a small mound of stone N. of cor., and deposit glass at the base of post.

79.85 The cor. of secs. 5, 6, 7, and 8.

Land, level bed of old lake.

Soil, wet alkali clay; 4th rate.

No timber.

No vegetation.

Poor grazing land.

From the cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the township, an iron post, 2 ins. diam., set, marked, and witnessed, as described in the official record of the survey of T. 18 S., R. 8 W., Group No. 207, Utah.

S. 0°05' E., bet. secs. 5 and 6.

Over level desert land, through scattered undergrowth.

17.50 Enter dry bed of old lake void of vegetation, bears NW. and S. 30° E.

40.50 Proportionate distance; find no trace of the 1/4 sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for 1/4 sec. cor., with brass cap marked

1/4

S6 | S5

1940

raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor., and

## DEPENDENT RESURVEY OF SUBDIVISION, T. 19 S., R. 8 W.

Chains

deposit glass at the base of the post.

80.90 The cor. of secs. 5, 6, 7, and 8.

Land, nearly level desert and dry bed of lake.

Soil, sandy clay and wet alkali clay; 3rd and 4th rates.

No timber.

Undergrowth, scattered salt brush on N. portion of mile.

Poor grazing land.

## DEPENDENT RESURVEY OF MEANDER LINES, T. 19 S., R. 8 W.

Reestablishment of surveys executed by  
Julien Batsman in 1871.

Note: The lake as shown on the original plat of this township, dated February 26, 1872, and which the following meanders formed the western side, has dried up. The shoreline at the present date is indefinite in most places.

From the meander cor. of fractional secs. 25 and 30, on the E. bdy. of the township.

Thence with <sup>adjusted</sup> meanders in sec. 25, along the W. side of dry lake, through scattered undergrowth.

N. 79°33' W., 20.36 chs.

N. 22°37' W., 60.97 chs.

N. 0°53' W., 5.26 chs. The restored meander cor. of fractional secs. 24 and 25.

Land, nearly level.

Soil, alkali clay; 3rd rate.

Undergrowth, scattered salt brush.

Thence in sec. 24.

N. 6°53' W., 81.10 chs. At 36.00 chs., enter low bench, bears N. and S.  
At 66.00 chs., leave bench, bears NW. and SE.  
At end of course, the restored meander cor. fractional secs. 13 and 24.

Land, nearly level alkali clay flat and bench.

Soil, alkali clay and sandy clay; 3rd rate.

Undergrowth, scattered salt brush and shadscale.

Thence in sec. 13.

N. 9°51' W., 46.36 chs.

N. 53°34' W., 25.85 chs. At 19.20 chs., telegraph line.  
At 20.70 chs., Union Pacific railroad track, bears N. 25°57' E., and S. 25°57' W.  
At 22.10 chs., Telegraph line.  
At 22.40 chs., road, parallel to railroad.  
At end of course, the restored meander cor. of fractional secs. 13 and 14.

## DEPENDENT RESURVEY OF MEANDER LINES, T. 19 S., R. 8 W.

Land, level.  
Soil, alkali clay and sandy clay; 3rd rate.  
Undergrowth, salt brush and shadscale.

Thence in sec. 14.

N.  $76^{\circ}52'$  W., 42.33 chs.

N.  $45^{\circ}42'$  W., 14.38 chs. The restored meander cor. of  
secs. 11 and 14.

Land, level.  
Soil, alkali clay; 3rd rate.  
Undergrowth scattered salt brush.

Thence in sec. 11.

N.  $0^{\circ}31'$  E., 25.22 chs. At 5.50 chs., old drainage canal,  
drains  $N.80^{\circ}W.$   
At 12.00 chs., old road, bears  
 $N.10^{\circ}E.$  and  $S.10^{\circ}W.$

N.  $68^{\circ}15'$  E., 54.63 chs. At 3.50 chs. old road, bears  
 $N.10^{\circ}E.$  and  $S.10^{\circ}W.$   
At end of course, the original  
meander cor. of fractional secs.  
11 and 12.

Land, level.  
Soil, alkali clay and sandy clay; 3rd rate.

Thence in sec. 12.

N.  $57^{\circ}58'$  E., 30.09 chs. At 30.00 chs. dim road, bears  
 $N.70^{\circ}W.$  and  $S.70^{\circ}E.$

N.  $42^{\circ}18'$  E., 25.59 chs. At 1.00 chs. S. rim of bench,  
40 ft. high, bears NW., and extends  
 $S.75^{\circ}E.$  for 3 chs. to SE. point.  
At 12.00 chs. N. edge of top,  
bears  $N.20^{\circ}W.$  and  $S.20^{\circ}E.$   
At 15.50 chs. N. base of same.  
At end of course, the restored  
meander cor. of fractional secs.  
1 and 12.

Land, nearly level and point of rocky bench.  
Soil, sandy clay and rocky clay; 3rd and 4th rates.  
Undergrowth, salt brush and shadscale.

Thence in sec. 1.

N.  $41^{\circ}31'$  E., 8.05 chs.

N.  $79^{\circ}21'$  E., 32.53 chs. At 8.60 chs. improved road,  
parallel to railroad.  
At 9.00 chs. telegraph line,  
parallel to railroad.  
At 11.00 chs. Union Pacific rail-  
road, single track, bears  $N.25^{\circ}57'$   
 $E.$  and  $S.25^{\circ}57'$  W.  
At 12.90 chs. telegraph line,  
parallel to railroad.

## DEPENDENT RESURVEY OF MEANDER LINES, T. 19 S., R. 8 W.

At end of course, the original meander cor. of fractional sec 1 and 6, on E. bdy. of the township.

Land, level.

Soil, alkali clay; 3rd rate.

Undergrowth, scattered salt brush.

## GENERAL DESCRIPTION OF T. 19 S., R. 8 W.

This township consists principally of nearly level valley or desert lands and level alkali clay flats, lying at an elevation of about 4500 feet above sea level. The south end of a low volcanic bench rising from 100 to 200 feet above the surrounding land, extends into the north-central part, covering all or portions of sections 1, 2, 3, 4, 9, 10, and 11. The rim of this bench in most places is abrupt and rocky. A black volcanic butte about 200 feet high, is located in the S $\frac{1}{2}$  of section 29. A low volcanic hill, is located in the E $\frac{1}{2}$  of section 23. In the central and northwest portions are large barren alkali clay flats which evidently were beds of former shallow lakes. In portions of sections 17, 20, and 21, there is a shallow salt pond, with a salt crust from 1 to 4 inches thick. The eastern part is the bed of a former shallow lake which is now only a barren alkali or salt flat. There is no distinct shore line along the meander line or any marked difference in the elevation between the lake bed and the surrounding land.

The soil is principally a heavy clay or sandy clay, containing considerable alkali, or the major portion of the township, and may be classified as 2nd to 4th rates; on volcanic bench, it is a light shallow sand or sandy clay with outcroppings of rock. Shell marl is found on the bench, and small pits have been opened up in sections 3 and 11.

The township, in general, is covered with a scattered to medium growth of greasewood, shadscale, salt brush, and weeds, with some sagebrush on top of the bench. Considerable salt grass is found in the southwest portion.

The main line of the Union Pacific Railroad, between Salt Lake City, Utah, and Los Angeles, California, crosses the east portion of the township, from section 1 to section 35. The Jerome siding is located in section 12, and the Clear Lake station and section houses, are located near center of section 34. A graded county road between Dese and Black Rock, parallels the west of the railroad. A graded road bears easterly from the Clear Lake station to Fillmore, Utah, leaving the township on the south boundary of section 35. There are several other unimproved roads extending through the township.

At one time, there were several families living in the W $\frac{1}{2}$  of section 34, adjacent to Clear Lake station, and there had been approximately 1000 acres of land under cultivation and irrigated, all now abandoned. These lands are located in sections 27 to 34 inclusive. Numerous ditches and old fences extend through the above sections. The water for these lands, was brought through canals from large springs and a lake, located in T. 20 S., R. 7 W., about 8 miles distant. Farming apparently was not a success, due no doubt to the excessive amount of alkali in the soil and the lack of drainage.

**GENERAL DESCRIPTION OF, T. 19 S., R. 8 W.**

The township is chiefly valuable for winter grazing of sheep and cattle, although the salt grass found in the southwest portion affords fair grazing for cattle during the summer months

With the exception of railroad employees, consisting of a section crew and station help, there are no settlers living in the township. There is no water, nor indications of mineral, oil, or coal within the township. The nearest post office is at Deseret, Utah, about 13 miles north-easterly from Clear Lake station.

The magnetic declination was not taken on account of a defective needle.

**Volume**

**#**

**R0556**



## CERTIFICATE OF SURVEYOR

I, Andrew Nelson, \_\_\_\_\_, HEREBY CERTIFY upon honor that, pursuant of special instructions bearing date of the 7th day of April 1939 received from the district cadastral engineer for Utah, with assignment instructions dated May 9, 1940, I have ~~surveyed~~ made a dependent resurvey of the west boundary of T. 19 S., R. 7 W.; the west boundary or Second Guide Meridian West, the south boundary, and subdivisional lines and meanders of T. 19 S., R. 8 W., of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes. Salt Lake City, Utah.  
January 27, 1942

Andrew Nelson  
 Assistant Cadastral Engineer  
 (Formerly Surveyor)

## CERTIFICATE OF APPROVAL

(OFFICE OF SUPERVISOR OF SURVEYS,

Denver, Colorado, October 31, 1942.

The foregoing field notes of the ~~survey of~~ dependent resurvey of the west boundary of T. 19 S., R. 7 W.; the west boundary or Second Guide Meridian West, the south boundary, and subdivisional lines and meanders of T. 19 S., R. 8 executed by Andrew Nelson, Surveyor under special instructions dated April 7, 1939, and assignment instructions dated May 9, 1940, having been critically examined, and the necessary corrections made prior to their certification by the engineer, the said field notes, and the survey therein described, are hereby approved.

W. H. [Signature]  
 Supervisor of Surveys.

## CERTIFICATE OF TRANSCRIPT

I certify that the foregoing transcript of the field notes of the above-described surveys in \_\_\_\_\_ is a true copy of the original field notes on file in the public survey office.

\_\_\_\_\_  
 Supervisor of Surveys.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Original

# FIELD NOTES

of the

Dependent Resurvey

of

North, South, East, and West Boundaries

and the

Subdivision

of

T. 19 S., R. 19 W.

Of the Salt Lake Meridian,

the State of Utah

EXECUTED BY

Andrew Nelson, Cadastral Surveyor

My special instructions dated April 30, 1956, which provided

the surveys included under Group No. 416, approved May 7, 1956

assignment instructions dated June 12, 1956.

Survey commenced June 13, 1956

Survey completed July 11, 1956

# INDEX DIAGRAM

Township 19. S., Range 19 W.

23 13 6	22 52 8	21 45 4	21 40 3	20 35 2	19 29 1 19
52 11 7	51 51 8	45 44 9	40 39 10	34 34 11	29 28 12 17
51 10 18	50 50 17	44 44 16	39 38 15	33 33 14	28 27 18 16
49 9 19	49 48 20	43 43 21	38 37 22	32 32 23	26 26 24 15
48 8 30	48 47 29	42 42 28	37 36 27	31 31 26	25 24 25 14
47 7 31	46 46 32	41 41 33	36 35 34	30 30 35	24 23 36 14
6	5	4	3	2	1

## Dependent Resurvey of T. 19 S., R. 19 W., S.L.M.

Chains

The south, west, east and north boundaries, and subdivisional lines were surveyed by Andrew J. Stewart, Jr., in 1882; the south and west boundaries were resurveyed by Robert E. L. Collier, in 1895.

The following field notes are those of the dependent resurvey of the south, west, east and north boundaries, and subdivisional lines of T. 19 S., R. 19 W., Salt Lake Meridian, Utah.

The survey was executed with a W. and L. E. Gurley solar transit, serial number 491037, which conforms to the standard instrumental specifications of the Bureau of Land Management. The instrument was in good condition and was maintained in precise adjustment throughout the progress of the survey.

The measurements were made with a Chicago narrow steel tape, 8 chains in length, graduated to tenths of links for the first link, to links for the next 99 links, and thereafter at intervals of 10 links. The tape was tested by comparison with a one-chain standard steel tape and found correct. The measurements were made on the slope and the vertical angle of each interval was ascertained by two clinometers in good adjustment. The slope distances were properly reduced to horizontal equivalents which are entered in the field note record.

The geographic position for the southeast corner of this township is in latitude  $39^{\circ} 06' 16''$  N. and longitude  $113^{\circ} 55' 26''$  W., as determined by traverse from Nevada and Utah boundary monument (M.P. 150).

The directions of the lines of survey were determined generally by sustained angulation carried forward from observation on Polaris for meridian. The magnetic declination was read at a number of stations throughout the township and the average of several readings was found to be  $17^{\circ}$  E.

## Dependent Resurvey of the South Bdy., T. 19 S., R. 19 W.

Reestablishment of the survey executed  
by Andrew J. Stewart Jr., in 1882;  
Resurveyed by Robert E. L. Collier,  
in 1895.

Beginning at the corner of Tps. 19 and 20 S., Rs. 18 and 19 W., monumented by a blue limestone  $15 \times 12 \times 6$  ins., firmly set, marked with 6 notches on 4 edges.

At the corner point

Set an iron post, 36 ins. long, 3 ins. diam., 24 ins. in the ground, with brass cap mkd.

T19S  
R19W | R18W  
S36 | S31  
S 1 | S 6  
T20S  
1956

Bury original stone monument alongside and raise a mound of stone around the post.

S.  $88^{\circ} 12'$  W., along the S. bdy. of sec. 36.

Dependent Resurvey, South Bdy., T. 19 S., R. 19 W.

Chains

Desc. 80 ft. over W. slope to  $\frac{1}{4}$  cor.  
Small wash, draining SW.

7.45

30.00

Small wash, draining SW.

40.97

Point for the  $\frac{1}{4}$  sec. cor. of sec. 36; at proportionate distance;  
there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground,  
with brass cap mkd.

$\frac{1}{4}$  S 36

1956

Deposit broken glass alongside the iron post.

51.10

Road, bears N. 38° E. and S. 38° W.; base of descent, bears NW. and  
SE., thence over gently rolling land.

65.60

Road, bears NW. and SE.

79.88

The closing cor. of secs. 1 and 2, T. 20 S., R. 19 W., monumented  
by a blue limestone 14x10x8 ins., mkd. cc on south face, 5 grooves  
on west and 1 groove on east face.

At the corner point

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground,  
with brass cap mkd.

T19S R19W

S36

S 2 | S 1

C C

T20S R19W

1956

Deposit original stone monument alongside iron post.

Deposit broken glass alongside iron post.

81.94

The cor. of secs. 35 and 36, monumented by a deposit of charcoal.

At the corner point

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground,  
with brass cap mkd.

T19S R19W

S35 | S36

S 2

T20S

1956

Deposit broken glass alongside iron post.

Land, level and gently rolling.

Soil, sandy loam and stony.

No timber; undergrowth, greasewood and shadscale.

N. 89° 31' W., along the S. bdy. of sec. 35.

Over level land.

32.40

Wash, 6 ft. deep, 40 lks. wide, drains NW.

Dependent Resurvey, South Bdy., T. 19 S., R. 19 W.

Chains

40.20 Point for the 1/4 sec. cor. of sec. 35, at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground, with brass cap mkd.

1/4 S 35

1956

Deposit broken glass alongside iron post.

Water well, bears N. 13° 56' W., 21.68 chs. dist.

51.90 Road, bears N. and S.

78.02 The closing cor. of secs. 2 and 3, T. 20 S., R. 19 W., monumented by a blue limestone, 12x10x9 ins., mkd. cc on south face, 4 grooves on west and 2 grooves on east face.

At the corner point

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground, with brass cap mkd.

T19S R19W

S35

S 3 | S 2

C C

T20S R19W

1956

Bury original stone monument alongside iron post.

Deposit broken glass at base of iron post.

80.40 The cor. of secs. 34 and 35, monumented by a deposit of charcoal.

At the corner point

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground, with brass cap mkd.

T19S R19W

S34 | S35

S 3

T20S R19W

1956

Deposit broken glass alongside iron post.

Land, level and gently rolling.

Soil, sandy loam.

No timber; undergrowth, greasewood and shadscale.

N. 89° 01' W., along the south bdy. of sec. 34.

Over level land.

5.70 Wash, 5 ft. deep, 80 lks. wide, drains N.

40.41 Point for the 1/4 sec. cor. of sec. 34, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground, with brass cap mkd.

Dependent Resurvey, South Bdy., T. 19 S., R. 19 W.

Chains	
63.70	<p style="text-align: center;"><u>1/4 S 34</u> 1956</p> <p>Deposit broken glass alongside iron post.</p> <p>Road, bears N. and S.</p>
77.62	<p>The closing cor. of secs. 3 and 4, T. 20 S., R. 19 W., monumented a stone, 16x12x5 ins., mkd. cc on south face, 3 grooves on west and 3 grooves on east faces.</p> <p>At the corner point</p> <p>Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground with brass cap mkd.</p> <p style="text-align: center;">T19S R19W <u>S34</u> S 4   S 3 C C T20S R19W 1956</p> <p>Deposit original stone monument alongside iron post.</p> <p>Deposit broken glass alongside iron post.</p>
80.82	<p>Point for the cor. of secs. 33 and 34, mkd. by charcoal deposit.</p> <p>At the corner point</p> <p>Set an iron post, 36 ins. long, 3 ins. diam., 24 ins. in the ground with brass cap mkd.</p> <p style="text-align: center;">T19S R19W <u>S33   S34</u> S 4 T20S R19W 1956</p> <p>Deposit broken glass alongside iron post.</p> <p>Land, level and gently rolling. Soil, sandy clay. No timber; undergrowth, greasewood and shadscale.</p>
33.70	<p>S. 89° 59' W., along the south bdy. of sec. 33.</p> <p>Over level land.</p> <p>Ditch, drains NE.</p>
38.60	<p>Same ditch as above, on curve from SW., and draining SE.</p>
40.24	<p>Point for the 1/4 sec. cor. of sec. 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground with brass cap mkd.</p> <p style="text-align: center;"><u>1/4 S 33</u> 1956</p> <p>Deposit broken glass alongside iron post.</p>

Dependent Resurvey, South Bdy., T. 19 S., R. 19 W.

Chains  
77.20

The closing cor. of secs. 4 and 5, T. 20 S., R. 19 W., monumented by a stone, 15x13x4 ins., mkd. cc on south face, 2 grooves on west and 4 grooves on east face.

At the corner point

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground, with brass cap mkd.

T19S R19W  
S33  
S 5 | S 4  
C C  
T20S R19W  
1956

Deposit original stone monument alongside iron post.

Deposit broken glass alongside iron post.

80.48

The cor. of secs. 32 and 33, monumented by a deposit of charcoal.

At the corner point

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground, with brass cap mkd.

T19S R19W  
S32 | S33  
S 5  
T20S R19W  
1956

Deposit broken glass alongside iron post.

Land, level.

Soil, sandy.

No timber; undergrowth, greasewood and shadscale.

S. 89° 38' W., along the south bdy. of sec. 32.

Over level land.

40.735

Point for the 1/4 sec. cor. of sec. 32, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground, with brass cap mkd.

1/4 S 32  
1956

Deposit broken glass alongside iron post.

77.10

The closing corner of secs. 5 and 6, T. 20 S., R. 19 W., monumented by a quartzite stone, 13x8x4 ins., mkd. cc on south face, no other markings.

At the corner point

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground, with brass cap mkd.

Chains

81.47

T19S R19W

S32

S 6 | S 5

C C

T20S R19W

1956

Deposit original stone alongside iron post.

Deposit broken glass alongside iron post.

The cor. of secs. 31 and 32, monumented by a deposit of charcoal.

At the corner point

Set an iron post, 36 ins. long, 3 ins. diam., 24 ins. in the ground with brass cap mkd.

T19S R19W

S31 | S32

S 6

T20S R19W

1956

Deposit broken glass alongside iron post.

Land, level.

Soil, sandy.

No timber; undergrowth, greasewood and shadscale.

40.61

S. 89° 35' W., along the south bdy. of sec. 31.

Over level land.

Point for the  $\frac{1}{2}$  sec. cor. of sec. 31, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground, with brass cap mkd.

 $\frac{1}{2}$  S 31

1956

Deposit broken glass alongside iron post.

74.50

Road, Gandy and Garrison, bears N. 2° 56' E. and S. 2° 56' W.

80.82

The cor. of Tps. 19 and 20 S., Rs. 19 and 20 W., monumented by a wood stake.

At the corner point

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground, and in a mound of stone, to top of post, with brass cap mkd.

T19S

R20W R19W

S36 | S31

S 1 | S 6

T20S

1956

Raise a mound of stone, south of corner.

Dependent Resurvey, South Bdy., T. 19 S., R. 19 W.

Chains

Deposit broken glass alongside iron post

Land, level.

Soil, sandy.

No timber; undergrowth, greasewood and shadscale

Dependent Resurvey, West Bdy., T. 19 S., R. 19 W.

Reestablishment of the survey executed by Andrew J. Stewart Jr., in 1882; Resurveyed by Robert E. L. Collier, in 1895.

N. 0° 06' E., along the west bdy. of sec. 31.

Over level land.

40.00

The 1/4 sec. cor. of sec. 36, T. 19 S., R. 20 W., monumented by a stone, 15x10x3 ins., unmarked.

At the corner point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a mound of stone to top of post, with brass cap mkd.



Deposit original stone alongside iron post.

Deposit broken glass alongside iron post.

40.38

The 1/4 sec. cor. of sec. 31, monumented by a stone, 18x2x2 ins., unmarked, found buried in trace of old mound of earth.

At the corner point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.



Deposit original stone alongside iron post.


Deposit broken glass alongside iron post.

80.00

The cor. of secs. 25 and 36, T. 19 S., R. 20 W., monumented by a quartzite stone, 10x6x4 ins., firmly set, mkd. 5 notches on south and 1 notch on north face.

At the corner point

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.



Deposit original stone alongside iron post.

Chains

Deposit broken glass alongside iron post.

80.82

The cor. of secs. 30 and 31, monumented by a small unmarked stone.

At the corner point

Set an iron post, 36 ins. long, 3 ins. diam., 24 ins. in the ground and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd.

T19S T19S

S25 | S30

| S31

R20W R19W

1956

Deposit original stone alongside iron post.

Deposit broken glass alongside iron post.

Land, level.

Soil, sandy and stony.

No timber; undergrowth, greasewood and shadscale.

N. 0° 07' E., along the west bdy. of sec. 30.

Over level land.

39.25

The 1/4 sec. cor. of sec. 25, T. 19 S., R. 20 W., monumented by a stone, 15x8x4 ins., mkd. 1/4 on west face.

At the corner point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

1/4 |

S 25

1956

Deposit original stone and broken glass alongside iron post.

40.65

Point for the 1/4 sec. cor. of sec. 30, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

1/4

S 30

1956

Deposit broken glass alongside iron post.

79.29

The cor. of secs. 24 and 25, T. 19 S., R. 20 W., monumented by a quartzite stone, 17x6x4 ins., mkd. with 2 notches on south face, no other marks.

At the corner point

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

Dependent Resurvey, West Bdy., T. 19 S., R. 19 W.

Chains

T19S T19S

S24 | S30  
S25

R20W R19W

1956

Deposit original stone alongside iron post.

Deposit broken glass alongside iron post.

81.31

The cor. of secs. 19 and 30, monumented by a stone, 8x5x4 ins., unmarked.

At the corner point

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

T19S T19S

S24 | S19  
S30

R20W R19W

1956

Deposit original stone alongside iron post.

Deposit broken glass alongside iron post.

Land, level.

Soil, sandy.

No timber; undergrowth, greasewood and shadscale.

N. 0° 07' E., along the west bdy. of sec. 19.

Over level land.

38.02

The 1/4 sec. cor. of sec. 24, T. 19 S., R. 20 W., monumented by a stone, 14x6x4 ins., mkd. 1/4 on west face.

At the corner point

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

1/4 |  
S 24

1956

Deposit original stone alongside iron post.

Deposit broken glass alongside iron post.

40.72

The 1/4 sec. cor. of sec. 19, monumented by a small, unmarked stone.

At the corner point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

1/4 |  
S 19

1956

1000

Report original notes alongside town post.

Report broken glass alongside town post.

1001

The top of cone 13 and 14, 1. 20 ft., 2. 20 ft., surrounded by a cone. (Total 100 ft. 2nd) 3 groups on north and 3 groups on south

At the center point

See on town post, 20 in. long, 3 in. diam., 27 in. in the ground and is a mass of stone, on top of post, with brass top and.

1001  
11  
11  
11  
11  
11

Report original notes alongside town post.

Report broken glass alongside town post.

1002

The top of cone 15 and 16, surrounded by a cone, total 100 ft., unmarked

At the center point

See on town post, 20 in. long, 3 in. diam., 27 in. in the ground and is a mass of stone, on top of post, with brass top and.

1002  
11  
11  
11  
11  
11

Report original notes alongside town post.

Report broken glass alongside town post.

Level, level  
Soil, sandy  
No. 1000, 1000, 1000, 1000 and 1000.

0 2' 11" 0., along the road by. of cone 16.

See level: level

1003

The top of cone 17, 18, 19 ft., 2. 20 ft., surrounded by a cone (Total 100 ft., unmarked)

At the center point

See on town post, 20 in. long, 3 in. diam., 27 in. in the ground and is a mass of stone, on top of post, with brass top and.

1003  
11  
11  
11  
11  
11

Report original notes alongside town post.

Report broken glass alongside town post.

Chains  
40.52 The  $\frac{1}{4}$  sec. cor. of sec. 18, marked by a quartzite stone, 8x6x2 ins., found buried in an old mound of earth.

At the corner point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 20 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

$\frac{1}{4}$   
S 18  
1956

Bury original stone and glass at base of post.

76.93 The cor. of secs. 12 and 13, T. 19 S., R. 20 W., monumented by a stone, 13x8x6 ins., mkd. 2 grooves on north and 4 grooves on south face.

At the corner point

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

T19S T19S  
S12 | S18  
S13 |  
R20W R19W  
1956

Deposit original stone alongside iron post.

Deposit broken glass alongside iron post.

81.16 The cor. of secs. 7 and 18, marked by old stake 2 ins. square, 1 ft. long, no trace of mound of earth.

At the corner point

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

T19S T19S  
S12 | S 7  
S18 |  
R20W R19W  
1956

Deposit broken glass alongside iron post.

Land, level.

Soil, sandy.

No timber; undergrowth, greasewood and shadscale.

N. 0° 04' W., along the west bdy. of sec. 7.

Over level land.

19.80 Ascend gradually over SE. slope.

23.80 Leave greasewood undergrowth, bears N. 75° E. and S. 75° W.

33.30 Old U. S. Highway No. 6, bears N. 41° E. to Delta, Utah, and S. 41° W. to Ely, Nevada.

35.78 The  $\frac{1}{4}$  sec. cor. of sec. 12, T. 19 S., R. 20 W., monumented by a

Chains

2010  
12.00

quartzite stone, 12x11x3 ins., mkd.  $\frac{1}{2}$  on west face.

At the corner point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

$\frac{1}{2}$   
S 12  
1956

Deposit original stone alongside iron post.

Deposit broken glass alongside iron post.

40.26

The  $\frac{1}{4}$  sec. cor. of sec. 7, marked by a quartzite stone, 12x8x6 ins., unmarked.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

$\frac{1}{4}$   
S 7  
1956

Deposit broken glass alongside iron post.

43.00

Wash, drains SE.

67.40

Wash, drains SE.

75.81

The cor. of secs. 1 and 12, T. 19 S., R. 20 W., monumented by a stone 16x6x6 ins., mkd. 1 groove on north and 5 grooves on south face.

At the corner point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

T19S T19S  
S 1 | S 7  
S12  
R20W R19W  
1956

Deposit original stone alongside iron post.

Deposit broken glass alongside iron post.

80.95

The cor. of secs. 6 and 7, monumented by a stone, 14x8x6 ins., mkd. 1 groove on north and 5 grooves on south face.

At the corner point

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

T19S T19S  
S 1 | S 6  
S 7  
R20W R19W  
1956

Deposit original stone alongside iron post.

Deposit broken glass alongside iron post.

Land, level to rolling SE. slope.  
Soil, sandy and stony.

Dependent Resurvey, West Bay., T. 19 S., R. 19 W.

Chains

No timber; undergrowth, greasewood and shadscale south 23.80 chs. dist.; remainder of line north, shadscale.

N. 0° 01' E., along the west bdy. of sec. 6.

Ascend gradually over SE. slope.

10.70

Wash, 3 ft. deep, 30 lks. wide, drains SE.

34.94

The 1/4 sec. cor. of sec. 1, T. 19 S., R. 20 W., monumented by a stone 12x8x5 ins., mkd. 1/4 on west face.

At the corner point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

1/4  
S 1  
1956

Deposit original stone alongside iron post.

Deposit broken glass alongside iron post.

40.58

The 1/4 sec. cor. of sec. 6, monumented by a stone, 18x7x4 ins., mkd. 1/4 on west face.

At the corner point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

1/4  
S 6  
1956

Deposit original stone alongside iron post.

Deposit broken glass alongside iron post.

41.10

Road, bears NW. and SE.

56.60

Wash, 3 ft. deep, 30 lks. wide, drains SE.

65.80

Wash, drains SE.

81.17

The cor. of Tps. 18 and 19 S., Rs. 19 and 20 W., monumented by a limestone, 18x13x7 ins., 6 grooves on each north, east, west and south faces.

At the corner point

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, 5 ft. base, to top of post, with brass cap mkd.

T188  
R20W R19W  
S36 | S31  
S 1 | S 6  
T19S  
1956

Deposit original stone and broken glass at base of post.

Land, gently rolling SE. slope.

Dependent Resurvey, West Bdy., T. 19 S., R. 19 W.

Chains

Soil, stony. No timber; undergrowth, shadscale.

Dependent Resurvey, East Bdy., T. 19 S., R. 19 W.

Reestablishment of the survey executed by Andrew J. Stewart Jr., in 1882.

From the cor. of Tps. 19 and 20 S., Rs. 18 and 19 W.

N. 0° 04' W., along the east bdy. of sec. 36.

Ascend over rolling SW. slope.

15.10

Small wash, drains SW.

16.60

Small wash, drains SW.; thence over east slope.

37.90

Wash, drains E.; asc. over SW. slope.

40.065

Point for the  $\frac{1}{4}$  sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 3 ins. diam., over ~~X~~ on solid blue limestone and in a mound of stone, 6 ft. base, to top of post, with brass cap mkd.

S36|S31  
1956

Ascend 35 ft. over broken and rocky SW. slope.

53.00

Draw, drains W. 1 ch., thence S.; asc. 45 ft. over steep, and rocky SSW. slope.

57.50

Spur, slopes W.; desc. over NW. slope.

60.50

Draw, drains SW.; asc. over SW. slope.

67.00

Top of ascent, in saddle, on N. 80° W. slope; desc. over NW. slope.

77.70

Draw, drains NE.; thence over E. slope.

80.13

Point for the cor. of secs. 25, 30, 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 3 ins. diam., 24 ins. in the ground and in a mound of stone, to top of post; with brass cap mkd.

T19S  
R19W R18W  
S25|S30  
S36|S31  
1956

Deposit broken glass alongside iron post.

Land, rolling to rough.

Soil, rocky.

No timber; no undergrowth.

N. 0° 04' W. along the east bdy. of sec. 25.

## Dependent Resurvey, East Bdy., T. 19 S., R. 19 W.

## Chains

Over rolling east slope,

.40 Small wash, drains NE.

6.80 Small wash, drains E.

13.80 Desc. over NE. slope.

16.00 Base of descent, bears NW. and SE.; thence over rolling W. slope.

24.00 Wash, drains NW.

39.90 Main wash, 4 ft. deep, 20 lks. wide, drains N. 80° W.

40.065 Point for the  $\frac{1}{4}$  sec. cor. of secs. 25 and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 3 ins. diam., 20 ins. in the ground and in a mound of stone, 5 ft. base, to top of post, with brass cap mkd.

$\frac{1}{4}$   
S 25 | S 30  
1956

Deposit broken glass alongside iron post.

Over rolling west slope.

43.20 Wash, drains W.

62.30 Wash, drains W.

74.90 Wash, drains SW.

80.13 The cor. of secs. 19, 24, 25 and 30, monumented by a stone, 16x16x8 ins., mkd. 4 grooves on north and 2 grooves on south face.

At the corner point

Set an iron post, 36 ins. long, 3 ins. diam., 20 ins. in the ground and in a mound of stone, 5 ft. base, to top of post, with brass cap mkd.

T19S  
R19W R18W  
S24 | S19  
S25 | S30  
1956

Deposit original stone alongside iron post.

Deposit broken glass alongside iron post.

Land, rolling.  
Soil, sandy and rocky.  
No timber; undergrowth, shade-scale.

N. 0° 13' W., along the east bdy. of sec. 24.

Over rolling west slope.

35.00 Dry lake bed, bears W, of line, 10 chs. dist.

40.71 The  $\frac{1}{4}$  sec. cor. of sec. 24, monumented by a stone, 18x12x8 ins., mkd.  $\frac{1}{4}$  on west face.

At the corner point

Dependent Resurvey, East Bdy., T. 19 S., R. 19 W.

Chains

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

$\frac{1}{4}$  |  
 S 24 |  
 1956

Deposit original stone alongside iron post.

Deposit broken glass alongside iron post.

43.70 Wash, drains NW.

45.90 Wash, drains NW.

68.80 Wash, drains NW.

80.50 The closing corner, of secs. 18 and 19, T. 19 S., R. 18 W., monumented by a limestone, 14x10x5 ins., mkd. cc on east face, and 3 grooves on north and 3 grooves on south face.

At the corner point

Set an iron post, 36 ins. long, 3 ins. diam., 20 ins. in the ground and in a mound of stone, 4 ft. base, to top of post, with brass cap mkd.

T19S T19S  
 S24 | S18 C  
     | S19 C  
 R19W R18W  
 1956

Deposit original stone alongside iron post.

Deposit broken glass alongside iron post.

81.42 The cor. of secs. 13 and 24, monumented by a blue limestone, 6x6x5 ins., mkd. 3 grooves on north and 3 grooves on south face.

At the corner point

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

T19S T19S  
 S13 | S18  
 S24 |  
 R19W R18W  
 1956

Deposit original stone alongside iron post.

Deposit broken glass alongside iron post.

Land, rolling, west to northwest slope.

Soil, sandy and rocky.

No timber; undergrowth, shadscale.

N. 0° 11' W., along the east bdy. of sec. 13.

Over rolling west to northwest slope.

60 Small wash, drains W.

286

## Dependent Resurvey, East Bdy., T. 19 S., R. 19 W.

Chains

31.90

Wash, drains NW.

40.17

The  $\frac{1}{2}$  sec. cor. of sec. 13, monumented by a blue limestone, 16x12x12 ins., mkd.  $\frac{1}{2}$  on west face.

At the corner point

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

$\frac{1}{2}$   
 S 13  
 1956

Deposit original stone alongside iron post.

Deposit broken glass alongside iron post.

40.50

Small wash, drains NW.

61.30

Wash, 4 ft. deep, 30 lks. wide, drains W.

75.10

Small wash, drains W.

79.35

The closing corner, of secs. 7 and 18, T. 19 S., R. 18 W., monumented by a blue limestone 12x9x7 ins., mkd. cc on east face, and 2 grooves on north and 4 grooves on south face.

At the corner point

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

T19S T19S  
 S13 |  $\frac{S}{S} \frac{7}{18}$  C  
 R19W R18W  
 1956

Deposit original stone alongside iron post.

Deposit broken glass alongside iron post.

80.34

The cor. of secs. 12 and 13, monumented by a deposit of charcoal.

At the corner point

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

T19S T19S  
 $\frac{S12}{S13}$  | S 7  
 R19W R18W  
 1956

Deposit broken glass alongside iron post.

Land, rolling west to northwest slope.

Soil, sandy and rocky.

No timber; undergrowth, shadscale.

N. 0° 08' W., along the east bdy. of sec. 12.

Over west slope.

Dependent Resurvey, East Bdy., T. 19 S., R. 19 W.

Chains	
5.00	Base of ascent, bears NW. and SE.; asc. over SW. slope.
6.10	Top of ascent, bench, bears NW. and SE.; thence over nearly level land.
7.70	Road, bears NE. and SW.
40.245	Point for the $\frac{1}{2}$ sec. cor. of sec. 12, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.
	$\frac{1}{2}$ S 12 1956
	Deposit broken glass alongside iron post.
48.10	Wash, 3 ft. deep, 40 lks. wide, drains NW.
59.90	Head of small draw, drains NW.
70.00	Descend 28 ft. over N. slope.
73.40	Draw, drains W.; asc. over S. slope.
75.50	Top of ascent; thence over nearly level land.
79.01	The closing corner of secs. 6 and 7, T. 19 S., R. 18 W., monumented by a blue limestone, 12x8x6 ins., mkd. cc on east face, 1 groove on north and 5 grooves on south face.
	At the corner point
	Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.
	T19S T19S S12 $\frac{S 6}{S 7}$ C R19W R18W 1956
	Deposit original stone alongside iron post.
	Deposit broken glass alongside iron post.
80.49	The cor. of secs. 1 and 12, monumented by an unmarked blue limestone.
	At the corner point
	Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a small mound of stone, to top of post, with brass cap mkd.
	T19S T19S S 1   S 6 S12 R19W R18W 1956
	Deposit original stone alongside iron post.
	Deposit broken glass alongside iron post.
	Land, rolling west to northwest slope.
	Soil, sandy and rocky.
	No timber; undergrowth, shadscale.

Dependent Resurvey, East Bdy., T. 19 S., R. 19 W.

Chains

N. 0° 12' W., along the east bdy of sec. 1

Over rolling west slope.

5.00 Draw, drains W.; asc. over SW. slope.

8.00 Top of ascent, on W. slope; thence over nearly level land.

18.70 Leave bench; desc. 40 ft. over NW. slope.

21.60 Base of descent, bears E. and W.; thence desc. gradually over NNW. slope.

27.00 Small wash, drains W.

40.56 Point for the 1/4 sec. cor. of sec. 1, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.



Deposit broken glass alongside iron post.

46.00 Enter greasewood undergrowth, bears NE. and SW.


54.10 Small wash, drains NW.

69.30 Small wash, drains NW.

81.12 The cor. of Tps. 18 and 19 S., Rs. 18 and 19 W., monumented by a blue limestone, 11x8x6 ins., mkd. 6 grooves on 2 sides.

At the corner point

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, 5 ft. base, to top of post, with brass cap mkd.



Deposit original stone alongside iron post.

Deposit broken glass alongside iron post.

Land, west to northwest slope.

Soil, sandy and rocky.

No timber; undergrowth, greasewood and shadscale.

Dependent Resurvey, North Bdy., T. 19 S., R. 19 W.

Reestablishment of the survey executed by A. J. Stewart, Jr., in 1882

N. 89° 50' W., bet. secs. 1 and 36, on N. bdy. of the Tp

Dependent Resurvey, North Ely, Nevada, R. 19 W.

Chains	
	Over nearly level land.
40.35	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.
	$\frac{1}{4} \frac{S 36}{S 1}$ 1956
	Deposit broken glass alongside iron post.
58.30	Ascend 5 ft. over east slope.
80.70	Point for the cor. of secs. 1, 2, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.
	$\begin{array}{r} T18S R19W \\ \hline S35   S36 \\ \hline S 2   S 1 \\ \hline T19S \\ 1956 \end{array}$
	Deposit broken glass alongside iron post.
	Land, nearly level. Soil, sandy loam. No timber; undergrowth, greasewood and shadscale.
	N. 89° 50' W., bet. secs. 2 and 35.
	Over nearly level to rolling land.
13.00	Descend over NW. slope.
16.00	Small wash, drains N.; asc. over NE. slope.
20.00	Low flat spur, slopes N.; desc. over NW. slope.
26.00	Base of descent, bears NNE. and SSW.; thence over nearly level land
40.35	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 35, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.
	$\frac{1}{4} \frac{S 35}{S 2}$ 1956
	Deposit broken glass alongside iron post.
80.70	Point for the sec. cor. of secs. 2, 3, 34 and 35, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

Chains

T18S R19W

S34 | S35

S 3 | S 2

T19S

1956.

Deposit broken glass alongside iron post.

Land, nearly level to rolling.

Soil, sandy loam.

No timber; undergrowth, greasewood and shadscale.

N. 89° 50' W., bet. secs. 3 and 34.

Over nearly level to rolling land.

6.90 Ascend 10 ft. over NE. slope.

8.90 Top of ascent, bears N. and S.; thence over nearly level land.

40.35 Point for the 1/4 sec. cor. of secs. 3 and 34, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

1/4 S 34  
S 3

1956

Deposit broken glass alongside iron post.

80.70 Point for the sec. cor. of secs. 3, 4, 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

T18S R19W

S33 | S34

S 4 | S 3

T19S

1956

Deposit broken glass alongside iron post.

Land, nearly level to rolling.

Soil, sandy loam.

No timber; undergrowth, greasewood and shadscale.

N. 89° 50' W., bet. secs. 4 and 33.

Over nearly level land.

40.35 Point for the 1/4 sec. cor. of secs. 4 and 33, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

1/4 S 33  
S 4

1956

Chains

Deposit broken glass alongside iron post.

71.40

Ascend 17 ft. over SE. slope.

72.40

Low rise, slopes S.

80.70

Point for the sec. cor. of secs. 4, 5, 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

T18S R19W

S32 | S33

S 5 | S 4

T19S

1956

Deposit broken glass alongside iron post.

Land, nearly level.

Soil, sandy loam.

No timber; undergrowth, greasewood and shadscale.

N. 89° 50' W., bet. secs. 5 and 32.

Ascend 30 ft. over rolling SE. slope, to the  $\frac{1}{2}$  sec. cor.

7.00

Small wash, drains SE.

17.50

Small wash, drains SE.

40.35

Point for the  $\frac{1}{2}$  sec. cor. of secs. 5 and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

$$\frac{1}{2} \frac{S 32}{S 5}$$
 1956

Deposit broken glass alongside iron post.

Ascend 30 ft. over rolling SE. slope, to the sec. cor.

45.60

Small wash, drains SE.

51.20

Old U. S. Highway No. 6, bears N. 37° E. to Delta, Utah, and S. 37° W. to Ely, Nevada.

75.60

Wash, 3 ft. deep, 15 lks. wide, drains SE.

80.70

Point for the sec. cor. of secs. 5, 6, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

T18S R19W

S31 | S32

S 6 | S 5

T19S

1956

Dependent Resurvey of the North Bdy of Tps 19 S., R. 19 W.

Chains		Semi-D	
	<p>Deposit broken glass alongside iron post.</p> <p>Land, rolling SE. slope. Soil, sandy loam and stony. No timber; undergrowth, shadscale.</p>	00.10	
	<p>N. 89° 50' W., bet. secs. 6 and 31.</p> <p>Ascend 85 ft. over E. slope.</p>		
16.60	Low ridge spur, slopes SE.; desc. 15 ft. over SW. slope.		
22.20	Draw, 6 ft. deep, 80 lks. wide, drains SE.; asc. 35 ft. over SE. slope to the 1/4 sec. cor.		
40.35	<p>Point for the 1/4 sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.</p> <p style="text-align: center;"> <math display="block">\frac{S \ 31}{S \ 6}</math> 1956 </p>		
	<p>Deposit broken glass alongside iron post.</p> <p>Ascend 80 ft. over SE. slope to the sec. cor.</p>		
80.30	<p>The cor. of Tps. 18 and 19 S., Rs. 19 and 20 W.</p> <p>Land, rolling SE. slope. Soil, sandy loam and rocky. No timber; undergrowth, shadscale.</p>		
<p>Dependent Resurvey of the Subdivisional Lines, T. 19 S., R. 19 W., Salt Lake Meridian, Utah.</p>			
<p>Reestablishment of the survey executed by Andrew J. Stewart Jr., in 1882.</p>			
	<p>From the cor. of secs. 35 and 36, on the S. bdy. of the Tp.</p> <p>N. 0° 30' E., bet. secs. 35 and 36.</p> <p>Ascend gradually over SW. slope.</p>		
16.70	Road, bears E. and W.		
27.10	Top of ascent, on W. slope; desc. gradually over NW. slope.		
40.52	<p>Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.</p> <p style="text-align: center;"> <math display="block">\frac{S \ 35}{S \ 36}</math> 1956 </p>	00.00	

Dependent Resurvey of the Subdivisional Line, T. 19 S., R. 19

Chains	
	Deposit broken glass alongside iron post.
81.04	Point for the cor. of secs. 25, 26, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.
	$\begin{array}{r} T19S \ R19W \\ \hline S26 \ S25 \\ \hline S35 \ S36 \\ 1956 \end{array}$
	Deposit broken glass alongside iron post.
	Land, nearly level to rolling.
	Soil, sandy loam.
	No timber; undergrowth, greasewood and shadscale.
	From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp
	S. 88° 49' W., bet. secs. 25 and 36.
	Ascend 52 ft. over steep rocky E. slope.
11.00	Ridge, bears N. and S.; desc. 175 ft. over rocky W. slope.
22.70	Base of steep descent, bears N. and S.; thence desc. 42 ft. over W. slope.
30.60	Low ridge spur, slopes N. 30° W.; desc. gradually over NW. slope.
40.56	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.
	$\begin{array}{r} \frac{1}{4} \ S \ 25 \\ \hline S \ 36 \\ 1956 \end{array}$
	Deposit broken glass alongside iron post.
46.00	Road, bears NE. and SW.
71.00	Enter greasewood undergrowth, bears N. and S.
81.12	The cor. of secs. 25, 26, 35 and 36.
	Land, east 30.00 chs. dist. rough and rolling; remainder of line west, gently rolling NW. slope.
	Soil, east 30.00 chs. dist. rocky; remainder of line west, sandy loam and stony.
	No timber; undergrowth, east 71.00 chs. dist. shadscale; remainder of line west, greasewood and shadscale.
	N. 0° 03' E., bet. secs. 25 and 26.
	Over gently rolling W. slope.
30.00	Leave greasewood undergrowth, bears NNW. and SSE.
40.52	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 26, at proportionate

Dependent Resurvey of the Subdivisional Lines, T. 19 S., R. 19 W.

Chains

distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

¼  
S 26 | S 25  
1956

Deposit broken glass alongside iron post.

69.80

Wash, 3 ft. deep, 30 lks. wide, drains W.

81.04

Point for the cor. of secs. 23, 24, 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

T19S R19W  
S23 | S24  
S26 | S25  
1956

Deposit broken glass alongside iron post.

from which

A water well, bears S. 88° 02' W., 21.71 chs. dist.

Land, gently rolling west slope.  
Soil, sandy loam.

No timber; undergrowth, south 30.00 chs. dist. dense greasewood; remainder of line north, shadecale.

From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp.

S. 89° 29' W., bet. secs. 24 and 25.

Descend 85 ft. over general west slope.

0.46

Point for the ¼ sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

¼  
S 24  
S 25  
1956

Deposit broken glass alongside iron post.

0.80

Descend 25 ft. over W. slope.

5.50

Road, bears N. 1° 30' E. and S. 6° 30' W.; desc. 30 ft. over W. slope.

1.50

Small wash, drains SW.

2.70

Bench, bears NNW. and S.; desc. 30 ft. over W. slope.

9.00

Base of bench, bears NNW. and S.

0.92

The cor. of secs. 23, 24, 25 and 26.

Chains		Station
	<p>Land, general west slope. Soil, sandy loam and stony. No timber; undergrowth, shadscale.</p>	
	<p>N. 0° 21' W., bet. secs. 23 and 24.</p> <p>Ascend gradually over west slope.</p>	
14.90	Low round spur, slopes W.; thence over rolling W. slope.	
37.60	Small draw, drains W.	
40.52	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.</p> <p style="text-align: center;"><math>\frac{1}{4}</math> S 23   S 24 1956</p>	
43.00	<p>Deposit broken glass alongside iron post.</p> <p>Small ridge spur, slopes NW.; thence over broken W. slope.</p>	
70.90	Road, bears NE. and SW.; asc. 50 ft. over rolling SW. slope.	
81.04	<p>Point for the cor. of secs. 13, 14, 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.</p> <p style="text-align: center;">T19S R19W S14   S13 S23   S24 1956</p>	
	<p>Deposit broken glass alongside iron post.</p> <p>Land, rolling. Soil, sandy and stony. No timber; undergrowth, shadscale.</p>	
	<p>From the cor. of secs. 13 and 24, on the E. bdy. of the Tp.</p> <p>S. 89° 13' W., bet. secs. 13 and 24.</p> <p>Descend gradually over W. slope.</p>	
9.60	Small wash, drains NW.	
25.50	Wash, drains NW.	
32.70	Road, bears N. 10° E. and S. 10° W.	
40.535	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.</p>	

Dependent Resurvey of the Subdivisional Lines, T. 19 S., R. 19 W.

Chains

1/4 S 13  
S 124  
1956

Deposit broken glass alongside iron post.

64.50 Enter dry lake bed, bears N. and S.

71.60 Road, bears NE. and SW.

76.10 Leave dry lake bed, bears NNE. and SSW.

81.07 The cor. of secs. 13, 14, 23 and 24.

Land, general west slope.  
Soil, sandy clay and stony.  
No timber; undergrowth, shadscale.

N. 0° 04' W., bet. secs. 13 and 14.

Descend 45 ft. over rolling W. to NW. slope.

4.10 Small draw, drains SW.

7.80 Head of small draw, drains W.

14.90 Small draw, drains NW.

16.90 Small draw, drains NW.

18.90 Base of bench, bears E. and SE.; thence desc. gradually over NW. slope.

27.80 Base of descent, bears NNE. and S.; thence over nearly level land.

40.52 Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

1/4 S 14 | S 13  
1956

Deposit broken glass alongside iron post.

81.04 Point for the cor. of secs. 11, 12, 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

T19S R19W  
S11 | S12  
S14 | S13  
1956

Deposit broken glass alongside iron post.

Land, rolling W. to NW. slope.  
Soil, sandy loam to stony.  
No timber; undergrowth, shadscale.

Dependent Resurvey of the Subdivisional Lines, T. 19 S., R. 19 W.

Chains

- From the cor. of secs. 12 and 13, on the E. bdy. of the Tp.  
S. 89° 42' W., bet. secs. 12 and 13.  
Descend 70 ft. over W. slope, to the  $\frac{1}{4}$  sec. cor.
- 3.45 Road, bears NNE. and SSW.
- 9.80 Road, bears NE. and SW.
- 16.40 Wash, drains SW.
- 23.00 Same wash as above, drains NW.
- 27.10 Same wash as above, drains SW.
- 36.30 Same wash as above, drains NW.
- 40.445 Point for the  $\frac{1}{4}$  sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 20 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.  
 $\frac{1}{4}$   $\frac{S\ 12}{S\ 13}$   
1956  
Deposit broken glass alongside iron post.
- 55.50 Wash, 3 ft. deep, 40 lks. wide, drains NW.
- 63.60 Descend 92 ft. over bench, W. slope.
- 65.60 Base of descent, bears NNE. and S.; desc. 27 ft. over W. slope.
- 80.89 The cor. of secs. 11, 12, 13 and 14.  
Land, rolling west slope.  
Soil, sandy loam and stony.  
No timber; undergrowth, shadscale.

---

- N. 0° 12' W., bet. secs. 11 and 12.  
Over nearly level land.
- 40.52 Point for the  $\frac{1}{4}$  sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.  
 $\frac{1}{4}$   $\frac{S\ 11}{S\ 12}$   
1956  
Deposit broken glass alongside iron post.
- 81.04 Point for the cor. of secs. 1, 2, 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

## Dependent Resurvey of the Subdivisional Lines, T. 19 S., R. 19 W.

Chains	
	<p style="text-align: center;">T19S R19W  <math>\frac{S\ 2}{S\ 1}</math>  <math>\frac{S11}{S12}</math>            1956</p> <p>Deposit broken glass alongside iron post.</p> <p>Land, nearly level.            Soil, sandy loam.            No timber; undergrowth, greasewood and shadscale.</p>
	<p>From the cor. of secs. 1 and 12, on the E. bdy. of the Tp.</p> <p>N. 89° 56' W., bet. secs. 1 and 12.</p> <p>Descend 46 ft. over west slope of bench.</p>
4.60	Base of bench, bears N. and S.
37.00	Wash, drains NW.
40.48	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 20 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.</p> <p style="text-align: center;"><math>\frac{1}{4}</math> <math>\frac{S\ 1}{S12}</math>            1956</p> <p>Deposit broken glass alongside iron post.</p>
41.00	Descend 62 ft. over W. slope of bench.
43.50	Base of bench, bears NE. and S.; thence over nearly level land.
80.96	<p>The cor. of secs. 1, 2, 11 and 12.</p> <p>Land, rolling to general west slope.            Soil, sandy clay and stony.            No timber; undergrowth, shadscale.</p>
	<p>N. 0° 02' W., bet. secs. 1 and 2.</p> <p>Over level land.</p>
26.00	Ascend gradually over SE. slope.
32.80	Top of ascent, bears W, and NE.; thence over nearly level land.
40.52	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.</p> <p style="text-align: center;"><math>\frac{1}{4}</math> <math>\frac{S\ 2}{S\ 1}</math>            1956</p> <p>Deposit broken glass alongside iron post.</p>

Chains	Description	Notes
72.30	Ascend 10 ft. over SE. slope.	
81.24	The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp.  Land, nearly level. Soil, sandy loam. No timber; undergrowth, greasewood and shadscale.	
	From the cor. of secs. 34 and 35, on the S. bdy. of the Tp.  N. 0° 13' E., bet. secs. 34 and 35.  Over level land.	
20.40	Fence, bears N. 62° 33' E. and S. 62° 33' W.	
31.40	Old water ditch, course NE.	
40.52	Point for the 1/4 sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.  S 34   S 35 1956	
	Deposit broken glass alongside iron post.	
48.00	Water ditch, course NE.	
66.20	Fence, bears N. 81° 45' W. and S. 81° 45' E.	
77.50	Small reservoir, bears W., 2 chs. dist.	
81.04	Point for the cor. of secs. 26, 27, 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.  T19S R19W S27   S26 S34   S35 1956	
	Deposit broken glass alongside iron post.	
	Land, level. Soil, sandy loam. No timber; undergrowth, greasewood and shadscale.	
	From the cor. of secs. 25, 26, 35 and 36.  N. 89° 31' W., bet. secs. 26 and 35.  Descend gradually over NW. slope.	
31.00	Descend over low bench; bears NNE. and SSW.	
33.40	Base of descent; thence over level land.  Deposit broken glass alongside iron post.	

Dependent Resurvey of the Subdivisional Lines, T. 19 S., R. 19 W.

Chains

40.405 Point for the  $\frac{1}{4}$  sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original corner.  
 Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

$\frac{1}{4}$   $\frac{S\ 26}{S\ 35}$   
 1956

Deposit broken glass alongside iron post.

55.40 Wash, 3 ft. deep, 30 lks. wide, drains NW.

77.40 Small wash, drains N.

80.81 The cor. of secs. 26, 27, 34 and 35.

Land, nearly level.  
 Soil, sandy loam.  
 No timber; undergrowth, greasewood and shadscale.

N. 0° 29' W., bet. secs. 26 and 27.

Over level land.

40.52 Point for the  $\frac{1}{4}$  sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original corner.  
 Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

$\frac{1}{4}$   
 S 27 | S 26  
 1956

Deposit broken glass alongside iron post.

50.30 Wash, 3 ft. deep, 30 lks. wide, drains NE.

81.04 Point for the cor. of secs. 22, 23, 26 and 27, at proportionate distance; there is no remaining evidence of the original corner.  
 Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

T19S R19W  
 $\frac{S22\ | \ S23}{S27\ | \ S26}$   
 1956

Deposit broken glass alongside iron post.

Land, level.  
 Soil, sandy loam.  
 No timber; undergrowth, greasewood and shadscale.

From the cor. of secs. 23, 24, 25 and 26.

N. 89° 31' W., bet. secs. 23 and 26.

Over nearly level land.

40.76 Point for the  $\frac{1}{4}$  sec. cor. of secs. 23 and 26, at proportionate

Chains

111110

distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

1/4 S 23  
S 26  
1956

Deposit broken glass alongside iron post.

65.10

Wash, drains NNE.

81.52

The cor. of secs. 22, 23, 26 and 27.

Land, level.

Soil, sandy loam.

No timber; undergrowth, greasewood and shadscale.

N. 0° 11' E., bet. secs. 22 and 23.

Over level land.

11.60

Road, bears NE. and SW.

40.52

Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

1/4  
S 22 | S 23  
1956

Deposit broken glass alongside iron post.

81.04

Point for the cor. of secs. 14, 15, 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

T19S R19W  
S15 | S14  
S22 | S23  
1956

Deposit broken glass alongside iron post.

Land, level.

Soil, sandy loam.

No timber; undergrowth, greasewood and shadscale.

From the cor. of secs. 13, 14, 23 and 24.

N. 89° 30' W., bet. secs. 14 and 23.

Descend 60 ft. over west slope, to base of bench.

2.90

Small wash, drains SW.

7.20

Base of descent, bears N. and S.; thence over level land.

40.365

Point for the 1/4 sec. cor. of secs. 14 and 23, at proportionate

## Dependent Resurvey of the Subdivisional Lines T. 19 S., R. 19 W.

Chains

distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

$$\frac{S 14}{S 23}$$

1956

Deposit broken glass alongside iron post.

41.90 Wash, drains N.

44.80 Wash, drains NE.

62.30 Old fence, bears N. 20° E. and S. 20° W.

68.10 Water tank, bears N. 20° E. and S. 20° W.

69.70 Old fence, bears N. 8° E. and S. 8° W.

80.73 The cor. of secs. 14, 15, 22 and 23.

Land, nearly level.

Soil, sandy loam.

No timber; undergrowth, greasewood and shadscale.

N. 0° 14' E., bet. secs. 14 and 15.

Over level land.

0.52 Point for the ¼ sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

$$\frac{S 15 | S 14}{1956}$$

Deposit broken glass alongside iron post.

1.04 Point for the cor. of secs. 10, 11, 14 and 15, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

$$\frac{T19S R19W}{S10 | S11}$$

$$\frac{S15 | S14}{1956}$$

Deposit broken glass alongside iron post.

Land, level.

Soil, sandy loam.

No timber; undergrowth, greasewood and shadscale.

From the cor. of secs. 11, 12, 13 and 14.

N. 89° 31' W., bet. secs. 11 and 14.

Descend over west slope of bench.

Chains

2.00

Base of bench, bears NNE. and SSE.; thence over level land.

40.145

Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

1/4 S 11 S 14 1956

Deposit broken glass alongside iron post.

49.00

Wash, drains N.

80.29

The cor. of secs. 10, 11, 14 and 15.

Land, level.  
Soil, sandy loam.  
No timber; undergrowth, greasewood and shadscale.

N. 0° 20' W., bet. secs. 10 and 11.

Over level land.

2.90

Ascend 20 ft. over south slope of bench.

5.90

Top of ascent, bench, bears E. and W.; thence over gently rolling east slope.

24.90

Desc. over N. slope of bench.

30.00

Base of descent, bears E. and W.; thence over nearly level land.

40.52

Point for the 1/4 sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

1/4 S 10 S 11 1956

Deposit broken glass alongside iron post.

81.04

Point for the cor. of secs. 2, 3, 10 and 11, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground, and in a mound of stone, to top of post, with brass cap mkd.

T19S R19W S 3 S 2 S 10 S 11 1956

Deposit broken glass alongside iron post.

Land, rolling to nearly level land.  
Soil, sandy loam.  
No timber; undergrowth, greasewood and shadscale.

From the cor. of secs. 1, 2, 11 and 12.

N. 89° 33' W., bet. secs. 2 and 11.

## Dependent Resurvey of the Subdivisional Lines, T. 19 S., R. 19 W.

Chains	
	Over nearly level land.
16.00	Ascend over east slope of low bench.
19.00	Top of ascent, low bench, bears NNE. and SSW.; thence over rolling land.
40.23	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.  $\frac{1}{4} \frac{S 2}{S 11}$ 1956
	Deposit broken glass alongside iron post.
80.46	The cor. of secs. 2, 3, 10 and 11.  Land, rolling to nearly level, Soil, sandy loam. No timber; undergrowth, greasewood and shadscale.
	N. $0^{\circ} 14'$ W., bet. secs. 2 and 3.  Over nearly level land.
38.00	Wash, drains NE.
40.52	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.  $\frac{1}{4}$ S 3   S 2 1956
	Deposit broken glass alongside iron post.
69.00	Ascend over S. slope.
70.80	Top of bench, bears E. and W.
75.80	Descend over N. slope of bench.
79.00	Base of descent, bears E. and W.; thence over level land.
80.84	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp.  Land, nearly level. Soil, sandy loam. No timber; undergrowth, greasewood and shadscale.
	From the cor. of secs. 33 and 34, on the S. bdy. of the Tp.  N. $0^{\circ} 02'$ W., bet. secs. 33 and 34.  Over level land.
27.50	Descend 10 ft. over N. slope of bench.
31.60	Base of descent, bears E. and W.; thence over level land.

Dependent Resurvey of the Subdivisional Lines, T. 19 S., R. 19 W.

Chains	
31.80	Ditch, course E.
40.335	Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.  $\begin{array}{c} \frac{1}{4} \\ S\ 33   S\ 34 \\ \hline 1956 \end{array}$  Deposit broken glass alongside iron post.
49.40	Ditch, course E.
80.67	Point for the cor. of secs. 27, 28, 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.  $\begin{array}{c} T19S\ R19W \\ \hline S28   S27 \\ \hline S33   S34 \\ \hline 1956 \end{array}$  Deposit broken glass alongside iron post.  Land, nearly level. Soil, sandy loam. No timber; undergrowth, greasewood and shadscale.
	From the cor. of secs. 26, 27, 34 and 35.  N. 89° 17' W., bet. secs. 27 and 34.  Over level land.
19.30	Wash, 3 ft. deep, 20 lks. wide, drains N.
25.30	Road, bears N. and S.
40.555	Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 34, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.  $\begin{array}{c} \frac{1}{4} \\ S\ 27 \\ \hline S\ 34 \\ \hline 1956 \end{array}$  Deposit broken glass alongside iron post.
81.11	The cor. of secs. 27, 28, 33 and 34.  Land, level. Soil, sandy loam. No timber; undergrowth, greasewood and shadscale.
	N. 0° 26' W., bet. secs. 27 and 28.  Over level land.

Dependent Resurvey of the Subdivisional Lines, T. 19 S., R. 19 W.

40.335 Point for the  $\frac{1}{4}$  sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner.  
 Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.  
 $\frac{1}{4}$   
 S 28 | S 27  
 1956  
 Deposit broken glass alongside iron post.

80.67 Point for the cor. of secs. 21, 22, 27 and 28, at proportionate distance; there is no remaining evidence of the original corner.  
 Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.  
 T19S R19W  
 $\frac{S21 | S22}{S28 | S27}$   
 1956  
 Deposit broken glass alongside iron post.  
 Land, level.  
 Soil, sandy loam.  
 No timber; undergrowth, greasewood and shadscale.

From the cor. of secs. 22, 23, 26 and 27.  
 N. 89° 32' W., bet. secs. 22 and 27.  
 Over level land.  
 13.00 Road, bears NE. and SW.  
 21.50 Road, bears N. and S.  
 40.51 Point for the  $\frac{1}{4}$  sec. cor. of secs. 22 and 27, at proportionate distance; there is no remaining evidence of the original corner.  
 Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.  
 $\frac{1}{4}$   $\frac{S 22}{S 27}$   
 1956  
 Deposit broken glass alongside iron post.

81.02 The cor. of secs. 21, 22, 27 and 28.  
 Land, level.  
 Soil, sandy loam.  
 No timber; undergrowth, greasewood and shadscale.

N. 0° 01' W., bet. secs. 21 and 22.  
 Over level land.  
 40.335 Point for the  $\frac{1}{4}$  sec. cor. of secs. 21 and 22, at proportionate

Dependent Resurvey of the Subdivisional Lines, T19 S., R. 1

Chains

distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

S 21 | S 22  
1956

Deposit broken glass alongside iron post.

72.30

Small wash, drains NE.

80.67

Point for the cor. of secs. 15, 16, 21 and 22, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

T19S R19W  
S16 | S15  
S21 | S22  
1956

Deposit broken glass alongside iron post.

Land, level.

Soil, sandy loam.

No timber; undergrowth, greasewood and shadscale.

From the cor. of secs. 14, 15, 22 and 23.

N. 89° 47' W., bet. secs. 15 and 22.

Over level land.

13.60

Road, bears NE. and SW.

40.635

Point for the 1/4 sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

S 15  
1/4 S 22  
1956

Deposit broken glass alongside iron post.

73.30

Small wash, drains NE.

81.27

The cor. of secs. 15, 16, 21 and 22.

Land, level.

Soil, sandy loam.

No timber; undergrowth, greasewood and shadscale.

N. 0° 05' E., bet. secs. 15 and 16, 300 ft. W. 1/4 sec. 15.

Over level land.

40.335

Point for the 1/4 sec. cor. of secs. 15 and 16, at proportionate

Dependent Resurvey of the Subdivisional Lines, T. 19 S., R. 19 W.

Chains

distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

$\frac{1}{4}$   
 S 16 | S 15  
 1956

Deposit broken glass alongside iron post.

80.67 Point for the cor. of secs. 9, 10, 15 and 16, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

T19S R19W  
 S 9 | S10  
 S16 | S15  
 1956

Deposit broken glass alongside iron post.

Land, level.  
 Soil, sandy loam.  
 No timber; undergrowth, greasewood and shadscale.

From the cor. of secs. 10, 11, 14 and 15.

S. 89° 58' W., bet. secs. 10 and 15.

Over level land.

5.50 Ascend over E. slope of bench, bears NNE. and SSW.

6.20 Top of ascent; thence over level land.

24.20 Descend over W. slope of bench, bears N. and S.

26.00 Base of descent; thence over level land.

40.74 Point for the  $\frac{1}{4}$  sec. cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 20 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

$\frac{1}{4}$   
 S 10  
 S 15  
 1956

Deposit broken glass alongside iron post.

81.48 The cor. of secs. 9, 10, 15 and 16.

Land, level.  
 Soil, sandy loam.  
 No timber; undergrowth, greasewood and shadscale.

N. 0° 20' W., bet. secs. 9 and 10.

Over level land.

Chains	Description
40.335	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.</p> <p style="text-align: center;"><math>\frac{1}{4}</math> S 9   S 10 1956</p> <p>Deposit broken glass alongside iron post.</p>
69.30	<p>Wash, 4 ft. deep, 30 lks. wide, drains NE.</p>
80.67	<p>Point for the cor. of secs. 3, 4, 9 and 10, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.</p> <p style="text-align: center;">T19S R19W S 4   S 3 S 9   S 10 1956</p> <p>Deposit broken glass alongside iron post.</p> <p>Land, level. Soil, sandy loam. No timber; undergrowth, greasewood and shadscale.</p>
40.73	<p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>S. 89° 41' W., bet. secs. 3 and 10.</p> <p>Over level land.</p>
40.73	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 20 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.</p> <p style="text-align: center;"><math>\frac{1}{4}</math> S 3 S 10 1956</p> <p>Deposit broken glass alongside iron post.</p>
67.20	<p>Wash, 3 ft. deep, 20 lks. wide, drains NE.</p>
81.46	<p>The cor. of secs. 3, 4, 9 and 10.</p> <p>Land, level. Soil, sandy loam. No timber; undergrowth, greasewood and shadscale.</p>
40.34	<p>N. 0° 18' E., bet. secs. 3 and 4.</p> <p>Over level land.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 3 and 4, at proportionate</p>

Dependent Resurvey of the Subdivisional Lines, T. 19 S., R. 19 W.

Chains	distance; there is no remaining evidence of the original corner.
81.48	<p>Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.</p> <p style="text-align: center;">S 4   S 3 1956</p> <p>Deposit broken glass alongside iron post.</p> <p>The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp.</p> <p>Land, level. Soil, sandy loam. No timber; undergrowth, greasewood and shadscale.</p>
40.36	<p>From the cor. of secs. 32 and 33, on the S. bdy. of the Tp.</p> <p>N. 0° 02' W., bet. secs. 32 and 33.</p> <p>Over level land.</p> <p>Point for the 1/4 sec. cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.</p> <p style="text-align: center;">S 32   S 33 1956</p> <p>Deposit broken glass alongside iron post.</p>
80.72	<p>Point for the cor. of secs. 28, 29, 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.</p> <p style="text-align: center;">T19S R19W S29   S28 S32   S33 1956</p> <p>Deposit broken glass alongside iron post.</p> <p>Land, level. Soil, sandy loam. No timber; undergrowth, greasewood and shadscale.</p>
40.25	<p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>N. 89° 59' W., bet. secs. 28 and 33.</p> <p>Over level land.</p> <p>Point for the 1/4 sec. cor. of secs. 28 and 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.</p>

Chains

$$\begin{array}{r} \frac{1}{4} \text{ S } 28 \\ \text{S } 33 \\ 1956 \end{array}$$

Deposit broken glass alongside iron post.

80.50

The cor. of secs. 28, 29, 32 and 33.

Land, level.

Soil, sandy loam.

No timber; undergrowth, greasewood and shadscale.

N. 0° 09' W., bet. secs. 28 and 29.

Over level land.

40.36

Point for the  $\frac{1}{4}$  sec. cor. of secs. 28 and 29, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

$$\begin{array}{r} \frac{1}{4} \\ \text{S } 29 \text{ S } 28 \\ 1956 \end{array}$$

Deposit broken glass alongside iron post.

80.72

Point for the cor. of secs. 20, 21, 28 and 29, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

$$\begin{array}{r} \text{T19S R19W} \\ \text{S20 | S21} \\ \text{S29 | S28} \\ 1956 \end{array}$$

Deposit broken glass alongside iron post.

Land, level.

Soil, sandy loam.

No timber; undergrowth, greasewood and shadscale.

From the cor. of secs. 21, 22, 27 and 28.

N. 89° 57' W., bet. secs. 21 and 28.

Over level land.

32.90

Wash, drains NE.

40.055

Point for the  $\frac{1}{4}$  sec. cor. of secs. 21 and 28, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

$$\begin{array}{r} \frac{1}{4} \text{ S } 21 \\ \text{S } 28 \\ 1956 \end{array}$$

Deposit broken glass alongside iron post.

Dependent Resurvey of the Subdivisional Lines, T. 19 S., R. 19 W.

Chains

80.11

The cor. of secs. 20, 21, 28 and 29.

Land, level.

Soil, sandy loam.

No timber; undergrowth, greasewood and shadscale.

N. 0° 02' W., bet. secs. 20 and 21.

Over level land.

40.36

Point for the 1/4 sec. cor. of secs. 20 and 21, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

1/4 S 20 | S 21  
1956

Deposit broken glass alongside iron post.

80.72

Point for the cor. of secs. 16, 17, 20 and 21, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

T19S R19W  
S17 | S16  
S20 | S21  
1956

Deposit broken glass alongside iron post.

Land, level.

Soil, sandy loam.

No timber; undergrowth, greasewood and shadscale.

From the cor. of secs. 15, 16, 21 and 22.

N. 89° 55' W., bet. secs. 16 and 21.

Over level land.

40.06

Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

1/4 S 16  
S 21  
1956

Deposit broken glass alongside iron post.

80.12

The cor. of secs. 16, 17, 20 and 21.

Land, level.

Soil, sandy loam.

No timber; undergrowth, greasewood and shadscale.

Dependent Resurvey of the Subdivisional Lines, T. 19 S., R. 19

Chains

N. 0° 05' E., bet. secs. 16 and 17.  
Over level land.

11.06

40.36

Point for the 1/4 sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

1/4  
S 17 | S 16  
1956

Deposit broken glass alongside iron post.

80.72

Point for the cor. of secs. 8, 9, 16 and 17, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

T19S R19W  
S 8 | S 9  
S17 | S16  
1956

Deposit broken glass alongside iron post.

Land, level.  
Soil, sandy loam.  
No timber; undergrowth, greasewood and shadscale.

From the cor. of secs. 9, 10, 15 and 16.

N. 89° 50' W., bet. secs. 9 and 16.

Over level land.

40.04

Point for the 1/4 sec. cor. of secs. 9 and 16, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

1/4 S 9  
S16  
1956

Deposit broken glass alongside iron post.

80.08

The cor. of secs. 8, 9, 16 and 17.

Land, level.  
Soil, sandy loam.  
No timber; undergrowth, greasewood and shadscale.

N. 0° 20' W., bet. secs. 8 and 9.

Over level land.

1.50

Wash, drains NE.

5.50

Same wash, on curve, from SE. and draining NE.

Dependent Resurvey of the Subdivisional Lines, T. 19 S., R. 19 W.

Chains  
40.36

Point for the  $\frac{1}{2}$  sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

$\frac{1}{2}$   
S 8 | S 9  
1956

Deposit broken glass alongside iron post.

80.72

Point for the cor. of secs. 4, 5, 8 and 9, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 20 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

T19S R19W  
S 5 | S 4  
S 8 | S 9  
1956

Deposit broken glass alongside iron post.

Land, level.

Soil, sandy loam.

No timber; undergrowth, greasewood and shadscale.

From the cor. of secs. 3, 4, 9 and 10.

N. 89° 51' W., bet. secs. 4 and 9.

Over level land.

40.025

Point for the  $\frac{1}{2}$  sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 20 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

$\frac{1}{2}$  S 4  
S 9  
1956

Deposit broken glass alongside iron post.

80.05

The cor. of secs. 4, 5, 8 and 9.

Land, level.

Soil, sandy loam.

No timber; undergrowth, greasewood and shadscale.

N. 0° 11' W., bet. secs. 4 and 5.

Over level land.

80.50

Ascend 25 ft. over SE. slope, to the cor. of secs. 4, 5, 32 and 33.

40.36

Point for the  $\frac{1}{2}$  cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.

Chains

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

$\frac{1}{4}$   
S 5 | S 4  
1956

Deposit broken glass alongside iron post.

81.53

The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp.

Land, gently rolling SE. slope.

Soil, sandy loam and stony.

No timber; undergrowth, greasewood and shadscale.

From the cor. of secs. 31 and 32, on the S. bdy. of the Tp.

N. 0° 05' W., bet. secs. 31 and 32.

Over level land.

40.50

Point for the  $\frac{1}{4}$  sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

$\frac{1}{4}$   
S 31 | S 32  
1956

Deposit broken glass alongside iron post.

81.00

Point for the cor. of secs. 29, 30, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

T19S R19W  
S30 | S29  
S31 | S32  
1956

Deposit broken glass alongside iron post.

Land, level.

Soil, sandy loam.

No timber; undergrowth, greasewood and shadscale.

From the cor. of secs. 28, 29, 32 and 33.

S. 89° 51' W., bet. secs. 29 and 32.

Over level land.

40.755

Point for the  $\frac{1}{4}$  sec. cor. of secs. 29 and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

$\frac{1}{4}$  S 29  
S 32  
1956

Dependent Resurvey of the Subdivisional Lines, T. 19 S., R. 19 W.

Chains	
81.51	<p>Deposit broken glass alongside iron post.</p> <p>The cor. of secs. 29, 30, 31 and 32.</p>
	<p>Land, level.</p> <p>Soil, sandy loam.</p> <p>No timber; undergrowth, greasewood and shadscale.</p>
	<p>S. 89° 27' W., bet. secs. 30 and 31.</p>
40.36	<p>Over level land.</p> <p>Point for the ¼ sec. cor. of secs. 30 and 31, at proportionate distance; there is no remaining evidence of the original corner.</p>
	<p>Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.</p>
	<p style="text-align: center;"> <math display="block">\frac{1}{4} \begin{array}{l} S\ 30 \\ S\ 31 \\ 1956 \end{array}</math> </p>
	<p>Deposit broken glass alongside iron post.</p>
70.40	<p>Road, Gandy and Garrison, bears N. 2° 56' E. and S. 2° 56' W.</p>
75.80	<p>Wash, drains NNE.</p>
80.57	<p>The cor. of secs. 30 and 31, on the W. bdy. of the Tp.</p>
	<p>Land, level.</p> <p>Soil, sandy loam.</p> <p>No timber; undergrowth, greasewood and shadscale.</p>
40.50	<p>From the cor. of secs. 29, 30, 31 and 32.</p>
	<p>N. 0° 07' W., bet. secs. 29 and 30.</p>
	<p>Over level land.</p>
	<p>Point for the ¼ sec. cor. of secs. 29 and 30, at proportionate distance; there is no remaining evidence of the original corner.</p>
	<p>Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.</p>
	<p style="text-align: center;"> <math display="block">\frac{1}{4} \begin{array}{l} S\ 30\   \ S\ 29 \\ 1956 \end{array}</math> </p>
	<p>Deposit broken glass alongside iron post.</p>
81.00	<p>Point for the cor. of secs. 19, 20, 29 and 30, at proportionate distance; there is no remaining evidence of the original corner.</p>
	<p>Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.</p>
	<p style="text-align: center;"> T19S R19W  <math display="block">\frac{1}{4} \begin{array}{l} S19\   \ S20 \\ S30\   \ S29 \\ 1956 \end{array}</math> </p>
	<p>Deposit broken glass alongside iron post.</p>

Chains	<p>Land, level. Soil, sandy loam. No timber; undergrowth, greasewood and shadscale.</p>	<p>12.18</p>
<p>40.71</p>	<p>From the cor. of secs. 20, 21, 28 and 29. N. 89° 56' W., bet. secs. 20 and 29. Over level land. Point for the ¼ sec. cor. of secs. 20 and 29, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd. S 20 S 29 1956 Deposit broken glass alongside iron post.</p>	<p>12.18</p>
<p>81.42</p>	<p>The cor. of secs. 19, 20, 29 and 30. Land, level. Soil, sandy loam. No timber; undergrowth, greasewood and shadscale.</p>	<p>02.04</p>
<p>40.36</p>	<p>S. 89° 40' W., bet. secs. 19 and 30. Over level land. Point for the ¼ sec. cor. of secs. 19 and 30, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd. ¼ S 19 S 30 1956 Deposit broken glass alongside iron post.</p>	<p>02.04</p>
<p>65.70</p>	<p>Road, Gandy and Garrison, bears N. 2° 56' E. and S. 2° 56' W.</p>	<p>00.18</p>
<p>80.21</p>	<p>The cor. of secs. 19 and 30, on the W. bdy. of the Tp. Land, level. Soil, sandy loam. No timber; undergrowth, greasewood and shadscale.</p>	<p>00.18</p>
<p>40.50</p>	<p>From the cor. of secs. 19, 20, 29 and 30. N. 0° 27' E., bet. secs. 19 and 20. Over level land. Point for the ¼ sec. cor. of secs. 19 and 20, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.</p>	<p>00.18</p>

Dependent Resurvey of the Subdivisional Lines, T. 19 S., R. 19 W.

Chains

S 19 | S 20  
1956

Deposit broken glass alongside iron post.

81.00

Point for the cor. of secs. 17, 18, 19 and 20, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

T19S R19W  
S18 | S17  
S19 | S20  
1956

Deposit broken glass alongside iron post.

Land, level.  
Soil, sandy loam.  
No timber; undergrowth, greasewood and shadscale.

From the cor. of secs. 16, 17, 20 and 21.

N. 89° 45' W., bet. secs. 17 and 20.

Over level land,

40.34

Point for the ¼ sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

¼ S 17  
S 20  
1956

Deposit broken glass alongside iron post.

80.68

The cor. of secs. 17, 18, 19 and 20.

Land, level.  
Soil, sandy loam.  
No timber; undergrowth, greasewood and shadscale.

S. 89° 53' W., bet. secs. 18 and 19.

Over level land,

40.38

Point for the ¼ sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

¼ S 18  
S 19  
1956

Deposit broken glass alongside iron post.

62.70

Road, Gandy and Garrison, bears N. 2° 56' E. and S. 2° 56' W.

80.64

The cor. of secs. 18 and 19, on the W. bdy. of the Tp.

Chains	<p>Land, level. Soil, sandy loam. No timber; undergrowth, greasewood and shadscale.</p>
	<p>From the cor. of secs. 17, 18, 19 and 20. N. 0° 18' W., bet. secs. 17 and 18. Over level land.</p>
40.50	<p>Point for the 1/2 sec. cor. of secs. 17 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.</p> <p style="text-align: center;">1/2 S 18   S 17 1956</p> <p>Deposit broken glass alongside iron post.</p>
40.60	<p>Small wash, drains E.</p>
81.00	<p>Point for the cor. of secs. 7, 8, 17 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.</p> <p style="text-align: center;">T19S R19W S 7   S 8 S18   S17 1956</p> <p>Deposit broken glass alongside iron post.</p> <p>Land, level. Soil, sandy loam. No timber; undergrowth, greasewood and shadscale.</p>
1.60	<p>From the cor. of secs. 8, 9, 16 and 17. N. 89° 33' W., bet. secs. 8 and 17. Over level land.</p>
40.595	<p>Wash, drains NE.</p>
40.595	<p>Point for the 1/2 sec. cor. of secs. 8 and 17, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.</p> <p style="text-align: center;">1/2 S 8 S17 1956</p> <p>Deposit broken glass alongside iron post.</p>
81.19	<p>The cor. of secs. 7, 8, 17 and 18.</p> <p>Land, level. Soil, sandy loam. No timber; undergrowth, greasewood and shadscale.</p>

Dependent Resurvey of the Subdivisional Lines, T. 19 S., R. 19 W.

Chains

S. 89° 58' W., bet. secs. 7 and 18.

Over level land.

40.45

Point for the 1/4 sec. cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

S 7  
1/4 S 18  
1956

Deposit broken glass alongside iron post.

58.70

Road, Gandy and Garrison; bears N. 2° 56' E. and S. 2° 56' W.

80.49

The cor. of secs. 7 and 18, on the W. bdy. of the Tp.

Land, level.

Soil, sandy loam.

No timber; undergrowth, greasewood and shadscale.

From the cor. of secs. 7, 8, 17 and 18.

N. 0° 06' W., bet. secs. 7 and 8.

Over level land.

40.50

Point for the 1/4 sec. cor. of secs. 7 and 8, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

1/4  
S 7 | S 8  
1956

Deposit broken glass alongside iron post.

55.00

Ascend 17 ft. gradually over SE. slope to sec. cor.

81.00

Point for the cor. of secs. 5, 6, 7 and 8, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.

T19S R19W  
S 6 | S 5  
S 7 | S 8  
1956

Deposit broken glass alongside iron post.

Land, level.

Soil, sandy loam.

No timber; undergrowth, greasewood and shadscale.

From the cor. of secs. 4, 5, 8 and 9.

N. 89° 21' W., bet. secs. 5 and 8.

Dependent Resurvey of the Subdivisional Lines, T. 19 S.

Chains	Over level land.
40.43	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 20 ins. in the ground and in a mound of stone, to top of post, with brass cap</p> $\frac{1}{4} \frac{S\ 5}{S\ 8}$ <p>1956</p>
	<p>Deposit broken glass alongside iron post.</p> <p>from which</p> <p>A spring, bears S. <math>19^{\circ} 15'</math> E., 7.60 chs. dist.</p>
80.86	<p>The cor. of secs. 5, 6, 7 and 8.</p> <p>Land, level. Soil, sandy loam. No timber; undergrowth, greasewood and shadscale.</p>
	<p>S. <math>89^{\circ} 54'</math> W., bet. secs. 6 and 7.</p> <p>Over nearly level land, to rolling SSE. slope.</p>
15.80	<p>Leave greasewood undergrowth, bears NE. and SW.</p>
38.40	<p>Old U. S. Highway No. 6, bears NE. to Delta, Utah, and SW. to El Nevada.</p>
40.33	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 6 and 7, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 20 ins. in the ground and in a mound of stone, to top of post, with brass cap</p> $\frac{1}{4} \frac{S\ 6}{S\ 7}$ <p>1956</p>
	<p>Deposit broken glass alongside iron post.</p> <p>from which</p> <p>U.S.C. &amp; G.S., mkd. W 74, bench mark, bears N. <math>64^{\circ}</math> E., 2.05 chs. dist. 1934</p>
55.30	<p>Road, bears N. and S.</p>
76.75	<p>Wash, drains SE.</p>
80.46	<p>The cor. of secs. 6 and 7, on the W. bdy. of the Tp.</p> <p>Land, nearly level to rolling SE. slope. Soil, sandy loam to stony. No timber; undergrowth, greasewood east 15.80 chs. dist.; remainder of line west, shadscale.</p>
	<p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. <math>0^{\circ} 05'</math> W., bet. secs. 5 and 6.</p>

Dependent Reurvey of the Subdivisional Lines, T. 19 S., R. 19 W.

- Ascend 23 ft. gradually over SE. slope.  
 Leave greasewood undergrowth, bears NE. and SW.
- Point for the  $\frac{1}{2}$  sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 36 ins. long, 3 ins. diam., 27 ins. in the ground and in a mound of stone, to top of post, with brass cap mkd.
- $\frac{1}{2}$   
S 6 | S 5  
1956
- Deposit broken glass alongside iron post.
- Ascend 26 ft. gradually over SE. slope.
- Old U. S. Highway No. 6, bears NE. to Delta, Utah, and SW. to Ely, Nevada.
- Wash, drains E. to SE.
- The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp.
- Land, general SE. slope.  
 Soil, sandy loam and stony.  
 No timber; undergrowth, greasewood south 18.00 chs. dist.; remainder of line north, shadscale.

#### General Description

The land within this township consists principally of nearly level land in a broad valley extending northeasterly and southwesterly across the township. Portions of secs. 5, 6 and 7 lie on the NW. side of the valley and are gently rolling with a general SE. drainage. The east range of sections and portions of secs. 14, 23, 26 and 35 lie on the SE. side of this valley and are gently rolling to rolling land with a general westerly or northwesterly drainage. The central valley has a northeasterly drainage through several washes which disappear in the northeasterly part of the township. A dry lake or playa is located in the SE $\frac{1}{4}$  of sec. 24 and covers approximately 40 acres. Another, of approximately the same size, is located in the SW $\frac{1}{4}$  of sec. 13 and the NW $\frac{1}{4}$  NW $\frac{1}{4}$  of sec. 24. Elevations vary from approximately 5000 ft. in the valley to slightly over 5100 along the E. bdy. of the township and in sec. 6.

A spring is located in the NW $\frac{1}{4}$  NE $\frac{1}{4}$  of sec. 8 and a water well is located in the SW $\frac{1}{4}$  SE $\frac{1}{4}$  of sec. 35, and one in the north center part of the NE $\frac{1}{4}$  of sec. 26. A small reservoir is located in the NE. cor. of sec. 34. No other water was found in the township, although some old irrigation ditches are located in secs. 33, 34 and the W $\frac{1}{2}$  of sec. 35.

Old U. S. Highway No. 6 crosses secs. 5, 6 and 7 in a NE-SW. direction. A road runs from this old highway southerly from its junction in sec. 7 through the west range of sections to Garrison, Utah. Other roads cross the township from the SE. cor. of sec. 12 southerly and southwesterly. The Conger Ranch, consisting of a rock house and cattle corral is located in the NE $\frac{1}{4}$  of sec. 34. There are no other habitations in the township.

Chains

The soil is generally a gravelly clay. Medium dense greasewood covers the valley floor and shadscale is found on the rolling ben slopes.

The nearest town is Garrison, Utah, located about 12 miles south the township. No evidences of minerals were noted in the area.



CERTIFICATE OF CADASTRAL ENGINEER

I, Andrew Nelson, HEREBY CERTIFY upon honor that, pursuant of special instructions bearing date of the 30 day of April, 19

I have ~~XXXX~~ dependently resurveyed the north, south, east and west boundaries of the subdivision of Township 19 South, Range 19 West,

of the Salt Lake Meridian, in the State of Utah, which is represented in the foregoing field notes as having been executed by me and under my direction; and the said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Salt Lake City, Utah
July 16, 1957

Andrew Nelson, Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C., OCT 15 1957, 19

The foregoing field notes of the ~~survey of~~ dependent resurvey of the north, south, east, and west boundaries and the subdivision of T. 19 S., R. 19 W., SLM, Utah.

executed by Andrew Nelson, Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

Carl G. Harrington
Chief, Division of Cadastral Engineering
Cadastral Engineering Staff Officer

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes.

Chief, Division of Cadastral Engineering

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
Original

FIELD NOTES

of the

Retracement of Utah-Nevada State Line Between

Mile Posts Nos. 153 and 155;

Dependent Resurvey of North and South Boundaries

and

Subdivisional Lines

of

Fractional Township 19 South, Range 20 West

*Of the*

Salt Lake

*Meridian,*

*the State of*

Utah

EXECUTED BY

Andrew Nelson, Cadastral Surveyor

*Under special instructions dated April 30, 1956, which provided*

*the surveys included under Group No. 416, approved May 7, 1956*

*and assignment instructions dated June 12, 1956*

*Survey commenced July 12, 1956*

*Survey completed July 12, 1956*

# INDEX DIAGRAM

NEVADA  
UTAH.

Township 19 South, Range 20 West

						3
6	5	4	3	2		1 9
						8
7	8	9	10	11		12 8
						7
18	17	16	15	14		13 7
						5
19	20	21	22	23		24 6
						4
30	29	28	27	26		25 5
					M.P. 153	3
31	32	33	34	35		36 4
					M.P. 154	2

16-88770-1

1  
M.P. 155

1066

Fractional Township 19 South, Range 20 West, S.L.M.

Chains

The portion of the Utah-Nevada State Line forming the west boundary of Township 19 South, Range 20 West, was originally surveyed by I. E. James, Deputy Surveyor, in 1870. In 1942, under Group No. 266, Nevada, Philip L. Inch, Cadastral Engineer, resurveyed the State Line between Mile Posts 147 and 153 inclusive, in connection with the survey of T. 15 N., R. 71 E., M.D.M., Nevada. The north and south boundaries of T. 19 S., R. 20 W., were originally surveyed by A. J. Stewart, Jr., in 1882, and resurveyed by R. E. L. Collier, in 1895, who at that time subdivided this fractional township.

The following field notes are those of a retracement of the Utah-Nevada State Line between Mile Posts 153 and 155, and a dependent resurvey of the north and south boundaries and subdivisional lines of T. 19 S., R. 20 W., S.L.M., Utah.

For description of instrumental equipment used and tests thereof, see field notes of T. 19 S., R. 19 W., executed concurrently under same Group No. 416, Utah. The directions of the survey lines were determined from meridians established by observations upon Polaris and carried forward as transit lines. The geographic position for the SE. cor. of this township is in latitude  $39^{\circ} 06' 15''$  N., longitude  $114^{\circ} 02' 14''$  W. by computation from Mile Post No. 150 on the Utah-Nevada State Line, which is recorded by the U.S.C. & G.S. as being latitude  $39^{\circ} 09' 45.066''$  N., and longitude  $114^{\circ} 02' 52.298''$  W.

Retracement of A Portion of the Utah-Nevada State Line.

Retracement of Survey executed by  
I. E. James, Deputy Surveyor, in 1870.

Beginning at State Line Mile Post No. 153, marked by an iron post, 3 ins. diam., conforming to the 1942 record of survey of T. 15 N., R. 71 E., Nevada.

S.  $0^{\circ} 05'$  W., along the 154th Mile of Utah-Nevada State Line.

Over nearly level land, through short undergrowth.

1.55 Point for the closing cor. of secs. 25 and 36, T. 19 S., R. 20 W., Utah, hereinafter described.

41.54 Point for the W.  $\frac{1}{4}$  sec. cor. of sec. 36, T. 19 S., R. 20 W., hereinafter described.

80.18 State Mile Post, No. 154, marked by old wood post, 4x4 ins. x 36 ins. long, set in flat mound of earth, no discernible marks remaining.

A standard Grazing Service iron post is set alongside cor.

Land, nearly level valley.

Soil, gravelly clay.

Undergrowth, dense greasewood. No timber.

S.  $0^{\circ} 11'$  W., along the 155th Mile of the Utah-Nevada State Line.

Over nearly level land, through short undergrowth.

1.35 Point for the closing cor. of Ts. 19 and 20 S., R. 20 W., hereinafter described.

32.65 Dim road, bears NE. and SW.

40.35 Small ditch, drains SE.

42.17 The NW. cor. of wire fences, bears E. and S.; thence along fence.

## Retracement of A Portion of the Utah-Nevada State Line

Chains

79.82

State Mile Post No. 155, marked by broken pieces of old wood post lying on the ground, in fence line. No evidence of earth mound.

A standard Grazing Service iron post, is set at this point.

Land, nearly level.

Soil, gravelly clay.

Undergrowth, greasewood and shadscale. No timber.

Dependent Resurvey of South Boundary, T. 19 S., R. 20 W.

Reestablishment of Survey Executed by A. J. Stewart, Jr., in 1882  
Resurvey by R. E. L. Collier, in 1895.

Beginning at the cor. of Ts. 19 and 20 S., Rs. 19 and 20 W., marked by an iron post, 3 ins. diam., described in resurvey of T. 19 S., R. 19 W., executed concurrently under this group.

West, bet. secs. 1 and 36.

Over level land, through short undergrowth.

11.80

Old road, bears NW. and SE.

40.02

The  $\frac{1}{4}$  sec. cor. of secs. 1 and 36, marked by a quartzite stone, 14x9x3 ins., firmly set, and marked  $\frac{1}{4}$  on N. face.

At the cor. point

Set an iron post, 3 ins. diam., 36 ins. long, 27 ins. in the ground with brass cap mkd.

$$\begin{array}{r} \frac{1}{4} \text{ S } 36 \\ \text{S } 1 \\ 1956 \end{array}$$

Bury the original corner and deposit broken glass at base of post.

46.39

The closing cor. of Ts. 19 and 20 S., R. 20 W., on the Utah-Nevada State Line, marked by remains of old wood post; no marks remaining.

At the cor. point

Set an iron post, 3 ins. diam., 36 ins. long, 27 ins. in the ground with brass cap mkd.

$$\begin{array}{r|l} \text{N} & \text{T19S} \\ \text{E} & \text{R20W} \\ \text{V} & \frac{\text{S36}}{\text{S } 1} \text{ C} \\ & \text{T20S} \\ & 1956 \end{array}$$

Deposit broken glass at base, and place collar of rock around post.

From this closing cor., Mile Post No. 154 on the Utah-Nevada State Line, bears N.  $0^{\circ} 11' \text{ E.}$ , 1.35 chs. dist.

Land, level.

Soil, gravelly clay.

Undergrowth, dense greasewood and shadscale.

Dependent Resurvey of North Boundary, T. 19 S., R. 20 W.

Chains

Reestablishment of Survey Executed by A. J. Stewart, Jr., in 1882. Resurvey by R. E. L. Collier, in 1895.

From the cor. of Ts. 18 and 19 S., Rs. 19 and 20 W., marked by an iron post, 3 ins. diam., described in resurvey of T. 19 S., R. 19 W., executed concurrently under this group.

N. 89° 50' W., bet. secs. 1 and 36.

Over gently rolling land sloping SE.; asc. 80 ft. to W. bdy., through short undergrowth.

40.57 The 1/4 sec. cor. of secs. 1 and 36, marked by the center of a deeply embedded mound of stone; no marked stone could be found.

At the cor. point

Set an iron post, 1 in. diam., 36 ins. long, 27 ins. in the ground, with brass cap mkd.

S 36 / S 1 / 1956

Deposit broken glass at base, and raise small mound of stone around post.

46.16 The closing cor. of Ts. 18 and 19 S., R. 20 W., on the State Line, marked by a quartzite stone, 16x10x6 ins., marked with 6 grooves on 2 sides, and lying in a small mound of stone.

At the cor. point

Set an iron post, 2 ins. diam., 36 ins. long, 27 ins. in the ground, with brass cap mkd.

N T18S / E R20W. / V S 36 C / S 1 C / T19S / 1956

Bury the original stone at base, and raise a mound of stone around post.

From the cor., Mile Post No. 148, on the Utah-Nevada State Line, bears S. 0° 06' W., 5.53 chs. dist., which is marked by an iron post, 3 ins. diam., conforming to the record and described in field notes of the 1942 survey of T. 15 N., R. 71 E., M.D.M., Nevada.

Land, gently sloping bench. Soil, gravelly and stony. Undergrowth, short shadscale. No timber.

Dependent Resurvey, Subdivision, T. 19 S., R. 20 W.

Reestablishment of Surveys Executed by R. E. L. Collier, in 1895.

From the cor. of secs. 25 and 36, on E. bdy., which is marked by an iron post, 3 ins. diam., described in field notes of resurvey of T. 19 S., R. 19 W., executed concurrently under this group.

Dependent Resurvey, Subdivision, T. 19 S., R. 20 W.

Chains

S. 89° 59' W., bet. secs. 25 and 36.  
Over level land, through short undergrowth.

37.00

Dim old road, bears NW. and SE.

40.07

The 1/4 sec. cor. of secs. 25 and 36, marked by a quartzite stone, 18x9x3 ins., firmly set and marked 1/4 on N. face.

At the cor. point

Set an iron post, 3 ins. diam., 36 ins. long, 27 ins. in the ground with brass cap mkd.

1/4 S 25  
S 36  
1956

Bury the original stone and broken glass at base of post.

46.40

The closing cor. of secs. 25 and 36, on State Line, marked by a quartzite stone, 15x11x4 ins., and marked with 1 groove on S. and CC on E. face.

At the cor. point

Set an iron post, 3 ins. diam., 36 ins. long, 27 ins. in the ground with brass cap mkd.

N | T19S  
E | S 25 C  
V | S 36 C  
R20W  
1956

Bury the original stone at base of post.

From this cor., Mile Post No. 153 on the Utah-Nevada State Line, bears N. 0° 05' E., 1.55 chs. dist.

Land, level.

Soil, gravelly clay.

Undergrowth, greasewood and shadscale. No timber.

At point for the W. 1/4 sec. cor. of sec. 36, on the State Line and midpoint between the NW. and SW. corners of the sec.

Set an iron post, 3 ins. diam., 36 ins. long, 27 ins. in the ground with brass cap mkd.

N | 1/4  
E | S 36  
V | 1956

Deposit broken glass at base, and place collar of rock around post.

From this cor., the closing cor. of secs. 25 and 36, on the State Line, bears N. 0° 05' E., 39.99 chs. dist., and Mile Post No. 154, on the Utah-Nevada State Line, bears S. 0° 05' W., 38.64 chs. dist.

From the cor. of secs. 24 and 25, on E. bdy. of the township, which is marked by an iron post, 3 ins. diam., described in field notes of resurvey of W. bdy. of T. 19 S., R. 19 W., executed concurrently under this group.

## Dependent Resurvey, Subdivision, T. 19 S., R. 20 W.

Chains

S. 89° 59' W., bet. secs. 24 and 25.

Over level land, through short undergrowth.

40.04

The  $\frac{1}{4}$  sec. cor. of secs. 24 and 25, which is marked by a quartzite stone, 12x12x2 ins., firmly set and marked  $\frac{1}{4}$  on N. face.

At the cor. point

Set an iron post, 2 $\frac{1}{2}$  ins. diam., 30 ins. long, 20 ins. in the ground with brass cap mkd.

	S 24
$\frac{1}{4}$	S 25
	1956

Bury the original stone and broken glass at base of the post.

46.45

The closing cor. of secs. 24 and 25, on the Utah-Nevada State Line, marked by a quartzite stone, 15x10x4 ins., firmly set; no marks remaining.

At the cor. point

Set an iron post, 2 ins. diam., 36 ins. long, 27 ins. in the ground, with brass cap mkd.

N	T19S
E	S 24 C
V	S 25 C
	R20W
	1956

Bury the original stone and broken glass at base of post, and raise a small mound of stone around post.

From this cor., Mile Post No. 152 on the Utah-Nevada State Line, bears N. 0° 04' E., 1.36 chs. dist.; marked by an iron post, 3 ins. diam., conforming to the 1942 record and described in survey of T. 15 N., R. 71 E., M.D.M., Nevada.

Land, level.

Soil, gravelly clay.

Undergrowth, greasewood and shadscale. No timber.

At the point for the W.  $\frac{1}{4}$  sec. cor. of sec. 25, on the Utah-Nevada State Line, and midpoint bet. the NW. and SW. corners of this sec.

Set an iron post, 1 in. diam., 36 ins. long, 27 ins. in the ground, with brass cap mkd.

N	$\frac{1}{4}$
E	S 25
V	1956

Deposit broken glass at base, and place collar of rock around post.

From this  $\frac{1}{4}$  sec. cor., the closing cor. of Ts. 14 and 15 N., R. 71 E., on State Line, bears S. 0° 04' W., 17.115 chs. dist.; which is marked by an iron post, 3 ins. diam., conforming to the record and described in the survey of T. 15 S., R. 71 E., M.D.M., Nevada.

From the cor. of secs. 13 and 24, on the E. bdy. of the township, which is marked by an iron post, 3 ins. diam., and described in field notes of resurvey of W. bdy., T. 19 S., R. 19 W., executed concurrently under this group.

Chains

West, bet. secs. 13 and 24.

Over level land, through short undergrowth.

8.30 Old road, bears NE. and SW.

25.30 Small drain, 2 ft. deep, course NE.

39.99 The  $\frac{1}{4}$  sec. cor. of secs. 13 and 24, marked by a quartzite stone, 14x13x3 ins., loosely set, no marks remaining.

At the cor. point

Set an iron post, 2 $\frac{1}{2}$  ins. diam., 30 ins. long, 20 ins. in the ground with brass cap mkd.

$\frac{1}{4}$   $\frac{S\ 13}{S\ 24}$   
1956

Bury the original stone and broken glass at the base of post, and raise a small collar of rock around post.

46.62 The closing cor. of secs. 13 and 24, on the State Line, marked by a quartzite stone, 15x8x3 ins., firmly set, no marks remaining.

At the cor. point

Set an iron post, 2 $\frac{1}{2}$  ins. diam., 30 ins. long, 20 ins. in the ground with brass cap mkd.

N | T19S  
E | S 13 C  
V | S 24 C  
R20W  
1956

Bury the original stone and broken glass at base of post.

From this cor., Mile Post No. 151 on the Utah-Nevada State Line, bears N. 0° 01' W., 1.32 chs. dist., which is marked by an iron post, 3 ins. diam., conforming to the 1942 record as described in field notes of survey T. 15 N., R. 71 E., M.D.M., Nevada.

Land, nearly level.

Soil, gravelly clay.

Undergrowth, greasewood and shadscale.

At the point for the W.  $\frac{1}{4}$  sec. cor. of sec. 24, on the State Line, and midpoint bet. the NW. and SW. corners of the sec.

Set an iron post, 2 $\frac{1}{2}$  ins. diam., 30 ins. long, 20 ins. in the ground with brass cap mkd.

N |  $\frac{1}{4}$   
E | S 24  
V | 1956

Deposit broken glass at base, and place collar of rock around post.

From this cor., the closing cor. of secs. 30 and 31, on E. bdy. of T. 15 N., R. 71 E., M.D.M., Nevada, bears S. 0° 01' E., 17.155 chs. dist.; marked by an iron post, 2 ins. diam., conforming to the 1942 record of survey of above township.

331

Dependent Resurvey, Subdivision, T. 19 S., R. 20 W.

Chains

From the cor. of secs. 12 and 13, on E. bdy. of township, which is marked by an iron post, 3 ins. diam., described in field notes of resurvey of W. bdy. of T. 19 S., R. 19 W., executed concurrently under this group.

S. 89° 43' W., bet. secs. 12 and 13.

Over nearly level land, through short undergrowth.

32.80

The old Delta-Ely road, bears N. 41° E. and S. 41° W.

40.00

The 1/4 sec. cor. of secs. 12 and 13, marked by a quartzite stone, 12x9x4 ins., firmly set and marked 1/4 on N. face.

At the cor. point

Set an iron post, 2 1/2 ins. diam., 30 ins. long, 20 ins. in the ground, with brass cap mkd.

1/4	S 12
	S 13
	1956

Bury the original stone and deposit broken glass at base of post; also place collar of rock around the post.

46.27

The closing cor. of secs. 12 and 13, on the State Line, marked by a quartzite stone, 16x10x6 ins., firmly set, marked with 4 grooves on S., 2 grooves on N., and CC on E. face.

At the cor. point.

Set an iron post, 2 1/2 ins. diam., 30 ins. long, 20 ins. in the ground, with brass cap mkd.

N	T19S
E	S 12 C
V	S 13 C
	R20W
	1956

Bury the original stone and deposit glass at base of post.

From this cor., Mile Post No. 150, on the Utah-Nevada State Line, bears N. 0° 04' E., 1.31 chs. dist., which is marked by an iron post 3 ins. diam., conforming to the 1942 record and described in survey of T. 15 N., R. 71 E., M.D.M., Nevada.

Land, nearly level.

Soil, gravelly clay.

Undergrowth, greasewood and shadscale. No timber.

At the point for W. 1/4 sec. cor. of sec. 13, on the Utah-Nevada State Line, and midpoint bet. the NW. and SW. corners of the sec.

Set an iron post, 2 1/2 ins. diam., 30 ins. long, 20 ins. in the ground, with brass cap mkd.

N	1/4
E	S 13
V	1956

Deposit broken glass at base, and place collar of rock around post.

Dependent Resurvey, Subdivision: T. 15 N., R. 71 E., M.D.M., Nevada.

Chains

chain 30

From this cor. the closing cor. of secs. 19 and 30, on E. bdy. of T. 15 N., R. 71 E., bears S. 0° 04' W., 17.25 chs. dist., which is marked by an iron post, 2 ins. diam., conforming to the 1942 record and described in survey of T. 15 N., R. 71 E., M.D.M., Nevada.


From the cor. of secs. 1 and 12, on E. bdy. of the township, which is marked by an iron post, 2½ ins. diam. and described in field notes of resurvey of W. bdy. of T. 19 S., R. 19 W., executed concurrently under this group.

S. 89° 54' W., bet. secs. 1 and 12.  
Over nearly level land.

14.60 Dim old road, bears NW. and SE.

39.70 Point selected for witness ¼ sec. cor. of secs. 1 and 12.

Set an iron post, 2½ ins. diam., 30 ins. long, 20 ins. in the ground, with brass cap mkd.




Deposit broken glass at base, and place collar of rock around post.

40.01 True point for ¼ sec. cor. at proportionate dist.; found the original cor., a quartzite stone, 14x10x3 ins., marked ¼ on one face, out of place lying in small drain 2 ft. deep, course SE. Bury stone, 1 ft. beneath ground at this point.

46.26 The closing cor. of secs. 1 and 12, on the State Line, marked by a quartzite stone, 14x12x4 ins., firmly set, marked with 5 grooves on S. and 1 groove on N.; no CC on stone.

At the cor. point

Set an iron post, 2½ ins. diam., 30 ins. long, 20 ins. in the ground, with brass cap mkd.



Bury the original stone at base of post; deposit glass at base, and place collar of rock around post.

From this cor., State Line Mile Post No. 149, bears N. 0° 04' W., 1.07 chs. dist, which is marked by an iron post, 3 ins. diam., conforming to the 1942 record and described in survey of T. 15 N., R. 71 E., M.D.M., Nevada.

Land, nearly level.  
Soil, gravelly clay.  
Undergrowth, shadscale. No timber.

At the point for W. ¼ sec. cor. of sec. 12, on the Utah-Nevada State Line, and midpoint bet. the NW. and SW. corners of the sec.

Set an iron post, 2½ ins. diam., 30 ins. long, 20 ins. in the ground, with brass cap mkd.

Dependent Resurvey, Subdivision, T. 19 S., R. 20. W.

Chains

N | ¼  
E | S 12  
V  
1956

Deposit broken glass at base, and place collar of rock around post.

From this cor. the closing cor. of secs. 18 and 19, on E. bdy., T. 15 N., R. 71 E., M.D.M., Nevada, bears S. 0°04' E., 17.25 chs. dist., which is marked by an iron post, 2 ins. diam., conforming to the 1942 survey record of T. 15 N., R. 71 E., M.D.M., Nevada.

At point for the W. ½ sec. cor. of sec. 1, on the Utah-Nevada State Line, and at proportionate dist., bet. the NW. and SW. corners of the sec.

Set an iron post, 2½ ins. diam., 30 ins. long, 20 ins. in the ground, with brass cap mkd.

N | ¼  
E | S 1  
V  
1956

Deposit glass at base, and place collar of rock around post.

From this cor., the closing cor. of secs. 7 and 18, on E. bdy. of T. 15 N., R. 71 E., M.D.M., Nevada, bears S. 0° 05' W., 17.31 chs. dist., which is marked by an iron post, 2 ins. diam., conforming to the 1942 survey record of that township.

General Description

The land within this fractional township is mostly nearly level valley land with easterly drainage. Section 1 lies on bench slope facing SE. The soil in general is a gravelly clay. Medium dense greasewood covers the valley bottom, shadscale is found on the bench slope. The only water is at Caine Spring located in sec. 25, near the State Line. The old highway between Delta, Utah, and Ely, Nevada, extends through secs. 12 and 13 in a NE. and SW. direction. There are no settlers in this township.

Chains		Chains
	<p>1. The following table shows the number of chains of stores in the United States, by type of store, for the years 1910 to 1920.</p>	<p>of in reco</p>
	<p>2. The following table shows the number of chains of stores in the United States, by type of store, for the years 1910 to 1920.</p>	
	<p>3. The following table shows the number of chains of stores in the United States, by type of store, for the years 1910 to 1920.</p>	
	<p>4. The following table shows the number of chains of stores in the United States, by type of store, for the years 1910 to 1920.</p>	
	<p>5. The following table shows the number of chains of stores in the United States, by type of store, for the years 1910 to 1920.</p>	
	<p>6. The following table shows the number of chains of stores in the United States, by type of store, for the years 1910 to 1920.</p>	
	<p>7. The following table shows the number of chains of stores in the United States, by type of store, for the years 1910 to 1920.</p>	
	<p>8. The following table shows the number of chains of stores in the United States, by type of store, for the years 1910 to 1920.</p>	
	<p>9. The following table shows the number of chains of stores in the United States, by type of store, for the years 1910 to 1920.</p>	
	<p>10. The following table shows the number of chains of stores in the United States, by type of store, for the years 1910 to 1920.</p>	
	<p>11. The following table shows the number of chains of stores in the United States, by type of store, for the years 1910 to 1920.</p>	



CERTIFICATE OF CADASTRAL ENGINEER

I, Andrew Nelson, HEREBY CERTIFY upon honor that, pursuance of special instructions bearing date of the 30th day of April, 1957, I have surveyed retraced the Utah-Nevada State Line between Mile Posts Nos. 153 and 155 and dependently resurveyed the north and south boundaries and subdivisional lines of fractional Township 19 South, Range 20 West.

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Salt Lake City, Utah
July 17, 1957

Andrew Nelson
Andrew Nelson, Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C., OCT 15 1957, 19

The foregoing field notes of the surveyed retracement of the Utah-Nevada State Line between Mile Posts Nos. 153 and 155; and the dependent resurvey of the north and south boundaries and subdivisional lines of fractional Township 19 South, Range 20 West.

executed by Andrew Nelson, Cadastral Surveyor
having been critically examined and found correct, are hereby approved.

Earl G. Harrington
Chief, Division of Cadastral Engineering
Cadastral Engineering Staff Officer

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in \_\_\_\_\_, is a true copy of the original field notes.

Chief, Division of Cadastral Engineering.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GENERAL LAND OFFICE

FIELD NOTES

OF

INDEPENDENT RESURVEY OF THE WEST BOUNDARY, T. 20 S., R. 7 W., AND THE  
WEST BOUNDARY AND SUBDIVISION OF, T. 20 S., R. 8 W.

Of the SALT LAKE Meridian,  
the State of UTAH

EXECUTED BY

ANDREW NELSON, SURVEYOR

Under special instructions dated April 7, 1939, which provided  
the surveys included under Group No. 299, bearing the approval of the  
Commissioner of the General Land Office under date of May 25, 1939  
assignment instructions dated May 9, 1940.

Survey commenced June 6, 1940.

Survey completed June 19, 1940.

# INDEX DIAGRAM.

Township 20 South , Range 8 West

14	• 52	• 43	• 35	• 28	• 22	• 1	6
	52	51	42	35	28	21	
13	7 51	8 42	9 34	10 27	11 20	12	5
	50	50	41	33	26	20	
11	13 49	17 40	16 33	15 26	14 19	13	4
	49	48	40	32	25	18	
10	19 47	20 39	21 31	22 25	23 18	24	3
	47	46	38	31	24	17	
8	20 46	29 37	28 30	27 23	26 16	25	3
	45	45	37	30	23	16	
7	21 44	28 36	28 29	24 22	25 15	26	2

## DEPENDENT RESURVEY OF T. 20 S., R. 8 W.

The official survey of T. 20 S., R. 8 W., Salt Lake Meridian, Utah, is shown upon plat approved February 26, 1872. The following field notes are those of a dependent restoration of the east and west boundaries, and subdivisional lines. The survey is a restoration of the original lines in their true original positions according to the identified evidence. Before reconstructing or restoring a corner, the lines of the original survey were retraced, and a search was made for evidence of the original corner monuments and other calls of the field notes. After completing the necessary retracements, the rules of proportionate measurement were applied to ascertain the position of each lost corner, and when duly identified or restored, the corner positions were properly re-monumented with the regulation iron survey posts.

The retracement data were submitted to the office for examination and verification, and in order to simplify the record, only the true line notes referring to the completed resurvey, are supplied here.

The resurvey was commenced June 6, 1940, and executed with Buff & Buff solar transit No. 16726, the property of the General Land Office. The horizontal plate of the instrument is provided with two double verniers, graduated to single minutes of arc, and has a full vertical circle provided with one double vernier, also graduated to single minutes of arc. The solar attachment was not used on this survey, and no description of it will be given here. The instrument was in good adjustment and was approved for use on this assignment by the district cadastral engineer for Utah, in assignment instructions dated May 9, 1940; conditional upon satisfactory field tests. These tests were made in the field prior to the commencement of the field work and the instrument was found to be free from appreciable error.

The geographic position of the south-east corner of the township is approximately as follows; latitude  $39^{\circ}01' N.$ , longitude  $112^{\circ}41' W.$

The measurements were made with a Lallie steel tape, 8 chains in length. The tape is graduated every link for the first chain and thereafter at intervals of 10 links. The tape was tested by comparison with a Lufkin standard tape, 1 chain in length, and found correct. The measurements were made on the slope, the vertical angle of each interval determined by the use of clinometers, and the slope distances properly reduced to true horizontal equivalents, which appear in these notes.

All azimuth determinations were made by reference to true meridians as established from hour angle observations made upon Polaris during the progress of the work. The lines were carried forward as transit lines, taking the mean of direct and reversed sights at each transit point.

June 2, 1940; at the standard corner of townships 20 south, ranges 7 and 8 west, in approximate latitude  $39^{\circ}01' N.$ , longitude  $112^{\circ}41' W.$ , at a mean time 7h 49m 36s p.m. by my watch which is 12s slow of 105th meridian standard time, determined by comparison with radio time signals on this day, I observe Polaris, west of the meridian, making four settings, two each with the telescope in direct and reversed positions, reading the time of each setting and the horizontal angle westward from the star to a definite point on center knob of black butte about 9 miles distant to the northwest.

Azimuth of Polaris at time of obser.	$0^{\circ} 32.3' W.$
Horizontal angle star to reference	$30^{\circ} 57.1$
True bearing to reference	$N. 31^{\circ} 29.4' W.$

## DEPENDENT RESURVEY OF T. 20 S., R. 8 W.

Chains

All of the exterior and subdivisinal lines of this township were surveyed by Julien Bausmah in 1871. In 1891 George O. Chaney resurveyed the west boundary, or Guide Meridian, and A.J. Stewart, Jr., the south boundary in 1892. The south boundary was again resurveyed in 1937 under Group No. 255 by Ralph Gentry. The north boundary is resurveyed under Group No. 299 by Andrew Nelson in 1940 while resurveying T. 19 S., R. 8 W.

## DEPENDENT RESURVEY OF WEST BOUNDARY, T. 20 S., R. 7 W.

Reestablishment of surveys executed by Julien Bausmah, Deputy Surveyor in 1871.

Beginning at the standard cor. of Ts. 20 S., Rs. 7 and 8 W., on the 4th Standard Parallel South; an iron post, 3 ins. diam., properly set, marked and witnessed as described in the official record of the survey T. 21 S., R. 7 W.

Note: The closing cor. of Ts. 21 S., Rs. 7 and 8 W., is N. 89°40' W., 0.96 chs. dist.

Thence with true resurvey line.

N. 0°26' E., bet. secs. 31 and 36.

Over nearly level land, through medium dense short undergrowth.

17.00 Dim unimproved road, bears NE. and SW.

40.39 The original  $\frac{1}{4}$  sec. cor., a volcanic stone, 16 x 10 x 6 ins., lying on the ground and partly covered, plainly marked  $\frac{1}{4}$  on one face; unwitnessed.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with the stone cor. deposited alongside, for  $\frac{1}{4}$  sec. cor., with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ \hline \text{S36} \mid \text{S31} \\ \hline 1940 \end{array}$$

raise a mound of stone 2 ft. base, 1 $\frac{1}{2}$  ft. high, W. of cor.

Continue same course, beginning new measurement.

40.38 The original cor. secs. 25, 30, 31, and 36, a volcanic rock, 15 x 10 x 8 ins., firmly set, properly marked with 5 notches on N., and 1 notch on S. edge; unwitnessed.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, stone cor. deposited alongside, for cor. secs. 25, 30, 31, and 36, with brass cap marked

$$\begin{array}{c} \text{T20S} \\ \text{R8W R7W} \\ \hline \text{S25} \mid \text{S30} \\ \hline \text{S36} \mid \text{S31} \\ \hline 1940 \end{array}$$

DEPENDENT RESURVEY WEST BOUNDARY, T. 20 S., R. 7 W.

Chains


40.27 Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.  
 Band, nearly level desert; surface broken on portion of mile by small sandy hummocks and sandy rises.  
 Soil, sandy clay; loose sand; lying on hard clay subsoil; 3rd rate.  
 Undergrowth, shadscale, yellow top, scattered greasewood and patches of grass.  
 Fair grazing.

N. 0°36' E., bet. secs. 25 and 30.

Over nearly level desert land, through short undergrowth.

40.28 The original ¼ sec. cor., a volcanic rock, 12 x 12 x 12 ins., lying on the ground, marked ¼ on one face; unwitnessed.  
 At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with stone cor. deposited alongside, for ¼ sec.  
 with brass cap marked




No accessories available.

Thence, N. 0°34' E.,

40.28 The original cor. of secs. 19, 24, 25, and 30, a volcanic rock, 16 x 10 x 8 ins., firmly set, marked with 4 notches on N., and 2 notches on S. edge; unwitnessed.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with stone cor. alongside, for cor. secs. 19, 24, 25, and 30, with brass cap marked



raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, nearly level desert.  
 Soil, sandy clay; 3rd rate.  
 Undergrowth, shadscale and scattered patches of grass.  
 Fair grazing.

N. 0°29' E., bet. secs. 19 and 24.

Over nearly level desert land through scattered short undergrowth.

DEPENDANT RESURVEY WEST BOUNDARY. T. 20 S., R. 7 W.

Trains

27.20 American Telephone and Telegraph Company's line, 10 wires bears N. 34°17' E. and S. 34°17' W.

27.21 Dir. road parallel to telephone line,

27.22 The original  $\frac{1}{4}$  sec. cor., a volcanic rock, 18 x 16 x 4 in. firmly set, marked  $\frac{1}{4}$  on N. face; unwitnessed.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with stone cor. deposited alongside, for  $\frac{1}{4}$  sec. cor., with brass cap marked



raise a

mound of stone, 2 ft. base, 1 1/2 ft. high, W. of post.


continue on same course, beginning new measurement.

27.23 Dir. road, bears N. 85° W. and S. 85° E.

27.24 The original cor. of secs. 13, 18, 19, and 24, a volcanic rock, 18 x 16 x 4 ins., firmly set, marked  $\frac{1}{4}$  notches on N. and S. faces; unwitnessed.

At point for cor.

Set an iron post, 3 ft. long, .2 ins. diam., 27 ins. in the ground, with the stone cor. deposited alongside, for cor. secs. 13, 18, 19, and 24, with brass cap marked



1940

raise a

mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

land, nearly level desert.

soil, sandy clay and heavy clay; 3rd rate.

salsolene, medium dense shadscale, greasewood, and some scattered grass.

air grazing.

27.25 ... set. secs. 13 and 18.

over nearly level desert land, through medium dense short salsolene.

27.26 ... appropriate distance; no evidence of the old  $\frac{1}{4}$  sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked



DEPENDENT RESURVEY OF WEST BOUNDARY, T. 20 S., R. 7 W.

Chains

Deposit a volcanic rock, 12 x 8 x 3 ins., marked X, at base of post.

42.20 Dim road, bears N. 30° W. and S: 30° E.

80.80 The original cor. of secs. 7, 12, 13, and 18, a volcanic rock, 16 x 15 x 7 ins., firmly set, marked 2 notches on N. and 4 notches on S. edge; unwitnessed.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with the original cor. stone deposited alongside, for cor. secs. 7, 12, 13, and 18, with brass cap marked

T20S	
R8W	R7W
S12	S7
S13	S18

1940

raise a

small mound of stone, W. of post.

Land, nearly level desert.

Soil, heavy clay; 3rd rate.

Undergrowth, greasewood, shadscale, and salt brush.

Fair grazing.

N. 0°27' E., bet. secs. 7 and 12.

Over nearly level desert land, through medium dense short undergrowth.

11.90 Dim road, parallel to S. side of canal.

12.60 A main canal (now abandoned) 30 lks. wide, 5 ft. deep, drains N. 41° W.

35.20 Old unused canal, 10 lks. wide, drains NW. for about 2 chs. thence nearly N.

40.24 The original ¼ sec. cor., a volcanic rock, 10 x 8 x 4 ins., firmly set, and very dimly marked ¼.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with stone cor. deposited alongside, for ¼ sec. cor., with brass cap marked

¼	
S12	S7

1940

raise a

small mound of stone, W. of post.

Thence, N. 0°26' E.

1.80 Recross last mentioned canal, drains N. 10° E.

6.50 Recross same, drains N. 70° W.

## DEPENDENT RESURVEY OF WEST BOUNDARY, T. 20 S., R. 7 W.

Chains

21.00 Leave greasewood and enter salt brush, bears NW. and SE.

40.37 The original cor. of secs. 1, 6, 7, and 12, a volcanic stone, 18 x 12 x 4 ins., lying on the ground, properly marked with 1 notch on 1 edge and 5 notches on opposite edge; unwitnessed.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with stone cor. deposited alongside, for cor. of secs. 1, 6, 7, and 12, with brass cap marked.

T20S	
R8W	R7W
S1	S6
S12	S7

1940

raise a

 mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Land, nearly level.

Soil, clay and wet alkali clay; 3rd and 4th rates.

Undergrowth, greasewood and salt brush.

Fair grazing.

N. 0°23' E., bet. secs. 1 and 6.

Over level alkali flat, through short salt brush.

9.10 Graded road between Fillmore and Clear Lake Station, bears N. 67° W. and S. 67° E.

40.25 The original ¼ sec. cor.; a volcanic stone, 16 x 8 x 8 ins. firmly set, marked ¼ on W. face; unwitnessed.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with stone cor. deposited alongside, for ¼ sec. cor., with brass cap marked.

¼	
S1	S6

1940

raise a

 small mound of stone W. of post.

Thence, N. 0°26' E.

40.44 The official cor. of Ts. 19 and 20 S., Rs. 7 and 8 W., an iron post, 3 ins. diam., properly set, marked and witnessed as described in the official record of resurvey of T. 19 S., R. 8 W., this group.

Land, level alkali flat, surface broken on N. half mile by a few low sandy hummocks.

Soil, wet alkali clay; 4th rate.

Undergrowth, scattered salt brush and weeds.

Poor grazing.

## DEPENDENT RESURVEY OF WEST BOUNDARY, T. 20 S., R. 8 W.

Chains

Reestablishment of surveys executed by Julien Bausman in 1871, and resurveyed by George O Chaney in 1891.

June 3, 1940: At the standard cor. of Ts. 20 S., Rs. 8 and 9 W., in approximate latitude  $39^{\circ}01'$  N., longitude  $112^{\circ}48'$  W., at a mean time, 6h 32m 46s p.m. by my watch which is 12s slow of 105th meridian time, I observe Polaris west of the meridian making four settings, two each with the telescope in direct and reversed positions, recording the time of each setting and the horizontal angle westward from the star to a mound of stone on a peak about 5 miles distant northwesterly.

Azimuth of Polaris at observation	$0^{\circ}53'.0'$ W.
Horizontal angle star to reference	$27^{\circ}48'.0'$
True bearing of reference mound	N. $28^{\circ}41'$ W.

From the above cor., high point on Sugar Leaf mountain, in T. 19 S., R. 6 W., bears N.  $61^{\circ}18'$  E.; top of sharp pointed hill about 25 miles distant, bears S.  $5^{\circ}13'$  E.; sharp peak in mountain range, bears S.  $76^{\circ}29'$  W., about 8 miles distant; and stone mound on high peak about 4 miles distant, bears N.  $54^{\circ}18'$  W. The closing cor. of Ts. 21 S., Rs. 8 and 9 W.; an iron post,  $\frac{3}{8}$  ins. diam., bears W., 1.24 chs. dist.

The standard cor. of Ts. 20 S., Rs. 8 and 9 W., on the 4th standard parallel south, is an iron post,  $\frac{3}{8}$  ins. diam., properly set, marked and witnessed as described in the official record of survey of T. 21 S., R. 8 W., Group No. 255, Utah.

Thence on true resurvey line from the above cor.

N.  $0^{\circ}51'$  E., along the W. bdy. of sec. 31, T. 20 S., R. 8 W.

Over gently rolling desert land, with a general easterly slope, through medium dense shadscale.

6.60 Trail or very dim trace of unused road, bears NE. and SW. Begin gradual ascent.

25.00 Top of rise, 30 ft. above cor., bears W. and slopes E.

40.05 The  $\frac{1}{4}$  sec. cor. on the E. bdy. of sec. 36, a quartzite stone, 16 x 10 x 4 ins., firmly set, marked  $\frac{1}{4}$  on W. face; unwitnessed.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, stone cor. deposited alongside, for  $\frac{1}{4}$  sec. cor. E. bdy. sec. 36, with brass cap marked

$\frac{1}{4}$   
S36

1940

raise a small mound of stone W. of post.

40.34 The  $\frac{1}{4}$  sec. cor. on W. bdy. sec. 31, a decayed portion of cedar post, no marks remaining.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with old cor. and glass deposited at base, for  $\frac{1}{4}$

DEPENDENT RESURVEY OF WEST BOUNDARY

Chains

sec. cor. on N. bdy. sec. 24, with brass cap marked

S31

small mound of stone E. of post. Thence, N. 0°09' E.

1.70 Descend gradual NE. slope, bears NW.

10.70 Base of gradual descent, bears NW. and SE.

39.67 The cor. of secs. 25 and 30, a quartzite stone, 18 x 8 x 4 ins., firmly set, marked with 5 notches on N., 4 notches on S., and 6 notches on W. edge; unwitnessed.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, stone cor. deposited alongside, for cor. secs. 25 and 36, T. 20 S., R. 9 W., with brass cap marked

T20S	T20S
.825	R8W
S36	S31
R9W	

1940

small mound of stone, E. of post.

40.25 The cor. of secs. 30 and 31, a portion of a decayed cedar post lying on the ground, no marks remaining.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, old cor. monument deposited alongside, for cor. of secs. 30 and 31, T. 20 S., R. 8 W., with brass cap marked

T20S	T20S
.825	S30
R9W	S31
	R8W

1940

small mound E. of post.

Cor. set on slight E. slope, 35 ft. below top of rise.

Land, gently rolling desert with general easterly slope. Soil, sandy clay; 2nd rate. Undergrowth, medium dense short shrubs; scattered grass. Pair grazing.

N. 0°36' E., along the N. bdy. of sec. 30

Over nearly level desert with general easterly slope, through short undergrowth.

DEPENDENT RESURVEY OF WEST BOUNDARY, T. 20 S., R. 9 W.

Chains

0.70 Unimproved road, bears N. 65° E. and S. 65° W.

9.30 Shallow wash, drains NE.

39.43 The  $\frac{1}{4}$  sec. cor. on E. bdy. of sec. 25, a quartzite stone, 20 x 10 x 7 ins., firmly set and marked on W. face; unwitnessed.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, stone cor. deposited alongside, for  $\frac{1}{4}$  sec. cor. on E. bdy. sec. 25, with brass cap marked

$\frac{1}{4}$  |  
S25

1940

raise a small mound of stone W. of post.

40.30 The  $\frac{1}{4}$  sec. cor. on W. bdy. of sec. 30, a cedar post, 2 ft. long, 2 ins. diam., lying on the ground, marked on one side, and R8W on opposite side.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old wood post cor. set alongside, for  $\frac{1}{4}$  sec. cor. on W. bdy. sec. 30, with brass cap marked

|  $\frac{1}{4}$   
S30

1940

raise a small mound of stone E. of post.

Thence, N. 0°26' E.

10.00 The S. top of low rise, bears NW. and slopes SE.

19.70 The N. edge of same, bears NW. and SE.; gently descend.

39.10 The cor. of secs. 24 and 25, a quartzite stone, 16 x 12 x 5 ins., loosely set, marked 4 notches on N., 2 notches on S., and 6 notches on W. edge; unwitnessed.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, stone cor. deposited alongside, for cor. secs. 24 and 25, T. 20 S., R. 9 W., with brass cap marked

T20S	T20S
S24	
	R8W
S25	
R9W	S30

1940

raise a small mound of stone, W. of post.

40.32 The cor. of secs. 19 and 30, a cedar post, 2 ft. long, 2 ins. diam., lying on ground, no marks remaining.

DEPARTMENT OF THE INTERIOR

Chains

At point for cor. ... with brass cap marked  
Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in  
ground, old post cor. alongside, for sec. cor.  
T. 20 S., R. 8 W., with brass cap marked

824 | T20S  
S19  
T20S | S30  
R9W | R8W

1940

deposit bro  
glass at base of post, and raise a small mound of stone  
the E.

Cor. is 75 ft. below top of rise.

Land, nearly level and gently rolling desert with a slight  
easterly slope.  
Soil, sandy clay; 2nd rate.  
Undergrowth, shadscale,  
Fair grazing.

N. 0°27' E., along the W. bdy. sec. 19.

Over nearly level land, through short undergrowth.

29.10 Small drainage ditch, course N. 80° E., about 4 chs. to  
reservoir.

29.50 Dim road, bears N. 60° E. and S. 60° W.

30.20 Point from which; shallow reservoir, size about 2 chs. N.  
and S., by 5 chs. E. and W., bears E. of line about 4 chs.  
dist. It is located on a hard white clay flat.

39.75 The 1/2 sec. cor. on E. bdy. of sec. 24, a quartzite stone,  
20 x 12 x 6 ins., lying on the ground, marked 1/2 on one  
side; unwitnessed.

At point for cor. ...

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the  
ground, stone cor. deposited alongside, for 1/2 sec. cor.  
on E. bdy. sec. 24, with brass cap marked

824

1940

raise a  
small mound of stone, W. of post.

40.33 The 1/2 sec. cor. on the E. bdy. of sec. 19, a greatly  
decayed cedar post, lying on the ground, no marks remaining.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the  
ground, old cor. monument and broken glass deposited  
alongside, for 1/2 sec. cor. on E. bdy. sec. 19, with brass  
marked

... of sec. 19, a greatly  
decayed cedar post, lying on the ground, no marks remaining.

DEPENDENT RESURVEY OF WEST BOUNDARY, T. 20 S., R. 8 W.

Chains

.4 S19
-----------

1940

raise a small mound of stone E. of post.

Thence, N. 0°28' E.

38.40 The cor. of secs. 13 and 24, a quartzite stone, 12 x 12 x 8 ins., firmly set, marked with 3 notches on N. and S., and 6 notches on W. edge.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with stone cor. and broken glass deposited at the base of the post, for cor. of secs. 13 and 24, T. 20 S., R. 8 W., with brass cap marked

T20S	T20S
S13	R8W
S24	S19
R9W	

1940

raise a small mound of stone, W. of post.

40.34 The cor. of secs. 18 and 19, a quartzite stone, 18 x 12 x 6 ins., lying on the ground, marked 3 notches on N. and S. edges.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with stone cor. and broken glass deposited at the base, for cor. secs. 18 and 19, T. 20 S., R. 8 W., with brass cap marked

S13	T20S
T20S	S18
R9W	S19
	R8W

1940

raise a small mound of stone E. of post.

Cor. set 15 ft. below last 1/4 sec. cor.

and, nearly level, slight easterly slope.  
Soil, sandy clay and heavy clay; 2nd to 3rd rates.  
Undergrowth, shadscale and a few greasewood.  
Fair grazing.

N. 0°01' W., along the W. bdy. sec. 18.

Over nearly level desert land, through short shadscale and few scattered greasewood.

17.00 Enter heavy greasewood.

38.34 The 1/4 sec. cor. on E. bdy. sec. 13, a quartzite stone,

DEPENDENT RESURVEY OF WEST BOUNDARY, T. 20 S., R. 8 W.

Chains

20 x 16 x 6 ins., lying on the ground, and marked  $\frac{1}{4}$  on face.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, stone cor. and broken glass deposited at base, for  $\frac{1}{4}$  sec. cor. on E. bdy. sec. 13, with brass cap marked

$\frac{1}{4}$   
S13  
1940

small mound of stone, W. of post. raise a

40.44 The  $\frac{1}{4}$  sec. cor. on the W. bdy. of sec. 18, a cedar post, 2 ft. long,  $1\frac{1}{2}$  ins. diam., firmly set, no marks remaining

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with the cedar post and broken glass deposited at the base, for  $\frac{1}{4}$  sec. cor. on W. bdy. sec. 18, with brass cap marked

$\frac{1}{4}$   
S18  
1940

small mound of stone E. of post. raise a

Thence, N. 0°04' W.

37.69 The cor. of secs. 12 and 13, a quartzite stone, 15 x 14 x 5 ins., firmly set, marked with 2 notches on N., 4 notches on S., and 6 notches on W. edge.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, stone cor. deposited alongside, for cor. of secs. 12 and 13, T. 20 S., R. 9 W., with brass cap marked

T20S | T20S  
S12 | R8W  
S13 | S18  
R9W |

1940

No accessories available.

40.34 The cor. of secs. 7 and 18, a greatly decayed cedar post, 2 ft. long, 2 ins. diam., lying on the ground, no marks remaining.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with post cor. and broken glass deposited at base, for cor. secs. 7 and 18, T. 20 S., R. 8 W., with brass cap marked

## DEPENDENT RESURVEY OF WEST BOUNDARY, T. 20 S., R. 8 W.

Chains

S12	T20S
T20S	S7
R9W	S18
	R8W

1940

small mound of stone, E. of post.

raise a

Land, nearly level desert.

Soil, heavy clay; 3rd rate.

Undergrowth, shadscale and greasewood.

Fair grazing.

N. 0°03' E., along the W. bdy. of sec. 7.

Over nearly level land, through medium dense undergrowth.

16.00 Leave nearly all greasewood, continue through shadscale.

37.36 The  $\frac{1}{4}$  sec. cor. on E. bdy. of sec. 12, a quartzite stone, 20 x 9 x 6 ins., lying on the ground, marked SC  $\frac{1}{4}$  on one face.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, stone cor. deposited alongside, for  $\frac{1}{4}$  sec. cor., on E. bdy. sec. 12, with brass cap marked

$\frac{1}{4}$	S12
---------------	-----

1940

No accessories available.

40.35 The  $\frac{1}{4}$  sec. cor. on the W. bdy. of sec. 7, a quartzite stone, 20 x 10 x 4 ins., firmly set, marked  $\frac{1}{4}$  on W. face, unwitnessed.

At the cor. point.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, stone cor. and glass deposited at base, for  $\frac{1}{4}$  sec. cor. on W. bdy. sec. 7, with brass cap marked

$\frac{1}{4}$	S7
---------------	----

1940

small mound of stone, E. of post.

raise a

Thence, N. 0°15' E.

37.01 The cor. of secs. 1 and 12, a quartzite stone, 18 x 10 x 5 ins., firmly set, marked with 1 notch on N., 5 notches on S., and 6 notches on W. edge.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, stone cor. deposited at base, for cor. of secs. 1 and 12, T. 20 S., R. 9 W., with brass cap marked

## DEPENDENT RESURVEY OF WEST BOUNDARY, T. 20 S., R. 8 W.

Chains

T20S	T20S
S1	
-----	
S12	R8W
R9W	S7

1940

No accessories available.

40.34 The cor. of secs. 6 and 7, a cedar post,  $3\frac{1}{2}$  ft. long, 4 ins. diam., lying on the ground and having dim scribe marks.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, post cor. and glass deposited alongside, for cor. of secs. 6 and 7, T. 20 S., R. 8 W., with brass cap marked

S1	T20S
	S6
T20S	-----
	S7
R9W	R8W

1940

Small circle of rock placed around cor. post.

Land, nearly level.

Soil, heavy clay; 2nd rate.

Undergrowth, shadscale and greasewood.

Fair grazing.

N.  $0^{\circ}50'$  E., along the W. bdy. sec. 6.

Over level land, through short shadscale undergrowth.

20.70 Dim unused road, bears N.  $56^{\circ}30'$  E. and S.  $56^{\circ}30'$  W.

36.59 The  $\frac{1}{4}$  sec. cor. on the E. bdy. of sec. 1, a quartzite stone  $16 \times 8 \times 8$  ins., firmly set, marked  $\frac{1}{4}$  on W. face.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, stone cor. and glass deposited alongside, for  $\frac{1}{4}$  cor. on E. bdy. sec. 1, with brass cap marked

$\frac{1}{4}$
S1

1940

No accessories available.


40.38 The  $\frac{1}{4}$  sec. cor. on the W. bdy. of sec. 6, a cedar post, 3 ft. long, 2 ins. diam., lying on the ground and marked  $\frac{1}{4}$  on one face.

At the cor. point.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, post cor. alongside, for  $\frac{1}{4}$  sec. cor. on W. bdy. sec. 6, with brass cap marked

DEPENDENT RESURVEY OF WEST BOUNDARY T. 20 S., R. 8 W.

Chains



Small circle of rock placed around post.

Continue on same course, beginning new measurement.

40.23 The cor. of Ts. 19 and 20 S., Rs. 8 and 9 W., an iron post, 3 ins. diam., properly set, marked and witnessed as described by me in record of survey of T. 19 S., R. 8 W., this Group.

Land, level.  
Soil, heavy clay; 3rd rate.  
Undergrowth, shadscale.  
Fair grazing.

DEPENDENT RESURVEY OF SUBDIVISION, T. 20 S., R. 8 W.

Reestablishment of surveys executed by  
Julien Bausman, U.S. Deputy Surveyor,  
in 1871.


Beginning at the standard cor. of secs. 35 and 36, on the 4th standard parallel south, or S. boundary of township; an iron post, 2 ins. diam., properly set, marked and witnessed as described in official record of survey T. 21 S., R. 8 W., Group No. 255, Utah.

Thence,  
N. 0°04' E., bet. secs. 35 and 36.

Over nearly level desert or valley land, through short shadscale undergrowth.

40.54 The original 4 sec. cor., a cedar post, 3 ft. long, 3 ins. diam., firmly set, and having dim scribe marks on two flattened surfaces; unwitnessed.

At point for cor.  
Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, post cor. deposited alongside, for ¼ sec. cor., with brass cap marked



raise a mound of stone, 2 ft. base, 1½ ft. high, W. of post.

Continue on same course, beginning new measurement.

29.20 American Telephone and Telegraph Company's transcontinental line, 10 wire, bears N. 34°17' E. and S. 34°17' W.

29.50 Dim service road parallel to telephone line.

40.50 The original sec. cor.; a cedar post, 2 ft. long, 4 ins. diam., squared at top, and having dim scribe marks on 4 side; unwitnessed:

At point for cor.

## DEPENDENT RESURVEY OF SUBDIVISION, T. 20 S., R. 8 W.

Chains

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, post cor. deposited alongside, for cor. of secs. 25, 26, 35, and 36, with brass cap marked

T20S	R8W
S26	S25

S35	S36
-----	-----

1940

mound of stone, 2 ft. base, 1½ ft. high, W. of cor. raise a

Land, nearly level.

Soil, sandy clay; 3rd rate.

Undergrowth, shadscale and some grass.

Fair grazing.

From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the township.

N. 89°30' W., bet. secs. 25 and 36.

Over nearly level desert land, through short undergrowth.

40.63 The original ¼ sec. cor., a cedar post, 3 ft. long, 3 ins. diam., broken off at surface with stump firmly set in the ground, dim scribe marks; unwitnessed.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, post cor. deposited alongside, for ¼ sec. cor., with brass cap marked

S25

S36

1940

mound of stone, 2 ft. base, 1½ ft. high, N. of post. raise a

Thence, N. 89°29' W.

32.90 American Telephone and Telegraph Company's transcontinental line, 10 wire, bears N. 34°17' E. and S. 34°17' W.

35.40 Dim service road along phone line.

40.63 The cor. of secs. 25, 26, 35, and 36.

Land, nearly level.

Soil, sandy clay; 2nd rate.

Undergrowth, short shadscale, and scattered grass.

Fair grazing.

N. 0°17' E., bet. secs. 25 and 26.

Over nearly level desert land, through short shadscale.


40.54 The original ¼ sec. cor., a cedar post, 3 ft. long, 3 ins. diam., firmly set and having dim scribe marks.

At point for cor.

DEPENDENT RESURVEY OF SUBDIVISION, T. 20 S., R. 8 W.

Chains

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, post cor. deposited alongside, for  $\frac{1}{4}$  sec. cor., with brass cap marked



raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Continue on same course, beginning new measurement.


10.50 Enter greasewood undergrowth,

23.50 Leave greasewood, continue through ~~shadscale~~ undergrowth.

40.54 The original sec. cor., a cedar post, 4 ft. long, 4 ins. diam., firmly set, and having dim scribe marks; unwitnessed.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, post cor. deposited alongside, for cor. of secs. 23, 24, 25, and 26, with brass cap marked



raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of post.

Land, nearly level.

Soil, sandy clay; heavy clay; 2nd and 3rd rates.

Undergrowth, shadscale and greasewood.

Fair grazing.

From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the township,

N.  $89^{\circ}10'$  W., bet. secs. 24 and 25.

Over nearly level desert land, through short undergrowth.


19.50 American Telephone and Telegraph line, 10 wire, bears N.  $34^{\circ}17'$  E. and S.  $34^{\circ}17'$  W.

19.70 Dim service road, parallel to same.

40.84 The original  $\frac{1}{4}$  sec. cor., which is stump of cedar post, firmly set in the ground (top of post missing)

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old stump deposited alongside, for  $\frac{1}{4}$  sec. cor., with brass cap marked



DEPENDENT RESERVE OF SECTION 23, T20S, R9W, S14

Chains Raise a small mound of stone, N. of cor. in sec. 23.  
Continue on same course, beginning new measurement.

10.73 The cor. of secs. 23, 24, 25, and 26.  
Land, nearly level.  
Soil, heavy clay; 3rd rate.  
Undergrowth, shadscale.  
Fair grazing.

N. 0°38' E. bet. secs. 23 and 24.  
Over level desert land, through short undergrowth.

14.92 Proportionate distance; no evidence of old sec. cor.  
Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, broken glass deposited at the base, for restored sec. cor., with brass cap marked

S23 | S24  
1940

of stone placed around post. small circle

12.10 Dim road, bears N. 80° E. and S. 80° W.

21.85 The original sec. cor., a cedar post, 3½ ft. long, 4 ins. diam., loosely set, and having dim scribe marks.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, post cor. deposited alongside, for cor. secs. 13, 14, 23, and 24, with brass cap marked.

T20S | R9W  
S14 | S13  
S23 | S24  
1940

small mound of stone, N. of post. raise a

Land, level desert.  
Soil, heavy clay; 3rd rate.  
Undergrowth, shadscale.  
Fair grazing.

From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the township.

N. 50°22' W., bet. secs. 13 and 24.

Over level desert land, through greasewood undergrowth.


22.00 Leave greasewood, continue through shadscale.

10.70 Proportionate distance; no evidence of the old sec. cor.

DEPENDENT RESURVEY OF SUBDIVISION, T. 20 S., R. 8 W.

Chains

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked



1940

circle of rock placed around post. small

Note; a dim road bearing E. and W., bears S. of cor., about 20 lks. dist.

41.70 Dim road, bears N. 80° W., and S. 80° E. to junction with another road bearing E. and W.

81.40 The cor. of secs. 13, 14, 23, and 24.

Land; level.  
Soil, clay; 3rd rate.  
Undergrowth, shadscale and greasewood.  
Fair grazing.

N. 0°50' E., bet. secs. 13 and 14.


Over level desert land, through short undergrowth.

2.00 Dim road, bears N. 85° W. and S. 85° E.

32.00 Leave white clay and enter sandy clay soil.

40.38 The original  $\frac{1}{4}$  sec. cor., a cedar post, 3 ft. long, 4 ins. diam., firmly set, and plainly marked  $\frac{1}{4}$  on W. face.  
At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old post cor. deposited alongside, for  $\frac{1}{4}$  sec. cor., with brass cap marked



1940


small mound of stone and earth, W. of post. raise a

Thence, N. 0°35' E.

40.63 The original sec. cor., a cedar post, 1½ ft. long, 3 ins. diam., firmly set, and properly marked; unwitnessed.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, post cor. deposited alongside, for cor. secs. 11, 12, 13, and 14, with brass cap marked



1940

DEPENDENT RESURVEY OF SUBDIVISION, T. 20 S. R. 8 W.

Chains

aniedO

Raise a small mound of stone, W. of post.  
 Land, level desert.  
 Soil, clay; sandy clay; 2nd and 3rd rates.  
 Undergrowth, shadscale.  
 Fair grazing land.

From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the township.

N. 98°14' W., bet. secs. 12 and 13.

Over level desert land, through greasewood undergrowth.

15.80 Dim road, bears N. 10° W. and S. 10° E.

34.00 Leave greasewood, continue through shadscale undergrowth.

40.55 The original  $\frac{1}{4}$  sec. cor., a cedar post, 3 ft. long, 3 ins diam., lying on the ground, and having dim scribe marks.

At point for cor.

Set an iron post, 3 ft. long, 1 in diam., 27 ins. in the ground, old post cor. deposited alongside, for  $\frac{1}{4}$  sec. cor. with brass cap marked

$\frac{1}{4}$   $\frac{S12}{S13}$

1940

circle of rock placed around post. small

Continue on same course, beginning new measurement.

40:53 The cor. of secs. 11, 12, 13, and 14.

Land, level desert.  
 Soil, sandy clay; 3rd rate.  
 Undergrowth, shadscale and greasewood.  
 fair grazing.

N. 0°33' E., bet. secs. 11 and 12.

Over level desert land, through short undergrowth.

40.38 The original  $\frac{1}{4}$  sec. cor.; a cedar post, 2 $\frac{1}{2}$  ft. long, 4 ins diam., firmly set, and having dim scribe marks.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old post cor. deposited alongside, for  $\frac{1}{4}$  sec. cor. with brass cap marked

$\frac{1}{4}$   
 S11 | S12

1940

small mound of stone, W. of post.

raise a

## DEPENDENT RESURVEY OF SUBDIVISION, T. 20 S., R. 8 W.

## Chains

Thence, N.  $0^{\circ}30'$  E.

36.60 Unimproved road, bears N.  $58^{\circ}45'$  W., and S.  $58^{\circ}45'$  E.

40.03 The original sec. cor.; the decayed stump of cedar post found buried in the ground; the top of post is missing.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, stump deposited alongside, for cor. secs. 1, 2, 11, and 12, with brass cap marked

T20S	R8W
S2	S1
S11	S12

1940

small mound of stone, W. of post.

raise a

Land, level desert.

Soil, fine clay and sandy clay; 2nd rate.

Undergrowth, shadscale.

Fair grazing.

From the cor. of secs. 1, 6, 7, and 12, on E. bdy. of the township.

N.  $88^{\circ}22'$  W., bet. secs. 1 and 12.

Over alkali flat covered with scattered salt brush.

27.50 Leave flat, enter nearly level desert land at top of a 5 ft. rim facing E., bears N.  $20^{\circ}$  W. and S.  $20^{\circ}$  E.; thence through greasewood undergrowth.

29.00 Old abandoned canal, drains N.  $10^{\circ}$  W.

40.49 Proportionate distance; no evidence of the old sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for restored sec. cor., with brass cap marked

S1

S12

1940

raise a

small mound of stone, N. of post.

52.20 A main canal (now abandoned) 30 lks. wide, 5 ft. deep, drains northerly.

60.00 Leave greasewood, continue through shadscale undergrowth.

80.97 The cor. of secs. 1, 2, 11, and 12.

Land, level alkali flat on E. end, and nearly level desert on W. portion of mile.

Soil, clay loam; alkali clay; 2nd and 3rd rates.

Undergrowth, shadscale, greasewood, and salt brush.

Fair grazing.

DEPENDENT RESURVEY OF SUBDIVISION, T. 20 S., R. 8 W.

Chains

From the cor. of secs. 1, 2, 35, and 36, on the N. bdy. the township, an iron post, 2 ins. diam., properly set, marked and witnessed as described by me in the record of resurvey, T. 19 S., R. 8 W., this Group

Thence:


S. 0°40' W., bet. secs. 1 and 2.

Over level desert land, through short undergrowth.

26.90 Graded road, between Fillmore via Clear Lake, and Clear Lake Station on Union Pacific Railroad, bears N. 61°55' and S. 61°55' E.

39.13 Proportionate distance; no evidence of old  $\frac{1}{4}$  sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked



raise a small mound of stone W. of post.

40.00 A main canal (now abandoned) 30 lks. wide, 4 ft. deep, drains N. 83°10' W.

78.50 The cor. of secs. 1, 2, 11, and 12.

Land, level desert.

Soil, clay loam; 2nd rate.

Undergrowth, shadscale and greasewood.

Fair grazing.

From the standard cor. of secs. 34 and 35, on the 4th standard parallel south, and S. bdy. of township; an iron post, 2 ins. diam., properly set, marked and witnessed as described in official record of survey T. 21 S., R. 8 W., of Group No. 255, Utah.

Thence:


N. 0°51' E., bet. secs. 34 and 35.

Over nearly level land, through short undergrowth.

40.23 The original  $\frac{1}{4}$  sec. cor.; a cedar post, 3 ft. long, 4 ins diam., lying on the ground, and having dim scribe marks.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old post cor. deposited alongside, for  $\frac{1}{4}$  sec. cor with brass cap marked



circle of rock placed around post.

small

DEPENDENT RESURVEY OF SUBDIVISION, T. 20 S., R. 8 W.

Chains

Thence, N. 1°06' E.

39.91

The original sec. cor., a cedar post, 3 1/2 ft. long, 4 ins. diam.; lying on the ground, with dim scribe marks.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, old post cor. deposited alongside, for cor. of secs. 26, 27, 34, and 35, with brass cap marked

T20S	R8W
S27	S26
S34	S35

1940

small mound of stone, W. of post. raise a

Land, nearly level desert.  
Soil, sandy clay; 3rd rate.  
Undergrowth, shadscale and greasewood.  
Fair grazing.

From the cor. of secs. 25, 26, 35, and 36.

S. 89°50' W., bet. secs. 26 and 35.

Over nearly level desert land, through short scattered undergrowth.

40.07

The original 1/4 sec. cor., a cedar post, 3 ft. long, 3 ins. diam., loosely set, and having dim scribe marks.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old post cor. deposited alongside, for 1/4 sec. cor., with brass cap marked

S26
S35

1940

small mound of stone, N. of cor. raise a

Thence, S. 88°57' W.

39.17

The cor. of secs. 26, 27, 34, and 35.

Land, nearly level desert.  
Soil, sand clay; heavy clay; 2nd to 3rd rates.  
Undergrowth, shadscale.  
Fair grazing.

N. 0°20' W., bet. secs. 26 and 27.

Over nearly level desert land, through short undergrowth.

9.50

Dim trace of road, bears nearly E. and NW.

## DEPENDENT RESURVEY OF SUBDIVISION, T. 20 S., R. 8 W.

Chains

41.02 The original  $\frac{1}{4}$  sec. cor., a cedar post, 3 ft. long, 4 in. squared, found lying on a small earth mound, and having dim scribe marks.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old post cor. deposited alongside, for  $\frac{1}{4}$  sec. cor. with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ \text{S27} \mid \text{S26} \\ 1940 \end{array}$$

mound of stone placed around post.

small

Thence, N.  $0^{\circ}07'$  W.

33.50 Dim trace of road, bears N.  $70^{\circ}$  E. and S.  $70^{\circ}$  W.

40.56 The original sec. cor., a cedar post,  $3\frac{1}{2}$  ft. long, 4 ins. diam., lying on small mound of earth, and having dim scribe marks.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, post cor. deposited alongside, for cor. secs. 22, 23, 26, and 27, with brass cap marked

$$\begin{array}{c} \text{T20S} \mid \text{R8W} \\ \text{S22} \mid \text{S23} \\ \hline \text{S27} \mid \text{S26} \\ 1940 \end{array}$$

small mound of stone, W. of post.

raise a

Land, nearly level desert.

Soil, clay; 2nd rate.

Undergrowth, shadscale.

Fair grazing.

From the cor. of secs. 23, 24, 25, and 26.

S.  $89^{\circ}47'$  W., bet. secs. 23 and 26.

Over level land, through scattered short undergrowth.

39.97 Proportionate distance; no evidence of old  $\frac{1}{4}$  sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked

$$\begin{array}{c} \text{S23} \\ \frac{1}{4} \text{---} \\ \text{S26} \end{array}$$

1940

circle of stone placed around post.

small

DEPENDENT RESURVEY OF SUBDIVISION, T. 20 S., R. 9 W.

Chains

58.30 Dim trace of old road, bears N. 80° E. and S. 80° W.

79.94 The cor. of secs. 22, 23, 26, and 27.


Land, level desert.  
Soil, clay; 2nd and 3rd rates.  
Undergrowth, shadscale.  
Fair grazing.

N. 0°15' E., bet. secs. 22 and 23.

Over level desert land, through short undergrowth.

40.45 Proportionate distance; no evidence of old 1/4 sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored 1/4 sec. cor., with brass cap marked




Small mound of stone around post.

60.00 Old road, bears N. 80° E. and S. 80° W.

80.89 The original sec. cor., a cedar post, 3 ft. long, 4 ins. diam., lying on the ground, and having dim scribe marks.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, old cor. deposited alongside, for cor. of secs. 14, 15, 22, and 23, with brass cap marked



raise a small mound of stone, W. of cor.

Land, level desert.  
Soil, heavy clay; 3rd rate.  
Undergrowth, shadscale.  
Fair grazing.

From the cor. of secs. 13, 14; 23, and 24.

S. 89°05' W., bet. secs. 14 and 23.

Over level desert land, through short undergrowth.

40.25 The original 1/4 sec. cor., a cedar post, 3 ft. long, 4 ins. diam., lying on the ground, and having dim scribe marks.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old cor. deposited alongside, for 1/4 sec. cor., with brass cap marked

DEPENDENT RESURVEY OF SUBDIVISION, T. 20S. R. 8W.

Chains

S14

S23

1940

Small circle of rock around post.  
Continue on same course, beginning new measurement.

40.25 The cor. of secs. 14, 15, 22, and 23.

Land, level.  
Soil, heavy clay; 2nd rate.  
Undergrowth, shadscale.  
Fair grazing.

N. 0°34' E., bet. secs. 14 and 15.

Over level desert land, through scattered short undergrowth

12.30 Dim road, bears nearly E. and W.

40.24 Proportionate distance; no evidence of old 1/4 sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored 1/4 sec. cor., with brass cap marked

S15 | S14

1940

Small mound of stone, W. of post. raise a

80.47 The original sec. cor., a cedar post, 3 ft. long, 4 ins. diam., firmly set, and having dim scribe marks.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, old cor. deposited alongside, for cor. secs. 10, 11, 14, and 15, with brass cap marked

T20S R8W

S10 | S11

S15 | S14

1940

mound of stone, W. of post. raise a small

Land, level.  
Soil, clay; 3rd rate.  
Undergrowth, shadscale, scattered greasewood and some salt brush.  
Fair grazing.

From the cor. of secs. 11, 12, 13, and 14.

S. 89°44' W., bet. secs. 11 and 14.

DEPENDENT RESURVEY OF SUBDIVISION, T. 20 S., R. 8 W.

Chains

Over level desert land, through scattered undergrowth.

40.37 Proportionate distance; no evidence of the  $\frac{1}{4}$  sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked

S11  
-----  
S14

1940

small mound of stone, N. of post.

raise a

65.00 Leave nearly all shadscale, continue through greasewood.

80.74 The cor. of secs. 10, 11, 14, and 15.

Land, level desert.  
Soil, clay; 2nd rate.  
Undergrowth, shadscale and greasewood.  
Fair grazing.

N. 0°28' E., bet. secs. 10 and 11.

Over nearly level desert, through medium dense greasewood undergrowth.

22.00 Leave greasewood, continue through shadscale.

40.39 Proportionate distance; old cor. found lying on the ground at considerable distance, no evidence of its original position.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked

$\frac{1}{4}$   
S10 | S11  
-----  
1940

small mound of stone, W. of post; also place old cor. at base of post.

raise a

79.70 Dim road, bears N. 30° W. and S. 30° E.

80.78 Proportionate distance; no evidence of the original sec. cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for restored cor. of secs. 2, 3, 10, and 11, with brass cap marked.

T20S | R8W  
S3 | S2  
-----  
S10 | S11  
-----  
1940

small mound of stone, W. of post.

raise a

Land, level desert.

## DEPENDENT RESURVEY OF SUBDIVISION, T. 20 S., R. 8 W.

Chains

Soil, clay; 2nd rate.  
Undergrowth, shadscale and greasewood.  
Fair grazing.

From the cor. of secs. 1, 2, 11, and 12.

S. 88°52' W., bet. secs. 2 and 11.

Over level desert land, through short undergrowth.

5.70 Unimproved road, bears N. 58°45' W. and S. 58°45' E.

40.39 The original  $\frac{1}{4}$  sec. cor.; a cedar post, 2½ ft. long, 3 ins. diam., firmly set, and having dim scribe marks.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old cor. deposited alongside, for  $\frac{1}{4}$  sec. cor., with brass cap marked

S2

S11

1940

small mound of stone, N. of post.

raise a

Thence, S. 89°05' W.

40.41 The cor. of secs: 2, 3, 10, and 11.

Land, level desert.  
Soil, clay; 2nd rate.  
Undergrowth, shadscale.  
Fair grazing.

From the cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the township, an iron post, 2 ins. diam., properly set, marked and witnessed, as described by me in record of resurvey of T. 19 S., R. 8 W., of this Group.

Thence,

S. 0°52' W., bet. secs. 2 and 3.

Over nearly level desert land, through short undergrowth.

28.30 Dim road, bears N. 10° W., and S. 10° E. to canal.

30.80 A main canal (now abandoned) 30 lks. wide, 4 ft. deep, drains N: 83°12' W.; an irrigation ditch bearing N. takes off from canal about 1 ch. E. of line.

33.10 Unimproved road, bears about S. 60° E., and westerly parallel to canal.

39.87 The original  $\frac{1}{4}$  sec. cor., a cedar post, 3 ft. long, 3 ins. diam., firmly set, with dim scribe marks.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old cor. deposited alongside, for  $\frac{1}{4}$  sec. cor., with brass cap marked

## DEPENDENT RESURVEY OF SUBDIVISION, T. 20 S., R. 8 W.

Chains

4.  
S3 | S2

1940

small mound of stone, W. of post. .

raise a

Thence, S.  $0^{\circ}44'$  W.

40.39 The cor. of secs. 2, 3, 10, and 11.

Land, nearly level.

Soil, clay; 2nd rate.

Undergrowth, shadscale and greasewood.

Fair grazing.

---

from the standard cor. of secs. 33 and 34, on the 4th standard parallel south, on S. bdy. of the township; an iron post, 2 ins. diam., properly set, marked and witnessed as described in official record of survey T. 21 S., R. 8 W. Group No. 255, Utah.

N.  $0^{\circ}25'$  E., bet. secs. 33 and 34.

Over level desert land, through medium dense undergrowth.

16.00 The E. end of a dyke forming the W. end of a reservoir recently constructed, bears W. of line about 10 chs. dist.

40.28 The original sec. cor.; a cedar post,  $2\frac{1}{2}$  ft. long, 4 ins. diam., lying on the ground and having dim scribe marks.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old cor. deposited alongside, for sec. cor., with brass cap marked

S33 | S34

1940

Place a small circle of rock around post.

Continue on same course, beginning new measurement.

40.29 The original sec. cor., a cedar post,  $3\frac{1}{2}$  ft. long, 4 ins. diam., lying on a trace of an old earth mound, and having dim scribe marks.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, old cor. deposited alongside, for cor. secs. 27, 28, 33, and 34, with brass cap marked

T20S | R8W

S28 | S27

S33 | S34

1940

small mound of stone, W. of post.

raise a

DEPENDENT RESURVEY OF SUBDIVISION, T. 20 S., R. 8 W.

Chains

Land, nearly level.  
Soil, sandy clay; 2nd rate.  
Undergrowth, greasewood and shadscale.  
Fair grazing.

From the cor. of secs. 26, 27, 34, and 35.

N. 89°12' W., bet. secs. 27 and 34.

Over nearly level land, through short undergrowth.

40.69 Proportionate distance; old cor. was found lying on the ground at considerable distance with no evidence of its original position.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old cor. post set alongside, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked

S27

S34

1940

Small circle of rock placed around post.

78.00 Small clay rim, 5 ft. high, facing W., bears N. 20° W. and S.; thence over lower ground.

81.38 The cor. of secs. 27, 28, 33, and 34.

Land, nearly level desert.  
Soil, clay; 2nd rate.  
Undergrowth, shadscale and greasewood.  
Fair grazing.

N. 0°17' E., bet. secs. 27 and 28.

Over nearly level desert land, through medium dense short undergrowth.

6.50 Low clay rim, 4 ft. high, facing SW., bears NW. and SE.; thence over higher ground nearly level.

40.21 Proportionate distance; no evidence of old  $\frac{1}{4}$  sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked

S28 | S27

1940

Small mound of stone, W. of post.

raise a

52.40 Dim road, bears NW. and SE.

55.10 Dim road, bears N. 80° E. and nearly W.

60.00 Small clay rim 3 ft. high, facing S., bears NW. and SE.; thence over higher ground.

DEPENDENT RESURVEY OF SUBDIVISION, T. 20 S., R. 9 W.

Chains

80.43

The original sec. cor.; a cedar post, 3 1/2 ft. long, 4 ins. diam., firmly set, and having plain scribe marks.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, old cor. deposited alongside, for cor. of secs. 21, 22, 27, and 28, with brass cap marked

T20S	R9W
S21	S22
S23	S27

1940

raise a small mound of stone, W. of post.

Land, nearly level; surface broken by small rims and eroded surface.

Soil, sandy clay; heavy white clay; 2nd and 3rd rates. Undergrowth, medium dense greasewood and shadscale. Fair grazing land.

From the cor. of secs. 22, 23, 26, and 27.

West, bet. secs. 22 and 27.

Over nearly level desert land, through scattered undergrowth.

40.30

The original sec. cor.; a cedar post, 2 1/2 ft. long, 3 ins. diam., lying on the ground, has dim scribe marks.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old cor. deposited alongside, for sec. cor., with brass cap marked

S22
S27

1940

A small circle of rock around the post.

Continue on same course, beginning new measurement.

1.70

Enter heavier undergrowth.

40.30

The cor. of secs. 21, 22, 27, and 28.

Land, nearly level desert.

Soil, sandy clay; heavy white clay; 2nd and 3rd rates. Undergrowth, shadscale and greasewood. Fair grazing.

N. 0°28' E., bet. secs. 21 and 22.

Over nearly level desert through scattered short undergrowth.

40.25

Proportionate distance; no evidence of the old 1/4 sec. cor.

DEPENDENT RESURVEY OF SUBDIVISION, T. 20 S., R. 8 W.

Chains

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored sec. cor., with brass cap marked

S21	S22
1940	

small mound of stone, W. of post.

raise a

4.00 1st road, bears N. 80° E. and S. 80° W.

50.00 Leave greasewood, continue through shadscale.

60.50 The original sec. cor.; a cedar post, 4 ft. long, 4 ins. squared, loosely set, and having dim scribe marks.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, old cor. deposited alongside, for cor. secs. 15, 16, 21, and 22, with brass cap marked

T20S	R8W
S16	S15
S21	S22
1940	

small mound of stone, W. of post.

raise a

Land, nearly level desert.

Soil, sandy clay; 2nd rate.

Undergrowth, greasewood and shadscale.

Cair grazing.

From the cor. of secs. 14, 15, 22, and 23.

S. 89°15' W., bet. secs. 15 and 22.

Over nearly level desert land, through scattered salt brush.

25.00 Leave salt brush, enter greasewood undergrowth.

30.15 The original sec. cor., a cedar post, 4 ft. long, 4 ins. diam., lying on ground and having dim scribe marks.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old cor. deposited alongside, for sec. cor., with brass cap marked

S15
S22

1940

A small circle of rock placed around post.

Continue on same course, beginning new measurement.

30.00 Leave Greasewood, enter shadscale undergrowth.

## DEPENDENT RESURVEY OF SUBDIVISION, T. 20 S., R. 8 W.

Chains

40.13 The cor. of secs. 15, 16, 21, and 22.

Land, nearly level desert.  
Soil, heavy clay; sandy clay; 3rd and 2nd rates.  
Undergrowth, shadscale and greasewood.  
Fair grazing land.

N. 0°09' W., bet. secs. 15 and 16.

Over nearly level desert land, through short undergrowth.

19.50 Dim road, bears nearly E. and W.

40.33 The original  $\frac{1}{4}$  sec. cor.; a cedar post, 3 ft. long, 3 ins. diam., firmly set, marked with dim scribe marks.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old cor. post deposited alongside, for  $\frac{1}{4}$  sec. cor. with brass cap marked

	$\frac{1}{4}$	
S16	S15	
1940		

raise a

mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of post.

Thence, N. 0°43' E.

40.33 The original sec. cor., a cedar post, 3 ft. long, 4 ins. squared, firmly set, and having dim scribe marks.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, old cor. post deposited alongside, for cor. of secs. 9, 10, 15, and 16, with brass cap marked

	T20S	R8W
	S9	S10
	S16	S15
1940		

No accessories available.

Land, nearly level desert.  
Soil, clay; 2nd rate.  
Undergrowth, shadscale and greasewood.  
Fair grazing.

From the cor. of secs. 10, 11, 14, and 15.

S. 89°53' W., bet. secs. 10 and 15.

Over nearly level land, through short undergrowth.

40.26 The original  $\frac{1}{4}$  sec. cor., a cedar post, 3 ft. long, 4 ins. diam., lying on the ground and having dim scribe marks.

DEPENDENT RESURVEY OF SUBDIVISION, T. 20 S., R. 8 W.

Chains

At point for cor. . . . .  
 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old post cor. deposited alongside, for  $\frac{1}{4}$  sec. cor. with brass cap marked

S10  
 $\frac{1}{4}$  ———  
 S15  
 1940

No accessories available.  
 Continue on same course, beginning new measurement.

40.37 The cor. of secs. 9, 10, 15, and 16.

Land, nearly level desert.  
 Soil, heavy clay; 2nd rate.  
 Undergrowth, shadscale and greasewood.  
 Fair grazing.

N. 0°24' E., bet. secs. 9 and 10.

Over nearly level desert, through short undergrowth.

40.32 Proportionate distance; no evidence of original  $\frac{1}{4}$  sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked

$\frac{1}{4}$   
 S9 | S10  
 1940

small mound of stone, W. of post. raise a

56.00 Leave shadscale, enter greasewood undergrowth.

80.64 Proportionate distance; no evidence of original sec. cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for restored cor. secs. 3, 4, 9, and 10, with brass cap marked

T20S | R8W  
 S4 | S3  
 S9 | S10  
 1940

mound of stone, 2 ft. base, 1½ ft. high, W. of post. raise a

Land, nearly level desert.  
 Soil, clay; 2nd rate.  
 Undergrowth, shadscale and greasewood.  
 Fair grazing

## DEPENDENT RESURVEY OF SUBDIVISION, T. 20 S., R. 8 W.

## Chains

From the cor. of secs. 2, 3, 10, and 11.

S. 89°47' W., bet. secs. 3 and 10.

Over nearly level land, through shadscale undergrowth.

0.70 Dim road, bears N. 30° W. and S. 30° E.

40.35 Proportionate distance; no evidence of the original sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked

$$\begin{array}{r} S3 \\ \frac{1}{4} \hline S10 \end{array}$$

1940

raise a small mound of stone N. of cor.

48.00 Leave shadscale, enter medium dense greasewood undergrowth.

80.70 The cor. of secs. 3, 4, 9, and 10.

Land, nearly level.

Soil, clay; 2nd rate.

Undergrowth, shadscale and greasewood.

Fair grazing.

From the cor. of secs. 3, 4, 33, and 34, on N. bdy. of the township, an iron post, 2 ins. diam., properly set, marked and witnessed as described by me in record of resurvey, T. 19 S., R. 8 W., of this Group.

S. 0°49' W., bet. secs. 3 and 4.

Over nearly level land, through short undergrowth.

13.00 Cross small irrigation ditch (abandoned) drains nearly N.

21.50 A main canal (abandoned) 30 lks. wide, 4 ft. deep, drains N. 83°20' W.

40.50 Proportionate distance; no evidence of the original sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked

$$\begin{array}{r} \frac{1}{4} \\ S4 \quad | \quad S3 \end{array}$$

1940

raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

49.30 The south end of right-of-way fence on W. side of railroad, bears E. of line about 3 chs. dist.

58.00 Graded road parallel to railroad, between Clear Lake Station and Desert to the N., and Black Rock to the S.

DEPENDENT RESURVEY OF SUBDIVISION, T. 20 S., R. 8 W.

Chains  
 59.40 Telegraph line, 13 wire, parallel to railroad.  
 64.30 Union Pacific Railroad, single track, bears N. 17°17' E. and S. 17°17' W.  
 69.20 Telegraph line, 8 wire, parallel to railroad.  
 70.50 Dim old road, parallel to railroad.  
 80.82 The cor. of secs. 3, 4, 9, and 10.  
 Land, nearly level.  
 Soil, clay; 2nd rate.  
 Undergrowth, greasewood and shadscale.  
 Fair grazing.

From the standard cor. of secs. 32 and 33, on 4th standard parallel south, on S. bdy. of township, an iron post, 2 ins. diam., properly set, marked and witnessed as described in official record of survey T. 21 S., R. 8 W., Group No. 255, Utah.

N. 0°28' E., bet. secs. 32 and 33.


Over nearly level desert land, through medium dense greasewood undergrowth.

1.50 Wash, 30 lks. wide, 5 ft. deep, drains N. 70° E.

40.35 The original  $\frac{1}{4}$  sec. cor., a cedar post, 3 ft. long, 4 ins. diam., loosely set and having dim scribe marks.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old cor. deposited alongside, for  $\frac{1}{4}$  sec. cor., with brass cap marked



Small circle of rock placed around post.

Continue on same course, beginning new measurement.


32.00 Leave greasewood, enter shadscale undergrowth.

39.20 Unimproved road, bears N. 20° W. to railroad, and S. 20° to reservoir about 70' chs. dist.

40.35 The original sec. cor., a cedar post, 3 ft. long, 4 ins. diam., loosely set in the ground, and properly marked.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, old cor. deposited alongside, for cor. of secs. 28, 29, 32, and 33, with brass cap marked



## DEPENDENT RESURVEY OF SUBDIVISION, T. 20 S., R. 8 W.

Chains

Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

From cor.: Telephone booth at Neels station bears N. 6°15' W.; switch stand at S. end of Neels side track bears N. 15°35' W.; semaphore No. 6258 on E. side of track bears N. 16°00' W.; road crossing sign on railroad, bears N. 18°27' W.; sign post Neels, bears N. 4°54' W.; center knob on black butte located in sec. 29, T. 19 S., R. 8 W., bears N. 3°45' W.; E. end of dike, bears S. 43°30' E., about 1¼ miles dist.; and W. end of same, bears S. 22°15' E., about 70 chs. dist.

Land, nearly level desert.

Soil, heavy clay and sandy clay; 2nd rate.

Undergrowth, greasewood and shadscale.

Fair grazing.

From the cor. of secs. 27, 28, 33, and 34.

N. 89°41' W., bet. secs. 28 and 33.

Over nearly level desert, through medium dense undergrowth.

21.50 Old river channel, 30 lks. wide, 4 ft. deep, drains N.

35.10 Old river channel, 30 lks. wide, 4 ft. deep, drains N.

40.26 Proportionate distance; old cedar stake found lying on the ground at considerable distance with no evidence of its original position.

Set an iron post, 7 ft. long, 1 in. diam., 27 ins. in the ground, old stake deposited alongside, for restored sec. cor., with brass cap marked

828

833

1640

Small circle of rock placed around post.

51.90 Old Beaver River channel, 40 lks. wide, 4 ft. deep, drains northerly.

67.00 Leave greasewood, enter shadscale undergrowth.

80.52 The cor. of secs. 28, 29, 32, and 33.

Land, nearly level; surface broken.

Soil, heavy clay, and sandy clay; 2nd rate.

Undergrowth, greasewood and shadscale.

Fair grazing land.

N. 0°20' E., bet. secs. 28 and 29.

Over nearly level land, through short undergrowth.

22.60 Low rise, 3 ft. high, extends S. 70° E. about 5.00 chs. to end.

25.00 Enter lower flat or bottom land, bears N. 20° W. and SE.

40.32 Proportionate distance; no evidence of original sec. cor.

DEPENDENT RESURVEY OF SUBDIVISION, T. 20 S., R. 8 W.

Chains

Set an iron post, .3 ft. long, 1 in. diam., 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked

S29 | S28

1940

raise a small mound of stone, W. of post.

48.00 Leave low flat, continue over higher ground, bears NE. and S. 20° W.

53.60 Dim road, bears N. 70° E. and S. 70° W.

68.50 Old unused road parallel to railroad.

69.30 Telegraph line, 11 wire, parallel to railroad.

74.25 Main line track of Union Pacific Railroad, bears N. 17° 16' and S. 17° 16' W.

75.10 Neels side track, parallel to main line track.

79.00 Telegraph line, 13 wire, bears same as railroad.

80.64 Proportionate distance; no evidence of the original sec. cor. Point for the restored sec. cor. falls in graded road therefore:

Set a quartzite stone, 15 x 12 x 6 ins., marked with 4 notches on E., 2 notches on S., and a cross X on top, buried in the ground with top of stone 6 ins. beneath surface of road, for true restored cor. of secs. 20, 21, 28, and 29.

At a point N. 0° 30' E., 1.00 ch. dist.

Set an iron post, .3 ft. long, 2 ins. diam., 27 ins. in the ground, for witness cor. to the restored cor. of secs. 20, 21, 28, and 29, with brass cap marked

T20S | R8W

S20 | S21

S29 | S28

WC

1940

raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

The true restored cor. falls in the graded road (11 lks. in from the W. edge) between Desert and Black Rock, parallel to railroad.

and, nearly level desert.

Soil, clay and sandy clay.

Undergrowth, shadscale and greasewood.

Fair grazing.

From the cor. of secs. 21, 22, 27, and 28.

N. 89° 31' W., bet. secs. 21 and 28.

Over nearly level desert land, through medium dense undergrowth.

4.70 Low clay rim, 3 ft. high, facing W., bears NW. and SE.; thence over lower ground.

## DEPENDENT RESURVEY OF SUBDIVISION T. 20 S., R. 8 W.

Chains

40.23 Proportionate distance; no evidence of original  $\frac{1}{4}$  sec. cor.Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked

S21

S28

1940

raise a small mound of stone, N. of post.

46.00 Old river channel, 20 lks. wide, 3 ft. deep, drains NW.

55.00 Low rim, 3 ft. high, facing SE., bears NE. and SW.; thence over higher ground.

76.60 Dim road, parallel to railroad.

77.00 Telegraph line, 11 wire, parallel to railroad.

78.50 Main line track of Union Pacific Railroad, bears N.  $17^{\circ}16'$  E. and S.  $17^{\circ}16'$  W.

78.75 Neels side track, bears same.

80.00 Telegraph line, 13 wire, bears same.

80.46 True restored cor. of secs. 20, 21, 28, and 29.

Land, nearly level desert.

Soil, clay; 2nd rate.

Undergrowth, shadscale and greasewood.

Fair grazing.

N.  $0^{\circ}30'$  E., bet. secs. 20 and 21.

Over nearly level land, through short undergrowth.

1.00 The witness cor. to the cor. of secs. 20, 21, 28, and 29.

14.40 Dim road, bears NE. and SW.

19.50 Enter greasewood undergrowth, leaving nearly all shadscale.

30.50 Dim road, bears E. and W.

39.40 A drainage channel, 50 lks. wide, 3 ft. deep, drains N.  $89^{\circ}20'$  W.40.32 Proportionate distance; no evidence of the original  $\frac{1}{4}$  sec. cor.Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked

S20 | S21

1940

raise a small mound of stone, W. of post.

DEPENDENT RESURVEY OF SUBDIVISION, T. 20 S., R. 8 W.

Chains	From cor., approximately S. 52°30' E. to N. end of Neale side track; and approximately S. 73°00' E. to small cone railroad bridge over old river channel.						
48.20	Old river channel, 20 lks. wide, 2 ft. deep, drains NW.						
80.64	Proportionate distance; no evidence of original sec. cor. Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, for restored cor. secs. 16, 17, 20, and 21, with brass cap marked						
	<table border="1"> <tr> <td>T20S</td> <td>R8W</td> </tr> <tr> <td>S17</td> <td>S16</td> </tr> <tr> <td>S20</td> <td>S21</td> </tr> </table>	T20S	R8W	S17	S16	S20	S21
T20S	R8W						
S17	S16						
S20	S21						
	1940						
	raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.						
	Land, nearly level desert. Soil, clay and sandy clay; 2nd rate. Undergrowth, greasewood and shadscale. Fair grazing.						
40.18	From the cor. of secs. 15, 16, 21, and 22. N. 89°26' W., bet. secs. 16 and 21. Over nearly level desert land, through short undergrowth. Proportionate distance; no evidence of original ¼ sec. cor. Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored ¼ sec. cor., with brass cap marked						
	<table border="1"> <tr> <td>S16</td> </tr> <tr> <td>¼</td> </tr> <tr> <td>S21</td> </tr> </table>	S16	¼	S21			
S16							
¼							
S21							
	1940						
	raise a small mound of stone, N. of cor.						
52.20	Dim road on E. side and parallel to railroad.						
52.60	Telegraph line, 8 wire, parallel to railroad.						
54.05	Main line of Union Pacific Railroad, bears N. 17°16' E., and S. 17°16' W.						
55.50	Telegraph line, 13 wire, bears same as railroad.						
56.00	Graded road parallel to railroad, between Desert and Black Rock.						
80.36	The cor. of secs. 16, 17, 20, and 21. Land, nearly level. Soil, heavy clay; 2nd rate. Undergrowth, greasewood and shadscale. Fair grazing.						
	N. 0°11' E., bet. secs. 16 and 17.						


DEPENDENT RESURVEY OF SUBDIVISION, T. 20 S., R. 8 W.

Chains

Over nearly level desert land, through short undergrowth.

40.32 Proportionate distance; no evidence of the original  $\frac{1}{4}$  sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked




raise a small mound of stone, W. of post.

From cor., small railroad bridge, bears about S.  $43^{\circ}30'$  E.

48.20 Earth dyke, 3 ft. high, bears N.  $53^{\circ}15'$  W. and S.  $53^{\circ}15'$  E. to end.

80.64 Proportionate distance; no evidence of original sec. cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for restored cor. secs. 8, 9, 16, and 17, with brass cap marked



raise a small mound of stone, W. of post.

Land, nearly level.  
Soil, heavy clay; 2nd rate.  
Undergrowth, greasewood and shadscale.  
Fair grazing.

From the cor. of secs. 9, 10, 15, and 16.

N.  $89^{\circ}27'$  W., bet. secs. 9 and 16.

Over nearly level desert land, through greasewood undergrowth.

27.50 Dim road on E. side and parallel to railroad.

27.90 Telegraph line, 8 wire, bears with railroad.

29.40 Union Pacific Railroad, single track, bears N.  $17^{\circ}17'$  E. and S.  $17^{\circ}17'$  W.

30.85 Telegraph line, 13 wire, bears same.

31.25 Graded road, parallel to railroad.

40.25 Proportionate distance; no evidence of original  $\frac{1}{4}$  sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked

DEPENDENT RESURVEY OF SUBDIVISION, T. 20S. R. 8W.

Chains

Level fifteen rods  
S9  
S16  
of West  
St. 01P

1940

raise a small mound of stone, N. of post.

20.49 The cor. of secs. 8, 9, 16, and 17.


Land, nearly level desert.  
Soil, heavy clay; 2nd rate.  
Undergrowth, medium dense greasewood.  
Fair grazing.

N. 0°24' E., bet. secs. 8 and 9.

Over nearly level land, through medium dense undergrowth

40.32 Proportionate distance; no evidence of original 1/4 sec. c

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored 1/4 sec. cor., with brass cap marked




raise a small mound of stone, W. of post.

42.90 An old abandoned canal, 40 lks. wide, 4 ft. deep, drain N. 70° W.

50.00 Old drain, 30 lks. wide, 3 ft. deep, course S. 20° W.

80.64 Proportionate distance; no evidence of original sec, cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for restored cor. secs. 4, 5, 8, and 9, with brass cap marked



raise a small mound of stone, W. of post.

Land, nearly level desert.  
Soil, clay loam; 2nd rate.  
Undergrowth, medium dense greasewood.  
Fair grazing.

From the cor. of secs. 3, 4, 9, and 10.

N. 59°30' W., bet. secs. 4 and 9.

Over nearly level land, through medium dense undergrowth.

DEPENDENT RESURVEY OF SUBDIVISION, T. 20 S., R. 8 W.

Chains	
3.10	Dim road on E. side and parallel to railroad.
3.40	Telegraph line, 8 wire, bears with railroad.
4.90	Union Pacific Railroad, single track, bears N. 17°17' E. and S. 17°17' W.
6.30	Telegraph line, 13 wire, parallel to railroad.
6.80	Graded road, between Deseret and Black Rock, parallel to railroad.
38.40	Old canal, 20 lks. wide, 1 ft. deep, drains S. 15° W.
40.20	The original $\frac{1}{4}$ sec. cor., a cedar stake, 2 $\frac{1}{2}$ ft. long, 3 ins. diam., firmly set, and having dim scribe marks.
	At point for cor.
	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old cor. deposited alongside, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\begin{array}{r} S4 \\ \frac{1}{4} \text{ ---} \\ S9 \end{array}$
	1940
	raise a small mound of stone, N. of post.
	Thence, N. 89°23' W.
34.10	Old canal, 30 lks. wide, 3 ft. deep, drains S. 15° W.
40.30	The cor. of secs. 4, 5, 8, and 9.
	Land, nearly level. Soil, clay; 2nd rate. Undergrowth, greasewood and shadscale. Fair grazing.
<hr/>	
	From the cor. of secs. 4, 5, 32, and 33, on N. bdy. of the township, an iron post, 2 ins. diam., properly set, marked and witnessed as described by me in resurvey of T. 19 S., R. 8 W., of this Group.
	S. 0°47' W., bet. secs. 4 and 5.
	Over nearly level land, through medium dense undergrowth.
0.05	Wire fence, bears E., and southerly along line.
13.40	Old ditch, drains NW.
19.90	The SW. cor. of fences bearing northerly and S. 89°20' E., bears E. of line, about 50 lks. dist.
20.10	Dim road, bears E. and W.
27.80	Old canal, drains N. 25° E. from nearly south; thence along same.
40.00	Same canal, turns E.

DEPENDENT RESURVEY OF SUBDIVISION, T. 20 S., R. 8 W.

Chains

40.14 Proportionate distance; no evidence of original  $\frac{1}{4}$  sec. cor.  
 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked

$\frac{1}{4}$   
 S5 | S4  
 1940

raise a

mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, W. of cor.

80.46 The cor. of secs. 4, 5, 8, and 9.  
 Land, nearly level.  
 Soil, clay; 2nd rate.  
 Undergrowth, greasewood, shadscale, and rabbit brush.  
 Fair grazing.

From the standard cor. of secs. 31 and 32, on 4th standard parallel south, on S. bdy., of the township, an iron post 2 ins. diam., properly set, marked and witnessed as described in official record of the survey of T. 21 S., R. 8 W., Group No. 255, Utah.

N. 0°27' E., bet. secs. 31 and 32.

Over nearly level desert land, with an easterly slope, through medium dense shadscale undergrowth.

40.33 Proportionate distance; no evidence of original cor.  
 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked

$\frac{1}{4}$   
 S31 | S32  
 1940

raise a small

mound of stone, W. of post.

80.67 Proportionate distance; no evidence of original sec. cor.  
 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for restored cor. secs. 29, 30, 31, and 32, with brass cap marked

T20S | R8W  
 S30 | S29  
 S31 | S32  
 1940

raise a

small mound of stone, W. of post.

Land, nearly level with a general easterly slope.  
 Soil, gravelly clay; 2nd rate.  
 Undergrowth, shadscale.  
 Fair grazing.

## DEPENDENT RESURVEY OF SUBDIVISION T. 20 S., R. 8 W.

## Chains

- From the cor. of secs. 28, 29, 32, and 33.  
N. 89°47' W., bet. secs. 29 and 32.  
Over nearly level land, through short undergrowth.
- 1.10 Unimproved road, bears N. 30° W. to railroad crossing and S. 30° E. to reservoir.
- 20.80 Dim road on E. side and parallel to railroad.
- 21.20 Telegraph line, 8 wire, parallel to railroad.
- 22.65 Union Pacific Railroad, single track, bears N. 17°16' E. and S. 17°16' W.
- 24.10 Telegraph line, 13 wire, bears same.
- 24.50 Graded road between Desert and Black Rock, parallel to railroad.
- 39.10 Low clay rim, 2 ft. high, facing W., bears N. 20° E. and S. 20° W.
- 40.30 Proportionate distance; no evidence of original cor.  
Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked
- |                               |
|-------------------------------|
| 829                           |
| $\frac{1}{4}$ <u>        </u> |
| 832                           |
| 1940                          |
- raise a
- small mound of stone, N. of post.
- 80.59 The cor. of secs. 29, 30, 31, and 32., 15 ft. above the  $\frac{1}{4}$  sec. cor. and 25 ft. above sec. cor.  
Land, nearly level desert; slight easterly slope.  
Soil, heavy clay and gravelly clay; 2nd rate.  
Undergrowth, shadscale.  
Fair grazing.
- 
- From the cor. of secs. 30 and 31, on the W. bdy. of the township.  
S. 89°48' E., bet. secs. 30 and 31.  
Over gently rolling desert land, with general easterly slope, through short undergrowth.
- 40.22 Proportionate distance; no evidence of original  $\frac{1}{4}$  sec. cor.  
Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked
- |                               |
|-------------------------------|
| S30                           |
| $\frac{1}{4}$ <u>        </u> |
| S31                           |
| 1940                          |
- raise a
- small mound of stone, N. of cor.

DEPENDENT RESURVEY OF SUBDIVISION, T. 20 S., R. 8 W.

Chains

30.57 The cor. of secs. 29, 30, 31, and 32, 30 ft. below sec. cor.  
 Land, gently rolling and nearly level.  
 Soil, gravelly clay; heavy clay; 2nd rate.  
 Undergrowth, shadscale.  
 Fair grazing.

N. 0°25' E., bet. secs. 29 and 30.

Over nearly level land, through short undergrowth; descend 30 ft. to  $\frac{1}{4}$  sec. cor.

39.50 Dim road, bears N. 60° E. and S. 60° W.

40.33 Proportionate distance; no evidence of original  $\frac{1}{4}$  sec. cor.  
 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked

1 — 4	S30	S29
	1940	

small mound of stone, W. of post. raise a

67.50 Small wash from the SW., drains N. 10° E.

76.20 Recross same, drains N. 30° W.

80.67 Proportionate distance; no evidence of original sec. cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for restored cor. secs. 19, 20, 29, and 30, with brass cap marked

T20S	R8W
S19	S20
S30	S29
1940	

small mound of stone, W. of post. raise a

Land, nearly level desert; slight NE. exposure.  
 Soil, gravelly clay and heavy clay; 2nd rate.  
 Undergrowth, shadscale.  
 Fair grazing.

From the cor. of secs. 20, 21, 28, and 29.

N. 89°47' W., bet. secs. 20 and 29.

Over nearly level land, through short undergrowth.

0.11 The W. edge of road, parallel to railroad.

18.50 Dim road, bears N. 55° E. and S. 55° W.

40.22 Proportionate distance; no evidence of original  $\frac{1}{4}$  sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked

## DEPENDENT RESURVEY OF SUBDIVISION, T. 20 S., R. 8 W.

Chains

S20

S29

1940

raise a

small mound of stone, N. of post.

54.30 Dim road, bears N. 60° W. and S. 60° E.

80.44 The cor. of secs. 19, 20, 29, and 30.

Land, nearly level.

Soil, clay and sandy clay; 2nd rate.

Undergrowth, shadscale.

Fair grazing.

From the cor. of secs. 19 and 30, on the N. bdy. of the township.

S. 69°50' E., bet. secs. 19 and 30.

Over nearly level desert with slight easterly slope, through short undergrowth.

15.30 Dim road, bears N. 15° W. about 30 chs. to reservoir, and S. 15° E.

40.10 Proportionate distance; no evidence of the orig. sec. cor.

Set an iron post, 3 ft. long, 3 in. diam., 27 ins. in the ground, for restored sec. cor., with brass cap marked

S19

S30

1940

raise a

small mound of stone, N. of post.

Cor. is about 20 ft. below sec. cor. on bdy.

76.50 Small wash, drains N. 10° W.

80.39 The cor. of secs. 19, 20, 29, and 30.

Land, nearly level; slight easterly slope.

Soil, clay; 2nd rate.

Undergrowth, shadscale.

Fair grazing.

N. 0°30' E., bet. secs. 19 and 20.

Over nearly level land, through short undergrowth.

11.50 Dim road, bears N. 70° W. and S. 70° E.

37.30 Dim road, bears E. and W.

39.40 A drainage ditch, drains W.

40.34 Proportionate distance; no evidence of original sec. cor.

DEPENDENT RESURVEY OF SUBDIVISION T. 20S, R. 8W.

Chains

anlarfo

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked

$\frac{1}{4}$   
S19 | S20

1940

small mound of stone, W. of post.

raise a

30.00 Enter greasewood undergrowth.

30.57 Proportionate distance; no evidence of original sec. cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in ground, for restored cor. secs. 17, 18, 19, and 20, with brass cap marked

T20S | R8W  
S18 | S17

S19 | S20

1940

small mound of stone, W. of post.

raise a

Land, nearly level desert.

Soil, clay; 2nd rate.

Undergrowth, shadscale, with greasewood on N. end of mile

Fair grazing.

From the cor. of secs. 16, 17, 20, and 21.

N. 89°44' W., bet. secs. 17 and 20.

Over nearly level land, through short undergrowth.

40.20 Proportionate distance; no evidence of the original position for  $\frac{1}{4}$  sec. cor. a cedar stake, 3 ft. long, 3 ins. diam., having dim scribe marks, was found lying on the ground out of place.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old stake deposited alongside, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked

S17  
\$ ———  
S20

1940

small mound of stone, N. of post.

raise a

41.60 Wash, 20 lbs. wide, 3 ft. deep, drains NW.

50.11 The cor. of secs. 17, 18, 19 and 20.

Land, nearly level desert.

Soil, clay; sandy clay; 2nd rate.

Undergrowth, greasewood.

Fair grazing

DEPENDENT RESURVEY OF SUBDIVISION, T. 20 S., R. 8 W.

Corner

From the cor. of secs. 18 and 19, on the W: bdy. of the township.


S. 89°50' E., bet. secs. 18 and 19:

Over nearly level land, through schadscale undergrowth.

40.16

Proportionate distance; no evidence of original cor. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked



1940

raise a small mound of stone, N. of post.

64.00

Leave shadscale and enter greasewood undergrowth.

80.45

The cor. of secs. 17, 18, 19, and 20.

Land, nearly level.  
Soil, sandy clay; 2nd rate.  
Undergrowth, shadscale and greasewood.  
Fair grazing:

N. 0°02' W., bet. secs. 17 and 18.

Over nearly level land, through medium dense greasewood and scattered shadscale.


26.20

Dim old road, bears NW. and SE.

40.33

Proportionate distance; no evidence of original  $\frac{1}{4}$  sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked




1940

raise a small mound of stone, W. of post.

80.67

Proportionate distance; no evidence of the original sec. cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for restored cor. secs. 7, 8, 17, and 18, with brass cap marked



1940

raise a small mound of stone, W. of post.

DEPENDENT RESURVEY OF SUBDIVISION, T. 20 S. R. 8 W.

Chains	<p>Land, nearly level. Soil, sandy clay and heavy clay; 2nd rate. Undergrowth, greasewood and shadscale. Fair grazing.</p>	marked
	<p>From the cor. of secs. 8, 9, 16, and 17. N. 89°44' W., bet. secs. 8 and 17. Over nearly level land, through medium dense undergrowth.</p>	21.04
40.34	<p>Proportionate distance; no evidence of the original <math>\frac{1}{4}</math> sec cor.  Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored <math>\frac{1}{4}</math> sec. cor., with brass cap marked</p> <p style="text-align: center;">S8 <math>\frac{1}{4}</math> S17</p> <p style="text-align: center;">1940</p> <p style="text-align: right;">raise a</p>	21.04
20.67	<p>The cor. of secs. 7, 8, 17, and 18. Land, nearly level desert. Soil, clay; 2nd rate. Undergrowth, greasewood. Fair grazing.</p>	
	<p>From the cor. of secs. 7 and 18, on W. bdy. of the township. S. 89°49' E., bet. secs. 7 and 18. Over nearly level desert land, through short undergrowth.</p>	23.04
33.20	<p>Dim old road, bears NW. and SE.</p>	
40.10	<p>The original <math>\frac{1}{4}</math> sec. cor.; a cedar stake, 2<math>\frac{1}{2}</math> ft. long, 2 ins. diam., firmly set, and having dim scribe marks.  At point for cor.  Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, old stake set alongside, for <math>\frac{1}{4}</math> sec. cor., with brass cap marked</p> <p style="text-align: center;">S7 <math>\frac{1}{4}</math> S18</p> <p style="text-align: center;">1940</p> <p style="text-align: right;">raise a</p>	22.00
40.37	<p>The cor. of secs. 7, 8, 17, and 18. Land, nearly level. Soil, clay; 2nd rate.</p>	

DEPENDENT RESURVEY OF SUBDIVISION T. 20 S., R. 8 W.

Chains

Undergrowth, greasewood.  
Fair grazing.


N. 0°08' E., bet. secs. 7 and 8.

Over nearly level land, through medium dense short undergrowth.

40.34

Proportionate distance; no evidence of original  $\frac{1}{4}$  sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked



small mound of stone, W. of post.

raise a

57.00

Shallow wash, 30 lks. wide, drains N. 20° E.


72.00

Recross same, drains NW.

80.67

Proportionate distance; no evidence of original sec. cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for restored cor. secs. 5, 6, 7, and 8, with brass cap marked



small mound of stone, W. of post.

raise a

Land, nearly level.  
Soil, clay; 2nd rate.  
Undergrowth, greasewood.  
Fair grazing

From the cor. of secs. 4, 5, 8, and 9.


N. 89°43' W., bet. secs. 5 and 8.

Over nearly level land, through medium dense undergrowth.

40.51

Proportionate distance; no evidence of the original  $\frac{1}{4}$  sec. cor.

Set an iron post; 3 ft. long, 1 in. diam.; 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked



1940

small mound of stone, N. of post.

raise a

Chains

enlanO

81.02 The cor. of secs. 5, 6, 7, and 8, on the N. bdy. of the township, an iron post, 2 ins. diam., properly set, marked and witnessed as described by me in the resurvey of T. 19 S., R. 8 W., this Group.

Land, nearly level.  
Soil, clay; 2nd rate.  
Undergrowth, greasewood.  
Fair grazing.

From the cor. of secs. 6 and 7, on the W. bdy. of the township, an iron post, 2 ins. diam., properly set, marked and witnessed as described by me in the resurvey of T. 19 S., R. 8 W., this Group.

S. 89°45' E., bet. secs. 6 and 7.

Over nearly level land, through short undergrowth.

40.06 Proportionate distance; no evidence of the original  $\frac{1}{4}$  sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked



1940

small mound of stone, N. of post. raise a

48.00 Leave shadscale, enter greasewood undergrowth.

66.20 Small wash, drains N. 30° W.

80.43 The cor. of secs. 5, 6, 7, and 8.

Land, nearly level.  
Soil, clay; 2nd rate.  
Undergrowth, shadscale and greasewood.  
Fair grazing.

From the cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the township, an iron post, 2 ins. diam., properly set, marked and witnessed as described by me in the resurvey of T. 19 S., R. 8 W., this Group.


S. 0°48' W., bet. secs. 5 and 6.

Over level desert land, through medium dense undergrowth.

8.00 Dim old road, bears E. 55° E. and N. 55° W.

40.13 Proportionate distance; no evidence of the original  $\frac{1}{4}$  sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for restored  $\frac{1}{4}$  sec. cor., with brass cap marked



1940

small mound of stone, W. of post. raise a

## DEPENDENT RESURVEY OF SUBDIVISION, T. 20 S., R. 8 W.

Chains

80.47 The cor. of secs. 5, 6, 7, and 8.

Land, level desert.  
Soil, heavy clay; 2nd rate.  
Undergrowth, greasewood.  
Fair grazing.

## GENERAL DESCRIPTION.

Township 20 South, Range 8 West consists of nearly level valley or desert land, except in the southwest corner which is gently rolling with a general easterly slope, being near the west edge of the valley. The elevation is about 4600 ft. above sea level. The soil is principally a heavy clay or sandy clay, containing some alkali; in the southwest part it is gravelly clay; can be classified as 2nd to 3rd rates throughout the township. Short undergrowth of greasewood, shadscale, salt brush and grass cover the township, affording a fair winter range for the grazing of stock.

The Union Pacific Railroad between Salt Lake City, Utah and Los Angeles, California, crosses the township in a northeast and southwest direction from sec. 3 to sec. 32; the Neels siding is located near the  $\frac{1}{4}$  sec. cor. bet. secs. 28 and 29. A graded county road between Deseret and Black Rock parallels the west side of railroad. A graded road between Clear Lake station, which is located about  $\frac{1}{2}$  mile north of this township, and Fillmore, Utah, crosses through secs. 1 and 2 in a northwest and southeast direction. There are several other unimproved roads in the township, used mainly by sheepmen. The American Telephone & Telegraph Company's transcontinental line crosses the southeast corner through secs. 24, 25, 35, and 36, in a southwest and northeast direction. Irrigation canals, now abandoned, which formerly brought water from Clear Lake about 4 miles to the east of this township, crosses the northeast portion; the water was used to irrigate lands in secs. 4 and 5, and adjacent lands in southern part of T. 19 S., R. 8 W. These lands have all been abandoned and former settlers moved away.

Recently a small reservoir has been constructed in NW $\frac{1}{4}$  SW $\frac{1}{4}$  of sec. 19. Another reservoir located in S $\frac{1}{2}$  of sec. 33, has been recently constructed by building a dyke nearly  $\frac{1}{2}$  mile long across old channels of the former Beaver River.

The channel of the former Beaver River enters on S. bdy. of sec. 33, and drains northerly, disappearing entirely in the northwest portion.

The township is chiefly valuable for grazing purposes. There is no water nor any settlers, and no indications of mineral, oil, or coal were found within the township.

The magnetic declination is approximately 16 $\frac{1}{2}$ ° E.



## CERTIFICATE OF SURVEYOR

I, Andrew Nelson, Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 29th day of July, 1936, and supplemental special instructions dated September 26, 1938, supplemental instructions received from the district cadastral engineer for Utah, with assignment October 27, 1938 and October 25, 1939, I have surveyed made a dependent resurvey of West Boundary and portions of the Subdivision; establishment of quarter section corners on the North Boundary, and Extension Survey completing the Subdivision of Township 27 South, Range 13 West of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Salt Lake City, Utah.  
April 23, 1941.

Andrew Nelson  
Surveyor

## CERTIFICATE OF APPROVAL

OFFICE OF SUPERVISOR OF SURVEYS,

Denver, Colorado, January 27, 1945.

The foregoing field notes of the survey of Dependent Resurvey of West Boundary, and portions of the Subdivision; establishment of quarter section corners on the North Boundary, and Extension Survey completing the Subdivision of Township 27 South, Range 13 West, Salt Lake Meridian, Utah. executed by Andrew Nelson, Surveyor under special instructions dated September 26, 1938 supplemental instructions dated July 29, 1936, and supplemental special land assignment instructions dated Oct. 27, 1938 & Oct. 25, 1939, having been critically examined, and the necessary corrections made prior to their certification by the engineer, the said field notes, and the survey therein described, are hereby approved.

W. H. Long  
Supervisor of Surveys.

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in~~  
~~is a true copy of the original field notes on file in the public survey office.~~

W. H. Long  
Supervisor of Surveys.









4-1939  
(September 1940)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

# FIELD NOTES.

Of the ..... Meridian,

in the State of .....

EXECUTED BY

Under special instructions dated ....., 19....., which provided

for the surveys included under Group No. ...., approved .....

and assignment instructions dated ....., 19.....

Survey commenced ....., 19.....

Survey completed ....., 19.....

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

# FIELD NOTES

Of the ..... Meridian,

in the State of .....

EXECUTED BY

Under special instructions dated ....., 19....., which provided

for the surveys included under Group No. ...., approved .....

and assignment instructions dated ....., 19.....

Survey commenced ....., 19.....

Survey completed ....., 19.....







UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

# FIELD NOTES

Of the ..... Meridian,

the State of .....

EXECUTED BY

under special instructions dated ....., 19....., which provided

for the surveys included under Group No. ...., approved .....

and assignment instructions dated ....., 19.....

Survey commenced ....., 19.....

Survey completed ....., 19.....

## Dependent Resurvey of the Subdivision of T. 23 S., R. 1 W.

## Chains

- 8.40 Road, bears NE. and SW.  
 17.70 Draw, drains NW., ascend 140 ft. along a SE. slope.  
 31.90 Spur, projects NW., descend 55 ft. along a W. slope.  
 36.95 Fence, bears N. and S.  
 40.01 The corner of sections 26, 27, 34, and 35.

Land, rolling mountain top.  
 Soil, sandy to gravelly mountain loam.  
 Timber, juniper, pinon, and pine.  
 Undergrowth, sagebrush, bitter brush, weeds, and grass.

-----

General Description

The land in the two sections under resurvey lies on the rolling top between the main Fork of the Sevier River to the west and Lost Creek to the east. The soil is a deep, sandy to rocky mountain loam. The timber is largely juniper and pinon, but in the higher elevations may be found Ponderosa pine and mountain mahogany. The undergrowth is perdominently sagebrush, with lesser amounts of bitter brush, rabbit brush, weeds and grass. There are no settlers living in the area, which lies partly in the national forest. No indications of commercial deposits of mineral were encountered.

-----



4-222  
(Feb., 1950)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

## FIELD ASSISTANTS

NAMES	CAPACITY
Fred R. Chappell	Principal Assistant
Reo V. Hunt	Chairman
Robert M. Hanson	Chairman
William D. Bowes	Chairman
Lyle D. Creel	Flagman
Grant L. Jones	Cornerman
Marion McMichell	Extension

CERTIFICATE OF CADASTRAL ENGINEER

I, Robert C. Yundt, Cadastral Engineer, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 18th day of July 1949, I have surveyed dependently resurveyed the southern two miles of the Salt Lake Meridian in Township 23 South, and Sections 35 and 36 in Township 23 South, Range 1 West-

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Salt Lake City, Utah  
April 15, 1951

Robert C. Yundt  
Robert C. Yundt  
Cadastral Engineer

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,  
Washington, D. C., SEP 22 1952, 19

The foregoing field notes of the survey of dependent resurvey of the southern two miles of the Salt Lake Meridian in Township 23 South, and Sections 35 and 36 in Township 23 South, Range 1 West of the Salt Lake Meridian, Utah

executed by Robert C. Yundt, Cadastral Engineer having been critically examined and found correct, are hereby approved.

Donald Clement  
Acting Chief, Division of Cadastral Engineering.

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

Chief, Division of Cadastral Engineering.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

# FIELD NOTES

of the

Dependent Resurvey of Portions of the Subdivision

and

Subdivision of Section 7

in

Township 23 South, Range 2 West

Of the Salt Lake Meridian,

the State of Utah

## EXECUTED BY

Robert C. Yundt, Cadastral Engineer

under special instructions dated July 18, 1949, which provided

for the surveys included under Group No. 373 Utah, approved August 17, 1949

and assignment instructions dated June 6, 1950

Survey commenced June 20, 1950

Survey completed June 27, 1950

# INDEX DIAGRAM

Township 23 South, Range 2 West

	6	5	3	4	3	2	1
	7	4					
	8						
2	9	6	8	9	10	11	12
	5						
	18	17	16	15	14	13	
	19	20	21	22	23	24	
	30	29	28	27	26	25	
	31	32	33	34	35	36	

## Township 23 South, Range 2 West

## Chains

The original survey of Township 23 South, Range 2 West of the Salt Lake Meridian, Utah, was commenced by Charles Mogo in 1856, continued by Augustus D. Ferron in 1876 and completed by John T. Breckon in 1896. The following field notes are those of a dependent resurvey of the lines between sections 4 and 5, 5 and 8, and the boundaries of section 7, together with the survey of a portion of the subdivision of section lines of section 7. The survey and resurvey was made at the request of the Division of Range Management of the Bureau of Land Management in order to determine the boundaries of certain public lands in the township.

The dependent resurvey is a restoration of the lines of the original survey in their true, original positions according to the identified evidence of the original survey. Before remonumenting an identified original corner or restoring a missing corner, the lines of the original survey were retraced and searches made for evidence of the original corner monument, and other calls of the field notes. After completing the necessary retracements, the rules of proportionate measurement were applied in order to ascertain the position of each lost corner, and when duly identified or restored, the corner positions were remonumented with the regulation iron survey posts. In order to simplify the record, only the true line notes referring to the completed resurvey, are supplied here.

The survey was made with Buff and Buff solar transit number 26594, the property of the Bureau of Land Management, and constructed in accordance with their standard specifications. The instrument was in good condition, and prior to the beginning of the field work, it was tested and found to be free from error. Since the directions of the lines of the survey were determined by the use of the solar attachment, the indicated meridians obtained by its use were compared with the true meridian established by Polaris observations, and found to be in close agreement. The instrument was maintained in good condition during the field work, and the continued accuracy of the solar attachment was verified by frequent checks on the true meridian.

The measurements were made with Lallie steel ribbon tapes eight chains in length. These tapes are graduated every link for the first chain, and thereafter at intervals of ten links. They were tested by comparison with a Lufkin standard steel tape, one chain in length, and found to be correct. The measurements were made on the slope, the vertical angle of each interval determined by the use of clinometers and the slope distances properly reduced to horizontal equivalents, which appear in these notes.

The geographic position of the southeast corner of section 7, as determined from the Bureau of Land Management state maps is as follows: Latitude  $39^{\circ}49'N.$ , longitude  $112^{\circ}03'W.$ . The radius for latitude was verified by meridian solar observations.

The mean magnetic declination was found to be  $16\frac{1}{4}^{\circ}$  E.

-----

Dependent Resurvey of a Portion of the West Boundary  
of T. 23 S., R. 2 W.

Reestablishment of the Surveys Executed by  
John T. Breckon in 1896.

Beginning at the corner of sections 7, 12, 13, and 18, T. 23 S., Rs. 2 and 3 W., marked by a limestone rock, 14x10x8 ins., firmly set in the ground, and in a mound of stone, and marked with four grooves on the south face and two grooves on the north face, and which I remonument as follows:

At the same point:

Dependent Resurvey of a Portion of the West Boundary  
of T. 23 S., R. 2 W.

Chains

Set an iron post, 3 ft. long and 2 ins. in diameter, 6 ins. in the ground to solid rock, and in a mound of stone, with brass cap mkd:

T23S	
R3W	R2W
S12	S 7
S13	S18

1950

Deposit the original stone alongside the iron post.

Thence:

N. 0°26' E., between sections 7 and 12.

Over mountainous land, through widely scattered timber and a scant undergrowth, ascend along a broken SE. slope.

20.00 Spur, projects SE., descend along a broken NE. slope.

27.00 Draw, drains S. 60° E., ascend along a SW. slope.

40.76 The  $\frac{1}{4}$  section corner of sections 7 and 12, marked by a limestone rock, 20x8x8 ins., firmly set in the ground, and in a mound of stone, and marked  $\frac{1}{4}$  on the west face:

At the same point:

Set an iron post, 3 ft. long and 1 in. in diameter, 20 ins. in the ground to solid rock, and in a mound of stone, with brass cap mkd:

$\frac{1}{4}$	
S12	S7

1950

Deposit the original stone alongside the iron post.

Thence:

N. 0° 50' W. beginning new measurement.

Ascend along a SW. slope over ledges.

21.00 Spur, projects S. 60° E., descend along a broken NE. slope over ledges.

26.00 Willow Creek wash, drains SE., ascend along a SW. slope over ledges.

41.09 The corner of sections 1, 6, 7, and 12, marked by a weathered sandstone rock, 16x8x5 ins., firmly set in the ground and in a mound of stone, and having chisel marks on both the north and south edges:

At the same point:

Set an iron post, 3 ft. long and 2 ins. in diameter, 28 ins. in the ground, and in a circular collar of stone, with brass cap mkd:

T23S	
R3W	R2W
S1	S6
S12	S7

1950

Chains

Deposit the original stone alongside the iron post.

Land, rough and broken mountain slopes.

Soil, rocky clay loam.

Timber, juniper and pinon.

Undergrowth, sagebrush, weeds, and grass.

Dependent Resurvey of the Subdivision of T. 23 S., R. 2 W.

Reestablishment of the Surveys Executed by Chas. Mogo  
in 1866 and John T. Breckon in 1896.

Beginning at the corner of sections 4, 5, 32, and 33 on the north boundary of the township, marked by a sandstone rock, 18x6x2 ins., firmly set in the ground and in a mound of stone and marked with four grooves on the east edge and two grooves on the west edge, and which monument as follows:

At the same points:

Set an iron post, 3 ft. long and 2 ins. in diameter, 20 ins. in the ground to solid rock, and in a mound of stone, with brass cap marked:

T225 R2W  
S33 S33

S6 S4  
T23  
1960

Deposit the original stone alongside the iron post.

Trench:

S. of 25' E. between sections 4 and 5.

Over nearly level land, through widely scattered timber and a scant undergrowth, descend along a general S. slope.

4.70 Small wash, drains E.

14.60 Wash, drains E.

38.75 Telephone line, bears N. 40° 45' E. and S. 40° 45' W.

40.35 The section corner of sections 4 and 5 at proportionate distance: No trace of the original corner being found.

Set an iron post, 3 ft. long and 1 in. in diameter, 15 ins. in the ground to solid rock, and in a mound of stone, with brass cap marked:

S6 S4

1960

Deposit broken glass at the base of the post.

40.90 Road, bears E. and W.

45.55 Road, bears E. and W.


53.45 Road, bears NE. and SW.

Chains

- 66.20 Road, bears NE. and SW.
- 68.50 Canal, about 20 links wide and 10 ft. deep, flows NE.
- 70.20 Road, bears NE. and SW.
- 80.66 The corner of sections 4, 5, 8, and 9, marked by a weathered sandstone rock, 12x8x5 ins., set in the ground at the corner of fences bearing south and east. There are no marks visible on the stone, but it has long been used as marking the corner point, and it is accepted as the best available evidence of the original corner point:

At the same point:

Set an iron post, 3 ft. long and 2 ins. in diameter, 20 ins. in the ground, with brass cap marked:



1950

Deposit the original stone alongside, and broken glass at the base of the post.

Land, gently rolling desert.  
 Soil, sandy to gravelly clay loam.  
 Timber, juniper.  
 Undergrowth, sagebrush, shadscale, weeds, and grass

S. 89° 20' W., between sections 5 and 8.

Over nearly level land, through widely scattered timber and a scant undergrowth, along a gentle SE. slope.

- .10 Road, bears NE. and SW.
- 6.75 Road, on the east bank of canal, bears NE. and SW., canal flows NE.
- 7.45 West bank of canal, bears NE. and SW.
- 8.00 Road, bears NE. and SW.
- 23.20 Wash, drains SE.
- 28.35 Wash, drains SE.
- 39.77 The  $\frac{1}{4}$  section corner of sections 5 and 8 at proportionate distance: No trace of the original corner being found:

Set an iron post, 3 ft. long and 1 in. in diameter, 20 ins. in the ground to solid rock, and in a mound of stone, with brass cap mkd.:

85



S8  
1950

Deposit broken glass at the base of the post.

## Dependent Resurvey of the Subdivision of T. 23 S., R. 2 W.

## Chains

- 40.00 Road, bears NW. and SE.
- 41.20 Telephone line, bears N. 40° 45' E., and S. 40° 45' W.
- 41.45 Wash, drains SE.
- 59.06 Wash, drains SE.
- 79.54 The original corner of sections 5, 6, 7, and 8, marked by a sandstone rock, 18x14x8 ins., firmly set in the ground and marked with five notches on each of the south and east edges, witnessed by a mound of stone to the west:
- At the same point:
- Set an iron post, 3 ft. long and 2 ins. in diameter, 24 ins. in the ground, and in a mound of stone, with brass cap marked:
- |          |
|----------|
| T23S R2W |
| S6 : S5  |
| -----    |
| S7 : S8  |
- 1950
- Deposit the original stone alongside the iron post.
- Land, gently rolling desert.  
Soil, sandy to gravelly clay loam.  
Timber, juniper.  
Undergrowth, sagebrush, shadscale, weeds and grass.
- 
- Beginning at the corner of sections 7, 12, 13, and 18 on the west boundary of the township:
- Thence:
- N. 89° 14' E. between sections 7 and 18.
- Over mountainous land, through widely scattered timber and a scant undergrowth, descend along a NE. slope.
- 15.30 Draw, drains S. 30° E., ascend along a SW. slope.
- 19.48 Point for the west 1/16 section corner of sections 7 and 18 at proportionate distance:
- Set an iron post, 3 ft. long and 1 in. in diameter, 24 ins. in the ground to solid rock, and in a mound of stone, with brass cap marked:
- |              |
|--------------|
| S7           |
| W 1/16 ----- |
| S18          |
- 1950
- Deposit broken glass at the base of the post.
- 21.00 Spur, projects S. 30° E. about 16 chains to end, descend along a NE. slope.
- 26.00 Leave mountainous land and enter nearly level desert, edge bears NE. and SW.
- 27.40 Road, bears S. 20° E. and N. 20° W.

## Dependent Resurvey of the Subdivision of T. 25 S., R. 2 W.

Chains					
39.76	<p>The <math>\frac{1}{4}</math> section corner of sections 7 and 18 at proportionate distances. No trace of the original corner being found:</p> <p>Set an iron post, 3 ft. long and 1 in. in diameter, 28 ins. in the ground and in a collar of stone, with brass cap marked:</p> <p style="text-align: center;">S7</p> <p style="text-align: center;"><math>\frac{1}{4}</math> ———</p> <p style="text-align: center;">S18 1950</p> <p style="text-align: center;">Deposit broken glass at the base of the post.</p>				
47.80	Telephone line, bears N. 40°45' E. and S. 40°45' W., also small wash draining SE.				
51.70	Road, bears NW. and SE.				
53.40	Wash, drains SE.				
67.00	Wash, drains SE.				
75.00	Road, bears NE. and SW.				
76.30	Fence, bears NE. and SW.				
79.43	Corner of fences extending E. and S.				
79.52	<p>The corner of sections 7, 8, 17, and 18, marked by a sandstone rock, 14x10x8 ins., firmly set in the ground, and marked with five notches on the east edge and four notches on the south edge:</p> <p>At the same point:</p> <p>Set an iron post, 3 ft. long and 2 ins. in diameter, 24 ins. in the ground, and in a collar of stone, with brass cap marked:</p> <p style="text-align: center;">T23S R2W</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 2px;">S7</td> <td style="padding: 2px;">S8</td> </tr> <tr> <td style="padding: 2px;">S18</td> <td style="padding: 2px;">S17</td> </tr> </table> <p style="text-align: center;">1950</p> <p style="text-align: center;">Deposit the original stone alongside the iron post.</p> <p>Land, mountainous in the west and nearly level desert in the east. Soil, sandy to rocky clay loam. Timber, juniper. Undergrowth, sagebrush, weeds, and grass.</p> <p style="text-align: center;">-----</p> <p>North, between sections 7 and 8.</p> <p>Over nearly level land, through a scant undergrowth.</p>	S7	S8	S18	S17
S7	S8				
S18	S17				
2.60	Fence, bears NE. and SW.				
3.10	Road, bears NE. and SW.				
11.20	Wash, drains E.				
14.00	Road, bears NE. and SW.				
28.90	Road, bears E. and W.				
36.70	Telephone line, bears N. 40°45' E. and S. 40°45' W.				

## Dependent Resurvey of the Subdivision of T. 23 S., R. 2 W.

## Chains

40.44 Point for the  $\frac{1}{4}$  section corner at proportionate distance: No trace of the original corner being found:

Set an iron post, 3 ft. long and 1 in. in diameter, 24 ins. in the ground, and in a mound of stone, with brass cap marked:

$\frac{1}{4}$   
S7 | S8

1950

Deposit broken glass at the base of the post.

52.10 Road, bears NW. and SE.

62.90 Wash, drains E.

68.20 Wash, drains E.

80.88 The corner of sections 5, 6, 7, and 8.

Land, gentle SE. slope.

Soil, gravelly to rocky clay loam.

Timber, juniper.

Undergrowth, sagebrush, weeds, and grass.

-----

Beginning at the corner of sections 1, 6, 7, and 12 on the west boundary of the township:

Thence:

East, between sections 6 and 7.

Over mountainous land, through scattering timber and a scant undergrowth, ascend 405 ft. over a steep SW. slope over ledges.

6.80 Rocky spur, projects SE., descend 465 ft. along a broken NE. slope over ledges.

23.70 Draw, drains SE., ascend 45 ft. along a SW. slope.

29.80 Spur, projects S., descend along a NE. slope.

39.45 The  $\frac{1}{4}$  section corner of sections 6 and 7, marked by a sandstone rock 14x10x6 ins., firmly set in the ground, and in a mound of stone, and marked  $\frac{1}{4}$  on the north face:

At the corner:

Set an iron post, 3 ft. long and 1 in. in diameter, 28 ins. in the ground and in a collar of stone, with brass cap marked:

S6

$\frac{1}{4}$  ———  
S7

1950

Deposit the original stone alongside the iron post.

-----

Thence:

## Survey of the Subdivision of section Lines of Section 7.

Chains	
	N. 89°52' E., beginning new measurement.
.90	Wash, drains S. 60° E.
9.00	Wash, drains SE.
16.50	Wash, drains SE.
19.90	Wash, drains SE.
24.10	Low spur, projects SE.
40.35	The corner of sections 5, 6, 7, and 8. Land, rough mountain slopes in the west and rolling land in the east. Soil, sandy to rocky clay loam. Timber, juniper and pinon. Undergrowth, sagebrush, weeds, and grass.
----- Subdivision of section 7, T. 23 S., R. 2 W. Beginning at the $\frac{1}{4}$ section corner of sections 7 and 18. Thence: N. 0°25' W. along the north-south center line of section 7. Over nearly level land, through widely scattered timber and a scant undergrowth.	
9.65	Wash, drains S. 20° E.
16.75	Road, in gulch drains SE.
25.75	Wash, drains SE.
36.35	Road, bears NE. and SW.
40.60	The center $\frac{1}{4}$ section corner of section 7 at the intersection of the center lines of the section: Set an iron post, 3 ft. long and 1 in. in diameter, 26 ins. in the ground, and in a mound of stone, with brass cap marked:  C $\frac{1}{4}$  S 7 1950  Deposit broken glass at the base of the post.
40.90	Road, bears E. and W.
44.20	Road, bears NW. and SE.
57.20	Spur, projects E.
61.75	Draw, drains S. 60° E.
78.45	Low spur, projects E.
81.32	The $\frac{1}{4}$ section corner of sections 6 and 7. Land, nearly level in the south, rolling in the north. Soil, sandy to gravelly clay loam. Timber, juniper. Undergrowth, sagebrush, weeds, and grass.

## Subdivision of Section 7

## Chains

Beginning at the  $\frac{1}{4}$  section corner of sections 7 and 8:

Thence:

S. 89° 28' W. along the east-west center line of section 7.

Over nearly level land, through a scant undergrowth.

31.00 Road, bears SE. and NW.

37.10 Road, bears NE. and SW.

40.04 The center  $\frac{1}{4}$  section corner of section 7.

42.80 Road, bears N. 80° E. and S. 80° W.

48.70 Road, bears SE. and NW.

52.70 Road, bears SE. and NW.

55.50 Wash, drains SE.

59.10 Wash, drains SE.

59.64 The center west  $\frac{1}{16}$  section corner of section 7 at proportionate distance:

Set an iron post, 3 ft. long and 1 in. in diameter, 34 ins. in the ground, in the west edge of a road bearing N. and S. with brass cap marked:

W  $\frac{1}{16}$   
C ————— C  
S 7  
1950

Deposit broken glass at the base of the post, and raise mounds of stone, 2 ft. base and 1 $\frac{1}{4}$  ft. high north and south of the post.

67.30 Spur, projects S. 30° E., descend along a SW. slope.

79.15 The  $\frac{1}{4}$  section corner of sections 7 and 12.

Land, nearly level in the east and rolling in the west.

Soil, sandy to gravelly clay loam.

Timber, few, widely scattered juniper in the west.

Undergrowth, sagebrush, weeds, and grass.

-----  
Beginning at the west  $\frac{1}{16}$  section corner of sections 7 and 18:

Thence:

N. 0° 03' W. along the north-south center line of the southwest quarter of section 7.

Over rolling land, through widely scattered timber and a scant undergrowth.

2.00 Spur, projects SE.

9.50 Spur, projects S. 60° E.

13.50 Road, bears S. 60° E. and N. 60° W.

14.60 Wash, drains S. 60° E.

Subdivision of Section 7, T. 13 N., R. 10 E., S. 10 N.

Chains

23.00 Road, bears N. 30° E., and S., 30° W.

28.90 Road, bears NE. and SW.

40.68 The center-west 1/16 section corner of section 7.

Land, low rolling hills.  
Soil, gravelly clay loam.  
Timber, juniper.  
Undergrowth, sagebrush, weeds, and grass.

General Description

The land in the area under survey is located in the rolling country north and west of the cultivated area north of Richfield, Utah. None of it is suitable for cultivation. The timber is principally juniper and pinyon and the undergrowth sagebrush, weeds and grass. In Willow Creek wash is a small intermittent stream of water. There are no settlers living in the area and no indications of commercial deposits of mineral were noted.

FIELD ASSISTANTS

4-680  
(Feb., 1960)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Fred R. Chappell	Principal Assistant
Reo V. Hunt	Chainman
Robert N. Hansen	Chainman
William D. Cowes	Flagman
Lyle D. Creel	Cornerman

CERTIFICATE OF CADASTRAL ENGINEER

424

I, Robert C. Yundt, Cadastral Engineer, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 18th day of July, 1949,

I have ~~surveyed~~ ~~independently~~ resurveyed the lines between sections 4 and 5, sections 5 and 8 and the boundaries of section 7, and subdivided section 7, Township 23 South, Range 2 West

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Salt Lake City, Utah, May 10, 1951

Robert C. Yundt
Robert C. Yundt
Cadastral Engineer

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
Washington, D. C., 19

The foregoing field notes of the ~~survey of~~ dependent resurvey of the lines between section 4 and 5, sections 5 and 8, and the boundaries of section 7, and subdivision of section 7, Township 23 South, Range 2 West of the Salt Lake Meridian, Utah

executed by Robert C. Yundt, Cadastral Engineer

having been critically examined and found correct, are hereby approved.

Donald J. Clement
Acting Chief, Division of Cadastral Engineering.

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in , is a true copy of the original field notes.

Chief, Division of Cadastral Engineering.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of the

Dependent Resurvey

of the

Northern Three Miles of the Salt Lake Meridian in Township 24 South

and the

Boundaries of Sections 1, 12, and 13 in Township 24 South, Range 1 West

Of the Salt Lake Meridian,

In the State of Utah

EXECUTED BY

Robert C. Yundt, Cadastral Engineer

Under special instructions dated July 18, 1949, 19, which provided

for the surveys included under Group No. 373-Utah, approved August 17, 1949

and assignment instructions dated September 28, 1949, 19  
and June 6, 1950

Survey commenced October 27, 1949, 19

Survey completed June 19, 1950, 19

# INDEX DIAGRAM

Township 24 South, Range 1 West

				5	6	
6	5	4	3	2	12	1 4
						11
7	8	9	10	11	10	12 3
						10
18	17	16	15	14	9	13 2
						8
19	20	21	22	23		24
30	29	28	27	26		25
31	32	33	34	35		36

1259

## Township 24 South, Range 1 West

The history of township 24 South Range 1 West, is as follows:

Part Surveyed	By Whom	Date	Retraced or		
			Resurveyed	By Whom	Date
S.L.Meridian	Bailey & Burrill	1874	Portion Retr.	Page & Swan	1897
Portion S.Bdy.	J. G. Burrill	1874	"	Resur.A.P.Hanson	1891
" " "	A. P. Hanson	1891	"	" Page & Swan	1897
W. Bdy.	Page & Swan	1897			
Portion N. Bdy.	A.D. Ferron-	1878			
" " "	Page & Swan	1897		Page & Swan	1897
Portion Sub-					
divisions	J. G. Burrill	1874			
Portion Sub-					
divisions	Page & Swan	1897			

The following field notes are those of a dependent resurvey of sections 1, 12, and 13 in Township 24 South, Range 1 West of the Salt Lake Meridian, Utah, re-establishing the surveys executed by Bailey and Burrill in 1874 and by Page and Swan in 1897.

This dependent resurvey is a reestablishment of the lines of the original survey in their true, original position, according to the identified evidence of that survey. Before remonumenting an identified original corner, or restoring a missing corner, the lines of the original survey were retraced, and searches made for evidence of the original corners and other calls of the field notes. After completing the necessary retracements, the rules of proportionate measurement were applied in order to ascertain the position of each lost corner, and when duly identified or restored the corner positions were remonumented with the regulation iron survey posts. In order to simplify the record, only the true line notes, referring to the completed resurvey, are supplied here.

The survey was executed with Buff and Buff solar transit number 26594, the property of the Bureau of Land Management, and constructed in accordance with their specifications. The instrument was in good condition and was tested and found free from error. Since the azimuth of the lines of the resurvey was determined by the use of the solar attachment, the indicated meridians obtained by the use of this attachment were compared to the true meridian determined by observations made upon Polaris, and found to be in satisfactory agreement. The instrument was maintained in good adjustment during the progress of the survey and the continued accuracy of the solar attachment was insured by additional checks with the instrument on the true meridian above described.

The measurements were made with Lallie steel ribbon tapes, eight chains in length. These tapes are graduated every link for the first chain, and thereafter at intervals of ten links. The tapes were tested by comparison with a Lufkin standard steel tape, one chain in length, and found to be correct. The measurements were made on the slope, the vertical angle of each interval determined by the use of clinometers, and the slope distances properly reduced to true horizontal equivalents, which appear in these field notes.

The geographic position of the southeast corner of sec. 13 as computed from the state maps is as follows:

Latitude 38°43' N. Longitude 111°51' W.

The mean magnetic declination was found to be 16° E.

-----

Dependent Resurvey of the Salt Lake Meridian  
in Township 24 South.

Reestablishment of the Surveys Executed by  
Bailey and Burrill in 1874.

Beginning at the corner of sections 13, 18, 19, and 24, Township 24 South, Ranges 1 East and 1 West, marked by a sandstone rock, 17x11x10 ins., firmly set in the ground and in a mound of stone at the corner of fences bearing E. and N. and marked with three grooves on the north and south edges:

Dependent Resurvey of the Salt Lake Meridian in T. 24 S.

Chains

At the same point

Set an iron post, 3 ft. long and 2 ins. in diameter, 28 ins. in the ground and in a mound of stone, with brass cap marked:

T24S	
R1W	R1E
S13	S18
S24	
S19	

1949

Deposit the original stone alongside the iron post.

-----

Thence:

N. 0° 04' W., between sections 13 and 18.

Over mountainous land, through widely scattered timber and a medium dense undergrowth, crossing and recrossing fence line.

10.17 The section corner of sections 13 and 18, marked by a granite rock, 16x11x5 ins., firmly set in the ground and in a mound of stone in fence line, and marked  $\frac{1}{4}$  on the west face:

At the same point:

Set an iron post, 3 ft. long and 1 in. in diameter, 12 ins. in the ground to solid rock, and in a mound of stone, with brass cap marked:

$\frac{1}{4}$	
S13	S18
1949	

Deposit the original stone alongside the iron post.

-----

Thence:

N. 89° 01' E., beginning new measurement.

11. Fork of Lost Creek, small stream of good water flows NE., ascend along a SE. slope.

10.12 The corner of sections 7, 12, 13, and 18, marked by a granite stone, 18x12x8 ins., firmly set in the ground and in a mound of stone in the fence line, marked with 2 notches on the north edge, 4 notches on the south edge, and 6 notches on the east and west edges:

At the same point:

Set an iron post, 3 ft. long and 2 ins. in diameter, 12 ins. in the ground to solid rock, and in a mound of stone, with brass cap marked:

T24S	
R1W	R1E
S12	S 7
S13	
S18	

1949

## Dependent Resurvey of the Salt Lake Meridian in T. 24 S.

Chains

Deposit the original stone alongside the iron post.

Land, rolling mountain slopes.  
Soil, gravelly to rocky mountain loam.  
Timber, juniper and pinon.  
Undergrowth, sagebrush, yellow top, weeds, and grass.

-----

N. 1°07' W. between sections 7 and 12.

Over mountainous land, through scattering timber and a medium dense undergrowth, ascend along a SE. slope.

- 8.40 Spur, projects NE., descend along a NW. slope.
- 21.40 Draw, drains NE., continue along an E. slope.
- 24.86 Rock ledge, bears NE. and SW.; and end of north-south fence line.
- 36.37 The  $\frac{1}{4}$  section corner of sections 7 and 12, marked by a granite stone, 15x12x6 ins., firmly set in the ground and in a mound of stone, and marked  $\frac{1}{4}$  on the west face:

At the same point:

Set an iron post, 3 ft. long and 1 in. in diameter, 18 ins. in the ground to solid rock, and in mound of stone, with brass cap marked:

	↑	
S12		S 7

1949

Deposit the original stone alongside the iron post.

-----

Thence:

N. 1°58' E., beginning new measurement.

Ascend along a steep SE. slope.

- 37.00 Spur, projects N. 60° E., descend along a NE. slope.
- 43.82 The corner of sections 1, 6, 7, and 12, marked by a granite stone, 36x12x8 ins., firmly set in the ground and in a mound of stone, and marked with 1 notch on the north edge, 5 notches on the south edge, and 6 notches on the east and west edges:

At the same point:

Set an iron post, 3 ft. long and 2 ins. in diameter, 18 ins. in the ground to solid rock, and in a mound of stone, with brass cap marked:

	T24S	
R1W		R1E
S1		S6
-----		
S12		S7

1949

Deposit the original stone alongside the iron post.

## Dependent Resurvey of the Salt Lake Meridian in T. 24 S.

Chains

Land, rough and broken mountain slopes.  
Soil, rocky mountain loam.  
Timber, juniper, pinon, and mahogany.  
Undergrowth, sagebrush, yellow top, weeds, and grass.

N. 1°04' W. between sections 1 and 6.

Over mountainous land, through scattering timber and medium dense undergrowth, descend 480 ft. along a steep NE. slope over ledges to the closing corner.

19.20 Ledge, about 75 ft. high, bears N. 30°W. and S. 30°E.

30.73 Fall 42 links N. 89°48' W. of the original closing corner of Ts. 23 and 24 S., R. 1 W.; hereinafter described.

Continue same line, with continuous measurement, between sections 6 and 36.

31.50 Lost Creek, stream of good water 10 links wide and 4 ins. deep, flows N. 20° W., ascend 25 ft. along a SW. slope.

35.30 Road, bears NW. and SE.

37.23 Proportionate distance: No trace of the original corner being found:

Set an iron post, 3 ft. long and 1 in. in diameter, 24 ins. in the ground to solid rock, and in a mound of stone, at the restored  $\frac{1}{4}$  section corner of section 6, T. 24 S., R. 1 E., with brass cap marked:

$\frac{1}{4}$ S6

1949

Deposit a sandstone rock, 5x4x3 ins., marked with a cross (X) at the base of the post.

Ascend 575 ft. along a SW. slope over ledges.

53.80 Fence, bears E. and W.

64.60 Spur, projects W., descend 125 ft. along a broken NW. slope over ledges.

70.77 Proportionate distance: No trace of the original  $\frac{1}{4}$  section corner of section 36, T. 23 S., R. 1 W.

Set an iron post, 3 ft. long and 1 in. in diameter, 18 ins. in the ground to solid rock, and in a mound of stone, with brass cap marked:

$\frac{1}{4}$ S36

1949

Deposit a limestone rock, 4x3x3 ins., marked with a cross (X) at the base of the post.

Descend 245 ft. along a broken NW. slope over ledges.

74.46 The original corner of townships 23 and 24 south, ranges 1 east and 1 west, and now the corner of townships 23 and 24 south, range 1 east only, marked by a trachyte stone, 18x10x4 ins., firmly set in the

431

Dependent Resurvey of the Salt Lake Meridian in T. 24 S.

Chains

ground, and marked with 6 notches on each of the N., S., E., and W., edges, and from which:

A cross (X) out in a limestone rock showing 3x3x2 ft. above ground, bears  $17\frac{3}{4}$  links N.  $85^{\circ}50'$  E.

At the corner point:

Set an iron post, 3 ft. long and 1 in. in diameter, 24 ins. in the ground to solid rock, and in a mound of stone, with brass cap marked:

T23S	
R1W	R1E
	S31
S36	
	S6
	T24S

1950 from which,

A pinon, 3 ins. in diameter, marked XBT, bears S.  $63^{\circ}23'$  W., 62 links distant.

Deposit the original stone alongside the iron post.

No other suitable tree available for marking.

Land, rough and broken mountain slopes.

Soil, rocky mountain loam.

Timber, juniper, pinon, and mahogany.

Undergrowth, sagebrush, bitter brush, yellow top, and grass.

-----

Dependent Resurvey of the North Boundary of T. 24 S., R. 1 W.

Reestablishment of the Surveys Executed by  
Page and Swan in 1897.

Beginning at the corner of sections 2, 3, 34, and 35 on the north boundary of the township, marked by a trachyte stone, 20x8x6 ins., firmly set in the ground and in a mound of stone, and marked with 2 notches on the east edge, four notches on the west edge, and 6 notches on the north and south edges.

At the same point:

Set an iron post, 3 ft. long and 2 ins. in diameter, 28 ins. in the ground, with brass cap marked:

T23S	R1W
S34	S35
S3	S2
T24S	
1950	

Deposit the original stone alongside the iron post.

Thence:

East, between sections 2 and 35.

Over mountainous land, through scattering timber and a medium dense

Dependent Resurvey of the North Boundary of T. 24 S., R. 1 W.

Chains

undergrowth, ascend along a NW. slope.

10.10 Spur, projects N., descend along a SE. slope.

39.97 The 1/4 section corner of sections 2 and 35, marked by a trachyte stone, 14x7 ins., firmly set in the ground in a fence line bearing W. and S. 85° W., and marked 1/4 on the north face, surrounded by a mound of stone.

At the same point:

Set an iron post, 3 ft. long and 1 in. in diameter, 28 ins. in the ground, with brass cap marked:

S35

1/4 ———

S2

1950

Deposit the original stone alongside the iron post.

Thence:

S. 89°36' E., beginning new measurement, along fence line.

10.60 Road, in draw draining N., ascend along a NW. slope.

22.00 Spur, projects NE., descend along a E. slope.

35.40 Corner of fence bearing W. and S. 33°45' E.

39.93 The corner of sections 1, 2, 35, and 36, marked by a trachyte stone, 23x14x8 ins., firmly set in the ground and in a mound of stone, and marked with 1 notch on the east edge, 5 notches on the west edge, and 6 notches on the north and south edges, and from which:

A juniper, 14 ins. in diameter, marked BTS35, bears N. 22°45' E., 28 links distant.

At the corner point:

Set an iron post, 3 ft. long and 2 ins. in diameter, 26 ins. in the ground, and in a mound of stone, with brass cap marked:

T23S R1W  
S35 S36

S2 S1

1950

Deposit the original stone alongside the iron post.

Land, rolling mountain slopes.

Soil, rocky mountain loam.

Timber, juniper and pinon.

Undergrowth, sagebrush, bitter brush, weeds, and grass.

S. 89°58' E. between sections 1 and 36.

Over mountainous land, through scattering timber and a medium dense

7.3.3

Dependent Resurvey of the North Boundary of T. 24 S., R. 1 W.

Chains

undergrowth, descend 350 ft. along a NE. slope over ledges.

10.10 Draw, drains SE., ascend 105 ft. along a SW. slope over ledges.

16.00 Spur, projects S., descend 160 ft. along a SE. slope over ledges.

31.20 Draw, drains NE., ascend 175 ft. along a NW. slope over ledges.

38.90 Spur, projects NE., old fence line along top, descend 20 ft. along an E. slope.

39.84 The  $\frac{1}{4}$  section corner of sections 1 and 36, marked by a trachyte stone, 20x15x9 ins., firmly set in the ground and in a mound of stone, marked  $\frac{1}{4}$  on the north face:

At the same point:

Set an iron post, 3 ft. long and 1 in. in diameter, 22 ins. in the ground to solid rock, and in a mound of stone, with brass cap marked:

S36

$\frac{1}{4}$  ———

S1

1949

Deposit the original stone alongside the iron post.

Thence:

S. 89°48' E., beginning new measurement.

Descend 250 ft. along a SE. slope over ledges.

9.50 Draw, drains NE., ascend 310 ft. along a N. slope over ledges.

23.40 Spur, projects N., descend 390 ft. along a NE. slope over ledges.

39.82 Intersect the west boundary of section 6 at a point 6.50 chains S. 1°04' E. of the  $\frac{1}{4}$  corner of sec. 6, township 24 south, range 1 east.

At the point of intersection.

Set an iron post, 3 ft. long and 3 ins. in diameter, 26 ins. in the ground to solid rock, and in a mound of stone, at the closing corner of townships 23 and 24 south, range 1 west, with brass cap marked:

T23S T24S

R1W R1E

S36

CC ——— S6

S1

T24S

1950

Deposit a limestone rock, 4x4x3 ins., marked with a cross (X) at the base of the post.

From the corner the original closing corner, marked by a trachyte stone, 15x10x7, ins., firmly set in the ground and in a mound of stone, and marked with 6 grooves on the north, east, and west sides and the letters "CC" on the east face,

454

Dependent Resurvey of the North Boundary of T. 24 S., R. 1 W.

Chains

bears S. 89°48' E., 42 links distant. I add the letters AM to the markings on the stone.

Land, rough and broken mountain slopes.  
Soil, rocky mountain loam.  
Timber, juniper, pinon, and mountain mahogany.  
Undergrowth, sagebrush, bitter brush, yellow top, weeds and grass.

Dependent Resurvey of the Subdivision of Township 24 South, Range 1 West.

Reestablishment of the Surveys Executed by J. G. Burrill in 1874 and Page and Swan in 1897.

Beginning at the corner of sections 13, 18, 19, and 24 on the east boundary of the township:

Thence:


S. 88°18' W. between sections 13 and 24.

Over rolling mountain top, through widely scattered timber and a medium dense undergrowth, ascend 75 ft. along a NE. slope.

30.00 Road, bears N. 89° W. and S. 89° E.

39.92 Proportional distance: No trace of the original corner being found:

Set an iron post, 3 ft. long and 1 in. in diameter, 26 ins. in the ground, and in a mound of stone, at the restored  $\frac{1}{4}$  section corner of sections 13 and 24 with brass cap marked:




Deposit broken glass at the base of the post.

79.84 The corner of sections 13, 14, 23, and 24, marked by a granite stone, 15x9x7 ins., firmly set in the ground and marked with 1 notch on the east edge, and 3 notches on the south edge.

At the same point:

Set an iron post, 3 ft. long and 2 ins. in diameter, 20 ins. in the ground to solid rock, and in a mound of stone, with brass cap marked:



Deposit the original stone alongside the iron post.

Land, low rolling hills.  
Soil, rocky mountain loam.  
Timber, juniper and pinon.  
Undergrowth, sagebrush, weeds, and grass.

Dependent Resurvey of the Subdivision of T. 24 S., R. 1 W.

Chains

N. 0°52' W. between sections 13 and 14.

Over rolling mountain top, through widely scattered timber and a medium dense undergrowth, descend 75 ft. over a N. slope.

3.40 Draw, drains E., ascend 125 ft. along a SW. slope to spur.


3.60 Road, bears E. and W.

21.10 Spur, projects E., descend along a NE. slope.

40.04 The  $\frac{1}{4}$  section corner of sections 13 and 14, marked by a granite stone, 11x9x6 ins., firmly set in the ground and in a mound of stone, and marked  $\frac{1}{4}$ , on the west face:

At the same point:

Set an iron post, 3 ft. long and 1 in. in diameter, 17 ins. in the ground to solid rock, and in a mound of stone, with brass cap marked:



1949

Deposit the original stone alongside the iron post.

Thence:

N. 1°05' W., beginning new measurement.


23.10 Road, bears NW. and SE.

40.05 In broad open valley draining N. 20° E.

The corner of sections 11, 12, 13, and 14, marked by a granite stone, 15x9x7 ins., firmly set in the ground and marked with 4 notches on the south edge and 1 notch on the east edge, not witnessed:

At the same point:

Set an iron post, 3 ft. long and 2 ins. in diameter, 24 ins. in the ground, and in a mound of stone, with brass cap marked:



1949

Deposit the original stone alongside the iron post.

Land, rolling mountain top.

Soil, gravelly mountain loam.

Timber, juniper and pinon.


Undergrowth, sagebrush, bitter brush, weeds, and grass..

Chains	Description
	Beginning at the corner of sections 7, 12, 13, and 18 on the east boundary of the township: S. 86°52' W. between sections 12 and 13.
	Over mountainous land, through scattering timber and a medium dense undergrowth, ascend along a SE. slope.
4.00	Low spur, projects N. 30° E., descend along a NW. slope.
10.40	Draw, drains N., ascend along a NE. slope.
42.10	The $\frac{1}{4}$ section corner of sections 12 and 13, marked by a trachyte stone, 14x12x6 ins., firmly set in the ground, and in a mound of stone, and marked $\frac{1}{4}$ on the north face:  At the same point:  Set an iron post, 3 ft. long and 1 in. in diameter, 18 ins. in the ground to solid rock, and in a mound of stone, with brass cap marked:  <div style="text-align: center;"> <p>S12</p> <p>—</p> <p>S13</p> <p>1949</p> </div> <p>Deposit the original stone alongside the iron post.</p> <p>-----</p>
	Thence: S. 88°32' W., beginning new measurement.
8.00	Low spur, projects N. 30° E., descend along a NW. slope.
39.09	The corner of sections 11, 12, 13, and 14.  Land, rolling mountain top. Soil, gravelly to rocky mountain loam. Timber, juniper and pinon. Undergrowth, sagebrush, weeds, and grass.
	N. 0°22' E. between sections 11 and 12.  Over rolling mountains, through scattering timber and a medium dense undergrowth, ascend along a SE. slope.
.90	Old road, bears NE. and SW.
21.00	Spur, projects NE., descend over a N. slope.
26.60	Road, bears E. and W.
27.50	Reservoir bears W. about 1 chain distant.
33.90	Draw, drains NE., ascend along a SE. slope.
39.81	The $\frac{1}{4}$ section corner of sections 11 and 12, marked by a granite stone, 15x8x8 ins., firmly set in the ground and in a mound of stone, and marked $\frac{1}{4}$ on the west face:  At the same point:

## Dependent Resurvey of the Subdivision of T. 24 S., R. 1 W.

Chains

Set an iron post, 3 ft. long and 1 in. in diameter, 26 ins. in the ground to solid rock, and in a mound of stone, with brass cap marked:



Deposit the original stone alongside the iron post.

From the  $\frac{1}{4}$  section corner a small frame house bears 11.69 chains N. 86°33' W.

Thence:

N. 0°20' E., beginning new measurement.


3.50 Spur, projects NE. descend.

23.80 Draw, drains NE., ascend along a SE. slope.

39.67 The corner of sections 1, 2, 11, and 12, marked by a sandstone rock 14x8x8 ins., firmly set in the ground and marked with 5 notches on the south edge and 1 notch on the east edge:

At the same point:

Set an iron post, 3 ft. long and 2 ins. in diameter, 10 ins. in the ground to solid rock, and in a mound of stone, with brass cap marked:



Deposit the original stone alongside the iron post.

From the corner, a gray sandstone, 22x17x11 ins., firmly set in the ground and in a mound of stone, and marked with 5 notches on the south edge and 1 notch on the east edge, bears 1.63 chains S. 32°42' E. I destroy this monument, and deposit the marked stone in the mound at the section corner.

Land, rolling mountain top.

Soil, gravelly mountain loam.

Timber, juniper and pinon.

Undergrowth, sagebrush, bitter brush, weeds, and grass.

Beginning at the corner of sections 1, 6, 7, and 12 on the east boundary of the township;

Thence:

S. 87°10' W. between sections 1 and 12.

Over mountainous land, through scattering timber and a medium dense undergrowth; ascend 135 ft. along a NE. slope.

9.60 Spur, projects N. 10° W., descend along a NW. slope.

## Dependent Resurvey of the Subdivision of T. 24 S., R. 1 W.

## Chains

- 33.20 Draw, drains N., ascend along a NE. slope.
- 40.71 Proportionate distance: No trace of the original corner being found.  
Set an iron post, 3 ft. long and 1 in. in diameter, 14 ins. in the ground to solid rock, and in a mound of stone, with brass cap marked:
- S1
- 1/4 —————
- S12  
1949
- Deposit a trachyte stone 5x5x3 ins., marked with a cross (X) at the base of the post.
- Corner on a spur projecting N.
- 45.40 Small draw drains N., ascend along a NE. slope.
- 50.00 Small spur, projects N., descend along a NW. slope.
- 60.50 Draw, drains NE., ascend along a SE. slope.
- 81.42 The corner of sections 1, 2, 11, and 12.
- Land, broken mountain slopes.  
Soil, rocky mountain loam.  
Timber, juniper and pinon.  
Undergrowth, sagebrush, weeds, and grass.
- 
- N. 1°49' E. between sections 1 and 2.
- Over mountainous land, through scattering timber and a medium dense undergrowth, ascend along a SE. slope.
- 3.50 Spur, projects NE., descend along a NW. slope.
- 8.50 Draw, drains N. 60 E.
- 28.45 Fence, bears S. 33°45' E. and N. 33°45' W.
- 34.85 The corner of sections 1, 2, 35 and 36.
- Land, broken mountain slopes.  
Soil, gravelly to rocky mountain loam.  
Timber, juniper and pinon.  
Undergrowth, sagebrush, black brush, weeds, and grass.
- 

General Description

The three sections resurveyed are located along the rolling top between the main fork of the Sevier River and Lost Creek. The drainage is northeastward into Lost Creek. The timber is mainly juniper and pinon, of value for firewood and posts only. The undergrowth is principally sagebrush, bitterbrush, weeds and grass. The soil is a gravelly to rocky mountain loam. The area is suitable for grazing only, and there are no settlers living on the land.

No indications of commercial deposits of mineral were noted.



CERTIFICATE OF CADASTRAL ENGINEER

65-1

I, Robert C. Yundt, Cadastral Engineer, HEREBY CERTIFY upon honor that, pursuance of special instructions bearing date of the 18th day of July, 1949,

I have dependently resurveyed the northern three miles of the Salt Lake Meridian in Township 24 South, / the north boundary of sections 1 and 2, and the boundaries of Sections 1, 12, and 13 in Township 24 South, Range 1 West

of the Salt Lake Meridian, in the State of Utah, which is represented in the foregoing field notes as having been executed by me and under my direction; and the said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Salt Lake City, Utah, April 8, 1951

Robert C. Yundt
Robert C. Yundt
Cadastral Engineer

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,

Washington, D. C., SEP 22 1952, 19

The foregoing field notes of the dependent resurvey of the northern three miles of the Salt Lake Meridian in Township 24 South, and the boundaries of sections 1, 12, and 13 in Township 24 South, Range 1 West of the Salt Lake Meridian, Utah

executed by Robert C. Yundt, Cadastral Engineer

having been critically examined and found correct, are hereby approved.

Donald B. Clements
Acting Chief, Division of Cadastral Engineering.

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

Chief, Division of Cadastral Engineering.

"BOOK F"

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GENERAL LAND OFFICE

FIELD NOTES

DEPENDENT RESURVEY OF WEST BOUNDARY, AND PORTIONS OF THE

SUBDIVISION : ESTABLISHMENT OF QUARTER SECTION CORNERS ON THE

NORTH BOUNDARY, AND EXTENSION SURVEY COMPLETING THE

SUBDIVISION OF TOWNSHIP 27 SOUTH, RANGE 13 WEST

Of the Salt Lake Meridian,

in the State of Utah

EXECUTED BY

Andrew Nelson, Surveyor

and supplemental special instructions dated September 26, 1938,  
Under special instructions dated July 29, 1936, which provided

for the surveys included under Group No. 271, bearing the approval of the  
Commissioner of the General Land Office under date of August 6, 1936, and  
November 1, 1938

supplemental and October 25, 1939  
and assignment instructions dated October 27, 1938

Survey commenced October 28, 1938

Survey completed December 7, 1939

# INDEX DIAGRAM.

Township 27 South, Range 13 West

	78	77	77	76	76	75
6	6 35	5 74	4 72	3 54	2 40	1
	35	34	71	70	53	39
5	7 33	8 23	9 69	10 52	11 37	12
	33	32	68	67	50	16
5	18 31	17 21	16 66	15 48	14 19	13
	30	30	65	63	47	13
4	19 29	20 20	21 62	22 46	23 12	24
	29	27	61	60	45	11
3	28 26	29 18	28 59	27 44	26 10	25
	26	25	58	57	43	9
2	31 21	32 17	33 56	34 42	35 7	36

## T. 27 S., R. 13 W.

The official survey of parts of the east, south and west boundaries and subdivisional lines is shown on the township plat approved November 26, 1878. The following notes are those of a dependent restoration of the west boundary and subdivisional lines previously surveyed, and an original survey of the remaining subdivision, completing the survey of the township. The resurvey is a restoration of the original lines in their true original positions according to the identified evidence. Before reconstructing or restoring a corner, the lines of the original survey were retraced, and a search made for evidence of the original corner monuments and other calls of the field notes. After completing the necessary retracements, the rules of proportionate measurement were applied to ascertain the position of each lost corner, and when duly identified or restored the corner positions were properly remonumented.

The retracement data were submitted to the office for examination and verification, and in order to simplify the record, only the true line notes, referring to the completed survey, are supplied here.

The survey was commenced October 28, 1938, and was executed with Buff and Buff solar transit number 16726, the property of the General Land Office. The horizontal plate of the instrument is provided with two double verniers, graduated to single minutes of arc, and has a full vertical circle provided with one double vernier, also graduated to single minutes of arc. The solar attachment of the instrument was not used on the survey, and no description of it will be given here. The instrument was in good adjustment, and was approved for use on this assignment by the district cadastral engineer for Utah in assignment instructions dated October 27, 1938, conditional upon satisfactory field tests. These tests were made in the field, prior to the commencement of the field work, and the instrument was found to be free from appreciable error.

The geographic position of the southeast corner of the township, determined from values given in the special instructions, is as follows: latitude,  $38^{\circ}25'N.$ , longitude,  $113^{\circ}15'W.$  The value for latitude was checked by observations made on line during the progress of the survey.

The measurements were made with a Lallie steel ribbon tape, 8 chains in length. The tape is graduated every link for the first chain and thereafter at intervals of ten links. The tape was tested by comparison with a Lufkin standard tape, one chain in length, and found to be correct. The measurements were made on the slope, the vertical angle of each interval determined by the use of clinometers, and the slope distances properly reduced to true horizontal equivalents, which appear in these notes.

All azimuth determinations were made by reference to the true meridians established on line during the progress of the field work. The lines were carried forward as transit lines, taking the mean of direct and reversed sights at each transit point.

November 11, 1939. At the corner of townships 27 and 28 south, ranges 13 and 14 west, in approximate latitude  $38^{\circ}25'N.$ , longitude,  $113^{\circ}21'W.$ , at a mean time, 5h 28m 14s p.m., by my watch, which is 10s slow of 105th meridian standard time, determined by comparison with radio time signals from radio station K S L on this day, I observe Polaris, east of the meridian, making four settings, two each with the telescope in direct and reversed positions, recording the time of each setting and the horizontal angle eastward from the star to a window in a rock ledge about eight miles to the northeast.

Azimuth of Polaris at the time of observation,  $N.1^{\circ}17.5'E.$   
 Horizontal angle from star to foresight, - -  $20^{\circ}55.8'$   
 True bearing of reference point, - - - - -  $N.22^{\circ}13.3'E.$

## DEPENDENT RESURVEY OF WEST BOUNDARY OF T. 27 S., R. 13 W.

Chains

Dependent Resurvey of West Boundary of T. 27 S.,  
R. 13 W. Reestablishment of the Survey ex-  
ecuted by Newel E. Britt, Deputy Surveyor  
in 1878.

The corner of townships 27 and 28 south, ranges 13 and 14  
west is marked by an iron post, 3 ins. diameter, firmly  
set, properly marked and witnessed, as described in the  
official record, and from which

The highest point on Frisco Peak bears N.28°29'E.  
Head frame of King David mine shaft bears N.55°24'E.  
Summit of Grampian Hill bears N.60°49'E.  
Farm buildings at Wah Wah Springs bear N.53°30'W.  
Antelope Peak bears S.22°20'E.  
Center one of five charcoal kilns bears S.82°28'W.  
Notch Peak bears N.2°19'W.

Thence, from the corner

N.0°11'E., on dependent resurvey, between sections 31  
and 36.

Over nearly level valley land sloping to the west,  
through a medium dense undergrowth; descend 50 ft. along  
a general NW. slope to the  $\frac{1}{4}$  section corner.

30.80 Swale, drains W.

40.15 The original  $\frac{1}{4}$  section corner, a volcanic stone, 12x12x12  
ins., lying on the ground, and marked  $\frac{1}{4}$  on one face.

At the corner point.

Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in  
the ground, for the  $\frac{1}{4}$  section corner, with brass cap  
marked

$\frac{1}{4}$   
S36|S31  
1939

Deposit the original corner stone and broken glass at  
the base of the post, and raise a small mound of stone  
around the post.

Thence

N.0°07'E., with continuous measurement.

Descend 50 ft. along a gentle NW. slope to the section  
corner.

57.20 Wash, 10 links wide, and 2 ft. deep, drains NW.

80.28 The original corner of sections 25, 30, 31, and 36,  
marked by a volcanic stone, 16x10x8 ins., firmly set  
in the ground and marked with 1 notch on the south and  
5 notches on the north edges.

At the corner point.

Set an iron post, 3 ft. long, 2 ins. diameter, 27 ins. in  
the ground, for the corner of sections 25, 30, 31, and 36,  
with brass cap marked

1939  
Resurveyed by

## DEPENDENT RESURVEY OF WEST BOUNDARY OF T. 27 S., R. 13 W.

## Chains

T27S	
R14W	R13W
S25	S30
S36	S31
1939	

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the post, and deposit broken glass and the original corner stone at the base of the post.

Land, nearly level desert, sloping to the west.  
Soil, coarse gravelly clay of granite formation; 3rd rate.  
Timber, none.  
Undergrowth, shadscale, match brush and bunch grass.  
Grazing, fair.

N.0°08'E., on dependent resurvey, between sections 25 and 30.

Over nearly level land, through scant undergrowth, descend 25 ft. along a gentle NW. slope to the  $\frac{1}{4}$  section corner.

23.20 Swale, drains N.70°W.

40.16 The original  $\frac{1}{4}$  section corner, a granite stone, 10x8x4 ins., firmly set in the ground, and marked  $\frac{1}{4}$  on west face.

At the corner point.

Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in the ground, for the  $\frac{1}{4}$  section corner, with brass cap marked

T27S	
S25	S30
1939	

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the post, and deposit broken glass and the original corner stone at the base of the post.

Thence

N.0°08'E., with continuous measurement.

Descend 25 ft. to the section corner.

80.28 The original corner of sections 19, 24, 25, and 30, marked by a volcanic stone, 14x12x8, firmly set in the ground, and marked with 2 notches on the south, and 4 notches on north edges, not witnessed.

At the corner point.

Set an iron post, 3 ft. long, 2 ins. diameter, 27 ins. in the ground, for the corner of sections 19, 24, 25, and 30, with brass cap marked

T27S	
R14W	R13W
S24	S19
S25	S30
1939	

Raise a mound of stone, 3 ft. base, 3 ft. high, west of the post, and deposit broken glass and the original corner stone at the base of the post.

DEPENDENT RESURVEY OF WEST BOUNDARY OF T. 27 S., R. 13 W.

Chains

Land, nearly level desert, sloping to the west.  
Soil, coarse gravelly clay; 3rd rate.  
Timber, none.  
Undergrowth, shadscale, match brush and grass.  
Fair grazing.

N.0°06'E., on dependent resurvey, between sections 19 and 24.

Over nearly level land, through scant undergrowth; descend 35 ft. along a gentle NW. slope.

40.12

The original  $\frac{1}{4}$  section corner, marked by a limestone rock, 11x10x5 ins., firmly set in the ground, and marked  $\frac{1}{4}$  on west face, not witnessed.

At the corner point.

Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in the ground, for the  $\frac{1}{4}$  section corner, with brass cap marked

$\frac{1}{4}$   
S24 | S19  
1939

Raise a mound of stone, 3 ft. base, 2 ft. high, west of post, and deposit broken glass and the original corner stone at the base of the post.

Thence

N.0°09'E., with continuous measurement.

Descend 25 ft. along gentle NW. slope to the section corner.

15.80

Wash, 10 links wide, 1 ft. deep, drains N.80°W.

34.75

Telephone line, bears N.70°37'W. and S.70°37'E.

35.80

Utah Highway No. 21, improved gravel road, bears N.70°37'W., and S.70°37'E., Ely, Nevada, to Milford, Utah.

80.24

The original corner of sections 13, 18, 19, and 24, marked by a limestone rock, 12x10x6 ins., firmly set in the ground and marked with 3 notches on N. and S. edges, not witnessed.

At the corner point.

Set an iron post, 3 ft. long, 2 ins. diameter, 27 ins. in the ground, for corner of sections 13, 18, 19, and 24, with brass cap marked

T27S  
R14W | R13W  
S13 | S18  
S24 | S19  
1939

Raise a mound of stone, 3 ft. base, 2 ft. high, west of post, and deposit broken glass and the original corner stone at the base of the post.

Land, nearly level desert, sloping to the west.  
Soil, coarse gravelly loam; 2nd rate.  
Timber, none.

## DEPENDENT RESURVEY OF WEST BOUNDARY OF T. 27 S., R. 13 W.

## Chains

Undergrowth, shadscale, match brush and grass.  
Fair grazing.

N.0°07'E., on dependent resurvey, between sections 13 and 18.

Over nearly level land, sloping W., descend 30 ft. along a NW. slope.

32.00 Enter flood plain area from Frisco Wash, bears NW and SE.; drains NW.

40.14 The original  $\frac{1}{2}$  section corner, marked by a volcanic stone, 9x8x6 ins., firmly set in the ground, and marked  $\frac{1}{2}$  on west face, not witnessed.

At the corner point.

Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in the ground, for the  $\frac{1}{2}$  section corner, with brass cap marked.

S13 | S18  
1939

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the post and deposit the original corner stone and broken glass at the base of the post.

Thence

N.0°07'E., with continuous measurement.

Descend along a general NW. slope.

52.80 Old road, bears NE. and SW.

80.27 Proportionate distance; no trace of the original corner can be found.

Set an iron post, 3 ft. long, 2 ins. diameter, 27 ins. in the ground, for the restored corner of sections 7, 12, 13, and 18, with brass cap marked

T27S  
R14W | R13W  
S12 | S7  
-----  
S13 | S18  
1939

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the post, and deposit broken glass at the base of the post.

Land, nearly level desert; W. exposure and drainage.

Soil, coarse gravelly clay; 2nd rate.

Timber, none.

Undergrowth, shadscale, match brush and grass.

Fair grazing.

N.0°07'E., on dependent resurvey, between section 7 and 18

Over nearly level land, through scant undergrowth, along a gentle NW. slope in the flood plain of Frisco Wash, draining NW.

## DEPENDENT RESURVEY OF WEST BOUNDARY OF T. 27 S., R. 13 W.

## Chains

7.90 Leave flood plain, edge bears NW. and SE.; continue along a gentle NW. slope.

40.13 The original  $\frac{1}{2}$  section corner, marked by a volcanic stone, 14x9x7 ins., firmly set in the ground, and marked  $\frac{1}{2}$  on W. face, not witnessed.

At the corner point.

Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in the ground, for the  $\frac{1}{2}$  section corner, with brass cap marked

$\frac{1}{2}$   
S12 | S7  
1939

Deposit the original corner stone and broken glass alongside the iron post, and raise a mound of stone, 3 ft. base 2 ft. high, west of the post.

Thence

N.0°07'E., with continuous measurement.

Descend along a gentle W. slope to the section corner.

70.70 Old pipeline, from Wah Wah Springs to Newhouse, Utah, bears N.88°45'W. and S.88°45'E.

80.25 Proportionate distance; no trace of the original corner can be found.

Set an iron post, 3 ft. long, 2 ins. diameter, 27 ins. in the ground, for the restored corner of sections 1, 6, 7, and 12, with brass cap marked

T27S  
R14W | R13W  
S1 | S6  
-----  
S12 | S7  
1939

Deposit broken glass at the base of post, and raise a mound of stone, 3 ft. base, 2ft. high, west of the post.

Land, gently sloping desert; drainage NW.

Soil, coarse gravelly clay; 3rd rate.

Timber, none.

Undergrowth, shedscale, match brush and grass.

Fair grazing.

N.0°07'E., on dependent resurvey, between sections 1 and 6.

Over nearly level land, through scant undergrowth, descend along a gentle W. slope.

11.70 Old fence line, (no wires remaining), bears NW. and SE., about 2 chains, thence N. for a short distance.

40.12 The original  $\frac{1}{2}$  section corner, marked by a granite stone, 12x8x6 ins., firmly set in the ground, and marked  $\frac{1}{2}$  on W. face, not witnessed.

At the corner point.

## DEPENDENT RESURVEY OF WEST BOUNDARY OF T. 27 S., R. 13 W.

## Chains

Set an iron post, 3 ft. long, 1 ins. diameter, 27 ins. in the ground, for  $\frac{1}{4}$  section corner, with brass cap marked

$\frac{1}{4}$   
 S1|S6  
 1939

Deposit broken glass and original corner stone alongside the iron post, and raise a mound of stone, 3 ft. base, 2 ft. high, to the west of the post.

Thence

N.0°12'E., with continuous measurement.

Descend along a gentle NW. slope.

- 74.39 The closing corner of townships 26 and 27 south, range 13 west, marked by an iron post, 3 ins. diameter, firmly set, properly marked and witnessed, as described in the official record.

Continue on same line, with continuous measurement.

- 80.23 The corner of townships 26 and 27 south, range 14 west, marked by an iron post, 3 ins. diameter, firmly set, properly marked and witnessed, as described in the official record, and from which

The highest point on Frisco Peak bears N.69°15'E.

Antelope Peak bears S.10°06'E.

Farm buildings at Wah Wah Springs bears S.85°00'W.

Land, nearly level desert, sloping to the west.

Soil, coarse sandy clay; 2nd rate.

Timber, none.

Undergrowth, shadscale, match brush and grass.

Fair grazing.

## DEPENDENT RESURVEY OF SUBDIVISION, T. 27 S., R. 13 W.

Dependent resurvey reestablishing the survey executed by Newell E. Britt, Deputy Surveyor, in 1878.

Beginning at the corner of sections 35 and 36, on the south boundary of the township, an iron post, 2 ins. diameter, firmly set, properly marked and witnessed, as described in the official record.

Thence

N.0°32'E., on dependent resurvey, between sections 35 and 36.

Over rolling, hilly land, through scattering timber and a medium dense undergrowth; descend along a NE. slope.

- .70 Small draw, drains SE.; ascend 165 ft. along a SW. slope.
- 7.90 Spur, projects S.80°E.; descend 190 ft. along a N. slope.
- 16.50 Draw, drains E. about 8 chains, thence SE.; ascend 185 ft. along a SE. slope.
- 35.70 Low spur, projects S.80°E.; descend 70 ft. along a north slope.

DEPARTMENT AGENCY OF SURVEYING, T. 22 S., R. 13 W.

Chains

- 38.40 Draw, drains S.80°E., heading about 10 chains westerly; ascend 70 ft. along a S. slope.
- 40.00 Record distance. No trace of original corner can be found.
- Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in the ground, for the restored  $\frac{1}{2}$  section corner, with brass cap marked
- $\frac{1}{2}$   
 335 | 336  
 1936
- Raise a mound of stone, 3 ft. base, 2 ft. high, west of the post. No suitable trees available for marking.
- Continue on same line, with continuous measurements..
- Ascend along a SE. slope.
- 45.40 Branch spur, projects SE.; continue ascent along a SE. slope.
- 50.90 Spur, 145 ft. above  $\frac{1}{2}$  section corner, projects E. about 10 chains and then SE.; descend 50 ft. along a NE. slope.
- 53.70 Head of draw, draining S.80°E.; ascend 10 ft. along a gradual SE. slope.
- 56.60 High ridge, bears N.60°E. and S.60°W.; descend along a NE. slope.
- 63.10 Head of draw, draining NE.; continue descent along a NE. slope.
- 77.10 Across draw, drains NW., 420 ft. below ridge, ascend 10 ft. along a SE. slope.
- 78.45 Spur, projects N. 10° E.; descend 35 ft. along E. slope near 10, of spur.
- FROM S. and E.
- 80.00 Record distance. No trace of the original corner can be found.

In the head of small draw, draining N.5°E.

Set an iron post, 3 ft. long, 2 ins. in diameter, 27 ins. in the ground, for the restored corner of sections 25, 26, 35, and 36, with brass cap marked,

T275 | R13W  
 525 | 525  
 ---  
 335 | 336  
 1936

From which

A juniper, 10 ins. diameter, marked T275R13W525525, bears NE4°00'E., 72 links distant.

No other suitable tree available for marking.

Land, rolling hills; SE. and N. exposures and drainage.  
 Soil, gravelly to rocky loam; 4th rate.  
 Timber, juniper and piñon.  
 Undergrowth, sagebrush, yellow top and grass.  
 Fair grazing.

DEPENDENT RESURVEY OF SUBDIVISION, T. 27 S., R. 13 W.

Chains

Beginning at the corner of sections 25 and 36 on the east boundary of the township, an iron post, 2 ins. diameter, firmly set, properly marked and witnessed, as described in the official record.

Thence

N.89°20'W., on dependent resurvey, between sections 25 and 36.

Over rolling mountainous land, through few widely scattered trees and medium dense short undergrowth; ascend steep NE. slope 150 ft.

8.30 Spur, slopes S.10°E.; descend steep NW. slope, 160 ft.

18.50 Draw, drains SE.; ascend steep SE. slope, 240 ft.

30.00 High spur, slopes SE.; descend gradual SW. slope, 60 ft. to

40.35 Proportionate distance; no trace of original corner can be found.

Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in the ground, for restored  $\frac{1}{4}$  section corner, with brass cap marked

$\frac{1}{4}$  S 25  
S 36  
1938

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of corner.

Continue descent over SW. slope, 60 ft. to

48.00 Head of shallow draw, drains S.; ascend 20 ft. over SE. slope.

51.00 Main ridge, slopes S.4°W. about 7 chains distant to saddle, thence SW, and rises N.10°E. for about 5 chains, thence northeasterly; descend steep W. slope, 180 ft.

58.60 Main draw, heading SE. about 10 chains, near saddle; drains NW., thence along a general broken N. slope, entering heavier timber; ascend 30 ft.

65.00 Low spur, slopes N.10°W., about 10 chains distant to end; descend 50 ft.

71.40 Head of branch draw, drains N.; ascend 35 ft.

77.30 Low spur, slopes N. about 8 chains distant to end; descend NW. slope.

80.71 The restored corner of sections 25, 26, 35, and 36, 270 ft. below  $\frac{1}{4}$  section corner.

Land, rolling mountainous; general E. to SE. and NW. exposures; drainage SE. and NW.  
Soil, rocky and gravelly, of limestone formation; 3rd rate. Timber, scrub cedar and pinon.  
Undergrowth, short shadscale, yellow top and sage. Grazing, fair.

## DEPENDENT RESURVEY OF SUBDIVISION, T. 27 S., R. 13 W.

Chains	N.0°50'W., dependent resurvey, between sections 25 and 26.
	Over rolling mountainous and hilly land, through scattering timber and short undergrowth; descending over rolling N. slope 160 ft.
19.50	Junction of draws, from S.10°W. and S.10°E., draining NW.; slight ascent over SW. slope 20 ft.
26.00	Low spur, slopes N.30°W.; descend NE. slope 120 ft.
34.50	Shallow main draw, drains NW.; ascend 5 ft. along W. slope.
40.00	Record distance; no trace of the original corner can be found. from S. and E.
	Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in the ground, for restored $\frac{1}{4}$ section corner, with brass cap marked
	$\frac{1}{4}$ S26   S25 1938
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.
40.80	Shallow wash, in swale, 50 links wide, drains W.
45.40	Low spur, 20 ft. above $\frac{1}{4}$ section corner, projects NW. about 8 chains distant to end; descend 50 ft.
49.40	Draw, drains W.; ascend 60 ft.
52.50	Low rise from E., bears W. about 2 chains distant to end; descend N. slope 50 ft.
55.40	Main wash, in wide draw, at base of descent, 1 chain wide, drains S.60°W.
57.00	Utah Highway No. 21, improved gravel road, bears N.60°E. and S.60°W., Ely, Nevada, to Milford, Utah.
58.17	Old railroad grade, bears N.70°E. and S.70°W.
60.40	Low rise, 25 ft. above wash, extends SW. 3 chains distant to end.
62.60	Wash, 1 chain wide, 2 ft. deep, drains SW.; thence gradually ascend S. slope up along small wash.
67.50	Dim old road, bears nearly E. and W.
80.00	Record distance; no trace of original corner can be found, after extended search.
	Set an iron post, 3 ft. long, 2 ins. diameter, 27 ins. in the ground, for restored corner of sections 23, 24, 25, and 26, with brass cap marked
	T27S R13W S23   S24 S26   S25 1938
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.

## DEPENDENT RESURVEY OF SUBDIVISION, T. 27 S., R. 13 W.

## Chains

Corner stands on W. edge of shallow wash, draining southerly, 90 ft. above main wash.

From corner N. 38° 54' W., 7.08 chains distant, to Corner No. 1, Survey 6356, Gulch lode.

Land, rolling mountainous and hilly; NW. and S. exposures; drainage SW.

Soil, rocky and gravelly; 3rd rate; limestone formation. Timber, scattering scrub cedar and pinon.

Undergrowth, short scattered shadscale, yellow top and sage.

Grazing, fair.

From the corner of sections 24 and 25 on E. boundary of township, an iron post, 2 ins. diameter, firmly set, properly marked and witnessed as described in the official record.

Thence

S. 87° 56' W., on dependent resurvey, between sections 24 and 25.

Over hilly land, through scattered timber and short undergrowth; descend SW. slope 65 ft.

- 6.50 Draw, drains S.; ascend SE. slope 75 ft.
- 15.30 Ridge, bears NE. and SW.; descend steep W. slope 140 ft.
- 23.00 Draw, drains SW.; thence over S. to SE. slope.
- 35.00 Low spur, slopes SW.; descend NW. slope 50 ft.
- 40.85 Intersect the original  $\frac{1}{4}$  section corner, marked by a granite stone, 14x8x5 ins., lying in an old mound of stone, plainly marked  $\frac{1}{4}$  on one face.

At corner point.

Set an iron post, 3 ft. long, 1 in. diameter, 25 ins. in the ground to rock and supported in mound of stone to top, for  $\frac{1}{4}$  section corner, with brass cap marked

$$\frac{1}{4} \frac{S \ 24}{S \ 25}$$

1938

Deposit original stone corner at base of post, and raise a mound of stone, 3 ft. base, 2 ft. high, N. of corner.

Thence

N. 86° 11' W., with continuous measurement.

- 41.00 Old dim road, bears nearly N. and S.
- 46.50 Draw, 50 ft. below  $\frac{1}{4}$  section corner, drains NW.; continue descent over general W. slope.
- 54.10 Telephone line, bears N. 43 $\frac{1}{2}$ ° E. and S. 43 $\frac{1}{2}$ ° W.
- 58.30 Main wash, at base of descent, 1 chain wide, 2 ft. deep, 100 ft. below  $\frac{1}{4}$  section corner, drains SW.; gradually ascend 30 ft. over rolling land, facing S. to section corner.

## DEPENDENT RESURVEY OF SUBDIVISIONS, T. 37 S., R. 13 W.

## Chains

- 60.00 Utah Highway No. 21, improved gravel road, bears NE. and SW., Ely, Nevada, to Milford, Utah.
- 68.597 Intersect line 1-4, Survey No. 6202, Castle Rock lode, at N.5°43'E. 0.747chains from Corner No. 1.
- 68.70 Wash, 1 chain wide, 3 ft. deep, drains S.
- 69.846 Intersect line 1-2, Survey No. 6202, Castle Rock lode, at N.52°30'W. 4.351chains from Corner No. 1.
- 71.70 Old unimproved road, bears N. and S.
- 72.90 Wash, 1 chain wide, 2 ft. deep, drains S.
- 78.50 Old unimproved road, bears N.10°W. and S.10°E.
- 81.00 Wash, 30 links wide, 3 ft. deep, drains S.
- 81.34 Intersect the restored corner of sections 23, 24, 25, and 26.

Land, rolling hills; SE. exposure and drainage on E. portion, and to SW. on W. portion.  
Soil, rocky and gravelly; 3rd rate.  
Timber, scattering scrub cedar and pinon.  
Undergrowth, sage, shadscale and yellow top.  
Grazing, poor to fair.

N.0°24'E., on dependent resurvey, between sections 23 and 24.

Over rolling land, facing easterly, through few scattered trees and short undergrowth; gradually ascend along small wash.

- 3.50 Leave wash from N.30°W., drains southerly; ascend along a gradual easterly slope.
- 5.15 Intersect line 2-1, Survey No. 6356, Gallego lode, at N.85°19'W. 4.23 chains distant, from Corner No. 2, a pine post, 4 ins. square, firmly set, scribed 2-6356.
- 9.70 Old unimproved road, bears N.20°W. and S.20°E.
- 10.25 Old dilapidated frame building, 12x18 ft. on line.
- 31.80 Wash, 20 links wide, 2 ft. deep, drains SE.
- 35.30 Power line, 3 wires, bears southeasterly and NW. for about 1½ chains distant, thence SW.
- 40.00 Record distance; no trace of the original corner can be found.

Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in the ground, for restored ¼ section corner, with brass cap marked

S23/S24

1938

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner, and deposit glass at base of the post.

## DEPENDENT RESURVEY OF SUBDIVISION, T. 27 S., R. 13 W.

Chains

Corner stands on a gradual E. slope, 175 ft. above section corner.

From  $\frac{1}{4}$  section corner, S.87°14'E. 27.12 chains distant to U. S. M. M. No. 2, which I find to be a sharp point on top a limestone pinnacle on S. face of which is chiseled USM2; no post or mound of stone which record describes as marking this monument could be found.

N.61°00'E., 13.48 chains distant to SW. corner of cemetery, west side of which bears N.16°W. 4.33 chains distant, and south side bears N.87 $\frac{1}{2}$ °E. 4.63 chains dist.

45.80 Telephone line, 2 wires, bears NW. and SE.

46.70 Road, bears, N.70°W. to Horn Silver mine, and S.70°E. to Utah Highway No. 21.

49.13 Intersect line 4-5, Survey No. 9056, Switch lode, at N.85°19'W. 1.98 chains distant from corner No. 4, a pine post, 4 ins. square, firmly set and properly marked.

58.50 Wash, 1 chain wide, 4 ft. deep, drains SE.

60.60 Railroad bears easterly, and southwesterly; E. end of bridge bears SW. about 40 links distant.

68.30 Wash, 1 chain wide, 4 ft. deep, drains S.20°E.

77.90 Telephone line, bears N.30°20'E. and S.30°20'W. from S. and E.

80.00 Record distance; no trace of original section corner.

Set an iron post, 3 ft. long, 2 ins. diameter, 27 ins. in the ground, for restored corner of sections 13, 14, 23, and 24, with brass cap marked

T27S R13W

S14 S13

S23 S24

1939

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.

Corner stands on a gradual W. slope, 190 ft. above  $\frac{1}{4}$  section corner.

From this corner N.47°02'W. 9.91 chains distant to corner No. 1, Lot 73, Dumbarton lode.

Land, rolling, with a general easterly to southeasterly exposure and drainage.

Soil, gravelly clay and stony; 3rd rate.

Timber, widely scattered scrub cedar and pinon.

Undergrowth, scant sage, shadscale and yellow top.

Grazing fair.

From the corner of sections 13 and 24 on E. boundary of township, marked by an iron post, 2 ins. diameter, firmly set and properly marked.

Thence

S.89°42'W., on dependent resurvey between sections 13 and 24.

## DEPENDENT RESURVEY OF SUBDIVISION, T. 27 S., R. 13 W.

## Chains

Over rolling land, facing W., through few scattered trees and short undergrowth; gradually descending rolling west slope.

- 6.70 Wash, 60 links wide, 2 ft. deep, drains SW.
- 11.30 Old dim road, bears NW. and SE.
- 23.80 Utah Highway No. 21, improved gravel road, on curve bearing NE. and SW., Ely, Nevada, to Milford, Utah.
- 25.70 Telephone line, bears S.16°W. and N.16°E. for about 30 links distant, thence N.53°E.
- 27.80 Old road, which formerly was the main street of town of Frisco, bears N.2½°E. and S.2½°W.
- 31.50 Wash, at base of descent, 50 links wide, 2 ft. deep, 50 ft. below section corner, drains SE.; gently ascend rolling land, with southerly exposure.
- 40.91 Intersect the original ¼ section corner, marked by a limestone, 16x14x12, loosely set in the ground, dimly marked ¼ on N. face, and surrounded by a few rock.
- At corner point.
- Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in the ground, for ¼ section corner, with brass cap marked
- $$\frac{1}{4} \begin{array}{c} S'13 \\ S'24 \\ 1938 \end{array}$$
- Raise a mound of stone, 3 ft. base, 2 ft. high, N. of post, and deposit original stone corner and glass at base of post.
- From corner N.14°55'E., 20.68½ chains distant, to Post No. 4, Lot 41, Frisco Mill Site.
- Thence
- N.87°10'W., with continuous measurement.
- 45.35 Old abandoned railroad track, bears N.36°E. and S.36°W.
- 51.80 Wash, 30 links wide, 3 ft. deep, drains S.
- 54.50 Power line, bears N.49°E. and S.49°W.
- 58.30 Old unimproved road, bears N.20°W. and S.
- 65.30 Wash, 50 links wide, 5 ft. deep, drains S.
- 69.30 Wash, 20 links wide, 4 ft. deep, drains S.
- 72.30 Wash, 50 links wide, 10 ft. deep, drains S.20°E.
- 79.50 Low rise, 65 ft. above ¼ section corner, bears N. and S.; descend gradual W. slope.
- 80.12 Telephone line, bears N.30°20'E. and S.30°20'W.
- 81.27 Intersect the restored corner of sections 13, 14, 23, and 24.

## DEPENDENT RESURVEY OF SUBDIVISION, T. 27 S., R. 13 W.

Chains

Land, rolling.  
Soil, gravelly and stony; 2nd rate.  
Timber, few scattered cedar and pinon.  
Undergrowth, short sage, shadscale and yellow top.  
Grazing, fair.

N.0°41'E., on dependent resurvey, between sections 13 and 14.

Over rolling hills, with general southerly exposure, through scattered timber and short undergrowth; gradually ascend.

- 9.50 Ravine, 50 ft. deep, drains SE.  
16.00 Pipe line, covered, bears NE. and SW.  
26.00 Ravine, 20 ft. deep, drains E. about 5 chains, thence SE.  
37.00 High point, on low spur, 185 ft. above section corner, slopes SE.; descend N. slope, 30 ft.  
39.20 On N. slope.

Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in the ground, for witness corner to the restored point for  $\frac{1}{4}$  section corner, with brass cap marked

$\frac{1}{4}$   
 W | C  
 S14 | S13  
 1939

from which

A cedar, 8 ins. diameter, bears N.41 $\frac{1}{2}$ °E., 46 links distant, marked WC  $\frac{1}{4}$  S13 BT

A cedar, 6 ins. diameter, bears S.41 $\frac{1}{2}$ °W., 12 links distant, marked WC  $\frac{1}{4}$  S14 BT

- 40.00 Record distance. no trace of original corner can be found.

Point for corner falls in channel of wash in bottom of draw, draining E., where it would be impracticable to set post; therefore at this point I deposit a granite stone, 22x10x9 ins., marked  $\frac{1}{4}$  on W. face and a cross (X) on top for true corner point,

Note: a draw from the N. enters this draw about 4 chains E. of corner point.

Gradually ascend along W. side of draw, through medium dense timber.

- 55.00 Cross draw, draining S.10°E.; thence along E. side.  
77.50 Recross same draw, drains S.10°W.; ascend S. slope.  
80.01 Record distance; no trace of original section corner can be found.

Set an iron post, 3 ft. long, 2 ins. diameter, 27 ins. in the ground and surrounded in a mound of stone to top, for restored corner of sections 13 and 14, only, with brass cap marked

DEPENDENT RESURVEY OF SUBDIVISION, T. 27 S., R. 13 W.

Chains

distance

S12  


---

S14 S13  
T27S R13W  
1939

from which

A pinon, 5 ins. diameter, bears S.25°45'E., 94 links distant, marked T27S R13W S13 BT

A cedar, 8 ins. diameter, bears S.12½°W., 50 links distant, marked T27S R13W S14 BT

Corner stands on a steep S. slope, 250 ft. above ¼ section corner.

Land, rolling and low hills, general SE. exposure and drainage.

Soil, rocky and gravelly; 3rd rate.

Timber, cedar and pinon.

Undergrowth, sage, yellow top and mountain rush.

Grazing, fair.

From the corner of sections 12 and 13, on E. boundary of township, an iron post, 2 ins. diameter, firmly set and properly marked.

Thence

N.88°38'W., on dependent resurvey, between sections 12 and 13.

Over rolling land, facing southeasterly, through medium dense timber and short scattered undergrowth; gradually ascend 150 ft. to ¼ section corner.

- 3.50 Small draw, near head, 25 ft. deep, drains S.
- 8.50 Small draw, 30 ft. deep, drains SE.
- 16.00 Draw, 30 ft. deep, drains SE.
- 22.50 Dim old road, on top of low spur, projecting S.20°E., bears N.20°W. and S.20°E.
- 25.00 Draw, drains SE.
- 35.00 Dim old wagon road, bears NW. and SE.
- 40.10 Small draw, drains SE.
- 40.33 Proportionate distance; no trace of original corner can be found.

Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in the ground and surrounded by a large mound of stone. to top, for restored ¼ section corner of section 13, only, with brass cap marked

¼ S13  
1939

from which

A cedar, 7 ins. diameter, bears S.42½°W., 21 links distant, marked ¼ S13 BT

## DEPENDENT RESURVEY OF SUBDIVISION, T. 27 S., R. 13 W.

## Chains

A pinon, 8 ins. diameter, bears S.6°W., 49 $\frac{1}{2}$  links distant, marked  $\frac{1}{4}$  S13 BT

Ascend E. slope.

41.53 Easting of 40.00 chains distant, from the corner of sections 11 and 12.

Set an iron post, 3 ft. long, 1 in. diameter, 20 ins. in the ground to rock and supported in a mound of stone to top, for section corner, on S. boundary of section 12, with brass cap marked

$\frac{1}{4}$  S12

1939 . . . . .

from which

A cedar, 5 ins. diameter, bears N.27 $\frac{1}{2}$ °E., 13 links distant, marked  $\frac{1}{4}$  S12 BT

A pinon, 7 ins. diameter, bears N.66 $\frac{1}{2}$ °W., 113 links distant, marked  $\frac{1}{4}$  S12 BT

50.60 Pipe line, covered, bears N.26°10'E. and S.26°10'W.

54.50 Low spur, 100 ft. above  $\frac{1}{4}$  section corner, slopes SE.

60.30 Draw, near head, drains S.

66.50 Head of draw, drains S. for 3 chains, thence SE.

74.00 Spur, 200 ft. above  $\frac{1}{4}$  section corner, projects S.; descend W. slope, 50 ft.

79.00 Draw, near head, drains SW.; ascend 20 ft. along S. slope.

80.66 The restored corner of sections 13 and 14.

Land, rolling and hilly; general SE. to S. exposure and drainage.

Soil, gravelly and stony; 3rd rate.

Timber, medium dense cedar and pinon.

Undergrowth, short sage, yellow top and mountain rush.

Grazing, fair to poor.

From the corner of sections 32 and 33, on S. boundary of township, an iron post, 2 ins. diameter, firmly set and properly marked, as described in the official record.

Thence

N.1°04'E., on dependent resurvey, along E. boundary of section 32,

Over gently rolling valley land, along E. side of Wah Wah Valley, through medium dense short undergrowth; gently descend NW. slope, 85 ft. to  $\frac{1}{4}$  section corner.

4.00 Wash, 60 links wide, 8 ft. deep, drains NW.

39.75 Intersect the original  $\frac{1}{4}$  section corner, a volcanic stone, 12x10x4 ins., plainly marked  $\frac{1}{4}$  on one face, lying on the ground, unwitnessed.

At corner point.

Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in

DEPENDENT RESURVEY OF SUBDIVISION, T. 27 S., R. 13 W.

Chains

the ground, for  $\frac{1}{4}$  section corner, of section 32, only, with brass cap marked

$\frac{1}{4}$   
S32  
1939

Deposit original stone alongside iron post, and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of corner.

Thence

N.0°56'E., with continuous measurement.

45.15 Southing of 40.00 chains from the closing corner of sections 28 and 33.

Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in the ground, for  $\frac{1}{4}$  section corner on W. boundary of section 33, with brass cap marked

$\frac{1}{4}$   
S33  
1939

Deposit glass at base of iron post, and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, E. of corner.

74.00 Old unimproved road, bears NE. and SW.

80.01 Intersect the original corner of sections 28, 29, 32, and 33, a volcanic stone, 16x10x5 ins., marked with 4 notches on E. edge, and 1 groove on S. face, loosely set in ground and in a small mound of stone.

At corner point.

Set an iron post, 3 ft. long, 2 ins. diameter, 27 ins. in the ground, for corner of sections 29 and 32, only, with brass cap marked

T27S R13W  
S29  
-----  
S32  
1939

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of corner, and deposit original stone corner alongside of iron post.

Corner stands on a gradual SW. exposure, 65 ft. below  $\frac{1}{4}$  section corner.

Land, gently rolling desert, with a gentle NW. and W. exposure and drainage.

Soil, coarse gravelly clay loam; 2nd rate.

Timber, none.

Undergrowth, medium dense short sage, shadscale and grass.

Grazing, fair.

N.0°07'E., on dependent resurvey, along E. boundary of section 29.

Over gently rolling desert land; sloping westerly, through short undergrowth; slight ascent to  $\frac{1}{4}$  section corner.

## DEPENDENT RESURVEY OF SUBDIVISION, T. 27 S., R. 13 W.

## Chains

- 0.30 Swale, drains SW.
- 5.14 Point for the closing corner of sections 28 and 33, hereinafter described.
- 10.50 Old unimproved road, formerly known as the Salt Lake-Piccho Road, bears NE. and SW.
- 29.50 Swale, drains SW.
- 40.20 Intersect the original  $\frac{1}{2}$  section corner, a volcanic stone, 16x12x8 ins., marked  $\frac{1}{2}$  on W. face, firmly set in the ground, unwitnessed.

At corner point.

Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in the ground, for  $\frac{1}{2}$  section corner of section 29, only, with brass cap marked

S29

1939

Deposit original stone corner at base of post, and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of corner.

Corner stands on slight W. exposure 50 ft. above section corner.

Thence

N.0°32'W., with continuous measurement.

- 45.12 Midpoint between the closing corners of sections 21 and 28, and sections 28 and 33.

Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in the ground, for  $\frac{1}{2}$  section corner, on W. boundary of section 28, with brass cap marked

S28

1939

Deposit glass at base of post, and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, E. of corner.

Corner stands on top of rise, bearing nearly E. and W.; begin slight descent along gentle W. exposure.

- 62.70 A main wash, 120 links wide, 2 ft. deep, drains NW.
- 67.10 Wash, 50 links wide, 5 ft. deep, drains NW.
- 68.60 Wash, 30 links wide, 4 ft. deep, drains NW.
- 79.49 Intersect original corner of sections 20, 21, 28, and 29; a volcanic stone, 14x12x10 ins., dimly marked, with 2 notches on S. and 4 notches on E. edges, firmly set in a small mound of stone.

At corner point.

Set an iron post, 3 ft. long, 2 ins. diameter, 27 ins. in the ground, for corner of sections 20 and 29, only, with brass cap marked

DEPENDENT RESURVEY OF SUBDIVISION, T. 27 S., R. 13 W.

Chains

T27S	R13W
S20	
S29	S28
1939	

Deposit the original stone corner alongside of iron post, and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of corner.

Land, gently rolling, with general westerly exposure and drainage.  
 Soil, coarse gravelly clay and scattered stones; 3rd rate.  
 Timber, none.  
 Undergrowth, short shadscale, yellow top and grass.  
 Grazing, fair.

N.0°11'W., on dependent resurvey, on E. boundary of section 20.

Over gently rolling valley land, sloping westerly, through short undergrowth.

- 5.61 Point for the closing corner of sections 21 and 28, hereinafter described.
- 10.90 Wash, 40 links wide, 2 ft. deep, drains N.60°W.
- 17.00 Telephone line, bears N.70°34'W. and S.70°34'E.
- 17.60 Utah Highway No. 21, improved gravelled road, bears same as telephone line, Ely, Nevada, to Milford, Utah.
- 25.80 Old Ely road, bears N.64½°W. and S.64½°E.
- 33.60 Wash, 2½ chains wide, 2 ft. deep, drains NW.
- 38.40 Wash, 2 chains wide, 3 ft. deep, drains NW.
- 40.33 Intersect original ¼ section corner, a granite stone, 12x10x8 ins., marked ¼ on W. face, firmly set in ground and surrounded by few stones.  
 At corner point.  
 Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in the ground, for ¼ section corner of section 20, only, with brass cap marked

¼	E
S20	
1939	

Deposit original stone corner at base of post, and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of corner.

Corner stands on gentle W. slope, 50 ft. below section corner.

Thence

N.1°35'E., with continuous measurement.

- 42.30 Wash, 20 links wide, 4 ft. deep, drains N.60°W.

- 45.61 Point midway between the closing corners of sections 16 and 21, and sections 21 and 28.

## DEPENDENT RESURVEY OF SUBDIVISION, T. 27 S., R. 13 W.

## Chains

Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in the ground, for  $\frac{1}{4}$  section corner of W. boundary of section 21, with brass cap marked

$\frac{1}{4}$   
S21

1939

Deposit glass at base of post, and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, E. of corner.

58.90 Wash, from E., 30 links wide, 2 ft. deep, drains S.60°W., 25 ft. below  $\frac{1}{4}$  section corner; begin slight ascent along W. slope.

62.60 Wash, 1 chain wide, 2 ft. deep, drains W.

74.00 Wash, 50 links wide, 1 ft. deep, drains W.

80.61 Intersect original corner of sections 16, 17, 20, and 21, a granite stone, 16x12x5 ins., marked with 3 notches on S. and 4 notches on E. edge, firmly set in ground and surrounded by a scattered mound of stone.

At corner point.

Set an iron post, 3 ft. long, 2 ins. diameter, 27 ins. in the ground, for corner of sections 17 and 20, only, with brass cap marked

T27S R13W  
S17 S21  
S20  
1939

Deposit the original stone corner alongside of iron post, and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of corner.

Land, gently rolling valley or desert, having a gradual westerly slope.

Soil, stony and gravelly clay; 3rd rate; granite formation.

Timber, none.

Undergrowth, medium dense sage, shadscale, yellow top and grass.

Grazing, fair.

N.0°24'E., on dependent resurvey, along E. boundary of section 17.

Over rolling and broken land, facing W. along E. edge of Wah Wah Valley, through dense short undergrowth.

5.01 Point for the closing corner of sections 16 and 21, hereinafter described.

10.50 Wash, 20 links wide, 1 ft. deep, drains S.60°W.

15.10 Wash, 50 links wide, 2 ft. deep, drains N.80°W.

21.00 Wash, 60 links wide, 2 ft. deep, drains N.80°W.

27.00 Ravine, 30 links wide, 8 ft. deep, drains N.70°W.

40.13 Intersect original  $\frac{1}{4}$  section corner, a granite stone,

DEPENDENT RESURVEY OF SUBDIVISION, T. 27 N., R. 13 W.

Chains

12x8x5 ins., marked  $\frac{1}{4}$  on W. side, and loosely set in a small mound of stone.

At corner point.

Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in the ground, for  $\frac{1}{4}$  section corner of section 17, only, with brass cap marked

$\frac{1}{4}$   
S17  
1939

Deposit original stone corner at base of post, and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of post.

Corner stands on a gradual W. slope, 35 ft. below section corner.

Thence

N.0°01'W., with continuous measurement.

41.50 Wash, 60 links wide, 2 ft. deep, drains NW.

44.99 Midpoint between the closing corners of sections 9 and 16, and sections 16 and 21.

Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in the ground, for  $\frac{1}{4}$  section corner on W. boundary of section 16, with brass cap marked

$\frac{1}{4}$   
S16  
1939

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, E. of post.

47.00 Old unimproved road, bears NW. and SE.

56.30 Wash, 50 links wide, 1 ft. deep, 35 ft. below original  $\frac{1}{4}$  section corner, drains W.; gradually ascend along rolling SW. slope, 70 ft. to section corner.

62.90 Old abandoned railroad grade at Newhouse, bears N.48 $\frac{1}{2}$ °W. and S.48 $\frac{1}{2}$ °E.

80.09 Intersect the original corner of sections 8, 9, 16 and 17, a granite stone, 20x16x8 ins., marked with 4 notches on S. and E. edges, loosely set in small mound of stone.

At corner point.

Set an iron post, 3 ft. long, 2 ins. diameter, 27 ins. in the ground, for corner of sections 8 and 17, only, with brass cap marked

T27S RL3W  
S8  
S17  
1939

Deposit original stone corner alongside iron post, and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of corner.

Land, rolling and broken, with general westerly slope,

## DEPENDENT RESURVEY OF SUBDIVISION, T. 27 S., R. 13 W.

## Chains

lying along the E. edge of Wah Wah Valley.  
Soil, rocky and gravelly clay; 3rd rate.  
Timber, none.  
Undergrowth, sage, yellow top and mountain rush.  
Grazing, fair.

N.0°15'E., on dependent resurvey, along E. boundary of section 8.

Over rolling valley land, through dense short undergrowth.

- 3.70 Wash, 1 ch. wide, 1 ft. deep, drains W.  
4.88 Point for the closing corner of sections 9 and 16, hereinafter described.  
9.80 Wash, 60 links wide, 5 ft. deep, drains S.80°W.  
20.70 Ravine, 5 ft. deep, drains W.  
40.04 Intersect the original  $\frac{1}{4}$  section corner, a granite stone, 12x8x5 ins., marked  $\frac{1}{4}$  on one face, lying in a scattered mound of stones.

At corner point.

Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in the ground, for  $\frac{1}{4}$  section corner of section 8, only, with brass cap marked

$\frac{1}{4}$   
S8  
1939

Deposit the original stone corner alongside of iron post, and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of post.

Corner stands on a general W. slope, 20 ft. above the section corner.

Thence

N.0°43'E., with continuous measurement.

- 44.89 Midpoint between the closing corners of sections 4 and 9, and sections 9 and 16.

Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in the ground, for  $\frac{1}{4}$  section corner, on W. boundary of section 9, with brass cap marked

$\frac{1}{4}$   
S9  
1939

Deposit a granite stone, 9x8x3 ins., marked  $\frac{1}{4}$  at base of post, and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, E. of corner.

- 48.00 Wash, 40 links wide, 4 ft. deep, drains S.70°W.  
51.40 Wash, 60 links wide, 2 ft. deep, drains W.  
63.00 Wash, 60 links wide, 2 ft. deep, drains S.60°W.  
71.00 Unimproved road, bears N.80°E. and S.80°W.



## DEPENDENT RESURVEY OF SUBDIVISION, T. 27 S., R. 13 W.

## Chains

- 40.85 Unimproved road, bears N.55°E. and S.55°W.; this was formerly the old Salt Lake - Pioche road.
- 68.00 Shallow swale, at base of descent, 35 ft. below  $\frac{1}{4}$  section corner, drains N.80°W.; thence slight ascent along W. exposure.
- 80.65 Intersect the original section corner, a granite stone, 12x8x6 ins., dimly marked with 1 notch on S. and 5 notches on E. edges, firmly set in the ground, unwitnessed.

At corner point.

Set an iron post, 3 ft. long, 2 ins. diameter, 27 ins. in the ground, for corner of sections 29, 30, 31 and 32, with brass cap marked

T27S	R13W
S30	S29
S31	S32
1939	

Deposit the original stone corner and broken glass at base of the iron post, and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of post.

Land, gently rolling valley, with a general northwesterly exposure and drainage.

Soil, gravelly clay; 2nd rate.

Timber, none.

Undergrowth, short scattered shadscale and yellow top.

Grazing, fair.

From the corner of sections 29 and 32, hereinbefore described.

S.89°02'W., on dependent resurvey, between sections 29 and 32.

Over gently rolling valley land, with slight SW. exposure, through short undergrowth; gently descend 80 ft. to  $\frac{1}{4}$  section corner.

- 4.00 Shallow swale, drains SW.
- 10.00 Shallow swale, drains SW.
- 30.40 Unimproved road, bears NE. and SW.
- 40.16 Proportionate distance; no trace of the original  $\frac{1}{4}$  section corner.

Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in the ground, for restored  $\frac{1}{4}$  section corner, with brass cap marked

$\frac{1}{4}$	S29
	S32
1939	

Deposit broken glass at base of post, and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of post.

Continue descent of 75 ft. to section corner.

- 73.50 Unimproved road; bears N. and S. to Antelope Spring.

## DEPENDENT RESURVEY OF SUBDIVISION, T. 27 S., R. 13 W.

Chains

chains

80.33 Intersect the original corner of sections 29, 30, 31 and 32.

Land, gently rolling, with a gradual SW. to W. exposure, and drainage.

Soil, coarse gravelly clay; 2nd rate.

Timber, none.

Undergrowth, short shadscale and yellow top.

Grazing, fair.

From the original corner of sections 25, 30, 31 and 36, on W. boundary of township, hereinbefore described.

Thence

N.88°10'E., on dependent resurvey, between sections 30 and 31.

Over gently rolling valley land, through short undergrowth, ascending 45 ft. to  $\frac{1}{4}$  section corner.

37.18 Intersect the original  $\frac{1}{4}$  section corner, a granite stone, 11x8x4 ins., lying on the ground, marked  $\frac{1}{4}$  on one face.

At corner point.

Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in the ground, for  $\frac{1}{4}$  section corner, with brass cap marked

$$\frac{1}{4} \begin{array}{c} S30 \\ S31 \\ 1939 \end{array}$$

Deposit original stone corner and broken glass at base of post, and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, N. of post.

Thence N.88°58'E., with continuous measurement.

Gently ascend 50 ft. to section corner.

61.50 Swale, drains NW.

77.34 Intersect the original corner of sections 29, 30, 31, and 32.

Land, gently rolling valley with a general NW. exposure, and drainage.

Soil, gravelly clay; 2nd rate.

Timber, none.

Undergrowth, shadscale and yellow top.

Grazing, fair.

N.0°13'E., on dependent resurvey, between sections 29 and 30.

Over gently rolling valley with westerly exposure, through short undergrowth.

17.90 Old unimproved road, bears nearly E. and W.

36.00 Shallow swale, drains W.

40.47 Intersect the original  $\frac{1}{4}$  section corner, a granite stone, 12x8x4 ins., marked  $\frac{1}{4}$  on one face, lying on the ground, unwitnessed.

## DEPENDENT RESURVEY OF SUBDIVISION, T. 27 S., R. 13 W.

## Chains

At corner point.

Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in the ground, for  $\frac{1}{4}$  section corner, with brass cap marked

$\frac{1}{4}$   
 S30 | S29  
 1939

Deposit original stone corner and broken glass at base of post, and raise a small mound of stone W. of post.

Corner stands on a slight W. slope, nearly level with section corner.

Thence

N.0°19'E., with continuous measurement.

- 80.93 Intersect original section corner, a granite stone, 16x6x6 ins., marked with 2 notches on one edge and 5 notches on cornering edge, and lying on the ground, unwitnessed.

At corner point.

Set an iron post, 3 ft. long, 2 ins. diameter, 27 ins. in the ground, for corner of sections 19, 20, 29 and 30, with brass cap marked

T27S R13W.  
 S19 | S20  
 S30 | S29  
 1939

Deposit original stone corner and broken glass at base of post, and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, W. of corner.

Land, gently rolling with a westerly exposure and drainage.

Soil, gravelly clay; 2nd rate.

Timber, none.

Undergrowth, short shadscale and yellow top.

Grazing, fair.

From the original corner of sections 20 and 29, heretofore described.

N.89°29'W., on dependent resurvey, between sections 20 and 29.

Over gently rolling land, through short undergrowth; gradually descending land, facing NW. 90 ft. to  $\frac{1}{4}$  section corner.

- 2.60 Wash, 20 links wide, 3 ft. deep, drains NW.
- 18.40 Wash, 1 ch. wide, 3 ft. deep, drains NW.
- 32.00 Wash, 20 links wide, 3 ft. deep, drains NW.
- 39.58 Intersect the original  $\frac{1}{4}$  section corner, a granite stone, 12x10x8 ins., marked  $\frac{1}{4}$  on one face, and lying on the ground, unwitnessed.

DEPENDENT RESURVEY OF SUBDIVISION, T. 27 S., R. 15 W.

Chains

At corner point.

Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in the ground, for  $\frac{1}{4}$  section corner, with brass cap marked

$$\frac{1}{4} \frac{S20}{S29} \\ 1939$$

Deposit original stone corner and broken glass at base of post, and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of post.

Descend 75 ft. to section corner.

Thence

S.89°37'W., with continuous measurement.

40.10 Swale, drains NW.

73.30 Unimproved road, bears N. and S. to Antelope Spring.

79.58 Intersect the original corner of sections 19, 20, 29, and 30.

Land, gently rolling valley; NW. exposure and drainage. Soil, coarse gravelly clay; 2nd rate.

Timber, none.

Undergrowth, short shadscale and yellow top.

Grazing, fair.

From the original corner of sections 19, 24, 25, and 30, on W. boundary of township, hereinbefore described.

Thence

N.88°31'E., on dependent resurvey, between sections 19 and 30.

Over gently rolling land, with NW. exposure, through short undergrowth; ascend 60 ft. to

37.35 Intersect the original  $\frac{1}{4}$  section corner, a granite stone, 14x10x7 ins., firmly set in the ground, and marked  $\frac{1}{4}$  on N. face.

At corner point.

Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in the ground, for  $\frac{1}{4}$  section corner, with brass cap marked

$$\frac{1}{4} \frac{S19}{S30} \\ 1939$$

Deposit the original stone corner and broken glass at base of post, and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of post.

Thence

N.87°42'E., with continuous measurement.

Ascend 90 ft. to

DEPENDENT RESURVEY OF SUBDIVISION, T. 27 S., R. 13 W.

Chains

77.55 Intersect the original corner of sections 19, 20, 29, and 30.

Land, gently rolling, with NW. exposure and drainage. Soil, gravelly clay; 2nd rate. Timber, none. Undergrowth, shadacale, yellow top and grass. Grazing, fair.

N.0°17'E., on dependent resurvey, between sections 19 and 20.

Over gently rolling land, facing NW., through short undergrowth; descend 25 ft. to  $\frac{1}{4}$  section corner.

10.80 Wash, 50 links wide, 5 ft. deep, drains NW.

40.17 Intersect original  $\frac{1}{4}$  section corner, a granite stone, 14x12x8 ins., marked  $\frac{1}{4}$  on W. face, loosely set in the ground.

At corner point.

Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in the ground, for  $\frac{1}{4}$  section corner, with brass cap marked



Deposit old stone corner and broken glass at base of post, and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, W. of post.

Thence  
N.0°14'E., with continuous measurement.

44.80 Telephone line, parallel to highway.

45.30 Utah Highway No. 21, improved gravelled road, bears N.70°35'W. and S.70°35'E., Ely, Nevada, to Milford, Utah.

48.40 Wash, 1 ch. wide, 1 ft. deep, drains NW.


71.50 Enter flood plain, drains NW.

78.00 Leave flood plain, edge bears NW. and SE., 50 ft. below  $\frac{1}{4}$  section corner.

80.00 Intersect the original section corner, a granite stone, 18x6x5 ins., marked with 3 notches on S. and 5 notches on E. edges.

At corner point.

Set an iron post, 3 ft. long, 2 ins. diameter, 27 ins. in the ground, for corner of sections 17, 18, 19, and 20, with brass cap marked



Deposit original stone corner and broken glass at base of

DEPENDENT RESURVEY OF SUBDIVISION, T. 23 S., R. 13 W.

Chains

post, and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of post.

Land, gently rolling desert, with slight NW. exposure and drainage.

Soil, gravelly and sandy clay, 2nd rate.

Timber, none.

Undergrowth, shadscale, yellow top and rabbit brush.

Grazing, fair.

From the corner of sections 17 and 20, heretofore described.

S.89°38'W., on dependent resurvey, between sections 17 and 20.

Over gently rolling land, through short undergrowth; gradually descend W. slope, 115 ft. to ¼ section corner.

31.40 Wash, 70 links wide, 1 ft. deep, drains NW.

38.00 Wash, 70 links wide, 1 ft. deep, drains NW.

40.09 Proportionate distance; no trace of original ¼ section corner.

Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in the ground, for restored ¼ section corner, with brass cap marked

S17  
320  
1939

Deposit broken glass at base of post, and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of post.

43.60 Wash, 50 links wide, 4 ft. deep, drains NW.

46.30 Graded road, bears N.8½°W., to Newhouse, Utah, and S.8½°E. to Highway No. 21.

49.20 Wash, 50 links wide, 5 ft. deep, drains NW.

56.50 Wash, 20 links wide, 3 ft. deep, drains NW.

80.18 Intersect original corner of sections 17, 18, 19 and 20, 70 ft. below ¼ section corner.

Land, gently rolling valley; general westerly exposure.

Soil, coarse gravelly and sandy clay, with scattered rock on E. end of mile; 2nd and 3rd rates.

Timber, none.

Undergrowth, shadscale, sage and yellow top.

Grazing, fair.

From the original corner of sections 13, 18, 19 and 24, on W. boundary of township, heretofore described.

N.87°30'E., on dependent resurvey, between sections 18 and 19.

Over gently rolling land, sloping NW., through short undergrowth; gently ascend 50 ft. to ¼ section corner.

## DEPENDENT RESURVEY OF SUBDIVISION, T. 27 S., R. 13 W.

## Chains

- 37.83 Intersect original  $\frac{1}{4}$  section corner, a granite stone, 10x10x3 ins., firmly set in the ground, and marked  $\frac{1}{4}$  on N. face.
- At corner point.
- Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in the ground, for  $\frac{1}{4}$  section corner, with brass cap marked
- $$\frac{1}{4} \begin{array}{c} S18 \\ S19 \\ 1939 \end{array}$$
- Deposit the stone corner and broken glass at base of post, and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of post.
- Thence
- N.89°00'E., with continuous measurement.
- 40.20 Wash, 20 links wide, 1 ft. deep, drains NW.
- 62.60 Wash, 50 links wide, 5 ft. deep, drains NW.
- 75.60 Wash, 15 links wide, 3 ft. deep, drains NW.
- 77.74 Intersect original corner of sections 17, 18, 19 and 20, 65 ft. above  $\frac{1}{4}$  section corner.
- Land, gently rolling, with a gentle NW. exposure and drainage.  
Soil, sandy and gravelly clay; 2nd rate.  
Timber, none.  
Undergrowth, shadscale, yellow top, and rabbit brush.  
Grazing, fair.
- N.0°20'E., on dependent resurvey, between sections 17 and 18.
- Over gently rolling land, through short undergrowth; descend gentle NW. slope, 50 ft. to  $\frac{1}{4}$  section corner.
- 4.10 Wash, 20 links wide, 5 ft. deep, drains W.
- 20.70 Swale, drains N.70°W.
- 39.82 Intersect the original  $\frac{1}{4}$  section corner, a granite stone, 16x10x6 ins., firmly set in the ground, and marked  $\frac{1}{4}$  on W. face.
- At corner point.
- Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in the ground, for  $\frac{1}{4}$  section corner, with brass cap marked
- $$\frac{1}{4} \begin{array}{c} S18 \\ S17 \\ 1939 \end{array}$$
- Deposit original stone corner at base of post, and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of corner.
- Thence
- N.0°04'E., with continuous measurement.

DEPENDENT RESURVEY OF SUBDIVISION, T. 27 S., R. 13 W.

Chains

5112

- 46.50 Wash, 20 links wide, 2 ft. deep, drains N.70°W.
- 53.50 Wash, 50 links wide, 5 ft. deep, drains N.70°W.
- 79.46 Proportionate distance; no trace of original section corner can be found.

Set an iron post, 3 ft. long, 2 ins. diameter, 27 ins. in the ground, for restored corner of sections 7, 8, 17, and 18, with brass cap marked

T27S	R13W
S7	S8
S18	S17
1939	

Deposit broken glass at base of post, and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of post.

Corner stands on slight SW. exposure, 20 ft. below ¼ section corner.

Land, gently rolling, with a general westerly exposure. Soil, sandy and gravelly clay; 2nd rate. Timber, none. Undergrowth, shadeless, yellow top and grass. Grazing, fair.

From the corner of sections 8 and 17, heretofore described

Thence

S.89°17'W., on dependent resurvey, between sections 8 and 17.

Over gently rolling valley land, sloping SW., through short undergrowth; gradually descend 185 ft. to ¼ section corner.

- 11.65 Old railroad grade to Newhouse, bears N.30°W. and S.30°E.
- 39.63 Intersect the original ¼ section corner, a granite stone, 16x8x7 ins., firmly set in the ground, and marked ¼ on N. face.

At the corner point.

Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in the ground, for ¼ section corner, with brass cap marked

¼	S8
	S17
1939	

Deposit the stone corner and broken glass at base of post, and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of post.

Thence

S.89°08'W., with continuous measurement.

- 58.10 Graded dirt road, bears N.8½°W. and S.8½°E.
- 80.19 Intersect the restored corner of sections 7, 8, 17 and 18, 100 ft. below ¼ section corner.

## DEPENDENT RESURVEY OF SUBDIVISION, T. 27 S., R. 13 W.

Chains

Land, gently rolling, with a general southwesterly exposure.

Soil, gravelly and sandy clay; 2nd rate.

Timber, none.

Undergrowth, shadscale, yellow top, and sagebrush.

Grazing, fair.

From the restored corner of sections 7, 12, 13, and 18, on W. boundary of township, heretofore described.

N.88°52'E., on dependent resurvey line, bet. sections 7 and 18.

Over rolling valley land, through short undergrowth; slight ascent of 35 ft. to  $\frac{1}{4}$  sec. corner.

21.00 Wash, 50 links wide, 1 ft. deep, drains N. 70° W.

37.28 Proportionate distance; no trace of the original corner can be found.

Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in the ground, for restored  $\frac{1}{4}$  section corner, with brass cap marked

S7  
 $\frac{1}{4}$   
S18

1939

Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, N. of post.

38.30 Unimproved road, bears NE. and SW.

46.00 Slope changes from a gentle W. slope to a SW. slope.

77.80 Intersect the restored corner of sections 7, 8, 17, and 18, 65 ft. above the  $\frac{1}{4}$  section corner.

Land, gently rolling.

Soil, sandy clay; 2nd rate.

Timber, none.

Undergrowth, shadscale, yellow top, and rabbit brush.

Grazing, fair.

N.0°05'W., on dependent resurvey, between sections 7 and 8.

Over gently rolling valley land, with a gentle westerly slope, through short undergrowth; ascend 25 ft. to  $\frac{1}{4}$  section corner.

39.64 Proportionate distance; no trace of the original corner.

Set an iron post, 3 ft long, 1 in. diameter, 27 ins. in the ground, for restored  $\frac{1}{4}$  section corner, with brass cap marked

$\frac{1}{4}$   
S7 | S8

1939

DEPENDENT RESURVEY OF SUBDIVISION, T. 27 S., R. 13 W.

Chains

Deposit broken glass at base of post, and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of corner.

51.00 Unimproved road, bears NE. and SW.

75.00 The W. side of concrete abutments which is the ruins of an old mill.

79.28 Proportionate distance; no trace of the original section corner.

Set an iron post, 3 ft. long, 2 ins. diameter, 27 ins. in the ground, for restored corner of sections 5, 6, 7, and 8, with brass cap marked

T27S	R13W
S6	S5
S7	S8

1939

Deposit broken glass at the base of post, and raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.

Land, gently rolling; general westerly slope.  
Soil, sandy and gravelly clay; 2nd rate.  
Timber, none.  
Undergrowth, shadscale and yellow top.  
Grazing, fair.

From the original corner of sections 5 and 8, heretofore described.

S.88°43'W., on dependent resurvey, between sections 5 and 8.

Over rolling valley land, sloping SW., through short undergrowth; gently descend 170 ft. to ¼ section corner.

25.20 Ravine, 8 ft. deep, drains SW. 60° W.

37.00 Wash, 50 links wide, 3 ft. deep, drains S. 60° W.

40.49 Proportionate distance; no trace of the original ¼ section corner can be found.

Set an iron post, 3 ft. long, 1 in. diameter, .27 ins. in the ground, for restored ¼ sec. corner, with brass cap marked

S5
¼
S8

1939

Deposit broken glass at base of post, and raise a mound of stone, 2 ft. base, 1½ ft. high, S. of corner.

Gradually descend 165 ft. to section corner.

61.30 Old railroad grade, bears N. 7½° W. and S. 7½° E.

## DEPENDENT RESURVEY OF SUBDIVISION, T. 27 S., R. 13 W.

Chain

- 80.10 Dim old road, bears N.10°W. and S.10°E.
- 80.98 Intersect the restored corner of sections 5, 6, 7, and 8.

Land, rolling; general SW. to W. exposure.  
Soil, gravelly and stony; 3rd rate.  
Timber, none.  
Undergrowth, shadscale, yellow top and greasewood.  
Grazing, fair.

From the restored corner of sections 1, 6, 7, and 12,  
on W. boundary of township, heretofore described.

N.89°34'E., on dependent resurvey, between sections  
6 and 7.

Over gently rolling valley land, with a gentle W. exposure,  
through medium dense undergrowth; ascend 65 ft. to  $\frac{1}{4}$   
section corner.

- 37.05 Proportionate distance; no trace of the original  $\frac{1}{4}$  section  
corner can be found.

Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in  
the ground, for restored  $\frac{1}{4}$  section corner, with brass cap  
marked

$$\frac{1}{4} \begin{array}{r} S6 \\ \hline S7 \end{array}$$

$$\frac{1}{4} \begin{array}{r} S6 \\ \hline S7 \end{array}$$

1939

Deposit glass at the base of the post, and raise a small  
mound of stone around post.

Gradually ascend 120 ft. to section corner.

- 77.51 Intersect the restored corner of sections 5, 6, 7, and 8.

Land, gently rolling; westerly slope.  
Soil, sandy and gravelly clay; 2nd rate.  
Timber, none.  
Undergrowth, shadscale, rabbit brush and yellow top.  
Grazing, fair.

N.1°22'E., on dependent resurvey, between sections 5  
and 6.

Over gently rolling land, sloping westerly, through  
short undergrowth; ascend 20 ft. to  $\frac{1}{4}$  section corner.

- 24.20 Wash, 50 lks. wide, 2 ft. deep, drains S. 80° W.
- 36.40 Wash, 30 lks. wide, 2 ft. deep, drains S. 60° W.

- 39.65 Intersect the original  $\frac{1}{4}$  section corner, a granite  
stone, 15x12x5 ins., lying on the ground, marked  $\frac{1}{4}$  on  
one face.

At corner point.

Set an iron post, 3 ft. long, 1 in. diameter, 27 ins.  
in the ground, for  $\frac{1}{4}$  section corner, with brass cap marked

$$\frac{1}{4}$$

$$S6 | S5$$

1939

## DEPENDENT RESURVEY OF SUBDIVISION, T. 27 S., R. 13 W.

Chains

Deposit the original stone corner at the base of the post, and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of post.

Land, rolling valley or desert, with westerly slope. Soil, coarse gravelly clay and rock; 3rd rate. Timber, none. Undergrowth, shadscale, sagebrush, and yellow top. Grazing, fair.

## SURVEY OF A PORTION OF THE SUBDIVISION, COMPLETING THE SURVEY OF, T. 27 S., R. 13 W.

From the ¼ section corner of secs. 5 and 6.

North, between sections 5 and 6.

Over gently rolling land sloping westerly, through short undergrowth.

15.40 Begin slight descent over land facing NW.

25.60 Wash, 50 links wide, 6 ft. deep, drains NW.

33.50 Wash, 20 links wide, 3 ft. deep, drains NW.

34.23 Intersect the north boundary of the township at a point, West 12.17 chains distant from the cor. of secs. 5, 6, 31, and 32, an iron post, 2 ins. diam., firmly set and properly marked as described in the official record of the survey of T. 26 S., R. 13 W., I efface the marks on the post that refer to sections 5 and 6, leaving same for sections 31 and 32, T. 26 S., R. 13 W., only.

At point of intersection.

Set an iron post, 3 ft. long, 2 ins. diameter, 27 ins. in the ground, for closing corner of sections 5 and 6, with brass cap marked

T26S R13W  
S31

S6 S5  
T27S R13W  
C C

1939

Raise a mound of stone, 2 ft. base, 1½ ft. high, S. of post.

Land, rolling valley or desert, with a westerly slope. Soil, coarse gravelly and sandy clay, scattered rock on N. end of mile; 3rd rate. Timber, none. Undergrowth, shadscale, sagebrush, and yellow top. Grazing, fair.

At a point S.89°57'W., 88 lks. distant from the restored corner of sections 13 and 14, or at an easting of 80.00 chains from the corner of sections 10, 11, 14, and 15, I establish the corner of sections 11 and 12, as follows:

Set an iron post, 3 ft. long, 2 ins. diameter, 27 ins. in the ground to rock and supported in a mound of stone to top, for corner of sections 11 and 12, with brass cap marked

## SUBDIVISION OF, T. 27 S., R. 13 W.

Chains

T27S	R13W
S11	S12
S14	

1939

from which

A pinon, 6 ins. diameter, bears N.43 $\frac{1}{4}$ °E., 51 links distant, marked T37S R13W S12 BT.

A cedar, 6 ins. diameter; bears N.50°W., 64 links distant, marked T27S R13W S11 BT.

Thence, North, between sections 11 and 12.

Over rolling mountainous land; through medium dense timber and scattering undergrowth; ascend steep S. slope.

- 5.40 Limestone outcrop, on hill, 95 ft. above section corner; continue gradual ascent.
- 13.10 Spur, 165 ft. above section corner, projects SE.; descend NE. slope.
- 18.60 Small draw near head, 60 ft. below spur, drains NE.
- 21.45 Intersect line 2-3, Survey No. 5199, Good Hope No. 1 lode, at N.55°55'E., 1.16 chains from Cbr. No. 2, identical with Cor. No. 3, Scorpion lode, this survey.
- 21.90 Draw at base of descent, 90 ft. below spur, drains S.80°E.; ascend rolling S. to SE. slope, 260 ft. to section corner.
- 27.40 Low spur, slopes S.70°E., a short distant to end.
- 29.60 Small draw, 30 ft. deep, drains S. 70°E.
- 38.05 On steep S. slope; southing of 40.00 chains distant from the corner of sections 1 and 12.

Set an iron post, 3 ft. long, 1 in. diameter, 20 ins. in the ground to rock and supported in a mound of stone, for  $\frac{1}{4}$  section corner, on W. boundary of section 12, with brass cap marked

$\frac{1}{4}$
S12

1939

from which

A pinon, 4 ins. diameter, bears N.30°E., 40 links distant, marked  $\frac{1}{4}$  S12 BT.

A cedar, 14 ins. diameter, bears S.71°E., 50 links distant, marked  $\frac{1}{4}$  S12 BT.

- 39.40 Spur from W., projects E. about 3.00 chains distant to end; descend steep NE. slope.
- 40.00 On gradual E. slope on E. edge of spur.

Set an iron post, 3 ft. long, 1 in. diameter, 20 ins. in the ground to rock, and supported in a mound of stone, for  $\frac{1}{4}$  section corner, on E. boundary of section 11, with brass cap marked

$\frac{1}{4}$
S11

1939

from which

SUBDIVISION OF T. 27 S., R. 13 W.

Chains

A pinon, 3 ins. diameter, bears S. 40° W., 18 links distant, marked only BT.

A cedar, 8 ins. diameter, bears N. 47° W., 85 links distant, marked  $\frac{1}{2}$  S11 BT.

43.70 Draw, 90 ft. below the  $\frac{1}{2}$  sec. cor., drains S. 60° E.; ascend steep S. to SW. slopes, 320 ft. to spur.

52.56 Intersect line 1-2, Survey No. 5391, Selma No. 8 lode, at S. 58° 27' W., 13.18 chains distant from Cor. No. 1, a pine post, 4 ins. square, firmly set and properly marked and witnessed, as described in record.

57.90 High spur, slopes S. 60° E., descend gradual NE. slope 15 ft.


60.50 Head of draw, drains S. 70° E.; ascend 30 ft.

63.90 Top of ascent on E. slope, slopes E. about 10 chains to end; descend steep NE. slope 100 ft.

69.00 Draw, drains N. 60° E.; ascend broken SE. slope, 60 ft. to

78.05 Point due west of corner of sections 1 and 12 on E. boundary.

Set an iron post, 3 ft. long, 2 ins. diameter, 18 ins. in the ground to rock, and supported in a large mound of stone, for corner of sections 1 and 12, with brass cap marked



1939

from which

A cedar, 10 ins. diameter, bears N. 23 $\frac{1}{2}$ ° E., 31 $\frac{1}{2}$  links distant, marked T27S R13W S1 BT.


A pinon, 5 ins. diameter, bears S. 10° 45' E., 65 links distant, marked T27S R13W S12 BT.

Corner stands on gradual SE. slope.

79.00 Spur, slopes SE.

80.00 On gradual NE. slope.

Set an iron post, 3 ft. long, 2 ins. diameter, 27 ins. in the ground, for corner of sections 2 and 11, with brass cap marked



1939

from which

A cedar, 8 ins. diameter bears S. 44° 45' W., 23 links distant, marked T27 S R13W S11 BT.

A cedar, 12 ins. diameter, bears N. 55 $\frac{1}{2}$ ° W., 82 links distant, marked T27S R13W S2 BT.

From this corner N. 27° 37' W., 3.88 $\frac{1}{2}$  chains distant to

## SUBDIVISION OF T. 27 S., R. 13 W.

## Chains

Corner No.1, Survey No. 6010, Blackbird No. 4 lode.

Land, mountainous; general southeasterly exposure and drainage.

Soil, rocky and gravelly; 3rd to 4th rates.

Timber, medium dense cedar and pinon.

Undergrowth, sage and shadscale.

Grazing, fair.

From the corner of sections 1 and 12.

East, on random line, between sections 1 and 12.

40.00 Set temporary  $\frac{1}{4}$  section corner.

81.52 Intersect the corner of sections 1 and 12, on E. boundary of township, an iron post, 2 ins. diameter, firmly set and properly marked and witnessed, as described in official record.

Thence

West, on true line, between sections 1 and 12.

Over rolling mountainous land, through scattering timber and short undergrowth; gradually ascend land facing SE.

6.70 Draw, 30 ft. deep, drains SE.

21.00 Draw, drains SE.; ascend steep E. slope, entering medium dense timber, bears N. and SE.

26.75 Pipe line to Horn Silver Mine, bears N, 17°18'W. and S. 17°18'E.

41.52 On steep, rocky E. slope, 540 ft. above section corner.

Set an iron post, 3 ft. long, 1 in. diameter, 20 ins. in the ground to rock, and supported in a mound of stone to top, for  $\frac{1}{4}$  section corner, with brass cap marked

$$\frac{1}{4} \frac{S 1}{S 12}$$

1939

from which

A cedar, 8 ins. diameter, bears N. 48 $\frac{1}{2}$ °E., 57 links distant, marked  $\frac{1}{4}$  S1 BT

A cedar, 6 ins. diameter, bears S. 49°45'E., 70 links distant, marked  $\frac{1}{4}$  S12 BT

From  $\frac{1}{4}$  section corner N. 48°24'E. about 38 chains distant to most southerly one of 3 old charcoal kilns.

41.94 Intersect line 4-1, Survey No. 5391, Burlington No. 8 Mine lode, at S. 19°17'W. 1.88 $\frac{1}{2}$  chains distant from corner No. 4, a pine post, 4 ins. diameter, firmly set and properly marked.

45.00 High spur, 90 ft. above  $\frac{1}{4}$  section corner, slopes NE.; gradually descend along N. slope of same.

52.00 Recross spur, ascends SE. to high point.

55.80 Recross same, bears N. 85°E. and SW., thence along N. slope.

## SUBDIVISION OF T. 27 S., R. 13 W.

Chains

301281

- 63.50 Recross same, ascends SE. and slopes NW. to saddle; descend steep W. slope 115 ft.
- 72.60 Gulch, drains S.30°E.; ascend NE. slope.
- 79.50 Cross spur, slopes SE.; continue ascent over SE. slope.
- 81.52 Intersect the corner of sections 1 and 12, 210 ft. above gulch.

Land, mountainous.  
Soil, coarse gravelly clay and rocky; 3rd to 4th rates.  
Timber, cedar and pinon.  
Undergrowth, sage, yellow top and bitter brush.  
Grazing, poor.

From the corner of sections 2 and 11.

North, between sections 1 and 2.

Over mountainous land, facing easterly, through medium dense timber and scattering undergrowth; descend NE. slope 40 ft.

- 2.00 Head of draw, drains S.70°E.; ascend 50 ft. to ridge.
- 3.38 Intersect line 3-4, Survey No. 5556, Triumphant No. 2 lode, at S.88°13'E. 1.802 chains distant from Corner No. 3, identical with Corner No. 4, Survey No. 5556, Triumphant No. 3 lode, and Corner No.1, Survey No. 6010, Blackbird No. 4 lode.
- 4.50 Ridge, bears N.80°W. and S.80°E.; thence along a rolling general E. slope.
- 19.80 Draw, 50 ft. deep, drains S.70°E.
- 26.94 West of line, 25 links distant, to Corner No. 4, Survey No. 5303, U Bet lode.
- 31.00 Draw, 40 ft. deep, drains SE.
- 35.20 Low spur, 60 ft. above section corner, slopes SE.
- 38.05 Northing of 40.00 chains from the corner of sections 1 and 12.

Set an iron post, 3 ft. long, 1 in. diameter, 20 ins. in the ground to rock, and in a small mound of stone, for  $\frac{1}{4}$  section corner on W. boundary of section 1, with brass cap marked

$\frac{1}{4}$   
S1

1939

from which

A pinon, 5 ins. diameter, bears N.69°E., 41 links distant, marked  $\frac{1}{4}$  S1 BT

A pinon, 9 ins. diameter, bears S.36 $\frac{1}{2}$ °E., 96 links distant, marked  $\frac{1}{4}$  S1 BT

Corner stands on gradual N. slope, 20 ft. below spur.

- 40.00 On steep N. slope, 20 ft. below the above  $\frac{1}{4}$  section corner.

## SUBDIVISION OF T. 27 S., R. 13 W.

Chains

Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in the ground, for  $\frac{1}{4}$  section corner, on E. boundary of section 2, with brass cap marked

$\frac{1}{4}$   
 S2 |  
 1939

from which

A cedar, 8 ins. diameter, bears S.37°W., 36 links distant, marked  $\frac{1}{4}$  S2 BT

A cedar, 9 ins. diameter, bears N.50°W., 45 links distant, marked  $\frac{1}{4}$  S2 BT

- 43.10 Draw, 100 ft. below last corner, drains S.80°E.  
 52.00 Draw, drains S.80°E.; ascend rolling S. slope, 210 ft.  
 62.40 Ridge, bears NW. and SE.; gently descend along E. slope.  
 67.30 Intersect N. boundary of township, West 16.08 chains distant from the corner of sections 1, 2, 35, and 36, an iron post, 2 ins. diameter, firmly set, marked and witnessed, as described in the official record. As this corner will now function only for sections 35 and 36, T. 26 S., R. 13 W., I efface marks on post and bearing trees that refer to sections 1 and 2.

At point of intersection.

Set an iron post, 3 ft. long, 2 ins. diameter, 27 ins. in the ground, for closing corner of sections 1 and 2, with brass cap marked

T26S R13W  
 S35  
 ———  
 S2 | S1  
 T27S | R13W  
 CC  
 1939

from which

A cedar, 10 ins. diameter, bears S.19°45'E., 169 links distant, marked T27S R13W S1 CC BT

A cedar, 10 ins. diameter, bears S.39°45'W., 35 links distant, marked T27S R13W S2 CC BT

Corner stands in head of shallow draw, drains S.70°E.

Land, rolling mountainous; general easterly exposure and drainage.

Soil, gravelly and rocky; 3rd to 4th rates.

Timber, cedar and pinon.

Undergrowth, sage and service brush.

Grazing, fair to poor.

From the restored corner of sections 25, 26, 35, and 36, heretofore described.

West, on sectional correction line, on random for distance only.

40.75 Set temporary  $\frac{1}{4}$  section corner.

80.75 Set temporary corner of sections 26, 27, 34, and 35.

SUBDIVISION OF T. 27 S., R. 13 W.

Chains

original

Thence

South, between sections 34 and 35, on random line.

40.00 Set temporary  $\frac{1}{4}$  section corner.

81.78 Intersect S. boundary of township, 4 links W. of the corner of sections 34 and 35, an iron post, 2 ins. diameter, firmly set, marked and witnessed, as described in official record.

Thence from the corner of sections 34 and 35, on S. boundary of township.

North, on Sectional Guide Meridian, between sections 34 and 35.

Over rolling mountainous land, through short undergrowth; along a broken and rolling general westerly slope.

1.60 Small shallow ravine, drains W.

21.80 Low spur, 50 ft. above section corner, projects W.

28.10 Draw, 10 ft. below spur, drains W.

38.30 Ridge, 90 ft. above section corner, bears E. and N. 70° W.

41.78 On a gradual NW. slope.

Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in the ground, for  $\frac{1}{4}$  section corner, with brass cap marked

$\frac{1}{4}$   
 S34 | S35  
 1938

Raise a mound of stone, 5 ft. base, 4 ft. high, W. of post.

43.40 Head of draw, drains W. for about 2 chains distant, thence NW.; ascend 50 ft. over SW. slope.

48.30 Low pass, in high rocky spur from E., projects N. 80° W., about 3 chains distant to high rocky peak; descend rolling N. slope.

64.10 Draw, 190 ft. below spur, drains NW.; thence along westerly slope.

71.20 Head of shallow draw, drains W.; ascend 55 ft.

75.50 Low spur, projects NW.; thence along E. slope.

79.00 Recross N. end of same spur from SW.; descend steep N. slope, 50 ft.

81.78 Set an iron post, 3 ft. long, 2 ins. diameter, 6 ins. in the ground to rock, and supported in a large mound of stone to top, for corner of sections 26, 27, 34, and 35, with brass cap marked

T27S R13W  
 S27 | S26  
 S34 | S35  
 1938

Corner stands on steep N. slope.

## SUBDIVISION OF T. 27 S., R. 13 W.

## Chains

Land, hilly and rolling mountainous; general westerly exposure and drainage.  
Soil, stony and gravelly clay; 3rd rate.  
Timber, few widely scattered scrub cedars.  
Undergrowth, sage, shadscale and yellow top.  
Grazing, fair.

From the restored corner of sections 25, 26, 35, and 36.

West, on Sectional Correction Line, between sections 26 and 35.

Over rolling mountainous land, through scattering timber and short undergrowth; slight ascent along N. slope to

- 0.90 Low spur, slopes N.; descend W. slope, 35 ft.  
3.60 Draw, drains N.10°W.; ascend NE. slope.  
6.50 N. point of spur, from S.; descend NW. slope.  
7.10 Draw, heads S. about 8 chains distant, drains N.10°E.; ascend steep rocky E. slope.  
12.80 High rocky spur, 165 ft. above section corner, projects N.20°E.; descend steep W. slope, 210 ft.  
20.20 Head of draw, drains N. about 2 chains distant, thence NW.  
22.00 Low spur, projects NW.; descend broken W. slope, 160 ft.  
39.70 Draw, drains NW.; ascend NE. slope.  
40.71 On steep rocky NE. slope.

Set an iron post, 3 ft. long, 1 in. diameter, 12 ins. in the ground to rock, and supported in a mound of stone, for section corner, with brass cap marked

$$\frac{1}{4} \frac{326}{335} \\ 1938$$

from which

A cedar, 12 ins. diameter, bears N.72 $\frac{1}{2}$ °W., 41 links distant, marked S26 BT

A red colored granite outcrop, 30 ft. high, bears N.80°E., about 5 chains distant.

- 43.70 Begin descent over rolling general westerly slope, leaving nearly all timber.  
64.20 Low spur, slope N.80°W.  
70.30 Recross same, slopes S.10°W.; descend W. slope into draw, 160 ft.  
77.90 Draw, drains NW.; ascend NE. slope, 45 ft. to  
80.71 The corner of sections 26, 27, 34, and 35.

Land, rolling mountainous, or hilly; general N. to NW. exposure and drainage.  
Soil, rocky and gravelly; 3rd to 4th rates.  
Timber, scattering scrub cedars.  
Undergrowth, sage, shadscale and yellow top.  
Grazing, fair.

## SUBDIVISION OF T. 27 S., R. 13 W.

Chains

North, on Sectional Guide Meridian, between sections 26 and 27.

Over rolling, hilly land, facing westerly, through short undergrowth; descend N. slope, 60 ft.

- 4.60 Draw, drains N.30°W.; continue gradual descent over land facing NW.
- 35.20 Telephone line, 2 wire, parallel to highway.
- 36.10 Utah Highway No. 21, improved gravel road, bears S.78½°E. and N.78½°W., Ely, Nevada, to Milford, Utah.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, and surrounded by a mound of stone, for ¼ section corner, with brass cap marked

¼  
S27 | S26  
1939

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.

Corner stands in wide shallow wash, draining N.70°W., 165 ft. below section corner.

From ¼ section corner, concrete watering trough, at Squaw Spring, bears S.81½°E. 35.46 chains distant. Head of spring in 20 ft. tunnel, bears S.28°E., about 2 chains distant from trough. House bears S.75°E., about 50 links distant from trough.

Ascend rolling S. to SW. slopes.

- 54.65 Old railroad bed to Newhouse, bears N.57°W. and S.57°E.
- 65.06 Intersect line 2-3, Survey No. 5986, Emporia No. 9 lode, at S.76°31'E., 68½ links distant, from Corner No. 2, identical with Corner No. 3, Emporia No. 7 lode, same survey, a pine post, 4 ins. square, firmly set, and properly marked.
- 73.66 Power line to King David Mine, bears N.55½°W. and S.55½°E.
- 78.10 Head of small draw, drains SW.
- 80.00 On steep rocky SW. slope, 250 ft. above ¼ section corner.
- Set an iron post, 3 ft. long, 2 ins. diameter, 15 ins. in the ground to rock, and supported in a mound of stone to top, for corner of sections 22, 23, 26, and 27, with brass cap marked

T27S | R13W  
S22 | S23  
-----  
S27 | S26  
1939

from which

A cedar limb, 8 ins. diameter, bears S.49½°E., 154 links distant, marked T27S R13W S26 BT

A cedar, 8 ins. diameter, bears S.58½°W., 46 links distant, marked T27S R13W S27 BT

Land, rolling and hilly; general NW. and SW. exposures.

## SUBDIVISION OF T. 27 S., R. 13 W.

## Chains

Soil, gravelly and stony; 3rd to 4th rates.  
 Timber, scattering scrub cedars on N. end of mile.  
 Undergrowth, sage and shadscale.  
 Grazing, fair.

East, on random line, between sections 23 and 26.

40.00 Set temporary  $\frac{1}{4}$  section corner.

79.50 Intersect N. and S. line, 3 links S. of the restored corner of sections 23, 24, 25, and 26.

Thence

S.89°59'W., on true line, between sections 23 and 26.

Over mountainous land, through few scattered trees and short undergrowth; gradually ascend rolling E. slope.

13.60 Power line, bears N.0°43'E. and S.0°43'W.

13.75 Intersect line 1-4, Lot 47, Americus lode, at S.0°51'W. 6.78 chains distant from Corner No. 1, and N.0°51'E. 10.206 chains distant from Corner No. 4. Corners are marked by pine posts, 4 ins. square, firmly set and properly marked. Record bearing and distance of line 1-4, this claim, is reported as being N.0°30'W. 1132.1 ft. (17.153 Chs.)

23.80 Small draw, drains S.10°E.

28.70 Head of draw, drains S.30°E.

33.20 Top of ascent, on high spur, 330 ft. above section corner, slopes S.10°E.; thence along a steep broken and rocky general S. slope; descend 95 ft. to

39.50 In small depression, draining S.

Set an iron post, 3 ft. long, 1 in. diameter, 29 ins. in the ground to rock, and supported in a mound of stone, for  $\frac{1}{4}$  section corner, with brass cap marked

$$\frac{1}{4} \frac{S23}{S26}$$

1939

from which

A cedar, 6 ins. diameter, bears S.2 $\frac{1}{2}$ °E., 74 links distant, marked  $\frac{1}{4}$  S26 BT

A pinon, 8 ins. diameter, bears N.27°W., 47 links distant, marked  $\frac{1}{4}$  S23 BT

Ascend 65 ft.

43.90 Spur, slopes S. about 2 chains to end; descend 50 ft.

47.40 Depression, drains S.

49.40 Top of rise, slopes S.

53.10 Depression, drains S.

60.90 Begin steep descent over broken and rocky SW. slope, 300 ft. to

79.50 The corner of sections 22, 23, 26, and 27.

**SUBDIVISION OF T. 27 S., R. 15 W.**

**Chains**

Land, mountainous.  
 Soil, rocky and shallow gravelly clay; 4th rate; limestone formation.  
 Timber, scattering cedar and pinon.  
 Undergrowth, scattering shadscale and sagebrush.  
 Grazing, poor.

North, on sectional guide meridian, between sections 22 and 23.

Over mountainous land, through scattering timber and short undergrowth; ascend rocky SW. slope, 90 ft.

- 4.20 Top of rise, on SW. slope; descend 10 ft.
- 6.60 Swale, drains SW.; ascend SW. slope.
- 15.00 Begin ascent along steep W. slope.
- 18.30 Top of ascent on W. slope, 185 ft. above section corner, bears S. and slopes SW.; descend NW. slope 35 ft.
- 20.20 Draw, drains SW.; ascend steep S. slope.
- 30.70 High spur, 500 ft. above section corner, slopes SW. about 15 chains distant to end; descend NW. slope, 150 ft.
- 38.00 Draw, near head, drains S. 80° W.; ascend 50 ft.
- 40.00 On SW. slope.

Set an iron post, 3 ft. long, 1 in. diameter, 3 ins. in the ground to rock, and supported in a mound of stone to top, for section corner, with brass cap marked

§  
 S22 | S23  
 1939

from which

A cedar limb, 4 ins diameter, bears S. 62° E., 52 links distant, marked § S23 BT

A pinon limb, 6 ins. diameter, bears N. 66° W., 145 links distant, marked § S22 BT

- 40.90 Old mine shaft on line.
- 44.80 Old mine tunnel, facing W., bears E. of line about 50 links distant.
- 53.30 Small draw, 80 ft. below § section corner, drains W.
- 58.40 A main draw, drains S. 20° W.; ascend steep general S. slope, 300 ft. to section corner.
- 63.70 Bend in spur, from N. 20° W., slopes S. 30° W.
- 74.70 Recross same, slopes S. 20° W.; continue ascent along W. slope.
- 77.491 Intersect line 4-1, Survey No. 5986, Reciprocity No. 3 lode at N. 73° 10' W. 0.063 chains distant from Corner No. 4, a pine post, 4 ins. square, firmly set and properly marked.
- 80.00 On W. slope, 735 ft. above section corner.

## SUBDIVISION OF T. 27 S., R. 13 W.

## Chains

Set an iron post, 3 ft. long, 2 ins. diameter, 24 ins. in the ground, and surrounded by a mound of stone, for corner of sections 14, 15, 22, and 23, with brass cap marked

T27S	R13W
S15	S14
S22	S23
1939	

from which

A pinon, 6 ins. diameter, bears N.54 $\frac{1}{2}$ °E., 24 links distant, marked T27S R13W S14 BT

A pinon, 10 ins. diameter, bears S.20 $\frac{1}{2}$ °E., 35 $\frac{1}{2}$  links distant, marked T27S R13W S23 BT

A pinon, 12 ins. diameter, bears S.70 $\frac{1}{2}$ °W., 44 $\frac{1}{2}$  links distant, marked T27S R13W S22 BT

A cedar, 6 ins. diameter, bears N.48 $\frac{1}{2}$ °W., 55 links distant, marked T27S R13W S15 BT

From section corner S.1°21'E. 2.527 chains distant to Corner No. 4, and S.2°16'E. 2.785 chains distant, to Corner No. 3, Survey No. 5986, Reciprocity No. 3 lode.

Land, mountainous; general SW. and S. exposures. Soil, rocky, of blue limestone formation, and shallow gravelly clay; 4th rate.

Timber, scattering cedar and pinon.

Undergrowth, scattering shadscale and bitter brush.

Grazing, poor.

N.89°59'E., on random line, between sections 14 and 23.

40.00 Set temporary  $\frac{1}{4}$  section corner.

79.98 Intersect N. and S. line, 3 links S. of the restored corner of sections 13, 14, 23, and 24.

Thence

S.89°58'W., on true line, between sections 14 and 23.

Gradually ascend over rolling land, facing E. to SE., through medium dense timber and short scattering undergrowth,

7.70 Pipe line, to Horn Silver Mine, bears NE. and SW.

8.30 Wash, 15 links wide, 4 ft. deep, drains S.30°E.

10.056 Intersect line 1-4, Lot 73, Dumbarton lode, at S.22°31'W. 7.33 chains distant from Corner No. 1, a pine post, 4 ins. square, firmly set and properly marked.

Note: The bearing of this line as recorded in original record is N.22°43'E.

17.706 Intersect line 2-3, this claim at S.22°37'W. 7.48 chains distant, from Corner No.2, a pine post, 4 ins. square, firmly set and properly marked.

Note: The bearing of this line, 2-3, as recorded in original record is S.22°43'W.

21.00 E. base of mountainous land, 80 ft. above section corner, bears nearly N. and S.; ascend steep E. slope.

SUBDIVISION OF T. 27 S., R. 13 W.

**Chains**

- 28.00 Slope, changes from E. to steep NE. and N. slopes.
  - 39.30 Spur, 450 ft. above section corner, projects S. 70° E. about 5 chains distant to end; thence along S. slope; descend 10 ft. to
  - 39.99 On S. slope.  
Set an iron post, 3 ft. long, 1 in. diameter, 6 ins. in the ground to rock, and supported in a mound of stone to top, for  $\frac{1}{4}$  section corner, with brass cap marked
- $$\frac{1}{4} \frac{S14}{S23}$$

1939
- from which
- A cedar, 10 ins. diameter, bears N. 89° E., 43 links distant, marked  $\frac{1}{4}$  S14 BT
  - A cedar, 12 ins. diameter, bears S. 21° E., 29 links distant, marked  $\frac{1}{4}$  S23 BT
- 42.60 Head of draw, drains S.; ascend steep broken SE. slope, 160 ft.
  - 52.60 Main ridge, bears N. and S.; descend steep broken SW. and S. slopes, 240 ft.
  - 62.60 Draw, near head, drains S. 20° W.; ascend 35 ft.
  - 63.60 Old mine tunnel, bears N. of line about 50 links distant.
  - 64.70 Low spur, slopes S. 20° W.; descend 80 ft.
  - 71.70 Shallow draw, drains S. 10° W.; ascend 20 ft.
  - 77.30 Spur, slopes S. 30° W.; descend steep W. slope, 60 ft. to
  - 79.98 The corner of sections 14, 15, 22, and 23, 330 ft. below main ridge.
- Land, mountainous; general E. and SW. exposures and drainage from high ridge.  
Soil, rocky and gravelly; limestone and granite formations; 4th rate.  
Timber, cedar and pinon.  
Undergrowth, shadscale, bitter brush and yellow top.  
Grazing, fair to poor.

North, on sectional guide meridian, between sections 14 and 15.

Over mountainous land, through scattering timber and short undergrowth; ascend along steep W. slope.

- 7.00 Head of draw, draining S., bears W. of line, 1 chain distant; ascend steep SW. slope.
- 8.35 Old mine tunnel, facing W. on line.
- 14.10 Trail, bears E. and W.
- 18.00 Ridge, 410 ft. above section corner, ascends NE. to high point, and slopes SW. about 4 chains distant to saddle; continue ascent over SW. slope.

## SUBDIVISION OF, T. 27 S., R. 13 W.

## Chains

- 18.01 Intersect line 3-4, Survey No. 4751, Hedges Fraction lode at N.51°36'E., 3.00 chains distant from Corner No. 3, a pine post, 4 ins. square, firmly set and properly marked.
- 19.90 Trail, bears N. 20° W. and S. 30° E.
- 24.30 Top of ascent, on abrupt W. slope of spur, 600 ft. above section corner, bears E. to high quartzite point, and slopes W.; descend abrupt ledgy NW. slope, 300 ft.
- 35.00 Gulch, drains S.70°W. about 3 chains distant to junction with gulch from N., thence SW.; ascend rocky SW. slope 200 ft. to  $\frac{1}{4}$  section corner.
- 37.69 Intersect line 1-2, Lot 71 Amd. Quartzite No. 2 lode at S.48°07'E. 6.64 chains distant from Corner No. 2, and N.48°07'W. 8.156 chains distant from Corner No. 1. Both corners of claim are marked with pine posts, 6 ins. diameter, firmly set and properly marked
- 40.00 On steep rocky W. slope, among granite outcrops.

Set an iron post, 3 ft. long, 1 in. diameter, 10 ins. in the ground to rock; and supported in a mound of stone to top, for  $\frac{1}{4}$  section corner, with brass cap marked

$\frac{1}{4}$   
 S15 | S14  
 1939

from which

A pinon, 14 ins. diameter, bears S.38 $\frac{1}{2}$ °E., 40 links distant; marked  $\frac{1}{4}$  S14 BT.

A pinon, 11 ins. diam., bears N.72°W., 127 links distant, marked  $\frac{1}{4}$  S15 BT.

From  $\frac{1}{4}$  section corner, S.21°01'E., 14.98 chains distant, (mean of two measurements) to U. S. M. M. No. 1, which is a cedar post, 5 ins. diameter, about 7 ft. high, set in a mound of stone. Nails in post and broken pieces of board at base, on which all marking have disappeared, are the only evidence of board on which the marks were originally placed. Post is located on a prominent point at west end of high quartzite spur from the E.

From the  $\frac{1}{4}$  section corner, S.34°40'W., 3.925 chains distant to Corner No. 2, Lot 65, Massachusetts lode, a hewn pine post, 5 ins. diameter, 4 ft. long, set in a mound of stone, marked USL65P2.

Ascend abrupt ledgy S. slope, 525 ft. to ridge.

- 52.275 Intersect line 4-1, Survey No. 4749, Oil City lode, at N.9°31'E. 8.99 chains distant, from Corner No. 4, identical with Corner No. 3, Lot 65, Massachusetts lode, a pine post, 4 ins. square, firmly set and properly marked.
- 55.20 High divide ridge, bears S. 70° E. about 10 chains distant to high point, thence southerly, and N. 20° W.; descend along E. and NE. slopes, 90 ft.
- 59.00 Head of draw, drains S. 70° E.; ascend steep SE. slope.
- 64.51 Intersect line 1-2, Survey No. 4749, Oil City lode, at N.77°24'W., 2.02 chains distant from Corner No. 1, a pine post, 4 ins. squared, firmly set and properly marked.
- 67.00 Spur, 200 ft. above draw, slopes SE.; thence along E. slope.
- 70.50 Head of draw, drains SE.

SUBDIVISION OF T. 27 S., R. 13 W.

Chains

71.90 Top of ascent, on high spur, 260 ft. above the draw at 67 chs., projects S. 60° E.; descend steep NE. slope, 150 ft.

80.00 On steep NE. slope.

Set an iron post, 3 ft. long, 2 ins. diameter, 27 ins. in the ground, for corner of sections 10, 11, 14, and 15, with brass cap marked

T27S	R13W
S10	S11
S15	S14

1939

from which

A pinon, 6 ins. diameter, bears N. 53°45' E., 45 links distant, marked T27S R13W S11 BT.

A pinon, 8 ins. diameter, bears S. 60½° E., 97 links distant, marked T27S R13W S14 BT.

A pinon, 10 ins. diameter, bears S. 40½° W., 28 links distant, marked T27S R13W S15 BT.

A pinon, 4 ins. diameter, bears N. 37°45' W., 70 links distant, marked T27S R13W S10 BT.

Land, rough mountainous; general SW. and E. exposures and drainage from divide of San Francisco Range.  
Soil, rocky; of quartzite, limestone and granite formations, with shallow gravelly clay; 4th rate.  
Timber, medium dense cedar and pinon.  
Undergrowth, sage and bitter brush.  
Grazing, poor to fair.

N. 89°57' E., on random line, between sections 11 and 14. for visible signal at the corner of sections 13 and 14.

40.00 Set temporary section corner.

80.00 The corner of sections 11 and 12, heretofore described. For description, see line between sections 11 and 12.

Thence between sections 12 and 14.

80.88 Intersect the restored corner of sections 13 and 14, heretofore described.

Thence,

S. 89°57' W., on true line, between sections 12 and 14.

Over rolling mountainous land, through medium dense timber and short undergrowth; gently ascend along S. slope to corner of sections 11 and 12.

0.15 Intersect line 4-1, Survey No. 5199, Scorpion No. 1 lode, at N. 55°55' E., 14.935 chains distant from corner No. 4.

0.88 The corner of sections 11 and 12.

Thence between sections 11 and 14, with new measurement counting distances from corner of sections 11 and 12.

SUBDIVISION OF T. 27 S., R. 13 W.

Chains	
2.60	Small draw near head, 10 ft. below corner, drains S. 30° E.; ascend E. slope 30 ft.
6.00	Low spur, slopes S.; thence along gradual SW. slope descending 50 ft.
12.20	Shallow draw, drains S.; begin ascent over rolling SE. slope.
24.30	Small draw; drains S.
33.50	Quartzite outcrop, 30 ft. high, on line, on low spur, slopes SE.
35.60	Small draw, drains S. 30° E.
36.07	Intersect line 2-3, Survey No. 4709, Excelsior No. 3 lode, at N. 26° 22' W., 2.425 chains distant from Corner No. 2, identical with Corner No. 3, Survey No. 4709, Excelsior No. 4 lode, a pine post, 4 ins. squared, firmly set, and properly marked.
40.00	On E. slope, 240 ft. above section corner.  Set an iron post, 3 ft. long, 1 in. diameter, 6 ins. in the ground to rock, and supported in a mound of stone, to top, for section corner, with brass cap marked
	$\frac{S11}{\frac{1}{4}}$ $S14$ 1939
	from which
	A pinon limb, 6 ins. diameter, bears S. 63½° W., 165 links distant, marked $\frac{1}{4}$ S14 BT.
	A pinon, 6 ins. diameter, bears N. 58° W., 122 links distant, marked $\frac{1}{4}$ S11 BT.
43.00	Low spur, 40 ft. above the $\frac{1}{4}$ section corner, projects S.; gradually descend along S. slope.
44.50	Small draw, drains S.
45.86	Intersect line 2-1, Survey No. 5205, Hesperides lode, at S. 75° 16' E., 1.937 chains distant, from Corner No. 2, identical with Corner No. 1, Ruby Mine lode, same survey, a pine post, 4 ins. squared, firmly set and properly marked
46.40	Low spur, slopes S.; continue along steep broken S. slope.
66.554	Intersect line 2-3, Survey No. 4709, Copperopolis No. 6 lode, at N. 26° 22' W., 4.83 chains distant from Corner No. 2, a pine post, 4 ins. square, firmly set and properly marked
73.50	Draw, near head, drains S. 60° E.; ascend abrupt NE. slope 240 ft. to
80.00	The corner of sections 10, 11, 14, and 15, 615 ft. above the $\frac{1}{4}$ section corner.

SUBDIVISION OF, T. 27 S., R. 13 W.

Chains

Land, rolling and rough mountainous; general S. and SE. exposures and drainage.  
 Soil, rocky and gravelly clay; 3rd to 4th rates.  
 Timber, cedar and pinon.  
 Undergrowth, sage and bitter brush.  
 Grazing, fair.

N. 0°01' W., bet. sections 10 and 11.

Over rough mountainous land, through medium dense timber and scattered undergrowth; descend along steep E. slope, 40 ft. to

- 5.50 Saddle in main divide ridge, bears N. 80° E. and S. 80° W.; descend steep N. slope.
- 12.70 Gulch, near head, 260 ft. below divide, drains NE.; thence along abrupt broken E. slope, descending.
- 13.18 Intersect line 2-1, Survey No. 4709, Copperopolis No. 5 lode at N. 63°38' E., 3.14 chains distant. from Corner No. 2, sawed pine post, 4 ins. square, firmly set and properly marked
- 23.10 High point, on E. slope, bears E. about 3 chains to end.
- 33.50 Begin abrupt descent over NE. slope.
- 40.00 On steep E. slope, in draw draining NE., 860 ft. below section corner.  
  
 Set an iron post, 3 ft. long, 1 in. diameter, 15 ins. in the ground to rock, and supported in a mound of stone to top, for  $\frac{1}{4}$  sec. corner, with brass cap marked  
  

$\frac{1}{4}$   
 S10 | S11  
 1939  
 from which  
 A pinon, 12 ins. diameter, bears S. 17° E., 39 links distant, marked  $\frac{1}{4}$  S11 BT.  
 A cedar, 5 ins. diam., bears N. 23 $\frac{1}{2}$ ° W., 30 links distant, marked  $\frac{1}{4}$  S10 BT.
- 42.90 Slope changes from abrupt NE. to rolling E. slope.
- 47.00 Begin abrupt descent over N. slope.
- 59.00 Gulch, 360 ft. below the  $\frac{1}{4}$  section corner, drains NW.; ascend steep broken SW. slope 130 ft.
- 65.58 Intersect line 5-6, Survey No. 4753, Townsite Extension lode, at S. 56°24' E., 74 links distant, from Corner No. 5, identical with Corner No. 6, Survey No. 6008, Blackbird No. 2 lode, which is not patented, a pine post, 4 ins. square, firmly set and properly marked
- 67.30 The W. point of spur, from SE., slopes off SW.; descend abrupt N. slope 225 ft.
- 74.70 Deep gulch, drains N. 80° W.; ascend steep S. slope 100 ft. to
- 80.00 On steep S. slope.

## SUBDIVISION OF, T. 27 S., R. 13 W.

## Chains

Set an iron post, 3 ft. long, 2 ins. diameter, 8 ins. in the ground to rock, and supported in a mound of stone to top, for corner of sections 2, 3, 10, and 11, with brass cap marked

T27S	R13W
S3	S2

S10	S11
-----	-----

1939

from which

A pinon, 6 ins. diameter, bears N. 38° E., 91 links distant, marked T27S R13W S2 BT.

A pinon, 8 ins. diameter, bears S. 15½° E., 43 links distant, marked T27S R13W S11 BT.

A cedar, 10 ins. diameter, bears S. 38½° W., 72 links distant, marked S10 BT.

A cedar, 8 ins. diameter, bears N. 22½° W., 55 links distant, marked S3 BT.

Land, high, rough, and mountainous.

Soil, rocky, with shallow gravelly clay; 4th rate.

Timber, medium dense cedar and pinon.

Undergrowth, scattered sage, bitter brush, and Brigham tea.

Grazing, fair to poor.

N. 89°57' E., on random line, between sections 2 and 11.

40.00 Set temporary ¼ section corner.

79.94 Intersect N. and S. line, 9 links N. of the corner of sections 2 and 11.

Thence

N. 89°59' W., on true line, between sections 2 and 11.

Over rough mountainous land, through dense timber and scattering undergrowth; ascend steep E. slope 225 ft.

9.50 High divide ridge, bears N. 30° E. and S. 30° W.; descend gradual W. slope to

12.20 Begin steep descent over W. slope.

31.40 Gulch, 500 ft. below ridge, heads N. about 7 chains distant, drains S. for about 9 chains thence westerly; ascend steep E. slope 200 ft.

38.40 High spur, projects S. 20° W., short distance to end; descend steep SW. slope 40 ft. to

39.97 On steep SW. slope.

Set an iron post, 3 ft. long, 1 in. diameter, 20 ins. in the ground to rock, and supported in a mound of stone to top, for ¼ section corner, with brass cap marked

S2.

¼	—————
	S11

1939

from which

SUBDIVISION OF, T. 27 S., R. 13 W.

Chains

A pinon, 14 ins. diameter, bears S.  $26\frac{1}{2}^{\circ}$  E., 34 links distant, marked  $\frac{1}{4}$  S11 BT.

A pinon, 8 ins. diameter, bears N.  $36^{\circ}45'$  W., 30 links distant, marked  $\frac{1}{4}$  S2 BT.

44.10 Branch gulch, 130 ft. below  $\frac{1}{4}$  section corner, heads N. about 5 chains distant, drains S.  $60^{\circ}$  W.; continue descent along steep general S. slope.

57.00 Slope changes from S. to a steep SW. slope.

62.50 Small branch gulch, drains SW.

75.10 Intersect line 3-4, Survey No. 4709, Cottonwood lode, at N.  $17^{\circ}50'$  E., 0.86 chains distant, from Corner No. 3, identical with Corner No. 3, Pathfinder lode, same survey, and Corners Nos. 1 and 2, Survey No. 6008, Blackbird No. 1 and Blackbird No. 2 lodes, (not patented).

Thence gradually descend along S. slope.

79.94 The corner of sections 2, 3, 10, and 11, 690 ft. below  $\frac{1}{4}$  section corner.

Land, mountainous, general E. and SW. exposures from divide ridge.

Soil, rocky with shallow gravelly clay; 4th rate.

Timber, dense cedar and pinon.

Undergrowth, scattered sage, bitter brush and Brigham tea.

Grazing, poor.

N.  $0^{\circ}01'$  W., on true line, between sections 2 and 3.

Over mountainous land, through medium dense timber and scattered undergrowth; ascend S. slope 40 ft.

1.80 Spur, from E., projects N.  $70^{\circ}$  W.; descend steep broken N. slope.

3.96 Intersect line 1-2, Survey No. 4752, Union lode, at S.  $20^{\circ}30'$  W., 2.60 chains distant from Corner No. 2, which is center of mound, alongside of which was lying, the post; a sawed pine, 4 ins. square, properly marked.

6.00 Enter head of narrow gulch, draining northerly.

7.86 Intersect line 2-3, Survey No. 4752, Union lode, at N.  $31^{\circ}57'$  W., 1.73 chains distant, from corner No. 2.

10.60 Leave bottom of deep narrow gulch, turns N.  $60^{\circ}$  W., 210 ft. below spur; ascend steep broken SW. slope, 250 ft. to spur.

11.13 Intersect line 4-1, Lot 64, Comet lode, at S.  $89^{\circ}41'$  W., 8.42 chains distant, from Corner No. 4, identical with Corner No. 2, Survey No. 6008, Blackbird No. 1 lode.

23.10 Spur, slopes SW.; ascend steep N. slope.

32.50 Gulch, 250 ft. below spur, drains S.  $80^{\circ}$  W.; ascend rolling SW. slope 130 ft. to  $\frac{1}{4}$  section corner.

## SUBDIVISION OF, T. 27 S., R. 13 W.

## Chains

36.50 Ravine, 20 ft. deep, drains W.

40.00 On steep SW. slope.

Set an iron post, 3 ft. long, 1 in. diameter, 20 ins. in the ground to rock, and supported in a mound of stone, for  $\frac{1}{4}$  section corner, with brass cap marked

$\frac{1}{4}$   
S3 | S2  
1939

from which

A cedar, 14 ins. diameter, bears S. 29° E., 39 links distant, marked  $\frac{1}{4}$  S2 BT.

A cedar, 16 ins. diam., bears S. 71 $\frac{1}{2}$ ° W., 46 links distant, marked  $\frac{1}{4}$  S3 BT.

From  $\frac{1}{4}$  section corner S. 30° 48' W., 18.87 chains distant to U. S. M. M. No. 5, which I find to be a rotted stump of a post, buried in the ground, located in center of small mound of stone, (no other evidence of post could be found) witnessed by two pinon bearing trees, NW. and SW., properly marked.

48.20 Shallow draw, drains SW.

54.00 Small draw, drains S. 30° W.; ascend steep SE. slope.

63.80 High spur, 340 ft. above  $\frac{1}{4}$  section corner, projects S. 30° W.; descend along W. slope 75 ft. to

67.30 Intersect the N. boundary of the township, West, 16.06 chains distant from corner of sections 2, 3, 34, and 35, an iron post, 2 ins. diameter, firmly set and properly marked and witnessed as described in official record. As this corner will now function only for sections 34 and 35, T. 26 S., R. 13 W., I destroy marks on post and bearing trees pertaining to sections 2 and 3.

At point of intersection.

Set an iron post, 3 ft. long, 2 ins. diameter, 27 ins. in the ground, and surrounded with a mound of stone to top, for closing corner of sections 2 and 3, with brass cap marked

T26S R13W  
S34  
-----  
S3 | S2  
T27S | R13W  
C C

1939

from which

A pinon, 9 ins. diam., bears S. 35° E., 78 lks. distant, marked T27S R13W S2 CC BT.

## SUBDIVISION OF, T. 27 S., R. 13 W.

## Chains

A pinon, 6 ins. diameter, bears S.  $12\frac{1}{2}^{\circ}$  W., 86 links distant, marked T27S R13W S3 CC BT.

Land, mountainous; general westerly exposure.  
Soil, rocky and gravelly clay; 3rd to 4th rates.  
Timber, cedar and pinon.  
Undergrowth, sagebrush.  
Grazing, fair.

From the corner of sections 26, 27, 34, and 35.

West, on sectional correction line, on random line, for distance, between sections 27 and 34.

40.00 Set temporary  $\frac{1}{4}$  section corner.

80.00 Set temporary corner of sections 27, 28, 33, and 34.

Thence

S.  $0^{\circ}01'$  E., on random line, between sections 33 and 34.

40.00 Set temporary  $\frac{1}{4}$  section corner.

83.53 Intersect the S. boundary of township, 4 links E. of the corner of sections 33 and 34, an iron post, 2 ins. diameter firmly set and properly marked and witnessed as described in official record.

Thence from corner.

N.  $0^{\circ}01'$  W., on true line, between sections 33 and 34.

Over rolling hilly land, through few scattering cedars and short undergrowth; descend NE. slope.

10.00 Draw, at bend, drains NE. from S.  $10^{\circ}$  E.

16.70 Low spur, slopes NE.

21.30 Head of draw, 50 ft. deep, drains NW.

25.00 Recross same spur, slopes N.  $70^{\circ}$  W.; descend N. slope.

30.60 Draw, drains NW.

38.00 Base of rolling hills, bears N.  $70^{\circ}$  W. and S.  $60^{\circ}$  E.; thence gradually descend over rolling desert land facing NW.

43.53 On gentle NW. exposure, 315 ft. below section corner.

Set an iron post, 3 ft. long, 1 in. diameter, 6 ins. in the ground to rock, and supported in a mound of stone to top, for  $\frac{1}{4}$  section corner, with brass cap marked

$\frac{1}{4}$   
S33 | S34

1939

from which

A cedar, 6 ins. diameter, bears S.  $47^{\circ}45'$  E., 329 lks. distant, marked  $\frac{1}{4}$  S34 BT.

A cedar, 7 ins. diameter, bears S.  $21^{\circ}$  W., 142 lks. dist., marked  $\frac{1}{4}$  S33 BT.

49.00 Large wash, 1 chain wide, 3 ft. deep, drains N.  $20^{\circ}$  W.

## SUBDIVISION OF T. 27 S., R. 13 W.

## Chains

- 55.00 Old sheep road, bears N.30°W. and S.30°E.
- 83.53 On rolling desert land, 100 ft. below  $\frac{1}{4}$  section corner.  
Set an iron post, 3 ft. long, 2 ins. diameter, 27 ins. in the ground, for corner of sections 27, 28, 33, and 34, with brass cap marked
- |      |      |
|------|------|
| T27S | R13W |
| S28  | S27  |
| S33  | S34  |
| 1938 |      |
- Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.
- Land, hilly on S. portion, rolling on N. portion; general NW. exposure and drainage.  
Soil, gravelly clay; 3rd rate.  
Timber, few cedars on S.  $\frac{1}{2}$  mile.  
Undergrowth, sage, shadscale and yellow top brush.  
Grazing, fair.
- 
- From the corner of sections 26, 27, 34, and 35.  
West, on true line, on sectional correction line, between sections 27 and 34.
- Over rolling and low hilly land, facing northerly, through short undergrowth; gradually descend NW. slope.
- 8.00 Enter few scattered cedars.
- 27.70 Wash,  $1\frac{1}{2}$  chains wide, 2 ft. deep, 200 ft. below section corner, drains NW. about 2 chains to junction with wash from S.
- 29.00 Dim old road, bears N.20°E. and S.20°W.
- 29.90 Wash, at base of descent, 1 chain wide, 2 ft. deep, drains N.; enter low hills, and leave all timber, bears NW. and S.; ascend E. slope 60 ft.
- 36.60 Top of ascent on N. slope, bears S. and slopes N.; thence along rolling N. slope.
- 37.80 Head of depression on N. slope, 45 ft. below top of ascent, drains N.; ascend 20 ft.
- 40.02 On NE. slope.
- Set an iron post, 3 ft. long, 1 in. diameter, 16 ins. in the ground to rock, and supported in a large mound of stone, for  $\frac{1}{4}$  section corner, with brass cap marked
- |               |     |
|---------------|-----|
| $\frac{1}{4}$ | S27 |
|               | S34 |
| 1938          |     |
- No other accessories available.
- 42.80 Spur, 50 ft. above  $\frac{1}{4}$  section corner, slopes N. about 8 chains distant to end; descend steep W. slope, 175 ft. to
- 55.20 Wash, 20 links wide, 2 ft. deep, at W. base of hills, drains NW.

SUBDIVISION OF T. 27 S., R. 13 W.

Chains

amir.

- 79.20 Wash, 20 links wide, 3 ft. deep, in shallow swale, drains NW.
- 80.04 Intersect the corner of sections 27, 28, 33, and 34.  
 Land, rolling and hilly; general N. to NW. exposure and drainage.  
 Soil, gravelly clay, with scattered rock; 3rd rate.  
 Timber, few scattered cedars on portion of mile.  
 Undergrowth, shadscale, sage and yellow top.  
 Grazing, fair.
- 
- West, on true line, on sectional correction line, between sections 28 and 33.  
 Over rolling desert land, facing N. and NW., through medium dense short undergrowth; slight ascent over N. exposure.
- 19.70 Old sheep road, bears NW. and SE.
- 27.40 Large wash, 1 chain wide, 2 ft. deep, drains N.20°W., from S.
- 34.50 Wash, 20 links wide, 2 ft. deep, at E. base of hilly land, drains N.
- 40.00 On NE. slope, 50 ft. above section corner.  
 Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in the ground, for  $\frac{1}{4}$  section corner, with brass cap marked
- $\frac{1}{4}$   $\frac{S\ 28}{S\ 33}$   
 1938
- Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, N. of corner.
- 44.70 Top of rise on N. slope, 35 ft. above  $\frac{1}{4}$  section corner, bears NE. and SW.; thence along N. slope.
- 48.30 Saddle in spur, from S.10°E., projects NW.  
 ascend SE. slope
- 50.70 S. edge of ledge point, 45 ft. above  $\frac{1}{4}$  section corner, bears N. to high point on spur; descend.
- 52.40 Rocky spur, projects S.30°W.; descend steep W. slope.
- 64.00 W. base of hill, bears N.10°E. and S.; gently descend over rolling land, facing W.
- 70.00 Unimproved road, bears NE. and SW.
- 77.96 Intersect E. boundary of section 29, at N.0°07'E., 5.14 chains from the corner of sections 29 and 32, hereinbefore described.  
 At point of intersection.  
 Set an iron post, 3 ft. long, 3 ins. diameter, 27 ins. in the ground, for closing corner of sections 28 and 33, with brass cap marked

## SUBDIVISION OF T. 27 S., R. 13 W.

Chains

S29	T27S	CC
	S28	
	S33	
	R13W	

1938

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, E. of corner.

Corner stands on slight SW. exposure, 330 ft. below spur.

Land, rolling and hilly.

Soil, gravelly clay and rocky; 3rd to 4th rates.

Timber, none.

Undergrowth, shadscale, sage and yellow top.

Grazing, fair.

From the corner of sections 27, 28, 33, and 34.

N.0°01'W., between sections 27 and 28.

Over gently rolling desert land, facing NW., through medium dense short undergrowth.

- 1.00 Swale, drains N.60°W.
- 4.80 Wash, 30 links wide, 3 ft. deep, drains N.70°W.
- 18.60 Wash, 20 links wide, 3 ft. deep, drains N.60°W.
- 25.00 Wash, 50 links wide, 2 ft. deep, drains W.
- 40.00 On slight W. exposure, 10 ft. below section corner.

Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in the ground, for  $\frac{1}{4}$  section corner, with brass cap mkd.

S28	S27
-----	-----

1939

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of corner.

- 42.50 Unimproved road, bears NE. and SW.
- 51.00 Telephone line, 1 wire, parallel to highway.
- 52.69 Utah Highway No. 21, improved gravelled road, bears N.57°W. and S.57°E., Ely, Nevada, to Milford, Utah.
- 53.60 S. edge of main wash, bears N.60°W. and S.80°E.; thence across bottom, draining N.60°W.
- 60.40 N. edge, 25 ft. below  $\frac{1}{4}$  section corner, bears N.60°W. and S.60°E.
- 61.40 Wash, from N.20°E., drains S.20°W.; gradually ascend rolling SW. exposure, 50 ft. to section corner.
- 80.00 On gentle SW. slope.

Set an iron post, 3 ft. long, 2 ins. diameter, 20 ins. in the ground to rock, and supported in a mound of stone, for corner of sections 21, 22, 27, and 28, with brass cap marked

SUBDIVISION OF T. 27 S., R. 13 W.

Chains

T27S	R13W
S21	S22
S28	S27
1939	

from which

A cedar, 10 ins. diameter, bears S.76 $\frac{1}{2}$ °W., 465 links distant, marked T27S R13W S28 BT

Land, rolling; NW. and SW. exposures.  
 Soil, gravelly clay and stony; 3rd rate.  
 Timber, none.  
 Undergrowth, shadscale, yellow top and sagebrush.  
 Grazing, fair.

East, on random line, between sections 22 and 27.

40.00 Set temporary  $\frac{1}{4}$  section corner.

80.08 Intersect the corner of sections 22, 23, 26, and 27.

Thence

West, on true line, between sections 22 and 27.

Over rolling land, facing SW., through scattering scrub cedars and short undergrowth; descend rocky SW. slope, 65 ft.

5.70 Wash, 20 links wide, 3 ft. deep, in ravine, drains S.; continue gradual descent over SW. slope.

9.10 Power line to King David Mine, bears N.55 $\frac{1}{2}$ °W. and S.55 $\frac{1}{2}$ °E.

16.84 Intersect line 1-4, Survey No. 5986, Emporia No. 8 lode, at S.8°23'W. 7.51 chains distant from Corner No. 1, identical with Corner No. 2 of Drum, and Corner No. 3 of Drum No. 1 lodes, same survey. Cor. point is center of mound stone, lying alongside of which the post, 3 ft. long, 4 ins. square and properly marked, was found.

24.00 Leave all but widely scattered trees.

28.30 Short draw, drains S.

31.90 Unimproved road to King David Mine, bears nearly N. and S.

39.00 Small swale, about 5 chains from head, drains S.20°W.

40.04 On a gradual SE. slope, 240 ft. below section corner.

Set an iron post, 3 ft. long, 1 in. diameter, 15 ins. in the ground to rock, and supported in a mound of stone, for  $\frac{1}{4}$  section corner, with brass cap marked

$\frac{1}{4}$	S22
	S27
1939	

from which

A cedar, 10 ins. diameter, bears N.68°45'E., 300 links distant, marked  $\frac{1}{4}$  S22 BT

61.00 Old railroad grade to Newhouse, bears N.46 $\frac{1}{2}$ °W. and S.46 $\frac{1}{2}$ °E.

61.40 Top of low round knoll, at W. edge of railroad cut.

## SUBDIVISION OF T. 27 S., R. 13 W.

## Chains

- 66.50 Ravine, drains S.30°W.
- 80.08 The corner of sections 21, 22, 27, and 28, 200 ft. below  $\frac{1}{4}$  section corner.
- Land, rolling, with general SW. and S. slopes.  
Soil, coarse gravelly clay and stony; 3rd rate.  
Timber, some scattered scrub cedars.  
Undergrowth, short shadscale, yellow top and bunch grass.  
Fair grazing.

West, on true line, between sections 21 and 28.

Over rolling desert land, sloping SW., through short undergrowth; descend 175 ft. to  $\frac{1}{4}$  section corner.

- 3.00 Small swale, drains SW.
- 15.00 Recross same, drains N.70°W.
- 25.70 Enter main drainage wash, 150 ft. below corner, bears N.70°W. and SE.; thence across wash, draining N.70°W.
- 29.00 Leave same, bears NW. and SE.; thence over gradual NW. slope.
- 40.00 On slight NW. exposure.
- Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in the ground, for  $\frac{1}{4}$  section corner, with brass cap marked

$$\begin{array}{r} \frac{1}{4} \quad S21 \\ \hline S28 \\ 1940 \end{array}$$

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of post.

- 43.80 Utah Highway No. 21, gravelled road, bears N.70°35'W. on tangent across valley, and S.70 $\frac{1}{2}$ °E., about 2 chains to bend, thence more southeasterly; an old road takes off to NW.
- 46.10 Telephone line, 1 wire, parallel to highway.
- 67.80 Wash, 20 links wide, 3 ft. deep, drains N.60°W.
- 78.24 On a gradual NW. exposure, 110 ft. below  $\frac{1}{4}$  section corner. Intersect E. boundary of section 20, N.0°11'W., 5.61 chains distant, from the corner of sections 20 and 29, heretofore described.
- At point of intersection.
- Set an iron post, 3 ft. long, 2 ins. diameter, 27 ins. in the ground, for closing corner of sections 21 and 28, with brass cap marked

$$\begin{array}{r} S20 \quad T27S \\ \hline S21 \quad C \\ S28 \quad C \\ R13W \\ 1939 \end{array}$$

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, E. of corner.

## SUBDIVISION OF T. 27 S., R. 13 W.

## Chains

Land, rolling; general SW. and NW. exposures.  
Soil, stony and gravelly, with sandy clay; 3rd rate.  
Undergrowth, short shadscale and yellow top.  
No timber.  
Fair grazing.

From the cor. of secs. 21, 22, 27, and 28,  
N.0°01'W., between sections 21 and 22.

Over rolling desert land, facing nearly W., through short  
undergrowth; slight ascent of 55 ft. to  $\frac{1}{4}$  section corner.

- 1.50 Swale, drains SW.
- 10.50 Wash, 20 links wide, 2 ft. deep, drains S.70°W.
- 25.80 Old railroad grade to Newhouse, on curve, bears N.49°W.  
and S.31°E.
- 29.30 Unimproved road, bears NE. and SW.
- 31.80 Wash, 50 links wide, 1 ft. deep, drains SW.
- 40.00 True point for  $\frac{1}{4}$  section corner falls in shallow wash,  
draining SW., where it is impracticable to set a perman-  
ent corner, therefore at
- 40.30 Set an iron post, 3 ft. long, 1 in. diameter, 15 ins. in  
the ground to rock, and supported in a mound of stone,  
for witness corner to the  $\frac{1}{4}$  section corner, with brass cap  
marked

	$\frac{1}{4}$	
S21	S22	
	WC	
	1939	

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of  
corner.

Gradually ascend SW. slope, entering hilly land, with  
few scattered cedars.

- 71.37 Intersect line 3-2, Survey No. 5922, ~~Sunbeam Mine No. 1 lode~~  
at N.70°19'E. 4.33 chains distant, from Corner No. 3, a  
hewn cedar post, 3 ft. long, 4 ins. diameter, set in  
mound of stone and properly marked.
- 75.60 Top of ascent, on flat topped spur, 210 ft. above  $\frac{1}{4}$   
section corner, projects W.; descend N. slope 10 ft. to
- 80.00 On a gradual N. slope.
- Set an iron post, 3 ft. long, 2 ins. diameter, 18 ins.  
in the ground to rock, and supported in a mound of stone,  
for corner of sections 15, 16, 21, and 22, with brass  
cap marked.

T27S	R13W
S16	S15
S21	S22
	1939

from which

A pinon, 6 ins. diameter, bears N.55 $\frac{1}{2}$ °E., 54 links  
distant, marked T27S R13W S15 BT

## SUBDIVISION OF, T. 27 S., R. 13 W.

## Chains

A cedar, 8 ins. diameter, bears S. 60°45' E., 216 links distant, marked T27S R13W S22 BT:

A cedar, 5 ins. diameter, bears N. 4½° W., 45 links distant, marked T27S R13W S16 BT.

No suitable tree available. in section 21.

Land, rolling and hilly; general SW. and W. exposures. Soil, gravelly and stony, with shallow sandy clay; 3rd to 4th rates.

Timber, scattered scrub cedar and pinon on N. portion. Undergrowth, shadscale and yellow top and grass. Fair grazing.

East, on random line, between sections 15 and 22.

40.00 Set temporary section corner.

80.10 Intersect N. and S. line, 2 links N. of the cor. of sections 14, 15, 22, and 23.

Thence

N. 89°59' W., on true line, between sections 15 and 22.

Over mountainous land, through scattered timber and short undergrowth; descend 50 ft. over rocky W. slope to

1.40 Draw, drains S. 20° W.; ascend steep broken SE. and E. slopes.

6.40 Short deep gulch, drains S. 30° E.

8.29 Intersect line 1-4, Survey No. 5986, Reciprocity No. 3 lode, at S. 73°10' E., 2.38 chains distant from Corner No. 1, a pine post, 3 ins. square, properly marked and set.

13.90 Top of ascent on high quartzite point, at S. end of spur from N., 290 ft. above draw; descend W. slope.

14.40 Intersect line 8-1, Survey No. 5986, Reciprocity No. 1 lode, at N. 12°30' W., (record is N. 12°03' W.,) 0.69 chains distant from Corner No. 8, identical with Corner No. 3 of Reciprocity No. 2, this survey, a sawed pine post, 4 ins. square, set in a mound of stone and properly marked. Reciprocity No. 2 not patented.

19.81 Intersect line 4-5, Survey No. 5946, Washington No. 6 Mining Claim lode, at N. 63°32' E., 2.94 chains distant from Corner No. 4; a sawed pine post, 4 ins. square, set in a mound of stone and properly marked.

20.90 Top of ledge point, facing W. 130 ft. below top of ascent; descend abrupt W. face.

24.00 Descent becomes less abrupt over W. and SW. slope.

30.70 Head of small draw, drains S. 20° W.

37.14 Intersect line 5-4, Survey No. 6170, Jennie Fraction lode, at S. 44°33' E., 5.26½ chains distant from Corner No. 5, a sawed pine post, 4 ins. square, properly marked

## SUBDIVISION OF, T. 27 S., R. 13 W.

Brigham

Chains

40.05

On gradual SW. slope, 650 ft. below top of ascent on spur.

Set an iron post, 3 ft. long, 1 in. diameter, 6 ins. in the ground to bedrock and supported in a large mound of stone to top, for  $\frac{1}{4}$  section corner, with brass cap marked

S15

S22

1939

from which

A pinon, 6 ins. diam., bears N. 85°15' E., 79 links distant, marked  $\frac{1}{4}$  S15 BT.

A pinon, 10 ins. diameter, bears S. 3°15' E., 28 links distant, marked  $\frac{1}{4}$  S22 BT.

From  $\frac{1}{4}$  section corner U.S.M.M. No. 3, bears N.27°24'W., 28.83 chains (mean of two measurements) distant, a fir post 4 ft. long, 6 ins. diameter, blazed on two sides and scribed USLMNo3 on W. face, firmly set in mound of stone, located on top of high rocky spur, slopes off SW.

From the  $\frac{1}{4}$  section corner U.S.M.M. No. 1 bears N.60°11'E.; and Corner No. 1, Survey No. 5946, Washington No. 2 Mining Claim, bears N.43°34'E. 1.993 chains distant.

Gradually descend rolling SW. slope to section corner.

45.10 Head of draw, drains SW for about 10 chains, thence southerly; continue descent.

54.42 Low spur, 165 ft. below the  $\frac{1}{4}$  section corner, slopes SW.; descend 75 ft. over NW. slope to gulch.

55.96 Intersect line 2-1, Survey No. 5946, Washington No. 5 Mining Claim lode, at S. 41°30' W., 3.14 chains distant from Corner No. 2.

57.15 Intersect line 2-3, Survey No. 5946, Washington No. 8 Mining Claim lode, at N.65°25' W., 0.94 chains distant from Corner No. 3.

62.70 Lobes Gulch, drains SW.; thence along a S. slope to

69.60 Spur, level with gulch, slopes SW.; descend 130 ft. to sec. cor

76.40 Head of small draw, drains NW.; thence along N. slope.

79.18 Intersect line 1-4, Survey No. 5922, Sunbeam Mine lode, at N.19°54'W., 3.657 chains distant from Corner No. 1, identical with Corner No. 6, Sunbeam Mine No. 1 this survey; corner point is center of small mound of stone, post not found.

80.10 The corner of sections 15, 16, 21, and 22.

Land, steep and mountainous; general S. and SW. exposures. Soil, rocky and shallow gravelly clay; 3rd to 4th rates. Timber, scattered cedar and pinon.

Undergrowth, short shadscale, sage, yellow top, and Brigham tea.

Fair grazing.

SUBDIVISION OF, T. 27 S., R. 13 W.

Chains

West, on true line, between sections 16 and 21.


Over rolling mountainous land, through scattering timber and short undergrowth; gradually descend over NW. slope.

188 Intersect line 2-3, Survey No. 5922, Sunbeam Mine lode, at N. 18°38' W., 3.93 chains distant from Corner No. 2, a sawed pine post, 4 ins. square, firmly set and properly marked

16.00 Slope changes from NW. to a SW. slope.

40.00 On W. slope, 370 ft. below section corner.

Set an iron post, 3 ft. long, 1 in. diameter, 12 ins. in the ground to bedrock, and supported in a large mound of stone to top, for section corner, with brass cap marked



Deposit a granite stone, 6 x 6 x 3 ins., marked with a cross (X) at base of post.


Gradually descend W. slope along W. base of mountainous land, 275 ft. to corner.

52.90 Old railroad bed to Newhouse, bears N. 21½° W. and S. 22° E.

77.18 Intersect the E. boundary of section 17, N. 0°24' E., 5.01 chains distant from the corner of sections 17 and 20, heretofore described.

At point of intersection.

Set an iron post, 3 ft. long, 2 ins. diameter, 27 ins. in the ground, for closing corner of sections 16 and 21, with brass cap marked



1939

Raise a mound of stone, 2 ft. base, 1½ ft. high, E. of corner.

Land, mountainous and rolling; general W. slope and drainage.  
 Soil, rocky with coarse gravelly clay and rock; 3rd to 4th rates.  
 Timber, scattered cedar and pinon on E. portion of mile.  
 Undergrowth, short shadscale, black brush, Brighar tea, and bunch grass.  
 Fair grazing.

## Chains

From the corner of sections 15, 16, 21, and 22.

N. 0°01' W., between sections 15 and 16.

Over rough mountainous land, through scattering timber and short undergrowth; descend N. slope 30 ft. to

- 1:10 Small draw, drains W.; ascend steep broken SW. slope.
- 11.20 Spur, 150 ft. above draw, projects SW.; descend steep N. slope 70 ft.
- 11.48 Point from which Corner No. 4, Survey No. 6482, Relief lode, bears N. 35°41' W., 1,844 chains distant, a sawed pine post, 4 ins. square, firmly set and properly marked.
- 13.00 Short deep gulch, drains S. 70° W.; ascend steep S. slope 70 ft.
- 17.00 Spur, projects S. 80° W.; descend NW. slope 50 ft.
- 19.90 Gulch, drains SW.; ascend 60 ft.
- 27.00 Spur, slopes W.; descend 30 ft.
- 28.67 Intersect line 2-3, Survey No. 5946, 022 Mining Claim lode, at S. 83°08' E.; 6.48 chains distant from Corner No. 2, identical with Corner No. 3 Cupric Mhg. Claim; and Corner No. 4, Harrison lodes, same survey, a pine post, conforming to the record.
- 29.40 A main gulch, drains S. 70° W.; ascend steep SW. slope 60 ft.
- 32.10 Old mine shaft and dump, bears E. of line,  $\frac{1}{2}$  chain distant.
- 36.80 Rise, slopes W.; descend 15 ft.
- 38.10 Depression, drains SW.; ascend 10 ft. to corner.
- 40.00 On SE. slope, in small depression.

Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in the ground, and surrounded with a mound of stone, for  $\frac{1}{4}$  section corner, with brass cap marked

$\frac{1}{4}$   
 S16 | S15  
 1939

from which

A cedar, 8 ins. diameter, bears N. 13 $\frac{1}{2}$ ° E., 176 links distant, marked  $\frac{1}{4}$  S15 BT.

A pinon, 8 ins. diameter, bears S. 22°45' W., 89 links distant, marked  $\frac{1}{4}$  S16 BT.

Ascend SW. slope 155 ft. to

- 52.20 High spur, projects S. 80° W. for 2 chains, thence more southerly; descend steep N. slope 110 ft.

## Chains

- 57.70 Gulch, drains S.80°W.
- 59.90 Gulch, drains S.40°W. 2 chains to junction with above gulch; ascend 170 ft. over rocky SW. slope.
- 66.60 High spur, slopes S.60°W.; thence along rocky W. slope.
- 68.00 Begin descent over NW. slope.
- 76.60 Gulch, 220 ft. below spur, drains W.; ascend 30 ft.
- 78.30 Low spur, slopes W. 3 chains to end; descend 25 ft.
- 79.00 Gulch, drains SW. 4 chains to junction; ascend 35 ft.
- 80.00 On steep, rocky SW. slope.

Set an iron post, 3 ft. long, 2 ins. diameter, over cross in solid rock, 36 ins. in a large mound of stone, for corner of sections 9, 10, 15, and 16, with brass cap marked

T27S	R13W
S9	S10
S16	S15
1939	

from which

A pinon, 10 ins. diameter, bears S.33 $\frac{1}{4}$ °E., 52 links distant, marked T27S R13W S15 BT

A cedar, 8 ins. diameter, bears S.40°45'W., 66 links distant, marked T27S R13W S16 BT

A pinon, 7 ins. diameter, bears N. 6 $\frac{1}{2}$ °W., 95 links distant, marked T27S R13W S9 BT

No suitable tree available in section 10.

Land, rough mountainous, general SW. and W. slope of mountain; drainage W.

Soil, rocky, with shallow clay and gravel; 4th rate. Timber, scattered scrub cedar and pinon.

Undergrowth, sage, shadscale, Brigham tea and black brush. Fair grazing.

---

S.89°59'E., on random line, between sections 10 and 15.

40.00 Set temporary  $\frac{1}{4}$  section corner.

79.96 Intersect the corner of sections 10, 11, 14, and 15.

Thence

N.89°59'W., on true line, between sections 10 and 15.

Over rough mountainous land, through medium dense timber and short scattered undergrowth; ascend steep NE. slope 160 ft. to

4.50 Divide ridge, bears N. and S.; descend abrupt NW. slope 680 ft.

27.20 Gulch, heads S. 5 chains, drains N.10°W.; thence along abrupt rocky N. and NE. slopes.

39.98 On a steep NE. slope, 680 ft. below divide.

SUBDIVISION OF T. 27 S., R. 13 W.

Chains

Set an iron post, 3 ft. long, 1 in. diameter, 18 ins. in the ground to rock, and supported in a mound of stone, for  $\frac{1}{4}$  section corner, with brass cap marked

$\frac{1}{4}$   $\frac{S10}{S15}$   
1939

from which

A pinon, 7 ins. diameter, bears N.86°E., 26 links distant, marked  $\frac{1}{4}$  S10 BT

A pinon, 6 ins. diameter, bears S.9 $\frac{1}{2}$ °E., 16 links distant, marked  $\frac{1}{4}$  S15 BT

45.00 Spur, 35 ft. above  $\frac{1}{4}$  section corner, projects N.30°W.; descend along N. and NW. slopes.

62.20 Spur, from S.80°E., slopes W.; thence along top to

73.00 Leave spur, slopes S.80°W.; descend NW. slope.

77.80 Gulch, 1240 ft. below spur at 45 chains, drains S.80°W.; ascend 25 ft. to

79.96 The corner of sections 9, 10, 15, and 16.

Land, rough mountainous.  
Soil, rocky, of granite formation; 4th rate.  
Timber, cedar and pinon.  
Undergrowth, scattered sage, shadscale, black brush and Brigham tea.  
Fair grazing.

West, on true line, between sections 9 and 16.

Over mountainous land, through short undergrowth and few scattered cedars; descend SW. slope 210 ft. to

11.80 Gulch, drains N.70°W.; continue more gradual descent over general westerly slope.

40.00 On a gradual SW. slope, 490 ft. below section corner.

Set an iron post, 3 ft. long, 1 in. diameter, 25 ins. in the ground, and surrounded with a mound of stone, for  $\frac{1}{4}$  section corner, with brass cap marked;

$\frac{1}{4}$   $\frac{S9}{S16}$   
1939

Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, N. of corner; descend 280 ft. to

76.90 Intersect E. boundary of section 8, N.0°15'E. 4.88 chains distant, from corner of sections 8 and 17, heretofore described.

At point of intersection,

Set an iron post, 3 ft. long, 2 ins. diameter, 27 ins. in the ground, for closing corner of sections 9 and 16, with brass cap marked

## SUBDIVISION OF, T. 27 S., R. 13 W.

Chains

T27S
S9 C
816 C
R13W
1939

Raise a mound of stone, 2 ft. base, 1½ ft. high, E. of corner.

Land, mountainous; general westerly exposure and drainage. Soil, rocky and shallow gravelly clay; 3rd to 4th rates. Timber, few scattered cedar and pinon on E. portion. Undergrowth, shadscale, black brush, Brigham tea and grass. Fair grazing.

From the corner of sections 9, 10, 15, and 16.

N. 0°01' W., between sections 9 and 10.

Over rough mountainous land, with general westerly slope, through few scattered cedar and pinon, and short undergrowth; ascend SW. slope, 50 ft. to

- 2.90 Low spur, slopes W.; descend NW. slope 55 ft.
- 6.00 Head of small draw, drains W.; ascend steep SW. slope 120 ft.
- 9.00 Spur, projects W. for 2 chains, thence NW.; descend NW. slope, 175 ft.
- 16.10 Gulch, drains S. 70° W., for about 5 chains, thence NW.; ascend abrupt SW. slope.
- 21.00 Slope changes to a W. slope.
- 29.90 Spur, 350 ft. above gulch, slopes W.; descend NW. slope, 50 ft.
- 32.00 Head of gulch, drains W.; ascend steep SW. slope 120 ft. to.
- 38.20 High rocky spur, from S. 60° E., slopes N. 30° W.; descend NE. slope 75 ft. to
- 40.00 On steep NE. slope.

Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in the ground, and surrounded with a mound of stone, for ¼ section corner, with brass cap marked

½
S9   S10
1939

from which

A pinon, 4 ins. diameter, bears S. 51°45' W., 53 links distant, marked only BT.

- 53.20 Gulch, 475 ft. below ¼ section corner, drains N. 70° W.; ascend SW. slope 75 ft.
- 59.20 Spur, slopes W.; descend along W. slope 140 ft.
- 71.20 A main gulch, drains W.; ascend steep S. slope 190 ft.
- 72.67 Intersect line 4-3, Survey No. 4611, Estelle lode; at N. 63°41' E., 7.34 chains distant from Corner No. 4.

SUBDIVISION OF T. 27 S., R. 15 W.

Chains

80.00 On steep S. slope.

Set an iron post, 3 ft. long, 2 ins. diameter, 24 ins. in the ground, and surrounded with a mound of stone to top, for corner of sections 3, 4, 9, and 10, with brass cap marked

T27S	R13W
------	------

S4	S3
----	----

S9	S10
----	-----

1959

from which

A cedar, 16 ins. diameter, bears S. 72½° E., 224 lks. distant, marked T27S R13W S10 BT.

A cedar, 8 ins. diameter, bears S. 23½° W., 142 lks. distant, marked BT only.

No other suitable trees within limits.

Land, rough mountainous; general westerly slope and drainage.

Soil, rocky, with shallow gravelly clay; 3rd to 4th rates.

Timber, few scattered scrub cedar and pinon.

Undergrowth, scattered sage, black brush, and yellow top.

Fair grazing.

S. 89°59' E., on random line, between sections 3 and 10.

40.00 Set temporary ¼ section corner.

80.06 Intersect the N. and S. line, 2 links N. of the corner of sections 2, 3, 10, and 11.

Thence

N. 89°58' W., on true line, between sections 3 and 10.

Over rough mountainous land, through medium dense timber and short scattered undergrowth; descend along steep S. slope.

1.48 Intersect line 1-2, Survey No. 4752, Union lode, at S. 20°30' W., 6.82 chains distant from Corner No. 2, heretofore described, and at N. 20°30' E. 71 links distant from Corner No. 5, of Blackbird No. 1, and Corner No. 3, of Blackbird No. 2, Survey No. 6008, unpatented.

13.00 A main gulch, 240 ft. below section corner, drains N. 30° W.; ascend steep broken NE. slope.

15.42 Intersect line 2-3, Survey No. 4755, Townsite lode, at N. 33°10' W., 6.80 chains distant from Corner No. 2, a pine post conforming to the record.

19.26 Intersect line 3-2, Survey No. 4611, Boston lode, at S. 20°37' W., 3.98 chains distant from Corner No. 3, a pine post, 4 ins. square, conforming to the record.

28.60 High ridge, 390 ft. above gulch, bears S. 10° E. and N. 10° W., for 4 chains, thence more westerly; descend steep NW. slope.

34.10 Small draw, heads SE. about 3 chains distant, 175 ft. below ridge, drains NW. for about 4 chains, thence westerly; continue descending along northerly slope.

## SUBDIVISION OF, T. 27 S., R. 13 W.

Chains

40.03

On steep N. slope, 260 ft. below ridge.

Set an iron post, 3 ft. long, 1 in. diameter, 24 ins. in the ground, and surrounded with a mound of stone, for  $\frac{1}{4}$  section corner, with brass cap marked

S3  
 $\frac{1}{4}$  S10  
 1939

from which

A pinon, 6 ins. diameter, bears N. 13° E., 34 links distant, marked  $\frac{1}{4}$  S3 BT.

A pinon, 10 ins. diameter, bears S. 25 $\frac{1}{2}$ ° E., 32 links distant, marked  $\frac{1}{4}$  S10 BT.

44.40

Short draw, 70 ft. below the  $\frac{1}{4}$  section corner, drains N. about 3 chains distant to gulch.

60.25

Gulch, 325 ft. below the  $\frac{1}{4}$  section corner, drains S. 20° W.; for  $\frac{1}{4}$  chains, thence westerly; ascend along abrupt broken S. slope.

62.40

Top of ascent on S. slope, 40 ft. above gulch, slopes S.; begin gradual descent along S. slope.

66.31

Intersect line 2-1, Survey No. 5393, Burro No. 5 Lode Mining Claim, at S. 0°45' E., 5.17 chains distant from Corner No. 2, a pine post, conforming to the record.

66.59

Intersect line 3-2, Survey No. 4611, Estelle lode at N. 20°37' E., 0.865 chains distant from Corner No. 3.

71.00

Sharp rocky point on S. slope; begin steeper descent.

80.00

The corner of sections 3, 4, 9, and 10, 520 ft. below  $\frac{1}{4}$  section corner.

Land, rough and mountainous.

Soil, rocky, with shallow gravelly clay; 4th rate.

Timber, cedar and pinon.

Undergrowth, shadscale, sage, black brush, and Brigham tea. Fair grazing.

West, on true line, between sections 4 and 9.

Over mountainous land, through few scattered trees and short undergrowth; gradually descend along steep S. slope.

2.50

Begin descent over S. slope.

2.69

Intersect line 1-4, Survey No. 4611, Estelle lode, at S. 20°37' W., 0.75 chains distant from Corner No. 1.

3.35

Intersect line 4-1, Survey No. 4611, Tunnel lode, at S. 53°37' W., 1.18 chains distant from Corner No. 4.

7.60

Spur, 65 ft. below section corner, from N. 70° E. slopes S. 80° W.; descend SW. slope.

15.20

Depression on S. slope, 150 ft. below spur, heads 2 chains N. in saddle, drains S.; thence along S. slope.

15.92

Intersect line 4-1, Survey No. 5394, Sun lode, at N. 68°48' W., 6.202 chains distant from Corner No. 4.

16.09

Intersect line 2-3, Survey No. 4877, Midvale Placer, at N. 0°25' W., 1.29 chains distant from point for Corner No. 3, determined through record tie of N. 80°52' W., 297.8 ft. from Corner No. 4, Survey No. 5394, Sun lode. Corners

## SUBDIVISION OF, T. 27 S., R. 13 W.

- Chains  
Nos. 2 and 3 are missing.
- 20.90. Begin descent over SW. slope.
- 30.00 Old railroad grade, and base of mountainous land, bears NW. and SE.; thence gradually descend over rolling land, sloping SW.
- 40.00 On gradual SW. slope, 500 ft. below section corner.  
Set an iron post, 3 ft. long, 1 in. diameter, 20 ins. in the ground, and surrounded with a mound of stone, for  $\frac{1}{4}$  section corner, with brass cap marked
- |               |
|---------------|
| S4            |
| $\frac{1}{4}$ |
| S9            |
- 1939
- Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.
- Dim old road bearing W. and S.  $70^\circ$  E., bears S. of corner, 15 links distant.
- 45.00 Unimproved road to Copper Gulch, bears NE. and SW.; also junction of old road from E.
- 49.00 Wash, 50 links wide, 3 ft. deep, drains SW.
- 56.13 Intersect line 1-7, Survey No. 4877, Midvale Placer, at South, 7.30 chains distant from Corner No. 1, a sawed pine post, 4 ins. square, firmly set, and properly marked
- 70.70 Wash, 50 links wide, 3 ft. deep, drains SW.
- 76.18 Intersect the E. boundary of section 5, North, 4.92 chains distant from corner of sections 5 and 8, heretofore described.
- At point of intersection.
- Set an iron post, 3 ft. long, 2 ins. diameter, 27 ins. in the ground, for closing corner of sections 4 and 9, with brass cap marked
- |       |
|-------|
| T27S  |
| S4 C  |
| S5    |
| S9 C  |
| R13W. |
- 1939
- Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, E. of corner.
- Land, mountainous, with general S. and SW. exposures on E. 30 chains; rolling desert land sloping SW. on remainder. Soil, rocky, gravel and shallow clay; 3rd and 4th rates. Timber, few scattered cedars on E. end of mile. Undergrowth, shadscale, black brush and Brigham tea. Fair grazing.

From the cor. of sections 3, 4, 9, and 10.

N.  $0^\circ 01'$  W., on true line, between sections 3 and 4

SUBDIVISION OF, T. 27 S., R. 13 W.

Chains

Over mountainous land, through few scattered scrub cedar and pinon and short undergrowth; ascend S. slope 15 ft.

1.20 Ridge, bears N. 80° E. and S. 80° W.; descend NW. slope 70 ft.

5.60 Small draw, drains S. 80° W.; ascend SW. slope 115 ft.

14.00 Spur, projects NW.; descend N. slope, 210 ft.

22.50 Copper Gulch, drains S. 85° W.; old road in bottom, bears E. and W.; ascend SW. slope.

35.00 Low bench spur, 70 ft. above gulch, slopes W.; descend 15 ft.

40.00 On gradual NW. slope.

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to rock, and supported in a mound of stone to top, for 1/4 section corner, with brass cap marked



Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of corner.

41.50 Draw, 15 ft. below the 1/4 section corner, drains W.; ascend broken S. and SW. slopes 160 ft.

52:30 Intersect line 2-3, Survey No. 5827, Mascot lode, at S. 68° 46' E., 8.96 chains distant from Corner No. 2, a pine post, conforming to the record.


57.00 Spur, projects W. for about 5 chains, thence SW.; descend NW. slope 70 ft.

63.60 Head of swale, drains W.; gradually ascend 50 ft. over SW. slope.

67.24 Intersect N. boundary of township, West 16.20 chains distant from corner of sections 3, 4, 33, and 34, an iron post, 2 ins. diameter, properly set, marked and witnessed as described in the official record. As this corner will now function only for sections 33 and 34, T. 26 S., R. 13 W., I destroy marks on post and bearing trees that pertain to sections 3 and 4.

At point of intersection.

Set an iron post, 3 ft. long, 2 ins. diameter, 18 ins. in the ground to rock, and supported by a mound of stone, for closing corner of sections 3 and 4, with brass cap marked



from which

SUBDIVISION OF T. 27 S., R. 13 W.

Chains

A pinon, 5 ins. diameter, bears S. 80 $\frac{1}{2}$ ° E., 312 lks. distant, marked S3 CC BT.

A cedar, 10 ins. diameter, bears S. 29° 45' W., 188 lks. distant, marked T27S R13W S4 CC BT.

Land, mountainous; general westerly exposure and drainage. Soil, stony and gravelly clay; 3rd and 4th rates. Timber, scattered cedar and pinon. Undergrowth, short sage, shadscale and black brush. Fair grazing.

From the corner of sections 5 and 8.

North, on E. boundary of section 5.

Over rolling desert land, facing SW., through short undergrowth; gradually ascending 70 ft. to  $\frac{1}{4}$  section corner.

- 4.92 The closing corner of sections 4 and 9.
- 14.10 Wash, 1 chain wide, 5 ft. deep, drains SW.
- 21.90 Wash, 50 links wide, 6 ft. deep, drains W.
- 31.00 Wash, 1 chain wide, 6 ft. deep, drains W. for 2 chains, thence SW.
- 33.60 Old railroad grade, bears NW. and SE.
- 37.50 Wash, 50 links wide, 5 ft. deep, drains W.
- 40.00 Set an iron post, 3 ft. long, 1 in. diameter, 15 ins. in the ground to rock; broken glass deposited at base of post, and supported in a mound of stone; for  $\frac{1}{4}$  section corner, on E. boundary of section 5, with brass cap marked

$\frac{1}{4}$   
S5

1939

Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, W. of corner.

- 44.92 Northing of 40.00 chains from closing corner of sections 4 and 9.

Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in the ground, with broken glass deposited at base of post, for  $\frac{1}{4}$  section corner on W. boundary of section 4, with brass cap marked

$\frac{1}{4}$   
S4

1939

Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, E. of corner.

Descend 25 ft. to

- 48.60 Wash, 1 $\frac{1}{2}$  chains wide, in ravine 20 ft. deep, main drainage from Copper Gulch, drains W.; thence along a gradual westerly slope.
- 57.40 Ravine, 15 ft. deep, drains W.

## SUBDIVISION OF T. 27 S., R. 13 W.

## Chains

69.90 Ravine, 20 ft. deep, drains SW.

72.12 Intersect N. boundary of township, West, 12.17 chains distant, from corner of sections 4, 5, 32, and 33, an iron post, 2 ins. diameter, firmly set, properly marked and witnessed as described in official record. As this corner will now function only for sections 32 and 33, T. 26 S., R. 13 W., I efface marks on the post that pertain to sections 4 and 5.

At point of intersection.

Set an iron post, 3 ft. long, 2 ins. diameter, 15 ins. in the ground to rock, and supported in a large mound of stone to top, for closing corner of sections 4 and 5, with brass cap marked

T26S R13W

S32

S5 | S4

T27S R13W

CC

1939

Corner stands on a gradual W. slope, nearly level with  $\frac{1}{4}$  section corner.

Land, rolling desert, sloping SW. and W.

Soil, stony and gravelly; 3rd rate.

No timber.

Undergrowth, short sage, shadscale, yellow top and

Brigham tea.

Fair grazing.

ESTABLISHMENT OF  $\frac{1}{4}$  SECTION CORNERS ON NORTH BOUNDARY

OF T. 27 S., R. 13 W.

From the original  $\frac{1}{4}$  section corner of sections 1 and 36, on S. boundary of T. 26 S., R. 13 W., an iron post, 1 in. diameter, properly set, marked and witnessed. I efface marks on post and bearing tree that pertain to section 1, leaving it the  $\frac{1}{4}$  section corner on S. boundary of section 36, only.

Thence

West, on N. boundary of section 1.

16.08 Point east 40.00 chains distant from closing corner of sections 1 and 2.

Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in the ground, for  $\frac{1}{4}$  section corner on N. boundary of section 1, T. 27 S., R. 13 W., with brass cap marked

$\frac{1}{4}$  S1

1939

from which

A cedar, 8 ins. diameter, bears S.45°E., 62 links distant, marked  $\frac{1}{4}$  S1 BT

A cedar, 10 ins. diameter, bears S.30°W., 18 links distant, marked  $\frac{1}{4}$  S1 BT

ESTABLISHMENT OF 1/4 SECTION CORNERS ON NORTH BOUNDARY  
T. 26 S., R. 13 W.

Chains

Corner stands on a gradual NE. slope.

From the original 1/4 section corner of sections 2 and 35, on S. boundary of T. 26 S., R. 13 W., an iron post, 1 in. diameter, properly set, marked and witnessed, as described in official record. I efface marks on post and bearing tree that pertain to section 2, leaving it on the 1/4 section corner for the S. boundary of section 35, only.

Thence

West, on N. boundary of section 2.

16.07 Midpoint between closing corners of sections 1 and 2, and 2 and 3.

Set an iron post, 3 ft. long, 1 in. diameter, 24 ins. in the ground, and surrounded with a mound of stone to top, for 1/4 section corner, on N. boundary of section 2, T. 27 S., R. 13 W., with brass cap marked

1/4 S2

1939

from which

A pinon, 14 ins. diameter, bears S.60°E., 42 links distant, marked 1/4 S2 BT

A pinon, 14 ins. diameter, bears S.73°W., 54 links distant, marked 1/4 S2 BT

Corner stands on steep SW. slope.

From the original witness 1/4 section corner of sections 3 and 34, on S. boundary of T. 26 S., R. 13 W., an iron post, 1 in. diameter, properly set, marked and witnessed as described in official record. I efface marks on post and bearing tree pertaining to sections 3, leaving it the 1/4 section corner on S. boundary of section 34, T. 26 S., R. 13 W., only. This witness corner is West 2.20 chains distant from the true corner point.

Thence

West, on N. boundary of section 3, counting distance from true corner point.

16.13 Midpoint between closing corners of sections 2 and 3, and 3 and 4.

Set an iron post, 3 ft. long, 1 in. diameter, 8 ins. in the ground to rock, and supported in a mound of stone, for 1/4 section corner on N. boundary of section 3, T. 27 S., R. 13 W., with brass cap marked

1/4 S3

1939

from which

A pinon, 8 ins. diameter, bears S.67 1/2°E., 85 links distant, marked 1/4 S3 BT

ESTABLISHMENT OF  $\frac{1}{4}$  SECTION CORNERS ON NORTH BOUNDARY  
OF T. 27 S., R. 13 W.

Chains

A cedar, 7 ins. diameter, bears S.51°W., 83 links distant, marked  $\frac{1}{4}$  S3 BT

Corner stands on steep S. slope.

From the original  $\frac{1}{4}$  section corner of sections 4 and 33 on S. boundary of T. 26 S., R. 13 W., an iron post, 1 in. diameter, properly set, marked and witnessed, as described in official record. I efface marks on post pertaining to section 4, leaving it the  $\frac{1}{4}$  section corner on S. boundary of section 33, only.

Thence

West, on N. boundary of section 4.

16.20 Point west 40.00 chains from closing corner of sections 3 and 4.

Set an iron post, 3 ft. long, 1 in. diameter, 18 ins. in the ground, and supported in a mound of stone to top, for  $\frac{1}{4}$  section corner on N. boundary of section 4, T. 27 S., R. 13 W., with brass cap marked

$\frac{1}{4}$  S4  
1939

Deposit a granite stone, 9x6x3 ins., marked with a cross, at base of post.

Corner stands on gentle W. slope.

From the original  $\frac{1}{4}$  section corner of sections 5 and 32 on S. boundary of T. 26 S., R. 13 W., an iron post, 1 in. diameter, properly set, marked and witnessed, as described in official record. I efface marks on post pertaining to section 5, leaving it the  $\frac{1}{4}$  section corner on S. boundary section 32, only.

Thence

West, on N. boundary of section 5.

12.17 Point midway between closing corners of sections 4 and 5, and sections 5 and 6.

Set an iron post, 3 ft. long, 1 in. diameter, 27 ins. in the ground, for  $\frac{1}{4}$  section corner on N. boundary of section 5, T. 27 S., R. 13 W., with brass cap marked

$\frac{1}{4}$  S5  
1939

Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, S. of corner.

Corner stands on a gentle NW. slope.

ESTABLISHMENT OF  $\frac{1}{4}$  SECTION CORNERS ON NORTH BOUNDARY  
OF T. 27 S., R. 13 W.

Chains

From the original  $\frac{1}{4}$  section corner of sections 6 and 31, on S. boundary of T. 26 S., R. 13 W., an iron post, 1 in. diameter, properly set, marked and witnessed, as described in official record. I efface marks on post that pertain to section 6, leaving it the  $\frac{1}{4}$  section corner on S. boundary section 31, only.

Thence

West, on N. boundary of section 6.

12.17 Point west, 40.00 chains distant from closing corner of sections 5 and 6.

Set an iron post, 3 ft. long, 1 in. diameter, 22 ins. in the ground to rock, and supported in a mound of stone, for  $\frac{1}{4}$  section corner on N. boundary of section 6, T. 27 S., R. 13 W., with brass cap marked

$\frac{1}{4}$  36

1939

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, S. of corner.

Corner stands on gentle W. slope.

GENERAL DESCRIPTION

This township contains rough and rolling mountains to nearly level desert lands. The south end of the San Francisco mountains extends into the township in a southerly direction. A divide enters the north boundary in section 2, and extends south to about the center of section 23. Rough hills are located in the southeast corner of the township. The western portion is sloping desert or valley, the land facing west into Wah Wah Valley. The mountainous portion is covered in general with a scattering to medium dense growth of scrub cedar and pinon pine timber; the desert portion has a medium growth of short shadscale, sage and grass, which affords fair grazing for sheep during the winter months.

The soil on the mountainous land is principally rocky, of limestone, quartz and porphyry formation, with shallow, coarse, gravelly clay, while on the desert it is a coarse, gravelly clay or sandy clay, and can be classed as third to fourth rate throughout.

The only water found within the township is a small seep spring, known as Squaw Spring, located in the NE $\frac{1}{4}$ SW $\frac{1}{4}$  section 26. It has been developed by tunnel into the hillside about 30 feet. It is used for culinary purposes and limited stock watering. Water for use at the Horn Silver mine is piped from Morehouse Spring in T. 26 S., R. 13 W.

The mountainous area appears to be mineralized, and has been extensively prospected. There are numerous patented mining claims located throughout the northeast portion. The Horn Silver mine, located in SE $\frac{1}{4}$  section 23, is the only mine being worked at present.

The old mining town of Frisco, now deserted, is located in SE $\frac{1}{4}$  section 13. The site of the mining town of Newhouse, of which nothing remains but a few foundations, is located in the NW $\frac{1}{4}$  section 8.

The Frisco Branch of the Union Pacific Railroad system between Milford, Utah, and the Horn Silver mine passes through section 24 and a portion of section 23.

## GENERAL DESCRIPTION.

The branch railroad formerly extending to Newhouse has been abandoned and rails removed.

Utah State Highway No. 21, improved gravelled road, between Milford, Utah, and Ely, Nevada, extends through the township in a general easterly-westerly direction from section 13 on the east boundary to section 19 on the west boundary. Several other unimproved roads traverse the township.

There is a house, barn and outbuildings located at Squaw Spring in SW $\frac{1}{4}$  section 26, owner unknown and unoccupied at time of survey.

There are no settlers living in the township.

No indications of coal or oil were noted.

Other than mining operations, the township is suitable only for grazing, it being a fair winter range for sheep.

The magnetic declination is 16°45' E.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GENERAL LAND OFFICE

FIELD ASSISTANTS

NAMES	CAPACITY
Molen Roper	Principal Assistant
Loyal Cortsen	Chainman
Clark Bonner	Chainman
Douglas McArthur	Axeman
Dominick Ardissonne	Axeman
Harold L. Clark	Axeman
Stanley Milner	Axeman
Robert Gemplet	Cornerman
Francis Fowler	Cornerman
Russel Hales	Cornerman
Lawrence E. Alsup	Flagman

## CERTIFICATE OF SURVEYOR

I, Andrew Nelson, Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 29th day of July, 1936, and supplemental special instructions dated September 26, 1938, supplemental instructions received from the district cadastral engineer for Utah, with assignment October 27, 1938 and instructions dated October 25, 1939, I have surveyed made a dependent resurvey of West Boundary and portions of the Subdivision; establishment of quarter section corners on the North Boundary, and Extension Survey completing the Subdivision of Township 27 South, Range 13 West of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in the specific manner described in the foregoing field notes.

Salt Lake City, Utah.  
April 23, 1941.

Andrew Nelson  
 Surveyor

## CERTIFICATE OF APPROVAL

OFFICE OF SUPERVISOR OF SURVEYS,

Denver, Colorado, January 27, 1945.

The foregoing field notes of the survey of Dependent Resurvey of West Boundary, and portions of the Subdivision; establishment of quarter section corners on the North Boundary, and Extension Survey completing the Subdivision of Township 27 South, Range 13 West, Salt Lake Meridian, Utah. executed by Andrew Nelson, Surveyor under special instructions dated September 26, 1938 supplemental instructions dated July 29, 1936, and supplemental special land assignment instructions dated Oct. 27, 1938 & Oct. 25, 1939, having been critically examined, and the necessary corrections made prior to their certification by the engineer, the said field notes, and the survey therein described, are hereby approved.

[Signature]  
 Supervisor of Surveys.

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY that the foregoing transcript of the field notes of the above described surveys in~~  
~~is a true copy of the original field notes on file in the public survey office.~~

[Signature]  
 Supervisor of Surveys.