Volume

#

R0577

ORIGINAL

Form 4–679
(January 1963)

R577

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF THE EAST BOUNDARY

A PORTION OF THE SOUTH BOUNDARY

AND

A PORTION OF THE SUBDIVISION

OF

TOWNSHIP 28 SOUTH, RANGE 9 EAST

Of the SALT LAKE Meridian,

In the State of UTAH.

EXECUTED BY

CRAIG P. SYLVESTER, SUPERVISORY CADASTRAL SURVEYOR

Under special instructions dated August 21, 19 63, which provided for the surveys included under Group Number 466, approved August 22, 1963, and assignment instructions dated September 24, 19 63.

Survey commenced May 19, 19 64

2

DEPT. OF THE INTERIOR
BUR OF LAND MGMT

1966 MAY 12 AM 10 25 .0

RECEIVED
STATE & LAND OFFICE
SALT LAKE CITY, UTAH

INDEX DIAGRAM

Township 28 South, Range 9 East,

6	5	4	3 26	27 2 26	17 1 17	6
7	8	9	10 24	25 11 24	16 12 15	5
18	17	16	15 32	23 14 22	14 13 14	4
19	20	21 37	32 22 31	21 23 20	13 24 12	3
30	29 35	36 28 34	29 27 29	19 26 19	11 25 10	2
31	32	33 33	28 34	18 35 8	9 36 7	2

Dependent Resurvey, East Boundary and Portions
of the South Boundary and Subdivisional lines
Township 28 South, Range 9 East

CHAINS

The east 3 miles of the north boundary were surveyed by A. D. Ferron in 1883, and resurveyed by Elliot Bird in 1940. The west 3 miles were surveyed by Charles F. Moore in 1934. The south boundary was surveyed by A. D. Ferron in 1883, and the west 4 miles resurveyed by Elliot Bird in 1919. The east boundary was surveyed by A. D. Ferron in 1883. The south 2 miles of the west boundary were surveyed by A. D. Ferron in 1883, and resurveyed by R. C. Yundt in 1949. The north 4 miles were surveyed by Charles F. Moore in 1934. The south and east portions of the subdivisional lines were surveyed by A. D. Ferron in 1883, and the southwest portion resurveyed by R. C. Yundt in 1949. The northwest portion of the subdivisional lines were surveyed by Charles F. Moore in 1934.

The following field notes are those of a dependent resurvey of the east boundary, and portions of the south boundary and subdivisional lines of T. 28 S., R. 9 E.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions, 1947, and the Special Instructions dated August 21, 1963.

Corners on the east-west lines were set on the true latitudinal curve. Lines connecting previously established corners were run by random and true method, but for simplification of the record, the random lines are omitted from these field notes.

All lines of this survey were run by direct method where lines were accessible; lines inaccessible were run by traverse or triangulation method. Distances to topography on lines run by traverse and triangulation methods are approximately as scaled from U.S.G.S. topographic sheets. The details of such traverses and triangulations have been thoroughly checked and verified, and in order to simplify the records, the diagrams and reductions are omitted from these field notes.

The directions of the lines of this survey were determined by reference to true meridians established on line by hour angle observations on Polaris. They were carried forward by sustained angulation, being supplemented by numerous other observations on Polaris taken throughout the progress of the survey.

Before restoring lost corners, the lines of the original survey were retraced and a diligent search made for any evidence of the original corners. The rules of proportionate measurement were applied to ascertain the position of the lost corner after every reasonable possibility of finding direct evidence of the corner had been exhausted.

The geographic position for the southeast corner of the township is in latitude 38°19'26.6" N. and longitude 110°52'44.1" W. as determined by traverse from United States Coast & Geodetic Survey Station 8M"Z11 located in sec. 17, T. 28 S., R. 10 E.

The magnetic declination was read at a number of stations throughout the township and the average of the several readings was found to be 15°30' E.

Dependent Resurvey, East Boundary, T. 28 S., R. 9 E.

CHAINS

Reestablishment of the Survey Executed by
A. D. Ferron, Deputy Surveyor, in 1883.

Beginning at the cor. of Tps. 28 and 29 S., Rs. 9 and 10 E., marked by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the record of the concurrent resurvey of the E. bdy. of T. 29 S., R. 9 E.

N. 0°15' E., bet. secs. 31 and 36.

Over broken and barren sandstone, asc. 35 ft. over gentle SW. slope.

40.30 The ¼ sec. cor. of secs. 31 and 36, marked by a mound of sandstone, no visible mkd., (apparently weathered away).

At the corner point

Set an iron post 30 ins. long, 2½ ins.diam., on solid sandstone, over an X, and in a mound of stone, 25 ins. high, with brass cap mkd.

T28S
R9E R10E
¼
S36 | S31
1964

N. 0°08' E., beginning new measurement.

Continue over barren sandstone, desc. 15 ft. along gentle W. slope.

19.50 Small wash, drains W.

33.60 Wash, 3 ft. deep, 20 lks. wide, drains W.

40.02 The cor. of secs. 25, 30, 31 and 36, marked by a sandstone 4x12x18 ins., plainly mkd. 1 notch on S. and 5 notches on N. face.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., on solid sandstone, over an X, and in a mound of stone 4 ft. base, to top, with brass cap mkd.

T28S
R9E R10E

S25 | S30
S36 | S31

1964

Place original stone alongside and W. of iron post.

Land, broken.
Soil, sand and exposed sandstone.
Very little vegetation.

N. 0°08' E., bet. secs. 25 and 30.

Over broken and barren sandstone, asc. 15 ft. along gentle W. slope.

Dependent Resurvey, East Boundary, T. 28 S., R. 9 E.

CHAINS

39.68 The ¼ sec. cor. of secs. 25 and 30, marked by a sandstone 5x8x20 ins., plainly mkd. ¼.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 10 ins. in the ground, in a mound of stone 4 ft. base, to top, with brass cap mkd.

T28S
R9E R10E
¼

S25|S30

1964

Place original stone alongside and W. of iron post.

Corner falls on low brushy rise.

N. 1°52' E., beginning new measurement.

Desc. 45 ft. over gravelly bench land.

40.16 The cor. of secs. 19, 24, 25 and 30, marked by a sandstone 8x12x20 ins., plainly mkd. 2 notches on S. and 4 notches on N. face.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 15 ins. in the ground, in a mound of stone 3 ft. base, to top, with brass cap mkd.

T28S
R9E R10E

S24|S19
S25|S30

1964

Place original stone alongside and W. of iron post.

Land, broken.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, shadscale and scattered bunch grass.

N. 1°10' W., bet. secs. 19 and 24.

Over broken desert land, over sand and exposed sandstone.

5.10 Crest of Fremont River Canyon, bears SE. and N., thence along ledges facing E.

12.60 Crest same rim, on point projecting E. about 3 chs., desc. 240 ft. over ledges facing E. By triangulation, topography scaled.

16.00 Base of ledges in canyon, bears E. and W., desc. 40 ft. over N. slope in canyon bottom.

33.20 Right bank Fremont River, bears E. and W., thence across river flowing eastward.

Dependent Resurvey, East Boundary, T. 28 S., R. 9 E.

CHAINS	
34.80	Left bank same river, bears E. and W., asc. S. slope in canyon bottom.
37.00	Base of steep ascent, bears W. and E. about 5 chs. to end, asc. 100 ft. over steep S. slope of spur. End triangulation.
40.16	Point for the ¼ sec. cor. of secs. 19 and 24, at proportionate distance; there is no remaining evidence of original corner, falls on steep S. slope and cannot be perpetuated. Asc. 30 ft. over S. slope.
40.71	Point selected for the witness ¼ sec. cor. of secs. 19 and 24.
	Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.
	T28S R9E R10E ¼ S24 | S19 W | C 1964
	Witness corner falls on S. edge of spur sloping E., thence over spur.
42.20	Power line, bears NW. and SE.
45.50	N. crest spur, bears W. and curves SE., desc. 120 ft. over ledge N. slope.
48.80	Base steep descent, bears W. and curve SE., asc. 20 ft. up W. side of small hollow.
64.10	Wash, 3 ft. deep, 20 lks. wide, drains SE. about 6 chs. to junction, thence S.
65.30	Highway, hardsurface, U-24, bears SE. and NW. on curve up small draw.
80.32	The cor. of secs. 13, 18, 19 and 24, marked by a sandstone 4x18x18 ins., marked 3 notches on S. and N. faces.
	At the corner point
	Set an iron post 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.
	T28S R9E R10E S13 | S18 S24 | S19 1964
	Place original stone alongside and W. of iron post.
	Land, broken. Soil, sand and exposed sandstone. Timber, none. Undergrowth, shadscale and willows on river bottom.
	N. 0°41' E., bet. secs. 13 and 18.
	Over desert land, asc. 10 ft. in bottom of small draw.

Dependent Resurvey, East Boundary, T. 28 S., R. 9 E.

CHAINS	
14.50	Neilson Wash, drains S. 10° E.
31.30	Base of steep ascent, bears NW. and SE., asc. 110 ft. over ledgy SW. slope.
39.10	Crest of steep ascent on rim, bears NW. and SE., asc. over broken sandstone formation; over an extensive area known as Factory Bench.
40.64	The ¼ sec. cor. of secs. 13 and 18, marked by a sandstone 6x16x30 ins., plainly mkd. ¼.
	At the corner point
	Set an iron post 30 ins. long, 2½ ins. diam., 10 ins. in the ground, in a mound of stone 4 ft. base, to top, with brass cap mkd.
	T28S R9E R10E ¼ S13 | S18 1964
	Place original stone alongside and W. of iron post.
	N. 0°32' E., beginning new measurement.
	Asc. 35 ft. over broken sandstone formation, draining W.
38.60	Crest low rim, bears NE. and curves S., desc. 40 ft. over rim facing NW. into head of small hollow.
40.35	Point for the cor. of secs. 7, 12, 13 and 18, at proportionate distance; there is no remaining evidence of original corner.
	Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T28S R9E R10E S12 | S 7 S13 | S18 1964
	Land, broken. Soil, sand and exposed sandstone. Timber, none. Undergrowth, shadscale and bunch grass.
	N. 0°32' E., bet. secs. 7 and 12.
	Over broken desert land, across sandstone formation, asc. 40 ft. over ledgy rim facing SE., out of head of small gulch.
1.40	Crest of rim, bears NE. and SW., asc. 50 ft. over broken sandstone formation draining SW.
33.20	Small gulch, drains W., about 5 chs. to junction, thence S.
40.35	The ¼ sec. cor. of secs. 7 and 12, marked by a sandstone 6x14x20 ins., plainly mkd. ¼.

Dependent Resurvey, East Boundary, T. 28 S., R. 9 E.

CHAINS	
	At the corner point Set an iron post 30 ins. long, 2½ ins. diam., 10 ins. in the ground, in a mound of stone 4 ft. base, to top, with brass cap mkd. T28S R9E R10E ¼ S12|S 7 1964 Place original stone alongside and W. of iron post.
	N. 0°26' W., beginning new measurement. Continue over broken sandstone formation, draining W.
38.00	Small wash, drains W., about 5 chs. to junction, thence SW.
39.93	The cor. of secs. 1, 6, 7 and 12, marked by a sandstone 8x20x20 ins., plainly mkd. 5 notches on S. and 1 notch on N. face. At the corner point Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R9E R10E S 1|S 6 S12|S7 1964 Place original stone alongside and W. of iron post. Land, broken. Soil, sand and exposed sandstone. Undergrowth, shadscale and scattered bunch grass.
	North, bet. secs. 1 and 6. Over broken desert land, draining W., on Factory Bench.
7.30	Wash, 3 feet deep, 50 lks. wide, drains SW., thence over sandy clay land with patches of exposed sandstone.
40.16	The ¼ sec. cor. of secs. 1 and 6, marked by a sandstone 4x14x18 ins., plainly mkd. ¼. At the corner point Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R9E R10E ¼ S 1|S 6 1964 Place original stone W. of corner.

Dependent Resurvey, East Boundary, T. 28 S., R. 9 E.

CHAINS

N. 0°34' E., beginning new measurement.

Continue over rolling sandy desert land, on Factory Bench.

40.13 The cor. of Tps. 27 and 28 S., Rs. 9 and 10 E., an iron post 3 ins. diam., set, mkd. and witnessed as described in the official record of the resurvey of a portion of the N. bdy. in 1940.

Land, rolling bench.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, scattered shadscale and bunch grass.

Dependent Resurvey, Portion of the South Boundary,
T. 28 S., R. 9 E.

Reestablishment of the Survey Executed by
A. D. Ferron, Deputy Surveyor, in 1883

From the cor. of Tps. 28 and 29 S., Rs. 9 and 10 E.

N. 89°53' W., bet. secs. 1 and 36.

Over broken desert land, draining NW.

17.00 Wash, 3 ft. deep, 20 lks. wide, drains NW.

37.50 Wash, 3 ft. deep, 30 lks. wide, drains N. from SE.

40.30 The ¼ sec. cor. of secs. 1 and 36, marked by a sandstone 10x12x20 ins., plainly mkd. ¼.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R9E

¼ S36 / S 1

T29S R9E

1964

Place original stone alongside and N. of iron post.

N. 89°44' W., beginning new measurement.

Continue over broken desert land.

8.20 Small wash, drains NE.

22.80 E. crest small gulch, bears NW. and SE. irregular, desc. 115 ft. over broken W. slope.

34.00 Wash in bottom of gulch, drains N. irregular, asc. 90 ft. over irregular E. slope.

40.11 Point for the cor. of secs. 1, 2, 35 and 36, at proportionate distance; there is no remaining evidence of original corner.

CHAINS

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R9E

S35	S36
S 2	S 1

T29S R9E

1964

Cor. falls on E. slope of terrace, 15 ft. below top.

Land, broken.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, scattered shadscale and bunch grass.

N. 89°44' W., bet. secs. 2 and 35.

Over broken desert land, asc. 15 ft. over E. slope.

.50 Crest of ascent, bears N. and S. irregular, thence over top of gravelly spur.

2.60 Crest of steep descent, bears N. and S., desc. 160 ft. over irregular W. slope.

17.00 Sweetwater Creek, small stream of water, drains N. irregular, asc. 35 ft. over general E. slope, in canyon bottom.

28.40 Small clay knoll, desc. over W. slope of clay hills in canyon.

40.11 The ¼ sec. cor. of secs. 2 and 35, marked by a sandstone 8x14x20 ins., plainly mkd. ¼.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R9E

	S35
¼	S 2

T29S R9E

1964

Place original stone alongside and N. of iron post.

N. 89°44' W., beginning new measurement.

Asc. 80 ft. over irregular E. slope, in canyon bottom, over clay formation.

27.40 Base of shale ledges, bears NE. and SW., asc. 165 ft. over SE. face of ledges.

30.70 Crest of same ledges, bears NE. and SW., thence over gravelly top of bench.

40.76 The cor. of secs. 2, 3, 34 and 35, marked by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the resurvey of a portion of the S. bdy. in 1919.

CHAINS	
	Land, broken. Soil, sand, clay and exposed sandstone. Timber, none. Undergrowth, very scattered shadscale and bunch grass.
	Dependent Resurvey of a Portion of the Subdivisional lines of T. 28 S., R. 9 E., Salt Lake Meridian, Utah
	Reestablishment of the Survey Executed by A. D. Ferron, Deputy Surveyor, in 1883.
	From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp.
	N. 0°46' E., bet. secs. 35 and 36.
	Over broken desert land, desc. 30 ft. over top of point projecting N.
7.60	Crest of N. end of point, bears SW. and NE. about 10 chs., thence S., desc. 130 ft. over ledgy N. slope, into canyon.
16.50	Sweetwater Creek, small stream of water, drains NE., thence down canyon.
21.60	Drift fence across canyon, bears E. 3 chs., W. 1.50 chs.
22.70	Same creek, drains NW.
33.70	Same creek, drains E., also base of ledgy ascent, bears E. and curves SW., asc. 80 ft. over ledgy S. slope.
37.80	Crest of ledgy S. slope, bears E. and curves SW., asc. 10 ft. over small bench.
40.06	The ¼ sec. cor. of secs. 35 and 36, marked by a sandstone 4x16x24 ins., plainly mkd. ¼.
	At the corner point
	Set an iron post 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R9E ¼ S35|S36 1964
	Place original stone alongside and W. of iron post.
	N. 0°15' E., beginning new measurement.
	Asc. 60 ft. over broken bench, draining eastward.
40.32	The cor. of secs. 25, 26, 35 and 36, marked by a sandstone 10x10x26 ins., plainly mkd. 1 notch on S. and E. faces.
	At the corner point
	Set an iron post 30 ins. long, 2½ ins. diam., on solid sandstone, over an X, in a mound of stone 4 ft. base, 28 ins. high, with brass cap mkd.

Dependent Resurvey, Portion of the Subdivision of T. 28 S., R. 9 E.

CHAINS	
	T28S R9E S26 | S25 S35 | S36 1964 Place original stone alongside and N. of iron post, in mound. Land, broken. Soil, sandy clay and exposed sandstone. Timber, none. Undergrowth, shadscale.
	From the cor. of seds. 25, 30, 31 and 36, on the E. bdy. of the Tp. N. 89°47' W., bet. secs. 25 and 36. Over broken desert land desc. 100 ft. over irregular sandstone formation.
3.80	Small wash, drains NW.
29.10	Crest E. rim of Sweetwater Canyon, bears SW. and N. irregular, desc. 150 ft. over ledgy W. slope.
31.50	Base of steep descent, bears SW. and N. irregular, thence over canyon bottom.
36.70	Sweetwater Creek, dry, drains N. irregular, asc. 15 ft. over E. slope in canyon.
40.16	The ¼ sec. cor. of secs. 25 and 36, marked by a sandstone 6x10x18 ins., no mks. visible. Stone is foreign to this area, but is accepted as best available evidence of the original corner. At the corner point Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R9E ¼ S25 S36 1964 Place old stone alongside and N. of iron post.
	N. 89°57' W., beginning new measurement. Asc. 10 ft. over gentle E. slope in canyon.
8.50	Base of steep ascent, bears N. and S. irregular, asc. 140 ft. over ledgy E. slope.
15.00	Crest of W. rim of Sweetwater Canyon, bears N. and S. irregular, asc. 20 ft. over broken bench, draining SE.
39.84	The cor. of secs. 25, 26, 35 and 36.

Dependent Resurvey, Portion of the Subdivision of T. 28 S., R. 9 E.

CHAINS	
	Land, broken. Soil, sandy clay and exposed sandstone. Timber, none. Undergrowth, shadscale and scattered bunch grass.
	N. 0°10' W., bet. secs. 25 and 26.
	Over broken desert land, asc. 85 ft. over SE. slope.
9.90	Low ridge, bears NE. and SW., desc. 65 ft. over NE. slope.
31.60	Small wash, drains NE., asc. 35 ft. over S. slope.
35.50	Low spur, slopes E., desc. 40 ft. over N. slope.
40.07	The ¼ sec. cor. of secs. 25 and 26, marked by a sandstone 8x20x28 ins., plainly mkd. ¼.
	At the corner point
	Set an iron post 30 ins. long, 2½ ins. diam., on solid sandstone, over an X, in a mound of stone 4 ft. base, to top, with brass cap mkd. T28S R9E ¼ S26 | S25 1964
	Place original stone alongside and W. of iron post.
	N. 0°35' E., beginning new measurement.
	Desc. N. slope.
.50	Bully, drains E., asc. 70 ft. over S. slope.
4.20	Low ridge, bears NE. and SW., desc. 65 ft. over NW. slope.
9.70	Small draw, drains NE., asc. 80 ft. over SE. slope.
12.50	Low spur, slopes NE., desc. 40 ft. over small bench, draining NE.
29.20	Crest low rim, bears SW. and NE., desc. 80 ft. over ledgy N. slope.
32.00	Base of same rim, bears NE. and SW., desc. over small bench, draining N.
40.25	The cor. of secs. 23, 24, 25 and 26, marked by a granite stone 10x10x20 ins., plainly mkd. 2 notches on S. and 1 notch on E. face.
	At the corner point
	Set an iron post 30 ins. long, 2½ ins. diam., 15 ins. in the ground, in a mound of stone 3 ft. base, with brass cap mkd. T28S R9E S23 | S24 S26 | S25 1964

CHAINS	
	Place original stone alongside and W. of iron post. Land, broken. Soil, sandy clay and exposed sandstone. Timber, none. Undergrowth, shadscale and bunch grass.
	From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp. N. 89°29' W., bet. secs. 24 and 25. Over broken desert land, asc. 20 ft. over gentle E. slope, on bench.
11.30	Low spur, slopes S., asc. 30 ft. along S. slope.
22.10	Knoll, about 5 chs. diam., desc. 40 ft. over W. slope of knoll.
24.00	Crest of rim of Fremont River Canyon, bears NE. and S., desc. 250 ft. over ledges facing W. By triangulation.
29.50	Right bank Fremont River, bears N. and curves SW., thence over river.
33.00	Left bank same river, bears N. and S., asc. gentle E. slope, in canyon.
40.59	Point for the ¼ sec. cor. of secs. 24 and 25, at midpoint; there is no remaining evidence of original corner. Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T28S R9E ¼ S24/S25 1964 Raise mound of stone 3 ft. base, 2½ ft. high, N. of corner. Asc. gentle E. slope in canyon bottom.
41.50	Base of steep ascent, bears NE. and curves SW., asc. 120 ft. over ledgy E. slope.
44.00	Crest of rim, bears NE. and curves SW., thence over point projecting S.
55.00	W. crest of point, bears N. and curves SE., desc. 150 ft. over ledgy SW. slope.
64.00	Base of descent, also left bank of Fremont River, bears N. and curves SE., thence over river.
67.50	Right bank of river, also base of steep ascent, bears N. and curves SE., asc. 180 ft. over ledgy E. slope.
75.00	Crest of steep ascent, bears N. and SE., thence over bench. End triangulation.
81.18	The cor. of secs. 23, 24, 25 and 26.

CHAINS	
	Land, broken. Soil, sand and exposed sandstone. Timber, none. Undergrowth, shadscale and bunch grass, willows along river.
	N. 0°17' E., bet. secs. 23 and 24.
	Over desert land on top of small gravelly bench.
13.10	Crest of steep descent, bears E. and SW., desc. 100 ft. over ledgy N. slope, into river canyon. By triangulation.
16.00	Base of steep descent, also right bank of Fremont River, bears E. and NW., thence over river.
19.20	Left bank of river, bears E. and NW., thence over river bottom.
22.30	Base of steep ascent, bears E. and W., asc. 100 ft. over ledgy S. slope.
24.10	Crest of steep ascent on rim, bears E. and W., asc. 40 ft. over gravelly bench. End triangulation.
40.22	Point for the ¼ sec. cor. of secs. 23 and 24, at mid-point; there is no evidence of original corner.
	Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R9E ¼ S23 | S24 1964
	Asc. S. slope of gravelly bench.
48.80	Rise, bears E. and W., desc. 45 ft. over N. slope.
57.20	Wash, 2 ft. deep, 20 lks. wide, drains SW., asc. irregular S. slope on Factory Bench.
58.00	Power Line, bears N. 85° W. and S. 85° E.
69.70	Highway, hard surface, U-24, bears N. 80° E. and S. 80° W.
80.44	The cor. of secs. 13, 14, 23 and 24, determined by a mound of stones foreign to this area, mks. have weathered away; accepted as the best available evidence of the original corner.
	At the corner point
	Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R9E S14 | S13 S23 | S24 1964

Dependent Resurvey, Portion of the Subdivision of T. 28 S., R. 9 E.

CHAINS	
	Land, broken, Soil, sandy clay and exposed sandstone. Timber, none. Undergrowth, shadscale and scattered bunch grass.
	From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp. N. 88°47' W., bet. secs. 13 and 24. Over broken desert land, across bottom of small cove.
3.50	Base of ledgy ascent, bears N. and S., asc. 150 ft. over E. slope.
6.00	Crest of steep ascent, bears N. and S., asc. 20 ft. over gentle E. slope, on Factory Bench.
17.60	Low rise, bears N. and S., desc. 35 ft. over gentle W. slope.
31.60	Shallow swale, drains S., asc. 10 ft. over gentle E. slope.
38.98	The ¼ section cor. of secs. 13 and 24, marked by a sandstone 3x14x20 ins., plainly mkd. ¼. At the corner point Set an iron post 30 ins. long, 2½ ins. diam., on solid sandstone, over an X, in a mound of stone 4 ft. base, to top, with brass cap mkd. T28S R9E ¼ S13/S24 1964 Place original stone alongside and N. of iron post.
	N. 89°41' W., beginning new measurement. Asc. 15 ft. over gentle E. slope.
19.80	Graded dirt road, bears N. 10° W., and S. 10° E., 4 chs. to highway U-24.
28.40	Low rise, bears N. and S., 3 chs. to highway U-24, desc. 35 ft. over W. slope.
40.20	The cor. of secs. 13, 14, 23 and 24. Land, broken. Soil, sand and exposed sandstone. Timber, none. Undergrowth, very scattered shadscale and bunch grass.
	N. 0°18' E., bet. sec. 13 and 14. Over desert land on extensive area known as Factory Bench, asc. gentle S. slope.
19.00	Base low terrace, bears E. and SW., asc. 60 ft. over S. slope.

CHAINS	
28.90	Crest same terrace, bears NW. and SE., thence over rolling bench.
29.00	Graded gravel road, bears NW. and SE.
40.19	The ¼ sec. cor. of secs. 13 and 14, marked by a sandstone 6x10x16 ins., dimly mkd. ¼. At the corner point Set an iron post 36 ins. long, 1 in. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R9E ¼ S14 | S13 1964 Place original stone alongside and W. of iron post.
	N. 0°01' W., beginning new measurement. Continue over nearly level land, on Factory Bench.
40.15	Point for the cor. of secs. 11, 12, 13 and 14, at proportionate distance; there is no evidence of original cor. Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R9E S11 | S12 S14 | S13 1964 Land, rolling. Soil, sandy clay. Timber, none. Undergrowth, very scattered shadscale and bunch grass.
	From the cor. of secs. 7, 12, 13 and 18. N. 89°37' W., bet. secs. 12 and 13. Over broken desert land, on Factory Bench, asc. 35 ft. over E. slope of small ravine.
2.30	Small point, projects S., 5 chs. to end, desc. 30 ft. over W. slope.
4.40	Wash in small ravine, drains S., 5 chs. to junction, asc. 55 ft. over E. slope.
9.70	W. crest of ravine, bears N. and S., thence over barren sandstone formation.
34.90	E. crest of small canyon, bears N. and S. irregular, desc. 150 ft. over ledges facing W.
37.80	Wash in canyon, drains S., asc. 100 ft. over ledgy E. slope.
39.95	Point for the ¼ sec. cor. of secs. 12 and 13, at proportionate distance; there is no evidence of original cor.

Dependent Resurvey, Portion of the Subdivision of T. 28 S., R. 9 E.

CHAINS	
	Set an iron post 30 ins. long, 2½ ins. diam., on solid sandstone, over an X, in a mound of stone 4 ft. base, to top, with brass cap mkd. T28S R9E ¼ S12 / S13 1964
	Cor. falls on shelf of ledgy E. slope.
	Asc. 50 ft. over ledgy E. slope.
42.50	W. crest of small canyon, bears S. and NW., asc. 25 ft. over rolling bench land.
79.90	The cor. of secs. 11, 12, 13 and 14.
	Land, broken E. portion, rolling W. portion. Soil, sandy clay and exposed sandstone. Timber, none. Undergrowth, shadscale and scattered bunch grass.
	N. 0°06' W., bet. secs. 11 and 12.
	Over rolling desert land, on Factory Bench.
14.50	Graded dirt road, bears NE. and SW., asc. 35 ft. over gentle S. slope.
29.50	Rise, bears E. and W., desc. 15 ft. over gentle NE. slope.
40.15	Point for the ¼ sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of original corner.
	Set an iron post 36 ins. long, 1 in. diam., 30 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R9E ¼ S11 | S12 1964
	Desc. 40 ft. over gentle NE. slope.
65.20	Wash, 2 ft. deep, 30 lks. wide, drains SE., asc. 20 ft. over gentle SE. slope.
80.30	The cor. of secs. 1, 2, 11 and 12, marked by a sandstone 4x10x16 ins., mkd. 5 notches on S. and 1 notch on E. face.
	At the corner point
	Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R9E S 2 | S 1 S11 | S12 1964
	Place original stone alongside and W. of iron post.

ent Resurvey, Portion of the Subdivision of T. 28 S., R. 9 E.

CHAINS

Land, rolling.
Soil, sandy clay.
Timber, none.
Very little vegetation.

From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp.

N. 89°37' W., bet. secs. 1 and 12.

Over rolling desert land on Factory Bench, desc. 40 ft.

4.60 Small wash, drains SW.

34.90 Wash in small ravine, drains S. irregular.

36.70 Graded dirt road, bears N. and S. about 5 chs., thence W.

40.11 Point for the ¼ sec. cor. of secs. 1 and 12, at midpoint; there is no evidence of original corner.

Set an iron post 30 ins. long, 2½ ins. diam., 10 ins. in the ground, in a mound of stone 3 ft. base, to top, with brass cap mkd.

T28S R9E

¼ S 1 / S12

1964

Desc. 35 ft. over W. slope of small ravine.

42.90 Wash in small ravine, drains S. irregular.

45.60 Same road, curves SW. and SE., asc. 80 ft. over irregular clay hills draining SE.

69.90 Small wash, drains S. 70° E., asc. 45 ft. over E. slope of clay rise.

80.22 The cor. of secs. 1, 2, 11 and 12.

Land, rolling E. portion, broken W. portion.
Soil, sandy clay.
Timber, none.
Very little vegetation.

N. 0°30' E., bet. secs. 1 and 2.

Over rolling clay hills, draining SE.

40.05 The ¼ sec. cor. of secs. 1 and 2, determined by a mound of black shale foreign to this area, accepted as the best available evidence of the original corner.

At the corner point

Set an iron post 36 ins. long, 1 in. diam., 28 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R9E

¼

S 2 | S 1

1964

Dependent Resurvey, Portion of the Subdivision of T. 28 S., R. 9 E.

CHAINS	
	N. 0°30' E., beginning new measurement.
	Asc. 65 ft. over irregular clay hills, drains SE.
4.00	Wash, 4 ft. deep, 20 lks. wide, drains SE.
39.90	The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., an iron post, set, mkd. and witnessed as described in the official record of the resurvey of a portion of the N. bdy. in 1940.
	Land, rolling. Soil, clay. Timber, none. Very little vegetation.
	From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp.
	N. 1°10' E., bet. secs. 34 and 35.
	Over broken desert land, across a small gravelly bench.
4.50	Crest of steep descent, bears W. and NE., desc. 110 ft. over NW. slope.
10.00	Base of steep descent, bears S. and NE., desc. 45 ft. over irregular clay hills, draining N.
38.22	The ¼ sec. cor. of secs. 34 and 35, marked by a sandstone 6x12x16 ins., mkd. ¼.
	At the corner point
	Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R9E ¼ S34|S35 1964
	Place original stone alongside and W. of iron post.
	N. 1°36' E., beginning new measurement.
	Desc. 25 ft. over clay hills.
16.00	Wash, 2 ft. deep, 30 lks. wide, drains NE., asc. 20 ft. over SE. slope.
25.00	Spur, slopes NE., desc. 25 ft. over NW. slope.
32.10	Small wash, drains NE., asc. 10 ft. over SE. slope, of clay hills.
42.05	The cor. of secs. 26, 27, 34 and 35, marked by a sandstone 6x10x16 ins., marked 1 notch on S. and 2 notches on E. face.
	At the corner point
	Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

Dependent Resurvey Portion of the Subdivision of T. 28 S. R. 9 E.

CHAINS

T28S R9E

S27	S26
S34	S35

1964

Place original stone alongside and W. of iron post.

Land, broken.
Soil, clay.
Timber, none.
Very little undergrowth.

From the cor. of secs. 25, 26, 35 and 36.

N. 89°49' W., bet. secs. 26 and 35.

Over broken desert land, across sandstone formation, asc. 215 ft. over irregular E. slope.

1.00 Leave sandstone, enter blue clay and shale formation.

21.90 Gravel topped ridge, bears N. and S., desc. 95 ft. over W. slope.

30.50 Small wash, drains S. 80° W., from N., asc. 15 ft. over SE. slope.

39.66 The ¼ sec. cor. of secs. 26 and 35, marked by a sandstone 6x12x14 ins., plainly mkd. ¼.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R9E

¼ S26 / S35

1964

Place original stone alongside and N. of iron post.

N. 89°50' W., beginning new measurement.

Asc. 10 ft. over steep SE. slope.

.70 Low spur, slopes SW., desc. 125 ft. over irregular W. slope.

25.30 Wash, 2 ft. deep, 20 lks. wide, drains N., thence over rolling clay spurs, sloping N.

39.76 The cor. of secs. 26, 27, 34 and 35.

Land, broken.
Soil, sandy clay.
Timber, none.
Undergrowth, scattered shadscale.

N. 1°10' W., bet. secs. 26 and 27.

Over broken desert land, asc. 15 ft. over SE. slope of small clay spur.

CHAINS	
.90	Spur, slopes NE., desc. 25 ft. over irregular N. slope.
11.80	Wash, 3 ft. deep, 20 lks. wide, drains NE., asc. 10 ft. over S. slope.
21.60	Base of steep ascent, bears W. and curves NE., asc. 80 ft. over SE. slope.
27.70	Spur, slopes E., desc. 125 ft. over broken NE. slope.
33.80	Ravine, drains NE., asc. 100 ft. over broken S. slope.
39.00	S. crest of bench, bears NE. and SW., thence over gravelly bench.
40.64	The ¼ sec. cor. of secs. 26 and 27, marked by a small mound of sandstone foreign to this area, marks have weathered away; accepted as best available evidence of the original corner.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R9E
¼
S27 | S26
1964

N. 0°34' E., beginning new measurement.

Continue over gravelly bench.

16.00	N. crest of bench, bears E. and W. irregular, desc. 75 ft. over steep N. slope.
20.00	Base of descent, bears E. and W. irregular, desc. 10 ft. over gravel bench.
39.54	The cor. of secs. 22, 23, 26 and 27, marked by a lava stone 6x10x16 ins., plainly mkd. 2 notches on S. and E. faces.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 15 ins. in the ground, in a mound of stone 4 ft. base, to top, with brass cap mkd.

T28S R9E

S22	S23
S27	S26

1964

Place original stone alongside and W. of iron post.

Land, broken.
Soil, sandy gravel and exposed sandstone.
Timber, none.
Undergrowth, heavy growth shadscale on benches.

From the cor. of secs. 23, 24, 25 and 26.

West, bet. secs. 23 and 26.

CHAINS	
	Over gravelly bench land.
9.80	E. rim small canyon, bears N. and SW., desc. 110 ft. over ledgy NW. slope.
16.00	Wash in bottom of canyon, drains NE., asc. 115 ft. over ledgy SE. slope.
21.30	W. rim of same canyon, bears NE. and SW., asc. 10 ft. over gravelly bench.
40.02	The ¼ sec. cor. of secs. 23 and 26, marked by a black lava stone 12x14x20 ins., plainly mkd. ¼.
	At the corner point
	Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.
	T28S R9E ¼ S23/S26 1964
	Place original stone alongside and N. of iron post.
	N. 89°51' W., beginning new measurement.
	Continue over gravelly bench.
28.10	Head of small hollow, about 20 ft. deep, drains N., continue over gravelly bench.
40.08	The cor. of secs. 22, 23, 26 and 27, in head of small hollow.
	Land, rolling bench. Soil, sandy gravel. Timber, none. Undergrowth, shadscale and bunch grass.
	N. 0°20' E., bet. secs. 22 and 23.
	Over gravelly bench land.
18.80	N. crest of bench, bears NE. and SW., desc. 110 ft. over NE. slope.
23.50	Base of steep descent, bears NE. and SW., thence over river bottom.
31.50	Right bank Fremont River, bears NE. and SW., thence over river.
34.00	Left bank same river, bears NE. and curves W., asc. 15 ft. over river bottom land.
40.32	Point for the ¼ sec. cor. of secs. 22 and 23, at mid-point; there is no evidence of original corner.
	Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

D ›endent Resurvey, Portion of the Subdivision of T. 28 S., R. 9 E.

CHAINS	
	T28S R9E ¼ S22 | S23 1964
	Asc. 25 ft. over gentle S. slope.
58.60	Highway, hard surface, U-24, bears N. 67° E. and S. 67° W.
67.05	Power line, bears N. 83°30' W. and S. 83°30' E.
80.64	The cor. of secs. 14, 15, 22 and 23, marked by a sandstone 14x14x16 ins., plainly mkd. 3 notches on S. and 2 notches on E. face.
	At the corner point
	Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T28S R9E S15 | S14 S22 | S23 1964
	Place original stone alongside and W. of iron post.
	Land, broken S. portion, rolling N. portion. Soil, sandy gravel S. portion, sandy clay N. portion. Timber, few cottonwood on river bottom. Undergrowth, shadscale on benches, willows along river.
	From the cor. of secs. 13, 14, 23 and 24.
	N. 89°40' W., bet. secs. 14 and 23.
	Over broken desert land, along gentle S. slope.
5.30	Small wash, drains S., asc. 25 ft. over gentle E. slope.
13.20	Low clay rise, bears N. and S., desc. 75 ft. over gentle W. slope.
19.50	Wash, drains S., asc. 80 ft. over E. slope.
27.10	Low clay spur, slopes S., thence over series of small clay spurs sloping S.
35.60	Crest clay spur, slopes S., desc. 40 ft. over gentle W. slope.
39.97	The ¼ sec. cor. of secs. 14 and 23, marked by a mound of stone foreign to this area, mks. have weathered away; accepted as best available evidence of the original cor.
	At the corner point
	Set an iron post 36 ins. long, 1 in. diam., 28 ins. in the ground, in a collar of stone, with brass cap mkd.
	T28S R9E ¼ S14 S23 1964

CHAINS	
	Cor. falls on N. slope of small clay hill, 2 chs. E. of large clay flat.
	N. 89°59' W., beginning new measurement.
	Desc. irregular W. slope of clay hills.
2.40	Leave clay hills, thence over clay flat.
19.70	Enter series of small clay hills.
29.00	Leave clay hills, thence over large clay flat, draining S.
36.00	Drain ditch, drains S. 20° E.
40.05	The cor. of secs. 14, 15, 22 and 23.
	Land, mostly rolling. Soil, clay. Very little vegetation.
	N. 0°14' E., bet. secs. 14 and 15.
	Over clay valley, asc. 15 ft. over gentle S. slope.
16.00	Enter clay hills, asc. 45 ft. over S. slope.
22.70	Flood control ditch, drains S. 20° E.
31.70	Clay rise, bears NW. and SE.
40.42	The ¼ sec. cor. of secs. 14 and 15, marked by a sandstone 4x12x14 ins., plainly mkd. ¼.
	At the corner point
	Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R9E ¼ S15 | S14 1964
	Place original stone alongside and W. of iron post.
	N. 0°03' E., beginning new measurement.
	Asc. 35 ft. over small clay hills.
15.00	Base of terrace, bears N. 10° W. and SE. irregular, asc. 85 ft. over broken SE. slope.
28.50	Crest same terrace, bears NW. and S., asc. 25 ft. over series of rolling clay hills, draining SE.
40.19	The cor. of secs. 10, 11, 14 and 15, marked by a sandstone 8x8x14 ins., marked 4 notches on S. and 2 notches on E. face.
	At the corner point
	Set an iron post 30 ins. long, 2½ ins. diam., 18 ins. in the ground, in a collar of stone, with brass cap mkd.

Dependent Resurvey, Portion of the Subdivision of T. 28 S., R. 9 E.

CHAINS	
	T28S R9E S10 | S11 S15 | S14 1964 Place original stone alongside and W. of iron post. Land, broken. Soil, clay. Very little vegetation.
	From the cor. of secs. 11, 12, 13 and 14. N. 89°37' W., bet. secs. 11 and 14. Over rolling clay bench.
8.10	Graded dirt road, bears S. and curves NE.
36.40	W. crest of rolling bench, desc. 50 ft. over W. slope of small ravine.
40.00	Point for the ¼ sec. cor. of secs. 11 and 14, at proportionate distance; there is no evidence of original corner. Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R9E ¼ S11 S14 1964 Asc. 100 ft. over general E. slope, across rolling clay hills.
47.00	Wash, drains SE.
63.40	Long clay spur, slopes SE.
73.00	Wash, drains SE.
76.80	Long tan clay spur, slopes SE., desc. 40 ft. over SW. slope.
80.00	The cor. of secs. 10, 11, 14 and 15. Land, level E. portion, rolling hills W. portion. Soil, clay. Very little vegetation.
	S. 89°52' W., bet. secs. 10 and 15. Over broken desert land, across series of clay spurs sloping SE., asc. 35 ft. over NE. slope.
5.20	Clay spur, slopes SE., desc. 30 ft. over SW. slope.
10.00	Gully, drains SE., asc. 50 ft. over E. slope.
18.20	Spur, slopes SE., desc. 125 ft. over SW. slope.
23.40	Wash, 3 ft. deep, 20 lks. wide, drains S. 20° W., asc. 150 ft. over E. slope.

CHAINS	
34.30	Spur, slopes S., desc. 100 ft. over NW. slope.
40.25	Point for the ¼ sec. cor. of secs. 10 and 15, at midpoint; there is no evidence of original corner. Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R9E ¼ S10/S15 1964 Desc. 20 ft. over NW. slope.
41.60	Wash, 3 ft. deep, 10 lks. wide, drains SE., 140 ft. over irregular NE. slope.
54.60	Spur, slopes SE., desc. 120 ft. over SW. slope.
62.20	Wash, 2 ft. deep, 30 lks. wide, drains SE., asc. 85 ft. over NE. slope.
73.20	Small spur, slopes NE., desc. 20 ft. along N. slope.
80.50	The cor. of secs. 9, 10, 15 and 16, marked by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the resurvey of a portion of the subdivision, in 1932. Land, broken. Soil, shale and clay. Very little vegetation.
	From the cor. of secs. 10, 11, 14 and 15. N. 0°09' E., bet. secs. 10 and 11. Over broken desert land, over series of clay spurs sloping SE., asc. 40 ft. over SW. slope.
4.90	Clay spur, slopes SE., desc. 35 ft. over NE. slope.
11.00	Wash, 2 ft. deep, 10 lks. wide, drains SE., asc. 65 ft. over rolling clay spurs, sloping SE.
30.40	Crest of brown clay rim, bears NW. and SE., thence over small bench, covered with brown clay.
39.50	Gully, about 20 ft. deep, drains SE.
40.05	The ¼ sec. cor. of secs. 10 and 11, marked by a small mound of sandstone in barren clay formation, marks have weathered away; accepted as best available evidence of the original corner. At the corner point Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R9E ¼ S10|S11 1964

Dependent Resurvey, Portion of the Subdivision of T. 28 S., R. 9 E.

CHAINS	
	N. 0°03' E., beginning new measurement.
	Continue over small bench, draining SE.
1.60	Small gully, drains SE.
21.00	Clay knoll, 10 ft. high, 3 chs. diam.
34.60	Small wash, drains E.
39.95	The cor. of secs. 2, 3, 10 and 11, marked by an iron post, 2 ins. diam., firmly set, with brass cap mkd. T28S R9E S 3 | S 2 S10 | S11 1934 Note: I find no record of this remonumentation in the record of the resurveys, in 1934. It was apparently omitted from the record, and is accepted as the best available evidence of the original corner. Land, rolling to broken. Soil, clay. Very little vegetation.
	From the cor. of secs. 1, 2, 11 and 12.
	N.89°57' W., bet. secs. 2 and 11.
	Over broken desert land, across barren clay hills draining SE.
1.40	Low clay spur, slopes SE., desc. 20 ft. along S. slope, over series of small spurs.
30.80	Wash, 6 ft. deep, 20 lks. wide, drains S. 75° E., asc. 35 ft. over E. slope of clay hills.
39.85	Point for the ¼ sec. cor. of secs. 2 and 11, at midpoint; there is no remaining evidence of original corner. Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R9E ¼ S 2 S11 1964 Asc. 20 ft. over E. slope.
41.40	Small gravelly knoll, asc. 10 ft. over gentle E. slope.
47.30	Small wash, drains E. irregular, asc. 15 ft. over gentle E. slope.
79.70	The cor. of secs. 2, 3, 10 and 11. Land, broken to rolling. Soil, clay. Very little vegetation.
	N. 89°27' W., bet. secs. 3 and 10.

CHAINS	
	Over rolling clay bench, asc. 50 ft. over gentle E. slope.
40.35	The ¼ sec. cor. of secs. 3 and 10, an iron post 1 in. diam., set, mkd. and witnessed as described in the official record of resurveys in 1934.
	S. 89°38' W., beginning new measurement.
	Asc. 40 ft. over E. slope.
10.00	Clay knoll, about 8 chs. diam., asc. 40 ft. over E. slope.
31.00	Base of clay breaks, bears N. and S. irregular, asc. 70 ft. over NE. slope of spur.
36.20	Spur, slopes SE., desc. 65 ft. over SW. slope.
40.40	The cor. of secs. 3 and 10, an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record of resurveys, in 1934.
	Land, rolling to broken. Soil, clay and shale. Very little vegetation.
	From the cor. of secs. 2, 3, 10 and 11.
	N. 0°09' E., bet. secs. 2 and 3.
	Over rolling bench land, across tan clay hills, draining E.
19.00	Wash in small hollow, drains E., asc. 35 ft. along gentle E. slope.
40.03	The ¼ sec. cor. of secs. 2 and 3, marked by a sandstone 4x10x12 ins., dimly mkd. ¼.
	At the corner point
	Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R9E ¼ S 3 | S 2 1964
	Place original stone alongside and W. of iron post.
	N. 0°05' E., beginning new measurement.
	Continue over clay bench, over series of clay hills, draining SE.
.80	Small wash, drains S. 70° E., asc. 10 ft. along broken E. slope.
29.00	Wash in small hollow, drains S. 50° E.
37.60	Enter gravelly topped low hills.

Dependent Resurvey, Portion of the Subdivision of T. 28 S., R. 9 E.

CHAINS	
40.02	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the resurvey of the N. bdy. in 1940. Land, rolling to broken. Soil, clay and shale. Very little vegetation.
	From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., an iron post 2 ins. diam., set, mkd. and witnessed as described in the resurvey of the S. bdy. in 1919. N. 1°10' E., bet. secs. 33 and 34. Over broken desert land, across clay spurs and gulleys draining E., asc. 35 ft.
5.50	Clay spur, slopes E.
7.70	Wash, 2 ft. deep, 10 lks. wide, drains E., asc. 70 ft.
24.70	Spur, slopes E.
29.70	Spur, slopes E., asc. 25 ft.
39.20	Spur, slopes E., desc. 30 ft. over N. slope of spur.
40.15	Point for the ¼ sec. cor. of secs. 33 and 34, at mid-point; there is no evidence of original corner. Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R9E ¼ S33 | S34 1964 Desc. 15 ft. over N. slope of spur.
40.60	Gully, drains E., asc. 200 ft. over ledgy S. slope. By traverse, topography scaled.
42.90	Ledgy and inaccessible point, projects E. from South Cainsville Mesa, desc. 120 ft. over ledgy NE. slope.
55.80	Spur, slopes NE., desc. 75 ft. over series of clay spurs and gulleys draining NE.
74.40	Spur, slopes N. 15° E., desc. 25 ft. along W. slope of spur.
80.30	The cor. of secs. 27, 28, 33 and 34, marked by a sandstone 14x16x20 ins., plainly mkd. 1 notch on S. and 3 notches on E. face. At the corner point Set an iron post 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R9E S28 | S27 S33 | S34 1964

CHAINS	
	Place original stone alongside and W. of iron post. Land, broken. Soil, clay. Very little vegetation.
	From the cor. of secs. 26, 27, 34 and 35. N. 89°39' W., bet. secs. 27 and 34. Over desert land, across rolling clay spurs, sloping N., asc. 15 ft. over E. slope of small spur.
2.30	Small spur, slopes N. 20° E., desc. 25 ft. over NW. slope.
8.00	Wash, 3 ft. deep, 20 lks. wide, drains N. 20° E., asc. 50 ft. along N. slope.
18.00	Low clay spur, slopes N., desc. 15 ft. along N. slope.
26.10	Small wash, drains N. 20° E., asc. 30 ft. over gentle E. slope.
40.14	The ¼ sec. cor. of secs. 27 and 34, marked by a sandstone 6x12x16 ins., plainly mkd. ¼. At the corner point. Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R9E ¼ S27/S34 1964 Place original stone alongside and N. of iron post.
	N. 89°49' W., beginning new measurement. Asc. 40 ft. over E. slope.
15.70	Tan clay ridge, bears N. and S., thence over series of small blue clay spurs and gullys draining N.
21.40	Clay spur, clopes N.
24.10	Clay spur, slopes N.
28.60	Clay spur, slopes N.
35.50	Clay spur, slopes N.
38.80	Clay spur, slopes N. 20° E., desc. 35 ft. over W. slope of spur.
40.49	The cor. of secs. 27, 28, 33 and 34. Land, broken. Soil, clay. Very little vegetation.
	N. 0°05' W., bet. secs. 27 and 28.

CHAINS	
	Over broken desert land, desc. 55 ft. along W. slope of clay spur.
5.30	Wash, drains NE., asc. 30 ft. over SE. slope of clay spur.
13.60	Spur, slopes NE., desc. 35 ft. over N. slope.
21.10	Same wash, drains NW. 10 chs. thence N., also base of steep ascent, asc. 175 ft. over broken SW. slope, on W. side of small pass through hills.
38.60	Crest of ascent on W. slope, desc. 20 ft. over broken NW. slope.
39.64	The ¼ sec. cor. of secs. 27 and 28, marked by a black lava stone 14x14x20 ins., plainly mkd. ¼, and is accepted as the original corner stone.
	At the corner point
	Set an iron post 30 ins. long, 2½ ins. diam., 15 ins. in the ground, in a mound of stone 3 ft. base, to top, with brass cap mkd.
	T28S R9E ¼ S28 | S27 1964
	Place original stone alongside and W. of iron post.
	Cor. falls on rocky NW. slope, about 30 ft. below crest of bench.
	N. 0°02' E., beginning new measurement.
	Desc. 165 ft. over rocky NW. slope.
9.70	Base of steep descent, bears SW. and curves N., desc. 15 ft. along gentle W. slope, in pass.
19.00	Base of small spur, bears NW. about 2 chs. and curves S., asc. 40 ft. over S. slope.
21.30	Spur, slopes W. 2 chs. to end, desc. 45 ft. along W. slope.
31.10	Crest of clay bank, about 10 ft. high, bears NE. and W., thence over Fremont River bottom land, through dense growth of willows, leave hills.
40.26	Point for the cor. of secs. 21, 22, 27 and 28, at proportionate distance; there is no evidence of original cor.
	Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T28S R9E S21 | S22 S28 | S27 1964
	Raised mound of stone 3 ft. base, 2½ ft. high W. of corner.

CHAINS	
	Land, broken. Soil, clay, sandy on river bottom. Timber, none. Undergrowth, dense willows along river.
	From the cor. of secs. 22, 23, 26 and 27.
	N. 89°52' W., bet. secs. 22 and 27.
	Over desert land, across gravelly bench draining N.
20.30	E. rim of small draw, bears NE. and SW., desc. 115 ft. over ledgy W. slope.
24.90	Wash in draw, drains N., asc. 115 ft. over ledgy E. slope.
30.50	W. rim same draw, bears N. and S. irregular, thence over gravelly bench.
39.97	The ¼ sec. cor. of secs. 22 and 27, marked by a black lava stone 10x16x20 ins., plainly mkd. ¼.
	At the corner point
	Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.
	T28S R9E
	¼ S22/S27
	1964
	Place original stone alongside and N. of iron post.
	N. 89°58' W., beginning new measurement.
	Continue over gravelly bench.
.80	E. crest small cove, bears NE. and S., desc. 65 ft. over W. slope.
3.80	Wash in bottom of cove, drains N., asc. 65 ft. over E. slope.
7.40	W. crest same cove, bears N. and S., thence over N. end of bench.
12.50	W. rim of bench, bears S. 70° W. and curves NE., desc. 180 ft. over ledgy NW. slope. By triangulation.
15.50	Base of descent, bears S. 70° W. and curves NE., thence over Fremont River bottom land.
20.50	Right bank Fremont River, bears NE. and curves W., thence over curve in river.
37.70	Right bank of river, bears NW. and curves E., thence over river bottom land.
40.22	The cor. of secs. 21, 22, 27 and 28.
	Land, broken. Soil, gravelly on benches, sandy along river. Timber, none. Undergrowth, shadscale on benches, willows along river.

Dependent Resurvey Portion of the Subdivision of T. 28 S. R. 9

CHAINS	
	N. 0°13' E., bet. secs. 21 and 22.
	Over Fremont River bottom land, through willows.
2.50	Right bank of Fremont River, bears NW. and SE., thence over river.
5.50	Left bank same river, bears NW. and SE., asc. 20 ft. over bottom land, draining S. Along old abandoned fence line.
24.43	Fence, on S. side of highway, bears S. 67° W. and N. 67° E.
25.60	Highway, U-24, under construction, bears S. 67° W. and N. 67° E.
26.62	Fence, on N. side of highway, bears S. 67° W. and N. 67° E.
30.60	Old abandoned highway, parallels new highway.
37.80	Power line, bears N. 66° E. and S. 66° W.
40.26	Point for the ¼ sec. cor. of secs. 21 and 22, at proportionate distance; there is no evidence of original cor.
	Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T28S R9E ¼ S21 | S22 1964
	Raised mound of stone 2½ ft. base, 2½ ft. high, W. of corner.
	Asc. 25 ft. over clay valley land, draining S.
68.30	Base of spur, bears NW. and SE. about 3 chs. to end, asc. 50 ft. over S. slope of spur.
71.30	Spur, slopes SE. 3 chs. to end, desc. 40 ft. over N. slope.
73.00	Base same spur, bears NW. and SE., thence along E. slope.
76.50	Base of spur, bears NW. and SE. 4 chs. to end, asc. 80 ft. over S. slope.
78.40	Spur, slopes SE., desc. 60 ft. over NE. slope.
80.52	The cor. of secs. 15, 16, 21 and 22, an iron post 2 ins. diam., set, mkd. and witnessed as described in the resurvey of a portion of the Tp. in 1932.
	Land, rolling. Timber, none. Soil, clay, sandy along river. Undergrowth, willows along river.
	From the cor. of secs. 14, 15, 22 and 23.
	S. 89°47' W., bet. secs. 15 and 22.
	Over valley desert land, across barren clay land, draining S.

Dependent Resurvey, Portion of the Subdivision of T. 28 S., R. 9 E.

CHAINS	
14.50	Drain ditch, drains S.
31.50	Small wash, drains SE., asc. 10 ft. over gentle SE. slope
40.37	The ¼ sec. cor. of secs. 15 and 22, marked by a sandstone 8x12x18 ins., plainly mkd. ¼.
	At the corner point
	Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T28S R9E
	¼ S15/S22
	1964
	Place original stone alongside and N. of iron post.
	N. 89°44' W., beginning new measurement.
	Asc. 20 ft. over gentle SE. slope.
19.30	Enter low rolling clay hills, asc. 30 ft. over general SE. slope.
39.94	The corner of secs. 15, 16, 21 and 22.
	Land, rolling. Soil, clay. Very little vegetation.
	From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp. an iron post 2 ins. diam., set, mkd. and witnessed as described in the resurvey of a portion of the S. bdy. in 1919.
	N. 0°50' E., bet. secs. 32 and 33.
	Over desert land on top of South Cainsville Mesa.
11.40	N. rim of mesa, bears E. and W. irregular, desc. 800 ft. over ledgy and inaccessible N. slope. By triangulation, topography scaled.
35.00	Base of ledges, desc. 200 ft. over broken N. slope, on spur.
39.48	The ¼ sec. cor. of secs. 32 and 33, marked by a sandstone 8x16x24 ins., plainly mkd. ¼.
	At the corner point
	Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.
	T28S R9E
	¼
	S32|S33
	1964
	Place original stone alongside and W. of iron post.

Dependent Resurvey, Portion of the Subdivision of T. 28 S., R. 9 E.

CHAINS	
	Cor. falls at base of large balanced rock, on backbone of spur, which slopes sharply N.
	N. 0°03' E., beginning new measurement.
	Desc. 190 ft. over broken N. slope.
4.00	Gully, drains N. 20° W., asc. 60 ft. over broken SW. slope.
5.30	Spur, slopes sharply N. 20° W., desc. 130 ft. over steep NE. slope.
9.50	Base of spur, bears SE. and N., desc. 35 ft. down rocky hollow.
25.80	Low clay hill, bears N. 10° W., S. 10° E., desc. 45 ft. over NE. slope.
27.00	Base of hills, desc. 15 ft. down small cove.
39.99	The cor. of secs. 28, 29, 32 and 33, marked by a sandstone 8x8x14 ins., plainly mkd. 1 notch on S. and 4 notches on E. face. At the corner point Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R9E S29 | S28 S32 | S33 1964 Place original stone alongside and W. of iron post. Land, broken. Soil, clay and exposed sandstone. Timber, none. Undergrowth, scattered shadscale.
	From the cor. of secs. 27, 28, 33 and 34.
	S. 89°40' W., bet. secs. 28 and 33.
	Over barren clay hills and gulleys draining generally N.
2.40	Small wash, drains N.
9.60	Tan topped clay knoll, about 3 chs. diam.
16.90	Slay spur, slopes N.
24.90	Clay spur, slopes N.
38.00	Tan topped clay point, projects N. 70 lks. to end, desc. 65 ft. over W. slope of point.
39.90	The ¼ sec. cor. of secs. 28 and 33, marked by a sandstone 4x10x12 ins., with part of mark broken off. At the corner point Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

Dependent Resurvey, Portion of the Subdivision of T. 28 S., R. 9 E.

CHAINS	
	T28S R9E
	$\frac{S28}{S33}$
	1964
	Place original stone alongside and N. of iron post.
	Cor. falls on steep W. slope, 10 ft. out of gully bottom.
	S. 89°51' W., beginning new measurement.
	Continue over barren clay hills and gullies draining N., desc. 100 ft.
.30	Gully, drains N.
4.30	Clay spur, slopes N.
11.00	Clay spur, slopes N.
21.60	Clay spur, slopes N.
27.90	Clay spur, slopes N.
35.80	Clay spur, slopes N., thence across small cove.
40.70	Small wash in cove, drains N.
41.07	The cor. of secs. 28, 29, 32 and 33.
	Land, broken. Soil, clay. Timber, none. Undergrowth, very scattered shadscale.
	S. 89°57' W., bet. secs. 29 and 32.
	Over broken desert land, across barren clay spurs and gullies draining N. Asc. 40 ft. over E. slope of spur.
1.40	Clay spur, slopes N., desc. 25 ft. over W. slope.
5.50	Small wash, drains N.
8.00	Clay spur, slopes N.
13.80	Clay spur, slopes N.
25.20	Clay spur, slopes N.
31.80	Clay spur, slopes N.
39.30	Small wash, drains N.
39.95	The ¼ sec. cor. of secs. 29 and 32, marked by a sandstone 8x10x16 ins., dimly mkd. ¼.
	At the corner point
	Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

De ·ident Resurvey, Portion of the Subdivision of T. 28 S., R. 9

CHAINS	
	T28S R9E ¼ S29/S32 1964 Place original stone alongside and N. of iron post.
	N. 89°53' W., beginning new measurement.
	Continue over clay spurs and gullies draining N., asc. 85 ft. over E. slope of spur.
2.10	Spur, slopes N.
11.20	Spur, slopes N.
17.30	Spur, slopes N.
21.80	Spur, slopes N., desc. 60 ft. over W. slope of spur.
27.10	Small wash, drains N., asc. 110 ft. over E. slope.
32.20	Clay spur, slopes N.
37.50	Clay spur, slopes N., desc. 65 ft. over W. slope.
40.22	The cor. of secs. 29, 30, 31 and 32, an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record of resurveys, in 1949.
	Land, broken. Soil, clay with gravel spots. Very little vegetation.
	From the cor. of secs. 28, 29, 32 and 33.
	N. 0°26' E., bet. secs. 28 and 29.
	Over desert land, desc. 25 ft. over gentle N. slope of bench.
10.90	Small wash, drains N. 20° E., desc. 15 ft. over gentle N. slope, through brown boulders.
24.10	Same wash, drains N. 10° W.
40.13	The ¼ sec. cor. of secs. 28 and 29, marked by a black lava stone 6x12x16 ins., mkd. ¼.
	At the corner point
	Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T28S R9E ¼ S29|S28 1964 Place original stone alongside and W. of iron post.
	N. 0°25' E., beginning new measurement.

CHAINS	
	Desc. gentle N. slope of bench.
1.00	Bank, about 20 ft. high, bears SW. and NE., thence over bottom land of Fremont River.
11.90	Right bank Fremont River, bears E. and SW., thence over river channel.
16.80	Left bank of river, bears E. and SW., also bank about 20 ft. high, thence through farms, along N-S fence line, from highway to river.
30.44	Fence, bears N. 66°46' E. and S. 66°46' W.
31.77	Highway, U-24, under construction, bears N. 66°46' E. and S. 66°46' W.
32.53	Fence, parallel highway.
34.70	Irrigation ditch, drains E., also power line, bears NE. and SW.
38.15	The witness cor. for secs. 20, 21, 28 and 29, an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record of resurveys, in 1932.
40.75	True point for the cor. of secs. 20,21, 28 and 29, falls in wash in unsafe place for corner monument.
	Land, rolling. Soil, sandy clay. Timber, none.
	From the cor. of secs. 21, 22, 27 and 28.
	N. 89°33' W., bet. secs. 21 and 28.
	Over Fremont River bottom land, through dense willows.
17.50	Right bank Fremont river channel, bears SW. and curves NE
20.60	Left bank of river, bears SW. and curves NE., thence over farm lands.
40.03	Point for the ¼ sec. cor. of secs. 21 and 28, determined latitudinally by a straight line, and longitudinally by fence bearing N. and S. There is no evidence of original corner.
	Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T28S R9E
	¼ S21/S28
	1964
	N. 89°33' W., beginning new measurement.
	Continue over level valley land, leave farms.
16.31	Fence, parallel highway.

Dependent Resurvey, Portion of the Subdivision of T. 28 S., R. 9 E.

CHAINS	
19.61	Highway, U-24, under construction, bears N. 66°46' E. and S. 66°46' W.
24.00	Fence, parallel highway.
29.77	Power line, bears S. 61°46' W. and N. 61°46' E.
40.27	True point for the cor. of secs. 20, 21, 28 and 29.
	Land, level. Soil, clay. Timber, none. Undergrowth, shadscale and willows along river.

General Description

The portion of T. 28 S., R. 9 E. covered by this resurvey consists mainly of broken desert land with a few small farms along the Fremont River, which meanders across the south portion of the Township, flowing in an easterly direction. The main road is highway U-24, which follows the river bottom lands across the township.

The soil is sand and exposed sandstone on higher elevations, clay on lower elevations. The elevation varies from about 4400 to 5900 ft. above sea level. Vegetation consists mainly of shadscale and bunch grass on higher elevations, willows and a few cottonwood trees along the river.

There are several families living on the farms along the river.

Form 4-680
(June 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
LaVern Griffin	Transitman
Ferrel Reynolds	Notekeeper
Merlin Robinson	Chainman
Morris E. Blackburn	Cornerman
Jerry Thomas	Flagman

CERTIFICATE OF SURVEY

I, Craig P. Sylvester, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 21st day of August, 19 63, I have dependently resurveyed the east boundary, a portion of the south boundary and a portion of the subdivision of T. 28 S., R. 9 E.

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

February 1, 1966
(Date)

(Supervisory Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date FEB 17 1966

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the dependent resurvey of the east boundary, a portion of the south boundary and a portion of the subdivison of T. 28 S., R. 9 E., Salt Lake Meridian, Utah.

executed by Craig P. Sylvester, Supervisory Cadastral Surveyor having been critically examined and found correct, are hereby approved.

APR 14 1966
(Date)

(Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in~~ T. 28 S., R. 9 E., Salt Lake Meridian, is a true copy of the original field notes.

~~(Date)~~

~~(Chief, Division of Engineering)~~

Blank

Page

Blank

Page

Form 4-679
(January 1963)

45

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF THE EAST BOUNDARY

AND PORTION OF THE SUBDIVISIONAL LINES

AND RETRACEMENT OF A PORTION OF THE SOUTH BOUNDARY

OF

TOWNSHIP 29 SOUTH, RANGE 9 EAST

Of the SALT LAKE Meridian,

In the State of UTAH.

EXECUTED BY

Craig P. Sylvester Supervisory Cadastral Surveyor

Under special instructions dated August 21, 19 63, which provided for the surveys included under Group Number 466, approved August 22, 1963, and assignment instructions dated September 24, 19 63.

Survey commenced April 2, 19 64

46

DEPT. OF THE INTERIOR
BUR OF LAND MGMT

1966 MAY 12 AM 10 24 .9

RECEIVED
STATE & LAND OFFICE
SALT LAKE CITY, UTAH

INDEX DIAGRAM

Township 29 SOUTH, Range 9 EAST,

6	5	4	3	2 20	21 1 20	7
7	8	9	10	11 18	19 12 17	6
18	17	16	15	14 15	16 13 14	5
19	20	21	22	23 12	13 24 12	4
30	29	28	27	26 10	11 25 9	3
31	32	33	34	35	8 36 7	2

Dependent Resurvey, East Boundary and Portion of the Subdivisional Lines, and Retracement of a Portion of the South Boundary, Township 29 South, Range 9 East

CHAINS

The north boundary was surveyed by A. D. Ferron in 1883, and the west 4 miles resurveyed by Elliot Bird in 1919. The east 2 miles were resurveyed concurrently and the record appears in the field notes of the resurvey of a portion of the south boundary of T. 28 S., R. 9 E. The east 2½ miles of the south boundary were surveyed by A. D. Ferron in 1883, and resurveyed by Elliot Bird in 1919. The west 3½ miles of the south boundary were surveyed by Elliot Bird in 1919. The west boundary was surveyed by Elliot Bird in 1919. The east boundary was surveyed by A. D. Ferron in 1883. The east 2 tiers of sections were surveyed by A. D. Ferron in 1883. The west 4 tiers of sections were surveyed by Elliot Bird in 1919.

The following field notes are those of a dependent resurvey of the east boundary, and portion of the subdivisional lines, and retracement of a portion of the south boundary of T. 29 S., R. 9 E.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions, 1947, and the Special Instructions dated August 21, 1963.

Corners on the east-west lines were set on the true latitudinal curve. Lines connecting previously established corners were run by random and true method, but for simplification of the record, the random lines are omitted from these field notes.

All lines of this survey were run by direct method where lines were accessible; lines inaccessible were run by traverse or triangulation method. Distances to topography on lines run by traverse and triangulation methods are approximate as scaled from U.S.G.S. topographic sheets. The details of such traverses and triangulations have been thoroughly checked and verified, and in order to simplify the records, the diagrams and reductions are omitted from these field notes.

The directions of the lines of this survey were determined by reference to true meridians established on line by hour angle observations on Polaris. They were carried forward by sustained angulation, being supplemented by numerous other observations on Polaris taken throughout the progress of the survey.

Before restoring lost corners, the lines of the original survey were retraced and a diligent search made for any evidence of the original corners. The rules of proportionate measurement were applied to ascertain the position of the lost corner after every reasonable possibility of finding direct evidence of the corner had been exhausted.

The geographic position for the southeast corner of the township is in latitude 38° 14' 11.1" N. and longitude 110° 52' 45.3" W., as determined by traverse from United States Geological Survey triangulation stations "Blue" located in sec. 4, T. 29 S., R. 10 E., and "Cattle" located in sec. 32, T. 29 S., R. 11 E.

The magnetic declination was read at a number of stations throughout the township and the average of the several readings was found to be 15°30'.

Dependent Resurvey, East Boundary, T. 29 S., R. 9 E.

CHAINS

Dependent Resurvey, East Boundary, T. 29 S., R. 9 E.

Reestablishment of the Survey Executed by
A. D. Ferron, Deputy Surveyor, in 1883.

Beginning at the cor. of T. 29 S., Rs. 9 and 10 E., mkd. by an iron post 3 ins. diam., set, mkd. and witnessed as described in the official record of the resurvey of 1919.

N. 0° 18' E., bet. secs. 31 and 36.

Over broken desert land.

13.00 Base of clay hill, asc. 50 ft. over S. slope.

15.10 Clay hill, bears NE. and SW., desc. 50 ft. over N. slope.

15.20 Small wash, drains W., asc. 30 ft. over S. slope.

21.30 Small saddle, bears E. and W., desc. 35 ft. over N. slope.

23.20 Head of small draw, drains NE., asc. 45 ft. over SE. slope.

32.30 Spur, slopes NE., desc. 110 ft. over NW. slope.

39.89 The ¼ sec. cor. of secs. 31 and 36, mkd. by a granite stone, 3x7x14 ins., plainly mkd. ¼.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S
R9E R10E
¼
S36 S31
1964

Place original stone alongside and W. of the iron post.

N. 0° 13' E., beginning new measurement.

Desc. 20 ft. over NW. slope.

3.[illegible] Small wash, drains E., asc. 60 ft. over S. slope.

4.[illegible] Rise, bears E. and W., desc. 20 ft. over N. slope.

12.5 Small wash, drains NW., asc. 30 ft. over SW. slope.

14.1[illegible] Spur, slopes W., desc. 65 ft. over NW. slope.

2[illegible] Same wash, [illegible] ft. deep, 20 lks. wide, drains E., asc. 90 ft. over SE. slope.

Dependent Resurvey, East Boundary, T. 29 S., R. 9 E.

CHAINS	
32.20	Rim of bench, bears NW. and SE., thence over bench.
40.18	The cor. of secs. 25, 30, 31 and 36, mkd. by a granite stone 4x10x14 ins., mkd. 1 notch on S. face, and 5 notches on N. face. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground, in a mound of stone 3½ ft. base, to top, with brass cap mkd. T29S R9E R10E S25 | S30 S36 | S31 1964 Place original stone alongside and W. of the iron post. Land, broken. Soil, sandy clay. Timber, none. Undergrowth, shadscale and bunch grass.
	N. 0° 15' W., bet. secs. 25 and 30. Over broken desert land, on small bench.
4.10	SW. side of small draw, bears NW. and SE., desc. 85 ft. over NE. slope.
11.00	Wash, drains NW., asc. 75 ft. over SW. slope.
26.70	Top of ascent, slopes W., desc. 75 ft. over NW. slope.
36.90	Small wash, drains W., asc. 15 ft. along gentle W. slope.
39.95	The ¼ sec. cor. of secs. 25 and 30, mkd. by a granite stone, 4x8x20 ins., plainly mkd. ¼. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R9E R10E ¼ S25 | S30 1964 Place original stone alongside and W. of the iron post.
	N. 0° 22' E., beginning new measurement. Asc. along gentle W. slope.
10.10	Small wash, drains NW., desc. 35 ft. over gentle NW. slope.

Dependent Resurvey, East Boundary, T. 29 S., R. 9 E.

CHAINS

40.22 The cor. of secs. 19, 24, 25 and 30, mkd. by a sandstone, 6x14x20 ins., mkd. 2 notches on S. and 4 notches on N. face.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S
R9E R10E
S24 | S19
S25 | S30
1964

Place original stone alongside and W. of the iron post.

Land, broken to rolling.
Soil, sandy clay and exposed sandstone.
Timber, none.
Undergrowth, shadscale and scattered bunch grass.

N. 0° 08' E., bet. secs. 19 and 24.

Desc. 45 ft. over rolling desert bench land.

40.24 The ¼ sec. cor. of secs. 19 and 24, mkd. by a sandstone, 3x8x24 ins., plainly mkd. ¼.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S
R9E R10E
¼
S24 | S19
1964

Place original stone alongside and W. of the iron post.

N. 0° 21' E., beginning new measurement.

Asc. 20 ft. over rolling bench, draining W.

7.20 Wash, drains W., continue over bench.

34.00 Slope changes, desc. 20 ft. over gentle N. slope.

40.20 The cor. of secs. 13, 18, 19 and 24, mkd. by a granite stone, 4x12x16 ins., mkd. 3 notches on N. and S. faces.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

Dependent Resurvey, East Boundary, T. 29 S., R. 9 E.

CHAINS	
	T29S R9E R10E S13 | S18 S24 | S19 1964 Place original stone alongside and W. of the iron post. Land, rolling. Soil, sand and exposed sandstone. Timber, none. Undergrowth, shadscale and bunch grass.
	N. 0° 01' W., bet. secs. 13 and 18. Over rolling desert land, desc. gentle N. slope.
8.00	Wash, drains generally N. from S. 2° W.; desc. 30 ft. over N. slope, along wash.
39.88	The ¼ sec. cor. of secs. 13 and 18, mkd. by a granite stone, 6x10x18 ins., plainly mkd. ¼. Note: original record described this as a sandstone. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground, in a mound of stone, 3½ ft. base, to top, with brass cap mkd. T29S R9E R10E ¼ S13 | S18 1964 Place original stone alongside and W. of the iron post.
	N. 0° 22' E., beginning new measurement. Desc. gentle N. slope, along W. side of wash.
6.20	Leave wash which drains to NW., asc. 15 ft. over gentle SW. slope.
27.00	Sandstone outcrop, bears E. and W.
40.70	The cor. of secs. 7, 12, 13 and 18, mkd. by a granite stone, 6x12x18 ins., mkd. 4 notches on S. and 2 notches on N. face. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R9E | R10E S12 | S 7 S13 | S18 1964

Dependent Resurvey, East Boundary, T. 29 S., R. 9 E.

CHAINS	
	Place original stone W. of corner. Land, rolling. Soil, sandy clay and exposed sandstone. Timber, none. Undergrowth, shadscale and bunch grass.
	N. 0° 08' E., bet. secs. 7 and 12. Over rolling desert land, asc. 50 ft. over S. slope.
8.00	Rise, bears NW. and SE. irregularly, desc. 40 ft. over gentle N. slope.
40.45	Point for the ¼ sec. cor. of secs. 7 and 12, at mid-point; there is no evidence of original corner. Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R9E R10E ¼ S12 | S 7 1964
	Desc. 30 ft. over gentle N. slope.
42.60	Dirt road, bears SE. and curves from NW. to N.
75.40	Same road on curve from S. to NE.
78.00	Small wash, drains NE.
80.90	The cor. of secs. 1, 6, 7 and 12, mkd. by a sandstone, 4x12x18 ins., plainly mkd. 5 notches on S. and 1 notch on N. face. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R9E R10E S 1 | S 6 S12 | S 7 1964 Place original stone alongside and W. of the iron post. Land, rolling. Soil, sandy clay and exposed sandstone. Timber, none. Undergrowth, shadscale and bunch grass.

Dependent Resurvey, East Boundary, T. 29 S., R. 9 E.

CHAINS	
	N. 0° 11' E., bet. secs. 1 and 6.
	Over rolling desert land, draining NW.
40.50	The ¼ sec. cor. of secs. 1 and 6, mkd. by a granite stone 5x10x14 ins., plainly mkd. ¼.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T29S R9E R10E ¼ S 1 | S 6 1964
	Place original stone alongside and W. of the iron post.
	N. 0° 09' E., beginning new measurement.
	Desc. 15 ft. over rolling desert land, draining NW.
40.48	The cor. of Tps. 28 and 29 S., Rs. 9 and 10 E., mkd. by a mound of stone, no visible marks. Accepted as the best available evidence of the original corner.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground, in a mound of stone 4 ft. base, to top, with brass cap mkd.
	T28S R9E R10E S36 | S31 S 1 | S 6 T29S 1964
	Land, rolling. Soil, sandy clay and exposed sandstone. Timber, none. Undergrowth, shadscale and bunch grass.

Retracement, Portion South Boundary, T. 29 S., R. 9 E.

Retracement of the Resurvey Executed by
Elliot Bird, in 1919

From the cor. of Tp. 29 S., Rs. 9 and 10 E.

S. 89° 33' W., along the S. bdy. of sec. 36.

Over broken desert land.

Note: The topography being substantially the same as recorded in the resurvey in 1919 is not entered in this retracement.

Retracement, Portion South Boundary, T. 29 S., R. 9 E.

CHAINS

3.44 The cor. of Tp. 30 S., Rs. 9 and 10 E., mkd. by an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record.

40.66 The ¼ sec. cor. of sec. 36, T. 29 S., R. 9 E., mkd. by an iron post 1 in. diam., set, mkd. and witnessed as described in the official record.

West, beginning new measurement.

2.59 The ¼ sec. cor. of sec. 1, T. 30 S., R. 9 E., mkd. by an iron post 1 in. diam., set, mkd. and witnessed as described in the official record.

40.35 The cor. of secs. 35 and 36, T. 29 S., R. 9 E., mkd. by an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record.

Dependent Resurvey of a Portion of the Subdivisional lines, T. 29 S., R. 9 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by A. D. Ferron, Deputy Surveyor, in 1883.

From the cor. of secs. 35 and 36, on the S. bdy. of the Tp.

N. 0° 06' W., bet. secs. 35 and 36.

Over broken desert land, asc. 40 ft. over SE. slope of clay hill.

5.50 Clay spur, slopes NE., desc. 75 ft. over NW. slope.

18.30 Wash, 3 ft. deep, 20 lks. wide, drains NE., desc. 30 ft. over NE. slope.

29.80 Small wash, drains NE., desc. 30 ft. over NE. slope.

40.28 The ¼ sec. cor. of secs. 35 and 36, mkd. by a granite stone, 3x8x14 ins., plainly mkd. ¼.
Note: original record described this as a sandstone.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R9E
¼
S35 | S36
1964

Place original stone alongside and W. of the iron post.

Dependent Resurvey, Portion, T. 29 S., R. 9 E.

CHAINS	
	N. 0° 49' E., beginning new measurement.
	Desc. 75 ft. over broken NE. slope.
1.50	Wash, 4 ft. deep, 20 lks. wide, drains NE.
4.80	Small wash, drains NE.
29.00	Wash, 4 ft. deep, 50 lks. wide, drains NE.
34.50	Wash area, drains N. from SE., desc. over rocky wash area.
40.41	Point for the cor. of secs. 25, 26, 35 and 36, at proportionate distance; there is no remaining evidence of original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.
	T29S R9E S26 | S25 S35 | S36 1964
	Land, broken. Soil, sandy clay and exposed sandstone. Timber, none. Undergrowth, shadscale and bunch grass.
	From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp.
	N. 89° 50' W., bet. secs. 25 and 36.
	Over broken desert land on small bench.
2.60	W. crest small bench, bears NW. and S., desc. 85 ft. over W. slope.
12.40	Small wash, drains N., asc. 90 ft. over E. slope.
20.90	Long spur, slopes N., desc. 60 ft. over W. slope.
32.00	Wash, 3 ft. deep, 30 lks. wide, drains N., asc. 25 ft. over gentle E. slope.
40.57	The ¼ sec. cor. of secs. 25 and 36, mkd. by a granite stone, 6x8x16 ins., plainly mkd. ¼.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.
	T29S R9E ¼ S25 S36 1964
	Place original stone alongside and N. of the iron post.

Dependent Resurvey, Portion, T. 29 S., R. 9 E.

CHAINS

N. 89° 43' W., beginning new measurement.

Asc. 25 ft. over E. slope.

3.00 Low ridge, bears N. and S. irregularly, desc. 55 ft. over NW. slope.

23.40 Wash, 2 ft. deep, 30 lks. wide, drains NW., desc. 50 ft. along irregular N. slope.

26.30 Gully, drains NW.

32.90 Gully, drains NW.

40.32 The cor. of secs. 25, 26, 35 and 36.

Land, broken.
Soil, sandy clay.
Timber, none.
Undergrowth, shadscale and bunch grass.

N. 89° 52' W., bet. secs. 26 and 35.

Over wash area draining North.

1.00 Leave wash area; thence over broken desert land; asc. 30 t. over E. slope.

4.30 W. crest small hollow, thence over rolling clay hills, draining N.

19.30 Wash in small hollow, drains NE.

27.70 Small ravine, drains NE.

32.70 Small ravine, drains NE.

40.23 Point for the ¼ sec. cor. of secs. 26 and 35, at proportionate distance; there is no evidence of original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R9E
¼ S26/S35

1964

Desc. 100 ft. over irregular W. slope.

56.50 Small draw, drains NW., asc. 65 ft. over gentle SE. slope.

71.00 Crest of rise, bears NE. and SW., desc. 90 ft. over NW. slope.

79.00 Small wash, drains NW.

80.46 The cor. of secs. 26 and 35, mkd. by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of resurveys in 1919.

Dependent Resurvey, Portion, T. 29 S., R. 9 E.

CHAINS	
	Land, broken. Soil, clay and sand. Timber, none. Undergrowth, shadscale and scattered bunch grass.
	From the cor. of secs. 25, 26, 35 and 36.
	N. 0° 04' W., bet. secs. 25 and 26.
	Over broken desert land, desc. down wash area.
1.00	Leave wash area, which drains to NE., asc. 30 ft. over S. slope of small hill.
5.00	Top of hill, desc. 30 ft. over irregular NW. slope.
25.60	Base of descent, asc. 30 ft. over irregular SW. slope.
40.41	The ¼ sec. cor. of secs. 25 and 26, mkd. by a granite stone 4x8x14 ins., plainly mkd. ¼.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T29S R9E ¼ S26 | S25 1964
	Place original stone alongside and W. of the iron post.
	Cor. is situated on top of small hill, which bears NE. and SW.
	N. 0° 54' E., beginning new measurement.
	Desc. 75 ft. over NW. slope.
3.40	Wash, 4 ft. deep, 30 lks. wide, drains NE., asc. 70 ft. over SE. slope.
8.40	Spur, slopes E., thence over series of small clay spurs and gullies draining E.
39.92	The cor. of secs. 23, 24, 25 and 26, mkd. by a granite stone, 3x12x16 ins., mkd. 2 notches on S. and 1 notch on E. face.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T29S R9E S23 | S24 S26 | S25 1964

Dependent Resurvey, Portion, T. 29 S., R. 9 E.

CHAINS

Place original stone alongside and W. of the iron post.

Cor. is situated in small ravine, draining NE.

Land, broken.
Soil, clay.
Timber, none.
Undergrowth, very scattered shadscale.

From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp.

N. 89° 53' W., bet. secs. 24 and 25.

Over rolling desert land on small bench, desc. 35 ft. over NW. slope.

8.00 Small hollow, drains N., asc. 20 ft. over gentle NE. slope.

14.70 Low rise, slopes N., desc. 35 ft. over gentle NW. slope.

40.33 The ¼ sec. cor. of secs. 24 and 25, marked by a granite stone, 8x10x16 ins., plainly mkd. ¼.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R9E
¼ S24/S25
1964

Place original stone alongside and N. of the iron post.

N. 89° 35' W., beginning new measurement.

Over broken desert land, draining N.

4.80 Wash in small hollow, drains NW.

10.90 Small gulch, drains NE.

23.20 Wash in small hollow, drains N.

28.62 Enter blue clay hills, draining N.

39.95 The cor. of secs. 23, 24, 25 and 26.

Land, broken.
Soil, sandy clay.
Timber, none.
Undergrowth, shadscale and scattered bunch grass.

N.89° 41' W., bet. secs. 23 and 26.

Over broken desert land, across low clay spurs and hollows, draining N.

Dependent Resurvey, Portion, T. 29 S., R. 9 E.

CHAINS	
9.00	Clay spur, slopes N.
15.50	Clay spur, slopes N.
25.00	Clay spur, slopes N.
32.00	Clay spur, slopes N., desc. 55 ft. over W. slope of spur.
40.02	The ¼ sec. cor. of secs. 23 and 26, mkd. by a granite stone, 4x10x16 ins., plainly mkd. ¼. Note: original record describes this as a sandstone. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R9E ¼ S23/S26 1964 Place original stone alongside and N. of the iron post.
	N. 89° 35' W., beginning new measurement. Asc. 40 ft. over E. slope of small hollow.
5.70	Low clay spur, slopes N., continue over rolling clay spurs, sloping N.
19.50	Clay spur, slopes N.
30.00	Low clay spur, slopes N.
40.52	The cor. of secs. 23 and 26, mkd. by an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record of the resurvey in 1919. Note: From this cor. the W¼ sec. cor. of sec. 23, bears North 39.04 chs. dist., instead of 40.00 chs. as recorded in the resurvey in 1919. Land, broken. Soil, clay. Very little vegetation.
	From the cor. of secs. 23, 24, 25 and 26. N. 0° 02' W., bet. secs. 23 and 24. Over broken desert land, across clay spurs and gullies draining NE.
9.00	Low clay spur, slopes NE., desc. 50 ft. over irregular N. slope.
29.70	Small wash, drains NW.
40.39	The ¼ sec. cor. of secs. 23 and 24, mkd. by a sandstone, 4x10x16 ins., plainly mkd. ¼. Note: original record describes this as a granite stone.

Dependent Resurvey, Portion, T. 29 S., R. 9 E.

CHAINS	
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T29S R9E ¼ S23 | S24 1964
	Place original stone alongside and W. of the iron post.
	N. 0° 20' E., beginning new measurement.
	Continue over irregular N. slope.
4.90	Slope changes, desc. 75 ft. over NE. slope.
11.10	Base of descent on NE. slope, asc. 50 ft. over SE. slope.
14.40	Spur, slopes E., desc. 60 ft. over NE. slope.
25.00	Small ravine, drains E., asc. 70 ft. over SE. slope.
30.40	Spur, slopes E., desc. 80 ft. over NE. slope.
39.85	The cor. of secs. 13, 14, 23 and 24, mkd. by a granite stone, 10x12x20 ins., mkd. 3 notches on S. and 1 notch on E. face. Note: original record describes this as a sandstone.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T29S R9E S14 | S13 S23 | S24 1964
	Place original stone alongside and W. of the iron post.
	Land, broken. Soil, sandy clay. Timber, none. Undergrowth, scattered shadscale.
	From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp.
	N. 89° 51' W., bet. secs. 13 and 24.
	Over broken desert bench land.
.90	Wash, 2 ft. deep, 20 lks. wide, drains N., asc. 20 ft. over E. slope.
15.00	Rise, bears NW. and SE., desc. 85 ft. over W. slope.

Dependent Resurvey, Portion, T. 29 S., R. 9 E.

CHAINS	
32.80	Small ravine, drains NW., asc. 30 ft. over NE. slope.
40.07	The ¼ sec. cor. of secs. 13 and 24, mkd. by a granite stone, 6x10x16 ins., plainly mkd. ¼. Note: the original record describes this as a sandstone. At the corner point Set an iron post, 30 inx. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R9E ¼ S13/S24 1964 Place original stone alongside and N. of the iron post.
	N. 89° 57' W., beginning new measurement. Over broken desert land, on top of small spur, which slopes N.
1.30	Crest of descent, bears N. and S., desc. 95 ft. over W. slope of spur.
8.20	Wash in small hollow, drains NW., asc. 75 ft. over E. slope.
13.10	E. crest of small gravel bench, bears NW. and S., thence over bench.
33.50	W. crest same bench, bears NW. and SE., desc. 70 ft. over SW. slope.
35.50	Wash in small hollow, drains NW., asc. 15 ft. over NE. slope.
40.22	The cor. of secs. 13, 14, 23 and 24. Land, broken. Soil, sandy clay. Timber, none. Undergrowth, shadscale and bunch grass.
	S. 89° 36' W., bet. secs. 14 and 23. Over broken desert land, asc. 50 ft. over NE. slope of spur.
3.30	Spur, slopes N., desc. 55 ft. over NW. slope.
6.70	Wash, 2 ft. deep, 20 lks. wide, drains NE., about 4 chs. to junction, asc. 50 ft. over E. slope.
10.40	Spur, slopes NE., desc. 35 ft.over W. slope.
20.00	Small ravine, drains NE., asc. 40 ft. over E. slope.
26.40	Clay spur, slopes NE., thence over series of clay spurs and gullies, draining NE.

Dependent Resurvey, Portion, T. 29 S., R. 9 E.

CHAINS	
40.26	Point for the ¼ sec. cor. of secs. 14 and 23, at mid-point; there is no remaining evidence of original corner. Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R9E ¼ S14/S23 1964 Asc. 230 ft. over barren and irregular clay formation, draining eastward.
74.50	Spur, slopes SE., desc. 50 ft. over W. slope.
77.00	Small ravine, drains SE., asc. 50 ft. over E. slope.
80.52	The cor. of secs. 14 and 23, mkd. by an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record of resurveys in 1919. Land, broken. Soil, clay. Very little vegetation.
	From the cor. of secs. 13, 14, 23 and 24. N. 0° 08' E., bet. secs. 13 and 14. Over broken desert land, desc. 15 ft. over NE. slope.
4.20	Wash, 4 ft. deep, 40 lks. wide, drains NW., asc. 60 ft. over SW. slope.
10.90	Crest small bench, bears NW. and SE., thence over gravelly bench.
28.80	N. crest same bench, bears E. and W., desc. 85 ft. over N. slope.
33.90	Wash, 3 ft. deep, 20 lks. wide, drains W., asc. S. slope of spur.
35.00	Spur, slopes W., desc. 70 ft. along W. slope.
40.34	Point for the ¼ sec. cor. of secs. 13 and 14, at mid-point; there is no remaining evidence of original corner. Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R9E ¼ S14|S13 1964 Desc. 25 ft. along W. slope.
48.00	Curve in wash, drains NW. from SW., asc. 55 ft. over SW. slope.

CHAINS	
56.30	Spur., slopes W., desc. 65 ft. over NW. slope.
72.20	Same wash, drains NE.
76.90	Same wash, drains NW., asc. 30 ft. over SW. slope.
78.00	Small spur, slopes NW., desc. 30 ft. over NE. slope.
80.68	The cor. of secs. 11, 12, 13 and 14, mkd. by a granite stone, 3x10x14 ins., mkd. 4 notches on S. and 1 notch on E. face. Note: original record describes this as a sandstone. At the corner point Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R9E S11 | S12 S14 | S13 1964 Place original stone alongside and W. of the iron post. Land, broken. Soil, gravelly. Timber, none. Undergrowth, shadscale and bunch grass.
	From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp. N. 89° 48' W., bet. secs. 12 and 13. Over desert land, draining NW.
15.50	Wash, 2 ft. deep, 20 lks. wide, drains NW.
40.42	The ¼ sec. cor. of secs. 12 and 13, mkd. by a granite stone, 3x12x12 ins., plainly mkd. ¼. Note: original record describes this as a sandstone. At the corner point. Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R9E ¼ S12 S13 1964 Place original stone alongside and N. of the iron post. N. 89° 50' W., beginning new measurement. Continue along gentle N. slope.
16.60	Wash, 2 ft. deep, 20 lks. wide, drains NW., asc. 35 ft. over NE. slope.

Dependent Resurvey, Portion, T. 29 S., R. 9 E.

CHAINS	
28.70	Low ridge, bears NW. and SE., desc. 100 ft. over W. slope.
37.80	Small wash, drains N.
39.90	The cor. of secs. 11, 12, 13 and 14.
	Land, broken. Soil, sandy clay. Timber, none. Undergrowth, shadscale and bunch grass.
	S. 89° 56' W., bet. secs. 11 and 14.
	Over desert land, draining N.
3.50	Wash, drains N. about 4 chs., thence NE., asc. 100 ft. over SE. slope.
17.50	Low ridge, bears N. and S. irregularly, desc. 90 ft. over W. slope.
28.40	Wash, drains N., asc. 20 ft. over gentle E. slope.
34.20	Rise, slopes N., desc. 20 ft. over W. slope.
38.10	Small wash, drains NE.
40.15	The ¼ sec. cor. of secs. 11 and 14, mkd. by a granite stone, 6x8x18 ins., plainly mkd. ¼. Note: original record describes this as a sandstone.
	At the corner point
	Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R9E ¼ S11/S14 1964
	Place original stone alongside and N. of the iron post.
	N. 89° 57' W., beginning new measurement.
	Asc. 35 ft. over E. slope.
7.10	Spur, slopes N., desc. 45 ft. over W. slope.
15.10	Small wash, drains N., asc. 40 ft. over E. slope.
26.20	Clay spur, slopes N., desc. 70 ft. over W. slope.
33.00	Wash, 3 ft. deep, 20 lks. wide, drains N. 20° E., asc. 70 ft. over E. slope.
35.20	Spur, slopes N., desc. 70 ft. over W. slope.
40.58	The cor. of secs. 11 and 14, an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record of resurveys in 1919.

Dependent Resurvey, Portion, T. 29 S., R. 9 E.

CHAINS	
	Land, broken. Soil, sandy clay. Very little vegetation.
	From the cor. of secs. 11, 12, 13 and 14. N. 0° 22' E., bet. secs. 11 and 12. Over desert land, desc. 20 ft. over N. slope.
6.70	Wash, 2 ft. deep, 20 lks. wide, drains NE. about 1 ch. to junction, thence N., desc. down small hollow.
21.00	Wash, drains NW., leave hollow, asc. S. slope.
26.00	Low spur, slopes W., desc. 30 ft. over NW. slope.
30.20	Same wash, drains NW. from SW., asc. 30 ft. along rocky W. slope.
40.33	The ¼ sec. cor. of secs. 11 and 12, mkd. by a granite stone, 6x12x14 ins., plainly mkd. ¼. Note: original record describes this as a sandstone. At the corner point Set an iron post 30 ins. long, 2½ ins. diam., 16 ins. in the ground, in a mound of stone 3 ft. base, to top, with brass cap mkd. T29S R9E ¼ S11 | S12 1964 Place original stone alongside and W. of the iron post.
	N. 0° 01' W., beginning new measurement. Asc. 80 ft. over ledgy SW. slope.
11.30	W. crest of bench, bears NW. and SE., desc. 15 ft. over gentle N. slope.
40.74	The cor. of secs. 1, 2, 11 and 12, mkd. by a granite stone, 6x12x18 ins., mkd. 5 notches on S. and 1 notch on E. face. Note: original record describes this as a sandstone. At the corner point Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R9E S 2 | S 1 S11 | S12 1964 Place original stone alongside and W. of the iron post.

Dependent Resurvey, Portion, T. 29 S., R. 9 E.

CHAINS	
	Land, broken. Soil, sandy clay. Timber, none. Undergrowth, shadscale and bunch grass.
	From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp.
	N. 89° 39' W., bet. secs. 1 and 12.
	Over broken bench land, draining N.
.20	Small wash, drains N., asc. 35 ft. over gentle E. slope.
14.00	Low spur, slopes N., desc. 45 ft. over W. slope.
22.00	Wash, 2 ft. deep, 20 lks. wide, drains N. 10° E., asc. 20 ft. over gentle E. slope.
32.10	Rise, slopes N., desc. 35 ft. over gentle W. slope.
40.05	The ¼ sec. cor. of secs. 1 and 12, mkd. by a granite stone 6x12x18 ins., plainly mkd. ¼. Note: original record describes this as a sandstone.
	At the corner point
	Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R9E ¼ S 1 / S12 1964
	Place original stone alongside and N. of the iron post.
	N. 89° 51' W., beginning new measurement.
	Desc. 20 ft. over desert bench land, draining NW.
10.60	Small wash, drains NW.
32.60	Wash, 3 ft. deep, 20 lks. wide, drains NW.
40.10	The cor. of secs. 1, 2, 11 and 12.
	Land, rolling. Soil, sand and exposed sandstone. Timber, none. Undergrowth, shadscale and bunch grass.
	S. 89° 50' W., bet. secs. 2 and 11.
	Over desert bench land, draining NW.
9.80	W. crest of bench, bears NW. and SE., desc. 145 ft. over ledgy SW. slope.
19.00	Wash, 4 ft. deep, 30 lks. wide, drains NW., asc. 95 ft. over E. slope.

Dependent Resurvey, Portion, T. 29 S., R. 9 E.

CHAINS	
24.50	Crest of ascent, bears NW. and SE., thence over N. end of gravelly bench.
31.30	W. crest of bench, bears N. and S. irregularly, desc. 70 ft. over W. slope.
38.50	Small wash, drains N., asc. gentle E. slope.
40.44	Point for the ¼ sec. cor. of secs. 2 and 11, at mid-point; there is no remaining evidence of original corner. Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R9E ¼ S 2 / S11 1964 Asc. 30 ft. over gentle E. slope.
50.30	Low ridge, bears N. and S. irregularly, desc. 70 ft. over W. slope.
62.30	Sweetwater Creek, dry, drains irregularly N.; asc. 30 ft. over gentle E. slope.
80.88	The cor. of secs. 2 and 11, mkd. by an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record of resurveys in 1919. Land, broken. Soil, sandy. Timber, none. Undergrowth, shadscale and bunch grass.

From the cor. of secs. 1, 2, 11 and 12.

N. 0° 01' W., bet. secs. 1 and 2.

Over desert land draining N., desc. 25 ft.

21.60	Curve in wash, drains irregularly NE. from NW.; thence over rolling NE. slope.
39.98	The ¼ sec. cor. of secs. 1 and 2, mkd. by a granite stone, 4x10x14 ins., plainly mkd. ¼. Note: original record describes this as a sandstone.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R9E
¼
S2 | S1
1964

Place original stone alongside and W. of the iron post.

Dependent Resurvey, Portion, T. 29 S., R. 9 E.

CHAINS

N. 0° 02' E., beginning new measurement.

Desc. 10 ft. over gentle N. slope of bench.

17.30 Slope changes, desc. 70 ft. over NW. slope, into small hollow.

24.30 Small hollow, drains NE., asc. 70 ft. over SE. slope.

30.50 Low spur, slopes NE., desc. 45 ft.over NW. slope.

36.00 Small hollow, drains NE., asc. 25 ft. over SE. slope.

40.88 The cor. of secs.1, 2, 35 and 36, on N. bdy. of the township, mkd. by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of a portion of the S. bdy. of T. 28 S., R. 9 E.

Land, broken.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, shadscale and bunch grass.

General Description

The portion of T. 29 S., R. 9 E. covered by this survey consists of broken desert land, with washes draining northward. The soil is mostly clay on the west portion, sand and exposed sandstone on the east portion. Vegetation consists of shadscale and scattered bunch grass. The elevation varies from about 4500 to 5,000 ft. above sea level. No water or permanent habitation was noted during the survey.

Form 4-680
(June 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
LaVern Griffin	Transitman
Ferrel Reynolds	Notekeeper
Merlin Robinson	Chainman
Morris E. Blackburn	Cornerman
Jerry L. Thomas	Flagman

CERTIFICATE OF SURVEY

I, Craig P. Sylvester, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 21st day of August, 19 63, I have dependently resurveyed the east boundary and portion of the subdivisional lines and retracement of a portion of the south boundary of Township 29 South, Range 9 East

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

March 22, 1965
(Date)

~~(Cadastral Surveyor)~~
(Supervisory Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date FEB 17 1966

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the dependent resurvey of the east boundary and portion of the subdivisional lines and retracement of a portion of the south boundary of Township 29 South, Range 9 East, S.L. Meridian, Utah

executed by Craig P. Sylvester, Supervisory Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

APR 14 1966
(Date)

(Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in~~

, is a true copy of the original field notes.

~~(Date)~~

~~(Chief, Division of Engineering)~~

Blank

Page

Blank

Page

ORIGINAL

73

Form 4-679
(January 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF THE EAST BOUNDARY

THE SOUTH BOUNDARY

AND SUBDIVISION

OF

TOWNSHIP 28 SOUTH, RANGE 10 EAST

Of the SALT LAKE Meridian,

In the State of UTAH.

EXECUTED BY

Craig P. Sylvester Supervisory Cadastral Surveyor

Under special instructions dated August 21, 19 63, which provided for the surveys included under Group Number 466, approved August 22, 1963, and assignment instructions dated September 24, 19 63.

Survey commenced April 17, 19 64

Dec. 27 64

DEPT. OF THE INTERIOR
BUR OF LAND MGMT

1966 MAY 12 AM 10 24 8

RECEIVED
STATE & LAND OFFICE
SALT LAKE CITY, UTAH

INDEX DIAGRAM

Township 28 SOUTH, Range 10 EAST,

6 64	64 5 63	52 4 51	43 3 42	33 2 32	24 1 23	7
7 61	62 8 61	50 9 50	41 10 41	32 11 31	22 12 21	6
18 59	60 17 58	48 16 48	40 15 39	30 14 29	20 13 19	5
19 57	58 20 56	47 21 46	37 22 37	28 23 27	18 24 17	4
30 55	55 29 54	45 28 44	36 27 35	26 26 25	16 25 15	3
31 13	53 32 12	43 33 11	34 34 10	24 35 9	14 36 8	2

Dependent Resurvey, East and South Boundaries and Subdivision
Township 28 South, Range 10 East

CHAINS

The north boundary was surveyed by A. D. Ferron in 1883, and resurveyed by Kenneth F. Hansen in 1954, and the record appears in the resurvey of the south boundary of T. 27 S., R. 10 E. The west boundary was surveyed by A. D. Ferron in 1883, and concurrently resurveyed, and the record appears in the field notes of the resurvey of the east boundary of T. 28 S., R. 9 E. The east and south boundaries, and the subdivisional lines were surveyed by A. D. Ferron in 1883.

The following field notes are those of a dependent resurvey of the east and south boundaries, and subdivisional lines of T. 28 S., R. 10 E.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions, 1947, and the Special Instructions dated August 21, 1963.

Corners on the east-west lines were set on the true latitudinal curve. Lines connecting previously established corners were run by random and true method, but for simplification of the record, the random lines are omitted from these field notes.

All lines of this survey were run by direct method where lines were accessible; lines inaccessible were run by traverse or triangulation method. Distances to topography on lines run by traverse and triangulation methods are approximately as scaled from U.S.G.S. topographic sheets. The details of such traverses and triangulations have been thoroughly checked and verified, and in order to simplify the records, the diagrams and reductions are omitted from these field notes.

The direction of the lines of this survey were determined by reference to true meridians established on line by hour angle observations on Polaris. They were carried forward by sustained angulation, being supplemented by numerous other observations on Polaris taken throughout the progress of the survey.

Before restoring lost corners, the lines of the original survey were retraced and a diligent search made for any evidence of the original corners. The rules of proportionate measurement were applied to ascertain the position of the lost corner after every reasonable possibility of finding direct evidence of the corner had been exhausted.

The geographic position for the southeast corner of the township is in latitude 38° 19' 25.2" N. and longitude 110° 46' 04.2" W., as determined by traverse from United States Geological Survey triangulation station "Blue" located in sec. 4, T. 29 S., R. 10 E., and United States Coast & Geodetic Survey station 8M"Z11 located in sec. 17.

The magnetic declination was read at a number of stations throughout the township and the average of the several readings was found to be 15° 30' E.

Dependent Resurvey, East Boundary, T. 28 S., R. 10 E.

CHAINS

Dependent Resurvey, East Boundary, T. 28 S., R. 10 E.

Reestablishment of the Survey Executed by A. D. Ferron, Deputy Surveyor, in 1883.

Beginning at the cor. of Tps. 28 and 29 S., Rs. 10 and 11 E., an iron post 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of the E. bdy. of T. 29 S., R. 10 E.

N. 0° 37' E., bet. secs. 31 and 36.

Over broken desert land of Pinto Hills, asc. 25 ft. along small wash, draining S. irregular.

8.00 Leave small wash, course S. from N. 10° E.

33.50 Base of clay hill, bears NE. and SW., asc. 80 ft. over SE. slope of hill. By traverse, topography scaled.

35.50 Top of ascent on E. face of hill, desc. 80 ft. over NE. slope.

38.50 Base of hill, bears NW. and SE., desc. gentle NE. slope. End traverse.

40.24 The ¼ sec. cor. of secs. 31 and 36, marked by a sandstone, 6x15x30 ins., plainly mkd. ¼.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S
R10E R11E
¼
S36 | S31

1964

Place original stone alongside and W. of iron post.

N. 0° 06' E., beginning new measurement.

Desc. 30 ft. over gravelly land, through scattered shadscale.

3.20 Small wash, drains E.

32.00 Small wash, drains E.

39.01 The witness cor. of secs. 25, 30, 31 and 36, marked by a sandstone 6x10x25 ins., marked 1 notch on S. and 5 notches on N. face, WC on E. face.

At the witness corner point

Dependent Resurvey, East Boundary, T. 28 S., R. 10 E.

CHAINS	
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R10E R11E W C S25 S30 S36 S31 1964 Place original stone alongside and W. of iron post. Cor. falls at base of impassable sandstone and clay hill. Note: Find no trace of the 2nd witness cor. recorded bet. secs. 30 and 31. Asc. 100 ft. over S. slope of hill, by traverse.
40.01	True point for the cor. of secs. 25, 30, 31 and 36, at record distance from witness corner, falls on top of impassable hill and cannot be monumented. Land, broken. Soil, gravelly red and white clay with exposed sandstone. Timber, none. Undergrowth, scattered shadscale and bunch grass.
	N. 0° 08' E., bet. secs. 25 and 30. Over broken desert land of Pinto Hills, desc. 100 ft. over N. slope of hill.
2.20	Base of clay hill, bears E. and W., thence over gravelly bench. End traverse.
17.00	Base of clay hills, bears N. and S. irregular, asc. 130 ft. along irregular W. slope.
26.20	Top of ascent on W. slope, desc. 75 ft. along W. slope.
32.50	Gully, drains SW., asc. 240 ft. over steep S. slope.
40.36	Point for the ¼ sec. cor. of secs. 25 and 30, at mid-point; there was no original corner established in 1883. Set an iron post 30 ins. long, 2½ ins. diam., 8 ins. in the ground, in a mound of stone 4 ft. base, to top, with brass cap mkd. T28S R10E R11E ¼ S25 S30 1964 Asc. 25 ft. over S. slope.
43.10	Ridge, bears E. and NW., desc. 300 ft. over broken NE. slope.
49.40	Base of steep descent, bears NW. and SE., asc. 25 ft. along E. slope.

Dependent Resurvey, East Boundary, T. 28 S., R. 10 E.

CHAINS

76.00 Base of steep ascent, bears E. and W. irregular, asc. 130 ft. over S. slope.

80.72 Point for the cor. of secs. 19, 24, 25 and 30, at record course and distance from its original witness corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground, in a mound of stone 4 ft. base, to top, with brass cap mkd.

T28S
R10E R11E
S24 | S19
S25 | S30
1964

From this corner the original witness cor. of secs. 19, 24, 25 and 30, bears east 27.00 chs. dist., (record course and distance) marked by a sandstone 5x10x18 ins., marked WC and 2 notches on S. and 4 notches on N. face.

Land, broken.
Soil, clay and exposed sandstone.
Timber, none.
Undergrowth, very scattered shadscale.

N. 0° 05' W., bet. secs. 19 and 24.

Over broken desert land, asc. 20 ft. over S. slope. By traverse.

.80 Ridge, bears E. and W., desc. 240 ft. over N. slope. Topography scaled.

8.00 Base steep descent, bears E. and W., thence along broken W. slope.

27.00 Base of steep ascent, bears W. and SE., asc. 250 ft. along impassable W. slope of clay and sandstone hills.

40.06 Point for the ¼ sec. cor. of secs. 19 and 24, at midpoint, falls in inaccessable hills and cannot be monumented. Desc. 220 ft. over broken NW. slope.

49.07 Proportionate point for the witness ¼ sec. cor. of secs. 19 and 24; there is no evidence of original witness cor., established in 1883.

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T28S
R10E R11E
¼
S24 | S19
W C
1964

Raised mound of stone 3 ft. base, 2½ ft.high W. of corner.

CHAINS	
	Cor. falls at base of steep descent, desc. 40 ft. over irregular N. slope of bench. End traverse.
55.70	Small wash, drains NW.
62.15	Wash, 3 ft. deep, 30 lks. wide, drains N. from SE., irregular, desc. along wash.
76.60	Leave wash area, which drains NW., thence over bench.
80.12	The cor. of secs. 13, 18, 19 and 24, marked by a limestone 8x10x16 ins., plainly mkd. 3 notches on N. and S. faces. At the corner point Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R10E R11E S13 | S18 S24 | S19 1964 Bury original stone alongside and W. of iron post. Land, broken. Soil, gravelly clay and exposed sandstone. Timber, none. Undergrowth, scattered shadscale and bunch grass.
	N. 0° 01' E., bet. secs. 13 and 18. Over broken desert land, desc. N. slope of bench.
1.70	Small wash, drains NE.
15.78	Crest of rim of ledges, bears E. and W. irregular, desc. 65 ft. over ledgy N. slope of river canyon.
18.90	Right bank Fremont River, bears E. and W., thence over river channel.
23.00	Left bank of river, bears E. and W., asc. 30 ft. over ledgy S. slope.
24.70	Crest of ledgy rim, bears E. and W., asc. 35 ft. over S. slope.
25.00	Highway, U-24, bears E. and W.
27.50	Power line, bears E. and W.
31.30	Rise, bears NW. and SE., desc. 50 ft. over rocky NE. slope.
40.59	Point for the ¼ sec. cor. of secs. 13 and 18, at midpoint; there is no remaining evidence of original corner. Set an iron post 30 ins. long, 2½ ins. diam., on solid sandstone, over an X, and in a mound of stone 4 ft. base, to top, with brass cap mkd.

Dependent Resurvey, East Boundary, T. 28 S., R. 10 E.

CHAINS

T28S
R10E R11E
¼
S13|S18
1964

Cor. falls at base of sandstone breaks, asc. 10 ft. over bottom in small hollow.

45.60 Graded road, bears NW. and SE., asc. 40 ft. up a small hollow, along wash, which drains irregularly SE. from N.

77.50 Wash course S., with branches from NW. and N. asc. 10 ft. along E. fork of wash.

81.18 The cor. of secs. 7, 12, 13 and 18, marked by a sandstone 6x10x14 ins., in a mound of stone, marked 2 notches on N. face, other notches weathered away.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 4 ins. in the ground, in a mound of stone 5 ft. base, to top, with brass cap mkd.

T28S
R10E R11E
S12|S7
S13|S18
1964

Place original stone in mound.

Cor. situated in W. edge small wash. Course S. from N. 10° E.

Land, broken.
Soil, clay, sand and exposed sandstone.
Timber, none.
Undergrowth, shadscale and bunch grass, willows on river bottom.

N. 0° 56' E., bet. secs. 7 and 12.

Over broken desert land, asc. 35 ft. over S. slope.

9.70 Knoll, stone capped, about 1 ch. diam., asc. 10 ft. over S. slope.

27.30 Unimproved road, bears NE. and SW.

28.90 Base of red and white hills, bears NE. and SW., asc. 60 ft. over ledgy S. slope.

30.80 Crest same hills, bears NE. and SW., desc. 55 ft. over irregular clay hills.

39.33 The ¼ sec. cor. of secs. 7 and 12, marked by a sandstone 4x12x14, plainly mkd. ¼.

At the corner point

CHAINS	
	Set an iron post 30 ins. long, 2½ ins. diam., 3 ins. in the ground, in a mound of stone 4 ft. base, to top, with brass cap mkd. T28S R10E R11E ¼ S12|S7 1964 Place original stone alongside iron post.
	N. 0° 23' E., beginning new measurement. Desc. 30 ft. over irregular red and white hills.
6.90	Small wash, drains W., asc. 25 ft. along sandy W. slope.
25.50	Wash, 2 ft. deep, 30 lks. wide, drains SW., asc. 40 ft. over gentle SE. slope.
40.33	The cor. of secs. 1, 6, 7 and 12, marked by a sandstone 8x12x12 ins., plainly mkd. 5 notches on S. and 1 notch on N. face. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R10E R11E S 1|S 6 S12|S 7 1964 Place original stone alongside and W. of iron post. Land, broken. Soil, clay and sand. Timber, none. Undergrowth, shadscale and bunch grass.
	N. 0° 18' E., bet. secs. 1 and 6. Over rolling sandy land, asc. gentle SE. slope.
3.80	Slope changes, asc. 40 ft. along gentle E. slope.
21.50	Base of E. end of butte, continue along E. slope.
40.31	The ¼ sec. cor. of secs. 1 and 6, marked by a sandstone 3x14x16 ins., plainly mkd. ¼. At the corner point Set an iron post 30 ins. long, 2½ ins. diam., 5 ins. in the ground, in a mound of stone 4 ft. base, to top, with brass cap mkd.

De endent Resurvey, East Boundary, T. 28 S., R. 10 E.

CHAINS

T28S
R10E R11E
¼
S 1 | S 6
1964

Place original stone in mound.

N. 1° 27' E., beginning new measurement.

Asc. 30 ft. along E. slope.

22.30 Low rise, bears E. and W., desc. 20 ft. over sandy N. slope.

31.60 Crest of steep descent, bears NW. and SE., desc. 110 ft. over ledgy NE. slope, into small draw.

33.50 Wash in small draw, drains SE., asc. 50 ft. over ledgy S. slope.

39.98 The cor. of Tps. 27 and 28 S., Rs. 10 and 11 E., marked by an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record of the resurvey of the S. bdy. of T. 27 S., R. 11 E., in 1929.

Land, broken.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, shadscale and bunch grass.

Dependent Resurvey, South Boundary, T. 28 S., R. 10 E.

Reestablishment of the Survey Executed by
A. D. Ferron, Deputy Surveyor, in 1883.

From the cor. of Tps. 28 and 29 S., Rs. 10 and 11 E., previously described.

N. 89° 36' W., bet. secs. 1 and 36.

Over broken desert land, asc. 20 ft. over NE. slope.

3.00 Small wash, drains NE.

23.90 Gully, drains NE., also base of clay hill, asc. 120 ft. over broken SE. slope.

30.90 Clay ridge, bears NE. and SW., desc. 105 ft.over broken NW. slope.

38.80 Wash in small hollow, drains N., asc. E. slope.

40.23 The ¼ sec. cor. of secs. 1 and 36, marked by a sandstone, 3x12x18 ins., plainly mkd. ¼.

At the corner point

CHAINS	
	Set an iron post 30 ins. long, 2½ ins. diam., 16 ins. in the ground, in a mound of stone 3 ft. base, to top, with brass cap mkd. T28S R10E ¼ S36 / S 1 T29S R10E 1964 Place original stone alongside and N. of iron post.
	N. 89° 59' W., beginning new measurement.
	Asc. 55 ft. over E. slope.
4.60	Clay spur, slopes N., desc. 40 ft. over W. slope.
8.00	Small hollow, drains N., asc. 75 ft. over NE. slope.
14.10	Spur, slopes NE., desc. 75 ft. over W. slope.
17.40	Hollow, drains N., asc. 165 ft. over ledgy E. slope.
24.60	Crest of steep ascent, bears N. and S. irregularly, asc. 40 ft. over gentle E. slope, over gravel bench.
39.85	The cor. of secs. 1, 2, 35 and 36, marked by a sandstone 6x8x22 ins., plainly mkd. 5 notches on W., and 1 notch on E. face. At the corner point Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R10E S35 | S36 S 2 | S 1 T29S R10E 1964 Place original stone alongside and W. of iron post. Land, broken. Soil, sand and exposed sandstone. Timber, none. Undergrowth, shadscale and bunch grass.
	N. 89° 31' W., bet. secs. 2 and 35.
	Over broken land, on gravelly bench, desc. 25 ft.
36.90	Wash, 2 ft. deep, 30 lks. wide, drains NW.
40.28	The ¼ sec. cor. of secs. 2 and 35, marked by a sandstone 3x14x24 ins., plainly mkd. ¼. At the corner point

Dependent Resurvey, South Boundary, T. 28 S., R. 10 E.

CHAINS	
	Set an iron post 1 in. diam., 36 ins. long, 26 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R10E ¼ S35 / S 1 T29S R10E 1964 Place original stone alongside and N. of iron post.
	N. 89° 54' W., beginning new measurement.
	Desc. 30 ft. over gentle W. slope.
25.80	E. side small hollow, bears N. and S., desc.65 ft. over W. slope.
29.60	Birch Creek, dry, drains N., asc. 55 ft. over E. slope.
31.00	W. side small hollow, bears E. and W., asc. 25 ft. over gentle E. slope.
35.50	Low rise, bears N. and S., desc. gentle W. slope.
40.13	The cor. of secs. 2, 3, 34 and 35, marked by a sandstone 4x6x14 ins., mkd. 4 notches on W. and 2 notches on E. face. Note: Original record erroneously described the stone corner as a granite. At the corner point Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R10E S34 | S35 S 3 | S 2 T29S R10E 1964 Place original stone alongside and N. of iron post. Land, broken. Soil, sand and exposed sandstone. Timber, none. Undergrowth, shadscale and bunch grass.
	S.89° 50' W., bet. secs. 3 and 34. Over broken desert land, draining NE.
3.70	Small wash, drains N.
12.70	Wash, 3 ft. deep, 30 lks. wide, drains NE.
39.50	Small wash, drains NE.
40.32	The ¼ sec. cor. of secs. 3 and 34, marked by a sandstone 3x8x14 ins., dimly mkd. ¼.

Dependent Resurvey, South Boundary, T. 28 S., R. 10 E.

CHAINS	
	At the corner point Set an iron post 36 ins. long, 1 in. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R10E ¼ S34 / S 3 T29S R10E 1964 Place original stone alongside and N. of iron post.
	S. 89° 33' W., beginning new measurement.
	Asc. 70 ft. over NE. slope.
2.60	Small wash, drains NE.
14.20	Wash, 3 ft. deep, 40 lks. wide, drains NE.
32.20	Base of clay spur, bears N. and S., asc. 55 ft. over E. slope.
36.30	Spur, slopes NE., desc. 20 ft. over NW. slope of spur.
40.30	Hollow, drains N., asc. E. slope.
40.48	The cor. of secs. 3, 4, 33 and 34, marked by a sandstone 4x8x16 ins., dimly mkd. 3 notches on E. and W. faces. At the corner point Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T28 S R10E S33 | S34 S 4 | S 3 T29S R10E 1964 Place original stone alongside and W. of iron post. From this corner U.S.G.S. triangulation station "Blue", located in latitude 38° 19' 19.941" N. and longitude 110° 49' 26.095" W., bears S. 16° 54' 20" W., 8.77 chs. dist. Land, broken. Soil, sand, blue clay and exposed sandstone. Timber, none. Undergrowth, scattered shadscale and bunch grass.
	N. 89° 48' W., bet. secs. 4 and 33. Over broken desert land, asc. 300 ft. over broken NE. slope and ledges facing NE. By triangulation; topography scaled.

Dependent Resurvey, South Boundary, T. 28 S., R. 10 E.

CHAINS

17.00 Crest of ledgy rim, bears NW. and SE. irregularly, thence over top of Blue Mesa, across sand and barren patches of sandstone. End triangulation.

31.90 Trail road, bears NW. and SE.

40.61 The ¼ sec. cor. of secs. 4 and 33, marked by a sandstone 3x12x24 ins., dimly mkd. ¼.

At the cor. point

Set an iron post 36 ins. long, 1 in. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R10E

¼ S33 / S 4

T29S R10E

1964

Place original stone alongside and N. of iron post.

N. 89° 52' W., beginning new measurement.

Desc. 20 ft. over rolling top of Blue Mesa, through heavy growth of shadscale.

40.44 The cor. of secs. 4, 5, 32 and 33, marked by a sandstone 3x8x30 ins., mkd. 2 notches on W. and 4 notches on E. face.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R10E

S32	S33
S 5	S 4

T29S R10E

1964

Place original stone alongside and W. of iron post.

Land, broken E. portion, rolling on mesa.
Soil, clay, sand and exposed sandstone.
Timber, none.
Undergrowth, shadscale.

N. 89° 17' W., bet. secs. 5 and 32.

Over broken desert land, desc. 40 ft. over gentle W. slope, on top of Blue Mesa.

20.00 W. crest of Blue Mesa, on point projecting W., bears NE. and SE., desc. 390 ft. over ledgy NW. slope.

31.80 Hollow, drains SW., asc. 35 ft. over SE. slope, over clay.

Dependent Resurvey, South Boundary, T. 28 S., R. 10 E.

CHAINS	
40.22	Point for the ¼ sec. cor. of secs. 5 and 32, at midpoint; there is no remaining evidence of the original corner. Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R10E ¼ S32 / S 5 T29S R10E 1964
	Asc. 20 ft. over SE. slope.
41.30	Spur, slopes S., desc. 120 ft. over W. slope. By triangulation, topography scaled.
44.10	Base of spur, bears N. and S., desc. 30 ft. over gentle W. slope in bottom of cove.
56.60	Wash in bottom of cove, drains N., asc. 20 ft. over gentle E. slope.
65.00	Base of steep ascent, bears NW. and SE., asc. 300 ft. over ledgy NE. slope.
73.30	Crest of steep ascent, on rim, bears NW. and SE., desc. 25 ft. over top of point, on N. end of Blue Mesa.
80.44	The corner of secs. 5, 6, 31 and 32, marked by a sandstone 3x12x30 ins., plainly mkd. 5 notches on E. and 1 notch on W. face. At the corner point Set an iron post 30 ins. long, 2½ ins. diam., 6 ins. in the ground, in a mound of stone 4 ft. base, to top, with brass cap mkd. T28S R10E S31 | S32 S 6 | S 5 T29S R10E 1964 Place original stone alongside and W. of iron post. Land, broken. Soil, sand, clay and exposed sandstone. Timber, none. Undergrowth, shadscale.
	N. 89° 55' W., bet. secs. 6 and 31. Over broken desert land of point on N. end of Blue Mesa, desc. 15 ft. over gentle W. slope.
11.80	Crest of steep descent, bears NW. and SE. irregularly, desc. 255 ft. over ledgy and irregular W. slope.
29.60	Hollow, drains N., asc. 65 ft. over E. slope of spur.

Dependent Resurvey, South Boundary, T. 28 S., R. 10 E.

CHAINS

32.80 Spur, slopes N., desc. 95 ft. over NW. slope.

37.70 Wash, 3 ft. deep, 30 lks. wide, drains N., asc. gentle E. slope, in canyon bottom.

39.82 The ¼ sec. cor. of secs. 6 and 31, marked by a sandstone 10x16x20 ins., plainly mkd. ¼.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R10E
¼ S31 / S 6
T29S R10E

1964

Place original stone alongside and N. of iron post.

N. 89° 20' W., beginning new measurement.

Asc. 10 ft. over E. slope in canyon bottom.

9.20 Base of steep ascent, bears N. and S. irregularly, asc. 180 ft. over ledgy E. slope.

15.10 Crest of steep ascent, bears N. and S. irregularly, desc. 10 ft. over rolling bench, through heavy growth of shadscale.

40.18 The cor. of Tps. 28 and 29 S., Rs. 9 and 10 E., monumented with a 2½" iron post, marked and witnessed as described in field notes of T. 29 S., R. 9 E., surveyed concurrently under this same group.

Land, broken E. portion, rolling W. portion.
Soil, sandy clay and exposed sandstone.
Timber, none.
Undergrowth, shadscale and scattered bunch grass.

Dependent Resurvey of the Subdivisional Lines, T. 28 S., R. 10 E., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by A. D. Ferron, Deputy Surveyor, in 1883.

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp.

North, bet. secs. 35 and 36.

Over broken desert land, over clay bench.

30.60 Leave bench, desc. 60 ft. over broken clay hills, draining NW.

Dependent Resurvey, T. 28 S., R. 10 E.

CHAINS	
40.74	The ¼ sec. cor. of secs. 35 and 36, marked by a sandstone 4x6x18 ins., plainly mkd. ¼. At the corner point Set an iron post 30 ins. long, 2½ ins. diam., 10 ins. in the ground, in a collar of stone, with brass cap mkd, T28S R10E ¼ S35 | S36 1964 Place original stone alongside and W. of iron post. Cor. falls on S. slope of small clay hill.
	N. 0° 19' E., beginning new measurement. Desc. 30 ft. over irregular clay hills, draining NW.
7.80	Small hollow, drains W., asc. 55 ft. over irregular SW. slope.
18.90	Low clay ridge, bears NW. and curves S., desc. 175 ft. over irregular NE. slope, over clay hills.
28.00	Base of clay hills, desc. 35 ft. over gentle N. slope.
39.80	Point for the cor. of secs. 25, 26, 35 and 36, at proportionate distance; there is no remaining evidence of original corner. Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T28S R10E S26 | S25 S35 | S36 1964 Raise a mound of stone 3 ft. base, 2½ ft. high W. of corner. Land, broken. Soil, clay, sand and exposed sandstone. Timber, none. Undergrowth, shadscale.
	From the true point for the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp. (From which its witness cor. bears S. 0° 06' W., 1.00 ch. dist.) N. 89° 45' W., bet. secs. 25 and 36. Over broken desert land, along S. slope of impassable clay and sandstone hills. By traverse.
24.00	Leave hills, desc. 30 ft. over gentle W. slope. End traverse.

Dependent Resurvey, T. 28 S., R. 10 E.

CHAINS	
28.50	Small wash, drains SW., 8 chs., thence W.
40.05	The ¼ sec. cor. of secs. 25 and 36, marked by a granite stone 6x10x20 ins., plainly mkd. ¼.
	Note: Original record erroneously described this cor. as a sandstone.
	At the corner point
	Set an iron post 36 ins. long, 1 in. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.
	T28S R10E ¼ S25/S36 1964
	Place original stone alongside and N. of iron post.
	N. 89° 31' W., beginning new measurement.
	Continue over desert land, draining N.
13.80	Small wash, drains NW.
20.50	Wash, 2 ft. deep, 30 lks. wide, drains N.
28.20	Rise, slopes N., desc. 15 ft. over gentle W. slope.
37.80	Small wash, drains NE. asc. gentle E. slope.
40.22	The cor. of secs. 25, 26, 35 and 36.
	Land, broken. Soil, sand, clay and exposed sandstone. Timber, none. Undergrowth, shadscale and bunch grass.
	N. 0° 25' W., bet. secs. 25 and 26.
	Over broken desert land, desc. 10 ft. over NE. slope.
3.10	Small wash, drains NE., asc. 25 ft. over land draining E.
11.90	Clay rise, bears E. and W., desc. 70 ft. along broken E. slope, over clay spurs.
37.30	Wash area, 2 ft. deep, 2 chs. wide, drains NW., desc. gentle N. slope.
39.50	Point for the ¼ sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of original corner.
	Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

CHAINS	
	T28S R10E ¼ S26 | S25 1964
	Asc. 30 ft. over irregular sandstone and red clay hills.
52.00	Sandstone and clay rise, bears E. and W., desc. 30 ft. over NW. slope.
60.00	Swale, drains NE., asc. 65 ft. over broken SW. slope.
79.60	The cor. of secs. 23, 24, 25 and 26, marked by a sandstone 6x14x20 ins., plainly mkd. 2 notches on S. and 1 notch on E. face. At the corner point Set an iron post 30 ins. long, 2½ ins. diam., 10 ins. in the ground, in a mound of stone 4 ft. base, to top, with brass cap mkd. T28S R10E S23 | S24 S26 | S25 1964 Place original stone alongside and W. of iron post. Land, broken. Soil, clay, sand and exposed sandstone. Timber, none. Undergrowth, shadscale.
	From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp. S. 88° 56' W., bet. secs. 24 and 25. Over broken land of Pinto Hills, desc. 20 ft. along S. slope of ridge.
11.40	W. end of ridge, desc. 185 ft. over W. slope.
26.20	Wash in bottom of hollow, drains SW., asc. 80 ft. over irregular E. slope, over sandstone formation.
41.07	The ¼ sec. cor. of secs. 24 and 25, marked by a sandstone 6x10x18 ins., plainly mkd. ¼. At the corner point Set an iron post 36 ins. long, 1 in. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R10E ¼ S24 / S25 1964 Place original stone alongside and N. of iron post.

Dependent Resurvey, T. 28 S., R. 10 E.

CHAINS	
	N. 89° 43' W., beginning new measurement.
	Asc. 10 ft. along broken N. slope.
8.00	Low sandstone point, projects N., desc. 105 ft. over broken SW. slope.
24.60	Wash, 2 ft. deep, 30 lks. wide, drains N., asc. 60 ft. over E. slope.
30.00	Spur, slopes NE., asc. 15 ft. along top of sandstone rise.
39.90	The cor. of secs. 23, 24, 25 and 26.
	Land, broken. Soil, sand, clay and exposed sandstone. Timber, none. Undergrowth, very scattered shadscale.
	N. 0° 30' E., bet. secs. 23 and 24.
	Over broken desert land, on top of sandstone rise.
1.50	N. crest of rise, bears NW. and E., desc. 50 ft. over NE. slope.
5.20	Wash in hollow, drains NE., asc. 60 ft. over irregular SW. slope.
31.90	Top of rise, bears E. and SW., desc. 80 ft. over N. slope, into Fremont River Canyon.
34.20	Right bank of Fremont River, bears NE. and SW., thence over river bed.
40.19	Left bank Fremont River, bears NE. and SW., also point for the ¼ sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of original corner, falls in sandy flood area of river channel and cannot be perpetuated.
45.19	Point selected for the witness ¼ sec. cor. of secs. 23 and 24.
	Set an iron post 36 ins. long, 1 in. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R10E ¼ S23|S24 W C 1964
	Asc. 20 ft. over river canyon bottom, through dense brush.
79.30	Highway U-24, bears N. 71° 02' E. and S. 71° 02' W., asc. 15 ft. over S. slope of small hill.
80.38	Point for the cor. of secs. 13, 14, 23 and 24, at proportionate distance; there is no remaining evidence of original corner.

Dependent Resurvey, T. 28 S., R. 10 E.

CHAINS	
	Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R10E S14 | S13 S23 | S24 1964 Land, broken. Soil, gravelly, clay in river bottom. Timber, few cottonwood along river. Undergrowth, shadscale, sagebrush and greasewood in river bottom.
	From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp. S. 89° 44' W., bet. secs. 13 and 24.
1.50	Small wash, course NE. from SE. Thence over broken desert land, on S. breaks of Fremont River Canyon, over top of point projecting N.
5.80	Crest of steep descent, bears N. and S., desc. 100 ft. over ledgy W. slope of river canyon. By triangulation, topography scaled.
18.00	Right bank Fremont River, bears N. 15° E., S. 15° W., thence over river flowing NE.
21.00	Left bank same river, bears N. 15° E. and S. 15° W., asc. 60 ft. over ledges facing E.
21.50	Crest of ledges, bears N. 15° E. and S., thence over top of point projecting S.
28.90	W. side of point, bears S. and curves NW., desc. 50 ft. over ledgy W. slope. End triangulation.
30.24	Point selected for the witness ¼ sec. cor. of secs. 13 and 24. Set an iron post 30 ins. long, 2½ ins. diam., 4 ins. in the ground, to bedrock, in a mound of stone 4 ft. base, to top, with brass cap mkd. T28S R10E ¼ W S13 C S24 1964
30.90	Left bank same river, bears S. and curves NW., thence over river flowing S.
34.20	Right bank same river, bears S. and curves NW., thence over N. end of sandy point.
40.04	Point for the ¼ sec. cor. of secs. 13 and 24, at proportionate distance; there is no evidence of original corner.

Dependent Resurvey, T. 28 S., R. 10 E.

CHAINS	
	Set an iron post 36 ins. long, 1 in. diam., 32 ins. in the ground, in a collar of stone from base of pipe to top, with brass cap mkd. T28S R10E ¼ S13/S24 1964 Note: this corner falls on N. end of sandy point and will probably be removed by floods at some future date, therefore the witness corner previously described was also established for this corner. Continue over N. end of sandy point.
46.00	Right bank same river, bears SW. and curves NE., thence over river, flowing NE.
52.50	Left bank same river, bears SW. and curves NE., asc. 20 ft. over gentle S. slope in canyon bottom, through heavy brush.
77.50	Highway, U-24, bears N. 71° 12' E. and S. 71° 02' W.
79.00	Graded dirt road, bears N. 10° E. and S. 10° W., 1 ch. to highway, asc. 15 ft. along S. slope of small hill.
80.08	The cor. of secs. 13, 14, 23 and 24. Land, broken, rolling in river bottom. Soil, gravelly with exposed sandstone, clay in river bottom land. Timber, few cottonwood along river. Undergrowth, shadscale with sage and greasewood in river bottom.
	N. 0° 09' E., bet. secs. 13 and 14. Over broken desert land, asc. 30 ft. along irregular E. slope of spur.
2.50	Power line, bears N. 70° E., S. 70° W.
28.30	Base of steep ascent, bears S. and NE., asc. 250 ft. over ledgy SE. slope.
39.50	Ridge top, 1 ch. wide, bears E. and SW., desc. 15 ft. over N. slope of ridge.
40.19	The ¼ sec. cor. of secs. 13 and 14, marked by a sandstone 5x15x20 ins., plainly mkd. ¼. At the corner point Set an iron post 36 ins. long, 1 in. diam., 3 ins. in the ground, in a mound of stone 4 ft. base, to top, with brass cap mkd. T28S R10E ¼ S14 | S13 1964

Dependent Resurvey, T. 28 S., R. 10 E.

CHAINS	
	Place original corner alongside and W. of iron post.
	N. 0° 09' W., beginning new measurement.
	Desc. 175 ft. over broken NE. slope.
12.20	Base of steep descent, bears NW. and SE. irregularly, desc. 25 ft. over rolling clay hills.
14.00	Small wash, drains E.
22.00	Top of clay knoll, 2 chs. diam.
37.70	Small wash, drains SE.
40.26	The corner of secs. 11, 12, 13 and 14, a sandstone 6x10x18 ins., plainly mkd. 4 notches on S. and 1 notch on E. face.
	At the corner point
	Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.
	T28S R10E S11 | S12 S14 | S13 1964
	Place original stone alongside and W. of iron post.
	Land, broken. Soil, sand, clay and exposed sandstone. Timber, none. Undergrowth, scattered shadscale.
	From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp.
	S. 88° 37' W., bet. secs. 12 and 13.
	Over broken desert land, across red clay hills, draining E.
4.00	Wash, 3 ft. deep, 20 lks. wide, drains SE., 5 chs. thence S.
18.50	Bulldozed road, bears S. and curves NE.
40.24	The ¼ sec. cor. of secs. 12 and 13, marked by a sandstone 3x12x16 ins., plainly mkd. ¼.
	At the corner point
	Set an iron post 36 ins. long, 1 in. diam., 6 ins. in the ground, in a mound of stone 4 ft. base, to top, with brass cap mkd.
	T28S R10E ¼ S12 S13 1964

Dependent Resurvey, T. 28 S., R. 10 E.

CHAINS	
	Place original stone alongside and W. of iron post.
	S. 89° 47' W., beginning new measurement.
	Continue over broken formation of red clay, sandstone and gypsum breaks.
17.60	Enter chain of low red clay hills, bearing N. and S. irregularly.
39.99	The cor. of secs. 11, 12, 13 and 14.
	Land, broken. Soil, red clay, sand and exposed sandstone. Timber, none. Undergrowth, very scattered shadscale.
	N. 0° 46' E., bet. secs. 11 and 12.
	Over broken desert land, asc. 35 ft. over land draining SE.
23.30	Crest of small chain of hills, bears NW. and SE. irregularly, desc. 60 ft. over gentle NE. slope.
40.66	The ¼ sec. cor. of secs. 11 and 12, marked by a sandstone 10x16x24 ins., plainly mkd. ¼.
	At the corner point
	Set an iron post 36 ins. long, 1 in. diam., 20 ins. in the ground, in a mound of stone 3 ft. base, to top, with brass cap mkd. T28S R10E ¼ S11 | S12 1964
	Place original stone alongside and W. of iron post.
	N. 0° 08' W., beginning new measurement.
	Continue over irregular clay and sandstone formation, draining SE.
7.40	Wash, 3 ft. deep, 30 lks. wide, drains SE., asc. gentle SE. slope.
20.00	Base of steep ascent, bears E. and W. irregularly, asc. 105 ft. over broken S. slope.
26.30	Low ridge, bears NE. and SW., desc. 90 ft. over NW. slope.
34.20	Base of steep descent, bears NE. and SW., desc. gentle NW. slope.

Dependent Resurvey, T. 28 S., R. 10 E.

CHAINS	
39.70	The cor. of secs. 1, 2, 11 and 12, determined by a mound of stone foreign to this area, marks have weathered away. Note: Original record describes a sandstone, 4x16x24 ins. At the corner point Set an iron post 30 ins. long, 2½ ins. diam., 10 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. T28S R10E S 2 | S 1 S11 | S12 1964 Land, broken. Soil, sand, clay and exposed sandstone. Timber, none. Undergrowth, scattered shadscale.
	From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp. S. 89° 23' W., bet. secs. 1 and 12. Over broken sandy desert land, asc. 75 ft. over E. slope.
15.80	Crest of sandy rise, bears N. and S., desc. 70 ft. over gentle W. slope.
39.03	The ¼ sec. cor. of secs. 1 and 12, a sandstone 3x8x12 in small mound of stone, marks have weathered away. At the corner point Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R10E ¼ S 1 / S12 1964 Place original stone alongside the iron post.
	N. 89° 56' W., beginning new measurement. Asc. 50 ft. over E. slope.
15.10	E. crest of clay ridge, bears N. and S., thence over ridge.
22.90	W. crest same ridge, bears NE. and SW., desc. 55 ft. over NW. slope.
27.20	Base same ridge, bears NE. and SW., desc. 10 ft. in small basin.

Dependent Resurvey, T. 28 S., R. 10 E.

CHAINS	
41.67	The cor. of secs. 1, 2, 11 and 12.
	Land, broken. Soil, sand, clay and exposed sandstone. Timber, none. Undergrowth, shadscale and bunch grass.
	N. 0° 48' E., bet. secs. 1 and 2.
	Over broken clay desert land with very little vegetation, asc. 50 ft. over SW. slope
4.00	Small wash, drains SW.
22.00	Small wash, drains SW.
40.50	The ¼ sec. cor. of secs. 1 and 2, marked by a sandstone 6x10x20 ins., dimly mkd. ¼.
	At the corner point
	Set an iron post 36 ins. long, 1 in. diam., 10 ins. in the ground, in a mound of stone 4 ft. base, 20 ins. high, with brass cap mkd.
	T28S R10E ¼ S 2 | S 1 1964
	Place original stone alongside and W. of iron post.
	N. 0° 30' E., beginning new measurement.
	Asc. 30 ft. over barren clay land.
38.10	Asc. along N. slope of small clay knoll.
40.16	The cor. of secs. 1 and 2, on the N. bdy., marked by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the official record of the resurvey of the S. bdy. of T. 27 S., R. 10 E., in 1954.
	Land, broken. Soil, sand, clay and exposed sandstone. Timber, none. Undergrowth, very scattered shadscale.
	From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp.
	N. 0° 02' E., bet. secs. 34 and 35.
	Over broken desert land, desc. 20 ft. over gentle N. slope.
39.42	The ¼ sec. cor. of secs. 34 and 35, marked by a sandstone 6x10x22 ins., plainly mkd. ¼.

CHAINS	
	At the corner point
	Set an iron post 36 ins. long, 1 in. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R10E ¼ S34|S35 1964
	Place original stone alongside and W. of iron post.
	N. 0° 13' E., beginning new measurement.
	Continue over broken desert land.
.40	Crest of rim, on point, curves SW. and SE., desc. 85 ft. over N. slope and ledges facing N.
5.20	Birch Creek, drains NW., asc. 90 ft. over ledgy S. slope, Creek dry at time of survey.
9.40	Crest of rim, bears W. and curves SE., asc. 20 ft. over broken desert land.
14.00	Cove in E. breaks of Birch Creek, continue over broken desert land.
40.97	The cor. of secs. 26, 27, 34 and 35, marked by a sandstone 8x12x20 ins., plainly mkd. 1 notch on S. and 2 notches on E. face.
	At the corner point
	Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R10E S27|S26 S34|S35 1964
	Place original stone alongside and W. of iron post.
	Land, broken. Soil, sand and exposed sandstone. Timber, none. Undergrowth, shadscale and bunch grass.
	From the cor. of secs. 25, 26, 35 and 36.
	S. 89° 54' W., bet. secs. 26 and 35.
	Over broken desert land, desc. 15 ft. over W. slope.
2.90	Small wash, drains NE., asc. 55 ft. over NE. slope.
15.30	Spur, slopes NE., desc. 50 ft. over W. slope.
17.30	Small draw, drains NE., asc. 75 ft. over E. slope.

Dependent Resurvey, T. 28 S., R. 10 E.

CHAINS	
26.00	Low ridge, bears S. and NE., asc. 15 ft. over irregular E. slope.
40.37	The ¼ sec. cor. of secs. 26 and 35, marked by a sandstone 4x10x18 ins., plainly mkd. ¼. At the corner point Set an iron post 36 ins. long, 1 in. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R10E ¼ S26 / S35 1964 Place original stone alongside and N. of iron post.
	N. 89° 37' W., beginning new measurement. Asc. 20 ft. over SE. slope.
7.80	Low clay ridge, bears S. and NE., desc. 70 ft. over W. slope.
14.20	Small hollow, drains NW., asc. 140 ft. over rocky E. slope.
24.50	E. crest of bench, bears N. and SE., thence over broken sandstone bench.
40.08	The cor. of secs. 26, 27, 34 and 35. Land, broken. Soil, sand, clay and exposed sandstone. Timber, none. Undergrowth, shadscale.
	N. 0° 16' E., bet. secs. 26 and 27. Over broken sandstone bench.
39.80	The ¼ sec. cor. of secs. 26 and 27, marked by a sandstone 6x8x18 ins., plainly mkd. ¼. At the corner point Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R10E ¼ S27 | S26 1964 Place original stone alongside and W. of iron post.

CHAINS	
	N. 0° 05' E., beginning new measurement.
	Continue over bench, across patches of barren sandstone.
24.00	N. crest of bench, bears SW. and curves SE., desc. 165 ft. over irregular NW. slope.
37.40	Small draw, drains NE., asc. 105 ft. over rocky SE. slope.
39.99	Point for the cor. of secs. 22, 23, 26 and 27, at proportionate distance; there is no remaining evidence of original corner, falls on steep and rocky SE. slope and cannot be perpetuated.
	Land, broken. Soil, sand and exposed sandstone. Timber, none. Undergrowth, shadscale and scattered bunch grass.
	From the cor. of secs. 23, 24, 25 and 26.
	N. 89° 43' W., bet. secs. 23 and 26.
	Over broken desert land of sandstone and clay, asc. 45 ft. over E. slope.
1.80	Low ridge, bears N. and SE., desc. 110 ft. over W. slope.
5.00	Base of ridge, bears N. and SE., thence over sandy land.
14.50	Wash, 4 ft. deep, 20 lks. wide, drains N., asc. 105 ft. over irregular E. slope.
26.00	Low ridge, bears N. and S. irregularly, desc. 45 ft. over W. slope.
40.13	The ¼ sec. cor. of secs. 23 and 26, marked by a sandstone 6x16x24 ins., plainly mkd. ¼.
	At the corner point
	Set an iron post 36 ins. long, 1 in. diam., 18 ins. in the ground, in a mound of stone 3 ft. base, to top, with brass cap mkd.
	T28S R10E ¼ S23/S26 1964
	Place original stone alongside and N. of iron post.
	N. 89° 42' W., beginning new measurement.
	Desc. 20 ft. over W. slope.
.60	[illegible] 11 draw, drains SW., asc. 115 ft. over irregular SE. slope.
13.70	[illegible]. end of ridge, bears N. and slopes sharply S., desc. 145 ft. over W. slope.

Dependent Resurvey, T. 28 S., R. 10 E.

CHAINS	
28.10	Wash in draw, drains N. irregularly, asc. 80 ft. over E. slope.
32.50	Spur, slopes N., desc. 60 ft. over W. slope.
37.80	Small draw, drains NE., asc. 100 ft. over SE. slope.
39.46	The true point for the cor. of secs. 22, 23, 26 and 27.
	Land, broken. Soil, sand, clay and exposed sandstone. Timber, none. Undergrowth, very scattered shadscale.

N. 0° 04' W., bet. secs. 22 and 23.

Over broken desert land, asc. 30 ft. along broken E. slope.

.50 The point selected for the witness cor. of secs. 22, 23, 26 and 27.

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R10E
S22 | S23
S27 | S26
W C
1964

7.00 Gully, drains E.

15.30 Top of ascent on high point projecting E. from bench, desc. 125 ft. over irregular N. slope.

27.50 Draw, drains E., asc. 105 ft. over irregular S. slope.

33.30 Top of ascent on rim, bears E. and curves SW., thence over small gravel bench.

39.99 The ¼ sec. cor. of secs. 22 and 23, marked by a sandstone 4x8x20 ins., plainly mkd. ¼.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R10E
¼
S22 | S23
1964

Place original stone alongside and W. of iron post.

N. 0° 30' E., beginning new measurement.

Desc. 105 ft. over ledgy N. slope, into Fremont River Canyon.

Dependent Resurvey, T. 28 S., R. 10 E.

CHAINS	
3.50	Base of ledgy N. slope, bears E. and W. irregularly, thence over river bottom land.
7.70	Right bank Fremont River, bears E. and W. irregularly, thence over river, which flows E. irregularly.
13.80	Left bank of same river, bears E. and W. irregularly, asc. 10 ft. over gentle S. slope of river bottom, through dense brush.
29.80	Highway, U-24, bears N. 84° 34' E. and S. 84° 34' W.
33.10	Power line, bears E. and W.
35.60	Base of ascent, bears E. and W. irregularly, asc. 120 ft. over rocky S. slope, leave river bottom land.
40.10	The cor. of secs. 14, 15, 22 and 23, marked by a sandstone 8x8x20 ins., plainly mkd. 3 notches on S. and 2 notches on E. face.
	At the corner point
	Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T28S R10E S15 | S14 S22 | S23 1964
	Place original stone alongside and W. of iron post.
	Land, broken, level in river bottom. Soil, sand, clay and exposed sandstone. Timber, few cottonwood on river bottom. Undergrowth, shadscale with heavy brush and willows along river.
	From the corner of secs. 13, 14, 23 and 24.
	S. 89° 49' W., bet. secs. 14 and 23.
	Over broken desert land, asc. 45 ft. over SE. slope of spur.
5.50	Spur, slopes S., about 3 chs. to highway, desc. 35 ft. over W. slope.
8.50	Base of spur, bears N. and S., also power line, bears N. 85° E. and S. 85° W., thence along gentle S. slope.
34.20	Base of ascent, bears N. and curves SW., asc. 185 ft. over E. slope.
39.80	Spur, slopes SE., desc. along S. slope.
40.39	The ¼ sec. cor. of secs. 14 and 23, marked by a sandstone, 6x6x16 ins., plainly mkd. ¼.
	Note: original record erroneously describes a sandstone 6x6x5 ft.

Dependent Resurvey, T. 28 S., R. 10 E.

CHAINS	
	At the corner point
	Set an iron post 30 ins. long, 2½ ins. diam., 6 ins. in the ground, in a mound of stone 4 ft. base, to top, with brass cap mkd.
	T28S R10E ¼ S14/S23 1964
	Place original stone alongside and N. of iron post.
	N. 89° 50' W., beginning new measurement.
	Desc. 80 ft. along S. slope.
5.10	Small draw, drains SW., asc. 140 ft. along irregular S. slope.
17.90	Ridge, bears N. and S., desc. 170 ft. over broken W. slope.
31.16	Wash in small draw, drains SW., asc. 220 ft. over NE. slope.
39.30	Spur, slopes SE., desc. 35 ft. along S. slope.
39.75	The cor. of secs. 14, 15, 22 and 23.
	Land, broken. Soil, gravelly sand and clay. Timber, none. Undergrowth, shadscale and scattered bunch grass.
	N. 0° 52' E., bet. secs. 14 and 15.
	Over broken desert land, asc. 50 ft. over S. slope of spur.
1.80	Spur, slopes SE., desc. 160 ft. over NE. slope.
7.90	Small draw, drains SE., asc. 145 ft. over S. slope.
10.90	S. crest of bench, bears E. and W. irregularly, asc. 10 ft. over bench.
39.86	The ¼ sec. cor. of secs. 14 and 15, marked by a sandstone 6x10x14 ins., plainly mkd. ¼.
	At the corner point
	Set an iron post 36 ins. long, 1 in. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.
	T28S R10E ¼ S15|S14 1964

CHAINS	
	Place original stone alongside and W. of iron post.
	N. 0° 12' E., beginning new measurement.
	Asc. 15 ft. over bench land, draining W.
8.00	Small wash, drains W.
40.23	The cor. of secs. 10, 11, 14 and 15, marked by a sandstone 4x10x16 ins., mkd. 4 notches on S. and 2 notches on E. face.
	At the corner point
	Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T28S R10E S10 | S11 S15 | S14 1964
	Place original stone alongside and W. of iron post.
	Land, broken. Soil, sand, clay and exposed sandstone. Timber, none. Undergrowth, shadscale.
	From the cor. of secs. 11, 12, 13 and 14.
	S. 89° 45' W., bet. secs. 11 and 14.
	Over broken desert land, across irregular red clay hills, bearing N. and S. Asc. 30 ft.
17.70	Base of steep ascent, bears S. and curves NW., asc. 155 ft. over NE. slope.
28.80	Crest of ascent on rim, bears N. and curves SE., thence over sandy bench.
39.65	Point for the ¼ sec. cor. of secs. 11 and 14, at midpoint there is no remaining evidence of original corner.
	Set an iron post 36 ins. long, 1 in. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T28S R10E ¼ S11 / S14 1964
	Desc. 45 ft. over rolling bench, draining SW.
79.30	The cor. of secs. 10, 11, 14 and 15.

Dependent Resurvey, T. 28 S., R. 10 E.

CHAINS

Land, broken E. portion, rolling W. portion.
Soil, clay E. portion, sand and exposed sandstone W. portion.
Timber, none.
Undergrowth, shadscale and scattered bunch grass.

N. 0° 24' E., bet. secs. 10 and 11.

Over rolling bench land, desc. 30 ft. along gentle W. slope.

21.70 Wash, 4 ft. deep, 20 lks. wide, drains SW., asc. 40 ft. over gentle SE. slope.

40.29 The ¼ sec. cor. of secs. 10 and 11, marked by a sandst[illegible] 3x8x15 ins., plainly mkd. ¼.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R10E
¼
S10|S11
1964

Place original stone alongside and W. of iron post.

N. 0° 04' E., beginning new measurement.

Desc. 15 ft. over rolling bench.

40.36 Point for the cor. of secs. 2, 3, 10 and 11, at proportionate distance; there is no remaining evidence of original corner.

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R10E
S 3|S 2
S10|S11
1964

Land, rolling.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, shadscale and bunch grass.

From the cor. of secs. 1, 2, 11 and 12.

S. 89° 40' W., bet. secs. 2 and 11.

Over broken desert land, over irregular clay hills, asc. 40 ft.

.40 Small wash, drains SW.

Dependent Resurvey, T. 28 S., R. 10 E.

CHAINS	
26.50	Enter irregular low red clay hills.
38.98	The ¼ sec. cor. of secs. 2 and 11, marked by a sandstone 4x10x16 ins., plainly mkd. ¼. At the corner point Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R10E ¼ S 2 / S11 1964 Place original stone alongside and N. of iron post. Cor. falls at base of bluff, which bears N. and S. irregularly.
	N. 89° 38' W., beginning new measurement. Asc. 80 ft. over ledgy E. slope.
2.50	Crest of bluff, bears N. and S. irregularly, desc. 35 ft. over gentle W. slope of bench.
31.50	Crest of low terrace, bears N. and S. irregularly, desc. 15 ft. over W. slope of terrace.
40.45	The cor. of secs. 2, 3, 10 and 11. Land, mostly rolling. Soil, sand, clay and exposed sandstone. Timber, none. Undergrowth, shadscale.
	N. 0° 05' E., bet. secs. 2 and 3. Over rolling desert land, desc. 25 ft. over gentle SW. slope.
8.00	Wash, 2 ft. deep, 20 lks. wide, drains SW., asc. 25 ft. over SE. slope.
11.70	Top of clay hill, bears E. and W., desc. 10 ft. along gentle W. slope.
36.50	Small wash, drains SW., asc. 5 ft. over gentle SW. slope.
40.36	Point for the ¼ sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of original corner. Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R10E ¼ S 3 | S 2 1964

Dependent Resurvey, T. 28 S., R. 10 E.

CHAINS

Asc. 20 ft. over rolling desert land.

80.72 The cor. of secs. 2 and 3, on the N. bdy. of the Tp., an iron post 2½ ins. diam., set, mkd. and witnessed as described in the official record of the resurvey of the S. bdy. of T. 27 S., R. 10 E., in 1954.

Land, rolling.
Soil, sandy clay.
Timber, none.
Undergrowth, shadscale.

From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp.

N. 0° 31' E., bet. secs. 33 and 34.

Over broken desert clay land, draining NE., desc. 50 ft.

25.50 Wash, 2 ft. deep, 20 lks. wide, drains NE., continue over broken clay land.

40.46 The ¼ sec. cor. of secs. 33 and 34, marked by a sandstone 4x14x20 ins., plainly mkd. ¼.

Note: Original record describes this sandstone as a "slate".

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R10E
¼
S33 | S34
1964

Place original stone alongside and W. of iron post.

N. 0° 48' E., beginning new measurement.

Desc. 85 ft. over clay hills, draining NE.

13.70 Wash, 2 ft. deep, 20 lks. wide, drains N. from S. 20° W., irregularly, desc. 20 ft. down small hollow.

29.90 Same wash, drains NE. from S., desc. 20 ft. over clay breaks, draining NE.

40.53 The cor. of secs. 27, 28, 33 and 34, marked by a sandstone 6x10x14 ins., in a mound of stone, marks have weathered away.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

CHAINS	
	T28S R10E S28 | S27 S33 | S34 1964 Place original stone alongside the iron post. Land, broken. Soil, clay. Timber, none. Undergrowth, scattered shadscale.
	From the cor. of secs. 26, 27, 34 and 35. N. 89° 57' W., bet. secs. 27 and 34. Over broken land, desc. gentle W. slope.
8.20	E. side of gulch, bears N. and S. irregularly, desc. 125 ft. over ledgy W. slope.
12.30	Birch Creek, dry, drains NW. irregularly, asc. 120 ft. over ledgy E. slope.
16.10	W. side same gulch, bears N. and S. irregularly, desc. 35 ft. over bench.
35.70	Small wash, drains NE., turning sharply to NW., then N.
39.79	The ¼ sec. cor. of secs. 27 and 34, marked by a granite stone 4x8x16 ins., plainly mkd. ¼. Note: Original record describes this as a sandstone. At the corner point Set an iron post 36 ins. long, 1 in.diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R10E ¼ S27 / S34 1964 Place original stone alongside and N. of iron post.
	N. 89° 55' W., beginning new measurement. Continue over broken clay bench, draining N.
1.70	Small wash, drains N., asc. 35 ft. over bench.
11.40	Top of rise, bears N. and S., desc. 30 ft. over bench.
14.50	Small wash, drains NE.
40.18	The cor. of secs. 27, 28, 33 and 34.

Dependent Resurvey, T. 28 S., R. 10 E.

CHAINS

Land, broken.
Soil, sand, clay and exposed sandstone.
Timber, none.
Undergrowth, shadscale.

N. 0° 08' E., bet. secs. 27 and 28.

Over broken land, draining NE., desc. 25 ft.

18.60 Wash, 3 ft. deep, 20 lks. wide, drains NE., asc. 30 ft. over clay breaks, draining NE.

39.75 The ¼ sec. cor. of secs. 27 and 28, determined by a sandstone 5x8x12 ins., in small mound of stone, marks weathered away.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R10E
¼
S28 | S27
1964

Place original stone alongside the iron post.

Cor. falls at base of clay terrace, facing S.

N. 0° 27' E., beginning new measurement.

Asc. 20 ft. over SE. slope of low terrace.

5.00 Crest of terrace, bears NE. and SW., asc. 10 ft. over broken clay hills.

36.50 Crest low terrace, bears NE. and SW., thence over broken brown gravel hills.

39.96 The cor. of secs. 21, 22, 27 and 28, marked by a sandstone 6x14x20 ins., plainly mkd. 2 notches on S. and 3 notches on E. face.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R10E
S21 | S22
S28 | S27
1964

Place original stone alongside and W. of iron post.

Land, broken.
Soil, clay.
Timber, none.
Undergrowth, very scattered shadscale.

CHAINS	
	From the true point for the cor. of secs. 22, 23, 26 and 27, (from which its witness cor. bears N. 0° 04' W., 0.50 chs. dist.)
	S. 89° 54' W., bet. secs. 22 and 27.
	Over broken desert land, across sandstone and clay formation, asc. 65 ft. over E. slope.
9.00	Low ridge, bears N. and S., desc. 30 ft. over gentle W. slope.
33.10	Rim, bears N. and S. irregularly, desc. 120 ft. over ledgy W. slope.
35.50	Base same rim, bears N. and S. irregularly, thence over small canyon bottom.
39.60	Birch Creek, dry, drains N. irregularly, asc. E. slope.
39.81	The ¼ sec. cor. of secs. 22 and 27, marked by a sandstone 6x10x20 ins., plainly mkd. ¼.
	At the corner point
	Set an iron post 36 ins. long, 1 in. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.
	T28S R10E ¼ S22/S27 1964
	Place original stone alongside and N. of iron post.
	N. 89° 53' W., beginning new measurement.
	Asc. 90 ft. over ledgy E. slope.
6.30	Crest of rim, bears N. and S. irregularly, asc. 15 ft. over gentle E. slope of bench.
19.60	Rise, bears N. and S., desc. 35 ft. over W. slope.
28.30	Wash, 4 ft. deep, 20 lks. wide, drains N., asc. 55 ft. over E. slope.
37.30	Low hill, bears N. and S., thence over broken clay bench, draining NE.
39.98	The cor. of secs. 21, 22, 27 and 28.
	Land, broken. Soil, sand, clay and exposed sandstone. Timber, none. Undergrowth, shadscale.
	N. 0° 04' E., bet. secs. 21 and 22.
	Over broken desert land, over brown gravelly hills, draining NE.
19.30	Crest steep descent, curves SE. and SW., desc. 80 ft. over N. slope.

Dependent Resurvey, T. 28 S., R. 10 E.

CHAINS

28.20 Wash in small hollow, drains N. 10° E., desc. down hollc

35.30 Base of gravelly spur, bears NE. and SW., asc. 65 ft. over SE. slope.

38.40 Spur, slopes NE., desc. 25 ft. over NW. slope.

39.89 The ¼ sec. cor. of secs. 21 and 22, marked by a black lava stone 8x8x16 ins., plainly mkd. ¼.

Note: Original record describes this as a sandstone.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R10E
¼
S21 | S22
1964

Place original stone alongside and W. of iron post.

N. 0° 09' W., beginning new measurement.

Desc. 60 ft. over NW. slope of spur.

4.00 Base of spur, bears NE. and SW., desc. 30 ft. over gentle N. slope in Fremont River Canyon, down small cove.

18.00 Leave mouth of cove.

21.00 Right bank of Fremont river channel, bears E. and W. irregularly, thence over river, flowing E. This is new channel made by highway.

24.20 Left bank same river, bears E. and W. irregularly, thence over river bottom, through willows.

39.00 Leave river bottom, asc. 25 ft. over embankment facing S., enter small hills.

40.52 The cor. of secs. 15, 16, 21 and 22, marked by a black lava stone 14x24x30 ins., plainly mkd. 3 notches on S. and E. faces.

Note: Original record describes this as a trachyte stone.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R10E
S16 | S15
S21 | S22
1964

Place original stone alongside and W. of iron post.

CHAINS	
	Cor. falls on W. slope of small clay hill. Land, broken, with level river bottom land. Soil, sand, clay and rocky. Timber, few cottonwood on river bottom. Undergrowth, shadscale, willows along river.
	From the cor. of secs. 14, 15, 22 and 23. N. 89° 53' W., bet. secs. 15 and 22. Over broken desert land, desc. 105 ft. along S. slope.
12.00	Base of hill, bears NW. and SE., 25 ft. along S. slope, in cove.
20.20	Gully, drains S., also base of steep ascent, bears N. and S., asc. 90 ft. over ledgy E. slope.
24.50	Crest of rim, bears NE. and S., asc. 15 ft. along broken S. slope.
32.40	Crest low rim, bears NE. and SW., thence over point, projecting S.
39.27	The ¼ sec. cor. of secs. 15 and 22, marked by a granite stone 3x8x10 ins., plainly mkd. ¼. At the corner point Set an iron post 36 ins. long, 1 in. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R10E ¼ S15/S22 1964 Place original stone alongside and N. of iron post.
	N. 89° 39' W., beginning new measurement. Continue over point, which projects S.
1.60	W. crest of point, bears NE. and SW., 4 chs. to end, desc. 100 ft. over ledgy W. slope.
4.30	Power line, 3 strand, bears N. 70° W. and S. 70° E., also base of ledgy descent, thence over valley land.
10.00	Highway, hard surface, bears N. 84° 15' W., and curves SE.
13.20	Enter neck of Fremont River bed; water has been diverted to new channel to south by highway work.
29.00	Leave old river channel.
35.00	Low gravelly rise, slopes S., 4 chs. to river bottom.

Dependent Resurvey, T. 28 S., R. 10 E.

CHAINS

40.10 Low gravelly clay rise, slopes S., desc. 20 ft. over W. slope.

40.88 The corner of secs. 15, 16, 21 and 22.

Land, broken E. portion, river bottom W. portion.
Soil, sand and exposed sandstone, some clay.
Timber, few cottonwood along river.
Undergrowth, shadscale, willows on river bottom.

N. 0° 31' E., bet. secs. 15 and 16.

Over broken bench land draining S., over small clay hills.

7.10 Highway, U-24, hard surface, bears N. 76° 42' W., and S. 76° 42' E.

13.30 Power line, 3 strand, bears E. and W.

40.09 The ¼ sec. cor. of secs. 15 and 16, marked by a trachyte stone 6x10x22 ins., plainly mkd. ¼.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

R28S R10E
¼
S16 | S15
1964

Place original stone alongside and W. of iron post.

N. 0° 06' W., beginning new measurement.

Asc. 30 ft. over rolling blue clay hills.

40.05 Point for the cor. of secs. 9, 10, 15 and 16, at proportionate distance; there is no evidence of original corner.

Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R10E
S 9 | S10
S16 | S15
1964

Set steel fence post beside iron post.

Land, rolling.
Soil, clay.
Timber, none.
Undergrowth, very scattered shadscale.

Dependent Resurvey, T. 28 S., R. 10 E.

CHAINS	
	From the cor. of 10, 11, 14 and 15.
	N. 89° 45' W., bet. secs. 10 and 15.
	Over broken bench land, desc. 35 ft. over gentle W. slope.
12.90	Wash, 3 ft. deep, 20 lks. wide, drains SW., asc. 25 ft. over gentle E. slope.
24.00	Enter barren blue clay hills, draining S.
38.70	Crest low terrace, desc. 10 ft. over W. slope.
40.27	Point for the ¼ sec. cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post 36 ins. long, 1 in. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T28S R10E ¼ S10/S15 1964
	Desc. 15 ft. over W. slope.
51.20	Wash, 6 ft. deep, 10 lks. wide, drains S. 20° W., asc. 35 ft. over gentle E. slope.
63.50	Crest low terrace, bears N. and S. irregularly, asc. 10 ft. over small bench.
80.54	The cor. of secs. 9, 10, 15 and 16.
	Land, broken to rolling clay hills. Soil, sand and clay. Timber, none. Undergrowth, very scattered shadscale.
	N. 0° 38' E., bet. secs. 9 and 10.
	Over rolling blue clay desert land, draining S., asc. 20 ft.
40.05	The ¼ sec. cor. of secs. 9 and 10, marked by a sandstone 4x8x15 ins., dimly mkd. ¼.
	At the corner point
	Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T28S R10E ¼ S 9|S10 1964
	Place original stone alongside and W. of iron post.

Dependent Resurvey, T. 28 S., R. 10 E.

CHAINS

N. 0° 20' E., beginning new measurement.

Asc. 20 ft. over gentle SE. slope.

40.04 The cor. of secs. 3, 4, 9 and 10, marked by a sandstone 4x14x24 ins., marked 5 notches on S. and 3 notches on E. face.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R10E

S 4	S 3
S 9	S10

1964

Place original stone alongside and W. of iron post.

Land, rolling.
Soil, clay.
Timber, none.
Undergrowth, very little shadscale.

From the cor. of secs. 2, 3, 10 and 11.

S. 89° 55' W., bet. secs. 3 and 10.

Over rolling desert land, desc. 15 ft. over gentle W. slope.

14.80 Wash, 2 ft. deep, 10 lks. wide, drains S. 20° W., asc. 10 ft. along gentle S. slope.

23.00 Small wash, drains S. 20° W., asc. 10 ft. along gentle S. slope.

40.08 Point for the ¼ sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of original corner.

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R10E

¼ S 3
S10

1964

Asc. 30 ft. over gentle SE. slope.

43.90 Small wash, drains SE.

63.60 Small wash, drains SE.

80.16 The cor. of secs. 3, 4, 9 and 10.

Land, rolling.
Soil, clay and clay shale.
Timber, none.
Undergrowth, very scattered shadscale.

Dependent Resurvey, T. 28 S., R. 10 E.

CHAINS	
	N. 0° 05' W., bet. secs. 3 and 4.
	Over rolling desert land, over blue clay, asc. 10 ft. over SE. slope.
16.30	Small wash, drains SE.
32.50	Small wash, drains S. 15° E.
40.19	Point for the ¼ sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of original corner.
	Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T28S R10E ¼ S 4 | S 3 1964
	Asc. 55 ft. over SE. slope.
62.50	Base of steep ascent, bears SW. and N. 10° E., asc. 50 ft. over SE. slope.
65.90	Spur, slopes E., desc. 55 ft. over N. slope.
70.50	Gully, drains E., asc. 45 ft. over S. slope.
72.20	Spur, slopes E., desc. 80 ft. over N. slope.
80.98	The cor. of secs. 3 and 4, on the N. bdy. of the Tp., marked by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the official record of the resurvey of the S. bdy. of T. 27 S., R. 10 E., in 1954.
	Land, rolling S. portion, broken N. portion. Soil, clay and clay shale. Timber, none. Undergrowth, very scattered shadscale.
	From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp.
	N. 2° 59' W., bet. secs. 32 and 33.
	Over broken desert land on high bench, over sand and exposed sandstone, asc. 70 ft. over S. slope.
27.50	NE. end of gravel hill, desc. 75 ft. over NW. slope.
33.50	Low sandstone rim, bears NE. and SW., desc. 10 ft. over NW. slope.
40.95	The ¼ sec. cor. of secs. 32 and 33, marked by a sandstone 4x15x20 ins., plainly mkd. ¼.

Dependent Resurvey, T. 28 S., R. 10 E.

CHAINS

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R10E
¼
S32 | S33
1964

Place original stone alongside and W.of iron post.

N. 0° 17' E., beginning new measurement.

Desc. 40 ft. over NW. slope.

16.50 S. crest of deep canyon, bears W. and NE., desc. 300 ft. over ledges facing generally NW. By triangulation, topography scaled.

28.00 Wash in canyon, drains W., asc. 280 ft. over ledges facing S.

29.00 N. crest of canyon, bears SW. and curves SE., thence over broken top of point, which projects NW. End triangulation.

40.81 The cor. of secs. 28, 29, 32 and 33, marked by a mound of sandstone; marks have weathered away.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone 3 ft. base, to top, with brass cap mkd.

T28S R10E
S29 | S28
S32 | S33
1964

Land, broken.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, shadscale.

From the cor. of secs. 27, 28, 33 and 34.

N. 89° 20' W., bet. secs. 28 and 33.

Over broken desert land, over blue clay formation, asc. 30 ft. along irregular N. slope.

8.50 Small wash, drains NE.

37.70 Small wash, drains NE.

40.35 The ¼ sec. cor. of secs. 28 and 33, marked by a sandstone 3x6x16 ins., dimly mkd. ¼.

Dependent Resurvey, T. 28 S., R. 10 E.

CHAINS

At the corner point

Set an iron post 36 ins. long, 1 in. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R10E
¼ S28/S33
1964

Place original stone alongside and N. of iron post.

N. 89° 17' W., beginning new measurement.

Asc. 105 ft. over E. slope, over clay shale ledges. By triangulation with topography scaled.

18.50 Spur, slopes N., asc. 250 ft. over inaccessible ledges facing NE.

41.00 N. crest of point, bears SE. and curves to SW., thence along N. edge of rim. End triangulation.

43.54 The cor. of secs. 28, 29, 32 and 33.

Land, broken.
Soil, clay E. portion, sand and exposed sandstone W. portion.
Timber, none.
Undergrowth, very scattered shadscale.

N. 3° 00' E., bet. secs. 28 and 29.

Over broken desert land, on high point, on N. end of Blue Mesa.

.25 Crest of high rim, curves SE. and SW., desc. 400 ft. over ledges facing N. and broken N. slope. By triangulation, topography scaled.

12.00 Base of steep descent, bears W. and NE. irregularly, desc. over gentle N. slope, in Blue Valley, down small hollow. End triangulation.

35.10 Base of low terrace, bears NW. and S., asc. 70 ft. over SW. slope.

39.00 Crest same terrace, bears NW. and curves to S., thence over small bench.

39.53 Point for the ¼ sec. cor. of secs. 28 and 29, at mid-point; there is no evidence of original corner.

Set an iron post 30 ins. long, 2½ ins. diam., 10 ins. in the ground, in a mound of stone 3 ft. base, to top, with brass cap mkd.

T28S R10E
¼
S29|S28
1964

Dependent Resurvey, T. 28 S., R. 10 E.

CHAINS	
	Desc. 10 ft. over small bench, on E. side of Blue Valley.
57.70	Crest of terrace, bears NE. and SW., desc. 105 ft. over NW. slope.
65.50	Base same terrace, bears NE. and SW., thence over bottom land of Blue Valley, draining N.
79.06	The cor. of secs. 20, 21, 28 and 29, marked by a sandstone 10x16x26 ins., plainly mkd. 2 notches on S. and 4 notches on E. face. At the corner point Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R10E S20 | S21 S29 | S28 1964 Place original stone alongside and W. of iron post. Land, broken S. portion, rolling N. portion. Soil, sand and exposed sandstone S. portion, clay N. portion. Timber, none. Undergrowth, very scattered shadscale.
	From the cor. of secs. 21, 22, 27 and 28. N. 89° 52' W., bet. secs. 21 and 28. Over broken land, over low clay hills, asc. 10 ft. over E. slope.
3.90	Low clay hill, bears N. and S., desc. 70 ft. over W. slope.
10.70	Wash, 2 ft. deep, 20 lks. wide, drains N., thence along N. slope.
23.00	Small wash, drains NE., asc. 75 ft. over irregular E. slope.
32.90	E. crest small bench, bears N. and S. irregularly, thence over bench.
40.02	The ¼ sec. cor. of secs. 21 and 28, marked by a sandstone 3x10x18 ins., plainly mkd. ¼. At the corner point Set an iron post 36 ins. long, 1 in. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R10E ¼ S21 / S28 1964

Dependent Resurvey, T. 28 S., R. 10 E.

CHAINS	
	Place original stone alongside and N. of iron post.
	N. 89° 47' W., beginning new measurement.
	Continue over gravelly bench.
2.50	Small wash, drains NE.
15.90	W. crest bench, bears NE. and SW. irregularly, desc. 85 ft. over NW. slope.
23.80	Base of descent, bears NE. and SW., irregularly, thence over nearly level land of Blue Valley.
40.11	The cor. of secs. 20, 21, 28 and 29.
	Land, broken E. portion; rolling W. portion. Soil, clay with gravel spots. Timber, none. Undergrowth, very scattered shadscale.
	N. 0° 23' E., bet. secs. 20 and 21.
	Over clay land of Blue Valley, draining NE.
2.00	Town Wash 3 ft. deep, 30 lks. wide, drains NE.
39.77	The ¼ sec. cor. of secs. 20 and 21, determined by old fence cor. post. Fences originally ran N., S. and W. from this post, but have been removed, and only a few posts and stubs of posts remain. Accepted as the best available evidence of the original corner position.
	At the corner point
	Set an iron post 36 ins. long, 1 in. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R10E ¼ S20 | S21 1964
	N. 0° 53' W., beginning new measurement.
	Desc. gentle N. slope, in Blue Valley.
2.40	Small hollow, drains E. to river bottom.
27.70	Clay bank, bears W. and curves SE., about 15 ft. high, thence over Fremont River bottom, through willows.
38.20	Right bank of river, bears NW. and curves SE., thence over river channel.
40.35	Point for the cor. of secs. 16, 17, 20 and 21, at proportionate distance; there is no remains of original corner, falls in Fremont River and cannot be monumented.

D: ·endent Resurvey, T. 28 S., R. 10 E.

CHAINS	
	Land, nearly level. Soil, clay with sand in river bottom. Timber, few cottonwood along river. Undergrowth, scattered shadscale with willows along river.
	From the cor. of secs. 15, 16, 21 and 22.
	N. 89° 38' W., bet. secs. 16 and 21.
	Over nearly level bottom land, through heavy brush.
3.60	Small clay knoll, about 12 ft. high, 1 ch. diam.
5.80	Wash, 3 ft. deep, 20 lks. wide, drains SE.
39.80	The ¼ sec. cor. of secs. 16 and 21, marked by a sandstone 5x12x14 ins., no visible marks, stake beside stone.
	Note: Original record erroneously describes this as a wooden post corner.
	At the corner point
	Set an iron post 36 ins. long, 1 in. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.
	T28S R10E ¼ S16/S21 1964
	S. 89° 35' W., beginning new measurement.
	Continue over level bottom land.
34.30	Left bank Fremont River, curves NW. and SE., thence over river.
40.56	True point for the cor. of secs. 16, 17, 20 and 21.
	Land, level. Soil, sandy clay. Timber, few cottonwood along river. Undergrowth, dense sagebrush and greasewood.
	From the true point for the cor. of secs. 16, 17, 20 and 21, which falls in Fremont River.
	N. 0° 07' E., bet. secs. 16 and 17.
	Over Fremont River.
2.60	Left bank Fremont River, curves NW. and SE., asc. 10 ft. over broken clay banks facing S.
6.00	Point selected for the witness cor. of secs. 16, 17, 20 and 21.

Dependent Resurvey, T. 28 S., R. 10 E.

CHAINS	
	Set an iron post 30 ins, long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R10E S17 | S16 S20 | S21 W C 1964
	Asc. gentle S. slope, in Blue Valley.
11.50	Highway, hard surface, U-24, bears N. 89° 30' E. and S. 89° 30' W.
15.30	Power line, bears E. and W.
40.35	Point for the ¼ sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of original corner. Set an iron post 36ins. long, 1 in. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R10E ¼ S17 | S16 1964 From this corner U.S.C. & G.S. station "8M"Z11", located in latitude 38° 22' 24.65" N., and Longitude 110° 50' 31.90" W., bears S. 22° 38' W., 7.19 chs. dist. Asc. gentle S. slope in Blue Valley
61.40	Base of small butte, bears NE. and SW., asc. 50 ft. over SE. slope.
64.10	Top same butte, bears NE. and SW., desc. 30 ft. over NW. slope of butte.
66.00	Base of butte, bears NE. and SW., asc. 35 ft. along E. slope.
80.70	Point for the cor. of secs. 8, 9, 16 and 17, at proportionate distance; there is no evidence of original corner. Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R10E S 8 | S 9 S17 | S16 1964 Land, level S. portion, broken N. portion. Soil, clay. Timber, none. Undergrowth, scattered shadscale.

Dependent Resurvey, T. 28 S., R. 10 E.

CHAINS	
	From the cor. of secs. 9, 10, 15 and 16.
	N. 89° 40' W., bet. secs. 9 and 16.
	Over rolling clay desert land, in Blue Valley, draining S.
40.27	Point for the ¼ sec. cor. of secs. 9 and 16, at proportionate distance; there is no evidence of original corner.
	Set an iron post 36 ins. long, 1 in. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.
	T28S R10E ¼ S 9 / S16 1964
	Continue over gentle SE. slope in Blue Valley.
14.70	Base of low shale dike, bears NE. and SW., asc. 85 ft. over E. slope of dike.
57.20	Crest of same dike, bears NE. and SW., desc. 75 ft. over W. slope.
59.70	Base same dike, bears NE. and SW., also small wash, drains S., asc. 25 ft. over gentle E. slope.
78.00	Base of steep bluff, bears N. and S. irregularly, asc. 60 ft. over steep E. slope.
80.54	The cor. of secs. 8, 9, 16 and 17.
	Land, mostly rolling. Soil, clay. Timber, none. Undergrowth, very scattered shadscale.
	N. 0° 06' E., bet. secs. 8 and 9.
	Over blue clay hills, on W. side of Blue Valley, asc. 25 ft. over S. slope.
2.30	Low spur, slopes E., desc. 35 ft. over N. slope.
7.50	Bottom small hollow, drains E., asc. 95 ft. over S. slope.
13.40	Spur, slopes E., desc. 65 ft. over N. slope.
15.50	Base of spur, bears W. and curves SE., thence over small cove.
24.50	Base of steep ascent, bears E. and W. irregularly, asc. 220 ft. over ledgy S. slope. By triangulation.
32.80	Crest of ledges, bears E. and W. irregularly, thence over broken sandstone point, extending SE. from Factory Bench. End triangulation.

Dependent Resurvey, T. 28 S., R. 10 E.

CHAINS

40.35 Point for the ¼ sec. cor. of secs. 8 and 9, at proportionate distance; there is no evidence of original corner.

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R10E
¼
S 8 | S 9
1964

Asc. 30 ft. over broken sandstone point.

48.10 Crest of ledges, bears NW. and SE., thence along impassable ledges facing generally E. By triangulation.

72.60 Crest same rim, bears NE. and curves SW., asc. 10 ft. over broken land, on Factory Bench. End triangulation.

80.70 Point for the cor. of secs. 4, 5, 8 and 9, at proportionate distance; there is no remaining evidence of original corner.

Set an iron post 30 ins. long, 2½ ins. diam., 16 ins. in the ground, in a mound of stone 3 ft. base, to top, with brass cap mkd.

T28S R10E
S 5 | S 4
S 8 | S 9
1964

Land, broken.
Soil, sand, clay and exposed sandstone.
Timber, none.
Undergrowth, very scattered shadscale.

From the cor. of secs. 3, 4, 9 and 10.

N. 89° 17' W., bet. secs. 4 and 9.

Over rolling clay land, in Blue Valley, asc. 40 ft. over gentle E. slope.

13.50 Base of steep ascent, bears NW. and S., asc. 240 ft. over ledgy E. slope. By triangulation, topography scaled.

19.00 Top of ascent on point, which projects S., thence over impassable series of shale spurs and gulleys, draining S.

40.54 Point for the ¼ sec. cor. of secs. 4 and 9, falls in inaccessible ledges and was not monumented.

62.80 E. crest of Factory Bench, bears N. and SW., thence over bench, across sandstone and gravel spots. End triangulation.

62.90 Point selected for the witness point bet. secs. 4 and 9.

Dependent Resurvey, T. 28 S., R. 10 E.

CHAINS	
	Set an iron post 36 ins. long, 1 in. diam., on solid sandstone, over an X, in a mound of stone, 4 ft. base, to top, with brass cap mkd. T28S R10E S 4 W S 9 P 1964 Note: From this witness point, a sandstone 6x12x24 ins. mkd. WC, and the mks. W¼ on solid sandstone beside this stone, bear north 18 lks. dist. This position was not recorded in the original survey and was not accepted as official. Continue over gentle SW. slope, on Factory Bench.
81.08	The cor. of secs. 4, 5, 8 and 9. Land, broken. Soil, sand, clay and exposed sandstone. Timber, none. Undergrowth, very scattered shadscale.
	N. 0° 10' W., bet. secs. 4 and 5. Over sandy land with patches of exposed sandstone, on top of Factory Bench.
40.35	The ¼ sec. cor. of secs. 4 and 5, marked by a sandstone 4x8x16 ins., plainly mkd. ¼. Note: Original record describes this as a slate stone. At the corner point Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R10E ¼ S 5 | S 4 1964 Place original stone alongside and W. of iron post.
	N. 0° 16' E., beginning new measurement. Asc. 10 ft. over gentle SW. slope, on Factory Bench.
1.80	Small wash, drains SW.
25.60	Small wash, drains SW.
39.69	The cor. of secs. 4 and 5, on the N. bdy. of the Tp., marked by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the official record of the resurvey of the S. bdy. of T. 27 S., R. 10 E., in 1954.

CHAINS

Land, rolling.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, shadscale and bunch grass.

From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp.

N. 2° 57' E., bet. secs. 31 and 32.

Over broken desert land on high bench, across sand and exposed sandstone.

22.00 Crest of high rim, bears NW. and SE. irregularly, desc. 300 ft. over NE. slope and ledges facing NE. By triangulation.

40.00 Base of steep descent, bears NW. and SE. irregularly, thence over level land of Blue Valley. Eng triangulation.

41.41 The ¼ sec. cor. of secs. 31 and 32, marked by a sandstone 3x14x14 ins., plainly mkd. ¼.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R10E
¼
S31 | S32

1964

Place original stone alongside and W. of iron post.

North, beginning new measurement.

Continue over level land in Blue Valley.

36.90 Town Wash, 10' deep, 60 lks. wide, drains NE.

39.70 The cor. of secs. 29, 30, 31 and 32, marked by a sandstone 6x18x24 ins., mkd. 1 notch on S. and 5 notches on E. faces.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R10E

S30 | S29
S31 | S32

1964

Place original stone alongside and W. of iron post.

Dependent Resurvey, T. 28 S., R. 10 E.

CHAINS	
	Land, broken S. portion, level N. portion. Soil, sand, clay and exposed sandstone. Timber, none. Undergrowth, very scattered shadscale and bunch grass.
	From the cor. of secs. 28, 29, 32 and 33.
	N. 89° 43' W., bet. secs. 29 and 32.
	Over broken desert land, on N. end of high point.
.30	Crest of ledges, bears SW. and curves SE., desc. 320 ft. over ledgy NW. slope. By triangulation, topography scaled.
7.00	Base of ledges, bears NE. and SW., desc. 50 ft. over steep NW. slope over clay and shale.
20.00	Small hollow, drains N., asc. 40 ft. over NE. slope.
29.00	Top of spur, which slopes W. from SE., desc. 30 ft. along top of spur. End triangulation.
36.44	The ¼ sec. cor. of secs. 29 and 32, marked by a sandstone 3x10x20 ins., plainly mkd. ¼.
	At the corner point
	Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R10E ¼ S29/S32 1964
	Place original stone alongside and N. of iron post.
	N. 89° 43' W., beginning new measurement.
	Asc. 25 ft. along top of spur.
6.50	Small rise on top of spur, desc. 60 ft. over W. slope, on end of spur.
10.70	Small draw, drains NW., thence over level desert land.
15.20	Small clay knoll, continue over desert land, in Blue Valley.
34.00	Town Wash, 10 ft. deep, 1 Ch. wide, drains NE.
39.90	The cor. of secs. 29, 30, 31 and 32.
	Land, broken E. portion, rolling W. portion. Soil, sandy clay and exposed sandstone. Timber, none. Undergrowth, very scattered shadscale.

Dependent Resurvey, T. 28 S., R. 10 E.

CHAINS

S. 89° 20' W., bet. secs. 30 and 31.

Over rolling desert land, in Blue Valley, asc. gentle E. slope.

4.50 Base of steep ascent, bears N. and S., asc. 300 ft. over steep E. slope and ledges facing E.

9.50 Crest of steep ascent, bears N. and S., thence over broken bench, over sand and exposed sandstone.

39.66 The ¼ sec. cor. of secs. 30 and 31, marked by a sandstone 6x16x24 ins., plainly mkd. ¼.

At the corner point

Set an iron post 36 ins. long, 1 in. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R10E

¼ S30/S31

1964

Place original stone alongside and N. of iron post.

N. 89° 44' W., beginning new measurement.

Desc. 45 ft. over broken bench, over sand and barren sandstone.

42.25 The cor. of secs. 25, 30, 31 and 36, on W. bdy. of the township, marked by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of the E. bdy. of T. 28 S., R. 9 E.

Land, broken.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, shadscale and bunch grass.

From the cor. of secs. 29, 30, 31 and 32.

N. 0° 03' W., bet. secs. 29 and 30.

Over rolling land of Blue Valley, asc. along gentle E. slope.

20.50 Base of steep ascent, bears S. and NE., asc. 240 ft. over inaccessible ledges facing SE. By traverse, topography scaled.

27.00 Spur, slopes E., desc. 240 ft. over N. slope.

33.00 Gully, drains E., asc. 200 ft. along ledgy E. slope.

37.99 Point selected for the witness ¼ sec. cor. of secs. 29 and 30.

Dependent Resurvey, T. 28 S., R. 10 E.

CHAINS	
	Set an iron post 36 ins. long, 1 in. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R10E ¼ W C S30 S29 1964
	Asc. 100 ft. over ledges facing SE.
39.99	Point for the ¼ sec. cor. of secs. 29 and 30, at proportionate distance; there is no remaining evidence of original corner. This position falls on inaccessible ledges facing SE. and is not monumented.
	Asc. 50 ft. over ledgy SE. slope.
55.00	Crest of ledgy ascent, bears S. and NE., thence over broken bench, on Steamboat Point.
69.00	N. crest of Steamboat Point, bears E. and SW., descend 340 ft. over ledges facing N. and broken N. slope.
79.00	Base of steep desc., bears E. and SW., desc. gentle N. slope in Blue Valley. End traverse.
79.98	Point for the cor. of secs. 19, 20, 29 and 30, at proportionate distance; there is no remaining evidence of original corner.
	Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R10E S19 S20 S30 S29 1964
	Land, broken. Soil, sand and exposed sandstone. Timber, none. Undergrowth, shadscale and scattered bunch grass.
	From the cor. of secs. 20, 21, 28 and 29.
	N. 88° 59' W., bet. secs. 20 and 29.
	Over level desert clay land, in Blue Valley, along gentle N. slope.
2.00	Town Wash, 4 ft. deep, 30 lks. wide, drains NE.
40.18	Point for the ¼ sec. cor. of secs. 20 and 29, at proportionate distance; there is no remaining evidence of original corner.
	Set an iron post 36 ins. long, 1 in. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R10E ¼ S20/S29 1964

Dependent Resurvey, T. 28 S., R. 10 E.

CHAINS

Continue over gentle N. slope in Blue Valley.

52.00 Base of steep ascent, bears S. and N. about 10 chs., asc. 200 ft. over ledgy E. slope of Steamboat Point. By traverse.

56.50 N. end of Steamboat Point, slopes NE., about 10 chs. to end, desc. 200 ft. over W. slope.

60.00 Base of steep descent, bears W. and NE., thence along broken N. slope, in Blue Valley.

80.36 The cor. of secs. 19, 20, 29 and 30.

Land, rolling E. portion, broken W. portion.
Soil, clay.
Timber, none.
Undergrowth, very scattered shadscale and greasewood.

S. 89° 02' W., bet. secs. 19 and 30.

Over rolling desert land in S. end of Blue Valley, along gentle N. slope.

40.07 The ¼ sec. cor. of secs. 19 and 30, marked by a sandston 6x16x30 ins., plainly mkd. ¼.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R10E
¼ S19/S30
1964

Place original stone alongside and N. of iron post.

N. 89° 40' W., beginning new measurement.

Continue over gentle N. slope, in Blue Valley.

33.40 Base of steep ascent, bears N. and S., asc. 250 ft. over ledgy E. slope, by triangulation.

38.40 Crest of steep ascent, on rim, bears N. and S., thence over broken point. End triangulation.

40.40 The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., marked by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of the E. bdy. of T.28 S., R. 9 E.

Land, level E. portion, broken W. portion.
Soil, sandy clay.
Timber, none.
Undergrowth, very scattered shadscale.

Dependent Resurvey, T. 28 S., R. 10 E.

CHAINS	
	From the cor. of secs. 19, 20, 29 and 30.
	N. 1° 15' W., bet. secs. 19 and 20.
	Over level bottom land of Blue Valley, desc. gentle N. slope.
19.90	Right bank of Fremont River, bears NW. and SE., thence over river, which flows eastward.
27.60	Left bank of river, bears NW. and SE., asc. gentle S. slope, through heavy brush.
40.00	Point for the ¼ sec. cor. of secs. 19 and 20, at proportionate distance; there is no remaining evidence of original corner.
	Set an iron post 36 ins. long, 1 in. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.
	T28S R10E ¼ S19 | S20 1964
	Asc. 15 ft. over gentle S. slope, in Blue Valley.
59.00	Highway, U-24, bears N. 60° 30' E. and S. 60° 30' W.
60.98	Power line, parallel highway.
80.00	Point for the cor. of secs. 17, 18, 19 and 20, at proportionate distance; there is no remaining evidence of original corner.
	Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T28S R10E S18 | S17 S19 | S20 1964
	Land, rolling. Soil, sandy clay. Timber, none. Undergrowth, sagebrush and greasewood in river bottom.
	From the true point for the cor. of secs. 16, 17, 20 and 21, (from which its witness cor. bears N. 0° 07' E., 6.00 chs. dist.)
	N. 89° 11' W., bet. secs. 17 and 20.
	Over Fremont River channel.
17.00	Leave river channel at its left bank, which bears SW. and NE.; thence over river bottom land, through willows.
40.80	Point for the ¼ sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of original corner.

Dependent Resurvey, T. 28 S., R. 10 E.

CHAINS	
	Set an iron post 36 ins. long, 1 in. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R10E ¼ S17/S20 1964
	Set steel fence post beside iron post.
49.00	Highway, U-24, bears N. 53° E. and S. 53° W.
52.20	Power line, parallel highway.
62.00	Base of steep ascent, bears N. and S. about 4 chs. to end, asc. 110 ft. over E. slope of point.
69.00	Spur, slopes S., desc. 115 ft. over steep W. slope.
72.10	Base of spur, bears N. and curves SE., thence over small cove.
81.60	The cor. of secs. 17, 18, 19 and 20.
	Land, rolling. Soil, sandy clay. Timber, none. Undergrowth, willows along river bottom.
	S. 89° 52' W., bet. secs. 18 and 19.
	Over rolling desert land, asc. gentle E. slope in cove.
11.00	Base of steep ascent, bears N. and S. irregularly, asc. 200 ft. over ledgy E. slope of bluff.
18.50	Crest of bluff, bears N. and S. irregularly, thence over broken land, on top of small bench.
38.50	E. crest of small canyon, bears N. and S., desc. 200 ft. over ledgy W. slope.
40.70	Point for the ¼ sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of original corner.
	Set an iron post 36 ins. long, 1 in. diam., 6 ins. in the ground, in a mound of stone 4 ft. base, to top, with brass cap mkd. T28S R10E ¼ S18/S19 1964
45.00	Wash in small canyon, drains S., asc. 240 ft. over ledgy E. slope.
51.00	W. crest small canyon, bears N. and S., asc. 40 ft. over broken E. slope, on top of point.

Dependent Resurve , T. 28 S., R. 10 E.

CHAINS	
56.90	Top of ascent on point, desc. 35 ft. over W. slope, on point.
69.60	E. crest small canyon, bears N. and S., desc. 175 ft. over ledgy W. slope.
77.00	Base of steep descent, bears N. and S. irregularly, thenc over small canyon bottom.
78.20	Wash, 5 ft. deep, 50 lks. wide, drains S., asc. gentle E. slope.
80.28	The cor. of secs. 13, 18, 19 and 24, on W. bdy. of the township, marked by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of the E. bdy. of T. 28 S., R. 9 E. Land, broken. Soil, sand and exposed sandstone. Timber, none. Undergrowth, shadscale and scattered bunch grass.
	From the cor. of secs. 17, 18, 19 and 20. N. 0° 46' E., bet. secs. 17 and 18. Over rolling desert land, asc. 30 ft. over gentle S. slope, in cove.
39.99	Point for the ¼ sec. cor. of secs. 17 and 18, at proportionate distance; there is no evidence of original corner. Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R10E ¼ S18 | S17 1964 Asc. gentle S. slope.
44.10	Base of steep ascent, in N. end of cove, bears S. and curves NE., asc. 200 ft. over ledgy SE. slope.
47.60	Crest of ledgy ascent; bears NE. and SW., thence over broken top of Factory Bench.
79.98	The cor. of secs. 7, 8, 17 and 18, marked by a sandstone 3x14x20 ins., plainly mkd. 4 notches on S. and 5 notches on E. face. At the corner point Set an iron post 30 ins. long, 2½ ins. diam., 24 ins, in the ground, in a collar of stone, with brass cap mkd. T28S R10E S 7 | S 8 S18 | S17 1964

CHAINS	
	Place original stone alongside and N. of iron post. Land, rolling S. portion, broken N. portion. Soil, sandy clay and exposed sandstone. Timber, none. Undergrowth, shadscale and scattered bunch grass.
	From the cor. of secs. 8, 9, 16 and 17. N. 89° 42' W., bet. secs. 8 and 17. Over broken desert land, asc. 240 ft. over ledgy E. slope. By triangulation, topography scaled.
9.00	Point, projects S., desc. 240 ft.over NW. slope.
16.50	Base of steep descent, bears NE. and SW., thence over small cove, draining S.
31.00	Base of steep ascent, bears N. and S. irregularly, asc. 240 ft. over ledgy E. slope.
38.30	E. crest of Factory Bench, bears N. and S. irregularly, thence over broken bench, over sand and exposed sandstone.
40.37	Point for the ¼ sec. cor. of secs. 8 and 17, at proportionate distance; there is no evidence of original corner. Set an iron post 36 ins. long, 1 in. diam., on solid sandstone, over an X, in a mound of stone 4 ft. base, to top, with brass cap mkd. T28S R10E ¼ S 8 / S17 1964 Desc. 20 ft. over sand and exposed sandstone, on Factory Bench.
80.74	The cor. of secs. 7, 8, 17 and 18. Land, broken. Soil, sand and exposed sandstone. Timber, none. Undergrowth, shadscale and scattered bunch grass.
	N. 89° 56' W., bet. secs. 7 and 18. Over broken desert land on Factory Bench, across sand and exposed sandstone formation.
34.40	Top of small sandstone rise, desc. 20 ft. over gentle SW. slope.
40.16	The ¼ sec. cor. of secs. 7 and 18, marked by a sandstone 6x8x25 ins., plainly mkd. ¼.

Dependent Resurvey, T. 28 S., R. 10 E.

At the corner point

Set an iron post 36 ins. long, 1 in. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R10E
¼ S 7 / S18
1964

Place original stone alongside and N. of iron post.

N. 89° 03' W., beginning new measurement.

Desc. 30 ft. over broken bench land, draining SW.

36.71 E. side of small hollow, bears N. and S., desc. 40 ft. over ledgy w. slope.

40.24 The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., marked by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of the E. bdy. of T. 28 S., R. 9 E.

Land, broken.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, shadscale and scattered bunch grass.

From the cor. of secs. 7, 8, 17 and 18.

N. 0° 16' E., bet. secs. 7 and 8.

Over or across land draining SW., on Factory Bench, across sand and exposed sandstone.

4[illegible].27 The ¼ sec. cor. of secs. 7 and 8, marked by a sandstone 4x10x24 ins., plainly mkd. ¼.

At the corner point

Set an iron post 36 ins. long, 1 in. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R10E
¼
S 7/S 8
1964

Place original stone alongside and W. of iron post.

N. [illegible]° 46' W., beginning new measurement.

As. [illegible] ft. over bench land draining SW.

4[illegible] Crest sandstone knoll, about 8 chs. diam., desc. 30 ft. along w. slope.

[illegible] S. [illegible] 10 [illegible]

CHAINS

16.50 Small wash, drains SW., asc. 35 ft. over SW. slope.

40.29 The cor. of secs. 5, 6, 7 and 8, marked by a sandstone 10x14x20 ins., plainly mkd. 5 notches on S. and E. faces.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R10E

S 6	S 5
S 7	S 8

1964

Place original stone alongside and W. of iron post.

Land, broken.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, shadscale and bunch grass.

From the cor. of secs. 4, 5, 8 and 9.

West, bet. secs. 5 and 8.

Over broken desert land on Factory Bench, along gentle S. slope.

.60 Small wash, drains S.

8.40 Slope changes, desc. 65 ft. over gentle SW. slope.

40.39 The ¼ sec. cor. of secs. 5 and 8, marked by a sandstone 2x8x14 ins., dimly mkd. ¼.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., on solid sandstone, over an X, in a mound of stone 4 ft. base, to top, with brass cap mkd.

T28S R10E

¼ S 5 / S 8

1964

Place original stone alongside and N. of iron post.

N. 89° 42' W., beginning new measurement.

Desc. 35 ft. over irregular sandstone formation, draining W.

31.50 Small wash, drains S., asc. 25 ft. along S. slope.

Dependent Resurvey, T. 28 S., R. 10 E.

CHAINS

36.50 Sandstone knob, about 15 ft. high, 20 ft. diam., desc. 25 ft. over SW. slope.

40.82 The cor. of secs. 5, 6, 7 and 8.

Land, broken.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, shadscale and bunch grass.

N. 89° 43' W., bet. secs. 6 and 7.

Over broken desert bench land, desc. 60 ft. over W. slope, across sand and exposed sandstone.

40.43 The ¼ sec. cor. of secs. 6 and 7, marked by a sandstone 5x12x20 ins., plainly mkd. ¼.

At the corner point

Set an iron post 36 ins. long, 1 in. diam., on solid sandstone, over an X, in a mound of stone 4 ft. base, to top, with brass cap mkd.

T28S R10E
¼ S 6 / S 7
1964

Place original stone alongside and N. of iron post.

N. 89° 40' W., beginning new measurement.

Desc. 75 ft. over W. slope, over sand and exposed sandstone.

39.54 The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., marked by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of the E. bdy. of T. 28 S., R. 9 E.

Land, broken.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, shadscale and bunch grass.

From the cor. of secs. 5, 6, 7 and 8.

N. 0° 20' E., bet. secs. 5 and 6.

Over broken desert land on Factory Bench, asc. 10 ft. along gentle W. slope.

30.70 Wash, 3 ft. deep, 20 lks. wide, drains W.

40.32 The ¼ sec. cor. of secs. 5 and 6, marked by a sandstone 6x14x20 ins., plainly mkd. ¼.

Dependent Resurvey, T. 28 S., R. 10 E.

CHAINS

At the corner point

Set an iron post 36 ins. long, 1 in. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R10E
¼
S 6|S 5
1964

Place original stone alongside and W. of iron post.

N. 0° 28' W., beginning new measurement.

Continue over gentle W. slope.

39.87 The cor. of secs. 5 and 6, on the N. bdy. of the Tp., marked by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record of the resurvey of the S. bdy. of T. 27 S., R. 10 E., in 1954.

Land, broken.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, shadscale and bunch grass.

General Description

The east boundary of T. 28 S., R. 10 E., is located about 4 miles west of Hanksville, Utah. With the exception of Blue Valley and the bottom land along the Fremont River, the township is broken desert land, with numerous washes and exposed sandstone rims.

The township is divided by the Fremont River, which enters the township on the W. bdy. of sec. 19, flows eastward and leaves the township on the E. bdy. of sec. 13. The north portion of the township drains south to this river, the south portion of the township drains north to the river. The main road is hard surface highway, U-24, which follows the river canyon along the north side of the river across the township.

The soil is sand and exposed sandstone on the higher elevations, clay on the lower elevations. The elevation varies from about 4350 to 5100 ft. above sea level. Vegetation consists mainly of shadscale and scattered bunch grass on higher elevations, willows and a few cottonwood trees in river bottom.

There is no habitation within the township.

CHAINS

Form 4-680
(June 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
LaVern Griffin	Transitman
Ferrel Reynolds	Notekeeper
Merlin Robinson	Chainman
Morris E. Blackburn	Cornerman
Jerry Thomas	Flagman

CERTIFICATE OF SURVEY

I, Craig P. Sylvester, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 21st day of August, 1963, I have dependently resurveyed the East Boundary and the South Boundary and subdivision of Township 28 South, Range 10 East

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

March 22, 1965
(Date)

Craig P. Sylvester
~~(Cadastral Surveyor)~~
(Supervisory Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date FEB 17 1966

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the dependent resurvey of the East Boundary and the South Boundary and subdivision of Township 28 South, Range 10 East, Salt Lake Meridian, State of Utah,

executed by Craig P. Sylvester, Supervisory Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

APR 14 1966
(Date)

E. E. Lemmon
(Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in , is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)

Blank

Page

Blank

Page

ORIGINAL

Original

Form 4–679
(January 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

145

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF THE EAST BOUNDARY

AND SUBDIVISION

OF

TOWNSHIP 29 SOUTH, RANGE 10 EAST

Of the SALT LAKE Meridian,

In the State of UTAH.

EXECUTED BY

CRAIG P. SYLVESTER SUPERVISORY CADASTRAL SURVEYOR

Under special instructions dated AUGUST 21, 19 63, which provided for the surveys included under Group Number 466, approved AUGUST 22, 1963, and assignment instructions dated SEPTEMBER 24, 19 63.

Survey commenced NOVEMBER 11, 19 63

146

DEPT. OF THE INTERIOR
BUR OF LAND MGMT

1966 MAY 12 AM 10 24 .7

RECEIVED
STATE & LAND OFFICE
SALT LAKE CITY, UTAH

INDEX DIAGRAM

Township 29 SOUTH, Range 10 EAST,

6 51	52 5 50	40 4 39	32 3 31	24 2 23	15 1 15	6
7 48	49 8 48	38 9 38	30 10 30	22 11 21	14 12 13	5
18 46	47 17 45	37 16 36	29 15 28	21 14 20	12 13 12	4
19 44	45 20 43	35 21 35	27 22 27	19 23 18	11 24 10	3
30 42	42 29 41	34 28 33	26 27 25	17 26 17	9 25 8	3
31	40 32	33 33	24 34	16 35	7 36	2

Dependent Resurvey, East Boundary and Subdivision
Township 29 South, Range 10 East

CHAINS

The north boundary was surveyed by A. D. Ferron in 1882, and concurrently resurveyed, and the record appears in the field notes of T. 28 S., R. 10 E. The west boundary was surveyed by A. D. Ferron in 1882, and concurrently resurveyed, and the record appears in the field notes of T. 29 S., R. 9 E. The south boundary was surveyed by A. D. Ferron in 1882, and resurveyed by Elliot Bird in 1919, and the record appears in the resurvey of the north boundary of T. 30 S., R. 10 E. The east boundary was surveyed by A. D. Ferron in 1882. The subdivisional lines were surveyed by A. D. Ferron in 1883.

The following field notes are those of a dependent resurvey of the east boundary and subdivisional lines of T. 29 S., R. 10 E.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions, 1947, and the Special Instructions dated August 21, 1963.

Corners on the east-west lines were set on the true latitudinal curve. Lines connecting previously established corners were run by random and true method, but for simplification of the record, the random lines are omitted from these field notes.

All lines of this survey were run by direct method where lines were accessible; lines inaccessible were run by traverse or triangulation method. Distances to topography on lines run by traverse and triangulation methods are approximately as scaled from U. S. G. S. topographic sheets. The details of such traverses and triangulations have been thoroughly checked and verified and in order to simplify the records, the diagrams and reductions are omitted from these field notes.

The direction of the lines of this survey were determined by reference to true meridians established on line by hour angle observations on Polaris. They were carried forward by sustained angulation, being supplemented by numerous other observations on Polaris taken throughout the progress of the survey.

Before restoring lost corners, the lines of the original survey were retraced and a diligent search made for any evidence of the original corners. The rules of proportionate measurement were applied to ascertain the position of the lost corner after every reasonable possibility of finding direct evidence of the corner had been exhausted.

The geographic position for the southeast corner of the township is in latitude 38°14'11.0" N. and longitude 110°46'02.6" W. as determined by traverse from United States Geological Survey triangulation station "Cattle" located in sec. 32, T. 29 S., R. 11 E., in latitude 38°14'24,169" N., and longitude 110°44'23.304" W.

The magnetic declination was read at a number of stations throughout the township and the average of the several readings was found to be 15°30' E.

Dependent Resurvey, East Boundary, T. 29 S., R. 10 E.

Dependent Resurvey, East Boundary, T. 29 S., R. 10 E.

CHAINS

Reestablishment of the Survey Executed by
A. D. Ferron, Deputy Surveyor, in 1882

Beginning at the cor. of Tps. 29 and 30 S., Rs. 10 and 11 E., marked by an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record of the resurvey of the E. bdy. of T. 30 S., R. 10 E., in 1919.

N. 0°31' W., bet. secs. 31 and 36.

Over broken desert land, asc. 40 ft. over S. slope.

1.30 Crest small hill, bears NE. and SW., desc. 130 ft. over NW. slope.

23.00 Wash, 2 ft. deep, 20 lks. wide, drains NE., asc. 90 ft. over SE. slope.

38.50 Ridge, bears NW. and SE., desc. 45 ft. over NE. slope.

40.11 The ¼ sec. cor. of secs. 31 and 36, marked by a sandstone 6x12x20 ins., firmly set and plainly mkd. ¼ on W. face. Note: original record describes this as a granite.

At the cor. point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T29S
R10E R11E
¼
S36|S31
1963

Place original stone alongside and N. of the iron post.

Raise mound of stone 3 ft. base, 2½ ft. high, W. of cor.

N. 0°17' W., beginning new measurement.

Desc. 65 ft. over NE. slope.

8.50 Base of hill, bears NW. and SE., thence over series of small knolls.

11.80 Asc. 55 ft. over broken desert land, draining E.

36.90 Top small hill.

40.40 The cor. of secs. 25, 30, 31 and 36, marked by a sandstone 4x6x10 ins., plainly mkd. 1 notch on S. and 5 notches on N. face. Note: original record describes this as a granite.

At the corner point.

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S
R10E R11E
S25|S30
S36|S31
1963

Place original stone alongside and N. of the iron post.

CHAINS

Land, broken.
Soil, sandy clay with exposed sandstone.
Timber, none.

N. 0° 17' W., bet. secs. 25 and 30.

Over broken desert land, desc. 35 ft. over NE. slope.

19.20 Wash, 3 ft. deep, 20 lks. wide, drains NE.

31.40 Wash, 4 ft. deep, 30 lks. wide, drains NE.

38.20 Graded dirt road, bears N. 5° W. and curves SE.

40.29 Point for the ¼ sec. cor. of secs. 25 and 30, at proportionate distance; there is no remaining evidence of the original corner, falls in road and cannot be monumented.

At the corner point

Set a 1 in. T-iron stake, 24 ins. long, 12 ins. under the surface of road.

from which

An iron post, 30 ins. long, 2½ ins. diam., set 24 ins. in the ground, in a collar of stone, for a reference monument, bears N. 45° E., 75.8 lks. dist., with brass cap mkd. T 29S R11E ¼ S30 50 ft. RM 1964 and an arrow pointing to the true corner.

An iron post, 30 ins. long, 2½ ins. diam., set 24 ins. in the ground, in a collar of stone, for a reference monument, bears N. 45° W., 75.8 lks. dist., with brass cap mkd. T29S R10E ¼ S25 50 ft. RM 1964 and an arrow pointing to the true corner.

Desc. 65 ft. over broken desert land, draining NE.

44.40 Wash, 4 ft. deep, 20 lks. wide, drains NE.

80.58 Point for the cor. of secs. 19, 24, 25 and 30, at proportionate distance; there is no remaining evidence of original corner.

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T29S
R10E R11E

S24	S19
S25	S30

1963

Raise a mound of stone 3 ft. base, 2½ ft. high W. of corner.

Land, broken.
Soil, sandy clay and exposed sandstone.
Timber, none.
Undergrowth, shadscale and scattered bunch grass.

N. 0°17' W., bet. secs. 19 and 24.

Over broken desert land, desc. 50 ft. over irregular NE. slope.

De endent Resurve East Boundar T. 29 S. R. 10 E.

CHAINS

9.00 Wash, 3 ft. deep, 20 lks. wide, drains NE.

17.10 Low rise, slopes E.

40.29 The ¼ sec. cor. of secs. 19 and 24, marked by a sandstone 6x10x10 ins., firmly set and plainly mkd. ¼ on W. face.
Note: original record describes this as a granite.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S
R10E R11E
¼
S24|S19
1963

Place original stone alongside and N. of the iron post.

Corner falls on W. side of small wash.

N. 0°02' E., beginning new measurement.

Desc. 55 ft. over broken land, draining NE.

40.08 The cor. of secs. 13, 18, 19 and 24, marked by a sandstone 8x8x20 ins., firmly set and plainly mkd. 3 notches on N. and S. faces.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 10 ins. in the ground, in a mound of stone 4 ft. base, to top, with brass cap mkd.

T29S
R10E R11E
S13|S18
S24|S19
1963

Place original stone alongside and N. of the iron post.

Land, broken.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, shadscale and bunch grass.

N. 0°11' W., bet. secs. 13 and 18.

Over broken and irregular desert land, draining NE., desc. 50 ft.

40.19 The ¼ sec. cor. of secs. 13 and 18, marked by a black limestone 6x6x25 ins. firmly set and plainly mkd. ¼ on W. face.
Note: original record describes this as a sandstone.

At the corner point

Set an iron post 30 ins. long, 2½ ins.diam., 14 ins. in the ground, in a mound of stone 3 ft. base, to top, with brass cap mkd.

Dependent Resurvey, East Boundary, T. 29 S., R. 10 E.

CHAINS

T29S
R10E R11E
¼
S13 | S18

1963

Place original stone alongside and N. of the iron post.

N. 0°36' W., beginning new measurement.

Over broken desert land.

2.00 Small wash, drains NE., asc. 20 ft. over SE. slope.

15.70 Base of steep ascent, bears irregularly NE. and SW.; asc. 115 ft. over broken SE. slope.

24.40 Spur, slopes NE.; desc. 115 ft. over NW. slope.

31.10 Base same spur, bears NE. and SW., thence over broken desert land.

39.89 The cor. of secs. 7, 12, 13 and 18, marked by a sandstone 6x12x24 ins., firmly set and plainly mkd. 4 notches on S. and 2 notches on N. face.
Note: original record describes this as a conglomerate stone.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S
R10E R11E

S12	S7
S13	S18

1963

Place original stone alongside and N. of the iron post.

Land, broken.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, shadscale and scattered bunch grass.

N. 0°03' E., bet. secs. 7 and 12.

Over broken desert land, draining W., asc. 70 ft.

10.00 Small rise, desc. 80 ft. over broken NW. slope.

33.00 Small wash, drains NW., asc. 25 ft. over broken W. slope.

40.40 The ¼ sec. cor. of secs. 7 and 12, marked by a conglomerate stone 6x6x20 ins., firmly set, but dimly mkd. ¼ on W. face.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

De endent Resurve , East Boundar , T. 29 S. R. 10 E.

CHAINS

T29S
R10E R11E
¼
S12|S7
1963

Bury original stone alongside and N. of the iron post.

N. 0°15' W., beginning new measurement.

Continue over broken land, draining W.

21.90 Low rise, bears E. and W., desc. 20 ft. over NW. slope..

40.09 The cor. of secs. 1, 6, 7 and 12, marked by a sandstone 4x4x20 ins., firmly set and mkd. 5 notches on S. and 1 notch on N. face.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S
R10E R11E
S1 |S6
S12|S7
1963

Place original stone alongside and N. of the iron post.

Land, broken.
Soil, sand and exposed sandstone.
Timber, none.

N. 0°21' W., bet. secs. 1 and 6.

Over broken desert land, draining NW.

24.00 Slope changes, desc. 60 ft. over N. slope.

40.14 The ¼ sec. cor. of secs. 1 and 6, marked by a sandstone 5x5x12 ins., firmly set and plainly mkd. ¼.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S
R10E R11E
¼
S1|S6
1963

Place original stone alongside and N. of the iron post.

N. 0°14' W., beginning new measurement.

Desc. 50 ft. over broken N. slope.

20.20 Wash, 2 ft. deep, 10 lks. wide, drains NW., desc. 30 ft. over NW. slope.

Dependent Resurvey, East Boundary, T. 29 S., R. 10 E.

CHAINS

35.30 Sand Wash, 5 ft. deep, 30 lks. wide, drains NE.

40.02 The cor. of Tps. 28 and 29 S., Rs. 10 and 11 E., marked by a sandstone 4x14x23 ins., firmly set and plainly mkd. 6 notches on N., S., E. and W. faces.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T28S
R10E R11E

S36	S31
S1	S6

T29S
1963

Place original stone alongside and N. of the iron post.

Raise a mound of stone 3 ft. base, 2½ ft. high, W. of corner.

Land, broken.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, shadscale and scattered bunch grass.

Dependent Resurvey of the Subdivisional Lines,
T. 29 S., R. 10 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
A. D. Ferron, Deputy Surveyor, in 1883.

Beginning at the cor. of secs. 35 and 36, on the S. bdy. of the Tp., marked by an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record of the resurvey of the S. bdy., in 1919.

N. 7°34' W., bet. secs. 35 and 36.

Over broken desert land, draining NE.

4.60 Wash, 2 ft. deep, 10 lks. wide, drains NE.; desc. 70 ft. over broken land draining N.

39.25 The ¼ sec. cor. of secs. 35 and 36, marked by a granite stone 4x16x20 ins., firmly set and plainly mkd. ¼ on W. face.

At the cor. point

Set an iron post 36 ins. long, 1 in. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R10E
¼
S35 | S36
1964

Bury original stone alongside and N. of the iron post.

Dependent Resurvey, T. 29 S., R. 10 E.

CHAINS

N. 3°38' E., beginning new measurement.

Over broken land, draining N., desc. 20 ft.

12.30 Wash, 2 ft. deep, 10 lks. wide, drains N. 10° E., asc. 30 ft. over S. slope.

27.80 Top of ascent, desc. 60 ft. over N. slope.

40.13 Point for the cor. of secs. 25, 26, 35 and 36, at proportionate distance; there is no remaining evidence of original corner.

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R10E

S26	S25
S35	S36

1964

Land, broken.
Soil, sandy clay.
Timber, none.
Undergrowth, shadscale and bunch grass.

From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp.

S. 89 00' W., bet. secs. 25 and 36.

Over broken land, asc. E. slope.

2.00 Base of steep ascent, bears N. and S., asc. 120 ft. over steep E. slope.

10.70 E. crest small bench, bears N. and S., thence over gravelly top of bench.

20.90 W. crest of bench, bears N. and S., desc. 90 ft. over steep W. slope.

26.90 Wash, 4 ft. deep, 10 lks. wide, drains N., also base of steep W. slope; thence along broken N. slope.

34.10 Wash, 3 ft. deep, 20 lks. wide, drains NE., asc. 30 ft. over E. slope.

38.00 Low spur, slopes N., desc. 30 ft. over W. slope.

39.80 Wash in bottom small draw, drains NE., asc. 20 ft. over E. slope.

41.09 Point for the ¼ sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post 30 ins. long, 2½ ins. diam., 12 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T29S R10E

¼ S25
S36
1964

Asc. 60 ft. over E. slope.

CHAINS	
43.50	E. crest small bench, bears N. and S., thence over top of bench.
56.10	W. crest of bench, bears N. and S., desc. 90 ft. over W. slope.
63.30	Base of steep descent, bears N. and S., thence along broken N. slope.
69.40	Wash, 3 ft. deep, 20 lks. wide, drains N. 20° E.
78.50	Low rise, slopes N., desc. 40 ft. over W. slope.
80.20	Wash, 3 ft. deep, 20 lks. wide, drains N., asc. 10 ft. over E. slope.
82.17	The cor. of secs. 25, 26, 35 and 36.
	Land, broken. Soil, sand and exposed sandstone. Timber, none. Undergrowth, shadscale and bunch grass.
	N. 2°45' W., bet. secs. 25 and 26.
	Over rolling desert land, along gentle W. slope.
13.50	Wash, 3 ft. deep, 20 lks. wide, drains W.
22.30	Slope changes, desc. 25 ft. over gentle NW. slope.
32.80	Small wash, drains NW.
40.10	The ¼ sec. cor. of secs. 25 and 26, marked by a granite stone 6x8x20 ins., firmly set and plainly mkd. ¼ on W. face.
	At the corner point
	Set an iron post 36 ins. long, 1 in. diam., 28 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R10E ¼ S26 | S25 1964
	Bury original stone alongside and W. of the iron post.
	N. 0°20' E., beginning new measurement.
	Desc. 45 ft. over NW. slope.
7.40	Wash, 2 ft. deep, 20 lks. wide, drains NW.; asc. 20 ft. over SW. slope of terrace.
10.90	Crest of ascent on terrace, desc. 40 ft. over NW. slope of terrace.
16.40	Wash, 2 ft. deep, 30 lks. wide, drains NW., desc. 20 ft. over gentle N. slope.
26.30	Bulldozed road, bears E. and W.

Dependent Resurvey, T. 29 S., R. 10 E.

CHAINS

40.13 The cor. of secs. 23, 24, 25 and 26, marked by a granite stone 6x14x16 ins., firmly set and plainly mkd. 1 notch on E. and 2 notches on S. face.
Note: original record describes this as a sandstone.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R10E

S23	S24
S26	S25

1964

Place original stone alongside and N. of the iron post.

Land, rolling.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, shadscale and bunch grass.

From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp.

S. 88°44' W., bet. secs. 24 and 25.

Over broken desert land, asc. 30 ft. over E. slope.

10.50 Base of spur, bears N. and S., asc. 50 ft. over steep E. slope.

13.60 Low spur, slopes N., desc. 20 ft. over W. slope.

14.70 Small ravine, drains NW. asc. 80 ft. over broken E. slope.

19.20 E. crest small bench, bears N. and S., thence over bench.

35.10 W. crest of bench, bears N. and S., desc. 70 ft. over W. slope.

39.90 Wash in bottom of small hollow, drains N., asc. 20 ft. over E. slope.

41.74 Point for the ¼ sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of original corner.

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R10E

¼ S24 / S25

1964

Asc. 50 ft. over E. slope.

48.00 E. crest small bench, bears N. and S., thence over bench.

62.30 W. crest of bench, bears NW. and SE., desc. 115 ft. over broken SW. slope.

72.70 Wash, 4 ft. deep, 20 lks. wide, drains NW.; asc. 35 ft. along rolling N. slope.

83.48 The cor. of secs. 23, 24, 25 and 26.

Dependent Resurvey, T. 29 S. R. 10 E.

CHAINS	
	Land, broken. Soil, sand and exposed sandstone. Timber, none. Undergrowth, shadscale and bunch grass.
	N. 0°36' E., bet. secs. 23 and 24.
	Over rolling desert land, desc. 30 ft. over gentle N. slope.
18.80	Wash, 4 ft. deep, 20 lks. wide, drains NW., asc. 15 ft. along gentle W. slope.
32.00	Small wash, drains W.
40.48	The ¼ sec. cor. of secs. 23 and 24, marked by a granite stone 6x8x20 ins., firmly set and plainly mkd. ¼ on W. face.
	At the corner point
	Set an iron post 36 ins. long, 1 in. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.
	T29S R10E ¼ S23 | S24 1964
	Place original stone alongside and N. of the iron post.
	N. 0°18' E., beginning new measurement.
	Decs. 20 ft. over rolling land, draining W.
29.40	Small wash, drains NW.
34.60	Small wash, drains W.
40.51	The cor. of secs. 13, 14, 23 and 24, marked by a granite stone 8x15x20 ins., firmly set and plainly mkd. 3 notches on S. and 1 notch on E. face.
	At the corner point
	Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.
	T29S R10E S14 | S13 S23 | S24 1964
	Place original stone alongside and N. of the iron post.
	Land, rolling. Soil, sand and exposed sandstone. Timber, none. Undergrowth, shadscale and scattered bunch grass.
	From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp.

Dependent Resurvey, T. 29 S., R. 10 E.

CHAINS

S. 89°06' W., bet. secs. 13 and 24.

Over broken desert land, asc. gentle E. slope.

9.20 Base of steep ascent, bears N. and S., asc. 65 ft. over rocky E. slope.

11.70 Spur, slopes N., desc. 60 ft. over rocky NW. slope.

19.60 Small draw, drains NE., asc. 40 ft. over NE. slope, over broken clay hills.

41.71 The ¼ sec. cor. of secs. 13 and 24, marked by a granite stone 4x12x18 ins., firmly set and plainly mkd. ¼ on N. face.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R10E

¼ S13/S24

1964

Place original stone alongside and N. of the iron post.

S. 89°16' W., beginning new measurement.

Over broken desert land.

3.10 Wash, 4 ft. deep, 20 lks. wide, drains N; asc. 70 ft. ove E. slope.

7.10 Spur, slopes N.; desc. 65 ft. over W. slope.

12.30 Wash in small draw, drains N.; asc. 75 ft. over broken E. slope.

23.40 Low ridge, bears irregularly N. and S.; desc. 85 ft. over W. slope, across rolling clay hills.

41.04 The cor. of secs. 13, 14, 23 and 24.

Land, broken.
Soil, sand, clay and exposed sandstone.
Timber, none.
Undergrowth, scattered shadscale and bunch grass.

N. 0°20' E., bet. secs. 13 and 14.

Over rolling desert land draining W.

2.30 Small wash, drains W.

12.10 Small wash, drains W.

40.49 The ¼ sec. cor. of secs. 13 and 14, marked by a granite stone 3x6x14 ins., firmly set and plainly mkd. ¼ on W. face.
Note: original record describes this as a sandstone.

At the corner point

Independent Resurvey, T. 29 S., R. 10 E.

CHAINS

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R10E
¼
S14|S13
1964

Place original stone alongside and W. of the iron post.

N. 0°21' E., beginning new measurement.

Desc. 20 ft. along gentle W. slope.

35.50 Wash, 2 ft. deep, 20 lks. wide, drains W.

40.26 The cor. of secs. 11, 12, 13 and 14, marked by a granite stone 8x16x18 ins., firmly set and plainly mkd. 4 notches on S. and 1 notch on E. face.
Note: original record describes this as a sandstone.
At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R10E
S11|S12
S14|S13
1964

Place original stone alongside and N. of the iron post.

Land, rolling desert.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, scattered shadscale and bunch grass.

From the cor. of secs. 7, 12, 13 and 18 on the E. bdy. of the Tp.

S. 89°39' W., bet. secs. 12 and 13.

Over rolling desert land, along gentle N. slope.

1.50 Small wash, drains N., desc. 20 ft. along gentle N. slope.

24.20 Wash, 6 ft. deep, 40 lks. wide, drains N. 20° E., asc. 30 ft. along N. slope.

40.86 Point for the ¼ sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of original cor.

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R10E
¼ S12/S13
1964

Desc. 30 ft. along N. slope.

De dent Resur e T 2 S R 10 E

CHAINS

45.10 Small hollow, drains NE., asc. 105 ft. over E. slope.

58.10 Top of ascent on low ridge, bears irregularly N. and S.; thence over gravelly bench on ridge.

71.90 Point, projects S., desc. 65 ft. over W. slope.

81.72 The cor. of secs. 11, 12, 13 and 14.

Land, rolling and broken.
Soil, sandy clay.
Timber, none.
Undergrowth, scattered shadscale and bunch grass.

N. 0°27' E., bet. secs. 11 and 12.

Over rolling desert land, along gentle W. slope.

40.41 The ¼ sec. cor. of secs. 11 and 12, marked by a granite stone 4x10x16 ins., firmly set and plainly mkd. ¼ on W. face.
Note: original record describes this as a sandstone.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R10E
¼
S11 | S12
1964

Place original stone alongside and W. of the iron post.

N. 0°23' E., beginning new measurement.

Continue along gentle W. slope

5.60 Trail road, bears NE. and SW.

40.15 The cor. of secs. 1, 2, 11 and 12, marked by a sandstone 4x10x18 ins., firmly set and plainly mkd. 5 notches on S. and 1 notch on E. face.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R10E

S2	S1
S11	S12

1964

Place original stone alongside and W. of the iron post.

Land, rolling.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, scattered shadscale and bunch grass.

Dependent Resurvey, T. 29 S., R. 10 E.

CHAINS

From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp.

S. 89°36' W., bet. secs. 1 and 12.

Over broken desert land, asc. 40 ft. over E. slope of clay knoll.

5.70 Clay knoll, about 4 chs. diam., desc. 80 ft. over W. slope of knoll.

9.20 Wash, 4 ft. deep, 30 lks. wide, drains irregularly N., asc. 40 ft. over NE. slope, across small clay hill.

40.93 The ¼ sec. cor. of secs. 1 and 12, marked by a sandstone 4x10x16 ins., firmly set and plainly mkd. ¼ on N. face.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 12 ins. in the ground, to bedrock, and in a mound of stone 3 ft. base, to top, with brass mkd.

T29S R10E

¼ S1/S12

1964

Place original stone alongside and N. of the iron post.

S. 89°54' W., beginning new measurement.

Asc. NE. slope.

2.40 Base of steep ascent, bears NW. and SE., asc. 135 ft. over steep NE. slope.

14.20 Crest steep ascent, bears NW. and SE., thence over broken sandstone bench.

25.00 Small hollow, drains N., continue over bench.

40.24 The cor. of secs. 1, 2, 11 and 12.

Land, broken.
Soil, clay, sand and exposed sandstone.
Timber, none.

N. 0°25' E., bet. secs. 1 and 2.

Over rolling land with exposed patches of sandstone, along gentle W. slope

40.50 The ¼ sec. cor. of secs. 1 and 2, marked by a sandstone 8x10x20 ins., firmly set and plainly mkd. ¼ on W. face.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R10E

¼

S2|S1

1964

De endent Resurvey, T. 29 S., R. 10 E.

CHAINS

Place original stone alongside and W. of the iron post.

N. 0°24' E., beginning new measurement.

Continue along gentle W. slope of sandstone bench.

2.80 Small wash, drains W.

22.00 Wash, 3 ft. deep, 20 lks. wide, drains W.

26.80 Sandstone rib, about 8 ft. high, bears NE. and SW.

40.25 The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., marked by an iron post set, mkd. and witnessed as described in the field notes of the concurrent resurvey of the S. bdy. of T. 28 S., R. 10 E.

Land, slightly broken.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, shadscale and scattered bunch grass.

From the cor. of secs. 34 and 35, on the S. bdy. of the Tp, an iron post, 2 ins. diam. set, mkd. and witnessed as described in the resurvey of the S. bdy., in 1919.

N. 1°16' E., bet. secs. 34 and 35.

Over broken desert land, desc. 90 ft. over N. slope.

11.30 Hollow, drains NE., asc. 50 ft. over SE. slope.

18.30 Spur, slopes NE., desc. 90 ft. over N. slope.

38.30 Small draw, drains NW., asc. 60 ft. over rocky S. slope.

39.70 Rocky rise, bears E. and W., desc. 20 ft. over N. slope.

40.32 Point for the ¼ sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of original cor.

Set an iron post 30 ins. long, 2½ ins. diam., 16 ins. in the ground, in a mound of stone 3 ft. base, to top, with brass cap mkd.

T29S R10E
¼
S34|S35
1964

Desc. 60 ft. over N. slope.

54.00 Wash, 3 ft. deep, 20 lks. wide, drains NW., asc. 60 ft. over S. slope.

61.10 Spur, slopes W., desc. 30 ft. over N. slope.

71.10 Wash, 2 ft. deep, 20 lks. wide, drains W., asc. 30 ft. over S. slope.

80.64 Point for the cor. of secs. 26, 27, 34 and 35, at proportionate distance; there is no remaining evidence of original corner.

Dependent Resurvey, T. 29 S., R. 10 E.

CHAINS	
	Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R10E S27 | S26 S34 | S35 1964 Corner falls on top of spur sloping W. Land, broken. Soil, clay, sand and exposed sandstone. Timber, none. Undergrowth, scattered shadscale and bunch grass.
	From the cor. of secs. 25, 26, 35 and 36. N. 89°53' W., bet. secs. 26 and 35. Over broken desert land, asc. 20 ft. over E. slope.
3.50	Low rise, bears N. and S., desc. 50 ft. over W. slope.
7.70	Wash, 3 ft. deep, 20 lks. wide, drains N., thence over gentle NE. slope.
19.30	Wash, 4 ft. deep, 30 lks. wide, drains N.
25.20	Wash, 3 ft. deep, 20 lks. wide, drains NE., asc. 40 ft. over NE. slope.
41.08	Point for the ¼ sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of original cor. Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R10E ¼ S26 S35 1964 Cor. falls at base of steep ascent, bears N. and S., asc. 190 ft. over ledge E. slope.
44.60	Crest of steep ascent, bears N. and S., thence over sandstone bench.
51.70	Leave bench, desc. 95 ft. over SW. slope, in small draw.
63.00	End of descent in draw draining SW., asc. 40 ft. over SE. slope.
73.60	Point, projects SW.; desc. 60 ft. over NW. slope, over spurs sloping W.
82.16	The cor. of secs. 26, 27, 34 and 35. Land, broken. Soil, clay, sand and exposed sandstone. Timber, none. Undergrowth, scattered shadscale and bunch grass.
	N. 0°05' W., bet. secs. 26 and 27.

De endent Resurve T. 29 S. R. 10 E.

CHAINS

Over broken desert land, desc. 50 ft. over N. slope of spur.

4.90 Small draw, drains W., asc. 95 ft. over ledgy S. slope of draw.

11.50 Crest low rim, bears irregularly E. and W., thence over bench, across patches of barren sandstone.

40.31 Point for the ¼ sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of original corner.

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R10E
¼
S27|S26
1964

Cor. falls on N. slope of clay hill; desc. 20 ft. over N. slope hill.

41.50 Base clay hill, desc. 100 ft. over broken NW. slope.

55.90 S. crest ravine, bears NW. and SE.; desc. 85 ft. over NE. slope.

58.47 Bottom ravine, drains NW.; asc. 100 ft. over SW. slope.

63.20 Point, projects W.; desc. 85 ft. over N. slope, into ravine.

66.30 Bottom ravine, drains W.; asc. 85 ft. over S. slope.

72.70 Point, projects W.; desc. 100 ft. over broken N. slope.

80.62 Point for the cor. of secs. 22, 23, 26 and 27, at proportionate distance; there is no remaining evidence of original cor.

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R10E
S22|S23
S27|S26
1964

Land, broken.
Soil, clay, sand and exposed sandstone.
Timber, none.
Undergrowth, scattered shadscale and bunch grass.

From the cor. of secs. 23, 24, 25 and 26.

N. 89°33' W., bet. secs. 23 and 26.

Over rolling desert land, desc. 20 ft. along gentle NW. slope.

13.80 Wash, 3 ft. deep, 20 lks.wide, drains N.

25.30 Wash, 3 ft. deep, 30 lks. wide, drains NW.

CHAINS	
39.00	Dirt road, bears irregularly SE. and W.
40.26	Point for the ¼ sec. cor. of secs. 23 and 26, at proportionate distance; there is no remaining evidence of original corner. Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R10E ¼ S23/S26 1964 Cor. falls on S. side of road. Continue along gentle N. slope.
70.50	Base of ascent, bears N. and S., asc. 60 ft. over E. slope of blue clay spur.
74.70	Clay spur, slopes N., desc. 30 ft. over NW. slope.
80.52	The cor. of secs. 22, 23, 26 and 27. Land, mostly rolling. Soil, sand, clay and exposed sandstone. Timber, none. Undergrowth, scattered shadscale and bunch grass.
	N. 0°16' E., bet. secs. 22 and 23. Over broken desert land, desc. 30 ft. over N. slope of clay hills.
9.70	Leave clay hills, desc. 25 ft. over rolling land, draining NE.
13.20	Dirt road, bears E. and W.
21.00	Wash, 3 ft. deep, 20 lks. wide, drains NE.
30.30	Wash, 4 ft. deep, 40 lks. wide, drains NE.
40.31	Point for the ¼ sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of original corner. Set an iron post 36 ins. long, 1 in. diam., 30 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R10E ¼ S22|S23 1964 Desc. 15 ft. over gentle NE. slope.
42.90	Wash, 2 ft. deep, 10 lks. wide, drains NE.
58.70	Trail road, bears NE. and SW.
72.80	Wash, 3 ft. deep, 20 lks. wide, drains NE.

De endent Resurve T. 29 S. R 10 E.

CHAINS

80.62 The cor. of secs. 14, 15, 22 and 23, marked by a granite s stone 8x12x20 ins., firmly set and plainly mkd. 3 notches on S. and 2 notches on E. face.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R10E

S15	S14
S22	S23

1964

Place original stone alongside and W. of the iron post.

Land, broken to rolling.
Soil, clay, sand and exposed sandstone.
Timber, none.
Undergrowth, shadscale and bunch grass.

From the cor. of secs. 13, 14, 23 and 24.

N. 89°43' W., bet. secs. 14 and 23.

Over broken land, desc. 20 ft. over gentle NW. slope.

5.10 Small wash, drains NW.

26.70 Birch Creek, dry, drains irregularly N.

40.40 The ¼ sec. cor. of secs. 14 and 23, marked by a sandstone 4x14x20 ins., firmly set and plainly mkd. ¼ on N. face. Note: original record describes this as a granite stone.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R10E

¼ S14 / S23

1964

Place original stone alongside and N. of the iron post.

N. 89°58' W., beginning new measurement.

Desc. 25 ft. along gentle N. slope.

12.10 Wash, 4 ft. deep, 20 lks. wide, drains N.

21.00 Wash, 3 ft. deep, 30 lks. wide, drains NE., asc. 20 ft. over gentle NE. slope

37.00 Trail road, bears N. and S.

40.34 The cor. of secs. 14, 15, 22 and 23.

Land, broken.
Soil, sandy.
Timber, none.
Undergrowth, shadscale and bunch grass.

Dependent Resurvey T. 29 S. R. 10 E.

CHAINS	
	N. 0°39' E., bet. secs. 14 and 15.
	Over broken desert land.
1.50	Wash, 4 ft. deep, 40 lks. wide, drains NE., asc. 25 ft. over gravelly SE. slope.
28.80	N. end gravelly rise, desc. 25 ft. over gentle NE. slope.
33.70	Trail road, bears NW. and SE.
38.70	Wash, 2 ft. deep, 30 lks. wide, drains NE.; asc. 10 ft. over S. slope, enter blue clay hills.
40.49	The ¼ sec. cor. of secs. 14 and 15, marked by a granite stone 6x10x20 ins., firmly set and plainly mkd. ¼ on W. face.
	At the corner point
	Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T29S R10E ¼ S15|S14 1964
	Place original stone alongside and W. of the iron post.
	N. 1°09' E., beginning new measurement.
	Asc. 15 ft. over S. slope of clay hill.
4.20	Crest clay hill, bears NE. and SW.; desc. 30 ft. over NE. slope, across clay hills.
23.10	Wash, 3 ft. deep, 20 lks. wide, drains NE.
40.35	Point for the cor. of secs. 10, 11, 14 and 15, at proportionate distance; there is no remaining evidence of original cor.
	Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T29S R10E S10|S11 S15|S14 1964
	Land, broken. Soil, sandy clay. Timber, none. Undergrowth, shadscale and bunch grass.
	From the cor. of secs. 11, 12, 13 and 14.
	N. 89°42' W., bet. secs. 11 and 14.
	Over rolling desert land, desc. 50 ft. over gentle W. slope.

De endent Resurve T. 29 S. R. 10 E.

CHAINS

29.35 Wash, 3 ft. deep, 20 lks. wide, drains N.; asc. 20 ft. over gentle E. slope.

39.93 The ¼ sec. cor. of secs. 11 and 14, marked by a granite stone 6x10x18 ins., firmly set and plainly mkd. ¼ on N. face.
Note: original record describes this as a sandstone.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R10E

¼ S11/S14

1964

Place original stone alongside and N. of the iron post.

N. 89°55' W., beginning new measurement.

Asc. 25 ft. over gentle E. slope.

26.10 Crest of steep descent, irregularly bearing N. and S.; desc. 60 ft. over W. slope.

30.10 Wash, 4 ft. deep, 20 lks. wide, drains N.; thence over rolling land.

39.95 The cor. of secs. 10, 11, 14 and 15.

Land, rolling and broken.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, shadscale and bunch grass.

N. 0°20' E., bet. secs. 10 and 11.

Over rolling desert land, along gentle E. slope.

2.50 Small wash, drains E.

10.00 Wash, 3 ft. deep, 30 lks. wide, drains NE.

10.80 Trail road, bears E. and W.

40.34 Point for the ¼ sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of original cor.

Set an iron post 36 ins. long, 1 in. diam., 30 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R10E

¼

S10|S11

1964

Continue along gentle E. slope.

42.30 Wash, 3 ft. deep, 20 lks. wide, drains NE.

50.00 Wash, 2 ft. deep, 10 lks. wide, drains E.

[illegible]

CHAINS	
71.40	Wash, 2 ft. deep, 20 lks. wide, drains E.
80.68	The cor. of secs. 2, 3, 10 and 11, marked by a granite stone 3x16x24 ins., firmly set and plainly mkd. 5 notches on S. and 2 notches on E. face. At the corner point Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R10E S3 S2 S10 S11 1964 Place original stone alongside and W. of the iron post. Land, rolling. Soil, sandy clay. Timber, [illegible]. Undergrowth, shadscale and scattered [illegible] grass.
	From the cor. of secs. 1, [illegible], 11 and [illegible]. N. 89°[illegible] W., bet. secs. [illegible]. [illegible] slope.
[illegible]	Trail road, bears [illegible] and [illegible].
[illegible]	Wash, [illegible] ft. deep, [illegible] lks. wide, [illegible] NE. slope.
40.23	The [illegible] face. [illegible] At the corner point Set an [illegible] the ground, in a collar of stone, with brass cap mkd. T29S R10E [illegible] 1964 Place original stone alongside and N. of the iron post.
	N. 89°52' W., beginning new measurement. Asc. 10 ft. over gentle NE. slope.
19.60	Crest low rise, bears S. and NW.; desc. 65 ft. over gentle W. slope.
29.80	Wash in bottom small hollow, drains N.; asc. 35 ft. over gentle NE. slope.
39.79	The corner of secs. 2, 3, 10 and 11.

De emdent Resurve T. 29 S. R. 10 E.

CHAINS

Land, rolling.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, shadscale and bunch grass.

N. 1°43' W., bet. secs. 2 and 3.

Over rolling desert land, desc. 30 ft. over gentle NE. slope.

8.90 Wash, 4 ft. deep, 30 lks. wide, drains NE., about 10 chs. to Birch Creek; thence over broken land on W. side of Birch Creek.

26.50 Wash, 3 ft. deep, 20 lks. wide, drains NE., about 7 chs. to Birch Creek.

36.90 Gully, drains NE., 6 chs. to Birch Creek.

40.05 The ¼ sec. cor. of secs. 2 and 3, marked by a granite stone 4x6x18 ins., firmly set and plainly mkd. ¼ on W. face.

At the corner point

Set an iron post 36 ins. long, 1 in. diam., 30 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R10E
¼
S3|S2
1964

Place original stone alongside and W. of the iron post.

N. 1°58' E., beginning new measurement.

Continue along gentle E. slope on W. side of Birch Creek.

18.90 Wash, 3 ft. deep, 30 lks. wide, drains NE., about 4 chain to Birch Creek.

40.75 The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., marked by an iron post 2½ ins. diam., set, and witnessed as described in the concurrent resurvey of the S. bdy. of T. 28 S., R. 10 E.

Land, slightly broken.
Soil, sand.
Timber, none.
Undergrowth, shadscale and bunch grass.

From the cor. of secs. 33 and 34, on the S. bdy. of the Tp., marked by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the resurvey of the S. bdy., in 1919.

N. 0°08' E., bet. secs. 33 and 34.

Over rolling desert land, on Blue Valley Benches.

40.26 Point for the ¼ sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of in 1 corner.

Dependent Resurvey, T. 29 S., R. 10 E.

CHAINS

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R10E
¼
S33|S34
1964

Continue over rolling land draining NW.

56.60 Dirt road, bears N. 20° W. and S. 20° E., desc. 30 ft. over NW. slope.

71.70 Small wash, drains NW.

80.52 The cor. of secs. 27, 28, 33 and 34, marked by a granite stone 6x14x24 ins. firmly set and plainly mkd. 1 notch on S. and 3 notches on E. face.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 16 ins. in the ground, in a mound of stone 3 ft. base, to top, with brass cap mkd.

T29S R10E
S28|S27
S33|S34
1964

Place original stone alongside and W. of the iron post.

Land, rolling.
Soil, sandy clay.
Timber, none.
Undergrowth, shadscale and bunch grass.

From the cor. of secs. 26, 27, 34 and 35.

N. 89°34' W., bet. secs. 27 and 34.

Over broken desert land, desc. 85 ft. over broken NW. slope.

16.90 Wash in bottom small draw, drains SW., about 5 chs. to junction, thence NW., asc. 40 ft. over SE. slope of spur.

19.80 Spur, slopes S., about 4 chs. to end, desc. 50 ft. over SW. slope.

22.30 Wash, 4 ft. deep, 20 lks. wide, drains N. 15° W., asc. 125 ft. over ledgy E. slope.

36.80 Point, projects N., desc. 25 ft. over W. slope of point.

40.85 Point for the ¼ sec. cor. of secs. 27 and 34, at proportionate distance; there is no remaining evidence of original corner.

Set an iron post 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.

Dependent Resurvey, T. 29 S., R. 10 E.

CHAINS

T29S R10E

$\frac{1}{4}$ $\frac{S27}{S34}$

1964

Desc. 25 ft. over W. slope of point.

44.70 Crest of steep descent, bears NE. and SW., desc. 80 ft. over broken NW. slope.

48.00 Ravine, drains N., asc. 90 ft. over broken E. slope.

51.20 Rim, bears N. and SE., about 15 ft. high, desc. 20 ft. over rolling land on top of Blue Mesa, across patches of barren sandstone.

70.10 Wash, 2 ft. deep, 10 lks. wide, drains irregularly NW.

81.71 The cor. of secs. 27, 28, 33 and 34.

Land, broken E. portion, rolling W. portion.
Soil, sandy clay with exposed sandstone.
Timber, none.
Undergrowth, shadscale and scattered bunch grass.

N. 0°38' E., bet. secs. 27 and 28.

Over rolling desert land on top of Blue Mesa.

4.40 Wash, 2 ft. deep, 20 lks. wide, drains NW. irregularly; asc. 50 ft. over S. slope of sandstone butte.

8.60 Top of ascent on butte, desc. 10 ft. along broken W. slope of butte.

24.20 N. end butte, desc. 130 ft. over broken N. slope.

39.86 Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of original corner.

Set an iron post 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R10E

$\frac{1}{4}$

S28|S27

1964

Desc. 10 ft. over N. slope.

44.10 Wash, 3 ft. deep, 20 lks. wide, drains NE.; asc. 85 ft. over broken SE. slope, on E. breaks of Blue Mesa.

51.80 Crest of breaks on E. side Blue Mesa, bears irregularly NE. and SW.; asc. 25 ft. over rolling land on Blue Mesa.

58.70 Top of rise, desc. 25 ft. over rolling land on Blue Mesa.

79.72 The cor. of secs. 21, 22, 27 and 28, marked by a sandstone 6x6x20 ins., firmly set and plainly mkd. 2 notches on S. and 3 notches on E. face.

At the corner point

Dependent Resurvey, T. 29 S., R. 10 E.

CHAINS	
	Set an iron post 30 ins. long, 2½ ins. diam., 6 ins. in the ground, to bedrock, in a mound of stone 4 ft. base, to top, with brass cap mkd. T29S R10E S21 | S22 S28 | S27 1964 Place original stone alongside and W. of the iron post. Land, broken S. portion, rolling N. portion. Soil, sand and exposed sandstone. Timber, none. Undergrowth, scattered shadscale and bunch grass.
	From the cor. of secs. 22, 23, 26 and 27. S. 89°45' W., bet. secs. 22 and 27. Over broken desert land, desc. 40 ft. over NW. slope, across blue clay hills.
10.85	Wash in small hollow, drains N.; asc. 80 ft. over NE. slope.
31.00	Low ridge, bears N. and S.; desc. 25 ft. over W. slope.
40.31	Point for the ¼ sec. cor. of secs. 22 and 27, at proportionate distance; there is no remaining evidence of original corner. Set an iron post 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone 4 ft. base, to top, with brass cap mkd. T29S R10E S S22 / S27 1964 Desc. 50 ft. over W. slope.
43.75	Ravine, drains N., asc. 40 ft. over E. slope.
54.60	Spur, slopes N.; desc. 40 ft. over W. slope.
58.30	Wash, 3 ft. deep, 20 lks. wide, drains N.; asc. 100 ft. over E. slope.
70.50	Crest low rim, bears N. and S.; asc. 25 ft. over gentle E. slope, on top of Blue Mesa.
80.62	The cor. of secs. 21, 22, 27 and 28. Land, broken E. portion, rolling W. portion. Soil, clay E. portion, sand and exposed sandstone W. portion. Timber, none. Undergrowth, scattered shadscale.
	N. 0°13' W., bet. secs. 21 and 22. Over rolling desert land on top of Blue Mesa.
19.20	Dirt road, bears E. and W.

Dependent Resurvey, T. 29 S., R. 10 E.

CHAINS

40.26 The ¼ sec. cor. of secs. 21 and 22, marked by a sandstone 4x18x24 ins., firmly set and plainly mkd. ¼ on W. face.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 6 ins. in the ground, to bedrock, in a mound of stone 4 ft. base, to top, with brass cap mkd.

T29S R10E
¼
S21|S22
1964

Place original stone alongside and W. of the iron post.

N. 1°06' E., beginning new measurement.

Over rolling land on Blue Mesa.

40.65 The cor. of secs. 15, 16, 21 and 22, marked by a sandsto 8x8x30 ins., plainly mkd. 3 notches on S. and E. faces.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R10E
S16|S15
S21|S22
1964

Place original stone alongside and W. of the iron post.

Land, rolling.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, shadscale and bunch grass.

From the cor. of secs. 14, 15, 22 and 23.

S. 89°58' W., bet. secs. 15 and 22.

Over rolling desert land.

2.70 Wash, 3 ft. deep, 20 lks. wide, drains NE.; asc. 50 ft. over gentle E. slope.

40.19 The ¼ sec. cor. of secs. 15 and 22, marked by a sandstone 3x6x28 ins., firmly set and plainly mkd. ¼ on N. face.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R10E
¼ S15/S22

1964
Place original stone alongside and N. of the Iron post.

Dependent Resurvey, T. 29 S., R. 10 E.

CHAINS	
	S. 89°57' W., beginning new measurement.
	Asc. 15 ft. over gentle E. slope.
4.00	Base of steep ascent, bears irregularly N. and S.; asc. 170 ft. over ledgy E. slope.
12.10	Crest of steep ascent, rim 15 ft. high, bears irregularly S. and NW., desc. 45 ft. over rolling land on Blue Mesa, over barren sandstone.
35.21	Dirt road, bears N. and S.
40.05	The cor. of secs. 15, 16, 21 and 22.
	Land, broken to rolling. Soil, clay E. portion, sand and exposed sandstone W. portion. Timber, none. Undergrowth, scattered shadscale and bunch grass.
	N. 0°45' E., bet. secs. 15 and 16.
	Over rolling desert land on Blue Mesa.
4.40	Small wash, drains W.
21.20	Slope changes, desc. 35 ft. over N. slope.
21.60	Trail road, bears NW. and SE.
25.20	Crest low rim, bears NW. and SE.; desc. 80 ft. over ledgy NE. slope, on E. breaks of Blue Mesa.
33.90	Gully, drains NE.; asc. 45 ft. over broken SE. slope.
40.55	Point for the ¼ sec. cor. of secs. 15 and 16, at proportionate distance; there is no remaining evidence of original corner.
	Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R10E ¼ S16 | S15 1964
	Asc. 80 ft. over broken SE. slope.
51.70	Crest of rim, bears N. and SW.; desc. 40 ft. over broken sandstone, along E. rim of Blue Mesa.
81.10	Point for the cor. of secs. 9, 10, 15 and 16, at proportionate distance; there is no remaining evidence of original corner.
	Set an iron post 30 ins. long, 2½ ins. diam., 16 ins. in the ground, to bedrock, in a mound of stone 3 ft. base, to top, with brass cap mkd. T29S R10E S9 | S10 S16 | S15 1964

De endent Resurve T. 29 S. R. 10 E.

CHAINS

Land, mostly broken.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, scattered shadscale and bunch grass.

From the cor. of secs. 10, 11, 14 and 15.

N. 89°39' W., bet. secs. 10 and 15.

Over rolling desert land, draining N.

8.50 Small wash, drains NE.

17.30 Trail road, bears NE. and SE. on curve.

24.40 Wash, 3 ft. deep, 20 lks. wide, drains NE.; asc. 25 ft. over E. slope.

40.22 The ¼ sec. cor. of secs. 10 and 15, marked by a sandstone 4x10x16 ins., firmly set and plainly mkd. ¼ on N. face.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R10E

¼ S10/S15

1964

Place original stone alongside and N. of the iron post.

N. 89°58' W., beginning new measurement.

Asc. 40 ft. over gentle E. slope.

27.20 Base of steep ascent, bears N. and S.; asc. 80 ft. over E. slope of blue clay spur.

30.80 Spur, slopes NE.; desc. 40 ft. over W. slope.

33.90 Small ravine, drains NE.; asc. 140 ft. over ledgy E. slope.

40.00 Crest of rim, about 15 ft. high, bears irregularly N. and S.; thence over top of bench.

40.16 The cor. of secs. 9, 10, 15 and 16.

Land, rolling and broken.
Soil, clay, sand and exposed sandstone.
Timber, none.
Undergrowth, scattered shadscale.

N. 1°15' W., bet. secs. 9 and 10.

Over broken and exposed sandstone, about 2 chs. W. of E. rim of Blue Mesa; asc. 40 ft.

31.00 Small ravine, drains E.

Dependent Resurvey, T. 29 S. R. 10 E.

CHAINS

40.56 Point for the ¼ sec. cor. of secs. 9 and 10, at proportionate distance; no ¼ sec. cor. was established in the original survey.

Set an iron post 30 ins. long, 2½ ins. diam., 14 ins. in the ground, to bedrock, in a mound of stone 4 ft. base, to top, with brass cap mkd.

T29S R10E
¼
S9|S10

1964

Asc. 40 ft. over rolling land; leave rim, which bears NE.

81.12 The cor. of secs. 3, 4, 9 and 10, marked by a sandstone 4x10x16 ins., set in small mound of stone, plainly mkd. 5 notches on S. and 3 notches on E. face.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., on solid sandstone, over an X, in a mound of stone 4 ft. base, to top, with brass cap mkd.

T29S R10E

S4	S3
S9	S10

1964

Place original stone alongside and W. of the iron post.

Land, broken S. portion, rolling N. portion.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, scattered shadscale and bunch grass.

From the cor. of secs. 2, 3, 10 and 11.

N. 89°34' W., bet. secs. 3 and 10.

Over broken land, asc. 30 ft. over NE. slope.

10.40 Wash, 3 ft. deep, 20 lks. wide, drains NE.

39.95 The ¼ sec. cor. of secs. 3 and 10, marked by a sandstone 10x16x20 ins., firmly set and plainly mkd. ¼ on N. face.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R10E
¼ S3/S10

1964

Place original stone alongside and N. of the iron post.

N. 89°26' W., beginning new measurement.

D e t R ur e T 2 S R 0 E

CHAINS

Asc. 50 ft. over E. slope.

23.50 Base of steep and ledgy ascent, bears S. and NW.; asc. 280 ft. over ledges facing NE. By triangulation.

34.30 Crest of ledges, bears NW. and S.; thence over rolling top of Blue Mesa. End triangulation.

42.50 The cor. of secs. 3, 4, 9 and 10.

Land, broken E. portion, rolling on mesa.
Soil, sand and exposed sandstone, some clay spots.
Timber, none.
Undergrowth, scattered shadscale and bunch grass.

N. 1°18' E., bet. secs. 3 and 4.

Over rolling land on Blue Mesa.

5.20 Crest of steep descent, bears NW. and SE.; desc. 245 ft. over ledgy NE. slope.

14.00 Draw, drains E.; asc. 55 ft. over S. slope.

16.50 Spur, slopes E.; desc. 80 ft. along E. slope.

25.20 Draw, drains E.; asc. 100 ft. over S. slope.

31.00 Point, projects E.; desc. 100 ft. over N. slope.

39.83 Point for the ¼ sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of original corner.

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R10E
¼
S4|S3
1964

Continue along E. slope.

42.50 Small wash, drains E.; asc. 70 ft. over S. slope.

46.62 Spur, slopes E.; desc. 65 ft. over N. slope.

56.80 Draw, drains E.; asc. 80 ft. over SE. slope. By traverse with topography scaled from U. S. G. S. quadrangle sheet.

68.00 Base of ledgy ascent, bears NE. and SW.; asc. 200 ft. over ledgy SE. slope.

71.50 Point, projects E.; desc. 200 ft. over ledgy NE. slope.

76.00 Base of ledgy NE. slope, bears NW. and SE.; desc. 60 ft. over N. slope.

79.66 The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., marked by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of the S. bdy. of T. 28 S., R. 10 E.

Land, broken.
Soil, sand, clay and exposed sandstone.
Timber, none.
Under rowth ver scattered shadscale.

Dependent Resurvey, T. 29 S., R. 10 E.

CHAINS

From the cor. of secs. 32 and 33, on the S. bdy., marked by an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record of the resurvey of the S. bdy., in 1919.

N. 2°55' E., bet. secs. 32 and 33.

Over rolling land on Blue Mesa.

.70 Coaly Wash, 4 ft. deep, 50 lks. wide, drains NW.; desc. 20 ft.

39.09 The ¼ sec. cor. of secs. 32 and 33, marked by a granite stone 6x10x12 ins., firmly set and plainly mkd ¼ on W. face.

At the corner point

Set an iron post 1 in. diam., 36 ins. long, 28 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R10E
¼
S32|S33
1964

Place original stone alongside and W. of the iron post.

N. 3°07' W., beginning new measurement.

Desc. 20 ft. over rolling top of Blue Mesa.

41.64 The cor. of secs. 28, 29, 32 and 33, marked by a granite stone 6x12x18 ins., firmly set and plainly mkd. 1 notch on S. and 4 notches on E. face.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R10E
S29|S28
S32|S33
1964

Place original stone alongside and N. of the iron post.

Land, rolling.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, black brush and bunch grass.

From the cor. of secs. 27, 28, 33 and 34.

N. 89°26' W., bet. secs. 28 and 33.

Over rolling land on Blue Mesa.

10.00 Dirt road, bears N. and S.

40.73 The ¼ sec. cor. of secs. 28 and 33, marked by a sandstone 4x10x18 ins., firmly set and plainly mkd. ¼ on N. face.

At the corner point

Dependent Resurvey, T. 29 S., R. 10 E.

CHAINS

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R10E

¼ S28/S33

1964

Place original stone alongside and N. of the iron post.

N. 89°43' W., beginning new measurement.

Desc. 10 ft. over rolling land.

22.10 Wash, 3 ft. deep, 20 lks. wide, drains NW.; asc. 10 ft.

36.50 Small wash, drains N.

40.33 The cor. of secs. 28, 29, 32 and 33.

Land, rolling.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, black brush and bunch grass.

N. 0°58' E., bet. secs. 28 and 29.

Over rolling land on Blue Mesa, desc. 20 ft.

6.90 Wash, 3 ft. deep, 20 lks. wide, drains N. 10° E.

22.00 Wash, 2 ft. deep, 40 lks. wide, drains N. 20° W.

40.96 The ¼ sec. cor. of secs. 28 and 29, marked by a granite stone 6x12x12 ins., firmly set and plainly mkd. ¼ on W. face.

At the corner point

Set an iron post 36 ins. long, 1 in. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R10E

¼

S29|S28

1964

Place original stone alongside and W. of the iron post.

N. 0°44' E., beginning new measurement.

Desc. 15 ft. over rolling land.

2.80 Wash, 3 ft. deep, 30 lks. wide, drains NW.

3.90 Bladed dirt road, bears E. and W.

37.96 The cor. of secs. 20, 21, 28 and 29, marked by a sandstone 3x10x12 ins., firmly set and plainly mkd. 2 notches on S. and 4 notches on E. face.

At the corner point

CHAINS

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R10E

S20	S21
S29	S28

1964

Place original stone alongside and W. of the iron post.

Land, rolling.
Soil, sand.
Timber, none.
Undergrowth, black brush and bunch grass.

From the cor. of secs. 21, 22, 27 and 28.

S. 89°52' W., bet. secs. 21 and 28.

Over rolling desert land on top of Blue Mesa; asc. 35 ft.

11.60 Trail road, bears N. and S.

40.29 The ¼ sec. cor. of secs.21 and 28, marked by a sandstone 6x8x12 ins., firmly set and plainly mkd. ¼ on N. face.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R10E

¼ S21 / S28

1964

Place original stone alongside and N. of the iron post.

S. 89°52' W., beginning new measurement.

Asc. 10 ft. over rolling mesa.

8.00 Crest low rise, bears N. and S.; desc. 30 ft. over gentle NW. slope.

22.30 Bladed dirt road, bears NE. AND SW.

40.45 The cor. of secs. 20, 21, 28 and 29.

Land, rolling.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, black brush and bunch grass.

N. 1°23' W., bet. secs. 20 and 21.

Over rolling land on top of Blue Mesa.

24.00 Leave rolling land, asc. 25 ft. over broken and barren sandstone.

40.25 The ¼ sec. cor. of secs. 20 and 21, marked by a sandstone [illegible] ins., firmly set and plainly mkd. ¼ on W. face.

Dependent Resurvey, T. 29 S., R. 10 E.

CHAINS

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 6 ins. in the ground, to bedrock, in a mound of stone 4 ft. base, to top, with brass cap mkd.

T29S R10E
¼
S20|S21
1964

Place original stone alongside and W. of the iron post.

N. 2°13' E., beginning new measurement.

Continue over barren sandstone.

16.00 Slope changes, desc. 35 ft. over gentle NW. slope.

40.47 The cor. of secs. 16, 17, 20 and 21, marked by a sandstone 4x14x22 ins., firmly set and plainly mkd. 3 notches on S. and 4 notches on E. face.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R10E
S17|S16
S20|S21
1964

Place original stone alongside and W. of the iron post.

Land, rolling S. portion, broken N. portion.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, black brush and scattered bunch grass.

From the cor. of secs. 15, 16, 21 and 22.

S. 89°35' W., bet. secs. 16 and 21.

Over rolling land on top of Blue Mesa, across patches of sandstone, asc. 10 ft.

18.80 Top of small sandstone knoll, desc. 60 ft. over gentle W. slope.

40.53 The ¼ sec. cor. of secs. 16 and 21, marked by a sandstone 5x8x14 ins., firmly set and plainly mkd. ¼ on N. face.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R10E
¼ S16/S21
1964

Place original stone alongside and N. of the iron post.

CHAINS	[illegible] 29 S., R. 10 E.
	S. 89°48' W., beginning new measurement.
	Desc. 30 ft. over gentle W. slope.'
8.00	Wash, 2 ft. deep, 10 lks. wide, drains NW.
40.29	The cor. of secs. 16, 17, 20 and 21.
	Land, rolling. Soil, sand and exposed sandstone. Timber, none. Undergrowth, black brush and scattered bunch grass.
	N. 0°49' E., bet. secs. 16 and 17.
	Over rolling land, across barren sandstone.
14.60	Small wash, drains W., desc. 15 ft. along W. slope.
37.60	S. side small ravine, bears E. and W., desc. 25 ft. over N. slope.
40.94	Point for the ¼ sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of original corner.
	Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R10E ¼ S17 | S16 1964
	Desc. 10 ft. over N. slope.
43.10	Wash in ravine, drains NW.; asc. 50 ft. over S. slope.
49.70	N. side samd ravine, bears E. and W. irregularly; asc. 60 ft. over broken SW. slope.
57.70	Small hollow, drains SW.
81.88	The cor. of secs. 8, 9, 16 and 17, marked by a sandstone 4x16x24 ins.,set in small mound of stone, plainly mkd. 4 notches on S. and E. faces.
	At the corner point
	Set an iron post 30 ins. long, 2½ ins.diam., on solid sandstone, over an X, in a mound of stone 4 ft. base, to top, with brass cap mkd. T29S R10E S8 | S9 S17 | S16 1964
	Place original stone alongside and W. of iron post cor.
	Land, mostly broken. Soil, sand and exposed sandstone. Timber, none. Undergrowth, scattered shadscale and bunch grass.

Dependent Resurvey, T. 29 S., R. 10 E.

CHAINS	
	From the cor. of secs. 9, 10, 15 and 16.
	N. 89°40' W., bet. secs. 9 and 16.
	Over broken desert land, across barren sandstone, desc. 100 ft. over gentle W. slope.
7.40	Trail road, bears N. and S.
29.00	Wash in hollow, drains SW.; asc. 80 ft. over broken SE. slope.
36.50	Crest of rise, bears N. and S.; desc. gentle W. slope.
40.12	The ¼ sec. cor. of secs. 9 and 16, marked by a sandstone 10x20x26 ins., set in mound of stone, plainly mkd. ¼ on N. face.
	At the corner point
	Set an iron post 30 ins. long, 2½ ins. diam., on solid sandstone, over an X, in a mound of stone 4 ft. base, to top, with brass cap mkd.
	T29S R10E
	¼ S9/S16
	1964
	Place original stone alongside and N. of the iron post.
	N. 89°52' W., beginning new measurement.
	Desc. 75 ft. over broken SW. slope.
21.80	Small hollow, drains SW.; asc. 40 ft. along broken S. slope.
40.64	The cor. of secs. 8, 9, 16 and 17.
	Land, broken. Soil, sand and exposed sandstone. Timber, none. Undergrowth, very scattered shadscale.
	N. 0°20' W., bet. secs. 8 and 9.
	Over broken desert land, asc. 60 ft. over SW. slope, across barren sandstone.
26.90	Top sandstone knoll, about 5 chs. diam.; desc. 50 ft. over N. slope.
29.30	Small wash, drains W.; asc. 40 ft. over SW. slope.
40.38	Point for the ¼ sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of original corner.
	Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T29S R10E
	¼ S8 | S9
	1964

Dependent Resurvey, T. 29 S., R. 10 E.

CHAINS	
	Asc. 40 ft. over gentle SW. slope.
54.70	Trail road, bears E. and W.
76.60	Rim, bears NW. and E.; desc. 90 ft. over ledgy N. slope, into head of canyon.
80.76	The cor. of secs. 4, 5, 8 and 9, marked by a sandstone 6x6x24 ins., firmly set and plainly mkd. 5 notches on S. and 4 notches on E. face. At the cor. point Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R10E S5 | S4 S8 | S9 1964 Place original stone alongside and W. of the iron post. Land, broken. Soil, sand and exposed sandstone. Timber, none.
	From the cor. of secs. 3, 4, 9 and 10. West, bet. secs. 4 and 9. Over rolling bench land, across patches of barren sandstone; desc. 20 ft. over gentle SW. slope.
37.80	Trail road, bears N. and S.
40.08	The ¼ sec. cor. of secs. 4 and 9, marked by a sandstone 6x9x16 ins., firmly set and plainly mkd. ¼ on N. face. At the corner point Set an iron post 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R10E S4 ¼ S9 1964 Place original stone alongside and N. of the iron post.
	S. 89°54' W., beginning new measurement. Desc. gentle SW. slope.
24.70	Rim, bears N. and curves SW.; desc. 110 ft. along broken N. slope, in head of canyon.
39.36	The cor. of secs. 4, 5, 8 and 9. Land, broken. Soil, sand and exposed sandstone. Timber, none. Undergrowth, scattered shadscale.

CHAINS

N. 0°11' E., bet. secs. 4 and 5.

Over broken desert land, in head of wide canyon; desc. 20 ft. over NW. slope.

8.40 Wash, 4 ft. deep, 20 lks. wide, drains NW.; desc. 50 ft. along W. slope, in head of canyon.

16.60 Small draw, drains W., continue along broken W. slope.

25.20 S. side draw, bears E. and W., desc. 125 ft. over ledgy N. slope.

34.80 Wash in draw, drains W., asc. 100 ft. over S. slope.

38.70 N. side draw, bears W. and curves NE.

38.92 Point selected for the witness ¼ sec. cor. of secs. 4 and 5.

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R10E
¼
W C
S5 | S4
1964

Continue over ledgy head of canyon.

39.92 Point for the ¼ sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of original corner. Falls on ledges facing E. and cannot be monumented. Asc. 200 ft. over ledgy SE. slope.

64.39 Crest of rim, bears NE. and SW.; asc. 20 ft. over broken bench.

79.84 The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., marked by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of the S. bdy. of T. 28 S., R. 10 E.

Land, broken.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, scattered shadscale.

From the cor. of secs. 31 and 32, on the S. bdy of the Tp., marked by an iron post 2 ins. diam. set, mkd. and witnessed as described in the official record of the resurvey of the S. bdy., in 1919.

N. 0°11' E., bet. secs. 31 and 32,

Over rolling land of Blue Mesa, about 1 ch. W. of dirt road, which bears N. and S.

39.22 The ¼ sec. cor. of secs. 31 and 32, marked by a granite stone 10x18x18 ins., firmly set and plainly mkd. ¼ on W. face.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

Dependent Resurvey, T. 29 S., R. 10 E.

CHAINS

T29S R10E
¼
S31|S32
1964

Place original stone alongside and W. of the iron post.

North, beginning new measurement.

Along W. side of dirt road which bears N. and S.; desc. 40 ft. over rolling mesa.

6.00 Road along E. side of line curves to NE.

39.36 The cor. of secs. 29, 30, 31 and 32, marked by a granite stone 6x6x20 ins., firmly set and plainly mkd. 1 notch on S. 5 notches on E. face.
Note: original record describes this as a sandstone.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R10E

S30|S29
S31|S32

1964

Place original stone alongside and W. of the iron post.

Land, rolling.
Soil, sandy clay.
Timber, none.
Undergrowth, black brush and bunch grass.

From the cor. of secs. 28, 29, 32 and 33.

S. 88°51' W., bet. secs. 29 and 32.

Over rolling land on top of Blue Mesa.

24.60 Wash, 3 ft. deep, 20 lks. wide, drains N. 20° W., continue over rolling land.

39.82 Point for the ¼ sec. cor. of secs. 29 and 32, at proportionate distance; there is no remaining evidence of original corner.

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R10E

¼ S29/S32

1964

Continue over rolling land.

51.70 Bladed dirt road, bears NE. and SW.; asc. 30 ft. over gentle E. slope.

d t u e T 2 S 10 E

CHAINS

61.00 Crest rise, bears N. and S.; desc. 55 ft. over gentle W. slope.

77.50 Wash, 3 ft. deep, 20 lks. wide, drains N. 25° W.

79.64 The cor. of secs. 29, 30, 31 and 32.

Land, rolling.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, black brush and bunch grass.

N. 88°22' W., bet. secs. 30 and 31.

Over rolling desert land on top of Blue Mesa, along gentl N. slope.

12.10 Small wash, drains NW.

16.60 Wash, 3 ft. deep, 20 lks. wide, drains N.

27.00 Small wash, drains N. 20° E.

37.50 Small wash, drains N.

40.04 Point for the ¼ sec. cor. of secs. 30 and 31, at proportionate distance; there is no remaining evidence of original corner.

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R10E

¼ S30/S31

1964

Asc. 40 ft. over gentle NE. slope.

46.10 Small wash, drains NE.

63.60 Enter blue clay hills; asc. 125 ft. over E. slope of hill

67.80 Low clay ridge, bears irregularly N. and S.; desc. 85 ft. over SW. slope.

74.10 Small draw, drains S.; asc. 65 ft. over E. slope of clay hill.

79.38 The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., marked by an iron post 2½ ins. diam. set, mkd. and witnessed as described in the field notes of the concurrent resurvey of the E. bdy. of T. 29 S., R. 9 E.

Land, broken.
Soil, sandy clay.
Timber, none.
Undergrowth, shadscale on mesa, none on clay hills.

From the cor. of secs. 29, 30, 31 and 32.
N 0° 04' W., between Secs. 29 and 30.
Over rolling land on top of Blue Mesa, desc. 15 ft. over gentle NW. slope.

5.70 Wash, 3 ft. deep, 30 lks. wide, drains NW.

Resurvey T. 29 S. R. 10 E.

CHAINS

40.44 The ¼ sec. cor. of secs. 29 and 30, marked by a sandstone 3x16x18 ins., firmly set and plainly mkd. ¼ on W. face.

At the cor. point

Set an iron post 30 ins. long, 2½ ins. diam., 18 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R10E
¼
S30|S29
1964

Place original stone alongside and W. of the iron post.

N. 0°17' E., beginning new measurement.

Desc. 25 ft. over gentle NW. slope.

11.40 Small wash, drains W.

23.30 Small wash, drains W.

40.19 The cor. of secs. 19, 20, 29 and 30, marked by a granite stone 8x16x20 ins., firmly set and plainly mkd. 2 notches on S. and 5 notches on E. face.
Note: original record describes this as a sandstone.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R10E

S19	S20
S30	S29

1964

Place original stone alongside and W. of the iron post.

Land, rolling.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, black brush and bunch grass.

From the cor. of secs. 20, 21, 28 and 29.

S. 89°59' W., bet. secs. 20 and 29.

Over rolling land on top of Blue Mesa, along gentle NW. slope.

21.20 Wash, 3 ft. deep, 20 lks. wide, drains N.

40.40 The ¼ sec. cor. of secs. 20 and 29, marked by a sandstone 10x18x20 ins., firmly set and plainly mkd. ¼ on N. face.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

CHAINS

T29S R10E

$\frac{S20}{S29}$

1964

Place original stone alongside and N. of the iron post.

N. 89°56' W., beginning new measurement.

Desc. 10 ft. along gentle N. slope.

5.20 Wash, 2 ft. deep, 30 lks. wide, drains N.

40.25 The cor. of secs. 19, 20, 29 and 30.

Land, rolling.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, black brush and bunch grass.

N. 89°23' W., bet. secs. 19 and 30.

Over rolling land on top of Blue Mesa, desc. 15 ft. over gentle NW. slope.

8.70 Wash, 3 ft. deep, 20 lks. wide, drains N.; asc. 35 ft. over gentle NE. slope.

40.05 The ¼ sec. cor. of secs. 19 and 30, marked by a granite stone 6x10x16 ins., firmly set and plainly mkd. ¼ on N. face.
Note: original record describes this as a sandstone.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R10E

$\frac{S19}{S30}$

1964

Place original stone alongside and N. of corner.

N. 88°02' W., beginning new measurement.

Asc. 30 ft. over gentle E. slope.

8.50 Base of steep ascent, bears irregularly N. and S.; asc. 105 ft. over E. slope. Enter hills.

15.00 Low ridge, bears N. and S.; desc. 60 ft. over W. slope.

23.00 Small hollow, drains NW.; asc. 40 ft. over E. slope of small spur.

27.90 Low spur, slopes N.; desc. 35 ft. over gentle NW. slope.

39.39 The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of th Tp., marked by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurr- rve of the E. bd . of . 29 S. R. 9 E.

Dependent Resurvey, T. 29 S., R. 10 E.

CHAINS

Land, rolling E. portion, broken W. portion.
Soil, sand and exposed sandstone E. portion, clay W. portion.
Timber, none.
Undergrowth, black brush and bunch grass.

From the cor. of secs. 19, 20, 29 and 30.

N. 0°08' E., bet. secs. 19 and 20.

Over rolling desert land on top of Blue Mesa, desc. 30 ft. over gentle NW. slope.

8.00 Small wash, drains W.

40.38 Point for the ¼ sec. cor. of secs. 19 and 20, at proportionate distance; there is no remaining evidence of original corner.

Set an iron post 30 ins. long, 2½ ins. diam., 10 ins. in the ground, to bedrock, in a mound of stone 4 ft. base, to top, with brass cap mkd.

T29S R10E
¼
S19|S20
1964

Desc. 40 ft. over gentle N. slope.

75.30 Wash, 6 ft. deep, 30 lks. wide, drains irregularly N., from S. 10° W., thence along W. side of wash.

80.76 The cor. of secs. 17, 18, 19 and 20, marked by a sandstone 8x8x20 ins., firmly set and plainly mkd. 3 notches on S. and 5 notches on E. face.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R10E
S18|S17
S19|S20
1964

Place original stone alongside and W. of the iron post.

Land, rolling.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, shadscale and scattered bunch grass.

From the cor. of secs. 16, 17, 20 and 21.

N. 89°15' W., bet. secs. 17 and 20.

Over rolling land on top of Blue Mesa, asc. 35 ft. over gentle NE. slope.

33.70 Top of sandy rise, bears N. and S.; desc. gentle W. slope over barren sandstone.

40.29 The ¼ sec. cor. of secs. 17 and 20, marked by a mound of

De endent Resurve T. 29 S. R. 10 E.

CHAINS

stone and faint ¼ mkd. on barren sandstone.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., on solid sandstone, over an X, in a mound of stone 4 ft. base, to top, with brass cap mkd.

T29S R10E

¼ S17/S20

1964

S. 89°17' W., beginning new measurement.

Desc. 115 ft. over broken W. slope, across barren sandstone.

20.60 Wash, 6 ft. deep, 40 lks. wide, drains NW., asc. 65 ft. over NE. slope.

36.60 N. end low rise, slopes N.; desc. 35 ft. over W. slope.

39.70 Wash, 4 ft. deep, 30 lks. wide, drains N. about 9 chs. to junction; asc. 10 ft. over E. slope.

40.66 The cor. of secs. 17, 18, 19 and 20.

Land, generally rolling to broken.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, black brush and scattered bunch grass.

N. 89°05' W., bet. secs. 18 and 19.
Over broken desert land, asc. 60 ft. over NE. slope.

39.84 The ¼ sec. cor. of secs. 18 and 19, marked by a sandstone 3x12x14 ins., firmly set and plainly mkd. ¼ on N. face.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R10E

¼ S18/S19

1964

Place original stone alongside and N. of the iron post.

N. 88°46' W., beginning new measurement.

Asc. 10 ft. over gentle NE. slope.

7.40 Small wash, drains NE.; asc. 10 ft. over NE. slope.

21.60 Base of steeper ascent, bears irregularly N. and S.; asc. 55 ft. over E. slope.

26.70 Low rise, slopes N.; desc. 40 ft. over W. slope.

Dependent Resurvey, T. 29 S., R. 10 E.

CHAINS	
39.51	The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., marked by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the concurrent resurvey of the E. bdy. of T. 29 S., R. 9 E. Land, broken. Soil, sand and exposed sandstone. Timber, none. Undergrowth, black brush and scattered bunch grass.
	From the cor. of secs. 17, 18, 19 and 20. N. 0°43' E., bet. secs. 17 and 18. Over broken land, desc. 20 ft. over N. slope.
9.30	Town Wash, 6 ft. deep, 30 lks. wide, drains NW., asc. 70 ft. along gentle SW. slope.
15.00	Crest low rim of ledges, bears NW. and SE., asc. 45 ft. along gentle W. slope.
30.00	Top of ascent on W. slope, desc. 10 ft. along W. slope.
41.20	The ¼ sec. cor. of secs. 17 and 18, marked by a sandstone 3x14x30 ins., firmly set but dimly mkd. ¼ on W. face; marks having nearly weathered away. At the corner point Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R10E ¼ S18 | S17 1964 Place original stone alongside and W. of the iron post.
	N. 0°06' E., beginning new measurement. Desc. 10 ft. along gentle W. slope.
19.10	Crest of low rim of ledges, bears NW. and SE.; desc. 75 ft. over NE. slope and ledges facing NE.
24.00	Base of rim, bears NW. and SE., desc. 30 ft. over gentle NE. slope.
40.50	The cor. of secs. 7, 8, 17 and 18, marked by a sandstone 4x14x28 ins., firmly set and mkd. 4 notches on S. and 5 notches on E. face. At the corner point Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R10E S7 | S8 S18 | S17 1964

De endent Resurve T 29 S R. 10 E

CHAINS

Place original stone alongside and W. of the iron post.

Land, rolling.
Soil, sand and exposed sandstone.
Timber, none.

From the cor. of secs. 8, 9, 16 and 17.

N. 89°48' W., bet. secs. 8 and 17.

Over broken land on top of Blue Mesa, desc. 40 ft. over gentle SW. slope.

38.30 E. rim small ravine, bears irregularly N. and S.; desc. 35 ft. over ledgy W. slope.

40.68 The ¼ sec. cor. of secs. 8 and 17, marked by a sandstone 10x16x30 ins. , supported by a small mound stone on barren sandrock, plainly mkd. ¼ on N. face.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., on solid sandstone over an X, in a mound of stone 4 ft. base, to top, with brass cap mkd.

T29S R10E

¼ S8/S17

1964

Place original stone alongside and N. of the iron post.

S. 89°34' W., beginning new measurement.

Desc. 50 ft. over W. slope in head of small ravine.

6.30 Wash in ravine, drains S., asc. 70 ft. over E. slope.

10.50 Low spur, slopes S., desc. 60 ft. over SW. slope.

20.00 Spur, slopes S., desc. 100 ft. over W. slope.

27.80 Wash, 2 ft. deep, 30 lks. wide, drains NW.; asc. 10 ft. over gentle NE. slope.

40.82 The cor. of secs. 7, 8, 17 and 18.

Land, broken.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, scattered shadscale and bunch grass.

N. 89°35' W., bet. secs. 7 and 18.

Over broken desert land, asc. 110 ft. over NE. slope.

19.40 Sandstone spur, slopes N. 20° W.; desc. 115 ft. over SW. slope.

30.90 Town Wash, 3 ft. deep, 40 lks. wide, drains irregularly ; asc. 45 ft. over broken E. slope.

Dependent Resurvey, T. 29 S., R. 10 E.

CHAINS	
40.39	The ¼ sec. cor. of secs. 7 and 18, marked by a sandstone 6x8x30 ins., firmly set and plainly mkd. ¼ on N. face. At the corner point Set an iron post 30 ins. long, 2½ ins. diam., 10 ins. in the ground, to bedrock, in a mound of stone 4 ft. base, to top, with brass cap mkd. T29S R10E ¼ S7/S18 1964 Deposit original stone alongside and N. of the iron post.
	N. 89°49' W., beginning new measurement. Asc. 105 ft. over broken E. slope.
11.30	Low rim, bears irregularly NW. and SE.; thence over broken bench.
32.20	Small gravel hill, bears N. and S.; desc. 50 ft. over W. slope.
39.32	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., marked by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of the E. bdy. of T. 29 S., R. 9 E. Land, broken. Soil, sand and exposed sandstone. Timber, none. Undergrowth, shadscale and scattered bunch grass.
	From the cor. of secs. 7, 8, 17 and 18. N. 0°55' E., bet. secs. 7 and 8. Over broken desert land, desc. 35 ft. over wash area.
13.20	Leave wash area,which drains to NW., asc. 95 ft. over ledgy S. slope.
16.10	Crest of ledgy ascent bears irregularly NW. and SE.; asc. 30 ft. over broken bench land.
31.80	Trail road, bears NE. and SW.
41.99	The ¼ sec. cor. of secs. 7 and 8, marked by a sandstone 6x8x20 ins., firmly set and plainly mkd. ¼ on W. face. At the corner point Set an iron post 30 ins. long, 2½ ins. diam., 18 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R10E ¼ S7|S8 1964 Deposit original stone alongside and W. of the iron post.

De endent Resurvey, T. 29 S., R. 10 E.

CHAINS

N. 0°17' E., beginning new measurement.

Desc. 15 ft. over broken bench.

19.30 Crest steep descent, bears irregularly NE. and SW.; desc. 100 ft. over ledgy NW. slope.

29.30 Wash in small ravine, drains SW., asc. 100 ft. over ledgy SE. slope.

38.30 Point, projects SW.; desc. 70 ft. over ledgy NW. slope of ravine.

39.92 The cor. of secs. 5, 6, 7 and 8, marked by a sandstone 6x10x14 ins., firmly set and plainly mkd. 5 notches on S. and E. faces.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., 12 ins. in the ground, to bedrock, in a mound of stone 3 ft. base, to top, with brass cap mkd.

T29S R10E

S6	S5
S7	S8

1964

Place original stone alongside and W. of the iron post.

Land, broken.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, scattered shadscale and bunch grass.

From the cor. of secs. 4, 5, 8 and 9.

N. 89°57' W., bet. secs. 5 and 8.

Over broken desert land, asc. 100 ft. over ledgy NE. slop .

7.90 Crest steep ascent, bears NW. and curves SE.; thence over broken and barren sandstone on N. end of Blue Mesa.

40.06 The ¼ sec. cor. of secs. 5 and 8, marked by a sandstone 6x10x20 ins., on barren sandstone, supported by small mound of stones, plainly mkd. ¼ on N. face.

At the corner point

Set an iron post 30 ins. long, 2½ ins. diam., on solid sandstone, over an X, in a mound of stone 4 ft. base, to top, with brass cap mkd.

T29S R10E

¼ S5
S8

1964

Place original stone alongside and N. of the iron post.

N. 88°36' W., beginning new measurement.

Asc. 30 ft. over broken bench.

De : dent Resurvey, T. 29 S., R. 10 E.

CHAINS	
16.40	Rim, bears SE. and curves NW.; desc. 105 ft. along ledgy S. slope of ravine.
25.00	End of descent, asc. 90 ft. along ledgy S. slope of ravine.
31.30	Same rim, bears SW. and curves SE.; thence over broken bench.
38.80	Rim, bears NE. and SW.; desc. 50 ft. over ledgy NW. slope.
40.05	The cor. of secs. 5, 6, 7 and 8.
	Land, broken. Soil, sand and exposed sandstone. Timber, none. Undergrowth, shadscale and bunch grass.
	S. 88°45' W., bet. secs. 6 and 7.
	Over broken desert land, desc. 60 ft. over ledgy NW. slope.
5.40	Wash in ravine, drains SW.; asc. 55 ft. over E. slope.
8.90	Spur, slopes SW.; desc. 55 ft. over NW. slope.
16.80	Wash, drains SW.; asc. 75 ft. over SE. slope.
24.00	Ledge point, projects SW.; desc. 185 ft. over ledgy W. slope.
34.40	Town Wash, drains irregularly N.; asc. 70 ft. over broken E. slope.
40.00	The ¼ sec. cor. of secs. 6 and 7, marked by a sandstone 6x16x26 ins., firmly set and plainly mkd. ¼ on N. face.
	At the corner point
	Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T29S R10E ¼ S6/S7 1964
	Place original stone alongside and N. of the iron post.
	N. 89°43' W., beginning new measurement.
	Asc. 60 ft. over broken E. slope.
7.70	Crest steep ascent, bears irregularly N. and S.; asc. 50 ft. over gentle E. slope of broken bench.
26.90	Top of ascent on bench, bears N. and S.; desc. 25 ft. over gentle W. slope.
40.43	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., marked by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of the E. bdy. of T. 29 S., R. 9 E.

De endent Resurve T. 29 S R 10 E.

CHAINS

Land, broken.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, shadscale and scattered bunch grass.

From the cor. of secs. 5, 6, 7 and 8.

N. 0°19' W., bet. secs. 5 and 6.

Over broken desert land, desc. 40 ft. over ledgy NW. slope.

3.40 Wash in ravine, drains SW.; asc. 90 ft. over ledgy SE. slope.

8.00 Point, projects W.; desc. 100 ft. over N. slope.

16.20 Wash in ravine, drains SW.; asc. 90 ft. over SE. slope.

22.20 Rim of bench, bears W. and NE.; asc. 30 ft. over broken sandstone bench, along E. side of breaks.

39.92 The ¼ sec. cor. of secs. 5 and 6, marked by a sandstone 6x12x30 ins., firmly set and plainly mkd. ¼ on W. face.

At the corner point

Set an iron post 30 ins. long, 2½ ins.diam., 6 ins. in the ground, in a mound of stone 4 ft. base, to top, with brass cap mkd.

T29S R10E
¼
S6|S5
1964

Place original stone alongside and W. of the iron post.

N. 0°07' E., beginning new measurement.

Continue over broken sandstone bench.

30.00 Head of small ravine about 40 ft. deep, drains W.; 15 ft. over broken sandstone bench.

39.88 The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., marked by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of the S. bdy. of T. 28 S., R. 10 E.

Land, broken.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, shadscale and bunch grass.

GENERAL DESCRIPTION

T. 29 S., R. 10 E. is made up of barren desert land, with rolling land of Blue Mesa in center of the Tp. and sandstone breaks on the east and west sides.

The only water noted during the survey consists of a few seeps in the bottom of Town Wash and Birch Creek.

There is no timber within the Tp. Undergrowth consists of scattered shadscale and bunch grass with a few willows in the wash bottoms.

CHAINS

Main access to the Tp. is by a dirt road which enters the Tp. on the E. bdy. of sec. 25, and leaves the Tp. on the S. bdy. of sec. 32. There are several small branches of this road within the Tp. constructed for oil exploration and stockmen's use.

The elevation varies from about 4500 to 5000 ft. above sea level.

Blank

Page

Form 4-680
(June 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
LaVern Griffin	Transitman
Ferrel Reynolds	Notekeeper
Ashley Allen	Front Chainman
Dean Crabb	Flagman
Morris E. Blackburn	Cornerman

CERTIFICATE OF SURVEY

I, Craig P. Sylvester, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 21st day of August, 19 63, I have dependently resurveyed the east boundary and subdivisional lines of Township 29 South, Range 10 East,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

January 13, 1966
(Date)

Craig P. Sylvester
~~(Cadastral Surveyor)~~
(Supervisory Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date FEB 17 1966

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the dependent resurvey of the east boundary and the subdivisional lines of Township 29 South, Range 10 East of the Salt Lake Meridian in the State of Utah,

executed by Craig P. Sylvester, Supervisory Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

APR 14 1966
(Date)

E. E. Lemmon
(Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in~~

, is a true copy of the original field notes.

(Date)

Blank

Page

Blank

Page

ORIGINAL

Form 4-679
(January 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

205

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY

AND SUBDIVISION

OF

TOWNSHIP 28 SOUTH, RANGE 11 EAST

Of the SALT LAKE Meridian,

In the State of UTAH.

EXECUTED BY

Craig P. Sylvester Supervisory Cadastral Surveyor

Under special instructions dated August 21, 1963, which provided for the surveys included under Group Number 466, approved August 22, 1963, and assignment instructions dated September 24, 1963.

Survey commenced December 16, 1963

[illegible] February [illegible]

206

DEPT. OF THE INTERIOR
BUR OF LAND MGMT

1966 MAY 12 AM 10 24 .6

RECEIVED
STATE & LAND OFFICE
SALT LAKE CITY, UTAH

INDEX DIAGRAM

Township 28 SOUTH, Range 11 EAST,

6 55	55 5 54	41 4 41	32 3 31	23 2 22	14 1 14
7 52	53 8 51	40 9 39	30 10 29	21 11 20	13 12 12
18 49	50 17 49	38 16 37	28 15 28	19 14 19	11 13 11
19 47	47 20 46	36 21 35	27 22 26	18 23 17	10 24 9
30 44	45 29 44	34 28 34	25 27 25	16 26 16	9 25 8
31 6	43 32 5	33 33 4	24 34 3	15 35 3	7 36 2

Dependent Resurvey, South Boundary and Subdivision, Township 28 South, Range 11 East

CHAINS

The north boundary was surveyed by A. D. Ferron in 1883, and was resurveyed by Elliot Bird and Charles F. Moore in 1934. The Henry Mountain Guide Meridian along the east boundary was surveyed by A. D. Ferron in 1883, and resurveyed by Elliot Bird in 1922, and the record appears in the resurvey of the Henry Mountain Guide Meridian in T. 28 S. The west boundary was surveyed by A. D. Ferron in 1883, and concurrently resurveyed, and the record appears in the field notes of T. 28 S., R. 10 E. The south boundary and subdivisional lines were surveyed by A. D. Ferron in 1883.

The following field notes are those of a dependent resurvey of the south boundary and subdivisional lines of T. 28 S., R. 11 E.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions, 1947, and the Special Instructions dated August 21, 1963.

Corners on the east-west lines were set on the true latitudinal curve. Lines connecting previously established corners were run by random and true method, but for simplification of the record, the random lines are omitted from these field notes.

All lines of this survey were run by the direct method where lines were accessible; lines inaccessible were run by traverse or triangulation methods. Distances to topography on lines run by traverse and triangulation methods are approximately as scaled from U.S.G.S. topographic sheets. The details of such traverses and triangulations have been thoroughly checked and verified, and in order to simplify the records, the diagrams and reductions are omitted from these field notes.

The direction of the lines of this survey were determined by reference to true meridians established on line by hour angle observations on Polaris. They were carried forward by sustained angulation, being supplemented by numerous other observations on Polaris taken throughout the progress of the survey.

Before restoring lost corners, the lines of the original survey were retraced and a diligent search made for any evidence of the original corners. The rules of proportionate measurement were applied to ascertain the position of the lost corner after every reasonable possibility of finding direct evidence of the corner had been exhausted.

The geographic position for the southeast corner of the township is at Latitude 38° 19' 23.6" N., and Longitude 110° 39' 22.2" W., as adjusted from traverses to U.S.G.S. triangulation stations, "Pinto" at Latitude 38° 23' 57.956" N., and Longitude 110° 45' 17.800" W., located N. 58° 55' W., 30.15 chains distance from the corner of sections 5, 6, 7 and 8, T. 28 S., R. 11 E., and "Hanks" at Latitude 38° 21' 47.741" N., and Longitude 110° 40' 42.723" W., located N. 41° 24' W., 25.98 chains distance from the ¼ section corner of sections 23 and 24, T. 28 S., R. 11 E.

The magnetic declination was read at a number of stations throughout the township and the average of the several readings was found to be 15° 30' E.

Dependent Resurvey, South Boundary, T. 28 S., R. 11 E.

CHAINS

Dependent Resurvey, South Boundary, T. 28 S., R. 11 E.

Reestablishment of the Survey Executed by
A. D. Ferron, Deputy Surveyor, in 1883.

Beginning at the corner of Tps. 28 and 29 S., Rs. 11 and 12 E., monumented by an iron post, 3 ins. diam., set, mkd and witnessed as described in the official record of the resurvey of the Henry Mt. Guide Meridian in 1922.

N. 89° 53' W., bet. secs. 1 and 36.

Over rolling sandy desert land, asc. 50 ft. over gentle E. slope.

40.27 Point for the ¼ sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T28S R11E
¼ S36 / S1
T29S
1963

Place boulder 2x2x2 ft. N. of corner, 3 ft. dist.

Asc. gentle E. slope.

44.20 Top of rise, bears N. and S., desc. 60 ft. over broken NW. slope.

60.70 Graded dirt road, Hanksville to Hite, bears N. 30° E., and S. 30° W.; thence over small flat, across small gullies draining N.

80.54 Point for the cor. of secs. 1, 2, 35 and 36, at proportionate distance; there is no remaining evidence of original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 3 ins. in the ground, in a mound of stone 4 ft. base, to top, with brass cap mkd.

T28S R11E
S35 | S36
S2 | S1
T29S
1963

Cor. situated on N. slope of small hill, on W. side of flat.

Land, rolling and broken.
Soil, sandy on rolling land, rocky gravel on broken land.
Timber, none.
Undergrowth, blackbrush and scattered bunch grass.

Dependent Resurvey, South Boundary, T. 28 S., R. 11 E.

CHAINS

N. 89° 53' W., bet. secs. 2 and 35.

Over broken desert land, asc. 35 ft. over broken E. slope of low hills.

8.80 E. crest of broken bench bears NE. and SW., desc. 35 ft. over W. slope of bench.

14.50 Dry Valley Wash, 3 ft. deep, 30 lks. wide, drains NE.; asc. 35 ft. over gentle E. slope of bench.

32.30 Top of small knoll.

40.27 Point for the ¼ sec. cor. of secs. 2 and 35, at proportionate distance; there is no remaining evidence of original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R11E
¼ S35 / S2
T29S
1963

Asc. 85 ft. over E. slope.

56.80 Trail road, bears NW. and SE.

79.30 Crest of low ridge, bears NE. and SW.; desc. 20 ft. over W. slope.

80.54 Point for the cor. of secs. 2, 3, 34 and 35, at proportionate distance; there is no remaining evidence of original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., on solid sandstone, over an X, and in a mound of stone 4 ft. base, 28 ins. high, with brass cap mkd.

T28S	R11E
S34	S35
S3	S2

T29S
1963

Land, mostly rolling.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, shadscale and bunch grass.

N. 89° 53' W., bet. secs. 3 and 34.

Over broken desert land, desc. 40 ft. over NW. slope.

30.90 Graded dirt road, Hanksville to Sawmill Basin, bears N. 5° W., and S. 5° E., asc. 35 ft. over E. slope.

40.27 The ¼ sec. cor. of secs. 3 and 34, marked by a sandstone, 4x8x10 ins., dimly mkd. ¼.

At the cor. point

Dependent Resurvey, South Boundary, T. 28 S., R. 11 E.

CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R11E
¼ S34 / S3
T29S
1963

Deposit the original stone alongside the iron post.

Cor. situated on rise, which slopes NE.

N. 89° 34' W., beginning new measurement.

Desc. 50 ft. over broken NW. slope.

16.00 Wash, 2 ft. deep, 30 lks. wide, drains NE.; asc. 15 ft. over E. slope.

23.00 Base of ledgy bluff, bears irregularly NW. and S., asc. 160 ft. over ledgy NE. slope.

35.00 Crest of ledgy NE. slope, bears NW. and S.; asc. 10 ft. over broken bench.

40.82 Point for the cor. of secs. 3, 4, 33 and 34, at proportionate distance; there is no remaining evidence of original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. i the ground, in collar of stone, with brass cap mkd.

T28S R11E
S33 | S34
S4 | S3
T29S
1963

Land, broken.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, shadscale and bunch grass.

N. 89° 34' W., bet. secs. 4 and 33.

Over broken desert land, desc. 10 ft. over gentle NW. slope.

18.90 Desc. 45 ft. over series of small gullies draining NW.

40.82 Point for the ¼ sec. cor. of secs. 4 and 33, at proportionate distance; there is no remaining evidence of original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in collar of stone, with brass cap mkd.

T28S R11E
¼ S33 / S4
T29S
1963

Dependent Resurvey, South Boundary, T. 28 S., R. 11 E.

CHAINS

Desc. 40 ft. along irregular N. slope, across series of small rises and gullies draining N.

81.64 Point for the corner of secs. 4, 5, 32 and 33, at proportionate distance; there is no remaining evidence of original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R11E
S32 | S33
S5 | S4
T29S
1963

Cor. situated on W. slope of small spur which projects N.

Land, broken.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, shadscale and bunch grass.

N. 89° 34' W., bet. secs. 5 and 32.

Over broken desert land, asc. 20 ft. over broken NE. slope.

8.00 E. rim of hollow, bears irregularly NW. and SE., desc. 130 ft. over ledgy W. slope of hollow.

18.10 Bull Creek, 5 ft. deep, 1 ch. wide, drains irregularly NW., asc. E. slope in bottom of hollow.

22.50 Base of ledgy ascent, bears irregularly N. and S., asc. 100 ft. over ledgy E. slope.

25.50 Crest of rim, bears irregularly N. and S., thence over top of spur.

29.00 W. crest of spur, projects irregularly N. and SW., desc. 80 ft. over ledgy W. slope, into small draw.

34.00 Wash in bottom of draw, drains irregularly N., asc. 40 ft. over steep E. slope.

38.82 Point selected for the witness ¼ sec. cor. of secs. 5 and 32.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R11E
¼ W C ← S32
S5
T29S
1963

Witness cor. falls at base of ledges facing E.

Asc. 40 ft. over ledgy E. slope.

Dependent Resurvey, South Boundary, T. 28 S., R. 11 E.

CHAINS	
40.82	Point for the ¼ sec. cor. of secs. 5 and 32, at proportionate distance, falls on inaccessible ledge and cannot be monumented. There is no evidence of original corner.
	Asc. 160 ft. over irregular ledges facing NE.
61.90	Top of red ledges, on ridge about 30 lks. wide, bears NE. and SW., desc. 70 ft. over NW. slope of ridge.
69.90	Base of ridge, bears NE. and S., thence over rolling desert land.
81.64	The corner of secs. 5, 6, 31 and 32, marked by a sandstone 2x8x12 ins., dimly mkd., 1 notch on W. and 5 notches on E. face.
	At the corner point
	Set an iron post. 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T28S R11E S31 | S32 S6 | S5 T29S 1963
	Deposit original stone alongside the iron post.
	Land, broken. Soil, sand and exposed sandstone. Timber, few cottonwood trees along Bull Creek. Undergrowth, scattered shadscale and bunch grass.
	N. 89° 47' W., bet. secs. 6 and 31.
	Over rolling desert land, asc. 75 ft. over E. slope.
17.90	Rocky rise, bears NE. and SW., desc. 90 ft. over broken NW. slope.
40.18	The ¼ sec. cor. of secs. 6 and 31, mkd. by a sandstone 4x6x14 ins., plainly mkd. ¼.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T28S R11E ¼ S31 S6 T29S 1963
	Deposit original stone alongside and N. of iron post.
	N. 89° 25' W., beginning new measurement.
	Desc. 20 ft. over broken land, across a series of gullie draining generally NW. to N.

Dependent Resurvey, South Boundary, T. 28 S., R. 11 E.

CHAINS	
21.40	E. bank of hollow, bears irregularly N. and S., desc. 60 ft. over W. slope of hollow.
25.90	Wash in bottom of hollow, drains N. 20° E.; asc. 60 ft. over E. slope of hollow.
31.10	W. bank hollow, bears irregularly N. and S.; desc. 35 ft. over broken W. slope.
40.21	The cor. of Tps. 28 and 29 S., Rgs. 10 and 11 E., mkd. by an iron post. 2½ ins. diam., set, mkd. and witnessed as described in field notes of the concurrent resurvey of the E. bdy. of T. 29 S., R. 10 E. Land, broken. Soil, sand and exposed sandstone. Timber, none. Undergrowth, shadscale and bunch grass.

Dependent Resurvey of the Subdivisional Lines, T. 28 S., R. 11 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by A. D. Ferron, Deputy Surveyor, in 1883.

Beginning at the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., previously described.

N. 0° 43' E., bet. secs. 35 and 36.

Over broken desert land, desc. 20 ft.

11.00 Dry Valley Wash, 20 lks. wide, 2 ft. deep, drains NE.; asc. 45 ft. over small pass.

26.50 Crest of a low hill, bears NE. and SW.; desc. 35 ft. over N. slope.

39.97 The ¼ sec. cor. of secs. 35 and 36, mkd. by a granite stone 6x8x12 ins., plainly mkd. ¼.

At the cor. point

Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

T28S R11E
¼
S35 | S36
1963

Deposit original stone alongside and N. of the iron post.

Raise a mound of stone 2½ ft. base, 2½ ft. high W. of cor.

N. 0° 04' E., beginning new measurement.

Asc. 55 ft. over sandy SE. slope.

Dependent Resurvey, T. 28 S., R. 11 E.

CHAINS	
17.40	Low sandy rise, bears E. and W., thence along sandy E. slope.
40.33	Point for the cor. of secs. 25, 26, 35 and 36, at proportionate distance; there is no remaining evidence of original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R11E S26 | S25 S35 | S36 1963 Land, broken. Soil, sandy-gravelly on hills. Timber, none. Undergrowth, blackbrush and scattered bunch grass.
	From the cor. of secs. 25 and 36, on the E. bdy. of the Tp., mkd. by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the record of resurvey of the Henry Mt. Guide Meridian, through T. 28 S., in 1922. S. 89° 56' W., bet. secs. 25 and 36. Over broken desert land, desc. 65 ft. over NW. slope.
13.70	Dry Valley Wash, 2 ft. deep, 2 chs. wide, drains NE.; asc. 60 ft. along broken SE. slope.
22.80	Crest of sandstone ledges, bears SW. and NE., asc. 10 ft. along broken S. slope.
31.50	Low spur, slopes S., desc. 50 ft. along broken S. slope.
39.69	Point selected for the witness ¼ sec. cor. of secs. 25 and 36. Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R11E ¼ W ← S25 C S36 1963
40.19	Point for the ¼ sec. of secs. 25 and 36, at proportionate distance, falls in gully draining SE., and cannot be perpetuated. There is no remaining evidence of original corner. Asc. 65 ft. over gentle E. slope.
49.00	Graded dirt road, Hanksville to Hite, bears NW. and SE.
80.38	The cor. of secs. 25, 26, 35 and 36. Land, broken. Soil, sand and exposed sandstone. Timber, none. Undergrowth, shadscale and bunch grass.

Dependent Resurvey, T. 28 S., R. 11 E.

CHAINS

N. 0° 04' W., bet. secs. 25 and 26.

Over sandy rolling desert land, along gentle E. slope.

40.15 Center graded dirt road, Hanksville to Hite, bears NW. and SE.

40.33 Point for the ¼ sec. cor. of secs. 25 and 26, at proportionate distance; falls on roadway.

At the corner point

Bury glass 24 ins. in the ground.

from which

An iron post, 30 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 15° 10' W., 1.00 ch. dist., with brass cap mkd. T28S R11E ¼ S26 66 ft. RM 1964 and an arrow pointing to the true corner.

An iron post, 30 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 44° 50' E., 1 ch. dist., with brass cap mkd. T28S R11E ¼ S25 66 ft. RM 1964 and an arrow pointing to the true corner.

Asc. 40 ft. along sandy E. slope.

80.66 Point for the cor. of secs. 23, 24, 25 and 26, at proportionate distance; there is no remaining evidence of original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R11E

S23	S24
S26	S25

1963

Land, rolling.
Soil, sandy.
Timber, none.
Undergrowth, shadscale and bunch grass.

From the cor. of secs. 24 and 25, on the E. bdy. of the Tp., mkd. by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the record of resurvey of the Henry Mt. Guide Meridian, through T. 28 S., in 1922.

N. 89° 57' W., bet. secs. 24 and 25.

Over rolling sandy desert land, asc. 65 ft. over irregular SE. slope.

40.33 Point for the ¼ sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of original corner.

Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground, in a collar of stone, with brass cap mkd.

Dependent Resurvey, T. 28 S., R. 11 E.

CHAINS	
	T28S R11E ¼ S24 / S25 1963
	Asc. 30 ft. over gentle SE. slope.
80.66	The cor. of secs. 23, 24, 25 and 26.
	Land, rolling. Soil, sandy. Timber, none. Undergrowth, shadscale and bunch grass.
	N. 0° 02' E., bet. secs. 23 and 24.
	Over rolling sandy desert land, asc. 70 ft. over SE. slope.
30.00	Top of ascent, thence over level bench.
40.33	Point for the ¼ sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of original corner.
	Set an iron post 36 ins. long, 1 in. diam., 28 ins. in the ground, in a collar of stone, with brass cap mkd.
	T28S R11E ¼ S23 | S24 1963
	from which
	U.S.G.S. triangulation station "Hanks", bears N. 41° 24' W., 25.98 chs. distance.
77.10	Slope changes, desc. 15 ft. over gentleNE. slope.
80.66	The cor. of secs. 13, 14, 23 and 24, mkd. by a lava stone, 10x20x30 ins., plainly mkd., 3 notches on S., 1 notch on E. face. Note: Official record describes this as a trachyte stone.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T28S R11E S14 | S13 S23 | S24 1963
	Deposit original stone alongside and N. of the iron post.
	Raise a mound of stone 2½ ft. base, 2 ft.high, W. of cor.
	Land, rolling. Soil, sandy. Timber, none. Undergrowth, shadscale and bunch grass.

CHAINS	
	From the cor. of secs. 13 and 24, on the E. bdy. of the Tp., mkd. by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the record of resurvey of the Henry Mt. Guide Meridian, through T. 28 S., in 1922.
	N. 89° 53' W., bet. secs. 13 and 24.
	Over rolling sandy bench land.
40.44	Point for the ¼ sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of original corner.
	Set an iron post, 36 ins. long, 1 in. diam., 28 ins. in the ground, in a collar of stone, with brass cap mkd.
	T28S R11E ¼ S13/S24 1964
	Asc. 30 ft. over rolling bench, along gentle N. slope.
80.88	The corner of secs. 13, 14, 23 and 24.
	Land, rolling bench. Soil, sandy. Timber, none. Undergrowth, shadscale and bunch grass.
	N. 0° 34' E., bet. secs. 13 and 14.
	Over rolling sandy desert land, desc. 70 ft. over irregular N. slope.
41.93	The ¼ sec. cor. of secs. 13 and 14, mkd. by a granite stone, 5x8x14 ins., dimly mkd. ¼. Note: Original record describes this stone as a trachyte.
	At the cor. point
	Set an iron post, 36 ins. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.
	T28S R11E ¼ S14 | S13 1963
	Deposit original stone alongside and N. of the iron post.
	Raise a mound of stone 2 ft. base, 2½ ft. high, W. of cor.
	N. 0° 08' W., beginning new measurement.
	Desc. 40 ft. over gentle N. slope.
4.10	Dirt road, bears E. and W.
39.40	Point for the cor. of secs. 11, 12, 13 and 14, at proportionate distance; there is no remaining evidence of original corner.

Dependent Resurvey, T. 28 S., R. 11 E.

CHAINS	
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R11E S11 | S12 S14 | S13 1963 Land, rolling. Soil, sandy. Timber, none. Undergrowth, shadscale and bunch grass.
	From the corner of secs. 12 and 13, on the E. bdy. of the Tp., mkd. by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the record of resurvey of the Henry Mt. Guide Meridian, through T. 28 S., in 1922. N. 89° 45' W., bet. secs. 12 and 13. Over broken desert land, asc. 30 ft. along gentle N. slope.
2.00	Small hollow drains N.
15.80	Wash, 2 ft. deep, 20 lks. wide, drains N.
31.90	Wash, 2 ft. deep, 10 lks. wide, drains NE.; thence over rolling bench land.
40.54	The ¼ sec. cor. of secs. 12 and 13, mkd. by a granite stone, 4x6x8 ins., plainly mkd. ¼. Note: Record describes this stone as a trachyte. At the corner point Set an iron post, 36 ins. long, 1 in. diam., 28 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R11E ¼ S12 S13 1964 Deposit original stone alongside and N. of the iron post.
	N. 88° 40' W., beginning new measurement. Continue over rolling bench land, along gentle N. slope.
20.20	Small wash, drains N.
27.30	Small wash, drains N.
40.25	The cor. of secs. 11, 12, 13 and 14. Land, broken to rolling. Soil, sandy. Timber, none. Undergrowth, shadscale and bunch grass.

CHAINS

N. 0° 21' W., bet. secs. 11 and 12.

Over rolling sandy bench land, desc. 55 ft. over N. slope.

39.40 The ¼ sec. cor. of secs. 11 and 12, mkd. by a granite stone, 8x10x12 ins., plainly mkd. ¼.
Note: Record describes this stone as a trachyte.

At the corner point

Set an iron post, 36 ins. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

T28S R11E
¼
S11 | S12
1963

Deposit original stone alongside and N. of the iron post.

Raise a mound of stone, 2 ft. base, 2½ ft. high, W. of cor.

N. 0° 19' E., beginning new measurement.

Desc. 20 ft. over gentle N. slope of bench.

28.20 S. rim of breaks of Dirty Devil River, bears irregularly NW. and SE.; desc. 90 ft. over ledgy N. slope.

31.10 Small draw, drains NE., asc. 40 ft. over ledgy SE. slope.

34.80 Small sandstone point, projects NE.; desc. 50 ft. over NE. slope.

37.60 Base of ledgy breaks, bears NW. and SE., thence over river bottom, through heavy growth of willows.

40.23 The cor. of secs. 1, 2, 11 and 12, mkd. by a sandstone, 6x10x20 ins., plainly mkd., 5 notches on S. and 1 notch on E. face.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T28S R11E
S2 | S1
S11 | S12
1963

Deposit original stone alongside and N. of the iron post.

Raise a mound of stone 3 ft. base, 2½ ft. high, W. of corner.

Land, rolling and broken.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, shadscale and bunch grass, willows along river bottom.

Dependent Resurvey, T. 28 S., R. 11 E.

CHAINS	
	From the cor. of secs. 1 and 12, on the E. bdy. of the Tp., mkd. by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the record of the resurvey of the Henry Mt. Guide Meridian, through T. 28 S., in 1922.
	N. 89° 58' W., bet. secs. 1 and 12.
	Over broken desert land; desc. 40 ft. over SW. slope, across barren sandstone, on E. side of Dirty Devil River.
9.00	Base of sandstone breaks, bears irregularly NW. and SE.; thence over river bottom through willows.
40.43	Point for the ¼ sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of original corner.
	Set an iron post, 36 ins. long, 1 in. diam., 28 ins. in the ground, in a collar of stone, with brass cap mkd.
	T28S R11E ¼ S1/S12 1964
	Raise a mound of stone 2½ ft. base, 2½ ft. high, N. of cor.
41.10	Leave willows, thence across sandy bed of Dirty Devil River, which flows SE.
50.50	Right bank of Dirty Devil River stream bed, bears NW. and SE., thence through willows in river bottom.
80.86	The cor. of secs. 1, 2, 11 and 12.
	Land, mostly river bottom. Soil, sand and exposed sandstone. Timber, none. Undergrowth, willows in river bottom.
	N. 0° 18' E., bet. secs. 1 and 2.
	Over sandy land of Dirty Devil River bottom; through willows.
16.00	Leave willows, thence across stream bed.
20.00	Present river channel, small stream of water, flows S. 70° E., continue across sandy stream bed.
32.00	Enter willows.
39.43	Point for the ¼ sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of original corner.
	Set an iron post, 36 ins. long, 1 in. diam., 28 ins. in the ground, in a collar of stone, with brass cap mkd.

Dependent Resurvey, T. 28 S., R. 11 E.

CHAINS	
	T28S R11E ¼ S2 | S1 1963
	Continue over sandy river bottom, through willows.
45.00	Leave river bottom and willows, asc. 30 ft. over sandy S. slope.
51.70	Base of barren sandstone hills, bears E. and W., asc. 70 ft. over S. slope.
59.80	Slope changes, asc. 10 ft. along broken W. slope, across barren sandstone.
79.00	The cor. of secs. 1 and 2, on the N. bdy. of the Tp., mkd. by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the resurvey of the S. bdy. of T. 27 S., R. 11 E., in 1934.
	Land, level river bottom and broken sandstone on N. portion. Soil, sand and exposed sandstone. Timber, none. Undergrowth, willows in river bottom.
	From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp.
	N. 0° 24' E., bet. secs. 34 and 35.
	Over broken desert land, along gentle W. slope, over sand and exposed sandstone.
23.90	Trail road, bears NW. and SE.
39.97	Point for the ¼ sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of original corner.
	Set an iron post, 36 ins. long, 2½ ins. diam., 28 ins. in the ground, in a collar of stone, with brass cap mkd.
	T28S R11E ¼ S34 | S35 1963
	Continue over sandy land, draining W.
75.30	Base of bluff, bears N. 70° W., and curves SE., asc. 75 ft. over SW. slope.
79.10	Crest of bluff, bears N. 70° W., and curves SE., thence over rolling bench.
79.94	The cor. of secs. 26, 27, 34 and 35, mkd. by a granite stone, 3x6x8 ins., plainly mkd. 1 notch on S. and 2 notches on E. face.
	At the corner point

Dependent Resurvey, T. 28 S., R. 11 E.

CHAINS	
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T28S R11E S27 | S26 S34 | S35 1963 Deposit original stone alongside and N. of the iron post. Raise a mound of stone, 2½ ft. base, 2½ ft. high, W. of cor. Land, broken. Soil, sand and exposed sandstone. Timber, none. Undergrowth, shadscale and scattered bunch grass.
	From the cor. of secs. 25, 26, 35 and 36. S. 89° 53' W., bet. secs. 26 and 35. Over sandy rolling desert land, asc. 35 ft. over gentle E. slope.
40.27	Point for the ¼ sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of original corner. Set an iron post, 36 ins. long, 1 in. diam., 28 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R11E ¼ S26 S35 1964 Asc. 15 ft. over gentle E. slope.
63.70	Crest of bluff, bears S. and NW., desc. 80 ft. over SW. slope of bluff.
73.50	Small draw, drains S., asc. 80 ft. over E. slope.
79.00	Crest of bluff, bears N. and S., thence over bench.
80.54	The cor. of 26,27, 34 and 35. Land, rolling and broken. Soil, sand and exposed sandstone. Timber, none. Undergrowth, shadscale and bunch grass.
	N. 0° 08' E., bet. secs. 26 and 27. Over rolling desert land,desc. 25 ft. along gentle W. slope.
40.41	The ¼ sec. cor. of secs. 26 and 27, mkd. by a granite stone, 6x10x12 ins., plainly mkd. ¼. Note: Official record describes this as a small gypsum rock.

Dependent Resurvey, T. 28 S., R. 11 E.

CHAINS

At the corner point

Set an iron post, 36 ins. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

T28S R11E
¼
S27 | S26
1963

Deposit original stone alongside and N. of the iron post.

Raise a mound of stone 3 ft. base, 2 ft. high, W. of cor.

N. 0° 32' W., beginning new measurement.

Desc. 10 ft. over sandy rolling bench land.

34.00 Small wash, drains NW.

40.25 Point for the cor. of secs. 22, 23, 26 and 27, at proportionate distance; there is no remaining evidence of original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R11E
S22 | S23
S27 | S26
1963

Land, rolling bench.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, shadscale and bunch grass.

From the cor. of secs. 23, 24, 25 and 26.

N. 89° 43' W., bet. secs. 23 and 26.

Over rolling sandy desert land; asc. 60 ft. over gentle E. slope.

23.20 Top of rise, bears N. and S.; desc. 70 ft. over gentle W. slope.

33.70 Gravel road, Hanksville to Hite, bears NW. and SE.

40.33 The ¼ sec. cor. of secs. 23 and 26, mkd. by a granite stone, 6x10x10 ins., plainly mkd. ¼.

At the corner point

Set an iron post, 36 ins. long, 1 in. diam., 28 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R11E
¼ S23
S26
1964

Dependent Resurvey, T. 28 S., R. 11 E.

CHAINS	
	Deposit original stone alongside and N. of the iron post.
	S. 89° 28' W., beginning new measurement.
	Desc. 60 ft. over gentle W. slope.
40.36	The cor. of secs. 22, 23, 26 and 27.
	Land, rolling. Soil, sandy. Timber, none. Undergrowth, blackbrush and scattered bunch grass.
	N. 0° 46' E., bet. secs. 22 and 23.
	Over sandy rolling bench land.
15.00	Enter series of small spurs and washes draining W.
23.00	Gravel road, Hanksville to Hite, bears N. 71° W., and S. 71° E., continue over small spurs and washes draining W.
33.10	Small wash, drains W.
40.25	Point for the ¼ sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of original corner.
	Set an iron post, 36 ins. long, 1 in. diam., 28 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R11E ¼ S22 | S23 1963
	Desc. 35 ft. over small spurs and washes draining W.
47.20	Leave small spurs and washes, desc. 25 ft. along sandy W. slope.
53.80	A lone sandstone knob, 50 lks. diam., 10 ft. high, bears W., 1.00 ch. distance.
80.50	The cor. of secs. 14, 15, 22 and 23, mkd. by a granite stone 12x12x16 ins., plainly mkd., 3 notches on S. and 2 notches on E. face. Note: Official record describes this as a sandstone.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T28S R11E S15 | S14 S22 | S23 1963
	Deposit original stone alongside and N. of the iron post.

Dependent Resurvey, T. 28 S., R. 11 E.

CHAINS	
	Raise a mound of stone 2½ ft. base, 2½ ft. high W. of cor. Land, broken. Soil, sand and exposed sandstone. Timber, none. Undergrowth, blackbrush and bunch grass.
	From the cor. of secs. 13, 14, 23 and 24. S. 89° 45' W., bet. secs. 14 and 23. Over rolling sandy desert land, asc. 10 ft. over gentle NE. slope.
19.90	Small wash, drains N.
27.00	Crest of low ridge, bears N. and S., desc. 60 ft. over W. slope.
39.84	Point for the ¼ sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R11E ¼ S14/S23 1963 Desc. 40 ft. over gentle W. slope.
47.20	Small wash, drains NW.
63.10	Crest of low ledges, bears irregularly N. and S., desc. 100 ft. over ledgy W. slope.
75.00	Base of ledges, desc. 10 ft. over gentle W. slope.
79.68	The cor. of secs. 14, 15, 22 and 23. Land, rolling and broken. Soil, sand and exposed sandstone. Timber, none. Undergrowth, shadscale and bunch grass.
	N. 0° 25' W., bet. secs. 14 and 15. Over rolling sandy desert land, asc. 30 ft. along gentle W. slope.
12.70	Gravel road, bears NE. and SW.; asc. 80 ft. over S. slope of bluff.
22.60	Crest of bluff, bears W. and SE.; thence over gravelly bench.
27.50	Gravel road, bears W. and curves SE.

Dependent Resurvey, T. 28 S., R. 11 E.

CHAINS	
40.68	Point for the ¼ sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of original corner. Set an iron post, 36 ins. long, 1 in. diam., 28 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R11E ¼ S15 | S14 1963 Continue over gravelly bench.
48.00	S. crest small hollow, bears NE. and SW., desc. 55 ft. over NW. slope into hollow.
52.00	Hollow, drains NE., 8 chs. dist., thence N.; asc. 60 ft. over SE. slope of hollow.
56.50	Low spur, slopes NE., desc. 120 ft. over broken NW. slope.
68.50	Bottom small draw, drains NW., asc. 30 ft. along broken W. slope.
81.36	The cor. of secs. 10, 11, 14 and 15, determined longitudinally by proportionate measurement, and on line with property line fences to the west. This fence was verified by property owners as marking the original sec. line. At the cor. point Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T28S R11E S10 | S11 S15 | S14 1963 Raise a mound of stone 3 ft. base, 2½ ft. high W. of corner. Cor. is situated 1 ch. N. of old gravel pit. Land, broken and rolling bench. Soil, gravelly. Timber, none. Undergrowth, shadscale and bunch grass.
	From the cor. of secs. 11, 12, 13 and 14. S. 89° 37' W., bet. secs. 11 and 14. Over sandy rolling bench land, desc. 20 ft. over gentle W. slope.
29.60	Crest of steeper descent, bears N. and S., desc. 40 ft. over W. slope.
33.40	Gully, drains NW.

Dependent Resurvey, T. 28 S., R. 11 E.

CHAINS	
40.24	The ¼ sec. cor. of secs. 11 and 14, mkd. by a conglomerate stone, 3x8x16 ins., plainly mkd. ¼. At the cor. point Set an iron post, 36 ins. long, 1 in. diam., 28 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R11E ¼ S11/S14 1964 Deposit original stone alongside and N. of the iron post.
	S. 89° 53' W., beginning new measurement. Desc. 80 ft. over W. slope, across rolling gravel hills.
32.70	Bladed road, bears N. and S., asc. 30 ft. over gravel hills.
40.34	The cor. of secs. 10, 11, 14 and 15. Land, rolling and broken hills. Soil, sand on bench, gravel on hills. Timber, none. Undergrowth, shadscale and bunch grass.
	N. 0° 12' W., bet. secs. 10 and 11. Over broken desert land, desc. 60 ft. along W. slope, across series of gravel hills.
14.10	Gravel road, bears NW. and SE., asc. 25 ft. along broken W. slope.
24.50	Low spur, slopes W., desc. 30 ft. over N. slope.
26.60	Dirt road, bears NE. and SW.
28.80	Fence, bears W., N. and NE., leave broken land, enter farm land; along north and south fence line.
40.02	The ¼ sec. cor. of secs. 10 and 11, determined by a fence cor., fence bears W. and S. from corner. At the corner point Set an iron post, 36 ins. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd. T28S R11E ¼ S10|S11 1963

Dependent Resurvey, T. 28 S., R. 11 E.

N. [illegible] 34' W., beginning new measurement.

Continue over farming land.

[illegible] Beginning of fence, bears N. and S.

[illegible] Crest of low terrace, bears NW. and SE., leave farm land, thence over gravelly rise.

[illegible] The point for cor. of secs. 2, 3, 10 and 11, determined by a fence corner, fences bearing E., W. and S., and is accepted as the best available evidence of the original cor. position.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R11E
S3 | S2
S10 | S11
1963

Land, broken N. and S. portions; farmland central portion.
Soil, sandy clay, gravelly N. and S. portions.
Timber, none.
Undergrowth, blackbrush and bunch grass.

From the cor. of secs. 1, 2, 11 and 12.

N. [illegible] 38' W., bet. secs. 2 and 11.

Over broken desert land, asc. 80 ft. over ledgy NE. slope along Dirty Devil River bottom.

[illegible] Rim of bench, bears NW. and SE., leave river bottom, thence along gentle N. slope of bench.

[illegible] Small hollow, drains N.

[illegible] Small hollow, drains N.

26.[illegible] Wash, 2 ft. deep, 20 lks. wide, drains N. 20° E.

[illegible] Wash, 2 ft. deep, 15 lks. wide, drains N.

[illegible] The ¼ sec. cor. of secs. 2 and 11, mkd. by a sandstone, 6x10x16 ins., plainly mkd. ¼.

At the cor. point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R11E
¼ S2
S11
1964

Deposit original stone alongside and N. of iron post.

Dependent Resurvey, T. 28 S., R. 11 E.

CHAINS	
	N. 89° 49' W., beginning new measurement.
	Desc. 35 ft. over broken NW. slope.
11.60	Small hollow, drains N. 20° W., asc. 25 ft. over E. slope of hollow.
25.78	Power line, 2 strand, bears N. and S., desc. 40 ft. over NW. slope.
37.90	Bulldozed road, bears N. and S., thence over gravel bench.
37.16	Fence, bears N. 87° E. and W., thence over gravelly bench.
40.22	The corner of secs. 2, 3, 10 and 11.
	Land, rolling and broken. Soil, gravelly sand, and exposed sandstone. Timber, none. Undergrowth, blackbrush and bunch grass.
	N. 0° 11' W., bet. secs. 2 and 3.
	Over desert land, across small gravelly bench.
4.10	N. crest gravelly bench, bears E. and SW., thence over bottom land of Dirty Devil River, across small pasture.
12.20	Fence, bears NE. and SW., thence through heavy growth of willows.
30.00	Right bank of Dirty Devil River, bears NE. and SW., thence across stream bed, drainage and small water flow NE.
38.67	Point for the ¼ sec. cor. of secs. 2 and 3, at proportionate distance; falls in Dirty Devil River and cannot be monumented.
40.00	Left bank of river, bears NE. and SW., asc. 10 ft. over irregular S. slope.
42.17	Point selected for the witness ¼ sec. cor. of secs. 2 and 3.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R11E ¼ S3 | S2 WC 1963
	Asc. 115 ft. over irregular S. slope.
54.90	Power line, 2 strand, bears N. 30° W. and S. 30° E.
69.70	Slope changes, asc. 35 ft. over series of small spurs sloping W., 2 chs. to highway, which bears N. and SW.

Dependent Resurvey, T. 28 S., R. 11 E.

CHAINS

77.63 Point for the cor. of secs. 2 and 3, on the N. bdy. of the Tp., falls on steep W. slope of highway cut. No evidence of original monument could be found.

Set 1 in. T-iron stake, 24 ins. long, 18 ins. in the ground, on steep W. slope of cut. Impractical to monument with regulation iron post.

From this stake the cor. of secs. 34 and 35, T. 27 S., R. 11 E., bears N. 89° 15' E., 1.92 chs. dist., (record course and distance) monumented with an iron post set, mkd. and witnessed as described in the official record of the resurvey of the S. bdy. of T. 27 S., R. 11 E., in 1934.

Land, broken and level river bottom.
Soil, sand and gravel.
Timber, none.
Undergrowth, willows on river bottom.

From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp.

N. 0° 12' E., bet. secs. 33 and 34.

Over broken desert land, desc. 35 ft. over NW. slope.

9.10 Small draw, drains NW., asc. 15 ft. along broken W. slope

25.50 Wash, 2 ft. deep, 20 lks. wide, drains W., asc. 115 ft. over irregular S. slope.

31.90 Crest low ridge, bears NE. and SW., desc. 30 ft. over NW. slope.

40.51 Point for the ¼ sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R11E
¼
S33 | S34
1963

Desc. N. slope on small ridge.

41.20 Crest of steep descent, bears irregularly E. and NW., desc. 325 ft. over ledgy N. slope.

63.20 Base of steep descent, bears E. and NW., thence along gentle E. slope.

81.02 Point for the cor. of secs. 27, 28, 33 and 34, at proportionate distance; there is no remaining evidence of original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

Dependent Resurvey, T. 28 S., R. 11 E.

CHAINS

T28S	R11E
S28	S27
S33	S34

1963

Land, broken and rolling.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, shadscale and bunch grass.

From the cor. of secs. 26, 27, 34 and 35.

N. 88° 56' W., bet. secs. 27 and 34.

Over broken desert land on S. end of mesa.

1.10 W. rim of mesa, bears NW. and SE., desc. 100 ft. over SW. slope.

9.00 Base of rim, bears NW. and SE., desc. 40 ft. over gentle W. slope.

40.64 Point for the ¼ sec. cor. of secs. 27 and 34, at proportionate distance; there is no remaining evidence of original corner.

Set an iron post, 36 ins. long, 1 in. diam., 28 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R11E
¼ S27
S34

1964

Asc. 15 ft. over gentle E. slope.

43.00 Graded dirt road, Hanksville to Sawmill Basin, bears N. 30° W., and S. 30° E.

53.50 Crest of low rise, bears irregularly N. and S., desc. 45 ft. over gentle W. slope.

81.28 The cor. of secs. 27, 28, 33 and 34.

Land, broken and rolling.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, shadscale and bunch grass.

N. 0° 03' E., bet. secs. 27 and 28.

Over rolling sandy desert land, draining N.

40.51 Point for the ¼ sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of original corner.

Set an iron post, 36 ins. long, 1 in. diam., 28 ins. in the ground, in a collar of stone, with brass cap mkd.

Dependent Resurvey, T. 28 S., R. 11 E.

CHAINS

T28S R11E
¼
S28 | S27
1963

Continue over rolling desert land.

81.02 The cor. of secs. 21, 22, 27 and 28, mkd. by a sandstone, 4x14x20 ins., plainly mkd. 2 notches on S., 3 notches on E. face.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R11E
S21 | S22
S28 | S27
1963

Deposit original stone alongside and N. of the iron post.

Land, rolling.
Soil, sand.
Timber, none.
Undergrowth, blackbrush and scattered bunch grass.

From the cor. of secs. 22, 23, 26 and 27.

N. 88° 41' W., bet. secs. 22 and 27.

Over sandy rolling desert land, desc. 60 ft. over NW. slope.

25.60 Small terrace, 10 ft. high, bears irregularly N. and S.

40.42 Point for the ¼ sec. cor. of secs. 22 and 27, at proportionate distance; there is no remaining evidence of original corner.

Set an iron post, 36 ins. long, 1 in. diam., 28 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R11E
¼ S22
S27
1964

Desc. 70 ft. over sandy NW. slope.

45.50 Small wash, drains N. 10° W.

76.60 Gravel road, Hanksville to Sawmill Basin, bears N. 25° W. and S. 25° E.

80.84 The cor. of secs. 21, 22, 27 and 28.

Land, rolling.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, shadscale and scattered bunch grass.

Dependent Resurvey, T. 28 S., R. 11 E.

CHAINS

N. 1°.27' E., bet. secs. 21 and 22.

Over rolling desert land.

8.40 Graded road, Hanksville to Sawmill Basin, bears N. 25° W., and S. 25° E.; asc. 10 ft. over SW. slope.

17.00 Base of steep ascent, bears irregularly E. and NW., asc. 115 ft. over ledgy S. slope.

21.60 Top of broken hill, bears irregularly N. and S.; thence along broken W. slope on top of hill.

38.20 Slope changes, desc. 20 ft. over NW. slope.

39.26 Point for the ¼ sec. cor. of secs. 21 and 22, at proportionate distance; there is no remaining evidence of original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T28S R11E
¼
S21 | S22
1963

Raise a mound of stone 3 ft. base, 2½ ft. high, W. of corner.

Desc. 85 ft. over broken NW. slope.

45.90 Base of steep descent, bears NE. and SW., desc. 40 ft. over NW. slope.

78.52 The point for cor. of secs. 15, 16, 21 and 22, monumented with a steel peg, firmly set in ground. This corner was identified by interested property owners as a perpetuation of the original corner, and has been accepted by the town of Hanksville. It is accepted as the best available evidence of the original cor. position.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R11E
S16 | S15
S21 | S22
1963

Raise a mound of stone 3 ft. base, 2½ ft. high, W. of corner.

Corner is situated in forks of road, ¼ mile SE. of Hanksville, Utah.

Land, broken and rolling.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, shadscale and scattered bunch grass.

Dependent Resurvey, T. 28 S., R. 11 E.

CHAINS

From the cor. of secs. 14, 15, 22 and 23.

S. 89° 54' W., bet. secs. 15 and 22.

Over rolling sandy desert land; desc. 65 ft. over gentle W. slope.

16.00 Graded dirt road, bears NE. and SW.

35.80 Small wash, drains N.; asc. 10 ft. along gentle N. slope.

39.96 Point for the ¼ sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of original corner.

Set an iron post, 36 ins. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

T28S R11E
¼ S15/S22

1964

Raise a mound of stone 2½ ft. base, 2½ ft. high, N. of corner.

Asc. 15 ft. along N. slope.

56.00 Spur on N. side of small hill, slopes N., desc. 25 ft. along N. slope.

61.90 Fence, net wire, bears N. and W., thence along fence.

76.00 Leave fence line, fence bears to NW.

77.70 Road, Hanksville to Hite, bears NW. and SE.

79.92 The cor. of secs. 15, 16, 21 and 22.

Land, rolling.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, shadscale and scattered bunch grass.

N. 1° 24' W., bet. secs. 15 and 16.

Over nearly level desert land, draining N.

2.50 Gravel road, Hanksville to Hite, bears SE. and NW., 2 chs to junction, with road bearing N. and S.; thence along E. side of hard surface road.

13.00 Commence crossing hard surface part of N. and S. highway, along its E. side.

28.00 Leave hard surface of highway, thence along W. side of N. and S. highway.

40.89 Point for the ¼ sec. cor. of secs. 15 and 16, at proportionate distance, falls in wash and cannot be perpetuated. This position will also be obliterated by highway work in near future. There is no evidence of original corner.

Set 1 in. T-iron stake, 24 ins. long, 18 ins. in the grou d

Dependent Resu . . . T. 28 S., R. 11 E.

CHAINS	
41.20	Wash, 4 ft. deep, 60 lks. wide, drains N. 10° E.
42.89	Point selected for the witness ¼ sec. cor. of secs. 15 and 16.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T28S R11E ¼ S16 | S15 W C 1964
	Thence across posted private property and Fremont River. By triangulation.
66.00	Right bank Fremont River, bears NE. and SW., thence across river.
71.00	Left bank of river, bears NE. and SW.; end triangulation; asc. 10 ft. over gentle S. slope, across rolling sand.
81.78	Point for the cor. of secs. 9, 10, 15 and 16, determined longitudinally by proportionate measurement, and latitudinally in line with fence to the E., and was verified by property owners as having been constructed along original section line.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T28S | R11E S9 | S10 S16 | S15 1963
	Place a boulder 2½x2x2 ft., alongside and W. of iron post.
	Land, level valley and river bottom. Soil, sand and sandy clay. Timber, none. Undergrowth, none.
	From the cor. of secs. 10, 11, 14 and 15.
	N. 89° 46' W., bet. secs. 10 and 15.
	Over broken desert land, asc. 25 ft. over E. slope of small hollow.
1.00	Crest of low gravel hill, desc. 90 ft. over broken W. slope.
16.80	Hard surface highway, U-24, bears N. and S., leave hills.
17.20	Fence, bears N., S. and W., thence along fence, enter farm land.

Dependent Resurvey, T. 28 S., R. 11 E.

CHAINS	
38.90	Cor. of fences, bearing E. and N.
40.64	Point for the ¼ sec. cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T28S R11E ¼ S10/S15 1964
	Cor. falls in small grove of cottonwood tress.
	Cont. over farm land.
60.30	Four strand barbed wire fence bears N. and S.
61.00	Enter Fremont River bottom, bears N. and S.
63.20	Right bank of river channel, bears N. and S.; river flows irregularly N.
65.70	Left bank of river, thence over river bottom land, through willows.
74.10	Leave river bottom, asc. 20 ft. over small sand dunes.
81.28	The cor. of secs. 9, 10, 15 and 16.
	Land, broken E. portion, farm land central portion, river bottom W. portion. Soil, gravelly, sandy on farm land and river bottom. Timber, few cottonwood in river bottom. Undergrowth, none.
	N. 0° 14' E., bet. secs. 9 and 10.
	Over sandy bottom land, asc. 15 ft. over S. slope.
11.40	Fence, net wire, bears E. and W.
12.90	Graded gravel road, bears E. and W.; also base of bluff, bears NW. and E.; asc. 100 ft. over broken SW. slope.
21.50	Crest of bluff, bears irregularly NW. and SE.; thence over broken sandstone formation on high bench, draining SW.
40.32	Point for the ¼ sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., on solid sandstone, over an X, and in a mound of stone 4 ft. base, 28 ins. high, with brass cap mkd.
	T28S R11E ¼ S9 | S10 1963

CHAINS

Cont. over barren irregular sandstone.

41.20 Gully, 15 ft. deep, drains S. 70° W., asc. 85 ft. over SW. slope.

56.50 Top of small black-topped hill, about 5 chs. diam.; desc. 70 ft. over N. slope of hill.

60.90 Rim, facing N. and NW., bears NE. and SW., desc. 100 ft. over ledgy N. slope.

64.30 Base of rim, desc. 35 ft. over N. slope in small cove in Muddy Creek Canyon.

80.64 Point for the cor. of secs. 3, 4, 9 and 10, at proportionate distance; there is no remaining evidence of original corner.

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R11E

S4	S3
S9	S10

1963

Land, broken.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, none.

From the cor. of secs. 2, 3, 10 and 11.

N. 89° 15' W., bet. secs. 3 and 10.

Over rolling desert land, along E. and W. fence line.

4.55 Fence, bears N., S. and E., enter Fremont River bottom and dense willows.

13.70 Right bank of river channel, bears N. and S., thence across river, draining N.

19.40 Left bank of river, bears irregularly N. and S.; asc. 15 ft. over sandy NE. slope; leave river bottom.

30.10 Hard surface highway, U-24, bears N. 10° W. and S. 10° E.; asc. 20 ft. over gentle NE. slope.

30.80 Fence, net wire, parallel to highway.

40.39 The ¼ sec. cor. of secs. 3 and 10, mkd. by a sandstone, 3x8x12 ins., plainly mkd. ¼.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R11E

¼ S3 / S10

1964

Dependent Resurvey, T. 28 S., R. 11 E.

CHAINS	
	Deposit original stone alongside the iron post.
	N. 89° 53' W., beginning new measurement.
	Asc. 20 ft. over broken NE. slope.
7.90	Small wash, drains NE.; asc. 15 ft. over NE. slope.
17.00	Base of steep ascent bears irregularly N. and S.; asc. 170 ft. over ledgy E. slope.
22.70	Crest of low ridge, bears irregularly N. and S.; desc. 145 ft. over ledgy W. slope.
31.30	Base same ridge, bears irregularly N. and SW.; desc. 35 ft. over NW. slope in small cove.
40.32	The corner of secs. 3, 4, 9 and 10.
	Land, rolling and river bottom E. portion, broken W. portion. Soil, sand and exposed sandstone. Timber, none. Undergrowth, none.
	N. 0° 01' E., bet. secs. 3 and 4.
	Over rolling land in small cove of Muddy Creek Canyon, desc. 20 ft. over NW. slope.
7.30	Small wash, drains NE.; asc. 45 ft. over SE. slope of low point.
16.90	S. rim of low point, bears NE. and SW.; thence over broken top of point.
31.70	N. rim same point, bears W. and SE.; desc. 80 ft. over ledge facing N.
32.00	Base same rim, thence over level creek bottom land, through willows.
40.32	Point for the ¼ sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in collar of stone, with brass cap mkd. T28S R11E ¼ S4 | S3 1963
	Continue over bottom land, through willows.
42.60	Right bank Muddy Creek, bears E. and W.; thence across river flowing E.
45.10	Left bank of creek, bears E. and W., thence over bottom land, through willows.
60.10	Base of steep ascent, bears irregularly E. and W.; asc. 150 ft. over ledgy S. slope.

Dependent Resurvey, T. 28 S., R. 11 E.

CHAINS

63.40 Crest of canyon rim, bears irregularly E. and SW.; asc. 20 ft. over rolling bench.

80.23 The cor. of secs. 3 and 4, on the N. bdy. of the Tp., mkd by an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record of the resurvey of the S. bdy. of T. 27 S., R. 11 E., in 1934.

Land, broken except for creek bottom.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, willows in canyon bottom.

From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp.

N. 0° 38' E., bet. secs. 32 and 33.

Over broken desert land, draining NE.; desc. 50 ft.

6.40 Small wash, drains NE.

30.80 Small hollow, 20 ft. deep, drains NE.

40.16 Point for the ¼ sec. cor. of secs. 32 and 33, at proportionate dist.; there is no remaining evidence of original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone 3½ ft. base, to top, with brass cap mkd.

T28S R11E
¼
S32 | S33
1963

Desc. 110 ft. over irregular N. slope.

58.00 Leave broken land, desc. 10 ft. over gentle N. slope.

80.32 Point for the cor. of secs. 28, 29, 32 and 33, at proportionate distance; there is no remaining evidence of original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T28S R11E
S29 | S28
S32 | S33
1963

Raise a mound of stone 3 ft. base, 2½ ft. high, W. of corner.

Land, broken and rolling.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, shadscale and bunch grass.

Dependent Resurvey, T. 28 S., R. 11 E.

CHAINS

From the cor. of secs. 27, 28, 33 and 34.

S. 89° 57' W., bet. secs. 28 and 33.

Over rolling desert land, asc. gentle E. slope.

8.00 Base of steep ascent, bears irregularly N. and S.; asc. 105 ft. over broken E. slope.

15.30 Crest of steep ascent, bears irregularly N. and S.; thence over broken top of low ridge.

27.40 Crest of steep descent, bears irregularly N. and S.; desc. 70 ft. over broken W. slope.

33.00 Base of descent, bears irregularly N. and S.; desc. 10 ft. over gentle W. slope.

40.53 Point for the ¼ sec. cor. of secs. 28 and 33, at proportionate distance; there is no remaining evidence of original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T28S R11E
¼ S28/S33
1964

Raise a mound of stone 2½ ft. base, 2 ft. high N. of corner.

Desc. 10 ft. over gentle W. slope.

52.00 Small wash, drains N. 10° E.; asc. 15 ft. along gentle N. slope.

81.06 The cor. of secs. 28, 29, 32 and 33.

Land, rolling and broken.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, shadscale and bunch grass.

N. 0° 14' E., bet. secs. 28 and 29.

Over rolling desert land, desc. 15 ft. over gentle N. slope.

18.50 Enter Bull Creek, drains irregularly N. from S. 10° W.

28.60 Leave creek, drains NE. from S.; also base of steep ascent, bears NE. and SW.; asc. 105 ft. over steep SE. slope of spur.

34.20 Spur, projects E.; desc. 100 ft. over N. slope.

40.00 Hollow, drains NE.; asc. 10 ft. over S. slope.

40.16 Point for the ¼ sec. cor. of secs. 28 and 29, at proportionate distance; there is no remaining evidence of original corner.

Dependent Resurvey, T. 28 S., R. 11 E.

CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T28S R11E
¼
S29 | S28
1963

Raise a mound of stone, 2½ ft. base, 2½ ft. high, W. of corner.

Asc. 95 ft. over S. slope, over irregular gypsum and clay breaks.

48.00 Spur, projects E.; desc. 80 ft. over N. slope.

54.90 Hollow, drains E.; asc. 130 ft. along E. face of ledgy clay and gypsum breaks.

80.32 The cor. of secs. 20, 21, 28 and 29, mkd. by a sandstone, 4x8x14 ins., plainly mkd. 2 notches on S. and 4 notches on E. face. This position falls on small gypsum ledge and cannot be safely monumented with regulation iron post.

At the cor. point

Set 1 in. T-iron peg, 24 ins. long, 18 ins. in the ground, from which its witness corner bears N. 0° 55'E., 0.50 chs. distance, hereinafter described. Reset the original stone alongside the iron peg.

Land, rolling and broken.
Soil, sand, clay and gypsum.
Timber, none.
Undergrowth, none.

From the cor. of secs. 21, 22, 27 and 28.

S. 89° 27' W., bet. secs. 21 and 28.

Over flat land, draining N.

13.10 Wash, 3 ft. deep, 20 lks. wide, drains N.

19.20 Wash, 4 ft. deep, 30 lks. wide, drains N.

24.00 Bull Creek, dry in channel, 10 ft. deep, 50 lks. wide, drains N. 10° E.

40.39 Point for the ¼ sec. cor. of secs. 21 and 28, at proportionate distance; there is no remaining evidence of original corner.

Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R11E
¼ S21/S28
1964

CHAINS

54.00 Base of steep ascent, bears irregularly N. and S.; asc. 160 ft. over broken ledgy E. slope, by triangulation with topography scaled from U.S.G.S. sheets.

80.78 True point for the cor. of secs. 20, 21, 28 and 29 (from which its witness corner bears N. 0° 55' E., 0.50 chs. dist.)

Land, rolling and broken.
Soil, sand, clay and gypsum.
Timber, none.
Undergrowth, none.

N. 0° 55' E., bet. secs. 20 and 21.

Over broken desert land, asc. 45 ft. over clay and gypsum formation.

0.50 Point selected for the witness cor. of secs. 20, 21, 28 and 29.

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T28S R11E
S20 | S21
S29 | S28
W C
1963

12.70 Top of ascent, desc. 80 ft. along broken E. slope.

25.35 Gully, 10 ft. deep, 50 lks. wide, drains E.

40.47 Point for the ¼ sec. cor. of secs. 20 and 21, at proportionate distance; there is no remaining evidence of original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T28S R11E
¼
S20 | S21
1963

Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of corner.

Thence along broken and irregular ledgy E. slope, by triangulation.

58.00 High spur, slopes NE.; end triangulation; desc. 10 ft. over top of spur.

61.10 Crest of rim., bears irregularly E. and W.; desc. 200 ft. over broken N. slope and ledges facing N.

78.60 Small hollow, drains NW.

Dependent Resurvey; T. 28 S., R. 11 E.

CHAINS	
80.94	Point for the cor. of secs. 16, 17, 20 and 21, at proportionate distance; there is no remaining evidence of original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R11E S17 | S16 S20 | S21 1963 Land, broken. Soil, gravelly with clay and gypsum breaks. Timber, none. Undergrowth, none.
	From the cor. of secs. 15, 16, 21 and 22. N. 88° 49' W., bet. secs. 16 and 21. Over nearly level bottom land, draining N.
.90	Graded gravel road, Hanksville to Sawmill Basin, bears N. and S.
2.90	Bull Creek, 10 ft. deep, 50 lks. wide, drains N.
16.40	Dirt landing strip, bears NW. and SE.
30.70	Spur, slopes N., desc. 70 ft. over W. slope.
33.30	Small hollow, drains N., asc. 75 ft. over E. slope.
36.10	Spur, slopes N., desc. 30 ft. over W. slope.
40.75	Point for the ¼ sec. cor. of secs. 16 and 21, at proportionate distance; there is no remaining evidence of original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R11E ¼ S16 / S21 1964 Desc. 105 ft. over W. slope.
49.20	Base of hills, bears irregularly N. and S.; thence across small valley.
59.00	Base of hills, bears irregularly N. and S.; asc. 100 ft. over broken E. slope.
66.10	Top of ascent on broken hills; desc. 60 ft. over W. slope.
73.90	Small draw, drains N.; asc. 25 ft. over E. slope.

Dependent Resurvey, T. 28 S., R. 11 E.

CHAINS

76.60 mall spur, slopes N.; desc. 20 ft. over W. slope, over eries of small hills.

81.50 he cor. of secs. 16, 17, 20 and 21.

Land, rolling and broken.
Soil, sand and clay, gravelly in hills.
Timber, none.
Undergrowth, none.

N. 1° 00' W., bet. secs. 16 and 17.

Over broken land, desc. 30 ft. over irregular gravel hills, draining NW.

6.00 Graded gravel road, Caineville to Hanksville, bears NE. and SW. on curve; asc. 30 ft. over SE. slope of gravel hill.

11.00 Top of small gravel hill; desc. 40 ft. over NW. slope of hill

16.50 Base of hill, bears NE. and SW.; thence over Fremont River bottom, through willows.

21.00 Power line, bears NW. and SE.

40.47 Point for the ¼ sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of original corner.

Set an iron post, 36 ins. long, 1 in. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R11E
¼
S17 | S16
1964

Set steel fence post beside corner.

Continue over river bottom.

44.00 Right bank of present river channel, bears E. and curves SW.; thence across river, flowing E.

48.60 Left bank same river, 10 ft. high, bears E. and curves SW. asc. gentle S. slope, over farm land.

53.20 Leave farms.

55.40 Small irrigation canal, drains E. irregularly.

58.25 Four strand barbed wire fence, bears E. and W.

69.50 Graded dirt road, bears NE. and SW.; asc. 15 ft. over gentle S. slope.

79.30 Base of small gypsum hill, bears E. and W.; asc. 60 ft. over S. slope.

80.94 Point for the cor. of secs. 8, 9, 16 and 17, at proportionate distance; there is no remaining evidence of original corner.

Dependent Resurvey, T. 28 S., R. 11 E.

CHAINS	
	Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R11E S8 | S9 S17 | S16 1963 Cor. falls on steep S. slope of small gypsum hill. Land, broken and rolling. Soil, gravelly S. portion, sandy N. portion. Timber, none. Undergrowth, none.
	From the cor. of secs. 9, 10, 15 and 16. N. 89° 27' W., bet. secs. 9 and 16. Over sandy desert land, covered with greasewood; asc. 20 ft. over gentle SE. slope.
20.50	Base of bluff, bears NE. and SW.; asc. 50 ft. over ledges facing SE.
21.10	Crest same bluff, bears NE. and SW.; asc. 70 ft. along broken S. slope on bench.
38.50	Small cove, drains S.; asc. 25 ft. over E. slope of cove.
40.49	Point for the ¼ sec. cor. of secs. 9 and 16, at proportionate distance; there is no remaining evidence of original corner. Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R11E ¼ S9 S16 1964 Asc. 20 ft. over E. slope of small cove, draining S.
41.40	Top of ascent on bench, bears N. and S.; desc. 60 ft. over broken W. slope of bench.
54.60	Leave broken land, desc. 30 ft. over sandy W. slope of cove.
71.50	Graded gravel road, bears NE. and SW.; cont. over sandy cove.
74.50	Base of clay spur, bears NE. and SW.; asc. 50 ft. over E. slope of spur.
75.90	Spur, projects S. about 3 chs. to end, desc. 10 ft. along S. slope of clay hill.
79.30	Small spur, projects S., 2 chs. to end, desc. along S. slope of hill.
80.98	The corner of secs. 8, 9, 16 and 17.

Dependent Resurvey, T. 28 S., R. 11 E.

CHAINS

Land, rolling and broken.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, none.

N. 0° 30' E., bet. secs. 8 and 9.

Over broken land, asc. 200 ft., by triangulation, over irregular bluff of sandstone and clay ledges facing S.

20.30 Crest of bluff, bears irregularly W. and SW.; asc. 30 ft. over broken bench, draining SW.

40.47 The ¼ sec. cor. of secs.8 and 9, mkd. by a sandstone, 4x12x12 ins., plainly mkd. ¼.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R11E
¼
S8 | S9
1963

Deposit original stone alongside and N. of the iron post.

N. 0° 01' E., beginning new measurement.

Asc. 50 ft. over broken bench, draining SW.

7.60 Wash, 1 ft. deep, 20 lks. wide, drains SW.

32.50 Small wash, drains SW.

40.13 The cor. of secs. 4, 5, 8 and 9, mkd. by a sandstone, 3x10x12 ins., plainly mkd. 5 notches on S. and 4 notches on E. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R11E
S5 | S4
S8 | S9
1964

Deposit original stone alongside and N. of the iron post.

Land, broken.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, none.

Dependent Resurvey, T. 28 S., R. 11 E.

CHAINS	
	From the cor. of secs. 3, 4, 9 and 10.
	N. 89° 08' W., bet. secs. 4 and 9.
	Over broken desert land, desc. 20 ft. over W. slope in cove.
5.50	Small wash, drains NE.; asc. 20 ft. over E. slope in cove.
9.00	Base of bluff, bears irregularly N. and S.; asc. 100 ft. over E. slope.
16.50	Crest same bluff, bears irregularly N. and S.; asc. 40 ft. over broken top of bench.
34.10	Wash, 3 ft. deep, 20 lks. wide, drains N., 2.00 chs. to head of small hollow.
40.15	The ¼ sec. cor. of secs. 4 and 9, mkd. by a sandstone, 2x6x16 ins., plainly mkd. ¼.
	At the cor. point
	Set an iron post, 36 ins. long, 1 in. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.
	T28S R11E ¼ S4/S9 1964
	Deposit original stone alongside and N. of the iron post.
	N. 89° 46' W., beginning new measurement.
	Continue over broken bench.
16.00	Base of steep ascent and ledges facing E.; asc. 150 ft. over E. slope.
28.00	Crest of steep ascent and ledges; thence over rolling sandy bench.
40.95	The cor. of secs. 4, 5, 8 and 9.
	Land, broken. Soil, sand and exposed sandstone. Timber, none. Undergrowth, none.
	N. 0° 26' E., bet. secs. 4 and 5.
	Over sandy rolling bench land, desc. 45 ft.
18.00	Crest of steep descent, bears NW. and SE.; desc. 200 ft. over steep NE. slope and ledges facing NE. By triangulation with topography scaled from U.S.G.S. quadrangle sheets.

Dependent Resurvey, T. 28 S., R. 11 E.

CHAINS	
27.00	Base of ledgy descent, bears irregularly NW. and SE.; thence over broken bench.
38.97	Point selected for the witness ¼ sec. cor. of secs. 4 and 5. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R11E ¼ W C S5 S4 1964 Witness cor. falls on crest of ledgy NE. slope.
39.97	Point for the ¼ sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of original corner, falls on inaccessible ledges facing NE. and cannot be monumented. Desc. 320 ft. over broken ledges facing NE. into Muddy Creek Canyon. By triangulation with topography scaled from U.S.G.S. quadrangle sheets.
75.00	Base of ledgy NE. slope, also right bank of Muddy Creek, bears irregularly SE. and N., thence across creek bed.
79.74	True point for the cor. of secs. 4 and 5, on the N. bdy. of the Tp., determined as being at a position midpoint bet. the N. ¼ sec. cors. of secs. 4 and 5, falls in creek bed and cannot be perpetuated. Note: the resurvey of this boundary, in 1934, calls for a witness corner S. 89° 49' E., 2.58 chs. distance. This witness corner has been removed by creek erosion and cannot be safely remonumented. The 1934 cor. of secs. 32 and 33, T. 27 S., R. 11 E., has also been washed away. The point selected for the witness cor. of secs. 4 and 5, on the N. bdy. of the Tp., bears S. 89° 49' E., 4.00 chs. distance; situated 1 ch. E. of left bank of Muddy Creek, course SE. from N. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T27S R11E W S32 C S5 S4 T28S R11E 1964 From the true point for this cor. the N. ¼ sec. cor. of sec. 4, bears S. 89° 49' E., 40.22 chs. dist., mkd. by an iron post 1 in. diam., set, mkd. and witnessed as described in the official record of the 1934 resurvey. From the same point the N. ¼ sec. cor. of sec. 5, bears N. 89° 49' W., 40.22 chs. dist., mkd. by an iron post 1 in. diam., set, mkd. and witnessed as described in the official record of the 1934 resurvey.

Dependent Resurvey, T. 28 S., R. 11 E.

CHAINS	
	Land, broken. Soil, sand and exposed sandstone. Timber, none. Undergrowth, willows on creek bottom.
	From the cor. of secs. 5, 6, 31 and 32, on the S. bdy.
	N. 0° 56' E., bet. secs. 31 and 32.
	Over rolling sandy desert land, asc. 80 ft. along gentle E. slope.
31.30	N. end rocky knoll, desc. 100 ft. over N. slope of knoll.
35.40	Base same knoll, bears E. and W.; thence over rolling sandy land.
40.48	The ¼ sec. cor. of secs. 31 and 32, mkd. by a granite stone, 2x8x16 ins., plainly mkd. ¼. Note: original record describes this as a sandstone.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 5 ins. in the ground, in a mound of stone, 4 ft. base, 22 ins. high, with brass cap mkd. T28S R11E ¼ S31 | S32 1963
	Bury original stone alongside and N. of the iron post.
	N. 0° 10' W., beginning new measurement.
	Continue over sandy desert land.
7.90	Small wash, drains W.
40.04	The cor. of secs. 29, 30, 31 and 32, mkd. with a sandstone, 2x6x12 ins., plainly mkd. 1 notch on S., and 5 notches on E. face.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R11E S30 | S29 S31 | S32 1963
	Bury original stone alongside and N. of the Iron post.
	Land, rolling. Soil, sand and exposed sandstone. Timber, none. Undergrowth, shadscale and bunch grass.

Dependent Resurvey, T. 28 S., R. 11 E.

CHAINS	
	From the cor. of secs. 28, 29, 32 and 33.
	N. 89° 24' W., bet. secs. 29 and 32.
	Over rolling desert land, asc. 20 ft. over gentle NE. slope.
5.00	Wash, a dry channel of Bull Creek, 3 ft. deep, 20 lks. wide, drains NE.
16.00	Main channel of Bull Creek, dry, drains NE., also base steep ascent bears N. 20° E. and S., asc. 100 ft. over ledgy E. slope of bluff.
34.00	Crest of bluff, bears N. 20° E. and S., asc. 40 ft. over gentle E. slope of bench.
40.84	The ¼ sec. cor. of secs. 29 and 32, mkd. by a sandstone, 4x12x16 ins., plainly mkd. ¼.
	At the corner point
	Set an iron post, 36 ins. long, 1 in. diam., 24 ins. in the ground, with brass cap mkd.
	T28S R11E ¼ S29/S32 1964
	Bury original stone alongside and N. of the iron post.
	Raise a mound of stone 3 ft. base, 2½ ft. high, N. of corner.
	N. 89° 20' W., beginning new measurement.
	Desc. 30 ft. over rolling desert land.
41.02	The cor. of secs. 29, 30, 31 and 32.
	Land, broken and rolling. Soil, sand and exposed sandstone. Timber, none. Undergrowth, shadscale and bunch grass.
	N. 89° 45' W., bet. secs. 30 and 31.
	Over broken desert land draining NW., desc. 70 ft.
18.40	Wash, 1 ft. deep, 10 lks. wide, drains NW.
23.60	Wash, 1 ft. deep, 30 lks. wide, drains irregularly N.
38.00	Crest low rim, bears NE. and SW.; desc. 30 ft. over NW. slope of small hollow.
40.42	Point for the ¼ sec. cor. of secs. 30 and 31, at proportionate distance; there is no remaining evidence of original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

Dependent Resurvey, T. 28 S., R. 11 E.

CHAINS

T28S R11E
¼ S30/S31
1963

Desc. NW. slope.

41.10 Sandy wash, 2 ft. deep, 30 lks. wide, drains irregularly N.; asc. 60 ft. over E. slope.

49.10 Crest of low rim of ledges, bears NE. and S.; thence over irregular formation South Pinto Hills.

78.93 Find no trace of witness cor. of secs. 25, 30, 31 and 36, reported to have been established 1.50 chs. E. of true point for cor.

80.43 True point for the cor. of secs. 25, 30, 31 and 36, on the W. bdy., from which its witness corner on W. bdy. of the Tp., bears S. 0° 06' W., 1.00 ch. distance, mkd. by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of the E. bdy. of T. 28 S., R. 10 E.

Land, broken.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, shadscale and bunch grass.

From the cor. of secs. 29, 30, 31 and 32.

N. 0° 15' W., bet. secs. 29 and 30.

Over rolling sandy desert land, draining W.

6.90 Small wash, drains W.

40.25 The ¼ sec. cor. of secs. 29 and 30, mkd. by a sandstone, 3x12x12 ins., plainly mkd. ¼.

At the corner point.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R11E
¼
S30|S29
1963

Bury original stone alongside and N. of the iron post.

N. 0° 01' E., beginning new measurement.

Continue over sandy land, draining W.

14.30 Crest of low rocky rise, 5.00 chs. long. General area known as South Pinto Hills.

Dependent Resurvey, T. 28 S., R. 11 E.

CHAINS	
21.70	Low rim, bears W. and curves NE., desc. 60 ft. over broken land, draining W.
34.70	Rim of small canyon, bears NE. and W., desc. 115 ft. over ledgy N. slope, into small cove.
40.75	The cor. of secs. 19, 20, 29 and 30, mkd. by a gypsum stone, in small mound of stones; mks. on stone weathered away. Note: original record describes this as a sandstone. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T28S R11E S19 | S20 S30 | S29 1963 Raise a mound of stone, 2½ ft. base, 2 ft.high, W. of corner. Land, rolling and broken. Soil, sand and exposed sandstone. Timber, none. Undergrowth, shadscale and bunch grass.
	From the true point for the cor. of secs. 20, 21, 28 and 29 (from which its witness cor. bears N. 0° 55' E., 0.50 chs. distance). N. 88° 56' W., bet. secs. 20 and 29. Over rolling sandy bench land; asc. 50 ft. over gentle E. slope.
22.20	Top of ascent on bench, bears N. and S.; desc. 20 ft. over gentle W. slope.
41.19	Point for the ¼ sec. cor. of secs. 20 and 29, at proportionate distance; there is no remaining evidence of original corner. Set an iron post, 36 ins. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd. T28S R11E ¼ S20/S29 1964 Raise a mound of stone 3 ft. base, 2 ft. high, N. of corner. Desc. 30 ft. over sandy W. slope.
61.40	Enter area of broken and barren sandstone; desc. 75 ft. over W. slope.
79.90	Crest of rim, bears irregularly N. and S.; desc. 125 ft. over ledgy W. slope.

R T. 2 S. 1 E.

CHAINS	
82.38	The cor. of secs. 19, 20, 29 and 30. Land, rolling and broken. Soil, sand and exposed sandstone. Timber, none. Undergrowth, blackbrush and bunch grass.
	West, bet. secs. 19 and 30. Over broken land in bottom of hollow; desc. 15 ft. over W. slope.
7.60	Sandy wash, 2 ft. deep, 20 lks. wide, drains NE.
14.60	Base of steep ascent, bears NE. and SW.; asc. 115 ft. over steep SE. slope and ledges facing SE.
17.90	Crest of ledges on W. side of hollow, bears NE. and SW.; asc. 30 ft. over irregular formation of South Pinto Hills.
39.93	Point for the ¼ sec. cor. of secs. 19 and 30, at proportionate distance; there is no remaining evidence of original corner. Set an iron post, 36 ins. long, 1 in. diam., 28 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R11E ¼ S19 / S30 1964 Asc. 15 ft. over broken bench.
53.06	The original witness cor. of secs. 19, 24, 25 and 30.
62.70	Small wash, drains S.
67.30	Base of clay hills, bears irregularly N. and S.; asc. 125 ft. over E. slope.
75.10	Crest of hills, desc. 40 ft. over broken W. slope.
80.06	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., mkd. by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the concurrent resurvey of the E. bdy. of T. 28 S., R. 10 E. Land, broken. Soil, sand and exposed sandstone, few clay hills. Timber, none. Undergrowth, blackbrush and bunch grass.
	From the cor. of secs. 19, 20, 29 and 30. N. 0° 50' W., bet. secs. 19 and 20. Over broken land of E. breaks of Sand Wash.
1.50	Base of ledges in small cove, bears W. and curves SE.; asc. 100 ft. over ledges facing S.

Dependent Resurvey T. 28 S. R. 11 E.

CHAINS	
4.20	Point, projects W. 4 chs. dist.; desc. 65 ft. along broken rim facing W.
17.00	Point, projects W. 3 chs. dist.; asc. 20 ft. along broken rim.
21.10	Point, projects W. 4 chs. dist.; desc. 75 ft. over steep N. slope and ledges facing N.
23.10	Base of rim, bears E. and W.; thence over sandy cove.
40.47	The ¼ sec. cor. of secs. 19 and 20, mkd. by a limestone in small mound of stones, faintly mkd. ¼. Note: original record describes this as a gypsum rock.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R11E ¼ S19 | S20 1963
	Deposit original stone alongside and N. of the iron post.
	Cor. falls 50 lks. S. of shale and gypsum ledge facing S.

	N. 3° 54' E., beginning new measurement.
	Over sandy bottom of cove.
.50	Base of shale and gypsum ledge, bears E. and W.; asc. 105 ft.
1.00	Point, projects W. 2.00 chs. dist.; desc. 115 ft. over ledges facing N.
1.30	Base same ledges, bears W. and curves NE.; desc. gentle W. slope in Sand Wash.
10.00	Sand Wash, 2 ft. deep, 20 lks. wide, drains NE.; desc. along gentle E. slope.
22.40	E. end of point, desc. 20 ft. over gentle N. slope in Fremont River bottom, through heavy growth of greasewood.
39.57	Point for the cor. of secs. 17, 18, 19 and 20, at proportionate distance; there is no remaining evidence of original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in collar of stone, with brass cap mkd. T28S R11E S18 | S17 S19 | S20 1964
	Set steel fence post alongside the iron post.

Dependent Resurvey, T. 28 S., R. 11 E.

CHAINS

Land, broken and rolling river bottom.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, greasewood in river bottom.

From the cor. of secs. 16, 17, 20 and 21.

N. 89° 40' W., bet. secs. 17 and 20.

Over broken gravel hills; desc. 55 ft. over W. slope.

5.30 Small hollow, drains N.; asc. 50 ft. over E. slope.

7.30 Gravel spur, projects N.; desc. 35 ft. over W. slope.

12.00 Gravel road, U-24, bears NE. and SW.

12.30 Four strand barbed wire fence, bears NE. and SW.; thence over farmland and corrals.

29.00 Four strand barbed wire fence, bears NW. and SE.; leave farms.

38.00 Same road, bears NW. and SE.; also base of steep ascent; asc. 55 ft. over irregular E. slope of red hills.

40.79 Point for the ¼ sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of original corner.

Set an iron post, 36 ins. long, 2½ ins. diam., 28 ins. in the ground, in a collar of stone, with brass cap mkd.

T28S R11E
¼ S17/S20
1964

Asc. 200 ft. over steep E. slope and ledges facing E.

53.20 Top of ridge, bears irregularly N. and S.; desc. 250 ft. over broken W. slope.

64.50 Sand Wash, 4 ft. deep, 20 lks. wide, drains N.; also base of hills; thence over Fremont River bottom land.

81.58 The cor. of secs. 17, 18, 19 and 20.

Land, rolling and broken.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, shadscale with greasewood in river bottom.

N. 89° 51' W., bet. secs. 18 and 19.

Over slightly rolling land of Fremont River bottom.

16.10 Base of steep ascent, bears N. and S. irregularly; asc. 125 ft. over steep E. slope and ledges facing E.

Dependent Resurvey, T. 28 S., R. 11 E.

CHAINS	
23.10	Crest of ascent, rim about 30 ft. high, bears irregularl N. and S.; desc. 10 ft. over sandy bench, draining N.
39.60	Wash, 6 ft. deep, 20 lks. wide, drains N.; continue over sandy bench.
40.64	Point for the ¼ sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of original corner. Set an iron post, 30 ins. long, 2½ ins. diam., on sandstone, over an X, in a mound of stone 3 ft. base, to top, with brass cap mkd. T28S R11E ¼ S18/S19 1964 Desc. 20 ft. over sandy bench, draining N.
82.21	The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp. mkd. by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in record of concurrent resurvey of the E. bdy. of T. 28 S., R. 10 E. Land, mostly rolling. Soil, sand and exposed sandstone. Timber, none. Undergrowth, shadscale on bench, greasewood in river bottom.
	From the cor. of secs. 17, 18, 19 and 20. N. 1° 07' W., bet. secs. 17 and 18. Over Fremont River bottom, through greasewood.
4.00	Enter dense growth of tamarac and willows.
8.00	Right bank Fremont River, bears irregularly E. and W.; thence across river, by triangulation, with topography scaled from U.S.G.S. sheets.
18.00	Left bank same river, bears irregularly E. and W.; asc. gentle S. slope, leave river bottom.
29.00	Gravel road, U-24, bears E. and curves SW.
36.00	Power line, bears irregularly E. and W.; also base of steep ascent, bears NE. and SW.; asc. 130 ft. over ledgy S. slope.
37.50	Crest of ledges, bears irregularly NE. and SW.; asc. 10 ft. over broken sandstone bench.
39.49	The ¼ sec. cor. of secs. 17 and 18, mkd. with a granite stone 5x5x16 ins. in mound of stones, no visible mks. Topography fits calls of original survey. It is accepted as the best remaining evidence of the original survey.

Dependent Resurvey, T. 28 S., R. 11 E.

CHAINS

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., on solid sandstone, over an X, in a mound of stone 4 ft. base, 25 ins. high, with brass cap mkd.

T28S R11E
¼
S18 | S17
1963

Deposit original stone in mound alongside and N. of iron post.

N. 0° 03' E., beginning new measurement.

Asc. 30 ft. over broken sandstone.

12.80 Leave barren sandstone; asc. 65 ft. over rolling S. slope.

40.33 The cor. of secs. 7, 8, 17 and 18, mkd. by a granite stone 6x10x14 ins., plainly mkd. 4 notches on S. and 5 notches on E. face. Original record describes this as a sandstone.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground, in a mound of stone 4 ft. base, to top, with brass cap mkd.

T28S R11E
S7 | S8
S18 | S17
1963

Deposit original stone in mound alongside and N. of iron post.

Cor. falls on low rise.

Land, rolling and broken ledges.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, blackbrush and bunch grass.

From the cor. of secs. 8, 9, 16 and 17.

S. 89° 29' W., bet. secs. 8 and 17.

Over broken desert land, by triangulation, with topography scaled from U.S.G.S. sheets; desc. 30 ft. over clay hill.

1.50 Base of hill, thence across draw.

5.00 Draw, drains SE.

7.00 Base of ledgy bluff, bears N. and SW.; asc. about 200 ft. along impassable clay and shale ledges facing generally S.

Dependent Resurvey, T. 28 S., R. 11 E.

CHAINS	
31.00	Spur, slopes S., desc. 200 ft. over ledges facing W.; thence across small cove, which drains S.
39.60	Point selected for the witness ¼ sec. cor. of secs. 8 and 17.
	Set an iron post, 36 ins. long, 1 in. diam., 18 ins. in the ground, in a mound of stone 3 ft. base, to top, with brass cap mkd.
	T28S R11E ¼ W C ← S8/S17 1964
	Witness cor. falls at base of shale ledge facing E.
	Asc. 140 ft. over irregular ledges facing SE.
40.44	Point for the ¼ sec. cor. of secs. 8 and 17, at proportionate distance; there is no remaining evidence of original corner, falls on inaccessible ledges, and cannot be monumented.
47.00	Crest of ledges, bears irregularly NE. and SW.; asc. 30 ft. over broken bench land, draining S., across sand and exposed sandstone.
79.40	Crest of low rise, bears N. and S.; desc. 10 ft. over gentle SW. slope.
80.88	The cor. of secs. 7, 8, 17 and 18.
	Land, broken. Soil, sand and exposed sandstone. Timber, none. Undergrowth, blackbrush and bunch grass on bench.
	N. 89° 09' W., bet. secs. 7 and 18.
	Over rolling sandy land; desc. 80 ft. over gentle SW. slope.
16.50	Small wash, drains SW.
31.10	Wash, 4 ft. deep, 30 lks. wide, drains S. 30° W.; asc. 25 ft. over gentle E. slope.
40.54	The ¼ sec. cor. of secs. 7 and 18, mkd. by a sandstone, 6x10x12 ins., plainly mkd. ¼.
	At the corner point
	Set an iron post, 36 ins. long, 1 in. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T28S R11E ¼ S7/S18 1964

Dependent Resurvey, T. 28 S., R. 11 E.

CHAINS	
	Bury original stone alongside and N. of the iron post.
	N. 88° 38' W., beginning new measurement.
	Asc. 5 ft. over sandy E. slope.
3.60	Crest small rise, bears N. and S.; desc. 105 ft. over gentle W. slope.
32.50	Wash, 3 ft. deep, 30 lks. wide, drains SW.; desc. 30 ft. over broken SW. slope.
40.85	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., mkd. by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of the E. bdy. of T. 28 S., R. 10 E.
	Land, rolling bench. Soil, sand and exposed sandstone. Timber, none. Undergrowth, shadscale and bunch grass.
	From the cor. of secs. 7, 8, 17 and 18.
	N. 0° 09' E., bet. secs.7 and 8.
	Over rolling sandy bench land, known as North Pinto Hills; desc. 20 ft. along gentle W. slope.
11.50	Wash, 1 ft. deep, 10 lks. wide, drains W.; asc. 25 ft. over SW. slope.
20.40	E. end of rise about 7.00 chs. long, covered with black boulders; desc. 25 ft. over gentle NW. slope.
39.00	Wash, 2 ft. deep, 10 ft. wide, drains S. 70° W.; asc. gentle SW. slope.
40.88	The ¼ sec. cor. of secs. 7 and 8, mkd. by a sandstone, 4x9x14 ins., plainly mkd. ¼.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., on solid sandstone, over an X, and in a mound of stone 4 ft. base, 28 ins. high, with brass cap mkd. T28S R11E ¼ S7 | S8 1963
	Deposit original stone alongside and N. of the iron post.
	N. 0° 08' W., beginning new measurement.
	Asc. 75 ft. over SW. slope, covered with black boulders.
16.00	Knoll, 8 chs. diam., covered with black boulders; desc. 50 ft. over N. slope.

Dependent Resurvey, T. 28 S., R. 11 E.

CHAINS	
21.60	Small wash, drains S. 70° W., thence over sandy land, draining SW.
36.60	Wash, 1 ft. deep, 10 lks. wide, drains S. 70° W., asc. 10 ft. over sandy S. slope.
40.84	The cor. of secs. 5, 6, 7 and 8, mkd. by a sandstone, 6x8x12 ins., plainly mkd., 5 notches on S. and E. face. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T28S R11E S6 | S5 S7 | S8 1963 Bury original stone alongside and N. of the iron post. Raise a mound of stone 3 ft. base, 2 ft. high, W. of corner. From this corner U.S.G.S. triangulation station "Pinto", located in latitude 38° 23' 57.956" N. and longitude 110° 45' 17.800" W., bears N. 58° 55' W., 30.15 chs. distance. Land, rolling to broken. Soil, sand. Timber, none. Undergrowth, shadscale and bunch grass.
	From the cor. of secs. 4, 5, 8 and 9. N. 89° 42' W., bet. secs. 5 and 8. Over rolling bench land known as North Pinto Hills; desc. 80 ft. over gentle NW. slope.
5.20	Dirt road, bears NW. and SE.
40.60	Point for the ¼ sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of original corner. Set an iron post, 30 ins. long, 2½ ins. diam., on solid sandstone, over an X, and in a mound of stone 4 ft. base, to top, with brass cap mkd. T28S R11E ¼ S5/S8 1964 Desc. 35 ft. over sandy bench land, draining SW.
41.00	Wash, 2 ft. deep, 10 lks. wide, drains SW.
75.90	Wash, 2 ft. deep, 20 lks. wide, drains SW.

Dependent Resurvey, T. 28 S., R. 11 E.

CHAINS	
81.20	The cor. of secs. 5, 6, 7 and 8. Land, rolling bench. Soil, sand and exposed sandstone. Timber, none. Undergrowth, shadscale and bunch grass.
	S. 89° 47' W., bet. secs. 6 and 7. Over sandy bench land; asc. 65 ft. over SE. slope.
17.00	Wash, 2 ft. deep, 10 lks. wide, drains SW.
32.90	Rise, bears N. and S.; desc. 25 ft. over SW. slope.
40.56	The ¼ sec. cor. of secs. 6 and 7, mkd. by a sandstone, 2x14x16 ins., plainly mkd. ¼. At the cor. point Set an iron post, 36 ins. long, 1 in. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd. T28S R11E ¼ S6/S7 1964 Deposit original stone alongside and N. of the iron post.
	S. 89° 35' W., beginning new measurement. Desc. 105 ft. over sandy W. slope.
32.30	Wash, 2 ft. deep, 20 lks. wide, drains SW.; asc. 20 ft. over SE. slope.
39.91	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., mkd. by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of the E. bdy. of T. 28 S., R. 10 E. Land, rolling to slightly broken. Soil, sand and exposed sandstone. Timber, none. Undergrowth, shadscale and bunch grass.
	From the cor. of secs. 5, 6, 7 and 8. N. 0° 15' E., bet. secs. 5 and 6. Over rolling sandy land; asc. 50 ft. over gentle S. slope.
31.60	Top of ascent, bears E. and W.; desc. 25 ft. over sandy NE. slope.
40.44	The ¼ sec. cor. of secs. 5 and 6, mkd. with a sandstone, 4x8x16 ins., plainly mkd. ¼.

Dependent Resurvey, T. 28 S., R. 11 E.

CHAINS	
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T28S R11E ¼ S6 | S5 1963
	Bury original stone alongside and N. of the iron post.
	Raise a mound of stone 3 ft. base, 2 ft. high, W. of corner.
	N. 1° 59' E., beginning new measurement.
	Desc. 30 ft. over sandy NE. slope.
1.70	Crest of ledgy descent, bears irregularly E. and W.; desc. 200 ft. over ledgy N. slope, into canyon.
15.60	Wash, in canyon bottom, drains E.; asc. 55 ft. over broken S. slope.
23.20	Spur, projects SE.; asc. 20 ft. over series of small clay spurs sloping SE.
28.20	Spur, projects SE., 3 chs. to end; desc. 50 ft. over N. slope.
31.50	Gully, drains E., 3.00 chs. thence S.; asc. 50 ft. over S. slope of red clay hills.
38.80	Wash, 1 ft. deep, 10 lks. wide, drains E., 2.00 chs.; thence S.
38.95	The cor. of secs. 5 and 6, on the N. bdy. of the Tp., mkd. by an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record of the resurvey of the S. bdy. of T. 27 S., R. 11 E., in 1934.
	Land, rolling S. portion, broken N. portion. Soil, sand S. portion, sand and clay hills N. portion. Timber, none. Undergrowth, shadscale and bunch grass.

General Description

T. 28 S., R. 11 E., is bisected by the Fremont River, which enters the township on the W. bdy. of sec. 18, and flows NE. to a junction with Muddy Creek, in sec. 3, forming the Dirty Devil River, which flows SE., leaving the township on the E. bdy. of sec. 12.

The south portion of the township consists mainly of sandy desert land, broken by several bluffs and washes, which drain N. to the Fremont River. The north portion of the township is mostly broken and the main drainage is south to the Fremont River.

Dependent Resurvey, T. 28 S., R. 11 E.

CHAINS

There are numerous roads within the township, the main one being state highway U-24, which enters the township on the W. bdy. of sec. 18, and bears eastward across the township to Hanksville, Utah, in sec. 16, thence northward to NE. cor. of sec. 2.

State highway 95 runs southeasterly from Hanksville in sec. 16, toward Hite, Utah, leaving the township on the S. bdy. of sec. 36.

The town of Hanksville is located in sec. 16, and a few farms are located in portions of secs. 10, 15 and 17.

The elevations over the township vary from about 4250 to 4700 ft. above sea level.

Blank

Page

orm 4–680
1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
LaVern Griffin	Transitman
Ashley D. Allen	Notekeeper
Merlin J. Robinson	Chainman
Gail E. [illegible]lds	Fl[illegible]
Charles Crabb	Cornerman

CERTIFICATE OF SURVEY

I, Craig P. Sylvester, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 21 day of August, 1963, I have dependently resurveyed the south boundary and subdivision of Township 28 South, Range 11 East,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

January 18, 1965
(Date)

Craig P. Sylvester
~~(Cadastral Surveyor)~~
(Supervisory Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date FEB 17 1966

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the dependent resurvey of the south boundary and subdivision of Township 28 South, Range 11 East

executed by Craig P. Sylvester, Cadastral Surveyor, Supervisory

having been critically examined and found correct, are hereby approved.

APR 14 1966
(Date)

(Chief, Division of Engineering)

~~CERTIFICATE OF TRANSCRIPT~~

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in

, is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)

Blank

Page

Blank

Page

Form 4-679
(January 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF THE

SOUTH BOUNDARY,

THE GUIDE MERIDIAN ALONG THE EAST BOUNDARY,

AND

[illegible]

[illegible]

TOWNSHIP 10 NORTH, RANGE 6 EAST

Of the SALT LAKE Meridian,

In the State of UTAH.

EXECUTED BY

[illegible] B [illegible] A [illegible] [illegible] SURVEYOR

[illegible] special instructions dated NOVEMBER 7, 19 63, which provided for the surveys included under Group Number 469, approved NOVEMBER 7, 1963, and assignment instructions dated JUNE 5, 19 64.

Survey commenced JUNE 15, 19 64

Survey completed [illegible]

270

DEPT. OF THE INTERIOR
BUR OF LAND MGMT

1966 MAY 31 AM 10 00 .0

RECEIVED
STATE & LAND OFFICE
SALT LAKE CITY, UTAH

INDEX DIAGRAM

Township 10 NORTH, Range 6 EAST,

6 65	66 5 64	52 4 51	42 3 41	32 2 31	22 1 7 22
7 63	63 8 62	50 9 49	40 10 39	30 11 29	21 12 6 20
18 60	61 17 59	48 16 47	38 15 38	28 14 28	19 13 5 18
19 57	58 20 56	46 21 45	36 22 36	27 23 26	17 24 4 17
30 54	55 29 54	44 28 44	35 27 34	25 26 24	16 25 3 15
31 13	53 32 12	43 33 11	33 34 10	23 35 9	14 36 2 8

Township 10 North, Range 6 East, Salt Lake Meridian, Utah

CHAINS

The Guide Meridian along the E. bdy. of the Tp. was surveyed by Julian Bausman in 1869. The south boundary was surveyed by T. C. Bailey in 1875. The west boundary was surveyed by J. G. Burrill in 1875, and dependently resurveyed by Elliot Bird in 1938. The north boundary was surveyed by J. G. Burrill in 1875, and concurrently resurveyed by Glen B. Hatch. The subdivisional lines were surveyed by Bailey and Burrill in 1875.

The following field notes are those of the dependent resurvey of the south and east boundaries and the subdivisional lines of Township 10 North, Range 6 East.

Before restoring the corners, the lines of the original survey were retraced and diligent search made for any evidence of the original corners, or other calls of the original field note record.

The rules of proportionate measurement were applied to ascertain the position of the lost corners, but not until exhausting every reasonable possibility of finding direct evidence for the control of each particular corner.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and special instructions dated November 7, 1963.

All lines of this survey were run by direct method where the lines were accessible; lines inaccessible were run by triangulation or traverse methods. Distances to topography on lines run by traverse or triangulation are approximate. The details of such triangulations or traverses have been thoroughly checked and verified, and in order to simplify the record the diagrams and reductions are omitted from these field notes.

The direction of the lines of this survey were determined by reference to true meridians established on line by elongation observations on Polaris and altitude observations on the sun. The lines were carried forward by sustained angulation being supplemented by other altitude observations on the sun taken throughout the progress of the survey.

The geographic position for the southeast corner of the township is at latitude 41° 33' 11.83" N. and longitude 111° 12' 24.57" W., which is the mean of section line ties to U.S.G.S. triangulation station "Limestone", at latitude 41° 35' 59.62" N. and longitude 111° 13' 44.85" W., located N. 34° 24' 26" W., 21.245 chs. dist. from the corner of sections 13, 14, 23 and 24, Township 10 North, Range 6 East, and U.S.G.S. triangulation station "South Twin", at latitude 41° 44' 07.82" N. and longitude 111° 20' 00.53" W., located S. 89° 16' 12" W., 49.36 chs. dist. from the ¼ section corner of sections 31 and 36, Township 12 North, Ranges 5 and 6 East.

The magnetic declination was read at several stations throughout the township and the average of these readings was found to be 15° 15' East.

Dependent Resurvey of the Guide Meridian, E. Bdy.
T. 10 N., R. 6 E.

CHAINS

Dependent Resurvey of the Guide Meridian, along the E. Bdy., T. 10 N., R. 6 E.

Reestablishment of the Survey Executed by Julian Bausman in 1869.

Note: The original field notes of the E. bdys. of Tps. 5 to 12 N., R. 6 E., designate the line as a "Guide Meridian". Various plats of adjoining townships have designated this line as "Guide Meridian North". The U. S. Dept. of Interior, General Land Office map of Utah dated 1943, designated it as "Guide Meridian East". We use the original designation, "Guide Meridian".

Beginning at the original cor. of Tps. 9 and 10 N., Rs. 6 and 7 E., monumented with a sandstone, 20x10x6 ins., firmly set and properly mkd.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., on solid rock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T10N
R6E R7E

S36 | S31
S1 | S6
T9N
1964

Bury the old stone cor., at base of mound, alongside the iron post.

Thence N. 0° 03' W., bet. secs. 31 and 36.

Over rolling mountainous land through dense sagebrush undergrowth. Asc. 10 ft. over SW. slope.

4.20 Spur, slopes SE.; desc. 20 ft. over NE. slope.

18.20 Draw, drains SE.; asc. 65 ft. over SE. slope.

34.60 Spur, slopes E.; desc. 10 ft. over gentle N. slope.

40.19 The orig. ¼ sec. cor. of secs. 31 and 36, monumented with a sandstone, 15x9x6 ins., firmly set and properly mkd.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd.

T10N
R6E R7E
¼
S36 | S31
1964

Bury original stone cor. alongside iron post.

Dependent Resurvey of the Guide Meridian, E. Bdy.
T. 10 N., R. 6 E.

CHAINS	
	N. 2° 08' W., beginning new measurement.
	Desc. 5 ft. over gentle N. slope.
2.90	Small wash, drains N. 80° E.; asc. 30 ft. over gentle SE. slope.
15.25	Spur, slopes N. 75° E.; desc. 75 ft. over N. slope.
33.40	Wash, in draw, drains E.; asc. 35 ft. over S. slope.
40.76	The orig. cor. of secs. 25, 30, 31 and 36, monumented with a broken sandstone, 24x7x4 ins., firmly set and properly mkd.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd.
	T10N R6E R7E S25 | S30 S36 | S31 1964
	Bury original stone cor. alongside iron post.
	Land, rolling mountainous. Soil, rocky clay loam. No timber. Undergrowth, dense sagebrush.
	N. 0° 06' W., bet. secs. 25 and 30.
	Over rolling mountain land through dense sagebrush undergrowth. Asc. 25 ft. over S. slope.
6.65	Ridge, bears E. and W.; desc. 130 ft. over N. slope.
29.95	Draw, drains N. 80° E.; asc. 165 ft. over S. slope.
40.82	Point for the ¼ sec. cor. of secs. 25 and 30 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T10N R6E R7E ¼ S25 | S30 1964
	Thence over nearly level land.
62.60	Desc. 50 ft. over NE. slope.
69.10	Draw, drains irregularly E.; asc. 85 ft. over SW. slope.

Dependent Resurvey of the Guide Meridian, E. Bdy., T. 10 N., R. 6 E.

CHAINS	
81.64	The orig. cor. of secs. 19, 24, 25 and 30, monumented with a sandstone, 20x16x8 ins., firmly set and properly mkd. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 5 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd. T10N R6E R7E S24 | S19 S25 | S30 1964 Bury original stone cor. alongside iron post. Land, rolling mountainous. Soil, clay loam. No timber. Undergrowth, dense sagebrush.
	N. 0° 17' E., bet. secs. 19 and 24. Over rolling mountainous land through dense sagebrush undergrowth. Asc. 100 ft. over SW. slope.
5.00	Spur, slopes E.; desc. 130 ft. over NE. slope.
17.50	Trail road, bears E. and W.
24.93	Fence, bears about N. 85° E. and S. 85° W. about 20.00 chs., thence NW.
32.15	Draw, drains E.; asc. 115 ft. over SE. slope.
39.83	Point for the ¼ sec. cor. of secs. 19 and 24 at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd. T10N R6E R7E ¼ S24 | S19 1964 Asc. 15 ft. over SE. slope.
41.00	Spur, slopes NE.; desc. 125 ft. over NW. slope.
74.25	Draw, drains irregularly E.; asc. 90 ft. over S. slope.
79.66	Point for the cor. of secs. 13, 18, 19 and 24 at proportionate dist.; there is no remaining evidence of the original cor.

Dependent Resurvey of the Guide Meridian, E. Bdy., T. 10 N., R. 6 E.

CHAINS	
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with glass at base, and brass cap mkd. T10N R6E R7E S13 | S18 S24 | S19 1964 Raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor. Land, rolling mountainous. Soil, rocky clay loam. No timber. Undergrowth, dense sagebrush.
	N. 0° 17' E., bet. secs. 13 and 18. Over rolling land through sagebrush undergrowth. Asc. 10 ft. over S. slope.
8.20	Spur, slopes E.; desc. 45 ft. over N. slope.
19.65	Small draw, drains E.; asc. 20 ft. over S. slope.
20.50	Fence, bears about N. 80° E. and S. 80° W. about 40.00 chs., thence curves S.
22.20	Small spur, slopes E.; desc. 20 ft. over N. slope.
28.70	Draw, drains E.; asc. 30 ft. over S. slope.
33.40	Spur, slopes E.; desc. 10 ft. over gentle NE. slope.
39.83	Point for the ¼ sec. cor. of secs. 13 and 18 at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd. T10N R6E R7E ¼ S13 | S18 1964 Desc. 25 ft. over NE. slope.
45.40	Small draw, drains E.; asc. 10 ft. over SE. slope.
46.90	Small spur, slopes E.; desc. 35 ft. over NW. slope.
60.65	Draw, drains NE.; asc. 20 ft. over SE. slope.
73.95	Trail road, on ridge, bears NE. and SW.; desc. 40 ft. over NW. slope.

Dependent Resurvey of the Guide Meridian, E. Bdy., T. 10 N., R. 6 E.

CHAINS	
79.30	Draw, drains NE.
79.66	The orig. cor. of secs. 7, 12, 13 and 18, monumented with a sandstone, 18x10x6 ins., firmly set and properly mkd. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd. T10N R6E R7E S12 | S7 S13 | S18 1964 Bury original stone cor. alongside iron post. Land, rolling mountainous. Soil, clay loam. No timber. Undergrowth, sagebrush and bunch grass.
	N. 1° 00' W., bet. secs. 7 and 12. Over rolling land through sagebrush and bunch grass undergrowth. Asc. 40 ft. over NE. slope.
11.60	Spur, slopes NE.; desc. 115 ft. over NW. slope.
25.80	Wash, 10 lks. wide, 2 ft. deep, drains NE.; enter reseeded area; desc. 20 ft. over NE. slope.
39.59	The orig. ¼ sec. cor. of secs. 7 and 12, monumented with a sandstone, 16x8x6 ins., firmly set and properly mkd. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd. T10N R6E R7E ¼ S12 | S7 1964 No accessories available. Bury original stone cor. alongside iron post. Cor. is situated in E. and W. fence line.
	N. 1° 24' E., beginning new measurement. Desc. 135 ft. over gently rolling NE. slope through reseeded area.

Dependent Resurvey of the Guide Meridian, E. Bdy., T. 10 N., R. 6 E.

CHAINS	
40.50	Improved gravel road, bears W. and curves NE.
40.68	The orig. cor. of secs. 1, 6, 7 and 12, monumented with a limestone, 12x8x6 ins., firmly set and properly mkd. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with glass at base, and brass cap mkd. T10N R6E R7E S1 | S6 S12 | S7 1964 Bury original stone cor. alongside iron post. Cor. is situated 3 lks. S. of fence, bears irregularly W., and curves NE. Land, rolling. Soil, clay loam. No timber. Undergrowth, sagebrush and bunch grass.
	N. 0° 08' E., bet. secs. 1 and 6. Over gently rolling land through sagebrush undergrowth. Desc. 50 ft. over gentle NE. slope.
0.03	Fence, bears irregularly W. and curves NE.
9.20	Canal, 25 lks. wide, 3 ft. deep, flows irregularly E.
15.90	Enter cultivated land, bears E. and W.
26.50	Old house, bears W. 1.50 chs.dist.; enter meadow land.
39.78	Point for the ¼ sec. cor. of secs. 1 and 6 at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd. T10N R6E R7E ¼ S1 | S6 1964 Continue over meadow land; desc. 10 ft. over gentle NE. slope.
55.00	Enter dense willows, bears NE. and SW.

Dependent Resurvey of the Guide Meridian, E. Bdy., T. 10 N., R. 6 E.

CHAINS	
55.30	Big Creek, with stream of water, 4 lks. wide, 3 ins. deep, flows E., curving NE.
56.50	Leave dense willows; enter meadow land.
59.90	Old fence, bears E. and W.; continue over meadow land.
79.56	The cor. of Tps. 10 and 11 N., Rs. 6 and 7 E., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the 1964 field notes of T. 11 N., R. 6 E.
	Land, nearly level farm and meadow land. Soil, clay loam. No timber. Undergrowth, sagebrush, willows and meadow grass.

Dependent Resurvey of the South Boundary, T. 10 N., R. 6 E.

Reestablishment of the Survey Executed by T. C. Bailey in 1875

	From the cor. of Tps. 9 and 10 N., Rs. 6 and 7 E., hereinbefore described.
	S. 89° 52' W., bet. secs. 1 and 36.
	Over rolling mountainous land through sagebrush undergrowth. Desc. 60 ft. over SW. slope.
9.15	Draw, drains S.; asc. 60 ft. over SE. slope.
20.20	Spur, slopes S.; desc. 85 ft. over SW. slope.
33.90	Wash, drains S., thence over nearly level land.
40.96	Point for the ¼ sec. cor. of secs. 1 and 36 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd. T10N R6E ¼ S36 / S1 T9N 1964
	Cor. is situated about 1.50 chs. N. of road, bears irregularly E. and W.
45.15	Small draw, drains SE.; asc. 90 ft. over SE. slope.
72.45	Spur, slopes S., thence along S. slope.

Dependent Resurvey of the South Boundary, T. 10 N., R. 6 E.

CHAINS	
81.92	The orig. cor. of secs. 1, 2, 35 and 36, monumented with a sandstone, 18x8x4 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd. T10N R6E S35 | S36 S2 | S1 T9N 1964 Bury original stone cor. alongside iron post. Cor. is situated in fence line bearing about N. 28° 30' W. and S. 28° 30' E. Land, rolling mountainous. Soil, rocky clay loam. No timber. Undergrowth, sagebrush.
	N. 89° 43' W., bet. secs. 2 and 35. Over rolling mountainous land through dense sagebrush. Asc. 10 ft. over SE. slope.
1.30	Small spur, slopes SE.; desc. 35 ft. over W. slope.
3.25	Wash, 15 lks. wide, 4 ft. deep, drains S.; asc. 55 ft. over SE. slope.
14.50	Spur, slopes S.; desc. 45 ft. over W. slope.
17.60	Draw, drains S.; asc. 85 ft. over SE. slope.
32.25	Rocky spur, slopes S.; desc. 55 ft. over SW. slope.
38.88	Point for the ¼ sec. cor. of secs. 2 and 35 at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd. T10N R6E ¼ S 35 / S2 T9N 1964 Raise a mound of stone, 4 ft. base, 2½ ft. high, N. of cor. Desc. 15 ft. over gentle SW. slope.
46.40	Improved dirt road, bears N. 40° W. and curves S. 80° E.

CHAINS	
48.00	Wash, 30 lks. wide, 4 ft. deep, drains S. 80° E. from NW.; asc. 10 ft. over NE. slope.
58.20	Top of ascent, slopes NE.; desc. 15 ft. over NW. slope.
61.45	Wash, 20 lks. wide, 6 ft. deep, drains N. 75° E.; asc. 35 ft. along N. slope.
62.75	Trail road, bears N. 80° E. and S. 80° W.
77.76	The orig. cor. of secs. 2, 3, 34 and 35, monumented with a sandstone, 16x8x6 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and brass cap mkd. T10N R6E S34 | S35 S3 | S2 T9N 1964 Bury original stone cor. alongside iron post, and raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor. Land, rolling mountainous. Soil, clay loam. No timber. Undergrowth, dense sagebrush.
	N. 89° 51' W., bet. secs. 3 and 34. Over gently rolling land through dense sagebrush undergrowth. Asc. 40 ft. along N. slope.
10.00	Top of ascent, slopes N.; desc. 10 ft. along N. slope.
24.00	Bottom of descent, slopes N.; asc. 20 ft. along N. slope.
35.00	Wash, drains N. 80° E.; asc. 5 ft. over SE. slope.
40.36	The orig. ¼ sec. cor. of secs. 3 and 34, monumented with a sandstone, 14x8x5 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T10N R6E ¼ S34 S3 T9N 1964

Dependent Resurvey of the South Boundary, T. 10 N., R. 6 E.

CHAINS

Bury original stone alongside iron post, and raise a mound of stone, 3 ft. base, 1½ ft. high, N. of cor.

Cor. is situated in small ravine, about 4.50 chs. S. of sandstone outcropping.

N. 89° 38' W., beginning new measurement.

Asc. 10 ft. over SE. slope.

5.00 Wash, drains SE. curving NE.; asc. 110 ft. along N. slope

39.62 Point for the cor. of secs. 3, 4, 33 and 34 at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T10N R6E

S33	S34
S4	S3

T9N
1964

Raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of cor.

Land, gently rolling.
Soil, clay loam.
No timber.
Undergrowth, dense sagebrush.

N. 89° 38' W., bet. secs. 4 and 33.

Over rolling land through dense sagebrush undergrowth. Along N. slope.

14.50 Wash, drains N. 75° E.; asc. 90 ft. over SE. slope.

27.00 Spur, slopes S.; desc. 5 ft. along S. slope.

29.60 Head of draw, drains S.; asc. 65 ft. over SE. slope.

32.90 Spur, slopes S.; desc. 50 ft. over W. slope.

36.60 Draw, drains S. 15° E.; asc. 100 ft. over NE. slope.

39.62 Point for the ¼ sec. cor. of secs. 4 and 33 at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T10N R6E

	S33
¼	S4

T9N
1964

Dependent Resurvey of the South Boundary, T. 10 N., R. 6 E.

CHAINS	
	Asc. 70 ft. over NE. slope.
48.80	Spur, slopes S. 85° E.; asc. 130 ft. over SE. slope.
79.24	The orig. cor. of secs. 4, 5, 32 and 33, monumented with a sandstone, 22x18x3 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T10N R6E S32 | S33 S5 | S4 T9N 1964 Bury original stone cor. alongside iron post, and raise a mound of stone, 3 ft. base, 1½ ft. high, N. of cor. Land, mountainous. Soil, rocky clay loam. No timber. Undergrowth, dense sagebrush.
	S. 89° 14' W., bet. secs. 5 and 32. Over mountainous land through dense sagebrush and scattered service berry undergrowth. Asc. 45 ft. over SE. slope.
5.50	Ridge, bears NE. and SW., with trail road along top; desc. 100 ft. over NW. slope.
20.00	Small draw, drains N.; enter oak brush; asc. 20 ft. over NE. slope.
26.00	Small spur, slopes N.; desc. 25 ft. over NW. slope.
35.00	Draw, drains NE.; asc. 35 ft. over SE. slope. Leave oak brush.
39.00	Ridge, bears N. 15° E. and S. 15° W.
39.87	The orig. ¼ sec. cor. of secs. 5 and 32, monumented with a sandstone, 16x12x3 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T10N R6E ¼ S32 S5 T9N 1964

Dependent Resurvey of the South Boundary, T. 10 N., R. 6 E.

CHAINS	
	Bury original stone cor. alongside iron post, and raise a mound of stone, 3½ ft. base, 3 ft. high, N. of cor.
	N. 88° 23' W., beginning new measurement.
3.00	Trail road, bears N. 20° E. and S. 20° W.
3.20	Fence, parallel to road.
6.00	Desc. 190 ft. over NW. slope.
39.92	The orig. cor. of secs. 5, 6, 31 and 32, monumented with a sandstone, 18x16x6 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T10N R6E S31 | S32 S6 | S5 T9N 1964 Bury original stone cor. alongside iron post, and raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor. Land, mountainous. Soil, rocky clay loam. No timber. Undergrowth, sagebrush, service berry and oak brush.
	N. 89° 48' W., bet. secs. 6 and 31. Over mountainous land through sagebrush undergrowth. Desc. 5 ft. over NW. slope.
1.50	Spur, slopes N. 80° W.; desc. 75 ft. over SW. slope.
12.60	Draw, drains N. 60° W.; asc. 60 ft. over NE. slope.
25.00	Spur, slopes NW.; desc. 110 ft. over W. slope.
30.60	Draw, drains N.; asc. 150 ft. over NE. slope.
39.44	The orig. ¼ sec. cor. of secs. 6 and 31, monumented with a sandstone, 15x8x4 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd. T10N R6E ¼ S31 / S6 T9N 1964

CHAINS

Bury original stone cor. alongside iron post, and raise a mound of stone, 2½ ft. base, 1½ ft. high, N. of cor.

Cor. is situated on ridge, bears N. and S.

N. 89° 45' W., beginning new measurement.

Desc. 315 ft. over NW. slope.

16.00 Wash, 15 lks. wide, 6 ft. deep, in draw, drains NE.; asc 150 ft. over SE. slope.

39.43 The cor. of Tps. 9 and 10 N., Rs. 5 and 6 E., monumented with an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record.

Land, mountainous.
Soil, rocky clay loam.
No timber.
Undergrowth, sagebrush and scattered service berry.

Reestablishment of the Survey by
Bailey and Burrill in 1875

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp.

N. 0° 45' W., bet. secs. 35 and 36.

Over rolling mountainous land through dense sagebrush undergrowth. Asc. 25 ft. over S. slope.

6.00 Spur, slopes SE.; asc. 55 ft. over gentle SE. slope.

33.50 Small spur, slopes E.; desc. 15 ft. over N. slope.

38.00 Small wash, drains E.; asc. 10 ft. over SE. slope.

40.00 Point of spur, slopes E.; desc. 10 ft. over NE. slope.

40.97 The orig. ¼ sec. cor. of secs. 35 and 36, monumented with a sandstone, 18x8x3 ins., set and mkd. as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T10N R6E
¼
S35 | S36
1964

Bury original stone cor. alongside iron post, and raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor.

Dependent Resurvey of the Subdivision, T. 10 N., R. 6 E.

CHAINS	
	N. 3° 42' E., beginning new measurement.
	Desc. 5 ft. over NE. slope.
1.20	Draw, drains S. 65° E.; asc. 145 ft. over gentle SE. slope.
30.00	Ridge, bears N. 70° E. and S. 70° W.; desc. 110 ft. over NW. slope.
39.60	The orig. cor. of secs. 25, 26, 35 and 36, monumented with a sandstone, 12x8x8 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T10N R6E S26 | S25 S35 | S36 1964
	Bury original stone cor. alongside iron post, and raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor.
	Land, rolling mountainous. Soil, rocky clay loam. No timber. Undergrowth, dense sagebrush.
	From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp.
	S. 89° 36' W., bet. secs. 25 and 36.
	Over rolling mountainous land through dense sagebrush undergrowth. Asc. 5 ft. along S. slope.
4.50	Ridge, bears N. 80° E. and S. 80° W.; desc. 15 ft. over gentle NW. slope.
29.25	Draw, drains N. 30° E.; asc. 55 ft. over SE. slope.
39.25	Point for the ¼ sec. cor. of secs. 25 and 36 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T10N R6E ¼ S25 / S36 1964
	Asc. 45 ft. over SE. slope.
45.30	Ridge, bears NE. and SW.; desc. 80 ft. over NW. slope.

Dependent Resurvey of the Subdivision, T. 10 N., R. 6 E.

CHAINS	
60.50	Draw, drains N. 20° W.; asc. 80 ft. over NE. slope.
77.00	Spur, slopes N.; desc. 5 ft. over NW. slope.
78.50	The cor. of secs. 25, 26, 35 and 36.
	Land, rolling mountainous. Soil, rocky clay loam. No timber. Undergrowth, dense sagebrush.
	N. 0° 36' E., bet. secs. 25 and 26.
	Over mountainous land through dense sagebrush undergrowth. Desc. 80 ft. over NW. slope.
8.55	Draw, drains E.; asc. 75 ft. over S. slope.
15.00	Spur, slopes E.; desc. 100 ft. over N. slope.
31.65	Draw, drains E.; asc. 130 ft. over steep S. slope.
39.82	Point for the ¼ sec. cor. of secs. 25 and 26 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd. T10N R6E ¼ S26 | S25 1964
	Asc. 20 ft. over S. slope.
41.40	Point of spur, slopes S.; asc. 55 ft. over gentle SW. slope.
71.60	Ridge, bears NW. and S. 75° E.; desc. 15 ft. over gentle N. slope.
79.64	The orig. cor. of secs. 23, 24, 25 and 26, monumented with a sandstone, 16x10x6 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T10N R6E S23 | S24 S26 | S25 1964
	Bury original stone cor. alongside iron post, and raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor.
	Cor. set in small saddle of ridge.

Dependent Resurvey of the Subdivision, T. 10 N. R. 6 E.

CHAINS	
	Land, rolling mountainous. Soil, rocky clay loam. No timber. Undergrowth, dense sagebrush.
	From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp.
	S. 88° 02' W., bet. secs. 24 and 25.
	Over rolling mountainous land through dense sagebrush undergrowth. Asc. 15 ft. over SE. slope.
6.80	Spur, slopes SE.; desc. 55 ft. over SW. slope.
15.60	Draw, drains S. 20° E.; asc. 80 ft. over SE. slope.
30.60	Top of ascent, slopes S.; desc. 25 ft. over SW. slope.
37.80	Draw, drains S.; asc. 10 ft. over E. slope.
38.80	Point for the ¼ sec. cor. of secs. 24 and 25 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T10N R6E ¼ S24 / S25 1964
	Asc. 40 ft. over E. slope.
43.10	Spur, slopes SE.; asc. 75 ft. along S. slope.
66.65	Wash, drains S. 80° E.; asc. 75 ft. over SE. slope.
75.00	Top of ascent, bears nearly N. and S.; desc. 5 ft. along N. slope.
77.60	The cor. of secs. 23, 24, 25 and 26.
	Land, rolling mountainous. Soil, clay loam. No timber. Undergrowth, dense sagebrush.
	N. 0° 35' W., bet. secs. 23 and 24.
	Over rolling mountainous land through dense sagebrush undergrowth. Asc. 45 ft. over SW. slope.
12.00	Ridge, bears N. 75° W. and S. 75° E.; desc. 60 ft. over NE. slope.
18.80	Draw, drains S. 70° E.; asc. 150 ft. over SW. slope.

Dependent Resurvey of the Subdivision, T. 10 N., R. 6 E.

CHAINS	
34.30	Trail road, bears irregularly E. and W.
34.50	Fence, bears about E., and W. about 8.00 chs., thence SW.
40.05	Point for the ¼ sec. cor. of secs. 23 and 24 at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd. T10N R6E ¼ S23 | S24 1964 Asc. 160 ft. over steep SW. slope.
51.90	Ridge, bears SE. and curves N.; desc. 50 ft. along rocky E. slope.
80.10	The orig. cor. of secs. 13, 14, 23 and 24, monumented with a sandstone, 20x10x6 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. T10N R6E S14 | S13 S23 | S24 1964 Bury original stone cor. alongside iron post, and raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor. From this cor., U.S.G.S. triangulation station "Limestone", bears N. 34° 24' 26" W., 21.245 chs. dist. Land, mountainous. Soil, rocky clay loam. No timber. Undergrowth, sagebrush.
	From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp. S. 87° 42' W., bet. secs. 13 and 24. Over mountainous land through sagebrush undergrowth. Asc. 255 ft. over SE. slope.
32.05	Spur, slopes NE.; desc. 15 ft. over gentle NW. slope.
39.06	The orig. ¼ sec. cor. of secs. 13 and 24, monumented with a granite stone, 12x10x7 ins., set and mkd. as described in the official record. At the cor. point

CHAINS	De[illegible] en R[illegible] of the Subdivision [illegible] 0 [illegible] R. 6 E
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd. T10N R6E ¼ S13/S24 1964 Bury original stone cor. alongside iron post.
	S. 89° 03' W., beginning new measurement.
	Desc. 60 ft. over NW. slope.
7.65	Draw, drains NE.; asc. 150 ft. over SE. slope.
14.10	Fence, on spur, bears NE. and SW., curving S.; desc. 65 ft. over NW. slope.
25.85	Draw, drains NE.; asc. 190 ft. over E. slope.
39.85	The cor. of secs. 13, 14, 23 and 24.
	Land, mountainous. Soil, rocky clay loam. No timber. Undergrowth, sagebrush.
	N. 0° 10' E., bet. secs. 13 and 14.
	Over mountainous land through sagebrush undergrowth. Asc. 75 ft. along E. changing to SE. slope.
25.15	Spur, slopes NE.; desc. 160 ft. over NE. slope.
40.81	Point for the ¼ sec. cor. of secs. 13 and 14 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T10N R6E ¼ S14 | S13 1964
	Raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor.
	Desc. 90 ft. over NE. slope.
49.90	Draw, drains E.; asc. 225 ft. over steep S. slope.
71.25	Rocky point on ridge, bears NE., N. 70° W. and S. 20° W.; desc. 145 ft. over steep NW. slope.
81.62	The orig. cor. of secs. 11, 12, 13 and 14, monumented with a limestone, 14x8x6 ins., set and mkd. as described in the official record.

Dependent Resurvey of the Subdivision, T. 10 N., R. 6 E.

CHAINS	
	At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground, and in a collar of stone to top, with brass cap mkd. T10N R6E S11 | S12 S14 | S13 1964 Bury original stone cor. alongside iron post, and raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor. Land, mountainous. Soil, rocky clay loam. No timber. Undergrowth, sagebrush.
	From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp. S. 89° 43' W., bet. secs. 12 and 13. Over mountainous land through sagebrush undergrowth. Asc. 235 ft. over E. slope.
34.90	Ridge, bears N. 25° W. and S. 25° E.; desc. 40 ft. over SW. slope.
39.59	Point for the ¼ sec. cor. of secs. 12 and 13 at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T10N R6E ¼ S12 S13 1964 Desc. 15 ft. over SW. slope.
40.80	Draw, drains S. 30° E.; asc. 175 ft. over SE. slope.
51.20	Ridge, bears N. and S., thence by triangulation, desc. about 240 ft. over steep SW. slope.
61.20	Draw, drains N. 20° W.; asc. about 200 ft. over NE. slope.
78.00	Top of ascent, slopes N.; end triangulation; desc. 5 ft. over NW. slope.
79.18	The cor. of secs. 11, 12, 13 and 14.

CHAINS	
	Land, mountainous. Soil, rocky clay loam. No timber. Undergrowth, sagebrush.
	N. 0° 31' W., bet. secs. 11 and 12. Over mountainous land through sagebrush undergrowth. Desc. 190 ft. over steep NW. slope.
10.70	Spur, slopes N. 20° W.; desc. 215 ft. over steep NE. slope.
21.00	Draw, drains N. 20° W.; asc. 25 ft. over SW. slope.
32.40	Spur, slopes N. 10° W.; desc. 10 ft. along E. slope.
40.46	Point for the ¼ sec. cor. of secs. 11 and 12 at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd. T10N R6E ¼ S11 | S12 1964 Thence, by triangulation, desc. about 200 ft. over NE. slope.
50.90	Fence, with canal along N. side, flowing N. 75° E., bears about N. 75° E. and S. 75° W.; enter nearly level meadow land.
65.90	Big Creek, with stream of water, 10 lks. wide, 2 ft. deep flows irregularly NE. Dense willows along creek.
80.92	Point for the cor. of secs. 1, 2, 11 and 12 at proportionate dist.; there is no remaining evidence of the original cor. End triangulation. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T10N R6E S2 | S1 S11 | S12 1964 From this cor., a farm house and buildings bear about N. 60° E., about 35.00 chs. dist. Land, mountainous S. portion; nearly level meadow N. portion. Soil, rocky clay loam S. portion; loam N. portion No timber. Undergrowth, sagebrush S. portion; grass N. portion, with dense willows along Big Creek.

Dependent Resurvey of the Subdivision, T. 10 N., R. 6 E.

CHAINS	
	From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp.
	N. 89° 56' W., bet. secs. 1 and 12.
	Over gently rolling land, along N. side of road, and along fence line bears irregularly W.
8.00	Road, with fence along N. side, gradually turns to about N. 88° W.
40.14	Point for the ¼ sec. cor. of secs. 1 and 12 at proportionate dist., falls in canal, 10 lks. wide, 2 ft. deep, flows N. 80° E., curving NE. There is no remaining evidence of the original cor.
40.24	Point selected for the witness ¼ sec. cor. of secs. 1 and 12, on N. bank of canal.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T10N R6E S1 → W S12 C 1964
	Cor. is situated about 1.00 ch. S. of road, bears irregularly E. and N.
	Thence, by triangulation, over nearly level meadow land.
41.20	Fence, bears N. and curves SW.; enter meadow land.
58.20	Big Creek, with stream of water, 10 lks. wide, 2 ft. deep, flows irregularly NE. Dense willows along creek.
80.28	The cor. of secs. 1, 2, 11 and 12.
	Land, nearly level. Soil, loam. No timber. Undergrowth, sagebrush E. portion; grass W. portion, with dense willows along Big Creek.
	N. 0° 42' E., bet. secs. 1 and 2.
	Over nearly level meadow land.
4.25	Fence, bears irregularly NE. and SW. Leave meadow land; enter dense sagebrush; asc. 45 ft. over SE. slope.
5.90	Improved gravel road to Randolph, bears NE. and SW.
11.90	Point of spur, slopes E.; desc. 15 ft. over NE. slope.
15.90	Draw, drains SE.; asc. 100 ft. over S. slope.
24.55	Ridge, bears S. 75° E. and N. 75° W.; desc. 10 ft. over NE. slope.

Dependent Resurvey of the Subdivision, T. 10 N., R. 6 E.

CHAINS	
34.45	Head of draw, drains SE.; asc. 15 ft. over SE. slope.
40.46	Point for the ¼ sec. cor. of secs. 1 and 2 at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd. T10N R6E ¼ S2|S1 1964 Asc. 75 ft. over SE. slope.
56.90	Ridge, bears N. 70° E. and S. 70° W.; desc. 170 ft. over NW. slope.
81.94	The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of S. bdy. of T. 11 N., R. 6 E. Land, mountainous. Soil, rocky loam. No timber. Undergrowth, sagebrush.
	From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp. N. 0° 04' W., bet. secs. 34 and 35. Over rolling mountainous land through dense sagebrush. Desc. 10 ft. over N. slope.
2.00	Wash, drains S. 75° E.; asc. 80 ft. over S. slope.
10.40	Spur, with trail road on top, slopes E.; desc. 65 ft. over NE. slope.
26.85	Draw, with trail road in bottom, drains E. about 3.00 chs., thence SE.; asc. 55 ft. over SE. slope.
31.00	Point of spur, slopes S. 70° E.; desc. 35 ft. over NE. slope.
38.85	Draw, with trail road in bottom, drains S. 60° E.; asc. 20 ft. over S. slope.
40.15	Point for the ¼ sec. cor. of secs. 34 and 35 at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd.

Independent Resurvey of the Subdivision, T. 10 N. R. 6 E.

CHAINS	
	T10N R6E ¼ S34 | S35 1964
	Asc. 50 ft. over S. slope.
42.05	Point of rocky spur, slopes SE.; asc. 100 ft. over gentle SE. slope.
80.30	The orig. cor. of secs. 26, 27, 34 and 35, monumented with a sandstone, 18x12x6 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd.
	T10N R6E S27 | S26 S34 | S35 1964
	Bury original stone cor. alongside iron post.
	Cor. is situated on ridge, bears N. 75° E. and S. 75° W.
	Land, rolling mountainous. Soil, rocky clay loam. No timber. Undergrowth, dense sagebrush.
	From the cor. of secs. 25, 26, 35 and 36.
	N. 89° 50' W., bet. secs. 26 and 35.
	Over rolling mountainous land through dense sagebrush undergrowth. Along N. slope.
3.30	Small draw, 20 ft. deep, drains N.
16.80	Draw, 30 ft. deep, drains N.
28.85	Head of draw, drains NE.; asc. 70 ft. over NE. slope.
39.90	Point for the ¼ sec. cor. of secs. 26 and 35 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone to top, with brass cap mkd.
	T10N R6E ¼ S26 S35 1964
	Cor. falls in head of draw which drains NE.

Dependent Resurvey of the Subdivision, T. 10 N., R. 6 E.

CHAINS	
	Asc. 65 ft. over NE. slope.
58.00	Ridge, bears N. 30° W. and S. 30° E.; desc. 60 ft. over SW. slope.
59.13	Fence, bears N. 47° 50' W. and S. 47° 50' E.
79.80	The cor. of secs. 26, 27, 34 and 35.
	Land, rolling mountainous. Soil, rocky clay loam. No timber. Undergrowth, dense sagebrush.
	N. 0° 39' W., bet. secs. 26 and 27.
	Over rolling mountainous land through dense sagebrush undergrowth. Desc. 20 ft. over NW. slope.
8.00	Head of draw, drains S. 60° W.; asc. 15 ft. over SW. slope.
18.78	Fence, bears N. 47° 50' W. and S. 47° 50' E.
18.90	Ridge, bears NW. and SE.; desc. 60 ft. over NE. slope.
34.25	Draw, drains SE.; asc. 85 ft. over rocky SW. slope.
40.23	The orig. ¼ sec. cor. of secs. 26 and 27, monumented with a sandstone, 17x12x6 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd.
	T10N R6E ¼ S27|S26 1964
	Bury original stone cor. alongside iron post.
	N. 0° 19' E., beginning new measurement.
	Asc. 30 ft. over SE. slope.
8.50	Spur, slopes S.; desc. 20 ft. along E. slope.
29.00	Fence, bears about N. 71° E. and S. 71° W.
30.00	Head of draw, drains SE.; asc. 30 ft. over SE. slope.
38.00	Ridge, bears NE. and SW.; desc. 10 ft. over gentle NW. slope.

Dependent Resurvey of the Subdivision, T. 10 N., R. 6 E.

CHAINS	
40.28	Point for the cor. of secs. 22, 23, 26 and 27, at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base to top, with brass cap mkd. T10N R6E S22 | S23 S27 | S26 1964 Land, rolling mountainous. Soil, rocky clay loam. No timber. Undergrowth, dense sagebrush.
	From the cor. of secs. 23, 24, 25 and 26. N. 89° 09' W., bet. secs. 23 and 26. Over rolling land through sagebrush undergrowth. Asc. 50 ft. along S. slope.
23.80	Head of draw, drains S.; asc. 70 ft. over SE. slope.
35.30	Ridge, bears NE. and curves W.; desc. 20 ft. over gentle NW. slope.
40.39	Point for the ¼ sec. cor. of secs. 23 and 26 at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone to top, with brass cap mkd. T10N R6E ¼ S23 / S26 1964
	Desc. 10 ft. over gentle NW. slope.
41.90	Head of draw, drains NE.; asc. 70 ft. over SE. slope.
45.48	Fence, bears about S. 73° W. and N. 73° E. for 13.00 chs., thence NE.
56.90	Ridge, bears NE. and SW.; desc. 105 ft. over NW. slope.
68.60	Draw, drains S. 15° E.; asc. 45 ft. over SE. slope.
78.50	Ridge, bears NE. and SW.; desc. 15 ft. over NW. slope.
80.78	The cor. of secs. 22, 23, 26 and 27.

Dependent Resurvey of the Subdivision T. 10 N. R. 6 E.

CHAINS	
	Land, rolling mountainous. Soil, rocky clay loam. No timber. Undergrowth, sagebrush.
	N. 0° 14'W., bet. secs. 22 and 23. Over mountainous land through sagebrush undergrowth. Desc. 10 ft. over gentle NW. slope.
9.30	Draw, drains W.; asc. 65 ft. over SW. slope.
15.90	Ridge, bears N. 75° W. and S. 75° E.; desc. 270 ft. over NE. slope.
40.28	Point for the ¼ sec. cor. of secs. 22 and 23 at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T10N R6E ¼ S22|S23 1964 Asc. 10 ft. along E. slope.
49.00	Spur, slopes N. 30° E.; desc. 70 ft. over NW. slope.
57.85	Draw, drains N. 35° E.; asc. 55 ft. over SE. slope.
67.35	Spur, slopes N. 60° E.; desc. 100 ft. over NW. slope.
80.56	The orig. cor. of secs. 14, 15, 22 and 23, monumented with a sandstone, 16x10x4 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T10N R6E S15|S14 S22|S23 1964 Bury original stone cor. alongside iron post. Land, mountainous. Soil, rocky clay loam. No timber. Undergrowth, sagebrush.

Dependent Resurvey of the Subdivision T. 10 N. R. 6

CHAINS	
	From the cor. of secs. 13, 14, 23 and 24.
	N. 89° 04' W., bet. secs. 14 and 23.
	Over mountainous land through sagebrush undergrowth. Asc. 140 ft. over E. slope.
6.60	High ridge, bears N. 30° W. and curves S.; desc. 400 ft. over steep SW. slope.
32.60	Draw, drains NW.; asc. 30 ft. over NE. slope.
39.40	Spur, slopes NW.; desc. 5 ft. over NW. slope.
40.58	The orig. ¼ sec. cor. of secs. 14 and 23, monumented with a sandstone, 18x8x7 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T10N R6E ¼ S14/S23 1964
	Bury original stone cor. alongside iron post.
	N. 88° 38' W., beginning new measurement.
	Desc. 35 ft. over NW. slope.
1.10	Draw, drains N. 20° W.; asc. 65 ft. over NE. slope.
11.10	Spur, slopes NW.; desc. 180 ft. over SW. slope.
25.50	Draw, drains N.; asc. 110 ft. over SE. slope.
30.10	Spur, slopes NE.; desc. 35 ft. over NW. slope.
39.58	The cor. of secs. 14, 15, 22 and 23.
	Land, mountainous. Soil, rocky clay. No timber. Undergrowth, sagebrush.
	N. 0° 52' W., bet. secs. 14 and 15.
	Over mountainous land through dense sagebrush. Desc. 90 ft. over NW. slope.
4.40	Draw, drains NE.; asc. 115 ft. over SE. slope.
18.00	Ridge, bears N. and curves SW.; desc. 50 ft. along top of ridge.

Dependent Resurvey of the Subdivision, T. 10 N., R. 6 E.

CHAINS	
40.13	The orig. ¼ sec. cor. of secs. 14 and 15, monumented with a sandstone, 16x8x6 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd. T10N R6E ¼ S15 | S14 1964 Bury original stone cor. alongside iron post.
	N. 0° 09' E., beginning new measurement. Desc. 200 ft. over N. slope, along ridge top.
25.00	Trail road, bears about N. 5° E. and S. 5° W.
40.13	The orig. cor. of secs. 10, 11, 14 and 15, monumented with a limestone, 16x14x8 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd. T10NR6E S10 | S11 S15 | S14 1964 Bury original stone cor. alongside iron post. Land, mountainous. Soil, rocky clay loam. Timber, scattered juniper in the center of sec. 14. Undergrowth, sagebrush.
	From the cor. of secs. 11, 12, 13 and 14. N. 89° 54' W., bet. secs. 11 and 14. Over mountainous land through sagebrush undergrowth. Desc. 135 ft. over steep NW. slope.
4.80	Draw, drains N. 20° W., asc. 40 ft. over NE. slope.
8.35	Spur, slopes N. 20° W.; desc. 60 ft. over NW. slope.
12.15	Draw, drains N. 20° W.; asc. 35 ft. over NE. slope.

Dependent Resurvey of the Subdivision, T. 10 N., R. 6 E.

CHAINS	
24.55	Small spur, slopes N.; desc. 105 ft. over NW. slope.
40.45	Point for the ¼ sec. cor. of secs. 11 and 14 at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd. T10N R6E ¼ S11/S14 1964 Desc. 260 ft. over NW. slope.
73.70	Draw, drains N. 20° E.; asc. 30 ft. over SE. slope.
79.10	Spur, slopes NE.; desc. 15 ft. along N. slope.
79.15	Trail road, bears about N. 20° E. and S. 20° W.
80.90	The cor. of secs. 10, 11, 14 and 15. Land, mountainous. Soil, rocky clay loam. No timber. Undergrowth, sagebrush.
	N. 0° 15' W., bet. secs. 10 and 11. Over rolling mountainous land through sagebrush undergrowth. Desc. 105 ft. over N. slope.
2.80	Fence, bears about N. 61° E. and S. 61° W.
27.15	Big Creek, with stream of water, 15 lks. wide, 2 ft. deep, flows NE.; asc. 20 ft. over gentle SE. slope.
30.75	Improved gravel road to Randolph, with fence along S. side, bears about N. 70° E. and S. 70° W.; asc. 120 ft. over SE. slope. Enter scattered juniper timber.
39.72	The orig. ¼ sec. cor. of secs. 10 and 11, monumented with a sandstone, 20x15x3 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd. T10N R6E ¼ S10 | S11 1964

Dependent Resurvey of the Subdivision, T. 10 N., R. 6 E.

CHAINS	
	Bury original stone cor. alongside iron post, and raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of cor.
	N. 0° 03' E., beginning new measurement.
	Asc. 70 ft. over SE. slope.
5.00	Ridge, bears E. and W.; desc. 95 ft. over NE. slope.
26.50	Draw, drains S. 30° E.; leave timber; asc. 110 ft. over SW. slope.
40.27	The orig. cor. of secs. 2, 3, 10 and 11, monumented with a sandstone, 22x8x8 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T10N R6E S3 | S2 S10 | S11 1964
	Bury original stone cor. alongside iron post.
	Land, mountainous. Soil, rocky clay loam. Timber, scattered juniper N. portion. Undergrowth, sagebrush.
	From the cor. of secs. 1, 2, 11 and 12.
	S. 88° 00' W., bet. secs. 2 and 11.
	Over mountainous land through sagebrush undergrowth. Over meadow land.
7.00	Fence, bears about N. 60° E. and S. 60° W.; leave meadow land; asc. 155 ft. over steep SE. slope.
9.85	Improved gravel road to Randolph, bears about N. 60° E. and S. 60° W.
16.60	Rocky spur, slopes S.; desc. 65 ft. over SW. slope.
21.65	Draw, drains S.; asc. 30 ft. over SE. slope.
23.00	Spur, slopes SE.; desc. 30 ft. over SW. slope.
32.50	Draw, drains SE.; asc. 40 ft. over NE. slope.
40.50	The orig. ¼ sec. cor. of secs. 2 and 11, monumented with a sandstone, 14x8x4 ins., set and mkd. as described in the official record.

CHAINS

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T10N R6E

¼ S2 / S11

1964

Bury original stone cor. alongside iron post.

N. 89° 02' W., beginning new measurement.

Asc. 135 ft. over gentle NE. slope.

28.20 Ridge, bears NW. and SE.; desc. 20 ft. over SW. slope.

35.75 Draw, drains S.; asc. 20 ft. over SW. slope.

39.68 The cor. of secs. 2, 3, 10 and 11.

Land, mountainous.
Soil, clay loam.
No timber.
Undergrowth, sagebrush.

N. 0° 45' E., bet. secs. 2 and 3.

Over mountainous land through sagebrush undergrowth. Asc. 185 ft. over SE. slope.

22.90 Ridge, bears E. and W.; desc. 305 ft. over N. slope.

38.00 Bottom of descent, thence over nearly level canyon bottom.

40.50 Wash, 20 lks. wide, 6 ft. deep, in Dry Canyon, drains irregularly E.

40.88 Point for the ¼ sec. cor. of secs. 2 and 3 at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T10N R6E

¼

S3 | S2

1964

Continue over nearly level canyon bottom.

Dependent Resurvey of the Subdivision, T. 10 N., R. 6 E.

CHAINS	
45.75	Trail road, bears about N. 60° E. and S. 60° W.; asc. 110 ft. over SE. slope.
61.05	Spur, slopes SE.; desc. 55 ft. over NE. slope.
70.85	Draw, drains SE.; asc. 110 ft. over SW. slope.
82.27	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of S. bdy. of T. 11 N., R. 6 E. Land, mountainous. Soil, clay loam. No timber. Undergrowth, sagebrush.
	From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp. N. 0° 05' W., bet. secs. 33 and 34. Over mountainous land through dense sagebrush undergrowth. Desc. 35 ft. over N. slope.
3.50	Draw, drains E.; asc. 135 ft. over S. slope.
18.15	Ridge, bears E. and W.; desc. 85 ft. over N. slope.
27.40	Draw, drains E.; asc. 60 ft. over SE. slope.
39.38	The orig. ¼ sec. cor. of secs. 33 and 34, monumented with a sandstone, 20x10x5 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd. T10N R6E ¼ S33|S34 1964 Bury original stone cor. alongside iron post.
	N. 0° 13' E., beginning new measurement. Asc. 45 ft. over SE. slope.
17.35	Trail road, on ridge, bears E. and S. 70° W.; desc. 115 ft. over N. slope.
32.00	Draw, drains E.; asc. 60 ft. over S. slope.
40.29	The cor. of secs. 27, 28, 33 and 34, monumented with a sandstone, 16x13x3 ins., set and mkd. as described in the official record.

Dependent Resurvey of the Subdivision, T. 10 N., R. 6 E.

CHAINS

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone to top, with brass cap mkd.

T10N R6E

S28	S27
S33	S34

1964

Bury original stone cor. alongside iron post.

Land, mountainous.
Soil, clay loam.
No timber.
Undergrowth, sagebrush.

From the cor. of secs. 26, 27, 34 and 35.

S. 89° 51' W., bet. secs. 27 and 34.

Over mountainous land through sagebrush undergrowth.
Asc. 5 ft. over SE. slope.

0.80 Spur, slopes SW.; desc. 95 ft. over NW. slope.

24.85 Draw, drains S.; asc. 15 ft. over gentle NE. slope.

36.40 Trail road and S. end of earthen dam, about 5.00 chs. long, bears N. and S.; desc. 5 ft. over NW. slope.

39.89 Point for the ¼ sec. cor. of secs. 27 and 34 at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T10N R6E

¼ S27 / S34

1964

Raise a mound of stone, 3 ft. base, 1½ ft. high, N. of cor.

Desc. 15 ft. over gentle NW. slope.

46.80 Large flat draw, drains N. 80° E.; asc. 105 ft. over SE. slope.

68.80 Small wash, drains SE.

79.78 The cor. of secs. 27, 28, 33 and 34.

Land, mountainous and rolling.
Soil, rocky loam.
No timber.
Undergrowth, sagebrush.

CHAINS	
	N. 0° 42' W., bet. secs. 27 and 28.
	Over rolling mountainous land through sagebrush undergrowth. Asc. 5 ft. over SE. slope.
0.80	Spur, slopes E.; desc. 20 ft. over NE. slope.
6.80	Draw, drains S. 70° E.; asc. 110 ft. over SW. slope.
19.60	Ridge, bears NW. and SE.; desc. 45 ft. over NE. slope.
30.30	Draw, drains S. 60° E.; asc. 50 ft. over SE. slope.
40.26	Point for the ¼ sec. cor. of secs. 27 and 28 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T10N R6E ¼ S28 | S27 1964
	Asc. 30 ft. over SE. slope.
43.45	Trail road, on ridge, bears N. 71° E. and S. 71° W.
43.60	Fence, bears about N. 71° E. and S. 71° W.
45.70	Fence, bears about N. 43° W. and S. 43° E. to intersection with preceding fence.
45.80	Ridge, bears E. and W.; desc. 235 ft. over NE. slope.
75.30	Draw, drains N. 70° W., curving NW.; asc. 40 ft. over SW. slope.
80.52	The orig. cor. of secs. 21, 22, 27 and 28, monumented with a sandstone, 18x12x6 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T10N R6E S21 | S22 S28 | S27 1964
	Bury original stone cor. alongside iron post.
	Land, rolling and mountainous. Soil, rocky clay loam. No timber. Undergrowth, sagebrush.

Dependent Resurvey of the Subdivision, T. 10 N., R. 6 E.

CHAINS	
	From the cor. of secs. 22, 23, 26 and 27.
	S. 89° 27' W., bet. secs. 22 and 27.
	Over rolling mountainous land through sagebrush undergrowth. Desc. 105 ft. over SW. slope.
13.60	Draw, drains N. 20° W.; asc. 20 ft. over NE. slope.
19.10	Spur, slopes N. 20° W.; desc. 30 ft. over SW. slope.
27.35	Head of draw, drains NW.; asc. 15 ft. over NE. slope.
33.80	Spur, slopes N.; desc. 10 ft. over NW. slope.
39.10	Draw, drains N. 20° E.; asc. 10 ft. over SE. slope.
40.13	The ¼ sec. cor. of secs. 22 and 27, monumented with a sandstone, 14x14x4 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd.
	T10N R6E ¼ S22/S27 1964
	Bury original stone cor. alongside iron post.
	N. 89° 40' W., beginning new measurement.
	Asc. 70 ft. over SE. slope.
17.40	Trail road, bears irregularly N. and S., on spur, slopes N.; desc. 90 ft. over SW. slope. Enter reseeded area.
40.41	The cor. of secs. 21, 22, 27 and 28.
	Land, rolling and mountainous. Soil, clay loam. No timber. Undergrowth, sagebrush and grass.
	N. 0° 22' E., bet. secs. 21 and 22.
	Over rolling mountainous land through sagebrush undergrowth.
0.50	Spur, slopes W.; desc. 50 ft. over NW. slope.
6.65	Wash, drains W.; asc. 25 ft. over S. slope.
9.85	Low spur, slopes W.; desc. 100 ft. over NW. slope.

Dependent Resurvey of the Subdivision, T. 10 N., R. 6 E.

CHAINS	
25.45	Small draw, drains NW.; continue descent.
40.19	The orig. ¼ sec. cor. of secs. 21 and 22, monumented with a broken sandstone, 16x10x4 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a collar of stone to top, with brass cap mkd. T10N R6E ¼ S21 | S22 1964 Bury original stone cor. alongside iron post. --- N. 0° 13' E., beginning new measurement. Desc. 90 ft. over NW. slope.
14.10	Draw, drains NW.; asc. 65 ft. over SW. slope.
20.00	E. margin of Big Creek Reservoir, bears West, approx. 6 chs. dist.
21.00	Small draw, drains SW.; continue ascent.
26.40	Spur, slopes W.; desc. 45 ft. over NW. slope.
33.40	Draw, drains W.; asc. 75 ft. over SW. slope.
38.90	Spur, slopes W.; desc. 10 ft. over NW. slope.
40.16	The orig. cor. of secs. 15, 16, 21 and 22, monumented with a gray sandstone, 16x8x4 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd. T10N R6E S16 | S15 S21 | S22 1964 Bury original stone cor. alongside iron post, and raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor. Land, rolling mountainous. Soil, clay loam. No timber. Undergrowth, sagebrush.

Dependent Resurvey of the Subdivision, T. 10 N., R. 6 E.

CHAINS	
	From the cor. of secs. 14, 15, 22 and 23.
	S. 89° 38' W., bet. secs. 15 and 22.
	Over rolling mountainous land through sagebrush undergrowth. Desc. 55 ft. over NW. slope.
6.40	Draw, drains NE.; asc. 130 ft. over SE. slope.
17.50	Spur, with trail road along top, slopes NE.; desc. 15 ft. over NW. slope.
29.60	Head of draw, drains N.; asc. 70 ft. over NE. slope.
39.50	Spur, slopes N.
39.86	Point for the ¼ sec. cor. of secs. 15 and 22 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T10N R6E ¼ S15/S22 1964
	Desc. 45 ft. over NW. slope.
52.00	Draw, drains NE.; asc. 60 ft. over NE. slope.
58.70	Spur, slopes NW.; desc. 65 ft. over SW. slope.
76.65	Top of small knoll; desc. 60 ft. over SW. slope.
79.72	The cor. of secs. 15, 16, 21 and 22.
	Land, mountainous. Soil, clay loam. No timber. Undergrowth, sagebrush.
	N. 0° 01' W., bet. secs. 15 and 16.
	Over mountainous land through sagebrush undergrowth. Desc. 140 ft. over NW. slope.
20.80	Draw, drains NW.; asc. 65 ft. over SW. slope.
37.00	Spur, slopes N. 60° W.; desc. 80 ft. over NE. slope.
41.69	The orig. ¼ sec. cor. of secs. 15 and 16, monumented with a gray sandstone, 14x10x3 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd.

Dependent Resurvey of the Subdivision, T. 10 N., R. 6 E.

CHAINS	
	T10N R6E ¼ S16 | S15 1964
	Bury original stone cor. alongside iron post.
	N. 0° 12' E., beginning new measurement.
	Desc. 75 ft. over NE. slope.
3.00	Wash, 60 lks. wide, 6 ft. deep, drains NE.; continue descent over NE. slope.
4.85	Trail road, bears irregularly N. 60° E. and S. 60° W.
4.95	Fence, parallel to trail road.
14.65	Big Creek, with stream of water, 10 lks. wide, 2 ft. deep, flows NE.; asc. 100 ft. over SE. slope.
26.80	Improved dirt road, bears irregularly E. and W.
39.46	The orig. cor. of secs. 9, 10, 15 and 16, monumented with a limestone, 20x15x6 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T10N R6E S9 | S10 S16 | S15 1964
	Bury original stone cor. alongside iron post.
	Cor. is situated on small spur, slopes SE.
	Land, mountainous. Soil, rocky clay loam. No timber. Undergrowth, sagebrush, with willows along Big Creek.
	From the cor. of secs. 10, 11, 14 and 15.
	N. 89° 15' W., bet. secs. 10 and 15.
	Over rolling mountain land through sagebrush undergrowth. By triangulation; desc. about 100 ft. over NW. slope.
5.00	Fence, bears about N. 61° E. and S. 61° W.
10.00	Enter dense willows, bears NE. and SW.
15.30	Big Creek, with stream of water, 10 lks. wide, 2 ft. deep, flows NE.; asc. about 20 ft. over SE. slope.

Dependent Resurvey of the Subdivision, T. 10 N., R. 6 E.

CHAINS	
19.19	Fence, bears N. and S. End triangulation; leave dense willows, bears NE. and SW.; asc. 60 ft. over gentle SE. slope.
33.30	Wash, 75 lks. wide, 5 ft. deep, drains S.; asc. 25 ft. over E. slope.
36.60	Improved dirt road to Randolph, bears about N. 65° E. and S. 65° W.
39.09	The orig. ¼ sec. cor. of secs. 10 and 15, monumented with a sandstone, 16x10x6 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T10N R6E
	¼ S10/S15
	1964
	Bury original stone cor. alongside iron post.
	N. 89° 56' W., beginning new measurement.
	Asc. 80 ft. over E. slope.
5.50	Spur, slopes S.; desc. 35 ft. over SW. slope.
20.50	Wash, in draw, drains SE.; asc. 70 ft. over SE. slope.
27.90	Red spur, slopes S. 20° E.; desc.70 ft. over SW. slope.
36.00	Wash, in draw, drains S.; asc. 40 ft. over SE. slope.
40.00	The cor. of secs. 9, 10, 15 and 16.
	Land, rolling and mountainous. Soil, rocky clay loam. No timber. Undergrowth, sagebrush, with dense willows along Big Creek.
	N. 0° 06' E., bet. secs. 9 and 10.
	Over rolling mountainous land through dense sagebrush undergrowth. Asc. 60 ft. over SE. slope.
23.00	Draw, drains S. 30° E.; asc. 160 ft. over SW. slope.
40.75	The ¼ sec. cor. of secs. 9 and 10, monumented with a limestone, 24x10x7 ins., set and mkd. as described in the official record.
	At the cor. point

Dependent Resurvey of the Subdivision, T. 10 N., R. 6 E.

CHAINS	
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone to top, with brass cap mkd. T10N R6E ¼ S9 | S10 1964 Bury original stone cor. alongside iron post.
	N. 0° 01' W., beginning new measurement.
	Asc. 165 ft. over SW. changing to S. slope.
17.50	Ridge, bears E. and W.; desc. 130 ft. over N. slope.
39.58	The orig. cor. of secs. 3, 4, 9 and 10, monumented with a limestone, 20x10x4 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd. T10N R6E S4 | S3 S9 | S10 1964 Bury original stone cor. alongside iron post.
	Land, mountainous. Soil, rocky clay loam. No timber. Undergrowth, sagebrush.
	From the cor. of secs. 2, 3, 10 and 11.
	N. 89° 23' W., bet. secs. 3 and 10.
	Over rolling mountainous land through dense sagebrush undergrowth. Asc. 40 ft. over gently rolling SE. slope.
15.60	Ridge, bears NE. and SW.; thence along gentle N. slope.
38.59	The orig. ¼ sec. cor. of secs. 3 and 10, monumented with a sandstone, 14x10x8 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.

ndent Resurvey of the Subdivision T. 10 N. R. 6 E.

CHAINS	
	T10N R6E ¼ S3/S10 1964 Bury original stone cor. alongside iron post.
	N. 89° 32' W., beginning new measurement.
	Desc. 40 ft. along N. slope.
21.65	Wash, drains N.; asc. 90 ft. along N. slope.
40.17	The cor. of secs. 3, 4, 9 and 10.
	Land, rolling mountainous. Soil, rocky clay loam. No timber. Undergrowth, dense sagebrush.
	N. 0° 02' E., bet. secs. 3 and 4.
	Over mountainous land through dense sagebrush undergrowth; desc. 175 ft. over N. slope.
17.50	Wash, 25 lks. wide, 6 ft. deep, in Dry Canyon, drains E.; asc. 170 ft. over S. slope.
18.10	Trail road, bears E. and W.
40.60	The orig. ¼ sec. cor. of secs. 3 and 4, monumented with a sandstone, 16x10x6 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone to top, with brass cap mkd.
	T10N R6E ¼ S4|S3 1964
	Bury original stone cor. alongside iron post.
	N. 0° 33' E., beginning new measurement.
	Asc. 140 ft. over S. slope.
20.70	Spur, slopes E.; desc. 25 ft. over NE. slope.
25.00	Draw, drains SE.; asc. 125 ft. over SW. slope.
41.15	The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of S. bdy. of T.11 N., R. 6 E.

. . . endent Resurvey of the Subdivision, T. 10 N., R. 6 E.

CHAINS	
	Land, mountainous. Soil, clay loam. No timber. Undergrowth, dense sagebrush.
	From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp. N. 0° 34' E., bet. secs. 32 and 33. Over mountainous land through dense sagebrush undergrowth. Asc. 40 ft. over S. slope.
3.25	Trail road, on ridge, bears NE. and SW.; desc. 285 ft. over NW. slope.
34.25	Wash, in draw, drains NE.; asc. 25 ft. over SE. slope.
40.40	The orig. ¼ sec. cor. of secs. 32 and 33, monumented with a sandstone, 12x12x6 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T10N R6E ¼ S32 | S33 1964 Bury original stone cor. alongside iron post.
	N. 0° 07' E., beginning new measurement. Asc. 115 ft. over SE. slope.
9.75	Spur, slopes E.; desc. 90 ft. over NE. slope.
15.45	Draw, drains E.; asc. 155 ft. over SE. slope.
33.80	Spur, slopes E.; desc. 10 ft. along E. slope.
39.41	The orig. cor. of secs. 28, 29, 32 and 33, monumented with a sandstone, 18x14x8 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T10N R6E S29 | S28 S32 | S33 1964 Bury original stone cor. alongside iron post, and raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor.

Dependent Resurvey of the Subdivision, T. 10 N., R. 6 E.

CHAINS	
	Land, mountainous. Soil, rocky loam. No timber. Undergrowth, dense sagebrush.
	From the cor. of secs. 27, 28, 33 and 34. N. 89° 28' W., bet. secs. 28 and 33. Over mountainous land through dense sagebrush undergrowth. Asc. 210 ft. over SE. slope.
14.30	Draw, 20 ft. deep, drains SE.; continue ascent over SE. slope.
39.31	Point for the ¼ sec. cor. of secs. 28 and 33 at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T10N R6E ¼ S28/S33 1964 Asc. 5 ft. over SE. slope.
40.20	Spur, slopes S.; desc. 80 ft. over SW. slope.
50.60	Head of draw, drains SE.; asc. 130 ft. over SE. slope.
64.20	Spur, slopes SE.; desc. 55 ft. over SW. slope.
70.70	Draw, drains SE.; asc. 65 ft. over E. slope.
78.62	The cor. of secs. 28, 29, 32 and 33. Land, mountainous. Soil, clay loam. No timber. Undergrowth, dense sagebrush.
	N. 0° 30' W., bet. secs. 28 and 29. Over mountainous land through dense sagebrush undergrowth. Desc. 5 ft. along E. slope.
2.00	Head of draw, drains SE.; asc. 90 ft. over S. slope.
5.85	Trail road, bears about S. 30° W., and N. 70° E.
5.95	Fence, bears about S. 30° W. and N. 60° E.
18.50	Ridge, bears NW. and SE.; desc. 40 ft. along W. slope.
26.45	Desc. 250 ft. over steep N. slope.

Dependent Resurvey of the Subdivision, T. 10 N., R. 6 E.

CHAINS	
39.38	The orig. ¼ sec. cor. of secs. 28 and 29, monumented with a sandstone, 18x12x4 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T10N R6E ¼ S29 | S28 1964 Bury original stone cor. alongside iron post, and raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor.
	North, beginning new measurement. Desc. 185 ft. over N. slope.
24.85	Draw, drains NE.; asc. 60 ft. over SE. slope.
26.10	Spur, slopes NE.; desc. 60 ft. over N. slope.
30.15	Draw, drains E.; asc. 65 ft. over SE. slope.
38.00	Ridge, bears N. 20° E. and curves S.
39.75	The cor. of secs. 20, 21, 28 and 29, monumented with a sandstone, 24x12x5 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T10N R6E S20 | S21 S29 | S28 1964 Bury original stone cor. alongside iron post, and raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor. Land, mountainous. Soil, rocky loam. No timber. Undergrowth, sagebrush.
	From the cor. of secs. 21, 22, 27 and 28. S. 88° 42' W., bet. secs. 21 and 28. Over mountainous land through dense sagebrush undergrowth. Desc. 65 ft. over SW. slope.
6.15	Draw, drains N. 20° W.; asc. 85 ft. over NE. slope.

CHAINS	
21.80	Spur, slopes N.; desc. 110 ft. over SW. slope.
30.25	Draw, drains N. 20° W.; asc. 30 ft. over NE. slope.
30.83	Fence, bears about N. 43° W. and S. 43° E.
34.95	Small spur, slopes N.; desc. 5 ft. over NW. slope.
38.14	The original ¼ sec. cor. of secs. 21 and 28, monumented with a sandstone, 16x12x6 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone to top, with brass cap mkd. T10N R6E ¼ S21/S28 1964 Bury original stone cor. alongside iron post.
	N. 89° 51' W., beginning new measurement. Desc. 20 ft. over NW. slope.
6.95	Draw, drains NE.; asc. 235 ft. over SE. slope.
39.95	The cor. of secs. 20, 21, 28 and 29. Land, mountainous. Soil, rocky clay loam. No timber. Undergrowth, dense sagebrush.
	N. 0° 52' E., bet. secs. 20 and 21. Over rolling mountainous land through sagebrush undergrowth. Desc. 90 ft. along W. slope.
0.50	Trail road, bears about N. 15° E. and S. 15° W.
23.85	Small draw, drains W.; asc. 30 ft. over SW. slope.
29.45	Spur, slopes W.; desc. 80 ft. over NW. slope.
40.39	The orig. ¼ sec. cor. of secs. 20 and 21, monumented with a sandstone, 14x8x4 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

Dependent Resurvey of the Subdivision. T. 10 N. R. 6 E.

CHAINS	
	T10N R6E ¼ S20 | S21 1964 Bury original stone cor. alongside iron post.
	N. 0° 59' E., beginning new measurement.
	Desc. 210 ft. over N. slope.
30.30	Draw drains N. 20° W.; asc. 30 ft. over SW. slope.
33.50	Small spur, slopes W.; desc. 15 ft. over NW. slope.
40.49	The orig. cor. of secs. 16, 17, 20 and 21, monumented with a sandstone, 20x10x4 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T10N R6E S17 | S16 S20 | S21 1964
	Bury original stone cor. alongside iron post, and raise a mound of stone, 3 ft. base, 1½ ft.high, W. of cor.
	Land, mountainous. Soil, rocky loam. No timber. Undergrowth, sagebrush.
	From the cor. of secs. 15, 16, 21 and 22.
	N. 89° 45' W., bet. secs. 16 and 21.
	Over rolling mountainous land through sagebrush undergrowth. Desc. 125 ft. over steep W. slope.
8.15	Wash, 20 lks. wide, 6 ft. deep, in draw, drains N.; asc. 190 ft. over NE. slope.
34.45	Ridge, bears N. and S.; desc. 20 ft. over W. slope.
37.30	The orig. ¼ sec. cor. of secs. 16 and 21, monumented with a sandstone, 16x10x4 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of the Subdivision T. 10 N., R. [illegible]

CHAINS	
	T10N R6E ¼ S16 / S21 1964
	Bury original stone cor. alongside iron post, and raise a mound of stone, 3 ft. base, 1½ ft. high, N. of cor.
	S. 89° 27' W., beginning new measurement.
	Desc. 65 ft. over NW. slope.
0.85	Trail road, bears about S. 60° W. and N. 20° E.
21.95	Draw, drains N.; asc. 20 ft. over NE. slope.
27.95	Ridge, bears NW. and SE.; desc. 25 ft. over W. slope.
35.95	Fence, bears about N. 13° W. and S. 13° E.
39.94	The cor. of secs. 16, 17, 20 and 21.
	Land, rolling mountainous. Soil, clay loam. No timber. Undergrowth, sagebrush and grass.
	N. 0° 11' W., bet. secs. 16 and 17.
	Over rolling mountainous land through sagebrush undergrowth. Asc. 30 ft. over SW. slope.
4.15	Ridge, bears NW. and SE.; desc. 180 ft. over NE. slope.
16.06	Fence, bears about S. 13° E. and N. 13° W. about 3.00 chs. to cor.
19.29	Cor. of fence, bears W. 14 lks. dist., with fences bearing E. and W., and about S. 13° E. and about N. 0° 30' W.
27.60	Bottom of descent, thence over nearly level canyon bottom.
37.60	Big Creek, with stream of water, 20 lks. wide, 2 ft. deep, flows E.
40.46	Point for the ¼ sec. cor. of secs. 16 and 17 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T10N R6E ¼ S17 | S16 1964

Dependent Resurvey of the Subdivision, T. 10 N., R. 6 E.

CHAINS	
	Cor. falls in tall sagebrush, 29 lks. E. of N. and S. fence line.
	Asc. 170 ft. over S. slope.
51.92	Cor. of fence, bears W. 9 lks. dist., with fences bearing about N., S., E., and W.
52.40	Improved dirt road to Randolph, bears E. and W. curving SW.
60.60	Trail road, bears NE. and SW.; asc. 95 ft. over SE. slope.
80.92	The orig. cor. of secs. 8, 9, 16 and 17, monumented with a sandstone, 32x16x3 ins., set in mound of stone, and plainly mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T10N R6E S8 | S9 S17 | S16 1964
	Bury original stone cor. alongside iron post, and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	Cor. is situated in fence line, bears about N. and S.
	Land, mountainous and rolling. Soil, rocky and gravelly. No timber. Undergrowth, sagebrush, with scattered willows along Big Creek.
	From the cor. of secs. 9, 10, 15 and 16.
	S. 89° 40' W., bet. secs. 9 and 16.
	Over rolling mountainous land through sagebrush undergrowth. Asc. 20 ft. over SE. slope.
4.50	Spur, slopes S.; desc. 10 ft. over gentle SW. slope.
14.00	Draw, drains SW.; asc. 75 ft. over SE. slope.
26.00	Top of ascent, slopes S.; desc. 20 ft. over SW. slope.
39.44	Point for the ¼ sec. cor. of secs. 9 and 16 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

Dependent Resurvey of the Subdivision, T. 10 N., R. 6 E.

CHAINS

T10N R6E

¼ S9 / S16

1964

Cor. falls in small draw which drains S.

Asc. 45 ft. over SE. slope.

47.90 Spur, slopes SW.; desc. 15 ft. over SW. slope.

58.60 Draw, drains SE.; asc. 110 ft. over SE. slope.

78.88 The cor. of secs. 8, 9, 16 and 17.

Land, rolling mountainous.
Soil, gravelly loam.
No timber
Undergrowth, sagebrush.

N. 0° 31' E., bet. secs. 8 and 9.

Over mountainous land through sagebrush undergrowth.
Asc. 355 ft. over steep SE. slope, and along fence line.

19.00 Ridge, bears E. and W.; desc. 190 ft. over NW. slope.

39.92 The orig. ¼ sec. cor. of secs. 8 and 9, monumented with a sandstone, 14x12x4 ins., set and mkd. as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.

T10N R6E

¼

S8 | S9

1964

Bury original stone cor. alongside iron post.

Cor. is situated in fence line, bears about N. 1° E. and S. 0° 31' W.

N. 0° 59' W., beginning new measurement.

Desc. 10 ft. over NE. slope.

2.00 Wash, drains NW.; asc. 10 ft. over SW. slope.

4.00 Small spur, slopes NW.; desc. 225 ft. over NW. slope.

23.65 Draw, drains N. 70° E.; asc. 50 ft. over SE. slope.

Dependent Resurvey of the Subdivision, T. 10 N., R. 6 E.

CHAINS	
30.70	Ridge, bears N. 70° E. and S. 70° W.; desc. 80 ft. over NW. slope.
38.80	Draw, drains N. 70° E.; asc. over gentle SE. slope.
40.83	Point for the cor. of secs. 4, 5, 8 and 9 at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd. T10N R6E S5 | S4 S8 | S9 1964 Raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor. Cor. is situated 1.42 chs. W. of N. and S. fence line. Land, mountainous. Soil, clay loam. No timber. Undergrowth, sagebrush.
	From the cor. of secs. 3, 4, 9 and 10. West, bet. secs. 4 and 9. Over mountainous land through sagebrush undergrowth. Asc. 15 ft. along N. slope.
4.70	Spur, slopes N.; desc. 25 ft. over NW. slope.
16.70	Draw, drains NW.; asc. 20 ft. over NE. slope.
19.70	Spur, slopes N.; desc. 130 ft. over NW. slope.
30.30	Draw, drains N. 60° E.; asc. 35 ft. over SE. slope.
39.69	Point for the ¼ sec. cor. of secs. 4 and 9 at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd. T10N R6E ¼ S4 / S9 1964 Raise a mound of stone, 3 ft. base, 1½ ft. high, N. of cor. Cor. is situated on small spur, slopes NE. Asc. 70 ft. over NE. slope.

Dependent Resurvey of the Subdivision, T. 10 N., R. 6 E.

CHAINS	
58.60	Spur, slopes N.; desc. 15 ft. over NW. slope.
70.60	Wash, in draw, drains N. 70° E.; asc. 20 ft. over SE. slope.
77.96	Fence, bears about N. and S.
79.38	The cor. of secs. 4, 5, 8 and 9.
	Land, mountainous. Soil, clay loam. No timber. Undergrowth, sagebrush.
	N. 1° 10' E., bet. secs. 4 and 5.
	Over mountainous land through dense sagebrush undergrowth. Asc. 55 ft. over SE. slope.
3.55	Ridge, bears N. 70° E. and S. 70° W.; desc. 95 ft. over N. slope.
20.75	Wash, 30 lks. wide, 6 ft. deep, in Dry Canyon, drains S. 75° E.; asc. 120 ft. over S. slope.
22.10	Trail road, bears N. 75° W. and S. 75° E.
40.83	Point for the ¼ sec. cor. of secs. 4 and 5 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T10N R6E ¼ S5 | S4 1964
	Cor. is situated 1.25 chs. W. of N. and S. fence line.
	Asc. 120 ft. over S. slope.
59.20	Ridge, bears E. and W.; desc. 20 ft. over N. slope.
62.90	Small draw, drains W.; asc. 40 ft. over SW. slope.
67.90	Spur, slopes W.; desc. 90 ft. over NW. slope.
82.68	The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of the S. bdy. of T. 11 N., R. 6 E.
	Land, mountainous. Soil, clay loam. No timber. Undergrowth, sagebrush and scattered buck brush.

Dependent Resurvey of the Subdivision. T. 10 N. R. 6 E.

CHAINS	
	From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp.
	N. 0° 20' E., bet. secs. 31 and 32.
	Over mountainous land through dense sagebrush undergrowth. Desc. 60 ft. over N. slope.
4.80	Small draw, drains W.; asc. 145 ft. over S. slope.
14.15	Spur, slopes W.; desc. 190 ft. over N. slope.
26.95	Draw, drains W.; asc. 95 ft. over S. slope.
31.35	Spur, slopes W.; desc. 140 ft. over N. slope.
39.77	The orig. ¼ sec. cor. of secs. 31 and 32, monumented with a sandstone, 24x12x6 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T10N R6E ¼ S31 | S32 1964
	Bury original stone cor. alongside iron post, and raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor.
	N. 0° 23' E., beginning new measurement.
	Desc. 10 ft. over N. slope.
0.60	Draw, drains W.; asc. 145 ft. over S. slope.
9.20	Spur, slopes W.; desc. 35 ft. over N. slope.
16.00	Head of draw, drains W.; asc. 60 ft. over SW. slope.
21.25	Spur, slopes S. 70° W.; desc. 175 ft. over NW. slope.
35.60	Draw, drains S. 70° W.; asc. 35 ft. over SE. slope.
40.12	The orig. cor. of secs. 29, 30, 31 and 32, monumented with a sandstone, 20x10x8 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 22 in. in the ground, with brass cap mkd.
	T10N R6E S30 | S29 S31 | S32 1964

Dependent Resurvey of the Subdivision, T. 10 N., R. 6 E.

CHAINS	
	Bury original stone cor. alongside iron post, and raise a mound of stone, 4 ft. base, 2½ ft. high, W. of cor.
	Land, mountainous. Soil, rocky loam. No timber. Undergrowth, dense sagebrush.
	From the cor. of secs. 28, 29, 32 and 33.
	N. 89° 36' W., bet. secs. 29 and 32.
	Over mountainous land through dense sagebrush undergrowth. Asc. 15 ft. over E. slope.
2.50	Ridge, with trail road along same, bears NE. and SW.; desc. 170 ft. over NW. slope.
4.30	Fence, bears about N. 37° E. and S. 37° W.
19.00	Draw, drains NW.; asc. 40 ft. over NE. slope.
25.80	Spur, slopes N. 20° W.; desc. 105 ft. over SE. slope.
34.50	Draw, drains NW.; asc.75 ft. over NE. slope.
39.87	Point for the ¼ sec. cor. of secs. 29 and 32 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T10N R6E ¼ S29 / S32 1964
	Asc. 20 ft. over NE. slope.
41.20	Spur, slopes N. 60° W.; desc. 160 ft. over SW. slope.
66.03	Head of draw, drains S. 70° W.; asc. 35 ft. over gentle SE. slope.
79.74	The cor. of secs. 29, 30, 31 and 32.
	Land, mountainous. Soil, rocky clay loam. No timber. Undergrowth, dense sagebrush.
	N. 89° 50' W., bet. secs. 30 and 31.
	Over mountainous land through dense sagebrush undergrowth. Asc. 25 ft. over SE. slope.
15.00	Spur, slopes S. 75° W.; desc. 320 ft. over NW. slope.

Dependent Resurvey of the Subdivision, T. 10 N., R. 6 E.

CHAINS	
37.77	Fence, bears irregularly N. along base of hills, and S. 25 lks. to cor., thence W.
38.30	Trail road, bears irregularly N. and S.
38.75	Fork of Big Creek, with stream of water, 4 lks. wide, 3 ins. deep, flows N.; asc. 25 ft. over E. slope.
40.14	Point for the ¼ sec. cor. of secs. 30 and 31, at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T10N R6E ¼ S30 / S31 1964 Cor. is situated 25 lks. N. of E. and W. fence line. Asc. 300 ft. over steep E. slope.
58.02	Fence, bears N. and S. 30 lks. to cor., thence E.
62.60	Ridge, bears N. and S.; desc. 15 ft. over gentle W. slope.
80.17	The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record. Land, mountainous. Soil, rocky clay loam. No timber. Undergrowth, sagebrush, with scattered willows along creek.
	From the cor. of secs. 29, 30, 31 and 32. N. 0° 35' W., bet. secs. 29 and 30. Over mountainous land through dense sagebrush undergrowth. Asc. 65 ft. over SE. slope.
3.30	Spur, slopes S. 75° W.; desc. 50 ft. over NW. slope.
12.90	Head of draw, drains W.; asc. 15 ft. over SW. slope.
16.75	Spur, slopes W.; desc. 225 ft. over N. slope.
40.04	The orig. ¼ sec. cor. of secs. 29 and 30, monumented with a sandstone, 20x18x10 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and brass cap mkd.

Dependent Resurvey of the Subdivision, T. 10 N., R. 6 E.

CHAINS	
	T10N R6E ¼ S30 | S29 1964 Bury original stone cor. alongside iron post, and raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor.
	N. 1° 11' E., beginning new measurement. Desc. 10 ft. over N. slope.
1.00	Wash, 25 lks. wide, 10 ft. deep, in draw, drains W.; asc. 75 ft. over SE. slope.
8.50	Spur, slopes S. 60° W.; desc. 5 ft. over NW. slope.
14.75	Head of draw, drains SW.; asc. 80 ft. over SE. slope.
25.00	Spur, slopes S. 65° W.; desc. 155 ft. over N. slope.
40.18	The orig. cor. of secs. 19, 20, 29 and 30, monumented with a sandstone, 20x18x6 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with brass cap mkd. T10N R6E S19 | S20 S30 | S29 1964 Bury original stone cor. alongside iron post. Land, mountainous. Soil, rocky loam. No timber. Undergrowth, dense sagebrush.
	From the cor. of secs. 20, 21, 28 and 29. N. 87° 20' W., bet. secs. 20 and 29. Over mountainous land through sagebrush undergrowth. Desc. 10 ft. over W. slope.
0.15	Trail road, bears N. 15° E., and S. 15° W.
19.80	Rocky point; desc. 175 ft. over SW. slope.
31.25	Draw, drains NW.; asc. 10 ft. over NE. slope.
36.75	Small spur, slopes NW.; desc. 10 ft. over NW. slope.
38.97	he orig. ¼ sec. cor. of secs. 20 and 29, monumented with sandstone, 18x10x4 ins., set and mkd. as described in he official record.

Dependent Resurvey of the Subdivision, T. 10 N., R. 6 E.

CHAINS	
	At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T10N R6E ¼ S20/S29 1964 Bury original stone cor. alongside iron post.
	S. 89° 48' W., beginning new measurement. Desc. 10 ft. over NW. slope.
1.90	Small draw, drains N.; asc. 10 ft. over NE. slope.
3.40	Small spur, slopes N.; desc. 10 ft. over NW. slope.
6.50	Small draw, drains N.; asc. 85 ft. over NE. slope.
13.90	Spur, slopes NW.; desc.85 ft. over SW. slope.
32.90	Draw, drains NW.; asc. 30 ft. over NE. slope.
39.90	The cor. of secs. 19, 20, 29 and 30. Land, mountainous. Soil, rocky clay loam. No timber. Undergrowth, sagebrush.
	N. 89° 26' W., bet. secs. 19 and 30. Over mountainous land through sagebrush undergrowth. Desc. 80 ft. over W. slope.
12.10	Draw, drains NW.; desc. 130 ft. over NW. slope.
33.50	Big Creek, with stream of water, 10 lks. wide, 1½ ft. deep, flows NE.; asc. 20 ft. over gentle SE. slope. Dense willows along creek.
38.50	Improved dirt road to Randolph, bears about N. 70° E. and S. 70° W. Cor. of fence, bears S. about 1.00 ch., with fences bearing irregularly S. 70° W. and S. from fence cor.
39.85	The orig. ¼ sec. cor. of secs. 19 and 30, monumented with a sandstone, 30x10x4 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., on solid rock, and in a mound of stone, 5 ft. base to top, with brass cap mkd.

Dependent Resurvey of the Subdivision, T. 10 N., R. 6 E.

CHAINS	
	T10N R6E ¼ S19/S30 1964
	Bury original stone cor. in mound of stone alongside iron post.
	Cor. is situated at base of ledge, 4 ft. high, 30 lks. long, bears E. and W.
	West, beginning new measurement.
	Asc. 210 ft. over SE. slope.
21.00	Spur, slopes S.; desc. 135 ft. over SW. slope.
31.50	Draw, drains S.; asc. 90 ft. over NE. slope.
39.72	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record.
	Land, mountainous. Soil, rocky loam. No timber. Undergrowth, sagebrush, with willows along Big Creek.
	From the cor. of secs. 19, 20, 29 and 30.
	N. 0° 22' W., bet. secs. 19 and 20.
	Over mountainous land through sagebrush undergrowth. Desc. 165 ft. over NE. slope.
12.50	Draw, drains NW.; asc. 25 ft. over SW. slope.
18.00	Small wash, drains SW.
20.00	Spur, slopes W.; desc. 35 ft. over NW. slope.
23.90	Small draw, drains W.; asc. 35 ft. over SW. slope.
27.25	Spur, slopes W.; desc. 130 ft. over NW. slope.
39.76	Point for the ¼ sec. cor. of secs. 19 and 20, at cor. of fences from the E. and N., accepted as being a perpetuation of the original cor. point.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T10N R6E ¼ S19 | S20 1964

Dependent Resurvey of the Subdivision, T. 10 N., R. 6 E.

CHAINS	
	N. 0° 23' E., beginning new measurement.
	Along fence line.
2.30	Big Creek, with stream of water, 10 lks. wide, 2 ft. deep, flows irregularly NE.; asc. 90 ft. over SE. slope.
8.90	Improved road to Randolph, bears about N. 20° E. and S. 20° W.
19.80	Spur, slopes E.; desc. 90 ft. over NE. slope.
20.25	Trail road, bears about N. 70° E. and S. 70° W.
28.70	N. Fork of Big Creek, with stream of water, 6 lks. wide, 1 ft. deep, flows E.; asc. 100 ft. over SE. slope.
33.10	Improved dirt road to Randolph, bears E. and W.
40.03	The orig. cor. of secs. 17, 18, 19 and 20, monumented with a sandstone, 18x8x4 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T10N R6E S18 | S17 S19 | S20 1964
	Bury original stone cor. alongside iron post.
	Cor. is situated 3 lks. SE. of cor. of fence, with fence bearing S. and E.
	Land, mountainous. Soil, rocky loam. No timber. Undergrowth, sagebrush, with willows along Big Creek.
	From the cor. of secs. 16, 17, 20 and 21.
	N. 89° 19' W., bet. secs. 17 and 20.
	Over rolling mountainous land through sagebrush undergrowth. Desc. 50 ft. over SW. slope.
7.60	Draw, drains NW.; asc. 25 ft. over NE. slope.
19.91	Fence, on spur, bears N. and S.; desc. 75 ft. over gentle NW. slope.
36.50	S. side of small knoll; continue descent over NW. slope.
39.98	The orig. ¼ sec. cor. of secs. 17 and 20, monumented with a sandstone, 12x8x6 ins., set and mkd. as described in the official record.

Dependent Resurvey of the Subdivision, T. 10 N., R. 6 E.

CHAINS	
	At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with brass cap mkd. T10N R6E ¼ S17/S20 1964 Bury original stone cor. alongside iron post.
	N. 89° 50' W., beginning new measurement. Desc. 25 ft. over gentle NW. slope.
8.15	Big Creek, with stream of water, 10 lks. wide, 3 ft. deep, flows NE. from irregularly W. Enter dense willows.
11.15	Same creek; flows irregularly E. from N. 75° W.
13.30	Same creek, flows irregularly N. 75° E. from SW.; asc. 120 ft. over gentle SE. slope. Leave willows.
21.90	Improved dirt road to Randolph, bears NE. and SW.
22.43	Fence, bears N. 89° 50' W. and NE. about 2.00 chs., thence N. about 20.00 chs., thence E., continue along fence line.
40.13	The cor. of secs. 17, 18, 19 and 20. Land, rolling mountainous. Soil, clay loam. No timber. Undergrowth, sagebrush, with willows along Big Creek.
	N. 89° 53' W., bet. secs. 18 and 19. Over rolling mountainous land through dense sagebrush undergrowth. Asc. 35 ft. over SE. slope.
6.35	Top of ascent, slopes S.; desc. 95 ft. over SW. slope.
25.55	Improved dirt road, bears NW. curving W. and SE. curving E.
29.00	N. fork of Big Creek, with stream of water, 5 lks. wide, 1 ft. deep, flows irregularly SE. from N. 80° W.; asc. 25 ft. over gentle NE. slope.
40.25	The orig. ¼ sec. cor. of secs. 18 and 19, monumented with a sandstone, 18x12x10 ins., set and mkd. as described in the official record. At the cor. point

CHAINS	
	Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd. T10N R6E ¼ S18/S19 1964 Bury original stone cor. alongside iron post.
	N. 89° 30' W., beginning new measurement. Asc. 35 ft. over NE. slope.
9.40	Top of ascent, slopes N.; desc. 35 ft. over NW. slope.
18.00	Draw, drains N. 80° E.; asc. 55 ft. over gentle SE. slope.
39.97	The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record. Land, rolling mountainous. Soil, gravelly loam. No timber. Undergrowth, sagebrush and rabbit brush.
	From the cor. of secs. 17, 18, 19 and 20. N. 0° 28' E., bet. secs. 17 and 18. Over rolling mountainous land through dense sagebrush undergrowth. Asc. 100 ft. over SE. slope.
14.50	Spur, slopes S.; asc. 10 ft. over gentle SW. slope.
39.72	The orig. ¼ sec. cor. of secs. 17 and 18, monumented with a broken sandstone, 18x10x5 ins., firmly set in a mound of stone, and plainly mkd. ¼ on W. face. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base to top, with brass cap mkd. T10N R6E ¼ S18 | S17 1964 Bury original stone cor. alongside iron post.

Dependent Resurvey of the Subdivision, T. 10 N., R. 6 E.

CHAINS

N. 0° 04' W., beginning new measurement.

Asc. 5 ft. over SW. slope.

1.00 Wash, 15 lks. wide, 1 ft. deep, drains SW.; asc. 55 ft. over SE. slope.

8.00 Spur, slopes SW.; asc. 230 ft. over SW. slope.

32.00 Leave dense sagebrush, enter shadscale.

35.00 Draw, 30 ft. deep, drains S. 70° W.

40.73 The orig. cor. of secs. 7, 8, 17 and 18, monumented with a washed boulder, 16x8x5 ins., set and mkd. as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and brass cap mkd.

T10N R6E

S7	S8
S18	S17

1964

Bury original stone cor. alongside iron post, and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, rolling mountainous.
Soil, gravelly loam.
No timber.
Undergrowth, sagebrush and shadscale.

From the cor. of secs. 8, 9, 16 and 17.

N. 89° 52' W., bet. secs. 8 and 17.

Over mountainous land through sagebrush undergrowth. Asc. 10 ft. over gentle SE. slope.

4.80 Top of ascent, slopes S.; desc. 15 ft. along S. slope.

15.10 Rocky spur, slopes SE.; desc. 55 ft. over SW. slope.

30.00 Draw, drains S.; asc. 85 ft. over NE. slope.

39.06 Point for the ¼ sec. cor. of secs. 8 and 17 at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T10N R6E

¼ S8 / S17

1964

Asc. 350 ft. over steep NE. slope.

Dependent Resurvey of the Subdivision, T. 10 N., R. 6 E.

CHAINS	
52.90	Top of steep ascent, bears NW. and SE.; asc. 25 ft. over gentle NE. slope.
66.75	Top of flat ridge, bears NW. and SE.; desc. 90 ft. over SW. slope.
78.12	The cor. of secs. 7, 8, 17 and 18. Land, mountainous. Soil, gravelly loam. No timber. Undergrowth, sagebrush and shadscale.
	N. 89° 44' W., bet. secs. 7 and 18. Over rolling mountainous land through shadscale undergrowth. Desc. 185 ft. over SW. slope.
4.00	Enter sagebrush undergrowth.
21.30	Draw, drains S. 10° W.; asc. 25 ft. over gentle SE. slope.
40.63	Point for the ¼ sec. cor. of secs. 7 and 18 at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd. T10N R6E ¼ S7/S18 1964 Asc. 30 ft. over gentle SE. slope.
52.00	Spur, slopes SW.; desc. 80 ft. over NW. slope.
66.00	Draw, drains SW.; asc. 20 ft. over gentle SE. slope.
81.12	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record. Land, rolling mountainous. Soil, clay loam. No timber. Undergrowth, sagebrush and shadscale.
	From the cor. of secs. 7, 8, 17 and 18. N. 1° 12' W., bet. secs. 7 and 8. Over mountainous land through shadscale and sagebrush undergrowth. Asc. 75 ft. over SW. slope.

Dependent Resurvey of the Subdivision, T. 10 N., R. 6 E.

CHAINS

13.00 Ridge, bears NW. and SE.; desc. 275 ft. over NW. slope.

40.20 The orig. ¼ sec. cor. of secs. 7 and 8, monumented with a sandstone, 16x10x3 ins., set and mkd. as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T10N R6E
¼
S7|S8
1964

Bury original stone cor. alongside iron post.

N. 1° 00' W., beginning new measurement.

Desc. 40 ft. over NW. slope.

4.30 Draw, drains N. 75° E.; desc. 75 ft. over gently rolling land.

40.21 The orig. cor. of secs. 5, 6, 7 and 8, monumented with a sandstone, 17x8x4 ins., set and mkd. as described in the official record.

At the cor. point

Set an irom post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd.

T10N R6E
S6|S5
S7|S8
1964

Bury original stone cor. alongside iron post.

Land, mountainous S. portion; gently rolling N. portion.
Soil, clay loam.
No timber.
Undergrowth, sagebrush, shadscale and scattered service berry.

From the cor. of secs. 4, 5, 8 and 9.

S. 89° 54' W., bet. secs. 5 and 8.

Over gently rolling mountainous land through dense sagebrush undergrowth. Asc. 125 ft. over gently rolling SE. slope.

27.25 Low spur, slopes S.; desc. 10 ft. over gentle SW. slope.

Dependent Resurvey of the Subdivision, T. 10 N., R. 6 E.

CHAINS	
39.64	Point for the ¼ sec. cor. of secs. 5 and 8 at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd. T10N R6E ¼ S5/S8 1964 Asc. 55 ft. over gently rolling NE. slope.
79.28	The cor. of secs. 5, 6, 7 and 8. Land, gently rolling mountainous. Soil, clay loam. No timber. Undergrowth, dense sagebrush.
	N. 89° 26' W., bet. secs. 6 and 7. Over rolling mountainous land through dense sagebrush undergrowth. Asc. 70 ft. over NE. slope.
12.20	Spur, slopes NE.; desc. 35 ft. over NW. slope.
21.30	Draw, drains NE.; asc. 125 ft. over SE. slope.
39.73	The orig. ¼ sec. cor. of secs. 6 and 7, monumented with a washed boulder, 12x12x8 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T10N R6E ¼ S6/S7 1964 Bury original stone cor. alongside iron post, and raise a mound of stone, 3 ft. base, 1½ ft. high, N. of cor.
	N. 89° 08' W., beginning new measurement. Asc. 25 ft. over SE. slope.
23.15	Spur, slopes SE.; desc. 115 ft. over SW. slope.
39.15	Trail road; bears irregularly N. and S.
40.01	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record.

Dependent Resurve of the Subdivision T. 10

CHAINS

Land, rolling mountainous.
Soil, rocky clay loam.
No timber.
Undergrowth, dense sagebrush.

From the cor. of secs. 5, 6, 7 and 8.

N. 0° 03' E., bet. secs. 5 and 6.

Over rolling mountainous land through dense sagebrush undergrowth. Desc. 55 ft. over NE. slope.

5.65 Draw, drains N. 65° E.; asc. 15 ft. over SE. slope.

16.00 Low spur, slopes E.; desc. 50 ft. over N. slope.

24.25 Wash, 30 lks. wide, 5 ft. deep, in Dry Canyon, drains S. 80° E.; asc. 40 ft. over S. slope.

28.20 Trail road, bears N. 80° W. and S. 80° E.

29.50 Spur, slopes E.; desc. 25 ft. over NE. slope.

34.60 Draw, drains SE.; asc. 40 ft. over SW. slope.

42.56 The orig. ¼ sec. cor. of secs. 5 and 6, monumented with a sandstone, 18x12x10 ins., set and mkd. as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T10N R6E
¼
S6 | S5
1964

Bury original stone cor. alongside iron post.

N. 0° 51' W., beginning new measurement.

Asc. 165 ft. over S. slope.

25.00 Ridge, bears E. and W.; desc. 190 ft. over N. slope.

36.80 Fence, bears about N. 85° E. and S. 85° W.

37.90 Wash, 20 lks. wide, 4 ft. deep, in Old Canyon, drains E.; asc. 10 ft. over S. slope.

39.00 Improved dirt road to Randolph, bears W. and N. 85° E.

39.49 The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of S. bdy. of T. 11 N., R. 6 E.

Dependent Resurvey of the Subdivision, T. 10 N., R. 6 E.

CHAINS

Land, rolling mountainous.
Soil, rocky clay loam.
No timber.
Undergrowth, dense sagebrush.

General Description

Township 10 North, Range 6 East, is located about 3 miles southeast of Randolph, Utah, and mostly consists of broken ridges and hills covered with a dense growth of sagebrush and scattered service berry undergrowth, except for the canyon bottoms which have a fair growth of grass and willows along the canyon streams. Timber consists of scattered growths of juniper in sections 10, 11, 14 and 15. There is a good stream of water in Big Creek, which flows northeasterly through the central portion of the township. There is a ranch house and buildings in section 1. No other habitations were noted. The soil is mostly clay loam in the canyons and rocky on the ridges. The area is drained in an easterly direction by numerous draws. The elevation varies from about 6,000 ft. above sea level in the northeast corner, to about 7,320 ft. above sea level at U.S.G.S. triangulation station "Limestone", which is located on the highest peak in the township in section 14. There are improved dirt and gravel roads in the bottom of Dry Canyon and Big Creek canyon, and numerous trail roads along the higher ridges which provide easy access throughout the township.

Blank

Page

Form 4-680
(June 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
James M. Hansen	Transitman
Jerril E. Smith	Notes
Terry S. Dabel	Front Chainman
Barth D. Hansen	Flagman
Ferrel D. Reynolds	Cornerman

340

CERTIFICATE OF SURVEY

I, , HEREBY CERTIFY upon honor that,

in pursuance of special instructions bearing date of the 7th day of November , 19 63 ,

I have dependently resurveyed the South boundary and Guide Meridian along the East boundary and the subdivisional lines of Township 10 North, Range 6 East.

of the Salt Lake Meridian, in the State of Utah , which

are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

(Date) (Cadastral Surveyor)

March 1, 1965 Glen B Hatch

(Date) (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date APR 14 1966

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the dependent resurvey of the South boundary and Gui Meridian along the East boundary and the subdivisional lines of Township 10 North, Range 6 East.

executed by Glen B. Hatch, Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

MAY 11 1966 R E Brown

(Date) Acting (Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

, is a true copy of the original field notes.

Blank

Page

Blank

Page

Form 4–679
(January 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

343

R577

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF THE

GUIDE MERIDIAN

ALONG THE EAST BOUNDARY,

THE SOUTH AND WEST BOUNDARIES,

AND

THE SUBDIVISIONAL LINES

OF

TOWNSHIP 11 NORTH, RANGE 6 EAST

Of the SALT LAKE Meridian,

In the State of UTAH.

EXECUTED BY

GLEN B. HATCH CADASTRAL SURVEYOR

Under special instructions dated NOVEMBER 7, 19 63, which provided for the surveys included under Group Number 469, approved NOVEMBER 7, 1963, and assignment instructions dated JUNE 5, 19 64.

Survey commenced JUNE 15, 19 64

Survey completed AUGUST 9 64

344

DEPT. OF THE INTERIOR
BUR OF LAND MGMT

1966 MAY 31 AM 10 00 .0

RECEIVED
STATE & LAND OFFICE
SALT LAKE CITY, UTAH

INDEX DIAGRAM

Township 11 NORTH, Range 6 EAST,

21 **6** 70	71 **5** 70	59 **4** 58	50 **3** 49	40 **2** 39	31 **1** 30 7
19 **7** 68	68 **8** 67	58 **9** 57	48 **10** 47	38 **11** 38	29 **12** 28 6
18 **18** 65	66 **17** 65	56 **16** 56	47 **15** 46	37 **14** 36	27 **13** 27 5
16 **19** 63	64 **20** 63	54 **21** 54	45 **22** 44	35 **23** 34	25 **24** 25 4
15 **30** 61	62 **29** 61	52 **28** 52	43 **27** 42	33 **26** 32	24 **25** 23 3
14 **31** 13	60 **32** 12	51 **33** 11	41 **34** 10	31 **35** 9	22 **36** 8 2

CHAINS

Township 11 North, Range 6 East, Salt Lake Meridian Utah

Note: The original field notes of the E. bdys. of Tps. 5 to 12 N., R. 5 E., designate the line as a "Guide Meridian." Various plats of adjoining townships have designated this line as "Guide Meridian North." The U. S. Dept. of Interior General Land Office map of Utah dated 1943 designated it as "Guide Meridian East." We use the original designation "Guide Meridian."

The Guide Meridian along the E. bdy. of the Tp. was surveyed by Julian Bausman in 1869. The south boundary was surveyed by J. G. Burrill in 1875. The west boundary was surveyed by T. C. Bailey in 1875. The north 4 miles of the west boundary were retraced or resurveyed by A. P. Hanson in 1900. The subdivision was surveyed by T. C. Bailey and J. G. Burrill in 1875. The north boundary was concurrently resurveyed by Glen B. Hatch in 1964, and the record appears in the 1964 field notes of Township 12 North, Range 6 East.

The following field notes are those of the dependent resurvey of the east, south and west boundaries, and the subdivisional lines of Township 11 North, Range 6 East.

Before restoring the corners, the lines of the original survey were retraced, and diligent search made for any evidence of the original corner, or other calls of the original field note record.

The rules of proportionate measurement were applied to ascertain the position of the lost corners, but not until exhausting every reasonable possibility of finding direct evidence for the control of each particular corner.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and special instructions dated November 7, 1963.

All lines of this survey were run by direct method where the lines were accessible; lines inaccessible were run by triangulation or traverse methods. Distances to topography on lines run by triangulation of traverse are approximate. The details of such triangulations or traverses have been thoroughly checked and verified, and in order to simplify the record the diagrams and reductions are omitted from these field notes.

The direction of the lines of this survey were determined by reference to true meridians established on line by elongation observations on Polaris and altitude observations on the sun. The lines were carried forward by sustained angulation being supplemented by other altitude observations on the sun taken throughout the progress of the survey.

The geographic position for the southeast corner of the township is at latitude 41° 38' 25.79" North, and longitude 111° 12' 24.93" West, as determined from section line ties to U.S.G.S. triangulation station "Limestone," at latitude 41° 35' 59.62" North, and longitude 111° 13' 44.85" West, located N. 34° 24' 26" W., 21.245 chs. dist. from the corner of sections 13, 14, 23 and 24, T. 10 N., R. 6 E., and U.S.G.S. triangulation station "South Twin," at latitude 41° 44' 07.82" North, and longitude 111° 20' 00.53" West, located S. 89° 16' 12" W. 49.36 chs. dist. from the ¼ section corner of sections 31 and 36, T. 12 N., Rs. 5 and 6 E.

Township 11 North, Range 6 East, Salt Lake Meridian, Utah

CHAINS

The magnetic declination was read at several stations throughout the township and the average of these readings was found to be 15° 15' East.

Dependent Resurvey of the Guide Meridian
Along the E. Bdy. T. 11 N., R. 6 E.

Reestablishment of the Survey Executed
by Julian Bausman in 1869

Beginning at the identified point for orig. cor. of Tps. 10 and 11 N., Rs. 6 and 7 East, at the cor. of fences from the NE. and N. 88° 08' W., which was shown by Bill Norris, long time resident and land owner of Randolph, Utah, who identified it as being a perpetuation of the original cor.; there is no remaining evidence of the original stone cor.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and brass cap mkd.

T11N
R6E R7E

S36	S31
S1	S6

T10N

1964

Thence,

N. 0° 35' E., bet. secs. 31 and 36.

Over level meadow and farm land.

40.52 Point for the ¼ sec. cor. of secs. 31 and 36 at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 12 ins. long, 1 in. diam., 24 ins. below ground, with brass cap mkd.

T11N
R6E R7E
¼
S36 | S31
1964

from which

An iron post, 30 ins. long, 2½ ins. diam., set 24 ins. in the ground, and in a fence line, for a reference monument, bears N. 0° 35' E., 56 lks. dist., with brass cap mkd. T11N R6E R7E S31 S36 RM 1964, and an arrow pointing to the true cor.

41.08 Fence, wire, bears about S. 80° W. and NE.

58.60 Canal, 20 lks. wide, 5 ft. deep, with stream of water, 5 lks. wide, 2 ft. deep, flows NE.; leave farm and meadow land; enter sagebrush.

61.53 Fence, wire, bears about E. and W.

62.40 Farm road, parallels fence.

Dependent Resurvey of the Guide Meridian
Along the E. Bdy. T. 11 N., R. 6 E.

CHAINS	
75.20	Same canal, flows irregularly N. 30° E., from SE.
80.30	Wire fence, bears N. 15° E. and S. 15° W.
80.45	Improved gravel road, bears N. 15° E. and S. 15° W.
81.04	Point for the cor. of secs. 25, 30, 31 and 36 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in cement, with brass cap mkd.
	T11N R6E R7E S25 | S30 S36 | S31 1964
	Raise a mound of cement and stone, 3 ft. base, 2 ft. high, W. of cor.
	Land, level farm and meadow S. portion; rolling N. portion Soil, clay loam. No timber. Undergrowth, sagebrush N. portion.
	N. 0° 35' E., bet. secs. 25 and 30.
	Over rolling land through dense sagebrush undergrowth. Asc. 30 ft. over gentle SE. slope.
0.35	Fence, wire, bears E. and W.
13.00	Trail road, bears NE. and SW.
33.10	Small spur, slopes E.; desc. 15 ft. over gentle NE. slope.
40.52	The orig. ¼ sec. cor. of secs. 25 and 30, monumented with a sandstone, 14x6x3 ins., firmly set and properly mkd.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with glass at base, and brass cap mkd.
	T11N R6E R7E ¼ S25 | S30 1964
	Bury original stone cor. alongside iron post.
	N. 0° 16' E., beginning new measurement.
3.50	Wash, 20 lks. wide, 4 ft. deep, drains SE.; asc. 30 ft. over gently rolling S. slope.
14.80	Small wash, drains E.

Dependent Resurvey of the Guide Meridian
Along the E. Bdy. T. 11 N., R. 6 E.

CHAINS	
27.65	Wash, drains SE.
37.15	Trail road, bears E. and W.
38.20	Spur, slopes E.; desc. 40 ft. over steep N. slope.
40.17	Point for the cor. of secs. 19, 24, 25 and 30 at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in cement, with brass cap mkd. T11N R6E R7E S24 | S19 S25 | S30 1964 Land, gently rolling. Soil, clay loam. No timber. Undergrowth, dense sagebrush.
	N. 0° 16' E., bet. secs. 19 and 24. Over rolling land through dense sagebrush. Desc. 20 ft. over N. slope.
1.20	Wire fence, bears E. and W. about 1.00 ch., thence S. about 3.00 chs. to end.
1.45	Improved gravel road to Randolph, bears E. and W.
1.65	Wire fence, bears E. and W.; enter farm land. Ditch, along N. side of fence, drains E.
32.84	Ditch, drains E., leave farm land, bears E. and W.; asc. 115 ft. over S. slope.
40.17	The orig. ¼ sec. cor. of secs. 19 and 24, monumented with a sandstone, 18x10x6 ins., firmly set and properly mkd. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd. T11N R6E R7E ¼ S24 | S19 1964 Bury original stone cor. alongside iron post. Cor. set in fence, bears E. and W.

Dependent Resurvey of the Guide Meridian
Along the E. Bdy. T. 11 N., R. 6 E.

CHAINS	
	N. 0° 16' E., beginning new measurement.
	Asc. 90 ft. over gently rolling SE. slope.
9.40	Small wash, drains E.
40.41	The orig. cor. of secs. 13, 18, 19 and 24, monumented with a sandstone, 16x12x3 ins., firmly set and properly mkd.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd.
	T11N R6E R7E S13 | S18 S24 | S19 1964
	Bury original stone cor. alongside iron post.
	Land, farm land S. portion; rolling N. portion. Soil, clay loam S. portion; rocky N. portion. No timber. Undergrowth, sagebrush.
	N. 0° 15' E., bet. secs. 13 and 18.
	Over rolling land through dense sagebrush undergrowth. Asc. 5 ft. over gentle SE. slope.
4.90	Ridge, bears NE. and SW.; desc. 60 ft. over NW. slope.
8.25	Wash, drains SW.; asc. 75 ft. over gentle SW. slope.
12.85	Wash, drains SW.
39.40	Top of small knoll; desc. 5 ft. over N. slope.
40.40	The orig. ¼ sec. cor. of secs. 13 and 18, monumented with a sandstone, 20x8x5 ins., firmly set and properly mkd.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd.
	T11N R6E R7E ¼ S13 | S18 1964
	Bury original stone cor. alongside iron post.
	N. 0° 15' E., beginning new measurement.

Dependent Resurvey of the Guide Meridian
Along the E. Bdy. T. 11 N. R. 6 E.

CHAINS	
	Desc. 65 ft. over gentle NE. slope.
24.10	Small wash, drains NE.; asc. 40 ft. over SE. slope.
29.20	Small spur, slopes E.; desc. 50 ft. over N. slope.
32.90	Draw, drains E.; asc. 105 ft. over S. slope.
40.33	The orig. cor. of secs. 7, 12, 13 and 18, monumented with a sandstone, 20x7x4 ins., firmly set and properly mkd.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, and in a collar of stone to top, with brass cap mkd.
	T11N R6E R7E S12 | S7 S13 | S18 1964
	Bury original stone cor. alongside iron post.
	Land, rolling. Soil, rocky loam. No timber. Undergrowth, dense sagebrush.
	N. 0° 09' E., bet. secs. 7 and 12.
	Over rolling land through dense sagebrush. Asc. 10 ft. over S. slope.
1.35	Point of spur, slopes SW.; desc. 20 ft. over NW. slope.
5.85	Wash, drains SW.; asc. 30 ft. over SE. slope.
17.70	Spur, slopes NE.; desc. 80 ft. over NW. slope.
40.27	The orig. ¼ sec. cor. of secs. 7 and 12, monumented with a sandstone, 14x10x5 ins., firmly set and properly mkd.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, with glass at base, and in a collar of stone to top, with brass cap mkd.
	T11N R6E R7E ¼ S12 | S7 1964
	Bury original stone cor. alongside iron post.
	Cor. set on fence, bears E. and W.

Dependent Resurvey of the Guide Meridian
the E. Bdy. T. 11 N. R.

CHAINS	
	N. 0° 11' E., beginning new measurement.
	Desc. 15 ft. over NW. slope.
1.30	Telephone line, bears about N. 36° W. and S. 36° E.
1.35	Wash, drains NE.; asc. 85 ft. over SE. slope.
21.25	Spur, slopes E.; desc. 275 ft. over steep N. slope.
40.33	Point for the cor. of secs. 1, 6, 7 and 12 at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T11N R6E R7E S1 | S6 S12 | S7 1964 Set a steel fence post, 5½ ft. long, alongside iron post. Land, rolling, mountainous. Soil, rocky clay loam. No timber. Undergrowth, dense sagebrush.
	N. 0° 11' E., bet. secs. 1 and 6.
	Over meadow land.
0.10	Ditch, 5 lks. wide, 3 ft. deep, flows E.
1.90	Middle Fork Canyon, with stream of water, 4 lks. wide, 2 ft. deep, flows irregularly E.; enter meadow land.
2.13	Fence, bears E. and W.
7.35	Trail road, bears W. and curves NE.; leave meadow land; asc. 55 ft. over SE. slope.
9.58	Fence, bears W. and E. 40 lks. to cor., thence N.
16.15	Point of spur, slopes E.; desc. 60 ft. over NE. slope.
22.00	Enter meadow land, bears E. and W.
24.70	Otter Creek, with stream of water, 5 lks. wide, 2 ft. deep, flows irregularly SE.; asc. 30 ft. over S. slope.
36.50	Fence, bears NW. about 50 lks. to cor. with fences bearing NW., N. 0° 20' E., and SE. about 40 lks. to cor., thence S.
40.00	Improved gravel road to Randolph, bears about N. 50° W. and S. 50° E.
40.33	Point for the ¼ sec. cor. of secs. 1 and 6 at proportionate dist.; there is no remaining evidence of the original cor.

Dependent Resurvey of the Guide Meridian
Along the E. Bdy. T. 11 N., R. 6 E.

CHAINS	
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in cement, with brass cap mkd. T11N R6E R7E ¼ S1 | S6 1964
	Cor. is set 3 lks. E. of N. and S. fence line.
	Asc. 230 ft. over SW. slope along E. side of fence.
52.10	Spur, slopes W.; desc. 50 ft. over N. slope.
57.10	Draw, drains W.; asc. 55 ft. over SW. slope.
60.70	Spur, slopes W.; desc. 50 ft. over NW. slope.
69.10	Draw, drains W.; asc. 60 ft. over SW. slope.
80.66	The cor. of Tps. 11 and 12 N., Rs. 6 and 7 E., monumented with a 2½ in. iron post, set, mkd. and witnessed as described in the 1964 field notes of T. 12 N., R. 6 E.
	Land, mountainous. Soil, rocky clay loam. No timber. Undergrowth, sagebrush, with willows along Middle Fork and Otter Creek.

Dependent Resurvey of the South Boundary, T. 11 N., R 6 E.

Reestablishment of the Survey Executed by J. G. Burrill in 1875.

	From the cor. of Tps. 10 and 11 N., Rs. 6 and 7 E., hereinbefore described.
	N. 88° 08' W., bet. secs. 1 and 36.
	Over farm land and along fence line.
17.50	Canal, 20 lks. wide, 3 ft. deep, flows N.; leave farm land.
18.59	Fence, bears N. and S.
19.05	Improved gravel road to Randolph, bears N. and S.
19.96	Old fence, bears N.; continue along fence line.; asc. 180 ft. over SE. slope.
39.81	Point for the ¼ sec. cor. of secs. 1 and 36 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and brass cap mkd.

Dependent Resurvey of the South Boundary T. 11 N. R. 6 E.

CHAINS

T11N R6E

¼ S36/S1

T10N

1964

Raise a mound of stone, 3 ft. base, 1½ ft. high, N. of cor.

Cor. set on spur, slopes NE.

Desc. 15 ft. along N. slope; continue along fence line.

47.75 Wash, drains N.

57.00 Spur, slopes N.; desc. 100 ft. over NW. slope.

63.20 Bottom of steep descent; enter gently rolling land.

79.62 The orig. cor. of secs. 1, 2, 35 and 36, monumented with a sandstone, 12x8x4 ins., set and mkd. as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd.

T11N R6E

S35 | S36
S2 | S1

T10N

1964

Bury original stone cor. alongside iron post.

Cor. set at cor. of fence from E. and N.

Land, nearly level farm E. portion; rolling W. portion.
Soil, clay loam.
No timber.
Undergrowth, sagebrush W. portion.

N. 89° 50' W., bet. secs. 2 and 35.

Over rolling land through dense sagebrush. Desc. 10 ft. over gentle NW. slope.

9.80 Wash, 30 lks. wide, 6 ft. deep, in Dry Canyon, drains NE.; asc. 95 ft. over SE. slope.

18.20 Unimproved road, bears NE. and SW.

31.75 Spur, slopes S.; desc. 30 ft. over W. slope.

33.20 Draw, drains SE.; asc. 70 ft. over SE. slope.

CHAINS	
40.10	The orig. ¼ sec. cor. of secs. 2 and 35, monumented with a sandstone, 14x8x5 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, and in a collar of stone to top, with brass cap mkd. T11N R6E ¼ S35 / S2 T10N 1964 Bury original stone cor. alongside iron post.
	S. 89° 28' W., beginning new measurement. Asc. 25 ft. over SE. slope.
6.00	Spur, slopes S.; desc. 20 ft. over W. slope.
8.25	Wash, drains S.; asc. 145 ft. over SE. slope.
33.75	Spur, slopes SW.; desc. 10 ft. over SW. slope.
40.01	The orig. cor. of secs. 2, 3, 34 and 35, monumented with a washed boulder, 12x12x8 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, and in a collar of stone, with brass cap mkd. T11N R6E S34 | S35 S3 | S2 T10N 1964 Bury original stone cor. alongside iron post. Land, rolling. Soil, rocky clay loam. No timber. Undergrowth, dense sagebrush.
	N. 89° 17' W., bet. secs. 3 and 34. Over rolling mountainous land through sagebrush undergrowth. Desc. 10 ft. over W. slope.
1.30	Wash, drains S., asc. 55 ft. along steep S. slope.
12.75	Wash, drains S.; asc. 95 ft. over SE. slope.

Dependent Resurvey of the South [illegible] R [illegible]

CHAINS	
15.85	Spur, slopes S.; thence along S. slope.
20.45	Spur, slopes S.; desc. 25 ft. over SW. slope.
26.20	Draw, drains SE.; asc. 100 ft. over SE. slope.
39.80	The orig. ¼ sec. cor. of secs. 3 and 34, monumented with a washed boulder, 12x6x4 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T11N R6E ¼ S34/S3 T10N 1964
	Bury original stone cor. alongside iron post.
	S. 89° 39' W., beginning new measurement.
	Asc. 10 ft. over SE. slope.
2.00	Draw, drains SE.; asc. 120 ft. over NE. slope.
14.50	Cor. of fence, with fence bearing N. 55° E. and S. 89° 39' W.; ridge bears NW. and SE.; thence along fence line; desc. 30 ft. over SW. slope.
16.60	Draw, drains S.; asc. 25 ft. over SE. slope.
28.00	Spur, slopes S.; desc. 90 ft. over SW. slope.
28.40	Trail road, bears N. and S.
38.75	Draw, drains S.; asc. 30 ft. over SE. slope.
39.76	Point for the cor. of secs. 3, 4, 33 and 34 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T11N R6E S33|S34 S4|S3 T10N 1964
	Land, mountainous. Soil, rocky. No timber. Undergrowth, sagebrush.
	S. 89° 39' W., bet. secs. 4 and 33.

CHAINS	
	Over mountainous land through sagebrush and scattered service berry undergrowth. Asc. 10 ft. over SE. slope, and along fence line.
1.50	Small spur, slopes S.; desc. 40 ft. over W. slope.
10.60	Small draw, drains S.; asc. 50 ft. over E. slope.
15.65	Spur, slopes S.; desc. 15 ft. over NW. slope.
20.65	Draw, drains N.; asc. 140 ft. over NE. slope.
39.76	The orig. ¼ sec. cor. of secs. 4 and 33, monumented with a conglomerate stone, 14x10x4 ins., set and dimly mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd. T11N R6E ¼ S33 / S4 T10N 1964 Bury original stone cor. alongside iron post.
	N. 88° 30' W., beginning new measurement. Asc. 10 ft. over gentle NE. slope; continue along fence line.
3.80	Ridge, bears N. and S.; desc. 270 ft. over NW. slope.
38.07	Fence, bears N. and S.; continue along fence line.
38.37	The orig. cor. of secs. 4, 5, 32 and 33, monumented with a sandstone, 22x16x10 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T11N R6E S32 | S33 S5 | S4 T10N 1964 Bury original stone cor. alongside iron post, and raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor. Land, mountainous. Soil, rocky. No timber. Undergrowth, sagebrush.
	S. 89° 26' W., bet. secs. 5 and 32.

CHAINS	
	Over rolling mountainous land through sagebrush undergrowth, and along fence line, bears irregularly W.; desc. 130 ft. over NW. slope.
4.10	Wash, drains NW.
18.00	Bottom of descent, slopes N.; thence over nearly level canyon bottom.
40.73	Point for the ¼ sec. cor. of secs. 5 and 32 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T11N R6E ¼ S32/S5 T10N 1964
	Cor. set on fence line bearing irregularly E. and about S. 85° W.
	Continue over nearly level bottom land.
57.05	Old Canyon, drains irregularly N. 80° E.; asc. 30 ft. over gentle SE. slope.
75.15	Water trough and spring bears S. 50 lks. dist.
76.00	Wash, drains SE.
80.00	Improved gravel road, bears N. 85° E. and S. 85° W.
81.46	The orig. cor. of secs. 5, 6, 31 and 32, monumented with a sandstone, 16x8x6 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground and in a collar of stone to top, with brass cap mkd.
	T11N R6E S31 | S32 S6 | S5 T10N 1964
	Bury original stone cor. alongside iron post.
	Land, mountainous E. portion; gently rolling W. portion. Soil, rocky clay loam. No timber. Undergrowth, sagebrush.
	N. 89° 48' W.; bet. secs. 6 and 31.
	Over rolling land through dense sagebrush. Asc. 80 ft. along gentle S. slope.
14.70	Wash, drains S.
38.70	Wash, drains S.; asc. 10 ft. over SE. slope.

Dependent Resurvey of the South Boundary, T. 11 N., R. 6 E.

CHAINS	
40.13	The orig. ¼ sec. cor. of secs. 6 and 31, monumented with a sandstone, 16x8x3 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T11N R6E ¼ S31/S6 T10N 1964
	Bury original stone cor. alongside iron post.
	N. 89° 51' W., beginning new measurement.
	Asc. 35 ft. over SE. slope.
10.00	Spur, slopes S.; desc. 20 ft. over W. slope.
17.05	Wash, drains S.; asc. 50 ft. over NE. slope.
20.00	Spur, slopes SE.; desc. 20 ft. over SW. slope.
25.80	Draw, drains SE.; asc. 75 ft. over NE. slope.
35.50	Spur, slopes SE.; desc. 20 ft. along S. slope.
40.42	The cor. of Tps. 10 and 11 N., Rs. 5 and 6 E., monumented with an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record of 1938 resurvey of T. 10 N., R. 5 E. Land, rolling. Soil, rocky loam. No timber. Undergrowth, sagebrush.

Dependent Resurvey of the West Boundary, T. 11 N. R. 6 E.

Reestablishment of the Survey Executed by T. C. Bailey in 1875.

	From the cor. of Tps. 10 and 11 N., Rs. 5 and 6 E.
	N. 0° 38' E., bet. secs. 31 and 36.
	Over rolling land through dense sagebrush. Asc. 30 ft. over S. slope.
3.15	Spur, slopes E.; desc. 30 ft. over NE. slope.
8.00	Draw, drains S. 80° E., asc. 230 ft. over SW. slope.
24.10	Ridge, bears SE. and NW.; desc. 40 ft. over NE. slope.
28.00	Wash, drains N. 70° E.
32.35	Wash, drains SE.; asc. 15 ft. over SE. slope.
35.50	Point of low spur, slopes E.; desc. 20 ft. over NE. slope.
38.50	Wash, drains SE.; asc. 10 ft. over SW. slope.
40.21	Point for the ¼ sec. cor. of secs. 31 and 36 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and brass cap mkd.

Dependent Resurvey of the West Boundary, T. 11 N., R. 6 E.

CHAINS	
	T11N R5E R6E ¼ S36 | S31 1964
	Raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor.
	Asc. 55 ft. over SW. slope.
47.20	Spur, slopes NW.; desc. 125 ft. over NW. slope.
61.15	Head of draw, drains NE.; asc. 15 ft. over SE. slope.
69.00	Spur, slopes E.; desc. 100 ft. over N. slope.
77.20	Pole Canyon, drains E.; asc. 55 ft. over S. slope.
77.65	Trail road, bears E. and W.
80.42	The orig. cor. of secs. 25, 30, 31 and 36, monumented with a sandstone, 24x12x6 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T11N R5E R6E S25 | S30 S36 | S31 1964
	Bury original stone cor. alongside iron post.
	Land, rolling. Soil, rocky loam. No timber. Undergrowth, sagebrush.
	N. 0° 18' E., bet. secs. 25 and 30.
	Over rolling mountain land through sagebrush undergrowth. Asc. 50 ft. over S. slope.
3.30	Spur, slopes SE.; desc. 10 ft. over NE. slope.
7.35	Wash, drains SE.; asc. 50 ft. over SW. slope.
13.20	Spur, slopes SE.; desc. 45 ft. over NE. slope.
21.00	Trail road, in bottom of draw, drains SE., bears NW. and SE.; asc. 295 ft. over SW. slope. Small grove of aspen timber in draw.
40.04	The orig. ¼ sec. cor. of secs. 25 and 30, monumented with a sandstone, 35x10x3 ins., loosely set and dimly mkd. ¼ on N. face.
	At the cor. point

Dependent Resurvey of the West Boundary, T. 11 N. R. 6 E.

CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T11N

R5E R6E

¼

S25 | S30

1964

Bury original stone cor. alongside iron post.

N. 0° 51' E., beginning new measurement.

Asc. 15 ft. over SW. slope.

1.50 Ridge, bears SE. and curves N.; asc. 135 ft. over SE. slope.

19.30 Top of ascent, slopes E.; desc. 60 ft. over NE. slope. Enter aspen timber.

38.00 Draw, drains SE.; asc. 15 ft. over SW. slope. Leave timber.

39.78 The orig. cor. of secs. 19, 24, 25 and 30, monumented with a sandstone, 15x12x3 ins., set and mkd. as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone to top, with brass cap mkd.

T11N
R5E R6E

S24 | S19
S25 | S30

1964

Bury original stone cor. alongside iron post.

Land, mountainous.
Soil, rocky.
Timber, aspen.
Undergrowth, sagebrush and service berry.

Reestablishment of the Resurvey Executed by A. P. Hanson in 1900, with reestablishment of closing cors. and establishment of E. ¼ sec. cors. on this line, pertaining to T. 11 N., R. 5 E.

N. 0° 02' E., bet. secs. 19 and 24.

Over mountainous land through dense sagebrush undergrowth Asc. 70 ft. over SW. slope.

of the West Boundary 11

CHAINS	
8.65	Ridge, bears E. and W., thence by triangulation; desc. about 100 ft. over NE. slope. Enter aspen timber.
31.55	Spur, slopes W. End triangulation. Leave timber; desc. 320 ft. over N. slope.
39.59	The 1890 resurvey ¼ sec. cor. of secs. 19 and 24, monumented with a sandstone, 12x10x4 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a collar of stone to top, with brass cap mkd.

T11N
R5E R6E
¼
S24 | S19
1964

Bury original stone cor. alongside iron post.

N. 0° 50' E., beginning new measurement along the west boundary of Sec. 19.
Desc. 95 ft. over N. slope.

4.40	Wash, drains E.
4.60	Trail road, in New Canyon, bears E. and W.; asc. 460 ft. over S. slope.
9.20	Small outcropping of ledges, bears E. and W.; continue ascent.
26.10	Ridge, bears NE. and SW.; desc. 45 ft. over NW. slope.
31.45	Wash, drains SW.; asc. 20 ft. over SE. slope.
34.40	Small spur, slopes W.; desc. 20 ft. over NW. slope.
39.56	The 1890 resurvey cor. of secs. 18 and 19, monumented with a sandstone, 18x18x8 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T11N
R5E R6E
S24 | S18
| S19
1964

Bury original stone cor. alongside iron post, and raise a mound of stone, 3 ft. base, 1½ ft. high, E. of cor.

Dependent Resurvey of the West [illegible] T. 11 N. R. 6 E.

CHAINS

Land, mountainous.
Soil, rocky loam.
Timber, aspen.
Undergrowth, dense sagebrush.

N. 1° 50' E., along the W. bdy. of sec. 18.

Over mountainous land through sagebrush undergrowth.
Asc. 225 ft. over SW. slope.

1.99 The orig. closing cor. of secs. 13 and 24, T. 11 N., R. 5 E., monumented with a sandstone, 16x14x6 ins., set and mkd. as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd.

T11N
R5E R6E

C S13 | S18
C S24 |

1964

Bury original stone cor. alongside iron post.

22.15 Ridge, bears NW. and SE.; desc. 50 ft. over NE. slope. Enter dense service berry and scrub oak brush.

28.30 Bottom of descent, slopes E.; asc. 20 ft. over SE. slope.

32.00 Small spur, slopes NE.; desc. 190 ft. over NE. slope.

39.84 The 1890 resurvey ¼ sec. cor. of sec. 18, monumented with a sandstone, 12x8x6 ins., set and mkd. as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.

T11N
R5E R6E
¼

| S18

1964

Bury original stone cor. alongside iron post.

N. 1° 51' E., beginning new measurement.

Desc. 30 ft. over NE. slope. Leave dense service berry and oak brush.

Dependent Resurvey of the West [illegible] T. 11 N., R. 6 E.

CHAINS	
1.91	Point for the E. ¼ sec. cor. of sec. 13, T. 11 N., R. 5 E., at midpoint between the closing cor. of secs. 13 and 24, and the closing cor. of secs. 12 and 13. Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, and in a collar of stone, with brass cap mkd. T11N R5E R6E ¼ S13 1964 from which A lone pine, 13 ins. diam., bears S. 64° 45' W., 104 lks. dist., mkd. ¼ S13BT. Desc. 30 ft. over NE. slope.
3.70	Draw, Drains E.; asc. 120 ft. over SW. slope.
16.25	Spur, slopes SE.; desc. 30 ft. over NE. slope.
20.10	Draw, drains SE.; asc. 60 ft. over SW. slope.
29.10	Ridge, bears E. and W.; desc. 85 ft. over N. slope.
39.76	The 1890 resurvey cor. of secs. 7 and 18, monumented with quartzite stone, 18x12x4 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T11N R5E R6E S13 S7 S18 1964 Bury original stone cor. alongside iron post, and raise a mound of stone, 3 ft. base, 1½ ft. high, E. of cor. Land, mountainous. Soil, rocky loam. No timber. Undergrowth, sagebrush, service berry and oak brush.
	N. 0° 15' E., along the W. bdy. of sec. 7. Over mountainous land through scattered aspen timber and dense sagebrush undergrowth. Desc. 30 ft. over N. slope.
1.91	The orig. closing cor. of secs. 12 and 13, T. 11 N., R. 5 E., monumented with a sandstone, 14x12x10 ins., set and mkd. as described in the official record.

Dependent [illegible] of the West Boundary T. 11 N. R. [illegible]

CHAINS

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T11N
R5E R6E

C S12 | S7
C S13 |

1964

Bury original stone cor. alongside iron post.

Desc. 25 ft. over N. slope.

3.00 Enter aspen timber.

5.20 Draw, drains E.; asc. 145 ft. over SE. slope. Leave timber.

18.00 Top of ascent, slopes E.; desc. 130 ft. over NE. slope.

26.00 Enter aspen timber.

33.80 Draw, drains E.; asc. 30 ft. over S. slope.

35.00 Leave timber.

38.00 Top of ascent, slopes E.; desc. 10 ft. over gentle NE. slope.

39.86 The 1890 resurvey ¼ sec. cor. of sec. 7, monumented with a sandstone, 18x12x4 ins., set and mkd. as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T11N
R5E R6E
¼
|S7

1964

Bury original stone cor. alongside iron post.

From this cor., a spring and water trough, bears N. 70° W., 10.00 chs. dist.

N. 0° 56' E., beginning new measurement.

Desc. 140 ft. over gentle NE. slope.

1.83 Point for the E. ¼ sec. cor. of sec. 12, T. 11 N., R 5 E., at mid point bet. the closing cor. of secs. 12 and 13, and the closing cor. of secs. 1 and 12.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

nt Resurvev of the West T. 1 E.

CHAINS

T11N
R5E R6E
¼
S12
1964

Raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor.

10.25 Trail road, bears NE. and SW. to spring.

35.60 Wash, drains E.; asc. 15 ft. over S. slope. Small grove of aspen in draw.

37.00 Spur, slopes S. 80° E.; desc. 10 ft. over gentle N. slope.

39.93 The 1890 resurvey cor. of secs. 6 and 7, monumented with a sandstone, 16x10x4 ins., set and mkd. as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.

T11N
R5E R6E
S12 | S6
S7
1964

Bury original stone cor. alongside iron post.

Land, mountainous.
Soil, rocky clay loam.
Timber, aspen.
Undergrowth, sagebrush.

N. 0° 14' E., along the W. bdy. of sec. 6.

Over mountainous land through dense aspen timber. Desc. 25 ft. over N. slope.

1.69 The orig. closing cor. of secs. 1 and 12, T. 11 N., R. 5 E., monumented with washed boulder, 12x10x5 ins., set and mkd. as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and brass cap mkd.

T11N
R5E R6E
C S1 | S6
C S12
1964

Bury original stone cor. alongside iron post.

Desc. 20 ft. over N. slope.

4.70 Draw, drains E.; asc. 15 ft. over S. slope. Leave timber.

8.50 Spur, slopes S. 80° E.; desc. 30 ft. over N. slope.

10.40 Draw, drains N. 70° E.; asc. 80 ft. over SE. slope.

19.40 Spur, slopes NE.; desc. 35 ft. over N. slope.

Dependent Resurvey of the West Boundary, T. 11 N., R. 6 E.

CHAINS	
34.60	Draw, drains SE.; asc. 125 ft. over SW. slope.
40.82	The 1890 resurvey ¼ sec. cor. of sec. 6, monumented with a sandstone, 16x12x5 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and brass cap mkd.
	T11N R5E R6E ¼ S6 1964
	Bury original stone cor. alongside iron post, and raise a mound of stone, 2½ ft. base, 1½ ft. high, E. of cor.
	N. 0° 16' E., beginning new measurement.
0.52	Point for the E. ¼ sec. cor. of sec. 1, T. 11 N. R. 5 E. at proportionate dist. bet. the closing cor. of secs. 1 and 12, and the cor. of Tps. 11 and 12 N., Rs. 5 and 6 E.
	Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T11N R5E R6E ¼ S1 1964
	Asc. 45 ft. over SW. slope.
5.50	Ridge, bears SE. and NW.; desc. 5 ft. over NW. slope.
18.60	Head of draw, drains W.; asc. 60 ft. over SW. slope.
33.00	Ridge, bears NW. and SE.; desc. 245 ft. over NE. slope.
44.00	Small wash, drains NE.
44.41	The cor. of Tps. 11 and 12 N. Rs. 5 and 6 E., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the 1964 field notes of T. 12 N., R. 6 E.
	Land, mountainous. Soil, rocky. Timber, scattered aspen. Undergrowth, sagebrush.

Dependent Resurvey of the Subdivision, T. 11 N., R. 6 E.

Reestablishment of the Survey Executed by T. C. Bailey and J. G. Burrill in 1875.

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp.

N. 1° 19' W., bet. secs. 35 and 36.

Over rolling land through dense sagebrush undergrowth. Desc. 20 ft. over gentle N. slope, and along fence line.

Dependent Resurvey of the Subdivision T. 11 N., R. 6 E.

CHAINS	
4.60	Dry Canyon, wash, 30 lks. wide, 8 ft. deep, drains N. 80° E.; asc. 50 ft. over gently rolling SE. slope.
15.96	Fence, bears about N. 80° E.; leave N. and S. fence line.
24.50	Trail road, bears about N. 80° E. and SW.
25.30	Small wash, drains SE.
38.79	The orig. ¼ sec. cor. of secs. 35 and 36, monumented with a sandstone, 12x10x2 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T11N R6E ¼ S35 | S36 1964 Bury original stone cor. alongside iron post.
	N. 1° 36' E., beginning new measurement. Asc. 185 ft. over SE. slope.
38.20	Ridge, bears E. and W.; desc. 10 ft. over gentle N. slope.
39.98	The orig. cor. of secs. 25, 26, 35 and 36, monumented with a washed boulder, 12x12x8 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T11N R6E S26 | S25 S35 | S36 1964 Bury original stone cor. alongside iron post, and raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of cor. Cor. set on fence line, bears E. and N. 88° W. Land, rolling. Soil, rocky clay loam. No timber. Undergrowth, sagebrush.
	From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp. N. 89° 47' W., bet. secs. 25 and 36. Over rolling mountainous land through dense sagebrush undergrowth, along S. side of wire fence. Asc. 130 ft. over E. slope.
40.02	Point for the ¼ sec. cor. of secs. 25 and 36 at proportionate dist.; there is no remaining evidence of the original cor.

Dependent Resurvey of the Subdivision, T. 11 N., R. 6 E.

CHAINS	
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T11N R6E ¼ S25/S36 1964
	Raise a mound of stone, 3 ft. base, 1½ ft. high, N. of cor.
	Cor. is located 60 lks. S. of E. and W. fence line.
	Asc. 95 ft. over E. slope.
50.60	Small wash, drains SE.
72.00	Slope changes; asc. 35 ft. over gentle NE. slope.
80.04	The cor. of secs. 25, 26, 35 and 36.
	Land, rolling mountainous. Soil, loam. No timber. Undergrowth, dense sagebrush.
	N. 0° 42' E., bet. secs. 25 and 26.
	Over rolling bench land through dense sagebrush undergrowth. Asc. 10 ft. over gently rolling land.
17.50	Desc. 50 ft. over NW. slope.
28.80	Wash, drains NE.; asc. 15 ft. over SE. slope.
32.50	Spur, slopes NE.; desc. 20 ft. over NW. slope.
40.26	The orig. ¼ sec. cor. of secs. 25 and 26, monumented with a sandstone, 16x10x4 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T11N R6E ¼ S26 | S25 1964
	Bury original stone cor. alongside iron post.
	N. 0° 57" E., beginning new measurement.
	Desc. 30 ft. over NW. slope.
3.20	Wash, drains N. 65° E.; asc. 80 ft. over SE. slope.
20.20	Ridge, bears N. 75° E. and S. 75° W.; desc. 45 ft. over gentle NW. slope.
26.30	Trail road, bears N. 75° E. and S. 75° W.
40.64	Point for the cor. of secs. 23, 24, 25 and 26 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd.

Dependent Resurvey of the Subdivision, T. 11 N., R. 6 E.

CHAINS	
	T11N R6E S23 | S24 S26 | S25 1964 Land, rolling bench land. Soil, gravelly loam. No timber. Undergrowth, sagebrush.
	From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp. S. 89° 03' W., bet. secs. 24 and 25. Over rolling bench land through sagebrush undergrowth. Asc. 100 ft. over NE. slope.
1.30	Fence, bears N. about 1.20 chs. thence E., and S. about 1.70 chs. to end.
2.40	Trail road, bears N. and curves W.
5.90	Same road, bears irregularly E. and W.
36.90	Same road, bears irregularly E. and about S. 70° W.; desc 10 ft. over NW. slope.
38.75	Draw, drains NE.; asc. 20 ft. over SE. slope.
39.89	The orig. ¼ sec. cor. of secs. 24 and 25, monumented with a washed boulder, 12x10x6 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone to top, with brass cap mkd. T11N R6E ¼ S24 / S25 1964 Bury original stone cor. alongside iron port.
	N. 88° 26' W., beginning new measurement. Asc. 20 ft. over SE. slope.
5.75	Spur, slopes NE.; desc. 80 ft. over NW. slope.
12.00	Draw, drains N.; asc. 60 ft. over E. slope.
15.45	Spur, slopes N.; asc. 45 ft. along N. slope.
23.05	Small draw, drains NE.; asc. 30 ft. over SE. slope.
33.40	Spur, slopes NE.; desc. 15 ft. over NW. slope.
39.57	The cor. of secs. 23, 24, 25 and 26. Land, rolling bench land. Soil, gravelly loam. No timber. Undergrowth, sagebrush.
	N. 0° 11' E., bet. secs. 23 and 24.

Dependent Resurvey of the Subdivision, T. 11 N., R. 6 E.

CHAINS	
	Over rolling land through sagebrush undergrowth. Desc. 210 ft. over NW. slope.
19.45	Improved gravel road to Randolph, bears irregularly E. and W.; end steep descent. SE. cor. of Little Creek Reservoir bears W. 1.50 chs. dist.
21.00	Improved gravel road to Randolph, bears SE. and curves N.
21.80	Fence, bears about S. 87° E. and N. 87° W. 61 lks to cor., thence N.; enter meadow land.
26.15	Ditch, 10 lks. wide, 2 ft. deep, flows irregularly E., from Little Creek Reservoir.
28.50	Dry channel of East Creek, drains irregularly E.
40.63	Point for the ¼ sec. cor. of secs. 23 and 24 at proportionate dist.
	Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd.
	T11N R6E ¼ S23 | S24 1964
	From this cor., the original stone cor., a sandstone, 12x8x4 ins., plainly mkd. and lying loose on the ground, was found N. 6° 30' W., 70 lks. dist. According to local residents, this cor. has been moved several times and is not at the original cor. point.
	Bury original stone cor. alongside iron post.
41.20	Ditch, 5 lks. wide, 1 ft. deep, flows E., from Little Creek Reservoir.
41.23	Fence, bears E. and W. 71 lks. to cor., thence S. Leave meadow land; asc. 85 ft. over SW. slope.
44.00	NE. cor. of Little Creek Reservoir, bears W. about 2.00 chs. dist.
53.10	Point of spur, slopes W.; desc. 15 ft. along W. slope.
67.00	Draw, drains S. 10° W.; asc. 150 ft. over SE. slope.
81.26	The orig. cor. of secs. 13, 14, 23 and 24, monumented with a washed boulder, 12x12x8 ins., set, and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd.
	T11N R6E S14 | S13 S23 | S24 1964
	Bury original stone cor. alongside iron post.
	Land, rolling mountainous. Soil, clay loam in meadow land, gravelly loam on hills. No timber. Undergrowth, sagebrush.

Dependent Resurvey of the Subdivision, T. 11 N., R. 6 E.

CHAINS	
	From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp.
	N. 89° 05' W., bet. secs. 13 and 24.
	Over rolling mountainous land through dense sagebrush undergrowth. Desc. 80 ft. over NW. slope.
12.40	Draw, drains SW.; asc. 45 ft. over SE. slope.
29.00	Spur, slopes SW.; desc. 70 ft. over W. slope.
34.15	Draw, drains SW. from N.; asc. 45 ft. over E. slope.
39.71	Point for the ¼ sec. cor. of secs. 13 and 24 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T11N R6E ¼ S13/S24 1964
	Asc. 30 ft. over gentle E. slope.
50.90	Spur, slopes SW.; desc. 45 ft. over NW. slope.
63.35	Draw, drains SW.; asc. 85 ft. over SE. slope.
79.42	The cor. of secs. 13, 14, 23 and 24.
	Land, rolling mountainous. Soil, gravelly. No timber. Undergrowth, dense sagebrush.
	N. 0° 39' E., bet. secs. 13 and 14.
	Over rolling mountainous land through dense sagebrush undergrowth. Along gentle E. slope.
9.50	Ridge, bears NE. and SW.; desc. 20 ft. over NW. slope.
13.90	Draw, drains SW.; asc. 30 ft. over SE. slope.
33.50	Ridge, bears NE. and SW.; desc. 10 ft. over gentle NW. slope.
40.67	The orig. ¼ sec. cor. of secs. 13 and 14, monumented with a washed boulder, 12x10x10 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T11N R6E ¼ S14 | S13 1964
	Bury original stone cor. alongside iron post.
	N. 0° 34' E., beginning new measurement.
	Desc. 95 ft. over NW. slope.

Dependent Resurvey of the Subdivision, T. 11 N., R. 6 E.

CHAINS	
38.20	Cor. of fence, with fence bearing N. and curving irregularly W., thence along fence line.
39.27	The orig. cor. of secs. 11, 12, 13 and 14, monumented with a sandstone, 12x10x6 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T11N R6E S11 | S12 S14 | S13 1964 Bury original stone cor. alongside iron post. Land, rolling mountainous. Soil, gravelly loam. No timber. Undergrowth, sagebrush.
	From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp. N. 88° 25' W., bet. secs. 12 and 13. Over rolling mountainous land through dense sagebrush undergrowth. Desc. 40 ft. over W. slope.
4.50	Draw, drains S.; asc. 60 ft. over gently rolling NE. slope.
38.17	The orig. ¼ sec. cor. of secs. 12 and 13, monumented with a sandstone, 18x6x6 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd. T11N R6E ¼ S12 S13 1964 Bury original stone cor. alongside iron post.
	S. 89° 22' W., beginning new measurement. Asc. 10 ft. over NE. slope.
7.00	Low ridge, bears SE. and curves N.; desc. 105 ft. over gentle NW. slope.
29.50	Wash, drains NW.
40.69	The cor. of secs. 11, 12, 13 and 14.

Resurvey of the

CHAINS	
	Land, rolling mountainous. Soil, gravelly loam. No timber. Undergrowth, sagebrush.
	N. 0° 32' W., bet. secs. 11 and 12. Over gently rolling land through sagebrush undergrowth and along E. side of fence line. Desc. 30 ft. over NW. slope.
5.30	Wash, drains N. 75° W.; asc. 15 ft. over SW. slope.
8.00	Small spur, slopes N. 75° W.; desc. 10 ft. over NE. slope.
10.05	Wash, drains N. 85° W.; asc. 20 ft. over S. slope.
14.00	Small knoll; desc. 45 ft. over N. slope.
20.40	Wash, drains N. 80° W.; asc. 10 ft. over S. slope.
24.40	Small spur, slopes N. 60° W.; desc. 10 ft. over NE. slope.
30.60	Wash, drains W.; asc. 10 ft. over S. slope.
34.80	Small spur, slopes N. 75° W.; desc. 25 ft. over NE. slope.
40.44	Point for the ¼ sec. cor. of secs. 11 and 12 at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone to top, with brass cap mkd. T11N R6E ¼ S11 | S12 1964 Cor. is situated 10 lks. E. of N. and S. fence line.
45.30	Small spur, slopes NE.; desc. 70 ft. over NW. slope.
59.30	Middle Fork Canyon, stream of water, 3 lks. wide, 6 ins. deep, flows irregularly N. 60° E.; enter meadow land
60.50	Fence, bearing E. and W. 15 lks. Dist. to cor., with fence bearing S. and E. from cor.
80.88	The orig. cor. of secs. 1, 2, 11 and 12, monumented with a sandstone, 12x8x6 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd. T11N R6E S2 | S1 S11 | S12 1964

CHAINS	
	Bury original stone cor. alongside iron post. Cor. is set in fence line bearing N. 89° 27' W. and S. 88° 32' E. Land, rolling. Soil, clay loam in meadow; gravelly on hills. No timber. Undergrowth, sagebrush and meadow grass.
	From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp. S. 89° 51' W., bet. secs. 1 and 12. Over nearly level bottom land through dense sagebrush undergrowth.
12.80	Enter dense willows along creek.
25.35	Telephone line, bears about N. 36° W. and S. 36° E.; leave dense willows.
35.00	Enter dense willows.
40.58	The orig. ¼ sec. cor. of secs. 1 and 12, monumented with a sandstone, 14x8x5 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T11N R6E ¼ S1/S12 1964 Bury original stone cor. alongside iron post. Cor. set in edge of willows along S. side of creek.
	N. 88° 32' W., beginning new measurement.
8.00	Middle Fork Canyon, stream of water, 5 lks. wide, 1 ft. deep, flows irregularly E.
10.00	Leave dense willows; enter meadow land.
30.60	Cor. of fence, with fence bearing N. and N. 88° 32' W.; thence along fence line.
39.32	The cor. of secs. 1, 2, 11 and 12. Land, nearly level bottom land. Soil, clay loam. No timber. Undergrowth, dense sagebrush and willows E. portion; meadow grass W. portion.

CHAINS	
	N. 0° 27' W., bet. secs. 1 and 2.
	Over gently rolling land through sagebrush undergrowth. Asc. 25 ft. over gentle S. slope. Leave bottom land.
24.00	Spur, slopes W.; desc. 40 ft. over N. slope.
29.00	Enter bottom land.
39.75	Fence, bears S. 75° E. and N. 75° W. about 3.00 chs., thence W., enter meadow land.
40.47	Point for the ¼ sec. cor. of secs. 1 and 2 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
	T11N R6E ¼ S2 | S1 1964
	Continue over nearly level meadow land.
42.50	Otter Creek, with stream of water, 5 lks. wide, 2 ft. deep, flows SE.
63.61	Fence, bears irregularly E. and W.; leave meadow land; asc. 50 ft. over S. slope.
63.80	Improved gravel road to Randolph, bears irregularly E. and W.
78.35	Telephone line, bears about N. 36° W. and S. 36° E.
80.44	The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the 1964 field notes of T. 12 N., R. 6 E.
	Land, rolling. Soil, clay loam. No timber. Undergrowth, sagebrush on hills; meadow grass in bottom land.
	From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp.
	N. 0° 39' E., bet. secs. 34 and 35.
	Over rolling mountainous land through sagebrush undergrowth. Asc. 165 ft. over S. slope.
12.60	Spur, slopes E.; desc. 35 ft. over NW. slope.
14.10	Draw, drains NE.; asc. 30 ft. over SE. slope.
19.00	Small spur, slopes E.; desc. 20 ft. over NE. slope.
21.50	Wash, drains SE.; asc. 85 ft. over SE. slope.

Dependent Resurvey of the Subdivision, T. 11 N., R. 6 E.

CHAINS

40.17 Point for the ¼ sec. cor. of secs. 34 and 35 at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.

T11N R6E
¼
S34 | S35

1964

Cor. set on ridge, bears NE. and SW.

Desc. 150 ft. over NW. slope.

42.35 Fence, bears about N. 46° E. and S. 46° W.

72.15 Wash, drains NE.; asc. 20 ft. over SE. slope.

80.34 The orig. cor. of secs. 26, 27, 34 and 35, monumented with a washed boulder, 12x8x6 ins., set and mkd. as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd.

T11N R6E

S27 | S26
S34 | S35

1964

Bury original stone cor. alongside iron post.

Land, rolling mountainous.
Soil, rocky clay loam.
No timber.
Undergrowth, sagebrush.

From the cor. of secs. 25, 26, 35 and 36.

N. 88° 02' W., bet. secs. 26 and 35.

Over rolling mountainous land through sagebrush undergrowth. Asc. 80 ft. over gentle E. slope, and along fence line.

39.36 The orig. ¼ sec. cor. of secs. 26 and 35, monumented with a sandstone, 14x8x5 ins., set and mkd. as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

CHAINS	
	T11N R6E ¼ S26/S35 1964 Bury original stone cor. alongside iron post. Cor. is set at cor. of fence bearing E., and about S 50° W.
	S. 89° 53' W., beginning new measurement. Asc. 50 ft. over gentle NE. slope.
15.00	Ridge, bears NE. and SW.; desc. 65 ft. over NW. slope.
32.50	Draw, drains NE.; asc. 65 ft. over SE. slope.
40.04	The cor. of secs. 26, 27, 34 and 35. Land, rolling mountainous. Soil, rocky clay loam. No timber. Undergrowth, sagebrush.
	N. 0° 06' W., bet. secs. 26 and 27. Over rolling mountainous land through sagebrush undergrowth. Desc. 35 ft. over N. slope.
8.15	Wash, drains E.; asc. 20 ft. over S. slope.
8.90	Fence, bears about N. 40° E. and S. 40° W.
19.90	Ridge, with trail road on top, bears N. 85° E. and S. 85° W.; desc. 40 ft. over NE. slope.
28.40	Draw, drains NW.; asc. 35 ft. over SW. slope.
40.13	The orig. ¼ sec. cor. of secs. 26 and 27, monumented with a sandstone, 14x8x3 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T11N R6E ¼ S27 | S26 1964 Bury original stone cor. alongside iron post.
	N. 1° 04' E., beginning new measurement. Asc. 25 ft. over SW. slope.

Dependent Resurvey of the Subdivision, T. 11 N. R. 6 E.

CHAINS	
5.50	Ridge, bears E. and W.; desc. 210 ft. over NW. slope.
34.50	Trail road, bears about N. 15° W. and S. 15° E.
40.19	The orig. cor. of secs. 22, 23, 26 and 27, monumented with a sandstone, 14x10x6 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T11N R6E S22 | S23 S27 | S26 1964 Bury original stone cor. alongside iron post. Land, rolling mountainous. Soil, clay loam. No timber. Undergrowth, sagebrush.
	From the cor. of secs. 23, 24, 25 and 26. N. 89° 06' W., bet. secs. 23 and 26. Over rolling mountainous land through sagebrush undergrowth. Desc. 115 ft. over NW. slope.
8.70	Draw, drains N.; asc. 130 ft. over SE. slope.
19.45	Spur, slopes N. 30° E.; desc. 125 ft. over NW. slope.
27.45	Draw, drains N. 20° E.; asc. 120 ft. over E. slope.
33.45	Spur, slopes N.; desc. 45 ft. over NW. slope.
39.85	The orig. ¼ sec. cor. of secs. 23 and 26, monumented with a sandstone, 16x8x5 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass alongside, and in a collar of stone, with brass cap mkd. T11N R6E ¼ S23 / S26 1964 Bury original stone cor. alongside iron post.
	N. 89° 43' W., beginning new measurement. Desc. 70 ft. over NW. slope.

CHAINS	
5.70	Draw, drains N.; asc. 40 ft. over NE. slope.
20.03	Fence, bears N. and S.
20.95	Wash, drains NE.; asc. 30 ft. over SE. slope.
34.80	Top of ascent, slopes N.; desc. 10 ft. over gentle NW. slope.
40.02	The cor. of secs. 22, 23, 26 and 27.
	Land, rolling mountainous. Soil, gravelly clay. No timber. Undergrowth, sagebrush.
	N. 0° 17' W., bet. secs. 22 and 23.
	Over rolling land through sagebrush undergrowth. Desc. 155 ft. over NW. slope.
22.70	Improved gravel road to Randolph, bears irregularly E. and W.; enter bottom land.
22.90	Cor. of fence, with fence bearing irregularly E. and W. and N.; thence along fence line. Enter cultivated land.
24.70	Old Canyon, stream of water, 3 lks. wide, 6 ins. deep, flows E.
40.24	Point for the ¼ sec. cor. of secs. 22 and 23 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone to top, with brass cap mkd. T11N R6E ¼ S22 | S23 1964
	Continue over cultivated land and along fence line. Asc. 60 ft. over gentle S. slope.
54.00	Ditch, with stream of water, 3 lks. wide, 3 ins. deep, flows SE.; leave cultivated land.
57.90	Low ridge, bears E. and W.; desc. 55 ft. over gentle N. slope.
61.85	Fence, bears E. and W.; leave N. and S. fence line.
62.35	Improved gravel road to Randolph, bears irregularly E. and W.
62.65	Fence, parallel to road.
62.70	New Canyon, stream of water, 3 lks. wide, 4 ins. deep, flows E.; asc. 20 ft. over gently rolling S. slope.
74.60	Wash, drains SE.
77.40	Low spur, slopes E.; desc. 10 ft. over NE. slope.

CHAINS

80.48 The orig. cor. of secs. 14, 15, 22 and 23, monumented with a broken sandstone, 22x14x4 ins., set and mkd. as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T11N R6E

S15	S14
S22	S23

1964

Bury original stone cor. alongside iron post.

Land, rolling.
Soil, clay loam.
No timber.
Undergrowth, sagebrush.

From the cor. of secs. 13, 14, 23 and 24.

S. 89° 54' W., bet. secs. 14 and 23.

Over rolling mountainous land through sagebrush undergrowth. Asc. 10 ft. over SE. slope.

1.00 Spur, slopes SW.; desc. 100 ft. over NW. slope.

14.30 Draw, drains SW.; asc. 65 ft. over SE. slope.

20.75 Spur, slopes SW.; desc. 135 ft. over NW. slope.

40.43 The orig. ¼ sec. cor. of secs. 14 and 23, monumented with a sandstone, 10x8x5 ins., set and mkd. as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone to top, with brass cap mkd.

T11N R6E

¼ S14 / S23

1964

Bury original stone cor. alongside iron post.

N. 89° 47' W., beginning new measurement.

Desc. 45 ft. over NW. slope.

8.05 Improved gravel road to Randolph, bears N. 10° W. and S. 20° E.

CHAINS	
9.25	Fence, bears about S. 20° E. and curves about N. 80° W.; thence over nearly level land.
25.00	Wash, drains SE.
40.07	The cor. of secs. 14, 15, 22 and 23.
	Land, rolling. Soil, gravelly loam. No timber. Undergrowth, sagebrush.
	N. 0° 13' W., bet. secs. 14 and 15.
	Over gently rolling land through dense sagebrush undergrowth. Asc. 65 ft. over gentle SE. slope.
3.20	Fence, bears about S. 80° E. and N.; thence along fence line.
6.00	Wash, drains SE.
30.45	Fence, bears about N. 50° W.; leave fence line.
40.26	The orig. ¼ sec. cor. of secs. 14 and 15, monumented with a sandstone, 12x10x8 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T11N R6E ¼ S15 | S14 1964
	Bury original stone cor. alongside iron post.
	N. 0° 21' W., beginning new measurement.
	Asc. 125 ft. over SE. slope.
22.20	Ridge, bears E. and W.; desc. 155 ft. over N. slope.
40.33	The orig. cor. of secs. 10, 11, 14 and 15, monumented with a sandstone, 16x14x6 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd. T11N R6E S10 | S11 S15 | S14 1964

CHAINS	
	Bury original stone cor. alongside iron post.
	Land, rolling. Soil, clay loam. No timber. Undergrowth, sagebrush.
	From the cor. of secs. 11, 12, 13 and 14.
	N. 89° 33' W., bet. secs. 11 and 14.
	Over gently rolling land through sagebrush undergrowth. Desc. 70 ft. over NW. slope.
10.00	Wash, drains NW.; asc. 20 ft. over gentle NE. slope.
31.45	Trail road, bears N. and curves W.
40.90	Fence, bears about N. 80° W. and S. 80° E.
40.92	Point for the ¼ sec. cor. of secs. 11 and 14 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a collar of stone, with brass cap mkd. T11N R6E ¼ S11/S14 1964
	Desc. 25 ft. over NW. slope.
55.85	Trail road, bears S. and curves NW.
55.95	Wash, 20 lks. wide, 5 ft. deep, drains N.; asc. 30 ft. over NE. slope.
67.35	Top of ascent, slopes N.; desc. 10 ft. along N. slope.
81.84	The cor. of secs. 10, 11, 14 and 15.
	Land, rolling. Soil, gravelly loam. No timber. Undergrowth, sagebrush.
	N. 0° 13' W., bet. secs. 10 and 11.
	Over rolling land through sagebrush undergrowth; desc. 90 ft. over N. slope.
4.45	Trail road, bears N. 70° W. and S. 70° E.
4.60	Fence, parallel to road.
9.60	Enter meadow land.
25.50	S. branch of Middle Fork Canyon, stream of water, 5 lks. wide, 3 ins. deep, flows E.; asc. 15 ft. over gentle SE. slope.

Dependent Resurvey of the Subdivision T. 11 N. R. 6 E.

CHAINS	
40.00	Canal, 5 lks. wide, 2 ft. deep, drains NE.; leave meadow land.
40.15	Point for the ¼ sec. cor. of secs. 10 and 11 at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd. T11N R6E ¼ S10 | S11 1964 Asc. 50 ft. over SE. slope.
49.30	Fence, bears NE. and SW.
61.00	Spur, slopes E.; desc. 150 ft. over NE. slope.
71.70	Canal, drains SE.; enter dense willows.
73.70	Middle Fork Canyon, stream of water, 10 lks. wide, 2 ft. deep, flows irregularly E.
75.00	Leave willows; asc. 15 ft. over SW. slope.
80.30	The orig. cor. of secs. 2, 3, 10 and 11, monumented with a sandstone, 16x12x4 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd. T11N R6E S3 | S2 S10 | S11 1964 Bury original stone cor. alongside iron post. Cor. set in fence line, bears about S. 55° E. and N. 55° W., 5 lks. to cor., thence N. Land, rolling. Soil, clay loam. No timber. Undergrowth, sagebrush, grass and willows.
	From the cor. of secs. 1, 2, 11 and 12. N. 89° 27' W., bet. secs. 2 and 11. Over gently rolling land through sagebrush undergrowth. Asc. 85 ft. over gentle E. slope, and along fence line.

Dependent Resurvey of the Subdivision, T. 11 N., R. 6 E.

CHAINS

40.03 The orig. ¼ sec. cor. of secs. 2 and 11, monumented with a broken sandstone, 8x6x3 ins.; no remaining markings on stone, but is accepted as the best available evidence of the original cor.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T11N R6E

¼ S2 / S11

1964

Bury original cor. alongside iron post.

Cor. is situated at cor. of fence from E. and SW.

S. 89° 41' W., beginning new measurement.

Asc. 150 ft. over SE. slope.

22.90 Top of ascent, slopes S.; desc. 135 ft. over SW. slope.

41.31 The cor. of secs. 2, 3, 10 and 11.

Land, rolling.
Soil, gravelly clay.
No timber.
Undergrowth, sagebrush.

N. 0° 22' E., bet. secs. 2 and 3.

Over rolling mountainous land through sagebrush undergrowth. Asc. 110 ft. over SW. slope, and along fence line.

15.00 Top of ascent, slopes W.; desc. 100 ft. over NW. slope.

40.10 The orig. ¼ sec. cor. of secs. 2 and 3, monumented with a sandstone, 14x8x4 ins., set and mkd. as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T11N R6E

¼

S3 | S2

1964

Bury original stone cor. alongside iron post.

Cor. is situated in fence cor. from which fences bear N., S., and W.

Resurvey of the Subdivi

CHAINS	
	N. 2° 21' E., beginning new measurement.
	Desc. 45 ft. over N. slope, and along fence line.
1.93	Cor. of fence, with fence bearing N., S., and E.; continue along fence line.
6.00	Wash, drains E.; asc. 60 ft. over gentle S. slope.
18.65	Otter Creek, with stream of water 4 lks. wide, 2 ft. deep, flows E.
23.65	Fence, bears irregularly E. and curves SW.
33.15	Improved gravel road to Randolph, bears N. 20° W. curving W., and S. 20° E. curving E.
37.00	Wash, 10 lks. wide, 2 ft. deep, drains SW.
41.88	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the 1964 field notes of T. 12 N., R. 6 E. Land, rolling. Soil, clay loam. No timber. Undergrowth, sagebrush.
	From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp.
	N. 0° 02' W., bet. secs. 33 and 34.
	Over rolling mountainous land through sagebrush and service berry undergrowth. Asc. 45 ft. over S. slope.
5.50	Ridge, bears E. and W.; desc. 90 ft. over N. slope.
16.65	Draw, drains NW.; asc. 70 ft. over SW. slope.
26.00	Ridge, bears E. and W.; desc. 20 ft. over gentle N. slope.
35.30	Desc. 95 ft. over steep NE. slope.
40.24	The orig. ¼ sec. cor. of secs. 33 and 34, monumented with a sandstone, 14x8x3 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground with glass at base, and brass cap mkd. T11N R6E ¼ S33 | S34 1964 Bury original stone cor. alongside iron post.

CHAINS	
	N. 0° 47' E., beginning new measurement.
	Desc. 175 ft. over steep NE. slope.
14.40	Wash, drains NW.; asc. 15 ft. over SW. slope.
21.10	Small spur, slopes NW.; desc. 15 ft. over NE. slope.
26.00	Wash, drains NW.; asc. 15 ft. over SW. slope.
36.80	Spur, slopes W.; desc. 20 ft. over N. slope.
40.37	Point for the cor. of secs. 27, 28, 33 and 34 at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and brass cap mkd. T11N R6E S28 | S27 S33 | S34 1964 Raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor. Land, rolling mountainous. Soil, clay loam. No timber. Undergrowth, sagebrush and service berry.
	From the cor. of secs. 26, 27, 34 and 35. N. 89° 41' W., bet. secs. 27 and 34. Over rolling mountainous land through sagebrush undergrowth. Asc. 85 ft. over SE. slope.
6.40	Fence, bears about N. 40° E. and S. 40° W.
24.00	Low ridge, bears NE. and SW.; desc. 10 ft. along N. slope.
38.00	Wash, drains N. 80° E.; asc. 10 ft. over SE. slope.
39.00	Fence, bears NW. and SE.
39.87	Point for the ¼ sec. cor. of secs. 27 and 34 at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd. T11N R6E ¼ S27 / S34 1964
	Asc. 65 ft. over SE. slope.
53.80	Ridge, with trail road on top, bears N. and S.; desc. 250 ft. along N. [illegible] of [illegible] sl[illegible] W.

CHAINS	
79.74	The cor. of secs. 27, 28, 33 and 34. Land, rolling mountainous. Soil, clay loam. No timber. Undergrowth, sagebrush.
	N. 0° 18' W., bet. secs. 27 and 28. Over rolling mountainous land through dense sagebrush undergrowth.
0.20	Wash, 10 lks. wide, 2 ft. deep, drains W.; asc. 5 ft. over S. slope.
3.70	Small spur, slopes W.; desc. 25 ft. over N. slope.
9.20	Wash, drains W.; asc. 5 ft. over S. slope.
16.15	Small spur, slopes W.; desc. 30 ft. over N. slope.
19.02	Fence, bears E. and W.
19.30	Wash, drains SW.; asc. 20 ft. over SW. slope.
26.15	Top of ascent, slopes W.; desc. 135 ft. over NW. slope.
40.37	Point for the ¼ sec. cor. of secs. 27 and 28 at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T11N R6E ¼ S28 | S27 1964 Raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor. Desc. 30 ft. over NW. slope.
41.25	Improved gravel road to Randolph, bears NE. and SW.
41.50	Fence, parallel to road; enter cultivated land.
45.15	Old Canyon, with stream of water, 3 lks. wide, 1 ft. deep, flows NE.; asc. 50 ft. over gentle SE. slope.
60.40	Ditch, drains NE.
62.50	Leave cultivated land; enter sagebrush.
72.00	Spur, slopes NE.; desc. 40 ft. over NE. slope.
80.74	The orig. cor. of secs. 21, 22, 27 and 28, monumented with a sandstone, 14x10x8 ins., set, and mkd. as described in the official record. At the cor. point

CHAINS	of
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and brass cap mkd. T11N R6E S21 | S22 S28 | S27 1964 Bury original stone cor. alongside iron post. Cor. set at cor. of fence, with fence bearing E. and S. 5° W. Land, rolling. Soil, loam. No timber. Undergrowth, sagebrush.
	From the cor. of secs. 22, 23, 26 and 27. N. 89° 22' W., bet. secs. 22 and 27. Over rolling land through sagebrush undergrowth. Desc. 125 ft. over NW. slope.
6.00	Trail road, bears N. 20° W. and S. 20° E.
26.40	Draw, drains NW.; asc. 15 ft. over gentle NE. slope.
28.85	Spur, slopes NW.; desc. 40 ft. over NW. slope.
36.55	Improved gravel road to Randolph, bears NE. and SW.
36.65	Fence, parallel to road.
40.43	Point for the ¼ sec. cor. of secs. 22 and 27 at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T11N R6E ¼ S22 / S27 1964 Enter dense willows, bears NE. and SW.
42.85	Old Canyon, with stream of water, 5 lks. wide, 1 ft. deep, flows irregularly NE.
44.80	Leave willows; enter cultivated land.
60.45	Leave cultivated land; asc. 105 ft. over gentle NE. slope.
67.35	Wash, 20 lks. wide, 5 ft. deep, drains SE.
67.85	Canal, 10 lks. wide, 3 ft. deep, flows NE.

of the Subdi T. E.

CHAINS	
69.15	Cor. of fence, with fence bearing N. and W.; thence along fence line.
77.85	Wash, 15 lks. wide, 4 ft. deep, drains S. 80° E.
80.86	The cor. of secs. 21, 22, 27 and 28.
	Land, rolling. Soil, clay loam. No timber. Undergrowth, sagebrush, with willows along creek.
	N. 0° 02' E., bet. secs. 21 and 22.
	Over mountainous land through dense sagebrush undergrowth. Desc. 10 ft. over NE. slope.
0.30	Wash, drains E.
1.00	Wash, 15 lks. wide, 4 ft. deep, drains S. 85° E.; asc. 310 ft. over steep S. slope.
24.85	Spur, slopes E.; asc. 55 ft. over SE. slope.
35.70	Ridge, bears W. and NE.; desc. 10 ft. over NW. slope.
40.07	The orig. ¼ sec. cor. of secs. 21 and 22, monumented with a sandstone, 18x12x7 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T11N R6E ¼ S21 | S22 1964
	Bury original stone cor. alongside iron post, and raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor.
	N. 0° 18' W., beginning new measurement.
	Desc. 325 ft. over steep N. slope.
21.45	New Canyon, with stream of water, 5 lks. wide, 5 ins. deep, flows E.; asc. 100 ft. over S. slope.
23.00	Improved dirt road to Randolph, bears E. and W.
40.00	The orig. cor. of secs. 15, 16, 21 and 22, monumented with a washed boulder, 12x10x8 ins., set and mkd. as described in the official record.
	At the cor. point

CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone to top, with brass cap mkd.

T11N R6E

S16	S15
S21	S22

1964

Bury original stone cor. alongside iron post.

Land, mountainous.
Soil, clay loam.
No timber.
Undergrowth, dense sagebrush.

From the cor. of secs. 14, 15, 22 and 23.

N. 89° 34' W., bet. secs. 15 and 22.

Over rolling mountain land through dense sagebrush undergrowth. Asc. 50 ft. over E. slope.

12.25 Top of knoll; desc. 20 ft. over gentle SW. slope.

32.00 Wash, drains S.; asc. 30 ft. over SE. slope.

40.70 The orig. ¼ sec. cor. of secs. 15 and 22, monumented with a washed boulder, 14x6x4 ins., set and mkd. as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd.

T11N R6E

¼ S15 / S22

1964

Bury original stone cor. alongside iron post.

N. 89° 36' W., beginning new measurement.

Asc. 100 ft. over gentle SE. slope.

12.04 Wash, drains SE.

26.55 Fence, bears about N. 5° E. and S. 5° W.

39.96 The cor. of secs. 15, 16, 21 and 22.

Land, rolling.
Soil, clay loam.
No timber.
Undergrowth, dense sagebrush.

Dependent Resurvey of the Subdivision T. 11 N. R. 6 E.

CHAINS	
	N. 0° 17' W., bet. secs. 15 and 16.
	Over rolling land through dense sagebrush. Asc. 150 ft. over SE. slope.
35.50	Ridge, bears E. and W.; desc. 5 ft. over gentle N. slope.
40.35	The orig. ¼ sec. cor. of secs. 15 and 16, monumented with a limestone, 16x10x5 ins., set and mks. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T11N R6E ¼ S16 | S15 1964
	Bury original stone cor. alongside iron post.
	N. 0° 05' E., beginning new measurement.
	Desc. 110 ft. over N. slope.
18.70	Draw, drains E.; asc. 15 ft. over S. slope.
22.75	Low spur, slopes E.; desc. 25 ft. over N. slope.
26.80	Wash, drains E.; asc. 15 ft. over S. slope.
30.40	Low spur, slopes E.; desc. 50 ft. over NE. slope.
37.30	Wash, drains E.; asc. 15 ft. over SE. slope.
40.24	The orig. cor. of secs. 9, 10, 15 and 16, monumented with a sandstone, 16x8x6 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T11N R6E S9 | S10 S16 | S15 1964
	Bury original stone cor. alongside iron post.
	Land, rolling. Soil, clay loam. No timber. Undergrowth, dense sagebrush.
	From the cor. of secs. 10, 11, 14 and 15.
	N. 89° 35' W., bet. secs. 10 and 15.

Dependent Resurvey of the Subdivision, T. 11 N., R. 6 E.

CHAINS	
	Over gently rolling land through dense sagebrush undergrowth. Desc. 30 ft. along gentle N. slope.
40.22	The orig. ¼ sec. cor. of secs. 10 and 15, monumented with a sandstone, 14x10x4 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T11N R6E ¼ S10/S15 1964
	Bury original stone cor. alongside iron post; and raise a mound of stone, 2½ ft. base, 1½ ft. high, N. of cor.
	N. 89° 41' W., beginning new measurement.
	Asc. 110 ft. over SE. slope.
23.40	Wash, drains SE.
27.35	Wash, drains SE.
40.19	The cor. of secs. 9, 10, 15 and 16.
	Land, rolling. Soil, loam. No timber. Undergrowth, dense sagebrush.
	N. 0° 24' E., bet. secs. 9 and 10.
	Over mountainous land through dense sagebrush. Asc. 50 ft. over SE. slope.
6.65	Ridge, bears E. and W.; desc. 145 ft. over steep N. slope.
17.00	South branch of Middle Fork Canyon, stream of water, 5 lks. wide, 3 ins. deep, flows E.; asc. 115 ft. over S. slope.
18.15	Trail road, bears E. and W.
33.80	Ridge, bears E. and W.; desc. 25 ft. over N. slope.
40.12	The orig. ¼ sec. cor. of secs. 9 and 10, monumented with a sandstone, 14x14x4 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T11N R 6E ¼ S9 | S10 1964

Dependent Resurvey of the Subdi[illegible] T. 11 N. R. 6 E.

CHAINS	
	Bury original stone cor. alongside iron post.
	N. 0° 05' E., beginning new measurement.
	Desc. 5 ft. over N. slope.
0.85	Wash, drains E.; asc. 60 ft. over SE. slope.
10.50	Spur, slopes E.; desc. 20 ft. over N. slope.
14.45	Small draw, drains E.; asc. 20 ft. over S. slope.
18.20	Spur, slopes NE.; desc. 20 ft. over NW. slope.
24.00	Small draw, drains E.; asc. 20 ft. over S. slope.
31.05	Ridge, bears E. and W.; desc. 100 ft. over steep N. slope
40.07	The orig. cor. of secs. 3, 4, 9 and 10, monumented with a sandstone, 19x11x6 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T11N R6E S4 | S3 S9 | S10 1964
	Bury original stone cor. alongside iron post, and raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of cor.
	Land, mountainous. Soil, rocky loam. No timber. Undergrowth, dense sagebrush.
	From the cor. of secs. 2, 3, 10 and 11.
	N. 89° 40' W., bet. secs. 3 and 10.
	Over rolling land through dense sagebrush. Desc. 20 ft. over SW. slope.
8.85	Middle Fork Canyon, with stream of water, 5 lks. wide, 2 ft. deep, flows irregularly SE.; asc. 95 ft. over NE. slope.
37.00	Spur, slopes NW.; desc. 40 ft. over W. slope.
39.92	Point for the ¼ sec. cor. of secs. 3 and 10 at proportionate dist.; there is no remaining evidence of the original cor.

Dependent [illegible] of the Subdivision T [illegible] N [illegible]

CHAINS	
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in cement, with brass cap mkd. T11N R6E ¼ S3 / S10 1964 Raise a mound of stone, 2½ ft. base, 1½ ft. high, N. of cor.
40.05	Trail road, bears N. and S.
41.00	Wash, drains N.; desc. 15 ft. along N. slope.
49.40	Wash, drains N.; asc. 50 ft. along N. slope.
71.15	Wash, drains N.
79.84	The cor. of secs. 3, 4, 9 and 10. Land, rolling. Soil, rocky clay loam. No timber. Undergrowth, dense sagebrush.
	N. 0° 11' E., bet. secs. 3 and 4. Over rolling mountainous land through dense sagebrush undergrowth. Desc. 65 ft. over N. slope.
10.40	Middle Fork Canyon, with stream of water, 5 lks. wide, 6 ins. deep, flows E.; spring bears W. about 4.00 chs. dist. Asc. 240 ft. over S. slope.
13.05	Trail road, bears E. and W.
39.94	The orig. ¼ sec. cor. of secs. 3 and 4, monumented with a sandstone, 14x6x3 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd. T11N R6E ¼ S4 | S3 1964 Bury original stone cor. alongside iron post.
	N. 2° 03' E., beginning new measurement. Asc. 5 ft. over S. slope.
2.60	[illegible]ur, slopes E.; desc. 10 ft. over N. slope.

CHAINS	
5.80	Wash, drains E.; asc. 20 ft. over S. slope.
11.40	Ridge, bears E. and W.; desc. 205 ft. over NW. slope.
32.00	Wash, drains NE.; asc. 20 ft. over SE. slope.
41.25	The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the 1964 field notes of T. 12 N., R. 6 E. Land, rolling mountainous. Soil, rocky clay loam. No timber. Undergrowth, dense sagebrush.
	From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp. N. 0° 47' W., bet. secs. 32 and 33. Over rolling mountainous land through dense sagebrush undergrowth. Desc. 190 ft. over N. slope.
3.00	Fence, bears about N. 1° W. and S. 1° E., thence along E. side of fence.
17.15	Wash, in Old Canyon, drains N. 75° E.; asc. 150 ft. over S. slope.
20.60	Improved dirt road to Randolph, bears about N. 55° E. and curves W.
39.51	Point for the ¼ sec. cor. of secs. 32 and 33 at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T11N R6E ¼ S32 | S33 1964 Cor. is situated 12 lks. E. of N. and S. fence line. Asc. 10 ft. oversouth slope.
42.50	Spur, slopes E.; desc. 135 ft. over N. slope.
54.25	Draw, drains E.; asc. 75 ft. over S. slope.
64.40	Spur, slopes NE.; desc. 80 ft. over NE. slope.
79.02	The orig. cor. of secs. 28, 29, 32 and 33, monumented with a sandstone, 16x10x8 ins., set and mkd. as described in the official record. At the cor. point

. De ende t Resurve of the Subdivision T 11 N R

CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T11N R6E

S29	S28
S32	S33

1964

Bury original stone cor. alongside iron post.

Cor. is situated 31 lks. E. of N. and S. fence line.

Land, mountainous.
Soil, clay loam.
No timber.
Undergrowth, dense sagebrush.

From the cor. of secs. 27, 28, 33 and 34.

S. 89° 30' W., bet. secs. 28 and 33.

Over mountainous land through dense sagebrush undergrowth Desc. 150 ft. over NW. slope.

20.65 Wash in Old Canyon, drains N. 30° W.; asc. 120 ft. over SE. slope.

24.95 Improved dirt road to Randolph, bears about N. 30° E. and S. 30° W.

39.87 Point for the ¼ sec. cor. of secs. 28 and 33 at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and brass cap mkd.

T11N R6E

¼ S28 / S33

1964

Raise a mound of stone, 3 ft. base, 1½ ft. high, N. of cor.

Asc. 95 ft. over SE. slope.

59.40 Spur, slopes NE.; desc. 60 ft. over NW. slope.

70.20 Draw, drains N. 30° W.; asc. 20 ft. over NE. slope.

79.74 The cor. of secs. 28, 29, 32 and 33.

Land, mountainous.
Soil, clay loam.
No timber.
Undergrowth, dense sagebrush.

N. 0° 18' E., bet. secs. 28 and 29.

CHAINS	
	Over mountainous land through dense sagebrush un Desc. 75 ft. over NE. slope; along E. side of wire fence which gradually diverges to W.
8.40	Pole Canyon, with stream of water, 3 lks. wide, 4 ins. deep, flows N. 80° E.; asc. 200 ft. over SE. slope. Spring bears W. 2.00 chs. dist.
22.10	Trail road, bears about N. 40° E. and S. 40° W.
36.45	Top of ascent, slopes E.; enter aspen timber; desc. 25 ft over NE. slope.
40.24	The orig. ¼ sec. cor. of secs. 28 and 29, monumented with a sandstone, 14x12x3 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T11N R6E ¼ S29 | S28 1964
	Bury original stone cor. alongside iron post.
	N. 0° 31' E., beginning new measurement.
	Desc. 170 ft. over steep NE. slope.
8.00	Leave timber, bears NW. and SE.
18.30	Wash, in bottom of canyon, drains E.; spring bears E. 4.00 chs. dist.; asc. 230 ft. over steep S. slope.
19.00	Trail road, bears E. and W.
20.34	Fence, bears E. and W. 1.50 chs. to N. and S. fence line.
37.00	Ridge, bears E. and W.; desc. 30 ft. over NE. slope; enter aspen timber, bears NW. and SE.
40.30	Point for the cor. of secs. 20, 21, 28 and 29 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T11N R6E S20 | S21 S29 | S28 1964
	Cor. set in W. edge of aspen timber.

t Reserve of

CHAINS

Land, mountainous.
Soil, rocky loam.
Timber, aspen.
Undergrowth, dense sagebrush.

From the cor. of secs. 21, 22, 27 and 28.

S. 88° 12' W., bet. secs. 21 and 28.

Over rolling land through dense sagebrush. Asc. 180 ft. over NE. slope.

21.00 Small wash, drains NE.

38.97 The orig. ¼ sec. cor. of secs. 21 and 28, monumented with a broken sandstone, 13x8x3 ins., set as described in the official record, but dimly marked.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T11N R6E

¼ S21/S28

1964

Bury original stone cor. alongside iron post.

N. 89° 20' W., beginning new measurement.

Asc. 20 ft. over NE. slope.

3.45 Low ridge, bears NW. and SE.; desc. 55 ft. over W. slope.

18.05 Trail road, in shallow draw, bears irregularly N. and S.; asc. 225 ft. over E. slope.

38.00 Enter aspen timber.

39.35 Leave timber.

39.65 The cor. of secs. 20, 21, 28 and 29.

Land, rolling E. portion; mountainous W. portion.
Soil, rocky loam.
Timber, aspen in extreme W. portion; no timber E. portion.
Undergrowth, dense sagebrush.

N. 0° 08' E., bet. secs. 20 and 21.

Over mountainous land through aspen timber and sagebrush undergrowth. Desc. 75 ft. over NE. slope.

10.00 Wash, drains SE.; asc. 25 ft. over SW. slope.

12.00 Leave timber.

Dependent Resurvey of the Subdivision T. 11 N. R. 6 E.

CHAINS	
20.10	Spur, slopes E.; desc. 115 ft. over NE. slope.
36.00	Slope changes; desc. 15 ft. over NW. slope.
40.30	Point for the ¼ sec. cor. of secs. 20 and 21 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T11N R6E. ¼ S20 | S21 1964
	Raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor.
	Desc. 35 ft. over NW. slope.
44.25	Trail road, bears NW. and SE.
48.90	Wash, drains NW.; asc. 15 ft. over SW. slope.
51.60	Small spur, slopes NW.; desc. 60 ft. over NW. slope.
59.00	Wash, in New Canyon, drains E.; asc. 30 ft. over S. slope.
60.90	Improved dirt road to Randolph, bears about N. 60° E. and S. 60° W.
69.20	Wash, drains SE.
73.05	Trail road, on small spur, bears E. curving S., and W. curving N.; desc. 15 ft. over N. slope.
80.60	Point for the cor. of secs. 16, 17, 20 and 21 at proportionate dist.;
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and brass cap mkd.
	T11N R6E S17 | S16 S20 | S21 1964
	Raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor.
	The original cor. was found N. 76° 17' W., 2.15 chs. dist., and was lying in a sagebrush. According to Fred Jewkes, a Bureau of Land Management employee in this area for several years, this cor. has been moved several times, and was not accepted as being at the original cor. point. I bury the original cor. alongside the iron post.
	Land, rolling and mountainous. Soil, clay loam. Timber, aspen in S. portion; no timber N. portion. Undergrowth, sagebrush.

Dependent Resurvey of the Subdivision T. 11 N. R. 6 E.

CHAINS

From the cor. of secs. 15, 16, 21 and 22.

S. 89° 45' W., bet. secs. 16 and 21.

Over mountainous land through dense sagebrush undergrowth
Asc. 10 ft. over SE. slope.

6.00 Top of ascent, slopes S.; desc. 30 ft. over SW. slope.

12.40 Draw, drains S.; asc. 105 ft. over SE. slope.

28.20 Spur, slopes S.; desc. 20 ft. over SW. slope.

31.30 Head of draw, drains S.; asc. 90 ft. over SE. slope.

39.12 Point for the ¼ sec. cor. of secs. 16 and 21 at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T11N R6E

¼ S16/S21

1964

Asc. 10 ft. over SE. slope.

42.75 Spur, slopes S.; desc. 155 ft. over W. slope.

52.65 Draw, drains S.; asc. 40 ft. over E. slope.

63.80 Asc. 10 ft. along N. slope.

78.24 The cor. of secs. 16, 17, 20 and 21.

Land, mountainous.
Soil, rocky clay loam.
No timber.
Undergrowth, sagebrush.

N. 0° 36' E., bet. secs. 16 and 17.

Over rolling land through dense sagebrush undergrowth.
Asc. 25 ft. over gently rolling SE. slope.

18.50 Small spur, slopes SE.; desc. 15 ft. over NE. slope.

22.90 ash, drains N. 60° E.; asc. 35 ft. over SE. slope.

32.50 Small spur, slopes E.; desc. 10 ft. over NE. slope.

40.30 Point for the ¼ sec. cor. of secs. 16 and 17 at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T11N R6E

¼

S17 | S16

1964

Dependent Resurvey of the Subdivision. T. 11 N. R. 6 E.

CHAINS	
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor
	Desc. 10 ft. over NE. slope.
46.50	Wash, drains SE.; asc. 45 ft. over SE. slope.
62.90	Small spur, slopes E.; desc. 55 ft. over NW. slope.
78.35	Cor. of fence, with fence bearing about S. 3° W. and N.; thence along fence line.
80.60	The orig. cor. of secs. 8, 9, 16 and 17, monumented with a sandstone, 10x8x6 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T11N R6E S8 | S9 S17 | S16 1964
	Bury original stone cor. alongside iron post.
	Land, rolling. Soil, loam. No timber. Undergrowth, sagebrush.
	From the cor. of secs. 9, 10, 15 and 16.
	S. 89° 49' W., bet. secs. 9 and 16.
	Over rolling mountain land through dense sagebrush undergrowth. Asc. 140 ft. over SE. slope.
12.50	Ridge, bears NE. and SW.; desc. 70 ft. over NW. slope.
38.62	Point for the ¼ sec. cor. of secs. 9 and 16 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T11N R6E ¼ S9 S16 1964
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
	Cor. set in small draw, drains S.
	Desc. 15 ft. over gentle SW. slope.
51.30	Wash, drains NW.; asc. 110 ft. over NE. slope.
65.05	Point of spur, slopes NW.; desc. 100 ft. over SW. slope.
70.50	Wash, drains NW.; asc. 20 ft. over NE. slope.
77.24	The cor. of secs. 8, 9, 16 and 17.
	Land, mountainous. Soil, rocky loam. No timber. Undergrowth, dense sagebrush.

Dependent Resurvey of the Subdivision T. 11 N. R. 6 E.

CHAINS

N. 0° 05' E., bet. secs. 8 and 9.

Over rolling mountainous land through dense sagebrush. Desc. 15 ft. over N. slope, and along fence line.

4.00 Wash, drains E.; asc. 10 ft. over S. slope.

9.00 Small spur, slopes E.; desc. 30 ft. over N. slope.

20.85 South branch of Middle Fork, stream of water, 4 lks. wide 3 ins. deep, flows E. A spring bears W. 3.00 chs. dist.; asc. 220 ft. over steep S. slope.

30.00 End steep ascent; asc. 15 ft. over gentle S. slope.

40.18 Point for the ¼ sec. cor. of secs. 8 and 9 at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T11N R6E
¼
S8 | S9
1964

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Cor. set on spur, slopes E., 15 lks. E. of N. and S. fence line.

Desc. 130 ft. over steep N. slope.

48.90 Wash, drains E.; asc. 30 ft. over S. slope.

61.40 Saddle, bet. two knolls, bears E. and W.; desc. 75 ft. over NW. slope.

80.36 The orig. cor. of secs. 4, 5, 8 and 9, monumented with a sandstone, 12x8x4 ins., set and mkd. as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T11N R6E

S5 | S4
S8 | S9
1964

Bury original stone cor. alongside iron post.

Cor. set. in N. and S. fence line.

Land, rolling mountainous.
Soil, rocky clay loam.
No timber.
Undergrowth, dense sagebrush.

From the cor. of secs. 3, 4, 9 and 10.

S. 89° 37' W., bet. secs. 4 and 9.

Over rolling N. slope of ridge, through dense sagebrush undergrowth. Along N. slope.

12.00 Asc. 55 ft. over NE. slope.

17.90 Spur, slopes N.; desc. 35 ft. over NW. slope.

25.00 Bottom of descent, slopes N.; thence along N. slope.

Dependent Resurvey of the Subdivision, T. 11 N. R. 6 E.

CHAINS	
37.26	The orig. ¼ sec. cor. of secs. 4 and 9, monumented with a sandstone, 20x9x5 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T11N R6E ¼ S4 / S9 1964 Bury original stone cor. alongside iron post, and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
	N. 89° 56' W., beginning new measurement.
	Asc. 80 ft. along N. slope.
25.00	Spur, slopes NE.; desc. 25 ft. over NW. slope.
36.80	Wash, drains NE.; asc. 15 ft. over NE. slope.
40.12	The cor. of secs. 4, 5, 8 and 9.
	Land, rolling. Soil, rocky clay loam. No timber. Undergrowth, sagebrush.
	N. 1° 01' W., bet. secs. 4 and 5.
	Over rolling land through dense sagebrush undergrowth., and along fence line.
5.00	Wash, drains E.
14.40	Spur, slopes E.
19.10	Wash, drains E.
22.50	Cor. of fence, with fence bearing about S. 86° E.; leave fence line.
30.20	Trail road, bears about N. 85° E. and S. 85° W.; asc. 30 ft. over gentle SW. slope. Spring and stock pond bears S. 80° E. about 15.00 chs. dist.
41.00	Wash, drains S. 10° E., from W.
41.15	Point for the ¼ sec. cor. of secs. 4 and 5 at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T11N R6E ¼ S5 | S4 1964
	Asc. 175 ft. over SW. slope.
41.70	Cor. of fence, bears E. 60 lks. dist., with fence bearing SE. and about N. 2- E.
61.20	Ridge, bears E. and W.; desc. 140 ft. over NE. slope.

Dependent Resurvey of the Subdivision T. 11 N. R. 6 E

CHAINS

81.78 The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the 1964 field notes of T. 12 N., R. 6 E.

Land, rolling.
Soil, clay loam.
No timber.
Undergrowth, sagebrush.

From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp.

N. 0° 05' W., bet. secs. 31 and 32.

Over mountainous land through dense sagebrush undergrowth
Desc. 10 ft. over NE. slope.

2.30 Wash, drains SE.; asc. 220 ft. over SW. slope.

36.30 Ridge, bears NW. and SE.; desc. 15 ft. over NE. slope.

40.24 The orig. ¼ sec. cor. of secs. 31 and 32, monumented with a sandstone, 16x10x3 ins., set and mkd. as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T11N R6E
¼
S31 | S32

1964

Bury original stone cor. alongside iron post.

N. 0° 26' E., beginning new measurement.

Desc. 10 ft. over NE. slope.

4.60 Wash, drains SE.; asc. 115 ft. over SW. slope.

25.00 Ridge, bears NW. and SE.; desc. 200 ft. over NE. slope.

39.97 The orig. cor. of secs. 29, 30, 31 and 32, monumented with a sandstone, 15x12x6 ins., set and mkd. as described in the official record.

t the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T11N R6E

S30	S29
S31	S32

1964

Bury original stone cor. alongside iron post.

Land, mountainous.
Soil, rocky clay loam.
No timber.
Undergrowth, sagebrush.

From the cor. of secs. 28, 29, 32 and 33.

Dependent Resurvey of the Subdivision, T. 11 N., R. 6 E.

CHAINS	
	N. 89° 47' W., bet. secs. 29 and 32.
	Over rolling mountainous land through dense sagebrush undergrowth. Asc. 150 ft. over NE. slope.
0.31	Fence, bears about N. and S.
40.04	Point for the ¼ sec. cor. of secs. 29 and 32 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T11N R6E ¼ S29 / S32 1964
	Asc. 15 ft. over NE. slope; enter scattered service berry undergrowth.
48.90	Small spur, slopes N.; desc. 30 ft. over NW. slope.
54.40	Wash, drains N. 10° W.; asc. 45 ft. over NE. slope.
62.00	Small spur, slopes N.; desc. 15 ft. over NW. slope.
80.08	The cor. of secs. 29, 30, 31 and 32.
	Land, rolling. Soil, rocky loam. No timber. Undergrowth, sagebrush and service berry.
	N. 89° 43' W., bet. secs. 30 and 31.
	Over rolling mountainous land through dense sagebrush and service berry undergrowth. Asc. 25 ft. over NE. slope.
3.00	Enter aspen timber, bears N. and S.
5.50	Leave timber, bears N. and S.
11.45	Small spur, slopes N.; desc. 30 ft. over gentle NW. slope.
20.00	Draw in Pole Canyon, draws NE.
25.25	Trail road, bears N. 75° E. and S. 75° W. curving W.; asc. 55 ft. over SE. slope.
40.22	Point for the ¼ sec. cor. of secs. 30 and 31 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with brass cap mkd. T11N R6E ¼ S30 / S31 1964
	Asc. 10 ft. over SE. slope.
43.10	Small spur, slopes SW.; desc. 50 ft. over SW. slope.
50.40	Draw, with trail road in bottom, drains SE.; asc. 130 ft. over NE. slope.
58.60	Spur, slopes S. 75° E.; desc. 30 ft. along S. slope.

Dependent Resurvey of the Subdivision, T. 11 N., R. 6 E.

CHAINS

79.83 The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp.

Land, rolling mountainous.
Soil, rocky clay loam.
Timber, scattered aspen.
Undergrowth, sagebrush and service berry.

From the cor. of secs. 29, 30, 31 and 32.

N. 0° 39' E., bet. secs. 29 and 30.

Over mountainous land through dense sagebrush and service berry undergrowth. Desc. 70 ft. over N. slope.

2.80 Pole Canyon, drains E.

3.05 Trail road, bears irregularly E. and W.; asc. 240 ft. over steep S. slope.

17.00 Ridge, bears E. and W.; desc. 145 ft. over N. slope.

20.60 Enter aspen timber, bears E. and W.

23.50 Leave timber.

31.30 End steep descent, thence over gently rolling land.

35.00 Small spur, slopes E.; desc. 30 ft. over gentle N. slope.

40.16 Point for the ¼ sec. cor. of secs. 29 and 30 at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and brass cap mkd.

T11N R6E
¼
S30 | S29

1964

Raise a mound of stone, 3 ft. base, 1½ ft. high, W. of Cor.

Cor. located about 70 lks. W. of trail road.

Desc. 10 ft. over gentle N. slope.

41.50 Trail road, bears about N. 10° W. and S. 10° E.

49.70 Trail road, bears about N. 75° W. and S. 75° E.

50.00 Wash, drains E.; asc. 55 ft. over gently rolling S. slope.

69.60 Wash, drains N. 70° E.; asc. 35 ft. over gentle SE. slope.

80.32 The orig. cor. of secs. 19, 20, 29 and 30, monumented wit a sandstone, 24x8x4 ins., set and mkd. as described in th official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.

T11N R6E

S19 | S20
S30 | S29

1964

Bury original stone cor. alongside iron post.

Dependent Resurvey of the Subdivision, T. 11 N., R. 6 E.

CHAINS	
	Land, mountainous S. portion; rolling N. portion. Soil, clay loam. Timber, aspen. Undergrowth, sagebrush and service berry.
	From the cor. of secs. 20, 21, 28 and 29.
	S. 88° 04' W., bet. secs. 20 and 29.
	Over mountainous land through sagebrush and service berry undergrowth. Asc. 50 ft. over steep E. slope.
2.38	Fence, bears about N. and S.; asc. 30 ft. over gentle E. slope.
13.80	Ridge, bears N. and S.; desc. 170 ft. over NW. slope.
35.50	Wash, drains SW.; asc. 10 ft. over SE. slope.
39.52	The orig. ¼ sec. cor. of secs. 20 and 29, monumented with a sandstone, 14x6x4 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd. T11N R6E ¼ S20 / S29 1964
	Bury original stone cor. alongside iron post.
	Cor. set on small spur, slopes SW.
	N. 88° 02' W., beginning new measurement.
	Desc. 20 ft. over SW. slope.
5.25	Trail road, in draw, drains S. 70° E.; asc. 90 ft. over gentle NE. slope.
32.25	Small spur, slopes S.; desc. 15 ft. over SW. slope.
33.10	Wash, drains SE.; asc. 50 ft. over E. slope.
40.24	The cor. of secs. 19, 20, 29 and 30.
	Land, rolling mountainous. Soil, rocky loam. No timber. Undergrowth, sagebrush and service berry.
	S. 89° 59' W., bet. secs. 19 and 30.
	Over rolling mountainous land through dense sagebrush undergrowth. Asc. 210 ft. over E. slope.
39.80	The orig. ¼ sec. cor. of secs. 19 and 30, monumented with a washed boulder, 14x8x8 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd.

Dependent Resurvey of the Subdivision, T. 11 N., R. 6 E.

CHAINS

T11N R6E

¼ S19 / S30

1964

Bury original stone cor. alongside iron post.

S. 89° 58' W., beginning new measurement.

Asc. 360 ft. over NE. slope.

10.50 Small wash, drains S. 20° E.

17.40 Wash, drains NE.

25.00 Enter aspen timber.

32.00 Spur, slopes SE.; leave timber; desc. 10 ft. over gentle SW. slope.

40.03 The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp.

Land, rolling mountainous.
Soil, rocky loam.
Timber, aspen in W. portion.
Undergrowth, sagebrush.

From the cor. of secs. 19, 20, 29 and 30.

N. 0° 49' E., bet. secs. 19 and 20.

Over rolling mountainous land through sagebrush undergrowth. Asc. 115 ft. over SW. slope.

20.00 Ridge, bears NW. and SE.; desc. 115 ft. over NE. slope. Enter aspen timber.

40.27 The orig. ¼ sec. cor. of secs. 19 and 20, monumented with a sandstone, 12x12x5 ins., set and mkd. as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground with glass at base, and in a collar of stone, with brass cap mkd.

T11N R6E

¼

S19 | S20

1964

Bury original stone cor. alongside iron post.

N. 0° 52' E., beginning new measurement.

Desc. 75 ft. over NE. slope.

6.00 Drain in New Canyon, drains E.

7.60 Improved dirt road, bears irregularly E. and W.; asc. 100 ft. over S. slope. Leave aspen timber.

12.70 Spur, slopes SE.; desc. 50 ft. over NE. slope.

17.00 Draw, drains SE.; asc. 300 ft. over steep SW. slope.

35.80 Rim of ridge, curves N. and bears SE.; asc. 15 ft. over gentle SE. slope.

Dependent Resurvey of the Subdivision, T. 11 N., R. 6 E.

CHAINS	
39.78	The orig. cor. of secs. 17, 18, 19 and 20, monumented with a sandstone, 16x10x8 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone to top, with brass cap mkd. T11N R6E S18 | S17 S19 | S20 1964 Bury original stone cor. alongside iron post. Land, mountainous. Soil, rocky clay loam. Timber, aspen. Undergrowth, sagebrush and service berry.
	From the cor. of secs. 16, 17, 20 and 21. S. 89° 37' W., bet. secs. 17 and 20. Over rolling land through dense sagebrush undergrowth. Asc. 45 ft. over gentle E. slope.
3.40	Trail road, bears N. and S.
3.54	Fence, bears N. and S.
16.55	Fence, bears about N., and S. about 4.00 chs., thence E.
29.70	Wash, drains SE.; asc. 25 ft. over NE. slope.
39.03	The orig. ¼ sec. cor. of secs. 17 and 20, monumented with a sandstone, 11x8x4 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T11N R6E ¼ S17 S20 1964 Bury original stone cor. alongside iron post.
	S. 89° 42' W., beginning new measurement. By triangulation, asc. about 300 ft. over NE. slope. Enter dense aspen timber and service berry undergrowth.
28.00	Leave timber.
30.01	End triangulation; fence bears SE. and NW. Asc. 35 ft. over gentle SE. slope.
39.72	The cor. of secs. 17, 18, 19 and 20. Land, rolling E. portion; mountainous W. portion. Soil, rocky clay loam. Timber, aspen. Undergrowth, sagebrush and service berry.
	S. 89° 20' W., bet. secs. 18 and 19.

Dependent Resurve of the Subdivision T. 11 N. R 6 E

CHAINS

Over mountainous land through sagebrush undergrowth. Asc. 10 ft. over gentle SE. slope.

3.00 Top of ascent, bears NW. and SE.; desc. 200 ft. over SW. slope.

21.15 Draw, drains SE.; asc. 220 ft. over NE. slope.

40.87 Point for the ¼ sec. cor. of secs. 18 and 19 at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and brass cap mkd.

T11N R6E

¼ S18/S19

1964

Raise a mound of stone, 3 ft. base, 1½ ft. high, N. of cor.

Asc. 255 ft. over NE. slope.

73.90 Ridge, bears NW. and SE.; desc. 70 ft. over SW. slope.

80.40 The cor. of secs. 18 and 19, on the W. bdy. of the Tp.

Land, mountainous.
Soil, rocky loam.
No timber.
Undergrowth, sagebrush.

From the cor. of secs. 17, 18, 19 and 20.

N 0° 09' E., bet. secs. 17 and 18.

Over mountainous land through sagebrush and scattered service berry undergrowth. Asc. 40 ft. over gentle SE. slope.

16.50 Ridge, bears NE. and SW.; desc. 15 ft. over gentle NW. slope.

23.00 Wash, drains NE., asc. 10 ft. over SE. slope.

31.30 Small spur, slopes E.; desc. 105 ft. over NE. slope.

34.60 Enter dense aspen timber, bears NW. and SE.

40.11 The orig. ¼ sec. cor. of secs. 17 and 18, monumented with a broken sandstone, 12x8x4 ins., set and mkd. as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T11N R6E

¼

S18|S17

1964

from which

An aspen, 4 ins. diam., bears S. 24° E., 12 lks. dist., mkd. ¼ S17 BT.

No other suitable bearing trees available.

CHAINS	
	Bury original stone cor. alongside iron post.
	N. 0° 15' W., beginning new measurement.
	By triangulation, desc. about 200 ft. over NE. slope.
15.00	Trail road, bears NW. and SE.; leave timber, bears NW. and SE.
17.00	Wash, drains E.; asc. about 30 ft. over gentle SE. slope.
40.07	The orig. cor. of secs. 7, 8, 17 and 18, monumented with a sandstone, 26x8x5 ins., set and mkd. as described in the official record. End triangulation.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone to top, with brass cap mkd.
	T11N R6E S7 | S8 S18 | S17 1964
	Bury original stone cor. alongside iron post.
	Land, mountainous. Soil, rocky clay loam. Timber, aspen. Undergrowth, sagebrush and service berry.
	From the cor. of secs. 8, 9, 16 and 17.
	S. 87° 28' W., bet. secs. 8 and 17.
	Over rolling mountain land through sagebrush undergrowth. Asc. 15 ft. over NE. slope.
5.10	Small spur, slopes NE.; desc. 15 ft. over NW. slope.
15.90	Draw, drains NE.; asc. 130 ft. over SE. slope.
39.25	The orig. ¼ sec. cor. of secs. 8 and 17, monumented with a sandstone, 12x10x5 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T11N R6E ¼ S8 / S17 1964

Dependent Resurvey of the Subdivision T. 11 N. R 6 E.

CHAINS

Bury original stone cor. alongside iron post, and raise a mound of stone, 3½ ft. base, 2½ ft. high, N. of cor.

N. 88° 57' W., beginning new measurement.

Asc. 145 ft. over SE. slope.

12.75 Trail road, bears NE. and SW.

40.43 The cor. of secs. 7, 8, 17 and 18.

Land, rolling.
Soil, clay loam.
No timber.
Undergrowth, sagebrush.

S. 86° 53' W., bet. secs. 7 and 18.

Over rolling land through dense sagebrush. Asc. 230 ft. over NE. slope.

26.80 Trail road, bears NW. and SE.

39.81 The orig. ¼ sec. cor. of secs. 7 and 18, monumented with a sandstone, 12x6x4 ins., set and mkd. as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T11N R6E

¼ S7/S18

1964

Bury original stone cor. alongside iron post.

N. 89° 15' W., beginning new measurement.

Asc. 280 ft. over NE. slope.

16.00 Enter aspen timber.

28.55 Spur, slopes N.; desc. 40 ft. over NW. slope. Leave timber.

38.06 The cor. of secs. 7 and 18, on the W. bdy. of the Tp.

Land, rolling mountainous.
Soil, rocky clay loam.
Timber, aspen W. portion; no timber E. portion.
Undergrowth, sagebrush and service berry.

From the cor. of secs. 7, 8, 17 and 18.

N. 0° 27' E., bet. secs. 7 and 8.

CHAINS	
	Over rolling mountainous land through dense sagebrush undergrowth. Asc. 30 ft. over S. slope.
8.00	Ridge, bears E. and W.; desc. 90 ft. over N. slope.
10.05	Trail road, bears E. and W.
17.40	Draw, drains E.; asc. 40 ft. over SE. slope.
22.00	Point of spur, slopes E.; desc. 65 ft. over NE. slope.
26.30	Draw in head of South Branch Middle Fork Canyon, drains S. 85° E.; asc. 80 ft. over SW. slope.
27.60	Trail road, bears S. 85° E. and N. 85° W.
34.25	Spur, slopes SE.; desc. 25 ft. over NE. slope.
38.60	Small wash, drains SE.; asc. 10 ft. over SE. slope.
39.87	The orig. ¼ sec. cor. of secs. 7 and 8, monumented with a sandstone, 15x10x6 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd. T11N R6E ¼ S7|S8 1964 Bury original stone cor. alongside iron post.
	N. 0° 37' E., beginning new measurement. Asc. 15 ft. over SE. slope.
3.00	Ridge, bears E. and W.; desc. 30 ft. over N. slope.
12.20	Wash, drains E.; asc. 20 ft. over S. slope.
14.00	Low spur, slopes E.; desc. 15 ft. over NE. slope.
15.25	Wash, drains E. 2.00 chs. thence SE.; asc. 70 ft. over SE. slope.
31.70	Ridge, bears NE. and SW.; desc. 110 ft. over NW. slope.
40.06	The orig. cor. of secs. 5, 6, 7 and 8, monumented with a sandstone, 12x10x8 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T11N R6E S6|S5 S7|S8 1964

Dependent Resurvey of the Subdivision, T. 11 N., R. 6 E.

CHAINS	
	Bury original stone cor. alongside iron post, and raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor. Land, rolling mountainous. Soil, rocky loam. No timber. Undergrowth, sagebrush.
	From the cor. of secs. 4, 5, 8 and 9. S. 87° 27' W., bet. secs. 5 and 8. Over rolling mountainous land through sagebrush undergrowth. Asc. 110 ft. over gentle NE. slope.
39.08	The orig. ¼ sec. cor. of secs. 5 and 8, monumented with a sandstone, 12x10x8 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T11N R6E ¼ S5/S8 1964 Bury original stone cor. alongside iron post, and raise a mound of stone, 3 ft. base, 1½ ft. high, N. of cor. N. 89° 40' W., beginning new measurement. Asc. 185 ft. over gentle NE. slope.
25.65	Small spur, slopes N.; thence along N. slope. Enter dense service berry undergrowth.
34.65	Desc. 40 ft. over NW. slope.
39.97	The cor. of secs. 5, 6, 7 and 8. Land, rolling mountainous. Soil, loam. No timber. Undergrowth, sagebrush and service berry.
	S. 88° 46' W., bet. secs. 6 and 7. Over rolling mountain land through sagebrush and service berry undergrowth. Desc. 20 ft. over NW. slope.
1.75	Wash, drains NE.; asc. 170 ft. along N. slope.
23.75	Trail road, bears SE. and NW., curving N. and then E. Enter aspen timber.
40.26	Point for the ¼ sec. cor. of secs. 6 and 7 at proportionate dist.; there is no remaining evidence of the original Cor.

CHAINS	
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T11N R6E ¼ S6/S7 1964
	Desc. 45 ft. over gentle NW. slope.
48.75	Wash, drains NE.; asc. 235 ft. along N. slope.
75.00	Leave timber, bears SE. and curves W.
77.75	The cor. of secs. 6 and 7, on the W. bdy. of the Tp.
	Land, rolling mountainous. Soil, rocky loam. Timber, aspen. Undergrowth, sagebrush and service berry.
	From the cor. of secs. 5, 6, 7 and 8.
	N. 1° 41' W., bet. secs. 5 and 6.
	Over mountainous land through sagebrush and service berry undergrowth. Desc. 40 ft. over NW. slope.
1.50	Trail road, bears E. and W., in Middle Fork Canyon, drains E.; asc. 185 ft. over SE. slope.
11.80	Point of spur, slopes E.; desc. 95 ft. over NE. slope.
32.50	Trail road, on turn, bears N. 50° E. and S. 30° E.
38.00	Wash, drains SE.; asc. 10 ft. over SW. slope.
42.46	Point for the ¼ sec. cor. of secs. 5 and 6 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and brass cap mkd. T11N R6E ¼ S6 | S5 1964
	Raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor.
	Asc. 40 ft. over SW. slope.
48.65	Low ridge, bears E. and W.; desc. 85 ft. over N. slope.
60.30	Wash, drains E.; asc. 270 ft. over SW. slope.

CHAINS

84.40 The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the 1964 field notes of T. 12 N., R. 6 E.

Land, mountainous.
Soil, clay loam.
No timber.
Undergrowth, sagebrush and service berry.

General Description

The East boundary of Township 11 North, Range 6 East, is located about 2 miles west of Randolph, Utah. The township is composed of rolling and mountainous land ranging in elevation from about 6,500 ft. along the east boundary to about 9,000 ft. above sea level, along the west boundary. The area is covered with a dense growth of sagebrush, with scattered patches of aspen timber and service berry undergrowth in the west portion. The area is drained in an easterly direction by Pole Canyon, Old Canyon, New Canyon, Middle Canyon and Otter Creek Canyon. These canyons all have small streams of water in the eastern portion. The soil is mostly clay loam. The area is accessible by improved roads in the main canyons and numerous trail roads throughout the township. This area is fair grazing for cattle and sheep. Little Creek Reservoir is located in the eastern portion of section 23., and supplies the irrigation water for Randolph. There is one ranch in section 23, west of the reservoir.

Form 4–680
(June 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Ferrel D. Reynolds	Transitman
Woodrow W. Campbell	Notes
Jerril E. Smith	Front Chainman
Bart D. Renshaw	Cornerman
Barth D. Hansen	Flagman

418

CERTIFICATE OF SURVEY

I, Glen B. Hatch, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 7th day of November, 19 63, I have dependently resurveyed the Guide Meridian along the East boundary, West and South boundaries, and the subdivisional lines of Township 11 Nc Range 6 East.

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

January 22, 1965 (Date) — Glen B. Hatch (Cadastral Surveyor)

(Date) — (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date APR 14 1966

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the Dependent resurvey of the Guide Meridian along East Boundary, West and South boundaries, and the subdivisional lines o Township 11 North, Range 6 East.

executed by Glen B. Hatch, Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

MAY 11 1966 (Date) — Acting R E Brown (Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

I [illegible]

, is a true copy of the original field notes.

[illegible]

Blank

Page

Blank

Page

Form 4-679
(January 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

421

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF THE

THIRD STANDARD PARALLEL NORTH

ALONG THE SOUTH BOUNDARY OF

TOWNSHIP 13 NORTH, RANGE 6 EAST;

THE GUIDE MERIDIAN, ALONG THE EAST BOUNDARY

THE WEST AND SOUTH BOUNDARIES

AND THE

SUBDIVISIONAL LINES

OF

TOWNSHIP 12 NORTH, RANGE 6 EAST

Of the SALT LAKE Meridian,

In the State of UTAH.

EXECUTED BY

GLEN B. HATCH CADASTRAL SURVEYOR

Under special instructions dated NOVEMBER 7, 19 63, which provided for the surveys included under Group Number 469, approved NOVEMBER 7, 1963, and assignment instructions dated JUNE 5, 19 64.

Survey commenced JULY 14, 19 64

422

DEPT. OF THE INTERIOR
BUR OF LAND MGMT

1966 MAY 31 AM 10 00 .0

RECEIVED
STATE & LAND OFFICE
SALT LAKE CITY, UTAH

INDEX DIAGRAM

Township 12 NORTH, Range 6 EAST,

7	6	5	4	3	2	
27 **6** 79	79 **5** 78	65 **4** 65	55 **3** 55	45 **2** 45	36 **1** 35	15
26 **7** 76	77 **8** 75	64 **9** 63	54 **10** 53	44 **11** 43	34 **12** 33	14
25 **18** 74	69 **17** 73	62 **16** 61	52 **15** 51	42 **14** 41	32 **13** 32	13
24 **19** 71	72 **20** 71	60 **21** 60	50 **22** 49	40 **23** 40	31 **24** 30	12
23 **30** 69	70 **29** 68	59 **28** 58	48 **27** 48	39 **26** 38	29 **25** 28	11
22 **31** 21	67 **32** 19	57 **33** 19	47 **34** 17	37 **35** 17	27 **36** 16	9

Township 12 North, Range 6 East

CHAINS

The Third Standard Parallel North, along the N. bdy., was surveyed by Julian Bausman in 1869. The Guide Meridian along the east boundary was surveyed by Julian Bausman in 1869. The south boundary was surveyed by T. C. Bailey in 1875. The north ½ mile of the west boundary was surveyed by Julian Bausman in 1869. The south 5½ miles of the west boundary were surveyed by T. C. Bailey and J. G. Burrill in 1875. The subdivisional lines were surveyed by T. C. Bailey and J. G. Burrill in 1875.

The following field notes are those of the dependent resurvey of the south boundary (Third Standard Parallel North), Township 13 North, Range 6 East, and the dependent resurvey of the east, west and south boundaries and the subdivisional lines of Township 12 North, Range 6 East.

Before restoring the corners, the lines of the original survey were retraced and diligent search made for any evidence of the original corner, or other calls of the original field note record.

The rules of proportionate measurement were applied to ascertain the position of the lost corners, but not until exhausting every reasonable possibility of finding direct evidence for the control of each particular corner.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and special instructions dated November 7, 1963.

All lines of this survey were run by direct method where the lines were accessible; lines inaccessible were run by triangulation methods. Distances to topography on line run by triangulation are approximate. The details of such triangulation have been thoroughly checked and verified, and in order to simplify the record the diagrams and reductions are omitted from these field notes.

The direction of the lines of this survey were determined by reference to true meridians established on line by elongation observations on Polaris and altitude observations on the sun. The lines were carried forward by sustained angulation being supplemented by other altitude observations on the sun taken throughout the progress of the survey.

The geographic position for the southeast corner of the township is at latitude 41°43'41.5" N. and longitude 111°12'22.68" W., which is the mean of section line ties to U. S. G. S. triangulation station "South Twin", at latitude 41°44'07.82" N. and longitude 111°20'00.53" W., located S. 89°16'12" W., 49.36 chs. dist. from the ¼ section corner of sections 31 and 36, Township 12 North, Ranges 5 and 6 East, and U. S. G. S. triangulation station "Limestone", at latitude 41°35'59.62" N. and longitude 111°13'44.85" W., located N. 34°24'26" W., 21.245 chs. dist. from the corner of sections 13, 14, 23 and 24, Township 10 North, Range 6 East.

The magnetic declination was read at several stations throughout the township and the average of these readings was found to be 15°15' E.

Dependent Resurvey of the Third Standard Parallel North Along the S. Bdy. of T. 13 N., R. 6 E.

Dependent Resurvey, Third Stan. Par. N., S. Bdy.
Townshi 13 North, Ran e 6 East

CHAINS

Reestablishment of the Survey
Executed by Julian Bausman in 1869

Beginning at the original standard cor. of Tps. 12 and 13 N., Rs. 6 and 7 E., monumented with a sandstone, 22x10x6 ins., firmly set and properly mkd.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd.

SC
T13N
R6E R7E

S36	S31
S1	S6

R6E R7E
T12N
1964

Bury original stone cor. alongside iron post.

Thence,

N. 89°42' W., along the S. bdy. of sec. 36.

Over gently rolling land through dense sagebrush. Asc. 60 ft. over E. slope.

17.60 Spur, slopes SE.; desc. 50 ft. over SW. slope.

32.05 Wash, drains S. 65° E.; asc. 20 ft. over gentle NE. slop .

39.655 Point for the N. ¼ sec. cor. of sec. 1, T. 12 N., R. 6 E., hereinafter described.

40.14 The original standard ¼ sec. cor. of sec. 36, monumented with a sandstone, 17x8x4 ins., firmly set and properly mkd.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd.

SC
T13N R6E

¼ S36

1964

Bury original stone cor. alongside iron post.

S. 89°57' W., beginning new measurement.

Asc. 75 ft. over gently rolling NE. slope.

21.70 Unimproved dirt road, bears about N. 75° E. and S. 75° W

CHAINS	
39.17	The original closing cor. of secs. 1 and 2, T. 12 N., R. 6 E., hereinafter described.
40.30	The original standard cor. of secs. 35 and 36, monumented with a sandstone, 12x10x6 ins., firmly set and properly mkd. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd. SC T13N R6E S35 | S36 1964 Bury original stone cor. alongside iron post. Land, gently rolling. Soil, rocky loam. No timber. Undergrowth, dense sagebrush.
	N. 89°42' W., along the S. bdy. of sec. 35. Asc. 20 ft. over gentle NE. slope.
4.40	Low ridge, bears NW. and SE.; desc. 25 ft. over SW. slope.
15.25	Wash, drains NW.; asc. 70 ft. over E. slope.
25.00	Spur, slopes N.; desc. 20 ft. over NW. slope.
38.255	Point for the N. ¼ sec. cor. of sec. 2, T. 12 N., R. 6 E., hereinafter described.
40.39	The original standard ¼ sec. cor. of sec. 35, monumented with a limestone, 16x12x10 ins., firmly set and properly mkd. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd. SC T13N R6E ¼ S35 1964 Bury original stone cor. alongside iron post, and raise a mound of stone, 2½ ft. base, 1½ ft. high, N. of cor.
	N. 89°51' W., beginning new measurement. Along N. slope.
2.00	Asc. 95 ft. over NE. slope.
10.00	Enter aspen timber, bears N. and S.
13.50	Spur, slopes N.; leave timber, bears N. and S.; desc. 30 ft. over NW. slope.

Dependent Resurvey, Third Stan. Par. N., S. Bdy.
Townshi 13 North Ran e 6 East

CHAINS

31.15 Draw, drains NE.; asc. 105 ft. over E. slope.

37.25 The original closing cor. of secs. 2 and 3, T. 12 N., R. 6 E., hereinafter described.

40.33 The original standard cor. of secs. 34 and 35, monumented with a red sandstone, 18x10x4 ins., firmly set and proper ly mkd.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd.

SC
T13N R6E

S34 | S35

1964

Bury original stone cor. alongside iron post.

Land, rolling.
Soil, rocky clay loam.
Timber, one patch of dense aspen.
Undergrowth, dense sagebrush and scattered service berry.

N. 89°21' W., along the S. bdy. of sec. 34.

Over rolling land through dense sagebrush. Asc. 10 ft. over gentle E. slope.

4.60 Ridge, bears NW. and SE.; thence over nearly level ridge top.

5.05 Unimproved dirt road, bears about N. 35° W. and S. 35° E.

35.00 Desc. 70 ft. over NW. slope.

36.255 Point for the N. ¼ sec. cor. of sec. 3, T. 12 N., R. 6 E. hereinafter described.

39.00 Wash, drains SW.; asc. 15 ft. over SE. slope.

39.98 The original standard ¼ sec. cor. of sec. 34, monumented with a sandstone, 16x10x5 ins., firmly set and properly mkd.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd.

SC
T13N R6E

¼ S34

1964

Bury original stone cor. alongside iron post.

N. 89°51' W., beginning new measurement.

Asc. 15 ft. over SE. slope.

Dependent Resurvey, Third Stan. Par. N., S. Bdy.
Township 13 North, Range 6 East

CHAINS	
4.00	Point of spur, slopes SW.; desc. 170 ft. over W. slope.
16.20	Wash, drains S. 10° W.; asc. 55 ft. over SE. slope.
22.70	Point of spur, slopes S.; desc. 135 ft. over NW. slope.
30.90	Wash, drains about S. 30° W.; asc. 50 ft. over SE. slope.
35.61	The original closing cor. of secs. 3 and 4, T. 12 N., R. 6 E., hereinafter described. Desc. 40 ft. along S. slope.
40.31	The original standard cor. of secs. 33 and 34, monumented with a sandstone, 25x12x6 ins., firmly set and properly mkd. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd. SC T13N R6E S33 | S34 1964 Bury original stone cor. alongside iron post. Land, rolling. Soil, rocky clay loam. No timber. Undergrowth, dense sagebrush and scattered service berry.
	N. 89°07' W., along the S. bdy. of sec. 33. Over rolling mountainous land through dense sagebrush. Desc. 40 ft. over SW. slope.
9.60	Wash, drains about S. 35° W.; asc. 10 ft. along S. slope.
15.90	Wash, drains S.
18.00	Low spur, slopes S.; desc. 50 ft. over SW. slope.
19.50	Wash, drains SW.; asc. 15 ft. over SE. slope.
20.85	Spur, slopes SW.; desc. 60 ft. over NW. slope.
25.20	Wash, drains SW.; asc. 50 ft. over SE. slope.
30.40	Spur, slopes SW.; desc. 105 ft. over NW. slope.
35.40	Wash, near head, drains about S. 20° W., asc. 50 ft. over SE. slope.
36.215	Point for the N. ¼ sec. cor. of sec. 4, T. 12 N., R. 6 E., hereinafter described.
40.31	Point for the standard ¼ sec. cor. of sec. 33 at proportionate dist. falls on rocky spur, slopes S.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, with glass at base, and in a mound of stone, 5 ft. base to top, with brass cap mkd.

Dependent Resurvey, Third Stan. Par. N., S. Bdy.
Towns[illegible] 13 North, [illegible] 6 East.

CHAINS	
	SC T13N R6E ¼ S33 1964
	Desc. 120 ft. over rocky NW. slope.
45.09	Highway right of way fence, parallels highway.
46.45	Center line of State Highway No. 3, bears N. 41° W. and curves E.
47.50	Wash, in bottom of canyon, drains NW.; asc. 210 ft. over steep NE. slope.
60.00	Spur, slopes NW.; desc. 20 ft. over NW. slope.
65.00	Wash, drains NW.; asc. 15 ft. over NE. slope.
67.10	Spur, slopes N.; desc. 30 ft. over NW. slope.
71.10	Spring branch, stream of water, 1 lk. wide, 2 ins. deep, flows N. Aspen timber, 1.00 ch. wide along spring branch; asc. 135 ft. over E. slope.
77.13	The original closing cor. of secs. 4 and 5, T. 12 N., R. 6 E., hereinafter described.
77.25	Enter aspen timber, bears N. and curves SE.
80.62	The original standard cor. of secs. 32 and 33, monumented with a sandstone, 20x10x8 ins., loosely set in small mound of stone and properly mkd. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd. SC T13N R6E S32 | S33 1964 Bury original stone cor. alongside iron post. Cor. is situated in fence line bearing N. 8°30' W. and S. 8°30' E., along W. edge of aspen grove. Land, rolling, mountainous. Soil, rocky clay loam. Timber, scattered patches of aspen. Undergrowth, dense sagebrush and scattered service berry.
	S. 89°38' W., along the S. bdy. of sec. 32. Over mountainous land through scattered patches of aspen timber and dense sagebrush. By triangulation; desc. about 150 ft. over W. slope.
20.00	Draw, drains N.; enter aspen timber; asc. about 150 ft. over NE. slope.
30.00	Leave timber.

Dependent Resurvey, Third Stan. Par. N., S. Bdy.
Township 13 North, Range 6 East

CHAINS	
34.16	Point for the N. ¼ sec. cor. of sec. 5, T. 12 N., R. 6 E. hereinafter described.
37.00	Top of ascent, ridge, bears NW. and SE. End triangulation. Desc. 15 ft. over gentle SW. slope.
38.89	The original standard ¼ sec. cor. of sec. 32, monumented with a sandstone, 18x5x4 ins., properly set and mkd.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd. SC T13N R6E ¼ S32 1964
	Bury original stone cor. alongside iron post.
	N. 89°20' W., beginning new measurement.
	Desc. 35 ft. over gentle SW. slope.
0.20	Unimproved dirt road, bears about N. 53° W. and S. 53° E.
9.90	Spur, slopes SW.; desc. 200 ft. over NW. slope.
29.00	Wash, in draw, drains SW.; asc. 75 ft. over SE. slope.
32.92	Point for the closing cor. of secs. 5 and 6, T. 12 N., R. 6 E., hereinafter described.
37.00	Spur, slopes S.; desc. 20 ft. over NW. slope.
39.70	Enter cultivated dry farm land, bears NE. and SW.
40.51	Point for the standard cor. of secs. 31 and 32 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd. SC T13N R6E S31 | S32 1964
	Land, mountainous. Soil, rocky clay loam. Timber, scattered aspen E. portion; no timber W. portion. Undergrowth, dense sagebrush and scattered service berry.
	N. 89°20' W., along the S. bdy. of sec. 31.
	Over mountainous dry farm land. Desc. 240 ft. over gently rolling SW. slope.
21.55	Leave dry farm land; enter scattered juniper timber.
27.00	Slope changes; desc. 400 ft. over steep and rocky W. slope.

Dependent Resurvey, Third Stan. Par. N., S. Bdy.
To shi 13 North Ran e 6 East

CHAINS

39.90 Bladed road, bears N. and S. Leave timber.

40.51 Point for the standard ¼ sec. cor. of secs. 6 and 31 at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone to top, with brass cap mkd.

SC
T13N R6E

¼ S31
S6
T12N R6E

1964

42.40 Wire fence, bears about N. 15° W. and S. 15° E. about 10.00 chs., thence NW.; enter farm land.

43.00 Irrigation ditch, flows N. 15° W.

51.85 Fence, and telephone line, bears about N. 56° W. and S. 56° E.; leave farm land.

51.95 Improved dirt road, parallels fence; asc. 40 ft. over NE. slope.

59.50 Fence, bears N. 2° E. and S. 2° W. about 10.00 chs., thence W.; desc. 30 ft. over gentle W. slope.

69.65 Small draw, drains N.; asc. 15 ft. over gentle NE. slope.

70.90 Fence, bears nearly N. and S. to Lake Town cemetary, about 4.00 chs. S. to NE. cor.

72.00 Top of ascent, slopes N.; desc. 40 ft. over gentle NW. slope.

80.10 Cement lined canal, flows N. from SW.

80.22 Fence, bears N. and curves SW.; enter farm land.

81.02 Point for the standard cor. of Tps. 12 and 13 N., Rs. 5 and 6 E., at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 6 ins. long, 1 in. diam., 24 ins. belo ground, with brass cap mkd.

SC
T1 3N
R5E R6E

S36	S31
S1	S6

R5E R6E
T12N
1964

from which

An iron post, 30 ins. long, 2½ ins. diam., set 24 in . in the ground, for a reference monument, bears S. 80°20' E., 52 ft. dist., with brass cap mkd. T12N R6E S6 RM 52 FT 1964, and an arrow pointing to the true cor.

G

Dependent Resurvey, Third Stan. Par. N., S. Bdy.
Township 13 North, Range 6 East.

CHAINS

An iron post, 30 ins. long, 2½ ins. diam., set 24 ins. in the ground, and in a fence line, for a reference monument, bears S. 1° W., 56 Ft. dist., with brass cap mkd. T12N R5E S1 RM 56 FT 1964, and an arrow pointing to the true cor.

The original standard cor. of secs. 35 and 36, T. 13 N., R. 5 E., bears N. 89°20' W., 81.02 chs. dist., monumented with a limestone, 40x10x6 ins., firmly set and plainly mkd.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone to top, with brass cap mkd.

SC
T13N R5E
S35 | S36
1964

Set original stone cor. alongside iron post.

Cor. set at corner of old fence from E. and N.

Land, mountainous E. ½., rolling W. ½.
Soil, rocky loam.
Timber, scattered juniper E. ½. No timber W. ½.
Undergrowth, dense sagebrush E. ½. Sagebrush and farm crop W. ½.

Dependent Resurvey of the Guide Meridian Along the E. Bdy.
T. 12 N., R. 6 E.

Reestablishment of the Survey
Executed by Julian Bausman in 1869.

Beginning at the original cor. of Tps. 11 and 12 N., Rs. 6 and 7 E., monumented with a sandstone, 20x5x5 ins., properly set, and mkd.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone to top, with brass cap mkd.

T12N
R6E R7E
S36 | S31
S1 | S6
T11N
1964

Bury original stone cor. alongside iron post.

Cor. set in N. and S. fence line.

Thence,

N. 0°11' E., bet. secs. 31 and 36.

De endent Resurve Guide Meridian E. Bd . T. 12 N. R. 6 E.

CHAINS

Over rolling land through dense sagebrush and along fence line. Desc. 40 ft. over N. slope.

4.00 Wash, in draw, drains W.; asc. 35 ft. over S. slope.

7.00 Spur, slopes W.; desc. 90 ft. over N. slope.

20.90 Wash, in draw, drains S. 75° W.; asc. 120 ft. over S. slope.

37.00 Low ridge, bears E. and W.; desc. 10 ft. over gentle N. slope.

40.28 The original ¼ sec. cor. of secs. 31 and 36, monumented with a sandstone, 16x7x3 ins., firmly set and properly mkd.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground, with glass at base, and in a collar of stone to top, with brass cap mkd.

T12N
R6E R7E
¼
S36 | S31

1964

Bury original stone cor. alongside iron post.

N. 0°09' E., beginning new measurement.

Continue along fence line; asc. 10 ft. over gentle S. slope.

8.00 Low spur, slopes W.; desc. 60 ft. over N. slope.

17.65 Wash, 15 lks. wide, 3 ft. deep, in draw, drains E.; asc. 65 ft. over S. slope.

29.30 Ridge, with trail road on top, bears NW. and SE.; thence over nearly level land.

40.26 The original cor. of secs. 25, 30, 31 and 36, monumented with a sandstone, 18x10x5 ins., firmly set and properly mkd.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd.

T12N
R6E R7E
S25 | S30
S36 | S31

1964

Bury original stone cor. alongside iron post.

Cor. set in N. and S. fence line.

D NOTE PAPER

Dependent Resurvey, Guide Meridian, E. Bdy., T. 12 N., R. 6 E.

CHAINS	
	Land, rolling. Soil, rocky gravel. No timber. Undergrowth, dense sagebrush.
	N. 0°07' E., bet. secs. 25 and 30. Over gently rolling land through dense sagebrush and along fence line.
3.60	Low spur, slopes E.; desc. 20 ft. over N. slope.
5.90	Wash, in small draw, drains SE.; asc. 50 ft. over gentle S. slope.
40.33	The original ¼ sec. cor. of secs. 25 and 30, monumented with a washed boulder, 16x8x5 ins., firmly set and properly mkd. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd. T12N R6E R7E ¼ S25 | S30 1964 Bury original stone cor. alongside iron post. Cor. set at cor. of fences from W., S. and NE.
	N. 0°12' E., beginning new measurement. Asc. 20 ft. over gentle S. Slope.
9.40	Top of small knoll; desc. 50 ft. over SW. slope.
29.65	Wash, drains N. 75° W.; asc. 25 ft. over SW. slope.
32.70	Spur, slopes W.; desc. 145 ft. over steep NW. slope.
40.41	The original cor. of secs. 19, 24, 25 and 30, monumented with a partially disintegrated sandstone, 8x8x5 ins., firmly set, with plain markings on small fragment. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone to top, with brass cap mkd. T12N R6E R7E S24 | S19 S25 | S30 1964 Bury original stone cor. alongside iron post.

De endent Resurve Guide Meridian E. Bd . T. 12 N. R. 6 E.

CHAINS

Land, rolling.
Soil, rocky gravelly loam.
No timber.
Undergrowth, dense sagebrush.

N. 0°11' E., bet. secs. 19 and 24.

Over rolling land through dense sagebrush. Desc. 35 ft. over NW. slope.

1.90 Wash, in draw, drains NE.; asc. 115 ft. over SE. slope.

10.80 Spur, slopes NE.; desc. 20 ft. over NW. slope.

14.60 Draw, drains N. 70° E.; asc. 40 ft. over SE. slope.

19.50 Ridge, bears NE. and SW.; desc. 170 ft. over steep NW. slope.

35.25 Wash, in draw, drains E.; asc. 35 ft. over S. slope.

40.44 The original ¼ sec. cor. of secs. 19 and 24, monumented with a sandstone, 18x8x5 ins., firmly set and properly mkd.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd.

T12N
R6E R7E
¼
S24|S19
1964

Bury original stone cor. alongside iron post.

N. 0°10' E., beginning new measurement.

Desc. 50 ft. over gentle N. slope.

11.90 Wash, in canyon, drains S. 70° E.; asc. 230 ft. over SW. slope.

12.30 Gravel surfaced highway, bears about N. 60° W. and S. 60° E.

23.30 Spur, slopes SW.; desc. 25 ft. over NW. slope.

25.60 Wash, 20 lks. wide, 6 ft. deep, drains S. 30° W.; asc. 90 ft. over SE. slope.

40.27 The original cor. of secs. 13, 18, 19 and 24, monumented with a washed boulder, 18x12x8 ins., firmly set and properly mkd.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd.

Dependent Resurvey, Guide Meridian, E. Bdy., T. 12 N., R. 6 E.

CHAINS	
	T12N R6E R7E S13 | S18 S24 | S19 1964 Bury original stone cor. alongside iron post. Land, rolling. Soil, rocky loam. No timber. Undergrowth, dense sagebrush.
	N. 0°14' E., bet. secs. 13 and 18. Over rolling land through dense sagebrush. Asc. 20 ft. over gentle S. slope.
16.20	Ridge, bears N. 75° W. and S. 75° E.; desc. 90 ft. over NE. slope.
40.20	Wash, 15 lks. wide, 3 ft. deep, drains E.; asc. 20 ft. over SE. slope.
42.76	Point for the ¼ sec. cor. of secs. 13 and 18 at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T12N R6E R7E ¼ S13 | S18 1964 Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. Asc. 35 ft. over SE. slope.
51.50	Ridge, bears nearly E. and W.; desc. 120 ft. over NE. slope.
74.20	Wash, 30 lks. wide, 12 ft. deep, in canyon, drains SE.; asc. 190 ft. over SW. slope.
75.25	Center line of state highway No. 3, bears about N. 44° W. and S. 44° E.
76.92	Highway right of way fence, parallel to highway.
85.52	The original cor. of secs. 7, 12, 13 and 18, monumented with a sandstone, 16x9x5 ins., firmly set and properly mkd. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

d' E Bd T N R 6 E

CHAINS

T12N
R6E R7E

S12	S7
S13	S18

1964

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, rolling.
Soil, rocky loam.
No timber.
Undergrowth, dense sagebrush.

N. 0°11' E., bet. secs. 7 and 12.

Over rolling land through dense sagebrush. Desc. 15 ft. over gentle NW. slope.

4.60 Head of small draw, drains W.; asc. 100 ft. over SW. sl .

25.50 Unimproved trail road, bears about N. 70° W., and S. 70° E.

30.00 Ridge, bears N. 70° W. and S. 70° E.; desc. 30 ft. over gentle NE. slope.

40.29 Point for the ¼ sec. cor. of secs. 7 and 12 at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd.

T12N
R6E R7E
¼
S12 | S7

1964

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Desc. 130 ft. over NE. slope.

52.90 Wash, 10 lks. wide, 2 ft. deep, in draw; drains E.; asc. 180 ft. over S. slope.

67.80 Trail road, on ridge, bears about N. 80° W. and S. 80° E. desc. 75 ft. over N. slope.

80.58 The original cor. of secs. 1, 6, 7 and 12, monumented with a gray conglomerate stone, 15x8x6 ins., firmly set and properly mkd.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd.

Dependent Resurvey, Guide Meridian, E. Bdy., T. 12 N., R. 6 E.

CHAINS	
	T12N R6E R7E S1 | S6 S12 | S7 1964 Bury original stone cor. alongside iron post; and raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of cor. Land, rolling. Soil, rocky loam. No timber. Undergrowth, dense sagebrush.
	N. 0°39' E., bet. secs. 1 and 6. Over rolling land through dense sagebrush. Desc. 10 ft. over N. slope.
4.90	Wash, 20 lks. wide, 2 ft. deep, drains irregularly E.; asc. 65 ft. over gentle SE. slope.
24.50	Ridge, bears about E. and W.; desc. 65 ft. over N. slope.
30.00	Draw, drains E.; asc. 90 ft. over SE. slope.
40.23	The original ¼ sec. cor. of secs. 1 and 6, monumented with a sandstone, 17x7x4 ins., firmly set and properly mkd. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd. T12N R6E R7E ¼ S1 | S6 1964 Bury original stone cor. alongside iron post, and raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of cor.
	N. 0°17' E., beginning new measurement. Desc. 125 ft. over NW. slope.
15.50	Draw, with small seep of water, flows E.; asc. 130 ft. over S. slope.
21.20	Ridge, bears E. and W.; desc. 20 ft. over gentle NE. slope.
40.46	The cor. of Tps. 12 and 13 N., Rs. 6 and 7 E., hereinbefore described. Land, rolling, Soil, rocky loam. No timber Undergrowth, dense sagebrush.
	Dependent Resurvey of the S. Bdy., T. 12 N., R. 6 E.

D endent esurve of the S Bd . T 1 N R 6 E

CHAINS

Reestablishment of the Survey
Executed by T. C. Bailey in 1875

From the cor. of Tps. 11 and 12 N., Rs. 6 and 7 E., herein before described.

N. 89°45' W., bet. secs. 1 and 36,

Over rolling land through dense sagebrush. Desc. 10 ft. over gentle W. slope.

7.50 Desc. 135 ft. over steep NW. slope.

18.50 Draw, drains S. 30° W.; asc. 120 ft. over steep SE. slope

25.20 Spur, slopes S. 20° W.; desc. 130 ft. over NW. slope.

33.20 Small draw, drains SE.; asc. 15 ft. over NE. slope.

35.00 Low spur, with trail road on top, slopes S.; desc. 15 ft. over gentle SW. slope.

40.51 The original ¼ sec. cor. of secs. 1 and 36, monumented with a sandstone, 25x10x4 ins., loosely set and dimly mkd. ¼ on N. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd.

T12N R6E

¼ S36/S1

T11N
1964

Bury original stone cor. alongside iron post.

N. 89°17' W., beginning new measurement.

Desc. 35 ft. over gentle SW. slope.

7.65 Trail road, bears about N. 50° W. and S. 50° E.

16.60 Wash, 30 lks. wide, 4 ft. deep, drains S. 50° E.; asc. 55 ft. over gentle NE. slope.

40.15 The original cor. of secs. 1, 2, 35 and 36, monumented with a sandstone, 20x15x2 ins., firmly set and plainly mkd. as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone to top, with br cap mkd.

T12N R6E

S35	S36
S2	S1

T11N
1964

Dependent Resurvey of the S. Bdy., T. 12 N., R. 6 E.

CHAINS	
	Bury original stone cor. alongside iron post. Land, rolling. Soil, rocky gravel. No timber. Undergrowth, dense sagebrush.
	N. 88°47' W., bet. secs. 2 and 35. Over rolling land through dense sagebrush. Asc. 85 ft. over gentle SE. slope.
1.43	Telephone line, bears about N. 36° W. and S. 36° E.
26.80	Point of spur, slopes S.; desc. 20 ft. over SW. slope.
32.45	Wash, 10 lks. wide, 3 ft. deep, drains S. 50° E.; asc. 10 ft. over NE. slope.
39.42	Point for the ¼ sec. cor. of secs. 2 and 35 at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T12N R6E ¼ S35 / S2 T11N 1964 Asc. 155 ft. over NE. slope.
60.20	Ridge, bears N. 20° W. and S. 20° E.; desc. 200 ft. over SW. slope.
77.60	Wash, 15 lks. wide, 3 ft. deep, drains S.; asc. 10 ft. over gentle SE. slope.
78.84	The original cor. of secs. 2, 3, 34 and 35, monumented with a sandstone, 18x16x12 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone to top, with brass cap mkd. T12N R6E S34 | S35 S3 | S2 T11N 1964 Bury original stone cor. alongside iron post. Land, rolling. Soil, rocky loam. No timber. Undergrowth, dense sagebrush.
	N. 88°53' W., bet. secs. 3 and 34.

[illegible]

[illegible]	Over rolling land through dense sagebrush. Asc. 25 ft. over SE. slope.
6.00	Top of ascent, bears N. and S.; desc. 40 ft. over gentle SW. slope.
[illegible]	Improved road, bears about S. 55° E. curving E. and N. 55° W. curving W.
[illegible]	Small wash, drains S. 50° W.
[illegible]	The original ¼ sec. cor. of secs. 3 and 34, monumented with a sandstone, 12x8x4 ins., firmly set and mkd. as described in the official record.
	At the cor. point
	Set in iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone to top, with brass cap mkd.
	T12N R6E
	¼ S34 / S3
	T11N
	1964
	Bury original stone cor. alongside iron post, and set a sandstone, 20x10x3 ins., N. of cor.

	S. 88 22' W., beginning new measurement.
	Over nearly level land in Otter Creek canyon.
[illegible]	Wash, 15 lks. wide, 3 ft. deep, drains S. 20° W.
[illegible]	Junction of roads, bearing S., NE., and SW.
[illegible]	Improved dirt road, bears about N. 65° W. and SE. curving NE.
[illegible]	Otter Creek, with stream of clear water, 5 lks. wide, 1 ft. deep, flows about S. 70° E.; asc. 115 ft. over NE. slope.
[illegible]	Point of spur, slopes N. 80° E.; thence along top of spur.
[illegible]	The original cor. of secs. 3, 4, 33 and 34, monumented with a limestone, 16x7x4 ins., firmly set and mkd. as described in the official record.
	At the cor. point
	Set in iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone to top, with brass cap mkd.
	T12N R6E
	S33 | S34 / S4 S3
	T11N
	1964
	Bury original stone cor. alongside iron post.

CHAINS	
	Land, rolling. Soil, loam. No timber. Undergrowth, dense sagebrush with willows along Otter Creek.
	N. 89°50' W., bet. secs. 4 and 33. Over rolling mountain land through dense sagebrush. Asc. 75 ft. over SE. slope.
12.15	Low ridge, bears NE. and SW.; desc. 70 ft. over NW. slope.
33.60	Wash, in flat draw, drains N. 75° E.; asc. 15 ft. over gentle NE. slope.
40.21	The original ¼ sec. cor. of secs. 4 and 33, monumented with a sandstone, 12x8x3 ins., loosely set and properly though dimly mkd. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd. T12S R6E ¼ S33 / S4 T11N 1964 Bury original stone cor. alongside iron post, and set a sandstone, 24x16x3 ins., N. of cor.
	N. 89°27' W., beginning new measurement. Asc. 105 ft. over gentle NE. slope.
39.05	Fence, wire, bears N. 2°30' E. and S. 2°30' W.
40.21	The original cor. of secs. 4, 5, 32 and 33, monumented with a sandstone, 13x7x3 ins., firmly set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone to top, with brass cap mkd. T12N R6E S32 | S33 S5 | S4 S11N 1964 Bury original stone cor. alongside iron post.

Dependent Resurvey of the S. Bdy., T. 12 N., R. 6 E.

CHAINS

Land, rolling, mountainous.
Soil, clay loam.
No timber.
Undergrowth, dense sagebrush.

N. 89°17' W., bet. secs. 5 and 32.

Over rolling mountain land through dense sagebrush and scattered service berry and chokecherry. Asc. 110 ft. over E. slope.

14.95 Top of ascent, bears N. and S., desc. 10 ft. over gentle NW. slope.

37.00 Small wash, drains N. 10° E., asc. 5 ft. over NE. slope.

40.07 The original ¼ sec. cor. of secs. 5 and 32, monumented with a sandstone, 16x6x3 ins., firmly set and mkd. as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd.

T12N R6E

S32
¼ S5

T11N
1964

Bury original stone cor. alongside iron post.

N. 89°06' W., beginning new measurement.

1.30 Unimproved dirt road, bears about N. 5° E. and S. 5° W.; asc. 350 ft. over steep NE. slope.

18.00 Enter dense service berry, chokecherry and scrub aspen.

35.00 High ridge, bears N. 70° W. and S. 70° E. Leave timber and undergrowth; desc. 25 ft. over gentle SW. slope.

40.04 The original cor. of secs. 5, 6, 31 and 32, monumented with a limestone, 14x10x6 ins., firmly set and mkd. as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone to top, with brass cap mkd.

T12N R6E

S31	S32
S6	S5

T11N
1964

Bury original stone cor. alongside iron post.

Land, rolling and mountainous.
Soil, rocky clay loam.
Timber, scrub aspen.

Dependent Resurvey of the S. Bdy., T. 12 N., R. 6 E.

CHAINS	
	Undergrowth, dense sagebrush, scattered service berry and chokecherry.
	S. 89°20' W., bet. secs. 6 and 31.
	Over mountainous land through dense sagebrush. Desc. 150 ft. over SW. slope.
27.65	Wash, drains N. 30° W.; asc. 25 ft. over NE. slope.
34.50	Small spur, slopes N.; desc. 25 ft. over NW. slope.
39.10	Point for the ¼ sec. cor. of secs. 6 and 31 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd. T12N R6E ¼ S31 / S6 T11N 1964
	Desc. 15 ft. over NW. slope.
42.60	Wash, drains NE.; asc. 150 ft. over NE. slope. Enter aspen timber and dense undergrowth.
63.00	Top of ascent, slopes N. Leave timber and dense undergrowth; desc. 65 ft. over NW. slope.
74.00	Small draw, drains N.
74.78	Point for the cor. of Tps. 11 and 12 N., Rs. 5 and 6 E. at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd. T12N R5E R6E S36 | S31 S1 | S6 T11N 1964
	From this cor., the ¼ sec. cor. of secs. 31 and 36, T. 12 N., Rs. 5 and 6 E., bears N. 2°52' W., 38.40 chs. dist., monumented with an iron post, 2½ ins.diam., hereinafter described.
	From the same cor., the W. ¼ sec. cor. of sec.. 6, T. 11 N., R. 6 E., bears S. 0°16' W., 44.41 chs. dist., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the 1964 field notes of the W. bdy., T. 11 N., R. 6 E.
	From the same cor., the cor. of secs. 1, 2, 35 and 36, Tps. 11 and 12 N., R. 5 E., bears N. 89°27' W., 86.35 chs. dist., monumented with a sandstone, 20x15x12 ins., firmly set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T12N R5E S35 | S36 S2 | S1 T11N 1964

Dependent Resurvey of the S. Bdy. T 12 N. R. 6 E.

CHAINS

Bury original stone cor. alongside iron post, and raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor.

Note: In accordance with the special instructions, all cors. outside the Tp. used for control, and any intervening cors., if any, should be remonumented with iron post, brass cap markers where practical. Therefore, at proportionate dist. bet. the cor. of secs. 1, 2, 35 and 36, Tps. 11 and 12 N., R. 5 E., and the cor. of Tps. 11 and 12 N., Rs. 5 and 6 E., I establish the ¼ sec. cor. of secs. 1 and 36, Tps. 11 and 12 N., R. 5 E. There is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T12N R5E

¼ S36/S1

T11N
1964

From this ¼ sec. cor., the cor. of secs. 1, 2, 35 and 36, Tps. 11 and 12 N., R. 5 E., bears N. 89°27' W., 39.10 chs. dist.

From the same ¼ sec. cor., the cor. of Tps. 11 and 12 N., Rs. 5 and 6 E., bears S. 89°27' E., 47.25 chs. dist.

Land, mountainous.
Soil, rocky clay loam.
Timber, scattered patches of aspen.
Undergrowth, sagebrush, service berry and chokecherry.

Dependent Resurvey of the W. Bdy., T. 12 N., R. 6 E.

Reestablishment of the Survey Executed by T. C. Bailey and J. G. Burrill in 1875.

From the reestablished cor. of Tps. 11 and 12 N., Rs. 5 and 6 E., hereinbefore described.

N. 2°52' W., Bet. secs. 31 and 36.

Over mountainous land through scattered aspen timber and dense undergrowth. By triangulation; desc. about 300 ft. over steep NE. slope.

25.00 Otter Creek (dry at this point), drains irregularly E.; asc. about 250 ft. over steep S. slope.

26.00 Improved dirt road, bears irregularly E. and W.

38.40 The original ¼ sec. cor. of secs. 31 and 36, monumented with a sandstone, 16x10x3 ins.; loosely set but properly mkd. as described in the official record. End triangulation.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 5 ft. ba. to top, with brass cap mkd.

T12N
R5E R6E
¼
S36|S31
1964

Bury original stone cor. in mound of stone alongside iron post.

Dependent Resurvey of the W. Bdy., T. 12 N., R. 6 E.

CHAINS	
	From this cor., U. S. G. S. triangulation station "South Twin", bears S. 89°16' 12" W., 49.36 chs. dist.
	N. 0°31' W., beginning new measurement.
	Asc. 40 ft. over SW. slope.
4.40	Spur, slopes SE.; desc. 15 ft. along E. slope.
13.70	Head of draw, drains SE.; asc. 45 ft. over SW. slope.
19.90	Ridge, bears NW. and E.; desc. 70 ft. over N. slope. Enter aspen timber.
26.70	Draw, drains S. 75° E. Leave timber; asc. 60 ft. over SW. slope.
32.00	Ridge, bears S. 70° E. and N. 70° W.; desc. 55 ft. over NE. slope.
33.73	Fence, wire, bears N. 57° E. and S. 57° W., with trail road along N. side.
34.75	Enter aspen timber, bears irregularly E. and NW.
40.88	The original cor. of secs. 25, 30, 31 and 36, monumented with a sandstone, 22x10x2 ins., firmly set and plainly mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone to top, with brass cap mkd.
	T12N R5E R6E S25 | S30 S36 | S31 1964
	Bury original stone cor. alongside iron post, and raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of cor.
	Land, mountainous. Soil, rocky loam. Timber, aspen. Undergrowth, sagebrush and service berry.
	N. 0°04' W., bet. secs. 25 and 30.
	Over rolling mountainous land through aspen timber and dense sagebrush. Desc. 30 ft. over gentle NE. slope.
6.80	Wash, drains irregularly E.; asc. 20 ft. over SE. slope. Leave timber.
10.00	Point of spur, slopes E.; desc. 40 ft. over NE. slope.
15.05	Wash, drains NE.; asc. 60 ft, over SE. slope.
31.45	Spur, slopes E.; desc. 10 ft. over gentle NE. slope.
35.85	Small wash, drains NE.
40.84	The original ¼ sec. cor. of secs. 25 and 30, monumented with a sandstone, 14x12x5 ins., firmly set and dimly mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd.
	T12N R5E R6E ¼ S25 | S30 1964

Dependent Resurvey of the W. Bdy., T. 12 N., R. 6 E.

CHAINS	
	Bury original stone cor. alongside iron post, and raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of cor.
	N. 0°26' W., beginning new measurement.
	Desc. 10 ft. over gentle NE. slope.
3.50	Wash, 10 lks. wide, 1 ft. deep, drains SE.; asc. 60 ft. over SW. slope.
4.41	Barbed-wire fence, bears about N. 84° W. and S. 84° E.
10.90	Ridge, with improved dirt road along top, bears E. and W.; desc. 115 ft. over NE. slope.
30.50	Unimproved dirt road, bears NW. and SE.
33.00	Enter dense undergrowth and scattered aspen timber.
40.98	The original cor. of secs. 19, 24, 25 and 30, monumented with a sandstone, 24x8x6 ins., firmly set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and brass cap mkd.
	T12N R5E R6E S24 | S19 S25 | S30 1964
	Bury original stone cor. alongside iron post.
	Land, mountainous, rolling. Soil, rocky loam. Timber, scattered aspen. Undergrowth, sagebrush and scattered service berry.
	N. 0°22' W., bet. secs. 19 and 24.
	Over rolling land through dense undergrowth and scattered aspen timber. Desc. 90 ft. over NE. slope.
7.00	Leave dense undergrowth and timber, bears NW. and SE.; enter dry farm.
24.10	Spur, slopes NE.; barbed-wire fence, bears about N. 89° E. and S. 89° W.; desc. 65 ft. over NW. slope. Leave dry farm.
39.40	Wash, drains NE.; asc. 5 ft. over SE. slope.
40.90	The original ¼ sec. cor. of secs. 19 and 24, monumented with a sandstone, 40x15x3 ins., firmly set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd.
	T12N R5E R6E ¼ S24 | S19 1964
	Set original stone cor. alongside iron post.
	N. 0°07' E., beginning new measurement.

Dependent Resurvey of the W. Bdy., T. 12 N., R. 6 E.

CHAINS	
	Asc. 15 ft. over SE. slope.
3.05	Spur, slopes E.; desc. 45 ft. over N. slope.
10.60	Small draw, drains E.; asc. 35 ft. over S. slope.
13.60	Spur, slopes E.; desc. 35 ft. over N. slope.
22.85	Wash, drains SE.; asc. 50 ft. over S. slope.
30.50	Ridge, bears E. and W. Enter dense aspen timber; desc. 40 ft. along E. slope.
40.70	The original cor. of secs. 13, 18, 19 and 24, monumented with a flintstone, 14x12x2 ins., firmly set and plainly mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and brass cap mkd. T12N R5E R6E S13 | S18 S24 | S19 1964 Bury original stone cor. alongside iron post, and raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of cor. Land, rolling. Soil, rocky clay loam. Timber, aspen. Undergrowth, dense sagebrush, scattered patches of dense service berry.
	N. 3°50' W., bet. secs. 13 and 18. Over mountainous land through dense aspen timber and sagebrush. Asc. 20 ft. along E. slope.
2.00	Leave dense aspen timber, bears irregularly S. and NE.; enter sagebrush.
13.00	Ridge, bears SW. and curves N.; desc. 30 ft. along gentle W. slope.
21.30	Slope changes; desc. 315 ft. over steep NW. slope.
34.80	Enter dense undergrowth and aspen timber.
39.50	Leave aspen timber.
40.35	Point for the ¼ sec. cor. of secs. 13 and 18 at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and brass cap mkd. T12N R5E R6E ¼ S13 | S18 1964 Raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of cor. Desc. 215 ft. over steep NW. slope.
48.75	Junction of draws from SW. and SE., drains N.; desc. 60 ft. along draw.
57.55	Lake Town Canyon, stream of clear water, 4 lks. wide, 3 ins. deep, flows about N. 55° E.; asc. 345 ft. over steep SW. slope.
59.00	Unimproved road to Lake Town, bears N. 55° E. and curves W.

[illegible] Resurv[illegible] of the W. Bdy. T. 12 N. R. 6 E.

CHAINS	
77.60	Ridge, bears NW. and SE.; desc. 20 ft. over NE. slope.
80.70	Point for the cor. of secs. 7, 12, 13 and 18 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone with brass cap mkd.

T12N
R5E R6E

S12	S7
S13	S18

1964

Land, mountainous.
Soil, rocky.
Timber, aspen S. portion; no timber N. portion.
Undergrowth, sagebrush and service berry.

N. 0°37' E., bet. secs. 7 and 12.

Over mountainous land through sagebrush and service berry undergrowth. Desc. 90 ft. over NE. slope, through scrub aspen timber and dense undergrowth.

4.30	Leave timber and dense undergrowth; enter sagebrush.
9.70	Junction of draws from NW. and NE. drains SE.; asc. 220 ft. over S. slope.
26.50	Ridge, bears E. and W., desc. 35 ft. over gentle NW. slope.
31.60	Trail road, bears N. 80° E. and S. 80° W.
40.26	The original ¼ sec. cor. of secs. 7 and 12, monumented with a sandstone, 15x12x5 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. dism., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd.

T12N
R5E R6E
¼
S12 | S7
1964

Bury original stone cor. alongside iron post, and raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor.

N. 0°50' E., beginning new measurement.

Desc. 70 ft. over gentle NW. slope.

10.50	Head of small draw, drains N. 75° W.
15.00	Spur, slopes NW.; desc. 250 ft. over NE. slope.
39.40	Trail road, bears N. 20° W. and S. 20° E., draw, drains NW.
40.69	Point for the cor. of secs. 1, 6, 7 and 12 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone with brass cap mkd.

T12N
R5E R6E

S1	S6
S12	S7

1964

Land mountainous.
Soil, rocky loam.
Timber, scattered aspen.
Undergrowth, sagebrush, service berry and oak.

Dependent Resurvey of the W. Bdy., T. 12 N., R. 6 E.

CHAINS	
	N. 0°50' E., bet. secs. 1 and 6.
	Over mountainous land through sagebrush undergrowth. Asc. 60 ft. over SW. slope.
13.00	Top of ascent, slopes W.; desc. 330 ft. over steep NW. slope.
34.50	Trail road, in draw, bears N. 30° E. and curves S.; asc. 60 ft. over SE. slope.
39.00	Spur, slopes NE.; desc. 100 ft. over NW. slope.
44.70	Point for the ¼ sec. cor. of secs. 1 and 6 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T12N R5E R6E ¼ S1|S6 1964

Dependent Resurvey of the W. Bdy., T. 12 N., R. 6 E.

Reestablishment of the Survey Executed by Julian Bausman in 1869.

	Desc. 165 ft. over NW. slope.
54.75	End steep descent; desc. 40 ft. over gentle NW. slope.
67.15	Bottom of descent, slopes W.; asc. 30 ft. over gentle S. slope.
70.20	Low ridge, bears E. and W.; desc. 90 ft. over N. slope.
84.40	Cement lined canal, flows NE.
84.54	Fence, bears NE. and SW.
85.39	The standard cor. of Tps. 12 and 13 N., Rs. 5 and 6 E., hereinbefore described.
	Land, mountainous. Soil, rocky, gravelly loam. No timber. Undergrowth, sagebrush, service berry and oak.

Dependent Resurvey of the Subdivision, T. 12 N., R. 6 E.

Reestablishment of the Survey Executed by T. C. Bailey and J. G. Burrill in 1875.

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp.

N. 2°38' E., bet. secs. 35 and 36.

Over rolling land through dense sagebrush. Asc. 25 ft. over S. slope.

Resurvey of the Subdivision, T. 12 N., R. 6 E.

CHAINS	
5.10	Small spur, slopes SE.; desc. 15 ft. over NE. slope.
16.00	Draw, drains SE.; asc. 200 ft. over SW. slope.
18.60	Trail road, bears NW. and SE.
35.20	S. edge of high rolling bench land; thence over gently rolling land.
40.47	The original ¼ sec. cor. of secs. 35 and 36, monumented with a sandstone, 14x5x3 ins., firmly set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T12N R6E ¼ S35|S36 1964 Bury original stone cor. alongside iron post.
	N. 0°30' E., beginning new measurement. Continue over gently rolling bench land.
22.90	Trail road, bears NW. and SE.; asc. 85 ft. over SE. slope.
40.71	The cor. of secs. 25, 26, 35 and 36, monumented with a sandstone, 18x9x4 ins., set, mkd. and witnessed as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd. T12N R6E S26|S25 S35|S36 1964 Bury original stone cor. alongside iron post. Land, rolling. Soil, gravelly loam. No timber. Undergrowth, dense sagebrush.
	From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp. N. 87°36' W., bet. secs. 25 and 36. Over rolling land through dense sagebrush. Asc. 20 ft. over gentle E. slope.
9.90	Low ridge, bears NW. and SE.; desc. 20 ft. over gentle SW. slope.

CHAINS	
12.70	Trail road, bears NW. and SE.
28.95	Draw, drains SE.; asc. 15 ft. over gentle SE. slope.
38.69	The original ¼ sec. cor. of secs. 25 and 36, monumented with a washed boulder, 14x9x6 ins., firmly set and plainly mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and brass cap mkd. T12N R6E ¼ S25/S36 1964 Bury original stone cor. alongside iron post.
	S. 89°48' W., beginning new measurement. Asc. 10 ft. over gentle SE. slope.
7.35	Trail road, bears NW. and SE.
19.05	Asc. 45 ft. over SE. slope.
40.03	The cor. of secs. 25, 26, 35 and 36. Land, gently rolling bench land. Soil, gravelly loam. No timber. Undergrowth, sagebrush.
	N. 0°24' E., bet. secs. 25 and 26. Over gently rolling bench land through sagebrush undergrowth. Asc. 55 ft. over gentle SE. slope.
18.10	Unimproved dirt road, on ridge, bears irregularly E. and W.; desc. 40 ft. over gentle N. slope.
29.00	Small flat draw, drains E.; asc. 15 ft. over gentle S. slope.
30.15	Unimproved dirt road, bears SW. and curves N.
36.50	Unimproved dirt road, on low ridge, bears W. and E. about 3.00 chs. to road bearing N. and S.; desc. 20 ft. over gentle N. slope.
39.22	Barbed-wire fence, bears S. 89°45' E. and N. 89°45' W.
40.66	Point for the ¼ sec. cor. of secs. 25 and 26 at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd. T12N R6E ¼ S26|S25 1964

CHAINS	
	Desc. 5 ft. over gentle N. slope.
46.20	Wash, 10 lks. wide, 2 ft. deep, drains E.; asc. 80 ft. over S. slope.
67.00	Ridge, bears E. and W.; desc. 110 ft. over N. slope.
68.70	Trail road, bears irregularly E. and W.
81.32	The original cor. of secs. 23, 24, 25 and 26, monumented with a limestone, 18x12x10 ins., firmly set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T12N R6E S23 | S24 S26 | S25 1964 Bury original stone cor. alongside iron post. Land, gently rolling. Soil, clay loam. No timber. Undergrowth, sagebrush.
	From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp. N. 88°30' W., bet. secs. 24 and 25. Over rolling land through dense sagebrush. Desc. 30 ft. over steep NW. slope.
2.15	Draw, drains NE.; asc. 210 ft. over SE. slope.
39.20	Point for the ¼ sec. cor. of secs. 24 and 25 at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T12N R6E ¼ S24 S25 1964 Asc. 20 ft. over SE. slope.
40.90	Ridge, bears NE. and SW.; desc. 120 ft. over NW. slope.
69.50	Trail road, bears irregularly N. and S.
74.40	Draw, drains N.; asc. 20 ft. over NE. slope.
78.40	The cor. of secs. 23, 24, 25 and 26. Land, rolling. Soil, rocky, gravelly loam. No timber.

Dependent Resurvey of the Subdivision, T. 12 N., R. 6 E.

CHAINS	
	Undergrowth, sagebrush.
	N. 0°44' E., bet. secs. 23 and 24.
	Over rolling land through dense sagebrush. Desc. 80 ft. over NE. slope.
8.60	Draw, drains N. 75° E.; asc. 20 ft. over gentle SE. slope.
25.10	Top of ascent, bears E. and W.; desc. 40 ft. over N. slope.
29.35	Draw, drains E.; asc. 55 ft. over SE. slope.
40.69	The original ¼ sec. cor. of secs. 23 and 24, monumented with a sandstone, 16x14x8 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T12N R6E ¼ S.[illegible] 1964.
	Bury original stone cor. alongside iron post.
	N. 0°17' E., beginning new measurement.
	Desc. 25 ft. over N. slope.
[illegible]	Draw, drains E., asc. 95 ft. over SW. slope.
16.25	Trail road, bears SE. and NW., curving to N.
27.20	Top of ascent, slopes W.; desc. 40 ft. over NW. slope.
35.40	Same trail road, bears NE. and SW. curving to S.
38.10	Small draw, drains E.; asc. 20 ft. over S. slope.
40.63	The original cor. of secs. 13, 14, 23 and 24, monumented with a sandstone, 18x14x8 ins., firmly set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T12N R6E S14 | S13 S23 | S24 1964
	Bury original stone cor. alongside iron post.

Resident Resurvey of the Subdivision T. 12 N. R. 6 E.

CHAINS	
	Land, rolling. Soil, rocky loam. No timber. Undergrowth, sagebrush.
	From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp.
	N. 88°01' W., bet. secs. 13 and 24.
	Over rolling land through dense sagebrush. Asc. 10 ft. over gently rolling land.
9.40	Desc. 130 ft. over NW. slope.
20.05	Small draw, drains SW.; asc. 40 ft. over SE. slope.
25.10	Point of spur, slopes S.; desc. 20 ft. over SW. slope.
27.00	Small draw, drains S. 20° W.; asc. 65 ft. over SE. slope.
29.70	Spur, slopes S.; desc. 135 ft. over steep SW. slope.
39.00	Point for the ¼ sec. cor of secs. 13 and 24 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd. T12N R6E ¼ S13/S24 1964
	Desc. 15 ft. over SW. slope.
41.55	Gravel surfaced highway, bears NW. and SE.
43.60	Wash, in canyon, drains SE.; asc. 50 ft. over NE. slope.
54.00	Spur, slopes NE.; desc. 10 ft. over gentle NW. slope.
68.00	Wash, 15 lks. wide, 2 ft. deep, with trail road alongside, drains N. 70° E.; asc. 20 ft. over SE. slope.
78.00	The cor. of secs. 13, 14, 23 and 24.
	Land, rolling. Soil, gravelly clay. No timber. Undergrowth, sagebrush.
	N. 0°22' E., bet. secs. 13 and 14.
	Over rolling land through dense sagebrush. Asc. 30 ft. over gentle SE. slope.
11.50	Spur, slopes E.; desc. 70 ft. over N. slope.
19.05	Draw, drains E.; asc. 35 ft. over S. slope.
22.25	Spur, slopes SE.; desc. 10 ft. over NE. slope.
25.00	Draw, drains SE.; asc. 50 ft. over SW. slope.

CHAINS	
34.00	Spur, slopes SE.; desc. 20 ft. over NE. slope.
40.47	The original ¼ sec. cor. of secs. 13 and 14, monumented with a sandstone, 16x14x5 ins., firmly set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T12N R6E ¼ S14 | S13 1964 Bury original stone cor. alongside iron post.
	N. 0°53' E., beginning new measurement. Desc. 25 ft. over NE. slope.
3.30	Draw, drains E.
5.50	Draw, drains SE.; asc. 70 ft. over SW. slope.
10.95	Spur, slopes SE.; asc. 50 ft. over gently rolling S. slope.
21.15	Gravel surfaced highway, bears NW. and SE.
40.59	The original cor. of secs. 11, 12, 13 and 14, monumented with a sandstone, 13x11x4 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone to top, with brass cap mkd. T12N R6E S11 | S12 S14 | S13 1964 Bury original stone cor. alongside iron post. Land, rolling. Soil, rocky loam. No timber. Undergrowth, sagebrush.
	From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp. S. 88°05' W., bet. secs. 12 and 13. Over rolling land through dense sagebrush. Desc. 185 ft. over SW. slope.
8.56	Highway Right of Way fence, bears about N. 44° W. and S. 44° E.

Dependent Resurvey of the Subdivision, T. 12 N., R. 6 E.

CHAINS	
10.16	Center line of State Highway No. 3, bears about N. 44° W. and S. 44° E.
12.10	Wash, 30 lks. wide, 6 ft. deep, in canyon, drains SE.; asc. 75 ft. over NE. slope.
29.25	Small draw, drains NE.
37.16	The original ¼ sec. cor. of secs. 12 and 13, monumented with a sandstone, 17x12x5 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone to top, with brass cap mkd. T12N R6E ¼ S12/S13 1964 Bury original stone cor. alongside iron post.
	S. 89°24' W., beginning new measurement. Asc. 90 ft. over gently rolling NE. slope.
31.80	Ridge, bears NW. and SE.; desc. 5 ft. over gentle SW. slope.
40.20	The cor. of secs. 11, 12, 13 and 14. Land, rolling. Soil, rocky loam. No timber. Undergrowth, sagebrush.
	N. 0°22' W., bet. secs. 11 and 12. Over rolling land through dense sagebrush. Asc. 40 ft. over SW. slope.
10.45	Ridge, bears W. and curves SE.; desc. 80 ft. over NE. slope.
28.50	Draw, drains E. Water trough and spring, bears N. 70° W., about 2.30 chs. dist.; asc. 75 ft. over S. slope.
39.30	Center line of state highway No. 3, bears W. curving NW. and E. curving SE.
40.45	Highway right of way fence, parallel to highway.
40.82	The original ¼ sec. cor. of secs. 11 and 12, monumented with a sandstone, 18x12x6 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and brass cap mkd.

Dependent Resurvey of the Subdivision, T. 12 N., R. 6 E.

CHAINS	
	T12N R6E ¼ S11 | S12 1964 Bury original stone cor. alongside iron post, and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	N. 0°25' W., beginning new measurement. Asc. 145 ft. over SE. slope.
13.10	Ridge, with trail road on top, bears E. and W.; desc. 60 ft. over N. slope.
17.25	Draw, drains E.
18.30	Small draw, drains SW.; asc. 190 ft. over SE. slope.
40.38	The original cor. of secs. 1, 2, 11 and 12, monumented with a broken sandstone, 24x17x3 ins., set and mkd. as described in the official record. At the cor. point. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T12N R6E S2 | S1 S11 | S12 1964 Bury original stone cor. alongside iron post. Land, rolling. Soil, rocky clay loam. No timber. Undergrowth, sagebrush.
	From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp. S. 89°12' W., bet: secs. 1 and 12. Over rolling land through dense sagebrush. Asc. 150 ft. over gently rolling NE. slope.
39.09	Point for the ¼ sec. cor. of secs. 1 and 12 at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and brass cap mkd. T12N R6E ¼ S1 S12 1964 Raise a mound of stone, 3 ft. base, 1½ ft. high, N. of cor.

Dependent Resurvey of the Subdivision, T. 12 N., R. 6 E.

CHAINS	
	Asc. 95 ft. over gently rolling NE. slope.
70.45	Trail road, bears NW. and SE.
78.18	The cor. of secs. 1, 2, 11 and 12.
	Land, rolling. Soil, loam. No timber. Undergrowth, dense sagebrush.
	N. 0°17' W., bet. secs. 1 and 2.
	Over rolling land through dense sagebrush. Asc. 25 ft. over SE. slope.
6.15	Trail road, bears NW. and SE.
7.30	Ridge, bears NW. and SE.; desc. 70 ft. over N. slope.
15.80	Draw, drains E.; asc. 35 ft. over SE. slope.
19.00	Point of spur, slopes E.; thence along E. slope.
30.00	Spur, slopes E.; desc. 60 ft. over NE. slope.
38.25	Draw, drains E.; asc. 10 ft. over SE. slope.
40.34	Point for the ¼ sec. cor. of secs. 1 and 2 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone to top, with brass cap mkd. T12N R6E ¼ S2 | S1 1964
	Asc. 15 ft. over SE. slope.
45.00	Spur, slopes E.; desc. 20 ft. over N. slope.
48.25	Draw, drains E.; asc. 65 ft. over S. slope.
54.00	Spur, slopes E.; desc. 30 ft. over gentle N. slope.
68.20	Draw, drains S. 75° E.; asc. 45 ft. over S. slope.
78.80	Trail road, bears N. 80° E. and S. 75° W.
82.00	The original closing cor. of secs. 1 and 2, on the N. bdy. of the Tp., (Third Standard Parallel North), monumented with a washed boulder, 18x12x8 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd.

Dependent Resurvey of the Subdivision, T. 12 N., R. 6 E.

CHAINS	
	T13N R6E S36 S2 | S1 C C T12N R6E 1964 Bury original stone cor. alongside iron post. From this cor., the standard cor. of secs. 35 and 36, T. 13 N., R. 6 E., bears S. 89°57' W., 1.13 chs. dist., hereinbefore described. Land, rolling. Soil, rocky loam. No timber. Undergrowth, sagebrush.
	Point for the N. ¼ sec. cor. of sec. 1, on the N. bdy. of the Tp., and at midpoint bet. the closing cor. of secs. 1 and 2, and the cor. of Tps. 12 and 13 N., Rs. 6 and 7 E. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T13N R6E ¼ S1 T12N R6E 1964 From this cor., the standard ¼ sec. cor. of sec. 36, T. 13 N., R. 6 E., bears N. 89°42' W., 0.485 chs. dist., hereinbefore described.
	From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp. N. 0°15' W., bet. secs. 34 and 35. Over rolling land through sagebrush undergrowth. Asc. 195 ft. over SE. slope.
26.15	Trail road, bears NE. and SW.
40.58	Point for the ¼ sec. cor. of secs. 34 and 35 at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd. T12N R6E ¼ S34 | S35 1964 Asc. 65 ft. over SE. slope.
50.40	Spur, slopes E.; desc. 70 ft. over NE. slope.
79.90	Draw, drains SE.; asc. 10 ft. over SW. slope.

Dependent Resurvey of the Subdivision, T. 12 N., R. 6 E.

CHAINS	
81.16	The original cor. of secs. 26, 27, 34 and 35, monumented with a sandstone, 14x12x10 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T12N R6E S27 | S26 S34 | S35 1964 Bury original stone cor. alongside iron post. Land, rolling. Soil, rocky clay loam. No timber. Undergrowth, sagebrush.
	From the cor. of secs. 25, 26, 35 and 36. N. 86°47' W., bet. secs. 26 and 35. Over rolling land through sagebrush undergrowth. Desc. 15 ft. over gentle SW. slope.
16.15	Slope changes; trail road, bears NW. and SE.; desc. 25 ft. over NW. slope.
25.75	Small wash, drains SW.; desc. 10 ft. over W. slope.
36.45	Trail road, bears N. 30° E. and S. 30° W.; draw, drains SW.; asc. 20 ft. over SE. slope.
40.26	The original ¼ sec. cor. of secs. 26 and 35, monumented with a sandstone, 16x12x3 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd. T12N R6E ¼ S26 S35 1964 Bury original stone cor. alongside iron post.
	S. 89°08' W., beginning new measurement. Asc. 120 ft. over SE. slope.
22.35	Spur, slopes SE.; desc. 140 ft. over SW. slope.
23.20	Telephone line, bears about N. 36° W. and S. 36° E.
41.17	The cor. of secs. 26, 27, 34 and 35.

CHAINS	
	Land, rolling. Soil, rocky loam. No timber. Undergrowth, sagebrush.
	N. 0°39' E., bet. secs. 26 and 27. Over rolling land through sagebrush undergrowth. Asc. 230 ft. over SW. slope.
24.00	S. edge of bench land, bears NW. and SE.; asc. 30 ft. over gently rolling S. slope.
25.28	Telephone line, bears about N. 36° W. and S. 36° E.
34.00	Trail road, bears NW. and SE.
37.88	Barbed-wire fence, bears N. 89°50' W. about 20.00 chs., thence NW. and S. 89°50' E.
40.56	The original ¼ sec. cor. of secs. 26 and 27, monumented with a limestone, 12x8x4 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone to top, with brass cap mkd. T12N R6E ¼ S27 | S26 1964 Bury original stone cor. alongside iron post.
	N. 1°26' E., beginning new measurement. Asc. 25 ft. over gentle S. slope.
21.50	Top of ascent, bears E. and W.; desc. 135 ft. over N. slope.
35.35	Draw, drains S. 80° E.; asc. 65 ft. over S. slope.
39.50	Trail road, bears NW. and SE.
40.75	The cor. of secs. 22, 23, 26 and 27, monumented with a sandstone, 16x14x10 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd. T12N R6E S22 | S23 S27 | S26 1964 Bury original stone cor. alongside iron post, and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Dependent Resurvey of the Subdivision, T. 12 N., R. 6 E.

CHAINS

Land, rolling.
Soil, rocky clay loam.
No timber.
Undergrowth, sagebrush.

From the cor. of secs. 23, 24, 25 and 26.

N. 89°45' W., bet. secs. 23 and 26.

Over rolling land through sagebrush undergrowth. Asc. 40 ft. over NE. slope.

8.35 Spur, slopes NE.; desc. 60 ft. over NW. slope.

16.85 Wash, in draw, drains N. 30° E.; asc. 170 ft. over NE. slope.

40.15 The original ¼ sec. cor. of secs. 23 and 26, monumented with a sandstone, 12x12x8 ins., set and mkd. as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone to top, with brass cap mkd.

T12N R6E

¼ S23/S26

1964

Bury original stone cor. alongside iron post.

N. 87°59' W., beginning new measurement.

Asc. 55 ft. over NE. slope.

17.25 Top of ascent, bears NW. and SE.; desc. 10 ft. over SW. slope.

24.45 Shallow draw, drains SE.; asc. 35 ft. over NE. slope.

31.15 Ridge, bears NW. and SE.; desc. 20 ft. over SW. slope.

40.26 The cor. of secs. 22, 23, 26 and 27.

Land, rolling.
Soil, clay loam.
No timber.
Undergrowth, sagebrush.

N. 3°04' E., bet. secs. 22 and 23.

Over rolling land through sagebrush undergrowth. Asc. 55 ft. over SW. slope.

11.30 Ridge, bears N. 70° W., and S. 70° E.; desc. 95 ft. over NE. slope.

30.05 Draw, drains S. 70° E.; asc. 100 ft. over SW. slope.

Dependent Resurvey of the Subdivision, T. 12 N., R. 6 E.

CHAINS	
40.40	The original ¼ sec. cor. of secs. 22 and 23, monumented with a sandstone, 14x9x4 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone to top, with brass cap mkd. T12N R6E ¼ S22|S23 1964 Bury original stone cor. alongside iron post.
	N. 1°15' E., beginning new measurement.
1.00	Spur, slopes E.; desc. 100 ft. over NE. slope.
22.00	Draw, drains E.; asc. 30 ft. over SE. slope.
35.00	Spur, slopes NE.; desc. 45 ft. over NW. slope.
40.68	The original cor. of secs. 14, 15, 22 and 23, monumented with a sandstone, 16x15x3 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone to top, with brass cap mkd. T12N R6E S15|S14 S22|S23 1964 Bury original stone cor. alongside iron post. Land, rolling. Soil, rocky clay loam. No timber. Undergrowth, sagebrush.
	From the cor. of secs. 13, 14, 23 and 24. N. 89° 05' W., bet. secs. 14 and 23. Over rolling land through dense sagebrush undergrowth. Asc. 95 ft. over gently rolling NE. slope.
39.10	Point for the ¼ sec. cor. of secs. 14 and 23 at proportionate dist.; there is no remaining evidence of the original cor.. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone to top, with brass cap mkd.

Dependent Resurvey of the Subdivision, T. 12 N., R. 6 E.

CHAINS	
	T12N R6E ¼ S14/S23 1964
	Asc. 80 ft. over gently rolling NE. slope.
78.20	The cor. of secs. 14, 15, 22 and 23.
	Land, gently rolling. Soil, clay loam. No timber. Undergrowth, sagebrush.
	N. 1°15' E., bet. secs. 14 and 15.
	Over rolling land through sagebrush undergrowth. Desc. 20 ft. over NE. slope.
7.00	Small draw, drains NE.; asc. 10 ft. over SE. slope.
10.00	Point of small spur, slopes E.; desc. 10 ft. over NE. slope.
13.00	Small draw, drains E.; asc. 10 ft. over S. slope.
22.00	Low spur, slopes E.; desc. 15 ft. over N. slope.
27.90	Draw, drains E.; asc. 15 ft. over S. slope.
32.20	Spur, slopes SE.; desc. 25 ft. over NE. slope.
40.77	The original ¼ sec. cor. of secs. 14 and 15, monumented with a sandstone, 15x13x6 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd. T12N R6E ¼ S15|S14 1964
	Bury original stone cor. alongside iron post.
	N. 0°52' E., beginning new measurement.
	Desc. 20 ft. over NE. slope.
2.00	Draw, drains S. 75° E.; asc. 90 ft. over S. slope.
20.50	Ridge, with trail road on top, bears E. and W.; desc. 40 ft. over N. slope.
34.05	Draw, drains E.; asc. 25 ft. over S. slope.
40.69	The original cor. of secs. 10, 11, 14 and 15, monumented with a sandstone, 16x14x3 ins., set and mkd. as described in the official record.

Dependent Resurvey of the Subdivision, T. 12 N., R. 6 E.

CHAINS	
	At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd. T12N R6E S10 | S11 S15 | S14 1964 Bury original stone cor. alongside iron post. Land, rolling. Soil, loam. No timber. Undergrowth, sagebrush.
	From the cor. of secs. 11, 12, 13 and 14. N. 88°23' W., bet. secs. 11 and 14. Over rolling land through sagebrush undergrowth. Desc. 10 ft. along gently rolling S. slope.
16.70	Gravel surfaced highway, bears NW. and SE.
25.20	Wash, drains S.; asc. 15 ft. along gently rolling S. slope.
37.20	The original ¼ sec. cor. of sec. 11 and 14, monumented with a sandstone, 14x10x6 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone to top, with brass cap mkd. T12N R6E ¼ S11 S14 1964 Bury original stone cor. alongside iron post.
	N. 89°16' W., beginning new measurement. Asc. 30 ft. over gently rolling SE. slope.
3.30	Wash, drains S. 20° E.
7.30	Wash, drains S.
16.30	Wash, drains S.
21.30	Wash, drains S. 20° E.
28.80	Wash, drains S. 20° E.
40.28	The cor. of secs. 10, 11, 14 and 15.

Dependent Resurve of the Subdivision T. 12 N., R. 6 E.

CHAINS

Land, gently rolling.
Soil, rocky loam.
No timber.
Undergrowth, sagebrush.

N. 1°05' W., bet. secs. 10 and 11.

Over rolling land through sagebrush undergrowth. Asc. 70 ft. over SE. slope.

18.20 Ridge, bears N. 75° W. and S. 75° E.; desc. 40 ft. over NE. slope.

30.35 Trail road, bears NE. and SW.

32.00 Draw, drains SE. curving E.; asc. 30 ft. over SE. slope.

40.88 The original ¼ sec. cor. of secs. 10 and 11, monumented with a sandstone, 12x10x4 ins., set and mkd. as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd.

T12N R6E
¼
S10|S11
1964

Bury original stone cor. alongside iron post.

N. 0°46' E., beginning new measurement.

Asc. 65 ft. over S. slope.

21.50 Ridge, bears NW. and SE.; desc. 10 ft. over gentle NE. slope.

23.00 Gravel surfaced highway, bears NW. and SE.

35.00 Wash, drains SE.; asc. 30 ft. over SW. slope.

38.81 Center line of state highway No. 3, bears about N. 38° W. and S. 38° E. curving E.

39.96 Highway right of way fence, parallel to highway.

40.91 The original cor. of secs. 2, 3, 10 and 11, monumented with a sandstone, 25x8x4 ins., set and mkd. as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, will glass at base, and brass cap mkd.

T12N R6E
S3|S2
S10|S11
1964

Dependent Resurvey of the Subdivision, T. 12 N., R. 6 E.

CHAINS	
	Bury original stone cor. alongside iron post, and raise a mound of stone, 3½ ft. base, 2½ ft. high, W. of cor. Land, rolling. Soil, rocky loam. No timber. Undergrowth, sagebrush.
	From the cor. of secs. 1, 2, 11 and 12. S. 89°45' W., bet. secs. 2 and 11. Over rolling land through sagebrush undergrowth. Desc. 110 ft. over SW. slope.
40.21	The original ¼ sec. cor. of secs. 2 and 11, monumented with a sandstone, 15x12x4 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and brass cap mkd. T12N R6E ¼ S2/S11 1964 Bury original stone cor. alongside iron post, and raise a mound of stone, 3 ft. base, 1½ ft. high, N. of cor. --- N. 86°30' W., beginning new measurement. Desc. 25 ft. over SW. slope.
4.15	Draw, drains S.; asc. 20 ft. over gentle E. slope.
16.00	Spur, slopes S.; desc. 15 ft. over gentle SW. slope.
24.90	Head of small draw, drains S.; asc. 25 ft. over gentle SE. slope.
34.55	Spur, slopes SE.; desc. 15 ft. over SW. slope.
36.89	The cor. of secs. 2, 3, 10 and 11. Land, rolling. Soil, rocky clay loam. No timber. Undergrowth, sagebrush.
	N. 1°28' W., bet. secs. 2 and 3. Over rolling land through dense sagebrush undergrowth. Asc. 30 ft. over SW. slope.
5.95	Spur, slopes SE.; asc. 125 ft. over SE. slope.
39.37	Point for the ¼ sec. cor. of secs. 2 and 3 at proportionate dist.; there is no remaining evidence of the original cor.

Dependent Resurvey of the Subdivision, T. 12 N., R. 6 E.

CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and brass cap mkd.

T12N R6E
¼
S3 | S2
1964

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Asc. 190 ft. over SE. slope.

65.25 Unimproved road, bears irregularly E. and W.

70.00 Ridge, bears E. and W.; desc. 20 ft. over NW slope.

73.85 Head of draw, drains NE.; trail road, bears NW. and SE.; asc. 10 ft. over SE. slope.

80.22 The original closing cor. of secs. 2 and 3, on the N. bdy. of the Tp., (Third Standard Parallel North), monumented with a sandstone, 12x8x6 ins., set and mkd. as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd.

T13N R6E
S35
S3 | S2
C | C
T12N R6E
1964

Bury original stone cor. alongside iron post.

From this cor., the standard cor. of secs. 34 and 35, T. 13 N., R. 6 E., bears N. 89°51' W., 3.08 chs. dist., hereinbefore described.

Land, rolling.
Soil, rocky clay loam.
No timber.
Undergrowth, sagebrush.

Point for the N. ¼ sec. cor. of sec. 2, on the N. bdy. of the Tp., and at mid point bet. the closing cor. of secs. 2 and 3, and the closing cor. of secs. 1 and 2.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T13N R6E
¼ S2
T12N R6E
1964

Dependent Resurvey of the Subdivision, T. 12 N., R. 6 E.

CHAINS	
	From this cor., the standard ¼ sec. cor. of sec. 35, T. 13 N., R. 6 E., bears N. 89°42' W., 2.135 chs. dist., hereinbefore described.
	From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp.
	N. 0°22' E., bet. secs. 33 and 34.
	Over rolling land through dense sagebrush. Desc. 95 ft. over NE. slope.
10.95	Otter Creek, with stream of water, 5 lks. wide, 1 ft. deep, flows irregularly E.; asc. 125 ft. over SW. slope.
15.45	Improved dirt road, bears about N. 50° W. and S. 50° E.
40.53	The original ¼ sec. cor. of secs. 33 and 34, monumented with a sandstone, 18x10x6 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone to top, with brass cap mkd.
	T12N R6E ¼ S33 | S34 1964
	Bury original stone cor. alongside iron post.
	N. 0°29' W., beginning new measurement.
	Asc. 25 ft. over SW. slope.
6.65	Spur, slopes SE.; asc. 90 ft. over rolling SE. slope.
18.65	Small draw, drains E.
32.65	Draw, drains SE.
36.25	Spur, slopes SE.; desc. 10 ft. over gentle N. slope.
40.65	The original cor. of secs. 27, 28, 33 and 34, monumented with a sandstone, 18x10x4 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd.
	T12N R6E S28 | S27 S33 | S34 1964
	Bury original stone cor. alongside iron post.
	Land, rolling. Soil, rocky clay loam. No timber. Undergrowth, sagebrush.

Dependent Resurvey of the Subdivision, T. 12 N., R. 6 E.

CHAINS	
	From the cor. of secs. 26, 27, 34 and 35.
	N. 89°30' W., bet. secs. 27 and 34.
	Over rolling land through sagebrush undergrowth. Desc. 10 ft. over SW. slope.
3.00	Wash, 15 lks. wide, 3 ft. deep, drains SE.; asc. 160 ft. over NE. slope.
15.45	Slope changes; asc. 25 ft. over gentle E. slope.
19.95	Unimproved road, bears N. and S.
28.00	Ridge, bears NW. and SE.; desc. 115 ft. over SW. slope.
39.90	The original ¼ sec. cor. of secs. 27 and 34, monumented with a limestone, 14x7x5 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T12N R6E
	¼ S27 / S34
	1964
	Bury original stone cor. alongside iron post.
	S. 88°59' W., beginning new measurement.
	Desc. 95 ft. over SW. slope.
19.70	Draw, drains SE.; asc. 70 ft. over NE. slope.
23.85	Spur, slopes SE.; desc. 25 ft. over SW. slope.
27.85	Small draw, drains SE.; asc. 50 ft. over SE. slope.
39.25	Wash, 5 lks. wide, 1 ft. deep, drains S. 20° E.
39.85	The cor. of secs. 27, 28, 33 and 34.
	Land, rolling. Soil, clay loam. No timber. Undergrowth, sagebrush.
	N. 0°25' E., bet. secs. 27 and 28.
	Over rolling land through sagebrush undergrowth. Asc. 135 ft. over SE. slope.
2.00	Wash, 5 lks. wide, 1 ft. deep, drains S. 20° E.
40.53	The original ¼ sec. cor. of secs. 27 and 28, monumented with a sandstone, 20x11x4 ins., set and mkd. as described in the official record.
	At the cor. point

Dependent Resurvey of the Subdivision, T. 12 N., R. 6 E.

CHAINS	
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd. T12N R6E ¼ S28|S27 1964 Bury original stone cor. alongside iron post.
	N. 0°10' W., beginning new measurement.
	Asc. 75 ft. over SE. slope.
14.65	Ridge, bears NW. and SE.; desc. 50 ft. over N. slope.
23.45	Draw, drains E.; asc. 20 ft. over S. slope.
27.10	Spur, slopes S. 70° E.; desc. 25 ft. over gentle NE. slope.
33.50	Barbed-wire fence, bears S. 78°50' W. and N. 78°50' E. about 25.00 chs., thence SE.
34.50	Draw, drains SE.; asc. 80 ft. over SW. slope.
40.42	The original cor. of secs. 21, 22, 27 and 28, monumented with a sandstone, 20x12x8 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone to top, with brass cap mkd. T12N R6E S21|S22 S28|S27 1964 Bury original stone cor. alongside iron post. Land, rolling. Soil, gravelly loam. No timber. Undergrowth, sagebrush.
	From the cor. of secs. 22, 23, 26 and 27.
	S. 89°41' W., bet. secs. 22 and 27.
	Over rolling land through sagebrush undergrowth. Desc. 10 ft. over gentle SW. slope.
1.00	Trail road, bears NW. and SE.
9.00	Small draw, drains S.; asc. 35 ft. over SE. slope.
16.15	Small spur, slopes S.; desc. 15 ft. over SW. slope.
23.40	Draw, drains SE.; asc. 180 ft. over NE. slope.
39.05	Unimproved road, bears about N. 30° W. and S. 30° E.

Dependent Resurvey of the Subdivision, T. 12 N., R. 6 E.

CHAINS	
40.02	The original ¼ Sec. cor. of secs. 22 and 27, monumented with a sandstone, 22x12x3 ins., set and mkd. as desc. in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd. T12N R6E ¼ S22/S27 1964 Bury original stone cor. alongside iron post.
	S. 89°24' W., beginning new measurement. Asc. 10 ft. over NE. slope.
1.35	Telephone line, bears about N. 36° W. and S. 36° E.
1.90	Improved road, on ridge, bears N. 20° W. and S. 20° E.; desc. 130 ft. over W. slope.
15.10	Small draw, drains S.; asc. 10 ft. over E. Slope.
29.05	Small spur, slopes S.; desc. 30 ft. over W. slope.
31.90	Wash, drains S. 20° W.; asc. 60 ft. over SE. slope.
41.05	The cor. of secs. 21, 22, 27 and 28. Land, rolling. Soil, rocky clay loam. No timber. Undergrowth, sagebrush.
	N. 0°29' E., bet. secs. 21 and 22. Over rolling land through sagebrush undergrowth. Asc. 140 ft. over SE. slope.
22.50	Low ridge, bears NE. and SW.; desc. 25 ft. over gentle NW. slope.
35.20	Improved road, bears irregularly E. and W.
40.09	The original ¼ sec. cor. of secs. 21 and 22, monumented with a sandstone, 18x14x3 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and brass cap mkd. T12N R6E ¼ S21|S22 1964 Bury original stone cor. alongside iron post, and raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor.

Dependent Resurvey of the Subdivision, T. 12 N., R. 6 E.

CHAINS	
	N. 2°38' E., beginning new measurement.
	Desc. 15 ft. over gentle NW. slope.
4.00	Trail road, bears NW. and SE.
4.20	Wash, 10 lks. wide, 2 ft. deep, drains NW.; asc. 95 ft. over SW. slope.
15.15	Telephone line, bears about N. 36° W., and S. 36° E.
21.00	Spur, slopes W.; desc. 20 ft. over NW. slope.
28.40	Draw, drains W.; asc. 65 ft. over SW. slope.
40.62	The original cor. of secs. 15, 16, 21 and 22, monumented with a gray sandstone, 18x10x6 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T12N R6E S16 | S15 S21 | S22 1964
	Bury original stone cor. alongside iron post.
	Land, rolling. Soil, rocky clay loam. No timber. Undergrowth, sagebrush.
	From the cor. of secs. 14, 15, 22 and 23.
	N. 89°37' W., bet. secs. 15 and 22.
	Over rolling land through sagebrush undergrowth. Desc. 15 ft. over gentle NW. slope.
7.00	Draw, drains N. 30° E.; asc. 225 ft. over NE. slope.
39.99	The original ¼ sec. cor. of secs. 15 and 22, monumented with a sandstone, 14x14x6 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T12N R6E ¼ S15 S22 1964
	Bury original stone cor. alongside iron post.

CHAINS	
	S. 88°24' W., beginning new measurement.
	Asc. 70 ft. over NE. slope.
36.55	Ridge, bears N. and S.; trail road, curves NE. and S. 20° E.; desc. 10 ft. over gentle SW. slope.
41.86	The cor. of secs. 15, 16, 21 and 22.
	Land, rolling. Soil, clay loam. No timber. Undergrowth, sagebrush.
	N. 0°33' E., bet. secs. 15 and 16.
	Over rolling land through sagebrush undergrowth. Asc. 10 ft. over gentle SW. slope.
1.00	Low ridge, bears E. and W.; desc. 25 ft. over NW. slope.
13.60	Small draw, drains W.; asc. 55 ft. over SW. slope.
30.00	Ridge, bears E. and S. 75° W.; desc. 25 ft. over gentle NW. slope.
36.70	Trail road, bears irregularly E. and curves NW. to N.
40.86	The original ¼ sec. cor. of secs. 15 and 16, monumented with a sandstone, 18x9x6 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T12N R6E ¼ S16|S15 1964
	Bury original stone cor. alongside iron post.
	N. 0°21' W., beginning new measurement.
	Desc. 15 ft. over gentle NW. slope.
5.00	Trail road, bears N. 30° E. and S. 30° W. curving to S.; draw, drains NE.; asc. 15 ft. over SE. slope.
8.80	Point of spur, slopes E.; desc. 35 ft. over NE. slope.
28.30	Head of draw, drains W.; asc. 60 ft. over S. slope.
28.50	Trail road, bears E. and S. 80° W.
40.60	Cor. of fence, with fence bearing S. 88°45' W. and N. 0°32' W., thence along fence.
40.72	The original cor. of secs. 9, 10, 15 and 16, monumented with a sandstone, 16x12x4 ins., set and mkd. as described in the official record.

CHAINS	
	At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone to top, with brass cap mkd. T12N R6E S9 | S10 S16 | S15 1964 Bury original stone cor. alongside iron post. Cor. set in fence line, with road along E. side, bearing irregularly N. and S. Land, rolling. Soil, rocky loam. No timber. Undergrowth, sagebrush.
	From the cor. of secs. 10, 11, 14 and 15. S. 89°22' W., bet. secs. 10 and 15. Over rolling land through dense sagebrush undergrowth. Asc. 15 ft. over NE. slope.
5.20	Low spur, slopes SE.; desc. 15 ft. over gentle SW. slope.
13.50	Draw, drains SE.; asc. 115 ft. over NE. slope.
25.40	Trail road, bears NE. and SW.
40.30	The original ¼ sec. cor. of secs. 10 and 15, monumented with a sandstone, 18x15x12 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone to top, with brass cap mkd. T12N R6E ¼ S10 S15 1964 Bury original stone cor. alongside iron post.
	S. 89°37' W., beginning new measurement. Asc. 10 ft. over NE. slope.
4.70	Same trail road, bears NW. and SE.; slope changes; asc. 90 ft. over SE. slope.
13.60	Same trail road, bears NE. and SW.
23.90	Same trail road, bears NW. and SE.; wash, drains SE.; asc. 50 ft. over NE. slope.
27.90	Same trail road, bears NE. and SW.

De endent Resurvey of the Subdivision, T. 12 N. R. 6 E.

CHAINS	
42.70	Improved road, bears irregularly N. and S.
42.92	The cor. of secs. 9, 10, 15 and 16.
	Land, rolling. Soil, clay loam. No timber. Undergrowth, sagebrush.
	N. 1°34' E., bet. secs. 9 and 10.
	Over rolling land along E. side of fence through sagebrush undergrowth. Desc. 30 ft. over NE. slope.
4.00	Road, bears irregularly N. and S. 10° E.
14.50	Draw, drains SE.; asc. 120 ft. over SW. slope.
30.00	Ridge, bears E. and W.; desc. 25 ft. over NE. slope.
40.05	Point for the ¼ sec. cor. of secs. 9 and 10 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T12N R6E ¼ S9 | S10 1964
	Asc. 45 ft. over SE. slope.
52.00	Ridge, bears NE. and SW.
52.50	Unimproved roads, bears NE., S. and W.
52.84	Fence, bears W. and NE., parallel to road; enter plowed farm land.
67.30	Fence, bears NW. and SE. about 3.00 chs. to cor. and NW. about 14.00 chs., thence curving N.; desc. 30 ft. over NE. slope.
80.10	The original cor. of secs. 3, 4, 9 and 10, monumented with a sandstone, 14x9x6 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground, to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd. T12N R6E S4 | S3 S9 | S10 1964
	Bury original stone cor. alongside iron post.

Dependent Resurvey of the Subdivision, T. 12 N., R. 6 E.

CHAINS	
	Land, rolling, with cultivated dry farm land N. portion. Soil, clay loam. No timber. Undergrowth, sagebrush.
	From the cor. of secs. 2, 3, 10 and 11. S. 88°19' W., bet. secs. 3 and 10. Over rolling land through sagebrush undergrowth. Desc. 20 ft. over SW. slope.
0.22	Highway right of way fence, parallel to highway.
1.60	Center line of state highway No. 3, bears about N. 38° W. and S. 38° E.
4.45	Wash, 10 lks. wide, 3 ft. deep, drains SE.; asc. 40 ft. over gentle NE. slope.
16.75	Old gravel surfaced highway, bears NW. and SE.
26.45	Top of small knoll; desc. 15 ft. over SW. slope.
31.45	Draw drains SE.; asc. 65 ft. over NE. slope.
40.44	Point for the ¼ sec. cor. of secs. 3 and 10 at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd. T12N R6E ¼ S3/S10 1964 Asc. 5 ft. over gentle NE. slope.
42.40	Small spur, slopes SE.; desc. 10 ft. over SW. slope.
46.90	Small draw, drains SE.; asc. 45 ft. over E. slope.
60.45	Top of ridge, bears N. and S.; improved dirt road, bears N. and curves SW.; desc. 35 ft. over NW. slope.
63.50	Fence, bears N. and S. curving SW.
67.30	Draw, drains NE.; asc. 60 ft. over SE. slope.
72.40	Enter plowed farm land, bears NE. and SW.
80.88	The cor. of secs. 3, 4, 9 and 10.
	Land, rolling. Soil, clay loam. No timber. Undergrowth, sagebrush.
	N. 0°09' E., bet. secs. 3 and 4.

Dependent Resurvey of the Subdivision, T. 12 N., R. 6 E.

CHAINS	
	Over rolling farm land. Asc. 15 ft. over gently rolling SE. slope.
10.00	Ridge, bears E. and W.; desc. 200 ft. over N. slope.
12.00	Leave farm land, bears E. and W.; enter dense sagebrush.
36.41	Fence, bears E. and W.
40.70	Point for the ¼ sec. cor. of secs. 3 and 4 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd. T12N R6E ¼ S4 | S3 1964
	Raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor.
	Cor. located on small spur, slopes N., in cultivated land.
	Leave sagebrush, bears SE. and SW.; enter farm land; desc. 50 ft. over NE. slope.
53.11	Highway right of way fence, bears SE. and NW. about 3.00 chs., thence S.
53.50	Wash, in canyon, drains NW.; asc. 250 ft. over steep SW. slope.
54.72	Center line of state highway No. 3, bears NW. and SE.
56.10	Highway right of way fence, parallel to highway.
72.00	Top of ascent, slopes sharply W.; desc. 155 ft. over steep NW. slope.
79.95	Draw, drains S. 80° W.; asc. 75 ft. over steep S. slope. Small patch of aspen timber in draw.
83.13	The original closing cor. of secs. 3 and 4, on the N. bdy. of the Tp., (Third Standard Parallel North), monumented with a washed boulder, 14x10x8 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd. T13N R6E S34 S4 | S3 C | C T12N R6E 1964
	Bury original stone cor. alongside iron post.

Dependent Resurvey of the Subdivision, T. 12 N., R. 6 E.

CHAINS

From this cor., the standard cor. of secs. 33 and 34, T. 13 N., R. 6 E., bears N. 89°51' W., 4.70 chs. dist., hereinbefore described.

Land, rolling, mountainous.
Soil, rocky clay loam.
Timber, aspen in extreme N. portion.
Undergrowth, sagebrush.

Point for the N. ¼ sec. cor. of sec. 3, on the N. bdy. of the Tp., and mid point bet. the closing cor. of secs. 3 and 4, and the closing cor. of secs. 2 and 3.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd.

T13N R6E

¼ S3

T12N R6E

1964

From this cor., the standard ¼ sec. cor. of sec. 34, T. 13 N., R. 6 E., bears N. 89°21' W., 3.725 chs. dist., hereinbefore described.

From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp.

N. 0°58' E., bet. secs. 32 and 33.

Over rolling land through dense sagebrush and scattered service berry undergrowth. Asc. 40 ft. over gentle SE. slope; along W. side of fence.

26.00 Ridge, bears E. and W.; desc. 45 ft. over gentle N. slope.

40.86 The original ¼ sec. cor. of secs. 32 and 33, monumented with a sandstone, 16x14x2 ins., set and mkd. as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a collar of stone, with brass cap mkd.

T12N R6E

¼

S32|S33

1964

Bury original stone cor. alongside iron post, and raise a mound of stone, 4 ft. base, 2 ft. high, W. of cor.

Cor. located on steep N. slope about 1.00 ch. W. of N. and S. fence line.

N. 0°39' W., beginning new measurement.

Desc. 100 ft. over steep N. slope.

Dependent Resurvey of the Subdivision, T. 12 N., R. 6 E.

CHAINS	
3.20	Otter Creek, (dry at this point), drains E.; asc. 210 ft. over steep S. slope.
4.85	Improved road, bears E. and W.
19.90	Slope changes; asc. 85 ft. over SE. slope.
26.30	Fence, bears about N. 16° W., curving N. and S. 16° E., curving S.
40.22	The original cor. of secs. 28, 29, 32 and 33, monumented with a sandstone, 18x11x8 ins., set and mkd. as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T12N R6E

S29	S28
S32	S33

1964

Bury original stone cor. alongside iron post, and raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor.

Land, rolling.
Soil, rocky loam.
No timber.
Undergrowth, sagebrush and scattered service berry.

From the cor. of secs. 27 and 28, 33 and 34.

N. 88°50' W., bet. secs. 28 and 33.

Over rolling land through sagebrush undergrowth. Asc. 100 ft. over SE. slope.

27.75	Spur, slopes SE.; desc. 25 ft. over gentle SW. slope.
40.12	The original ¼ sec. cor. of secs. 28 and 33, monumented with a sandstone, 17x12x4 ins., set and mkd. as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T12N R6E

	S28
¼	S33

1964

Bury original stone cor. alongside iron post, and raise a mound of stone, 3½ ft. base, 1½ ft. high, N. of cor.

S. 89°08' W., beginning new measurement.

1.00	Wash, drains SE.; asc. 90 ft. over gentle rolling SE. slope.

FIELD NOTE PAPER

481

Dependent Resurvey of the Subdivision, T. 12 N., R. 6 E.

CHAINS	
21.35	Spur, slopes S.; desc. 180 ft. over steep NW. slope.
33.85	Draw, drains S. 30° E.; asc. 175 ft. over steep E. slope.
39.98	The cor. of secs. 28, 29, 32 and 33.
	Land, rolling. Soil, rocky clay loam. No timber. Undergrowth, sagebrush.
	N. 1°13' E., bet. secs. 28 and 29.
	Over rolling land through dense sagebrush and scattered service berry. Desc. 10 ft. along E. slope.
7.00	Head of draw, drains SE.; asc. 190 ft. over SE. slope.
23.50	Wash, drains SE.; continue ascent.
39.10	Ridge, bears E. and W.; desc. 10 ft. over gentle N. slope.
40.29	Point for the ¼ sec. cor. of secs. 28 and 29 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T12N R6E ¼ S29 | S28 1964
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of cor.
	Desc. 50 ft. over gentle N. slope.
48.75	Wash, 10 lks. wide, 1 ft. deep, drains E.; asc. 60 ft. over S. slope.
62.00	Ridge, bears E. and W.; desc. 55 ft. over N. slope.
62.47	Fence, bears about N. 79° E. and S. 79° W.
76.40	Draw, drains about N. 75° E.; asc. 10 ft. over gentle SE. slope.
80.58	The original cor. of secs. 20, 21, 28 and 29, monumented with a sandstone, 22x5x4 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T12N R6E S20 | S21 S29 | S28 1964

218402

Dependent Resurvey of the Subdivision, T. 12 N., R. 6 E.

CHAINS	
	Bury original stone cor. alongside iron post, and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	Land, rolling. Soil, clay loam. No timer. Undergrowth, sagebrush.
	From the cor. of secs. 21, 22, 27 and 28.
	N. 89°25' W., bet. secs. 21 and 28.
	Over rolling land through sagebrush undergrowth. Desc. 60 ft. over SW. slope.
4.10	Draw, drains SE.; asc. 125 ft. over rolling NE. slope.
40.02	The original ¼ sec. cor. of secs. 21 and 28, monumented with a sandstone, 12x8x3 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd. T12N R6E ¼ S21/S28 1964
	Bury original stone cor. alongside iron post.
	S. 89°23' W., beginning new measurement.
	Asc. 50 ft. over NE. slope.
22.75	Spur, slopes NE.; desc. 30 ft. over NW. slope.
32.50	Draw, drains NE.; asc. 10 ft. over gentle SE. slope.
38.50	The cor. of secs. 20, 21, 28 and 29.
	Land, rolling. Soil, clay loam. No timber. Undergrowth, sagebrush.
	N. 0°03' E., bet. secs. 20 and 21.
	Over rolling land through sagebrush undergrowth. Asc. 40 ft. over SE. slope.
5.50	Ridge, bears E. and W.; trail road, bears N. 80° E. and S. 70° W.; desc. 75 ft. over NE. slope.
23.00	Draw, drains S. 75° E.
24.75	Improved dirt road, bears about N. 75° W. curving SW. and S. 75° E. curving E., asc. 25 ft. over SW. slope.
35.00	Small spur, slopes W.; desc. 15 ft. over NW. slope.

CHAINS	
38.20	Small draw, drains SW.; asc. 30 ft. over SE. slope.
40.66	Point for the ¼ sec. cor. of secs. 20 and 21 at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone to top, with brass cap mkd. T12N R6E ¼ S20|S21 1964 Asc. 40 ft. over SE. slope.
61.90	Low ridge, bears E. and W.; desc. 30 ft. over gentle N. slope.
81.32	The original cor. of secs. 16, 17, 20 and 21, monumented with a washed boulder, 12x10x6 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd. T12N R6E S17|S16 S20|S21 1964 Bury original stone cor. alongside iron post, and raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of cor. Land, rolling. Soil, rocky clay loam. No timber. Undergrowth, sagebrush.
	From the cor. of secs. 15, 16, 21 and 22. N. 88°15' W., bet. secs. 16 and 21. Over rolling mountainous land through dense sagebrush undergrowth. Desc. 165 ft. over SW. slope.
20.40	Telephone line, bears about N. 36° W. and S. 36° E.
33.60	Small draw, drains NW.; trail road, bears NW. and SE.; desc. 15 ft. over W. slope.
36.10	Draw, drains NE.; asc. 25 ft. over SE. slope.
40.11	The original ¼ sec. cor. of secs. 16 and 21, monumented with a limestone, 20x10x4 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground, and in a collar of stone, with brass cap mkd.

Dependent Resurvey of the Subdivision, T. 12 N., R. 6 E.

CHAINS	
	T12N R6E ¼ S16/S21 1964
	Bury original stone cor. alongside iron post.
	S. 89°05' W., beginning new measurement.
	Asc. 50 ft. over SE. slope.
4.50	Small spur, slopes NE.; desc. 25 ft. over NW. slope.
19.75	Draw, drains NE.; asc. 50 ft. over SE. slope.
26.65	Slope changes; asc. 25 ft. over NE. slope.
40.52	The cor. of secs. 16, 17, 20 and 21.
	Land, rolling, mountainous. Soil, rocky clay loam. No timber. Undergrowth, sagebrush.
	N. 0°08' W., bet. secs. 16 and 17.
	Over mountainous land through dense sagebrush undergrowth. Desc. 150 ft. over N. slope.
9.40	Trail road, bears NE. and SW.
24.40	Canyon, drains S. 75° W.; asc. 155 ft. over SE. slope.
33.00	Spur, slopes SW.; desc. 60 ft. over NW. slope.
39.75	Small draw, drains S. 15° W.
40.16	Point for the ¼ sec. cor. of secs. 16 and 17 at proportionate dist.; there is no remaining evidence of the original cor.
	set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone to top, with brass cap mkd. T12N R6E ¼ S17|S16 1964
	Asc. 230 ft. over SE. slope.
71.60	Ridge, bears E. and W.; desc. 50 ft. over N. slope.
77.75	Draw, drains W.; asc. 25 ft. over S. slope.
79.57	Fence, bears about N. 89°30' E. and S. 89°30' W.
80.32	The original cor. of secs. 8, 9, 16 and 17, monumented with a limestone, 18x12x7 ins., set and mkd. as described in the official record.
	At the cor. point

CHAINS	
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T12N R6E S8 | S9 S17 | S16 1964 Bury original stone cor. alongside iron post, and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. Land, mountainous. Soil, rocky clay loam. No timber. Undergrowth, sagebrush and scattered service berry.
	From the cor. of secs. 9, 10, 15 and 16. S. 89°23' W., bet. secs. 9 and 16. Over rolling mountainous land through dense sagebrush undergrowth. Desc. 15 ft. over gentle W. slope; along N. side of fence.
21.55	Small draw, drains S.; asc. 35 ft. over SE. slope.
29.25	Ridge, bears N. and S.; desc. 70 ft. over SW. slope.
40.25	Draw, drains S. 30° E.
40.47	Point for the ¼ sec. cor. of secs. 9 and 16 at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and brass cap mkd. T12N R6E ¼ S9 S16 1964 Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. Cor. is located 56 lks. N. of fence bearing about N. 88°45' E. and S. 88°45' W. Asc. 170 ft. over E. slope.
53.05	Ridge, bears N. and S.; desc. 50 ft. over gentle SW. slope.
59.95	Trail road, bears N. and S.
78.24	Telephone line, bears about N. 36° W. and S. 36° E.
80.94	The cor. of secs. 8, 9, 16 and 17. Land, rolling. Soil, rocky clay loam. No timber. Undergrowth, dense sagebrush and scattered service berry.

Dependent Resurvey of the Subdivision, T. 12 N., R. 6 E.

CHAINS

N. 0°04' W., bet. secs. 8 and 9.

Over rolling mountainous land through sagebrush and scattered service berry undergrowth. Asc. 50 ft. over gentle SW. slope.

3.72 Telephone line, bears about N. 36° W. and S. 36° E.

5.90 Trail road, bears about N. 75° E. and S. 75° W.

6.90 Ridge, bears E. and W.; desc. 100 ft. over NW. slope. Enter aspen timber.

9.00 Leave aspen timber.

15.80 Draw, drains SW.; asc. 130 ft. over SW. slope.

28.75 Ridge, bears NW. and SE.; desc. 90 ft. over NE. slope.

36.80 Enter aspen timber.

40.48 The original ¼ sec. cor. of secs. 8 and 9, monumented with a sandstone, 18x10x6 ins., set and mkd. as describe in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. i the ground, and in a collar of stone to top, with brass cap mkd.

T12N R6E
¼
S8|S9
1964

Bury original stone cor. alongside iron post.

N. 1°24' W., beginning new measurement.

Desc. 20 ft. over NE. slope.

8.00 Bottom of descent in small swale; leave aspen timber; asc. 40 ft. over SE. slope.

12.90 Low spur, slopes NE.; desc. 195 ft. over NW. slope.

31.50 Draw, drains NE.; asc. 50 ft. over SE. slope.

34.60 Spur, slopes E.; desc. 15 ft. along E. slope.

40.96 The cor. of secs. 4, 5, 8 and 9, monumented with a conglomerate stone, 20x10x8 ins., set and mkd. as described in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. i the ground, and in a collar of stone to top, with brass cap mkd.

T12N R6E

S5|S4
S8|S9

1964

Bury original stone cor. alongside iron post.

Dependent Resurvey of the Subdivision, T. 12 N., R. 6 E.

CHAINS	
	Cor. located at cor. of old fences from E. and about N. 1° E. Land, rolling mountainous. Soil, clay loam. Timber, scattered aspen S. portion; no timber N. portion. Undergrowth, sagebrush and service berry.
	From the cor. of secs. 3, 4, 9 and 10. N. 89°33' W., bet. secs. 4 and 9. Over rolling dry farm land. Asc. 20 ft. over gentle NE. slope.
5.25	Ridge, bears N. and SE.; desc. 50 ft. over SW. slope.
7.25	Fence, bears N. and S., curving to SE.
19.95	Leave cultivated land; enter sagebrush.
30.95	Shallow draw, drains NE.; asc. 25 ft. over gentle NE. slope.
42.05	Fence, on ridge, bears N. and S.; enter cultivated land.
42.08	Point for the ¼ sec. cor. of secs. 4 and 9 at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone to top, with brass cap mkd. T12N R6E ¼ S4/S9 1964 Desc. 70 ft. over NW. slope.
67.85	Shallow draw, drains NE.; asc. 35 ft. over gentle SE. slope.
73.25	Fence, bears NW. and SE. and N. 89°33' W., thence along fence line; leave cultivated land.
73.35	Trail road, bears NW. and SE.
84.16	The cor. of secs. 4, 5, 8 and 9. Land, rolling dry farm land. Soil, clay loam. No timber. Undergrowth, sagebrush in portions.
	N. 0°57' E., bet. secs. 4 and 5. Over rolling land through sagebrush undergrowth. Asc. 65 ft. over gentle SE. slope along old fence line.
9.00	Trail road, bears NW. and SE.
9.15	Fence cor., with fence bearing SE.; continue along fence line.

Dependent Resurvey of the Subdivision, T. 12 N., R. 6 E.

CHAINS	
12.25	Top of ascent, slopes E.; desc. 100 ft. over gentle NE. slope.
40.71	The original ¼ sec. cor. of secs. 4 and 5, monumented with a sandstone, 18x12x8 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone to top, with brass cap mkd.
	T12N R6E ¼ S5 | S4 1964
	Bury original stone cor. alongside iron post.
	N. 2°27' E., beginning new measurement.
	Continue along fence line; desc. 50 ft. over NE. slope.
8.00	Draw, drains W.; asc. 65 ft. over SW. slope.
18.00	Spur, slopes SE.; desc. 20 ft. over NE. slope.
18.50	Trail road, bears SE. and NW.
18.65	Cor. of fence, with fence bearing about S. 60° E. curving E., and N. 9° W.; leave fence line.
22.35	Draw, drains NE.; asc. 25 ft. over SE. slope.
27.75	Ridge, bears NW. and SE.; desc. 210 ft. over NE. slope.; enter aspen timber.
43.08	The original closing cor. of secs. 4 and 5, on the N. bdy. of the Tp., (Third Standard Parallel North) monumented with a sandstone, 12x8x6 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T13N R6E S33 S5 | S4 C | C T12N R6E 1964
	Bury original stone cor. alongside iron post.
	From this cor., the standard cor. of secs. 32 and 33, T. 13 N., R. 6 E., bears N. 89°07' W., 3.49 chs. dist., hereinbefore described.

Dependent Resurvey of the Subdivision, T. 12 N., R. 6 E.

CHAINS	
	Land, rolling mountainous. Soil, rocky clay loam. Timber, aspen in extreme N. portion. Undergrowth, sagebrush and scattered service berry.
	Point for the N. ¼ sec. cor. of sec. 4, on the N. bdy. of the Tp., and mid point bet. the closing cor. of secs. 3 and 4, and the closing cor. of secs. 4 and 5. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd. T13N R6E ¼ S4 T12N R6E 1964 From this cor., the standard ¼ sec. cor. of sec. 33, T. 13 N., R. 6 E., bears N. 89°07' W., 4.095 chs. dist., hereinbefore described.
	From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp. N. 1°37' E., bet. secs. 31 and 32. Over mountainous land through scattered aspen timber and sagebrush undergrowth. Asc. 15 ft. over SW. slope.
3.00	Ridge, bears about N. 75° W. and S. 75° E.; thence by triangulation, desc. about 300 ft. over NE. slope. Enter aspen timber.
30.01	End triangulation; leave timber.
32.75	Otter Creek, (dry at this point), drains irregularly E.; asc. 20 ft. over S. slope.
39.50	Improved dirt road, bears E. and W.
40.19	The original ¼ sec. cor. of secs. 31 and 32, monumented with a sandstone, 40x30x24 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone to top, with brass cap mkd. T12N R6E ¼ S31|S32 1964 Set original stone cor. alongside iron post, and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. N. 0°21' W., beginning new measurement. Asc. 185 ft. over steep S. slope.

Dependent Resurvey of the Subdivision T. 12 N. R. 6 E.

CHAINS	
7.65	Ridge, bears E. and W.; desc. 110 ft. over N. slope.
15.00	Draw, with trail road in bottom, drains E.; asc. 175 ft. over S. slope.
25.00	Ridge, bears E. and W.; desc. 70 ft. over N. slope.
34.00	Draw, drains E.; asc. 65 ft. over SE. slope.
40.74	The original cor. of secs. 29, 30, 31 and 32, monumented with a sandstone, 15x10x4 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T12N R6E S30 | S29 S31 | S32 1964
	Bury original stone cor. alongside iron post, and raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor.
	Land, mountainous. Soil, rocky loam. Timber, aspen in S. portion. Undergrowth, dense sagebrush, with willows along Otter Creek.
	From the cor. of secs. 28, 29, 32 and 33.
	N. 89°16' W., bet. secs. 29 and 32.
	Over rolling mountainous land through dense sagebrush undergrowth. Asc. 25 ft. over E. slope.
1.00	Ridge, bears N. and S.
1.24	Fence, bears about N. 5° W. and S. 5° E. curving S.; desc. 65 ft. over SW. slope.
17.80	Draw, drains S.; asc. 75 ft. over E. slope.
24.00	Small spur, slopes S.; desc. 20 ft. over W. slope.
33.70	Small draw, drains S.; asc. 40 ft. over E. slope.
39.69	Point for the ¼ sec. cor. of secs. 29 and 32 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T12N R6E ¼ S29 S32 1964
	Asc. 15 ft. over E. slope.
43.70	Small spur, slopes S.; desc. 20 ft. over SW. slope.

CHAINS	
49.20	Draw, drains SW.; asc. 40 ft. over SE. slope.
53.50	Spur, slopes S.; desc. 120 ft. over W. slope.
58.50	Draw, drains S.; asc. 170 ft. over SE. slope.
79.38	The cor. of secs. 29, 30, 31 and 32.
	Land, rolling mountainous. Soil, rocky clay loam. No timber. Undergrowth, sagebrush.
	N. 87°57' W., bet. secs. 30 and 31.
	Over mountainous land through sagebrush undergrowth. Asc. 15 ft. over SE. slope.
2.00	Top of ascent, slopes S.; desc. 20 ft. over gentle SW. slope.
20.00	Draw, drains SE. from N.; asc. 130 ft. over NE. slope.
24.30	Enter aspen timber, bears N. and S.
30.00	Leave timber, bears NW. and SE.
40.30	The original ¼ sec. cor. of secs. 30 and 31, monumented with a washed boulder, 18x9x9 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and brass cap mkd.
	T12N R6E
	¼ S30 / S31
	1964
	Bury original stone cor. alongside iron post, and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
	S. 83°55' W., beginning new measurement.
	Desc. 105 ft. over steep SW. slope.
6.50	Draw, with trail road in bottom, drains SE.; asc. 195 ft. over NE. slope. Enter aspen timber.
9.40	Leave timber, bears N. and S.
12.60	Enter aspen timber, bears N. and S.
17.00	Leave timber, bears N. and S.
26.55	Fence, bears about N. 57° E. and S. 57° W.
26.65	Trail road, parallel to fence.
35.00	Enter aspen timber.
37.86	The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp.

Dependent Resurvey of the Subdivision, T. 12 N., R. 6 E.

CHAINS

Land, rolling mountainous.
Soil, rocky loam.
Timber, aspen W. portion.
Undergrowth, sagebrush.

From the cor. of secs. 29, 30, 31 and 32.

N. 0°42' E., bet. secs. 29 and 30.

Over rolling mountainous land through dense sagebrush undergrowth. Asc. 25 ft. over SE. slope.

6.90 Ridge, bears E. and W.; desc. 5 ft. along E. slope.

15.00 Spur, slopes E.; desc. 50 ft. over NE. slope. Enter a timber.

19.00 Leave aspen timber.

21.80 Draw, drains SE.; asc. 105 ft. over steep SE. slope.

29.90 Small spur, slopes SE.; desc. 10 ft. over gentle NE. slope.

39.00 Shallow draw, drains SE.

40.78 Point for the ¼ sec. cor. of secs. 29 and 30 at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass alongside, and brass cap mkd.

T12N R6E
¼
S30|S29
1964

Raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of cor.

Cor. set in fence, bearing about N. 63° E. and S. 63° W., with dim trail road along S. side.

Asc. 90 ft. over SW. slope.

52.70 Ridge, bears E. and W.; desc. 65 ft. over N. slope.

62.75 Improved dirt road, bears about N. 80° E. and S. 80° W., in draw, drains N. 80° E.; asc. 60 ft. over S. slope.

63.10 Fence, bears about N. 80° E. about 8.00 chs., thence N. and S. 80° W., about 4.00 chs., thence S. Enter cultivated land.

80.00 Ridge, bears E. and W.; desc. 5 ft. over gentle N. slope.

81.56 Point for the cor. of secs. 19, 20, 29 and 30 at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2½ ins. diam.,24 ins. in the ground, and in a collar of stone to top, with brass cap mkd.

lent Resurvey of the Subdivision, T. 12 N., R. 6 E.

CHAINS	
	T12N R6E S19 | S20 S30 | S29 1964 Land, rolling. Soil, loam. Timber, aspen in S. portion. Undergrowth, sagebrush.
	From the cor. of secs. 20, 21, 28 and 29. N. 88°39' W., bet. secs. 20 and 29. Over rolling land through dense sagebrush undergrowth. Asc. 50 ft. over gentle SE. slope.
18.60	Trail road, on low ridge, bears NE. and SW.; desc. 20 ft. over gentle NW. slope.
40.11	Point for the ¼ sec. cor. of secs. 20 and 29 at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T12N R6E ¼ S20 S29 1964 Desc. 35 ft. over NW. slope.
46.50	Improved dirt road, in draw, draining NE.; asc. 50 ft. over SE. slope.
65.00	Small draw, drains SE.; asc. 40 ft. over NE. slope.
71.65	Fence, bears S. and N. about 3.00 chs., thence W.; enter cultivated land.
80.22	The cor. of secs. 19, 20, 29 and 30. Land, rolling. Soil, clay loam. No timber. Undergrowth, dense sagebrush.
	S. 88°18' W., bet. secs. 19 and 30. Over rolling cultivated land. By triangulation, asc. about 20 ft. over NE. slope.
5.00	Low ridge, bears N. and S.; desc. about 100 ft. over gently rolling W. slope.
40.41	Point for the ¼ sec. cor. of secs. 19 and 30, at proportionate dist.; there is no remaining evidence of the original cor. End triangulation. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

De endent Resurvey of the Subdivision, T. 12 N., R. 6 E.

CHAINS

T12N R6E

¼ S19/S30

1964

Cor. located in cultivated land about 3.00 chs. S. of E. and W. fence.

Thence, by triangulation, desc. about 70 ft. over gentle W. slope.

70.00 Draw, drains N.; asc. about 50 ft. over E. slope. Leave cultivated land.

74.00 Enter dense undergrowth.

79.31 The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of th Tp.

Land, rolling and cultivated.
Soil, loam.
No timber.
Undergrowth, dense service berry and young aspen W. portion.

From the cor. of secs. 19, 20, 29 and 30.

N. 0°41' E., bet. secs. 19 and 20.

Over rolling cultivated land. Asc. 15 ft. over gentle SE. slope.

3.13 Fence, bears E. and W.; leave cultivated land, enter dense sagebrush.

8.55 Ridge, bears NE. and SW.; desc. 40 ft. over gently rolling NW. slope.

40.78 The original ¼ sec. cor. of secs. 19 and 20, monumented with a sandstone, 16x14x6 ins., set and mkd. as describe in the official record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. i the ground, with glass at base, and brass cap mkd.

T12N R6E

¼

S19|S20

1964

Bury original stone cor. alongside iron post, and raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of cor.

N. 1°48' E., beginning new measurement.

Desc. 10 ft. over NW. slope.

2.85 Wash, drains W.; asc. 20 ft. over S. slope.

8.20 Ridge, bears NE. and W.; desc. 280 ft. over NW. slope.

·endent Resurvey of the Subdivision, T. 12 N., R. 6 E.

CHAINS	
40.85	The original cor. of secs. 17, 18, 19 and 20, monumented with a limestone, 18x12x8 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 3½ ft. base to top, with brass cap mkd. T12N R6E S18 | S17 S19 | S20 1964 Bury original stone cor. alongside iron post. Land, rolling S. portion; mountainous N. portion. Soil, rocky clay loam. No timber. Undergrowth, sagebrush.
	From the cor. of secs. 16, 17, 20 and 21. S. 89°42' W., bet. secs. 17 and 20. Over rolling mountainous land through dense sagebrush undergrowth. Asc. 40 ft. over SE. slope.
16.00	Ridge, bears NE. and SW.; trail road, along same; desc. 85 ft. over NW. slope.
30.50	Small draw, drains N.; asc. 35 ft. over NE. slope.
33.40	Spur, slopes NW.; desc. 25 ft. over SW. slope.
40.03	The original ¼ sec. cor. of secs. 17 and 20, monumented with a sandstone, 11x7x5 ins., set and mkd. as described in the official record. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and brass cap mkd. T12N R6E ¼ S17 S20 1964 Bury original stone cor. alongside iron post, and raise a mound of stone, 2½ ft. base, 1½ ft. high, N. of cor.
	N. 86°40' W., beginning new measurement. Desc. 70 ft. over SW. slope.
10.50	Draw, drains NW.; asc. 50 ft. over NE. slope.
24.00	Top of ascent, slopes N.; desc. 150 ft. over steep NW. slope.
38.55	The cor. of secs. 17, 18, 19 and 20.

Dependent Resurvey of the Subdivision, T. 12 N., R. 6 E.

CHAINS

Land, rolling mountainous.
Soil, rocky clay loam.
No timber.
Undergrowth, dense sagebrush and scattered service berry.

S. 88°22' W., bet. secs. 18 and 19.

Over mountainous land through dense sagebrush and scatte - ed service berry undergrowth. Desc. 20 ft. over NW. slope.

1.50 Draw, drains NE.; asc. 135 ft. over steep SE. slope.

8.15 Spur, slopes N.; desc. 295 ft. over steep W. slope.

19.80 Draw, drains N.; asc. 290 ft. over steep SE. slope.

40.82 Point for the ¼ sec. cor. of secs. 18 and 19 at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. i the ground, and in a collar of stone, with brass cap mkd.

T12N R6E

¼ S18 / S19

1964

Desc. 105 ft. over NW. slope.

57.15 Draw, drains N.; asc. 55 ft. over E. slope.

63.25 Spur, slopes N.; desc. 25 ft. over W. slope.

77.10 Draw, drains N.; asc. 45 ft. over SE. slope. Enter dense undergrowth and aspen timber.

81.24 The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp.

Land, mountainous.
Soil, rocky clay loam.
Timber, aspen in extreme W. portion.
Undergrowth, sagebrush and scattered service berry.

From the cor. of secs. 17, 18, 19 and 20.

N. 1°21' W., bet. secs. 17 and 18.

Over mountainous and broken land through dense undergrowth. Desc. 70 ft. over NW. slope.

3.00 Draw, drains NE.; asc. 15 ft. over SE. slope.

9.50 Top of ascent, slopes E.; desc. 105 ft. over NE. slope.

29.50 Spur, slopes NE.; desc. 185 ft. over steep NW. slope.

39.64 Point for the ¼ sec. cor. of secs. 17 and 18 at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. i the ground, and in a collar of stone to top, with brass

FIELD NOTE PAPER

497

Dependent Resurvey of the Subdivision, T. 12 N., R. 6 E.

CHAINS	
	cap mkd. T12N R6E ¼ S18 | S17 1964
	Cor. set at base of steep NW. slope.
	Desc. 20 ft. over NW. slope.
44.00	Dim trail road, bears SE. and NW., curving to N.
45.50	Canyon, drains NW.; asc. 65 ft. over SW. slope.
49.80	Top of ascent, slopes W.; desc. 145 ft. over steep NW. slope.
56.20	Same canyon, drains NE.; asc. 90 ft. over SE. slope.
57.80	Same trail road, bears NE. and SW.
65.20	Point of rocky spur, slopes E.; desc. 155 ft. over steep NE. slope.
73.00	Same canyon, drains NW.; asc. 145 ft. over SE. slope.
75.00	Same trail road, bears NW. and SE.
79.28	Point for the cor. of secs. 7, 8, 17 and 18 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone to top, with brass cap mkd. T12N R6E S7 | S8 S18 | S17 1964
	Land, mountainous. Soil, rocky. No timber. Undergrowth, sagebrush, oak brush and service berry.
	From the cor. of secs. 8, 9, 16 and 17.
	S. 88°43' W., bet. secs. 8 and 17.
	Over rolling mountainous land through dense undergrowth. Desc. 85 ft. over rolling SW. slope.
16.70	Draw, drains S.; asc. 30 ft. over SE. slope.
19.15	Spur, slopes SW.; desc. 35 ft. over NW. slope.
24.65	Draw, drains SW.; asc. 10 ft. over gentle SE. slope.
34.25	Spur, slopes SW.; desc. 40 ft. over NW. slope.
40.17	The original ¼ sec. cor. of secs. 8 and 17, monumented with a sandstone, 16x14x3 ins., set and mkd. as described in the official record.
	At the cor. point

Dependent Resurvey of the Subdivision, T. 12 N., R. 6 E.

CHAINS	
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone to top, with brass cap mkd. T12N R6E ¼ S8/S17 1964 Bury original stone cor. alongside iron post.
	N. 87°23' W., beginning new measurement.
	Desc. 105 ft. over NW. slope.
5.50	Draw, drains SW.; asc. 105 ft. over SE. slope. Enter scattered scrub juniper timber.
19.40	Top of ascent, slopes S.; desc. 225 ft. over steep SW. slope.
31.50	Top of ledges, about 20 ft. high, bears NW. and SE.; leave timber; desc. 315 ft. over steep SW. slope.
39.00	Wash, drains S.; asc. 30 ft. over SE. slope.
39.98	The cor. of secs. 7, 8, 17 and 18.
	Land, mountainous. Soil, rocky. Timber, scrub juniper W. portion. Undergrowth, sagebrush and service berry.
	S. 89°17' W., bet. secs. 7 and 18.
	Over mountainous land through dense undergrowth. By triangulation; asc. about 100 ft. over SE. slope.
6.00	Ledgy spur, slopes SW.; desc. about 150 ft. over NW. slope.
19.80	Canyon, with dim trail road along same, drains N.; asc. about 70 ft. over NE. slope. Enter dense service berry and oak brush.
27.80	Point of spur, slopes N.; desc. about 700 ft. over NW. slope.
37.55	Lake Town Canyon, with stream of water, 2 lks. wide, 4 ins. deep, flows NE.; asc. 65 ft. over SE. slope. Leave dense service berry and oak brush.
39.15	Improved dirt road, bears NE. and SW.
40.44	Point for the ¼ sec. cor. of secs. 7 and 18 at proportionate dist.; there is no remaining evidence of the original cor. End triangulation.
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base to top, with brass cap mkd.

NOTE PAPER

Dependent Resurvey of the Subdivision, T. 12 N., R. 6 E.

CHAINS	
	T12N R6E ¼ S7/S18 1964
	Asc. 400 ft. over steep and ledgy SE. slope.
58.30	Spur, slopes S.; desc. 135 ft. over SW. slope.
69.70	Draw, drains SE.; asc. 220 ft. over NE. slope.
78.90	Enter dense aspen timber.
84.50	Leave dense timber.
84.73	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp.
	Land, mountainous. Soil, rocky clay loam. Timber, aspen. Undergrowth, dense sagebrush, service berry and oak brush.
	From the cor. of secs. 7, 8, 17 and 18.
	N. 6°16' E., bet. secs. 7 and 8.
	Over steep, mountainous land through scattered juniper timber. By triangulation; asc. about 255 ft. over SE. slope.
18.55	End triangulation; spur, slopes SW.; asc. 20 ft. over SW. slope.
26.95	Spur, slopes W.; desc. 165 ft. along steep, rocky W. slope.
39.87	The original ¼ sec. cor. of secs. 7 and 8, monumented with a limestone, 14x10x2 ins., set and mkd. as described in the official record.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base to top, with brass cap mkd. T12N R6E ¼ S7|S8 1964
	Bury original stone cor. alongside iron post.
	N. 5°49' W., beginning new measurement.
	Asc. 10 ft. along steep W. slope.
4.60	Rocky spur, slopes W.; desc. 145 ft. over NW. slope along W. side of low limestone ledges.
10.00	Spur, slopes NW.; desc. 460 ft. over steep NE. slope; enter dense service berry and oak brush.

De[illegible]ent Resurvey of the Subdivision, T. 12 N., R. 6 E.

CHAINS	
23.50	Draw, drains about N. 20° W.; desc. along E. side of draw.
25.00	Draw, drains W.; asc. 300 ft. over steep and rocky SW. slope.
40.70	Rocky spur, slopes W.; desc. 10 ft. over ledge NW. slope.
41.14	Point for the cor. of secs. 5, 6, 7 and 8 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T12N R6E
	S6 | S5
	S7 | S8
	1964
	Cor. set at base of small ledge, 10 ft. high, bears NW. and SE.
	Land, mountainous. Soil, rocky. Timber, scattered juniper S. portion. Undergrowth, sagebrush, service berry and oak brush.
	From the cor. of secs. 4, 5, 8 and 9.
	S. 89°55' W., bet. secs. 5 and 8.
	Over mountainous land through dense sagebrush undergrowth. Asc. 175 ft. over E. slope.
16.15	Ridge, curves NE. and SE.; desc. 165 ft. over W. slope.
22.30	Trail road, bears NE. and SW.
32.15	Small draw, drains S., asc. 15 ft. over NE. slope.
35.00	Top of ascent, slopes N.; desc. 35 ft. over NW. slope.
39.41	Point for the ¼ sec. cor. of secs. 5 and 8 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone to top, with brass cap mkd.
	T12N R6E
	¼ S5 / S8
	1964
	Desc. 225 ft. over NW. slope.
55.06	Telephone line, bears about N. 36° W. and S. 36° E.
55.45	Small wash, drains NW.
59.85	Draw, drains N.; asc. 35 ft. over E. slope.

Dependent Resurvey of the Subdivision, T. 12 N., R. 6 E.

CHAINS	
61.05	Rocky spur, slopes N.; desc. 250 ft. over steep NW. slope.
78.82	The cor. of secs. 5, 6, 7 and 8. Land, mountainous. Soil, rocky. No timber. Undergrowth, sagebrush and service berry.
	S. 89°36' W., bet. secs. 6 and 7. Over mountainous land through sagebrush undergrowth. By triangulation; desc. about 250 ft. over steep NW. slope.
16.90	Improved road, bears irregularly N. and S.
17.90	Lake Town Canyon, with stream of water, 2 lks. wide, 4 ins. deep, flows N.; asc. about 110 ft. over NE. slope.
23.90	Point of spur, slopes NE.; desc. about 100 ft. over NW. slope.
26.90	Draw, drains NE.; asc. about 600 ft. over steep and rocky SE. slope.
39.91	Point for the ¼ sec. cor. of secs. 6 and 7 at proportionate dist.; there is no remaining evidence of the original cor. End triangulation. Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd. T12N R6E ¼ S6/S7 1964 Cor. located on small spur, slopes SE. Desc. 65 ft. over SW. slope.
44.35	Draw, drains SE.; asc. 130 ft. over NE. slope.
54.40	Ridge, bears NE. and SW.; desc. 235 ft. over W. slope, changing to SW. slope.
83.91	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp. Land, mountainous. Soil, rocky gravelly loam. No timber. Undergrowth, sagebrush.
	From the cor. of secs. 5, 6, 7 and 8. N. 4°03' E., bet. secs. 5 and 6. Over mountainous land through scattered juniper timber and dense sagebrush undergrowth. Desc. 160 ft. over NW. slope.

CHAINS	
6.50	Draw, drains W.; asc. 320 ft. over S. slope.
18.70	Spur, slopes W.; desc. 170 ft. over NW. slope.
26.00	Small draw, drains S. 80° W.; asc. 80 ft. over S. slope.
26.92	Telephone line, bears about N. 41° W. and S. 41° E.
33.40	Spur, slopes W.; desc. 60 ft. over NW. slope.
40.00	Small draw, drains S. 80° W.; asc. 10 ft. over SE. slope.
41.03	Point for the ¼ sec. cor. of secs. 5 and 6 at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and brass cap mkd. T12N R6E ¼ S6 | S5 1964 Raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of cor. Asc. 30 ft. over SE. slope.
44.50	Spur, slopes S. 80° W., thence by triangulation; desc. about 200 ft. over N. slope.
56.00	Draw, drains W.; asc. about 170 ft. over SW. slope.
65.00	Point of spur, slopes SW.; desc. about 150 ft. over NW. slope.
76.00	Rocky draw, drains SW.; asc. about 70 ft. over SE. slope.
84.12	Intersect the N. bdy. of the Tp., (Third Standard Parallel North). Point for the closing cor. of secs. 5 and 6 at proportionate dist.; there is no remaining evidence of the original cor. End triangulation. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone to top, with brass cap mkd. T13N R6E S32 S6 | S5 C | C T12N R6E 1964 From this cor., the standard cor. of secs. 31 and 32, T. 13 N., R. 6 E., bears N. 89°20' W., 7.59 chs. dist., hereinbefore described. Land, mountainous. Soil, rocky. Timber, scattered juniper. Undergrowth, dense sagebrush.

FIELD NOTE PAPER

503

Dependent Resurvey of the Subdivision, T. 12 N., R. 6 E.

CHAINS

Point for the N. ¼ sec. cor. of sec. 5, on the N. bdy. of the Tp., and mid point bet. the closing cor. of secs. 4 and 5, and the closing cor. of secs. 5 and 6.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with glass at base, and in a collar of stone, with brass cap mkd.

T13N R6E

¼ S5

T12N R6E

1964

Raise a mound of stone, 3 ft. base, 1½ ft. high, S. of cor.

From this cor., the standard ¼ sec. cor. of sec. 32, T. 13 N., R. 6 E., bears S. 89°38' W., 4.73 chs. dist., hereinbefore described.

General Description

Township 12 North, Range 6 East is located about 2 miles south of Bear Lake, and about ¼ of a mile south of Lake Town, Utah. The south-eastern portion is rolling land covered with a dense growth of sagebrush and scattered service berry undergrowth. This area is drained in a southeasterly direction by numerous washes. The north-western portion is mountainous and steep, covered with sagebrush, service berry and oak undergrowth. Timber consists of scattered aspen and juniper in the northwest portion. This area is drained in a northerly direction. Soil in the township is mostly clay loam, and rocky along the higher ridges. There are small streams of water in Lake Town Canyon, in the northwest portion, and Otter Creek, in the southern portion, and an intermittent stream in the canyon along state highway 3, which enters the township on the north boundary of section 4, and bears southeasterly through sections 2, 3, 4, 11, 12 and 13, and leaves the township at the northeast corner of section 13. There are numerous dirt roads throughout the township. There is some dry farming in section 19, but the area is used mostly for summer grazing of cattle. The elevation varies from about 6,500 ft. above sea level in the southeast corner, to about 9,000 ft. above sea level in the northwest corner.

CHAINS

Form 4–680
(June 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Ferrel D. Reynolds	Transitman
Jerril E. Smith	Notes
Terry S. Dabel	Front Chain
James M. Hansen	Cornerman
Barth D. Hansen	Flagman

506

CERTIFICATE OF SURVEY

I, Glen B. Hatch, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 7th day of November, 1963, I have dependently resurveyed the south boundary, (Third Standard Parallel Township 13 North, Range 6 East, and the east, west and south boundaries, subdivisional lines of Township 12 North, Range 6 East

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

(Date) (Cadastral Surveyor)

January 20, 1965 Glen B Hatch
(Date) (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date APR 14 1966

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the dependent resurvey of the south boundary, (Third Standard Parallel North), Township 13 North, Range 6 East, and the east, west and south boundaries, and the subdivisional lines of Township 12 Nort Range 6 East

executed by Glen B. Hatch, Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

MAY 11 1966 R E Brown
(Date) Acting (Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

, is a true copy of the original field notes.

Blank

Page

Blank

Page

Form 4-679
(January 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
ORIGINAL

509

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY

AND

SUBDIVISIONAL LINES

OF

TOWNSHIP 29 SOUTH, RANGE 11 EAST

Of the SALT LAKE Meridian,

In the State of UTAH.

EXECUTED BY

CRAIG P. SYLVESTER, CADASTRAL SURVEYOR

Under special instructions dated AUGUST 21, 19 63, which provided for the surveys included under Group Number 466, approved August 22, 1963, and assignment instructions dated September 24, 19 63.

Survey commenced OCTOBER 28, 19 63

completed JANUARY 9 19 64

510

DEPT. OF THE INTERIOR
BUR OF LAND MGMT

1956 JUL 26 AM 11 03

STATE & LAND OFFICE
SALT LAKE CITY, UTAH

INDEX DIAGRAM

Township 29 SOUTH, Range 11 EAST,

6 49 48	5 37 47	4 29 36	3 22 29	2 15 21	1 14
7 46 46	8 35 45	9 28 35	10 20 27	11 13 20	12 13
18 44 43	17 34 43	16 26 34	15 19 26	14 12 19	13 11
19 42 41	20 33 41	21 25 32	22 18 24	23 11 17	24 10
30 40 39	29 32 38	28 24 31	27 17 23	26 9 16	25 8
31 38 6	32 30 5	33 22 4	34 15 3	35 7 2	36 2

GPO 831242

Dependent Resurvey, South Boundary and Subdivision,
Township 29 South, Range 11 East

CHAINS

The North boundary was surveyed by A. D. Ferron in 1882, and was concurrently resurveyed and the record appears in the field notes of T. 28 S., R. 11 E. The East boundary (Henry Mountain Guide Meridian) was surveyed by A. D. Ferron in 1882, and resurveyed by Elliot Bird in 1922, and the record appears in the resurvey of the Henry Mountain Guide Meridian, in T. 29 S. The West boundary was surveyed by A. D. Ferron in 1882, and concurrently resurveyed, and the record appears in the field notes of T. 29 S., R. 10 E. The South boundary of T. 29 S., R. 11 E., was surveyed by A. D. Ferron in 1882. The subdivisional lines were surveyed by A. D. Ferron in 1883.

The following field notes are those of a dependent resurvey of the South boundary and subdivisional lines of T. 29 S., R. 11 E.

The survey was executed in accordance with the specifications as set forth in the Manual of Instructions, 1947, and the Special Instructions dated August 21, 1963. Lines connecting previously established corners were run by random and true method, but for simplification of the record, the random lines are omitted from these field notes.

All lines of this survey were run by the direct method where the lines were accessible; lines inaccessible were run by traverse or triangulation methods. Distances to topography on lines run by traverse and triangulation methods are approximately as scaled from U.S.G.S. topographic sheets. The details of such traverses and triangulations have been thoroughly checked and verified, and in order to simplify the records, the diagrams and reductions are omitted from these field notes.

The direction of the lines of this survey were determined by reference to true meridians established on line by hour angle observations on Polaris. They were carried forward by sustained angulation, being supplemented by numerous other observations on Polaris taken throughout the progress of the survey.

Before restoring lost corners, the lines of the original survey were retraced and a diligent search made for any evidence of the original corners. The rules of proportionate measurement were applied to ascertain the position of the lost corner after every reasonable possibility of finding direct evidence of the corner had been exhausted.

The geographic position for the southeast corner of the township is in latitude 38°14'08.18" N. and longitude 110°39'22.98" W., as determined by traverse from United States Geological Survey triangulation station, "Cattle," situated in section 32, on Adams Butte at latitude 38° 14'24.169" N. and longitude 110°44'23.304" W.

The magnetic declination was read at a number of stations throughout the township and the average of the several readings was found to be 15°30'E.

Dependent Resurvey, South Bounda . T. 29 S., R. 11 E.

CHAINS

Reestablishment of the Survey Executed
by A. D. Ferron, Deputy Surveyor in 1882

Beginning at the corner of Tps. 29 and 30 S., Rs. 11 and 12 E., monumented by an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record.

N. 88°32' W., bet. secs. 1 and 36.

Over sandy desert land, covered with bunch grass; asc. 30 ft. over gentle NE. slope.

42.63 The ¼ sec. cor. of secs. 1 and 36, mkd. by a granite stone, 4x8x12 ins., plainly mkd. ¼.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R11E
¼ S36
S1
T30S
1963

Bury original stone N. and alongside the iron post.

N. 89° 38'W., beginning new measurement.

Asc. gentle NE. slope.

13.60 Halfway Wash, 2 ft. deep, 1 ch. wide, drains NE.; asc. 65 ft. over E. slope, across series of small clay hills.

39.92 Point for the cor. of secs. 1, 2, 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R11E
S35 | S36
S2 | S1
T30S
1963

Land, rolling to broken on W. portion.
Soil, sandy clay on W. portion.
No timber.
Undergrowth, bunch grass.

N. 89°38' W., bet. secs. 2 and 35.

Over broken desert land; asc. 85 ft. over E. slope, across series of low clay hills.

11.60 Low rim, bears irregularly N. and S., thence over broken top of small bench.

15.40 Small wash, drains S. about 5 chs., thence SE.; asc. 25 ft. over broken bench.

CHAINS	
25.30	Crest of low rim, about 6 ft. high, bears S. and NE., thence over rolling sandy bench, covered with black brush and bunch grass.
39.93	Point for the ¼ sec. cor. of secs. 2 and 35, at proportionate dist.; there is no remaining evidence of original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T29S R11E ¼ S35/S2 T30S 1963 Place 3 large boulders around the iron post. Continue over sandy bench.
43.70	Crest of low rise, bears N. and S.; desc. 30 ft. over gentle W. slope.
53.50	Bulldozed road, bears SW. and NE.
72.30	Small wash, drains N. 20° W.; asc. 20 ft. over gentle E. slope.
79.86	The cor. of secs. 2, 3, 34 and 35, marked by a granite stone, 4x5x10 ins., plainly mkd. 2 notches on E. and 4 notches on W. face. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R11E S34 | S35 S3 | S2 T30S 1963 Bury original stone N. and alongside the iron post. Land, broken to rolling. Soil, sand and exposed sandstone. No timber. Undergrowth, black brush and bunch grass on bench land.
	N. 89°36' W., bet. secs. 3 and 34. Over rolling sandy bench land; asc. 25 ft. over gentle E. slope.
5.80	Crest of low rise, bears N. and S.; desc. 50 ft. over gentle W. slope.
28.80	Wash, 2 ft. deep, 20 lks. wide, drains N.; asc. 35 ft. over gentle E. slope.
40.21	The ¼ sec. cor. of secs. 3 and 34, marked by a sandstone, 3x8x12 ins., dimly mkd. ¼. At the cor. point

Dependent Resurvey, South Boundary, T. 29 S., R. 11 E.

CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R11E
¼ S34/S3
T30S
1963

from which

A table rock, 12 ft. diam., 10 ft. high, bears S. 35° W., 6 chs. dist.

Bury original stone N. and alongside the iron post.

N. 89°59' W., beginning new measurement.

Asc. 15 ft. over sandy E. slope.

2.00 Low rise, bears N. and S., thence along N. slope.

14.50 Rise, bears N. and S.; desc. 130 ft. over broken W. slope.

38.50 Wash, in small ravine, drains NW. about 8 chs. to junction, thence N.; asc. 30 ft. over E. slope of small rise in ravine.

39.81 The corner of secs. 3, 4, 33 and 34, marked by a granite stone, 5x12x14 ins., mkd. 3 notches on E. and W. faces.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R11E
S33 | S34
S4 | S3
T30S
1963

Bury original stone N. and alongside iron post.

Cor. falls on E. crest of small rise in ravine.

Land, rolling E. portion, broken W. portion.
Soil, sandy gravel and exposed sandstone.
No timber.
Undergrowth, black brush and bunch grass.

N. 89°22' W., bet. secs. 4 and 33.

Over broken desert land, draining N.; asc. E. slope of small rise in ravine.

1.70 Small rise in ravine, slopes N. about 4 chs. to end; desc. W. slope.

3.20 Wash, 1 ft. deep, 30 lks. wide, drains N. about 5 chs. to junction; asc. 30 ft. over W. slope.

9.70 W. crest of small ravine, bears N. and S., thence over rolling bench land draining N.

20.80 Trail road, bears N. and S.

Dependent Resurvey, South Boundary, T. 29 S., R. 11 E.

CHAINS

40.42 The ¼ sec. cor. of secs. 4 and 33, marked by a granite stone, 4x8x14 ins., plainly mkd. ¼.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R11E
¼ S33
S4
T30S
1963

Bury original stone N. and alongside the iron post.

Cor. falls on crest of small terrace facing W.

S. 89° 52' W., beginning new measurement.

Desc. 25 ft. over rolling desert land, draining N.

2.40 Small wash, drains N.

21.20 Colie Wash, 3 ft. deep, 20 lks. wide, drains N. 10° E.; asc. 65 ft. over E. slope of terrace.

24.30 Crest of terrace, bears N. and S., thence over gravelly bench.

38.70 Wash with small seep of water in small swale, drains N. 20° E.

39.96 The cor. of secs. 4, 5, 32 and 33, mkd. by a granite stone, 4x12x16 ins., plainly mkd. 4 notches on E. and 2 notches on W. faces.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R11E
S32 | S33
S5 | S4
T30S
1963

Bury original stone N. and alongside iron post.

Land, rolling to broken.
Soil, sandy gravel.
No timber.
Undergrowth, black brush and scattered bunch grass.

N. 89°39' W., bet. secs. 5 and 32.

Over rolling gravelly desert land, draining N.; asc. 25 ft. over E. slope of swale.

2.64 Fence, net wire, bears N. 5° W. and S. 5° E., thence over gravelly bench land draining N.

13.40 Wash, 3 ft. deep, 20 lks. wide, drains N.

Dependent Resurvey, South Boundary, T. 29 S., R. 11 E.

CHAINS	
26.30	Cow Wash, 5 ft. deep, 40 lks. wide, drains N. 20° E.
35.80	Fence, net wire, bears N. 25° E. and S. 25° W.
36.10	Graded dirt road, bears N. 25° E. to Hanksville and S. 25° W. to Sawmill Basin.
40.23	The ¼ sec. cor. of secs. 5 and 32, marked by a sandstone, 2x12x14 ins., plainly mkd. ¼.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground, in a mound of stone, 2½ ft. base, with brass cap mkd.
	T29S R11E ¼ S32/S5 T30S 1963
	From this cor. U.S.G.S. triangulation station "Cattle," bears N. 0°19' W., 21.76 chs. distance.
	Bury original stone N. and alongside iron post.
	N. 88°59' W., beginning new measurement.
	Continue over gravelly bench land, draining N.
6.10	Slope changes; desc. 50 ft. over gentle NW. slope.
15.80	Wash, 4 ft. deep, 20 lks. wide, drains N., thence along gentle N. slope.
27.60	Wash, 3 ft. deep, 20 lks. wide, drains NE., continue along N. slope.
40.26	The cor. of secs. 5, 6, 31 and 32, marked by a granite stone, 6x12x12 ins., plainly mkd. 5 notches on E. and 1 notch on W. faces.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T29S R11E S31 | S32 S6 | S5 T30S 1963
	Bury original stone N. and alongside the iron post.
	Raise a mound of stone, 2½ ft. base, 2½ ft. high, W. of cor.
	Land, rolling to slightly broken. Soil, sandy gravel. No timber. Undergrowth, black brush and scattered bunch grass.
	N. 89°01' W., bet. secs. 6 and 31.

Dependent Resurvey of the Subdivision, T. 29 S., R. 11 E.

CHAINS	
18.80	Crest of rim of bluff, bears SE. and NW.; desc. 100 ft. over broken NE. slope.
24.90	Base of bluff, bears NW. and SE.; desc. along rolling E. slope.
30.00	Small wash, drains E.; asc. 20 ft. along rolling E. slope.
40.32	Point for the ¼ sec. cor. of secs. 35 and 36 at proportionate dist.; there is no remaining evidence of original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd. T29S R11E ¼ S35 | S36 1963 Asc. 40 ft. along broken E. slope over series of small spurs sloping E.
50.40	Spur, slopes E.; desc. 75 ft. over NE. slope of spur.
53.70	Base of spur, bears NW. and SE.; desc. 30 ft. along rolling E. slope.
68.90	Wash, 3 ft. deep, 30 lks. wide, drains E.; desc. 10 ft. along gentle E. slope.
77.90	Fence, 4-strand barbed wire, bears N. 62°14' E. and S. 62°14' W.
80.64	The cor. of secs. 25, 26, 35 and 36, marked by a mound of stone, no visible marks. Stone is foreign to this area. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R11E S26 | S25 S35 | S36 1963 Land, broken and rolling. Soil, sandy clay and exposed sandstone. No timber. Undergrowth, black brush and scattered bunch grass.

From the cor. of secs. 25 and 36, on the E. bdy. of the Tp., marked by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of 1922.

N. 89°15' W., bet. secs. 25 and 36.

Over rolling desert land covered with black brush and scattered bunch grass; asc. 30 ft. over gentle NE. slope.

31.60	Wash, 2 ft. deep, 30 lks. wide, drains NE.
41.02	The ¼ sec. cor. of secs. 25 and 36, marked by a sandstone, 5x8x12 ins., plainly mkd. ¼.

Dependent Resurvey of the Subdivision, T. 29 S., R. 11 E.

CHAINS

At the cor. point

Set an iron post, 36 ins. long, 1 in. diam., 28 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R11E
¼ S25/S36
1963

Bury original stone N. and alongside iron post.

Cor. falls about 5.50 chs. S. of fence, bearing E. & W.

N. 88°54' W., beginning new measurement.

Asc. 40 ft. over rolling E. slope.

37.15 Fence, 4-strand barbed wire, bears N. 62°14' E. and S. 62° 14' W.

43.73 The cor. of secs. 25, 26, 35 and 36.

Land, rolling.
Soil, sand.
No timber.
Undergrowth, black brush and bunch grass.

N. 2°29' E., bet. secs. 25 and 26.

Over broken desert land covered with shadscale and scattered bunch grass, along E. slope over series of small gullies draining E.

5.00 Small wash, drains E.

40.24 Point for the ¼ sec. cor. of secs. 25 and 26 at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R11E
¼
S26|S25
1963

Asc. 40 ft. along broken E. slope.

68.50 Base of ledgy bluff, bears NE. and SW.; asc. 200 ft. over ledgy SE. slope. By triangulation with topography scaled from U.S.G.S. sheets.

71.80 Crest of same bluff, bears NE. and SW., thence over narrow top of mesa. End triangulation.

74.60 Top of ascent on mesa; desc. N. slope of mesa.

78.10 Crest of ledgy rim, bears irregularly NE. and SW.; desc. 105 ft. over ledgy NW. slope.

80.48 Point for the cor. of secs. 23, 24, 25 and 26 at proportionate dist.; there is no remaining evidence of the original corner.

Dependent Resurvey of the Subdivision, T. 29 S., R. 11 E.

CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd.

T29S R11E
S23 | S24
S26 | S25
1963

Cor. falls 60 lks. N. of base of ledges, on steep NW. slope.

Land, broken.
Soil, sandy clay with exposed sandstone.
No timber.
Undergrowth, shadscale and scattered bunch grass.

From the cor. of secs. 24 and 25, on the E. bdy., mkd. by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of 1922.

N. 88°18' W., bet. secs. 24 and 25.

Over rolling desert land; asc. 45 ft. over gentle NE. slope.

1.00 Graded dirt road, Hanksville to Hite, bears N. and S.

8.30 Wash, 6 ft. deep, 30 lks. wide, drains NE.

27.50 Enter broken land; asc. 20 ft. over E. slope.

41.41 The ¼ sec. cor. of secs. 24 and 25, mkd. by a sandstone, 2x12x14 ins., mkd. ¼.

At the cor. point

Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R11E
¼ S24
S25
1963

Bury original stone N. and alongside iron post.

S. 89°44' W., beginning new measurement.

Asc. 80 ft. over broken E. slope. By triangulation, with topography scaled from U.S.G.S. sheets.

36.50 Base of ledgy bluff, bears NE. and SW.; asc. 200 ft. over ledgy SE. slope.

38.40 Crest same bluff, bears NE. and SW., thence across top of narrow mesa.

39.00 Crest of ledgy rim, bears irregularly NE. and SW.; desc. 100 ft. over ledgy NW. slope.

39.91 The cor. of secs. 23, 24, 25 and 26. End of triangulation.

Land, rolling to broken.
Soil, sandy clay and exposed sandstone.

Dependent Resurvey of the Subdivision, T. 29 S., R. 11 E.

CHAINS

No timber.
Undergrowth, shadscale and scattered bunch grass.

N. 0°24' E., bet. secs. 23 and 24.

Over broken desert land; desc. 160 ft. over broken and irregular NW. slope of bluff.

10.80 Base of broken NW. slope of bluff, bears irregularly NE. and SW.; desc. 20 ft. along base of bluff.

25.40 Top of small hill; desc. 60 ft. over N. slope of hill.

27.00 Base of same hill, about 5 chs. diam.; desc. over gentle N. slope.

40.20 Point for the ¼ sec. cor. of secs. 23 and 24 at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 1 in. diam., 29 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R11E
¼
S23 | S24
1963

Desc. 65 ft. over sandy N. slope.

80.40 Point for the cor. of secs. 13, 14, 23 and 24 at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T29S R11E
S14 | S13
S23 | S24
1963

Raise a mound of stone, 2½ ft. base, 2½ ft. high, W. of corner.

Land, broken and rolling.
Soil, sand and exposed sandstone.
No timber.
Undergrowth, shadscale and bunch grass.

From the cor. of secs. 13 and 24, on the E. bdy., marked by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record.

N. 89°29' W., bet. secs. 13 and 24.

Over rolling sandy desert land; asc. 20 ft. along gentle N. slope.

5.20 Graded dirt road, Hanksville to Hite, bears N. 10° W. and S. 10° E.

14.30 Wash, 2 ft. deep, 10 lks. wide, drains N.

32.90 Base of steep ascent, bears S. and NW.; asc. 150 ft. over broken E. slope.

Dependent Re[illegible] of the Subdivision T. 29 S. R. 11 E.

CHAINS

40.34 The ¼ sec. cor. of secs. 13 and 24, marked by a sandstone, 4x10x14 ins., plainly mkd. ¼.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd.

T29S R11E
¼ S13/S24
1963

Bury original stone N. and alongside iron post.

Cor. falls on top of bluff.

N. 89°16' W., beginning new measurement.

Desc. 120 ft. over broken W. slope of bluff.

14.60 Base of bluff, bears irregularly S. and NE, thence along broken N. slope.

35.00 Wash, 2 ft. deep, 20 lks. wide, drains N.

40.46 The cor. of secs. 13, 14, 23 and 24.

Land, rolling and broken.
Soil, sand and exposed sandstone.
No timber.
Undergrowth, black brush and bunch grass.

N. 0°05' W., bet. secs. 13 and 14.

Over rolling sandy desert land covered with shadscale and bunch grass; desc. 55 ft. over gentle N. slope.

40.20 Point for the ¼ sec. cor. of secs. 13 and 14 at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 1 in. diam., 28 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R11E
¼
S14|S13
1963

Desc. 50 ft. over gentle N. slope.

80.40 The cor. of secs. 11, 12, 13 and 14, determined by a mound of conglomerate stone, no visible marks. Stone is foreign to this area.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R11E
S11|S12
S14|S13
1963

Dependent Resurvey of the Subdivision, T. 29 S., R. 11 E.

CHAINS	
	Land, rolling. Soil, sand. No timber. Undergrowth, shadscale and bunch grass.
	From the cor. of secs. 12 and 13, on the E. bdy., marked by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of 1922. Cor. is located on NE. cor. of small BLM test plot.
	N. 88°35' W., bet. secs. 12 and 13.
	Over rolling sandy desert land draining N.
20.30	Graded dirt road, Hanksville to Hite, bears N. 25° W. and S. 25° E.
29.60	Wash, 4 ft. deep, 20 lks. wide, drains N. 25° E., thence over series of small washes draining N.
40.58	The ¼ sec. cor. of secs. 12 and 13, marked by a granite stone, 8x12x14 ins., plainly mkd. ¼.
	At the cor. point
	Set an iron post, 36 ins. long, 1 in. diam., 28 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R11E ¼ S12/S13 1963
	Bury original stone N. and alongside iron post.
	S. 89°11' W., beginning new measurement.
	Continue over rolling desert land draining N.
9.30	Wash, 3 ft. deep, 20 lks. wide, drains N. 20° E.
17.40	Wash, 4 ft. deep, 20 lks. wide, drains N. 20° E.
37.10	Wash, 3 ft. deep, 10 lks. wide, drains N. 30° W. 5 chs., thence N. 30° E.
40.43	The cor. of secs. 11, 12, 13 and 14.
	Land, rolling. Soil, sandy. No timber. Undergrowth, shadscale and bunch grass.
	N. 0°24' W., bet. secs. 11 and 12.
	Over rolling sandy desert land; desc. 35 ft. over gentle N. slope.
40.30	Point for the ¼ sec. cor. of secs. 11 and 12 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground, in a collar of stone, with brass cap mkd.

CHAINS	
	T29S R11E ½ S11 | S12 1963
	Cor. falls on S. side of small wash.
	Desc. 40 ft. over rolling desert land draining N.
80.60	Point for the cor. of secs. 1, 2, 11 and 12 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T29S R11E S2 | S1 S11 | S12 1963
	Land, rolling. Soil, sandy. No timber. Undergrowth, shadscale and bunch grass.
	From the cor. of secs. 1 and 12, on the E. bdy., marked by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of 1922.
	S. 89°26' W., bet. secs. 1 and 12.
	Over broken sandy land covered with black brush and bunch grass; asc. 35 ft. over irregular NE. slope.
.20	Wash, 2 ft. deep, 10 lks. wide, drains irregularly N.
10.80	Wash, 3 ft. deep, 20 lks. wide, drains N. 40° E.
40.45	The ¼ sec. cor. of secs. 1 and 12, marked by a granite stone, 4x4x8 ins., in a mound of stone, plainly mkd. ¼.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T29S R11E ¼ S1 S12 1963
	Bury original stone N. and alongside iron post.
	N. 88°47' W., beginning new measurement.
	Asc. 70 ft. over E. slope.
12.50	Crest of low terrace, bears N. and S.; desc. 95 ft. over W. slope.
19.60	Graded road, Hanksville to Hite, bears N. and S., thence over rolling land.
37.00	Trail road, bears NW. and SE.

[illegible] Subdivision, T. 29 S., R. 1[illegible]

CHAINS	
41.20	The cor. of secs. 1, 2, 11 and 12.
	Land, broken and rolling. Soil, sandy and exposed sandstone. No timber. Undergrowth, black brush and scattered bunch grass.
	N. 1°05' E., bet. secs. 1 and 2.
	Over rolling desert land draining N.
3.00	Trail road, bears NW. and SE.
40.31	Point for the ¼ sec. cor. of secs. 1 and 2 at proportionate dist.; there is no remaining evidence of the original corner.
	Set an iron post, 36 ins. long, 1 in. diam., 28 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R11E ¼ S2 S1 1963
	Desc. 20 ft. over rolling desert land.
76.60	Base of series of low hills, bears irregularly NE. and SW.; asc. 30 ft. over SE. slope.
77.30	Top of round hill; desc. 25 ft. along W. slope of hill.
80.22	The cor. of secs. 1, 2, 35 and 36, on the N. bdy., mkd. by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the concurrent resurvey of the S. bdy. of T. 28 S., R. 11 E.
	Land, rolling and broken. Soil, sand and gravelly on hills. No timber. Undergrowth, shadscale and scattered bunch grass.
	From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp.
	N. 1°34' W., bet. secs. 34 and 35.
	Over sandy desert land, desc. 50 ft. over NW. slope.
17.30	Petrified tree stump and trunk of tree, 18 ins. diam., 8 ft. long.
20.90	Wash, 4 ft. deep, 30 lks. wide, drains NW.; desc. 20 ft. along rolling W. slope.
40.10	Point for the ¼ sec. cor. of secs. 34 and 35 at proportionate dist.; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd.

CHAINS	
	T29S R11E ¼ S34 | S35 1963
	Desc. 20 ft. along rolling W. slope.
52.50	Small wash, drains W.
80.20	Point for the cor. of secs. 26, 27, 34 and 35 at proportionate dist.; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., on solid sandstone, over an (x), and in a mound of stone, 4 ft. base to top, with brass cap mkd. T29S R11E S27 | S26 S34 | S35 1963 Land, rolling to slightly broken. Soil, sand and exposed sandstone. No timber. Undergrowth, shadscale and bunch grass.
	From the cor. of secs. 25, 26, 35 and 36. N. 89°56' W., bet. secs. 26 and 35. Over broken desert land covered with shadscale and bunch grass; asc. 125 ft. over broken E. slope.
39.89	Point for the ¼ sec. cor. of secs. 26 and 35 at proportionate dist.; there is no remaining evidence of the original corner. Set an iron post, 36 ins. long, 1 in. diam., 14 ins. in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd. T29S R11E ¼ S26 S35 1963 Asc. 10 ft. over broken E. slope.
41.20	E. crest of small mesa, bears irregularly NE. and SW., thence over mesa.
46.00	W. crest same mesa, bears NE. and SW.; desc. 110 ft. over irregular NW. slope.
79.78	The cor. of secs. 26, 27, 34 and 35. [illegible]l, broken. [illegible]oil, sandy clay and exposed sandstone. [illegible]o timber. [illegible]ndergrowth, shadscale and scattered bunch grass.

Dependent Resurvey of the Subdivision, T. 29 S., R. 11 E.

CHAINS

N. 1°21' E., bet. secs. 26 and 27.

Over broken land; desc. 80 ft. over NW. slope.

15.50 Wash, 5 ft. deep, 20 lks. wide, drains W.; asc. 40 ft. over S. slope.

23.90 Low spur, slopes W.; desc. 55 ft. over broken NW. slope.

40.10 Point for the ¼ sec. cor. of secs. 26 and 27 at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 36 ins. long, 1 in. diam., 26 ins. in the ground, with brass cap mkd.

T29S R11E
¼
S27 | S26
1963

Set one large boulder N. of corner.

Desc. 20 ft. over broken NW. slope.

56.60 Small wash, drains NW.; desc. 30 ft. over gentle NW. slope.

80.20 The cor. of secs. 22, 23, 26 and 27, marked by a granite stone, 3x8x8 ins., mkd. 2 notches on S. and 2 notches on E. faces.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R11E
S22 | S23
S27 | S26
1963

Bury original stone N. and alongside iron post.

Land, broken.
Soil, sand and exposed sandstone.
No timber.
Undergrowth, shadscale and scattered bunch grass.

From the cor. of secs. 23, 24, 25 and 26.

N. 88°05' W., bet. secs. 23 and 26.

Over broken desert land; desc. 150 ft. over NW. slope of bluff.

10.30 Base of steep descent, bears NE. and SW.; desc. 30 ft. over gentle NW. slope.

39.97 The ¼ sec. cor. of secs. 23 and 26, marked by a sandstone, 4x8x12 ins., plainly mkd. ¼.

At the cor. point

Set an iron post, 36 ins. long, 1 in. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.

Dependent Resurvey of the Subdivision, T. 29 S., R. 11 E.

CHAINS

T29S R11E
¼ S23
S26

1964

Bury original stone N. and alongside iron post.

S. 87°52' W., beginning new measurement.

Desc. 40 ft. over sandy NW. slope.

41.45 The cor. of secs. 22, 23, 26 and 27.

Land, broken.
Soil, sand and exposed sandstone.
No timber.
Undergrowth, shadscale and scattered bunch grass.

N. 1°18' E., bet. secs. 22 and 23.

Over broken desert land; desc. 20 ft. over gentle NW. slope.

6.40 Collie Wash, 5 ft. deep, 50 lks. wide, drains NE.; desc. 10 ft. over gentle NE. slope.

40.43 The ¼ sec. cor. of secs. 22 and 23, determined by a gray sandstone, in a mound of stone, no visible marks, but rock is foreign to this area.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R11E
¼
S22 | S23
1964

Bury original stone N. and alongside iron post.

N. 0°05' E., beginning new measurement.

Desc. 45 ft. over sandy N. slope.

40.77 The cor. of secs. 14, 15, 22 and 23, determined by a mound of stone, no visible marks, but foreign to this area and fits the calls of the original field note record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R11E
S15 | S14
S22 | S23
1964

Land, slightly broken to rolling.
Soil, sand and exposed sandstone.
No timber.
Undergrowth, shadscale and bunch grass.

Dependent Resurvey of the Subdivision T. 29 S., R. 11 E.

CHAINS	
	From the cor. of secs. 13, 14, 23 and 24.
	N. 89°00' W., bet. secs. 14 and 23.
	Over broken desert land; desc. 40 ft. along gentle N. slope.
37.10	Wash, 3 ft. deep, 30 lks. wide, drains N.
40.67	The ¼ sec. cor. of secs. 14 and 23, marked by a sandstone, 5x10x18 ins., plainly mkd. ¼.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T29S R11E ¼ S14/S23 1963
	Bury original stone N. and alongside iron post.
	S. 89°51' W., beginning new measurement.
	Continue along gentle N. slope.
15.20	Collie Wash, 2 ft. deep, 20 lks. wide, drains N.
40.25	The cor. of secs. 14, 15, 22 and 23.
	Land, broken. Soil, sandy. No timber. Undergrowth, black brush and bunch grass.
	N. 0°35' W., bet. secs. 14 and 15.
	Over rolling sandy desert land; desc. 50 ft. over gentle N. slope.
40.16	Point for the ¼ sec. cor. of secs. 14 and 15 at proportionate dist.; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T29S R11E ¼ S15 | S14 1963
	Desc. 25 ft. over sandy N. slope.
79.57	Point selected for the witness cor. of secs. 10, 11, 14 and 15.
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T29S R11E W C S10 | S11 S15 | S14 1963

De endent Resurvey of the Subdivision, T. 29 S., R. 11 E.

CHAINS

80.32 True point for the cor. of secs. 10, 11, 14 and 15 at proportionate dist. falls in wash area and cannot be perpetuated; there is no remaining evidence of the original corner.

Land, rolling.
Soil, sand.
No timber.
Undergrowth, shadscale and bunch grass.

From the cor. of secs. 11, 12, 13 and 14.

N. 89°07' W., bet. secs. 11 and 14.

Over rolling sandy clay desert land; asc. 20 ft. along gentle N. slope.

2.10 Small wash, drains N. 20° E.

40.83 The ¼ sec. cor. of secs. 11 and 14, marked by a granite stone, 8x10x14 ins., plainly mkd. ¼.

At the cor. point

Set an iron post, 36 ins. long, 1 in diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R11E
¼ S11/S14
1963

Bury original stone N. and alongside iron post.

Cor. falls on E. side of small hollow.

S. 89°52' W., beginning new measurement.

Desc. 25 ft. over W. slope, into small hollow.

2.30 Collie Wash in hollow, drains N. 20° E.; asc. 25 ft. ove E. slope of hollow.

11.30 W. side of same hollow, bears irregularly NE. and SW.; desc. 20 ft. along gentle N. slope.

40.74 True point for the cor. of secs. 10, 11, 14 and 15 from which its witness cor. bears S. 0°35' E., 0.75 chs. dist.

Land, rolling.
Soil, sandy clay with gravel spots.
No timber.
Undergrowth, shadscale and bunch grass.

N. 0°06' W., bet. secs. 10 and 11.

Over broken desert land, across wash area.

3.00 Cow Wash, 3 ft. deep, 30 lks. wide, drains NE., leave wash area.

23.60 Small wash, drains E.; desc. gentle NE. slope.

40.16 The ¼ sec. cor. of secs. 10 and 11, mkd. by a sandstone, 5x8x12 ins., plainly mkd. ¼.

CHAINS	
	At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R11E ¼ S10 | S11 1963 Bury original stone N. and alongside iron post.
	N. 0°24' E., beginning new measurement. Desc. gentle N. slope.
14.30	Wash, in small hollow, drains NE.; desc. 20 ft. over gentle N. slope.
40.55	The cor. of secs. 2, 3, 10 and 11, marked by a sandstone, 12x12x14 ins., plainly mkd. 5 notches on S. and 2 notches on E. faces. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R11E S3 | S2 S10 | S11 1963 Bury original stone N. and alongside iron post. Land, broken. Soil, sand and exposed sandstone. No timber. Undergrowth, shadscale and bunch grass.
	From the cor. of secs. 1, 2, 11 and 12. N. 89°18' W., bet. secs. 2 and 11. Over rolling desert land; asc. 35 ft. over E. slope.
6.30	E. crest of low rise, bears irregularly N. and S.
12.20	W. crest of same rise, bears S. and N. about 15 chs. to end; desc. 25 ft. over W. slope.
20.30	Collie Wash, 1 ft. deep, 10 lks. wide, drains N. 20° E.; asc. 40 ft. over gentle W. slope.
41.09	The ¼ sec. cor. of secs. 2 and 11, marked by a granite stone, 10x10x12 ins., plainly mkd. ¼. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R11E ¼ S2 / S11 1963 Bury original stone N. and alongside iron post.

Dependent Resurvey of the Subdivision, T. 29 S., R. 11 E.

CHAINS	
	N. 89°47' W., beginning new measurement.
	Desc. 40 ft. over broken desert land draining N.
4.00	Small wash, drains N.
8.00	Top small rise, bears S. and N. about 8 chs. to end.
18.80	Wash, 2 ft. deep, 20 lks. wide, drains N. 20° E.
24.50	Low rise, bears N. and S.
33.50	Enter flat in Dry Valley, leave broken land.
39.71	The cor. of secs. 2, 3, 10 and 11.
	Land, broken. Soil, sand with gravel spots. No timber. Undergrowth, black brush and bunch grass.
	N. 1°19' E., bet. secs. 2 and 3.
	Over rolling desert land draining NE.
1.90	Dry Valley Wash, 10 ft. deep, 40 lks. wide, drains NE.
39.79	Point for the ¼ sec. cor. of secs. 2 and 3 at proportionate dist.; there is no remaining evidence of the original corner.
	Set an iron post, 36 ins. long, 1 in diam., 24 ins. in the ground, with brass cap mkd. T29S R11E ¼ S3 S2 1963
	Raise a mound of stone, 3 ft. base, 1½ ft. high, W. of corner.
	Desc. 10 ft. over rolling desert land draining NE.
79.86	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., marked by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the concurrent resurvey of the S. bdy. of T. 28 S., R. 11 E.
	Land, rolling. Soil, sandy with gravel spots. No timber. Undergrowth, black brush and bunch grass.
	From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp.
	N. 0°14' E., bet. secs. 33 and 34.
	Over rolling desert land; desc. 30 ft. over NW. slope.
3.40	Wash, 3 ft. deep, 40 lks. wide, drains NW.
14.80	Trail road, bears NW. and SE.
26.00	Wash, 3 ft. deep, 20 lks. wide, drains NE., thence along gentle E. slope.

Dependent Resurvey of the Subdivision, T. 29 S., R. 11 E.

CHAINS	
40.08	The ¼ sec. cor. of secs. 33 and 34, marked by a sandstone 4x6x12 ins., plainly mkd. ¼.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R11E ¼ S33 | S34 1963
	Bury original stone N. and alongside iron post.
	N. 2°41' W., beginning new measurement.
	Asc. 30 ft. along gentle E. slope.
21.00	Small wash, drains E.
40.28	The cor. of secs. 27, 28, 33 and 34, marked by a sandstone, 3x6x14 ins., plainly mkd. 1 notch on S. and 3 notches on E. faces.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R11E S28 | S27 S33 | S34 1963
	Bury original stone N. and alongside iron post.
	Land, rolling. Soil, sand with gravel spots. No timber. Undergrowth, shadscale and bunch grass.
	From the cor. of secs. 26, 27, 34 and 35.
	N. 89°41' W., bet. secs. 27 and 34.
	Over broken desert land; asc. 10 ft. over gentle E. slope.
11.50	Top low rise, bears N. and S.; desc. 70 ft. over NW. slope.
26.50	Small wash, drains NW.
39.79	Point for the ¼ sec. cor. of secs. 27 and 34 at proportionate dist.; there is no remaining evidence of the original corner.
	Set an iron post, 36 ins. long, 1 in. diam., on solid sandstone, over an (X), and in a mound of stone, 4 ft. base, 30 ins. high, with brass cap mkd. T29S R11E ¼ S27/S34 1963

Dependent Resurvey of the Subdivision, T. 29 S., R. 11 E.

CHAINS	
	Continue over broken NW. slope.
49.80	Collie Wash, 2 ft. deep, 30 lks. wide, drains NE.; asc. 75 ft. over NE. slope.
57.00	Old rock quarry.
79.58	The cor. of secs. 27, 28, 33 and 34.
	Land, broken. Soil, sand and exposed sandstone. No timber. Undergrowth, shadscale and bunch grass.
	N. 0°06' E., bet. secs. 27 and 28.
	Over rolling sandy desert land; desc. 80 ft. over gentle NW. slope.
40.19	Point for the ¼ sec. cor. of secs. 27 and 28 at proportionate dist.; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R11E ¼ S28 | S27 1963
	Desc. 20 ft. over sandy NW. slope.
50.50	Trail road, bears NW. and SE.
62.60	Enter rocky and eroded area; desc. 85 ft. over broken NW. slope.
80.38	The cor. of secs. 21, 22, 27 and 28, marked by a sandstone, 4x10x14 ins., mkd. 2 notches on S. and 3 notches on E. face.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R11E S21 | S22 S28 | S27 1963
	Bury original stone N. and alongside iron post.
	Land, rolling and broken. Soil, sand and exposed sandstone. No timber. Undergrowth, black brush and bunch grass.
	From the cor. of secs. 22, 23, 26 and 27.
	N. 89°15' W., bet. secs. 22 and 27.
	Over broken desert land; desc. 10 ft. over W. slope.

[illegible] T. 29 S. R. [illegible] E.

CHAINS	
4.00	Collie Wash, 5 ft. deep, 30 lks. wide, drains irregularly N.; asc. 165 ft. over broken E. slope of ridge.
24.80	Crest of ridge, bears N. and S.; desc. gentle W. slope on ridge.
40.83	The ¼ sec. cor. of secs. 22 and 27, marked by a sandstone, 4x8x15 ins., plainly mkd. ¼.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T29S R11E ¼ S22/S27 1963
	Bury original stone N. and alongside iron post.
	N. 89°44' W., beginning new measurement.
	Desc. 45 ft. over gentle W. slope on ridge.
21.10	Enter rocky and broken land; desc. 90 ft. over broken NW. slope.
40.52	The cor. of secs. 21, 22, 27 and 28.
	Land, broken. Soil, sand and exposed sandstone. No timber. Undergrowth, black brush and bunch grass.
	N. 0°27' W., bet. secs. 21 and 22.
	Over broken desert land; desc. 35 ft. along rocky W. slope.
25.10	Cow Wash, 3 ft. deep, 60 lks. wide, drains NW. from SW.; desc. along E. side of wash.
40.00	Same wash, drains NE.; asc. gentle E. slope.
40.41	Point for the ¼ sec. cor. of secs. 21 and 22 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T29S R11E ¼ S21 | S22 1963
	Asc. 30 ft. over gentle SE. slope.
72.20	Base of series of low sandstone ledges, bears NE. and SW.; asc. 55 ft. over broken SE. slope.
80.82	The cor. of secs. 15, 16, 21 and 22, marked by a sandstone, 6x10x16 ins., mkd. 3 notches on S. and E. faces.
	At the cor. point

Dependent Resurvey of the Subdivision T. 29 S., R. 11 E.

CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., on solid sandstone, over an (X), and in a mound of stone, 4 ft. base, 26 ins. high, with brass cap mkd.

T29S R11E
S16 | S15
S21 | S22
1963

Bury original cor. in mound of stone and alongside iron post.

Land, broken.
Soil, sand and exposed sandstone.
No timber.
Undergrowth, black brush and bunch grass.

From the cor. of secs. 14, 15, 22 and 23.

S. 89°43' W., bet. secs. 15 and 22.

Over broken desert land, along gentle N. slope.

26.70 Wash, 3 ft. deep, 10 lks. wide, drains N.

42.13 The ¼ sec. cor. of secs. 15 and 22, marked by a sandstone, 5x5x12 ins., plainly mkd. ¼.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R11E
¼ S15
S22
1963

Bury original stone N. and alongside iron post.

N. 89°15' W., beginning new measurement.

Desc. 10 ft. along N. slope.

12.70 Cow Wash, 3 ft. deep, 30 lks. wide, drains N.; asc. 115 ft. over broken E. slope.

40.76 The cor. of secs. 15, 16, 21 and 22.

Land, broken.
Soil, sand and exposed sandstone.
No timber.
Undergrowth, black brush and bunch grass.

N. 0°13' E., bet. secs. 15 and 16.

Over broken desert land; asc. 20 ft. over SE. slope.

2.60 Leave broken land; asc. 30 ft. over gentle S. slope of high bench, across sand and exposed sandstone.

40.42 The ¼ sec. cor. of secs. 15 and 16, marked by a granite stone, 8x18x18 ins., plainly mkd. ¼.

ent Res... of the Subdivision ... 29 ... R. 11 E.

CHAINS

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.

T29S R11E
¼
S16 | S15
1963

Bury original stone N. and alongside iron post.

N. 1°03' E., beginning new measurement.

Continue over sandy bench.

10.20 Crest of bluff, bears irregularly E. and NW.; desc. 185 ft. over ledgy NE. slope.

24.20 Base same bluff, bears E. and W.; desc. 15 ft. over gentle N. slope.

37.50 Dry Valley Wash, 4 ft. deep, 50 lks. wide, drains NE.

40.22 Point for the cor. of secs. 9, 10, 15 and 16 at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T29S R11E
S9 | S10
S16 | S15
1963

Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of corner.

Land, rolling and broken.
Soil, sand and exposed sandstone.
No timber.
Undergrowth, black brush and bunch grass.

From the true point for the cor. of secs. 10, 11, 14 and 15, from which its witness cor. bears S. 0°35' E., 0.75 chs. distance.

N. 89°35' W., bet. secs. 10 and 15.

Over rolling sandy clay land draining NE.

6.10 Cow Wash, 2 ft. deep, 30 lks. wide, drains NE.; asc. 55 ft. over gentle NE. slope.

40.55 Point for the ¼ sec. cor. of secs. 10 and 15 at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.

Dependent Resurvey of the Subdivision, T. 29 S., R. 11 E.

CHAINS

T29S R11E
¼ S10
S15
1963

Continue over sandy desert land.

77.00 Dry Valley Wash, 10 ft. deep, 20 lks. wide, drains NE.

81.10 The cor. of secs. 9, 10, 15 and 16.

Land, rolling.
Soil, sandy clay.
No timber.
Undergrowth, shadscale and scattered bunch grass.

N. 0°16' W., bet. secs. 9 and 10.

Over rolling desert land; asc. 20 ft. along gentle E. slope.

28.10 Graded dirt road, Hanksville to Sawmill Basin, bears N. 20° E. and S. 20° W.

40.21 Point for the ¼ sec. cor. of secs. 9 and 10 at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.

T29S R11E
¼
S9 | S10
1963

Cor. falls at base of low sandstone ledges.

Continue along gentle W. slope.

47.10 Base of sandstone ledges, bears irregularly E. and SW.; asc. 130 ft. over ledgy S. slope.

59.00 Crest of same ledges, bear irregularly E. and W.; asc. 50 ft. over S. slope on E. side of small mesa.

76.20 N. crest of small mesa, bears E. and W.; desc. 150 ft. over ledgy N. slope.

79.00 Base same ledges, bears E. and W.; desc. gentle E. slope.

80.42 The cor. of secs. 3, 4, 9 and 10, marked by a sandstone, 4x10x14 ins., plainly mkd. 5 notches on S. and 3 notches on E. faces.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R11E
S4 | S3
S9 | S10
1963

[illegible]y original stone [illegible] and alongside iron post.

Dependent Resurvey of the Subdivision, T. 29 S., R. 11 E.

CHAINS

Cor. falls 60 lks. S. of small wash which drains E.

Land, rolling and broken.
Soil, sand and exposed sandstone.
No timber.
Undergrowth, black brush and bunch grass.

From the cor. of secs. 2, 3, 10 and 11.

N. 89°40' W., bet. secs. 3 and 10.

Over gravelly desert land; asc. 35 ft. over gentle NE. slope.

.90 Dry Valley Wash, 10 ft. deep, 20 lks. wide, drains NE.

14.60 Crest of low terrace, bears NE. and SW.; asc. 35 ft. over broken sandy bench draining E.

39.53 The ¼ sec. cor. of secs. 3 and 10, determined by a circular mound of stone, no visible marks, but fits the calls of original field note record.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R11E
¼ S3/S10
1963

N. 89°55' W., beginning new measurement.

Asc. 70 ft. over broken sandy E. slope.

5.10 Small wash, drains S. 80° E.

25.90 Graded dirt road, Hanksville to Sawmill Basin, bears N. 15° W. and S. 15° E.

42.14 The cor. of secs. 3, 4, 9 and 10.

Land, broken.
Soil, sand and exposed sandstone.
No timber.
Undergrowth, shadscale and bunch grass.

N. 1°45' E., bet. secs. 3 and 4.

Over broken desert land draining E.
1.00 Wash drains easterly.
39.99 Point for the ¼ sec. cor. of secs. 3 and 4 at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T29S R11E
¼
S4|S3
1963

Dependent Resurvey of the Subdivision, T. 29 S., R. 11 E.

CHAINS	
	Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of corner.
	Continue along broken E. slope.
52.00	Base of steep ascent, bears NE. and SW.; asc. 140 ft. over ledgy SE. slope of bluff.
60.00	Crest of same bluff, bears NE. and SW.; desc. 65 ft. over broken N. slope on high bench.
79.98	The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., marked by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of the S. bdy. of T. 28 S., R. 11 E.
	Land, broken. Soil, sand and exposed sandstone. No timber. Undergrowth, shadscale and scattered bunch grass.
	From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp.
	N. 0°19' E., bet. secs. 32 and 33.
	Over rolling desert land; desc. 45 ft. over gentle N. slope.
40.16	The ¼ sec. cor. of secs. 32 and 33, marked by a sandstone, 5x12x20 ins., plainly mkd. ¼.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R11E ¼ S32 | S33 1963
	Bury original stone N. and alongside iron post.
	N. 0°01' E., beginning new measurement.
	Desc. 10 ft. over gentle N. slope.
13.60	Cow Wash, in small hollow, drains NE.; desc. 20 ft. over NE. slope.
23.10	Graded dirt road, Hanksville to Sawmill Basin, bears NE. and SW.; desc. 40 ft. over broken N. slope.
38.60	Wash, 2 ft. deep, 30 lks. wide, small seep of water, drains E. 3 chs., thence N.; desc. broken N. slope.
39.90	The cor. of secs. 28, 29, 32 and 33, marked by a conglomerate stone, 10x10x20 ins., plainly mkd. 1 notch on S. and 4 notches on E. faces.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

Dependent Resurvey of the Subdivision, T. 29 S., R. 11 E.

CHAINS

T29S R11E

S29	S28
S32	S33

1963

Bury original stone N. and alongside iron post.

Land, rolling to broken.
Soil, sand and exposed sandstone.
No timber.
Undergrowth, black brush and bunch grass.

From the cor. of secs. 27, 28, 33 and 34.

N. 89°53' W., bet. secs. 28 and 33.

Over broken desert land, along gentle N. slope.

20.80 Crest of low rise, bears N. and S.; desc. 120 ft. over gentle W. slope.

38.22 The ¼ sec. cor. of secs. 28 and 32, marked by a sandstone, 6x8x30 ins., plainly mkd. ¼.

At the cor. point

Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R11E

	S28
¼	S33

1963

Bury original cor. N. and alongside iron post.

Cor. falls on E. side of wash.

N. 89°54' W., beginning new measurement.

Over broken land draining N.

3.00 Colie Wash, 3 ft. deep, 40 lks. wide, small seep of water, drains N.; asc. 45 ft. over gentle E. slope.

13.20 Crest low rise, bears N. and S.; desc. gentle N. slope.

16.30 Cow Wash, small stream of water, drains NE.; asc. gentle N. slope.

35.20 Graded dirt road, Hanksville to Sawmill Basin, bears N. and S.

37.00 Wash, 2 ft. deep, 30 lks. wide, drains N.

40.25 The cor. of secs. 28, 29, 32 and 33.

Land, slightly broken.
Soil, sand and exposed sandstone.
No timber.
Undergrowth, black brush and bunch grass.

Dependent Resurvey of the Subdivision, T. 29 S., R. 11 E.

CHAINS	
	N. 0°06' W., bet. secs. 28 and 29.
	Over rolling desert land; desc. 35 ft. over gentle NE. slope.
39.79	The ¼ sec. cor. of secs. 28 and 29, marked by a sandst 3x12x18 ins., plainly mkd. ¼.
	At the cor. point
	Set an iron post, 36 ins. long, 1 in. diam., 28 ins. in the ground, in a collar of stone, with brass cap mkd.
	T29S R11E ¼ S29 | S28 1963
	Bury original stone N. and alongside iron post.
	N. 3°32' W., beginning new measurement.
	Desc. 20 ft. over gentle N. slope.
21.20	Slope changes; asc. 30 ft. over gentle S. slope.
31.30	Crest low rise, bears E. and W.; desc. 30 ft. over gentle N. slope.
40.77	The cor. of secs. 20, 21, 28 and 29, marked by a sandstone, 3x10x18 ins., plainly mkd. 2 notches on S. and 4 notches on E. faces.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T29S R11E S20 | S21 S29 | S28 1963
	Bury original stone N. and alongside iron post.
	Raise a mound of stone, 2½ ft. base, 2½ ft. high, W. of corner.
	Land, rolling. Soil, sand and exposed sandstone. No timber. Undergrowth, black brush and scattered bunch grass.
	From the cor. of secs. 21, 22, 27 and 28.
	N. 89°55' W., bet. secs. 21 and 28.
	Over broken desert land, along N. slope.
16.50	Trail road, bears N. and S.
21.10	Cow Wash, 2 ft. deep, 30 lks. wide, drains NE.; asc. 40 ft. along gentle N. slope.
40.55	The ¼ sec. cor. of secs. 21 and 28, marked by a sandstone, 5x8x10 ins., plainly mkd. ¼.

Dependent Resurvey of the Subdivision, T. 29 S., R. 11 E.

CHAINS

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd.

T29S R11E
¼ S21
S28
1963

Bury original stone N. and alongside iron post.

N. 89°42' W., beginning new measurement.

Asc. 45 ft. over gentle NE. slope.

6.40 Graded dirt road, Hanksville to Sawmill Basin, bears N. and S.

19.70 Low rise, bears NE. and SW.; desc. 45 ft. over gentle NW. slope.

40.63 The cor. of secs. 20, 21, 28 and 29.

Land, broken.
Soil, sand and exposed sandstone.
No timber.
Undergrowth, shadscale and scattered bunch grass.

N. 0°22' W., bet. secs. 20 and 21.

Over rolling desert land; desc. 55 ft. over gentle NW. slope.

38.10 Dry Valley Wash, 4 ft. deep, 50 lks. wide, drains NE.

40.63 Point for the ¼ sec. cor. of secs. 20 and 21 at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R11E
¼
S20 | S21
1963

Desc. 25 ft. over gentle N. slope.

81.26 The cor. of secs. 16, 17, 20 and 21, marked by a limestone, 2x16x18 ins., plainly mkd. 3 notches on S. and 4 notches on E. faces.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R11E
S17 | S16
S20 | S21
1963

Bury original stone N. and alongside iron post.

CHAINS	
	Land, rolling. Soil, sand and exposed sandstone. No timber. Undergrowth, greasewood and bunch grass.
	From the cor. of secs. 15, 16, 21 and 22. S. 89°34' W., bet. secs. 16 and 21. Over rolling desert land; desc. 70 ft. over gentle W. slope.
33.80	Graded dirt road, Hanksville to Sawmill Basin, bears N. 30° W. and S. 30° E.
40.43	The ¼ sec. cor. of secs. 16 and 21, marked by a sandstone, 6x10x14 ins., plainly mkd. ¼. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R11E ¼ S16/S21 1963 Bury original stone N. and alongside iron post.
	N. 88°35' W., beginning new measurement. Desc. 15 ft. over gentle NW. slope.
8.10	Dry Valley Wash, 5 ft. deep, 50 lks. wide, drains N. 10° E., thence over rolling land draining N.
40.65	The cor. of secs. 16, 17, 20 and 21. Land, rolling. Soil, sand. No timber. Undergrowth, black brush and bunch grass.
	N. 0°30' E., bet. secs. 16 and 17. Over rolling desert land; desc. 10 ft. over gentle N. slope.
19.40	Graded dirt road, bears NE. and SW.; asc. 15 ft. along gentle E. slope.
40.03	Point for the ¼ sec. cor. of secs. 16 and 17 at proportionate dist.; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, to bedrock, and in a mound of stone, 4 ft. base to top, with brass cap mkd. T29S R11E ¼ S17 | S16 1963

De ent Resurvey of the Subdivision T 29 S. R. 11 E.

CHAINS

Asc. 10 ft. along gentle E. slope.

47.00 Slope changes; desc. 40 ft. over gentle NE. slope.

80.06 Point for the cor. of secs. 8, 9, 16 and 17 at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R11E
S8 | S9
S17 | S16
1963

Land, rolling.
Soil, sand and exposed sandstone.
No timber.
Undergrowth, black brush and bunch grass.

From the cor. of secs. 9, 10, 15 and 16.

N. 89°53' W., bet. secs. 9 and 16.

Over rolling desert land, draining NE.

8.00 Graded gravel road, Hanksville to Sawmill Basin, bears N. 10° E. and S. 10° W.; asc. 35 ft. over gentle E. slope.

24.75 Base of broken ascent, bears irregularly NE. and SW.; asc. 85 ft. over broken E. slope.

34.00 Crest of low rim, bears irregularly NE. and SW., thence over broken bench.

40.63 Point for the ¼ sec. cor. of secs. 9 and 16 at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., on solid sandstone, over an (X), and in a mound of stone, 4 ft. base, 28 ins. high, with brass cap mkd.

T29S R11E
¼ S9 / S16
1963

Desc. 30 ft. over broken bench draining S.

60.10 Small wash, drains S. 80° E., thence over rolling bench.

81.26 The cor. of secs. 8, 9, 16 and 17.

Land, rolling and broken.
Soil, sand and exposed sandstone.
No timber.
Undergrowth, black brush and bunch grass.

N. 0°05' E., bet. secs. 8 and 9.

Over rolling desert land; asc. 30 ft. over gentle SW. slope.

36.10 Crest low rise, slopes W.; desc. 15 ft. over gentle NW. slope.

De endent Resurve of the Subdivision T. 29 S. R. 11 E.

CHAINS

40.03 The ¼ sec. cor. of secs. 8 and 9, marked by a sandstone, 8x10x12 ins., plainly mkd. ¼.

At the cor. point

Set an iron post, 36 ins. long, 1 in. diam., 20 ins. in t e ground to bedrock, in a mound of stone, 4 ft. base to top with brass cap mkd.

T29S R11E
¼
S8 | S9
1963

Bury original stone N. and alongside iron post.

N. 0°20' E., beginning new measurement.

Desc. 60 ft. over NW. slope.

25.80 Small draw, drains W., thence along broken W. slope.

33.20 Small wash, drains W.

40.88 The cor. of secs. 4, 5, 8 and 9, marked by a sandstone, 3x12x18 ins., plainly mkd. 5 notches on S. and 4 notches on E. faces.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R11E
S5 | S4
S8 | S9
1963

Bury original stone N. and alongside iron post.

Land, rolling to broken.
Soil, sand and exposed sandstone.
No timber.
Undergrowth, shadscale and bunch grass.

From the corner of secs. 3, 4, 9 and 10.

N. 89°31' W., bet. secs. 4 and 9.

Over broken desert land; asc. 130 ft. over NE. slope, across irregular red clay hills.

23.00 Crest of steep ascent, bears N. 10° E., and irregularly SE.; asc. 25 ft. over gentle E. slope of bench.

36.30 Top of ascent on bench, bears N. and S.; desc. 10 ft. over W. slope.

40.47 The ¼ sec. cor. of secs. 4 and 9, marked by a sandstone, 4x12x14 ins., plainly mkd. ¼.

Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

Res of the Subdivision, T. 29 S., R. 11 E.

CHAINS	
	T29S R11E ¼ S4/S9 1963 Bury original stone N. and alongside iron post.
	N. 89°30' W., beginning new measurement. Desc. 110 ft. over W. slope of bench.
16.00	N. end of small red knoll covered with boulders, about 6 ft. high, 1 ch. diam.
40.13	The cor. of secs. 4, 5, 8 and 9. Land, broken to rolling. Soil, clay hills E. portion, sandy W. portion. No timber. Undergrowth, black brush and bunch grass on bench.
	N. 1°43' E., bet. secs. 4 and 5. Over broken desert land; desc. 40 ft. along gentle E. slope.
40.38	The ¼ sec. cor. of secs. 4 and 5, marked by a sandstone, 3x10x12 ins., plainly mkd. ¼. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with brass cap mkd. T29S R11E ¼ S5 | S4 1963 Bury original stone N. and alongside iron post.
	N. 0°19' E., beginning new measurement. Thence by triangulation, with topography scaled from U.S.G.S. sheet, "Mt. Ellen 1 SW."
5.00	Crest of rim, bears irregularly W. and NE.; desc. 100 ft. over ledgy N. slope.
8.00	Base of rim in small cove, bears NW. and E.; asc. 110 ft. over ledgy S. slope.
16.00	Point, projects W.; desc. 100 ft. over ledgy N. slope.
20.00	Base of point, thence across small cove in canyon bottom.
26.00	Base of ledges facing S.; asc. 100 ft. over S. slope.
28.00	Point, projects W., thence along ledgy E. breaks of small canyon.
31.90	Leave canyon rim; desc. 40 ft. over broken bench. End triangulation.

Dependent Resurvey of the Subdivision, T. 29 S., R. 11 E.

CHAINS

39.49 The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., marked by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurre t resurvey of the S. bdy. of T. 28 S., R. 11 E.

Land, broken.
Soil, sand and exposed sandstone.
No timber.
Undergrowth, black brush and bunch grass.

From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp.

North, bet. secs. 31 and 32.

Over broken desert land; desc. 65 ft. over N. slope.

31.00 Small wash, drains N. 10° W.

39.39 The ¼ sec. cor. of secs. 31 and 32, marked by a sandstone 8x10x120 ins., plainly mkd. ¼.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R11E
¼
S31 | S32
1963

Bury original stone N. and alongside iron post.

N. 0°16' W., beginning new measurement.

Desc. 45 ft. over broken N. slope.

40.20 The cor. of secs. 29, 30, 31 and 32, marked by a sandston , 5x10x15 ins., plainly mkd. 1 notch on S. and 5 notches on E. faces.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R11E
S30 | S29
S31 | S32
1963

Bury original stone W. and alongside iron post.

Land, broken.
Soil, sand and exposed sandstone.
No timber.
Undergrowth, black brush and bunch grass.

From the cor. of secs. 28, 29, 32 and 33.

S. 89°55' W., bet. secs. 29 and 32.

Over rolling desert land; asc. 50 ft. along gentle N. slo e

CHAINS	
32.40	Wash, 2 ft. deep, 20 lks. wide, drains NE.
39.90	Crest of rise, bears N. and S.; desc. broken W. slope.
40.71	The ¼ sec. cor. of secs. 29 and 32, marked by a sandstone, 3x14x20 ins., plainly mkd. ¼. At the cor. point Set an iron post, 36 ins. long, 1 in. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with brass cap mkd. T29S R11E ¼ S29/S32 1963 Bury original stone N. and alongside iron post.
	N. 89°13' W., beginning new measurement. Desc. 40 ft. over broken W. slope.
21.00	Wash, 3 ft. deep, 40 lks. wide, drains N.; asc. 10 ft. along gentle N. slope.
40.18	The cor. of secs. 29, 30, 31 and 32. Land, rolling and broken. Soil, sand and exposed sandstone. No timber. Undergrowth, shadscale and bunch grass.
	N. 89°31' W., bet. secs. 30 and 31. Over broken desert land; asc. 35 ft. along gentle N. slope.
4.00	Wash, 3 ft. deep, 40 lks. wide, drains NE.
23.50	Wash, 5 ft. deep, 50 lks. wide, drains N.
30.90	Low rise, bears N. and S.; desc. 25 ft. over gentle NW. slope.
38.86	The ¼ sec. cor. of secs. 30 and 31, marked by a sandstone, 3x12x14 ins., plainly mkd. ¼. At the cor. point Set an iron post, 36 ins. long, 1 in. diam., 20 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd. T29S R11E ¼ S30/S31 1963 Bury original stone N. and alongside iron post. Cor. falls in low swale, which drains N.

Dependent Resurvey of the Subdivision, T. 29 S., R. 11 E.

CHAINS	
	N. 88°03' W., beginning new measurement.
	Asc. 45 ft. over rolling NE. slope.
41.29	The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., marked by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of the E. bdy. of T. 29 S., R. 10 E.
	Land, broken to rolling. Soil, sand and exposed sandstone. No timber. Undergrowth, shadscale and bunch grass.
	From the cor. of secs. 29, 30, 31 and 32.
	N. 0°05' E., bet. secs. 29 and 30.
	Over rolling desert land; desc. 25 ft. over gentle NE. slope.
2.10	Wash, 4 ft. deep, 50 lks. wide, drains irregularly NE.
40.15	The ¼ sec. cor. of secs. 29 and 30, marked by a granite stone, 3x8x16 ins., plainly mkd. ¼.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T29S R11E ¼ S30 | S29 1963
	Bury original stone N. and alongside iron post.
	N. 0°06' W., beginning new measurement.
	Desc. 25 ft. over gentle NE. slope.
10.00	Wash, 3 ft. deep, 50 lks. wide, drains NE.
13.45	Graded dirt road, bears NE. and SW.
37.00	Wash, 4 ft. deep, 50 lks. wide, drains NE.
40.45	Point for the cor. of secs. 19, 20, 29 and 30 at proportionate dist.; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T29S R11E S19 | S20 S30 | S29 1963
	Land, rolling. Soil, sandy. No timber. Undergrowth, black brush and bunch grass.

Dependent Resurvey of the Subdivision, T. 29 S., R. 11 E.

CHAINS	
	From the cor. of secs. 20, 21, 28 and 29.
	N. 89°45' W., bet. secs. 20 and 29.
	Over rolling desert land; desc. 30 ft. over gentle NW. slope.
15.20	Dry Valley Wash, 5 ft. deep, 40 lks. wide, drains N. 30° E.; asc, 10 ft. over gentle NE. slope.
37.85	The ¼ sec. cor. of secs. 20 and 29, marked by a sandstone, 5x10x12 ins., dimly mkd. ¼.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T29S R11E ¼ S20/S29 1963
	Bury original stone N. and alongside iron post.
	N. 89°19' W., beginning new measurement.
	Asc. 45 ft. along gentle N. slope.
3.60	Bulldozed road, bears N. and S.
25.90	Bull Creek, 3 ft. deep, 30 lks. wide, drains N. 20° E.
28.60	Top of round clay hill; desc. 30 ft. over W. slope of hill.
32.20	Recross Bull Creek, drains S. 80° E. about base of hill; asc. gentle NE. slope.
40.43	The cor. of secs. 19, 20, 29 and 30.
	Land, rolling to broken. Soil, sand and exposed sandstone. No timber. Undergrowth, shadscale and scattered bunch grass.
	N. 88°50' W., bet. secs. 19 and 30.
	Over broken desert land; asc. 80 ft. over NE. slope.
9.00	Bull Creek, 3 ft. deep, 30 lks. wide, drains NE. about 3 chs., thence E.
40.35	Point for the ¼ sec. cor. of secs. 19 and 30 at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T29S R11E ¼ S19/S30 1963
	Cor. falls on low hill, which bears NE. and SW.; desc. 125 ft. over broken W. slope.

Dependent Resurvey of the Subdivision, T. 29 S., R. 11 E.

CHAINS	
50.10	Gully, drains NE.; asc. 90 ft. over an irregular E. slope
71.20	Crest of irregular hills, bears N. and S.; desc. 115 ft. over broken W. slope.
80.50	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., marked by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of the E. bdy. of T. 29 S., R. 10 E. Land, broken. Soil, sand and exposed sandstone. No timber. Undergrowth, scattered shadscale and bunch grass.
	From the cor. of secs. 19, 20, 29 and 30. N. 0°43' W., bet. secs. 19 and 20. Over broken desert land.
1.00	Bull Creek, 3 ft. deep, 40 lks. wide, drains E.; asc. 80 ft. over S. slope of irregular clay hills.
7.00	Crest of hills, bears E. and NW.; desc. 130 ft. over irregular NE. slope.
19.00	Base of hills, bears NW. and SE.; thence along E. slope.
40.45	Point for the ¼ sec. cor. of secs. 19 and 20 at proportionate dist.; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R11E ¼ S19 | S20 1963 Continue along gentle E. slope.
76.70	Wash, 3 ft. deep, 40 lks. wide, drains NE.; asc. 30 ft. over slope of rocky clay hill.
78.50	Crest low hill; desc. 30 ft. over N. slope of hill.
80.90	Point for the cor. of secs. 17, 18, 19 and 20, at proportionate dist.; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd. T29S R11E S18 | S17 S19 | S20 1963 Land, broken. Soil, sand and exposed sandstone, small clay hills. No timber. Undergrowth, shadscale and bunch grass.

Dependent Resurvey of the Subdivision, T. 29 S., R. 11 E.

CHAINS	
	From the cor. of secs. 16, 17, 20 and 21.
	S. 89°59' W., bet. secs. 17 and 20.
	Over rolling desert land; asc. 25 ft. along gentle N. slope.
15.80	Bladed dirt road, bears NE. and SW.
39.92	The ¼ sec. cor. of secs. 17 and 20, marked by a limestone, 3x10x18 ins., plainly mkd. ¼.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.
	T29S R11E ¼ S17/S20 1963
	Bury original stone N. and alongside iron post.
	N. 89°40' W., beginning new measurement.
	Desc. 20 ft. along irregular N. slope.
26.40	Wash, 5 ft. deep, 40 lks. wide, upper part of Bull Creek, drains irregularly N.
38.00	Enter low clay hills; asc. 10 ft. along N. slope of clay hill.
38.83	The corner of secs. 17, 18, 19 and 20.
	Land, rolling to broken. Soil, sand and low clay hills. No timber. Undergrowth, scattered shadscale and bunch grass.
	N. 89°22' W., bet. secs. 18 and 19.
	Over broken desert land draining N., across clay and sandstone hills.
19.20	Hollow, 45 ft. deep, drains SW.; asc. 65 ft. over E. slope of hollow.
22.00	Hill, bears NE. and SW.; desc. 80 ft. over W. slope of hill.
30.10	Wash, 3 ft. deep, 40 lks. wide, drains NW.; asc. 25 ft. over irregular N. slope.
38.93	The ¼ sec. cor. of secs. 18 and 19, marked by a limestone, 8x16x20 ins., plainly mkd. ¼.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd.

Dependent Resurvey of the Subdivision, T. 29 S., R. 11 E.

CHAINS	
	T29S R11E ¼ S18/S19 1963
	Bury original stone N. and alongside iron post.
	N. 89°02' W., beginning new measurement.
	Continue along broken N. slope.
10.10	Small wash, drains NE.
17.30	Small wash, drains NE.
24.50	Wash, 3 ft. deep, 30 lks. wide, drains NE.
40.77	The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., marked by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of the E. bdy. of T. 29 S., R. 10 E.
	From the cor. of secs. 17, 18, 19 and 20.
	N. 0°53' W., bet. secs. 17 and 18.
	Over broken desert land; desc. 10 ft. along small wash draining N.
21.50	Leave small wash; asc. 100 ft. over S. slope of sandstone hill.
25.80	Crest of sandstone hill, bears E. and W.; desc. 125 ft. over N. slope.
36.50	Base of same hill, bears NW. and SE., also wash, 3 ft. deep, 40 lks. wide, drains N. 20° W.; desc. 15 ft. over N. slope.
40.45	Point for the ¼ sec. cor. of secs. 17 and 18 at proportionate dist.; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T29S R11E ¼ S18/S17 1963
	Desc. 30 ft. over broken NE. slope.
71.00	Wash, 8 ft. deep, 90 lks. wide, drains NE.; asc. 70 ft. over SE. slope of sandstone hill.
76.00	Crest of sandstone hill, bears NE. and SW.; desc. 40 ft. over NW. slope of hill.
80.90	The cor. of secs. 7, 8, 17 and 18, marked by a sandstone 5x8x14 ins., plainly mkd. 4 notches on S. and 5 notches on E. faces.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., on solid sandstone, over an (X), and in a mound of stone, 4 ft. base to top, with brass cap mkd.

Dependent Resurvey of the Subdivision, T. 29 S., R. 11 E.

CHAINS	
	T29S R11E S7 | S8 S18 | S17 1963
	Bury original cor. in mound of stone and alongside iron post.
	Cor. falls on low sandstone ledge, on N. side of small wash.
	Land, broken. Soil, sandy clay and exposed sandstone. No timber. Undergrowth, shadscale and bunch grass.
	From the cor. of secs. 8, 9, 16 and 17.
	N. 88°53' W., bet. secs. 8 and 17.
	Over rolling sandy desert land; asc. 15 ft. over gentle E. slope.
12.12	Low rim, bears irregularly SW. and NE.; desc. 40 ft. over broken land draining NE. in small basin.
30.60	Base of low bluff, bears N. and SE.; asc. 35 ft. over NE. slope.
31.20	Crest of same bluff, bears N. and SE.; desc. 10 ft. over broken bench.
40.80	The ¼ sec. cor. of secs. 8 and 17, marked by a sandstone, 6x8x20 ins., plainly mkd. ¼.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T29S R11E ¼ S8 S17 1963
	Bury original stone N. and alongside iron post.
	N. 89°46' W., beginning new measurement.
	Continue over broken bench.
2.80	W. crest of bench, bears NW. and SE.; desc. 70 ft. over ledgy SW. slope.
10.70	Base of ledgy slope, bears N. and SE., also wash, drains N.; desc. 25 ft. over bottom of small hollow.
21.30	Bull Creek, 2 ft. deep, 30 lks. wide, drains NE.
25.30	Base of ledgy terrace, bears NE. and SW.; asc. 80 ft. over ledgy SE. slope.
28.20	Crest of same terrace, bears NE. and SW.; desc. 15 ft. over broken NW. slope of sandstone hill.
39.85	Small wash, drains N. 50° E.

De[illegible]t Resurvey of [illegible] S[illegible]

CHAINS	
39.89	The cor. of secs. 7, 8, 17 and 18. Land, rolling to broken. Soil, sand and exposed sandstone. No timber. Undergrowth, shadscale and bunch grass.
	N. 89°50' W., bet. secs. 7 and 18. Over rocky broken bench.
2.60	Small wash, drains S. 80° E.
9.60	Leave broken land, thence over level rocky bench.
32.00	Leave bench, enter broken land along N. face of low clay banks.
38.69	The ¼ sec. cor. of secs. 7 and 18, marked by a granite stone, 3x10x12 ins., in a mound of stone and earth, no visible marks. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R11E S7 ¼ S18 1963 Cor. falls in small cove in clay banks, which faces N.
	N. 89°36' W., beginning new measurement. Desc. 60 ft. along irregular clay banks, facing N.
9.00	Leave clay banks; desc. 20 ft. over small pass, which bears N. and S.
14.50	Lone white boulder, 6 ft. high, 8 ft. diam.
24.50	Small wash, drains N.; asc. 55 ft. over E. slope of irregular clay hills.
37.70	Crest of hills, bears N. and S.; desc. 20 ft. over broken bench.
40.26	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., marked by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of the E. bdy. of T. 29 S., R. 10 E. Land, broken. Soil, sand, clay and exposed sandstone. No timber. Undergrowth, shadscale and bunch grass.
	From the cor. of secs. 7, 8, 17 and 18. N. 0°01' W., bet. secs. 7 and 8.

Dependent Resurvey of the Subdivision, T. 29 S., R. 11 E.

CHAINS

Over broken desert land; asc. 40 ft. along irregular E. slope.

37.00 Low spur, slopes E.; desc. 45 ft. over N. slope.

40.22 The ¼ sec. cor. of secs. 7 and 8, marked by a granite stone, 6x10x18 ins., plainly mkd. ¼.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R11E
¼
S7 | S8
1963

Bury original stone W. and alongside iron post.

Raise a mound of stone, 2½ ft. base, 2½ ft. high, W. of corner.

N. 0°09' E., beginning new measurement.

Desc. 30 ft. over rolling sandy desert land.

40.13 The cor. of secs. 5, 6, 7 and 8, marked by a granite stone, 5x6x18 ins., plainly mkd. 5 notches on S. and E. faces.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.

T29S R11E
S6 | S5
S7 | S8
1963

Bury original stone N. and alongside iron post.

Land, broken to rolling.
Soil, sand and exposed sandstone.
No timber.
Undergrowth, shadscale and bunch grass.

From the cor. of secs. 4, 5, 8 and 9.

N. 89°41' W., bet. secs. 5 and 8.

Over broken desert land; desc. 120 ft. over W. slope.

29.00 Crest small black knoll, 2 chs. diam.

37.79 The ¼ sec. cor. of secs. 5 and 8, marked by a sandstone, 5x8x12 ins., in small mound of stone, dimly mkd. ¼.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd.

Dependent Resurvey of the Subdivision, T. 29 S., R. 11 E.

CHAINS

T29S R11E
¼ S5/S8
1963

Bury original cor. in mound of stone and alongside iron post.

N. 89°48' W., beginning new measurement.

Desc. broken W. slope.

1.40 E. rim small hollow, bears N. 20° E. and S. 20° W.; desc. 35 ft. over ledgy W. slope.

4.00 Bull Creek, dry at time of survey, drains NE.; asc. 70 ft. over ledgy E. slope.

9.90 W. rim same hollow, bears N. 20° E. and S. 20° W.; desc. 25 ft. over rolling sandy bench, with patches of exposed sandstone.

38.60 Small wash, drains NE.; asc. 5 ft. over gentle E. slope.

43.05 The cor. of secs. 5, 6, 7 and 8.

Land, broken to rolling.
Soil, sand and exposed sandstone.
No timber.
Undergrowth, black brush and scattered bunch grass.

N. 89°37' W., bet. secs. 6 and 7.

Over rolling sandy bench land; asc. 50 ft. over gentle E. slope.

1.50 Unimproved dirt road, bears irregularly N. and S.

18.50 Crest of low rise, bears N. and S., thence over rolling land.

38.70 N. end small island mesa, 1 ch. wide, 5 chs. long; desc. 20 ft. over W. slope of mesa.

40.17 The ¼ sec. cor. of secs. 6 and 7, marked by a sandstone, 3x10x14 ins., plainly mkd. ¼.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.

T29S R11E
¼ S6/S7
1963

Bury original stone N. and alongside iron post.

Cor. falls at base of W. slope of small mesa.

N. 89°34' W., beginning new measurement.

Desc. 35 ft. over gentle W. slope.

endent Resurvey of the Subdivision, T. 29 S., R. 11 E.

CHAINS	
10.30	Small barren flat in small basin; asc. 35 ft. over gentle E. slope of basin.
36.30	W. side of flat in basin; desc. 10 ft. over rocky W. slope.
39.03	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., marked by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of the E. bdy. of T. 29 S., R. 10 E. Land, broken and rolling. Soil, sand and exposed sandstone. No timber. Undergrowth, black brush and bunch grass.
	From the cor. of secs. 5, 6, 7 and 8. N. 0°35' E., bet. secs. 5 and 6. Over rolling sandy bench land.
40.33	The ¼ sec. cor. of secs. 5 and 6, marked by a sandstone, 4x6x10 ins., plainly mkd. ¼. At the cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T29S R11E ¼ S6 | S5 1963 Bury original stone N. and alongside iron post.
	N. 0°28' E., beginning new measurement. Continue over rolling bench land.
14.50	Unimproved dirt road, bears NE. and SW.
39.84	The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., marked by iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of the S. bdy. of T. 28 S., R. 11 E. Land, rolling. Soil, sand. No timber. Undergrowth, black brush and scattered bunch grass.

General Description

T. 29 S., R. 11 E. is located about 3 miles south of Hanksville, Utah, and consists of rolling sandy desert land, broken by several bluffs and deep washes. The general drainage is northeast to the Fremont River.

Main roads within the township consist of the Hanksville to Hite road, which bears southward through the northeast

CHAINS

portion of the township, and the Hanksville to Sawmill Basin road, which bears southward through the central portion of the township. Several trail roads branch off these roads, used mainly by stockmen.

No permanent dwellings were noted within the township.

Several intermittent springs, in the bottom of the washes, was the only water noted during the survey.

Vegetation consists of brush and scattered bunch grass; there is no timber.

The elevation of the township varies from about 4400 to 5000 feet above sea level.

Form 4-680
(June 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
LaVern Griffin	Transit (Crew Chief)
Gail E. Reynolds	Notes
Charles D. Crabb	Front chain
Jay Hyatt	Flagman
Calvin M. Gleave	Cornerman

562

CERTIFICATE OF SURVEY

I, CRAIG P. SYLVESTER, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 21st day of August, 1963, I have dependently resurveyed the South boundary and the subdivisional lines of Township 29 South, Range 11 East,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

March 18, 1964
(Date)

(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date NOV 29 1965

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the dependent resurvey of the South boundary and subdivisional lines of Township 29 South, Range 11 East,

executed by Craig P. Sylvester, Cadastral Surveyor,

having been critically examined and found correct, are hereby approved.

JUN 15 1966
(Date)

(Chief, Division of Engineering)

~~CERTIFICATE OF TRANSCRIPT~~

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in , is a true copy of the original field notes.

~~(Date)~~

~~(Chief, Division of Engineering)~~

Blank

Page

Blank

Page

Form 4-679
(January 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

565

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF A PORTION OF

TOWNSHIP 30 SOUTH, RANGE 11 EAST

Of the SALT LAKE Meridian,

In the State of UTAH.

EXECUTED BY

Craig P. Sylvester, Cadastral Surveyor

Under special instructions dated August 21, 19 63, which provided for the surveys included under Group Number 466, approved August 22, 1963, and assignment instructions dated September 24, 19 63.

Survey commenced October 11, 19 63

Survey completed November 21, 19 63

DEPT. OF THE INTERIOR
BUR OF LAND MGMT

1986 JUL 26 AM 11 03 .4

OFFICE & LAND OFFICE
SALT LAKE CITY, UTAH

INDEX DIAGRAM

Township 30 SOUTH, Range 11 EAST,

6 22	23 5 22	17 4 17	13 3 12	9 2 8	5 1 5
7 20	21 8 19	16 9 15	11 10 11	7 11 7	4 12 3
18	18 17	14 16	9 15	6 14	2 13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

GPO 831242

Dependent Resurvey, North Portion, T. 30 S., R. 11 E.

CHAINS

The north boundary was surveyed by A. D. Ferron in 1882, and was concurrently resurveyed, and the record appears in the field notes of T. 29 S., R. 11 E. The north 3 miles of the east and the north 4 miles of the west boundaries were surveyed by A. D. Ferron in 1882, and resurveyed by Elliot Bird in 1919. The south 3 miles of the east and the south 2 miles of the west boundaries and the south boundary were surveyed by Elliot Bird in 1919. The subdivisional lines of the north ½ of the township were surveyed by A. D. Ferron in 1882. The subdivisional lines of the south ½ of the township were surveyed and the north boundaries of sections 19 to 24 resurveyed by Elliot Bird in 1919. A portion of the boundaries of secs. 25 and 26 were dependently resurveyed and the sections were subdivided by Robert C. Yundt in 1949.

The following field notes are those of a dependent resurvey of the north ½ of the subdivision of T. 30 S., R. 11 E.

The survey was executed with W.&L. E. Gurley Transit #570614 constructed in accordance with the standard instrumental specifications of the Bureau of Land Management. The instrument was in good condition prior to the beginning of the survey and was maintained in proper adjustment throughout the progress of the survey.

Corners on the east-west lines were set on the true latitudinal curve. Lines connecting previously established corners were run by random and true method, but for simplification of the record, the random lines are omitted from these field notes.

Measurements herein contained were made with a narrow steel tape, 8 chains in length, graduated every link for the first 100 links, and thereafter at intervals of 10 links. The tape was tested by a 1 chain standard steel tape and found to be correct. Measurements were made on the slope with vertical angles of each interval ascertained by a clinometer in good adjustment; horizontal equivalents alone are entered in the field notes. All lines of this survey were run by the direct method where the lines were accessible; lines inaccessible were run by traverse or triangulation methods. Distances to topography on lines run by traverse and triangulation methods are approximate, as scaled from U.S.G.S. topographic sheets. The details of such traverses and triangulations have been thoroughly checked and verified, and in order to simplify the records, the diagrams and reductions are omitted from these field notes.

The direction of the lines of this survey were determined by reference to true meridians established on line by observations on Polaris at elongation. They were carried forward by sustained angulation, being supplemented by numerous other observations on Polaris taken throughout the progress of the survey.

Before restoring lost corners, the lines of the original survey were retraced and a diligent search made for any evidence of the original corners. The rules of proportionate measurement were applied to ascertain the position of the lost corner after every reasonable possibility of finding direct evidence of the corner had been exhausted.

The geographic position for the cor. of secs. 13 and 24, on the east boundary of the township is in latitude 38° 11' 32.84" N. and longitude 110°39'22.98" W., as determined

Dependent Resurvey, North Portion, T. 30 S., R. 11 E.

CHAINS

by traverse from U.S.G.S. triangulation station "Cattle," situated in sec. 32, T. 29 S., R. 11 E.

The magnetic declination was read at a number of stations throughout the township and the average of the several readings was found to be 15°30' E.

Dependent Resurvey T. 30 S., R. 11 E.

Reestablishment of the Survey Executed by A. D. Ferron, Deputy Surveyor, 1883.

Beginning at the cor. of secs. 13 and 14, an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of resurveys in T. 30 S., R. 11 E. in 1919.

N. 0°03' W., bet. secs. 13 and 14.

Over rocky broken bench land, covered with black brush; desc. 10 ft. over N. slope of small rise.

16.00 Slope changes; desc. 80 ft. over NW. slope of rise.

36.80 Base of rise, bears NE. and SW.; desc. gentle NW. slope.

40.37 The ¼ sec. cor. of secs. 13 and 14, monumented by a sandstone 2x9x12 ins. plainly mkd. "¼".

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T30S R11E
¼
S14 | S13
1963

bury original stone beside iron post.

N. 1° 28' E., beginning new measurement.

Desc. 45 ft. over gentle NW. slope, covered with black brush.

36.76 The cor. of secs. 11, 12, 13 and 14, monumented by a sandstone 5x18x20 ins., plainly mkd. 4 notches on S., and 1 notch on E. faces.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T30S R11E
S11 | S12
S14 | S13
1963

bury original stone beside iron post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of iron post.

Land, broken.

Dependent Resurvey T. 30 S., R. 11 E.

CHAINS

Soil, gravelly and rocky.
Timber, none.
Undergrowth, blackbrush.

The cor. of secs. 12 and 13 on the east boundary of the Tp., established by the resurvey of the Henry Mountain Guide Meridian in 1921, has been removed by bulldozer work, and was reestablished at proportionate distance between the E. ¼ sec. cors. of secs. 12 and 13.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.

T30S
R11E R12E
S12 | S13 |
1963

From this cor. the E. ¼ sec. cor. of sec. 12 bears N. 39.70 chs. dist., monumented by an iron post 1 in. diam., set, mkd. and witnessed as described in the official record.

From the same cor. the E. ¼ sec. cor. of sec. 13 bears S. 39.70 chs. dist., monumented with an iron post 1 in. diam., set, mkd. and witnessed as described in the official record.

S. 89°07' W. bet. secs. 12 and 13.

Over rolling sandy desert land, covered with shadscale; asc. 60 ft. over E. slope.

12.00 Base of bluff, bears NE. and SW. irregular; asc. 200 ft. over steep SE. slope and ledges facing SE.

17.50 Crest of same bluff, bears NE. and SW. irregular; asc. 20 ft. over E. slope of bench.

21.50 Top of ascent; desc. 35 ft. over gentle W. slope.

40.95 Point for the ¼ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 36 ins. long, 1 in. diam., 28 ins. in the ground, in a collar of stone, with brass cap mkd.

T30S R11E
¼ S12/S13
1963

Desc. 35 ft. over W. slope.

52.35 E. side of hollow, bears NE. and SW.; desc. 50 ft. over W. slope into hollow.

57.25 Wash in bottom of hollow, drains N.; asc. 50 ft. over E. slope.

60.95 W. side same hollow, bears NE. and SW.; desc. 15 ft. over rolling land.

Dependent Resurvey T. 30 S. R. 11 E.

CHAINS

81.90 The cor. of secs. 11, 12, 13 and 14.

Land, rolling and broken.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, blackbrush.

N. 0°11' W., bet. secs. 11 and 12.

Over rolling desert land, covered with black brush; desc. 25 ft. along gentle W. slope.

17.40 Small wash, drainsW.; desc. 35 ft. over NW. slope.

40.17 The ¼ sec. cor. of secs. 11 and 12, monumented with a sandstone, 6x12x18 ins., plainly mkd. "¼."

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground, in a mound of stone 3 ft. base to top, with brass cap mkd.

T30S R11E
¼
S11 | S12
1963

Place original stone beside iron post.

N. 0°56' E., beginning new measurement.

Continue over gentle NW. slope.

.75 Small wash, drains W.

14.80 Wash, 2 ft. deep, 20 lks. wide, drains W.; asc. 30 ft. over SW. slope.

29.50 Crest of low rim, bears E. and W., thence along W. slope.

35.10 Rim, bears NW. and SE.; desc. 40 ft. along broken E. slop .

40.27 Point for the cor. of secs. 1, 2, 11 and 12, at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.

T30S R11E
S2 | S1
S11 | S12
1963

Cor. falls on E. slope of small hollow.

Land, broken and rolling.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, black brush and scattered bunch grass.

From the cor. of secs. 1 and 12 on the E. bdy. of the Tp. which is monumented with an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record.

Dependent Resurvey, T. 30 S., R. 11 E.

CHAINS	
	S. 89°54' W., bet. secs. 1 and 12.
	Over broken desert land, draining N.; asc. 100 ft. over E. slope of spur.
7.20	Spur, slopes N.; desc. 90 ft. over W. slope.
16.10	Wash, 2 ft. deep, 20 lks. wide, drains N. 20° W., thence over broken desert land, draining N.
34.00	Wash, 3 ft. deep, 20 lks. wide, drains N.
40.70	Point for the ¼ sec. cor. of secs. 1 and 12, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T30S R11E ¼ S1/S12 1963
	Place a boulder 2x2x2 ft. N. of iron post.
	Desc. 15 ft. along broken N. slope.
44.00	Wash, 2 ft. deep, 15 lks. wide, drains N.; asc. 10 ft. along N. slope.
53.00	Small wash, drains NE.; asc. 25 ft. over NE. slope.
63.00	Base of steep ascent, bears N. and S.; asc. 110 ft. over E. slope.
67.00	Crest of high spur, slopes N.; desc. 75 ft. over W. slope.
76.20	Wash, 3 ft. deep, 20 lks. wide, drains N.; asc. 15 ft. over E. slope.
81.40	The cor. of secs. 1, 2, 11 and 12, previously described.
	Land, broken. Soil, sand and exposed sandstone. Timber, none. Undergrowth, black brush and scattered bunch grass.
	N. 0°52' W., bet. secs. 1 and 2.
	Over broken desert land; desc. 60 ft. along E. slope of small hollow.
15.70	Leave hollow; desc. 55 ft. over gentle N. slope.
40.27	The ¼ sec. cor. of secs. 1 and 2, monumented by a sandstone, 4x18x18 ins., plainly mkd."¼".
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T30S R11E ¼ S2 | S1 1963

Dependent Resurvey, T. 30 S., R. 11 E.

CHAINS

Bury original stone beside iron post.

N. 1°01' W., beginning new measurement.

Desc. N. slope.

3.80 Graded dirt road, bears E. and W.; desc. 10 ft. along E. slope.

8.00 Halfway Wash, 3 ft. deep, 1 ch. wide, drains NE.; asc. 20 ft. over SE. slope.

14.50 Wash, 2 ft. deep, 30 lks. wide, drains SE.; thence over series of small gullies draining SE.

40.63 The cor. of secs. 1, 2, 35 and 36 on the N. bdy., monumented by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of T. 29 S., R. 11 E.

Land, broken.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, black brush.

From the cor. of secs. 14 and 15, an iron post, 2 ins. diam., set, mkd. and witnessed as described in the officia record of resurveys in T. 30 S., R. 11 E., in 1919.

N. 0°53' W., bet. secs. 14 and 15.

Over broken desert land, covered with black brush; desc. 100 ft. over irregular N. slope.

33.30 Wash, 4 ft. deep, 40 lks. wide, drains NE.; desc. 15 ft. over gentle NE. slope.

40.01 The ¼ sec. cor. of secs. 14 and 15, monumented by a mound of stone, no visible marks, but agrees with the original field notes.

t the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T30S R11E
¼
S15|S14
1963

. 2°11' E., beginning new measurement.

esc. 80 ft. over NE. slope.

13.40 ash, 3 ft. deep, 20 lks. wide, drains NE.

17.20 raded dirt road, bears NE. and SW.

37.60 mall hollow, 2 chs. wide, drains NE.

39.84 oint for the cor. of secs. 10, 11, 14 and 15, at proporionate dist.; there is no remaining evidence of the riginal cor.

Dependent Resurvey T. 30 S., R. 11 E.

CHAINS	
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone 4 ft. base to top, with brass cap mkd. T30S R11E S10 | S11 S15 | S14 1963 Land broken. Soil, gravelly. Timber, none. Undergrowth, black brush and scattered bunch grass.
	From the cor. of secs. 11, 12, 13 and 14. N. 87°56' W., bet. secs. 11 and 14. Over broken desert land, covered with black brush; desc. 80 ft. over gentle NW. slope.
31.40	Wash, 2 ft. deep, 20 lks. wide, drains N.; asc. 30 ft. over E. slope.
40.26	Point for the ¼ sec. cor. of secs. 11 and 14, at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 36 ins. long, 1 in. diam., 28 ins. in the ground, in a collar of stone, with brass cap mkd. T30S R11E ¼ S11 S14 1963 Asc. 35 ft. over E. slope.
43.20	Low rise, slopes N.; desc. 20 ft. over W. slope.
52.20	Wash, 2 ft. deep, 30 lks. wide, drains N.; asc. 65 ft. over NE. slope.
68.45	Graded dirt road, bears N. and S.
79.30	Wash, in small hollow, drains NE.
80.52	The cor. of secs. 10, 11, 14 and 15. Land, broken. Soil, sand and exposed sandstone. Timber, none. Undergrowth, black brush and scattered bunch grass.
	N. 0°04' W., bet. secs. 10 and 11. Over broken desert land, covered with black brush; desc. 45 ft. over NE. slope.
12.70	Halfway Wash, 5 ft. deep, 20 lks. wide, drains NE.
39.82	Point for the ¼ sec. cor. of secs. 10 and 11, at proportionate dist.; there is no remaining evidence of original corner.

Dependent Resurvey T. 30 S., R. 11 E.

CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T30S R11E
¼
S10|S11
1963

Raise a mound of stone, 2½ ft. base, 2½ ft. high, W. of iron post.

Desc. 55 ft. over gentle NE. slope.

39.90 Bulldozed road, bears E. and W.

69.60 Wash, 3 ft. deep, 30 lks. wide, drains NE.; asc. 10 ft. over gentle SE. slope.

79.64 Point for the cor. of secs. 2, 3, 10 and 11, at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T30S R11E
S3|S2
S10|S11
1963

Land, broken desert.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, black brush and scattered bunch grass.

From the cor. of secs. 1, 2, 11 and 12.

N. 89°00' W., bet. secs. 2 and 11.

Over broken desert land; asc. 20 ft. over E. slope of spur.

1.50 Spur, slopes N.; desc. 50 ft. over NW. slope.

11.20 Wash, 4 ft. deep, 20 lks. wide, drains W. irregularly; desc. 20 ft. along wash.

17.60 Leave wash which changes course to NW.; desc. 20 ft. over NW. slope.

24.90 Halfway Wash, 3 ft. deep, 10 lks. wide, drains N.; asc. 15 ft. over gentle E. slope.

37.00 Bulldozed road, bears N. and S.

40.70 The ¼ sec. cor. of secs. 2 and 11, monumented by a sandstone, 5x18x18 ins., plainly mkd. "¼".

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.

T30S R11E
¼ S2/S11
1963

Dependent Resurvey T. 30 S., R. 11 E.

CHAINS	
	Bury original stone beside iron post.
	N. 87°56' W., beginning new measurement.
	Asc. 45 ft. over gentle E. slope.
17.10	Crest of low rise, bears N. and S.; desc. 30 ft. over W. slope.
33.40	Wash, 4 ft. deep, 30 lks. wide, drains NE.; asc. 35 ft. over gentle E. slope.
40.37	The cor. of secs. 2, 3, 10 and 11.
	Land, broken and rolling. Soil, sand and exposed sandstone. Timber, none. Undergrowth, black brush and scattered bunch grass.
	N. 0°07' W., bet. secs. 2 and 3.
	Over rolling desert land, covered with black brush; asc. 35 ft. over gentle SE. slope.
8.50	Small wash, drains E.
38.10	Top low rise, bears NE. and SW.; desc. gentle NE. slope.
39.82	Point for the ¼ sec. cor. of secs. 2 and 3, at proportionate dist.; there is no remaining evidence of original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T30S R11E ¼ S3|S2 1963
	Desc. 60 ft. over rolling NE. slope.
55.80	Small wash, drains NE.
79.23	The cor. of secs. 2, 3, 34 and 35, on the N. bdy., monumented by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of T. 29 S., R. 11 E.
	Land, rolling. Soil, sand and exposed sandstone. Timber, none Undergrowth, black brush and scattered bunch grass.
	From the cor. of secs. 15, 16, 21 and 22, an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of resurveys in T. 30 S., R. 11 E., in 1919.
	N. 0°44' W., bet. secs. 15 and 16.
	Over broken desert land, covered with yellow brush and scattered bunch grass; desc. 20 ft. along W. slope.

Dependent Resurvey T. 30 S., R. 11 E.

CHAINS	
10.90	Wash, 3 ft. deep, 20 lks. wide, drains NE.; asc. 65 ft. over S. slope of small hill.
19.20	Crest of round hill; desc. 45 ft. over NE. slope of hill.
24.10	Base of hill, also small hollow, drains E.; desc. 85 ft. over NE. slope.
35.30	Halfway Wash in bottom of small hollow, drains E.; asc. 20 ft. over SE. slope.
39.56	The ¼ sec. cor. of secs. 15 and 16, monumented by a granite stone, 6x12x18 ins. plainly mkd."¼".
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T30S R11E ¼ S16 | S15 1963
	Place original stone N. of iron post.
	N. 2°48' E., beginning new measurement.
	Asc. 35 ft. over SE. slope.
3.50	S. crest small bench, bears NE. and W., thence over bench.
9.90	N. crest same bench, bears E. and W.; desc. 60 ft. over N. slope.
14.40	Wash, 3 ft. deep, 30 lks. wide, drains E.; asc. 60 ft. over S. slope.
20.80	Low spur, slopes E.; desc. 100 ft. over N. slope.
24.70	Wash, 2 ft. deep, 10 lks. wide, drains NE.; asc. 30 ft. over S. slope.
28.70	Low spur, slopes E.; thence along broken E. slope.
38.00	Head of small draw, drains N.; desc. 50 ft. over N. slope.
39.51	Point selected for the witness cor. of secs. 9, 10, 15 and 16.
	Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground, in a mound of stone 4 ft. base to top, with brass cap mkd.
	T30S R11E W C S9 | S10 S16 | S15 1963
	Desc. into draw.
40.51	Point for the cor. of secs. 9, 10, 15 and 16, at proportionate dist., falls in bottom of gully and cannot be perpetuated. There is no remaining evidence of original cor.

Dependent Resurvey T. 30 S., R. 11 E.

CHAINS	
	Land, broken. Soil, sand and exposed sandstone. Timber, none. Undergrowth, black brush and scattered bunch grass.
	From the cor. of secs. 10, 11, 14 and 15.
	N. 89°25' W., bet. secs. 10 and 15.
	Over broken desert land, covered with black brush; asc. 25 ft. over E. slope.
10.00	Low spur, slopes NE.; desc. 55 ft. over NW. slope.
16.90	Halfway wash, 4 ft. deep, 20 lks. wide, drains NE.; asc. 45 ft. over SE. slope of small draw.
26.90	W. side small draw, bears NE. and SW.; asc. 40 ft. over gentle E. slope.
40.64	The ¼ sec. cor. of secs. 10 and 15, monumented with a sandstone, 8x10x14 ins., plainly mkd. "¼".
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T30S R11E ¼ S10/S15 1963
	Place original stone North of iron post.
	N. 89°47' W., beginning new measurement.
	Asc. 65 ft. over E. slope.
21.30	Low spur, slopes NE.; desc. 125 ft. over NW. slope.
30.30	Wash, 4 ft. deep, 20 lks. wide, drains N.; asc. 65 ft. over E. slope.
34.00	Small spur, slopes N.; desc. 35 ft. over W. slope into small draw.
40.23	True point for the cor. of secs. 9, 10, 15 and 16, from which its witness cor. bears S. 2°48' W., 1.00 ch. dist., previously described.
	Land, broken. Soil, sand and exposed sandstone. Timber, none. Undergrowth, black brush and scattered bunch grass.
	N. 0°25' W., bet. secs. 9 and 10.
	Over broken desert land; desc. 90 ft. N. slope in bottom of small draw.
8.00	Leave mouth of draw; desc. 30 ft. over gentle NE. slope.
16.60	Small wash, drains NE.

Dependent Resurvey T. 30 S., R. 11 E.

CHAINS

40.46 The ¼ sec. cor. of secs. 9 and 10, monumented by a sandstone, 16x16x34 ins., plainly mkd. "¼".

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T30S R11E
¼
S9 | S10
1963

Place original stone N. of iron post.

Raise a mound of stone, 2½ ft. base, 2½ ft. high, W. of iron post.

N. 0°26' W., beginning new measurement.

Desc. 40 ft. over rolling N. slope.

9.00 Wash, 3 ft. deep, 40 lks. wide, drains NE.

25.00 Graded dirt road, bears S. 80° E. and N. 80° W.

37.50 Wash, 5 ft. deep, 50 lks. wide, drains NW.; desc. along W. slope.

39.27 The cor. of secs. 3, 4, 9 and 10, monumented with a sandstone, 4x12x20 ins., plainly mkd. and firmly set.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., on solid sandstone, over an X, in a mound of stone 4 ft. base to top, with brass cap mkd.

T30S R11E
S4 | S3
S9 | S10
1963

Cor. falls on edge of small ledge facing SW.

Place original stone N. of iron post.

Land, broken to rolling.
Soil, sand and exposed sandstone.
Timber, none.
Undergrowth, black brush and scattered bunch grass.

From the cor. of secs. 2, 3, 10 and 11.

N. 89°31' W., bet. secs. 3 and 10.

Over broken desert land, covered with black brush and scattered bunch grass; asc. 85 ft. over E. slope.

24.10 Crest of low rim, bears N. and S. irregularly; desc. 15 ft. over gentle W. slope.

40.65 Point for the ¼ sec. cor. of secs. 3 and 10, at proportionate dist.; there is no remaining evidence of original ...

Resurvey T. 30 S., R. 11 E.

CHAINS	
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T30S R11E ¼ S3/S10 1963
	Place a boulder 1x2x2 ft. N. of iron post.
	Desc. 65 ft. over gentle W. slope.
81.30	The cor. of secs. 3, 4, 9 and 10.
	Land, broken. Soil, sand and exposed sandstone. Timber, none. Undergrowth, black brush and scattered bunch grass.
	N. 0°59' E., bet. secs. 3 and 4.
	Over broken desert land, covered with black brush and scattered bunch grass, along irregular W. slope.
16.00	Small hill top; desc. 20 ft. over NW. slope.
40.09	The ¼ sec. cor. of secs. 3 and 4, monumented with a conglomerate stone, 8x12x18 ins., plainly mkd. "¼."
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T30S R11E ¼ S4 | S3 1963
	Bury original stone beside iron post.
	N. 0°27' E., beginning new measurement.
	Desc. 80 ft. along broken W. slope.
14.90	Wash, 5 ft. deep, 20 lks. wide, drains W.; asc. 45 ft. over S. slope of small knoll.
20.00	Top of knoll, about 5 chs. diam.; asc. 45 ft. over irregular NW. slope.
38.83	The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of T. 29 S., R. 11 E.
	Land, broken. Soil, sand and exposed sandstone. Timber, none. Undergrowth, black brush and scattered bunch grass.

Dependent Resurvey, T. 30 S., R. 11 E.

CHAINS	
	From the cor. of secs. 16, 17, 20 and 21, an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of resurveys in T. 30 S., R. 11 E., in 1919.
	N. 0°20' E., bet. secs. 16 and 17.
	Over gravelly bench land, covered with bunch grass; desc. 95 ft. over N. slope.
24.00	Crest of steep decent, bears NE. and SW.; desc. 70 ft. along broken E. slope of draw.
30.30	Small spur, slopes NE.; desc. 100 ft. over N. slope.
34.10	Gully, drains NE., about 6 chs. to junction; asc. 80 ft. over steep SE. slope.
38.20	Spur, slopes NE.; desc. 50 ft. over N. slope.
40.38	The ¼ sec. cor. of secs. 16 and 17, monumented with a granite stone, 6x8x14 ins., plainly mkd. "¼."
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone 3 ft. base, 10 ins. high, with brass cap mkd.
	T30S R11E ¼ S17 | S16 1963
	Cor. falls in small swale; which drains E.
	Place original stone N. of iron post.
	N. 0°09' E., beginning new measurement.
	Desc. N. slope.
1.50	Rocky knob on small spur; desc. 120 ft. over N. slope.
9.10	Wash, 2 ft. deep, 50 lks. wide, drains N. 10° W.; desc. 95 ft. along W. slope of small draw.
22.90	Same wash, drains N. 10° E., irregular; desc. 70 ft. along wash.
32.20	Same wash, drains N. 10°W.; asc. 10 ft. along W. slope of small draw.
39.74	The cor. of secs. 8, 9, 16 and 17, monumented with a granite stone, 12x12x18 ins., plainly mkd. 4 notches on S., and 4 notches on E. face.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T30S R11E S8 | S9 S17 | S16 1963
	Bury original stone N. of iron post.

Dependent Resurvey T. 30 S. R. 11 E.

CHAINS	
	Land, broken. Soil, gravelly. Timber, none. Undergrowth, black brush and bunch grass.
	From the true point for the cor. of secs. 9, 10, 15 and 16, from which its witness cor. bears S. 2°48' W., 1.00 ch. dist., previously described.
	N. 89°56' W., bet. secs. 9 and 16.
	Over broken desert land; asc. 180 ft. over broken E. slope of draw.
8.60	Crest of ledges facing E.; asc. 10 ft. along broken S. slope of hill.
14.40	Spur, slopes S.; desc. 35 ft. along ledgy S. slope.
19.10	Spur, slopes S.; desc. 55 ft. along broken S. slope.
22.70	Spur, slopes S.; desc. 130 ft. over SW. slope of hill.
30.20	Wash, 5 ft. deep, 40 lks. wide, drains NW.; asc. 60 ft. over NE. slope.
37.00	Top small knoll; desc. 10 ft. along N. slope over low clay hills.
40.43	The ¼ sec. cor. of secs. 9 and 16, monumented with a gray sandstone, 10x10x12 ins., in small mound of stone, plainly mkd. ¼.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground, in a mound of stone 3 ft. base to top, with brass cap mkd.
	T30S R11E ¼ S9/S16 1963
	Place original stone N. of iron post.
	Cor. falls on top of small clay hill.
	N. 89°45' W., beginning new measurement.
	Desc. 40 ft. over irregular slope.
9.80	Wash, 3 ft. deep, 30 lks. wide, drains NW.; asc. 80 ft. over E. slope.
14.10	Low ridge, bears N. and S.; desc. 100 ft. over irregular W. slope.
29.80	Swale, drains N.; asc. 40 ft. over E. slope.
34.30	Low spur, slopes N.; desc. 30 ft. over W. slope.
40.50	The cor. of secs. 8, 9, 16 and 17.

CHAINS	
	Land, broken. Soil, gravelly. Timber, none. Undergrowth, black brush and bunch grass.
	N. 0°22' E., bet. secs. 8 and 9.
	Over broken desert land, covered with black brush and scattered bunch grass; desc. 70 ft. along W. slope of small hollow.
17.80	Wash, 4 ft. deep, 10 lks. wide, drains N. 20° E.; asc. 35 ft. along E. slope of small hollow.
32.00	Gravel road, bears N. 50° E. and S. 50° W., leave broken land; desc. over gravelly bench land, sloping NE.
40.05	The ¼ sec. cor. of secs. 8 and 9, monumented with a granite stone, 8x12x18 ins. dimly mkd. "¼."
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, withbrass cap mkd.
	T30S R11E ¼ S8 | S9 1963
	Place original stone N. of iron post.
	A fence cor. of Fairview Ranch bears W. 40 lks. dist., fence bears W. and N.
	N. 0°23' W., beginning new measurement.
	Desc. 45 ft. over gravelly bench land, draining NE.
3.90	Gully, 10 ft. deep, 60 lks. wide, drains N. 60° E.
37.50	Small wash, drains NE.
39.89	The cor. of secs. 4, 5, 8 and 9, monumented with a limestone, 10x12x16 ins., plainly mkd. 5 notches on S. and 4 notches on E. faces.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T30S R11E S5 | S4 S8 | S9 1963
	Place original stone N. of iron post.
	Corner falls in net wire fence, fence bears N. and S.
	Land, broken to rolling. Soil, gravelly. Timber, none. Undergrowth, black brush and scattered bunch grass.

Dependent Resurvey T. [illegible]

CHAINS	
	From the cor. of secs. [illegible], 4, 9 and [illegible].
	N. 89°35' W., bet. secs. 4 and 9
	Over broken desert land, covered with [illegible] and scattered bunch grass, desc. [illegible] ft. over [illegible] slope
.20	Wash, 5 ft. deep, 20 lks. wide, drains NW [illegible] over rolling desert land.
9.10	Wash, 2 ft. deep, 15 lks. wide, drains N.
34.00	Small wash, drains N.
40.26	The ¼ sec. cor. of secs. 4 and 9, [illegible] stone, 4x6x12 ins., plainly [illegible]
	At the cor. point
	Set an iron post, [illegible] the ground, [illegible]
	T[illegible]
	[illegible]
	[illegible]
	Bury original stone [illegible]
	N. 89°47' W., beginning [illegible]
	Asc. [illegible] ft. over rolling desert [illegible]
[illegible].10	Small wash, drains N.
18.60	Wash in small hollow, drains N. [illegible] E. slope.
26.70	Crest of low rise, bears N. and [illegible] gentle NW. slope.
38.50	Small wash, drains NE.
40.14	The [illegible] of secs. 4, 5, 8 and [illegible]
	Land, rolling to slightly [illegible] Soil, gravelly sand. Timber, none. Undergrowth, black brush and scattered [illegible]
	N. [illegible]45' E., bet. secs. 4 and [illegible]
	Over rolling gravelly desert land [illegible] brush and scattered bunch grass, desc. [illegible] ft. over [illegible] slope along fence line.
20.76	Wash, 2 ft. deep, 20 lks. wide, drains NE.
35.83	Fence, bears NE., [illegible] chs. thence NW., [illegible] seep of water.
38.50	Wash with small spring of water, drains NE.
39.92	The ¼ sec. cor. of secs. 4 and 5, determined by a [illegible] fence cor. and mound of stone, no visible mes[illegible]

Dependent Resurvey T. 30 S., R. 11 E.

CHAINS

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T30S R11E
¼
S5|S4
1963

Cor. falls at fence corner; fence bears N., S., and W.

N. 0°41' E., beginning new measurement.

Desc. 65 ft. over gentle N. slope.

.41 Fence, bears SE., 3 chs. thence SW., enclosing small spring.

38.85 The cor. of secs. 4, 5, 32 and 33, on the N. bdy of the Tp., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of T. 29 S., R. 11 E.

Land, rolling.
Soil, gravelly.
Timber, none.
Undergrowth, black brush and scattered bunch grass.

From the cor. of secs. 17, 18, 19 and 20, an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of resurveys in T. 30 S., R. 11 E., in 1919.

N. 0°09' W., bet. secs. 17 and 18.

Over rolling bench land; desc. 145 ft. over gentle NW. slope, along old fence line.

11.80 Wash area, 3 ft. deep, 1 ch. wide, drains NW.

39.98 The ¼ sec. cor. of secs. 17 and 18, monumented with a granite stone, 6x8x12 ins., plainly mkd. "¼."

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.

T30S R11E
¼
S18|S17
1963

Bury original stone N. of iron post.

Cor. falls on old fence line.

N. 0°02' W., beginning new measurement.

Desc. 60 ft. over NW. slope.

9.30 Stock pond in small hollow.

Dependent Resurvey, T. 30 S., R. 11 E.

CHAINS	
20.20	Irrigation ditch, drains NE.; asc. 50 ft. over SE. slope, enter low hills.
31.20	Spur, slopes E.; desc. 20 ft. along E. slope.
34.80	Low ridge, bears NE. and SW.; desc. 95 ft. over NW. slope.
40.13	The cor. of secs. 7, 8, 17 and 18, monumented by a granite stone, 20x12x3, plainly mkd. 4 notches on S. and 5 notches on E. faces.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T30S R11E S7 | S8 S18 | S17 1963
	Place original stone N. of iron post.
	Raise a mound of stone, 2½ ft. base, 2½ ft. high, W. of iron post.
	Land, rolling to hilly. Timber, none. Soil, gravelly. Undergrowth, black brush and scattered bunch grass.
	From the cor. of secs. 8, 9, 16 and 17.
	S. 89°06' W., bet. secs. 8 and 17.
	Over broken desert land, covered with black brush and scattered bunch grass; desc. 15 ft. over W. slope.
2.30	Wash, 5 ft. deep, 40 lks. wide, drains N.; asc. 60 ft. over E. slope.
6.30	Top of round shale hill; desc. 50 ft. over W. slope.
11.60	Wash, 3 ft. deep, 30 lks. wide, drains NE.; asc. 70 ft. over gentle NE. slope.
22.50	Small wash, drains NE.
44.13	The ¼ sec. cor. of secs. 8 and 17, marked by a sandstone, 4x10x20 ins., plainly mkd. "¼".
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.
	T30S R11E ¼ S8 S17 1963
	Bury original stone N. of iron post.

Dependent Resurvey, T. 30 S., R. 11 E.

CHAINS	
	N. 88°28' W., beginning new measurement.
	Asc. 30 ft. over gentle NE. slope.
12.90	Graded dirt road, Hanksville to Sawmill Bench, bears N. 10° E. and S. 10° W.
15.10	Irrigation ditch, drains NE. to Fairview Ranch; asc. along old fence.
29.60	Base low ridge, bears N. and S.; asc. 60 ft. over E. slope.
33.50	Crest same ridge, bears N. and S.; desc. 75 ft. over W. slope.
36.37	The cor. of secs. 7, 8, 17 and 18.
	Land, rolling and broken. Soil, gravelly. Timber, none. Undergrowth, black brush and scattered bunch grass.
	N. 89°52' W., bet. secs. 7 and 18.
	Over broken desert land; asc. 65 ft. along N. slope, over low hills.
7.00	Low spur, slopes N.; desc. 150 ft. over W. slope.
19.30	Bull Cr., in small hollow, drains N., small seep of water; asc. 220 ft. over E. slope.
30.30	Ridge, bears N. and S.; desc. 125 ft. over W. slope.
34.60	Small hollow, drains N.; asc. 115 ft. over E. slope.
38.10	Top of hill, bears N. and S.; desc. 90 ft. over W. slope.
39.83	Point for the ¼ sec. cor. of secs. 7 and 18, at proportionate dist.; there is no remaining evidence of original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone 3 ft. base to top, with brass cap mkd. T30S R11E ¼ S7/S18 1963
	Cor. falls on W. slope at base of hill.
40.80	Small wash, drains N.; asc. 45 ft. over E. slope.
44.20	Low spur, slopes N.; desc. 40 ft.over W. slope.
47.30	Small wash, drains N.; asc. 165 ft. over E. slope.
56.40	Low ridge, bears N. and S.; desc. 75 ft. over W. slope.
71.40	Wash, 5 ft. deep, 20 lks. wide, drains N.; asc. 40 ft. over E. slope.
79.42	The cor. of secs. 7 and 18, on the W. bdy., marked with an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record.

Dependent Resurvey, T. 30 S., R. 11 E.

CHAINS

Land, broken desert.
Soil, sandy clay and rocky.
Timber, none.
Undergrowth, black brush and scattered bunch grass.

From the cor. of secs. 7, 8, 17 and 18.

N. 0°08' E., bet. secs. 7 and 8.

Over broken desert land; desc. 30 ft. along W. slope of small hill.

12.50 Leave hills; desc. 65 ft. over gentle N. slope.

29.80 Wash, 2 ft. deep, 30 lks. wide, drains N. 10° E.; desc. 15 ft. over gentle N. slope.

39.96 The ¼ sec. cor. of secs. 7 and 8, monumented with a sandstone, 6x10x12 ins., plainly mkd. "¼".

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T30S R11E
¼
S7 | S8
1963

Place original stone beside iron post.

Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of iron post.

Cor. falls on W. side of wash; wash drains N. 10° W.

N. 0° 24' E., beginning new measurement.

Desc. 65 ft. over gentle N. slope.

3.80 Wash, 3 ft. deep, 20 lks. wide, drains N. 10° W.

40.03 The cor. of secs. 5, 6, 7 and 8, monumented with a granite stone, 2x4x20 ins., plainly mkd. 5 notches on S. and 5 notches on E. faces.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T30S R11E
S6 | S5
S7 | S8
1963

Bury original stone N. of corner.

Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.

Dependent Resurvey, T. 30 S., R. 11 E.

CHAINS

Land, broken.
Soil, shallow sand, exposed sandstone.
Timber, none.
Undergrowth, shadscale and scattered bunch grass.

From the cor. of secs. 4, 5, 8 and 9.

N. 89°47' W., bet. secs. 5 and 8.

Over rolling land of Fairview Ranch; asc. 30 ft. along gentle N. slope. Corner is located on N. and S. fence line.

40.20 The ¼ sec. cor. of secs. 5 and 8, monumented with a sandstone, 5x12x16 ins., plainly mkd. "¼".

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground, in a mound of stone, 2½ ft. base to top, with brass cap mkd.

T30S R11E
¼ S5/S8
1963

Place original stone N. of iron post.

N. 89°49' W., beginning new measurement.

Continue along rolling N. slope.

1.70 Fence, bears N. and S.

2.00 Graded dirt road, Handsville to Sawmill Basin, bears N. and S.; cont. along gentle N. slope.

39.90 The cor. of secs. 5, 6, 7 and 8.

Land, rolling.
Soil, gravelly.
Timber, none.
Undergrowth, shadscale and bunch grass.

N. 89°55' W., bet. secs. 6 and 7.

Over rolling desert land, covered with shadscale and bunch grass; desc. 15 ft. along gentle N. slope.

15.40 Wash, 5 ft. deep, 20 lks. wide, drains N.; asc. 10 ft. along N. slope.

21.80 Crest of small rise, bears N. and S.; desc. 15 ft. over gentle NW. slope.

23.80 Bull Cr., drains N.; asc. gentle E. slope.

39.99 The ¼ sec. cor. of secs. 6 and 7, marked with a sandstone 5x10x14 ins., plainly mkd. "¼".

At the cor. point

Dependent Resurvey T. 30 S., R. 11 E.

CHAINS	
	Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground, in a mound of stone, 2½ ft. base to top, with brass cap mkd. T30S R11E ¼ S6/S7 1963 Place original stone N. of corner.
	N. 89°49' W., beginning new measurement.
	Asc. 10 ft. over E. slope.
4.20	Crest low rise, bears N. and S.; desc. 20 ft. over W. slope.
7.80	Swale, drains N.; asc. 25 ft. over E. slope.
11.80	Top of round hill; desc. 65 ft. over W. slope.
17.40	Base of same hill, also small wash, drains N.; asc. 55 ft. along broken N. slope, over series of small gullies draining N.
33.16	Top of low hill, bears N. and S.; desc. 35 ft. over W. slope.
37.80	Wash, drains N.; asc. gentle E. slope.
39.54	The cor. of secs. 6 and 7, on the W. bdy., marked by an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record of the resurvey of the W. bdy. in 1919.
	Land, broken. Soil, sand and clay. Timber, none. Undergrowth, shadscale and bunch grass.
	From the cor. of secs. 5, 6, 7 and 8.
	N. 0°23' E., bet. secs. 5 and 6.
	Over rolling to broken desert land; desc. 65 ft. over N. slope.
22.60	Wash, 4 ft. deep, 20 lks. wide, drains NW.
38.60	Wash, 3 ft. deep, 30 lks. wide, drains NW.
39.97	The ¼ sec. cor. of secs. 5 and 6, monumented by a sandstone, 4x6x12 ins., plainly mkd. "¼."
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T30S R11E ¼ S6 | S5 1963

endent Resurvey T. 30 S., R. 11 E.

CHAINS

Bury original stone N. of corner.

Raise a mound of stone, 2½ ft. base, 2½ ft. high, W. of cor.

N. 0°27' E., beginning new measurement.

Desc. 70 ft. over gentle N. slope.

39.50 The cor. of secs. 5, 6, 31 and 32, on the N. bdy., monumented by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of the S. bdy. of T. 29 S., R. 11 E.

Land, slightly broken to rolling.
Soil, sandy with exposed sandstone.
Timber, none.
Undergrowth, shadscale and bunch grass.

General Description

The north ½ of T. 30 S., R. 11 E., covered by this resurvey consists of broken to rolling desert land, located 9 miles south of Hanksville, Utah. The drainage is generally north to northeast. The soil is mostly sand, with exposed patches of sandstone and low sandstone ledges. There is very little timber on this portion of the township. Undergrowth consists of black brush, shadscale and scattered bunch grass.

The only habitation consists of the Fairview Ranch, located in sec. 8.

The main road in the township is the Hanksville to Sawmill Basin road, which bears southward through the west portion of the township. A branch leaves this road at Fairview Ranch and bears eastward across the township. Other roads consist of trail roads used by stockmen.

The elevation of the north ½ of the township varies from about 5000 to 5700 ft. above sea level.

Form 4–680
(June 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
LaVern Griffin	Transit (Crew Chief)
Gail E. Reynolds	Notes
Charles D. Crabb	Front chain
Jay Hyatt	Flagman
Calvin M. Gleave	Cornerman

5. 2

CERTIFICATE OF SURVEY

I, CRAIG P. SYLVESTER, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 21st day of August, 1963, I have surveyed a portion of Township 30 South, Range 11 East,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by me and under my direction and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in a specific manner described in the foregoing field notes.

April 15, 1964
(Date)

(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

RECEIVED FOR APPROVAL
NOV 29 1965

BUREAU OF LAND MANAGEMENT
Washington, D.C.

The foregoing field notes of the dependent resurvey of a portion of Township 30 South, Range 11 East,

executed by Craig P. Sylvester, Cadastral Surveyor,

having been critically examined and found correct, are hereby approved.

JUN 15 1966
(Date)

(Chief, Division of Engineering)

~~CERTIFICATE OF TRANSCRIPT~~

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in

is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)