

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
ORIGINAL
FIELD NOTES

OF THE
DEPENDENT RESURVEY OF
PORTIONS OF
THE EAST BOUNDARY (FIRST GUIDE MERIDIAN EAST),
WEST BOUNDARY AND SUBDIVISIONAL LINES
OF
TOWNSHIP 29 SOUTH, RANGE 4 EAST

Of the Salt Lake Meridian,
In the State of Utah

EXECUTED BY

Craig P. Sylvester Supervisory Cadastral Surveyor

Under special instructions dated March 26, 1976, approved March 29, 1976,

_____, which provided for the surveys included under U.S. Survey/Group
Number 560, and assignment instructions dated April 7, 1976.

Survey commenced May 11, 1976

Survey completed June 29, 1976

INDEX DIAGRAM

Township 29 S., Range 4 E.

7	6 31	5	4 24	3 21	2 1	
6	7 29	30 8 28	23 9 23	20 10 18	16 11 16	12
4	18 26	27 17 25	22 16	18 15 17	15 14 14	12 13 11
	19	20	21	22 13	13 23 9	10 24 3
	30	29	28	27	26	8 25 2
	31	32	33	34	35	8 36

Township 29 South, Range 4 East, Salt Lake Meridian, Utah

CHAINS

The south boundary was surveyed by A. D. Ferron in 1883, and the east 1 mile resurveyed by John P. Walker in 1904. The east boundary was surveyed by A. D. Ferron in 1883, and the south 3 miles resurveyed by Adolphe Jessen in 1891. The north boundary was surveyed by A. D. Ferron in 1883, the east 5½ miles were resurveyed by H. D. Heist in 1902, the north boundaries of secs. 2, 3, 4 and 5 were resurveyed by Elliot Bird in 1920, and the west 1 mile was resurveyed by Elliot Bird and E. Eliason in 1934-35. The north 2½ miles of the west boundary were surveyed by J. G. Burrill in 1876, and the south 3½ miles surveyed, and the north ½ mile between secs. 13 and 18 resurveyed by A. D. Ferron in 1883. The subdivisional lines, with the exception of secs. 2, 3, 4 and 5, were surveyed by A. D. Ferron in 1883, the subdivisional lines of secs. 2, 3, 4 and 5 were surveyed, and a portion of the subdivisional lines resurveyed by Elliot Bird in 1920. The subdivisional lines along the Aquarius Forest boundary were resurveyed by J. P. Walker in 1904. A number of corners were remonumented by Ferrel D. Reynolds, Supervisory Survey Technician, in 1969, under the remonumentation cooperative agreement between BLM and the U.S. Forest Service.

The following field notes are those of a dependent resurvey of the east boundary (First Guide Meridian East) between secs. 19-24 and 25-30, the north 3 miles of the west boundary, and a portion of the subdivisional lines of Township 29 South, Range 4 East, Salt Lake Meridian, Utah.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group 560, Utah, dated March 26, 1976.

The directions of the lines of this survey were determined by reference to true meridians established on line by hour angle observations on Polaris. They were carried forward by sustained angulation, being supplemented by numerous other observations on Polaris taken throughout the progress of the survey.

Measurements were determined by electronic means along survey lines where accessible. Distances to topography on lines run by traverse due to rough terrain, timber and private property are approximately as scaled from U.S.G.S. topographic sheets.

Before restoring lost corners, the lines of the original survey were retraced and a diligent search made for any evidence of the original corners. The rules of proportionate measurement were applied to ascertain the position of the lost corner after every reasonable possibility of finding direct evidence of the corner had been exhausted.

The geographic position for the southeast corner of sec. 25, as determined by ties to United States Geological Survey triangulation station "Teasdale" located in sec. 18, T. 29 S., R. 4 E., is as follows.

Latitude 38°15'07.1" N. Longitude 111°24'48.3" W.

The magnetic declination was read at a number of stations throughout the township and the average of the several readings was found to be 16°00' E.

Dependent Resurvey of the First Guide Meridian East,
on a Portion of the East Boundary of T. 29 S., R. 4 E.,
Salt Lake Meridian, Utah

CHAINS

Dependent Resurvey of the First Guide Meridian East,
on a Portion of the East Boundary of T. 29 S., R. 4 E.,
Salt Lake Meridian, Utah

(Restoring the 1883 survey by A. D. Ferron and the
1891 resurvey by Adolphe Jessen)

Beginning at the cor. of secs. 25, 30, 31 and 36, on the
E. bdy. of the township, determined by a sandstone,
12 x 10 x 6 ins., in a mound of stone, dimly mkd. 1 notch
on S and 5 notches on N edge.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 29 S
R 4 E R 5 E

S 25 | S 30
S 36 | S 31

1976

Raise a mound of stone, 2 ft. base, 2 ft. high, W of cor.

Deposit the mkd. stone alongside the iron post.

N. 0°09' E., bet. secs. 25 and 30.

Over sandy land; asc. gentle S slope.

- 9.50 Enter scattering juniper and pinon growth.
- 18.70 Low spur, slopes E; desc. NE slope.
- 36.20 Small draw, drains W; leave scattering timber.
- 38.40 Graded gravel road, bears NW to Teasdale and curves SE.
to Grover.
- 39.65 The ¼ sec. cor. of secs. 25 and 30, determined at record
course and distance from the original bearing tree

A pinon, 10 ins. diam., bears S. 40° E., 44 lks.
dist., mkd. ¼ SBT.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 29 S
R 4 E R 5 E

¼
|
S 25 | S 30

1976

Dependent Resurvey of the First Guide Meridian East,
on a Portion of the East Boundary of T. 29 S., R. 4 E.,
Salt Lake Meridian, Utah

CHAINS

Cor. is located on gentle S slope of small rise.

N. 0°12' E., beginning new measurement.

Desc. general NW slope.

39.85 The cor. of secs. 19, 24, 25 and 30, monumented with a sandstone, 15 x 6 x 5 ins., plainly mkd. 2 notches on S and 4 notches on N edge.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.

T 29 S
R 4 E R 5 E

S 24 | S 19
S 25 | S 30

1976

Deposit the mkd. stone alongside the iron post.

Cor. is located on NW slope.

N. 0°16' W., bet. secs. 19 and 24.

Over broken land, through scattering juniper and pinon; desc. gentle NW slope.

12.10 Donkey Creek, drains NE; asc. gentle SE slope.

38.60 Graded gravel road, bears NE and SW; over level land.

39.97 The ¼ sec. cor. of secs. 19 and 24, monumented with a basalt stone, 24 x 12 x 12 ins., plainly mkd. ¼ on W face.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.

T 29 S
R 4 E R 5 E

¼
|
S 24 | S 19
|

1976

Deposit the mkd. stone alongside the iron post.

N. 0°02' E., beginning new measurement.

Over level land.

9.00 Graded gravel road, bears NW and SE.

6
6

Dependent Resurvey of the First Guide Meridian East,
on a Portion of the East Boundary of T. 29 S., R. 4 E.,
Salt Lake Meridian, Utah

CHAINS	
11.00	Same road, bears NE and SW.
11.90	Birch Creek, drains E.
15.30	Fremont River, 2 ft. deep, 20 lks. wide, flows S. 80° E.
16.90	Same road, bears NW and SE; asc. ledges facing SW.
21.40	Low ridge, bears N. 75° W. and S. 75° E.; thence along broken and ledgy W slope.
39.78	The cor. of secs. 13, 18, 19 and 24, monumented with a sandstone, 18 x 18 x 18 ins., in a mound of stone, mkd. 3 notches on N and S edges, from which an original bearing tree A pinon, 6 ins. diam., bears N. 14°10' W., 23 lks. dist., mkd. T29S R4E S13. (Record, N. 35° W., 22 lks. dist.) At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base to top of brass cap, mkd. T 29 S R 4 E R 5 E S 13 S 18 S 24 S 19 1976 Deposit the mkd. stone alongside the iron post.

Dependent Resurvey of a Portion of the West Boundary of
T. 29 S., R. 4 E., Salt Lake Meridian, Utah

(Restoring the 1883 survey by A. D. Ferron)

From the cor. of secs. 18 and 19, T. 29 S., R. 4 E., on the W. bdy. of the Tp., monumented with an iron post, 3 ins. diam., extending 10 ins. above ground, with brass cap mkd. as described in the official record of the 1904 resurvey.

from which

A pinon, 10 ins. diam., bears N. 32°30' E., 46 lks. dist., mkd. T29S R4E S18 BT.

A pinon, 12 ins. diam., bears S. 83° E., 82 lks. dist., mkd. RES T29S R4E S19 BT.

N. 0°33' W., bet. secs. 13 and 18.

Dependent Resurvey of a Portion of the West Boundary of
T. 29 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	Over broken mountain land, covered with scattering pinon and juniper; desc. along ledgy W slope.
9.50	Spur, slopes W; desc. NW slope.
12.80	Draw, drains W; asc. broken and steep S slope.
15.20	Spur, slopes W; desc. NW slope.
18.80	Draw, drains W; asc. along broken W slope.
35.70	Small draw, W; continue along W slope.
39.96	The $\frac{1}{4}$ sec. cor. of secs. 13 and 18, monumented with a shale rock, 12 x 10 x 6 ins., marks have weathered away, from which the original bearing tree A pinon, 12 ins. diam., bears N. 45° E., 16 lks. dist., mkd. $\frac{1}{4}$ SBT. At the corner point Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone and dirt, 4 ft. base to top of brass cap, mkd. <div style="text-align: center;"> <p>T 29 S R 3 E R 4 E $\frac{1}{4}$ S 13 S 18 1976</p> </div> Deposit the shale rock alongside the iron post. <div style="text-align: center;"> <p>(Restoring the 1876 survey by J. G. Burrill and the 1883 resurvey by A. D. Ferron)</p> </div> N. 0°07' W., beginning new measurement. Asc. along broken W slope.
5.20	High spur, slopes N. 85° W.; desc. over broken N slope.
15.00	Base of steep descent, bears E and SW; desc. gentle N slope, in valley, leave timber.
26.00	Rise, bears NE and SW; desc. gentle N slope.
39.45	Dirt road, bears NE and SW.
39.75	The cor. of secs. 7, 12, 13 and 18, monumented with a sandstone, 20 x 12 x 12 ins., mkd. 2 notches on N and 4 notches on S edge. Blue steel fence post alongside cor. At the corner point Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the West Boundary of
T. 29 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	<p style="text-align: center;">T 29 S R 3 E R 4 E</p> <p style="text-align: center;">S 12 S 7 S 13 S 18</p> <p style="text-align: center;">1976</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <p>A fence cor. bears N. 70° W., 7½ lks. dist., fences bear N, W and E.</p>
	<p style="text-align: center;">(Restoring the 1876 survey by J. G. Burrill)</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°02' E., bet. secs. 7 and 12.</p> <p>Over brush covered bench land; desc. gentle N slope.</p>
0.06	Fence, bears E and W; thence along W side of N and S fence.
13.00	Enter farm land, leave fence, which bears E.
40.01	Point for the ¼ sec. cor. of secs. 7 and 12, at proportionate distance, falls in farm and was not monumented. There is no evidence of the original corner.
44.82	Fence, bears E and W.
44.84	Point selected for the witness ¼ sec. cor. of secs. 7 and 12.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">W C R 3 E R 4 E ¼ S 12 S 7 ↓ 1976</p>
	Across roadway.
45.49	Center of hard surface road, bears E and W.
46.16	Fence line, bears E and W; thence over grass pasture land of Bicknell Bottoms.
58.60	Fremont River, 20 lks. wide, 2 ft. deep, flows E irregularly; asc. gentle S slope, over pasture land.
80.02	Point for the cor. of secs. 1, 6, 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the West Boundary of
T. 29 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS

T 29 S
R 3 E R 4 E

S 1	S 6
S 12	S 7

1976

Set a cedar post, 6 ins. diam., 4 ft. high, alongside the iron post.

Cor. is located in native grass pasture.

N. 0°02' E., bet. secs. 1 and 6.

Over grass pasture and farm land.

- 21.40 Fence, parallel highway.
- 23.76 Center line of hard surface State Highway No. 24, on curve from SE to NW.
- 25.53 Fence, parallel highway; asc. along W slope of knoll, along N and S fence line, leave farms.
- 40.01 The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, determined latitudinally by fence line to west, and on line between sec. cors. The original stone, a black volcanic rock, 16 x 12 x 10 ins., plainly mkd. $\frac{1}{4}$ was found lying loose and was not used to determine the corner location.

At the corner point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T 29 S
R 3 E R 4 E

$\frac{1}{4}$
S 1 S 6

1976

Deposit the mkd. stone alongside the iron post.

N. 0°02' E., beginning new measurement.

Asc. along W slope of knoll.

- 5.40 Dirt road, bears SW and NE, through saddle in knoll.
- 35.30 Abandoned hard surface highway, bears NW and SE.
- 39.97 The cor. of Tps. 28 and 29 S., Rs. 3 and 4 E., monumented with an iron post, 3 ins. diam., extending 10 ins. above ground, in a scattering mound of stone, mkd. as described in the official record of the 1934-35 resurvey.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 29 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS		
	<p>Dependent Resurvey of a Portion of the Subdivisional Lines of T. 29 S., R. 4 E., Salt Lake Meridian, Utah (Restoring the 1883 survey by A. D. Ferron)</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp.</p> <p>S. 88°07' W., bet. secs. 25 and 36.</p> <p>Over broken valley land, draining N.</p> <p>34.90 Donkey Creek, dry, drains N. 10° E. irregularly; asc. gentle NE slope.</p> <p>40.91 The ¼ sec. cor. of secs. 25 and 36, monumented with a basalt stone, 12 x 9 x 6 ins., plainly mkd. ¼ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 29 S R 4 E</p> <p style="text-align: center;">¼ S 25 S 36</p> <p style="text-align: center;">1976</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 2 ft. base, 2 ft. high, N of cor.</p> <hr/> <p>S. 88°17' W., beginning new measurement.</p> <p>Asc. NE slope.</p> <p>8.00 Enter scattering juniper and pinon growth.</p> <p>40.11 The cor. of secs. 25, 26, 35 and 36, monumented with an iron post, 4 ins. diam., extending 20 ins. above ground, in a mound of stone, with brass cap mkd. as described in the 1904 resurvey.</p> <p>from which the 1904 bearing trees</p> <p style="padding-left: 40px;">A cedar, 6 ins. diam., bears N. 78° E., 53 lks. dist., mkd. T29S R4E S25 BT.</p> <p style="padding-left: 40px;">A cedar, 12 ins. diam., bears S. 54°15' W., 36 lks. dist., mkd. RES T29S R4E S35 BT.</p> <p style="padding-left: 40px;">A pinon, 10 ins. diam., bears N. 11° W., 33 lks. dist., mkd. T29S R4E S26 BT.</p>	
	<p>N. 0°44' E., bet. secs. 25 and 26.</p> <p>Over broken land, covered with scattering juniper and pinon growth; desc. NE slope.</p>	

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 29 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS							
40.63	<p>The ¼ sec. cor. of secs. 25 and 26, monumented with an iron post, 2½ ins. diam., extending 6 ins. above ground, mkd. as described in the official record of the 1969 remonumentation.</p> <p style="text-align: center;">_____</p> <p>N. 0°04' E., beginning new measurement.</p> <p>Desc. gentle NE slope, leave pinon and juniper.</p>						
40.73	<p>The cor. of secs. 23, 24, 25 and 26, monumented with a plastic pipe, 3 ins. diam., set in a mound of rock and concrete. This position is recognized as the cor. by adjacent landowners, and is accepted as the best available evidence of the original corner position.</p> <p>At the corner point</p> <p>Drive an iron post, 30 ins. long, 2½ ins. diam., flush with top of plastic pipe, with brass cap mkd.</p> <p style="text-align: center;">T 29 S R 4 E</p> <p style="text-align: center;"> <table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 2px;">S 23</td> <td style="padding: 2px;"> </td> <td style="padding: 2px;">S 24</td> </tr> <tr> <td style="padding: 2px;">S 26</td> <td style="padding: 2px;"> </td> <td style="padding: 2px;">S 25</td> </tr> </table> </p> <p style="text-align: center;">1976</p>	S 23		S 24	S 26		S 25
S 23		S 24					
S 26		S 25					
11.00	<p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp.</p> <p>S. 89°30' W., bet. secs. 24 and 25.</p> <p>Over rolling land, covered with brush; desc. gentle NW slope.</p>						
21.10	<p>Graded dirt road, bears N. 53° E. and S. 53° W.</p>						
38.30	<p>Graded dirt road, bears N. 46° W. to Teasdale, and S. 46° E. to Grover.</p>						
38.93	<p>Point selected for the witness ¼ sec. cor. of secs. 24 and 25.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">W C</p> <p style="text-align: center;">T 29 S R 4 E</p> <p style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 2px;">¼ ←</td> <td style="padding: 2px;">S 24</td> </tr> <tr> <td></td> <td style="padding: 2px;">S 25</td> </tr> </table> </p> <p style="text-align: center;">1976</p>	¼ ←	S 24		S 25		
¼ ←	S 24						
	S 25						
38.97	<p>Raise a mound of stone, 2 ft. base, 1½ ft. high, N of cor.</p> <p>Fence, parallels road, enter grain field.</p>						

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 29 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
40.33	Point for the ¼ sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner. Corner point falls in grain field and was not monumented.
47.20	Leave fields; asc. gentle NE slope, enter scattering juniper and pinon growth.
62.30	Low spur, slopes N; desc. along gentle N slope.
80.66	The cor. of secs. 23, 24, 25 and 26.
N. 1°21' E., bet. secs. 23 and 24.	
Over rolling valley land, draining E.	
29.50	Birch Creek, small stream of water, drains E irregularly; asc. SE slope.
31.50	Graded dirt road, bears NW to Teasdale and SE to Grover.
40.65	The ¼ sec. cor. of secs. 23 and 24, monumented with a trachyte stone, 14 x 10 x 6 ins., plainly mkd. ¼ on W face.
At the corner point	
Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.	
<p style="text-align: center;">T 29 S R 4 E</p> <p style="text-align: center;"> ½</p> <p style="text-align: center;"> </p> <p style="text-align: center;">S 23 S 24</p> <p style="text-align: center;"> </p> <p style="text-align: center;"> 1976</p>	
Deposit the mkd. stone alongside the iron post.	
N. 0°03' E., beginning new measurement.	
Asc. SE slope, over broken land, enter juniper and pinon.	
24.50	Crest of low rim, bears E and W irregularly; thence over bench, through thick juniper and pinon.
40.03	The cor. of secs. 13, 14, 23 and 24, monumented with a basalt stone, 16 x 15 x 10 ins., mkd. 1 notch on E and 3 notches on S edge.
At the corner point	
Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.	

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 29 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS

T 29 S R 4 E

S 14	S 13
S 23	S 24

1976

from which

A pinon, 8 ins. diam., bears N. $11^{\circ}20'$ E., 53 lks.
dist., mkd. S13 BT.

A pinon, 14 ins. diam., bears S. 20° W., $81\frac{1}{2}$ lks.
dist., mkd. T29S R4E S23 BT.

A pinon, 10 ins. diam., bears N. $79^{\circ}20'$ W., 59 lks.
dist., mkd. T29S R4E S14 BT.

Deposit the mkd. stone alongside the iron post.

From the cor. of secs. 13, 18, 19 and 24, on the E. bdy.
of the Tp.

N. $89^{\circ}52'$ W., bet. secs. 13 and 24.

Over broken land, through juniper and pinon; desc. W
slope.

- 0.60 Head of draw, drains S. 80° W.; desc. along S slope.
- 11.00 Spur, slopes S; desc. over W slope.
- 13.70 Gravel road, bears N and S.
- 19.60 Fremont River, 20 lks. wide, 2 ft. deep, flows S. 10° E.;
asc. over gentle E slope.
- 39.55 Irrigation canal, 30 lks. wide, flows S. 25° E.
- 39.74 Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 24, at propor-
tionate distance; there is no remaining evidence of the
original corner.
- Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins.
in the ground to bedrock, in a mound of stone, 4 ft. base
to top of brass cap, mkd.

T 29 S R 4 E

$\frac{1}{4}$	S 13
	S 24

1976

Asc. gentle E slope.

- 55.00 Base of ascent, bears NW and SE; asc. over broken NE
slope.
- 79.24 Crest of rim, bears N and S irregularly; thence over bench.
- 79.48 The cor. of secs. 13, 14, 23 and 24.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 29 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	<p>N. 0°01' E., bet. secs. 13 and 14.</p> <p>Over broken land on bench, through pinon and juniper; along W side of rim, on bench.</p>
5.10	Head of small cove in rim, drains E; continue over bench.
16.40	Top of ascent on bench, bears E and W.
19.20	Rim, bears NW and SE irregularly; desc. steep and ledgy NE slope.
37.00	Base of steep descent, bears NW and SE irregularly; desc. gentle NE slope, in valley.
39.57	<p>The $\frac{1}{4}$ sec. cor. of secs. 13 and 14, monumented with an iron post, $2\frac{1}{2}$ ins. diam., protruding 6 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> $\frac{1}{4}$ S 14 S 13 USFS S3152 1969 </div> <p>This cor. was remonumented by an employee of the U.S. Forest Service, a registered land surveyor, in 1969, and is accepted as the best available evidence of the original corner position.</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>N. 0°08' E., beginning new measurement.</p> <p>Desc. gentle NE slope.</p>
11.80	Canal, 20 lks. wide, 3 ft. deep, flows S. 32° E.
16.60	Fremont River, 24 lks. wide, 2 ft. deep, flows S. 70° E. from NW; asc. gentle S slope.
33.00	Gravel road, bears S. 31° E. and N; thence up road.
40.08	<p>Point for the cor. of secs. 11, 12, 13, and 14, falls in cattle guard established at record distance from the witness cor. and on a line projected from the $\frac{1}{4}$ sec. cor. of secs. 11 and 14.</p> <p>From this point, the witness cor. of secs. 11, 12, 13 and 14, bears N. 89°55' W., 72.4 lks. dist., monumented with an iron post, $2\frac{1}{2}$ ins. diam., protruding 6 ins. above ground and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> USFS T 29 S R 4 E WC $\frac{S 11 S 12}{S 14 S 13}$ 47.8 FT. EAST  1969 S3152 </div>

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 29 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS

This witness cor. was established by an employee of the U.S. Forest Service, a registered land surveyor, in 1969, and is accepted as the best available evidence of the original cor. position.

From the cor. of secs. 23, 24, 25 and 26.

N. 88°34' W., bet. secs. 23 and 26.

Over rolling land in valley; desc. gentle E slope.

40.11 The $\frac{1}{4}$ sec. cor. of secs. 23 and 26, monumented with an iron post, 2 $\frac{1}{2}$ ins. diam., extending 6 ins. above ground, mkd. as described in the official record of the 1969 remonumentation.

S. 87°39' W., beginning new measurement.

Continue over level land, through fields.

13.00 Old ranch house and corrals.

19.50 Birch Creek, small stream of water, drains N. 25° E.

30.64 Fence, bears N and S.

38.04 The cor. of secs. 22, 23, 26 and 27, monumented with a red sandstone, 30 x 8 x 6 ins., mks. have weathered away; this stone is recognized by the adjacent landowners as the corner, and is accepted as the best available evidence of the original corner position.

At the corner point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 4 E

S 22		S 23
S 27		S 26

1976

Deposit the unmkd. stone and a steel fence post alongside the corner.

Corner is located in field.

N. 1°12' W., bet. secs. 22 and 23.

Over level land, across grain field.

21.70 Field road, bears E and W.

30.10 Graded gravel road, bears N. 75° E. and S. 66° W.; enter scattering juniper and pinon. Asc. gentle SE slope.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 29 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS						
42.32	<p>The $\frac{1}{4}$ sec. cor. of secs. 22 and 23, monumented with an iron post, $2\frac{1}{2}$ ins. diam., extending 6 ins. above ground, mkd. as described in the official record of the 1969 remonumentation.</p>					
	<p>N. $3^{\circ}47'$ E., beginning new measurement. Asc. SE slope, through juniper and pinon.</p>					
13.00	<p>Spur, slopes NE from W; desc. NW slope.</p>					
18.50	<p>Base of spur, bears NE and SW; thence over nearly level land, through greasewood, leave timber.</p>					
38.52	<p>The cor. of secs. 14, 15, 22 and 23, monumented with a basalt stone, 12 x 8 x 6 ins., mkd. 3 notches on S and 2 notches on E edge.</p>					
	<p>At the corner point Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>					
	<p style="text-align: center;">T 29 S R 4 E <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 15</td> <td style="padding: 0 5px;">S 14</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 22</td> <td style="padding: 0 5px;">S 23</td> </tr> </table> </p>	S 15	S 14	S 22	S 23	
S 15	S 14					
S 22	S 23					
	<p style="text-align: center;">1976</p> <p>Deposit the mkd. stone alongside the iron post. Place 1 boulder alongside the iron post.</p>					
	<p>From the cor. of secs. 13, 14, 23 and 24. S. $89^{\circ}59'$ W., bet. secs. 14 and 23.</p>					
	<p>Over rolling land on bench top, through juniper and pinon; asc. gentle E slope.</p>					
27.20	<p>Low rim on bench, bears NW and SE; desc. SW slope.</p>					
40.37	<p>The $\frac{1}{4}$ sec. cor. of secs. 14 and 23, monumented with a basalt stone, 18 x 10 x 6 ins., plainly mkd. $\frac{1}{4}$ on N face.</p>					
	<p>At the corner point Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.</p>					
	<p style="text-align: center;">T 29 S R 4 E <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 0 5px;">$\frac{1}{4}$</td> <td style="border-right: 1px solid black; padding: 0 5px;">S 14</td> <td style="padding: 0 5px;">S 23</td> </tr> </table> </p>	$\frac{1}{4}$	S 14	S 23		
$\frac{1}{4}$	S 14	S 23				
	<p style="text-align: center;">1976</p> <p>Deposit the mkd. stone alongside the iron post.</p>					

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 29 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	<p>S. 89°04' W., beginning new measurement.</p> <p>Desc. SW slope, through juniper and pinon.</p>
9.50	Head of small draw, drains W; thence down draw.
22.50	Enter nearly level valley land covered with greasewood; leave timber.
37.09	The cor. of secs. 14, 15, 22 and 23.
	<p>N. 0°10' E., bet. secs. 14 and 15.</p> <p>Over nearly level land, covered with greasewood.</p>
7.00	Wash, 30 lks. wide, 20 ft. deep, drains NE.
31.10	Boulder Creek, small stream of water, flows NE; asc. gentle E slope.
40.07	<p>The ¼ sec. cor. of secs. 14 and 15, monumented with a granite stone, 10 x 10 x 10 ins., plainly mkd. ¼ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 29 S R 4 E</p> <p> </p> <p> ¼</p> <p> </p> <p>S 15 S 14</p> <p> </p> <p> 1976</p> </div> <p>Deposit the mkd. stone alongside the iron post, no other accessories available.</p>
	<p>N. 0°28' W., beginning new measurement.</p> <p>Along gentle E slope, on bench.</p>
28.10	Crest small rim, bears E and W.
30.40	Base of same rim, bears E and W; thence over nearly level land in valley.
40.33	<p>The cor. of secs. 10, 11, 14 and 15, determined by fence corner; fences bear S, E and W. This position is harmoniously related to existing original cors., has long been recognized as the cor. by adjacent landowners, and is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 29 S R 4 E</p> <p> </p> <p>S 10 S 11</p> <p>S 15 S 14</p> <p> </p> <p> 1976</p> </div>

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 29 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	<p>From the true point for the cor. of secs. 11, 12, 13 and 14.</p>
	<p>N. 89°55' W., bet. secs. 11 and 14.</p>
	<p>Over rolling valley land.</p>
0.724	<p>The witness cor. of secs. 11, 12, 13 and 14, previously described.</p>
39.55	<p>Wash, drains S.</p>
39.66	<p>Point for the ¼ sec. cor. of secs. 11 and 14, determined longitudinally by old N and S fence line and latitudinally on line between found cors.</p>
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 4 ft. base to top of brass cap, mkd.</p>
	<p style="text-align: center;">R 29 S R 4 E</p>
	<p style="text-align: center;">¼ $\frac{S 11}{S 14}$</p>
	<p style="text-align: center;">1976</p>
	<p>Corner is located on sloping W bank of wash.</p>
	<p>N. 89°55' W., beginning new measurement.</p>
	<p>Over nearly level land.</p>
17.70	<p>Fremont River, 25 lks. wide, 2 ft. deep, flows SE irregularly; continue over nearly level land.</p>
38.12	<p>The cor. of secs. 10, 11, 14 and 15.</p>
	<p>N. 1°16' W., bet. secs. 10 and 11.</p>
	<p>Over valley land; desc. gentle N slope, through farms.</p>
35.90	<p>Center of new Utah Highway No. 24, on bridge over Fremont River, bears E and W; thence up river.</p>
40.05	<p>Abandoned highway, bears E and W.</p>
40.35	<p>Point for the ¼ sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original corner.</p>
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 29 S R 4 E</p>
	<p style="text-align: center;">¼ S 10 S 11</p>
	<p style="text-align: center;">1976</p>

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 29 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS

from which

An X, on concrete abutment of old highway bridge, bears S. 18° E., 10 lks. dist.

Cor. is located on E bank of Fremont River, 5 ft. E of water line.

Continue up river bottom, through dense willows and swamp land.

54.00 Fremont River, 20 lks. wide, 2 ft. deep, drains easterly.

62.00 Leave river bottom; asc. gentle S slope.

80.70 The cor. of secs. 2, 3, 10 and 11, determined by a mound of stone, This position is recognized by local landowners as the original corner position, and is accepted as the best available evidence of the original cor. position.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.

T 29 S R 4 E

S 3 | S 2
S 10 | S 11

1976

From the cor. of secs. 14, 15, 22 and 23.

S. 89°55' W., bet. secs. 15 and 22.

Over nearly level valley land, across scattering farms and brush pastures.

17.50 Boulder Creek, drains N. 10° E.

41.05 The ¼ sec. cor. of secs. 15 and 22, determined by fence corner, fences bear S, E and N, 27 lks. dist. thence W. This position is harmoniously related to existing original cors., has long been recognized as the cor. by adjacent landowners, and is accepted as the best available evidence of the original cor. position.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T 29 S R 4 E

¼ S 15
S 22

1976

S. 89°59' W., beginning new measurement.

Continue over farm land.

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 29 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
40.44	<p>Point for the cor. of secs. 15, 16, 21 and 22, determined longitudinally by N and S pole fence, and latitudinally by proportionate distance.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 29 S R 4 E</p> <p style="text-align: center;">S 16 S 15 S 21 S 22</p> <p style="text-align: center;">1976</p> <p>Cor. is located on N and S pole fence line.</p> <p>From this cor., the ¼ sec. cor. of secs. 21 and 22, bears S. 0°13' W., 39.68 chs. dist., monumented with a sandstone, 20 x 15 x 8 ins., firmly set and plainly mkd. ¼ on W face, bearing tree has been destroyed.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 29 S R 4 E</p> <p style="text-align: center;">¼ S 21 S 22 1976</p> <p>Deposit the mkd. stone alongside the iron post.</p>
4.90	<p>N. 0°36' E., bet. secs. 15 and 16.</p> <p>Over farm land, along N and S pole fence.</p>
39.68	<p>Leave pole fence, which bears NW; enter farms, along N and S wire fence line.</p> <p>The ¼ sec. cor. of secs. 15 and 16, monumented with a basalt stone, 10 x 8 x 6 ins., firmly set and plainly mkd. ¼ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 29 S R 4 E</p> <p style="text-align: center;">¼ S 16 S 15 1976</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Cor. is located 2 lks. E of fence corner, fences bear N, S and W.</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 29 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS

N. 0°12' E., beginning new measurement.

Over valley land, along N and S fence line.

27.43 Hard surface road, bears S. 55°55' W. to Teasdale and
N. 55°55' E. to State Highway No. 24.

40.38 The cor. of secs. 9, 10, 15 and 16, monumented with a
basalt stone, 14 x 10 x 6 ins., mkd. 4 notches on S and
3 notches on E edge.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins.
in the ground to bedrock, in a mound of stone, 4 ft. base
to top of brass cap, mkd.

T 29 S R 4 E

S 9	S 10
S 16	S 15

1976

Deposit the mkd. stone alongside the iron post.

Cor. is in line with fences extending S and W.

From the cor. of secs. 10, 11, 14 and 15.

S. 89°48' W., bet. secs. 10 and 15.

Over valley land, through scattering patches of juniper
and pinon, across small farms and pastures, along E and
W fence line.

25.50 Foot of small bench, bears NW and SE; asc. NE slope,
leave fence.

30.20 Crest of same bench, bears NW and SE; thence over rocky
bench, through scattering juniper and pinon.

39.97 The ¼ sec. cor. of secs. 10 and 15, monumented with a
lava stone, 12 x 8 x 6 ins., firmly set and plainly mkd.
¼ on N face.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 29 S R 4 E

¼	S 10	S 15
	S 15	

1976

Deposit the mkd. stone alongside the iron post.

Raise a mound of stone, 2 ft. base, 2 ft. high, N of cor.

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 29 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	S. 89°39' W., beginning new measurement.
	Continue over rocky bench, through scattering juniper and pinon.
21.10	Hard surface road, bears N. 29°30' E. to State Highway No. 24 and S. 29°30' W. to Teasdale.
40.69	The cor. of secs. 9, 10, 15 and 16.
	N. 0°29' W., bet. secs. 9 and 10.
	Over rocky bench land, through very scattered juniper and pinon.
34.75	Center line of hard surface highway, U-24, bears N. 89°16' E. and S. 89°16' W.
39.94	Abandoned hard surface highway, bears N. 89°13' E. and S. 89°13' W.
40.65	Point for the ¼ sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> <p>T 29 S R 4 E</p> <p>¼</p> <p> </p> <p>S 9 S 10</p> <p> </p> <p>1976</p> </div>
	Raise a mound of stone, 2 ft. base, 2 ft. high, W of cor.
73.90	Small rim of bench, bears E and W irregularly; desc. N slope.
75.00	Base of same rim, bears E and W irregularly; thence over river bottom land, through willows and swamp.
80.00	Fremont River, 20 lks. wide, 2 ft. deep, meandering SE through swampy bottom land.
81.30	The cor. of secs. 3, 4, 9 and 10, monumented with a basalt stone, 10 x 10 x 10 ins., firmly set and plainly mkd. 5 notches on S and 3 notches on E edge.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> <p>T 29 S R 4 E</p> <p>S 4 S 3</p> <p>S 9 S 10</p> <p>1976</p> </div>
	Deposit the mkd. stone alongside the iron post.
	Set wood post, 2 x 6 ins., 5 ft. high, alongside corner.

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 29 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	Cor. is located 13 lks. E of river edge.
	(Restoring the 1883 survey by A. D. Ferron and the 1920 resurvey by Elliot Bird)
	From the cor. of secs. 2, 3, 10 and 11.
	N. 89°43' W., bet. secs. 3 and 10.
	Over broken land, draining S.
26.00	Low spur, slopes S; desc. SW slope.
38.60	Draw, drains S irregularly; thence along S slope.
39.67	The ¼ sec. cor. of secs. 3 and 10, monumented with a sandstone, 18 x 10 x 8 ins., firmly set in a mound of stone and dimly mkd. ¼ on N face, a cedar post with forest signs nailed to it, and S¼S3 scribed on post, alongside stone.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T 29 S R 4 E
	¼ $\frac{S 3}{S 10}$
	1976
	Place the mkd. stone alongside the iron post.
	S. 89°57' W., beginning new measurement.
	Continue along broken S slope.
28.50	Flume to carry water across river bottom, bears NE and SW; thence over river bottom.
39.87	The cor. of secs. 3, 4, 9 and 10.
	(Restoring the 1883 survey by A. D. Ferron)
	From the cor. of secs. 16, 17, 20 and 21, monumented with a sandstone, 12 x 10 x 6 ins., in a scattered mound of stone, mkd. 3 notches on S and 4 notches on E edge, from which the original bearing trees
	A pinon, 14 ins. diam., bears N. 48½° E., 78 lks. dist., mkd. T29S R4E S16 BT RES. (Record, N. 52½° E., 84 lks. dist.)
	A pinon, 10 ins. diam., bears S. 36° E., 96 lks. dist., mkd. T29S R4E S21 BT. (Record, S. 39° E., 102 lks. dist.)

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 29 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS

A yellow pine, 14 ins. diam., bears S. 11° W., 84 lks. dist., mkd. RES T29S R4E S20 BT. (Record, S. 60° W.)

A yellow pine, 16 ins. diam., bears N. 50½° W., 85 lks. dist., mkd. T29S R4E S17 BT. (Record, N. 48° W., 78 lks. dist.)

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.

T 29 S R 4 E

S 17		S 16
S 20		S 21

1976

Place the mkd. stone, in mound, alongside the iron post.

From this cor., a U.S. Forest Service Boundary Post No. 96 bears South, 5 lks. dist., (record) monumented with an iron post, 3 ins. diam., in a mound of stone, mkd. as described in the resurvey of the Aquarius Forest boundary by J. P. Walker in 1904. This cor. was also designated by J. P. Walker as a witness cor. for the cor. of secs. 16, 17, 20 and 21.

N. 0°26' E., bet. secs. 16 and 17.

Over broken land, through juniper and pinon; asc. SE slope of small spur.

- 0.70 Low spur, slopes NE; thence over rocky bench.
- 13.00 Dirt trail road, bears E and W.
- 17.90 Bullberry Creek, dry, drains E irregularly.
- 40.07 Point for the ¼ sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of brass cap, mkd.

T 29 S R 4 E

	¼	
S 17		S 16

1976

from which

A pinon, 8 ins. diam., bears S. 63° W., 15 lks. dist., mkd. ¼ S17 BT.

Desc. over rocky NE slope of bench, through juniper and pinon.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 29 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS							
47.00	Head of draw, drains N; desc. along W slope down draw.						
68.00	Ravine, drains W about 2 chs. to main draw; asc. over rocky SW slope.						
77.50	Spur, slopes NW; desc. steep NE slope.						
80.14	Point for the cor. of secs. 8, 9, 16 and 17, at proportionate distance; there is no remaining evidence of the original corner.						
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.						
	T 29 S R 4 E						
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 2px;">S 8</td> <td style="padding: 2px;"> </td> <td style="padding: 2px;">S 9</td> </tr> <tr> <td style="padding: 2px;">S 17</td> <td style="padding: 2px;"> </td> <td style="padding: 2px;">S 16</td> </tr> </table>	S 8		S 9	S 17		S 16
S 8		S 9					
S 17		S 16					
	1976						
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.						
	From the cor. of secs. 9, 10, 15 and 16.						
	N. 89°04' W., bet. secs. 9 and 16.						
	Over rocky bench, draining NE.						
39.88	Hard surface State Highway, No. 117, bears N to State Highway No. 24 and S to Teasdale.						
40.22	Point for the ¼ sec. cor. of secs. 9 and 16, at proportionate distance; there is no remaining evidence of the original corner.						
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.						
	T 29 S R 4 E						
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 2px;">¼</td> <td style="padding: 2px;"> </td> <td style="padding: 2px;">S 9</td> </tr> <tr> <td style="padding: 2px;"></td> <td style="padding: 2px;"> </td> <td style="padding: 2px;">S 16</td> </tr> </table>	¼		S 9			S 16
¼		S 9					
		S 16					
	1976						
	Place a boulder, 24 x 24 x 30 ins., W of cor.						
	Asc. along N slope of rocky bench.						
61.00	Ravine, drains NW; asc. over steep and rocky NE slope.						
69.70	Spur, slopes N. 10° W.; desc. along rocky N slope.						
72.80	Ravine, drains NW; asc. over rocky NE slope.						
80.44	The cor. of secs. 8, 9, 16 and 17.						
	N. 1°05' E., bet. secs. 8 and 9.						

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 29 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	Over broken mountain land, through scattering juniper and pinon; desc. over rocky NE slope.
17.00	Wash in Cigarette Hollow, drains N. 10° E. from SW; asc. over SE slope.
36.90	High spur, slopes E; desc. over rocky N slope.
40.07	Point for the ¼ sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.
	T 29 S R 4 E ¼ S 8 S 9 1976
	Desc. over rocky N slope.
48.50	Canal, 10 lks. wide, 1 ft. deep, drains W from N. 15° E.; enter valley land.
51.90	Hard surface State Highway, No. 24 on curve bearing northwesterly and southeasterly bears E and curves SW; enter farm land.
77.00	Fremont River, 20 lks. wide, 2 ft. deep, drains NE from W irregularly; asc. SE slope.
80.14	The cor. of secs. 4, 5, 8 and 9, monumented with an iron post, 2 ins. diam., extending 8 ins. above ground, mkd. as described in the resurvey of a portion of the township in 1920.
	(Restoring the 1883 survey by A. D. Ferron and the 1920 resurvey by Elliot Bird)
	From the cor. of secs. 3, 4, 9 and 10. N. 89°45' W., bet. secs. 4 and 9. Over broken land; asc. along S slope.
15.00	Spur, slopes S; desc. over SW slope.
28.50	Fremont River, 20 lks. wide, 2 ft. deep, drains S. 70° E. from NW; enter valley bottom land.
38.51	Point for the ¼ sec. cor. of secs. 4 and 9, determined longitudinally by N and S fence line, and latitudinally by proportionate measurement. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 29 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	<p>T 29 S R 4 E</p> <p>$\frac{1}{4}$ $\frac{S 4}{S 9}$</p> <p>1976</p>
	<p>Set a cedar post, 6 ins. diam., 5 ft. high, alongside the iron post.</p> <p>Cor. is located in old N and S fence line.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>West, beginning new measurement.</p> <p>Continue over valley bottom land.</p>
35.50	Fremont River, 20 lks. wide, 2 ft. deep, drains NE; asc. over SE slope.
39.66	The cor. of secs. 4, 5, 8 and 9.
	<p>(Restoring the 1883 survey by A. D. Ferron and the 1904 resurvey by J. P. Walker)</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>N. 89°47' W., bet. secs. 17 and 20.</p> <p>Over mountain land, covered with scattering juniper, pinon and ponderosa pine; asc. over NE slope.</p>
6.00	Base of steep ascent, bears NW and SE; asc. over steep NE slope.
14.40	N end of high gypsum spur, slopes N. 10° W.; desc. over steep W slope.
20.00	Base of same spur, bears N and S irregularly; thence over bottom of wide draw.
23.00	Dirt road, bears N and S.
24.80	Bullberry Creek, drains N; continue over bottom of draw.
39.91	<p>The $\frac{1}{4}$ sec. cor. of secs. 17 and 20, monumented with a limestone, 22 x 10 x 3 ins., firmly set and mkd. $\frac{1}{4}$ on N face, from which the original bearing trees</p> <p style="padding-left: 40px;">A pinon, 14 ins. diam., bears S. 8° W., 235 lks. dist., mkd. RES $\frac{1}{4}$ SBT.</p> <p style="padding-left: 40px;">A pinon, 16 ins. diam., bears N. 72°30' W., 46 lks. dist., mks. grown over.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

28
29

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 29 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS		
	<p>T 29 S R 4 E</p> <p>$\frac{1}{4} \frac{S 17}{S 20}$</p> <p>1976</p> <p>Deposit the mkd. stone alongside the iron post.</p> <hr/> <p>N. 85°14' W., beginning new measurement.</p> <p>Continue over bottom of draw.</p>	
9.50	Base of ascent, bears NE and SE irregularly; asc. over broken and irregular SE slope.	
21.80	Spur, slopes SE; asc. along broken S slope.	
26.60	Ravine, drains SE; asc. over E slope.	
35.80	Spur, slopes S; desc. over SW slope.	
38.40	Head of ravine, drains SE; asc. over broken SE slope.	
39.55	U. S. Forest Reserve Boundary Post No. 97, monumented with an iron post, 3 ins. diam., set in a mound of stone, mkd. as described in the resurvey of the Aquarius Forest Reserve boundary by J. P. Walker in 1904. This cor. was also designated by J. P. Walker as a witness cor. for the cor. of secs. 17, 18, 19, and 20.	
39.59	<p>The cor. of secs. 17, 18, 19 and 20, monumented with a trachyte stone, 14 x 10 x 8 ins., mkd. 3 notches on S and 5 notches on E edge, from which the original bearing trees</p> <p>A fallen pinon, 14 ins. diam., bears N. 40¼° E., 38 lks. dist., mkd. T29S R4E S17 BT.</p> <p>A fallen pinon, 16 ins. diam., bears S. 67½° E., 75 lks. dist., mkd. T29S R4E S20 BT.</p> <p>A pinon, 10 ins. diam., bears S. 21½° W., 9 lks. dist., mkd. T29S R4E S19 BT.</p> <p>A pinon, 12 ins. diam., bears N. 24¼° W., 35 lks. dist., mkd. T29S R4E S18 BT.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., on solid rock, over an X, in a mound of stone, 5 ft. base to top of brass cap, mkd.</p>	
	<p>T 29 S R 4 E</p> <p>$\frac{S 18}{S 19} \mid \frac{S 17}{S 20}$</p> <p>1976</p> <p>Place the mkd. stone alongside iron post, in mound.</p>	
	S. 89°18' W., bet. secs. 18 and 19.	

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 29 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	Over broken mountain land, covered with juniper and pinon; asc. over ledgy SE slope.
20.50	High spur on S end of Black Ridge, slopes S; desc. over SW slope.
24.40	Ravine, drains S. 10° E; asc. over SE slope.
27.00	Spur, slopes S; desc. over general W slope, through thick juniper and pinon.
39.76	The ¼ sec. cor. of secs. 18 and 19, monumented with a trachyte stone, 18 x 10 x 8 ins., firmly set mkd. ¼ on N face, from which the original bearing trees <p style="margin-left: 40px;">A pinon, 12 ins. diam., bears S. 25° W., 29 lks. dist., mkd. RES S19 BT.</p> <p style="margin-left: 40px;">A cedar, 12 ins. diam., bears N. 48° W., 26 lks. dist., mkd. ¼ S18 BT.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.</p> <p style="text-align: center;">T 29 S R 4 E</p> <p style="text-align: center;">¼ $\frac{S\ 18}{S\ 19}$</p> <p style="text-align: center;">1976</p> <p>Place the mkd. stone in mound, alongside the iron post.</p> <p>From this cor., USGS triangulation station "Teasdale" bears N. 58°52' E., 19.77 chs. dist.. latitude 38°17'00.073" N., longitude 111°30'36.639" W., as published by U.S.G.S., a brass tablet 3 ins. diam., seated in concrete on solid rock..</p> <hr style="width: 20%; margin: 20px auto;"/> <p>S. 87°31' W., beginning new measurement.</p> <p>Desc. over broken SW slope.</p>
2.00	Small draw, drains SW.
19.00	Spur, slopes S; desc. over steep W slope.
24.50	Ravine, drains SW; thence along ledgy and inaccessible S slope.
39.00	Spur, slopes SW; desc. over W slope.
39.98	The cor. of secs. 18 and 19, on the W. bdy. of the Tp., previously described.
	(Restoring the 1883 survey by A. D. Ferron)
	From the cor. of secs. 17, 18, 19 and 20. N. 0°21' W., bet. secs. 17 and 18.

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 29 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	Over broken mountain land, covered with juniper and pinon; asc. over SE slope.
7.50	Spur, slopes E; desc. along steep E slope.
12.20	Draw, drains E; asc. along steep E slope.
29.00	Spur, slopes N. 23° E.; desc. over NW slope.
36.50	Draw, drains NE; asc. over SE slope.
39.26	Point for the ¼ sec. cor. of secs. 17 and 18, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd. <div style="text-align: center;"> <p>T 29 S R 4 E</p> <p>¼</p> <p> </p> <p>S 18 S 17</p> <p> </p> <p>1976</p> </div>
	Cor. is located on spur, which slopes E; thence along E slope.
42.30	Small draw, drains N. 72° E.; continue along E slope.
54.00	High spur, slopes E; desc. over steep and ledgy N slope.
78.52	Point for the cor. of secs. 7, 8, 17 and 18, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a collar of stone, with brass cap, mkd. <div style="text-align: center;"> <p>T 29 S R 4 E</p> <p>S 7 S 8</p> <p>— —</p> <p>S 18 S 17</p> <p>1976</p> </div>
	Raise a mound of stone, 2 ft. base, 2 ft. high, W of cor. Cor. is located on a small ridge, which bears N and S.
	From the cor. of secs. 8, 9, 16 and 17. N. 88°42' W., bet. secs. 8 and 17. Over broken mountain land, covered with scattering pinon and juniper; asc. over NE slope.
2.70	Spur, slopes N. 70° W.; thence along broken N slope.
14.00	Draw, drains N.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 29 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
16.20	N side of knoll; continue along broken N slope.
40.25	Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 17, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.
	T 29 S R 4 E
	$\frac{1}{4}$ $\frac{S 8}{S 17}$
	1976
41.20	Wash in Cigarette Hollow, drains N. 80° E. from S; thence through small hollow.
57.00	Base of ascent, bears NW and SE; asc. over broken and ledgy NE slope.
67.60	Spur, slopes N. 10° E.; asc. along broken N slope.
80.50	The cor. of secs. 7, 8, 17 and 18.
	S. $88^\circ 16'$ W., bet. secs. 7 and 18.
	Over broken mountain land, through juniper and pinon; desc. over NW slope.
3.10	Ravine, drains N. 40° W.; asc. over NE slope.
7.00	Spur, slopes N. 25° E.; desc. over broken NW slope.
17.40	Draw, drains N; asc. over NE slope.
25.00	Spur, slopes N; desc. over W slope.
30.30	Ravine, drains N; asc. over NE slope.
35.10	Spur, slopes N; desc. over broken and ledgy W slope.
40.18	The $\frac{1}{4}$ sec. cor. of secs. 7 and 18, monumented with a trachyte stone, 15 x 8 x 8 ins., firmly set in a mound of stone, plainly mkd. $\frac{1}{4}$ on N face, from which the original bearing tree A pinon, 14 ins. diam., bears N. 88° W., 17 lks. dist., mkd. $\frac{1}{4}$ SBT. At the corner point Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.
	T 29 S R 4 E
	$\frac{1}{4}$ $\frac{S 7}{S 18}$
	1976

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 29 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS		
	Deposit the mkd. stone, in mound, alongside the iron post.	
	Cor. falls at base of sandstone ledges facing W.	
	N. 89°45' W., beginning new measurement.	
	Desc. broken W slope.	
7.20	Ravine, drains N. 20° W.; thence along broken and ledgy N slope, over series of small spurs and washes, draining N.	
21.50	Spur, slopes N; desc. over NW slope.	
27.00	Base of descent, bears NE and SW; desc. over gentle NW slope of bench in valley.	
39.56	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., previously described.	
	From the cor. of secs. 7, 8, 17 and 18.	
	N. 0°19' W., bet. secs. 7 and 8.	
	Over broken mountain land, covered with scattering pinon and juniper; along top of smal ridge, which bears N and S.	
7.50	Crest of steep descent, bears NW and SE irregularly; desc. over steep NE slope and ledges facing NE.	
27.60	Draw, drains W; asc. over S slope.	
33.20	Spur, slopes W; desc. over NW slope.	
38.80	Ravine, drains W; asc. SW slope.	
39.26	The ¼ sec. cor. of secs. 7 and 8, monumented with a trachyte stone, 14 x 10 x 10 ins., firmly set and plainly mkd. ¼ on W face.	
	At the corner point	
	Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.	
	<div style="text-align: center;"> <p>T 29 S R 4 E</p> <p>¼</p> <p> </p> <p>S 7 S 8</p> <p> </p> <p>1976</p> </div>	
	Deposit the mkd. stone in mound, alongside the iron post.	
	(Restoring the 1880 survey by A. D. Ferron and the 1920 retracement by Elliot Bird)	

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 29 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS						
	<p>N. 0°49' E., beginning new measurement.</p> <p>Asc. SW slope.</p>					
2.40	Spur, slopes N. 70° W.; desc. over NW slope.					
8.00	Base of steep descent, bears NW and SE; desc. gentle N slope, leave hills.					
20.80	Hard surface State Highway No. 24, bears N. 84°45' W. and S. 84°45' E.; enter pasture land.					
38.00	Fremont River, 30 lks. wide, 2 ft. deep, meanders E from NW.					
39.40	Point for the cor. of secs. 5, 6, 7 and 8, determined latitudinally by E and W fence line, and longitudinally by proportionate distance.					
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 29 S R 4 E</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 6</td> <td style="padding: 0 5px;">S 5</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 7</td> <td style="padding: 0 5px;">S 8</td> </tr> </table> <p style="text-align: center;">1976</p>	S 6	S 5	S 7	S 8	
S 6	S 5					
S 7	S 8					
	<p>Cor. is located in E and W fence line.</p> <p>From this cor., the N ¼ sec. cor. of sec. 8, bears S. 89°41' E., 40.35 chs. dist., monumented with an iron post, 1 in. diam., extending 10 ins. above ground, mkd. as described in the resurvey of a portion of the subdivision by Elliot Bird in 1920.</p>					
	<p>N. 89°43' W., bet. secs. 6 and 7.</p> <p>Over valley land along Fremont River, across fields and pasture, along washed out E and W fence line.</p>					
0.25	Fremont River on N end of meander; thence across river bottom covered with dense growth of willows and swamp.					
9.50	Leave swampy bottom land and river meanders; thence over farms.					
14.20	Irrigation ditch, drains NE; asc. over steep and ledgy SE slope, leave fence line.					
20.00	Top of ascent; thence along steep and ledgy S slope.					
40.35	The ¼ sec. cor. of secs. 6 and 7, monumented with a trachyte stone, 24 x 14 x 14 ins., firmly set in a mound of stone, and plainly mkd. ¼ on N face.					
	<p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.</p>					

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 29 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS

T 29 S R 4 E

$$\frac{1}{4} \frac{S 6}{S 7}$$

1976

Deposit the mkd. stone in mound, alongside the iron post.

(Restoring the 1883 survey by A. D. Ferron)

N. 89°47' W., beginning new measurement.

Along S slope.

- 1.00 Slope changes; desc. over W slope.
- 7.50 Wash, drains SW; desc. gentle W slope over rocky bench in valley, leave hills.
- 13.70 Old abandoned hard surface State Highway No. 24, bears N. 22°30' W. and S. 22°30' E.
- 16.50 Hard surface State Highway No. 24, bears N. 85° W. and S. 85° E.
- 39.73 The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., previously described.

General Description

The portion of T. 29 S., R. 4 E., resurveyed consists mainly of valley land along the Fremont River, extending into the surrounding mountains. The valley land is mainly small farms and grass pasture on the river bottom and dry pasture land on the higher benches. The mountains are steep and rocky with exposed ledges of sandstone and gypsum. The Fremont River enters the township on the W. bdy. of sec. 7, meanders eastward and leaves the township on the E. bdy. of sec. 24. State highway No. 24, enters the township on the W. bdy. of sec. 6, bears eastward and leaves the township on the E. bdy. of sec. 12. There are numerous other farm roads within the township.

Permanent habitation within the area surveyed consists of the town of Teasdale, located in sec. 16, and several homes on the surrounding farms.

The elevation of the township varies from about 6800 to 8500 ft. above mean sea level.

The mean magnetic declination was read at a number of stations throughout the township and the average of several readings was found to be 16°00' E.

CERTIFICATE OF SURVEY

(I) ~~(WX)~~ Craig P. Sylvester, Supervisory Cadastral Surveyor, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 26th day of March 1976, (I) ~~(WX)~~ have dependently resurveyed portions of the east boundary (First Guide Meridian East), west boundary and subdivisional lines of Township 29 South, Range 4 East

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

January 6, 1977
(Date)

Craig P. Sylvester
(Cadastral Surveyor)
Supervisory

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Washington, D.C.
Denver, Colorado

The foregoing field notes of the dependent resurvey of portions of the east boundary (First Guide Meridian East), west boundary and subdivisional lines of T. 29 S., R. 4 E., Salt Lake Meridian, Utah

executed by Craig P. Sylvester, Supervisory Cadastral Surveyor having been critically examined and found correct, are hereby approved.

OCT 04 1979
(Date)

J. [Signature]
(Chief, Division of Cadastral Survey)

Chief, Cadastral Survey Examination and Approval Staff
CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in [] is a true copy of the original field notes.~~

(Date)

(Chief, Division of Cadastral Survey)

36

38

INDEX DIAGRAM

Township 13 South, Range 10 East

6	5	4	3	2 14	1 13
7 38	8 37	9	10	11	12 12
18 36 36	17 29 35	16 24	15 19 24	14 11 18	13 11
19 34 33	20 29 32	21 23 28	22 17 22	23 10 17	24 9
30 31	29 27 30	28 21 26	27 16 21	26 8 16	25 8
31	32 25	33 20 6	34 14 5	35 7 4	36 2

Township 13 South, Range 10 East, Salt Lake Meridian, Utah

CHAINS

T. 13 S., R. 10 E.

History of Surveys

Surveyed by Retr. or Resurveyed by

NORTH BOUNDARY

All	A.D. Ferron	1885	H.W. Miller	1923
W. 1 mi.	A.D. Ferron	1881	A.D. Ferron	1885

SOUTH BOUNDARY

All	A.D. Ferron	1880	A.D. Ferron	1890
-----	-------------	------	-------------	------

EAST BOUNDARY

All	A.D. Ferron	1885		
S. 3 mi.			A.D. Ferron	1890
S. 2½ mi. and N.				
1 mi.			Glen B. Hatch	1965
E. Bdy., secs.			E. Bird and	1947
12 & 13, and N½			G.W. Johnson	
Sec. 24				

WEST BOUNDARY

S. 4 mi.	A.D. Ferron	1880	A.D. Ferron	1890
N. 2 mi.	A.D. Ferron	1881		
All			Miller, Nelson & Bandy	1923 - 28

SUBDIVISIONS

Sec. 6	A.D. Ferron	1881		
S½ Tp.	A.D. Ferron	1890		
N½ Tp.	A.D. Ferron	1901		
Portion			A.D. Ferron	1901
Bdys., secs. 4 &			Miller and Nelson	
10				1931 - 35
Subdivision of	Bird, Miller &			
secs. 4 & 10	Nelson	1931 - 35		
Bdys., Sec. 11			Gentry, Nelson & Clark	1942
Subdivision of	Gentry, Nelson &			
Sec. 11	Clark	1942		
Underground tra-	H.W. Miller	1932		
verse of coal mine in				
Sec. 6				
Underground tra-	Nelson & Bird			
verse of coal mine in		1931 - 35		
secs. 9 and 10				
Underground tra-	Gentry, Nelson &			
verse of coal	Clark	1942		
mine in sec. 11				

The following field notes describe the dependent resurvey of a portion of the south boundary and a portion of the subdivisional lines of Township 13 South, Range 10 East, Salt Lake Meridian, Utah.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated May 7, 1976.

Dependent Resurvey of a Portion of the South Boundary,
T. 13 S., R. 10 E., Salt Lake Meridian, Utah

CHAINS

The direction of the lines of this survey were determined by reference to true meridians established on line by hour angle observations on Polaris. They were carried forward by sustained angulation, being supplemented by numerous other observations on Polaris taken throughout the progress of the survey.

Measurements were determined by electronic means along survey lines where accessible. Distances to topography on lines run by traverse due to rough terrain, timber and private property are approximately as scaled from U.S.G.S. topographic sheets.

Before restoring lost corners, the lines of the original survey were retraced and a diligent search was made for any evidence of the original corners. The rules of proportionate measurement were applied to ascertain the position of the lost corner after every reasonable possibility of finding direct evidence of the corner had been exhausted.

The geographic position for the southeast corner of the township, as determined from a tie made to U.S.G.S. triangulation station "GRAVES" located in sec. 1 of the township, is as follows:

Latitude $39^{\circ}38.7'$ N. Longitude $110^{\circ}44.4'$ W.

The magnetic declination is $14^{\circ}50'$ E.

Dependent Resurvey of a Portion of the South Boundary,
T. 13 S., R. 10 E., Salt Lake Meridian, Utah
(Restoring the 1880 survey and the 1890 resurvey
of A. D. Ferron)

Beginning at the cor. of Tps. 13 and 14 S., Rs. 10 and 11 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set and mkd. as described in the official record of the 1965 resurvey of the S. bdy. of T. 13 S., R. 11 E.

N. $89^{\circ}00'$ W., bet. secs. 1 and 36.

Over rolling bench land, through pinon and cedar growth; desc. SW slope.

7.80 Draw, drains SE; asc. SE slope.

13.70 E rim of mesa, bears N and S; over mesa top.

16.70 W rim of mesa, bears N and S; desc. SW slope.

25.00 Base of hill, bears N and S; over rolling land.

40.90 The $\frac{1}{4}$ sec. cor. of secs. 1 and 36, monumented with a sandstone, $12 \times 8 \times 6$ ins., firmly set and plainly mkd. $\frac{1}{4}$ on N face.

At the corner point

Dependent Resurvey of a Portion of the South Boundary,
T. 13 S., R. 10 E., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T 13 S R 10 E'

¼ $\frac{S\ 36}{S\ 1}$

T 14 S
1976

Deposit the mkd. stone alongside the iron post.

Cor. is located 39 lks. N of barbed wire fence, bears E and W.

N. 89°12' W., beginning new measurement.

4.50 Wash, drains SW.

18.50 Trail road, bears NW and SE.

39.26 The cor. of secs. 1, 2, 35, and 36, established in the 1890 resurvey of the S. bdy. of T. 13 S., R. 10 E., monumented with a sandstone, 16 x 8 x 6 ins., firmly set and plainly mkd. 5 notches on W and 1 on E edges.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T 13 S R 10 E

$\frac{S\ 35}{S\ 2} \mid \frac{S\ 36}{S\ 1}$

T 14 S
1976

Deposit the mkd. stone alongside the iron post.

Cor. is located 34 lks. N of barbed wire fence, bears E and W.

West, bet. secs. 2 and 35.

Over rolling land, through lightly scattering pinon and juniper growth.

2.22 Point for the cor. of secs. 1, 2, 35, and 36, determined by original bearing trees. This cor. was established in the 1880 survey of the N. bdy. of T. 14 S., R. 10 E., and not recovered during the 1890 resurvey of the S. bdy. of T. 13 S., R. 10 E.

from which the original bearing trees

A cedar, 13 ins. diam., bears N. 32° E., 76 lks. dist., with faint scribe marks.

Dependent Resurvey of a Portion of the South Boundary,
T. 13 S., R. 10 E., Salt Lake Meridian, Utah

CHAINS	
	A cedar, 6 ins. diam., bears S. 78° E., 110 lks. dist., with faint scribe marks.
	This cor. point was not monumented because it has no control. The 1890 cor. previously described is the controlling cor.
11.30	Trail road, bears NE and S.
16.36	Power line, bears N. 36°05' W. and S. 36°05' E., also cardinal wash, drains SW; asc. gradual E slope.
41.09	The 1/4 sec. cor. of secs. 2 and 35, determined at record dist., from the original bearing trees
	A cedar, 7 ins. diam., bears N. 37° E., 50 lks. dist., mkd. 1/4 S BT. (Record, N. 27° E.)
	A cedar, 5 ins. diam., bears S. 56°11' E., 26 lks. dist., mkd. 1/4 S BT. (Record, N. 35° E.)
	At the corner point
	Set an iron post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.
	T 13 S R 10 E
	1/4 S 35 S 2
	T 14 S 1976
	Cor. is located 1.30 chs. N of barbed wire fence, bears E and W.
	S. 89°42' W., bet. secs. 2 and 35, beginning new measurement.
	Asc. steep E slope.
11.00	E rim of mesa, bears N and S; over mesa top.
30.00	W rim of mesa, bears N and S; desc. W slope.
34.50	Draw, drains SW; along S slope of mesa.
41.35	Point for the cor. of secs. 2, 3, 34, and 35, at proportionate dist., falls on inaccessible slide area where it is impracticable to establish a permanent monument; there is no remaining evidence of the original cor. From which its witness cor. bears N. 14°52' W., 46 lks. dist., hereinafter described in the subdivisional line bet. secs. 34 and 35.
	S. 89°42' W., bet. secs. 3 and 34.
	Over broken land, through scattering pinon and juniper growth; desc. steep SW slope.
17.50	Draw, drains S.; over rolling bench land.

Dependent Resurvey of a Portion of the South Boundary,
T. 13 S., R. 10 E., Salt Lake Meridian, Utah

CHAINS

- 28.50 Dirt road, bears N and S.
- 41.35 The $\frac{1}{4}$ sec. cor. of secs. 3 and 34, monumented with a sandstone, 20 x 7 x 4 ins., firmly set and plainly mkd. $\frac{1}{4}$ on N face.
- At the corner point
- Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to bedrock, in a collar of stone, with brass cap mkd.
- T 13 S R 10 E
- $\frac{1}{4}$ $\frac{S\ 34}{S\ 3}$
- T 14 S
1976
- from which
- A pinon, 10 ins. diam., bears N. 83° E., 31 lks. dist., mkd. BT.
- Deposit the mkd. stone alongside the iron post.
- _____
- S. $89^\circ 36'$ W., beginning new measurement.
- 2.00 Draw, drains SW.
- 13.80 W rim of bench, bears N and S; desc. broken W slope.
- 31.00 Meads Wash, drains S; over bottom land.
- 40.36 The cor. of secs. 3, 4, 33, and 34, monumented with a sandstone, 18 x 8 x 4 ins., firmly set and plainly mkd. 3 notches on E and W edges, from which an original bearing tree
- A dead cedar, 6 ins. diam., bears N. 30° W., 76 lks. dist., with faint scribe marks.
- At the corner point
- Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
- T 13 S R 10 E
- $\frac{S\ 33\ | \ S\ 34}{S\ 4\ | \ S\ 3}$
- T 14 S
1976
- Deposit the mkd. stone alongside the iron post.
- Set a steel fence post, 6 ft. long, alongside the cor.

Dependent Resurvey of a Portion of the South Boundary,
T. 13 S., R. 10 E., Salt Lake Meridian, Utah

CHAINS	
	N. 89°57' W., bet. secs. 4 and 33. Over mountainous land, through scattering pinon and juniper growth; asc. gradual E slope.
6.00	Base of hill, bears N and S; asc. broken E slope.
14.25	E rim of bench, bears N and S; over rolling bench land.
27.00	Draw, drains SE.
32.00	Power line, bears N. 52°34' W. and S. 52°34' E.
38.40	Dirt road, bears NE and SW.
39.12	The ¼ sec. cor. of secs. 4 and 33, monumented with a sandstone, 14 x 7 x 6 ins., firmly set and plainly mkd. ¼ on N face. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T 13 S R 10 E ¼ $\frac{S\ 33}{S\ 4}$ T 14 S 1976 Deposit the mkd. stone alongside the iron post. Set a cedar post alongside the cor.
	S. 89°55' W., beginning new measurement.
18.00	W rim of bench, bears NE and SW; desc. broken NW slope.
21.00	Power line, bears N. 16° W. and S. 16° E.
30.00	Base of hill, bears NE and SW; over rolling land.
38.00	Wash in Warehouse Canyon, drains SW.
40.06	The cor. of secs. 4, 5, 32, and 33, monumented with a sandstone, 15 x 14 x 6 ins., firmly set and plainly mkd. 4 notches on E and 2 on W edges. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T 13 S R 10 E $\frac{S\ 32}{S\ 5} \mid \frac{S\ 33}{S\ 4}$ T 14 S 1976 Deposit the mkd. stone alongside the iron post.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 13 S., R. 10 E., Salt Lake Meridian, Utah

CHAINS

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 13 S., R. 10 E., Salt Lake Meridian, Utah

(Restoring the 1890 survey of A. D. Ferron)

From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., heretofore described.

N. 8°28' W., bet. secs. 35 and 36.

Over rolling bench land, covered with sagebrush.

40.21 Point for the ¼ sec. cor. of secs. 35 and 36, at proportionate distance, falls in center of dirt road, which bears N and S; there is no remaining evidence of the original corner.

Deposit broken glass and rock mkd. with X, 10 ins. below road surface, from which

An iron post, 30 ins. long, 2½ ins. diam., set 18 ins. in the ground, in a collar of stone, for a reference monument, bears N. 45° E., 22.7 lks. dist., mkd. RM T13S R10E ¼ S36 above arrow pointing to the cor. point, and 15 FT 1976 below arrow.

An iron post, 30 ins. long, 2½ ins. diam., set 18 ins. in the ground, in a collar of stone, for a reference monument, bears N. 45° W., 22.7 lks. dist., mkd. RM T13S R10E ¼ S35 above arrow pointing to the cor. point, and 15 FT 1976 below arrow.

64.50 Same dirt road, bears SE and NW.

80.42 The cor. of secs. 25, 26, 35, and 36, monumented with a sandstone, 16 x 6 x 6 ins. firmly set and plainly mkd. 1 groove on E and S faces, from which an unrecorded bearing tree

A cedar, 6 ins. diam., bears N. 84°30' E., 62 lks. dist., mkd. S5.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 13 S R 10 E

S 26 | S 25
S 35 | S 36

1976

Deposit the mkd. stone alongside the iron post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 13 S., R. 10 E., Salt Lake Meridian, Utah

CHAINS	
	<p>From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set in a mound of stone, and mkd. as described in the 1965 resurvey of the W. bdy. of T. 13 S., R. 11 E.</p>
	<p>S. 88°41' W., bet. secs. 25 and 36.</p>
	<p>Over broken bench land, along S edge of reseeded area.</p>
10.00	<p>Draw, drains SSE.</p>
23.00	<p>Draw, drains SSE.</p>
47.51	<p>Point for the ¼ sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original cor.</p>
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., on solid sandstone, over a cross, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p>
	<p>T 13 S R 10 E</p> $\frac{1}{4} \begin{array}{c} \text{S 25} \\ \text{S 36} \end{array}$ <p>1976</p>
58.00	<p>Draw, drains SE.</p>
95.02	<p>The cor. of secs. 25, 26, 35, and 36.</p>
	<p>N. 0°30' W., bet. secs. 25 and 26.</p>
	<p>Over broken hills, through pinon and juniper; asc. along W slope.</p>
14.80	<p>Spur, slopes W; desc. over NW slope.</p>
38.00	<p>Wash, drains SW.</p>
39.77	<p>Point for the ¼ sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original cor.</p>
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p>
	<p>T 13 S R 10 E</p> $\begin{array}{c} \frac{1}{4} \\ \\ \text{S 26} \quad \quad \text{S 25} \\ \\ 1976 \end{array}$
	<p>from which</p>
	<p>A cedar, 5 ins. diam., bears N. 40° W., 10 lks. dist., mkd. S26 BT.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 13 S., R. 10 E., Salt Lake Meridian, Utah

CHAINS

Asc. SW slope in hollow.

41.20 S edge of bench, bears E and W irregularly; thence over reseeded area.

79.54 The cor. of secs. 23, 24, 25, and 26, monumented with a sandstone, 20 x 14 x 6 ins., firmly set and plainly mkd. 1 groove on E and 2 grooves on S face, with a mound of stone, W of cor.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T 13 S R 10 E

S 23	S 24
S 26	S 25

1976

Deposit the mkd. stone alongside the iron post.

From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., extending 6 ins. above ground, mkd. as described in the 1965 resurvey of the W. bdy. of T. 13 S., R. 11 E.

S. 88°31' W., bet. secs. 24 and 25.

Over rolling bench, across reseeded area.

4.30 Wash, drains SE.

47.32 Point for the ¼ sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.

T 13 S R 10 E

¼	S 24
	S 25

1976

52.00 Trail road, bears N. 80° E. and N. 80° W.

63.00 W edge of bench, bears N and S; desc. steep W slope.

82.00 Wash, drains SE; thence over reseeded area of bench.

94.64 The cor. of secs. 23, 24, 25, and 26.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 13 S., R. 10 E., Salt Lake Meridian, Utah

CHAINS	
	N. 5°11' E., bet. secs. 23 and 24. Over rolling bench, across reseeded area.
24.50	Dirt road, bears E and W.
39.53	Point for the ¼ sec. cor. of secs. 23 and 24, at proportionate distance falls in dirt road; there is no remaining evidence of the original corner. Bury sandstone, mkd. with an X, and deposit broken glass, 12 ins. below road surface, from which An iron post, 30 ins. long, 2½ ins. diam., set 18 ins. in the ground, in a collar of stone, for a reference monument, bears N. 45° E., 37.9 lks. dist., mkd. RM T13S R10E ¼ S24 25 FT 1976, with an arrow pointing to the corner point. An iron post, 30 ins. long, 2½ ins. diam., set 18 ins. in the ground, in a collar of stone, for a reference monument, bears N. 45° W., 37.9 lks. dist., mkd. RM T13S R10E ¼ S23 25 FT 1976, with an arrow pointing to the corner point.
66.50	Draw, drains SW irregularly.
74.50	Dirt road, bears NE and SW.
79.06	The cor. of secs. 13, 14, 23, and 24, monumented with a sandstone, 16 x 10 x 4 ins., firmly set and plainly mkd. 1 notch on E and 3 notches on S edges, from which the original bearing trees A cedar, 8 ins. diam., bears S. 37° E., 8 lks. dist., mkd. T13S R10E S24 BT. A cedar, 8 ins. diam., bears S. 3° W., 28 lks. dist., mkd. T13S R10E S23 BT. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T 13 S R 10 E S 14 S 13 S 23 S 24 1976 Deposit the mkd. stone alongside the iron post. Raise a mound of stone, 2 ft. base, 2 ft. high, W of cor.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 13 S., R. 10 E., Salt Lake Meridian, Utah

CHAINS

From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp.; monumented with an iron post, 2 ins. diam., set in a mound of stone, and mkd. as described in the 1947 resurvey of a portion of the W. bdy. of T. 13 S., R. 11 E.

S. 86°43' W., bet. secs. 13 and 24.

Over broken mountain land, covered with pinon and juniper; asc. over SE slope.

20.50 Spur, slopes S; desc. over SW slope.

43.66 Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.

T 13 S R 10 E

1/4 S 13 / S 24

1976

Cor. is located on SE slope in small hollow, 15 lks. E of large white sandstone boulder.

(Restoring the 1890 survey and the 1901 resurvey by A. D. Ferron)

S. 86°45' W., beginning new measurement.

18.25 Top of ledges, bear N. 70° W. and S. 70° E.; desc. over steep SW slope.

38.20 Draw, drains S. 10° W.

40.60 Dirt road, bears NE and SW.

43.66 The cor. of secs. 13, 14, 23, and 24.

N. 0°06' W., bet. secs. 13 and 14.

Over broken mountain land, covered with juniper and pinon; asc. over SE slope.

11.00 S rim of ledges; thence along E slope.

37.50 Draw, drains SE; asc. over SW slope.

40.14 Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate distance; this point was not monumented in the original survey because of rough terrain.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 13 S., R. 10 E., Salt Lake Meridian, Utah

CHAINS	
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a collar of stone, to top of brass cap, mkd.</p> <div style="text-align: center;"> <p>T 13 S R 10 E</p> <p>¼</p> <p>S 14 S 13</p> <p>1976</p> </div> <p>Asc. over SW slope.</p>
51.69	Point for the original witness ¼ sec. cor. of secs. 13 and 14 at proportionate dist.; there is no remaining evidence of the original cor. No monument was established.
54.50	High ridge, bears SE and NW; desc. along broken E slope.
80.28	The cor. of secs. 11, 12, 13, and 14, monumented with an iron post, 2 ins. diam., set in a mound of stone, and mkd. as described in the 1942 resurvey of a portion of the subdivisional lines in T. 13 S., R. 10 E.
	<p>From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., monumented with an iron post, 2 ins. diam., set in a mound of stone, and mkd. as described in the 1947 resurvey of a portion of the W. bdy. of T. 13 S., R. 11 E.</p> <p>S. 81°33' W., bet. secs. 12 and 13.</p> <p>Over mountainous land, through juniper and pinon; desc. over SW slope.</p>
4.00	Trail road in bottom of Left Fork Dead Man Canyon, bears N. 15° W. and S. 15° E.; asc. over E slope.
39.00	Ridge, bears NW and SE; desc. over W slope.
47.20	Red cedar line tree, in bottom of East Fork Alrad Canyon, blazes on E and W faces, canyon drains S. 15° W.; asc. over SE slope.
47.83	<p>The ¼ sec. cor. of secs. 12 and 13, monumented with a stationary sandstone boulder, 4 x 3 x 3 ft. mkd. ¼ on E face, from which the original bearing trees</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears S. 31° W., 19 lks. dist., mkd. ¼ S13 BT.</p> <p style="padding-left: 40px;">A pine, 14 ins. diam., bears N. 67°30' W., 34 lks. dist., mkd. ¼ S12 BT.</p> <p>Moved original boulder over and at the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 13 S., R. 10 E., Salt Lake Meridian, Utah

CHAINS

T 13 S R 10 E

1/4 S 12 / S 13

1976

S. 89°55' W., beginning new measurement.

Asc. over SE slope.

11.00 Ridge, bears N and S; desc. over steep W slope.

24.50 Bottom of Alrad Canyon, drains S; W slope.

26.00 Jeep trail, bears NNW and SSE.

40.35 The cor. of secs. 11, 12, 13, and 14.

From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., monumented with an iron post, 2 ins. diam., set in a mound of stone, and mkd. as described in the 1947 resurvey of a portion of the W. bdy. of T. 13 S., R. 11 E.

S. 84°02' W., bet. secs. 1 and 12.

Over broken mountain land, through juniper and pinon; desc. over steep W slope.

9.00 Bottom of Left Fork Dead Man Canyon, drains S.; asc. over E slope.

44.00 Ridge, bears N and S; desc. over W slope.

46.70 The 1/4 sec. cor. of secs. 1 and 12, monumented with a sandstone, 16 x 12 x 2 ins., firmly set and plainly mkd. 1/4 on N face, with a mound of stone W of corner, from which the original bearing trees

A pine, 12 ins. diam., bears N. 23° E., 11 lks. dist., mkd. 1/4 S1 BT.

A pine, 10 ins. diam., bears S. 89° E., 80 lks. dist., mkd. 1/4 S12 BT.

At the corner point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.

T 13 S R 10 E

1/4 S 1 / S 12

1976

Bury the mkd. stone alongside the iron post.

S. 89°58' W., beginning new measurement.

Desc. steep W slope.

52

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 13 S., R. 10 E., Salt Lake Meridian, Utah

CHAINS	
16.40	Bottom of Alrad Canyon, drains SW; asc. over E slope.
27.00	Ridge, bears N and S irregularly; desc. over SW slope.
35.00	Draw, drains S. 20° E.; asc. over SE slope.
38.38	The cor. of secs. 1, 2, 11, and 12, monumented with an iron post, 2 ins. diam., extending 4 ins. above sandstone, with concrete around base, and mkd. as described in the 1942 resurvey of a portion of the subdivisional lines.
	N. 2°50' W., bet. secs. 1 and 2.
	Over broken mountain land, covered with juniper and pinon, with patches of oak brush; asc. over SE slope.
25.00	Ridge, bears NW and SE; desc. over NE slope.
41.84	The ¼ sec. cor. of secs. 1 and 2, determined by a mound of stone, no marks could be identified. This is the best available evidence of the original corner position.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	<p style="text-align: center;">T 13 S R 10 E</p> <p style="text-align: center;"> ½</p> <p style="text-align: center;"> </p> <p style="text-align: center;">S 2 S 1</p> <p style="text-align: center;"> </p> <p style="text-align: center;"> 1976</p> <hr style="width: 20%; margin: auto;"/>
	N. 0°44' W., beginning new measurement.
	Desc. NE slope, through sagebrush.
3.00	Dirt road, bears N. 32° W. and S. 34° E.
7.30	Wash, drains NW; asc. over SW slope.
32.00	Slope changes; thence along gentle W slope, on ridge.
40.92	The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., monumented with an iron post, 2 ins. diam., extending 8 ins. above ground, and mkd. as described in the 1923 resurvey of the S. bdy. of T. 12 S., R. 10 E.
	From this cor., U.S.G.S. triangulations station "Graves" bears S. 40°54' E., 37.90 chs. dist., marked by a cross (X) chiseled on solid rock, its geographic position as given by U.S.G.S. is Latitude 39°43'37.150" N. and Longitude 110°45'12.169" W.
	(Restoring the 1890 survey by A. D. Ferron)
	From the true point for the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., previously described.
	N. 14°52' W., bet. secs. 34 and 35.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 13 S., R. 10 E., Salt Lake Meridian, Utah

CHAINS

Over rolling bench.

0.46

Point selected for the witness cor. to the cor. of secs. 2, 3, 34, and 35.

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.

W C
T 13 S R 10 E

S 34 | S 35
S 3 | S 2

T 14 S
1976

Cor. is located on bench, 25 lks. N of rim.

8.00

Rim of bench, bears NE and SW; desc. over NW slope.

20.00

Base of steep descent, bears NE and SW; thence over rolling land.

33.80

Draw, drains SW; asc. gentle S slope, over reseeded area.

41.38

The ¼ sec. cor. of secs. 34 and 35, monumented with a sandstone, 22 x 12 x 6 ins., set in a mound of stone, plainly mkd. ¼ on W face.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.

T 13 S R 10 E

¼
S 34 | S 35

1976

Place the mkd. stone in mound, alongside the iron post.

N. 0°23' E., beginning new measurement.

Over rolling land.

39.77

Point for the cor. of secs. 26, 27, 34 and 35, at proportionate distance. The original stone corner, a sandstone, 16 x 14 x 6 ins., was found lying loose on the ground, apparently moved by land railing, and its original position could not be determined.

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.

T 13 S R 10 E

S 27 | S 26
S 34 | S 35

1976

Bury the mkd. stone alongside the iron post.

54

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 13 S., R. 10 E., Salt Lake Meridian, Utah

CHAINS	
3.00	<p>From the cor. of secs. 25, 26, 35, and 36. S. 89°59' W., bet. secs. 26 and 35. Over broken land, draining S. Cardinal Wash, drains S.</p>
8.50	Trail road, bears NW and SE.
20.00	Base of steep ascent, bears N and S; asc. E slope.
32.70	Ridge, bears NW and SE; desc. over SW slope.
40.45	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 5 ft. base, to top of brass cap, mkd.</p>
	<p style="text-align: center;">T 13 S R 10 E $\frac{1}{4}$ $\frac{S\ 26}{S\ 35}$ 1976</p>
62.40	<p>Cor. is located in small draw, which drains S. 70° W.; thence over rolling land. Power line, bears N. 36°05' W. and S. 36°05' E.</p>
80.90	The cor. of secs. 26, 27, 34, and 35.
25.40	<p>N. 0°02' W., bet. secs. 26 and 27. Over rolling land, across reseeded area. Power line, bears S. 36°05' E. and N. 36°05' W.</p>
39.77	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T 13 S R 10 E $\frac{1}{4}$ S 27 S 26 1976</p>
78.00	<p>Set a cedar post, 6 ft. high, alongside the iron post. Dirt road, bears N. 10° E. and S. 15° W.</p>
79.54	The cor. of secs. 22, 23, 26, and 27, monumented with a sandstone, 18 x 16 x 8 ins., firmly set in a mound of stone, mkd. 2 notches on S and E edges.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 13 S., R. 10 E., Salt Lake Meridian, Utah

CHAINS

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 13 S R 10 E

S 22 | S 23
S 27 | S 26

1976

Bury the mkd. stone alongside the iron post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

From the cor. of secs. 23, 24, 25, and 26.

S. 89°54' W., bet. secs. 23 and 26.

Over rolling land, across reseeded area.

20.50 Wash, drains SW.

26.00 Wash, drains SE, enter pinon and juniper; asc. NE slope.

31.50 Trail road, bears S and NW.

40.13 Point for the ¼ sec. cor. of secs. 23 and 26, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a collar of stone, with brass cap mkd.

T 13 S R 10 E

¼ S 23
S 26

1976

Cor. is located on general NE slope, in small draw, which drains NE.

43.50 Spur, slopes N; desc. over NW slope.

56.00 Leave hills and timber; thence over small valley.

79.80 Dirt road, bears N. 10° E. and S. 10° W.

80.26 The cor. of secs. 22, 23, 26, and 27.

N. 4°59' E., bet. secs. 22 and 23.

Over rolling land, across reseeded area.

16.00 Dirt road, bears NW and SE.

20.50 Dirt road, bears NW and SE.

37.20 Hollow, drains SE; asc. S slope, leave reseeded area.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 13 S., R. 10 E., Salt Lake Meridian, Utah

CHAINS

- 39.76 Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
- T 13 S R 10 E

|

$\frac{1}{4}$

|

S 22 | S 23

|

1976
- Raise a mound of stone, 2 ft. base, 2 ft. high, W of cor.
- 41.30 Wash, drains SE; asc. over SW slope.
- 79.52 The cor. of secs. 14, 15, 22, and 23, monumented with a sandstone, 20 x 6 x 5 ins., set in a mound of stone, mkd. 2 notches on E and 3 notches on S edges, from which an original bearing tree
- A pine, 12 ins. diam., bears N. $62^{\circ}15'$ E., 31 lks. dist., mkd. T13S R10E S14 BT.
- Two other fallen bearing trees were identified.
- At the corner point
- Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4 ft. base. to top of brass cap, mkd.
- T 13 S R 10 E

S 15 | S 14

S 22 | S 23

1976
- Place the mkd. stone in mound, alongside the iron post.
-
- (Restoring the 1890 survey and the
1901 resurvey by A. D. Ferron)
- _____
- From the cor. of secs. 13, 14, 23, and 24.
- N. $89^{\circ}50'$ W., bet. secs. 14 and 23.
- Over broken land, covered with juniper and pinon; along S slope.
- 38.50 Draw, drains S.
- 40.39 The $\frac{1}{4}$ sec. cor. of secs. 14 and 23, monumented with a sandstone, 18 x 9 x 6 ins., firmly set and plainly mkd. $\frac{1}{4}$ on N face, with a mound of stone S of cor., from which an original bearing tree
- A pine, 14 ins. diam., bears S. $78^{\circ}30'$ E., 30 lks. dist., mkd. T13S R10E S23 BT.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 13 S., R. 10 E., Salt Lake Meridian, Utah

CHAINS

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.

T 13 S R 10 E

¼ S 14 / S 23

1976

Place the mkd. stone in mound alongside the iron post.

N. 89°36' W., beginning new measurement.

Continue along broken S slope, over series of small spurs and washes draining S.

40.06 The cor. of secs. 14, 15, 22, and 23.

(Restoring the 1901 survey by A. D. Ferron)

N. 0°38' E., bet. secs. 14 and 15.

Over broken mountain land, covered with juniper and pinon; asc. over SW slope.

38.00 Draw, drains SW.

39.74 The ¼ sec. cor. of secs. 14 and 15, marked with an X and ¼ alongside, on top of boulder, 20 x 13 x 12 ft. from which the original bearing trees

A pine, 10 ins. diam., bears N. 81° E., 40 lks. dist., mkd. ¼ S14 BT.

A pine, 13 ins. diam., bears S. 20° W., 47 lks. dist., mkd. ¼ S15 BT.

From the corner point

An iron post, 30 ins. long, 2½ ins. diam., set 22 ins. in the ground, in a collar of stone, for a reference monument, bears West, 19.7 lks. dist., mkd. RM T13S R10E ¼ S15 13FT 1976 with an arrow pointing to the cor. point.

N. 0°21' E., beginning new measurement.

Asc. over SW slope, through juniper and pinon.

7.50 Spur, slopes W; desc. over NW slope.

25.80 Dirt road, bears NE and SW.

27.00 Bottom of Cordingly Canyon, drains SW; asc. over NE slope.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 13 S., R. 10 E., Salt Lake Meridian, Utah

CHAINS

40.28 The cor. of secs. 10, 11, 14, and 15, monumented with an iron post, 2 ins. diam., set in a mound of stone, and mkd. as described in the 1931-35 resurvey and subdivision of secs. 4 and 10.

(Restoring the 1890 survey by A. D. Ferron)


From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., previously described.

N. 3°19' W., bet. secs. 33 and 34.

Over mountainous land, through scattering pinon and juniper growth; along broken E slope.

40.05 Point for the 1/4 sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.



Raise a mound of stone, 4 ft. base, 2 ft. high, W of cor.

67.00 Rim of bench, bears NE and SW; over rolling land.


74.00 Small draw, drains E.

80.10 The cor. of secs. 27, 28, 33, and 34, monumented with a sandstone, 18 x 8 x 8 ins., firmly set and plainly mkd. 3 notches on E edge and 1 groove on S face, from which an unrecorded bearing tree

A pinon, 12 ins. diam., bears S. 30° E., 24 lks. dist., mkd. S34 BT.

At the corner point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit the mkd. stone alongside the iron post.

Raise a mound of stone, 4 ft. base, 2 ft. high, W of cor.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 13 S., R. 10 E., Salt Lake Meridian, Utah

CHAINS	
	<p>From the cor. of secs. 26, 27, 34, and 35.</p> <p>N. 89°58' W., bet. secs. 27 and 34.</p> <p>Over railed and reseeded bench land.</p>
10.00	Bulldozed road, bears N and S.
26.00	Leave railed area, bears N and S; desc. W slope.
38.60	Wash, 15 ft. deep, 20 lks. wide, drains S; asc. E slope.
40.04	The ¼ sec. cor. of secs. 27 and 34, monumented with a sandstone, 24 x 20 x 20 ins., firmly set and plainly mkd. ¼ on N face.
	<p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 13 S R 10 E</p> <p style="text-align: center;">¼ $\frac{S\ 27}{S\ 34}$</p> <p style="text-align: center;">1976</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, E of cor., with mkd. stone in mound.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°34' W., beginning new measurement.</p>
13.00	Bottom of Meads Wash, drains SE; asc. E slope.
35.60	Top of bench, bears N and S.
36.00	The cor. of secs. 27, 28, 33, and 34.
	<p>N. 0°36' W., bet. secs. 27 and 28.</p> <p>Over rolling bench land, through pinon and juniper.</p>
28.00	Rim of bench, thence along broken E slope.
39.97	Point for the ¼ sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner.
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 13 S R 10 E</p> <p style="text-align: center;">¼ S 28 S 27 1976</p> <p>Cor. is located on steep E slope.</p>
75.50	Rim of same bench; over rolling land.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 13 S., R. 10 E., Salt Lake Meridian, Utah

CHAINS

79.94

The cor. of secs. 21, 22, 27, and 28, monumented with a sandstone, 20 x 10 x 6 ins., firmly set in a mound of stone and dimly mkd. 3 notches on E and 2 notches on S edges, from which 2 unrecorded bearing trees

A pinon, 7 ins. diam., bears N. 55° E., 17 lks. dist., with faint scribe marks.

A pinon, 8 ins. diam., bears N. 40° W., 15 lks. dist., with faint scribe marks.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, with brass cap mkd.

T 13 S R 10 E

S 21	S 22
S 28	S 27

1976

Deposit the mkd. stone alongside the iron post.

Cor. is located 70 lks. dist., W of the E edge of bench.

From the cor. of secs. 22, 23, 26, and 27.

S. 89°49' W., bet. secs. 22 and 27.

Over rolling land, railed and reseeded.

13.50 Draw, drains SW; asc. broken SE slope.

28.00 E rim of bench, bears NE and SW; over rolling land.

39.03 The ¼ sec. cor. of secs. 22 and 27, monumented with a sandstone, 16 x 10 x 8 ins., set in a mound of stone, with no visible marks. This position is accepted as the best available evidence of the original cor.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.

T 13 S R 10 E

¼	S 22	S 27
	S 22	S 27

1976

Deposit the unmkd. stone alongside the iron post.

N. 89°39' W., beginning new measurement.

0.35 Power line, bears N. 36°05' W. and S. 36°05' E.

5.90 Draw, drains S.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 13 S., R. 10 E., Salt Lake Meridian, Utah

03

CHAINS	
13.00	W rim of bench, bears NE and S; desc. W slope, through scattering pinon and juniper growth.
25.00	Meads Wash, drains S; asc. broken E slope.
37.10	E rim of bench, bears N and S; over rolling land.
37.79	The cor. of secs. 21, 22, 27, and 28.
N. 3°41' E., bet. secs. 21 and 22.	
Along E rim of bench, through pinon and juniper growth.	
18.50	Desc. broken NE slope.
30.00	Spur, slopes S. 70° E.
39.93	The ¼ sec. cor. of secs. 21 and 22, monumented with a sandstone, 29 x 8 x 6 ins., set in a mound of stone and plainly mkd. ¼ on W face.
At the corner point	
Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.	
<p style="text-align: center;">T 13 S R 10 E ½ S 21 S 22 1976</p>	
Deposit the mkd. stone alongside the iron post.	
Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.	
N. 0°29' E., beginning new measurement.	
1.00	Small wash, drains E.
2.00	Power line, bears N. 62° W. and S. 62° E.
7.00	Wash, drains SE; asc. SW slope.
28.00	Dirt road, bears NW and SE.
37.00	Spur, slopes W; desc. NW slope of draw.
39.81	The cor. of secs. 15, 16, 21, and 22, mkd. with a sandstone boulder, 15 x 10 x 8 ins., above ground, mkd. with a cross at the exact cor. point, with 3 grooves on the S and E sides also 1 in. pipe protruding 6 ins. above the cross; the cross is located on the E face of the boulder. This point cannot be improved upon.
Cor. is located in the bottom of draw, drains W.	
(Restoring the 1890 survey and the 1901 resurvey by A. D. Ferron)	

62

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 13 S., R. 10 E., Salt Lake Meridian, Utah

CHAINS

From the cor. of secs. 14, 15, 22, and 23.

N. 89°47' W., bet. secs. 15 and 22.

Over mountainous land, through pinon and juniper growth;
along S slope.

20.00 Wash, drains S.

22.70 Dirt road, bears NE and SW; asc. SE slope.

40.09 The $\frac{1}{4}$ sec. cor. of secs. 15 and 22, mkd. by an old mound
of stone, no mkd. rock, from which the original bearing
trees

A cedar, 10 ins. diam., bears N. 58° E., 21 lks.
dist., mkd. $\frac{1}{4}$ S15 BT. (Record, 15 lks. dist.)

A pinon, 10 ins. diam., bears S. 48°30' W., 53
lks. dist., mkd. $\frac{1}{4}$ S22 BT. (Record, 57 lks. dist.)

At the corner point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 14 ins.
in the ground to bedrock, in a mound of stone, 3 ft. base,
to top of brass cap, mkd.

T 13 S R 10 E

$\frac{1}{4}$ $\frac{S 15}{S 22}$

1976

Cor. is located on NE slope.

N. 89°28' W., beginning new measurement.

Asc. NE slope.

1.15 Ridge, bears NW and SE; along broken S slope.

25.75 Spur, slopes S; desc. SW slope.

40.68 The cor. of secs. 15, 16, 21, and 22.

(Restoring the 1901 survey by A. D. Ferron)

N. 0°04' E., bet. secs. 15 and 16.

Over broken mountainous land, through pinon and juniper
growth; asc. SW slope.

40.11 The $\frac{1}{4}$ sec. cor. of secs. 15 and 16, mkd. by an old mound
of stone, from which the original bearing trees

A pinon, 14 ins. diam., bears East, 57 lks. dist.,
mkd. $\frac{1}{4}$ S15 BT.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 13 S., R. 10 E., Salt Lake Meridian, Utah

CHAINS

A pinon, 12 ins. diam., bears S. 50° W., 7 lks.
dist., mkd. $\frac{1}{4}$ S16 BT.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins.
in the ground to bedrock, in a mound of stone, 5 ft. base,
to top of brass cap, mkd.

T 13 S R 10 E

$\frac{1}{4}$
 |
 S 16 | S 15
 |
 1976

Cor. is located on steep SW slope, 1.00 ch. dist., W
of base of ledges, bears NW and SE.

N. 0°32' E., beginning new measurement.

- 8.00 Top of ledges and spur, slopes NW; desc. NW slope.
- 27.00 Bottom of canyon, drains SW; asc. SE slope.
- 38.92 The cor. of secs. 9, 10, 15, and 16, monumented with an
iron post, 2 ins. diam., extending 6 ins. above mound of
stone, with brass cap mkd. as described in the official
record of the resurvey executed in 1931-35.

(Restoring the 1890 survey by A. D. Ferron)

From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of
the Township.

N. 2°42' W., bet. secs. 32 and 33.

Over broken bench land; asc. S slope through scattering
pinon and juniper trees.

- 15.00 Wash, drains S.
- 35.00 Rim of bench, bears NE and SW irregularly; enter railed
and reseeded area.
- 37.13 Power line, bears S. 52°36' E. and N. 52°36' W.
- 39.13 Power line, bears S. 52°36' E. and N. 52°36' W.
- 39.96 Point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33, at propor-
tionate distance; there is no remaining evidence of the
original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins.
in the ground, in a collar of stone, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 13 S., R. 10 E., Salt Lake Meridian, Utah

CHAINS	
	<p style="text-align: center;">T 13 S R 10 E $\frac{1}{4}$ S 32 S 33 1976</p> <p>Set a 6 ft. cedar post alongside the iron post.</p> <p>Raise a mound of stone, 2 ft. high, 4 ft. base to W.</p> <p>Cor. is located on nearly level railed and reseeded area.</p> <p>78.80 Rim of bench, bears NE and SW, leave railed area; desc. NW slope.</p> <p>79.92 Point for the cor. of secs. 28, 29, 32, and 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone to top of brass cap, mkd.</p> <p style="text-align: center;">T 13 S R 10 E S 29 S 28 S 32 S 33 1976</p> <p>Raise a mound of stone, 2 ft. high, 4 ft. base to W.</p> <p>Cor. is located on steep, broken NW slope.</p>
	<p>From the cor. of secs. 27, 28, 33, and 34.</p> <p>N. 89°46' W., bet. secs. 28 and 33.</p> <p>Over bench land, through dense pinon and juniper trees.</p> <p>3.00 Enter railed and reseeded area, bears N and S.</p> <p>6.00 Bulldozed road, bears N. 54° E. and S. 54° W.</p> <p>8.80 Desc. W slope.</p> <p>18.00 Warehouse Canyon, drains SW; asc. E slope.</p> <p>22.00 E rim of bench top, bears NE and SW; over bench top.</p> <p>39.14 The ¼ sec. cor. of secs. 28 and 33, monumented with a sandstone, 12 x 6 x 5 ins., firmly set in a mound of stone, with no visible marks, from which an unrecorded bearing tree,</p> <p style="padding-left: 40px;">A dead and fallen pinon, 12 ins. diam., bears N. 15° W., 42 lks. dist., mkd. ¼ S28 BT.</p> <p>At the corner point</p>

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 13 S., R. 10 E., Salt Lake Meridian, Utah

CHAINS	
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p>
	<p style="text-align: center;">T 13 S R 10 E</p>
	<p style="text-align: center;">¼ $\frac{S\ 28}{S\ 33}$</p>
	<p style="text-align: center;">1976</p>
	<p>Deposit the mkd. stone alongside the iron post.</p>
	<p>This position is harmoniously related to existing original cors. and is accepted as the best available evidence of the original cor. position.</p>
	<p style="text-align: center;">_____</p> <p>S. 89°38' W., beginning new measurement.</p>
31.35	<p>W rim of bench, bears NE and SW; desc. NW slope.</p>
39.13	<p>The cor. of secs. 28, 29, 32, and 33.</p>
	<p style="text-align: center;">_____</p> <p>N. 1°06' E., bet. secs. 28 and 29.</p>
	<p>Across broken clay hills; desc. NW slope through sagebrush.</p>
27.50	<p>Draw, drains SW irregularly; asc. SE slope through scattering pinon and juniper growth.</p>
39.92	<p>The ¼ sec. cor. of secs. 28 and 29, monumented with a sandstone, 21 x 13 x 7 ins., firmly set in a mound of stone and plainly mkd. ¼ on W face.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T 13 S R 10 E</p>
	<p style="text-align: center;">¼ S 29 S 28</p>
	<p style="text-align: center;">1976</p>
	<p>Deposit the mkd. stone alongside the iron post.</p>
	<p>Raise a mound of stone, 2 ft. high, 3 ft. base to W.</p>
	<p>Cor. is located 50 lks. W of ledges and head of draw that drains SE.</p>
	<p style="text-align: center;">_____</p> <p>N. 1°51' W., beginning new measurement.</p>
	<p>Asc. SE slope.</p>
6.50	<p>Spur, slopes E; thence over rolling bench land.</p>
40.74	<p>Point for the cor. of secs. 20, 21, 28, and 29, at proportionate distance; there is no remaining evidence of the original corner.</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 13 S., R. 10 E., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone to brass cap mkd.

T 13 S R 10 E

S 20	S 21
S 29	S 28

1976

from which

A pinon, 13 ins. diam., bears N. 16°38' E., 22 lks. dist., mkd. BT.

A pinon, 12 ins. diam., bears S. 80°35' W., 160 lks. dist., mkd. BT.

Cor. is located on nearly level land.

From the cor. of secs. 21, 22, 27, and 28.

N. 89°33' W., bet. secs. 21 and 28.

Across bench top, through dense pinon and juniper growth.

17.00 Enter railed and reseeded area, bears N and S.

23.00 Bulldozed road, bears N and S.

34.30 W rim of bench, bears N and S, enter pinon and juniper trees; desc. W slope.

38.99 Point for the ¼ sec. cor. of secs. 21 and 28, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base to top of brass cap, mkd.

T 13 S R 10 E

¼	S 21
	S 28

1976

from which

A pinon, 7 ins. diam., bears S. 68° W., 35 lks. dist., mkd. BT.

A pinon, 7 ins. diam., bears N. 8° W., 43 lks. dist., mkd. BT.

Cor. is located on steep W slope.

41.00 Foot of W slope, thence over nearly level land.

77.98 The cor. of secs. 20, 21, 28, and 29.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 13 S., R. 10 E., Salt Lake Meridian, Utah

CHAINS

- N. $1^{\circ}26'$ E., bet. secs. 20 and 21.
Across rolling bench land, through scattering pinon and juniper trees.
- 9.90 State Highway No. 157, bears N. 61° E. and S. 61° W.
- 32.00 Old railroad bed, bears N. 54° E. and S. 54° W.
- 40.25 Small draw, drains W.
- 40.73 Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 21, at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to bedrock, in a collar of stone to top of brass cap, mkd.
- T 13 S R 10 E

$\frac{1}{4}$

S 20 | S 21

1976
- Cor. is located in gently rolling bench land.
- 62.00 Old railroad bed, bears N. 67° E. and S. 67° W.; asc. steep S slope in bottom of draw, drains S.
- 81.46 The cor. of secs. 16, 17, 20, and 21, monumented with an iron post, $\frac{3}{4}$ in. diam., that has been cemented into a drilled hole in boulder, 10 x 5 x 4 ft.; the pipe extends 6 ins. out of the boulder and is in a cross with 3 grooves on the S and 4 on E edges. Cor. point cannot be improved upon and a new monument is not established.
-
- (Restoring the 1901 survey by A. D. Ferron)
-
- N. $0^{\circ}16'$ E., bet. secs. 16 and 17.
Asc. steep S slope over broken mountain land and precipitous ledges.
- 21.50 Ridge, bears SE and NW; desc. N slope.
- 27.00 Draw, drains NE.
- 28.50 Draw, drains E; asc. SE slope.
- 39.59 The $\frac{1}{4}$ sec. cor. of secs. 16 and 17, monumented with a sandstone, 12 x 10 x 5 ins., firmly set in a mound of stone and plainly mkd. $\frac{1}{4}$ on W face, from which the original bearing trees
- A pinon, 8 ins. diam., bears S. 10° E., 23 lks. dist., mkd. $\frac{1}{4}$ S16 BT.
- A pinon, 8 ins. diam., bears N. 20° W., 16 lks. dist., mkd. $\frac{1}{4}$ S17 BT.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 13 S., R. 10 E., Salt Lake Meridian, Utah

CHAINS	Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base, to top of brass cap, mkd.
	<p>T 13 S R. 10 E</p> <p>¼ S 17 S 16 1976</p>
	Deposit the mkd. stone alongside the iron post. Cor. is located on spur that slopes E.
	<hr style="width: 20%; margin: auto;"/>
	N. 1°34' E., beginning new measurement. Desc. NE slope.
7.00	Draw, drains E; asc. SE slope over broken mountain land.
29.00	Steep ridge, 8236 ft. in elevation, bears NE and SW; desc. N slope, through fir and oak brush.
37.71	The cor. of secs. 8, 9, 16, and 17, monumented with a sandstone, 24 x 18 x 12 ins., firmly set in a mound of stone and plainly mkd. 4 notches on S and E edges, from which the original bearing tree A fir, 15 ins. diam., bears S. 40° W., 13 lks. dist., mkd. with a grown over blaze, remark S17 BT.
	At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base, to top of brass cap, mkd.
	<p>T 13 S R 10 E</p> <p>S 8 S 9 S 17 S 16</p> <p>1976</p>
	Deposit the mkd. stone alongside the iron post. Cor. is located on N slope at E edge of fir growth.
	<hr style="width: 20%; margin: auto;"/>
	(Restoring the 1890 survey by A. D. Ferron)
	From the cor. of secs. 28, 29, 32, and 33. N. 89°49' W., bet. secs. 29 and 32. Over broken land, covered with sagebrush; desc. over NW slope.
30.50	Wash, drains SW; thence along broken S slope.
39.27	Point for the ¼ sec. cor. of secs. 29 and 32, at proportionate distance; there is no remaining evidence of the original corner.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 13 S., R. 10 E., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.

T 13 S R 10 E

$\frac{1}{4}$ $\frac{S\ 29}{S\ 32}$

1976

Cor. is located 6 lks. N of E and W fence line.

51.52 Power line, bears S. $52^{\circ}34'$ E. and N. $52^{\circ}34'$ W.

53.52 Power line, bears S. $52^{\circ}34'$ E. and N. $52^{\circ}34'$ W.

70.00 Hard surface road, bears W and NE; thence along road way.

78.54 Point for the cor. of secs. 29, 30, 31 and 32, determined longitudinally by projection of fences to N and S, and latitudinally by proportionate measurement, falls in roadway..

Drive an 8 in. spike flush with road surface, from which

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 20 ins. in the ground, in a collar of stone, for a reference monument, bears S. $5^{\circ}00'$ E., 27.3 lks. dist., mkd. RM T13S R10E S32 18 FT 1976, and an arrow pointing to the true point.

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 20 ins. in the ground, in a collar of stone, for a reference monument, bears N. $5^{\circ}00'$ W., 15.2 lks. dist., mkd. RM T13S R10E S30 10 FT 1976, and an arrow pointing to the true point.

From this cor., the $\frac{1}{4}$ sec. cor. of secs. 31 and 32, bears S. $0^{\circ}02'$ E., 39.84 chs. dist., determined by an iron post, $1\frac{1}{2}$ ins. diam., at cor. of fences, which bear N, S and W. This position is harmoniously related to existing original cors. and is accepted as the best available evidence of the original cor. position.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.

T 13 S R 10 E

$\frac{1}{4}$
|
S 31 | S 32

1976

Deposit the found iron post alongside the BLM iron post.

N. $0^{\circ}06'$ W., bet. secs. 29 and 30.

Over rolling land, along N and S fence line.

18.62 Power line, bears S. $52^{\circ}34'$ E. and N. $52^{\circ}34'$ W.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 13 S., R. 10 E., Salt Lake Meridian, Utah

CHAINS	
20.62	Power line, bears S. 52°34' E. and N. 52°34' W.
39.84	The ¼ sec. cor. of secs. 29 and 30, monumented with a sandstone, 18 x 8 x 5 ins., firmly set and plainly mkd. ¼ on W face.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	<p style="text-align: center;">T 13 S R 10 E</p> <p style="text-align: center;"> </p> <p style="text-align: center;">S 30 S 29</p> <p style="text-align: center;"> </p> <p style="text-align: center;">1976</p>
	Deposit the mkd. stone alongside the iron post.
	Cor. is located at old fence cor., fences bear S and W.
	N. 0°11' W., beginning new measurement.
	Over land covered with sagebrush.
13.15	State Highway No. 157, bears N. 51° E. and S. 51° W.
26.80	Old railroad bed, bears N. 44° E. and S. 44° W.; asc. over SW slope, enter scattering juniper and pinon.
39.52	The cor. of secs. 19, 20, 29, and 30, monumented with a sandstone, 18 x 8 x 8 ins., firmly set and plainly mkd. 2 notches on S and 5 notches on E edges.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	<p style="text-align: center;">T 13 S R 10 E</p> <p style="text-align: center;">S 19 S 20</p> <p style="text-align: center;">S 30 S 29</p> <p style="text-align: center;">1976</p>
	Bury the mkd. stone alongside the iron post.
	from which
	A pine, 8 ins. diam., bears S. 63° E., 39 lks. dist., mkd. BT.
	A pine, 10 ins. diam., bears N. 74° W., 26 lks. dist., mkd. BT.
	From the cor. of secs. 20, 21, 28 and 29.
	S. 88°36' W., bet. secs. 20 and 29.
	Over rolling land, through scattering juniper and pinon growth.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 13 S., R. 10 E., Salt Lake Meridian, Utah

68

CHAINS	
36.30	State Highway No. 157, bears N. 64°10' E. and S. 64°10' W.
38.89	The ¼ sec. cor. of secs. 20 and 29, monumented with a sandstone, 14 x 10 x 8 ins., firmly set and plainly mkd. ¼ on N face.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 13 S R 10 E
	¼ $\frac{S\ 20}{S\ 29}$
	1976
	Bury the mkd. stone alongside the iron post, and raise a mound of stone, 2 ft. base, 2 ft. high, N of cor.
	Cor. is located on edge of old railroad bed.
	S. 89°55' W., beginning new measurement.
0.50	Old railroad bed, parallels highway.
39.30	The cor. of secs. 19, 20, 29, and 30.
	N. 88°57' W., bet. secs. 19 and 30.
	Over rolling land, covered with pinon and juniper; along S slope.
3.50	Trail road, bears N and S.
13.00	Spur, slopes S; desc. over W slope.
18.00	Wash, drains S; thence over rolling land, leave timber.
39.66	The ¼ sec. cor. of secs. 19 and 30, monumented with a sandstone, 24 x 18 x 12 ins., firmly set and plainly mkd. ¼ on N face.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T 13 S R 10 E
	¼ $\frac{S\ 19}{S\ 30}$
	1976
	Bury the mkd. stone alongside the iron post.
	N. 89°58' W., beginning new measurement.
32.75	Power line, bears S. 50°30' E. and N. 50°30' W.
34.75	Power line, bears S. 50°30' E. and N. 50°30' W.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 13 S., R. 10 E., Salt Lake Meridian, Utah

CHAINS	
39.76	<p>The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., extending 8 ins. above ground, and mkd. as described in the 1923 resurvey of the E. bdy. of T. 13 S., R. 9 E.</p>
	<p>From the cor. of secs. 19, 20, 29, and 30. N. 0°54' E., bet. secs. 19 and 20. Over rolling land, covered with juniper and pinon; asc. over gentle S slope.</p>
36.00	<p>Old railroad bed, bears N. 50° E. and S. 50° W.</p>
41.76	<p>The $\frac{1}{4}$ sec. cor. of secs. 19 and 20, determined by a mound of stone, no marks identified, this point is accepted as the best available evidence of the original cor., from which an unrecorded bearing tree</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears S. 74° E., 15 lks. dist., faint scribe marks visible.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p> <div style="text-align: center;"> <p>T 13 S R 10 E</p> <p> </p> <p> $\frac{1}{4}$</p> <p>S 19 S 20</p> <p> </p> <p> 1976</p> </div> <p>from which</p> <p style="padding-left: 40px;">A pine, 7 ins. diam., bears N. 82° W., 44 lks. dist., mkd. BT.</p>
	<p>N. 1°13' E., beginning new measurement.</p>
20.40	<p>Trail road, bears NE and SW.</p>
30.00	<p>Rim, bears NE and SW; desc. over NW slope.</p>
40.32	<p>The cor. of secs. 17, 18, 19, and 20, monumented with a sandstone, 18 x 13 x 12 ins., firmly set and plainly mkd. 3 notches on S and 5 notches on E edges.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 13 S R 10 E</p> <p> </p> <p>S 18 S 17</p> <p>S 19 S 20</p> <p> </p> <p> 1976</p> </div>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 13 S., R. 10 E., Salt Lake Meridian, Utah

CHAINS

Bury the mkd. stone alongside the iron post, and raise a mound of stone, 2 ft. base, 2 ft. high, W of cor.

From this cor., the 1890 survey cor. of secs. 17, 18, 19, and 20, bears S. 52°52' W., 1.20 chs. dist., monumented with a sandstone, 17 x 11 x 9 ins., firmly set in a mound of stone and plainly mkd. 3 notches on S and 5 notches on E edges. The letters "AM" were added to the markings.

from which

A dead pine, 12 ins. diam., bears S. 80° E., 9 lks. dist., faint scribe marks visible. (Record, S. 62° E.)

(Restoring the 1890 survey and the 1901 resurvey
by A. D. Ferron)

From the cor. of secs. 16, 17, 20, and 21.

S. 89°09' W., bet. secs. 17 and 20.

Over mountain land, covered with juniper and pinon; asc. NE slope.

4.00 Saddle, bears N and S; thence along broken S slope, over series of spurs and washes draining S.

37.80 Spur, slopes SW; desc. over NW slope.

39.46 The $\frac{1}{4}$ sec. cor. of secs. 17 and 20, marked with an X and $\frac{1}{4}$ alongside, on the N face of a sandstone boulder, 30 x 20 x 15 ft. above ground, from which

A pine, 7 ins. diam., bears S. 50° E., 9 lks. dist., faint scribe marks visible. (Record, S. 8° E., 20 lks. dist.)

An iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears North, 1lk. dist., mkd. RM T13S R10E $\frac{1}{4}$ S17 0.7 FT 1976, and an arrow pointing to the true point.

N. 89°42' W., beginning new measurement.

Desc. over NW slope.

2.00 Draw, drains SW; asc. over NE slope.

4.00 Rim of bench, bears NE and SE; thence over bench.

27.80 Ridge, bears NE and SW; desc. over NW slope.

39.21 The cor. of secs. 17, 18, 19, and 20.


Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 13 S., R. 10 E., Salt Lake Meridian, Utah

CHAINS	
	<p>S. 89°43' W., bet. secs. 18 and 19.</p> <p>Over rolling land, covered with sagebrush; desc. over NW slope.</p>
4.45	Old railroad bed, bears NE and SW; desc. over gentle W slope.
29.95	Helper Canyon, drains SW.
39.85	Point for the ¼ sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original corner.
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 13 S R 10 E</p> <p style="text-align: center;">¼ $\frac{S 18}{S 19}$</p> <p style="text-align: center;">1976</p>
	Set a cedar post, 5 ft. high, alongside the iron post.
40.55	Wash, 3 ft. deep, 15 lks. wide, drains SW.
51.00	Enter Helper, Utah, thence down E and W street.
79.86	The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., determined by a railroad spike, driven flush to surface of asphalt road, this position was identified by local surveyors and Helper City engineer as a perpetuation of the original corner position. This position is harmoniously related to existing original cors. and is accepted as the best available evidence of the original cor. position.
	<p>From the cor. of secs. 17, 18, 19, and 20.</p> <p>N. 0°13' W., bet. secs. 17 and 18.</p> <p>Over broken mountain land, covered with scattering pinon and juniper; asc. over SW slope.</p>
1.50	Spur, slopes NW; desc. over NE slope.
9.80	Draw, drains SW; asc. over SW slope.
39.20	Point, projects NW; thence over top of point.
39.64	The ¼ sec. cor. of secs. 17 and 18, monumented with a sandstone, 28 x 10 x 4 ins., firmly set and plainly mkd. ¼ on W face, from which an original bearing tree
	<p>A cedar, 10 ins. diam., bears West, 16 lks. dist., mkd. ¼ S BT.</p> <p>At the corner point</p>

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 13 S., R. 10 E., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.



Place the mkd. stone in mound alongside the iron post.

Cor. is located on point; desc. over NW slope.

N. 0°03' E., beginning new measurement.

Desc. over NW slope.

10.00 Helper Canyon, drains SW; asc. over SE slope.

14.00 Spur, slopes SE; desc. over NE slope.

18.50 Draw, drains SE; asc. over broken and ledgy SW slope.


38.37 The cor. of secs. 7, 8, 17, and 18, monumented with a sandstone, 16 x 14 x 5 ins., firmly set and plainly mkd. 4 notches on S and 5 notches on E edges, from which the original bearing trees

A pine, 10 ins. diam., bears S. 52°30' E., 14 lks. dist., mkd. T13S R10E S17 BT.

A fallen pine, 14 ins. diam., bears N. 7° W., 37 lks. dist., mkd. with faint scribe marks.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.



Bury the mkd. stone alongside the iron post, and raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

From the cor. of secs. 8, 9, 16, and 17.

N. 89°08' W., bet. secs. 8 and 17.

Over broken and ledgy mountain land, covered with pinon and juniper trees, with patches of oak brush; desc. over NW slope.

1.50 Draw, drains N; asc. over NE slope.

6.00 Spur, slopes N. 10° E.; thence along N slope.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 13 S., R. 10 E., Salt Lake Meridian, Utah

CHAINS	
13.00	Ridge, bears NW and SE; desc. over broken W slope.
31.00	Draw, drains SW; thence along steep S slope.
39.71	The $\frac{1}{4}$ sec. cor. of secs. 8 and 17, monumented with a sandstone, 16 x 12 x 4 ins., firmly set and dimly mkd. $\frac{1}{4}$ on N face, from which the original bearing trees
	A cedar, 6 ins. diam., bears S. 11° E., 52 lks. dist., mkd. $\frac{1}{4}$ S17 BT.
	A pine, 12 ins. diam., bears N. 15° W., 30 lks. dist., mkd. $\frac{1}{4}$ S8 BT.
	At the corner point
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.
	T 13 S R 10 E
	$\frac{1}{4}$ $\frac{S 8}{S 17}$
	1976
	Place the mkd. stone in mound, alongside the iron post.
	S. $89^{\circ}34'$ W., beginning new measurement.
	Along steep S slope.
4.00	Slope changes; desc. SW slope.
20.00	Helper Canyon, drains SW; asc. over E slope.
35.00	Spur, slopes S; desc. over W slope.
40.24	The cor. of secs. 7, 8, 17, and 18.
	N. $89^{\circ}37'$ W., bet. secs. 7 and 18.
	Over broken mountain land, through juniper and pinon; desc. over broken SW slope.
6.00	Draw, drains SE; asc. over NE slope.
26.10	Ridge, bears NW and SE; desc. over SW slope.
39.65	The $\frac{1}{4}$ sec. cor. of secs. 7 and 18, monumented with a sandstone, 26 x 20 x 4 ins., firmly set and plainly mkd. $\frac{1}{4}$ on N face, from which the original bearing trees
	A pine, 14 ins. diam., bears N. 30° E., 185 lks. dist., mkd. $\frac{1}{4}$ S7 BT. Tree is now dead.
	A pine, 14 ins. diam., bears S. 20° W., 23 lks. dist., mkd. $\frac{1}{4}$ S18 BT T13S R10E.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 13 S., R. 10 E., Salt Lake Meridian, Utah

CHAINS

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.

T 13 S R 10 E

¼ $\frac{S 7}{S 18}$

1976

Bury the mkd. stone alongside the iron post, and raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.

N. 86°47' W., beginning new measurement.

Along steep and broken S slope.

19.40 Draw, drains SW.

40.92 The cor. of secs. 7, 12, 13, and 18, monumented with an iron post, 2 ins. diam., extending 6 ins. above ground, and mkd. as described in the 1923 resurvey of the E. bdy. of T. 13 S., R. 9 E.

General Description

Township 13 South, Range 10 East, is located approximately 3 miles north of Price, Utah. U.S. Highway 6, 50 runs northeast from Price to the town of Helper, population approximately 2,000, which lies on the west boundary of the township. The eastern part of Helper lies within sections 18 and 19. State Highway 157 runs south from Helper on the east side of U.S. Highway 6, 50. It branches east approximately 1 mile south of Helper, into section 30. About the center of section 30 it turns northeast and runs through parts of sections 29, 20 and 21 to the town of Kenilworth located on the boundary of sections 16 and 21. There are several dirt roads that run north from Price into and through the township. Section 1 can be reached by a dirt road that branches south from State Highway 33 which connects with U.S. Highway 6, 50 approximately 2 miles north of Helper.

Section 1 and the northly sections contained in this survey contain steep mountain land with drainage generally in a southerly direction. The south 3 tiers of sections contain gently rolling and broken bench land, with mesas and buttes and several deep washes and canyons with drainage generally in a southerly direction. Elevation ranges from approximately 6200 ft. in the south part of the area surveyed to approximately 8800 ft. in section 1.

The timber is mostly pinon pines and cedars with some fir and aspens in the higher elevations. Much of the land in the south 3 tiers of sections has been railed and re-seeded. The undergrowth is sagebrush and other native brushes.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 13 S., R. 10 E., Salt Lake Meridian, Utah

CHAINS

There are several old railroad beds in the west part of the township. A power line runs southeast and northwest through section 22, 27, and 35, and two parallel power lines run northwest and southeast through sections 19, 30, 29, and 32 and separate in section 33. The Denver and Rio Grande railroad tracks run through the towns of Helper along the west boundary of the township.

Coal has been mined in the north part of this township for many years but mainly on land adjoining but not included in this survey. At the present time the portion of township surveyed is used for agriculture.

CERTIFICATE OF SURVEY

(I) ~~(We)~~ Gail E. Reynolds, HEREBY
 CERTIFY upon honor that, in pursuance of special instructions bearing date of the 7th day
 of May, 1976, (I) ~~(We)~~ have dependently resurveyed a portion of
 the south boundary and a portion of the subdivisional lines of
 Township 13 South, Range 10 East,

of the Salt Lake Meridian, in the State of Utah, which
 are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my)
~~(our)~~ direction; and that said survey has been made in strict conformity with said special instruc-
 tions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in
 specific manner described in the foregoing field notes.

April 1, 1977
 (Date)

Gail E. Reynolds
 (Cadastral Surveyor)

April 1, 1977
 (Date)

Under the Supervision of
Glen B. Hatch
 (Cadastral Surveyor)

Acting Chief, Branch of Cadastral Survey
 CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
 Washington, D.C.
 Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the south
 boundary and a portion of the subdivisional lines of T. 13 S., R. 10 E.,
 Salt Lake Meridian, Utah

executed by Gail E. Reynolds, Cadastral Surveyor
 having been critically examined and found correct, are hereby approved.

OCT 10 1979
 (Date)

J. D. Voorhees
 (Chief, Division of Cadastral Survey)
 Chief, Cadastral Survey Examination and Approval Staff

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in
 is a true copy of the original field notes.~~

~~(Date) (Signature)~~

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

81

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

A PORTION OF THE SUBDIVISIONAL LINES

OF

TOWNSHIP 42 SOUTH, RANGE 1 EAST

Of the Salt Lake

Meridian,

In the State of Utah

EXECUTED BY

Jerry L. Thomas

Supervisory Cadastral Surveyor

Under special instructions dated January 7, 19 76, approved January 8, 1976,

_____, which provided for the surveys included under ~~XXXXXX~~ Group
Number 561, and assignment instructions dated April 8, 19 76.

Survey commenced April 20, 19 76

Survey completed April 26, 19 76

INDEX DIAGRAM

Township 42 S., Range 1 E.

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
6	6				
31	5 32	4 33	3 34	3 35	1 36

Township 42 South, Range 1 East, Salt Lake Meridian, Utah

CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines of sections 31 through 36, T. 42 S., R. 1 E., Salt Lake Meridian, Utah.

The south boundary, the south 2 miles of the Salt Lake Meridian, west boundary of T. 42 S., R. 1 E., and the subdivisional lines of sections 31 through 36 were surveyed by J. G. Burrill in 1877. The south 1 mile of the east boundary was surveyed by T. C. Bailey in 1877. The south 2 miles of the Salt Lake Meridian, west boundary of T. 42 S., R. 1 E., were resurveyed and the north 4 miles surveyed by T. C. Rathbone and L. E. Bolinger in 1916. The north 5 miles of the east boundary, the north boundary and subdivisional lines of sections 1 through 25 were surveyed, and the north boundaries of sections 31 through 36 and the south 1 mile of the east boundary were resurveyed by T. C. Rathbone and L. E. Bolinger in 1917.

The resurvey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 561, Utah, dated January 7, 1976.

The direction of the lines of this dependent resurvey were determined by reference to the true meridian established on line by hour angle observations on Polaris. The lines were carried forward by sustained angulation being supplemented by other hour angle observations on Polaris taken throughout the progress of the resurvey. Measurements were made by electronic telemetry.

Before restoring the corners, the lines of the original surveys were retraced and diligent search made for any evidence of the original corners, bearing trees and other calls of the field note record. When duly identified the corner positions were remonumented and new bearing objects marked.

The geographic position of the southeast corner of the township as determined from a tie made to U.S.G.S. "Tps. COR. T. 42 and 43 S., R. 1 W. and R. 1 E." on the south boundary of the township, is:

Latitude $37^{\circ}06'24.7''$ N. Longitude $111^{\circ}44'29.6''$ W.

The magnetic declination is $14^{\circ}15'$ E.

Dependent Resurvey of a portion of the Subdivisional Lines, T. 42 S., R. 1 E., Salt Lake Meridian, Utah

Reestablishment of the survey executed by
T. C. Bailey, Deputy Surveyor, in 1877

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., set, mkd. and witnessed as described in the concurrent resurvey of the N. bdy. of T. 43 S., R. 1 E.

N. $0^{\circ}37'$ E., bet. secs. 35 and 36.

Over gentle rolling desert land, through scattering undergrowth.

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 42 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS
16.58

Power transmission line, bears N. 74°07' W. and
S. 74°07' E.

38.97

The $\frac{1}{4}$ sec. cor. of secs. 35 and 36, monumented with a
sandstone, 7 x 5 x 4 ins., set in a small mound of stone
with no visible markings, and is accepted as the best
available evidence of the original corner position.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

```

T 42 S R 1 E
  |
   $\frac{1}{4}$ 
  |
S 35 | S 36
  |
  1976

```

Deposit the unmkd. stone alongside and raise a mound of
stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W of cor.

N. 0°04' W., beginning new measurement.

Begin descent over broken NW slope.

35.20

Wash, 30 lks. wide, 2 ft. deep, in bottom of draw, drains
SW; asc. along broken E slope.

39.25

Point for the cor. of secs. 25, 26, 35 and 36, at propor-
tionate distance longitudinally and at record dist. from
the witness $\frac{1}{4}$ sec. cor. of secs. 25 and 26. There is no
remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

```

T 42 S R 1 E
  |
  S 26 | S 25
  S 35 | S 36

```

1976

Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W of
cor.

Cor. is located in bottom of small ravine, which drains
E.

From this point, the $\frac{1}{4}$ sec. cor. of secs. 25 and 36, bears
N. 89°46' E., 40.15 chs. dist., monumented with an iron
post, 1 in. diam., firmly set, projecting 10 ins. above
ground; the witness cor. to the $\frac{1}{4}$ sec. cor. of secs. 25
and 26, bears N. 0°48' E., 41.29 chs. dist., monumented
with an iron post, 1 in. diam., firmly set, projecting 10
ins. above ground; the $\frac{1}{4}$ sec. cor. of secs. 26 and 35,
bears N. 89°15' W., 40.06 chs. dist., monumented with an
iron post, projecting 10" above ground, with brass caps
marks as described in the official record of the 1917 re-
survey of a portion of the subdivisional lines of T. 42 S.
R. 1 E. The topography being essentially the same, is
omitted from these field notes.

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 42 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS

- From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., set, mkd. and witnessed as described in the concurrent resurvey of the N. bdy. of T. 43 S., R. 1 E. N. $0^{\circ}24'$ E., bet. secs. 34 and 35.
- Over slightly broken desert land, through scattering undergrowth.
- 4.00 Wash, 20 lks. wide, 3 ft. deep, in bottom of draw, drains NE; asc. along gentle E slope.
- 20.00 Enter gentle rolling land.
- 38.95 Power transmission line, bears N. $74^{\circ}07'$ W. and S. $74^{\circ}07'$ E.
- 39.39 Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to bedrock, in a collar of stone, to top of brass cap, mkd.
- T 42 S R 1 E

$\frac{1}{4}$

|

S 34 | S 35

|

1976
- Begin descent over N slope.
- 43.00 Wash, 25 lks. wide, 3 ft. deep, in bottom of draw, drains NE; asc. over SE slope.
- 48.00 Top of spur, slopes E; desc. over N slope.
- 52.00 Wash, 30 lks. wide, 3 ft. deep, in bottom of draw, drains E; asc. over S slope.
- 76.00 Enter bottom of draw, draining S. 20° W.; asc. along bottom.
- 78.78 The cor. of secs. 26, 27, 34 and 35, monumented with a sandstone, 10 x 8 x 4 ins., firmly set, projecting 5 ins. above ground, dimly mkd. 2 notches on E and 1 notch on S edge, and in a scattered mound of stone.
- At the corner point
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
- T 42 S R 1 E

S 27 | S 26

S 34 | S 35

1976
- Deposit the dimly mkd. stone alongside the iron post.
-
- From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., set, mkd. and witnessed as described in the concurrent resurvey of the N. bdy. of T. 43 S., R. 1 E.

Dependent Resurvey of a portion of the Subdivisional Lines, T. 42 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS	N. 1°24' E., bet. secs. 33 and 34.
	Over gentle rolling desert land, through scattering undergrowth.
29.00	Wash, 25 lks. wide, 2 ft. deep, in bottom of draw, drains N. 80° E.
40.57	Point for the ¼ sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> <p>T 42 S R 1 E</p> <p> </p> <p> ¼</p> <p> </p> <p> S 33 S 34</p> <p> </p> <p> 1976</p> </div>
	Deposit an unmkd. stone, 16 x 9 x 2 ins., alongside the iron post.
	Asc. over gradual SE slope.
61.12	Power transmission line, bears N. 74°07' W. and S. 74°07' E.
72.00	Top of spur, slopes E; desc. over NE slope.
81.14	The cor. of secs. 33 and 34, monumented with a white sandstone, 14 x 7 x 3 ins., firmly set, projecting 7 ins. above ground, and mkd. 3 notches on E edge, with a scattered mound of stone to W.
	At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> <p>T 42 S R 1 E</p> <p> S 27</p> <hr style="width: 50%; margin: 0 auto;"/> <p> S 33 S 34</p> <p> 1976</p> </div>
	Deposit the mkd. stone alongside and raise a mound of stone, 2½ ft. base, 1½ ft. high, S of iron post. From this point, the closing cor. of secs. 27 and 28, bears West, 1.355 chs. dist., monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground. Add the marks CC 1976.
8.00	From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., set, mkd. and witnessed as described in the concurrent resurvey of the N. bdy. of T. 43 S., R. 1 E. N. 2°18' E., bet. secs. 32 and 33. Over gentle rolling desert land, through scattering undergrowth. Small wash, drains E; asc. over gradual SE slope.

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 42 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS	
40.33	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 42 S R 1 E</p> <p>$\frac{1}{4}$</p> <p>S 32 S 33</p> <p>1976</p> </div> <p>Deposit a sandstone, 14 x 10 x 5 ins., alongside the iron post.</p> <p>Asc. over gradual S slope.</p>
60.00	<p>Top of sandy ridge, bears E and W; desc. over gradual N slope.</p>
80.66	<p>The cor. of secs. 32 and 33, monumented with a sandstone, 10 x 6 x 4 ins., set in a scattered mound of stone, dimly mkd. 2 notches on E edge.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 42 S R 1 E</p> <p>S 28</p> <hr style="width: 50%; margin: 0 auto;"/> <p>S 32 S 33</p> <p>1976</p> </div> <p>Deposit the dimly mkd. stone alongside the iron post.</p> <p>From this point, the closing cor. of secs. 28 and 29, bears N. $89^{\circ}19'$ W., 2.27 chs. dist., monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground. Add the marks CC 1976.</p>
	<p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., set, mkd. and witnessed as described in the concurrent resurvey of the N. bdy. of T. 43 S., R. 1 E.</p> <p>N. $0^{\circ}29'$ E., bet. secs. 31 and 32.</p> <p>Asc. over gradual S slope, through scattering undergrowth.</p>
34.90	<p>Top of sandy ridge, bears E and W; desc. over N slope.</p>
39.96	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 42 S R 1 E</p> <p>$\frac{1}{4}$</p> <p>S 31 S 32</p> <p>1976</p> </div>

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 42 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS								
	<p>Set a 2 x 4 ins. wood post, 36 ins. long, alongside the iron post.</p> <p>Desc. over gradual N slope.</p> <p>44.00 Bottom of descent, bears NE and SW; thence over gentle rolling land.</p> <p>79.92 The cor. of secs. 29, 30, 31 and 32, monumented with an iron pipe, 1½ ins. diam., projecting 3 ins. above ground, established by a local survey. This position is harmoniously related to existing original cors., and is accepted as the best available evidence of the original corner position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 42 S R 1 E</p> <p style="text-align: center;"> <table border="1" style="margin: auto;"> <tr> <td style="padding: 2px;">S 30</td> <td style="padding: 2px;"> </td> <td style="padding: 2px;">S 29</td> </tr> <tr> <td style="padding: 2px;">S 31</td> <td style="padding: 2px;"> </td> <td style="padding: 2px;">S 32</td> </tr> </table> </p> <p style="text-align: center;">1976</p> <p>Deposit iron pipe alongside the iron post.</p>	S 30		S 29	S 31		S 32	
S 30		S 29						
S 31		S 32						
	<p>The ¼ sec. cor. of sec. 32 only, on the N. bdy. of sec. 32, monumented with a sandstone, 10 x 9 x 3 ins., set in a scattered mound of stone, dimly mkd. ¼ on S face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 42 S R 1 E</p> <p style="text-align: center;"> <table border="1" style="margin: auto;"> <tr> <td style="padding: 2px;">¼ S 32</td> </tr> </table> </p> <p style="text-align: center;">1976</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>From this point, the ¼ sec. cor. of sec. 29, T. 42 S., R. 1 E., bears S. 89°19' E., 0.43 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. as described in the official record of the 1917 resurvey of a portion of the subdivisional lines of T. 42 S., R. 1 E., and the cor. of secs. 29, 30, 31 and 32, bears N. 89°36' W., 40.69 chs. dist., heretofore described.</p>	¼ S 32						
¼ S 32								
	<p>The ¼ sec. cor. of secs. 30 and 31, monumented with a sandstone, 10 x 10 x 4 ins., firmly set in scattered mound of stone and dimly mkd. ¼ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>							

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 42 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS

T 42 S R 1 E

$$\frac{1}{4} \frac{S 30}{S 31}$$

1976

Deposit the dimly mkd. stone alongside the iron post.

From this point, the cor. of secs. 29, 30, 31 and 32, bears N. 89°57' E., 39.38 chs. dist., heretofore described.

From the same point the cor. of secs. 25, 30, 31, and 36, Tps. 42 S., Rs. 1 E. and 1 W., bears N. 89°24' W., 40.42 chs. dist., monumented with an iron post, 2 ins. diam., in a mound of stone to top with brass cap mkd. as described in the official record of the 1916 resurvey of a portion of the Salt Lake Meridian.

Due to an error of closure, in sec. 31, it was necessary to retrace the $N\frac{1}{2}$ mile between secs. 31 and 36, Tps. 42 S., Rs. 1 E. and 1 W. and was found to be N. 0°31' E., 39.59 chs.

General Description

Township 42 South, Range 1 East is located on East Clark Bench about 3 miles west of Glen Canyon City. The elevation varies from 4,400 to 4,800 ft. above sea level. The soil is mostly sandy to sandy loam in the southern portion of the township.

Access is by way of U. S. Highway No. 89, which crosses through the north tier of sections of T. 43 S., R. 1 E., with a few trail roads extending into the southern portion of the township.

The principle use of the area surveyed is livestock grazing. The only improvements noted were some small tract surveys in section 32.

This portion of the township is mostly rolling sandy hills with scattered undergrowth of bunch grass, brigham tea and cacti.

The average number of readings throughout the area surveyed gives a mean magnetic declination of 14°15' E.

91

CERTIFICATE OF SURVEY

(1) ~~WEX~~ Jerry L. Thomas, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 7th day of January, 1976, (1) ~~WEX~~ have dependently resurveyed a portion of the subdivisional lines of T. 42 S., R. 1 E.,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), (1) ~~WEX~~ and under (my) ~~WEX~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

March 11, 1977

(Date)

Jerry L. Thomas
(Cadastral Surveyor)
Supervisory

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Washington, D.C.
Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines of T. 42 S., R. 1 E., Salt Lake Meridian, Utah

executed by Jerry L. Thomas, Supervisory Cadastral Surveyor having been critically examined and found correct, are hereby approved.

JAN 16 1980

(Date)

W. J. [Signature]
(Chief, Division of Cadastral Survey)

Acting Chief, Cadastral Survey Examination and Approval Staff

CERTIFICATE OF TRANSCRIPT

~~I Certify that the foregoing transcript of the field notes of the above described surveys is a true copy of the original field notes.~~

(Date)

(Chief, Division of Cadastral Survey)

INDEX DIAGRAM

Township 43 S., Range 1 E.

7 2 6	7 27 5	6 25 4	5 22 3	4 19 2	3 15 1
27 2 7	27 26 8	24 24 9	21 21 10	19 18 11	14 14 12
18	17	23 16	20 15	17 17 14	13 12 13
19	20	21	22	16 23	12 11 24
30	29	28	27	26	10 9 25
31	32	33	34	35	9 36

Township 43 South, Range 1 East, Salt Lake Meridian, Utah

CHAINS

The following field notes are those of the dependent resurvey of a portion of the Salt Lake Meridian along the west boundary, the north boundary and a portion of the subdivisional lines of T. 43 S., R. 1 E., Salt Lake Meridian, Utah.

The east 4 miles of the south boundary, the east boundary, the north boundary, the north 3 miles of the Salt Lake Meridian, east boundary of T. 43 S., R. 1 W., and a portion of the subdivisional lines were surveyed by J. G. Burrill in 1877. The east 4 miles of the south boundary, the east boundary, the Salt Lake Meridian, east boundary of section 13 and the south $\frac{1}{2}$ mile of the east boundary of section 12, T. 43 S., R. 1 W., the south 4 miles of the 4th meridional line west, the south boundaries of sections 7 and 8 were resurveyed, and the west 2 miles of the south boundary, the south 3 miles of the Salt Lake Meridian, east boundary of T. 43 S., R. 1 W., and the subdivisional lines of sections 17, 18, 19, 20, 29, 30, 31 and 32, were surveyed by A. Nelson and E. Bird in 1917.

The resurvey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 561, Utah, dated January 7, 1976.

The direction of the lines of this dependent resurvey were determined by reference to the true meridian established on line by hour angle observations on Polaris. The lines were carried forward by sustained angulation being supplemented by other hour angle observations on Polaris taken throughout the progress of the resurvey. Measurements were made by electronic telemetry.

Before restoring the corners, the lines of the original surveys were retraced and diligent search made for any evidence of the original corners, bearing trees and other calls of the field note record. When duly identified the corner positions were remonumented and new bearing objects marked.

The geographic position of the southeast corner of the township as determined from a tie made to U.S.G.S. "1/4 COR. SEC. 8" on the south boundary of section 8, is:

Latitude $37^{\circ}01'11.3''$ N. Longitude $111^{\circ}44'30.5''$ W.

The magnetic declination is $14^{\circ}15'$ E.

Dependent Resurvey of a Portion of the Salt Lake Meridian, West Boundary of T. 43 S., R. 1 E., Salt Lake Meridian, Utah

Reestablishment of the survey executed by J. G. Burrill, Deputy Surveyor, in 1877

Beginning at the $\frac{1}{4}$ sec. cor. of sec. 7, T. 43 S., R. 1 E., which is monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. as described in the official record of the 1917 resurvey of a portion of the W. bdy. of T. 43 S., R. 1 W.

Dependent Resurvey of a portion of the Salt Lake
Meridian, West Boundary of T. 43 S., R 1 E.,
Salt Lake Meridian, Utah

CHAINS		
	N. 0°22' E., on the W. bdy. of sec. 7.	
	Over gentle rolling desert land, through scattering undergrowth.	
13.00	Rim of cove, bears E and W; desc. over broken W slope.	
27.00	Bottom of descent, drains W; asc. over broken SW slope.	
39.20	Wash, in bottom of draw, drains NW 1 ch., thence W.	
40.00	The cor. of secs. 6 and 7, monumented with a sandstone, 16 x 12 x 2 ins., mkd. 1 notch on N and 5 notches on S, firmly set, 8 ins. in the ground, with scattered mound of stone to W.	
	At the corner point	
	Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.	
	<p style="text-align: center;">T 43 S R 1 W R 1 E S 12 S 6 S 7</p>	
	1976	
	Deposit the mkd. stone alongside the iron post.	
	Cor. is located on top of small spur, sloping S into wash.	
	N. 0°57' E., on the W. bdy. of sec. 6.	
	Over slightly broken desert land, through scattering undergrowth; asc. over broken SW slope.	
16.00	Top of sandy spur, projects W from NE; desc. over NW slope.	
30.00	Base of descent, bears NE and SW; thence over nearly level land.	
39.86	The ¼ sec. cor. of sec. 6, monumented with a small mound of stone harmoniously related to identified original cors., is accepted as the best available evidence of the original cor. position.	
	At the corner point	
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.	
	<p style="text-align: center;">T 43 S R 1 W R 1 E ¼ S 6 </p>	
	1976	
	Raise mound of stone, 2½ ft. base, 1½ ft. high, E of cor.	

Dependent Resurvey of a portion of the Salt Lake
Meridian, West Boundary of T. 43 S., R. 1 E.,
Salt Lake Meridian, Utah

CHAINS	
	N. 0°03' E., beginning new measurement.
21.00	Wash in bottom of draw, drains W; thence along broken W slope.
21.35	Telephone line, 2 strand, bears N. 85°13' E. and S. 85°13' W.
21.74	Fence line, 4 strand, bears N. 85°13' E. and S. 85°13' W.
24.20	Center line of U.S. Highway No. 89A, bears N. 85°13' E. and S. 85°13' W.
27.80	Fence line, 4 strand, bears N. 85°13' E. and S. 85°13' W.
27.84	Power line, 3 strand, bears N. 85°13' E. and S. 85°13' W.
40.03	The cor. of Tps. 42 and 43 S., Rs. 1 E. and 1 W., is monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. as described in the official record of the 1961 resurvey of the Salt Lake Meridian, W. Bdy. of T. 42 S., R. 1 E. This cor. is also identified as a U.S.G.S. triangulation station at Latitude 37°06'27.36" N., Longitude 111°51'02.38" W.
Dependent Resurvey of the N. Bdy. of T. 43 S., R. 1 E., Salt Lake Meridian, Utah	
Reestablishment of the survey executed by J. G. Burrill, Deputy Surveyor, in 1877	
From the cor. of Tps. 42 and 43 S., Rs. 1 and 2 E., which is monumented with an iron post, 3 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. as described in the official record of the 1917 resurvey of the N. bdy. of T. 42 S., R. 2 E.	
N. 88°39' W., bet. secs. 1 and 36.	
Over nearly level land, through scattering undergrowth.	
18.00	Base of ascent, bears N and S; asc. over E slope.
20.36	Power transmission line, bears N. 74°07' W. and S. 74°07' E.
40.13	The ¼ sec. cor. of secs. 1 and 36, monumented with a sandstone, 28 x 15 x 8 ins., firmly set 18 ins. in the ground mkd. ¼ on N face.
At the corner point	
Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.	

Dependent Resurvey of the North Boundary of
T. 43 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS		
	<p style="text-align: center;">T 42 S R 1 E</p> <p style="text-align: center;">$\frac{1}{4} \frac{S 36}{S 1}$</p> <p style="text-align: center;">T 43 S R 1 E 1976</p> <p>Deposit the mkd. stone alongside the iron post, in the mound of stone.</p> <p>Cor. is located 93½ lks. N of fence line, bearing E and W.</p> <p style="text-align: center;">_____</p> <p>N. 89°39' W., beginning new measurement.</p> <p>Asc. over slightly broken E slope, through scattering undergrowth.</p>	
12.00	Top of ascent, bears N and S; thence over nearly level land.	
14.50	Dirt road, bears N and S.	
28.00	Trail road, bears NE and SW.	
40.23	<p>The cor. of secs. 1, 2, 35 and 36, monumented with a sandstone, 14 x 12 x 2 ins., firmly set 8 ins. in the ground, mkd. 4 notches on W edge.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 42 S R 1 E</p> <p style="text-align: center;">$\frac{S 35}{S 2} \mid \frac{S 36}{S 1}$</p> <p style="text-align: center;">T 43 S R 1 E 1976</p> <p>Deposit the mkd. stone alongside and raise a mound of stone, 2½ ft. base, 1½ ft. high, N of iron post.</p>	
40.12	<p>N. 89°36' W., bet. secs. 2 and 35.</p> <p>Over gentle rolling land, through scattering undergrowth.</p> <p>Point for the ¼ sec. cor. of secs. 2 and 35, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 42 S R 1 E</p> <p style="text-align: center;">$\frac{1}{4} \frac{S 35}{S 2}$</p> <p style="text-align: center;">T 43 S R 1 E 1976</p>	

Dependent Resurvey of the North Boundary of
T. 43 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS							
	Set a cedar post, 5 ft. long, 8 ins. diam., alongside iron post.						
	Cor. is located 140 lks. N of fence line, bearing E and W.						
54.00	Rim of wide draw, bears NE and SW; desc. over NW slope.						
80.24	The cor. of secs. 2, 3, 34, and 35, monumented with a sandstone, 20 x 14 x 6 ins., dimly mkd. and set in a scattered mound of stone.						
	At the corner point						
	Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, to top of brass cap, mkd.						
	T 42 S R 1 E						
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">S 34</td> <td style="text-align: center;"> </td> <td style="text-align: center;">S 35</td> </tr> <tr> <td style="text-align: center;">S 3</td> <td style="text-align: center;"> </td> <td style="text-align: center;">S 2</td> </tr> </table>	S 34		S 35	S 3		S 2
S 34		S 35					
S 3		S 2					
	T 43 S R 1 E 1976						
	Deposit the dimly mkd. stone alongside the iron post in the mound of stone.						
	Cor. is located N. 77°16' W., 11.41 chs. dist., of the cor. of fences, bearing E, W and S.						
	N. 89°42' W., bet. secs. 3 and 34.						
	Over gentle rolling land, through scattering undergrowth.						
3.00	Wash, 8 ft. deep, 20 lks. wide, in bottom of draw, drains NE; asc. over SE slope.						
11.00	Top of ascent, bears NE and SW; thence over nearly level land.						
36.00	Rim of draw, bears NE and SW; desc. over W slope.						
39.95	The ¼ sec. cor. of secs. 3 and 34, monumented with a sandstone, 20 x 12 x 8 ins., firmly set in a small mound of stone with no visible markings.						
	At the corner point						
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.						
	T 42 S R 1 E						
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">¼</td> <td style="text-align: center;">S 34</td> </tr> <tr> <td></td> <td style="text-align: center;">S 3</td> </tr> </table>	¼	S 34		S 3		
¼	S 34						
	S 3						
	T 43 S R 1 E 1976						
	Deposit the unmkd. stone alongside and raise a mound of stone, 2½ ft. base, 1½ ft. high, N of iron post.						

Dependent Resurvey of the North Boundary of
T. 43 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS							
	N. 89°58' W., beginning new measurement.						
	Desc. over W slope.						
1.00	Wash, 4 ft. deep, 30 lks. wide, drains NE; asc. over E slope.						
5.00	Top of ascent, bears NW and SW; thence over nearly level land.						
15.50	Trail road, bears NW and SE.						
40.25	Point for the cor. of secs. 3, 4, 33, and 34, at proportionate distance; there is no remaining evidence of the original corner.						
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a small collar of stone, with brass cap mkd.						
	<p style="text-align: center;">T 42 S R 1 E</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">S 33</td> <td style="text-align: center;"> </td> <td style="text-align: center;">S 34</td> </tr> <tr> <td style="text-align: center;">S 4</td> <td style="text-align: center;"> </td> <td style="text-align: center;">S 3</td> </tr> </table> <p style="text-align: center;">T 43 S R 1 E 1976</p>	S 33		S 34	S 4		S 3
S 33		S 34					
S 4		S 3					
	Cor. is located 62½ lks. N of fence line, which bears N. 87° E. and S. 87° W.						
	N. 89°58' W., bet. secs. 4 and 33.						
	Over gentle rolling desert land, with scattering undergrowth.						
40.25	Point for the ¼ sec. cor. of secs. 4 and 33, at proportionate distance; there is no remaining evidence of the original corner.						
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.						
	<p style="text-align: center;">T 42 S R 1 E</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">¼</td> <td style="text-align: center;">S 33</td> </tr> <tr> <td></td> <td style="text-align: center;">S 4</td> </tr> </table> <p style="text-align: center;">T 43 S R 1 E 1976</p>	¼	S 33		S 4		
¼	S 33						
	S 4						
	Set a wood post, 4 x 4 ins., 4 ft. long, alongside the iron post.						
	Continue over gentle rolling land.						
65.50	Wash, drains NE.						
80.50	The cor. of secs. 4, 5, 32, and 33, marked by a piece of re-bar, projecting 8 ins. above ground, established by a local survey. This position is harmoniously related to existing original cors., and is accepted as the best available evidence of the original corner position.						
	At the corner point						

Dependent Resurvey of the North Boundary of
T. 43 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 42 S R 1 E

S 32	S 33
S 5	S 4

T 43 S R 1 E
1976

An iron rod, 1 in. diam., projecting 7 ft. above ground, is 2 lks. S of iron post.

Cor. is located 177 lks. N of fence line, which bears E and W.

N. 89°16' W., bet. secs. 5 and 32.

Over gentle rolling desert land, through scattering undergrowth.

40.01 The ¼ sec. cor. of secs. 5 and 32, marked by a piece of re-bar, projecting 8 ins. above ground, established by a local survey. This position is harmoniously related to existing original cors., and is accepted as the best available evidence of the original corner position.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 42 S R 1 E

¼	S 32	
	S 5	S 5

T 43 S R 1 E
1976

An iron rod, 1 in. diam., projecting 7 ft. above ground, is 2 lks. S of iron post.

N. 88°40' W., beginning new measurement.

Continue over gentle rolling land.

40.89 The cor. of secs. 5, 6, 31, and 32, monumented with a sandstone, 6 x 5 x 2 ins. firmly set, projecting 2 ins. above ground and mkd. 5 notches on E and 1 notch on W edge.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

101

Dependent Resurvey of the North Boundary of
T. 43 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS					
	<p>T 42 S R 1 E</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>S 31</td> <td>S 32</td> </tr> <tr> <td>S 6</td> <td>S 5</td> </tr> </table> <p>T 43 S R 1 E 1976</p> <p>Deposit the mkd. stone and set a cedar post, projecting 5 ft. above ground, alongside the iron post.</p>	S 31	S 32	S 6	S 5
S 31	S 32				
S 6	S 5				
	<p>N. 89°33' W., bet. secs. 6 and 31.</p> <p>Over gentle rolling desert land, through scattering undergrowth.</p>				
39.97	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p>T 42 S R 1 E</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>$\frac{1}{4}$</td> <td>S 31</td> </tr> <tr> <td></td> <td>S 6</td> </tr> </table> <p>T 43 S R 1 E 1976</p> <p>Set steel fence post, projecting 4 ft. above ground, alongside the iron post.</p>	$\frac{1}{4}$	S 31		S 6
$\frac{1}{4}$	S 31				
	S 6				
44.00	Trail road, bears N. 80° W. and S. 80° E.				
70.00	Intersection of trail roads, bear N. 80° E., N. 85° W., S. 35° E. and N. 35° W.				
79.94	The cor. of Tps. 42 and 43 S., Rs. 1 E and 1 W., heretofore described.				
	<p>Dependent Resurvey of a portion of the Subdivisional Lines of T. 43 S., R. 1 E., Salt Lake Meridian, Utah</p>				
	<p>Reestablishment of the survey executed by J. G. Burrill, Deputy Surveyor, in 1877</p>				
	<p>From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. as described in the official record of the 1917 resurvey of the E. bdy. of T. 43 S., R. 1 E., from which the remaining bearing trees mkd. in 1917</p> <p>A cedar, 10 ins. diam., bears N. 16° E., 366 lks. dist., mkd. T43S R2E S30 BT.</p>				

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 43 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS

A cedar, 10 ins. diam., bears S. 12° E., 49 lks.
dist., mkd. T43S R2E S31 BT.

A cedar, 8 ins. diam., bears S. $26\frac{1}{2}^{\circ}$ W., 541 lks.
dist., mkd. T43S R1E S36 BT.

A cedar, 10 ins. diam., bears N. $38\frac{1}{4}^{\circ}$ W., 276 lks.
dist., mkd. T43S R1E S25 BT.

N. $89^{\circ}49'$ W., bet. secs. 25 and 36.

Over rolling land, through scattered juniper and pinon
timber; desc. over NW slope.

40.10

Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36, at propor-
tionate distance; there is no remaining evidence of the
original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 43 S R 1 E

$\frac{1}{4}$	S 25
	S 36

1976

Set a cedar post, 5 ft. long, projecting 3 ft. above
ground, alongside the iron post.

Over gentle rolling desert land.

80.20

Point for the cor. of secs. 25, 26, 35, and 36, determined
latitudinally by proportionate distance and longitudinal-
ly by a fence line bearing N and S. There is no remaining
evidence of the original monument.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 43 S R 1 E

S 26		S 25
S 35		S 36

1976

Cor. is located in fence line, bearing N and S.

From this point, the cor. of secs. 1, 2, 35 and 36, on
the S. bdy. of the Tp., bears S. $0^{\circ}06'$ E., 80.30 chs.
dist., monumented with an iron post, 2 ins. diam., firmly
set, projecting 12 ins. above ground, with brass cap mkd.
as described in the official record of the 1917 resurvey
of the S. bdy. of T. 43 S., R. 1 E.

The control line was fully retraced, and no evidence of
the intervening corner was found.

N. $0^{\circ}04'$ W., bet. secs. 25 and 26.

Over gentle rolling desert land, through scattering
undergrowth; along fence line.

103

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 43 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS

30.00 Trail road, bears E and W.

40.15 Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 43 S R 1 E

$$\begin{array}{c} \frac{1}{4} \\ | \\ \text{S 26} \quad | \quad \text{S 25} \\ | \\ 1976 \end{array}$$

Cor. is located in fence line, bearing N and S.

Desc. over gradual NE slope.

54.00 Top of spur, slopes NE; desc. over gradual NW slope.

80.30 Point for the cor. of secs. 23, 24, 25, and 26, determined latitudinally by proportionate distance and longitudinally by a fence line bearing N and S. There is no remaining evidence of the original monument.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, $3\frac{1}{2}$ ft. base, to top of brass cap, mkd.

T 43 S R 1 E

$$\begin{array}{c} \text{S 23} \quad | \quad \text{S 24} \\ \text{S 26} \quad | \quad \text{S 25} \end{array}$$

1976

Point for the cor. of secs. 19, 24, 25, and 30, is reestablished from a tie made to the $\frac{1}{4}$ sec. cor. of secs. 25 and 30, and the $\frac{1}{4}$ sec. cor. of secs. 19 and 24, Tps. 43 S., Rs. 1 E., and 1 W., by proportionate measurement. There is no remaining evidence of the iron post, monumented in the 1917 resurvey of the E. bdy. of T. 43 S., R. 1 E.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 43 S
R 1 E R 2 E
$$\begin{array}{c} \text{S 24} \quad | \quad \text{S 19} \\ \text{S 25} \quad | \quad \text{S 30} \end{array}$$

1976

Deposit a piece of concrete, 6 ins. diam., 14 ins. long, alongside the iron post.

From this point, the $\frac{1}{4}$ sec. cor. of secs. 25 and 30, Tps. 43 S., Rs. 1 E. and 1 W., bears South, 40.00 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, and the $\frac{1}{4}$ sec. cor. of secs. 19 and 24, bears North, 40.00 chs. dist., monumented with an iron post, 1 in. diam., firmly set, pro-

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 43 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS	
<p>40.15</p>	<p>jecting 10 ins. above ground, with brass caps mkd. as described in the official record of the 1917 resurvey of the E. bdy. of T. 43 S., R. 1 E.</p> <p>N. 89°38' W., bet. secs. 24 and 25.</p> <p>Over gentle rolling desert land, through scattering undergrowth.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 43 S R 1 E</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S\ 24}{S\ 25}$</p> <p style="text-align: center;">1976</p>
45.80	Trail road, bears N. 10° E. and S. 10° W.
80.30	The cor. of secs. 23, 24, 25, and 26.
<p>30.00</p> <p>40.15</p>	<p>N. 0°04' W., bet. secs. 23 and 24.</p> <p>Over rolling desert land, through scattering juniper, pinon and undergrowth; desc. over NW slope.</p> <p>Slope changes; thence along W slope.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 43 S R 1 E</p> <p style="text-align: center;">$\frac{1}{4}$</p> <p style="text-align: center;">S 23 S 24</p> <p style="text-align: center;">1976</p>
64.00	Slope changes; desc. over N slope; leave scattered timber.
78.03	Cor. of fence line, with fences bearing S. 0°04' E. and N. 44°41' W.
80.30	<p>Point for the cor. of secs. 13, 14, 23, and 24, determined latitudinally by proportionate distance and longitudinally by the extension of the fence line to the South; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

105

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 43 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS						
	<p style="text-align: center;">T 43 S R 1 E</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 14</td> <td style="padding: 0 5px;">S 13</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 23</td> <td style="padding: 0 5px;">S 24</td> </tr> </table> <p style="text-align: center;">1976</p>	S 14	S 13	S 23	S 24	
S 14	S 13					
S 23	S 24					
	<p>From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. as described in the official record of the 1917 resurvey of the E. bdy. of T. 43 S., R. 1 E.</p> <p>N. 89°26' W., bet. secs. 13 and 24.</p> <p>Over rolling desert land, through scattering undergrowth; asc. over NE slope.</p> <p>11.00 Slope changes; asc. over E slope.</p> <p>35.00 Top of spur, slopes NE; desc. over NW slope.</p> <p>40.20 Point for the ¼ sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 43 S R 1 E</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">¼</td> <td style="padding: 0 5px;">S 13</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">S 24</td> </tr> </table> <p style="text-align: center;">1976</p> <p>Desc. over NW slope, through scattering juniper and pinon.</p> <p>62.00 Slope changes; desc. along N slope; leave timber.</p> <p>71.30 Trail road, bears NW and SE.</p> <p>80.40 The cor. of secs. 13, 14, 23, and 24.</p>	¼	S 13		S 24	
¼	S 13					
	S 24					
	<p>N. 0°40' W., bet. secs. 13 and 14.</p> <p>Over broken land, through scattering undergrowth; desc. over N slope.</p> <p>15.50 Trail road, bears NW and SE.</p> <p>40.15 Point for the ¼ sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p>					

001

Dependent Resurvey of a portion of the Subdivisional Lines, T. 43 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS	
	<p style="text-align: center;">T 43 S R 1 E $\frac{1}{4}$ S 14 S 13 1976</p> <p>Desc. over broken NW slope.</p> <p>63.00 Slope changes; desc. over N slope.</p> <p>80.30 Point for the cor. of secs. 11, 12, 13, and 14, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 43 S R 1 E S 11 S 12 S 14 S 13 1976</p> <p>Set a pine post, 4 ft. long, projecting 3 ft. above ground.</p>
	<p>From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. as described in the official record of the 1917 resurvey of the E. bdy. of T. 43 S., R. 1 E.</p> <p>N. 89°53' W., bet. secs. 12 and 13.</p> <p>Over broken land, through scattering juniper, pinon and undergrowth; along N slope.</p> <p>6.00 Slope changes; desc. over NW slope.</p> <p>41.06 Point for the ¼ sec. cor. of secs. 12 and 13, at proportionate distance, falls near edge of sandstone ledge and is unsafe to monument.</p> <p>Desc. along ledgy S slope of spur.</p> <p>47.22 The witness ¼ sec. cor. of secs. 12 and 13, mkd. with a large X ¼ WC chiseled on flat sandstone surface of ledge.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., over X and in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">W C T 43 S R 1 E $\frac{1}{4}$ S 12 S 13 1976</p>

Dependent Resurvey of a portion of the Subdivisional Lines, T. 43 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS	
<p>2.00</p> <p>20.00</p> <p>34.12</p>	<p>N. 88°29' W., beginning new measurement.</p> <p>Desc. over SW slope.</p> <p>Bottom of draw, drains NW; thence along broken N slope over series of small draws and spurs.</p> <p>Thence along gradual N slope.</p> <p>The cor. of secs. 11, 12, 13, and 14.</p>
<p>40.15</p> <p>80.30</p>	<p>N. 0°42' E., bet. secs. 11 and 12.</p> <p>Over rolling desert land, through scattering undergrowth; desc. over gradual N slope.</p> <p>Point for the ¼ sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 43 S R 1 E</p> <p> </p> <p> ¼</p> <p> </p> <p>S 11 S 12</p> <p> </p> <p> 1976</p> </div> <p>Set a cedar post, 5 ft. long, projecting 3½ ft. above ground.</p> <p>Continue over gradual N slope.</p> <p>The cor. of secs. 1, 2, 11 and 12, monumented with a charred cedar post, loosely set, projecting 18 ins. above ground, mkd. 1 notch on E and 5 notches on S edge.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 43 S R 1 E</p> <p> </p> <p> S 2 S 1</p> <p> S 11 S 12</p> <p> </p> <p> 1976</p> </div> <p>Deposit the charred cedar post alongside and set a cedar post, 5 ft. long, projecting 3 ft. above ground.</p>
	<p>From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. as described in the official record of the 1917 resurvey of the E. bdy. of T. 43 S., R. 1 E.</p> <p>N. 89°02' W., bet. secs. 1 and 12.</p>

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 43 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS	
	Over gentle rolling desert land, through scattering undergrowth.
28.50	Dirt road, bears NW and SE.
40.19	The ¼ sec. cor. of secs. 1 and 12, monumented with a sandstone, 12 x 10 x 3 ins., firmly set, projecting 5 ins. above ground, mkd. ¼ on N face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 43 S R 1 E
	$\frac{1}{4} \begin{array}{c} \text{S 1} \\ \text{S 12} \end{array}$
	1976
	Deposit the mkd. stone alongside the iron post.
	N. 89°02' W., beginning new measurement.
	Over gentle rolling desert land.
40.19	The cor. of secs. 1, 2, 11, and 12.
	N. 0°42' E., bet. secs. 1 and 2.
	Over rolling desert land, through scattering undergrowth.
13.38	Fence line, 4 strand, bears N. 80°55' W. and S. 80°55' E.
15.49	U. S. Highway No. 89A, bears N. 80°55' W. and S. 80°55' E.
19.43	Fence line, 4 strand, bears N. 80°55' W. and S. 80°55' E.
19.46	Power line, 3 strand, bears same as fence line.
21.00	Dirt road, bears NW and SE.
40.15	Point for the ¼ sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 43 S R 1 E
	$\frac{1}{4} \begin{array}{c} \\ \text{S 2} \quad \quad \text{S 1} \\ \end{array}$
	1976
	From this point, a re-bar, bears E, 0.608 chs. dist., with cap mkd.

Dependent Resurvey of a portion of the Subdivisional Lines, T. 43 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS						
	<div style="text-align: center;"> <table border="1"> <tr><td>28</td></tr> <tr><td>27</td></tr> </table> D </div> <p>Also fence line, bearing N. 1°30' W. and S. 1°30' E., bears E, 2.708 chs. dist.</p> <p>Continue over gentle rolling land.</p>	28	27			
28						
27						
72.00	Trail road, bears NE and SW.					
79.35	Fence line, bearing E and W.					
80.30	The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., heretofore described.					
	<p>From the cor. of secs. 13, 14, 23, and 24.</p> <p>N. 89°47' W., bet. secs. 14 and 23.</p> <p>Over broken desert land, through scattering undergrowth; along N slope.</p>					
2.25	Fence line, 4 strand, bears N. 44°41' W. and S. 44°41' E.					
20.00	Slope changes; desc. over NW slope.					
41.07	Point for the ¼ sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original corner.					
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 43 S R 1 E</p> <div style="text-align: center;"> <table border="1"> <tr><td>¼</td><td>S 14</td></tr> <tr><td></td><td>S 23</td></tr> </table> </div> <p style="text-align: center;">1976</p>	¼	S 14		S 23	
¼	S 14					
	S 23					
	Desc. over W slope.					
60.00	Small wash in bottom of draw, drains N; asc. over NE slope.					
66.00	Top of spur, slopes N; desc. over NW slope.					
72.00	Bottom of draw, drains N; asc. over E slope.					
82.14	The cor. of secs. 14, 15, 22, and 23, monumented with a sandstone, 14 x 12 x 6 ins., set in a scattered mound of stone and dimly mkd. 2 notches on E edge.					
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 43 S R 1 E</p> <div style="text-align: center;"> <table border="1"> <tr><td>S 15</td><td>S 14</td></tr> <tr><td>S 22</td><td>S 23</td></tr> </table> </div> <p style="text-align: center;">1976</p>	S 15	S 14	S 22	S 23	
S 15	S 14					
S 22	S 23					

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 43 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS	
	Deposit the dimly mkd. stone alongside and raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.
	N. 0°42' E., bet. secs. 14 and 15.
	Over broken desert land, through scattering undergrowth; desc. along E slope.
3.00	Slope changes; desc. over N slope.
14.00	Bottom of draw, drains NE; asc. over SE slope.
21.00	Top of spur, slopes NE; desc. along broken E slope.
36.00	Top of low spur, slopes E; desc. over NE slope.
40.03	Point for the ¼ sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> <p>T 43 S R 1 E</p> <p> </p> <p> ¼</p> <p> </p> <p>S 15 S 14</p> <p> </p> <p> 1976</p> </div>
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.
40.50	Bottom of descent, drains E; asc. over SW slope.
52.00	Top of spur, slopes E; desc. over gradual N slope.
68.00	Top of spur, slopes E; desc. over NE slope.
80.06	The cor. of secs. 10, 11, 14, and 15, at intersection of barbed wire fences extending N. 12° E., W and SE. This position is harmoniously related with identified existing original cors. in the area, and is accepted as the best available evidence of the original cor. position.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> <p>T 43 S R 1 E</p> <p> </p> <p>S 10 S 11</p> <p>S 15 S 14</p> <p> </p> <p> 1976</p> </div>
	From the cor. of secs. 11, 12, 13, and 14. N. 89°57' W., bet. secs. 11 and 14. Over rolling desert land, through scattering undergrowth; along N slope.

111

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 43 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS	
29.00	Trail road, bears NW and SE.
40.12	Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 43 S R 1 E
	$\frac{1}{4}$ $\frac{S 11}{S 14}$
	1976
	Set a cedar post, 4 ft. long, projecting 2 ft. above ground.
	Continue along N slope.
58.00	Wash in bottom of draw, drains N; asc. over gradual NE slope.
80.24	The cor. of secs. 10, 11, 14, and 15.
	N. $0^{\circ}36'$ E., bet. secs. 10 and 11.
	Over rolling desert land, through scattering undergrowth; desc. over gentle NE slope.
3.00	Small wash in bottom of draw, drains NE; asc. over SE slope.
10.00	Top of spur, slopes NE; desc. over gradual N slope.
40.27	Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 43 S R 1 E
	$\frac{1}{4}$ S 10 S 11
	1976
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W of cor.
	Continue over gradual N slope.
80.54	Point for the cor. of secs. 2, 3, 10, and 11, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 43 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS					
	<p style="text-align: center;">T 43 S R 1 E</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 3</td> <td style="padding: 0 5px;">S 2</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 10</td> <td style="padding: 0 5px;">S 11</td> </tr> </table> <p style="text-align: center;">1976</p> <p>Set a cedar post, 4 ft. long, projecting 2 ft. above ground, alongside the iron post.</p>	S 3	S 2	S 10	S 11
S 3	S 2				
S 10	S 11				
	<p>From the cor. of secs. 1, 2, 11, and 12.</p> <p>N. 89°48' W., bet. secs. 2 and 11.</p> <p>Over gentle rolling desert land, through scattering undergrowth.</p>				
19.00	Small wash, drains NE.				
40.19	Point for the ¼ sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original corner.				
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 43 S R 1 E</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 0 5px;">¼</td> <td style="border-right: 1px solid black; padding: 0 5px;">S 2</td> <td style="padding: 0 5px;">S 11</td> </tr> </table> <p style="text-align: center;">1976</p>	¼	S 2	S 11	
¼	S 2	S 11			
51.50	Trail road, bears N. 20° E. and S. 20° W.				
63.20	Fence line, 4 strand, bears N. 12° E. and S. 12° W.				
80.38	The cor. of secs. 2, 3, 10, and 11.				
	<p>N. 0°52' E., bet. secs. 2 and 3.</p> <p>Over gentle rolling desert land, through scattering undergrowth.</p>				
25.49	Telephone line, 2 wire, bears N. 80°55' W. and S. 80°55' E.				
25.89	Fence line, 4 strand, parallels highway.				
28.01	U.S. Highway No. 89A, 55 lks. wide, bears N. 80°55' W. and S. 80°55' E.				
31.97	Fence line, 4 strand, parallels highway.				
32.00	Power line, 3 strand, bears N. 80°55' W. and S. 80°55' E.				
40.00	Dirt road, bears E and W.				
40.27	Point for the ¼ sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.				
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>				

Dependent Resurvey of a portion of the Subdivisional Lines, T. 43 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS	
	<p style="text-align: center;">T 43 S R 1 E $\frac{1}{4}$ S 3 S 2 1976</p> <p>Raise a mound of stone, 3½ ft. base, 1½ ft. high, W of cor.</p>
53.00	Trail road, bears NW and SE.
78.88	Fence line, 4 strand, bears E and W.
80.54	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., heretofore described.
	<p>From the cor. of secs. 10, 11, 14, and 15. N. 89°21' W., bet. secs. 10 and 15. Over rolling desert land, through scattering undergrowth. Along gentle N slope.</p>
4.00	Bottom of draw, drains NE; asc. over SE slope.
18.00	Top of spur, projects NE; desc. over gradual NW slope.
40.14	The ¼ sec. cor. of secs. 10 and 15, monumented with a sandstone, 16 x 10 x 8 ins., firmly set, projecting 6 ins. above ground, mkd. ¼ on N face.
	<p>At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 43 S R 1 E $\frac{1}{4}$ $\frac{S 10}{S 15}$ 1976</p>
	<p>Deposit the mkd. stone alongside the iron post. Cor. is located in fence line which bears E and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°21' W., beginning new measurement. Over gentle rolling land.</p>
40.34	The cor. of secs. 9, 10, 15 and 16, marked by a charred cedar stake, 3 ft. long, squared on one end, mkd. 3 notches on E and 4 notches on S edge.
	<p>At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 43 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS					
	<p style="text-align: center;">T 43 S R 1 E</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 9</td> <td style="padding: 0 5px;">S 10</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 16</td> <td style="padding: 0 5px;">S 15</td> </tr> </table> <p style="text-align: center;">1976</p> <p>Deposit the mkd. stake alongside the iron post.</p> <p>Cor. is located in fence line which bears E and W.</p>	S 9	S 10	S 16	S 15
S 9	S 10				
S 16	S 15				
40.09	<p>N. 0°45' E., bet. secs. 9 and 10.</p> <p>Over gentle rolling desert land, through scattering undergrowth; desc. over gradual N slope.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>				
64.00	<p style="text-align: center;">T 43 S R 1 E</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 9</td> <td style="padding: 0 5px;">S 10</td> </tr> </table> <p style="text-align: center;">1976</p> <p>Deposit a rotted cedar stake, 18 ins. long, alongside the iron post.</p> <p>Desc. over gradual N slope.</p> <p>Slope changes; desc. over NW slope.</p>	S 9	S 10		
S 9	S 10				
80.18	<p>The cor. of secs. 9, 10, 15 and 16, monumented with a charred cedar stake, 3 ft. long, projecting 2 ft. above scattered mound of stone, mkd. 3 notches on E and 4 notches on S edge.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>				
	<p style="text-align: center;">T 43 S R 1 E</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 4</td> <td style="padding: 0 5px;">S 3</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 9</td> <td style="padding: 0 5px;">S 10</td> </tr> </table> <p style="text-align: center;">1976</p> <p>Deposit the mkd. stake alongside the iron post.</p>	S 4	S 3	S 9	S 10
S 4	S 3				
S 9	S 10				
	<p>From the cor. of secs. 2, 3, 10, and 11.</p> <p>N. 89°30' W., bet. secs. 3 and 10.</p> <p>Over nearly level desert land, through scattering undergrowth.</p>				

115

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 43 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS	
40.19	<p>The $\frac{1}{4}$ sec. cor. of secs. 3 and 10, monumented with a sandstone, 12 x 12 x 8 ins., firmly set, projecting 6 ins. above ground, mkd. $\frac{1}{4}$ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 43 S R 1 E</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S 3}{S 10}$</p> <p style="text-align: center;">1976</p> <p>Deposit the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. $89^{\circ}41'$ W., beginning new measurement.</p> <p>Asc. over gradual NE slope.</p>
25.00	Top of spur, slopes N; desc. over NW slope.
40.07	The cor. of secs. 3, 4, 9, and 10.
7.50	<p>N. $0^{\circ}54'$ E., bet. secs. 3 and 4.</p> <p>Over gentle rolling desert land, through scattering undergrowth; desc. over gradual NW slope.</p> <p>Wash, 20 lks. wide, 4 ft. deep, drains E; asc. over gradual S slope.</p>
37.84	Telephone line, 2 wire, bears N. $80^{\circ}55'$ W. and S. $80^{\circ}55'$ E.
38.23	Fence line, 4 strand, parallels highway.
39.78	<p>Point selected for the witness cor. to the $\frac{1}{4}$ sec. cor of secs. 3 and 4.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">W C T 43 S R 1 E $\frac{1}{4}$ ↑ S 4 S 3 1976</p>
40.09	<p>Deposit a sandstone, 14 x 12 x 6 ins., alongside the iron post.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4, at proportionate distance, falls on S edge of paved highway, U.S. Highway No. 89A, where it is impracticable to establish a permanent monument; there is no remaining evidence of the original corner.</p>

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 43 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS	
40.35	Center line of U.S. Highway 89A, 55 lks. wide, bears N. 80°55' W. and S. 80°55' E.
44.28	Fence line, 4 strand, parallels highway.
44.31	Power line, 3 strand, bears N. 80°55' W. and S. 80°55' E.
48.00	Top of low ridge, bears NE and SW; desc. over gradual N slope.
68.00	Trail road, bears E and W.
79.56	Fence line, 4 strand, bears N. 87° E. and S. 87° W.
80.18	The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., heretofore described.
	From the cor. of secs. 9, 10, 15, and 16.
	N. 89°27' W., bet. secs. 9 and 16.
	Over rolling desert land, through scattering undergrowth; along gradual N slope.
24.00	Spur, slopes NW; desc. over W slope.
31.00	Wash, 20 lks. wide, 2 ft. deep, drains N; asc. over E slope.
38.25	Top of spur, slopes N; desc. over W slope.
40.10	The ¼ sec. cor. of secs. 9 and 16, monumented with a sandstone, 18 x 10 x 3 ins., firmly set, projecting 8 ins. above ground, mkd. ¼ on N face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 43 S R 1 E
	¼ $\frac{S 9}{S 16}$
	1976
	Deposit the mkd. stone alongside the iron post.
	Cor. is located 6 lks. S of fence line, bearing N. 89°23' W. and S. 89°23' E.
	N. 89°16' W., beginning new measurement.
	Desc. over W slope.
2.00	Bottom of draw, drains N; asc. over E slope.
5.00	Top of spur, slopes N; thence along gradual N slope.

117

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 43 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS	
40.11	<p>The cor. of secs. 8, 9, 16, and 17, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. as described in the official record of the 1917 resurvey of a portion of the subdivisional lines of T. 43 S., R. 1 E.</p> <p>Cor. is located in fence line, bearing E and W.</p> <p>From the cor., U.S.G.S triangulation station "1/4 Cor Sec. 8" at Latitude 37°04'42.20" N., Longitude 111°49'25.7" W., bears N. 89°27" W., 40.10 chs. dist., monumented with an iron post 1 in. diam., projecting 10 ins. above ground with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ S 8 1917 </p>
26.50	<p>N. 0°47' E., bet. secs. 8 and 9.</p> <p>Over gentle rolling desert land, through scattering undergrowth; desc. over gradual N slope.</p> <p>Wash, drains northeasterly.</p>
39.89	<p>Point for the 1/4 sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T 43 S R 1 E 1/4 S 8 S 9 1976 </p> <p>Deposit a sandstone, 10 x 10 x 6 ins., alongside the iron post.</p>
79.78	<p>Point for the cor. of secs. 4, 5, 8 and 9, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T 43 S R 1 E S 5 S 4 S 8 S 9 1976 </p> <p>Set a steel pipe, 2 1/2 ins. diam., 3 ft. long, alongside the iron post, projecting 12 ins. above ground.</p>
	<p>From the cor. of secs. 3, 4, 9, and 10.</p> <p>N. 89°42' W., bet. secs. 4 and 9.</p>

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 43 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS	
	Over rolling desert land, through scattering undergrowth; desc. over W slope.
8.00	Wash, 30 lks. wide, 2 ft. deep, drains NE; asc. over SE slope.
22.00	Top of ascent, slopes gradually NE; thence over gentle rolling land.
40.07	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 43 S R 1 E
	$\frac{1}{4}$ $\frac{S 4}{S 9}$
	1976
	Deposit a sandstone, 20 x 12 x 4 ins., and set a steel pipe, 1 in. diam., 18 ins. long, projecting 6 ins. above ground, alongside iron post.
	Thence along gradual N slope.
80.14	The cor. of secs. 4, 5, 8, and 9.
	N. $0^{\circ}37'$ E., bet. secs. 4 and 5.
	Over gentle rolling desert land, through scattering undergrowth; asc. over gradual S slope.
8.50	Top of rise, bears E and W; desc. over gradual N slope.
39.89	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 43 S R 1 E
	$\frac{1}{4}$ S 5 S 4
	1976
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W of cor.
50.05	Telephone line, 2 strand, bears N. $80^{\circ}55'$ W. and S. $80^{\circ}55'$ E.
50.45	Fence line, 4 strand, parallels highway.
53.15	U.S. Highway 89A, 55 lks. wide, bears N. $80^{\circ}55'$ W. and S. $80^{\circ}55'$ E.
56.55	Fence line, 4 strand, parallels highway.

Dependent Resurvey of a portion of the Subdivisional Lines, T. 43 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS	
56.58	Power line, 3 strand, bears N. 80°55' W. and S. 80°55' E.
70.00	Trail road, bears E and W.
71.00	Wash, drains E.
77.83	Fence line, 4 strand, bears E and W.
79.78	The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., heretofore described.
<p>From the cor. of secs. 7 and 8, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. as described in the official record of the 1917 resurvey of a portion of the subdivisional lines of T. 43 S., R 1 E.</p>	
<p>N. 0°52' E., bet. secs. 7 and 8.</p>	
<p>Over nearly level desert land, through scattering undergrowth.</p>	
0.03	Fence line, 4 strand, bears E and W.
3.00	Dirt road, bears NW and SE.
40.04	<p>Point for the ¼ sec. cor. of secs. 7 and 8, at proportionate distance; there is no remaining evidence of the original corner.</p>
<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	
<p style="text-align: center;">T 43 S R 1 E ¼ S 7 S 8 1976</p>	
<p>Set a cottonwood post, 3 ft. long, projecting 12 ins. above ground, alongside the iron post.</p>	
<p>Asc. over gradual S slope.</p>	
64.20	Top of ascent, bears E and W; desc. over gradual N slope.
80.08	<p>Point for the cor. of secs. 5, 6, 7 and 8, at proportionate distance; there is no remaining evidence of the original corner.</p>
<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	
<p style="text-align: center;">T 43 S R 1 E S 6 S 5 S 7 S 8 1976</p>	
<p>Set a steel fence post, 4 ft. long, projecting 2 ft. above ground, alongside the iron post.</p>	

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 43 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS	
40.07	<p>From the cor. of secs. 4, 5, 8, and 9.</p> <p>N. 89°12' W., bet. secs. 5 and 8.</p> <p>Over gentle rolling desert land, through scattering undergrowth.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 43 S R 1 E</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S 5}{S 8}$</p> <p style="text-align: center;">1976</p> <p>Deposit a sandstone, 16 x 12 x 8 ins., alongside the iron post.</p>
80.14	<p>The cor. of secs. 5, 6, 7, and 8.</p>
37.80	<p>N. 89°25' W., bet. secs. 6 and 7.</p> <p>Over nearly level desert land, through scattering undergrowth.</p> <p>Trail road, bears NW and SE.</p>
40.07	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 43 S R 1 E</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S 6}{S 7}$</p> <p style="text-align: center;">1976</p> <p>Set a cedar post, 5 ft. long, projecting 3 ft. above ground, alongside the iron post.</p> <p>Asc. over gradual E slope.</p>
64.60	<p>Top of ascent, bears NW and SE; desc. over gradual W slope.</p>
79.80	<p>Wash in bottom of draw, drains SW; asc. over SE slope.</p>
80.54	<p>The cor. of secs. 6 and 7, W. bdy. of T. 43 S., R. 1 E., hereinbefore described.</p>
	<p>From the cor. of secs. 5, 6, 7, and 8.</p> <p>N. 0°04' E., bet. secs. 5 and 6.</p>

Dependent Resurvey of a portion of the Subdivisional Lines, T. 43 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS		
	Over gentle rolling desert land, through scattering undergrowth.	
29.00	Wash, drains NE.	
40.04	Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.	
	<p>T 43 S R 1 E</p> <p style="margin-left: 100px;">1/4</p> <p style="margin-left: 80px;"> </p> <p style="margin-left: 80px;">S 6 S 5</p> <p style="margin-left: 100px;"> </p> <p style="margin-left: 100px;">1976</p>	
	Set a squared post, 3 ft. long, projecting 1 ft. above ground, alongside the iron post.	
	Desc. over gradual N slope.	
41.00	Small wash, drains NE.	
61.76	Telephone line, 2 strand, bears N. 80°55' W. and S. 80°55' E.	
62.15	Fence line, 4 strand, parallels highway.	
64.28	U.S. Highway No. 89A, 55 lks. wide, bears N. 80°55' W. and S. 80°55' E.	
68.25	Fence line, 4 strand, parallels highway.	
68.29	Power line, 3 strand, bears N. 80°55' W. and S. 80°55' E.	
75.00	Trail road, bears E and W.	
76.97	Fence line, 4 strand, bears E and W.	
80.08	The cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the Tp., heretofore described.	
General Description		
<p>Township 43 South, Range 1 East, is located on East Clark Bench about 3 miles west of Glen Canyon City. The elevation varies from 4,400 to 4,800 ft. above sea level. The soil is mostly sandy to sandy loam in the north and east portions of the township.</p> <p>Access is by way of U.S. Highway No. 89A, which crosses through the north tier of sections, with a few trail roads extending into the southern portion of the township.</p> <p>The principle use of the area surveyed is livestock grazing. The only improvements noted was the small settlement of Church Wells located in section 2.</p>		

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 43 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS

This portion of the township is mostly rolling sandy hills with scattered undergrowth of bunch grass, brigham tea and cacti.

The average number of readings throughout the area surveyed gives a mean magnetic declination of $14^{\circ}15'$ E.

Form 9180-8
(March 1969)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Craig P. Sylvester	Supervisory Cadastral Surveyor
Ferrel D. Reynolds	Surveying Technician
Gail E. Reynolds	Surveying Technician
Stewart Burt	Surveying Technician
Daniel Mates	Surveying Technician
Frank Profaizer	Surveying Technician
Donald Buhler	Surveying Technician

[Handwritten signature]

APR 1969

Acting Chief, Bureau of Land Management and Approval

FOR THE DIRECTOR

CERTIFICATE OF SURVEY

(I) ~~(WXX)~~ Jerry L. Thomas, ~~Surveyor~~, ~~of the State of Utah~~, ~~do hereby~~ HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 7th day of January 1976, I ~~(WXX)~~ have dependently resurveyed a portion of the Salt Lake Meridian along the west boundary, the north boundary and a portion of the subdivisional lines of T. 43 S., R. 1 E.,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

March 11, 1977
(Date)

Jerry L. Thomas
(Cadastral Surveyor)
Supervisory

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Washington, D.C.
Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the Salt Lake Meridian along the west boundary, the north boundary, and a portion of the subdivisional lines of T. 43 S., R. 1 E., Salt Lake Meridian, Utah

executed by Jerry L. Thomas, Supervisory Cadastral Surveyor having been critically examined and found correct, are hereby approved.

JAN 16 1980
(Date)

Alan S. Arnold
(Chief, Division of Cadastral Survey)
Acting Chief, Cadastral Survey Examination and Approval Staff

CERTIFICATE OF TRANSCRIPT

I CERTIFY that the foregoing transcript of the field notes of the above described surveys is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey)

R599

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

125

ORIGINAL
FIELD NOTES

OF THE
DEPENDENT RESURVEY

OF THE

EAST BOUNDARY

AND

A PORTION OF THE NORTH BOUNDARY

AND

A PORTION OF THE SUBDIVISIONAL LINES

OF

TOWNSHIP 19 SOUTH, RANGE 8 EAST

Of the Salt Lake Meridian,

In the State of Utah

EXECUTED BY

Glen B. Hatch Supervisory Cadastral Surveyor

Under special instructions dated May 6, 1975, approved May 7, 1975,

_____, which provided for the surveys included under U.S. Survey/Group
Number 559, and assignment instructions dated October 31, 1975.

Survey commenced November 10, 1975

Survey completed December 10, 1975

INDEX DIAGRAM

Township 19 S., Range 8 E.

						7
6	5	4	3	2	15	1 6
34				14		13
7	33 8	9	10	11	13	12 5
32				20		12
18	32 17	16	15	19 14	12	13 4
31	31	27	24	19		11
19	30 20	26 21	23 22	18 28	10	24 3
	29	26	23	18		10
30	29	25 28	22 27	17 26	9	25 3
29	29	25	21	16		9
31	28 32	24 33	21 34	15 35	8	36 2

Dependent Resurvey of T. 19 S., R. 8 E., Salt Lake Mer., Utah

CHAINS

The history of surveys of Township 19 South, Range 8 East, Salt Lake Meridian, Utah, is as follows:

T. 19 S., R. 8 E.

History of Surveys

<u>Surveyed by</u>	<u>Retr. or Resurveyed by</u>
--------------------	-------------------------------

EAST BOUNDARY

N. 3 mi.	A. D. Ferron	1880
S. 3 mi.	A. D. Ferron	1882

SOUTH BOUNDARY

W. 3½ mi.	A. D. Ferron	1873	
E. 2½ mi.	A. D. Ferron	1882	
All			Glen B. Hatch 1962

WEST BOUNDARY (Second Guide Meridian East)

All	A. D. Ferron	1873	
W. bdy., secs. 7 and 18			J. W. Dougall 1911
Portion			J. L. Thomas, concurrently

NORTH BOUNDARY

All	A. D. Ferron	1873
-----	--------------	------

SUBDIVISIONS

NW Portion	A. D. Ferron	1873
SE portion	A. D. Ferron	1882
Portion		A. D. Ferron 1882

The following field notes describe the dependent resurvey of the east boundary, a portion of the north boundary, and a portion of the subdivisional lines of the township.

The survey was executed in accordance with specification set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 559, Utah, dated May 6, 1975.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The direction of the lines were determined by reference to the true meridian established on line by hour angle observations on Polaris. The lines were carried forward by sustained angulation being supplemented by other hour angle observations on Polaris taken throughout the progress of the resurvey. Measurements were made by Electronic Telemetry.

The geographic position of the southeast corner of the township, as computed from section line ties to U.S.C. and G.S. triangulation station "Buckhorn", located N. 54°09' W., 35.426 chs. distance from the 1/4 sec. cor.

Dependent Resurvey of T. 19 S., R. 8 E., Salt Lake Mer., Utah

CHAINS

of secs. 5 and 32, Tps. 18 and 19 S., R. 9 E., is as follows:

Latitude 39°07'08" N. Longitude 110°57'41" W.

The mean magnetic declination is 14°45' E.

Dependent Resurvey of the E. Bdy. of T. 19 S., R. 8 E.,
Salt Lake Meridian, Utah
(Restoring the 1882 survey by A. D. Ferron)

Beginning at the cor. of Tps. 19 and 20 S., Rs. 8 and 9 E. monumented with an iron post, 2½ ins. diam., extending 20 ins. above ground and in a mound of stone, with brass cap mkd.

T 19 S
R 8 E R 9 E
S 36 S 31
S 1 S 6
T 20 S
1962

N. 0°54' W., bet. secs. 31 and 36.

Over broken land, through shadscale undergrowth.

38.10 Ferron Creek, 30 lks. wide, 5 ft. deep, flows East; enter tamarack and willow undergrowth.

40.06 Point for the ¼ sec. cor. of secs. 31 and 36, at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with cottonwood post, 4 ins. diam., 5 ft. long, alongside, with brass cap mkd.

T 19 S
R 8 E R 9 E
¼
S 36 S 31
1975

Cor. is located on the left bank of Ferron Creek, 30 lks. wide, flowing West from E and SE.

45.10 Ferron Creek, 40 lks. wide, flows SE from NW; leave tamarack and willow undergrowth; asc. SE slope.

64.30 Rim of bench above Ferron Creek, bears NE and SW; thence over rolling bench land.

80.12 The cor. of secs. 25, 30, 31 and 36, monumented with a sandstone, 20 x 6 x 6 ins., set in a mound of stone, and plainly mkd. 1 notch on S and 5 notches on N edges.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base to top, with brass cap mkd.

Dependent Resurvey of E. Bdy. of
T. 19 S., R. 8 E., Salt Lake Mer., Utah

CHAINS

T 19 S
R 8 E R 9 E
S 25 | S 30
S 36 | S 31
1975

Deposit the mkd. stone in mound of stone alongside the iron post.

N. 0°41' W., bet. secs. 25 and 30.

Over gently rolling desert bench land through shadscale undergrowth.

40.44 The $\frac{1}{4}$ sec. cor. of secs. 25 and 30, monumented with a sandstone, 14 x 8 x 3 ins., set 3 ins. in the ground, and mkd. $\frac{1}{4}$ on W face.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 19 S
R 8 E R 9 E
 $\frac{1}{4}$
S 25 | S 30
|
1975

Deposit the mkd. stone alongside the iron post.

N. 0°42' W., beginning new measurement.

40.39 Point for the cor. of secs. 19, 24, 25 and 30, at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 19 S
R 8 E R 9 E
S 24 | S 19
S 25 | S 30
1975

N. 0°42' W., bet. secs. 19 and 24.

Over gently rolling desert bench land through scattered shadscale undergrowth.

40.39 Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 24, at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of E. Bdy. of
T. 19 S., R. 8 E., Salt Lake Mer., Utah

CHAINS		
80.78	<p style="text-align: center;">T 19 S R 8 E R 9 E 1/4 S 24 S 19 1975</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.</p> <p>The cor. of secs. 13, 18, 19 and 24, monumented with a sandstone, 16 x 7 x 6 ins., firmly set 6 ins. in the ground, and plainly mkd. 3 notches on N and S edges.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 19 S R 8 E R 9 E S 13 S 18 S 24 S 19 1975</p> <p>Deposit the mkd. stone alongside the iron post.</p>	
11.50 12.50 41.67 50.00 51.00 70.00 83.34	<p style="text-align: center;">Reestablishment of the survey executed by A. D. Ferron, in 1880</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°38' W., bet. secs. 13 and 18.</p> <p>Desc. over gently rolling desert land through scattered shadscale and sagebrush undergrowth.</p> <p>Rock Canyon Creek, 15 lks. wide, 12 ins. deep, flows E.</p> <p>Enter cultivated land, bears E and W.</p> <p>Point for the ¼ sec. cor. of secs. 13 and 18, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 19 S R 8 E R 9 E 1/4 S 13 S 18 1975</p> <p>Leave cultivated land, bears nearly E and W.</p> <p>Farm road, bears S. 80° W. and curves N. 60° E.; asc. broken SE slope.</p> <p>Rim of bench, bears E and W; thence over nearly level land.</p> <p>The cor. of secs. 7, 12, 13 and 18, monumented with a sandstone, 36 x 14 x 6 ins., set in mound of stone, and plainly mkd. 4 notches on S and 2 on N edges.</p>	

Dependent Resurvey of E. Bdy. of
T. 19 S., R. 8 E., Salt Lake Mer., Utah

CHAINS

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 19 S
R 8 E R 9 E
S 12 | S 7
S 13 | S 18
1975

Deposit the mkd. stone alongside the iron post.

N. 2°19' E., bet. secs. 7 and 12.

Over rolling bench land through shadscale undergrowth.

21.50 Graded dirt road, bears E and curves SW to Castle Dale.

36.78 The ¼ sec. cor. of secs. 7 and 12, monumented with a sandstone, 20 x 14 x 4 ins., in small mound of stone, plainly mkd. ¼ on W face.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 19 S
R 8 E R 9 E
¼
S 12 | S 7
1975

Deposit the mkd. stone alongside the iron post.

N. 0°46' E., beginning new measurement.

23.00 Rim of bench, bears E and W; desc. abruptly about 80 ft. over precipitous N slope into box canyon.

30.00 Box canyon, drains E; asc. abruptly about 80 ft. over precipitous S slope.

36.00 Rim of box canyon, bears E and W; asc. gentle S slope.

39.00 Spur, slopes S. 25° E.

40.19 The cor. of secs. 1, 6, 7 and 12, monumented with a sandstone, 48 x 30 x 2 ins., in small mound of stone, mkd. 1 notch on N edge, and 5 notches on S edge.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd.

T 19 S
R 8 E R 9 E
S 1 | S 6
S 12 | S 7
1975

Dependent Resurvey of E. Bdy. of
T. 19 S., R. 8 E., Salt Lake Mer., Utah

CHAINS

Deposit the mkd. stone alongside the iron post.

N. 0°23' W., bet. secs. 1 and 6.

Over broken bench land through shadscale undergrowth.

14.00 Deep gulch, drains E.

23.00 Small draw, drains S. 60° E. from N, thence along E side of draw.

33.00 Small draw drains W about 1.50 chs. to draw draining S.

38.00 Point of low spur, slopes W.

40.13 The ¼ sec. cor. of secs. 1 and 6, monumented with a sandstone, 15 x 12 x 6 ins., in small mound of stone, plainly mkd. ¼ on W face.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 19 S
R 8 E R 9 E
¼
S 1 | S 6
1975

Deposit the mkd. stone alongside the iron post, and raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.

N. 2°33' W., beginning new measurement.

0.40 Small wash, drains W.

14.80 Rim of The Breaks, above Cottonwood Creek, bears N. 86° E. and S. 86° W.; desc. abruptly about 200 ft. over precipitous N slope.

19.00 Cottonwood Creek, 25 lks. wide, 18 ins. deep, flows E; thence over nearly level bottom land, enter cottonwood timber.

31.00 Leave timber, bears E and W.

35.00 Farm road, bears E and W.

40.00 The cor. of Tps. 18 and 19 S., Rs. 8 and 9 E., monumented with an iron post, 2½ ins. diam., extending 6 ins. above ground, with mound of stone to S, and brass cap mkd.

T 18 S
R 8 E R 9 E
S 36 | S 31
S 1 | S 6
T 19 S
R 8 E R 9 E
1970

Dependent Resurvey of a portion of N. Bdy.
T. 19 S., R. 8 E., Salt Lake Mer., Utah

CHAINS

Dependent Resurvey of a portion of N. Bdy.
T. 19 S., R. 8 E., Salt Lake Mer., Utah
(Restoring the 1873 survey by A. D. Ferron)

S. 89°48' W., bet. secs. 1 and 36.

Over broken land by traverse, topography scaled from
U.S.G.S. quadrangle map "Haden Holes", 7½' series, 1969.
Asc. abruptly about 125 ft. over ledgy point projecting S.

7.00 Top of ledgy point projects S; desc. abruptly 125 ft.
over sandstone ledge facing SW.

10.00 Farm road, at base of ledges, bears N. 43° W. and curves
E, thence along bottom land in Cottonwood Creek, enter
cottonwood timber and willows.

21.00 Cottonwood Creek, 20 lks. wide, 12 ins. deep, flows
S. 20° E. from N.

27.00 Cottonwood Creek, flows N. 75° E. from S. 75° W.

37.00 Cottonwood Creek, flows S. 85° E. from N. 85° W.

41.21 Point for the ¼ sec. cor. of secs. 1 and 36, at propor-
tionate dist.; there is no remaining evidence of the
original witness ¼ sec. cor. (Record -- 10.00 chs. North.)

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in
the ground, and in a collar of stone, with brass cap mkd.

T 18 S R 8 E
S 36
¼ S 1
T 19 S R 8 E
1975

Above cor. is located on steep N. slope, 50 lks. S of
Cottonwood Creek.

Continue by traverse.

59.00 Cottonwood Creek, flows Easterly from S. 30° W., enter
meadow land.

82.42 Point for the cor. of secs. 1, 2, 35 and 36, at cor. of
barb wire fences from S. 89°30' E., N. 89°30' W.,
N. 0°30' E. and an abandoned fence line from S. This
position is harmoniously related to existing original
cors. and is accepted as the best available evidence of
the position of the original cor. point.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in
the ground, with brass cap mkd.

T 18 S R 8 E
S 35 | S 36
S 2 | S 1
T 19 S R 8 E
1975

Dependent Resurvey of a portion of Subdivisional Lines
T. 19 S., R. 8 E., Salt Lake Mer., Utah

134

Dependent Resurvey of a portion of Subdivisional Lines
T. 19 S., R. 8 E., Salt Lake Mer., Utah

CHAINS

(Restoring the 1882 survey by A. D. Ferron)

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., in mound of stone, 3 ft. base, 2 ft. high, with brass cap mkd.

T 19 S R 8 E
S 35 | S 36
S 2 | S 1
T 20 S
1962

N. 1°07' W., bet. secs. 35 and 36.

Over broken desert land through shadscale undergrowth.

16.00 Ferron Creek, 25 lks. wide, 15 ins. deep, flows N. 55° E.; thence across bottom land through cottonwood timber.

27.00 Leave bottom land and timber; asc. broken SE slope.

33.30 Rim of bench, bears N. 60° E. and S. 60° W.; thence over rolling bench land.

40.14 The ¼ sec. cor. of secs. 35 and 36, monumented with a sandstone, 19 x 16 x 4 ins., firmly set in a mound of stone, not mkd. but accepted as the original cor.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 19 S R 8 E
¼
S 35 | S 36
1975

Deposit the mkd. stone alongside the iron post.

N. 0°52' W., beginning new measurement.

23.50 Peavine Wash, 10 lks. wide, 15 ins. deep, flows irregularly E.

35.50 West edge of knoll; desc. N slope.

40.28 The cor. of secs. 25, 26, 35 and 36, monumented with a sandstone, 16 x 10 x 5 ins., firmly set in a small mound of stone, and plainly mkd. 1 notch on S and E edges.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 19 S R 8 E
S 26 | S 25
S 35 | S 36
1975

Deposit the mkd. stone alongside the iron post.

Dependent Resurvey of a portion of Subdivisional Lines
T. 19 S., R. 8 E., Salt Lake Mer., Utah

481

CHAINS

	<p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., heretofore described.</p> <p>N. 89°07' W., bet. secs. 25 and 36.</p> <p>Over rolling bench land through scattered shadscale undergrowth.</p> <p>30.50 Wash, 20 lks. wide, 4 ft. deep, drains S.</p> <p>39.17 The ¼ sec. cor. of secs. 25 and 36, monumented with a sandstone, 14 x 12 x 10 ins., firmly set 6 ins. in the ground, plainly mkd. ¼ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 19 S R 8 E</p> <p> S 25</p> <p>¼ ———</p> <p> S 36</p> <p> 1975</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°03' W., beginning new measurement.</p>
<p>16.00</p>	<p>Spur, slopes S. 40° E.</p>
<p>40.41</p>	<p>The cor. of secs. 25, 26, 35 and 36.</p>
	<p>N. 0°32' W., bet. secs. 25 and 26.</p> <p>Over rolling desert land.</p> <p>38.82 Point for the ¼ sec. cor. of secs. 25 and 26, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 19 S R 8 E</p> <p> ¼</p> <p> </p> <p> S 26 S 25</p> <p> </p> <p> 1975</p> </div> <p>51.00 Wash, drains S. 50° E.; asc. SW slope.</p> <p>58.00 Rim of bench, curves SW and SE; thence over rolling bench land.</p> <p>77.64 The cor. of secs. 23, 24, 25 and 26, monumented with a sandstone, 15 x 10 x 2 ins., set 3 ins. in the ground, plainly mkd. 1 notch on E and 2 on S edges, and witnessed by a small mound of stone to W.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>

Dependent Resurvey of a portion of Subdivisional Lines
T. 19 S., R. 8 E., Salt Lake Mer., Utah

CHAINS		
	<p style="text-align: center;">T 19 S R 8 E S 23 S 24 S 26 S 25 1975</p> <p>Deposit the mkd. stone alongside the iron post.</p>	
	<p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., heretofore described.</p> <p>S. 87°38' W., bet. secs. 24 and 25.</p> <p>Over rolling desert bench land.</p> <p>13.00 Wash, drains S. 40° E.; asc. 200 ft. over broken SE slope.</p> <p>30.50 Rim of bench, bears N. 50° E. and S. 50° W.; desc. over bench land.</p> <p>39.71 Point for the ¼ sec. cor. of secs. 24 and 25, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T 19 S R 8 E ¼ S 24 S 25 1975</p> <p>41.00 Deep, rocky gulch, drains S.</p> <p>45.15 Narrow ledgy spur, slopes S. 40° W.</p> <p>49.00 Head of deep ledgy draw, drains S.</p> <p>79.42 The cor. of secs. 23, 24, 25 and 26.</p>	
	<p style="text-align: center;">(Restoring the 1873 survey by A. D. Ferron and the 1882 resurvey by A. D. Ferron)</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°55' W., bet. secs. 23 and 24.</p> <p>Over rolling bench land.</p> <p>41.67 Point for the ¼ sec. cor. of secs. 23 and 24, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 19 S R 8 E ¼ S 23 S 24 1975</p> <p>50.00 Wash, drains N. 50° E.</p>	

Dependent Resurvey of a portion of Subdivisional Lines
T. 19 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS	
65.00	Large flat spur, slopes N. 25° E.; desc. along W slope.
72.00	Small spur, slopes N. 60° W.
74.50	Small spur, slopes N. 70° W.
81.50	Small spur, slopes N. 45° W.
83.34	The cor. of secs. 13, 14, 23 and 24, monumented with a sandstone, 15 x 10 x 2 ins., firmly set 10 ins. in the ground and in a mound of stone, mkd. 1 notch on E and 3 notches on S edges. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd. <div style="text-align: center;"> T 19 S R 8 E S 14 S 13 S 23 S 24 1975 </div> Deposit the mkd. stone alongside the iron post.
	From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., heretofore described. S. 89°28' W., bet. secs. 13 and 24. Over rolling bench land.
10.00	Base of broken bench, bears N and S; asc. 150 ft. over broken E slope.
15.00	Point of ledge spur, slopes sharply S; desc. abruptly.
18.00	Narrow draw, drains N. 30° W.
21.00	Point of narrow spur, slopes N. 40° W.
22.50	Draw, 40 ft. deep, drains N. 40° W.
35.00	Draw, 50 ft. deep, drains N; asc. E slope.
38.30	Flat spur, slopes N.
39.87	Point for the ¼ sec. cor. of secs. 13 and 24, at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 3½ ft. base to top, with brass cap mkd. <div style="text-align: center;"> T 19 S R 8 E S 13 ¼ ——— S 24 1975 </div> Desc. over steep NW slope.
44.00	Draw, drains N.
46.00	Narrow spur, slopes N. 10° W.

Dependent Resurvey of a portion of Subdivisional Lines
T. 19 S., R. 8 E., Salt Lake Mer., Utah

CHAINS	
50.00	Wash, 25 lks. wide, 3 ft. deep, in draw, drains N.
71.15	Long flat spur, slopes N. 20° E.; desc. SW slope.
79.50	Small draw, drains NW curving W.
79.74	The cor. of secs. 13, 14, 23 and 24.
N. 0°08' W., bet. secs. 13 and 14.	
Over broken bench land.	
0.50	Small draw, drains W.
7.00	Spur, slopes N. 15° W.
25.00	Point of narrow spur, slopes N from S. 30° E.
39.83	Point for the ¼ sec. cor. of secs. 13 and 14, at proportionate dist.; there is no remaining evidence of the original cor.
Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.	
<p style="text-align: center;">T 19 S R 8 E $\frac{1}{4}$ S 14 S 13 1975</p>	
56.60	Rock Canyon Creek, 25 lks. wide, 12 ins. deep, flows E turning to SE.
79.66	Point for the cor. of secs. 11, 12, 13 and 14, at proportionate dist.; there is no remaining evidence of the original cor.
Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.	
<p style="text-align: center;">T 19 S R 8 E S 11 S 12 S 14 S 13 1975</p>	
(Restoring the 1882 survey by A. D. Ferron)	
From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., heretofore described.	
S. 86°48' W., bet. secs. 12 and 13.	
Over rolling bench land.	
38.50	Point of spur, slopes sharply S.
38.91	Point for the ¼ sec. cor. of secs. 12 and 13, determined longitudinally by an old property line fence, extending N and S, and latitudinally on line between sec. cors.; there is no remaining evidence of the original cor. monument.

Dependent Resurvey of a portion of Subdivisional Lines
T. 19 S., R. 8 E., Salt Lake Mer., Utah

CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 19 S R 8 E
 S 12
¼ S 13
 1975

(Restoring the 1873 survey by A. D. Ferron and the 1882 survey by A. D. Ferron)

S. 86°48' W., beginning new measurement.

12.50 Wash, 30 lks. wide, 4 ft. deep, drains S. 40° E.

40.24 The cor. of secs. 11, 12, 13 and 14.

N. 0°52' W., bet. secs. 11 and 12.

Over rolling bench land.

39.84 Point for the ¼ sec. cor. of secs. 11 and 12, at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 19 S R 8 E
 ¼
 S 11 | S 12
 1975

61.50 Wash, 10 lks. wide, 3 ft. deep, drains S. 65° E.

79.40 Gravel road, bears S. 89° W. and N. 89° E.

79.68 Point for the cor. of secs. 1, 2, 11 and 12, at proportionate dist. longitudinally, and controlled latitudinally by an extension of property line fence to west, which is on the section line according to local residents. There is no remaining evidence of the original cor. monument.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 19 S R 8 E
 S 2 | S 1
 S 11 | S 12
 1975

(Restoring the 1873 survey by A. D. Ferron)

From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., heretofore described.

S. 89°17' W., bet. secs. 1 and 12.

Over rolling and broken bench land.

Dependent Resurvey of a portion of Subdivisional Lines
T. 19 S., R. 8 E., Salt Lake Mer., Utah

CHAINS		
10.00	Wash, drains S. 60° E.	
41.73	<p>The ¼ sec. cor. of secs. 1 and 12, monumented with a sandstone, 10 x 6 x 2 ins., firmly set 4 ins. in the ground, and plainly mkd. ¼ on N face, and witnessed by a small mound of stone to N.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 19 S R 8 E</p> <p>¼ <u>S 1</u></p> <p>S 12</p> <p>1975</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p> <hr/> <p>(Restoring the 1873 survey by A. D. Ferron and the 1882 survey by A. D. Ferron)</p> <hr/> <p>S. 88°25' W., beginning new measurement.</p>	
2.50	Wash, drains S.	
20.30	N edge of gravel road, bears S. 75° E. and S. 89° W. to Castle Dale, thence along N side of road.	
40.55	The cor. of secs. 1, 2, 11 and 12.	
(Restoring the 1873 survey by A. D. Ferron)		
	S. 88°55' W., bet. secs. 2 and 11.	
	Along N edge of gravel road.	
18.50	Junction of graded road, with fence along W side, bears N. 24° E.; thence along fence line along N side of gravel road to Castle Dale.	
40.69	Point for the ¼ sec. cor. of secs. 2 and 11, at projected intersection of property line fences from N, E and W, falls in gravel road, curves SE and E and NW and W. This point is harmoniously related to existing original cors. and the east - west fence line is recognized by local residents as being on the sec. line, and is accepted as the best available evidence of the position of the original cor. There is no remaining evidence of the original cor.	
	At the corner point	
	Bury an iron post, 10 ins. long, 1 in. diam., 8 ins. below surface of road, with brass cap mkd.	
	<div style="text-align: center;"> <p>T 19 S R 8 E</p> <p>¼ <u>S 2</u></p> <p>S 11</p> <p>1975</p> </div>	

Dependent Resurvey of a portion of Subdivisional Lines
T. 19 S., R. 8 E., Salt Lake Mer., Utah

CHAINS

from which

An iron post, 30 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 36°17' E., 53 lks. dist., mkd. RM T19S R8E ¼S2 35 FT 1975 and an arrow pointing to the true corner.

An iron post, 30 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 36°17' W., 13.6 lks. dist., mkd. RM T19S R8E ¼S11 9FT 1975 and an arrow pointing to the true corner.

From the cor. of secs. 1, 2, 11 and 12.


N. 1°32' W., bet. secs. 1 and 2.

Over rolling land.

23.20 Trail road, bears N. 60° E. and S. 60° W.

40.36 Point for the ¼ sec. cor. of secs. 1 and 2, at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.




53.00 Cottonwood Creek, 30 lks. wide, 15 ins. deep, flows N. 70° E.; enter young cottonwood timber.

65.00 Enter meadow land, edge bears E and W.

81.42 The cor. of secs. 1, 2, 35 and 35, on the N. bdy. of the Tp., hereinbefore described.

(Restoring the 1873 survey by A. D. Ferron and the 1882 resurvey by A. D. Ferron)

From the true point for the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., which its witness cor. bears North, 3.15 chs. dist., and is an iron post, 2½ ins. diam., extending 6 ins. above ground, with brass cap mkd.



N. 0°28' E., bet. secs. 34 and 35.

Over cultivated land.

Dependent Resurvey of a portion of Subdivisional Lines
T. 19 S., R. 8 E., Salt Lake Mer., Utah

CHAINS	
3.20	Leave cultivated land, bears E and W.
8.50	Base of bench, bears E and W; asc. abruptly 200 ft. over S slope.
11.85	Rim of bench, top of ledge, 75 ft. high, bears W and curves NE; thence over rolling bench land.
39.85	The ¼ sec. cor. of secs. 34 and 35, monumented with a sandstone, 24 x 16 x 2 ins., firmly set 6 ins. in the ground and plainly mkd. ¼ on W face. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	<p>T 19 S R 8 E</p> <p>¼</p> <p>S 34 S 35</p> <p>1975</p>
	Deposit the mkd. stone alongside the iron post.
	N. 1°01' W., beginning new measurement.
	Desc. over rolling bench land.
39.14	Point for the cor. of secs. 26, 27, 34 and 35, at proportionate dist. falls in Peavine Wash, 5 lks. wide, 15 ins. deep, flows irregularly E., and cannot be perpetuated. Point for the witness cor. of secs. 26, 27, 34 and 35, bears N. 0°30' W., 0.05 chs. dist., hereinafter described.
	(Restoring the 1882 survey by A. D. Ferron)
	From the cor. of secs. 25, 26, 35 and 36.
	S. 88°07' W., bet. secs. 26 and 35.
	Over rolling desert land.
23.00	Spur, slopes S. 50° E.
40.82	Point for the ¼ sec. cor. of secs. 26 and 35, at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>T 19 S R 8 E</p> <p>¼ <u>S 26</u></p> <p>S 35</p> <p>1975</p>
57.00	Peavine Wash, 10 lks. wide, 15 ins. deep, flows irregularly S. 50° E.; asc. NE slope.
70.00	Point of spur, slopes N; desc. NW slope.

Dependent Resurvey of a portion of Subdivisional Lines
T. 19 S., R. 8 E., Salt Lake Mer., Utah

CHAINS 81.64	<p>True point for the cor. of secs. 26, 27, 34 and 35.</p> <hr/> <p>(Restoring the 1873 survey by A. D. Ferron, and the 1882 resurvey by A. D. Ferron)</p> <hr/> <p>N. 0°30' W., bet. secs. 26 and 27.</p> <p>Over rolling desert bench land.</p>				
0.05	<p>Point for the witness cor. of secs. 26, 27, 34 and 35.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>W C</p> <p>T 19 S R 8 E</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 27</td> <td style="padding: 0 5px;">S 26</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 34</td> <td style="padding: 0 5px;">S 35</td> </tr> </table> <p>↓</p> <p>1975</p> </div>	S 27	S 26	S 34	S 35
S 27	S 26				
S 34	S 35				
23.00	<p>Wash, drains S. 50° E.</p>				
39.13	<p>The ¼ sec. cor. of secs. 26 and 27, monumented with a sandstone, 18 x 10 x 6 ins., firmly set 8 ins. in the ground, and plainly mkd. ¼ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 19 S R 8 E</p> <p>¼</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 27</td> <td style="padding: 0 5px;">S 26</td> </tr> </table> <p>↓</p> <p>1975</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p> <hr/> <p>N. 0°39' E., beginning new measurement.</p>	S 27	S 26		
S 27	S 26				
6.50	<p>Wash, drains S. 60° W.</p>				
26.20	<p>Trail road, bears E and W along spur, slopes W.</p>				
38.87	<p>The cor. of secs. 22, 23, 26 and 27, monumented with a steel fence post, in mound of stone. This position is harmoniously related to existing original cors. and is accepted as a perpetuation of the original cor. point. There is no remaining evidence of the original cor. monument.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 19 S R 8 E</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 22</td> <td style="padding: 0 5px;">S 23</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 27</td> <td style="padding: 0 5px;">S 26</td> </tr> </table> <p>1975</p> </div>	S 22	S 23	S 27	S 26
S 22	S 23				
S 27	S 26				

Dependent Resurvey of a portion of Subdivisional Lines
T. 19 S., R. 8 E., Salt Lake Mer., Utah

CHAINS		
	Place steel fence post alongside the iron post.	
	From the cor. of secs. 23, 24, 25 and 26. S. 88°22' W., bet. secs. 23 and 26. Over rolling desert bench land.	
16.50	Trail road, bears N. 15° E. and S. 15° W.	
40.37	Point for the ¼ sec. cor. of secs. 23 and 26, at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.	
	T 19 S R 8 E ¼ S 23 S 26 1975	
41.00	Wash, drains N. 55° W.	
73.00	Wash, 15 lks. wide, 5 ft. deep, drains irregularly N. 50° W.	
80.74	The cor. of secs. 22, 23, 26 and 27.	
	(Restoring the 1873 survey by A. D. Ferron)	

	N. 0°38' E., bet. secs. 22 and 23. Over gently rolling desert bench land.	
5.00	Wash, 15 lks. wide, 4 ft. deep, drains N. 50° W.	
41.33	Point for the ¼ sec. cor. of secs. 22 and 23, at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.	
	T 19 S R 8 E ¼ S 22 S 23 1975	
57.00	Wash, drains N. 35° E.	
82.66	Point for the cor. of secs. 14, 15, 22 and 23, determined at intersection of old fence line from N, and projection of old abandoned fence line from W. This point is harmoniously related to existing original cors., and is accepted as the best existing evidence of the position of the original cor. At the corner point	

Dependent Resurvey of a portion of Subdivisional Lines
T. 19 S., R. 8 E., Salt Lake Mer., Utah

CHAINS	
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 19 S R 8 E S 15 S 14 S 22 S 23 1975</p>
<p>5.50</p> <p>13.00</p> <p>39.28</p>	<p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>S. 87°53' W., bet. secs. 14 and 23.</p> <p>Over rolling desert bench land.</p> <p>Wash, 20 lks. wide, 2 ft. deep, drains N.</p> <p>Low ridge, bears N and S.</p> <p>Point for the ¼ sec. cor. of secs. 14 and 23, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 19 S R 8 E ¼ S 14 S 23 1975</p>
<p>40.00</p> <p>71.50</p> <p>78.56</p> <p>0.50</p> <p>32.00</p> <p>32.95</p> <p>40.21</p> <p>5.50</p>	<p>Small wash, drains N.</p> <p>Wash, 25 lks. wide, 5 ft. deep, drains N.</p> <p>The cor. of secs. 14, 15, 22 and 23.</p> <p>N. 1°40' W., bet. secs. 14 and 15.</p> <p>Over rolling desert land, along old fence line.</p> <p>Wash, 30 lks. wide, 3 ft. deep, drains E.</p> <p>Low spur, slopes E.</p> <p>Fence line turns NE; desc. N slope.</p> <p>Point for the ¼ sec. cor. of secs. 14 and 15, on line bet. sec. cors. and determined latitudinally by property line fence bearing E and W.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 19 S R 8 E ¼ S 15 S 14 1975</p> <p>N. 1°40' W., beginning new measurement.</p> <p>Rock Canyon Creek, 15 lks. wide, 8 ins. deep, flows irregularly E.</p>

Dependent Resurvey of a portion of Subdivisional
T. 19 S., R. 8 E., Salt Lake Mer., Utah

CHAINS 6.00	Fence, from SE, thence along fence line; enter cultivated land west of line.
23.00	Farm road, bears S. 65° W. and curves N, thence along W side of road.
39.52	Fence, bears W, enter graded road from W.
40.27	Point for the cor. of secs. 10, 11, 14 and 15, at projected intersection of property line fences from W, S and N. This point has long been recognized and used by adjacent land owners and local surveyors, and is accepted as the best available evidence of the position of the original cor. At the corner point Bury an iron post, 10 ins. long, 1 in. diam., 8 ins. below surface of ground at west edge of graded road, with brass cap mkd. <div style="text-align: center;"> <p>T 19 S R 8 E S 10 S 11 S 15 S 14 1975</p> </div> from which An iron post, 30 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 33°11' E., 89.4 lks. dist., mkd. RM T19S R8E S14 59 FT 1975 and an arrow pointing to the true corner. An iron post, 30 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 14°17' W., 77.3 lks. dist., mkd. RM T19S R8E S15 51 FT 1975, and an arrow pointing to the true corner.
36.80	From the cor. of secs. 11, 12, 13 and 14. S. 88°31' W., bet. secs. 11 and 14. Over gently rolling desert land. Wash, with stream of water, 10 lks. wide, 12 ins. deep, flows S. 50° E., from N.
40.32	Point for the ¼ sec. cor. of secs. 11 and 14, at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. <div style="text-align: center;"> <p>T 19 S R 8 E S 11 ¼ S 14 1975</p> </div>
50.00	Enter cultivated land, bears NW and SE.
80.50	Graded road, bears N and S; leave cultivated land.
80.64	The cor. of secs. 10, 11, 14 and 15.

Dependent Resurvey of a portion of Subdivisional Lines
T. 19 S., R. 8 E., Salt Lake Mer., Utah

CHAINS

(Restoring the 1873 survey by A. D. Ferron and
the 1882 resurvey by A. D. Ferron)

From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of
the Tp., monumented with an iron post, 2½ ins. diam.,
extending 6 ins. above ground, with brass cap mkd.

T 19 S R 8 E
S 33 | S 34
S 4 | S 3
T 20 S
1962

N. 0°44' E., bet. secs. 33 and 34.

Over rolling desert bench land.

3.50 Desc. N slope of bench, bears E and W.

5.00 Base of bench; thence over rolling desert land.

36.95 Graded road, bears E and W.

39.43 Point for the ¼ sec. cor. of secs. 33 and 34, at propor-
tionate dist.; there is no remaining evidence of the
original cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in
the ground, with brass cap mkd.

T 19 S R 8 E
¼
S 33 | S 34
1975

Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of
cor.

64.10 Clay spur, 30 ft. high, slopes E.

77.90 Wash, 15 lks. wide, with stream of water, 6 ins. wide,
2 ins. deep, flows irregularly E.

78.86 The cor. of secs. 27, 28, 33 and 34, monumented with a
flintstone, 13 x 6 x 6 ins., set 6 ins. in the ground,
and mkd. 1 notch on S and 3 notches on E edges.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in
the ground, with brass cap mkd.

T 19 S R 8 E
S 28 | S 27
S 33 | S 34
1975

Deposit the mkd. stone alongside the iron post.

From the true point for the cor. of secs. 26, 27, 34 and
35.

S. 89°01' W., bet. secs. 27 and 34.

Dependent Resurvey of a portion of Subdivisional Lines
T. 19 S., R. 8 E., Salt Lake Mer., Utah

CHAINS		
40.60	<p>Over rolling desert land through sagebrush and greasewood undergrowth along bottom land of Peavine Wash, flowing irregularly E from irregularly W.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 34, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 19 S R 8 E</p> <p>$\frac{1}{4}$ S 27</p> <hr style="width: 50px; margin: 0 auto;"/> <p>S 34</p> <p>1975</p> </div> <p>Cor. is located 35 lks. N of Peavine Wash, 5 lks. wide, 12 ins. deep, flows irregularly E.</p>	
77.00	<p>Wash, with stream of water, 6 ins. wide, 3 ins. deep, flows irregularly E.</p>	
81.20	<p>The cor. of secs. 27, 28, 33 and 34.</p>	
6.00	<p>N. $0^{\circ}03'$ E., bet. secs. 27 and 28.</p> <p>Over rolling land through greasewood undergrowth.</p> <p>Peavine Wash, flows East.</p>	
23.70	<p>Rim of bench land, bears E and W; thence over nearly level land.</p>	
26.18	<p>Fence, bears W and N, with trail road along N side, thence along fence line; enter cultivated land.</p>	
40.60	<p>Point for $\frac{1}{4}$ sec. cor. of secs. 27 and 28, at proportionate dist. latitudinally and controlled longitudinally by N - S property line fence; there is no remaining evidence of the original cor. monument.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 19 S R 8 E</p> <p>$\frac{1}{4}$</p> <p>S 28 S 27</p> <hr style="width: 50px; margin: 0 auto;"/> <p>1975</p> </div>	
8.00	<p>N. $0^{\circ}40'$ W., beginning new measurement.</p> <p>Continue along fence line; leave cultivated land.</p> <p>Desc. N slope of bench; fence turns to NW.</p>	
40.60	<p>The cor. of secs. 21, 22, 27 and 28, monumented with a sandstone, 12 x 6 x 5 ins., set 6 ins. in the ground, and plainly mkd. 2 notches on S and 3 on E edges.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>	

Dependent Resurvey of a portion of Subdivisional Lines
T. 19 S., R. 8 E., Salt Lake Mer., Utah

CHAINS	
	<p style="text-align: center;">T 19 S R 8 E S 21 S 22 S 28 S 27 1975</p> <p>Deposit the mkd. stone alongside the iron post.</p>
<p>26.00</p> <p>40.90</p>	<p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>N. 88°46' W., bet. secs. 22 and 27.</p> <p>Over rolling desert land.</p> <p>Wash, 40 lks. wide, 6 ft. deep, with stream of water, 4 lks. wide, 6 ins. deep, flows N. 20° E.</p> <p>Point for the ¼ sec. cor. of secs. 22 and 27, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 19 S R 8 E ¼ S 22 S 27 1975</p>
<p>81.80</p>	<p>The cor. of secs. 21, 22, 27 and 28.</p>
<p>40.63</p>	<p style="text-align: center;">(Restoring the 1873 survey by A. D. Ferron)</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°09' W., bet. secs. 21 and 22.</p> <p>Over gently rolling desert land.</p> <p>Point for the ¼ sec. cor. of secs. 21 and 22, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p>
<p>81.26</p>	<p style="text-align: center;">T 19 S R 8 E ¼ S 21 S 22 1975</p> <p>The cor. of secs. 15, 16, 21 and 22, monumented with a sandstone, 10 x 6 x 4 ins., set 4 ins. in the ground, and plainly mkd. 3 notches on S and E edges.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a portion of Subdivisional Lines
T. 19 S., R. 8 E., Salt Lake Mer., Utah

CHAINS		
	<p style="text-align: center;">T 19 S R 8 E $\frac{S\ 16}{S\ 21}$ $\frac{S\ 15}{S\ 22}$ 1975</p> <p>Deposit the mkd. stone alongside the iron post.</p>	
<p>41.40</p>	<p>From the cor. of secs. 14, 15, 22 and 23. N. 89°44' W., bet. secs. 15 and 22. Over gently rolling desert land. Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 22, at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 19 S R 8 E $\frac{1}{4}$ $\frac{S\ 15}{S\ 22}$ 1975</p>	
<p>77.30</p>	<p>Wash, 25 lks. wide, 4 ft. deep, drains N. 30° E.</p>	
<p>82.80</p>	<p>The cor. of secs. 15, 16, 21 and 22.</p>	
<p>12.00</p> <p>35.40</p> <p>40.31</p>	<p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., extending 6 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T 19 S R 8 E $\frac{S\ 32}{S\ 5}$ $\frac{S\ 33}{S\ 4}$ T 20 S 1962</p> <p>N. 0°04' E., bet. secs. 32 and 33. Over rolling desert land. Clay ridge, bears E and W; desc. over N slope. Wash, 100 lks. wide, 8 ft. deep, with stream of water, 12 ins. wide, 4 ins. deep, flows E. Point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33, at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 19 S R 8 E $\frac{1}{4}$ $\frac{S\ 32}{S\ 33}$ 1975</p>	
<p>66.10</p>	<p>Gravel road, bears E to Paradise Ranch and W to Clawson.</p>	

Dependent Resurvey of a portion of Subdivisional Lines
T. 19 S., R. 8 E., Salt Lake Mer., Utah

CHAINS					
80.62	<p>Point for the cor. of secs. 28, 29, 32 and 33, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T 19 S R 8 E</td></tr> <tr><td>S 29 S 28</td></tr> <tr><td>S 32 S 33</td></tr> <tr><td>1975</td></tr> </table> </div>	T 19 S R 8 E	S 29 S 28	S 32 S 33	1975
T 19 S R 8 E					
S 29 S 28					
S 32 S 33					
1975					
40.81	<p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>N. 89°48' W., bet. secs. 28 and 33.</p> <p>Over gently rolling desert land.</p> <p>Point for the ¼ sec. cor. of secs. 28 and 33, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, to bedrock, and in a mound of stone, 2½ ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T 19 S R 8 E</td></tr> <tr><td>¼ S 28</td></tr> <tr><td>S 33</td></tr> <tr><td>1975</td></tr> </table> </div>	T 19 S R 8 E	¼ S 28	S 33	1975
T 19 S R 8 E					
¼ S 28					
S 33					
1975					
79.40	Gravel road, bears N. 10° E. and S. 10° W.				
81.62	The cor. of secs. 28, 29, 32 and 33.				
2.00	<p>N. 1°04' W., bet. secs. 28 and 29.</p> <p>Over gently sloping land.</p> <p>Enter cultivated land changing to meadow land.</p>				
25.00	Peavine Wash, 5 lks. wide, 12 ins. deep, flows S. 75° E.; asc. gentle S slope.				
40.32	Point for the ¼ sec. cor. of secs. 28 and 29, at proportionate dist. falls on private land and is not monumented; there is no remaining evidence of the original cor. monument.				
50.00	Leave meadow and swamp land, bears E and W.				
53.50	Enter roadway, with fences along both sides, bears N and SE curving S, thence along road.				
80.64	<p>Point for the cor. of secs. 20, 21, 28 and 29, at proportionate dist. latitudinally and controlled longitudinally by center line of gravel road which bears N and S, and recognized as being along the section line by local residents of the area. There is no remaining evidence of the original cor. monument.</p> <p>Set an iron post, 10 ins. long, 1 in. diam., 10 ins. below surface of roadway, with brass cap mkd.</p>				

Dependent Resurvey of a portion of Subdivisional Lines
T. 19 S., R.8 E., Salt Lake Mer., Utah

CHAINS	<p>T 19 S R 8 E S 20 S 21 S 29 S 28 1975</p>
	<p>from which</p> <p>An iron post, 30 ins. long, 2½ ins. diam., set 20 ins. in the ground, for a reference monument, bears N. 37°45' E., 83.3 lks. dist., mkd. RM T19S R8E S21 55 FT 1975, and an arrow pointing to the true cor.</p> <p>An iron post, 30 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 37°45' W., 83.3 lks. dist., mkd. RM T19S R8E 55FT 1975, and an arrow pointing to the true cor.</p>
<p>41.95</p>	<p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>S. 89°47' W., bet. secs. 21 and 28.</p> <p>Over gently rolling desert land.</p> <p>Point for the ¼ sec. cor. of secs. 21 and 28, on line bet. sec. cors., and controlled longitudinally by extension of property line fences from N and S; there is no remaining evidence of the original cor. monument.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 19 S R 8 E ¼ S 21 S 28 1975</p> <p>Cor. is located near NE edge of small knoll.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°47' W., beginning new measurement.</p>
<p>39.82</p>	<p>Fence, bears N and S, enter roadway.</p>
<p>40.64</p>	<p>The cor. of secs. 20, 21, 28 and 29.</p>
<p>16.60</p>	<p>N. 0°35' E., bet. secs. 20 and 21.</p> <p>Along gravel roadway.</p>
<p>40.31</p>	<p>Road, turns to about N. 20° E.; fences bears E and W, enter shadscale.</p> <p>Point for the ¼ sec. cor. of secs. 20 and 21, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 19 S R 8 E ¼ S 20 S 21 1975</p>

Dependent Resurvey of a portion of Subdivisional Lines
T. 19 S., R. 8 E., Salt Lake Mer., Utah

CHAINS					
43.25	<p>Cor. is 1.00 ch. W of gravel road, bearing N and S.</p> <p>Enter gravel roadway, bears N from SE, thence along roadway.</p>				
74.50	<p>Rock Canyon Creek, 100 lks. wide, 6 ft. deep, with small stream of water, flows N. 65° E., from West.</p>				
80.62	<p>Point for the cor. of secs. 16, 17, 20 and 21, at proportionate dist. latitudinally and controlled longitudinally by gravel road, bearing N and S; there is no remaining evidence of the original cor. monument.</p> <p>Set an iron post, 10 ins. long, 1 in. diam., 10 ins. below surface of roadway, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 19 S R 8 E</p> <table style="margin: auto;"> <tr> <td>S 17</td> <td>S 16</td> </tr> <tr> <td>S 20</td> <td>S 21</td> </tr> </table> <p>1975</p> </div> <p>from which</p> <p>An iron post, 30 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 41°20' W., 34.8 lks. dist., mkd. RM T19S R8E S20 23FT 1975, and an arrow pointing to the true cor.</p> <p>An iron post, 30 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 49°53' W., 31.8 lks. dist., mkd. RM T19S R8E S17 21FT 1975, and an arrow pointing to the true cor.</p> <p>From the same cor., a property line fence bearing E and W, recognized by adjacent land owners as being on the section line, bears North, 80.62 chs. dist., and is used for control latitudinally for proportionate distance to the S.</p> <p>The control line was fully retraced, and no evidence of the intervening cor. was found.</p>	S 17	S 16	S 20	S 21
S 17	S 16				
S 20	S 21				
39.24	<p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>S. 87°15' W., bet. secs. 16 and 21.</p> <p>Over gently rolling desert land.</p> <p>The ¼ sec. cor. of secs. 16 and 21, monumented with a sandstone, 8 x 6 x 3 ins., firmly set 4 ins. in the ground, and plainly mkd. ¼ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 19 S R 8 E</p> <table style="margin: auto;"> <tr> <td>¼</td> <td>S 16</td> </tr> <tr> <td></td> <td>S 21</td> </tr> </table> <p>1975</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p>	¼	S 16		S 21
¼	S 16				
	S 21				

Dependent Resurvey of a portion of Subdivisional Lines
T. 19 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS	
31.00	<p>N. 88°35' W., beginning new measurement.</p> <p>Rock Canyon Creek, 150 lks. wide, 6 ft. deep, with stream of water, 4 lks. wide, 5 ins. deep, flows irregularly N. 50° E. from S. 60° W.; enter cultivated land.</p>
42.14	<p>Fence, bears N and S, enter roadway.</p>
42.39	<p>The cor. of secs. 16, 17, 20 and 21.</p>
<p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., extending 12 ins. above ground, with brass cap mkd.</p>	
<p style="text-align: center;">T 19 S R 8 E S 31 S 32 S 6 S 5 T 20 S 1962</p>	
5.00	<p>N. 1°01' E., bet. secs. 31 and 32.</p> <p>Over rolling desert land.</p> <p>Wash, drains S. 65° E.</p>
40.63	<p>The ¼ sec. cor. of secs. 31 and 32, monumented with a sandstone, 10 x 9 x 6 ins., projecting 6 ins. above ground, and plainly mkd. ¼ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
<p style="text-align: center;">T 19 S R 8 E ¼ S 31 S 32 1975</p>	
<p>Deposit the mkd. stone alongside the iron post.</p>	
<p>N. 1°31' W., beginning new measurement.</p>	
37.50	<p>Gravel road, bears N. 89°30' W. and S. 89°30' E.</p>
38.01	<p>Fence, parallel to gravel road, enter cultivated land.</p>
39.85	<p>Point for the cor. of secs. 29, 30, 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with steel fence post alongside, brass cap mkd.</p>
<p style="text-align: center;">T 19 S R 8 E S 30 S 29 S 31 S 32 1975</p>	

Dependent Resurvey of a portion of the Subdivisional Lines
T. 19 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS	
	<p>From this cor., the cor. of secs. 19, 20, 29 and 30, bears N. 0°10' W., 79.68 chs., monumented with an iron post, hereinafter described.</p> <p>The control line was fully retraced, and no evidence of the intervening cor. was found.</p>
<p>40.67</p> <p>81.34</p>	<p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>S. 88°48' W., bet. secs. 29 and 32.</p> <p>Over nearly level farm land.</p> <p>Point for the ¼ sec. cor. of secs. 29 and 32, at proportionate dist. falls on private farm land and is not monumented; there is no remaining evidence of the original cor.</p> <p>The cor. of secs. 29, 30, 31 and 32.</p>
<p>40.73</p> <p>40.38</p>	<p>S. 89°05' W., bet. secs. 30 and 31.</p> <p>Over nearly level farm land.</p> <p>Point for the ¼ sec. cor. of secs. 30 and 31, on line bet. sec. cors., and controlled longitudinally by property line fences extending N and S; there is no remaining evidence of the original cor. monument.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 19 S R 8 W</p> <p>¼ S 30</p> <p> S 31</p> <p> 1975</p> </div> <hr style="width: 20%; margin: auto;"/> <p>S. 89°05' W., beginning new measurement.</p> <p>Continue over farm land, along N side of fence and gravel road, bearing W.</p> <p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., (Second Guide Meridian East) monumented with an iron post, 1 in. diam., 8 ins. below surface of gravel road, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 19 S</p> <p>R 7 E R 8 E</p> <p>S 25 S 30</p> <p>S 36 S 31</p> <p>1975</p> </div> <p>This cor. described in the field notes of the concurrent resurvey of the E. bdy. of T. 19 S., R. 7 E.</p>
	<p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>S. 88°06' W., bet. secs. 20 and 29.</p> <p>Over gently rolling land.</p>

Dependent Resurvey of a portion of the Subdivisional Lines
T. 19 S., R. 8 E., Salt Lake Meridian, Utah

<p>CHAINS 0.50</p>	<p>Fence, bears N and S, enter farm and meadow land.</p>
<p>41.08</p>	<p>Point for the ¼ sec. cor. of secs. 20 and 29, on line bet. sec. cors., and controlled longitudinally by property line fence extending N and S; there is no remaining evidence of the original cor. monument.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 19 S R 8 E S 20 ¼ S 29 1975</p>
<p>38.98</p>	<p>S. 88°06' W., beginning new measurement.</p> <p>Continue over farm land.</p> <p>The cor. of secs. 19, 20, 29 and 30, monumented with an iron post, 2 ins. diam., with 3 in. brass cap mkd.</p> <p style="text-align: center;">T 19 S R 8 E S 19 S 20 S 30 S 29 1975 KING RLS 1929</p> <p>This point is accepted as a perpetuation of the original cor. position.</p>
<p>0.70 1.00 1.30 41.24 8.00</p>	<p>N. 1°10' W., bet. secs. 19 and 20.</p> <p>Over rolling farm land.</p> <p>Fence, bears E and W.</p> <p>Gravel road, bears E and W.</p> <p>Fence, bears E, W and N; thence along fence line.</p> <p>Point for the ¼ sec. cor. of secs. 19 and 20, at proportionate dist. latitudinally and controlled longitudinally by N and S fence line; there is no remaining evidence of the original cor. monument.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 19 S R 8 E ¼ S 19 S 20 1975</p> <p>N. 0°46' W., beginning new measurement.</p> <p>Continue over farm land and along fence line.</p> <p>Rock Canyon Creek, flows E.</p>

Dependent Resurvey of a portion of the Subdivisional Lines
T. 19 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS	
41.23	<p>The cor. of secs. 17, 18, 19 and 20, at cor. of fences extending S, E and W, monumented with an iron post, 2 ins. diam., with 3 in. brass cap mkd.</p> <p style="text-align: center;">T 19 S R 8 E S 18 S 17 S 19 S 20 1975 KING RLS 1929</p> <p>This point is accepted as a perpetuation of the original cor. position.</p>
0.25	<p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>S. 89°20' W., bet. secs. 17 and 20.</p> <p>Fence, bears N and S, enter meadow and farm land.</p>
42.45	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 20, at cor. of fences extending N, S and old fence line to West. This position is harmoniously related to existing original cors. and is accepted as the best existing evidence of the position of the original cor.; there is no remaining evidence of the original cor. monument.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 19 S R 8 E $\frac{1}{4}$ S 17 S 20 1975</p> <p>S. 89°34' W., beginning new measurement.</p> <p>Over farm and meadow land and along fence line.</p>
39.70	<p>The cor. of secs. 17, 18, 19 and 20.</p>
40.22	<p>S. 89°13' W., bet. secs. 18 and 19.</p> <p>Over level farm land, and along fence line.</p> <p>New fence, bears South.</p>
40.42	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19, at cor. of old fences, extending N, E and W. This position is harmoniously related to existing original cors. and is accepted as the best available evidence of the position of the original cor.; there is no remaining evidence of the original cor. monument.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 19 S R 8 E $\frac{1}{4}$ S 18 S 19 1975</p>

Dependent Resurvey of a portion of the Subdivisional Lines
T. 19 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS	
	S. 89°13' W., beginning new measurement.
	Continue over farm land along fence line.
15.00	Right of way fence, bears N. 51°15' E and S. 51°15' W.
16.05	Centerline of State Highway No. 10, bears N. 51°15' E. and S. 51°15' W., also, graded dirt road bears W, thence along dirt road.
40.37	The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., (Second Guide Meridian East) monumented with an iron post, 1 in. diam., buried 6 ins. below surface of road, with brass cap mkd.
	<div style="text-align: center;"> <p>T 19 S R 7 E R 8 E S 13 S 18 S 24 S 19 1975</p> </div>
	This cor. described in the field notes of the concurrent resurvey of the E. bdy. of T. 19 S., R. 7 E.
	From the cor. of secs. 17, 18, 19 and 20.
	N. 0°13' W., bet. secs. 17 and 18.
	Over meadow and pasture land.
40.54	Point for the ¼ sec. cor. of secs. 17 and 18, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> <p>T 19 S R 8 E ½ S 18 S 17 1975</p> </div>
42.70	Right of way fence, parallel to highway.
43.08	Power line, parallel to highway.
43.67	State Highway No. 10, bears N. 51°15' E. and S. 51°15' W.
44.65	Right of way fence, parallel to highway; thence over farm land, along fence line.
81.08	Point for the cor. of secs. 7, 8, 17 and 18, at cor. of fences extending N, S, E and W. This point is harmoniously related to existing original cors. and is accepted as the best available evidence of the position of the original cor.; there is no remaining evidence of the original cor. monument.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a portion of the Subdivisional Lines
T. 19 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS	<p style="text-align: center;">T 19 S R 8 E S 7 S 8 S 18 S 17 1975</p>
	<p>S. 89°20' W., bet. secs. 7 and 18. Over rolling land, along fence line.</p> <p>8.50 Wash, drains S. 65° E.</p> <p>20.00 Spur, slopes S. 65° E., thence along general S slope. End of fence line.</p> <p>40.43 Point for the ¼ sec. cor. of secs. 7 and 18, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 19 S R 8 E ¼ S 7 S 18 1975</p>
	<p>65.00 Spur, slopes S. 50° E.; desc. over rolling land.</p>
	<p>81.17 The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., (Second Guide Meridian East) monumented with an iron post, 2½ ins. diam., with brass cap mkd.</p> <p style="text-align: center;">T 19 S R 7 E R 8 E S 12 S 7 S 13 S 18 1975</p> <p>This cor. described in the field notes of the concurrent resurvey of the E. bdy. of T. 19 S., R. 7 E.</p>
	<p>From the cor. of secs. 7, 8, 17 and 18. N. 0°10' W., bet. secs. 7 and 8. Over rolling land, and along fence line.</p> <p>39.99 Point for the ¼ sec. cor. of secs. 7 and 8, at cor. of property line fences extending N, S, E and W. This position is harmoniously related to existing original cors., and is accepted as the best existing evidence of the position of the original cor. point; there is no remaining evidence of the original cor. monument.</p> <p>At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 19 S R 8 E ¼ S 7 S 8 1975</p>

Dependent Resurvey of a portion of the Subdivisional Lines
T. 19 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS													
12.35	<p>North, beginning new measurement.</p> <p>Continue over rolling land along fence line.</p> <p>Spur, on Johnson Bench, slopes N. 75° E.; desc. NE slope.</p>												
17.00	<p>Paved road, bears N and curves W; thence along E side of road.</p>												
40.12	<p>Point for the cor. of secs. 5, 6, 7 and 8, at proportionate dist. latitudinally and controlled longitudinally by old fence line bearing N and S; there is no remaining evidence of the original cor. monument.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 19 S R 8 E</p> <table border="0"> <tr><td>S 6</td><td> </td><td>S 5</td></tr> <tr><td>S 7</td><td> </td><td>S 8</td></tr> </table> <p>1975</p> </div> <p>From this cor., point for the ¼ sec. cor. of secs. 5 and 6, bears N. 0°26' W., 40.12 chs. dist., at cor. of property line fences extending N, S and E. This position is harmoniously related to existing original cors., and is accepted as the best available evidence of the position of the original cor.; there is no remaining evidence of the original cor. monument.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 19 S R 8 E</p> <table border="0"> <tr><td>¼</td><td> </td><td></td></tr> <tr><td>S 6</td><td> </td><td>S 5</td></tr> </table> <p>1975</p> </div>	S 6		S 5	S 7		S 8	¼			S 6		S 5
S 6		S 5											
S 7		S 8											
¼													
S 6		S 5											
40.72	<p>S. 89°22' W., bet. secs. 6 and 7.</p> <p>Over gently rolling land.</p> <p>Point for the ¼ sec. cor. of secs. 6 and 7, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 19 S R 8 E</p> <table border="0"> <tr><td>¼</td><td> </td><td>S 6</td></tr> <tr><td></td><td> </td><td>S 7</td></tr> </table> <p>1975</p> </div>	¼		S 6			S 7						
¼		S 6											
		S 7											
81.73	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., (Second Guide Meridian East) monumented with an iron post, 2½ ins. diam., with brass cap mkd.</p> <div style="text-align: center;"> <p>T 19 S</p> <p>R 7 E R 8 E</p> <table border="0"> <tr><td>S 1</td><td> </td><td>S 6</td></tr> <tr><td>S 12</td><td> </td><td>S 7</td></tr> </table> <p>1975</p> </div>	S 1		S 6	S 12		S 7						
S 1		S 6											
S 12		S 7											

Dependent Resurvey of a portion of the Subdivisional Lines
T. 19 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS

This cor. described in the field notes of the concurrent resurvey of the E. bdy., T. 19 S., R. 7 E.

General Description

Township 19 South, Range 8 East is located south of Castle Dale and east of Clawson. The southeast portion of this township is rolling to broken clay ridges and benches covered with a sparse growth of shadscale undergrowth. The north and west areas are mostly privately owned farm land. The area is drained in an easterly direction by Cottonwood Creek in the north portion, Rock Canyon Creek in the central portion and Ferron Creek in southern portion. The area varies from about 5,500 ft. to about 5,900 ft. above sea level.

The soil is mostly clay, with some gravelly benches in the northwest portion. Vegetation is a sparse growth of shadscale, greasewood and some sage. There is water in Cottonwood Creek, Rock Canyon Creek, Ferron Creek and Peavine Wash. No other water was noted. The only timber in the township is along Cottonwood Creek and Ferron Creek, where patches of cottonwood trees are growing. There are ranches located in sections 1, 2, 13, and 36, as well as throughout the western portion of the township. Utah Power and Light Co. is presently constructing a large power plant in sec. 16. State Highway No. 10 bears southwesterly through the northwestern portion of the township.

The average magnetic declination was found to be 14°45' East.

Form 9180-8
(March 1969)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Daniel T. Mates	Surveying Technician
T. Stewart Burt	Surveying Technician
Frank C. Profaizer	Surveying Technician
Gail E. Reynolds	Surveying Technician
Ferrel D. Reynolds	Surveying Technician
Jerry L. Thomas	Supervisory Cadastral Surveyor
Craig P. Sylvester	Supervisory Cadastral Surveyor

Handwritten signature

400 44 030

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

163

CERTIFICATE OF SURVEY

(I) ~~(WA)~~, Glen B. Hatch, ~~Surveyor~~, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 6th day of May, 1975, (I) ~~(WA)~~ have dependently resurveyed the east boundary, a portion of the north boundary and a portion of the subdivisional lines of Township 19 South, Range 8 East

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), ~~(US)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

November 11, 1976

(Date)

(Cadastral Surveyor)
Supervisory

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Washington, D.C.
Denver, Colorado

The foregoing field notes of the dependent resurvey of the east boundary, a portion of the north boundary and a portion of the subdivisional lines of Township 19 South, Range 8 East, of the Salt Lake Meridian, Utah

executed by Glen B. Hatch, Supervisory Cadastral Surveyor having been critically examined and found correct, are hereby approved.

DEC 04 1979

(Date)

Chief, Cadastral Survey Examination and Approval Staff

CERTIFICATE OF TRANSCRIPT

~~I Certify That the foregoing transcript of the field notes of the above described surveys in~~
~~is a true copy of the original field notes.~~

(Date)

(Chief, Division of Cadastral Survey)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
ORIGINAL

164

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF THE

WEST THREE MILES OF THE SOUTH BOUNDARY,

and

A PORTION OF THE SUBDIVISIONAL LINES

OF

TOWNSHIP 19 SOUTH, RANGE 9 EAST,

Of the Salt Lake Meridian,
In the State of Utah

EXECUTED BY

Glen B. Hatch Supervisory Cadastral Surveyor

Under special instructions dated May 6, 1975, approved May 7, 1975,

_____, which provided for the surveys included under U.S. Survey/Group
Number 559, and assignment instructions dated October 31, 1975.

Survey commenced November 12, 1975

Survey completed December 11, 1975

INDEX DIAGRAM

Township 19 S., Range 9 E.

6 34	35 5 33	22 4 22	12 8	2	1
7 31	32 8 31	21 9 20	11 10	11	12
18 30	30 17 29	19 16 18	10 15	14	13
19 27	28 20 27	17 21 16	8 22	23	24
30 25	26 29 24	15 28 14	7 27	26	25
31 5	23 32 3	13 33 2	6 34	35	36

Dependent Resurvey of a portion of
T. 19 S., R. 9 E., Salt Lake Meridian, Utah

CHAINS

The history of surveys of Township 19 South, Range 9 East, Salt Lake Meridian, Utah is as follows:

T. 19 S., R. 9 E.

History of Surveys

Surveyed by Retr. or Resurveyed by

SOUTH BOUNDARY

W. 3 mi.	A. D. Ferron	1882	
E. 3 mi.	H. D. Heist and		
	W. A. Stumm	1910	
W. 3½ mi.			H. W. Miller and
			W. Byergo
			1918
E. 2 mi.			H. W. Miller and
			W. Byergo
			1918

NORTH BOUNDARY

W. 2 mi.	A. D. Ferron	1873	
			A. D. Ferron
			1880
E. 4 mi.	A. D. Ferron	1880	
E. 3 mi.			H. D. Heist and
			W. A. Stumm
			1910
All			G. B. Hatch
			1970

WEST BOUNDARY

S. 3 mi.	A. D. Ferron	1882	
N. 3 mi.	A. D. Ferron	1880	
All			G. B. Hatch, concur-
			rently

SUBDIVISION

NW portion	A. D. Ferron	1880	
SW portion	A. D. Ferron	1882	
E 1/2	H. D. Heist and		
	W. A. Stumm	1910	
Portion			H. D. Heist and
			W. A. Stumm
			1910

The following field notes describe the dependent resurvey of a portion of the south boundary, and a portion of the subdivisional lines of Township 19 South, Range 9 East, Salt Lake Meridian, Utah.

The survey was executed in accordance with specifications as set forth in the Manual of Surveying Instructions, 1973 and the Special Instructions for Group No. 559, Utah, dated May 6, 1975.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original corners or other calls of the original field notes. Identified corners were re-monumented in their original positions, lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of lines were determined by reference to true meridians established on line by hour angle observations on Polaris and altitude observations on the sun. The lines were carried forward by sustained angulation being supplemented by other numerous hour angle observations on Polaris and altitude observations on the sun.

Dependent Resurvey of a portion of
T. 19 S., R. 9 E., Salt Lake Meridian, Utah

CHAINS	<p>Distances were obtained by chaining and an electronic distance measuring device.</p> <p>The geographic position of the southeast corner of section 33, as computed from section line ties to U.S.C. and G.S. triangulation station "Buck Horn", at Latitude 39°12'36.818" N., and Longitude 110°56'28.236" N., located N. 54°09' W., 35.426 chs. dist. from the 1/4 sec. cor. of secs. 5 and 32, Tps. 18 and 19 S., R. 9 E., is as follows:</p> <p style="text-align: center;">Latitude 39°07'08" N. Longitude 110°54'21" W.</p> <p>The mean magnetic declination is 14°45' E.</p>
	<p>Dependent Resurvey of a portion of the S. Bdy., T. 19 S., R. 9 E., Salt Lake Meridian, Utah</p>
	<p>(Restoring the 1882 survey by A. D. Ferron and the 1918 resurvey by H. W. Miller and W. Byergo)</p>
	<p>Beginning at the cor. of secs. 33 and 34, on the S. bdy. of T. 19 S., R. 9 E., monumented with a sandstone, 18 x 10 x 4 ins., projecting 9 ins. above ground and dimly mkd. 3 notches on the E and W edges, with a mound of stone to the N.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T 19 S R 9 E S 33 S 34 S 4 T 20 S 1975 </p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Rebuild mound of stone, 3 ft. base, 2 ft. high, N of cor. S. 89°54' W., along the S. bdy. of sec. 33.</p> <p>Over rolling and broken bench land through scattering shadscale and greasewood undergrowth.</p>
7.80	Red Wash, drains S. 69° E.
11.60	Asc. 100 ft. abruptly over NE slope.
13.60	Spur, projects N; desc. 70 ft. over NW slope.
19.30	Same wash, course N. 45° E.; asc. gradually.
26.40	Spur, projects SE; desc. gradually.
30.20	Same wash, course S. 54° E.; asc. gradually.
38.15	Same wash, course N. 37° E.; asc. gradually.
39.22	The witness ¼ sec. cor. of sec. 4 only, T. 20 S., R. 9 E., monumented with an iron post, 1 in. diam. projecting 18 ins. above the ground, encircled by a collar of stone, with brass cap mkd.

Dependent Resurvey of a portion of the S. Bdy.
T. 19 S., R. 9 E., Salt Lake Meridian, Utah

CHAINS	
	$\frac{1}{4} \text{ S } 4 \xrightarrow{\text{WC}}$ 1918
39.90	Asc. 40 ft. abruptly over rocky SE slope.
40.26	The $\frac{1}{4}$ sec. cor. of sec. 33 only, monumented with an iron post, 1 in. diam., projecting 18 ins. above the ground, encircled by a collar of stone, with brass cap mkd.
	$\frac{1}{4} \text{ S } 33$ 1918
	S. 89°48' W., beginning new measurement.
	Over rough, broken, bench land through scattered shad-scale.
	Asc. 80 ft. abruptly over rocky SE slope.
2.40	Top of ascent, bears NE and SW; thence over bench land.
23.80	Jeep trail, bears S. 80° W. to Horn Silver Gulch Road and N. 80° E. to Gaging Station for Ferron, Cottonwood and Huntington Creeks; asc. gradually over SE slope.
30.40	S tip of bluff; desc. gradually over SW slope.
32.70	Draw, drains N; asc. gradually over NE slope.
37.50	S side of rocky point.
37.75	The closing cor. of secs. 4 and 5, T. 20 S., R. 9 E., monumented with an iron post, 2 ins. diam., projecting 18 ins. above the ground, encircled by a collar of stone, with brass cap mkd.
	$\begin{array}{c} \text{T } 19 \text{ S } \text{ R } 9 \text{ E} \\ \text{S } 33 \\ \hline \text{S } 5 \text{ } \text{S } 4 \\ \\ \text{C } \text{ C} \\ \text{T } 20 \text{ S} \\ 1918 \end{array}$
40.31	The cor. of secs. 32 and 33, monumented with a sandstone, 20 x 10 x 10 ins., projecting 10 ins. above ground and mkd. with 4 notches on E and 2 notches on W edges.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., over a (X), deeply chiseled in sandstone bedrock, 7 ins. below surface of ground, encircled by a mound of stone, 4 ft. base to top, with brass cap mkd.
	$\begin{array}{c} \text{T } 19 \text{ S } \text{ R } 9 \text{ E} \\ \text{S } 32 \text{ } \text{S } 33 \\ \hline \text{S } 5 \\ \text{T } 20 \text{ S} \\ 1975 \end{array}$
	Deposit the mkd. stone alongside the iron post.
	West, along S. bdy. of sec. 32.
	Over rolling bench land, through scattering shadscale.

Dependent Resurvey of a portion of the S. Bdy.
T. 19 S., R. 9 E., Salt Lake Meridian, Utah

CHAINS 6.00	Head of small draw, drains S; asc. gradually over E slope.
9.60	Top of ascent, bears N and S; desc. gradually over rolling land.
37.54	The $\frac{1}{4}$ sec. cor. of sec. 5 only, T. 20 S., R. 9 E., monumented with an iron post, 1 in. diam., projecting 6 ins. above a mound of stone, with brass cap mkd.
	$\frac{1}{4} \text{ S } 5$ <hr style="width: 50px; margin: auto;"/> 1918
40.55	The $\frac{1}{4}$ sec. cor. of sec. 32 only, monumented with a sandstone, 16 x 10 x 6 ins., projecting 8 ins. above ground and mkd. $\frac{1}{4}$ on the N face.
	At the corner point
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 14 ins. in the ground to bedrock, encircled by a mound of stone, 4 ft. base to top, with brass cap mkd.
	$\begin{array}{c} \text{T } 19 \text{ S } \text{ R } 9 \text{ E} \\ \frac{1}{4} \text{ S } 32 \\ \hline 1975 \end{array}$
	Deposit the mkd. stone alongside the iron post.
	<hr style="width: 100px; margin: auto;"/>
	S. 89°53' W., beginning new measurement.
	Over rolling desert land with short shadscale.
14.50	Leave rolling land; asc. 90 ft. abruptly over E slope.
16.60	Ridge, bears N and S; desc. gradually over NW slope.
26.50	Spur, projects NW; desc. 50 ft. abruptly over SW slope.
33.00	Draw, course NW; asc. gradually over NE slope.
34.70	Spur, projects NW; desc. gradually over SW slope.
36.20	Draw, course N; asc. gradually over E slope.
36.93	The closing cor. of secs. 5 and 6, T. 20 S., R. 9 E., monumented with an iron post, 2 ins. diam., projecting 12 ins. above the ground, with brass cap mkd.
	$\begin{array}{c} \text{T } 19 \text{ S } \text{ R } 9 \text{ E} \\ \text{S } 32 \\ \hline \text{S } 6 \text{ } \text{S } 5 \\ \text{C } \text{ C} \\ \text{T } 20 \text{ S} \\ 1918 \end{array}$
37.80	Spur, projects NE.
38.70	Desc. 50 ft. abruptly over W slope of spur.
40.31	The cor. of secs. 31 and 32, monumented with a sandstone, 8 x 4 x 4 ins., projecting 6 ins. above ground, and mkd. with 5 notches on the E and 1 notch on W edges.
	At the corner point
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground to bedrock, with brass cap mkd.

Dependent Resurvey of a portion of the S. Bdy.
T. 19 S., R. 9 E., Salt Lake Meridian, Utah

CHAINS	<p style="text-align: center;">T 19 S R 9 E S 31 S 32 S 6 T 20 S 1975</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.</p>
<p>2.00</p> <p>4.40</p> <p>6.40</p> <p>14.90</p> <p>15.00</p> <p>21.50</p> <p>27.00</p> <p>32.00</p> <p>36.44</p>	<p>S. 89°50' W., along S. bdy. of sec. 31.</p> <p>Over rough, broken bench land with short shadscale.</p> <p>Draw, drains N; asc. 50 ft. gradually over E slope.</p> <p>Spur, projects NE; desc. gradually over NW slope.</p> <p>Draw, drains NE; asc. gradually over SE slope.</p> <p>Head of draw; drains SE.</p> <p>Spur, projects SE; asc. 60 ft. along S slope.</p> <p>Spur, bears N and S; desc. 60 ft. over NW slope.</p> <p>Draw, drains N; asc. gradually over NE slope.</p> <p>Spur, projects NW; desc. gradually over SW slope.</p> <p>The $\frac{1}{4}$ sec. cor. of sec. 6 only, T. 20 S., R. 9 E., monumented with an iron post, 1 in. diam., projecting 12 ins. above ground, with brass cap mkd.</p>
<p>38.30</p>	<p style="text-align: center;"><u>$\frac{1}{4}$ S 6</u> 1918</p> <p>Head of draw, drains SW.</p>
<p>39.35</p>	<p>The $\frac{1}{4}$ sec. cor. of sec. 31, monumented with a sandstone, 24 x 16 x 6 ins., projecting 12 ins. above ground, and plainly mkd. $\frac{1}{4}$ on the N face, with a mound of stone N of cor.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground to bedrock, encircled with a collar of stone, with brass cap mkd.</p>
<p>4.50</p> <p>12.00</p>	<p style="text-align: center;">T 19 S R 9 E <u>$\frac{1}{4}$ S 31</u> 1975</p> <p>Deposit the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 89°48' W., beginning new measurement.</p> <p>Over rocky volcanic and sandstone formations.</p> <p>Begin abrupt descent of 140 ft. over W slope.</p> <p>Bottom of canyon, course N; asc. 80 ft. abruptly over E slope.</p>

171

Dependent Resurvey of a portion of the S. Bdy.
T. 19 S., R. 9 E., Salt Lake Meridian, Utah

CHAINS	
15.20	Spur, projects N; desc. gradually over W slope.
19.00	Head of draw, drains N; asc. gradually over NE slope.
23.00	Begin 120 ft. descent over rocky NW slope into canyon.
34.50	Bottom of canyon, course NE; asc. gradually along N side of canyon.
37.86	The cor. of Tps. 19 and 20 S., Rs. 8 and 9 E., monumented with an iron post, 2½ ins. diam., set in a mound of stone, 4 ft. base to top, with brass cap mkd.

T 19 S
R 8 E R 9 E
S 36 | S 31
S 1 | S 6
T 20 S
1962

Dependent Resurvey of a portion of the Subdivision,
T. 19 S., R. 9 E., Salt Lake Meridian, Utah

(Restoring the 1882 survey by A. D. Ferron
and the 1910 retracement by H. D. Heist and W. A. Stumm)

From the cor. of secs. 33 and 34, on the S. bdy. of the Tp.
N. 0°12' W., bet. secs. 33 and 34.

Over broken bench land and bluffs, through scattering
short shadscale; asc. 70 ft. over S slope.

14.80	Spur, slopes SW; asc. 30 ft. along E slope.
33.20	Rocky bluff, bears NE and SW; desc. gradually over NE slope.
40.53	The ¼ sec. cor. of secs. 33 and 34, monumented with a sandstone, 24 x 12 x 8 ins., projecting 12 ins. above ground and plainly mkd. ¼ on the W face.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins.
in the ground to bedrock, encircled by a collar of stone,
with brass cap mkd.

T 19 S R 9 E
¼
|
S 33 | S 34
|
1975

Deposit the mkd. stone alongside the iron post.

N. 0°08' W., beginning new measurement.

Continue over broken benches and bluffs, through short
shadscale.

Dependent Resurvey of a portion of the Subdivision,
T. 19 S., R. 9 E., Salt Lake Meridian, Utah

CHAINS					
2.80	Head of draw, drains N; desc. gradually over rolling land.				
40.83	<p>The cor. of secs. 27, 28, 33 and 34, monumented with a weathered sandstone 24 x 14 x 10 ins., firmly set in a mound of stone, with no legible mks. This position is harmoniously related to existing original cors., and is accepted as the best available evidence of the original cor.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., over a (X), deeply chiseled in sandstone bedrock, 3 ins. below surface of ground, encircled by a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 19 S R 9 E</p> <table border="1" style="margin: auto;"> <tr> <td>S 28</td> <td>S 27</td> </tr> <tr> <td>S 33</td> <td>S 34</td> </tr> </table> <p>1975</p> </div> <p>Deposit the unmkd. stone alongside the iron post.</p>	S 28	S 27	S 33	S 34
S 28	S 27				
S 33	S 34				
15.10	<p>N. 0°14' W., bet. secs. 27 and 28.</p> <p>Over rolling desert land through short shadscale; asc. gradually over rolling land.</p>				
27.00	Top of white clay knoll; desc. gradually over N slope.				
27.00	Gulch, drains NW.				
31.00	Rocky point, projects W.				
40.64	<p>The ¼ sec. cor. of secs. 27 and 28, monumented with a sandstone, 16 x 14 x 6 ins., projecting 8 ins. above ground and plainly mkd. ¼ on the W face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., over a (X), deeply chiseled in sandstone bedrock, 8 ins. below surface of ground, encircled by a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 19 S R 9 E</p> <table border="1" style="margin: auto;"> <tr> <td style="text-align: center;">¼</td> <td></td> </tr> <tr> <td>S 28</td> <td>S 27</td> </tr> </table> <p>1975</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p>	¼		S 28	S 27
¼					
S 28	S 27				
6.40	<p>N. 0°53' W., beginning new measurement.</p> <p>Over broken benches and bluffs.</p>				
6.40	S side of gorge, 140 ft. deep, drains E.				
8.75	Wash, in bottom of gorge drains E.				
10.10	N side of gorge.				
11.20	Top of bluff; desc. 40 ft. over NE slope.				

173

Dependent Resurvey of a portion of the Subdivision,
T. 19 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS	
14.50	Draw, drains SE; asc. 50 ft. over SW slope.
21.00	Top of clay knoll; desc. 60 ft. over NE slope.
27.10	Draw, drains NE; asc. 70 ft. over SE slope.
33.80	N edge of bench bears NW and SE; desc. 60 ft. over N slope.
38.32	The witness cor. of secs. 21, 22, 27 and 28, monumented with a sandstone, 14 x 8 x 6 ins., firmly set in a mound of stone, dimly mkd. 1 notch on W edge. At the witness cor. point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> W C T 19 S R 9 E ↑ S 21 S 22 S 28 S 27 1975 </div> Deposit the mkd. stone alongside the iron post. Raise a mound of stone, 3½ ft. base, 2 ft. high, W of cor. <hr style="width: 20%; margin: 10px auto;"/> N. 0°12' W., beginning new measurement.
0.10	Enter San Rafael River bottom, bears E and W.
0.25	Point for cor. of secs. 21, 22, 27 and 28, at proportionate dist., falls in old river channel where it is impractical to establish a permanent monument.
	N. 0°12' W., along E. bdy. of sec. 21. Over river bottom land, with rich cover of native grasses.
13.50	Right bank of San Rafael River, bears N. 45° E., and S. 45° W., 3 to 4 ft. deep, with alkali water.
15.50	Left bank of San Rafael River, bears N. 45° E. and S. 45° W.
17.30	Leave river bottom; asc. over gentle S slope.
20.80	Asc. 180 ft. abruptly over red sandstone ledges on rocky SE slope.
27.40	Top of rocky bluff, bears E and W; desc. 120 ft. over NW slope.
32.50	Draw, drains NW; asc. 100 ft. over SW slope.
40.02	Point for the W. ¼ sec. cor. of sec. 22 only, at midpoint latitudinally bet. the closing cor. of secs. 15 and 22, and true point for cors. 21, 22, 27 and 28, and on the E. bdy. of sec. 21. Set an iron post, 30 ins. long, 2½ ins. diam., over a (X), deeply chiseled in sandstone bedrock, encircled by a mound of stone, 4 ft. base to top, with brass cap mkd.

Dependent Resurvey of a portion of the Subdivision,
T. 19 S., R. 9 E., Salt Lake Meridian, Utah

CHAINS

T 19 S R 9 E

| ¼

| S 22

1975

40.67 The ¼ sec. cor. of sec. 21 only, monumented with a sandstone, 12 x 6 x 4 ins., mkd. ¼ on W face, firmly set in a mound of stone, 4 ft. base.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., over a (X), deeply chiseled in sandstone bedrock, 3 ins. below surface of ground, encircled by a mound of stone, 4 ft. base to top, with brass cap mkd.

T 19 S R 9 E

| ¼

| S 21

1975

Deposit the mkd. stone alongside the iron post.

N. 0°19' E., beginning new measurement.

Over rough, rocky bench land; desc. 160 ft. over sandstone ledges on NW slope.

3.40 Enter large hollow, drains W.

10.20 Leave large hollow; asc. 120 ft. abruptly over S slope.

18.70 Top of ascent, bears E and W; thence over nearly level bench.

25.60 Edge of bench, bears E and W; desc. 90 ft. over rough rocky N slope.

29.80 Draw, drains W; asc. gradually over S slope.

34.70 Top of red sandstone knoll; desc. gradually over NW slope.

39.37 The closing cor. of secs. 15 and 22, monumented with an iron post, 2 ins. diam., projecting 18 ins. above the ground, encircled by a collar of stone, with brass cap mkd.

T 19 S R 9 E

S 21	S 15	C
	S 22	C

1910

41.01 The cor. of secs. 16 and 21, monumented with a sandstone, 16 x 15 x 4 ins., projecting 8 ins. above ground and mkd. with 3 notches on S and E edges.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground to bedrock, encircled by a collar of stone, with brass cap mkd.

Dependent Resurvey of a portion of the Subdivision,
T. 19 S., R. 9 E., Salt Lake Meridian, Utah

CHAINS	
	T 19 S R 9 E S 16 S 21 S 15 1975
	Deposit the mkd. stone alongside the iron post.
	(Restoring the 1880 survey by A. D. Ferron and the 1910 resurvey by H. D. Heist and W. A. Stumm)
	N. 0°37' W., along the E. bdy. of sec. 16.
	Over rocky and mountainous bench land; asc. 80 ft. abruptly over SE slope.
4.80	Rocky spur, projects SW; desc. 140 ft. over NW slope.
10.60	Draw, drains SW; asc. 160 ft. abruptly over SE slope.
21.00	Rocky ridge, bears E and W; desc. 100 ft. abruptly over N slope.
31.10	Draw, drains NW; asc. 40 ft. over SW slope.
36.80	Spur, projects NW; desc. 30 ft. abruptly over NW slope.
38.20	Point for the W. ¼ sec. cor. of sec. 15, at midpoint latitudinally, bet. closing cors and on the E. bdy. of sec. 16.
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground to bedrock, encircled by a collar of stone, with brass cap mkd.
	T 19 S R 9 E ¼ S 15 1975
40.04	The ¼ sec. cor. of sec. 16, monumented with an iron post, 1 in. diam., projecting 6 ins. above the ground, with brass cap mkd.
	¼ S 16 1975 1910
	Removed the mks. (S 15) and added (1975) to the brass cap markings.
	<hr style="width: 20%; margin: auto;"/>
	N. 0°14' W., beginning new measurement.
	Over sandstone ledges and broken bench land; desc. 80 ft. over general NW slope.
7.20	Wash, course S. 65° W.; asc. 60 ft. over SE slope.
14.80	Rocky spur, projects SW; desc. 70 ft. over NW slope.
26.30	Draw, drains W; asc. 60 ft. over S slope.
32.80	Rocky spur, projects NW; desc. 80 ft. abruptly over NW slope.

Dependent Resurvey of a portion of the Subdivision,
T. 19 S., R. 9 E., Salt Lake Meridian, Utah

CHAINS 38.00	<p>The closing cor. of secs. 10 and 15, monumented with an iron post, 2 ins. diam., projecting 6 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T 19 S R 9 E S 9 C C S 10 S 16 S 15 1910</p>
40.16	<p>The cor. of secs. 9 and 16, monumented with an iron post, 2 ins. diam., projecting 12 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T 19 S R 9 E S 9 S 16 1910</p>
	<p>N. 0°12' W., along the E. bdy. of sec. 9.</p> <p>Over rocky mountainous land; desc. 40 ft. abruptly over NW slope.</p> <p>1.80 Wash, course S. 82° W.; asc. 90 ft. over S slope.</p> <p>5.70 Rocky spur, projects SW; desc. 90 ft. over NW slope.</p> <p>12.60 Draw, drains SW; as. 120 ft. over SE slope.</p> <p>22.70 Ridge, bears NE and SW; desc. gradually over NW slope.</p> <p>37.79 Point for the W. $\frac{1}{4}$ sec. cor. of sec. 10 only, at midpoint latitudinally bet. closing cors. and on the E. bdy. of sec. 9.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground to bedrock, encircled by a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 19 S R 9 E ¼ S 10 1975</p>
40.18	<p>The $\frac{1}{4}$ sec. cor. of sec. 9 only, monumented with an iron post, 1 in. diam., badly deteriorated and defectively mkd., projecting 12 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T 19 S R 9 E ¼ S 9 S 10 1918</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 19 S R 9 E ¼ S 9 1975</p>

177

Dependent Resurvey of a portion of the Subdivision,
T. 19 S., R. 9 E., Salt Lake Meridian, Utah

CHAINS									
	<p>Deposit the defectively mkd. iron post inverted and alongside the new iron post.</p>								
	<p>Raise a mound of stone, 4 ft. base, 2 ft. high, W of cor.</p>								
	<p>N. 0°16' W., beginning new measurement.</p>								
	<p>Over rocky sandstone ledges; desc. 80 ft. over rolling NE slope.</p>								
33.10	<p>Wash, course N. 34° W.; asc. over SW slope.</p>								
37.56	<p>The closing cor. of secs. 3 and 10, monumented with a mound of stone, with no evidence of an iron post previously set. This position is harmoniously related to existing original cors. and is accepted as the best available evidence of the original cor.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 19 S R 9 E</p> <table border="0"> <tr> <td>S 9</td> <td> </td> <td>S 3</td> <td>C</td> </tr> <tr> <td></td> <td> </td> <td>S 10</td> <td>C</td> </tr> </table> <p>1975</p> </div>	S 9		S 3	C			S 10	C
S 9		S 3	C						
		S 10	C						
40.16	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, E of cor.</p> <p>The cor. of secs. 4 and 9, monumented with a sandstone, 12 x 10 x 8 ins., projecting 6 ins. above the ground, and mkd. with 5 notches on S and 3 notches on E edges, with a mound of stone, W of cor.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 19 S R 9 E</p> <table border="0"> <tr> <td>S 4</td> <td> </td> <td>S 3</td> </tr> <tr> <td>S 9</td> <td> </td> <td>S 3</td> </tr> </table> <p>1975</p> </div>	S 4		S 3	S 9		S 3		
S 4		S 3							
S 9		S 3							
	<p>Deposit the mkd. stone alongside the iron post.</p>								
	<p>Rebuild mound of stone, 3 ft. base, 2 ft. high, W of cor.</p>								
	<p>N. 0°10' W., along E. bdy. of sec. 4.</p>								
	<p>Over broken benches, through shadscale and greasewood; asc. over SE slope.</p>								
27.00	<p>Top of ascent bears NE and SW; desc. over NW slope.</p>								
37.41	<p>Point for the W. ¼ sec. cor. of sec. 3 only, at proportionate distance latitudinally bet. the closing cor. of secs. 3 and 10, and the cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., and on the E. bdy. of sec. 4.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>								

Dependent Resurvey of a portion of the Subdivision,
T. 19 S., R. 9 E., Salt Lake Meridian, Utah

CHAINS

T 19 S R 9 E
|
1/4
|
S 3
|
1975

Place a steel fence post alongside the iron post.

Cor. is located on E slope, 60 lks. W of wash, draining N.

40.33 The 1/4 sec. cor. of sec. 4, monumented with a sandstone, 16 x 12 x 4 ins., projecting 8 ins. above ground, and mkd. 1/4 on W face, with a mound of stone W of cor.

At the corner point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 19 S R 9 E
|
1/4
|
S 4
|
1975

Deposit the mkd. stone alongside the iron post.

Rebuild mound of stone, 3 ft. base, 2 ft. high, W of cor.

Cor. is located on W slope of spur.

N. 0°36' W., beginning new measurement.

Over nearly level desert land.

10.50 Road, unimproved, 16 lks. wide, bears N. 49° W., and S. 49° E.

30.40 Wash, drains S. 81° W.

32.30 Same road, unimproved, 16 lks. wide, bears N. 39° E., and S. 39° W.

37.30 Wash, drains S. 60° W.

40.66 The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. above the ground, with brass cap mkd.

T 18 S R 9 E
S 33 | S 34
S 4 | S 3
T 19 S R 9 E
1970

(Restoring the 1882 survey by A. D. Ferron)

From the cor. of secs. 32 and 33, on the S. bdy. of the Tp., heretofore described.

N. 0°17' W., bet. secs. 32 and 33.

Over rough, broken bench land, through shadscale undergrowth.

Dependent Resurvey of a portion of the Subdivision,
T. 19 S., R. 9 E., Salt Lake Meridian, Utah

CHAINS	
17.80	Head of draw, drains NE.
22.10	N edge of bench, bears NW and SE; desc. 50 ft. over NE slope.
34.00	Gulch, drains SW; asc. 50 ft. over SW slope.
39.80	Spur, sloping S; thence along W slope.
40.30	Point for the 1/4 sec. cor. of secs. 32 and 33, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<pre> T 19 S R 9 E 1/4 S 32 S 33 1975 </pre>
	Place steel fence post alongside iron post.
	Cor. is located on W slope of clay spur; desc. 50 ft. over broken NW slope.
46.70	Draw, drains NE; asc. 50 ft. over SE slope.
51.20	Clay spur, slopes NE; desc. 50 ft. gradually over NW slope.
59.30	Wash, drains NE.
63.80	Wash, drains NE; asc. over rolling land.
72.10	Wash, drains NE; asc. SE slope.
80.60	The cor. of secs. 28, 29, 32 and 33, monumented with a sandstone, 24 x 14 x 14 ins., set in a mound of stone, plainly mkd. 1 notch on S and 4 notches on the E edges.
	At the corner point
	Set an iron post, 30 ins. long, 2 1/2 ins. diam., over a (X), deeply chiseled in sandstone bedrock, 8 ins. below surface of the ground, encircled by a mound of stone, 4 ft. base to top, with brass cap mkd.
	<pre> T 19 S R 9 E S 29 S 28 S 32 S 33 1975 </pre>
	Deposit the mkd. stone alongside the iron post.
	From the cor. of secs. 27, 28, 33 and 34.
	S. 88°55' W., bet. secs. 28 and 33.
	Over nearly level desert land with some shadscale.
21.90	Wash, drains N. 9° E.
29.80	Jeep trail, bears S. 23° W. to Horn Silver Gulch Road and N. 23° E. to Gaging Station for Ferron, Cottonwood and Huntington Creeks.

Dependent Resurvey of a portion of the Subdivision,
T. 19 S., R. 9 E., Salt Lake Meridian, Utah

CHAINS	
36.70	Edge of bench, bears NE; desc. gradually over NW slope.
38.00	Hollow, drains N; asc. over NE slope.
40.48	The $\frac{1}{4}$ sec. cor. of secs. 28 and 33, monumented with a sandstone, 16 x 12 x 4 ins., projecting 8 ins. above ground, and mkd. $\frac{1}{4}$ on N face.
	At the corner point
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, encircled by a collar of stone, with brass cap mkd.
	T 19 S R 9 E $\frac{1}{4}$ $\frac{S 28}{S 33}$ 1975
	Deposit the mkd. stone alongside the iron post.
	Place steel fence post alongside iron post.
	<hr style="width: 20%; margin: auto;"/> S. $89^{\circ}42'$ W., beginning new measurement.
	Over broken bluffs and benches; asc. gradually.
2.80	Spur, bears N. 10° W.; desc. gradually over W slope.
5.10	Draw, drains N. 10° W.; asc. gradually over NE slope.
18.00	Wash, drains N. 57° E.
29.60	Asc. 40 ft. over E slope of bluff.
40.23	The cor. of secs. 28, 29, 32 and 33.
	N. $0^{\circ}08'$ E., bet. secs. 28 and 29.
	Over broken benches and sandstone ledges; desc. gradually over NW slope.
6.80	Gulch, drains NE; asc. gradually over SE slope.
12.10	Spur, projects NE; desc. gradually over N slope.
18.00	Gulch, drains NE; asc. gradually over SE slope.
22.50	Top of ascent, slopes E; desc. gradually over NE slope.
26.70	Gulch, drains E; asc. gradually over S slope.
29.00	Top of bluff, bears E and W; desc. 100 ft. over N slope.
33.80	Enter Ferron Creek bottom.
37.00	Ferron Creek, 50 lks. wide, 18 ins. deep, course N. 64° E.
40.36	Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a portion of the Subdivision,
T. 19 S., R. 9 E., Salt Lake Meridian, Utah

CHAINS

T 19 S R 9 E

$$\begin{array}{c} \frac{1}{4} \\ | \\ \text{S } 29 \mid \text{S } 28 \\ | \\ 1975 \end{array}$$

Place steel fence post alongside iron post.

- 52.70 Leave Ferron Creek bottom; asc. gradually over S slope.
- 54.90 Point of spur, projects E; desc. gradually over N slope.
- 56.50 Draw, drains E; asc. 50 ft. over S slope.
- 61.10 Top of ascent, bears E and W; thence over nearly level bench.
- 73.20 Draw, drains SE.
- 80.72 The cor. of secs. 20, 21, 28 and 29, monumented with a weathered sandstone, 16 x 14 x 8 ins., projecting 8 ins. above ground, with no legible mkds. This position is harmoniously related to existing original cors., and is accepted as the best available evidence of the original cor.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{T } 19 \text{ S } \text{R } 9 \text{ E} \\ \text{S } 20 \mid \text{S } 21 \\ \text{S } 29 \mid \text{S } 28 \\ 1975 \end{array}$$

Deposit the unmkd. stone alongside the iron post.

Place steel fence post alongside iron post.

Cor. is located at base of E slope of small clay spur sloping S.

From the cor. of secs. 21, 22, 27 and 28.

N. 88°58' W., bet. secs. 21 and 28.

Over river bottom and broken benches through scattered cottonwood trees and willows.

- 7.10 Right bank of San Rafael River, bears N. 22° E., and S. 22° W., river is 90 lks. wide, 2 to 4 ft. deep, alkali-water.
- 8.00 Left bank of San Rafael River, bears N. 22° E. and S. 22° W.
- 19.90 Left bank of San Rafael River, bears N. 26° W. and S. 26° E., 1.10 chs. wide, 2 to 4 ft. deep.
- 21.00 Right bank of San Rafael River, bears N. 26° W. and S. 26° E.
- 27.20 Jeep trail, bears S to Horn Silver Gulch Road and N to Gaging Station for Ferron, Cottonwood and Huntington Creeks.

Dependent Resurvey of a portion of the Subdivision,
T. 19 S., R. 9 E., Salt Lake Meridian, Utah

CHAINS	
31.30	Ferron Creek, 70 lks. wide, 2 ft. deep, course N. 20° E.
32.20	Leave creek and river bottom; asc. 60 ft. abruptly over SE slope.
40.96	<p>The ¼ sec. cor. of secs. 21 and 28, monumented with a sandstone, 10 x 10 x 7 ins., set in a mound of stone, with no legible mks. This position is harmoniously related to existing original cors. and is accepted as the best available evidence of the original cor.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, encircled by a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 19 S R 9 E</p> <p>¼ $\frac{S 21}{S 28}$</p> <p>1975</p> </div> <p>Deposit the unmkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/>
7.60	S. 89°45' W., beginning new measurement.
23.10	Over broken benches through shadscale.
7.60	Draw, drains S. 58° E.; asc. gradually over NE slope.
23.10	Spur, projects S; desc. gradually over SW slope.
26.30	Head of draw, drains SW; asc. over SE slope.
38.79	The cor. of secs. 20, 21, 28 and 29.
24.20	N. 0°23' W., bet. secs. 20 and 21.
40.59	Over rolling, broken, benches and sandstone ledges.
24.20	Spur, projects W; desc. gradually over NW slope.
40.59	<p>The ¼ sec. cor. of secs. 20 and 21, monumented with a sandstone, 18 x 12 x 6 ins., projecting 9 ins. above ground, and dimly mkd. ¼ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, encircled by a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 19 S R 9 E</p> <p>¼</p> <p>S 20 S 21</p> <p>1975</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Cor. is located on W end of spur, 50 ft. above base.</p> <hr style="width: 20%; margin: 10px auto;"/>

Dependent Resurvey of a portion of the Subdivision,
T. 19 S., R. 9 E., Salt Lake Meridian, Utah

CHAINS	
	N. 0°19' E., beginning new measurement. Desc. over sandstone ledges into creek bottom.
4.20	Gulch, drains NE.
8.80	Enter Cottonwood Creek bottoms.
27.30	Cottonwood Creek, 70 lks. wide, 16 ins. deep, course S. 56° E., from S. 85° W.
28.20	Leave Cottonwood Creek bottom; asc. abruptly over broken SE slope.
40.07	The cor. of secs. 16, 17, 20 and 21, monumented with a sandstone, 16 x 8 x 6 ins., projecting 8 ins. above ground, and mkd. with 3 notches on S edge, and 4 notches on E edge. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, encircled by a collar of stone, with brass cap mkd. <div style="text-align: center;"> <p>T 19 S R 9 E S 17 S 16 S 20 S 21 1975</p> </div> Deposit the mkd. stone alongside the iron post. Cor. is located in small draw of clay hill, near base of E slope.
	From the cor. of secs. 16 and 21. S. 89°39' W., bet. secs. 16 and 21. Over sandstone ledges; asc. abruptly over SE slope.
3.10	Spur, projects SW; desc. 100 ft. over NW slope.
9.50	Draw, drains S; asc. 100 ft. over E slope.
15.60	Spur, projects S; desc. 100 ft. over W slope.
19.80	Enter Huntington Creek bottom.
26.90	Huntington Creek, 60 lks. wide, 2 ft. deep, course S. 58° E.
28.80	Huntington Creek, course N. 39° E.
31.70	Huntington Creek, course S. 64° E.
37.10	Huntington Creek, course N. 30° E.
39.99	The ¼ sec. cor. of secs. 16 and 21, monumented with a sandstone, 12 x 8 x 6 ins., projecting 6 ins. above ground, and dimly mkd. ¼ on N face. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, encircled by a collar of stone, with brass cap mkd.

Dependent Resurvey of a portion of the Subdivision,
T. 19 S., R. 9 E., Salt Lake Meridian, Utah

CHAINS	
	<p style="text-align: center;">T 19 S R 9 E $\frac{1}{4}$ $\frac{S 16}{S 21}$ 1975</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Cor. is located on left bank of Huntington Creek, bears S. 12° E. and curves SW.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°42' W., beginning new measurement.</p> <p>Over creek bottom, through scattered cottonwood trees.</p> <p>0.60 Bend in Huntington Creek, course enters at S. 47° W., leaves at S. 12° E.</p> <p>7.80 Huntington Creek, course S. 13° E.</p> <p>13.50 Leave Huntington Creek bottoms; asc. gradually over NE slope.</p> <p>19.80 Spur, projects N; desc. gradually over NW slope.</p> <p>31.20 Draw, drains N; asc. over NE slope.</p> <p>36.50 Gulch, drains SE.</p> <p>39.85 The cor. of secs. 16, 17, 20 and 21.</p> <hr/> <p>N. 0°05' E., bet. secs. 16 and 17.</p> <p>Over broken benches and sandstone ledges.</p> <p>5.80 Gulch, drains NE.</p> <p>18.00 Hollow, drains E; asc. 180 ft. over S slope.</p> <p>29.00 Spur, slopes NE from NW; desc. NE slope.</p> <p>40.16 Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 17, at proportionate dist. falls on E slope of wash, where it is impracticable to establish a permanent monument; there is no remaining evidence of the original cor.</p> <p>40.31 Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 16 and 17.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">W C T 19 S R 9 E $\frac{1}{4}$ ↓ S 17 S 16 ↓ 1975</p> <p>Raise a mound of stone, 4 ft. base, 2 ft. high, W of cor.</p> <p>Cor. is located on top of small red spur, projecting NE.</p> <p>43.10 Gulch, drains E; asc. over SE slope.</p>

Dependent Resurvey of a portion of the Subdivision,
T. 19 S., R. 9 E., Salt Lake Meridian, Utah

CHAINS																					
52.50	Spur, slopes E; desc. over NE slope.																				
59.00	Gulch, drains E; asc. over SE slope.																				
80.32	<p>The cor. of secs. 8, 9, 16 and 17, monumented with a sandstone, 24 x 10 x 6 ins., projecting 12 ins. above ground, and mkd. with 4 notches on the S and E edges.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, encircled by a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 19 S R 9 E</p> <table border="1" style="margin: auto;"> <tr> <td>S 8</td> <td>S 9</td> </tr> <tr> <td>S 17</td> <td>S 16</td> </tr> </table> <p>1975</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p>	S 8	S 9	S 17	S 16																
S 8	S 9																				
S 17	S 16																				
	<p>From the cor. of secs. 9 and 16.</p> <p>S. 89°37' W., bet. secs. 9 and 16.</p> <p>Over sandstone formations and broken benches; asc. gradually along general N slope.</p> <tr> <td data-bbox="284 1298 440 1338">13.70</td> <td data-bbox="440 1298 1377 1338">Spur, projects NW; desc. abruptly over broken NW slope.</td> </tr> <tr> <td data-bbox="284 1365 440 1405">25.20</td> <td data-bbox="440 1365 1377 1405">Enter Huntington Creek bottom.</td> </tr> <tr> <td data-bbox="284 1432 440 1473">27.60</td> <td data-bbox="440 1432 1377 1473">Wash, course S. 62° W.</td> </tr> <tr> <td data-bbox="284 1499 440 1540">38.10</td> <td data-bbox="440 1499 1377 1540">Same wash, course N. 31° W.</td> </tr> <tr> <td data-bbox="284 1567 440 2577">39.48</td> <td data-bbox="440 1567 1377 2577"> <p>The ¼ sec. cor. of secs. 9 and 16, monumented with a mound of stone; there is no other visible remaining evidence of the original cor. This position is harmoniously related to existing original cors. and is accepted as the best available evidence of the original cor.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, encircled by a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 19 S R 9 E</p> <table border="1" style="margin: auto;"> <tr> <td>¼ S 9</td> <td></td> </tr> <tr> <td>S 16</td> <td></td> </tr> </table> <p>1975</p> </div> <p>S. 89°55' W., beginning new measurement.</p> <p>Over creek bottom, through scattered willow undergrowth and cottonwood trees.</p> <tr> <td data-bbox="284 2333 440 2373">2.20</td> <td data-bbox="440 2333 1377 2373">Huntington Creek, 50 lks. wide, 20 ins. deep, course S. 29° W.</td> </tr> <tr> <td data-bbox="284 2427 440 2467">7.80</td> <td data-bbox="440 2427 1377 2467">Leave Huntington Creek bottom; asc. gradually along N slope.</td> </tr> <tr> <td data-bbox="284 2521 440 2561">22.30</td> <td data-bbox="440 2521 1377 2561">Draw, drains N; asc. 40 ft. over NE slope.</td> </tr> </td></tr>	13.70	Spur, projects NW; desc. abruptly over broken NW slope.	25.20	Enter Huntington Creek bottom.	27.60	Wash, course S. 62° W.	38.10	Same wash, course N. 31° W.	39.48	<p>The ¼ sec. cor. of secs. 9 and 16, monumented with a mound of stone; there is no other visible remaining evidence of the original cor. This position is harmoniously related to existing original cors. and is accepted as the best available evidence of the original cor.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, encircled by a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 19 S R 9 E</p> <table border="1" style="margin: auto;"> <tr> <td>¼ S 9</td> <td></td> </tr> <tr> <td>S 16</td> <td></td> </tr> </table> <p>1975</p> </div> <p>S. 89°55' W., beginning new measurement.</p> <p>Over creek bottom, through scattered willow undergrowth and cottonwood trees.</p> <tr> <td data-bbox="284 2333 440 2373">2.20</td> <td data-bbox="440 2333 1377 2373">Huntington Creek, 50 lks. wide, 20 ins. deep, course S. 29° W.</td> </tr> <tr> <td data-bbox="284 2427 440 2467">7.80</td> <td data-bbox="440 2427 1377 2467">Leave Huntington Creek bottom; asc. gradually along N slope.</td> </tr> <tr> <td data-bbox="284 2521 440 2561">22.30</td> <td data-bbox="440 2521 1377 2561">Draw, drains N; asc. 40 ft. over NE slope.</td> </tr>	¼ S 9		S 16		2.20	Huntington Creek, 50 lks. wide, 20 ins. deep, course S. 29° W.	7.80	Leave Huntington Creek bottom; asc. gradually along N slope.	22.30	Draw, drains N; asc. 40 ft. over NE slope.
13.70	Spur, projects NW; desc. abruptly over broken NW slope.																				
25.20	Enter Huntington Creek bottom.																				
27.60	Wash, course S. 62° W.																				
38.10	Same wash, course N. 31° W.																				
39.48	<p>The ¼ sec. cor. of secs. 9 and 16, monumented with a mound of stone; there is no other visible remaining evidence of the original cor. This position is harmoniously related to existing original cors. and is accepted as the best available evidence of the original cor.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, encircled by a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 19 S R 9 E</p> <table border="1" style="margin: auto;"> <tr> <td>¼ S 9</td> <td></td> </tr> <tr> <td>S 16</td> <td></td> </tr> </table> <p>1975</p> </div> <p>S. 89°55' W., beginning new measurement.</p> <p>Over creek bottom, through scattered willow undergrowth and cottonwood trees.</p> <tr> <td data-bbox="284 2333 440 2373">2.20</td> <td data-bbox="440 2333 1377 2373">Huntington Creek, 50 lks. wide, 20 ins. deep, course S. 29° W.</td> </tr> <tr> <td data-bbox="284 2427 440 2467">7.80</td> <td data-bbox="440 2427 1377 2467">Leave Huntington Creek bottom; asc. gradually along N slope.</td> </tr> <tr> <td data-bbox="284 2521 440 2561">22.30</td> <td data-bbox="440 2521 1377 2561">Draw, drains N; asc. 40 ft. over NE slope.</td> </tr>	¼ S 9		S 16		2.20	Huntington Creek, 50 lks. wide, 20 ins. deep, course S. 29° W.	7.80	Leave Huntington Creek bottom; asc. gradually along N slope.	22.30	Draw, drains N; asc. 40 ft. over NE slope.										
¼ S 9																					
S 16																					
2.20	Huntington Creek, 50 lks. wide, 20 ins. deep, course S. 29° W.																				
7.80	Leave Huntington Creek bottom; asc. gradually along N slope.																				
22.30	Draw, drains N; asc. 40 ft. over NE slope.																				

Dependent Resurvey of a portion of the Subdivision,
T. 19 S., R. 9 E., Salt Lake Meridian, Utah

CHAINS	
33.60	Draw, drains NW.
39.67	The cor. of secs. 8, 9, 16 and 17.
	N. 0°10' W., bet. secs. 8 and 9.
	Over sandstone ledges and rolling desert land; desc. abruptly over NE slope.
7.80	Enter hollow, drains E.
19.70	Leave hollow.
28.40	Wash, drains S. 47° E.; asc. over SW slope.
40.02	The $\frac{1}{4}$ sec. cor. of secs. 8 and 9, monumented with a sandstone, 16 x 12 x 4 ins., projecting 8 ins. above ground and dimly mkd. $\frac{1}{4}$ on W side.
	At the corner point
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, encircled by a collar of stone, with brass cap mkd.
	T 19 S R 9 E $\frac{1}{4}$ S 8 S 9 1975
	Deposit the mkd. stone alongside the iron post.

	N. 0°03' W., beginning new measurement.
	Over broken and rolling bench land.
3.10	Top of spur, projects SE; desc. abruptly.
6.30	Draw, drains E.
28.10	Draw, drains E.
38.90	Draw, drains SE.
40.36	The cor. of secs. 4, 5, 8 and 9, monumented with a limestone, 15 x 10 x 5 ins., projecting 7 ins. above ground, and mkd. with 5 notches on S and 4 notches on E edges, with a mound of stone, W of cor.
	At the corner point
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 19 S R 9 E S 5 S 4 S 8 S 9 1975
	Deposit the mkd. stone alongside the iron post.
	Raise a mound of stone, 4 ft. base, 2 ft. high, W of cor.

187

Dependent Resurvey of a portion of the Subdivision,
T. 19 S., R. 9 E., Salt Lake Meridian, Utah

CHAINS	
	From the cor. of secs. 4 and 9.
	S. 88°43' W., bet. secs. 4 and 9.
	Over broken benches with creek bottom and wash.
4.70	Wash, drains N. 42° W.; asc. gradually over NE slope.
11.80	Spur, slopes NW; desc. gradually over SW slope.
17.20	Gulch, drains N; asc. over E slope.
22.00	Top of ascent, bears N and S; desc. over SW slope.
28.00	Wash, drains N. 65° W.; asc. over NE slope.
34.50	Gulch, drains N.
40.14	The $\frac{1}{4}$ sec. cor. of secs. 4 and 9, monumented with a mound of stone; there is no other visible remaining evidence of the original cor. This position is harmoniously related to existing original cors. and is accepted as the best available evidence of the original cor.
	At the corner point
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 19 S R 9 E $\frac{1}{4}$ $\frac{S 4}{S 9}$ 1975
	Raise a mound of stone, 4 ft. base, 2 ft. high, N of cor.

	N. 89°03' W., beginning new measurement.
	Desc. over W slope into creek bottoms.
8.30	Enter Huntington Creek bottoms.
11.00	Huntington Creek, 60 lks. wide, 18 ins. deep, course S. 60° W.
16.20	Leave Huntington Creek bottoms; asc. gradually over NE slope.
38.85	The cor. of secs. 4, 5, 8 and 9.
	N. 1°19' W., bet. secs. 4 and 5.
	Over rolling desert land, through shadscale undergrowth.
13.10	Wash, drains N. 79° E.
40.39	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5, determined latitudinally by a barbed wire fence extending E and W, and longitudinally on line bet. sec. cors., found a sandstone, 10 x 8 x 5 ins., dimly mkd. $\frac{1}{4}$ lying loose on the ground.
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a portion of the Subdivision,
T. 19 S., R. 9 E., Salt Lake Meridian, Utah

CHAINS	
	<p style="text-align: center;">T 19 S R 9 E $\frac{1}{4}$ S 5 S 4 1975</p> <p>Deposit the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1°19' W., beginning new measurement.</p> <p>Over gently rolling desert land.</p> <p>28.50 Wash, drains E.</p> <p>40.17 The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., projecting 6 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T 18 S R 9 E S 32 S 33 S 5 S 4 T 19 S R 9 E 1970</p>
	<p>From the cor. of secs. 31 and 32, on the S. bdy. of the Tp., heretofore described.</p> <p>N. 0°16' E., bet. secs. 31 and 32.</p> <p>Over rough broken benches and sandstone ledges.</p> <p>5.10 Draw, 40 ft. deep, drains NW.</p> <p>7.30 Ridge, bears NW.</p> <p>11.20 Gulch, drains NE.</p> <p>15.40 Small draw, drains NE.</p> <p>18.80 Gulch, drains NW.</p> <p>27.70 Gulch, drains NE.</p> <p>32.60 Gulch, drains NW.</p> <p>39.94 The ¼ sec. cor. of secs. 31 and 32, monumented with a sandstone, 24 x 16 x 4 ins., projecting 12 ins. above ground, and mkd. ¼ on the W face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, encircled by a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 19 S R 9 E $\frac{1}{4}$ S 31 S 32 1975</p> <p>Deposit the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/>

189

Dependent Resurvey of a portion of the Subdivision,
T. 19 S., R. 9 E., Salt Lake Meridian, Utah

CHAINS	
	N. 0°46' W., beginning new measurement. Over sandstone formations.
9.00	Head of draw, drains W; asc. 100 ft. over SW slope.
13.70	Draw, drains SW.
17.30	Top of bluff, bears NE and SW; 100 ft. over broken NW slope.
21.50	Enter Ferron Creek bottom.
28.70	Bend in Ferron Creek, course enters from S. 58° W., and curves N. 58° W.
35.00	Ferron Creek, 60 lks. wide, 1 ft. deep, course N. 59° E.
39.56	The cor. of secs. 29, 30, 31 and 32, monumented with a weathered sandstone, 12 x 8 x 6 ins., projecting 6 ins. out of ground, in a sandy area with no other stones in the immediate proximity. This position is harmoniously related to existing original cors. and is accepted as the best available evidence of the original cor. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 19 S R 9 E S 30 S 29 S 31 S 32 1975 </div> Deposit the unmkd. stone alongside the iron post.
	From the cor. of secs. 28, 29, 32 and 33. S. 89°10' W., bet. secs. 29 and 32. Over red sandstone formations and broken benches.
2.10	Wash, drains NE.
14.00	Wash, drains NE.
20.50	Base of bluff; asc. 200 ft. over broken NE slope.
25.40	Top of bluff; desc. 180 ft. over broken NW slope.
40.38	Point for the ¼ sec. cor. of secs. 29 and 32, at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, encircled by a mound of stone, 3 ft. base to top, with brass cap mkd. <div style="text-align: center;"> T 19 S R 9 E ¼ S 29 S 32 1975 </div> Cor. is located on W slope of bluff.

Dependent Resurvey of a portion of the Subdivision,
T. 19 S., R. 9 E., Salt Lake Meridian, Utah

CHAINS	
42.40	Wash, drains NW.
53.30	Draw, drains NW; asc. over broken NE slope.
59.40	Spur, projects N; desc. over NW slope.
67.70	Wash, drains N.
72.80	Enter Ferron Creek bottoms.
74.10	Ferron Creek, 50 lks. wide, 16 ins. deep, course N. 5° E.
80.76	The cor. of secs. 29, 30, 31 and 32.
	N. 89°02' W., bet. secs. 30 and 31.
	Over creek bottom, broken benches and sandstone formations.
1.90	Ferron Creek, 50 lks. wide, 16 ins. deep, course S. 26° W.
8.80	Ferron Creek, course N. 19° E.
16.60	Gulch, drains NE; asc. 100 ft. abruptly over steep NE slope.
20.20	Top of ascent, bears NW and SE; thence over nearly level bench.
27.60	Head of draw, drains SE.
39.93	The $\frac{1}{4}$ sec. cor. of secs. 30 and 31, monumented with a sandstone, 20 x 15 x 3 ins., firmly set in a mound of stone, and plainly mkd. $\frac{1}{4}$ on N face.
	At the corner point
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, encircled by a collar of stone, with brass cap mkd.
	<p style="text-align: center;">T 19S R 9 E $\frac{1}{4}$ $\frac{S 30}{S 31}$ 1975</p>
	Deposit the mkd. stone alongside the iron post.
	S. 89°27' W., beginning new measurement.
	Over sandstone formations with broken benches.
6.80	Gulch, drains SW; asc. along S slope.
13.00	Low spur, slopes SW; desc. over NW slope.
23.30	Wash, drains S.
27.50	Wash, drains S. 25° E.; asc. over broken NE slope.
38.24	The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented with an iron post, 2 $\frac{1}{2}$ ins. diam., set in a mound of stone, 4 ft. base to top, with brass cap mkd.

Dependent Resurvey of a portion of the Subdivision,
T. 19 S., R. 9 E., Salt Lake Meridian, Utah

CHAINS	<p style="text-align: center;">T 19 S R 8 E R 9 E S 25 S 30 S 36 S 31 1975</p>
	<p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°27' W., bet. secs. 29 and 30.</p> <p>Over creek bottom.</p> <p>12.70 Leave Ferron Creek bottom; asc. 150 ft. abruptly over broken S slope.</p> <p>17.60 Spur, projects E; desc. over N slope.</p> <p>19.80 Draw, drains SE; asc. over S slope.</p> <p>26.00 Draw, drains S. 5° E.</p> <p>33.40 Ridge, bears NW and SE; desc. over broken N slope.</p> <p>36.70 Wash, drains NE.</p> <p>39.00 Same wash, drains SW.</p> <p>40.29 The ¼ sec. cor. of secs. 29 and 30, monumented with a sandstone, 20 x 8x 5 ins., projecting 10 ins. above ground, and dimly mkd. ¼ on the W face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 19 S R 9 E ¼ S 30 S 29 1975</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Place steel fence post alongside iron post.</p> <p>Cor. is located 50 lks. W of wash, draining SW.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1°03' E., beginning new measurement.</p> <p>Over sandstone ledges and broken benches.</p> <p>0.70 Same wash, drains SE; asc. abruptly 120 ft. over broken SW slope.</p> <p>6.00 Ridge, bears NW and SE; desc. over broken NE slope.</p> <p>13.10 Gulch, drains E; asc. over SW slope.</p>

Dependent Resurvey of a portion of the Subdivision,
T. 19 S., R. 9 E., Salt Lake Meridian, Utah

CHAINS	
16.90	Spur, projects SE; desc. over broken NE slope.
25.30	Wash, drains SE; asc. broken SW slope.
41.42	The cor. of secs. 19, 20, 29 and 30, monumented with a sandstone, 15 x 8 x 4 ins., firmly set in a mound of stone, mkd. with 2 notches on S and 5 notches on E edges.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, encircled by a mound of stone, 4 ft. base to top, with brass cap mkd.
	$\begin{array}{r} T\ 19\ S\ R\ 9\ E \\ \hline S\ 19\ \ S\ 20 \\ S\ 30\ \ S\ 29 \\ \hline 1975 \end{array}$
	Deposit the mkd. stone alongside the iron post.
	From the cor. of secs. 20, 21, 28 and 29.
	S. 89°51' W., bet. secs. 20 and 29.
	Over rough broken benches and sandstone ledges.
3.80	Gulch, drains SE; asc. over NE slope.
7.00	Gulch, drains SE.
25.00	Ridge, bears NE and SW; desc. over NW slope.
40.22	Point for the ¼ sec. cor. of secs. 20 and 29, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{r} T\ 19\ S\ R\ 9\ E \\ \hline \frac{1}{4} \quad S\ 20 \\ \hline S\ 29 \\ \hline 1975 \end{array}$
	Place steel fence post alongside iron post.
	Cor. is located in ravine, drains S. 20° W.
52.80	Gulch, drains S.
55.40	Gulch, drains SE.
61.90	Head of draw, drains SW.
68.80	Draw, drains SE.
80.44	The cor. of secs. 19, 20, 29 and 30.
	S. 89°35' W., bet. secs. 19 and 30.
	Over sandstone ledges and rolling desert land; asc. gradually over E slope.
22.30	Top of ascent; thence over nearly level bench.

Dependent Resurvey of a portion of the Subdivision,
T. 19 S., R. 9 E., Salt Lake Meridian, Utah

CHAINS	
33.00	Wash, drains NE.
39.90	Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 20, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, encircled by a collar of stone, with brass cap mkd.
	$\begin{array}{r} T\ 19\ S\ R\ 9\ E \\ \quad \quad \quad S\ 19 \\ \frac{1}{4} \quad \quad \quad \hline \quad \quad \quad S\ 30 \\ \quad \quad \quad 1975 \end{array}$
54.00	Wash, drains N.
79.60	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., projecting 6 ins. above the ground, with brass cap mkd.
	$\begin{array}{r} T\ 19\ S \\ R\ 8\ E\ R\ 9\ E \\ \quad \quad \quad S\ 24\ \quad S\ 19 \\ \quad \quad \quad S\ 25\ \quad S\ 30 \\ \quad \quad \quad 1975 \end{array}$
	<p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. $0^{\circ}03'$ E., bet. secs. 19 and 20.</p> <p>Over rolling desert land, through shadscale undergrowth.</p>
7.30	Draw, drains SE.
11.80	Draw, drains SE.
14.00	Ridge, bears NE and SW.
31.70	Wash, drains NW.
40.16	The $\frac{1}{4}$ sec. cor. of secs. 19 and 20, monumented with a weathered sandstone, 18 x 10 x 4 ins., firmly set in a mound of stone, with no legible mks. This position is harmoniously related to existing original cors. and is accepted as the best available evidence of the original cor.
	At the corner point
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to bedrock, encircled by a mound of stone, 5 ft. base to top, with brass cap mkd.
	$\begin{array}{r} T\ 19\ S\ R\ 9\ E \\ \quad \quad \quad \frac{1}{4} \\ \quad \quad \quad \\ \quad \quad \quad S\ 19\ \quad S\ 20 \\ \quad \quad \quad \\ \quad \quad \quad 1975 \end{array}$
	Deposit the unmkd. stone alongside the iron post.
	<hr style="width: 20%; margin: auto;"/> <p>N. $0^{\circ}02'$ W., beginning new measurement.</p>

Dependent Resurvey of a portion of the Subdivision,
T. 19 S., R. 9 E., Salt Lake Meridian, Utah

CHAINS	
	Over gently rolling desert land.
12.80	Wash, drains N. 38° E.
20.20	Same wash, drains N. 66° W.
22.40	Same wash, drains N. 28° E.
30.90	Same wash, drains N. 37° W.
40.51	The cor. of secs. 17, 18, 19 and 20, monumented with a sandstone, 16 x 10 x 4 ins., projecting 8 ins. above ground and mkd. with 3 notches on the S and 5 notches on the E edges.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 19 S R 9 E S 18 S 17 S 19 S 20 1975
	Deposit the mkd. stone alongside the iron post.
	Raise a mound of stone, 4 ft. base, 2 ft. high, W of cor.
	From the cor. of secs. 16, 17, 20 and 21.
	S. 89°50' W., bet. secs. 17 and 20.
	Over broken benches, sandstone ledges and creek bottom; desc. 90 ft. over broken W slope.
9.60	Enter Cottonwood Creek bottoms.
19.70	Cottonwood Creek, 60 lks. wide, 14 ins. deep, course S. 77° E.
27.30	Cottonwood Creek, course N. 3° E.
36.40	Cottonwood Creek, course S. 39° E.
38.80	Leave Cottonwood Creek bottoms; asc. 160 ft. over broken NE slope.
40.18	Point for the ¼ sec. cor. of secs. 17 and 20, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, encircled by a collar of stone, with brass cap mkd.
	T 19 S R 9 E ¼ S 17 S 20 1975
45.70	Top of ascent, bears N and S; thence over nearly level land.
54.50	Gulch, drains N.

Dependent Resurvey of a portion of the Subdivision,
T. 19 S., R. 9 E., Salt Lake Meridian, Utah

CHAINS	
60.10	Deep draw, drains N.
80.36	The cor. of secs. 17, 18, 19 and 20.
	S. 89°39' W., bet. secs. 18 and 19. Over rolling desert land.
16.50	Wash, drains N. 7° E.
40.29	Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19, at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 19 S R 9 E S 18 $\frac{1}{4}$ ——— S 19 1975 </div>
	Place steel fence post alongside iron post.
47.00	Wash, drains N. 17° W.
68.50	Gulch, drains NE.
80.40	Wash, drains N.
80.58	The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., projecting 6 ins. above ground, encircled by a collar of stone, with brass cap mkd. <div style="text-align: center;"> T 19 S R 8 E R 9 E S 13 S 18 S 24 S 19 1975 </div>
	From the cor. of secs. 17, 18, 19 and 20. N. 0°04' W., bet. secs. 17 and 18. Over rolling benches, through short shadscale.
17.10	Top of bench; desc. gradually over NE slope.
28.90	Wash, drains S. 56° E.; asc. 60 ft. over SW slope.
40.12	Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 18, at proportionate dist.; found original sandstone, 18 x 10 x 8 ins., plainly mkd. $\frac{1}{4}$ lying loose at bottom of small draw, drains S. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, encircled by a collar of stone, with brass cap mkd. <div style="text-align: center;"> T 19 S R 9 E $\frac{1}{4}$ S 18 S 17 1975 </div>

Dependent Resurvey of a portion of the Subdivision,
T. 19 S., R. 9 E., Salt Lake Meridian, Utah

CHAINS	
	<p>Deposit the mkd. stone alongside the iron post, Place steel fence post alongside iron post. Asc. 30 ft. to top of bench.</p>
45.60	Unimproved road, 16 lks. wide, bears N. 66° W. to Castle Dale, and S. 66° E.
48.40	Head of draw, drains NE; desc. 60 ft. over NE slope.
53.80	Hollow, drains NE.
69.70	Enter Cottonwood Creek bottom.
80.24	<p>Point for the cor. of secs. 7, 8, 17 and 18, at proportionate dist., falls in cultivated area where it is impracticable to establish a permanent monument; there is no remaining evidence of the original cor.</p> <p>Point selected for the witness cor. to secs. 7, 8, 17 and 18, bears N. 0°04' E., 0.60 chs. dist., hereinafter described.</p>
	<p>From the cor. of secs. 8, 9, 16 and 17. S. 89°47' W., bet. secs. 8 and 17. Over rolling desert land, with some meadow in W portion.</p>
8.10	Gulch, drains NE; desc. gradually.
40.24	<p>Point for the ¼ sec. cor. of secs. 8 and 17, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 19 S R 9 E</p> <p>¼ <u> S 8 </u></p> <p> S 17</p> <p> 1975</p> </div>
	Place steel fence post alongside iron post.
54.10	Enter Cottonwood Creek bottoms.
58.60	Cottonwood Creek, 50 lks. wide, 14 ins. deep, course S. 31° E.
61.10	Cottonwood Creek, course N. 24° E.
65.50	Cottonwood Creek, course S. 43° E.
80.48	True point for cor. of secs. 7, 8, 17 and 18.
	<p>S. 89°41' W., bet. secs. 7 and 18. Asc. gradually over broken benches with some meadow land in the E portion.</p>
7.20	Leave Cottonwood Creek bottoms.
22.40	Draw, drains NE.

Dependent Resurvey of a portion of the Subdivision,
T. 19 S., R. 9 E., Salt Lake Meridian, Utah

CHAINS
40.18

The ¼ sec. cor. of secs. 7 and 18, monumented with a sandstone, 12 x 8 x 6 ins., projecting 6 ins. above ground, and mkd. ¼ on the N face.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

T 19 S R 9 E
S 7
¼ S 18
1975

Deposit the mkd. stone alongside the iron post.

Place steel fence post alongside the iron post.

N. 86°07' W., beginning new measurement.

Over broken benches and rolling desert land.

3.50 Secondary road, 25 lks. wide, bears N. 13° E. to Castle Dale, and S. 13° W.; asc. 80 ft. over broken SE slope.

10.60 Point of spur, projects S; desc. SW slope.

11.80 Enter large hollow, drains S.

19.30 Leave hollow; asc. 80 ft. abruptly over broken SE slope.

22.80 Top of ascent, bears NE and SW; thence over nearly level bench.

27.50 Gulch, drains S.

41.39 The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., projecting 6 ins. above the ground, encircled by a collar of stone, with brass cap mkd.

T 19 S
R 8 E R 9 E
S 12 | S 7
S 13 | S 18
1975

From the true point for the cor. of secs. 7, 8, 17 and 18.

N. 0°04' E., bet. secs. 7 and 8.

Over grassy meadow land and creek bottom.

0.60 Point for the witness cor. of secs. 7, 8, 17 and 18.

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

W C
T 19 S R 9 E
S 7 | S 8
S 18 ↓ S 17
1975

Place steel fence post alongside iron post.

Dependent Resurvey of a portion of the Subdivision,
T. 19 S., R. 9 E., Salt Lake Meridian, Utah

CHAINS	
	Cor. is located at edge of cultivated area, in grassy meadow.
35.80	Cottonwood Creek, 60 lks. wide, 10 ins. deep, course S. 18° E.
39.42	Point for the witness $\frac{1}{4}$ sec. cor. of secs. 7 and 8. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> W C T 19 S R 9 E ¼ ↑ S 7 S 8 1975 </div>
	Place steel fence post alongside the iron post.
	Cor. is located 15 lks. E of Cottonwood Creek.
40.12	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8, at proportionate dist., falls in the middle of Cottonwood Creek, 60 lks. wide, course S. 23° W. where it is impracticable to establish a permanent monument; there is no remaining evidence of the original cor.
45.10	Cottonwood Creek, course S. 37° E.
47.50	Leave Cottonwood Creek bottoms; asc. 80 ft. gradually over SW slope.
80.24	Point for the cor. of secs. 5, 6, 7 and 8, at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> T 19 S R 9 E S 6 S 5 S 7 S 8 1975 </div>
	Place steel fence post alongside the iron post.
	From the cor. of secs. 4, 5, 8 and 9. S. 89°42' W., bet. secs. 5 and 8. Over broken benches and rolling desert land.
23.30	Wash, drains NE.
40.08	Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 8, at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> T 19 S R 9 E ¼ $\frac{S 5}{S 8}$ 1975 </div>

Dependent Resurvey of a portion of the Subdivision,
T. 19 S., R. 9 E., Salt Lake Meridian, Utah

CHAINS	
	Place steel fence post alongside iron post.
57.70	Small ridge, bears NE and SW.
62.10	Gulch, drains SE.
67.40	Wash, drains S. 41° E.
80.16	The cor. of secs. 5, 6, 7 and 8.
S. 89°32' W., bet. secs. 6 and 7.	
	Over broken benches and sandstone formations.
2.60	Asc. 100 ft. abruptly over broken E slope.
4.80	Top of bluff, bears N. 25° E. and S. 25° W.
5.20	Desc. 100 ft. abruptly over broken SW slope.
9.30	E edge of large hollow, drains S.
16.20	W edge of large hollow; asc. 80 ft. over broken SE slope.
21.50	Spur, projects S; desc. 80 ft. over broken SW slope.
32.20	Base of W side of bluff.
39.47	Point for the witness $\frac{1}{4}$ sec. cor. of secs. 6 and 7.
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>W C T 19 S R 9 E $\frac{1}{4}$ ← $\frac{S 6}{S 7}$ 1975</p>
	Raise a mound of stone, 4 ft. base, 2 ft. high, N of cor.
39.72	Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7, at proportionate dist., falls on edge of wash where it is impracticable to establish a permanent monument; there is no remaining evidence of the original cor.
48.30	Large wash, drains S; asc. 40 ft. over SE slope.
59.20	Spur, projects SW; desc. 40 ft. over broken SW slope.
62.30	Enter Cottonwood Creek bottoms with scattering timber of cottonwood trees.
64.40	Cottonwood Creek, 60 lks. wide, 12 ins. deep, course S. 51° E.
68.30	Leave Cottonwood Creek bottoms; asc. 80 ft. abruptly over broken E slope.
72.00	Point of spur, projects S; desc. SW slope.
76.10	Draw, drains SE; asc. 40 ft. over SE slope.
79.54	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented with an iron post, 2 $\frac{1}{2}$ ins. diam., in a mound of stone, 3 ft. base to top of brass cap mkd.

Dependent Resurvey of a portion of the Subdivision,
T. 19 S., R. 9 E., Salt Lake Meridian, Utah

CHAINS

T 19 S
R 8 E R 9 E
S 1 | S 6
S 12 | S 7
1975

From the cor. of secs. 5, 6, 7 and 8.

N. 1°28' W., bet. secs. 5 and 6.

Over broken benches and sandstone formations.

- 8.30 Asc. 80 ft. along steep E slope.
- 10.70 Top of ascent, slopes E; thence along steep, rough E slope.
- 17.20 Desc. 60 ft. over steep rough NE slope.
- 19.40 S edge of hollow, drains E.
- 24.30 N edge of hollow; asc. 80 ft. over broken SE slope.
- 28.10 Top of ascent, slopes E; thence along steep rough E slope.
- 38.90 Desc. 60 ft. over steep, rough NE slope.
- 40.12 Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6, at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 19 S R 9 E
 $\frac{1}{4}$
S 6 | S 5
1975

Place steel fence post alongside iron post.

Cor. is located 50 lks SW of small wash draining SE.

- 44.20 Wash, drains S. 66° E.; asc. 180 ft. abruptly over broken SE slope.
- 49.60 Top of ascent, bears E and W; thence over nearly level bench.
- 64.80 Draw, drains SW; asc. 50 ft. over SW slope.
- 75.90 Desc. 60 ft. over rough NW slope.
- 79.00 Wash, drains S. 51° W.; asc. 30 ft. over SE slope.
- 80.39 The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set in a mound of stone, 3 ft. base to top of brass cap mkd.

T 18 S R 9 E
S 31 | S 32
S 6 | S 5
T 19 S R 9 E
1970

Dependent Resurvey of a portion of the Subdivision,
T 19 S., R. 9 E., Salt Lake Meridian, Utah

CHAINS

General Description

The NW cor. of Township 19 South, Range 9 East, is located about two miles E of the town of Castle Dale. Secs. 4, 9 and 16, are drained by Huntington Creek. Secs. 18 and 19 are drained by Rock Canyon Creek. Secs. 6, 7, 8, 17 and 20 are drained by Cottonwood Creek. Secs. 31, 29 and 28 are drained by Ferron Creek. These creeks all join in sec. 21, and form the San Rafael River, which flows SE through the Tp. The land encountered in this survey, generally drains to the SE. The elevation varies from 5,724 ft. above sea level in the SW $\frac{1}{4}$ of sec. 4, to 5,340 ft. above sea level in the SE $\frac{1}{4}$ of sec. 21.

Access for the N portion of the Tp. is by way of an improved dirt road from Utah State Highway No. 10. Access for the W portion of the Tp. is by way of Wilsonville unimproved road, which also interchange with Highway No. 10. Access for the S portion of Tp. is by way of Jeep Trail that interchanges with the Horn Silver Gulch unimproved road from Ferron.

The predominate timber is cottonwood trees scattered throughout the creek bottoms, where there is also some willows. The undergrowth consists mostly of shadscale with some native grasses.

The principal use of the area is livestock grazing and recreation for hunters.

The only improvements noted were a ranch occupancy in section 7, and a Gaging Station in section 21.

The mean of a considerable number of observations of the magnetic declination throughout the Tp. is $14^{\circ}45'$ E.

CERTIFICATE OF SURVEY


(I) ~~(XX)~~ Glen B. Hatch, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 6th day of May, 1975, (I) ~~(XX)~~ have dependently resurveyed a portion of the south boundary and a portion of the subdivisional lines of Township 19 South, Range 9 East

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), ~~(XX)~~ and under (my) ~~(XX)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

November 17, 1976

(Date)



(Cadastral Surveyor)

Supervisory

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Washington, D.C.
Denver, Colorado

The foregoing field notes of the dependant resurvey of a portion of the south boundary and a portion of the subdivisional lines of Township 19 South, Range 9 East, Salt Lake Meridian, Utah

executed by Glen B. Hatch, Supervisory Cadastral Surveyor having been critically examined and found correct, are hereby approved.

DEC 04 1979

(Date)



(Chief, Division of Cadastral Survey)

Chief, Cadastral Survey Examination and Approval Staff

CERTIFICATE OF TRANSCRIPT

~~I Certify That the foregoing transcript of the field notes of the above described surveys in~~
~~is a true copy of the original field notes.~~

(Date)

(Chief, Division of Cadastral Survey)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
ORIGINAL

R599

204

-7-

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF

SECOND STANDARD PARALLEL SOUTH,

ON THE SOUTH BOUNDARY OF T. 10 S., R. 24 E.,

THE EAST, WEST AND NORTH BOUNDARIES

AND

SUBDIVISIONAL LINES

OF

TOWNSHIP 10 SOUTH, RANGE 24 EAST

Of the Salt Lake Meridian,

In the State of Utah

EXECUTED BY

Jerry L. Thomas Supervisory Cadastral Surveyor

Under special instructions dated January 30, 19 75, approved January 30, 1975,

_____ , which provided for the surveys included under ~~XXXXXX~~ Group

Number 557 , and assignment instructions dated April 30 , 1975 .

Survey commenced May 6 , 19 75

Survey completed August 19 , 19 75

INDEX DIAGRAM

Township 10 S., Range 24 E.

29	28	27	26	25	23
22 6	90 5	74 4	63 3	52 2	40 1 15
90	89	73	62	51	40
21 7	88 8	73 9	61 10	50 11	38 12 14
87	86	72	61	59	37
20 18	85 17	71 16	60 15	48 14	36 13 13
84	83	70	58	47	36
19 19	82 20	69 21	57 22	46 23	34 24 12
81	80	68	56	45	33
17 30	79 29	67 28	55 27	44 26	32 25 11
78	77	66	54	43	31
16 31	75 32	64 33	53 34	42 35	30 36 9
8	7	5	4	3	1

Township 10 South, Range 24 East, Salt Lake Meridian, Utah

CHAINS

The following field notes are those of the dependent resurvey of the south boundary (Second Standard Parallel South), the east, west and north boundaries, the subdivisional lines and the retracement of the boundaries between private and federal lands of a tract and a mining claim in T. 10 S., R. 24 E., Salt Lake Meridian, Utah

The north boundary of section 6 was surveyed by D. G. Major in 1883. The south boundary (Second Standard Parallel South), the east, west and north boundaries, the subdivisional lines and Atlanta Lode M.S. No. 5275 were surveyed by A. R. Talamantes and H. D. Heist in 1904. Allotment No. 266, No. 19 War-Atze was surveyed by A. R. Talamantes and H. D. Heist in 1905.

The resurvey was executed in accordance with the specifications as set forth in the Manual of Survey Instructions, 1973, and the Special Instructions for Group No. 557, Utah, dated January 30, 1975.

The direction of the lines of this survey was determined by altitude observations on the sun. The lines were carried forward by sustained angulation being supplemented by other altitude observations on the sun taken throughout the progress of the survey. The vertical angles of measurements made on the slope were ascertained by a clinometer in good adjustment; the horizontal equivalents only are entered in the field notes.

Before restoring the corners, the lines of the original surveys were retraced and a diligent search made for any evidence of the original corners, bearing trees and other calls of the field note record. When duly identified, the corner positions were remonumented and new bearing objects marked.

The geographic position of the southeast corner of the township as determined from a tie made to U.S.C. & G.S. "G.L.O. Station No. 5", 1931 which is the Stan. Cor. of Secs. 33 and 34, T. 10 S., R. 25 E., resurveyed concurrently under this same group, is:

Latitude 39°53'54" N. Longitude 109°09'09" W.

The mean magnetic declination is 14°30' E.

Dependent Resurvey of the Second Standard Parallel South,
on the South Boundary of T. 10 S., R. 24 E.,
Salt Lake Meridian, Utah

(Restoring the survey executed by
A. R. Talamantes and H. D. Heist in 1904)

Beginning at the stan. cor. of Tps. 10 S., Rs. 24 and 25 E., monumented with a sandstone, 24 x 13 x 8 ins., firmly set 12 ins. in the ground, mkd. SC on N face and 6 notches on E, W and N edge.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4½ ft. base, to top of brass cap mkd.

Dependent Resurvey, Second Standard Parallel South,
S. Bdy., T. 10 S., R. 24 E., Salt Lake Mer., Utah

CHAINS		
	SC T 10 S R 24 E R 25 E <u>S 36 S 31</u> 1975	
	Deposit the mkd. stone alongside the iron post.	
	N. 89°55' W., on the S. bdy. of sec. 36.	
	Asc. over E slope through scattered sagebrush and shad-scale.	
4.00	Top of spur, slopes N; desc. over NW slope.	
5.50	Bottom of small draw, drains NW; thence along N slope.	
12.00	Bottom of draw, drains N.	
20.00	Slope changes; desc. over NW slope.	
25.00	Dirt road, bears N and S.	
25.90	Evacuation Creek, drains N; asc. over gradual NE slope.	
35.00	Spur, slopes N; desc. over NW slope.	
40.01	Point for the stan. $\frac{1}{4}$ sec. cor. of sec. 36, at proportionate distance; there is no remaining evidence of the original corner.	
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.	
	SC T 10S R 24 E <u>$\frac{1}{4}$ S 36</u> 1975	
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of corner.	
	Corner is located on E bank of Evacuation Creek.	
40.50	Evacuation Creek, drains SW; asc. over SE slope.	
43.50	Top of ascent, bears NE and SW; over nearly level land.	
49.00	Begin descent over W slope.	
52.90	Evacuation Creek, drains NE; asc. over NE slope.	
63.00	Top of spur, slopes N; desc. over NW slope.	
65.50	Bottom of draw, drains N; asc. over NE slope.	
67.00	Top of narrow ridge, bears N and S; desc. over steep W slope.	
70.50	Wash, 20 lks. wide, 12 ins. deep, in bottom of canyon, drains NW; asc. over NE slope.	
78.80	Rim of canyon, bears NW and SE; thence along gentle N slope.	

Dependent Resurvey, Second Standard Parallel South,
S. Bdy., T. 10 S., R. 24 E., Salt Lake Mer., Utah

CHAINS
80.02

The stan. cor. of secs. 35 and 36, monumented with a sandstone, 20 x 11 x 5 ins., firmly set 10 ins. in the ground, mkd. SC on N face, 1 notch on E and 5 notches on W edge.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base to top, with brass cap mkd.

SC
T 10 S R 24 E
|
S 35 | S 36

1975

Deposit the mkd. stone alongside the iron post.

S. 89°59' W., on the S. bdy. of sec. 35.

Along rocky N slope through scattered shadscale and sagebrush.

- 4.00 Slope changes; desc. over NW slope.
7.50 Bottom of draw, drains N; thence along N slope.
13.50 Begin ascent over SE slope.
16.00 Top of narrow spur, projects NE; desc. over NW slope.
21.50 Bottom of draw, drains NE from W; asc. along bottom of draw, draining E.
39.50 Top of small spur, slopes N; begin descent over W slope.
39.65 The stan. ¼ sec. cor. of sec. 35, monumented with a sandstone, 28 x 11 x 3 ins., firmly set 12 ins. in the ground, mkd. SC ¼ on N face, from which the original bearing trees

A scrub cedar, 6 ins. diam., bears N. 79° W.,
12 lks. dist., mkd. SC ¼ S BT. (Record, 14 lks.)

A cedar, 8 ins. diam., bears N. 86° E., 36 lks.
dist., mkd. SC ¼ S BT. (Record, 32 lks.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.

SC
T 10 S R 24 E
|
¼ S 35

1975

Deposit the mkd. stone alongside the iron post.

West, beginning new measurement.

Dependent Resurvey, Second Standard Parallel South,
S. Bdy., T. 10 S., R. 24 E., Salt Lake Mer., Utah

CHAINS	
	Desc. over W slope.
3.00	Bottom of draw, drains N; asc. over E slope.
9.50	Top of spur, slopes NE; desc. over NW slope.
13.00	Bottom of draw, drains N; asc. over steep E slope.
31.30	Top of ridge, bears NW and SE; enter scattered cedar timber.
34.50	Begin descent over W slope.
39.25	Head of hollow, course SE; asc. over rocky SE slope.
40.44	The stan. cor. of secs. 34 and 35, monumented with a sandstone, 20 x 12 x 5 ins., firmly set 12 ins. in the ground, mkd. SC on N face, 4 notches on the W and 2 notches on the E edge, from which the original bearing trees
	A cedar, 4 ins. diam., bears N. 73° E., 50 lks dist., mkd. T10S R24E S35 BT.
	A cedar, 5 ins. diam., bears N. 23° W., 51 lks. dist., mkd. T10S R24E S34 BT.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	SC T 10 S R 24 E S 34 S 35 1975
	Deposit the mkd. stone alongside the iron post.
	S. 89°59' W., on the S. bdy. of sec. 34.
	Asc. over rocky SE slope through scattered juniper and cedar timber.
2.70	Top of spur, slopes S; thence along broken S slope.
11.00	Slope changes; desc. over W slope.
13.00	Small wash in bottom of draw, drains NW; thence along gentle N slope.
19.00	Same wash, drains SW; asc. over rocky SE slope.
23.50	Spur, slopes S; desc. along gentle S slope.
27.00	Slope changes; desc. over W slope.
31.50	Small wash at base of descent, drains NW; asc. over gentle NE slope.
40.22	The stan. ¼ sec. cor. of sec. 34, monumented with a sandstone, 18 x 15 x 5 ins., firmly set 10 ins. in the ground, mkd. SC ¼ on N face, from which the remains of the original bearing trees

Dependent Resurvey, Second Standard Parallel South,
S. Bdy., T. 10 S., R. 24 E., Salt Lake Mer., Utah

CHAINS

A cedar stump, 5 ins. diam., bears N. 30° E., 39
lks. dist., mkd. SC $\frac{1}{4}$ S BT. (Record, 38 lks.)

A cedar, 6 ins. diam., bears N. 59° W., 22 lks.
dist., mkd. SC $\frac{1}{4}$ S BT.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 4 ins.
in the ground to bedrock, in a mound of stone, 4½ ft.
base to top, with brass cap mkd.

SC
T 10 S R 24 E

$\frac{1}{4}$ S 34

1975

Deposit the mkd. stone alongside the iron post.

N. 89°59' W., beginning new measurement.

Asc. over gentle SE slope through scattered juniper and
pinon.

9.00 Top of spur, projects N; desc. over NW slope.

30.00 Small wash in bottom of hollow, drains N; asc. over NE
slope.

39.96 The stan. cor. of secs. 33 and 34, monumented with a
sandstone, 20 x 15 x 5 ins., firmly set 10 ins. in the
ground, mkd. SC on N face and 3 notches on the E and W
edge, from which the remains of the original bearing trees

A cedar, 10 ins. diam., bears N. 43° E., 61 lks.
dist., with a healed blaze. (Record, 59 lks.)

There is no remaining evidence of the other bearing
tree.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins.
in the ground to bedrock, in a mound of stone, 4½ ft.
base to top, with brass cap mkd.

SC
T 10 S R 24 E

S 33 | S 34

1975

Deposit the mkd. stone alongside the iron post.

N. 89°58' W., on the S. bdy. of sec. 33.

Asc. over NE slope through scattered juniper and cedar
timber, sagebrush and native grasses.

5.00 Top of spur, slopes N; desc. over NW slope.

16.75 Small wash, drains NE; asc. over steep slope.

211

Dependent Resurvey, Second Standard Parallel South,
S. Bdy., T. 10 S., R. 24 E., Salt Lake Mer., Utah

CHAINS	
28.00	Top of ridge, bears N and S; desc. over broken NW slope.
35.00	Bottom of hollow, drains N; asc. over NE slope.
39.83	<p>The stan. $\frac{1}{4}$ sec. cor. of sec. 33, monumented with a sandstone, 36 x 15 x 10 ins., firmly set 15 ins. in the ground, mkd. SC $\frac{1}{4}$ on N face, from which the remains of the original bearing trees</p> <p>A stump hole, bears N. 47° E., 45 lks. dist., a pinon, dead and lying alongside, 15 ins. diam., with scribe marks $\frac{1}{4}$ S33 BT visible on opened blaze. (Record, cedar.)</p> <p>A dead pinon, 6 ins. diam., bears N. 32° W., 54 lks. dist., mkd. $\frac{1}{4}$ SC BT. (Record, cedar 55 lks.)</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">SC T 10 S R 24 E <u> </u> <u> </u> $\frac{1}{4}$ S 33 <u> </u> 1975</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p style="text-align: center;">—————</p> <p>N. 89°59' W., beginning new measurement.</p> <p>Asc. over steep NE slope through thick scrub juniper and pinon timber.</p>
5.00	Top of spur, slopes NE; desc. over NW slope.
8.00	Bottom of draw, drains N; asc. over NE slope.
11.50	Top of ridge, bears NW and SE; desc. over SW slope.
21.00	Bottom of draw, drains SW; asc. over SE slope.
24.50	Top of spur, projects SW; desc. over NW slope.
32.00	Small wash in bottom of draw, drains N; asc. over E slope.
34.00	Top of spur, slopes NE; desc. over NW slope.
39.84	<p>The stan. cor. of secs. 32 and 33, monumented with a sandstone, 36 x 14 x 6 ins., firmly set 14 ins. in the ground, mkd. SC on N face, 4 notches on E and 2 notches on W edge, from which the original bearing trees</p> <p>A cedar, 12 ins. diam., bears N. 63° E., 58 lks. dist., mkd. SC S32 BT T10S R24E. (Record, S33 57 lks.)</p> <p>A cedar, 30 ins. diam., bears N. 18½° W., 9 lks. dist., mkd. SC S33 BT T10S R24E. (Record, S32.)</p> <p>At the corner point</p>

Dependent Resurvey, Second Standard Parallel South,
S. Bdy., T. 10 S., R. 24 E., Salt Lake Mer., Utah

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

SC
T 10 S R 24 E
|
S 32 | S 33

1975

Deposit the mkd. stone alongside the iron post.

N. 89°59' W., on the S. bdy. of sec. 32.

Along gentle N slope through scattered juniper and pinon, sagebrush and native grasses.

- 2.00 Small wash, drains N; asc. over NE slope.
- 8.50 Top of spur, slopes N; desc. over NW slope.
- 11.00 Slope changes; along N slope.
- 17.00 Slope changes; asc. over NE slope.
- 20.00 Top of spur, projects NE; desc. over NW slope.
- 25.50 Top of spur, slopes NW; desc. over W slope.
- 31.00 Saddle on small ridge, bears NW and SE; desc. along bottom of draw, draining W.
- 39.90 Wash, 20 lks. wide, 12 ins. deep, drains N; asc. over gentle E slope.
- 40.13 The stan. ¼ sec. cor. of sec. 32, determined from the remains of the original bearing trees

A cedar, 6 ins. diam., bears N. 36° E., 60 lks. dist., mkd. SC ¼ S BT.

A cedar, 6 ins. diam., bears N. 36° W., 6 lks. dist., mkd. SC ¼ S BT.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

SC
T 10 S R 24 E

¼ S 32

1975

Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.

N. 89°50' W., beginning new measurement.

Asc. over E slope through scattered juniper and pinon.

213

Dependent Resurvey, Second Standard Parallel South,
S. Bdy., T. 10 S., R. 24 E., Salt Lake Mer., Utah

CHAINS	
3.50	Spur, slopes N; desc. over NW slope.
6.50	Bottom of draw, drains N; asc. over NE slope.
9.50	Top of spur, slopes N; desc. over NW slope.
14.00	Slope changes; desc. over W slope.
25.00	Small wash in bottom of hollow, drains N; asc. over NE slope.
37.50	Top of spur, projects NW; desc. over rocky W slope.
39.49	<p>The stan. cor. of secs. 31 and 32, monumented with a sandstone, 26 x 12 x 8 ins., firmly set 8 ins. in the ground, and in a mound of stone. This corner was erroneously mkd. SC $\frac{1}{4}$ on the N face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 5 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>SC</p> <p>T 10 S R 24 E</p> <p> </p> <p>S 31 S 32</p> </div> <p>1975</p> <p>Deposit the mkd. stone alongside the iron post.</p>
	West, on the S. bdy. of sec. 31.
	Desc. over rocky W slope through native grasses and scattered sagebrush and shadscale.
3.50	Bottom of draw, drains NW; asc. over NE slope.
8.50	Top of spur, slopes N; desc. over W slope through scattered juniper and pinon.
19.20	Base of descent, bears NE and SW; along gentle N slope on S edge of hollow.
26.20	Base of ascent, bears NE and SW; asc. over NE slope.
27.70	Top of spur, slopes S; desc. over NW slope.
29.20	Bottom of draw, drains N; asc. over E slope.
32.70	Top of spur, projects N; desc. over W slope.
35.70	Bottom of draw, drains N; asc. over E slope.
38.50	Top of spur, projects N; desc. over W slope.
40.17	<p>The stan. $\frac{1}{4}$ sec. cor. of sec. 31, monumented with a sandstone, 24 x 16 x 6 ins., loosely set in a mound of stone, dimly mkd. SC $\frac{1}{4}$ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4$\frac{1}{2}$ ft. base to top, with brass cap mkd.</p>

Dependent Resurvey, Second Standard Parallel South,
S. Bdy., T. 10 S., R. 24 E., Salt Lake Mer., Utah

CHAINS

SC
T 10 S R 24 E

¼ S 31

1975

Deposit the mkd. stone alongside the iron post.

West, beginning new measurement.

Desc. over NW slope.

- 2.50 Bottom of draw, drains N; asc. over NE slope.
- 5.00 Top of spur, slopes N; desc. over W slope.
- 7.00 Bottom of draw, drains NW; asc. over NE slope.
- 9.00 Top of small spur, slopes N; desc. along N slope.
- 11.00 Bottom of descent slopes N; asc. over NE slope.
- 13.50 Top of ridge, bears NW and SE; desc. over SW slope.
- 22.00 Bottom of descent, slopes S; asc. over SE slope.
- 26.00 Top of spur, slopes S; desc. over steep SW slope.
- 30.50 Wash in bottom of hollow, drains NW; asc. over NE slope.
- 37.00 Top of spur, slopes NW; desc. over W slope.
- 38.50 Bottom of draw, drains N; asc. over NE slope.
- 39.54 The stan. cor. of Tps. 10 S., Rs. 23 and 24 E., monumented with a sandstone, 36 x 16 x 4 ins., set in a mound of stone on solid sandstone, mkd. SC on N face, 6 notches on E, W and N edge.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., over a (X) cross chiseled in solid sandstone, in a mound of stone, 4½ ft. base to top, with brass cap mkd.

SC
T 10 S
R 23 E R 24 E

S 36 | S 31

1975

Deposit the mkd. stone alongside the iron post.

Dependent Resurvey of the E. Bdy. of T. 10 S., R. 24 E.,
Salt Lake Meridian, Utah

(Restoring the survey executed by A. R. Talamantes
and H. D. Heist in 1904)

Dependent Resurvey of the E. Bdy. of T. 10 S., R. 24 E.,
Salt Lake Meridian, Utah

CHAINS	
	From the stan. cor. of Tps. 10 S., Rs. 24 and 25 E., heretofore described.
	N. 0°01' W., bet. secs. 31 and 36.
	Desc. over NE slope through native grasses, shadscale and sagebrush.
5.00	Slope changes; desc. over N slope.
11.25	Dirt road, bears E and W.
13.00	Small wash, drains NW.
13.20	Dirt road, bears NE and SW.
14.75	Small wash, drains W; asc. over S slope.
23.00	Top of spur, slopes SW; desc. over NW slope.
34.00	Wash, 20 lks. wide, 12 ins. deep, drains SW; asc. along E slope.
40.02	The $\frac{1}{4}$ sec. cor. of secs. 31 and 36, monumented with a sandstone, 24 x 16 x 4 ins., firmly set 12 ins. in the ground, mkd. $\frac{1}{4}$ on W face and a scattered mound of stone to W.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<pre> T 10 S R 24 E R 25 E ¼ S 36 S 31 1975 </pre>
	Deposit the mkd. stone alongside the iron post.
	<hr style="width: 20%; margin: 0 auto;"/>
	N. 0°10' E., beginning new measurement.
	Asc. along E slope.
6.00	Small draw, drains SE; asc. over SW slope.
18.00	Same draw, drains SW; asc. over SE slope.
24.00	Top of spur, slopes E; desc. over NE slope.
28.00	Slope changes; desc. along E slope.
40.48	The cor. of secs. 25, 30, 31 and 36, monumented with a sandstone, 30 x 14 x 12 ins., firmly set 14 ins. in the ground, mkd. 1 notch on S and 5 notches on N edge and a scattered mound of stone to W.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base to top, with brass cap mkd.

Dependent Resurvey of the E. Bdy. of T. 10 S., R. 24 E.,
Salt Lake Meridian, Utah

CHAINS	
	<p style="text-align: center;">T 10 S R 24 E R 25 E S 25 S 30 S 36 S 31 1975</p> <p>Deposit the mkd. stone alongside the iron post.</p>
	<p>N. 0°09' W., bet. secs. 25 and 30.</p> <p>Desc. along gentle E slope through native grasses, sagebrush and shadscale.</p>
11.00	Head of draw, drains N. 30° E.
28.00	Spur, slopes NE; desc. over E slope.
38.00	Spur, slopes N. 80° E.; desc. over NE slope.
39.97	The ¼ sec. cor. of secs. 25 and 30, monumented with a sandstone, 18 x 14 x 8 ins., firmly set 10 ins. in the ground, mkd. ¼ on W face with small mound of stone to W.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.
	<p style="text-align: center;">T 10 S R 24 E R 25 E ¼ S 25 S 30 1975</p> <p>Deposit the mkd. stone alongside the iron post.</p>
	<p>N. 0°05' W., beginning new measurement.</p> <p>Desc. over NE slope.</p>
6.75	Wash, 30 lks. wide, 2 ft. deep, drains NW; along gentle W slope.
13.00	Wash, 20 lks. wide, 12 ins. deep, drains SW; asc. over SE slope.
22.00	Top of spur, slopes SE; desc. along E slope.
30.00	Slope changes; asc. over steep S slope.
33.50	Top of sandstone butte, bears SW and NE; desc. over N slope.
40.14	Point for the cor. of secs. 19, 24, 25 and 30, at proportionate distance; there is no remaining evidence of the original corner.

Dependent Resurvey of the E. Bdy. of T. 10 S., R. 24 E.,
Salt Lake Meridian, Utah

CHAINS					
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 10 S R 24 E R 25 E</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S 24</td> <td style="padding: 2px 5px;">S 19</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S 25</td> <td style="padding: 2px 5px;">S 30</td> </tr> </table> <p>1975</p> </div>	S 24	S 19	S 25	S 30
S 24	S 19				
S 25	S 30				
	<p>N. 0°05' W., bet. secs. 19 and 24.</p> <p>Desc. over N slope through native grasses, shadscale, and sagebrush.</p> <p>12.00 Bottom of draw, drains NW; asc. along W slope.</p> <p>17.00 Top of spur, slopes NW; desc. over N slope.</p> <p>22.00 Bottom of draw, drains NW; asc. over SW slope.</p> <p>31.00 Top of ridge, bears NW and SE; desc. over NW slope.</p> <p>40.14 The ¼ sec. cor. of secs. 19 and 24, monumented with a sandstone, 14 x 8 x 4 ins., firmly set 8 ins. in the ground, mkd. ¼ on W face, with small mound of stone to W.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 10 S R 24 E R 25 E</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S 24</td> <td style="padding: 2px 5px;">S 19</td> </tr> </table> <p>¼</p> <p>1975</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of corner.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°02' E., beginning new measurement.</p> <p>Desc. over NW slope.</p> <p>9.00 Small wash in bottom of draw, drains W; asc. over SW slope.</p> <p>17.00 Top of spur, slopes W; thence along W slope.</p> <p>23.00 Bottom of draw, drains W; asc. over SW slope.</p> <p>30.00 Top of spur, slopes W; desc. over N slope.</p> <p>34.00 Bottom of draw, drains NW; along W slope.</p>	S 24	S 19		
S 24	S 19				

Dependent Resurvey of the E. Bdy. of T. 10 S., R. 24 E.,
Salt Lake Meridian, Utah

CHAINS	
38.00	Slope changes; asc. over SW slope.
40.43	Point for the cor. of secs. 13, 18, 19 and 24, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base to top, with brass cap mkd. <div style="text-align: center;"> T 10 S R 24 E R 25 E S 13 S 18 S 24 S 19 1975 </div>
	N. 0°02' E., bet. secs. 13 and 18. Asc. over SW slope through native grasses, shadscale and scattered sagebrush.
2.00	Top of spur, slopes W; desc. over NE slope.
8.50	Head of draw, drains N. 30° E.; thence along E slope.
14.00	Spur, slopes NE; desc. over NW slope.
18.00	Slope changes; desc. along E slope.
29.00	Small wash in bottom of hollow, drains W; asc. over S slope.
34.00	Top of spur, slopes SW; desc. over NW slope.
36.50	Bottom of draw, drains SW; asc. over SE slope.
40.43	The ¼ sec. cor. of secs. 13 and 18, monumented with a sandstone, 24 x 10 x 4 ins., firmly set 12 ins. in the ground, mkd. ¼ on W face with a small mound of stone to W. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone to top, with brass cap mkd. <div style="text-align: center;"> T 10 S R 24 E R 25 E ¼ S 13 S 18 1975 </div> Deposit the mkd. stone alongside the iron post. Corner is set on S slope, 10 ft. below top of spur, projecting W. <hr style="width: 20%; margin: 10px auto;"/> N. 0°06' E., beginning new measurement. Asc. over SE slope.
0.60	Top of spur, projecting W; desc. over NW slope.

Dependent Resurvey of the E. Bdy. of T. 10 S., R. 24 E.,
Salt Lake Meridian, Utah

CHAINS																	
4.00	Bottom of draw, drains NW; asc. over S slope.																
5.50	Top of spur, slopes W; desc. over steep NW slope.																
16.30	Dirt road, bears N. 60° E. and S. 60° W.; desc. over gentle N slope.																
24.00	S rim of canyon, bears NE and SW; desc. over steep N slope.																
34.00	Evacuation Creek in canyon bottom, drains SE; asc. over steep rocky SW slope.																
38.80	N rim of canyon, bears NW and E; over gentle S slope.																
38.99	The cor. of secs. 7, 12, 13 and 18, monumented with a sandstone, 24 x 13 x 8 ins., firmly set in mound of stone, dimly mkd. 2 notches on N edge.																
	At the corner point																
	Set an iron post, 28 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 5 ft. base to top, with brass cap mkd.																
	<table style="margin: auto;"> <tr><td colspan="2">T 10 S</td></tr> <tr><td colspan="2">R 24 E R 25 E</td></tr> <tr><td colspan="2"> </td></tr> <tr><td style="border-right: 1px solid black;">S 12</td><td>S 7</td></tr> <tr><td style="border-right: 1px solid black;">S 13</td><td>S 18</td></tr> <tr><td colspan="2"> </td></tr> <tr><td colspan="2">1975</td></tr> </table>	T 10 S		R 24 E R 25 E				S 12	S 7	S 13	S 18			1975			
T 10 S																	
R 24 E R 25 E																	
S 12	S 7																
S 13	S 18																
1975																	
	Deposit the accepted stone alongside the iron post.																
	Cor. is set on small spur, gently sloping S.																
	N. 0°09' W., bet. secs. 7 and 12.																
	Asc. over gentle S slope through native grasses, shade-scale and sagebrush.																
10.50	Underground pipeline, bears N and S. 26° E.																
17.00	Slope changes; asc. over SE slope.																
23.00	Top of spur, slopes SE; desc. over NE slope.																
25.00	Underground pipeline, bears N. 25° W. and S.																
32.00	Bottom of draw, drains E; asc. over SE slope.																
40.07	The ¼ sec. cor. of secs. 7 and 12, monumented with a sandstone, 24 x 14 x 3 ins., firmly set 12 ins. in the ground, mkd. ¼ on W face with small mound of stone to W.																
	At the corner point																
	Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.																
	<table style="margin: auto;"> <tr><td colspan="2">T 10 S</td></tr> <tr><td colspan="2">R 24 E R 25 E</td></tr> <tr><td colspan="2"> </td></tr> <tr><td colspan="2">¼</td></tr> <tr><td colspan="2"> </td></tr> <tr><td style="border-right: 1px solid black;">S 12</td><td>S 7</td></tr> <tr><td colspan="2"> </td></tr> <tr><td colspan="2">1975</td></tr> </table>	T 10 S		R 24 E R 25 E				¼				S 12	S 7			1975	
T 10 S																	
R 24 E R 25 E																	
¼																	
S 12	S 7																
1975																	

Dependent Resurvey of the E. Bdy. of T. 10 S., R. 24 E.,
Salt Lake Meridian, Utah

CHAINS					
	<p>Deposit the mkd. stone alongside the iron post.</p> <hr/> <p>N. 0°12' W., beginning new measurement.</p> <p>Asc. over SE slope.</p> <p>4.50 Top of spur, slopes NE; desc. over N slope.</p> <p>16.00 S rim of canyon, bears E and W; desc. over steep N slope.</p> <p>26.00 White River, 3 chs. wide, flows W; thence along canyon bottom.</p> <p>31.00 Base of sandstone ledge, bears E and W; asc. abruptly.</p> <p>34.00 N rim of canyon, bears E and W; asc. over gentle SW slope.</p> <p>39.99 The cor. of secs. 1, 6, 7 and 12, monumented with a sandstone, 24 x 10 x 8 ins., firmly set 12 ins. in the ground, mkd. 5 notches on S and 1 notch on N edge with small mound of stone to W.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 10 S</p> <p>R 24 E R 25 E</p> <table border="1" style="margin: auto;"> <tr> <td>S 1</td> <td>S 6</td> </tr> <tr> <td>S 12</td> <td>S 7</td> </tr> </table> <p>1975</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p>	S 1	S 6	S 12	S 7
S 1	S 6				
S 12	S 7				
	<p>N. 0°01' W., bet. secs. 1 and 6.</p> <p>Asc. over SW slope through native grasses, shadscale and scattered sagebrush.</p> <p>21.50 Top of spur, slopes SW; desc. over NW slope.</p> <p>26.00 Small wash in bottom of draw, drains SW; asc. over SW slope.</p> <p>29.00 Underground pipeline, bears N. 23° E. and S. 23° W.</p> <p>30.50 Dirt road, bears NW and SE.</p> <p>37.70 Top of spur, slopes SW; desc. over NW slope.</p> <p>39.69 The ¼ sec. cor. of secs. 1 and 6, monumented with a sandstone, 18 x 10 x 4 ins., firmly set 10 ins. in the ground, mkd. ¼ on W face with scattered mound of stone to W.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to top, in a mound of stone, 4 ft. base to top, with brass cap mkd.,</p>				

Dependent Resurvey of the E. Bdy. of T. 10 S., R. 24 E.,
Salt Lake Meridian, Utah

CHAINS	
	<p style="text-align: center;">T 10 S R 24 E R 25 E 1/4 S 1 S 6 1975</p> <p>Deposit the mkd. stone alongside the iron post.</p> <hr/> <p>N. 0°10' E., beginning new measurement.</p> <p>Desc. over NW slope.</p> <p>2.00 Bottom of draw, drains SW; asc. over SE slope.</p> <p>6.00 Top of spur, slopes SW; thence along W slope.</p> <p>10.50 Top of ridge, bears NE and SW; desc. over NW slope.</p> <p>26.00 Head of draw, drains SW; asc. over SE slope along W side of draw.</p> <p>39.55 The cor. of Tps. 9 and 10 S., Rs. 24 and 25 E., monument- ed with a sandstone, 14 x 6 x 6 ins., firmly set 8 ins. in the ground, dimly mkd. 6 notches on the N, S, E and W edges, surrounded by a scattered mound of stone.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone to top, with brass cap mkd.</p> <p style="text-align: center;">T 9 S R 24 E R 25 E S 36 S 31 S 1 S 6 T 10 S 1975</p> <p>Deposit the dimly mkd. stone alongside the iron post.</p>
	<p style="text-align: center;">Dependent Resurvey of the W. Bdy. of T. 10 S., R. 24 E., Salt Lake Meridian, Utah (Restoring the survey executed by H. R. Talamantes and H. D. Heist in 1904)</p> <hr/> <p>From the stan. cor. of Tps. 10 S., Rs. 23 and 24 E., heretofore described.</p> <p>N. 0°03' W., bet. secs. 31 and 36.</p> <p>Desc. over NE slope through native grasses, shadscale and sagebrush.</p> <p>4.00 Small wash in bottom of draw, drains NW; asc. over SW slope.</p> <p>8.00 Top of spur, slopes W; desc. over NW slope.</p>

Dependent Resurvey of the W. Bdy. of T. 10 S., R. 24 E.,
Salt Lake Meridian, Utah

CHAINS	
12.00	Base of descent, bears SW and NE; thence over nearly level bottom land.
21.00	Asphalt Wash, 30 lks. wide, 10 ft. deep, drains NE.
30.00	Small wash, drains E.
39.93	The $\frac{1}{4}$ sec. cor. of secs. 31 and 36, monumented with a sandstone, 18 x 8 x 8 ins., firmly set 10 ins. in the ground, dimly mkd. $\frac{1}{4}$ on W face with small mound of stone to W. At the corner point Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 10 S R 23 E R 24 E $\frac{1}{4}$ S 36 S 31 1975 </div> Deposit the dimly mkd. stone alongside the iron post. Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W of cor. <hr style="width: 20%; margin: auto;"/> N. $0^{\circ}02'$ W., beginning new measurement. Continue over bottom land through thick sagebrush. 2.00 Asphalt Wash, 30 lks. wide, 8 ft. deep, drains NW. 4.25 Same wash, drains NE. 9.00 Same wash, drains NW. 13.50 Same wash, drains NE; desc. over gentle NE slope. 40.12 The cor. of secs. 25, 30, 31 and 36, monumented with a sandstone, 36 x 8 x 8 ins., firmly set 18 ins. in the ground, mkd. 5 notches on N and 1 notch on S edge with scattered mound of stone to W. At the corner point Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 10 S R 23 E R 24 E S 25 S 30 S 36 S 31 1975 </div> Deposit the mkd. stone alongside the iron post. Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W of cor. <hr/> North, bet. secs. 25 and 30.

Dependent Resurvey of the W. Bdy. of T. 10 S., R. 24 E.,
Salt Lake Meridian, Utah

CHAINS	
	Over gentle rolling land through native grasses, shade and scattered sagebrush.
1.00	Asphalt Wash, drains SE; begin ascent over gentle NW slope
3.50	Dirt road, bears N. 14°30' E. and S. 14°30' W.
7.00	Asphalt Wash, drains NE.
13.00	Base of steep ascent, bears NE and SW; asc. over ledgy SE slope.
18.00	Top of spur, slopes NE; desc. over NW slope.
20.00	Bottom of draw, drains NE; asc. over SE slope.
23.00	Top of spur, slopes E; desc. over N slope.
26.00	Bottom of draw, drains E; asc. over SE slope.
30.00	Top of ascent; thence along gentle E slope.
35.00	Slope changes; desc. over steep N slope.
36.75	Bottom of draw, drains E; asc. over SE slope.
40.44	The 1/4 sec. cor. of secs. 25 and 30, monumented with a sandstone, 28 x 10 x 6 ins., firmly set 18 ins. in the ground, mkd. 1/4 on W face with small mound of stone to W.
	At the corner point
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.
	<p>T 10 S R 23 E R 24 E 1/4 S 25 S 30 1975</p>
	Deposit the mkd. stone alongside the iron post.
	<hr style="width: 20%; margin: 0 auto;"/>
	N. 0°01' W., beginning new measurement.
	Desc. over NE slope.
3.00	Bottom of draw, drains E; asc. over SE slope.
4.50	Top of spur, slopes E; desc. over NE slope.
7.00	Bottom of draw, drains E; asc. over SE slope.
11.00	Top of spur, slopes E; desc. along gentle E slope.
19.50	Begin descent over steep NE slope.
32.00	Base of descent, bears NW and SE; thence over nearly level bottom land.
38.00	Wash, 20 lks. wide, 5 ft. deep, drains NE.
39.96	The cor. of secs. 19, 24, 25 and 30, monumented with a sandstone, 24 x 14 x 6 ins., firmly set 12 ins. in the ground, mkd. 4 notches on N and 2 notches on S edge.

Dependent Resurvey of the W. Bdy. of T. 10 S., R. 24 E.,
Salt Lake Meridian, Utah

CHAINS	
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 10 S R 23 E R 24 E S 24 S 19 S 25 S 30 1975</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.</p>
	<p>N. 0°12' E., bet. secs. 19 and 24.</p> <p>Desc. over gentle N slope through native grasses, shade and sagebrush.</p> <p>3.00 Dirt road, bears N. 4° W. and S. 4° E.</p> <p>6.00 Asphalt Wash, 30 lks. wide, 8 ft. deep, drains NW.</p> <p>18.00 Same wash, drains NE.</p> <p>25.00 Same wash, drains W.</p> <p>30.00 Base of steep ascent, bears NW and SE; asc. over steep SW slope.</p> <p>35.00 Top of spur, projects NW; desc. over NE slope.</p> <p>37.50 Bottom of draw, drains NW; asc. over SW slope.</p> <p>40.39 The ¼ sec. cor. of secs. 19 and 24, monumented with a sandstone, 30 x 14 x 6 ins., firmly set 15 ins. in the ground, mkd. ¼ on W face, with scattered mound of stone to W.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 10 S R 23 E R 24 E ¼ S 24 S 19 1975</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°46' W., beginning new measurement.</p> <p>Asc. over SW slope.</p> <p>0.50 Top of spur, slopes NW; desc. over N slope.</p>

Dependent Resurvey of the W. Bdy. of T. 10 S., R. 24 E.,
Salt Lake Meridian, Utah

<p>CHAINS 4.00</p>	<p>Small wash in bottom of draw, drains W; asc. over SW slope.</p>				
<p>24.00</p>	<p>Base of high ridge, bears NW and SE; asc. over steep SW slope.</p>				
<p>30.50</p>	<p>Top of ridge, bears NW and SE; desc. over rocky NE slope through scattered juniper and pinon.</p>				
<p>38.78</p>	<p>The cor. of secs. 13, 18, 19 and 24, monumented with a sandstone, 18 x 8 x 6 ins., firmly set 10 ins. in the ground, mkd. 3 notches on the N and S edge, from which the original bearing trees</p> <p>A cedar, 9 ins. diam., bears N. 21° E., 91 lks. dist., mkd. T10S R24E S18 BT.</p> <p>A cedar, 10 ins. diam., bears S. 83°30' E., 33 lks. dist., mkd. T10S R24E S19 BT. (Record, 35 lks.)</p> <p>A cedar, 12 ins. diam., bears S. 67° W., 49 lks. dist., mkd. T10S R23E S24 BT. (Record, 46 lks.)</p> <p>A cedar, 7 ins. diam., bears N. 25° W., 91 lks. dist., mkd. T10S R23E S13 BT.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 10 S</p> <p>R 23 E R 24 E</p> <p> </p> <table border="1" style="margin: auto;"> <tr> <td>S 13</td> <td>S 18</td> </tr> <tr> <td>S 24</td> <td>S 19</td> </tr> </table> <p> </p> <p>1975</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p>	S 13	S 18	S 24	S 19
S 13	S 18				
S 24	S 19				
	<p>N. 0°02' E., bet. secs. 13 and 18.</p> <p>Desc. over NE slope through scattered shadscale, grass, juniper and pinon.</p>				
<p>4.00</p>	<p>Bottom of draw, drains NE; thence along broken E slope.</p>				
<p>19.00</p>	<p>Base of ridge, bears NE and SW; asc. over steep SW slope.</p>				
<p>36.00</p>	<p>Top of spur, slopes E; desc. along E slope.</p>				
<p>36.54</p>	<p>The witness ¼ sec. cor. of secs. 13 and 18, monumented with a sandstone, 20 x 12 x 6 ins. firmly set 12 ins. in the ground, mkd. ¼ WC on W face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC</p> <p>T 10 S</p> <p>R 23 E R 24 E</p> <p> </p> <p>¼</p> <p>▲</p> <table border="1" style="margin: auto;"> <tr> <td>S 13</td> <td>S 18</td> </tr> </table> <p> </p> <p>1975</p> </div>	S 13	S 18		
S 13	S 18				

Dependent Resurvey of the W. Bdy. of T. 10 S., R. 24 E.,
Salt Lake Meridian, Utah

CHAINS					
	<p>Deposit the mkd. stone alongside the iron post.</p> <p style="text-align: center;">_____</p> <p>N. 0°15' E., beginning new measurement.</p> <p>Desc: over rocky NE slope.</p>				
0.50	Rim of sandstone ledge, bears NW and SE; desc. over perpendicular ledge.				
2.50	Bottom of cover in sandstone, course E; asc. abruptly.				
2.97	True point for the ¼ sec. cor. of secs. 13 and 18, at proportionate dist., falls on perpendicular face of sandstone ledge, and cannot be monumented.				
6.30	Top of sandstone spur, projects E; begin abrupt descent over N slope.				
18.00	Bottom of draw, drains NE; asc. over SE slope.				
21.00	Top of spur, slopes NE; desc. over N slope.				
28.00	Base of ridge, bears E and W; desc. over gradual N slope.				
43.25	<p>Point for the cor. of secs. 7, 12, 13 and 19, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 10 S</p> <p>R 23 E R 24 E</p> <p style="margin-left: 100px;"> </p> <table style="margin-left: 100px; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 12</td> <td style="padding: 0 5px;">S 7</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 13</td> <td style="padding: 0 5px;">S 18</td> </tr> </table> <p style="margin-left: 100px;"> </p> <p>1975</p> </div> <p>Corner is set 36 lks. E of small wash draining N.</p>	S 12	S 7	S 13	S 18
S 12	S 7				
S 13	S 18				
	<p>N. 0°15' E., bet. secs. 7 and 12.</p> <p>Desc. over gradual N slope through scattered native grasses, shadscale and sagebrush.</p>				
6.00	Enter river bottom land.				
11.00	White River, 3 chs. wide, flows SW.				
20.00	Leave river bottom land; asc. over S slope.				
29.00	Slope changes; asc. over SE slope.				
40.00	Top of spur, slopes E; desc. over N slope.				
40.28	<p>The ¼ sec. cor. of secs. 7 and 12, monumented with a limestone, 16 x 10 x 5 ins., firmly set 8 ins. in the ground, mkd. ¼ on W face and in a scattered mound of stone.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base to top, with brass cap mkd.</p>				

Dependent Resurvey of the W. Bdy. of T. 10 S., R. 24 E.,
Salt Lake Meridian, Utah

CHAINS	
	<p style="text-align: center;">T 10 S R 23 E R 24 E S 12 S 7 1975</p> <p>Deposit the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°02' E., beginning new measurement.</p> <p>Desc. over NE slope.</p> <p>1.50 Small wash in bottom of draw, drains SE; asc. over SW slope.</p> <p>8.50 Top of spur, slopes W; desc. over NW slope.</p> <p>10.00 Small wash, drains W; asc. over SE slope.</p> <p>18.50 Top of spur, slopes E; desc. over N slope.</p> <p>22.00 Bottom of draw, drains E; asc. over steep SE slope.</p> <p>33.00 Rim of ledge, bears NE and SW; asc. over gentle SE slope.</p> <p>40.12 The cor. of secs. 1, 6, 7 and 12, monumented with a sandstone, 18 x 12 x 8 ins., firmly set 10 ins. in the ground, mkd. 1 notch on N and 5 notches on S edge with scattered mound of stone to W.</p> <p>At the corner poin</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T 10 S R 23 E R 24 E S 1 S 6 S 12 S 7 1975</p> <p>Deposit the mkd. stone alongside the iron post.</p>
	<p>N. 0°03' W., bet. secs. 1 and 6.</p> <p>Asc. over gentle SE slope through scattered native grasses, shadscale and sagebrush.</p> <p>1.00 Top of small spur, slopes E; desc. over NE slope.</p> <p>8.00 Bottom of draw, drains SE; asc. over SW slope.</p> <p>15.00 Top of ridge, bears NE and SW; desc. over NW slope.</p> <p>24.00 Bottom of draw, drains SW; asc. over SE slope.</p> <p>39.50 Top of spur, projects W; desc. over gentle N slope.</p>


Dependent Resurvey of the W. Bdy. of T. 10 S., R. 24 E.,
Salt Lake Meridian, Utah

CHAINS
39.89

The 1/4 sec. cor. of secs. 1 and 6, monumented with a sandstone, 14 x 8 x 6 ins., firmly set 8 ins. in the ground, mkd. 1/4 on W face.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a mound of stone to top, with brass cap mkd.



Deposit the mkd. stone alongside the iron post.

Corner is located at cor. of fences extending N and S.

N. 0°05' E., beginning new measurement.

Desc. over gentle N slope.

13.00 Bottom of draw, drains NW; asc. over S slope.

18.00 Dirt road, bears N. 69° E. and S. 69° W.

21.00 Top of ridge, bears E and W; desc. over N slope.


28.50 Bottom of draw, drains NW; asc. over SW slope.

31.00 Top of ascent, bears NW and SE; desc. over gentle N slope.

40.30 The cor. of Tps. 9 and 10 S., Rs. 23 and 24 E., monumented with a broken sandstone, loosely set, one broken piece having 6 notches on one edge.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit the pieces of stone alongside the iron post.

Corner is located in fence, extending N and S.

Dependent Resurvey of the N. Bdy. of T. 10 S., R. 24 E.,
Salt Lake Meridian, Utah

(Restoring the survey executed by A. R. Talamantes
and H. D. Heist in 1904)

Dependent Resurvey of the N. Bdy. of T. 10 S., R. 24 E.,
Salt Lake Meridian, Utah

CHAINS	
	<p>From the cor. of Tps. 9 and 10 S., Rs. 24 and 25 E., heretofore described.</p> <p>S. 89°59' W., bet. secs. 1 and 36.</p> <p>Asc. over SE slope through scattered shadscale and native grasses.</p>
4.00	Top of spur, projects SW; desc. over NW slope.
18.00	Bottom of draw, drains SW; asc. over E slope.
26.00	Top of spur, slopes SE; thence along S slope.
31.00	Begin descent over SW slope.
32.50	Bottom of draw, drains S; asc. over SE slope.
37.00	Top of spur, projects S; desc. over W slope.
39.89	<p>The $\frac{1}{4}$ sec. cor. of secs. 1 and 36, monumented with a sandstone, 15 x 10 x 4 ins., firmly set, 8 ins. in the ground, mkd. $\frac{1}{4}$ on N face, surrounded by a scattered mound of stone.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 9 S R 24 E</p> <p>$\frac{1}{4}$ $\frac{S 36}{S 1}$</p> <p>T 10 S</p> <p>1975</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°56' W., beginning new measurement.</p> <p>Desc. over SW slope.</p>
3.50	Bottom of draw, drains SW; asc. over SE slope.
7.50	Top of spur, slopes SW; desc. over NW slope.
12.00	Bottom of draw, drains SW; thence along S slope.
19.00	Wash, 20 lks. wide, 6 ins. deep, in bottom of hollow, drains SE; asc. over NE slope.
23.00	Top of spur, projects SE; desc. over SW slope.
28.00	Bottom of draw, drains SE; asc. over SE slope.
30.50	Top of spur, slopes SE; desc. over SW slope.
35.00	Bottom of draw, drains SE; asc. over SE slope.
39.85	<p>The cor. of secs. 1, 2, 35 and 36, monumented with a sandstone, 14 x 8 x 6 ins., firmly set 8 ins. in the ground, mkd. 5 notches on W and 1 notch on E edge, with scattered mound of stone to W.</p> <p>At the corner point</p>

Dependent Resurvey of the N. Bdy. of T. 10 S R. 24 E.,
Salt Lake Meridian, Utah

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T 9 S R 24 E S 35 S 36 S 2 S 1 T 10 S 1975</p> <p>Deposit the mkd. stone alongside the iron post.</p>
	<p>N. 89°58' W., bet. secs. 2 and 35.</p> <p>Asc. over E slope through scattered native grasses and shadscale.</p> <p>3.00 Top of ridge, bears N and S; desc. over W slope.</p> <p>12.50 Head of draw, drains SW; thence along broken S slope.</p> <p>20.50 Bottom of draw, drains S; asc. over steep SE slope.</p> <p>23.00 Top of spur, slopes S; desc. over SW slope.</p> <p>25.50 Bottom of draw, drains S; asc. over SE slope.</p> <p>29.00 Top of spur, projects S; desc. over W slope.</p> <p>32.50 Bottom of draw, drains SW; asc. over SE slope.</p> <p>35.50 Top of spur, slopes SW; desc. over SW slope.</p> <p>39.87 Point for the ¼ sec. cor. of secs. 2 and 35, at proportionate distance, falls in a scattered mound of stone; there is no remaining evidence of the original corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T 9 S R 24 E ¼ <u> S 35 </u> S 2 T 10 S 1975</p> <p>Cor. is set on small edge, bears E and W, 30 ft. above dirt road in canyon bottom.</p> <p>Desc. over SW slope.</p> <p>42.00 Dirt road in canyon bottom, bears N and SE; also small wash along edge of road, drains irregularly SE; asc. over steep NE slope.</p> <p>49.00 Top of spur, slopes SE; asc. over SE slope.</p> <p>62.00 Rim of sandstone ledge, bears NE and SW; asc. over NE slope.</p> <p>78.50 Top of spur, projects NW; desc. over SW slope through scattered juniper and pinon timber.</p>

Dependent Resurvey of the N. Bdy. of T. 10 S., R. 24 E.,
Salt Lake Meridian, Utah

CHAINS					
79.74	<p>The cor. of secs. 2, 3, 34 and 35, monumented with a sandstone, 14 x 10 x 6 ins., firmly set 8 ins. in the ground, mkd. 2 notches on E and 4 notches on W edge, with a scattered mound of stone to W.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 9 S R 24 E</p> <table border="1" style="margin: auto;"> <tr> <td>S 34</td> <td>S 35</td> </tr> <tr> <td>S 3</td> <td>S 2</td> </tr> </table> <p>T 10 S 1975</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p>	S 34	S 35	S 3	S 2
S 34	S 35				
S 3	S 2				
	<p>S. 89°53' W., bet. secs. 3 and 34.</p> <p>Desc. over SW slope through scattered juniper, pinon, native grasses and shadscale.</p> <p>2.00 Bottom of draw, drains NW; asc. over NE slope.</p> <p>4.50 Top of spur, slopes NW; desc. along N slope.</p> <p>14.00 Bottom of descent, drains N; asc. over NE slope.</p> <p>15.25 Dirt road, bears N. 20° E. and S.</p> <p>19.00 Slope changes; asc. over steep E slope.</p> <p>28.00 Rim of ledge, bears N and S; thence along gentle S slope.</p> <p>29.00 Dirt road, bears N. 85° W. and irregularly SE; slope changes; thence along gentle N slope.</p> <p>36.86 Intersect line 2-3, Atlanta Lode, M.S. No. 5275 at a point from which</p> <div style="margin-left: 40px;"> <p>Cor. No. 2, Atlanta Lode, M.S. No. 5275 monumented with a sandstone, 30 x 8 x 6 ins., projecting 10 ins. above ground, chiseled 2-4-5275 on SE face, bears N. 68°18' W., 20.88 chs. dist.</p> <p>Cor. No. 3, Atlanta Lode, M.S. No. 5275 monumented with a sandstone, 30 x 12 x 4 ins., projecting 10 ins. above ground, chiseled 3-5275 on NW face, bears S. 68°18' E., 1.83 chs. dist.</p> </div> <p>39.50 Top of ascent, bears NW and SE; over nearly level land, leave timber.</p> <p>39.89 The ¼ sec. cor. of secs. 3 and 34, determined from a tie of record bearing and distance to Cor. No. 3, Atlanta Lode, M.S. No. 5275.</p> <p>At the corner point</p>				

Dependent Resurvey of the N. Bdy. of T. 10 S., R. 24 E.,
Salt Lake Meridian, Utah

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 9 S R 24 E
 $\frac{1}{4}$ $\frac{S 34}{S 3}$
 T 10 S
 1975

From this cor., Cor. No. 3 of M.S. No. 5275, heretofore described, bears S. 81° 55' E., 4.78 chs. dist.

N. 89°49' W., beginning new measurement.

Over nearly level land.

7.50 Begin ascent over NE slope.

9.17 Intersect line 4-1, Atlanta Lode, M.S. No. 5275 at a point from which

Cor. No. 1, Atlanta Lode, M.S. No. 5275 monumented with a sandstone, 28 x 14 x 6 ins., projecting 10 ins. above ground, chiseled 1-1-5275 on NE face, bears N. 68°18' W., 9.61 chs. dist.

Cor. No. 4, Atlanta Lode, M.S. No. 5275 monumented with a sandstone, 32 x 12 x 6 ins., projecting 12 ins. above ground, chiseled 4-5275 on NW face, bears S. 68°18' E., 13.10 chs. dist.

13.00 Top of spur, slopes N; desc. over NW slope.

16.00 Bottom of draw, drains NW; asc. over NW slope.

18.50 Small spur, slopes N; desc. over NW slope.

28.00 Base of descent, bears NE and SW; thence over nearly level land.

40.14 The cor. of secs. 3, 4, 33 and 34, monumented with a sandstone, 15 x 10 x 5 ins., firmly set in scattered mound of stone, dimly mkd. 3 notches on the E and W edge.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone to top, with brass cap mkd.

T 9 S R 24 E
 S 33 | S 34
 S 4 | S 3
 T 10 S
 1975

Deposit the mkd. stone alongside the iron post.

N. 89°56' W., bet. secs. 4 and 33.

Over nearly level land through scattered native grasses, shadscale and sagebrush.

Dependent Resurvey of the N. Bdy. of T. 10 S., R. 24 E.
Salt Lake Meridian, Utah

CHAINS					
33.00	Begin descent over SW slope.				
39.94	The ¼ sec. cor. of secs. 4 and 33, monumented with a sandstone, 12 x 8 x 6 ins., firmly set in a small mound of stone, mkd. ¼ on N face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd. <div style="text-align: center;"> <p>T 9 S R 24 E</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding-right: 5px;">¼</td> <td style="border-left: 1px solid black; padding-left: 5px;">S 33</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 5px;">S 4</td> </tr> </table> <p>T 10 S 1975</p> </div> Deposit the mkd. stone alongside the iron post. <hr style="width: 20%; margin: 10px auto;"/> N. 89°55' W., beginning new measurement. Desc. over SW slope.	¼	S 33		S 4
¼	S 33				
	S 4				
4.00	Small wash in bottom of draw, drains SW; asc. over SE slope.				
9.00	Top of spur, slopes SW; desc. over NW slope.				
12.50	Small draw, drains SW; asc. over SE slope.				
16.00	Rim of hollow, bears NE and SW; thence over nearly level land.				
40.29	The cor. of secs. 4, 5, 32 and 33, monumented with a sandstone, 18 x 6 x 5 ins., firmly set 10 ins. in the ground, mkd. 4 notches on E and 2 notches on W edge. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone to top, with brass cap mkd. <div style="text-align: center;"> <p>T 9 S R 24 E</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding-right: 5px;">S 32</td> <td style="border-left: 1px solid black; padding-left: 5px;">S 33</td> </tr> <tr> <td style="padding-right: 5px;">S 5</td> <td style="border-left: 1px solid black; padding-left: 5px;">S 4</td> </tr> </table> <p>T 10 S 1975</p> </div> Deposit the mkd. stone alongside the iron post.	S 32	S 33	S 5	S 4
S 32	S 33				
S 5	S 4				
	N. 89°51' W., bet. secs. 5 and 32. Over nearly level land, through scattered native grasses and shadscale.				
1.00	Rim of hollow, bears NE and SW; desc. over NW slope.				
5.00	Small wash in bottom of hollow, drains SW; asc. over SE slope.				
9.00	W rim of hollow, bears NE and SW; thence over nearly level land.				

Dependent Resurvey of the N. Bdy. of T. 10 S., R. 24 E.,
Salt Lake Meridian, Utah

CHAINS	
20.00	Begin ascent over NE slope.
24.50	Top of ascent slopes N; desc. over NW slope.
31.00	Bottom of descent, bears NE and SW; asc. along rocky S slope.
39.91	The $\frac{1}{4}$ sec. cor. of secs. 5 and 32, monumented with a sandstone, 14 x 10 x 4 ins., firmly set 8 ins. in the ground, mkd. $\frac{1}{4}$ on N face with scattered mound of stone to N. At the corner point Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 14 ins. in the ground to top, in a mound of stone, 4 ft. base to top, with brass cap mkd. <div style="text-align: center;"> T 9 S R 24 E S 32 $\frac{1}{4}$ ——— S 5 T 10 S 1975 </div> Deposit the mkd. stone alongside the iron post. <hr style="width: 20%; margin: auto;"/> West, beginning new measurement. Along rocky S slope.
17.00	Slope changes; desc. over W slope.
21.50	Head of draw, drains SW; asc. over SE slope.
25.00	Slope changes; thence over nearly level land.
40.03	The cor. of secs. 5, 6, 31 and 32, monumented with a sandstone, 16 x 10 x 5 ins., firmly set 8 ins. in the ground, mkd. 5 notches on E and 1 notch on W edge with scattered mound of stone to N. At the corner point Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3 $\frac{1}{2}$ ft. base to top, with brass cap mkd. <div style="text-align: center;"> T 9 S R 24 E S 31 S 32 S 6 S 5 T 10 S 1975 </div> Deposit the mkd. stone alongside the iron post. <hr/> N. 89°56' W., bet. secs. 6 and 31. Over gentle rolling land, through scattered native grasses, shadscale and sagebrush.
6.00	Begin descent over gentle W slope.

Dependent Resurvey of the N. Bdy. of T. 10 S., R. 24 E.,
Salt Lake Meridian, Utah

CHAINS 39.99	<p>The $\frac{1}{4}$ sec. cor. of secs. 6 and 31, monumented with a sandstone, 14 x 10 x 5 ins., firmly set 8 ins. in the ground, mkd. $\frac{1}{4}$ on N face and in a scattered mound of stone.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 9 S R 24 E $\frac{1}{4}$ <u>S 31</u> S 6 T 10 S 1975</p> <p>Deposit the mkd. stone alongside the iron post.</p> <hr/> <p>N. 89°57' W., beginning new measurement.</p> <p>Over nearly level land.</p>
10.25	Dirt road, bears N. 5° E. and S. 5° W.
26.00	Small stock pond in bottom of draw, drains NW; asc. over gentle NE slope.
30.00	Slope changes; thence along gentle N slope.
39.35	The cor. of Tps. 9 and 10 S., Rs. 23 and 24 E., heretofore described.
<p>Dependent Resurvey of the Subdivisional Lines of T. 10 S., R. 24 E., Salt Lake Meridian, Utah</p>	
<p>(Restoring the survey executed by A. R. Talamantes and H. D. Heist in 1904)</p>	
<p>From the stan. cor. of secs. 35 and 36, S. Bdy.</p>	
<p>N. 0°07' W., bet. secs. 35 and 36.</p>	
<p>Desc. over gentle N slope through scattered shadscale and native grasses.</p>	
2.00	Slope changes; desc. over rocky NE slope.
9.00	Small wash in bottom of hollow, drains E; asc. over steep S slope.
12.00	Top of spur, slopes E; desc. over steep N slope.
17.00	Bottom of draw, drains NE; asc. over SE slope.
27.00	Top of spur, projects NE; desc. over NW slope.
40.41	<p>The $\frac{1}{4}$ sec. cor. of secs. 35 and 36, monumented with a sandstone, 36 x 20 x 8 ins., firmly set 18 ins. in the ground, mkd. $\frac{1}{4}$ on W face with scattered mound of stone to W.</p>
<p>At the corner point</p>	

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 10 S R 24 E</p> <p> </p> <p> ¼</p> <p> </p> <p> S 35 S 36</p> <p> </p> <p> 1975</p> </div>
	<p>Deposit the mkd. stone alongside the iron post.</p>
	<p>N. 0°08' E., beginning new measurement.</p>
	<p>Desc. over NW slope.</p>
8.00	<p>Bottom of draw, drains NE; desc. along gentle E slope.</p>
15.25	<p>Small wash in bottom of hollow, drains SE; asc. over steep S slope.</p>
19.00	<p>Top of spur, projects SE; desc. over NE slope.</p>
21.00	<p>Bottom of draw, drains E; asc. over SE slope.</p>
28.00	<p>Top of spur, projects NE; desc. over NW slope.</p>
38.50	<p>Bottom of draw, drains NE; asc. over SE slope.</p>
40.00	<p>The cor. of secs. 25, 26, 35 and 36, monumented with a sandstone, 24 x 8 x 6 ins., firmly set 18 ins. in the ground, mkd. 1 notch on the S and E edge.</p>
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 10 S R 24 E</p> <p> </p> <p> S 26 S 25</p> <p> S 35 S 36</p> <p> </p> <p> 1975</p> </div>
	<p>Deposit the mkd. stone alongside the iron post.</p>
	<p>Cor. is located on SE slope at base of ledge 10 ft. high, bearing NE and SW.</p>
	<p>From the cor. of secs. 25, 30, 31 and 36, E. Bdy.</p>
	<p>S. 89°58' W., bet. secs. 25 and 36.</p>
	<p>Asc. over gentle E slope through scattered native grasses, shadscale and sagebrush.</p>
0.50	<p>Top of small spur, slopes N; desc. along gentle N slope.</p>

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
9.75	Spur, projects NW; desc. over SW slope.
22.00	Slope changes; desc. over N slope.
38.50	Evacuation Creek, drains N; asc. over E slope.
40.08	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{r} T\ 10\ S\ R\ 24\ E \\ \quad \quad \quad S\ 25 \\ \frac{1}{4} \quad \quad \quad \hline \quad \quad \quad S\ 36 \\ \quad \quad \quad 1975 \end{array}$
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N of corner.
	Asc. over NE slope.
55.00	Top of spur, slopes N; desc. over NW slope.
60.00	Bottom of draw, drains NE; asc. over SE slope.
65.50	Top of spur, slopes NE; desc. over NW slope.
77.80	Bottom of draw, drains NE; asc. over SE slope.
80.16	The cor. of secs. 25, 26, 35 and 36.
	N. $0^{\circ}12'$ W., bet. secs. 25 and 26.
	Asc. over SE slope and sandstone ledge.
3.00	Top of spur, slopes NE; desc. over NW slope through native grasses and shadscale.
14.50	Small wash in bottom of hollow, drains NE; asc. over SE slope.
22.50	Top of spur, slopes E; desc. over N slope.
27.00	Bottom of draw, drains E; asc. over SE slope.
36.00	Top of spur, slopes E; desc. over N slope.
40.20	The $\frac{1}{4}$ sec. cor. of secs. 25 and 26, monumented with a sandstone, 20 x 15 x 10 ins., firmly set 10 ins. in the ground, mkd. $\frac{1}{4}$ on W face with scattered mound of stone to W.
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, in a mound of stone, $4\frac{1}{2}$ ft. base to top, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
	<p style="text-align: center;">T 10 S R 24 E</p> <p style="text-align: center;"> $\frac{1}{4}$ S 26 S 25 1975 </p> <p>Deposit the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°12' W., beginning new measurement.</p> <p>Desc. over N slope.</p> <p>9.00 Bottom of hollow, drains NE; asc. over steep S slope.</p> <p>15.00 Top of spur, slopes E; thence along E slope.</p> <p>20.75 Spur, slopes E; desc. over NE slope.</p> <p>26.50 Bottom of draw, drains NE; asc. over SE slope.</p> <p>34.00 Top of spur, projects NE; desc. over NW slope.</p> <p>39.64 The cor. of secs. 23, 24, 25 and 26, monumented with a sandstone, 18 x 11 x 7 ins., firmly set 10 ins. in the ground, mkd. 2 notches on S and 1 notch on E edge, with small mound of stone to W.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T 10 S R 24 E</p> <p style="text-align: center;"> S 23 S 24 S 26 S 25 1975 </p> <p>Deposit the mkd. stone alongside the iron post.</p>
	<p>From the cor. of secs. 19, 24, 25 and 30, E. Bdy.</p> <p>S. 89°48' W., bet. secs. 24 and 25.</p> <p>Along N slope through native grasses, shadscale and sagebrush.</p> <p>9.50 Base of ridge, bears NW and SE; asc. over steep rocky NE slope.</p> <p>13.50 Top of ridge, bears NW and SE; desc. over SW slope.</p> <p>22.00 Spur, slopes SW; desc. over steep NW slope.</p> <p>29.00 Evacuation Creek, drains N; asc. over SE slope.</p> <p>32.50 Slope changes; thence along rocky S slope.</p>


Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
39.99	<p>The ¼ sec. cor. of secs. 24 and 25, monumented with a sandstone, 24 x 10 x 4 ins., firmly set 12 ins. in the ground, mkd. ¼ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T 10 S R 24 E</p> <p style="text-align: center;">¼ $\frac{\\$ 24}{\\$ 25}$ 1975</p> <p>Deposit the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°49' W., beginning new measurement.</p> <p>Along S slope.</p> <p>3.50 Bottom of draw, drains SE; asc. over SE slope.</p> <p>20.00 Slope changes; asc. over E slope.</p> <p>25.50 Point of spur, slopes SE; desc. over SW slope.</p> <p>30.50 Bottom of descent, drains S; asc. over SE slope.</p> <p>34.50 Top of ridge, bears NE and SW; desc. over NW slope.</p> <p>40.23 The cor. of secs. 23, 24, 25 and 26.</p>
	<p>N. 0°25' E., bet. secs. 23 and 24.</p> <p>Desc. over NW slope through scattered native grasses, shadscale and sagebrush.</p> <p>3.50 Small wash in bottom of hollow, drains NE; asc. over SE slope.</p> <p>11.00 Slope changes; asc. over S slope.</p> <p>19.00 Top of spur, slopes E; desc. over N slope.</p> <p>25.00 Bottom of draw, drains E; asc. over SE slope.</p> <p>39.80 Dirt road, bears SW and curves N.</p> <p>40.30 The ¼ sec. cor. of secs. 23 and 24, monumented with a sandstone, 30 x 20 x 6 ins., firmly set 15 ins. in the ground, mkd. ¼ on W face with small mound of stone to W.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS

T 10 S R 24 E



Deposit the mkd. stone alongside the iron post.

There is no remaining evidence of the original bearing trees.

N. 0°04' W., beginning new measurement.

Asc. over SE slope and sandstone ledge, 30 ft. high.

- 0.40 Top of spur, slopes NE; desc. over NW slope.
- 1.75 Dirt road, bears NW and curves S.
- 6.00 Bottom of draw, drains NE; asc. over SE slope.
- 11.00 Top of spur, slopes NE; desc. over NW slope.
- 11.75 Small wash in bottom of hollow, drains E; asc. over SE slope.
- 15.25 Top of spur, slopes E; desc. over NE slope.
- 21.00 Bottom of draw, drains E; asc. over S slope.
- 22.50 Dirt road, bears E and W.
- 25.75 Top of ridge, bears E and W; desc. over N slope.
- 33.00 Dirt road, curves NE and SE; enter juniper and pinon.
- 33.25 Bottom of descent drains NE; asc. over SE slope.
- 39.50 Top of spur, slopes E; desc. over N slope.
- 39.91 The cor. of secs. 13, 14, 23 and 24, monumented with a sandstone, 18 x 14 x 5 ins., firmly set 10 ins. in the ground, mkd. 3 notches on S and 1 notch on E edge with small mound of stone to W, from which the remaining original bearing tree


A juniper, 6 ins. diam., bears N. 70° W., 1.71 chs. dist. mkd. T10S R24E S14 BT. (Record, 1.74)

There is no remaining evidence of the other bearing tree.

At the corner point:

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone to top, with brass cap mkd.

T 10 S R 24 E



1975

Deposit the mkd. stone alongside the iron post.

241

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
	<p>From the cor. of secs. 13, 18, 19 and 24, E. Bdy. S. 89°24' W., bet. secs. 13 and 24. Desc. over SW slope through scattered native grasses and shadscale.</p>
2.50	Head of draw, drains SW; thence along S slope.
12.50	Slope changes; desc. over SW slope.
19.50	Bottom of draw, drains NW; thence along N slope.
22.00	Slope changes; desc. over NW slope.
27.75	Evacuation Creek, drains NE; asc. over gentle E slope of creek bottom.
33.70	Small wash, drains SE into creek; asc. over gentle NE slope.
39.95	<p>The $\frac{1}{4}$ sec. cor. of secs. 13 and 24, monumented with a sandstone, 28 x 10 x 4 ins., firmly set 18 ins. in the ground, mkd. $\frac{1}{4}$ on N face with scattered mound of stone to N.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 4$\frac{1}{2}$ ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 10 S R 24 E <u> S 13</u> $\frac{1}{4}$ S 24 1975</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°51' W., beginning new measurement.</p> <p>Asc. over NE slope.</p>
4.00	Small wash in bottom of draw, drains NE; asc. over SE slope.
18.50	Top of spur, projects NE; desc. over NW slope.
27.70	Small wash in bottom of draw, drains NE; asc. over SE slope.
36.80	Dirt road, bears N and SW; also slope change; asc. over NE slope.
40.07	The cor. of secs. 13, 14, 23 and 24.
	<p>N. 0°05' W., bet. secs. 13 and 14. Desc. over NE slope through native grasses, shadscale and sagebrush.</p>

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
5.00	Bottom of descent, slopes NE; thence along E slope.
11.00	Spur, slopes NE; desc. over NW slope.
20.00	Bottom of descent, slopes W; thence along broken W slope.
38.00	Top of low ridge, bears E and W; desc. over gradual N slope.
39.90	<p>The $\frac{1}{4}$ sec. cor. of secs. 13 and 14, monumented with a sandstone, 20 x 14 x 5 ins., firmly set 10 ins. in the ground, mkd. $\frac{1}{4}$ on W face with a small mound of stone to W.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 10 S R 24 E</p> <p>$\frac{1}{4}$</p> <p> </p> <p>S 14 S 13</p> <p> </p> <p>1975</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>N. $0^{\circ}01'$ W., beginning new measurement.</p> <p>Desc. over gradual N slope.</p>
17.00	Bottom of draw, drains NW; asc. over SW slope.
20.00	Top of spur, slopes W; desc. over NW slope.
23.50	Bottom of descent slopes SW; thence along E slope.
31.00	Slope changes; desc. over NE slope.
40.04	<p>The cor. of secs. 11, 12, 13 and 4, monumented with a sandstone, 32 x 12 x 5 ins., firmly set 20 ins. in the ground, mkd. 4 notches on S and 1 notch on E edge with small mound of stone to W.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, $4\frac{1}{2}$ ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 10 S R 24 E</p> <p> </p> <p>S 11 S 12</p> <p>S 14 S 13</p> <p> </p> <p>1975</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>From the cor. of secs. 7, 12, 13 and 18, E. Bdy.</p> <p>S. $89^{\circ}55'$ W., bet. secs. 12 and 13.</p>

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
	Desc. over rocky ledgey SW slope through scattered native grasses, shadscale and sagebrush.
5.00	Bottom of descent, slopes S; asc. over ledgey SE slope.
9.00	N rim of Evacuation Creek Canyon, bears NE and SW; asc. over gradual SE slope.
16.25	Spur, slopes S; desc. over SW slope.
22.75	Dirt road, bears N. 45° W. and S. 45° E.
23.00	Bottom of draw, drains SE; asc. over NE slope.
29.00	Top of spur, slopes N; thence along N slope of draw.
36.50	Bottom of draw, drains NE; asc. along S slope.
40.31	The ¼ sec. cor. of secs. 12 and 13, monumented with a sandstone, 20 x 14 x 5 ins., firmly set 10 ins. in the ground, mkd. ¼ on N face with a scattered mound of stone to N.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base to top, with brass cap mkd.
	T 10 S R 24 E ¼ $\frac{S 12}{S 13}$ 1975
	Deposit the mkd. stone alongside the iron post.
	—————
	S. 89°54' W., beginning new measurement.
	Asc. over steep E slope.
5.00	Top of ridge, bears N and S; desc. over gradual W slope.
9.25	Dirt road, bears NE and SW.
27.00	Bottom of draw, drains NW; thence along N slope.
33.70	Top of spur, slopes NW; desc. over SW slope.
37.50	Dirt road, bears NW and SE in bottom of draw, draining NW; asc. over NE slope.
39.72	The cor. of secs. 11, 12, 13 and 14.
	N. 0°01' E., bet. secs. 11 and 12.
	Desc. over NE slope through scattered native grasses, shadscale and sagebrush.
1.10	Dirt road, bears NW and SE.
2.00	Small wash in bottom of draw, drains NW; asc. over S slope.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
10.00	Top of spur, projects W; desc. over NW slope.
15.00	Bottom of draw, drains W; asc. over SW slope.
20.00	Top of ridge, bears NW and E; desc. over NE slope.
33.00	Small wash in bottom of hollow, drains NW; asc. over SW slope.
39.00	Top of ascent, slopes W; desc. over NW slope.
39.94	The $\frac{1}{4}$ sec. cor. of secs. 11 and 12, monumented with a sandstone, 20 x 12 x 8 ins., firmly set 8 ins. in the ground, dimly mkd. $\frac{1}{4}$ on W face with small mound of stone to W. At the corner point Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd. <div style="text-align: center;"> <p>T 10 S R 24 E</p> <p>$\frac{1}{4}$</p> <p> </p> <p>S 11 S 12</p> <p> </p> <p>1975</p> </div> Deposit the mkd. stone alongside the iron post. <hr style="width: 20%; margin: auto;"/> N. $0^{\circ}05'$ W., beginning new measurement. Desc. over NW slope.
2.00	Bottom of draw, drains SW; asc. over SE slope.
6.00	Top of spur, slopes SW; thence along broken W slope.
17.00	Spur, slopes NW; desc. over N slope.
21.50	Small wash in bottom of hollow, drains NW; asc. over SW slope.
35.00	Spur, slopes W; desc. over NW slope.
38.00	Bottom of draw, drains SW; asc. over SE slope.
39.94	The cor. of secs. 1, 2, 11 and 12, monumented with a sandstone, 23 x 16 x 8 ins., firmly set 12 ins. in the ground, mkd. 5 notches on S and 1 notch on E edge surrounded by a mound of stone. At the corner point Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd. <div style="text-align: center;"> <p>T 10 S R 24 E</p> <p> </p> <p>S 2 S 1</p> <p>— —</p> <p>S 11 S 12</p> <p> </p> <p>1975</p> </div> Deposit the mkd. stone alongside the iron post.

245

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
	From the cor. of secs. 1, 6, 7 and 12, E. Bdy.
	S. 89°47' W., bet. secs. 1 and 12.
	Along broken ledgy S slope through scattered native grasses, shadscale and weeds.
12.30	Underground pipeline, bears N. 23° E. and S. 23° W.; slope changes; desc. over SW slope.
27.00	Small wash in bottom of draw, drains SW; desc. along S slope.
39.93	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone to top, with brass cap mkd.
	<div style="text-align: center;"> T 10 S R 24 E $\frac{1}{4}$ $\frac{S 1}{S 12}$ 1975 </div>
	Desc. over SW slope.
48.50	Enter river bottom, bears NW and SE.
51.00	White River, 3 chs. wide, flows SE.
57.00	Base of ledge, bears NW and SE; asc. over perpendicular ledge.
61.50	Rim of ledge, bears NW and SE; desc. along gradual S slope.
68.00	Slope changes; desc. over SW slope.
73.00	Dirt road, bears NW and SE; also bottom of descent; asc. over NE slope.
75.00	Top of spur, slopes N; desc. over W slope.
79.50	Bottom of draw, drains SW; asc. over SE slope.
79.86	The cor. of secs. 1, 2, 11 and 12.
	N. 0°03' E., bet. secs. 1 and 2.
	Asc. over SE slope through scattered native grasses and shadscale.
4.00	Top of spur, slopes E; desc. over N slope.
10.00	Bottom of draw, drains SW; asc. over SE slope.
16.00	Saddle on ridge, bears NE and SW; desc. over NW slope.
19.00	Dirt road, bears NW and SE.
32.00	S rim of White River Canyon, bears NW and SE; desc. over NE slope.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS
37.03

Point selected for a witness point.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

W P
T 10 S R 24 E

S 2 | S 1

1975

from which

Cor. No. 3, Allotment Nos. 19 and 266, War-Atze, monumented with a sandstone, 20 x 8 x 8 ins., above ground, dimly mkd. bears N. 85°33' W., 1.576 chs. dist.

Bury a cottonwood post, 5 ft. long, projecting 3 ft. above ground, alongside the iron post.

37.77

The original witness ¼ sec. cor. of secs. 1 and 2, determined from a tie of record bearing and distance to Cor. No. 3 of Allotment No. 19 and No. 266, War-Atze and the remains of the original bearing tree

Cor. No. 3, Allotment No. 19 and No. 266, War-Atze, heretofore described, bears S. 68°30' W., 1.68 chs. dist.

A stump hole, bears N. 82½° W., 69 lks. dist.
(Record, N. 82° W.)

Corner falls near edge of river bottom and is unsafe to monument an iron post.

N. 0°15' E., beginning new measurement.

Along river bottom land.

1.00

White River, 3 chs. wide, flows W.

1.88

True point for the ¼ sec. cor. of secs. 1 and 2 at proportionate distance, falls in White River, 3 chs. wide, and cannot be monumented.

6.35

Intersect line 3-4, Allotment No. 19 and No. 266, War-Atze, at a point from which

Cor. No. 3, Allotment No. 19 and No. 266, heretofore described, bears S. 12°52' W., 7.14 chs. dist.

Point for Cor. No. 4, Allotment No. 19 and No. 266, War-Atze, bears N. 12°52' E., 9.84 chs. dist. hereinafter described.


Cors. No. 1, 2, and 4, Allotment No. 19 and No. 266 War-Atze were searched for and not found; therefore the allotment was established according to the original survey

Cor. No. 2 was not monumented.

At point for cor. No. 4

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with a cottonwood stake, projecting 2 ft. above ground, alongside iron post, with brass cap mkd. T10S R24E S1 Cor 4 WAR ATZE 1975.
16.20	Dirt road, bears NW and SE.
16.41	Intersect line 4-1, Allotment No. 19 and No. 266, War-Atze, at a point from which Cor. No. 4, heretofore described, bears S. 77°37' E., 2.20 chs. dist. Point for Cor. No. 1, Allotment No. 19 and No. 266, War-Atze, bears N. 77°37' W., 21.78 chs. dist.
	Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd. T10S R24E S2 Cor 1 War Atze 1975.
20.00	Leave river bottom; base of ascent, bears NW and SE; asc. over SW slope.
23.00	Slope changes; asc. over steep S slope.
30.00	Top of spur, slopes E; desc. over N slope.
36.00	Bottom of draw, drains NE; asc. over SE slope.
41.73	The cor. of secs. 1, 2, 35 and 36, on the N. Bdy., heretofore described.
	From the stan. cor. of secs. 34 and 35, S. Bdy. N. 0°03' E., bet. secs. 34 and 35. Asc. over SE slope through pinon, juniper, scattered shadscale and native grasses.
3.50	Top of ridge, bears E and W; desc. over NE slope.
16.00	Bottom of draw, drains N. 10° W.; thence along W slope.
24.00	Slope changes; asc. over SW slope.
27.00	Top of spur, slopes W; desc. over NW slope.
39.50	Point selected for the witness ¼ sec. cor. of secs. 34 and 35. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
40.15	True point for the ¼ sec. cor. of secs. 34 and 35, at proportionate dist., falls in dirt road, which bears NW and SE; also bottom of draw, drains NW; there is no remaining evidence of the original cor.



Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS					
52.00	Bottom of draw, drains SW; asc. over S slope.				
56.20	Top of spur, slopes W; desc. over NW slope.				
61.00	Bottom of draw, drains SW; asc. over SW slope.				
64.00	Top of spur, slopes SW; thence along steep W slope.				
71.50	Top of narrow ridge, bears NW and SE; desc. over rocky NE slope.				
80.00	Head of draw, drains NE; asc. over SE slope.				
80.30	The cor. of secs. 26, 27, 34 and 35, monumented with a sandstone, 20 x 10 x 5 ins., firmly set 10 ins. in the ground, mkd. 1 notch on S and 2 notches on E edge, from which the original bearing trees				
	<p style="margin-left: 40px;">A cedar, 10 ins. diam., bears S. 56° E., 23 lks. dist., mkd. T10S R24E S35 BT.</p>				
	<p style="margin-left: 40px;">A dead cedar, 6 ins. diam., bears N. 59° W., 57 lks. dist., mkd. T10S R24E S27 BT. (Record, 56 lks.)</p>				
	At the corner point				
	Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base to top, with brass cap mkd.				
	T 10 S R 24 E				
	<table border="1" style="margin: auto;"> <tr> <td style="padding: 2px;">S 27</td> <td style="padding: 2px;">S 26</td> </tr> <tr> <td style="padding: 2px;">S 34</td> <td style="padding: 2px;">S 35</td> </tr> </table>	S 27	S 26	S 34	S 35
S 27	S 26				
S 34	S 35				
	1975				
	Deposit the mkd. stone alongside the iron post.				
	From the cor. of secs. 25, 26, 35 and 36.				
	S. 89°58' W., bet. secs. 26 and 35.				
	Asc. over SE slope through scattered native grasses and shadscale.				
3.50	Top of spur, projects NE; desc. over NW slope.				
11.00	Bottom of draw, drains N; asc. over NE slope.				
19.00	Top of spur, projects NE; desc. over NW slope.				
24.50	Bottom of draw, drains NE; asc. over SE slope.				
31.50	Top of spur, slopes NE; thence along gradual N slope.				
39.86	The ¼ sec. cor. of secs. 26 and 35, monumented with a sandstone, 16 x 6 x 3 ins., firmly set 8 ins. in the ground, mkd. ¼ on N face.				
	At the corner point				
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone to top, with brass cap mkd.				

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
	T 10 S R 24 E $\frac{1}{4}$ $\frac{S 26}{S 35}$ 1975
	Deposit the mkd. stone alongside the iron post.
	—————
	West, beginning new measurement.
	Along broken N slope.
9.70	Dirt road, bears N and S; slope changes; asc. over NE slope.
21.50	Top of spur, slopes NE; thence along N slope; enter scattered juniper and pinon timber.
27.00	Slope changes; asc. over NE slope.
34.00	Top of spur, slopes NE; desc. over NW slope.
40.00	Head of draw, drains NE; asc. over SE slope.
40.30	The cor. of secs. 26, 27, 34 and 35.
	—————
	N. 0°17' W., bet. secs. 26 and 27.
	Asc. over SE slope through scattered juniper, pinon, shadscale and native grasses.
11.00	S rim of ridge, bears NE and SW; thence along ridge top.
25.00	Begin descent over NE slope.
32.00	Slope changes; thence along rocky E slope.
39.47	The $\frac{1}{4}$ sec. cor. of secs. 26 and 27, monumented with a sandstone, 20 x 12 x 6 ins., firmly set 10 ins. in the ground, mkd. $\frac{1}{4}$ on W face, from which the original bearing trees
	A cedar, 6 ins. diam., bears S. 58° E., 38 lks. dist., mkd. $\frac{1}{4}$ S BT. (Record, N. 58° E., 27 lks.)
	A cedar, 6 ins. diam., bears N. 74° W., 62 lks. dist., mkd. $\frac{1}{4}$ S BT. (Record, 60 lks.)
	At the corner point
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T 10 S R 24 E $\frac{1}{4}$ S 27 S 26 1975
	Deposit the mkd. stone alongside the iron post.
	—————
	N. 0°01' E., beginning new measurement.
	Along steep, rocky E slope.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS					
6.50	Small wash in bottom of hollow, drains W; asc. over steep SW slope.				
11.00	Top of ridge, bears W and SE; desc. over gradual N slope.				
19.50	Spur, projects N. 20° E.; desc. along steep W slope.				
30.50	Spur, slopes W; desc. over NW slope.				
35.00	Slope changes; desc. over NE slope.				
40.34	<p>The cor. of secs. 22, 23, 26 and 27, monumented with a sandstone, 18 x 8 x 6 ins., firmly set 9 ins. in the ground, mkd. 2 notches on the S and E edge, from which the original bearing trees</p> <p>A cedar, 8 ins. diam., bears N. 88° E., 30½ lks. dist., mkd. T10S R24E S23 BT.</p> <p>A cedar, 6 ins. diam., bears S. 27°30' E., 26 lks. dist., mkd. T10S R24E S26 BT. (Record, 36 lks.)</p> <p>A cedar, 6 ins. diam., bears S. 36° W., 41½ lks. dist., mkd. T10S R24E S27 BT. (Record, 48 lks.)</p> <p>A cedar, 4 ins. diam., bears N. 45° W., 80 lks. dist., mkd. T10S R24E S22 BT.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 10 S R 24 E</p> <table border="1" style="margin: auto;"> <tr> <td style="padding: 2px;">S 22</td> <td style="padding: 2px;">S 23</td> </tr> <tr> <td style="padding: 2px;">S 27</td> <td style="padding: 2px;">S 26</td> </tr> </table> <p>1975</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p>	S 22	S 23	S 27	S 26
S 22	S 23				
S 27	S 26				
	<p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S. 89°59' W., bet. secs. 23 and 26.</p> <p>Desc. over NW slope through scattered shadscale, sagebrush and native grasses.</p>				
3.25	Small wash in bottom of hollow, drains NE; asc. along N slope.				
14.50	Slope changes; asc. over NE slope; enter scattered juniper and pinon timber.				
25.00	Dirt road, bears N. 20° E. and S. 20° W.				
40.04	<p>The ¼ sec. cor. of secs. 23 and 26, monumented with a sandstone, 18 x 12 x 4 ins., firmly set 10 ins. in the ground, mkd. ¼ on N face, from which the original bearing trees</p> <p>A cedar, 7 ins. diam., bears N. 64° E., 74 lks. dist., mkd. ¼ S BT.</p> <p>A cedar, 18 ins. diam., bears S. 49° W., 57½ lks. dist., mkd. ¼ S BT.</p>				

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone to top, with brass cap mkd.</p> <p style="text-align: center;">T 10 S R 24 E $\frac{1}{4}$ $\frac{S\ 23}{S\ 26}$ 1975</p> <p>Deposit the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 89°55' W., beginning new measurement.</p> <p>Asc. over NE slope through scattered juniper and pinon timber.</p>
15.50	Top of ridge, bears N and S; desc. over NW slope.
28.00	Small wash in bottom of hollow, drains NE; asc. over NE slope.
34.00	Top of spur, projects N; desc. over NW slope.
38.00	Bottom of draw, drains N; asc. over NE slope.
39.98	The cor. of secs. 22, 23, 26 and 27.
	<p>North, bet. secs. 22 and 23.</p> <p>Desc. over NE slope through scattered juniper and pinon, shadscale and native grasses.</p>
8.50	Small wash in bottom of hollow, drains W; asc. over SW slope.
13.50	Top of narrow ridge, bears NW and SE; desc. over NE slope.
27.00	Bottom of draw, drains NW; asc. over broken SW slope.
37.50	Top of spur, slopes NW; desc. over NW slope.
40.08	<p>The ¼ sec. cor. of secs. 22 and 23, monumented with a sandstone, 20 x 14 x 5 ins., firmly set 10 ins. in the ground, mkd. ¼ on W face, from which the original bearing trees</p> <p style="padding-left: 40px;">A juniper, 9 ins. diam., bears N. 59° E., 48 lks. dist., mkd. ¼ S BT. (Record, 46 lks.)</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears N. 20½° W., 25 lks. dist., mkd. ¼ S BT.</p>
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
	<p style="text-align: center;">T 10 S R 24 E $\frac{1}{4}$ S 22 S 23 1975</p> <p>Deposit the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°04' W., beginning new measurement.</p> <p>Desc. over NW slope through scattered juniper, pinon and sagebrush.</p> <p>9.50 Bottom of draw, drains W; leave timber; asc. over SW slope.</p> <p>20.00 Top of spur, slopes SW; thence along rocky W slope.</p> <p>25.00 Base of sandstone ledges, bears NW and SE; asc. over SW slope and perpendicular ledges.</p> <p>29.50 Top of sandstone ridge, bears NW and SE; desc. over steep rocky NE slope.</p> <p>35.00 Head of draw, drains NE; desc. over gentle N slope.</p> <p>40.11 The cor. of secs. 14, 15, 22 and 23, monumented with a sandstone, 16 x 10 x 6 ins., firmly set 8 ins. in the ground, mkd. 3 notches on S and 2 notches on E edge.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T 10 S R 24 E S 15 S 14 S 22 S 23 1975</p> <p>Deposit the mkd. stone alongside the iron post.</p>
	<p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>S. 89°56' W., bet. secs. 14 and 23.</p> <p>Asc. over NE slope through scattered native grasses and shadscale.</p> <p>4.00 Top of spur, projects NE; desc. over SW slope.</p> <p>14.50 Bottom of draw, drains NW; asc. over NE slope.</p> <p>23.50 Top of spur, slopes N; desc. over W slope.</p> <p>27.75 Small wash in bottom of draw, drains N; asc. over NE slope.</p> <p>33.00 Bottom of draw, drains NE; asc. abruptly over E slope.</p>

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

<p>CHAINS 40.01</p>	<p>The $\frac{1}{4}$ sec. cor. of secs. 14 and 23, monumented with a sandstone, 24 x 12 x 7 ins., firmly set in a small mound of stone, dimly mkd. $\frac{1}{4}$ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, $4\frac{1}{2}$ ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 10 S R 24 E</p> <p>$\frac{1}{4}$ <u>S 14</u></p> <p>S 23</p> <p>1975</p> </div> <p>Deposit the dimly mkd. stone alongside the iron post.</p> <p>Corner is set on ledge, 15 ft. below top of spur.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. $89^{\circ}58'$ W., beginning new measurement.</p> <p>Asc. abruptly over perpendicular ledge.</p>
<p>0.50</p> <p>16.75</p> <p>23.00</p> <p>28.25</p> <p>36.50</p> <p>38.50</p> <p>40.25</p>	<p>Top of spur, projects NE; desc. along rocky N slope.</p> <p>Slope changes; desc. over W slope.</p> <p>Wash in bottom of hollow, drains NW.</p> <p>Dirt road, bears N. 25° W. and S. 25° E.; asc. over NE slope.</p> <p>Top of spur, slopes NE; desc. along gradual N slope.</p> <p>Draw, drains N; asc. over N slope.</p> <p>The cor. of secs. 14, 15, 22 and 23.</p>
<p>2.50</p> <p>5.00</p> <p>14.00</p> <p>18.50</p> <p>26.00</p> <p>28.50</p> <p>35.75</p> <p>40.07</p>	<p>N. $0^{\circ}08'$ E., bet. secs. 14 and 15.</p> <p>Desc. over NW slope through scattered shadscale, sagebrush and native grasses.</p> <p>Bottom of draw, drains NE; asc. over SE slope.</p> <p>Top of spur, projects NE; desc. over NW slope.</p> <p>Slope changes; desc. over N slope.</p> <p>Bottom of draw, drains NE; asc. over SE slope.</p> <p>Slope changes; desc. over NE slope.</p> <p>Bottom of draw, drains NW; asc. over SW slope.</p> <p>Top of spur, slopes W; desc. over N slope.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 14 and 15, monumented with a sandstone, 28 x 10 x 4 ins., firmly set 14 ins. in the ground, mkd. $\frac{1}{4}$ on the W face with scattered mound of stone to W.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, $4\frac{1}{2}$ ft. base to top, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
	<p style="text-align: center;">T 10 S R 24 E</p> <p style="text-align: center;"> $\frac{1}{4}$ S 15 S 14 1975 </p> <p>Deposit the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°05' E., beginning new measurement.</p> <p>Desc. over N slope.</p> <p>1.50 Slope changes; desc. over NW slope of draw.</p> <p>13.00 Base of steep descent, bears E and W; desc. over gradual N slope into river bottom.</p> <p>24.00 Enter river, bottom, bears NE and SW; thence over bottom-land.</p> <p>28.00 White River, 3 chs. wide, flows SW.</p> <p>40.04 Point for the cor. of secs. 10, 11, 14 and 15, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 10 S R 24 E</p> <p style="text-align: center;"> S 10 S 11 S 15 S 14 1975 </p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <p>Corner is located at base of talus slope and about 1 ch. S of base of ledge, 50 ft. high.</p>
	<p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>N. 89°55' W., bet. secs. 11 and 14.</p> <p>Asc. over gentle NE slope through scattered shadscale, sagebrush and native grasses.</p> <p>5.50 Top of spur, slopes N; desc. over NW slope.</p> <p>8.75 Bottom of draw, drains N; asc. over NE slope.</p> <p>15.00 Top of spur, slopes N; desc. over W slope.</p> <p>25.00 Bottom of draw, drains SW; thence along S slope.</p> <p>32.00 Point of spur, slopes SW; desc. over W slope.</p> <p>37.25 Small wash in bottom of draw, drains NW; thence along gentle N slope.</p>

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
<p>40.19</p>	<p>The $\frac{1}{4}$ sec. cor. of secs. 11 and 14, monumented with a sandstone, 28 x 12 x 5 ins., firmly set 12 ins. in the ground, mkd. $\frac{1}{4}$ on N face, surrounded by a scattered mound of stone.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 10 S R 24 E</p> <p> S 11</p> <p>$\frac{1}{4}$ ——— S 14</p> <p> 1975</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N of cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. $89^{\circ}55'$ W., beginning new measurement.</p> <p>Along gentle N slope.</p>
<p>12.00</p> <p>20.50</p> <p>29.50</p> <p>40.05</p>	<p>Dirt road, bears N. 45° E. and S.; enter river bottom land.</p> <p>Small wash, drains NW.</p> <p>White River, 3 chs. wide, flows SW.</p> <p>The cor. of secs. 10, 11, 14 and 15.</p> <hr/> <p>N. $0^{\circ}21'$ E., bet. secs. 10 and 11.</p> <p>Asc. over rocky S slope.</p> <p>2.30 Top of rocky spur, slopes SW; desc. over NW slope.</p> <p>9.50 Small wash, drains SW; asc. over SE slope.</p> <p>18.50 Top of spur, slopes SW; thence along gentle W slope.</p> <p>34.00 Bottom of draw, drains SW; asc. over SE slope.</p> <p>39.80 Top of spur, slopes W; desc. over NW slope.</p> <p>40.04 Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 10 S R 24 E</p> <p> $\frac{1}{4}$</p> <p> </p> <p> S 10 S 11</p> <p> </p> <p> 1975</p> </div> <p>Desc. over rocky NW slope.</p>

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
47.00	Slope changes; thence along W slope.
55.00	Wash in bottom of draw, drains SW; asc. over S slope.
70.00	Top of spur, slopes SW; thence along W slope.
79.10	Slope changes; asc. over SW slope.
80.08	The cor. of secs. 2, 3, 10 and 11, monumented with a sandstone, 15 x 9 x 5 ins., set in a scattered mound of stone, dimly mkd. 5 notches on S and 1 notch on E edge.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T 10 S R 24 E S 3 S 2 S 10 S 11 1975
	Deposit the mkd. stone alongside the iron post.
	From the cor. of secs. 1, 2, 11 and 12.
	N. 89°48' W., bet. secs. 2 and 11.
	Asc. over SE slope through scattered native grasses and shadscale.
2.50	Top of spur, slopes SW; desc. over NW slope.
11.00	Bottom of draw, drains SW; thence along S slope.
19.00	Enter river bottom land.
25.00	Small wash, drains NW.
36.00	White River, 3 chs. wide, flows irregularly S.
39.85	True Point for the ¼ sec. cor. of secs. 2 and 11, at proportionate dist., falls near river bank and is unsafe to monument; there is no remaining evidence of the original cor.; leave river bottom land; asc. over E slope.
40.16	Point selected for the witness ¼ sec. cor. of secs. 2 and 11.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	W C T 10 S R 24 E S 2 ¼ — S 11 —> 1975
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.
	Asc. steep rocky E slope.
47.50	Rim of steep ascent, bears N and S; thence along gentle S slope of ridge top.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
55.00	Slope changes; desc. over broken SW slope.
73.00	Spur, slopes S; desc. over gradual SW slope.
79.70	The cor. of secs. 2, 3, 10 and 11.
N. 0°26' E., bet. secs. 2 and 3.	
Asc. over SW slope through scattered native grasses and shadscale.	
9.00	Top of high spur, projects SE; thence along broken E slope.
12.00	Spur, slopes E; desc. over broken NE slope.
16.50	Bottom of draw, drains E; along steep broken E slope.
28.00	Bottom of draw, drains SE; asc. over SE slope.
36.25	Top of high spur, slopes E; desc. over NE slope.
39.00	Slope changes; along E slope.
39.48	The ¼ sec. cor. of secs. 2 and 3, monumented with a sandstone, 16 x 10 x 5 ins., firmly set 8 ins. in the ground, dimly mkd. ¼ on W face and a scattered mound of stone to W.
At the corner point	
Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.	
<p style="text-align: center;">T 10 S R 24 E</p> <p style="text-align: center;"> </p> <p style="text-align: center;"> ¼</p> <p style="text-align: center;"> </p> <p style="text-align: center;"> S 3 S 2</p> <p style="text-align: center;"> </p> <p style="text-align: center;"> 1975</p>	
Deposit the mkd. stone alongside the iron post.	
Corner is set on E slope, 20 ft. below top of spur, sloping NE.	
<p style="text-align: center;">—————</p>	
N. 0°05' W., beginning new measurement.	
Asc. over gentle SE slope.	
1.00	Spur, slopes NE; desc. over NE slope.
5.00	Bottom of draw, drains NE; asc. along E slope.
14.50	Top of spur, slopes NE; desc. over N slope.
18.75	Bottom of draw, drains E; asc. over SE slope.
22.00	Top of spur, slopes E; desc. over NE slope.
26.00	Bottom of draw, drains E; asc. over steep SE slope.
35.50	Top of ridge, bears NE and SW; desc. over NW slope.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
39.50	Head of small draw, drains NW; asc. over SW slope.
39.86	The cor. of secs. 2, 3, 34 and 35, on the N. Bdy., heretofore described.
	From the stan. cor. of secs. 33 and 34, S. Bdy., heretofore described.
	N. 0°01' E., bet. secs. 33 and 34.
	Desc. over NE slope through scattered juniper, pinon, native grasses and shadscale.
9.50	Wash, 20 lks. wide, 3 ft. deep, drains NE; asc. over SE slope.
24.00	Top of high spur, projects NE; desc. over NE slope.
34.00	Wash, 25 lks. wide, 2 ft. deep, drains NE; asc. along E slope.
39.75	The $\frac{1}{4}$ sec. cor. of secs. 33 and 34, monumented with a sandstone, 20 x 10 x 5 ins., firmly set 10 ins. in the ground, mkd. $\frac{1}{4}$ on W face, from which the original bearing trees
	A cedar, 10 ins. diam., bears S. 81° E., 43 $\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S34 BT. (Record, 43 lks.)
	A cedar, 10 ins. diam., bears S. 85° W., 58 lks. dist., mkd. $\frac{1}{4}$ S33 BT. (Record, 57 lks.)
	At the corner point
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone to top with brass cap mkd.
	T 10 S R 24 E $\frac{1}{4}$ S 33 S 34 1975
	Deposit the mkd. stone alongside the iron post.
	N. 0°36' E., beginning new measurement.
	Asc. along E slope through thick juniper and pinon timber.
6.00	Bottom of draw, drains NE; asc. over SE slope.
15.75	Point of high spur, slopes NE; desc. over NW slope.
22.00	Base of main descent, bears NE and SW; desc. over gradual NW slope.
34.00	Slope changes; desc. over gentle N slope.
40.15	The cor. of secs. 27, 28, 33, and 34, monumented with a sandstone, 18 x 10 x 10 ins., firmly set 6 ins. in the ground, plainly mkd. 1 notch on S and 3 notches on E edges, surrounded by a mound of stone, from which the original bearing trees

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS

A cedar, 10 ins. diam., bears N. $13\frac{1}{2}^\circ$ E., 122 $\frac{1}{2}$ lks. dist., mkd. T10S R24E S27 BT. (Record, 121 lks.)

A cedar, 5 ins. diam., bears S. 65° E., 142 lks. dist., mkd. T10S R24E S34 BT. (Record, 141 lks.)

A cedar, 4 ins. diam., bears S. $12\frac{1}{2}^\circ$ W., 38 $\frac{1}{2}$ lks. dist., mkd. T10S R24E S33 BT.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 18 ins. in the ground to bedrock, in a collar of stone to top, with brass cap mkd.

T 10 S R 24 E

S 28	S 27
S 33	S 34

1975

Deposit the mkd. stone alongside the iron post.

Corner is located on E edge of small wash, 3 ft. deep, 10 lks. wide, drains N.

From the cor. of secs. 26, 27, 34 and 35.

S. $89^\circ 44'$ W., bet. secs. 27 and 34.

Asc. over E slope through scattered juniper, pinon, native grasses and shadscale.

- 6.00 Top of narrow ridge, bears NW and SE; desc. over SW slope.
- 11.00 Slope changes; desc. along S slope.
- 32.00 Bottom of draw, drains S; asc. over SE slope.
- 36.25 Top of spur, slopes S; desc. over SW slope.
- 39.80 Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 27 and 34.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 $\frac{1}{2}$ ft. base to top, with brass cap mkd.

W C
T 10 S R 24 E

$\frac{1}{4}$ ←	S 27
	S 34

1975

- 39.98 Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 34, at proportionate distance, falls in bottom of gully, 15 lks. wide, draining S., where it is impracticable to establish a permanent monument; there is no remaining evidence of the original cor.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
4.00	Bottom of draw, drains NE; thence along E slope.
8.00	Slope changes; desc. over NE slope.
13.50	Bottom of draw, drains NE; asc. over SE slope.
19.00	Top of spur, slopes NE; desc. over N slope.
27.00	Wash, 20 lks. wide, 6 ins. deep, drains NW; asc. over SW slope.
35.00	Top of ascent, slopes W; desc. over NW slope.
40.00	The cor. of secs. 21, 22, 27 and 28, monumented with a Sandstone, 26 x 14 x 4 ins., firmly set 13 ins. in the ground, mkd. 2 notches on S and 3 notches on E edge, with small mound of stone to W, from which the original bearing trees
	A stump hole, bears N. 82° E., 53 lks. dist., a cedar, dead and lying down, alongside, 14 ins. diam., with scribe marks T10S R24E S22 BT. (Record, 55 lks.)
	A cedar, 6 ins. diam., bears S. 57° E., 30 lks. dist., mkd. T10S R24E S27 BT. (Record, 28 lks.)
	A cedar, 7 ins. diam., bears S. 78° W., 34½ lks. dist., mkd. T10S R24E S28 BT.
	A cedar, 7 ins. diam., bears N. 51° W., 44 lks. dist., mkd. T10S R24E S21 BT. (Record, 42 lks.)
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 10 S R 24 E S 21 S 22 S 28 S 27 1975
	Deposit the mkd. stone alongside the iron post.
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.
	From the cor. of secs. 22, 23, 26 and 27.
	S. 89°59' W., bet. secs. 22 and 27.
	Asc. over NE slope through scattered juniper, pinon, shadscale and native grasses.
4.50	Top of spur, slopes NW; desc. over SW slope.
10.00	Bottom of draw, drains NW; asc. over NE slope.
15.00	Top of spur, slopes NW; desc. over SW slope.
19.00	Bottom of draw, drains NW; asc. along N slope.
26.00	Slope changes; asc. over NE slope.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
29.00	Top of spur, slopes N; desc. over NW slope.
33.50	Slope changes; desc. over W slope.
39.85	<p>The $\frac{1}{4}$ sec. cor. of secs. 22 and 27, monumented with a sandstone, 20 x 8 x 6 ins., firmly set 10 ins. in the ground, mkd. $\frac{1}{4}$ on N face with small mound of stone to N, from which the original bearing trees</p> <p style="padding-left: 40px;">A cedar, 10 ins. diam., bears S. 69° W., 51 lks. dist., mkd. $\frac{1}{4}$ S26 BT. (Record, S27, 45 lks.)</p> <p style="padding-left: 40px;">A cedar, 8 ins. diam., bears N. 79° W., 27 lks. dist., mkd. $\frac{1}{4}$ S22 BT.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>T 10 S R 24 E</p> <p>$\frac{1}{4}$ $\frac{S 22}{S 27}$</p> <p>1975</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Corner is located in bottom of draw, on E edge of small wash, draining N.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°59' W., beginning new measurement.</p> <p>Asc. over NE slope.</p>
11.00	Top of spur, slopes N; desc. over NW slope.
17.00	Bottom of draw, drains NW; thence along N slope.
21.00	Bottom of small draw, drains NE; asc. over E slope.
25.00	Top of ridge, bears N and S; desc. over broken NW slope.
39.99	The cor. of secs. 21, 22, 27 and 28.
2.00	<p>N. 0°03' W., bet. secs. 21 and 22.</p> <p>Desc. over NW slope through scattered juniper, pinon, shadscale and native grasses.</p>
10.00	Bottom of draw, drains SW; asc. over S slope.
17.00	Base of high ridge, bears NE and SW; asc. over SE slope and perpendicular ledge.
23.75	Top of ridge, bears E and SW; desc. over steep N slope.
32.00	Small wash in bottom of draw, drains W; asc. over steep SW slope.
35.00	Top of high spur, slopes NW; desc. over steep N slope.
39.80	Slope changes; desc. over NW slope.
39.80	Bottom of draw, drains W; asc. over SW slope.
39.92	The $\frac{1}{4}$ sec. cor. of secs. 21 and 22, monumented with a

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
	<p>sandstone, 24 x 12 x 8 ins., firmly set 12 ins. in the ground, mkd. ¼ on W face, from which the original bearing trees</p> <p>A cedar, 8 ins. diam., bears S. 81° E., 81 lks. dist., mkd. ¼ S22 BT.</p> <p>A cedar, 7 ins. diam., bears N. 28° W., 36 lks. dist., mkd. ¼ S21 BT.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 10 S R 24 E</p> <p>¼</p> <p> </p> <p>S 21 S 22</p> <p> </p> <p>1975</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°13' W., beginning new measurement.</p> <p>Asc. over steep SW slope.</p> <p>4.00 Top of spur, slopes SW; desc. over NW slope.</p> <p>6.00 Bottom of draw, drains W; thence along W slope.</p> <p>7.00 Spur, slopes NW; desc. over steep NE slope.</p> <p>17.00 Bottom of draw, drains NE; thence along steep E slope.</p> <p>20.50 Spur, slopes NE; desc. over steep N slope.</p> <p>27.00 Base of steep descent, bears E and W; desc. over gradual N slope of river bottom land.</p> <p>39.99 Point for the cor. of secs. 15, 16, 21 and 22, at proportionate distance, falls near rivers edge; there is no remaining evidence of the original corner.</p> <p>True cor. point not remonumented due to danger of spring flooding conditions. Witness cor. hereinafter described.</p>
	<p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>S. 89°53' W., bet. secs. 15 and 22.</p> <p>Along gentle N slope through scattered juniper, pinon, sagebrush, shadscale and native grasses.</p> <p>3.50 Bottom of draw, drains NE; asc. over E slope.</p> <p>8.00 Top of spur, slopes NE; desc. over NW slope.</p> <p>11.00 Bottom of draw, drains N; asc. over NE slope.</p> <p>14.50 Top of ridge, bears NW and SE; desc. over SW slope.</p> <p>17.00 Bottom of draw, drains S; thence along steep S slope.</p> <p>19.00 Spur, slopes SW; desc. over steep W slope.</p>

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
27.00	Head of draw, drains S. 80° W.; thence along gentle S slope.
35.50	Tip of spur, slopes S; desc. over gentle SW slope.
39.00	Wash, 25 lks. wide, 6 ins. deep, drains N; asc. over NE slope.
39.89	The ¼ sec. cor. of secs. 15 and 22, monumented with a sandstone, 24 x 8 x 6 ins., firmly set 12 ins. in the ground, mkd. ¼ on N face, with small mound of stone to N.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{r} T\ 10\ S\ R\ 24\ E \\ \quad S\ 15 \\ \frac{1}{4} \quad \frac{S\ 22}{1975} \end{array}$
	Deposit the mkd. stone alongside the iron post.
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.
	S. 89°42' W., beginning new measurement.
	Asc. over NE slope through scattered shadscale and native grasses.
4.75	Base of spur, bears NW and SE; asc. over NE slope.
7.00	Top of spur, slopes N; desc. over NW slope.
10.00	Bottom of draw, drains N; asc. over NE slope.
13.00	Top of sandstone ridge, bears N and S; desc. over steep NW slope.
24.00	Base of steep descent, bears N and S; enter river bottom land with thick sagebrush, tamarack and rabbit brush.
35.92	Point selected for the witness cor. of secs. 15, 16, 21 and 22.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} W\ C \\ T\ 10\ S\ R\ 24\ E \\ \quad \\ \leftarrow S\ 16 \quad \quad S\ 15 \\ \quad S\ 21 \quad \quad S\ 22 \\ \quad \\ 1975 \end{array}$
	Set a cottonwood post, 5 ft. long, projecting 3 ft. above ground, alongside the iron post.
40.04	True point for the cor. of secs. 15, 16, 21 and 22.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS		
	N. 0°03' E., bet. secs. 15 and 16.	
	Over river bottom land through scattered cottonwoods, tamarack, sagebrush and native grasses.	
3.00	White River, 3 chs. wide, flows SW.	
7.00	Base of spur, bears NE and SW; leave river bottom land; asc. over SE slope.	
12.50	Top of spur, slopes E; desc. over NE slope.	
17.50	Base of descent, bears NW and SE; enter river bottom land.	
38.50	White River, 3 chs. wide, flows SE.	
39.99	Point for the ¼ sec. cor. of secs. 15 and 16, on the eroding left bank of river, at proportionate distance; there is no remaining evidence of the original corner.	
	True cor. point not remonumented due to danger of destruction by further erosion of river bank.	
42.43	Point selected for the witness ¼ sec. cor. of secs. 15 and 16.	
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.	
	<div style="text-align: center;"> <p>W C</p> <p>T 10 S R 24 E</p> <p>¼</p> <p> </p> <p>S 16 S 15</p> <p>↓</p> <p>1975</p> </div>	
	Set a cottonwood post, 5 ft. long, projecting 3 ft. above ground, alongside the iron post.	
44.00	Base of ascent, bears NW and SE; leave river bottom land; asc. over SW slope.	
71.00	Top of ascent, slopes W; desc. over gradual NW slope.	
79.98	The cor. of secs. 9, 10, 15 and 16, monumented with a sandstone, 20 x 10 x 4 ins., firmly set 10 ins. in the ground, mkd. 3 notches on the S and E edge, with a scattered mound of stone to W.	
	At the corner point	
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone to top, with brass cap mkd.	
	<div style="text-align: center;"> <p>T 10 S R 24 E</p> <p> </p> <p>S 9 S 10</p> <p>S 16 S 15</p> <p> </p> <p>1975</p> </div>	
	Deposit the mkd. stone alongside the iron post.	

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
	From the cor. of secs. 10, 11, 14 and 15.
	S. 89°50' W., bet. secs. 10 and 15.
	Asc. over rocky SE slope.
4.50	Top of spur, slopes SW; desc. along S slope.
6.50	Bottom of draw, drains SW.
8.50	Spur, slopes S; desc. over SW slope.
12.00	Bottom of draw, drains S; asc. over SE slope.
15.50	Top of spur, slopes S; desc. over SW slope.
22.50	Slope changes; desc. along S slope.
36.17	Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 10 and 15.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, $4\frac{1}{2}$ ft. base to top, with brass cap mkd.
	W C T 10 S R 24 E $\frac{1}{4}$ ← $\frac{S 10}{S 15}$ 1975
	Corner is located on ledge, 15 ft. high, on right bank of White River.
	Desc. over ledgy SW slope.
39.97	True point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 15, at proportionate distance, falls in White River, 3 chs. wide, flowing NW, and cannot be monumented; there is no remaining evidence of the original corner.
	Over river bottom land.
53.00	Base of steep ledgy slope, bears NW and SE; leave river bottom land; asc. over perpendicular ledges and NE slope.
56.00	Top of ascent, bears NW and SE; thence along N slope.
72.70	Spur, slopes SW; desc. over W slope.
75.50	Base of main descent, bears N and S; desc. over gradual W slope.
79.94	The cor. of secs. 9, 10, 15 and 16.
	N. 0°25' E., bet. secs. 9 and 10.
	Desc. over NW slope through scattered shadscale and native grasses.
16.50	Slope changes; desc. over gradual N slope.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
37.30	Bottom of descent, bears E and W; enter river bottom land with thick tamarack and young cottonwood timber.
39.71	Point for the ¼ sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> <p>T 10 S R 24 E</p> <p> </p> <p> ¼</p> <p> </p> <p> S 9 S 10</p> <p> </p> <p> 1975</p> </div>
	Set a cedar post, 5 ft. long, projecting 3 ft. above ground, alongside the iron post.
	Continue over river bottom land.
46.70	White River, 3 chs. wide, flows W.
48.20	Base of ledge, bears E and W; leave river bottom land; asc. over perpendicular ledge.
51.20	Rim of ledge, bears E and W; asc. over gradual SE slope.
62.70	Rim of sandstone ledge, bears NE and SW; asc. over S slope.
68.70	Top of spur, slopes W; desc. over NW slope.
79.42	The cor. of secs. 3, 4, 9 and 10, monumented with a sandstone, 18 x 10 x 6 ins., firmly set 10 ins. in the ground, mkd. 5 notches on S and 3 notches on E edge, with mound of stone to W.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> <p>T 10 S R 24 E</p> <p> </p> <p> S 4 S 3</p> <p> S 9 S 10</p> <p> </p> <p> 1975</p> </div>
	Deposit the mkd. stone alongside the iron post.
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of corner.
	From the cor. of secs. 2, 3, 10 and 11.
	S. 89°18' W., bet. secs. 3 and 10.
	Desc. over rocky SW slope through scattered shadscale and native grasses.
1.75	Bottom of draw, drains S; asc. over SE slope.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
6.00	Top of spur, slopes S; desc. over SW slope.
9.25	Bottom of draw, drains S; asc. over steep SE slope.
13.50	Top of solid sandstone spur, projects S; desc. over steep SW slope.
22.00	Bottom of draw, drains S; asc. over broken SE slope.
29.00	Top of solid sandstone spur, projects S; desc over steep SW slope.
33.00	Bottom of draw, drains S; asc. over SE slope.
35.50	Top of spur, slopes S; desc. over SW slope.
37.50	Bottom of descent, slopes S; asc. along rocky S slope.
39.92	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 10, on face of sandstone ledge, 6 ft. high, at proportionate distance, where a permanent monument cannot be established; there is no remaining evidence of the original corner.
40.34	Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 3 and 10.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, $4\frac{1}{2}$ ft. base to top, with brass cap mkd.
	<p style="text-align: center;">W C T 10 S R 24 E $\frac{1}{4}$ $\frac{S 3}{S 10}$ → 1975</p>
	Asc. over steep rocky SE slope.
43.00	Rim of sandstone ledge, bears NE and SW; along gentle N slope.
49.00	Slope changes; desc. over gradual W slope.
75.00	Slope changes; desc. over NW slope.
79.84	The cor. of secs. 3, 4, 9 and 10.
	North, bet. secs. 3 and 4.
	Desc. over gentle NW slope, through scattered sagebrush, shadscale and native grasses.
1.50	E edge of bottom of draw, draining S; thence along gentle W slope.
16.00	Wash, 15 lks. wide, 6 ins. deep, in bottom of draw, drains W; asc. over S slope.
31.00	Slope changes; asc. over SW slope.
36.00	Top of spur, projects W; desc. over N slope.
40.02	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T 10 S R 24 E ¼ S 4 S 3 1975</p> <p>Desc. over N slope.</p>
46.50	Dirt road in bottom of hollow, bears E and W; hollow, drains W; asc. over SW slope.
55.00	Top of spur, slopes W; desc. over NW slope.
70.00	Bottom of draw, drains SW; asc. over S slope.
79.75	S rim of plateau, bears E and W; thence over nearly level land.
80.32	The cor. of secs. 3, 4, 33 and 34, N. Bdy., heretofore described.
	<p>From the stan. cor. of secs. 32 and 33, S. Bdy., heretofore described.</p> <p>N. 0°05' W., bet. secs. 32 and 33.</p> <p>Desc. over gradual N slope through scattered juniper, pinon, sagebrush, shadscale and native grasses.</p>
2.00	Wash, 20 lks. wide, 12 ins. deep, drains NW; asc. over SW slope.
14.00	Top of spur, slopes W; thence along W slope.
20.00	Point of spur, slopes N. 10° W.; desc. over steep N slope.
29.75	Wash in bottom of hollow, drains NW; asc. over SW slope.
39.50	Top of small spur, slopes W; desc. over NW slope.
39.96	<p>The ¼ sec. cor. of secs. 32 and 33, monumented with a sandstone, 20 x 14 x 4 ins., firmly set 10 ins. in the ground and mkd. ¼ on W face, from which the remaining original bearing tree</p> <p style="padding-left: 40px;">A dead pinon, 12 ins. diam., bears N. 61° E., 47 lks. dist., mkd. ¼ S33 BT.</p> <p>There is no remaining evidence of the other bearing tree.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base to top, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
	T 10 S R 24 E $\frac{1}{4}$ S 32 S 33 1975
	Deposit the mkd. stone alongside the iron post. Corner is located on NW slope, 15 ft. below top of spur, sloping W.
	<hr style="width: 20%; margin: auto;"/>
	N. 0°01' W., beginning new measurement.
	Desc. over NW slope through sparsely scattered juniper timber.
3.00	Bottom of draw, drains W; asc. over SW slope.
11.75	Top of ridge, bears NW and SE; thence along gentle W slope.
20.50	Slope changes; desc. over gentle N slope.
23.50	Small wash, drains W; asc. over S slope.
28.00	Top of ridge, bears NW and SE; desc. over NE slope.
38.50	Bottom of draw, drains NE; asc. over SE slope.
39.96	The cor. of secs. 28, 29, 32 and 33, monumented with a sandstone, 28 x 12 x 12 ins., firmly set 14 ins. in the ground and mkd. 1 notch on S and 4 notches on E edge, from which the original bearing trees
	A cedar, 6 ins. diam., bears N. 73° E., 21 lks. dist., mkd. T10S R24E S28 BT.
	A dead cedar, 6 ins. diam., bears S. 22° E., 62 lks. dist., mkd. T10S R24E S33 BT.
	A cedar, 6 ins. diam., bears S. 10° W., 123 lks. dist., mkd. T10S R24E S32 BT. (Record, 121 lks.)
	A cedar, 6 ins. diam., bears N. 33° W., 48 lks. dist., mkd. T10S R24E S29 BT.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T 10 S R 24 E S 29 S 28 S 32 S 33 1975
	Deposit the mkd. stone alongside the iron post. Corner is located on SE slope near top of spur, sloping NE.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
	From the cor. of secs. 27, 28, 33 and 34.
	N. 89°59' W., bet. secs. 28 and 33.
	Along gentle N slope through scattered juniper, pinon, sagebrush and native grasses.
5.50	Base of low ridge, bears NW and SE; asc. over NE slope.
10.50	Top of ridge, bears NW and SE; desc. over SW slope.
15.25	Bottom of draw, drains NW; asc. over NE slope.
20.50	Top of spur, slopes N; desc. over NW slope.
25.75	Small wash, drains NE; asc. over NE slope.
30.50	Spur, slopes NE; desc. over NW slope.
34.00	Bottom of draw, drains NE; asc. over NE slope.
39.90	Top of spur, projects N; desc. over W slope.
40.08	The ¼ sec. cor. of secs. 28 and 33, is determined at record bearing and distance from the remains of the original bearing trees
	A cedar, 4 ins. diam., bears S. 48° W., 91 lks. dist., mkd. ¼ S33 BT.
	A cedar, 5 ins. diam., bears N. 47° W., 64 lks. dist., mkd. ¼ S28 BT.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stne, 4 ft. base to top, with brass cap mkd.
	T 10 S R 24 E ¼ S 28 S 33 1975
	Corner is located on W slope, 5 ft. below top of spur, projecting N.
	N. 89°59' W., beginning new measurement.
	Desc. over W slope through scattered juniper timber.
3.50	Small wash, drains NE; asc. over gradual E slope.
18.00	Base of ridge, bears N and S; asc. over steep E slope.
22.50	Top of spur, slopes NE; thence along N slope.
27.00	Spur, slopes NW; desc. over W slope.
33.00	Slope changes; desc. over NW slope.
38.50	Bottom of draw, drains NE; asc. over SE slope.
40.03	The cor. of secs. 28, 29, 32 and 33.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
	N. 0°05' W., bet. secs. 28 and 29.
	Asc. over SE slope through scattered juniper, pinon, shadscale and native grasses.
0.50	Top of spur, slopes NE; desc. over N slope.
10.00	Small wash in bottom of draw, drains NE; thence along E slope.
17.50	Top of small spur, slopes NE; desc. over NW slope.
23.00	Wash, 10 lks. wide, 6 ins. deep, drains W; thence along W slope.
29.00	Same wash, drains N. 10° E. from SW.
36.00	Same wash drains N. 70° W. from S. 10° E.; asc. over SW slope.
39.88	The ¼ sec. cor. of secs. 28 and 29, monumented with a sandstone, 24 x 8 x 6 ins., set in small mound of stone, and dimly mkd. ¼ on W face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T 10 S R 24 E ¼ S 29 S 28 1975
	Deposit the mkd. stone alongside the iron post.

	N. 0°01' W., beginning new measurement.
	Asc. over SW slope.
1.00	Top of narrow spur, projects W; desc. along rocky W slope.
3.00	Bottom of descent, slopes W; asc. over SW slope.
4.30	Top of narrow spur, projects W; desc. abruptly over N slope.
10.50	Head of draw, drains N. 20° W.; thence along W slope.
25.90	Bottom of draw, drains W; asc. over SW slope.
29.25	Top of low ridge, bears NW and SE; desc. over NE slope.
34.00	Bottom of draw, drains NW; asc. over SW slope.
38.50	Top of spur, slopes W; desc. along gentle W slope.
40.00	The cor. of secs. 20, 21, 28 and 29, monumented with a sandstone, 20 x 14 x 6 ins., firmly set in a mound of stone, mkd. 2 notches on S and 4 notches on E edge and scattered mound of stone to W.
	At the corner point

273

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, $4\frac{1}{2}$ ft. base to top, with brass cap mkd.

T 10 S R 24 E

S 20	S 21
S 29	S 28

1975

Deposit the mkd. stone alongside the iron post.

From the cor. of secs. 21, 22, 27 and 28.

S. $89^{\circ}50'$ W., bet. secs. 21 and 28.

Desc. over NW slope through scattered juniper, pinon, sagebrush, shadscale and native grasses.

- 2.00 Bottom of draw, drains SW; asc. over SE slope.
- 8.00 Top of spur, projects SW; desc. over NW slope.
- 15.00 Bottom of draw, drains SW; leave juniper and pinon timber; thence along gentle S slope.
- 20.50 Wash, 20 lks. wide, 12 ins. deep, drains NW; thence along gentle N slope.
- 24.00 Dirt road along bottom of wash in Southam Canyon, draining NW, bears NW and SE.
- 36.50 Wash, 25 lks. wide, 2 ft. deep, drains SW.
- 40.06 Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
- T 10 S R 24 E
- | | |
|---------------|------|
| $\frac{1}{4}$ | S 21 |
| | S 28 |
- 1975
- Raise a mound of stne, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N of corner.
- Over nearly level land.
- 42.00 Wash, 25 lks. wide, 12 ins. deep, drains NW.
- 50.00 Base of spur, bears NW and SE; asc. over NE slope.
- 53.00 Top of spur, slopes N; desc. over NW slope.
- 55.50 Wash in bottom of draw, drains N; asc. over E slope.
- 67.00 Top of spur, projects NE; desc. over NW slope.
- 72.00 Bottom of draw, drains N; asc. over NE slope.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
77.00	Top of spur, projects N; desc. over gentle W slope.
80.12	The cor. of secs. 20, 21, 28 and 29.
	<p>N. 0°01' W., bet. secs. 20 and 21.</p> <p>Desc. abruptly over NW slope through thick native grasses.</p>
18.00	Base of main descent, bears NE and SW; slope changes; desc. over gradual N slope.
28.50	Dirt road, bears E and W.
30.25	Wash, 25 lks. wide, 2 ft. deep, drains E; asc. over SE slope.
33.00	Spur, slopes E; thence along E slope.
38.50	Spur, slopes NE; desc. over NW slope.
40.05	<p>The ¼ sec. cor. of secs. 20 and 21, monumented with a sandstone, 20 x 16 x 6 ins., firmly set in mound of stone, mkd. ¼ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base to top, with brass cap mkd.</p>
	<p style="text-align: center;">T 10 S R 24 E</p> <p style="text-align: center;"> ½</p> <p style="text-align: center;"> </p> <p style="text-align: center;">S 20 S 21</p> <p style="text-align: center;"> </p> <p style="text-align: center;"> 1975</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Corner is located on sandstone ledge, 8 ft. high, bears NE and SW.</p>
	<p style="text-align: center;">—————</p> <p>N. 0°03' W., beginning new measurement.</p> <p>Desc. over sandstone ledge and NW slope.</p>
9.00	Slope changes; desc. over N slope.
15.00	Wash in Southam Canyon, 20 lks. wide, 2 ft. deep, drains NW; asc. over SW slope.
19.30	Spur, slopes W; desc. along W slope.
30.25	Spur, slopes W; desc. over NW slope.
33.50	Bottom of draw, drains W; asc. over SW slope.
36.50	Spur, slopes W; desc. over NW slope.
39.65	Small wash in bottom of draw, drains W; asc. over S slope.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

<p>CHAINS 40.05</p>	<p>The cor. of secs. 16, 17, 20 and 21, monumented with a sandstone, 20 x 12 x 6 ins., set 10 ins. in the ground, mkd. 3 notches on S edge. No other legible markings can be found.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 5 ft. base to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 10 S R 24 E</p> <p> </p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 17</td> <td style="padding: 0 5px;">S 16</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 20</td> <td style="padding: 0 5px;">S 21</td> </tr> </table> <p> </p> <p>1975</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p>	S 17	S 16	S 20	S 21
S 17	S 16				
S 20	S 21				
<p>2.50</p> <p>4.50</p> <p>10.00</p> <p>27.50</p> <p>39.98</p>	<p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>N. 89°59' W., bet. secs. 16 and 21.</p> <p>Over river bottom land through tamarack, scattered cottonwoods, sagebrush and native grasses.</p> <p>White River, 3 chs. wide, flows SW.</p> <p>Base of spur, bears NE and SW; leave river bottom land and cottonwood timber; asc. over SE slope.</p> <p>Top of spur, slopes S; desc. over gradual SW slope.</p> <p>Base of descent, bears NW and SE; enter river bottom land and cottonwood timber.</p> <p>Point for the ¼ sec. cor. of secs. 16 and 21, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 10 S R 24 E</p> <p>¼ <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 16</td> <td style="padding: 0 5px;">S 21</td> </tr> </table></p> <p>1975</p> </div> <p>Set a cottonwood post, 5 ft. long, projecting 3 ft. above ground, alongside the iron post.</p> <p>Continue over river bottom land.</p>	S 16	S 21		
S 16	S 21				
<p>57.00</p> <p>59.90</p> <p>71.50</p> <p>79.96</p>	<p>White River, 3 chs. wide, flows NW.</p> <p>Base of sandstone ledges, bears NW and SE; asc. over NE slope.</p> <p>Top of ridge, bears NW and SE; desc. along S slope of draw.</p> <p>The cor. of secs. 16, 17, 20 and 21.</p>				

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
	N. 0°04' W., bet. secs. 16 and 17.
	Asc. over S slope of draw.
2.50	Top of spur, slopes W; desc. over NW slope.
8.00	Slope changes; desc. over N slope.
10.50	Rim of sandstone ledge, bears NW and SE; desc. abruptly over NE slope.
13.00	Base of descent, bears NW and SE; enter river bottom land with tamarack and cottonwood timber.
21.00	White River, 3 chs. wide, flows W.
32.00	Wash, drains SW.
33.00	Base of ascent, bears NW and SE; leave river bottom land; asc. over SW slope.
38.50	Top of spur, projects W; desc. over N slope.
39.50	Base of spur, bears E and W; asc. over gradual S slope.
39.98	Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 10 S R 24 E $\frac{1}{4}$ S 17 S 16 1975
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W of corner.
41.00	Dirt road, bears N and curves W.
47.00	Leave road, bearing NW and S; thence along gentle W slope.
53.00	Base of spur, bears NW and SE; asc. over SW slope.
60.00	Top of spur, slopes W; desc. over N slope.
65.00	Bottom of draw, drains W; asc. over S slope.
79.96	The cor. of secs. 8, 9, 16 and 17, monumented with a sandstone, 14 x 10 x 4 ins., firmly set 8 ins. in the ground, mkd. 4 notches on S and E edge and in a scattered mound of stone.
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, $4\frac{1}{2}$ ft. base to top, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
	T 10 S R 24 E S 8 S 9 S 17 S 16 1975
	Deposit the mkd. stone alongside the iron post.
	From the cor. of secs. 9, 10, 15 and 16.
	N. 89°52' W., bet. secs. 9 and 16.
	Desc. over gradual NW slope through scattered shadscale and native grasses.
4.00	Slope changes; desc. over W slope.
8.00	Base of slope, bears N and S; enter river bottom land with thick tamarack.
13.00	White River, 3 chs. wide, flows S.
22.50	Base of steep ascent, bears N and S; leave river bottom land; asc. over steep E slope.
31.00	Top of ascent, bears N and S; desc. over gradual W slope.
40.08	The ¼ sec. cor. of secs. 9 and 16, monumented with a sandstone, 14 x 10 x 4 ins., firmly set 8 ins. in the ground, mkd. ¼ on N face, with small mound of stone to N.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base to top, with brass cap mkd.
	T 10 S R 24 E ¼ S 9 S 16 1975
	Deposit the mkd. stone alongside the iron post.
	S. 89°59' W., beginning new measurement.
	Desc. over W slope.
1.50	Bottom of draw, drains S; asc. over E slope.
7.00	Top of ridge, bears N and S; desc. over W slope.
19.00	Head of draw, drains SW; asc. over SE slope.
22.50	Top of spur, slopes SW; desc. over W slope.
26.00	Small wash in bottom of draw, drains S; asc. over E slope.
31.50	Top of ridge, bears N and S; desc. over SW slope.
36.00	Bottom of draw, drains SW; asc. along S slope.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
40.02	The cor. of secs. 8, 9, 16 and 17.
	N. 0°15' E., bet. secs. 8 and 9. Asc. over S slope through scattered shadscale and native grasses.
0.25	Top of spur, projects W; desc. over N slope.
6.50	Dirt road in bottom of draw, draining W, bears E and W; asc. over gradual SE slope.
38.50	Top of spur, slopes E; desc. along gentle E slope.
39.81	Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 5 ft. base to top, with brass cap mkd.
	T 10 S R 24 E $\frac{1}{4}$ S 8 S 9 1975
	Continue along rocky E slope.
45.50	Head of draw, drains S. 10° E.; asc. over S slope.
52.00	Spur, slopes E; desc. over N slope.
54.75	Bottom of draw, drains E; asc. over S slope.
57.75	Spur, slopes E; desc. over gradual NE slope.
68.00	Bottom of draw, drains SE; asc. over gradual S slope.
79.62	The cor. of secs. 4, 5, 8 and 9, monumented with a sandstone, 16 x 10 x 6 ins., firmly set 8 ins. in the ground, mkd. 5 notches on S and 4 notches on E edge with small mound of stone to W. At the corner point Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 10 S R 24 E S 5 S 4 S 8 S 9 1975
	Deposit the mkd. stone alongside and raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft. high, W of iron post.
	From the cor. of secs. 3, 4, 9 and 10. N. 89°50' W., bet. secs. 4 and 9.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
	Desc. over NW slope through scattered sagebrush, shad-scale and native grasses.
1.75	Wash, 30 lks. wide, 6 ins. deep, drains N. 85° W.; thence along gentle N slope of wash.
12.00	Wash turns S; asc. over E slope.
16.00	Top of spur, slopes S; desc. over W slope.
19.00	Bottom of draw, drains S; thence along gentle S slope.
26.00	Top of spur, slopes S; desc. over SW slope.
33.90	Dirt road, bears N. 45° W. and S. 45° E.; asc. over E slope.
40.31	The $\frac{1}{4}$ sec. cor. of secs. 4 and 9, monumented with a sandstone, 16 x 8 x 5 ins., firmly set 8 ins. in the ground, mkd. $\frac{1}{4}$ on N face with small mound of stone to N. At the corner point Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 10 S R 24 E $\frac{1}{4}$ $\frac{S}{S}$ $\frac{4}{9}$ 1975 </div> Deposit the mkd. stone alongside and set a mound of stone, 2 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft. high, N of corner. <hr style="width: 20%; margin: auto;"/> N. 89°40' W., beginning new measurement. Asc. over E slope.
5.50	Top of ridge, bears NW and SE; desc. over S slope.
14.00	Bottom of draw, drains SW; asc. over SE slope.
18.00	Top of spur, slopes S; desc. along gentle S slope.
26.00	Small wash, drains S.
40.00	The cor. of secs. 4, 5, 8 and 9.
	N. 0°02' E., bet. secs. 4 and 5. Asc. over gradual S slope through scattered shadscale and native grasses.
33.75	Base of high ridge, bears NW and SE; asc. over steep SW slope.
39.90	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5, on steep inaccessible slope, at proportionate distance, where it is unsafe to establish a permanent monument; there is no remaining evidence of the original corner. Asc. over ledgy S slope.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
40.95	<p>Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 4 and 5.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, $4\frac{1}{2}$ ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>W C T 10 S R 24 E $\frac{1}{4}$ S 5 S 4 1975</p> </div> <p>Corner is located on shelf, bearing NW and SE, 25 ft. below top of ridge.</p> <p>Asc. over sandstone ledge.</p>
42.50	Top of ridge, bears E and W; desc. over N slope.
48.00	Bottom of draw, drains W; asc. over S slope.
52.00	Top of spur, slopes W; desc. over NW slope.
59.00	Wash in bottom of hollow, drains W; asc. over SE slope.
71.50	Top of spur, slopes W; thence along W slope.
80.09	The cor. of secs. 4, 5, 32 and 33, N. Bdy., heretofore described.
	<p>From the stan. cor. of secs. 31 and 32, S. Bdy., heretofore described.</p> <p>N. $0^{\circ}21'$ E., bet. secs. 31 and 32.</p> <p>Along rocky W slope through scattered shadscale and native grasses.</p> <p>3.00 Top of spur, slopes NW; desc. over steep N slope.</p> <p>11.00 Wash, 20 lks. wide, 12 ins. deep, drains NW; asc. along W slope.</p> <p>12.75 Old jeep trail, bears NW and SE.</p> <p>16.00 Bottom of draw, drains SW; asc. along E slope of draw.</p> <p>27.50 Head of draw, drains S. 10° E.; asc. over S slope.</p> <p>36.00 Spur, slopes W; desc. over N slope.</p> <p>37.50 Small wash in draw, drains N. 10° W.; thence desc. along W slope of draw.</p> <p>39.85 The $\frac{1}{4}$ sec. cor. of secs. 31 and 32, monumented with a sandstone, 20 x 8 x 5 ins., firmly set 10 ins. in the ground, mkd. $\frac{1}{4}$ on W face, from which the original bearing tree</p> <p style="padding-left: 40px;">A cedar, 8 ins. diam., bears N. 28° W., 16 lks. dist., mkd. $\frac{1}{4}$ S31 BT. (Record, 22 lks.)</p> <p>There is no remaining evidence of the other bearing tree.</p>

281

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base to top, with brass cap mkd.

T 10 S R 24 E
|
¼
S 31 | S 32
|
1975

Deposit the mkd. stone alongside the iron post.

N. 0°44' W., beginning new measurement.

Desc. over NW slope through scattered juniper and pinon timber.

- 5.00 Bottom of draw, drains SW; asc. over SE slope.
10.50 Top of spur, slopes SW; desc. over NW slope.
13.7- Bottom of draw, drains W; asc. over SW slope.
16.00 Top of spur, projects NW; desc. along E slope of draw.
35.00 Top of spur, slopes NE; desc. over gentle N slope.
40.38 The cor. of secs. 29, 30, 31 and 32, monumented with a sandstone, 28 x 12 x 5 ins., firmly set 14 ins. in the ground, mkd. 1 notch on S and 5 notches on E edge, from which the original bearing trees

A cedar, 6 ins. diam., bears N. 11° E., 96 lks. dist., mkd. T10S R24E S29 BT.

A cedar, 7 ins. diam., bears S. 72° E., 196 lks. dist., mkd. T10S R24E S32 BT.

A cedar, 7 ins. diam., bears S. 50° W., 168 lks. dist., mkd. T10S R24E S31 BT.

A cedar, 7 ins. diam., bears N. 53° W., 94 lks. dist., mkd. T10S R24E S30 BT.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 10 S R 24 E
|
S 30 | S 29
S 31 | S 32
|
1975

Bury the mkd. stone alongside the iron post.

Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of corner.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
	From the cor. of secs. 28, 29, 32 and 33.
	N. 89°41' W., bet. secs. 29 and 32.
	Asc. over SE slope through scattered juniper and pinon timber.
0.50	Top of spur, slopes NE; desc. over NW slope.
4.75	Bottom of draw, drains NE; asc. over E slope.
9.50	Top of spur, projects N; desc. over NW slope.
12.00	Bottom of draw, drains NW; asc. over NE slope.
15.50	Top of spur, slopes N; desc. over NW slope.
18.50	Bottom of draw, drains N; asc. over NE slope.
21.50	Top of spur, slopes N; desc. over NW slope.
28.00	Bottom of draw, drains N; asc. over NE slope.
31.00	Top of spur, slopes N; desc. over W slope.
34.50	Wash, 20 lks. wide, 6 ins. deep, in hollow, drains N; asc. along N slope.
39.67	The ¼ sec. cor. of secs. 29 and 32, monumented with a sandstone, 18 x 14 x 8 ins., firmly set 10 ins. in the ground, mkd. ¼ on N face, from which the original bearing trees
	A cedar, 10 ins. diam., bears S. 50° E., 123 lks. dist., mkd. ¼ S32 BT.
	A cedar, 12 ins. diam., bears N. 36° W., 20 lks. dist., mkd. ¼ S29 BT.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 10 S R 24 E S 29 ¼ S 32 1975
	Deposit the mkd. stone alongside the iron post.

	N. 89°39' W., beginning new measurement.
	Along N slope.
1.00	Bottom of draw, drains NE; asc. over E slope.
3.75	Top of ridge, bears N and S; desc. over SW slope.
19.00	Bottom of draw, drains NW; asc. over NE slope.
23.00	Top of spur, slopes NW; desc. over SE slope.
25.00	Bottom of draw, drains NW; asc. over broken NE slope.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
31.50	Top of spur, slopes N; desc. over W slope.
38.00	Wash, 20 lks. wide, 2 ft. deep, drains NW; asc. along gentle N slope.
40.10	The cor. of secs. 29, 30, 31 and 32.
	S. 89°58' W., bet. secs. 30 and 31.
	Asc. along gentle N slope, through scattered juniper, pinon, sagebrush, shadscale and native grasses.
2.50	Base of spur, bears N and S; asc. over E slope.
4.50	Top of spur, slopes N; desc. over NW slope.
6.00	Bottom of draw, drains N; asc. over NE slope.
7.50	Top of spur, projects N; desc. over steep W slope.
12.50	Base of spur, bears N and S; desc. along gentle N slope.
27.50	Small wash in bottom of draw, drains N; asc. along gradual N slope.
37.00	Small draw, drains NE; asc. over NE slope.
38.50	Top of spur, slopes N; desc. over gentle NW slope.
40.02	The $\frac{1}{4}$ sec. cor. of secs. 30 and 31, monumented with a sandstone, 28 x 10 x 8 ins., firmly set 14 ins. in the ground, and mkd. $\frac{1}{4}$ on N face, from which the original bearing trees
	A cedar, 12 ins. diam., bears S. 13° E., 133 lks. dist., mkd. $\frac{1}{4}$ S31 BT. (Record, 130 lks.)
	A cedar, 4 ins. diam., bears N. 21° W., 29 lks. dist., mkd. $\frac{1}{4}$ S30 BT. (Record, 36 lks.)
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T 10 S R 24 E $\frac{1}{4}$ $\frac{S 30}{S 31}$ 1975
	Deposit the mkd. stone alongside the iron post.
	S. 89°41' W., beginning new measurement.
	Desc. over NW slope, through scattered juniper and pinon timber.
2.50	Bottom of draw, drains NE; asc. over SE slope.
5.50	Top of spur, projects NE; desc. over NW slope.
9.00	Top of spur, projects NW; desc. over SW slope.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
12.00	Bottom of draw, drains NW; asc. over NE slope.
15.50	Top of spur, projects NW; desc. over steep SW slope.
25.75	Wash, 20 lks. wide, 12 ins. deep, drains N. 85° W.; thence along gentle N slope.
33.70	Wash, 20 lks. wide, 12 ins. deep, drains SW; thence along gentle S slope.
38.25	Wash, 25 lks. wide, 6 ft. deep, drains NW; thence along gentle N slope.
39.47	The cor. of secs. 25, 30, 31 and 36, W. Bdy., heretofore described.
	From the cor. of secs. 29, 30, 31 and 32.
	N. 0°02' E., bet. secs. 29 and 30.
	Desc. over gradual N slope through scattered sagebrush, shadscale and native grasses.
1.00	Wash, 20 lks. wide, 2 ft. deep, drains NW.
5.00	Same wash, drains NE; asc. over SE slope.
12.00	Top of spur, slopes E; desc. over NE slope.
30.25	Wash, 20 lks. wide, 3 ft. deep, drains W; asc. over gradual S slope.
31.50	Dirt road, bears N. 80° E. and S. 80° W.
39.94	The ¼ sec. cor. of secs. 29 and 30, monumented with a sandstone, 23 x 14 x 5 ins., firmly set 10 ins. in the ground, mkd. ¼ on W face, from which the original bearing trees
	A cedar, 6 ins. diam., bears N. 72° E., 62 lks. dist., mkd. ¼ S29 BT.
	A cedar, 4 ins. diam., bears S. 61° W., 63 lks. dist., mkd. ¼ S30 BT.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone to top, with brass cap mkd.
	<p style="text-align: center;">T 10 S R 24 E</p> <p style="text-align: center;">¼ S 30 S 29 1975</p>
	Deposit the mkd. stone alongside the iron post.
	N. 0°08' W., beginning new measurement.
	Asc. over S slope through scattered juniper and pinon timber.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
6.50	Top of ridge, bears E and W; desc. over N slope.
9.50	Small wash in bottom of draw, drains W; thence along broken W slope.
21.00	Bottom of draw, drains W; asc. over S slope.
31.50	Top of spur, slopes W; desc. over steep NW slope.
38.50	Bottom of small draw, drains NW; thence along W slope.
39.64	The cor. of secs. 19, 20, 29 and 30, monumented with a sandstone, 24 x 10 x 5 ins., set on solid sandstone, in a mound of stone, mkd. 2 notches on S and 5 notches on E edge.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam. over a cross (X) in solid sandstone, in a mound of stone, 5 ft. base to top, with brass cap mkd.
	<pre> T 10 S R 24 E S 19 S 20 S 30 S 29 1975 </pre>
	Deposit the mkd. stone alongside the iron post.
	Corner is located on W slope, 5 ft. below top of spur, sloping N.
	From the cor. of secs. 20, 21, 28 and 29.
	N. 89°57' W., bet. secs. 20 and 29.
	Desc. over ledgey NW slope through scattered shadscale and native grasses.
4.50	Bottom of draw, drains N; asc. over NE slope.
8.50	Top of spur, slopes N; desc. over NW slope.
12.00	Wash, 20 lks. wide, 6 ins. deep, drains NE; asc. over gentle E slope.
15.40	Dirt road, bears N. 45° E. and S. 45° W.; asc. over SE slope.
23.00	Head of draw, drains S. 75° E.; asc. over E slope.
26.50	Spur, slopes NE; thence along N slope.
30.50	Bottom of draw, drains NE; asc. over NE slope.
33.50	Top of spur, slopes N; desc. along steep N slope.
39.89	The ¼ sec. cor. of secs. 20 and 29, monumented with a sandstone, 20 x 12 x 5 ins., firmly set 10 ins. in the ground, mkd. ¼ on N face.
	At the corner point

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T 10 S R 24 E ¼ $\frac{S\ 20}{S\ 29}$ 1975</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Corner is located on steep N slope, 40 ft. below top of ridge, bearing E and W.</p> <p style="text-align: center;">_____</p> <p>N. 89°58' W., beginning new measurement.</p> <p>Along steep rocky N slope.</p>
2.00	Slope changes; asc. over NE slope.
4.00	Spur, slopes N; desc. along N slope.
8.50	Top of spur, slopes NW; desc. over NW slope.
16.00	Small wash in bottom of draw, drains NE; asc. over SE slope.
21.00	Top of spur, slopes NE; thence along N slope.
28.00	Slope changes; asc. over E slope.
31.50	Top of ridge, bears N and S; desc. over steep W slope.
36.00	Small wash in bottom of draw, drains NW; thence along N slope.
38.25	Top of small spur, slopes N; desc. over gentle W slope.
39.86	The cor. of secs. 19, 20, 29 and 30.
	<p>N. 89°46' W., bet. secs. 19 and 30.</p> <p>Desc. over W slope through scattered juniper, pinon, shadscale and native grasses.</p>
1.50	Bottom of small draw, drains N; thence along N slope.
7.00	Top of spur, slopes NW; desc. over W slope.
11.25	Bottom of draw, drains NW; thence along N slope.
22.00	Top of spur, slopes N; desc. over NW slope.
24.00	Base of spur, bears N and S; desc. over gradual NW slope.
37.50	Slope changes; desc. over W slope in small draw.
39.73	<p>The ¼ sec. cor. of secs. 19 and 30, monumented with a sandstone, 24 x 18 x 4 ins., firmly set 10 ins. in the ground, mkd. ¼ on N face, from which the original bearing trees</p> <p style="padding-left: 40px;">A cedar, 10 ins. diam., bears N. 41° E., 55½ lks. dist., mkd. ¼ S19 BT.</p>

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
	<p>A cedar, 16 ins. diam., bears S. 55° E., 79 lks. dist., mkd. $\frac{1}{4}$ S30 BT.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 10 S R 24 E $\frac{1}{4}$ $\frac{S 19}{S 30}$ 1975</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Corner is located in bottom of draw, 20 lks. E of wash, draining S.</p> <p style="text-align: center;">_____</p> <p>N. 89°17' W., beginning new measurement.</p> <p>Along bottom of draw.</p> <p>2.00 Leave draw; thence along gradual S slope.</p> <p>9.00 Top of spur, projects S; leave timber; desc. along broken S slope.</p> <p>18.00 Top of spur, slopes SW; desc. over W slope.</p> <p>30.50 Wash, 20 lks. wide, 12 ins. deep, drains NW; thence along gentle N slope.</p> <p>36.00 Asphalt Wash, 40 lks. wide, 6 ft. deep, drains NE.</p> <p>38.50 Small wash, drains N into Asphalt Wash.</p> <p>39.10 Dirt road, bears N and S. 25° E.</p> <p>39.68 The cor. of secs. 19, 24, 25 and 30, W. Bdy., heretofore described.</p>
	<p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°21' E., bet. secs. 19 and 20.</p> <p>Desc. over NW slope through scattered juniper, pinon sagebrush, shadscale and native grasses.</p> <p>3.25 Small wash in bottom of draw, drains W; asc. over S slope.</p> <p>4.50 Top of small spur, slopes W; desc. over NW slope.</p> <p>9.00 Bottom of draw, drains SW; asc. over SE slope.</p> <p>17.00 Top of ridge, bears E and W; desc. over NW slope.</p> <p>21.00 Head of draw, drains W; asc. over SW slope.</p> <p>28.00 Top of high spur, slopes W; desc. over NW slope.</p> <p>39.95 The $\frac{1}{4}$ sec. cor. of secs. 19 and 20, monumented with a sandstone, 20 x 10 x 6 ins., firmly set 10 ins. in the ground, mkd. $\frac{1}{4}$ on W face, from which the original bearing trees</p>

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS

A cedar, 20 ins. diam., bears S. 86° E., 23 lks.
dist., mkd. $\frac{1}{4}$ S20 BT.

A cedar, 24 ins. diam., bears N. 45° W., 5 lks.
dist., mkd. $\frac{1}{4}$ S19 BT.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins.
in the ground to bedrock, in a mound of stone, 4 ft.
base to top, with brass cap mkd.

T 10 S R 24 E
 $\frac{1}{4}$
 |
 S 19 | S 20
 |
 1975

Deposit the mkd. stone alongside the iron post.

N. 0°08' W., beginning new measurement.

Desc. over NW slope through scattered juniper, pinon
and shadscale.

- 7.00 Bottom of draw, drains NE; leave timber; asc. over SE
slope.
- 9.00 Top of small spur, slopes NE; desc. over NE slope.
- 13.00 Wash, drains NW; thence along gentle W slope.
- 29.00 Spur, slopes W; along broken W slope.
- 38.50 Bottom of draw, drains SW; asc. over S slope.
- 39.85 The cor. of secs. 17, 18, 19 and 20, monumented with a
sandstone, 26 x 18 x 5 ins., firmly set in a mound of
stone, mkd. 3 notches on S and 5 notches on E edge.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 3 ins.
in the ground to bedrock, in a mound of stone, 4½ ft.
base to top, with brass cap mkd.

T 10 S R 24 E
 |
 S 18 | S 17
 S 19 | S 20
 |
 1975

Deposit the mkd. stone alongside the iron post.

From the cor. of secs. 16, 17, 20 and 21.

S. 89°46' W., bet. secs. 17 and 20.

Desc. along S slope of draw, through scattered shadscale
and native grasses.

- 4.50 Rim of hollow, bears NW and SE; desc. over ledgy SE
slope.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
12.50	Small wash in bottom of hollow, drains NW; asc. over NE slope.
16.00	Small draw, drains N. 25° E.; asc. over E slope.
21.50	Top of spur, slopes N; desc. over NW slope.
33.50	Head of draw, drains N; asc. over E slope.
36.00	Top of spur, slopes N; desc. over NW slope.
38.66	The ¼ sec. cor. of secs. 17 and 20, monumented with a sandstone, 30 x 15 x 5 ins., set in a mound of stone, dimly mkd. ¼ on N face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base to top, with brass cap mkd.
	T 10 S R 24 E S 17 ¼ ——— S 20 1975
	Deposit the mkd. stone alongside the iron post.
	S. 89°43' W., beginning new measurement.
	Desc. over NW slope.
0.50	Small wash in bottom of draw, drains NE; asc. over NE slope.
32.00	Base of high ridge, bears NW and SE; asc. over steep ledgey NE slope.
37.00	Rim of ridge, bears N. 10° W. and S. 45° E.; desc. along S slope.
40.94	The cor. of secs. 17, 18, 19 and 20.
	S. 89°56' W., bet. secs. 18 and 19.
	Along gentle S slope through scattered shadscale and native grasses.
4.00	Slope changes; desc. over W slope.
6.00	Wash, 30 lks. wide, 6 ins. deep; drains NW; thence along gentle N slope.
11.00	Small wash, drains NE; asc. over E slope.
14.25	Slope changes; asc. over SE slope.
24.50	Top of spur, slopes NE; asc. over NE slope.
35.00	Top of high ridge, bears N and S; desc. over steep W slope.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
39.98	Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T 10 S R 24 E $\frac{1}{4}$ $\frac{S 18}{S 19}$ 1975
	Desc. over NW slope.
43.00	Bottom of draw, drains SW; asc. over SE slope.
47.50	Top of spur, slopes S; desc. over SW slope.
52.50	Small wash, drains NW; thence along N slope.
60.25	Small wash, drains N; asc. over broken NE slope.
79.81	The cor. of secs. 13, 18, 19 and 24, W. Bdy., heretofore described.
	From the cor. of secs. 17, 18, 19 and 20. N. $0^{\circ}06'$ E., bet. secs. 17 and 18. Asc. over S slope through scattered shadscale and native grasses.
0.70	Top of ascent, bears E and W; desc. along W slope.
11.00	Point of spur, slopes N; desc. over N slope.
15.50	Bottom of draw, drains W; asc. over SW slope.
20.00	Top of spur, slopes W; desc. over NW slope.
25.00	Bottom of draw, drains W; asc. over SW slope.
28.50	Top of spur, slopes W; desc. over N W slope.
30.00	Bottom of draw, drains W; asc. over S slope.
34.50	Top of spur, slopes SW; thence along W slope of knoll.
37.00	Spur, slopes W; desc. over N slope.
39.59	The $\frac{1}{4}$ sec. cor. of secs. 17 and 18, monumented with a sandstone, 20 x 16 x 6 ins., firmly set 10 ins. in the ground, mkd. $\frac{1}{4}$ on W face, with scattered mound of stone to W.
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
	<p>T 10 S R 24 E</p> <p style="margin-left: 100px;"> </p> <p style="margin-left: 100px;">1/4</p> <p style="margin-left: 100px;"> </p> <p style="margin-left: 100px;">S 18 S 17</p> <p style="margin-left: 100px;"> </p> <p style="margin-left: 100px;">1975</p>
	<p>Deposit the mkd. stone alongside the iron post.</p> <p>Corner is located on N slope, 15 ft. below top of spur, sloping W.</p>
	<hr style="width: 20%; margin: 0 auto;"/>
	<p>North, beginning new measurement.</p> <p>Desc. over N slope.</p>
5.00	Bottom of draw, drains W; asc. over SW slope.
8.50	Top of ridge, bears NW and SE; desc. over NE slope.
12.75	Bottom of draw, drains NE; thence desc. along rocky E slope.
24.00	Base of spur, bears NW and SE; desc. over NE slope.
28.00	Slope changes; desc. over gradual N slope.
40.04	The cor. of secs. 7, 8, 17 and 18, monumented with a sandstone, 52 x 10 x 6 ins., firmly set 10 ins. in the ground, mkd. 4 notches on S and 5 notches on E edge. (Record, sandstone, 36 x 10 x 6 ins.)
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.</p>
	<p>T 10 S R 24 E</p> <p style="margin-left: 100px;"> </p> <p style="margin-left: 100px;">S 7 S 8</p> <p style="margin-left: 100px;">S 18 S 17</p> <p style="margin-left: 100px;"> </p> <p style="margin-left: 100px;">1975</p>
	<p>Deposit the mkd. stone alongside the iron post.</p>
	<p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>S. 89°32' W., bet. secs. 8 and 17.</p> <p>Along S slope through scattered shadscale and native grasses.</p>
3.00	Begin descent over SW slope.
6.75	Dirt road, bears NW and SE.
8.00	Wash, 30 lks. wide, 6 ins. deep, drains irregularly S; asc. over gradual E slope.
27.50	Top of spur, slopes SE; desc. over SW slope.
33.50	Slope changes; desc. over W slope.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
39.73	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 17, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., over a cross (X) chiseled in solid sandstone, in a mound of stone, $4\frac{1}{2}$ ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 10 S R 24 E</p> <p>$\frac{1}{4}$ $\frac{S 8}{S 17}$</p> <p>1975</p> </div> <p>Desc. over W slope.</p>
44.50	<p>Base of descent, bears NW and SE; enter river bottom land, with scattered cottonwoods and tamarack.</p>
60.50	<p>White River, 3 chs. wide, flows NW.</p>
62.00	<p>Base of steep ascent, bears NW and SE; leave river bottom land; asc. over NE slope.</p>
64.00	<p>Top of ascent, bears NW and SE; thence along gentle N slope.</p>
66.00	<p>Head of draw, drains NE.</p>
73.25	<p>Bottom of draw, drains N.</p>
79.46	<p>The cor. of secs. 7, 8, 17 and 18.</p>
	<p>West, bet. secs. 7 and 18.</p>
	<p>Along gradual N slope through scattered shadscale and native grasses.</p>
11.00	<p>Point of spur, slopes N; desc. over gradual NW slope.</p>
32.00	<p>Edge of river bottom land, bears NE and SW; over bottom land through scattered cottonwoods and tamarack.</p>
35.81	<p>Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 7 and 18.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>W C</p> <p>T 10 S R 24 E</p> <p>$\frac{1}{4}$ $\frac{S 7}{S 18}$</p> <p>1975</p> </div>
	<p>Set a cottonwood post, 6 ft. long, projecting 4 ft. above ground, alongside the iron post.</p>
40.02	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 18, near river edge, at proportionate distance; where it is unsafe to establish a permanent monument; there is no remaining evidence of the original corner.</p>
41.00	<p>White River, 3 chs. wide, flows SW.</p>

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
44.00	Edge of river bottom land, bears NE and SW; thence along gentle S slope.
53.00	Enter river bottom land, bears NW and SE.
58.00	White River, 3 chs. wide, flows NW.
70.00	Leave river bottom land, bears NW and SE; asc. over NE slope.
71.50	Slope changes; thence along slightly broken N slope.
79.80	The cor. of secs. 7, 12, 13 and 18, W. Bdy., heretofore described.
From the cor. of secs. 7, 8, 17 and 18.	
N. 0°11' W., bet. secs. 7 and 8.	
Desc. over gradual N slope through scattered shadscale and native grasses.	
19.50	Enter river bottom land, bears NW and SE; enter scattered cottonwood timber and tamarack.
28.00	White River, 3 chs. wide, flows W.
31.00	Leave river bottom land, bears N. 80° W. and S. 80° E.; asc. over steep S slope.
35.00	Top of high sandstone butte; desc. over NE slope.
41.83	The ¼ sec. cor. of secs. 7 and 8, monumented with a sandstone, 12 x 8 x 6 ins., firmly set 6 ins. in the ground, mkd. ¼ on W face.
At the corner point	
Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.	
<p>T 10 S R 24 E</p> <p>¼</p> <p> </p> <p>S 7 S 8</p> <p> </p> <p>1975</p>	
Deposit the mkd. stone alongside the iron post.	
<hr style="width: 20%; margin: auto;"/>	
N. 0°06' W., beginning new measurement.	
Desc. over NE slope.	
3.00	Bottom of draw, drains W; asc. over SW slope.
5.50	Top of spur, slopes W; desc. over NW slope.
8.00	Bottom of draw, drains SW; asc. over S slope.
12.00	Top of spur, slopes W; desc. over NW slope.
14.00	Bottom of draw, drains SW; asc. over SW slope.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS							
17.50	Top of spur, slopes W; desc. over NW slope.						
19.00	Bottom of draw, drains SW; asc. over steep S slope.						
22.50	Top of spur, slopes SE; thence along steep E slope.						
30.00	Slope changes; asc. over SE slope.						
35.00	Top of spur, slopes W; desc. over steep N slope.						
39.86	The cor. of secs. 5, 6, 7 and 8, monumented with a sandstone, 16 x 8 x 5 ins., firmly set 8 ins. in the ground, mkd. 5 notches on the S and E edges. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd. <div style="text-align: center;"> <table border="0"> <tr><td>T 10 S R 24 E</td></tr> <tr><td> </td></tr> <tr><td>S 6 S 5</td></tr> <tr><td>S 7 S 8</td></tr> <tr><td> </td></tr> <tr><td>1975</td></tr> </table> </div> Deposit the mkd. stone alongside the iron post. Corner is located on steep N slope, 40 ft. above bottom of wash, draining W.	T 10 S R 24 E		S 6 S 5	S 7 S 8		1975
T 10 S R 24 E							
S 6 S 5							
S 7 S 8							
1975							
28.50	From the cor. of secs. 4, 5, 8 and 9. S. 89°48' W., bet. secs. 5 and 8. Along gentle S slope through scattered shadscale and native grasses.						
39.85	Small wash, drains S; asc. over gradual SE slope. The ¼ sec. cor. of secs. 5 and 8, monumented with a sandstone, 14 x 6 x 4 ins., firmly set 8 ins. in the ground, mkd. ¼ on N face, with small mound of stone to N. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table border="0"> <tr><td>T 10 S R 24 E</td></tr> <tr><td>¼ S 5</td></tr> <tr><td>¼ S 8</td></tr> <tr><td>1975</td></tr> </table> </div> Deposit the mkd. stone alongside the iron post. <hr style="width: 20%; margin: auto;"/> N. 87°50' W., beginning new measurement. Asc. over gradual SE slope.	T 10 S R 24 E	¼ S 5	¼ S 8	1975		
T 10 S R 24 E							
¼ S 5							
¼ S 8							
1975							
14.00	Base of ridge, bears N and S; asc. over steep E slope.						
20.00	Top of ridge, bears N and S; desc. over NW slope.						

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
34.00	Bottom of small draw, drains NW; thence along steep N slope.
40.17	The cor. of secs. 5, 6, 7 and 8.
S. 89°05' W., bet. secs. 6 and 7.	
Along steep N slope through scattered shadscale and native grasses.	
3.00	Spur, slopes NW; desc. over NW slope.
7.75	Base of spur, bears NE and SW; thence along bottom of hollow.
9.75	Wash, 25 lks. wide, 6 ins. deep, drains SW; asc. over broken SE slope.
36.00	Top of ridge, bears NE and SW; desc. over NW slope.
39.85	Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 6 and 7.
Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., over a cross (X) chiseled in solid sandstone, in a mound of stone, 4 $\frac{1}{2}$ ft. base to top, with brass cap mkd.	
<p style="text-align: center;">W C T 10 S R 24 E $\frac{1}{4}$ ← $\frac{S 6}{S 7}$ 1975</p>	
39.96	Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7, falls on steep sandstone ledge, where it is impossible to establish a permanent monument; there is no remaining evidence of the original corner.
Desc. over steep NW slope.	
49.00	Small wash in bottom of hollow, drains SW; asc over steep E slope.
59.00	Top of ridge, bears NE and SW; desc. over NW slope.
65.00	Small wash in bottom of hollow, drains SW; asc. over SE slope.
75.50	Rim of hollow, bears N and S; thence along gentle S slope.
79.37	The cor. of secs. 1, 6, 7 and 12, W. Bdy., heretofore described.
From the cor. of secs. 5, 6, 7 and 8.	
N. 0°03' E., bet. secs. 5 and 6.	
Desc. over steep N slope through scattered shadscale and native grasses.	
5.00	Small wash in bottom of hollow, drains W; asc. along E slope.
18.00	Bottom of draw, drains SE; asc. over SE slope.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
22.50	Top of spur, slopes SE; asc. along E slope.
28.00	Bottom of draw, drains SE; asc. over SE slope.
30.00	Top of spur, slopes E; desc. over NE slope.
31.00	Bottom of draw, drains NE; desc. along steep E slope.
38.50	Spur, slopes NE; desc. over NE slope.
39.31	Point for the ¼ sec. cor. of secs. 5 and 6, falls on steep sandstone ledge, where it is impossible to establish a permanent monument; there is no remaining evidence of the original corner.
39.94	Point selected for the witness ¼ sec. cor. of secs. 5 and 6.
	Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base to top, with brass cap mkd.
	<p style="text-align: center;">W C T 10 S R 24 E ¼ S 6 S 5 ↓ 1975</p>
	Desc. over NE slope.
43.00	Small wash in bottom of draw, drains SE; asc. over steep S slope.
52.00	Rim of draw, bears W and NE; over nearly level land.
60.00	Begin descent over NE slope.
62.50	Bottom of draw, drains E; asc. over S slope.
76.50	Top of ascent, bears E and W; desc. over gentle N slope.
78.87	The cor. of secs. 5, 6, 31 and 32, N. Bdy., heretofore described.

General Description

Township 10 South, Range 24 East, is situated about 2½ miles south of Bonanza, Utah. The elevation varies from 5,000 to 6,000 feet above sea level. The soil varies from loam to clay loam with exposed sandstone outcroppings scattered over most of the township.

The White River flows through the northern portion of the township in a westerly direction and Evacuation Creek, located in the eastern portion, flows north into the White River.

There has been mineral and gas exploration over most of the township with numerous dirt roads and jeep trails leading to drill holes, making most of the township accessible. The old Ignatio Stage Stop is located in section 2, southeast of the White River Bridge.

An average number of readings throughout the township gives a mean magnetic declination of 14°30' E.

CERTIFICATE OF SURVEY

298

(I) ~~(we)~~ Jerry L. Thomas, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 30th day of January, 1975, (I) ~~(we)~~ have resurveyed the South Boundary (Second Standard Parallel South), East, West and North Boundaries and the Subdivisional Lines in T. 10 S., R. 24 E.,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

December 13, 1976
(Date)

Jerry L. Thomas
(Cadastral Surveyor)
Supervisory

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Washington, D.C.
Denver, Colorado

The foregoing field notes of the resurvey of the South Boundary (Second Standard Parallel South) East, West and North Boundaries and the Subdivisional Lines in T. 10 S., R. 24 E., Salt Lake Meridian, Utah

executed by Jerry L. Thomas, Supervisory Cadastral Surveyor having been critically examined and found correct, are hereby approved.

JAN 18 1980
(Date)

J. Voorhees
(Chief, Division of Cadastral Survey)

Chief, Cadastral Survey Examination and Approval Staff
CERTIFICATE OF TRANSCRIPT

~~I Certify that the foregoing transcript of the field notes of the above described surveys in~~
~~is a true copy of the original field notes.~~

(Date)

(Chief, Division of Cadastral Survey)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
ORIGINAL

FIELD NOTES

OF THE

RETRACEMENT OF THE

UTAH-COLORADO STATE BOUNDARY LINE

FROM THE 199th TO 206th MILE CORNER,

AND THE

DEPENDENT RESURVEY OF THE

SECOND STANDARD PARALLEL SOUTH ALONG THE

SOUTH BOUNDARY OF TOWNSHIP 10 SOUTH, RANGE 25 EAST;

THE NORTH BOUNDARY AND SUBDIVISIONAL LINES

OF

TOWNSHIP 10 SOUTH, RANGE 25 EAST

Of the Salt Lake

Meridian,

In the State of Utah

EXECUTED BY

Glen B. Hatch Supervisory Cadastral Surveyor

Under special instructions dated January 30, 19 75, approved January 30, 1975,

_____, which provided for the surveys included under ~~XXXXXX~~ Group
Number 557, and assignment instructions dated May 7, 19 75.

Survey commenced May 12, 19 75

Survey completed August 15, 19 75

INDEX DIAGRAM

Township 10 S., Range 25 E.

13	14	15	16	17	18	
6	69 5	56 4	46 3	37 2	28 1	5
68	67	55	46	36	27	
7	66 8	54 9	45 10	35 11	26 12	4
66	65	53	45	35	25	
18	64 17	52 16	43 15	34 14	24 13	4
63	63	52	43	33	23	
19	62 20	51 21	42 22	32 23	22 24	3
61	60	50	41	31	22	
30	59 29	49 28	40 27	30 26	20 25	2
58	58	49	39	29	20	
31	57 32	48 33	38 34	28 35	19 36	2
6	7	9	9	11	12	

UTAH - COLORADO STATE BOUNDARY LINE

Township 10 South, Range 25 East, Salt Lake Meridian, Utah

CHAINS

The history of surveys of Township 10 South, Range 25 East, Salt Lake Meridian, Utah, is as follows:

The west mile on the north boundary was surveyed by Daniel G. Major in 1883. The east boundary (Utah-Colorado State Bdy.) was surveyed by Allen D. Wilson in 1885, re-traced by A. R. Talamantes and Harvey D. Heist in 1904, and resurveyed by John M. Tufts in 1936. The south boundary (Second Standard Parallel South), the north boundary, west boundary and subdivisional lines were surveyed by A. R. Talamantes and H. D. Heist in 1904.

The following field notes describe the dependent resurvey of the south and north boundaries and the subdivisional lines of Township 10 South, Range 25 East, and the re-tracement of the Utah-Colorado Boundary line from the 199th to 206th mile corner.

The resurvey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973 and Special Instructions for Group No. 557, Utah, dated January 30, 1975.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of lines were determined by reference to true meridians established on line by hour angle observations on Polaris and altitude observations on the sun. The lines were carried forward by sustained angulation being supplemented by other numerous hour angle observations on Polaris and altitude observations on the sun.

Distances were obtained using the electronic distant measuring device - Hewlett-Packard 3800A Distance Meter and an 8 chain steel tape.

The geographic position of the southeast corner of the township is at latitude $39^{\circ}53'54''$ N. and longitude $109^{\circ}02'59''$ W., as computed from section line ties to U.S.C. & G.S. triangulation station "G.L.O. Station No. 5" which is common with the standard corner of sections 33 and 34, T. 10 S., R. 25 E., of latitude $39^{\circ}53'53.417''$ N. and longitude $109^{\circ}05'45.922''$ W. as published by U.S.C. and GS.

The mean magnetic declination is $14^{\circ}30'$ E.

Retracement of the Utah-Colorado Boundary Line, on the East Bdy. of T. 10 S., R. 25 E., Salt Lake Meridian, Utah

(Retracing the survey executed by Allen D. Wilson in 1885, the 1904 retracement by Talamantes and Heist and the 1936 resurvey by John M. Tufts)

Beginning at the 199th mile post on the Utah-Colorado boundary, monumented with an iron post, 3 ins. diam., in a mound of stone to top, with brass cap mkd.

Retracement of the Utah-Colorado Boundary Line, on the East Bdy. of T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
	199M UTAH COLO 1936
	N. 0°08' W., on the 200th mile, over mountainous land, through scattering timber; desc. 280 ft. over general N slope.
32.00	Ravine, drains N. 65° W.; asc. 360 ft. over SW slope.
47.50	Top of ridge, bears N. 40° W. and S. 80° E.; desc. 300 ft. over N slope.
63.50	Point for the stan. closing cor. of Tps. 10 and 11 S., R. 25 E., Utah, hereinafter described; desc. 180 ft. over N slope.
70.00	Leave timber.
73.00	Wash, 40 lks. wide, 6 ft. deep, in Hells Hole Canyon, drains W.
74.50	Trail road in bottom of Hells Hole Canyon, curves N. 80° W. and N. 70° E.; asc. 80 ft. over S slope.
80.20	The 200th mile post, monumented with an iron post, 3 ins. diam., set in a mound of stone, 3½ ft. base, 3 ft. high, with brass cap mkd.
	200M UTAH COLO 1936
	from which the original bearing trees
	A cedar, 6 ins. diam., bears S. 85°30' E., 4½ lks. dist., mkd. 200M COLO BT.
	A cedar, 6 ins. diam., bears S. 65°30' W., 58 lks. dist., mkd. 200M UTAH BT.
	N. 0°08' W., on the 201st mile.
	Asc. 280 ft. over mountainous land on S slope.
7.00	Rim of Hells Hole Canyon, top of ledge, 30 ft. high, bears N. 85° E. and S. 85° W.; desc. 120 ft. over gentle NW slope.
45.60	The 201st mile post AP, monumented with an iron post, 3 ins. diam., protruding 12 ins. above the ground, with brass cap mkd.
	201 AP UTAH COLO 1936
	N. 0°10' W., beginning new measurement.
	Desc. 40 ft. on top of mesa.

Retracement of the Utah-Colorado Boundary Line, on the East Bdy. of T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
17.65	The closing cor. of secs. 25 and 36, T. 10 S., R. 25 E., hereinafter described; desc. 200 ft. over N slope, through scattering timber.
28.50	Bottom of draw, drains N. 50° W.; asc. 80 ft. over SW slope.
31.50	Point of spur, slopes W; desc. 40 ft. over NW slope.
43.78	Wash, drains irregularly S. 40° W.
44.29	The witness cor. for the 201st mile post, monumented with an iron post, 3 ins. diam., protruding 18 ins. above the ground and in a mound of stone, 3 ft. base, with brass cap mkd.
	<p>201M</p> <p>UTAH COLO</p> <p>W C</p> <p>1936</p>
	from which the original bearing trees
	A cedar, 8 ins. diam., bears N. 51°15' E., 31½ lks. dist., mkd. 201M COLO WC BT.
	A cedar, 6 ins. diam., bears S. 74°45' W., 31½ lks. dist., mkd. 201M UTAH WC BT.

	N. 0°09' W., beginning new measurement, on the 202nd mile.
	Asc. 100 ft. over SE slope.
6.10	Top of ledge, 15 ft. high, bears E and W; continue along nearly level land.
24.10	Asc. gradually 100 ft.
42.10	Asc. 380 ft. over steep and broken SE slope.
52.83	Point for the closing cor. of secs. 24 and 25, T. 10 S., R. 25 E., hereinafter described; asc. 80 ft.
55.10	Rim of bench, bears N. 85° E. and S. 85° W.
55.85	The 201M +65.46 AP, monumented with an iron post, 3 ins. diam., protruding 10 ins. above the ground, with brass cap mkd.
	<p>201M</p> <p>+65.46</p> <p>UTAH AP COLO</p> <p>1885</p> <p>1936</p>

	N. 0°08' W., beginning new measurement.
14.58	The 202nd mile post, monumented with an iron post, 3 ins. diam., protruding 10 ins. above ground, with brass cap mkd.

Retracement of the Utah-Colorado Boundary Line, on the East
Bdy. of T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	<div style="text-align: center;"> 202M UTAH COLO 1936 </div>
	N. 0°13' W., along the 203rd mile, over nearly level land.
11.50	Trail road on top of Weaver Ridge, bears W and S. 47° E.; desc. 80 ft. over N slope, enter dense timber.
21.50	Pipeline, bears N. 74° W. and S. 74° E.; desc. 260 ft. along steep E slope.
58.00	Bottom of Weaver Canyon, drains W. Leave timber, bears E and W.
59.00	Trail road, bears E and W; asc. 80 ft. over steep S slope.
63.29	Point for the closing cor. of secs. 13 and 24, T. 10 S., R. 25 E., hereinafter described; asc. 120 ft.
66.00	Top of ledge, 10 ft. high, bears E and W.; thence enter dense timber.
74.00	Low spur slopes W; desc. 50 ft. over NW slope.
80.27	The 203rd mile post, monumented with an iron post, 3 ins. diam., protruding 16 ins. above the ground, with brass cap mkd.
	<div style="text-align: center;"> 203M UTAH COLO 1936 </div> <p>The original bearing tree to the SE is dead and fallen. The original bearing tree to the SW is dead and rotted.</p>
	N. 0°13' W., on the 204th mile; over rolling bench land, through dense timber; desc. 40 ft. over NW slope.
2.50	Small draw, drains S. 45° W. from E; asc. 240 ft. over general S slope.
21.50	Trail road along top of ridge, curves S. 60° W. and S. 73° E.; desc. 280 ft. over N slope.
33.50	Wash, drains N. 40° W.; asc. 80 ft. along W slope, leave dense timber.
39.00	Top of ascent, slopes W; thence along W slope.
50.00	Desc. 100 ft. over NW slope.
64.15	Point for the closing cor. of secs. 12 and 13, T. 10 S., R. 25 E., hereinafter described; desc. 60 ft. over NW slope. Leave timber, bears NE and SW.
70.00	Wash, drains S. 48° W.; asc. 80 ft. over SE slope.
80.14	Point for the 204th mile post.

Retracement of the Utah-Colorado Boundary Line, on the East
Bdy. of T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
	<p>From which the witness 204th mile post bears West 0.23 chs. dist., monumented with an iron post, 3 ins. diam., in a mound of stone, 3 ft. base to top of brass cap, mkd.</p> <div style="text-align: center;"> <p>204 M</p> <p>UTAH COLO</p> <p>1936</p> </div>
	<p>N. 0°32' W., on the 205th mile, over mountainous land; asc. 200 ft. over steep SE slope.</p> <p>7.50 Top of narrow spur, slopes S. 40° W.; desc. 60 ft. over NW slope.</p> <p>13.00 End of descent, slopes west; asc. 60 ft. along W slope.</p> <p>24.00 Wash, drains S. 35° W.; asc. 70 ft. over SE slope, enter timber, bears NE and SW.</p> <p>31.00 Spur, slopes S. 45° W.; desc. 70 ft. over NW slope.</p> <p>38.50 Draw, drains S. 50° W.; asc. 100 ft. over SE slope.</p>
	<p>51.38 The 204M +51.16 AP, on ridge, bears S. 25° W. and N. 10° E., monumented with an iron post, 3 ins. diam., protruding 12 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>204M +51.16 AP</p> <p>UTAH COLO</p> <p>1885 1936</p> </div>
	<p>from which the original bearing trees</p> <p>A pinon, 7 ins. diam., bears N. 52½° E., 58 lks. dist., mkd. AP 204M +51.16 COLO BT. (Record, 66 lks.)</p> <p>A pinon, 14 ins. diam., bears N. 82 3/4° W., 84 lks. dist., mkd. AP 204M +51.16 UTAH BT. (Record, 79 lks.)</p>
	<p>N. 0°20' W., beginning new measurement; desc. 140 ft. along W slope.</p> <p>11.63 Point for the closing cor. of secs. 1 and 12, T. 10 S., R. 25 E., hereinafter described; desc. 80 ft. along West slope of ravine, draining N.</p> <p>19.00 Ravine, turns N. 30° W.; asc. 50 ft. along W slope.</p> <p>26.50 Spur, slopes W; desc. 80 ft. over NW slope.</p> <p>28.59 The 205th mile post, monumented with an iron post, 3 ins. diam., protruding 12 ins. above ground, with brass cap mkd.</p>

Retracement of the Utah-Colorado Boundary Line, on the East
Bdy. of T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

205M
|
UTAH COLO
|
1936

from which

A cedar, 12 ins. diam., bears N. 60° E., 30 lks
dist., with blaze mark but no visible scribe mks.

N. 0°25' W., on the 206th mile; over mountainous land
through scattering timber; desc. steep NW slope.

8.80 Draw, drains W; asc. 140 ft. over S slope.

9.00 Spur, slopes S. 70° W.; desc. 140 ft. along W slope.

43.50 Draw, drains W.

52.50 Spur, slopes W; desc. 120 ft. over NE slope.

62.89 Point for the closing cor. of Tps. 9 and 10 S., R. 25 E.,
hereinafter described.

80.28 The 206th mile post, monumented with an iron post, 3 ins.
diam., protruding 20 ins. above ground, in a mound of
stone to top, with brass cap mkd.

206M
|
UTAH COLO
|
1936

Dependent Resurvey of the Second Standard Parallel
South, on the S. Bdy. of T. 10 S., R. 25 E.,
Salt Lake Meridian, Utah

(Restoring the 1904 survey by
A. R. Talamantes and H. D. Heist)

From the stan. cor. of Tps. 10 S., Rs. 24 and 25 E.,
described in the field notes of the concurrent resurvey
of the S. bdy. of T. 10 S., R. 24 E.

N. 89°53' E., along the S. bdy. of sec. 31.

Over rocky land.

1.00 Bottom of draw, drains N; asc. 80 ft. over E slope.

5.50 Top of spur, slopes N; desc. 40 ft.

13.00 Bottom of wash, drains N. 40° E.

21.00 Spur, slopes N; desc. slightly.

25.00 Bend in wash, course N. 30° W. from N. 60° E.

28.00 Trail road, bears N. 60° W. and S. 60° E.; asc. 40 ft.
along N. slope.

Dependent Resurvey of the Second Standard Parallel South,
on the S. Bdy. of T. 10 S., R. 25 E., Salt Lake Mer., Utah

CHAINS	
40.08	<p>The stan. $\frac{1}{4}$ sec. cor. of sec. 31, monumented with a limestone, 24 x 8 x 6 ins., firmly set 6 ins. in the ground, with no visible marks, and with a mound of stone to the N, harmoniously related to existing original cors. and is accepted as the best available evidence of the original cor.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>SC T 10 S R 25 E <u> </u> $\frac{1}{4}$ S 31 <u> </u> 1975</p> </div> <p>Deposit unmkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. $89^{\circ}55'$ E., beginning new measurement.</p> <p>Asc. 80 ft. over NW slope.</p>
16.00	Top of spur, slopes N; desc. 40 ft. over NE slope.
29.00	Wash, drains N. 40° W.; asc. 120 ft. over SW slope.
39.96	<p>The stan. cor. of secs. 31 and 32, monumented with a sandstone, 20 x 8 x 8 ins., protruding 8 ins. above ground, marked SC on N face, 1 notch on W and 5 notches on the E edges.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>SC T 10 S R 25 E <u> </u> S 31 S 32 <u> </u> 1975</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p>
	<p>S. $89^{\circ}57'$ E., on the S. bdy. of sec. 32.</p> <p>Desc. 50 ft. over rocky E slope.</p>
2.50	Draw, course S; asc. 100 ft. over W slope.
8.12	<p>The closing cor. of secs. 4 and 5, T. 11 S., R. 25 E., monumented with a sandstone, 18 x 12 x 12 ins., protruding 10 ins. above ground, mkd. CC on the S face, 3 notches on the E and W edges.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Second Standard Parallel South,
on the S. Bdy. of T. 10 S., R. 25 E., Salt Lake Mer., Utah

CHAINS	
	<p>T 10 S R 25 E S 25 ----- S 5 S 4 C C T 11 S R 25 E 1975</p>
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, S of cor.
	Desc. slightly.
18.00	Bottom of hollow, course S. 75° W.; asc. 80 ft. over NW slope.
25.00	Top of spur, slopes S. 50° E.; desc. 100 ft. along small draw, course E.
34.00	Bottom of ravine, course S; asc. 80 ft. over E slope.
34.50	Underground pipeline, bears N. 5° W. and S. 5° E.
40.13	The stan. ¼ sec. cor. of sec. 32, monumented with a sandstone, 24 x 8 x 4 ins., protruding 8 ins. above ground, mkd. ¼SC on N face, with a mound of stone to N.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base to top, with brass cap mkd.
	<p>S C T 10 S R 25 E ¼ S 32 ----- 1975</p>
	Deposit the mkd. stone, in mound, alongside the iron post.

	N. 89°59' E., beginning new measurement.
	Asc. slightly.
3.00	Top of spur, slopes S; desc. 100 ft. over E slope.
14.00	Bottom of wash, drains S. 28° W.; asc. 220 ft. over W slope.
29.50	Top of spur, slopes N; desc. 80 ft. over NE slope.
33.50	Draw, drains N; asc. 80 ft. over W slope.
38.00	Spur, slopes N; desc. 40 ft. over NE slope.
39.97	The stan. cor. of secs. 32 and 33, monumented with a sandstone, 18 x 15 x 10 ins., protruding 12 ins. above ground, mkd. SC on the N with 2 notches on the W and 4 notches on the E faces, and with a mound of stone to the NW.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

Dependent Resurvey of the Second Standard Parallel South,
on the S. Bdy. of T. 10 S., R. 25 E., Salt Lake Mer., Utah

CHAINS	
	<p style="text-align: center;">S C T 10 S R 25 E <u>S 32 S 33</u> 1975</p> <p>Deposit the mkd. stone alongside the iron post.</p>
	<p>S. 89°54' E., on the S. bdy. of sec. 33.</p> <p>Descend slightly over rocky land.</p>
5.00	Bottom of hollow, course N. 35° W.; asc. 40 ft. over SW slope.
15.00	Improved road, State Route No. 45, curves N. 10° W. and S. 40° E.; asc. 160 ft. over NW slope.
40.02	<p>The stan. $\frac{1}{4}$ sec. cor. of sec. 33, monumented with a sandstone, 28 x 10 x 6 ins., protruding 10 ins. above ground, mkd. $\frac{1}{4}$SC, with a mound of stone to the N.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">S C T 10 S R 25 E <u>$\frac{1}{4}$ S 33</u> 1975</p> <p>Deposit the mkd. stone alongside the iron post.</p>
	<p>S. 89°56' E., beginning new measurement.</p> <p>Asc. 380 ft. along steep, rocky N slope.</p>
39.94	The stan. cor. of secs. 33 and 34, monumented with a brass tablet, set in concrete block, 12 ins. square, mkd.
	<p style="text-align: center;">S C T 10 S R 25 E <u>S 33 S 34</u> 1931</p> <p>from which an original bearing tree</p> <p style="padding-left: 40px;">A pinon, 10 ins. diam., bears N. 13° W., 75 lks. dist., mkd. SC T10S R25E S33 BT. (Record, 72 lks.)</p> <p>This cor. is common with U.S.C. and G.S. triangulation station "G.L.O. Station No. 5".</p>
	<p>S. 89°54' E., on the S. bdy. of sec. 34.</p> <p>Asc. 80 ft. along rocky N slope.</p>
2.25	Jeep trail, bears N. 65° E. and S. 88° W.
6.00	Spur, slopes S. 60° W.; desc. 140 ft. over SE slope.

310

Dependent Resurvey of the Second Standard Parallel South,
on the S. Bdy. of T. 10 S., R. 25 E., Salt Lake Mer., Utah

CHAINS	
14.00	Wash, drains S. 30° W.; asc. 100 ft. over NW slope, enter scattered juniper.
18.00	Spur, slopes S. 50° W.; desc. 50 ft. along S slope.
26.00	Wash, drains S. 50° W.; asc. 100 ft. over NW slope.
30.00	Spur, slopes S. 60° W.; desc. slightly.
35.50	Draw, drains S. 50° W.; asc. 80 ft. over W slope.
39.84	The stan. $\frac{1}{4}$ sec. cor. of sec. 34, monumented with a broken sandstone, 20 x 14 x 6 ins., (record, 14 x 10 x 5), protruding 8 ins. above ground, mkd. $\frac{1}{4}$ SC.
	At the corner point
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd.
	S C T 10 S R 25 E $\frac{1}{4}$ S 34 <hr/> 1975
	from which the original bearing trees
	A pinon, 10 ins. diam., bears N. 51° E., 110 lks. dist., mkd. SC $\frac{1}{4}$ SBT. (Record, 105 lks.)
	A pinon, 12 ins. diam., bears N. 28° W., 33 lks. dist., mkd. SC $\frac{1}{4}$ SBT. (Record, 30 lks.)
	Deposit the mkd. stone in mound of stone, alongside the iron post.

	S. 89°59' E., beginning new measurement.
0.40	Top of ridge, bears N. 45° E. and S. 45° W.; desc. 70 ft. over SE slope; enter heavy pinon and juniper.
7.00	Bottom of draw, drains S. 40° W.; asc. 80 ft. over W slope.
12.80	Spur, slopes S. 30° W.; thence over nearly level land.
30.00	Desc. 120 ft. over NE slope.
36.00	Bottom of draw, drains N; asc. 80 ft. over NW slope.
39.95	The stan. cor. of secs. 34 and 35, monumented with a sandstone, 24 x 9 x 4 ins., protruding 8 ins. above ground, plainly mkd. SC on the N face, 4 notches on the W and 2 notches on the E faces.
	At the corner point
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	S C T 10 S R 25 E S 34 S 35 <hr/> 1975

Dependent Resurvey of the Second Standard Parallel South,
on the S. Bdy. of T. 10 S., R. 25 E., Salt Lake Mer., Utah

CHAINS	
	<p>from which the original bearing trees</p> <p>A pinon, 6 ins. diam., bears N. 25° E., 24 lks. dist., mkd. SC T10S R25E S35 BT.</p> <p>A pinon, bears NW, dead and fallen.</p> <p>Deposit the mkd. stone alongside the iron post and rebuild mound of stone, 2½ ft. base, 1½ ft. high, N of cor.</p>
	<p>N. 89°58' E., on the S. bdy. of sec. 35.</p> <p>Asc. 80 ft. over rocky NW slope.</p>
5.00	Top of ridge, bears N and S; desc. 220 ft. over NE slope.
15.50	Draw, drains N. 30° E.; asc. slightly.
19.00	Spur, slopes N; desc. 60 ft. over NE slope.
23.00	Draw, drains N. 15° E.; asc. NW slope.
29.50	Spur, slopes N. 30° E.; desc. 120 ft. over NE slope.
35.50	Wash, drains N; asc. 40 ft. over NW slope.
39.87	<p>The stan. ¼ sec. cor. of sec. 35, monumented with a sandstone, 28 x 12 x 5 ins., protruding 12 ins. above ground, mkd. ¼SC on N face, and with a mound of stone to the N.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>S C</p> <p>T 10 S R 25 E</p> <p>¼ S 35</p> <hr style="width: 50px; margin: 0 auto;"/> <p>1975</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Rebuild mound of stone, 3 ft. base, 1½ ft. high, N of cor.</p>
	<p>S. 89°52' E., beginning new measurement.</p> <p>Asc. 40 ft. along N slope.</p>
7.50	Top of spur, slopes N; desc. 120 ft. over NE slope.
21.50	Draw, drains N. 40° E.; desc. 80 ft. over NE slope.
40.04	<p>The stan. cor. of secs. 35 and 36, monumented with a sandstone, 24 x 14 x 4 ins., protruding 12 ins. above ground, mkd. SC on the N face, 5 notches on the W and 1 notch on the E faces, and with a mound of stone to the N.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.</p>

Dependent Resurvey of the Second Standard Parallel South,
on the S. Bdy. of T. 10 S., R. 25 E.; Salt Lake Mer., Utah

CHAINS

S C
T 10 S R 25 E
S 35 | S 36
1975

Deposit the mkd. stone alongside the iron post.

S. 89°56' E., on the S. bdy. of sec. 36.

Ascend slightly over rocky land.

2.00 Rim of mesa, bears N. 35° E. and S. 35° W.; desc. abruptly
280 ft. over SE slope.

14.00 Bottom of wash, drains N; asc. 140 ft. over NW slope.

36.90 Intersect the Utah-Colorado boundary line.

Point for the stan. closing. cor. of Tps. 10 and 11 S.,
R. 25 E.

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins.
in the ground, in a collar of stone, with brass cap mkd.

SC
T 10 S
R 25 E |
C S 36 |
C S 1 |
T 11 S R 25 E
1975

From this point, the 200th mile post, on the Utah-Colorado
State Boundary, bears N. 0°08' W., 16.70 chs. dist., monu-
mented with an iron post heretofore described.

From this same point, the 199th mile post, bears
S. 0°08' E., 63.50 chs. dist., monumented with an iron
post, 3 ins. diam., heretofore described.

From the same point, the original stan. closing cor. of
Tps. 10 and 11 S., R. 25 E., bears S. 89°56' E., 0.11 chs.
dist., monumented with a sandstone, 12 x 12 x 4 ins.,
above ground, plainly mkd. SC on the N face, CC on the W
face, and 6 notches on the W edge. Add the marks "AM" on
the S face

from which the original bearing trees

A pinon, 8 ins. diam., bears N. 88°30' W., 19 lks.
dist., mkd. T10S R25E S36 BT.

A pinon, 8 ins. diam., bears N. 18° W., 39 lks.
dist., mkd. T10S R25E S36 BT.

Dependent Resurvey of the N. Bdy.,
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

(Restoring the 1904 survey by
A. R. Talamantes and H. D. Heist)

Dependent Resurvey of the North Boundary,
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
	From the cor. of Tps. 9 and 10 S., Rs. 24 and 25 E., described in the field notes of the concurrent resurvey of T. 10 S., R. 24 E.
	East, bet. secs. 6 and 31.
	Desc. 50 ft. over rocky land.
4.00	Draw, drains S; asc. 90 ft. over NW slope.
12.00	Ridge, bears N and S; desc. 80 ft. over E slope.
16.00	Trail road, bears N and S.
17.00	Wash, drains S.
17.50	Pipeline, bears N. 12° W. and S. 12° E.; asc. 80 ft. over NW slope.
29.00	Spur, slopes S. 40° W.; desc. 50 ft. over SE slope.
37.00	Wash, drains S. 50° W.; asc. 40 ft. over NW slope.
39.93	The $\frac{1}{4}$ sec. cor. of secs. 6 and 31, monumented with a sandstone, 10 x 6 x 6 ins., (record, 16 x 8 x 4), firmly set 6 ins. in the ground, and in a mound of stone, harmoniously related to existing original cors. and is accepted as the best existing evidence of the original cor.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd.
	T 9 S R 25 E S 31 $\frac{1}{4}$ ——— S 6 T 10 S 1975
	Deposit the unmkd. stone alongside the iron post.

	N. 89°55' E., beginning new measurement.
	Ascend 100 ft. over rocky W slope.
13.00	Spur, slopes S. 45° W.; desc. 40 ft. over SE slope.
20.50	Draw, drains S; asc. 40 ft. over W slope.
23.50	Spur, slopes S; desc. 60 ft. over E slope.
32.70	Wash, drains S. 10° W.; asc. 60 ft. over W slope.
39.00	Top of ridge, bears N and S.
40.04	The cor. of secs. 5, 6, 31 and 32, monumented with a sandstone, 15 x 12 x 5 ins., protruding 10 ins. above ground, mkd. 5 notches on the E and 1 notch on the W edge.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap mkd.

314

Dependent Resurvey of the North Boundary,
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	T 9 S R 25 E S 31 S 32 S 6 S 5 T 10 S R 25 E 1975
	Deposit the mkd. stone alongside the iron post.
	N. 89°54' E., bet. secs. 5 and 32.
	Desc. 20 ft. over rocky E slope.
3.00	Trail road, bears N and S; thence over rolling land.
26.00	Edge of mesa, bears N. 30° W. and S. 30° E.; desc. 400 ft. over precipitous E slope.
36.20	Pipeline, bears N. 48° W. and S. 48° E.
36.70	Enter wash, drains S. 50° E.
39.30	Leave wash; asc. 60 ft. over E slope.
40.04	Point for the ¼ sec. cor. of secs. 5 and 32, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, and in a mound of stone, 3½ ft. base to top, with brass cap mkd.
	T 9 S R 25 E S 32 ¼ ——— S 5 T 10 S R 25 E 1975
	Asc. 100 ft. over rocky W slope.
43.00	Spur, slopes SW; top of ledge, 50 ft. high, bears N. 50° E. and S. 50° W.; desc. abruptly 200 ft. over precipitous SE slope.
48.00	Right bank of White River, course S. 12° W. from N. 35° E.
49.33	Intersect line 11-1 Pantaloon Allotment No. 270, No. 23.
	From this point cor. No. 11 bears N. 55°23' E., 30.12 chs. dist., monumented with a sandstone, 16 x 12 x 4 ins., above ground, mkd. P COR 11 on S face, with a mound of stone S of cor.
	The 4 mile cor. was searched for and not found.
	From the same point of intersection, point for cor. No. 1, bears S. 55°23' W., 38.95 chs. dist. determined from original B0, falls in White River and is not monumented.
	from which
	A cross (X) on ledge, 6 ft. high, bears N. 46°30' W., 22.2 ft. dist.
	The 4½ mile cor. was searched for and not found.
51.00	Left bank of the White River, bears N. 40° E. and S. 40° W.; asc. 40 ft.

Dependent Resurvey of the North Boundary,
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS						
64.03	<p>Intersect line 4-5 Pantaloon Allotment No. 270, No. 23, at a point from which cor. No. 4 bears S. 66°48' W., 1.12 chs. dist., monumented with a sandstone, in place, 22 x 18 x 5 ins. above ground, mkd. +P COR NO4.</p> <p>From the same point of intersection, cor. No. 5, bears N. 66°48' E., 10.97 chs. dist., monumented with a mound of stone, only, but is harmoniously related to existing original cors. on this allotment, and is accepted as the best available evidence of the original corner position.</p> <p>64.20 Bend in underground pipeline, bears S. 25° E. and S. 53° W.; desc. 20 ft.</p> <p>67.00 Mouth of Weaver Canyon, course from S. 35° E.; asc. 140 ft. over NW slope.</p> <p>80.08 The cor. of secs. 4, 5, 32 and 33, monumented with a limestone, 24 x 15 x 4 ins., protruding 12 ins. above ground, mkd. with 4 notches on the E and 2 notches on the W edges, with a mound of stone to the W.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T 9 S R 25 E</td></tr> <tr><td> S 32 S 33</td></tr> <tr><td> S 5 S 4</td></tr> <tr><td>T 10 S R 25 E</td></tr> <tr><td> 1975</td></tr> </table> </div> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Rebuild mound of stone, 2 ft. base, 1½ ft. high, W of cor.</p>	T 9 S R 25 E	S 32 S 33	S 5 S 4	T 10 S R 25 E	1975
T 9 S R 25 E						
S 32 S 33						
S 5 S 4						
T 10 S R 25 E						
1975						
	<p>S. 89°59' E., bet. secs. 4 and 33.</p> <p>Asc. 120 ft. over rocky NW slope.</p>					
6.00	Spur, slopes N; desc. 100 ft. over NE slope.					
10.00	Draw, drains N. 20° W.; asc. 300 ft. over E slope.					
20.50	Spur, slopes N. 60° W.; desc. 160 ft. along steep N slope.					
39.87	<p>The ¼ sec. cor. of secs. 4 and 33, monumented with a sandstone, 20 x 12 x 3 ins., protruding 10 ins. above ground, mkd. ¼ on N face, with small mound of stone to the N.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T 9 S R 25 E</td></tr> <tr><td> ¼ S 33</td></tr> <tr><td> S 4</td></tr> <tr><td>T 10 S R 25 E</td></tr> <tr><td> 1975</td></tr> </table> </div> <p>Deposit the mkd. stone alongside the iron post.</p> <p>S. 89°57' E., beginning new measurement.</p>	T 9 S R 25 E	¼ S 33	S 4	T 10 S R 25 E	1975
T 9 S R 25 E						
¼ S 33						
S 4						
T 10 S R 25 E						
1975						

Dependent Resurvey of the North Boundary,
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
	Desc. 120 ft. over steep NE slope.
4.50	Wash, drains N; asc. 50 ft. along N slope.
12.00	Top of ascent, slopes N; desc. 160 ft. along steep N slope.
39.99	The cor. of secs. 3, 4, 33 and 34, monumented with a limestone, 20 x 15 x 4 ins., protruding 10 ins. above ground, mkd. with 3 notches on the E and W edges, and with a mound of stone alongside.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	<div style="text-align: center;"> <p>T 9 S R 25 E S 33 S 34 S 4 S 3 T 10 S R 25 E 1975</p> </div>
	Deposit the mkd. stone alongside the iron post.
	East, bet. secs. 3 and 34.
	Ascend 140 ft. over rocky NW slope.
17.00	Spur, slopes N; desc. 50 ft. over E slope.
20.50	Draw, drains N. 40° W.; asc. 90 ft. over W slope.
23.50	Spur, slopes N. 30° W.; desc. 40 ft. over NE slope.
25.50	Wash, drains N. 20° W.; asc. 300 ft. over steep NW slope.
40.05	Point for the ¼ sec. cor. of secs. 3 and 34, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	<div style="text-align: center;"> <p>T 9 S R 25 E S 34 ¼ S 3 T 10 S R 25 E 1975</p> </div>
	Asc. 60 ft. over NW slope.
42.60	Spur, slopes N; desc. 120 ft. over steep E slope.
47.50	Wash, drains N; asc. 320 ft. over steep W slope.
56.50	Spur, slopes N; desc. 400 ft. over steep E slope.
67.50	Wash, drains N; asc. 180 ft. over steep W slope.
75.50	Spur, slopes N; desc. 120 ft. over E slope.
80.10	The cor. of secs. 2, 3, 34 and 35, monumented with a sandstone, 20 x 12 x 3 ins., protruding 12 ins. above ground, mkd. with 4 notches on the W and 2 notches on the E edges, with a mound of stone to the W.

Dependent Resurvey of the North Boundary,
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base to top, with brass cap mkd.

T 9 S R 25 E
S 34 | S 35
S 3 | S 2
T 10 S R 25 E
1975

Deposit the mkd. stone alongside the iron post.

S. 89°40' E., bet. secs. 2 and 35.

Desc. 50 ft. over rocky NE slope.

- 4.50 Bottom of Cripple Horse Canyon, drains N. 20° W.; asc. 260 ft. over steep W slope.
- 18.00 Spur, slopes S; thence desc. 40 ft. along rocky S slope.
- 26.00 Head of draw, drains S; asc. 40 ft. along S slope.
- 35.00 Top of ascent, slopes S; desc. over SE slope.
- 39.75 Draw, drains S.
- 40.02 The ¼ sec. cor. of secs. 2 and 35, monumented with a broken sandstone, 32 x 8 x 3 ins., protruding 8 ins. above ground, and dimly mkd. ¼.
- At the corner point
- Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base to top, with brass cap mkd.
- T 9 S R 25 E
S 35
¼ | S 2
T 10 S R 25 E
1975
- Deposit the mkd. stone alongside the iron post.
- N. 89°37' E., beginning new measurement.
- Asc. 600 ft. over broken and precipitous SW slope.
- 30.00 Enter scattering juniper and pinon.
- 35.00 Top of ridge, bears N and S. 20° E.; desc. 40 ft. over NE slope.
- 40.06 The cor. of secs. 1, 2, 35 and 36, monumented with a sandstone, 24 x 8 x 4 ins., protruding 8 ins. above ground, mkd. with 5 notches on the W and 1 notch on the E edges, and with a mound of stone to the W.
- from which the original bearing trees:

Dependent Resurvey of the North Boundary,
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

A cedar, 12 ins. diam., bears N. 71° E., 77 lks.
dist., mkd. T9S R25E S36 BT.

A pinon, 6 ins. diam., bears S. 11° E., 72 lks
dist., mkd. T10S R25E S1 BT.

A cedar, 10 ins. diam., bears S. 20° W., 96 lks.
dist., mkd. T10S R25E S2 BT.

A cedar, 6 ins. diam., bears N. 65° W., 36 lks.
dist., mkd. T9S R25E S35 BT.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins.
in the ground to bedrock, and in a mound of stone, 3 ft.
base to top, with brass cap mkd.

T 9 S R 25 E
S 35 S 36
S 2 S 1
T 10 S R 25 E
1975

Deposit the mkd. stone alongside the iron post.

N. 89°54' E., bet. secs. 1 and 36.

Desc. 60 ft. over rocky NE slope.

4.00 Draw, drains N. 35° E.; asc. slightly.

7.00 Point of spur, slopes N; desc. slightly.

10.00 Draw, drains N. 60° E.; asc. 140 ft. over NW slope.

26.00 Top of ridge, bears N and S; desc. 60 ft. over E slope.

34.32 Intersect the Utah-Colorado State Boundary.

Point for the closing cor. of Tps. 9 and 10 S., R. 25 E.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, and in a collar of stone, with brass cap
mkd.

T 9 S
R 25 E
C S 36
C S 1
T 10 S
R 25 E
1975

From this point, the 206th mile post, on the Utah-Colorado
State Boundary, bears N. 0°25' W., 17.39 chs. dist.,
monumented with an iron post, 3 ins. diam., heretofore
described.

From the same point, the 205th mile post, bears
S. 0°25' E., 62.89 chs. dist., monumented with an iron
post, 3 ins. diam., heretofore described.

Dependent Resurvey of the North Boundary,
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
	<p>From the same point, the original closing cor. of Tps. 9 and 10 S., R. 25 E., bears N. 89°54' E., 1.33 chs. dist., monumented with a sandstone, 15 x 13 x 7 ins., mkd. UCC on the W, and 6 notches on the N and S edges. Add the marks "AM" to top of rock.</p> <p>from which the original bearing tree</p> <p>A cedar, 10 ins. diam., bears N. 40° W., 37 lks. dist., mkd. T9S R25E S36 BT.</p>
	<p>Dependent Resurvey of the Subdivisional Lines of T. 10 S., R. 25 E., Salt Lake Meridian, Utah</p>
	<p>(Restoring the 1904 survey by A. R. Talamantes and H. D. Heist)</p> <hr/> <p>From the stan. cor. of secs. 35 and 36, on the S. bdy. of the Tp., heretofore described.</p> <p>N. 0°25' E., bet. secs. 35 and 36.</p> <p>Desc. 320 ft. over NE slope.</p>
29.00	<p>Base of descent, bears N. 35° W. and S. 35° E.; enter Hells Hole Canyon.</p>
41.10	<p>The ¼ sec. cor. of secs. 35 and 36, monumented with a sandstone, 24 x 12 x 3 ins., protruding 12 ins. above ground, mkd. ¼ on the W face, and in a mound of stone.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 10 S R 25 E</p> <p> </p> <p> ¼</p> <p> </p> <p> S 35 S 36</p> <p> </p> <p> 1975</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.</p> <hr/> <p>N. 0°08' W., beginning new measurement.</p>
8.00	<p>Trail road, bears N. 25° W. and S. 25° E.</p>
13.00	<p>Wash, in Hells Hole Canyon, drains N. 20° W.</p>
27.00	<p>Asc. 160 ft. over rocky SW slope.</p>
36.00	<p>Spur, slopes N. 50° W.; desc. 80 ft. over N slope.</p>
38.91	<p>The cor. of secs. 25, 26, 35 and 36, monumented with a sandstone, 28 x 15 x 5 ins., protruding 15 ins. above ground, mkd. with 1 notch on the S and E edges, and with a mound of stone alongside.</p> <p>from which the only remaining original bearing tree</p>

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

A cedar, 12 ins. diam., bears S. 54° E., 39 lks.
dist., mkd. T10S R25E S36 BT.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, and in a collar of stone, with brass cap
mkd.

T 10 S R 25 E
S 26 S 25
S 35 S 36
1975

S. 89°47' E., bet. secs. 25 and 36.

Asc. 40 ft. along rocky N slope, through juniper and
pinon.

5.00 Trail road, bears N. 78° W. and S. 78° E.

13.00 Same trail road, bears N. 85° E. and S. 85° W.; asc. 80
ft. over NE slope.

16.00 Same trail road, curves S. 75° W. from N.

25.00 Top of ascent, leave timber; over sagebrush flat.

28.50 North end of abandoned landing strip, bears S. 19° W.

36.56 Intersect the Utah-Colorado State Boundary at the closing
cor. of secs. 25 and 36, monumented with a sandstone,
24 x 9 x 4 ins., protruding 8 ins. above ground, mkd. CC
on W face, 1 notch on S and 5 notches on N edges.

from which the original bearing tree

A cedar, 6 ins. diam., bears N. 48° W., 89 lks.
dist., mkd. T10S R25E S25 BT.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 10 S
R 25 E
C S 25
C S 36
1975

Deposit the mkd. stone alongside the iron post.

From this point, the witness 201st mile post, on the
Utah-Colorado State Boundary, bears N. 0°10' W., 26.64
chs. dist., monumented with an iron post, 3 ins. diam.,
heretofore described.

From the same point, the 201st mile post AP, on Utah-
Colorado State Boundary, bears S. 0°10' E., 17.65 chs.
dist., monumented with an iron post, 3 ins. diam.,
heretofore described.

From the cor. of secs. 25, 26, 35 and 36.

N. 0°07' E., bet. secs. 25 and 26.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
	Desc. 160 ft. over rocky N slope, through dense timber.
1.50	Trail road, bears E and W.
6.50	Wash, drains W; asc. 200 ft. over SE slope.
28.00	Top of spur, slopes S. 60° W.; desc. 120 ft. over NE slope. Leave timber, bears E and W.
34.00	Draw, drains S. 78° W.; asc. 80 ft. over SE slope.
40.87	The $\frac{1}{4}$ sec. cor. of secs. 25 and 26, monumented with a sandstone, 15 x 10 x 4 ins., protruding 10 ins. above ground, mkd. $\frac{1}{4}$ on W face, and with a mound of stone to the N.
	At the corner point
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<pre> T 10 S R 25 E 1/4 S 26 S 25 1975 </pre>
	Deposit the mkd. stone alongside the iron post.
	Rebuild mound of stone, 3 ft. base, 2 ft. high, W of cor.

	N. 0°10' E., beginning new measurement.
	Asc. 80 ft. along spur.
9.00	Spur, slopes S from E; desc. 150 ft. over NW slope.
17.00	Spur, slopes N. 65° W.
20.50	Draw, drains N. 65° W.; asc. 100 ft. over SW slope.
31.00	Top of ascent, slopes W; desc. 80 ft. over NW slope.
38.00	Wash, drains S. 75° W.; asc. 40 ft. over S slope.
39.05	The cor. of secs. 23, 24, 25 and 26, monumented with a sandstone, 24 x 14 x 4 ins., firmly set 10 ins. in the ground, mkd. 2 notches on the S and 1 on the E edges, with a mound of stone to the W.
	At the corner point
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<pre> T 10 S R 25 E S 23 S 24 S 26 S 25 1975 </pre>
	Deposit the mkd. stone alongside the iron post.
	Rebuild mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W of cor.

322

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS																			
	S. 89°04' E., bet. secs. 24 and 25.																		
	Desc. slightly over rocky land.																		
3.00	Wash, drains S. 80° W.; asc. 600 ft. over steep W slope through scattering juniper and pinon.																		
29.00	Top of ridge, bears N. 55° E. and S. 55° W.; desc. 80 ft. over broken SE slope.																		
36.14	Intersect the Utah-Colorado State Boundary.																		
	Point for the closing cor. of secs. 24 and 25, at proportionate dist.; there is no remaining evidence of the original cor.																		
	Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.																		
	<table style="margin-left: auto; margin-right: auto;"> <tr><td></td><td>T 10 S</td><td></td></tr> <tr><td></td><td>R 25 E</td><td></td></tr> <tr><td>C</td><td>S 24</td><td> </td></tr> <tr><td>C</td><td>S 25</td><td> </td></tr> <tr><td></td><td>1975</td><td></td></tr> </table>		T 10 S			R 25 E		C	S 24		C	S 25			1975				
	T 10 S																		
	R 25 E																		
C	S 24																		
C	S 25																		
	1975																		
	From this point, the 201+65.46 mile post A.P., on the Utah-Colorado State Bdy., bears N. 0°09' W., 3.02 chs. dist., monumented with an iron post, 3 ins. diam., heretofore described.																		
	From the same point, the witness 201st mile post, on the Utah-Colorado State Boundary, bears S. 0°09' E., 52.83 chs. dist., monumented with an iron post, 3 ins. diam., heretofore described.																		
	From the cor. of secs. 23, 24, 25 and 26.																		
	N. 0°12' W., bet. secs. 23 and 24.																		
	Ascend 500 ft. over rocky SE slope.																		
17.50	Top of ridge, bears N. 50° E. and S. 50° W.; desc. 50 ft. through scattering juniper and pinon, over NW slope.																		
23.00	Draw, drains W; asc. 100 ft. over S slope.																		
30.00	Spur, slopes S. 50° W.; desc. 60 ft. over NW slope.																		
40.39	The ¼ sec. cor. of secs. 23 and 24, monumented with a sandstone, 24 x 10 x 3 ins., protruding 10 ins. above ground, mkd. ¼ on W face.																		
	At the corner point																		
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.																		
	<table style="margin-left: auto; margin-right: auto;"> <tr><td></td><td>T 10 S R 25 E</td><td></td></tr> <tr><td></td><td>¼</td><td></td></tr> <tr><td></td><td> </td><td></td></tr> <tr><td></td><td>S 23</td><td> S 24</td></tr> <tr><td></td><td> </td><td></td></tr> <tr><td></td><td>1975</td><td></td></tr> </table>		T 10 S R 25 E			¼						S 23	S 24					1975	
	T 10 S R 25 E																		
	¼																		
	S 23	S 24																	
	1975																		
	Deposit the mkd. stone alongside the iron post.																		

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

- N. 0°03' E., beginning new measurement.
- 2.00 Trail road, bears N. 80° W. and S. 80° E.; desc. 240 ft. over N slope.
- 36.00 Underground pipeline, bears N. 85° W. and curves S. 45° E.; desc. 40 ft. over N slope.
- 39.83 The cor. of secs. 13, 14, 23 and 24, monumented with a sandstone, 24 x 16 x 5 ins., (record, 18 x 15 x 3), firmly set 10 ins. in the ground, mkd. 1 notch on the E and 3 notches on the S edges.
- from which the original bearing trees
- A cedar, 12 ins. diam., bears N. 68° E., 22 lks. dist., mkd. T10S R25E S13 BT.
 - A cedar, 6 ins. diam., bears S. 39° E., 39 lks. dist., mkd. T10S R25E S24 BT.
 - A cedar, 10 ins. diam., bears S. 43° W., 28 lks. dist., mkd. T10S R25E S23 BT. (Record, 30 lks.)
 - A pinon, 16 ins. diam., bears N. 55° W., 88 lks. dist., mkd. T10S R25E S14 BT. (Record, 80 lks.)
- At the corner point
- Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
- | | |
|---------------|------|
| T 10 S R 25 E | |
| S 14 | S 13 |
| S 23 | S 24 |
| 1975 | |
- Deposit the mkd. stone alongside the iron post and raise a mound of stone, 2 ft. base, 1 ft. high, W of cor.
-
- East, bet. secs 13 and 24.
- Ascend 60 ft. along rocky N slope, through heavy juniper and pinon.
- 18.00 Spur, slopes N; desc. 60 ft. over NE slope.
- 23.00 Trail road, in bottom of Weaver Canyon, curves N. 40° W. and S. 70° E.; canyon drains N. 40° W; asc. 160 ft. over SW slope.
- 36.02 Intersect the Utah-Colorado State Boundary.
- Point for the closing cor. of secs. 13 and 24.
- Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a mound of stone, 3½ ft. base to top, with brass cap mkd.
- | | |
|--------|------|
| T 10 S | |
| R 25 E | |
| C | S 13 |
| C | S 24 |
| 1975 | |

324

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

From this point, the 203rd mile post, on the Utah-Colorado State Boundary, bears N. $0^{\circ}13'$ W., 16.98 chs. dist., monumented with an iron post, 3 ins. diam., heretofore described.

From the same point, the 202nd mile post, on the Utah-Colorado State Boundary, bears S. $0^{\circ}13'$ E., 63.29 chs. dist., monumented with an iron post, 3 ins. diam., heretofore described.

From the same point, the original cor. of secs. 13 and 24, monumented with a sandstone, 24 x 14 x 5 ins., protruding 12 ins. above ground, mkd. C on the E, U CC on the W, and 3 notches on the N and S faces, bears East, 0.65 chs. dist. Add the marks "AM" on the E face.

From the cor. of secs. 13, 14, 23 and 24.

N. $0^{\circ}58'$ E., bet. secs. 13 and 14.

Desc. 60 ft. over N slope.

4.00 Trail road, bears E and W.

5.00 Wash, in Weaver Canyon, drains W; asc. 140 ft. over SW slope.

10.00 Spur, slopes S. 80° W.; desc. 40 ft. over NW slope.

12.00 Draw, drains S. 70° W.; asc. 240 ft. over S slope.

26.50 Spur, slopes S. 35° W.; desc. 160 ft. over NW slope.

36.00 Draw, drains W; asc. 60 ft. over S slope.

40.00 Spur, slopes W; desc. 20 ft. over NW slope.

41.80 The $\frac{1}{4}$ sec. cor. of secs. 13 and 14, monumented with a sandstone, 20 x 6 x 6 ins., protruding 6 ins. above ground, mkd. $\frac{1}{4}$ on W face.

from which the original bearing trees

A pinon, 12 ins. diam., bears N. 43° E., 57 lks. dist., mkd. $\frac{1}{4}$ S13 BT.

A pinon, 12 ins. diam., bears S. 40° W., 6 lks. dist., mkd. $\frac{1}{4}$ S14 BT. (Record, 5 lks.)

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 10 S R 25 E

$\frac{1}{4}$
|
S 14 | S 13
|
1975

Deposit the mkd. stone alongside the iron post.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
	North, beginning new measurement.
	Desc. 40 ft. over rocky NW slope.
4.00	Wash, drains S. 55° W.; asc. 200 ft. over SE slope.
10.50	Spur, slopes S. 40° W.; asc. 40 ft. along W slope.
22.00	Top of ridge, curves W and S. 65° E.; desc. 280 ft. over NE changing to NE slope.
39.27	The cor. of secs. 11, 12, 13 and 14, monumented with a sandstone, 15 x 10 x 4 ins., protruding 10 ins. above ground, mkd. 4 notches on the S and 1 notch on the E edges.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T 10 S R 25 E S 11 S 12 S 14 S 13 1975
	Deposit the mkd. stone alongside the iron post.
	S. 89°58' E., bet. secs. 12 and 13.
	Desc. 30 ft. over E slope.
1.50	Wash, drains N; asc. 110 ft. over W slope.
8.00	Spur, slopes N.
9.00	Trail road, curves S and N. 80° E.; desc. 100 ft. over NE slope.
24.00	Wash, drains N; asc. 80 ft. over NW slope.
34.96	Intersect the Utah-Colorado State Boundary.
	Point for the closing cor. of secs. 12 and 13.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 10 S R 25 E C S 12 C S 13 1975
	From this point, the 204th mile post, on the Utah-Colorado State Boundary, bears N. 0°13' W., 15.99 chs. dist., monumented with an iron post, 3 ins. diam., heretofore described.
	From the same point, the 203rd mile post, on the Utah-Colorado State Boundary, bears S. 0°13' E., 64.15 chs. dist., monumented with an iron post, 3 ins. diam., heretofore described.

326

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
	<p>From the same point, the original closing cor. of secs. 12 and 13, bears S. 89°58' E., 1.05 chs. dist., monumented with a sandstone, 20 x 6 x 6 ins., protruding 6 ins. above ground, mkd. CC on the W face. Add the marks "AM" to E face.</p> <p>from which the remaining original bearing tree</p> <p>A pinon, 6 ins. diam., bears S. 36° W., 33 lks. dist., mkd. T10S R25E S13 BT.</p>
	<p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>N. 0°06' W., bet. secs. 11 and 12.</p> <p>Desc. 100 ft. along E changing to NE slope.</p>
13.50	Wash, drains N. 50° W.; asc. 80 ft. over SW slope.
23.00	Top of ascent, slopes W; desc. 60 ft. over NW slope.
34.00	Wash, drains S. 25° W.; asc. 20 ft. over SE slope.
39.23	<p>The ¼ sec. cor. of secs. 11 and 12, monumented with a weathered and unmarked limestone, 18 x 14 x 4 ins., protruding 12 ins. above ground, with a mound of stone to the W, harmoniously related to existing original cors. and is accepted as the best available evidence of the original cor.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 10 S R 25 E</p> <p>¼</p> <p>S 11 S 12</p> <p>1975</p> </div> <p>Deposit the unmkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1°06' W., beginning new measurement.</p> <p>Asc. 160 ft. over SE slope.</p>
10.00	Spur, slopes E; desc. 40 ft. over NE slope.
13.00	Draw, drains S. 55° E.; asc. 200 ft. over rocky S slope.
20.00	Top of ridge, bears N. 60° E. and S. 60° W.; desc. 80 ft. along W slope.
33.00	Wash, drains N. 70° W.; asc. 40 ft. over SW slope.
37.00	Spur, slopes N; desc. 40 ft. over N slope.
39.70	<p>The cor. of secs. 1, 2, 11 and 12, monumented with a limestone, 18 x 12 x 4 ins., protruding 12 ins. above ground, mkd. with 5 notches on the S and 1 notch on the E edges.</p> <p>from which the original bearing trees</p>

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

A cedar, 12 ins. diam., bears N. 83° E., 20 lks. dist., mkd. T10S R25E S1 BT.

A pinon, 10 ins. diam., bears S. 53° E., 47 lks. dist., mkd. T10S R25E S12 BT.

A pinon, 8 ins. diam., bears S. 24° W., 11 lks. dist., mkd. T10S R25E S11 BT.

A cedar, 5 ins. diam., bears N. 61° W., 10 lks. dist., mkd. T10S R25E S2 BT.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 10 S R 25 E	
S 2	S 1
S 11	S 12
1975	

Deposit the mkd. stone alongside the iron post.

N. 89°56' E., bet. secs. 1 and 12.

Asc. 120 ft. over NW slope, through heavy juniper and pinon.

13.00 Ridge, bears N and S; desc. 80 ft. over NE slope.

18.00 Draw, drains N. 20° E.; asc. 50 ft. over NW slope.

23.00 Spur, slopes N; desc. 50 ft. over E slope.

25.00 Draw, drains N; asc. 40 ft. over NW slope.

30.00 Spur, slopes N; desc. 40 ft. over NE slope.

35.21 Intersect the Utah-Colorado State Boundary.

Point for the closing cor. of secs. 1 and 12.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 10 S	
R 25 E	
C S 1	
C S 12	
1975	

From this point, the 205th mile post, on the Utah-Colorado State Bdy., bears N. 0°20' W., 16.96 chs. dist., monumented with an iron post, 3 ins. diam., heretofore described.

From the same point, the 204+51.16 A.P., on the Utah-Colorado State Bdy., bears S. 0°20' E., 11.63 chs. dist., monumented with an iron post, 3 ins. diam., heretofore described.

From the same point, the original closing cor. of secs. 1 and 12, bears N. 89°56' E., 0.11 chs. dist., monumented with a sandstone, 15 x 12 x 4 ins., above ground, mkd. CC on W faces. Add the marks "AM" on the E face.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

from which the remaining original bearing tree

A pinon, 8 ins. diam., bears S. 71° W., 17 lks.
dist., mkd. T10S R25E S12 BT.

From the cor. of secs. 1, 2, 11 and 12, heretofore
described.

N. 0°17' E., bet. secs. 1 and 2.

Desc. 160 ft. over NW slope.

6.50 Draw, drains W; asc. 170 ft. over S slope.

12.00 Spur, slopes S. 80° W.; desc. 50 ft. over NW slope.

16.00 Draw, drains W; asc. 40 ft. over S slope.

20.00 Spur, slopes W; desc. 50 ft. over NW slope.

25.00 Draw, drains W; asc. 40 ft. over SW slope.

31.00 Spur, slopes N. 55° W.; desc. 80 ft. along W slope.

38.22 Point for the ¼ sec. cor. of secs. 1 and 2, at record
bearing and dist. from the remaining original bearing tree:

A cedar, 24 ins. diam., bears N. 79° E., 23 lks.
dist., mkd. ¼ S1 BT.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins.
in the ground to bedrock, and in a mound of stone, 3½ ft.
base to top, with brass cap mkd.

T 10 S R 25 E

¼
|
S 2 | S 1

1975

N. 0°11' E., beginning new measurement.

Desc. 20 ft. along W slope.

6.00 Spur, slopes N. 40° W.; desc. 400 ft. over rocky N slope.

18.00 Wash, in bottom of Cripple Horse Canyon, drains S. 80° W.;
asc. 460 ft. over rocky S slope.

34.00 Ridge, bears N. 30° W. from E; desc. 60 ft. over NE
slope.

41.61 The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the
Tp., heretofore described.

From the stan. cor. of secs. 34 and 35, on the S. bdy.
of the Tp., heretofore described.

N. 0°25' E., bet. secs. 34 and 35.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
	Desc. 120 ft. over NW slope.
10.00	Wash, drains N. 65° W.; asc. 40 ft. over SW slope.
25.00	Top of ascent, slopes W; desc. 120 ft. over SW slope.
40.33	The ¼ sec. cor. of secs. 34 and 35, monumented with a sandstone, 24 x 6 x 6 ins., protruding 6 ins. above ground, mkd. ¼ on the W face.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>T 10 S R 25 E</p> <p style="margin-left: 100px;">¼</p> <p style="margin-left: 100px;"> </p> <p style="margin-left: 100px;">S 34 S 35</p> <p style="margin-left: 100px;"> </p> <p style="margin-left: 100px;">1975</p>
	Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor.
	Deposit the mkd. stone alongside the iron post.
	<hr style="width: 20%; margin: 0 auto;"/>
	N. 0°04' E., beginning new measurement.
	Desc. 60 ft. along rocky W slope, through scattering juniper and pinon.
9.00	Crest of spur, slopes N. 10° W.; desc. 500 ft. along E slope of spur sloping N.
39.79	The cor. of secs. 26, 27, 34 and 35, monumented with a sandstone, 20 x 15 x 4 ins., protruding 12 ins. above ground, mkd. 1 notch on the S and 2 notches on the E edges.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>T 10 S R 25 E</p> <p style="margin-left: 100px;">S 27 S 26</p> <p style="margin-left: 100px;">S 34 S 35</p> <p style="margin-left: 100px;">1975</p>
	Deposit the mkd. stone alongside the iron post.
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.
	From the cor. of secs. 25, 26, 35 and 36.
	N. 89°57' W., bet. secs. 26 and 35.
	Desc. 100 ft. along rocky spur, slopes N. 70° W.
6.50	Trail road, bears N and S; desc. 60 ft. over SW slope.
12.00	Wash, in bottom of Hells Hole Canyon, drains N. 30° W.

330

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS 14.00	Trail road, bears N. 50° W. and S. 50° E.; asc. 130 ft. over NE slope, through juniper and pinon.
28.00	Spur, slopes N; desc. 130 ft. over W slope.
34.50	Deep draw, drains N; asc. 110 ft. over E slope.
36.00	Spur, slopes N; desc. gentle W slope.
39.92	The ¼ sec. cor. of secs. 26 and 35, monumented with a sandstone, 24 x 8 x 4 ins., protruding 8 ins. above ground, mkd. ¼ on W face. from which the original bearing trees A cedar, 6 ins. diam., bears N. 1° E., 37 lks. dist., mkd. ¼SBT. A cedar, 6 ins. diam., bears S. 67° W., 24 lks. dist., mkd. ¼SBT. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 10 S R 25 E ¼ $\frac{S 26}{S 35}$ 1975 Deposit the mkd. stone alongside the iron post. N. 89°51' W., beginning new measurement. Asc. 20 ft. over rolling land.
17.00	Spur, slopes N; desc. 120 ft. over W slope.
27.50	Wash, drains N; asc. 80 ft. over NE slope.
33.50	Top of ascent, slopes N; desc. along N slope.
39.87	The cor. of secs. 26, 27, 34 and 35.
	N. 0°14' E., bet. secs. 26 and 27. Desc. 120 ft. along spur sloping N.
16.00	Wash, drains N. 50° E.; asc. 80 ft. over S slope.
22.00	Spur, slopes N. 60° E.; desc. 80 ft. over NE slope.
27.00	Draw, drains N. 55° E.; asc. 60 ft. along E slope.
39.50	Point for the ¼ sec. cor. of secs. 26 and 27, determined by the original bearing trees. A pinon, 10 ins. diam., bears N. 41° E., 11 lks. dist., mkd. ¼S26BT. A dead pinon, 10 ins. diam., bears N. 38° W., 59 lks. dist., mkd. ¼S27BT.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 10 S R 25 E
 ½
 |
S 27 | S 26
 |
 1975

N. 0°07' W., beginning new measurement.

Desc. 80 ft. over rocky N slope.

11.00 Trail road in bottom of Hells Hole Canyon, bears N. 80° W. and S. 55° E.; canyon drains N. 80° W.; asc. 60 ft. over SW slope.

19.00 Spur, slopes W; desc. 50 ft. over NW slope.

28.00 Wash, drains S. 60° W.; asc. 170 ft. over SE slope.

40.48 The cor. of secs. 22, 23, 26 and 27, monumented with a weathered mound of stone, with no visible marks, but harmoniously related to existing original cors. and is accepted as the best available evidence of the original corner position.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T 10 S R 25 E
S 22 | S 23
S 27 | S 26
 1975

From the cor. of secs. 23, 24, 25 and 26.

N. 89°50' W., bet. secs. 23 and 26.

Asc. 300 ft. over steep, rocky SE slope.

20.00 Spur, bears N. 50° E. and curves S. 20° W.; desc. 400 ft. over W slope.

39.00 Wash, drains S.

40.25 The ¼ sec. cor. of secs. 23 and 26, monumented with a sandstone, 20 x 13 x 4 ins., protruding 12 ins. above ground, plainly mkd. ¼ on the N face, and with a mound of stone to the N.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

332

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
	<p style="text-align: center;">T 10 S R 25 E $\frac{1}{4}$ $\frac{S\ 23}{S\ 26}$ 1975</p> <p>Deposit the mkd. stone alongside the iron post and rebuild mound of stone, 2 ft. base, 1½ ft. high, N of cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°54' W., beginning new measurement.</p> <p>Asc. 50 ft. over SE slope.</p> <p>8.00 Spur, slopes S; desc. 80 ft. over W slope.</p> <p>10.50 Draw, drains S; asc. 300 ft. along broken S slope.</p> <p>29.00 Point of spur, slopes S; desc. 300 ft. over steep SW slope.</p> <p>34.50 Draw, drains S; asc. 80 ft. over SE slope.</p> <p>39.57 The cor. of secs. 22, 23, 26 and 27.</p>
	<p>North, bet. secs. 22 and 23.</p> <p>Asc. 180 ft. over precipitous and ledgy SE slope.</p> <p>4.50 Top of narrow spur, bears N. 50° E. and S. 70° W.; desc. 140 ft. along broken W slope.</p> <p>10.00 Head of draw, drains W; asc. 40 ft. over SW slope.</p> <p>13.00 Spur, slopes W; desc. 200 ft. over NW slope.</p> <p>27.00 Wash, drains S. 50° W.; asc. 200 ft. over SE slope.</p> <p>40.05 Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 23, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T 10 S R 25 E $\frac{1}{4}$ S 22 S 23 1975</p> <p>Asc. 340 ft. over steep and rocky SE slope.</p> <p>51.00 Ridge, bears N. 50° E. and S. 50° W.; desc. 60 ft. over NW slope. Enter timber.</p> <p>58.50 Wash, drains S. 65° W.; asc. 240 ft. over broken SW slope.</p> <p>76.00 Trail road, on ridge, bears S. 30° E. and N. 30° W.; asc. along E slope.</p> <p>80.10 The cor. of secs. 14, 15, 22 and 23, monumented with a limestone, 20 x 15 x 4 ins., firmly set 10 ins. in the ground, mkd. with 2 notches on the E and 3 notches on the S edges.</p>

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

from which bearing trees of unknown and recent origin

A pinon, 8 ins. diam., bears N. 60° E., 41 lks.
dist., mkd. T10S R25E S14 BT.

A pinon, 6 ins. diam., bears S. 70° E., 115 lks.
dist., mkd. T10S R25E S23 BT.

A pinon, 12 ins. diam., bears N. 45° W., 89 lks.
dist., mkd. T10S R25E S15 BT.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 10 S R 25 E
S 15 | S 14
S 22 | S 23
1975

Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of
cor.

Deposit the mkd. stone alongside the iron post.

From the cor. of secs. 13, 14, 23 and 24.

N. 89°57' W., bet. secs. 14 and 23.

Desc. 80 ft. through juniper and pinon along N slope.

10.50 Underground pipeline, bears N. 47° W. and S. 47° E.

13.00 Draw, drains N. 40° W.; asc. 140 ft. over NE slope.

27.50 Spur, slopes N; desc. 60 ft. over NW slope.

30.00 Draw, drains N; asc. 80 ft. over NE slope.

35.00 Spur, slopes N; desc. 40 ft. over NW slope.

39.76 The ¼ sec. cor. of secs. 14 and 23, monumented with a
sandstone, 20 x 12 x 4 ins., protruding 10 ins. above
ground, mkd. ¼ on the N face.

from which the original bearing trees

A cedar, 8 ins. diam., bears N. 41° E., 17 lks.
dist., mkd. ¼S23BT.

A cedar, 10 ins. diam., bears N. 52° W., 13 lks.
dist., mkd. ¼S14BT.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 10 S R 25 E
¼ S 14
S 23
1975

Deposit the mkd. stone alongside the iron post.

334

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
	S. 89°58' W., beginning new measurement.
0.50	Draw, drains N; asc. 60 ft. over E slope.
5.00	Spur, slopes N; desc. 100 ft. over NW slope.
14.50	Wash, drains N; asc. 20 ft. over NE slope.
25.00	Spur, slopes N; desc. 40 ft. over NW slope.
32.00	Draw, drains N. 10° E.; asc. 200 ft. over E slope.
39.88	The cor. of secs. 14, 15, 22 and 23.
	N. 0°06' W., bet. secs. 14 and 15.
	Desc. 240 ft. along rocky E slope, through juniper and pinon.
28.00	Spur, slopes N. 20° E.; desc. 80 ft. over N slope.
33.00	Head of draw, drains N; desc. 120 ft. along draw.
40.96	The ¼ sec. cor. of secs. 14 and 15, monumented with a limestone, 18 x 15 x 7 ins., firmly set 12 ins. in the ground, and dimly mkd. ¼ on the W face, and with a mound of stone to the W.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 10 S R 25 E ½ S 15 S 14 1975
	Rebuild mound of stone, 2 ft. base, 1½ ft. high, W of cor.
	Deposit the mkd. stone alongside the iron post.
	N. 0°04' W., beginning new measurement.
19.50	Underground pipeline, on curve, bears N. 40° W. and S. 65° E.
22.00	Wash in Weaver Canyon, drains N. 60° W.; asc. 120 ft. over S slope.
32.00	Spur, slopes W; desc. 160 ft. over NW slope.
40.02	The cor. of secs. 10, 11, 14 and 15, monumented with a sandstone, 16 x 12 x 8 ins., (record, 20 x 9 x 8 ins.) protruding 10 ins. above ground, mkd. with 4 notches on the S and 2 notches on the E edges.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

T 10 S R 25 E

S 10 | S 11

S 15 | S 14

1975

Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W of cor.

Deposit the mkd. stone alongside the iron post.

From the cor. of secs. 11, 12, 13 and 14.

N. $89^{\circ}58'$ W., bet. secs. 11 and 14.

Asc. 140 ft. over E slope.

5.00 Spur, slopes N; desc. 120 ft. over W slope.

9.00 Draw, drains N; asc. 200 ft. over NE slope.

19.00 Spur, slopes N; desc. 240 ft. over W slope.

26.00 Draw, drains N. 10° W.; asc. 200 ft. over NE slope.

34.00 Spur, slopes N. 15° W.; desc. 160 ft. over steep NW slope.

41.48 The $\frac{1}{4}$ sec. cor. of secs. 11 and 14, monumented with a sandstone, 24 x 11 x 3 ins., protruding 10 ins. above ground, mkd. $\frac{1}{4}$ on the N face.

From which the original bearing trees

A cedar, 6 ins. diam., bears S. 63° E., 15 lks. dist., mkd. $\frac{1}{4}$ S14BT.

A cedar, 11 ins. diam., bears N. 78° W., 8 lks. dist., mkd. $\frac{1}{4}$ S11BT.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 10 S R 25 E

 $\frac{1}{4}$ S 11

S 14

1975

Deposit the mkd. stone alongside the iron post.

S. $89^{\circ}50'$ W., beginning new measurement.

3.00 Draw, drains N. 50° W.; asc. along N slope.

8.00 Spur, slopes N. 55° W.; desc. 360 ft. over SW slope.

33.00 Wash, drains N. 45° W.; asc. slightly over NE slope.

35.00 Point of spur, slopes N; desc. 40 ft. over NW slope.

38.99 The cor. of secs. 10, 11, 14 and 15.

N. $0^{\circ}06'$ W., bet. secs. 10 and 11.

336

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
2.50	Wash, drains N. 70° W.
10.50	Wash, drains S. 80° W.; asc. 400 ft. over steep and broken SW slope.
28.50	Spur, slopes S. 75° W.; desc. 200 ft. along W slope.
37.00	Head of draw, drains W; asc. 80 ft. over SW slope.
39.57	Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11, at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd. <div style="text-align: center;"> T 10 S R 25 E $\frac{1}{4}$ S 10 S 11 1975 </div>
	Asc. 120 ft. over SW slope.
43.50	Point of spur, slopes W; desc. 160 ft. over NW slope.
46.00	Wash, drains S. 30° W.; asc. 380 ft. over SW slope.
65.00	Ridge, bears N. 75° W. and S. 75° E.; desc. 100 ft. over NE slope.
68.50	Wash, drains N. 60° W.; asc. 140 ft. over SW slope.
79.14	The cor. of secs. 2, 3, 10 and 11, monumented with a sandstone, 20 x 10 x 3 ins., protruding 8 ins. above ground, dimly mkd. with 5 notches on the S and 2 notches on the E edges, and in a mound of stone, on ridge, bears N. 60° W. and S. 40° E. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd. <div style="text-align: center;"> T 10 S R 25 E S 3 S 2 S 10 S 11 1975 </div>
	Deposit the mkd. stone alongside the iron post.
	From the cor. of secs. 1, 2, 11 and 12. N. 89°57' W., bet. secs. 2 and 11. Along the N slope of spur.
6.00	Spur, slopes N. 75° W.; desc. 260 ft. over rocky W slope.
12.00	Wash, drains N. 35° W.; asc. 300 ft. over broken NE slope, through juniper and pinon.
29.00	Spur, slopes N; desc. 80 ft. over W slope.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS
39.85

The $\frac{1}{4}$ sec. cor. of secs. 2 and 11, monumented with a weathered sandstone, 24 x 12 x 3 ins., protruding 12 ins. above ground, in a scattered mound of stone.

from which the original bearing trees

A dead pinon, 8 ins. diam., bears N. 19° E., 28 lks. dist., mkd. $\frac{1}{4}$ S2BT.

A pinon, 8 ins. diam., bears S. 71° W., 81 lks. dist., mkd. $\frac{1}{4}$ S11BT. (Record, 83 lks.)

At the corner point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 3 $\frac{1}{2}$ ft. base to top, with brass cap mkd.

T 10 S R 25 E
 $\frac{1}{4}$ $\frac{S 2}{S 11}$
1975

Deposit the unmkd. stone, in mound of stone, alongside the iron post.

N. 89°56' W., beginning new measurement.

Desc. 240 ft. over steep W slope.

- 7.50 Wash, drains W from S. 35° E.; thence along draw.
13.00 Draw, turns N; asc. 280 ft. over precipitous NE slope.
24.00 Spur, slopes N; desc. 80 ft. over NW slope.
27.00 Draw, drains N; asc. 200 ft. over NE slope.
35.00 Ridge, bears N. 60° W. and S. 40° E.
40.00 The cor. of secs. 2, 3, 10 and 11.

N. 0°10' E., bet. secs. 2 and 3.

Over nearly level ridge top.

- 3.00 Desc. 240 ft. over NE slope, through scattering juniper and pinon.
19.00 Draw, drains N. 10° W.; desc. 80 ft. along W slope.
35.00 Head of draw, drains W; continue along W slope.
39.69 The $\frac{1}{4}$ sec. cor. of secs. 2 and 3, monumented with a weathered sandstone, 20 x 10 x 3 ins., (record, 25 x 10 x 3 ins.), protruding 10 ins. above ground.
from which the original bearing trees
A cedar, 14 ins. diam., bears N. 49° E., 27 lks. dist., mkd. $\frac{1}{4}$ S2BT.
A cedar, 10 ins. diam., bears S. 81° W., 50 lks. dist., mkd. $\frac{1}{4}$ S3BT. (Record, 45 lks.)

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
	<p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 10 S R 25 E</p> <p>¼</p> <p>S 3 S 2</p> <p>1975</p> </div> <p>Deposit the unmkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°03' E., beginning new measurement.</p> <p>Along E slope of spur.</p> <p>6.00 Desc. 600 ft. along steep E changing to NE slope.</p> <p>39.92 The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., heretofore described.</p>
	<p>From the stan. cor. of secs. 33 and 34, on the S. bdy. of the Tp., identical with U.S.C. and G.S. triangulation station GLO Station No. 5, heretofore described.</p> <p>N. 0°05' E., bet. secs. 33 and 34.</p> <p>Over rolling foothills.</p> <p>10.00 Spur, slopes S. 45° W. from E; desc. 160 ft. over N slope.</p> <p>15.00 Wash, drains W; asc. 240 ft. over S slope.</p> <p>24.00 Spur, slopes W; desc. 280 ft. over N slope.</p> <p>32.00 Wash, drains S. 75° W.; asc. 80 ft. over SE slope.</p> <p>37.00 Spur, slopes S. 75° W.; desc. 40 ft. over NW slope.</p> <p>40.76 The ¼ sec. cor. of secs. 33 and 34, monumented with a sandstone, 24 x 10 x 3 ins., protruding 10 ins. above ground, mkd. ¼ on the W face.</p> <p>from which the original bearing trees</p> <p style="padding-left: 40px;">A pinon, 16 ins. diam., bears S. 31° E., 25 lks. dist., mkd. ¼ S34 BT.</p> <p style="padding-left: 40px;">A pinon, 10 ins. diam., bears N. 89° W., 19 lks. dist., mkd. ¼ S33 BT.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 10 S R 24 E</p> <p>¼</p> <p>S 33 S 34</p> <p>1975</p> </div>

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

- Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.
- Deposit the mkd. stone alongside the iron post.
-
- N. 0°02' E., beginning new measurement.
- 1.00 Draw, drains S. 50° W.; asc. 200 ft. through scattering juniper and pinon, over SE slope.
- 10.00 Top of spur, slopes W; desc. 100 ft. over N slope.
- 14.00 Head of draw, drains N. 80° W.; thence along W slope.
- 23.00 Ridge, bears N. 45° W. and S. 45° E.; desc. 40 ft. over NE slope.
- 29.00 Head of draw, drains E; asc. 40 ft. over SE slope.
- 34.00 Spur, slopes E; desc. 40 ft. over NE slope.
- 39.47 The cor. of secs. 27, 28, 33 and 34, monumented with a sandstone, 24 x 12 x 5 ins., protruding 12 ins. above ground, mkd. with 1 notch on the S and 3 notches on the E edges.
- At the corner point
- Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base to top, with brass cap mkd.
- | | | |
|------|------|------|
| T 10 | S R | 25 E |
| S 28 | S 27 | |
| S 33 | S 34 | |
| 1975 | | |
- Deposit the mkd. stone alongside the iron post.
-
- From the cor. of secs. 26, 27, 34 and 35.
- N. 89°54' W., bet. secs. 27 and 34.
- Desc. 40 ft. over rocky NW slope.
- 12.50 Wash, drains N. 45° E. from S; asc. 480 ft. over rocky E slope through scattering juniper and pinon.
- 28.00 End steep ascent, bears N and S; asc. gradually 80 ft. over E slope.
- 38.00 Top of ridge, bears N. 50° W.
- 39.71 The ¼ sec. cor. of secs. 27 and 34, monumented with a sandstone, 20 x 15 x 4 ins., protruding 12 ins. above ground, mkd. ¼ on N face.
- At the corner point
- Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd.

340

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
	T 10 S R 25 E $\frac{1}{4}$ $\frac{S 27}{S 34}$ 1975
	Deposit the mkd. stone alongside the iron post.

	N. 89°57' W., beginning new measurement.
	Desc. 220 ft. over rocky SW slope.
16.00	Draw, drains N. 50° W.; asc. 60 ft. over NE slope.
25.00	Spur, slopes N; desc. 80 ft. over NW slope.
28.00	Wash, drains N. 15° E.; asc. 280 ft. over E slope.
40.35	The cor. of secs. 27, 28, 33 and 34.

	N. 0°12' E., bet. secs. 27 and 28.
	Along E slope, through juniper and pinon.
4.00	Desc. 120 ft. along draw, drains N.
8.00	Draw, drains N. 5° E.; desc. 200 ft. along E slope.
36.00	Spur, slopes N. 10° E.; desc. 40 ft. along spur.
40.71	The $\frac{1}{4}$ sec. cor. of secs. 27 and 28, monumented with a sandstone, 24 x 14 x 3 ins., (record, 20 x 11 x 3 ins.) protruding 12 ins. above ground, mkd. $\frac{1}{4}$ on W face.
	from which the original bearing trees
	A cedar, 8 ins. diam., bears N. 23° E., 25 lks. dist., mkd. $\frac{1}{4}$ S27BT. (Record, 27 lks.)
	A cedar, 4 ins. diam., bears N. 31° W., 23 lks. dist., mkd. $\frac{1}{4}$ S28BT. (Record, 21 lks.)
	At the corner point
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T 10 S R 25 E $\frac{1}{4}$ S 28 S 27 1975
	Deposit the mkd. stone alongside the iron post.

	N. 0°03' E., beginning new measurement.
	Desc. 120 ft. over rocky NW slope.
9.00	Draw, drains N. 10° E.; asc. along E slope.
20.00	Spur, slopes N. 25° E.; desc. 80 ft. over NE slope.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
28.00	Head of draw, drains E; asc. 80 ft. over steep SE slope.
31.50	Spur, slopes N. 80° E.; desc. 220 ft. over steep NE slope.
39.46	The cor. of secs. 21, 22, 27 and 28, monumented with a sandstone, 28 x 14 x 4 ins., protruding 14 ins. above ground, mkd. with 2 notches on the S and 3 notches on the E edges. from which the remaining original bearing trees A cedar, 4 ins. diam., bears N. 51° E., 39 lks. dist., mkd. T10S R25E S22 BT. A cedar, 10 ins. diam., bears N. 50° W., 65 lks. dist., mkd. T10S R25E S21BT. (Record, 67 lks.) At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. <div style="text-align: center;"> T 10 S R 25 E S 21 S 22 S 28 S 27 1975 </div> Deposit the mkd. stone alongside the iron post.
	From the cor. of secs. 22, 23, 26 and 27. N. 89°46' W., bet. secs. 22 and 27. Asc. 80 ft. above precipitous and ledgy S slope.
4.00	Top of ascent, on S slope of spur, slopes W; desc. 280 ft. along spur.
26.00	Trail road, bears N. 30° E. and S. 30° W.; thence along nearly level land.
31.00	Wash, drains S. 40° W.
39.99	The ¼ sec. cor. of secs. 22 and 27, monumented with a sandstone, 20 x 15 x 5 ins., protruding 12 ins. above ground, mkd. ¼ on the N face and with a mound of stone to the N. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 10 S R 25 E ¼ S 22 S 27 1975 </div> Deposit the mkd. stone alongside the iron post. N. 89°46' W., beginning new measurement. Desc. over gently rolling land.

342

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
8.00	Wash in bottom of Hells Hole Canyon, drains N. 10° W., curving W.
9.00	Trail road, bears N. 65° W. and S. 65° E.; asc. 180 ft. over NE slope, through scattering juniper and pinon.
26.00	Narrow spur, slopes N. 30° W.; desc. 150 ft. over steep W slope.
30.00	Draw, drains N; asc. 120 ft. over NE slope.
40.02	The cor. of secs. 21, 22, 27 and 28.
	N. 0°01' E., bet. secs. 21 and 22. Desc. 100 ft. over rocky NE slope.
3.50	Draw, drains N. 50° E.; asc. 120 ft. over SE slope.
13.50	Top of ascent, slopes E; desc. 200 ft. over SE slope.
33.00	Trail road, bears N. 30° W. and S. 30° E.
35.00	Wash, in bottom of Hells Hole Canyon, drains N. 40° W.
39.86	The $\frac{1}{4}$ sec. cor. of secs. 21 and 22, monumented with a sandstone, 20 x 8 x 8 ins., protruding 8 ins. above ground, mkd. $\frac{1}{4}$ on the W face, and with a mound of stone to the W. At the corner point Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. T 10 S R 25 E $\frac{1}{4}$ S 21 S 22 1975 Rebuild mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, W of cor. Deposit the mkd. stone alongside the iron post. N. 0°09' E., beginning new measurement. Asc. 220 ft. over rocky SW slope.
22.00	Point of spur, slopes W; desc. 140 ft. over NW slope.
27.00	Draw, drains S. 70° W.; asc. 400 ft. over broken SW slope.
37.00	Ridge, bears E and N. 80° W.; desc. 60 ft. over NE slope.
40.05	The cor. of secs. 15, 16, 21 and 22, monumented with a sandstone, 20 x 11 x 5 ins., firmly set 8 ins. in the ground, and mkd. with 3 notches on the E and S edges, 10S on the N and 25S on the S faces. At the corner point

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T 10 S R 25 E
S 16 | S 15
S 21 | S 22
1975

Deposit the mkd. stone alongside the iron post.

From the cor. of secs. 14, 15, 22 and 23.

S. 89°57' W., bet. secs. 15 and 22.

Asc. 40 ft. through juniper and pinon on ridge top.

1.00 Trail road, curves S. 30° E. and W.; thence along road.

4.00 Road, turns N. 75° W.

8.00 Road, turns S. 40° W.; desc. 80 ft. over NW slope.

13.00 Head of draw, drains N. 20° W.; asc. 150 ft. over NE slope.

27.00 Same trail road, on ridge, bears N. 45° W. turning N and S. 60° E.; desc. over SW slope.

40.12 The ¼ sec. cor. of secs. 15 and 22, monumented with a limestone, 24 x 20 x 4 ins., firmly set 10 ins. in the ground, mkd. ¼ on the N face.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 4½ ft. base to top, with brass cap mkd.

T 10 S R 25 E
¼ S 15
S 22
1975

Deposit the mkd. stone alongside the iron post.

N. 89°59' W., beginning new measurement.

Desc. 320 ft. along rocky draw, drains W.

25.50 Junction of draw from N; drains S. 80° W.; desc. 100 ft. along N side of wash.

37.85 Same wash, drains N. 45° W.

39.85 The cor. of secs. 15, 16, 21 and 22.

N. 0°04' E., bet. secs. 15 and 16.

Desc. slightly.

2.00 Wash, drains N. 45° W.; asc. 200 ft. over SW slope.

15.00 Spur, slopes N. 80° W.; desc. 320 ft. over steep N slope.

344

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
23.00	Wash, drains W; asc. 360 ft. over steep S slope.
35.00	Spur, slopes S. 50° W.; desc. 50 ft. over NW slope.
39.73	The ¼ sec. cor. of secs. 15 and 16, monumented with a weathered limestone, 20 x 10 x 3 ins., protruding 10 ins. above ground, and in a mound of stone.
	from which the original bearing trees
	A cedar, 12 ins. diam., bears S. 61° E., 25 lks. dist., mkd. ¼ S15 BT.
	A cedar, 8 ins. diam., bears N. 70° W.; 77 lks. dist., mkd. ¼ S16 BT.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>T 10 S R 25 E</p> <p>¼</p> <p> </p> <p>S 16 S 15</p> <p> </p> <p>1975</p>
	Raise a mound of stone, 3 ft. base, W of cor.
	Deposit the unmkd. stone alongside the iron post.
	North, beginning new measurement.
0.20	Draw, drains S. 45° W.; asc. 50 ft. over S slope.
5.00	Spur, slopes S. 75° W.; desc. 180 ft. over NW slope.
15.00	Wash, drains S. 50° W.; asc. 240 ft. over SE slope.
25.00	Spur, slopes S. 60° W.; desc. 140 ft. over NW slope.
33.00	Draw, drains S. 50° W.; asc. 160 ft. over S slope.
40.14	The cor. of secs. 9, 10, 15 and 16, monumented with a crumbled limestone, 12 x 6 x 3 ins.
	from which the original bearing trees
	A cedar, 5 ins. diam., bears N. 71° E., 110 lks. dist., mkd. T10S R25E S10 BT.
	A cedar, 6 ins. diam., bears S. 63° E., 16 lks. dist., mkd. T10S R25E S15 BT.
	A cedar, 10 ins. diam., bears S. 87° W., 121 lks. dist., mkd. T10S R25E S16 BT. (Record, 14 ins. diam.)
	A cedar, 8 ins. diam., bears N. 69° W., 77 lks. dist., mkd. T10S R25E S9 BT.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone, 3 ft. base to top, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

T 10 S R 25 E
S 9 | S 10
S 16 | S 15
1975

Deposit the unmkd. stone, in mound of stone, alongside the iron post.

From the cor. of secs. 10, 11, 14 and 15.

S. 88°17' W., bet. secs. 10 and 15.

- 2.00 Underground pipeline, on curve, bears N and S. 22° W.
- 3.00 Wash, in bottom of Weaver Canyon, drains N. 25° E.; asc. 120 ft. over rocky SE slope.
- 11.50 Spur, slopes N. 30° E.; desc. 120 ft. over NW slope.
- 16.00 Wash, drains N. 20° E.; asc. 420 ft. over E slope.
- 30.00 Spur, slopes N. 30° E.; desc. 60 ft. over NW slope.
- 35.00 Head of draw, drains N. 20° E.; asc. 80 ft. over E slope.
- 39.00 Spur, slopes N.
- 39.66 The $\frac{1}{4}$ sec. cor. of secs. 10 and 15, monumented with a sandstone, 20 x 14 x 5 ins., protruding 12 ins. above ground, dimly mkd. $\frac{1}{4}$ on the N face, and with a mound of stone to the N.

At the corner point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T 10 S R 25 E
 $\frac{1}{4}$ S 10
S 15
1975

Deposit the mkd. stone in mound of stone, alongside the iron post.

N. 89°59' W., beginning new measurement.

Desc. 240 ft. over steep NW slope.

- 6.00 Draw, drains N; asc. 400 ft. over NE slope.
- 22.00 Trail road, on top of spur, bears N. 45° W. and S. 15° E.; desc. 120 ft. over SW slope.
- 29.00 Head of draw, drains S; thence along S slope.
- 40.15 The cor. of secs. 9, 10, 15 and 16.

N. 0°06' E., bet. secs. 9 and 10.

Asc. 40 ft. over S slope.

346

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
1.50	Top of spur, slopes W; desc. 40 ft. over N slope.
4.00	Draw, drains W; asc. 40 ft. over S slope.
7.00	Spur, slopes W; desc. 120 ft. over N slope.
12.50	Draw, drains W; asc. 120 ft. over S slope.
18.00	Spur, slopes W; desc. 140 ft. over NE slope.
23.00	Draw, drains W; asc. 140 ft. over SW slope.
30.00	Spur, slopes W; desc. 240 ft. over N slope.
33.00	Trail road, bears N. 80° W. and S. 80° E.
40.45	The ¼ sec. cor. of secs. 9 and 10, monumented with a sandstone, 20 x 8 x 7 ins., protruding 8 ins. above ground, mkd. ¼ on the W face. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd. T 10 S R 25 E ½ S 9 S 10 1975 Deposit the mkd. stone alongside the iron post. N. 0°08' W., beginning new measurement. Desc. 520 ft. on E side of wash, drains N. 25.00 Base of steep desc., bears E and N. 50° W.; thence along W edge of the bottom of Weaver Canyon. 34.00 Asc. 50 ft. over SE slope. 38.50 Top of spur, slopes E; desc. 40 ft. over NE slope. 39.82 The cor. of secs. 3, 4, 9 and 10, monumented with a sandstone, 20 x 11 x 3 ins., protruding 10 ins. above ground, mkd. with 5 notches on the S and 3 notches on the E edges. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd. T 10 S R 25 E S 4 S 3 S 9 S 10 1975 Deposit the mkd. stone alongside the iron post.
	From the cor. of secs. 2, 3, 10 and 11.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
	S. 89°57' W., bet. secs. 3 and 10.
	Desc. 400 ft. over rocky SW slope.
27.00	Wash, drains W; desc. 40 ft. along wash.
31.00	Leave wash, drains S. 45° W.; asc. 120 ft. over SE slope.
39.81	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 10, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	<p style="text-align: center;">T 10 S R 25 E $\frac{1}{4}$ $\frac{S 3}{S 10}$ 1975</p>
	Asc. 80 ft. along S slope.
45.00	Spur, slopes S. 40° W.; desc. 720 ft. over rocky W slope.
69.00	End steep descent, enter Weaver Canyon.
72.00	Wash in Weaver Canyon, drains N.
73.50	Underground pipeline, bears S. 12° W. and curves N. 40° W.; asc. 80 ft. over NE slope.
79.62	The cor. of secs. 3, 4, 9 and 10.
	N. 0°38' W., bet. secs. 3 and 4.
	Desc. 120 ft. over NE slope.
5.00	Wash, in Weaver Canyon, drains N. 50° W.
7.00	Underground pipeline, bears N. 50° W. and S. 50° E.; asc. 220 ft. over SW slope.
22.00	Spur, slopes W; desc. 200 ft. over NW slope.
27.00	Wash, drains S. 85° W.; asc. 560 ft. over steep SW slope.
39.28	The $\frac{1}{4}$ sec. cor. of secs. 3 and 4, monumented with a sandstone, 18 x 10 x 4 ins., protruding 10 ins. above ground, mkd. $\frac{1}{4}$ on the W face.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 2 ins. in the ground to bedrock, and in a mound of stone, 4½ ft. base to top, with brass cap mkd.
	<p style="text-align: center;">T 10 S R 25 E $\frac{1}{4}$ S 4 S 3 1975</p>
	Deposit the mkd. stone in mound of stone, alongside the iron post.

348

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
	<p>N. 0°01' W., beginning new measurement.</p> <p>Asc. 200 ft. over rocky ledges, on SW slope.</p>
4.00	Top of ledge, 10 ft. high, bears E and W; thence over broken land.
9.50	Top of ridge, bears S. 60° E. and N. 60° W.; desc. 1100 ft. over steep and broken N slope.
40.32	The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., hereinbefore described.
	<p>From the stan. cor. of secs. 32 and 33, on the S. bdy. of the Tp., heretofore described.</p> <p>North, bet. secs. 32 and 33.</p> <p>Desc. 60 ft. over broken desert land.</p>
6.00	Wash, drains N. 50° W. from E; asc. 100 ft. over S slope.
14.00	Spur, slopes W; desc. 80 ft. over N slope.
25.00	Draw, drains S. 50° W.; asc. 40 ft. over SE slope.
31.00	Spur, slopes S. 45° W.; desc. 40 ft. over NW slope.
37.50	Draw, drains W; asc. slightly over SW slope.
39.98	<p>The $\frac{1}{4}$ sec. cor. of secs. 32 and 33, monumented with a sandstone, 20 x 8 x 8 ins., protruding 8 ins. above ground, plainly mkd. $\frac{1}{4}$ on the W face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 10 S R 25 E</p> <p>$\frac{1}{4}$</p> <p> </p> <p>S 32 S 33</p> <p> </p> <p>1975</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p>
	<p>N. 0°06' E., beginning new measurement.</p> <p>Along rolling desert land.</p>
6.00	Wash, drains W.
11.00	Wash, drains S. 40° W.; asc. 100 ft. over general SW slope
29.00	Wash, drains S. 15° W.; asc. gentle SE slope.
40.19	The cor. of secs. 28, 29, 32 and 33, monumented with a sandstone, 20 x 12 x 4 ins., protruding 12 ins. above ground, mkd. with 4 notches on the E and 1 notch on the S edges, and with a mound of stone to the W.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

	<p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 10 S R 25 E S 29 S 28 S 32 S 33 1975</p> <p>Rebuild mound of stone, 3 ft. base, 1½ ft. high, W of cor.</p> <p>Deposit the mkd. stone alongside the iron post.</p>
	<p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>S. 89°57' W., bet. secs. 28 and 33.</p> <p>Asc. 30 ft. over E slope through juniper and pinon.</p>
1.50	Ridge, bears N and S; desc. 80 ft. over NW slope.
7.50	Wash, drains N. 35° W.; asc. 80 ft. over NE slope.
19.00	Spur, slopes W from S. 50° E.; desc. 160 ft. along spur.
39.91	The ¼ sec. cor. of secs. 28 and 33, monumented with a sandstone, 24 x 12 x 5 ins., protruding 12 ins. above ground, set in a mound of stone, mkd. ¼ on the N face.
	<p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T 10 S R 25 E ¼ S 28 S 33 1975</p> <p>Deposit the mkd. stone alongside the iron post.</p>
	<p>N. 89°54' W., beginning new measurement.</p> <p>Desc. 200 ft. over broken desert land, along spur.</p>
13.00	Wash, drains S. 40° W. from N.; asc. 40 ft. over SE slope.
16.00	Spur, slopes S. 40° W.; desc. 120 ft. over SW slope.
28.00	Improved dirt road, State Route No. 45, bears N. 10° W. and S. 10° E.; desc. slightly.
40.01	The cor. of secs. 28, 29, 32 and 33.
	<p>N. 0°07' E., bet. secs. 28 and 29.</p> <p>Asc. slightly over rocky land.</p>
6.00	Road on low ridge, bears N. 58° E. and S. 58° W.; desc. 80 ft.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
20.00	Wash, drains N. 43° W.; asc. 80 ft. over S slope.
26.00	Spur, slopes W; desc. over N slope.
31.00	Draw, drains W; asc. over SW slope.
35.00	Spur, slopes W; desc. 20 ft. over NW slope.
37.00	Draw, drains W; asc. 60 ft. over S slope.
40.05	Point for the ¼ sec. cor. of secs. 28 and 29, at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <p>T 10 S R 25 E</p> <p>¼</p> <p> </p> <p>S 29 S 28</p> <p> </p> <p>1975</p> </div>
	Asc. slightly.
41.70	Spur, slopes N. 50° W.; desc. 80 ft. over NE slope.
48.00	Improved dirt road, State Route 45, bears N. 36° W. and S. 36° E.; desc. 20 ft.
59.00	Wash, drains W; asc. 60 ft. over broken SW slope.
80.10	The cor. of secs. 20, 21, 28 and 29, monumented with a sandstone, 24 x 10 x 5 ins., protruding 10 ins. above ground, mkd. with 4 notches on the E and 2 notches on the S edges, and with a mound of stone to the W, on spur, slopes N. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <p>T 10 S R 25 E</p> <p>S 20 S 21</p> <p>S 29 S 28</p> <p>1975</p> </div>
	Deposit the mkd. stone alongside the iron post.
	From the cor. of secs. 21, 22, 27 and 28. S. 89°58' W., bet. secs. 21 and 28. Desc. slightly over rocky land.
4.50	Wash, drains N. 55° E.; asc. 400 ft. over E slope.
14.50	Spur, slopes N; desc. 320 ft. over steep NW slope.
27.00	Wash, drains N; from S. 45° W.; asc. 240 ft. over SE slope.
36.00	Spur, slopes N. 55° E.; desc. 40 ft. over NW slope.
40.01	The ¼ sec. cor. of secs. 21 and 28, monumented with a limestone, 28 x 12 x 3 ins., firmly set 10 ins. in the ground and mkd. ¼ on the N face.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 10 S R 25 E S 21 ¼ ——— S 28 1975
	Raise a mound of stone N of the cor.
	Deposit the mkd. stone alongside the iron post.
	Cor. is located on steep N slope.
	—————
	N. 89°58' W., beginning new measurement.
	Along steep N slope.
1.80	Head of draw, drains N. 40° E.; asc. 240 ft.
12.80	Ridge, bears N. 10° E. and S. 10° W.; desc. 240 ft. over general W slope.
36.00	Wash, drains N. 10° W.; asc. 50 ft. over E slope.
39.81	The cor. of secs. 20, 21, 28 and 29.
	N. 0°02' E., bet. secs. 20 and 21.
	Desc. 100 ft. over rocky N slope.
11.00	Wash, drains N. 20° W.; thence along W slope.
30.00	Spur, slopes N. 40° W.; desc. 80 ft. over NE slope.
39.93	Point for the ¼ sec. cor. of secs. 20 and 21, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T 10 S R 25 E ¼ S 20 S 21 1975
	Desc. 100 ft. over NE slope.
55.00	Draw, drains N. 25° E.; asc. 40 ft. over SE slope.
62.00	Point of spur, slopes N. 40° E.; desc. 200 ft. over NE slope.
74.00	Draw, drains N. 40° W.; asc. 100 ft. over SW slope.
79.86	The cor. of secs. 16, 17, 20 and 21, monumented with a sandstone, 24 x 8 x 4 ins., (record, 32 x 9 x 3 ins.) protruding 8 ins. above ground, mkd. with 3 notches on the S and 4 notches on the E edges, and with a mound of stone to the W.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS		
	<p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T 10 S R 25 E S 17 S 16 S 20 S 21 1975</p> <p>Deposit the mkd. stone alongside the iron post.</p>	
<p>6.50</p> <p>38.00</p> <p>39.92</p>	<p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>N. 89°58' W., bet. secs. 16 and 21.</p> <p>Asc. 140 ft. over rocky NE slope.</p> <p>Ridge, bears N. 50° W. and S. 50° E.; desc. 680 ft. over precipitous SW slope.</p> <p>Wash in Hells Hole Canyon, drains S. 45° W. from S. 20° E.</p> <p>Point for the ¼ sec. cor. of secs. 16 and 21, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T 10 S R 25 E ¼ S 16 S 21 1975</p> <p>Cor. is located at base of 15 ft. ledge on the N. side of wash.</p> <p>Desc. 40 ft. along bottom land in Hells Hole Canuon.</p> <p>Wash in bottom of Hells Hole Canyon, drains N.</p> <p>Trail road, bears N. 44° W. and S. 44° E.; asc. 200 ft. over rocky NE slope.</p> <p>Top of asc., slopes N; desc. 40 ft. over NW slope.</p> <p>Draw, drains N; asc. 260 ft. over NE slope.</p> <p>Spur, slopes N. 20° E.; desc. 60 ft. over NW slope.</p> <p>Head of draw, drains N; asc. 40 ft. over NE slope.</p> <p>Spur, slopes N. 40° W.; desc. 80 ft. over SW slope.</p> <p>The cor. of secs. 16, 17, 20 and 21.</p>	
<p>7.00</p>	<p>N. 0°09' E., bet. secs. 16 and 17.</p> <p>Desc. 120 ft. over rocky and ledgy NW slope.</p> <p>Spur, slopes N. 10° W.; desc. 200 ft. over precipitous and broken NE slope.</p>	

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
17.50	Road, bears N. 63° E. and S. 63° W.
18.50	Wash, drains N. 63° E.; asc. 80 ft. over broken SE slope.
27.50	Spur, slopes S. 60° E.; desc. 120 ft. over broken NE slope.
39.61	The ¼ sec. cor. of secs. 16 and 17, monumented with a sandstone, 18 x 12 x 7 ins., protruding 12 ins. above ground, mkd. ¼ on the W face, and with a mound of stone to the W.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<pre> T 10 S R 25 E ¼ S 17 S 16 1975 </pre>
	Rebuild mound of stone W of the cor.
	Deposit the mkd. stone alongside the iron post.

	N. 0°07' E., beginning new measurement.
	Desc. 20 ft. in bottom land.
4.00	Wash in bottom of Hells Hole Canyon, drains N. 20° E. from S. 30° E.
16.00	Same wash, drains S. 65° W.; asc. 200 ft. over broken and ledgy SW slope.
22.00	Spur, slopes W; desc. 80 ft. along broken W slope.
30.50	Draw, drains W; asc. 240 ft. along broken and precipitous W slope.
39.80	Spur, slopes W; desc. slightly.
40.60	The cor. of secs. 8, 9, 16 and 17, monumented with a sandstone, 28 x 12 x 3 ins., protruding 12 ins. above ground, mkd. with 4 notches on the S and E edges.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	<pre> T 10 S R 25 E S 8 S 9 S 17 S 16 1975 </pre>
	Deposit the mkd. stone alongside the iron post.
	From the cor. of secs. 9, 10, 15 and 16.
	N. 89°50' W., bet. secs. 9 and 16.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
	Desc. 220 ft. along rocky S slope of spur, sloping W, through scattering juniper and pūnon.
18.00	Draw, drains N. 40° W.; asc. 140 ft. over NE slope.
30.00	Ridge, bears N. 55° W. and S. 55° E.; desc. 160 ft. over SW slope.
39.76	The ¼ sec. cor. of secs. 9 and 16, monumented with a squared cedar post and a scattering mound of stone, harmoniously related to existing original cors. and is accepted as the best available evidence of the original cor. position.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T 10 S R 25 E S 9 ¼ S 16 1975
	Place squared cedar post in mound of stone alongside the iron post.

	N. 89°47' W., beginning new measurement.
	Desc. 120 ft. along steep and rocky S slope.
9.00	Draw, drains N. 70° W.; asc. 120 ft. over NE slope.
25.00	Spur, slopes N. 60° W.; desc. 320 ft. over W slope along small draw, draining W.
36.00	Wash, turns to N. 85° W.; thence along N slope.
39.97	The cor. of secs. 8, 9, 16 and 17.
	N. 0°03' W., bet. secs. 8 and 9.
	Over broken land; desc. 120 ft. over steep N slope.
1.50	Draw, drains W.; asc. 120 ft. along steep, general W slope.
15.50	Narrow spur, slopes N. 25° W.; desc. 280 ft. over steep NE slope.
24.50	Draw, drains N. 35° W.
26.50	Same draw, drains N. 40° E.
29.00	Same draw, drains W.; asc. 360 ft. over precipitous SW slope.
37.00	Spur, slopes W.; desc. 60 ft. over N slope.
39.89	The ¼ sec. cor. of secs. 8 and 9, monumented with a sandstone, 24 x 12 x 4 ins. (record, 18 x 10 x 4 ins.) protruding 12 ins. above ground, mkd. ¼ on N face.
	At the corner point

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top mkd.

T 10 S R 25 E
 $\frac{1}{4}$
 S 8 | S 9
 1975

Deposit the mkd. stone alongside the iron post.

N. 0°08' E., beginning new measurement.

Desc. 40 ft. over NW slope.

1.50 Draw, drains W; asc. 80 ft. over SW slope.

7.00 Spur, slopes N. 50° W.; desc. 380 ft. over steep N slope.

15.00 Wash, drains N. 10° W.; asc. 460 ft. over steep and broken SW slope.

29.00 Narrow ridge, bears N. 65° W. and S. 65° E.; desc. 160 ft. over NE slope.

36.00 Wash, drains N. 55° W.; asc. 80 ft. over SW slope.

39.64 The cor. of secs. 4, 5, 8 and 9, monumented with a weathered limestone, 15 x 14 x 5 ins., protruding 12 ins. above ground, with no visible marks, and in a mound of stone, harmoniously related to existing original cors. and is accepted as the best available evidence of the original corner position.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T 10 S R 25 E
 S 5 | S 4
 S 8 | S 9
 1975

Deposit the unmkd. stone and a 4x4 cedar post, in mound of stone, alongside the iron post.

From the cor. of secs. 3, 4, 9 and 10.

S. 89°54' W., bet. secs. 4 and 9.

Asc. 580 ft. over steep and ledgy E slope.

15.00 Road on ridge top, bears N. 40° W. and S; desc. 200 ft. over SW slope.

33.00 Wash, drains N. 50° W.; asc. 80 ft. over NE slope.

37.00 Point of spur, slopes N; desc. 120 ft. over steep NW slope.

39.54 The ¼ sec. cor. of secs. 4 and 9, monumented with a

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
	<p>mound of stone, no visible markings, harmoniously related to existing original cors. and is accepted as the best available evidence of the original corner position.</p> <p>At the corner point.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 10 S R 25 E</p> <p>¼ $\frac{S\ 4}{S\ 9}$</p> <p>1975</p> </div>
	<p>S. 89°25' W., beginning new measurement.</p> <p>Desc. 40 ft. over NW slope.</p> <p>1.00 Wash, drains S. 50° W.; asc. 120 ft. over SE slope.</p> <p>13.00 Spur, slopes S. 60° W.; desc. 320 ft. over NW slope.</p> <p>33.00 Draw, drains S.45° W.; asc. 40 ft. over SE slope.</p> <p>37.00 Top of ascent, slopes S; desc. 40 ft. over SW slope.</p> <p>40.12 The cor. of secs. 4, 5, 8 and 9.</p>
	<p>N. 0°34' W., bet. secs. 4 and 5.</p> <p>Asc. 140 ft. over rocky SW slope.</p> <p>4.00 Point of spur, slopes W; desc. 100 ft. over NW slope.</p> <p>8.00 Draw, drains S. 65° W.; asc. 200 ft. over SE slope.</p> <p>13.50 Spur, slopes S. 70° W.; asc. along W slope.</p> <p>19.00 Spur, slopes N. 60° W.; desc. 80 ft. over NE slope.</p> <p>22.00 Draw, drains N. 60° W.; asc. 60 ft. over SW slope.</p> <p>28.00 Spur, slopes N. 50° W.; desc. 300 ft. over steep NE slope.</p> <p>40.04 The ¼ sec. cor. of secs. 4 and 5, monumented with a limestone, 20 x 10 x 3 ins., protruding 10 ins. above ground, mkd. ¼ on the W face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 10 S R 25 E</p> <p>¼</p> <p>S 5 S 4</p> <p>1975</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p>

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
	N. 0°18' W., beginning new measurement.
	Desc. 400 ft. over rocky NE slope.
12.00	Wash, in Weaver Canyon, drains W.
12.50	Pipeline, bears N. 58° W. and S. 58° W.; asc. 280 ft. over SW slope.
30.00	Spur, slopes N. 50° W.; desc. 240 ft. over steep NW slope.
40.26	The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., hereinbefore described.
	From the stan. cor. of secs. 31 and 32, on the S. bdy. of the Tp., heretofore described.
	N. 0°16' E., bet. secs. 31 and 32.
	Asc. slightly over rolling desert land.
3.00	Spur, slopes S. 50° W.; desc. 80 ft. over NW slope.
14.50	Wash, drains S. 40° W.; from irregularly N.; thence along wash.
24.00	Leave wash, drains S from N. 60° E.; asc. 120 ft. along W slope of spur.
39.84	The ¼ sec. cor. of secs. 31 and 32, monumented with a sandstone, 18 x 9 x 5 ins., protruding 8 ins. above ground, plainly mkd. ¼ on the W face, and with a mound of stone to the W.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	<p style="text-align: center;">T 10 S R 25 E</p> <p style="text-align: center;"> </p> <p style="text-align: center;"> ¼</p> <p style="text-align: center;"> </p> <p style="text-align: center;">S 31 S 32</p> <p style="text-align: center;"> </p> <p style="text-align: center;"> 1975</p>
	Deposit the mkd. stone alongside the iron post.
	N. 0°04' E., beginning new measurement.
	Draw, drains S. 25° W.; asc. 80 ft. over SE slope.
24.00	Road, on ridge, bears N. 55° W. and S. 55° E.; desc. 60 ft. over gentle NE slope
40.40	The cor. of secs. 29, 30, 31 and 32, monumented with a sandstone, 28 x 11 x 4 ins., protruding 10 ins. above ground, plainly mkd. with 5 notches on the E and 1 notch on the S edges, and with a mound of stone to the W.
	At the corner point

358

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T 10 S R 25 E S 30 S 29 S 31 S 32 1975</p> <p>Deposit the mkd. stone alongside the iron post.</p>
	<p>From the cor. of secs. 28, 29, 32 and 33. N. 89°58' W., bet. secs. 29 and 32. Asc. 20 ft. over rocky land.</p>
3.50	Spur, slopes S. 25° W.; desc. 40 ft. over NW slope.
12.00	Head of draw, drains S. 50° W.
17.50	Spur, slopes S. 20° W.; desc. 40 ft. over W slope.
23.00	Draw, drains S. 15° W.; asc. slightly over S slope.
37.50	Trail road, on ridge, bears N. 83° E. and S. 42° W.
39.96	<p>The ¼ sec. cor. of secs. 29 and 32, monumented with a sandstone, 36 x 12 x 6 ins., (record, 28 x 8 x 6 ins.) protruding 12 ins. above ground, mkd. ¼ on the N face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T 10 S R 25 E ¼ S 29 S 32 1975</p> <p>Deposit the mkd. stone alongside the iron post.</p>
	<p>N. 89°57' W., beginning new measurement. Desc. slightly over rocky desert land.</p>
10.50	Underground pipeline, bears N. 8° W. and S. 8° E.; on spur sloping N; desc. 40 ft. over W slope.
18.00	Draw, drains N; asc. slightly.
22.00	Spur, slopes N; desc. 80 ft. over broken W slope.
32.50	Draw, drains N; asc. 40 ft. over E slope.
37.50	Spur, slopes N; desc. 40 ft. over W slope.
39.92	The cor. of secs. 29, 30, 31 and 32.
	N. 89°50' W., bet. secs. 30 and 31.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
	Desc. over rocky desert land.
2.50	Draw, drains N; asc. 40 ft. over E slope.
5.00	Spur, slopes N; desc. over broken NW slope.
18.50	Draw, drains N; asc. 20 ft.
22.00	Spur, slopes N; along rolling land.
35.00	Spur, slopes N; desc. 50 ft. over W slope.
39.00	Draw, drains N.
39.89	The $\frac{1}{4}$ sec. cor. of secs. 30 and 31, monumented with a sandstone, 28 x 15 x 8 ins., protruding 15 ins. above ground, mkd. $\frac{1}{4}$ on the N face.
	At the corner point
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd.
	T 10 S R 25 E $\frac{1}{4}$ $\frac{S 30}{S 31}$ 1975
	Raise a mound of stone, N of cor.
	Deposit the mkd. stone alongside the iron post.

	N. $89^{\circ}52'$ W., beginning new measurement.
2.50	Spur, slopes N; desc. 40 ft. over W slope.
9.50	Improved dirt road, State Route No. 207, bears N. 15° E. and S. 15° W.; thence over rolling desert land.
30.00	Spur, slopes N; desc. slightly.
33.00	Wash, drains N.
40.28	The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., described in the field notes of the E. bdy. of T. 10 S., R. 24 E., resurveyed concurrently.
	From the cor. of secs. 29, 30, 31 and 32.
	N. $0^{\circ}02'$ E., bet. secs. 29 and 30.
	Desc. 100 ft. over rocky land.
25.50	Road, State Route No. 207, on curve, bears N. 60° E. and S. 35° W.
27.50	Wash, drains W; asc. 80 ft. over SE slope of spur.
40.10	The $\frac{1}{4}$ sec. cor. of secs. 29 and 30, monumented with a sandstone, 27 x 12 x 4 ins., protruding 12 ins. above ground, plainly mkd. $\frac{1}{4}$ on the W face, and with a mound of stone to the W.
	At the corner point

360

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 10 S R 25 E</p> <p> ½</p> <p> </p> <p>S 30 S 29</p> <p> </p> <p> 1975</p> </div> <p>Rebuild a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°03' W., beginning new measurement.</p> <p>Asc. slightly over rolling desert land.</p> <p>4.00 Spur, slopes S from N. 30° E.; thence along rolling W slope.</p> <p>22.00 Spur, slopes W; desc. 40 ft. along rolling W slope.</p> <p>39.98 The cor. of secs. 19, 20, 29 and 30, monumented with a sandstone, 24 x 10 x 8 ins., protruding 10 ins. above ground, plainly mkd. 5 notches on the E and 2 notches on the S edges, and with a mound of stone to the W.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 10 S R 25 E</p> <p>S 19 S 20</p> <p>S 30 S 29</p> <p> 1975</p> </div> <p>Rebuild mound of stone W of cor.</p> <p>Deposit the mkd. stone alongside the iron post.</p>
	<p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>N. 89°58' W., bet. secs. 20 and 29.</p> <p>Desc. 120 ft. over broken desert land.</p> <p>32.00 Spur, slopes N.</p> <p>35.50 Road, State Route No. 45, bears N. 30° W. and S. 30° E.</p> <p>39.99 Point for the ¼ sec. cor. of secs. 20 and 29, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
	<p style="text-align: center;">T 10 S R 25 E $\frac{1}{4}$ $\frac{S 20}{S 29}$ 1975</p> <p>From this cor., U.S.G.S. VTBM, "K26", at Latitude 39°55'43.157" N. and Longitude 109°07'32.543" W., monumented with a standard brass tablet on concrete block, bears N. 18°46'30" W. 3.975 chs. dist., with brass tablet mkd.</p> <p style="text-align: center;">5824.506 FT $\frac{K 26}{1933}$</p>
46.50	Road, State Route No. 207, bears S. 20° W. and curves N. 65° E.
52.00	Spur, slopes S. 35° W.; desc. 120 ft. over gentle NW slope
62.00	Underground pipeline, bears N. 8° W. and S. 8° E.
79.98	The cor. of secs. 19, 20, 29 and 30.
	<p>S. 89°52' W., bet. secs. 19 and 30.</p> <p>Desc. 80 ft. over broken desert land.</p>
20.00	Wash, drains S. 35° W.
27.00	Same wash, drains N. 50° W.
36.00	Same wash, drains S. 45° W.; asc. gentle SE slope.
40.05	The $\frac{1}{4}$ sec. cor. of secs. 19 and 30, monumented with a sandstone, 32 x 20 x 6 ins., protruding 18 ins. above ground, mkd. $\frac{1}{4}$ on the N face.
	<p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 10 S R 25 E $\frac{1}{4}$ $\frac{S 19}{S 30}$ 1975</p> <p>Deposit the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>N. 89°28' W., beginning new measurement.</p> <p>Over rolling and broken desert land.</p>
15.00	Spur, slopes S. 30° W.; desc. 120 ft. over NW slope.
23.00	Draw, drains S. 20° W.; asc. 40 ft. over SE slope.
26.00	Spur, slopes S. 10° W.; desc. 40 ft. over NW slope.
30.00	Head of draw, drains S.
35.00	Narrow ridge, bears N. 40° E. and S. 40° W.; desc. over NW slope.

362

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
40.33	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., as described in the field notes of the E. bdy. of T. 10 S., R. 24 E., resurveyed concurrently.
	From the cor. of secs. 19, 20, 29 and 30. N. 0°02' W., bet. secs. 19 and 20. Over rolling desert land.
7.00	Spur, slopes W; desc. 40 ft. over N slope.
12.00	Wash, drains S. 80° W.; asc. 80 ft. over general SW slope.
19.00	Spur, slopes S. 75° W.; desc. 40 ft. over NW slope.
27.00	Wash, drains W; asc. slightly.
35.50	Underground pipeline, bears N. 52° W. and S. 52° E.
40.15	The $\frac{1}{4}$ sec. cor. of secs. 19 and 20, monumented with a sandstone, 24 x 11 x 4 ins., protruding 10 ins. above ground, plainly mkd. $\frac{1}{4}$ on the W face, and with a mound of stone to the W. At the corner point Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 10 S R 25 E $\frac{1}{4}$ S 19 S 20 1975 </div> Rebuild mound of stone W of cor. Deposit the mkd. stone alongside the iron post. <hr style="width: 20%; margin: auto;"/> N. 0°22' E., beginning new measurement. Desc. 40 ft. over rolling and broken desert land.
20.00	Spur, slopes N. 30° E.; desc. 120 ft. over NW slope.
39.74	The cor. of secs. 17, 18, 19 and 20, monumented with a sandstone, 24 x 8 x 4 ins., protruding 8 ins. above ground, mkd. 5 notches on the E and 3 notches on the S edges. At the corner point Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 10 S R 25 E S 18 S 17 S 19 S 20 1975 </div> Rebuild mound of stone W of cor. Deposit the mkd. stone alongside the iron post.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
	From the cor. of secs. 16, 17, 20 and 21.
	S. 89°59' W., bet. secs. 17 and 20.
	Desc. 180 ft. over rocky ledges, on broken W slope.
6.50	Trail road, bears N. 30° E. and S. 30° W.; desc. 20 ft.
8.00	Wash, drains N. 30° E.; asc. 360 ft. over broken and precipitous SE slope.
15.00	Spur, slopes N. 40° E.; desc. 120 ft. over NW slope.
21.00	Draw, drains N. 35° E.; asc. 120 ft. over SE slope.
26.00	Ridge, bears N and S.
29.00	Road, bears N. 30° E. and curves S.; desc. 120 ft. over W slope.
39.77	The $\frac{1}{4}$ sec. cor. of secs. 17 and 20, monumented with a sandstone, 30 x 12 x 6 ins., (record, 24 x 10 x 8 ins.), protruding 12 ins. above ground, mkd. $\frac{1}{4}$ on the N face, and with a mound of stone to the N.
	At the corner point
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 10 S R 25 E $\frac{1}{4}$ $\frac{S 17}{S 20}$ 1975
	Rebuild mound of stone, N of cor.
	Deposit the mkd. stone alongside the iron post.
	—————
	N. 89°55' W., beginning new measurement.
	Desc. 120 ft. over broken desert land.
15.00	Wash, drains N; asc. 40 ft. over E slope.
19.00	Point of spur, slopes N; desc. 80 ft. over NW slope.
25.00	Draw, drains N; thence over rolling desert land.
35.00	Road, State Route No. 45, bears N. 50° W. and S. 50° E.
39.96	The cor. of secs. 17, 18, 19 and 20.
	N. 89°20' W., bet. secs. 18 and 19.
	Asc. 40 ft. over rolling desert land.
11.00	Spur, slopes N. 32° W.; desc. 60 ft. over SW slope.
16.00	Wash, drains N. 30° W.; asc. 20 ft.
23.00	Spur, slopes N; desc. 40 ft. over W slope.
29.00	Underground pipeline, bears N. 8° W. and S. 8° E.

364

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
30.00	Draw, drains N. 10° W.; asc. over NE slope.
40.33	Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19, at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd. <div style="text-align: center;"> T 10 S R 25 E $\frac{1}{4}$ $\frac{S 18}{S 19}$ 1975 </div>
	Desc. 120 ft. over broken desert land.
60.00	Wash, drains N. 20° W. from S. 65° E.; asc. 40 ft. over NE slope.
72.00	Spur, slopes N; desc. 60 ft. over SW slope.
80.66	The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., described in the field notes of the E. bdy. of T. 10 S., R. 24 E., surveyed concurrently.
	From the cor. of secs. 17, 18, 19 and 20. North, bet. secs. 17 and 18. Desc. slightly over rolling desert land.
3.20	Dirt road, State Route No. 45, bears N. 50° W. and S. 50° E.; desc. 80 ft. over gentle NE slope.
20.00	Wash, drains W; asc. 80 ft. over SW slope.
31.00	Spur, slopes W; desc. 40 ft. over N slope.
38.50	Draw, drains W; asc. slightly over S slope.
40.08	The $\frac{1}{4}$ sec. cor. of secs. 17 and 18, monumented with a sandstone, 20 x 11 x 3 ins., protruding 10 ins. above ground, mkd. $\frac{1}{4}$ on the W face, and with a mound of stone to the W. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base to top, with brass cap mkd. <div style="text-align: center;"> T 10 S R 25 E $\frac{1}{4}$ S 18 S 17 1975 </div>
	Deposit the mkd. stone alongside the iron post. <hr style="width: 20%; margin: 10px auto;"/>
	N. 0°08' W., beginning new measurement. Asc. 40 ft. over rolling desert land.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
4.00	Spur, slopes W; thence over rolling desert land.
34.00	Desc. 80 ft. over N slope.
39.50	Wash, drains N. 85° W.
40.15	The cor. of secs. 7, 8, 17 and 18, monumented with a sandstone, 24 x 14 x 4 ins., protruding 12 ins. above ground, mkd. with 5 notches on the E and 4 notches on the S edges, and with a mound of stone to the W. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 10 S R 25 E S 7 S 8 S 18 S 17 1975 </div> Rebuild mound of stone W of cor. Deposit the mkd. stone alongside the iron post.
	From the cor. of secs. 8, 9, 16 and 17. N. 89°31' W., bet. secs. 8 and 17. Desc. 400 ft. over ledges on precipitous W slope.
8.00	Enter bottom land in Hells Hole Canyon, bears N and S.
13.50	Wash, in Hells Hole Canyon, drains N. 25° W.; asc. 240 ft. over precipitous E slope.
23.00	Spur, slopes N. 20° E.; desc. over NW slope.
27.00	Wash, drains N. 50° E.; asc. 300 ft. over steep SE slope.
39.00	Road on ridge top, bears N. 37° E. and S. 37° W.
39.45	The ¼ sec. cor. of secs. 8 and 17, monumented with a sandstone, 24 x 12 x 7 ins., firmly set 10 ins. in the ground, and plainly mkd. ¼ on the N face. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. <div style="text-align: center;"> T 10 S R 25 E S 8 ¼ S 17 1975 </div> Deposit the mkd. stone alongside the iron post. Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor. S. 89°56' W., beginning new measurement. Desc. 200 ft. over broken desert land.

366

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
23.00	Wash, drains N; asc. 40 ft. over E slope.
26.00	Spur, slopes N; desc. 120 ft. over steep W slope.
31.00	Draw, drains S. 15° W.; thence along draw draining nearly W.
40.53	The cor. of secs. 7, 8, 17 and 18.
N. 89°54' W., bet. secs. 7 and 18.	
1.00	Wash, drains W; asc. 20 ft. along N slope.
13.00	Spur, slopes N. 40° W.; desc. 120 ft. over rolling desert land.
36.00	Spur, slopes N. 80° W.; thence along S slope.
40.24	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 18, at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, $3\frac{1}{2}$ ft. base to top, with brass cap mkd. <div style="text-align: center;"> T 10 S R 25 E $\frac{1}{4}$ $\frac{S 7}{S 18}$ 1975 </div>
	Desc. 140 ft. over broken desert land.
51.00	Wash, drains N; asc. 100 ft. over broken NE slope.
58.00	Spur, slopes N. 20° W.; desc. 200 ft. over broken SW slope.
64.00	Evacuation Creek, with stream of alkaline water, 3 ins. deep, flows N; asc. 80 ft. over ledgy SE slope.
74.50	Underground pipeline, bears N. 20° W. and S. 20° E.
80.48	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., as described in the field notes of the E. bdy. of T. 10 S., R. 24 E., resurveyed concurrently.
From the cor. of secs. 7, 8, 17 and 18.	
N. 0°04' W., bet. secs. 7 and 8.	
Asc. 100 ft. over SW slope.	
13.00	Top of ascent, slopes W; desc. 60 ft. over NW slope.
23.00	Draw, drains W; asc. 60 ft. over SW slope.
28.00	Spur, slopes W; desc. 140 ft. over N slope.
39.50	Wash, drains N. 80° W.
40.37	The $\frac{1}{4}$ sec. cor. of secs. 7 and 8, monumented with a weathered sandstone, 18 x 10 x 5 ins., protruding 10 ins. above ground, and with a mound of stone to the W, harmoniously related to existing original cors. and is

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

accepted as the best available evidence of the original corner position.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 10 S R 25 E
 $\frac{1}{4}$
 |
 S 7 | S 8
 |
 1975

Rebuild mound of stone W of cor.

Deposit the unmkd. stone alongside the iron post.

N. 0°50' W., beginning new measurement.

Asc. 100 ft. over broken desert land.

- 9.00 Rim above White River, curves S. 80° W. and N. 60° E.; desc. 500 ft. over rocky ledges on precipitous N slope.
- 20.00 Enter bottom land.
- 26.00 Left bank of the White River, bears N. 80° E. and S. 80° W., river course W.
- 29.00 Right bank of the White River, bears N. 87° E. and S. 87° W.; asc. 260 ft. over SW slope.
- 38.87 The cor. of secs. 5, 6, 7 and 8, monumented with a sandstone, 16 x 8 x 6 ins., protruding 8 ins. above ground, mkd. with 5 notches on the S and E edges, and with a scattered mound of stone alongside.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T 10 S R 25 E
 S 6 | S 5
 S 7 | S 8
 1975

Deposit the mkd. stone alongside the iron post.

From the cor. of secs. 4, 5, 8 and 9.

N. 88°51' W., bet. secs. 5 and 8.

Desc. 180 ft. over SW slope.

- 12.50 Wash, drains N. 85° W.; asc. slightly.
- 19.00 Low ridge, bears N. 60° W. and S. 60° E.; desc. 40 ft. over SW slope.
- 24.00 Head of draw, drains S; asc. slightly over SE slope.

368

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
30.00	Top of asc. slopes S; desc. 80 ft. over SW slope.
40.00	The $\frac{1}{4}$ sec. cor. of secs. 5 and 8, monumented with a sandstone, 28 x 8 x 6 ins., protruding 8 ins. above ground, mkd. $\frac{1}{4}$ on the N face. At the corner point Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd. T 10 S R 25 E $\frac{1}{4}$ S 5 S 8 1975 Deposit the mkd. stone alongside the iron post. S. $88^{\circ}44'$ W., beginning new measurement. Desc. 240 ft. over rocky ledge, on broken SW slope.
7.00	Enter bottom of Hells Hole Canyon, bears N. 45° W. and S. 45° E.
11.50	Wash, drains, N. 45° E.; asc. 120 ft. over NE slope.
14.50	Point of spur, slopes N; desc. 200 ft. over precipitous W slope.
17.00	Left bank of the White River, bears N and S; river course S; through river and bottom land.
32.00	Right bank of the White River, bears N. 30° E. and S. 30° W.; asc. 240 ft. over SE slope.
40.59	The cor. of secs. 5, 6, 7 and 8. N. $88^{\circ}38'$ W., bet. secs. 6 and 7. Asc. 80 ft. over rocky SE slope.
5.00	Spur, slopes S. 40° W.; desc. 240 ft. over W slope.
11.00	Wash, drains S; asc. 200 ft. over broken SE slope.
20.00	Spur, slopes N. 40° E.; asc. 240 ft. along N slope.
30.00	Spur, slopes N; desc. 80 ft. over NW slope.
34.50	Draw, drains N; asc. 40 ft. over NE slope.
37.00	Dirt road, on low ridge, bears N. 35° W. and S. 35° E.
40.13	The $\frac{1}{4}$ sec. cor. of secs. 6 and 7, monumented with a sandstone, 16 x 10 x 6 ins., protruding 10 ins. above ground, mkd. $\frac{1}{4}$ on the N face. At the corner point Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
	T 10 S R 25 E $\frac{1}{4}$ $\frac{S 6}{S 7}$ 1975
	Deposit the mkd. stone alongside the iron post.

	N. 89°59' W., beginning new measurement.
	Desc. 240 ft. over rocky land.
30.00	Draw, drains S. 50° W.
40.05	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., as described in the field notes of the E. bdy. of T. 10 S., R. 24 E., resurveyed concurrently.
	From the cor. of secs. 5, 6, 7 and 8.
	N. 0°03' W., bet. secs. 5 and 6.
	Asc. 160 ft. over SE changing to E slope.
18.00	Draw, drains S. 13° E.; asc. 80 ft. over SW slope.
26.00	Rim of White River, curves N and S. 30° E.; desc. along precipitous and ledgy E slope.
38.00	Draw, drains E.
39.96	Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6, at proportionate dist.; falls on steep ledges and cannot be perpetuated; there is no remaining evidence of the original cor. Asc. along precipitous E slope.
44.48	Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 5 and 6.
	Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	W C T 10 S R 25 E $\frac{1}{4}$ S 6 S 5 ↓ 1975
	Cor. is located on rim of White Canyon, 800 ft. high, bears N. 30° E. and curves S.
	Asc. gradually 40 ft.
66.00	Trail road, bears S. 75° W. and curves N; asc. 40 ft. along E slope of spur projecting S.
80.21	The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., heretofore described.

370

Dependent Resurvey of the Subdivisional Lines of
T. 10 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	General Description
	<p>This township is located on the south side of the White River, except sec. 6 and portions of secs. 5, 7 and 8, and on the Utah-Colorado State line. The area is drained in a northerly direction by deep ravines and canyons which drain into the White River.</p> <p>The soil is sandy with sandstone and shale prevalent throughout. Scattered juniper and pinon is found on the north and east portions of the township and scattered cottonwoods are found along the White River.</p> <p>The White River and Evacuation Creek, with a stream of alkaline water, both located in the northwest portion of the township, is the only water found in the township. The west half of the township is accessible by means of State Routes Nos. 45 and 207, both of which are improved dirt roads. Oil shale is the only mineral noted in the township.</p> <p>The mean of a number of observations of the magnetic declination throughout the township is $14^{\circ}30'$ E.</p>

372

CERTIFICATE OF SURVEY

(I) ~~(We)~~ Glen B. Hatch, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 30th day of January, 1975, (I) ~~(We)~~ have retraced the Utah-Colorado State Boundary line bet. mile cor's. 199 and 206, and dependently resurveyed the Second Standard Parallel South along the South Boundary of Township 10 South, Range 25 East, the north boundary and the subdivisional lines of Township 10 South, Range 25 East

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

December 7, 1976
(Date)

Glen B Hatch
(Cadastral Surveyor)
Supervisory

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Washington, D.C.
Denver, Colorado

The foregoing field notes of the retracement of the Utah-Colorado State Boundary line bet. mile post 199 and 206, and the dependent resurvey of the Second Standard Parallel South, along the South Boundary of Township 10 South, Range 25 East, and the north boundary and subdivisional lines of Township 10 South, Range 25 East

executed by Glen B. Hatch, Supervisory Cadastral Surveyor having been critically examined and found correct, are hereby approved.

JAN 18 1980
(Date)

J. Voorhes
(Chief, Division of Cadastral Survey)

Chief, Cadastral Survey Examination and Approval Staff
CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in~~
~~, is a true copy of the original field notes.~~

(Date)

(Chief, Division of Cadastral Survey)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
ORIGINAL

R599 -9- 373

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF

THE WEST BOUNDARY,

A PORTION OF THE NORTH AND SOUTH BOUNDARIES,

AND A PORTION OF THE SUBDIVISIONAL LINES

OF

TOWNSHIP 16 SOUTH, RANGE 2 WEST

Of the Salt Lake Meridian,

In the State of Utah

EXECUTED BY

Craig P. Sylvester Supervisory Cadastral Surveyor

Under special instructions dated January 10, 1974, approved January 14, 1974

_____, which provided for the surveys included under U.S. Survey/Group
Number 551, and assignment instructions dated February 27, 1974.

Survey commenced March 27, 1974

Survey completed May 17, 1974

INDEX DIAGRAM

Township 16 South, Range 2 West,

13	12	11			
10 6	56 8	45 4	38 8	2	1
55	54	45	37		
9 7	53 8	44 9	36 10	28 11	12
53	52	43	35	28	20
8 18	52 17	43 16	35 15	26 14	19 13
51	51	42	34	25	18
8 19	50 20	41 21	33 22	24 23	17 24
49	48	39	32	24	17
7 30	47 29	40 28	31 27	22 26	16 25
47		39	30	22	15
6 31	46 32	38 33	29 34	21 35	13 36
5	4	3	3	2	

Dependent Resurvey of a portion of the S. Bdy. of
T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS

Dependent Resurvey of a portion of the S. Bdy. of
T. 16 S., R. 2 W., Salt Lake Meridian, Utah
(Restoring the 1871 survey by Ferdinand Dickert)

Beginning at the cor. of secs. 1, 2, 35 and 36, on the S.
bdy. of the Tp., monumented with a limestone,
16 x 8 x 6 ins., firmly set and plainly mkd. 5 notches on
W and 1 on E edges.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 16 S R 2 W

S 35	S 36
S 2	S 1

T 17 S R 2 W
1974

Deposit the mkd. stone alongside the iron post.

Set a steel fence post alongside the iron post.

S. 89°48' W., bet. secs. 2 and 35.

Over rolling hills, through sagebrush and shadscale; desc.
W slope.

12.00 Sevier River, 2.00 chs. wide, 2 ft. deep, flows N. 38° W.,
over gentle rolling land.

40.00 Point for the ¼ sec. cor. of secs. 2 and 35, at propor-
tionate distance; there is no remaining evidence of the
original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 16 S R 2 W

¼	S 35
	S 2

T 17 S
1974

Continue over gently rolling land, draining northeasterly.

80.00 Point for the cor. of secs. 2, 3, 34 and 35, at propor-
tionate distance; there is no remaining evidence of the
original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 16 S R 2 W

S 34	S 35
S 3	S 2

T 17 S
1974

Dependent Resurvey of a portion of the S. Bdy. of
T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS		
	S. 89°48' W., bet. secs. 3 and 34.	
	Over gentle rolling land, through sagebrush and shadscale.	
39.00	Trail road, bears N and S.	
40.00	Point for the ¼ sec. cor. of secs. 3 and 34, at proportionate distance; there is no remaining evidence of the original corner.	
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.	
	T 16 S R 2 W	
	$\frac{1}{4} \frac{S \ 34}{S \ 3}$	
	T 17 S 1974	
46.30	Wire fence, bears N and S.	
80.00	The cor. of secs. 3, 4, 33 and 34, monumented with a broken sandstone, 16 x 8 x 4 ins., firmly set and plainly mkd. 3 notches on E and W edges.	
	At the corner point	
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.	
	T 16 S R 2 W	
	$\begin{array}{c c} S \ 33 & S \ 34 \\ \hline S \ 4 & S \ 3 \end{array}$	
	T 17 S 1974	
	Deposit the mkd. stone alongside the iron post.	
	N. 89°57' W., bet. secs. 4 and 33.	
	Over rolling land, through sagebrush and shadscale.	
8.09	Trail road, bears N. 60° E. and S. 60° W.; asc. SE slope.	
20.005	Point for the E 1/16 sec. cor. of secs. 4 and 33.	
	Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.	
	T 16 S R 2 W	
	$E \ 1/16 \frac{S \ 33}{S \ 4}$	
	T 17 S R 2 W 1974	
28.00	Low ridge, bears NE and SW; desc. W slope.	

Dependent Resurvey of a portion of the S. Bdy. of
T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS	
34.21	Right-of-way fence, bears N. 1°45' E. and S. 1°45' W., over gentle rolling land.
35.70	U.S. Highway No. 91, bears N. 1°45' E. and S. 1°45' W.
37.21	Right-of-way fence, bears N. 1°45' E. and S. 1°45' W.
37.83	Power line, bears N. 2° E. and S. 2° W.
40.01	Point for the ¼ sec. cor. of secs. 4 and 33, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 16 S R 2 W ¼ $\frac{S 33}{S 4}$ T 17 S 1974 Set a steel fence post alongside the iron post.
60.015	Point for the W 1/16 sec. cor. of secs. 4 and 33. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 16 S R 2 W W 1/16 $\frac{S 33}{S 4}$ T 17 S 1974 Set a steel fence post alongside the iron post.
80.02	The cor. of secs. 4, 5, 32 and 33, monumented with a sandstone, 20 x 10 x 2 ins., firmly set and plainly mkd. 4 notches on E and 2 on W edges. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 16 S R 2 W $\frac{S 32}{S 5} \mid \frac{S 33}{S 4}$ T 17 S 1974 Deposit the mkd. stone alongside the iron post. Cor. is located at the cor. of fence, bearing N, S and W.
	S. 89°42' W., bet. secs. 5 and 32.

Dependent Resurvey of a portion of the S. Bdy. of
T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS	
	Over gentle rolling land, along fence line with trail road on N side of fence.
40.26	<p>The $\frac{1}{4}$ sec. cor. of secs. 5 and 32, monumented with a sandstone, 18 x 10 x 6 ins., firmly set and plainly mkd. $\frac{1}{4}$ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 2 W</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S\ 32}{S\ 5}$</p> <p style="text-align: center;">T 17 S 1974</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Cor. is located in E - W fence line with trail road on N side of fence.</p>
21.69	S. 89 ^o 45' W., beginning new measurement.
	Intersect fence line from N.
40.27	<p>Point for the cor. of secs. 5, 6, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 2 W</p> <p style="text-align: center;">$\frac{S\ 31}{S\ 6}$ $\frac{S\ 32}{S\ 5}$</p> <p style="text-align: center;">T 17 S 1974</p> <p>Cor. is located 2 lks. dist. N of E - W fence line with trail road on N side of fence.</p>
40.27	<p>S. 89^o45' W., bet. secs. 6 and 31.</p> <p>Over nearly level land, along fence line with trail road on N side of fence.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

380

Dependent Resurvey of a portion of the S. Bdy. of
T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS

T 16 S R 2 W

$$\frac{1}{4} \frac{S 31}{S 6}$$
T 17 S
1974

Cor. is located 2½ lks. dist., N of E - W fence line.

80.54 The cor. of Tps. 16 and 17 S., Rs. 2 and 3 W., monumented with a sandstone, 20 x 12 x 6 ins., firmly set and plainly mkd. 6 notches on N, S, E and W edges.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 16 S
R 3 W R 2 W
$$\frac{S 36}{S 1} \quad \frac{S 31}{S 6}$$
T 17 S
1974

Deposit the mkd. stone alongside the iron post.

Cor. is located at the cor. of fence bearing E, W and N with trail road N of fence.

Dependent Resurvey of the W. Bdy., T. 16 S.,
R. 2 W., Salt Lake Meridian, Utah
(Restoring the 1871 survey by Ferdinand Dickert)

N. 0°01' E., bet. secs. 31 and 36.

Over gentle rolling land, through sagebrush and shadscale undergrowth, along fence.

19.94 Cor. of fence, bears S and E.

20.11 Point for the S 1/16 sec. cor. of secs. 31 and 36.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 16 S
R 3 W R 2 W
S 1/16

S 36 S 31

1974

40.22 The ¼ sec. cor. of secs. 31 and 36, determined by a steel fence post, firmly set in the ground and surrounded by a small mound of stone. This position is harmoniously related to existing original cors., and is accepted as the best available evidence of the original cor. position.

Dependent Resurvey of the W. Bdy., T. 16 S.,
R. 2 W., Salt Lake Meridian, Utah

CHAINS

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 16 S
R 3 W R 2 W
|
¼
|
S 36 | S 31
|
1974

Set the steel fence post alongside and raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

N. 0°09' E., beginning new measurement.

Over rolling land, through dense sagebrush.

40.08 The cor. of secs. 25, 30, 31 and 36, monumented with a granite stone, 14 x 10 x 6 ins., firmly set and plainly mkd. 6 grooves on E and W, 5 on N and 1 on S faces.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.

T 16 S
R 3 W R 2 W

S 25 | S 30
S 36 | S 31

1974

Deposit the mkd. stone alongside the iron post.

N. 0°06' E., bet. secs. 25 and 30.

Over rolling land, through dense sagebrush.

14.92 Wash, drains E.

34.22 Wash, drains E.

40.71 Point for the ¼ sec. cor. of secs. 25 and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 16 S
R 3 W R 2 W
|
¼
|
S 25 | S 30
|
1974

Set a steel fence post alongside the iron post.

Dependent Resurvey of the W. Bdy., T. 16 S.,
R. 2 W., Salt Lake Meridian, Utah

CHAINS	
81.42	<p>The cor. of secs. 19, 24, 25 and 30, monumented with a sandstone, 12 x 9 x 8 ins., firmly set and plainly mkd. 4 notches on N and 2 on S edges.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 3 W R 2 W</p> <p style="text-align: center;">S 24 S 19 S 25 S 30</p> <p style="text-align: center;">1974</p> <p>Deposit the mkd. stone alongside the iron post.</p>
6.00	<p>N. 1°01' W., bet. secs. 19 and 24.</p> <p>Over gentle rolling land, through sagebrush and shadscale.</p>
22.20	<p>Wash, drains E.</p>
24.09	<p>Trail road, bears NE and SW.</p>
24.09	<p>Fence, bears N. 89° E. and S. 89° W.</p>
41.12	<p>The ¼ sec. cor. of secs. 19 and 24, monumented with a sandstone, 18 x 10 x 6 ins., firmly set and plainly mkd. ¼ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 3 W R 2 W ¼ S 24 S 19 1974</p> <p>Deposit the mkd. stone alongside the iron post.</p>
3.65	<p>N. 0°54' W., beginning new measurement.</p> <p>Trail road, bears NW and SE.</p>
39.71	<p>The cor. of secs. 13, 18, 19 and 24, monumented with a sandstone, 18 x 6 x 5 ins., firmly set and dimly mkd. 3 notches on S and N edges.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the W. Bdy., T. 16 S.,
R. 2 W., Salt Lake Meridian, Utah

CHAINS					
	<p style="text-align: center;">T 16 S R 3 W R 2 W</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 13</td> <td style="padding: 0 5px;">S 18</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 24</td> <td style="padding: 0 5px;">S 19</td> </tr> </table> <p style="text-align: center;">1974</p> <p>Deposit the mkd. stone alongside the iron post.</p>	S 13	S 18	S 24	S 19
S 13	S 18				
S 24	S 19				
	<p>N. 0°01' W., bet. secs. 13 and 18.</p> <p>Over rolling land, through dense sagebrush.</p>				
15.70	Wash, 25 lks. wide, 4 ft. deep, drains SE; asc. SW slope of hill.				
24.00	Enter scattering juniper growth.				
39.87	The ¼ sec. cor. of secs. 13 and 18, monumented with a sandstone, 16 x 9 x 5 ins., firmly set, no markings, only rock in the immediate area.				
	<p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 3 W R 2 W ¼ S 13 S 18 1974</p> <p>Deposit the unmkd. stone alongside the iron post.</p>				
	<p style="text-align: center;">—————</p> <p>N. 1°44' E., beginning new measurement.</p>				
5.90	Top of hill, bears NW and SE; desc. NE slope.				
20.00	Base of hill, bears NW and SE; over gentle rolling land.				
40.59	The cor. of secs. 7, 12, 13 and 18, monumented with a sandstone, 20 x 12 x 10 ins., firmly set and dimly mkd. 4 notches on S and 2 on N edges.				
	<p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 3 W R 2 W</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 12</td> <td style="padding: 0 5px;">S 7</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 13</td> <td style="padding: 0 5px;">S 18</td> </tr> </table> <p style="text-align: center;">1974</p> <p>Deposit the mkd. stone alongside the iron post.</p>	S 12	S 7	S 13	S 18
S 12	S 7				
S 13	S 18				

Dependent Resurvey of the W. Bdy., T. 16 S.,
R. 2 W., Salt Lake Meridian, Utah

CHAINS	
	<p>N. 0°06' W., bet. secs. 7 and 12.</p>
	<p>Over rolling land, through sagebrush and scattering juniper.</p>
4.40	<p>Wash, 30 lks. wide, 6 ft. deep, drains E.</p>
5.65	<p>Dirt road, bears E and W.</p>
21.48	<p>Fence, bears E and W.</p>
40.29	<p>The ¼ sec. cor. of secs. 7 and 12, monumented with a quartzite stone, 12 x 10 x 3 ins., firmly set, no markings, stone foreign to this area, and is accepted as the best available evidence of the original cor.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<div style="text-align: center;"> <p>T 16 S R 3 W R 2 W ½ S 12 S 7 1974</p> </div>
	<p>Deposit the unmkd. stone alongside the iron post.</p>
	<p>N. 0°05' W., beginning new measurement.</p>
	<p>Asc. SE slope of hill.</p>
38.67	<p>Spur, slopes E; desc. NE slope.</p>
40.12	<p>The cor. of secs. 1, 6, 7 and 12, monumented with a sandstone, 18 x 14 x 12 ins., firmly set and plainly mkd. 5 notches on S and 1 on N edges.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<div style="text-align: center;"> <p>T 16 S R 3 W R 2 W S 1 S 6 S 12 S 7 1974</p> </div>
	<p>Deposit the mkd. stone alongside the iron post.</p>
	<p>N. 0°01' E., bet. secs. 1 and 6.</p>
	<p>Over mountainous land, through scattering juniper growth.</p>
39.90	<p>Point for the ¼ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.</p>

Dependent Resurvey of the W. Bdy., T. 16 S.,
R. 2 W., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 16 S
R 3 W R 2 W
 |
 ¼
 |
S 1 | S 6
 |
1974

Set a steel fence post alongside the cor.

79.80 The cor. of Tps. 15 and 16 S., Rs. 2 and 3 W., monumented with a sandstone, 12 x 8 x 6 ins., firmly set and plainly mkd. 6 notches on N, S, E and W edges.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 15 S
R 3 W R 2 W

S 36 | S 31
S 1 | S 6

T 16 S
1974

Deposit the mkd. stone alongside the iron post.

Dependent Resurvey of a portion of the N. Bdy. of
T. 16 S., R. 2 W., Salt Lake Meridian, Utah
(Restoring the 1871 survey by Ferdinand Dickert)

Beginning at the cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., monumented with a sandstone, 24 x 14 x 3 ins., firmly set and plainly mkd. 3 notches on E and W edges.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 15 S R 2 W

S 33 | S 34
S 4 | S 3

T 16 S
1974

Deposit the mkd. stone alongside the iron post.

Cor. is located 36 lks. dist., W of N - S fence line.

S. 89°43' W., bet. secs. 4 and 33.

Dependent Resurvey of a portion of the N. Bdy. of
T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS							
	Over gentle rolling land, through sagebrush.						
3.85	Dirt road, bears N. 10° E. and S. 10° W.						
40.13	The ¼ sec. cor. of secs. 4 and 33, monumented with a sandstone, 12 x 10 x 8 ins., firmly set and plainly mkd. ¼ on N face.						
	At the corner point						
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.						
	T 15 S R 2 W						
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">¼</td> <td style="text-align: center;"> <table border="1" style="border-collapse: collapse;"> <tr> <td style="padding: 2px;">S 33</td> </tr> <tr> <td style="padding: 2px;">S 4</td> </tr> </table> </td> </tr> </table>	¼	<table border="1" style="border-collapse: collapse;"> <tr> <td style="padding: 2px;">S 33</td> </tr> <tr> <td style="padding: 2px;">S 4</td> </tr> </table>	S 33	S 4		
¼	<table border="1" style="border-collapse: collapse;"> <tr> <td style="padding: 2px;">S 33</td> </tr> <tr> <td style="padding: 2px;">S 4</td> </tr> </table>	S 33	S 4				
S 33							
S 4							
	T 16 S 1974						
	Deposit the mkd. stone alongside the iron post.						
	Cor. is located at the cor. of old abandoned fence line projecting N and W.						
	West, beginning new measurement.						
	Over nearly level land.						
40.24	The cor. of secs. 4, 5, 32 and 33, monumented with a sandstone, 16 x 10 x 6 ins., firmly set and plainly mkd. 4 notches on E and 2 on W edges.						
	At the corner point						
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.						
	T 15 S R 2 W						
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">S 32</td> <td style="text-align: center;"> </td> <td style="text-align: center;">S 33</td> </tr> <tr> <td style="text-align: center;">S 5</td> <td style="text-align: center;"> </td> <td style="text-align: center;">S 4</td> </tr> </table>	S 32		S 33	S 5		S 4
S 32		S 33					
S 5		S 4					
	T 16 S 1974						
	Deposit the mkd. stone alongside the iron post.						
	S. 89°57' W., bet. secs. 5 and 32.						
	Over nearly level land, through sagebrush and grass.						
40.00	The ¼ sec. cor. of secs. 5 and 32, monumented with a sandstone, 14 x 8 x 6 ins., firmly set and plainly mkd. ¼ on N face.						
	At the corner point						
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.						

Dependent Resurvey of a portion of the N. Bdy. of
T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS	
	<p style="text-align: center;">T 15 S R 2 W</p> <p style="text-align: center;">$\frac{1}{4} \frac{S 32}{S 5}$</p> <p style="text-align: center;">T 16 S 1974</p> <p>from which</p> <p style="padding-left: 40px;">A stock well, bears S. 5°08' E., 40.68 chs. dist.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p style="text-align: center;">_____</p> <p>N. 89°45' W., beginning new measurement.</p> <p>Over rolling land.</p> <p>17.64 Spur, slopes NE, enter scattering juniper.</p> <p>23.24 Small draw, drains NE.</p> <p>25.74 Spur, slopes NE.</p> <p>32.44 Draw, drains N. 60° E.</p> <p>40.24 The cor. of secs. 5, 6, 31 and 32, monumented with a sandstone, 18 x 6 x 4 ins., firmly set and plainly mkd. 5 notches on E and 1 on W edges.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 15 S R 2 W</p> <p style="text-align: center;">$\frac{S 31}{S 6} \mid \frac{S 32}{S 5}$</p> <p style="text-align: center;">T 16 S 1974</p> <p>Deposit the mkd. stone alongside the iron post.</p>
	<p>N. 89°39' W., bet. secs. 6 and 31.</p> <p>Over rolling land, through medium dense juniper growth.</p> <p>3.30 Fence, bears N. 50° W. and S. 50° E.</p> <p>40.24 The ¼ sec. cor. of secs. 6 and 31, monumented with a sandstone, 14 x 12 x 6 ins., firmly set and plainly mkd. ¼ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a portion of the N. Bdy. of
T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS	
	<p style="text-align: center;">T 15 S R 2 W</p> <p style="text-align: center;"> $\frac{1}{4}$ $\frac{S\ 31}{S\ 6}$ </p> <p style="text-align: center;">T 16 S 1974</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears S. 89° E., 8 lks. dist., mkd. $\frac{1}{4}$ S6 BT.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°55' W., beginning new measurement.</p> <p>Over rolling land, through medium dense juniper growth.</p> <p>37.00 Trail road, bears N and S.</p> <p>40.25 The cor. of Tps. 15 and 16 S., Rs. 2 and 3 W., previously described.</p>
	<p style="text-align: center;">Dependent Resurvey of a portion of the Subdivisional Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah (Restoring the 1871 survey by Ferdinand Dickert)</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp.</p> <p>N. 0°03' W., bet. secs. 35 and 36.</p> <p>Over rolling hills, through scattering juniper growth; asc. gentle S slope.</p> <p>20.045 Point for the S 1/16 sec. cor. of secs. 35 and 36.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T 16 S R 2 W S 1/16 S 35 S 36 1974 </p> <p>Set a steel fence post alongside the iron post.</p> <p>40.09 The $\frac{1}{4}$ sec. cor. of secs. 35 and 36, monumented with a sandstone, 12 x 10 x 5 ins., firmly set and plainly mkd. $\frac{1}{4}$ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone to top of brass cap, mkd.</p>

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS

T 16 S R 2 W
 $\frac{1}{4}$
 |
 S 35 | S 36
 |
 1974

Deposit the mkd. stone alongside the iron post.

Set a steel fence post alongside the iron post.

N. $0^{\circ}06'$ W., beginning new measurement.

Over rolling hills, along E slope.

12.10 Small spur, slopes E.

40.68 The cor. of secs. 25, 26, 35 and 36, monumented with a sandstone, 16 x 8 x 5 ins., firmly set and plainly mkd. 1 dot on S and E faces.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 16 S R 2 W
 $\frac{1}{4}$
 |
 S 26 | S 25
 S 35 | S 36
 1974

Deposit the mkd. stone alongside the iron post.

Set a steel fence post alongside the iron post.

From the calculated point for the cor. of secs. 25 and 36, on the E. bdy. of the T., in the Sevier Bridge Reservoir.

N. $89^{\circ}32'$ W., bet. secs. 25 and 36.

Over water.

40.40 Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36, at proportionate distance; falls in Sevier Bridge Reservoir.

45.30 West shore of reservoir, bears N and S, over rolling land.

45.80 Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 25 and 36.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

W C
 T 16 S R 2 W
 $\frac{1}{4}$ $\frac{S 25}{S 36}$ \rightarrow
 1974

Dependent Resurvey of a portion of the Subdivisional Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS	
57.00	State road, under construction, bears N and S; asc. gentle E slope.
80.80	The cor. of secs. 25, 26, 35 and 36.
N. 0°12' W., bet. secs. 25 and 26.	
Over rolling hills, along E slope, through scattering juniper growth.	
1.40	Small spur, slopes N. 80° E.
18.50	Small draw, drains N. 70° E.
24.50	Spur, slopes N. 50° E.
40.10	The ¼ sec. cor. of secs. 25 and 26, monumented with a limestone, 14 x 10 x 10 ins., firmly set and dimly mkd. ¼ on W face.
At the corner point	
Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone to top of brass cap, mk.d	
<p style="text-align: center;">T 16 S R 2 W</p> <p style="text-align: center;"> </p> <p style="text-align: center;">¼</p> <p style="text-align: center;"> </p> <p style="text-align: center;">S 26 S 25</p> <p style="text-align: center;"> </p> <p style="text-align: center;">1974</p>	
Deposit the mkd. stone alongside the iron post.	
Set a steel fence post alongside the iron post.	
N. 1°13' E., beginning new measurement.	
4.35	Draw, drains E.
19.75	Spur, slopes E.
29.00	Wash, drains E.
39.75	The cor. of secs. 23, 24, 25 and 26, monumented with a sandstone, 14 x 10 x 8 ins., firmly set and plainly mkd. 2 notches on S and 1 on E edges.
At the corner point	
Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of brass cap, mkd.	
<p style="text-align: center;">T 16 S R 2 W</p> <p style="text-align: center;">S 23 S 24</p> <p style="text-align: center;">S 26 S 25</p> <p style="text-align: center;">1974</p>	

Dependent Resurvey of a portion of the Subdivisional Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS	
	<p>Deposit the mkd. stone alongside the iron post.</p>
	<p>From the cor. of secs. 24 and 25, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., projecting 6 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 2 W R 1 W</p> <p style="text-align: center;">S 24 S 19 S 25 </p> <p style="text-align: center;">1973</p> <p>N. 89°40' W., bet. secs. 24 and 25.</p>
0.50	Sevier Bridge Reservoir shoreline, bears NW and SE; thence over water.
40.23	Point for the ¼ sec. cor. of secs. 24 and 25, at proportionate distance; falls in Sevier Bridge Reservoir.
57.95	Sevier Bridge Reservoir shoreline, bears NE and SW, over rolling land.
61.15	Hard surface road, bears N. 7°25' E. and S. 7°25' W.
62.58	Power line, bears N. 7°25' E. and S. 7°25' W.; asc. E slope, through scattering juniper growth.
74.30	Spur, slopes SE; desc. SW slope.
80.46	The cor. of secs. 23, 24, 25 and 26.
	<p>N. 0°36' E., bet. secs. 23 and 24.</p> <p>Over rolling hills, along E slope, through scattering juniper growth.</p>
29.30	Trail road, bears E and W in draw, that drains E; asc. S slope.
39.86	<p>The ¼ sec. cor. of secs. 23 and 24, monumented with a limestone, 16 x 12 x 6 ins., firmly set and plainly mkd. ¼ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of brass cap, mkd.</p> <p style="text-align: center;">T 16 S R 2 W ¼ S 23 S 24 1974</p>
	<p>Deposit the mkd. stone alongside the iron post.</p>

Dependent Resurvey of a portion of the Subdivisional Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS												
	<p>North, beginning new measurement.</p> <p>Over rolling hills; asc. S slope.</p> <p>7.40 Spur, slopes S. 80° E.; along E slope.</p> <p>13.50 Draw, drains E.</p> <p>34.60 Draw, drains E.</p> <p>39.00 Spur, slopes E.</p> <p>40.16 Point for the cor. of secs. 13, 14, 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base to top of brass cap, mkd.</p> <p style="text-align: center;">T 16 S R 2 W</p> <p style="text-align: center;"> <table border="0"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 14</td> <td style="padding: 0 5px;">S 13</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 23</td> <td style="padding: 0 5px;">S 24</td> </tr> </table> </p> <p style="text-align: center;">1974</p>	S 14	S 13	S 23	S 24							
S 14	S 13											
S 23	S 24											
	<p>From the cor. of secs. 13 and 24, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., projecting 6 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T 16 S</p> <p style="text-align: center;">R 2 W R 1 W</p> <p style="text-align: center;"> <table border="0"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 13</td> <td style="padding: 0 5px;">S 18</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 24</td> <td style="padding: 0 5px;"></td> </tr> </table> </p> <p style="text-align: center;">1973</p> <p>S. 89°54' W., bet. secs. 13 and 24.</p> <p>Over rolling land, through shadscale and sagebrush.</p> <p>17.60 Wash, 10 lks. wide, 5 ft. deep, drains NW.</p> <p>35.45 Old hard surface road, (unimproved) bears N. 26° E. and S. 26° W.</p> <p>40.30 Point for the ¼ sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 2 W</p> <p style="text-align: center;"> <table border="0"> <tr> <td style="padding: 0 5px;">¼</td> <td style="border-right: 1px solid black; padding: 0 5px;">S 13</td> <td style="padding: 0 5px;">S 24</td> </tr> <tr> <td></td> <td style="border-right: 1px solid black; padding: 0 5px;">S 24</td> <td></td> </tr> </table> </p> <p style="text-align: center;">1974</p> <p>Set a steel fence post alongside the iron post.</p> <p>41.13 Power line, bears N. 24° E. and S. 24° W.</p>	S 13	S 18	S 24		¼	S 13	S 24		S 24		
S 13	S 18											
S 24												
¼	S 13	S 24										
	S 24											

Dependent Resurvey of a portion of the Subdivisional Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS		
57.64	Wash, 10 lks. wide, 4 ft. deep, drains N; asc. W slope.	
58.95	Point selected for the witness W 1/16 sec. cor. of secs. 13 and 24. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.	
	<p>W C T 16 S R 2 W</p>	
	<p>W 1/16 ← $\frac{S\ 13}{S\ 24}$</p>	
	1974	
	Set a steel fence post alongside the iron post.	
60.04	Center line of highway, bears N. 0°05' E. and S. 0°05' W., to Yuba Dam State Park.	
60.45	True point for the W 1/16 sec. cor. of secs. 13 and 24, falls within highway right-of-way and cannot be perpetuated.	
74.34	Draw, drains S. 70° E.	
80.60	The cor. of secs. 13, 14, 23 and 24.	
	N. 0°10' E., bet. secs. 13 and 14.	
	Over broken hills, along E slope and through lightly scattering juniper growth.	
4.14	Spur, slopes E.	
19.75	Draw, drains E.	
22.25	Spur, slopes E.	
39.75	Ravine, drains E.	
40.16	Point for the ¼ sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., on solid rock, in a mound of stone, 3 ft. base to top of brass cap, mkd.	
	<p>T 16 S R 2 W ¼ S 14 S 13 1974</p>	
	Set a steel fence post alongside the iron post.	
57.60	Spur, slopes E.	
60.24	Point for the N 1/16 sec. cor. of secs. 13 and 14. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.	

Dependent Resurvey of a portion of the Subdivisional Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS		
	<p style="text-align: center;">T 16 S R 2 W N 1/16 S 14 S 13 1974</p> <p>Set a steel fence post alongside the iron post.</p> <p>67.80 Rise, slopes N. 75° E., desc. N slope.</p> <p>80.32 The cor. of secs. 11, 12, 13 and 14, determined by an old fence cor., bearing N and SW, and a limestone, 14 x 8 x 6 ins., loosely set, with illegible markings.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 2 W S 11 S 12 S 14 S 13 1974</p> <p>Deposit the mkd. stone alongside the iron post.</p>	
	<p>From the cor. of secs. 12 and 13, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., projecting 6 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 2 W R 1 W S 12 S 13 S 7 1974</p> <p>S. 89°45' W., bet. secs. 12 and 13.</p> <p>Over rolling land, through sagebrush and shadscale.</p> <p>40.62 The ¼ sec. cor. of secs. 12 and 13, monumented with a sandstone, 10 x 10 x 6 ins., firmly set and plainly mkd. ¼ on N face.</p> <p>At the corner point.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 2 W ¼ S 12 S 13 1974</p> <p>Deposit the mkd. stone alongside the iron post.</p>	

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS	
	S. 89°59' W., beginning new measurement.
7.30	Wash, 30 lks. wide, 4 ft. deep, drains N; asc. gradual E slope.
18.57	Highway to Yuba Dam State Park, bears S. 0°50' W. and curves NW.
23.50	Spur, slopes N.
28.85	Spur, slopes N; desc. W slope.
40.10	The cor. of secs. 11, 12, 13 and 14.
	From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp.
	N. 0°42' E., bet. secs. 34 and 35.
	Over gently rolling land, through sagebrush and shadscale.
40.20	The $\frac{1}{4}$ sec. cor. of secs. 34 and 35, monumented with a sandstone, 16 x 8 x 6 ins., firmly set and plainly mkd. $\frac{1}{4}$ on W face.
	At the corner point
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 16 S R 2 W</p> <p style="text-align: center;"> $\frac{1}{4}$ S 34 S 35 1974 </p>
	Deposit the mkd. stone alongside the iron post.
	N. 0°35' W., beginning new measurement.
	Over nearly level land, draining northeasterly.
36.50	Wash, drains northeasterly to Sevier River.
40.12	The cor. of secs. 26, 27, 34 and 35, determined latitudinally by an old fence line bearing E and W and longitudinally by proportionate measurement.
	At the corner point
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 16 S R 2 W</p> <p style="text-align: center;"> S 27 S 26 S 34 S 35 1974 </p>

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS	
	From the cor. of secs. 25, 26, 35 and 36.
	S. 89°28' W., bet. secs. 26 and 35.
	Over rolling hills, through widely scattering juniper growth; asc. E slope.
10.00	Trail road, on ridge, bears N and S; desc. W slope.
19.00	Ledge, 20 ft. high, bears N and S; desc. abruptly.
19.925	Point for the E 1/16 sec. cor. of secs. 26 and 35.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 16 S R 2 W
	E 1/16 $\frac{S\ 26}{S\ 35}$
	1974
30.00	Base of hill, bears NW and S; leave scattering juniper, over gentle rolling land.
39.85	Point for the ¼ sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 16 S R 2 W
	¼ $\frac{S\ 26}{S\ 35}$
	1974
64.50	Right bank of Sevier River, bears N and S.
67.00	Sevier River, flows N.
67.50	Left bank of Sevier River, bears N and S.
79.70	The cor. of secs. 26, 27, 34 and 35.
	N. 0°16' E., bet. secs. 26 and 27.
	Over gentle rolling land, through dense sagebrush.
16.00	Left bank of Sevier River, bears N. 25° W. and S. 25° E.
20.14	Point for the S 1/16 sec. cor. of secs. 26 and 27, falls in the Sevier River, that flows N. 25° W. and cannot be monumented.
22.72	Point selected for the witness S 1/16 sec. cor. of secs. 26 and 27, on the right bank of the Sevier River, bears N. 15° W. and S. 15° E.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS		
	<p style="text-align: center;">W C T 16 S R 2 W S 1/16</p> <p style="text-align: center;">S 27 ↓ S 26</p> <p style="text-align: center;">1974</p>	
25.50	Base of spur, bears NE and SW; asc. SE slope.	
27.00	Spur, slopes SW; desc. NW slope.	
35.00	Base of spur, bears NE and SW; over gentle rolling land.	
40.28	Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original corner.	
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.	
	<p style="text-align: center;">T 16 S R 2 W $\frac{1}{4}$ S 27 S 26 1974</p>	
50.50	Right bank of Sevier River, bears N. 40° E. and S. 40° W.	
52.00	Sevier River, flows NE.	
53.50	Left bank of Sevier River, bears N. 20° E. and SW.	
60.16	Fence, bears E and W.	
60.42	Point for the N $\frac{1}{16}$ sec. cor. of secs. 26 and 27.	
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.	
	<p style="text-align: center;">T 16 S R 2 W N 1/16</p> <p style="text-align: center;">S 27 S 26</p> <p style="text-align: center;">1974</p>	
63.00	Left bank of Sevier River, bears N. 30° W. and S. 30° E.	
65.00	Sevier River, flows NW.	
72.50	Right bank of Sevier River, bears N. 10° W. and S. 10° E.	
80.56	The cor. of secs. 22, 23, 26 and 27, monumented with a sandstone, 10 x 7 x 7 ins., firmly set and plainly mkd. 2 grooves on the S face, no marks on E face.	
	At the corner point	
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.	

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS					
	<p style="text-align: center;">T 16 S R 2 W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 22</td> <td style="padding: 0 5px;">S 23</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 27</td> <td style="padding: 0 5px;">S 26</td> </tr> </table> <p style="text-align: center;">1974</p> <p>Deposit the mkd. stone alongside the iron post.</p>	S 22	S 23	S 27	S 26
S 22	S 23				
S 27	S 26				
	<p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S. 89°57' W., bet. secs. 23 and 26.</p> <p>Over rolling hills and spurs, through lightly scattering juniper growth.</p>				
9.10	Wash, drains SE; asc. E slope.				
20.40	Trail road on ridge, bears N and S.				
21.20	Drift fence, bears N and S; desc. W slope.				
39.99	Point for the ¼ sec. cor. of secs. 23 and 26, at proportionate distance; there is no remaining evidence of the original corner.				
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone to top of brass cap, mkd.				
	<p style="text-align: center;">T 16 S R 2 W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">¼</td> <td style="padding: 0 5px;">S 23</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">S 26</td> </tr> </table> <p style="text-align: center;">1974</p>	¼	S 23		S 26
¼	S 23				
	S 26				
59.985	Point for the W 1/16 sec. cor. of secs. 23 and 26.				
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.				
	<p style="text-align: center;">T 16 S R 2 W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">W 1/16</td> <td style="padding: 0 5px;">S 23</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">S 26</td> </tr> </table> <p style="text-align: center;">1974</p>	W 1/16	S 23		S 26
W 1/16	S 23				
	S 26				
75.00	Enter bottom land.				
79.98	The cor. of secs. 22, 23, 26 and 27.				
	<p>N. 0°08' E., bet. secs. 22 and 23.</p> <p>Over nearly level bottom land, through sagebrush and rabbitbrush.</p>				
27.50	Right bank of Sevier River, bears E and W.				
29.00	Sevier River, flows E.				

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS	
31.50	Left bank of Sevier River, bears E and W.
37.50	U.S. Highway No. 91, bears N. 23°20' E. and S. 35°30' W.
40.03	Point for the ¼ sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 16 S R 2 W ¼ S 22 S 23 1974 </div>
	Set a steel fence post alongside the iron post.
40.50	Left bank of Sevier River, bears N. 65° W. and S. 65° E.
41.50	Sevier River, flows N. 62° W.
42.50	Right bank of Sevier River, bears N. 65° W. and S. 65° E.
51.58	Power line, bears N. 33°25' E. and S. 33°25' W.
59.00	Right bank of Sevier River, bears N. 70° E. and S. 70° W.
61.00	Sevier River, flows N. 66° E.
63.00	Left bank of Sevier River, bears N. 70° E. and S. 70° W.
76.00	Left bank of Sevier River, bears E and W.
77.00	Sevier River, flows N. 80° W.
78.00	Right bank of Sevier River, bears E and W.
80.06	The cor. of secs. 14, 15, 22 and 23, monumented with a sandstone, 12 x 10 x 6 ins., firmly set and plainly mkd. 3 grooves on the S and 2 on the E faces. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 16 S R 2 W S 15 S 14 S 22 S 23 1974 </div>
	Deposit the mkd. stone alongside the iron post.
	From the cor. of secs. 13, 14, 23 and 24. S. 89°36' W., bet. secs. 14 and 23. Over mountainous land, through scattering juniper growth; asc. E slope.

400

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS	
3.00	Ridge, bears N and S; desc. W slope.
9.77	Fence, bears N and S.
20.00	Leave scattering juniper growth.
40.13	The $\frac{1}{4}$ sec. cor. of secs. 14 and 23, monumented with a sandstone, 20 x 20 x 2 ins., firmly set and plainly mkd. $\frac{1}{4}$ on N face.
	At the corner point
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 16 S R 2 W
	$\frac{1}{4}$ $\frac{S\ 14}{S\ 23}$
	1974
	Deposit the mkd. stone alongside the iron post.
	Set a steel fence post alongside the iron post.
	<hr style="width: 20%; margin: auto;"/> N. $89^{\circ}53'$ W., beginning new measurement.
17.47	Right-of-way fence, bears N. $23^{\circ}20'$ E. and S. $23^{\circ}20'$ W.
18.775	Point selected for the witness W $1/16$ sec. cor. of secs. 14 and 23.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	W C T 16 S R 2 W
	W $1/16$ $\frac{S\ 14}{S\ 23}$
	1974
	Set a steel fence post alongside the iron post.
20.075	True point for the W $1/16$ sec. cor. of secs. 14 and 23, on the E edge of the highway and cannot be perpetuated.
20.78	Center line of U.S. Highway No. 91, bears N. $23^{\circ}20'$ E. and S. $23^{\circ}20'$ W.
22.01	Right-of-way fence, bears N. $23^{\circ}20'$ E. and S. $23^{\circ}20'$ W.
22.55	Power line, bears N. $23^{\circ}40'$ E. and S. $23^{\circ}40'$ W., over gentle rolling bottom land.
40.15	The cor. of secs. 14, 15, 22 and 23.
	N. $0^{\circ}04'$ W., bet. secs. 14 and 15.
	Over nearly level bottom land, through sagebrush and salt grass.

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS	
3.00	Right bank of Sevier River, bears N. 80° E. and S. 80° W.
5.00	Sevier River, flows N. 70° E.
7.00	Left bank of Sevier River, bears N. 80° E. and S. 80° W.
12.00	Left bank of Sevier River, bears E and W.
14.50	Sevier River, flows S. 80° W.
17.00	Right bank of Sevier River, bears E and W.
27.00	Right bank of Sevier River, bears E and W.
28.50	Sevier River, flows East.
30.00	Left bank of Sevier River, bears E and W.
40.95	Point for the ¼ sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} \text{T 16 S R 2 W} \\ \\ \frac{1}{4} \\ \\ \text{S 15} \quad \quad \text{S 14} \\ \\ \text{1974} \end{array}$
	Set a steel fence post alongside the iron post.
45.00	Left bank of Sevier River, bears N. 50° W. and S. 50° E.
49.00	Right bank of Sevier River, bears N. 50° W. and S. 50° E.
56.00	Right bank of Sevier River, bears S. 80° E. and N. 80° W.
57.50	Sevier River, flows S. 70° E.
59.00	Left bank of Sevier River, bears S. 80° E. and N. 80° W.
81.90	The cor. of secs. 10, 11, 14 and 15, determined by cor. of fence, bearing N and E, and a 5/8 in. rebar with metal cap mkd.
	$\frac{24}{25} \quad \quad 25$
	This position is accepted as the best available evidence of the original cor. position.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} \text{T 16 S R 2 W} \\ \\ \text{S 10} \quad \quad \text{S 11} \\ \text{S 15} \quad \quad \text{S 14} \\ \\ \text{1974} \end{array}$

402

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS	
	Bury local cor., inverted and alongside the iron post.
	From the cor. of secs. 11, 12, 13 and 14. N. 89°30' W., bet. secs. 11 and 14. Over gentle rolling land, through sagebrush and shadscale; desc. W slope.
13.48	Right-of-way fence, bears N. 41°25' E. and S. 41°25' W.
15.95	Center line of U.S. Highway No. 91, bears N. 41°25' E. and S. 41°25' W.
17.43	Right-of-way fence, bears N. 41°25' E. and S. 41°25' W., over nearly level bottom land.
18.85	Power line, parallels highway.
32.00	Right bank of Sevier River on sharp bend, bears N and S, over water.
40.04	Point for the ¼ sec. cor. of secs. 11 and 14, determined by the intersection of projection of fences from the S and W, falls in the Sevier River, that flows S. 64° E., and cannot be monumented, and is accepted as the best available evidence of the original cor. position.
	N. 88°46' W., beginning new measurement.
1.00	Right bank of Sevier River, bears N. 64° W. and S. 64° E.
1.51	Point selected for the witness ¼ sec. cor. of secs. 11 and 14. Set an iron post, 30 ins. long, 2½ ins., diam., 26 ins. in the ground, with brass cap mkd.
	W C T 16 S R 2 W ¼ $\frac{S\ 11}{S\ 14}$ → 1974
	Corner is located in E - W fence line.
24.00	Right bank of Sevier River on bend, bears NW and SE; thence over water which flows W.
36.00	Left bank of Sevier River on bend, bears NW and SE.
40.43	The cor. of secs. 10, 11, 14 and 15.
	N. 1°14' E., bet. secs. 10 and 11. Over nearly level bottom land, along fence line.
16.00	Small canal, flows NW.

Dependent Resurvey of a portion of the Subdivisional Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS	
18.00	Enter old river channel, that bears N and E.
38.00	Leave old river channel, that bears S and E.
40.40	The 1/4 sec. cor. of secs. 10 and 11, determined by fence cor., bearing N, S, and E, and is accepted as the best available evidence of the original cor. position.
	At the corner point
	Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 16 S R 2 W</p> <p style="text-align: center;"> 1/4 </p> <p style="text-align: center;">S 10 S 11</p> <p style="text-align: center;"> </p> <p style="text-align: center;">1974</p>
	N. 1°23' E., beginning new measurement.
14.00	Left bank of Sevier River, bears N. 60° W. and S. 60° E.
16.00	Sevier River, flows NW.
18.00	Right bank of Sevier River, bears N. 20° W. and SE.
40.41	The cor. of secs. 2, 3, 10 and 11, monumented with a broken sandstone, 10 x 10 x 8 ins., firmly set, with no visible markings, only rock in area, and is accepted as the best available evidence of the original cor. position.
	At the corner point
	Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 16 S R 2 W</p> <p style="text-align: center;">S 3 S 2</p> <p style="text-align: center;">S 10 S 11</p> <p style="text-align: center;">1974</p>
	Deposit the unmkd. stone alongside the iron post.
	From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp.
	N. 0°06' W., bet. secs. 33 and 34.
	Over gentle rolling land, through sagebrush and shadscale.
3.90	Wash, 30 lks. wide, 5 ft. deep, drains SW; asc. gentle SE slope.
6.90	Trail road, bears NE and SW.
20.04	Point for the S 1/16 sec. cor. of secs. 33 and 34.
	Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

404

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS	
	<p style="text-align: center;">T 16 S R 2 W S 1/16</p> <p style="text-align: center;">S 33 S 34</p> <p style="text-align: center;">1974</p>
40.08	<p>The $\frac{1}{4}$ sec. cor. of secs. 33 and 34, monumented with a broken sandstone, 8 x 6 x 4 ins., firmly set and dimly mkd. $\frac{1}{4}$ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 2 W $\frac{1}{4}$ S 33 S 34 1974</p> <p>Deposit the mkd. stone alongside the iron post.</p>
	<p style="text-align: center;">N. $0^{\circ}03'$ E., beginning new measurement.</p>
17.50	Trail road, bears NE and SW.
40.10	Right-of-way fence, bears N. $35^{\circ}45'$ E. and S. $35^{\circ}45'$ W.
40.27	<p>The cor. of secs. 27, 28, 33 and 34, monumented with a sandstone, 14 x 10 x 4 ins., firmly set and plainly mkd. 3 notches on E and 1 on S edges.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 2 W S 28 S 27 S 33 S 34 1974</p> <p>Deposit the mkd. stone alongside the iron post.</p>
	<p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>S. $89^{\circ}47'$ W., bet. secs. 27 and 34.</p> <p>Over gentle rolling land, through sagebrush and shadscale.</p>
19.47	Fence, bears N and S.
39.81	<p>The $\frac{1}{4}$ sec. cor. of secs. 27 and 34, monumented with a quartzite stone, 12 x 10 x 6 ins., firmly set and plainly mkd. $\frac{1}{4}$ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS	
	<p style="text-align: center;">T 16 S R 2 W</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S\ 27}{S\ 34}$</p> <p style="text-align: center;">1974</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p style="text-align: center;">_____</p> <p>S. 89°51' W., beginning new measurement.</p>
13.40	Dirt road, bears NE and SW.
23.20	Same road, bears NW and SE.
40.08	Right-of-way fence, bears N. 35°45' E. and S. 35°45' W.
40.20	The cor. of secs. 27, 28, 33 and 34.
	<p>N. 0°16' E., bet. secs. 27 and 28.</p> <p>Over gentle rolling land, through sagebrush and shadscale.</p>
3.15	U.S. Highway No. 91, bears N. 35°45' E. and S. 35°45' W.
8.37	Right-of-way fence, bears N. 35°45' E. and S. 35°45' W.; thence along fence line.
9.46	Power line, bears N. 33°30' E. and S. 33°30' W.
39.95	Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner.
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 2 W</p> <p style="text-align: center;">$\frac{1}{4}$</p> <p style="text-align: center;">S 28 S 27</p> <p style="text-align: center;">1974</p> <p>Cor. is located in N - S fence line.</p>
50.96	Fence from S, bears NW.
51.35	Wash, 20 lks. wide, 4 ft. deep, drains N. 70° E.
59.925	Point for the N 1/16 sec. cor. of secs. 27 and 28.
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 2 W</p> <p style="text-align: center;">N 1/16</p> <p style="text-align: center;">S 28 S 27</p> <p style="text-align: center;">1974</p>

406

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS							
	Set a steel fence post alongside the iron post.						
69.20	Fence line, bears E and W, enter reseeded area.						
79.90	The cor. of secs. 21, 22, 27 and 28, monumented with a sandstone, 18 x 12 x 5 ins., firmly set with faint markings, the only rock in the area.						
	At the corner point						
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.						
	T 16 S R 2 W						
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">S 21</td> <td style="text-align: center;"> </td> <td style="text-align: center;">S 22</td> </tr> <tr> <td style="text-align: center;">S 28</td> <td style="text-align: center;"> </td> <td style="text-align: center;">S 27</td> </tr> </table>	S 21		S 22	S 28		S 27
S 21		S 22					
S 28		S 27					
	1974						
	Deposit the mkd. stone alongside the iron post.						
	From the cor. of secs. 22, 23, 26 and 27.						
	S. 89°06' W., bet. secs. 22 and 27.						
	Over gentle rolling land, through sagebrush and shadscale.						
3.00	Right bank of Sevier River, bears N. 20° W. and S. 20° E.						
4.50	Sevier River, flows N. 20° W.						
6.00	Left bank of Sevier River, bears N. 20° W. and S. 20° E.						
20.13	Point for the E 1/16 sec. cor. of secs. 22 and 27.						
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.						
	T 16 S R 2 W						
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">E 1/16</td> <td style="text-align: center;">-</td> <td style="text-align: center;">S 22</td> </tr> <tr> <td></td> <td style="text-align: center;">-</td> <td style="text-align: center;">S 27</td> </tr> </table>	E 1/16	-	S 22		-	S 27
E 1/16	-	S 22					
	-	S 27					
	1974						
20.26	Dirt road, bears N and S.						
23.49	Right-of-way fence, bears N. 35°30' E. and S. 35°30' W.						
25.91	U.S. Highway No. 91, bears N. 35°30' E. and S. 35°30' W.						
27.31	Right-of-way fence, bears N. 35°30' E. and S. 35°30' W.						
34.27	Power line, bears N. 33°25' E. and S. 33°25' W.						
40.26	The ¼ sec. cor. of secs. 22 and 27, monumented with a sandstone, 10 x 8 x 7 ins., firmly set, with no legible mks., in N - S fence line, being used by local land owners, and is accepted as the best available evidence of the original cor. position.						
	At the corner point						

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS	
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 2 W</p> <p style="text-align: center;">¼ $\frac{S\ 22}{S\ 27}$</p> <p style="text-align: center;">1974</p> <p>Deposit the unmkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 89°43' W., beginning new measurement.</p>
21.43	Fence, bears N and S.
25.13	Over reseeded area.
39.72	The cor. of secs. 21, 22, 27 and 28.
	<p>N. 0°51' W., bet. secs. 21 and 22.</p> <p>Over nearly level reseeded area.</p>
13.00	Trail road, bears NE and SW.
21.00	Leave reseeded area, through sagebrush and shadscale.
27.58	Fence, bears E and W.
40.55	<p>The ¼ sec. cor. of secs. 21 and 22, monumented with a sandstone, 12 x 12 x 6 ins., firmly set and plainly mkd. ¼ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 2 W</p> <p style="text-align: center;">¼ S 21 S 22 1974</p> <p>Deposit the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°37' E., beginning new measurement.</p>
11.90	Fence, bears S. 45° W. and N. 45° E., 86 lks. dist. to cor. of fence, thence N. 0°39' W.
40.49	The cor. of secs. 15, 16, 21 and 22, marked with a broken sandstone, at the cor. of fence, bearing S. 0°39' E. and NE, and is accepted as the best available evidence of the original cor. position.

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS	
	<p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 2 W</p> <p style="text-align: center;"> $\begin{array}{c c} \hline S 16 & S 15 \\ \hline S 21 & S 22 \\ \hline \end{array}$ </p> <p style="text-align: center;">1974</p> <p>Deposit the broken sandstone (pieces) alongside the iron post.</p>
	<p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>N. 89°51' W., bet. secs. 15 and 22.</p> <p>Over nearly level bottom land, through sagebrush and shadscale.</p> <p>3.00 Right bank of Sevier River, bears N and S.</p> <p>5.00 Bend in Sevier River, flows NE and SE.</p> <p>7.00 Left bank of Sevier River, bears N and S.</p> <p>38.00 Dirt road, bears N and S; asc. gentle E slope.</p> <p>40.16 Point for the ¼ sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 2 W</p> <p style="text-align: center;"> $\frac{1}{4} \frac{S 15}{S 22}$ </p> <p style="text-align: center;">1974</p> <p>40.73 Fence, bears N and S.</p> <p>45.36 Fence, bears N and S.</p> <p>56.77 Base of foothills, bears N and S; asc. E slope.</p> <p>60.24 Point for the W 1/16 sec. cor. of secs. 15 and 22.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 2 W</p> <p style="text-align: center;"> $W \frac{1}{16} \frac{S 15}{S 22}$ </p> <p style="text-align: center;">1974</p> <p>60.53 Fence, bears N and S.</p>

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS	
67.10	Low spur, slopes N; desc. gentle NW slope.
80.32	The cor. of secs. 15, 16, 21 and 22.
	N. 0°01' E., bet. secs. 15 and 16.
	Over rolling land, through sagebrush and very lightly scattering juniper growth.
26.37	Wash, 20 lks. wide, 5 ft. deep, drains E.
38.30	Wash, 20 lks. wide, 4 ft. deep, drains SE.
40.71	Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 16, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 16 S R 2 W</p> <p style="text-align: center;"> $\frac{1}{4}$</p> <p style="text-align: center;"> </p> <p style="text-align: center;">S 16 S 15</p> <p style="text-align: center;"> </p> <p style="text-align: center;"> 1974</p>
81.42	The cor. of secs. 9, 10, 15 and 16, monumented with a sandstone, 18 x 12 x 10 ins., firmly set and plainly mkd. 4 grooves on the S and 3 on E faces.
	At the corner point
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 16 S R 2 W</p> <p style="text-align: center;">S 9 S 10</p> <p style="text-align: center;">S 16 S 15</p> <p style="text-align: center;">1974</p>
	Deposit the mkd. stone alongside the iron post.
	From the cor. of secs. 10, 11, 14 and 15.
	S. 89°50' W., bet. secs. 10 and 15.
	Over nearly level land, through sagebrush and shadscale.
25.56	Dirt road at base of hill, bears N and S; asc. E slope through lightly scattering juniper growth.
40.15	The $\frac{1}{4}$ sec. cor. of secs. 10 and 15, marked by a $\frac{5}{8}$ in. rebar, projecting 6 ins. above ground, in a scattering mound of stone, with metal cap mkd.
	<p style="text-align: center;"> 48</p> <p style="text-align: center;">----- 49</p>

410

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS	
	<p>This position is harmoniously related with other identified original cors. in the area and is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 2 W</p> <p style="text-align: center;">¼ $\frac{S 10}{S 15}$</p> <p style="text-align: center;">1974</p> <p>Bury rebar, inverted and alongside the iron post.</p> <p>Cor. is located in N - S fence line.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°58' W., beginning new measurement.</p> <p>Over rolling land.</p> <p>9.00 Enter, draw, drains NE.</p> <p>18.00 Leave draw, drains E; asc. E slope.</p> <p>33.00 Spur, slopes N; desc. NW slope.</p> <p>39.96 The cor. of secs. 9, 10, 15 and 16.</p>
	<p>N. 0°03' E., bet. secs. 9 and 10.</p> <p>Over rolling land, through sagebrush and shadscale.</p> <p>2.00 Small wash, drains NE.</p> <p>12.00 Small wash, drains NE.</p> <p>23.35 Draw, drains E.</p> <p>39.58 Point for the ¼ sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 2 W</p> <p style="text-align: center;">¼ S 9 S 10 1974</p> <p>43.73 Fence in draw draining E, bears N. 60° W. and S. 60° E.</p> <p>59.86 Wide draw, drains E.</p> <p>68.52 Trail road, bears N. 70° W. and S. 70° E.</p>

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS	
79.16	<p>The cor. of secs. 3, 4, 9 and 10, monumented with a granite stone, 18 x 6 x 6 ins., firmly set and plainly mkd. 5 notches on S and 3 on E edges.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 2 W</p> <p style="text-align: center;"> $\begin{array}{c c} \text{S } 4 & \text{S } 3 \\ \hline \text{S } 9 & \text{S } 10 \end{array}$ </p> <p style="text-align: center;">1974</p> <p>Deposit the mkd. stone alongside the iron post.</p>
<p>25.00</p> <p>28.00</p> <p>31.00</p> <p>39.00</p> <p>40.00</p> <p>40.94</p> <p>44.00</p> <p>46.00</p> <p>48.00</p> <p>57.00</p> <p>60.86</p> <p>61.41</p>	<p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>S. 88°48' W., bet. secs. 3 and 10.</p> <p>Over nearly level bottom land, through sagebrush and shadscale.</p> <p>Right bank of Sevier River, bears N. 50° E. and S. 50° W.</p> <p>Sevier River, flows NE.</p> <p>Left bank of Sevier River, bears N. 40° E. and S. 40° W.</p> <p>Left bank of Sevier River, bears N and S.</p> <p>Sevier River, flows S.</p> <p>Point for the ¼ sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 2 W</p> <p style="text-align: center;"> $\frac{1}{4} \frac{\text{S } 3}{\text{S } 10}$ </p> <p style="text-align: center;">1974</p> <p>Cor. is located on right bank of Sevier River, bears N and S.</p> <p>Right bank of Sevier River, bears N. 20° W. and S. 20° E.</p> <p>Sevier River, flows N.</p> <p>Left bank of Sevier River, bears N and S.</p> <p>Small canal, flows N.</p> <p>Dirt road, bears N and S; asc. gentle E slope.</p> <p>Point for the W 1/16 sec. cor. of secs. 3 and 10.</p>

412

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS		
81.88	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 2 W</p> <p style="text-align: center;">W 1/16 $\frac{S 3}{S 10}$</p> <p style="text-align: center;">1974</p> <p>Set a steel fence post alongside the iron post.</p> <p>The cor. of secs. 3, 4, 9 and 10.</p>	
6.75 14.33 39.23 41.26	<p>N. 0°39' E., bet. secs. 3 and 4.</p> <p>Over rolling land, through sagebrush and shadscale; asc. SE slope.</p> <p>Point of spur, slopes NE; desc. NW slope.</p> <p>Draw, drains E., over rolling land.</p> <p>The ¼ sec. cor. of secs. 3 and 4, determined by the cor. of fence, bearing N and E; and is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 2 W</p> <p style="text-align: center;"> ¼</p> <p style="text-align: center;"> </p> <p style="text-align: center;">S 4 S 3</p> <p style="text-align: center;"> </p> <p style="text-align: center;"> 1974</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°17' W., beginning new measurement.</p> <p>Along fence line.</p> <p>The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp.</p>	
20.07	<p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp.</p> <p>N. 0°19' W., bet. secs. 32 and 33.</p> <p>Over gentle rolling land, through sagebrush and shadscale.</p> <p>Point for the S 1/16 sec. cor. of secs. 32 and 33.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS	
	<p style="text-align: center;">T 16 S R 2 W S 1/16</p> <p style="text-align: center;">S 32 S 33</p> <p style="text-align: center;">1974</p>
40.14	<p>Cor. is located 1 lk. dist., S of fence cor., bearing N, S and E.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 32 and 33, monumented with a sandstone, 12 x 12 x 6 ins., firmly set and plainly mkd. $\frac{1}{4}$ on W face.</p>
	<p>At the corner point</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 2 W $\frac{1}{4}$ S 32 S 33 1974</p>
	<p>Deposit the mkd. stone alongside the iron post.</p> <p>Cor. is located in N - S fence line.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. $0^{\circ}23'$ W., beginning new measurement.</p>
40.96	<p>The cor. of secs. 28, 29, 32 and 33, determined by a fence cor., fences bearing N, S and W; and is accepted as the best available evidence of the original cor. position.</p>
	<p>At the corner point</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 2 W S 29 S 28 S 32 S 33 1974</p>
	<p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>S. $89^{\circ}36'$ W., bet. secs. 28 and 33.</p> <p>Over rolling land, through sagebrush and shadscale.</p>
2.24	U.S. Highway No. 91, bears N. $35^{\circ}45'$ E. and S. $35^{\circ}45'$ W.
5.92	Right-of-way fence, paralleling highway.
6.42	Power line, bears N. $33^{\circ}30'$ E. and S. $33^{\circ}30'$ W.
28.40	Rise, bears NE and SW.

414

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS	
39.69	<p>The $\frac{1}{4}$ sec. cor. of secs. 28 and 33, monumented with a limestone, 14 x 6 x 6 ins., firmly set and plainly mkd. $\frac{1}{4}$ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 2 W</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S\ 28}{S\ 33}$</p> <p style="text-align: center;">1974</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Set a steel fence post alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. $88^{\circ}30'$ W., beginning new measurement.</p>
6.50	<p>Wash, 20 lks. wide, 4 ft. deep, drains N. 75° E.</p>
20.40	<p>Point for the W $\frac{1}{16}$ sec. cor. of secs. 28 and 33.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 2 W</p> <p style="text-align: center;">W $\frac{1}{16}$ $\frac{S\ 28}{S\ 33}$</p> <p style="text-align: center;">1974</p> <p>Set a steel fence post alongside the iron post.</p>
40.80	<p>The cor. of secs. 28, 29, 32 and 33.</p>
	<p>N. $0^{\circ}24'$ W., bet. secs. 28 and 29.</p>
	<p>Over rolling land, through sagebrush and shadscale.</p>
25.10	<p>Draw, drains E.</p>
39.49	<p>The $\frac{1}{4}$ sec. cor. of secs. 28 and 29, monumented with a limestone, 12 x 12 x 6 ins., firmly set and dimly mkd. $\frac{1}{4}$ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 2 W</p> <p style="text-align: center;">$\frac{1}{4}$</p> <p style="text-align: center;">S 29 S 28</p> <p style="text-align: center;">1974</p>

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS							
	<p>Deposit the mkd. stone alongside the iron post.</p> <p>Cor. is located at the cor. of fence bearing N, S and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°34' E., beginning new measurement.</p> <p>40.95 The cor. of secs. 20, 21, 28 and 29, monumented with a sandstone, 12 x 6 x 6 ins., firmly set and plainly mkd. 4 grooves on E and 2 on S face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 2 W</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 20</td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">S 21</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 29</td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">S 28</td> </tr> </table> <p style="text-align: center;">1974</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Cor. is located in fence line, bearing N. 75° W. and S. 75° E.</p>	S 20		S 21	S 29		S 28
S 20		S 21					
S 29		S 28					
	<p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>N. 89°01' W., bet. secs. 21 and 28.</p> <p>Over nearly level reseeded area.</p> <p>17.44 Fence, bears N and S, leave reseeded area.</p> <p>40.33 Point for the ¼ sec. cor. of secs. 21 and 28, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 2 W</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">¼</td> <td style="border-right: 1px solid black; padding: 0 5px;">S 21</td> <td style="padding: 0 5px;"></td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="border-right: 1px solid black; padding: 0 5px;">S 28</td> <td style="padding: 0 5px;"></td> </tr> </table> <p style="text-align: center;">1974</p> <p>72.00 Trail road, bears N and S.</p> <p>80.66 The cor. of secs. 20, 21, 28 and 29.</p>	¼	S 21			S 28	
¼	S 21						
	S 28						
	<p>N. 0°06' W., bet. secs. 20 and 21.</p> <p>Over rolling land, through sagebrush and shadscale.</p> <p>19.50 Trail road, bears N. 70° E. and S. 70° W.</p> <p>25.50 Draw, drains NE.</p> <p>33.00 Draw, drains N. 75° E.</p>						

416

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS

40.10 The $\frac{1}{4}$ sec. cor. of secs. 20 and 21, monumented with a cedar post in a mound of stone. This position is harmoniously related to existing original cors., and is accepted as the best available evidence of the original cor. position.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 16 S R 2 W
 $\frac{1}{4}$
 S 20 | S 21
 1974

Reset cedar post alongside the iron post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

N. $0^{\circ}20'$ E., beginning new measurement.

40.09 The cor. of secs. 16, 17, 20 and 21, monumented with a limestone, 20 x 12 x 6 ins., firmly set and plainly mkd. 4 dots on E and 3 on S faces.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 16 S R 2 W
 S 17 | S 16
 S 20 | S 21
 1974

Deposit the mkd. stone alongside the iron post.

From the cor. of secs. 15, 16, 21 and 22.

N. $89^{\circ}41'$ W., bet. secs. 16 and 21.

Over rolling land, through sagebrush and shadscale.

40.21 Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 21, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 16 S R 2 W
 $\frac{1}{4}$ S 16
 S 21
 1974

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS	
54.10	<p>Set a steel fence post alongside the iron post.</p> <p>Raise a mound of stone, 2½ ft. base, 1 ft. high, N of cor.</p> <p>Trail road, bears N and S.</p>
80.42	<p>The cor. of secs. 16, 17, 20 and 21.</p>
29.00	<p>N. 0°15' E., bet. secs. 16 and 17.</p> <p>Over gentle rolling land, through sagebrush and shadscale.</p> <p>Trail road, bears NW and SE.</p>
40.55	<p>The ¼ sec. cor. of secs. 16 and 17, monumented with a quartzite stone, 12 x 10 x 7 ins., firmly set and plainly mkd. ¼ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 16 S R 2 W</p> <p> </p> <p> ¼</p> <p> </p> <p>S 17 S 16</p> <p> </p> <p> 1974</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p>
15.40	<p>N. 0°12' W., beginning new measurement.</p> <p>Dirt road, bears N. 50° E. and S. 50° W.</p>
40.11	<p>The cor. of secs. 8, 9, 16 and 17, monumented with a sandstone, 16 x 10 x 4 ins., firmly set and plainly mkd. 4 grooves on S and E faces.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 16 S R 2 W</p> <p> </p> <p> S 8 S 9</p> <p> S 17 S 16</p> <p> </p> <p> 1974</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p>
	<p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>S. 89°52' W., bet. secs. 9 and 16.</p> <p>Over rolling land, through sagebrush and shadscale.</p>

418

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS	
0.40	Small wash, 10 lks. wide, 2 ft. deep, drains N. 25° E.
40.11	The ¼ sec. cor. of secs. 9 and 16, monumented with a sandstone, 12 x 10 x 5 ins., firmly set and plainly mkd. ¼ on N face.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 16 S R 2 W
	$\frac{1}{4} \begin{array}{c} S 9 \\ S 16 \end{array}$
	1974
	Deposit the mkd. stone alongside the iron post.

	S. 89°50' W., beginning new measurement.
3.18	Trail road, bears N and S.
12.55	Dirt road, bears N. 45° E. and S. 45° W.
40.18	The cor. of secs. 8, 9, 16 and 17.
	N. 0°35' W., bet. secs. 8 and 9.
	Over gentle rolling land, through sagebrush and shadscale.
20.30	Fence, bears N. 89°20' W. and S. 89°20' E.
39.86	The ¼ sec. cor. of secs. 8 and 9, monumented with a cedar post, in an old mound of stone. This position is harmoniously related with other identified original cors. in the area and is accepted as the best available evidence of the original cor. position.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 16 S R 2 W
	$\begin{array}{c} \frac{1}{4} \\ \\ S 8 \quad \quad S 9 \\ \end{array}$
	1974
	Reset cedar post alongside the iron post.

	N. 0°31' E., beginning new measurement.
3.50	Wash, 10 lks. wide, 1 ft. deep, drains E.
22.50	Wash, 10 lks. wide, 3 ft. deep, drains N. 70° E.

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS						
40.14	<p>The cor. of secs. 4, 5, 8 and 9, monumented with a broken limestone, with a small mound of stone to W, and is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 2 W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 5</td> <td style="padding: 0 5px;">S 4</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 8</td> <td style="padding: 0 5px;">S 9</td> </tr> </table> <p style="text-align: center;">1974</p> <p>Deposit broken limestone alongside the iron post.</p>	S 5	S 4	S 8	S 9	
S 5	S 4					
S 8	S 9					
	<p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>N. 89°23' W., bet. secs. 4 and 9.</p> <p>Over rolling land, through sagebrush and shadscale; asc. E slope.</p>					
3.50	Ridge, bears N and S; desc. W slope.					
22.57	Dirt road, bears N and S.					
40.12	<p>The ¼ sec. cor. of secs. 4 and 9, monumented with a sandstone, 13 x 8 x 3 ins., firmly set and plainly mkd. ¼ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 2 W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">¼</td> <td style="padding: 0 5px;">S 4</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">S 9</td> </tr> </table> <p style="text-align: center;">1974</p> <p>Deposit the mkd. stone alongside the iron post.</p>	¼	S 4		S 9	
¼	S 4					
	S 9					
	N. 89°43' W., beginning new measurement.					
40.27	The cor. of secs. 4, 5, 8 and 9.					
	N. 0°10' E., bet. secs. 4 and 5.					
	Over nearly level land, through sagebrush and grass.					
4.50	Trail road, bears NE and SW.					
7.10	Wash, 10 lks. wide, 3 ft. deep, drains NE.					

Dependent Resurvey of a portion of the Subdivisional Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS	
27.10	Dirt road, bears N. 57° E. and S. 57° W.
39.36	<p>The ¼ sec. cor. of secs. 4 and 5, monumented with a sandstone, 12 x 12 x 4 ins., firmly set and plainly mkd. ¼ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 16 S R 2 W</p> <p>¼</p> <p> </p> <p>S 5 S 4</p> <p> </p> <p>1974</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Set a steel fence post alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°09' E., beginning new measurement.</p>
40.24	<p>The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp.</p> <hr/> <p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp.</p> <p>N. 0°19' W., bet. secs. 31 and 32.</p> <p>Over nearly level farm land, along E side of trail road.</p>
0.18	Trail road bearing E and W.
40.36	<p>Point for the ¼ sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 16 S R 2 W</p> <p>¼</p> <p> </p> <p>S 31 S 32</p> <p> </p> <p>1974</p> </div> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located on E edge of trail road, bears N and S.</p>
80.72	<p>The cor. of secs. 29, 30, 31 and 32, monumented with a granite stone, 14 x 8 x 6 ins., firmly set and plainly mkd. 5 notches on E and 1 on S edges.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS

T 16 S R 2 W

S 30	S 29
S 31	S 32

1974

Deposit the mkd. stone alongside the iron post.

Cor. is located in E - W fence line and 50 lks. dist.,
W of trail road, bears N and S.

S. 89°26' W., bet. secs. 30 and 31.

Over nearly level farm land, along fence line.

40.06 Point for the $\frac{1}{4}$ sec. cor. of secs. 30 and 31, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone to top of brass cap, mkd.

T 16 S R 2 W

$\frac{1}{4}$	S 30	S 31
	S 31	

1974

Cor. is located in E - W fence line.

From this cor., U.S.C. & G.S. triangulation station "Fan 1938", bears S. 0°17' E., 16.77 chs. dist., a brass tablet, 3 ins. diam., seated in concrete monument, projecting 6 ins. above ground, located at: Latitude 39°23'04.944" N., and Longitude 112°07'04.682" W., as published by U.S.C. & G.S.

60.09 Point for the W $\frac{1}{16}$ sec. cor. of secs. 30 and 31.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 16 S R 2 W

W $\frac{1}{16}$	S 30	S 31
	S 31	

1974

Cor. is located in E - W fence line.

60.74 Cor. of fence, bears N, S and E; asc. gentle E slope, through dense sagebrush.

66.66 Small wash, drains SE.

79.93 The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp.

From the cor. of secs. 29, 30, 31 and 32.

Dependent Resurvey of a portion of the Subdivisional Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS	
40.47	<p>N. 0°06' E., bet. secs. 29 and 30.</p> <p>Over nearly level farm land, along W side of farm road.</p> <p>The ¼ sec. cor. of secs. 29 and 30, monumented with a sandstone, 12 x 10 x 8 ins., firmly set and plainly mkd. ¼ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 16 S R 2 W</p> <p>¼</p> <p> </p> <p>S 30 S 29</p> <p> </p> <p>1974</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Cor. is located at the cor. of fence, bearing E, W and N, also 20 lks. dist. W of trail road that bears N and S.</p>
39.92	<p>N. 0°06' E., beginning new measurement.</p> <p>Along fence line.</p> <p>The cor. of secs. 19, 20, 29 and 30, monumented with a sandstone, 12 x 12 x 4 ins., firmly set and plainly mkd. 5 grooves on E and 2 on S faces.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 16 S R 2 W</p> <p>S 19 S 20</p> <p>S 30 S 29</p> <p>1974</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Cor. is located at the cor. of fence, bearing N, S and E.</p>
0.65 9.35 40.45	<p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>S. 88°48' W., bet. secs. 20 and 29.</p> <p>Over gentle rolling land, through sagebrush and shadscale.</p> <p>Fence, bears N and S.</p> <p>Fence, bears N. 87°35' E. and S. 87°35' W.</p> <p>The ¼ sec. cor. of secs. 20 and 29, monumented with a sandstone, 14 x 8 x 6 ins., firmly set and plainly mkd. ¼ on N face.</p>

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 16 S R 2 W

¼ $\frac{S\ 20}{S\ 29}$

1974

Deposit the mkd. stone alongside the iron post.

Set a steel fence post alongside the iron post.

Cor. is located 67 lks. dist. N of E - W fence line.

West, beginning new measurement.

39.91 Trail road, bears N and S.

40.11 The cor. of secs. 19, 20, 29 and 30.

N. 88°59' W., bet. secs. 19 and 30.

Over nearly level farm land.

39.95 The ¼ sec. cor. of secs. 19 and 30, monumented with a sandstone, 12 x 12 x 10 ins., with a cedar post alongside, no legible markings. This position is accepted as the best available evidence of the original cor. position.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 16 S R 2 W

¼ $\frac{S\ 19}{S\ 30}$

1974

Deposit the unmkd. stone alongside the iron post.

Cor. is located at the W edge of cultivated land that bears N and S.

S. 89°16' W., beginning new measurement.

Asc. gentle E slope, through sagebrush and shadscale.

20.01 Point for the W 1/16 sec. cor. of secs. 19 and 30.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS	
	<p>T 16 S R 2 W</p> <p>W 1/16 $\frac{S 19}{S 30}$</p> <p>1974</p>
	Set a steel fence post alongside the cor.
21.62	Fence, bears N and S.
23.00	Small wash, drains SE.
28.00	Same wash, drains N. 75° E.
39.92	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp.
	From the cor. of secs. 19, 20, 29 and 30.
	N. 0°06' E., bet. secs. 19 and 20.
	Over nearly level land, along fence and dirt road.
19.78	Leave fence, that bears W.
24.00	Dirt road, bears N. 20° E., enter dense sagebrush.
40.08	The ¼ sec. cor. of secs. 19 and 20, monumented with a sandstone, 12 x 12 x 8 ins., firmly set and plainly mkd. ¼ on W face.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>T 16 S R 2 W</p> <p>¼</p> <p>S 19 S 20</p> <p>1974</p>
	Deposit the mkd. stone alongside the iron post.
	N. 0°31' E., beginning new measurement.
41.13	The cor. of secs. 17, 18, 19 and 20, monumented with a sandstone, 18 x 8 x 8 ins., firmly set and dimly mkd. 5 grooves on E and 3 on S faces.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>T 16 S R 2 W</p> <p>S 18 S 17</p> <p>S 19 S 20</p> <p>1974</p>

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS	
	Deposit the mkd. stone alongside the iron post.
	From the cor. of secs. 16, 17, 20 and 21.
	N. 89°53' W., bet. secs. 17 and 20.
	Over gentle rolling land, through sagebrush and shadscale.
40.11	Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 16 S R 2 W
	$\frac{1}{4}$ $\frac{S 17}{S 20}$
	1974
	Set a steel fence post alongside the iron post.
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, 1 ft. high, N of cor.
51.20	Improved dirt road, bears N. 26°30' E. and S. 26°30' W.
80.22	The cor. of secs. 17, 18, 19 and 20.
	S. 89°51' W., bet. secs. 18 and 19.
	Over rolling land, through sagebrush and shadscale.
9.23	Trail road, bears N. 45° E. and S. 45° W.
40.81	Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 16 S R 2 W
	$\frac{1}{4}$ $\frac{S 18}{S 19}$
	1974
	Set a steel fence post alongside the iron post.
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, 1 ft. high, N of cor.
61.215	Point for the W $\frac{1}{16}$ sec. cor. of secs. 18 and 19.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 16 S R 2 W
	W $\frac{1}{16}$ $\frac{S 18}{S 19}$
	1974

Dependent Resurvey of a portion of the Subdivisional Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS	
81.62	<p>Set a steel fence post alongside the iron post.</p> <p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp.</p>
8.20	<p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°10' W., bet. secs. 17 and 18.</p> <p>Over gentle rolling land, through sagebrush and shadscale.</p> <p>Trail road, bears NE and SW.</p>
40.31	<p>The ¼ sec. cor. of secs. 17 and 18, monumented with a sandstone, 12 x 12 x 4 ins., firmly set and plainly mkd. ¼ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 16 S R 2 W</p> <p> </p> <p> ¼</p> <p> </p> <p> S 18 S 17</p> <p> </p> <p> 1974</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p> <p>_____</p> <p>N. 0°03' E., beginning new measurement.</p>
40.83	<p>The cor. of secs. 7, 8, 17 and 18, monumented with a quartzite stone, 16 x 9 x 8 ins., firmly set and plainly mkd. 5 grooves on E face, no other markings.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base to top of brass cap, mkd.</p> <div style="text-align: center;"> <p>T 16 S R 2 W</p> <p> </p> <p> S 7 S 8</p> <p> S 18 S 17</p> <p> </p> <p> 1974</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p>
32.00	<p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>N. 89°31' W., bet. secs. 8 and 17.</p> <p>Over gentle rolling land, through sagebrush and shadscale.</p> <p>Trail road, bears N. 15° E. and S. 15° W.</p>

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS	
40.19	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 17, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 2 W</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S 8}{S 17}$</p> <p style="text-align: center;">1974</p> <p>Raise a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, N of cor.</p>
80.38	<p>The cor. of secs. 7, 8, 17 and 18.</p>
39.93	<p>S. $89^{\circ}21'$ W., bet. secs. 7 and 18.</p> <p>Over rolling land, through sagebrush and shadscale.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 2 W</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S 7}{S 18}$</p> <p style="text-align: center;">1974</p> <p>Set a steel fence post alongside the iron post.</p> <p>Raise a mound of stone, $2\frac{1}{2}$ ft. base, 1 ft. high, N of cor.</p>
55.30	<p>Draw, drains S. 70° E., asc. NE slope through lightly scattering juniper growth.</p>
69.00	<p>Slope changes, along N slope.</p>
71.00	<p>Slope change; desc. NW slope.</p>
79.50	<p>Base of hill, bears NE and S, over rolling land.</p>
80.30	<p>The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp.</p>
19.30	<p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. $0^{\circ}09'$ E., bet. secs. 7 and 8.</p> <p>Over rolling land, through sagebrush and shadscale.</p> <p>Point for the S $1/16$ sec. cor. of secs. 7 and 8.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a portion of the Subdivisional Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS		
	<p>T 16 S R 2 W S 1/16 S 7 S 8 1974</p>	
20.12	Fence, bears E and W.	
38.60	<p>The 1/4 sec. cor. of secs. 7 and 8, monumented with a sandstone, 10 x 9 x 4 ins., firmly set and plainly mkd. 1/4 on W face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T 16 S R 2 W 1/4 S 7 S 8 1974 </p> <p>Deposit the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°01' E., beginning new measurement.</p>	
22.00	Trail road, bears NE and SW.	
40.22	<p>The cor. of secs. 5, 6, 7 and 8, monumented with a squared cedar post, 3 ins. diam., projecting 5 1/2 ft. above ground. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T 16 S R 2 W S 6 S 5 S 7 S 8 1974 </p> <p>Reset cedar post alongside the iron post.</p>	
	<p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>S. 88°55' W., bet. secs. 5 and 8.</p> <p>Over gentle rolling land, through sagebrush and shadscale.</p>	
2.15	Trail road, bears NE and SW.	
40.15	<p>The 1/4 sec. cor. of secs. 5 and 8, monumented with an old cedar post, 3 ins. diam., in a small mound of stone. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p>	

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS		
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 2 W</p> <p style="text-align: center;">¼ $\frac{S\ 5}{S\ 8}$</p> <p style="text-align: center;">1974</p> <p>Reset cedar post alongside the iron post.</p> <p style="text-align: center;">_____</p> <p>N. 89°34' W., beginning new measurement.</p> <p>9.55 Trail road, bears NE and SW.</p> <p>40.05 The cor. of secs. 5, 6, 7 and 8.</p>	
	<p>N. 89°55' W., bet secs. 6 and 7.</p> <p>Over rolling land, through sagebrush and shadscale.</p> <p>24.00 Trail road, bears NE and SW.</p> <p>40.15 The ¼ sec. cor. of secs. 6 and 7, monumented with a sandstone, 12 x 10 x 8 ins., firmly set and plainly mkd. ¼ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 16 S R 2 W</p> <p style="text-align: center;">¼ $\frac{S\ 6}{S\ 7}$</p> <p style="text-align: center;">1974</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p style="text-align: center;">_____</p> <p>N. 89°06' W., beginning new measurement.</p> <p>Asc. gentle E slope.</p> <p>3.50 Trail road, bears NW and SE.</p> <p>20.22 Point for the W 1/16 sec. cor. of secs. 6 and 7, at proportionate distance.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of brass cap, mkd.</p> <p style="text-align: center;">T 16 S R 2 W</p> <p style="text-align: center;">W 1/16 $\frac{S\ 6}{S\ 7}$</p> <p style="text-align: center;">1974</p>	

Dependent Resurvey of a portion of the Subdivisional Lines, T. 16 S., R. 2 W., Salt Lake Meridian, Utah

CHAINS

40.34 The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp.

From the cor. of secs. 5, 6, 7 and 8.


N. 0°05' E., bet. secs. 5 and 6.

Over rolling land, through sagebrush and shadscale.

40.32 The ¼ sec. cor. of secs. 5 and 6, monumented with a sandstone, 12 x 10 x 6 ins., firmly set and plainly mkd. ¼ on W face.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit the mkd. stone alongside the iron post.

N. 0°05' E., beginning new measurement.

10.00 Enter scattering juniper growth.

39.81 The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp.

General Description

The area resurveyed within T. 16 S., R. 2 W., Salt Lake Meridian, varies from mountainous in the extreme east portion, to bottom lands in the central and rolling in the western portion. The elevation ranges from about 5,000 to 5,600 ft. above sea level. The soil varies from sandy clay loam on the higher elevations to black loam in the bottom lands. The vegetation consists of sagebrush, shadscale, bunchgrass, willows along river and lightly scattering juniper growth on the higher elevations.

The Sevier Bridge Reservoir is located in portions of secs. 25 and 36, from which the Sevier River flows in a northerly direction, leaving the township on the N. bdy. of sec. 3.

Access is by U.S. Highway No. 91, which enters the township on the E. bdy. of sec. 1 and leaves on the S. bdy. of sec. 33. There are numerous gravel and dirt roads throughout the township.

The principal use of the area is livestock grazing, with several dry farms under cultivation in the western portion.

Molten Spring and Blue Springs are located in the NE¼NE¼ of sec. 34.

The mean magnetic declination is 16°30' E.

CERTIFICATE OF SURVEY

(I) ~~(We)~~, Craig P. Sylvester, Supervisory Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 10th day of January, 19 74, (I) ~~(We)~~ have dependently resurveyed the west boundary, a portion of the north and south boundaries and a portion of the subdivisional lines of T. 16 S., R. 2 W.,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

April 28, 1975
(Date)

Craig P. Sylvester
(Cadastral Surveyor)
Supervisory

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
~~Washington, D.C.~~
Denver, Colorado

The foregoing field notes of the dependent resurvey of the west boundary, a portion of the north and south boundaries and a portion of the subdivisional lines of T. 16 S., R. 2 W., Salt Lake Meridian, Utah

executed by Craig P. Sylvester, Supervisory Cadastral Surveyor having been critically examined and found correct, are hereby approved.

DEC 04 1979
(Date)

J. J. [Signature]
(Chief, Division of Cadastral Survey)
Chief, Cadastral Survey Examination and Approval Staff

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above described surveys in _____, is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey) 6-6-67-226

INDEX DIAGRAM

Township 33 S., Range 5 W.,

			15		
6	5	4 37	3 32	2	1 10
		45	36		24
14 7 54	8 44	9 35	10	11 23	12 9
54	53	43		31	22
13 18 52	17 42	16	15 30	14 21	13 8
52	51	41	34	29	21
21 19 50	20 40	21 34	22 28	23 19	24 7
50	49	40	33	27	18
11 30 47	29 39	28	27 26	26 17	25 6
47	46			25	17
10 31 45	32	33	34 24	35 16	36 5
4				3	2

- Subdivision of Section 3 - Page 55
- Subdivision of Section 9 - Page 59
- Subdivision of Section 12 - Page 62
- Subdivision of Section 13 - Page 63
- Subdivision of Section 21 - Page 64
- Subdivision of Section 23 - Page 66
- Subdivision of Section 24 - Page 69
- Subdivision of Section 25 - Page 71
- Subdivision of Section 26 - Page 73
- Subdivision of Section 29 - Page 77
- Subdivision of Section 35 - Page 80

Township 33 South, Range 5 West, Salt Lake Meridian, Utah

CHAINS

The east boundary (Panguitch Guide Meridian) was surveyed by J.G. Burrill in 1874. The south boundary, the south 5 miles of the west boundary, the east 4 miles of the north boundary and a portion of the subdivisional lines were surveyed by T.C. Bailey and J.G. Burrill in 1874. The north 1 mile of the west boundary, the west 2 miles of the north boundary and a portion of the subdivisional lines were surveyed, and a portion of the west boundary retraced by Ralph Gentry in 1920. The cor. of secs. 4, 5, 32, and 33 on the N. bdy. of the Tp. was remonumented by W.H. Sylvester, Supervisory Cadastral Surveyor, as recorded in the official record of the 1960 survey of a portion of T. 32 S., R. 5 W. The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp. was remonumented by Ferrel D. Reynolds, Supervisory Survey Technician, in 1968, under the remonumentation cooperative agreement between BLM and U.S. Forest Service. The east 4 miles of the north boundary were retraced by Craig P. Sylvester in 1964.

The following field notes are those of a dependent resurvey of the east boundary, portions of the south, north, and west boundaries and subdivisional lines, and the survey of the subdivision of sections 3, 9, 12, 13, 21, 23, 24, 25, 26, 29, and 35, Township 33 South, Range 5 West, Salt Lake Meridian, Utah.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group 574, Utah, dated April 20, 1978.

The directions of the lines of this survey were determined by reference to true meridians established on line by hour angle observations on Polaris. They were carried forward by sustained angulation, being supplemented by numerous other observations on Polaris taken throughout the progress of the survey.

Measurements were determined by electronic means along survey lines.

Before restoring lost corners, the lines of the original survey were retraced and a diligent search made for any evidence of the original corners. The rules of proportionate measurement were applied to ascertain the position of the lost corner after every reasonable possibility of finding direct evidence of the corner had been exhausted.

The geographic position of the southeast corner of the township, as determined by ties to United States Geological Survey triangulation station "Sec. Cor. 36/32S/5W", NE corner of township, is as follows:

Latitude $37^{\circ} 53' 27.06''$ N. Longitude $112^{\circ} 21' 27.82''$ W

The mean magnetic declination is $15^{\circ} 30'$ E.

Dependent Resurvey of a Portion of the South Boundary,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

(Restoring the 1874 Survey by
J.G. Burrill and T.C. Bailey)

436

Dependent Resurvey of a Portion of the South Boundary,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	<p>Beginning at the cor. of Tps. 33 and 34 S., Rs. 4½ and 5 W., monumented with a gray granite stone, 14 x 8 x 6 ins., firmly set 6 ins. in the ground, and plainly mkd. 6 notches on 3 edges.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W R 4½ W</p> <p style="text-align: center;">S 36 S 31 S 1 S 6</p> <p style="text-align: center;">R 5 W R 4½ W</p> <p style="text-align: center;">T 34 S 1978</p> <p>Bury the mkd. stone alongside the iron post.</p> <p>S. 89° 56' W., bet. secs. 1 and 36.</p> <p>Over brush covered bench land; desc. over gentle W slope.</p>
40.29	<p>The ¼ sec. cor. of secs. 1 and 36, monumented with a granite stone, 12 x 10 x 8 ins., firmly set 6 ins. in the ground, and plainly mkd. ¼ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W</p> <p style="text-align: center;">¼ $\frac{S 36}{S 1}$</p> <p style="text-align: center;">T 34 S R 5 W 1978</p> <p>Bury the mkd. stone and set a steel fence post alongside the iron post.</p> <p style="text-align: center;">—————</p> <p>N. 89° 49' W., beginning new measurement.</p> <p>Desc. over gentle W slope.</p>
40.07	<p>The cor. of secs. 1, 2, 35, and 36, monumented with a granite stone, 14 x 8 x 6 ins., firmly set 8 ins. in the ground and plainly mkd. 1 notch on E and 5 notches on W edges.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the South Boundary,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS					
	<p>T 33 S R 5 W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 35</td> <td style="padding: 0 5px;">S 36</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 2</td> <td style="padding: 0 5px;">S 1</td> </tr> </table> <p>T 34 S R 5 W 1978</p> <p>Bury the mkd. stone alongside the iron post.</p> <p>Cor. is located at fence cor., fences bear S and W.</p>	S 35	S 36	S 2	S 1
S 35	S 36				
S 2	S 1				
	<p>S. 89° 41' W., bet. secs. 2 and 35.</p> <p>Over bench land; desc. over gentle W slope, along E and W fence line.</p>				
20.10	<p>Point for the E 1/16 sec. cor. of secs. 2 and 35.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">E 1/16</td> <td style="padding: 0 5px;">S 35</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">S 2</td> </tr> </table> <p style="text-align: center;">T 34 S R 5 W 1978</p> <p>Cor. is located on fence cor., fences bear N and E.; desc. over gentle W slope, across reseeded area.</p>	E 1/16	S 35		S 2
E 1/16	S 35				
	S 2				
40.20	<p>The ¼ sec. cor. of secs. 2 and 35, determined by steel fence post set in a small mound of stone. This point is recognized by adjacent land owners and is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">¼</td> <td style="padding: 0 5px;">S 35</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">S 2</td> </tr> </table> <p style="text-align: center;">T 34 S R 5 W 1978</p> <p>Set a steel fence post alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 39' W., beginning new measurement.</p> <p>Desc. gentle W slope, across reseeded area.</p>	¼	S 35		S 2
¼	S 35				
	S 2				
19.50	<p>Trail road, bears S and NW.</p>				
40.20	<p>The cor. of secs. 2, 3, 34, and 35, determined at intersection of N and S fence with old abandoned fences from E and W. This position is harmoniously related to existing original cors., and is accepted as the best available evidence of the original cor. position.</p>				

Dependent Resurvey of a Portion of the South Boundary,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T 33 S R 5 W

S 34	S 35
S 3	S 2

T 34 S R 5 W
1978

From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., monumented with a granite stone, 16 x 14 x 8 ins., firmly set 10 ins. in the ground, and plainly mkd. 1 notch on W and 5 notches on E edges, at fence cor., fences bear N, S, and E.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T 33 S R 5 W

S 31	S 32
S 6	S 5

T 34 S R 5 W
1978

Bury the mkd. stone alongside the iron post.

S. 89° 57' W., bet. secs. 6 and 31.

Over broken hills; asc. over E slope.

13.10 Graded dirt road, bears NW and SE.

40.19 The ¼ sec. cor. of secs. 6 and 31, monumented with a granite stone, 12 x 8 x 6 ins., firmly set 6 ins. in the ground, and plainly mkd. ¼ on N face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 33 S R 5 W

¼	S 31	
	S 6	

T 34 S R 5 W
1978

Bury the mkd. stone alongside the iron post

S. 89° 30' W., beginning new measurement.

Asc. over NE slope.

Dependent Resurvey of a Portion of the South Boundary,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

38.11 The cor. of Tps. 33 and 34 S., Rs. 5 and 6 W., monumented with a granite stone, 20 x 17 x 16 ins., firmly set 10 ins. in the ground, and plainly mkd. 6 notches on 4 edges.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 33 S
R 6 W R 5 W

S 36	S 31
S 1	S 6

R 6 W R 5 W
1978

Bury the mkd. stone alongside the iron post.

Cor. is located 3 lks. E of fence cor., fences bear W and N.

Dependent Resurvey of the East Boundary,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

(Restoring the 1874 Survey by J.G. Burrill)

From the cor. of Tps. 33 and 34 S., Rs. 4½ and 5 W., previously described.

N. 0° 34' E., bet. secs. 31 and 36.

Over rolling bench land, covered with shadscale; along gentle W slope.

40.38 The ¼ sec. cor. of secs. 31 and 36, monumented with a granite stone, 17 x 8 x 8 ins., firmly set 4 ins. in the ground, and plainly mkd. ¼ on W face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 33 S
R 5 W R 4½ W

S 36	S 31
------	------

1978

Bury the mkd. stone and set a steel fence post alongside the iron post.

Dependent Resurvey of the East Boundary,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS					
	<p>N. 0° 45' E., beginning new measurement.</p> <p>Continue along gentle W slope.</p> <p>40.42 Point for the cor. of secs. 25, 30, 31, and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 33 S R 5 W R 4½ W</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 25</td> <td style="padding: 0 5px;">S 30</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 36</td> <td style="padding: 0 5px;">S 31</td> </tr> </table> <p>1978</p> </div> <p>A fence cor., bears N. 45° W., 18 lks. dist., fences bear N and W.</p> <p>Cor. is located in wash area, which drains NW.</p>	S 25	S 30	S 36	S 31
S 25	S 30				
S 36	S 31				
	<p>N. 0° 45' E., bet. secs. 25 and 30.</p> <p>Over rolling bench land, covered with shadscale; along gentle W slope, on E side of N and S fence line.</p> <p>40.42 The ¼ sec. cor. of secs. 25 and 30, monumented with a basalt stone, 10 x 10 x 10 ins., firmly set 6 ins. in the ground, and plainly mkd. ¼ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 33 S R 5 W R 4½ W</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 25</td> <td style="padding: 0 5px;">S 30</td> </tr> </table> <p>1978</p> </div> <p>Bury the mkd. stone alongside the iron post.</p> <p>Cor. is located 23 lks. E of fence cor., fences bear S and W.</p>	S 25	S 30		
S 25	S 30				
	<p>N. 0° 18' E., beginning new measurement.</p> <p>Continue along general W slope.</p> <p>19.80 Trail road on low spur, bears N. 69° E. and S. 69° W.</p> <p>40.33 The cor. of secs. 19, 24, 25, and 30, at proportionate distance; there is no remaining evidence of the original cor.</p>				

Dependent Resurvey of the East Boundary,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T 33 S
R 5 W R 4½ W

S 24	S 19
S 25	S 30

1978

Set a steel fence post alongside the iron post.

Cor. is located in flood area, which drains W.

N. 0° 18' E., bet. secs. 19 and 24.

Over bench land, covered with shadscale; along gentle W slope.

20.20 Trail road on small rise, bears E and W.

40.33 The ¼ sec. cor. of secs. 19 and 24, monumented with a black granite stone, 18 x 14 x 12 ins., firmly set 6 ins. in the ground, and plainly mkd. ¼ on W face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T 33 S
R 5 W R 4½ W

¼		
	S 24	S 19

1978

Bury the mkd. stone alongside the iron post.

N. 0° 29' E., beginning new measurement.

Continue along gentle W slope.

21.00 Sanford Creek, drains W.

40.37 The cor. of secs. 13, 18, 19, and 24, monumented with a granite stone, 18 x 12 x 10 ins., firmly set 8 ins. in the ground, and mkd. 3 grooves on N and S faces, and 6 notches on E edge.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

442

Dependent Resurvey of the East Boundary,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS							
	<p style="text-align: center;">T 33 S R 5 W R 4½ W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 13</td> <td style="padding: 0 5px;">S 18</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 24</td> <td style="padding: 0 5px;">S 19</td> </tr> </table> <p style="text-align: center;">1978</p> <p>Bury the mkd. stone and set a steel fence post alongside the iron post.</p>	S 13	S 18	S 24	S 19		
S 13	S 18						
S 24	S 19						
<p>0.50</p> <p>32.70</p> <p>40.41</p>	<p>N. 0° 24' E., bet. secs. 13 and 18.</p> <p>Over brush covered bench land; along gentle W slope.</p> <p>Dirt road, bears N. 88° W. and S. 88° E.</p> <p>Graded dirt road, bears N. 89° W. and S. 89° E.</p> <p>The ¼ sec. cor. of secs. 13 and 18, monumented with a granite stone, 16 x 12 x 10 ins., firmly set 6 ins. in the ground, and plainly mkd. ¼ on W face, with a steel fence post alongside.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p>						
<p>40.75</p>	<p style="text-align: center;">T 33 S R 5 W R 4½ W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 13</td> <td style="padding: 0 5px;">S 18</td> </tr> </table> <p style="text-align: center;">1978</p> <p>Bury the mkd. stone and reset the steel fence post alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 23' E., beginning new measurement.</p> <p>Continue along gentle W slope.</p> <p>The cor. of secs. 7, 12, 13, and 18, monumented with a granite stone, 22 x 12 x 9 ins., firmly set 10 ins. in the ground, and plainly mkd. 2 grooves on N and 4 grooves on S face, also 6 notches on E edge.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W R 4½ W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 12</td> <td style="padding: 0 5px;">S 7</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 13</td> <td style="padding: 0 5px;">S 18</td> </tr> </table> <p style="text-align: center;">1978</p>	S 13	S 18	S 12	S 7	S 13	S 18
S 13	S 18						
S 12	S 7						
S 13	S 18						

Dependent Resurvey of the East Boundary,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

Bury the mkd. stone and set a steel fence post alongside the iron post.

N. 0° 28' E., bet. secs. 7 and 12.

Over brush covered bench, along gentle W slope.

40.01 Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 12, determined latitudinally by E and W fence line and longitudinally on line between sec. corners. A granite stone, 16 x 10 x 10 ins., plainly mkd. $\frac{1}{4}$ was found lying loose where bulldozer had moved it during fencing operations.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T 33 S
R 5 W R 4 $\frac{1}{2}$ W

$\frac{1}{4}$
|
S 12 | S 7
|

1978

Bury the mkd. stone alongside the iron post.

N. 0° 28' E., beginning new measurement.

Continue along gentle W slope.

19.50 Trail road, bears SW and E.

20.00 Fence cor., fences bear E and N along section line.

33.00 Trail road, bears NW and SE.

40.34 The cor. of secs. 1, 6, 7, and 12, determined by a re-bar set in a mound of stone. This position has long been recognized as the cor. by adjacent land owners, and is accepted as the best available evidence of the original cor. position.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T 33 S
R 5 W R 4 $\frac{1}{2}$ W

S 1 | S 6
S 12 | S 7

1978

Set re-bar alongside the iron post.

Cor. is located 1 lk. W of N and S fence line.

444

Dependent Resurvey of the East Boundary,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	<p>N. 0° 26' E., bet. secs. 1 and 6.</p>
	<p>Over brush covered bench land, draining W, along N and S fence line.</p>
40.32	<p>The ¼ sec. cor. of secs. 1 and 6, monumented with a granite stone, 8 x 6 x 6 ins., set 2 ins. in the ground and dimly mkd. ¼ on W face. Also scattered mound of stone.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T 33 S R 5 W R 4½ W</p>
	<p style="text-align: center;">¼ S 1 S 6 </p>
	<p style="text-align: center;">1978</p>
	<p>Bury the mkd. stone alongside the iron post.</p>
	<p>Cor. is located in N and S fence line.</p>
	<p style="text-align: center;">————— </p> <p>N. 0° 26' E., beginning new measurement.</p>
	<p>Continue along gentle W slope, on N and S fence line.</p>
1.20	<p>Trail road, bears NW and SE.</p>
40.36	<p>The cor. of Tps. 32 and 33 S., Rs. 4½ and 5 W., monumented with an iron post, 2½ ins. diam., extending 8 ins. above ground, mkd. as described in the official record of the 1964 resurvey of a portion of the S. bdy. of T. 32 S., R. 5 W.</p>
	<p>This cor. has been designated as a triangulation station by U.S.G.S. located at Latitude 37°58'43.061" N, Longitude 112°21'24.488" W, as published by U.S.G.S.</p>
<p>Dependent Resurvey of a Portion of the West Boundary, T. 33 S., R. 5 W., Salt Lake Meridian, Utah</p>	
<p>(Restoring the 1874 Survey by J.G. Burrill and T.C. Bailey)</p>	
	<p>From the cor. of Tps. 33 and 34 S., Rs. 5 and 6 W., previously described.</p>
	<p>N. 0° 30' E., bet. secs. 31 and 36.</p>
	<p>Over mountain bench land, covered with juniper and pinon; along E side of reseeded area on N and S fence line.</p>
37.40	<p>Graded dirt road, bears E and W; asc. over SE slope, in wide draw.</p>

Dependent Resurvey of a Portion of the West Boundary,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS		
39.86	<p>The $\frac{1}{4}$ sec. cor. of secs. 31 and 36, monumented with a sandstone, 14 x 6 x 4 ins., firmly set 6 ins. in the ground, and plainly mkd. $\frac{1}{4}$ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 33 S R 6 W R 5 W</p> <p>$\frac{1}{4}$</p> <p>S 36 S 31</p> <p>1978</p> </div> <p>Bury the mkd. stone alongside the iron post, and raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W of cor.</p> <hr style="width: 20%; margin: auto;"/> <p>N. $1^{\circ} 16'$ E., beginning new measurement.</p> <p>Asc. over SE slope in bottom of wide draw.</p>	
39.83	<p>Point for the cor. of secs. 25, 30, 31, and 36, determined at record course and distance from original bearing tree</p> <p>A pine, 14 ins. diam., bears S. 26° W., 185 lks. dist., mkd. T33S R6W S36 BT.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 33 S R 6 W R 5 W</p> <p>S 25 S 30 S 36 S 31</p> <p>1978</p> </div> <p>Raised mound of stone, 3 ft. base, 3 ft. high, W of cor.</p>	
	<p style="text-align: center;">(Restoring the 1874 survey by J.G. Burrill and T.C. Bailey, and the 1920 Retracement by Ralph Gentry)</p> <hr style="width: 20%; margin: auto;"/> <p>N. $0^{\circ} 37'$ E., bet. secs. 25 and 30.</p> <p>Over mountain bench land, covered with juniper and pinon; asc. over S slope.</p>	
39.83	<p>The $\frac{1}{4}$ sec. cor. of secs. 25 and 30, monumented with a granite stone, 16 x 12 x 8 ins., firmly set in a small mound of stone and plainly mkd. $\frac{1}{4}$ on W face.</p> <p>At the corner point</p>	

446

Dependent Resurvey of a Portion of the West Boundary,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 33 S R 6 W R 5 W</p> <p style="text-align: center;">¼ S 25 S 30 </p> <p style="text-align: center;">1978</p> <p>Place the mkd. stone in mound alongside the iron post.</p>
	<p>N. 0° 29' E., beginning new measurement.</p> <p>Asc. along E slope in hollow.</p>
40.18	<p>The cor. of secs. 19, 24, 25, and 30, monumented with a granite stone, 16 x 16 x 8 ins., firmly set 10 ins. in the ground, and plainly mkd. 2 notches on S and 4 notches on N edges, also mound of stone S of corner, original bearing tree missing.</p>
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 33 S R 6 W R 5 W</p> <p style="text-align: center;">S 24 S 19 S 25 S 30</p> <p style="text-align: center;">1978</p>
	<p>Bury the mkd. stone and set a steel fence post alongside the iron post.</p>
	<p>N. 0° 57' E., bet. secs. 19 and 24.</p> <p>Over mountain bench land, covered with scattered juniper and pinon; asc. over SW slope.</p>
39.10	<p>Dirt road, bears N. 72° W. and S. 72° E.</p>
40.07	<p>The ¼ sec. cor. of secs. 19 and 24, monumented with a granite stone, 14 x 10 x 8 ins., firmly set 6 ins. in the ground, and plainly mkd. ¼ on W face.</p>
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the West Boundary,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	<p style="text-align: center;">T 33 S R 6 W R 5 W</p> <p style="text-align: center;"> $\frac{1}{4}$ S 24 S 19 </p> <p style="text-align: center;">1978</p> <p>Bury the mkd. stone and set a steel fence post alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 48' E., beginning new measurement.</p> <p>Over rolling mountain bench.</p> <p>40.00 Trail road, bears SW and NE.</p> <p>40.20 The cor. of secs. 13, 18, 19, and 24, monumented with an iron post, 2½ ins. diam., extending 8 ins. above ground, mkd. as described in the official record of the 1968 remonumentation.</p> <p>Cor. is located at fence cor., fences bear N and W.</p>
	<p>N. 0° 57' E., bet. secs. 13 and 18.</p> <p>Over mountain bench land, along W side of fence, which bears N irregularly; with trail road along E side of fence.</p> <p>37.40 Wash in Tebbs Hollow, drains E irregularly; asc. over S slope.</p> <p>40.18 The ¼ sec. cor. of secs. 13 and 18, monumented with a granite stone, 18 x 14 x 6 ins., firmly set in a small mound of stone, plainly mkd. ¼ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 33 S R 6 W R 5 W</p> <p style="text-align: center;"> $\frac{1}{4}$ S 13 S 18 </p> <p style="text-align: center;">1978</p> <p>Bury the mkd. stone alongside the iron post.</p> <p>Cor. is located in reseeded area, 120 lks. W of N and S fence line.</p> <hr style="width: 20%; margin: 10px auto;"/>

33

Dependent Resurvey of a Portion of the West Boundary,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS					
39.69	<p>N. 0° 40' E., beginning new measurement.</p> <p>Asc. over S slope.</p> <p>The cor. of secs. 7, 12, 13, and 18, monumented with a granite boulder, 28 x 14 x 8 ins., firmly set 10 ins. in the ground, and plainly mkd. 6 notches on E and W edges, 4 grooves on S and 2 grooves on N face.</p> <p>from which</p> <p style="padding-left: 40px;">A cedar, 16 ins. diam., bears S. 48° W., 10 lks. dist., marks have overgrown.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 33 S R 6 W R 5 W</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 12</td> <td style="padding: 0 5px;">S 7</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 13</td> <td style="padding: 0 5px;">S 18</td> </tr> </table> <p>1978</p> </div> <p>Place the mkd. stone and set a steel fence post alongside the iron post.</p> <p>Cor. is located 12 lks. E of N and S fence line.</p>	S 12	S 7	S 13	S 18
S 12	S 7				
S 13	S 18				
39.81	<p>N. 1° 18' E., bet. secs. 7 and 12.</p> <p>Over mountain land, covered with juniper and pinon; asc. over SE slope. Along fence line, which bears N and S.</p> <p>The ¼ sec. cor. of secs. 7 and 12, monumented with a granite stone, 10 x 8 x 6 ins., firmly set 5 ins. in the ground and plainly mkd. ¼ on W face.</p> <p>from which</p> <p style="padding-left: 40px;">A pinon, 14 ins. diam., bears N. 58° E., 14 lks. dist., faint scribe marks (record, N. 41° E., 10 lks. dist.).</p> <p style="padding-left: 40px;">A pinon, 12 ins. diam., bears N. 58° W., 28 lks. dist., illegible scribe marks (record, N. 41° 30' W., 21 lks. dist.).</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 33 S R 6 W R 5 W</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 12</td> <td style="padding: 0 5px;">S 7</td> </tr> </table> <p>1978</p> </div>	S 12	S 7		
S 12	S 7				

Dependent Resurvey of a Portion of the West Boundary,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	<p>Bury the mkd. stone and set a steel fence post alongside the iron post.</p>
	<p>Cor. is located 42 lks. E of N and S fence line.</p>
	<p>N. 0° 08' E., beginning new measurement.</p>
	<p>Continue over mountain land.</p>
39.99	<p>The cor. of secs. 1, 6, 7, and 12, monumented with an iron post, 2 ins. diam., extending 10 ins. above ground, with brass cap mkd. as described in the official record of the 1920 resurvey.</p> <p>from which</p> <p style="padding-left: 40px;">A pinon, 14 ins. diam., bears S. 79° W., 35 lks. dist., mkd. T33S R6W S12 BT.</p> <p style="padding-left: 40px;">A pinon, 12 ins. diam., bears N. 56° W., 59 lks. dist., mkd. T33S R6W S1 BT.</p>
	<p>Dependent Resurvey of a Portion of the North Boundary, T. 33 S., R. 5 W., Salt Lake Meridian, Utah</p>
	<p>(Restoring the 1874 Survey by J.G. Burrill and T.C. Bailey and the 1964 Resurvey by C.P. Sylvester)</p>
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 3 and 34, on the N. bdy. of the Tp., hereinafter described.</p>
	<p>S. 88° 59' W., bet. secs. 3 and 34.</p>
	<p>Over hilly land, covered with shadscale; asc. over general E slope.</p>
0.615	<p>Highway right-of-way and fence bears N. 32°55'30" E., and S. 32°55'30" W.</p>
20.14	<p>Point for the W 1/16 sec. cor. of secs. 3 and 34.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 32 S R 5 W</p> <p style="text-align: center;">W 1/16 $\frac{S\ 34}{S\ 3}$</p> <p style="text-align: center;">T 33 S R 5 W 1978</p>
	<p>Set a steel fence post alongside the iron post.</p>
40.28	<p>The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., hereinafter described.</p>

450

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 33 S., R. 5 W., Salt Lake Meridian, Utah

(Restoring the 1874 Survey by
J.G. Burrill and T.C. Bailey)

From the cor. of secs. 1, 2, 35, and 36, on the S. bdy.
of the Tp., previously described.

N. 0° 23' E., bet. secs. 35 and 36.

Over brush covered bench land; along gentle W slope.

40.20 The $\frac{1}{4}$ sec. cor. of secs. 35 and 36, monumented with a
granite stone, 10 x 8 x 6 ins., firmly set 4 ins. in the
ground and plainly mkd. $\frac{1}{4}$ on W face. Also Bureau of Land
Management sign on steel fence post, 5 lks. E of cor.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, in a collar of stone, with brass cap mkd.

T 33 S R 5 W

$\frac{1}{4}$
|
S 35 | S 36
|

1978

Bury the mkd. stone alongside the iron post.

N. 0° 24' E., beginning new measurement.

Continue along gentle W slope.

40.27 The cor. of secs. 25, 26, 35, and 36, monumented with a
granite stone, 14 x 10 x 8 ins., firmly set 8 ins. in the
ground, and plainly mkd. 1 notch on S and E edges. Also
Bureau of Land Management sign on steel fence post, 6 lks.
N of cor.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in
the ground, in a collar of stone, with brass cap mkd.

T 33 S R 5 W

S 26 | S 25
S 35 | S 36

1978

Bury the mkd. stone alongside the iron post.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., previously described.
	S. 89° 52' W., bet. secs. 25 and 36.
	Over brush covered bench land, along E and W fence line; desc. over gentle W slope.
40.49	The ¼ sec. cor. of secs. 25 and 36, monumented with a granite stone, 12 x 8 x 4 ins., firmly set 4 ins. in the ground, and plainly mkd. ¼ on N face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 33 S R 5 W
	¼ $\frac{S\ 25}{S\ 36}$
	1978
	Bury the mkd. stone alongside the iron post.
	Cor. is located on E and W fence line.
	S. 89° 47' W., beginning new measurement.
20.11	Point for the W 1/16 sec. cor. of secs. 25 and 36.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T 33 S R 5 W
	W 1/16 $\frac{S\ 25}{S\ 36}$
	1978
	Set a steel fence post alongside the iron post.
40.22	The cor. of secs. 25, 26, 35, and 36.
	N. 0° 23' E., bet. secs. 25 and 26.
	Over brush covered bench land, along gentle W slope.
10.50	Dirt road, bears S. 81° W. and N. 81° E.
20.115	Point for the S 1/16 sec. cor. of secs. 25 and 26.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T 33 S R 5 W.
	S 1/16
	S 26 S 25
	1978

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS		
40.23	<p>The ¼ sec. cor. of secs. 25 and 26, monumented with a granite stone, 12 x 8 x 6 ins., firmly set 4 ins. in the ground, and plainly mkd. ¼ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W</p> <p style="text-align: center;"> $\frac{1}{4}$ S 26 S 25 </p> <p style="text-align: center;">1978</p> <p>Bury the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 23' E., beginning new measurement.</p> <p>Continue along gentle W slope.</p>	
5.70	<p>Dirt road, bears S. 38° W. and N. 38° E.</p>	
20.13	<p>Point for the N 1/16 sec. cor. of secs. 25 and 26.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W N 1/16</p> <p style="text-align: center;">S 26 S 25</p> <p style="text-align: center;">1978</p>	
40.26	<p>The cor. of secs. 23, 24, 25, and 26, monumented with a granite stone, 12 x 8 x 8 ins., firmly set 4 ins. in the ground and plainly mkd. 2 notches on S and 1 notch on E edges.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W</p> <p style="text-align: center;"> S 23 S 24 S 26 S 25 </p> <p style="text-align: center;">1978</p> <p>Bury the mkd. stone alongside the iron post.</p>	
	<p>From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., previously described.</p> <p>S. 89° 37' W., bet. secs. 24 and 25.</p>	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	Over brush covered bench land; desc. over gentle W slope.
18.40	Trail road, bears N and S.
20.225	Point for the E 1/16 sec. cor. of secs. 24 and 25.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T 33 S R 5 W
	E 1/16 $\frac{S\ 24}{S\ 25}$
	1978
	Set a cedar post alongside the iron post.
20.75	Fence, bears S and N. 28 lks. dist., thence W.
40.45	Point for the ¼ sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 33 S R 5 W
	¼ $\frac{S\ 24}{S\ 25}$
	1978
	Set a cedar post alongside the corner.
40.78	Fence, bears S and N, 37 lks. dist., thence E.
44.00	Trail road, bears NE and SW.
60.675	Point for the W 1/16 sec. cor. of secs. 24 and 25.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T 33 S R 5 W
	W 1/16 $\frac{S\ 24}{S\ 25}$
	1978
	Set a cedar post alongside the iron post.
61.60	Trail road, bears N and S.
80.90	The cor. of secs. 23, 24, 25, and 26.
	N. 0° 35' E., bet. secs. 23 and 24.
	Over brush covered bench land; along gentle W slope.
20.10	Point for the S 1/16 sec. cor. of secs. 23 and 24.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
40.20	<p style="text-align: center;">T 33 S R 5 W S 1/16</p> <p style="text-align: center;">S 23 S 24</p> <p style="text-align: center;">1978</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <p>The 1/4 sec. cor. of secs. 23 and 24, monumented with a granite stone, 12 x 10 x 6 ins., firmly set 6 ins. in the ground, and plainly mkd. 1/4 on W face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p>
20.10	<p style="text-align: center;">T 33 S R 5 W</p> <p style="text-align: center;">1/4 S 23 S 24 </p> <p style="text-align: center;">1978</p> <p>Bury the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 36' E., beginning new measurement.</p> <p>Continue along gentle W slope.</p> <p>Point for the N 1/16 sec. cor. of secs. 23 and 24.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p>
30.50	<p style="text-align: center;">T 33 S R 5 W N 1/16</p> <p style="text-align: center;">S 23 S 24</p> <p style="text-align: center;">1978</p> <p>Sanford Creek, 1 ft. deep, 40 lks. wide, drains W; dry at time of survey.</p>
40.20	<p>The cor. of secs. 13, 14, 23, and 24, monumented with a red granite stone, 16 x 14 x 4 ins., firmly set 6 ins. in the ground, and plainly mkd. 3 notches on S and 1 notch on E edges. Corner is located in E and W fence line.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 E</p> <p style="text-align: center;">S 14 S 13 S 23 S 24</p> <p style="text-align: center;">1978</p> <p>Bury the mkd. stone alongside the iron post.</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., previously described.
	S. 89° 28' W., bet. secs. 13 and 24.
	Over brush covered bench land; desc. over gentle W slope.
40.27	The ¼ sec. cor. of secs. 13 and 24, monumented with a cobble stone, 14 x 8 x 6 ins., firmly set 6 ins. in the ground, and plainly mkd. ¼ on N face. Also a steel fence post 1 lk. E of corner.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T 33 S R 5 W
	¼ $\frac{S 13}{S 24}$
	1978
	Bury the mkd. stone alongside the iron post.
	S. 89° 19' W., beginning new measurement.
	Continue over gentle W slope.
20.165	Point for the W 1/16 sec. cor. of secs. 13 and 24.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T 33 S R 5 W
	W 1/16 $\frac{S 13}{S 24}$
	1978
	Cor. is located 2 lks. S of fence cor., fences bear N and W.
24.00	Trail road, bears N and S.
40.33	The cor. of secs. 13, 14, 23, and 24.
	N. 0° 56' E., bet. secs. 13 and 14.
	Over bench land, covered with shadscale; along gentle W slope.
11.10	Dirt road, bears N. 81° W. and S. 81° E.
40.07	Point for the ¼ sec. cor. of secs. 13 and 14, determined longitudinally by old fence line to south and latitudinally at midpoint bet. corners. This point falls on N edge of gravel road, which bears E and W. A basalt stone, 14 x 12 x 12 ins., plainly mkd. ¼ was found lying loose on S side of road.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS							
	<p>At the corner point</p> <p>Bury the mkd. stone 15 ins. below road surface.</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 29° 54' E., 57.6 lks. dist., with brass cap mkd. T33S R5W ¼ S13 38 FT RM 1978 and an arrow pointing to the corner point.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 41° 14' W., 66.7 lks. dist., with brass cap mkd. T33S R5W ¼ S14 44 FT RM 1978 and an arrow pointing to the corner point.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 0° 47' E., beginning new measurement.</p> <p>Continue along gentle W slope.</p>						
<p>40.07</p>	<p>The cor. of secs. 11, 12, 13, and 14, monumented with a basalt stone, 12 x 8 x 4 ins., firmly set 6 ins. in the ground, and plainly mkd. 1 groove on E face, marks on S edge have chipped away.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 33 S R 5 W</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 11</td> <td style="padding: 0 5px;">S 12</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 14</td> <td style="padding: 0 5px;">S 13</td> </tr> </table> <p>1978</p> </div> <p>Bury the mkd. stone alongside the iron post.</p>	S 11	S 12	S 14	S 13		
S 11	S 12						
S 14	S 13						
<p>19.88</p>	<p>From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., previously described.</p> <p>S. 88° 46' W., bet. secs. 12 and 13.</p> <p>Over bench land, covered with shadscale; desc. over gentle W slope.</p> <p>Point for the E 1/16 sec. cor. of secs. 12 and 13.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 33 S R 5 W</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">E 1/16</td> <td style="border-right: 1px solid black; padding: 0 5px;">S 12</td> <td style="padding: 0 5px;">S 13</td> </tr> <tr> <td></td> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;"></td> </tr> </table> <p>1978</p> </div> <p>Cor. is located at fence cor., fences bear W and N.</p>	E 1/16	S 12	S 13			
E 1/16	S 12	S 13					

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	Continue along fence line.
33.80	Trail road, bears N. 44° E. and S. 44° W.
39.76	Point for the ¼ sec. cor. of secs. 12 and 13, determined at fence cor., fences bear E and S. This position is recognized as the corner point by property owners and is accepted as the best available evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	<p style="text-align: center;">T 33 S R 5 W</p> <p style="text-align: center;">¼ $\frac{S\ 12}{S\ 13}$</p> <p style="text-align: center;">1978</p> <hr style="width: 20%; margin: auto;"/>
	S. 88° 33' W., beginning new measurement.
	Continue over rolling bench land, draining W.
40.22	The cor. of secs. 11, 12, 13, and 14.
	N. 0° 28' E., bet. secs. 11 and 12.
	Over bench land, covered with shadscale, draining NW.
40.49	The ¼ sec. cor. of secs. 11 and 12, monumented with a lava stone, 12 x 8 x 8 ins., firmly set 4 ins. in the ground, and plainly mkd. ¼ on W face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	<p style="text-align: center;">T 33 S R 5 W</p> <p style="text-align: center;">¼ S 11 S 12 </p> <p style="text-align: center;">1978</p>
	Bury the mkd. stone alongside the iron post.
	N. 0° 49' E., beginning new measurement.
	Continue over bench land.
40.51	The cor. of secs. 1, 2, 11, and 12, monumented with a granite stone, 16 x 14 x 10 ins., firmly set 6 ins. in the ground, and plainly mkd. 1 notch on E and 2 notches on S edges, no other marks identified. Also steel fence post, with Bureau of Land Management corner sign, 5 lks. W of corner.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS					
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 2</td> <td style="padding: 0 5px;">S 1</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 11</td> <td style="padding: 0 5px;">S 12</td> </tr> </table> <p style="text-align: center;">1978</p> <p>Bury the mkd. stone alongside the iron post.</p>	S 2	S 1	S 11	S 12
S 2	S 1				
S 11	S 12				
<p>10.00</p> <p>40.18</p>	<p>From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., previously described.</p> <p>N. 89° 56' W., bet. secs. 1 and 12.</p> <p>Over bench land, covered with shadscale, draining NW.</p> <p>Trail road, bears SE and N. 87° W.</p> <p>The ¼ sec. cor. of secs. 1 and 12, monumented with a granite stone, 14 x 12 x 8 ins., firmly set 7 ins. in the ground, and plainly mkd. ¼ on N face. Also steel fence post with Bureau of Land Management sign alongside corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 0 5px;">¼</td> <td style="border-right: 1px solid black; padding: 0 5px;">S 1</td> <td style="padding: 0 5px;">S 12</td> </tr> </table> <p style="text-align: center;">1978</p> <p>Bury the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 88° 11' W., beginning new measurement.</p> <p>Desc. over W slope of bench.</p>	¼	S 1	S 12	
¼	S 1	S 12			
<p>39.52</p> <p>40.13</p>	<p>The cor. of secs. 1, 2, 11, and 12.</p> <hr/> <p>From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., previously described.</p> <p>N. 0° 15' E., bet. secs. 34 and 35.</p> <p>Over rolling bench land, draining W; along N and S fence line and dirt road.</p> <p>The ¼ sec. cor. of secs. 34 and 35, monumented with a granite stone, 10 x 8 x 6 ins., firmly set 4 ins. in the ground, and plainly mkd. ¼ on W face.</p> <p>At the corner point</p>				

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W</p> <p style="text-align: center;"> $\frac{1}{4}$ S 34 S 35 </p> <p style="text-align: center;">1978</p> <p>Bury the mkd. stone alongside the iron post.</p> <p>Cor. is located at fence cor., fences bear S, E, and W.</p> <p style="text-align: center;">_____</p> <p>N. 0° 23' E., beginning new measurement.</p>
0.30	Dirt road, bears E and W.
8.50	Gravel road, bears E and W.
40.24	<p>Point for the cor. of secs. 26, 27, 34, and 35, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W</p> <p style="text-align: center;"> $\frac{1}{4}$ S 27 S 26 S 34 S 35 </p> <p style="text-align: center;">1978</p> <p>Raise a mound of stone, 2 ft. base, 2 ft. high, W of cor. and set a steel fence post alongside the iron post.</p> <p>From this cor., the ¼ sec. cor. of secs. 27 and 34, bears S. 89° 22' W., 40.10 chs. dist., monumented with a granite stone, 16 x 12 x 8 ins., firmly set 8 ins. in the ground, and plainly mkd. ¼ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W</p> <p style="text-align: center;"> $\frac{1}{4}$ S 27 S 34 </p> <p style="text-align: center;">1978</p> <p>Bury the mkd. stone and set a steel fence post alongside the iron post.</p>
	<p>From the cor. of secs. 25, 26, 35, and 36.</p> <p>S. 89° 35' W., bet. secs. 26 and 35.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	Over bench land, covered with shadscale; desc. over gentle W slope.
20.16	Point for the E 1/16 sec. cor. of secs. 26 and 35.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T 33 S R 5 W
	E 1/16 $\frac{S\ 26}{S\ 35}$
	1978
	Set a steel fence post alongside the corner.
36.00	Graded dirt road, bears N. 55° E. and S. 55° W.
40.32	The ¼ sec. cor. of secs. 26 and 35, monumented with a granite stone, 10 x 8 x 6 ins., firmly set 4 ins. in the ground, and plainly mkd. ¼ on N face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T 33 S R 5 W
	¼ $\frac{S\ 26}{S\ 35}$
	1978
	Bury the mkd. stone and set a steel fence post alongside the iron post.

	S. 89° 38' W., beginning new measurement.
	Desc. over gentle W slope.
40.17	The cor. of secs. 26, 27, 34, and 35.
	N. 0° 17' E., bet. secs. 26 and 27.
	Over bench land, covered with shadscale; along gentle W slope.
40.24	The ¼ sec. cor. of secs. 26 and 27, monumented with a granite stone, 12 x 10 x 6 ins., firmly set 6 ins. in the ground, and plainly mkd. ¼ on W face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

T 33 S R 5 W

$$\begin{array}{c} \frac{1}{4} \\ | \\ \text{S } 27 \quad | \quad \text{S } 26 \\ | \end{array}$$

1978

Bury the mkd. stone alongside the iron post.

Cor. is located at fence cor., fences bear N and W.

N. $0^{\circ} 24'$ E., beginning new measurement.

Asc. over SW slope, along N and S fence line.

20.045 Point for the N 1/16 sec. cor. of secs. 26 and 27.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 33 S R 5 W
N 1/16

S 27 | S 26

1978

Cor. is located on N and S fence line.

40.09 The cor. of secs. 22, 23, 26, and 27, monumented with a lava stone, 18 x 12 x 8 ins., firmly set 8 ins. in the ground, and plainly mkd. 2 notches on S and E edges.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T 33 S R 5 W

$$\begin{array}{c} \text{S } 22 \quad | \quad \text{S } 23 \\ \hline \text{S } 27 \quad | \quad \text{S } 26 \end{array}$$

1978

Bury the mkd. stone alongside the iron post.

Cor. is locate in N and S fence line.

From the cor. of secs. 23, 24, 25, and 26.

S. $89^{\circ} 23'$ W., bet. secs. 23 and 26.

Over bench land, covered with shadscale; desc. over W slope.

20.135 Point for the E 1/16 sec. cor. of secs. 23 and 26.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS		
	<p style="text-align: center;">T 33 S R 5 W</p> <p style="text-align: center;">E 1/16 $\frac{S\ 23}{S\ 26}$</p> <p style="text-align: center;">1978</p>	
40.27	<p>The $\frac{1}{4}$ sec. cor. of secs. 23 and 26, monumented with a granite stone, 14 x 6 x 6 ins., firmly set 6 ins. in the ground, and plainly mkd. $\frac{1}{4}$ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p>	
	<p style="text-align: center;">T 33 S R 5 W</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S\ 23}{S\ 26}$</p> <p style="text-align: center;">1978</p> <p>Bury the mkd. stone alongside the iron post.</p>	
	<p style="text-align: center;">_____</p> <p>S. 89° 36' W., beginning new measurement.</p> <p>Continue over top of bench.</p>	
20.135	<p>Point for the W 1/16 sec. cor. of secs. 23 and 26.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T 33 S R 5 W</p> <p style="text-align: center;">W 1/16 $\frac{S\ 23}{S\ 26}$</p> <p style="text-align: center;">1978</p> <p>Set a steel fence post alongside the iron post.</p>	
40.27	<p>The cor. of secs. 22, 23, 26, and 27.</p>	
20.08	<p>N. 0° 34' E., bet. secs. 22 and 23.</p> <p>Over broken bench land, covered with shadscale; desc. over N slope in small draw.</p> <p>Point for the S 1/16 sec. cor. of secs. 22 and 23.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W S 1/16</p> <p style="text-align: center;">S 22 S 23</p> <p style="text-align: center;">1978</p>	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

- Cor. is located in N and S fence line.
- 40.16 Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
- T 33 S R 5 W
- $\frac{1}{4}$
 |
 S 22 | S 23
 |
- 1978
- Cor. is located in N and S fence line.
- 80.32 The cor. of secs. 14, 15, 22, and 23, determined by corner of fences bearing S and W. This position is harmoniously related to existing original cors., has long been recognized as the cor. by adjacent land owners, and is accepted as the best available evidence of the original cor. position.
- At the corner point
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
- T 33 S R 5 W
- | | | |
|------|--|------|
| S 15 | | S 14 |
| S 22 | | S 23 |
- 1978
-
- From the cor. of secs. 13, 14, 23, and 24.
- S. $89^{\circ} 26'$ W., bet. secs. 14 and 23.
- Over rolling bench land, covered with shadscale, along E and W fence line.
- 37.20 Dirt road, bears NW and SE.
- 39.00 Enter wide wash area of Sanford Creek, drains NW.
- 40.29 Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
- T 33 S R 5 W
- $\frac{1}{4}$ $\frac{S 14}{S 23}$
- 1978

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS		
	Set a steel fence post alongside the iron post, which is located 8 lks. N of E and W fence line.	
	Continue across wash area.	
60.435	Point for the W 1/16 sec. cor. of secs. 14 and 23.	
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.	
	T 33 S R 5 W	
	W 1/16 $\frac{S 14}{S 23}$	
	1978	
	Set a steel fence post alongside the iron post.	
80.58	The cor. of secs. 14, 15, 22, and 23.	
	N. 0° 25' E., bet. secs. 14 and 15.	
	Over broken bench land; asc. over SW slope of small ravine.	
20.08	Point for the S 1/16 sec. cor. of secs. 14 and 15.	
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.	
	T 33 S R 5 W S 1/16	
	S 15 S 14	
	1978	
	Set a steel fence post alongside the iron post.	
21.00	Sanford Creek, drains W.	
28.60	Dirt road, bears N. 76° W. and S. 76° E.	
40.16	Point for the ¼ sec. cor. of secs. 14 and 15, at proportionate distance, falls in gravel road. A granite stone, 10 x 8 x 6 ins., plainly mkd. ¼ on one face, was found lying loose in the barrow pit.	
	At the corner point	
	Bury the mkd. stone, 15 ins. below road surface.	
	from which	
	An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 45° E., 30.3 lks. dist., with brass cap mkd. RM T33S R5W ¼ S14 20 FT 1978 and an arrow pointing to the corner point.	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

- An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 45° W., 30.3 lks. dist., with brass cap mkd. RM T33S R5W ¼ S15 20 FT 1978 and an arrow pointing to the corner point.
- Set a steel fence post alongside each reference monument.
- 80.32 The cor. of secs. 10, 11, 14, and 15, monumented with a mound of stone, and verified by remains of old fence lines to N and E, and is accepted as the best available evidence of the position of the original corner.
- At the corner point
- Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
- T 33 S R 5 W
- | | |
|------|------|
| S 10 | S 11 |
| S 15 | S 14 |
- 1978
- Set a steel fence post alongside the iron post.
-
- From the cor. of secs. 11, 12, 13, and 14.
- S. 89° 51' W., bet. secs. 11 and 14.
- Over rolling bench land, covered with shadscale; desc. over gentle W slope.
- 40.69 The ¼ sec. cor. of secs. 11 and 14, determined by mound of stone and remains of old fence corner, and is accepted as the best available evidence of the position of the original corner.
- At the corner point
- Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
- T 33 S R 5 W
- | | | |
|---|------|------|
| ¼ | S 11 | S 14 |
|---|------|------|
- 1978
- Set a cedar post, 5 ft. high, 1.5 lks. S of cor.
-
- S. 89 °22' W., beginning new measurement.
- Desc. over gentle W slope.
- 40.48 The cor. of secs. 10, 11, 14, and 15.

466

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

From the cor. of secs. 2, 3, 10, and 11, determined by cor. of fences bearing N and W. This position is harmoniously related to existing original cors., and is accepted as the best available evidence of the original corner position.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 33 S R 5 W

S 3	S 2
S 10	S 11

1978

N. $0^{\circ} 16'$ E., bet. secs. 2 and 3.

Over valley land, draining W, along N and S fence line and on W side of N and S graveled road.

40.22 The $\frac{1}{4}$ sec. cor. of secs. 2 and 3, determined by cor. of fences bearing N, S, and W and in line with the extension of fence to E. This position is accepted as the best available evidence of the original cor. position. A granite stone, 12 x 8 x 6 ins., mkd. $\frac{1}{4}$ on one face was found 20 lks. S in corral fence.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 33 S R 5 W

$\frac{1}{4}$
S 3 S 2

1978

Bury the mkd. stone alongside the iron post.

N. $0^{\circ} 21'$ E., beginning new measurement.

Along N and S fence line.

40.20 Road on E side of bridge across Sevier River, bears NW and SE, about 1 ch., thence south.

40.80 True point for the cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., falls in Sevier River, from which its witness cor. bears N. $89^{\circ} 32'$ E., 0.48 chs. dist., monumented with an iron post, $2\frac{1}{2}$ ins. diam., extending 6 ins. above a collar of stone, mkd. as described in the official record of the 1964 resurvey of a portion of the S. bdy. of T. 32 S., R. 5 W.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS		
	From the cor. of secs. 22, 23, 26, and 27.	
	S. 89° 00' W., bet. secs. 22 and 27.	
	Over broken bench land, covered with shadscale; along N slope on S side of small draw.	
20.275	Point for the E 1/16 sec. cor. of secs. 22 and 27.	
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.	
	T 33 S R 5 W	
	E 1/16 $\frac{S\ 22}{S\ 27}$	
	1978	
	Set a steel fence post alongside the iron post.	
40.55	The ¼ sec. cor. of secs. 22 and 27, monumented with a basalt stone, 18 x 14 x 4 ins., firmly set 8 ins. in the ground, and plainly mkd. ¼ on N face.	
	At the corner point	
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.	
	T 33 S R 5 W	
	¼ $\frac{S\ 22}{S\ 27}$	
	1978	
	Bury the mkd. stone and set a steel fence post alongside the iron post.	
	Cor. is located near top of terrace, which bears NW and SE.	

	S. 89° 16' W., beginning new measurement.	
	Desc. over SW slope, into ravine.	
18.00	Graded dirt road, bears N and S.	
39.74	The cor. of secs. 21, 22, 27, and 28, monumented with a granite stone, 8 x 8 x 4 ins., firmly set 4 ins. in the ground, and plainly mkd. 3 notches on E and 2 notches on S edges.	
	At the corner point	
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.	
	T 33 S R 5 W	
	S 21 S 22 S 28 S 27	
	1978	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	<p>Bury the mkd. stone alongside the iron post. Cor. is located at corner of fences bearing N, S, and W.</p>
	<p>N. 0° 20' E., bet. secs. 21 and 22. Over grass meadow land, draining W.</p>
40.21	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 27 ins. in the ground, surrounded by a collar of stone from bottom of hole to top of brass cap, mkd.</p>
	<p style="text-align: center;">T 33 S R 5 W $\frac{1}{4}$ S 21 S 22 1978</p>
80.42	<p>Set a steel fence post alongside the iron post. Cor. is located in wide ditch. Point for the cor. of secs. 15, 16, 21, and 22, determined at the intersection of the extension of fences to the N and E, and is accepted as the best available evidence of the position of the original cor., falls in bend of small canal.</p>
	<p>From the cor. of secs. 14, 15, 22, and 23. S. 89° 11' W., bet. secs. 15 and 22. Over rolling bench land draining W, over reseeded area, along E and W fence line.</p>
39.90	<p>Cattle guard across graded dirt road, which bears N and S.</p>
40.33	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 22, determined at corner of fences bearing N and W, and in line with a new fence to the E, and is accepted as the best available evidence of the position of the original cor. At the corner point Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 33 S R 5 W $\frac{1}{4}$ $\frac{S 15}{S 22}$ 1978</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

S. 89° 12' W., beginning new measurement.

Over valley land, along E and W fence line.

39.78 Point selected for the witness cor. to the cor. of secs.
15, 16, 21, and 22, in old E and W fence line.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in
the ground, with brass cap mkd.

W C
T 33 S R 5 W

←	S 16		S 15
	S 21		S 22

1978

40.26 True point for the cor. of secs. 15, 16, 21, and 22.

From the cor. of secs. 9, 10, 15, and 16, determined
longitudinally by an old fence which bears N and S, and
latitudinally by the extension of a fence to the E, and is
accepted as the best available evidence of the position of
the original cor.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in
the ground, with brass cap mkd.

T 33 S R 5 W

S 9		S 10
S 16		S 15

1978

N. 0° 02' W., bet. secs. 9 and 10.

Over river bottom land, covered with grass, along N and S
fence line.

7.50 Sevier River, 2 ft. deep, 1.20 chs. wide, drains NE.

40.06 The ¼ sec. cor. of secs. 9 and 10, monumented with a
granite stone, 12 x 6 x 6 ins., firmly set 6 ins. in the
ground, and plainly mkd. ¼ on W face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in
the ground, with brass cap mkd.

T 33 S R 5 W

S 9		S 10
	¼	

1978

Bury the mkd. stone and set a steel fence post alongside
the iron post.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS		
	<p>Cor. is located in N and S fence line.</p> <hr/> <p>N. 0° 21' E., beginning new measurement.</p> <p>Asc. along gentle E slope.</p> <p>38.40 Highway right-of-way fence, U.S. Highway No. 89, bears N. 20° 08' E., and S. 20° 08' W.; thence over highway.</p> <p>40.09 Point for the cor. of secs. 3, 4, 9, and 10, determined at intersection of fence lines from E, W, and S, and is accepted as the best available evidence of the position of the original cor., falls on shoulder of highway.</p> <p>At the corner point</p> <p>Bury glass 12 ins. below gravel surface.</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 66° 05' E., 80.3 lks. dist., with brass cap mkd. RM T33S R5W S3 53 FT 1978 and an arrow pointing to the corner point.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears S. 58° 50' E., 59 lks. dist., with brass cap mkd. RM T33S R5W S10 39 FT 1978 and an arrow pointing to the corner point.</p>	
	<p>From the cor. of secs. 2, 3, 10, and 11.</p> <p>S. 88° 48' W., bet. secs. 3 and 10.</p> <p>Over rolling bench land, draining W, along E and W fence line at top of irrigated pasture land.</p> <p>40.11 Point for the ¼ sec. cor. of secs. 3 and 10, determined at corner fences bearing E, W and S, and is accepted as the best available evidence of the position of the original cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W</p> <p style="text-align: center;">¼ $\frac{S 3}{S 10}$</p> <p style="text-align: center;">1978</p> <hr/> <p>S. 88° 54' W., beginning new measurement.</p> <p>Over irrigated pasture land, along E and W fence line.</p>	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
18.20	Sevier River, 2 ft. deep, 1 ch. wide, drains N irregularly; continue over bottom land.
20.19	<p>Point for the W 1/16 sec. cor. of secs. 3 and 10.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W</p> <p style="text-align: center;">W 1/16 $\frac{S\ 3}{S\ 10}$</p> <p style="text-align: center;">1978</p>
39.76	Highway right-of-way fence, U.S. No. 89, bears N. 20° 08' E. and S. 20° 08' W.
40.38	The cor. of secs. 3, 4, 9, and 10.
	<p>N. 0° 06' E., bet. secs. 3 and 4.</p> <p>Over U.S. Highway No. 89.</p>
1.69	Center of U.S. Highway No. 89, bears N. 20° 08' E. and S. 20° 08' W.
4.50	W right-of-way for U.S. Highway No. 89, bears N. 20° 08' E. and S. 20° 08' W.; thence through lot and buildings of Bear Valley Junction.
10.50	Utah Highway No. 20, bears N. 84° 10' W. and S. 84° 10' E., 3.00 chs. to junction with U.S. Highway No. 89; asc. along gentle E slope of brush covered bench.
20.08	<p>Point for the S 1/16 sec. cor. of secs. 3 and 4.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W</p> <p style="text-align: center;">S 1/16</p> <p style="text-align: center;">S 4 S 3</p> <p style="text-align: center;">1978</p> <p>Set a steel fence post alongside the iron post.</p>
22.85	Fence line, bears N. 75° 34' W. and S. 75° 34' E.
40.16	<p>The ¼ sec. cor. of secs. 3 and 4, monumented with a granite stone, 12 x 6 x 4 ins., firmly set 6 ins. in the ground, and plainly mkd. ¼ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS		
	<p style="text-align: center;">T 33 S R 5 W</p> <p style="text-align: center;"> $\frac{1}{4}$ S 4 S 3 </p> <p style="text-align: center;">1978</p> <p>Bury the mkd. stone and set a steel fence post alongside the iron post, also raise a small mound of stone W of cor.</p>	
19.94	<p>N. 0° 20' E., beginning new measurement.</p> <p>Asc. along gentle E slope.</p> <p>Point for the N 1/16 sec. cor. of secs. 3 and 4.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T 33 S R 5 W</p> <p style="text-align: center;">N 1/16</p> <p style="text-align: center;">S 4 S 3</p> <p style="text-align: center;">1978</p>	
25.60	<p>Set a steel fence post alongside the iron post.</p> <p>Dirt road, bears E and W.</p>	
41.02	<p>The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp. in bottom of small draw, monumented with an iron post, 2½ ins. diam., extending 8 ins. above ground, mkd. as described in the official record of the 1964 resurvey of a portion of the S. bdy. of T. 32 S., R. 5 W.</p>	
	<p>From the cor. of secs. 28, 29, 32, and 33, determined latitudinally by E and W fence line and longitudinally by proportionate measurement.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T 33 S R 5 W</p> <p style="text-align: center;"> $\frac{S\ 29}{S\ 32}$ $\frac{S\ 28}{S\ 33}$ </p> <p style="text-align: center;">1978</p>	
	<p>Set a steel fence post alongside the iron post.</p> <p>From this cor., the cor. of secs. 27, 28, 33, and 34, bears S. 89° 56' E., 80.14 chs. dist., determined at intersection of fences from S and E, also a stone, 16 x 12 x 8 ins., no marks identified, this position is accepted as the best available evidence of the position of the original corner.</p>	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 33 S R 5 W

S 28	S 27
S 33	S 34

1978

Cor. is located in muddy bottom land.

The control line was fully retraced, and no evidence of the intervening corner was found, and was not monumented because it falls on private land.

N. 0° 16' W., bet. secs. 28 and 29.

Over farm land on W side of valley.

39.90 Farm lane, bears E and W.

40.08 Point for the ¼ sec. cor. of secs. 28 and 29, determined latitudinally by E and W fence line and on line bet. sec. cors.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 33 S R 5 W

	¼	
S 29		S 28

1978

N. 0° 16' W., beginning new measurement.

Continue over farmland and brush pasture.

20.09 Point for the N 1/16 sec. cor. of secs. 28 and 29. Not monumented.

Corner point at cor. of fences bearing N and W; thence along fence line.

40.18 Point for the cor. of secs. 20, 21, 28, and 29, determined longitudinally by N and S fence line and latitudinally by proportionate measurement.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 33 S R 5 W

S 20	S 21
S 29	S 28

1978

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	From the cor. of secs. 21, 22, 27, and 28.
	N. 89° 37' W., bet. secs. 21 and 28.
	Over river bottom pasture land, covered with grass.
7.60	Sevier River, about 2 ft. deep, 1 ch. wide, drains N.
40.35	Point for the ¼ sec. cor. of secs. 21 and 28, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 33 S R 5 W
	¼ $\frac{S 21}{S 28}$
	1978
	Cor. is located in E and W fence line, on N side of lane.
59.15	Fence, bears N. 0° 20' E. and S. 0° 20' W., along highway right-of-way.
60.28	U.S. Highway No. 89, bears N. 0° 20' E. and S. 0° 20' W.
60.525	Point for the W 1/16 sec. cor. of secs. 21 and 28, falls on W side of highway, not monumented.
61.42	Fence on W side of highway, parallels highway; thence through yards and farm land.
80.70	The cor. of secs. 20, 21, 28, and 29.
	N. 0° 30' E., bet. secs. 20 and 21.
	Over farm land, along fence line.
20.09	Point for the S 1/16 sec. cor. of secs. 20 and 21.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 33 S R 5 W
	S 1/16
	S 20 S 21
	1978
	Cor. is located 4 lks. N of fence cor., from which fences bear E, W, and S.
20.40	Graded gravel road, bears E and W; enter rolling brush covered bench land.
40.18	The ¼ sec. cor. of secs. 20 and 21, monumented with a granite stone, 10 x 10 x 6 ins., firmly set 5 ins. in the ground, and plainly mkd. ¼ on W face, also steel fence post alongside cor.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W</p> <div style="text-align: center;"> $\begin{array}{c} \frac{1}{4} \\ \\ \text{S } 20 \quad \quad \text{S } 21 \\ \end{array}$ </div> <p style="text-align: center;">1978</p> <p>Bury the mkd. stone and reset the steel fence post alongside the iron post.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 0° 26' E., beginning new measurement.</p> <p>Over bench land, draining E.</p> <p>6.00 Graded dirt road, bears N. 26° W. and S. 26° E.</p> <p>39.45 Fence, bears E and W, 1.10 chs. dist.; thence N.</p> <p>40.11 Point for the cor. of secs. 16, 17, 20, and 21, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W</p> <div style="text-align: center;"> $\begin{array}{c} \text{S } 17 \quad \quad \text{S } 16 \\ \text{S } 20 \quad \quad \text{S } 21 \end{array}$ </div> <p style="text-align: center;">1978</p> <p>Set a steel fence post alongside the iron post.</p>
	<p>From the true point for the cor. of secs. 15, 16, 21, and 22.</p> <p>N. 89° 43' W., bet. secs. 16 and 21.</p> <p>Over pasture land, covered with grass.</p> <p>34.50 Sevier River, about 2 ft. deep, 1.00 ch. wide, drains N.</p> <p>40.25 Point for the ¼ sec. cor. of secs. 16 and 21, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W</p> <div style="text-align: center;"> $\frac{1}{4} \frac{\text{S } 16}{\text{S } 21}$ </div> <p style="text-align: center;">1978</p>

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	Set a steel fence post alongside the iron post.
	Continue over grassy bottom land.
54.55	Fence, parallels highway.
55.70	U.S. Highway No. 89, bears N. 4° 27' E. and S. 4° 27' W.
56.85	Fence, parallels highway.
60.375	Point for the W 1/16 sec. cor. of secs. 16 and 21.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T 33 S R 5 W
	W 1/16 $\frac{S\ 16}{S\ 21}$
	1978
	Set a steel fence post alongside the iron post.
80.50	The cor. of secs. 16, 17, 20, and 21.
	N. 0° 27' E., bet. secs. 16 and 17.
	Over rolling and broken brush covered land; along gentle E slope.
40.11	Point for the ¼ sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T 33 S R 5 W
	$\frac{1}{4}$ S 17 S 16
	1978
	Set a steel fence post alongside the iron post.
50.00	Wash in Tebbs Hollow, drains E.
80.22	The cor. of secs. 8, 9, 16, and 17, at corner of fences bearing E and S. 0° 52' W. A granite stone, 20 x 12 x 12 ins., plainly mkd. 4 notches on 2 edges was wired to the fence corner. This position is accepted as a careful and faithful perpetuation of the position of the original cor.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

T 33 S R 5 W

S 8	S 9
S 17	S 16

1978

Place the mkd. stone alongside the iron post.

From the cor. of secs. 9, 10, 15, and 16.

N. 89° 42' W., bet. secs. 9 and 16.

Over grassy river bottom land.

- 1.60 Sevier River, about 2 ft. deep, 1.00 ch. wide, drains N.
- 28.35 Fence, parallels highway.
- 29.56 U.S. Highway No. 89, bears N. 20° 08' E. and S. 20° 08' W.
- 30.77 Fence, parallels highway.
- 40.48 The $\frac{1}{4}$ sec. cor. of secs. 9 and 16, monumented with a granite stone, 12 x 12 x 6 ins., firmly set 8 ins. in the ground, and plainly mkd. $\frac{1}{4}$ on N. face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 33 S R 5 W

$\frac{1}{4}$	S 9	S 16
---------------	-----	------

1978

Bury the mkd. stone and set a steel fence post alongside the iron post.

Cor. is located 73 lks. S of E and W fence line.

N. 89° 49' W., beginning new measurement.

Asc. gentle E slope.

- 20.055 Point for the W 1/16 sec. cor. of secs. 9 and 16.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T 33 S R 5 W

W 1/16	S 9	S 16
--------	-----	------

1978

Set a steel fence post alongside the iron post.

Cor. is located 45 lks. S of E and W fence line.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
40.11	The cor. of secs. 8, 9, 16, and 17.
	N. 0° 16' E., bet. secs. 8 and 9.
	Over broken desert land; asc. over SE slope.
20.055	Point for the S 1/16 sec. cor. of secs. 8 and 9.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 33 S R 5 W
	S 1/16
	S 8 S 9
	1978
	Set a steel fence post alongside the iron post.
40.11	The ¼ sec. cor. of secs. 8 and 9, monumented with a granite stone, 14 x 8 x 6 ins., firmly set 6 ins. in the ground, and plainly mkd. ¼ on W face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 33 S R 5 W
	¼
	S 8 S 9
	1978
	Bury the mkd. stone and set a steel fence post alongside the iron post.
	N. 0° 10' E., beginning new measurement.
	Over brushy bench.
20.05	Point for the N 1/16 sec. cor. of secs. 8 and 9.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 33 S R 5 W
	N 1/16
	S 8 S 9
	1978
	Set a steel fence post alongside the iron post.
40.10	The cor. of secs. 4, 5, 8, and 9, monumented with an iron post, 2 ins. diam., extending 10 ins. above ground, with brass cap mkd. as described in the official record of the 1920 resurvey.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	<p>From the cor. of secs. 3, 4, 9, and 10.</p> <p>N. 89° 43' W., bet. secs. 4 and 9.</p> <p>Over U.S. Highway No. 89.</p>
0.59	Center U.S. Highway No. 89, bears N. 20° 08' E. and S. 20° 08' W.
1.80	Fence, parallels highway; thence over brush land.
40.25	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W</p> <p style="text-align: center;">$\frac{1}{4} \frac{S 4}{S 9}$</p> <p style="text-align: center;">1978</p> <p>Set a steel fence post alongside the iron post.</p> <p>Continue through tall brush.</p>
60.375	<p>Point for the W 1/16 sec. cor. of secs. 4 and 9.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W</p> <p style="text-align: center;">W 1/16 $\frac{S 4}{S 9}$</p> <p style="text-align: center;">1978</p> <p>Set a steel fence post alongside the iron post.</p>
68.00	Bear Creek, small stream of water, drains S. 15° E.; asc. over E slope.
80.50	The cor. of secs. 4, 5, 8, and 9.
	<p>From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., previously described.</p> <p>N. 0° 01' E., bet. secs. 31 and 32.</p> <p>Over brush pasture land, draining E; along N and S fence line.</p>
35.00	Leave fence line, which turns E.
40.10	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
80.20	<p style="text-align: center;">T 33 S R 5 W</p> <p style="text-align: center;"> $\frac{1}{4}$ S 31 S 32 </p> <p style="text-align: center;">1978</p> <p>Set a steel fence post alongside the iron post.</p> <p>Continue over brush pasture land.</p> <p>Point for the cor. of secs. 29, 30, 31, and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W</p> <p style="text-align: center;"> S 30 S 29 S 31 S 32 </p> <p style="text-align: center;">1978</p> <p>Set a steel fence post alongside the iron post.</p>
40.26	<p>From the cor. of secs. 28, 29, 32, and 33.</p> <p>S. 89° 56' W., bet. secs. 29 and 32.</p> <p>Over farm land, along E and W fence line.</p> <p>The ¼ sec. cor. of secs. 29 and 32, determined at corner of fences bearing N, S, E, and W. This position is accepted as the best available evidence of the original cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W</p> <p style="text-align: center;"> $\frac{1}{4}$ $\frac{S 29}{S 32}$ </p> <p style="text-align: center;">1978</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 09' W., beginning new measurement.</p> <p>Over brush pasture land, along S side of E and W fence line.</p> <p>20.44 Fence, bears S and N. 27 lks., thence E and W.</p> <p>20.63 Point for the W 1/16 sec. cor. of secs. 29 and 32.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS		
41.26	<p style="text-align: center;">T 33 S R 5 W</p> <p style="text-align: center;">W 1/16 $\frac{S 29}{S 32}$</p> <p style="text-align: center;">1978</p> <p>Set a steel fence post alongside the iron post.</p> <p>The cor. of secs. 29, 30, 31, and 32.</p>	
9.20 11.40 40.93	<p>N. 89° 33' W., bet. secs. 30 and 31.</p> <p>Over brush pasture land.</p> <p>Fence, bears S and N 92 lks., thence E.</p> <p>Graded dirt road, bears N. 34° E. and S. 34° W.; asc. over E slope, enter low hills.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 30 and 31, monumented with a lava stone, 14' x 14 x 8 ins., firmly set 6 ins. in the ground, and plainly mkd. $\frac{1}{4}$ on N face, from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A pine stump, 14 ins. diam., bears S. 6° E., 106 lks. dist., (Record, S. 4° W., 108 lks. dist.) NE bearing tree destroyed by wood haulers.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S 30}{S 31}$</p> <p style="text-align: center;">1978</p>	
36.18	<p>Bury the mkd. stone and set a steel fence post alongside the iron post.</p> <p style="text-align: center;">_____</p> <p>S. 88° 04' W., beginning new measurement.</p> <p>Asc. over E slope.</p> <p>The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., previously described.</p>	
0.75	<p>From the cor. of secs. 29, 30, 31, and 32.</p> <p>N. 0° 31' E., bet. secs. 29 and 30.</p> <p>Over brush covered bench land, draining E.</p> <p>Fence, bears E and W.</p>	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
20.05	<p>Point for the S 1/16 sec. cor. of secs. 29 and 30.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W S 1/16</p> <p style="text-align: center;">S 30 S 29</p> <p style="text-align: center;">1978</p> <p>Set a steel fence post alongside the iron post.</p>
40.10	<p>Point for the ¼ sec. cor. of secs. 29 and 30, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W</p> <p style="text-align: center;">¼ </p> <p style="text-align: center;">S 30 S 29</p> <p style="text-align: center;">1978</p> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located on E edge of N and S dirt road, in wide wash area; asc. along E slope, up N and S road, and on W side of N and S fence line.</p>
60.15	<p>Point for the N 1/16 sec. cor. of secs. 29 and 30.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W N 1/16</p> <p style="text-align: center;">S 30 S 29</p> <p style="text-align: center;">1978</p> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located on W edge of graded dirt road.</p>
80.20	<p>The cor. of secs. 19, 20, 29, and 30, monumented with a granite stone, 16 x 12 x 8 ins., firmly set 10 ins. in the ground, and plainly mkd. 2 notches on S and 5 notches on E edges.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

T 33 S R 5 W.

S 19	S 20
S 30	S 29

1978

Bury the mkd. stone and set a steel fence post
alongside the iron post.

From the cor. of secs. 20, 21, 28, and 29.

S. 89° 28' W., bet. secs. 20 and 29.

Over farm land.

20.05 Fence, bears N and S.

20.085 Point for the E 1/16 sec. cor. of secs. 20 and 29.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in
the ground, with brass cap mkd.

T 33 S R 5 W

E 1/16	S 20
	S 29

1978

Set a steel fence post alongside the iron post.

20.40 Graded gravel road, bears N and S.

38.20 Graded gravel road, bears N. 70° W. and S. 70° E.

40.17 The ¼ sec. cor. of secs. 20 and 29, monumented with a
granite stone, 18 x 10 x 8 ins., firmly set 10 ins. in the
ground, and plainly mkd. ¼ on N face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in
the ground, in a collar of stone, with brass cap mkd.

T 33 S R 5 W

¼	S 20
	S 29

1978

Bury the mkd. stone and set a steel fence post alongside
the iron post.

S. 89° 30' W., beginning new measurement.

Asc. over general E slope.

8.20 Graded gravel road, bears S. 20° W. and curves NE.

40.24 The cor. of secs. 19, 20, 29, and 30.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	S. 89° 18' W., bet. secs. 19 and 30,
	Over hills draining E; asc. over general E slope.
40.16	The ¼ sec. cor. of secs. 19 and 30, monumented with a granite stone, 16 x 12 x 6 ins., firmly set 6 ins. in the ground, and plainly mkd. ¼ on N face, from which an original bearing tree
	A pine, 16 ins. diam., bears N. 20° W., 20 lks. dist., faint scribe marks (record, N. 5° W.). No trace of other bearing tree.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T 33 S R 5 W
	¼ $\frac{S\ 19}{S\ 30}$
	1978
	Place the mkd. stone and set a steel fence post alongside the iron post.
	S. 89° 04' W., beginning new measurement.
	Asc. over NE slope.
36.85	The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., previously described.
	From the cor. of secs. 19, 20, 29, and 30.
	N. 0° 37' E., bet. secs. 19 and 20.
	Over hills, covered with shadscale; along general E slope.
38.10	Graded dirt road, bears N. 64° W. and S. 64° E.
40.18	The ¼ sec. cor. of secs. 19 and 20, monumented with a granite stone, 14 x 8 x 4 ins., firmly set 8 ins. in the ground, and dimly mkd. ¼ on W face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T 33 S R 5 W
	¼ S 19 S 20
	1978

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

Bury the mkd. stone and set a steel fence post
alongside the iron post.

N. 0° 28' E., beginning new measurement.

Continue over top of low ridge.

40.04 The cor. of secs. 17, 18, 19, and 20, monumented with a
granite stone, 20 x 18 x 4 ins., firmly set 10 ins. in the
ground, and plainly mkd. 3 notches on S and 5 notches on E
edges.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in
the ground, in a collar of stone, with brass cap mkd.

T 33 S R 5 W

S 18	S 17
S 19	S 20

1978

Bury the mkd. stone and set a steel fence post alongside
the iron post.

From the cor. of secs. 16, 17, 20, and 21.

S. 89° 29' W., bet. secs. 17 and 20.

Over low hills, covered with shadscale; asc. over general
E slope.

19.90 Graded dirt road, bears N. 48° W. and S. 48° E.

40.34 The ¼ sec. cor. of secs. 17 and 20, monumented with a
granite stone, 16 x 10 x 8 ins., firmly set 6 ins. in the
ground, and plainly mkd. ¼ on N face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in
the ground, in a collar of stone, with brass cap mkd.

T 33 S R 5 E

¼	S 17	S 20
	S 17	S 20

1978

Bury the mkd. stone and set a steel fence post alongside
the iron post.

S. 89° 21' W., beginning new measurement.

Asc. over NE slope.

39.93 The cor. of secs. 17, 18, 19, and 20.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS		
<p>40.21</p>	<p>S. 88° 57' W., bet. secs. 18 and 19.</p> <p>Over hills covered with shadscale; asc. over E slope.</p> <p>The ¼ sec. cor. of secs. 18 and 19, monumented with a granite stone, 14 x 12 x 10 ins., firmly set 8 ins. in the ground, and plainly mkd. ¼ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W</p> <p style="text-align: center;">¼ S 18 S 19</p> <p style="text-align: center;">1978</p> <p>Bury the mkd. stone and set a steel fence post alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 32' W., beginning new measurement.</p> <p>Over rolling mountain bench.</p>	
<p>36.00</p>	<p>Trail road, bears N and SW.</p>	
<p>36.32</p>	<p>The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., previously described.</p>	
<p>39.86</p>	<p>From the cor. of secs. 17, 18, 19, and 20.</p> <p>N. 1° 53' E., bet. secs. 17 and 18.</p> <p>Over mountain land covered with shadscale; desc. over N slope.</p> <p>The ¼ sec. cor. of secs. 17 and 18, monumented with a granite stone, 16 x 8 x 6 ins., set in a small mound of stone, and plainly mkd. ¼ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W</p> <p style="text-align: center;"> ¼ S 18 S 17 </p> <p style="text-align: center;">1978</p> <p>Bury the mkd. stone and set a steel fence post alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/>	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS							
	N. 2° 16' E., beginning new measurement.						
	Desc. over N slope, enter juniper and pinon trees.						
3.50	Graded gravel road, bears E and W.						
5.00	Wash in Tebbs Hollow, drains E.						
39.72	the cor. of secs. 7, 8, 17, and 18, monumented with a granite stone, 14 x 10 x 8 ins., firmly set 8 ins. in the ground, and plainly mkd. 4 notches on the S and 5 notches on the E edges.						
	At the corner point						
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.						
	T 33 S R 5 W						
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 2px;">S 7</td> <td style="padding: 2px;"> </td> <td style="padding: 2px;">S 8</td> </tr> <tr> <td style="padding: 2px;">S 18</td> <td style="padding: 2px;"> </td> <td style="padding: 2px;">S 17</td> </tr> </table>	S 7		S 8	S 18		S 17
S 7		S 8					
S 18		S 17					
	1978						
	Bury the mkd. stone and set a cedar post alongside the iron post.						
	From the cor. of secs. 8, 9, 16, and 17.						
	S. 88° 09' W., bet. secs. 8 and 17.						
	Over mountain land covered with shadscale; asc. over E slope.						
37.93	The ¼ sec. cor. of secs. 8 and 17, monumented with a granite stone, 14 x 12 x 6 ins., firmly set 6 ins. in the ground, and plainly mkd. ¼ on N face.						
	At the corner point						
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.						
	T 33 S R 5 W						
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 2px;">¼</td> <td style="padding: 2px;"> </td> <td style="padding: 2px;">S 8</td> </tr> <tr> <td style="padding: 2px;"></td> <td style="padding: 2px;"> </td> <td style="padding: 2px;">S 17</td> </tr> </table>	¼		S 8			S 17
¼		S 8					
		S 17					
	1978						
	Bury the mkd. stone and set a steel fence post alongside the iron post.						
	S. 89° 44' W., beginning new measurement.						
	Over brushy flat, draining E.						
40.16	The cor. of secs. 7, 8, 17, and 18.						

488

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
39.59	<p>N. 88° 19' W., bet. secs. 7 and 18.</p> <p>Over mountain land, covered with juniper and pinon; asc. over E slope.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 7 and 18, monumented with a granite stone, 14 x 8 x 6 ins., firmly set 6 ins. in the ground, and plainly mkd. $\frac{1}{4}$ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S 7}{S 18}$</p> <p style="text-align: center;">1978</p> <p>Bury the mkd. stone and set a steel fence post alongside the iron post.</p> <p>Cor. is located on N bank of wash which drains NE.</p> <p style="text-align: center;">—————</p> <p>S. 87° 18' W., beginning new measurement.</p> <p>Asc. over general E slope.</p>
38.72	<p>The cor. of secs. 7, 12, 13, and 18; on the W. bdy. of the Tp., previously described.</p> <hr/> <p>From the cor. of secs. 7, 8, 17, and 18.</p> <p>N. 3° 17' E., bet. secs. 7 and 8.</p> <p>Over mountain land covered with juniper and pinon trees; along broken E slope.</p> <p>39.98 The $\frac{1}{4}$ sec. cor. of secs. 7 and 8, monumented with a granite stone, 16 x 16 x 6 ins., firmly set 8 ins. in the ground, and plainly mkd. $\frac{1}{4}$ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W</p> <p style="text-align: center;">$\frac{1}{4}$ S 7 S 8 </p> <p style="text-align: center;">1978</p> <p>Bury the mkd. stone and set a steel fence post alongside the iron post.</p>

Subdivision of Section 3,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	<p>Subdivision of Section 3, T. 33 S., R. 5 W., Salt Lake Meridian, Utah</p>
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 3 and 10. N. $0^{\circ} 09'$ E., on the N and S center line of sec. 3. Over irrigated pasture land.</p>
20.11	<p>Point for the center south $\frac{1}{16}$ sec. cor. of sec. 3, not monumented.</p>
31.20	<p>Sevier River, drains NE.</p>
40.22	<p>Point for the center $\frac{1}{4}$ sec. cor. of sec. 3, at intersection with the E and W center line. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <p>T 33 S R 5 W</p> <p>$C\frac{1}{4}$ S 3</p> <p>1978</p> </div> <p>Cor. is located in N and S fence line.</p> </p>
60.23	<p>Point for the center north $\frac{1}{16}$ sec. cor. of sec. 3. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <p>T 33 S R 5 W</p> <p>C</p> <p>N $\frac{1}{16}$ S 3</p> <p>C</p> <p>1978</p> </div> </p>
70.89	<p>Intersect southeasterly right-of-way of U.S. Highway No. 89. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, for a reference monument to the witness point at the intersection with the center line of U.S. Highway No. 89, with brass cap mkd. <div style="text-align: center;"> <p>WP ↑ S 3</p> <p>369.5 FT RM</p> <p>1978</p> </div> <p>From this point, a highway right-of-way marker, bears N. $32^{\circ} 55' 30''$ E., 2.07 chs. dist., monumented with an iron post, projecting 6 ins. above ground with brass cap mkd. STATION 580+00.</p> </p>

Subdivision of Section 3,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS		
	<p>From this same point a highway right-of-way marker, bears S. 32° 55' 30" W., 8.07 chs. dist., monumented with an iron post, projecting 6 ins. above ground with brass cap mkd. STATION 573+26.</p>	
76.49	<p>The witness point at intersection with center line of U.S. Highway No. 89 and E. bdy. of original lot 3.</p>	
	<p>At the witness point</p>	
	<p>Drove spike, 6 ins. long, at intersection.</p>	
	<p>Continue over highway right-of-way.</p>	
81.14	<p>The ¼ sec. cor. of secs. 3 and 34, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., in a collar of stone, extending 5 ins. above ground, with brass cap mkd. as described in the official record of the 1964 resurvey of a portion of the S. bdy. of T. 32 S., R. 5 W.</p>	
	<p>From the ¼ sec. cor. of secs. 2 and 3.</p>	
	<p>S. 88° 50' W., on the E and W center line of sec. 3.</p>	
	<p>Over irrigated pasture land, draining W.</p>	
30.50	<p>Sevier River, about 2 ft. deep, 1.00 ch. wide, drains NE irregularly.</p>	
40.19	<p>The center ¼ sec. cor. of sec. 3.</p>	
60.395	<p>Point for the center west 1/16 sec. cor. of sec. 3 on highway right-of-way which bears N. 0° 14' E., and S. 0° 08' W., 0.245 chs. dist.</p>	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p>	
	<p>T 33 S R 5 W</p>	
	<p>W 1/16</p>	
	<p>C ————— C</p>	
	<p>S 3</p>	
	<p>1978</p>	
	<p>Thence across highway right-of-way.</p>	
63.89	<p>Center line U.S. Highway No. 89, bears N. 32° 55' 30" E. and S. 32° 55' 30" W.</p>	
67.555	<p>Highway right-of-way and fence, parallels highway.</p>	
80.60	<p>The ¼ sec. cor. of secs. 3 and 4.</p>	
	<p>From the west 1/16 sec. cor. of secs. 3 and 10.</p>	
	<p>N. 0° 08' E., on the N and S center line of the SW¼ of sec. 3.</p>	
	<p>Over pasture land.</p>	
2.60	<p>Sevier River, flows NW.</p>	

Subdivision of Section 3,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
8.50	Same river, flows NE.
12.70	Same river, flows NW.
20.095	Point for the SW 1/16 sec. cor. of sec. 3, at intersection with the E and W center line of the SW $\frac{1}{4}$ of sec. 3. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. T 33 S R 5 W SW 1/16 S 3 1978
21.60	Same river, flows NE.
39.945	Intersect highway right-of-way, bears S. 32° 55' 30" W. and N. 0° 08' E., thence along right-of-way.
40.19	The center west 1/16 sec. cor. of sec. 3.
	From the point for the center south 1/16 sec. cor. of sec. 3. S. 88° 52' W., along the E and W center line of the SW $\frac{1}{4}$ of sec. 3. Over pasture land.
7.00	Bend in Sevier River, flows N from NW.
20.195	The SW 1/16 sec. cor. of sec. 3.
21.50	Sevier River, flows NE.
30.24	Highway right-of-way, bears N. 20° 08' E. and S. 88° 52' W., thence along right-of-way.
32.27	Highway right-of-way, bears S. 20° 08' W. and N. 88° 52' E., thence over highway.
33.50	Center of U.S. Highway No. 89, bears N. 20° 08' E. and S. 20' 08' W.
34.71	Highway right-of-way, bears S. 20° 08' W. and S. 88° 52' W., thence along right-of-way.
36.74	Highway right-of-way, bears N. 20° 08' E. and N. 88° 52' E.
40.39	The S 1/16 sec. cor. of secs. 3 and 4.
	From the center west 1/16 sec. cor. of sec. 3. N. 0° 14' E., along the N and S center line of the NW $\frac{1}{4}$ of sec. 3. Over bench land covered with shadscale, along highway right-of-way.

Subdivision of Section 3,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
3.26	Highway right-of-way, bears N. 32° 55' 30" E. and S. 0° 14' W., thence over highway.
5.355	Center of U.S. Highway No. 89, bears N. 32° 55' 30" E. and S. 32° 55' 30" W.
7.47	Highway right-of-way, bears N. 32° 55' 30" E. and N. 0° 14' E., thence along right-of-way.
10.975	Highway right-of-way, bears S. 32° 55' 30" W. and S. 0° 14' W., thence over brushy bench, draining E.
19.975	<p>Point for the NW 1/16 sec. cor. of sec. 3, at intersection with the E and W center line of the NW¼ of sec. 3.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W</p> <p style="text-align: center;">NW 1/16 S 3</p> <p style="text-align: center;">1978</p> <p>Set a steel fence post alongside the iron post.</p>
20.60	Graded dirt road, bears N. 80° W. and S. 80° E.
40.97	The W 1/16 sec. cor. of secs. 3 and 34, on the N. bdy. of the Tp., previously described.
6.98	<p>From the center north 1/16 sec. cor. of sec. 3.</p> <p>S. 88° 45' W., on the E and W center line of the NW¼ of sec. 3.</p> <p>Over pasture land, through trees and corrals.</p> <p>Intersect highway right-of-way of U.S. Highway No. 89.</p> <p>From this point highway right-of-way marker station 573+26 bears N. 32° 55' 30" E., 4.82 chs. dist., previously described.</p> <p>Thence along right-of-way line.</p>
9.267	<p>Highway right-of-way line bears S. 32° 55' 30" W. and N. 88° 45' E.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, for a reference monument to the witness point at the intersection of the S. bdy. of lot 3, and the center line of U.S. Highway, No. 89, with brass cap mkd.</p> <p style="text-align: center;">S 3</p> <p style="text-align: center;">R M</p> <p style="text-align: center;">← 90.7 FT</p> <p style="text-align: center;">WP</p> <p style="text-align: center;">1978</p>

Subdivision of Section 3,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

From this point a highway right-of-way marker bears S. $32^{\circ} 55' 30''$ W., 20.32 chs. dist., monumented with an iron post projecting 6 ins. above ground with brass cap mkd. STATION 555+76.

From this same point a highway right-of-way marker bears S. $32^{\circ} 55' 40''$ W., 0.162 chs. dist., monumented with an iron post projecting 6 ins. above ground with brass cap mkd. STATION 569+17.

10.641 The witness point at intersection of center line of highway and S. bdy. of original lot 3.

Drove a spike, 6 ins. long, at witness point.

12.015 Highway right-of-way bears S. $32^{\circ} 55' 30''$ W. and S. $88^{\circ} 45'$ W.

Thence along right-of-way.

14.305 Highway right-of-way bears N. $32^{\circ} 55' 30''$ E. and N. $88^{\circ} 45'$ E.

19.00 Graded dirt road, bears N. 80° W. and S. 80° E.

20.18 The NW $1/16$ sec. cor. of sec. 3.

40.36 The N $1/16$ sec. cor. of secs. 3 and 4.

Subdivision of Section 9,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

From the $1/4$ sec. cor. of secs. 9 and 16.

N. $0^{\circ} 19'$ E., on the N and S center line of sec. 9.

Over bench land draining E; asc. over SE slope.

0.73 Fence, bears E and W.

20.025 Point for the center south $1/16$ sec. cor. of sec. 9.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 33 S R 5 W

C
|
S $1/16$ | S 9
|
C
1978

Set a steel fence post alongside the iron post.

40.05 Point for the center $1/4$ sec. cor. of sec. 9, at intersection with E and W center line.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

Subdivision of Section 9,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS		
	<p style="text-align: center;">T 33 S R 5 W C 1/4 S 9 1978</p> <p>Set a steel fence post alongside the iron post.</p>	
60.095	<p>Point for the center north 1/16 sec. cor. of sec. 9.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	
62.60	<p style="text-align: center;">T 33 S R 5 W C N 1/16 S 9 C 1978</p> <p>Set a steel fence post alongside the iron post.</p> <p>Bear Creek, small stream of water, flows S. 60° E.; thence over wide valley, through tall sagebrush.</p>	
80.14	<p>The ¼ sec. cor. of secs. 4 and 9.</p>	
13.82	<p>From the ¼ sec. cor. of secs. 9 and 10.</p> <p>N. 89° 43' W., on the E and W center line of sec. 9.</p> <p>Over brush pasture land; asc. over gentle E slope.</p> <p>Intersect highway right-of-way, also fence, bears N. 20° 08' E. and S. 20° 08' W.</p>	
15.035	<p>Center line of U.S. Highway No. 89, bears N. 20° 08' E. and S. 20° 08' W.</p>	
16.255	<p>Intersect highway right-of-way, also fence, bears N. 20° 08' E. and S. 20° 08' W.</p>	
40.23	<p>The center ¼ sec. cor. of sec. 9.</p>	
60.305	<p>Point for the center west 1/16 sec. cor. of sec. 9.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	
80.38	<p style="text-align: center;">T 33 S R 5 W W 1/16 C ————— C S 9 1978</p> <p>Set a steel fence post alongside the iron post.</p> <p>The ¼ sec. cor. of secs. 8 and 9.</p>	

Subdivision of Section 9,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	<p>From the W 1/16 sec. cor. of secs. 9 and 16.</p> <p>N. 0° 18' E., on the N and S center line of the SW$\frac{1}{4}$ of sec. 9.</p> <p>Over low hills; along E slope.</p>
0.45	Fence line, bears E and W.
20.04	<p>Point for the SW 1/16 sec. cor. of sec. 9, at intersection with the E and W center line of the SW$\frac{1}{4}$ of sec. 9.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W SW 1/16 S 9 1978</p> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located on top of low ridge, which bears N. 70° E. and S. 70° W.; desc. over N slope.</p>
40.08	The center west 1/16 sec. cor. of sec. 9.
	<p>From the center south 1/16 sec. cor. of sec. 9.</p> <p>N. 89° 46' W. on the E and W center line of the SW$\frac{1}{4}$ of sec. 9.</p> <p>Over low hills, covered with shadscale; asc. along S slope.</p>
20.065	<p>The SW 1/16 sec. cor. of sec. 9.</p> <p>Desc. along N slope of low ridge.</p>
40.13	The S 1/16 sec. cor. of sec. 8 and 9.
	<p>From the center west 1/16 sec. cor. of sec. 9.</p> <p>N. 0° 15' E. on the N and S center line of the NW$\frac{1}{4}$ of sec. 9.</p> <p>Over mountain bench land, covered with shadscale; along gentle E slope.</p>
20.05	<p>Point for the NW 1/16 sec. cor. of sec. 9, at intersection with the E and W center line of the NW$\frac{1}{4}$ of sec. 9.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W NW 1/16 S 9 1978</p>

496

Subdivision of Section 9,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	<p>Set a steel fence post alongside the iron post.</p> <p>Cor. is on top of long spur, which slopes E; desc. over N slope.</p>
33.00	Bear Creek, small stream of water, flows S. 60° E.; thence over valley, through tall sagebrush.
40.10	The W 1/16 sec. cor. of secs. 4 and 9.
	<p>From the center north 1/16 sec. cor. of sec. 9.</p> <p>N. 89° 43' W., on the E and W center line of the NW$\frac{1}{4}$ of sec. 9.</p> <p>Over low hills, covered with shadscale; asc. over NE slope.</p>
20.10	The NW 1/16 sec. cor. of sec. 9.
40.20	The N 1/16 sec. cor. of secs. 8 and 9.
	<p>Subdivision of Section 12, T. 33 S., R. 5 W., Salt Lake Meridian, Utah</p>
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 12 and 13.</p> <p>N. 0° 09' E., on the N and S center line of sec. 12.</p> <p>Over bench land draining W, covered with shadscale; along gentle W slope.</p>
40.17	<p>Point for the center $\frac{1}{4}$ sec. cor. of sec. 12, at intersection with the E and W center line.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W</p> <p style="text-align: center;">C 1/4 S 12</p> <p style="text-align: center;">1978</p>
81.24	<p>Set a steel fence post alongside the iron post.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 1 and 12.</p>
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp., previously described.</p> <p>S. 89° 00' W., on the E and W center line of sec. 12.</p> <p>Over bench land, covered with shadscale; desc. over gentle W slope, along E and W fence.</p>
13.60	Dirt road bears N. 52° W. and S. 52° E.
19.985	Point for the center east 1/16 sec. cor. of sec. 12.

Subdivision of Section 12,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W E 1/16</p> <p style="text-align: center;">C ————— C</p> <p style="text-align: center;">S 12 1978</p> <p>Cor. is located at fence corner, fences bear E and S.</p>
39.97	The center ¼ sec. cor. of sec. 12.
79.94	The ¼ sec. cor. of secs. 11 and 12.
	<p>From the E 1/16 sec. cor. of secs. 12 and 13.</p> <p>N. 0° 19' E. on the N and S center line of the SE¼ of sec. 12.</p> <p>Over bench land, covered with shadscale; along gentle W slope.</p>
16.00	Dirt road along old abandoned canal, bears NE and SW.
40.09	The center east 1/16 sec. cor. of sec. 12.
	<p>Subdivision of Section 13, T. 33 S., R. 5 W., Salt Lake Meridian, Utah</p>
	<p>From the ¼ sec. cor. of secs. 13 and 24.</p> <p>N. 0° 46' E., on the N and S center line of sec. 13.</p> <p>Over bench land, covered with shadscale; along gentle W slope.</p>
5.00	Dirt road, bears S. 83° E. and N. 83° W.
37.80	Graded gravel road, bears N. 83° 30' W. and S. 83° 30' E.
39.97	Fence cor., fences bear W and N; thence along fence.
40.18	Point for the center ¼ sec. cor. of sec. 13, at intersection with E and W center line.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W</p> <p style="text-align: center;">C 1/4 S 13</p> <p style="text-align: center;">1978</p> <p>Continue along fence line.</p>
60.00	Dirt road, bears SW and N.
80.67	The ¼ sec. cor. of secs. 12 and 13.

Subdivision of Section 13,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp., previously described.</p>
	<p>S. $89^{\circ} 09'$ W., on the E and W center line of sec. 13.</p>
	<p>Over bench land, covered with shadscale; desc. over gentle W slope.</p>
40.02	<p>The center $\frac{1}{4}$ sec. cor. of sec. 13.</p>
55.50	<p>Dirt road, bears N. 15° E. and S. 15° W.</p>
60.125	<p>Point for the center west $1/16$ sec. cor. of sec. 13.</p>
	<p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 33 S R 5 W W 1/16 C ————— C S 13 1978</p>
	<p>Cor. on fence line, which bears S and N. 8 lks, thence E.</p>
80.23	<p>The $\frac{1}{4}$ sec. cor. of secs. 13 and 14.</p>
	<p>From the W $1/16$ sec. cor. of secs. 13 and 24.</p>
	<p>N. $0^{\circ} 51'$ E. on the N and S center line of the SW$\frac{1}{4}$ of sec. 13.</p>
	<p>Over bench land draining W; along N and S fence line.</p>
8.50	<p>Dirt road, bears N. 83° W. and S. 83° E.</p>
19.00	<p>Dirt road, bears N. 15° E. and S. 15° W.</p>
39.40	<p>Graded gravel road, bears E and W.</p>
40.13	<p>The center west $1/16$ sec. cor. of sec. 13.</p>
<p>Subdivision of Section 21, T. 33 S., R. 5 W., Salt Lake Meridian, Utah</p>	
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 21 and 28.</p>
	<p>N. $0^{\circ} 24'$ E. on the N and S center line of sec. 21.</p>
	<p>Over bench land.</p>
20.10	<p>Point for the center south $1/16$ sec. cor. of sec. 21, not monumented.</p>
24.50	<p>Sevier River, flows NW.</p>
40.20	<p>Point for the center $\frac{1}{4}$ sec. cor. of sec. 21, at intersection with E and W center line.</p>

Subdivision of Section 21,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W C 1/14 S 21 1978</p> <p>Set a steel fence post alongside the iron post.</p> <p>66.20 Sevier River, flows E.</p> <p>80.35 The ¼ sec. cor. of secs. 16 and 21.</p>
	<p>From the ¼ sec. cor. of secs. 21 and 22.</p> <p>N. 89° 38' W. on the E and W center line of sec. 21.</p> <p>Over grass pasture land.</p> <p>40.30 The center ¼ sec. cor. of sec. 21.</p> <p>47.50 Sevier River, flows N.</p> <p>57.91 Intersect highway right-of-way, also fence, bears N. 4° 20' E. and S. 4° 20' W.</p> <p>59.15 U.S. Highway No. 89, bears N. 4° 20' E. and S. 4° 20' W.</p> <p>60.39 Intersect right-of-way, also fence, bears N. 4° 20' E. and S. 4° 20' W.</p> <p>60.44 Point for the center west 1/16 sec. cor. of sec. 21.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W W 1/16 C ————— C S 21 1978</p> <p>Set a steel fence post alongside the iron post.</p> <p>77.50 Graded dirt road, bears N. 28° W. and S. 28° E.</p> <p>80.58 The ¼ sec. cor. of secs. 20 and 21.</p>
	<p>From the point for the W 1/16 sec. cor. of secs. 21 and 28.</p> <p>N. 0° 27' E. on the N and S center line of the SW¼ of sec. 21.</p> <p>Over U.S. Highway No. 89.</p>

Subdivision of Section 21,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
20.095	<p>Point for the SW 1/16 sec. cor. of sec. 21, at intersection with the E and W center line of the SW$\frac{1}{4}$ of sec. 21, falls on hard surface of highway.</p> <p>Drove small nail at corner point</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 58° 22' E., 94 lks. dist., with brass cap mkd. RM T33S R5W SW1/16 S21 62 FT 1978 and an arrow pointing to the corner point.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 73° 07' E., 83.3 lks. dist., with brass cap mkd. RM T33S R5W SW1/16 S21 55 FT 1978 an and arrow pointing to the corner point.</p> <p>Continue over highway.</p>
39.54	Intersect westerly highway right-of-way and fence bears N. 4° 20' E. and S. 4° 20' W.
40.19	The center west 1/16 sec. cor. of sec. 21.
	<p>From the point for the center south 1/16 sec. cor. of sec. 21.</p> <p>N. 89° 38' W. on the E and W center line of the SW 1/4 of sec. 21.</p> <p>Over grass pasture land.</p>
18.94	Intersect highway right-of-way, and fence, bears N and S.
20.155	The SW 1/16 sec. cor. of sec. 21.
20.26	Center of U.S. Highway No. 89, bears N and S.
21.40	Highway right-of-way and fence, bears N and S; thence along E and W fence line.
40.31	The S 1/16 sec. cor. of secs. 20 and 21.
	<p>From the center west 1/16 sec. cor. of sec. 21.</p> <p>N. 0° 25' E. on the N and S center line of the NW$\frac{1}{4}$ of sec. 21.</p> <p>Over brush covered bench land; along gentle E slope.</p>
40.13	The W 1/16 sec. cor. of secs. 16 and 21.
	<p style="text-align: center;">Subdivision of Section 23, T. 33 S., R. 5 W., Salt Lake Meridian, Utah</p>

Subdivision of Section 23,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

- From the $\frac{1}{4}$ sec. cor. of secs. 23 and 26.
N. $0^{\circ} 35'$ E. on the N and S center line of sec. 23.
Over high bench land covered with shadscale.
- 20.13 Point for the center south $\frac{1}{16}$ sec. cor. of sec. 23.
Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
- T 33 S R 5 W
- C
|
S 1/16 | S 23
|
C
1978
- Set a steel fence post alongside the iron post.
- 40.26 Point for the center $\frac{1}{4}$ sec. cor. of sec. 23, at intersection with the E and W center line.
Set an aluminum post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with cap mkd.
- T 33 S R 5 W
- C 1/4 | S 23
- 1978
- Set a steel fence post alongside the aluminum post.
Cor. is located on top of rim, which bears NW and SE; thence over top of bench.
- 60.36 Point for the center north $\frac{1}{16}$ sec. cor. of sec. 23.
Set an aluminum post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with cap mkd.
- T 33 S R 5 W
- C
|
N 1/16 | S 23
|
C
1978
- Set a steel fence post alongside the aluminum post.
- 80.46 The $\frac{1}{4}$ sec. cor. of secs. 14 and 23.
-
- From the $\frac{1}{4}$ sec. cor. of secs. 23 and 24.
S. $89^{\circ} 28'$ W. on the E and W center line of sec. 23.
Over bench land; desc. over gentle W slope.
- 40.27 The center $\frac{1}{4}$ sec. cor. of sec. 23.
- 60.41 Point for the center west $\frac{1}{16}$ sec. cor. of sec. 23.

Subdivision of Section 23,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS		
80.55	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W W 1/16</p> <p style="text-align: center;">C ————— C S 23 1978</p> <p>Set a steel fence post alongside the iron post.</p> <p>The ¼ sec. cor. of secs. 22 and 23.</p>	
40.28	<p>From the N 1/16 sec. cor. of secs. 23 and 24.</p> <p>S. 89° 27' W., on the E and W center line of the NE¼ of sec. 23.</p> <p>Desc. over gentle W slope.</p> <p>The center north 1/16 sec. cor. of sec. 23.</p>	
40.27	<p>From the S 1/16 sec. cor. of secs. 23 and 24.</p> <p>S. 89° 25' W., on the E and W center line of the SE¼ of sec. 23.</p> <p>The center south 1/16 sec. cor. of sec. 23.</p>	
20.105	<p>From the W 1/16 sec. cor. of secs. 23 and 26.</p> <p>N. 0° 34' E. on the N and S center line of the SW¼ of sec. 23.</p> <p>Over top of bench; along gentle W slope.</p> <p>Point for the SW 1/16 sec. cor. of sec. 23, at intersection with the E and W center line of the SW¼ of sec. 23.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W SW 1/16 S 23 1978</p>	
40.21	<p>Set a steel fence post alongside the iron post.</p> <p>The center west 1/16 sec. cor. of sec. 23.</p>	
	<p>From the center south 1/16 sec. cor. of sec. 23.</p> <p>S. 89° 32' W. on the E and W center line of the SW¼ of sec. 23.</p>	

Subdivision of Section 23,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	<p>Along N slope of terrace, over series of small spurs and draws draining N.</p>
20.14	The SW 1/16 sec. cor. of sec. 23.
40.28	The S 1/16 sec. cor. of secs. 22 and 23.
<p>Subdivision of Section 24, T. 33 S., R. 5 W., Salt Lake Meridian, Utah</p>	
	<p>From the 1/4 sec. cor. of secs. 24 and 25.</p> <p>N. 0° 31' E. on the N and S center line of sec. 24.</p> <p>Over rolling land draining W.</p>
3.60	Trail road, bears NE and SW.
40.26	<p>Point for the center 1/4 sec. cor. of sec. 24, at intersection with E and W center line.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W</p> <p style="text-align: center;">C 1/4 S 24</p> <p style="text-align: center;">1978</p>
	<p>Set a steel fence post alongside the iron post.</p>
60.435	<p>Point for the center north 1/16 sec. cor. of sec. 24.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W</p> <p style="text-align: center;">C</p> <p style="text-align: center;">N 1/16 S 24</p> <p style="text-align: center;">C</p> <p style="text-align: center;">1978</p>
	<p>Set a steel fence post alongside the iron post.</p>
66.00	Sanford Creek, drains W.
80.61	The 1/4 sec. cor. of secs. 13 and 24.
	<p>From the 1/4 sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp., previously described.</p> <p>S. 89° 31' W. on the E and W center line of sec. 24.</p> <p>Over rolling land draining W.</p>
40.30	The center 1/4 sec. cor. of sec. 24.

Subdivision of Section 24,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS		
60.49	<p>Point for the center west 1/16 sec. cor. of sec. 24.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W W 1/16</p> <p style="text-align: center;">C ————— C</p> <p style="text-align: center;">S 24 1978</p> <p>Set a steel fence post alongside the iron post.</p>	
61.20	Trail road, bears N and S.	
80.68	The ¼ sec. cor. of secs. 23 and 24.	
40.23	<p>From the W 1/16 sec. cor. of secs. 24 and 25.</p> <p>N. 0° 33' E. on the N and S center line of the SW¼ of sec. 24.</p> <p>Over rolling land draining W.</p> <p>The center west 1/16 sec. cor. of sec. 24.</p>	
20.14	<p>N. 0° 33' E. on the N and S center line of the NW¼ of sec. 24.</p> <p>Over rolling land draining W.</p> <p>Point for the NW 1/16 sec. cor. of sec. 24, at intersection with the E and W center line of the NW¼ of sec. 24.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W NW 1/16 S 24 1978</p> <p>Set a steel fence post alongside the iron post.</p>	
28.00	Sanford Creek, drains W.	
40.28	The W 1/16 sec. cor. of secs. 13 and 24.	
20.18	<p>From the center north 1/16 sec. cor. of sec. 24.</p> <p>S. 89° 25' W., on the E and W center line of the NW¼ of sec. 24.</p> <p>Over rolling land draining W.</p> <p>The NW 1/16 sec. cor. of sec. 24.</p>	
24.00	Trail road, bears N and S.	

Subdivision of Section 24,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
40.36	The N 1/16 sec. cor. of secs. 23 and 24.
Subdivision of Section 25, T. 33 S., R. 5 W., Salt Lake Meridian, Utah	
	From the 1/4 sec. cor. of secs. 25 and 36. N. 0° 33' E., on the N and S center line of sec. 25. Over rolling land, draining W.
26.20	Dirt road, bears NE and SW.
40.30	Point for the center 1/4 sec. cor. of sec. 25, at inter- section with the E and W center line. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 33 S R 5 W C 1/4 S 25 1978 </div> Set a steel fence post alongside the iron post.
60.45	Point for the center north 1/16 sec. cor. of sec. 25. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 33 S R 5 W C N 1/16 S 25 C 1978 </div> Set a steel fence post alongside the iron post. A fence corner bears N. 25° 40' W., 60 lks. dist., fences bear N and W.
80.60	The 1/4 sec. cor. of secs. 24 and 25.
	From the 1/4 sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp., previously described. S. 89° 41' W., along the E and W center line of sec. 25. Over rolling land, draining W.
20.315	Point for the center east 1/16 sec. cor. of sec. 25. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Subdivision of Section 25,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS		
	<p style="text-align: center;">T 33 S R 5 W E 1/16 C ————— C S 25 1978</p> <p>Set a steel fence post alongside the iron post.</p> <p>A fence corner, bears N. 29° 10' W., 60 lks. dist., fences bear E, W, and N.</p> <p>27.00 Dirt road, bears NE and SW.</p> <p>40.63 The center ¼ sec. cor. of sec. 25.</p> <p>60.73 Fence bears N and S.</p> <p>60.80 Point for the center west 1/16 sec. cor. of sec. 25.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T 33 S R 5 W W 1/16 C ————— C S 25 1978</p> <p>Set a steel fence post alongside the iron post.</p> <p>80.97 The ¼ sec. cor. of secs. 25 and 26.</p>	
	<p>From the center east 1/16 sec. cor. of sec. 25.</p> <p>N. 0° 26' E., on the N and S center line of the NE¼ of sec. 25.</p> <p>0.52 Fence, bears E and W.</p> <p>7.50 Trail road on top of rise, bears NE and SW.</p> <p>40.32 The E 1/16 sec. cor. of secs. 24 and 25.</p>	
	<p>From the W 1/16 sec. cor. of secs. 25 and 36.</p> <p>N. 0° 28' E., on the N and S center line of the SW¼ of sec. 25.</p> <p>Over rolling land, draining W, along N and S fence.</p> <p>12.70 Graded dirt road, bears N. 85° E. and S. 85° W.</p> <p>40.27 The center west 1/16 sec. cor. of sec. 25.</p>	
	<p>N. 0° 28' E., on the N and S center line of the NW¼ of sec. 25.</p> <p>Over rolling land, draining W, along N and S fence.</p>	

Subdivision of Section 25,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
20.145	<p>Point for the NW 1/16 sec. cor. of sec. 25, at intersection with the E and W center line of the NW$\frac{1}{4}$ of sec. 25.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W</p> <p style="text-align: center;">NW 1/16 S 25</p> <p style="text-align: center;">1978</p> <p>Cor. is located in N - S fence line.</p>
20.96	Corner of fences, bearing E and S.
22.60	Trail road, bears NE and SW.
40.29	The W 1/16 sec. cor. of secs. 24 and 25.
	<p>From the center north 1/16 sec. cor. of sec. 25.</p> <p>S. 89° 39' W., on the E and W center line of the NW$\frac{1}{4}$ of sec. 25.</p> <p>Over rolling land, draining W, along S side of E and W fence line.</p>
20.195	The NW 1/16 sec. cor. of sec. 25.
23.50	Trail road, bears NE and SW.
40.39	The N 1/16 sec. cor. of secs. 25 and 26.
	<p>Subdivision of Section 26, T. 33 S., R. 5 W., Salt Lake Meridian, Utah</p>
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 26 and 35.</p> <p>N. 0° 25' E. on the N and S center line of sec. 26.</p> <p>Over bench land, draining W.</p>
20.12	<p>Point for the center south 1/16 sec. cor. of sec. 26.</p> <p>Set an aluminum post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W</p> <p style="text-align: center;">C</p> <p style="text-align: center;">S 1/16 S 26</p> <p style="text-align: center;">C</p> <p style="text-align: center;">1978</p> <p>Set a steel fence post alongside the aluminum post.</p>

Subdivision of Section 26,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS		
40.24	<p>Point for the center $\frac{1}{4}$ sec. cor. of sec. 26, at intersection with the E and W center line.</p> <p>Set an aluminum post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W C 1/4 S 26 1978</p>	
60.29	<p>Set a steel fence post alongside the aluminum post.</p> <p>Point for the center north $\frac{1}{16}$ sec. cor. of sec. 26.</p> <p>Set an aluminum post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W C N 1/16 S 26 C 1978</p>	
80.34	<p>Set a steel fence post alongside the aluminum post.</p> <p>Desc. over N slope into small ravine.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 23 and 26.</p>	
5.50 20.145	<p>From the $\frac{1}{4}$ sec. cor. of secs. 25 and 26.</p> <p>S. $89^{\circ} 37'$ W., on the E and W center line of sec. 26.</p> <p>Over broken bench land, draining W.</p> <p>Trail road, bears NE and SW.</p> <p>Point for the center east $\frac{1}{16}$ sec. cor. of sec. 26.</p> <p>Set an aluminum post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W E 1/16 C ————— C S 26 1978</p>	
40.29	<p>Set a steel fence post alongside the aluminum post.</p> <p>The center $\frac{1}{4}$ sec. cor. of sec. 26.</p>	
60.42	<p>Point for the center west $\frac{1}{16}$ sec. cor. of sec. 26.</p> <p>Set an aluminum post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with cap mkd.</p>	

Subdivision of Section 26,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	<p style="text-align: center;">T 33 S R 5 W W 1/16</p> <p style="text-align: center;">C ————— C</p> <p style="text-align: center;">S 26 1978</p> <p>Set a steel fence post alongside the aluminum post.</p> <p>80.55 The $\frac{1}{4}$ sec. cor. of secs. 26 and 27.</p>
	<p>From the center east 1/16 sec. cor. of sec. 26.</p> <p>N. $0^{\circ} 24'$ E., on the N and S center line of the NE$\frac{1}{4}$ of sec. 26.</p> <p>Over bench land covered with shadscale, draining W.</p> <p>20.09 Point for the NE 1/16 sec. cor. of sec. 26, at intersection with the E and W center line of the NE$\frac{1}{4}$ of sec. 26.</p> <p>Set an aluminum post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W NE 1/16 S 26 1978</p> <p>Set a steel fence post alongside the aluminum post.</p> <p>40.18 The E 1/16 sec. cor. of secs. 23 and 26.</p>
	<p>From the N 1/16 sec. cor. of secs. 25 and 26.</p> <p>S. $89^{\circ} 30'$ W. on the E and W center line of the NE$\frac{1}{4}$ of sec. 26.</p> <p>Over bench land, draining W.</p> <p>20.14 The NE 1/16 sec. cor. of sec. 26.</p> <p>40.28 The center north 1/16 sec. cor. of sec. 26.</p>
	<p>From the E 1/16 sec. cor. of secs. 26 and 35.</p> <p>N. $0^{\circ} 24'$ E., on the N and S center line of the SE$\frac{1}{4}$ of sec. 26.</p> <p>Over bench land, draining W.</p> <p>5.60 Trail road, bears N. 70° E. and S. 70° W.</p> <p>18.40 Trail road, bear NE and SW.</p> <p>20.115 Point for the SE 1/16 sec. cor. of sec. 26, at intersection with the E and W center line of the SE$\frac{1}{4}$ of sec. 26.</p>

Subdivision of Section 26,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS		
40.23	<p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W SE 1/16 S 26 1978</p> <p>Set a steel fence post alongside the corner.</p> <p>The center east 1/16 sec. cor. of sec. 26.</p>	
19.30 20.15 40.30	<p>From the S 1/16 sec. cor. of secs. 25 and 26.</p> <p>S. 89° 36' W., on the E and W center line of the SE¼ of sec. 26.</p> <p>Over bench land, draining W.</p> <p>Trail road, bears NE and SW.</p> <p>The SE 1/16 sec. cor. of sec. 26.</p> <p>The center south 1/16 sec. cor. of sec. 26.</p>	
20.05 40.10	<p>From the center west 1/16 sec. cor. of sec. 26.</p> <p>N. 0° 25' E., on the N and S center line of the NW¼ of sec. 26.</p> <p>Over bench land, draining W.</p> <p>Point for the NW 1/16 sec. cor. of sec. 26, at intersection with the E and W center line of the NW¼ of sec. 26.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W NW 1/16 S 26 1978</p> <p>Set a steel fence post alongside the aluminum post.</p> <p>The W 1/16 sec. cor. of secs. 23 and 26.</p>	
20.13 40.26	<p>From the center north 1/16 sec. cor. of sec. 26.</p> <p>S. 89° 37' W., on the E and W center line of the NW¼ of sec. 26.</p> <p>Over bench land; desc. over NW slope.</p> <p>The NW 1/16 sec. cor. of sec. 26.</p> <p>The N 1/16 sec. cor. of secs. 26 and 27.</p>	

Subdivision of Section 29,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

Subdivision of Section 29,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

From the $\frac{1}{4}$ sec. cor. of secs. 29 and 32.

N. $0^{\circ} 12'$ W., on the N and S center line of sec. 29.

Over brush covered pasture land draining E; along
N and S fence line.

19.905 Point for the center south $\frac{1}{16}$ sec. cor. of sec. 29.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 33 S R 5 W

```

      C
      |
S 1/16 | S 29
      |
      C
      |
    1978
  
```

Set a steel fence post alongside the iron post.

19.92 Fence, bears W and E, 15 lks. thence N and S.

39.81 Point for the center $\frac{1}{4}$ sec. cor. of sec. 29, at inter-
section with the E and W center line.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., flush
with surface of field road, with brass cap mkd.

T 33 S R 5 W

C $\frac{1}{4}$ S 29

1978

from which

A fence corner post, bears N. 20° E., 20 lks. dist.

A gate post, bears S. 10° E., 15 lks. dist.

59.875 Point for the center north $\frac{1}{16}$ sec. cor. of sec. 29.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 33 S R 5 W

```

      C
      |
N 1/16 | S 29
      |
      C
      |
    1978
  
```

Set a steel fence post alongside the iron post.

60.14 Fence line, bears E and W.

Subdivision of Section 29,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
79.94	The $\frac{1}{4}$ sec. cor. of secs. 20 and 29.
20.105	<p>From the $\frac{1}{4}$ sec. cor. of secs. 28 and 29.</p> <p>S. $89^{\circ} 33'$ W., on the E and W center line of sec. 29.</p> <p>Over brush and grass pasture land; along E and W fence line and farm road.</p> <p>Point for the center east $\frac{1}{16}$ sec. cor. of sec. 29, not monumented.</p>
40.21	The center $\frac{1}{4}$ sec. cor. of sec. 29.
60.58	<p>Point for the center west $\frac{1}{16}$ sec. cor. of sec. 29.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W W $\frac{1}{16}$</p> <p style="text-align: center;">C ————— C</p> <p style="text-align: center;">S 29 1978</p> <p>Set a steel fence post alongside the iron post.</p>
80.95	The $\frac{1}{4}$ sec. cor. of secs. 29 and 30.
20.075	<p>From the point for the center east $\frac{1}{16}$ sec. cor. of sec. 29.</p> <p>N. $0^{\circ} 14'$ W., on the N and S center line of the $NE\frac{1}{4}$ of sec. 29.</p> <p>Over brush pasture land.</p> <p>Point for the NE $\frac{1}{16}$ sec. cor. of sec. 29, at intersection with the E and W center line of the $NE\frac{1}{4}$ of sec. 29.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W NE $\frac{1}{16}$ S 29 1978</p> <p>Set a steel fence post alongside the iron post.</p>
20.21	Fence, bears E and W, 18 lks. dist., thence N and W.
40.15	The E $\frac{1}{16}$ sec. cor. of secs. 20 and 29.
	<p>From the point for the N $\frac{1}{16}$ sec. cor. of secs. 28 and 29.</p> <p>S. $89^{\circ} 30'$ W. on the E and W center line of the $NE\frac{1}{4}$ of sec. 29.</p>

Subdivision of Section 29,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	Over brush pasture land, along E and W fence line and field road.
20.095	The NE 1/16 sec. cor. of sec. 29.
40.19	The center north 1/16 sec. cor. of sec. 29.
	From the W 1/16 sec. cor. of secs. 29 and 32.
	N. 0° 10' E., on the N and S center line of the SW $\frac{1}{4}$ of sec. 29.
	Over brush covered bench land.
0.28	Fence, bears E and W.
19.975	Point for the SW 1/16 sec. cor. of sec. 29, at intersection with the E and W center line of the SW $\frac{1}{4}$ of sec. 29.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 33 S R 5 W
	SW 1/16 S 29
	1978
	Set a steel fence post alongside the iron post.
39.95	The center west 1/16 sec. cor. of sec. 29.
	From the center south 1/16 sec. cor. of sec. 29.
	S. 89° 21' W., on the E and W center line of the SW $\frac{1}{4}$ of sec. 29.
	Over brush pasture land; asc. over E slope.
20.50	The SW 1/16 sec. cor. of sec. 29.
41.00	The S 1/16 sec. cor. of secs. 29 and 30.
	From the center north 1/16 sec. cor. of sec. 29.
	S. 89° 31' W., on the E and W center line of the NW $\frac{1}{4}$ of sec. 29.
	Over brush covered pasture land.
40.14	Fence, bears N and S.
40.28	Graded dirt road, bears N and S.
40.49	The N 1/16 sec. cor. of secs. 29 and 30.

Subdivision of Section 35,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	<p>Subdivision of Section 35, T. 33 S., R. 5 W., Salt Lake Meridian, Utah</p>
40.15	<p>From the $\frac{1}{4}$ sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp., previously described.</p> <p>N. $0^{\circ} 18'$ E., on the N and S center line of sec. 35.</p> <p>Over rolling bench covered with shadscale, draining W.</p> <p>Point for the center $\frac{1}{4}$ sec. cor. of sec. 35, at intersection with the E and W center line.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W C 1/4 S 35 1978</p> <p>Cor. is located in E and W fence line.</p>
77.10	Dirt road, bears NE and SW.
80.39	The $\frac{1}{4}$ sec. cor. of secs. 26 and 35.
20.125	<p>From the $\frac{1}{4}$ sec. cor. of secs. 35 and 36.</p> <p>S. $89^{\circ} 37'$ W., on the E and W center line of sec. 35.</p> <p>Over rolling bench land, draining W.</p> <p>Point for the center east $\frac{1}{16}$ sec. cor. of sec. 35.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W E 1/16 C ————— C S 35 1978</p> <p>Cor. at fence corner, fences bear N, S, and W.</p>
40.25	The center $\frac{1}{4}$ sec. cor. of sec. 35.
80.49	The $\frac{1}{4}$ sec. cor. of secs. 34 and 35.
	<p>From the center east $\frac{1}{16}$ sec. cor. of sec. 35.</p> <p>N. $0^{\circ} 21'$ E., on the N and S center line of the NE$\frac{1}{4}$ of sec. 35.</p> <p>Over rolling bench land, draining W.</p>

Subdivision of Section 35,
T. 33 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
40.25	The E 1/16 sec. cor. of secs. 26 and 35.
	<p>From the E 1/16 sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp., previously described.</p> <p>N. 0° 20' E., on the N and S center line of the SE$\frac{1}{4}$ of sec. 35.</p> <p>Over rolling bench land, draining W.</p>
40.17	The center east 1/16 sec. cor. of sec. 35.
	<p style="text-align: center;">General Description</p> <p>Township 33 South, Range 5 West is located about 5 miles north of Panguitch, Utah. The township consists mainly of bench ground with a few farms on the E and W portions. The central portions, along the Sevier River is mainly grass pasture bottom land. There are several large reseeded areas on the east bench. The Sevier River enters the township on the south boundary of sec. 33, flows northward and leaves the township on the north boundary of sec. 3.</p> <p>U.S. Highway No. 89, enters the township on the south boundary of sec. 32, bears NE and leaves the township on the North boundary of sec. 3. There are numerous other farm roads within the township.</p> <p>The only habitation noted were homes in secs. 16 and 21, and a service station, store and home at Bear Valley Junction located in sec. 3.</p> <p>The elevation varies from about 6450 to 7200 ft. above sea level.</p>

CERTIFICATE OF SURVEY

(We), Craig P. Sylvester and Gail E. Reynolds, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 20th day of April 1978, (We) have dependently resurveyed the east boundary, portions of the north, south and west boundaries and subdivisional lines, and surveyed the subdivision of secs. 3, 9, 12, 13, 21, 23, 24, 25, 26, 29, and 35, T. 33 S., R. 5 W.,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (us) and under (our) direction, and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

October 9, 1979

(Date)

Craig P. Sylvester
(Cadastral Surveyor)
Supervisory

October 9, 1979

(Date)

Gail E. Reynolds
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Washington, D.C.
Denver, Colorado

The foregoing field notes of the dependent resurvey of the east boundary, portions of the north, south and west boundaries and subdivisional lines, and surveyed the subdivision of secs. 3, 9, 12, 13, 21, 23, 24, 25, 26, 29, and 35, T. 33 S., R. 5 W., Salt Lake Meridian, Utah

executed by Craig P. Sylvester and Gail E. Reynolds, Cadastral Surveyors having been critically examined and found correct, are hereby approved.

DEC 14 1979

(Date)

Ray S. Spitz
ACTING Chief, Cadastral Survey Examination and Approval Staff

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

R599

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
ORIGINAL

FIELD NOTES

OF THE
DEPENDENT RESURVEY OF
A PORTION OF THE SUBDIVISIONAL LINES,
AND
THE SURVEY OF A PORTION OF
THE SUBDIVISION OF SECTION 26,
TOWNSHIP 43 SOUTH, RANGE 5 WEST

Of the Salt Lake Meridian,
In the State of Utah

EXECUTED BY

Craig P. Sylvester Supervisory Cadastral Surveyor

Under special instructions dated October 3, 1977, approved October 4, 1977,

_____, which provided for the surveys included under U.S. Survey/Group
Number 575, and assignment instructions dated October 4, 1977.

Survey commenced October 11, 1977

Survey completed October 13, 1977

INDEX DIAGRAM

Township 43 South, Range 5 West

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23 4	24
30	29	28	27	26 2 1	25
31	32	33	34	35	36

Subdivision of Section 26

Page 4-6

Township 43 South, Range 5 West, Salt Lake Meridian, Utah

CHAINS

The boundaries of section 26 were surveyed by T. C. Bailey and J. G. Burrill in 1877. The west boundary and west half mile of the north boundary were dependently resurveyed by Andrew Nelson in 1937.

The following field notes are those of a dependent resurvey of a portion of the subdivisional lines, and the survey of a portion of the subdivision of section 26, Township 43 South, Range 5 West, Salt Lake Meridian, Utah.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group 575, Utah, dated October 3, 1977.

The directions of the lines of this survey were determined by reference to true meridians established on line by hour angle observations on Polaris. They were carried forward by sustained angulation, being supplemented by numerous other observations on Polaris taken throughout the progress of the survey.

Measurements were determined by electronic means along survey lines, where accessible. Distances to topography on lines inaccessible due to rough terrain, timber and private property are approximately as scaled from U.S.G.S. topographic sheets.

The geographic position of the southeast corner of section 26, as scaled from U.S. Geological Survey quadrangle Map Johnson SW, Utah-Arizona, prepared in 1954, is as follows:

Latitude 37° 02.2' N. Longitude 112° 22.5' W.

The magnetic declination was read at a number of stations and the average of the several readings was found to be 15° 30' E.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 43 S., R. 5 W., Salt Lake Meridian, Utah

(Restoring the 1877 survey by T. C. Bailey and J. G. Burrill)

Beginning at the cor. of secs. 25, 26, 35, and 36, determined by intersection of fence lines extended from N, S, E, and W. This point falls on hard surface of Highway No. 136 and cannot be monumented.

At the corner point

Drive a spike, 6 ins. long, flush with road surface, from which

An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 30° 45' E., 97 lks. dist., with brass cap mkd. RM T43S R5W S36 64.2 FT 1977 and an arrow pointing to the cor.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 43 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	<p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 13° 29' W., 101 lks. dist., with brass cap mkd. RM T43S R5W S35 66.6 FT 1977 and an arrow pointing to the cor.</p>
	<p>N. 89° 59' W., bet. secs. 26 and 35.</p>
	<p>Over rolling valley land, across Highway No. 136.</p>
0.56	<p>Center line of Highway No. 136, bears N. 75° 10' E. and S. 75° 10' W.</p>
11.33	<p>Fence cor., fences bear N. 75° 10' E. and S. 75° 10' W. and west, thence along fence line.</p>
19.715	<p>Point for the E 1/16 sec. cor. of secs. 26 and 35, not monumented.</p>
39.43	<p>The ¼ sec. cor. of secs. 26 and 35, monumented with a sandstone, 14 x 12 x 4 ins., firmly set and dimly mkd. ¼; also old survey lath and stakes around cor.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p>T 43 S R 5 W</p>
	<p>¼ $\frac{S\ 26}{S\ 35}$</p>
	<p>1977</p>
	<p>Bury mkd. stone alongside the iron post.</p>
	<p>Cor. is located in E and W fence line.</p>
	<p>N. 89° 38' W., beginning new measurement.</p>
	<p>Asc. gentle SE slope, along E and W fence line.</p>
39.81	<p>The cor. of secs. 26, 27, 34, and 35, monumented with an iron post, 2 ins. diam., extending 10 ins. above ground, with brass cap mkd. as described in the dependent resurvey of a portion of the subdivisional lines of T. 43 S., R. 5 W., in 1937.</p>
	<p>From the cor. of secs. 25, 26, 35, and 36.</p>
	<p>N. 0° 35' E., bet. secs. 25 and 26.</p>
	<p>Over rolling valley land, across Highway No. 136.</p>
0.11	<p>Center line of Highway No. 136, bears N. 75° 10' E. and S. 75° 10' W.</p>
2.42	<p>Fence corner, fences bear N. 75° 10' E., S. 75° 10' W., and N; thence along fence line.</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 43 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS

19.95 Point for the S 1/16 sec. cor. of secs. 25 and 26, not monumented.

39.90 The 1/4 sec. cor. of secs. 25 and 26, monumented with a sandstone, 14 x 10 x 4 ins., in fence cor., marks have weathered away.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 43 S R 5 W

1/4
|
S 26 | S 25
|

1977

Bury mkd. stone alongside the iron post.

Cor. is located at fence corner., fences bear N, S, and E.

N. 0° 23' E., beginning new measurement.

Asc. gentle N slope, along N and S fence line.

19.99 Point for the N 1/16 sec. cor. of secs. 25 and 26.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 43 S R 5 W

N 1/16
|
S 26 | S 25
|

1977

Cor. is located in N and S fence line.

39.98 The cor. of secs. 23, 24, 25, and 26, monumented with a sandstone, 16 x 10 x 6 ins., firmly set and mkd. 1 notch on E and 2 notches on S edges.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 43 S R 5 W

S 23 | S 24
S 26 | S 25

1977

Bury mkd. stone alongside the iron post.

Cor. is located at fence cor., fences bear E and S.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 43 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
19.945	<p>N. 89° 42' W., bet. secs. 23 and 26.</p> <p>Over rolling valley land, covered with brush; asc. over gentle SE. slope.</p> <p>Point for the E 1/16 sec. cor. of secs. 23 and 26.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 43 S R 5 W</p> <p style="text-align: center;">E 1/16 $\frac{S\ 23}{S\ 26}$</p> <p style="text-align: center;">1977</p> <p>Set cedar post, 6 ins. diam., 4 ft. high, alongside cor.</p>
29.00	<p>Enter juniper and pinon, soil changes to rocky gravel.</p>
39.89	<p>The ¼ sec. cor. of secs. 23 and 26, monumented with an iron post, 1 in. diam., extending 10 ins. above ground, with brass cap mkd. as described in the dependent resurvey of a portion of the subdivisional lines of T. 43 S., R. 5 W., in 1937.</p>
<p>Subdivision of Section 26, T. 43 S., R. 5 W., Salt Lake Meridian, Utah</p>	
19.985	<p>From the ¼ sec. cor. of secs. 26 and 35.</p> <p>N. 0° 09' E., on the N and S center line of sec. 26.</p> <p>Point for the center south 1/16 sec. cor. of sec. 26.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C S 1/16 S 26 C 1977</p>
39.97	<p>Raise a mound of stone, 2 ft. base, 2 ft. high, W of cor.</p> <p>Cor. is located 30 lks. N of E and W fence line.</p> <p>Point for the center ¼ sec. cor. of sec. 26, at intersection with the E and W center line.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 43 S R 5 W</p> <p style="text-align: center;">C ¼ S 26</p> <p style="text-align: center;">1977</p> <p>Set cedar post, 6 ins. diam., 4 ft. high, alongside cor.</p>

Subdivision of Section 26,
T. 43 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	Asc. SE slope, enter juniper and pinon timber.
59.75	Old E and W fence line.
60.025	Point for the center north 1/16 sec. cor. of sec. 26. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.
80.08	The ¼ sec. cor. of secs. 23 and 26, previously described.
	From the ¼ sec. cor. of secs. 25 and 26. N. 89° 53' W., on the E and W center line of sec. 26.
19.865	Point for the center east 1/16 sec. cor. of sec. 26. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	Cor. is located at fence cor. being constructed, fences bear E and S.
39.73	The center ¼ sec. cor. of sec. 26. Asc. SE slope, enter pinon and juniper.
79.67	The ¼ sec. cor. of secs. 26 and 27, monumented with an iron post, 1 in. diam., projecting 10 ins. above ground with brass cap mkd. as described in the field notes of the 1937 resurvey.
	From the N 1/16 sec. cor. of secs. 25 and 26. N. 89° 47' W., on the E and W center line of the NE¼ of sec. 26.
39.81	The center north 1/16 sec. cor. of sec. 26.
	From the point for the E 1/16 sec. cor. of secs. 26 and 35. N. 0° 22' E., on the N and S center line of the SE¼ of sec. 26.

Subdivision of Section 26,
T. 43 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
19.965	<p>Point for the SE 1/16 sec. cor. of sec. 26, at intersection with the E and W center line of the SE$\frac{1}{4}$.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S 26 1977</p>
39.93	<p>The center east 1/16 sec. cor. of sec. 26.</p>
	<p>From the point for the S 1/16 sec. cor. of secs. 25 and 26. N. 89° 56' W., on the E and W center line of the SE$\frac{1}{4}$ of sec. 26.</p>
19.79	<p>The SE 1/16 sec. cor. of sec. 26.</p>
39.58	<p>The center south 1/16 sec. cor. of sec. 26.</p>
	<p style="text-align: center;">General Description</p> <p>Section 26 consists of rolling valley land on the east and south portions, with hills and cliffs on the NE portion. Vegetation consists of shadscale and sagebrush, with pinon and juniper trees on the NE portion of the section. The only water is wells on the private land, being used for sprinkler irrigation. There is no permanent habitation at present time. The section is located about 8 miles east of Kanab, Utah.</p>

Form 9180-8
(March 1969)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Ferrel D. Reynolds	Supervisory Surveying Technician
Gail E. Reynolds	Supervisory Surveying Technician
Stewart Burt	Survey Aid
Donald Buhler	Survey Aid
Kathryn Johnson	Survey Aid
Donzil Worthington	Survey Aid
Bryan Seibold	Survey Aid

527

CERTIFICATE OF SURVEY

(I) ~~(We)~~ Craig P. Sylvester, ~~Surveyor~~, ~~of the State of Utah~~, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 3rd day of October, 1977, (I) ~~(We)~~ have dependently resurveyed a portion of the subdivisional lines and surveyed a portion of the subdivision of section 26, T. 43 S., R. 5 W.,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

November 9, 1978
(Date)

Craig P. Sylvester
(Cadastral Surveyor)
Supervisory

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Washington, D.C.
Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines and the survey of a portion of the subdivision of section 26, T. 43 S., R. 5 W., Salt Lake Meridian, Utah

executed by Craig P. Sylvester, Supervisory Cadastral Surveyor having been critically examined and found correct, are hereby approved.

FEB 07 1980
(Date)

J. Voorhes
(Chief, Division of Cadastral Survey)

Chief, Cadastral Survey Examination and Approval Staff

~~CERTIFICATE OF TRANSCRIPT~~

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____ is a true copy of the original field notes.

R599

FIELD NOTES

OF THE

 DEPENDENT RESURVEY OF PORTIONS

 OF THE

 SOUTH AND EAST BOUNDARIES

 AND

 SUBDIVISIONAL LINES,

 TOWNSHIP 11 SOUTH, RANGE 19 WEST,

Of the _____ SALT LAKE _____ Meridian,
 In the State of _____ UTAH _____

EXECUTED BY

Terrence O. Nickerson, Cadastral Surveyor

Under special instructions dated May 27, 19 75, approved June 6, 1975,

_____, which provided for the surveys included under U.S. Survey/Group
 Number 564, and assignment instructions dated June 10, 19 75.

Survey commenced June 24, 19 75

Survey completed September 5, 19 75

INDEX DIAGRAM

Township 11 South, Range 19 West,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25 6
31	32	33	34	35 5 1	36

T. 11 S., R. 19 W., Salt Lake Meridian, Utah

CHAINS

The following field notes describe the dependent resurvey of portions of the south and east boundaries and subdivisional lines, Township 11 South, Range 19 West, Salt Lake Meridian, Utah.

H. L. Baldwin surveyed the east 2 miles of the south boundary, the south 5 miles of the east boundary, and the west and north boundaries of section 36 in 1914. John W. Dougall resurveyed the east boundary in 1915.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 564, Utah, dated May 27, 1975.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of lines were determined by direct solar observations and refer to the true meridian.

The letters GIR are marked on the brass caps of corners located on the Goshutes Indian Reservation boundary.

The geographic position of the corner of sections 25 and 36, on the east boundary of the township, as scaled from the Geological Survey quadrangle map, "IBAPAH PEAK, UTAH", prepared in 1972, is as follows:

Latitude: 39° 50.0' N. Longitude: 113° 55.4' W.

The mean magnetic declination is 16½° E.

Dependent Resurvey of a Portion of the South Boundary,
T. 11 S., R. 19 W., Salt Lake Meridian, Utah

(Restoring the survey executed by H. L. Baldwin in 1914)

Beginning at the cor. of secs. 35 and 36, on the S. bdy. of the Tp., monumented with a granite stone, 14 x 12 x 5 ins., firmly set, protruding 4 ins. above the ground, in a collar of stone, 3 ft. base, to top, with 1 notch on E. edge, and 5 notches on W. edge.

from which

A pine, 40 ins. diam., bears N. 29° E., 56 lks. dist., with scribe marks R19W S36 BT AP GIR visible on partially healed blaze.
(Record, spruce, N. 20° E.)

A pine, 16 ins. diam., bears N. 20° W., 41 lks. dist., with scribe marks T11S R19W S35 AP GIR visible on partially healed blaze.
(Record, spruce, N. 29° W.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, to bedrock, in a collar of stone, 4 ft. base, to top, with brass cap mkd.

Dependent Resurvey, Portion of S. Bdy.,
T. 11 S., R. 19 W., Salt Lake Mer., Utah

CHAINS	<table border="1"> <tr> <td>T 11 S</td> <td>R 19 W</td> </tr> <tr> <td colspan="2">GIR</td> </tr> <tr> <td>S 35</td> <td>S 36</td> </tr> </table>	T 11 S	R 19 W	GIR		S 35	S 36
T 11 S	R 19 W						
GIR							
S 35	S 36						
	<p>1975</p> <p>Deposit granite stone alongside the iron post.</p> <p>N. 89° 57' W., along the S. bdy. of sec. 35.</p> <p>Desc. over steep, rocky W. slope, through heavy timber and moderate undergrowth.</p>						
2.84	<p>The closing cor. of secs. 1 and 2, T. 12 S., R. 19 W., monumented with an iron post, 2½ ins. diam., set, mkd., and witnessed as described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T. 12 S., R. 19 W., executed concurrently under this same group.</p>						
31.30	<p>Enter burn area, edge bears N. 20° W. and S. 20° E., with dense aspen reproduction and dense undergrowth.</p>						
39.91	<p>The ¼ sec. cor. of sec. 35, monumented with a granite stone, 18 x 8 x 6 ins., firmly set, protruding 10 ins. above the ground mkd. /4 on N. face, in a scattered mound of stone, 2½ ft. base, 2 ins. high.</p> <p>from which the remains of the remaining original bearing tree</p> <p>A log, species and size indeterminate, bears North, 18 lks. dist., with faint scribe marks visible on open blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground, to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>						
	<table border="1"> <tr> <td>T 11 S</td> <td>R 19 W</td> </tr> <tr> <td>¼ S 35</td> <td></td> </tr> </table> <p>1975</p> <p>Deposit original granite stone alongside the iron post.</p>	T 11 S	R 19 W	¼ S 35			
T 11 S	R 19 W						
¼ S 35							
	<p>Dependent Resurvey of a Portion of the East Boundary, T. 11 S., R. 19 W., Salt Lake Meridian, Utah</p>						
	<p>(Restoring the survey executed by H. L. Baldwin in 1914 and the resurvey executed by John W. Dougall in 1915)</p>						
	<p>From the true point for the cor. of secs. 25 and 36, on the E. bdy. of the Tp., determined at record dist. from the witness cor. to the cor. of secs. 25 and 36, and on a line from the cor. of secs. 30 and 31, T. 11 S., R. 18 W., hereinafter described, projected through the witness cor., falls in loose slide rock area where it is impracticable to establish a permanent monument.</p> <p>N. 0° 03' W., along the E. bdy. of sec. 25.</p> <p>Asc. along steep W. slope, through heavy timber and light undergrowth.</p>						

Dependent Resurvey, Portion of E. Bdy.,
T. 11 S., R. 19 W., Salt Lake Mer., Utah

CHAINS

0.15

The witness cor. to the cor. of secs. 25 and 36, established by H. L. Baldwin as the witness cor. to the cor. of secs. 25, 30, 31, and 36, monumented with a granite stone, 18 x 12 x 6 ins., firmly set, protruding 4 ins. above ground, with 5 faint notches on NE. edge and chisel marks WC on S. face, from which the original bearing trees

A spruce, 13 ins. diam., bears N. $51\frac{1}{2}^\circ$ E., 30 lks. dist., with scribe marks T11S R18W S30 BT visible on partially healed blaze.


A spruce, 7 ins. diam., bears S. $60\frac{1}{2}^\circ$ E., 28 lks. dist., with scribe marks T11S R18W S31 WC BT visible on open blaze.

A spruce, 11 ins. diam., bears S. $41\frac{1}{2}^\circ$ W., 7 lks. dist., with illegible scribe marks visible on partially healed blaze.

A spruce, 16 ins. diam., bears N. $59\frac{1}{2}^\circ$ W., 7 lks. dist., with scribe marks AP GIR T11S R19W S25 WC BT visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, in a collar of stone, $3\frac{1}{2}$ ft. base, to top, with brass cap mkd.



1975

Deposit the original stone alongside the iron post.

0.44 The cor. of secs. 30 and 31, T. 11 S., R. 18 W., monumented with an iron post, 3 ins. diam., firmly set, protruding 12 ins. above ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd. as described in the official record of the 1915 resurvey of the W. bdy. of T. 11 S., R. 18 W., from which the original bearing trees

A pine, 13 ins. diam., bears N. 53° E., 27 lks. dist., with scribe marks S30 BT visible on partially healed blaze.

A pine, 8 ins. diam., bears S. $28\frac{1}{2}^\circ$ E., 49 lks. dist., with scribe marks T11S R18W S31 BT visible on partially healed blaze.

N. $0^\circ 03'$ W., beginning new measurement.

Asc. over steep, rocky SW. slope, through heavy timber and light undergrowth.

21.94

The 1914 witness point, monumented with a mound of stone, 3 ft. base, 3 ft. high, on a spur, slopes N. 70° W. This point now functions as an angle point on the E. bdy. of sec. 25.

533

Dependent Resurvey, Portion of E. Bdy.,
T. 11 S.; R. 19 W.; Salt Lake Mer., Utah

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 1 in. in the ground, to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.

AP	
T 11 S	
R 19 W	R 18 W
S 25	S 30

1975

North, beginning new measurement.

16.93 The ¼ sec. cor. of sec. 25 only, on the E. bdy. of the Tp., marked with a cross (X) on the N. toe of a granite outcrop, with marks ¼ S above the cross (X), from which the original bearing trees

A spruce, 24 ins. diam., bears N. 85° E., 234 lks. dist., with scribe marks 30 visible on partially healed blaze.

A stump, size and species indeterminate, bears S. 63° W., 168 lks. dist., with visible blaze.

and new accessories

A spruce, 23 ins. diam., bears S. 74° W., 159 lks. dist., mkd. ¼ S25 BT.

An iron post, 28 ins. long, 2½ ins. diam., set 4 ins. in the ground, to solid rock, in a mound of stone, 4 ft. base, to top, for a reference monument, bears N. 70° W., 27.3 lks. dist., with brass cap mkd. T12S R19W S25 RM 18 FT 1975 and an arrow pointing to the cor.

From this cor. the cor. of secs. 24 and 25, on the E. bdy. of the Tp., bears North, 43.17 chs. dist., monumented with a granite stone, 30 x 30 x 8 ins., wedged between large boulders, with faint X chiseled on NW. edge of stone, from which the original bearing trees

A spruce, 23 ins. diam., bears N. 24° E., 50 lks. dist., with faint scribe marks BT visible on chopped out blaze.

A pine, 13 ins. diam., bears S. 55½° E., 23 lks. dist., with no marks visible on chopped open blaze.

A spruce, 12 ins. diam., bears S. 28¾° W., 29 lks. dist., with healed blaze.

A double pine, 14 ins. diam., bears N. 20¾° W., 17 lks. dist., with scribe marks R19W S24 BT visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 7 ins. in the ground, to bedrock, in a mound of stone, 6 ft. base, to top, with brass cap mkd.

535

Dependent Resurvey, Portion of Subdivisional Lines,
T. 11 S., R. 19 W., Salt Lake Mer., Utah

CHAINS	
	<p>A double white pine, 32 ins. diam., bears N. 40° E., 69 lks. dist., mkd. ¼ S36 BT.</p> <p>A white pine, 10 ins. diam., bears S. 55° W., 41 lks. dist., mkd. ¼ S35 BT.</p> <p>Deposit original granite stone alongside the iron post.</p> <p>N. 0° 27' W., beginning new measurement.</p> <p>Asc. over steep, rocky SW. slope, through moderate timber and dense undergrowth.</p> <p>16.90 Spur, slopes W.; desc. over steep NE. slope.</p> <p>21.51 Original line tree, a spruce, 18 ins. diam., with 2 hack marks on N. face and 2 hack marks on S. face.</p> <p>N. 0° 11' W., beginning new measurement.</p> <p>Desc. over steep, rocky NE. slope, through moderate timber and light undergrowth.</p> <p>18.33 The cor. of secs. 25, 26, 35, and 36, mkd. with a cross (X) on the SE. edge of a granite boulder, 20 x 6 x 4 ft. above ground, from which the original bearing trees</p> <p>A fir, 13 ins. diam., bears N. 16¼° E., 53 lks. dist., with healed blaze. (Record, white pine, N. 16° 10' E.)</p> <p>A fir, 20 ins. diam., bears S. 4° E., 41 lks. dist., with scribe marks T11S R19W AP GIR visible on partially healed blaze. (Record, spruce)</p> <p>A fir, 20 ins. diam., bears S. 82½° W., 12 lks. dist., with healed blaze. (Record, white pine)</p> <p>A white pine, 11 ins. diam., bears N. 40° W., 81 lks. dist., with healed blaze.</p> <p>Remark cross (X) on rock, no other permanent monument is practicable to set.</p> <p>from which new accessories</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 21 ins. in the ground, for a reference monument, bears S. 25° E., 9.4 lks. dist., with brass cap mkd. T11S R19W S36 RM 6.2 FT TO COR 1975.</p>
	<p>From the true point for the cor. of secs. 25 and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89° 15' W., bet. secs. 25 and 36.</p> <p>Desc. over steep, rocky W. slope, through scattering timber and light undergrowth.</p> <p>5.20 Foot of large granite pinnacle; asc. over steep cliff.</p> <p>8.60 Top of large granite pinnacle; desc. over steep cliff.</p> <p>12.90 Foot of large granite pinnacle; continue to desc. over steep, rocky W. slope.</p>

Dependent Resurvey, Portion of Subdivisional Lines,
T. 11 S., R. 19 W., Salt Lake Mer., Utah

CHAINS	
29.70	Top of granite ledge; desc. over steep, rocky ledge.
31.30	Foot of granite ledge; continue to desc. over steep, rocky W. slope.
37.10	Foot of steep descent; continue to desc. over gentle W. slope, enter heavy timber.
39.94	<p>The $\frac{1}{4}$ sec. cor. of secs. 25 and 36, monumented with an unmarked granite stone, 20 x 9 x 4 ins., firmly set, protruding 10 ins. above ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, from which original bearing trees</p> <p>A spruce, 12 ins. diam., bears S. $33\frac{1}{4}^{\circ}$ E., 45 lks. dist., with illegible scribe marks visible on partially healed blaze.</p> <p>A pine, 28 ins. diam., bears N. $5\frac{1}{4}^{\circ}$ W., 26 lks. dist., mkd. $\frac{1}{4}$ S25 BT on partially healed blaze. (Record, spruce)</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, in a collar of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 11 S R 19 W GIR $\frac{1}{4}$ $\frac{S 25}{S 36}$</p> <p style="text-align: center;">1975</p> <p>Deposit original stone alongside the iron post.</p> <p style="text-align: center;">-----</p> <p>S. $89^{\circ} 54'$ W., begin new measurement.</p> <p>Desc. over gentle W. slope, through heavy timber and light undergrowth.</p>
5.20	Creek, 2 lks. wide, course N. 25° W.; asc. over NE. slope.
30.70	Spur, slopes N.; desc. over NW. slope, undergrowth becomes dense.
33.90	Ravine, drains N.; asc. over NE. slope.
40.07	The cor. of secs. 25, 26, 35, and 36.

GENERAL DESCRIPTION

The area encompassed in this survey is located about 20 miles south southeast of Irapah, Utah. Terrain is mountainous; the elevation varies from 9,000 to 11,000 ft. above sea level. Drainage is generally to the west, provided by several small ravines and creeks. There are no roads or trails near the surveyed lines. Timber consists of pine, fir, spruce, and aspen.

538

CERTIFICATE OF SURVEY

(I) ~~(We)~~, Terrence O. Nickerson, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 27th day of May, 1975, (I) ~~(We)~~ have dependently resurveyed a portion of the south and east boundaries and subdivisional lines, Township 11 South, Range 19 West,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

12/22/78 (Date) Terrence O. Nickerson (Cadastral Surveyor)

(Date) (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Washington, D.C. Denver, Colorado

The foregoing field notes of the dependent resurvey of portions of the south and east boundaries and subdivisional lines, Township 11 South, Range 19 West, Salt Lake Meridian, Utah,

executed by Terrence O. Nickerson, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JAN 21 1980 (Date) J. Voorhes (Chief, Division of Cadastral Survey) Chief, Cadastral Survey Examination and Approval Staff

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes.

(Date) (Chief, Division of Cadastral Survey) GPO 849-626

R599

539

FIELD NOTES

OF THE

 DEPENDENT RESURVEY

 OF

 PORTIONS OF THE SOUTH AND WEST BOUNDARIES

 AND

 SUBDIVISIONAL LINES,

 AND

 THE SURVEY OF THE SUBDIVISION

 OF

 SECTIONS 27, 29, 30, 33, AND 35,

 TOWNSHIP 12 SOUTH, RANGE 19 WEST,

Of the _____ SALT LAKE _____ Meridian,
 In the State of _____ UTAH _____

EXECUTED BY

Terrence O. Nickerson, Cadastral Surveyor

Under special instructions dated May 27, 19 75, approved June 6, 1975,

_____, which provided for the surveys included under U.S. Survey/Group
 Number 564, and assignment instructions dated June 10, 19 75.

Survey commenced June 24, 19 75

Survey completed September 5, 19 75

INDEX DIAGRAM

Township 12 South, Range 19 West,

6	5	4	3	2	7 1
7	8	9	10	11	6 12
18	17	16	15	14	4 13
19	20	21	22	11 23	24
3	19		15		
30	18		14		
	20	28	27	26	25
	18	17	14		
		16			
31	32	33	13 34	9 35	36
			2	1	

- Survey of the Subdivision of Section 27..... pages 19-21
- Survey of the Subdivision of Section 29..... pages 21-22
- Survey of the Subdivision of Section 30..... pages 23-25
- Survey of the Subdivision of Section 33..... pages 25-27
- Survey of the Subdivision of Section 35..... pages 27-29

T. 12 S., R. 19 W., Salt Lake Meridian, Utah

CHAINS

The following field notes describe the dependent resurvey of a portion of the south and west boundaries and subdivisional lines and the survey of the subdivision of sections 27, 29, 30, 33, and 35, Township 12 South, Range 19 West, Salt Lake Meridian, Utah.

In 1914, H. L. Baldwin surveyed portions of the south, west, and north boundaries and subdivisional lines. In 1915-1916, John W. Dougall resurveyed a portion of the south boundary and surveyed portions of the south and west boundaries and subdivisional lines.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 564, Utah, dated May 27, 1975.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of lines were determined by direct solar observations and refer to the true meridian.

The letters GIR are marked on the brass caps of corners located on the Goshutes Indian Reservation boundary.

The geographic position of the $\frac{1}{4}$ section corner of section 35 only, on the south boundary of the township, as determined from a tie made to U.S.G.S. triangulation station "TROUT," located in the SW $\frac{1}{4}$ of section 14, is as follows:

Latitude: 39° 43' 31" N. Longitude: 113° 57' 26" W.

The mean magnetic declination is 16 $\frac{1}{2}$ ° E.

Dependent Resurvey of a Portion of the South Boundary,
T. 12 S., R. 19 W., Salt Lake Meridian, Utah

(Restoring the survey executed by H. L. Baldwin in 1914
and the resurvey and survey
executed by John W. Dougall in 1915-1916)

Beginning at the $\frac{1}{4}$ sec. cor. of sec. 35 only, on the S. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, protruding 15 ins. above the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd. in 1915 as the $\frac{1}{4}$ sec. cor. of secs. 2 and 35. Change the marks so the brass cap is now mkd.

T 12 S	R 19 W
$\frac{1}{4}$ S 35	
T 13 S	R 19 W

1975
1915

from which the remains of the 1915 bearing trees

A mahogany stump, 8 ins. diam., bears S. 71 $\frac{1}{4}$ ° W., 170 lks. dist., with scribe marks $\frac{1}{4}$ S2 BT visible on open blaze.

A root hole, bears N. 52° W., 26 lks. dist., with a pine lying alongside, 18 ins. diam., with scribe marks $\frac{1}{4}$ S BT visible on partially healed blaze.

Dependent Resurvey, Portion of S. Bdy.,
T. 12 S., R. 19 W., Salt Lake Mer., Utah

CHAINS																
	<p>N. 89° 56' W., along the S. bdy. of sec. 35.</p> <p>Asc. over broken N. slope, through heavy timber and dense undergrowth.</p> <p>19.97 Point for the W. 1/16 sec. cor. of sec. 35 only.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T 12 S</td><td>R 19 W</td></tr> <tr><td>W 1/16</td><td>S 35</td></tr> </table> <p>1975</p> </div> <p>from which</p> <p>A fir, 13 ins. diam., bears N. 70½° E., 37 lks. dist., mkd. W 1/16 S35 BT.</p> <p>39.94 The cor. of secs. 34 and 35, on the S. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, protruding 2 ft. above the ground, in a scattered mound of stone, 4 ft. base, 1 ft. high, with brass cap mkd. as described in the official record of the 1915-1916 resurvey of the N. bdy. of T. 13 S., R. 19 W. This cor. refers to T. 12 S., R. 19 W. only. Change the marks so the brass cap is now mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T 12 S</td><td>R 19 W</td></tr> <tr><td>GIR</td><td></td></tr> <tr><td>S 34</td><td>S 35</td></tr> <tr><td>T 13 S</td><td>R 19 W</td></tr> <tr><td>S 3</td><td></td></tr> </table> <p>1975 1915</p> </div> <p>Rebuild the mound of stone surrounding the iron post, 5 ft. base, to top.</p>	T 12 S	R 19 W	W 1/16	S 35	T 12 S	R 19 W	GIR		S 34	S 35	T 13 S	R 19 W	S 3		
T 12 S	R 19 W															
W 1/16	S 35															
T 12 S	R 19 W															
GIR																
S 34	S 35															
T 13 S	R 19 W															
S 3																
	<p>S. 89° 48' W., along the S. bdy. of sec. 34.</p> <p>Over broken N. slope, through scattering timber and dense undergrowth.</p> <p>9.20 Ravine, drains N. 25° E.</p> <p>40.05 The ¼ sec. cor. of sec. 34 only, on the S. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, protruding 12 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. in 1915 as the ¼ sec. cor. of secs. 3 and 34. Change the marks so the brass cap is now mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T 12 S</td><td>R 19 W</td></tr> <tr><td>¼ S 34</td><td></td></tr> <tr><td>T 13 S</td><td>R 19 W</td></tr> </table> <p>1975 1915</p> </div> <p>from which original bearing trees</p> <p>An aspen, 10 ins. diam., bears N. 78½° E., 33 lks. dist., with healed blaze.</p> <p>An aspen, 12 ins. diam., bears S. 71½° W., 58 lks. dist., with healed blaze.</p> <hr/> <p>N. 89° 56' W., beginning new measurement.</p> <p>Asc. over broken N. slope, through scattering timber and dense undergrowth.</p> <p>30.50 Spur ridge, bears N. and S. 80° E.; desc. along W. slope.</p>	T 12 S	R 19 W	¼ S 34		T 13 S	R 19 W									
T 12 S	R 19 W															
¼ S 34																
T 13 S	R 19 W															

Dependent Resurvey, Portion of S. Bdy.,
T. 12 S., R. 19 W., Salt Lake Mer., Utah

<p>CHAINS 34.10</p>	<p>The closing cor. of secs. 3 and 4, T. 13 S., R. 19 W., monumented with an iron post, 1 in. diam., firmly set, extending 15 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd. as described in the official record of the 1916 survey of the subdivisional lines of T. 13 S., R. 19 W.</p> <p>from which original bearing trees</p> <p>A bristlecone pine, 13 ins. diam., bears S. $34\frac{1}{2}^{\circ}$ E., 43 lks. dist., with scribe marks C T13S R19W S3 BT visible on partially healed blaze.</p> <p>A bristlecone pine, 12 ins. diam., bears S. $29\frac{1}{4}^{\circ}$ W., 55 lks. dist., with scribe marks CC T13S R19W S4 BT visible on partially healed blaze.</p>
<p>39.94</p>	<p>The cor. of secs. 33 and 34, on the S. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, protruding 16 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T 12 S</p> <p style="text-align: center;">S 33 S 34 R 19 W</p> <p style="text-align: center;">T 13 S</p> <p style="text-align: center;">1915</p> <p>from which original bearing trees</p> <p>A pine snag, 6 ins. diam., bears N. 21° E., 49 lks. dist., with scribe marks T12S R19W S34 BT visible on open blaze.</p> <p>A bristlecone pine, 22 ins. diam., bears N. 63° W., 40 lks. dist., with scribe marks T12S R19W 33 BT.</p>
<p>Dependent Resurvey of a Portion of the West Boundary, T. 12 S., R. 19 W., Salt Lake Meridian, Utah</p>	
<p>(Restoring the survey executed by John W. Dougall in 1916)</p>	
<p>10.90</p>	<p>From the $\frac{1}{4}$ sec. cor. of secs. 25 and 30, on the W. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, protruding 10 ins. above ground, with brass cap mkd. as described in the official record of the 1916 survey of the W. bdy. of T. 12 S., R. 19 W., from which the remains of the original bearing trees</p> <p>A mahogany, 8 ins. diam., bears N. 45° E., 6 lks. dist., with no visible blaze. (Record, 10 ins. diam.)</p> <p>A mahogany, 6 ins. diam., bears S. 85° W., 14 lks. dist., with healed blaze.</p> <p>and new bearing tree</p> <p>A mahogany, 10 ins. diam., bears N. 30° E., 17 lks. dist., mkd. $\frac{1}{4}$ S30 BT.</p> <p>Add the marks T12S R19W and R20W on the brass cap, and raise a mound of stone, 3 ft. base, 10 ins. high around the iron post.</p> <p>North, bet. secs. 25 and 30.</p> <p>Asc. over steep, rocky S. slope, through dense mountain mahogany.</p>


544

Dependent Resurvey, Portion of W. Bdy.,
T. 12 S., R. 19 W., Salt Lake Mer., Utah

CHAINS
20.03

Point for the N. 1/16 sec. cor. of secs. 25 and 30.

Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground, to solid bedrock, in a mound of stone, 2½ ft. base, to top, with brass cap mkd.



from which

A pine, 8 ins. diam., bears N. 45° E., 31 lks. dist., mkd. N 1/16 S30 BT.

A pine, 12 ins. diam., bears N. 85° W., 21 lks. dist., mkd. N 1/16 S25 BT.

40.06

The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, protruding 14 ins. above ground, with brass cap mkd. as described in the official record of the 1916 survey of the W. bdy. of T. 12 S., R. 19 W., alongside of which is a limestone, 10 x 2 ins., protruding 10 ins. above the ground, with 4 grooves on E. edge and 2 grooves on S. edge, from which bearing trees mkd. by Baldwin in 1914

A pine stump, 10 ins. diam., bears N. 21¼° E., 12 lks. dist., with a pine log lying alongside, with illegible scribing on rotted blaze.

A white pine, 18 ins. diam., bears S. 35° E., 40 lks. dist., with healed blaze.

A pine snag, 15 ins. diam., bears S. 33¾° W., 36 lks. dist., with healed blaze.

A spruce snag, 15 ins. diam., bears N. 39½° W., 25 lks. dist., with scribe marks 19S R20W S24 SW COR GIR BT visible on open blaze.

and new bearing trees

A pine, 10 ins. diam., bears N. 45° E., 48 lks. dist., mkd. T12S R19W S19 BT.

A pine, 9 ins. diam., bears S. 50° W., 43 lks. dist., mkd. T12S R20W S25 BT.

A fir, 9 ins. diam., bears N. 70° W., 33 lks. dist., mkd. T12S R20W S24 BT.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 12 S., R. 19 W., Salt Lake Meridian, Utah

(Restoring the surveys executed by
H. L. Baldwin in 1914 and John W. Dougall in 1916)

From the cor. of secs. 13, 14, 23, and 24, monumented with a slate stone, 18 x 12 x 4 ins., loosely set in a scattered mound of stone, 1 ft. base, 6 ins. high, mkd. with 1 groove on E. face, 3 notches on S. edge, and AP GIR on W. face, from which the remaining original bearing trees

Dependent Resurvey, Portion of Subdivisional Lines,
T. 12 S., R. 19 W., Salt Lake Mer., Utah

CHAINS

A spruce, 13 ins. diam., bears S. $13\frac{3}{4}^{\circ}$ W.,
222 lks. dist., with scribe marks T12S R19W
S23 AP GIR BT visible on partially healed
blaze.

A pine, 26 ins. diam., bears N. 26° W., 147 lks.
dist., with scribe marks T12S R19W S14 AP GIR
BT visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in
the ground, in a mound of stone, 3 ft. base, to top, with
brass cap mkd.

T 12 S	R 19 W
GIR	
S 14	S 13
S 23	S 24

1975

from which

A fir, 12 ins. diam., bears N. 88° E., 151 lks.
dist., mkd. T12S R19W S13 BT.

A spruce, 15 ins. diam., bears S. 68° E., 134 lks.
dist., mkd. T12S R19W S24 BT.

N. $0^{\circ} 02'$ W., bet. secs. 13 and 14, along the E. bdy. of
the Goshute Indian Reservation bdy.

Desc. over steep N. slope, through open land.

13.10 Creek, 10 lks. wide, 1 ft. deep, course S. 70° E.; asc.
over steep, rocky S. slope; enter timber, edge bears
N. 70° W. and S. 70° E.

30.60 Ridge bears generally E. and W.; desc. over NE. slope.

39.83 The $\frac{1}{4}$ sec. cor. of secs. 13 and 14, monumented with a
slate stone, 24 x 10 x 4 ins., firmly set, protruding
14 ins. above ground, mkd. $\frac{1}{4}$ S on W. face, from which
the original bearing trees

A spruce, 11 ins. diam., bears S. $61\frac{1}{2}^{\circ}$ E., 41 lks.
dist., with illegible scribe marks visible on
partially healed blaze.

A fir, 17 ins. diam., bears N. $45\frac{1}{2}^{\circ}$ W., 42 lks.
dist., with illegible scribe marks visible on
partially healed blaze. (Record, spruce)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in
the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with
brass cap mkd.

T 12 S	R 19 W
GIR	
S 14	S 13

1975

Deposit slate stone alongside the iron post.

546

Dependent Resurvey, Portion of Subdivisional Lines,
T. 12 S., R. 19 W., Salt Lake Mer., Utah


CHAINS													
	<p>N. 0° 04' W., beginning new measurement.</p> <p>Desc. over steep NE. slope, through heavy timber and light undergrowth.</p> <p>32.00 Trout Creek, 10 lks. wide, 1 ft. deep, course S. 50° E.; asc. over steep and rocky S. slope.</p> <p>39.88 The cor. of secs. 11, 12, 13, and 14, monumented with a sandstone, 24 x 8 x 4 ins., loosely set in a scattered mound of stone, 3 ft. base, 1 ft. high, with 2 notches on E. edge and 4 notches on S. edge, from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A down triple mahogany, 10 ins. diam., bears N. 19° E., 73 lks. dist., with scribe marks T12S R19W S12 visible on open blaze.</p> <p style="padding-left: 40px;">A mahogany, 15 ins. diam., bears S. 50½° E., 225 lks. dist., with scribe marks T12S R19W S13 BT visible on open blaze.</p> <p style="padding-left: 40px;">A mahogany, 14 ins. diam., bears S. 44° W., 39 lks. dist., with scribe marks T12S R19W S14 BT visible on open blaze.</p> <p style="padding-left: 40px;">A mahogany, 8 ins. diam., bears N. 49° W., 41 lks. dist., with scribe marks T12S R19W S11 GIR BT visible on open blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., over a cross (X) on solid rock, in a mound of stone, 6 ft. base, to top, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 12 S.</td> <td style="border-left: 1px solid black; padding: 0 10px;">R 19 W</td> </tr> <tr> <td style="padding: 0 10px;">GIR</td> <td style="border-left: 1px solid black; padding: 0 10px;"> </td> </tr> <tr> <td style="padding: 0 10px;">S 11</td> <td style="border-left: 1px solid black; padding: 0 10px;">S 12</td> </tr> <tr> <td style="padding: 0 10px;">S 14</td> <td style="border-left: 1px solid black; padding: 0 10px;">S 13</td> </tr> <tr> <td style="padding: 0 10px;">GIR</td> <td style="border-left: 1px solid black; padding: 0 10px;"> </td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 10px;">1975</td> </tr> </table> <p>from which</p> <p style="padding-left: 40px;">An aspen, 7 ins. diam., bears N. 74° E., 76 lks. dist., mkd. T12S R19W S12 BT.</p> <p>Deposit the sandstone alongside the iron post.</p>	T 12 S.	R 19 W	GIR		S 11	S 12	S 14	S 13	GIR		1975	
T 12 S.	R 19 W												
GIR													
S 11	S 12												
S 14	S 13												
GIR													
1975													
<p>35.90</p> <p>40.16</p>	<p>North, bet. secs. 11 and 12.</p> <p>Asc. over steep, rocky SE. slope, through scattering timber and moderate undergrowth.</p> <p>Spur, slopes SE.</p> <p>The ¼ sec. cor. of secs. 11 and 12, monumented with a granite stone, 24 x 14 x 4 ins., loosely set, protruding 18 ins. above the ground, mkd. 1/4 S on W. face; from which the original bearing trees</p> <p style="padding-left: 40px;">A double pinon, 43 ins. diam., bears N. 84½° E., 100 lks. dist., with illegible scribe marks visible on partially healed blaze.</p> <p style="padding-left: 40px;">A pinon, 32 ins. diam., bears N. 86° W., 127 lks. dist., with illegible scribe marks on partially healed blaze.</p>												

Dependent Resurvey, Portion of Subdivisional Lines,
T. 12 S., R. 19 W., Salt Lake Mer., Utah

CHAINS

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., $2\frac{1}{2}$ ins. in the ground, with brass cap mkd.



Bury the granite stone alongside the iron post.

North, beginning new measurement.

Asc. over steep, rocky SE. slope, through scattering timber and moderate undergrowth.

27.00 Spur, slopes W.; desc. over rock slide, over NW. slope.

39.50 The witness cor. to the cor. of secs. 1, 2, 11, and 12, monumented with a sandstone, 14 x 14 x 5 ins., loosely set in a mound of stone, 4 ft. base, 2 ft. high, mkd. WC on N. face, 1 notch on E. edge, 5 notches on S. edge, and GIR on W. face, from which the original bearing trees

A spruce, 12 ins. diam., bears N. $78\frac{1}{2}^{\circ}$ E., 42 lks. dist., mkd. T12S R19W S1 GIR WC BT.


A spruce, 9 ins. diam., bears S. 16° E., 41 lks. dist., mkd. T12S R19W S12 GIR WC BT.

A spruce, 10 ins. diam., bears S. $30\frac{1}{4}^{\circ}$ W., 122 lks. dist., mkd. T12S R19W S11 GIR WC BT.

A spruce, 14 ins. diam., bears N. $19\frac{1}{4}^{\circ}$ W., 141 lks. dist., with scribe marks T12S R19W S2 GIR WC BT visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 2 ins. in the ground, to solid rock, in a mound of stone, 5 ft. base, to top, with brass cap mkd.



40.05 True point for the cor. of secs. 1, 2, 11, and 12, determined latitudinally at proportionate dist. and longitudinally on projection of the sec. line to the S., falls on large rock slide where it is impracticable to establish a permanent monument.

N. $0^{\circ} 03'$ E., bet. secs. 1 and 2.

Asc. along W. slope over rock slide, through scattering timber and light undergrowth.

548

Dependent Resurvey, Portion of Subdivisional Lines,
T. 12 S., R. 19 W., Salt Lake Mer., Utah

CHAINS
11.00

Spur, slopes W.; desc. over steep, rocky NW. slope.

39.92

The $\frac{1}{4}$ sec. cor. of secs. 1 and 2, monumented with a granite stone, 25 x 8 x 4 ins., loosely set, protruding 18 ins. above the ground, in a scattered mound of stone, 3 ft. base, 6 ins. high, mkd. $\frac{1}{4}$ S on W., face, from which the remains of the original bearing trees

A spruce stump, size indeterminate, bears S. 21° E., 6 lks. dist., with no visible blaze.

A spruce, 19 ins. diam., bears S. $50\frac{1}{2}^\circ$ W., 78 lks. dist., with illegible scribe marks visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, to solid bedrock, in a mound of stone, $4\frac{1}{2}$ ft. base, to top, with brass cap mkd.

T 12 S R 19 W
 $\frac{1}{4}$
 GIR
 S 2 S 1
 |
 1975

from which a new bearing tree

A spruce, 32 ins. diam., bears N. 18° E., 73 lks. dist., mkd. $\frac{1}{4}$ S1 BT.

N. $0^\circ 07'$ E., beginning new measurement.

Desc. over N. slope, through heavy timber and moderate undergrowth.

17.00

Fork of Fifteen Mile Creek, 10 lks. wide, 6 ins. deep, course N. 70° W.; asc. over steep, rocky SW. slope, through dense aspen.

39.98

The $80 \frac{1}{16}$ sec. cor. of secs. 1 and 2, monumented with a granite stone, 20 x 10 x 3, firmly set protruding 12 ins. above the ground, faintly mkd. $\frac{1}{4}$ on W. face, from which the original bearing trees

An aspen, 6 ins. diam., bears S. 55° E., 33 lks. dist., with healed blaze.

A pinon, 42 ins. diam., bears N. $31\frac{1}{2}^\circ$ W., 120 lks. dist., with scribe marks $\frac{1}{4}$ S BT visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, in a collar of stone, $2\frac{1}{2}$ ft. base, to top, with brass cap mkd.

$\frac{1}{16}$
GIR
S 2 S 1
 |
 80
 1975

Dependent Resurvey, Portion of Subdivisional Lines,
T. 12 S., R. 19 W., Salt Lake Mer., Utah

CHAINS

Deposit the original stone alongside the iron post.

N. $0^{\circ} 21'$ E., beginning new measurement.

Asc. over steep, rocky S. slope, through heavy aspen and light undergrowth.

13.50 Spur, slopes N. 70° W.; desc. over N. slope, through old burn area.

34.50 Ravine, drains N. 70° W.; asc. over S. slope.

37.04 Intersect the N. bdy. of the Tp. at the closing cor. of secs. 1 and 2, monumented with a granite stone, 24 x 10 x 6 ins., firmly set, protruding 4 ins. above a mound of stone, 3 ft. base, 6 ins. high, mkd. AP GIR on N. face, from which the remains of the original bearing trees

A stump, size and species indeterminate, bears S. 43° E., 36 lks. dist., no blaze visible.

A snag, species indeterminate, 10 ins. diam., bears S. 50° W., 4 lks. dist., with fragmentary scribe marks visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, in a collar of stone, 3 ft. base, to top, with brass cap mkd.

T 11 S R 19 W
GIR
S 35

S 2 | S 1
T 12 S
CC

1975

Deposit the original stone alongside the iron post.

From this cor. the $\frac{1}{4}$ sec. cor. of sec. 35 only, on the S. bdy. of T. 11 S., R. 19 W., bears N. $89^{\circ} 57'$ W., 18.07 chs. dist., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd., and witnessed as described in the field notes of the dependent resurvey of a portion of the S. bdy. of T. 11 S., R. 19 W., executed concurrently under this same group.

From the cor. of secs. 34 and 35, on the S. bdy. of the Tp.

N. $0^{\circ} 01'$ W., bet. secs. 34 and 35.

Desc. over steep N. slope, through heavy timber and moderate undergrowth.

19.98 Point for the S. $1/16$ sec. cor. of secs. 34 and 35.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

550

Dependent Resurvey, Portion of Subdivisional Lines,
T. 12 S., R. 19 W., Salt Lake Mer., Utah

CHAINS

S 1/16
GIR |
S 34 | S 35

1975

from which

A fir, 10 ins. diam., bears N. $74\frac{1}{2}^\circ$ E., 40 lks.
dist., mkd. S 1/16 S35 BT.

A fir, 9 ins. diam., bears S. $81\frac{1}{4}^\circ$ W., 24 lks.
dist., mkd. S 1/16 S34 BT.

and a tree for which there is no known record

A fir, 12 ins. diam., bears S. 32° W., 16 lks.
dist., with healed blazes on N., S., E., and
W. faces.

- 22.00 Ravine, drains N. 55° E.; asc. over steep S. slope; leave heavy timber, edge bears N. 55° E. and S. 55° W.
- 27.40 Spur, slopes E.; desc. over N. slope.
- 35.00 Creek, 5 lks. wide, course E.; asc. over steep S. slope.
- 39.96 The $\frac{1}{4}$ sec. cor. of secs. 34 and 35, monumented with a slate stone, 24 x 12 x 4 ins., loosely set, in a scattered mound of stone, mkd. $\frac{1}{4}$ S on W. face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground, to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.

T 12 S R 19 W
 $\frac{1}{4}$
S 34 | S 35
GIR |

1975

Deposit the original stone alongside the iron post.

N. $0^\circ 01'$ W., beginning new measurement.

Asc. steep S. slope, through moderate undergrowth.

- 9.00 Spur, slopes E.; desc. over steep N. slope.
- 12.50 Enter heavy timber, edge bears generally E. and W.
- 38.30 Creek, 10 lks. wide, 1 ft. deep, course S. 75° E.; asc. over steep S. slope; leave timber, edge bears E. and W.
- 39.96 The cor. of secs. 26, 27, 34, and 35, monumented with an iron post, 2 ins. diam., loosely set, protruding 18 ins. above ground, in a scattered mound of stone, 2 ft. base, 6 ins. high, with brass cap mkd. as described in the official record of the 1916 survey of a portion of the subdivisional lines of T. 12 S., R. 19 W.
- Add the marks GIR on the brass cap and rebuild the mound of stone around the iron post, 4 ft. base, to top.

Dependent Resurvey, Portion of Subdivisional Lines,
T. 12 S., R. 19 W., Salt Lake Mer., Utah

CHAINS

From the cor. of secs. 22, 23, 26, and 27, monumented with an iron post, 2 ins. diam., loosely set, protruding 12 ins. above ground, in a scattered mound of stone, 4 ft. base, 10 ins. high, with brass cap erroneously mkd. in 1916. Add the marks S22 1975; the brass cap is now mkd.

GIR	T 12 S
S 22	S 23
S 27	S 26
R 19 W	
1975	
1916	

from which the remains of the 1916 bearing trees

An aspen log, 6 ins. diam., bears N. $9\frac{3}{4}^{\circ}$ E., 140 lks. dist., with illegible scribe marks visible on open blaze.

An aspen stump, 6 ins. diam., bears S. $80\frac{1}{2}^{\circ}$ W., 45 lks. dist., with scribe marks T12S R19W S27 BT visible on open blaze.

and new bearing trees

An aspen, 3 ins. diam., bears N. 10° E., 5 lks. dist., mkd. X BT.

An aspen, 3 ins. diam., bears S. $80\frac{1}{2}^{\circ}$ W., 61 lks. dist., mkd. X BT.

An aspen, 8 ins. diam., bears N. 70° W., 30 lks. dist., mkd. T12S R19W S22 BT.

Rebuild mound of stone surrounding iron post, 4 ft. base, to top.

N. $0^{\circ} 45'$ W., bet. secs. 22 and 23.

Asc. over steep SE. slope, through moderate timber and dense undergrowth.

39.90 The $\frac{1}{4}$ sec. cor. of secs. 22 and 23, monumented with a quartzite stone, 22 x 12 x 6 ins., firmly set, protruding 2 ins. above a mound of stone, 2 $\frac{1}{2}$ ft. base, 10 ins. high, mkd. $\frac{1}{4}$ S on W. face, from which the remains of the original bearing tree

An aspen snag, 8 ins. diam., bears N. $49\frac{1}{2}^{\circ}$ E., 26 lks. dist., with scribe marks BT visible on partially healed blaze. (Record, N. $59\frac{1}{2}^{\circ}$ E.)

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 23 ins. in the ground, in a mound of stone, 5 ft. base, to top, with brass cap mkd.

T 12 S	R 19 W
S 22	S 23
GIR	$\frac{1}{4}$

1975

from which new bearing trees

An aspen, 5 ins. diam., bears N. 50° E., 29 lks. dist., mkd. $\frac{1}{4}$ S23 BT.

An aspen, 4 ins. diam., bears S. 80° W., 32 lks. dist., mkd. X BT.

Deposit the original stone alongside the iron post.

552

Dependent Resurvey, Portion of Subdivisional Lines,
T. 12 S., R. 19 W., Salt Lake Mer., Utah

CHAINS

N. $0^{\circ} 32'$ E., beginning new measurement.

Asc. over steep SE. slope, through medium timber and dense undergrowth.

30.00 Leave timber, edge bears generally E. and W.; continue over loose slide rock.

36.00 Top of ascent, slopes S. 30° W.; desc. over NW. slope.

39.94 The cor. of secs. 14, 15, 22, and 23, monumented with a quartzite stone, 24 x 9 x 6 ins., loosely set, protruding 6 ins. above mound of stone, 3 ft. base, 16 ins. high, mkd. 2 notches on E. edge, 3 notches on S. edge, and AP GIR on W. face, from which the original bearing trees

A spruce, 10 ins. diam., bears N. 27° E., 38 lks. dist., mkd. T12S R19W AP GIR BT visible on open blaze.

A spruce, 10 ins. diam., bears S. $59\frac{1}{2}^{\circ}$ W., 53 lks. dist., mkd. T12S R19W AP GIR BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 2 ins. in the ground, to bedrock, in a mound of stone, 6 ft. base, to top, with brass cap mkd.

T 12 S	R 19 W
GIR	GIR
S 15	S 14
S 22	S 23
GIR	
1975	

from which a new bearing tree

A pine, 7 ins. diam., bears N. 40° E., 16 lks. dist., mkd. X BT.

Deposit the original stone alongside the iron post.

From this cor. USGS triangulation station "TROUT", bears N. $23^{\circ} 26'$ E., 18.09 chs. dist., a brass tablet, 3 ins. diam., seated in concrete.

From the cor. of secs. 13, 14, 23, and 24.

N. $89^{\circ} 59'$ W., bet. secs. 14 and 23.

Asc. over NE. slope, through heavy timber and moderate undergrowth.

38.27 Original line tree, a spruce, 22 ins. diam., with 2 hack marks on E. face and 2 hack marks on W. face.

N. $89^{\circ} 59'$ W., beginning new measurement.

1.72 The $\frac{1}{4}$ sec. cor. of secs. 14 and 23, monumented with a quartz stone, 24 x 10 x 6 ins., loosely set, protruding 6 ins. above a mound of stone, 2 ft. base, 1 ft. high, mkd. $\frac{1}{4}$ S on N. face, from which the original bearing trees

Dependent Resurvey, Portion of Subdivisional Lines,
T. 12 S., R. 19 W., Salt Lake Mer., Utah

CHAINS

A spruce, 12 ins. diam., bears S. 74° E., 10 lks. dist., with healed blaze.

A spruce, 8 ins. diam., bears N. $65\frac{1}{2}^{\circ}$ W., 6 lks. dist., with scribe marks $\frac{1}{4}$ S14 BT visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, in a collar of stone, 3 ft. base, to top, with brass cap mkd.

T 12 S R 19 W

GIR

$\frac{1}{4}$ S 14
S 23

1975

Deposit the original stone alongside the iron post.

S. $89^{\circ} 57'$ W., beginning new measurement.

Asc. slightly over NE. slope, through heavy timber and light undergrowth.

- 10.00 Begin to asc. over steep NE. slope.
- 32.00 Leave heavy timber and light undergrowth, edge bears generally N. and S.; continue to asc. steep NE. slope over slide rock.
- 37.00 Top of ascent, slopes S. 30° W.; desc. over NW. slope over slide rock.
- 40.04 The cor. of secs. 14, 15, 22, and 23.

From the cor. of secs. 33 and 34, on the S. bdy. of the Tp.

N. $0^{\circ} 05'$ W., bet. secs. 33 and 34.

Desc. over stoney W. slope, through moderate timber and light undergrowth.

- 40.01 The $\frac{1}{4}$ sec. cor. of secs. 33 and 34, monumented with an iron post, 1 in. diam., firmly set, protruding 6 ins. above mound of stone, 2 ft. base, 6 ins. high, with brass cap mkd. as described in the official record of the 1916 survey of a portion of the subdivisional lines of T. 12 S. R. 19 W., from which the original bearing trees

An aspen, 8 ins. diam., bears N. 25° E., 19 lks. dist., with illegible scribe marks visible on partially healed blaze.

An aspen, 10 ins. diam., bears S. 82° W., 20 lks. dist., with scribe marks $\frac{1}{4}$ S33 BT visible on partially healed blaze.

Add the marks T12S R19W GIR 1975 on the brass cap and rebuild the mound of stone surrounding the iron post, $3\frac{1}{2}$ ft. base, to top.

554

Dependent Resurvey, Portion of Subdivisional Lines,
T. 12 S., R. 19 W., Salt Lake Mer., Utah

CHAINS

From the cor. of secs. 26, 27, 34, and 35.

S. 89° 44' W., bet. secs. 27 and 34.

Asc. steep E. slope, through light undergrowth.

39.98 The $\frac{1}{4}$ sec. cor. of secs. 27 and 34, determined from the original bearing trees

An aspen, 10 ins. diam., bears S. 37° E., 10 lks. dist., with illegible scribe marks visible on bark blaze. (Record, S. 35° E.)

An aspen, 11 ins. diam., bears N. 58° W., 15 lks. dist., with scribe marks $\frac{1}{4}$ S BT visible on bark blaze. (Record, N. 55° W.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground, to solid rock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 12 S R 19

$\frac{1}{4}$ $\frac{S 27}{S 34}$

GIR

1975

from which a bearing tree for which there is no known record

An aspen, 12 ins. diam., bears N. 46½° E., 5 lks. dist., with scribe marks $\frac{1}{4}$ S BT 34 visible on partially healed blaze.

From the $\frac{1}{4}$ sec. cor. of secs. 27 and 28, monumented with an iron post, 1 in. diam., firmly set, protruding 12 ins. above the ground, with brass cap mkd. as described in the official record of the 1916 survey of a portion of the subdivisional lines of T. 12 S., R. 19 W., from which the remains of the original bearing tree

An uprooted aspen, 6 ins. diam., bears N. 42¾° W., 143 lks. dist., with no visible blaze. (Record, N. 43½° W.)

Cor. is located on open NW. slope.

North, bet. secs. 27 and 28.

Asc. over steep NW. slope, through scattering timber and light undergrowth.

13.00 Spur, slopes W.; continue to asc. over gentle NW. slope.

19.95 Point for the N. 1/16 sec. cor. of secs. 27 and 28.

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, 2 ft. base, to top, with brass cap mkd.

N 1/16

S 28 | S 27

1975

Dependent Resurvey, Portion of Subdivisional Lines,
T. 12 S., R. 19 W., Salt Lake Mer., Utah

CHAINS

from which

An aspen, 9 ins. diam., bears S. $15\frac{1}{2}^{\circ}$ E., 91 lks.
dist., mkd. N 1/16 S27 BT.

An aspen, 8 ins. diam., bears N. 32° W., 67 lks.
dist., mkd. N 1/16 S28 BT.

Cor. is located on N. edge of small rock slide.

22.80 Top of ascent, slopes W.; desc. over NW. slope.

29.00 Enter dense undergrowth, edge bears generally E. and W.

39.90 The cor. of secs. 21, 22, 27, and 28, monumented with a
basalt stone, 27 x 9 x 9 ins., firmly set, protruding
10 ins. above ground, in a mound of stone, $2\frac{1}{2}$ ft. base,
to top, with 3 grooves on E. face and 2 notches on S. edge.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in
the ground, in a collar of stone, 4 ft. base, to top, with
brass cap mkd.

T 12 S	R 19 W
S 21	S 22
S 28	S 27

1975

Deposit the original stone alongside the iron post.

Cor. is located in a downed barbed wire fence, 4 strands,
extending E. and W.

From the cor. of secs. 22, 23, 26, and 27.

N. $89^{\circ} 57'$ W., bet. secs. 22 and 27.

Asc. over steep E. slope, through light undergrowth.

25.70 Top of steep E. slope; continue to asc. over gentle
E. slope.

37.00 Ridge, bears generally N. and S.; desc. over gentle
W. slope; enter aspen and bristlecone pine timber.

39.94 The $\frac{1}{4}$ sec. cor. of secs. 22 and 27, monumented with a
granite stone, 15 x 12 x 6 ins., loosely set, protruding
3 ins. above a mound of stone, 3 ft. base, 1 ft. high,
mkd. $\frac{1}{4}$ S on N. face, from which the remaining original
bearing tree

An aspen, 6 ins. diam., bears S. 52° E., 54 lks.
dist., with scribe marks $\frac{1}{4}$ S2 visible on bark
blaze. (Record, S. 58° E., 57 lks.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in
the ground, to bedrock, in a mound of stone, 3 ft. base,
to top, with brass cap mkd.

556

Dependent Resurvey, Portion of Subdivisional Lines,
T. 12 S., R. 19 W., Salt Lake Mer., Utah

CHAINS

T 12 S R 19 W

GIR

$$\frac{1}{4} \begin{array}{r} S 22 \\ S 27 \end{array}$$

1975

Deposit the original stone alongside the iron post.

S. 89° 57' W., beginning new measurement.

Desc. over steep W. slope, through heavy aspen and dense undergrowth.

20.04 Point for the W. 1/16 sec. cor. of secs. 22 and 27.

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

GIR

$$\begin{array}{r} W 1/16 \\ GIR \end{array} \begin{array}{r} S 22 \\ S 27 \end{array}$$

1975

from which

An aspen, 6 ins. diam., bears N. 65° E., 29 lks. dist., mkd. W 1/16 S22 BT.

An aspen, 8 ins. diam., bears S. 36° E., 34 lks. dist., mkd. W 1/16 S27 BT.

30.20 Leave aspen timber, edge bears generally N. and S.; enter scattering sagebrush.

39.10 Dirt road, 10 lks. wide, bears N. 15° E. and S. 15° W.; continue descent through dense chokecherry undergrowth.

40.08 The cor. of secs. 21, 22, 27, and 28.

From the ¼ sec. cor. of secs. 32 and 33, monumented with an iron post, 1 in. diam., firmly set, protruding 15 ins. above ground, in a scattered mound of stone, 2½ ft. base, 6 ins. high, with brass cap mkd. as described in the official record of the 1916 survey of a portion of the subdivisional lines of T. 12 S., R. 19 W.

Rebuild mound of stone surrounding the iron post, 3 ft. base, to top, and add the marks T12S R19W 1975 on the brass cap.

North, bet. secs. 32 and 33.

Asc. over steep SW. slope, through sagebrush.

9.20 Ridge, bears N. 10° E. and S.; continue to asc. along ridge.

19.995 Point for the N. 1/16 sec. cor. of secs. 32 and 33.

Set an iron post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, in a collar of stone, 2½ ft. base, to top, with brass cap mkd.

Dependent Resurvey, Portion of Subdivisional Lines,
T. 12 S., R. 19 W., Salt Lake Mer., Utah

CHAINS		
	N 1/16 S 32 S 33 1975	
37.50	Ridge, bears N. 70° W. and S. 70° E.; desc. over gentle N. slope.	
39.99	<p>The cor. of secs. 28, 29, 32, and 33, monumented with an iron post, 2 ins. diam., firmly set, protruding 15 ins. above the ground, in a scattered mound of stone, 2½ ft. base, 6 ins. high, with brass cap mkd. as described in the official record of the 1916 survey of a portion of the subdivisional lines of T. 12 S., R. 19 W.</p> <p>Rebuild the mound of stone surrounding the iron post, 4 ft. base, to top, and add the marks GIR 1975 on the brass cap.</p>	
	<p>From the ¼ sec. cor. of secs. 28 and 33, monumented with an iron post, 1 in. diam., firmly set, protruding 8 ins. above the ground, with brass cap mkd. as described in the official record of the 1916 survey of a portion of the subdivisional lines of T. 12 S., R. 19 W., from which the original bearing trees</p> <p style="padding-left: 40px;">An aspen, 11 ins. diam., bears North, 13 lks. dist., with healed blaze. (Record, 12 lks.)</p> <p style="padding-left: 40px;">An aspen, 8 ins. diam., bears S. 85° E., 10 lks. dist., with healed blaze.</p> <p>Add the marks T12S R19W 1975 on the brass cap.</p> <p>S. 89° 54' W., bet. secs. 28 and 33.</p> <p>Desc. along N. slope, through heavy aspen timber and dense undergrowth.</p>	
12.60	Bottom of descent, slopes N.; asc. along N. slope.	
19.98	<p>Point for the W. 1/16 sec. cor. of secs. 28 and 33.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.</p>	
	GIR W 1/16 $\frac{S\ 28}{S\ 33}$ GIR 1975	
	<p>from which</p> <p style="padding-left: 40px;">An aspen, 11 ins. diam., bears S. 16½° W., 104 lks. dist., mkd. W 1/16 S33 BT.</p> <p style="padding-left: 40px;">An aspen, 12 ins. diam., bears N. 25° W., 84 lks. dist., mkd. W 1/16 S28 BT.</p> <p>Cor. is located in the center of a dirt road, 15 lks. wide, bears N. 45° W. and S. 45° E.</p>	
25.20	Leave aspen timber, edge bears N. and S.; slope, changes to NE. slope.	
39.96	The cor. of secs. 28, 29, 32, and 33.	

558

Dependent Resurvey, Portion of Subdivisional Lines,
T. 12 S., R. 19 W., Salt Lake Mer., Utah

CHAINS													
7.00	<p>N. 89° 55' W., bet. secs. 29 and 32. Asc. over NE. slope, through moderate sagebrush.</p>												
35.00	<p>Ridge, bears N. 60° W. and S. 70° E.; desc. over SW. slope.</p>												
40.06	<p>Continue descent over steep and rocky ledges.</p> <p>The ¼ sec. cor. of secs. 29 and 32, monumented with an iron post, 1 in. diam., firmly set, protruding 5 ins. above a mound of stone, 2 ft. base, 10 ins. high, with brass cap mkd. as described in the official record of the 1916 survey of a portion of the subdivisional lines of T. 12 S., R. 19 W.</p> <p>Rebuild the mound of stone surrounding the iron post, 3 ft. base, to top, and add the marks GIR T12S R19W 1975 on the brass cap.</p> <p>Cor. is located on S. toe of quartz cliff, 40 ft. high, and 12 ft. above rocky ravine, drains S.</p>												
1.10	<p>From the ¼ sec. cor. of secs. 29 and 30, monumented with an iron post, 1 in. diam., loosely set, protruding 20 ins. above ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd. as described in the official record of the 1916 survey of a portion of the subdivisional lines of T. 12 S., R. 19 W.</p> <p>Rebuild the mound of stone surrounding the iron post, 4 ft. base, to top, and add the marks GIR T12S R19W 1975 on the brass cap.</p> <p>N. 0° 09' E., bet. secs. 29 and 30. Asc. over S. slope, through sagebrush.</p>												
15.50	<p>Ridge, bears N. 80° W. and S. 80° E.; desc. over N. slope.</p>												
40.11	<p>Enter heavy aspen timber, edge bears generally E. and W.</p> <p>The cor. of secs. 19, 20, 29, and 30, monumented with an iron post, 2 ins. diam., firmly set, protruding 8 ins. above a mound of stone, 2 ft. base, 1 ft. high, with brass cap erroneously mkd. in 1916. Add the marks S19 S20 75; the brass cap is now mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">GIR</td></tr> <tr><td>S 19</td><td>S 20</td></tr> <tr><td>S 30</td><td>S 29</td></tr> <tr><td>T 12 S</td><td>R 19 W</td></tr> <tr><td colspan="2">75</td></tr> <tr><td colspan="2">1916</td></tr> </table> </div> <p>from which bearing trees mkd. by H. L. Baldwin in 1914</p> <p>A spruce, 13 ins. diam., bears N. 3¾° E., 46 lks. dist., with healed blaze.</p> <p>A spruce, 15 ins. diam., bears S. 62¼° E., 84 lks. dist., with scribe marks S R19W S29 BT visible on partially healed blaze. (Record, 96 lks.)</p> <p>A spruce, 15 ins. diam., bears S. 64¾° W., 28 lks. dist., with healed blaze.</p> <p>A spruce, 20 ins. diam., bears N. 53° W., 44 lks. dist., with scribe marks T12S R19W S19 BT visible on partially healed blaze.</p> <p>Rebuild the mound of stone surrounding the iron post, 4 ft. base, to top.</p> <p>Cor. is located in downed barb wire fence, 4 strands, extending E. and W.</p>	GIR		S 19	S 20	S 30	S 29	T 12 S	R 19 W	75		1916	
GIR													
S 19	S 20												
S 30	S 29												
T 12 S	R 19 W												
75													
1916													

Dependent Resurvey, Portion of Subdivisional Lines,
T. 12 S., R. 19 W., Salt Lake Mer., Utah

883

CHAINS	
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 20 and 29, monumented with a quartzite stone, 12 x 12 x 4 ins., firmly set, protruding 5 ins. above ground, mkd. $\frac{1}{4}$ S on N. face, from which the remains of the original bearing trees</p> <p>A root hole, bears S. 36° E., 22 lks. dist., with an aspen lying alongside, 18 ins. diam., with no visible blaze.</p> <p>A spruce, 22 ins. diam., bears N. 47$\frac{1}{4}$° W., 100 lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 12 S R 19 W</p> <p> GIR</p> <p> $\frac{1}{4}$ $\frac{S 20}{S 29}$</p> <p> GIR</p> <p> 1975</p> </div> <p>from which a new bearing tree</p> <p>An aspen, 10 ins. diam., bears S. 62° W., 8 lks. dist., mkd. $\frac{1}{4}$ S29 BT.</p> <p>Deposit the original stone alongside the iron post.</p> <p>S. 89° 41' W., bet. secs. 20 and 29.</p> <p>Asc. along N. slope, through scattering timber and dense undergrowth.</p>
17.50	Top of ascent, slopes N.; desc. over NW. slope, through heavy aspen and pine timber.
33.00	Ravine, drains N. 30° E.; asc. over SE. slope.
38.10	Ridge, bears generally N. and S.; desc. over gentle W. slope.
40.09	The cor. of secs. 19, 20, 29, and 30.
<p>Survey of the Subdivision of Section 27, T. 12 S., R. 19 W., Salt Lake Meridian, Utah</p>	
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 27 and 34.</p> <p>N. 0° 01' E., along the N. and S. center line of sec. 27.</p> <p>Desc. over NE. slope, through heavy aspen and bristlecone pine and moderate undergrowth.</p>
11.50	Dirt road, 10 lks. wide, bears E. and W.
12.60	Bottom of descent, slopes E.; asc. over steep, rocky SE. slope.
40.12	Point for the center $\frac{1}{4}$ sec. cor. of sec. 27, at intersection with the E. and W. center line of sec. 27.
	<p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 15 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

560

Survey of Subdivision of Sec. 27,
T. 12 S., R. 19 W., Salt Lake Mer., Utah

CHAINS

T 12 S. R 19 W
C ¼ S 27
GIR
1975

Asc. over W. slope.

60.05 Point for the center N. 1/16 sec. cor. of sec. 27.

Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

C
N 1/16 | S 27
GIR |
C
1975

from which

A bristlecone pine, 6 ins. diam., bears S. 27° E., 87 lks. dist., mkd. X at breast height and BT at base.

An aspen, 5 ins. diam., bears N. 81½° W., 35 lks. dist., mkd. CN 1/16 S27 BT.

79.98 The ¼ sec. cor. of secs. 22 and 27.

From the ¼ sec. cor. of secs. 26 and 27, monumented with a granite stone, 16 x 8 x 8 ins., loosely set, protruding 12 ins. above ground, in a scattered mound of stone, mkd. 4 S. on W. face, with a mound of stone, 3 ft. base, 2 ft. high, 6 lks. W. of cor.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground, to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.

T 12 S R 19 W
¼
S. 27 | S 26
1975

Deposit the original stone alongside the iron post.

S. 89° 59' W., along the E. and W. center line of sec. 27.

Asc. over steep E. slope, through scattering aspen and dense sagebrush.

34.40 Ridge, bears N. 10° W. and S. 10° E.; desc. over steep, rocky W. slope, through bristlecone pine timber.

38.20 Foot of steep descent; continue to desc. over gentle W. slope; leave timber, edge bears N. and S.

40.01 The center ¼ sec. cor. of sec. 27.

60.02 Point for the center W. 1/16 sec. cor. of sec. 27.

Survey of Subdivision of Sec. 27,
T. 12 S., R. 19 W., Salt Lake Mer., Utah

CHAINS	
80.03	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">W 1/16 C ————— C S 27 1975</p> <p>Continue to desc. over gentle W. slope, through sagebrush.</p> <p>The ¼ sec. cor. of secs. 27 and 28.</p>
19.93	<p>From the center W. 1/16 sec. cor. of sec. 27.</p> <p>N. 0° 03' W., along the N. and S. center line of the NW¼ of sec. 27.</p> <p>Asc. over SW. slope, through scattering timber and dense sagebrush.</p> <p>Point for the NW. 1/16 sec. cor. of sec. 27, at intersection with the E. and W. center line of the NW¼ of sec. 27.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S 17 GIR 1975</p> <p>Continue to ascend over SW. slope.</p>
35.50	Enter heavy timber, edge bears E. and W.
39.88	The W. 1/16 sec. cor. of secs. 22 and 27.
14.00	<p>From the center N. 1/16 sec. cor. of sec. 27.</p> <p>S. 89° 57' W., on the E. and W. center line of the NW¼ of sec. 27.</p> <p>Desc. over W. slope, through heavy aspen and dense undergrowth.</p> <p>Leave heavy aspen, edge bears N. and S.; continue to desc. over rocky W. slope, through dense sagebrush.</p>
20.04	The NW. 1/16 sec. cor. of sec. 27.
35.00	Enter heavy aspen, edge bears N. and S.
40.06	The N. 1/16 sec. cor. of secs. 27 and 28.
	<p>Survey of the Subdivision of Section 29, T. 12 S., R. 19 W., Salt Lake Meridian, Utah</p>
	<p>From the ¼ sec. cor. of secs. 29 and 32.</p> <p>North, along the N. and S. center line of sec. 29.</p> <p>Asc. over rock ledges.</p>

562

Survey of Subdivision of Sec. 29,
T. 12 S., R. 19 W., Salt Lake Mer., Utah

CHAINS	
3.00	Leave rock ledges, edge bears E. and W.; continue to asc. over SW. slope, through dense sagebrush.
4.00	Top of ascent, slopes SW.; desc. over SW. slope.
39.99	Point for the center $\frac{1}{4}$ ' sec. cor. of sec. 29, at intersection with the E. and W. center line of sec. 29. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, in a collar of stone, $2\frac{1}{2}$ ft. base, to top, with brass cap mkd. <div style="text-align: center;"> T 12 S R 19 W C $\frac{1}{4}$ S 29 G 1975 I R </div>
80.26	Continue to desc. over W. slope. The $\frac{1}{4}$ sec. cor. of secs. 20 and 29. <hr/> From the $\frac{1}{4}$ sec. cor. of secs. 28 and 29, monumented with an iron post, 1 in. diam.; firmly set, protruding 14 ins. above ground, in a scattered mound of stone, with brass cap mkd. as described in the official record of the 1916 survey of a portion of the subdivisional lines of T. 12 S., R. 19 W., from which the remains of the original bearing trees A root hole, bears S. 80° E., 10 lks. dist., with a fir lying alongside, size indeterminate, with scribe marks $\frac{1}{4}$ S28 BT visible on open blaze. (Record, pine) A root hole, bears West, 10 lks. dist., with a fir lying alongside, size indeterminate, with scribe marks $\frac{1}{4}$ S29 BT visible on open blaze. (Record, pine) and new bearing trees A fir, 10 ins. diam., bears S. 55° E., 28 lks. dist., mkd. $\frac{1}{4}$ S28 BT. A fir, 17 ins. diam., bears S. 80° W., 33 lks. dist., mkd. $\frac{1}{4}$ S29 BT. Rebuild the mound of stone surrounding the iron post, 4 ft. base, to top, and add the marks T12S R19W 1975 on the brass cap. S. $89^{\circ} 54'$ W., along the E. and W. center line of sec. 29. Asc. over NE. slope, through heavy fir and aspen and moderate undergrowth.
28.50	Leave timber, edge bears N. and S., top of ascent, slopes N.; desc. over SW. slope, through moderate sagebrush.
40.06	The center $\frac{1}{4}$ sec. cor. of sec. 29. Continue to desc. over SW. slope.
60.30	Bottom of descent, slopes S.; asc. over SE. slope.
80.25	The $\frac{1}{4}$ sec. cor. of secs. 29 and 30.

Survey of the Subdivision of Section 30,
T. 12 S., R. 19 W., Salt Lake Meridian, Utah

CHAINS	
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 30 and 31, monumented with an iron post, 1 in. diam., firmly set, protruding 6 ins. above ground, in a scattered mound of stone, with brass cap mkd. as described in the official record of the 1916 survey of a portion of the subdivisional lines of T. 12 S., R. 19 W.</p> <p>Rebuild the mound of stone surrounding the iron post, 4 ft. base, to top, and add the marks T12S R19W 75 on the brass cap.</p> <p>N. $0^{\circ} 04'$ E., along the N. and S. center line of sec. 30.</p> <p>Asc. over SW. slope, through dense sagebrush undergrowth.</p>
6.40	Spur ridge, N. 70° W. and S. 70° E.; desc. along NE. slope.
32.50	Dirt road, bears N. 70° W. and S. 70° E.; continue over nearly level land.
37.30	Enter timber, edge bears generally E. and W.
40.02	<p>Point for the center $\frac{1}{4}$ sec. cor. of sec. 30, at intersection with the E. and W. center line of sec. 30.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 12 S R 19 W GIR C $\frac{1}{4}$ S 30</p> <p style="text-align: center;">1975</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 14 ins. diam., bears N. 73° E., 82 lks. dist., mkd. C$\frac{1}{4}$ S30 BT.</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears N. 31° W., $7\frac{1}{2}$ lks. dist., mkd. C$\frac{1}{4}$ S30 BT.</p> <p>Desc. over steep NE. slope, through heavy fir, pine, and aspen timber and moderate undergrowth.</p>
60.05	<p>Point for the center N. $1/16$ sec. cor. of sec. 29.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, in a collar of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;"> C GIR S 30 N 1/16 C</p> <p style="text-align: center;">1975</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears S. 69° E., 26 lks. dist., mkd. CN $1/16$ S30 BT.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 4° W., 14 lks. dist., mkd. CN $1/16$ S30 BT.</p> <p>Continue to desc. over NE. slope.</p>

564

Survey of Subdivision of Sec. 30,
T. 12 S., R. 19 W., Salt Lake Mer., Utah

CHAINS
80.08

The $\frac{1}{4}$ sec. cor. of secs. 19 and 30, monumented with a conglomerate stone, 16 x 12 x 4 ins., firmly set, protruding 4 ins. above ground, faintly mkd. $\frac{1}{4}$ on N. face, from which the remains of the original bearing trees

A spruce stump, 13 ins. diam., bears S. 25° E., 5 lks. dist., mkd. $\frac{1}{4}$ S30 BT on partially healed blaze.

A root hole, bears N. 38 $\frac{1}{2}$ ° W., 30 lks. dist., with a spruce lying alongside, 10 ins. diam., with scribe marks $\frac{1}{4}$ S19 BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 23 ins. in the ground, with brass cap mkd.

T 12 S R 19 W
 $\frac{1}{4}$ $\frac{S 19}{S 30}$

1975

from which new bearing trees

A pine, 10 ins. diam., bears N. 20° E., 45 lks. dist., mkd. $\frac{1}{4}$ S19 BT.

A fir, 12 ins. diam., bears S. 25° W., 27 lks. dist., mkd. $\frac{1}{4}$ S30 BT.

From the $\frac{1}{4}$ sec. cor. of secs. 29 and 30.

N. 89° 57' W., along the E. and W. center line of sec. 30.

Asc. over gentle E. slope, through dense sagebrush.

1.50 Top of ascent, slopes N.; desc. over NW. slope.

11.00 Bottom of descent, slopes N.; asc. over E. slope.

12.10 Dirt road, 10 lks. wide, bears N. 15° E. and S. 15° W.

31.80 Ridge, bears generally N. and S.; desc. over W. slope; enter timber, edge bears N. and S.

40.06 The center $\frac{1}{4}$ sec. cor. of sec. 30.

45.00 Bottom of descent, slopes N.; asc. over E. slope.

57.00 Slope changes to S. slope; continue to asc. along S. slope, through dense mountain mahogany undergrowth.

77.97 The $\frac{1}{4}$ sec. cor. of secs. 25 and 30, on the W. bdy. of the Tp., hereinbefore described.

From the center N. 1/16 sec. cor. of sec. 29.

N. 89° 58' W., along the E. and W. center line of the NW $\frac{1}{4}$ of sec. 30.

Asc. over steep E. slope, through heavy timber and moderate undergrowth.

432

Survey of Subdivision of Sec. 30,
T. 12 S., R. 19 W., Salt Lake Mer., Utah

CHAINS 37.93	<p>The N. 1/16 sec. cor. of secs. 25 and 30, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p style="text-align: center;">Survey of the Subdivision of Section 33, T. 12 S., R. 19 W., Salt Lake Meridian, Utah</p> <hr/> <p>From the $\frac{1}{4}$ sec. cor. of sec. 33 only, on the S. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, protruding 16 ins. above ground, in a scattered mound of stone, with brass cap mkd. in 1915 as the $\frac{1}{4}$ sec. cor. of secs. 4 and 33. Change the marks so the brass cap is now mkd.</p> <p style="text-align: center;">T 12 S R 19 W $\frac{1}{4}$ S 33 ----- T 13 S R 19 W</p> <p style="text-align: center;">1975 1915</p> <p>Rebuild the mound of stone surrounding the iron post, 3 ft. base, to top.</p> <p>North, along the N. and S. center line of sec. 33.</p> <p>Asc. over SW. slope, through dense sagebrush.</p>
39.92	<p>Point for the center $\frac{1}{4}$ sec. cor. of sec. 33, at intersection with the E. and W. center line of sec. 33.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 23 ins. in the ground, in a collar of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 12 S R 19 W GIR C $\frac{1}{4}$ S 33</p> <p style="text-align: center;">1975</p> <p>Continue to asc. over SW. slope.</p>
59.91	<p>Point for the center N. 1/16 sec. cor. of sec. 33.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 23 ins. in the ground, in a collar of stone, $2\frac{1}{2}$ ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;"> G C I N 1/16 S 33 R C</p> <p style="text-align: center;">1975</p>
60.20	Top of ascent, slopes W.; desc. over NW. slope.
73.20	Enter aspen timber, edge bears generally E. and W.
79.90	The $\frac{1}{4}$ sec. cor. of secs. 28 and 33.
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 33 and 34.</p> <p>S. $89^{\circ} 51'$ W., along the E. and W. center line of sec. 33.</p> <p>Desc. over SW. slope, through moderate fir and aspen and moderate undergrowth.</p>
4.50	Leave timber, edge bears generally N. and S.; continue to desc. over SW. slope, through dense sagebrush.
39.91	The center $\frac{1}{4}$ sec. cor. of sec. 33.

566

Survey of Subdivision of Sec. 33,
T. 12 S., R. 19 W., Salt Lake Mer., Utah

CHAINS	
59.87	<p>Continue to desc. over SW. slope, through light sagebrush.</p> <p>Point for the center W. 1/16 sec. cor. of sec. 33.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, in a collar of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">W 1/16 C ————— C S 33 1975</p>
60.50	<p>Continue to desc. over SW. slope, through light sagebrush undergrowth.</p> <p>Ravine, drains S.; asc. over E. slope, through light sagebrush.</p>
74.30	<p>Spur, slopes S.; desc. over W. slope, through light sagebrush.</p>
79.83	<p>The ¼ sec. cor. of secs. 32 and 33.</p>
5.00	<p>From the center W. 1/16 sec. cor. of sec. 33.</p> <p>N. 0° 01' W., along the N. and S. center line of the NW¼ of sec. 33.</p> <p>Asc. over SW. slope, through light sagebrush.</p> <p>Continue to asc. over SE. slope.</p>
19.99	<p>Point for the NW. 1/16 sec. cor. of sec. 33, at intersection with the E. and W. center line of the NW¼ of sec. 33.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">GIR NW 1/16 S 33 1975</p>
24.60	<p>Continue to asc. over SE. slope, through light sagebrush.</p> <p>Spur, slopes S. 70° W.; desc. over N. slope, through light sagebrush.</p>
35.00	<p>Enter light aspen timber, edge bears generally E. and W.</p>
40.00	<p>The W. 1/16 sec. cor. of secs. 28 and 33.</p>
18.50	<p>From the center N. 1/16 sec. cor. of sec. 33.</p> <p>S. 89° 51' W., along the E. and W. center line of the NW¼ of sec. 33.</p> <p>Desc. over SW. slope, through light sagebrush.</p> <p>Continue to desc. over SE. slope, through light sagebrush.</p>
19.98	<p>The NW. 1/16 sec. cor. of secs. 32 and 33.</p> <p>Continue to desc. along SE. slope, through light undergrowth.</p>

Survey of Subdivision of Sec. 33,
T. 12 S., R. 19 W., Salt Lake Mer., Utah

CHAINS 39.98	<p>The N. 1/16 sec. cor. of secs. 32 and 33.</p> <hr/> <p style="text-align: center;">Survey of the Subdivision of Section 35, T. 12 S., R. 19 W., Salt Lake Meridian, Utah</p> <hr/> <p>From the 1/4 sec. cor. of sec. 35 only, on the S. bdy. of the Tp.</p> <p>N. 0° 01' W., along the N. and S. center line of sec. 35.</p> <p>Desc. over steep N. slope, through heavy fir and spruce and light undergrowth.</p>
20.065	<p>Point for the center S. 1/16 sec. cor. of sec. 35.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, 2½ ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} C \\ \\ S\ 1/16 \quad \quad S\ 35 \\ \\ C \end{array}$ <p>1975</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears S. 54¼° E., 42 lks. dist., mkd. CS 1/16 S35 BT.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 23° W., 9½ lks. dist., mkd. CS 1/16 S35 BT.</p> <p>Continue to desc. over steep N. slope, through heavy fir and spruce and light undergrowth.</p>
40.13	<p>Point for the center 1/4 sec. cor. of sec. 35, at intersection with the E. and W. center line of sec. 35.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, in a collar of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} T\ 12\ S \quad R\ 19\ W \\ \\ C\ 1/4 \\ S\ 35 \\ \\ 1975 \end{array}$ </div> <p>Continue to desc. over steep N. slope, through heavy timber and light undergrowth.</p>
48.10	<p>Creek, 5 lks. wide, course N. 60° E.; asc. steep, rocky S. slope; leave timber, edge bears generally E. and W.; continue through dense undergrowth.</p>
52.00	<p>Ridge, bears generally E. and W.; desc. over steep, rocky N. slope.</p>
60.50	<p>Creek, 5 lks. wide, course S. 60° E.; asc. over steep N. slope, through light sagebrush.</p>
79.97	<p>The 1/4 sec. cor. of secs. 26 and 35, monumented with an iron post, 1 in. diam., firmly set, protruding 30 ins. above ground, in a mound of stone, 4½ ft. base, to top, with brass cap mkd. as described in the official record of the 1916 survey of a portion of the subdivisional lines of T. 12 S., R. 19 W., from which the remains of the original bearing trees</p>

568

Survey of Subdivision of Sec. 35,
T. 12 S., R. 19 W., Salt Lake Mer., Utah

CHAINS	<p>A pinon stump, size indeterminate, bears N. 14° E., 48 lks. dist., with a pinon log lying alongside, 6 ins. diam., with burned out blaze.</p> <p>A down pinon, 20 ins. diam., bears S. 7½° E., 142 lks. dist., with no marks visible on burned out, open blaze.</p> <p>Add the marks T12S R19W on the brass cap.</p>
	<p>From the ¼ sec. cor. of secs. 35 and 36, monumented with an iron post, 1 in. diam., firmly set, protruding 10 ins. above ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd. as described in the official record of the 1916 survey of a portion of the subdivisional lines of T. 12 S., R. 19 W., from which the original bearing trees</p>
	<p>A pine, 10 ins. diam., bears N. 43° E., 14 lks. dist., mkd. ¼ S36 BT visible on partially healed blaze.</p>
	<p>A pine, 9 ins. diam., bears N. 80° W., 17 lks. dist., with healed blaze.</p>
	<p>S. 89° 52' W., along the E. and W. center line of sec. 15. Desc. along steep N. slope, through heavy timber and light undergrowth.</p>
8.20	<p>Ravine, drains N.; asc. over NE. slope, through scattering timber and moderate undergrowth.</p>
20.20	<p>Top of ascent, slopes N.; desc. along steep N. slope.</p>
39.95	<p>The center ¼ sec. cor. of sec. 35.</p>
	<p>Continue to desc. along N. slope, through scattering timber and moderate undergrowth.</p>
48.50	<p>Creek, 5 lks. wide, course N. 65° E.; asc. over SE. slope, leave timber, edge bears N. 65° E. and S. 65° W., continue through light sagebrush.</p>
59.92	<p>Point for the center W. 1/16 sec. cor. of sec. 35.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">W 1/16 C ————— C GIR S 35 1975</p>
	<p>Continue to asc. over SE. slope, through light sagebrush.</p>
79.89	<p>The ¼ sec. cor. of secs. 34 and 35.</p>
	<p>From the W. 1/16 sec. cor. of sec. 35 only, on the S. bdy. of the Tp.</p>
	<p>N. 0° 01' W., along the N. and S. center line of the SW¼ of sec. 35.</p>

Survey of Subdivision of Sec. 35,
T 12 S., R. 19 W., Salt Lake Mer., Utah

CHAINS	
	Desc. over steep N. slope, through heavy timber and dense undergrowth.
20.03	<p>Point for the SW. 1/16 sec. cor. of sec. 35, at intersection with the E. and W. center line of the SW$\frac{1}{4}$ of sec. 35.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 2 ins. in the ground, to bedrock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S 35 GIR 1975</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 59$\frac{3}{4}$° E., 15 lks. dist., mkd. SW 1/16 S35 BT.</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears N. 50$\frac{1}{2}$° W., 15 lks. dist., mkd. X at breast height and BT at base.</p> <p>Continue to desc. over steep N. slope, through heavy timber and dense undergrowth.</p>
33.50	Creek, 5 lks. wide, course N. 70° E.; asc. over SE. slope, leave timber, edge bears N. 70° E. and S. 70° W.; continue through light sagebrush.
40.05	The center W. 1/16 sec. cor. of sec. 35.
	<p>From the center S. 1/16 sec. cor. of sec. 35.</p> <p>S. 89° 59' W., along the E. and W. center line of the SW$\frac{1}{4}$ of sec. 35.</p> <p>Desc. along steep broken N. slope, through heavy timber and dense undergrowth.</p>
19.96	<p>The SW. 1/16 sec. cor. of sec. 35.</p> <p>Continue along broken N. slope, through heavy timber and dense undergrowth.</p>
39.93	The S. 1/16 sec. cor. of secs. 34 and 35.
	<p style="text-align: center;">GENERAL DESCRIPTION</p> <p>Township 12 South, Range 19 West, is situated about 20 miles south southeast of Ibapah, Utah. The elevation varies from about 7,550 to 12,000 feet above sea level. The soil varies from sandy loam and decomposed granite to solid granite rock.</p> <p>There are numerous small streams draining the area. Access to the area is gained by small secondary dirt roads in the western portions of the township. The eastern portion of the township has no roads. Access is provided by small hiking trails up main ridges.</p> <p>The Queen of Sheba mine, now abandoned, is situated in the southeast $\frac{1}{4}$ of section 2. There are numerous deposits of gold, silver, and other valuable minerals, but most of these deposits are not of significant quantity to make mining practicable.</p>

570

T. 12 S., R. 19 W.; Salt Lake Mer., Utah

CHAINS

The vegetation consists of mountain mahogany, choke-cherry, buckbrush, sagebrush, meadow grass, and other native grass. The timber consists of pine, fir, spruce, aspen, and bristlecone pine.

572

CERTIFICATE OF SURVEY

(I) (~~WA~~), Terrence O. Nickerson, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 27th day of May, 1975, (I) (~~WA~~) have dependently resurveyed portions of the south and west boundaries and subdivisional lines, and surveyed the subdivision of sections 27, 29, 30, 33, and 35, Township 12 South, Range 19 West,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), (~~WA~~) and under (my) (~~WA~~) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

12/22/78 (Date) Terrence O. Nickerson (Cadastral Surveyor)

(Date) (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Washington, D.C. Denver, Colorado

The foregoing field notes of the dependent resurvey of portions of the south and west boundaries and subdivisional lines, and the survey of the subdivision of sections 27, 29, 30, 33, and 35, Township 12 South, Range 19 West, Salt Lake Meridian, Utah,

executed by Terrence O. Nickerson, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JAN 21 1980 (Date) J. J. Voorhees (Chief, Division of Cadastral Survey)

Chief, Cadastral Survey Examination and Approval Staff

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes.

(Date) (Chief, Division of Cadastral Survey) GPO 849-626

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

R599

573

FIELD NOTES

OF THE

RETRACEMENT OF

A PORTION OF THE NEVADA AND UTAH STATE BOUNDARY,

FROM MILE POST 109 TO MILE POST 108 + 7 CHAINS,

AND THE

DEPENDENT RESURVEY OF

A PORTION OF THE SUBDIVISIONAL LINES,

TOWNSHIP 12 SOUTH, RANGE 20 WEST,

Of the SALT LAKE Meridian,
In the State of UTAH

EXECUTED BY

Terrence O. Nickerson, Cadastral Surveyor

Under special instructions dated May 27, 19 75, approved June 6, 1975,

_____, which provided for the surveys included under U.S. Survey/Group
Number 564, and assignment instructions dated June 10, 1975.

Survey commenced June 24, 19 75

Survey completed September 5, 19 75

INDEX DIAGRAM

Township 12 South, Range 20 West,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24 2
30	29	28	27	26	25
31	32	33	34	35	36

Retracement, Nevada and Utah State Boundary..... pages 1-2

T. 12 S., R. 20 W., Salt Lake Meridian, Utah

CHAINS

The following field notes describe the retracement of the Nevada and Utah State Boundary from Mile Post 109 to Mile Post 108 + 7 chains, and the dependent resurvey of a portion of the subdivisional lines, Township 12 South, Range 20 West, Salt Lake Meridian, Utah.

The Nevada and Utah State Boundary was surveyed by I. E. James in 1871. In 1916, John W. Dougall resurveyed and retraced that portion of the Nevada and Utah State Boundary along the west boundary of fractional Township 12 South, Range 20 West, Salt Lake Meridian, and surveyed the subdivisional lines of fractional Township 12 South, Range 20 West. In 1922, Walter H. Good resurveyed the Nevada and Utah State Boundary from Mile Post 104 to Mile Post 110, along the east boundary of Township 22 North, Range 70 East, Mount Diablo Meridian, Nevada, and set closing corners for the Nevada side.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 564, Utah, dated May 27, 1975.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of lines were determined by direct solar observations and refer to the true meridian.

The letters GIR are marked on the brass caps of corners located on the Goshutes Indian Reservation boundary.

The geographic position of the corner of sections 19, 24, 25, and 30, as determined from a tie made to U.S.G.S. triangulation station "TROUT," in the SW $\frac{1}{4}$ of section 14, Township 12 South, Range 19 West, Salt Lake Meridian, Utah, is:

Latitude: 39° 45' 15" N. Longitude: 114° 02' 29" W.

The mean magnetic declination is 16 $\frac{1}{2}$ ° E.

Retracement of a Portion of the Nevada and Utah State Boundary, T. 12 S., R. 20 W., Salt Lake Meridian, Utah

(Retracing the survey executed by I. E. James in 1871, the retracement and resurvey executed by John W. Dougall in 1916, and the resurvey executed by Walter H. Good in 1922)

Beginning at Mile Post 109, on the Nevada and Utah State Boundary, monumented with an iron post, 3 ins. diam., loosely set, protruding 30 ins. above the ground, in a scattered mound of stone, 3 ft. base, 1 $\frac{1}{2}$ ft. high, with brass cap mkd. as described in the official record of the 1916 retracement and resurvey, with a wood post alongside, 6 ins. diam., with scribe marks UTAH visible on E. face and NEVADA on W. face.

Rebuild the mound of stone, 4 ft. base, 3 ft. high, around the iron post and reset wood post alongside iron post.

Retracement, Portion of Nevada and Utah State Bdy.,
T. 12 S., R. 20 W., Salt Lake Mer., Utah

CHAINS	
	N. 1° 01' W., along the Nevada and Utah State Boundary. Asc. over steep S. slope, through scattering timber and dense mountain mahogany undergrowth.
11.97	The closing cor. of secs. 24 and 25, hereinafter described.
12.10	Spur ridge, slopes W.; desc. over NW. slope.
12.90	The $\frac{1}{4}$ sec. cor. of sec. 27 only, on the E. bdy. of T. 22 N., R. 70 E., Mount Diablo Meridian, Nevada, monumented with an iron post, 1 in. diam., firmly set, protruding 12 ins. above the ground, with brass cap mkd. as described in the official record of the 1922 resurvey of the Nevada and Utah State Boundary.
41.00	Ravine, drains S. 80° E.; asc. over steep SE. slope.
70.70	Spur ridge, bears N. 60° W. and S. 60° E.; desc. over NE. slope.
71.22	Mile Post 108 + 7 chains, which is also the witness cor. to Mile Post 108, on the Nevada and Utah State Boundary, monumented with an iron post, 3 ins. diam., firmly set, protruding 2 ft. above ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd. as described in the official record of the 1916 retracement and resurvey of the Nevada and Utah State Boundary.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 12 S., R. 20 W., Salt Lake Meridian, Utah

(Restoring the survey executed by John W. Dougall in 1916)

From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., monumented with an iron post, 3 ins. diam., set, mkd., and witnessed as described in the field notes of the dependent resurvey of a portion of the W. bdy. of T. 12 S., R. 19 W., executed concurrently under this same group.

S. 89° 56' W., bet. secs. 24 and 25.

Asc. over rocky E. slope, through scattering mountain mahogany.

13.50 Spur ridge, bears N. 70° W. and S. 70° E.; desc. along SW. slope.

22.92 Intersect the Nevada and Utah State Boundary at the closing cor. of secs. 24 and 25, monumented with an iron post, 2 ins. diam., firmly set, protruding 3 ft. above the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd. as described in the official record of the 1916 survey of the subdivisional lines of fractional T. 12 S., R. 20 W.

from which original bearing trees

A mahogany, 11 ins. diam., bears N. 46 $\frac{1}{2}$ ° E.,
116 lks. dist., with scribe marks CC T12S R20W
S24 BT visible on open blaze.

A mahogany, 15 ins. diam., bears S. 60 $\frac{1}{2}$ ° E.,
103 lks. dist., with scribe marks CC T12S R20W
S25 BT visible on open blaze.

Dependent Resurvey, Portion of Subdivisional Lines,
T. 12 S., R. 20 W., Salt Lake Mer., Utah

CHAINS

Add the marks GIR on the brass cap.

From this cor. Mile Post 109, on the Nevada and Utah State Boundary, bears S. 1° 01' E., 11.97 chs. dist., hereinbefore described.

GENERAL DESCRIPTION

The area resurveyed within T. 12 S., R. 20 W., lies approximately 20 miles south of Ibapah, Utah. The terrain is very steep and mountainous; elevation varies from about 8,600 ft. to about 10,000 ft. above sea level. Drainage is provided by numerous small ravines and springs. The drainage is generally to the north. No roads of any kind were noted in the area.

579

CERTIFICATE OF SURVEY

(I) ~~(WA)~~, Terrence O. Nickerson, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 27th day of May, 1975, (I) ~~(WA)~~ have retraced a portion of the Nevada and Utah State Boundary, from Mile Post 109 to Mile Post 108 + 7 chains, and dependently resurveyed a portion of the subdivisional lines, Township 12 South, Range 20 West,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

12/22/78 (Date) Terrence O. Nickerson (Cadastral Surveyor)

(Date) (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Washington, D.C. Denver, Colorado

The foregoing field notes of the retracement of a portion of the Nevada and Utah State Boundary, from Mile Post 109 to Mile Post 108 + 7 chains, and the dependent resurvey of a portion of the subdivisional lines, Township 12 South, Range 20 West, Salt Lake Meridian, Utah, executed by Terrence O. Nickerson, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JAN 21 1980 (Date) J. J. [Signature] (Chief, Division of Cadastral Survey) Chief, Cadastral Survey Examination and Approval Staff

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes.

(Date) (Chief, Division of Cadastral Survey) GPO 849-626

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

580

R599

-15-

ORIGINAL
FIELD NOTES

OF THE
DEPENDENT RESURVEY
OF A
PORTION OF THE NORTH BOUNDARY OF T. 27 S., R. 2 $\frac{1}{2}$ W.,
AND A PORTION OF THE SUBDIVISIONAL LINES
OF
TOWNSHIP 26 SOUTH, RANGE 3 WEST

Of the Salt Lake Meridian,
In the State of Utah

EXECUTED BY

Ferrel D. Reynolds Cadastral Surveyor

Under the Supervision of

Glen B. Hatch, Acting Chief, Branch of Cadastral Survey

Under special instructions dated March 20, 19 75, approved March 24, 1975,

_____, which provided for the surveys included under U.S. Survey/Group
Number 558, and assignment instructions dated June 6, 1975.

Survey commenced June 10, 1975

Survey completed October 17, 1975

INDEX DIAGRAM

Township 26 S., Range 3 W.

27	27	16			
6 26	5 15	4 7	3	2	1
25	25	14			
7 24	8 13	9 6	10	11	12
23	23	12			
18 22	17 11	16 6	15	14	13
21	21	10			
19 20	20 10	21 5	22	23	24
19	18	9			
30 17	29 8	28 4	27	26	25
	3	2			
31	32	33	34	35	36

Dependent Resurvey of T. 26 S., R. 3 W.,
Salt Lake Meridian, Utah

CHAINS

T. 26 S., R. 3 W.

History of Surveys

Surveyed by Retr. or Resurveyed by

NORTH BOUNDARY (5th Stand. Par. S.)

W. 4 miles	A. D. Ferron	1878	
E. 2 miles	Page and Swan	1897	
S. bdys., secs. 33 & 34, (T. 25 S., R. 3 W.)			A. P. Hansen 1891
W. 4 miles			J. L. Thomas and Fred R. Chappell 1970- 1971

EAST BOUNDARY

S. 3.5 miles Breckon and McCarty
1897

WEST BOUNDARY

N. 3.5 miles	A. D. Ferron	1878	
S. 1.5 miles	J. T. Breckon	1896	
S. 1 mile			J. T. Breckon 1898
All			C. P. Sylvester 1975

SOUTH BOUNDARY

All Breckon and McCarty
1898

SUBDIVISIONS

N.W. portion	A. D. Ferron	1878	
Remaining portion			
	Breckon and McCarty	1898	
Portion			Breckon and McCarty 1898

The following field notes are those of a dependent resurvey of a portion of the north boundary of T. 27 S., R. 2½ W., and a portion of the subdivisional lines of T. 26 S., R. 3 W., Salt Lake Meridian, Utah.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated March 20, 1975.

The directions of the lines of this survey were determined by reference to true meridians established on line by hour angle observations on Polaris. They were carried forward by sustained angulation, being supplemented by numerous other observations on Polaris taken throughout the progress of the survey.

Before restoring lost corners, the lines of the original survey were retraced and a diligent search was made for any evidence of the original corners. The rules of proportionate measurement were applied to ascertain the position of the lost corner after every reasonable possibility of finding direct evidence of the corner had been exhausted.

583

Dependent Resurvey of T. 26 S., R. 3 W.,
Salt Lake Meridian, Utah

CHAINS

The geographic position for the southeast corner of section 28, as determined from a tie made to U.S.G.S. triangulation station "Flat Top, 1952" located in section 26, T. 26 S., R. 4 W., Salt Lake Meridian, is:

Latitude $38^{\circ}30'02.8''$ N. Longitude $112^{\circ}06'58.8''$ W.

The magnetic declination was read at a number of stations throughout the township and the average of the several readings was found to be $15\frac{1}{2}^{\circ}$ East.

Dependent Resurvey of a portion of the N. Bdy. of
T. 27 S., R. $2\frac{1}{2}$ W., Salt Lake Meridian, Utah

(Restoring the 1898 survey by Breckon and McCarty)

Beginning at the cor. of secs. 3, 4, 27, and 28, on the N. bdy. of the Tp., monumented with a granite stone, 18 x 10 x 4 ins., firmly set and plainly mkd. with 3 notches on E and W edges.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 S R 3 W	
S 28	S 27
S 4	S 3
T 27 S R $2\frac{1}{2}$ W	
1975	

Deposit the mkd. stone alongside the iron post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
N. $89^{\circ}58'$ W., bet. secs. 4 and 28.

Over mountainous land, through scattering patches of pine and aspen growth; desc. W slope.

9.50 Draw, drains NW.

39.36 The $\frac{1}{4}$ sec. cor. of secs. 4 and 28, monumented with a granite stone, 14 x 8 x 6 ins., firmly set and plainly mkd. $\frac{1}{4}$ on N face.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, $3\frac{1}{2}$ ft. base to top of brass cap, mkd.

T 26 S R 3 W	
$\frac{1}{4}$	S 28
	S 4
T 27 S R $2\frac{1}{2}$ W	
1975	

Dependent Resurvey of a portion of the N. Bdy. of
T. 27 S., R. 2½ W., Salt Lake Meridian, Utah

CHAINS									
	Deposit the mkd. stone alongside the iron post.								
	S. 89°54' W., beginning new measurement.								
9.00	Small spur, projecting N. 65° W.; continue to desc. W slope.								
39.57	The cor. of secs. 4, 5, 28, and 29, monumented with a granite stone, 14 x 8 x 6 ins., firmly set and plainly mkd. 4 notches on E and 2 on W edges.								
	At the corner point								
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T 26 S R 3 W</td></tr> <tr><td style="text-align: center;"> </td></tr> <tr><td>S 29 S 28</td></tr> <tr><td>S 5 S 4</td></tr> <tr><td style="text-align: center;"> </td></tr> <tr><td>T 27 S R 2½ W</td></tr> <tr><td style="text-align: center;">1975</td></tr> </table>	T 26 S R 3 W		S 29 S 28	S 5 S 4		T 27 S R 2½ W	1975	
T 26 S R 3 W									
S 29 S 28									
S 5 S 4									
T 27 S R 2½ W									
1975									
	Deposit the mkd. stone alongside the iron post.								
	Cor. is located at the cor. of fence projecting N, S and W.								
	S. 89°48' W., bet. secs. 5 and 29.								
	Over mountainous land, through pine, aspen, juniper and oak brush; desc. W slope.								
7.50	Trail road, bears NW and SE.								
22.00	Draw, drains NW.								
37.83	Intersect netwire fence bearing N and S.								
38.05	The cor. of Tps. 27 S., Rs. 2½ and 3 W., monumented with a sandstone, 16 x 12 x 10 ins., firmly set and plainly mkd. 6 notches on E, W, and S edges.								
	At the corner point								
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of brass cap, mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T 26 S R 3 W</td></tr> <tr><td style="text-align: center;"> </td></tr> <tr><td>S 29</td></tr> <tr><td>S 1 S 5</td></tr> <tr><td style="text-align: center;"> </td></tr> <tr><td>T 27 S</td></tr> <tr><td>R 3 W R 2½ W</td></tr> <tr><td style="text-align: center;">1975</td></tr> </table>	T 26 S R 3 W		S 29	S 1 S 5		T 27 S	R 3 W R 2½ W	1975
T 26 S R 3 W									
S 29									
S 1 S 5									
T 27 S									
R 3 W R 2½ W									
1975									
	Deposit the mkd. stone alongside the iron post.								

585

Dependent Resurvey of a portion of the N. Bdy. of
T. 27 S., R. 2½ W., Salt Lake Meridian, Utah

CHAINS

Cor. is located S. 53° W., 28 lks. dist., from cor. of
netwire fence bearing E and S.

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 26 S., R. 3 W., Salt Lake Meridian, Utah

(Restoring the 1898 survey by Breckon and McCarty)

From the cor. of secs. 3, 4, 27, and 28, on the S. bdy.
of the Tp.

N. 0°20' W., bet. secs. 27 and 28.

Over mountainous land, through scattering patches of pine,
aspen and oak brush, along W slope.

42.22 The ¼ sec. cor. of secs. 27 and 28, monumented with a
granite stone, 18 x 12 x 4 ins., firmly set and plainly
mkd. ¼ on W face, from which the remains of an original
bearing tree

An aspen, 8 ins. diam., bears S. 5° W., 18½ lks.
dist., mkd. ¼ S BT.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins.
in the ground to bedrock, in a mound of stone, 3 ft. base
to top of brass cap, mkd.

T 26 S R 3 W
 |
 ¼
 |
 S 28 | S 27
 |
 1975

Deposit the mkd. stone alongside the iron post.

Cor. is located in scattering pine and aspen growth.

N. 1°43' W., beginning new measurement.

24.00 Begin steep desc. of N slope.

39.51 The cor. of secs. 21, 22, 27, and 28, monumented with a
granite stone, 18 x 10 x 8 ins., firmly set and plainly
mkd. with 3 notches on E and 1 on S edges, from which the
remains of the original bearing trees

A spruce, 16 ins. diam., bears S. 34°45' E., 16 lks.
dist., mkd. T26S R3W S27 BT. (Record, 52 lks.)


A spruce, 12 ins. diam., bears S. 74°30' W., 5 lks.
dist., mkd. T26S R3W S28 BT. (Record, 50 lks.)

At the corner point

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 26 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.



Deposit the mkd. stone alongside the iron post.

Set a steel fence post alongside the iron post.

Cor. is located on steep NE slope of hill.


N. 1°25' W., bet. secs. 21 and 22.

Over mountainous land, through pine, aspen, and juniper growth; desc. NE slope.

30.00 Spur, projecting NE; desc. steep N slope.

39.69 Point selected for the witness ¼ sec. cor. of secs. 21 and 22.

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 6 ft. base to top of brass cap, mkd.




39.89 True point for the ¼ sec. cor. of secs. 21 and 22, at proportionate distance; there is no remaining evidence of the original cor. Cor. point falls on broken ledges and cannot be perpetuated.

61.00 Trail road in bottom of Dry Canyon, bears N. 50° W. and S. 50° E.; canyon drains N. 50° W.; asc. steep broken SW slope.

79.78 The cor. of secs. 15, 16, 21, and 22, monumented with a sandstone, 14 x 8 x 4 ins., loosely set, with no visible markings; witnessed by a mound of stone, W of cor.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of brass cap, mkd.



Dependent Resurvey of a portion of the Subdivisional Lines, T. 26 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
	<p>Deposit the unmkd. stone alongside the iron post. Cor. is located on steep broken S slope.</p>
	<p>N. 0°04' E., bet. secs. 15 and 16. Over mountainous land, through scattering pinon, juniper, and mahogany growth; asc. SW slope.</p>
23.00	Slope changes; asc. along SE slope.
39.53	<p>Point for the ¼ sec. cor. of secs. 15 and 16, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a collar of stone to top of brass cap, mkd.</p> <div style="text-align: center;"> <p>T 26 S R 3 W</p> <p>¼</p> <p> </p> <p>S 16 S 15</p> <p> </p> <p>1975</p> </div> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor. Cor. is located on NE slope of draw, draining SE; continue to asc.</p>
50.00	Ridge, bears E and W; desc. NW slope.
64.00	Draw, course NE; along E slope.
79.06	<p>The cor. of secs. 9, 10, 15, and 16, monumented with an old mound of stone, 3 ft. base, 1½ ft. high; no mkd. rock. This is accepted as the best available evidence of the original cor.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of brass cap, mkd.</p> <div style="text-align: center;"> <p>T 26 S R 3 W</p> <p> </p> <p>S 9 S 10</p> <p>S 16 S 15</p> <p> </p> <p>1975</p> </div> <p>Cor. is located on N slope of hill, in thick oak brush.</p>
	<p>N. 1°08' W., bet. secs. 9 and 10. Over mountainous land, through pinon, juniper and oak brush, along E slope.</p>
20.00	Cross ridge, bears NE and SW; desc. NW slope.

589

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 26 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
43.09	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of brass cap, mkd.</p> <div style="text-align: center;"> <p>T 26 S R 3 W</p> <p>$\frac{1}{4}$</p> <p> </p> <p>S 4 S 3</p> <p> </p> <p>1975</p> </div>
71.50	<p>Bottom of canyon, course N. 30° W.; continue along W slope.</p>
85.21	<p>Intersect the S. bdy. of sec. 34, T. 25 S., R. 3 W., (5th Standard Parallel South).</p> <p>Point for the closing cor. of secs. 3 and 4.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 25 S R 3 W</p> <p>S 34</p> <hr style="width: 50%; margin: auto;"/> <p>S 4 S 3</p> <p> </p> <p>C C</p> <p>T 26 S R 3 W</p> <p>1975</p> </div> <p>From this point the original closing cor. of secs. 3 and 4 bears N. $2^{\circ}38'$ E., 1.836 chs. dist., monumented with a granite stone, 14 x 12 x 4 ins., firmly set 8 ins. in the ground and mkd. with 3 notches on the E and W edges, CC on S face. Add the marks "AM" on S face.</p> <p>From this same point the standard cor. of secs. 33 and 34, T. 25 S., R. 3 W., bears S. $88^{\circ}55'$ W., 30.11 chs. dist., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set and mkd. as described in the 1970-71 resurvey of a portion of the Fifth Standard Parallel South.</p> <p>From this same point the standard $\frac{1}{4}$ sec. cor. of sec. 34, T. 25 S., R. 3 W., bears N. $88^{\circ}55'$ E., 9.94 chs. dist., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set and mkd. as described in the 1970-71 resurvey of a portion of the Fifth Standard Parallel South.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, S of cor.</p>
	<p>From the cor. of secs. 4, 5, 28, and 29, on the S. bdy. of the Tp.</p>

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 26 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
	N. 1°22' W., bet. secs. 28 and 29.
	Over mountainous land, through scattering pinon and juniper growth, along W slope.
13.80	Draw, drains NW.
30.00	Draw, drains NW; asc. SW slope.
42.85	Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.
	<div style="text-align: center;"> <p>T 26 S R 3 W</p> <p style="margin-left: 100px;"> </p> <p style="margin-left: 100px;">$\frac{1}{4}$</p> <p style="margin-left: 100px;"> </p> <p style="margin-left: 100px;">S 29 S 28</p> <p style="margin-left: 100px;"> </p> <p style="margin-left: 100px;">1975</p> </div>
43.00	Top of spur, projecting W; continue to asc. SW slope.
82.90	Point for the cor. of secs. 20, 21, 28, and 29, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, $3\frac{1}{2}$ ft. base to top of brass cap, mkd.
	<div style="text-align: center;"> <p>T 26 S R 3 W</p> <p style="margin-left: 100px;"> </p> <p style="margin-left: 100px;">S 20 S 21</p> <p style="margin-left: 100px;">S 29 S 28</p> <p style="margin-left: 100px;"> </p> <p style="margin-left: 100px;">1975</p> </div>
	Cor. is located on SW slope of hill, in scattering mahogany growth.
	From the cor. of secs. 21, 22, 27, and 28.
	N. 89°10' W., bet. secs. 21 and 28.
	Over mountainous land, through pine, aspen and juniper growth; asc. NE slope.
20.00	Top of spur, projecting N; desc. along NW slope.
39.77	Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.

Dependent Resurvey of a portion of the Subdivisional Lines, T. 26 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
	<p style="text-align: center;">T 26 S R 3 W</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S\ 21}{S\ 28}$</p> <p style="text-align: center;">1975</p> <p>79.54 The cor. of secs. 20, 21, 28, and 29.</p>
	<p>N. 0°50' E., bet. secs. 20 and 21.</p> <p>Over mountainous land, through pinon, juniper, and mahogany growth; asc. SW slope.</p> <p>10.25 Top of small peak; desc. along NW slope of mountain.</p> <p>40.04 Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 21, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of brass cap mkd.</p>
	<p style="text-align: center;">T 26 S R 3 W</p> <p style="text-align: center;">$\frac{1}{4}$</p> <p style="text-align: center;">S 20 S 21</p> <p style="text-align: center;">1975</p> <p>41.15 Bottom of draw, drains NW; asc. SW slope.</p> <p>54.00 Top of ridge, bears SE and NW; desc. NE slope.</p> <p>79.97 Point selected for the witness cor. of secs. 16, 17, 20, and 21.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 20 ins. in the ground, in a mound of stone, 4 ft. base to top of brass cap, mkd.</p>
	<p style="text-align: center;">T 26 S R 3 W</p> <p style="text-align: center;">W C</p> <p style="text-align: center;">↑</p> <p style="text-align: center;">$\frac{S\ 17}{S\ 20}$ $\frac{S\ 16}{S\ 21}$</p> <p style="text-align: center;">1975</p> <p>Cor. is located at S base of ledge outcrop, 15 ft. high, on steep E slope.</p> <p>80.08 The cor. of secs. 16, 17, 20, and 21, mkd. by a small mound of stone on rock outcrop; as described in the original survey, no mkd. rock found, point impractical to monument.</p> <p>From the cor. of secs. 15, 16, 21, and 22.</p>

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 26 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
	N. 88°55' W., bet. secs. 16 and 21.
	Over broken mountainous land, through pinon, juniper and mahogany growth; desc. along SW slope.
22.00	Trail road in bottom of Dry Canyon, bears NW and SE; canyon drains NW; asc. NE slope.
38.21	Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 21, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 6 ft. base to top of brass cap, mkd.
	T 26 S R 3 W
	$\frac{1}{4}$ $\frac{S 16}{S 21}$
	1975
46.00	Along broken N slope.
76.42	True point for the cor. of secs. 16, 17, 20, and 21.
	N. 2°22' W., bet. secs. 16 and 17.
	Over mountainous land, through pinon and juniper growth; desc. steep N slope.
15.00	Trail road in bottom of Dry Canyon, bears NW and SE, canyon drains NW; asc. steep SW slope.
40.28	Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 16 and 17.
	Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of brass cap, mkd.
	W C
	T 26 S R 3 W
	$\frac{1}{4}$ ↑
	S 17 S 16
	1975
40.68	True point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original cor. True point falls on broken W face of ledges and cannot be perpetuated.
68.00	Ridge, bears NE and SW; desc. NW slope.
81.36	Point for the closing cor. of secs. 16 and 17, and the 80 1/16 sec. cor. of sec. 9, at proportionate distance and on the S. bdy. of sec. 9, there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a portion of the Subdivisional Lines, T. 26 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS		
	<p style="text-align: center;">T 26 S R 3 W</p> <p style="text-align: center;"> $\frac{1/16 \text{ S } 9 \text{ 80}}{\text{S } 17 \quad \quad \text{S } 16}$ </p> <p style="text-align: center;">C C 1975</p> <p>From this cor., the cor. of secs. 9, 10, 15, and 16, bears S. 87°23' E., 79.90 chs. dist.</p> <p>From this sme point, the cor. of secs. 8 and 9, on the N. bdy. of sec. 17, bears N. 87°34' W., 21.44 chs. dist., hereinafter described.</p> <p>Cor. is located on steep W slope of hill.</p>	
	<p>From the cor. of secs. 9, 10, 15, and 16.</p> <p>N. 87°23' W., bet. secs. 9 and 16.</p> <p>Over mountainous land, through aspen, pinon, juniper and mahogany growth; asc. NE slope.</p>	
6.00	Ridge, bears N and S; desc. W slope.	
39.95	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 16, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 S R 3 W</p> <p style="text-align: center;"> $\frac{1}{4} \frac{\text{S } 9}{\text{S } 16}$ </p> <p style="text-align: center;">1975</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.</p> <p>Cor. is located in hollow, drains W.</p>	
79.90	<p>The closing cor. of secs. 16 and 17, and the 80 1/16 sec. cor. of sec. 9, previously described.</p> <p style="text-align: center;">_____</p> <p>N. 87°34' W., beginning new measurement.</p>	
7.00	Draw, drains SW.	
19.73	<p>Point for the 80 1/16 sec. cor. of sec. 17, on the S. bdy. of sec. 9, at proportionate distance from the W.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 S R 3 W</p> <p style="text-align: center;"> $\frac{1/16 \text{ S } 17 \text{ 80}}{\quad \quad \quad}$ </p> <p style="text-align: center;">1975</p>	

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 26 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

- 21.44 Raise a mound of stone, 3 ft. base, 2 ft. high, S of cor.
The cor. of secs. 8 and 9, on the N. bdy. of sec. 17,
monumented with a trachyte stone, 18 x 10 x 6 ins., firmly
set and plainly mkd. 4 notches on S and E edges.
At the corner point
Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins.
in the ground to bedrock, in a mound of stone, 3 ft. base
to top of brass cap, mkd.
- T 26 S R 3 W
|
S 8 | S 9
S 17
1975
- Deposit the mkd. stone in a mound alongside the iron post.
Cor. is located on SW slope of hill.
-
- N. 0°14' W., bet. secs. 8 and 9.
Over mountainous land, through scattering pinon and
juniper growth; asc. W slope.
- 8.50 Ridge, bears NW and SE; desc. along NW slope.
- 22.00 Spur, projects NW; continue to desc.
- 34.00 Draw, drains NW.
- 40.11 The ¼ sec. cor. of secs. 8 and 9, monumented with a
trachyte stone, 18 x 12 x 4 ins., firmly set and plainly
mkd. ¼ on W face.
At the corner point
Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins.
in the ground, in a collar of stone, to top of brass cap,
mkd.
- T 26 S R 3 W
¼
|
S 8 | S 9
|
1975
- Deposit the mkd. stone alongside the iron post.
Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
-
- N. 0°09' E., beginning new measurement.
- 21.00 Draw, drains NW.
- 40.00 The cor. of secs. 4, 5, 8, and 9, monumented with a por-
phyry stone, 18 x 10 x 4 ins., firmly set and plainly
mkd. with 5 notches on S and 4 on E edges.

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 26 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone to top of brass cap, mkd.

$$\begin{array}{c} \text{T 26 S R 3 W} \\ | \\ \text{S 5} \quad | \quad \text{S 4} \\ \text{S 8} \quad | \quad \text{S 9} \\ | \\ 1975 \end{array}$$

Deposit the mkd. stone alongside the iron post.

Cor. is located on gentle NW slope.

From the cor. of secs. 3, 4, 9, and 10.

N. 86°57' W., bet. secs. 4 and 9.

Over mountainous land, through pinon, juniper, mahogany and oak brush; desc. NW slope.

19.62

Point for the 80 1/16 sec. cor. of secs. 4 and 9, at proportionate distance.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{T 26 S R 3 W} \\ \\ 1/16 \frac{\text{S 4}}{\text{S 9}} 80 \\ \\ 1975 \end{array}$$

Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.

30.00

Slope changes; desc. along SW slope.

59.99

The ¼ sec. cor. of secs. 4 and 9, monumented with a trachyte stone, 18 x 12 x 6 ins., firmly set and plainly mkd. ¼ on W face.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of brass cap, mkd.

$$\begin{array}{c} \text{T 26 S R 3 W} \\ \\ \frac{1}{4} \frac{\text{S 4}}{\text{S 9}} \\ \\ 1975 \end{array}$$

Deposit the mkd. stone alongside the iron post.

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 26 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
<p>20.00</p> <p>21.50</p> <p>39.67</p>	<p>S. 89°44' W., beginning new measurement.</p> <p>Desc. W slope.</p> <p>Base of steep desc.; desc. gradual NW slope.</p> <p>Live Oak Canyon, drains NW.</p> <p>The cor. of secs. 4, 5, 8, and 9.</p>
<p>27.70</p> <p>40.39</p>	<p>N. 0°38' W., bet. secs. 4 and 5.</p> <p>Over rolling bench land, through sage and shadscale undergrowth; desc. gentle NW slope.</p> <p>Live Oak Canyon, 5 ft. deep, 50 lks. wide, drains N. 33° W.; continue gradual descent.</p> <p>The ¼ sec. cor. of secs. 4 and 5, monumented with a trachyte stone, 18 x 12 x 6 ins., firmly set and plainly mkd. ¼ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of brass cap, mkd.</p> <div style="text-align: center;"> <p>T 26 S R 3 W</p> <p> </p> <p> ¼</p> <p> </p> <p> S 5 S 4</p> <p> </p> <p> 1975</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p>
<p>40.30</p>	<p>N. 0°36' W., beginning new measurement.</p> <p>The closing cor. of secs. 4 and 5, on the S. bdy. of sec. 33, T. 25 S., R. 3 W., Fifth Standard Parallel South, monumented with a trachyte stone, 16 x 8 x 5 ins., firmly set and plainly mkd. with 4 notches on E and 2 on W edges, CC on S face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone to top of brass cap, mkd.</p> <div style="text-align: center;"> <p>T 25 S R 3 W</p> <p> </p> <p> S 33</p> <p> </p> <p> S 5 S 4</p> <p> </p> <p> C C</p> <p> T 26 S R 3 W</p> <p> 1975</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p>

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 26 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

From this point the standard cor. of secs. 32 and 33, T. 25 S., R. 3 W., bears S. 89°06' W., 5.70 chs. dist., monumented with an iron post, 2½ ins. diam., set and mkd. as described in the 1970-71 resurvey of a portion of the Fifth Standard Parallel South.

From this same point the standard ¼ sec. cor. of sec. 33, T. 25 S., R. 3 W., bears N. 89°06' E., 34.68 chs. dist., monumented with an iron post, 2½ ins. diam., set and mkd. as described in the 1970-71 resurvey of a portion of the Fifth Standard Parallel South.

The point for the ¼ sec. cor. of sec. 4 only, T. 26 S., R. 3 W., at proportionate distance, on the N. bdy. of sec. 4.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ S 4
 T 26 S R 3 W
 1975

Raise a mound of stone, 3 ft. base, 2 ft. high, S of cor.

From this point the standard cor. of secs. 33 and 34, T. 25 S., R. 3 W., bears N. 89°24' E., 10.81 chs. dist., monumented with an iron post, 2½ ins. diam., set and mkd. as described in the 1970-71 resurvey of a portion of the Fifth Standard Parallel South.

From this same point the standard ¼ sec. cor. of sec. 33, T. 25 S., R. 3 W., bears S. 89°24' W., 28.79 chs. dist., monumented with an iron post, 2½ ins. diam., set and mkd. as described in the 1970-71 resurvey of a portion of the Fifth Standard Parallel South.

The point for the 80 1/16 sec. cor. of sec. 4 only, T. 26 S., R. 3 W., at proportionate distance on the N. bdy. of sec. 4.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{16}$ S4 80
 T 26 S R 3 W
 1975

Raise a mound of stone, 3 ft. base, 2 ft. high, S of cor.

From this point the standard ¼ sec. cor. of sec. 33, T. 25 S., R. 3 W., bears N. 89°06' E., 12.12 chs. dist., monumented with an iron post, 2½ ins. diam., set and mkd. as described in the 1970-71 resurvey of a portion of the Fifth Standard Parallel South.

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 26 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
	<p>From the cor. of secs. 29 and 30, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set and mkd. as described in field notes of the concurrent resurvey of T. 26 S., R. 4 W.</p>
	<p>N. 0°06' E., bet. secs. 29 and 30.</p>
	<p>Over mountainous land, through pinon, juniper and mahogany growth; asc. SW slope.</p>
14.00	<p>Top of hill; desc. N slope.</p>
42.67	<p>Point for the ¼ sec. cor. of secs. 29 and 30, at proportionate distance; there is no remaining evidence of the original stone cor.</p>
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone to top of brass cap, mkd.</p>
	<div style="text-align: center;"> <p>T 26 S R 3 W</p> <p> </p> <p> ¼</p> <p> </p> <p> S 30 S 29</p> <p> </p> <p> 1975</p> </div>
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p>
59.00	<p>Bottom of small canyon, course NW; asc. along W slope.</p>
82.57	<p>Point for the original closing cor. of secs. 29 and 30, as determined from an original bearing tree</p> <p style="padding-left: 40px;">A juniper, 8 ins. diam., bears S. 49°35' W., 32 lks. dist., mkd. T26S R3W S30 BT.</p>
83.03	<p>Intersect the S. bdy. of sec. 20.</p> <p>Point for the closing cor. of secs. 29 and 30, falls in dirt road, bearing NW and SE and cannot be monumented.</p>
	<p>At exact cor. position, deposit broken glass, 12 ins. below surface of road.</p>
	<p>from which</p>
	<p style="padding-left: 40px;">An iron post, 30 ins. long, 2½ ins. diam., set 24 ins. in the ground with a mound of stone by cor. for reference monument, bears S. 68°44' E., 37.9 lks. dist., with brass cap mkd. T26S R3W CC S29 RM 25 FT. 1975 and an arrow pointing to the cor.</p>
	<p style="padding-left: 40px;">An iron post, 30 ins. long, 2½ ins. diam., set 24 ins. in the ground with a mound of stone to W, for reference monument, bears S. 42°26' W., 31.8 lks. dist., with brass cap mkd. T26S R3W CC S20 RM 21 FT. 1975 and an arrow pointing to the cor.</p>
	<p>From this point the cor. of secs. 19 and 20, on the N. bdy. of sec. 30, bears S. 89°58' W., 25.18 chs. dist., hereinafter described.</p>
	<p>From this same point the ¼ sec. cor. of sec. 20, bears N. 89°58' E., 14.90 chs. dist., hereinafter described.</p>

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 26 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
	From the cor. of secs. 20, 21, 28, and 29.
	S. 89°58' W., along the S. bdy. of sec. 20.
	Over mountainous land, through pinon, juniper and mahog- any growth; desc. broken W slope.
19.89	Point for the 80 1/16 sec. cor. of sec. 20, at propor- tionate distance.
	Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, in a mound of stone, 4 ft. base to top of brass cap, mkd.
	T 26 S R 3 W
	<u>1/16 S 20 80</u> 1975
39.08	Point for the ¼ sec. cor. of sec. 29, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.
	T 26 S R 3 W
	<u>¼ S 29</u> 1975
63.26	Point for the ¼ sec. cor. of sec. 20, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T 26 S R 3 W
	<u>¼ S 20</u> 1975
	from which
	A pinon, 12 ins. diam., bears N. 11° W., 21 lks. dist., mkd. ¼ S20 BT.
74.00	Draw, drains NW.
78.16	The closing cor. of secs. 29 and 30, heretofore described.
103.34	Point for the cor. of secs. 19 and 20, on the N. bdy. of sec. 30, determined latitudinally by record dist. from the N and longitudinally by proportionate measurement E and W.
	Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground, in a mound of stone, 3 ft. base to top of brass cap, mkd.

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 26 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

T 26 S R 3 W

S 19	S 20
S 30	

1975

N. 89°58' W., along N. bdy. of sec. 30, beginning new measurement.

Over rolling land, through pinon, juniper and mahogany growth.

1.00 Draw, drains NW.

15.20 Point for the $\frac{1}{4}$ sec. cor. of sec. 30, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T 26 S R 3 W

$\frac{1}{4}$	S 30
1975	

Set a cedar post, 6 ft. long, alongside the iron post.

Over gentle rolling reseeded area.

39.78 Point for the $\frac{1}{4}$ sec. cor. of sec. 19, at proportionate bearing and distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T 26 S R 3 W

$\frac{1}{4}$	S 19
1975	

Set a cedar post, 6 ft. long, alongside the iron post.

N. 89°38' W., beginning new measurement.

15.80 Point for the 80 $\frac{1}{16}$ sec. cor. of sec. 30, at proportionate distance.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T 26 S R 3 W

$\frac{1}{16}$	S 30	80
1975		

Set a cedar post, 6½ ft. long, alongside the iron post.

31.50 Dirt road in draw, bears NE and SW; asc. SE slope.

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 26 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS		
	From the true point for the cor. of secs. 16, 17, 20 and 21, previously described.	
	N. 89°41' W., bet. secs. 17 and 20.	
	Over mountainous land, through pinon, juniper and mahogany growth; asc. N-NW slope.	
20.27	Point for the 80 1/16 sec. cor. of secs. 17 and 20, at proportionate distance.	
	Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of brass cap, mkd.	
	T 26 S R 3 W	
	$1/16 \frac{S 17}{S 20} 80$	
	1975	
22.00	Spur, projecting NW; desc. W slope.	
63.39	Point for the ¼ sec. cor. of secs. 17 and 20, at proportionate bearing and distance; there is no remaining evidence of the original cor.	
	Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base to top of brass cap, mkd.	
	T 26 S R 3 W	
	$\frac{1}{4} \frac{S 17}{S 20}$	
	1975	
	(Restoring the 1878 survey by A. D. Ferron)	
	N. 89°46' W., beginning new measurement.	
	Over rolling land, through lightly scattering juniper growth; desc. NW slope.	
40.54	The cor. of secs. 17, 18, 19, and 20.	
	S. 89°35' W., bet. secs. 18 and 19.	
	Over gentle rolling land, through sagebrush and shadscale.	
25.50	Draw, drains NE.	
40.01	Point for the ¼ sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original corner.	
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.	

Dependent Resurvey of a portion of the Subdivisional Lines, T. 26 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS		
	T 26 S R 3 W	
	$\frac{1}{4}$ $\frac{S 18}{S 19}$	
	1975	
	Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.	
46.00	Dirt road, bears NW and SE.	
77.46	The cor. of secs. 13, 18, 19, and 24, monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the concurrent resurvey of the E. bdy. of T. 26 S., R. 4 W.	
	From the cor. of secs. 17, 18, 19, and 20.	
	N. 0°42' W., bet. secs. 17 and 18.	
	Over rolling land, through sagebrush and shadscale.	
40.30	The ¼ sec. cor. of secs. 17 and 18, monumented with a sandstone, 16 x 8 x 8 ins., firmly set and plainly mkd. ¼ on W face.	
	At the corner point	
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.	
	T 26 S R 3 W	
	$\frac{1}{4}$	
	S 18 S 17	
	1975	
	Deposit the mkd. stone alongside the iron post.	
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.	
	N. 0°32' W., beginning new measurement.	
29.00	Draw, drains NW.	
40.26	The cor. of secs. 7, 8, 17, and 18, monumented with a trachyte stone, 16 x 10 x 8 ins., firmly set and plainly mkd. 5 notches on E and 4 on S edges.	
	At the corner point	
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.	

Dependent Resurvey of a portion of the Subdivisional Lines, T. 26 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS						
	<p style="text-align: center;">T 26 S R 3 W</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 7</td> <td style="padding: 0 5px;">S 8</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 18</td> <td style="padding: 0 5px;">S 17</td> </tr> </table> <p style="text-align: center;">1975</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Set a steel fence post, alongside the iron post.</p>	S 7	S 8	S 18	S 17	
S 7	S 8					
S 18	S 17					
	<p>From the cor. of secs. 8 and 9, on the N. bdy. of sec. 17.</p> <p>S. 87°52' W., bet. secs. 8 and 17.</p> <p>Over mountainous land, through scattering pinon and juniper growth; desc. SW slope.</p>					
34.00	Dirt road, bears N and S; over rolling land.					
39.22	<p>The ¼ sec. cor. of secs. 8 and 17, monumented with a trachyte stone, 14 x 6 x 4 ins., firmly set and dimly mkd. ¼ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.</p>					
	<p style="text-align: center;">T 26 S R 3 W</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">¼</td> <td style="padding: 0 5px;">S 8</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">S 17</td> </tr> </table> <p style="text-align: center;">1975</p> <p>Deposit the mkd. stone alongside the iron post.</p>	¼	S 8		S 17	
¼	S 8					
	S 17					
	<p>N. 89°35' W., beginning new measurement.</p>					
1.00	Canal, drains North.					
40.78	The cor. of secs. 7, 8, 17, and 18.					
	<p>S. 89°14' W., bet. secs. 7 and 18.</p> <p>Over gentle rolling land, through sagebrush and shadscale growth.</p>					
14.00	Draw, drains NW.					
31.30	Draw, drains NW.					
39.82	<p>The ¼ sec. cor. of secs. 7 and 18, monumented with a trachyte stone, 14 x 10 x 8 ins., firmly set and plainly mkd. ¼ on N face.</p> <p>At the corner point</p>					

Dependent Resurvey of a portion of the Subdivisional Lines, T. 26 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of brass cap, mkd.</p> <p style="text-align: center;">T 26 S R 3 W</p> <p style="text-align: center;">¼ $\frac{S 7}{S 18}$</p> <p style="text-align: center;">1975</p> <p>Deposit the mkd. stone alongside the iron post.</p> <hr/> <p>S. 89°25' W., beginning new measurement.</p> <p>16.20 Point of hill, projecting N.</p> <p>37.06 The cor. of secs. 7, 12, 13, and 18, monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the concurrent resurvey of the E. bdy. of T. 26 S., R. 4 W.</p>
	<p>From the cor. of secs. 7, 8, 17, and 18.</p> <p>N. 0°33' W., bet. secs. 7 and 8.</p> <p>Over rolling land, through sagebrush and shadscale.</p> <p>40.29 The ¼ sec. cor. of secs. 7 and 8, monumented with a granite stone, 14 x 6 x 6 ins., firmly set and plainly mkd. ¼ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 26 S R 3 W</p> <p style="text-align: center;">¼ S 7 S 8 1975</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Set a steel fence post alongside the corner.</p> <hr/> <p>N. 0°22' W., beginning new measurement.</p> <p>40.34 The cor. of secs. 5, 6, 7, and 8, monumented with a trachyte stone, 16 x 8 x 8 ins., firmly set and plainly mkd. 5 notches on S and E edges.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base to top of brass cap, mkd.</p>

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 26 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS						
	<p style="text-align: center;">T 26 S R 3 W</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 6</td> <td style="padding: 0 5px;">S 5</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 7</td> <td style="padding: 0 5px;">S 8</td> </tr> </table> <p style="text-align: center;">1975</p> <p>Deposit the mkd. stone alongside the iron post.</p>	S 6	S 5	S 7	S 8	
S 6	S 5					
S 7	S 8					
	<p>From the cor. of secs. 4, 5, 8, and 9.</p> <p>S. 89°24' W., bet. secs. 5 and 8.</p> <p>Over rolling bench land, through sagebrush and shadscale; desc. gentle NW slope.</p> <p>22.00 Dirt road, bears N. 17° W. and S. 17° E.</p> <p>32.50 Canal, drains N. 10° E.</p> <p>40.18 The $\frac{1}{4}$ sec. cor. of secs. 5 and 8, monumented with a trachyte stone, 10 x 10 x 6 ins., firmly set and plainly mkd. $\frac{1}{4}$ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of brass cap, mkd.</p> <p style="text-align: center;">T 26 S R 3 W</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">$\frac{1}{4}$</td> <td style="border-right: 1px solid black; padding: 0 5px;">S 5</td> <td style="padding: 0 5px;">S 8</td> </tr> </table> <p style="text-align: center;">1975</p> <p>Deposit the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°40' W., beginning new measurement.</p> <p>40.32 The cor. of secs. 5, 6, 7, and 8.</p>	$\frac{1}{4}$	S 5	S 8		
$\frac{1}{4}$	S 5	S 8				
	<p>S. 89°48' W., bet. secs. 6 and 7.</p> <p>Over gentle rolling land, through sagebrush and shadscale.</p> <p>40.80 The $\frac{1}{4}$ sec. cor. of secs. 6 and 7, monumented with a granite stone, 13 x 7 x 5 ins., firmly set and plainly mkd. $\frac{1}{4}$ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 2$\frac{1}{2}$ ft. base to top of brass cap, mkd.</p>					

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 26 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS		
	<p style="text-align: center;">T 26 S R 3 W</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S 6}{S 7}$</p> <p style="text-align: center;">1975</p> <p>Deposit the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°17' W., beginning new measurement.</p>	
23.83	Dirt road, bears N. 12° E. and S. 12° W.	
27.20	Wash, 2 ft. deep, 20 lks. wide, drains NW; asc. E slope.	
32.40	Top of low ridge, bears N and S; desc. W slope.	
37.40	The cor. of secs. 1, 6, 7, and 12, monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the concurrent resurvey of the E. bdy. of T. 26 S., R. 4 W.	
	<p>From the cor. of secs. 5, 6, 7, and 8.</p> <p>N. 0°45' W., bet. secs. 5 and 6.</p> <p>Over gentle rolling land, through sagebrush and shadscale growth.</p>	
40.16	<p>Point for the ¼ sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of brass cap, mkd.</p> <p style="text-align: center;">T 26 S R 3 W</p> <p style="text-align: center;">$\frac{1}{4}$</p> <p style="text-align: center;">S 6 S 5</p> <p style="text-align: center;">1975</p>	
80.54	<p>The closing cor. of secs. 5 and 6, on the S. bdy. of sec. 32, T. 25 S., R. 3 W., (Fifth Standard Parallel South) mkd. with a trachyte stone, 18 x 8 x 6 ins., firmly set and plainly mkd. 5 notches on E and 1 on W edges, CC on S face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 25 S R 3 W</p> <p style="text-align: center;">S 32</p> <p style="text-align: center;">S 6 S 5</p> <p style="text-align: center;">C C</p> <p style="text-align: center;">T 26 S R 3 W</p> <p style="text-align: center;">1975</p>	

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 26 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

Deposit the mkd. stone alongside the iron post.

Raise a mound of stone, 3 ft. base, 2 ft. high, S of cor.

From this point the standard cor. of secs. 31 and 32, T. 25 S., R. 3 W., (Fifth Standard Parallel South), bears S. $89^{\circ}32'$ W., 5.73 chs. dist., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set and mkd. as described in the 1970-71 resurvey of a portion of the Fifth Standard Parallel South.

From this same point the standard $\frac{1}{4}$ sec. cor. of sec. 32, T. 25 S., R. 3 W., (Fifth Standard Parallel South), bears N. $89^{\circ}32'$ E., 34.57 chs. dist., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set and mkd. as described in the 1970-71 resurvey of a portion of the Fifth Standard Parallel South.

The point for the $\frac{1}{4}$ sec. cor. of sec. 5 only, T. 26 S., R. 3 W., is at midpoint on the N. bdy. of sec. 5.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ S 5
 T 26 S R 3 W
 1975

Raise a mound of stone, 3 ft. base, 2 ft. high, S of cor.

From this point the standard $\frac{1}{4}$ sec. cor. of sec. 32, T. 25 S., R. 3 W., bears S. $89^{\circ}32'$ W., 5.72 chs. dist., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set and mkd. as described in the 1970-71 resurvey of a portion of the Fifth Standard Parallel South.

From this same point the standard cor. of secs. 32 and 33, T. 25 S., R. 3 W., bears N. $89^{\circ}32'$ E., 34.59 chs. dist., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set and mkd. as described in the 1970-71 resurvey of a portion of the Fifth Standard Parallel South.

The point for the $\frac{1}{4}$ sec. cor. of sec. 6 only, T. 26 S., R. 3 W., at proportionate distance on the N. bdy. of sec. 6.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.

$\frac{1}{4}$ S 6
 T 26 S R 3 W
 1975

Raise a mound of stone, 3 ft. base, 2 ft. high, S of cor.

From this point the standard $\frac{1}{4}$ sec. cor. of sec. 31, T. 25 S., R. 3 W., bears S. $89^{\circ}38'$ W., 5.58 chs. dist., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set and mkd. as described in the 1970-71 resurvey of a portion of the Fifth Standard Parallel South.

Dependent Resurvey of a portion of the Subdivisional
Lines, T. 26 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

From this same point the standard cor. of secs. 31 and 32, T. 25 S., R. 3 W., bears N. 89°38' E., 34.60 chs. dist., monumented with an iron post, 2½ ins. diam., set and mkd. as described in the 1970-71 resurvey of a portion of the Fifth Standard Parallel South.

GENERAL DESCRIPTION

The area resurveyed within T. 26 S., R. 3 W., varies from mountainous in the south and east portion to gentle rolling in the northwest portion. The elevation ranges from 5,700 to 9,400 ft. above sea level. The soil varies from sandy clay loam to very rocky at higher elevations. The vegetation consists of sagebrush, shadscale and native grasses at lower elevations to pine, aspen, juniper and mahogany at higher elevations. The general drainage is to the northwest. The principal use of this area is livestock grazing.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Frank Profazier	Surveying Technician
Craig Kennedy	Survey Aid
Douglas Carlson	Survey Aid
Russell Brown	Survey Aid

CERTIFICATE OF SURVEY

(I)(WE), Ferrel D. Reynolds, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 20th day of March, 1975, (I)(WE) have dependently resurveyed a portion of the north boundary of T. 27 S., R. 2 1/2 W., and a portion of the subdivisional lines of Township 26 South, Range 3 West

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (I)(WE), (us) and under (my) (I)(WE) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

February 18, 1976
(Date)

Ferrel D. Reynolds
(Cadastral Surveyor)

Under the supervision of

(Date)

Allen B. Hatch
(Cadastral Surveyor)
Acting Chief, Branch of Cadastral Survey

CERTIFICATE OF APPROVAL

~~*At the date he signed the Certificate of Survey he was a Surveying Technician, BUREAU OF LAND MANAGEMENT, Washington, D.C., Denver, Colorado~~

The foregoing field notes of the dependent resurvey of a portion of the north boundary of T. 27 S., R. 2 1/2 W., and a portion of the subdivisional lines of T. 26 S., R. 3 W., Salt Lake Meridian, Utah

executed by Ferrel D. Reynolds, Cadastral Surveyor having been critically examined and found correct, are hereby approved.

MAR 18 1980
(Date)

Allen B. Hatch
(Chief, Division of Cadastral Survey)

Acting Chief, Cadastral Survey Examination and Approval Staff

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey) GPO 810-434

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

R599

ORIGINAL

FIELD NOTES

OF THE
 DEPENDENT RESURVEY
 OF THE
 NORTH BOUNDARY OF T. 27 S., R. 3 W.,
 THE
 EAST TWO MILES OF THE NORTH BOUNDARY
 OF T. 27 S., R. 4 W.,
 THE EAST BOUNDARY OF T. 26 S., R. 4½ W.,
 THE EAST BOUNDARY
 AND THE
 SUBDIVISIONAL LINES OF T. 26 S., R. 4 W.

Of the Salt Lake Meridian,
 In the State of Utah

EXECUTED BY

Craig P. Sylvester Supervisory Cadastral Surveyor

Under special instructions dated March 20, 19 75, approved March 24, 1975,

_____, which provided for the surveys included under U.S. Survey/Group
 Number 558, and assignment instructions dated July 15, 19 75.

Survey commenced August 4, 19 75

Survey completed October 17, 19 75

INDEX DIAGRAM

Township 26 S., Range 4 W.

	83	82	63	53	42	32	
23	80 6 81	5 62	4 52	3 41	2 31	1 17	
	79	78	61	51	40	30	
21	80 7 77	8 60	9 49	10 40	11 29	12 16	
	76	75	60	49	39	29	
21	77 18 74	17 59	16 48	15 38	14 28	13 15	
	72	71	58	47	37	27	
20	73 19 70	20 57	21 45	22 36	23 26	24 14	
	68	64	54	43	32	24	
18	70 30 65	29 55	28 44	27 34	26 25	25 13	
	68	67	56	45	35	26	
	11	10	9	7	6	5	
	31	32	33	34	35	36	

Township 26 South, Range 4 West, Salt Lake Meridian, Utah

CHAINS

The north $3\frac{1}{2}$ miles of the east boundary, the east 4 miles of the north boundary (Fifth Standard Parallel South), and the east portion of the subdivisional lines were surveyed by A. D. Ferron in 1878. The south $1\frac{1}{2}$ miles of the east boundary, the south and west boundaries, the west 2 miles of the north boundary, and the west portion of the subdivisional lines were surveyed by J. T. Breckon in 1896. The south mile of the east boundary and the southeast portion of the subdivisional lines were correctively surveyed by J. T. Breckon in 1898. The north boundary was resurveyed by Jerry L. Thomas and Fred R. Chappell in 1970-71. The subdivisional line between secs. 29 and 30 was resurveyed by J. C. Scoles. U.S. Mineral Surveyor in 1932.

The following field notes are those of a dependent resurvey of the north boundary of T. 27 S., R. 3 W., the east two (2) miles of the north boundary of T. 27 S., R. 4 W., the east boundary of T. 26 S., R. $4\frac{1}{2}$ W., the east boundary and the subdivisional lines of T. 26 S., R. 4 W., Salt Lake Meridian, Utah.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group 558, Utah, dated March 20, 1975.

The directions of the lines of this survey were determined by reference to true meridians established on line by hour angle observations on Polaris. They were carried forward by sustained angulation, being supplemented by numerous other observations on Polaris taken throughout the progress of the survey.

Measurements were determined by electronic means along survey lines where accessible. Distances to topography on lines run by traverse due to rough terrain, timber and private property are approximately as scaled from U.S.G.S. topographic sheets.

Before restoring lost corners, the lines of the original survey were retraced and a diligent search made for any evidence of the original corners. The rules of proportionate measurement were applied to ascertain the position of the lost corner after every reasonable possibility of finding direct evidence of the corner had been exhausted.

The geographic position for the southeast corner of the township, as determined by ties to U.S.G.S. triangulation station "Flat Top", located in section 26, T. 26 S., R. 4 W., is as follows:

Latitude $38^{\circ}30'02.7''$ N. Longitude $112^{\circ}10'36.6''$ W.

The magnetic declination was read at a number of stations throughout the township and the average of the several readings was found to be $15^{\circ}30'$ E.

Dependent Resurvey of the North Boundary of
T. 27 S., R. 3 W., Salt Lake Meridian, Utah

(Restoring the 1896 survey by J. T. Breckon)

Dependent Resurvey of the North Boundary of
T. 27 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
	<p>Beginning at the cor. of Tps. 27 S., Rs. 2½ and 3 W., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of T. 26 S., R. 3 W.</p> <p>S. 89°57' W., along the N. bdy. of sec. 1.</p> <p>Over mountainous land, through pinon, juniper and oak brush growth; desc. over N slope.</p> <p>2.11 Point for the S ¼ sec. cor. of sec. 29, T. 26 S., R. 3 W., at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 26 S R 3 W</p> <p style="text-align: center;"><u>¼ S 29</u></p> <p style="text-align: center;">T 27 S R 3 W 1975</p> <p>Set a cedar post, 5 ft. high, alongside the iron post.</p> <p>Cor. is located on gentle N slope; in dense oak brush.</p> <p>10.00 Slope changes; desc. over W slope, down wide draw.</p> <p>20.00 Enter small mountain flat.</p> <p>40.17 The N ¼ sec. cor. of sec. 1, T. 27 S., R. 3 W., monumented with a granite stone, 18 x 12 x 4 ins., firmly set and mkd. ¼ on S face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.</p> <p style="text-align: center;">T 26 S R 3 W</p> <p style="text-align: center;"><u>¼ S 1</u></p> <p style="text-align: center;">T 27 S R 3 W 1975</p> <p>Deposit the mkd. stone alongside the iron post, in a mound of stone.</p> <p style="text-align: center;">_____</p> <p>N. 89°19' W., beginning new measurement.</p> <p>Desc. over NW slope, through juniper, pinon and mahogany growth.</p> <p>2.10 The cor. of secs. 29 and 30, T. 26 S., R. 3 W., monumented with a granite stone, 18 x 10 x 6 ins., firmly set and plainly mkd. 5 notches on E and 1 notch on W edge.</p> <p>At the corner point</p>

Dependent Resurvey of the North Boundary of
T. 27 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.</p>
	<p style="text-align: center;">T 26 S R 3 W S 30 S 29 — S 1</p>
	<p style="text-align: center;">T 27 S R 3 W 1975</p>
	<p>Deposit the mkd. stone alongside the iron post, in a mound of stone.</p>
	<p>Cor. is located on NW slope, above draw which drains W.</p>
30.00	<p>Slope changes; desc. steep W slope, on ridge top.</p>
40.43	<p>The cor. of secs. 1 and 2, T. 27 S., R. 3 W., monumented with a granite stone, 20 x 8 x 6 ins., firmly set and plainly mkd. 5 notches on W and 1 notch on E edge, from which the original bearing trees</p>
	<p style="padding-left: 40px;">A pinon, 9 ins. diam., bears S. 33°30' E., 15 lks. dist., mkd. T27S R3W S1 BT.</p>
	<p style="padding-left: 40px;">A pinon, 10 ins. diam., bears S. 62°30' W., 22 lks. dist., mkd. T27S R3W S2 BT.</p>
	<p style="padding-left: 40px;">A cedar, 10 ins. diam., bears N. 45° W., 21 lks. dist., mkd. T26S R3W BT. (Unrecorded)</p>
	<p style="padding-left: 40px;">A pinon, 8 ins. diam., bears N. 45° E., 9 lks. dist., mkd. T26S R3W BT. (Unrecorded)</p>
	<p>At the corner point</p>
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.</p>
	<p style="text-align: center;">T 26 S R 3 W S 30 — S 2 S 1 </p>
	<p style="text-align: center;">T 27 S R 3 W 1975</p>
	<p>Deposit the mkd. stone alongside the iron post, in a mound of stone.</p>
	<p>Cor. is located on broken W slope, 10 lks. N of E and W fence line.</p>
	<p>S. 89°34' W., along the N. bdy. of sec. 2.</p>
	<p>Over mountainous land, covered with juniper, pinon and oak brush; desc. over steep W slope.</p>

Dependent Resurvey of the North Boundary of
T. 27 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
2.25	<p>Point for the S $\frac{1}{4}$ sec. cor. of sec. 30, T. 26 S., R. 3 W., at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.</p> <p style="text-align: center;">T 26 S R 3 W</p> <p style="text-align: center;"><u>$\frac{1}{4}$ S 30</u></p> <p style="text-align: center;">T 27 S R 3 W 1975</p> <p>Desc. W slope.</p>
14.00	<p>Base of mountains, bears N and S irregularly; desc. W slope, leave mountains, enter reseeded area.</p>
40.17	<p>Point for the N $\frac{1}{4}$ sec. cor. of sec. 2, T. 27 S., R. 3 W., at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 S R 3 W</p> <p style="text-align: center;"><u>$\frac{1}{4}$ S 2</u></p> <p style="text-align: center;">T 27 S R 3 W 1975</p> <p>Cor. is located in E and W fence line.</p>
42.83	<p>Point for the 80 $\frac{1}{16}$ sec. cor. of sec. 30, T. 26 S., R. 3 W., at proportionate distance.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 S R 3 W</p> <p style="text-align: center;"><u>$\frac{1}{16}$ S 30</u> 80</p> <p style="text-align: center;">1975</p> <p>Cor. is located in E and W fence line.</p>
64.29	<p>The closing cor. of T. 26 S., Rs. 3 and 4 W., hereinafter described.</p>
73.50	<p>Small wash, drains SW.</p>
80.14	<p>Dirt road, bears NE and SW; asc. over gentle SE slope, leave fence line.</p>
80.34	<p>The cor. of secs. 2 and 3, T. 27 S., R. 3 W., monumented with a lava stone, 14 x 8 x 6 ins., firmly set and mkd. 4 notches on W and 2 notches on E edges. Also scattering stones and blue steel fence post by cor.</p> <p>At the corner point</p>

Dependent Resurvey of the North Boundary of
T. 27 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS					
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 26 S R 4 W</p> <p style="text-align: center;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2" style="text-align: center;">S 25</td></tr> <tr><td style="text-align: center;">S 3</td><td style="text-align: center;">S 2</td></tr> </table> </p> <p style="text-align: center;">T 27 S R 3 W 1975</p> <p>Deposit the mkd. stone alongside the iron post, and set steel fence post by cor.</p>	S 25		S 3	S 2
S 25					
S 3	S 2				
	<p>S. 89°00' W., along the N. bdy. of sec. 3, T. 27 S., R. 3 W.</p> <p>Over mountain valley land, across reseeded area; asc. over gentle SE slope.</p>				
24.29	The S ¼ sec. cor. of sec. 25, T. 26 S., R. 4 W., hereinafter described.				
35.00	Leave reseeded area, enter juniper and pinon timber.				
40.47	Point for the N ¼ sec. cor. of sec. 3, T. 27 S., R. 3 W., at midpoint; there is no remaining evidence of the original corner.				
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 S R 4 W</p> <p style="text-align: center;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td colspan="2" style="text-align: center;">¼ S 3</td></tr> </table> </p> <p style="text-align: center;">T 27 S R 3 W 1975</p> <p>Raise a mound of stone, 2 ft. base, 2 ft. high, S of cor.</p> <p>Asc. E slope, through juniper and pinon timber.</p>	¼ S 3			
¼ S 3					
48.50	Spur, slopes S; desc. over W slope.				
58.00	Draw, drains S; asc. over E slope.				
64.63	The closing cor. of secs. 25 and 26, T. 26 S., R. 4 W., hereinafter described. Also top of spur, slopes S; desc. over W slope.				
70.10	Draw, drains S; asc. over steep SE slope, leave trees.				
80.94	The cor. of secs. 3 and 4, T. 27 S., R. 3 W., monumented with a granite stone, 20 x 14 x 12 ins., plainly mkd. 3 notches on E and W edges.				
	<p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.</p>				

Dependent Resurvey of the North Boundary of
T. 27 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	<p style="text-align: center;">T 26 S R 4 W</p> <p style="text-align: center;"> $\begin{array}{c} \text{S } 26 \\ \hline \text{S } 4 \quad \quad \text{S } 3 \\ \\ \text{T } 27 \text{ S } \text{ R } 3 \text{ W} \\ 1975 \end{array}$ </p> <p>Deposit the mkd. stone alongside the iron post, in a mound of stone.</p>
	<p>N. 89°23' W., along the N. bdy. of sec. 4, T. 27 S., R. 3 W.</p> <p>Over mountain land, covered with shadscale; asc. over steep SE slope.</p> <p>4.00 Spur, slopes S; desc. over SW slope.</p> <p>9.60 Small draw, drains S; asc. over SE slope.</p> <p>17.00 High spur, slopes S; desc. over W slope.</p> <p>20.60 Intersect line 2-3, Mineral Survey No. 7276, Freedom No. 3 claim.</p>
	<p>From this intersection, cor. No. 2, bears N. 19°16' W., 9.19 chs. dist., marked by an iron post, 1½ ins. diam., extending 10 ins. above ground, with brass cap mkd. 2-F 3, 7276.</p> <p>From the same intersection, cor. No. 3, bears S. 19°16' E., 0.16 chs. dist., marked by an iron post, 1½ ins. diam., extending 10 ins. above ground, with brass cap mkd. 3-F. 3, 2-F 5., 7276, from which the original bearing tree</p> <p style="padding-left: 40px;">A juniper, 24 ins. diam., bears S. 25°18' E., 1.58 chs. dist., mkd. 3-F 3 2-F5 7276 BT.</p>
21.50	Draw, drains S; asc. along S slope.
23.94	The S ¼ sec. cor. of sec. 26, T. 26 S., R. 4 W., hereinafter described.
27.20	Spur, slopes S; desc. over steep SW slope, over slide rock.
39.77	Point for the N ¼ sec. cor. of sec. 4, T. 27 S., R. 3 W., at midpoint; there is no evidence of the original corner.
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 S R 4 W</p> <p style="text-align: center;"> $\begin{array}{c} \hline \frac{1}{4} \text{ S } 4 \\ \hline \end{array}$ </p> <p style="text-align: center;">T 27 S R 3 W 1975</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears S. 53° W., 69 lks. dist., mkd. ¼ S4 BT.</p>

Dependent Resurvey of the North Boundary of
T. 27 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS											
	<p>Raise a mound of stone, 4 ft. base, 2 ft. high, N of cor., to turn water away from cor. position, which is located in small cut, which drains S.</p>										
	<p>Along S slope in bottom of draw, which drains S.</p>										
42.80	<p>Base of steep ascent, bears S and curves NE; asc. over steep and rocky E slope.</p>										
56.50	<p>Ridge, bears N and S; desc. over steep and rocky W slope, over numerous cuts and mining development work.</p>										
64.19	<p>The closing cor. of secs. 26 and 27, T. 26 S., R. 4 W., hereinafter described.</p>										
69.00	<p>Base of steep descent, bears N and S; desc. over general W slope.</p>										
79.54	<p>The cor. of secs. 4 and 5, T. 27 S., R. 3 W., determined by a mound of stone with rebar in center, no legible marks could be identified on stones, from which original bearing trees</p>										
	<p>A pine, 14 ins. diam., bears S. 38° E., 95 lks. dist., mkd. T27S R3W S4 BT.</p>										
	<p>A fallen pine, 12 ins. diam., bears S. 48° W., 65 lks. dist., mkd. T27S R3W S5 BT.</p>										
	<p>At the corner point</p>										
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p>										
	<p style="text-align: center;">T 26 S R 4 W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">S 27</td> </tr> <tr> <td style="text-align: center;">S 5</td> <td style="text-align: center;">S 4</td> </tr> <tr> <td colspan="2" style="text-align: center;"> </td> </tr> <tr> <td colspan="2" style="text-align: center;">T 27 S R 3 W</td> </tr> <tr> <td colspan="2" style="text-align: center;">1975</td> </tr> </table>	S 27		S 5	S 4			T 27 S R 3 W		1975	
S 27											
S 5	S 4										
T 27 S R 3 W											
1975											
	<p>N. 89°44' W., along the N. bdy. of sec. 5, T. 27 S., R. 3 W.</p>										
	<p>Over mountain land, covered with shadscale and scattering juniper and pinon growth; desc. over general W slope.</p>										
9.10	<p>Intersect line 1-4, Mineral Survey No. 7292, Farmer John No. 3 claim.</p>										
	<p>From this intersection, cor. No. 1 bears N. 0°40' W., 0.42 chs. dist., marked by a galvanized pipe, ¾ ins. diam., extending 10 ins. above ground, with brass cap mkd. 1-F.J. 3, 7292. from which the original bearing tree</p>										
	<p>A juniper, 12 ins. diam., bears N. 17°08' W., 1.27 chs. dist., mkd. 1 F J 3 BT.</p>										

Dependent Resurvey of the North Boundary of
T. 27 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
	<p>From the same intersection, cor No. 4 bears S. 0°40' E., 8.71 chs. dist., marked by a galvanized pipe, 3/4 ins. diam., extending 10 ins. above ground, with brass cap mkd. 4-F.J. 3, 7292, from which the original bearing tree</p>
	<p>A juniper, 12 ins. diam., bears S. 72°21' E., 93 lks. dist., mkd. 4-F J 3, 7292 BT.</p>
25.14	<p>The S 1/4 sec. cor. of sec. 27, T. 26 S., R. 4 W., hereinafter described.</p>
40.42	<p>Point for the N 1/4 sec. cor. of sec. 5, T. 27 S., R. 3 W., determined from the original bearing tree</p>
	<p>A cedar, 14 ins. diam., bears S. 45°30' E., 35 lks. dist., mkd. 1/4 S BT.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T 26 S R 4 W</p>
	<p style="text-align: center;">1/4 S 5</p>
	<p style="text-align: center;">T 27 S R 3 W 1975</p>
	<p>The original stone for this cor. was not found.</p>
	<p style="text-align: center;">S. 89°38' W., beginning new measurement.</p>
	<p>Desc. gentle NW slope, in valley.</p>
25.20	<p>The closing cor. of secs. 27 and 28, T. 26 S., R. 4 W., hereinafter described. Corner is located in wide wash, which drains S. 85° W.</p>
26.00	<p>Draw, drains South.</p>
28.60	<p>Gravel road, bears N. 4° W. and S. 4° E.; asc. over E slope of hill.</p>
34.90	<p>Crest of ascent, bears N and S; thence along N slope.</p>
40.18	<p>The cor. of secs. 5 and 6, T. 27 S., R. 3 W., marked by a mound of stone, original corner has been broken, but plain notches can be found on broken pieces.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base to top of brass cap, mkd.</p>
	<p style="text-align: center;">T 26 S R 4 W</p>
	<p style="text-align: center;">S 28</p>
	<p style="text-align: center;">S 6 S 5</p>
	<p style="text-align: center;">T 27 S R 3 W 1975</p>

Dependent Resurvey of the North Boundary of
T. 27 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
	Place original pieces of mkd. stone in mound alongside the iron post.
	S. 89°39' W., along the N. bdy. of sec. 6, T. 27 S., R. 3 W.
	Over mountain land, covered with shadscale and scattering juniper and pinon timber; along N slope.
16.00	Small wash, drains N. 80° E.; asc. along S slope.
24.585	The S ¼ sec. cor. of sec. 28, T. 26 S., R. 4 W., hereinafter described.
27.20	Base of steep ascent, bears N and S irregularly; asc. over steep E slope.
39.62	Point for the N ¼ sec. cor. of sec. 6, T. 27 S., R. 3 W., at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 5 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.
	T 26 S R 4 W <hr style="width: 10%; margin: auto;"/> ¼ S 6 T 27 S R 3 W 1975
	Asc. over steep E slope.
41.20	Ridge, bears N and S; desc. over steep SW slope.
47.00	Rocky draw, drains S; asc. over SE slope.
52.80	Spur, slopes S; desc. over steep and ledgy W slope.
64.15	The closing cor. of secs. 28 and 29, T. 26 S., R. 4 W., hereinafter described. Desc. over broken NW slope.
77.30	Point for the cor. of Tps. 27 S., Rs. 3 and 4 W., determined longitudinally by proportionate distance, and latitudinally by an old fence line bearing E and W.
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.
	T 26 S R 4 W <hr style="width: 10%; margin: auto;"/> S 29 S 1 S 6 R 4 W R 3 W T 27 S 1975

Dependent Resurvey of a portion of the N. Bdy. of
T. 27 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS	Dependent Resurvey of a portion of the N. Bdy. of T. 27 S., R. 4 W., Salt Lake Meridian, Utah (Restoring the 1896 survey by John T. Breckon)
	From the cor. of Tps. 27 S., Rs. 3 and 4 W. S. 89°39' W., along the N. bdy. of sec. 1, T. 27 S., R. 4 W. Over broken and rocky mountain land on E side of Marysvale Canyon; desc. over steep W slope.
7.10	Denver and Rio Grande Railroad, not now in use, bears N. 1°16' W. and S. 1°16' E. Also base of steep descent; thence over canyon bottom.
10.20	Sevier River, 1.00 ch. wide, 2 ft. deep, flows N.
13.30	U.S. Highway No. 89, bears N. 1°30' W. and S. 1°30' E., in Marysvale Canyon bottom.
16.00	Base of steep ascent, bears N and S irregularly; asc. over steep E slope.
25.21	The witness S ¼ sec. cor. of sec. 29, T. 26 S., R. 4 W., hereinafter described. Also base of impassable ledges; thence along ledgy N slope.
25.87	True point for the S ¼ sec. cor. of sec. 29, T. 26 S., R. 4 W., falls on inaccessible ledges and cannot be monumented; continue along ledgy N slope.
39.62	Point for the N ¼ sec. cor. of sec. 1, T. 27 S., R. 4 W., at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd. T 26 S R 4 W ----- ¼ S 1 T 27 S R 4 W 1975
	Desc. along steep N slope, over slide rock.
64.885	The closing cor. of secs. 29 and 30, T. 26 S., R. 4 W., hereinafter described.
69.60	Deer Creek, 8 lks. wide, 6 ins. deep, flows N. 55° E. irregularly.
70.90	Graded dirt road, bears N. 35° E. and S. 54° W.; also base of steep ascent; asc. along broken and ledgy S slope.
71.11	Intersect line 1-2, Pittsburg Mill Site, Mineral Survey No. 6678B. From this intersection, cor. No. 1 bears N. 45°45' E., 7.96 chs. dist., marked by an iron post, 2 ins. diam., extending 30 ins. above ground, mkd. P M S 1-6678B.

Dependent Resurvey of a portion of the N. Bdy. of
T. 27 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS	
	<p>From this same intersection, the point for cor. No. 2 bears S. 45°45' W., 0.69 chs. dist., determined by proportionate course and distance. Road work has destroyed the original corner monument.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">P M S cor-2 6678B</p> <p style="text-align: center;">1975</p>
71.62	<p>Intersect line 2-3, Pittsburg Mill Site, Mineral Survey No. 6678B.</p> <p>From this intersection, cor. No. 3 bears N. 1°55' W., 9.51 chs. dist., marked by an iron post, 2 ins. diam., extending 30 ins. above ground, stamped P M S 3-6678B.</p> <p>From this same intersection, cor. No. 2 bears S. 1°55' E., 0.48 chs. dist., previously described.</p>
79.24	<p>Point for the cor. of secs. 1 and 2, T. 27 S., R. 4 W., at proportionate distance; there is no remaining evidence of the original corner, falls on small ledge and cannot be monumented.</p> <p>From this same point, the point selected for the witness cor. of secs. 1 and 2, T. 27 S., R. 4 W., bears South 0.05 chs. dist.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.</p> <p style="text-align: center;">W C T 26 S R 4 W</p> <p style="text-align: center;">S 30 S 2 \nearrow S 1 T 27 S R 4 W 1975</p>
17.20 25.40 26.02 35.80	<p>From the true point for the cor. of secs. 1 and 2, T. 27 S., R. 4 W.</p> <p>S. 89°39' W., along the N. bdy. of sec. 2, T. 27 S., R. 4 W.</p> <p>Over mountainous land, covered with pinon, juniper and oak brush; asc. along broken and ledgy S slope.</p> <p>Ledgy spur, slopes S; desc. over broken SW slope.</p> <p>Rocky and ledgy draw, drains S; asc. over SE slope.</p> <p>The S ¼ sec. cor. of sec. 30, T. 26 S., R. 4 W., hereinafter described.</p> <p>Spur, slopes S; thence along S slope in head of draw, across slide rock.</p>

625

Dependent Resurvey of a portion of the N. Bdy. of
T. 27 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS

39.62 Point for the N $\frac{1}{4}$ sec. cor. of sec. 2, T. 27 S., R. 4 W., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground, in a mound of stone, 4 ft. base to top of brass cap, mkd.

T 26 S R 4 W

$\frac{1}{4}$ S 2

T 27 S R 4 W

1975

from which

A cedar, 8 ins. diam., bears S. 33° W., 46 lks. dist., mkd. $\frac{1}{4}$ S2 BT.

42.40 Leave head of draw; thence along gentle S slope of bench.

50.00 Wash, drains S. 15° E.; asc. over gentle SE slope.

64.70 Wash in small draw, drains SE; asc. over gentle SE slope.

66.01 The closing cor. of T. 27 S., Rs. 4 and 4 $\frac{1}{2}$ W., hereinafter described.

73.10 Dirt road, bears NW and S; asc. over gentle SE slope.

79.24 The cor. of secs. 2 and 3, T. 27 S., R. 4 W., monumented with a limestone, 16 x 14 x 4 ins., plainly mkd. 2 notches on E and 4 notches on W edges. Mound of stone S of cor.

At the corner point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T 26 S R 4 $\frac{1}{2}$ W

S 36

S 3 | S 2

T 27 S R 4 W

1975

from which

A pine, 6 ins. diam., bears S. 3° W., 56 lks. dist., mkd. T27S R4W S3 BT.

Bury the mkd. stone alongside the iron post.

Dependent Resurvey of the East Boundary of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

(Restoring the 1896 survey and the 1898 correction
survey by J. T. Breckon

Dependent Resurvey of the East Boundary of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah


CHAINS

From the closing cor. of Tps. 26 S., Rs. 3 and 4 W., on the S. bdy. of the Tp., monumented with a sandstone, 16 x 12 x 6 ins., firmly set and plainly mkd. 6 notches on E and W edges, and CC on N face, from which the remains of an original bearing tree

A pinon, 10 ins. diam., bears N. 4° W., 70 lks. dist., mkd. with illegible scribe marks.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a collar of stone, with brass cap mkd.



T 27 S R 3 W
1975

from which

A pinon, 10 ins. diam., bears N. 38° E., 45 lks. dist., mkd. BT.

Bury the mkd. stone alongside the iron post.

N. 0°03' E., bet. secs. 25 and 30.

Over mountain land, through juniper and pinon timber; desc. over gentle NW slope.

8.20 Small wash, drains SW; asc. over S slope.


24.00 Dirt road, bears NE and SW.

42.98 The ¼ sec. cor. of secs. 25 and 30, monumented with a sandstone, 18 x 16 x 6 ins., firmly set and plainly mkd. ¼ on W face, from which an original bearing tree

A pinon, 10 ins. diam., bears S. 30° E., 13 lks. dist., mkd. ¼ S BT.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.



Bury the mkd. stone alongside the iron post, and raise a mound of stone, 2 ft. base, 2 ft. high, W of cor.

Dependent Resurvey of the East Boundary of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS															
	N. 0°05' E., beginning new measurement.														
	Asc. S slope.														
9.00	Same road, bears NW and SE.														
11.00	Ridge, bears E and W; desc. over NW slope.														
36.50	Same road, bears NE and SW, in draw draining north-easterly; asc. over SE slope.														
40.49	The cor. of secs. 19, 24, 25, and 30, monumented with a trachyte stone, 17 x 9 x 7 ins., firmly set and plainly mkd. 4 notches on N and 1 notch on S edge.														
	At the corner point														
	Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.														
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T 26 S</td></tr> <tr><td style="text-align: center;">R 4 W</td><td style="text-align: center;">R 3 W</td></tr> <tr><td colspan="2" style="text-align: center;"> </td></tr> <tr><td style="text-align: center;">S 24</td><td style="text-align: center;">S 19</td></tr> <tr><td style="text-align: center;">S 25</td><td style="text-align: center;">S 30</td></tr> </table>	T 26 S		R 4 W	R 3 W			S 24	S 19	S 25	S 30				
T 26 S															
R 4 W	R 3 W														
S 24	S 19														
S 25	S 30														
	1975														
	Place the mkd. stone in mound alongside the iron post.														
	(Restoring the 1896 survey by J. T. Breckon)														
	N. 0°01' E., bet. secs. 19 and 24.														
	Over mountain land, through scattering juniper and pinon; asc. over SE slope.														
18.00	Ridge, bears W and NE; desc. over NW slope.														
33.00	Dirt road, bears NW and SE.														
40.67	The ¼ sec. cor. of secs. 19 and 24, monumented with a trachyte stone, 14 x 8 x 6 ins., firmly set and plainly mkd. ¼ on W face.														
	At the corner point														
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.														
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T 26 S</td></tr> <tr><td style="text-align: center;">R 4 W</td><td style="text-align: center;">R 3 W</td></tr> <tr><td colspan="2" style="text-align: center;">¼</td></tr> <tr><td colspan="2" style="text-align: center;"> </td></tr> <tr><td style="text-align: center;">S 24</td><td style="text-align: center;">S 19</td></tr> <tr><td colspan="2" style="text-align: center;"> </td></tr> <tr><td colspan="2" style="text-align: center;">1975</td></tr> </table>	T 26 S		R 4 W	R 3 W	¼				S 24	S 19			1975	
T 26 S															
R 4 W	R 3 W														
¼															
S 24	S 19														
1975															
	Bury the mkd. stone alongside the iron post, and raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.														

Dependent Resurvey of the East Boundary of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS

(Restoring the 1878 survey by A. D. Ferron)

N. 0°40' E., beginning new measurement.

Desc. over NW slope.

3.50 Draw, drains NW; asc. over SW slope.

15.10 Ridge, bears E and W; desc. over N slope.

38.94 The cor. of secs. 13, 18, 19, and 24, monumented with a tracyte stone, 14 x 12 x 6 ins., firmly set and plainly mkd. 3 notches on N and S edges.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 S	
R 4 W R 3 W	
S 13	S 18
S 24	S 19

1975

Bury the mkd. stone alongside the iron post, and raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

N. 0°23' W., bet. secs. 13 and 18.

Over rolling land; desc. over gentle N slope.

23.90 Dirt road, bears NW and SE; asc. gentle SW slope.

40.33 The ¼ sec. cor. of secs. 13 and 18, monumented with a porphyry rock, 20 x 14 x 6 ins., firmly set and plainly mkd. ¼ on W face.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 S	
R 4 W R 3 W	
¼	
S 13	S 18

1975

Bury the mkd. stone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

N. 0°02' E., beginning new measurement.

Asc. SW slope.

Dependent Resurvey of the East Boundary of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS		
10.00	Spur, slopes NW; desc. over NW slope.	
39.93	<p>The cor. of secs. 7, 12, 13, and 18, monumented with a porphyry stone, 15 x 12 x 8 ins., firmly set and dimly mkd. 3 notches on S and 2 notches on N edge.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 S R 4 W R 3 W S 12 S 7 S 13 S 18 1975</p> </div> <p>Bury the mkd. stone alongside the iron post.</p>	
	N. 1°24' W., bet. secs. 7 and 12.	
	Over rolling land, covered with shadscale and sagebrush.	
37.60	Dirt road, bears N. 10° E. and S. 10° W.	
40.44	<p>Point for the ¼ sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 S R 4 W R 3 W ¼ S 12 S 7 1975</p> </div> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p>	
46.90	Dirt road, bears NE and SW.	
48.20	Draw, drains NW.	
51.00	Same road, bears NW and SE.	
55.30	Same road, bears NE and SW.	
60.50	Same draw, drains NE.	
66.50	Top of small hill, bears N. 30° E. and S. 30° W.; desc. over NW slope.	
80.88	The cor. of secs. 1, 6, 7, and 12, monumented with a limestone, 18 x 12 x 5 ins., firmly set and plainly mkd. 5 notches on S and 1 notch on N edge.	

Dependent Resurvey of the East Boundary of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS																	
	<p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td colspan="2">T 26 S</td></tr> <tr><td colspan="2">R 4 W R 3 W</td></tr> <tr><td colspan="2"> </td></tr> <tr><td>S 1</td><td>S 6</td></tr> <tr><td>—</td><td>—</td></tr> <tr><td>S 12</td><td>S 7</td></tr> <tr><td colspan="2"> </td></tr> <tr><td colspan="2">1975</td></tr> </table> </div> <p>Bury the mkd. stone alongside the iron post.</p>	T 26 S		R 4 W R 3 W				S 1	S 6	—	—	S 12	S 7			1975	
T 26 S																	
R 4 W R 3 W																	
S 1	S 6																
—	—																
S 12	S 7																
1975																	
<p>10.50</p> <p>31.30</p> <p>40.26</p>	<p>N. 0°29' W., bet. secs. 1 and 6.</p> <p>Over rolling land, covered with shadscale and sagebrush.</p> <p>Draw, drains NW.</p> <p>Trail road, bears E and W.</p> <p>The ¼ sec. cor. of secs. 1 and 6, monumented with a trachyte stone, 15 x 7 x 6 ins., firmly set and plainly mkd. ¼ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a collar of stone, 3 ft. base to top of brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td colspan="2">T 26 S</td></tr> <tr><td colspan="2">R 4 W R 3 W</td></tr> <tr><td colspan="2"> </td></tr> <tr><td colspan="2">¼</td></tr> <tr><td colspan="2"> </td></tr> <tr><td>S 1</td><td>S 6</td></tr> <tr><td colspan="2"> </td></tr> <tr><td colspan="2">1975</td></tr> </table> </div> <p>Bury the mkd. stone alongside the iron post.</p>	T 26 S		R 4 W R 3 W				¼				S 1	S 6			1975	
T 26 S																	
R 4 W R 3 W																	
¼																	
S 1	S 6																
1975																	
<p>8.30</p> <p>40.33</p>	<p>N. 0°31' W., beginning new measurement.</p> <p>Trail road, bears NW and SE.</p> <p>The closing cor. of Tps. 26 S., Rs. 3 and 4 W., on the S. bdy. of T. 25 S., R. 3 W., (Fifth Standard Parallel South) monumented with a granite stone, 17 x 10 x 6 ins., firmly set and plainly mkd. 6 notches on N, S, E, and W edges and CC on S face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.</p>																

Dependent Resurvey of the East Boundary of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS

T 25 S R 3 W

S 31	
S 1	S 6

C C

T 26 S

R 4 W R 3 W

1975

Bury the mkd. stone alongside the iron post.

From this corner, the standard cor. of Tps. 25 S., Rs. 3 and 4 W., bears S. $89^{\circ}43'$ W., 8.36 chs. dist., monumented with an iron post, $2\frac{1}{2}$ ins. diam., extending 9 ins. above ground, with brass cap mkd. as described in the 1970-71 resurvey of a portion of the Fifth Standard Parallel South in R. 3 W.

From the same cor., the standard $\frac{1}{4}$ sec. cor. of sec. 31, T. 25 S., R. 3 W., bears N. $89^{\circ}43'$ E., 31.88 chs. dist., monumented with an iron post, $2\frac{1}{2}$ ins. diam., extending 8 ins. above ground, with brass cap mkd. as described in the 1970-71 resurvey of a portion of the Fifth Standard Parallel South in R. 3 W.

Dependent Resurvey of the East Boundary of
T. 26 S., R. $4\frac{1}{2}$ W., Salt Lake Meridian, Utah

(Restoring the 1896 survey by John T. Breckon)

Point for the closing cor. of Tps. 26 S., Rs. 4 and $4\frac{1}{2}$ W., determined by an extension of the E. bdy. of T. 26 S., R. $4\frac{1}{2}$ W., from the original closing cor. of Tps. 26 S., Rs. 4 and $4\frac{1}{2}$ W., to an intersection with the N. bdy. of T. 27 S., R. 4 W.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.

C C	
T 26 S	
R $4\frac{1}{2}$ W R 4 W	
S 36	S 30
S 2	

T 27 S R 4 W
1975

from which

A pinon, 10 ins. diam., bears N. 43° E., 27 lks. dist., mkd. T26S R4W S30 BT.

A cedar, 5 ins. diam., bears N. 23° W., 42 lks. dist., mkd. BT.

N. $0^{\circ}56'$ W., along the E. bdy. of sec. 36, T. 26 S., R. $4\frac{1}{2}$ W.

Dependent Resurvey of the East Boundary of
T. 26 S., R. 4½ W., Salt Lake Meridian, Utah

CHAINS

- Over mountain land, covered with juniper, pinon and oak brush; asc. over gentle SE slope.
- 0.60 The original closing cor. of Tps. 26 S., Rs. 4 and 4½ W., monumented with a sandstone, 18 x 12 x 6 ins., firmly set and plainly mkd. 6 notches on N, E, and W edges and CC on N face. The letters "AM" were added to this stone.
- 5.00 Small draw, drains S. 35° E.; asc. over SE slope.
- 35.50 Ridge, bears E and W; desc. over N slope on ridge.
- 40.64 Point for the E ¼ sec. cor. of sec. 36, T. 26 S., R. 4½ W., at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
- T 26 S
R 4½ W R 4 W
¼ |
S 36 |
1975
- from which
- A pinon, 14 ins. diam., bears S. 10° W., 50 lks. dist., mkd. ¼ S36 BT.
- 42.94 The W ¼ sec. cor. of sec. 30, T. 26 S., R. 4 W., hereinafter described.
- 56.30 Ravine, drains N. 44° E.; asc. over SE slope.
- 78.00 Spur, slopes E; desc. over N slope.
- 80.68 Point for the cor. of secs. 25 and 36, T. 26 S., R. 4½ W., at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.
- T 26 S
R 4½ W R 4 W
S 25 |
S 36 | S 30
1975
- from which
- A cedar, 10 ins. diam., bears S. 72° W., 26 lks. dist., mkd. S36 BT.
- Cor. is located 30 lks. S of bulldozed road to mining claims.

Dependent Resurvey of the East Boundary of
T. 26 S., R. 4½ W., Salt Lake Meridian, Utah

CHAINS	
	<p>N. 0°56' W., along the E. bdy. of sec. 25, T. 26 S., R. 4½ W.</p>
	<p>Over mountainous land, covered with juniper, pinon and oak brush; desc. N slope.</p>
2.30	<p>The closing cor. of secs. 19 and 30, T. 26 S., R. 4 W., hereinafter described.</p>
4.20	<p>Draw, drains E; asc. over SE slope.</p>
15.30	<p>Ridge, bears N. 66° E. and S. 66° W.; desc. over N slope.</p>
29.00	<p>Draw, drains N. 72° E.; thence along E slope of small spur, in bottom of draw.</p>
32.50	<p>Small spur in draw, slopes E, about 6.00 chs. to end.</p>
35.80	<p>Ravine, drains E, about 6.00 chs. to main wash; asc. over SE slope.</p>
40.04	<p>Point for the E ¼ sec. cor. of sec. 25, T. 26 S., R. 4½ W., at proportionate distance; there is no remaining evidence of the original corner.</p>
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.</p>
	<div style="text-align: center;"> <p>T 26 S R 4½ W R 4 W ¼ S 25 1975</p> </div>
	<p>Asc. over steep SE slope.</p>
42.29	<p>The W ¼ sec. cor. of sec. 19, T. 26 S., R. 4 W., hereinafter described; asc. over broken SE slope.</p>
59.80	<p>Ridge, bears N. 80° E. and S. 80° W.; desc. over steep N slope.</p>
68.10	<p>Draw, drains N. 81° E.; asc. broken SE slope.</p>
80.08	<p>Point for the cor. of secs. 24 and 25, T. 26 S., R. 4½ W., at proportionate distance; there is no remaining evidence of the original corner.</p>
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base to top of brass cap, mkd.</p>
	<div style="text-align: center;"> <p>T 26 S R 4½ W R 4 W S 24 S 19 S 25 1975</p> </div>
	<p>Cor. is located on spur, which slopes SE.</p>

Dependent Resurvey of the East Boundary of
T. 26 S., R. 4½ W., Salt Lake Meridian, Utah

CHAINS	
	<p>N. 0°56' W., along the E. bdy. of sec. 24, T. 26 S., R. 4½ W.</p>
	<p>Over mountainous land, covered with pinon, juniper and scattering oak brush; desc. NE slope.</p>
2.20	<p>The closing cor. of secs. 18 and 19, T. 26 S., R. 4 W., hereinafter described.</p>
7.70	<p>Draw, drains SE; asc. over SW slope.</p>
40.04	<p>Point for the E ¼ sec. cor. of sec. 24, T. 26 S., R. 4½ W., at proportionate distance; there is no remaining evidence of the original corner.</p>
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.</p>
	<p style="text-align: center;"> T 26 S R 4½ W R 4 W ¼ S 24 1975 </p>
42.29	<p>The W ¼ sec. cor. of sec. 18, T. 26 S., R. 4 W., hereinafter described.</p>
51.40	<p>Spur, slopes S. 10° E. from N. 20° W.; asc. along E slope.</p>
62.90	<p>Spur, slopes E; desc. over NE slope.</p>
67.10	<p>Ravine, drains S. 50° E.; asc. along general E slope.</p>
80.08	<p>The cor. of secs. 13 and 24, T. 26 S., R. 4½ W., monumented with a lava stone, 16 x 10 x 6 ins., mkd. 4 notches on the one edge. Also mound of stone scattered around corner.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 5 ft. base to top of brass cap, mkd.</p>
	<p style="text-align: center;"> T 26 S R 4½ W R 4 W S 13 S 18 S 24 1975 </p>
	<p>Place the mkd. stone alongside the iron post in a mound of stone.</p>
	<p>N. 0°48' W., along the E. bdy. of sec. 13, T. 26 S., R. 4½ W.</p>
	<p>Over broken and mountainous land, covered with juniper, pinon and scattering oak brush; asc. along E slope.</p>

Dependent Resurvey of the East Boundary of
T. 26 S., R. 4½ W., Salt Lake Meridian, Utah

CHAINS	
2.30	The closing cor. of secs. 7 and 18, T. 26 S., R. 4 W., hereinafter described.
4.60	Low spur, slopes E; desc. N slope.
10.70	Ravine, drains E; asc. over SE slope.
20.80	Spur, slopes E; desc. steep NE slope.
30.10	Draw, drains N. 47° E.; asc. along steep E slope.
40.00	Point for the E ¼ sec. cor. of sec. 13, T. 26 S., R. 4½ W., at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.
	<p>T 26 S R 4½ W R 4 W ¼ S 13 1975</p>
	Cor. is located 1.00 ch. S of small ravine, which drains E; continue along E slope.
42.27	The W ¼ sec. cor. of sec. 7, T. 26 S., R. 4 W., hereinafter described.
53.70	Ridge, bears N. 75° E. and S. 75° W.; desc. over steep NW slope.
71.50	Draw, drains N. 75° E. from SW; asc. along E slope.
77.20	Ridge, bears NE and SW; desc. steep NW slope.
80.00	point for the cor. of secs. 12 and 13, T. 26 S., R. 4½ W., at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.
	<p>T 26 S R 4½ W R 4 W S 12 S 7 S 13 1975</p>
	from which
	<p>A pinon, 12 ins. diam., bears S. 60° W., 3 lks. dist., mkd. T26S R4½W S13 BT.</p>

Dependent Resurvey of the East Boundary of
T. 26 S., R. 4½ W., Salt Lake Meridian, Utah

CHAINS	
	N. 0°48' W., along the E. bdy. of sec. 12, T. 26 S., R. 4½ W.
	Over mountainous land, covered with scattering juniper and pinon; desc. over steep NW slope.
2.24	The closing cor. of secs. 6 and 7, T. 26 S., R. 4 W., hereinafter described.
18.00	Ravine, drains W; asc. along W slope.
27.00	Spur, slopes W; desc. along W slope.
40.00	Point for the E ¼ sec. cor. of sec. 12, T. 26 S., R. 4½ W., at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of brass cap mkd.
	<pre> T 26 S R 4½ W R 4 W ¼ S 12 1975 </pre>
	Cor. is located in small wash, which drains NW; desc. over irregularly NW slope.
42.24	The W ¼ sec. cor. of sec. 6, T. 26 S., R. 4 W., hereinafter described. Desc. over general NW slope, over series of spurs and small draws, draining NW.
69.20	Dry Wash Canyon, drains NE; also unimproved road in canyon; asc. SE slope.
81.90	Intersect the Fifth Standard Parallel South.
	Point for the closing cor. of Tps. 26 S., Rs. 4 and 4½ W., at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., on solid rock, over an "X", in a mound of stone, 4 ft. base to top of brass cap, mkd.
	<pre> T 25 S R 4 W S 31 ----- S 12 S 6 C C R 4½ W R 4 W T 26 S 1975 </pre>
	From this corner, the standard cor. of Tps. 25 S., Rs. 4 and 4½ W., bears S. 89°37' W., 8.69 chs. dist., monumented with an iron post, 2½ ins. diam., set in a mound of stone to top of brass cap mkd. as described in the resurvey of the Fifth Standard Parallel South in R. 4 W., in 1971.

637

Dependent Resurvey of the East Boundary of
T. 26 S., R. 4½ W., Salt Lake Meridian, Utah


CHAINS	
	<p>From the same closing cor., the standard ¼ sec. cor. of sec. 31, T. 25 S., R. 4 W., bears N. 89°37' E., 31.33 chs. dist., monumented with an iron post, 2½ ins. diam., set in a mound of stone to top of brass cap mkd. as described in the resurvey of the Fifth Standard Parallel South in R. 4 W., in 1971.</p>
	<p>Dependent Resurvey of the Subdivisional Lines of T. 26 S., R. 4 W., Salt Lake Meridian, Utah</p>
	<p>(Restoring the 1896 survey and the 1898 corrective survey by J. T. Breckon)</p>
	<p>From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp.</p>
	<p>N. 89°56' W., bet. secs. 24 and 25.</p>
	<p>Over mountainous land, through scattering juniper and pinon; asc. over SE slope.</p>
10.00	<p>Spur, slopes S; desc. along S slope.</p>
20.00	<p>Draw, drains SE; asc. over NE slope.</p>
38.50	<p>Ridge, bears NW and SE; desc. over W slope.</p>
40.08	<p>The ¼ sec. cor. of secs. 24 and 25, monumented with a trachyte stone, 16 x 12 x 6 ins., firmly set and plainly mkd. ¼ on N face.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 26 S R 4 W</p>
	<p style="text-align: center;">¼ $\frac{S\ 24}{S\ 25}$</p>
	<p style="text-align: center;">1975</p>
	<p>Bury the mkd. stone alongside the iron post, and raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.</p>
	<p>N. 89°42' W., beginning new measurement.</p>
	<p>Desc. over W slope.</p>
17.00	<p>Draw, drains NW, from S; asc. over NE slope.</p>
39.00	<p>Spur, slopes NW; desc. over W slope.</p>
40.20	<p>The cor. of secs. 23, 24, 25, and 26, monumented with a trachyte stone, 16 x 8 x 6 ins., firmly set and plainly mkd. 2 notches on S and 1 notch on E edge.</p>

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.



Place the mkd. stone alongside the iron post in a mound of stone.


S. 0°19' W., bet. secs. 25 and 26.

Over mountainous land, through juniper and pinon; asc. along W slope.

15.00 Slope changes; asc. over steep N slope.

40.95 Point for the ¼ sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.



42.00 Spur, slopes E; asc. along E slope.

58.00 High spur, slopes SE; desc. over SW slope.

65.00 Slope changes; desc. over steep S slope.

84.64 The closing cor. of secs. 25 and 26, monumented with a granite stone, 14 x 6 x 6 ins., firmly set and dimly mkd. 5 notches on W and 1 notch on E edges, CC on N face, from which the original bearing trees

A cedar, 24 ins. diam., bears N. 49°50' E., 7 lks. dist., with faint scribe marks.

A cedar, 20 ins. diam., bears N. 36° W., 23 lks. dist., with faint scribe marks.

This cor. will now function as an amended monument and the letters "AM" were stamped on the original stone.

84.84 Intersect the N. bdy. of T. 27 S., R. 3 W.

Point for the closing cor. of secs. 25 and 26.

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of brass cap, mkd.

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS

T 26 S R 4 W
C C
|
S 26 | S 25
S 3
T 27 S R 3 W
1975

From this cor., the cor. of secs. 3 and 4, T. 27 S., R.3 W., bears S. 89°00' W., 16.31 chs. dist., previously described.

From the same cor., the N ¼ sec. cor. of sec. 3, T. 27 S., R. 3 W., bears N. 89°00' E., 24.16 chs. dist., previously described.

From this same closing cor., U.S.G.S. triangulation station "Flat Top" bears N. 9°26' W., 36.61 chs. dist., monumented with a standard brass tablet 3 ins. diam., set in concrete on rock outcrop.

Point for the S ¼ sec. cor. of sec. 25, T. 26 S., R. 4 W., on the N. bdy. of T. 27 S., R. 3 W., and midpoint bet. the closing cor. of Tps. 26 S., Rs. 3 and 4 W., and the closing cor. of secs. 25 and 26, T. 26 S., R. 4 W.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T 26 S R 4 W

¼ S 25
T 27 S R 3 W
1975

Set a cedar post, 6 ins. diam., 5 ft. high, alongside the iron post.

From this cor., the cor. of secs. 2 and 3, T. 27 S., R. 3 W., bears N. 89°00' E., 24.29 chs. dist., previously described.

From this same cor., the N ¼ sec. cor. of sec. 3, T. 27 S., R. 3 W., bears S. 89°00' W., 16.18 chs. dist., previously described.

From the cor. of secs. 23, 24, 25, and 26.

N. 0°09' E., bet. secs. 23 and 24.

Over mountainous land, through scattering juniper and pinon timber; desc. along W slope.

5.00 Spur, slopes NW; desc. over NE slope.

16.00 Draw, drains NW; asc. over SW slope.

25.50 Ridge, bears E and NW; desc. over N slope.

38.00 Draw, drains N. 10° E.; desc. along E slope of draw.

40.20 The ¼ sec. cor. of secs. 23 and 24, monumented with a trachyte stone, 16 x 10 x 6 ins., firmly set and plainly mkd. ¼ on W face.

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T 26 S R 4 W
|
¼
S 23 | S 24
|
1975

Bury the mkd. stone alongside the iron post, and raise mound of stone, 3 ft. base, 2 ft. high, W of cor.

Corner is located 50 lks. W of trail road, in bottom of draw, which drains N.

N. 0°43' W., beginning new measurement.

Desc. along E slope, in draw.

23.00 Trail road in draw, bears NW and SE, draw, drains NW; desc. over N slope, over broken land.

39.80 Point for the cor. of secs. 13, 14, 23, and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 S R 4 W
|
S 14 | S 13
S 23 | S 24
|
1975

from which

A cedar, 12 ins. diam., bears N. 65° 34' E., 31 lks. dist., mkd. BT.

A pinon, 14 ins. diam., bears N. 6°30' W., 41 lks. dist., mkd. BT.

Raise a mound of stone, 3 ft. base, 2 ft. high, S of cor.

(Restoring the 1878 survey by A. D. Ferron)

From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp.

N. 89°39' W., bet. secs. 13 and 24.

Over rolling land, covered with shadscale and sagebrush.

40.52 Point for the ¼ sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.

641

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS	
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 S R 4 W</p> <p style="text-align: center;">¼ $\frac{S\ 13}{S\ 24}$</p> <p style="text-align: center;">1975</p> <p>Set a cedar post, 6 ins. diam., 5 ft. high, alongside the iron post, and raise a mound of stone N of corner.</p>
40.67	Trail road in draw, bears N and S, draw drains N; asc. over gentle NE slope, enter scattering juniper and pinon.
55.00	Low ridge, bears N and S; thence along N slope of bench.
81.04	The cor. of secs. 13, 14, 23, and 24.
	<p>N. 0°26' W., bet. secs 13 and 14.</p> <p>Over broken land, covered with juniper and pinon; along W slope.</p>
25.00	Spur, slopes W; continue along W slope.
38.10	Spur, slopes N. 10° W.; desc. over NE slope.
39.80	Point for the ¼ sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 S R 4 W</p> <p style="text-align: center;">¼ S 14 S 13 1975</p>
	Raise a mound of stone, 4 ft. base, 3 ft. high, W of cor.
46.00	Saddle, bears E and W; asc. S slope of hill.
55.00	Top of small hill, bears N. 15° E.; desc. over NW slope.
68.00	Trail road, bears NE and SW, also base of hills; desc. over gentle N slope in valley.
79.60	The cor. of secs. 11, 12, 13, and 14, monumented with a limestone, 12 x 8 x 6 ins., firmly set and plainly mkd. 4 notches on S and 1 notch on E edges.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS					
	<p style="text-align: center;">T 26 S R 4 W</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 11</td> <td style="padding: 0 5px;">S 12</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 14</td> <td style="padding: 0 5px;">S 13</td> </tr> </table> <p style="text-align: center;">1975</p> <p>Bury the mkd. stone alongside the iron post, and set steel fence post alongside the corner.</p>	S 11	S 12	S 14	S 13
S 11	S 12				
S 14	S 13				
	<p>From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp.</p> <p>N. 89°36' W., bet. secs. 12 and 13.</p> <p>Over broken land, covered with shadscale and sagebrush; asc. gentle NE slope.</p>				
13.00	Dirt road, bears N. 30° E. and S. 30° W.				
28.00	Low ridge, bears N and S; desc. over SW slope.				
41.00	The $\frac{1}{4}$ sec. cor. of secs. 12 and 13, monumented with a trachyte stone, 12 x 8 x 6 ins., firmly set and plainly mkd. $\frac{1}{4}$ on N face.				
	<p>At the corner point</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 26 S R 4 W</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">$\frac{1}{4}$</td> <td style="border-right: 1px solid black; padding: 0 5px;">S 12</td> <td style="padding: 0 5px;">S 13</td> </tr> </table> <p style="text-align: center;">1975</p> <p>Bury the mkd. stone alongside the iron post.</p>	$\frac{1}{4}$	S 12	S 13	
$\frac{1}{4}$	S 12	S 13			
	<p style="text-align: center;">_____</p> <p>S. 89°14' W., beginning new measurement.</p> <p>Desc. gentle SW slope.</p>				
18.80	Wash, drains NW; asc. gentle NE slope.				
31.00	Dirt road, bears NW and SE.				
40.37	The cor. of secs. 11, 12, 13, and 14.				
	<p>N. 0°47' W., bet. secs. 11 and 12.</p> <p>Over rolling land, covered with shadscale and sagebrush; desc. over gentle NE slope.</p>				
9.00	Dirt road, bears NW and SE.				
40.41	The $\frac{1}{4}$ sec. cor. of secs. 11 and 12, monumented with a trachyte stone, 13 x 10 x 4 ins., firmly set and plainly mkd. $\frac{1}{4}$ on W face.				

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS	
	<p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 S R 4 W</p> <p>¼</p> <p> </p> <p>S 11 S 12</p> <p> </p> <p>1975</p> </div> <p>Bury the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°56' W., beginning new measurement.</p>
2.50	Wash, 30 lks. wide, 2 ft. deep, drains NW; asc. over SW slope of hill.
24.50	Ridge, bears NW and E; desc. over NW slope.
39.89	The cor. of secs. 1, 2, 11, and 12, monumented with a trachyte stone, 12 x 6 x 4 ins., firmly set and plainly mkd. 5 notches on S and 1 notch on E edges.
	<p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 S R 4 W</p> <p> </p> <p>S 2 S 1</p> <p>— —</p> <p>S 11 S 12</p> <p> </p> <p>1975</p> </div> <p>Bury the mkd. stone alongside the iron post.</p> <p>Corner is located at fence cor.; fences bear N and W.</p>
	<p>From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp.</p> <p>S. 89°43' W., bet. secs. 1 and 12.</p> <p>Over broken land, covered with shadscale and sagebrush; along gentle N slope.</p>
9.20	Small wash, drains N; asc. over NE slope.
19.90	Spur, slopes N; desc. over NW slope.
33.00	Small draw, drains N; asc. over NE slope.
39.97	The ¼ sec. cor. of secs. 1 and 12, monumented with a limestone, 20 x 10 x 5 ins., firmly set and plainly mkd. ¼ on N face.
	<p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.</p>

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS	
	<p style="text-align: center;">T 26 S R 4 W</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S 1}{S 12}$</p> <p style="text-align: center;">1975</p> <p>Place the mkd. stone alongside the iron post, in a mound of stone.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°07' W., beginning new measurement.</p> <p>Asc. NE slope.</p>
25.50	Spur, slopes N. 38° E.; desc. over NW slope.
40.53	The cor. of secs. 1, 2, 11, and 12.
	<p>N. 0°12' W., bet. secs. 1 and 2.</p> <p>Over broken land, covered with shadscale and sagebrush; desc. over N slope.</p>
4.50	Small wash, drains N. 25° E.; desc. over gentle NE slope.
40.18	<p>The $\frac{1}{4}$ sec. cor. of secs. 1 and 2, monumented with a limestone, 14 x 8 x 6 ins., firmly set and plainly mkd. $\frac{1}{4}$ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 S R 4 W</p> <p style="text-align: center;">$\frac{1}{4}$</p> <p style="text-align: center;">S 2 S 1</p> <p style="text-align: center;">1975</p> <p>Bury the mkd. stone alongside the iron post, and set steel fence post alongside the corner.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°05' W., beginning new measurement.</p> <p>Along gentle E slope.</p>
25.00	Base of hill, bears NE and SW; asc. SE slope.
40.22	<p>The closing cor. of secs. 1 and 2, on the S. bdy. of T. 25 S., R. 4 W., (Fifth Standard Parallel South) monumented with a limestone, 16 x 12 x 6 ins., firmly set and plainly mkd. 5 notches on W and 1 notch on E edges, and CC on S face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of brass cap, mkd.</p>

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS

T 25 S R 4 W
S 36

S 2 | S 1
C | C
T 26 S R 4 W
1975

Place the mkd. stone in mound alongside the iron post.

From this cor., the standard cor. of secs. 35 and 36, T. 25 S., R. 4 W., bears S. $89^{\circ}17'$ W., 8.73 chs. dist., monumented with an iron post, $2\frac{1}{2}$ ins. diam., in a mound of stone, with brass cap mkd. as described in the 1970-71 resurvey of the Fifth Standard Parallel South, through R. 4 W.

From this same cor., the standard $\frac{1}{4}$ sec. cor. of sec. 36, T. 25 S., R. 4 W., bears N. $89^{\circ}17'$ E., 31.66 chs. dist., monumented with an iron post, $2\frac{1}{2}$ ins. diam., extending 8 ins. above ground, with brass cap mkd. as described in the 1970-71 resurvey of the Fifth Standard Parallel South, through R. 4 W.

Point for the N $\frac{1}{4}$ sec. cor. of sec. 1, T. 26 S., R. 4 W., on the Fifth Standard Parallel South, and midpoint bet. the closing cor. of Tps. 26 S., Rs. 3 and 4 W., and the closing cor. of secs. 1 and 2, T. 26 S., R. 4 W.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T 25 S R 4 W

 $\frac{1}{4}$ S 1
T 26 S R 4 W
1975

From this cor., the standard cor. of Tps. 25 S., Rs. 3 and 4 W., bears N. $89^{\circ}06'$ E., 31.695 chs. dist., monumented with an iron post, $2\frac{1}{2}$ ins. diam., extending 8 ins. above ground, with brass cap mkd. as described in the 1970-71 resurvey of the Fifth Standard Parallel South, through R. 4 W.

From this same cor., the standard $\frac{1}{4}$ sec. cor. of sec. 36, T. 25 S., R. 4 W., bears S. $89^{\circ}06'$ W., 8.395 chs. dist., monumented with an iron post, $2\frac{1}{2}$ ins. diam., extending 8 ins. above ground, with brass cap mkd. as described in the 1970-71 resurvey of the Fifth Standard Parallel South, through R. 4 W.

(Restoring the 1896 survey and the 1898
corrective resurvey by J. T. Breckon)

From the cor. of secs. 23, 24, 25, and 26.

N. $89^{\circ}59'$ W., bet. secs. 23 and 26.

Over mountainous land, covered with scattering juniper and pinon; along broken N slope.

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS		
28.00	High spur, slopes N; desc. over W slope.	
37.00	Draw, drains N; asc. over E slope.	
40.04	<p>The $\frac{1}{4}$ sec. cor. of secs. 23 and 26, monumented with a sandstone, 18 x 12 x 6 ins., firmly set and plainly mkd. $\frac{1}{4}$ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 26 S R 4 W</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S\ 23}{S\ 26}$</p> <p style="text-align: center;">1975</p> <p>Bury the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. $89^{\circ}49'$ W., beginning new measurement.</p> <p>Asc. broken E slope.</p>	
18.40	Ridge, bears S and NW; desc. over SW slope.	
40.73	<p>Intersect line 1-2, Mineral Survey No. 5264, Hard to Crack No. 3 claim.</p> <p>From this intersection cor. No. 1, identical with cors. No. 1, Hard to Crack Nos. 1 and 2 lodes of the same survey, bears N. $82^{\circ}35'$ W., 0.07 chs. dist., marked by a cedar post, 4 ins. diam., 4 ft. high, in a mound of stone, from which the original bearing trees</p> <p style="padding-left: 40px;">A pinon, 8 ins. diam., bears S. $67^{\circ}15'$ W., 0.727 chs. dist., mkd. with faint scribe marks.</p> <p style="padding-left: 40px;">A cedar, 18 ins. diam., bears S. 89° W., 0.93 chs. dist., mkd. with faint scribe marks.</p> <p>From this same intersection, cor. No. 2, identical with Cor. No. 2 Hard to Beat No. 1 lode of the same survey, bears S. $82^{\circ}35'$ E., 22.90 chs. dist., marked by a cedar post, in a mound of stone, mkd. with faint scribe marks.</p>	
40.86	<p>The cor. of secs. 22, 23, 26, and 27, monumented with a sandstone, 18 x 10 x 8 ins., firmly set and mkd. 2 notches on E and 1 notch on S edge, from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A pinon stump, 3 ft. high, bears S. 67° W., 68 lks. dist., mkd. T.</p> <p style="padding-left: 40px;">A pinon, 15 ins. diam., bears N. 41° W., 135 lks. dist., mkd. T26S R4W S22 BT.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	

647

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS						
	<p style="text-align: center;">T 26 S R 4 W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 22</td> <td style="padding: 0 5px;">S 23</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 27</td> <td style="padding: 0 5px;">S 26</td> </tr> </table> <p style="text-align: center;">1975</p> <p>Bury the mkd. stone alongside the iron post, and raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p>	S 22	S 23	S 27	S 26	
S 22	S 23					
S 27	S 26					
	<p>S. 0°04' E., bet. secs. 26 and 27.</p> <p>Over mountainous land, through juniper and pinon; asc. over N slope.</p>					
9.09	<p>Intersect line 3-4, Mineral Survey No. 5264, Hard to Crack No. 2 claim.</p> <p>From this intersection, cor. No. 4, identical with cor. No. 4 Hard to Crack No. 3 lode of the same survey, bears S. 80°36' E., 0.24 chs. dist., marked by a post in mound of stone, faint scribe marks on post.</p> <p>From this same intersection cor. No. 3, identical with cor. No. 3 Tough Nut No. 2 lode of the same survey, bears N. 80°36' W., 22.52 chs. dist., mkd. by a post in mound of stone, faint scribe marks on post.</p>					
28.00	Ridge, bears E and W; desc. over steep SW slope.					
35.00	Draw, drains W; asc. NW slope.					
41.25	<p>The ¼ sec. cor. of secs. 26 and 27, monumented with a sandstone, 16 x 8 x 5 ins., firmly set and plainly mkd. ¼ on W face, from which the original bearing trees</p> <p style="padding-left: 40px;">A dead pinon, 10 ins. diam., bears N. 85° E., 5 lks. dist., mkd. ¼ S26 BT.</p> <p style="padding-left: 40px;">A cedar, 14 ins. diam., bears N. 73° W., 68 lks. dist., mkd. ¼ S27 BT.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.</p> <p style="text-align: center;">T 26 S R 4 W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 27</td> <td style="padding: 0 5px;">S 26</td> </tr> </table> <p style="text-align: center;">1975</p> <p>Place the mkd. stone alongside the iron post, in a mound of stone.</p>	S 27	S 26			
S 27	S 26					
	<p style="text-align: center;">_____</p> <p>S. 0°06' W., beginning new measurement.</p>					

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS									
3.00	Spur, slopes W; desc. over SW slope.								
6.00	Draw, drains W; asc. over NW slope.								
12.00	High spur, slopes W; thence over series of spurs and draws, draining W.								
27.28	Intersect line 2-3, Mineral Survey No. 7292, Farmer John No. 1.								
	From this intersection cor. No. 2, identical with cor. No. 4, Farmer John lode of the same survey, bears S. 89° 15' W., 22.67 chs. dist., monumented with an iron post, 2 ins. diam., with cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr><td style="text-align: center;">S E</td><td style="border-left: 1px solid black; border-right: 1px solid black;"></td></tr> <tr><td style="text-align: center;">JENNIE</td><td style="border-left: 1px solid black; border-right: 1px solid black;"></td></tr> <tr><td style="text-align: center;">7292</td><td style="border-left: 1px solid black; border-right: 1px solid black;">2 F J I</td></tr> <tr><td style="text-align: center;">4 F J</td><td style="border-left: 1px solid black; border-right: 1px solid black;"></td></tr> </table>	S E		JENNIE		7292	2 F J I	4 F J	
S E									
JENNIE									
7292	2 F J I								
4 F J									
	From this same intersection cor. No. 3, bears N. 89° 15' E., 0.06 chs. dist., monumented with a steel rod, 1/2 ins. diam., with cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr><td style="text-align: center;">R L S</td></tr> <tr><td style="text-align: center;">3 1 5 5</td></tr> </table>	R L S	3 1 5 5						
R L S									
3 1 5 5									
33.00	Spur, slopes W; desc. along steep W slope.								
43.31	Intersect the N. bdy. of T. 27 S., R. 3 W.								
	Point for the closing cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original corner.								
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of brass cap, mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr><td style="text-align: center;">C C</td></tr> <tr><td style="text-align: center;">T 26 S R 4 W</td></tr> <tr><td style="text-align: center;"> </td></tr> <tr><td style="text-align: center;">S 27 S 26</td></tr> <tr><td style="text-align: center;">S 4</td></tr> <tr><td style="text-align: center;">T 27 S R 3 W</td></tr> <tr><td style="text-align: center;">1975</td></tr> </table>	C C	T 26 S R 4 W		S 27 S 26	S 4	T 27 S R 3 W	1975	
C C									
T 26 S R 4 W									
S 27 S 26									
S 4									
T 27 S R 3 W									
1975									
	From this cor., the cor. of secs. 4 and 5, T. 27 S., R. 3 W., bears N. 89°23' W., 15.35 chs. dist., previously described.								
	From this same cor., the N ¼ sec. cor. of sec. 4, T. 27 S., R. 3 W., bears S. 89°23' E., 24.42 chs. dist., previously described.								
	Point for the S ¼ sec. cor. of sec. 26, T. 26 S., R. 4 W., on the N. bdy. of T. 27 S., R. 3 W., and midpoint bet. the closing cor. of secs. 25 and 26, and the closing cor. of secs. 26 and 27, T. 26 S., R. 4 W.								
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 4 ft. base to top of brass cap, mkd.								

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS

T 26 S R 4 W
 $\frac{1}{4}$ S 26
T 27 S R 3 W
1975

Cor. is located on steep S slope, in loose slide rock.

From this cor., the N $\frac{1}{4}$ sec. cor. of sec. 4, T. 27 S., R. 3 W., bears N. 89°23' W., 15.83 chs. dist., previously described.

From the same cor., the cor. of secs. 3 and 4, T. 27 S., R. 3 W., bears S. 89°23' E., 23.94 chs. dist., previously described.

From the cor. of secs. 22, 23, 26, and 27.

N. 2°43' W., bet. secs. 22 and 23.

Over mountainous land, covered with juniper and pinon; asc. long W slope.

9.31 Intersect line 3-4, Mineral Survey No. 5264, Hard to Crack No. 1 claim.

From this intersection, cor. No. 4, bears S. 80°42' E., 1.45 chs. dist., marked by a pine post, in a mound of stone, 4 ins. square, scribed 4-5264.

From this same intersection, cor. No. 1, Mineral Survey No. 5264, North Side Lode, bears N. 80°42' W., 11.34 chs. dist., marked by a pine post, in a mound of stone, scribed 1-5264.

15.00 Mouth of small draw, drains SW; asc. over S slope.

40.36 The $\frac{1}{4}$ sec. cor. of secs. 22 and 23, monumented with a limestone, 16 x 12 x 6 ins., firmly set and plainly mkd. $\frac{1}{4}$ on W face.

At the corner point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 S R 4 W
 $\frac{1}{4}$
S 22 | S 23
1975

from which

A cedar, 6 ins. diam., bears S. 88° E., 160 lks. dist., mkd. $\frac{1}{4}$ S23 BT.

Bury the mkd. stone alongside the iron post, and raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS					
	<p>N. 1°57' E., beginning new measurement.</p> <p>Asc. over S slope.</p> <p>4.00 Ridge, bears E and W; desc. over NW slope.</p> <p>31.20 Trail road in draw, which drains S. 80° W.; asc. over S slope.</p> <p>40.10 The cor. of secs. 14, 15, 22 and 23, monumented with a trachyte stone, 17 x 10 x 6 ins., firmly set and dimly mkd. 2 notches on E edge, with a large mound of stone W of cor.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.</p> <div style="text-align: center;"> <p>T 26 S R 4 W</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 15</td> <td style="padding: 0 5px;">S 14</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 22</td> <td style="padding: 0 5px;">S 23</td> </tr> </table> <p>1975</p> </div> <p>Place the mkd. stone in mound alongside the iron post, and raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p>	S 15	S 14	S 22	S 23
S 15	S 14				
S 22	S 23				
	<p style="text-align: center;">(Restoring the 1896 survey by J. T. Breckon)</p> <hr style="width: 20%; margin: auto;"/> <p>From the cor. of secs. 13, 14, 23, and 24.</p> <p>N. 89°38' W., bet. secs. 14 and 23.</p> <p>Over mountain land, covered with juniper and pinon; along N slope.</p> <p>12.00 Trail road in draw, bears N and S, draw drains N.</p> <p>19.00 Spur, slopes N; desc. over NW slope.</p> <p>30.00 Ravine, drains NE; also trail road, bears NE and SW; asc. E slope.</p> <p>40.52 Point for the ¼ sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 S R 4 W</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">¼ S 14</td> <td style="padding: 0 5px;">S 23</td> </tr> </table> <p>1975</p> </div>	¼ S 14	S 23		
¼ S 14	S 23				

651

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS	
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.</p> <p>From this cor., cor. No. 1, Mineral Survey No. 6677, Yellow Jacket No. 6 claim, bears N. 17°12' W., 3.897 chs. dist., marked by a squared post, 6677 only legible marks, from which the original bearing tree</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears S. 47°39' E., 3.30 chs. dist., mkd. 1-4-6677 BT.</p> <p>At the corner point</p>
68.00	Slope changes; thence along S slope.
69.50	Trail road, bears N and S.
81.04	The cor. of secs. 14, 15, 22, and 23.
	<p>N. 0°45' W., bet. secs. 14 and 15.</p> <p>Over mountainous land, covered with scattering juniper and pinon; asc. SE slope.</p>
13.00	Trail road, bears E and W.
19.00	Spur, slopes E; desc. over NE slope.
35.00	Small spur, slopes N. 40° E.; desc. over N slope.
39.00	Ravine, drains NE; asc. over SE slope.
40.08	Point for the ¼ sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original corner.
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 S R 4 W</p> <p> </p> <p> ¼</p> <p> </p> <p> S 15 S 14</p> <p> </p> <p> 1975</p> </div>
	<p>Raise a mound of stone, 5 ft. base, 3 ft. high, W of cor.</p>
46.40	Spur, slopes NE; desc. over NW slope.
59.00	Draw, drains N. 10° E.; desc. over NE slope.
80.16	The cor. of secs. 10, 11, 14 and 15, monumented with a sandstone, 16 x 10 x 6 ins., firmly set, marks have weathered away, mound of stone W of cor.
	<p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS					
	<p style="text-align: center;">T 26 S R 4 W</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S 10</td> <td style="padding: 2px 5px;">S 11</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S 15</td> <td style="padding: 2px 5px;">S 14</td> </tr> </table> <p style="text-align: center;">1975</p> <p>Place the mkd. stone alongside the iron post, in a mound of stone.</p>	S 10	S 11	S 15	S 14
S 10	S 11				
S 15	S 14				
	<p>(Restoring the 1878 survey by A. D. Ferron)</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the cor. of secs. 11, 12, 13, and 14.</p> <p>N. 89°13' W., bet. secs. 11 and 14.</p> <p>Over rolling land, covered with shadscale and sagebrush, along gentle N slope.</p> <p>7.00 Dirt road, bears N. 15° W. and S. 15° E.</p> <p>16.00 Draw, drains NW.</p> <p>40.72 Point for the ¼ sec. cor. of secs. 11 and 14, at proportionate dist., based on the irregular boundary method, there is no remaining evidence of the original corner position.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 S R 4 W</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 2px 5px;">¼</td> <td style="border-right: 1px solid black; padding: 2px 5px;">S 11</td> <td style="padding: 2px 5px;">S 14</td> </tr> </table> <p style="text-align: center;">1975</p> <p>Raise mound of stone, 3 ft. base, 2 ft. high, N of cor.</p>	¼	S 11	S 14	
¼	S 11	S 14			
	<p>(Restoring the 1896 survey by J. T. Breckon)</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°11' W., beginning new measurement.</p> <p>Asc. over E slope.</p> <p>8.00 Spur, slopes N; desc. over W slope.</p> <p>16.00 Draw, drains N; asc. over NE slope.</p> <p>35.20 Spur, slopes N; desc. over W slope.</p> <p>37.50 Draw, drains N; asc. over E slope.</p> <p>40.74 The cor. of secs. 10, 11, 14, and 15.</p>				

653

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS

N. 0°20' E., bet. secs. 10 and 11.


Over broken land, covered with shadscale and sagebrush;
desc. over N slope.

31.00 Wash, 20 lks. wide, 2 ft. deep, drains N. 20° E.; desc.
over gentle NE slope, leave hills.

40.18 The ¼ sec. cor. of secs. 10 and 11, monumented with a
trachyte stone, 14 x 6 x 6 ins., firmly set and plainly
mkd. ¼ on W face.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.



Bury the mkd. stone alongside the iron post, and raise
mound of stone, 2 ft. base, 2 ft. high, W of cor.

(Restoring the 1878 survey by A. D. Ferron)


N. 0°44' W., beginning new measurement.

Desc. over gentle NE slope.

38.95 The cor. of secs. 2, 3, 10, and 11, monumented with a
trachyte stone, 12 x 8 x 6 ins., firmly set and plainly
mkd. 4 notches on S and 2 notches on E edges.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, in a collar of stone, with brass cap mkd.



Bury the mkd. stone alongside the iron post.

Corner is located in cor. of netwire fence, which bears
N. 10° W. and S. 30° E.

From the cor. of secs. 1, 2, 11, and 12.

S. 89°36' W., bet. secs. 2 and 11.

Over broken hills, covered with shadscale and sagebrush;
desc. over W slope, along fence line.

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS	
1.00	Small ravine, drains N. 25° E.; asc. SE slope.
21.50	Low ridge, bears N. 30° W. and S. 30° E.; desc. SW slope.
27.50	Wash, drains N. 15° W., also base of hills; thence over rolling valley.
38.50	Dirt road, bears N. 9° W. and S. 9° E.
40.10	The ¼ sec. cor. of secs. 2 and 11, monumented with a limestone, 18 x 10 x 6 ins., firmly set and plainly mkd. ¼ on N face.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T 26 S R 4 W
	$\frac{1}{4} \begin{array}{c} S 2 \\ S 11 \end{array}$
	1975
	Bury the mkd. stone alongside the iron post.
	Corner is located in E and W fence line.

	N. 89°37' W., beginning new measurement.
12.00	Draw, drains NE.
22.37	Leave fence line, which bears N. 24° W.
22.80	Dirt road, bears N. 24° W. and S. 24° E.
40.43	The cor. of secs. 2, 3, 10,, and 11.
	N. 0°21' W., bet. secs. 2 and 3.
	Over valley land, covered with shadscale and sagebrush; desc. gentle NE slope.
39.83	The ¼ sec. cor. of secs. 2 and 3, monumented with a trachyte stone, 16 x 12 x 6 ins., firmly set and plainly mkd. ¼ on W face.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T 26 S R 4 W
	$\frac{1}{4} \begin{array}{c} \\ S 3 \quad \quad S 2 \\ \end{array}$
	1975
	Bury the mkd. stone alongside the iron post.

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS							
	N. 0°25' W., beginning new measurement.						
3.00	Dirt road, bears N. 24° W. and S. 24° E.						
19.80	Draw, drains NW.						
40.27	The closing cor. of secs. 2 and 3, on the S. bdy. of T. 25 S., R. 4 W., (Fifth Standard Parallel South) monumented with a trachyte stone, 24 x 12 x 8 ins., firmly set and plainly mkd., 4 notches on W and 2 notches on E edges, CC on S face.						
	At the corner point						
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.						
	<table style="margin: auto;"> <tr><td>T 25 S R 4 W</td></tr> <tr><td style="border-bottom: 1px solid black;">S 35</td></tr> <tr><td>S 3 S 2</td></tr> <tr><td style="text-align: center;">C C</td></tr> <tr><td>T 26 S R 4 W</td></tr> <tr><td>1975</td></tr> </table>	T 25 S R 4 W	S 35	S 3 S 2	C C	T 26 S R 4 W	1975
T 25 S R 4 W							
S 35							
S 3 S 2							
C C							
T 26 S R 4 W							
1975							
	Bury the mkd. stone alongside the iron post.						
	From this cor., the standard cor. of secs. 34 and 35, T. 25 S., R. 4 W., bears S. 89°47' W., 8.605 chs. dist., monumented with an iron post, 2½ ins. diam., extending 8 ins. above ground, with brass cap mkd. as described in the 1970-71 resurvey of the Fifth Standard Parallel South, through R. 4 W.						
	From this same cor., the standard ¼ sec. cor. of sec. 35, T. 25 S., R. 4 W., bears N. 89°47' E., 31.275 chs. dist., monumented with an iron post, 2½ ins. diam., extending 8 ins. above ground, with brass cap mkd. as described in the 1970-71 resurvey of the Fifth Standard Parallel South, through R. 4 W.						
	Point for the N ¼ sec. cor. of sec. 2, T. 26 S., R. 4 W., on the Fifth Standard Parallel South, and midpoint bet. the closing cor. of secs. 1 and 2, and the closing cor. of secs. 2 and 3, T. 26 S., R. 4 W.						
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.						
	<table style="margin: auto;"> <tr><td>T 25 S R 4 W</td></tr> <tr><td style="border-bottom: 1px solid black;">¼ S 2</td></tr> <tr><td>T 26 S R 4 W</td></tr> <tr><td>1975</td></tr> </table>	T 25 S R 4 W	¼ S 2	T 26 S R 4 W	1975		
T 25 S R 4 W							
¼ S 2							
T 26 S R 4 W							
1975							
	Raise a mound of stone, 2 ft. base, 2 ft. high, S of cor.						
	From this cor., the standard cor. of secs. 35 and 36, T. 25 S., R. 4 W., bears N. 89°53' E., 31.635 chs. dist., monumented with an iron post, 2½ ins. diam., extending 8 ins. above ground, with brass cap mkd. as described in the 1970-71 resurvey of the Fifth Standard Parallel South, through R. 4 W.						

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS	
	<p>From this same corner, the standard $\frac{1}{4}$ sec. cor of sec. 35, T. 25 S., R. 4 W., bears S. $89^{\circ}53'$ W., 9.095 chs. dist., monumented with an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., extending 8 ins. above ground, with brass cap mkd. as described in the 1970-71 resurvey of the Fifth Standard Parallel South, through R. 4 W.</p>
	<p>(Restoring the 1896 survey and the 1898 corrective survey by J. T. Breckon)</p>
	<p>From the cor. of secs. 22, 23, 26 and 27.</p>
	<p>S. $89^{\circ}58'$ W., bet. secs. 22 and 27.</p>
	<p>Over mountain land, through scattering juniper and pinon; asc. over SE slope.</p>
2.00	<p>Trail road, bears NW and SE.</p>
10.00	<p>Slope changes; desc. along broken N slope.</p>
40.03	<p>The $\frac{1}{4}$ sec. cor. of secs. 22 and 27, monumented with a trachyte stone, 12 x 6 x 3 ins., firmly set and plainly mkd. $\frac{1}{4}$ on N face.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T 26 S R 4 W</p>
	<p style="text-align: center;">$\frac{1}{4}$ $\frac{S 22}{S 27}$</p>
	<p style="text-align: center;">1975</p>
	<p>Bury the mkd. stone alongside the iron post.</p>
	<p>S. $89^{\circ}57'$ W., beginning new measurement.</p>
	<p>Along broken N slope.</p>
4.795	<p>Intersect line 1-4, Mineral Survey No. 5264, Tough Nut No. 2 claim.</p>
	<p>From this intersection, cor. No. 1, identical with cor. No. 1, Tough Nut No. 1 lode of the same survey, bears N. $1^{\circ}29'$ W., 5.77 chs. dist., marked with a mound of stone.</p>
	<p>From this same intersection, cor. No. 4, bears S. $1^{\circ}29'$ E., 3.37 chs. dist., marked with a mound of stones.</p>
34.50	<p>Dirt road, bears NE and SW; thence over S edge of sage flat.</p>
41.02	<p>The cor. of secs. 21, 22, 27, and 28, monumented with a sandstone, 18 x 12 x 6 ins., firmly set and plainly mkd. 3 notches on E and 1 notch on S edge.</p>
	<p>At the corner point</p>

657

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.

T 26 S R 4 W
|
S 21 | S 22
S 28 | S 27
|
1975

Bury the mkd. stone alongside the iron post, and set a steel fence post alongside the corner.

S. $0^{\circ}11'$ E., bet. secs. 27 and 28.

Over mountain bench land, covered with shadscale and sagebrush; asc. gentle N slope.

6.00 Dirt road, bears N. 20° E. and S. 20° W.; also saddle, bears E and W; desc. gentle S slope.

40.55 The $\frac{1}{4}$ sec. cor. of secs. 27 and 28, monumented with a granite stone, 14 x 12 x 12 ins. firmly set and plainly mkd. $\frac{1}{4}$ on W face.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 S R 4 W
|
 $\frac{1}{4}$
S 28 | S 27
|
1975

Bury the mkd. stone alongside the iron post, and raise a mound of stone, 2 ft. base, 2 ft. high, W of corner.

S. $0^{\circ}11'$ W., beginning new measurement.

Desc. gentle S slope.

39.00 Draw, drains SW.

43.83 Intersect the N. bdy. of T. 27 S., R. 3 W.

Point for the closing cor. of secs. 27 and 28.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 S R 4 W
C C
|
S 28 | S 27
S 5
T 27 S R 3 W
1975

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS

Raise a mound of stone, 4 ft. base, 3. ft. high, NE of cor.

Corner is located on N edge of wash.

From this cor., the cor. of secs. 5 and 6, T. 27 S., R. 3 W., bears S. $89^{\circ}38'$ W., 14.98 chs. dist., previously described.

From this same cor., the N $\frac{1}{4}$ sec. cor. of sec. 5, T. 27 S., R. 3 W., bears N. $89^{\circ}38'$ E., 25.20 chs. dist., previously described.

From this same cor., the true point for the original closing cor. of secs. 27 and 28, bears S. $0^{\circ}11'$ W., 0.08 chs. dist., determined at record course and distance from the original bearing tree

A cedar, 10 ins. diam., bears N. $71^{\circ}35'$ W., 18 lks. dist., faint scribe marks visible.

This point falls in wash, and was not remonumented,

Point for the S $\frac{1}{4}$ sec. cor. of sec. 27, T. 26 S., R. 4 W., on the N. bdy. of T. 27 S., R. 3 W., and midpoint bet. the closing cor. of secs. 26 and 27, and the closing cor. of secs. 27 and 28, T. 26 S., R. 4 W.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T 26 S R 4 W

$\frac{1}{4}$ S 27

T 27 S R 3 W
1975

from which

A cedar, 7 ins. diam., bears S. 21° E., 50 lks. dist., mkd. BT.

From this cor., the N $\frac{1}{4}$ sec. cor. of sec. 5, T. 27 S., R. 3 W., bears N. $89^{\circ}44'$ W., 15.28 chs. dist., previously described.

From this same cor., the cor. of secs. 4 and 5, T. 27 S., R. 3 W., bears S. $89^{\circ}44'$ E., 25.14 chs. dist., previously described.

From the cor. of secs. 21, 22, 27, and 28.

N. $0^{\circ}04'$ W., bet. secs. 21 and 22.

Over rolling land of Sage Flat.

33.00

Dirt road, bears E and W; asc. over gentle S slope.

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS	
40.15	<p>The $\frac{1}{4}$ sec. cor. of secs. 21 and 22, monumented with a sandstone, 8 x 8 x 6 ins., firmly set and plainly mkd. $\frac{1}{4}$ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 S R 4 W</p> <p>$\frac{1}{4}$</p> <p>S 21 S 22</p> <p>1975</p> </div> <p>Bury the mkd. stone alongside the iron post, and set steel fence post alongside the corner.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. $1^{\circ}32'$ W., beginning new measurement.</p> <p>Asc. over S slope.</p>
12.50	<p>Enter juniper and pinon.</p>
31.195	<p>Intersect line 4-1, Mineral Survey No. 4670 A, Independent No. 3 claim.</p> <p>From this intersection, cor. No. 1, bears S. $84^{\circ}10'$ E., 6.145 chs. dist., marked with a mound of stone, from which the original bearing trees</p> <p style="padding-left: 40px;">A pinon, 14 ins. diam., bears N. 23° E., 0.215 chs. dist., mkd. 1-4670 A BT.</p> <p style="padding-left: 40px;">A pinon, 16 ins. diam., bears S. $16^{\circ}15'$ E., 0.545 chs. dist., mkd. 1-4670 A BT.</p> <p>From this same intersection, cor. No. 4, identical with cor. No. 1, Independent lode of the same survey, bears N. $84^{\circ}10'$ W., 2.895 chs. dist., marked with a mound of stone, from which the original bearing trees</p> <p style="padding-left: 40px;">A pinon, 12 ins. diam., bears S. 16° W., 0.465 chs. dist., mkd. 4-1-4670 A BT.</p> <p style="padding-left: 40px;">A pinon, 16 ins. diam., bears N. $73^{\circ}30'$ W., 0.36 chs. dist., mkd. 4-1-4670 A BT.</p>
40.55	<p>The cor. of secs. 15, 16, 21, and 22, monumented with a quartzite stone, 14 x 9 x 6 ins., firmly set and plainly mkd. 3 notches on S and E edges, from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A pine stump, 10 ins. diam., bears N. $84^{\circ}30'$ E., 31 lks. dist., mkd. with faint scribe marks.</p> <p style="padding-left: 40px;">A cedar, 12 ins. diam., bears S. $11^{\circ}30'$ E., 106 lks. dist., mkd. with visible scribe marks.</p> <p>At the corner point</p>

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T 26 S R 4 W
|
S 16 | S 15
S 21 | S 22
|
1975

Bury the mkd. stone alongside the iron post.

(Restoring the 1896 survey by J. T. Breckon)

From the cor. of secs. 14, 15, 22, and 23.

N. 89°50' W., bet. secs. 15 and 22.

Over rocky mountain land; asc. over SE slope.

7.00 Low rocky spur, slopes S; desc. over SW slope.

40.84 Point for the ¼ sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 S R 4 W

¼ S 15
 S 22

1975

Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.

49.00 Wash, 30 lks. wide, 5 ft. deep, drains S; asc. gentle E slope, across scattering patches of reseeded area.

55.40 Dirt road, bears N. 20° W. and S. 20° E.

72.50 Dirt road, bears NW and NE.

74.28 Intersect line 1-2, Mineral Survey No. 4670 A, Independent No. 3 claim.

From this intersection, cor. No. 1, bears S. 5°57' W., 10.01 chs. dist., marked with a mound of stone, from which the original bearing trees

A pinon, 14 ins. diam., bears N. 23° E., 21.5 lks. dist., mkd. 1-4670 A BT.

A pinon, 16 ins. diam., bears S. 16°15' E., 54.5 lks. dist., mkd. 1-4670 A BT.

661

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS	
81.68	<p>From this same intersection, cor. No. 2, identical with cor. No. 1, Western lode of the same survey, bears N. 5°57' E., 12.695 chs. dist., marked with a post in a mound of stone, mkd. with faint scribe marks.</p> <p>The cor. of secs. 15, 16, 21, and 22.</p>
14.00	<p>N. 0°04' W., bet. secs. 15 and 16.</p> <p>Over mountain land, through juniper and pinon; asc. over SE slope.</p> <p>Dirt road, bears NW and SE.</p>
29.00	<p>Top of ascent on low divide, bears NE and SW; desc. over NE slope.</p>
41.29	<p>The ¼ sec. cor. of secs. 15 and 16, monumented with a trachyte stone, 14 x 8 x 6 ins., firmly set and plainly mkd. ¼ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 S R 4 W</p> <p>¼</p> <p> </p> <p>S 16 S 15</p> <p> </p> <p>1965</p> </div> <p>Place the mkd. stone alongside the iron post in a mound of stone.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°01' W., beginning new measurement.</p> <p>Desc. over N slope.</p>
17.94	<p>Intersect line 2-3, Mineral Survey No. 4670 A, North Extension claim; also fence cor., fences bear N and N. 84°23' W., enter reseeded area.</p> <p>From this intersection, cor No. 2, identical with cor. No. 3, Deer Trail lode of the same survey, bears S. 84°23' E., 4.385 chs. dist., marked with a mound of stone.</p> <p>From this same intersection, cor. No. 3, identical with cor. No. 2, Alice Extension lode of the same survey, bears N. 84°23' W., 4.69 chs. dist., marked with a squared post in a mound of stone, weathered scribe marks on post.</p>
30.00	<p>Small draw, drains SE; asc. over SE slope.</p>
40.14	<p>The cor. of secs. 9, 10, 15, and 16, monumented with a lava stone, 14 x 6 x 6 ins., firmly set and plainly mkd. 4 notches on S and 3 notches on E edges.</p> <p>At the corner point</p>

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS	
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 S R 4 W S 9 S 10 S 16 S 15 1975</p> <p>Bury the mkd. stone alongside the iron post.</p> <p>Corner is located in fence cor., fences bear NW, S, E, and W.</p>
	<p>From the cor. of secs. 10, 11, 14, and 15.</p> <p>N. 88°05' W., bet. secs. 10 and 15.</p> <p>Over mountain land, through juniper and pinon; asc. over NE slope.</p>
10.00	Spur, slopes N; desc. over NW slope.
33.00	Draw, drains N. 20° E.; asc. over E slope.
41.09	<p>The ¼ sec. cor. of secs. 10 and 15, monumented with a trachyte stone, 12 x 6 x 4 ins., firmly set and plainly mkd. ¼ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 26 S R 4 W ¼ S 10 S 15 1975</p> <p>Bury the mkd. stone alongside the iron post, and raise mound of stone, 2 ft. base, 2 ft. high, N of corner.</p> <p>Cor. is located 125 lks. S of E and W fence line.</p>
	<p>N. 89°47' W., beginning new measurement.</p>
2.00	Spur, slopes N. 15° E.; desc. over NW slope.
10.00	Draw, drains N. 20° E.; asc. over SE slope. Also washed out trail road in draw, bears NE and SW.
32.00	Slope changes; asc. along S slope, enter reseeded area.
39.58	The cor. of secs. 9, 10, 15, and 16.
	<p>N. 1°41' W., bet. secs. 9 and 10.</p>

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS	
	Over mountain land, across reseeded area; asc. gentle S slope.
30.00	Head of draw, drains N. 80° E.; asc. SE slope, leave reseeded area, enter timber.
39.50	Ridge, bears NE and SW; desc. over NW slope.
40.46	The $\frac{1}{4}$ sec. cor. of secs. 9 and 10, monumented with a trachyte stone, 18 x 10 x 10 ins., firmly set and plainly mkd. $\frac{1}{4}$ on W face, from which the original bearing trees
	A cedar, 12 ins. diam., bears S. 70° E., 8 lks. dist., mkd. $\frac{1}{4}$ S BT.
	A pinon, 10 ins. diam., bears N. 84° W., 36 lks. dist., mkd. $\frac{1}{4}$ S BT.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base to top of brass cap, mkd.
	<pre> T 26 S R 4 W ¼ S 9 S 10 1975 </pre>
	Place the mkd. stone alongside the iron post in a mound of stone.
	N. 0°16' E., beginning new measurement.
	Desc. over NW slope.
19.50	Spur, slopes sharply N. 40° W.; desc. over NE slope.
31.10	Draw, drains N. 38° W.; desc. along broken W slope, in canyon.
38.33	Point selected for the witness cor. of secs. 3, 4, 9, and 10.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<pre> W C T 26 S R 4 W ↑ S 4 S 3 S 9 S 10 1975 </pre>
	From which
	A pinon, 15 ins. diam., bears S. 23°50' E., 25 lks. dist., mkd. S10 BT.

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS	
38.84	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor. True point for the cor. of secs. 3, 4, 9, and 10, at proportionate distance, falls in gully, which drains W and cannot be perpetuated; there is no remaining evidence of the original corner.</p>
	<p style="text-align: center;">(Restoring the 1878 survey by A. D. Ferron)</p>
	<p>From the cor. of secs. 2, 3, 10, and 11. N. 88°48' W., bet. secs. 3 and 10.</p>
	<p>Over mountain land, covered with shadscale and sagebrush; asc. gentle NE slope.</p>
0.10	<p>Fence, bears N and S.</p>
5.00	<p>Trail road, bears N and S.</p>
12.50	<p>Draw, drains NE.</p>
28.00	<p>Base of steep ascent, bears NW and SE; asc. NE slope, enter mountains.</p>
40.71	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 10, at proportionate dist., based on the irregular boundary method; there is no remaining evidence of the original corner position.</p>
	<p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of brass cap, mkd.</p>
	<p style="text-align: center;">T 26 S R 4 W</p>
	<p style="text-align: center;">$\frac{1}{4}$ $\frac{S\ 3}{S\ 10}$</p>
	<p style="text-align: center;">1975</p>
	<p>from which</p>
	<p style="text-align: center;">A cedar, 12 ins. diam., bears N. 20° E., 67 lks. dist., mkd. $\frac{1}{4}$ S3 BT.</p>
	<p>Cor. is located 10 lks. S of wash, which drains E.</p>
	<p style="text-align: center;">(Restoring the 1896 survey by J. T. Breckon)</p>
	<p>N. 88°44' W., beginning new measurement.</p>
	<p>Asc. over NE slope, through juniper and pinon.</p>
20.00	<p>High ridge, bears NE and SW; desc. over steep W slope.</p>
40.71	<p>True point for the cor. of secs. 3, 4, 9, and 10.</p>

665

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS	
	N. 0°29' E., bet. secs. 3 and 4.
	Over broken mountain land, through scattering juniper and pinon; desc. down canyon bottom, which drains N.
9.00	Leave canyon bottom, which bears NE; asc. along ledgy E slope.
10.00	Draw, drains NE.
16.00	Spur, slopes E; desc. over NE slope.
19.20	Small draw, drains E; asc. SE slope.
26.50	Spur, slopes N. 80° E.; desc. along E slope.
38.84	The ¼ sec. cor. of secs. 3 and 4, monumented with a sandstone, 18 x 14 x 4 ins., firmly set and plainly mkd. ¼ on W face.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.
	<p style="text-align: center;">T 26 S R 4 W ¼ S 4 S 3 1975</p>
	Place the mkd. stone alongside the iron post in a mound of stone.
	N. 0°27' E., beginning new measurement.
	Desc. along E slope.
11.00	Draw, drains E; asc. SE slope.
16.00	Spur, slopes E; thence along broken E slope.
31.50	Small draw, drains N. 80° E.; asc. over SE slope.
38.88	The closing cor. of secs. 3 and 4, on the S. bdy. of T. 25 S., R. 4 W., (Fifth Standard Parallel South) monumented with a limestone, 16 x 16 x 10 ins., firmly set and plainly mkd. 3 notches on E and W edges, CC on S face.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS

T 25 S R 4 W
S 34

S 4 | S 3
C | C
T 26 S R 4 W
1975

Place the mkd. stone alongside the iron post in a mound of stone.

Cor. located on top of spur, which slopes E.

From this cor., the standard cor. of secs. 33 and 34, T. 25 S., R. 4 W., bears S. 89°31' W., 8.455 chs. dist., monumented with an iron post, 2½ ins. diam., in a mound of stone, with brass cap mkd. as described in the 1970-71 resurvey of the Fifth Standard Parallel South, through R. 4 W.

From this same cor., the standard ¼ sec. cor. of sec. 34, T. 25 S., R. 4 W., bears N. 89°31' E., 31.635 chs. dist., monumented with an iron post, 2½ ins. diam., in a mound of stone, with brass cap mkd. as described in the 1970-71 resurvey of the Fifth Standard Parallel South, through R. 4 W.

Point for the N ¼ sec. cor. of sec. 3, T. 26 S., R. 4 W., on the Fifth Standard Parallel South, and midpoint bet. the closing cor. of secs. 2 and 3, and the closing cor. of secs. 3 and 4, T. 26 S., R. 4 W.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T 25 S R 4 W

¼ S 3
T 26 S R 4 W
1975

Raise a mound of stone, 3 ft. base, 2 ft. high, S of cor.

From this cor., the standard cor. of secs. 34 and 35, T. 25 S., R. 4 W., bears N. 89°31' E., 31.59 chs. dist., monumented with an iron post, 2½ ins. diam., extending 8 ins. above ground, with brass cap mkd. as described in the 1970-71 resurvey of the Fifth Standard Parallel South, through R. 4 W.

From this same cor., the standard ¼ sec. cor. of sec. 34, T. 25 S., R. 4 W., bears S. 89°31' W., 8.56 chs. dist., monumented with an iron post, 2½ ins. diam., in a mound of stone, with brass cap mkd. as described in the 1970-71 resurvey of the Fifth Standard Parallel South, through R. 4 W.

(Restoring the 1896 survey and the 1898 correction survey by J. T. Breckon)

667

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS	
	<p>From the cor. of secs. 21, 22, 27, and 28. S. 89°28' W., bet. secs. 21 and 28. Over mountain land, covered with scattering juniper and pinon; asc. along N slope.</p>
23.00	Slope changes; asc. over NE slope.
38.77	<p>Intersect line 4-1, Mineral Survey No. 5263, Old Dispute claim. From this intersection, cor. No. 4, bears S. 10°54' E., 0.375 chs. dist., marked with a post, in a mound of stone, from which an original bearing tree A pine, 10 ins. diam, bears S. 11°10' E., 0.436 chs. dist., mkd. 4-5263 BT. From this same intersection. cor. No. 1, identical with cor. No. 1, Bradburn lode of the same survey, bears N. 10°54' W., 8.725 chs. dist., marked with a squared pine post, in a mound of stone, mkd. with weathered scribe marks, from which an original bearing tree A pine, 10 ins. diam., bears S. 72°15' E., 0.665 chs. dist., mkd. 1-1-5263 BT.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 21 and 28, determined at record course and distance from the original ¼ sec. cor. of secs. 21 and 28, established in 1896 and corrected in 1898. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd. T 26 S R 4 W ¼ $\frac{S 21}{S 28}$ 1975 From this cor., the original ¼ sec. cor. of secs. 21 and 28, bears S. 72° W., 53 lks. dist., marked with a mound of stone, no legible marks, from which an original bearing tree A cedar, 10 ins. diam., bears N. 27° W., 11 lks. dist., mkd. ¼ SBT. (Record, N. 30°40' W., 10 lks. dist.)</p>
	<p>S. 89°29' W., beginning new measurement. Asc. over NE slope.</p>
3.50	Top of flat ridge, bears NE and S; desc. along N slope.
13.00	Ravine, drains N; asc. over NE slope.
40.71	<p>The cor. of secs. 20, 21, 28, and 29, monumented with a sandstone, 18 x 10 x 10 ins., firmly set and plainly mkd. 4 notches on E and 1 notch on S edge, from which the original bearing trees</p>

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS

A pine, 10 ins. diam., bears N. 10° E., 31 lks. dist., faint scribe marks visible. (Record, N. 7° 45' E., 35 lks. dist.)

A dead pine, 10 ins. diam., bears S. 20° E., 55 lks. dist., faint scribe marks visible. (Record, S. 20° 40' E., 62 lks. dist.)

A pine, 12 ins. diam., bears S. 60° W., 36 lks. dist., faint scribe marks visible. (Record, S. 60° 55' W., 14.1 lks. dist.)

A cedar, 12 ins. diam., bears N. 43° W., 66 lks. dist., faint scribe marks visible. (Record, N. 49° 15' W., 63 lks. dist.)

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.

T 26 S R 4 W	
S 20	S 21
S 29	S 28
1975	

Bury the mkd. stone alongside the iron post.

(Restoring the 1896 survey by J. T. Breckon)

S. 0°10' E., bet. secs. 28 and 29.

Over broken and ledgy mountain land, through scattering juniper and pinon; along ridge top, which bears N and S irregularly.

4.395 Intersect line 4-5, Mineral Survey No. 5263, Granite No. 1 claim.

From this intersection, cor. No. 5, identical with cor. No. 4, Granite No. 2 lode of the same survey, bears N. 83°48' E., 1.52 chs. dist., marked with a mound of stone, from which an original bearing tree

A cedar, 10 ins. diam., bears N. 41°30' W., 12 lks. dist., mkd. 5-4-5263 BT.

From this same intersection, cor. No. 4, identical with cor. No. 3, New Discovery lode of the same survey, bears S. 83°48' W., 16.00 chs. dist., marked with a scattering mound of stone.

5.50 Peak on top of ridge; desc. along ledgy W slope.

23.00 Spur, slopes SW; desc. over SE slope.

27.50 Draw, drains S. 60° W.; asc. along ledgy W slope.

39.86 The ¼ sec. cor. of secs. 28 and 29, monumented with a trachyte stone, 18 x 12 x 8 ins., firmly set and plainly mkd. ¼ on W face.

At the corner point

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

$$\begin{array}{c} \text{T 26 S R 4 W} \\ | \\ \text{S 29} \quad | \quad \text{S 28} \\ | \\ 1975 \end{array}$$

Bury the mkd. stone alongside the iron post.

S. 1°51' E., beginning new measurement.

Asc. along ledgy W slope.

- 13.00 Spur, slopes W; desc. over broken and ledgy SW slope.
33.10 Draw, drains W; asc. over NW slope.
37.00 Spur, slopes sharply W; desc. along ledgy W slope.
44.42 Intersect the N. bdy. of T. 27 S., R. 3 W.

Point for the closing cor. of secs. 28 and 29, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.

$$\begin{array}{c} \text{C C} \\ \text{T 26 S R 4 W} \\ | \\ \text{S 29} \quad | \quad \text{S 28} \\ \hline \text{S 6} \\ \text{T 27 S R 3 W} \\ 1975 \end{array}$$

From this cor., the cor. of Tps. 27 S., Rs. 3 and 4 W., bears S. 89°39' W., 13.15 chs. dist., previously described.

From this same cor., the N ¼ sec. cor. of sec. 6, T. 27 S., R. 3 W., bears N. 89°39' E., 24.53 chs. dist., previously described.

Point for the S ¼ sec. cor. of sec. 28, T. 26 S., R. 4 W., on the N. bdy. of T. 27 S., R. 3 W., and midpoint bet. the closing cor. of secs. 27 and 28, and the closing cor. of secs. 28 and 29, T. 26 S., R. 4 W.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{T 26 S R 4 W} \\ \\ \frac{1}{4} \quad \text{S 28} \\ \hline \text{T 27 S R 3 W} \\ 1975 \end{array}$$

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS	
	<p>Raise mound of stone, 3 ft. base, 2 ft. high, N of cor.</p> <p>From this cor., the N $\frac{1}{4}$ sec. cor. of sec. 6, T. 27 S., R. 3 W., bears S. $89^{\circ}39'$ W., 15.035 chs. dist., previously described.</p> <p>From this same cor., the cor. of secs. 5 and 6, T. 27 S., R. 3 W., bears N. $89^{\circ}39'$ E., 24.585 chs. dist., previously described.</p>
	<p>From the cor. of secs. 20, 21, 28, and 29.</p> <p>N. $1^{\circ}10'$ W., bet. secs. 20 and 21.</p> <p>Over mountain land, covered with scattering juniper and pinon; desc. over steep and ledgy NE slope.</p>
12.595	<p>Intersect line 3-4, Mineral Survey No. 5263, Bismuth No. 1 claim.</p> <p>From this intersection, cor. No. 3, bears N. $76^{\circ}51'$ E., 9.99 chs. dist., marked with a pine post, in a mound of stone, mkd. with weathered scribe marks, from which the original bearing trees</p> <p style="padding-left: 40px;">A pine, 30 ins. diam., bears N. $65^{\circ}30'$ W., 51 lks. dist., mkd. 3-2-5263 BT.</p> <p style="padding-left: 40px;">A pine, 18 ins. diam., bears N. $5^{\circ}30'$ W., 38 lks. dist., mkd. 3-2-5263 BT.</p> <p>From this same intersection, cor. No. 4, bears S. $76^{\circ}51'$ W., 4.545 chs. dist., marked with a squared cedar post, in a mound of stone, mkd. with weathered scribe marks.</p>
26.50	<p>Canyon, drains W, also trail road in canyon bottom; asc. steep and ledgy SW slope.</p>
40.03	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 21, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 S R 4 W</p> <p style="margin-left: 100px;">$\frac{1}{4}$</p> <p style="margin-left: 80px;">S 20 S 21</p> <p style="margin-left: 100px;">1975</p> </div>
45.00	<p>Spur, slopes W; desc. over NW slope.</p>
56.60	<p>Draw, drains SW; asc. over S slope.</p>
71.00	<p>Ridge, bears NE and SW; desc. over NW slope.</p>
80.06	<p>The cor. of secs. 16, 17, 20, and 21, monumented with a sandstone, 18 x 10 x 8 ins., firmly set and plainly mkd. 4 notches on E and 2 notches on S edges.</p>

671

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a collar of stone, with brass cap mkd.

T 26 S R 4 W
S 17 S 16
S 20 S 21
1975

Bury the mkd. stone alongside the iron post.

From the cor. of secs. 15, 16, 21, and 22.

N. 89°39' W., bet. secs. 16 and 21.

17.00 Ridge, bears NW and S; desc. over SW slope.

37.77 Intersect line 2-3, Mineral Survey No. 4670A, Pittsburg No. 3 claim.

From this intersection, cor. No. 2, identical with Cor. No. 4, Pittsburg No. 1 lode of the same survey, bears N. 7°26' E., 20.97 chs. dist., marked with a squared pine post, in a mound of stone, mkd. with weathered scribe marks, from which the original bearing trees

A pine, 15 ins. diam., bears S. 86° 30' E., 31 lks. dist., mkd. 2-4-4670A.

A pine, 10 ins. diam., bears S. 59° W., 35 lks. dist., mkd. 2-4-4670A.

From this same intersection, cor. No. 3, bears S. 7°26' W., 1.81 chs. dist., marked with a scattering mound of stone.

39.00 Draw, drains S; asc. over E slope.

40.16 The ¼ sec. cor. of secs. 16 and 21, monumented with a trachyte stone, 18 x 14 x 6 ins., in a mound of stone, plainly mkd. ¼ on N face, from which the original bearing trees

A pine, 12 ins. diam., bears N. 67° E., 28 lks. dist., (record, 25 lks.) mkd. ¼ S BT.

A pine stump, 36 ins. diam., bears S. 57°30' W., 115 lks. dist., (record 118 lks.) mkd. ¼ S BT.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of brass cap, mkd.

T 26 S R 4 W
¼ S 16
¼ S 21
1975

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS	
	Place the mkd. stone alongside the iron post in a mound of stone.
	Cor. is located 5 lks. S of fence cor., fences bear W and N. 15° E.
	S. 87°46' W., beginning new measurement.
	Asc. E slope.
25.00	Ridge, bears N and S; desc. over NW slope.
41.02	The cor. of secs. 16, 17, 20, and 21.
	N. 0°13' W., bet. secs. 16 and 17.
	Over mountainous land, covered with juniper and pinon; desc. over NW slope.
5.40	Draw, drains W; asc. over ledgy SW slope.
14.50	Spur, slopes N. 80° W.; desc. over N slope.
19.00	Ravine, drains W; asc. over SW slope.
32.00	Spur, slopes W; thence along ledgy W slope.
41.67	Point for the ¼ sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., on solid rock, over an X, in a mound of stone, 4 ft. base to top of brass cap, mkd.
	T 26 S R 4 W ¼ S 17 S 16 1975
	Continue along W slope.
46.50	Spur, slopes W; continue along W slope.
61.00	Spur, slopes W; desc. over NW slope.
67.00	Draw, drains W; asc. over SW slope.
76.00	Spur, slopes S. 75° W.; thence along ledgy W slope.
83.34	The cor. of secs. 8, 9, 16, and 17, monumented with a trachyte stone, 16 x 12 x 4 ins., firmly set and plainly mkd. 4 notches on E edge, from which the original bearing trees
	A pine, 12 ins. diam., bears S. 89° E., 8 lks. dist., mkd. T26S R4W S16 BT.
	A pine, 12 ins. diam., bears S. 66° W., 37 lks. dist., mkd. T26S R4W S17 BT.

673

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS																			
	<p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T 26</td><td>S R</td><td>4 W</td></tr> <tr><td></td><td> </td><td></td></tr> <tr><td>S 8</td><td> </td><td>S 9</td></tr> <tr><td>S 17</td><td> </td><td>S 16</td></tr> <tr><td></td><td> </td><td></td></tr> <tr><td></td><td>1975</td><td></td></tr> </table> </div> <p>Bury the mkd. stone alongside the iron post.</p>	T 26	S R	4 W				S 8		S 9	S 17		S 16					1975	
T 26	S R	4 W																	
S 8		S 9																	
S 17		S 16																	
	1975																		
41.87	<p>From the cor. of secs. 9, 10, 15, and 16.</p> <p>S. 88°18' W., bet. secs. 9 and 16.</p> <p>Over rolling mountain top, across reseeded area, along E and W fence line.</p> <p>The ¼ sec. cor. of secs. 9 and 16, monumented with a trachyte stone, 12 x 10 x 10 ins., firmly set and plainly mkd. ¼ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of brass cap, mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T 26</td><td>S R</td><td>4 W</td></tr> <tr><td></td><td> </td><td></td></tr> <tr><td>¼</td><td> </td><td>S 9</td></tr> <tr><td></td><td> </td><td>S 16</td></tr> <tr><td></td><td> </td><td></td></tr> <tr><td></td><td>1975</td><td></td></tr> </table> </div> <p>Place the mkd. stone alongside the iron post in a mound of stone.</p> <p>Cor. is located 11 lks. N of E and W fence line.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 87°22' W., beginning new measurement.</p> <p>Asc. over NE slope, on mountain top.</p>	T 26	S R	4 W				¼		S 9			S 16					1975	
T 26	S R	4 W																	
¼		S 9																	
		S 16																	
	1975																		
33.00	Ridge, bears N. 30° E. and S. 30° W.; desc. over W slope.																		
39.54	The cor. of secs. 8, 9, 16, and 17.																		
3.50	<p>N. 0°51' E., bet. secs. 8 and 9.</p> <p>Over broken and ledgy mountain land, covered with juniper and pinon; along steep W slope.</p> <p>Spur, slopes W; desc. over NW slope.</p>																		
16.50	Draw, drains W; asc. over SW slope.																		

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS	
22.50	Spur, slopes W; desc. over NW slope.
30.00	Draw, drains W; asc. over SW slope.
38.00	Ridge, bears E and W; desc. along W slope.
38.98	Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.
	<p style="text-align: center;">T 26 S R 4 W $\frac{1}{4}$ S 8 S 9 1975</p>
	from which
	A cedar, 8 ins. diam., bears N. 15° E., 29 lks. dist., mkd. $\frac{1}{4}$ S9 BT.
	A cedar, 6 ins. diam., bears S. 70° W., 8 lks. dist., mkd. $\frac{1}{4}$ S8 BT.
	Desc. along steep W slope.
77.40	Deep draw, drains NE; asc. over SE slope.
77.96	The cor. of secs. 4, 5, 8, and 9, monumented with a granite stone, 14 x 10 x 8 ins., firmly set and plainly mkd. 5 notches on S and 4 notches on E edges, from which the original bearing tree
	A cedar, 15 ins. diam., bears N. 60° E., 12 lks. dist., (record, 20 lks.) mkd. T26S R4W S9 BT
	At the corner point
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.
	<p style="text-align: center;">T 26 S R 4 W S 5 S 4 S 8 S 9 1975</p>
	Place the mkd. stone alongside the iron post in a mound of stone.
	From the true point for the cor. of secs. 3, 4, 9, and 10. S. $88^\circ 18'$ W., bet. secs. 4 and 9.
	Over broken mountain land, covered with scattering pinon, and juniper; desc. over W slope, in canyon bottom.

675

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS	
0.50	Wash in canyon bottom, drains N irregularly; asc. over steep SE slope.
14.00	Ridge, bears N and S; thence over ridge top.
22.20	Top of ascent, bears S and NW; desc. over SW slope.
37.00	Draw, drains SW; asc. along S slope.
40.71	The $\frac{1}{4}$ sec. cor. of secs. 4 and 9, monumented with a sandstone, 20 x 12 x 5 ins., firmly set and plainly mkd. $\frac{1}{4}$ on N face.
	from which
	A cedar, 12 ins. diam., bears south, 34 lks. dist., mkd. $\frac{1}{4}$ SBT. (Not recorded)
	A cedar, 30 ins. diam., bears N. 45° W., 20 lks. dist., mkd. $\frac{1}{4}$ SBT. (Not recorded)
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base to top of brass cap, mkd.
	T 26 S R 4 W
	$\frac{1}{4}$ $\frac{S\ 4}{S\ 9}$
	1975
	Place the mkd. stone alongside the iron post in a mound of stone.
	N. 89°17' W., beginning new measurement.
	Asc. along broken S slope.
12.00	Spur, slopes S. 30° W.; desc. over NW slope.
26.50	Draw, drains N. 55° W.; asc. along N slope.
32.00	Rocky spur, slopes N; desc. over NW slope.
38.20	Draw, drains N. 40° E.; asc. over steep E slope.
38.60	The cor. of secs. 4, 5, 8, and 9.
	N. 0°29' E., bet. secs. 4 and 5.
	Over mountain land, covered with scattering juniper and pinon; asc. along broken E slope.
18.00	High spur, slopes N. 40° E.; desc. over NW slope.
24.70	Ravine, drains N. 30° E.; desc. along E slope.
35.00	Spur, slopes N. 10° E.; desc. over N slope.

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS

40.18 The $\frac{1}{4}$ sec. cor. of secs. 4 and 5, determined by a large crumbling boulder, marks have weathered away. This is the only boulder in the vicinity and fits the calls of the original survey.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in crumbling boulder, in a mound of stone, 4 ft. base to top of brass cap, mkd.

T 26 S R 4 W
 $\frac{1}{4}$
 S 5 | S 4
 1975

N. $1^{\circ}28'$ W., beginning new measurement.

Desc. over NW slope, on E side of Marysvale Canyon.

28.50 Base of descent, bears NW and SE; asc. over steep SW slope.

37.61 The closing cor. of secs. 4 and 5, on the S. bdy. of T. 25 S., R. 4 W., (Fifth Standard Parallel South) monumented with a sandstone, 18 x 14 x 8 ins., firmly set and plainly mkd. 2 notches on W and 4 notches on E edges, CC on S face.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.

T 25 S R 4 W
 S 33
 S 5 | S 4
 C | C
 T 26 S R 4 W
 1975

Bury the mkd. stone alongside the iron post.

From this cor., the standard cor. of secs. 32 and 33, T. 25 S., R. 4 W., bears S. $89^{\circ}21'$ W., 8.485 chs. dist., monumented with an iron post, in a mound of stone, with brass cap mkd. as described in the 1970-71 resurvey of the Fifth Standard Parallel South, through R. 4 W.

From this same cor., the standard $\frac{1}{4}$ sec. cor. of sec. 33, T. 25 S., R. 4 W., bears N. $89^{\circ}21'$ E., 31.925 chs. dist., monumented with an iron post, in a mound of stone, with brass cap mkd. as described in the 1970-71 resurvey of the Fifth Standard Parallel South, through R. 4 W.

Point for the N $\frac{1}{4}$ sec. cor. of sec. 4, T. 26 S., R. 4 W., on the Fifth Standard Parallel South, and midpoint bet. the closing cor. of secs. 3 and 4, and the closing cor. of secs. 4 and 5, T. 26 S., R. 4 W.

677

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.

T 25 S R 4 W

¼ S 4
T 26 S R 4 W
1975

From this cor., the standard cor. of secs. 33 and 34, T. 25 S., R. 4 W., bears N. 89°21' E., 31.94 chs. dist., monumented with an iron post, 2½ ins. diam., in a mound of stone, with brass cap mkd. as described in the 1970-71 resurvey of the Fifth Standard Parallel South, through R. 4 W.

From this same cor., the standard ¼ sec. cor. of sec. 33, T. 25 S., R. 4 W., bears S. 89°21' W., 8.47 chs. dist., monumented with an iron post, 2½ ins. diam., with brass cap mkd. as described in the 1970-71 resurvey of the Fifth Standard Parallel South, through R. 4 W.

From the cor. of secs. 20, 21, 28, and 29.

S. 89°49' W., bet. secs. 20 and 29.

Over mountainous land, covered with scattering juniper and pinon; desc. over broken and ledgy W slope.

32.80 Base of steep descent, bears N and S irregularly; desc. over W slope, in Marysvale Canyon.

34.33 Intersect line 4-1, Copper Mint Claim, Mineral Survey No. 5263.

From this intersection, cor. No. 4, bears N. 11°11' W., 3.75 chs. dist., marked with a pine post, in a mound of stone, scribed 4-5263.

From this same intersection, cor. No. 1, identical with cor. No. 1, New Discovery lode same survey, bears S. 11°11' E., 4.99 chs. dist., determined by a mound of stone.

39.29 The ¼ sec. cor. of secs. 20 and 29, determined by a mound of stone, and an iron post, 2 ins. diam., set in a concrete base, 1 ft. square, with brass cap mkd.

Sevier County
20
29
Land Survey

This monument has long been used by local property owners and is recognized as the original cor. position.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS	
	T 26 S R 4 W $\frac{1}{4} \begin{array}{c} \text{S } 20 \\ \text{S } 29 \end{array}$ 1975
	Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor., and place the county marker in mound.
	—————
	S. 89°52' W., beginning new measurement.
	Desc. over gentle W slope in Marysvale Canyon.
14.80	Denver and Rio Grande Railroad, not in use, bears N. 2° W. and curves SE.
17.00	Sevier River, 50 lks. wide, 3 ft. deep, flows N. 8° W.; asc. gentle E slope, through summer cabins and grounds of Rock Candy Resort.
21.40	U.S. Highway No. 89, bears N and SE on curve.
24.50	Leave Rock Candy Resort.
27.00	Base of steep ascent, bears N and SW; asc. steep SE slope.
39.58	Point for the cor. of secs. 19, 20, 29, and 30, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of brass cap, mkd.
	T 26 S R 4 W $\begin{array}{c c} \text{S } 19 & \text{S } 20 \\ \text{S } 30 & \text{S } 29 \end{array}$ 1975
	from which
	A lone cedar, 12 ins. diam., bears S. 41° E., 73 lks. dist., mkd. T26S R4W S29 BT.
	(Restoring the 1896 survey by J. T. Breckon and the 1932 survey by J. C. Scoles, Mineral Surveyor)
	—————
	S. 0°32' W., bet. secs. 29 and 30.
	Over mountainous land, covered with scattering juniper and pinon; desc. over steep SE slope.
7.20	Wash in canyon, drains E; thence over canyon bottom.

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS	
8.50	Small spur in canyon, slopes E.
10.00	Wash, drains S. 80° E.; asc. steep and broken N slope.
20.93	Intersect line 2-3, American Flag No. 3 claim, Mineral Survey No. 6678 A.
	From this intersection, cor. No. 2, bears S. 89°59' W., 2.65 chs. dist., marked with a squared cedar post, 3 ft. above ground, scribed A F 3-2-6678 A.
	From this same intersection, true point for cor. No. 3, bears N. 89°59' E., 20.01 chs. dist., from which its witness cor. bears S. 89°59' W., 3.126 chs. dist., marked with a pine post, in a mound of stone, scribed WC A F 3-3-6678 A.
37.30	Ridge, bears N. 65° E. and S. 65° W.; desc. over SE slope.
39.88	The ¼ sec. cor. of secs. 29 and 30, monumented with a sandstone, 20 x 10 x 10 ins., firmly set and plainly mkd. ¼, also scattering mound of stone.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	<p style="text-align: center;">T 26 S R 4 W</p> <p style="text-align: center;"> </p> <p style="text-align: center;"> ¼</p> <p style="text-align: center;">S 30 S 29</p> <p style="text-align: center;"> </p> <p style="text-align: center;"> 1975</p>
	Bury the mkd. stone alongside the iron post, and raise a mound of stone, 2 ft. base, 2 ft. high, W of cor.
	S. 3°29' E., beginning new measurement.
	Desc. over broken and ledgy SE slope.
17.70	Spur, slopes SE; desc. over broken and ledgy S slope.
20.46	Intersect line 3-4, Iron Side No. 2 claim, Mineral Survey No. 6678 A.
	From this intersection, cor. No. 4, bears S. 89°58' W., 0.77 chs. dist., marked with an iron post, 2 ins. diam., extending 2 ft. above ground, stamped IS, 2-4-6678A.
	From this same intersection, cor. No. 3, bears N. 89°58' E., 19.56 chs. dist., marked with a squared cedar post, set in a mound of stone, with scribe marks IS 1-6678A legible.
31.10	Base of steep descent, bears E and SW; desc. over S slope, in Deer Creek Canyon.
36.20	Gravel road, bears N. 75° E. and curves SW in canyon bottom.

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS	
39.60	Deer Creek, 10 lks. wide, 6 ins. deep, flows N. 72° E.; asc. over steep NW slope.
43.53	The original closing cor. of secs. 29 and 30, determined with a scattering mound of stone, no marks could be identified. This position was verified by ties to cor. No. 1, Pittsburg Millsite, Mineral Survey No. 6678B.
44.71	<p>Intersect the N. bdy. of T. 27 S., R. 4 W.</p> <p>Point for the closing cor. of secs. 29 and 30.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.</p> <div style="text-align: center;"> <p>CC</p> <p>T 26 S R 4 W</p> <p> </p> <p>S 30 S 29</p> <p>S 1</p> <p>T 27 S R 4 W</p> <p>1975</p> </div> <p>From this cor., the true point for the cor. of secs. 1 and 2, T. 27 S., R. 4 W., bears S. 89°39' W., 14.355 chs. dist., previously described.</p> <p>From this same cor., the N ¼ sec. cor. of sec. 1, T. 27 S., R. 4 W., bears N. 89°39' E., 25.265 chs. dist., previously described.</p>
	<p>Point for the S ¼ sec. cor. of sec. 29, T. 26 S., R. 4 W., on the N. bdy. of T. 27 S., R. 4 W., and midpoint bet. the closing cor. of secs. 28 and 29, and the closing cor. of secs. 29 and 30, T. 26 S., R. 4 W., falls on inaccessible ledges and cannot be monumented.</p> <p>From this point, the N ¼ sec. cor. of sec. 1, T. 27 S., R. 4 W., bears S. 89°39' W., 13.75 chs. dist., previously described.</p> <p>From this same point, the cor. of Tps. 27 S., Rs. 3 and 4 W., bears N. 89°39' E., 25.87 chs. dist., previously described.</p> <p>From this same cor. point, the point selected for the witness S ¼ sec. cor. of sec. 29, bears N. 89°39' E., 0.66 chs. dist.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.</p> <div style="text-align: center;"> <p>WC</p> <p>T 26 S R 4 W</p> <p>¼ ← S 29</p> <p>T 27 S R 4 W</p> <p>1975</p> </div> <p>Witness cor. located 40 lks. E of base of ledges.</p>

681

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS	
	<p>Point for the S $\frac{1}{4}$ sec. cor. of sec. 30, T. 26 S., R. 4 W., on the N. bdy. of T. 27 S., R. 4 W., and at proportionate distance bet. the closing cor. of secs. 29 and 30, T. 26 S., R. 4 W., and the closing cor. of T. 26 S., Rs. 4 and $4\frac{1}{2}$ W.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.</p> <p style="text-align: center;">T 26 S R 4 W</p> <p style="text-align: center;">$\frac{1}{4}$ <u>S 30</u></p> <p style="text-align: center;">T 26 S R 4 W 1975</p> <p>From this cor., the N $\frac{1}{4}$ sec. cor. of sec. 2, T. 27 S., R. 4 W., bears S. $89^{\circ}39'$ W., 13.60 chs. dist., previously described.</p> <p>From this same cor., the true point for the cor. of secs. 1 and 2, T. 27 S., R. 4 W., bears N. $89^{\circ}39'$ E., 26.02 chs. dist., previously described.</p>
	<p style="text-align: center;">(Restoring the 1896 survey by J. T. Breckon)</p> <hr style="width: 20%; margin: auto;"/> <p>From the cor. of secs. 19, 20, 29, and 30.</p> <p>S. $88^{\circ}12'$ W., bet. secs. 19 and 30.</p> <p>Over mountainous land, covered with scattering juniper and pinon; asc. along steep and ledgy S slope.</p> <p>7.50 Spur, slopes SE; continue along S slope.</p> <p>13.80 Ravine, drains S. 20° E.; asc. along W slope.</p> <p>26.00 Draw, drains S. 40° E.; asc. over steep SE slope.</p> <p>39.60 The $\frac{1}{4}$ sec. cor. of secs. 19 and 30, monumented with a limestone, 14 x 10 x 10 ins., firmly set and plainly mkd. $\frac{1}{4}$ on N face, from which the original bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears N. 82° E., 48 lks. dist., mkd. $\frac{1}{4}$ S19 BT.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a mound of stone, 4 ft. base to top of brass cap, mkd.</p> <p style="text-align: center;">T 26 S R 4 W</p> <p style="text-align: center;">$\frac{1}{4}$ <u>S 19</u> S 30</p> <p style="text-align: center;">1975</p> <p>Place the mkd. stone alongside the iron post in a mound of stone.</p>

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS							
	<p>S. 88°46' W., beginning new measurement.</p> <p>Asc. over SE slope.</p>						
2.90	Ridge, bears N. 48° E. and S. 48° W.; desc. over NW slope.						
9.28	<p>Intersect line 4-1, B. W. claim, Mineral Survey No. 4913.</p> <p>From this intersection, cor. No. 1, identical with Cor. No. 1, Blue Eagle Mining claim No. 3 of the same survey, bears N. 4°58' E., 1.37 chs. dist., marked with a squared pine post, in a mound of stone, scribed 1-14913, from which the original bearing tree</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears N. 80° W., 14 lks. dist., scribed BT 1-1-4913.</p> <p>From the same intersection, cor. No. 4, bears S. 4°58' W., 21.49 chs. dist., marked with a squared pine post, in a mound of stone, scribed 4-4913.</p>						
14.20	Draw, drains NE; asc. along N slope.						
26.82	<p>Intersect line 2-3, Blue Eagle claim, Mineral Survey No. 4913.</p> <p>From this intersection, cor. No. 2, identical with Cor. No. 2, Blue Eagle Mining claim No. 2 of the same survey, bears N. 12°57' E., 12.52 chs. dist., marked with a squared pine post, in a mound of stone, scribed 2-2-4913, from which the original bearing trees</p> <p style="padding-left: 40px;">A cedar, 10 ins. diam., bears N. 36° E., 82 lks. dist., scribed 2-2-4913.</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears S. 51°30' E., 41 lks. dist., scribed 2-2-4913.</p> <p>From the same intersection, cor. No. 3, bears S. 12°57' W., 10.38 chs. dist., marked with a squared pine post, in a mound of stone, scribed 3-4913, from which the original bearing tree</p> <p style="padding-left: 40px;">A cedar, 12 ins. diam., bears S. 10° E., 3 lks. dist., scribed 3-4913.</p>						
35.00	Ravine, drains NE; asc. over E slope.						
39.79	<p>Intersect the E. bdy. of T. 26 S., R. 4½ W.</p> <p>Point for the closing cor. of secs. 19 and 30, T. 26 S., R. 4 W. at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of brass cap, mkd.</p> <div style="text-align: center; margin-top: 20px;"> <p>T 26 S R 4½ W R 4 W</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 25</td> <td style="border-right: 1px solid black; padding: 0 5px;">S 19</td> <td style="padding: 0 5px;">C</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="border-right: 1px solid black; padding: 0 5px;">S 30</td> <td style="padding: 0 5px;">C</td> </tr> </table> <p>1975</p> </div>	S 25	S 19	C		S 30	C
S 25	S 19	C					
	S 30	C					

683

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS

from which

A pinon, 8 ins. diam., bears N. 47° E., 21 lks. dist., mkd. S19 BT.

From this closing cor., the cor. of secs. 25 and 36, T. 26 S., R. $4\frac{1}{2}$ W., bears S. $0^{\circ}56'$ E., 2.30 chs. dist., previously described.

From this same closing cor., the E $\frac{1}{4}$ sec. cor. of sec. 25, T. 26 S., R. $4\frac{1}{2}$ W., bears N. $0^{\circ}56'$ W., 37.74 chs. dist., previously described.

Point for the W $\frac{1}{4}$ sec. cor. of sec. 30, T. 26 S., R. 4 W., on the E. bdy. of T. 26 S., R. $4\frac{1}{2}$ W., and at proportionate distance bet. the original closing cor. of Tps. 26 S., Rs. 4 and $4\frac{1}{2}$ W., and the closing cor. of secs. 19 and 30, T. 26 S., R. 4 W.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T 26 S
R $4\frac{1}{2}$ W R 4 W
|
| $\frac{1}{4}$
|
| S 30
|
1975

from which

A pine, 5 ins. diam., bears S. 34° E., 115 lks. dist., mkd. $\frac{1}{4}$ BT.

Cor. is located in brush clearing, on gentle N slope.

From this cor., the E $\frac{1}{4}$ sec. cor. of sec. 36, T. 26 S., R. $4\frac{1}{2}$ W., bears S. $0^{\circ}56'$ E., 2.30 chs. dist., previously described.

From this same cor., the cor. of secs. 25 and 36, T. 26 S., R. $4\frac{1}{2}$ W., bears N. $0^{\circ}56'$ W., 37.74 chs. dist., previously described.

From the cor. of secs. 19, 20, 29, and 30.

N. $1^{\circ}12'$ W., bet. secs. 19 and 20.

Over broken mountainous land, through scattering timber; asc. over SE slope.

8.00 Spur, slopes E; desc. over ledgy NE slope.

17.00 Draw, drains N. 85° E.; asc. over SE slope.

21.80 Spur, slopes N. 85° E.; desc. along broken E slope.

34.40 Spur, slopes E; desc. over NE slope.

38.00 Base of descent, bears E and W; thence over bottom of small draw.

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS	
39.00	Trail road, bears E and W, about 3.00 chs. to trash dump.
39.98	The $\frac{1}{4}$ sec. cor. of secs. 19 and 20, monumented with a sandstone, 14 x 8 x 6 ins., firmly set and plainly mkd. $\frac{1}{4}$ on N face, also scattering mound of stone.
	At the corner point
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<pre> T 26 S R 4 W S 19 S 20 1975 </pre>
	Bury the mkd. stone alongside the iron post, and raise a mound of stone, 3 ft. base, 2 ft. high, W of corner.
	N. $1^{\circ}19'$ W., beginning new measurement.
	Over bottom of small draw.
4.00	Base of steep ascent, bears E and W; asc. over steep W slope.
10.40	High spur, slopes E; desc. along broken E slope.
34.00	Base of mountains, bears NW and S; desc. along E slope in bottom of Marysvale Canyon.
39.22	Point for the cor. of secs. 17, 18, 19 and 20, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<pre> T 26 S R 4 W S 18 S 17 S 19 S 20 1975 </pre>
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	from which
	A power pole No. 7, bears N. $6^{\circ}50'$ W., 138 lks. dist., scribed with an "X", 4 ins. above ground on pole.
	From the cor. of secs. 16, 17, 20, and 21.
	S. $89^{\circ}13'$ W., bet. secs. 17 and 20.
	Over broken mountain land, through scattering juniper and pinon; along broken N slope.
7.00	Ravine, drains N; asc. over NE slope.
13.90	Ridge, bears NW and SE; desc. over SW slope.

685

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS	
22.80	Draw, drains S; asc. over SE slope.
28.10	Ledgy narrow spur, slopes sharply S; desc. over broken and ledgy W slope.
39.50	Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.
	T 26 S R 4 W
	$\frac{1}{4}$ $\frac{S 17}{S 20}$
	1975
	from which
	A pinon, 20 ins. diam., bears N. 65° E., 13 lks. dist., mkd. $\frac{1}{4}$ S17 BT.
	Cor. is located in bottom of draw, which drains S; asc. over SE slope.
45.70	Spur, slopes S; desc. over ledgy and broken SW slope.
69.70	Base of steep descent, bears N. 20° W. and S. 20° E. irregularly; thence across Marysvale Canyon.
70.60	Denver and Rio Grande railroad, abandoned, bears N. 20° W. and S. 20° E., up canyon.
71.80	Sevier River, 1.20 chs. wide, 2 ft. deep, drains N; asc. gentle E slope in canyon bottom.
77.30	U.S. Highway No. 89, bears N and curves SE.
79.00	The cor. of secs. 17, 18, 19, and 20.
	S. $88^\circ 57'$ W., bet. secs. 18 and 19.
	Over broken and ledgy mountain land, covered with scattering juniper and pinon; asc. over E slope in Marysvale Canyon.
1.70	Base of steep and broken ascent, bears N and SE; asc. over steep E slope.
20.10	High spur, slopes NE; asc. along broken N slope.
29.50	High spur, slopes N. 15° E.; desc. steep NW slope.
39.56	Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS

T 26 S R 4 W

$$\frac{1}{4} \begin{array}{l} \text{S 18} \\ \text{S 19} \end{array}$$

1975

from which

A juniper, 5 ins. diam., bears S. $41^{\circ}30'$ W.,
54 lks. dist., mkd. $\frac{1}{4}$ S19 BT.

A pinon, 6 ins. diam., bears N. $66^{\circ}45'$ W.,
31 lks. dist., mkd. $\frac{1}{4}$ S18 BT.

Desc. broken NW slope.

43.80 Canyon, drains N. 61° E.; asc. along irregular S slope.69.60 Draw, drains S. 49° E.; asc. over steep NE slope.78.93 Intersect the E. bdy. of T. 26 S., R. $4\frac{1}{2}$ W.

Point for the closing cor. of secs. 18 and 19, T. 26 S.,
R. 4 W., at proportionate distance; there is no remaining
evidence of the original corner.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins.
in the ground to bedrock, in a mound of stone, 4 ft. base
to top of brass cap, mkd.

$$\begin{array}{c} \text{T 26 S} \\ \text{R } 4\frac{1}{2} \text{ W R 4 W} \\ | \\ \text{S 24 } \left| \begin{array}{l} \text{S 18 C} \\ \text{S 19 C} \end{array} \right. \end{array}$$

1975

From this cor., the cor. of secs. 24 and 25, T. 26 S.,
R. $4\frac{1}{2}$ W., bears S. $0^{\circ}56'$ E., 2.20 chs. dist., previously
described.

From this same closing cor., the E $\frac{1}{4}$ sec. cor. of sec. 24,
T. 26 S., R. $4\frac{1}{2}$ W., bears N. $0^{\circ}56'$ W., 37.84 chs. dist.,
previously described.

Point for the W $\frac{1}{4}$ sec. cor. of sec. 19, T. 26 S., R. 4 W.,
on the E. bdy. of T. 26 S., R. $4\frac{1}{2}$ W., and at midpoint bet.
the closing cor. of secs. 19 and 30, and the closing cor.
of secs. 18 and 19, T. 26 S., R. 4 W.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins.
in the ground to bedrock, in a mound of stone, 4 ft. base
to top of brass cap, mkd.

$$\begin{array}{c} \text{T 26 S} \\ \text{R } 4\frac{1}{2} \text{ W R 4 W} \\ | \\ \frac{1}{4} \\ | \\ \text{S 19} \\ | \\ 1975 \end{array}$$

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS	
	<p>From this cor., the E $\frac{1}{4}$ sec. cor. of sec. 25, T. 26 S., R. 4$\frac{1}{2}$ W., bears S. 0°56' E., 2.25 chs. dist., previously described.</p> <p>From the same cor., the cor. of secs. 24 and 25, T. 26 S., R. 4$\frac{1}{2}$ W., bears N. 0°56' W., 37.79 chs. dist., previously described.</p>
	<p>From the cor. of secs. 17, 18, 19, and 20.</p> <p>N. 0°27' W., bet. secs. 17 and 18.</p> <p>Over broken mountainous land, along E slope on W side of Marysvale Canyon.</p>
3.50	U.S. Highway No. 89, bears N. 4° W. and curves SE; thence along highway.
8.30	Leave highway.
12.50	Left bank of Sevier River, bears N irregularly; thence across bend in river.
15.00	Leave river; asc. along gentle E slope in canyon.
21.20	U.S. Highway No. 89, bears N. 16°30' E. and curves SW.
39.21	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 26 S R 4 W</p> <p>$\frac{1}{4}$</p> <p>S 18 S 17</p> <p>1975</p> </div>
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <p>Cor. is located at base of hill, which bears E and W; asc. steep S slope.</p>
45.20	Spur, slopes E; thence along broken and impassable ledges of W wall of Marysvale Canyon.
78.42	<p>Point for the cor. of secs. 7, 8, 17, and 18, at proportionate distance, falls on inaccessible ledges and cannot be monumented; there is no remaining evidence of the original corner. From which</p> <p>Point selected for witness cor. bears N. 66° 50' E., 1.10 chs. dist.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of brass cap, mkd.</p>

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS

W C
T 26 S R 4 W

S 7	S 8
S 18	S 17



1975

Cor. is located at base of ledges, in small cove facing E.

From the cor. of secs. 8, 9, 16, and 17.

S. 83°42' W., bet. secs. 8 and 17.

Over broken mountainous land, through scattering juniper and pinon; desc. along N slope in draw, which drains W.

10.00 Wash in draw, drains S. 80° W.; desc. along S slope.

27.00 Draw, drains NW; asc. over NE slope.

33.20 Spur, slopes N. 15° W.; desc. over NW slope.

39.59 The ¼ sec. cor. of secs. 8 and 17, determined with a boulder in place, 6 x 4 x 3 ft. above ground, with rocks piled on top, no marks could be identified. This is the only boulder in area and fits the description of the original survey.

At the corner point

Chisel a cross (X) on solid rock

from which

An iron post, 30 ins. long, 2½ ins. diam., set 15 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, for a reference monument, bears S. 87°40' W., 5 lks. dist., with brass cap mkd. RM T26S R4W ¼ S8 S17 1975 and an arrow pointing to the cor.

S. 87°40' W., beginning new measurement.

Desc. SW slope.

7.00 Small draw, drains S. 20° W.; asc. SE slope.

10.40 Spur, slopes S; desc. steep and broken W slope, into Marysvale Canyon.

26.20 Base of steep descent, bears N and S irregularly; desc. over W slope, in Marysvale Canyon.


28.10 Denver and Rio Grande railroad, abandoned, bears S and curves NE.

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS	
30.80	Sevier River, 1.00 ch. wide, 2 ft. deep, flows N; asc. E slope in Marysvale Canyon.
32.70	U.S. Highway No. 89, bears N. 7°10' E. and S. 7°10' W.
34.40	Base of steep ascent, bears N and S irregularly; asc. over steep and ledgy E slope of the W wall of Marysvale Canyon.
39.99	True point for the cor. of secs. 7, 8, 17, and 18.
N. 89°40' W., bet. secs. 7 and 18.	
Over broken and ledgy mountain land, through juniper and pinon; asc. over ledgy E slope.	
14.00	Spur, slopes N. 50° E.; asc. along broken N slope.
35.00	Draw, drains NE; asc. over NE slope.
38.90	Spur, slopes NE; over NW slope.
39.99	Point for the ¼ sec. cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.	
T 26 S R 4 W	
$\frac{1}{4} \begin{array}{l} S 7 \\ S 18 \end{array}$	
1975	
from which	
A pinon, 5 ins. diam., bears South, 8 lks. dist., mkd. ¼ S18 BT.	
A pinon, 6 ins. diam., bears N. 65° W., 30 lks. dist., mkd. ¼ S7 BT.	
Raise a mound of stone, 2 ft. base, 1½ ft. high, W of cor. Desc. NW slope.	
43.50	Draw, drains NE; asc. steep NE slope, through oak brush.
76.00	Small spur, slopes N; asc. along N slope in draw.
79.54	Intersect the E. bdy. of T. 26 S., R. 4½ W.
Point for the closing cor. of secs. 7 and 18, T. 26 S., R. 4 W., at proportionate distance; there is no remaining evidence of the original corner.	
Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.	

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS




1975

From this cor., the cor. of secs. 13 and 24, T. 26 S., R. 4½ W., bears S. 0°48' E., 2.30 chs. dist., previously described.

From this same closing cor., the E ¼ sec. cor. of sec. 13, T. 26 S., R. 4½ W., bears N. 0°48' W., 37.70 chs. dist., previously described.

Point for the W ¼ sec. cor. of sec. 18, T. 26 S., R. 4 W., on the E. bdy. of T. 26 S., R. 4½ W., and at midpoint bet. the closing cor. of secs. 18 and 19, and the closing cor. of secs. 7 and 18, T. 26 S., R. 4 W.

Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of brass cap, mkd.



From this cor., the E ¼ sec. cor. of sec. 24, T. 26 S., R. 4½ W., bears S. 0°56' E., 2.25 chs. dist., previously described.

From the same cor., the cor. of secs. 13 and 24, T. 26 S., R. 4½ W., bears N. 0°56' W., 37.79 chs. dist., previously described.

From the true point for the cor. of secs. 7, 8, 17, and 18.

N. 1°49' E., bet. secs. 7 and 8.

Over broken mountain land, covered with scattering pinon and juniper, along ledgy and impassable E slope, on W wall of Marysvale Canyon.

- 13.00 Draw, drains E.
- 20.00 Point, projects E; continue along ledgy E slope.
- 31.70 Spur, slopes E; desc. over NE slope.
- 39.23 Point for the ¼ sec. cor. of secs. 7 and 8, at proportionate distance; there is no remaining evidence of the original corner.

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 S R 4 W
|
 $\frac{1}{4}$
|
S 7 | S 8
|
1975

from which

A pinon, 8 ins. diam., bears N. 20° E., 50 lks. dist., mkd. $\frac{1}{4}$ S8 BT.

A pinon, 6 ins. diam., bears N. 65° W., 42 lks. dist., mkd. $\frac{1}{4}$ S7 BT.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

Cor. is located at base of mountain, thence along E slope on W side of Marysvale Canyon.

- 40.10 Wash, 10 lks. wide, 2 ft. deep, drains E.
- 59.50 U.S. Highway No. 89, bears N. $12^{\circ}30'$ W. and S. $12^{\circ}30'$ E.
- 65.00 Sevier River, 1.00 ch. wide, 2 ft. deep, flows N. 9° W., asc. along gentle W slope in Marysvale Canyon.
- 74.10 Denver and Rio Grande railroad, abandoned, bears N. 16° W. and S. 16° E.
- 78.46 The cor. of secs. 5, 6, 7, and 8, determined by a mound of stone with pipe in center, with survey lath and poles around pipe. This is the best evidence of the position of the original corner, and is being used by local land owners as the cor. The original marked stone, a sandstone, 20 x 8 x 8 ins., was found about 90 lks. W of this position in the rip-rap of an old abandoned dugout.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 S R 4 W
|
S 6 | S 5
S 7 | S 8
|
1975

Bury the mkd. stone alongside the iron post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

From the cor. of secs. 4, 5, 8, and 9.

S. $86^{\circ}04'$ W., bet. secs. 5 and 8.

Over broken mountain land, covered with scattering pinon and juniper; asc. broken E slope.

- 23.00 Ridge, bears N. 48° W. and S. 20° E.; desc. over steep SW slope.

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS	
28.90	Spur, slopes SW; desc. W slope.
39.07	Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.
	T 26 S R 4 W
	$\frac{1}{4}$ $\frac{S 5}{S 8}$
	1975
	Desc. over NW slope.
51.10	Ravine, drains N. 40° W.; asc. along N slope.
58.60	Spur, slopes N. 10° W.; desc. broken and irregular W slope, into Marysvale Canyon.
77.50	Base of steep descent, bears N. 20° W. and S. 20° E.; thence over bottom of canyon.
78.14	The cor. of secs. 5, 6, 7, and 8.
	N. $88^{\circ}41'$ W., bet. secs. 6 and 7.
	Over bottom of Marysvale Canyon, through cottonwood trees.
4.60	Denver and Rio Grande railroad, abandoned, bears N. 30° W. and S. 30° E.
6.50	Sevier River, 1.00 ch. wide, 2 ft. deep, flows N. 30° W.
8.20	U.S. Highway No. 89, bears N. $4^{\circ}30'$ W. and S. $4^{\circ}30'$ E.
35.00	Ridge, bears N and S; desc. over SW slope.
39.80	Draw, drains S; asc. over E slope.
41.84	Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., on solid rock, over an X, in a mound of stone, 4 ft. base to top of brass cap, mkd.
	T 26 S R 4 W
	$\frac{1}{4}$ $\frac{S 6}{S 7}$
	1975
	from which
	A pinon, 6 ins. diam., bears S. 12° W., 33 lks. dist., mkd. $\frac{1}{4}$ S7 BT.
	Asc. over steep E slope.


Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS

- 52.10 Rocky knoll on spur, which slopes SE; asc. over SE slope.
- 77.70 Rocky ridge, bears NE and SW; desc. NW slope.
- 83.05 Intersect the E. bdy. of T. 26 S., R. 4½ W.

Point for the closing cor. of secs. 6 and 7, T. 26 S., R. 4 W., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.




From this cor., the cor. of secs. 12 and 13, T. 26 S., R. 4½ W., bears S. 0°48' E., 2.24 chs. dist., previously described.

From this same closing cor., the E ¼ sec. cor. of sec. 12, T. 26 S., R. 4½ W., bears N. 0°48' W., 37.76 chs. dist., previously described.

Point for the W ¼ sec. cor. of sec. 7, T. 26 S., R. 4 W., on the E. bdy. of T. 26 S., R. 4½ W., and at midpoint bet. the closing cor. of secs. 7 and 18, and the closing cor. of secs. 6 and 7, T. 26 S., R. 4 W.

Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.



From this cor., the E ¼ sec. cor. of sec. 13, T. 26 S., R. 4½ W., bears S. 0°48' E., 2.27 chs. dist., previously described.

From the same cor., the cor. of secs. 12 and 13, T. 26 S., R. 4½ W., bears N. 0°48' W., 37.73 chs. dist., previously described.

Point for the W ¼ sec. cor. of sec. 6, T. 26 S., R. 4 W., on the E. bdy. of T. 26 S., R. 4½ W., and at proportionate distance bet. the closing cor. of secs. 6 and 7, T. 26 S., R. 4 W., and the closing cor. of Tps. 26 S., Rs. 4 and 4½ W., on the N. bdy. of the Tp.

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 S
R 4½ W R 4 W
|
¼
|
S 6
|
1975

From this cor., the E ¼ sec. cor. of sec. 12, T. 26 S., R. 4½ W., bears S. 0°48' E., 2.24 chs. dist., previously described.

From the same cor., the closing cor. of T. 26 S., Rs. 4 and 4½ W., on the N. bdy. of the Tp., bears N. 0°48' W., 39.66 chs. dist., previously described.

From the cor. of secs. 5, 6, 7, and 8.

N. 0°06' E., bet. secs. 5 and 6.

Over broken mountain land, through scattering juniper and pinon; asc. over SW slope, in Marysvale Canyon.

- 11.90 Point, projects W; desc. over steep N slope.
- 19.00 Enter bottom land of Marysvale Canyon.
- 22.00 Denver and Rio Grande railroad, bears N. 76° E. and S. 76° W., railroad now abandoned.
- 24.50 Sevier River, 80 lks. wide, 2 ft. deep, flows N. 72° E.; asc. over gentle S slope in Marysvale Canyon.
- 32.10 U.S. Highway No. 89, bears N. 65° E. and S. 65° W.; asc. over steep SE slope, leave canyon bottom.
- 39.26 The ¼ sec. cor. of secs. 5 and 6, monumented with a granite stone, 12 x 6 x 6 ins., firmly set and plainly mkd. ¼ on W face, also scattering mound of stone.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 S R 4 W
|
¼
|
S 6 | S 5
|
1975

Bury the mkd. stone alongside the iron post, and raise a mound of stone, 2 ft. base, 2 ft. high, W of corner.

N. 5°04' W., beginning new measurement.

Asc. over SE slope.

- 12.50 Spur, slopes E; desc. over NE slope.

695

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS

- 17.00 Ravine, drains E; asc. along E slope.
- 31.80 Ravine, drains S. 75° E.; asc. over SE slope.
- 40.20 Spur, slopes S. 80° E.; asc. along broken and ledgy E slope.
- 43.21 Intersect the S. bdy. of T. 25 S., R. 4 W. (Fifth Standard Parallel South).

Point for the closing cor. of secs. 5 and 6, T. 26 S., R. 4 W., at proportionate distance; there is no remaining evidence of the original corner. This point falls on small ledge and cannot be monumented.

From this point the standard cor. of secs. 31 and 32, T. 25 S., R. 4 W., bears S. $89^{\circ}21'$ W., 8.385 chs. dist., Monumented with an iron post, $2\frac{1}{2}$ ins. diam., in a mound of stone, with brass cap mkd. as described in the 1970-71 resurvey of the Fifth Standard Parallel South, through R. 4 W.

From this same point, the standard $\frac{1}{4}$ sec. cor. of sec. 32, T. 25 S., R. 4 W., bears N. $89^{\circ}21'$ E., 32.025 chs. dist., monumented with an iron post, $2\frac{1}{2}$ ins. diam., in a mound of stone, with brass cap mkd. as described in the 1970-71 resurvey of the Fifth Standard Parallel South, through R. 4 W.

From this same point, the point selected for the witness closing cor. of secs. 5 and 6, bears S. $89^{\circ}21'$ W., 0.08 chs. dist.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.

```

      W C
      T 25 S R 4 W
      S 32
      ---
      S 6 | S 5 >
      C | C
      T 26 S R 4 W
      1975
  
```

from which

An X, 6 ins. high, on large boulder, bears
N. 30° W., 15 lks. dist.

Point for the N $\frac{1}{4}$ sec. cor. of sec. 5, T. 26 S., R. 4 W., on the S. bdy. of T. 25 S., R. 4 W., (Fifth Standard Parallel South) and midpoint bet. the closing cor. of secs. 4 and 5, and the closing cor. of secs. 5 and 6, T. 26 S., R. 4 W.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS

T 25 S R 4 W

 $\frac{1}{4}$ S 5T 26 S R 4 W
1975

From this cor., the standard $\frac{1}{4}$ sec. cor. of sec. 32, T. 25 S., R. 4 W., bears S. $89^{\circ}21'$ W., 8.435 chs. dist., monumented with an iron post, $2\frac{1}{2}$ ins. diam., in a mound of stone, with brass cap mkd. as described in the 1970-71 resurvey of the Fifth Standard Parallel South, through R. 4 W.

From this same corner, the standard cor. of secs. 32 and 33, T. 25 S., R. 4 W., bears N. $89^{\circ}21'$ E., 31.975 chs. dist., monumented by an iron post, $2\frac{1}{2}$ ins. diam., in a mound of stone, with brass cap mkd. as described in the 1970-71 resurvey of the Fifth Standard Parallel South, through R. 4 W.

Point for the N $\frac{1}{4}$ sec. cor. of sec. 6, T. 26 S., R. 4 W., on the S. bdy. of T. 25 S., R. 4 W., (Fifth Standard Parallel South) and at proportionate distance bet. the closing cor. of secs. 5 and 6, T. 26 S., R. 4 W., and the closing cor. of Tps. 26 S., Rs. 4 and $4\frac{1}{2}$ W.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., on solid rock, over a X, in a mound of stone, 4 ft. base to top of brass cap, mkd.

T 25 S R 4 W

 $\frac{1}{4}$ S 6T 26 S R 4 W
1975

Cor. is located on steep W slope, about 4.00 chs. E of ravine, which drains N.

From this cor., the standard $\frac{1}{4}$ sec. cor. of sec. 31, T. 25 S., R. 4 W., bears S. $89^{\circ}37'$ W., 8.385 chs. dist., monumented by an iron post, $2\frac{1}{2}$ ins. diam., in a mound of stone, with brass cap mkd. as described in the 1970-71 resurvey of the Fifth Standard Parallel South, through R. 4 W.

From this same cor., the standard cor. of secs. 31 and 32, T. 25 S., R. 4 W., bears N. $89^{\circ}37'$ E., 32.035 chs. dist., monumented by an iron post, $2\frac{1}{2}$ ins. diam., in a mound of stone, with brass cap mkd. as described in the 1970-71 resurvey of the Fifth Standard Parallel South, through R. 4 W.

Dependent Resurvey of the Subdivisional Lines of
T. 26 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS

General Description

Township 26 South, Range 4 West, consists of broken rocky mountain land, with the lower elevations covered with sagebrush and shadscale, and the higher elevations covered with pinon, juniper and oak brush. Some of the higher benches have been reseeded to grass.

The township is divided by the Sevier River, which flows north through the west half of the township. U.S. Highway No. 89, and the Denver and Rio Grande railroad, now abandoned, parallel the river through the township. There are numerous other dirt roads within the township generally used for mining, hunting, and care of grazing land and livestock. There is numerous mining claims located in the south and west portions of the township.

The only habitations within the township are the Rock Candy Resort and Lodge and Hoover's Cafe, located along State Highway No. 89, in sec. 29.

The elevation of the township varies from about 5600 to 8000 ft. above sea level.

699

CERTIFICATE OF SURVEY

(IXWA) Craig P. Sylvester, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 20th day

of March 19 1975, (IXWA) have dependently resurveyed the north boundary of T. 27 S., R. 3 W., the east two miles of the north boundary of T. 27 S., R. 4 W., the east boundary of T. 26 S., R. 4 1/2 W., the east boundary and the subdivisional lines of T. 26 S., R. 4 W.,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), (us) and under (my) (our) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

September 21, 1978 (Date) [Signature] (Cadastral Surveyor) Supervisory

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Washington, D.C. Denver, Colorado

The foregoing field notes of the dependent resurvey of the north boundary of T. 27 S., R. 3 W., the east two miles of the north boundary of T. 27 S., R. 4 W., the east boundary of T. 26 S., R. 4 1/2 W., the east boundary and the subdivisional lines of T. 26 S., R. 4 W., Salt Lake Meridian, Utah

executed by Craig P. Sylvester, Supervisory Cadastral Surveyor having been critically examined and found correct, are hereby approved.

MAR 18 1980 (Date) [Signature] (Chief, Division of Cadastral Survey) Acting Chief, Cadastral Survey Examination and Approval Staff

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

[Signature] (Date)

