Form 9180-6
(March 1977)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

R601

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF THE EAST AND NORTH BOUNDARIES,

THE EAST 5 MILES OF THE SOUTH BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES,

AND PARTIAL SUBDIVISION OF

SECTIONS 10, 12, 14, 18, 19, 29, AND 32,

TOWNSHIP 3 NORTH, RANGE 1 EAST

Of the Salt Lake Meridian,

In the State of Utah.

EXECUTED BY

Glen B. Hatch, Supervisory Cadastral Surveyor

Frank Profaizer, Cadastral Surveyor

Daniel T. Mates, Cadastral Surveyor

Under special instructions dated August 16, 19 66, approved August 16, 1966,

_____, which provided for the surveys included under ~~U.S. Survey~~/Group Number 500-1, and assignment instructions dated July 5, 19 77.

Survey commenced July 5, 19 77

Survey completed July 28, 19 78

Form 9180-6
(March 1977)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

R601

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF THE EAST AND NORTH BOUNDARIES,

THE EAST 5 MILES OF THE SOUTH BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES,

AND PARTIAL SUBDIVISION OF

SECTIONS 10, 12, 14, 18, 19, 29, AND 32,

TOWNSHIP 3 NORTH, RANGE 1 EAST

Of the Salt Lake Meridian,

In the State of Utah.

EXECUTED BY

Glen B. Hatch, Supervisory Cadastral Surveyor

Frank Profaizer, Cadastral Surveyor

Daniel T. Mates, Cadastral Surveyor

Under special instructions dated August 16, 19 66, approved August 16, 1966,

_____, which provided for the surveys included under ~~U.S. Survey~~/Group Number 500-1, and assignment instructions dated July 5, 19 77.

Survey commenced July 5, 19 77

Survey completed July 28, 19 78

INDEX DIAGRAM

Township 3 N., Range 1 E.,

15	14	13	13	12	11	
6	5	4	27 3 26	24 2 23	19 1 18	6
7 34	8	9	25 10 24	22 11 21	17 12 17	5
18 33	33 17	16	15	20 14 19	15 13	4
19 31	32 20 31	21	22	23	24	3
30	30 29 30	28 28	27	26	25	3
31	30 32 10	28 33 9	34 9	35 8	36 7	1

Subdivision of Sec. 10 - Page 34
Subdivision of Sec. 12 - Page 38
Subdivision of Sec. 14 - Page 39
Subdivision of Sec. 18 - Page 42
Subdivision of Sec. 19 - Page 44
Subdivision of Sec. 29 - Page 46
Subdivision of Sec. 32 - Page 47

GPO 840-243

Township 3 North, Range 1 East, Salt Lake Meridian, Utah

CHAINS

The following field notes describe the dependent resurvey of the east and north boundaries, the east 5 miles of the south boundary, a portion of the subdivisional lines, and partial subdivision of sections 10, 12, 14, 18, 19, 29, and 32, Township 3 North, Range 1 East, Salt Lake Meridian, Utah.

The original survey of T. 3 N., R. 1 E., was commenced by Joseph Troskolawski in 1855. This survey was retraced and extended by C. L. Ericzon in 1875. The survey of the subdivision and exterior boundaries of the township was completed by Otto E. Salomon in 1886. The south 5½ miles of the east boundary was resurveyed by Robert Gorlinski in 1894. The cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the township was remonumented by R.C. Yundt in 1949 during the resurvey of the subdivisional lines of T. 2 N., R. 1 E. Portions of the west range of sections were resurveyed by R. C. Yundt in 1952.

The resurvey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 500-1, Utah, dated August 16, 1966.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein. The true line topographic calls were scaled from U.S.G.S. quadrangle maps and are only approximate.

The directions of lines were determined by reference to true meridians established on line by hour angle observations on Polaris. The lines were carried forward by sustained angulation being supplemented by other numerous hour angle observations on Polaris. Distances were obtained using the electronic measuring device, Hewlett, Packard 3800A District Meter.

The geographic position of the southeast corner of the township, as scaled from the U.S.G.S. quadrangle map, "BOUNTIFUL PEAK, UTAH", prepared in 1952, is as follows:

Latitude 40°56.6' N. Longitude 111°46.6' W.

The mean magnetic declination is 15°30' E.

Dependent Resurvey of the East Boundary,
T. 3 N., R. 1 E., Salt Lake Meridian, Utah

Restoring the Survey Executed by Otto E. Salomon in 1886, and the Resurvey Executed by Robert Gorlinski in 1894

Beginning at the cor. of Tps. 2 and 3 N., Rs. 1 and 2 E., monumented with a quartzite, 12 x 10 x 8 ins., firmly set 8 ins. in the ground, plainly mkd. with 6 notches on the N, S, E, and W edges and with a mound of stone W of cor., from which the original bearing trees

CHAINS

A lone pine, 20 ins. diam., bears S. 88°35' E., 144 lks. dist., with blaze grown over.

A mahogany, 8 ins. diam., bears N. 13°55' W., 142 lks. dist., with illegible scribe marks barely visible.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base to top of brass cap, mkd.

T 3 N
R 1 E | R 2 E

S 36 | S 31
S 1 | S 6

T 2 N
1977

Deposit the mkd. stone alongside the iron post.

N. 0°18' W., on the E. bdy. of sec. 36.

Asc. over S slope through thick undergrowth.

40.19 Point for the ¼ sec. cor. of sec. 36 only, at proportionate distance; there is no remaining evidence of the original cor.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 3 N
R 1 E | R 2 E

¼ S 36 |

1977

Cor. is located on small game trail, 10 lks. N of shallow, dry ravine, drains E.

80.38 The cor. of secs. 25 and 36 only, monumented with a quartzite, 14 x 11 x 6 ins., firmly set 15 ins. in the ground, plainly mkd. 5 notches on the N and 1 notch on the S edges.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd.

T 3 N
R 1 E | R 2 E

S 25 | S 31
S 36 |

1977

CHAINS	
	Deposit the mkd. stone alongside the iron post.
	N. 0°03' W., on the E. bdy. of sec. 25.
	Asc. over SW slope through dense aspen and brush.
0.45	Intersect the closing cor. of secs. 30 and 31, T. 3 N., R. 2 E., monumented with a granite, 20 x 10 x 4 ins., firmly set 16 ins. in the ground, plainly mkd. 5 grooves on N, 1 groove on S, and CC on E faces.
40.14	Point for the ¼ sec. cor. of sec. 25 only, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 3 N R 1 E R 2 E ¼ S 25 | 1977
	Cor. is located on E slope in an aspen hollow.
80.28	The cor. of secs. 24 and 25 only, monumented with a quartzite, 20 x 12 x 10 ins., firmly set 18 ins. in the ground, plainly mkd. 2 notches on the S and 4 notches on the N edges, and with a mound of stone W of cor.
	from which the original bearing tree
	A mahogany, 6 ins. diam., lies dead and fallen S. 24½° W., 245 lks. dist. (record, 238 lks.)
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 3 N R 1 E R 2 E S 24 | S 30 S 25 | 1977
	Rebuild mound of stone, 2 ft. high, 2½ ft. base, W of cor.
	Deposit the mkd. stone alongside the iron post.
	N. 0°22' W., on the E. bdy. of sec. 24.
	Along steep E slope, through dense undergrowth.
1.78	Intersect the closing cor. of secs. 19 and 30, T. 3 N., R. 2 E., monumented with a sandstone, 15 x 12 x 4 ins., (record, 20 x 13 x 5 ins.) firmly set, 12 ins. in the ground, plainly mkd. 4 grooves on the N, 2 grooves on the S, and CC on the E faces. Cor. is located in dense clump of willows.

CHAINS	
40.12	The ¼ sec. cor. of sec. 24 only, monumented with a granite, 14 x 6 x 6 ins., firmly set 6 ins. in the ground, plainly mkd. ¼ on W face, with a mound of stone, W of cor. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd. T 3 N R 1 E R 2 E ¼ S 24 | 1977 Deposit the mkd. stone alongside the iron post.
	N. 0°19' W., beginning new measurement.
20.00	Deep Creek, drains E.
40.26	The cor. of secs. 13 and 24 only, monumented with a sandstone, 20 x 14 x 5 ins., firmly set 6 ins. in the ground, plainly mkd. 3 notches on the N and S edges, and with a mound of stone W of cor. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of brass cap mkd. T 3 N R 1 E R 2 E S 13 / S 24 | S 19 1977 Deposit the mkd. stone alongside the iron post.
	N. 0°06' W., on the E. bdy. of sec. 13. Along brush covered E slope.
2.53	The closing cor. of secs. 18 and 19, T. 3 N., R. 2 E., monumented with a sandstone, 14 x 10 x 6 ins., (record, 13 x 12 x 8 ins.) firmly set 12 ins. in the ground, plainly mkd. 3 grooves on the N and S faces and CC on the E face, bears West, 3 lks. dist.
40.16	The ¼ sec. cor. of sec. 13 only, monumented with a granite, 12 x 10 x 8 ins., firmly set 4 ins. in the ground, plainly mkd. ¼ on the W face, and with a mound of stone W of cor.

☆ U.S. Government Printing Office-1978-778-206/433

Dependent Resurvey of the East Boundary,
T. 3 N., R. 1 E., Salt Lake Meridian, Utah

CHAINS	
	At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base to top of brass cap, mkd. T 3 N R 1 E R 2 E ¼ S 13 | 1977 Deposit the mkd. stone alongside the iron post.
	N. 0°20' W., beginning new measurement.
40.18	The cor. of secs. 12 and 13 only, monumented with a sandstone, 14 x 12 x 10 ins., firmly set 12 ins. in the ground, plainly mkd. 4 notches on the S and 2 notches on the N edges, and with a mound of stone S of cor. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd. T 3 N R 1 E R 2 E S 12 | S 7 S 13 | 1977 Deposit the mkd. stone alongside the iron post. Cor. is located 1 chain N of draw, drains E.
	N. 1°51' W., on the E. bdy. of sec. 12. Asc. through heavy undergrowth.
0.40	The closing cor. of secs. 7 and 18, T. 3 N., R. 2 E., monumented with a sandstone, 15 x 12 x 10 ins., firmly set 13 ins. in the ground, plainly mkd. 4 grooves on the S, 2 grooves on the N, and CC on the E faces, and with a mound of stone E of cor., bears East, 1 lk. dist.
37.50	Center Fork of Deep Creek, drains NE.
40.40	Point for the ¼ sec. cor. of sec. 12 only, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

CHAINS

T 3 N
R 1 E | R 2 E

¼ S 12 |

1977

Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor.

79.98 The closing cor. of secs. 6 and 7, T. 3 N., R. 2 E., monumented with a red sandstone, 16 x 14 x 4 ins., firmly set 14 ins. in the ground, plainly mkd. 5 grooves on the S, 1 groove on the N and CC on the E faces, bears West, 7 lks. dist.

from the closing cor., the original bearing object

A red sandstone boulder, 40 x 20 x 15 ft., bears N. 4° E., 22 lks. dist., mkd. X T3N R2E S6 BT.

80.80 The cor. of secs. 1 and 12 only, monumented with a red sandstone, 14 x 10 x 2 ins., (record, 18 x 13 x 3 ins.,) firmly set 6 ins. in the ground, plainly mkd. 5 notches on the S and 1 notch on the N edges, and in a mound of stone.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 3 N
R 1 E | R 2 E

S 1 / S 12 | S 6

1977

Deposit the mkd. stone alongside the iron post.

N. 3°01' E., on the E. bdy. of sec. 1.

Desc. through dense undergrowth.

40.17 The ¼ sec. cor. of secs. 1 and 6, monumented with a sandstone, 12 x 10 x 6 ins., firmly set 6 ins. in the ground, plainly mkd. ¼ on the W face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

T 3 N
R 1 E | R 2 E

¼

S 1 | S 6

1977

Dependent Resurvey of the East Boundary,
T. 3 N., R. 1 E., Salt Lake Meridian, Utah

CHAINS	
	Deposit the mkd. stone alongside the iron post.
	N. 0°20' E., beginning new measurement.
3.00	Dirt road, bears E and W.
8.50	North Fork of Deep Creek, drains E.
39.99	The cor. of Tps. 3 and 4 N., Rs. 1 and 2 E., monumented with a granite stone, 15 x 10 x 8 ins., firmly set 12 ins. in the ground, plainly mkd. 6 notches on the N, S, E, and W edges, and with a mound of stone NW of the cor. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd. T 4 N R 1 E R 2 E S 36 | S 31 S 1 | S 6 T 3 N 1977 Deposit the mkd. stone alongside the iron post. Cor. is located in a fence line extending E and W. From this point, a rebar of unknown origin, extends 6 ins. above ground, with 1½ in. cap mkd. with the Nos. 1, 6, 31, and 36, bears N. 71° W., 3 lks. dist.

Dependent Resurvey of the South Boundary,
T. 3 N., R. 1 E., Salt Lake Meridian, Utah

(Restoring the Survey executed by
Otto E. Salomon in 1886)

	From the cor. of Tps. 2 and 3 N., Rs. 1 and 2 E., heretofore described.
	N. 89°54' W., bet. secs. 1 and 36.
	Along steep S slope.
39.89	Point for the ¼ sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.

CHAINS	
	T 3 N R 1 E ¼ S 36 / S 1 T 2 N 1977
	Cor. is located 1 ch. N of spur, slopes E.
79.78	Point for the cor. of secs. 1, 2, 35, and 36, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd. T 3 N R 1 E S 35 | S 36 S 2 | S 1 T 2 N R 1 E 1977 Cor. is located 10 lks. N of creek in bottom of draw, drains NE.
	N. 89°54' W., bet. secs. 2 and 35. Asc. over steep E slope.
37.50	Trail road, bears NW and SE.
39.89	Point for the ¼ sec. cor. of secs. 2 and 35, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 3 N R 1 E ¼ S 35 / S 2 T 2 N R 1 E 1977
42.50	Bountiful Peak road, bears NW and SE.
79.78	Point for the cor. of secs. 2, 3, 34, and 35, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base to top of brass cap, mkd.

☆ U.S. Government Printing Office-1978-778-206/433

Dependent Resurvey of the South Boundary,
T. 3 N., R. 1 E., Salt Lake Meridian, Utah

CHAINS	
	T 3 N R 1 E S 34 | S 35 S 3 | S 2 T 2 N R 1 E 1977 Cor. is located on steep S slope, 1 ch. S of ridge top, bears NE and SW.
	N. 89°54' W., bet. secs. 3 and 34. Along steep S slope.
33.00	Barnard Creek, drains SW.
39.89	Point for the ¼ sec. cor. of secs. 3 and 34, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd. T 3 N R 1 E ¼ S 34 / S 3 T 2 N R 1 E 1977 Cor. is located on S slope at W edge of aspen grove.
79.78	Point for the cor. of secs. 3, 4, 33, and 34, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of brass cap, mkd. T 3 N R 1 E S 33 | S 34 S 4 | S 3 T 2 N R 1 E 1977
	N. 89°54' W., bet. secs. 4 and 33. Desc. over W slope, through dense oak and maple.
39.89	Point for the ¼ sec. cor. of secs. 4 and 33, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.

Dependent Resurvey of the South Boundary,
T. 3 N., R. 1 E., Salt Lake Meridian, Utah

CHAINS	
	T 3 N R 1 E ¼ S 33 / S 4 T 2 N R 1 E 1977
79.78	The cor. of secs. 4, 5, 32, and 33, monumented with a granite stone, 14 x 11 x 7 ins., mkd. 2 notches on the W and 3 faint notches still visible on the E edges, firmly set 8 ins. in the ground, and with a mound of stone alongside. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of brass cap, mkd. T 3 N R 1 E S 32 | S 33 S 5 | S 4 T 2 N 1977 from which A spruce, 24 ins. diam., bears S. 5° W., 18 lks. dist., mkd. T2N R1E S5 BT. A spruce, 12 ins. diam., bears N. 30° W., 27 lks. dist., mkd. T3N R1E S32 BT. Deposit the mkd. stone alongside the iron post.
	S. 89°48' W., bet. secs. 5 and 32. Desc. over steep NW slope.
33.50	Rick's Creek in bottom of Ford Canyon, drains SW.
39.86	Point for the ¼ sec. cor. of secs. 5 and 32, at proportionate distance, falls on steep ledge and cannot be monumented; there is no remaining evidence of the original cor. The point selected for the witness cor. to the ¼ sec. cor. of secs. 5 and 32, bears S. 80° 53' W., 8 lks. dist. Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base to top of brass cap, mkd. T 3 N R 1 E ¼ S 32 / S 5 — W C T 2 N R 1 E 1977

Dependent Resurvey of the South Boundary,
T. 3 N., R. 1 E., Salt Lake Meridian, Utah

CHAINS	
	From the true point, a rebar of unknown origin, extending 6 ins. above ground, bears N. 27° 12' E., 24 lks. dist.
59.79	Point for the W 1/16 sec. cor. of secs. 5 and 32.
	Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base to top of brass cap, mkd.
	T 3 N R 1 E W 1/16 S 32 / S 5 T 2 N R 1 E 1977
79.72	The cor. of secs. 5, 6, 31, and 32, monumented with an iron post, 2½ ins. diam., extending 4 ins. above ground, with brass cap mkd. as described in the official record of the 1949 resurvey of the subdivision of T. 2 N., R. 1 E.

Dependent Resurvey of the North Boundary,
T. 3 N., R. 1 E., Salt Lake Meridian, Utah

(Restoring the Survey Executed by
Otto E. Salomon in 1886)

	From the cor. of Tps. 3 and 4 N., Rs. 1 and 2 E., heretofore described.
	S. 89°50' W., bet. secs. 1 and 36.
	Asc. over rolling land, through heavy undergrowth.
39.60	Point for the ¼ sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
	T 4 N R 1 E ¼ S 36 / S 1 T 3 N R 1 E 1977

CHAINS	
	Cor. is located on NE slope and is 5.5 lks. S of E-W fence line.
79.20	The cor. of secs. 1, 2, 35, and 36, determined by a mound of stone at the corner of old fence lines extending S and E, this position is harmoniously related to existing original cors. and is accepted as the best available evidence of the original cor. position. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a collar of stone, with brass cap mkd. T 4 N R 1 E S 35 | S 36 S 2 | S 1 T 3 N R 1 E 1977
	S. 89°54' W., bet. secs. 2 and 35. Desc. steep W slope.
22.00	South Fork of Line Creek, drains N.
39.93	Point for the ¼ sec. cor. of secs. 2 and 35, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of brass cap, mkd. T 4 N R 1 E ¼ S 35 S 2 T 3 N R 1 E 1977
	Cor. is located 3½ chs. SE of head of hollow, drains SE.
79.86	Point for the cor. of secs. 2, 3, 34, and 35, at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, and in a mound of stone, 3½ ft. base to top of brass cap, mkd. T 4 N R 1 E S 34 | S 35 S 3 | S 2 T 3 N R 1 E 1977

Dependent Resurvey of the North Boundary,
T. 3 N., R. 1 E., Salt Lake Meridian, Utah

CHAINS	
	from which A pine, 20 ins. diam., bears N. 82° W., 27 lks. dist., mkd. S34 BT. Cor. is located on NE slope.
	S. 89°54' W., bet. secs. 3 and 34. Desc. NE slope.
10.00	Line Creek, drains NE; asc. SE slope.
39.93	Point for the ¼ sec. cor. of secs. 3 and 34, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base to top of brass cap, mkd. T 4 N R 1 E ¼ S 34 / S 3 T 3 N R 1 E 1977 Cor. is located on steep SE slope.
79.86	Point for the cor. of secs. 3, 4, 33, and 34, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 3 ins. in the ground to bedrock, in a mound of stone, 5 ft. base to top of brass cap, mkd. T 4 N R 1 E S 33 | S 34 S 4 | S 3 T 3 N R 1 E 1977 Cor. is located on SE slope.
	S. 89°54' W., bet. secs. 4 and 33. Asc. steep SE slope.
10.50	Dirt road, bears N and S.
20.50	Gravel road to Francis Peak, bears N and S.
39.93	Point for the ¼ sec. cor. of secs. 4 and 33, at proportionate distance; there is no remaining evidence of the original cor.

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd. T 4 N R 1 E ¼ S 33 / S 4 T 3 N R 1 E 1977 Cor. is located on steep N slope, 1½ chs. N of top of ridge, bears E and W. Desc. along steep NW slope.
79.86	Point for the cor. of secs. 4, 5, 32, and 33, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of brass cap, mkd. T 4 N R 1 E S 32 | S 33 S 5 | S 4 T 3 N R 1 E 1977 from which A pine, 24 ins. diam., bears S. 87° W., 80 lks. dist., mkd. T3N R1E S5 BT.
	S. 89°54' W., bet. secs. 5 and 32. Desc. steep NW slope.
39.93	Point for the ¼ sec. cor. of secs. 5 and 32, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T 4 N R 1 E ¼ S 32 / S 5 T 3 N R 1 E 1977 Cor. is located in bottom of ravine, drains NW.
79.86	Point for the cor. of secs. 5, 6, 31, and 32, at proportionate distance; there is no remaining evidence of the original cor.

Dependent Resurvey of the North Boundary,
T. 3 N., R. 1 E., Salt Lake Meridian, Utah

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T 4 N R 1 E S 31 | S 32 S 6 | S 5 T 3 N R 1 E 1977 from which A pine, 20 ins. diam., bears N. 35° E., 37 lks. dist., mkd. T4N R1E S32 BT. A pine, 20 ins. diam., bears S. 38° W., 36 lks. dist., mkd. T3N R1E S6 BT. Cor. is located on steep N slope.
	S. 89°54' W., bet. secs. 6 and 31. Desc. along steep NW slope.
39.93	Point for the ¼ sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd. T 4 N R 1 E ¼ S 31 / S 6 T 3 N R 1 E 1977 Cor. is located on gentle N slope in dense oak and maple.
80.66	The cor. of Tps. 3 and 4 N., Rs. 1 E. and 1 W., monumented with an iron post, 2½ ins. diam., protruding 6 ins. above ground, with brass cap mkd. as described in the official record of the 1952 resurvey.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 3 N., R. 1 E., Salt Lake Meridian, Utah

(Restoring the Survey Executed by Otto E. Salomon in 1886)

From the cor. of secs. 13, 14, 23, and 24, at proportionate distance; there is no remaining evidence of the original cor.

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of brass cap, mkd. T 3 N R 1 E S 14 | S 13 S 23 | S 24 1978 Cor. is located on steep, open SW slope. From this cor., the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., bears S. 0° 17' E., 240.70 chs. dist., heretofore described. From this same cor., the cor. of secs. 13 and 24, on the E. bdy. of the Tp., bears N. 89°53' E., 79.99 chs. dist., heretofore described. The control lines were fully retraced, and no evidence of intervening cors. was found. N. 0° 07' W., bet. secs. 13 and 14. Asc. SW slope.
9.50	Dirt road, bears NW and SE; desc. NE slope.
20.06	Point for the S 1/16 sec. cor. of secs. 13 and 14. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 3 N R 1 E S 1/16 S 14 | S 13 1978 Cor. is located in dense undergrowth on NE slope.
40.12	Point for the ¼ sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base to top of brass cap, mkd. T 3 N R 1 E ¼ | S 14 | S 13 | 1977 Cor. is located on gentle E slope.
58.00	Deep creek, drains SE.

U.S. Government Printing Office-1978-778-206/433

CHAINS	
80.24	Point for the cor. of secs. 11, 12, 13, and 14, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 3 N R 1 E S 11 | S 12 S 14 | S 13 1978 Cor. is located on W slope, 2 chs. E of draw, draining S.
	From the cor. of secs. 12 and 13, on the E. bdy. of the Tp., heretofore described. S. 89°48' W., bet. secs. 12 and 13. Asc. steep SE slope, through dense timber and undergrowth.
19.97	Point for the E 1/16 sec. cor. of secs. 12 and 13. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd. T 3 N R 1 E E 1/16 S 12 / S 13 1978 from which A pine, 24 ins. diam., bears N. 65° E., 25 lks. dist., mkd. BT. Cor. is located on N slope, 1 ch. S of draw, drains E.
39.94	Point for the ¼ sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of brass cap, mkd. T 3 N R 1 E ¼ S 12 / S 13 1977
79.88	The cor. of secs. 11, 12, 13, and 14.
	N. 1°42' W., bet. secs. 11 and 12.

CHAINS	
	Asc. along W slope.
40.13	Point for the ¼ sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 3 N R 1 E ¼ S 11 | S 12 1977
	Cor. is located on W slope, in aspen grove.
80.26	Point for the cor. of secs. 1, 2, 11, and 12, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd. T 3 N R 1 E S 2 | S 1 S 11 | S 12 1978
	Cor. is located on steep NW slope, 1.50 chs. E of North Fork of Deep Creek and 3.00 chs. S of North Fork of Deep Creek.
	From the cor. of secs. 1 and 12 on the E. bdy. of the Tp., heretofore described.
	S. 89°25' W., bet. secs. 1 and 12.
	Asc. over rugged NE slope.
39.82	Point for the ¼ sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a collar of stone, with brass cap mkd. T 3 N R 1 E ¼ S 1 S 12 1977
40.33	Intersect a pine, 16 ins. diam., which I mark with 2 hacks on the E and W edges for a line tree.
79.64	The cor. of secs. 1, 2, 11, and 12.

U.S. Government Printing Office-1978-778-206/433

CHAINS	
	N. 1°58' E., bet. secs. 1 and 2.
	Desc. steep N slope.
3.00	North Fork of Deep Creek, drains NE.
40.14	Point for the ¼ sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., on solid rock, in a mound of stone, 4½ ft. base to top of brass cap, mkd.
	T 3 N R 1 E ¼ S 2 | S 1 1977
	Cor. is located on steep E slope at the top of a ledge, 50 ft. high.
81.18	The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., heretofore described.
	From the cor. of secs. 13, 14, 23, and 24.
	N. 89°56' W., bet. secs. 14 and 23.
	Desc. steep SW slope through thick undergrowth.
9.50	Road to Francis Peak, bears NW and SE.
15.00	Bend in road, bears N and NW.
20.025	Point for the E 1/16 sec. cor. of secs. 14 and 23.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T 3 N R 1 E E 1/16 S 14 / S 23 1978
	from which
	A pine, 12 ins. diam., bears S. 29° E., 24 lks. dist., mkd. BT.
	Cor. is located on NW slope about 2 chs. S of road to Bountiful Peak.
25.00	Bountiful Peak road, bears NE and S.
40.05	Point for the ¼ sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original cor.

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 3 N R 1 E ¼ S 14 / S 23 1978 from which A pine, 12 ins. diam., bears S. 3° W., 56 lks. dist., mkd. BT. Cor. is located on gentle S slope.
65.00	Right Fork of Farmington Creek, drains NW.
72.00	Van Fleet Creek, drains NE.
80.10	Point for the cor. of secs. 14, 15, 22, and 23, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 3 N R 1 E S 15 | S 14 S 22 | S 23 1978 from which A pine, 10 ins. diam., bears N. 49° E., 14 lks. dist., mkd. BT. Cor. is located on top of spur, slopes NE. From this cor., the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., bears S. 0°21' E., 240.64 chs. dist., heretofore described. From this same cor., the cor. of secs. 17, 18, 19, and 20, bears S. 89°57' W., 239.57 chs. dist., hereinafter described. The control lines were fully retraced and no evidence of intervening cors. was found.
	N. 0°06' W., bet. secs. 14 and 15. Desc. N slope through thick undergrowth.
23.00	Farmington Creek, drains W.
26.00	Skyline Drive road, bears E and W.
40.10	Point for the ¼ sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 3 N., R. 1 E., Salt Lake Meridian, Utah

CHAINS	
	T 3 N R 1 E ¼ S 15 | S 14 1978
	Cor. is located in maple grove.
60.15	Point for the N 1/16 sec. cor. of secs. 14 and 15.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 3 N R 1 E N 1/16 S 15 | S 14 1978
80.20	Point for the cor. of secs. 10, 11, 14, and 15, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T 3 N R 1 E S 10 | S 11 S 15 | S 14 1977
	Cor. is located on W edge of flat bench.
	From the cor. of secs. 11, 12, 13, and 14.
	N. 89°57' W., bet. secs. 11 and 14.
	Desc. steep NW slope.
13.00	Deep Creek, drains SE.
20.02	Point for the E 1/16 sec. cor. of secs. 11 and 14.
	Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a collar of stone with brass cap mkd.
	T 3 N R 1 E E 1/16 S 11 / S 14 1978

CHAINS	
	from which
	A pine, 8 ins. diam., bears N. 50° W., 4 lks. dist., mkd. BT.
40.04	Point for the ¼ sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base to top of brass cap, mkd.
	T 3 N R 1 E
	¼ S 11 / S 14
	1978
	Cor. is located on E slope, 1 ch. E of top of main divide, bears NW and S.
57.50	Francis Peak road, bears NW and SE.
60.06	Point for the W 1/16 sec. cor. of secs. 11 and 14.
	Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of brass cap, mkd.
	T 3 N R 1 E
	W 1/16 S 11 / S 14
	1978
	Cor. is located on top of long flat spur, 2½ chs. W of road, slopes SE.
80.08	The cor. of secs. 10, 11, 14, and 15.
	N. 1°22' W., bet. secs. 10 and 11.
	Asc. slightly along W edge of flat bench.
8.00	Francis Peak road, bears NW and SE.
20.06	Point for the S 1/16 sec. cor. of secs. 10 and 11.
	Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base to top of brass cap, mkd.
	T 3 N R 1 E
	S 1/16
	S 10 | S 11
	1978

☆ U.S. Government Printing Office-1978-778-206/433

CHAINS	
	Cor. is located 50 lks. S of main divide, bearing SE and NW.
40.12	Point for the ¼ sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a collar of stone, with brass cap mkd. T 3 N R 1 E ¼ S 10 | S 11 1978 Cor. is located on open S slope, 4 chs. south of spur, slopes E.
60.18	Point for the N 1/16 sec. cor. of secs. 10 and 11. Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd. T 3 N R 1 E N 1/16 S 10 | S 11 1978 Cor. is located on steep E slope; spur slopes E, 1 ch. N of cor.
80.24	Point for the cor. of secs. 2, 3, 10, and 11, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 3 N R 1 E S 3 | S 2 S 10 | S 11 1978 Cor. is located on SE slope; spur slopes E 1.50 chs. N of cor.
	From the cor. of secs. 1, 2, 11, and 12. N. 89°58' W., bet. secs. 2 and 11.
1.50	North Fork of Deep Creek, drains NE.

CHAINS	
39.80	Point for the ¼ sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a collar of stone, with brass cap mkd. T 3 N R 1 E ¼ S 2 / S 11 1978 Cor. is located on spur projecting SE.
54.00	North Fork of Deep Creek, drains SE.
76.50	North Fork of Deep Creek, drains NE.
79.60	The cor. of secs. 2, 3, 10, and 11.
	N. 1°47' E., bet. secs. 2 and 3. Along steep E slope.
21.00	South Fork of Line Creek, drains NE.
40.12	Point for the ¼ sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base to top of brass cap, mkd. T 3 N R 1 E ¼ S 3 | S 2 1977 from which A spruce, 12 ins. diam., bears East, 32 lks. dist., mkd. ¼ S2 BT. Cor. is located S. 20° E., about 2.50 chs. dist., from center of small dry pond, 50 lks. diam.
81.00	The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., heretofore described.
	From the cor. of secs. 10, 11, 14, and 15. N. 89°58' W., bet. secs. 10 and 15. Desc. steep SW slope.

U.S. Government Printing Office-1978-778-206/433

CHAINS	
20.00	Point for the E 1/16 sec. cor. of secs. 10 and 15. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 3 N R 1 E E 1/16 S 10 / S 15 1977
40.00	Point for the ¼ sec. cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T 3 N R 1 E ¼ S 10 / S 15 1977
80.00	Point for the cor. of secs. 9, 10, 15, and 16, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 3 N R 1 E S 9 | S 10 S 16 | S 15 1977 Cor. is located on steep W slope. From this cor., the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., bears S. 0°20' E., 320.74 chs. dist., heretofore described. From this same cor., the cor. of secs. 7, 8, 17, and 18, bears S. 89°52' W., 159.34 chs. dist., hereinafter described. The control lines were fully retraced and no evidence of intervening cors. was found.
	N. 1°05' W., bet. secs. 9 and 10. Asc. along steep W slope.
17.00	Whipple Creek, drains SW.
40.10	Point for the ¼ sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the original cor.

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of brass cap, mkd. T 3 N R 1 E ¼ S 9 | S 10 1977
60.15	Point for the N 1/16 sec. cor. of secs. 9 and 10. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T 3 N R 1 E N 1/16 S 9 | S 10 1977 Cor. is located 15 lks. W of small draw, drains S.
80.20	Point for the cor. of secs. 3, 4, 9, and 10, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd. T 3 N R 1 E S 4 | S 3 S 9 | S 10 1977 From this cor., the cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., bears S. 89°59' W., 238.01 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set, protruding 6 ins. above ground, with brass cap mkd. as described in the official record of the 1952 resurvey. The control line was fully retraced and no evidence of intervening cors. was found.
	From the cor. of secs. 2, 3, 10, and 11. N. 89°59' W., bet. secs. 3 and 10. Asc. steep E slope.
19.90	Point for the E 1/16 sec. cor. of secs. 3 and 10. Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.

U.S. Government Printing Office-1978-778-206/433

CHAINS	
	T 3 N R 1 E E 1/16 S 3 / S 10 1978
	Cor. is located on NE slope in large bowl.
39.80	Point for the ¼ sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a collar of stone, with brass cap mkd.
	T 3 N R 1 E ¼ S 3 / S 10 1977
	Cor. is located on SW slope.
49.00	Francis Peak road, bears NW and SE.
59.70	Point for the W 1/16 sec. cor. of secs. 3 and 10.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 3 N R 1 E W 1/16 S 3 / S 10 1978
	Cor. is located on E slope at NW edge of aspen grove, 3½ chs. E of spur slopes S.
79.60	The cor. of secs. 3, 4, 9, and 10.
	N. 1°35' E., bet. secs. 3 and 4.
	Asc. over contoured SW slope.
27.00	Francis Peak road, bears E and W.
40.11	Point for the ¼ sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base to top of brass cap, mkd.
	T 3 N R 1 E ¼ S 4 | S 3 1977

CHAINS	
	Cor. is located on SE slope, about 1 ch. SE of trail road, bears NE and SW.
80.85	The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., heretofore described.
	From the cor. of secs. 32 and 33, on the S. bdy. of the Tp., heretofore described.
	N. 0°10' W., bet. secs. 32 and 33.
	Desc. over steep NW slope, through dense timber.
20.50	Rick's Creek in bottom of Ford Canyon, drains SW.
40.12	Point for the ¼ sec. cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 3 N R 1 E ¼ S 32 | S 33 1977
80.24	The cor. of secs. 28, 29, 32, and 33, monumented with a quartzite, 16 x 10 x 5 ins., (record, granite, 20 x 14 x 9 ins.) set 6 ins. in the ground, with 2 notches still visible on the E face, and with a mound of stone, N of cor.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of brass cap, mkd.
	T 3 N R 1 E S 29 | S 28 S 32 | S 33 1977
	Deposit the mkd. stone alongside the iron post.
	N. 0°55' W., bet. secs. 28 and 29.
	Along steep W slope, through dense undergrowth.
20.04	Point for the S 1/16 sec. cor. of secs. 28 and 29.
	Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base to top of brass cap, mkd.

☆ U.S. Government Printing Office-1978-778-206/433

CHAINS	
	T 3 N R 1 E S 1/16 S 29 | S 28 1978
30.06	Point for the N-S 1/64 sec. cor. of secs. 28 and 29, falls on vertical ledge and cannot be monumented. Point selected for the witness cor., bears N. 5°31' E., 23 lks. dist. Set an iron post, 28 ins. long, 2½ ins. diam., over a cross (X) on granite stone ledge, and in a mound of stone, 3½ ft. base to top of brass cap, mkd. W C T 3 N R 1 E N-S 1/64 S 29 ↓ S 28 1978
40.08	Point for the ¼ sec. cor. of secs. 28 and 29, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base to top of brass cap, mkd. T 3 N R 1 E ¼ S 29 | S 28 1977 Cor. is located on W slope, in dense undergrowth.
80.16	Point for the cor. of secs. 20, 21, 28, and 29, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., on top of granite boulder, 5 x 3 x 2 ft. above ground at SW base of 15" pine, in a mound of stone, 3½ ft. base to top of brass cap, mkd. T 3 N R 1 E S 20 | S 21 S 29 | S 28 1977 From this cor., the cor. of secs. 24 and 25, on the E. bdy of the Tp., bears S. 89°57' E., 320.16 chs. dist., heretofore described.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 3 N., R. 1 E., Salt Lake Meridian, Utah

CHAINS	
	From this same cor., the cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., bears N. 0°03' E., 321.15 chs. dist., heretofore described. The control lines were fully retraced and no evidence of intervening cors. was found.
	From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., heretofore described. N. 0°27' W., bet. secs. 31 and 32.
40.16	The ¼ sec. cor. of secs. 31 and 32, monumented with an iron post, 2½ ins. diam., firmly set, protruding 2 ins. above ground, with brass cap mkd. as described in the official record of the 1952 resurvey.
	N. 0°37' W., beginning new measurement.
40.14	The cor. of secs. 29, 30, 31, and 32, monumented with an iron post, 2½ ins. diam., firmly set, protruding 2 ins. above ground, with brass cap mkd. as described in the official record of the 1952 resurvey. Cor. is located at corner of fences extending N and E.
	From the cor. of secs. 28, 29, 32, and 33. S. 89°54' W., bet. secs. 29 and 32. Desc. steep NW slope.
40.13	Point for the ¼ sec. cor. of secs. 29 and 32, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a collar of stone, with brass cap mkd. T 3 N R 1 E ¼ S 29 / S 32 1978
80.26	The cor. of secs. 29, 30, 31, and 32.
	N. 0°26' W., bet. secs. 29 and 30.
20.06	Point for the S 1/16 sec. cor. of secs. 29 and 30. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

U.S. Government Printing Office-1978-778-206/433

CHAINS	
	T 3 N R 1 E S 1/16 S 30 | S 29 1977
	Cor. is located in cor. of fences, extending S and E.
40.12	The ¼ sec. cor. of secs. 29 and 30, monumented with an iron post, 2½ ins. diam., firmly set, protruding 1 in. above ground, with brass cap mkd. as described in the official record of the 1952 resurvey.
	N. 0°37' W., beginning new measurement.
40.18	The cor. of secs. 19, 20, 29, and 30, monumented with an iron post, 2½ ins. diam., firmly set, protruding 2 ins. above ground with brass cap mkd. as described in the official record of the 1952 resurvey.
	From the cor. of secs. 20, 21, 28, and 29.
	West, bet. secs. 20 and 29.
	Desc. along NW slope.
39.85	Point for the ¼ sec. cor. of secs. 20 and 29, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a collar of stone, with brass cap mkd.
	T 3 N R 1 E ¼ S 20 / S 29 1978
	from which
	An oak, 4 ins. diam., bears N. 65½° E., 22 lks. dist., mkd. BT.
	Cor. is located in dense oak and undergrowth on steep NW slope.
79.70	The cor. of secs. 19, 20, 29, and 30.
	S. 89°40' W., bet. secs. 19 and 30.
19.80	Point for the E 1/16 sec. cor. of secs. 19 and 30, at midpoint falls on private land and is not monumented.

CHAINS	
39.60	The ¼ sec. cor. of secs. 19 and 30, monumented with an iron post, 2½ ins. diam., set in cement, flush with the ground, with brass cap mkd. as described in the official record of the 1952 resurvey.
	From the cor. of secs. 19, 20, 29, and 30.
	N. 0°13' W., bet. secs. 19 and 20.
4.00	Steed Creek, drains W.
19.89	Point for the S 1/16 sec. cor. of secs. 19 and 20.
	Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base to top of brass cap, mkd. T 3 N R 1 E S 1/16 S 19 | S 20 1978
39.78	The ¼ sec. cor. of secs. 19 and 20, monumented with a brass tablet, 3 ins. diam., set in a boulder, 30 x 20 x 20 ins., mkd. ¼ on W face of boulder, with brass tablet mkd. as described in the official record of the 1952 resurvey.
	from which A 4 x 4 ft. white post, bears N. 16° 36' E., 11 lks. dist., with the words SEC COR painted on it.
	N. 0°12' W., beginning new measurement.
40.01	The cor. of secs. 17, 18, 19, and 20, monumented with a brass tablet, 3 ins. diam., set in concrete, mkd. DAVIS COUNTY SURVEY 18 | 17 19 | 20
	from which the bearing trees established in 1952 by R.C. Yundt, Cadastral Surveyor, A mountain mahogany, 4 ins. diam., bears N. 84°30' E., 13 lks. dist., mkd. BT. A mountain mahogany, 4 ins. diam., bears S. 38°45' W., 31 lks. dist., mkd. BT. A mountain mahogany, 4 ins. diam., bears N. 31° W., 76 lks. dist., mkd. BT.

U.S. Government Printing Office-1978-778-206/433

CHAINS	
	N. 89°48' W., bet. secs. 18 and 19.
19.94	Point for the E 1/16 sec. cor. of secs. 18 and 19. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T 3 N R 1 E E 1/16 S 18 / S 19 1977
39.88	The ¼ sec. cor. of secs. 18 and 19, monumented with an iron post, 2½ ins. diam., set in concrete, flush with the ground, with brass cap mkd. as described in the official record of the 1952 resurvey.
	From the cor. of secs. 17, 18, 19, and 20. N. 0°01' W., bet. secs. 17 and 18.
39.99	The ¼ sec. cor. of secs. 17 and 18, monumented with an iron post, 2½ ins. diam., protruding 5 ins. above ground, with a mound of stone W of cor., with brass cap mkd. as described in the official record of the 1952 resurvey.
	N. 0°10' E., beginning new measurement.
20.06	Point for the N 1/16 sec. cor. of secs. 17 and 18. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 3 N R 1 E N 1/16 S 18 | S 17 1978 Cor. is located on steep NE slope in grove of young maple trees.
40.12	Point for the cor. of secs. 7, 8, 17, and 18, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T 3 N R 1 E S 7 | S 8 S 18 | S 17 1977

CHAINS	
	Cor. is located about 1 ch. N of Farmington Canyon road, bears SE and SW. From this cor., the cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the Tp., bears N. 0°07' E., 161.11 chs. dist., heretofore described. The control line was fully retraced and no evidence of intervening cors. was found.
	N. 88°44' W., bet. secs. 7 and 18.
19.825	Point for the E 1/16 sec. cor. of secs. 7 and 18. Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a collar of stone, with brass cap mkd. T 3 N R 1 E E 1/16 S 7 / S 18 1977 Cor. is located on steep W slope.
39.65	The ¼ sec. cor. of secs. 7 and 18, monumented with an iron post, 2½ ins. diam., firmly set, protruding 2 ins. above ground, with brass cap mkd. as described in the official record of the 1952 resurvey.
	S. 89°26' W., beginning new measurement.
20.00	The W 1/16 sec. cor. of secs. 7 and 18, a county monument, 3 in. tablet set in concrete block, 4 x 4 ins., and 4 ins. above ground, mkd. DAVIS COUNTY SURVEY 1952 This position is accepted as a careful and faithful determination of the position of the cor.
40.00	The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., monumented with an iron post, firmly set, protruding 2 ins. above ground, with brass cap mkd. as described in the official record of the 1952 resurvey. Cor. is located on E edge of gravel road, bears N and S.

Subdivision of Section 10, T. 3 N., R. 1 E.,
Salt Lake Meridian, Utah

U.S. Government Printing Office-1978-778-206/433

Subdivision of Section 10, T. 3 N., R. 1 E.,
Salt Lake Meridian, Utah

CHAINS	
	From the ¼ sec. cor. of secs. 10 and 15.
	N. 1°13' W., on the N and S center line of sec. 10.
	Asc. SW slope.
20.055	Point for the center south 1/16 sec. cor. of sec. 10.
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T 3 N R 1 E C S 1/16 | S 10 C 1978
40.11	Point for the center ¼ sec. cor. of sec. 10, at intersection with the E and W center line.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 3 N R 1 E C ¼ S 10 1977
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
60.165	Point for the center north 1/16 sec. cor. of sec. 10.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T 3 N R 1 E C N 1/16 | S 10 C 1978
	Cor. is located 1 ch. E of Whipple Creek, drains S.
65.00	Francis Peak road, bears NW and SE.
80.22	The ¼ sec. cor. of secs. 3 and 10.
	From the ¼ sec. cor. of secs. 10 and 11.
	N. 89°59' W., on the E and W center line of sec. 10.
19.95	Point for the center east 1/16 sec. cor. of sec. 10.

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 5 ft. base to top of brass cap, mkd. T 3 N R 1 E C —— E 1/16 / S 10 —— C 1978
32.00	Francis Peak road, bears N and SE.
39.90	The center ¼ sec. cor. of sec. 10.
48.00	Whipple Creek, drains SW.
59.85	Point for the center west 1/16 sec. cor. of sec. 10. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T 3 N R 1 E C —— W 1/16 / S 10 —— C 1977
79.80	The ¼ sec. cor. of secs. 9 and 10.
	From the center east 1/16 sec. cor. of sec. 10. N. 1°18' W., on the N and S center line of the NE¼ of sec. 10. Asc. SW slope.
20.055	Point for the NE 1/16 sec. cor. of sec. 10, at the intersection with the E and W center line of the NE¼ of sec. 10. Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of brass cap, mkd. T 3 N R 1 E NE 1/16 S 10 1978 Cor. is located on steep E slope, 1.50 chs. E from crest of main divide, bearing NW and SE.
40.11	The E 1/16 sec. cor. of secs. 3 and 10.
	From the N 1/16 sec. cor. of secs. 10 and 11. N. 89°59' W., on the E and W center line of the NE¼ of sec. 10. Asc. NE slope.

U.S. Government Printing Office-1978-778-206/433

CHAINS	
19.925	The NE 1/16 sec. cor. of sec. 10.
38.00	Francis Peak road, bears NW and SE.
39.85	The center north 1/16 sec. cor. of sec. 10.
	From the E 1/16 sec. cor. of secs. 10 and 15.
	N. 1°17' W., on the N and S center line of the SE¼ of sec. 10.
	Asc. steep SW slope.
17.50	Francis Peak road, bears NW and SE.
20.055	Point for the SE 1/16 sec. cor. of sec. 10, at the intersection of the E and W center line of the SE¼ of sec. 10.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T 3 N R 1 E
	SE 1/16 S 10
	1977
40.11	The center east 1/16 sec. cor. of sec. 10.
	From the S 1/16 sec. cor. of secs. 10 and 11.
	N. 89°58' W., on the E and W center line of the SE¼ of sec. 10.
	Desc. over SW slope.
15.00	Bend in Francis Peak road, bears SE and SW.
19.975	The SE 1/16 sec. cor. of sec. 10.
21.50	Francis Peak road, bears NW and SE.
39.95	The center south 1/16 sec. cor. of sec. 10.
	From the center west 1/16 sec. cor. of sec. 10.
	N. 1°09' W., on the N and S center line of the NW¼ of sec. 10.
	Asc. steep SW slope.
20.05	Point for the NW 1/16 sec. cor. of sec. 10, at the intersection of the E and W center line of the NW¼ of sec. 10.

Subdivision of Section 10, T. 3 N., R. 1 E.,
Salt Lake Meridian, Utah

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 3 N R 1 E NW 1/16 S 10 1977 Raise a mound of stone, 2 ft. base, 1½ ft. high, S of cor. Cor. is located on S slope.
40.10	The W 1/16 sec. cor. of secs. 3 and 10.
	From the center north 1/16 sec. cor. of sec. 10. N. 89°59' W., on the E and W center line of the NW¼ of sec.10. Desc. steep SW slope.
1.00	Whipple Creek, drains SE.
19.925	The NW 1/16 sec. cor. of sec. 10.
39.85	The N 1/16 sec. cor. of secs. 9 and 10.

Subdivision of Section 12, T. 3 N., R. 1 E.,
Salt Lake Meridian, Utah

	From the ¼ sec. cor. of secs. 12 and 13. N.1° 48' W., on the N and S center line of sec. 12. Desc. along steep NE slope.
40.27	Point for the center ¼ sec. cor. of sec. 12, at intersection with the E and W center line. Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a collar of stone, with brass cap mkd. T 3 N R 1 E C 1/4 S 12 1978 from which A spruce, 10 ins. diam., bears N. 20° 07' W., 45½ lks. dist., mkd. BT. Cor. is located in dense undergrowth on steep NE slope.

U.S. Government Printing Office-1978-778-206/433

Subdivision of Section 12, T. 3 N., R. 1 E.,
Salt Lake Meridian, Utah

CHAINS	
80.54	The ¼ sec. cor. of secs. 1 and 12.
	From the ¼ sec. cor. of sec. 12 only, on the E. bdy. of the Tp.
	S. 89°36' W., on the E and W center line of sec. 12.
	Asc. over E slope.
19.94	Point for the center east 1/16 sec. cor. of sec. 12
	Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of brass cap, mkd.
	T 3 N R 1 E
	C — E 1/16 / S 12 — C
	1978
39.88	The center ¼ sec. cor. of sec. 12.
79.76	The ¼ sec. cor. of secs. 11 and 12.

Subdivision of Section 14, T. 3 N., R. 1 E.,
Salt Lake Meridian, Utah

	From the ¼ sec. cor. of secs. 14 and 23.
	N. 0°06' W., on the N and S center line of sec. 14.
	Desc. along E slope through dense undergrowth.
20.055	Point for the center south 1/16 sec. cor. of sec. 14.
	Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of brass cap, mkd.
	T 3 N R 1 E
	C S 1/16 | S 14 C
	1978
	Cor. is located on steep N slope.
22.00	Farmington Creek, drains W.
24.50	Skyline Drive road, bears E and W.

42

Subdivision of Section 14, T. 3 N., R. 1 E.,
Salt Lake Meridian, Utah

CHAINS	
40.11	Point for the center ¼ sec. cor. of sec. 14, at intersection with the E and W center line. Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a collar of stone, with brass cap mkd. T 3 N R 1 E C 1/4 S 14 1978 Cor. is located at point of spur, slopes SE.
48.00	Francis Peak road, bears NW and SE.
60.165	Point for the center north 1/16 sec. cor. of sec. 14. Set an iron post, 28 ins. long, 2½ ins. diam., on solid rock, in a mound of stone, 3½ ft. base to top of brass cap, mkd. T 3 N R 1 E C N 1/16 | S 14 C 1978 Cor. is located on SW slope.
80.22	The ¼ sec. cor. of secs. 11 and 14.
	From the ¼ sec. cor. of secs. 13 and 14. N. 89°57' W., on the E and W center line of sec. 14. Asc. steep E slope.
20.02	Point for the center east 1/16 sec. cor. of sec. 14. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 3 N R 1 E C — E 1/16 / S 14 — C 1978 Cor. is located on E slope, 2.00 chs. NW of bend in foot trail, bearing NE and S.
35.00	Francis Peak road, bears NW and SE.
40.04	The center ¼ sec. cor. of sec. 14.
60.06	Point for the center west 1/16 sec. cor. of sec. 14. not monumented.

U.S. Government Printing Office-1978-778-206/433

CHAINS	
80.08	The ¼ sec. cor. of secs. 14 and 15.
	From the E 1/16 sec. cor. of secs. 14 and 23.
	N. 0°07' W., on the N and S center line of the SE¼ of sec. 14.
	Desc. NE slope.
1.50	Skyline Drive road, bears W and SE.
2.50	Farmington Creek, drains NW.
3.50	Skyline Drive road, bears NW and SE.
15.00	Gravel road to Francis Peak, bears NW and SE.
20.055	Point for the SE 1/16 sec. cor. of sec. 14, at intersection with the E and W center line of the SE¼ of sec. 14.
	Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base to top of brass cap, mkd.
	T 3 N R 1 E
	SE 1/16 S 14
	1978
	Cor. is located on W slope.
27.00	Francis Peak road, bears NW and SE.
40.11	The center east 1/16 sec. cor. of sec. 14.
	From the S 1/16 sec. cor. of secs. 13 and 14.
	N. 89°57' W., on the E and W center line of the SE¼ of sec. 14.
	Asc. NE slope.
14.00	Francis Peak road, bears NW and SE.
20.025	The SE 1/16 sec. cor. of sec. 14.
20.78	Gravel road to Francis Peak, bears NW and SE.
32.00	Skyline Drive road, bears NW and SE.
34.00	Farmington Creek, drains NW.
40.05	The center south 1/16 sec. cor. of secs. 14.
	From the point for the center west 1/16 sec. cor. of sec. 14.

Subdivision of Section 14, T. 3 N., R. 1 E.,
Salt Lake Meridian, Utah

CHAINS	
	N. 0°06' W., on the N and S center line of the NW¼ of sec. 14.
	Asc. steep S slope.
20.055	Point for the NW 1/16 sec. cor. of sec. 14, at intersection with the E and W center line of the NW¼ of sec. 14.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 3 N R 1 E NW 1/16 S 14 1978
	Cor. is located on SW slope in dense undergrowth and aspen.
40.11	The W 1/16 sec. cor. of secs. 11 and 14.
	From the center north 1/16 sec. cor. of sec. 14.
	N. 89°57' W., on the E and W center line of the NW¼ of sec. 14.
	Desc. SW slope.
6.00	Francis Peak road, bears NW and SE.
20.02	The NW 1/16 sec. cor. of sec. 14.
40.04	The N 1/16 sec. cor. of secs. 14 and 15.

Subdivision of Section 18, T. 3 N., R.1 E.,
Salt Lake Meridian, Utah

	From the ¼ sec. cor. of secs. 18 and 19.
	N. 0°08' E., on the N and S center line of sec. 18.
40.09	Point for the center ¼ sec. cor. of sec. 18, falls in reservoir and cannot be monumented. The point was reestablished from ties furnished by Davis County Surveyor's Office.
	from which A manhole over aqueduct bears N. 83°26' E., 339.43 ft. dist. A PK and washer in wooden power pole, bears S. 7°45' E., 531.08 ft. dist.
	This position is accepted as a careful and faithful determination of the cor. position.

U.S. Government Printing Office-1978-778-206/433

Subdivision of Section 18, T. 3 N., R. 1 E.,
Salt Lake Meridian, Utah

CHAINS	
	N. 0°21' E., beginning new measurement.
20.38	Point for the center north 1/16 sec. cor. of sec. 18.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T 3 N R 1 E C N 1/16 | S 18 C 1977
40.76	The ¼ sec. cor. of secs. 7 and 18.
	From the ¼ sec. cor. of secs. 17 and 18.
	N. 89°39' W., on the E and W center line of sec. 18.
19.89	Point for the center east 1/16 sec. cor. of sec. 18.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	E 1/16 C_____C S 18 1977
39.78	Point for the center ¼ sec. cor. of sec. 18.
	N. 89°43' W., beginning new measurement.
19.97	Point for the center west 1/16 sec. cor. of sec. 18, not monumented.
39.94	The ¼ sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set in concrete flush with the ground, with brass cap mkd. as described in the official record of the 1952 resurvey.
	From the center east 1/16 sec. cor. of sec. 18.
	N. 0°16' E., on the N and S center line of the NE¼ of sec. 18.
20.22	Point for the NE 1/16 sec. cor. of sec. 18.
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.
	NE 1/16 S 18 1977

Subdivision of Section 18, T. 3 N., R. 1 E.,
Salt Lake Meridian, Utah

CHAINS	
40.44	The E 1/16 sec. cor. of secs. 7 and 18.
	From the N 1/16 sec. cor. of secs. 17 and 18.
	N. 89°11' W., on the E and W center line of the NE¼ of sec. 18.
19.855	The NE 1/16 sec. cor. of sec. 18.
39.71	The center north 1/16 sec. cor. of sec. 18.
	From the point for the center west 1/16 sec. cor. of sec. 18.
	N. 0°34' E., on the N and S center line of the NW¼ of sec. 18.
20.19	The NW 1/16 sec. cor. of sec. 18, monumented with a brass tablet, 3 ins. diam., set in a concrete block, protruding 4 ins. above ground, mkd. with the words DAVIS COUNTY SURVEY and an X on top, and is accepted as a careful and faithful determination of the position of the cor.
	N. 0°06' E., beginning new measurement.
20.28	The W 1/16 sec. cor.of secs. 7 and 18.
	From the center north 1/16 sec. cor. of sec. 18.
	S. 89°44' W., on the E and W center line of the NW¼ of sec. 18.
19.90	The NW 1/16 sec. cor. of sec. 18.
	Subdivision of Section 19, T. 3 N., R. 1 E., Salt Lake Meridian, Utah
	From the ¼ sec. cor. of secs. 19 and 30.
	N. 0°14' E., on the N and S center line of sec. 19.
19.97	Point for the center south 1/16 sec. cor. of sec. 19, falls on and is surrounded by private land and is not monumented.
39.94	The center ¼ sec. cor. of sec. 19, monumented with a brass tablet, set by Davis County Surveyors in concrete, 3 ft. below surface of ground mkd.

U.S. Government Printing Office-1978-778-206/433

CHAINS	
	C 1/4 S 19 DAVIS COUNTY from which A (PK) nail in street, bears N. 0°09' W., 102.37 ft. dist. An (X) chiseled in curb, bears N. 0°09' W., 69.50 ft. dist. Both reference points are set in front of private residence and were set by the county surveyor. This cor. point is accepted as a careful and faithful determination of the position of the cor.
	N. 1°02' W., beginning new measurement.
40.24	The ¼ sec. cor. of secs. 18 and 19.
	From the ¼ sec. cor. of secs. 19 and 20. S. 89°53' W., on the E and W center line of sec. 19.
19.64	Point for the center east 1/16 sec. cor. of sec. 19. Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base to top of brass cap, mkd. E 1/16 C ——— C S 19 1978 Cor. is located 50 lks. N of small gulley, 15 ft. deep, drains W and 30 lks. S of spur, slopes W.
39.28	The center 1/4 sec. cor. of sec. 19.
	S. 89°59' W., beginning new measurement.
40.30	The ¼ sec. cor. of secs. 19 and 24, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set in concrete flush with the ground with brass cap mkd. as described in the official record of the 1952 resurvey.
	From the point for the E 1/16 sec. cor. of secs. 19 and 30. N. 0°01' E., on the north and south center line of the SE¼ of sec. 19.

Subdivision of Section 19, T. 3 N., R. 1 E.,
Salt Lake Meridian, Utah

CHAINS	
19.93	Point for the SE 1/16 sec. cor. of sec. 19, at the intersection with the east and west center line of the SE¼ of sec. 19. Set an iron post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd. T 3 N R 1 E SE 1/16 S 19 1978 Cor. is located, south 4 lks. dist. from cement irrigation ditch, runs from east to west, and at NE cor. of small shed, 8' x 8'.
39.12	Small gulley, 15 ft. deep, drains W.
39.86	The center east 1/16 sec. cor. of sec. 19.
	From the S 1/16 sec. cor. of secs. 19 and 20. S. 89°47' W., on the east and west center line of the SE¼ of sec. 19.
19.72	The SE 1/16 sec. cor. of sec. 19.
39.44	Point for the center south 1/16 sec. cor. of sec. 19.
	Subdivision of Section 29, T. 3 N., R. 1 E., Salt Lake Meridian, Utah
	From the ¼ sec. cor. of secs. 29 and 32. N. 0°43' W., on the N and S center line of sec. 29.
20.05	Point for the center south 1/16 sec. cor. of sec. 29. Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a collar of stone, with brass cap mkd. T 3 N R 1 E C | S 1/16 | S 29 | C 1978 Cor. is located on steep SW slope.
30.075	Point for the center north south 1/64 sec. cor. of sec. 29. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

U.S. Government Printing Office-1978-778-206/433

Subdivision of Section 29, T. 3 N., R. 1 E.,
Salt Lake Meridian, Utah

CHAINS	
	T 3 N R 1 E C NS 1/64 | S 29 C 1978
40.10	Point for the center ¼ sec. cor. of sec. 29, at intersection with the E and W center line of sec. 29. Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base to top of brass cap, mkd. T 3 N R 1 E C 1/4 S 29 1978 Cor. is located 1.50 chs. N Davis Creek and 20 lks. S of granite ledge, bearing NW and SE.
80.23	The ¼ sec. cor. of secs. 20 and 29.
	From the ¼ sec. cor. of secs. 28 and 29. S. 89°56' W., on the E and W center line of sec. 29.
39.96	The center ¼ sec. cor. of sec. 29.
79.92	The ¼ sec. cor. of secs. 29 and 30.
	Subdivision of Section 32, T. 3 N., R. 1 E., Salt Lake Meridian, Utah
	From the point for the ¼ sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp., heretofore described. N. 0°21' W., on the N and S center line of sec. 32.
40.11	Point for the center ¼ sec. cor. of sec. 32, at intersection with the E and W center line. Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a collar of stone, with brass cap mkd. T 3 N R 1 E C 1/4 S 32 1978 Cor. is located 15 lks. W of small ravine, drains W.

CHAINS	
80.24	The ¼ sec. cor. of secs. 29 and 32.
	From the ¼ sec. cor. of secs. 32 and 33.
	S. 89°53' W., on the E and W center line of sec. 32.
40.00	The center ¼ sec. cor. of sec. 32.
59.97	Point for the center west 1/16 sec. cor. of sec. 32.
	Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of brass cap, mkd.
	T 3 N R 1 E
	C $\frac{\text{W } 1/16}{\text{S } 32}$ C
	1978
	Cor. is located on W slope, 3½ chs. E of road along base of shelf of foothills.
79.94	The ¼ sec. cor. of secs. 31 and 32.

General Description

Most of the land encompassed by this survey is located within the Wasatch National Forest. The city of Farmington is located in parts of sections, 18, 19, 30, and 31. The township is drained by numerous creeks, the most notable being Farmington Creek on the west side of the Tp. and Deep Creek on the east side. Elevation ranges from 4300 ft. above sea level in Farmington City to 9400 ft. above sea level on the north boundary near Francis Peak. A ridge divides Morgan and Davis Counties that extends between Francis Peak and Bountiful Peak and beyond with steep slopes on each side, covered with pine, aspen, oak, maple, and numerous types of dense undergrowth.

The primary access to the interior of the Tp. is the Skyline Drive road from Farmington City to Bountiful Peak to Bountiful City. A branch of this road also goes to Francis Peak.

The principle uses of the area are recreation and grazing.

Mean magnetic declination was found to be 15° 30' E.

☆ U.S. Government Printing Office-1978-778-206/433

Form 9600-11
(August 1979)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
John Hales	Surveying Technician
T. Stewart Burt	Surveying Technician
Kevin Hinkley	Survey Aid
Merlin Sinfield	Survey Aid
Mark McKay	Survey Aid
Blaine Tew	Survey Aid

52

CERTIFICATE OF SURVEY

XX (We), Glen B. Hatch, Frank Profaizer, and Daniel T. Mates, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 16th day of August, 1966, XX (We) have dependently resurveyed the east and north boundaries, the east 5 miles of the south boundary, a portion of the subdivisional lines, and partial subdivision of sections 10, 12, 14, 18, 19, 29, and 32, T. 3 N., R. 1 E.,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by XXX, (us) and under (XX) (our) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

September 14, 1979 (Date)	Frank C. Profaizer (Cadastral Surveyor)
September 14, 1979	Glen B. Hatch (Supervisory Cadastral Surveyor)
September 14, 1979 (Date)	Daniel T. Mates (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Denver, Colorado

The foregoing field notes of the dependent resurvey of the east and north boundaries, the east 5 miles of the south boundary, a portion of the subdivisional lines, and partial subdivision of sections 10, 12, 14, 18, 19, 29, and 32, T. 3 N., R. 1 E., Salt Lake Meridian, Utah

executed by Glen B. Hatch, Supervisory Cadastral Surveyor, Frank Profaizer, and Daniel T. Mates, Cadastral Surveyors
having been critically examined and found correct, are hereby approved.

OCT 28 1980 (Date)	D. Van Ness (Chief, Cadastral Survey Examination and Approval Staff)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in , is a true copy of the original field notes.~~

~~(Date) (Chief, Cadastral Survey Examination and Approval Staff)~~

R601

Form 9600-9
(December 1979)
(formerly 9180-6)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

A PORTION OF THE SUBDIVISIONAL LINES,

THE ADJUSTED ORIGINAL MEANDER LINE

OF THE

EAST SHORE OF RUSH LAKE

THROUGH SECTION 26

AND

THE SURVEY OF A PORTION OF THE SUBDIVISION

OF

SECTION 26,

TOWNSHIP 4 SOUTH, RANGE 5 WEST

Of the Salt Lake Meridian,

In the State of Utah.

EXECUTED BY

Glen B. Hatch Supervisory Cadastral Surveyor

Under special instructions dated December 15, 19 78, approved January 10, 1979,

and Supplemental Special Instructions dated November 19, 1979 and approved November 26, 1979.

_____, which provided for the surveys included under U.S. Survey/Group

Number 585, and assignment instructions dated January 17, 19 79.

Survey commenced February 22, 19 79

Survey completed October 23, 19 80

INDEX DIAGRAM

Township 4 S., Range 5 W.,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23 6	24
30	29	28	27 8 5	26 4 2	25
31	32	33	34 1	35	36

Subdivision of Sec. 26 Page 9
Meander lines E Shore Rush Lake Page 11

Township 4 South, Range 5 West, Salt Lake Meridian, Utah

CHAINS

A portion of the subdivisional lines and the Rush Valley Military Reserve was surveyed by C.L. Craig in 1856. A portion of the subdivisional lines and the Rush Valley Military Reserve was resurveyed, and a portion of the subdivision was surveyed by E. W. Koeber in 1886. A portion of the subdivisional lines was retraced and resurveyed and a portion surveyed by Alonzo J. Stookey in 1905.

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, the adjusted original meander line of the east shore of Rush Lake through Sec. 26, and the survey of a portion of the subdivision of Sec. 26, Township 4 South, Range 5 West, Salt Lake Meridian, Utah.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions 1973, the Special Instructions dated December 15, 1978, and the Supplemental Special Instructions dated November 19, 1979.

The directions of the lines of this survey were determined by reference to the true meridian established on line by hour angle observations on Polaris. They were carried forward by sustained angulation, being supplemented by other hour angle observations on Polaris.

The distances along surveyed lines were determined by electronic measurement.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the southeast corner of Sec. 26, as scaled from U.S.G.S. topographic sheet "Stockton" 15 minute series, 1955, is at Latitude 40° 26' 10" North and Longitude 112° 21' 56" West.

The mean magnetic declination was found to be 16° East.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 4 S., R. 5 W., Salt Lake Meridian, Utah

---

(Reestablishment of the Survey Executed by Alonzo J. Stookey in 1905

Beginning at the ¼ sec. cor. of secs. 34 and 35, monumented with a sandstone, 10 x 7 x 5 ins., firmly set 5 ins. in the ground, and plainly mkd. ¼ on W face.

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, with cap mkd.

CHAINS	
	T 4 S R 5 W ¼ S 34 | S 35 1980
	Set a wooden post and bury the mkd. stone alongside the aluminum post.
	N. 0° 37' E., bet. secs. 34 and 35.
	Over nearly level wetland.
39.60	The closing cor. of secs. 26 and 34, monumented with a sandstone, 16 x 8 x 5 ins., firmly set 12 ins. in the ground, mkd. CC on W face.
	At the corner point
	Set a cedar post, 6 ft. long, 4 ins. sq., 3 ft. in the ground, mkd. S26 on N, S35 on E, S34 on S, and T 4 S R 5 W CC with 4 grooves on W faces.
	Bury the mkd. stone alongside the wooden post.
40.43	The NW cor. of sec. 35, monumented with a sandstone, 18 x 9 x 4 ins., firmly set 14 ins. in the ground, mkd. 2 notches on E edge and 1 groove on S face.
	At the corner point
	Set a cedar post, 6 ft. long, 4 ins. sq., 3 ft. in the ground, mkd. T 4 S S26 on NE, R5W S35 on SE, and S26 on the SW and NW faces, and 2 notches on the E edge and 1 notch on the S edge.
	Set a fiberglass fence post and bury the mkd. stone alongside the wooden post.
	Reestablishment of the Survey Executed by E. W. Koeber in 1886, and the Retracement Executed by Alonzo J. Stookey in 1905
	From the cor. of secs. 25, 26, 35, and 36, monumented with a sandstone, 15 x 12 x 5 ins., firmly set 10 ins. in the ground, and plainly mkd. 1 notch on the S and E edges. Cor. is located in N and S fence line.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 4 S R 5 W S 26 | S 25 S 35 | S 36 1979

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 4 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	Bury the mkd. stone alongside the iron post.
	S. 89° 42' W., bet. secs. 26 and 35.
	Over gently rolling land through sagebrush undergrowth.
20.08	Point for the E 1/16 sec. cor. of secs. 26 and 35.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with cedar post alongside, with brass cap mkd. T 4 S R 5 W E 1/16 S 26 / S 35 1979
	from which
	A sandstone, 8 x 6 x 4 ins., above ground, plainly mkd. with a cross (+) on N face, bears N. 7° 12' W., 19 lks. dist.
	Cor. of fence bears N. 19° 34' W., 19 lks. dist., with fence extending N and E.
26.58	Transmission line, bears N. 32° E. and S. 32° W.
30.64	Center line of State Highway No. 36, bears N. 35° 36' E. and S. 35° 36' W.
32.41	Transmission line, parallel to highway.
33.56	Center line of Union Pacific Railroad, parallel to highway.
36.00	Enter cultivated land, bears NE and W.
40.16	The ¼ sec. cor. of secs. 26 and 35, monumented with a limestone, 15 x 10 x 9 ins., firmly set 8 ins. in the ground, and in a collar of stone, plainly mkd. ¼ on N face.
	At the corner point
	Set an aluminum alloy post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with cap mkd. T 4 S R 5 W ¼ S 26 / S 35 1979
	Bury the mkd. stone alongside the aluminum post.
	Cor. is located in fence line, extending S. 89° 53' W., and about S. 85° E.
	S. 89° 53' W., beginning new measurement.

CHAINS	
	Over gently rolling land, along fence line.
22.62	The meander cor. of secs. 26 and 35, on E shore of Rush Lake, monumented with an iron post, 1½ ins. diam., extending 6 ins. above ground. This position is harmoniously related to existing original corners, and is accepted as a careful and faithful perpetuation of the position of the original meander cor.
	At the corner point
	Set an aluminum alloy post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with cap mkd.
	T 4 S R 5 W MC S 26 / S 35 1979
	Place the iron post alongside the aluminum post.
	Reestablishment of the Survey Executed by Alonzo J. Stookey in 1905
	N. 89° 44' W., beginning new measurement.
	Over nearly level land, along fence line.
3.17	Cor. of fence, on the margin of the bed of Rush Lake, with fences extending N. 9° 16' E., S. 89° 44' E., and S. 12° W.
17.01	The NW cor. of sec. 35.
	Reestablishment of the Survey Executed by E.W. Koeber in 1886, and the Retracement Executed by Alonzo J. Stookey in 1905
	From the cor. of secs. 25, 26, 35, and 36.
	N. 0° 31' W., bet. secs. 25 and 26.
	Over rolling land, through sagebrush undergrowth, along fence line.
0.31	Cor. of fences extending E, W, and N. 0° 31' W., continue along fence line.
20.00	Cor. of fence, with fences extending S. 0° 31' E., N. 0° 31' W., and W, continue along fence line.
20.12	Point for the S 1/16 sec. cor. of secs. 25 and 26, falls on solid private land and is not monumented.
40.24	The ¼ sec. cor. of secs. 25 and 26, monumented with a sandstone, 6 x 5 x 5 ins., firmly set 6 ins. in the ground, and plainly mkd. ¼ on W face. Cor. is located in N and S fence line, and in line with old fence line to E.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 4 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 4 S R 5 W ¼ S 26 | S 25 1979 Bury the mkd. stone alongside the iron post.
	N. 0° 31' W., beginning new measurement. Continue along fence line.
0.81	Right-of-way fence, bears N. 35° 36' E. and S. 35° 36' W.
0.91	Transmission line, parallel to fence.
2.11	Center line of State Highway No. 36, bears N. 35° 36' E. and S. 35° 36' W.
4.45	Transmission line, parallel to highway.
5.96	Center line of Union Pacific Railroad, bears N. 35° 36' E. and S. 35° 36' W.
8.00	Enter cultivated land, bears NE and SW.
39.94	The cor. of secs. 23, 24, 25, and 26, monumented with a granite stone, 13 x 13 x 8 ins., firmly set 10 ins. in the ground, plainly mkd. 1 notch on E and 2 on S edges. Cor. is located in old abandoned fence line, bears E and W. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T 4 S R 5 W S 23 | S 24 S 26 | S 25 1979 Bury the mkd. stone alongside the iron post.
	Reestablishment of the Survey Executed by Alonzo J. Stookey in 1905
	From the meander cor. of secs. 27 and 34, monumented with a broken limestone, 18 x 6 x 5 ins., firmly set 15 ins. in the ground, mkd. MC on E and 1 groove on S faces.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 4 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.
	T 4 S | S 27 / S 34 | R 5 W | MC
	1980
	Set a wooden post and bury the mkd. stone alongside the iron post.
	S. 89° 37' E., bet. secs. 27 and 34.
	Over nearly level land.
0.40	Unimproved road, bears NE and SW.
5.00	Margin of the bed of Rush Lake.
23.42	The closing cor. of secs. 26 and 27, monumented with a quartzite stone, 12 x 10 x 3 ins., firmly set 8 ins. in the ground, mkd. with 1 groove on S face.
	At the corner point
	Set a cedar post, 6 ft. long, 4 ins. sq., 3 ft. in the ground, mkd. T 4 S R 5 W CC and 5 grooves on, S 26 on E, S34 on S, and S27 on W faces.
	Bury the mkd. stone alongside the wooden post.
25.36	The closing cor. of secs. 26 and 34.

Reestablishment of the Survey Executed by E.W. Koeber in 1886, and the Retracement Executed by Alonzo J. Stookey in 1905

	From the cor. of secs. 23, 24, 25, and 26.
	S. 89° 42' W., bet. secs. 23 and 26.
	Over nearly level land along abandoned fence line, with cultivated land to S.
0.42	Cor. of fence, with fence extending S and S. 89° 42' W., thence along fence line.
39.73	The ¼ sec. cor. of secs. 23 and 26, monumented with an old wood hub in mound of stone. This point is harmoniously related to existing original cors., and is accepted as the best available evidence of the original cor. point.
	At the corner point
	Set an aluminum alloy post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with cap mkd.

CHAINS

T 4 S R 5 W

¼ S 23 / S 26

1979

Reestablishment of the Survey Executed by E.W. Koeber in 1886, and the Resurvey Executed by Alonzo J. Stookey in 1905

S. 89° 32' W., beginning new measurement.

Continue along fence line.

8.25 The meander cor. of secs. 23 and 26, on the E shore of Rush Lake, determined by cor. of fences, bearing S. 21° 39' W., and N. 89° 32' E., and is accepted as the best available evidence of the position of the original cor.

At the corner point

Set an aluminum alloy post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with cap mkd.

T 4 S R 5 W

MC / S 23 / S 26

1979

Reestablishment of the Survey Executed by Alonzo J. Stookey in 1905

S. 87° 23' W., beginning new measurement.

Across Rush Lake

23.63 The meander cor. of secs. 23 and 26, on W shore of Rush Lake, monumented with a limestone, 18 x 9 x 6 ins., firmly set 15 ins. in the ground, plainly mkd. MC on E face, with 2 grooves on S face.

At the corner point

Set an aluminum alloy post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with cap mkd.

T 4 S R 5 W

S 23 / S 26 / MC

1979

Bury the mkd. stone alongside the aluminum post.

CHAINS	
	Reestablishment of the Survey Executed by E.W. Koeber in 1886, and the Resurvey Executed by Alonzo J. Stookey in 1905
	N. 89° 37' W., beginning new measurement.
	Asc. 20 ft. over SE slope. Enter sagebrush.
2.00	Road, on slight curve, bears N. 45° E. and S. 20° W.; asc. 95 ft. over SE slope.
8.85	The cor. of secs. 22, 23, 26, and 27, monumented with a quartzite stone, 18 x 9 x 6 ins., firmly set 8 ins. in the ground, and in a collar of stone, plainly mkd. 2 notches on S and E edges.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T 4 S R 5 W T 22 | S 23 S 27 | S 26 1979
	Bury the mkd. stone alongside the iron post.
	S. 0° 25' W., bet. secs. 26 and 27.
	Over gently rolling land.
37.88	The meander cor. of secs. 26 and 27, monumented with a sandstone, 18 x 10 x 8 ins., firmly set 15 ins. in the ground, mkd. MC on the S face and 2 grooves on the E face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T 4 S R 5 W S 27 | S 26 MC 1980
	Bury the mkd. stone alongside the iron post.
	Reestablishment of the Survey Executed by Alonzo J. Stookey in 1905
	S. 0° 24' W., beginning new measurement.
	Over nearly level land.

CHAINS	
1.42	Point for the ¼ sec. cor. of sec. 26, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd. T 4 S R 5 W ¼ | S 26 | 1980
2.07	Point for the ¼ sec. cor. of sec. 27. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd. T 4 S R 5 W ¼ | | S 27 | 1980
6.10	Margin of the bed of Rush Lake
42.02	The closing cor. of secs. 26 and 27.
	Survey of a Portion of the Subdivision of Section 26, T. 4 S., R. 5 W., Salt Lake Meridian, Utah
	From the ¼ sec. cor. of secs. 26 and 35. N. 0° 13' W., on the north and south center line of sec. 26. Over nearly level cultivated land.
20.07	Point for the center south 1/16 sec. cor. Set an aluminum alloy post, 28 ins. long, 2½ ins. diam., 6 ins. below the ground, with cap mkd. T 4 S R 5 W C | S 1/16 | S 26 | C 1979

CHAINS	
	Set a steel fence post, 36 ins. in the ground, alongside the aluminum post.
	Continue over cultivated land.
40.14	Point for the C¼ sec. cor. of sec. 26, at the intersection with the E and W center line, falls on solid private land, and at request of land owner, point not monumented.
	Continue over cultivated land.
80.18	The ¼ sec. cor. of secs. 23 and 26.
	From the ¼ sec. cor. of secs. 25 and 26.
	S. 89° 33' W., on the E and W center line of sec. 26.
	Over gently rolling land.
0.55	Right-of-way fence, bears N. 35° 36' E. and S. 35° 36' W.
0.64	Transmission line, parallel with right-of-way fence.
1.46	Center line of State Highway No. 36, bears N. 35° 36' E. and S. 35° 36' W.
3.19	Transmission line, parallel to highway.
4.28	Center of Union Pacific Railroad, bears N. 35° 36' E. and S. 35° 36' W.
18.95	Enter cultivated land, bears N and S.
19.97	Point for the center east 1/16 sec. cor. of sec. 26, falls on private cultivated land and is not monumented.
	Continue over cultivated land.
39.94	The C¼ sec. cor. of sec. 26.
57.66	Intersect the meander line on the east side of Rush Lake.
59.05	Fence, bears N. 9° 16' E. and S. 9° 16' W.
81.09	The ¼ sec. cor. of sec. 26.
	From the E 1/16 sec. cor. of secs. 26 and 35.
	N. 0° 22' W., on the N and S center line of the SE¼ of sec. 26.
	Over gently rolling land, through sagebrush undergrowth, along E side of fence bears nearly N.
13.72	Transmission line, parallel to highway.
14.92	Center line of State Highway No. 36, bears N. 35° 36' E. and S. 35° 36' W.
17.10	Transmission line, parallel to highway.

Survey of a Portion of the Subdivision of Section 26,
T. 4 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
18.67	Center line of Union Pacific Railroad, bears N. 35° 36' E. and S. 35° 36' W.
20.10	Point for the SE 1/16 sec. cor. of sec. 26, at the intersection with the E and W center line of the SE¼.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 4 S R 5 W SE 1/16 S 26 1979
40.19	The point for the center east 1/16 sec. cor.
	From the point for the S 1/16 sec. cor. of secs. 25 and 26.
	S. 89° 37' W., on the E and W center line of the SE¼ of sec. 26.
	Over gently rolling land, along N side of fence line.
15.37	Right-of-way fence, bears N. 35° 36' E. and S. 35° 36' W.
15.45	Transmission line, parallel to fence.
16.30	Center line of State Highway No. 36, bears N. 35° 36' E. and S. 35° 36' W.
17.85	Transmission line, parallel to highway.
18.98	Center line of Union Pacific Railroad, bears N. 35° 36' E. and S. 35° 36' W.
20.03	The SE 1/16 sec. cor. of sec. 26.
40.06	The center south 1/16 sec. cor. of sec. 26.
	Adjusted Original Meanders of East Shore, Rush Lake through Sec. 26, T. 4 S., R. 5 W., Salt Lake Meridian, Utah
	Reestablishment of the Meanders of East Shore of Rush Lake, Sec. 26, Executed by E.W. Koeber in 1886
	From the meander cor. of secs. 26 and 35, on the E shore of Rush Lake.
	N. 9° 13' E., over nearly level cultivated land.
24.04	Point for the adjusted angle point No. 1.
	Set an aluminum alloy post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with cap mkd.

66

Adjusted Original Meanders of East Shore, Rush Lake
through Sec. 26, T. 4 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	AP-1 T 4 S R 5 W S 26 1979
	Thence,
	N. 3° 09' E., beginning new measurement.
	Continue over cultivated land.
16.34	Intersect the E-W center line of sec. 26.
29.18	Intersect fence line, bears N. 9° 16' E. and S. 9° 16' W., leave cultivated land, enter grass.
36.06	Point for adjusted angle point No. 2.
	Set an aluminum alloy post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with cap mkd.
	AP-2 T 4 S R 5 W S 26 1979
	Thence,
	N. 21° 56' E., beginning new measurement.
	Continue over grassy land.
22.04	The meander cor. of secs. 23 and 26, on E shore of Rush Lake.

General Description

Section 26, Township 4 South, Range 5 West, is located adjacent to Stockton, Utah. The southeast portion is gently rolling land covered with sagebrush; the west, northeast, and north portions are nearly level farm land. Rush Lake is located in the western portion of the section, and at the time of this survey, covered a larger area than normal.

State Highway No. 36 and the Union Pacific Railroad pass through the southeast portion of the section.

There are homes located in the northeast quarter, the northeast quarter of the southeast quarter, and the southeast quarter of the southeast quarter.

No water was noted other than Rush Lake, which fluctuates greatly depending on the season.

The elevation is about 5,100 ft. above sea level, and the magnetic declination is 16° East.

Form 9600–11
(August 1979)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Frank Profaizer	Supervisory Land Surveyor
Gary Kratz	Supervisory Land Surveyor
Donald Buhler	Supervisory Land Surveyor
Scott McMullin	Supervisory Land Surveyor
Richard Zaninovich	Supervisory Land Surveyor
Mike Fitzgerald	Supervisory Land Surveyor
Brett Hillier	Surveying Technician
Stewart Burt	Surveying Technician
John Mavor	Survey Aid

68

CERTIFICATE OF SURVEY

(I) (~~We~~) Glen B. Hatch, Supervisory Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 15th day of December, 1978, and Supplemental Special Instructions dated November 19, 1979, (I) (~~We~~) have dependently resurveyed a portion of the subdivisional lines, the adjusted original meander line of the east shore of Rush Lake through Section 26, and surveyed a portion of the subdivision of Section 26 of Township 4 South, Range 5 West,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), (~~us~~) and under (my) (~~our~~) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

December 15, 1980
(Date)

Glen B Hatch
(Cadastral Surveyor)
Supervisory

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines, the adjusted original meander line of the east shore of Rush Lake through Section 26, and the survey of a portion of the subdivision of Section 26 of T. 4 S., R. 5 W. of Salt Lake Meridian, Utah

executed by Glen B. Hatch, Supervisory Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

FEB 26 1981
(Date)

D. Voorhees
(Chief, Cadastral Survey Examination and Approval Staff)

~~CERTIFICATE OF TRANSCRIPT~~

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in , is a true copy of the original field notes.

~~(Date)~~

~~(Chief, Cadastral Survey Examination and Approval Staff)~~

R601 69

Form 9600–9
(December 1979)
(formerly 9180–6)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

A PORTION OF THE EAST BOUNDARY

(FIRST GUIDE MERIDIAN EAST),

A PORTION OF THE SUBDIVISIONAL LINES

AND THE

SURVEY OF PORTIONS OF

THE SUBDIVISION OF SECTIONS 12 AND 13,

OF

TOWNSHIP 35 SOUTH, RANGE 4 EAST

Of the Salt Lake Meridian,

In the State of Utah.

EXECUTED BY

Glen B. Hatch Supervisory Cadastral Surveyor

Under special instructions dated October 31, 1978, approved November 1, 1978,

, which provided for the surveys included under ~~U.S. Survey~~/Group Number 583, and assignment instructions dated November 1, 1978.

Survey commenced November 15, 1978

Survey completed November 29, 1978

INDEX DIAGRAM

Township 35 S., Range 4 E.,

6	5	4	3	2	1 6
7	8	9	10	11	5 12 2 3
18	17	16	15	14	5 1 13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision of Sec. 12 - Page 7
Subdivision of Sec. 13 - Page 11

Township 35 South, Range 4 East, Salt Lake Meridian, Utah

CHAINS

The east boundary (First Guide Meridian East) was surveyed by William Lewman in 1893 and a portion dependently resurveyed and a portion independently resurveyed by Andrew Nelson in 1937. A portion of the subdivisional lines were surveyed by William Lewman in 1894 and a portion dependently resurveyed by Donald A. Cannon in 1959.

The following field notes are those of the dependent resurvey of a portion of the east boundary (First Guide Meridian East), a portion of the subdivisional lines and the survey of portions of the subdivision of sections 12 and 13, Township 35 South, Range 4 East, Salt Lake Meridian, Utah.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated October 31, 1978.

The direction of the lines of this survey were determined by reference to true meridians established on line by hour angle observations on Polaris. The lines were carried forward by sustained angulation being supplemented by other hour angle observations on Polaris.

Measurements were determined by electronic means along survey lines that were accessible, otherwise by traverse methods.

Before restoring the corners, the lines of the original survey were retraced and diligent search made for any evidence of the original corners or other evidence of the original field note record. The rules of proportionate measurement were applied to ascertain the position of the lost corners, but not until exhausting every reasonable possibility of finding direct evidence of the original corners.

The geographic position of the east ¼ sec. cor. of sec. 13, is at latitude 37°45'52" N., and longitude 111°24'16" W., as computed from the plat accepted October 12, 1962.

The magnetic declination was found to be 14° 30' E.

Dependent Resurvey of a Portion of the East Boundary,
(First Guide Meridian East),
T. 35 S., R. 4 E., Salt Lake Meridian, Utah

Reestablishment of the Independent Resurvey
Executed by Andrew Nelson in 1937

Beginning at the east ¼ sec. cor. of sec. 13, monumented with an iron post, 1 in. diam., extending 12 ins. above ground, and in a collar of stone, with brass cap mkd. as described in the official record of the 1937 resurvey.

from which the bearing tree mkd. in 1937

A juniper, 14 ins. diam., bears N. 56°15' W., 93 lks. dist., mkd. ¼ S13 BT.

Dependent Resurvey of a Portion of the East Boundary,
(First Guide Meridian East),
T. 35 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	N. 2°06' W., along the E. bdy. of sec. 13. Note: The topography along this line is the same as reported in 1937 and is omitted from these field notes.
20.105	Point for the N 1/16 sec. cor. of sec. 13. Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground and in a collar of stone, with brass cap mkd. T 35 S R 4 E R 5 E N 1/16 | | S 13 | 1978
40.21	The cor. of secs. 12 and 13, monumented with an iron post, extending 16 ins. above solid sandstone, and in a mound of stone, 3 ft. base to top of brass cap mkd. as described in the official record of the 1937 resurvey. from which the accessories mkd. in 1937 A pinon, 10 ins. diam., bears N. 4° 30' W., 67 lks. dist., scribed T35S R4E S12 BT. A cross (+) and B O on sandstone ledge, bears S. 36°45' W., 18 lks. dist.
	N. 1°40' E., along the E. bdy. of sec. 12. Note: The topography along this line is the same as reported in 1937 and is omitted from these field notes.
18.13	Point for the S 1/16 sec. cor. of sec. 12. Set an iron post, 1 in. diam., 16 ins. long, 6 ins. in drill hole in solid sandstone on SW face of sandstone knoll, with brass cap mkd. T 35 S R 4 E R 5 E S 1/16 | | S 12 | 1978
36.26	The ¼ sec. cor. of sec. 12, monumented with an iron post, 1 in. diam., extending 10 ins. above solid sandstone, with brass cap mkd. as described in the official record of the 1937 resurvey.

CHAINS	
	Dependent Resurvey of a Portion of the Subdivisional Lines, T. 35 S., R. 4 E., Salt Lake Meridian, Utah
	Reestablishment of the Survey Executed by William Lewman in 1894
	From the cor. of secs. 12 and 13, on the E. bdy. of the Tp., heretofore described.
	N. 89° 08' W., bet. secs. 12 and 13.
	Over broken land through widely scattered timber.
19.10	Point for the E 1/16 sec. cor. of secs. 12 and 13.
	Set an iron post, 28 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top of brass cap, mkd.
	T 35 S R 4 E
	E $\frac{1}{16}$ $\frac{S\ 12}{S\ 13}$
	1978
20.10	Top of ledge, 20 ft. high, bears N. 45° W. and curves S. 80° E.; desc. over broken SW slope into Escalante River bottom.
29.00	Escalante River, 60 lks. wide, 15 ins. deep, flows S; thence over level land.
36.00	Base of broken slope and ledges, bears N and S; asc. abruptly about 60 ft.
38.20	The ¼ sec. cor. of secs. 12 and 13, monumented with a sandstone, 20 x 4 x 3 ins., in small mound of stone, plainly mkd. ¼ on N face.
	from which the original bearing tree
	A juniper, 8 ins. diam., bears N. 88° E., 30 lks. dist., scribed ¼ S BT.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, and in a collar of stone to top, with brass cap mkd.
	T 35 S R 4 E
	¼ $\frac{S\ 12}{S\ 13}$
	1978
	Bury the mkd. stone alongside the iron post.
	Cor. is located on narrow shelf of ledge; 6 ft. high, 3 ft. wide, at base of near vertical ledge, 50 ft. high, bearing N and S.

74

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 35 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	S. 89° 08' W., beginning new measurement.
	Asc. abruptly over sandstone ledges, facing E.
2.00	Top of ledges, bears N and S; thence asc. over broken land.
8.30	State Highway No. 54, curves NE to Boulder, Utah and SW to Escalante, Utah.
16.50	Same highway, bears N. 63° W. to Escalante and S. 63° E. to Boulder, Utah; asc. over ledgy SE slope of spur.
20.14	Point for the W 1/16 sec. cor. of secs. 12 and 13.
	Set an iron post, 28 ins. long, 2½ ins. diam., over a cross (+) on solid sandstone, and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T 35 S R 4 E
	W 1/16 S 12/S 13
	1978
	Asc. SE slope.
21.00	Spur, projects N. 40° E.; asc. over general NE slope.
35.80	State Highway No. 54, on curve, bears N. 35° E. to Boulder and S. 45° W. to Escalante.
39.70	Power line, bears N. 28° E. and S. 28° W.
40.28	The cor. of secs. 11, 12, 13, and 14, monumented with a soft sandstone, 36 x 18 x 6 ins., with small mound of stone alongside. No marks remaining on original stone.
	from which the original remaining bearing trees
	A juniper, 18 ins. diam., bears S. 49° W., 29 lks. dist., scribed T35S R4E S14 BT.
	A pinon, 12 ins. diam., bears N. 3° W., 88½ lks. dist., scribed T35S R4E S11 BT.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd.
	T 35 S R 4 E
	S 11 | S 12 / S 14 | S 13
	1978
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor., and place the unmkd. stone in the mound.

CHAINS	
	S. 0° 01' E., bet. secs. 13 and 14.
	Over rolling broken land through scattered timber.
1.00	Power line, bears N. 28° E. and S. 28° W.
3.00	State Highway No. 54, bears N. 67° E. to Boulder and S. 67° W. to Escalante.
20.00	Top of ascent, thence over rolling land.
40.00	Point for the ¼ sec. cor. of secs. 13 and 14, at record bearing and distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 35 S R 4 E
	¼
	S 14 | S 13
	1978
	No accessories available.
	From the cor. of secs. 11, 12, 13, and 14.
	N. 6° 58' W., bet. secs. 11 and 12.
	Over exposed broken sandstone through widely scattered timber.
7.20	Top of sandstone ledge, 100 ft. high, bears S. 45° W. and curves E; desc. abruptly into River bottom.
15.75	Escalante River, 50 lks. wide, 12 ins. deep, flows N. 30° E.; enter tamarack undergrowth.
18.77	Point for the S 1/16 sec. cor. of secs. 11 and 12.
	Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 35 S R 4 E
	S 1/16
	S 11 | S 12
	1978
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.
21.00	Leave tamarack undergrowth; asc. abruptly over sandstone ledges.
22.00	Top of ledges, 25 ft. high, bears E and curves NW; asc. over broken and ledgy SW slope.

76

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 35 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
34.00	Top of high sandstone spur, projects S. 80° W.; desc. abruptly over sandstone ledges on NW slope.
37.54	Point for the ¼ sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 16 ins. long, 1 in. diam., 8 ins. in drill hole in solid sandstone, with brass cap mkd. T 35 S R 4 E ¼ S 11 | S 12 1978 from which A pinon, 3 ins. diam., bears S. 60° E., 8½ lks. dist., scribed BT.
37.90	Top of ledge, 20 ft. high, bears NE and SW.; desc. abruptly.
75.08	The cor. of secs. 1, 2, 11, and 12, monumented with an iron post, 2½ ins. diam., in mound of stone, 4 ft. base, 2 ft. high, with brass cap mkd. as described in the official record of the 1959 resurvey.
	From the cor. of secs. 1 and 12, on the E. bdy. of the Tp., monumented with an iron post, 2 ins. diam., extending 10 ins. above ground, and in a collar of stone, with brass cap mkd. as described in the official record of the 1937 resurvey. from which the remaining original bearing trees A juniper, 12 ins. diam., bears S. 36° W., 66 lks. dist., scribed T35S R4E S12 BT. A juniper, 12 ins. diam., bears N. 64° W., 45 lks. dist., scribed T35S R4E S1 BT. S. 86° 45' W., bet. secs. 1 and 12. Over broken land through scattered timber.
4.00	Power line, bears S. 46° W. and N. 46° E.
16.00	Ledgy draw, drains S. 30° W.; thence along broken general S slope.
42.00	Ledgy draw, 80 ft. deep, drains S; asc. over ledgy SE slope.
44.61	Point for the ¼ sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 16 ins. long, 1 in. diam., 8 ins. in drill hole in solid sandstone, with brass cap mkd.

☆ U.S. Government Printing Office-1978-778-206/433

CHAINS	
	T 35 S R 4 E ¼ S 1 / S 12 1978
	from which
	A pinon, 8 ins. diam., bears N. 10° E., 28 lks. dist., mkd. BT.
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.
	Continue ascent over SE slope.
47.00	Top of ascent, sandstone rim, bears N. 30° E. and curves S.; desc. abruptly about 300 ft. over broken and ledgy W slope.
53.00	State Highway No. 54, bears S. 17° W. and N. 17° E.
54.50	Calf Creek, 30 lks. wide, 12 ins. deep, flows S. 10° W.; asc. abruptly about 250 ft. over ledgy E slope.
70.00	Deep, narrow draw, drains S. 60° E.; asc. abruptly about 200 ft. over near vertical NE slope.
88.50	Head of ledgy draw, drains S; asc. over SE slope.
89.22	The cor. of secs. 1, 2, 11, and 12.
	Survey of the Subdivision of Section 12, T. 35 S., R. 4 E., Salt Lake Meridian, Utah
	From the ¼ sec. cor. of secs. 12 and 13.
	N. 3° 39' W., along the N and S center line of sec. 12.
	Over broken land; asc. abruptly along ledgy E slope.
18.11	Point for the center south 1/16 sec. cor. of sec. 12.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T 35 S R 4 E C S 1/16 | S 12 C 1978
	from which
	A cottonwood, 8 ins. diam., bears N. 17° E., 36 lks. dist., scribed CS 1/16 BT.

CHAINS	
23.50	Escalante River, 60 lks. wide, 16 ins. deep, flows S. 50° E.; asc. abruptly about 150 ft. over ledgy SW slope.
36.22	Point for the center ¼ sec. cor. of sec. 12, at intersection with E and W center line.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T 35 S R 4 E C¼ S 12 1978
	Continue along W slope of draw.
39.00	Draw, drains nearly S from NE; asc. over ledgy SE slope.
40.50	Power line, bears N. 46° E. and S. 46° W.
69.00	Deep gulch, drains W; asc. abruptly about 200 ft. over ledgy S slope.
76.63	The ¼ sec. cor. of secs. 1 and 12.
	From the ¼ sec. cor. of sec. 12, on the E. bdy. of the Tp., heretofore described.
	N. 89° 20' W., on the E and W center line of sec. 12.
	Over broken land through widely scattered timber.
9.00	Ledgy draw, 50 ft. deep, drains S. 45° W.; asc. over SE slope.
13.00	Ledgy point, bears S, thence along broken S slope.
20.80	Point for the center E 1/16 sec. cor. of sec. 12.
	Set an iron post, 28 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T 35 S R 4 E C —— E 1/16 —— C S 12 1978
29.00	Draw, drains S. 30° W.; asc. over SE slope.
36.00	Top of inaccessible sandstone knob, 1.00 ch. diam.; desc. abruptly over broken W slope.
41.60	The center ¼ sec. cor. of sec. 12.
	Continue on the E and W center line.
42.00	Draw, drains S; asc. over E slope.

Survey of the Subdivision of Section 12,
T. 35 S., R.4 E., Salt Lake Meridian, Utah

CHAINS	
46.00	Power line, bears N. 46° E. and S. 46° W.
55.50	Calf Creek, 30 lks. wide, 12 ins. deep, flows S. 18° W.; asc. abruptly over ledgy E slope.
57.00	State Highway No. 54, bears S. 16° W. and N. 16° E.
62.00	Sandstone knob, on spur, slopes S; desc. over W slope.
62.87	Point for the center W 1/16 sec. cor. of sec. 12.
	Set an iron post, 16 ins. long, 1 in. diam., 6 ins. in drill hole, in solid sandstone, with brass cap mkd. T 35 S R 4 E C W 1/16 C S 12 1978
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.
64.00	Draw, drains S; asc. over E slope.
84.14	The ¼ sec. cor. of secs. 11 and 12.
	From the E 1/16 sec. cor. of secs. 12 and 13.
	N. 0° 59' W., on the N and S center line of the SE¼ of sec. 12.
18.12	Point for the SE 1/16 sec. cor. of sec. 12, at intersection with the E and W center line of the SE¼ of sec. 12.
	Set an iron post, 28 ins. long, 2½ ins. diam., over a cross (X) on solid sandstone, and in a mound of stone, 4 ft. base to top of brass cap, mkd. T 35 S R 4 E SE 1/16 S 12 1978
25.00	Ledgy draw, drains S. 40° W.; asc. over SE slope.
36.24	The center E 1/16 sec. cor. of sec. 12.
	From the S 1/16 sec. cor. of sec. 12, on the E. bdy. of the Tp., heretofore described.
	N. 89° 14' W., on the E and W center line of the SE¼ of sec. 12.
19.95	The SE 1/16 sec. cor. of sec. 12.
23.00	Ledgy draw, drains S. 25° W.; asc. over SE slope.
33.50	Escalante River, 60 lks. wide, 18 ins. deep, flows S. 30° E. from N. 45° W.; thence over nearly level bottom land.

CHAINS	
39.90	The center S 1/16 sec. cor. of sec. 12.
	From the W 1/16 sec. cor. of secs. 12 and 13. N. 5° 20' W., on the N and S center line of the SW¼ of sec. 12. Over broken land.
2.50	State Highway No. 54, bears N. 65° W. to Escalante and S. 65° E. to Boulder.
18.43	True point for the SW 1/16 sec. cor. of sec. 12, at intersection with the E and W center line of the SW¼ of sec. 12, falls in Escalante River, 40 lks. wide, 20 ins. deep, flows E, and deemed unsafe to perpetuate.
18.68	Point selected for the witness cor. to the SW 1/16 sec. cor. of sec. 12. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. W C T 35 S R 4 E SW 1/16 ↓ S 12 1978 Asc. over gently rolling land.
23.04	Point for the C-S-N-SW 1/256 sec. cor. of sec. 12. Set an iron post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, in trail road, bears NE and SW, with brass cap mkd. S 12 C-S-N-SW 1/256 1978
36.86	The center W 1/16 sec. cor. of sec. 12.
	From the center S 1/16 sec. cor. of sec. 12. S. 89° 54' W., on the E and W center line of the SW¼ of sec. 12.
7.00	State Highway No. 54, on slight curve, bears N. 60° W. to Boulder and S. 55° E. to Escalante.
19.50	Escalante River, 50 lks. wide, 18 ins. deep, flows N. 45° E. from W.; thence along river.
20.70	True point for the SW 1/16 sec. cor. of sec. 12.

Survey of the Subdivision of Section 12,
T. 35 S., R.4 E., Salt Lake Meridian, Utah

CHAINS	
24.50	Power line, bears N. 46° E. and S. 46° W., leave Escalante River, flows E from N. 80° W.
31.05	Point for the C-W-SW 1/64 sec. cor. of sec. 12.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	S 12 C-W-SW 1/64 1978
39.40	Escalante River, 70 lks. wide, 12 ins. deep, flows N. 30° E.
41.40	The S 1/16 sec. cor. of secs. 11 and 12.
	From the C-W-SW 1/64 sec. cor. of sec. 12.
	N. 6° 09' W., on the N and S center line of the NW¼SW¼ sec. 12.
2.00	Escalante River, 50 lks. wide, 20 ins. deep, flows S. 60° E. from W.; asc. abruptly about 50 ft. over sandstone ledges.
3.50	Top of ledges, bears S. 60° E. and curves W.
4.65	Point for the C-S-NW-SW 1/256 sec. cor. of sec. 12.
	Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top of brass cap, mkd.
	S 12 C-S-NW-SW 1/256 1978
	From the C-S-N-SW 1/256 sec. cor. of sec. 12.
	N. 89° 55' W., on the E and W center line of the SE¼NW¼SW¼ sec. 12.
10.42	The C-S-NW-SW 1/256 sec. cor. of sec. 12.
	Survey of the Subdivision, Section 13, T. 35 S., R. 4 E., Salt Lake Meridian, Utah
	From the ¼ sec. cor. of sec. 12 and 13.
	S. 1° 03' 30" E., on a calculated bearing, on the N and S center line of sec. 13.
	Along sandstone ledges facing E.

Survey of the Subdivision of Section 13,
T. 35 S., R.4 E., Salt Lake Meridian, Utah

CHAINS	
13.00	Draw, drains NE; asc. broken NW slope.
20.34	True point for the center N 1/16 sec. cor. of sec. 13, falls on near vertical ledges about 150 ft. high, and cannot be perpetuated.
	From this point, the witness cor. for the center N 1/16 sec. cor. of sec. 13, bears S. 89° 30' E., 0.80 chs. dist., hereinafter described.
22.00	Top of ledges, curves NE and NW; desc. over broken exposed sandstone.
27.00	Solid sandstone draw, drains NE; asc. over NW slope.
40.68	Point for the C¼ sec. cor. of sec. 13, at the intersection with the E and W center line of sec. 13.
	Set an iron post, 16 ins. long, 1 in. diam., 6 ins. in drill hole, on solid sandstone, with brass cap mkd.
	T 35 S R 4 E
	C¼ S 13
	1978
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.
	From the ¼ sec. cor. of sec. 13, on the E. bdy. of the Tp., heretofore described.
	N. 89° 56' W., on the E and W center line of sec. 13.
	Asc. over E slope.
8.00	Draw, drains S; asc. over sandstone SE slope.
38.50	Small draw, drains S; asc. over SE slope.
38.90	The C¼ sec. cor. of sec. 13.
79.91	The ¼ sec. cor. of secs. 13 and 14.
	From the N 1/16 sec. cor. of sec. 13, on the E. bdy. of the Tp., heretofore described.
	N. 89° 30' W., on the E and W center line of the NE¼ of sec. 13.
	Asc. abruptly over broken and ledgy NE slope.
33.00	Draw, drains N. 40° E.; asc. abruptly over ledgy SE slope.
37.74	Point selected for the witness cor. to the center N 1/16 sec. cor. of sec. 13, on rim, about 150 ft. high, bears NE and curves W.

Survey of the Subdivision of Section 13,
T. 35 S., R.4 E., Salt Lake Meridian, Utah

CHAINS	
	Set an iron post, 16 ins. long, 1 in. diam., 8 ins. in drill hole in solid sandstone, with brass cap mkd. W C T 35 S R 4 E ← C N 1/16 S 13 C 1978
	Desc. abruptly over sandstone ledges on NW slope.
38.54	True point for the center N 1/16 sec. cor. of sec. 13.

General Description

That portion of T. 35 S., R. 4 E., covered in this survey is located approximately 15 miles east of Escalante, Utah. The area is mostly exposed sandstone ledges along the breaks of the Escalante River, which enters section 12 in the southwest quarter and flows easterly for a half mile thence southeasterly leaving the township in the northeast quarter of section 13.

Timber consists of scattered pinon and juniper, with cottonwood and tamarack along the Escalante River, and also along Calf Creek, which enters section 12 in the northwest quarter and flows southerly into the Escalante River in the northeast quarter of the southwest quarter of section 12.

Soil is shallow sand with considerably exposed sandstone on the breaks and sandy loam along the Escalante River bottom.

The elevation varies from 5,200 ft. above sea level along the river to 5,800 ft. in the north corner of section 12.

There is a partially constructed house in the S½SE¼NW¼SW¼ of section 12, and a cabin and corrals in the SW¼SE¼ section 12 and the NW¼NE¼ section 13.

The area is drained in a southerly direction by Calf Creek, which drains into the Escalante River, thence drains in an easterly direction by the river.

Access to the area is by Utah State highway No. 54, which enters section 12 from Boulder, along Calf Creek, and leaves the area to Escalante, Utah, near the corner of sections 11, 12, 13, and 14.

Form 9600–11
(August 1979)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Lanny Talbot	Engineering Technician
Kevin Hinckley	Surveying Technician
Russell Brown	Survey Aid

CERTIFICATE OF SURVEY

(I) (~~We~~) Glen B. Hatch, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 31st day of October, 19 78, (I) (~~We~~) have dependently resurveyed a portion of the E. Bdy. (First Guide Meridian East), a portion of the subdivisional lines and surveyed a portion of the subdivision of sections 12 and 13, Township 35 South, Range 4 East,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), (~~us~~) and under (my) (~~our~~) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

January 5, 1979
(Date)

Glen B Hatch
(Cadastral Surveyor)
Supervisory

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the E. Bdy. (First Guide Meridian East), a portion of the subdivisional lines and the survey of a portion of the subdivision of sections 12 and 13, T. 35 S., R. 4 E., Salt Lake Meridian, Utah

executed by Glen B. Hatch, Supervisory Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

NOV 18 1980
(Date)

Allen E Arnold
ACTING (Chief, Cadastral Survey Examination and Approval Staff)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief, Cadastral Survey Examination and Approval Staff)~~

Form 9180–6
(March 1977)

R601

86

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF THE

SOUTH BOUNDARY OF TOWNSHIP 15 SOUTH, RANGE 7 EAST,

(THIRD STANDARD PARALLEL SOUTH),

THE WEST BOUNDARY OF

TOWNSHIP 16 SOUTH, RANGE 8 EAST,

THE EAST BOUNDARY OF

TOWNSHIP 16 SOUTH, RANGE 6 EAST,

A PORTION OF THE SOUTH BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES

AND

THE SUBDIVISION OF 14 SECTIONS OF

TOWNSHIP 16 SOUTH, RANGE 7 EAST

Of the Salt Lake Meridian,

In the State of Utah.

EXECUTED BY

Jerry L. Thomas Supervisory Cadastral Surveyor

Under special instructions dated April 6, 19 76, approved April 8, 1976,

, which provided for the surveys included under U.S. Survey/Group

Number 565, and assignment instructions dated June 21, 19 76.

Survey commenced July 6, 19 76

Survey completed September 26, 19 78

INDEX DIAGRAM

Township 16 S., Range 7 E.,

	7	6	5	4	3	2
21	67 **6** 65	67 **5** 65	54 **4** 53	46 **3** 45	38 **2** 37	32 **1** 31 14
20	66 **7** 63	64 **8** 62	52 **9** 52	44 **10** 44	36 **11** 36	30 **12** 29 13
19	64 **18** 61	62 **17** 60	51 **16** 50	42 **15** 41	35 **14** 34	28 **13** 28 12
18	61 **19** 58	59 **20** 58	49 **21** 49	40 **22** 40 39	33 **23** 33	27 **24** 26 11
16	59 **30** 56	57 **29** 55	48 **28** 48	**27**	**26** 33	25 **25** 24 10
15	57 **31** 23	54 **32**	46 **33** 23	39 **34** 22	**35**	23 **36** 9

Subdivision of Sec. 5 Page 68
Subdivision of Sec. 8 Page 69
Subdivision of Sec. 9 Page 69
Subdivision of Sec. 14 Page 72
Subdivision of Sec. 15 Page 73
Subdivision of Sec. 16 Page 75
Subdivision of Sec. 17 Page 77
Subdivision of Sec. 21 Page 78
Subdivision of Sec. 22 Page 79
Subdivision of Sec. 24 Page 83
Subdivision of Sec. 27 Page 84
Subdivision of Sec. 28 Page 85
Subdivision of Sec. 34 Page 86

GPO 840-243

Township 16 South, Range 7 East, Salt Lake Meridian, Utah

CHAINS

The following field notes describe the dependent resurvey of the south boundary of T. 15 S., R. 7 E., (Third Standard Parallel South), the west boundary of T. 16 S., R. 8 E., the east boundary of T. 16 S., R. 6 E., a portion of the south boundary, a portion of the subdivisional lines and the subdivision of 14 sections of T. 16 S., R. 7 E., Salt Lake Meridian, Utah.

The south boundary of sec. 36, along the Third Standard Parallel South through Range 6 East was retraced during the resurvey of the Third Standard Parallel South through Range 7 East.

The Third Standard Parallel South on the south boundary of T. 15 S., R. 7 E., was surveyed by A.D. Ferron in 1873. The Third Standard Parallel South on the south boundary of T. 15 S., R. 7 E., was resurveyed, the east boundary of T. 16 S., R. 6 E., and the east and south boundaries and subdivisional lines of T. 16 S., R. 7 E., were surveyed by J.C. Dick in 1900. NOTE: In the 1900 survey J.C. Dick made the section corners along the north boundary of T. 16 S., R. 7 E., common with the standard corners along the Third Standard Parallel South. The south boundary of section 35 was resurveyed by E. Bird in 1946. A portion of the subdivisional lines were resurveyed by B. Owens in 1961. The ¼ sec. cor. of secs. 36, on the east boundary of T. 16 S., R. 6 E., and the closing cor. of Tps. 16 and 17 S., R. 7 E., were remonumented by A. Nelson in 1965 under the remonumentation cooperative agreement bet. the B.L.M. and the U.S.F.S. The south boundary, excluding the south boundary of section 35, was resurveyed by J.L. Thomas in 1968 - 69.

The resurvey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 565, Utah, dated April 6, 1976.

The directions of the lines of this survey were determined by altitude observations on the sun and Polaris. The lines were carried forward by sustained angulation being supplemented by other altitude observations on the sun and Polaris taken throughout the progress of the survey. The measurements were made by electronic telementry and the verticle angles of these measurements made on the slope were ascertained by a theodolite in good adjustment. The horizontal equivalents only are entered in the field notes.

The geographic position of the southeast corner of the township as determined by a tie to the United States Coast and Geodetic Survey triangulation station "EAST" is as follows:

Latitude 39° 22' 52" N. Longitude 111° 04' 36" W.

The mean magnetic declination is 16° E.

Dependent Resurvey of the South Boundary of
T. 15 S., R. 7 E., (Third Standard Parallel South),
Salt Lake Meridian, Utah

Dependent Resurvey of the South Boundary of
T. 15 S., R. 7 E., (Third Standard Parallel South),
Salt Lake Meridian, Utah

CHAINS	
	(Restoring the Survey Executed by A.D. Ferron in 1873 and the Dependent Resurvey Executed by J.C. Dick in 1900
	Beginning at the closing stan. cor. of Tps. 15 and 16 S., R. 7 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 18 ins. above ground and surrounded by a collar of stone, with brass cap mkd. as described in the official record of the 1947 resurvey of a portion of the Third Standard Parallel South, R. 8 E., from which the original bearing trees
	An aspen, 18 ins. diam., bears S. 26°15' W., 22 lks. dist., mkd. T16S R7E S1 BT.
	An aspen, 10 ins. diam., bears N. 20°30' W., 32 lks. dist., mkd. T15S R7E S36 BT.
	From the above closing cor., the ¼ sec. cor. of secs. 1 and 6 bears S. 0°07' E., 37.30 chs. dist., hereinafter described.
	From the same closing cor., the stan. Tp. cor. of Tps. 15 and 16 S., R. 8 E., bears N. 0°07' W., 12.61 chs. dist., hereinafter described.
	S. 89°56' W., on the S. bdy. of sec. 36.
	Over gentle rolling top of Gentry Mountain, through grassy clearing.
24.60	Dirt road, bears N. 14° E. and S. 14° W.
39.96	The stan. ¼ sec. cor. of sec. 36, common with the ¼ sec. cor. of sec. 1, T. 16 S., R. 7 E., monumented with the original cor. tree, an aspen, 14 ins. diam., mkd. ¼ on N face and ¼ S on S face.
	from which
	An aspen, (an original bearing tree) 10 ins. diam., bears S. 10° E., 27½ lks. dist., mkd. ¼ S1 BT. (Record, N. 10° W., S36).
	A spruce, (a new bearing tree) 7 ins. diam., bears N. 6° W., 31½ lks. dist., mkd. SC ¼ S36 BT.
	An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 89°56' E., 4 lks. dist., with brass cap mkd. SC T15S R7E ¼ S36 S1 T16S R7E RM 1976 and an arrow pointing to the corner.
	S. 89°58' W., beginning new measurement.
	Desc. over W slope, through thick aspen and pine timber.
39.55	The stan. cor. of secs. 35 and 36, common with the cor. of secs. 1 and 2, T. 16 S., R. 7 E., monumented with a sandstone, 14 x 8 x 5 ins., firmly set projecting 8 ins. above ground, and mkd. 5 notches on W and 1 notch on E edge, from which the remains of the original bearing trees

CHAINS

A pine, 24 ins. diam., bears N. 72½° E., 31½ lks. dist., with a healed blaze.

A downed pine, 18 ins. diam., bears S. 7½° W., 28 lks. dist., badly rotted.

A pine, 18 ins. diam., bears N. 31° W., 15½ lks. dist., with a healed blaze. (Record, N. 28½° W., 14 lks. dist.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.

SC
T 15 S R 7 E

S 35	S 36
S 2	S 1

T 16 S R 7 E
1976

from which new bearing trees

A pine, 36 ins. diam., bears S. 37° E., 34 lks. dist., mkd. T16S R7E S1 BT.

A pine, 30 ins. diam., bears S. 60¼° W., 21½ lks. dist., mkd. T16S R7E S2 BT.

Deposit the mkd. stone alongside the iron post.

S. 89°55' W., on the S. bdy. of sec. 35.

Desc. along N slope through thick pine timber.

39.64 The stan. ¼ sec. cor. of sec. 35, common with the ¼ sec. cor. of sec. 2, T. 16 S., R. 7 E., monumented with a sandstone boulder in place, 5 x 3 x 2 ft., above ground, mkd. with a cross (X) ¼ SC.

from which

A rotted pine stump, (an original bearing tree), 36 ins., diam., bears S. 42° E., 13 lks. dist., no visible scribe markings.

A rotted pine stump, (an original bearing tree), 14 ins., diam., bears North, 27 lks. dist., no visible scribe markings.

An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears North, 1 lk. dist., with brass cap mkd. SC T15S R7E ¼ S35 S2 T16S RM 1976 and an arrow pointing to the cor.

A pine, (a new bearing tree) 12 ins. diam., bears N. 83° E., 32½ lks. dist., mkd. SC ¼ S35 BT.

CHAINS	
	A pine, (a new bearing tree), 10 ins. diam., bears S. 72° W., 73 lks. dist., mkd. ¼ S2 BT.
	S. 89° 37' W., beginning new measurement.
	Over rough and broken mountainous land, through thick pine timber; desc. over steep NW slope.
38.93	The stan. cor. of secs. 34 and 35, common with the cor. of secs. 2 and 3, T. 16 S., R. 7 E., monumented with a sandstone, 16 x 7 x 7 ins., with illegible markings, set in a mound of stone, from which the original bearing trees
	A mahogany, 8 ins. diam., bears N. 86½° E., 28 lks. dist., mkd. BT. (Record, 34 lks.)
	A mahogany, 9 ins. diam., bears S. 26½° E., 40 lks. dist., mkd. T16S E B. (Record, S. 32½° E.)
	A mahogany, 14 ins. diam., bears S. 14° W., 81½ lks. dist., mkd. T16S R7E S3 BT. (Record, S. 12½° W., 78 lks. dist.)
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.
	S C T 15 S R 7 E S 34 | S 35 S 3 | S 2 T 16 S 1976
	Deposit the mkd. stone alongside and set a red aluminum post, 6 ft. long, with an attention sign on top, alongside the iron post.
	S. 89° 55' W., on the S. bdy. of sec. 34.
	Over rough and broken mountainous terrain, through thick mahogany, oak brush and pine timber; desc. over steep SW slope.
29.50	Small creek, 10 lks. wide, 2 ins. deep, flows SW; bottom of Tie Fork Canyon.
31.75	Trail road, bears NE and SW; asc. over SE slope.
39.74	Point for the stan. ¼ sec. cor. of sec. 34, common with the ¼ sec. cor. of sec. 3, T. 16 S., R. 7 E., at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

CHAINS	
	S C T 15 S R 7 E ¼ S 34 / S 3 T 16 S 1976
	Cor. is set on steep SW slope, 150 lks. E of spring branch, flowing S.
	Desc. over SW slope.
41.50	Bottom of deep draw, drains S; asc. over SE slope.
79.48	Point for the stan. cor. of secs. 33 and 34, common with the cor. of secs. 3 and 4, T. 16 S., R. 7 E., at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd. S C T 15 S R 7 E S 33 | S 34 / S 4 | S 3 T 16 S 1976
	S. 89°55' W., on the S. bdy. of sec. 33. Over rough and broken mountainous land, through scattered oak brush and pine timber; asc. over steep SE slope.
39.74	Point for the stan. ¼ sec. cor. of sec. 33, common with the ¼ sec. cor. of sec. 4, T. 16 S., R. 7 E., at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd. S C T 15 S R 7 E ¼ S 33 / S 4 T 16 S 1976 from which A pine, 9 ins. diam., bears N. 83° E., 8 lks. dist., mkd. SC T15S R7E ¼ S33 BT. A pine, 8 ins. diam., bears S. 71° E., 23½ lks. dist., mkd. T16S R7E ¼ S4 BT.

CHAINS	
	Continue ascent along steep S slope.
77.96	Point for the original witness cor. to the stan. cor. of secs. 32 and 33, at record distance, falls on E edge of paved road; there is no remaining evidence of the original witness corner.
78.18	Center line of Highway No. 31, bears S. 41° E. and N. 41° W.
79.00	Huntington Creek, 40 lks. wide, flows SE.
79.48	Point for the stan. cor. of secs. 32 and 33, common with the cor. of secs. 4 and 5, T. 16 S., R. 7 E., at proportionate distnce; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. S C T 15 S R 7 E S 32 | S 33 S 5 | S 4 T 16 S 1976 from which A pine, 20 ins. diam., bears S. 4° E., 32 lks. dist., mkd. T16S R7E BT. A pine, 24 ins. diam., bears N. 23° W., 4 lks. dist., mkd. SC T15S R7E S32 BT.
	S. 89°55' W., on the S. bdy. of sec. 32. Over rough and broken mountainous land; along bottom of Huntington Canyon.
0.50	Base of steep ascent, bears NW and SE; asc. over steep NE slope.
39.74	Point for the stan. ¼ sec. cor. of sec. 32, common with the ¼ sec. cor. of sec. 5, T. 16 S., R. 7 E., at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a collar of stone, with brass cap mkd. S C T 15 S R 7 E ¼ S 32 / S 5 T 16 S 1976

CHAINS	
	Set a red aluminum post, 6 ft. long, with an attention sign on top, alongside the iron post.
	Continue ascent over steep E slope, through scattered aspen timber.
79.48	The stan. sec. cor. of secs. 31 and 32, common with the cor. of secs. 5 and 6, T. 16 S., R. 7 E., monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. S C T 15 S R 7 E S 31 | S 32 S 6 | S 5 T 16 S R 7 E 1946 from which A pine, 14 ins. diam., bears S. 56°18' E., 361 lks. dist., mkd. SC T16S R7E S5 BT. There is no official record of this corner setting, but it is harmoniously related to existing original cors., and is accepted as a careful and faithful perpetuation of the position of the original corner.
	S. 89° 54' W., on the S. bdy. of sec. 31. Over mountainous land, through scattered aspen and pine timber; along gentle S slope.
40.00	Top of spur, slopes S; thence along steep S slope.
40.28	Point for the stan. ¼ sec. cor. of sec. 31, common with the ¼ sec. cor. of sec. 6, T. 16 S., R. 7 E., at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. S C T 15 S R 7 E ¼ S 31 / S 6 T 16 S 1978 Cor. is located on steep rocky S slope. Desc. over SW slope.
51.96	Point for the closing Tp. cor. of Tps. 16 S., Rs. 6 and 7 E., hereinafter described.

95

Dependent Resurvey of the South Boundary of
T. 15 S., R. 7 E., (Third Standard Parallel South),
Salt Lake Meridian, Utah

CHAINS	
84.07	Point for the original stan. Tp. cor. of Tps. 15 S., Rs. 6 and 7 E., at proportionate distance; there is no remaining evidence of the original corner. This now becomes an angle point. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. AP T 15 S R 7 E S 31 1978 From this point the original stan. cor. of secs. 35 and 36, T. 15 S., R. 6 E., bears S. 89° 54' W., 80.56 chs. dist., monumented with a rough-surfaced sandstone ledge, 8 ft. high, mkd. with an X chiseled on S face, with 1 notch to the E and 5 notches to the W. There is no remaining evidence of the original bearing trees. This now becomes an angle point. from which An iron post, 28 ins. long, 2½ ins. diam., set 14 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, for a reference monument, bears N. 89°54' E., 0.16 chs. dist., with brass cap mkd. RM AP T15S R6E S36 1978 and an arrow pointing to the cor. U.S.C. and G.S. triangulation station "EAST" bears N. 38° 20' W., 57.50 chs. dist., monumented with a standard brass tablet set in concrete mkd. EAST 1937.
	Point for the original stan. ¼ sec. cor. of sec. 36, T. 15 S., R. 6 E., at midpoint bet. angle points and on the S. bdy. of sec. 36. There is no remaining evidence of the original cor. This now becomes an angle point. Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base, to top of brass cap, mkd. AP T 15 S R 6 E S 36 1978
	Dependent Resurvey of the West Boundary, T. 16 S., R. 8 E., Salt Lake Meridian, Utah
	(Restoring the Survey Executed by James C. Dick in 1900)

Dependent Resurvey of the West Boundary,
T. 16 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS	
	From the cor. of Tps. 16 and 17 S., Rgs. 7 and 8 E., monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above mound of stone, 3½ ft. diam., with brass cap mkd. as described in the official record of the 1968 - 69 resurvey of the N. bdy. of T. 17 S., R. 7 E.
	N. 0°10' W., bet. secs. 31 and 36.
	Over slightly broken bottom of Huntington Canyon, through scattered juniper timber; desc. over rocky NE slope.
17.00	Huntington Creek, 12 ins. deep, 40 lks. wide, flows E; asc. over SW slope.
23.50	Center line of State Highway No. 31, bears NW and SE; asc. over broken S slope, through juniper and pinon timber.
39.78	The ¼ sec. cor. of secs. 31 and 36, monumented with a sandstone 18 x 8 x 6 ins., firmly set projecting 10 ins. above ground and mkd. ¼ on W face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 16 S R 7 E R 8 E ¼ S 36 | S 31 1976
	Deposit the mkd. stone and set a steel fence post, 6 ft. long, alongside the iron post.
	N. 0°03' E., beginning new measurement.
39.82	The cor. of secs. 25, 30, 31, and 36, monumented with a sandstone 16 x 10 x 4 ins., firmly set projecting 8 ins. above ground and mkd. 5 notches on N and 1 notch on S edges.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.
	T 16 S R 7 E R 8 E S 25 | S 30 S 36 | S 31 1976

CHAINS

from which

A sandstone boulder, 10 x 6 x 5 ft. above ground, bears West, 4½ lks. dist., mkd. X BO on E face.

Deposit the mkd. stone alongside the iron post.

N. 0°15' W., bet. secs. 25 and 30.

Over broken mountainous land; asc. over steep rocky S slope.

40.25 The ¼ sec. cor. of secs. 25 and 30, monumented with a sandstone, 14 x 12 x 4 ins., firmly set, projecting 6 ins. above ground, mkd. ¼ on W face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 16 S
R 7 E R 8 E

¼
|
S 25 | S 30
|

1976

Deposit the mkd. stone alongside the iron post.

Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.

N. 0°11' E., beginning new measurement.

Desc. over steep rocky NW slope.

39.82 The cor. of secs. 19, 24, 25, and 30, monumented with a sandstone, 16 x 12 x 6 ins., firmly set, projecting 6 ins. above ground, mkd. 2 notches on S and 4 notches on N edges, from which the original bearing trees

A pine, 14 ins. diam., bears N. 50° E., 58 lks. dist., mkd. with a healed blaze. (Record, N. 51° E.)

A pine, 20 ins. diam., bears S. 89° E., 26 lks. dist., mkd. with a healed blaze.

A pine, 14 ins. diam., bears S. 48° W., 55 lks. dist., mkd. with a healed blaze. (Record, S. 50° W., 57 lks. dist.)

A pine, 16 ins. diam., bears N. 40° W., 59 lks. dist., mkd. T16S R7E S24 BT. (Record, 61 lks.)

CHAINS	
	At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd. T 16 S R 7 E R 8 E S 24 | S 19 S 25 | S 30 1976 Deposit the mkd. stone alongside the iron post.
	N. 0°03' E., bet. secs. 19 and 24. Over rough mountainous land, through thick pine timber; desc. over steep NW slope.
39.75	Point for the ¼ sec. cor. of secs. 19 and 24, at proportionate distance; there is no remaining evidence of the the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 16 S R 7 E R 8 E ¼ S 24 | S 19 1976 Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor. Asc. over SW slope.
71.50	Trail road, bears NW and E.
79.50	The cor. of secs. 13, 18, 19, and 24, monumented with a sandstone, 16 x 10 x 8 ins., firmly set, projecting 6 ins. above ground, mkd. 3 notches on N and S edges. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd. T 16 S R 7 E R 8 E S 13 | S 18 S 24 | S 19 1976

CHAINS	
	Deposit the mkd. stone alongside the iron post.
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.
	N. 0°04' E., bet. secs. 13 and 18.
	Over mountainous land; over nearly level top of plateau.
1.50	Trail road, bears NE and SW.
31.50	Trail road, bears W and SE; desc. over gradual NE slope.
39.88	The ¼ sec. cor. of secs. 13 and 18, monumented with a sandstone, 16 x 8 x 6 ins., firmly set, projecting 6 ins. above ground, mkd. ¼ on W face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 16 S R 7 E R 8 E ¼ S 13 | S 18 1976
	Deposit the mkd. stone alongside the iron post.
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.
	Cor. is located in sagebrush clearing, 0.11 chs. E of fence line, bearing N and S.
	N. 0°09' W., beginning new measurement.
	Desc. over gradual NE slope.
38.90	Trail road, bears NE and SW.
39.89	The cor. of secs. 7, 12, 13, and 18, monumented with a sandstone, 12 x 8 x 4 ins., in a scattered mound of stone, with no legible markings, from which the remains of the original bearing trees
	A rotted aspen stump, bears S. 1° E., 157 lks. dist., no legible markings.
	A rotted aspen stump, bears S. 78° W., 135 lks. dist., no legible markings.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of the West Boundary,
T. 16 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS	
	T 16 S R 7 E R 8 E S 12 | S 7 S 13 | S 18 1976 Deposit the unmkd. stone alongside the iron post. Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.
	N. 0°01' E., bet. secs. 7 and 12. Over rolling top of "Gentry Mountain"; along gentle E slope.
39.96	The ¼ sec. cor. of secs. 7 and 12, monumented with a limestone, 16 x 12 x 6 ins., firmly set, projecting 6 ins. above ground, mkd. ¼ on W face, from which the remains of the original bearing trees A fallen aspen with stump in place, bears S. 64° E., 153 lks. dist., with no legible markings. A fallen aspen with stump in place, bears N. 27° W., 213 lks. dist., with no legible markings. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd. T 16 S R 7 E R 8 E ¼ S 12 | S 7 1976 Deposit the mkd. stone alongside the iron post. Cor. is located 6½ lks. E of fence line, bearing N and S.
	N. 0°07' W., beginning new measurement. Asc. over gradual SE slope, through small aspen timber.
39.96	The cor. of secs. 1, 6, 7, and 12, monumented with a sandstone 12 x 10 x 3 ins., firmly set, projecting 4 ins. above ground, mkd. 5 notches on S and 1 notch on N edges, from which the remains of an original bearing tree A stump hole, bears S. 20° E., 148 lks. dist. At the corner point

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 16 S R 7 E R 8 E S 1 | S 6 S 12 | S 7 1976 Deposit the mkd. stone alongside the iron post. Cor. is located in bottom of grassy drainage, draining SE and 22½ lks. W of fence line, bearing N and S.
	N. 0°07' W., bet. secs. 1 and 6. Over rolling mountain top, through scattered aspen timber; along gentle E slope.
25.00	Dirt road, bears E and W.
39.88	Point for the ¼ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 16 S R 7 E R 8 E ¼ | S 1 | S 6 | 1976 Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor. Cor. is located 7 lks. W of fence line, bearing N and S.
77.18	The closing stan. cor. of Tps. 15 and 16 S., R. 7 E., hereinbefore described. Asc. over S slope, through thick aspen and pine timber.
89.79	The stan. Tp. cor. of Tps. 15 and 16 S., R. 8 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 18 ins. above ground and surrounded by a collar of stone, with brass cap mkd. as described in the official record of the 1947 resurvey of a portion of the Third Standard Parallel South, R. 8 E.

CHAINS

Dependent Resurvey of the East Boundary,
T. 16 S., R. 6 E., Salt Lake Meridian, Utah

From the cor. of Tps. 16 and 17 S., R. 6 E., monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. as described in the official record of the 1965 remonumentation.

N. 1°18' W., on the E. bdy. of sec. 36.

Over rolling mountainous land, through sagebrush and grass; desc. over NE slope.

4.42 Point for the closing cor. of secs. 6 and 31, Tps. 16 and 17 S., R. 7 E., hereinafter described.

40.05 The original ¼ sec. cor. of sec. 36, monumented with an iron post, 2½ ins., diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. as described in the official record of the 1965 remonumentation. This now becomes an angle point. Add marks for angle point of secs. 31 and 36; the cap now mkd.

A P
T 16 S
R 6 E R 7 E

S 36 | S 31

1965
1978

N. 1°25' E., beginning new measurement.

Desc. over gentle N slope through small grassy clearing.

4.23 Point for the ¼ sec. cor. of sec. 31 only, T. 16 S., R. 7 E., hereinafter described.

37.21 The closing cor. of secs. 25 and 36, monumented with a sandstone, 14 x 14 x 6 ins., firmly set, projecting 6 ins. above ground, mkd. 5 notches on N and 1 notch on S edges, from which the original bearing trees

A pine, 6 ins. diam., bears N. 62° E., 5 lks. dist., mkd. T16S R7E S31 BT.

A pine, 10 ins. diam., bears S. 53° W., 24 lks. dist., mkd. T16S R6E S36 BT.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

CHAINS

T 16 S
R 6 E R 7 E

C S 25 |
C S 36 | S 31

1978

Deposit the mkd. stone alongside the iron post.

Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.

Thence along the E. bdy. of sec. 25.

39.66 The original cor. of secs. 25, 30, 31, and 36, monumented with a small mound of stone, from which the original bearing trees

A pine, 10 ins. diam., bears S. 89° E., 68 lks. dist., dimly mkd.

A dead pine, 14 ins. diam., bears N. 88° W., 53 lks. dist., faintly scribed S25.

This now becomes an angle point.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

AP
T 16 S
R 6 E R 7 E

|
S 25 | S 31
|

1978

Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.

N. 0°21' E., on the E. bdy. of sec. 25.

Over rough broken mountainous land; desc. over steep N slope through thick pine timber.

4.42 Point for the closing cor. of secs. 30 and 31, T. 16 S., R. 7 E., hereinafter described.

39.65 The original ¼ sec. cor. of secs. 25 and 30, monumented with a sandstone 16 x 8 x 4 ins., firmly set, projecting 6 ins. above ground, mkd. ¼ on W face. This now becomes an angle point.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of the East Boundary,
T. 16 S., R. 6 E., Salt Lake Meridian, Utah

CHAINS	
	AP T 16 S R 6 E R 7 E | S 25 | S 30 | 1978
	from which
	A spruce, 9 ins. diam., bears S. 28°40' W., 25 lks. dist., mkd. AP S25 BT.
	Deposit the mkd. stone alongside the iron post.
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.
	———————
	N. 0°10' E., beginning new measurement.
4.37	Point for the ¼ sec. cor. of sec. 30 only, T. 16 S., R. 7 E., hereinafter described.
37.06	The closing cor. of secs. 24 and 25, monumented with a sandstone 16 x 8 x 4 ins., firmly set, projecting 8 ins. above ground, mkd. 4 notches on N and 2 notches on S edges.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base, to top of brass cap, mkd.
	T 16 S R 6 E R 7 E C S 24 | C S 25 | S 30 1978
	Deposit the mkd. stone alongside the iron post.
	Thence along the E. bdy. of sec. 24.
39.52	The original cor. of secs. 19, 24, 25, and 30, monumented with a sandstone 18 x 10 x 6 ins., set in a mound of stone, mkd. 4 notches on N and 2 notches on S edges. This now becomes an angle point.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.

CHAINS	
	AP T 16 S R 6 E R 7 E S 24 | S 30 1978 from which A pine, 8 ins. diam., bears S. 32°40' W., 11 lks. dist., mkd. AP S24 BT. Deposit the mkd. stone alongside the iron post. Angle point is located near edge of sandstone ledge, 75 ft. high, bears NE and W.
	N. 0°25' E., on the E. bdy. of sec. 24. Over broken mountainous land, through thick aspen and pine timber; asc. over ledgy N slope.
4.45	Point for the closing cor. of secs. 19 and 30, T. 16 S., R. 7 E., hereinafter described. Desc. over NE slope.
11.50	Bottom of "Rilda Canyon", drains S. 75° E., asc. over steep S slope.
40.01	Point for the original ¼ sec. cor. of secs. 19 and 24, at proportionate distance; there is no remaining evidence of the original corner. This now becomes an angle point. Set an iron post, 28 ins. long, 2½ ins. daim., 12 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base, to top of brass cap, mkd. AP T 16 S R 6 E R 7 E S 24 | S 19 1978 Asc. over S slope through scattered pine timber.
44.475	Point for the ¼ sec. cor. of sec. 19 only, T. 16 S., R. 7 E., hereinafter described.
44.50	Top of spur, projects E; desc. over N slope through thick pine timber.
80.02	Point for the original cor. of secs. 13, 18, 19, and 24, at proportionate distance; there is no remaining evidence of the original corner. This now becomes an angle point.

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. AP T 16 S R 6 E R 7 E S 13 | S 19 1978 Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.
	N. 0°25' E., on the E. bdy. of sec. 13. Over broken mountainous land, through thick pine and aspen timber; asc. along steep E slope.
4.48	Point for the closing cor. of secs. 18 and 19, T. 16 S., R. 7 E., hereinafter described.
6.00	Top of spur, slopes NE; desc. over steep N slope.
40.01	Point for the original ¼ sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original corner. This now becomes an angle point. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd. AP T 16 S R 6 E R 7 E S 13 | S 18 1978 Asc. over S slope.
44.495	Point for the ¼ sec. cor. of sec. 18 only, T. 16 S., R. 7 E., hereinafter described.
71.50	Bottom of "Mill Fork Canyon", drains E; asc. over SE slope through scattered aspen timber.
80.02	Point for the original cor. of secs. 7, 12, 13, and 18, at proportionate distance; there is no remaining evidence of the original corner. This now becomes an angle point. Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base, to top of brass cap, mkd.

107

Dependent Resurvey of the East Boundary,
T. 16 S., R. 6 E., Salt Lake Meridian, Utah

CHAINS	
	AP T 16 S R 6 E R 7 E S 12 | S 18 1978 Set a red aluminum post 6 ft long, with attention sign on top, alongside the iron post.
	N. 0°25' E., on the E. bdy. of sec. 12. Over rough mountainous land, through thick aspen timber; asc. over SE slope.
4.49	Point for the closing cor. of secs. 7 and 18, T. 16 S., R. 7 E., hereinafter described. Asc. over steep ledgy S slope.
40.01	Point for the original ¼ sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner. This now becomes an angle point. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. AP T 16 S R 6 E R 7 E S 12 | S 7 1978 Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post. Asc. along E slope through scattered aspen timber.
44.655	Point for the ¼ sec. cor. of sec. 7 only, T. 16 S., R. 7 E., hereinafter described. Asc. over SE slope through grassy clearing.
79.94	Point selected for the witness cor. to the angle point for secs. 1 and 7. Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd.

CHAINS	
	WC AP T 16 S R 6 E R 7 E ↑ S 1 | S 7 | 1978
	Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.
80.02	True point for the original cor. of secs. 1, 6, 7, and 12, at proportionate distance, falls on edge of small sandstone ledge and cannot be monumented; there is no remaining evidence of the original corner. This now becomes an angle point.
	N. 0°25' E., on the E. bdy. of sec. 1.
	Over broken mountainous land through thick aspen and burned pine timber; along steep E slope.
4.80	Point for the closing cor. of secs. 6 and 7, T. 16 S., R. 7 E., hereinafter described.
	Asc. over steep SE slope.
39.95	Point selected for the witness cor. to the angle point of secs. 1 and 6.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	WC AP T 16 S R 6 E R 7 E ↑ S 1 | S 6 | 1978
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor., and set an aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.
40.01	True point for the original ¼ sec. cor. of secs. 1 and 6, at proportionate distance, falls on edge of broken sandstone ledge and cannot be monumented. There is no remaining evidence of the original corner. This now becomes an angle point.
44.80	Point for the ¼ sec. cor. of sec. 6 only, T. 16 S., R. 7 E., hereinafter described.
53.00	Bottom of "Crandall Canyon", drains E; asc. over steep S slope.
83.70	Intersect the Third Standard Parallel South.

109

Dependent Resurvey of the East Boundary,
T. 16 S., R. 6 E., Salt Lake Meridian, Utah

CHAINS	
	Point for the closing Tp. cor. of Tps. 16 S., Rgs. 6 and 7 E., at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base, to top of brass cap, mkd.
	T 15 S R 7 E S 31 S 1 | S 6 C C T 16 S R 6 E R 7 E 1978
	Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.
	From this point the stan. ¼ sec. cor. of sec. 31, T. 15 S., R. 7 E., common with the ¼ sec. cor. of sec. 6, T. 16 S., R. 7 E., bears N. 89°54' E., 11.68 chs. dist., hereinbefore described.
	From this same point the angle point of sec. 31, T. 15 S., R. 7 E., bears S. 89°54' W., 32.11 chs. dist., hereinbefore described.
	Dependent Resurvey of a Portion of the S. Bdy., T. 16 S., R. 7 E., Salt Lake Meridian, Utah
	(Restoring the Survey Executed by J.C. Dick in 1900 and the Dependent Resurvey Executed by Jerry L. Thomas in 1968-1969)
	From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. as described in the official record of the 1946 resurvey.
	S. 88°23' W., bet. secs. 3 and 34.
39.87	The ¼ sec. cor. of secs. 3 and 34, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. as described in the official record of the 1968 - 1969 resurvey of the N. bdy. of T. 17 S., R. 7 E.
	S. 88° 23' W., beginning new measurement.
39.86	The witness cor. to the cor. of secs. 3, 4, 33, and 34, monumented with an iron post, 2½ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. as described in the official record of the 1968 - 1969 resurvey of the N. bdy. of T. 17 S., R. 7 E.
39.87	The cor. of secs. 3, 4, 33, and 34, marked by a cross (X) on solid sandstone.

CHAINS	
	S. 87°12' W., bet. secs. 4 and 33.
40.08	The ¼ sec. cor. of secs. 4 and 33, monumented with an iron post, 2½ ins. diam., firmly set projecting 6 ins. above ground, with brass cap mkd. as described in the official record of the 1965 remonumentation.
	This mile and a half was resurveyed because of the misclosure found in secs. 33 and 34.
	From the ¼ sec. cor. of secs. 6 and 31, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set projecting 6 ins. above ground with brass cap mkd. as described in the official record of the 1968 - 1969 resurvey.
	S. 89°51' W., bet. secs. 6 and 31.
12.28	The closing cor. of secs. 6 and 31, Tps. 16 and 17 S., R. 7 E., monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. as described in the official record of the 1965 remonumentation. I add the marks AM on the brass cap.
12.40	Intersect the E. bdy. of sec. 36, T. 16 S., R. 6 E.
	Point for the closing cor. of secs. 6 and 31.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 16 S	T 16 S	
R 6 E	R 7 E	
S 36	S 31	C
	S 6	C
	T 17 S	

1978

From this point the cor. of Tps. 16 and 17 S., R. 6 E., bears S. 1°18' E., 4.42 chs. dist., heretofore described.

From this same point the angle point for secs. 31 and 36 bears N. 1°18' W., 35.63 chs. dist., heretofore described.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 16 S., R. 7 E., Salt Lake Meridian, Utah

(Restoring the survey executed by J.C. Dick in 1900)

From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. as described in the official record of the 1946 resurvey of the N. bdy. of sec. 2, T. 17 S., R. 7 E.

N. 0°04' E., bet. secs. 35 and 36.

CHAINS	
	Over broken bench land, through scattered juniper and pinon; desc. over N slope.
39.82	The ¼ sec. cor. of secs. 35 and 36, monumented with a sandstone, 14 x 8 x 6 ins., firmly set, projecting 8 ins. above ground, mkd. ¼ on W face, from which the remaining original bearing tree A pinon, 10 ins. diam., bears N. 85° W., 21 lks. dist., mkd. with a blaze. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd. T 16 S R 7 E ¼ S 35 | S 36 1976 from which new bearing trees A pinon, 14 ins. diam., bears N. 53½° E., 64½ lks. dist., mkd. ¼ S36 BT. A pinon, 9 ins. diam., bears S. 56° W., 33 lks. dist., mkd. ¼ S35 BT. Deposit the mkd. stone alongside the iron post.
	N. 0°04' E., beginning new measurement. Desc. along E slope through thick pinon and juniper.
4.00	Dirt road, bears NE and SW.
19.50	Huntington Creek, 40 lks. wide, flows SE.
24.35	Center line of Highway No. 31, bears N. 77° W. and S. 77° E.; asc. over gradual S slope.
39.84	The cor. of secs. 25, 26, 35, and 36, monumented with a sandstone boulder, 26 x 20 x 8 ins., above ground, mkd. with an X with 1 notch on E and 1 notch S, from which A sandstone boulder, (original bearing object) 8 x 8 x 10 ft. above ground, mkd. with a cross (X) and BO, bears N. 2° E., 21 lks. dist. An iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, for a reference monument, bears S. 0°04' W., 29 lks. dist., with brass cap mkd. RM T16S R7E S25 S26 S35 S36 1976 and an arrow pointing to the corner.
	From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., heretofore described. N. 89°54; W., bet. secs. 25 and 36.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 16 S., R. 7 E., Salt Lake Meridian, Utah

CHAINS	
	Over rough and broken mountainous land; along broken and rocky S slope.
40.00	Point for the ¼ sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 16 S R 7 E
	¼ S 25 / S 36
	1978
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.
41.00	Top of spur, projects SW; desc. over NW slope.
80.00	The cor. of secs. 25, 26, 35, and 36.
	N. 0°23' W., bet. secs. 25 and 26.
	Over broken mountainous land; asc. over gradual S slope.
39.92	The ¼ sec. cor. of secs. 25 and 26, monumented with an unmarked sandstone, 14 x 10 x 8 ins., firmly set in a scattered mound of stone, from which the original bearing trees
	A cedar, 10 ins. diam., bears S. 88° E., 41 lks. dist., mkd. ¼ S25 BT. (Record, N. 86° E.)
	A pine, 12 ins. diam., bears S. 31° W., 27 lks. dist., mkd. ¼ S26 BT. (Record, S. 66° E., 18 lks.)
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 16 S R 7 E
	¼ / S 26 | S 25
	1976
	Deposit the unmarked stone alongside the iron post.
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.
	N. 0°36' E., beginning new measurement.
	Desc. over NW slope through thick juniper and pinon.

113

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 16 S., R. 7 E., Salt Lake Meridian, Utah

CHAINS	
11.50	Dirt road in bottom of "Bear Creek Canyon", bears NE and SW; along canyon bottom.
14.00	"Bear Creek", 10 lks. wide, 2 ins. deep, flows SW; asc. over gentle SE slope.
40.22	Point for the cor. of secs. 23, 24, 25, and 26, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base, to top of brass cap, mkd. T 16 S R 7 E S 23 | S 24 S 26 | S 25 1978 Cor. is located 1.00 ch. S of wash, drains E, and on a steep NE slope.
	From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., heretofore described. N. 89°51' W., bet. secs. 24 and 25. Over broken mountainous land through thick pine timber; decs. over steep NW slope.
19.95	Point for the E 1/16 sec. cor. of secs. 24 and 25. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. E 1/16 S 24 / S 25 1978 Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor. Desc. over steep NW slope.
39.90	Point for the ¼ sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 16 S R 7 E ¼ S 24 / S 25 1978 Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.

CHAINS	
	Desc. over NW slope.
67.00	"Bear Creek", 10 lks. wide, 2 ins. deep, in bottom of canyon, flows S; asc. over SE slope.
79.80	The cor. of secs. 23, 24, 25, and 26.
	N. 0°04' W., bet. secs. 23 and 24.
	Over broken mountainous land; desc. over NE slope through scattered pinon and juniper.
40.22	Point for the ¼ sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 16 S R 7 E ¼ S 23 | S 24 1978
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.
	Cor. is located at base of sandstone ledge.
	Asc. over SE slope.
80.44	The cor. of secs. 13, 14, 23, and 24, monumented with an unmarked sandstone, 12 x 11 x 8 ins., set in a mound of stone, and is accepted as the best available evidence of the original corner position.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd.
	T 16 S R 7 E S 14 | S 13 S 23 | S 24 1978
	from which
	A pine, 24 ins. diam., bears S. 63° E., 53½ lks. dist., mkd. T16S R7E S24 BT.
	Deposit the unmarked stone alongside the iron post.
	From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., heretofore described.

CHAINS	
	N. 89°10' W., bet. secs. 13 and 24.
	Over top of "Gentry Mountain"; over nearly level land.
1.80	Dirt road, bears NE and curves SW.
19.995	Point for the E 1/16 sec. cor. of secs. 13 and 24.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	E 1/16 S 13 / S 24
	1978
	Set an aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.
	Cor. is located 2.00 chs. N of fence line, bears N. 75° W. and S. 75° E.
	Desc. over steep ledgy W slope.
39.99	Point for the ¼ sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 16 S R 7 E
	¼ S 13 / S 24
	1978
	Raise a mound of stone, 3 ft. base, 2 ft. high, SW of cor.
	Cor. is located 1.50 chs. N of draw, draining S. 55° W., and 2.00 chs. S of base of sandstone ledge, 450 ft. high.
	Asc. along steep S slope.
64.00	Bottom of "Bear Creek Canyon", drains S; asc. over steep E slope.
79.98	The cor. of secs. 13, 14, 23, and 24.
	N. 0°07' W., bet. secs. 13 and 14.
	Over rough and broken mountainous land; asc. over ledgy SE slope.
4.26	The original witness cor. of secs. 13, 14, 23, and 24, monumented with a sandstone boulder, 3 x 2 ft. above ground, mkd. with a cross (X), 3 notches on S and 1 notch on E edge, from which the original bearing tree
	A white pine, 36 ins. diam., bears E, 6 lks. dist., mkd. WC T16S R7E S13 BT.

CHAINS	
	This cor. now becomes an angle point. Add AP to sandstone.
	N. 0°07' W., beginning new measurement.
	Asc. over ledgy S slope.
34.91	Point for the ¼ sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 16 S R 7 W
	¼ S 14 | S 13
	1978
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.
	Cor. is located near S edge of small stock pond.
	Asc. over SE slope.
73.98	The cor. of secs. 11, 12, 13, and 14, monumented with a sandstone, 14 x 11 x 3 ins., firmly set, projecting 4 ins. above ground, mkd. 4 notches on S and 1 notch on E edge, from which the remains of the original bearing trees
	An aspen, 8 ins. diam., bears S. 23° E., 45 lks. dist., mkd. T16S R7E S13. (Record, S. 32° E., 30 lks. dist.)
	A dead aspen, 4 ins. diam., bears S. 30½° W., 53 lks. dist., mkd. T16S R7E S14. (Record, S. 35° W., 34 lks. dist.)
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 16 S R 7 E
	S 11 | S 12 / S 14 | S 13
	1976
	Deposit the mkd. stone alongside the iron post.
	From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., heretofore described.
	S. 89°48' W., bet. secs. 12 and 13.

CHAINS	
	Over gentle rolling top of "Gentry Mountain"; along gradual S slope through scattered aspen timber.
38.50	Dirt road, bears N and S.
40.04	The ¼ sec. cor. of secs. 12 and 13, monumented with a sandstone, 16 x 12 x 4 ins., firmly set, projecting 8 ins. above ground, mkd. ¼ on N face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 16 S R 7 E
	¼ S 12 / S 13
	1978
	Deposit the mkd. stone alongside the iron post.
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.
	S. 89°40' W., beginning new measurement.
	Along gentle S slope of grassy clearing.
40.01	The cor. of secs. 11, 12, 13, and 14.
	N. 0°11' W., bet. secs. 11 and 12.
	Over rough mountainous land; desc. over NW slope through thick pine timber.
13.50	Bottom of McCadden Hollow, drains SW; leave timber; asc. over SE slope.
26.50	Fence line, bears NW and SE.
39.77	The ¼ sec. cor. of secs. 11 and 12, monumented with a sandstone, 16 x 8 x 4 ins., firmly set, projecting 8 ins. above ground, mkd. ¼ on W face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 16 S R 7 E
	¼ S 11 | S 12
	1976
	Deposit the mkd. stone alongside the iron post.

CHAINS	
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.
	N. 0°01' W., beginning new measurement.
	Asc. over SE slope, through sparsely scattered aspen timber.
39.88	The cor. of secs. 1, 2, 11, and 12, monumented with a sandstone, 20 x 14 x 3 ins., firmly set, projecting 10 ins. above ground, mkd. 5 notches on S and 1 notch on E edges.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 16 S R 7 E S 2 | S 1 S 11 | S 12 1976
	from which new bearing trees
	An aspen, 7 ins. diam., bears East, 26½ lks. dist., mkd. T16S R7E S12 BT.
	An aspen, 7 ins. diam., bears S. 10° W., 40½ lks. dist., mkd. T16S R7E S11 BT.
	An aspen, 7 ins. diam., bears West, 6 lks. dist., mkd. T16S R7E S2 BT.
	Deposit the mkd. stone alongside the iron post.
	Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.
	From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., heretofore described.
	S. 89°29' W., bet. secs. 1 and 12.
	Over rolling top of "Gentry Mountain"; asc. over gentle E slope.
33.50	Dirt road, bears NE and SW.
38.00	Dirt road, bears NW and SE; desc. over W slope through small aspen timber.
40.07	Point for the ¼ sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

CHAINS	
	T 16 S R 7 E ¼ S 1 / S 12 1976
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.
	Desc. over W slope through small aspen and scattered pine timber.
80.14	The cor. of secs. 1, 2, 11, and 12.
	N. 0°02' W., bet. secs. 1 and 2.
	Over rolling top of "Gentry Mountain", along E slope through scattered aspen timber.
28.00	Fence line, bears N. 45° E. and S. 45° W.
39.89	The ¼ sec. cor. of secs. 1 and 2, monumented with a sandstone, 14 x 10 x 4 ins., firmly set, projecting 8 ins. above ground, mkd. ¼ on W face, from which the remains of the old bearing trees
	An aspen, 14 ins. diam., bears S. 20½° E., 126 lks. dist., mkd. R7E. No other markings visible.
	A dead aspen, 14 ins. diam., bears S. 1° W., 125 lks. dist., with no visible markings. (Record, S. 0°30' W.)
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 16 S R 7 E ¼ S 2 | S 1 1976
	from which a new bearing tree
	An aspen, 14 ins. diam., bears S. 68° E., 107 lks. dist., mkd. ¼ S1 BT.
	Deposit the mkd. stone alongside the iron post.
	N. 0°38' E., beginning new measurement.
	Along E slope.
13.50	Dirt road, bears NE and SW; asc. over SE slope.

CHAINS	
37.86	The cor. of secs. 1 and 2, common with the stan. cor. of secs. 35 and 36, T. 15 S., R. 7 E., heretofore described.
	From the cor. of secs. 25, 26, 35, and 36. N. 89°59' W., bet. secs. 26 and 35. Over rough and broken mountainous land; asc. over SE slope
39.97	The ¼ sec. cor. of secs. 26 and 35, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. as described in the official record of the 1961 resurvey of a portion of the subdivisional lines of T. 16 S., R. 7 E.
	From the cor. of secs. 23, 24, 25, and 26. S. 87°57' W., bet. secs. 23 and 26. Over rough and broken mountainous land; asc. over ledgy SE slope.
39.92	True point for the ¼ sec. cor. of secs. 23 and 26, at proportionate distance, falls in bottom of draw, draining SW, where it is impracticable to establish a permanent monument; there is no remaining evidence of the original corner.
40.42	Point selected for the witness cor. to the ¼ sec. cor. of secs. 23 and 26. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. W C T 16 S R 7 E ¼ S 23 / S 26 1978 Along steep S slope.
79.84	The cor. of secs. 22, 23, 26, and 27, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. as described in the official record of the 1961 resurvey of a portion of the subdivisional lines of T. 16 S., R. 7 E.
	N. 0°05' W., bet. secs. 22 and 23. Over broken mountainous land; desc. over NW slope.
20.20	Point for the S 1/16 sec. cor. of secs. 22 and 23. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

CHAINS	
	S 1/16 S 22 | S 23 1978 Cor. is located on W sagebrush slope, 1.72 chs. E of Highway No. 31. Asc. over SW slope.
40.40	Point for the ¼ sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 16 S R 7 E ¼ S 22 | S 23 1978 Cor. is located 10 lks. W of draw, draining SW. Asc. over SW slope.
80.80	Point for the cor. of secs. 14, 15, 22, and 23, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 16 S R 7 E S 15 | S 14 S 22 | S 23 1978 Raise a mound of stone, 6 ft. base, 4 ft. high, W of cor.
	From the cor. of secs. 13, 14, 23, and 24. S. 88°12' W., bet. secs. 14 and 23. Over rough and broken mountainous land; asc. over steep ledgy E slope.
39.94	Point for the ¼ sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original corner.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 16 S., R. 7 E., Salt Lake Meridian, Utah

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base, to top of brass cap, mkd. T 16 S R 7 E ¼ S 14 / S 23 1978 Desc. over steep W slope.
79.88	The cor. of secs. 14, 15, 22, and 23.
	N. 0°24' W., bet. secs. 14 and 15. Over rough and broken mountainous land; asc. along steep W slope.
40.40	Point for the ¼ sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd. T 16 S R 7 E ¼ S 15 | S 14 1978
41.50	Bottom of draw, drains NW; along steep W slope.
61.00	Bottom of McCadden Hollow, drains SW; asc. over SE slope.
80.80	The cor. of secs. 10, 11, 14, and 15, monumented with a sandstone, 20 x 16 x 5 ins., firmly set, projecting 10 ins. above ground, mkd. 4 notches on S and 2 notches on E edges. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd. T 16 S R 7 E S 10 | S 11 S 15 | S 14 1978 Deposit the mkd. stone alongside the iron post.

CHAINS	
	From the cor. of secs. 11, 12, 13, and 14.
	N. 89°50' W., bet. secs. 11 and 14.
	Over rolling mountainous land; desc. over NW slope through thick pine timber.
29.00	McCadden Hollow, drains SW.
39.59	The ¼ sec. cor. of secs. 11 and 14, monumented with a sandstone boulder, 3 x 2 x 1 ft. above ground, mkd. with a cross (X) for true point and a ¼ N of cross.
	from which
	An iron post, 28 ins. long, 2½ ins. diam., set 14 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base to top, for a reference monument, bears S. 89°50' E., 1 lk. dist., with brass cap mkd. RM T16S R7E ¼ S11 S14 1976 and an arrow pointing to the corner.
	S. 89°53' W., beginning new measurement.
	Desc. over SW slope.
20.33	Point for the W 1/16 sec. cor. of secs. 11 and 14.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T 16 S R 7 E
	W 1/16 S 11 / S 14
	1976
40.66	The cor. of secs. 10, 11, 14, and 15.
	N. 0°03' W., bet. secs. 10 and 11.
	Over rolling mountainous land; desc. along grassy W slope.
39.92	The ¼ sec. cor. of secs. 10 and 11, monumented with a sandstone, 14 x 12 x 4 ins., firmly set, projecting 6 ins. above ground, mkd. ¼ on W face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 16 S R 7 E
	¼ S 10 | S 11
	1976

CHAINS	
	Deposit the mkd. stone alongside the iron post.
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.
	N. 0°13' W., beginning new measurement.
	Desc. along grassy W slope through scattered aspen timber.
1.50	Bottom of Trail Canyon, drains SW; asc. over SE slope through scattered aspen and pine timber.
39.80	The cor. of secs. 2, 3, 10, and 11, monumented with a sandstone, 20 x 14 x 6 ins., firmly set, projecting 10 ins. above ground, mkd. 5 notches on S and 2 notches on E edges, from which the remains of the original bearing trees
	A pine, 20 ins. diam., bears N. 74° E., 77 lks. dist., with a healed blaze. (Record, 75 lks. dist.)
	A pine, 40 ins. diam., bears S. 88° E., 57 lks. dist., very dimly mkd. (Record, 55 lks. dist.)
	A pine, 30 ins. diam., bears S. 11° W., 63 lks. dist., with a healed blaze.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 16 S R 7 E
	S 3 | S 2
	S 10 | S 11
	1976
	Deposit the mkd. stone alongside the iron post.
	From the cor. of secs. 1, 2, 11, and 12.
	N. 89°23' W., bet. secs. 2 and 11.
	Over rolling mountainous land; asc. over E slope through scattered aspen timber.
12.75	Fence line, bears N. 12°30' E. and S. 12°30' W.
25.50	Dirt road, bears N and S.
40.17	The ¼ sec. cor. of secs. 2 and 11, monumented with a limestone, 14 x 10 x 4 ins., firmly set, projecting 6 ins. above ground, mkd. ¼ on N face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

CHAINS	
	T 16 S R 7 E ¼ S 2 / S 11 1976
	Deposit the mkd. stone alongside the iron post.
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.
	S. 89°31' W., beginning new measurement.
	Desc. over SW slope through sagebrush and grass.
13.00	Trail road, bears N. 20° E. and S. 20° W.
15.00	Trail road, bears N and SE; also top of spur, slopes S; desc. over W slope.
40.17	The cor. of secs. 2, 3, 10, and 11.
	N. 1°34' E., bet. secs. 2 and 3.
	Over rolling mountainous land; asc. over SE slope through scattered aspen and pine timber.
8.50	Dirt road, bears NE and SW.
28.00	NW rim of "Gentry Mountain", bears NE and SW; desc. over NW slope.
39.42	Point for the ¼ sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 16 S R 7 E ¼ S 3 | S 2 1976
	from which
	A pine, 20 ins. diam., bears N. 4° E., 19 lks. dist., mkd. ¼ S2 BT.
	A pine, 16 ins. diam., bears S. 27° W., 10 lks. dist., mkd. ¼ S3 BT.
77.36	The cor. of secs. 2 and 3, common with the stan. cor. of secs. 34 and 35, T. 15 S., R. 7 E., heretofore described.

CHAINS	
	From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., heretofore described.
	N. 0°04' W., bet. secs. 33 and 34.
	Over rough and broken mountainous land; desc. over steep ledgy NE slope.
39.15	Point for the ¼ sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T 16 S R 7 E ¼ S 33 | S 34 1978
78.30	The cor. of secs. 27, 28, 33, and 34, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. as described in the official record of the 1961 resurvey.
	Restoring the survey executed by J.C. Dick in 1900 and the Dependent Resurvey Executed by B. Owens in 1961
	From the ¼ sec. cor. of secs. 27 and 28, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. as described in the official record of the 1961 resurvey.
	N. 0°06' W., bet. secs. 27 and 28.
19.845	Point for the N 1/16 sec. cor. of secs. 27 and 28.
	Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base, to top of brass cap, mkd.
	T 16 S R 7 E N 1/16 S 28 | S 27 1978
21.50	Rilda Canyon, course NE.
22.00	Dirt road, bears NE and SW.
39.69	The cor. of secs. 21, 22, 27, and 28, monumented with an iron post, 2½ ins. diam., firmly set projecting 6 ins. above ground with brass cap mkd. as described in the official record of the 1961 resurvey.

CHAINS	
	From the ¼ sec. cor. of secs. 22 and 27, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. as described in the official record of the 1961 resurvey.
	N. 89° 43' W., bet. secs. 22 and 27.
8.00	Rilda Canyon, course NE.
11.00	Dirt road, bears NE and SW.
20.00	Point for the W 1/16 sec. cor. of secs. 22 and 27.
	Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base, to top of brass cap, mkd.
	T 16 S R 7 E
	W 1/16 S 22 / S 27
	1978
	Cor. is located on gentle S slope, 15 ft. N of rim of ledge, bearing E and W.
40.00	The cor. of secs. 21, 22, 27, and 28.
	Restoring the survey executed by J.C. Dick in 1900
	N. 0°12' W., bet. secs. 21 and 22.
	Over broken mountainous land; asc. over ledgy SE slope.
39.46	Point for the ¼ sec. cor. of secs. 21 and 22, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 16 S R 7 E
	¼ S 21 | S 22
	1978
	from which
	A pine, 14 ins. diam., bears S. 54° E., 34 lks. dist., mkd. BT.
59.19	Point for the N 1/16 sec. cor. of secs. 21 and 22.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	N 1/16 S 21 | S 22
	1978

CHAINS	
72.00	Small stream in bottom of "Mill Fork Canyon" flows E.
73.50	Gravel road, bears W to "Swisher Coal Mine" and E to State Highway No 31; asc. over ledgy S slope.
78.92	The cor. of secs. 15, 16, 21, and 22, monumented with a sandstone boulder, mkd. with a cross (X), with 3 notches on S and E side.
	from which
	An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 45° E., 41 lks. dist., with brass cap mkd. T16S R7E S15 RM 1978 27 FT and an arrow pointing to the cor.
	An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 45° W., 41 lks. dist., with brass cap mkd. T16S R7E S16 RM 1978 27 FT and an arrow pointing to the cor.
	and new bearing trees
	A pine, 14 ins. diam., bears N. 6° E., 65 lks. dist., mkd. T16S R7E S15 BT.
	A pine, 10 ins. diam., bears S. 48° E., 43½ lks. dist., mkd. T16S R7E S22 BT.
	A cedar, 12 ins. diam., bears S. 35° W., 28½ lks. dist., mkd. T16S R7E S21 BT.
	A cedar, 10 ins. diam., bears N. 52° W., 24 lks. dist., mkd. T16S R7E S16 BT.
	From the cor. of secs. 14, 15, 22, and 23.
	S. 88°56' W., bet. secs. 15 and 22.
	Over rough and broken mountainous land; desc. over ledgy W slope.
10.00	Coal mine road, bears N and S.
13.75	Bottom of "Trail Canyon", drains S; asc. over E slope.
15.00	Coal mine road, bears N and S.
40.02	Point for the ¼ sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd.
	T 16 S R 7 E
	¼ S 15 / S 22
	1978

CHAINS	
	Cor. is located at the top and near the E edge of a sandstone boulder, 21 x 15 x 13 ft. above ground.
41.00	Base of descent, bears NW and SE; enter bottom of "Huntington Canyon".
44.50	State Highway No. 31, bears NW and SE on a curve.
48.50	"Huntington Creek", 40 lks. wide, flows SE.
52.00	Gravel road, bears S to "Swisher Coal Mine" and NW to State Highway No. 31.
60.03	Point for the W 1/16 sec. cor. of secs. 15 and 22.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	W 1/16 S 15 / S 22
	1978
	Cor. is located 0.40 chs. S of Huntington Creek, which flows S. 72° E.
80.04	The cor. of secs. 15, 16, 21, and 22.
	N. 0° 20' W., bet. secs. 15 and 16.
	Over rough and broken mountainous land; asc. over steep S slope.
2.50	Top of spur, slopes S. 80° E.; along steep E slope through thick juniper, pinon and scattered pine timber.
20.105	Point for the S 1/16 sec. cor. of secs. 15 and 16.
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T 16 S R 7 E S 1/16
	S 16 | S 15
	1976
	Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.
40.21	Point for the ¼ sec. cor. of secs. 15 and 16, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap mkd.

CHAINS	
	T 16 S R 7 E ¼ S 16 | S 15 1976
	from which
	A pinon, 14 ins. diam., bears S. 10° E., 45½ lks. dist., mkd. ¼ S15 BT.
	A pinon, 14 ins. diam., bears S. 41° 30' W., 31 lks. dist., mkd. ¼ S16 BT.
	Desc. over ledgy NE slope.
59.96	Point selected for the witness cor. to the N 1/16 sec. cor. of secs. 15 and 16.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone. with brass cap mkd.
	W C T 16 S R 7 E N 1/16 S 16 | S 15 1976
	Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.
60.315	True point for the N 1/16 sec. cor. of secs. 15 and 16, falls on steep loose clay slope and is unsafe to monument.
71.50	"Huntington Creek", 40 lks. wide, flows SE; asc. over gradual SE slope.
80.42	The cor. of secs. 9, 10, 15, and 16, monumented with a sandstone 16 x 14 x 10 ins., firmly set, projecting 8 ins. above ground, mkd. 4 notches on S and 3 notches on E edges.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd.
	T 16 S R 7 E S 9 | S 10 S 16 | S 15 1976
	from which
	A juniper, 6 ins. diam., bears S. 8° E., 76 lks. dist., mkd. T16S R7E S15 BT.

CHAINS	
	A pine, 16 ins. diam., bears N. 88° W., 51½ lks. dist., mkd. T16S R7E S9 BT.
	A spruce, 12 ins. diam., bears N. 12° W., 121 lks. dist., mkd. T16S R7E S9 BT.
	Deposit the mkd. stone alongside the iron post.
	From the cor. of secs. 10, 11, 14, and 15.
	S. 88° 39' W., bet. secs. 10 and 15.
	Over rolling mountainous land; desc. over W slope through sagebrush and grass.
12.50	Trail Canyon, course S.
32.50	Dirt road, bears NW and SE.
39.98	Point for the ¼ sec. cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.
	T 16 S R 7 E
	¼ S 10 / S 15
	1976
59.97	Point for the W 1/16 sec. cor. of secs. 10 and 15.
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T 16 S R 7 E
	W 1/16 S 10 / S 15
	1976
	Desc. over SW slope.
79.00	State Highway No. 31, bears N. 20° W. and S. 20° E.
79.96	The cor. of secs. 9, 10, 15, and 16.
	N. 0° 29' E., bet. secs. 9 and 10.
	Over mountainous land; along bottom of "Huntington Canyon".
3.00	State Highway No. 31, bears N. 20° W. and S. 20° E.
20.005	Point for the S 1/16 sec. cor. of secs. 9 and 10.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

CHAINS	
	S 1/16 S 9 | S 10 1976
	Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.
	Cor. is located 0.62 chs. S of base of sandstone ledge, 70 ft. high.
40.01	Point for the ¼ sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T 16 S R 7 E ¼ S 9 | S 10 1978
	Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.
	Cor. is located 0.35 chs. W of base of sandstone cliff, 50 ft. high.
	Along broken W slope.
80.02	Point for the cor. of secs. 3, 4, 9, and 10, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 16 S R 7 E S 4 | S 3 S 9 | S 10 1978
	Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.
	Raise a mound of stone, 4 ft. base, 4 ft. high, W of cor.
	From the cor. of secs. 2, 3, 10, and 11.
	S. 88° 51' W., bet. secs. 3 and 10.
	Over rolling mountainous land; asc. over SE slope through scattered aspen and pine timber.
5.50	Dirt road, bears NE and SW.

CHAINS	
39.55	Point for the ¼ sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T 16 S R 7 E ¼ S 3 / S 10 1978 Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post. Asc. over NE slope through thick pine timber and dead fall.
79.10	The cor. of secs. 3, 4, 9, and 10.
	N. 1° 15' E., bet. secs. 3 and 4. Over rough and broken mountainous land; asc. over SW slope through scrub juniper and pinon timber.
40.02	Point for the ¼ sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T 16 S R 7 E ¼ S 4 | S 3 1978
42.00	"Tie Fork Canyon", 10 lks. wide, flows SW.
44.00	Dirt road, bears NE and SW; asc. over S slope.
78.84	The cor. of secs. 3 and 4 common with the stan. cor. of secs. 33 and 34, T. 15 S., R. 7 E., heretofore described.
	From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. as described in the official record of the 1965 remonumentation. N. 1° 02' W., bet. secs. 32 and 33. Over rolling mountainous land; desc. over NE slope.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 16 S., R. 7 E., Salt Lake Meridian, Utah

CHAINS	
26.00	Trail road, bears NE and SW.
40.38	The ¼ sec. cor. of secs. 32 and 33, monumented with a sandstone 16 x 10 x 4 ins., firmly set, projecting 6 ins. above ground, mkd. ¼ on W face, from which the remains of the original bearing tree A pine stump, 8 ins. diam., bears S. 37° E., 6 lks. dist. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd. T 16 S R 7 E ¼ S 32 | S 33 1976 Deposit the mkd. stone alongside the iron post.
	N. 1° 19' W., beginning new measurement. Asc. over gradual SE slope.
2.00	Top of spur, projects NE; desc. over steep N slope.
39.36	The cor. of secs. 28, 29, 32, and 33, monumented with a sandstone 16 x 12 x 4 ins., firmly set, projecting 6 ins. above ground, mkd. 1 notch on S and 4 notches on E edges, from which the original bearing trees A pine, 16 ins. diam., bears N. 6° E., 115 lks. dist., with a healed blaze. A pine, 16 ins. diam., bears S. 65° E., 27 lks. dist., with a healed blaze. A pine, 16 ins. diam., bears S. 3° W., 88 lks. dist., with a healed blaze. A pine, 24 ins. diam., bears N. 78° W., 85½ lks. dist., with a healed blaze. (Record, 95 lks. dist.) At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 16 S R 7 E S 29 | S 28 S 32 | S 33 1976 Deposit the mkd. stone alongside the iron post.

CHAINS	
	From the cor. of secs. 27, 28, 33, and 34.
	S. 88° 39' W., bet. secs. 28 and 33.
	Over rough and broken mountainous land; desc. over NW slope.
40.60	Point for the ¼ sec. cor. of secs. 28 and 33, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 16 S R 7 E ¼ S 28 / S 33 1978
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.
81.20	The cor. of secs. 28, 29, 32, and 33.
	N. 0° 42' W., bet. secs. 28 and 29.
	Over rough and broken mountainous land; desc. along E slope.
39.67	The ¼ sec. cor. of secs. 28 and 29, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. ¼ S 29 | S 28 1946
	from which
	A pine stump, 8 ins. diam., bears N. 14° E., 13½ lks. dist., mkd. ¼ S28 BT.
	A pine stump, 9 ins. diam., bears N. 47° W., 43 lks. dist., mkd. BT.
	There is no official record of this corner setting. This position is harmoniously related to existing original cors., and is accepted as a careful and faithful perpetuation of the position of the original corner.
	N. 2° 00' E., beginning new measurement.
0.30	Trail road, bears E and W.
2.50	"Rilda Canyon" flows E; asc. over SW slope.
4.75	Trail road, bears NW and SE; asc. over steep SW slope.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 16 S., R. 7 E., Salt Lake Meridian, Utah

CHAINS	
40.10	Point for the cor. of secs. 20, 21, 28, and 29, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base, to top of brass cap, mkd. T 16 S R 7 E S 20 | S 21 S 29 | S 28 1978
	From the cor. of secs. 21, 22, 27, and 28. S. 89° 00' W., bet. secs. 21 and 28. Over rough and broken mountainous land; asc. over SE slope.
40.08	Point for the ¼ sec. cor. of secs. 21 and 28, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd. T 16 S R 7 E ¼ S 21 S 28 1978
80.16	The cor. of secs. 20, 21, 28, and 29.
	N. 0° 11' E., bet. secs. 20 and 21. Over rough and broken mountainous land; asc. over SW slope.
40.10	Point for the ¼ sec. cor. of secs. 20 and 21, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd. T 16 S R 7 E ¼ S 20 | S 21 1978
79.60	Small stream in bottom of "Mill Fork Canyon", flows E.

CHAINS	
80.20	Point for the cor. of secs. 16, 17, 20, and 21, at proportionate distance, falls in dirt road, 25 lks. wide, bears E and W. There is no remaining evidence of the original corner. At the corner point Deposit a brass cap, mkd. T16S R7E S16 S17 S20 S21 1978, 12 ins. below surface of road, from which An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 46° E., 197 lks. dist., with brass cap mkd. T16S R7E RM S16 130 FT 1978 and an arrow pointing to the cor. An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 46° W., 197 lks. dist., with brass cap mkd. T16S R7E RM S20 130 FT 1978 and an arrow pointing to the cor.
	From the cor. of secs. 15, 16, 21, and 22. S. 89° 55' W., bet. secs. 16 and 21. Over broken mountainous land; along ledgy S slope through scattered juniper and pinon.
19.91	Point for the E 1/16 sec. cor. of secs. 16 and 21. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. E 1/16 S 16 / S 21 1978 Cor. is located 81 lks. N of rim of sandstone ledge, 70 ft. high and on S edge of old bulldozed road, bearing E and W.
39.82	Point for the ¼ sec. cor. of secs. 16 and 21, at proportionate distance, falls near rim of sandstone ledge; there is no remaining evidence of the original corner. Chisel a large X and a ¼ to the N, on sandstone ledge. from which An iron post, 12 ins. long, 1 in. diam., set 6 ins. in solid sandstone, for a reference monument, bears N. 38° 22' E., 3.3 lks. dist., with brass cap mkd. T16S R7E RM ¼ S16 2.18 FT 1978 and an arrow pointing to the cor. An iron post, 12 ins. long, 1 in. diam., set 6 ins. in solid sandstone, for a reference monument, bears S. 55° 18' E., 3.3 lks. dist., with brass cap mkd. T16S R7E RM ¼ S21 2.18 FT 1978 and an arrow pointing to the cor.

CHAINS	
	Cor. point is located 1.06 chs. N of dirt road in bottom of canyon, bearing E and W.
	Desc. over sandstone ledge.
61.50	Dirt road, bears W and S. 85° E.
79.64	The cor. of secs. 16, 17, 20, and 21.
	N. 0° 27' W., bet. secs. 16 and 17.
	Over rough and broken mountainous land; asc. over S slope.
20.05	Point for the S 1/16 sec. cor. of secs. 16 and 17.
	Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.
	S 1/16 S 17 | S 16 1978
	Cor. is surrounded by large sandstone boulders. On the boulder to the S, I raise a mound of stone, 2½ ft. base 1½ ft. high.
	Asc. over steep ledgy S slope.
40.10	Point for the ¼ sec. cor. of secs. 16 and 17, at proportionate distance, falls near edge of sandstone ledge 5 ft. high; there is no remaining evidence of the original corner.
	Chisel X with ¼ to the N on sandstone ledge.
	from which
	An iron post, 28 ins. long, 2½ ins. diam., set 10 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base to top, for a reference monument, bears S. 0° 27' E., 14 lks. dist., with brass cap mkd. T16S R7E RM S16 S17 1978 and an arrow pointing to the cor.
80.20	Point for the cor. of secs. 8, 9, 16, and 17, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., over X chiseled in solid sandstone, in a mound of stone, 4 ft. base, to top of brass cap, mkd.
	T 16 S R 7 E S 8 | S 9 S 17 | S 16 1978
	Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.

CHAINS	
	From the cor. of secs. 9, 10, 15, and 16.
	S. 89° 45' W., bet. secs. 9 and 16.
	Over rolling and broken mountainous land; along bottom of "Huntington Canyon".
5.00	"Huntington Creek", 40 lks. wide, flows S; asc. over steep E slope.
19.95	Point for the E 1/16 sec. cor. of secs. 9 and 16.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	E 1/16 S 9 / S 16
	1978
	Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.
	Cor. is located in large grassy area.
39.90	Point for the ¼ sec. cor. of secs. 9 and 16, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T 16 S R 7 E
	¼ S 9 / S 16
	1978
	Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.
	Cor. is located in a large open grassy area.
79.80	The cor. of secs. 8, 9, 16, and 17.
	N. 0° 51' E., bet. secs. 8 and 9.
	Over rough and broken mountainous land; desc. along E slope.
20.05	Point for the S 1/16 sec. cor. of secs. 8 and 9.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	S 1/16
	S 8 | S 9
	1978

CHAINS	
	Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.
37.00	Bottom of "Little Bear Canyon", drains E; asc. over steep S slope.
40.10	Point for the ¼ sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap mkd. T 16 S R 7 E ¼ S 8 | S 9 1978 Asc. over steep S slope and ledges.
80.20	Point for the cor. of secs. 4, 5, 8, and 9, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T 16 S R 7 E S 5 | S 4 S 8 | S 9 1978 Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.
	From the cor. of secs. 3, 4, 9, and 10. S. 89° 53' W., bet. secs. 4 and 9. Over rough and broken mountainous land; desc. over steep SW slope.
33.75	State Highway No. 31, in bottom of "Huntington Canyon", bears N. 24° 25' W. and S. 24° 25' E.
38.00	"Huntington Creek", 40 lks. wide, flows S. 25° E.; asc. over NE slope.
39.64	Point for the ¼ sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 16 S., R. 7 E., Salt Lake Meridian, Utah

CHAINS	
	T 16 S R 7 E ¼ S 4 / S 9 1978
	Asc. over steep NW slope.
79.28	The cor. of secs. 4, 5, 8, and 9.
	N. 1° 02' E., bet. secs. 4 and 5.
	Over rough mountainous land; desc. over NE slope.
39.00	Top of spur, slopes NE; desc. over N slope.
40.10	Point for the ¼ sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4½ ft. base, to top of brass cap, mkd.
	T 16 S R 7 E ¼ S 5 | S 4 1978
	Desc. over steep N slope.
56.00	Small stream, 15 lks. wide, in bottom of "Crandall Canyon", flows E.
57.00	Bulldozed road, bears E and W; asc. over steep S slope.
78.96	The cor. of secs. 4 and 5, common with the stan. cor. of secs. 32 and 33, T. 15 S., R. 7 E., heretofore described.
	From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above ground with brass cap mkd. as described in the official record of the 1965 remonumentation.
	N. 0° 18' W., bet. secs. 31 and 32.
	Over mountainous land; asc. over SW slope through thick pine and aspen timber.
39.63	The ¼ sec. cor. of secs. 31 and 32, monumented with a sandstone, 16 x 14 x 8 ins., firmly set, projecting 8 ins. above ground, mkd. ¼ on W face, from which the remains of the original bearing tree
	An aspen 8 ins. diam., bears S. 66° E., 43 lks. dist., mkd. S32 BT. (Record, 41 lks. dist.)

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 16 S R 7 E

¼

S 31 | S 32

1976

Deposit the mkd. stone and set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.

N. 0° 11' E., beginning new measurement.

Desc. over NE slope.

39.52 The cor. of secs. 29, 30, 31, and 32, monumented with a sandstone, 18 x 10 x 5 ins., firmly set, projecting 10 ins. above ground, mkd. 1 notch on S and 5 notches on E edges.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.

T 16 S R 7 E

S 30 | S 29
S 31 | S 32

1976

Deposit the mkd. stone and set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.

From the cor. of secs. 28, 29, 32, and 33.

S. 89° 51' W., bet. secs. 29 and 32.

Over rough and broken mountainous land; asc. over steep E slope through thick aspen and pine timber.

39.66 Point for the ¼ sec. cor. of secs. 29 and 32, at proportionate distance, falls on sandstone boulder, 10 x 5 x 3 ft. above ground; there is no remaining evidence of the original corner.

Chisel a large cross (X) with a ¼ to the N.

Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the sandstone boulder.

No other monumentation necessary.

79.32 The cor. of secs. 29, 30, 31, and 32.

CHAINS	
	N. 89° 07' W., bet. secs. 30 and 31.
	Over mountainous land; asc. over steep E slope.
38.00	Top of spur, slopes N; enter grassy clearing; along N slope.
40.19	Point for the ¼ sec. cor. of secs. 30 and 31, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 16 S R 7 E
	¼ S 30 / S 31
	1978
	Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.
	Desc. over NW slope.
51.75	Intersect the E. bdy. of sec. 25, T. 16 S., R. 6 E.
	Point for the closing cor. of secs. 30 and 31, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 16 S R 6 E R 7 E S 25 | S 30 C / S 31 C
	1978
	from which
	An aspen, 6 ins. diam., bears N. 57° 30' E., 15½ lks. dist., mkd. T16S R7E S30 BT.
	A pine, 10 ins. diam., bears S. 46° E., 15 lks. dist., mkd. T16S R7E S31 BT.
	A pine, 6 ins. diam., bears N. 75° W., 16 lks. dist., mkd. T16S R6E S25 BT.
	From this point the angle point for secs. 25 and 31, bears S. 0° 21' W., 4.42 chs. dist., heretofore described.
	From this same point the angle point for secs. 25 and 30, bears N. 0° 21' E.,35.23 chs. dist., heretofore described.

CHAINS	
	The point for the ¼ sec. cor. of sec. 31 only, T. 16 S., R. 7 E., is at midpoint on the W. bdy. of sec. 31. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 16 S R 6 E R 7 E | ¼ | S 31 1978 From this point the angle point for secs. 31 and 36, bears S. 1° 25' W., 4.23 chs. dist., heretofore described. From this same point the angle point for secs. 25 and 31, bears N. 1° 25' E., 35.43 chs. dist., heretofore described. Cor. is located 44 lks. S of spring branch, 3 lks. wide flows E.
	From the cor. of secs. 29, 30, 31, and 32. N. 0° 08' W., bet. secs. 29 and 30. Over rough and broken mountainous land; desc. along steep E slope.
39.98	The ¼ sec. cor. of secs. 29 and 30, marked by a cross on S face of sandstone ledge and a ¼ S of cross. from which An iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top for a reference monument, bears S. 0° 08' E., 1 lk. dist., with brass cap mkd. T16S R7E RM S29 S30 1976 and an arrow pointing to the cor. Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.
	N. 0° 16' E., beginning new measurement. Asc. over ledgy S slope.
32.50	Bottom of "Rilda Canyon", drains SE; asc. over S slope.
39.84	Point for the cor. of secs. 19, 20, 29, and 30, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base, to top of brass cap, mkd.

145

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 16 S., R. 7 E., Salt Lake Meridian, Utah

CHAINS	
	T 16 S R 7 E S 19 | S 20 S 30 | S 29 1978
	From the cor. of secs. 20, 21, 28, and 29. S. 89° 54' W., bet. secs. 20 and 29. Over rough mountainous land; desc. over SW slope.
40.07	Point for the ¼ sec. cor. of secs. 20 and 29, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base, to top of brass cap, mkd. T 16 S R 7 E ¼ S 20 / S 29 1978 Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.
80.14	The cor. of secs. 19, 20, 29, and 30.
	N. 89° 48' W., bet. secs. 19 and 30. Over mountainous land; desc. along S slope through scattered mahogany.
21.00	Bottom of "Rilda Canyon", drains SE; asc. over NE slope through thick pine and aspen timber.
40.07	Point for the ¼ sec. cor. of secs. 19 and 30, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 16 S R 7 E ¼ S 19 / S 30 1978 Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post. Asc. over NE slope.
51.47	Intersect the E. bdy. of sec. 24, T. 16 S., R. 6 E.

CHAINS	
	Point for the closing cor. of secs. 19 and 30, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base, to top of brass cap, mkd. T 16 S R 6 E R 7 E S 24 | S 19 C | S 30 C 1978 From this point the angle point for secs. 24 and 30, bears S. 0° 25' W., 4.45 chs. dist., heretofore described. From this same point the angle point for secs. 19 and 24, bears N. 0° 25' E., 35.56 chs. dist., heretofore described.
	The point for the ¼ sec. cor. of sec. 30 only, T. 16 S., R. 7 E., is at midpoint on the W. bdy. of sec. 30. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 16 S R 6 E R 7 E | ¼ | S 30 1978 From this point the angle point for secs. 25 and 30, bears S. 0° 10' W., 4.37 chs. dist., heretofore described. From this same point the cor. of secs. 24 and 30, bears N. 0° 10' E., 35.15 chs. dist., heretofore described.
	From the cor. of secs. 19, 20, 29, and 30. N. 0° 20' E., bet. secs. 19 and 20. Over mountainous land; asc. over steep S slope through scattered mahogany brush.
39.84	Point for the ¼ sec. cor. of secs. 19 and 20, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

CHAINS	
	T 16 S R 7 E ¼ S 19 | S 20 1978 Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post. Desc. along E slope.
79.68	Point for the cor. of secs. 17, 18, 19, and 20, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T 16 S R 7 E S 18 | S 17 S 19 | S 20 1978 Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.
	From the cor. of secs. 16, 17, 20, and 21. N. 89° 31' W., bet. secs. 17 and 20. Over mountainous land; along dirt road in bottom of "Mill Fork Canyon".
17.00	Leave road, which curves NW.
22.50	Mill Fork Canyon, 10 lks. wide, flows SE; asc. over NE slope.
39.96	Point for the ¼ sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T 16 S R 7 E ¼ S 17 S 20 1978 Asc. over NE slope through grove of small aspen timber.
79.92	The cor. of secs. 17, 18, 19, and 20.

CHAINS	
	N. 89° 23' W., bet. secs. 18 and 19.
	Over mountainous land; along N slope.
39.92	Point for the ¼ sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T 16 S R 7 E ¼ S 18 / S 19 1978
	Raise a mound of stone, 5 ft. base, 3 ft. high, W of cor., for protection from erosion.
51.37	Intersect the E. bdy. of sec. 13, T. 16 S., R. 6 E.
	Point for the closing cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 16 S R 6 E | R 7 E S 13 | S 18 C / S 19 C 1978
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, East of cor.
	From this point the angle point for secs. 13 and 19, bears S. 0° 25' W., 4.48 chs. dist., heretofore described.
	From this same point the angle point for secs. 13 and 18, bears N. 0° 25' E., 35.53 chs. dist., heretofore described.
	The point for the ¼ sec. cor. of sec. 19 only, T. 16 S., R. 7 E., is at midpoint on the W. bdy. of sec. 19.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T 16 S R 6 E | R 7 E ¼ S 19 1978

CHAINS	
	From this point the angle point for secs. 19 and 24, bears S. 0° 25' W., 4.465 chs. dist., heretofore described. From this same point the angle point for secs. 13 and 19, bears N. 0° 25' E., 35.545 chs. dist., heretofore described.
	From the cor. of secs. 17, 18, 19, and 20. N. 0° 21' W., bet. secs. 17 and 18. Over mountainous land; desc. over N slope through thick pine and aspen timber.
39.84	Point for the ¼ sec. cor. of secs. 17 and 18, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 16 S R 7 E ¼ S 18 | S 17 1978
41.00	"Mill Fork Canyon", drains SE; asc. over SW slope.
79.68	The cor. of secs. 7, 8, 17, and 18, monumented with a sandstone, 16 x 14 x 5 ins., firmly set, projecting 6 ins. above ground, mkd. 4 notches on S and 5 notches on E edges, from which the original bearing trees A pine, 20 ins. diam., bears N. 74° E., 61 lks. dist., mkd. T16S R7E S8 BT. A pine, 24 ins. diam., bears N. 55° W., 39 lks. dist., mkd. T16S R7E S7 BT. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd. T 16 S R 7 E S 7 | S 8 S 18 | S 17 1976 Deposit the mkd. stone alongside the iron post.
	From the cor. of secs. 8, 9, 16, and 17. S. 89° 09' W., bet. secs. 8 and 17. Over mountainous land; asc. over steep E slope.

CHAINS	
39.90	Point for the ¼ sec. cor. of secs. 8 and 17, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T 16 S R 7 E ¼ S 8 / S 17 1978 Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.
79.80	The cor. of secs. 7, 8, 17, and 18.
	N. 88° 58' W., bet. secs. 7 and 18. Over broken mountainous land; asc. over SE slope.
38.98	Point for the ¼ sec. cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd. T 16 S R 7 E ¼ S 7 / S 18 1978
50.28	Intersect the E. bdy. of sec. 12, T. 16 S., R. 6 E. Point for the closing cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., over a cross (X) chiseled in solid sandstone, in a mound of stone, 4½ ft. base, to top of brass cap, mkd. T 16 S R 6 E | R 7 E S 12 | S 7 C / S 18 C 1978 From this point the angle point for secs. 12 and 18, bears S. 0° 25' W., 4.49 chs. dist., heretofore described. From this same point the angle point for secs. 7 and 12, bears N. 0° 25' E., 35.52 chs. dist., heretofore described.

151

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 16 S., R. 7 E., Salt Lake Meridian, Utah

CHAINS	
	The point for the ¼ sec. cor. of sec. 18 only, T. 16 S., R. 7 E., is at midpoint on the W. bdy. of sec. 18. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd. T 16 S R 6 E | R 7 E | ¼ | S 18 1978 From this point the angle point for secs. 13 and 18, bears S. 0° 25' W., 4.485 chs. dist., heretofore described. From this same point the angle point for secs. 12 and 18, bears N. 0° 25' E., 35.525 chs. dist., heretofore described.
	From the cor. of secs. 7, 8, 17, and 18. N. 0° 10' W., bet. secs. 7 and 8. Over broken mountainous land; asc. over steep ledgy S slope.
39.79	The ¼ sec. cor. of secs. 7 and 8, monumented with a sandstone, 20 x 10 x 4 ins., firmly set, projecting 10 ins. above ground, mkd. ¼ on W face, from which the original bearing trees An aspen, 12 ins. diam., bears S. 46° E., 5 lks. dist., dimly mkd. An aspen, 12 ins. diam., bears N. 53° W., 19 lks. dist., dimly mkd. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 16 S R 7 E ¼ S 7 | S 8 1976 Deposit the mkd. stone alongside the iron post. Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 16 S., R. 7 E., Salt Lake Meridian, Utah

CHAINS	
	N. 2° 32' E., beginning new measurement.
	Along E slope through small aspen grove.
1.00	Spur, slopes NE; desc. over N slope; enter grassy clearing.
39.70	Point for the cor. of secs. 5, 6, 7, and 8, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.
	T 16 S R 7 E S 6 | S 5 S 7 | S 8 1978
	Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.
	From the cor. of secs. 4, 5, 8, and 9.
	S. 88° 37' W., bet. secs. 5 and 8.
	Over rough and broken mountainous land; asc. over steep ledgy NE slope.
39.68	Point for the ¼ sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 16 S R 7 E ¼ S 5 S 8 1978
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.
	Desc. over NW slope.
79.36	The cor. of secs. 5, 6, 7, and 8.
	N. 88° 00' W., bet. secs. 6 and 7.
	Over rough and broken mountainous land; asc. over steep NE slope.
39.66	Point for the ¼ sec. cor. of secs. 6 and 7, at proportionate distance; there is no remaining evidence of the original corner.

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd.

T 16 S R 7 E

¼ S 6 / S 7

1978

Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.

51.36 Intersect the E. bdy. of sec. 1, T. 16 S., R. 6 E.

True point for the closing cor. of secs. 6 and 7, at proportionate distance, falls on edge of sandstone ledge, 1 ft. high and cannot be monumented; there is no remaining evidence of the original corner.

Point selected for the witness cor. to the closing cor. of secs. 6 and 7, bears N. 0° 25' E., 0.02 chs. dist.

Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.

W C
T 16 S
R 6 E R 7 E

S 1 | S 6 C
| S 7 C

1978

From the true point the angle point for secs. 1 and 7, bears S. 0° 25' W., 4.80 chs. dist. heretofore described.

From this same true point the angle point for secs. 1 and 6, bears N. 0° 25' E., 35.21 chs. dist., heretofore described.

The point for the ¼ sec. cor. of sec. 7 only, T. 16 S., R. 7 E., is at midpoint on the W. bdy. of sec. 7.

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 16 S
R 6 E R 7 E

| ¼
| S 7

1978

From this point the angle point for secs. 7 and 12, bears S. 0° 25' W., 4.645 chs. dist., heretofore described.

CHAINS

From this same point the angle point for secs. 1 and 7, bears N. 0° 25' E., 35.365 chs. dist., heretofore described.

The point for the ¼ sec. cor. of sec. 6 only, T. 16 S., R. 7 E., is at proportionate distance on the W. bdy. of sec. 6.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 16 S
R 6 E | R 7 E
¼
S 6
1978

Raise a mound of stone, 2½ ft. base, 1½ ft. high, E of cor.

From this point the true angle point for secs. 1 and 6, bears S. 0° 25' W., 4.79 chs. dist., heretofore described.

From this same point the closing cor. of secs. 1 and 6, Tps. 16 S., Rs. 6 and 7 E., bears N. 0° 25' E., 38.90 chs. dist., heretofore described.

From the cor. of secs. 5, 6, 7, and 8.

N. 2° 36' W., bet. secs. 5 and 6.

Over rough and broken mountainous land; desc. over NE slope.

38.20 Small stream, 10 lks. wide, in bottom of "Crandall Canyon", flows E; asc. over S slope.

38.50 Trail road, bears E and W.

39.70 The ¼ sec. cor. of secs. 5 and 6, monumented with a sandstone, 16 x 10 x 4 ins., firmly set, projecting 2 ins. above ground, mkd. ¼ on W face.

There is no remaining evidence of the original bearing trees.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 16 S R 7 E
¼
S 6 | S 5
1978

Deposit the mkd. stone alongside the iron post.

155 Dependent Resurvey of a Portion of the Subdivisional Lines, T. 16 S., R. 7 E., Salt Lake Meridian, Utah

CHAINS	
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor., and set a red aluminum post, 6 ft. long with attention sign on top, alongside the iron post.
	N. 4° 11' E., beginning new measurement.
	Asc. over S slope.
39.00	Enter small grove of aspen timber; also top of ridge, bears E and W.
40.00	Leave aspen timber; enter grassy clearing.
41.27	The cor. of secs. 5 and 6, common with the stan. cor. of secs. 31 and 32, T. 15 S., R. 7 E., heretofore described.
	Subdivision of Section 5, T. 16 S., R. 7 E., Salt Lake Meridian, Utah
	From the ¼ sec. cor. of secs. 5 and 8.
	N. 0° 57' E., on the N and S center line of sec. 5.
	Over steep NW slope, through scattering timber and undergrowth.
39.92	Point for the center ¼ sec. cor. of sec. 5, at the intersection with E and W center line.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap, mkd.
	T 16 S R 7 E
	C 1/4 S 5
	1978
	Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.
	Cor. is located on steep NW slope among small aspen and undergrowth.
44.00	"Crandall Canyon", drains NE; asc. over SE slope.
45.50	Dirt road, bears NE and SW.
79.89	The stan. ¼ sec. cor. of secs. 5 and 32, on the N. bdy. of the Tp., heretofore described.
	From the ¼ sec. cor. of secs. 4 and 5.
	S. 88° 20' W., on the E and W center line of sec. 5.

Subdivision of Section 5, T. 16 S., R. 7 E.,
Salt Lake Meridian, Utah

CHAINS	
	Desc. gradually over steep N slope, through scattering timber and undergrowth.
39.75	The center ¼ sec. cor. of sec. 5.
54.00	"Crandall Canyon", drains NE; asc. gradually over SE slope.
57.00	Dirt road, bears NE and SW.
81.89	The ¼ sec. cor. of secs. 5 and 6.

Subdivision of Section 8, T. 16 S., R. 7 E.,
Salt Lake Meridian, Utah

From the ¼ sec. cor. of secs. 8 and 17.

N. 1° 01' E., on the N and S center line of sec. 8.

Desc. over steep NE slope, through scattering timber and undergrowth.

39.96 Point for the center ¼ sec. cor. of sec. 8, at the intersection with the E and W center line.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 16 S R 7 E

C 1/4 S 8

1978

Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.

Cor. is located alongside the SE edge of boulder, 10 x 9 x 7 ft., from which the NE end of a sandstone cliff, 6 chs. long and 75 lks. high, bears N. 8° E., 1.20 chs. dist.

79.83 The ¼ sec. cor. of secs. 5 and 8.

From the ¼ sec. cor. of secs. 8 and 9.

S. 88° 57' W., on the E and W center line of sec. 8.

Asc. over steep SE slope, through scattering timber and undergrowth.

39.78 The center ¼ sec. cor. of sec. 8.

80.50 The ¼ sec. cor. of secs. 7 and 8.

Subdivision of Section 9, T. 16 S., R. 7 E.,
Salt Lake Meridian, Utah

157

Subdivision of Section 9, T. 16 S., R. 7 E.,
Salt Lake Meridian, Utah

CHAINS	
	From the ¼ sec. cor. of secs. 9 and 16.
	N. 0° 40' E., on the N and S center line of sec. 9.
	Asc. over broken SE slope, through medium undergrowth.
20.03	Point for the center S 1/16 sec. cor. of sec. 9.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	C S 1/16 | S 9 C 1978
	Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.
	Cor. is located East 45 lks. from small draw draining North.
31.00	Little Bear Canyon, drains E; asc. over steep S slope.
40.06	Point for the center ¼ sec. cor. of sec. 9 at the intersection with the E and W center line.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T 16 S R 7 E C 1/4 S 9 1978
	Set a red aluminum post, 6 ft. long, with yellow attention sign on top, alongside the iron post.
	Cor. is located on steep SE slope, and S 16 lks. from base of red sandstone ledge, 28 lks. high.
80.11	The ¼ sec. cor. of secs. 4 and 9.
	From the ¼ sec. cor. of secs. 9 and 10.
	S. 89° 49' W., on the E and W center line of sec. 9.
	Desc. abruptly over broken E slope, through light undergrowth.
15.50	Highway No. 31, 45 lks. wide, bears N. 21° W. and S. 21° E.
19.50	"Huntington Creek", 50 lks. wide, course winding SE.
19.89	Point for the center E 1/16 sec. cor. of sec. 9.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

Subdivision of Section 9, T. 16 S., R. 7 E.,
Salt Lake Meridian, Utah

CHAINS	
	E 1/16 C ——— C S 9 1978
	Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.
	Cor. is located South, 40 lks. from S bank of "Huntington Creek", on gradual NW slope.
39.78	The center ¼ sec. cor. of sec. 9.
	Over broken S slope, through scattered undergrowth.
79.55	The ¼ sec. cor. of secs. 8 and 9.
	From the E 1/16 sec. cor. of secs. 9 and 16.
	N. 0° 34' E., on the N and S center line of the SE¼ of sec. 9.
	Desc. over steep NW slope, through scattering of undergrowth.
20.02	Point for the SE 1/16 sec. cor. at the intersection with the E and W center line of the SE¼.
	Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base, to top of brass cap, mkd.
	SE 1/16 S9 1978
	Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.
	Cor. is located 1.50 chs. East from ridge projecting N. 40° E. and West, 2.00 chs. from top edge of sandstone cliff.
34.00	Little Bear Canyon, 15 lks. wide, drains NE.
40.04	The center E 1/16 sec. cor. of sec. 9.
	From the S 1/16 sec. cor. of secs. 9 and 10.
	S. 89° 47' W., on the E and W center line of the SE¼ of sec. 9.
	Desc. over moderate SW slope, through scattering undergrowth.
6.50	Highway No. 31, 60 lks. wide, bears N. 21° W. and S. 21° E.
9.50	Huntington Creek, 50 lks. wide, course winding SE.

Subdivision of Section 9, T. 16 S., R. 7 E.,
Salt Lake Meridian, Utah

CHAINS	
19.92	The SE 1/16 sec. cor. of sec. 9.
39.84	The center S 1/16 sec. cor. of sec. 9.
	S. 89° 47' W., on the E and W center line of the SW¼ of sec. 9.
	Asc. gradually over steep N slope, through scattered timber.
18.00	Top of ascent; desc. abruptly over NW slope, through scattered timber.
39.84	The S 1/16 sec. cor. of secs. 8 and 9.

Subdivision of Section 14, T. 16 S., R. 7 E.,
Salt Lake Meridian, Utah

	From the ¼ sec. cor. of secs. 14 and 23.
	N. 0° 07' E., on the N and S center line of sec. 14.
	Asc. abruptly over broken SW slope, through scattered timber and undergrowth.
39.79	Point for the center ¼ sec. cor. of sec. 14, at the intersection with E and W center line.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T 16 S R 7 E C 1/4 S 14 1978
	Set a red aluminum post, 6 ft. long, with yellow attention sign on top, alongside the iron post.
	Cor. is located on NE slope, among some large pine timber.
75.50	McCadden Hollow, drains W.
79.61	The ¼ sec. cor. of secs. 11 and 14.
	From the ¼ sec. cor. of secs. 13 and 14.
	S. 89° 04' W., on the E and W center line of sec. 14.
	Asc. over moderate SE slope, through scattered timber.
39.76	The center ¼ sec. cor. of sec. 14.

☆ GPO 1980—680-288/121

Subdivision of Section 14, T. 16 S., R. 7 E.,
Salt Lake Meridian, Utah

CHAINS	
59.91	Point for the center W 1/16 sec. cor. of sec. 14. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. C W 1/16 / S 14 C 1978 Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post. Cor. is located on NW slope, among some large pine timber.
72.00	Desc. over steep W slope, through scattered undergrowth.
80.06	The ¼ sec. cor. of secs. 14 and 15.

Subdivision of Section 15, T. 16 S., R. 7 E.,
Salt Lake Meridian, Utah

	From the ¼ sec. cor. of secs. 15 and 22. N. 0° 22' W., on the N and S center line of sec. 15. Asc. abruptly over broken SW slope, through scattered undergrowth.
40.30	Point for the center ¼ sec. cor. of sec. 15, at the intersection with E and W center line. Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 16 S R 7 E C 1/4 S 15 1978 Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post. Desc. gradually across W slope, through scattered undergrowth.
60.45	Point for the center N 1/16 sec. cor. of sec. 15. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. C N 1/16 | S 15 C 1978 Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.

161

Subdivision of Section 15, T. 16 S., R. 7 E.,
Salt Lake Meridian, Utah

CHAINS	
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	Cor. is located N 1 ch. from a small draw, draining SW.
	Asc. abruptly over broken SW slope, through scattered undergrowth.
80.60	The ¼ sec. cor. of secs. 10 and 15.
	From the ¼ sec. cor. of secs. 14 and 15.
	S. 88° 47' W., on the E and W center line of sec. 15.
	Desc. abruptly over broken ledges and sheer faced cliffs.
14.00	Trail Canyon, course S.
15.00	Dirt road, bears N and S.
21.00	Dirt road, bears NE and SW.
34.00	Dirt road, bears N and S.
40.00	The center ¼ sec. cor. of sec. 15.
60.00	Point for the center W 1/16 sec. cor. of sec. 15.
	Set an iron post, 28 ins. long, 2½ ins. diam., over chiseled X in bedrock, in a mound of stone, 5 ft. base, to top of brass cap, mkd.
	C $\frac{\text{W } 1/16}{\text{S } 15}$ C
	1978
	Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.
	Cor. is located among some very large boulders.
64.50	Highway No. 31, 60 lks. wide, bears N. 5° W. and S. 5° E.
68.00	Huntington Creek, 50 lks. wide, course S.
80.00	The ¼ sec. cor. of secs. 15 and 16.
	From the W 1/16 sec. cor. of secs. 15 and 22.
	N. 0° 21' W., on the N and S center line of the SW¼ of sec. 15.
2.00	Huntington Creek, 50 lks. wide, course SE.
7.00	Highway No. 31, 45 lks. wide, bears N. 40° W.
40.25	The center W 1/16 sec. cor. of sec. 15.

Subdivision of Section 15, T. 16 S., R. 7 E.,
Salt Lake Meridian, Utah

CHAINS	
	N. 0° 21' W., on the N and S center line of the NW¼ of sec. 15.
20.13	Point for the NW 1/16 sec. cor. at the intersection with the E and W center line of the NW¼ of sec. 15.
	Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd.
	NW 1/16 S 15
	1978
	Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.
	Cor. is located E 2.00 chs. from sandstone ledges and N. 27 lks. from small draw that drains SW.
40.26	The W 1/16 sec. cor. of secs. 10 and 15.
	From the center N 1/16 sec. cor. of sec. 15.
	S. 88° 43' W., on the E and W center line of the NW¼ of sec. 15.
	Desc. abruptly over broken SW slope, through scattered undergrowth.
20.00	The NW 1/16 sec. cor. of sec. 15.
32.00	Highway No. 31, 45 lks. wide, bears N. 20° W. and S. 20° E.
35.50	Huntington Creek, 50 lks. wide, course S.
40.00	The true point for the N 1/16 sec. cor. of secs. 15 and 16.
	Subdivision of Section 16, T. 16 S., R. 7 E., Salt Lake Meridian, Utah
	From the ¼ sec. cor. of secs. 16 and 21.
	N. 0° 24' W., on the N and S center line of sec. 16.
	Asc. abruptly over broken S slope, through scattered undergrowth.
20.075	Point for the center S 1/16 sec. cor. of sec. 16.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	C S 1/16 | S 16 C
	1978

163

Subdivision of Section 16, T. 16 S., R. 7 E.,
Salt Lake Meridian, Utah

CHAINS	
	Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.
	from which
	A sandstone ledge, 12 ft. high, bears N. 3° 28' E., 6½ lks. dist., to a cross chiseled in south face, mkd. X BO.
39.65	Point selected for the witness cor. to the center ¼ sec. cor. of sec. 16.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	W C T 16 S R 7 E C 1/4 | S 16 1978
	Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.
	Cor. is located on small bench between two sandstone ledges.
40.15	True point for the center ¼ sec. cor. of sec. 16, at the intersection with E and W center line, falls on face of sandstone ledge, 10 ft. high, where it is impracticable to establish a permanent monument.
80.30	The ¼ sec. cor. of secs. 9 and 16.
	From the ¼ sec. cor. of secs. 15 and 16.
	S. 89° 50' W., on the E and W center line of sec. 16.
	Asc. over broken E slope, through scattered undergrowth.
19.93	Point for the center E 1/16 sec. cor. of sec. 16.
	Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.
	E 1/16 C ——— C S 16 1978
	Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.
	Cor. is located on steep NE slope.
39.86	The center ¼ sec. cor. of sec. 16.
79.71	The ¼ sec. cor. of secs. 16 and 17.

Subdivision of Section 16, T. 16 S., R. 7 E.,
Salt Lake Meridian, Utah

CHAINS	
	From the E 1/16 sec. cor. of secs. 16 and 21.
	N. 0° 22' W., on the N and S center line of the SE¼ of sec. 16.
	Asc. abruptly over broken S slope, through scattered undergrowth.
20.09	Point for the SE 1/16 sec. cor. at the intersection with the E and W center line of the SE¼.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	SE 1/16 S 16
	1978
	Cor. is located on N edge of old mine road, 24 lks. wide, bearing S. 51° E., and N. 51° W.
40.18	The center E 1/16 sec. cor. of sec. 16.
	From the S 1/16 sec. cor. of secs. 15 and 16.
	S. 89° 52' W., on the E and W center line of the SE¼ of sec. 16.
	Asc. over steep E slope, through scattered undergrowth.
19.92	The SE 1/16 sec. cor. of sec. 16.
39.84	The center S 1/16 sec. cor. of sec. 16.
	Subdivision of Section 17, T. 16 S., R. 7 E., Salt Lake Meridian, Utah
	From the ¼ sec. cor. of secs. 17 and 20.
	N. 0° 24' W., on the N and S center line of sec. 17.
	Desc. moderate NE slope, through scattered timber and undergrowth.
11.00	Mill Fork Canyon, drains SE; asc. over moderate SW slope, through scattered timber and undergrowth.
39.97	Point for the center ¼ sec. cor. of sec. 17, at the intersection with the E and W center line.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T 16 S R 7 E
	C 1/4 S 17
	1978

165

Subdivision of Section 17, T. 16 S., R. 7 E.,
Salt Lake Meridian, Utah

CHAINS	
	Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.
	Cor. is located south 95 lks. from base of 50 ft. high cliff, and West 13 lks. from small draw.
	Asc. over broken ledges and sheer face cliffs.
79.94	The ¼ sec. cor. of secs. 8 and 17.
	From the ¼ sec. cor. of secs. 16 and 17.
	S. 89° 20' W., on the E and W center line of sec. 17.
	Asc. abruptly over broken SE slope, through scattered timber and undergrowth.
39.93	The center ¼ sec. cor. of sec. 17.
79.00	"Mill Fork Canyon," drains SE.
79.86	The ¼ sec. cor. of secs. 17 and 18.

Subdivision of Section 21, T. 16 S., R. 7 E.,
Salt Lake Meridian, Utah

	From the ¼ sec. cor. of secs. 21 and 28.
	North, on the N and S center line of sec. 21.
	Asc. abruptly over broken ledges and sheer face cliffs.
39.78	Point for the center ¼ sec. cor. of sec. 21, at intersection with E and W center line.
	Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.
	T 16 S R 7 E
	C 1/4 S 21
	1978
	Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.
76.50	Mill Fork Canyon, 30 lks. wide, course SE.
77.50	Dirt road, 20 lks. wide, bears E and W.
79.56	The ¼ sec. cor. of secs. 16 and 21.

☆GPO 1980—680-288/121

Subdivision of Section 21 T. 16 S., R. 7 E.,
Salt Lake Meridian, Utah

CHAINS	
	From the ¼ sec. cor. of secs. 21 and 22.
	S. 89° 27' W., on the E and W center line of sec. 21.
	Asc. over broken SE slope, through scattered undergrowth.
39.94	The center ¼ sec. cor. of sec. 21.
79.88	The ¼ sec. cor. of secs. 20 and 21.

Subdivision of Section 22, T. 16 S., R. 7 E.,
Salt Lake Meridian, Utah

	From the ¼ sec. cor. of secs. 22 and 27, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. as described in the official record of the 1961 resurvey.
	N. 0° 08' W., on the N and S center line of sec. 22.
	Desc. over moderate NW slope, through scattered timber and undergrowth.
4.00	"Rilda Canyon", 30 lks. wide, course NE.
5.50	Dirt road, 20 lks. wide, bears N. 53° E. and S. 53° W.
19.96	Point for the center S 1/16 sec. cor. of sec. 22.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	C S 1/16 | S 22 C 1978
	Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.
39.92	Point for the center ¼ sec. cor. of sec. 22, at the intersection with E and W center line.
	Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd.
	T 16 S R 7 E C 1/4 S 22 1978
	Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.
41.50	Dirt road, 15 lks. wide, bears NW and SE.

167

Subdivision of Section 22, T. 16 S., R. 7 E.,
Salt Lake Meridian, Utah

CHAINS	
43.00	Huntington Creek, 50 lks. wide, course SE.
48.00	Highway No. 31, 45 lks. wide, bears N. 35° W. and S. 35° E.
59.88	Point for the center N 1/16 sec. cor. of sec. 22.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	C N 1/16 | S 22 C 1973
	Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.
	Cor. is located East 2 chs. from East edge of asphalt road.
79.84	The ¼ sec. cor. of secs. 15 and 22.
	From the ¼ sec. cor. of secs. 22 and 23.
	S. 89° 36' W., on the E and W center line of sec. 22.
	Asc. across broken ledges and steep S slope, through scattered undergrowth.
13.00	Dirt road, bears N and S.
15.50	Trail Canyon, course S.
16.50	Dirt road, 30 lks. wide, bears N and S.
19.99	Point for the center E 1/16 sec. cor. of sec. 22.
	Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, to top of brass cap, mkd.
	E 1/16 C ——— S 22 ——— C 1978
	Set a red aluminum post, 6 ft. long, with attention sign on top, alongside boulder, 9½ x 7 x 4 ft., located 6 ft. W of cor.
34.50	Highway No. 31, 45 lks. wide, bears N. 35° W. and S. 35° E.
36.00	"Huntington Creek", 50 lks. wide, course SE.
39.00	Dirt road, 15 lks. wide, bears NW and SE.

Subdivision of Section 22, T. 16 S., R. 7 E.,
Salt Lake Meridian, Utah

CHAINS	
39.98	The center ¼ sec. cor. of sec. 22.
59.97	Point for the center W 1/16 sec. cor. of sec. 22. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. W 1/16 C ——— C S 22 1978 Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post. Cor. is located South 85 lks. from main draw that drains N. 70° E., and situated on steep N slope.
79.96	The ¼ sec. cor. of secs. 21 and 22.
	From the E 1/16 sec. cor. of secs. 22 and 27, monumented with an iron post, 2½ ins. diam., firmly set projecting 6 ins. above ground, with brass cap mkd. as described in the official record of the 1961 resurvey. N. 0° 07' W., on the N and S center line of the SE¼ of sec. 22. Over bottom of Huntington, Rilda, and Trail Canyons, through scattered undergrowth.
20.08	Point for the SE 1/16 sec. cor. at the intersection with the E and W center line of the SE¼. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. SE 1/16 S 22 1978 Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post. Cor. is located at East edge of sagebrush flat and at base of NW slope.
29.00	Huntington Creek, 50 lks. wide, course SE.
32.50	Highway No. 31, 45 lks. wide, bears S. 79° E. and N. 79° W.
40.16	The center E 1/16 sec. cor. of sec. 22.
	From the S 1/16 sec. cor. of secs. 22 and 23. S. 89° 56' W., on the E and W center line of the SE¼ of sec. 22.

CHAINS	
	Over bottom of Huntington, Rilda, and Trail Canyons, through scattered undergrowth.
1.70	Highway No. 31, 45 lks. wide, curving from NW to SW.
3.50	Huntington Creek, 50 lks. wide, course SE.
19.98	The SE 1/16 sec. cor. of sec. 22.
24.00	"Rilda Canyon", course NE.
26.00	Dirt road, 20 lks. wide, bears N. 40° E. and S. 40° W.
39.96	The center S 1/16 sec. cor. of sec. 22.
	From the center W 1/16 sec. cor. of sec. 22.
	N. 0° 10' W., on the N and S center line of the NW¼ of sec. 22.
	Desc. over steep N slope, through scattered undergrowth.
19.84	Point for the NW 1/16 sec. cor. at the intersection with the E and W center line of the NW¼ of sec. 22.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	NW 1/16 S 22
	1978
	Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.
	Cor. is located on grassy slope N. 40° E., and W, 1.80 chs. from top edge of sandstone cliffs.
32.00	Mill Fork Canyon, 30 lks. wide, course NE.
34.50	Dirt road, 20 lks. wide, bears E and W.
39.68	The W 1/16 sec. cor. of secs. 15 and 22.
	From the center N 1/16 sec. cor. of sec. 22.
	S. 89° 16' W., on the E and W center line of the NW¼ of sec. 22.
	Desc. gradually across W slope, through scattered undergrowth.
2.20	Highway No. 31, 45 lks. wide, bears N and S.
4.00	"Huntington Creek", 50 lks. wide, course S.
7.50	Dirt road, 20 lks. wide, bears N and S.
20.00	The NW 1/16 sec. cor. of sec. 22.
40.00	The N 1/16 sec. cor. of secs. 21 and 22.

☆ GPO 1980—680-288/121

CHAINS	
	Subdivision of Section 24, T. 16 S., R. 7 E., Salt Lake Meridian, Utah
	From the ¼ sec. cor. of secs. 24 and 25.
	North, on the N and S center line of sec. 24.
	Desc. over steep NW slope, through scattered timber and undergrowth.
39.98	Point for the center ¼ sec. cor. of sec. 24, at the intersection with E and W center line.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T 16 S R 7 E C 1/4 S 24 1978
	Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.
59.00	Spur, projects SW; desc. over broken ledges and sheer face cliffs.
79.96	The ¼ sec. cor. of secs. 13 and 24.
	From the ¼ sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp., heretofore described.
	N. 89° 30' W., on the E and W center line of sec. 24.
	Desc. abruptly over broken ledges and sheer face cliffs.
19.97	Point for the center E 1/16 sec. cor. of sec. 24.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	E 1/16 C ——— C S 24 1978
	Cor. is located on small bench between two sandstone cliffs.
39.94	The center ¼ sec. cor. of sec. 24.
67.00	Bear Creek Canyon, course S; asc. over broken ledges and sheer face cliffs.
79.88	The ¼ sec. cor. of secs. 23 and 24.

CHAINS	
	Subdivision of Section 25, T. 16 S., R. 7 E., Salt Lake Meridian, Utah
	From the ¼ sec. cor. of secs. 25 and 36.
	N. 0° 02' E., on the N and S center line of sec. 25.
	Over steep NW slope, through scattered stands of native grasses and broken ledges.
40.08	Point for the center ¼ sec. cor. of sec. 25, at the intersection with E and W center line.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T 16 S R 7 E
	C 1/4 S 25
	1978
	Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.
80.10	The ¼ sec. cor. of secs. 24 and 25.
	From the ¼ sec. cor. of secs. 25 and 30, on the E. bdy. of Tp., heretofore described.
	S. 89° 52' W., on the E and W center line of sec. 25.
	Desc. over steep NW slope, through scattered stands of native grasses and undergrowth.
39.80	The center ¼ sec. cor. of sec. 25.
80.09	The ¼ sec. cor. of secs. 25 and 26.
	Subdivision of Section 27, T. 16 S., R. 7 E., Salt Lake Meridian, Utah
	From the center ¼ sec. cor. of sec. 27, monumented with an iron post, 2½ ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd. as described in the official record of the 1961 resurvey.
	S. 89° 57' W., on the E and W center line of sec. 27.
	Desc. over steep NW slope, through scattered timber and undergrowth.
19.93	Point for the center W 1/16 sec. cor. of sec. 27.

Subdivision of Section 27, T. 16 S., R. 7 E.,
Salt Lake Meridian, Utah

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd. W 1/16 C ——— C S 27 1978 Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.
39.86	The ¼ sec. cor. of secs. 27 and 28.
	From the center W 1/16 sec. cor. of sec. 27. N. 0° 02' W., on the N and S center line of the NW¼ of sec. 27. Desc. gradually across steep W slope through scattered undergrowth.
19.72	Point for the NW 1/16 sec. cor. at the intersection with the E and W center line of the NW¼ of sec. 22. Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. NW 1/16 S 22 1978
32.00	"Rilda Canyon", 30 lks. wide, course NE.
34.00	Dirt road, 20 lks. wide, bears N. 60° E. and S. 60° W.
39.46	The W 1/16 sec. cor. of secs. 22 and 27.
	From the center N 1/16 sec. cor. of sec. 27, monumented with an iron post, 2½ ins. diam., firmly set in a mound of stone, 2½ ft. base, to top of brass cap mkd. as described in the official record of the 1961 resurvey. N. 89° 52' W., on the E and W center line of the NW¼ of sec. 27. Asc. abruptly over steep E slope.
19.96	The NW 1/16 sec. cor. of secs. 27.
39.91	The N 1/16 sec. cor. of secs. 27 and 28.
	Subdivision of Section 28, T. 16 S., R. 7 E., Salt Lake Meridian, Utah
	From the ¼ sec. cor. of secs. 28 and 33. N. 0° 18' E., on the N and S center line of sec. 28. Desc. abruptly over NE slope, through broken ledges and scattered stands of timber.

CHAINS	
39.69	Point for the center ¼ sec. cor. of sec. 28, at the intersection with the E and W center line. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd. T 16 S R 7 E C 1/4 S 28 1978 Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.
42.50	"Rilda Canyon", 30 lks. wide, course NE.
44.50	Dirt road, 20 lks. wide, bears N. 84° E. and S. 84° W.
59.60	Point for the center N 1/16 sec. cor. of sec. 28. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. C N 1/16 | S 28 C 1978 Set a red aluminum post, 6 ft. long, with attention sign on top, alongside the iron post.
79.51	The ¼ sec. cor. of secs. 21 and 28.
	From the ¼ sec. cor. of secs. 27 and 28. S. 88° 38' W., on the E and W center line of sec. 28. Asc. over NE slope, through scattered timber and undergrowth.
40.36	The center ¼ sec. cor. of sec. 28.
81.64	The ¼ sec. cor. of secs. 28 and 29.
	Subdivision of Section 34, T. 16 S., R. 7 E., Salt Lake Meridian, Utah
	From the ¼ sec. cor. of secs. 3 and 34, on the S. bdy. of the Tp., heretofore described. N. 0° 06' W., on the N and S center line of sec. 34.

Subdivision of Section 34, T. 16 S., R. 7 E.,
Salt Lake Meridian, Utah

CHAINS	
	Desc. abruptly over N slope, through scattered timber and undergrowth.
21.00	North Fork of Meetinghouse Canyon, course E; asc. abruptly over broken ledges and sheer faced cliffs.
38.88	True point for the center ¼ sec. cor. of sec. 34, at intersection with E and W center line, falls on face of sandstone ledge, where it is impracticable to establish a permanent monument.
39.18	Point selected for the witness cor. to the center ¼ sec. cor. of sec. 34. Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd. W C C 1/4 | S 34 ↓ 1978
77.76	The ¼ sec. cor. of secs. 27 and 34, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground with brass cap mkd. as described in the official record of the 1961 resurvey.
	From the true point for the ¼ sec. cor. of secs. 34 and 35, from which its witness cor. bears N. 0°08' W., 1.20 chs. dist., monumented with an iron post, 2½ ins. diam., projecting 14 ins. above ground and in a mound of stone, with brass cap mkd. as described in the official record of the 1961 resurvey. S. 88° 47' W., on the E and W center line of sec. 34. Over steep S slope through broken ledges and sheer face cliffs.
39.85	True point for the center ¼ sec. cor. of sec. 34.
79.68	The ¼ sec. cor. of secs. 33 and 34.

General Description

A considerable variety of land and soil is found in this township. The elevation varies from about 6,400 ft. above sea level in the southeast corner of the township to about 10,000 ft. above sea level along the W. bdy. of the township. Most of the township is rough and broken except the northeast corner which is rolling mountain top. There is some gentle rolling land in the bottom of Huntington Canyon, adjacent the Huntington Creek, which flows through the township in a southeast direction.

There is thick aspen, pine and fir timber on the north slopes on the high ridges, with white cedar and pinon scattered at the lower elevations.

T. 16 S., R. 7 E., Salt Lake Meridian, Utah

	CHAINS		
		The township is accessible by Utah State Highway No. 31, which enters through the E. bdy. of sec. 36 and exists through the N. bdy. of sec. 4. There are numerous gravel and dirt roads in the side canyons serving the working coal mines located in sections 16 and 22, and the non-working coal mines in sections 5, 25, 28, and 34. Part of Utah Power and Light Companies, Huntington Power Plant operation is in section 36.	

Form 9180-8
(March 1969)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Frank C. Profaizer	Supvy. Surveying Technician
Donald A. Buhler	Surveying Technician
Kevin Hinckley	Surveying Technician
Bryan Seibold	Surveying Technician
Donzil Q. Worthington	Surveying Technician
Kathyrn Johnson	Survey Aid
Ellis Peterson	Survey Aid

177

CERTIFICATE OF SURVEY

(I) (~~We~~) Jerry L. Thomas, Supervisory Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 6th day of April, 1976, (I) (~~We~~) have dependently resurveyed the south boundary of T. 15 S., R. 7 E., (Third Standard Parallel South), the west boundary of T. 16 S., R. 8 E., the east boundary of T. 16 S., R. 6 E., a portion of the south boundary, a portion of the subdivisional lines, and the subdivision of 14 sections of T. 16 S., R. 7 E.,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), (~~us~~) and under (my) (~~our~~) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

April 6, 1979
(Date)

Jerry L. Thomas
(Cadastral Surveyor)
Supervisory

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
~~Washington, D.C.~~
Denver, Colorado

The foregoing field notes of the dependent resurvey of the south boundary of T. 15 S., R. 7 E., (Third Standard Parallel South), the west boundary of T. 16 S., R. 8 E., the east boundary of T. 16 S., R. 6 E., a portion of the south boundary, a portion of the subdivisional line, and the subdivision of 14 sections of T. 16 S., R. 7 E., Salt Lake Meridian, Utah

executed by Jerry L. Thomas, Supervisory Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

MAR 10 1981
(Date)

J. D. Voorhees
~~(Chief, Division of Cadastral Survey)~~
Chief, Cadastral Survey Examination and Approval Staff

~~CERTIFICATE OF TRANSCRIPT~~

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

(Date)

Form 9180-6
(March 1977)

R601

178

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF THE WEST BOUNDARY OF T. 10 S., R. 22 E.,

THE EAST 4 MILES OF THE SOUTH BOUNDARY

(SECOND STANDARD PARALLEL SOUTH)

THE

NORTH BOUNDARY AND A PORTION OF THE

SUBDIVISIONAL LINES

OF

TOWNSHIP 10 SOUTH, RANGE 21 EAST

Of the Salt Lake Meridian,

In the State of Utah.

EXECUTED BY

Jerry L. Thomas Supervisory Cadastral Surveyor

Under special instructions dated May 26, 1977, approved May 27, 1977,

_____, which provided for the surveys included under ~~U.S. Survey~~/Group Number 569, and assignment instructions dated May 27, 1977.

Survey commenced May 28, 19 77

Survey completed August 12, 19 77

INDEX DIAGRAM

Township 10 S., Range 21 E.,

27	25	24	22	20	19	
6 69 68	5 62 67	4 54 61	3 45 53	2 37 45	1 36	17
7 67 66	8 60 65	9 52 60	10 44 52	11 35 43	12 35	15
18 64 64	17 59 63	16 51 58	15 42 50	14 34 42	13 33	14
19	20 57	21 49 56	22 41 48	23 32 40	24 31	12
30	29	28 48 56	27 39 47	26 30 39	25 30	10
31	32 54	33 46 2	34 38 3	35 29 5	36 6	9

Township 10 South, Range 21 East, Salt Lake Meridian, Utah

CHAINS

The history of surveys of Township 10 South, Range 21 East, Salt Lake Meridian, Utah, is as follows:

The west boundary, (Green River Guide Meridian), was surveyed by A. D. Ferron in 1879. The south boundary, (Second Standard Parallel South), the east and north boundaries, the subdivisional lines and the subdivision of sections were surveyed, and the west boundary (Green River Guide Meridian), was resurveyed by D. G. Major in 1882. The north and east boundaries were resurveyed by A. R. Talamantes and H. D. Heist in 1904. The south boundary, (Second Standard Parallel South), was retraced by A. Nelson and R. W. Hodge in 1923. The west boundary, (Green River Guide Meridian), was resurveyed by H. W. Miller in 1928.

The following field notes describe the dependent resurvey of the west boundary of T. 10 S., R. 22 E., the east 4 miles of the south boundary, (Second Standard Parallel South), the north boundary and a portion of the subdivisional lines of T. 10 S., R. 21 E., Salt Lake Meridian, Utah.

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 569, Utah, dated May 26, 1977.

Preliminary to the resurvey the lines of the original survey were retraced and a search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The direction of lines were determined by means of lines projected by fore- and backsights from azimuths obtained by direct solar observations or observations on Polaris.

The geographic position of the southeast corner of the township as determined by ties to the United States Coast and Geodetic Survey triangulation station "Two Water", located in sec. 1, is as follows:

Latitude 39° 53.8' N. Longitude 109° 29.3' W.

The mean magnetic declination is 14° 30' E.

Dependent Resurvey, Second Standard Parallel South, S. Bdy., T. 10 S., R. 21 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by D. G. Major in 1882, and the Retracement by A. Nelson and R. W. Hodge in 1923

Dependent Resurvey, Second Standard Parallel South,
S. Bdy., T. 10 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
	Beginning at the standard cor. of secs. 32 and 33, monumented with a sandstone, 30 x 9 x 5 ins., firmly set in a mound of stone, mkd. SC and 6 grooves on N, 4 grooves on E, and 2 grooves on W face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.
	S C T 10 S R 21 E | S 32 | S 33 1977
	Deposit the mkd. stone alongside the iron post.
	Cor. is located near bottom of SW slope, about 2 chs. NE of wash, draining N. 30° W.
	S. 89° 58' E., on the S. bdy. of sec. 33.
	Over slightly broken desert land through scattered shadscale and native grasses; asc. over SW slope.
20.18	The stan. W 1/16 sec. cor. of sec. 33, monumented with a sandstone, 32 x 14 x 3 ins., firmly set, projecting 25 ins. above ground, mkd. SC 1/16 on N face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a collar of stone, with brass cap mkd.
	S C T 10 S R 21 E W 1/16 S 33 1977
	Deposit the mkd. stone alongside the iron post.
	S. 89° 59' E., beginning new measurement.
	Along gentle N slope.
20.22	The stan. ¼ sec. cor. of sec. 33, monumented with a sandstone, 14 x 6 x 3 ins., firmly set, projecting 7 ins. above ground, mkd. SC ¼ on N face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

U.S. Government Printing Office-1978-778-206/433

CHAINS

S C
T 10 S R 21 E

¼ S 33

1977

Deposit the mkd. stone alongside the iron post.

N. 89° 51' E., beginning new measurement.

Desc. over gentle NE slope.

20.21 The stan. E 1/16 sec. cor. of sec. 33, monumented with a sandstone, 26 x 16 x 3 ins., firmly set, projecting 14 ins. above ground, mkd. SC 1/16 on N face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

S C
T 10 S R 21 E

E 1/16 S 33

1977

Deposit the mkd. stone alongside the iron post.

S. 89° 55' E., beginning new measurement.

Desc. over E slope.

20.17 The stan. cor. of secs. 33 and 34, monumented with a sandstone, 26 x 8 x 3 ins., firmly set, projecting 14 ins. above ground, mkd. SC on N, 3 notches on E and W edges.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.

S C
T 10 S R 21 E

S 33 | S 34

1977

Deposit the mkd. stone alongside the iron post.

Cor. is located at head of small draw, draining NE.

N. 89° 59' E., on the S. bdy. of sec. 34.

Along gentle N slope through scattered shadscale and native grasses.

CHAINS	
20.16	The stan. W 1/16 sec. cor. of sec. 34, monumented with a sandstone, 20 x 7 x 5 ins., firmly set, projecting 10 ins. above ground, mkd. SC 1/16 on N face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd. S C T 10 S R 21 E W 1/16 S 34 1977 Deposit the mkd. stone alongside the iron post.
	S. 89° 59' E., beginning new measurement. Desc. over gentle NE slope.
20.15	The stan. ¼ sec. cor. of sec. 34, monumented with a sandstone, 20 x 8 x 4 ins., firmly set, projecting 10 ins. above mound of stone, mkd. SC ¼ on N face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., over a cross (X) on solid sandstone, in a mound of stone, 4 ft. base, to top of brass cap, mkd. S C T 10 S R 21 E ¼ S 34 1977 Deposit the mkd. stone alongside the iron post.
	S. 89° 57' E., beginning new measurement. Over nearly level land.
20.28	The stan. E 1/16 sec. cor. of sec. 34, monumented with a sandstone, 20 x 8 x 4 ins., firmly set in a mound of stone, mkd. SC 1/16 on N face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., over cross (X) in solid sandstone, in a mound of stone, 4 ft. base, to top of brass cap, mkd. S C T 10 S R 21 E E 1/16 S 34 1977 Deposit the mkd. stone alongside the iron post.

U.S. Government Printing Office-1978-778-206/433

CHAINS	
	S. 89° 50' E., beginning new measurement.
	Desc. over gentle NE slope.
20.21	The stan. cor. of secs. 34 and 35, monumented with a sandstone, 27 x 10 x 7 ins., firmly set, projecting 17 ins. above ground, mkd. 2 notches on E edge, 4 notches on W edge, and SC on N face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base, to top of brass cap, mkd.
	S C T 10 S R 21 E S 34 | S 35 1977
	Deposit the mkd. stone alongside the iron post.
	Cor. is located in bottom of draw, draining W.
	S. 89° 59' E., on the S. bdy. of sec. 35.
	Over slightly broken land through scattered shadscale and native grasses; along gentle N slope in bottom of draw.
20.22	The stan. W 1/16 sec. cor. of sec. 35, monumented with a sandstone, 20 x 6 x 6 ins., firmly set, projecting 10 ins. above ground, mkd. SC 1/16 on N face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top of brass cap, mkd.
	S C T 10 S R 21 E W 1/16 S 35 1977
	Deposit the mkd. stone alongside the iron post.
	N. 89° 59' E., beginning new measurement.
	Over gently rolling land through scattered small sagebrush and native grasses.
7.10	Bulldozed road, bears N and S.
20.19	The stan. ¼ sec. cor. of sec. 35, monumented with a sandstone, 20 x 8 x 3 ins., firmly set, projecting 10 ins. above ground, mkd. SC ¼ on N face.

CHAINS	
	At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd. S C T 10 S R 21 E ¼ S 35 1977 Deposit the mkd. stone alongside the iron post.
	S. 89° 55' E., beginning new measurement. Over nearly level land.
20.18	The stan. E 1/16 sec. cor. of sec. 35, monumented with a sandstone, 25 x 8 x 8 ins., firmly set, projecting 12 ins. above ground, mkd. SC 1/16 on N face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. S C T 10 S R 21 E E 1/16 S 35 1977 Deposit the mkd. stone alongside the iron post. Raise a mound of stone, 3½ ft. base, 1½ ft. high, N of iron post.
	S. 89° 45' E., beginning new measurement. Desc. over gentle E slope.
20.52	The stan. cor. of secs. 35 and 36, monumented with a sandstone, 30 x 8 x 6 ins., firmly set in a mound of stone, mkd. 1 notch on E and 5 notches on W edges, and SC on N face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd. S C T 10 S R 21 E | S 35 | S 36 1977 Deposit the mkd. stone alongside the iron post.

U.S. Government Printing Office-1978-778-206/433

CHAINS	
	East, on the S. bdy. of sec. 36.
	Over rolling and broken land through scattered shadscale and native grasses; asc. over gradual NW slope.
1.00	Top of ridge, bears NE and SW; desc. over SE slope.
19.56	The stan. W 1/16 sec. cor. of sec. 36, monumented with a sandstone, 18 x 4 x 4 ins., firmly set, projecting 9 ins. above ground, mkd. SC 1/16 on N face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.
	S C T 10 S R 21 E W 1/16 S 36 1977
	Deposit the mkd. stone alongside the iron post.
	Cor. is located 125 lks. W of wash in bottom of canyon.
	East, beginning new measurement.
	Desc. over gradual E slope.
1.25	Bottom of Sand Wash, 12 ins. deep, 30 lks. wide, in bottom of canyon, drains NE; asc. over ledgy W slope.
20.23	The stan. ¼ sec. cor. of sec. 36, monumented with a sandstone, 18 x 6 x 3 ins., firmly set, projecting 9 ins. above ground, mkd. SC ¼ on N face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	S C T 10 S R 21 E ¼ S 36 1977
	Deposit the mkd. stone alongside the iron post.
	S. 89° 59' E., beginning new measurement.
	Over gentle rolling land.
20.61	The stan. E 1/16 sec. cor. of sec. 36, monumented with a sandstone, 12 x 12 x 6 ins., firmly set in a mound of stone, mkd. SC 1/16 on N face.
	At the corner point

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.

S C
T 10 S R 21 E

E 1/16 S 36

1977

Deposit the mkd. stone alongside the iron post.

N. 88° 47' E., beginning new measurement.

Over gentle rolling land.

20.39 The stan. cor. of T. 10 S., R. 21 E., only, monumented with a sandstone, 20 x 8 x 8 ins., firmly set in a mound of stone, badly weather worn with no visible marks. This position is accepted as the best available evidence of the original corner.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.

S C
T 10 S R 21 E
S 36

1977

Deposit the unmkd. stone alongside the iron post.

Cor. is located near bottom of small branch gulch, draining NE into a large main draw, draining N.

From this point the stan. cor. of T. 10 S., R. 22 E., monumented with a limestone, 24 x 9 x 8 ins., firmly set, projecting 12 ins. above ground, mkd. 6 notches on N, S, and E edges, bears N. 2° 11' E., 8.27 chs. dist.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.

S C
T 10 S
R 22 E
S 31

1977

Deposit the mkd. stone alongside the iron post.

CHAINS

Dependent Resurvey of the West Boundary,
T. 10 S., R. 22 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
D. G. Major in 1882 and the Resurvey
by A. R. Talamantes and H. D. Heist in 1904

From the stan. cor. of T. 10 S., R. 22 E., heretofore described.

N. 0° 31' W., on the W. bdy. of sec. 31.

Over broken desert land through scattered shadscale and native grasses; desc. over gradual NE slope.

12.06 Point for the S 1/16 sec. cor. of sec. 36, T. 10 S., R. 21 E., at proportionate distance; there is no remaining evidence of the original corner.

Corner point not monumented.

32.39 Point for the ¼ sec. cor. of sec. 36, T. 10 S., R. 21 E., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 10 S
R 21 E | R 22 E
¼ |
S 36 |

1977

Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.

39.71 The ¼ sec. cor. of sec. 31, monumented with a sandstone, 26 x 12 x 4 ins., firmly set, projecting 12 ins. above ground, dimly mkd. ¼ on W face, and a scattered mound of stone to W.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.

T 10 S
R 21 E | R 22 E
| ¼
| S 31

1977

Deposit the mkd. stone alongside the iron post.

CHAINS	
	N. 0° 07' W., beginning new measurement.
	Desc. over NE slope.
13.01	Point for the N 1/16 sec. cor. of sec. 36, T. 10 S., R. 21 E., at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
33.34	Point for the cor. of secs. 25 and 36, T. 10 S., R. 21 E., at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., set over a cross (X) chiseled in solid sandstone, in a mound of stone, 4½ ft. base, to top of brass cap, mkd. T 10 S R 21 E R 22 E S 25 | S 31 S 36 | 1977
	Cor. is located on steep W slope approximately 50 ft. below the rim of mesa.
	Asc. over rocky SW slope.
40.27	The cor. of secs. 30 and 31, monumented with a sandstone, 24 x 10 x 6 ins., firmly set, projecting 12 ins. above ground, mkd. 5 notches on N and 1 notch on S edges.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd. T 10 S R 21 E R 22 E S 25 | S 30 S 31 | 1977
	Deposit the mkd. stone alongside the iron post.
	N. 0° 31' W., on the W. bdy. of sec. 30.
	Over nearly level mesa top, through scattered shadscale and native grasses.
13.40	Point for the S 1/16 sec. cor. of sec. 25, T. 10 S., R. 21 E., at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
33.73	Point for the ¼ sec. cor. of sec. 25, T. 10 S., R. 21 E., at proportionate distance; there is no remaining evidence of the original corner.

☆ U.S. Government Printing Office-1978-778-206/433

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 10 S R 21 E R 22 E ¼ | S 25 | 1977
	Cor. is located on W slope, 40 lks. E of wash draining N. 1 ch., thence W.
39.97	The ¼ sec. cor. of sec. 30, monumented with a sandstone, 20 x 10 x 8 ins., firmly set, projecting 10 ins. above ground, mkd. ¼ on W face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd. T 10 S R 21 E R 22 E | ¼ | S 30 1977
	Deposit the mkd. stone alongside the iron post.
	N. 0° 28' W., beginning new measurement.
	Desc. over rocky N slope.
14.09	Point for the N 1/16 sec. cor. of sec. 25, T. 10 S., R. 21 E., at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
34.42	Point for the cor. of secs. 24 and 25, T. 10 S., R. 21 E., at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base, to top of brass cap, mkd. T 10 S R 21 E R 22 E S 24 / S 25 | S 30 1977
39.45	The cor. of secs. 19 and 30, monumented with a sandstone, 20 x 10 x 5 ins., firmly set, projecting 10 ins. above ground, mkd. 4 notches on N and 2 notches on S edges.

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.

T 10 S
R 21 E R 22 E

S 24 | S 19
| S 30

1977

Deposit the mkd. stone alongside the iron post.

N. 0° 22' W., along the W. bdy. of sec. 19.

Over broken desert land through scattered shadscale and native grasses; asc. over SW slope.

15.30 Point for the S 1/16 sec. cor. of sec. 24, T. 10 S., R. 21 E., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 5 ft. base, to top of brass cap, mkd.

T 10 S
R 21 E R 22 E

S 1/16 |
S 24 |

1977

Corner is located 30 lks. N of ravine, drains W.

35.05 Improved dirt road, bears NW to Ouray and SE to Bitter Creek gas field.

35.63 Point for the ¼ sec. cor. of sec. 24, T. 10 S., R. 21 E., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 10 S
R 21 E R 22 E

¼ |
S 24 |

1977

Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.

CHAINS	
40.45	The ¼ sec. cor. of sec. 19, monumented with a sandstone, 18 x 10 x 6 ins., firmly set, projecting 8 ins. above mound of stone, mkd. ¼ on W face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 10 S R 21 E R 22 E | ¼ | S 19 1977 Deposit the mkd. stone alongside the iron post. Raise a mound of stone, 2½ ft. base, 1½ ft. high, E of cor.
	N. 0° 27' W., beginning new measurement. Desc. over N slope.
15.51	Point for the N 1/16 sec. cor. of sec. 24, T. 10 S., R. 21 E., at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
35.84	Point for the cor. of secs. 13 and 24, T. 10 S., R. 21 E., at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 6 ft. base, to top of brass cap, mkd. T 10 S R 21 E R 22 E S 13 / S 24 | S 19 1977 Cor. is located on a spur, bearing NW. Slope changes; asc. over steep S slope.
39.92	The cor. of secs. 18 and 19, monumented with a sandstone, 24 x 8 x 5 ins., firmly set, projecting 12 ins. above ground, mkd. 3 notches on N and S edges. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.

193

Dependent Resurvey of the West Boundary,
T. 10 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
	T 10 S R 21 E R 22 E S 13 | S 18 | S 19 1977 Deposit the mkd. stone alongside the iron post.
	N. 0° 19' W., along the W. bdy. of sec. 18. Over broken desert land through scattered shadscale and native grasses; asc. over steep S slope.
16.25	Point for the S 1/16 sec. cor. of sec. 13, T. 10 S., R. 21 E., at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
36.58	Point for the ¼ sec. cor. of sec. 13, T. 10 S., R. 21 E., at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 17 ins. in the ground to bedrock, in a collar of stone, with brass cap mkd. T 10 S R 21 E R 22 E ¼ | S 13 | 1977 Cor. is located on small spur, sloping NW.
40.15	The ¼ sec. cor. of sec. 18, monumented with a sandstone, 24 x 8 x 5 ins., firmly set, projecting 10 ins. above ground, mkd. ¼ on W face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 10 S R 21 E R 22 E | ¼ | S 18 1977 Deposit the mkd. stone alongside the iron post.

U.S. Government Printing Office-1978-778-206/433

Dependent Resurvey of the West Boundary,
T. 10 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
	N. 0° 18' W., beginning new measurement.
	Along W slope.
16.76	Point for the N 1/16 sec. cor. of sec. 13, T. 10 S., R. 21 E., at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
18.00	Bottom of Sand Wash, 12 ins. deep, 40 lks. wide, drains N. 35° E.; thence along E slope.
24.00	Sand Wash, drains N. 35° W.
30.00	Sand Wash, drains N. 35° E.
37.09	Point for the cor. of secs. 12 and 13, T. 10 S., R. 21 E., at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, to top of brass cap, mkd.
	T 10 S R 21 E R 22 E S 12 | S 13 | S 18 1977
39.88	The cor. of secs. 7 and 18, monumented with a sandstone, 24 x 6 x 5 ins., projecting 10 ins. above ground, mkd. 4 notches on S and 2 notches on N edges.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.
	T 10 S R 21 E R 22 E S 12 | S 7 | S 18 1977
	Deposit the mkd. stone alongside the iron post.
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, E of cor.
	N. 0° 34' W., along the W. bdy. of sec. 7.
	Over broken desert land through scattered shadscale and native grasses; desc. over NE slope.
11.00	Sand Wash, 12 ins. deep, 40 lks. wide, drains NW.

CHAINS	
17.54	Point for the S 1/16 sec. cor. of sec. 12, T. 10 S., R. 21 E., at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
37.87	Point for the ¼ sec. cor. of sec. 12, T. 10 S., R. 21 E., at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 10 S R 21 E R 22 E ¼ S 12 1977 Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor. Cor. is located on gentle NW slope, 1 ch. N of base of bench.
43.63	The ¼ sec. cor. of sec. 7, monumented with a sandstone, 16 x 8 x 8 ins., firmly set, projecting 6 ins. above ground, mkd. ¼ on W face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam, 14 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 10 S R 21 E R 22 E ¼ S 7 1977 Deposit the mkd. stone alongside the iron post.
	—————————— N. 0° 15' W., beginning new measurement. Desc. over gentle NW slope.
14.57	Point for the N 1/16 sec. cor. of sec. 12, T. 10 S., R. 21 E., at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., on solid sandstone, in a mound of stone, 5 ft. base, to top of brass cap, mkd.

CHAINS	
	T 10 S R 21 E R 22 E N 1/16 | S 12 | 1977
	Cor. is located on W slope on sandstone ledge, 10 ft. high, bears S and NE.
34.90	Point for the cor. of secs. 1 and 12, T. 10 S., R. 21 E., at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.
	T 10 S R 21 E R 22 E S 1 | S 7 S 12 | 1977
	Cor. is located on N slope of spur, bears E and W.
37.16	The cor. of secs. 6 and 7, monumented with a mound of stone. This position is harmoniously related to existing original cors., and is accepted as the best available evidence of the original cor. position.
	At the corner point (center of mound)
	Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.
	T 10 S R 21 E R 22 E S 1 | S 6 | S 7 1977
	N. 0° 28' W., along the W. bdy. of sec. 6.
	Over broken desert land through scattered shadscale and native grasses; desc. along W slope.
18.07	Point for the S 1/16 sec. cor. of sec. 1, T. 10 S., R. 21 E., at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
38.40	Point for the ¼ sec. cor. of sec. 1, T. 10 S., R. 21 E., at proportionate distance; there is no remaining evidence of the original corner.

197

Dependent Resurvey of the West Boundary,
T. 10 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 10 S R 21 E R 22 E ¼ S 1 1977 Cor. is located on steep NE slope.
39.64	The ¼ sec. cor. of sec. 6, monumented with a sandstone, 24 x 8 x 7 ins., firmly set, projecting 10 ins. above ground, mkd. ¼ on W face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 10 S R 21 E R 22 E ¼ S 6 1977 Deposit the mkd. stone alongside the iron post. Cor. is located 15 lks. N of draw, drains N. 10° W.
	N. 0° 29' W., beginning new measurement. Asc. along W slope.
5.00	Sand Wash, 12 ins. deep, 40 lks. wide, drains E from W.
10.00	Sand Wash, drains N. 30° W.
19.09	Point for the N 1/16 sec. cor. of sec. 1, T. 10 S., R. 21 E., at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
20.00	Leave Sand Wash, drains NE from SW.
40.56	The cor. of Tps. 9 and 10 S., Rs. 21 and 22 E., monumented with a sandstone, 30 x 12 x 12 ins., firmly set, projecting 20 ins. above ground and in a scattered mound of stone, mkd. 6 notches on N, S, E, and W, edges. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.

U.S. Government Printing Office-1978-778-206/433

Dependent Resurvey of the West Boundary,
T. 10 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
	T 9 S R 21 E R 22 E S 36 | S 31 S 1 | S 6 T 10 S 1977 Deposit the mkd. stone alongside the iron post.

Dependent Resurvey of the North Boundary,
T. 10 S., R. 21 E., Salt Lake Meridian,Utah

CHAINS	
	N. 88° 46' W., along the N. bdy. of sec. 1.
	Over broken desert land through scattered shadscale and native grasses; asc. over NE slope.
20.39	Point for the E 1/16 sec. cor. of sec. 1, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
40.26	The ¼ sec. cor. of sec. 36, T. 9 S., R. 21 E., monumented with a sandstone, 14 x 8 x 3 ins., firmly set, projecting 10 ins. above ground, mkd. ¼ on N face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.
	T 9 S R 21 E ¼ S 36 1977
	Deposit the mkd. stone alongside the iron post.
40.78	The ¼ sec. cor. of sec. 1, monumented with a sandstone, 14 x 8 x 5 ins., firmly set, projecting 9 ins. above ground, mkd. ¼ on N face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.
	T 9 S ¼ S 1 T 10 S R 21 E 1977
	Deposit the mkd. stone alongside the iron post.

CHAINS	
	S. 89° 06' W., beginning new measurement.
	Asc. over gradual SE slope.
20.295	Point for the W 1/16 sec. cor. of sec. 1, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
28.60	Unimproved road, bears N and S.
30.60	Pipeline, above ground, bears N and S.
39.08	The cor. of secs. 35 and 36, T. 9 S., R. 21 E., monumented with a sandstone, 24 x 12 x 4 ins., firmly set, projecting 12 ins. above ground, mkd. 1 notch on E and 5 notches on W edges.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.
	T 9 S R 21 E | S 35 | S 36 S 1 T 10 S 1977
	Deposit the mkd. stone alongside the iron post.
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.
40.59	The cor. of secs. 1 and 2, monumented with a scattered mound of stone. This position is harmoniously related to existing original cors., and is accepted as the best available evidence of the original corner position.
	At the corner point (center of mound)
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S S 35 S 2 | S 1 T 10 S R 21 E 1977
	From this point, U.S.C. & G.S. triangulation station "TWO WATER," bears S. 59° 27' E., 17.54 chs. dist., a brass tablet, 3 ins. diam., seated in concrete, in a sandstone boulder, located at Latitude 39° 59' 01.475" N., Longitude 109° 30' 18.802" W., as published by U.S.C. & G.S.
	S. 89° 12' W., along the N. bdy. of sec. 2.

Dependent Resurvey of the North Boundary,
T. 10 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
	Over slightly broken desert land through scattered shadscale and native grasses; asc. over gradual E slope.
20.365	Point for the E 1/16 sec. cor. of sec. 2, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
38.54	The ¼ sec. cor. of sec. 35, T. 9 S., R. 21 E., monumented with a sandstone, 18 x 8 x 4 ins., firmly set, projecting 8 ins. above ground, mkd. ¼ on N face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, to top of brass cap, mkd.
	T 9 S R 21 E ¼ S 35 T 10 S 1977
	Deposit the mkd. stone alongside the iron post.
40.73	The ¼ sec. cor. of sec. 2, monumented with a broken sandstone, bottom half firmly set, mkd. 4 on N face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, to top of brass cap, mkd.
	T 9 S ¼ S 2 T 10 S R 21 E 1977
	Deposit the mkd. stone alongside the iron post.
	S. 89° 06' W., beginning new measurement.
	Over nearly level land.
12.50	Dirt road, bears NE and SW.
20.195	Point for the W 1/16 sec. cor. of sec. 2, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
	Asc. over gradual SE slope.
37.33	Pipeline, above ground, bears N. 59° W. and S. 59° E.
37.89	Point for the cor. of secs. 34 and 35, T. 9 S., R. 21 E., at proportionate distance; there is no remaining evidence of the original corner.

201

Dependent Resurvey of the North Boundary,
T. 10 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 9 S R 21 E S 34 | S 35 S 2 T 10 S 1977
40.39	The cor. of secs. 2 and 3, monumented with a sandstone, 25 x 8 x 6 ins., firmly set, projecting 15 ins. above ground, mkd. 4 notches on W and 2 notches on E edges. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base, to top of brass cap, mkd. T 9 S S 34 S 3 | S 2 T 10 S R 21 E 1977 Deposit the mkd. stone alongside the iron post.
	S. 88° 21' W., on the N. bdy. of sec. 3. Over slightly broken land through scattered shadscale and native grasses; desc. over SW slope.
20.455	Point for the E 1/16 sec. cor. of sec. 3, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
26.80	Dirt road, bears NW and SE; thence over nearly level land.
37.58	Point for the ¼ sec. cor. of sec. 34, T. 9 S., R. 21 E., at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top of brass cap, mkd. T 9 S R 21 E ¼ S 34 T 10 S 1977
40.91	The ¼ sec. cor. of sec. 3, monumented with a sandstone, 16 x 8 x 4 ins., firmly set, projecting 8 ins. above ground, mkd. ¼ on S face.

☆ U.S. Government Printing Office-1978-778-206/433

CHAINS	
	At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 9 S ¼ S 3 T 10 S R 21 E 1977 Deposit the mkd. stone alongside the iron post. from this cor., A valve on gas well, "Natural Buttes No. 25", bears S. 30° 21' E., 29.50 chs. dist.
	N. 89° 50' W., beginning new measurement. Over nearly level land.
19.885	Point for the W 1/16 sec. cor. of sec. 3, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
21.00	Dirt road, bears NW and SE; thence over nearly level land.
36.75	The cor. of secs. 33 and 34, T. 9 S., R. 21 E., monumented with a sandstone, 18 x 13 x 6 ins., firmly set, projecting 9 ins. above ground, mkd. 3 notches on E and W edges. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 9 S R 21 E S 33 | S 34 S 3 T 10 S 1977 Deposit the mkd. stone alongside the iron post.
39.77	The cor. of secs. 3 and 4, monumented with a sandstone, 24 x 6 x 4 ins., firmly set, projecting 14 ins. above ground, mkd. 3 notches on E and W edges. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

203

Dependent Resurvey of the North Boundary,
T. 10 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
	T 9 S S 33 S 4 | S 3 T 10 S R 21 E 1977 Deposit the mkd. stone alongside the iron post.
	S. 88° 57' W., on the N. bdy. of sec. 4. Over nearly level land through scattered shadscale and native grasses.
19.99	Point for the E 1/16 sec. cor. of sec. 4, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
36.39	Point for the ¼ sec. cor. of sec. 33, T. 9 S., R. 21 E., at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base, to top of brass cap, mkd. T 9 S R 21 E ¼ S 33 T 10 S 1977
39.98	Point for the ¼ sec. cor. of sec. 4, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base, to top of brass cap mkd. T 9 S ¼ S 4 T 10 S R 21 E 1977 Desc. over rocky SW slope.
60.225	Point for the W 1/16 sec. cor. of sec. 4, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented. Asc. over gentle NE slope.
75.80	The cor. of secs. 32 and 33, T. 9 S., R. 21 E., monumented with a sandstone, 20 x 8 x 6 ins., set in a mound of stone, dimly mkd. 4 notches on E and 2 notches on W edges.

U.S. Government Printing Office-1978-778-206/433

CHAINS	
	At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base, to top of brass cap, mkd. T 9 S R 21 E | S 32 | S 33 S 4 T 10 S 1977 Deposit the mkd. stone alongside the iron post.
80.47	The cor. of secs. 4 and 5, monumented with a sandstone, 20 x 20 x 5 ins., firmly set, projecting 10 ins. above mound of stone, mkd. 4 notches on E and 2 notches on W edges. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base, to top of brass cap, mkd. T 9 S S 32 S 5 | S 4 | T 10 S R 21 E 1977 Deposit the mkd. stone alongside the iron post.
	S. 89° 08' W., on the N. bdy. of sec. 5. Over slightly broken desert land through scattered shadscale and native grasses; desc. over SW slope.
11.00	Cottonwood Wash, 12 ins. deep, 40 lks. wide, drains N.
20.215	Point for the E 1/16 sec. cor. of sec. 5, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
36.70	The ¼ sec. cor. of sec. 32, T. 9 S., R. 21 E., monumented with a sandstone, 18 x 8 x 5 ins., firmly set, projecting 10 ins. above ground, dimly mkd. ¼ on N face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.

205

Dependent Resurvey of the North Boundary,
T. 10 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
	T 9 S R 21 E ¼ S 32 T 10 S 1977
	Deposit the mkd. stone alongside the iron post.
40.43	The ¼ sec. cor. of sec. 5, monumented with a sandstone, 16 x 8 x 3 ins., firmly set, projecting 8 ins. above ground, mkd. ¼ on S face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S ¼ S 5 T 10 S R 21 E 1977
	Deposit the mkd. stone alongside the iron post.
	S. 89° 02' W., beginning new measurement.
	Asc. over gradual E slope.
20.20	The W 1/16 sec. cor. of sec. 5, monumented with a sandstone, 16 x 9 x 2 ins., firmly set, projecting 8 ins. above ground, mkd. 1/16 on S face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	W 1/16 S 5 T 10 S R 21 E 1977
	Deposit the mkd. stone alongside the iron post.
	S. 89° 02' W., beginning new measurement.
	Desc. along gentle N slope.
14.89	The cor. of secs. 31 and 32, T. 9 S., R. 21 E., monumented with a sandstone, 28 x 12 x 6 ins., firmly set, projecting 14 ins. above ground, mkd. 5 notches on E and 1 notch on W edges.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.

U.S. Government Printing Office-1978-778-206/433

CHAINS

T 9 S R 21 E
|
S 31 | S 32
S 5

T 10 S
1977

Deposit the mkd. stone alongside the iron post.

20.20 The cor. of secs. 5 and 6, monumented with a sandstone, 26 x 8 x 6 ins., firmly set projecting 14 ins. above ground, mkd. 5 notches on E and 1 notch on W edges.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft, base, to top of brass cap, mkd.

T 9 S

S 31
S 6 | S 5
|
T 10 S R 21 E

1977

Deposit the mkd. stone alongside the iron post.

S. 88° 41' W., on the N. bdy. of sec. 6.

Over gentle rolling desert land through scattered shadscale and native grasses; desc. along gentle N slope.

20.34 The E 1/16 sec. cor. of sec. 6, monumented with a sandstone, 26 x 4 x 3 ins., firmly set, projecting 14 ins. above ground, mkd. 1/16 on S face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.

E 1/16 S 6

T 10 S R 21 E
1977

Deposit the mkd. stone alongside the iron post.

S. 89° 24' W., beginning new measurement.

Desc. over NW slope.

14.71 Point for the ¼ sec. cor. of sec. 31, T. 9 S., R. 21 E., at proportionate distance; there is no remaining evidence of the original corner.

207

Dependent Resurvey of the North Boundary,
T. 10 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, to top of brass cap mkd. T 9 S R 21 E ¼ S 31 1977
20.07	The ¼ sec. cor. of sec. 6, monumented with a sandstone, 24 x 8 x 6 ins., firmly set, projecting 10 ins. above ground, mkd. ¼ on S face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. ¼ S 6 T 10 S R 21 E 1977 Deposit the mkd. stone alongside the iron post.
	N. 88° 22' W., beginning new measurement. Along gentle N slope.
19.71	The W 1/16 sec. cor. of sec. 6, monumented with a sandstone, 20 x 10 x 6 ins., set in a mound of stone, dimly mkd. 1/16 on S face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd. W 1/16 S 6 T 10 S R 21 E 1977 Deposit the mkd. stone alongside the iron post.
	S. 87° 26' W., beginning new measurement. Over gentle rolling land.
20.59	The cor. of Tps. 9 and 10 S., Rs. 20 and 21 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. as described in the official record of the 1928 resurvey of the E. bdy. of T. 10 S., R. 20 E.

CHAINS

Dependent Resurvey of the Subdivisional Lines
of T. 10 S., R. 21 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
D. G. Major in 1882

From the stan. cor. of secs. 35 and 36, on the S. bdy. of the Tp., heretofore described.

N. 0° 06' E., bet. secs. 35 and 36.

Over rolling to broken desert land.

20.34 Point for the S 1/16 sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Corner point not monumented.

40.68 Point for the ¼ sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

T 10 S R 21 E

¼

S 35 | S 36

1977

Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.

Cor. is located on S slope, near the N rim of a deep ravine that drains NE.

61.02 Point for the N 1/16 sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original cor.

Corner point not monumented.

81.36 Point for the cor. of secs. 25, 26, 35, and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, encircled with a collar of stone, with brass cap mkd.

T 10 S R 21 E

S 26 | S 25
S 35 | S 36

1977

CHAINS	
	Cor. is located on E slope, 1.00 ch. E of the top of a spur, sloping N.
	From the cor. of secs. 25 and 36, on the E. bdy. of the Tp., heretofore described.
	S. 89° 43' W., bet. secs. 25 and 36.
	Across broken desert land.
20.125	Point for the E 1/16 sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
40.25	Point for the ¼ sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.
	T 10 S R 21 E
	¼ S 25 / S 36
	1977
	Cor. is located on W slope, 20 lks. E of the bottom of draw, draining N.
53.00	Sand Wash, drains N. 20° E.
60.375	Point for the W 1/16 sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.
	T 10 S R 21 E
	W 1/16 S 25 / S 36
	1977
	Cor. is located on steep, rocky S slope, 50 lks. N of draw, that drains E into Sand Wash.
80.50	The cor. of secs. 25, 26, 35, and 36.
	N. 0° 48' W., bet. secs. 25 and 26.
	Across broken desert land.
20.34	Point for the S 1/16 sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.

U.S. Government Printing Office-1978-778-206/433

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 10 S R 21 E S 1/16 S 26 | S 25 1977 Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor. Cor. is located on S slope, 40 lks. S of top of spur, slopes E.
40.68	Point for the ¼ sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 10 S R 21 E ¼ | S 26 | S 25 | 1977 Cor. is located on E slope, 20 lks. W of small draw, draining S.
61.02	Point for the N 1/16 sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
81.36	Point for the sec. cor. of secs. 23, 24, 25, and 26, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 5 ins. in the ground to bedrock, in a mound of stone, 4. ft. base, to top of brass cap, mkd. T 10 S R 21 E S 23 | S 24 S 26 | S 25 1977 Cor. is located on top of spur, slopes NE.
	From the cor. of secs. 24 and 25, on the E. bdy. of the Tp., heretofore described. S. 89° 45' W., bet. secs. 24 and 25. Across broken desert land.

CHAINS	
15.00	Sand Wash, drains N.
20.235	Point for the E 1/16 sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
40.47	Point for the ¼ sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base, to top of brass cap, mkd. T 10 S R 21 E ¼ S 24 / S 25 1977 Cor. is located on nearly level spur top, 2.00 chs. E of base of ridge that bears N and S.
60.705	Point for the W 1/16 sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
80.94	The cor. of secs. 23, 24, 25, and 26.
	N. 0° 14' W., bet. secs. 23 and 24. Across broken desert land.
20.34	Point for the S 1/16 sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
32.60	Dirt road, bears N. 60° W. and E.
40.68	Point for the ¼ sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd. T 10 S R 21 E ¼ S 23 | S 24 1977 Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor. Cor. is located in the bottom of hollow, draining NE.

U.S. Government Printing Office-1978-778-206/433

CHAINS	
61.02	Point for the N 1/16 sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 10 S R 21 E N 1/16 S 23 | S 24 1977 Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor. Cor. is located on S slope, 1.00 ch. S of top of small ridge, bearing E and W.
81.36	Point for the cor. of secs. 13, 14, 23, and 24, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 10 S R 21 E S 14 | S 13 S 23 | S 24 1977 Cor. is located on ridge, 1 ch. W of cliff, bearing N and S.
	From the cor. of secs. 13 and 24, on the E. bdy. of the Tp., heretofore described. S. 89° 47' W., bet. secs. 13 and 24. Across broken desert land.
20.165	Point for the E 1/16 sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
28.00	Sand Wash, drains N.
40.33	Point for the ¼ sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.

CHAINS	
	T 10 S R 21 E ¼ S 13 / S 24 1977
	Cor. is located on N slope, 4 chs. N of top of spur, slopes E.
60.495	Point for the W 1/16 sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
80.66	The cor. of secs. 13, 14, 23, and 24.
	N. 0° 46' W., bet. secs. 13 and 14.
	Across broken, rugged, desert land.
20.34	Point for the S 1/16 sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
40.68	Point for the ¼ sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.
	T 10 S R 21 E ¼ S 14 | S 13 1977
	Cor. is located on top of spur, slopes NW.
61.02	Point for the N 1/16 sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
81.36	Point for the cor. of secs. 11, 12, 13, amd 14, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 5 ft. base, to top of brass cap, mkd.

☆ U.S. Government Printing Office-1978-778-206/433

CHAINS	
	T 10 S R 21 E S 11 | S 12 S 14 | S 13 1977 Cor. is located 1.00 ch. from spur that bears W, and 6 lks. from a rocky ledge, bearing N.
	From the cor. of secs. 12 and 13, on the E. bdy. of the Tp., heretofore described. S. 89° 49' W., bet. secs. 12 and 13. Across very rugged, broken, desert land with steep slopes and deep washes.
20.32	Point for the E 1/16 sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
40.64	Point for the ¼ sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 3 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base, to top of brass cap, mkd. T 10 S R 21 E ¼ S 12 / S 13 1977 Cor. is located on W edge of sandstone spur, projects N.
60.96	Point for the W 1/16 sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
81.28	The cor. of secs. 11, 12, 13, and 14.
	N. 0° 21' W., bet. secs. 11 and 12. Across broken, desert land.
20.34	Point for the S 1/16 sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original corner. Corner point not remonumented.

CHAINS	
40.68	Point for the ¼ sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, encircled with a collar of stone, with brass cap mkd. T 10 S R 21 E ¼ S 11 | S 12 1977 Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor. Cor. is located 1.00 ch. E of rocky ledge, bearing N.
61.02	Point for the N 1/16 sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
81.36	Point for the cor. of secs. 1, 2, 11, and 12, at proportionate distance falls in dirt road that bears E and W; there is no remaining evidence of the original corner. Bury brass cap, 8 ins. below the surface of dirt road, mkd. T 10 S R 21 E S 2 | S 1 S 11 | S 12 1977 from which An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, encircled with a collar of stone, for a reference monument, bears N. 45° E., 75 lks. dist., with a brass cap mkd. T10S R21E S1 49.5 FT RM 1977 and an arrow pointing to the cor. An iron post, 28 ins. long, 2½ ins. diam., set 12 ins. in the ground to bedrock, encircled with a mound of stone, for a reference monument, bears S. 45° E., 75 lks. dist., with a brass cap mkd. T10S R21E S12 RM 49.5 FT 1977 and an arrow pointing to the cor. A chimney of tin building, "Gas Producing Enterprises, Inc.", located by a gas well, bears N. 39° 25' W., 9.00 chs. dist. From the cor. of secs. 1 and 12, on the E. bdy. of the Tp., heretofore described.

U.S. Government Printing Office-1978-778-206/433

CHAINS	
	S. 89° 50' W., bet. secs. 1 and 12.
	Across Sand Wash and rolling desert land.
16.00	Sand Wash, drains N.
20.285	Point for the E 1/16 sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
40.57	Point for the ¼ sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.
	T 10 S R 21 E
	¼ S 1 / S 12
	1977
60.855	Point for the W 1/16 sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
79.55	Dirt road, bears N and W.
81.14	The cor. of secs. 1, 2, 11, and 12.
	N. 0° 38' W., bet. secs. 1 and 2.
	Across rolling to broken desert land.
11.00	Dirt road, bears N. 30° W. and S. 30° E.
20.34	Point for the S 1/16 sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
40.68	Point for the ¼ sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base, to top of brass cap, mkd.
	T 10 S R 21 E
	¼ / S 2 | S 1
	1977

CHAINS	
	Cor. is located on gentle NW slope, 2½ chs. E of bulldozed road and above the ground natural gas pipeline.
50.00	Pipeline, above the ground, and dirt road, bears NE and SW.
61.02	Point for the N 1/16 sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
82.90	The cor. of secs. 1 and 2, on N. bdy. of the Tp., heretofore described.
	From the stan. cor. of secs. 34 and 35, on the S. bdy. of the Tp., heretofore described. N. 0° 02' E., bet. secs. 34 and 35. Over gently rolling land with shadscale and native grasses; descend over gentle N slope along W edge of draw.
20.305	Point for the S 1/16 sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
40.61	Point for the ¼ sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, to top of brass cap, mkd. T 10 S R 21 E ¼ S 34 | S 35 1977 Cor. is located on open flat.
60.915	Point for the N 1/16 sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
81.22	Point for the cor. of secs. 26, 27, 34, and 35, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 5 ft. base, to top of brass cap, mkd.

CHAINS	
	T 10 S R 21 E S 27 | S 26 S 34 | S 35 1977 Cor. is located on W slope, 1.00 ch. W of spur, slopes N.
	From the cor. of secs. 25, 26, 35, and 36. N. 89° 58' W., bet. secs. 26 and 35. Across broken desert land.
20.30	Point for the E 1/16 sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
34.00	Dirt road, bears NE and SW.
40.60	Point for the ¼ sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 10 S R 21 E ¼ S 26 / S 35 1977 Raise a mound of stone, 3 ft. base, 1½ ft. high, N of cor. Cor. is located on E slope.
60.90	Point for the W 1/16 sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
81.20	The cor. of secs. 26, 27, 34, and 35.
	N. 0° 30' W., bet. secs. 26 and 27. Across broken desert land.
20.305	Point for the S 1/16 sec. cor. of secs. 26 and 27, at porportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
40.61	Point for the ¼ sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original corner.

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, encircled by a collar of stone, with brass cap mkd. T 10 S R 21 E ¼ S 27 | S 26 1977 Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor. Cor. is located on E slope, near base of ridge.
60.915	Point for the N 1/16 sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
81.22	Point for the cor. of secs. 22, 23, 26, and 27, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, encircled by a collar of stone, with brass cap mkd. T 10 S R 21 E S 22 | S 23 S 27 | S 26 1977 Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor. Cor. is located 30 lks. out of bottom of draw, draining SW.
	From the cor. of secs. 23, 24, 25, and 26. S. 89° 58' W., bet. secs. 23 and 26. Across broken and rolling desert land.
20.20	Point for the E 1/16 sec. cor. of secs. 23 and 26, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
23.00	Dirt road, bears N and S.
40.40	Point for the ¼ sec. cor. of secs. 23 and 26, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

☆ U.S. Government Printing Office-1978-778-206/433

CHAINS	
	T 10 S R 21 E ¼ S 23 / S 26 1977
	Raise a mound of stone, 3 ft. base, 1½ ft. high, N of cor.
	Cor. is located on top of low spur, projects NW.
60.60	Point for the W 1/16 sec. cor. of secs. 23 and 26, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented,
80.80	The cor. of secs. 22, 23, 26, and 27.
	N. 0° 24' W., bet. secs. 22 and 23.
	Across broken and rolling desert land.
20.305	Point for the S 1/16 sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
40.61	Point for the ¼ sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, encircled by a collar of stone, with brass cap mkd.
	T 10 S R 21 E ¼ S 22 | S 23 1977
	Cor. is located on N edge of ridge, 5.00 chs. S of wash.
60.915	Point for the N 1/16 sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
62.50	Pipeline, above ground, bears NW and SE.
81.22	Point for the cor. of secs. 14, 15, 22, and 23, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 2 ins. in the ground to bedrock, in a mound of stone, 5 ft. base, to top of brass cap, mkd.

221

Dependent Resurvey of the Subdivisional Lines
of T. 10 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
	T 10 S R 21 E S 15 | S 14 S 22 | S 23 1977 Cor. is located on E edge of low ridge, bears NW.
	From the cor. of secs. 13, 14, 23, and 24. S. 89° 51' W., bet. secs. 14 and 23. Across rolling desert land.
20.25	Point for the E 1/16 sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
40.50	Point for the ¼ sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 10 S R 21 E ¼ S 14 / S 23 1977 Raise a mound of stone, 3 ft. base, 1½ ft. high, N of cor. Cor. is located on ridge top, bears NW and SE.
54.30	Dirt road, bears NW and SE.
60.75	Point for the W 1/16 sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
81.00	The cor. of secs. 14, 15, 22, and 23
	N. 0° 34' W., bet. secs. 14 and 15. Across broken desert land.
7.50	Dirt road, bears E and W.
20.305	Point for the S 1/16 sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, to top of brass cap, mkd.

☆ U.S. Government Printing Office-1978-778-206/433

CHAINS	
	T 10 S R 21 E S 1/16 S 15 | S 14 1977
	Cor. is located 40 lks. N of broken sandstone ledge, bears E and W.
40.61	Point for the ¼ sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, encircled by a collar of stone, with brass cap mkd.
	T 10 S R 21 E ¼ S 15 | S 14 1977
	Cor. is located 75 lks. W of small wash on E slope of low rolling hill.
60.915	Point for the N 1/16 sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
81.22	Point for the cor. of secs. 10, 11, 14, and 15, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.
	T 10 S R 21 E S 10 | S 11 S 15 | S 14 1977
	Cor. is located in bottom of draw, 1.00 ch. N of wash, drains W.
	From the cor. of secs. 11, 12, 13, and 14.
	S. 89° 45' W., bet. secs. 11 and 14.
	Across broken desert land.
20.175	Point for the E 1/16 sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.

CHAINS	
40.35	Point for the ¼ sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 10 S R 21 E ¼ S 11 / S 14 1977 Raise a mound of stone, 3 ft. base, 1½ ft. high, N of cor. Cor. is located on E slope of ridge, bears N and S, 40 lks. from the top.
60.525	Point for the W 1/16 sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
80.70	The cor. of secs. 10, 11, 14, and 15.
	N. 0° 20' W., bet. secs. 10 and 11. Across rolling desert land.
20.305	Point for the S 1/16 sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
40.61	Point for the ¼ sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 5 ft. base, to top of brass cap, mkd. T 10 S R 21 E ¼ S 10 | S 11 1977 Cor. is located in flat, 3.00 chs. NE of wash.
60.915	Point for the N 1/16 sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
81.22	Point for the cor. of secs. 2, 3, 10, and 11, at proportionate distance; there is no remaining evidence of the original corner.

U.S. Government Printing Office-1978-778-206/433

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., over a cross (X) marked in solid sandstone, in a mound of stone, 6 ft. base, to top of brass cap, mkd. T 10 S R 21 E S 3 | S 2 S 10 | S 11 1977
	From the cor. of secs. 1, 2, 11, and 12.
	S. 89° 38' W., bet. secs. 2 and 11.
3.00	Dirt road, bears N and E.
	Across rolling desert land.
20.165	Point for the E 1/16 sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
40.33	Point for the ¼ sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, encircled by a collar of stone, with brass cap mkd. T 10 S R 21 E ¼ S 2 / S 11 1977
60.495	Point for the W 1/16 sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
80.66	The cor. of secs. 2, 3, 10, and 11.
	N. 0° 57' W., bet. secs. 2 and 3.
	Across rolling desert land.
10.00	Dirt road, bears NE and SW.
20.305	Point for the S 1/16 sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
40.61	Point for the ¼ sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 10 S R 21 E ¼ S 3 | S 2 1977
52.50	Dirt road, bears E and W.
55.50	Dirt road, bears NW and SE.
60.915	Point for the N 1/16 sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
63.00	Dirt road, bears NE and SW.
82.19	The cor. of secs. 2 and 3, on the N. bdy. of the Tp., heretofore described.
	From the stan. cor. of secs. 33 and 34, on the S. bdy. of the Tp., heretofore described. North, bet. secs. 33 and 34. Across wash and rolling desert land.
20.255	Point for the S 1/16 sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
40.51	Point for the ¼ sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 10 S R 21 E ¼ S 33 | S 34 1977 Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor. Cor. is located on gentle SW slope, 5.00 chs. S of point of sandstone spur.

U.S. Government Printing Office-1978-778-206/433

CHAINS	
60.765	Point for the N 1/16 sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
81.02	Point for the cor. of secs. 27, 28, 33, and 34, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 10 S R 21 E S 28 | S 27 S 33 | S 34 1977 Cor. is located on W slope of ridge, bears N and S, 2.00 chs. from top.
	From the cor. of secs. 26, 27, 34, and 35. S. 89° 54' W., bet. secs. 27 and 34. Across rolling desert land.
20.205	Point for the E 1/16 sec. cor. of secs. 27 and 34, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
40.41	Point for the ¼ sec. cor. of secs. 27 and 34, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 10 S R 21 E ¼ S 27 S 34 1977 Cor. is located on gentle N slope, 2.00 chs. S of wash, drains N.
60.615	Point for the W 1/16 sec. cor. of secs. 27 and 34, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
80.82	The cor. of secs. 27, 28, 33, and 34.

227

Dependent Resurvey of the Subdivisional Lines
of T. 10 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
	N. 0° 44' W., bet. secs. 27 and 28.
	Across wash and rolling desert land.
20.255	Point for the S 1/16 sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
40.51	Point for the ¼ sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.
	T 10 S R 21 E ¼ S 28 | S 27 1977
	Cor. is located near bottom of swale, drains SE.
60.765	Point for the N 1/16 sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
81.02	Point for the cor. of secs. 21, 22, 27, and 28, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.
	T 10 S R 21 E S 21 | S 22 S 28 | S 27 1977
	Cor. is located on gentle E slope, 2.00 chs. W of wash, drains NE.
	From the cor. of secs. 22, 23, 26, and 27.
	S. 89° 42' W., bet. secs. 22 and 27.
	Across broken desert land.
20.28	Point for the E 1/16 sec. cor. of secs. 22 and 27, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.

U.S. Government Printing Office-1978-778-206/433

CHAINS	
40.56	Point for the ¼ sec. cor. of secs. 22 and 27, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 10 S R 21 E ¼ S 22 / S 27 1977 Raise a mound of stone, 3 ft. base, 1½ ft. high, N of cor. Cor. is located on S slope, 1.00 ch. N of draw, drains E and 1.00 ch. S of mesa rim, bearing NE and SW.
60.84	Point for the W 1/16 sec. cor. of secs. 22 and 27, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
81.12	The cor. of secs. 21, 22, 27, and 28.
	N. 0° 17' W., bet. secs. 21 and 22. Across rolling desert land.
20.255	Point for the S 1/16 sec. cor. of secs. 21 and 22, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
40.51	Point for the ¼ sec. cor. of secs. 21 and 22, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 10 S R 21 E ¼ S 21 | S 22 1977 Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor. Cor. is located on sandy flat, 4 chs. N of base of round hill.
60.765	Point for the N 1/16 sec. cor. of secs. 21 and 22, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.

CHAINS	
77.15	Dirt road, bears E and W.
81.02	Point for the cor. of secs. 15, 16, 21, and 22, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 10 S R 21 E S 16 | S 15 S 21 | S 22 1977 from which A mound of stone, bears S. 8° 23' W., 2.94 chs. dist. A valve on natural gas well "Natural Buttes No. 19", bears S. 40° 26' W., 34.64 chs. dist. Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor.
	From the cor. of secs. 14, 15, 22, and 23. S. 89° 33' W., bet. secs. 15 and 22. Across rolling desert land.
20.24	Point for the E 1/16 sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
40.48	Point for the ¼ sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 10 S R 21 E ¼ S 15 / S 22 1977 Raise a mound of stone, 3 ft. base, 1½ ft. high, N of cor. Cor. is located 2.00 chs. N of wash, drains NE.
43.00	Improved dirt road, bears NE and SW.
60.00	Dirt road, bears NW and SE.
60.72	Point for the W 1/16 sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original corner.

U.S. Government Printing Office-1978-778-206/433

CHAINS	
	Corner point not monumented.
80.96	The cor. of secs. 15, 16, 21, and 22.
	N. 0° 10' W., bet. secs. 15 and 16.
	Across rolling desert land.
20.255	Point for the S 1/16 sec. cor. of secs. 15 and 16, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
29.80	Dirt road, bears NW and SE.
40.51	Point for the ¼ sec. cor. of secs. 15 and 16, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 10 S R 21 E
	¼
	S 16 | S 15
	1977
	Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor.
	Cor. is located 3.26 chs. S of man made water ponds.
57.00	Dirt road, bears NE and SW.
60.765	Point for the N 1/16 sec. cor. of secs. 15 and 16, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
81.02	Point for the cor. of secs. 9, 10, 15, and 16, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 10 S R 21 E
	S 9 | S 10
	S 16 | S 15
	1977
	Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor.
	Cor. is located on top of ridge, bears N.

CHAINS	
	From the cor. of secs. 10, 11, 14, and 15.
	S. 89° 24' W., bet. secs. 10 and 15.
	Across rolling desert land.
10.60	Dirt road, bears N and SW.
20.10	Point for the E 1/16 sec. cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
40.20	Point for the ¼ sec. cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 10 S R 21 E ¼ S 10 / S 15 1977
	Raise a mound of stone, 3 ft. base, 1½ ft. high, N of cor.
	Cor. is located on the W edge of wash, drains NE from SE.
60.30	Point for the W 1/16 sec. cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
64.00	Dirt road, bears NE and SW.
80.40	The cor. of secs. 9, 10, 15 and 16.
	N. 0° 37' W., bet. secs. 9 and 10.
	Across rolling desert land.
20.255	Point for the S 1/16 sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 10 S R 21 E S 1/16 S 9 | S 10 1977
	Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor.

CHAINS	
	Cor. is located on gentle NW slope of flat land.
40.51	Point for the ¼ sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 10 S R 21 E ¼ S 9 | S 10 1977
	Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor.
	Cor. is located on top of rolling, sandy ridge, bears NE and SW.
60.765	Point for the N 1/16 sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
81.02	Point for the cor. of secs. 3, 4, 9, and 10, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base, to top of brass cap, mkd.
	T 10 S R 21 E S 4 | S 3 S 9 | S 10 1977
	Cor. is located on N side of spur, slopes E.
	From the cor. of secs. 2, 3, 10, and 11.
	S. 89° 14' W., bet. secs. 3 and 10.
	Across rolling desert land.
8.00	Fork of dirt road, bears NE, SW and S.
20.195	Point for the E 1/16 sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
40.39	Point for the ¼ sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original corner.

233

Dependent Resurvey of the Subdivisional Lines
of T. 10 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, encircled by a collar of stone, with brass cap mkd. T 10 S R 21 E ¼ S 3 / S 10 1977
60.585	Point for the W 1/16 sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
80.78	The cor. of secs. 3, 4, 9, and 10.
	N. 0° 54' W., bet. secs. 3 and 4. Across rolling desert land, broken by washes and low ridges.
20.255	Point for the S 1/16 sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
40.51	Point for the ¼ sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 10 S R 21 E ¼ S 4 | S 3 1977 Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor. Cor. is located on gentle E slope of small ridge, bears N and S, 50 lks. W of wash, draining N.
60.765	Point for the N 1/16 sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
82.16	The cor. of secs. 3 and 4, on the N. bdy. of the Tp., heretofore described.
	From the stan. cor. of secs. 32 and 33, on the S. bdy. of the Tp., heretofore described.

☆ U.S. Government Printing Office-1978-778-206/433

CHAINS	
	N. 0° 25' E., bet. secs. 32 and 33.
	Across broken desert land.
20.195	Point for the S 1/16 sec. cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
40.39	Point for the ¼ sec. cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, encircled by a collar of stone, with brass cap mkd.
	T 10 S R 21 E ¼ S 32 | S 33 1977
	Cor. is located on spur sloping NE into wash, draining NW; thence W.
60.585	Point for the N 1/16 sec. cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
79.00	Cottonwood Wash, drains NE.
80.78	Point for the cor. of secs. 28, 29, 32, and 33, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 10 S R 21 E S 29 | S 28 S 32 | S 33 1977
	Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor.
	From this cor., the cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., projecting 10 ins. above ground with brass cap mkd. as described in the official record of the 1928 resurvey, bears N. 89° 37' W., 162.32 chs. dist. The control line was fully retraced and no evidence of the intervening cors. was found.
	From this same cor., the cor. of secs. 20, 21, 28, and 29, bears N. 0° 57' W., 80.78 chs. dist., hereinafter described. The control line was fully retraced and no evidence of the intervening cor. was found.

CHAINS	
	From the cor. of secs. 27, 28, 33, and 34.
	S. 89° 51' W., bet. secs. 28 and 33.
	Across broken and rolling desert land.
20.05	Point for the E 1/16 sec. cor. of secs. 28 and 33, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
40.10	Point for the ¼ sec. cor. of secs. 28 and 33, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 10 S R 21 E
	¼ S 28 / S 33
	1977
	Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor.
	Cor. is located on gentle, rolling, flat land.
60.15	Point for the W 1/16 sec. cor. of secs. 28 and 33, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
78.00	Cottonwood Wash, drains NE.
80.20	The cor. of secs. 28, 29, 32, and 33.
	From the cor. of secs. 21, 22, 27, and 28.
	S. 89° 41' W., bet. secs. 21 and 28.
	Across broken and rolling desert land.
20.125	Point for the E 1/16 sec. cor. of secs. 21 and 28, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
40.25	Point for the ¼ sec. cor. of secs. 21 and 28, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, encircled by a collar of stone, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines
of T. 10 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
	T 10 S R 21 E ¼ S 21 / S 28 1977
	Cor. is located on E slope of hill, bearing N, 2.00 chs. from top.
60.375	Point for the W 1/16 sec. cor. of secs. 21 and 28, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented,
80.50	The cor. of secs. 20, 21, 28, and 29, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, encircled by a collar of stone, with brass cap mkd.
	T 10 S R 21 E S 20 | S 21 S 29 | S 28 1977
	Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor.
	Cor. is located in an open flat, 20.00 chs. W of a rocky point.
	From this cor., the cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set in a mound of stone, projecting 20 ins. above ground, with brass cap mkd. as described in the official record of the 1928 resurvey, bears S. 89° 54' W., 161.38 chs. dist.
	The control line was fully retraced, and no evidence of the intervening cors. was found.
	N. 0° 14' W., bet. secs. 20 and 21.
	Across rolling desert land.
20.195	Point for the S 1/16 sec. cor. of secs. 20 and 21, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
40.39	Point for the ¼ sec. cor. of secs. 20 and 21, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 5 ft. base, to top of brass cap, mkd.

237

Dependent Resurvey of the Subdivisional Lines
of T. 10 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
	T 10 S R 21 E ¼ S 20 | S 21 1977
	Cor. is located on large flat.
60.585	Point for the N 1/16 sec. cor. of secs. 20 and 21, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
80.78	Point for the cor. of secs. 16, 17, 20, and 21, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, encircled by a collar of stone, with brass cap mkd. T 10 S R 21 E S 17 | S 16 S 20 | S 21 1977 Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor. Cor. is located 1.00 ch. N of wash, draining W and 1.00 ch. S of ridge, bears W and near the bottom of small wash, draining S.
	From the cor. of secs. 15, 16, 21, and 22. S. 89° 28' W., bet. secs. 16 and 21. Across rolling desert land.
20.115	Point for the E 1/16 sec. cor. of secs. 16 and 21, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
27.50	Dirt road, bears NE and S.
40.23	Point for the ¼ sec. cor. of secs. 16 and 21, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

CHAINS	
	T 10 S R 21 E ¼ S 16 / S 21 1977
	Raise a mound of stone, 3 ft. base, 1½ ft. high, N of cor.
	Cor. is located on top of gravel spur, approximately 2.00 chs. N of dirt road.
43.25	Improved dirt road, bears NW and SE.
60.345	Point for the W 1/16 sec. cor. of secs. 16 and 21, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
80.46	The cor. of secs. 16, 17, 20, and 21.
	N. 0° 20' W., bet. secs. 16 and 17.
	Across broken desert land.
15.00	Improved dirt road, bears NW and SE.
20.195	Point for the S 1/16 sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
40.39	Point for the ¼ sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, encircled by a collar of stone, with brass cap mkd.
	T 10 S R 21 E ¼ S 17 | S 16 1977
	Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor.
	Cor. is located 2.00 chs. S of ridge, bearing NW and 70 lks. SE of the intersection of 2 washes that drain N.
54.00	Pipeline, above ground, bears NW and SE.
60.585	Point for the N 1/16 sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.

239

Dependent Resurvey of the Subdivisional Lines
of T. 10 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
80.78	Point for the cor. of secs. 8, 9, 16, and 17, at proportionate dist.; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 10 S R 21 E S 8 | S 9 S 17 | S 16 1977 from which A value on natural gas well "Natural Buttes No. 3", bears S. 47° W., 31.19 chs. dist. Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor. Cor. is located on gentle N slope.
	From the cor. of secs. 9, 10, 15, and 16. S. 89° 19' W., bet. secs. 9 and 16. Across slightly broken desert land.
20.18	Point for the E 1/16 sec. cor. of secs. 9 and 16, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
40.36	Point for the ¼ sec. cor. of secs. 9 and 16, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, encircled by a collar of stone, with brass cap mkd. T 10 S R 21 E ¼ S 9 S 16 1977
60.54	Point for the W 1/16 sec. cor. of secs. 9 and 16, at proportionate distance; there is no remaining evidence of the original cor. Corner point not monumented.
80.72	The cor. of secs. 8, 9, 16, and 17.
	N. 0° 38' W., bet. secs. 8 and 9. Across broken and rolling desert land.

CHAINS	
20.195	Point for the S 1/16 sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
40.39	Point for the ¼ sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 10 S R 21 E ¼ S 8 | S 9 1977 Cor. is located on W edge of ridge, bears N, 10 lks. E of wash, draining N.
60.585	Point for the N 1/16 sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
80.78	Point for the cor. of secs. 4, 5, 8, and 9, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., on solid sandstone, in a mound of stone, 5 ft. base, to top of brass cap, mkd. T 10 S R 21 E S 5 | S 4 S 8 | S 9 1977 Cor. is located 1.00 ch. N of wash, drains W, 1.50 chs. S of ridge, bearing W, and 1.00 ch. W of ridge, bears S.
	From the cor. of secs. 3, 4, 9, and 10. S. 89° 07' W., bet. secs. 4 and 9. Across slightly broken desert land.
20.19	Point for the E 1/16 sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.

CHAINS	
40.38	Point for the ¼ sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a collar of stone, with brass cap mkd. T 10 S R 21 E ¼ S 4 / S 9 1977 Cor. is located on flat clay surface, near the E edge of low spur, bearing N and S.
60.57	Point for the W 1/16 sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
80.76	The cor. of secs. 4, 5, 8, and 9.
	N. 0° 40' W., bet. secs. 4 and 5. Across broken and rolling desert land.
20.195	Point for the S 1/16 sec. cor.of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
40.39	Point for the ¼ sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd. T 10 S R 21 E ¼ S 5 | S 4 1977 Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor. Cor. is located on top of sandy spur, bears S and 3.00 chs. S of rocky ledge, bearing W.
60.585	Point for the N 1/16 sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.

☆ U.S. Government Printing Office-1978-778-206/433

CHAINS	
81.91	The cor. of secs. 4 and 5, on the N. bdy. of the Tp., heretofore described.
	From the cor. of secs. 16, 17, 20, and 21.
	S. 89° 28' W., bet. secs. 17 and 20.
	Across slightly broken desert land.
20.145	Point for the E 1/16 sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
40.29	Point for the ¼ sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, encircled by a collar of stone, with brass cap mkd.
	T 10 S R 21 E
	¼ S 17 / S 20
	1977
	Cor. is located on gravelly, rolling hill, approximately 3.50 chs. N of wash, draining N from W.
60.435	Point for the W 1/16 sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
80.58	Point for the cor. of secs. 17, 18, 19, and 20, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, encircled by a collar of stone, with brass cap mkd.
	T 10 S R 21 E
	S 18 | S 17 / S 19 | S 20
	1977
	Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor.
	Cor. is located on sandy flat, 2.00 chs. E of Cottonwood Wash.
	From this cor., the stan. cor. of secs. 31 and 32, on the S. bdy. of the Tp., monumented with a sandstone, 15 x 6 x 6 ins., above ground, firmly set and plainly mkd. SC and 6 grooves on N, 5 grooves on E, and 1 groove on W faces, bears S. 0° 10' E., 241.68 chs. dist.

243

Dependent Resurvey of the Subdivisional Lines
of T. 10 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
	The control line was fully retraced, and no evidence of the intervening corners was found.
	N. 89° 50' W., bet. secs. 18 and 19.
	Across slightly broken desert land.
2.00	Cottonwood Wash, drains N.
20.105	Point for the E 1/16 sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
40.21	Point for the ¼ sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, encircled by a collar of stone, with brass cap mkd.
	T 10 S R 21 E
	¼ S 18 / S 19
	1977
	Raise a mound of stone, 3 ft. base, 1½ ft. high, N of cor.
	Cor. is located on nearly flat land, approximately 5.00 chs. E of mesa top.
60.315	Point for the W 1/16 sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
80.78	The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., projecting 10 ins. above ground, with brass cap mkd. as described in the official record of the 1928 resurvey.
	From the cor. of secs. 17, 18, 19, and 20.
	N. 0° 35' W., bet. secs. 17 and 18.
	Along Cottonwood Wash and over broken desert land.
9.00	Leave Cottonwood Wash, drains NE.
20.14	Point for the S 1/16 sec. cor. of secs. 17 and 18, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.

CHAINS	
40.28	Point for the ¼ sec. cor. of secs. 17 and 18, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, encircled by a collar of stone, with brass cap mkd. T 10 S R 21 E ¼ S 18 | S 17 1977 Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor. Cor. is located 30 lks. E of top of spur, slopes N.
60.42	Point for the N 1/16 sec. cor. of secs. 17 amd 18, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
65.50	Pipeline, above ground, bears E and W.
80.56	Point for the cor. of secs. 7, 8, 17, and 18, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, encircled by a collar of stone, with brass cap mkd. T 10 S R 21 E S 7 | S 8 S 18 | S 17 1977 Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor. Cor. is located on rolling, gravelly swale, 1.50 chs. E of wash, draining N.
	From the cor. of secs. 8, 9, 16, and 17. S. 89° 17' W., bet. secs. 8 and 17. Across broken desert land.
20.21	Point for the E 1/16 sec. cor. of secs. 8 and 17, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
40.42	Point for the ¼ sec. cor. of secs. 8 and 17, at proportionate distance; there is no remaining evidence of the original corner.

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 10 S R 21 E ¼ S 8 / S 17 1977
54.20	Improved dirt road, bears NW and SE. Descend into Cottonwood Wash.
60.63	Point for the W 1/16 sec. cor. of secs. 8 and 17, at proportionate distance, falls in Cottonwood Wash, drains N; there is no remaining evidence of the original corner. Corner point not monumented.
80.84	The cor. of secs. 7, 8, 17, and 18.
	N. 88° 31' W., bet. secs. 7 and 18. Across rolling desert land.
20.145	Point for the E 1/16 sec. cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
30.00	Improved dirt road, bears NE and SW; thence W.
40.29	Point for the ¼ sec. cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 5 ft. base, to top of brass cap, mkd. T 10 S R 21 E ¼ S 7 / S 18 1977
60.435	Point for the W 1/16 sec. cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original corner. Corner point not monumented.
80.82	The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., projecting 10 ins. above ground, with brass cap mkd. as described in the official record of the 1928 resurvey.

CHAINS	
	From the cor. of secs. 7, 8, 17, and 18.
	N. 0° 32' W., bet. secs. 7 and 8.
	Across slightly broken desert land.
9.50	Improved dirt road, bears E and W.
20.14	Point for the S 1/16 sec. cor. of secs. 7 and 8, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
40.28	Point for the ¼ sec. cor. of secs. 7 and 8, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., over a cross (X) chiseled in solid sandstone, in a mound of stone, 5 ft. base, to top of brass cap, mkd.
	T 10 S R 21 E ¼ S 7 | S 8 1977
	Cor. is located on exposed sandstone hill.
60.42	Point for the N 1/16 sec. cor. of secs. 7 and 8, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
80.56	Point for the cor. of secs. 5, 6, 7, and 8, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, encircled by a collar of stone, with brass cap mkd.
	T 10 S R 21 E S 6 | S 5 S 7 | S 8 1977
	Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor.
	Cor. is located 1.50 chs. E of wash, drains N, on a rolling, gravelly swale.
	From the cor. of secs. 4, 5, 8, and 9.
	S. 89° 10' W., bet. secs. 5 and 8.

247

Dependent Resurvey of the Subdivisional Lines
of T. 10 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
	Across broken desert land.
20.00	Cottonwood Wash, drains N.
20.16	Point for the E 1/16 sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
40.32	Point for the ¼ sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 10 S R 21 E
	¼ S 5 / S 8
	1977
	Raise a mound of stone, 3 ft. base, 1½ ft. high, N of cor.
	Cor. is located on S edge of small mesa top, 20 ft. N of rim.
60.48	Point for the W 1/16 sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
80.64	The cor. of secs. 5, 6, 7, and 8.
	N. 89° 35' W., bet. secs. 6 and 7.
	Across rolling desert land.
20.11	Point for the E 1/16 sec. cor. of secs. 6 and 7, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
40.22	Point for the ¼ sec. cor. of secs. 6 and 7, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 10 S R 21 E
	¼ S 6 / S 7
	1977
	Raise a mound of stone, 3 ft. base, 1½ ft. high, N of cor.

Dependent Resurvey of the Subdivisional Lines
of T. 10 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
	Cor. is located on E slope of small spur, slopes E.
60.33	Point for the W 1/16 sec. cor. of secs. 6 and 7, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
80.29	The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., projecting 10 ins. above ground, with brass cap mkd. as described in the official record of the 1928 resurvey.
	From the cor. of secs. 5, 6, 7, and 8.
	N. 0° 51' W., bet. secs. 5 and 6.
	Across rolling desert land.
20.14	Point for the S 1/16 sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
40.28	Point for the ¼ sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 10 S R 21 E
	¼
	S 6 | S 5
	1977
	Cor. is located on top of spur, bears W.
60.42	Point for the N 1/16 sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.
	Corner point not monumented.
81.77	The cor. of secs. 5 and 6, on the N. bdy. of the Tp., heretofore described.

General Description

The land encompassed in this survey is located approximately thirty miles south of the city of Vernal, Utah. Access from Vernal is southwest on U.S. Highway 40 approximately fifteen miles, then south on State Highway 88 to the town of Ouray in the Uintah and Ouray Reservation. South of the town of Ouray there is a dirt road which runs east. This road enters the township in sec. 18 after approximatly six miles. There are several dirt roads in the township.

249

Dependent Resurvey of the Subdivisional Lines
of T. 10 S., R. 21 E., Salt Lake Meridian, Utah

	CHAINS	
		This township is rough, barren, desert land cut by many washes, the largest of which is Cottonwood Wash which drains irregularly north through the western part of the township. Elevation ranges from approximately 5,000 ft. in the northeast part of the township to approximately 5,500 ft. in the southeast part. There are several natural gas wells and pipelines in this township and the northeast part is called the Bitter Creek Gas Field. Oil shale is also found in this township. The mean magnetic declination is found to be 14° 30' E.

Form 9600–11
(August 1979)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
James McDaniel	Survey Aid
Bryan Seibold	Survey Aid
Craig Black	Survey Aid

251

CERTIFICATE OF SURVEY

(I) (~~We~~) Jerry L. Thomas, Supervisory Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 26th day of May, 1977, (I) (~~We~~) have dependently resurveyed the west boundary of T. 10 S., R. 22 E., the east 4 miles of the south boundary, (Second Standard Parallel South), the north boundary and a portion of the subdivisional lines of T. 10 S., R. 21 E.,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), (~~us~~) and under (my) (~~our~~) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

November 30, 1979
(Date)

Jerry L. Thomas
(Cadastral Surveyor)
Supervisory

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Denver, Colorado

The foregoing field notes of the dependent resurvey of the west boundary of T. 10 S., R. 22 E., the east 4 miles of the south boundary, (Second Standard Parallel South), the north boundary and a portion of the subdivisional lines of T. 10 S., R. 21 E., Salt Lake Meridian, Utah

executed by Jerry L. Thomas, Supervisory Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

FEB 23 1981
(Date)

J. D. Voorhees
(Chief, Cadastral Survey Examination and Approval Staff)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.~~

~~(Date)~~ ~~(Chief, Cadastral Survey Examination and Approval Staff)~~

Form 9600–11
(August 1979)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Stewart Burt	Surveying Technician
James McDaniel	Survey Aid
Craig Black	Survey Aid
Bryan Seibold	Survey Aid

308

CERTIFICATE OF SURVEY

XXXWe), Jerry L. Thomas and Ferrel D. Reynolds
Craig P. Sylvester and Gail E. Reynolds, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 20th day of July, 19 77 XXX(We) have dependently resurveyed the south boundary, the south 2 miles of the west boundary, the east boundary, the south 2 tiers of sections, and the east 3 ranges of sections in Township 9 South, Range 22 East,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by XXX), (us) and underXXX) (our) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

February 17, 1979 (Date) — Jerry L. Thomas, Supervisory (Cadastral Surveyor)

February 17, 1979 (Date) — Ferrel D. Reynolds (Cadastral Surveyor)

February 17, 1979 (Date) — Craig P. Sylvester, Supervisory (Cadastral Surveyor)

February 17, 1979 (Date) — Gail E. Reynolds (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Denver, Colorado

The foregoing field notes of the dependent resurvey of the south boundary, the south 2 miles of the west boundary, the east boundary, the south 2 tiers of sections, and the east 3 ranges of sections in Township 9 South, Range 22 East, Salt Lake Meridian, Utah.

executed by
Jerry L. Thomas, Supervisory Cadastral Surveyor
Gail E. Reynolds, Cadastral Surveyor
Craig P. Sylvester, Supervisory Cadastral Surveyor
Ferrel D. Reynolds, Cadastral Surveyor
having been critically examined and found correct, are hereby approved.

APR 14 1981 (Date) — (Chief, Cadastral Survey Examination and Approval Staff)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

(Date) — (Chief, Cadastral Survey Examination and Approval Staff)

R601

Form 9180-6
(March 1977)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

309

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF THE

NORTH BOUNDARY, THE SOUTH BOUNDARY

AND

SUBDIVISIONAL LINES

OF

TOWNSHIP 9 SOUTH, RANGE 23 EAST

Of the Salt Lake Meridian,

In the State of Utah.

EXECUTED BY

Gail E. Reynolds, Cadastral Surveyor

Craig P. Sylvester, Supervisory Cadastral Surveyor

Jerry L. Thomas, Supervisory Cadstral Surveyor

Ferrel D. Reynolds, Cadastral Surveyor

Under special instructions dated July 20, 1977, approved July 22, 1977,

, which provided for the surveys included under ~~U.S. Survey~~ Group Number 572, and assignment instructions dated July 20, 1977.

Survey commenced August 1, 19 77

Survey completed September 2, 19 77

INDEX DIAGRAM

Township 9 South, Range 23 East,

13 6 65 64	12 5 52 63	11 4 42 51	10 3 32 41	9 2 23 31	8 1 22
7 63 62	8 50 61	9 40 49	10 30 39	11 21 29	12 20
18 60 59	17 48 58	16 38 47	15 29 37	14 19 28	13 19
19 57 57	20 46 56	21 36 45	22 27 35	23 18 26	24 17
30 55 54	29 44 53	28 34 43	27 25 34	26 16 24	25 15
31 52 7	32 42 6	33 32 5	34 24 4	35 14 3	36 1

GPO 840-243

Township 9 South, Range 23 East, Salt Lake Meridian, Utah

CHAINS

The North, South, East and West boundaries, subdivisional lines and subdivision of sections were surveyed by D. G. Major in 1882 and suspended on August 15, 1903. The North, South, East, and West boundaries and subdivisional lines were surveyed by Talamantes and Heist in 1904. The east boundary was resurveyed concurrently under T. 9 S., R. 24 E. The west boundary was resurveyed concurrently under T. 9 S., R. 22 E.

The following field notes are those of a dependent resurvey of the North and South boundaries and the subdivisional lines of T. 9 S., R. 23 E., Salt Lake Meridian, Utah.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973 and the Special Instructions dated July 20, 1977.

The directions of the lines of this survey were determined by reference to the true meridians established on line by hour angle observations on Polaris. They were carried forward by sustained angulation, being supplemented by numerous other observations on Polaris taken throughout the progress of the survey.

Distances were determined by electronic measurement along survey lines. Distances to some topography are approximately as scaled from U.S.G.S. topographic sheets.

Before restoring lost corners, the lines of the original survey were retraced and a diligent search made for any evidence of the original corners. The rules of proportionate measurement were applied to ascertain the position of the lost corner after every reasonable possibility of finding direct evidence of the original corner had been exhausted.

The geographic position of the southeast corner of the township, as determined by ties to United States Geological Survey triangulation station "JEK 6 ET 6" dated 1966 located S. 45° 06' E., 19.464 chs. distance from the ¼ sec. cor. of secs. 25 and 30 on the west boundary of the township, is as follows:

Latitude 39° 59' 07" N. Longitude 109° 15' 56" W.

The mean magnetic declination is 14° 30' E.

Dependent Resurvey of the South Boundary of
T. 9 S., R. 23 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
Alfredo R. Talamantes and Harvey D. Heist, United
States Deputy Surveyors, in 1904

Beginning at the cor. of Tps. 9 and 10 S., Rs. 23 and 24 E., monumented with an iron post, 30 ins. long, 2½ ins. diam., set and mkd. as described in the field notes of the W. bdy. of T. 9 S., R. 24 E., executed concurrently under Group 568.

CHAINS	
	N. 89° 57' W., bet. secs. 1 and 36.
	Desc. a rolling W slope, through scattered shadscale and sagebrush.
14.90	Low spur, slopes S.
39.82	The ¼ sec. cor. of secs. 1 and 36, monumented with a sandstone, 22 x 8 x 5 ins., firmly set 10 ins. in the ground and plainly mkd. ¼ on N face, witnessed by a mound of stone, 3 ft. base, 1½ ft. high, to N.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 23 E ¼ S 36 / S 1 T 10 S R 23 E 1977
	Deposit the mkd. stone alongside the iron post.
	N. 89° 57' W., beginning new measurement.
	Over rolling desert land, through scattered shadscale and sagebrush.
	Desc. gentle NW slope.
20.00	Draw, drains NW irregularly.
31.20	Draw, drains N; asc. E slope.
39.97	The cor. of secs. 1, 2, 35, and 36, monumented with a sandstone, 20 x 10 x 9 ins., firmly set 10 ins. in the ground and plainly mkd. 5 notches on W and 1 notch on E edges.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a collar of stone to brass cap mkd.
	T 9 S R 23 E S 35 | S 36 S 2 | S 1 T 10 S R 23 E 1977
	Deposit the mkd. stone alongside the iron post.
	Set a steel fence post, 6 ft. high, alongside the iron post.

CHAINS	
	N. 89° 57' W., bet. secs. 2 and 35.
	Over broken desert land, through sagebrush and shadscale.
	Asc. E slope.
1.00	Trail road, bears NE and SW.
6.50	Spur, slopes NE.
8.50	Spur, slopes N.
27.00	Ridge, bears N and S; along N slope.
30.00	Spur, slopes NW; desc. SW slope.
37.00	Draw, drains N; asc. E slope.
39.91	The ¼ sec. cor. of secs. 2 and 35, monumented with a sandstone, 20 x 8 x 6 ins., firmly set 10 ins. in the ground, and plainly mkd. ¼ on N face.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base to brass cap mkd.
	T 9 S R 23 E ¼ S 35 / S 2 T 10 S R 23 E 1977
	Deposit the mkd. stone alongside the iron post.
	The cor. is located at the head of a draw, which drains N. 80° E.
	N. 89° 56' W., beginning new measurement.
	Asc. NE slope.
1.20	Spur, slopes NE.
7.00	Ridge, bears NW and SE irregularly; desc. along NW slope.
26.00	Draw, drains NE irregularly; asc. E slope.
31.00	Ridge, bears N and S; desc. W slope.
39.93	The cor. of secs. 2, 3, 34, and 35, monumented with a sandstone, 15 x 6 x 6 ins., firmly set 8 ins. in the ground and plainly mkd. with 2 notches on E and 4 notches on W edges. Witnessed by a mound of stone, 2 ft. base, 1½ ft. high to W.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

CHAINS	
	T 9 S R 23 E S 34 | S 35 S 3 | S 2 T 10 S R 23 E 1977 Deposit the mkd. stone alongside the iron post. Cor. is located on E edge of small hollow.
	N. 89° 58' W., bet. secs. 3 and 34. Over rolling desert land, through widely scattered shadscale and sagebrush. Desc. gentle W slope.
15.00	Slope changes; asc. SE slope.
27.00	Spur, slopes S; desc. NW slope.
40.01	The ¼ sec. cor. of secs. 3 and 34, monumented with a sandstone, 15 x 6 x 5 ins., firmly set in a mound of stone and dimly mkd. ¼ on N face. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base to brass cap mkd. T 9 S R 23 E ¼ S 34 / S 3 T 10 S R 23 E 1977 Deposit the mkd. stone alongside the iron post. Cor. is located on gentle SW slope.
	N. 89° 55' W., beginning new measurement. Desc. gentle SW slope.
7.00	Draw, drains N irregularly.
11.00	Draw, drains NW.
21.50	Draw, drains NE.
27.50	Trail road, bears N and SE.
35.15	Top of knoll slopes N.
40.11	The cor. of secs. 3, 4, 33, and 34, monumented with a sandstone, 16 x 5 x 4 ins., firmly set 10 ins. in the ground and plainly mkd. 3 notches on E and W edges. Witnessed by a mound of stone S.

CHAINS	
	At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to brass cap mkd. T 9 S R 23 E S 33 | S 34 S 4 | S 3 T 10 S R 23 E 1977 Deposit the mkd. stone alongside the iron post. Cor. is located on S side of small draw, which drains NE.
	N. 89° 54' W., bet. secs. 4 and 33. Over gently rolling desert land, through scattered sagebrush and shadscale.
38.20	Draw, drains N.
40.04	The ¼ sec. cor. of secs. 4 and 33, monumented with a sandstone, 18 x 8 x 5 ins., firmly set in a mound of stone and plainly mkd. ¼ on N face. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base to brass cap mkd. T 9 S R 23 E ¼ S 33 / S 4 T 10 S R 23 E 1977 Deposit the mkd. stone alongside the iron post. Cor. is located on top of low spur that slopes NE.
	N. 89° 58' W., beginning new measurement. Asc. NE slope.
17.50	Top of ridge, bears N and S; desc. SW slope.
39.94	The cor. of secs. 4, 5, 32, and 33, monumented with a sandstone, 20 x 8 x 6 ins., firmly set in a mound of stone and plainly mkd. 4 notches on E and 2 notches on W edges. At the corner point

CHAINS	
	Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base to brass cap mkd. T 9 S R 23 E S 32 | S 33 S 5 | S 4 T 10 S R 23 E 1977 Deposit the mkd. stone alongside the iron post. Set a steel fence post alongside the iron post.
	S. 89° 56' W., bet. secs. 5 and 32. Over broken desert land, through scattered sagebrush and shadscale. Desc. SW slope.
8.00	Draw, drains N. 20° W.; along meandering draw.
23.00	Same draw, drains S. 30° W.
27.00	Same draw, drains N. 45° W.
35.00	Same draw, drains S. 45° W.
36.00	Same draw, drains N. 60° W.
38.90	Draw, drains N.
39.93	The ¼ sec. cor. of secs. 5 and 32, monumented with a sandstone, 14 x 6 x 6 ins., firmly set 10 ins. in the ground and plainly mkd. ¼ on N face. Witnessed by a mound of stone to N. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base to brass cap mkd. T 9 S R 23 E ¼ S 32 / S 5 T 10 S R 23 E 1977 Deposit the mkd. stone alongside the iron post. Rebuild the original mound of stone, 3 ft. base, 2 ft. high to N. Set a 6 ft. steel fence post alongside the iron post. --- N. 89° 59' W., beginning new measurement.

CHAINS	
1.00	Trail road, bears NW and SE; asc. E slope.
18.80	Top of bluff, bears N and S; over top.
25.00	Draw, drains N.
40.03	The cor. of secs. 5, 6, 31 and 32, monumented with a sandstone, 19 x 8 x 6 ins., firmly set 6 ins. in the ground and plainly mkd. 5 notches on E and 1 notch on W edges.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock and in a collar of stone to brass cap mkd.
	T 9 S R 23 E S 31 | S 32 S 6 | S 5 T 10 S R 23 E 1977
	Deposit the mkd. stone alongside the iron post.
	Set a 6 ft. steel fence post alongside the iron post.
	West, bet. secs. 6 and 31.
	Over broken desert land, through scattered sagebrush and shadscale.
	Over top of bluff.
4.50	Desc. W slope along draw, drains W.
16.20	Draw, drains N; asc. SE slope.
32.25	Top of narrow plateau, which bears NE and SW; desc. NW slope.
40.08	The ¼ sec. cor. of secs. 6 and 31, monumented with a sandstone, 19 x 5 x 4 ins., firmly set 6 ins. in the ground and plainly mkd. ¼ on N face.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock and in a mound of stone, 4½ ft. base to brass cap mkd.
	T 9 S R 23 E ¼ S 31 / S 6 T 10 S R 23 E 1977
	Deposit the mkd. stone alongside the iron post.
	Cor. is located on NW slope.

Dependent Resurvey of the South Boundary of
T. 9 S., R. 23 E., Salt Lake Meridian, Utah

CHAINS	
	S. 89° 53' W., beginning new measurement.
3.00	Spur, slopes NW.
11.50	Spur, slopes N.
18.50	Spur, slopes N.
26.50	Bulldozed road, bears N and S.
32.50	Ridge, bears NW and SE; desc. gentle SW slope.
39.00	Draw, drains S.
39.47	The cor. of Tps. 9 and 10 S., Rs. 22 and 23 E., monumented with an iron post, 2½ ins. diam., extending 6 ins. out of the ground, set, mkd. and witnessed as described in the field notes of the E. bdy. of T. 9 S., R. 22 E., surveyed concurrently in this same Group.

Dependent Resurvey of the North Boundary of
T. 9 S., R. 23 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
Alfredo R. Talamantes and Harvey D. Heist, United
States Deputy Surveyors, in 1904

From the cor. of Tps 8 and 9 S., Rs. 23 and 24 E., monumented with an iron post, 3 ins. diam., extending 12 ins. out of the ground, with brass cap mkd. as described in the official record of the 1916 survey of the E. bdy. of T. 8 S., R. 23 E.

N. 89° 59' W., bet. secs. 1 and 36.

Over rolling desert land, through scattered sagebrush and shadscale.

Desc. SW slope.

5.00	Draw, drains NW; asc. gentle NE slope.
17.00	Spur, slopes NW; desc. along NW slope.
20.05	Point for the E. 1/16 sec. cor. of secs. 1 and 36.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 8 S R 23 E

$$E\ 1/16\ \frac{S\ 36}{S\ 1}$$

T 9 S R 23 E
1977

CHAINS	
	Set a 6 ft., 4 x 4 inch post alongside the iron post.
40.10	The ¼ sec. cor. of secs. 1 and 36, monumented with a sandstone, 18 x 12 x 4 ins., firmly set 8 ins. in the ground and plainly mkd. ¼ on N face.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 8 S R 23 E ¼ S 36 / S 1 T 9 S R 23 E 1977
	Deposit the mkd. stone alongside the iron post.
	Set a 6 ft. steel fence post alongside the iron post.
	N. 89° 51' W., beginning new measurement.
10.00	Enter nearly level land, bears NE and SW.
24.50	Draw, drains SW.
40.12	The cor. of secs. 1, 2, 35, and 36, monumented with a sandstone, 12 x 6 x 6 ins., firmly set 6 ins. in the ground and in an old fence line, which bears E and W. marks on rock have weathered away. This position is is harmoniously related to existing original cors. and is accepted as the best available evidence of the original cor. position.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 8 S R 23 E S 35 | S 36 S 2 | S 1 T 9 S R 23 E 1977
	Deposit the weathered stone alongside the iron post.
	N. 89° 59' W., bet. secs. 2 and 35.
	Over nearly level land, through scattered sagebrush and shadscale.
7.00	Draw, drains SE irregularly.

320

Dependent Resurvey of the North Boundary of
T. 9 S., R. 23 E., Salt Lake Meridian, Utah

CHAINS	
40.03	Point for the ¼ sec. cor. of secs. 2 and 35, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone to brass cap mkd. T 8 S R 23 E ¼ S 35 / S 2 T 9 S R 23 E 1977
59.20	Bulldozed road, bears N and S.
62.70	Draw, drains NE.
80.06	The cor. of secs. 2, 3, 34, and 35, monumented with a sandstone, 14 x 8 x 3 ins., firmly set in a small mound of stone with illegible marks. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to brass cap mkd. T 8 S R 23 E S 34 | S 35 S 3 | S 2 T 9 S R 23 E 1977 Deposit the mkd. stone alongside the iron post. Cor. is located in small cove at the base of clay hills facing E.
	N. 89° 50' W., bet. secs. 3 and 34. Asc. broken E slope, through mostly barren land.
2.60	Spur, slopes SE; over broken S slope.
15.20	Spur, slopes SW; desc. along broken SW slope.
39.98	The ¼ sec. cor. of secs. 3 and 34, monumented with a sandstone, 16 x 10 x 4 ins., firmly set in a mound of stone and dimly mkd. ¼ on N face. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to brass cap mkd.

☆ U.S. Government Printing Office-1978-778-206/433

CHAINS	
	T 8 S R 23 E ¼ S 34 / S 3 T 9 S R 23 E 1977
	Deposit the mkd. stone alongside the iron post.
	N. 89° 47' W., beginning new measurement.
	Over rolling desert land, through scattered sagebrush and shadscale.
11.00	Gas line, bears N and S., bulldozed road, bears NE and SW.
24.00	Spur, slopes S; desc. SW slope.
40.07	The cor. of secs. 3, 4, 33, and 34, monumented with a small mound of stone and old survey stake. This position is harmoniously related to existing original cors. and is accepted as the best available evidence of the original cor. position.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone to brass cap mkd.
	T 8 S R 23 E S 33 | S 34 S 4 | S 3 T 9 S R 23 E 1977
	S. 89° 55' W., bet. secs. 4 and 33.
	Over nearly level land, through sagebrush and shadscale.
5.00	Wash, 30 lks. wide, 5 ft. deep, drains SW irregularly.
40.02	The ¼ sec. cor. of secs. 4 and 33, monumented with a sandstone, 16 x 10 x 4 ins., firmly set 6 ins. in the ground and plainly mkd. ¼ on N face.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 8 S R 23 E ¼ S 33 / S 4 T 9 S R 23 E 1977

CHAINS	
	Deposit the mkd. stone alongside the iron post.
	N. 89° 52' W., beginning new measurement.
	Asc. gentle E slope, through scattered sagebrush and shadscale.
26.00	Ridge, bears N and S; desc. W slope.
32.50	Bulldozed road and underground gas line, bears S. 75° E. and N. 75° W.
40.07	The cor. of secs. 4, 5, 32, and 33, monumented with a small mound of stone, and old survey stake. This position is harmoniously related to existing original cors. and is accepted as the best available evidence of the original cor. position. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 8 S R 23 E S 32 | S 33 S 5 | S 4 T 9 S R 23 E 1977 Raise a mound of stone, 2½ ft. base, 1½ ft. high to N.
	S. 89° 56' W., bet. secs. 5 and 32.
	Over rolling S slope, through scattered sagebrush and shadscale.
5.00	Draw, drains S. irregularly.
38.00	Draw, drains SW irregularly.
39.75	The ¼ sec. cor. of secs. 5 and 32, monumented with a sandstone, 14 x 8 x 4 ins., firmly set 6 ins. in the ground and dimly mkd. ¼ on N face. This stone is the only stone in the immediate area. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 8 S R 23 E ¼ S 32 / S 5 T 9 S R 23 E 1977

CHAINS	
	Deposit the mkd. stone alongside the iron post. No available accessories.
	N. 89° 58' W., beginning new measurement. Over nearly level land, through scattered sagebrush and shadscale.
11.00	Asc. SE slope.
15.75	Top of spur, slopes SW; desc. NW slope.
26.00	Enter nearly level land; desc. gentle W slope.
40.01	Point for the cor. of secs. 5, 6, 31, and 32, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground and in a collar of stone, 4 ft. base to brass cap mkd. T 8 S R 23 E S 31 | S 32 S 6 | S 5 T 9 S R 23 E 1977 Cor. is located on S side of small draw that drains NW.
	N. 89° 58' W., bet. secs. 6 and 31. Over gently rolling desert land, through scattered sagebrush and shadscale.
40.01	Point for the ¼ sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the oiginal cor. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone to brass cap mkd. T 8 S R 23 E ¼ S 31 / S 6 T 9 S R 23 E 1977
78.77	True point for the cor. of Tps. 8 and 9 S., Rs. 22 and 23 E., from which its witness cor. bears S. 0° 14' E., 40 lks. dist., set, mkd. and witnessed as described in the field notes of the E. bdy. of T. 9 S., R. 22 E., surveyed concurrently in this same Group.

CHAINS	
	Dependent Resurvey of the Subdivisional Lines of T. 9 S., R. 23 E., Salt Lake Meridian, Utah
	Reestablishment of the Survey Executed by Alfredo R. Talamantes and Harvey D. Heist, United States Deputy Surveyors, in 1904
	From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., hereinbefore described.
	N. 0°05' E., bet. secs. 35 and 36.
	Over rolling desert land, through sagebrush and shadscale.
0.75	Trail road, bears NE and SW.
13.60	Draw, drains NW irregularly; asc. SW slope.
16.00	Spur, slopes W.
26.50	Spur, slopes NW; desc. NE slope.
39.96	The ¼ sec. cor. of secs. 35 and 36, monumented with a sandstone, 14 x 8 x 4 ins., firmly set 6 ins. in the ground, with no visible marks; witnessed by a mound of stone, 3 ft. base, 1½ ft. high to W, and is accepted as the best available evidence of the original cor. position.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 23 E ¼ S 35 | S 36 1977
	Deposit the unmarked stone alongside the iron post.
	North, beginning new measurement.
6.00	Draw, drains NW; asc. along W slope.
13.50	Spur, slopes W.
23.00	Spur, slopes W.
30.00	Spur, slopes W.
34.00	Spur, slopes W; desc. gentle N slope.
40.11	The cor. of secs. 25, 26, 35, and 36, monumented with a sandstone, 20 x 6 x 6 ins., firmly set 8 ins. in the ground and plainly mkd. 1 notch on E and S edges.
	At the corner point

U.S. Government Printing Office-1978-778-206/433

CHAINS	
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone to brass cap mkd. T 9 S R 23 E S 26 | S 25 S 35 | S 36 1977 Deposit the mkd. stone alongside the iron post. Set a 6 ft. steel fence post alongside the iron post.
	From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., set, mkd. and witnessed as described in the field notes of the W. bdy. of T. 9 S., R. 24 E., surveyed concurrently under Group 568.
	West, bet. secs. 25 and 36.
	Over broken desert land, through sagebrush and shadscale.
	Desc. NW slope.
16.30	Spur, slopes N; desc. W slope.
39.46	The ¼ sec. cor. of secs. 25 and 36, monumented with a sandstone, 24 x 8 x 6 ins., firmly set 10 ins. in the ground and dimly mkd. ¼ on N face. Witnessed by a mound of stone, 3 ft. base, 1½ ft. high to N.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 9 S R 23 E ¼ S 25 / S 36 1977 Deposit the mkd. stone alongside the iron post.
	S. 89° 52' W., beginning new measurement.
	Desc. W slope.
4.00	Draw, drains NW; over rolling land.
15.00	Bottom of hollow, drains N.
23.00	Spur, slopes N.
40.21	The cor. of secs. 25, 26, 35, and 36.

CHAINS	
	N. 0° 09' E., bet. secs. 25 and 26.
	Over broken desert land, through sagebrush and shadscale.
	Desc. general N slope.
7.00	Draw, drains NW.
11.00	Saddle on spur, bears NE and SW.
28.00	Draw, drains NE; asc. S slope.
33.00	Top of spur, slopes NE; desc. NW slope.
39.94	The ¼ sec. cor. of secs. 25 and 26, monumented with a sandstone, 12 x 8 x 4 ins., firmly set in a mound of stone and plainly mkd. ¼ on W face.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to brass cap mkd.
	T 9 S R 23 E ¼ S 26 | S 25 1977
	Deposit the mkd. stone alongside the iron post.
	N. 0° 03' E., beginning new measurement.
	Desc. N slope.
5.00	Draw, drains NE; along E slope.
14.00	Draw, drains W; asc. S slope.
16.80	Top of spur, slopes W; desc. N slope.
25.00	Top of knoll, bears NE and SW; along top of spur.
28.00	Top of small knoll; desc. NE slope.
40.02	The cor. of secs. 23, 24, 25, and 26, monumented with a sandstone, 16 x 10 x 6 ins., firmly set in a mound of stone and plainly mkd. 1 notch on E and 2 notches on S edges.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to brass cap mkd.

CHAINS	
	T 9 S R 23 E S 23 | S 24 S 26 | S 25 1977 Deposit the mkd. stone alongside the iron post.
	From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., set, mkd. and witnessed as described in the field notes of the W. bdy. of T. 9 S., R. 24 E., surveyed concurrently under Group 568.
	S. 89° 51' W., bet. secs. 24 and 25.
	Over broken desert land, through sagebrush and shadscale.
	Along S slope.
5.85	Spur, slopes SW; desc. NW slope.
24.50	Draw, drains NE irregularly.
33.00	Top of spur, slopes N; desc. W slope.
36.50	Draw, drains N; asc. E slope.
39.45	The ¼ sec. cor. of secs. 24 and 25, monumented with a sandstone, 20 x 8 x 5 ins., firmly set in a mound of stone and plainly mkd. ¼ on N face.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 23 E ¼ S 24 / S 25 1977
	Deposit the mkd. stone alongside the iron post.
	Raise a mound of stone, 3 ft. base, 2 ft. high to N.
	N. 89° 56' W., beginning new measurement.
3.00	Top of spur, slopes N; desc. along NW slope.
18.78	Underground gas line, bears N. 80° 54' W. and S. 66° 22' E.
20.30	Top of ridge bears NW and SE; desc. W slope.
26.00	Bottom of hollow, drains NW; asc. NE slope.
36.00	Spur, slopes NW; desc. W slope.

CHAINS	
39.50	Draw, drains N; asc. E slope.
40.26	The cor. of secs. 23, 24, 25, and 26.
	N. 0° 03' E., bet. secs. 23 and 24.
	Over broken desert land, through sagebrush and shadscale.
	Desc. NE slope.
4.00	Draw, drains NW; also underground gas line, which bears approximately N. 80° 54' W. and S. 80° 54' E.; S slope.
7.50	Spur, slopes W; along general W slope.
17.00	Spur, slopes W; desc. NW slope.
35.00	Draw, drains NW; asc. NE slope.
39.86	The ¼ sec. cor. of secs. 23 and 24, monumented with a ½ inch rebar and a mound of stone. This position is harmoniously related to existing original cors. and is accepted as the best available evidence of the original cor. position.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to brass cap mkd.
	T 9 S R 23 E
	¼
	S 23 | S 24
	1977
	Deposit the rebar alongside the iron post.
	N. 0° 01' E., beginning new measurement.
1.00	Top of raise; desc. NW slope.
31.00	Draw, drains E; along W edge of draw which drains N.
40.36	The cor. of secs. 13, 14, 23, and 24, monumented with a sandstone, 22 x 12 x 8 ins., firmly set 10 ins. in the ground and plainly mkd. 3 notches on S and 1 notch on E edges.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone to brass cap mkd.

Dependent Resurvey of the Subdivisional Lines
of T. 9 S., R. 23 E., Salt Lake Meridian, Utah

CHAINS	
	T 9 S R 23 E S 14 | S 13 S 23 | S 24 1977 Deposit the mkd. stone alongside the iron post. Cor. is located on the tip of low spur which slopes N.
	From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., set, mkd. and witnessed as described in the field notes of the W. bdy. of T. 9 S., R. 24 E., surveyed concurrently under Group 568. S. 89° 59' W., bet. secs. 13 and 24. Over gently rolling desert land, through sagebrush and shadscale.
7.50	Draw, drains N to NW.
24.00	Draw, drains NE.
25.00	Bulldozed road, bears N. 21° E. and S. 21° W.; asc. E slope.
35.00	Spur, slopes NE; desc. NW slope.
39.84	Point for the ¼ sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base to brass cap mkd. T 9 S R 23 E ¼ S 13 / S 24 1977 Continue along broken N slope.
65.20	Spur, slopes NW into saddle; desc. W slope.
79.00	Draw, drains NW.
79.68	The cor. of secs. 13, 14, 23, and 24.
	N. 0° 05' W., bet. secs. 13 and 14. Over broken desert land, through sagebrush and shadscale. Desc. gentle N slope.
1.00	Draw, drains NW; over nearly level land.

CHAINS	
11.00	Base of hill, bears SE and NW; asc. SW slope.
13.25	Spur, slopes W; desc. NW slope.
17.00	Base of hill, bears E and W; over rolling NW slope.
29.94	Four strand barb wire fence line, bears E and W.
39.97	The ¼ sec. cor. of secs. 13 and 14, monumented with a sandstone, 16 x 8 x 6 ins., firmly set in a mound of stone and plainly mkd. ¼ on W face. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone to brass cap mkd. T 9 S R 23 E ¼ S 14 | S 13 1977 Deposit the mkd. stone alongside the iron post.
	N. 0° 06' W., beginning new measurement.
9.00	Draw, drains W irregularly.
13.50	Improved graveled road, bears N. 85° E. and S. 85° W.
19.50	Draw, drains NW; asc. gentle S slope.
40.16	The cor. of secs. 11, 12, 13, and 14, monumented with a sandstone, 14 x 12 x 8 ins., firmly set in a mound of stone and plainly mkd. 1 notch on E and 4 notches on S edges. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 13 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to brass cap mkd. T 9 S R 23 E S 11 | S 12 S 14 | S 13 1977 Deposit the mkd. stone alongside the iron post.
	From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., set, mkd. and witnessed as described in the field notes of the W. bdy. of T. 9 S., R. 24 E., surveyed concurrently under Group 568.

CHAINS	
	West, bet. secs. 12 and 13.
	Over rolling desert land, through sagebrush and shadscale.
	Asc. NE slope.
4.57	Top of low ridge, bears NE and SW; desc. gradual W slope.
19.88	Point for the E. 1/16 sec. cor. of secs. 12 and 13.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 23 E
	E 1/16 S 12 / S 13
	1977
	Raise a mound of stone, 2 ft. base, 1½ ft. high to N.
39.76	Point for the ¼ sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 23 E
	¼ S 12 / S 13
	1977
	Raise a mound of stone, 2 ft. base, 1½ ft. high to N.
47.00	Draw, drains NW; asc. gentle E slope.
59.64	Point for the W. 1/16 sec. cor. of secs. 12 and 13.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 23 E
	W 1/16 S 12 / S 13
	1977
	Raise a mound of stone, 3½ ft. base, 2 ft. high to N.
69.00	Asc. point of spur, which slopes E.
79.52	The cor. of secs. 11, 12, 13, and 14.
	N. 0° 23' W., bet. secs. 11 and 12.
	Over rolling desert land, through sagebrush and shadscale.
	Asc. S slope.

CHAINS	
1.80	Top of spur, slopes E; desc. N slope.
5.00	Base of hill, bears SE and NW; over rolling desert land.
40.05	The ¼ sec. cor. of secs. 11 and 12, monumented with a sandstone, 12 x 8 x 4 ins., set alongside old survey stake. Part of the ¼ still visible on sandstone. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 9 S R 23 E ¼ S 11 | S 12 1977 Deposit the mkd. stone alongside the iron post.
	N. 0° 13' W., beginning new measurement.
3.00	Draw, drains W.
15.00	Draw, drains SW.
35.00	Bulldozed road, bears NE and SW.
39.81	The cor. of secs. 1, 2, 11, and 12, monumented with a broken sandstone, dimly mkd. alongside old survey stake. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 9 S R 23 E S 2 | S 1 S 11 | S 12 1977 Deposit the pieces of the broken stone alongside the iron post.
	From the true point for the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., from which the witness cor. bears S. 0° 06' W., 1.30 chs. dist., set, mkd. and witnessed as described in the field notes of the W. bdy. of T. 9 S., R. 24 E., surveyed concurrently under Group 568. S. 89° 58' W., bet. secs. 1 and 12. Over broken desert land, through sagebrush and shadscale.

CHAINS	
	Asc. gentle NE slope.
6.60	Spur, slopes N.
21.00	Low spur, slopes N; desc. along N slope.
33.00	Spur, slopes NW.
40.03	The ¼ sec. cor. of secs. 1 and 12, monumented with a sandstone, 20 x 8 x 4 ins., firmly set 10 ins. in the ground and plainly mkd. ¼ on N face.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 23 E
	¼ S 1 / S 12
	1977
	Deposit the mkd. stone alongside the iron post.
	S. 89° 41' W., beginning new measurement.
	Continue along N slope through series of washes and spurs.
39.98	The cor. of secs. 1, 2, 11, and 12.
	N. 0° 09' W., bet. secs. 1 and 2.
	Over rolling desert land, through sagebrush and shadscale.
	Desc. N slope.
10.00	Enter Coyote Wash area; through scattered willow growth.
40.09	Underground gas line, bears S. 80° E. and N. 80° W.
40.29	Point for the ¼ sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 23 E
	¼ / S 2 | S 1 / 1977
	No accessories available.
78.62	The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., hereinbefore described.

CHAINS	
	From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., hereinbefore described.
	N. 0° 03' E., bet. secs. 34 and 35.
	Over broken desert land, through sagebrush and shadscale.
	Asc. S slope.
10.25	Top of knoll, bears E and W; desc. N slope.
40.00	The ¼ sec. cor. of secs. 34 and 35, monumented with a sandstone, 14 x 8 x 5 ins., firmly set 5 ins. in the ground and plainly mkd. ¼ on W face. Witnessed by a mound of stone to W.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 23 E ¼ S 34 | S 35 1977
	Deposit the mkd. stone alongside the iron post.
	Rebuild original mound of stone, 3 ft. base, 2 ft. high.
	N. 0° 05' W., beginning new measurement.
7.50	Draw, drains NE; asc. SE slope.
23.50	Top of ridge, bears NE and SW; desc. NW slope.
40.00	The cor. of secs. 26, 27, 34, and 35, monumented with a sandstone, 16 x 12 x 8 ins., firmly set in a mound of stone and plainly mkd. 1 notch on S and 2 notches on E edges.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone to brass cap mkd.
	T 9 S R 23 E S 27 | S 26 S 34 | S 35 1977
	Deposit the mkd. stone alongside the iron post.
	From the cor. of secs. 25, 26, 35, and 36.
	S. 89° 56' W., bet. secs. 26 and 35.

CHAINS	
	Over rolling desert land, through sagebrush and shadscale.
36.50	Draw, drains N.
39.87	The ¼ sec. cor. of secs. 26 and 35, monumented with a sandstone, 18 x 6 x 4 ins., firmly set 8 ins. in the ground and plainly mkd. ¼ on N face. Witnessed by a mound of stone to N. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 9 S R 23 E ¼ S 26 / S 35 1977 Deposit the mkd. stone alongside the iron post. Rebuild original mound of stone, 3 ft. base, 2 ft. high to N.
	N. 89° 53' W., beginning new measurement.
15.00	Draw, drains NW; asc. gentle NE slope.
38.55	Low spur, slopes NW; desc. SW slope.
40.01	The cor. of secs. 26, 27, 34, and 35.
	N. 0° 03' E., bet. secs. 26 and 27. Over broken desert land, through sagebrush and shadscale. Desc. N slope.
6.00	Draw, drains NE; asc. SE slope.
10.50	Spur, slopes SW; along W slope.
16.50	Spur, slopes W.
22.00	Saddle on ridge, which bear NW and SE; desc. along E slope.
38.00	Spur, slopes NE.
40.03	The ¼ sec. cor. of secs. 26 and 27, monumented with a sandstone, 14 x 12 x 4 ins., firmly set in a mound of stone and dimly mkd. ¼ on W face. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone to brass cap mkd.

CHAINS	
	T 9 S R 23 E ¼ S 27 | S 26 1977 Deposit the mkd. stone alongside the iron post.
	N. 0° 02' E., beginning new measurement.
2.00	Draw, drains E; asc. SE slope.
7.20	Ridge, bears E and W; desc. N slope.
39.00	Draw, drains NE.
39.94	The cor. of secs. 22, 23, 26, and 27, monumented with a sandstone, 12 x 4 x 4 ins., firmly set in a mound of stone. Marks have weathered away. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone to brass cap mkd. T 9 S R 23 E S 22 | S 23 S 27 | S 26 1977 Deposit the unmkd. stone alongside the iron post.
	From the cor. of secs. 23, 24, 25, and 26. N. 89° 59' W., bet. secs. 23 and 26. Over rolling desert land, through sagebrush and shadscale. Asc. NE slope.
1.70	Spur, slopes N; desc. along N slope.
16.70	Draw, drains NE; asc. SE slope.
19.20	Spur, slopes NE; desc. along NW slope.
39.80	Trail road, bears NE and SW.
39.96	Point for the ¼ sec. cor. of secs. 23 and 26, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base to brass cap mkd.

Dependent Resurvey of the Subdivisional Lines
of T. 9 S., R. 23 E., Salt Lake Meridian, Utah

CHAINS	
	T 9 S R 23 E ¼ S 23 / S 26 1977
	Continue over rolling land.
44.80	Draw, drains N.
79.92	The cor. of secs. 22, 23, 26 and 27.
	N. 0° 02' W., bet. secs. 22 and 23.
	Over gently rolling land, through sagebrush and shadscale.
8.00	Base of hill, bears NE and SW; asc. SE slope.
13.70	Top of ridge, bears NE and SW; desc. NW slope.
17.00	Underground gas pipeline, bears N. 80° W. and S. 80° E.
30.00	Top of knoll, 6.00 chs. diam., desc. N slope.
35.00	Draw, drains W; asc. SW slope.
39.50	Top of spur, slopes SE; along E slope.
40.23	The ¼ sec. cor. of secs. 22 and 23, monumented with a sandstone, 14 x 6 x 6 ins., firmly set in a mound of stone and plainly mkd. ¼ on W face.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone to brass cap mkd.
	T 9 S R 23 E ¼ S 22 | S 23 1977
	Deposit the mkd. stone alongside the iron post.
	Cor. is located on steep E slope, 30 ft. below mesa top.
	N. 0° 09' W., beginning new measurement.
	Asc. along steep E slope.
2.40	Top of mesa, bears NE and SW; desc. gentle N slope.
40.26	The cor. of secs. 14, 15, 22, and 23, monumented with a sandstone, 14 x 6 x 4 ins., firmly set in a mound of stone and plainly mkd. 3 notches on S edge and no marks visible on E edge.
	At the corner point

Dependent Resurvey of the Subdivisional Lines
of T. 9 S., R. 23 E., Salt Lake Meridian, Utah

CHAINS	
	Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone to brass cap mkd. T 9 S R 23 E S 15 | S 14 S 22 | S 23 1977 Deposit the mkd. stone alongside the iron post.
	From the cor. of secs. 13, 14, 23, and 24.
	N. 89° 53' W., bet. secs. 14 and 23.
	Over broken desert land, through sagebrush and shadscale.
	Over gently rolling land.
8.50	Base of ascent; asc. SE slope.
12.00	Spur, slopes NE; along N slope.
20.00	Spur, slopes NW; desc. SW slope.
27.00	Foot of descent; over rolling land.
38.00	Draw, drains NE.
40.01	The ¼ sec. cor. of secs. 14 and 23, monumented with a sandstone, 20 x 10 x 3 ins., firmly set in a mound of stone and plainly mkd. ¼ on N face.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 9 S R 23 E ¼ S 14 S 23 1977 Deposit the mkd. stone alongside the iron post. Raise a mound of stone, 3 ft. base, 2 ft. high to N.
	N. 89° 47' W., beginning new measurement.
8.00	Trail raod, bears N and S.
15.00	Begin ascending SE slope.
23.00	Top of ridge, bears NE and SW; desc. NW slope.
38.00	Draw, drains N; over rolling land.
40.05	The cor. of secs. 14, 15, 22, and 23.

CHAINS	
	N. 0° 10' W., bet. secs. 14 and 15.
	Over broken desert land, through sagebrush and shadscale.
	Desc. gentle N slope.
4.50	Draw, drains W; asc. SW slope.
11.00	Spur, slopes NW; desc. gradual N slope.
39.94	Point for the ¼ sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 23 E ¼ S 15 | S 14 1977
	Raise a mound of stone, 2 ft. base, 2 ft. high to W.
40.05	Draw, drains NW.
62.00	Improved graveled road, bears N. 84° E. and S. 84° W.; asc. S slope.
67.00	Low ridge, bears NE and SW; desc. NW slope.
79.88	The cor. of secs. 10, 11, 14, and 15, monumented with a sandstone, 20 x 8 x 8 ins., firmly set in a mound of stone and plainly mkd. 4 notches on S and 2 notches on E edges.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone to brass cap mkd.
	T 9 S R 23 E S 10 | S 11 S 15 | S 14 1977
	Deposit the mkd. stone alongside the iron post.
	Cor. is located on steep W slope, 20 ft. below a small spur that projects S.
	From the cor. of secs. 11, 12, 13, and 14.
	S. 89° 51' W., bet. secs. 11 and 14.
	Over broken desert land, through sagebrush and shadscale.
	Along broken S slope.

CHAINS	
14.60	Saddle on spur, projects SW; desc. NW slope.
39.37	The ¼ sec. cor. of secs. 11 and 14, monumented with a sandstone, 12 x 8 x 4 ins., firmly set in a mound of stone and plainly mkd. ¼ on N face. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to brass cap mkd. T 9 S R 23 E ¼ S 11 / S 14 1977 Deposit the mkd. stone in mound alongside the iron post.
	N. 89° 52' W., beginning new measurement.
8.00	Draw, drains NW.
11.50	Draw, drains NE; asc. E slope.
14.50	Trail road, bears N and S.
20.00	Spur, slopes NE; desc. NW slope.
25.00	Draw, drains NE; asc. E slope.
37.00	Spur, slopes N; desc. W slope.
40.78	The cor. of secs. 10, 11, 14, and 15.
	N. 0° 05' W., bet. secs. 10 and 11. Over broken desert land, through sagebrush and shadscale. Asc. SW slope.
1.50	Spur, slopes W; desc. N slope.
10.00	Draw, drains W; asc. S slope.
25.00	Top of low ridge, bears E and W; desc. gradual N slope.
40.10	Point for the ¼ sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 9 S R 23 E ¼ S 10 | S 11 1977

CHAINS	
	Raise a mound of stone, 2 ft. base, 1 ft. high to W.
52.00	Draw, drains NW; enter Coyote Wash area.
60.15	Point for the N. 1/16 sec. cor. of secs. 10 and 11.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 9 S R 23 E N 1/16 S 10 | S 11 1977
	Set 2 x 6 in. post, 4 ft. deep, extending 6 ft. out of the ground alongside the iron post.
80.20	Point for the cor. of secs. 2, 3, 10, and 11, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam. 24 ins. in the ground, with brass cap mkd. T 9 S R 23 E S 3 | S 2 S 10 | S 11 1977
	Set 2 x 8 in. post, 4 ft. deep, extending 6 ft. out of the ground alongside the iron post.
	Cor. is located on E edge of wash area.
	From the cor. of secs. 1, 2, 11, and 12.
	N. 89° 50' W., bet. secs. 2 and 11.
	Over rolling desert land, through sagebrush and shadscale.
	Along N slope.
5.50	Low spur, slopes N; desc. NW slope.
39.72	The ¼ sec. cor. of secs. 2 and 11, monumented with a sandstone, 12 x 10 x 3 ins., firmly set 5 ins. in the ground, with a dimly mkd. ¼ on N face.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 9 S R 23 E ¼ S 2 / S 11 1977

CHAINS	
	Deposit the mkd. stone alongside the iron post.
	N. 89° 42' W., beginning new measurement.
20.00	Enter Coyote Wash area, drains SW.
40.11	The cor. of secs. 2, 3, 10, and 11.
	N. 0° 32' W., bet. secs. 2 and 3.
	Over gently rolling desert land, through sagebrush and shadscale.
	Asc. gentle S slope through wash area.
29.40	Small rise, bears SE and NW.
40.10	The ¼ sec. cor. of secs. 2 and 3, monumented with a small mound of weathered sandstone. Only rocks in the area and is harmoniously related to existing original cors. and is accepted as the best available evidence of the original cor. position.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 23 E
	¼
	S 3 | S 2
	1977
	Cor. is located on N side of sand dune.
	N. 0° 10' W., beginning new measurement.
0.25	Draw, drains SE; begin ascending SW slope.
8.30	Trail road, over underground gas line, bears S. 86° E. and N. 86° W.
23.00	Trail road, bears E and W.
30.00	Asc. broken S slope.
36.20	Spur, slopes SE; desc. NE slope.
38.21	The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., hereinbefore described.
	From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., hereinbefore described.

☆ GPO 1980—680-288/121

CHAINS	
	N. 0° 05' W., bet. secs. 33 and 34.
	Over gently rolling desert land, through sagebrush and shadscale.
	Desc. NE slope.
1.00	Draw, drains NE.
10.00	Low spur, slopes NE.
27.00	Draw, drains E.
30.00	Trail road, bears NW and SE.
40.01	The ¼ sec. cor. of secs. 33 and 34, monumented with a sandstone, 16 x 8 x 2 ins., firmly set 10 ins. in the ground plainly mkd. ¼ on W face.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a collar of stone to brass cap mkd.
	T 9 S R 23 E ¼ S 33 | S 34 1977
	Deposit the mkd. stone alongside the iron post.
	Cor. is located on gentle E slope.
	N. 0° 02' W., beginning new measurement.
	Continue along gentle E slope.
11.60	Begin desc. of gentle NE slope.
39.86	The cor. of secs. 27, 28, 33, and 34, monumented with a limestone, 18 x 6 x 6 ins., firmly set and plainly mkd. 1 notch on S and 3 notches on E edges. Witnessed by 4 mounds of stone (one in each section).
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 5 ft. base to brass cap mkd.
	T 9 S R 23 E S 28 | S 27 S 33 | S 34 1977
	Deposit the mkd. stone in mound alongside the iron post.

CHAINS	
	Cor. is located at the head of small draw, which drains N into main draw.
	From the cor. of secs. 26, 27, 34, and 35.
	N. 89° 54' W., bet. secs. 27 and 34.
	Over rolling desert land, through sagebrush and shadscale.
	Desc. NW slope.
8.00	Draw, drains NW.
26.00	Draw, drains NW.
39.94	The ¼ sec. cor. of secs. 27 and 34, monumented with a sandstone, 12 x 10 x 3 ins., firmly set in a mound of stone and dimly mkd. ¼ on N face.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base to brass cap mkd.
	T 9 S R 23 E
	¼ S 27 / S 34
	1977
	Deposit the mkd. stone in mound alongside the iron post.
	S. 89° 53' W., beginning new measurement.
21.50	Draw, drains NW.
38.70	Draw, drains NW.
40.24	The cor. of secs. 27, 28, 33, and 34.
	N. 0° 03' E., bet. secs. 27 and 28.
	Over broken desert land, through sagebrush and shadscale.
	Desc. broken E slope.
9.50	Draw, drains NW; along bottom of draw.
12.50	Same draw, drains E; asc. SE slope.
14.50	Spur, slopes E; desc. NE slope.
19.00	Same draw, drains NW; along bottom of draw.
23.00	Same draw, drains NE; asc. along E slope.
37.50	Spur, slopes NE; desc. NE slope.

CHAINS	
40.01	The ¼ sec. cor. of secs. 27 and 28, monumented with a sandstone, 14 x 9 x 6 ins., firmly set 5 ins. in the ground and plainly mkd. ¼ on W face. Witnessed by four small mounds of stone (two mounds to E and two to W). At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 9 S R 23 E ¼ S 28 | S 27 1977 Deposit the mkd. stone alongside the iron post. Destroy original mound of stone and raise a mound of stone, 3 ft. base, 2 ft. high to W.
	N. 0° 08' W., beginning new measurement.
1.50	Bottom of hill; along E slope.
17.50	Spur, slopes E.
33.00	Draw, drains NW; asc. SW slope.
39.99	The cor. of secs. 21, 22, 27, and 28, monumented with a sandstone, 14 x 10 x 4 ins., firmly set 8 ins. in the ground and plainly mkd. 3 notches on E and 2 on S edges. Witnessed by four mounds of stone (one in each section and a mound of stone to W). At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 9 S R 23 E S 21 | S 22 S 28 | S 27 1977 Deposit the mkd. stone alongside the iron post. Destroy the four small mounds of stone and rebuild the mound of stone, 3½ ft. base, 3 ft. high to W.
	From the cor. of secs. 22, 23, 26, and 27. N. 89° 53' W., bet. secs. 22 and 27. Over broken desert land, through sagebrush and shadscale. Asc. gentle E slope.

CHAINS	
18.00	Slope changes; asc. steep E slope.
24.00	Saddle on ridge, bears N and S; desc. NW slope.
28.00	Draw, drains N; asc. E slope.
32.70	Spur, slopes N; desc. NW slope.
37.00	Draw, drains N; asc. NE slope.
40.00	The ¼ sec. cor. of secs. 22 and 27, monumented with a sandstone, 18 x 7 x 5 ins., firmly set 8 ins. in the ground with no visible markings. Witnessed by a mound of stone to N. Also old survey stake alongside the cor. This position is harmoniously related to existing original cors. and is accepted as the best available evidence of the original cor. position. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to brass cap mkd. T 9 S R 23 E ¼ S 22 / S 27 1977 Deposit the unmarked stone alongside the iron post.
	S. 89° 56' W., beginning new measurement.
1.40	Spur, slopes NW; along NE slope.
6.90	Spur, slopes NW; desc. SE slope.
10.00	Draw, drains NW; asc. NE slope.
13.00	Ridge, bears SE and NW; desc. along S slope.
37.00	End of point of ridge; desc. SW slope.
40.31	The cor. of secs. 21, 22, 27, and 28.
	N. 0° 04' W., bet. secs. 21 and 22. Over broken desert land, through sagebrush and shadscale. Asc. SW slope.
3.30	Spur, slopes W; desc. N slope.
17.00	Draw, drains W; asc. S slope.
19.50	Spur, slopes SW; desc. along W slope.
27.00	Bulldozed road over underground gas line, bears SE and NW.
36.50	Draw, drains W.

CHAINS	
39.78	The ¼ sec. cor. of secs. 21 and 22, monumented with a sandstone, 14 x 10 x 4 ins., firmly set and plainly mkd. ¼ on W face. Witnessed by four mounds of stone (two mounds to E and two to W). At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a collar of stone to brass cap mkd. T 9 S R 23 E ¼ S 21 | S 22 1977 Deposit the mkd. stone alongside the iron post.
	N. 0° 06' W., beginning new measurement. Along general W slope.
8.75	Spur, slopes NW; along NW slope.
29.00	Draw, drains W; along W slope.
40.20	The cor. of secs. 15, 16, 21, and 22, monumented with a steel rebar in the center of a aerial photo target. This position is harmoniously related to existing original cors. and is accepted as the best available evidence of the original cor. position. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, over rebar and in a collar of stone to brass cap mkd. T 9 S R 23 E S 16 | S 15 S 21 | S 22 1977
	From the cor. of secs. 14, 15, 22, and 23. S. 89° 20' W., bet. secs. 15 and 22. Over rolling desert land, through sagebrush and shadscale. Along general N slope.
11.00	Draw, drains N.
22.00	Spur, slopes N.

CHAINS	
40.04	The ¼ sec. cor. of secs. 15 and 22, monumented with a steel rebar in a collar of stone. This position is harmoniously related to existing original cors., has long been recognized as the cor. by local surveyors, and is accepted as the best available evidence of the original cor. position. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground over rebar, with brass cap mkd. T 9 S R 23 E ¼ S 15 / S 22 1977 Raise a mound of stone, 2 ft. base, 1½ ft. high to N.
	West, beginning new measurement.
2.25	Trail road, bears SE and NW.
10.50	Draw, drains NW.
15.75	Draw, drains N.
21.00	Improved graveled road, bears NE and SW.
29.50	Same road, bears N and S; asc. E slope.
33.30	Top of ridge, bears N and S; desc. W slope.
40.27	The cor. of secs. 15, 16, 21, and 22.
	N. 0° 07' E., bet. secs. 15 and 16. Over broken desert land, through sagebrush and shadscale. Along W slope.
8.20	Improved graveled road, bears NE and SW. Also junction of trail road, bears W; along broken E slope.
22.50	Spur, slopes E.
29.00	Spur, slopes NE; desc. N slope.
36.50	Saddle on spur, projects N. 10° E.; along W slope.
39.50	Spur, slopes NW; desc. NE slope.
40.03	The ¼ sec. cor. of secs. 15 and 16, monumented with a mound of weathered sandstone, 3 ft. base, 2 ft. high. No markings identified. This position is harmoniously related to exisitng original cors. and is accepted as the best available evidence of the original cor. position.

CHAINS	
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone to brass cap mkd.
	T 9 S R 23 E ¼ S 16 | S 15 1977
	Raise a mound of stone, 3½ ft. base, 2 ft. high to W.
	Set a cottonwood post, 4 ft. high alongside the iron post.
	N. 0° 10' W., beginning new measurement.
2.00	Slope changes; asc. SE slope.
7.00	Top of breaks, bears NE and SW; desc. along W slope.
29.00	Enter bottom land along Coyote Wash.
40.16	Point for the cor. of secs. 9, 10, 15, and 16, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 23 E S 9 | S 10 S 16 | S 15 1977
	Raise a mound of stone, 2½ ft. base, 2 ft. high to N.
	Set 6 ft. steel fence post alongside the iron post.
	Cor. is located on E bank of Coyote Wash.
	From the cor. of secs. 10, 11, 14, and 15.
	S. 89° 54' W., bet. secs. 10 and 15.
	Over broken desert land, through sagebrush and shadscale.
	Desc. W slope.
1.00	Bottom of hill; along N slope.
21.70	Spur, slopes N; desc. along NW slope.
39.26	Point selected for the witness cor. to the ¼ sec. cor. of secs. 10 and 15.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

CHAINS	
	W C T 9 S R 23 E ¼ < S 10 / S 15 1977
	Raise a mound of stone, 3 ft. base, 2 ft. high to N.
40.06	True point for the ¼ sec. cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of the original cor. This point falls in Coyote Wash, which drains S and is unsafe to monument.
49.50	Bulldozed road, bears SE and NW.
57.00	Low ridge, bears NE and SW; desc. SW slope.
60.09	Point for the W 1/16 sec. cor. of secs. 10 and 15.
	Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to brass cap mkd.
	T 9 S R 23 E W 1/16 S 10 / S 15 1977
62.00	Draw, drains S; desc. along SW slope.
80.12	The cor. of secs. 9, 10, 15, and 16.
	N. 0° 15' W., bet. secs. 9 and 10.
	Over rolling desert land, through sagebrush and shadscale.
	Along E bank of Coyote Wash.
8.00	Asc. S slope.
13.00	Spur, slopes SE; desc. general N slope.
27.50	Bulldozed road, bears SE and NW.
40.16	The ¼ sec. cor. of secs. 9 and 10, monumented with a scattered mound of stone. This position is harmoniously related to existing original cors. and is accepted as the best available evidence of the original cor. position.
	At the corner point (center of mound)
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 23 E ¼ S 9 | S 10 1977

CHAINS	
	Raise a mound of stone, 3 ft. base, 2 ft. high to W.
	Cor. is located at the head of small hollow, which drains W.
	N. 0° 03' W., beginning new measurement.
	Asc. S slope.
4.50	Top of sandy ridge, bears E and W; desc. rolling N slope.
19.00	Draw, drains NW irregularly; over gently rolling land.
40.08	Point for the cor. of secs. 3, 4, 9, and 10, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 23 E
	S 4 | S 3 / S 9 | S 10
	1977
	Set a 6 ft. steel fence post alongside the iron post.
	From the cor. of secs. 2, 3, 10, and 11.
	S. 89° 55' W., bet. secs. 3 and 10.
	Over rolling desert land, through sagebrush and shadscale.
	Through bottom land along Coyote Wash.
2.00	Coyote Wash, drains S; over wash area.
6.00	Draw, drains SW irregularly.
10.50	Draw, drains S irregularly; begin ascending E slope.
40.11	Point for the ¼ sec. cor. of secs. 3 and 10, at proportionate distance. A sandstone, 12 x 8 x 4 ins., with a dimly mkd. ¼ on it was found lying loosely on the ground.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 23 E
	¼ S 3 / S 10
	1977
	Deposit the mkd. stone alongside the iron post.
42.00	Top of spur, slopes NE; desc. NW slope.
46.00	Draw, drains N; asc. E slope.

CHAINS	
52.50	Spur, slopes N; desc. NW slope.
80.22	The cor. of secs. 3, 4, 9, and 10.
	N. 0° 13' W., bet. secs. 3 and 4.
	Over rolling desert land, through sagebrush and shadscale.
	Along gentle rolling W slope.
3.00	Draw, drains W irregularly.
19.50	Draw, drains SW irregularly.
25.00	Spur, slopes SW.
39.00	Trail road, bears NE and SW.
40.08	The ¼ sec. cor. of secs. 3 and 4, monumented with a sandstone, 14 x 12 x 4 ins., firmly set 5 ins. in the ground without any visible markings. This rock is foreign to the area and harmoniously related to existing original cors. and is accepted as the best available evidence of the original cor. position.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 23 E ¼ S 4 | S 3 1977
	Deposit the unmarked stone alongside the iron post.
	N. 0° 15' W., beginning new measurement.
4.70	Top of low sand dune, bears NE and SW.
17.00	Draw, drains SW.
20.50	Bulldozed road, over underground gas line, bears S. 75° E. and N. 75° W.
38.60	The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., hereinbefore described.
	From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., hereinbefore described.
	N. 0° 02' W., bet. secs. 32 and 33.
	Over rolling desert land, through sagebrush and shadscale.
	Desc. NW slope.

Dependent Resurvey of the Subdivisional Lines
of T. 9 S., R. 23 E., Salt Lake Meridian, Utah

CHAINS	
40.04	Point for the ¼ sec. cor. of secs. 32 and 33, at proportionate distance. A sandstone, 15 x 6 x 4 ins., was found lying loosely on the ground with a dimly mkd. ¼ on the face. The cor. has been dislocated by a bulldozer. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 9 S R 23 E ¼ S 32 | S 33 1977 Deposit the mkd. stone alongside the iron post. Raise a mound of stone, 3 ft. base, 2 ft. high to W.
43.00	Draw, drains W irregularly; asc. S slope.
52.00	Low ridge, bears E and W; over gently rolling land.
64.20	Low ridge, bears E and W; desc. NW slope.
80.08	The cor. of secs. 28, 29, 32, and 33, monumented with a sandstone, 20 x 12 x 4 ins., firmly set in a mound of stone and plainly mkd. 1 notch on S and 4 notches on E edges. Witnessed by a 2 inch iron pipe, extending 4 ft. out of the ground alongside. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a collar of stone to brass cap mkd. T 9 S R 23 E S 29 | S 28 S 32 | S 33 1977 Deposit the mkd. stone alongside the iron post. Set a 6 ft. steel fence post alongside the iron post.
	From the cor. of secs. 27, 28, 33, and 34. S. 89° 59' W., bet. secs. 28 and 33. Over rolling desert land, through sagebrush and shadscale. Asc. E slope.
5.40	Spur, slopes N; desc. NW slope.
14.50	Draw, drains NW; asc. gentle NE slope.

CHAINS	
26.00	Trail road, bears N and S.
42.37	The ¼ sec. cor. of secs. 28 and 33, monumented with a sandstone, 16 x 8 x 8 ins., firmly set 6 ins. in the ground and plainly mkd. ¼ on N face. Witnessed by a mound of stone to N. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 9 S R 23 E ¼ S 28 / S 33 1977 Deposit the mkd. stone alongside the iron post. Rebuild original mound of stone, 2 ft. base, 1½ ft. high to N.
	N. 89° 32' W., beginning new measurement. Begin ascending gentle SW slope.
28.00	Draw, drains NW; asc. gentle NE slope.
34.00	Trail road, bears SE and NW.
37.58	The cor. of secs. 28, 29, 32, and 33.
	N. 0° 01' W., bet. secs. 28 and 29. Over rolling desert land, through sagebrush and shadscale. Desc. gentle N slope.
10.00	Trail road, bears SE and NW.
22.00	Draw, drains NW; asc. S slope.
28.20	Spur, slopes W; desc. NW slope.
40.04	The ¼ sec. cor. of secs. 28 and 29, monumented with a sandstone, 12 x 10 x 4 ins., firmly set 6 ins. in the ground and dimly mkd. ¼ on W face. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone to brass cap mkd.

CHAINS	
	T 9 S R 23 E ¼ S 29 | S 28 1977
	Deposit the mkd. stone alongside the iron post.
	N. 0° 01' E., beginning new measurement.
19.00	Draw, drains NW; asc. SW slope.
23.65	Five inch gas line, bears S. 45° 28' E. and N. 59° 17' W., alongside a bulldozed road; desc. gentle W slope.
39.90	Improved graveled road, bears NE and SW.
40.04	Point for the cor. of secs. 20, 21, 28, and 29, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a collar of stone to brass cap mkd.
	T 9 S R 23 E S 20 | S 21 S 29 | S 28 1977
	Raise a mound of stone, 4 ft. base, 3 ft. high to W.
	From the cor. of secs. 21, 22, 27 and 28.
	N. 89° 53' W., bet. secs. 21 and 28.
	Over broken desert land, through sagebrush and shadscale.
	Desc. SW slope.
6.50	Draw, drains NW; asc. NE slope.
15.00	Spur, slopes N; desc. NW slope.
20.50	Draw, drains N; asc. NE slope.
35.50	Spur, slopes N; desc. along N slope.
38.50	Spur, slopes N.
39.94	The ¼ sec. cor. of secs. 21 and 28, monumented with a sandstone, 15 x 8 x 6 ins., firmly set 4 ins. in the ground and plainly mkd. ¼ on N face.
	At the corner point

CHAINS	
	Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base to brass cap mkd.
	T 9 S R 23 E
	¼ S 21 / S 28
	1977
	Deposit the mkd. stone alongside the iron post.
	Cor. is located on NW slope.
	N. 89° 32' W., beginning new measurement.
0.60	Draw, drains NW; asc. along NE slope.
11.00	Top of ridge, bears NW and SE; desc. SW slope.
17.00	Bottom of canyon, drains N; asc. broken E slope.
39.60	Improved graveled road, bears NE and SW.
39.93	The cor. of secs. 20, 21, 28, and 29.
	North, bet. secs. 20 and 21.
	Over broken desert land, through sagebrush and shadscale.
	Asc. S slope.
3.50	Top of ridge, bears E and W; desc. NE slope.
10.50	Spur, slopes NE; desc. NW slope.
29.00	Bulldozed road, alongside 12 inch gas line, bears S. 78° 30' E. and N. 78° 30' W.
32.00	Draw, drains NE; asc. along NE slope.
40.04	The ¼ sec. cor. of secs. 20 and 21, monumented with a sandstone, 18 x 12 x 6 ins., firmly set in a mound of stone and plainly mkd. ¼ on W face.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to brass cap mkd.
	T 9 S R 23 E
	¼ S 20 | S 21
	1977

Dependent Resurvey of the Subdivisional Lines
of T. 9 S., R. 23 E., Salt Lake Meridian, Utah

CHAINS	
	Deposit the mkd. stone in mound alongside the iron post.
	N. 0° 01' W., beginning new measurement.
7.20	Top of low ridge, bears E and W; desc. NW slope.
22.00	Spur, slopes W; desc. broken NW slope.
36.50	Draw, drains NE; asc. SE slope.
38.00	Top of shelf, bears NE and W; over level land.
39.78	The cor. of secs. 16, 17, 20, and 21, monumented with a sandstone, 24 x 9 x 9 ins., firmly set in a mound of stone, no markings identified. This position is harmoniously related to existing original cors. and is accepted as the best available evidence of the original cor. position. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base to brass cap mkd. T 9 S R 23 E S 17 | S 16 S 20 | S 21 1977 Deposit the unmarked stone in mound alongside the iron post.
	From the cor. of secs. 15, 16, 21, and 22.
	N. 89° 50' W., bet. secs. 16 and 21.
	Over broken desert land, through sagebrush and shadscale.
	Desc. W slope.
8.20	Draw, drains N; asc. E slope.
11.00	Improved graveled road, bears N and S.
15.00	Top of rise; desc. along the foot of N slope.
36.50	Spur, slopes N; desc. NW slope.
39.87	Point for the ¼ sec. cor. of secs. 16 and 21, at proportionate distance; there is no remaining evidence of the original cor. position. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines
of T. 9 S., R. 23 E., Salt Lake Meridian, Utah

CHAINS	
	T 9 S R 23 E
	¼ S 16 / S 21
	1977
	Raise a mound of stone, 4 ft. base, 3 ft. high to N.
40.20	Draw, drains SW; along N side of draw.
52.90	Same draw, drains N; asc. E slope.
55.00	Spur, slopes N; along N slope.
58.40	Spur, slopes N; desc. NW slope.
62.00	Same draw, drains W; along bottom of draw.
72.00	Leave draw, drains NW; asc. NE slope.
75.00	Spur, slopes N; desc. NW slope.
77.50	Draw, drains NE; asc. SE slope.
78.70	Top of shelf, bears NW and SW; over level land.
79.74	The cor. of secs. 16, 17, 20, and 21.
	N. 0° 11' W., bet. secs. 16 and 17.
	Over broken desert land, through sagebrush and shadscale.
	At edge of shelf; desc. N slope.
1.00	Draw, drains NE; asc. SE slope.
6.90	Top of small mesa, bears E and W; desc. NW slope.
28.50	Draw, drains W; asc. S slope.
30.50	Spur, slopes W; desc. N slope.
37.00	Enter hollow, bears NE and SW.
40.02	The ¼ sec. cor. of secs. 16 and 17, monumented with a sandstone, 20 x 8 x 6 ins., firmly set 5 ins. in the ground and plainly mkd. ¼ on W face.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 5 ins. in the ground to bedrock in a mound of stone, 4 ft. base brass cap mkd.
	T 9 S R 23 E
	¼ S 17 | S 16
	1977
	Deposit the mkd. stone in mound alongside the iron post.

CHAINS	
	N. 0° 03' W., beginning new measurement.
7.00	Bottom of hollow, drains W irregularly; asc. S slope.
15.00	Leave hollow, bears E and W; asc. broken S slope.
25.50	Top of ridge, bears E and W; desc. N slope.
37.00	Enter bottom land along Coyote Wash, drains SW.
39.98	True point for the cor. of secs. 8, 9, 16, and 17, at proportionate distance, falls in Coyote Wash; there is no remaining evidence of the original cor.
	From the cor. of secs. 9, 10, 15, and 16.
	N. 89° 58' W., bet. secs. 9 and 16.
	Over wash area and broken desert land, through sagebrush, shadscale and willow growth.
0.10	Coyote Wash, drains N.
1.50	Leave same wash; asc. gentle E slope.
5.00	Low spur, slopes N; desc. gentle W slope.
10.00	Enter low land along Coyote Wash, bears NE and SW.
16.00	Leave low land along Coyote Wash, bears NE and SW; asc. SE slope.
22.00	Top of low spur, slopes S; desc. SW slope.
31.00	Enter low land along Coyote Wash, bears N and S.
39.95	Point for the ¼ sec. cor. of secs. 9 and 16, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to brass cap mkd.
	T 9 S R 23 E
	¼ S 9 / S 16
	1977
	Cor. is located at the foot of spur, bears NW and SE.
	Asc. NE slope.
43.00	Spur, slopes N; desc. along gentle N slope.
79.10	Point selected for the witness cor. to the cor. of secs. 8, 9, 16, and 17.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

CHAINS	
	W C T 9 S R 23 E S 8 | S 9 S 17 | S 16 1977
	Raise a mound of stone, 2 ft. base, 1 ft. high to W.
79.45	Left bank of Coyote Wash, bears N and S; over wash area.
79.90	True point for the cor. of secs. 8, 9, 16, and 17.
	N. 0° 04' W., bet. secs. 8 and 9.
	Over broken desert land, through sagebrush, shadscale and willow growth.
	Over nearly level land along wash area.
14.00	Leave Coyote Wash, bears E and SW; asc. S slope.
23.00	Top of saddle on low ridge, bears E and W; desc. gentle N slope.
39.98	The ¼ sec. cor. of secs. 8 and 9, monumented with a sandstone, 20 x 10 x 4 ins., firmly set 10 ins. in the ground and dimly mkd. ¼ on W face.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone to brass cap mkd.
	T 9 S R 23 E ¼ | S 8 | S 9 | 1977
	Deposit the mkd. stone alongside the iron post.
	N. 0° 20' W., beginning new measurement.
	Over rolling sand dunes, through sagebrush, shadscale and bunch grass.
	Asc. gentle S slope.
5.00	Bulldozed road, bears E and W.
17.00	Top of sandy spur, slopes SW; desc. NW slope.
22.00	Draw, drains SW; asc. S slope.
27.00	Top of sand dunes, bears NE and SW; over sand dunes.
35.00	Desc. N slope of sand dunes.

CHAINS	
37.00	Base of sand dunes, bears NE and SW; over nearly level land.
40.11	The cor. of secs. 4, 5, 8, and 9, monumented with an old cottonwood post set in a mound of stone. This position is harmoniously related to existing original cors. and is accepted as the best available evidence of the original cor. position. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone with brass cap mkd. T 9 S R 23 E S 5 | S 4 S 8 | S 9 1977
	From the cor. of secs. 3, 4, 9, and 10. S. 89° 59' W., bet. secs. 4 and 9. Over rolling desert land, through sagebrush and shadscale. Desc. gentle W slope.
6.50	Bulldozed road, bears N and S.
14.00	Draw, drains SW; asc. gentle SE slope.
32.50	Top of low clay hills, bears NE and SW; desc. NW slope.
40.07	The ¼ sec. cor. of secs. 4 and 9, monumented with an old survey stake in scattered mound of stone. This position is harmoniously related to existing original cors. and is accepted as the best available evidence of the original cor. position. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a collar of stone to brass cap mkd. T 9 S R 23 E ¼ S 4 / S 9 1977 Cor. is located on low barren clay hill.
	S. 89° 47' W., beginning new measurement. Over rolling desert land.
39.89	The cor. of secs. 4, 5, 8, and 9.

CHAINS	
	N. 0° 18' W., bet. secs. 4 and 5.
	Over rolling desert land, through sagebrush and shadscale.
	Desc. gentle N slope.
17.00	Draw, drains W; asc. rolling S slope.
21.00	Spur, slopes W; desc. N slope.
27.00	Draw, drains W; asc. along rolling W slope.
40.15	The ¼ sec. cor. of secs. 4 and 5, monumented with a mound of stone. These stones are the only stones in the area and are accepted as the best available evidence of the original cor. position.
	At the corner point (center of mound)
	Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to brass cap mkd.
	T 9 S R 23 E ¼ S 5 | S 4 1977
	N. 0° 23' W., beginning new measurement.
15.00	Draw, drains SW.
18.00	Same draw, drains SE; asc. along SW slope.
38.70	The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., hereinbefore described.
	From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., hereinbefore described.
	N. 0° 02' E., bet. secs. 31 and 32.
	Over broken desert land, through sagebrush and shadscale.
	Across nearly level bench top.
5.00	Desc. NW slope.
26.00	Draw, drains WSW; asc. SW slope.
39.94	The ¼ sec. cor. of secs. 31 and 32, monumented with a sandstone, 24 x 6 x 4 ins., firmly set in a mound of stone, and plainly mkd. ¼ on W face.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., on solid rock and in a mound of stone, 5 ft. base to brass cap mkd.

U.S. Government Printing Office-1978-778-206/433

CHAINS	
	T 9 S R 23 E ¼ S 31 | S 32 1977 Deposit the mkd. stone in mound alongside the iron post.
	N. 0° 09' W., beginning new measurement.
1.70	Spur, slopes W; desc. NW slope.
9.00	Spur, slopes NW; desc. N slope.
25.00	Draw, drains SW; asc. S slope.
29.00	Spur, slopes W; desc. NW slope.
40.10	The cor. of secs. 29, 30, 31, and 32, monumented with a sandstone, 18 x 10 x 5 ins., firmly set 10 ins. in the ground and plainly mkd. 1 notch on S and 5 notches on E edges. Witnessed by four small mounds of stone (one in each section). At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to brass cap mkd. T 9 S R 23 E S 30 | S 29 S 31 | S 32 1977 Deposit the mkd. stone alongside the iron post.
	From the cor. of secs. 28, 29, 32, and 33. S. 89° 58' W., bet. secs. 29 and 32. Over rolling desert land, through sagebrush and shadscale. Asc. along gentle N slope.
40.01	The ¼ sec. cor. of secs. 29 and 32, monumented with a sandstone, 24 x 10 x 5 ins., firmly set 10 ins. in the ground and plainly mkd. ¼ on N face. Witnessed by a mound of stone to W. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

CHAINS	
	T 9 S R 23 E ¼ S 29 / S 32 1977
	Deposit the mkd. stone alongside the iron post.
	Set a 5 ft. steel pipe alongside the iron post.
	Remove the original mound of stone and raise a mound of stone, 3 ft. base, 2 ft. high to N.
	The cor. is located on low spur, which slopes N.
	S. 89° 57' W., beginning new measurement.
	Desc. NW slope.
39.98	The cor. of secs. 29, 30, 31 and 32.
	S. 89° 59' W., bet. secs. 30 and 31.
	Over rolling desert land, through sagebrush and shadscale.
	Desc. NW slope.
11.00	Draw, drains SW; asc. SE slope.
20.85	Ridge, bears N and S; desc. W slope.
26.20	Spur, slopes SW; asc. gentle SE slope.
40.10	Point for the ¼ sec. cor. of secs. 30 and 31, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 23 E ¼ S 30 / S 31 1977
	Raise a mound of stone, 3½ ft. base, 2 ft. high to N.
41.00	Bulldozed road, bears NE and SW.
59.00	Draw, drains SE; asc. W slope.
60.50	Spur, slopes SE; desc. SW slope.
62.50	Draw, drains SE; asc. E slope.
79.72	The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., set, mkd. and witnessed as described in the field notes of the E. bdy. of T. 9 S., R. 22 E., surveyed concurrently under this Group.

CHAINS	
	From the cor. of secs. 29, 30, 31, and 32.
	N. 0° 02' W., bet. secs. 29 and 30.
	Over broken desert land, through sagebrush and shadscale.
	Desc. gentle NW slope.
3.50	Draw, drains SW; asc. S slope.
6.00	Spur, slopes W; desc. N slope.
15.00	Draw, drains SW; over gently rolling land.
38.50	Draw, drains SW; asc. S slope.
40.03	The ¼ sec. cor. of secs. 29 and 30, monumented with a sandstone, 18 x 8 x 6 ins., firmly set 8 ins. in the ground and plainly mkd. ¼ on W face. Witnessed by a mound of stone, 3 ft. base, 1½ ft. high to W.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 23 E ¼ S 30 | S 29 1977
	Deposit the mkd. stone alongside the iron post.
	N. 0° 06' W., beginning new measurement.
7.80	Ridge, bears E and W; desc. NE slope.
27.50	Improved graveled road, bears E and W, slope changes; asc. S slope.
36.00	Ridge, bears E and W; desc. NW slope.
40.08	The cor. of secs. 19, 20, 29, and 30, monumented with a sandstone, 20 x 10 x 6 ins., firmly set 8 ins. in the ground and plainly mkd. 2 notches on S and 5 notches on E edges.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 5 ft. base to brass cap mkd.
	T 9 S R 23 E S 19 | S 20 S 30 | S 29 1977

CHAINS	
	Deposit the mkd. stone alongside the iron post.
	From the cor. of secs. 20, 21, 28, and 29.
	N. 89° 53' W., bet. secs. 20 and 29.
	Over broken desert land, through sagebrush and shadscale.
	Asc. SE slope.
3.60	Spur, slopes S; desc. SW slope.
11.00	Draw, drains SW; asc. SE slope.
12.40	Point of spur, projects S; desc. SW slope.
18.00	Draw, drains WNW; desc. along N slope.
28.50	Draw, drains NW.
31.00	Ten inch gas line, bears S. 68° E. and N. 68° W., enter hollow, bears NE and SW.
40.00	The ¼ sec. cor. of secs. 20 and 29, monumented with a sandstone, 12 x 8 x 4 ins., firmly set 6 ins. in the ground and plainly mkd. ¼ on N face. Witnessed by a mound of stone, 2 ft. base, 1½ ft. high to N.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 23 E
	¼ S 20 / S 29
	1977
	Deposit the mkd. stone alongside the iron post.
	S. 89° 48' W., beginning new measurement.
17.00	Leave hollow; asc. E slope.
23.50	Spur, slopes NW; desc. SW slope.
28.00	Draw, drains NW; over N slope.
34.00	Draw, drains N; asc. E slope.
38.00	Spur, slopes N; desc. NW slope.
40.06	The cor. of secs. 19, 20, 29, and 30.

Dependent Resurvey of the Subdivisional Lines
of T. 9 S., R. 23 E., Salt Lake Meridian, Utah

CHAINS	
	N. 89° 50' W., bet. secs. 19 and 30.
	Over broken desert land, through sagebrush and shadscale.
	Desc. NW slope.
10.00	Draw, drains NW; asc. NE slope.
16.00	Spur, slopes N; desc. along NW slope.
27.50	Draw, drains N; asc. rolling NE slope.
40.05	The ¼ sec. cor. of secs. 19 and 30, monumented with a sandstone, 20 x 10 x 5 ins., firmly set 8 ins. in the ground and plainly mkd. ¼ on N face. Witnessed by a mound of stone, 3 ft. base, 1½ ft. high to N.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 23 E
	¼ S 19 / S 30
	1977
	Deposit the mkd. stone alongside the iron post.
	N. 89° 52' W., beginning new measurement.
2.20	Saddle on ridge, bears N and S; desc. W slope.
13.00	Bulldozed road, bears SE and NW.
14.00	Draw, drains NW; along N slope.
39.49	The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., set, mkd. and witnessed as described in the field notes of the E. bdy. of T. 9 S., R. 22 E., surveyed concurrently under this group.
	From the cor. of secs. 19, 20, 29, and 30.
	N. 0° 12' W., bet. secs. 19 and 20.
	Over broken desert land, through sagebrush and shadscale.
	Desc. rolling N slope.
19.00	Draw, drains NE; along rolling E slope.
19.50	Ten inch gas pipeline, bears S. 67° E. and N. 67° W.
29.00	Slope changes; asc. SW slope.
32.00	Spur, slopes W; desc. NW slope.
37.50	Draw, drains NE; along E slope.

CHAINS	
40.08	Point for the ¼ sec. cor. of secs. 19 and 20, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base to brass cap mkd. T 9 S R 23 E ¼ S 19 | S 20 1977 Cor. is located on rocky E slope.
43.00	Low spur, slopes NE; desc. N slope.
46.00	Twelve inch gas line, bears S. 81° E. and N. 81° W.
50.00	Draw, drains E; asc. S slope.
53.00	Spur, slopes E; desc. NE slope.
65.00	Draw, drains NW; along E edge of draw.
68.50	Same draw, drains NE; asc. SE slope.
71.00	Ridge, bears NE and SW; desc. NW slope.
80.16	The cor. of secs. 17, 18, 19, and 20, monumented with a limestone, 19 x 9 x 9 ins., firmly set in a mound of stone and plainly mkd. 3 notches on S and 5 notches on E edges. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base to brass cap mkd. T 9 S R 23 E S 18 | S 17 S 19 | S 20 1977 Deposit the mkd. stone alongside the iron post.
	From the cor. of secs. 16, 17, 20, and 21. N. 89° 52' W., bet. secs. 17 and 20. Over broken desert land, through sagebrush and shadscale. Across nearly level shelf.
3.00	Begin ascending E slope.
4.15	Point of small mesa top, projects S; desc. W slope.

CHAINS	
5.00	Bottom of descent; over rolling top of shelf.
18.00	Begin asc. of SE slope.
21.00	Top of ridge, bears NE and SW; desc. NW slope.
31.00	Draw, drains NW; asc. NE slope.
36.00	Spur, slopes NE; desc. NW slope.
40.21	The ¼ sec. cor. of secs. 17 and 20, monumented with a sandstone, 14 x 10 x 4 ins., firmly set 8 ins. in the ground and dimly mkd. ¼ on N face. Witnessed by a mound of stone to N.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 23 E
	¼ S 17 / S 20
	1977
	Deposit the mkd. stone alongside the iron post.
	Rebuild original stone mound to N, 3 ft. base, 2 ft. high.
	Cor. is located in small hollow, which drains N.
	N. 89° 44' W., beginning new measurement.
	Asc. NE slope.
3.00	Saddle on low ridge, bears SE and NW; desc. SW slope.
7.00	Enter draw, which drains W.
12.00	Leave draw, drains NW; along S edge of draw.
20.50	Same draw, drains SW; asc. SE slope.
22.00	Spur, slopes SW; desc. NW slope.
40.09	The cor. of secs. 17, 18, 19, and 20.
	S. 89° 52' W., bet. secs. 18 and 19.
	Over broken desert land, through sagebrush and shadscale.
	Desc. gentle W slope.
7.00	Small draw, drains N; asc. E slope.
10.20	Top of sandy bench, bears N and S; desc. along N slope.
20.00	Draw, drains N.

CHAINS	
40.04	The ¼ sec. cor. of secs. 18 and 19, monumented with a sandstone, 16 x 8 x 6 ins., firmly set 10 ins. in the ground and plainly mkd. ¼ on N face. Witnessed by a mound of stone to N. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 9 S R 23 E ¼ S 18 / S 19 1977 Deposit the mkd. stone alongside the iron post. Rebuild original mound of stone to N. 3 ft. base, 2 ft. high.
	N. 89° 53' W., beginning new measurement.
5.00	Draw, drains N from W; along bottom of draw.
9.00	Leave draw, drains E from S; asc. E slope.
23.20	Sandy ridge, bears N and S; desc. over rolling W slope.
37.60	Low ridge, bears N and S; desc. gentle W slope.
39.29	The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., set, mkd. and witnessed as described in the field notes of the E. bdy. of T. 9 S., R. 22 E., surveyed concurrently under this group.
	From the cor. of secs. 17, 18, 19, and 20. N. 0° 06' E., bet. secs. 17 and 18. Over broken desert land, through sagebrush and shadscale. Desc. gentle N slope.
2.50	Draw, drains W; asc. S slope.
9.40	Spur, slopes W; desc. NW slope.
19.20	Small draw, drains W.
32.00	Begin descending NE slope
38.00	Enter bottom land along Coyote Wash, bears SE and NW.
39.90	The ¼ sec. cor. of secs. 17 and 18, monumented with a sandstone, 16 x 9 x 8 ins., firmly set 6 ins. in the ground and plainly mkd. ¼ on W face. Witnessed by a mound of stone to W.

CHAINS	
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 23 E ¼ S 18 | S 17 1977
	Deposit the mkd. stone alongside the iron post.
	Rebuild original mound of stone to W, 3 ft. base, 2 ft. high.
	N. 0° 09' W., beginning new measurement.
3.00	Coyote Wash, drains NW; asc. SW slope.
24.00	Draw, drains SW; along gentle W slope.
33.00	Draw, drains NW; asc. SW slope.
40.08	The cor. of secs. 7, 8, 17, and 18, monumented with an old survey stake in mound of stone. No marks identified. This position is harmoniously related to existing original cors. and is accepted as the best available evidence of the original cor. position.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone to brass cap mkd.
	T 9 S R 23 E S 7 | S 8 S 18 | S 17 1977
	From true point for the cor. of secs. 8, 9, 16, and 17.
	N. 89° 54' W., bet. secs. 8 and 17.
	Over broken desert land, through sagebrush, shadscale and willow growth along Coyote Wash.
	Across nearly level bottom land in Coyote Wash.
13.00	Leave Coyote Wash, bears N and S; asc. E slope.
32.00	Top of ridge, bears N and S; desc. W slope.
40.05	The ¼ sec. cor. of secs. 8 and 17, monumented with a sandstone, 14 x 10 x 6 ins., firmly set 6 ins. in the ground and plainly mkd. ¼ on N face.
	At the corner point

CHAINS	
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone to brass cap mkd.
	T 9 S R 23 E
	¼ S 8 / S 17
	1977
	Deposit the mkd. stone alongside the iron post.
	N. 89° 43' W., beginning new measurement.
7.50	Draw, drains S; asc. along S slope.
21.00	Spur, slopes S.
40.09	The cor. of secs. 7, 8, 17, and 18.
	N. 89° 50' W., bet. secs. 7 and 18.
	Over broken desert land, through sagebrush and shadscale.
	Asc. SE slope.
5.00	Spur, slopes NE; desc. NW slope.
18.00	Bottom of hollow, bears NE and NW and drains N; asc. NE slope.
27.30	Spur, slopes NW; desc. SW slope.
40.21	The ¼ sec. cor. of secs. 7 and 18, monumented with a sandstone, 20 x 8 x 8 ins., firmly set in a mound of stone and plainly mkd. ¼ on N face.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to brass cap mkd.
	T 9 S R 23 E
	¼ S 7 / S 18
	1977
	Deposit the mkd. stone in mound alongside the iron post.
	N. 88° 54' W., beginning new measurement.
4.00	Spur, slopes N; desc. NW slope.
11.00	Low spur, slopes NW.
14.00	Draw, drains NW; asc. SE slope.

CHAINS	
23.50	Ridge, bears NE and SW; desc. NW slope.
39.09	The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., set, mkd. and witnessed as described in the field notes of the E. bdy. of T. 9 S., R. 22 E., surveyed concurrently under this group.

From the cor. of secs. 7, 8, 17, and 18.

N. 0° 06' W., bet. secs. 7 and 8.

Over broken desert land, through sagebrush and shadscale.

Asc. SW slope.

10.00	Spur, slopes NW; desc. gentle NW slope.
36.00	Bulldozed road, bears N. 74° 30' E. and S. 74° 30' W.
40.02	Point for the ¼ sec. cor. of secs. 7 and 8, at proportionate distance; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 9 S R 23 E

¼

S 7 | S 8

1977

No available accessories.

59.00	Draw, drains SW; asc. gentle S slope.
80.04	Point for the cor. of secs. 5, 6, 7, and 8, at proportionate distance; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 9 S R 23 E

S 6	S 5
S 7	S 8

1977

No available accessories.

From the cor. of secs. 4, 5, 8, and 9.

S. 89° 58' W., bet. secs. 5 and 8.

Over rolling desert land, through sagebrush and shadscale.

Asc. NW slope.

374

Dependent Resurvey of the Subdivisional Lines
of T. 9 S., R. 23 E., Salt Lake Meridian, Utah

CHAINS	
2.50	Top of sand dune, bears S and NW; over sand dunes.
15.00	Desc. NW slope.
27.00	Draw, drains NE; asc. E slope.
31.00	Spur, slopes NE; desc. NW slope.
39.92	The ¼ sec. cor. of secs. 5 and 8, monumented with an old survey stake, set in a mound of stone. This position is harmoniously related to existing original cors. and is accepted as the best available evidence of the original cor. position. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to brass cap mkd. T 9 S R 23 E ¼ S 5 / S 8 1977 Cor. is located in barren clay hills.
	N. 89° 39' W., beginning new measurement.
26.00	Draw, drains SW; asc. sandy SE slope.
40.04	The cor. of secs. 5, 6, 7, and 8.
	N. 89° 53' W., bet. secs. 6 and 7. Over sand dunes, through sagebrush and bunch grass. Asc. general E slope.
5.25	Top of sand dunes, bears irregularly N and S; desc. rolling W slope.
20.00	Draw, drains S.
40.08	The ¼ sec. cor. of secs. 6 and 7, monumented with a sandstone, 10 x 8 x 6 ins., firmly set in scattered mound of stone and dimly mkd. ¼ on N face. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone to brass cap mkd. T 9 S R 23 E ¼ S 6 / S 7 1977

CHAINS	
	Deposit the mkd. stone alongside the iron post.
	N. 89° 09' W., beginning new measurement.
3.75	Draw, drains S; leave sand dunes; asc. gentle SE slope.
24.00	Enter broken clay hills; bears N and S; asc. E slope.
34.00	Top of clay hills, bears N and S; over gently rolling sand dunes.
39.01	The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., set, mkd. and witnessed as described in the field notes of the E. bdy. of T. 9 S., R. 22 E., surveyed concurrently under this group.
	From the cor. of secs. 5, 6, 7, and 8.
	N. 0° 17' W., bet. secs. 5 and 6.
	Over rolling sand dunes, through sagebrush and shadscale.
	Asc. general S slope.
21.00	Top of sand dunes, bears SE and NW; desc. general N slope.
29.00	Leave sand dunes, bears E and W; over gently rolling clay flat.
40.02	The ¼ sec. cor. of secs. 5 and 6, monumented with a sandstone, 20 x 12 x 6 ins., firmly set 10 ins. in the ground and dimly mkd. ¼ on W face.
	At the cor. point
	Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone to brass cap mkd.
	T 9 S R 23 E ¼ S 6 | S 5 1977
	Deposit the mkd. stone alongside the iron post.
	N. 0° 10' W., beginning new measurement.
7.00	Draw, drains SE; asc. S slope.
18.50	Ridge, bears E and W; desc. general NW slope of clay hills
38.59	The cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the Tp., hereinbefore described.

T. 9 S., R. 23 E., Salt Lake Meridian, Utah

CHAINS

General Description

The township is located 6 miles west of Bonanza, Utah and 20 miles southeast of Ouray, Utah.

The area surveyed within T. 9 S., R. 23 E., is mostly broken desert land, with some gently rolling land in the northern portion. The elevation ranges from 4900 to 5400 feet above sea level. The soil varies from rocky to clay-pan to sand dunes in the northern portion of the township.

Coyote Wash crosses the township from east to west and drains most of the township. The wash is dry except during times of flash floods. There is a few stock ponds scattered throughout the township.

The Chapita Wells Gas Field is located in the southwest portion of the township. Gas operations are the principle users of the township along with the grazing of sheep. There was no mining deposits of value noted.

Two major gas lines cross the township, one enters in sec. 1 and runs WNW. and leaves the township in sec. 4, the other enters in sec. 25 and runs WNW. leaving the township in sec. 19. The smaller gas lines from the gas wells connect into these two main lines. There is one improved graveled road that runs E and W through the township, with numerous secondary roads and desert trail roads throughout the township.

There is no permanent residents in the township and no land under cultivation.

The land is covered with low shadscale, scattered sagebrush and sparse native grasses. There is no timber in the township.

The mean magnetic declination is 14½° E., taken from a recent isogonics map.

Form 9600-11
(August 1979)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Don Buhler	Surveying Technician
Donzil Q. Worthington	Survey Aid
Kathryn Johnson	Survey Aid
Russell Brown	Surveying Technician
Andrea Myslicki	Survey Aid
Steven Reese	Survey Aid

378

CERTIFICATE OF SURVEY

~~(I)~~ (We), Craig P. Sylvester and Gail E. Reynolds
Jerry L. Thomas and Ferrel D. Reynolds, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 20th day of July, 1977 ~~(I)~~ (We) have dependently resurveyed the North and South boundaries and subdivisional lines of Township 9 South, Range 23 East,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by ~~(me)~~ (us) and under ~~(my)~~ (our) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

April 12, 1977 (Date)	Jerry L. Thomas Supervisory (Cadastral Surveyor)
April 12, 1977 (Date)	Craig P. Sylvester Supervisory (Cadastral Surveyor)
April 12, 1977 (Date)	Gail E. Reynolds (Cadastral Surveyor)
April 12, 1977 (Date)	Ferrel D. Reynolds (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Denver, Colorado

The foregoing field notes of the dependent resurvey of the North and South boundaries and subdivisional lines of Township 9 South, Range 23 East, Salt Lake Meridian, Utah

executed by
Jerry L. Thomas, Supervisory Cadastral Surveyor
Craig P. Sylvester, Supervisory Cadastral Surveyor
Gail E. Reynolds, Cadastral Surveyor
Ferrel D. Reynolds, Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

APR 14 1981 (Date) — J. D. Voorhees (Chief, Cadastral Survey Examination and Approval Staff)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.~~

~~(Date) (Chief, Cadastral Survey Examination and Approval Staff)~~

Form 9180-6
(March 1977)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF THE EAST AND WEST BOUNDARIES,

AND THE SUBDIVISIONAL LINES

OF

TOWNSHIP 9 SOUTH, RANGE 24 EAST

Of the Salt Lake Meridian,

In the State of Utah.

EXECUTED BY

Craig P. Sylvester, Supervisory Cadastral Surveyor

Ferrel D. Reynolds, Cadastral Surveyor

Under special instructions dated May 20, 19 77, approved May 20, 1977,

_____, which provided for the surveys included under ~~U.S. Survey~~/Group Number 568, and assignment instructions dated May 23, 19 77.

Survey commenced May 23, 19 77

Survey completed September 2, 19 77

INDEX DIAGRAM

Township 9 S, Range 24 E.,

14 6 61	62 5 60	51 4 51	43 3 42	34 2 33	25 1 9 23
13 7 59	60 8 59	50 9 49	41 10 41	33 11 32	22 12 7 22
12 18 57	58 17 57	49 16 48	40 15 40	31 14 31	21 13 6 21
11 19 56	56 20 55	47 21 47	39 22 38	29 23 28	19 24 5 18
10 30 53	54 29 53	46 28 45	37 27 37	28 26 27	16 25 3 16
9 31	52 32	44 33	35 34	26 35	15 36 2

GPO 840-243

CHAINS

T. 9 S., R. 24 E.

History of Surveys

	Surveyed by		Retr. or Resurveyed by	
SOUTH BOUNDARY				
West 1 mile	D.G. Major	1883		
			A.R. Talamantes and H.D. Heist	1904
East 4 miles	A.R. Talamantes and H.D. Heist	1904		
All			J.L. Thomas	1975
NORTH BOUNDARY				
All	D.G. Major	1883		
			A.R. Talamantes and H.D. Heist	1904
All			Ralph Gentry	1916
EAST BOUNDARY				
All	D.G. Major	1883		
			A.R. Talamantes and H.D. Heist	1904
WEST BOUNDARY				
All	D.G. Major	1883		
			A.R. Talamantes and H.D. Heist	1904
SUBDIVISIONS				
All	D.G. Major	1883		
			A.R. Talamantes and H.D. Heist	1904

The following field notes are those of a dependent resurvey of the east and west boundaries, and the subdivisional lines of Township 9 South, Range 24 East, Salt Lake Meridian, Utah.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated May 20, 1977.

The directions of the lines of this survey were determined by reference to the true meridians established on line by hour angle observations on Polaris. They were carried forward by sustained angulation, being supplemented by numerous other observations on Polaris taken throughout the progress of the survey.

The distances along surveyed lines were determined by electronic measurement.

Before restoring lost corners, the lines of the original survey were retraced and a diligent search made for any evidence of the original corners. The rules of proportionate measurement were applied to ascertain the position of the lost corner after every reasonable possibility of finding direct evidence of the corner had been exhausted.

CHAINS

The geographic position for the southeast corner of the township, as determined from a tie made to U.S.G.S. triangulation state "JEK 8 ET 1966" located in sec. 32, T. 9 S., R. 24 E., Salt Lake Meridian, is:

Latitude 39° 59' 06" N. Longitude 109° 09' 09" W.

The magnetic declination was read at a number of stations throughout the township and the average of the several readings was found to be 15° East.

Dependent Resurvey of the East Boundary of T. 9 S., R. 24 E., Salt Lake Meridian, Utah

(Restoring the 1904 Survey by A.R. Talamantes and H.D. Heist)

Beginning at the cor. of Tps. 9 and 10 S., Rs. 24 and 25 E., an iron post, 2½ ins. diam., extending 10 ins. above ground and in a collar of stone, with brass cap mkd. as described in the official record of the 1975 resurvey.

N. 0° 02' E., bet. secs. 31 and 36.

Over broken land, through sagebrush and shadscale.

40.02 True point for the ¼ sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original cor. The cor. point falls in small wash, 6 lks. wide, 2 ft. deep, drains SE.

40.72 Point selected for the witness cor. to the ¼ sec. cor. of secs. 31 and 36.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

W C
T 9 S
R 24 E R 25 E

¼
S 36 | S 31
↓

1977

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

80.04 Point for the cor. of secs. 25, 30, 31, and 36, at proportionate distance; there is no remaining evidence of the original cor.

Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap, mkd.

U.S. Government Printing Office-1978-778-206/433

CHAINS	
	T 9 S R 24 E R 25 E S 25 | S 30 S 36 | S 31 1977 Cor. is located near base of spur, projecting S.
	N. 0° 02' E., bet. secs. 25 and 30. Over rolling land, through sagebrush and shadscale; asc. S. slope.
40.02	The ¼ sec. cor. of secs. 25 and 30, monumented with a sandstone, 17 x 8 x 5 ins., firmly set 12 ins. in the ground and plainly mkd. ¼ on W face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap mkd. T 9 S R 24 E R 25 E ¼ S 25 | S 30 1977 Deposit the mkd. stone alongside the iron post.
	North, beginning new measurement. Asc. SE slope.
6.22	Intersect line 2-3 of Mineral Survey No. 5274, Number Five Lode. From this point cor. No. 2 of the Number Five Lode, identical with cor. No. 3 of Number Four Lode, survey No. 5273, bears S. 62° 37' E., 16.15 chs. dist., a sandstone, 18 x 3 x 16 ins., above ground, firmly set and plainly mkd. 2-5274, from which a cross (X) and B.R. 2-5274, chiseled on a ledge, 6 ft. high, bears S. 66° 39' W., 2.81 chs. dist. From this same point cor. No. 3 of the Number Five Lode, bears N. 62° 37' W., 6.43 chs. dist., a sandstone, 14 x 14 x 16 ins., above ground, firmly set and plainly mkd. 3-5274, from which a cross (X) and B.R. 3-5274, chiseled on point of ledge, 10 ft. high, bears N. 6° 59' E., 3.18 chs. dist.
11.28	Intersect line 1-4 of Mineral Survey No. 5274, Number Five Lode.

CHAINS	
	From this point cor. No. 1 of the Number Five Lode, identical with cor. No. 4 of Number Four Lode, survey No. 5273, bears S. 62° 43' E., 18.54 chs. dist., a sandstone, 20 x 8 x 16 ins., above ground, firmly set and plainly mkd. 1-5274, from which a cross (X) and B.R. 1-5274, chiseled on flat sandstone formation, bears S. 60° 54' E., 1.38 chs. dist.
	From this same point cor. No. 4 of the Number Five Lode, bears N. 62° 43' W., 4.05 chs. dist., a sandstone, 12 x 3 x 16 ins. above ground, firmly set and plainly mkd. 1-5274, from which a cross (X) and B.R. 1-5274, chiseled on a flat sandstone formation, bears N. 88° 35' E., 1.43 chs. dist.
18.75	Hard surface road, bears E and W.
21.78	Intersect line 1-2 of Mineral Survey No. 5260, Tom Paine No. 9 Lode.
	From this point cor. No. 1 of the Tom Paine No. 9 Lode, identical with cor. No. 2 of the No. 8 Washington Lode, survey No. 5259, bears S. 67° 40' E., 8.50 chs. dist., a sandstone, 14 x 5 x 12 ins. above ground, firmly set and plainly mkd. 1-5260.
	From this same point cor. No. 2 of the Tom Paine No. 9 Lode, identical with cor. No. 1 of the No. 10 McCaslin Lode, survey No. 5261, bears N. 67° 40' W., 14.23 chs. dist., mkd. by an old mound of stone, no visible marks or evidence of the original bearing object.
	At the corner point
	Set a copperweld, 30 ins. long, 5/8 ins. in diam., 24 ins. in the ground and in a collar of stone, mkd.
	1-5261 / 2-5260
26.69	Intersect line 3-4 of Mineral Survey No. 5260, Tom Paine No. 9 Lode.
	From this point cor. No. 3 of the Tom Paine No. 9 Lode, identical with cor. No. 4 of the No. 10 McCaslin Lode, survey No. 5261, bears N. 67° 40' W., 12.56 chs. dist., a sandstone, 14 x 3 x 16 ins., above ground, firmly set and plainly mkd. 3-5260, from which a cross (X) and B.R. 3-5260, chiseled on a small ledge, 4 ft. high, facing S, bears N. 31° 53' E., 1.34 chs. dist.
	From this same point cor. No. 4 of the Tom Paine No. 9 Lode, identical with cor. No. 3 of the No. 8 Washington Lode, survey No. 5259, bears S. 67° 40' E., 10.18 chs. dist., a sandstone, 10 x 8 x 12 ins., above ground, firmly set and plainly mkd. 4-5260. There is no remaining evidence of the original bearing object.
26.98	Intersect line 1-4 of Mineral Survey No. 5197, Walsh Lode.
	From this point cor. No. 1 of the Walsh Lode, identical with cor. No. 4 of the Blue Jay Lode, same survey, bears N. 61° 54' W., 20.49 chs. dist., a sandstone, 15 x 4 x 14 ins., above ground, firmly set and plainly mkd. 1-4-5197, from which a cross (X) and 1-4-5197 B.R. Chiseled on a sandstone, 30 x 18 x 3 ins., set 16 ins. in the ground, bears N. 10° 25' W., 0.40 chs. dist.

☆ U.S. Government Printing Office-1978-778-206/433

CHAINS	
	From this same point cor. No. 4 of the Walsh Lode, identical with cor. No. 1 of the Red Bird Lode, same survey, bears S. 61° 54' E., 2.26 chs. dist., an erroded sandstone, 14 x 4 x 10 ins. above ground and in a scattered mound of stone, dimly mkd. 1-4-5197, from which a cross (X) and 1-4-5197 B.R. chiseled on a sandstone, 16 x 8 x 10 ins. above ground, bears N. 26° 40' W., 0.46 chs. dist.
32.00	Intersect line 2-3 of Mineral Survey No. 5197, Walsh Lode.
	From this point cor. No. 2 of the Walsh Lode, identical with cor. No. 3 of the Blue Jay Lode, same survey, bears N. 61° 31' W., 18.35 chs. dist., mkd. by an old mound of stone, no visible marks or evidence of the original bearing objects.
	At the corner point
	Set a copperweld, 30 ins. long, 5/8 ins. diam., 24 ins. in the ground and in a collar of stone, mkd.
	2-5197 / 3-5197
	From this same point cor. No. 3 of the Walsh Lode, identical with cor. No. 2 of the Red Bird Lode, same survey, bears S. 61° 31' E., 4.39 chs. dist., a sandstone, 14 x 4 x 12 ins. above ground, firmly set and dimly mkd. 2-3-5197, from which a cross (X) and 2-3-5197 B.R. chiseled on a sandstone, 10 x 6 x 10 ins. above ground, bears S. 53° 40' W., 0.62 chs. dist., and a cross and 2-3-5197 B.R. chiseled on a sandstone, 12 x 8 x 6 ins. above ground, bears S. 14° 07' E., 58 lks. dist.
39.97	The cor. of secs. 19, 24, 25, and 30, monumented with a sandstone, 16 x 6 x 4 ins., firmly set 10 ins. in the ground and plainly mkd. 4 notches on the N and 2 notches on the S edges.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 24 E R 25 E S 24 | S 19 S 25 | S 30 1977
	Deposit the mkd. stone alongside the iron post.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	Cor. is located on SE slope of spur.
	N. 0° 02' W., bet. secs. 19 and 24.
	Over broken desert land, through sagebrush and shadscale; asc. SE slope.

CHAINS	
40.14	The ¼ sec. cor. of secs. 19 and 24, monumented with a weathered sandstone, 16 x 12 x 6 ins., firmly set 10 ins. in the ground, in a mound of stone, dimly mkd. ¼ on W face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap mkd. T 9 S R 24 E R 25 E ¼ S 24 | S 19 1977 Deposit the mkd. stone alongside the iron post. Cor. is located on gentle N slope.
	N. 0° 01' W., beginning new measurement.
40.04	The cor. of secs. 13, 18, 19, and 24, monumented with a sandstone, 20 x 12 x 4 ins., firmly set 12 ins. in the ground, and plainly mkd. 3 notches on N and S edges. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd. T 9 S R 24 E R 25 E S 13 | S 18 S 24 | S 19 1977 Deposit the mkd. stone alongside the iron post. Cor. is located on NE slope of hill.
	North, bet. secs. 13 and 18. Over broken desert land, through sagebrush and shadscale; desc. NE slope.
40.02	The ¼ sec. cor. of secs. 13 and 18, monumented with a sandstone, 18 x 10 x 6 ins., firmly set 12 ins. in the ground and plainly mkd. ¼ on W face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd.

U.S. Government Printing Office-1978-778-206/433

CHAINS

T 9 S
R 24 E R 25 E

¼

S 13 | S 18

1977

Deposit the mkd. stone alongside the iron post.

North, beginning new measurement.

Over rolling desert land, through sagebrush and shadscale.

40.04 The cor. of secs. 7, 12, 13, and 18, monumented with a broken sandstone, 12 x 6 x 5 ins., set in a small mound of stone. This position is accepted as the best available evidence of the original cor. position.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd.

T 9 S
R 24 E R 25 E

S 12 | S 7
S 13 | S 18

1977

Deposit the unmkd. stone alongside the iron post.

Cor. is located on gentle rolling desert land.

N. 0° 01' W., bet. secs. 7 and 12.

Over rolling desert land, through sagebrush and shadscale.

40.08 The ¼ sec. cor. of secs. 7 and 12, monumented with a sandstone, 14 x 8 x 4 ins., firmly set 6 ins. in the ground, and plainly mkd. ¼ on W face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.

T 9 S
R 24 E R 25 E

¼

S 12 | S 7

1977

Deposit the mkd. stone alongside the iron post.

CHAINS	
	N. 0° 02' W., beginning new measurement.
	Over rolling desert land, through sagebrush and shadscale.
6.57	Intersect line 1-4 of Mineral Survey No. 5184, Lorna Doone Lode.
	From this point cor. No. 1 of the Lorna Doone Lode, identical with cor. No. 4 of the New York Lode, same survey, bears S. 61° 23' E., 22.32 chs. dist., mkd. by a mound of stone only.
	At the corner point (center of mound)
	Set a copperweld, 30 ins. long, 5/8 ins. diam., 24 ins. in the ground and in a collar of stone, with cap mkd.
	1-5184 / 4-5184
	From this same point, cor. No. 4 of the Lorna Doone Lode, identical with cor. No. 1 of Mineral Survey No. 5186, Eureka Lode, bears N. 61° 23' W., 0.41 chs. dist., mkd. by an old mound of stone only.
	At the corner point
	Set a copperweld, 30 ins. long, 5/8 ins. diam., 24 ins. in the ground and in a collar of stone, with cap mkd.
	1-5186 / 4-5184
	from which U.S.L.M. No. 4
	A sandstone, 14 x 6 x 16 ins. above ground, firmly set and plainly mkd. U.S.L.M. No. 4 on NE face, bears West, 350 ft. dist. (same as record).
10.00	Dirt road, bears E and W on turn.
11.62	Intersect line 2-3 of Mineral Survey No. 5186, Eureka Lode.
	From this point cor. No. 2 of the Eureka Lode, identical with cor. No. 3 of the Lorna Doone Lode, bears S. 64° 04' E., 2.20 chs. dist., mkd. by an old mound of stone only.
	At the corner point (center of mound)
	Set a copperweld, 30 ins. long, 5/8 ins. diam., 24 ins. in the ground and in a collar of stone, with cap mkd.
	2-5186 / 3-5184
	From this same point, cor. No. 3 of the Eureka Lode, identical with cor. No. 2 of Mineral Survey No. 5186, Thunderbuss Lode, bears N. 64° 04' W., 20.50 chs. dist., monumented with a sandstone, 28 x 15 x 4 ins., set in a mound of stone and chiseled 3-2-5186.
40.08	The cor. of secs. 1, 6, 7, and 12, monumented with a broken sandstone, 16 x 8 x 4 ins., firmly set 4 ins. in the ground and plainly mkd. 5 notches on the S and 1 notch on N edges.
	At the corner point

Dependent Resurvey of the East Boundary of
T. 9 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap mkd.

T 9 S
R 24 E R 25 E

S 1	S 6
S 12	S 7

1977

Deposit the mkd. stone alongside the iron post.

Set a cedar post, 7 ft. long, 24 ins. in the ground, alongside the iron post.

N. 0° 01' W., bet. secs. 1 and 6.

Over broken desert land, through sagebrush and shadscale.

40.05 Point for the ¼ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original cor.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap mkd.

T 9 S
R 24 E R 25 E

¼

S 1 | S 6

1977

Cor. is located on N edge of small wash, 5 lks. wide, 1 ft. deep, drains NW.

78.09 The cor. of Tps. 8 and 9 S., Rs. 24 and 25 E., monumented with an iron post, 3½ ins. diam., protruding 8 ins. above ground with brass cap mkd. as described in the official record of the 1916 resurvey.

Dependent Resurvey of the West Boundary of
T. 9 S., R. 24 E., Salt Lake Meridian, Utah

(Restoring the 1904 Survey by
A.R. Talamantes and H.D. Heist)

Beginning at the cor. of Tps. 9 and 10 S., Rs. 23 and 24 E., monumented with an iron post, 2½ ins. diam., extending 6 ins. above ground and in a collar of stone, with brass cap mkd. as described in the official record of the 1975 resurvey.

CHAINS	
	N. 0° 04' E., bet. secs. 31 and 36.
	Over broken desert land, through sagebrush and shadscale.
39.98	The ¼ sec. cor. of secs. 31 and 36, monumented with a sandstone, 14 x 6 x 4 ins., firmly set 6 ins. in the ground and plainly mkd. ¼ on W face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd.
	T 9 S R 23 E R 24 E ¼ S 36 | S 31 1977
	Deposit the mkd. stone alongside the iron post.
	Cor. is located 3 lks. W of netwire fence, bears N and S.
	N. 0° 04' W., beginning new measurement.
	Over broken desert land.
6.00	Trail road, bears E and W.
40.22	The cor. of secs. 25, 30, 31, and 36, monumented with a sandstone, 20 x 6 x 2 ins., firmly set 12 ins. in the ground and plainly mkd. 5 notches on the N and 1 notch on the S edges.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 23 E R 24 E S 25 | S 30 S 36 | S 31 1977
	Deposit the mkd. stone alongside the iron post.
	Cor. is located 3 lks. E of netwire fence, bears N and S.
	Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.
	N. 0° 06' E., bet. secs. 25 and 30.
	Over broken desert land, through sagebrush and shadscale; along W slope.

U.S. Government Printing Office-1978-778-206/433

CHAINS	
39.94	The ¼ sec. cor. of secs. 25 and 30, monumented with a sandstone, 20 x 6 x 4 ins., firmly set 10 ins. in the ground and plainly mkd. ¼ on W face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 9 S R 23 E R 24 E ¼ S 25 | S 30 1977 Deposit the mkd. stone in mound alongside the iron post. Cor. is located on NW slope of hill.
	N. 0° 15' E., beginning new measurement. Along E slope.
40.02	The cor. of secs. 19, 24, 25, and 30, monumented with a sandstone, 20 x 7 x 6 ins., firmly set in a mound of stone and dimly mkd. 4 notches on the N and 2 notches on the S edges. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4 ft, base, to top of brass cap, mkd. T 9 S R 23 E R 24 E S 24 | S 19 S 25 | S 30 1977 Deposit the mkd. stone in mound alongside the iron post. Cor. is located on SE slope of hill, at base of ledges 10 ft. high.
	N. 0° 01' E., bet. secs. 19 and 24. Over broken desert land, through sagebrush and shadscale; asc. SE slope.
40.07	The ¼ sec. cor. of secs. 19 and 24, monumented with a sandstone, 16 x 10 x 6 ins., firmly set in a mound of stone and plainly mkd. ¼ on W face. At the corner point

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., on solid rock and in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 9 S R 23 E R 24 E ¼ S 24 | S 19 1977 Deposit the mkd. stone in mound alongside the iron post. Cor. is located on low ridge, bears NW and SE, also 5 lks. E. of netwire fence, bears NW and SE.
	N. 0° 07' E., beginning new measurement. Desc. NE slope.
40.11	The cor. of secs. 13, 18, 19, and 24, monumented with a sandstone, 16 x 6 x 4 ins., firmly set 8 ins. in the ground and plainly mkd. 3 notches on the N and S edges. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap mkd. T 9 S R 23 E R 24 E S 13 | S 18 S 24 | S 19 1977 Deposit the mkd. stone alongside the iron post. Cor. is located at the cor. of netwire fence, bears W and irregularly S.
	N. 0° 19' E., bet. secs. 13 and 18. Over broken desert land, through sagebrush and shadscale; asc. SE slope.
25.00	Dirt road, bears N. 68° W. and S. 68° E.
40.04	The ¼ sec. cor. of secs. 13 and 18, monumented with a sandstone, 22 x 6 x 4 ins., firmly set 12 ins. in the ground and plainly mkd. ¼ on W face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.

U.S. Government Printing Office-1978-778-206/433

CHAINS

T 9 S
R 23 E R 24 E

¼
S 13 | S 18

1977

Deposit the mkd. stone alongside the iron post.

Cor. is located on N slope of clay bank.

N. 0° 35' W., beginning new measurement.

40.04 The cor. of secs. 7, 12, 13, and 18, monumented with a sandstone, 16 x 8 x 5 ins., firmly set 10 ins. in the ground and plainly mkd. 4 notches on the S and 2 notches on the N edges.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.

T 9 S
R 23 E R 24 E

S 12 | S 7
S 13 | S 18

1977

Deposit the mkd. stone alongside the iron post.

N. 0° 06' E., bet. secs. 7 and 12.

Over broken desert land, through sagebrush and shadscale.

40.06 Point for the ¼ sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original cor.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 9 S
R 23 E R 24 E

¼
S 12 | S 7

1977

78.82 Point selected for the witness cor. to the cor. of secs. 1, 6, 7, and 12.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap mkd.

394

Dependent Resurvey of the West Boundary of
T. 9 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
	W C T 9 S R 23 E R 24 E S 1 | S 6 S 12 | S 7 1977
80.12	True point for the cor. of secs. 1, 6, 7, and 12, falls in main channel of Coyote Wash, 2.00 chs. wide, 6 ft. deep, course NW.
	N. 0° 06' E., bet. secs. 1 and 6.
	Over broken desert land, through sagebrush and shadscale.
40.06	The ¼ sec. cor. of secs. 1 and 6, monumented with a sandstone, 14 x 8 x 4 ins., firmly set 8 ins. in the ground and dimly mkd. ¼ on W face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 23 E R 24 E ¼ S 1 | S 6 1977
	Deposit the mkd. stone alongside the iron post.
	N. 0° 01' W., beginning new measurement.
20.11	Point for the N 1/16 sec. cor. of secs. 1 and 6.
	Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.
	T 9 S R 23 E R 24 E N 1/16 S 1 | S 6 1977
38.21	The cor. of Tps. 8 and 9 S., Rs. 23 and 24 E., monumented with an iron post, 3 ins. diam., extending 12 ins. above ground with brass cap mkd. as described in the official record of the 1916 resurvey.

U.S. Government Printing Office-1978-778-206/433

CHAINS	
	Dependent Resurvey of the Subdivisional Lines, T. 9 S., R. 24 E., Salt Lake Meridian, Utah
	(Restoring the 1904 Survey by A.R. Talamantes and H.D. Heist)
	From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., extending 14 ins. above ground and in a mound of stone, with brass cap mkd. as described in the official record of the 1975 resurvey.
	North, bet. secs. 35 and 36.
	Over broken desert land, through sagebrush and shadscale; asc. SE slope.
39.92	The ¼ sec. cor. of secs. 35 and 36, monumented with a weathered sandstone, 16 x 10 x 6 ins., firmly set 8 ins. in the ground, in a mound of stone, marks have been obliterated.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.
	T 9 S R 24 E ¼ S 35 | S 36 1977
	Deposit the weathered stone alongside the iron post.
	Cor. is located on S slope of spur projecting W., and 35 lks. E of point of sandstone ledges, 20 ft. high.
	N. 0° 01' E., beginning new measurement.
39.98	The cor. of secs. 25, 26, 35, and 36, monumented with a sandstone, 16 x 8 x 4 ins., firmly set 8 ins. in the ground and plainly mkd. 1 notch on S and E edges.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, to top of brass cap, mkd.
	T 9 S R 24 E S 26 | S 25 S 35 | S 36 1977

CHAINS	
	Deposit the mkd. stone in mound alongside the iron post.
	From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., heretofore described. S. 89° 55' W., bet. secs. 25 and 36. Over broken desert land, through sagebrush and shadscale; asc. SE slope.
39.88	Point for the ¼ sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 9 S R 24 E ¼ S 25 / S 36 1977
79.76	The cor. of secs. 25, 26, 35, and 36.
	North, bet. secs. 25 and 26. Over broken desert land, through sagebrush and shadscale; desc. NW slope.
9.25	Bottom of Wagon Hound Canyon, drains SW, also State Highway No. 45 bears NE and SW; asc. SE slope.
40.07	The ¼ sec. cor. of secs. 25 and 26, monumented with a sandstone, 16 x 8 x 4 ins., firmly set 10 ins. in the ground and plainly mkd. ¼ on W face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 9 S R 24 E ¼ S 26 | S 25 1977 Deposit the mkd. stone alongside the iron post. Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

U.S. Government Printing Office-1978-778-206/433

CHAINS	
	N. 0° 12' W., beginning new measurement.
16.65	Intersect line 2-3 of Mineral Survey No. 5277, Number Eight Lode.
	From this point cor. No. 2 of the Number Eight Lode, identical with cor. No. 3 of the Number Seven Lode, same survey, bears S. 66° 05' E., 22.10 chs. dist., mkd. by an old mound of stone.
	At the corner point (center of mound)
	Set a copperweld, 30 lks. long, 5/8 ins. diam., 24 ins. in the ground and in a collar of stone, with cap mkd.
	2-5277 |
	From this same point cor. No. 3 of the Number Eight Lode, bears N. 66° 05' W., 0.63 chs. dist., monumented with a sandstone, 6 x 4 x 15 ins., above ground, firmly set and dimly mkd. 3-5277.
	At the corner point
	Set a copperweld, 30 ins. long, 5/8 ins. diam., 24 ins. in the ground and in a collar of stone, with cap mkd.
	| 3-5277
18.01	Intersect line 3-4 of Mineral Survey No. 5277, Number Eight Lode.
	From this point cor. No. 3 of the Number Eight Lode, bears S. 27° 36' W., 1.24 chs. dist., heretofore described
	From this same point cor. No. 4 of the Number Eight Lode, bears N. 27° 36' E., 3.27 chs. dist., monumented with a sandstone, 14 x 12 x 14 ins. above ground, firmly set and chiseled 4-5277, with a mound of stone alongside.
	Over rolling desert land.
40.08	The cor. of secs. 23, 24, 25, and 26, monumented with a sandstone, 16 x 8 x 5 ins., firmly set in a mound of stone, markings have been obliterated.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, to top of brass cap, mkd.
	T 9 S R 24 E
	S 23 | S 24 S 26 | S 25
	1977
	Deposit the weathered stone alongside the iron post.
	Cor. is located on NW slope of small knoll.

CHAINS	
	From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., heretofore described.
	N. 89° 58' W., bet. secs. 24 and 25.
	Over broken desert land, through sagebrush and shadscale; asc. SE slope.
14.72	Intersect line 2-3 of Mineral Survey No. 5197, Walsh Lode.
	From this point cor. No. 2 of the Walsh Lode, identical with cor. No. 3 of the Blue Jay Lode, same survey, bears N. 61° 31' W., 1.60 chs. dist., heretofore described.
	From this same point cor. No. 3 of the Walsh Lode, identical with cor. No. 2 of the Red Bird Lode, same survey, bears S. 61° 31' E., 21.14 chs. dist., heretofore described.
24.60	Intersect line 1-4 of Mineral Survey No. 5197, Blue Jay Lode.
	From this point cor. No. 4 of the Blue Jay Lode, identical with cor. No. 1 of the Walsh Lode, bears S. 62° 53' E., 7.32 chs. dist., heretofore described.
	From this same point cor. No. 1 of the Blue Jay Lode, identical with cor. No. 4 of Frying Pan Lode, same survey, bears N. 62° 53' W., 15.10 chs. dist., monumented with a sandstone, 12 x 8 x 20 ins. above ground, firmly set and chiseled 1-4-5197.
31.46	Intersect line 3-4 of Mineral Survey No. 5261, McCaslin No. 10 Lode.
	From this point cor. No. 4 of the McCaslin No. 10 Lode, identical with cor. No. 3 of the Tom Paine No. 9 Lode, Survey No. 5260, bears S. 66° 47' E., 21.62 chs. dist., heretofore described.
	From this same point cor. No. 3 of the McCaslin No. 10 Lode, identical with cor. No. 4 of the Mary Mc. Lode Survey No. 5196, bears N. 66° 47' W., 1.07 chs. dist., monumented with a broken sandstone, 18 x 12 x 4 ins., firmly set in a collar of stone and chiseled 3-5261 on E face and 4-5196 on W face. There is no remaining evidence of the original bearing rocks.
39.96	Point for the ¼ sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 24 E
	¼ S 24 / S 25
	1977
	Set a post, 4 x 6 ins. diam., 5 ft. long, alongside the iron post.

☆ U.S. Government Printing Office-1978-778-206/433

CHAINS	
43.06	Intersect line 2-3 of Mineral Survey No. 5196, Mary Mc. Lode. From this point cor. No. 2 of the Mary Mc. Lode, identical with cor. No. 2 of the Ouray Lode, same survey, bears N. 66° 58' W., 12.91 chs. dist., mkd. by an old mound of stone, no mkd. rock. At the corner point (center of mound) Set a copperweld, 30 ins. long, 5/8 ins. diam., 20 ins. in the ground and in a collar of stone, with cap mkd. | 2-5196 | 2-5196 From this same point of intersection, cor. No. 3 of the Mary Mc. Lode, identical with cor. No. 2 of the McCaslin No. 10 Lode, survey No. 5261, bears S. 66° 58' E., 9.82 chs. dist., mkd. by an old mound of stone. At the corner point (center of mound) Set a copperweld, 30 ins. long, 5/8 ins. diam., 24 ins. in the ground and in a collar of stone, with cap mkd. | 3-5196 | 2-5261
50.00	Hard surface road, bears N. 72° W. and S. 72° E.
59.94	Point for the W 1/16 sec. cor. of secs. 24 and 25. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 9 S R 24 E W 1/16 S 24 / S 25 1977 Set a post, 5 ft. long, alongside the cor.
75.50	State highway No. 45, bears N and S; asc. gentle E slope.
79.92	The cor. of secs. 23, 24, 25, and 26.
	N. 0° 03' E., bet. secs. 23 and 24. Over rolling desert land, through sagebrush and shadscale.
9.50	Hard surface road, bears NW and SE.
15.00	State highway No. 45, bears N. 20° W. and S. 20° E.
32.49	Intersect line 2-3 of Mineral Survey No. 5217, Rangely Bell Lode. From this point cor. No. 2 of the Rangely Bell Lode, identical with cor. No. 3 of the Utah Lode, survey No. 5197, bears S. 62° 19' E., 3.42 chs. dist., mkd. by an old mound of stone.

CHAINS	
	At the corner point (center of mound)
	Set a copperweld, 30 ins. long, 5/8 ins. diam., 24 ins. in the ground and in a collar of stone, with cap mkd.
	2-5217 | / 3-5197 |
	From this same point of intersection, cor. No. 3 of the Rangely Bell Lode, identical with cor. No. 2 of the Short Leg Lode, Survey No. 5218, bears N. 62° 19' W., 19.30 chs. dist., mkd. by an old mound of stone.
	At the corner point (center of mound)
	Set a copperweld, 28 ins. long, 5/8 ins. diam., 24 ins. in the ground and in a collar of stone, with cap mkd.
	2-5218 | / 3-5217 |
40.01	The ¼ sec. cor. of secs. 23 and 24, monumented with a sandstone, 16 x 8 x 6 ins., firmly set 10 ins. in the ground and plainly mkd. ¼ on W face.
	Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.
	T 9 S R 24 E
	¼
	S 23 | S 24
	1977
	Deposit the mkd. stone alongside the iron post.
	North, beginning new measurement.
24.00	Dirt road, bears NE and SW.
39.98	The cor. of secs. 13, 14, 23, and 24, monumented with a weathered sandstone, 14 x 8 x 6 ins., firmly set in a mound of stone with illegible markings.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 24 E
	S 14 | S 13 / S 23 | S 24
	1977
	Deposit the weathered stone alongside the iron post.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

U.S. Government Printing Office-1978-778-206/433

CHAINS	
	From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., heretofore described.
	S. 89° 43' W., bet. secs. 13 and 24.
	Over broken desert land, through sagebrush and shadscale; asc. NE slope.
39.86	The ¼ sec. cor. of secs. 13 and 24, monumented with a weathered sandstone, 16 x 8 x 6 ins., firmly set 6 ins. in the ground with illegible markings.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 24 E
	¼ S 13 / S 24
	1977
	Deposit the weathered stone and set a steel fence post, alongside the iron post.
	West, beginning new measurement.
30.00	Dirt road, bears NE and SW.
39.92	The cor. of secs. 13, 14, 23, and 24.
	North, bet. secs. 13 and 14.
	Over broken desert land, through sagebrush and shadscale; desc. gentle NE slope.
39.98	The ¼ sec. cor. of secs. 13 and 14, monumented with a sandstone, 18 x 8 x 5 ins., firmly set 10 ins. in the ground and dimly mkd. ¼ on W face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground and in a collar of stone with brass cap mkd.
	T 9 S R 24 E
	¼ S 14 | S 13
	1977
	Deposit the mkd. stone alongside the iron post.

402

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
	N. 0° 06' E., beginning new measurement.
40.21	The cor. of secs. 11, 12, 13, and 14, monumented with a weathered sandstone, 18 x 10 x 8 ins., firmly set 8 ins. in the ground. Marks have been obliterated.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd.
	T 9 S R 24 E S 11 | S 12 S 14 | S 13 1977
	Deposit the weathered stone alongside the iron post.
	From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., heretofore described.
	S. 89° 55' W., bet. secs. 12 and 13.
	Over broken desert land, through sagebrush and shadscale.
25.00	Dirt road, bears S. 15° W. and N. 15° E.
39.93	The ¼ sec. cor. of secs. 12 and 13, monumented with a sandstone, 20 x 12 x 6 ins., firmly set 10 ins. in the ground and plainly mkd. ¼ on N face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, to top of brass cap, mkd.
	T 9 S R 24 E ¼ S 12 S 13 1977
	Deposit the mkd. stone alongside the iron post.
	Cor. is located on point of spur, projecting N.
	West, beginning new measurement.
39.86	The cor. of secs. 11, 12, 13, and 14.
	N. 0° 02' W., bet. secs. 11 and 12.
	Over broken desert land, through sagebrush and shadscale.

U.S. Government Printing Office-1978-778-206/433

CHAINS

40.07 The ¼ sec. cor. of secs. 11 and 12, monumented with a badly weathered sandstone, 12 x 6 x 4 ins., firmly set in a mound of stone. Marks have been obliterated.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd.

T 9 S R 24 E

¼

S 11 | S 12

1977

Deposit the weathered stone alongside the iron post.

N. 0° 01' E., beginning new measurement.

40.09 The cor. of secs. 1, 2, 11, and 12, monumented with a sandstone, 18 x 10 x 6 ins., firmly set 8 ins. in the ground and plainly mkd. 5 notches on the S and 1 notch on the E edges.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd.

T 9 S R 24 E

S 2 | S 1
S 11 | S 12

1977

Deposit the mkd. stone alongside the iron post.

From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., heretofore described.

N. 89° 59' W., bet. secs. 1 and 12.

Over broken desert land, through sagebrush and shadscale.

39.89 The ¼ sec. cor. of secs. 1 and 12, monumented with a sandstone, 16 x 8 x 5 ins., firmly set 6 ins. in the ground and plainly mkd. ¼ on N face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, to top of brass cap, mkd.

CHAINS	
	T 9 S R 24 E ¼ S 1 / S 12 1977
	Deposit the mkd. stone alongside the iron post.
	Cor. is located on W edge of small wash, drains N.
	S. 89° 57' W., beginning new measurement.
22.25	Intersect line 3-4 of Mineral Survey No. 5382, White River No. 21 Lode.
	From this point cor. No. 3 of the White River No. 21 Lode, identical with cor. No. 4 of the White River No. 22 Lode, same survey, bears N. 63° 10' W., 12.24 chs. dist., monumented with a sandstone, 10 x 4 x 22 ins., above ground and chiseled 3-4-5382, from which a cross (X) and 3-4-5382 B.R. chiseled on a sandstone, 18 x 10 x 5 ins., set 12 ins. in the ground, bears S. 34° 15' E., 0.61 chs. dist., and a sandstone, 20 x 13 x 4 ins., set 14 ins. in the ground and chiseled 3-4-5382 B.R., bears S. 79° 50' W., 0.52 chs. dist.
	From this same point cor. No. 4 of the White River No. 21 Lode, identical with cor. No. 3 of the White River No. 20 Lode, same survey, bears S. 63° 10' E., 10.42 chs. dist., monumented with a sandstone, 10 x 4 x 18 ins., above ground and chiseled 3-4-5382, from which a cross (X) and 3-4-5382 B.R., chiseled on a sandstone, 7 x 9 x 4 ins., above ground, bears S. 33° 20' E., 0.53 chs. dist., and a sandstone, 27 x 13 x 4 ins., above ground and chiseled 3-4-5382 B.R., bears N. 89° 25' W., 0.79 chs. dist.
32.23	Intersect line 1-2 of Mineral Survey No. 5382, White River No. 21 Lode.
	From this point cor. No. 1 of the White River No. 21 Lode, identical with cor. No. 2 of the White River No. 20 Lode, same survey, bears S. 63° 07' E., 19.00 chs. dist., monumented with a sandstone, 9 x 4 x 15 ins. above ground and chiseled 2-1-5382, from which a cross (X) and 2-1-5382 B.R. chiseled on a sandstone, 6 x 8 x 3 ins. above ground, bears N. 27° W., 0.64 chs. dist., and a sandstone, 16 x 15 x 3 ins., above ground and chiseled 2-1-5382 B.R., bears N. 68° 45' E., 0.64 chs. dist.
	From this same point cor. No. 2 of the White River No. 21 Lode, identical with cor. No. 1 of the White River No. 22 Lode, same survey, bears N. 63° 07' W., 3.67 chs. dist., monumented with a sandstone, 10 x 6 x 12 ins., above ground and chiseled 2-1-5382, from which a cross (X) and 2-1-5382 B.R. chiseled on a sandstone, 6 x 10 x 4 ins., above ground, bears N. 28° 35' W., 0.73 chs. dist., and a sandstone, 6 x 12 x 3 ins., above ground and chiseled 2-1-5382 B.R., bears N. 84° 05' E., 0.60 chs. dist.
39.91	The cor. of secs. 1, 2, 11, and 12.

☆ U.S. Government Printing Office-1978-778-206/433

CHAINS	
	N. 0° 01' W., bet. secs. 1 and 2.
	Over broken desert land, through sagebrush and shadscale; asc. gentle SW slope.
3.68	Intersect line 1-2 of Mineral Survey No. 5382, White River No. 22 Lode.
	From this point cor. No. 1 of the White River No. 22 Lode identical with cor. No. 2 of the White River No. 21 Lode, same survey, bears S. 65° 26' E., 4.84 chs. dist., heretofore described.
	From this same point cor. No. 2 of the White River No. 22 Lode, identical with cor. No. 1 of the White River No. 23 Lode, same survey, bears N. 65° 26' W., 17.51 chs. dist., monumented with a sandstone, 8 x 3 x 12 ins. above ground and chiseled 2-1-5382, from which a cross (X) and 2-1-5382 B.R. chiseled on a sandstone, 6 x 12 x 4 ins., above ground, bears N. 73° 35' E., 0.54 chs. dist., and a sandstone, 6 x 8 x 3 ins., above ground and chiseled 215382 B.R., bears N. 26° 45' W., 0.70 chs. dist.
8.62	Intersect line 3-4 of Mineral Survey No. 5382, White River No. 22 Lode.
	From this point cor. No. 4 of the White River No. 22 Lode identical with cor. No. 3 of the White River No. 21 Lode, same survey, bears S. 65° 23' E., 7.41 chs. dist., heretofore described.
	From this same point cor. No. 3 of the White River No. 22 Lode, identical with cor. No. 4 of the White River No. 23 Lode, same survey, bears N. 65° 23' W., 14.98 chs. dist., monumented with a sandstone, 15 x 4 x 20 ins. above ground and chiseled 3-4-5382, from which a cross (X) and 3-4-5382 B.R. chiseled on a sandstone, 8 x 20 x 4 ins. above ground, bears S. 85° 10' W., 0.63 chs. dist., and a sandstone, 10 x 12 x 4 ins. above ground and chiseled 3-4-5382 B.R., bears S. 21° 00' E., 0.58 chs. dist.
40.05	The ¼ sec. cor. of secs. 1 and 2, monumented with a weathered sandstone, 14 x 6 x 4 ins. firmly set 6 ins. in the ground. Marks have been obliterated.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 9 S R 24 E

¼

S 2 | S 1

1977

Deposit the weathered stone alongside the iron post.

CHAINS	
	N. 0° 02' W., beginning new measurement.
10.00	Trail road, bears NE and SW.
19.07	Point selected for the witness cor. to the N 1/16 sec. cor. of secs. 1 and 2. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. W C T 9 S R 24 E N 1/16 S 2 ↑ S 1 1977
20.07	True point for the N 1/16 sec. cor. of secs. 1 and 2, falls in stock pond, 2.00 chs. wide, 1 ft. deep and cannot be perpetuated.
38.30	The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., monumented with an iron post, 2 ins. diam., extending 14 ins. above ground, with brass cap mkd as described in the official record of the 1916 resurvey.
	From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., extending 8 ins. above ground, with brass cap mkd. as described in the official record of the 1975 resurvey.
	N. 0° 01' E., bet. secs. 34 and 35.
	Over broken desert land, through sagebrush and shadscale; asc. SW slope.
25.50	Trail road in canyon, bears NE and SW; asc. SE slope.
40.08	Point for the ¼ sec. cor. of secs. 34 and 35, at proportionate distance, falls in perpendicular ledges and cannot be monumented.
47.85	The original witness cor. to the ¼ sec. cor. of secs. 34 and 35, monumented with a sandstone, 20 x 8 x 4 ins., firmly set in a mound of stone and dimly mkd. ¼ WC on W face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, to top of brass cap, mkd. W C T 9 S R 24 E ¼ S 34 | S 35 ↓ 1977 Deposit the mkd. stone in mound alongside the iron post.

CHAINS	
	Cor. is located on sandstone spur, projecting E.
	N. 0° 09' W., beginning new measurement.
	Desc. over gentle NE slope.
19.50	Trail road, bears E and W; asc. gentle S slope.
32.10	The cor. of secs. 26, 27, 34, and 35, monumented with a sandstone, 14 x 8 x 6 ins., firmly set 6 ins. in the ground and plainly mkd. 2 notches on the E and 1 notch on the S edges.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 24 E S 27 | S 26 S 34 | S 35 1977
	Deposit the mkd. stone alongside the iron post.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	Cor. is located on gentle NW slope.
	From the cor. of secs. 25, 26, 35, and 36.
	N. 89° 54' W., bet. secs. 26 and 35.
	Over broken desert land, through sagebrush and shadscale; desc. along NW slope.
19.00	State highway No. 45 in Wagon Hound Canyon, bears NE and SW; asc. SE slope.
39.90	Point for the ¼ sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 24 E ¼ S 26 / S 35 1977
	Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.
	Cor. is located on N edge of sandy wash, 10 lks. wide, 1 ft. deep, drains E.
79.80	The cor. of secs. 26, 27, 34, and 35.

CHAINS	
	N. 0° 13' W., bet. secs. 26 and 27.
	Over broken desert land, through sagebrush and shadscale; desc. N-NW slope.
40.14	The ¼ sec. cor. of secs. 26 and 27, monumented with a weathered sandstone, 18 x 8 x 4 ins., firmly set 10 ins. in the ground, marks have been obliterated.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 24 E ¼ S 27 | S 26 1977
	Deposit the weathered stone alongside the iron post.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	N. 0° 03' E., beginning new measurement.
39.84	The cor. of secs. 22, 23, 26, and 27, monumented with a broken and weathered sandstone, 18 x 8 x 4 ins., firmly set in a mound of stone, only 1 notch visible, other marks obliterated.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, to top of brass cap, mkd.
	T 9 S R 24 E S 22 | S 23 S 27 | S 26 1977
	Deposit the weathered stone alongside the iron post.
	From the cor. of secs. 23, 24, 25, and 26.
	N. 89° 55' W., bet. secs. 23 and 26.
	Over broken desert land, through sagebrush and shadscale.
39.90	The ¼ sec. cor. of secs. 23 and 26, monumented with an old mound of stone has been used by local surveyors and landowners and is accpeted as the best available evidence of the original cor.
	At the corner point (center of mound)

U.S. Government Printing Office-1978-778-206/433

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base, to top of brass cap, mkd. T 9 S R 24 E ¼ S 23 / S 26 1977
	S. 89° 53' W., beginning new measurement.
39.86	The cor. of secs. 22, 23, 26, and 27.
	N. 0° 02' W., bet. secs. 22 and 23.
	Over broken desert land, through sagebrush and shadscale; desc. gentle NE slope.
9.00	Hard surface road, bears S. 74° W. and N. 74° E.
25.00	Dirt road, bears NW and SE.
40.12	The ¼ sec. cor. of secs. 22 and 23, monumented with a sandstone, 16 x 12 x 6 ins., firmly set in a mound of stone and dimly mkd. ¼ on W face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, to top of brass cap, mkd. T 9 S R 24 E ¼ S 22 | S 23 1977
	Deposit the mkd. stone in mound alongside the iron post.
	N. 0° 04' W., beginning new measurement.
9.00	Dirt road, bears E and W.
27.93	Intersect line 1-4 of Mineral Survey No. 5220, Break of Day Lode.
	From this point cor. No. 1 of the Break of Day Lode, identical with cor. No. 4 of the Superior Lode, survey No. 5219, bears S. 62° 58' E., 0.02 chs. dist., marked by an old scattered mound of stone, no mkd. rock or evidence of original bearing rocks.

CHAINS	
	At the corner point (center of mound) Set a copperweld, 30 ins. long, 5/8 ins. diam., 20 ins. in the ground and in a collar of stone, with cap mkd. 1-5220 4-5219 From this same point of intersection, cor. No. 4 of the Break of Day Lode, identical with cor. No. 1 of the Triumph Lode, survey No. 5221, bears N. 62° 58' W., 22.71 chs. dist., marked by an old mound of stone, from which a cross (X) and 4-5220 chiseled on a sandstone surface, bears N. 83° 45' W., 1.25 chs. dist., no evidence of the other bearing mark. At the corner point Set a copperweld, 30 ins. long, 5/8 ins. diam., 18 ins. in the ground and in a collar of stone, with cap mkd. 1-5221 4-5220
33.03	Intersect line 2-3 of Mineral Survey No. 5220, Break of Day Lode. From this point cor. No. 2 of the Break of Day Lode, identical with cor. No. 3 of the Superior Lode, survey No. 5219, bears S. 62° 58' E., 2.23 chs. dist., mkd. by an old mound of stone. At the corner point (center of mound) Set a copperweld, 30 ins. long, 5/8 ins. diam., 20 ins. in the ground and in a collar of stone, with cap mkd. 2-5220 3-5219 From this same point of intersection, cor. No. 3 of the Break of Day Lode, identical with cor. No. 2 of the Triumph Lode, survey No. 5221, bears N. 62° 58' W., 20.50 chs. dist., marked by an old mound of stone. At the corner point (center of mound) Set a copperweld, 30 ins. long, 5/8 ins. diam., 20 ins. in the ground and in a collar of stone, with cap mkd. 2-5221 3-5220
40.08	The cor. of secs. 14, 15, 22, and 23, monumented with a sandstone, 18 x 8 x 6 ins., firmly set 8 ins. in the ground and plainly mkd. 3 notches on S and 2 notches on E edges. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

☆ U.S. Government Printing Office-1978-778-206/433

CHAINS	
	T 9 S R 24 E S 15 | S 14 S 22 | S 23 1977 Deposit the mkd. stone alongside the iron post. Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor. Cor. is located in bottom of draw, drains NW.
	From the cor. of secs. 13, 14, 23, and 24. S. 89° 54' W., bet. secs. 14 and 23. Over broken desert land, through sagebrush and shadscale; asc. NE slope.
27.00	State highway No. 45, bears N. 27° W. and S. 27° E.
39.91	The ¼ sec. cor. of secs. 14 and 23, monumented with a sandstone, 18 x 8 x 6 ins., firmly set 10 ins. in the ground and plainly mkd. ¼ on N face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap mkd. T 9 S R 24 E ¼ S 14 S 23 1977 Deposit the mkd. stone alongside the iron post.
	N. 89° 44' W., beginning new measurement.
39.92	The cor. of secs. 14, 15, 22, and 23.
	N. 0° 01' W., bet. secs. 14 and 15. Over broken desert land, through sagebrush, shadscale, and greasewood; asc. SW slope.
39.72	The ¼ sec. cor. of secs. 14 and 15, monumented with a sandstone, 12 x 6 x 4 ins., firmly set in a mound of stone and plainly mkd. ¼ on W face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.

CHAINS	
	T 9 S R 24 E ¼ S 15 | S 14 1977 Deposit the mkd. stone alongside the iron post. Cor. is located on gentle NW slope.
	N. 0° 04' W., beginning new measurement.
40.28	The cor. of secs. 10, 11, 14, and 15, monumented with a sandstone, 18 x 12 x 6 ins., firmly set 6 ins. in the ground and plainly mkd. 4 notches on S and 2 notches on E edges. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd. T 9 S R 24 E S 10 | S 11 S 15 | S 14 1977 Deposit the mkd. stone alongside the iron post. Cor. is located on gentle NE slope.
	From the cor. of secs. 11, 12, 13, and 14. S. 89° 59' W., bet. secs. 11 and 14. Over broken desert land, through sagebrush, shadscale and greasewood; in bottom of draw.
39.89	The ¼ sec. cor. of secs. 11 and 14, monumented with a sandstone, 14 x 6 x 6 ins., firmly set 6 ins. in the ground and plainly mkd. ¼ on N face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd. T 9 S R 24 E ¼ S 11 S 14 1977

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
	Deposit the mkd. stone alongside the iron post.
	S. 89° 58' W., beginning new measurement.
19.00	State highway No. 45, bears N. 7° 30' W. and S. 7° 30' E.
40.02	The cor. of secs. 10, 11, 14, and 15.
	N. 0° 02' E., bet. secs. 10 and 11.
	Over broken desert land, through sagebrush, shadscale and greasewood; desc. NE slope.
24.00	Hard surface road, bears N. 70° E. and S. 70° W.
40.04	Point for the ¼ sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 24 E ¼ S 10 | S 11 1977
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
47.50	State highway No. 45, bears N. 25° W. and S. 25° E.
80.08	The cor. of secs. 2, 3, 10, and 11, monumented with a sandstone, 24 x 10 x 8 ins., firmly set 10 ins. in the ground and plainly mkd. 5 notches on S and 2 notches on E edges.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, to top of brass cap, mkd.
	T 9 S R 24 E S 3 | S 2 S 10 | S 11 1977
	Deposit the mkd. stone alongside the iron post.
	Cor. is located on N slope of spur.
	From the cor. of secs. 1, 2, 11, and 12.
	West, bet. secs. 2 and 11.

414

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
	Over broken desert land, through sagebrush, shadscale and greasewood.
39.91	The ¼ sec. cor. of secs. 2 and 11, monumented with a weathered sandstone, 14 x 8 x 6 ins., set in a mound of stone, marks have been obliterated.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd.
	T 9 S R 24 E
	¼ S 2 / S 11
	1977
	Deposit the weathered stone alongside the iron post.
	S. 89° 54' W., beginning new measurement.
39.90	The cor. of secs. 2, 3, 10, and 11.
	N. 0° 02' E., bet. secs. 2 and 3.
	Over broken desert land, through sagebrush and shadscale; desc. N slope.
21.00	Trail road, bears N. 72° E. and S. 72° W.
35.50	Coyote Wash, drains SW.
38.27	Intersect line 2-3 of Mineral Survey No. 5382, White River No. 26 Lode.
	From this point cor. No. 2 of the White River No. 26 Lode, identical with cor. No. 3 of the White River No. 25 Lode, same survey, bears S. 68° 18' E., 1.40 chs. dist., monumented with a sandstone, 13 x 12 x 3 ins. above ground and chiseled 3-2-5382.
	From this same point cor. No. 3 of the White River No. 26 Lode, identical with cor. No. 2 of the White River No. 27 Lode, same survey, bears N. 68° 18' W., 21.27 chs. dist., monumented with a sandstone, 12 x 12 x 3 ins., above ground and chiseled 3-2-5382.
39.99	The ¼ sec. cor. of secs. 2 and 3, monumented with a broken and weathered sandstone, 12 x 6 x 4 ins., firmly set 5 ins. in the ground with a mound of stone W. Marks have been obliterated.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd.

☆ U.S. Government Printing Office-1978-778-206/433

CHAINS	
	T 9 S R 24 E ¼ S 3 | S 2 1977
	Deposit the weathered stone alongside the iron post.
	N. 0° 06' E., beginning new measurement.
3.08	Intersect line 4-1 of Mineral Survey No. 5382, White River No. 26 Lode.
	From this point cor. No. 1 of White River No. 26 Lode, identical with cor. No. 4 of White River No. 25 Lode, same survey, bears S. 68° 23' E., 3.92 chs. dist., monumented with a sandstone, 18 x 16 x 6 ins., above ground and chiseled 4-1-5382.
	From this same point cor. No. 4 of White River No. 26 Lode, identical with cor. No. 1 of White River No. 27 Lode, same survey, bears N. 68° 23' W., 18.76 chs. dist., monumented with a sandstone, 16 x 12 x 6 ins., above ground and chiseled 4-1-5382.
38.69	The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., monumented with an iron post, 2 ins. diam., extending 16 ins. above ground and in a mound of stone to top of brass cap, mkd. as described in the official record of the 1916 resurvey.
	From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., extending 8 ins. above ground and in a collar of stone, with brass cap mkd. as described in the official record of the 1975 resurvey.
	N. 0° 02' E., bet. secs. 33 and 34.
	Over broken desert land, through sagebrush and shadscale; desc. gentle NW slope.
4.00	Trail road, bears N. 70° W. and S. 70° E.
12.35	Intersect line 1-2 of Mineral Survey No. 5275, Alabama Lode.
	From this point cor. No. 1 of the Alabama Lode, identical with cor. No. 2 of the Alaska Lode, same survey, bears S. 67° 28' E., 1.04 chs. dist., monumented with a sandstone, 16 x 4 x 12 ins. above ground and chiseled 2-1-5275, from which the cor. of secs. 3, 4, 33, and 34, Tps. 9 and 10 S., R. 24 E., bears S. 4° 37' W., 11.99 chs. dist., heretofore described.
	From this same point cor. No. 2 of the Alabama Lode, identical with cor. No. 1 of the Asteroid Lode, same survey, bears N. 67° 28' W., 21.69 chs. dist., monumented with a sandstone, 8 x 4 x 12 ins. above ground and chiseled 2-1-5275, from which a cross (X) and B.R. 2-1-5275, chiseled on a rock in place, 8 x 10 x 4 ft. high, bears N. 51° 14' E., 4.08 chs. dist.

416

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
17.248	Intersect line 3-4 of Mineral Survey No. 5275, Alabama Lode. From this point cor. No. 3 of the Alabama Lode, identical with cor. No. 4 of the Asteroid Lode, same survey, bears N. 67° 35' W., 19.80 chs. chs. dist., monumented with a sandstone, 18 x 6 x 10 ins. above ground and chiseled 3-4-5275, from which a cross (X) and B.R. 3-4-5275, chiseled on a small ledge, 1½ ft. high, bears N. 75° 16' E., 1.14 chs. dist. From this same point cor. No. 4 of the Alabama Lode, identical with cor. No. 3 of the Alaska Lode, same survey, bears S. 67° 35' E., 2.93 chs. dist., monumented with a sandstone, 12 x 11 x 11 ins.above ground and chiseled 3-4-5275, from which a cross (X) and B.R. 3-4-5275, chiseled on solid flat sandstone formation, bears N. 19° 26' E., 0.86 chs. dist.
40.03	The ¼ sec. cor. of secs. 33 and 34, monumented with a sandstone, 18 x 8 x 6 ins.; firmly set 8 ins. in the ground and plainly mkd. ¼ on W face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd. T 9 S R 24 E ¼ S 33 | S 34 1977 Deposit the mkd. stone alongside the iron post. --- N. 0° 03' E., beginning new measurement.
40.00	The cor. of secs. 27, 28, 33, and 34, monumented with a sandstone, 18 x 6 x 6 ins., firmly set in a mound of stone and dimly mkd. 3 notches on E and 1 notch on S edges. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock and in a collar of stone, with brass cap mkd. T 9 S R 24 E S 28 | S 27 S 33 | S 34 1977 Deposit the mkd. stone alongside the iron post. Cor. is located on gentle W slope of spur.

U.S. Government Printing Office-1978-778-206/433

CHAINS	
	From the cor. of secs. 26, 27, 34, and 35.
	N. 89° 53' W., bet. secs. 27 and 34.
	Over broken desert land, through sagebrush and shadscale.
39.80	Trail road, bears NE and SW.
39.93	Point for the ¼ sec. cor. of secs. 27 and 34, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 24 E
	¼ S 27 / S 34
	1977
	Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.
	Cor. is located on W edge of road.
79.86	The cor. of secs. 27, 28, 33, and 34.
	N. 0° 02' E., bet. secs. 27 and 28.
	Over broken desert land, through sagebrush and shadscale; desc. along W slope.
20.005	Point for the S 1/16 sec. cor. of secs. 27 and 28.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 24 E S 1/16
	S 28 | S 27
	1977
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
38.00	Trail road, bears E and W; asc. S slope.
40.01	The ¼ sec. cor. of secs. 27 and 28, monumented with a sandstone, 18 x 10 x 6 ins., firmly set 8 ins. in the ground and plainly mkd. ¼ on W face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd.
	T 9 S R 24 E
	¼ S 28 | S 27
	1977

CHAINS	
	Deposit the mkd. stone alongside the iron post.
	Cor. is located in bottom of small draw, drains S.
	N. 0° 04' E., beginning new measurement.
7.00	Trail road on top of ridge, bears NW and SE.
40.05	The cor. of secs. 21, 22, 27, and 28, monumented with a sandstone, 18 x 10 x 6 ins., firmly set 10 ins. in the ground and plainly mkd. 3 notches on E and 2 notches on S edges.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 24 E
	S 21 | S 22 / S 28 | S 27
	1977
	Deposit the mkd. stone alongside the iron post.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	From the cor. of secs. 22, 23, 26, and 27.
	N. 89° 40' W., bet. secs. 22 and 27.
	Over broken desert land, through sagebrush and shadscale; asc. NE slope.
18.00	Dirt road, in draw, bears S. 47° W. and N. 47° E.
39.52	The ¼ sec. cor. of secs. 22 and 27, monumented with a sandstone, 18 x 12 x 5 ins., firmly set in a mound of stone and plainly mkd. ¼ on N face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 24 E
	¼ S 22 / S 27
	1977
	Deposit the mkd. stone alongside the iron post.
	Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.

U.S. Government Printing Office-1978-778-206/433

CHAINS	
	N. 89° 59' W., beginning new measurement.
9.00	Dirt road, bears N. 67° W. and S. 67° E.
40.11	The cor. of secs. 21, 22, 27, and 28.
	N. 0° 01' E., bet. secs. 21 and 22.
	Over broken desert land, through sagebrush and shadscale; desc. gentle NE slope.
20.50	Dirt road, bears N. 79° W. and S. 79° E.
40.04	The ¼ sec. cor. of secs. 21 and 22, monumented with a sandstone, 24 x 8 x 8 ins., firmly set in a mound of stone and plainly mkd. ¼ on W face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground and in a collar of stone, with brass cap mkd.
	T 9 S R 24 E ¼ S 21 | S 22 1977
	Deposit the mkd. stone alongside the iron post.
	N. 0° 02' E., beginning new measurement.
19.975	Point for the N 1/16 sec. cor. of secs. 21 and 22.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 24 E N 1/16 S 21 | S 22 1977
39.95	The cor. of secs. 15, 16, 21, and 22, monumented with a sandstone, 14 x 10 x 6 ins., firmly set in a mound of stone and plainly mkd. 3 notches on S and E edges, T 9 S on NE face and 24 E on SE face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 24 E S 16 | S 15 S 21 | S 22 1977

420

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
	Deposit the mkd. stone alongside the iron post. Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	From the cor. of secs. 14, 15, 22, and 23. S. 89° 51' W., bet. secs. 15 and 22. Over broken desert land, through sagebrush and shadscale; asc. gentle NE slope.
13.73	Intersect line 2-3 of Mineral Survey No. 5220, Break of Day Lode. From this point cor. No. 2 of the Break of Day Lode, identical with cor. No. 2 of the Superior Lode, survey No. 5210, bears S. 62° 58' E., 17.65 chs. dist., heretofore described. From this same point cor. No. 3 of the Break of Day Lode, identical with cor. No. 2 of the Triumph Lode, survey No. 5221, bears N. 62° 58; W., 5.08 chs. dist., heretofore described.
39.73	The ¼ sec. cor. of secs. 15 and 22, monumented with a sandstone, 14 x 8 x 6 ins., firmly set 6 ins. in the ground and plainly mkd. ¼ on N face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 9 S R 24 E ¼ S 15 / S 22 1977 Deposit the mkd. stone alongside the iron post.
	N. 89° 51' W., beginning new measurement.
39.76	The cor. of secs. 15, 16, 21, and 22.
	N. 0° 07' W., bet. secs. 15 and 16. Over broken desert land, through sagebrush and shadscale.
10.50	Trail road, bears NW and SE.
40.14	Point for the ¼ sec. cor. of secs. 15 and 16, at proportionate distance, falls in hard surface road, bears N. 81° E. and S. 81° W.; there is no remaining evidence of the original cor. Due to total private land in secs. 15 and 16, no monument was set.
80.28	The cor. of secs. 9, 10, 15, and 16, monumented with a sandstone, 20 x 10 x 6 ins. firmly set 8 ins. in the ground and plainly mkd. 4 notches on the S and 3 notches on the E edges.

U.S. Government Printing Office-1978-778-206/433

CHAINS	
	At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock and in a collar of stone, with brass cap mkd. T 9 S R 24 E S 9 | S 10 S 16 | S 15 1977 Deposit the mkd. stone alongside the iron post.
	From the cor. of secs. 10, 11, 14, and 15. N. 89° 35' W., bet. secs. 10 and 15. Over broken desert land, through sagebrush and shadscale; asc. NE slope.
33.50	Hard surface road, bears S. 36° W. and N. 36° E.
39.67	The ¼ sec. cor. of secs. 10 and 15, monumented with a sandstone, 14 x 10 x 6 ins., firmly set 8 ins. in the ground and dimly mkd. ¼ on N face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap mkd. T 9 S R 24 E ¼ S 10 S 15 1977 Deposit the mkd. stone alongside the iron post. Set a steel fence post, N of cor.
	S. 89° 59' W., beginning new measurement.
39.95	The cor. of secs. 9, 10, 15, and 16.
	North, bet. secs. 9 and 10. Over broken desert land, through sagebrush and shadscale; desc. gentle NE slope.
40.04	The ¼ sec. cor. of secs. 9 and 10, monumented with a conglomerate stone, 20 x 14 x 4 ins., firmly set in a mound of stone and plainly mkd. ¼ on W face.

CHAINS	
	At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 9 S R 24 E ¼ S 9 | S 10 1977 Deposit the mkd. stone alongside the iron post.
	N. 0° 07' W., beginning new measurement.
30.00	Coyote Wash, 1 ch. wide, 3 ft. deep, drains W.
39.81	The cor. of secs. 3, 4, 9, and 10, monumented with a sandstone, 20 x 10 x 6 ins., firmly set 8 ins. in the ground and dimly mkd. 5 notches on S and 3 notches on E edges. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 9 S R 24 E S 4 | S 3 S 9 | S 10 1977 Deposit the mkd. stone alongside the iron post. Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	From the cor. of secs. 2, 3, 10, and 11. N. 89° 49' W., bet. secs. 3 and 10. Over broken desert land, through sagebrush and shadscale; desc. NW slope.
15.00	State highway No. 45, bears N. 18° W. and S. 18° E.
19.97	Point for the E 1/16 sec. cor. of secs. 3 and 10, falls in large wash, 20 lks. wide, 12 ft. deep, drains N; asc. NE slope.
20.27	Point selected for the witness cor. to the E 1/16 sec. cor. of secs. 3 and 10. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

U.S. Government Printing Office-1978-778-206/433

CHAINS	
	W C T 9 S R 24 E E 1/16 S 3 / S 10 1977
39.94	The ¼ sec. cor. of secs. 3 and 10, monumented with a sandstone, 15 x 10 x 4 ins., firmly set 6 ins. in the ground and plainly mkd. ¼ on N face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd. T 9 S R 24 E ¼ S 3 / S 10 1977 Deposit the mkd. stone alongside the iron post. Cor. is located on N rim of spur, projecting W.
	S. 89° 54' W., beginning new measurment.
15.00	Coyote Wash, 2 chs. wide, 2 ft. deep, drains SW; asc. SE slope.
39.84	The cor. of secs. 3, 4, 9, and 10.
	N. 0° 13' W., bet. secs. 3 and 4. Over broken desert land, through sagebrush and shadscale; desc. N-NW slope.
40.29	The ¼ sec. cor. of secs. 3 and 4, monumented with a sandstone, 18 x 8 x 6 ins., firmly set 5 ins. in the ground and plainly mkd. ¼ on W face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground and in a collar of stone, with brass cap mkd. T 9 S R 24 E ¼ S 4 | S 3 1977 Deposit the mkd. stone alongside the iron post.

CHAINS	
	N. 0° 29' E., beginning new measurement.
20.04	Point for the N 1/16 sec. cor. of secs. 3 and 4. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 9 S R 24 E N 1/16 S 4 | S 3 1977
38.27	The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., monumented with an iron post, 2 ins. diam., extending 12 ins. above ground, with brass cap mkd. as described in the official record of the 1916 resurvey.
	From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., extending 10 ins. above ground, with brass cap mkd. as described in the official record of the 1975 resurvey. N. 0° 09' E., bet. secs. 32 and 33. Over broken desert land, through sagebrush and shadscale; desc. NW slope.
39.98	The ¼ sec. cor. of secs. 32 and 33, monumented with an old mound of stone. This position is accepted as the best available evidence of the original cor. position. At the corner point (center of mound) Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd. T 9 S R 24 E ¼ S 32 | S 33 1977 Set a steel fence post, NE of cor.
	N. 0° 07' E., beginning new measurement.
6.14	Intersect line 1-2 of Mineral Survey No. 5276, Abysinia Lode. From this point cor. No. 1 of the Abysinia Lode, identical with cor. No. 2 of the Alexandria Lode, same survey, bears S. 66° 22' E., 19.81 chs. dist., monumented with a sandstone, 12 x 10 x 11 ins. above ground and chiseled 2-1-5276, from which a cross (X) and B.R. 2-1-5276, chiseled on a small ledge 2 ft. high, bears N. 0° 27' E., 4.30 chs. dist.

U.S. Government Printing Office-1978-778-206/433

CHAINS	
	From this same point cor. No. 2 of the Abysinia Lode, bears N. 66° 22' W., 2.92 chs. dist., monumented with a sandstone, 11 x 8 x 13 ins. above ground and chiseled 2-5276, from which a cross (X) and B.R. 2-5276 chiseled on solid sandstone formation, bears S. 67° 57' E., 88 lks. dist.
10.00	Trail road, bears NW and SE.
11.05	Intersect line 3-4 of Mineral Survey No. 5276, Abysinia Lode.
	From this point cor. No. 3 of the Abysinia Lode, bears N. 66° 20' W., 1.02 chs. dist., monumented with a sandstone, 34 x 10 x 8 ins., set in a mound of stone and chiseled 3-5276, from which a cross (X) and B.R. 3-5276 chiseled on a small ledge 4 ft. high, bears N. 48° 52' E., 1.64 chs. dist.
	From this same point cor. No. 4 of the Absyinia Lode, identical with cor. No. 3 of the Alexandria Lode, same survey, bears S. 66° 20' E., 21.72 chs. dist., monumented with a sandstone, 8 x 6 x 10 ins. above ground and chiseled 3-4-5276, from which a cross (X) and B.R. 3-4-5276, chiseled on a small edge, 2 ft. high, bears N. 73° 39' W., 2.05 chs. dist.
18.00	Trail road, bears N. 25° W. and S. 25° E.
32.00	Same road, bears N. 50° E. and S. 50° W.
40.30	The cor. of secs. 28, 29, 32, and 33, monumented with a sandstone, 15 x 12 x 6 ins., firmly set 8 ins. in the ground and plainly mkd. 4 notches on E and 1 notch on S edges.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 24 E
	S 29 | S 28
	S 32 | S 33
	1977
	Deposit the mkd. stone and set a steel fence post alongside the iron post.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	From the cor. of secs. 27, 28, 33, and 34.
	N. 89° 45' W., bet. secs. 28 and 33.
	Over broken land, through sagebrush and shadscale.
40.00	The ¼ sec. cor. of secs. 28 and 33, monumented with a sandstone, 14 x 7 x 4 ins., firmly set 6 ins. in the ground and dimly mkd. ¼ on N face.

CHAINS	
	At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd. T 9 S R 24 E ¼ S 28 / S 33 1977 Deposit the mkd. stone alongside the iron post.
	N. 89° 43' W., beginning new measurement.
33.50	Trail road, bears NE and SW.
40.07	The cor. of secs. 28, 29, 32, and 33.
	N. 0° 10' W., bet. secs. 28 and 29. Over broken desert land, through sagebrush and shadscale.
39.86	The ¼ sec. cor. of secs. 28 and 29, monumented with a sandstone, 16 x 8 x 6 ins., firmly set 6 ins. in the ground and dimly mkd. ¼ on W face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 9 S R 24 E ¼ S 29 | S 28 1977 Deposit the mkd. stone alongside the iron post. Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	N. 0° 06' E., beginning new measurement.
39.80	The cor. of secs. 20, 21, 28, and 29, monumented with a sandstone, 14 x 10 x 6 ins., firmly set 4 ins. in the ground and plainly mkd. 4 notches on E and 2 notches on S edges. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd.

CHAINS	
	T 9 S R 24 E S 20 | S 21 S 29 | S 28 1977 Deposit the mkd. stone alongside the iron post.
	From the cor. of secs. 21, 22, 27, and 28. N. 89° 54' W., bet. secs. 21 and 28. Over broken desert land, through sagebrush and shadscale; asc. SE slope.
40.04	The ¼ sec. cor. of secs. 21 and 28, monumented with a sandstone, 18 x 8 x 5 ins., firmly set 8 ins. in the ground and plainly mkd. ¼ on N face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 9 S R 24 E ¼ S 21 / S 28 1977 Deposit the mkd. stone alongside the iron post. Cor. is located on SW slope of hill.
	S. 89° 50' W., beginning new measurement.
40.12	The cor. of secs. 20, 21, 28, and 29.
	N. 0° 01' E., bet. secs. 20 and 21. Over broken desert land, through sagebrush and shadscale; desc. gentle NW slope.
40.02	Point for the ¼ sec. cor. of secs. 20 and 21, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 9 S R 24 E ¼ S 20 | S 21 1977

428

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
40.60	Dirt road, bears E and W.
80.04	The cor. of secs. 16, 17, 20, and 21, monumented with a sandstone, 16 x 8 x 4 ins., firmly set 4 ins. in the ground and plainly mkd. 4 notches on E and 3 notches on S edges. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 9 S R 24 E S 17 | S 16 S 20 | S 21 1977 Deposit the mkd. stone alongside the iron post. Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor. Cor. is located on gentle N slope.
	From the cor. of secs. 15, 16, 21, and 22. S. 89° 58' W., bet. secs. 16 and 21. Over broken desert land, through sagebrush and shadscale; asc. gentle E slope.
40.09	The ¼ sec. cor. of secs. 16 and 21, monumented with a sandstone, 20 x 10 x 6 ins., firmly set in a mound of stone and dimly mkd. ¼ on N face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 9 S R 24 E ¼ S 16 / S 21 1977 Deposit the mkd. stone in mound alongside the iron post. Cor. is located on S slope of low hill.
	S. 89° 59' W., beginning new measurement.
40.06	The cor. of secs. 16, 17, 20, and 21.

☆ U.S. Government Printing Office-1978-778-206/433

CHAINS	
	N. 0° 03' E., bet. secs. 16 and 17.
	Over broken desert land, through sagebrush and shadscale.
2.00	Dirt road, bears E and W.
40.17	The ¼ sec. cor. of secs. 16 and 17, monumented with a sandstone, 18 x 6 x 4 ins., firmly set 6 ins. in the ground and dimly mkd. ¼ on W face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd.
	T 9 S R 24 E ¼ S 17 | S 16 1977
	Deposit the mkd. stone alongside the iron post.
	Set a steel fence post, N of cor.
	N. 0° 20' W., beginning new measurement.
40.07	The cor. of secs. 8, 9, 16, and 17, monumented with a weathered sandstone, 12 x 6 x 6 ins., firmly set 4 ins. in the ground and witnessed by a mound of stone to W., marks have been obliterated.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 24 E S 8 | S 9 S 17 | S 16 1977
	Deposit the weathered stone and set a steel fence post alongside the iron post.
	Cor. is located at base of hill, bears NW and SE.
	From the cor. of secs. 9, 10, 15, and 16.
	S. 89° 47' W., bet. secs. 9 and 16.
	Over broken desert land, through sagebrush and shadscale; asc. SE slope.
39.93	The ¼ sec. cor. of secs. 9 and 16, monumented with a sandstone, 18 x 10 x 5 ins., firmly set in a mound of stone and dimly mkd. ¼ on N face.

430

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
	At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 9 S R 24 E ¼ S 9 / S 16 1977 Deposit the mkd. stone and set a steel fence post alongside the iron post.
	N. 89° 52' W., beginning new measurement.
40.23	The cor. of secs. 8, 9, 16, and 17.
	N. 0° 06' W., bet. secs. 8 and 9. Over broken desert land, through sagebrush and shadscale.
40.21	The ¼ sec. cor. of secs. 8 and 9, monumented with a sandstone, 16 x 6 x 5 ins., firmly set 6 ins. in the ground and plainly mkd. ¼ on W face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd. T 9 S R 24 E ¼ S 8 | S 9 1977 Deposit the mkd. stone alongside the iron post.
	N. 0° 09' E., beginning new measurement.
40.19	The cor. of secs. 4, 5, 8, and 9, monumented with a sandstone, 18 x 8 x 6 ins., firmly set 8 ins. in the ground and plainly mkd. 5 notches on S and 4 notches on E edges. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 9 S R 24 E S 5 | S 4 S 8 | S 9 1977

U.S. Government Printing Office-1978-778-206/433

CHAINS	
	Deposit the mkd. stone alongside the iron post. Cor. is located on NW rim of small rise.
	From the cor. of secs. 3, 4, 9, and 10. N. 89° 37' W., bet. secs. 4 and 9. Over broken desert land, through sagebrush and shadscale; desc. SW slope.
40.01	Point for the ¼ sec. cor. of secs. 4 and 9, at proportionate distance, falls in flood area on the right bank of Coyote Wash, drains N. There is no remaining evidence of the original cor.
41.01	Point selected for the witness cor. to the ¼ sec. cor. of secs. 4 and 9, on the left bank of Coyote Wash, also top of low spur, slopes N. Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd. W C T 9 S R 24 E ¼ S 4 / S 9 > 1977
	Over bottom land in Coyote Wash.
80.02	The cor. of secs. 4, 5, 8, and 9.
	N. 0° 03' W., bet. secs. 4 and 5. Over broken desert land, through sagebrush and shadscale; desc. NW slope.
3.00	Coyote Wash, 30 lks. wide, 3 ft. deep, drains W.
39.97	The ¼ sec. cor. of secs. 4 and 5, monumented with a sandstone, 18 x 10 x 6 ins., firmly set 6 ins. in the ground and plainly mkd. ¼ on W face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd. T 9 S R 24 E ¼ S 5 | S 4 1977
	Deposit the mkd. stone alongside the iron post.

432

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
	Cor. is located on ridge, bears NE and SW.
	N. 0° 12' E., beginning new measurement.
	Over rolling land.
4.00	Trail road, bears N. 55° E. and S. 55° W.
38.17	The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., monumented with an iron post, 2 ins. diam., extending 8 ins. above ground with brass cap mkd. as described in the official record of the 1916 resurvey.
	From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., extending 8 ins. above ground with brass cap mkd. as described in the official record of the 1975 resurvey.
	North, bet. secs. 31 and 32.
	Over broken desert land, through sagebrush and shadscale.
40.01	The ¼ sec. cor. of secs. 31 and 32, monumented with a sandstone, 16 x 8 x 6 ins., firmly set 6 ins. in the ground and plainly mkd. ¼ on W face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 24 E ¼ S 31 | S 32 1977
	Deposit the mkd. stone alongside the iron post.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	N. 0° 05' E., beginning new measurement.
40.10	The cor. of secs. 29, 30, 31, and 32, monumented with a sandstone, 16 x 8 x 6 ins., firmly set 4 ins. in the ground and dimly mkd. 5 notches on E and 1 notch on S edges.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

U.S. Government Printing Office-1978-778-206/433

CHAINS	
	T 9 S R 24 E S 30 | S 29 S 31 | S 32 1977 Deposit the mkd. stone and set a cedar post alongside the iron post. From this cor., U.S.G.S. triangulation station "JEK 8 ET 1966", bears S. 62° 32' 23" E., 53.105 chs. dist., mkd. by a standard aluminum tablet cemented in rock, mkd. JEK 8 ET 1966 +.
	From the cor. of secs. 28, 29, 32, and 33. N. 89° 59' W., bet. secs. 29 and 32. Over broken desert land, through sagebrush and shadscale.
40.32	The ¼ sec. cor. of secs. 29 and 32, monumented with a sandstone, 14 x 8 x 6 ins., firmly set 6 ins. in the ground and plainly mkd. ¼ on N face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap mkd. T 9 S R 24 E ¼ S 29 / S 32 1977 Deposit the mkd. stone and set a steel fence post alongside the iron post. Cor. is located on gentle N slope.
	S. 89° 57' W., beginning new measurement.
25.00	Trail road, bears NW and SE.
39.75	The cor. of secs. 29, 30, 31, and 32.
	N. 89° 38' W., bet. secs. 30 and 31. Over broken desert land, through sagebrush and shadscale.
36.50	Trail road, bears N and S.
40.64	The ¼ sec. cor. of secs. 30 and 31, monumented with a sandstone, 14 x 8 x 6 ins., firmly set 4 ins. in the ground and plainly mkd. ¼ on N face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap mkd.

434

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
	T 9 S R 24 E ¼ S 30 / S 31 1977
	Deposit the mkd. stone alongside the iron post.
	S. 89° 55' W., beginning new measurement.
12.50	Jeep trail, bears N and S.
38.78	The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., heretofore described.
	From the cor. of secs. 29, 30, 31, and 32.
	N. 0° 06' E., bet. secs. 29 and 30.
	Over broken desert land, through sagebrush and shadscale.
13.00	Dirt road, bears NW and SE on curve.
19.93	Point for the S 1/16 sec. cor. of secs. 29 and 30.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 24 E S 1/16 S 30 | S 29 1977
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	Cor. is located 50 lks. E of dirt road.
21.50	Dirt road, bears N. 15° E. and S. 15° W.
39.86	The ¼ sec. cor. of secs. 29 and 30, monumented with a sandstone, 20 x 10 x 6 ins., firmly set 8 ins. in the ground and plainly mkd. ¼ on W face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 9 S R 24 E ¼ S 30 | S 29 1977
	Deposit the mkd. stone alongside the iron post.

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	N. 0° 04' W., beginning new measurement.
17.00	Dirt road, in draw, bears NE and SW.
39.96	The cor. of secs. 19, 20, 29, and 30, monumented with a sandstone, 14 x 10 x 8 ins., firmly set 6 ins. in the ground and plainly mkd. 5 notches on E and 2 notches on S edges. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 9 S R 24 E S 19 | S 20 S 30 | S 29 1977 Deposit the mkd. stone alongside the iron post. Cor. is located in bottom of draw, drains NE.
	From the cor. of secs. 20, 21, 28, and 29. N. 89° 50' W., bet. secs. 20 and 29. Over broken desert land, through sagebrush and shadscale; desc. W slope.
40.04	The ¼ sec. cor. of secs. 20 and 29, monumented with a sandstone, 16 x 14 x 8 ins., firmly set 8 ins. in the ground and plainly mkd. ¼ on N face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 9 S R 24 E ¼ S 20 S 29 1977 Deposit the mkd. stone alongside the iron post. Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.
	N. 89° 57' W., beginning new measurement.
32.00	Dirt road, bears NE and SW, in small canyon.
39.92	The cor. of secs. 19, 20, 29, and 30.

CHAINS	
	N. 89° 45' W., bet. secs. 19 and 30.
	Over broken desert land, through sagebrush and shadscale; asc. E slope.
39.88	The ¼ sec. cor. of secs. 19 and 30, monumented with a sandstone, 18 x 10 x 6 ins., firmly set 6 ins. in the ground and plainly mkd. ¼ on N face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.
	T 9 S R 24 E ¼ S 19 / S 30 1977
	Deposit the mkd. stone alongside the iron post.
	N. 89° 44' W., beginning new measurement.
39.34	The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., heretofore described.
	From the cor. of secs. 19, 20, 29, and 30.
	N. 0° 02' W., bet. secs. 19 and 20.
	Over broken desert land, through sagebrush and shadscale; asc. SE slope.
39.95	The ¼ sec. cor. of secs. 19 and 20, monumented with a sandstone, 16 x 6 x 5 ins., firmly set 8 ins. in the ground and plainly mkd. ¼ on W face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.
	T 9 S R 24 E ¼ S 19 | S 20 1977
	Deposit the mkd. stone in mound alongside the iron post.
	N. 0° 18' W., beginning new measurement.

U.S. Government Printing Office-1978-778-206/433

CHAINS	
40.14	The cor. of secs. 17, 18, 19, and 20, monumented with a sandstone, 20 x 8 x 5 ins., firmly set in a mound of stone and dimly mkd. 5 notches on E and 3 notches on S edges. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd. T 9 S R 24 E S 18 | S 17 S 19 | S 20 1977 Deposit the mkd. stone alongside the iron post. Cor. is located on top of ridge, bears NE and SW.
	From the cor. of secs. 16, 17, 20, and 21. S. 89° 50' W., bet. secs. 17 and 20. Over broken desert land, through sagebrush and shadscale; asc. SE slope.
4.00	Dirt road, bears NE and SW.
39.98	The ¼ sec. cor. of secs. 17 and 20, monumented with a sandstone, 18 x 12 x 6 ins., firmly set 6 ins. in the ground and plainly mkd. ¼ on N face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 9 S R 24 E ¼ S 17 / S 20 1977 Deposit the mkd. stone alongside the iron post. Cor. is located on top of bench, bears E and W.
	N. 89° 35' W., beginning new measurement.
23.00	Dirt road, bears S and NW in bottom of draw, drains NW.
40.22	The cor. of secs. 17, 18, 19, and 20.
	N. 89° 50' W., bet. secs. 18 and 19. Over broken desert land, through sagebrush and shadscale; desc. NW slope.

CHAINS	
39.68	The ¼ sec. cor. of secs. 18 and 19, monumented with a sandstone, 18 x 10 x 4 ins., firmly set 6 ins. in the ground and plainly mkd. ¼ on N face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 9 S R 24 E ¼ S 18 / S 19 1977 Deposit the mkd. stone alongside the iron post. Cor. is located on steep E slope of low knoll.
	N. 89° 34' W., beginning new measurement.
39.25	The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., heretofore described.
	From the cor. of secs. 17, 18, 19, and 20. N. 0° 08' E., bet. secs. 17 and 18. Over broken desert land, through sagebrush and shadscale; desc. N-NW slope.
9.00	Dirt road, bears E and W.
40.15	The ¼ sec. cor. of secs. 17 and 18, monumented with a sandstone, 20 x 8 x 6 ins., firmly set on solid rock and in a mound of stone and plainly mkd. ¼ on W face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., on solid rock (over cross), and in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 9 S R 24 E ¼ S 18 | S 17 1977 Deposit the mkd. stone in mound alongside the iron post. Cor. is located on S rim of small bench, bears E and W.
	N. 0° 01' W., beginning new measurement.
40.12	The cor. of secs. 7, 8, 17, and 18, monumented with a sandstone, 16 x 8 x 5 ins., firmly set in a mound of stone and plainly mkd. 5 notches on E and 4 notches on S edges.

U.S. Government Printing Office-1978-778-206/433

CHAINS	
	At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, to top of brass cap, mkd. T 9 S R 24 E S 7 | S 8 S 18 | S 17 1977 Deposit the mkd. stone in mound alongside the iron post.
	From the cor. of secs. 8, 9, 16, and 17. N. 89° 51' W., bet. secs. 8 and 17. Over broken desert land, through sagebrush and shadscale.
39.95	Point for the ¼ sec. cor. of secs. 8 and 17, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., on solid rock (over cross), in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 9 S R 24 E ¼ S 8 / S 17 1977 Cor. is located on steep SE slope of hill.
79.90	The cor. of secs. 7, 8, 17, and 18.
	N. 89° 50' W., bet. secs. 7 and 18. Over broken desert land, through sagebrush and shadscale.
40.07	Point for the ¼ sec. cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd. T 9 S R 24 E ¼ S 7 / S 18 1977 Cor. is located on S edge of small wash, 6 lks. wide, 6 ins. deep, drains SW.

CHAINS	
79.24	The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., heretofore described.

From the cor. of secs. 7, 8, 17 and 18.

North, bet. secs. 7 and 8.

Over rolling desert land, through sagebrush and shadscale.

40.21 The ¼ sec. cor. of secs. 7 and 8 monumented with a sandstone, 12 x 8 x 4 ins., firmly set 4 ins. in the ground and dimly mkd. ¼ on W face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap mkd.

T 9 S R 24 E

¼

S 7 | S 8

1977

Deposit the mkd. stone alongside the iron post.

N. 0° 17' W., beginning new measurement.

38.00 Coyote Wash, 25 lks. wide, 2 ft. deep, drains NW.

40.13 Point for the cor. of secs. 5, 6, 7, and 8, at proportionate distance; there is no remaining evidence of the original cor.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap mkd.

T 9 S R 24 E

S 6 | S 5
S 7 | S 8

1977

Cor. is located in bottom land of Coyote Wash.

From the cor. of secs. 4, 5, 8, and 9.

N. 89° 56' W., bet. secs. 5 and 8.

Over bottom land in Coyote Wash, through sagebrush and shadscale.

40.03 The ¼ sec. cor. of secs. 5 and 8, monumented with a sandstone, 14 x 8 x 4 ins., firmly set 4 ins. in the ground and plainly mkd. ¼ on N face.

CHAINS	
	At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd. T 9 S R 24 E ¼ S 5 / S 8 1977 Deposit the mkd. stone alongside the iron post. Cor. is located at base of hill, bears NE and SW. N. 89° 47' W., beginning new measurement. Asc. SE slope.
40.08	The cor. of secs. 5, 6, 7, and 8.
	N. 89° 43' W., bet. secs. 6 and 7. Over bottom land, through sagebrush and shadscale.
4.00	Coyote Wash, 1.00 ch. wide, 3 ft. deep, drains NW.
40.02	The ¼ sec. cor. of secs. 6 and 7, monumented with a sandstone, 20 x 8 x 6 ins., firmly set 10 ins. in the ground and plainly mkd. ¼ on N face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap mkd. T 9 S R 24 E ¼ S 6 / S 7 1977 Deposit the mkd. stone alongside the iron post. S. 89° 47' W., beginning new measurement. Over rolling land.
2.00	Trail road, bears NE and SW.
37.00	Enter Coyote Wash, drains NW from NE on bend.
38.92	True point for the cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., heretofore described.

442

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 24 E., Salt Lake Meridian, Utah

CHAINS	
	From the cor. of secs. 5, 6, 7, and 8.
	N. 0° 07' W., bet. secs. 5 and 6.
	Over rolling desert land, through sagebrush and shadscale; asc. gentle SW slope.
19.00	Trail road, bears NE and SW.
40.13	The ¼ sec. cor. of secs. 5 and 6, monumented with a sandstone, 16 x 8 x 6 ins., firmly set 6 ins. in the ground and plainly mkd. ¼ on W face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap mkd.
	T 9 S R 24 E ¼ S 6 | S 5 1977
	Deposit the mkd. stone alongside the iron post.
	N. 0° 09' E., beginning new measurement.
38.00	The cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the Tp., monumented with an iron post, 2 ins. diam., extending 12 ins. above ground with brass cap mkd. as described in the official record of the 1916 resurvey.

General Description

The area resurveyed within T. 9 S., R. 24 E., Salt Lake Meridian, varies from mountainous in the extreme southern portion to gentle rolling desert land in the northern portion. The general drainage is to the west. The elevation ranges from about 5100 ft. in the NW portion to 5800 ft. above sea level in the far south. The soil is sandy clay loam in most areas, with some small sandstone outcroppings throughout the township. The vegetation consists of sagebrush, shadscale and greasewood, with light juniper growth in secs. 34 and 35 only.

The mining town of Bonanza is located in sec. 23, with Little Bonanza located in sec. 16.

Access is by State Route No. 45 which enters the township on the north boundary of sec. 3, traversing through secs. 10, 11, 14, 23, 24, 25, and 26, and leaving on the south boundary of sec. 35. There are numerous gravel and dirt roads throughout the township.

The principal uses of the area are gilsonite mining and seasonal livestock grazing.

☆ GPO 1980—680-288/121

Form 9600-11
(August 1979)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Daniel Mates	Surveying Technician
Craig Black	Survey Aid
Russell Brown	Survey Aid
Ellis Peterson	Survey Aid

CERTIFICATE OF SURVEY

XX (We), Ferrel D. Reynolds and Craig P. Sylvester, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 20th day of May, 1977, XX (We) have dependently resurveyed the east and west boundaries and the subdivisional lines of Township 9 South, Range 24 East,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by XXX, (us) and under XXX (our) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

December 7, 1979 (Date) — Craig P. Sylvester (Cadastral Surveyor) Supervisory

December 7, 1979 (Date) — Ferrel D. Reynolds (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Denver, Colorado

The foregoing field notes of the dependent resurvey of the east and west boundaries and the subdivisional lines of Township 9 South, Range 24 East of the Salt Lake Meridian in the State of Utah.

executed by Ferrel D. Reynolds and Craig P. Sylvester

having been critically examined and found correct, are hereby approved.

APR 14 1981 (Date) — (Chief, Cadastral Survey Examination and Approval Staff)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in , is a true copy of the original field notes.~~

~~(Date) (Chief, Cadastral Survey Examination and Approval Staff)~~

```
2008.11.19 15:15 B T:\field_notes\rectangular_ notes\r0601\r0601-0000.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0000.tif
2008.11.19 15:20 B T:\field_notes\rectangular_ notes\r0601\r0601-0044.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0044.tif
2008.11.19 15:20 B T:\field_notes\rectangular_ notes\r0601\r0601-0045.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0045.tif
2008.11.19 15:20 B T:\field_notes\rectangular_ notes\r0601\r0601-0046.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0046.tif
2008.11.19 15:20 B T:\field_notes\rectangular_ notes\r0601\r0601-0047.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0047.tif
2008.11.19 15:20 B T:\field_notes\rectangular_ notes\r0601\r0601-0048.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0048.tif
2008.11.19 15:20 B T:\field_notes\rectangular_ notes\r0601\r0601-0049.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0049.tif
2008.11.19 15:20 B T:\field_notes\rectangular_ notes\r0601\r0601-0050.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0050.tif
2008.11.19 15:20 B T:\field_notes\rectangular_ notes\r0601\r0601-0051.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0051.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0052.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0052.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0053.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0053.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0054.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0054.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0055.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0055.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0056.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0056.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0057.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0057.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0058.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0058.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0059.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0059.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0060.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0060.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0061.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0061.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0062.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0062.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0063.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0063.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0064.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0064.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0065.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0065.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0066.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0066.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0067.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0067.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0068.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0068.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0069.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0069.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0070.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0070.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0071.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0071.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0072.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0072.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0073.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0073.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0074.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0074.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0075.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0075.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0076.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0076.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0077.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0077.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0078.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0078.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0079.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0079.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0080.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0080.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0081.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0081.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0082.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0082.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0083.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0083.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0084.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0084.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0085.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0085.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0086.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0086.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0087.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0087.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0088.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0088.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0089.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0089.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0090.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0090.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0091.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0091.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0092.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0092.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0093.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0093.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0094.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0094.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0095.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0095.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0096.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0096.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0097.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0097.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0098.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0098.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0099.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0099.tif
2008.11.19 15:21 B T:\field_notes\rectangular_ notes\r0601\r0601-0100.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0100.tif
2008.11.19 15:22 B T:\field_notes\rectangular_ notes\r0601\r0601-0101.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0101.tif
2008.11.19 15:22 B T:\field_notes\rectangular_ notes\r0601\r0601-0102.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0102.tif
2008.11.19 15:22 B T:\field_notes\rectangular_ notes\r0601\r0601-0103.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0103.tif
2008.11.19 15:22 B T:\field_notes\rectangular_ notes\r0601\r0601-0104.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0104.tif
2008.11.19 15:22 B T:\field_notes\rectangular_ notes\r0601\r0601-0105.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0105.tif
2008.11.19 15:22 B T:\field_notes\rectangular_ notes\r0601\r0601-0106.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0106.tif
2008.11.19 15:22 B T:\field_notes\rectangular_ notes\r0601\r0601-0107.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0107.tif
2008.11.19 15:22 B T:\field_notes\rectangular_ notes\r0601\r0601-0108.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0108.tif
2008.11.19 15:22 B T:\field_notes\rectangular_ notes\r0601\r0601-0109.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0109.tif
2008.11.19 15:22 B T:\field_notes\rectangular_ notes\r0601\r0601-0110.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0110.tif
2008.11.19 15:22 B T:\field_notes\rectangular_ notes\r0601\r0601-0111.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0111.tif
2008.11.19 15:22 B T:\field_notes\rectangular_ notes\r0601\r0601-0112.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0112.tif
2008.11.19 15:22 B T:\field_notes\rectangular_ notes\r0601\r0601-0113.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0113.tif
2008.11.19 15:22 B T:\field_notes\rectangular_ notes\r0601\r0601-0114.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0114.tif
2008.11.19 15:22 B T:\field_notes\rectangular_ notes\r0601\r0601-0115.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0115.tif
2008.11.19 15:22 B T:\field_notes\rectangular_ notes\r0601\r0601-0116.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0116.tif
2008.11.19 15:22 B T:\field_notes\rectangular_ notes\r0601\r0601-0117.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0117.tif
2008.11.19 15:22 B T:\field_notes\rectangular_ notes\r0601\r0601-0118.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0118.tif
2008.11.19 15:22 B T:\field_notes\rectangular_ notes\r0601\r0601-0119.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0119.tif
2008.11.19 15:22 B T:\field_notes\rectangular_ notes\r0601\r0601-0120.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0120.tif
2008.11.19 15:22 B T:\field_notes\rectangular_ notes\r0601\r0601-0121.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0121.tif
2008.11.19 15:22 B T:\field_notes\rectangular_ notes\r0601\r0601-0122.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0122.tif
2008.11.19 15:22 B T:\field_notes\rectangular_ notes\r0601\r0601-0123.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0123.tif
2008.11.19 15:22 B T:\field_notes\rectangular_ notes\r0601\r0601-0124.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0124.tif
2008.11.19 15:22 B T:\field_notes\rectangular_ notes\r0601\r0601-0125.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0125.tif
2008.11.19 15:22 B T:\field_notes\rectangular_ notes\r0601\r0601-0126.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0126.tif
2008.11.19 15:22 B T:\field_notes\rectangular_ notes\r0601\r0601-0127.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0127.tif
2008.11.19 15:22 B T:\field_notes\rectangular_ notes\r0601\r0601-0128.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0128.tif
2008.11.19 15:22 B T:\field_notes\rectangular_ notes\r0601\r0601-0129.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0129.tif
2008.11.19 15:22 B T:\field_notes\rectangular_ notes\r0601\r0601-0130.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0130.tif
2008.11.19 15:22 B T:\field_notes\rectangular_ notes\r0601\r0601-0131.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0131.tif
2008.11.19 15:22 B T:\field_notes\rectangular_ notes\r0601\r0601-0132.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0132.tif
2008.11.19 15:22 B T:\field_notes\rectangular_ notes\r0601\r0601-0133.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0133.tif
2008.11.19 15:22 B T:\field_notes\rectangular_ notes\r0601\r0601-0134.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0134.tif
2008.11.19 15:22 B T:\field_notes\rectangular_ notes\r0601\r0601-0135.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0135.tif
2008.11.19 15:22 B T:\field_notes\rectangular_ notes\r0601\r0601-0136.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0136.tif
2008.11.19 15:22 B T:\field_notes\rectangular_ notes\r0601\r0601-0137.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0137.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0138.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0138.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0139.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0139.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0140.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0140.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0141.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0141.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0142.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0142.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0143.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0143.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0144.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0144.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0145.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0145.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0146.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0146.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0147.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0147.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0148.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0148.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0149.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0149.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0150.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0150.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0151.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0151.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0152.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0152.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0153.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0153.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0154.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0154.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0155.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0155.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0156.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0156.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0157.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0157.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0158.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0158.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0159.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0159.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0160.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0160.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0161.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0161.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0162.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0162.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0163.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0163.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0164.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0164.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0165.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0165.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0166.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0166.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0167.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0167.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0168.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0168.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0169.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0169.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0170.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0170.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0171.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0171.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0172.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0172.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0173.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0173.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0174.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0174.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0175.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0175.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0176.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0176.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0177.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0177.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0178.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0178.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0179.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0179.tif
2008.11.19 15:23 B T:\field_notes\rectangular_ notes\r0601\r0601-0180.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0180.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0181.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0181.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0182.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0182.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0183.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0183.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0184.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0184.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0185.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0185.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0186.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0186.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0187.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0187.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0188.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0188.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0189.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0189.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0190.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0190.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0191.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0191.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0192.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0192.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0193.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0193.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0194.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0194.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0195.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0195.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0196.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0196.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0197.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0197.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0198.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0198.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0199.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0199.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0200.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0200.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0201.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0201.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0202.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0202.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0203.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0203.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0204.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0204.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0205.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0205.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0206.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0206.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0207.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0207.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0208.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0208.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0209.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0209.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0210.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0210.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0211.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0211.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0212.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0212.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0213.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0213.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0214.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0214.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0215.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0215.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0216.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0216.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0217.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0217.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0218.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0218.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0219.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0219.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0220.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0220.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0221.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0221.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0222.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0222.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0223.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0223.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0224.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0224.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0225.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0225.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0226.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0226.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0227.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0227.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0228.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0228.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0229.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0229.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0230.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0230.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0231.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0231.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0232.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0232.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0233.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0233.tif
2008.11.19 15:24 B T:\field_notes\rectangular_ notes\r0601\r0601-0234.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0234.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0235.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0235.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0236.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0236.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0237.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0237.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0238.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0238.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0239.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0239.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0240.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0240.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0241.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0241.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0242.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0242.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0243.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0243.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0244.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0244.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0245.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0245.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0246.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0246.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0247.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0247.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0248.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0248.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0249.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0249.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0250.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0250.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0251.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0251.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0307.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0307.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0308.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0308.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0309.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0309.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0310.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0310.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0311.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0311.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0312.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0312.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0313.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0313.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0314.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0314.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0315.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0315.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0316.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0316.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0317.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0317.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0318.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0318.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0319.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0319.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0320.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0320.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0321.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0321.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0322.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0322.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0323.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0323.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0324.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0324.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0325.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0325.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0326.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0326.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0327.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0327.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0328.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0328.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0329.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0329.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0330.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0330.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0331.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0331.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0332.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0332.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0333.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0333.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0334.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0334.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0335.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0335.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0336.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0336.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0337.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0337.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0338.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0338.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0339.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0339.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0340.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0340.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0341.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0341.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0342.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0342.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0343.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0343.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0344.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0344.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0345.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0345.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0346.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0346.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0347.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0347.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0348.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0348.tif
2008.11.19 15:25 B T:\field_notes\rectangular_ notes\r0601\r0601-0349.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0349.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0350.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0350.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0351.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0351.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0352.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0352.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0353.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0353.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0354.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0354.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0355.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0355.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0356.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0356.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0357.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0357.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0358.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0358.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0359.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0359.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0360.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0360.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0361.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0361.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0362.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0362.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0363.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0363.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0364.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0364.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0365.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0365.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0366.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0366.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0367.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0367.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0368.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0368.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0369.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0369.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0370.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0370.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0371.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0371.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0372.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0372.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0373.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0373.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0374.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0374.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0375.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0375.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0376.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0376.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0377.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0377.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0378.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0378.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0379.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0379.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0380.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0380.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0381.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0381.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0382.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0382.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0383.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0383.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0384.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0384.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0385.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0385.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0386.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0386.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0387.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0387.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0388.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0388.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0389.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0389.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0390.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0390.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0391.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0391.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0392.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0392.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0393.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0393.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0394.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0394.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0395.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0395.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0396.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0396.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0397.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0397.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0398.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0398.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0399.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0399.tif
2008.11.19 15:26 B T:\field_notes\rectangular_ notes\r0601\r0601-0400.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0400.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0401.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0401.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0402.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0402.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0403.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0403.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0404.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0404.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0405.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0405.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0406.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0406.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0407.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0407.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0408.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0408.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0409.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0409.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0410.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0410.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0411.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0411.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0412.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0412.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0413.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0413.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0414.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0414.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0415.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0415.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0416.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0416.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0417.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0417.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0418.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0418.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0419.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0419.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0420.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0420.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0421.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0421.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0422.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0422.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0423.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0423.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0424.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0424.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0425.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0425.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0426.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0426.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0427.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0427.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0428.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0428.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0429.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0429.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0430.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0430.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0431.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0431.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0432.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0432.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0433.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0433.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0434.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0434.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0435.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0435.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0436.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0436.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0437.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0437.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0438.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0438.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0439.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0439.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0440.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0440.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0441.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0441.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0442.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0442.tif
2008.11.19 15:27 B T:\field_notes\rectangular_ notes\r0601\r0601-0443.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0443.tif
2008.11.19 15:28 B T:\field_notes\rectangular_ notes\r0601\r0601-0444.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0601-0444.tif
```