

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

R602

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF THE WEST BOUNDARY

OF SECTION 18,

A PORTION OF THE SUBDIVISIONAL LINES

AND

THE SURVEY OF THE SUBDIVISION OF A PORTION OF SECTION 18,

TOWNSHIP 19 SOUTH, RANGE 12 EAST

Of the Salt Lake Meridian,

In the State of Utah

EXECUTED BY

Craig P. Sylvester Supervisory Cadastral Surveyor

Under special instructions dated January 26, 1979, approved January 29, 1979,
and Supplemental Special Instructions dated December 12, 1979, and approved
December 14, 1979

_____, which provided for the surveys included under U.S. Survey/Group
Number 588, and assignment instructions dated September 14, 1979
and January 25, 1980

Survey commenced October 29, 1979

Survey completed April 24, 1980

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

R602

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF THE WEST BOUNDARY

OF SECTION 18,

A PORTION OF THE SUBDIVISIONAL LINES

AND

THE SURVEY OF THE SUBDIVISION OF A PORTION OF SECTION 18,

TOWNSHIP 19 SOUTH, RANGE 12 EAST

Of the Salt Lake Meridian,

In the State of Utah

EXECUTED BY

Craig P. Sylvester Supervisory Cadastral Surveyor

Under special instructions dated January 26, 1979, approved January 29, 1979,
and Supplemental Special Instructions dated December 12, 1979, and approved
December 14, 1979

_____, which provided for the surveys included under U.S. Survey/Group
Number 588, and assignment instructions dated September 14, 1979
and January 25, 1980

Survey commenced October 29, 1979

Survey completed April 24, 1980

INDEX DIAGRAM

Township 19 South, Range 12 East

6	5	4	3	2	1
7	8	9	10	11	12
3 18	17	16	15	14	13
3					
19	20	21	22	23	24
29	28	27	26	25	
31	32	33	34	35	36

Subdivision of Section 18 - Page 4

Township 19 South, Range 12 East, Salt Lake Meridian, Utah

CHAINS

The east and north boundaries of Section 18 were surveyed by J.C. Clark in 1929. The south boundary of Section 18 was surveyed by A.D. Ferron in 1880 and resurveyed by J.C. Clark in 1929. The west boundary of T. 19 S., R. 12 E., was surveyed by H.D. Heist and W.A. Stumm in 1910.

The following field notes are those of a dependent resurvey of the west boundary of Section 18, a portion of the subdivisional lines, and the subdivision of a portion of Section 18, Township 19 South, Range 12 East, Salt Lake Meridian, Utah.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and Special Instructions for Group 588, Utah, dated January 26, 1979, and Supplemental Special Instructions, dated December 12, 1979.

The direction of the lines of this survey were determined by reference to true meridians established on line by hour angle observations on Polaris. They were carried forward by sustained angulation, being supplemented by numerous other observations on Polaris taken throughout the progress of the survey.

Before restoring lost corners, the lines of the original survey were retraced and a diligent search made for any evidence of the original corners. The rules of proportionate measurement were applied to ascertain the position of the lost corner after every reasonable possibility of finding direct evidence of the corner had been exhausted.

The geographic position of the southeast corner of Section 18, as determined by ties to U.S.G.S. triangulation station "Reef" located in sec. 18, is as follows:

Latitude $39^{\circ} 09' 44.6''$ N. Longitude $110^{\circ} 36' 15.5''$ W.

The magnetic declination was read at a number of stations and the average of the several readings was found to be $15^{\circ} 30'$ E.

Dependent Resurvey of a Portion of the West Boundary,
T. 19 S., R. 12 E., Salt Lake Meridian, Utah

(Restoring the Survey Executed by H.D. Heist and
W.A. Stumm in 1910)

Beginning at the cor. of secs. 13, 18, 19, and 24, monumented with an iron post, 3 ins. diam., extending 12 ins. above ground, with brass cap mkd. as described in the official record of the 1910 survey of the E. bdy. of T. 19 S., R. 11 E.

N. $0^{\circ} 29'$ E., bet. secs. 13 and 18.

Over broken and ledgy desert land, draining SW.

19.955 Point for the S $1/16$ sec. cor. of secs. 13 and 18.

Dependent Resurvey of a Portion of the West Boundary,
T. 19 S., R. 12 E., Salt Lake Meridian, Utah

CHAINS	
	<p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.</p> <p style="text-align: center;">T 19 S R 11 E R 12 E S 1/16</p> <p style="text-align: center;">S 13 S 18</p> <p style="text-align: center;">1979</p> <p>Asc. over broken and ledgy SW slope.</p>
39.91	<p>Point for the ¼ sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 5 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 19 S R 11 E R 12 E</p> <p style="text-align: center;">¼ S 13 S 18 </p> <p style="text-align: center;">1979</p> <p>Asc. over broken and ledgy SW slope.</p>
58.40	Crest of rim, bears NW and SE; thence over mountain top.
59.865	<p>Point for the N 1/16 sec. cor. of secs. 13 and 18.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., on solid rock, over a cross (+), in a mound of stone, 5 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 19 S R 11 E R 12 E N 1/16</p> <p style="text-align: center;">S 13 S 18</p> <p style="text-align: center;">1980</p>
62.50	Graded dirt road, bears S. 54½° E. and N. 54½° W.
79.82	The cor. of secs. 7, 12, 13, and 18, monumented with an iron post, 3 ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the official record of the 1910 survey of the E. bdy. of T. 19 S., R. 11 E.
Dependent Resurvey of a Portion of the Subdivisional Lines, T. 19 S., R. 12 E., Salt Lake Meridian, Utah	
(Restoring the Survey Executed by A.D. Ferron in 1880 and Resurvey by J.C. Clark in 1929)	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 19 S., R. 12 E., Salt Lake Meridian, Utah

CHAINS		
20.03	<p>From the $\frac{1}{4}$ sec. cor. of secs. 18 and 19, monumented with an iron post, 1 in. diam., extending 12 ins. above ground, with brass cap mkd. as described in the official record of the 1929 survey.</p> <p>S. $89^{\circ} 42'$ W., bet. secs. 18 and 19.</p> <p>Over broken and ledgy desert land, draining S.</p> <p>Point for the W $\frac{1}{16}$ sec. cor. of secs. 13 and 18.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 19 S R 12 E</p> <p style="text-align: center;">W $\frac{1}{16}$ $\frac{S 18}{S 19}$</p> <p style="text-align: center;">1979</p> <p>Continue along broken S slope.</p>	
56.73	<p>The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., heretofore described.</p> <hr/> <p>(Restoring the Survey Executed by J.C. Clark in 1929)</p> <p>From the $\frac{1}{4}$ sec. cor. of secs. 7 and 18, determined by a mound of stone and at record course and distance from an original bearing tree. The original corner and one bearing tree have been destroyed by road work.</p> <p>At the corner point</p> <p>Set an iron post, 36 ins. long, 1 in. diam., 28 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 19 S R 12 E</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S 7}{S 18}$</p> <p style="text-align: center;">1979</p> <p>from which an original bearing tree</p> <p style="text-align: center;">A pine limb, 12 ins. diam., bears N. $12^{\circ} 15'$ W., 45 lks. dist., mkd. S7 BT.</p> <p>Cor. is located on N edge of dirt road.</p> <p>S. $89^{\circ} 42'$ W., bet. secs. 7 and 18.</p> <p>Over mountain land, through juniper and pinon trees.</p>	
19.96	<p>Point for the W $\frac{1}{16}$ sec. cor. of secs. 7 and 18.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 19 S., R. 12 E., Salt Lake Meridian, Utah

CHAINS		
	<p style="text-align: center;">T 19 S R 12 E</p> <p style="text-align: center;">W 1/16 $\frac{S 7}{S 18}$</p> <p style="text-align: center;">1980</p>	
39.92	<p>Set a juniper post alongside the corner.</p> <p>Point for the 80 1/16 sec. cor. of secs. 7 and 18.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p>	
	<p style="text-align: center;">T 19 S R 12 E</p> <p style="text-align: center;">1/16 $\frac{S 7}{S 18}$ 80</p> <p style="text-align: center;">1980</p>	
51.30	<p>Continue over mountain top.</p> <p>Huff Hollow, drains NW.</p>	
55.96	<p>The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., heretofore described.</p>	
<p>Subdivision of a Portion of Section 18, T. 19 S., R. 12 E., Salt Lake Meridian, Utah</p>		
19.98	<p>From the ¼ sec. cor. of secs. 18 and 19.</p> <p>N. 0° 04' W., on the N and S center line of sec. 18.</p> <p>Over broken and ledgy land; asc. over general S slope.</p> <p>Point for the center - south 1/16 sec. cor. of sec. 18.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p>	
29.97	<p style="text-align: center;">T 19 S R 12 E</p> <p style="text-align: center;">C</p> <p style="text-align: center;">S 1/16 S 18</p> <p style="text-align: center;">C</p> <p style="text-align: center;">1979</p> <p>Point for the center - north - south 1/64 sec. cor. of sec. 18.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>	

Subdivision of a Portion of Section 18,
T. 19 S., R. 12 E., Salt Lake Meridian, Utah

CHAINS	
	<div style="text-align: center;"> <p>C N-S 1/64 S 18 C 1979</p> </div> <p>Cor. is located on steep S slope of small spur.</p>
39.96	<p>True point for the center 1/4 sec. cor. of sec. 18, at intersection with E and W center line, falls on inaccessible ledges and cannot be monumented.</p>
43.21	<p>Point selected for the witness cor. to the center 1/4 sec. cor. of sec. 18.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p>
	<div style="text-align: center;"> <p>W C T 19 S R 12 E C 1/4 S 18 ↓ 1979</p> </div>
59.89	<p>Point for the center - north 1/16 sec. cor. of sec. 18.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>
	<div style="text-align: center;"> <p>T 19 S R 12 E C N 1/16 S 18 C 1980</p> </div>
79.82	<p>The 1/4 sec. cor. of secs. 7 and 18.</p>
	<p>From the true point for the 1/4 sec. cor. of secs. 17 and 18, from which its witness cor. bears S. 0° 03' E., 2.50 chs. dist., monumented with an iron post, 1 in. diam., firmly set in a collar of stone, with brass cap mkd. as described in the official record of the 1929 survey.</p>
	<p>S. 89° 39' W., on the E and W center line of sec. 18.</p> <p>Over broken and ledgy land; asc. over general E slope.</p>
39.95	<p>True point for the center 1/4 sec. cor. of sec. 18.</p>
49.95	<p>Point for the center - east - west 1/64 sec. cor. of sec. 18.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>

Subdivision of a Portion of Section 18,
T. 19 S., R. 12 E., Salt Lake Meridian, Utah

CHAINS		
	<p style="text-align: center;">E-W 1/64 C ————— C S 18 1979</p>	
59.95	<p>Point for the center - west 1/16 sec. cor. of sec. 18.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p>	
	<p style="text-align: center;">T 19 S R 12 E W 1/16 C ————— C S 18 1979</p>	
69.95	<p>Point for the center - west - west 1/64 sec. cor. of sec. 18.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p>	
	<p style="text-align: center;">T 19 S R 12 E W-W 1/64 C ————— C S 18 1980</p>	
79.95	<p>Point for the center 80 1/16 sec. cor. of sec. 18.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p>	
	<p style="text-align: center;">T 19 S R 12 E 1/16 C — 80 — C S 18 1980</p>	
96.31	<p>The ¼ sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp., heretofore described.</p>	
	<p>From the W 1/16 sec. cor. of secs. 18 and 19.</p> <p>N. 0° 02' W., on the N and S center line of the SW¼ of sec. 18.</p> <p>Over broken land; asc. over general S slope of reef.</p>	
19.975	<p>Point for the south - west 1/16 sec. cor. of sec. 18, at intersection with the E and W center line of the SW¼.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p>	

Subdivision of a Portion of Section 18,
T. 19 S., R. 12 E., Salt Lake Meridian, Utah

CHAINS		
	<p>T 19 S R 12 E</p> <p>SW 1/16 S 18</p> <p>1979</p>	
29.96	<p>Point for the center - north SW 1/64 sec. cor. of sec. 18.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p>	
	<p>S 18</p> <p>C-N-SW</p> <p>1/64</p> <p>1979</p>	
39.945	<p>The center - west 1/16 sec. cor. of sec. 18.</p>	
	<p>From the center - south 1/16 sec. cor. of sec. 18.</p> <p>S. 89° 41' W., on the E and W center line of the SW¼ of sec. 18.</p> <p>Over broken and ledgy S slope of reef.</p>	
10.005	<p>Point for the center - east SW 1/64 sec. cor. of sec. 18.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p>	
	<p>S 18</p> <p>C-E-SW</p> <p>1/64</p> <p>1979</p>	
20.01	<p>The south - west 1/16 sec. cor. of sec. 18.</p>	
56.54	<p>The S 1/16 sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp., heretofore described.</p>	
	<p>From the center - east SW 1/64 sec. cor. of sec. 18.</p> <p>N. 0° 03' W., on the N and S center line of the NE¼ of the SW¼ of sec. 18.</p> <p>Over broken and ledgy S slope of reef.</p>	
9.985	<p>True point for the northeast - southwest 1/64 sec. cor. of sec. 18, at intersection with the E and W center line of the NE¼ of the SW¼, falls on ledges and cannot be monumented.</p>	
19.97	<p>The center - east - west 1/64 sec. cor. of sec. 18.</p>	
	<p>From the center - north - south 1/64 sec. cor. of sec. 18.</p> <p>S. 89° 40' W., on the E and W center line of the NE¼ of the SW¼ of sec. 18.</p> <p>Over broken and ledgy SE slope of reef.</p>	

Subdivision of a Portion of Section 18,
T. 19 S.; R. 12 E., Salt Lake Meridian, Utah

CHAINS		
10.00	True point for the northeast - southwest 1/64 sec. cor. of sec. 18.	
12.25	Point selected for the witness cor. to the northeast - southwest 1/64 sec. cor. of sec. 18.	
	Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.	
	W C S 18 NE - SW → 1/64 1979	
20.00	The center - north - southwest 1/64 sec. cor. of sec. 18.	
	From the center - west 1/16 sec. cor. of sec. 18.	
	N. 0° 01' W., on the N and S center line of the NW¼ of sec. 18.	
	Asc. over broken and ledgy S slope of reef.	
6.60	Top ascent on rim, bears irregularly E and W; thence over bench covered with juniper and pinon.	
9.30	Dirt road, bears E and W.	
9.965	Point for the center - south - northwest 1/64 sec. cor. of sec. 18.	
	Set an iron post, 28 ins. long, 2½ ins. diam., on solid sandstone, over a cross (+), in a mound of stone, 5 ft. base, to top of brass cap, mkd.	
	T 19 S R 12 E C-S-NW 1/64 S 18 1980	
	from which	
	The SW cor. of a concrete building, Bell Telephone U-0140842, bears N. 17° 41' E., 1.08 chs. dist.	
	The NW cor. of fence around EPA weather station bears S. 10° 57' E., 1.52 chs. dist.	
	U.S.G.S. triangulation station "Reef", bears S. 26° 26' 45" E., 1.29 chs. dist.	
19.93	Point for the northwest 1/16 sec. cor. of sec. 18, at intersection with the E and W center line of the NW¼.	
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.	
	T 19 S R 12 E NW 1/16 S 18 1980	

Subdivision of a Portion of Section 18,
T. 19 S., R. 12 E., Salt Lake Meridian, Utah

CHAINS	
39.87	<p>Raise a mound of stone, 2 ft. base, 2 ft. high, N of cor. The W 1/16 sec. cor. of secs. 7 and 18.</p>
8.20	<p>Top of rim, bears irregularly; E and W; thence over bench.</p>
9.975	<p>Point for the south - north 80 1/64 sec. cor. of sec. 18. Not monumented.</p>
13.50	<p>Dirt road, bears S. 75° E. and N. 75° W.</p>
19.95	<p>Point for the north 80 1/16 sec. cor. of sec. 18, at intersection with the E and W center line of the NW¼.</p>
39.90	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T 19 S R 12 E 1/16</p>
	<p style="text-align: center;">N ————— 80 S 18 1980</p>
39.90	<p>The 80 1/16 sec. cor. of secs. 7 and 18.</p>
	<p>From the center - north 1/16 sec. cor. of sec. 18.</p>
	<p>S. 89° 40' W., on the E and W center line of the NW¼ of sec. 18.</p>
	<p>Asc. over broken and ledgy SE slope of reef.</p>
2.80	<p>Top of ascent on rim, bears irregularly NE and SW; thence over mountain bench.</p>
8.20	<p>Dirt road, bears NE and SW.</p>
19.98	<p>The northwest 1/16 sec. cor. of sec. 18.</p>
29.975	<p>Point for the center - west - northwest 1/64 sec. cor. of sec. 18. Not monumented.</p>
39.97	<p>The north 80 1/16 sec. cor. of sec. 18.</p>
52.50	<p>Dirt road, bears N. 55° W. and S. 55° E.</p>
56.17	<p>The N 1/16 sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp., heretofore described.</p>
	<p>From the center - west - west 1/64 sec. cor. of sec. 18.</p>
	<p>North, on the N and S center line of the SW¼ of the NW¼ of sec. 18.</p>
	<p>Asc. over broken and ledgy S slope of reef.</p>

Subdivision of a Portion of Section 18,
T. 19 S., R. 12 E., Salt Lake Meridian, Utah

CHAINS	
7.70	Top of rim, bears irregularly E and W; thence over bench.
9.97	Point for the southwest - northwest 1/64 sec. cor. of
	sec. 18, at intersection with the E and W center line of the SW $\frac{1}{4}$ of the NW $\frac{1}{4}$.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 5 ft. base, to top of brass cap, mkd.
	T 19 S R 12 E
	SW-NW 1/64
	S 18
	1980
	from which
	The NE cor. of fence around building, U-11685 and U-28029, bears S. 47° 12' E., 1.105 chs. dist.
	Antenna for Utah Highway Patrol, bears S. 61° 18' E., 2.90 chs. dist.
	The NW cor. of building, U-0142245 bears S. 65° 19' 20" E., 4.59 chs. dist.
11.20	Dirt road, bears N. 82° W. and S. 82° E.
19.94	Point for the center - west - northwest 1/64 sec. cor. of
	sec. 18. Not monumented.
	From the center - south - northwest 1/64 sec. cor. of sec. 18.
	S. 89° 40' W., along the E and W center line of the SW $\frac{1}{4}$ of the NW $\frac{1}{4}$ of sec. 18.
	Over mountain bench land.
5.00	Dirt road, bears N. 77° W. and S. 77° E.
10.00	The southwest - northwest 1/64 sec. cor. of sec. 18.
20.00	Point for the south - north 80 1/64 sec. cor. of sec. 18.
	Not monumented.
	General Description
	Section 18, T. 19 S., R. 12 E., is located about 20 miles SE of Cleveland, Utah. The section consists of mountainous desert land covered with juniper and pinon on the higher elevations. The south and east portions of the section consist of broken and ledgy face of a high reef, the NW portion of the section is high mountain bench land on Cedar Mountain. There is a dirt road through the NW portion of the section used mostly to service several radio towers and visit a BLM campground located along the rim of the reef. No permanent water was noted during the survey. The elevation varies from about 6200 to 7665 ft. above sea level. There is no permanent habitation within the section.

CERTIFICATE OF SURVEY

(I) ~~(W&X)~~ Craig P. Sylvester, Supervisory Cadastral Surveyor, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 26th day and Supplemental Special Instructions dated December 12, 1979 of January, 1979, (I) ~~(W&X)~~ have dependently resurveyed the west boundary of section 18, a portion of the subdivisional lines, and surveyed the subdivision of a portion of Section 18 of Township 19 South, Range 12 East,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), ~~(W&X)~~ and under (my) ~~(W&X)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

March 27, 1981

(Date)

Craig P. Sylvester
(Cadastral Surveyor)
Supervisory

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Denver, Colorado

The foregoing field notes of the dependent resurvey of the west boundary of Section 18, a portion of the subdivisional lines, and the survey of the subdivision of a portion of Section 18 of Township 19 South, Range 12 East, Salt Lake Meridian, Utah

executed by Craig P. Sylvester, Supervisory Cadastral Surveyor having been critically examined and found correct, are hereby approved.

MAR 26 1982

(Date)

James A. Helmer
ACTING (Chief, Cadastral Survey Examination and Approval Staff)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

(Date)

(Chief, Cadastral Survey Examination and Approval Staff)

INDEX DIAGRAM

Township 9 South, Range 25 East

6 54 54	5 39 53	4 29 38	3 20 28	2 13 20	1 4 12	4
7 52 51	8 37 49	9 28 37	10 19 27	11 11 19	12 4 11	4
18 48 48	17 35 47	16 26 34	15 18 26	14 10 17	13 3 10	3
19 46 46	20 33 45	21 24 33	22 16 24	23 9 16	24 2 8	2
30 43 42	29 32 41	28 23 31	27 15 22	26 7 14	25 2 6	2
31 39	32 30	33 21	34 13	35 5	36	

Mineral Surveys Nos. 5183 and 5184 - Page 55
 Allotments Nos. 267 and 268 - Page 56

Township 9 South, Range 25 East, Salt Lake Meridian, Utah

CHAINS

The north portion of the east boundary (Utah - Colorado State Boundary) was surveyed by R.J. Reeves in 1879. The south portion of the east boundary was surveyed by A.D. Wilson in 1885. The entire east boundary was retraced by A.R. Talamantes and H.D. Heist in 1904. The boundary between witness mile post 208 and mile post 211 was retraced by A.H. Adams in 1904-05. The boundary between mile post 206 and mile post 207 was retraced by W.J. Cunningham in 1936. The boundary between mile post 206 and witness mile post 208 was resurveyed by John M. Tufts in 1936. The west 1 mile of the south boundary was surveyed by D.G. Majors in 1883, and the east 5 miles surveyed and the west 1 mile resurveyed by A.R. Talamantes and H.D. Heist in 1904, and the entire south boundary resurveyed by G.B. Hatch in 1975. The west boundary was surveyed by A.R. Talamantes and H.D. Heist in 1904, and resurveyed concurrently under this same group and the record shows in the field notes of the resurvey of the east boundary of T. 9 S., R. 24 E. The north boundary was surveyed by A.R. Talamantes and H.D. Heist in 1904 and resurveyed by J.C. Clark in 1935. The subdivisional lines were surveyed by A.R. Talamantes and H.D. Heist in 1904.

The following field notes are those of a retracement of the Utah - Colorado State Boundary between mile post 207 and mile post 214, and a dependent resurvey of the subdivisional lines and a portion of allotment Nos. 267, 268 and 270, and a portion of Mineral Survey Nos. 5183 and 5184 of Township 9 South, Range 25 East, Salt Lake Meridian, Utah.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group 568, Utah, dated May 20, 1977.

The directions of the lines of this survey were determined by reference to true meridians established on line by hour angle observations on Polaris. They were carried forward by sustained angulation, being supplemented by numerous other observations on Polaris taken throughout the progress of the survey.

Measurements were determined by electronic means.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the southeast corner of the township as determined by ties to U.S.G.S. triangulation station "JEK 10 ET", established in 1966, is as follows:

Latitude $39^{\circ} 59' 07''$ N. Longitude $109^{\circ} 03' 21''$ W.

The magnetic declination was read at a number of stations throughout the township and the average of the several readings was found to be 15° E.


Retracement of the Utah and Colorado State Boundary,
Between the 207th and 214th Mile Posts, Along the
E. Bdy. of T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

Retracement of the Utah and Colorado State Boundary,
Between the 207th and 214th Mile Posts, Along the
E. Bdy. of T. 9 S., R. 25 E., Salt Lake Meridian, Utah

(Retracement of the Resurvey Executed
by John M. Tufts in 1936)

From mile post 207 on the Utah and Colorado State Boundary,
monumented with an iron post, 3 ins. diam., set in a mound
of stone, with brass cap mkd.



from which

A cedar, 18 ins. diam., bears N. 36° 30' E.,
36 lks. dist., mkd. 207 M COLO BT.

A cedar, 8 ins. diam., bears N. 76° 30' W.,
84 lks. dist., mkd. 207 M UTAH BT.

Mile post is located 10 lks. south of wash, draining
S. 65° W.


N. 0° 24' W., along the 208th mile of the Utah and
Colorado State Boundary.

Over broken land, through scattered juniper and pinon.

43.15 The witness 208th mile post, monumented with an sandstone,
26 x 12 x 8 ins., mkd. 208 WC on S, 1885 on N, U on W,
and C on E faces.

At the witness mile post point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins.
in the ground, and in a collar of stone, with brass cap
mkd.



Place mkd. stone in collar of stone by iron post.

(Retracement of the Retracement Executed by
A.H. Adams in 1904 - 05)

N. 0° 36' E., along the 209th and 210th miles of the
Utah and Colorado State Boundary.

Over broken land on top of high point

19.90 The closing cor. of secs. 24 and 25, T. 9 S., R. 25 E.,
S.L.M., Utah, hereinafter described.

Retracement of the Utah and Colorado State Boundary,
Between the 207th and 214th Mile Posts, Along the
E. Bdy. of T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
61.53	Cor. No. 2 of Jimmy Colorow allotment N. 267, No. 20, hereinafter described.
76.00	Gilsonite Draw, 10 ft. deep, 30 lks. wide, drains N. 10° W.; desc. along E side of wash.
85.10	Left bank of White River, bears E and W; thence over river and sandy river bottom.
90.00	Right bank of same river, bears E and W; asc over S slope.
94.20	Old road, bears E and W; asc. over steep and ledgy S slope.
99.69	The closing cor. of secs. 13 and 24, T. 9 S., R. 25 E., S.L.M., Utah, hereinafter described.
105.63	Point for the 209¼ mile post, at record distance; no remaining evidence of this mile post could be found.
113.02	<p>The 210+58.07 mile post and Astronomical Station, monumented with a sandstone, 16 x 12 x 3 ins., firmly set, mkd. with UT and illegible numbers on W face, COL on E face, other marks badly weathered.</p> <p>At the mile post point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">210M+58.07 UT COL AST STA 1977</p> <p>Place mkd. stone in mound.</p>
21.26	<p>N. 0° 12' E., along the 211th mile of the Utah and Colorado State Boundary.</p> <p>Over broken land on narrow top of ridge, which bears E and W.</p> <p>The 211th mile post, monumented with a sandstone, 20 x 6 x 6 ins., firmly set, mkd. UT on W, COL on E and 211M on S faces, also mound of stone.</p> <p>At the mile post point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">211M UT COL 1977</p> <p>Place mkd. stone in mound alongside the iron post.</p> <p>Mile post located on top of narrow ridge, which bears E and W.</p>

Retracement of the Utah and Colorado State Boundary,
Between the 207th and 214th Mile Posts, Along the
E. Bdy. of T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

(Retracement of the Retracement Executed by
A.R. Talamantes and H.D. Heist in 1904)

N. 0° 28' W., along the 212th mile of the Utah and
Colorado State Boundary.

Over broken land; desc. over N slope.

45.20 The closing cor. of secs. 12 and 13, T. 9 S., R. 25 E.,
S.L.M., Utah, hereinafter described.

68.40 Pipe line, bears N. 81° 30' E. and S. 81° 30' W.

79.91 The 212th mile post, monumented with a sandstone,
22 x 18 x 4 ins., firmly set and plainly mkd. COL 212M
on E face, marks on Utah side weathered away.

At the mile post point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

212M

UT | COL

1977

Bury mkd. stone alongside the iron post.

N. 0° 29' E., along the 213th mile of the Utah and
Colorado State Boundary.

Over rolling desert land, covered with shadscale; along
gentle W slope.

45.25 The closing cor. of secs. 1 and 12, T. 9 S., R. 25 E.,
S.L.M., Utah, hereinafter described.

80.37 The 213th mile post, monumented with a sandstone,
16 x 10 x 4 ins., firmly set and mkd. UT on the W face,
other marks obliterated, mound of stone, W of cor.

At the mile post point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

213M

UT | COL

1977

Bury mkd. stone alongside the iron post and rebuild
mound of stone, W of cor.

N. 0° 13' E., along the 214th mile of the Utah and
Colorado State Boundary.

Over broken desert land, draining NE; desc. over N
slope.

Retracement of the Utah and Colorado State Boundary,
Between the 207th and 214th Mile Posts, Along the
E. Bdy. of T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

- 43.23 The closing cor. of Tps. 8 and 9 S., R. 25 E., S.L.M., Utah, monumented with an iron post, 3 ins. diam., extending 10 ins. above ground, with brass cap mkd. as described in the official record of the 1935 resurvey.
- 80.45 The 214th mile post, monumented with a slate stone, 18 x 12 x 2 ins., firmly set and plainly mkd. COL 214M on the E face, Utah marks have flaked away.

At the mile post point

Set an iron post 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

214M
|
UT | COL
|
1977

Bury mkd. stone alongside the iron post, and raise a small mound of stone, W of cor.

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

(Restoring the Survey Executed by
A.R. Talamantes and H.D. Heist in 1904)

From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., in a mound of stone, with brass cap mkd. as described in the official record of the 1975 resurvey of the N. bdy. of T. 10 S., R. 25 E.

N. 0° 15' E., bet. secs. 35 and 36.

Over broken mountain land, covered with juniper and pinon; desc. over gentle N slope.

- 40.21 The ¼ sec. cor. of secs. 35 and 36, monumented with a limestone, 24 x 12 x 4 ins., firmly set, 8 ins. in the ground, marks have been obliterated, with small mound of stone, W of cor.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.

T 9 S R 25 E

|
¼
|
S 35 | S 36
|
1977

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

39.72 Bury the mkd. stone alongside the iron post.
Cor. is located about 1.00 ch. W of wash in canyon.

N. 0° 51' W., beginning new measurement.
Desc. along W side of wash in canyon bottom.
The cor. of secs. 25, 26, 35, and 36, monumented with a sandstone, 24 x 7 x 4 ins., firmly set 6 ins. in the ground and plainly mkd. 1 notch on S and E edges.
from which
 A cedar, 12 ins. diam., bears N. 73° E., 56 lks. dist., mkd. T9S R25E S25 BT. (Record, 52 lks.)
 A cedar, 10 ins. diam., bears S. 46° W., 27 lks. dist., mkd. T9S R25E S35 BT. (Record, 31 lks.)
No other bearing trees identified.
At the corner point
Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 9 S R 25 E

S 26	S 25
S 35	S 36

1977

Bury the mkd. stone alongside the iron post.

20.45 N. 89° 57' E., bet. secs. 25 and 36.
Over broken mountain land, through scattered juniper and pinon; asc. over W slope.
Point for the W 1/16 sec. cor. of secs. 25 and 36.
Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.

T 9 S R 25 E

W 1/16	S 25
	S 36

1977

Cor. is located in bottom of draw, on bend; asc. over steep and ledgy W slope.

34.17 Intersect the E. bdy. of the Tp.
Point for the closing cor. of secs. 25 and 36.

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 9 S
R 25 E
C S 25 |
C S 36 |

1977

From this closing cor., the 206th mile post on the Utah and Colorado State Boundary, bears S. 0° 24' E., 62.48 chs. dist., monumented with an iron post, 3 ins. diam., set in a mound of stone, with brass cap mkd.

206M
|
UTAH | COLO
|
1936

From this same closing cor., the 207th mile post bears N. 0° 24' W., 17.52 chs. dist., heretofore described.

35.30 The original closing cor. of secs. 25 and 36, monumented with a limestone, 18 x 12 x 3 ins., above ground, mkd. C on E, U CC on W faces, 1 notch on S and 5 notches on N edges.

from which

A pinon, 12 ins. diam., bears S. 77° W., 69 lks. dist., mkd. T9S R25E BT.

A pinon, 10 ins. diam., bears N. 87° W., 28 lks. dist., mkd. T9S R25E BT.

This cor. will now act as an amended monument and the letters "AM" were added to the original marks.

From the cor. of secs. 25, 26, 35, and 36.

N. 0° 13' E., bet. secs. 25 and 26.

Over broken mountain land; desc. over steep NW slope.

40.07 Point for the ¼ sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 9 S R 25 E

¼
|
S 26 | S 25
|


1977

77.14 Point selected for the witness cor. to the cor. of secs. 23, 24, 25, and 26.

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.



1977

Set a cottonwood post, 6 ins. diam., 4 ft. high, alongside the witness cor.; thence through willows and flood area.

78.53

Intersect line 7-8 Frank Colorado Allotment No. 268 No. 21.

From this intersection, Cor. No. 7, bears S. 77° 03' W., 62.89 chs. dist., monumented with a sandstone, 16 x 10 x 3 ins., set in a mound of stone, mkd. FC 7 on E face.

From this same intersection, Cor. No. 8, bears N. 77° 03' E., 25.64 chs. dist., monumented with a shale sandstone, 20 x 12 x 6 ins., plainly mkd. COL 8, also small mound of stone NW of cor.

80.14

Point for the cor. of secs. 23, 24, 25, and 26, at proportionate distance, falls in area subject to floods from White River and cannot be perpetuated. There is no remaining evidence of the original corner.

N. 89° 14' E., bet. secs. 24 and 25.

Over bottom land in White River Canyon, through dense willows and greasewood.

7.41

Intersect line 7-8 Frank Colorado Allotment No. 268 No. 21.

From this intersection, Cor. No. 7, bears S. 77° 03' W., 70.50 chs. dist., heretofore described.


From this same intersection, Cor. No. 8, bears N. 77° 03' E., 18.03 chs. dist., heretofore described.

33.65

The closing cor. of secs. 24 and 25, on the E. bdy. of the Tp., monumented with a sandstone, 24 x 16 x 6 ins., firmly set 8 ins. in the ground and plainly mkd. CC U on W, and COL on E faces, 2 notches on S and 4 notches on N edges.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.



1977

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
	<p>Bury the mkd. stone upside down, alongside the iron post.</p> <p>From this closing cor., the 208th mile post witness cor., on the Utah and Colorado State Boundary, bears S. 0° 36' W., 19.90 chs. dist., heretofore described.</p> <p>From this same closing cor., the 210+58.07 mile post on the Utah and Colorado State Boundary, bears N. 0° 36' E., 93.12 chs. dist., heretofore described.</p>
	<p>From the true point for the cor. of secs. 23, 24, 25, and 26.</p> <p>N. 0° 01' E., bet. secs. 23 and 24.</p> <p>Over bottom land in White River Canyon, through dense willows.</p>
3.50	<p>Left bank White River, bears N. 15° E. and S. 15° W.; thence across river.</p>
8.20	<p>Right bank of the same river, bears N. 15° E and S. 15° W.</p>
40.07	<p>The ¼ sec. cor. of secs. 23 and 24, monumented with a mound of sandstone and oil shale, no marks could be identified. This position is accepted as the best available evidence of the original corner position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 9 S R 25 E</p> <p style="text-align: center;"> $\frac{1}{4}$ S 23 S 24 </p> <p style="text-align: center;">1977</p>
	<p>Raise a mound of stone, 2 ft. base, 2 ft. high, W of cor.</p> <p>Cor. is located about 25 lks. E of old trail road.</p> <p style="text-align: center;">_____</p> <p>N. 0° 03' E., beginning new measurement.</p> <p>Continue along bank on W side of canyon.</p>
6.00	<p>Old trail road, bears NE and SW.</p>
40.07	<p>The cor. of secs. 13, 14, 23, and 24, monumented with a mound of stone, 1 notch identified on broken piece of sandstone.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

T 9 S R 25 E

S 14 | S 13
S 23 | S 24

1977

Cor. is located on steep S slope about 1.50 chs. below top of spur, which slopes W.

N. 89° 48' E., bet. secs. 13 and 24.

Over broken mountain land; asc. along ledgy and inaccessible S slope.

34.42

Point for the closing cor. of secs. 13 and 24, on the E. bdy. of the Tp., at proportionate distance between the 208th mile post witness cor. and mile post 210+58.07; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 9 S
R 25 E
C S 13 |
C S 24 |

1977

Raise a small mound of stone W of cor.

From this closing cor., the 208th mile post witness cor. bears S. 0° 36' W., 99.69 chs. dist., heretofore described.

From this same closing cor., the 210+58.07 mile post bears N. 0° 36' E., 13.33 chs. dist., heretofore described.

From the cor. of secs. 13, 14, 23, and 24.

N. 1° 01' W., bet. secs. 13 and 14.

Over broken mountain land; asc. over steep S slope.

39.97

Point for the ¼ sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.

T 9 S R 25 E

¼
|
S 14 | S 13
|

1977

Asc. along E slope of spur.

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS													
79.94	<p>The cor. of secs. 11, 12, 13, and 14, monumented with a sandstone, 18 x 14 x 6 ins., in a scattered mound of stone, only one notch identified.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 9 S R 25 E</p> <p style="text-align: center;"> <table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 0 5px;">S 11</td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">S 12</td> </tr> <tr> <td style="padding: 0 5px;">S 14</td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">S 13</td> </tr> </table> </p> <p style="text-align: center;">1977</p> <p>Bury the mkd. stone alongside the iron post.</p> <p>Cor. is located 94 lks. N and 30 lks, W of draw, draining SW.</p>	S 11		S 12	S 14		S 13						
S 11		S 12											
S 14		S 13											
	<p>East, bet. secs. 12 and 13.</p> <p>Over broken land, covered with shadscale; desc. over E slope.</p>												
35.57	<p>The original closing cor. of secs. 12 and 13, monumented with a sandstone, 18 x 9 x 4 ins., firmly set 8 ins. in the ground and mkd. CC on W face, 2 notches on N and 4 notches on S edges. This cor. will now act as an amended monument and the letters "AM" were added to the marks.</p>												
35.66	<p>Intersect the E. bdy. of the Tp.</p> <p>Point for the closing cor. of secs. 12 and 13.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr> <td></td> <td style="padding: 0 5px;">T 9 S</td> <td></td> </tr> <tr> <td></td> <td style="padding: 0 5px;">R 25 E</td> <td></td> </tr> <tr> <td style="padding: 0 5px;">C</td> <td style="padding: 0 5px;">S 12</td> <td style="padding: 0 5px;"> </td> </tr> <tr> <td style="padding: 0 5px;">C</td> <td style="padding: 0 5px;">S 13</td> <td style="padding: 0 5px;"> </td> </tr> </table> </p> <p style="text-align: center;">1977</p> <p>From this closing cor., the 211th mile post, on the Utah and Colorado State Boundary, bears S. 0° 28' E., 45.20 chs. dist., heretofore described.</p> <p>From this same closing cor., the 212th mile post, on the Utah and Colorado State Boundary, bears N. 0° 28' W., 34.71 chs. dist., heretofore described.</p>		T 9 S			R 25 E		C	S 12		C	S 13	
	T 9 S												
	R 25 E												
C	S 12												
C	S 13												
	<p>From the cor. of secs. 11, 12, 13, and 14.</p> <p>N. 0° 39' E., bet. secs. 11 and 12.</p>												
12.30	<p>Over broken land, covered with scattered shadscale; asc. SE slope.</p> <p>Pipeline, bears S. 72° 45' W. and N. 72° 45' E.</p>												

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

39.89

The ¼ sec. cor. of secs. 11 and 12, monumented with a sandstone, 14 x 10 x 4 ins., firmly set 6 ins. in the ground, with weathered marks with mound of stone, W of cor.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 9 S R 25 E

¼
S 11 | S 12

1977

Bury the mkd. stone alongside the iron post, and raise a small mound of stone W of cor.

N. 0° 08' E., beginning new measurement.

Desc. along general W slope.

40.47

The cor. of secs. 1, 2, 11, and 12, determined by old mound of stone, no marks identified, with old lath and survey stakes around corner. This position is accepted as the best available evidence of the original corner.

At the corner point (center of mound)

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.

T 9 S R 25 E

S 2 | S 1
S 11 | S 12

1977

S. 89° 22' E., bet. secs. 1 and 12.

Over rolling desert land, covered with shadscale.

35.06

The original closing cor. of secs. 1 and 12, monumented with a sandstone, 14 x 8 x 2 ins., mkd. CC U on W and COL on E face, part of stone with notches has been broken off. This cor. will now act as an amended monument and the letters "AM" were added to the marks.

35.22

Intersect the E. bdy. of the Tp.

Point for the closing cor. of secs. 1 and 12.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS		
39.96	<p style="text-align: center;">T 9 S R 25 E C — S 1 C — S 12 1977</p> <p>From this closing cor., the 212th mile post on the Utah and Colorado State Boundary, bears S. 0° 29' W., 45.25 chs. dist., heretofore described.</p> <p>From this same closing cor., the 213th mile post on the Utah and Colorado State Boundary, bears N. 0° 29' E., 35.12 chs. dist., heretofore described.</p> <hr/> <p>From the cor. of secs. 1, 2, 11, and 12. N. 0° 01' W., bet. secs. 1 and 2.</p> <p>Over rolling desert land, covered with shadscale; asc. gentle S slope.</p> <p>The ¼ sec. cor. of secs. 1 and 2, monumented with a sandstone, 16 x 8 x 6 ins., firmly set, 6 ins. in the ground, marks have been obliterated, with mound of stone, W of cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 9 S R 25 E ¼ S 2 S 1 1977</p> <p>Bury the cor. stone alongside the iron post.</p> <hr/> <p>N. 0° 56' E., beginning new measurement.</p> <p>Desc. along E slope of low spur.</p>	
37.96	<p>The cor. of secs. 1 and 2, T. 9 S., R. 25 E., monumented with an iron post, 2 ins. diam., extending 12 ins. above ground, with brass cap mkd. as described in the official record of the 1935 resurvey.</p> <hr/> <p>From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the official record of the 1975 resurvey of the N. bdy. of T. 10 S., R. 25 E.</p> <p>N. 0° 07' E., bet. secs. 34 and 35.</p>	

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS		
11.60	<p>Over broken mountain land, through scattered juniper and pinon; desc. along E slope of spur.</p> <p>Wash in Cripple Horse Canyon, drains N. 60° W.; thence along W slope in canyon.</p>	
39.97	<p>Point for the ¼ sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 9 S R 25 E</p> <p>¼</p> <p>S 34 S 35</p> <p>1977</p> </div> <p>Asc. over steep SW slope.</p>	
79.94	<p>The cor. of secs. 26, 27, 34, and 35, monumented with a limestone, 20 x 16 x 3 ins., firmly set 8 ins. in the ground and plainly mkd. 1 notch on S and 2 notches on E edges, with old mound of stone, W of cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 9 S R 25 E</p> <p>S 27 S 26</p> <p>S 34 S 35</p> <p>1977</p> </div> <p>Place mkd. stone in collar of stone, alongside the iron post.</p>	
39.71	<p>From the cor. of secs. 25, 26, 35, and 36.</p> <p>N. 89° 57' W., bet. secs. 26 and 35.</p> <p>Over broken mountain land, through scattered juniper and pinon; desc. over steep NW slope.</p> <p>The ¼ sec. cor. of secs. 26 and 35, monumented with a limestone, 15 x 10 x 3 ins., firmly set, marks have been obliterated, with mound of stone, N of cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p>	

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS		
39.79	<p style="text-align: center;">T 9 S R 25 E</p> <p style="text-align: center;"> $\frac{1}{4}$ $\frac{S\ 26}{S\ 35}$ </p> <p style="text-align: center;">1977</p> <p>Place the cor. stone in mound alongside the iron post. Cor. is located 60 lks. E of draw, draining N.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 89° 59' W., beginning new measurement. Desc. over W slope.</p> <p>The cor. of secs. 26, 27, 34, and 35.</p>	
39.87	<p>N. 0° 14' W., bet. secs. 26 and 27.</p> <p>Over broken mountain land, through scattered juniper and pinon; along steep E slope.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 26 and 27, monumented with a sandstone, 18 x 10 x 6 ins., firmly set 8 ins. in the ground and plainly mkd. $\frac{1}{4}$ on W face, with mound of stone, W of corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>	
31.50 33.80 40.66	<p style="text-align: center;">T 9 S R 25 E</p> <p style="text-align: center;"> $\frac{1}{4}$ S 27 S 26 </p> <p style="text-align: center;">1977</p> <p>Bury the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 05' E., beginning new measurement. Desc. along W slope.</p> <p>Left bank of White River, bears N. 70° W. and S. 70° E., thence over river.</p> <p>Right bank of same river, bears N. 70° W. and S. 70° E.</p> <p>The cor. of secs. 22, 23, 26, and 27, monumented with a sandstone, 14 x 8 x 6 ins., firmly set 6 ins. in the ground and plainly mkd. 2 notches on S and E edges.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

T 9 S R 25 E

S 22	S 23
S 27	S 26

1977

Bury the mkd. stone alongside the iron post.

From the true point for the cor. of secs. 23, 24, 25,
and 26.

N. 89° 41' W., bet. secs. 23 and 26.

Over river bottom land, through dense willows and
scattered cottonwood trees.

- 3.40 Left bank of White River, bears N. 48° E. and S. 48° W.;
thence over river.
- 5.30 Right bank of same river, bears N. 48° E. and S. 48° W.
- 12.60 Right bank of same river, bears N. 46° W. and S. 46° E.
- 15.50 Left bank of same river, bears N. 46° W. and S. 46° E.
- 34.70 Left bank of same river, bears N. 61° E. and S. 61° W.
- 37.60 Right bank of same river, bears N. 61° E. and S. 61° W.
- 39.92 Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 26, at pro-
portionate distance; there is no remaining evidence of
the original corner.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 9 S R 25 E

$\frac{1}{4}$	S 23
	S 26

1977

Set a cedar post, 6 ins. diam., 5 ft. high, alongside
the corner.

- 79.84 The cor. of secs. 22, 23, 26, and 27.

North, bet. secs. 22 and 23.

Over river bottom, through willows and cottonwood trees.

- 2.00 Bulldozed road, bears E and W; asc. over steep S slope
and ledges facing S.
- 30.30 Gilsonite vein and old workings.
- 39.62 The $\frac{1}{4}$ sec. cor. of secs. 22 and 23, monumented with a
sandstone, 16 x 14 x 2 ins., in a mound of stone, part of
 $\frac{1}{4}$ still legible.

At the corner point

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.

T 9 S R 25 E

½
|
S 22 | S 23
|

1977

Place the mkd. stone in mound alongside the iron post.

From this cor., U.S.G.S. triangulation station "JEK-10" bears S. 10° 36' 20" E., 18.125 chs. dist.

N. 0° 01' E., beginning new measurement.

Over top of small mesa.

40.04

The cor. of secs. 14, 15, 22, and 23, monumented with a sandstone, 16 x 8 x 8 ins., firmly set 6 ins. in the ground and plainly mkd. 2 notches on E and 3 notches on S edges, with large mound of stone, W of cor.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.

T 9 S R 25 E

S 15 | S 14
S 22 | S 23

1977

Place the mkd. stone in mound alongside the iron post.

From the cor. of secs. 13, 14, 23, and 24.

S. 89° 56' W., bet. secs. 14 and 23.

Over broken and ledgy land; along steep S slope.

39.57

The ¼ sec. cor. of secs. 14 and 23, monumented with a sandstone, 18 x 10 x 2 ins., firmly set 8 ins. in the ground and plainly mkd. ¼ on N face, old mining claim mound of stone bears N, 4 lks. dist.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 9 S R 25 E

¼ S 14
 S 23

1977

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS		
40.31	<p>Bury the mkd. stone alongside the iron post.</p> <p>Cor. is located 30 lks. E of draw, draining N. 20° E.</p> <p>N. 89° 54' W., beginning new measurement.</p> <p>Desc. over steep W slope.</p> <p>The cor. of secs. 14, 15, 22, and 23.</p>	
38.95	<p>N. 0° 29' E., bet. secs. 14 and 15.</p> <p>Over broken bench, covered with shadscale.</p> <p>The ¼ sec. cor. of secs. 14 and 15, monumented with a sandstone, 8 x 6 x 6 ins., firmly set 4 ins. in the ground with part of ¼ still on stone, other part of stone has been broken off, with scattered mound of stone around cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 9 S R 25 E</p> <p>¼</p> <p>S 15 S 14</p> <p>1977</p> </div> <p>Place the mkd. stone in collar of stone, alongside the iron post.</p> <p>Cor. is located 150 lks. S of small wash, draining S. 70° E.</p> <p>N. 0° 12' W., beginning new measurement.</p> <p>Over broken bench.</p>	
36.40	<p>Underground pipeline, bears S. 82° 10' W. and N. 82° 10' E.</p>	
41.04	<p>The cor. of secs. 10, 11, 14, and 15, monumented with a sandstone, 14 x 8 x 6 ins., firmly set 6 ins. in the ground and plainly mkd. 4 notches on S and 2 notches on E edges.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p> <div style="text-align: center;"> <p>T 9 S R 25 E</p> <p>S 10 S 11</p> <p>S 15 S 14</p> <p>1977</p> </div>	

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
	Place the mkd. stone in mound, alongside the iron post.
38.35	<p>From the cor. of secs. 11, 12, 13, and 14. N. 89° 54' W., bet. secs. 11 and 14. Over broken land, covered with shadscale; asc. over SW slope.</p> <p>The ¼ sec. cor. of secs. 11 and 14, monumented with a sandstone, 12 x 8 x 4 ins., firmly set 6 ins. in the ground and plainly mkd. ¼ on N face.</p> <p>At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 9 S R 25 E</p> <p style="text-align: center;">¼ $\frac{S\ 11}{S\ 14}$</p> <p style="text-align: center;">1977</p> <p>Bury the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 89° 59' W., beginning new measurement. Continue over broken bench.</p>
5.90	Underground pipeline, bears N. 82° 10' E. and S. 82° 10' W.
39.90	The cor. of secs. 10, 11, 14, and 15.
39.82	<p>N. 0° 02' E., bet. secs. 10 and 11. Over broken bench land, covered with shadscale; along general E slope.</p> <p>The ¼ sec. cor. of secs. 10 and 11, monumented with a sandstone, 16 x 8 x 4 ins., firmly set, 6 ins. in the ground, marks have been obliterated, with mound of stone, W of cor.</p> <p>At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 9 S R 25 E</p> <p style="text-align: center;"> ¼ S 10 S 11 </p> <p style="text-align: center;">1977</p> <p>Place the mkd. stone in mound.</p> <hr style="width: 20%; margin: auto;"/>

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS						
40.06	<p>N.0° 03' W., beginning new measurement.</p> <p>Desc. gentle E slope.</p> <p>The cor. of secs. 2, 3, 10, and 11, determined by a mound of sandstone, no legible marks on stones, old lath and survey stakes around cor. This position is accepted as the best available evidence of the original corner.</p> <p>At the corner point (center of mound)</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 9 S R 25 E</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 3</td> <td style="padding: 0 5px;">S 2</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 10</td> <td style="padding: 0 5px;">S 11</td> </tr> </table> <p style="text-align: center;">1977</p> <p>Cor. is located on W side of top of sandstone knoll.</p>	S 3	S 2	S 10	S 11	
S 3	S 2					
S 10	S 11					
39.38	<p>From the cor. of secs. 1, 2, 11, and 12.</p> <p>S. 89° 43' W., bet. secs. 2 and 11.</p> <p>Over rolling bench land, covered with shadscale; asc. along gentle S slope.</p> <p>Point for the ¼ sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 9 S R 25 E</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">¼ S 2</td> <td style="padding: 0 5px;">S 11</td> </tr> </table> <p style="text-align: center;">1977</p>	¼ S 2	S 11			
¼ S 2	S 11					
78.76	<p>Raise a mound of stone, 2 ft. base, 2 ft. high, W of cor.</p> <p>The cor. of secs. 2, 3, 10, and 11.</p>					
40.04	<p>N. 0° 04' E., bet. secs. 2 and 3.</p> <p>Over rolling desert land, covered with shadscale; desc. over N slope.</p> <p>The ¼ sec. cor. of secs. 2 and 3, monumented with a sandstone, 18 x 8 x 4 ins., firmly set, 6 ins. in the ground, marks have been obliterated.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>					

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
38.33	<p style="text-align: center;">T 9 S R 25 E</p> <p style="text-align: center;"> $\frac{1}{2}$ S 3 S 2 1977 </p> <p>Bury the cor. stone alongside the iron post.</p> <p>N. 0° 04' E., beginning new measurement.</p> <p>Desc. along gentle E slope.</p> <p>The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., monumented with an iron post, 2 ins. diam., extending 10 ins. above ground, in a collar of stone, with brass cap mkd. as described in the official record of the 1935 resurvey.</p>
13.77	<p>From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., extending 6 ins. above ground, with brass cap mkd. as described in the official record of the 1975 resurvey of the N. bdy. of T. 10 S., R. 25 E.</p> <p>N. 0° 01' E., bet. secs. 33 and 34.</p> <p>Over broken mountain land; desc. over ledgy N slope.</p> <p>Intersect line 7 - 8, Pantaloon Allotment No. 270 No. 23.</p> <p>From point of intersection, Cor. No. 7, bears S. 85° 04' 30" W., 32.95 chs. dist., monumented with a limestone, 16 x 10 x 4 ins., firmly set 6 ins. in the ground, mkd. P7 on N face.</p> <p>From the same intersection point, point for Cor. No. 8, determined by Grant Boundary method, bears N. 85° 04' 30" E., 2.79 chs. dist., (not monumented). From this point, Cor. No. 9, bears N. 54° 58' 30" E., 19.19 chs. dist., hereinafter described.</p>
23.30	Left bank White River, bears N. 40° E. and S. 40° W.
26.40	Right bank same river, bears N. 40° E. and S. 40° W.
31.76	<p>Intersect line 10 - 11, Pantaloon Allotment No. 270 No. 23.</p> <p>From this intersection, the point for Cor. No. 10, bears N. 80° 26' E., 4.91 chs. dist., determined by Grant Boundary method, this point falls on caving ledges of bluff and cannot be monumented. From this point, Cor. No. 9 bears S. 60° 00' E., 15.18 chs. dist., monumented with a sandstone, 12 x 8 x 8 ins., above ground, mkd. P COR 9 on W face, also mound of stone, W of cor.</p> <p>From this same intersection, Cor. No. 11, bears S. 80° 26' W., 86.98 chs. dist., monumented with a sandstone, 16 x 12 x 4 ins., above ground, mkd. P COR 11 on S face, also mound of stone, S of cor.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

40.13 The 1/4 sec. cor. of secs. 33 and 34, monumented with a sandstone, 15 x 10 x 4 ins., firmly set 6 ins. in the ground, with a mound of stone alongside, marks have been obliterated.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.

T 9 S R 25 E

S 33 | S 34

1977

Place the cor. stone in mound.

N. 0° 05' E., beginning new measurement.

Asc. over steep SE slope.

40.10 Point for the cor. of secs. 27, 28, 33, and 34, at proportionate distance. The original witness cor., a sandstone, 14 x 6 x 4 ins., mkd. WC and 1 notch and 3 notches on the edges was found lying loose at base of cut and was not used for corner location.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 9 S R 25 E

S 28 | S 27
S 33 | S 34

1977

Bury the witness cor. alongside the iron post.

From the cor. of secs. 26, 27, 34, and 35.

S. 89° 57' W., bet. secs. 27 and 34.

Over broken mountainous land; asc. over steep E slope.

40.34 The 1/4 sec. cor. of secs. 27 and 34, monumented with a sandstone, 35 x 15 x 15 ins., firmly set 10 ins. in the ground, and plainly mkd. 1/4 on N face, with mound of stone, N of cor.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS		
	<p style="text-align: center;">T 9 S R 25 E</p> <p style="text-align: center;"> $\frac{1}{4}$ $\frac{S\ 27}{S\ 34}$ </p> <p style="text-align: center;">1977</p> <p>Place the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89° 35' W., beginning new measurement.</p> <p>Desc. over general W slope, on E side of canyon.</p> <p>36.70 Left bank of White River, curves NE and SE.</p> <p>38.50 Right bank of same river, curves NE and SE.</p> <p>39.89 The cor. of secs. 27, 28, 33, and 34.</p>	
	<p>N. 1° 02' E., bet. secs. 27 and 28.</p> <p>Over mountain land; asc. along gentle E slope on W side of White River Canyon.</p> <p>8.50 Dirt road, bears W and E, about 5.00 chs.; thence N and S.</p> <p>14.30 Cowboy Canyon, 5 ft. deep, 20 lks. wide, drains E.</p> <p>40.11 The $\frac{1}{4}$ sec. cor. of secs. 27 and 28, monumented with a sandstone, 12 x 8 x 4 ins., set in a mound of stone, marks have been obliterated.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p>	
	<p style="text-align: center;">T 9 S R 25 E</p> <p style="text-align: center;"> $\frac{1}{4}$ S 28 S 27 </p> <p style="text-align: center;">1977</p> <p>Place the cor. stone in mound alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 02' E., beginning new measurement.</p> <p>Asc. along W slope.</p> <p>40.19 The cor. of secs. 21, 22, 27, and 28, monumented with a sandstone, 18 x 8 x 4 ins., firmly set 4 ins. in the ground, and plainly mkd. 2 notches on S and 3 notches on E edge.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p>	

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS		
	T 9 S R 25 E $\begin{array}{c c} \text{S } 21 & \text{S } 22 \\ \text{S } 28 & \text{S } 27 \end{array}$ 1977 Place the mkd. stone in mound, alongside the iron post. Cor. is located about 100 ft. below top of hill, on steep W slope.	
	From the cor. of secs. 22, 23, 26, and 27. N. 89° 59' W., bet. secs. 22 and 27. Over river bottom land, through willows and cottonwood trees, on N side of canyon.	
11.50	Bulldozed road along base of steep S slope, bears N. 80° E. and W; thence along road.	
32.20	Leave road, which curves NW; enter bottom land and trees.	
39.68	Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 27, at propor- tionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.	
	T 9 S R 25 E $\frac{1}{4} \begin{array}{c} \text{S } 22 \\ \text{S } 27 \end{array}$ 1977 from which A cottonwood, 20 ins. diam., bears S. 78° E., 7 lks. dist., mkd. BT.	
48.60	Right bank of White River, bears N. 36° W. and S. 36° E., thence over river.	
53.00	Left bank of same river, bears S. 36° E. and curves NW.	
57.00	Left bank same river, bears S. 37° W. and curves NE.	
59.80	Right bank same river, bears S. 43° W. and curves NE; asc. over gentle SE slope.	
66.40	Same road, bears S and curves NE; asc. steep E slope and impassable ledges facing E.	
79.36	The cor. of secs. 21, 22, 27, and 28.	
	N. 0° 28' W., bet. secs. 21 and 22. Over broken and ledgy land; desc. along steep W slope.	
39.76	The $\frac{1}{4}$ sec. cor. of secs. 21 and 22, monumented with a sandstone, 18 x 14 x 4 ins., firmly set 8 ins. in the ground and plainly mkd. $\frac{1}{4}$ on W face, with mound of stone, W of cor.	

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.

T 9 S R 25 E

$\frac{1}{4}$
 |
 S 21 | S 22

1977

Place the mkd. stone in mound alongside the iron post.

N. $0^{\circ} 11'$ W., beginning new measurement.

Continue over broken bench.

35.54 Intersect line 1 - 4, M.S. No. 5103 Lucky Boy lode.

From this intersection, Cor. No. 1, identical with Cor. No. 4 Scorpion lode, same survey, bears S. $60^{\circ} 14'$ E., 21.01 chs. dist., monumented with a sandstone, 24 x 10 x 5 ins., lying on the ground alongside a mound of stone, mkd. 4-1-5103. This position was verified at record distance from Cor. No. 2 Lucky Boy lode. No original bearing stones were identified.

At the corner point

Set a Copperweld, 28 ins. long, $\frac{5}{8}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

S 4
LB1
5103

Place collar of stone around cor. with mkd. stone in collar.

From this same intersection, Cor. No. 4, identical with Cor. No. 1 Leavenworth lode, same survey, bears N. $60^{\circ} 14'$ W., 1.75 chs. dist., monumented with a sandstone, 28 x 10 x 4 ins., firmly set and plainly mkd. 4-1-5103, mound of stone, W of cor. No bearing marks were identified.

38.40 Trench from gilsonite work, bears N. 60° W. and S. 60° E.

39.87 The cor. of secs. 15, 16, 21, and 22, monumented with a decayed sandstone, firmly set in the ground, marks have been obliterated, with mound of stone, W of cor., and old survey lath around cor.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

T 9 S R 25 E

S 16		S 15
S 21		S 22

1977

Rebuild mound of stone, W of cor.

From the cor. of secs. 14, 15, 22, and 23.

N. 89° 58' W., bet. secs. 15 and 22.

Over broken bench, covered with shadscale; desc. over gentle W slope.

39.81 The ¼ sec. cor. of secs. 15 and 22, monumented with a sandstone, 16 x 12 x 3 ins., firmly set 6 ins. in the ground and plainly mkd. ¼ on N face with small mound of stone, N of cor.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 9 S R 25 E

¼		S 15
		S 22

1977

Bury the mkd. stone alongside the iron post.

Cor. is located 80 lks. W of draw, draining E from NW.

S. 89° 59' W., beginning new measurement.

Asc. over NE slope of small draw.

39.98 The cor. of secs. 15, 16, 21, and 22.

N. 0° 05' E., bet. secs. 15 and 16.

Over rolling hills, covered with shadscale; asc. over gentle S slope.

40.01 The ¼ sec. cor. of secs. 15 and 16, monumented with a sandstone, 12 x 8 x 3 ins., firmly set 4 ins. in the ground and plainly mkd. ¼ on W face, with small mound of stone, W of cor.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 9 S R 25 E

		¼
S 16		S 15

1977

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS					
	<p>Bury the mkd. stone alongside the iron post.</p> <p style="text-align: center;">_____</p> <p>N. 0° 31' W., beginning new measurement.</p> <p>Asc. along gentle E slope.</p> <p>24.60 Underground pipeline, bears N. 82° 20' E. and S. 82° 20' W.; asc. gentle SE slope.</p> <p>39.99 The cor. of secs. 9, 10, 15, and 16, monumented with a sandstone, 14 x 4 x 3 ins., firmly set 6 ins. in the ground and plainly mkd. 4 notches on S and 3 notches on E edges, with mound of stone, W of cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 9 S R 25 E</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 9</td> <td style="padding: 0 5px;">S 10</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 16</td> <td style="padding: 0 5px;">S 15</td> </tr> </table> <p style="text-align: center;">1977</p> <p>Bury the mkd. stone alongside the iron post.</p>	S 9	S 10	S 16	S 15
S 9	S 10				
S 16	S 15				
	<p>From the cor. of secs. 10, 11, 14, and 15.</p> <p>N. 89° 59' W., bet. secs. 10 and 15.</p> <p>Over broken desert bench land, covered with shadscale; asc. over gentle E slope.</p> <p>39.98 The ¼ sec. cor. of secs. 10 and 15, monumented with a sandstone, 16 x 8 x 4 ins., firmly set 6 ins. in the ground and plainly mkd. ¼ on N face, with mound of stone, N of cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 9 S R 25 E</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">¼ S 10</td> <td style="padding: 0 5px;">S 15</td> </tr> </table> <p style="text-align: center;">1977</p> <p>Bury the mkd. stone alongside the iron post.</p> <p style="text-align: center;">_____</p> <p>S. 89° 59' W., beginning new measurement.</p> <p>Asc. over gentle SE slope.</p> <p>40.28 The cor. of secs. 9, 10, 15, and 16.</p>	¼ S 10	S 15		
¼ S 10	S 15				

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS		
	<p>N. 0° 09' E., bet. secs. 9 and 10.</p> <p>Over broken desert bench land, covered with shadscale; asc. S slope.</p> <p>6.80 Hard surface road, bears N. 50° E. and S. 50° W., on top of rise; desc. over gentle NW slope.</p> <p>39.78 The ¼ sec. cor. of secs. 9 and 10, monumented with a sandstone, 12 x 10 x 3 ins., set in a mound of stone, dimly mkd. ¼ on W face, with survey lath and stakes around corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p> <div style="text-align: center;"> <p>T 9 S R 25 E</p> <p>¼</p> <p>S 9 S 10</p> <p>1977</p> </div> <p>Place the mkd. stone in mound alongside the iron post; cor. is located on rise, which slopes W.</p>	
<p>40.23</p>	<p>N. 0° 18' W., beginning new measurement.</p> <p>Desc. over broken bench, draining N.</p> <p>The cor. of secs. 3, 4, 9, and 10, monumented with a sandstone, 18 x 8 x 4 ins., set in a mound of stone, marks have been obliterated.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 9 S R 25 E</p> <p>S 4 S 3</p> <p>S 9 S 10</p> <p>1977</p> </div> <p>Place the cor. stone alongside the iron post.</p> <p>Raise a mound of stone, 2 ft. base, 2 ft. high, W of cor.</p>	
<p>20.70</p>	<p>From the cor. of secs. 2, 3, 10, and 11.</p> <p>N. 89° 56' W., bet. secs. 3 and 10.</p> <p>Over broken desert bench land, covered with shadscale; desc. over W slope.</p> <p>Hard surface road, bears N. 4° 30' E. and S. 4° 30' W.</p>	

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

39.99 The $\frac{1}{4}$ sec. cor. of secs. 3 and 10, monumented with a sandstone, 16 x 12 x 4 ins., firmly set 4 ins. in the ground and plainly mkd. $\frac{1}{4}$ on N face, with mound of stone, N of cor.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.

T 9 S R 25 E

$\frac{1}{4}$ $\frac{S 3}{S 10}$

1977

Place the mkd. stone in mound alongside the iron post.

N. $89^{\circ} 55'$ W., beginning new measurement.

Desc. over SW slope.

40.33 The cor. of secs. 3, 4, 9, and 10.

N. $0^{\circ} 13'$ E., bet. secs. 3 and 4.

Over broken desert bench land, covered with shadscale; asc. over S slope.

40.17 The $\frac{1}{4}$ sec. cor. of secs. 3 and 4, monumented with a deteriorated sandstone, 14 x 6 x 6 ins., firmly set 6 ins. in the ground marks have been obliterated, with mound of stone, W of cor.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 9 S R 25 E

$\frac{1}{4}$
S 4 | S 3

1977

Place cor. stone alongside the iron post.

Rebuild mound of stone, W of cor.

N. $0^{\circ} 01'$ E., beginning new measurement.

Continue over broken bench.

38.17 The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., monumented with an iron post, 2 ins. diam., extending 8 ins. above ground, with brass cap mkd. as described in the official record of the 1935 resurvey with mound of stone, W of cor.

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

	<p>From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., extending 6 ins. above ground, with brass cap mkd. as described in the official record of the 1975 resurvey of the N. bdy. of T. 10 S., R. 25 E.</p> <p>North, bet. secs. 32 and 33.</p> <p>Over broken mountain land; desc. over N slope.</p> <p>4.53 Intersect line 5 - 6, Pantaloon Allotment No. 270 No. 23.</p> <p>From point of intersection, mile post No. 1, bears S. 86° 26' W., 2.85 chs. dist., monumented with an unmkd. limestone, 16 x 8 x 3 ins., firmly set in a mound of stone, 2 ft. base, 1 ft. high. This stone is harmoniously related to existing original corners on this allotment and is accepted as the best existing evidence of the original mile cor.</p> <p>From the same point of intersection, point for Cor. No. 6, determined by Grant Boundary method, bears N. 86° 26' E., 20.99 chs. dist. (not monumented). From this point, Cor. No. 7, bears N. 79° 22' E., 26.47 chs. dist., heretofore described.</p> <p>8.40 Left bank of White River, bears N. 85° W. and S. 85° E.; thence over river.</p> <p>10.20 Right bank of same river, bears N. 80° W. and S. 80° E.; thence over river bottom.</p> <p>18.14 Intersect line 10 - 11, Pantaloon Allotment No. 270 No. 23.</p> <p>From this intersection, the point for Cor. No. 10, bears N. 80° 26' E., 85.79 chs. dist., heretofore described.</p> <p>From this same intersection, Cor. No. 11, bears S. 80° 26' W., 6.10 chs. dist., heretofore described.</p> <p>39.73 The ¼ sec. cor. of secs. 32 and 33, monumented with a sandstone, 18 x 14 x 4 ins., set in a mound of stone, and plainly mkd. ¼ on W face.</p> <p>At the corner point.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap mkd.</p> <div style="text-align: center;"> <p>T 9 S R 25 E</p> <p>¼</p> <p>S 32 S 33</p> <p>1977</p> </div> <p>Place the mkd. stone in mound alongside the iron post; cor. is located on steep shale SE slope.</p>
--	---

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
	N. 0° 03' E., beginning new measurement. Asc. over steep SE slope.
3.79	Intersect line 1 - 4, M.S. No. 5254, No. 1 Black Beauty lode. From this intersection, Cor. No. 4, bears S. 54° 23' E., 1.54 chs. dist., monumented with a sandstone, 20 x 16 x 8 ins., above ground, mkd. 4-5254. No bearing marks identified. From this same intersection, Cor. No. 1, identical with Cor. No. 4, M.S. 5255, No. 2 Rose lode, bears N. 54° 23' W., 21.03 chs. dist., monumented with a sandstone, 24 x 16 x 4 ins., above ground, mkd. 1-5254 on E face and 4-5255 on W face.
6.40	Gilsonite vein, bears N. 54° 20' W. and S. 54° 20' E., also top of bench; thence over broken bench.
8.99	Intersect line 2 - 3, M.S. No. 5254, No. 1 Black Beauty lode. From this intersection, Cor. No. 3, bears S. 54° 03' E., 3.44 chs. dist., monumented with a sandstone, 12 x 8 x 4 ins., above ground, mkd. 3-5254. No bearing marks identified. From this same intersection, Cor. No. 2, identical with Cor. No. 3, M.S. 5255, No. 2 Rose lode, bears N. 54° 03' W., 19.15 chs. dist., monumented with a sandstone, 14 x 12 x 8 ins., above ground, mkd. 2-5254 on E face and 3-5255 on W face. No bearing marks identified.
40.11	The cor. of secs. 28, 29, 32, and 33, monumented with a sandstone, 14 x 10 x 3 ins., set in a mound of stone and plainly mkd. 1 notch on S and 4 notches on E edges. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap mkd. T 9 S R 25 E S 29 S 28 S 32 S 33 1977 Place the mkd. stone in mound, alongside the iron post.
39.83	From the cor. of secs. 27, 28, 33, and 34. S. 89° 47' W., bet. secs. 28 and 33. Over broken mountain land, on W side of White River Canyon; asc. E slope. The ¼ sec. cor. of secs. 28 and 33, monumented with a sandstone, 22 x 6 x 3 ins., firmly set 8 ins. in the ground and plainly mkd. ¼ on N face, with mound of stone, S of cor.

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 9 S R 25 E

¼ $\frac{S\ 28}{S\ 33}$

1977

Set the mkd. stone alongside the iron post, and raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.

S. 89° 58' W., beginning new measurement.

Asc. over NE slope.

39.94 The cor. of secs. 28, 29, 32, and 33.

N. 0° 03' W., bet. secs. 28 and 29.

Over broken desert bench.

39.59 Point selected for the witness cor. to the ¼ sec. cor. of secs. 28 and 29.

Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.

W C
T 9 S R 25 E

¼
↑
S 29 | S 28
|

1977

40.21 Point for the ¼ sec. cor. of secs. 28 and 29, at proportionate distance; falls in wash in ravine, which drains SE, and cannot be monumented; there is no remaining evidence of the original cor. Asc. over S slope.

43.20 Bladed dirt road, bears SW and NE; asc. along broken E slope.

57.30 Same road, bears NW and SE; thence along broken E slope.

67.70 Fork of same road, in Cowboy Canyon, roads bear E, SW, and SE; asc. steep S slope.

80.42 The cor. of secs. 20, 21, 28, and 29, monumented with a sandstone, 14 x 10 x 4 ins., firmly set 4 ins. in the ground and plainly mkd. 2 notches on S and 4 notches on E edges, with mound of stone, W of cor.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

T 9 S R 25 E

S 20	S 21
S 29	S 28

1977

Place the mkd. stone in mound, alongside the iron post.

From the cor. of secs. 21, 22, 27, and 28.

S. 89° 57' W., bet. secs. 21 and 28.

Over broken mountain land; desc. over steep and ledgy W slope.

40.95 Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28, at proportionate distance, falls on steep and ledgy S slope and cannot be monumented.

49.43 The witness $\frac{1}{4}$ sec. cor. of secs. 21 and 28, monumented with a sandstone, 24 x 14 x 4 ins., set in a mound of stone and plainly mkd. $\frac{1}{4}$ and WC on N face.

At the witness corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 3 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.

W C
T 9 S R 25 E

$\frac{1}{4}$ $\frac{S 21}{S 28}$ →

1977

Place the mkd. stone in mound alongside the iron post.

S. 89° 57' W., beginning new measurement.

Asc. along broken S slope, in ravine.

31.11 The cor. of secs. 20, 21, 28, and 29.

N. 0° 02' E., bet. secs. 20 and 21.

Over broken bench land, through scattered juniper; asc. along E slope.

39.71 The $\frac{1}{4}$ sec. cor. of secs. 20 and 21, monumented with a sandstone, 16 x 10 x 4 ins., firmly set, 6 ins. in the ground, marks have been obliterated, with small mound of stone, W of cor.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

T 9 S R 25 E

$$\begin{array}{c} \frac{1}{4} \\ | \\ \text{S } 20 \quad | \quad \text{S } 21 \\ | \end{array}$$

1977

Bury the cor. stone alongside the iron post and rebuild mound of stone, W of cor.

Cor. is located 60 lks. N of wash, draining E.

N. $0^{\circ} 12' E.$, beginning new measurement.

Asc. over SW slope.

39.97 The cor. of secs. 16, 17, 20, and 21, monumented with a sandstone, 14 x 10 x 6 ins., firmly set 4 ins. in the ground, and mkd. 3 notches on S and 4 notches on E edges, with mound of stone, N of cor.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 9 S R 25 E

$$\begin{array}{c} \text{S } 17 \quad | \quad \text{S } 16 \\ \text{S } 20 \quad | \quad \text{S } 21 \end{array}$$

1977

Bury the mkd. stone alongside the iron post.

From the cor. of secs. 15, 16, 21, and 22.

N. $89^{\circ} 52' W.$, bet. secs. 16 and 21.

Over broken desert land; asc. over NE slope.

3.00 Trench, 20 lks. wide, about 60 ft. deep, bears N. $60^{\circ} W.$ and S. $60^{\circ} E.$

7.57 Intersect line 1 - 4, M.S. 5103, Leavenworth lode.

From this intersection, Cor. No. 1, identical with Cor. No. 4, Lucky Boy lode, same survey, bears S. $60^{\circ} 10' E.$, 7.00 chs. dist., heretofore described.

From this same intersection, Cor. No. 4, identical with Cor. No. 1, Cowboy lode, same survey, bears N. $60^{\circ} 10' W.$, 15.70 chs. dist., falls in old stone building and cannot be monumented. This point was determined by original ties to this old stone building, the original witness cor., bearing tree and bearing object have been destroyed by gilsonite mining operations.

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS		
40.03	<p>The $\frac{1}{4}$ sec. cor. of secs. 16 and 21, monumented with a sandstone, 20 x 14 x 4 ins., firmly set 8 ins. in the ground, marks have been obliterated, with mound of stone, N of cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 9 S R 25 E</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S\ 16}{S\ 21}$</p> <p style="text-align: center;">1977</p> <p>Place the cor. stone alongside the iron post and rebuild mound of stone, N of cor.</p> <hr style="width: 20%; margin: auto;"/> <p>S. $89^{\circ} 49'$ W., beginning new measurement.</p> <p>Asc. over E slope, through juniper trees.</p>	
31.60	Rim, bears N and S; thence over brush covered bench, leave trees.	
39.87	The cor. of secs. 16, 17, 20, and 21.	
12.50	<p>N. $0^{\circ} 22'$ W., bet. secs. 16 and 17.</p> <p>Over rolling bench land, covered with shadscale.</p>	
36.20	Hard surface road, bears N. $49^{\circ} 10'$ E. and S. $49^{\circ} 10'$ W., continue over bench.	
40.31	Graded gravel road, bears N. 60° W. and S. 60° E.	
40.31	<p>The $\frac{1}{4}$ sec. cor. of secs. 16 and 17, determined by an iron stake, in the ground with lath around the iron stake, and substantiated by tie to USLM No. 3 which bears N. $85^{\circ} 18'$ W., 5.10 chs. dist. (record, N. $85^{\circ} 15'$ W., 5.10 chs. dist.).</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 9 S R 25 E</p> <p style="text-align: center;">$\frac{1}{4}$</p> <p style="text-align: center;">S 17 S 16</p> <p style="text-align: center;">1977</p> <hr style="width: 20%; margin: auto;"/> <p>N. $0^{\circ} 25'$ W., beginning new measurement.</p> <p>Over broken desert land.</p>	

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

- 0.14 Intersect line 1 - 4, M.S. 5253 Bandanna No. 9 Lode.
- From this intersection, Cor. No. 1, identical with Cor. No. 1, M.S. 5185 Archie lode, bears N. $61^{\circ} 41'$ W., 0.60 chs. dist., determined by a mound of stone and old wood stake. This position was also verified as record course and distance from USLM No. 3.
- At the corner point
- Set a Copperweld, 30 ins. long, $5/8$ in. diam., 24 ins. in the ground, with brass cap mkd.
- B 1
5253
A 1
5185
- Place collar of stone around corner.
- From this same intersection, Cor. No. 4, identical with Cor. No. 4, M.S. 5103 Dixie lode, bears S. $61^{\circ} 41'$ E., 22.13 chs. dist., determined by a mound of stone and old wooden stake. This position was also verified as record course and distance from USLM No. 3.
- At the corner point
- Set a Copperweld, 30 ins. long, $5/8$ ins. diam., 24 ins. in the ground, with brass cap mkd.
- 4
5103
4
5253
- Place collar of stone around corner.
- 2.50 Trench for gilsonite mining, 20 lks. wide, about 60 ft. deep, bears N. $61^{\circ} 30'$ W. and S. $61^{\circ} 30'$ E.
- 5.30 Intersect line 2 - 3, M.S. 5185 Archie lode.
- From this intersection, Cor. No. 2, M.S. 5185, identical with Cor. No. 2, M.S. 5253, Bandanna No. 9 Lode, bears S. $61^{\circ} 33'$ E., 2.10 chs. dist., determined by a mound of stone and old wooden stake. This position was also verified as record course and distance from USLM No. 3.
- At the corner point
- Set a Copperweld, 30 ins. long, $5/8$ ins. diam., 24 ins. in the ground, with brass cap mkd.
- B 2
5253
A 2
5185
- Place collar of stone around corner.
- From this same intersection, Cor. No. 3, identical with Cor. No. 2, Davy Crockett Lode, bears N. $61^{\circ} 33'$ W., 20.61 chs. dist., monumented with a sandstone, 18 x 8 x 5 ins., above ground, mkd. 3-2-5185. The bearing objects for this cor. have been destroyed by mining work.

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS					
23.20	Underground pipeline, bears E and W.				
39.67	<p>The cor. of secs. 8, 9, 16, and 17, monumented with a sandstone, 16 x 14 x 8 ins., firmly set, 6 ins. in the ground, marks have been obliterated, with old survey lath and steel fence post alongside.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 9 S R 25 E</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 8</td> <td style="padding: 0 5px;">S 9</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 17</td> <td style="padding: 0 5px;">S 16</td> </tr> </table> <p style="text-align: center;">1977</p> <p>Bury the cor. stone alongside the iron post.</p> <p>Cor. is located 40 lks. S of wash, draining W.</p>	S 8	S 9	S 17	S 16
S 8	S 9				
S 17	S 16				
7.00	<p>From the cor. of secs. 9, 10, 15, and 16.</p> <p>S. 89° 11' W., bet. secs. 9 and 16.</p> <p>Over broken desert land, draining NW; desc. over NW slope.</p> <p>Hard surface road, bears N. 49° 10' E. and S. 49° 10' W.</p>				
39.80	<p>The ¼ sec. cor. of secs. 9 and 16, monumented with a sandstone, 20 x 8 x 4 ins., firmly set 8 ins. in the ground and dimly mkd. ¼ on N face, with small mound of stone, N of cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 9 S R 25 E</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 0 5px;">¼</td> <td style="border-right: 1px solid black; padding: 0 5px;">S 9</td> <td style="padding: 0 5px;">S 16</td> </tr> </table> <p style="text-align: center;">1977</p> <p>Bury the mkd. stone alongside the iron post and rebuild small mound of stone, N of cor.</p> <p style="text-align: center;">_____</p> <p>N. 89° 18' W., beginning new measurement.</p> <p>Continue along N slope.</p>	¼	S 9	S 16	
¼	S 9	S 16			
40.32	<p>The cor. of secs. 8, 9, 16, and 17.</p> <p>N. 0° 04' W., bet. secs. 8 and 9.</p> <p>Over broken desert land, draining NW.</p>				

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
39.91	<p>The $\frac{1}{4}$ sec. cor. of secs. 8 and 9, determined by a mound of weathered sandstone, also old survey lath and stakes. This position is harmoniously related to existing original cors., and is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point (center of mound)</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 9 S R 25 E</p> <p>$\frac{1}{4}$</p> <p>S 8 S 9</p> <p>1977</p> </div> <p>N. $0^{\circ} 10'$ W., beginning new measurement.</p> <p>Asc. over SW slope.</p>
40.10	<p>The cor. of secs. 4, 5, 8, and 9, monumented with a sandstone, 14 x 8 x 4 ins., firmly set, 6 ins. in the ground, marks have been obliterated. with small mound of stone, S of cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 9 S R 25 E</p> <p>S 5 S 4</p> <p>S 8 S 9</p> <p>1977</p> </div> <p>Place cor. stone alongside the iron post.</p> <p>Rebuild mound of stone, N of cor.</p>
39.68	<p>From the cor. of secs. 3, 4, 9, and 10.</p> <p>N. $89^{\circ} 55'$ W., bet. secs. 4 and 9.</p> <p>Over broken desert land; desc. over W slope.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 4 and 9, monumented with a sandstone, 14 x 8 x 6 ins., firmly set 6 ins. in the ground and plainly mkd. $\frac{1}{4}$ on N face, with mound of stone, N of cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

T 9 S R 25 E

$$\frac{1}{4} \begin{array}{c} S 4 \\ S 9 \end{array}$$

1977

Bury the mkd. stone alongside the iron post; rebuild mound of stone, N of cor.

S. 89° 51' W., beginning new measurement.

Desc. over W slope.

40.48 The cor. of secs. 4, 5, 8, and 9.

N. 0° 07' E., bet. secs. 4 and 5.

Over broken desert land; desc. over N slope.

40.46 The $\frac{1}{4}$ sec. cor. of secs. 4 and 5, monumented with a sandstone, 16 x 8 x 4 ins., firmly set, 4 ins. in the ground, marks have been obliterated, with weathered mound of stone, W of cor.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 9 S R 25 E

$$\frac{1}{4} \begin{array}{c} | \\ S 5 \quad | \quad S 4 \end{array}$$

1977

Place the cor. stone alongside the iron post.

N. 0° 08' E., beginning new measurement.

Continue along general W slope.

37.79 The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., monumented with an iron post, 2 ins. diam., extending 10 ins. above ground, with a mound of stone north, with brass cap mkd. as described in the official record of the 1935 resurvey.

From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., extending 6 ins. above ground, in a collar of stone, with brass cap mkd. as described in the official record of the 1975 resurvey of the N. bdy. of T. 10 S., R. 25 E.

N. 0° 08' E., bet. secs. 31 and 32.

Over broken desert bench land; along gentle E slope.

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

40.12

The $\frac{1}{4}$ sec. cor. of secs. 31 and 32, monumented with a sandstone, 16 x 10 x 4 ins., firmly set in a mound of stone and plainly mkd. $\frac{1}{4}$ on W face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.

T 9 S R 25 E

$\frac{1}{4}$
 |
 S 31 | S 32
 |

1977

Place the mkd. stone in mound alongside the iron post.

N. $0^{\circ} 03'$ W., beginning new measurement.

Asc. along E slope.

18.71 Intersect line 2 - 3, M.S. No. 5270, Number One lode.

From this intersection, Cor. No. 2, bears S. $62^{\circ} 28'$ E., 3.885 chs. dist., monumented with a sandstone, 20 x 14 x 6 ins., in a scattered mound of stone, marks illegible, no bearing objects identified.

At the corner point

Set a Copperweld, 30 ins. long, $\frac{5}{8}$ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.

2
5270

Place the mkd. stone in mound alongside the Copperweld.

From this same intersection, Cor. No. 3, identical with Cor. No. 2, Number Two lode, same survey, bears N. $62^{\circ} 28'$ W., 18.855 chs. dist., monumented with a sandstone, 12 x 8 x 8 ins., above ground, plainly mkd. 3-2-5270, no bearing object identified.

21.30 Gilsonite vein, bears NW and SE.

23.72 Intersect line 1 - 4, M.S. 5270, Number One lode.

From this intersection, Cor. No. 1, bears S. $62^{\circ} 14'$ E., 6.21 chs. dist., monumented with a sandstone, 12 x 12 x 10 ins., above ground, plainly mkd. 1-5270, from which an X on flat sandstone, bears S. $36^{\circ} 31'$ E., 32.4 ft. dist.

From this same intersection, Cor. No. 4, identical with Cor. No. 1, Number Two lode, same survey, bears N. $62^{\circ} 14'$ W., 16.525 chs. dist., monumented with a sandstone, 12 x 12 x 10 ins., above ground, plainly mkd. 4-1-5270, no bearing object identified.

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

39.92 The cor. of secs. 29, 30, 31, and 32, monumented with a sandstone, 14 x 8 x 4 ins., firmly set 6 ins. in the ground and plainly mkd. 1 notch on S and 5 notches on E edges, with mound of stone, W of cor.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.

T 9 S R 25 E

S 30	S 29
S 31	S 32

1977

Place the mkd. stone in mound alongside the iron post.

From the cor. of secs. 28, 29, 32, and 33.

S. 89° 55' W., bet. secs. 29 and 32.

Over rolling desert land, covered with shadscale.

40.12 The ¼ sec. cor. of secs. 29 and 32, monumented with a sandstone, 15 x 12 x 3 ins., firmly set, 4 ins. in the ground, marks have been obliterated, with mound of stone, N of cor.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.

T 9 S R 25 E

¼	S 29	S 32
	S 32	

1977

Place the cor. stone in mound alongside the iron post.

N. 89° 59' W., beginning new measurement.

Continue over rolling desert land.

3.465 Intersect line 2 - 3, M.S. 5256, No. 3 Pink lode.

From this intersection, Cor. No. 3, identical with Cor. No. 2, M.S. 5255, No. 2 Rose lode bears S. 53° 50' E., 11.725 chs. dist., monumented with a sandstone, 14 x 14 x 8 ins., above ground, mkd. 3-5256 and 2-5255.

From this same intersection, Cor. No. 2, identical with Cor. No. 4, No. 4 Grey Lode, same survey, bears N. 53° 50' W., 11.059 chs. dist., monumented with a sandstone, 16 x 12 x 8 ins., above ground, mkd. 2-4-5256. No bearing objects identified.

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
10.86	<p>Intersect line 1 - 4, M.S. 5256, No. 3 Pink lode.</p> <p>From this intersection, Cor. No. 4, identical with Cor. No. 1, M.S. 5255, No. 2 Rose Lode, bears S. 53° 49' E., 18.94 chs. dist., monumented with a sandstone, 16 x 10 x 4 ins., above ground, mkd. 4-5256 and 1-5255.</p> <p>From this same intersection, Cor. No. 1, identical with Cor. No. 1, No. 4 Gray lode, same survey, bears N. 53° 49' W., 3.815 chs. dist., monumented with a sandstone, 14 x 12 x 10 ins., above ground, mkd. 1-1-5256. No bearing objects identified.</p>
23.50	<p>Underground pipeline, bears NW and SE.</p>
26.94	<p>Intersect line 3 - 4, M.S. 5272, Number One lode.</p> <p>From this intersection, Cor. No. 4, bears S. 58° 22' E., 3.06 chs. dist., monumented with a sandstone, 14 x 12 x 4 ins., above ground, marks illegible, with mound of stone, S of cor., from which an X on sandstone outcrop bears S. 17° 37' W., 130.9 ft. dist.</p> <p>From this same intersection, Cor. No. 3, identical with Cor. No. 1, Number Two lode, same survey, bears N. 58° 22' W., 19.675 chs. dist., monumented with a sandstone, 30 x 16 x 4 ins., set in a mound of stone and plainly mkd. 3-1-5272. The bearing object for this cor. is now covered with sand and cannot be identified.</p>
35.47	<p>Intersect line 1 - 2, M.S. 5272, Number One lode.</p> <p>From this intersection, Cor. No. 1, bears S. 58° 30' E., 10.61 chs. dist., monumented with a sandstone, 24 x 16 x 4 ins., set in a scattered mound of stone, dimly mkd. 1-5272.</p> <p>from which</p> <p style="padding-left: 40px;">An "X" with 1-5272 chiseled alongside, on sandstone ledge, bears N. 19° 09' E., 53.6 ft. dist.</p> <p style="padding-left: 40px;">U.S.L.M. No. 11, bears N. 32° 21' W., 64.6 ft. dist. (record, N. 32° 08' W.)</p> <p>From this same intersection, Cor. No. 2, identical with Cor. No. 2, Number Two lode, same survey, bears N. 58° 30' W., 12.135 chs. dist., monumented with a sandstone, 20 x 14 x 4 ins., above ground, marks illegible, with a mound of stone, N of cor., bearing object X weathered away but mound of stone at record course and distance.</p>
39.91	<p>The cor. of secs. 29, 30, 31, and 32.</p> <hr/> <p>S. 89° 57' W., bet. secs. 30 and 31.</p> <p>Over broken desert land, covered with shadscale; asc. along N slope.</p>
30.23	<p>Intersect line 1 - 4, M.S. 5270, Number Two lode.</p> <p>From this intersection, Cor. No. 1, identical with Cor. No. 4, Number One lode, same survey, bears S. 61° 29' E., 17.77 chs. dist., heretofore described.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

From this same intersection, Cor. No. 4, identical with Cor. No. 1, M.S. 5271, Number Three lode, bears N. 61° 29' W., 4.935 chs. dist., monumented with a sandstone, 14 x 8 x 8 ins., above ground, mkd. 1-5271 and 4-5270, with mound of stone around cor.

39.84 Intersect line 2 - 3, M.S. 5271, Number Three lode.

From this intersection, Cor. No. 2, identical with Cor. No. 3, M.S. 5270, Number Two lode, bears S. 62° 20' E., 3.58 chs. dist., monumented with a sandstone, 16 x 10 x 5 ins., above ground, plainly mkd. 2-5271 and 3-5270. Bearing object not identified.

From this same intersection, Cor. No. 3, identical with Cor. No. 2, Number Four lode, same survey, bears N. 62° 20' W., 19.11 chs. dist., monumented with a sandstone, 20 x 16 x 10 ins., above ground, plainly mkd. 3-2-5271.

39.98 The 1/4 sec. cor. of secs. 30 and 31, monumented with a sandstone, 16 x 8 x 4 ins., set in a mound of stone, marks have been obliterated.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., on solid sandstone, over an X, in a mound of stone, 4 ft. base, to top of brass cap, mkd.

T 9 S R 25 E

1/4 S 30 / S 31

1977

Place the cor. stone in mound alongside the iron post.

S. 89° 57' W., beginning new measurement.

Desc. over W slope.

13.50 Dirt road, bears N. 10° E. and S. 10° W.

22.70 Underground pipeline, bears S. 36° 45' W. and N. 36° 45' E.

40.01 The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of the E. bdy. of T. 9 S., R. 24 E.

From the cor. of secs. 29, 30, 31, and 32.

N. 0° 02' W., bet. secs. 29 and 30.

Over broken desert land, covered with shadscale.

2.72 Intersect line 1 - 2, M.S. 5272, Number One lode.

From this intersection, Cor. No. 1, bears S. 58° 30' E., 15.815 chs. dist., heretofore described.

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
8.01	<p>From this same intersection, Cor. No. 2, identical with Cor. No. 2, Number Two lode, same survey, bears N. 58° 30' W., 6.93 chs. dist., heretofore described.</p> <p>Intersect line 3 - 4, M.S. 5272, Number One lode.</p> <p>From this intersection, Cor. No. 4, bears S. 58° 22' E., 18.30 chs. dist., heretofore described.</p>
11.40	<p>From this same intersection, Cor. No. 3, identical with Cor. No. 1, Number Two lode, same survey, bears N. 58° 22' W., 4.435 chs. dist., heretofore described.</p> <p>Underground pipeline, bears N. 55° 30' W. and S. 55° 30' E.</p>
20.285	<p>Intersect line 1-2, M.S. 5257, No. 5, Yellowstone lode.</p> <p>From this intersection, Cor. No. 1, identical with Cor. No. 2, M.S. 5256, No. 4 Grey lode, bears S. 56° 26' E., 8.905 chs. dist., monumented with a sandstone, 18 x 10 x 4 ins., above ground, mkd. 1-5257 and 2-5256. Bearing object marks have been obliterated, only mound of stone remains.</p>
25.57	<p>From this same intersection, Cor. No. 2, identical with Cor. No. 1, M.S. 5258, No. 6 Stonewall lode, bears N. 56° 26' W., 13.765 chs. dist., monumented with a sandstone, 16 x 16 x 4 ins., above ground, mkd. 2-5257 and 1-5258. Bearing object marks have been obliterated only mound of stone remains.</p> <p>Intersect line 3 - 4, M.S. 5257, No. 5 Yellowstone lode.</p> <p>From this intersection, Cor. No. 4, identical with Cor. No. 3, M.S. 5256, No. 4 Grey lode, bears S. 56° 35' E., 10.725 chs. dist., monumented with a sandstone, 14 x 12 x 4 ins., above ground, marks partly obliterated. Bearing object marks have been obliterated, only mound remains.</p> <p>From this same intersection, Cor. No. 3, identical with Cor. No. 4, M.S. 5258, No. 6 Stonewall lode, bears N. 56° 35' W., 11.91 chs. dist., mkd. by a X on solid sandstone with a mound of stone alongside, other marks mostly obliterated, also mound of stone where bearing object marks should be.</p>
32.30	<p>Dirt road, bears N. 85° W. and S. 85° E.</p>
39.98	<p>The ¼ sec. cor. of secs. 29 and 30, determined by a mound of stone with old survey stakes and lath around the mound, no marks could be identified. This position is accepted as the best available evidence of the original cor.</p> <p>At the corner point (center of mound)</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

T 9 S R 25 E

$$\begin{array}{c} \frac{1}{4} \\ | \\ \text{S } 30 \quad | \quad \text{S } 29 \\ | \end{array}$$

1977

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

North, beginning new measurement.

Asc. over SE slope.

40.05 The cor. of secs. 19, 20, 29, and 30, monumented with a sandstone, 20 x 12 x 4 ins., firmly set 10 ins. in the ground, and plainly mkd. 2 notches on S and 5 notches on E edges, with mound of stone, W of cor.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 9 S R 25 E

$$\begin{array}{c} \text{S } 19 \quad | \quad \text{S } 20 \\ \text{S } 30 \quad | \quad \text{S } 29 \end{array}$$

1977

Bury the mkd. stone alongside the iron post and rebuild mound of stone, W of cor.

From the cor. of secs. 20, 21, 28, and 29.

S. 89° 35' W., bet. secs. 20 and 29.

Over broken desert land, through scattered juniper; asc. over NE slope.

40.00 The ¼ sec. cor. of secs. 20 and 29, monumented with a sandstone, 16 x 10 x 5 ins., firmly set 8 ins. in the ground, and dimly mkd. ¼ on N face, with mound of stone, N of cor.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 9 S R 25 E

$$\begin{array}{c} \frac{1}{4} \quad \text{S } 20 \\ \text{S } 29 \end{array}$$

1977

Bury the mkd. stone alongside the iron post.

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
39.97	<p>S. 89° 48' W., beginning new measurement.</p> <p>Over broken bench land.</p> <p>The cor. of secs. 19, 20, 29, and 30.</p>
21.40	<p>West, bet. secs. 19 and 30.</p> <p>Over broken desert land, covered with shadscale; desc. over gentle NW slope.</p> <p>Hard surface road, bears S. 39° 40' W. and N. 39° 40' E.; asc. over gentle E slope.</p>
39.96	<p>The ¼ sec. cor. of secs. 19 and 30, monumented with a sandstone, 15 x 10 x 4 ins., set in a mound of stone and plainly mkd. ¼ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 9 S R 25 E</p> <p style="text-align: center;">¼ $\frac{S 19}{S 30}$</p> <p style="text-align: center;">1977</p> <p>Place the mkd. stone in mound alongside the iron post.</p>
4.50	<p>S. 89° 53' W., beginning new measurement.</p> <p>Along gentle N slope.</p> <p>Underground pipeline, bears N. 36° 10' E. and S. 36° 10' W.</p>
40.01	<p>The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of the E. bdy. of T. 9 S., R. 24 E.</p>
24.60	<p>From the cor. of secs. 19, 20, 29, and 30.</p> <p>N. 0° 05' E., bet. secs. 19 and 20.</p> <p>Over broken desert land, covered with shadscale; desc. over gentle NW slope.</p> <p>Hard surface road, bears N. 42° 10' E. and S. 42° 10' W.</p>
40.08	<p>The ¼ sec. cor. of secs. 19 and 20, monumented with a weathered sandstone, 8 x 6 x 2 ins., set in a small mound of stone and dimly mkd. ¼ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
	<p style="text-align: center;">T 9 S R 25 E</p> <p style="text-align: center;"> $\frac{1}{4}$ S 19 S 20 1977 </p> <p>Place the mkd. stone in mound alongside the iron post. Cor. is located on sandstone rim, which slopes W.</p> <p style="text-align: center;">-----</p> <p>N. 0° 01' E., beginning new measurement.</p> <p>Desc. along general W slope.</p> <p>20.60 Underground pipeline, bears N. 36° 10' E. and S. 36° 10' W.</p> <p>40.13 The cor. of secs. 17, 18, 19, and 20, monumented with a sandstone, 18 x 8 x 6 ins., firmly set, 6 ins. in the ground, marks have been obliterated, with mound of stone, W of cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 9 S R 25 E</p> <p style="text-align: center;"> S 18 S 17 S 19 S 20 1977 </p> <p>Bury the cor. stone alongside the iron post and rebuild mound of stone, W of cor.</p>
	<p>From the cor. of secs. 16, 17, 20, and 21.</p> <p>N. 89° 55' W., bet. secs. 17 and 20.</p> <p>Over broken desert land, covered with shadscale; desc. over gentle W slope.</p> <p>13.30 Hard surface road, bears S. 46° 40' W. and N. 46° 40' E.; desc. along gentle N slope.</p> <p>39.87 The ¼ sec. cor. of secs. 17 and 20, monumented with a sandstone, 20 x 14 x 3 ins., firmly set 10 ins. in the ground and plainly mkd. ¼ on N face, with steel fence post, 3 lks. N of cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 9 S R 25 E</p> <p style="text-align: center;"> $\frac{1}{4}$ S 17 S 20 1977 </p>


Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
25.90 40.17	<p>Bury the mkd. stone alongside the iron post.</p> <p>_____</p> <p>N. 89° 56' W., beginning new measurement.</p> <p>Continue along gentle N slope.</p> <p>Underground pipeline, bears N. 36° 10' E. and S. 36° 10' W.</p> <p>The cor. of secs. 17, 18, 19, and 20.</p>
39.91	<p>West, bet. secs. 18 and 19.</p> <p>Over broken desert land, covered with shadscale; desc. over W slope.</p> <p>The ¼ sec. cor. of secs. 18 and 19, monumented with a sandstone, 14 x 12 x 6 ins., firmly set 6 ins. in the ground, marks have been obliterated, with mound of stone, N of cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 9 S R 25 E</p> <p style="text-align: center;">¼ $\frac{S 18}{S 19}$</p> <p style="text-align: center;">1977</p>
40.15	<p>Bury the cor. stone alongside the iron post.</p> <p>_____</p> <p>S. 89° 50' W., beginning new measurement.</p> <p>Desc. over W slope.</p> <p>The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of the E. bdy. of T. 9 S., R. 24 E.</p>
40.07	<p>From the cor. of secs. 17, 18, 19, and 20.</p> <p>N. 0° 04' E., bet. secs. 17 and 18.</p> <p>Over broken desert land, covered with shadscale; desc. over NW slope.</p> <p>The ¼ sec. cor. of secs. 17 and 18, monumented with a sandstone, 18 x 5 x 4 ins., firmly set 6 ins. in the ground and plainly mkd. ¼ on W face, with mound of stone, W of cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

T 9 S R 25 E



1977

Bury the mkd. stone alongside the iron post.

N. 0° 06' W., beginning new measurement.

Over broken bench.


37.30 Underground pipeline, bears N. 75° 55' W. and S. 75° 55' E

40.10 The cor. of secs. 7, 8, 17, and 18, monumented with a sandstone, 16 x 6 x 6 ins., firmly set 6 ins. in the ground and plainly mkd. 4 notches on S and 5 notches on E edges, with mound of stone, W of cor.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 9 S R 25 E



1977

Bury the mkd. stone alongside the iron post.

From the cor. of secs. 8, 9, 16, and 17.

N. 89° 29' W., bet. secs. 8 and 17.


Over broken desert land, covered with shadscale; desc. over gentle NW slope.

39.77 The ¼ sec. cor. of secs. 8 and 17, monumented with a sandstone, 12 x 8 x 4 ins., firmly set 6 ins. in the ground and plainly mkd. ¼ on N face, with a mound of stone, N of cor.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 9 S R 25 E



1977

Bury the mkd. stone alongside the iron post and rebuild mound of stone, N of cor.

S. 89° 56' W., beginning new measurement.

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
	Over broken desert land.
23.20	Gravel road, bears NW and SE.
25.72	Intersect line 2 - 3, M.S. 5183, Raffle lode.
	<p>From this intersection, Cor. No. 2, identical with Cor. No. 3, M.S. 5185, Plumed Knight lode, bears S. 60° 19' E., 8.51 chs. dist., determined at record course and distance from bearing object:</p> <p>A cross (X) and 3-5185, chiseled on face of sandstone ledge, bears N. 72° 45' E., 103.7 ft. dist., marks for other bearing object have been obliterated.</p> <p>At the corner point</p> <p>Set a Copperweld, 30 ins. long, 5/8 ins. diam., 24 ins in the ground, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \overline{2-5183} \quad \overline{3-5185} \\ \end{array}$ </div> <p>Place collar of stone around corner; cor. is located on N side of gravel road.</p> <p>From this same intersection point, Cor. No. 3, identical with Cor. No. 2, Black Jack lode, same survey, bears N. 60° 19' W., 14.20 chs. dist., determined at record course and distance from bearing object:</p> <p>A cross (X) and 3-2-5183, chiseled on face of sandstone ledge, bears N. 5° 25' W., 81.5 ft. dist., marks for other bearing objects have been obliterated.</p> <p>At the corner point</p> <p>Set a Copperweld, 30 ins. long, 5/8 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \overline{2-5183} \quad \overline{3-5183} \\ \end{array}$ </div> <p>Place a collar of stone around corner.</p>
30.20	Trench, 30 lks. wide, 50 ft. deep, bears N. 60° W, and S. 60° E.
34.91	Intersect line 1 - 4, M.S. 5183, Raffle lode.
	<p>From this intersection point, Cor. No. 1, identical with Cor. No. 4, M.S. 5185 Plumed Knight lode, bears S. 60° 15' E., 16.35 chs. dist., determined at record course and distance from bearing object:</p> <p>A cross (X) and 1-5183, chiseled on face of sandstone ledge, bears S. 67° 15' W., 131.8 ft. dist., marks for other bearing object not identified.</p> <p>At the corner point</p> <p>Set a Copperweld, 30 ins. long, 5/8 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

1-5183 | 4-5185

Place a collar of stone around corner.

From this same intersection point, Cor. No. 4, identical with Cor. No. 1, Black Jack lode, same survey, bears N. 60° 15' W., 6.38 chs. dist., determined by Grant Boundary method; there is no remaining evidence of the original corner.

At the corner point

Set a Copperweld, 30 ins. long, 5/8 ins. diam., 24 ins. in the ground, with brass cap mkd.

1-5183 | 4-5183

Place a collar of stone around corner.

From this cor., Cor. No. 3, M.S. 5183, Raffle lode, identical with Cor. No. 2, Black Jack lode, same survey, bears N. 31° 38' W., 4.56 chs. dist.

39.73 The cor. of secs. 7, 8, 17, and 18.

N. 89° 58' W., bet. secs. 7 and 18.

Over broken desert land, covered with shadscale; asc. over E slope.

11.20 Underground pipeline, bears N. 75° 55' W. and S. 75° 55' E.

39.94 The 1/4 sec. cor. of secs. 7 and 18, monumented with a sandstone, 12 x 8 x 4 ins., firmly set, 4 ins. in the ground, marks have been obliterated, with mound of stone, N of cor.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 9 S R 25 E

1/4 $\frac{S 7}{S 18}$

1977

Bury cor. stone alongside the iron post and rebuild mound of stone, N of cor.

S. 89° 41' W., beginning new measurement.

Desc. over gentle NW slope.

40.09 The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of the E. bdy. of T. 9 S., R. 24 E.

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

Cor. is located 60 lks. W of small wash, draining NW.

From the cor. of secs. 7, 8, 17, and 18.

N. $0^{\circ} 07' W.$, bet. secs. 7 and 8.

Over broken desert land, covered with shadsale; desc. over NE slope.

2.77 Intersect line 1 - 4, M.S. 5183, Raffle lode.

From this intersection, Cor. No. 1, identical with Cor. No. 4, M.S. 5185 Plumed Knight lode, bears S. $60^{\circ} 15' E.$, 21.91 chs. dist., heretofore described.

From this same intersection, Cor. No. 4, identical with Cor. No. 1, Black Jack lode, same survey, bears N. $60^{\circ} 15' W.$, 0.82 chs. dist., heretofore described.

5.20 Trench, 20 lks. wide, 50 ft. deep, bears N. $60^{\circ} W.$ and S. $60^{\circ} E.$

7.95 Intersect line 2 - 3, M.S. 5183, Black Jack lode.

From this intersection, Cor. No. 2, identical with Cor. No. 3, Raffle lode, same survey, bears S. $62^{\circ} 06' E.$, 1.91 chs. dist., heretofore described.

From this same intersection, Cor. No. 3, identical with Cor. No. 2, M.S. 5184, Wasatch Lode, bears N. $62^{\circ} 06' W.$, 20.82 chs. dist., determined at record course and distance from original bearing objects

A cross (X) and 3-5183 chiseled on face of sandstone ledge, bears N. $13^{\circ} 05' E.$, 119.5 ft. distance.

A cross (X) and 2-5184 chiseled on sandstone boulder, bears N. $28^{\circ} 30' W.$, 129.5 ft. distance.

At the corner point

Set a Copperweld, 28 ins. long, $\frac{5}{8}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

2-5184 | 3-5183

Place mound of stone around the corner, which is located in small wash.

9.70 Gravel road, bears N. $60^{\circ} W.$ and S. $60^{\circ} E.$; asc. over SW slope.

40.04 The $\frac{1}{4}$ sec. cor. of secs. 7 and 8, monumented with a mound of weathered sandstone, these stones are foreign to this area and fit the topographic calls of the original survey. This position is accepted as the best available evidence of the original corner.

At the corner point (center of mound)

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

T 9 S R 25 E

$$\begin{array}{c} \frac{1}{4} \\ | \\ \text{S } 7 \quad | \quad \text{S } 8 \\ | \end{array}$$

1977

Cor. is located about 1.50 chs. E of bulldozed road.

N. $0^{\circ} 15'$ W., beginning new measurement.

Asc. over S slope.

39.83 The cor. of secs. 5, 6, 7, and 8, monumented with a mound of weathered sandstone, dim notches on edge of one stone, stones foreign to this area.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 9 S R 25 E

$$\begin{array}{c} \text{S } 6 \quad | \quad \text{S } 5 \\ \text{S } 7 \quad | \quad \text{S } 8 \end{array}$$

1977

Bury stone with dim marks alongside the iron post.

From the cor. of secs. 4, 5, 8, and 9.

S. $89^{\circ} 47'$ W., bet. secs. 5 and 8.

Over broken desert land, covered with shadscale; desc. over gentle NW slope.

39.85 The $\frac{1}{4}$ sec. cor. of secs. 5 and 8, monumented with a sandstone, 16 x 12 x 3 ins. firmly set 6 ins. in the ground and plainly mkd. $\frac{1}{4}$ on N face, with mound of stone, N of cor.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 9 S R 25 E

$$\frac{1}{4} \begin{array}{c} \text{S } 5 \\ \text{S } 8 \end{array}$$

1977

Bury the mkd. stone alongside the iron post and rebuild mound of stone, N of cor.

N. $89^{\circ} 34'$ W., beginning new measurement.

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS	
39.73	<p>Desc. over gentle NW slope.</p> <p>The cor. of secs. 5, 6, 7, and 8.</p>
39.88	<p>N. 89° 58' W., bet. secs. 6 and 7.</p> <p>Over rolling desert land, covered with shadscale; desc. over gentle NW slope.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 6 and 7, monumented with a weathered sandstone, firmly set, no legible marks, stone foreign to this area, and is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 9 S R 25 E</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S 6}{S 7}$</p> <p style="text-align: center;">1977</p> <p>Bury the cor. stone alongside the iron post; no other accessories.</p>
39.90	<p>N. 89° 54' W., beginning new measurement.</p> <p>Along gentle N slope.</p> <p>The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of the E. bdy. of T. 9 S., R. 24 E.</p>
40.04	<p>From the cor. of secs. 5, 6, 7, and 8.</p> <p>N. 0° 09' W., bet. secs. 5 and 6.</p> <p>Over rolling desert land, covered with shadscale; desc. over gentle NW slope.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 5 and 6, monumented with a weathered sandstone, 16 x 12 x 2 ins., firmly set, 6 ins. in the ground, marks have been obliterated. This is the only stone in this area.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 9 S R 25 E</p> <p style="text-align: center;">$\frac{1}{4}$ S 6 S 5</p> <p style="text-align: center;">1977</p>

Dependent Resurvey of the Subdivisional Lines,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS		
38.09	<p>Set the cor. stone alongside the iron post; no other accessories.</p> <p style="text-align: center;">_____</p> <p>N. 0° 04' W., beginning new measurement.</p> <p>Asc. over gentle S slope.</p> <p>True point for the cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the Tp., from which its witness cor. bears S. 89° 59' E., 2.00 chs. dist., monumented with an iron post, 2 ins. diam., extending 10 ins. above ground, with brass cap mkd. as described in the official record of the 1935 resurvey.</p> <p>Mound of stone, 2 ft. base, 2½ ft. high, N of cor.</p>	
<p>Dependent Resurvey of a Portion of Mineral Survey Nos. 5183 and 5184, T. 9 S., R. 25 E., Salt Lake Meridian, Utah</p>		
<p>(Reestablishment of the Mineral Surveys Executed by Edgar F. Harmston, U.S. Mineral Surveyor, in 1904)</p>		
22.70	<p>From Cor. No. 1, of the Black Jack lode, M.S. No. 5183, identical with Cor. No. 4 of the Raffle lode, same survey, heretofore described.</p> <p>Thence, N. 61° 59' W.</p>	
22.70	<p>Point for Cor. No. 4 of the Black Jack Lode, M.S. 5183, identical with Cor. No. 1 of the Wasatch Lode, M.S. No. 5184, at proportionate distance based on the Grant Boundary Adjustment method; there is no remaining evidence of the original corner. Point not monumented.</p> <p style="text-align: center;">_____</p> <p style="text-align: center;">Wasatch Lode</p> <p>Thence, N. 57° 46' W.</p>	
22.70	<p>Point for Cor. No. 4 of the Wasatch Lode, M.S. No. 5184, identical with Cor. No. 1 of the New York Lode, same survey, at proportionate distance based on the Grant Boundary Adjustment method; there is no remaining evidence of the original corner. Point not monumented.</p> <p style="text-align: center;">_____</p> <p style="text-align: center;">New York Lode</p> <p>Thence, N. 64° 21' W.</p>	
22.71	<p>Cor. No. 4 of the New York Lode, M.S. No. 5184, identical with Cor. No. 1 of the Lorna Doone Lode, same survey, monumented as described in the field notes of the concurrent resurvey of the E. bdy. of T. 9 S., R. 24 E.</p>	
<p>Wasatch Lode</p> <p>From Cor. No. 2 of the Wasatch Lode, M.S. No. 5184, identical with Cor. No. 3 of the Black Jack Lode, M.S. No. 5183, heretofore described.</p>		

Dependent Resurvey of a Portion of
Mineral Survey Nos. 5183 and 5184,
T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

- 22.71 Thence N. 57° 58' W.
Point for Cor. No. 3 of the Wasatch Lode, M.S. No. 5184, identical with Cor. No. 2 of the New York Lode, same survey, at proportionate distance based on the Grant Boundary Adjustment method; there is no remaining evidence of the original corner. Point not monumented.
- New York Lode
- 22.72 Thence N. 64° 33' W.
Point for Cor. No. 3 of the New York Lode, M.S. No. 5184, identical with Cor. No. 2 of the Lorna Doone Lode, same survey, at proportionate distance based on the Grant Boundary Adjustment method; there is no remaining evidence of the original corner. Point not monumented.
- Lorna Doone Lode
- 22.72 Thence N. 60° 58' W.
Cor. No. 3 of the Lorna Doone Lode, M.S. No. 5184, identical with Cor. No. 2 of the Eureka Lode, M.S. No. 5186, monumented as described in the field notes of the concurrent resurvey of the E. bdy. of T. 9 S., R. 24 E.
-
- Dependent Resurvey of a Portion of Allotments Nos. 267 and 268, T. 9 S., R. 25 E., Salt Lake Meridian, Utah
-
- (Reestablishment of the Survey Executed by A.R. Talamantes and H.D. Heist, U.S. Deputy Surveyors, in 1905)
- 34.62 From Cor. No. 8, Allotment No. 268, No. 21, heretofore described.
Thence N. 5° 03' W., along line 8-1.
Cor. No. 1, identical with Cor. No. 3, Allotment No. 267, No. 20, monumented with a sandstone, 16 x 10 x 2 ins., firmly set 6 ins. in the ground and mkd. "No. 3" on NE face and "No. 1" on SW face; other marks have been obliterated.
- 12.39 Thence N. 74° 06' E., along line 3-2 of Allotment No. 267, No. 20.
Cor. No. 2, monumented with a slate stone, 30 x 15 x 4 ins., firmly set 6 ins. in the ground and mkd. "No. 2" on W face; other marks have been obliterated.
This cor. will now function as an amended monument, mkd. AM on stone cor.
- 12.62 Intersect the E. bdy. of the Tp. Point for Cor. No. 2, Allotment No. 267, No. 20.
Set a steel copperweld rod, 30 ins. long, 5/8 ins. diam., 20 ins. in the ground, with brass cap mkd.

JC2
267-20

Dependent Resurvey of a Portion of Allotments Nos. 267
and 268, T. 9 S., R. 25 E., Salt Lake Meridian, Utah

CHAINS

Place a collar of stone around copperweld.

From this cor., Mile Post 210+58.07 bears
N. 0° 36' E., 51.49 chs. dist., heretofore described.

General Description

Township 9 South, Range 25 East, consists mainly of rolling to broken desert land, with the exception of the SE portion of the township which is very ledgy and broken along the White River Canyon. The main road within the township is a hard surface county road, which enters the township on the west boundary of sec. 30, bears NE and leaves the township on the north boundary of sec. 3. There are numerous other dirt and gravel roads within the township used mainly for gilsonite mining and care of gas and oil pipelines which cross the township. The only permanent water noted during the survey was the White River which flows through the SE portion of the township. The elevation of the township varies from about 5000 to 6000 ft. above sea level. There is no permanent habitation within the township.

CERTIFICATE OF SURVEY

~~XX~~(We), Craig P. Sylvester and Ferrel D. Reynolds, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 20th day of May, 19 77, ~~XX~~(We) have retraced the Utah and Colorado State Boundary between mile post 207 and mile post 214, and dependently resurveyed the subdivisional lines and a portion of Allotment Nos. 267, 268 and 270 and a portion of Mineral Survey Nos. 5183 and 5184 of Township 9 South, Range 25 East,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by ~~XX~~, (us) and under ~~XX~~ (our) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

January 26, 1982 (Date) [Signature: Craig P. Sylvester] (Cadastral Surveyor) Supervisory
January 26, 1982 (Date) [Signature: Ferrel D. Reynolds] (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Denver, Colorado

The foregoing field notes of the retracement of the Utah and Colorado State Boundary between mile post 207 and mile post 214, and the dependent resurvey of the subdivisional lines and a portion of Allotment Nos. 267, 268 and 270 and a portion of Mineral Survey Nos. 5183 and 5184 of Township 9 South, Range 25 East of the Salt Lake Meridian, Utah

executed by Craig P. Sylvester, Supervisory Cadastral Surveyor
Ferrel D. Reynolds, Cadastral Surveyor
having been critically examined and found correct, are hereby approved.

June 21, 1982 (Date) [Signature: Glen B. Hatch] (Chief Cadastral Surveyor for Utah)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

[Signature] (Date) [Signature] (Chief Cadastral Surveyor for Utah)

INDEX DIAGRAM

Township 4 South, Range 21 East

		2	1		
6	5	7 4	6 3 4	2	1
		6	5		
7	8	9	10	11	12
13	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision of Section 3 - Page 8
 Subdivision of Section 4 - Page 11

Township 4 South, Range 21 East, Salt Lake Meridian, Utah

CHAINS

The following field notes are those of the dependent resurvey of a portion of the north boundary, a portion of the subdivisional lines and the survey of the subdivisions of secs. 3 and 4, T. 4 S., R. 21 E., Salt Lake Meridian, Utah.

The resurvey and survey were executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and special instructions for Group No. 593, Utah, dated September 21, 1979.

The north boundary was surveyed by A.D. Ferron in 1879, dependently resurveyed by A. Jesson and F. Harmston in 1900 and dependently resurveyed by J.L. Thomas in 1973. The subdivisional lines were surveyed by A.D. Ferron and Buettner in 1879.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The direction of all lines were determined by observations on Polaris and carried forward by sustained angulation and the distances were determined by a Hewlett Packard 3820A electronic distance meter.

The geographic position of the southeast corner of sec. 3 is at Latitude $40^{\circ} 29' 31.86''$ N. and Longitude $109^{\circ} 32' 17.10''$ W., as computed by traverse and section line ties to U.S.G.S. triangulation station "SEC. COR 2NW/4S/21E", identical with the NW corner of sec. 2, T. 4 S., R. 21 E.

The mean magnetic declination is $14^{\circ} 15'$ E.

Dependent Resurvey of a Portion of the North Boundary,
T. 4 S., R. 21 E., Salt Lake Meridian, Utah

(Reestablishment of the Survey Executed by A.D. Ferron, Deputy Surveyor in 1879, and the Resurveys Executed by A. Jesson and F. Harmston, Deputy Surveyors, in 1900 and Jerry L. Thomas, Cadastral Surveyor, in 1973)

Beginning at the cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set in a mound of stone, $4\frac{1}{2}$ ft. base, to top of brass cap, mkd. as described in the official record of the 1973 resurvey.

This cor. is also used to function as U.S.G.S. triangulation station "SEC COR 2NW/4S/21E", with geographic coordinates: Latitude $40^{\circ} 30' 24.047''$ N., Longitude $109^{\circ} 32' 17.631''$ W.

Dependent Resurvey of a Portion of the North Boundary,
T. 4 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
	<p>from which</p> <p>U.S.C. & G.S. horizontal control station "STANAKER", monumented with a standard brass tablet, firmly set in concrete, mkd. and witnessed as published by U.S.C. & G.S., bears S. 68° 51' E., 10.635 chs. dist., with geographic coordinates: Latitude 40° 30' 21.544" N., and Longitude 109° 32' 09.157" W.</p> <p>S. 89° 32' W., bet. secs. 3 and 34.</p> <p>Over rolling land.</p>
4.50	The mean high water mark along the southern shore of Steinaker Reservoir, bears NE and SW; thence across reservoir.
20.21	Point for the E 1/16 sec. cor. of secs. 3 and 34, at proportionate distance; falls in Steinaker Reservoir where it is impractical to establish a permanent monument.
40.42	Point for the 1/4 sec. cor. of secs. 3 and 34, at proportionate distance; falls in Steinaker Reservoir where it is impractical to establish a permanent monument.
49.00	The mean high water mark of the western shore of Steinaker Reservoir, bears NE and SW.
60.63	The W 1/16 sec. cor. of secs. 3 and 34, monumented with an iron post, 2½ ins. diam., firmly set and extending 6 ins. above ground, with brass cap mkd. as described in the official record of the field notes of the 1973 resurvey.
64.00	Power transmission line, bears N. 45° W. and S. 45° E.
72.00	Spur, slopes S.
77.00	Bottom of draw, drains SE.
80.84	The cor. of secs. 3, 4, 33, and 34, monumented with an iron post, 2½ ins. diam., extending 6 ins. above ground, with brass cap mkd. as described in the official record of the field notes of the 1973 resurvey.
	<p>S. 89° 10' W., bet. secs. 4 and 33.</p> <p>Over rolling land, through scattered juniper, sagebrush and shadscale.</p>
1.10	Dirt road, bears NW and SE.
15.00	Dirt road, bears NE and SW.
20.28	Point for the E 1/16 sec. cor. of secs. 4 and 33.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the North Boundary,
T. 4 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
	<p>T 3 S R 21 E</p> <p>E 1/16 $\frac{S\ 33}{S\ 4}$</p> <p>T 4 S R 21 E 1980</p>
	<p>Set a steel fence post, 6 ft. long, alongside the iron post.</p> <p>Cor. is located on N slope in scattered juniper.</p>
40.56	<p>The $\frac{1}{4}$ sec. cor. of secs. 4 and 33, monumented with an iron post, $2\frac{1}{2}$ ins. diam., extending 6 ins. above ground, with brass cap mkd. as described in the official record of the field notes of the 1973 resurvey.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. $89^{\circ} 22'$ W., beginning new measurement.</p>
0.70	Wash, 25 lks. wide, 6 ft. deep, drains NE.
18.25	Power transmission line, bears N. $31^{\circ} 12'$ W. and S. $31^{\circ} 12'$ E.
19.10	Fence, bears N and S.
19.805	<p>The W $\frac{1}{16}$ sec. cor. of secs. 4 and 33, monumented with an iron post, $2\frac{1}{2}$ ins. diam., extending 10 ins. out of a collar of stone, with brass cap mkd. as described in the official record of the field notes of the 1973 resurvey.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. $89^{\circ} 19'$ W., beginning new measurement.</p>
5.20	Dirt road, on curve, bears SW and NW.
8.20	Dirt road, bears NE and SW.
19.33	Fence, bears N and S.
19.865	<p>The cor. of secs. 4, 5, 32, and 33, monumented with a nail in the center of paved road, bearing N and S.</p> <p>from which the 1973 reference monuments</p> <p style="padding-left: 40px;">An iron post, $2\frac{1}{2}$ ins. diam., extending 6 ins. above ground, bears N. 45° E., 46.4 ft. dist., with brass cap mkd. as described in the official record of the field notes of the 1973 resurvey.</p> <p style="padding-left: 40px;">An iron post, $2\frac{1}{2}$ ins. diam., extending 6 ins. above ground, bears S. 45° E., 46.4 ft. dist., with brass cap mkd. as described in the official record of the field notes of the 1973 resurvey.</p>
	<p>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 4 S., R. 21 E., Salt Lake Meridian, Utah</p>
	<p>(Reestablishment of the Survey Executed by Ferron and Buettner in 1879)</p> <hr style="width: 20%; margin: 10px auto;"/>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 4 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS

From the cor. of secs. 2, 3, 10, and 11, monumented with a cobble stone, 12 x 8 x 4 ins., firmly set 8 ins. in the ground and plainly mkd. 2 grooves on E face and 5 grooves on S face.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 4 S R 21 E

S 3	S 2
S 10	S 11

1980

Bury the mkd. stone alongside the iron post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

Cor. is located in fence cor., bearing S and W.

N. 0° 41' W., bet. secs. 2 and 3.

Over pasture and cultivated farm land.

40.43

The ¼ sec. cor. of secs. 2 and 3, monumented with a Uintah County brass cap, 1 in. diam., mkd. T4S R21E ¼ S2 S3 RLS. Old charred cedar post alongside.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, over Uintah County cor., with brass cap mkd.

T 4 S R 21 E

¼	
S 3	S 2

1980

Deposit the charred cedar post alongside the iron post.

Cor. is located in fence cor., bearing N, S and W.

N. 0° 12' W., beginning new measurement.

14.50

Paved road, bears NE and SW.

16.50

Steinaker Service Canal, drains SW.

19.56

The N 1/16 sec. cor. of secs. 2 and 3, monumented with Uintah County chrome pin, ½ in. diam., 6 ins. long, set in a sandstone ledge, and is accepted as a careful and faithful determination of the position of the cor.

At the corner point

Set an iron post, 15 ins. long, 1 in. diam., drilling 6 ins. into solid sandstone, and in a collar of stone, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 4 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
	<p style="text-align: center;">N 1/16</p>
	<p style="text-align: center;">S 3 S 2</p>
	<p style="text-align: center;">1980</p>
	<p>Deposit the chrome pin alongside the iron post.</p>
	<p>Cor. is located on SE slope of broken sandstone reef, 8 lks. W of drainage, draining SE.</p>
	<p>Over broken sandstone reef.</p>
32.75	<p>Top of reef, bears E and W.</p>
33.50	<p>Power transmission line, bears N. 76° E. and S. 76° W.</p>
39.585	<p>The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., heretofore described.</p>
	<p>From the cor. of secs. 2, 3, 10, and 11.</p>
	<p>S. 89° 15' W., bet. secs. 3 and 10.</p>
	<p>Over nearly level pasture and swamp land.</p>
40.24	<p>Point for the ¼ sec. cor. of secs. 3 and 10, at propor- tionate distance; there is no remaining evidence of the original corner.</p>
	<p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>
	<p style="text-align: center;">T 4 S R 21 E</p>
	<p style="text-align: center;">¼ $\frac{S 3}{S 10}$</p>
	<p style="text-align: center;">1980</p>
	<p>Set a pine post, 15 ft. long, alongside the aluminum post.</p>
	<p>Cor. is located in willows 52 lks. E of 10 strand barb wire fence line, bearing N and S.</p>
60.36	<p>Point for the W 1/16 sec. cor. of secs. 3 and 10, falls in Steinaker Service Canal, drains SW. Not monumented.</p>
80.48	<p>The cor. of secs. 3, 4, 9, and 10, monumented with a Uintah County brass cap, 1 in. diam., set flush with paved road, bearing N and S, with brass cap mkd.</p>
	<p style="text-align: center;">T 4 S R 21 E</p>
	<p style="text-align: center;">$\frac{S 4 S 3}{S 9 S 10}$</p>
	<p>Cor. is located in S bound lane. Nelson Marshal, county surveyor, says this point is a remonumentation of the original corner position after the road was put in. This position is accepted as a careful and faithful reestab- lishment of the position of the original corner.</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 4 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS		
	N. 0° 42' W., bet. secs. 3 and 4.	
	Through residential area along paved road.	
9.50	Paved road, bears NE, SW and S.	
20.015	Point for the S 1/16 sec. cor. of secs. 3 and 4.	
	Set an iron post, 15 ins. long, 1 in. diam., drilled 7 ins. into solid sandstone, with brass cap mkd.	
	S 1/16	
	S 4 S 3	
	1980	
	Cor. is located on SE slope in scattered junipers.	
40.03	The ¼ sec. cor. of secs. 3 and 4, monumented with a Uintah County brass cap, 1 in. diam., on ½ in. steel rod in a mound of stone, with brass cap mkd. RLS Uintah County survey, and is accepted as a careful and faithful perpetuation of the position of the original corner.	
	At the corner point	
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground over county cor., and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.	
	T 4 S R 21 E	
	¼ 	
	S 4 S 3 	
	1980	
	Cor. is located on N slope and in the cor. of an old down fence line, bearing E, W, N, and S.	

	N. 0° 42' W., beginning new measurement.	
6.50	Steinaker Feeder Canal, bears NE and SW.	
19.98	Point for the N 1/16 sec. cor. of secs. 3 and 4, not monumented.	
40.38	The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., heretofore described.	
	From the cor. of secs. 3, 4, 9, and 10.	
	S. 89° 22' W., bet. secs. 4 and 9.	
	Over residential area.	
17.50	Paved road, bears NE and SW.	
20.12	Point for the E 1/16 sec. cor. of secs. 4 and 9.	
	Set an iron post, 15 ins. long, 1 in. diam., drilled 9 ins. into solid sandstone, with brass cap mkd.	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 4 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS

T 4 S R 21 E

E 1/16 $\frac{S 4}{S 9}$

1980

Cor. is located above homes on 30 ft. sandstone ledge,
sloping SE.

- 40.24 The $\frac{1}{4}$ sec. cor. of secs. 4 and 9, monumented with a Uintah
County brass cap, 1 in. diam., on $\frac{1}{2}$ in. steel rod, set
flush with the ground on the N edge of a four strand
barb wire fence cor., bearing S and W, and is accepted
as a careful and faithful perpetuation of the position
of the original corner.

At the corner point

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, over Uintah County cor., with aluminum
cap mkd.

T 4 S R 21 E

 $\frac{1}{4}$ $\frac{S 4}{S 9}$

1980

Cor. is located on top of clay ridge, bearing NE and SW.

S. $89^{\circ} 30'$ W., beginning new measurement.

Over residential area.

- 40.30 The cor. of secs. 4, 5, 8, and 9, monumented with a bolt
set flush with the pavement on bridge over Rockpoint
canal which drains E. Paved road, bears N and S. This
point is being used as the cor. point by local land
owners and the county surveyor and is accepted as the best
available evidence of the original corner position.

from which

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 24
ins. in the ground, 3 lks. N of chain link fence
cor., which bears E and S for a reference monument,
bears S. $40^{\circ} 56'$ E., 61.7 lks. dist., with brass
cap mkd. RM T4S R21E S9 40.7 FT 1980 and an arrow
pointing to true cor. point.

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 24
ins. in the ground alongside telephone pole, for
a reference monument, bears S. $70^{\circ} 41'$ W., 47 lks.
dist., with brass cap mkd. RM T4S R21E S8 31 FT
1980, with arrow pointing to true cor. point.

The cor. is located at the intersection of 2500 North
and 2500 West streets.

N. $0^{\circ} 30'$ W., bet. secs. 4 and 5.

Through residential area.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 4 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
13.50	Steinaker Feeder Canal, bears E and W.
40.03	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 28 ins. in the ground, flush with paved road, with brass cap mkd.
<p>T 4 S R 21 E</p> <p>$\frac{1}{4}$</p> <p>S 5 S 4</p> <p>1980</p>	
	Cor. is located on E edge of paved road in cut in clay hill.
60.045	Point for the N $\frac{1}{16}$ sec. cor. of secs. 4 and 5, not monumented.
64.00	Dirt road, bears NE and SW.
80.16	The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., heretofore described.
<p>Survey of the Subdivision of Section 3, T. 4 S., R. 21 E., Salt Lake Meridian, Utah</p>	
	From the $\frac{1}{4}$ sec. cor. of secs. 3 and 10. N. $0^{\circ} 35'$ W., on the N and S center line of sec. 3.
20.115	Point for the center S $\frac{1}{16}$ sec. cor. of sec. 3, not monumented.
30.50	Steinaker Service Canal, drains SW.
32.50	Paved road, bears NE and SW.
40.23	Point for the center $\frac{1}{4}$ sec. cor. of sec. 3, at intersection with the E and W center line. Set an iron post, 15 ins. long, 1 in. diam., drilled 12 ins. into solid sandstone, with brass cap mkd.
<p>T 4 S R 21 E</p> <p>C $\frac{1}{4}$ S 3</p> <p>1980</p>	
	Cor. is located in drainage, draining SE at base of ledge, 18 ft. high, bearing NW and SE.
60.00	Point for the center N $\frac{1}{16}$ sec. cor. of sec. 3. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd.

Survey of the Subdivision of Section 3,
T. 4 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS

C
|
N 1/16 | S 3
|
C
1980

Cor. is located on N slope in scattered junipers.

64.50 Power transmission line, bears N. 76° E. and S. 76° W.

66.50 Steinaker Reservoir mean high water mark on southern shore, bears E and W.

80.215 Point for the ¼ sec. cor. of secs. 3 and 34.

From the ¼ sec. cor. of secs. 2 and 3.

S. 88° 58' W., on the E and W center line of sec. 3.

20.08 Point for the center E 1/16 sec. cor. of sec. 3.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

E 1/16
C ————— C
S 3
1980

Cor. is located in cultivated land, 3 lks. S of netwire fence line, bearing E and W.

20.24 Netwire fence line, bears N and S.

26.00 Paved road, bears NE and SW.

28.00 Steinaker Service Canal, drains SW.

40.16 The center ¼ sec. cor. of sec. 3.

60.325 Point for the center W 1/16 sec. cor. of sec. 3.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

W 1/16
C ————— C
S 3
1980

Raise a mound of stone, 3½ ft. base, 2 ft. high, N of cor.

Cor. is located on N slope in scattered scrub juniper trees.

80.49 The ¼ sec. cor. of secs. 3 and 4.

From the center E 1/16 sec. cor. of sec. 3.

Survey of the Subdivision of Section 3,
T. 4 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
	N. 0° 24' W., on the N and S center line of the NW $\frac{1}{4}$.
3.00	Paved road, bears NE and SW.
4.50	Steinaker Service Canal, drains SW.
19.66	Point for the NE 1/16 sec. cor. of sec. 3, at intersection with the E and W center line of the NE $\frac{1}{4}$.
	Set an aluminum post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., over cross on solid sandstone, in a mound of stone, 6 $\frac{1}{2}$ ft. base, to aluminum cap, mkd.
	NE 1/16 S 3
	1980
	Cor. is located on S slope in scattered juniper trees.
29.00	Power transmission line, bears N. 76° E. and S. 76° W.
34.00	Steinaker Reservoir mean high water mark on southern shore, bears SE and NW.
39.78	Point for the E 1/16 sec. cor. of secs. 3 and 34, on the N. bdy. of the Tp.
	From the N 1/16 sec. cor. of secs. 2 and 3.
	S. 89° 16' W., on the E and W center line of the NE $\frac{1}{4}$ of sec. 3.
20.14	The NE 1/16 sec. cor. of sec. 3.
40.28	The center N 1/16 sec. cor. of sec. 3.
	From the point for the W 1/16 sec. cor. of secs. 3 and 10.
	N. 0° 39' W., on the N and S center line of the SW $\frac{1}{4}$ of sec. 3.
20.065	Point for the SW 1/16 sec. cor. of sec. 3, at intersection with the E and W center line of the SW $\frac{1}{4}$.
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	SW 1/16 S 3
	1980
	Set a 5 ft. cottonwood post alongside the iron post.
	Cor. is located on gentle SE slope in greasewood.
21.50	Paved road, bears NE and SW.
39.60	Ridge, bears E and W.
40.13	The center W 1/16 sec. cor. of sec. 3

Survey of the Subdivision of Section 3,
T. 4 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
	From the point for the center S 1/16 sec. cor. of sec. 3.
	S. 89° 06' W., on the E and W center line of the SW $\frac{1}{4}$ of sec. 3.
11.50	Steinaker Service Canal, drains SW.
20.145	The SW 1/16 sec. cor. of sec. 3.
23.50	Paved road, bears NE and SW.
40.29	The S 1/16 sec. cor. of secs. 3 and 4.
	From the center W 1/16 sec. cor. of sec. 3.
	N. 0° 39' W., on the N and S center line of the NW $\frac{1}{4}$ of sec. 3.
19.30	Dirt road, bears NE and SW.
19.875	Point for the NW 1/16 sec. cor. of sec. 3, at inter- section with the E and W center line of the NW $\frac{1}{4}$.
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.
	NW 1/16 S 3
	1980
	Cor. is located on right bank of canal, draining NE.
20.22	Center of Steinaker Feeder Canal, 2 ft. deep, 30 lks. wide, draining NE.
24.00	Steinaker Reservoir mean high water mark, bears SE and NW.
27.50	Steinaker Reservoir mean high water mark, bears NE and SW.
40.185	The W 1/16 sec. cor. of secs. 3 and 34, on the N. bdy. of the Tp.
	From the center N 1/16 sec. cor. of sec. 3.
	S. 89° 16' W., on the E and W center line of the NW $\frac{1}{4}$ of sec. 3.
19.50	Dirt road, bears NE and SW.
20.19	The NW 1/16 sec. cor. of sec. 3.
21.00	Steinaker Feeder Canal, drains NE.
40.38	The point for the N 1/16 sec. cor. of secs. 3 and 4.
	Survey of the Subdivision of Section 4, T. 4 S., R. 21 E., Salt Lake Meridian, Utah
	From the $\frac{1}{4}$ sec. cor. of secs. 4 and 9.
	N. 0° 57' W., on the N and S center line of sec. 4.

Survey of the Subdivision of Section 4,
T. 4 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
6.50	Paved road, bears NE and SW.
19.85	Dirt road, bears E and W.
20.04	Point for the center S 1/16 sec. cor. of sec. 4.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} C \\ \\ S\ 1/16 \quad \quad S\ 4 \\ \\ C \end{array}$
	1980
	Set a pine post, 6 ft. long, alongside the iron post.
	Cor. is located on right bank of Steinaker Feeder Canal, draining E.
40.01	Net wire fence, bears E and W, 8 lks. to fence cor., from which fences bear S and E.
40.08	Point for the center ¼ sec. cor. of sec. 4, at intersection with the E and W center line.
	Set an iron post, 30 ins. long, 2½ ins. diam., 30 ins. in the ground, with brass cap mkd.
	T 4 S R 21 E
	C ¼ S 4
	1980
	Cor. is located in front yard of ranch house.
60.10	Four strand barb wire fence, bears E and W.
60.12	Point for the center N 1/16 sec. cor. of sec. 4, determined by a rebar, ½ in. diam. This point is being used by adjacent land owners and is accepted as a careful and faithful determination of the position of the corner.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, 1½ ft. high, to top of aluminum cap, mkd.
	$\begin{array}{c} C \\ \\ N\ 1/16 \quad \quad S\ 4 \\ \\ C \end{array}$
	1980
	Cor. is located on SE slope of clay hill in scrub juniper trees.
71.00	Dirt road, bears NE and SW.
80.26	The ¼ sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp.

Survey of the Subdivision of Section 4,
T. 4 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 3 and 4.</p> <p>S. $89^{\circ} 26'$ W., on the E and W center line of sec. 4.</p>
9.50	Steinaker Feeder Canal, drains NE.
20.20	Point for the center E $\frac{1}{16}$ sec. cor. of sec. 4, not monumented.
40.40	The center $\frac{1}{4}$ sec. cor. of sec. 4.
60.395	Point for the center W $\frac{1}{16}$ sec. cor. of sec. 4, not monumented.
80.39	The $\frac{1}{4}$ sec. cor. of secs. 4 and 5.
	<p>From the point for the center E $\frac{1}{16}$ sec. cor. of sec. 4.</p> <p>N. $0^{\circ} 50'$ W., on N and S center line of the NE $\frac{1}{4}$ of sec. 4.</p>
20.01	<p>Point for the NE $\frac{1}{16}$ sec. cor. of sec. 4, at intersection with the E and W center line of the NE $\frac{1}{4}$.</p> <p>Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">NE $\frac{1}{16}$ S 4</p> <p style="text-align: center;">1980</p> <p>Cor. is located in cultivated land.</p>
37.50	Dirt road, bears NE and SW.
40.285	The E $\frac{1}{16}$ sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp.
	<p>From the point for the N $\frac{1}{16}$ sec. cor. of secs. 3 and 4.</p> <p>S. $89^{\circ} 32'$ W., on the E and W center line of the NE $\frac{1}{4}$ of sec. 4.</p>
20.24	The NE $\frac{1}{16}$ sec. cor. of sec. 4.
40.48	The center N $\frac{1}{16}$ sec. cor. of sec. 4.
	<p>From the E $\frac{1}{16}$ sec. cor. of secs. 4 and 9.</p> <p>N. $0^{\circ} 50'$ W., on the N and S center line of the SE $\frac{1}{4}$ of sec. 4.</p>
20.025	<p>Point for the SE $\frac{1}{16}$ sec. cor. of sec. 4, at intersection with the E and W center line of the SE $\frac{1}{4}$.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">SE $\frac{1}{16}$ S 4</p> <p style="text-align: center;">1980</p>

Survey of the Subdivision of Section 4,
T. 4 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
	Cor. is located in hollow, draining W.
20.90	Paved road, bears NE and SW.
32.00	Steinaker Feeder Canal, drains NE.
40.05	The point for the center E 1/16 sec. cor. of sec. 4.
	From the S 1/16 sec. cor. of secs. 3 and 4.
	S. 89° 24' W., on the E and W center line of the SE $\frac{1}{4}$ of sec. 4.
20.16	The SE 1/16 sec. cor. of sec. 4.
21.00	Paved road, bears NE and SW.
40.32	The center S 1/16 sec. cor. of sec. 4.
	From the point for the center W 1/16 sec. cor. of sec. 4.
	N. 0° 41' W., on the N and S center line of the NW $\frac{1}{4}$ of sec. 4.
20.025	Point for the NW 1/16 sec. cor. of sec. 4, at intersection with the E and W center line of the NW $\frac{1}{4}$.
	Set an aluminum post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	NW 1/16 S4
	1980
	Cor. is located on N side of pole fence cor., bearing E, S and W.
36.50	Dirt road, bears NE and SW.
40.16	The W 1/16 sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp.
	From the center N 1/16 sec. cor. of sec. 4.
	S. 89° 23' W., on the E and W center line of the NW $\frac{1}{4}$ of sec. 4.
19.90	The NW 1/16 sec. cor. of sec. 4.
39.83	The point for the N 1/16 sec. cor. of secs. 4 and 5.
	General Description
	The area surveyed and resurveyed within secs. 3 and 4, T. 4 S., R. 21 E., is located 3 miles N of Vernal, Utah. The elevation varies from 5400 ft. to 5850 ft. The SE and NW portions are farm and pasture land with a sandstone reef projecting from the SW portion of the sections to the NE cor. of sec. 3. There are homes scattered throughout the two sections. Steinaker Reservoir is located in the north portion of sec. 3.
	The mean magnetic declination is N. 14 1/4° E.

CERTIFICATE OF SURVEY

(I) ~~(We)~~, Gail E. Reynolds, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 21st day of September, 19 79, (I) ~~(We)~~ have dependently resurveyed a portion of the north boundary, a portion of the subdivisional lines and surveyed the subdivisions of sections 3 and 4, T. 4 S., R. 21 E.,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

January 4, 1982
(Date) *Gail E Reynolds*
Supervisory (Cadastral Surveyor)

(Date) _____
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the north boundary, a portion of the subdivisional lines and the survey of the subdivisions of sections 3 and 4 of T. 4 S., R. 21 E., Salt Lake Meridian, Utah

executed by Gail E. Reynolds, Supervisory Cadastral Surveyor
having been critically examined and found correct, are hereby approved.

MAR 31 1982
(Date) *Mary L. Speight*
ACTING (Chief, Cadastral Survey Examination and Approval Staff)

~~CERTIFICATE OF TRANSCRIPT~~

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____ is a true copy of the original field notes.

R602

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF A PORTION OF THE SOUTH BOUNDARY

AND SUBDIVISIONAL LINES,

AND THE

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES

AND SUBDIVISION OF SECTION 33

OF

TOWNSHIP 18 SOUTH, RANGE 4 WEST

Of the Salt Lake Meridian,

In the State of Utah

EXECUTED BY

Craig P. Sylvester Supervisory Cadastral Surveyor

Under special instructions dated January 15, 19 81, approved January 19, 1981,

_____, which provided for the surveys included under ~~U.S. Survey~~/Group
Number 611, and assignment instructions dated January 19, 19 81.

Survey commenced February 17, 19 81

Survey completed February 29, 19 81

700

INDEX DIAGRAM

Township 18 South, Range 4 West

6	5	4	3	2	1
7	8	9	10	11	12
13	14	15	16	17	18
19	20	21	22	23	24
25	26	27	28	29	30
31	32	2 33 1	5 34	35	36

Subdivision of Section 33

- Page 5

Township 18 South, Range 4 West, Salt Lake Meridian, Utah

CHAINS

A portion of the south boundary was surveyed by Elliot Bird in 1925 and portions of the subdivisional lines surveyed by Ferdinand Dickert in 1870 and A.J. Stewart in 1874.

The following field notes are those of a dependent resurvey of a portion of the south boundary, and subdivisional lines and the survey of a portion of the subdivisional lines and subdivision of Section 33, Township 18 South, Range 4 West, Salt Lake Meridian, Utah.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group 611, Utah, dated January 15, 1981.

The directions of the lines of this survey were determined by reference to true meridians established on line by hour angle observations on Polaris. They were carried forward by sustained angulation, being supplemented by numerous other observations on Polaris taken throughout the progress of the survey. Measurements were determined by electronic means.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the southeast corner of Section 33, as scaled from U.S.G.S. quadrangle sheet "Holden", 15' series, is as follows:

Latitude $39^{\circ} 11' 55''$ N. Longitude $112^{\circ} 17' 45''$ W.

The mean magnetic declination is $14^{\circ} 40'$ E.

Dependent Resurvey of a Portion of the South Boundary,
T. 18 S., R. 4 W., Salt Lake Meridian, Utah

(Restoring the 1925 Survey Executed by Elliot Bird)

Beginning at the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set and extending 10 ins. above ground, with brass cap mkd. as described in the official record of the 1925 survey of the N. bdy. of T. 19 S., R. 4 W.

N. $89^{\circ} 22'$ W., bet. secs. 4 and 33.

Over rolling hills, covered with juniper and pinon.

41.58 The $\frac{1}{4}$ sec. cor. of secs. 4 and 33, monumented with an iron post, 1 in. diam., firmly set and extending 10 ins. above ground, with brass cap mkd. as described in the official record of the 1925 survey of the N. bdy. of T. 19 S., R. 4 W.

N. $89^{\circ} 22'$ W., beginning new measurement.

Continue over rolling hills.

Dependent Resurvey of a portion of the South Boundary,
T. 18 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS	
32.00	Improve gravel road, bears NNW, SSE and W; enter farm land.
32.52	Old fence line, bears N. 23° 00' W.
40.04	Point for the cor. of secs. 4, 5, 32, and 33, determined by an E and W gravel road and fence line from the north and is accepted as the best available evidence of the position of the original corner. Bury glass 12 ins. below road surface. from which An aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, for a reference monument, bears N. 3° 45' E., 31.8 lks. dist., with aluminum cap mkd. T18S R4W S33 RM 21 FT 1981 and an arrow pointing to the cor. An aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, for a reference monument, bears N. 44° 48' W., 43.9 lks. dist., with aluminum cap mkd. T18S R4W S32 RM 29FT 1981 and an arrow pointing to the cor.
Dependent Resurvey of a Portion of the Subdivisional Lines, T. 18 S., R. 4 W., Salt Lake Meridian, Utah	
(Restoring the 1874 Survey Executed by A.J. Stewart Jr.)	
	From the point for the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., hereinbefore described. N. 0° 33' W., bet. secs. 32 and 33. Over nearly level farm land.
18.05	Old fence line, bears N. 23° 00' W. and S. 23° 00' E.
19.80	Improved gravel road, bears NNW and SSE.
20.315	Point for the S 1/16 sec. cor. of secs. 32 and 33. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 18 S R 4 W S 1/16 S 32 S 33 1981
	Set a juniper post alongside the iron post.
40.63	The ¼ sec. cor. of secs. 32 and 33, monumented with a sandstone, 16 x 8 x 8 ins., firmly set 8 ins. in the ground and plainly mkd. ¼ on W face. At the corner point Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS	
39.69	<p style="text-align: center;">T 18 S R 4 W</p> <p style="text-align: center;"> $\frac{1}{4}$ S 32 S 33 </p> <p style="text-align: center;">1981</p> <p>Bury the mkd. stone and set a juniper post alongside the aluminum post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 42' W., beginning new measurement.</p> <p>Over nearly level land.</p> <p>The cor. of secs. 28, 29, 32, and 33, determined at fence cor., from which fences bear S and W. This position is harmoniously related with existing original cors. and is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 18 S R 4 W</p> <p style="text-align: center;"> S 29 S 28 S 32 S 33 </p> <p style="text-align: center;">1981</p>
38.86	<p>From the ¼ sec. cor. of secs. 27 and 34, monumented with a sandstone, 16 x 8 x 8 ins., firmly set in a mound of stone, plainly mkd. ¼ on N face. This cor. will now function as the ¼ sec. cor. of sec. 27 only.</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">T 18 S R 4 W</p> <p style="text-align: center;"> $\frac{1}{4}$ S 27 </p> <p style="text-align: center;">1981</p> <p>Bury the mkd. stone alongside the aluminum post.</p> <p>S. 89° 56' W., along the S. bdy. of sec. 27.</p> <p>Over rolling land, through scattered juniper and sagebrush.</p>
40.33	<p>The closing cor. of secs. 33 and 34, hereinafter described.</p>
40.33	<p>The cor. of secs. 27, 28, 33, and 34, monumented with a quartz stone, 20 x 12 x 8 ins., firmly set 10 ins. in the ground, and plainly mkd. 1 notch on S and 3 notches on E edges. This cor. will now function as the cor. of secs. 27 and 28 only.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 18 S R 4 W

$\frac{S\ 28}{S\ 33}$ | $\frac{S\ 27}{S\ 33}$

1981

Bury the mkd. stone alongside the aluminum post.

Cor. is located in N and S fence line.

N. 89° 31' W., along the S. bdy. of sec. 28.

Over rolling land, through scattered juniper and sagebrush.

20.205 Point for the E 1/16 sec. cor. of secs. 28 and 33.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 18 S R 4 W

E 1/16 $\frac{S\ 28}{S\ 33}$

1981

Set a juniper post alongside the iron post.

40.41 The ¼ sec. cor. of secs. 28 and 33, determined by the original bearing tree and old mound of stone. No marks identified on stones.

from which the original bearing tree

A cedar, 10 ins. diam., bears N. 45° 00' W., 118 lks. dist., scribe marks partly grown over.

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 28 S R 4 W

$\frac{1}{4}$ $\frac{S\ 28}{S\ 33}$

1981

S. 88° 37' W., beginning new measurement.

Over rolling land.

40.62 The cor. of secs. 28, 29, 32, and 33.

Survey of a Portion of the Subdivisional Lines
T. 18 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS

Survey of a Portion of the Subdivisional Lines,
T. 18 S., R. 4 W., Salt Lake Meridian, Utah

From the cor. of secs. 3, 4, 33, and 34, on the S. bdy.
of the Tp., hereinbefore described.

North, bet. secs. 33 and 34.

Over rolling land, covered with juniper and pinon.

41.86 Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34, at 40.00
chs. of southing from the closing cor. of secs. 33 and
34.

Set an aluminum post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins.
in the ground to bedrock, in a mound of stone, 4 ft. base,
to top of aluminum cap, mkd.

T 18 S R 4 W

$\frac{1}{4}$
 |
 S 33 | S 34
 |

1981

81.86 Intersect the S. bdy. of sec. 27.

Point for the closing cor. of secs. 33 and 34.

Set an aluminum post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, and in a collar of stone, with aluminum
cap mkd.

T 18 S R 4 W

S 27
 ———
 S 33 | S 34
 C C

1981

Set a juniper post alongside the aluminum post.

From this closing cor., the cor. of secs. 27 and 28,
bears S. $89^{\circ} 56'$ W., 1.47 chs. dist.

Survey of the Subdivision of Section 33,
T. 18 S., R. 4 W., Salt Lake Meridian, Utah

From the $\frac{1}{4}$ sec. cor. of secs. 4 and 33, on the S. bdy.
of the Tp., hereinbefore described.

N. $0^{\circ} 12'$ W., on the N and S center line of sec. 33.

21.23 Point for the center S $\frac{1}{16}$ sec. cor. of sec. 33, at
20.00 chs. of southing from the center $\frac{1}{4}$ sec. cor. of
sec. 33.

Set an aluminum post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins.
in the ground, and in a collar of stone, with aluminum
cap mkd.

Survey of a Portion of the Subdivision of Section 33,
T. 18 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS		
	<p style="text-align: center;">T 18 S R 4 W</p> <p style="text-align: center;">C S 1/16 S 33 C</p> <p style="text-align: center;">1981</p>	
41.23	<p>Cor. is located on W slope of spur.</p> <p>Point for the center $\frac{1}{4}$ sec. cor. of sec. 33, at intersection with the E and W center line.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>	
81.74	<p style="text-align: center;">T 18 S R 4 W</p> <p style="text-align: center;">C $\frac{1}{4}$ S 33</p> <p style="text-align: center;">1981</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 28 and 33.</p>	
21.73	<p>From the $\frac{1}{4}$ sec. cor. of secs. 33 and 34.</p> <p>S. $89^{\circ} 46'$ W., on the E and W center line of sec. 33.</p> <p>Point for the center E $\frac{1}{16}$ sec. cor. of sec. 33, at 20.00 chs. of easting from the center $\frac{1}{4}$ sec. cor. of sec. 33.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	
41.73	<p style="text-align: center;">T 18 S R 4 W</p> <p style="text-align: center;">E 1/16</p> <p style="text-align: center;">C ——— S 33 ——— C</p> <p style="text-align: center;">1981</p> <p>The center $\frac{1}{4}$ sec. cor. of sec. 33.</p>	
82.00	<p>The $\frac{1}{4}$ sec. cor. of secs. 32 and 33.</p>	
40.26	<p>From the center E $\frac{1}{16}$ sec. cor. of sec. 33.</p> <p>N. $0^{\circ} 05'$ E., on the N and S center line of the NE$\frac{1}{4}$ of sec. 33.</p> <p>The E $\frac{1}{16}$ sec. cor. of secs. 28 and 33.</p>	
40.15	<p>From the center S $\frac{1}{16}$ sec. cor. of sec. 33.</p> <p>S. $89^{\circ} 20'$ W., on the E and W center line of the SW$\frac{1}{4}$ of sec. 33.</p> <p>The S $\frac{1}{16}$ sec. cor. of secs. 32 and 33.</p>	

T. 18 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS	General Description
	<p>Section 33, T. 18 S., R. 4 W., consists of small rolling hills covered with scattered juniper and pinon, with a small valley in the east part of the section used for dry land wheat farming. There are several dirt roads crossing the section. There is no permanent water or habitation within the section.</p>

CERTIFICATE OF SURVEY

(I) ~~(We)~~, Craig P. Sylvester, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 15th day of January, 1981, (I) ~~(We)~~ have dependently resurveyed a portion of the south boundary and subdivisional lines and surveyed a portion of the subdivisional lines, and subdivided section 33, Township 18 South, Range 4 West,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), ~~(XX)~~ and under (my) ~~(XX)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

January 6, 1982
(Date)

Craig P. Sylvester
(Cadastral Surveyor)
Supervisory

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the south boundary and subdivisional lines and the survey of a portion of the subdivisional lines, and subdivision of section 33, Township 18 South, Range 4 West, Salt Lake Meridian, Utah

executed by Craig P. Sylvester, Supervisory Cadastral Surveyor having been critically examined and found correct, are hereby approved.

MAR 31 1982
(Date)

Mary T. Oriatt
ACTING (Chief, Cadastral Survey Examination and Approval Staff)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief, Cadastral Survey Examination and Approval Staff)~~

INDEX DIAGRAM

Township 41 S., Range 13 W.

	6	5	3	2
6	5 53	4 43	8 33	2 26
	51	50	42	1 17
				25
7	8 51	9 41	10 33	11 24
67	66	49	40	12 15
				23
18 64	17 48	16 39	15 32	14 22
63	63	48	38	13 14
				21
19 61	20 47	21 37	22 30	23 21
59	58	46	36	24 14
				20
60 80 57	29 45	28 35	27 28	26 19
55	55	44	35	25 12
				19
57 81 54	32 44	33 34	34 27	35 18
11	9	9	8	36
				7

Township 41 South, Range 13 West, Salt Lake Meridian, Utah

CHAINS

T. 41 S., R. 13 W.

History of Surveys

<u>Surveyed by</u>	<u>Retr. or Resurveyed by</u>
--------------------	-------------------------------

NORTH BOUNDARY (Eighth Standard Parallel South)

W. 4½ mi.	Julien Bausman	1870	
E. ½ mi.,			
Sec. 2	J.G. Burrill	1877	
W. 4 mi.			H.D. Heist 1902
E. 1 mi.	Jenkins and West		
		1897	
W. 5 mi.			Jenkins and West 1897
N. Bdy., Sec. 6			R.C. Yundt 1949

EAST BOUNDARY

S. 4 mi.	Bailey and Burrill		
		1877	
N. 2 mi.	Jenkins and West		
		1897	
S. 4 mi.			Jenkins and West 1897
E. Bdy., Sec. 24			R.E.L. Collier 1909

WEST BOUNDARY (Second Guide Meridian West)

All	Joseph Gorlinski		
		1870	
N. 1 mi.			Bailey and Burrill 1877
All			Jenkins and West 1897
S. 2 mi.			H.G. Mason 1918-1919
W. bdy., Sec. 7			
and N½ W. Bdy., Sec. 18			A. Nelson 1931
N. 2½ mi.			R.C. Yundt 1949

SOUTH BOUNDARY

All	Bailey and Burrill		
		1877	
All			Jenkins and West 1897
S. bdy., sec. 35			Stewart and Snow 1909

SUBDIVISIONS

Portion	Joseph Gorlinski		
		1870	
Portion	Bailey and Burrill		
		1877	
Portion			Jenkins and West 1897
Completion	Jenkins and West		
		1897	
Sec. 7			A. Nelson 1931
Sec. 6			R.C. Yundt 1949

The following field notes are those of a dependent resurvey of a portion of the south boundary of T. 40 S., R. 13 W. (Eighth Standard Parallel South) a portion of the south and east boundaries and a portion of the subdivisional lines of T. 41 S., R. 13 W., Salt Lake Meridian, Utah.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 578, Utah, dated March 29, 1978.

Township 41 South, Range 13 West, Salt Lake Meridian, Utah

CHAINS

The directions of the lines of this survey were determined by reference to the true meridians established on line by hour angle observations on Polaris. They were carried forward by sustained angulation, being supplemented by numerous other observations on Polaris taken throughout the progress of the survey.

Distances were determined by electronic measurement along surveyed lines.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were re-monumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the southeast corner of section 35 as scaled from U.S. Geological Survey map, "La Verkin 3 N.E., Utah" is as follows:

Latitude 37° 10.2' N. Longitude 113° 16.4' W.

The mean magnetic declination is 14° 30' E.

Dependent Resurvey of a Portion of the S. Bdy.,
(Eighth Standard Parallel South),
T. 40 S., R. 13 W., Salt Lake Meridian, Utah

(Restoring the 1897 Survey by Jenkins and West)

Beginning at the standard cor. of Tps. 40 S., Rs. 12 and 13 W., monumented with an iron post, 3 ins. diam., extending 12 ins. out of the ground, with brass cap mkd. as described in the official record of the 1909 survey of the Eighth Standard Parallel South through R. 12 W.

S. 89° 51' W., along S. bdy. of sec. 36.

Over broken mountain land, through sagebrush, shadscale and scattered cedar trees; asc. E slope.

39.64

The standard ¼ sec. cor. of sec. 36, common with the ¼ sec. cor. of sec. 1, T. 41 S., R. 13 W., monumented with a limestone, 20 x 10 x 8 ins., extending 12 ins. out of the ground, plainly mkd. SC ¼ on N face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.

S C
T 40 S R 13 W

¼ $\frac{S\ 36}{S\ 1}$

T 41 S
1978

Dependent Resurvey of a Portion of the S. Bdy.,
(Eighth Standard Parallel South),
T. 40 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS

- Deposit the mkd. stone in mound alongside the iron post.
- S. 89° 50' W., beginning new measurement.
- Desc. over W slope.
- 39.87 The standard cor. of secs. 35 and 36, common with the cor. of secs. 1 and 2, T. 41 S., R. 13 W., monumented with a stationary sandstone ledge, 4 x 3 x 2 ft. above ground, plainly mkd. SC with 5 grooves on W side of cross and 1 groove on E, located on W rim of ledge.
- from which
- An iron post, 28 ins. long, 2½ ins. diam., set on solid sandstone and in a mound of stone, 3½ ft. base, to top for reference monument, bears S. 89° 50' W., 0.01 chs. dist., with brass cap mkd. RM T40S R13W S1 S2 S35 S36 T41S 1978 and an arrow pointing to the cor.
- Cor. is located 1.00 ch. E of ravine, drains N.
- (Restoring the Survey by J. Bausman in 1870 and the Retracement by H.D. Heist in 1902)
- From the standard cor. of secs. 34 and 35, common with the cor. of secs. 2 and 3, T. 41 S., R. 13 W., monumented with an iron post, 2½ ins. diam., extending 12 ins. out of ground and in a mound of stone, 3½ ft. base, with Washington County brass cap, mkd.
- | | |
|--------|------|
| R 13 W | |
| T 40 S | |
| S 34 | S 35 |
| S 3 | S 2 |
- T 41 S
1974
- A lava rock, 30 x 12 x 8 ins., mkd. 2 and 4 notches, in mound alongside the iron post.
- N. 89° 37' W., along the S. bdy. of sec. 34.
- Over rocky lava ridge, through sagebrush and scattered cedar trees; asc. E slope.
- 20.42 Point for the standard E 1/16 sec. cor. of sec. 34, common with the E 1/16 sec. cor. of sec. 3, T. 41 S., R. 13 W.
- Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the S. Bdy.,
 (Eighth Standard Parallel South),
 T. 40 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS

S C
 T 40 S R 13 W

E 1/16 $\frac{S\ 34}{S\ 3}$

T 41 S R 13 W
 1978

Set 6 ft. cedar post alongside the cor.

Cor. is located on SW slope in sand dunes.

40.84 The standard $\frac{1}{4}$ sec. cor. of sec. 34, common with the $\frac{1}{4}$ sec. cor. of sec. 3, T. 41 S., R. 13 W., monumented with a lava rock, 20 x 10 x 6 ins., firmly set 10 ins. in the ground and plainly mkd. $\frac{1}{4}$ SC on S face.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

S C
 T 40 S R 13 W

$\frac{1}{4}$ $\frac{S\ 34}{S\ 3}$

T 41 S R 13 W
 1978

Deposit the mkd. stone alongside the iron post.

Raise a mound of stone, 3 ft. base, 2 ft. high, to the N.

N. 89° 39' W., beginning new measurement.

Over gently rolling land, through sagebrush and native grasses.

41.01 The cor. of secs. 3 and 4, T. 41 S., R. 13 W., common with the original standard cor. of secs. 33 and 34, monumented with a lava rock, 18 x 12 x 9 ins., firmly set 5 ins. in the ground and plainly mkd. 3 notches on E and W edges, with SC on N face. Witnessed by a mound of stone, 2 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft. high to N.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

S C
 T 40 S R 13 W

$\frac{S\ 4}{S\ 3}$

T 41 S
 1978

Deposit the mkd. stone alongside the iron post.

Cor. is located in small saddle, bears E and W.

Dependent Resurvey of a Portion of the S. Bdy.,
(Eighth Standard Parallel South),
T. 40 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS	
	<p>N. 89° 49' W., along the N. bdy. of sec. 4, T. 41 S., R. 13 W.</p>
	<p>Asc. SE slope, through sagebrush and scattered cedar trees.</p>
20.28	<p>Point for the E 1/16 sec. cor. of sec. 4 only.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;"> <hr style="width: 100px; margin: 0 auto;"/> E 1/16 S 4 T 41 S R 13 W 1978 </p>
	<p>Set a 6 ft. cedar post alongside the iron post.</p>
40.56	<p>The ¼ sec. cor. of sec. 4, common with the original standard ¼ sec. cor. of sec. 33, monumented with a sandstone, 36 x 14 x 5 ins., firmly set 12 ins. in the ground, with a dimly mkd. ¼ on S face.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, to top of brass cap, mkd.</p>
	<p style="text-align: center;"> <hr style="width: 100px; margin: 0 auto;"/> ¼ S 4 T 41 S R 13 W 1978 </p>
	<p>Deposit the mkd. stone alongside the iron post.</p>
	<p>Cor. is located on sandy SE slope.</p>
	<p style="text-align: center;"> <hr style="width: 100px; margin: 0 auto;"/> </p>
	<p>N. 89° 46' W., beginning new measurement.</p>
	<p>Asc. SE slope.</p>
4.40	<p>Trail road on top of sandy ridge, bears N and S; desc. W slope.</p>
20.61	<p>Point for the W 1/16 sec. cor. of sec. 4 only.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;"> <hr style="width: 100px; margin: 0 auto;"/> W 1/16 S 4 T 41 S R 13 W 1978 </p>
	<p>Cor. is located at base of sandy ridge, bears N and S.</p>
	<p>Asc. gentle E slope.</p>
34.50	<p>Old highway, bears N. 52° E., and S. 52° W.</p>
37.74	<p>The standard closing cor. of secs. 32 and 33, monumented with a wooden stake in mound of stone, with broken sandstone, 10 x 8 x 4 ins., alongside, plainly mkd. 4 notches on E and 2 notches on W edges.</p>

Dependent Resurvey of a Portion of the S. Bdy.,
 (Eighth Standard Parallel South)
 T. 40 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS		
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 40 S R 13 W C C</p> <p style="text-align: center;"><u>S 32 S 33</u> 1978</p> <p>Deposit the mkd. stone alongside the iron post.</p>	
41.08	Fence on the right-of-way line of Interstate 15, bears N. 41° 26' E. and S. 41° 26' W.	
41.22	<p>The cor. of secs. 4 and 5, T. 41 S., R. 13 W., common with the original standard cor. of secs. 32 and 33, monumented with an iron post, 2½ ins. diam., extending 5 ins. above ground, set in concrete and a collar of stone, with a Washington County brass cap, mkd.</p> <p style="text-align: center;">T 40 S</p> <p style="text-align: center;"><u>S 5 S 4</u></p> <p style="text-align: center;">T 41 S R 13 W 1974</p> <p>This position is accepted as a careful and faithful perpetuation of the position of the original corner.</p>	
	<p>N. 89° 42' W., along the N. bdy. of sec. 5, T. 41 S., R. 13 W.</p> <p>Across highway right-of-way.</p>	
6.70	Center of north-bound lane of Interstate 15, bears N. 42° 53' E. and S. 42° 53' W.	
8.50	Center of south-bound lane of Interstate 15, bears N. 42° 53' E. and S. 42° 53' W.	
11.40	Fence on the right-of-way line of Interstate 15, bears N. 42° 53' E. and S. 42° 53' W.	
20.56	<p>Point for the E 1/16 sec. cor. of sec. 5 only.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;"><u>E 1/16 S 5</u> T 41 S R 13 W 1978</p>	
41.12	<p>Set a 6 ft. cedar post alongside the iron post.</p> <p>The ¼ sec. cor. of sec. 5, common with the original standard ¼ sec. cor. of sec. 32, monumented with an iron post, 2½ ins. diam., extending 8 ins. above ground, with a Washington County brass cap, mkd.</p>	

Dependent Resurvey of a Portion of the S. Bdy.,
 (Eighth Standard Parallel South)
 T. 40 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS

T 40 S

 $\frac{1}{4}$

S 5
 T 41 S
 R 13 W
 1974

A white limestone, 10 x 6 x 5 ins., mkd. $\frac{1}{4}$ SC, was buried alongside the iron post.

Cor. is located in an old down fence line, bears E and W.

N. 89° 44' W., beginning new measurement.

Over gently rolling sandy land, through sagebrush and scattered cedar trees.

20.71 Point for W 1/16 sec. cor. of sec. 5 only.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16 S 5
 T 41 S R 13 W
 1978

Raise a mound of stone, 3 ft, base, 2 ft. high, S of cor.

Cor. is located in old fence line, bears E and W.

41.42 The cor. of secs. 5 and 6, common with the original standard cor. of secs. 31 and 32, monumented with an iron post, 2 ins. diam., extending 8 ins. above ground, with brass cap mkd. as described in the official record of the 1949 resurvey.

Cor. is located in old fence line, bears E and W.

Dependent Resurvey of a Portion of the S. Bdy.,
 T. 41 S., R. 13 W., Salt Lake Meridian, Utah

(Restoring the Survey by Bailey and Burrill in 1877, the Resurvey by Jenkins and West in 1897 and the Retracement by Stewart and Snow in 1909

From the cor. of secs. 1, 2, 35, and 36, Tps. 41 and 42 S., R. 13 W., monumented with a limestone, 17 x 12 x 5 ins., firmly set 7 ins. in the ground and plainly mkd. 1 notch on E and 5 notches on W edges.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.

Dependent Resurvey of a Portion of the S. Bdy.,
T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS												
	<p style="text-align: center;">T 41 S R 13 W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 35</td> <td style="padding: 0 5px;">S 36</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 2</td> <td style="padding: 0 5px;">S 1</td> </tr> </table> <p style="text-align: center;">T 42 S R 13 W 1978</p> <p>Deposit the mkd. stone in mound alongside the iron post. Cor. is located in a barbwire fence line, bears E and W. S. 89° 58' W., along the S. bdy. of sec. 35.</p> <p>Over rolling bench land, through sagebrush and native grass.</p> <p>40.00 Point for the $\frac{1}{4}$ sec. cor. of sec. 35, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., on solid rock, in a mound of stone, 5 ft. base, to top of brass cap mkd.</p> <p style="text-align: center;">T 41 S R 13 W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">$\frac{1}{4}$</td> <td style="padding: 0 5px;">S 35</td> </tr> </table> <p style="text-align: center;">1978</p> <p>Cor. is located on steep W slope.</p> <p>52.00 Road in the town of Hurricane, bears N and W.</p> <p>80.00 The cor. of secs. 34 and 35, monumented with a 4 in. square metal survey marker in paved road, mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 34</td> <td style="padding: 0 5px;">S 35</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 3</td> <td style="padding: 0 5px;">S 2</td> </tr> </table> <p>This position is accepted as a careful and faithful perpetuation of the position of the original corner.</p>	S 35	S 36	S 2	S 1	$\frac{1}{4}$	S 35	S 34	S 35	S 3	S 2	
S 35	S 36											
S 2	S 1											
$\frac{1}{4}$	S 35											
S 34	S 35											
S 3	S 2											
	<p style="text-align: center;">(Restoring the Survey by Bailey and Burrill in 1877 and the Resurvey by Jenkins and West in 1897)</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 53' W., along the S. bdy. of sec. 34. Along paved road.</p> <p>39.97 The $\frac{1}{4}$ sec. cor. of sec. 34, monumented with a steel bolt in road, set by Washington County Surveyor, Howard G. Stevens in 1974, and accepted as the best available evidence of the original cor. point. No B.L.M. monument set due to private land.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 53' W., beginning new measurement. Along roadway.</p>											

Dependent Resurvey of a Portion of the S. Bdy.,
T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS	
40.04	<p>The cor. of secs. 33 and 34, monumented with a nail in a washer, mkd. Washington County Survey. Recorded in the County Surveyors Records as the point for the cor., and is accepted as the best available evidence of the original cor. point. No B.L.M. monument set, due to private land.</p>
0.85	<p>West, along the S. bdy. of sec. 33.</p> <p>Along road.</p> <p>The closing cor. of secs. 3 and 4, T. 42 S., R. 13 W., monumented with a copperhead, 2 ins. diam., mkd.</p> <p style="text-align: center;">L.S. 2685</p> <p style="text-align: center;">S 4 S 3</p> <p>The cor. is located in oiled road, bears E and W, and is accepted as the best available evidence of the original corner.</p>
39.97	<p>The 1/4 sec. cor. of sec. 33, monumented with a Washington County brass cap, flush with road, mkd.</p> <p style="text-align: center;">1/4 S 33 1974</p> <p>Cor. is located in oiled road, bears E and W, and is accepted as the best available evidence of the original corner.</p>
10.00	<p>N. 89° 59' W., beginning new measurement.</p> <p>Along road.</p> <p>Leave road, bears N and E.</p>
40.02	<p>The cor. of secs. 32 and 33, monumented with a black lava stone, 12 x 12 x 10 ins., firmly set 6 ins. in the ground and plainly mkd. 2 notches on W and 4 notches on E edges.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 41 S R 13 W S 32 S 33 S 4</p> <p style="text-align: center;">1978</p> <p>Deposit the mkd. stone alongside the iron post.</p>
	<p>S. 89° 59' W., along the S. bdy. of sec. 32.</p> <p>Asc. NE slope of Volcano Mtn., through sagebrush and native grasses.</p>

Dependent Resurvey of a Portion of the S. Bdy.,
T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS

0.86 The closing cor. of secs. 4 and 5, T. 42 S., R. 13 W., monumented with an iron post, 24 ins. long, 2½ ins. diam., set 20 ins. in the ground with Washington County brass cap mkd. for the cor. of secs. 32 and 33. A lava rock, 12 x 10 x 9 ins., plainly mkd. CC on S face and 1 notch on W edge is lying alongside the iron post.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 41 S R 13 W

S 32	
S 5	S 4
C C	
T 42 S R 13 W	
1978	

Invert Washington County cor. and set alongside the iron post.

Deposit the mkd. stone alongside the iron post.

40.19 The ¼ sec. cor. of sec. 32, monumented with a mound of stone. No marks identified. This point fits the pattern of the survey and is accepted as the best available evidence of the original corner.

At the corner point (center of mound)

Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.

T 41 S R 13 W

¼	S 32
---	------

T 42 S R 13 W
1978

West, beginning new measurement.

Desc. NW slope of Volcano Mtn.

39.91 The cor. of secs. 31 and 32, monumented with a black lava stone, 10 x 8 x 4 ins., firmly set 5 ins. in the ground and plainly mkd. 5 notches on E and 1 notch on W edges.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

Dependent Resurvey of a Portion of the S. Bdy.,
T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS	
	<p style="text-align: center;">T 41 S R 13 W S 31 S 32 S 5 T 42 S R 13 W 1978</p> <p>Deposit the mkd. stone alongside the iron post.</p>
0.76	<p>S. 89° 56' W., along the S. bdy. of sec. 31. Desc. W slope, through sagebrush and native grasses.</p> <p>The closing cor. of secs. 5 and 6, T. 42 S., R. 13 W., monumented with a black lava stone, 20 x 10 x 4 ins., firmly set 10 ins. in the ground and plainly mkd. 5 notches on E and 1 notch on W edges and CC on S face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>
40.10	<p style="text-align: center;">T 41 S R 13 W S 31 S 6 S 5 C C T 42 S R 13 W 1978</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>The ¼ sec. cor. of sec. 31, monumented with a 1 in. iron pipe in a mound of stone. This point fits the pattern of the survey and is accepted as the best available evidence of the original corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>
23.00 39.69	<p style="text-align: center;">T 41 S R 13 W ¼ S 31 T 42 S R 13 W 1978</p> <p>Set a 6 ft. cedar post and the 1 in. iron pipe alongside the iron post.</p> <p>S. 89° 58' W., beginning new measurement.</p> <p>Over gently rolling desert land.</p> <p>Utah State Highway No. 9, bears N. 73° E. and S. 73° W.</p> <p>Point for the 80 1/16 sec. cor. of sec. 31.</p>

Dependent Resurvey of a Portion of the S. Bdy.,
T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap mkd.

T 41 S R 13 W

80 1/16 S 31

T 42 S R 13 W
1978

52.47 The closing cor. of secs. 6 and 31, Tps. 41 and 42 S., R. 13 W., on the east bdy. of sec. 36, T. 41 S., R. 14 W., monumented with a lava rock, 5 x 6 x 16 ins., firmly set 8 ins. in the ground and plainly mkd. 6 notches on N and S edges.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 41 S
R 14 W R 13 W

S 36		S 31	C
		S 6	C

T 42 S
1978

Deposit the mkd. stone alongside the iron post.

From this point the cor. of secs. 1 and 36, Tps. 41 and 42 S., R. 14 W., bears S. 0° 07' W., 6.91 chs. dist., set and mkd. as described in the field notes of the concurrent resurvey of T. 41 S., R. 14 W.

Dependent Resurvey of a Portion of the E. Bdy.,
T. 41 S., R. 13 W., Salt Lake Meridian, Utah

(Restoring the 1877 Survey by Bailey and Burrill and
the 1897 Resurvey by Jenkins and West)

From the cor. of secs. 25 and 36, on the E. bdy. of the Tp., monumented with a limestone, 20 x 8 x 8 ins., firmly set 8 ins. in the ground and plainly mkd. 1 notch on S and 5 notches on N edges.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 41 S
R 13 W R 12 W

S 25	
S 36	

1978

Dependent Resurvey of a Portion of the E. Bdy.,
T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS

- Deposit the mkd. stone alongside the iron post.
- Raise a mound of stone, 2½ ft. base, 1½ ft. high to W.
N. 1° 17' W., along the E. bdy. of sec. 25.
- Desc. broken NW slope, through sagebrush and native
grasses.
- 39.60 Point for the ¼ sec. cor. of sec. 25.
- Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins.
in the ground to bedrock, in a mound of stone, 3½ ft.
base, to top of brass cap, mkd.
- T 41 S
R 13 W R 12 W
- ¼
S 25
- 1978
- Cor. is located 20 lks. E of small draw, drains S.
- 42.86 Point for an angle point identical with the SE cor. of
the NE¼ of sec. 25.
- Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.
- T 41 S
R 13 W R 12 W
- AP
- S 25
- 1978
- Raise a mound of stone, 3½ ft. base, 1½ ft. high to W.
- Cor. is located 30 lks. E of small draw, drains S.
- Asc. SW slope.
- 65.00 Virgin River, 3.00 chs. wide, drains N. 80° W.; asc.
broken S slope over ledges.
- 81.36 The closing cor. of secs. 19 and 30, T. 41 S., R. 12 W.,
monumented with an iron post, 2 ins. diam., extending 6
ins. out of a mound of stone, 4 ft. base, with brass cap
mkd. as described in the official record of the 1909
resurvey.
- 82.46 The cor. of secs. 24 and 25, monumented with an iron
post, 3 ins. diam., extending 12 ins. out of a mound of
stone, 4 ft. base, with brass cap mkd. as described in
the official record of the 1909 resurvey.
- NOTE: There is no remaining evidence of the original
witness cor. to the cor. of secs. 19, 24, 25, and 30,
established in 1877 and then recovered in the 1897
resurvey. This cor. was not mentioned in the 1909
retracement.

Dependent Resurvey of a Portion of the E. Bdy.,
T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS										
	(Restoring the 1877 Survey by Bailey and Burrill, the 1897 Resurvey by Jenkins and West and the 1909 Retracement by R.E.L. Collier)									
	<hr/> N. 0° 17' E., along the E. bdy. of sec. 24. Asc. broken S slope, through sagebrush and native grasses.									
40.01	The ¼ sec. cor. of sec. 24, monumented with an iron post, 1 in. diam., extending 6 ins. out of a mound of stone, 3 ft. base, with brass cap mkd. as described in the official record of the 1909 resurvey.									
	<hr/> N. 0° 21' E., beginning new measurement.									
39.60	The closing cor. of secs. 18 and 19, T. 41 S., R. 12 W., monumented with an iron post, 2 ins. diam., extending 16 ins. out of the ground and in a mound of stone, 3 ft. base, to top of brass cap mkd. as described in the official record of the 1909 resurvey.									
40.20	The cor. of secs. 13 and 24, monumented with a sandstone, 20 x 8 x 8 ins., firmly set 15 ins. in the ground and plainly mkd. 3 notches on N and S edges. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.									
	<table border="0"> <tr> <td colspan="2">T 41 S</td> </tr> <tr> <td>R 13 W</td> <td>R 12 W</td> </tr> <tr> <td style="border-right: 1px solid black;">S 13</td> <td>S 18</td> </tr> <tr> <td style="border-right: 1px solid black;">S 24</td> <td></td> </tr> </table> 1978		T 41 S		R 13 W	R 12 W	S 13	S 18	S 24	
T 41 S										
R 13 W	R 12 W									
S 13	S 18									
S 24										
	Deposit the mkd. stone alongside the iron post. Raise a mound of stone, 3 ft. base, 2 ft. high to W.									
	<hr/> (Restoring the 1877 Survey by Bailey and Burrill and the 1897 Resurvey by Jenkins and West)									
	<hr/> N. 0° 29' E., along the E. bdy. of sec. 13. Over rolling bench land, through sagebrush and native grasses.									
40.68	The ¼ sec. cor. of sec. 13, monumented with a limestone, 15 x 12 x 3 ins., firmly set 10 ins. in the ground, and plainly mkd. ¼ on W face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.									

Dependent Resurvey of a Portion of the E. Bdy.,
T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS

T 41 S
R 13 W R 12 W

¼
|
S 13
|

1978

Deposit the mkd. stone alongside the iron post.

Raise a mound of stone, 2½ ft. base, 1½ ft. high to W.

N. 0° 29' E., beginning new measurement.

29.00 Utah State Highway No. 9, bears E and W.

38.62 The closing cor. of secs. 7 and 18, T. 41 S., R. 12 W., monumented with an iron post, 2 ins. diam., extending 18 ins. out of the ground, and in a collar of stone, with brass cap mkd. as described in the official record of the 1909 resurvey.

40.68 The cor. of secs. 12 and 13, monumented with a limestone, 20 x 8 x 8 ins., firmly set 10 ins. in the ground and plainly mkd. 4 notches on S and 2 notches on N edges.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 41 S
R 13 W R 12 W

S 12 |
S 13 | S 7

1978

Deposit the mkd. stone alongside the iron post.

Raise a mound of stone, 2 ft. base, 2 ft. high to W.

NOTE: There is no remaining evidence of the original witness cor. to the cor. of secs. 7, 12, 13, and 18, established in 1877 and then recovered in the 1897 resurvey.

(Restoring the 1897 Survey by Jenkins and West)

N. 0° 05' W., along the E. bdy. of sec. 12.

Desc. over rolling NW slope, through sagebrush and native grasses.

39.93 True point for the ¼ sec. cor. of sec. 12, at proportionate distance falls in gulch. There is no remaining evidence of the original corner.

40.43 Point selected for the witness cor. to the ¼ sec. cor. of sec. 12, on top of ledge, 15 ft. high, bears S and curves NE.

Dependent Resurvey of a Portion of the E. Bdy.,
T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS		
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">W C T 41 S R 13 W R 12 W</p> <p style="text-align: center;">↓ ½ S 12 ↓</p> <p style="text-align: center;">1978</p>	
77.95	<p>The closing cor. of secs. 6 and 7, T. 41 S., R. 12 W., monumented with an iron post, 2 ins. diam., extending 10 ins. out of ground, with brass cap mkd. as described in the official record of the 1909 survey.</p>	
79.86	<p>The original cor. of secs. 1, 6, 7, and 12, now functioning as an angle point, monumented with a sandstone, 20 x 9 x 9 ins., firmly set in a mound of stone. Markings on this stone were destroyed in the 1897 survey by Jenkins and West and the 1909 survey by R.E.L. Collier.</p> <p>At the angle point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">A P T 41 S R 13 W R 12 W</p> <p style="text-align: center;">S 12 S 6</p> <p style="text-align: center;">1978</p> <p>Deposit the defaced stone in mound of stone.</p> <p>Raise a mound of stone, 3 ft. base, 1½ ft. high to W.</p>	
0.95	<p>N. 0° 07' W., along the E. bdy. of sec. 12.</p> <p>Over broken NW slope.</p> <p>The closing cor. of secs. 1 and 12, monumented with a sandstone, 15 x 6 x 6 ins., firmly set 5 ins. in the ground, and plainly mkd. 5 notches on S and 1 notch on N edges, and CC on NW face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 S R 13 W R 12 W</p> <p style="text-align: center;">C S 1 C S 12 S 6</p> <p style="text-align: center;">1978</p>	

Dependent Resurvey of a Portion of the E. Bdy.,
T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS

- Deposit the mkd. stone alongside the iron post.
- Raise a mound of stone, 3 ft. base, 1½ ft. high to W.
- Thence along the E. bdy. of sec. 1 with continuous measurement.
- 40.01 The ¼ sec. cor. of sec. 1, monumented with a limestone, 16 x 6 x 5 ins., firmly set 10 ins. in the ground, and plainly mkd. ¼ on W face.
- At the corner point
- Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base, to top of brass cap, mkd.
- T 41 S
R 13 W R 12 W
- ¼ |
S 1 |
- 1978
- Deposit the mkd. stone alongside the iron post.
- Raise a mound of stone, 3 ft. base, 2 ft. high to W.
- _____
- N. 0° 06' W., beginning new measurement.
- 35.00 La Verkin Creek, drains SW; along W side of creek.
- 42.25 The closing cor. of secs. 1 and 6, on the Eighth Standard Parallel South, monumented with an iron post, 3 ins. diam., extending 3 ft. out of ground, with brass cap mkd. as described in the official record of the 1909 resurvey.
- from which
- A black sandstone boulder, 6 x 6 x 3 ft., bears
S. 42° W., 145 lks. dist., mkd. S1BX0
- From this cor., the standard cor. of secs. 31 and 36, Tps. 40 S., Rs. 12 and 13 W., heretofore described, bears S. 89° 58' W., 1.85 chs. dist.
- From this same cor., the standard ¼ sec. cor. of sec. 31, T. 40 S., R. 12 W., monumented with an iron post, 1 in. diam., extending 10 ins. out of the ground, with brass cap mkd. as described in the official record of the 1909 survey, bears N. 89° 58' E., 37.70 chs. dist.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS

(Restoring the 1897 Survey by Jenkins and West)

From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., heretofore described.

N. 0° 15' W., bet. secs. 35 and 36.


Desc. rolling N slope, through sagebrush and native grasses.

39.89 The ¼ sec. cor. of secs. 35 and 36, monumented with a cross (X), 10 ins. E of a ¼ mkd. on limestone ledge.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., over cross (X), in a mound of stone, 6 ft. base, to top of brass cap, mkd.

T 41 S R 13 W



1978

Cor. is located on steep S slope.

N. 0° 08' E., beginning new measurement.


2.00 Utah State Highway No. 59, bet. Hurricane and Colorado City, bears SE and NW on curve; desc. broken NW slope.

39.87 The cor. of secs. 25, 26, 35, and 36, monumented with a limestone, 15 x 12 x 5 ins., firmly set 5 ins. in the ground and plainly mkd. 1 notch on E and S edges.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 41 S R 13 W



1978

Deposit the mkd. stone alongside the iron post.

Cor. is located on gentle E slope.


Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS	
40.17	<p>From the cor. of secs. 25 and 36, on the E. bdy. of the Tp., heretofore described.</p> <p>S. 89° 57' W., bet. secs. 25 and 36.</p> <p>Over rolling bench land, through sagebrush and native grasses.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 25 and 36, monumented with a limestone, 15 x 8 x 6 ins., firmly set in a mound of stone and plainly mkd. $\frac{1}{4}$ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 15 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S\ 25}{S\ 36}$</p> <p style="text-align: center;">1978</p> <p>Deposit the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 26' W., beginning new measurement.</p>
39.70	<p>The cor. of secs. 25, 26, 35, and 36.</p> <hr/> <p>N. 0° 44' W., bet. secs. 25 and 26.</p> <p>Over low bench, through sagebrush and native grasses.</p> <p>Virgin River, drains N. 70° W.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 25 and 26, monumented with an iron post, 2$\frac{1}{2}$ ins. diam., extending 8 ins. out of the ground, with a Washington County brass cap, mkd.</p> <p style="text-align: center;">$\frac{1}{4}$</p> <p style="text-align: center;">S 26 S 25</p> <p style="text-align: center;">T 41 S R 13 W 1971</p> <p>This position is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>Steel fence post, 6 ft. long, set alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 42' W., beginning new measurement.</p> <p>Over nearly level land in the town of La Verkin.</p> <p>Utah State Highway No. 9, bears N. 20° E. and S. 20° W.</p>
26.50	
40.15	
35.00	

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS

- 40.11 Point for 80 1/16 sec. cor. of secs. 25 and 26. No monument set due to construction and private property.
- 45.63 The closing cor. of secs. 25 and 26, on the S. bdy. of sec. 24, monumented with an iron post, 2 1/2 ins. diam., 13 ins. under ground, with a Washington County brass cap, mkd.



This cor. is located in a garden spot, and is accepted as a careful and faithful perpetuation of the position of the original corner.

From this cor., the cor. of secs. 23 and 24, bears N. 87° 56' W., 1.06 chs. dist., hereinafter described.


From the cor. of secs. 24 and 25, on the E. bdy. of the Tp., heretofore described.

N. 87° 56' W., bet. secs. 24 and 25.

Asc. W slope, through sagebrush and native grasses.

- 20.06 Point for the E 1/16 sec. cor. of secs. 24 and 25.


Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



Raise a mound of stone, 3 ft. base, 1 1/2 ft. high to N.

- 40.12 Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate distance. This cor. was not monumented in earlier surveys.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 1/2 ft. base, to top of brass cap mkd.



Cor. is located on broken W slope.

- 75.00 Utah State Highway No. 9, bears N. 20° E. and S. 20° W.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS	
79.18	The closing cor. of secs. 25 and 26, heretofore described.
80.24	The cor. of secs. 23 and 24, monumented with an iron post, 2½ ins. diam., 6 ins. underground, with Washington County brass cap, mkd.
<p>T 41 S</p> <p>S 23 S 24</p> <p>S 26</p> <p>R 13 W</p> <p>1978</p>	
Cor. is located in a garden spot, and is accepted as a careful and faithful perpetuation of the position of the original corner.	
<p>(Restoring the 1877 Survey by J.G. Burrill and T.C. Bailey)</p>	
N. 0° 02' W., bet. secs. 23 and 24.	
Over nearly level land in the town of La Verkin.	
39.90	Point for the ¼ sec. cor. of secs. 23 and 24, at proportionate distance; falls in trailer court and is not monumented due to private property. There is no remaining evidence of the original corner.
79.80	The cor. of secs. 13, 14, 23, and 24, monumented with a sandstone, 12 x 10 x 8 ins., firmly set in a collar of stone, and plainly mkd. 3 notches on S edge and dimly mkd. 1 notch on E edge.
At the corner point	
Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.	
<p>T 41 S R 13 W</p> <p>S 14 S 13</p> <p>S 23 S 24</p> <p>1978</p>	
Deposit the mkd. stone alongside the iron post.	
Cor. is located 4 lks. W of a fence cor., bearing N and W.	
From the cor. of secs. 13 and 24, on the E. Bdy. of the Tp., heretofore described.	
N. 88° 17' W., bet. secs. 13 and 24.	
Over rolling bench land, through sagebrush and native grasses.	
36.50	Utah State Highway No. 9, bears N and S; over gentle W slope.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS	
40.33	<p>The $\frac{1}{4}$ sec. cor. of secs. 13 and 24, monumented with a limestone, 14 x 9 x 9 ins., firmly set 10 ins. in the ground and plainly mkd. $\frac{1}{4}$ on N face. Steel fence post, 6 ft. high alongside.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S\ 13}{S\ 24}$</p> <p style="text-align: center;">1978</p> <p>Deposit the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. $88^{\circ} 15'$ W., beginning new measurement.</p>
33.00	<p>Utah State Highway No. 17, bears S and NW on curve.</p>
40.31	<p>The cor. of secs. 13, 14, 23, and 24.</p>
13.00	<p>N. $0^{\circ} 05'$ E., bet. secs. 13 and 14.</p> <p>Asc. SW slope, through sagebrush and native grasses.</p> <p>Utah State Highway No. 17, bears NW and SE.</p>
19.755	<p>Point for the S $\frac{1}{16}$ sec. cor. of secs. 13 and 14.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;">S $\frac{1}{16}$</p> <p style="text-align: center;">S 14 S 13</p> <p style="text-align: center;">1978</p> <p>Cor. is located on top of nearly level spur, slopes W.</p> <p>Along W slope.</p>
39.51	<p>The $\frac{1}{4}$ sec. cor. of secs. 13 and 14, monumented with an iron post, $2\frac{1}{2}$ ins. diam., set in concrete flush with ground, with a Washington County brass cap, mkd.</p> <p style="text-align: center;">T 41 S</p> <p style="text-align: center;">S 14 S 13</p> <p style="text-align: center;">R 13 W</p> <p style="text-align: center;">1975</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS	
	<p>Cor. is located on SE slope, and is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p style="text-align: center;">_____</p> <p>N. 0° 04' E., beginning new measurement.</p> <p>Asc. SE slope.</p>
19.99	<p>Point for the N 1/16 sec. cor. of secs. 13 and 14.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 41 S R 13 W N 1/16</p> <p style="text-align: center;">S 14 S 13</p> <p style="text-align: center;">1978</p>
39.98	<p>Cor. is located on top of low ridge, bears NE and SW.</p> <p>The cor. of secs. 11, 12, 13, and 14, monumented with a lava rock, 18 x 10 x 9 ins., firmly set in a collar of stone, and plainly mkd. 4 notches on S and 1 notch on E edges.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;">S 11 S 12 S 14 S 13</p> <p style="text-align: center;">1978</p> <p>Cor. is located at foot of hill, bears N and S and under a four strand barbwire fence line, bears N and S.</p>
	<p style="text-align: center;">(Restoring the 1877 Survey by Burrill and Bailey and the 1897 Resurvey by Jenkins and West)</p>
40.55	<p>From the cor. of secs. 12 and 13, on the E. bdy. of the Tp., heretofore described.</p> <p>N. 89° 35' W., bet. secs. 12 and 13.</p> <p>Desc. W slope, through sagebrush and native grasses.</p> <p>The ¼ sec. cor. of secs. 12 and 13, monumented with a limestone, 20 x 10 x 5 ins., set in a mound of stone, no marks identified. This cor. position fits the pattern of the survey and is accepted as the best available evidence of the original corner.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS	
40.54	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;">¼ $\frac{S 12}{S 13}$</p> <p style="text-align: center;">1978</p> <p>Deposit the unmkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 1½ ft. high to N.</p> <p>Cor. is located on S side of draw, drains W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 36' W., beginning new measurement.</p> <p>Desc. along draw, draining irregularly W.</p> <p>The cor. of secs. 11, 12, 13, and 14.</p>
11.00	<p>N. 0° 32' W., bet. secs. 11 and 12.</p> <p>Desc. along W slope.</p> <p>La Verkin Creek, 1 ft. deep, 15 ft. wide, drains SW; asc. S slope over pasture land.</p>
20.14	<p>Point for the S 1/16 sec. cor. of secs. 11 and 12.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;">S 1/16</p> <p style="text-align: center;">S 11 S 12</p> <p style="text-align: center;">1978</p> <p>Deposit broken glass alongside the iron post, with 4 ft. cedar post.</p> <p>Cor. is located in a pasture.</p>
40.28	<p>The ¼ sec. cor. of secs. 11 and 12, monumented with a limestone boulder in place, 15 x 15 x 15 ins. above ground and plainly mkd. ¼ on top of boulder.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., over the ¼ marks on top of boulder and in a mound of stone 3½ ft. base, to top of brass cap, mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS		
	<p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;"> $\frac{1}{4}$ S 11 S 12 </p> <p style="text-align: center;">1978</p> <p>Cor. is located on SE slope.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 02' W., beginning new measurement.</p> <p>Asc. along SE slope.</p> <p>39.86 The cor. of secs. 1 and 12, monumented with a lava rock, 20 x 12 x 9 ins., firmly set in a mound of stone, and plainly mkd. 5 notches on S and 1 notch on E edges.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;"> S 11 S 1 S 12 </p> <p style="text-align: center;">1978</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Cor. is on SE slope at old fence cor., fences bear N and W.</p>	
	<p>N. 89° 55' E., bet. secs. 1 and 12.</p> <p>Along S slope, through sagebrush and native grasses.</p> <p>18.63 Point selected for the witness cor. to the W 1/16 sec. cor. of secs. 1 and 12.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">W C T 41 S R 13 W</p> <p style="text-align: center;"> W 1/16 $\frac{S 1}{S 12}$ \rightarrow </p> <p style="text-align: center;">1978</p> <p>Cor. is located on top of ledge, bears N and S.</p> <p>20.26 True point for the W 1/16 sec. cor. of secs. 1 and 12, falls on perpendicular ledges and cannot be monumented.</p> <p>31.00 La Verkin Creek, 1 ft. deep, 10 ft. wide, drains SW; asc. W slope.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS		
40.52	<p>The $\frac{1}{4}$ sec. cor. of secs. 1 and 12, monumented with a limestone, 20 x 8 x 6 ins., firmly set in a mound of stone and plainly mkd. $\frac{1}{4}$ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, $3\frac{1}{2}$ ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S 1}{S 12}$</p> <p style="text-align: center;">1978</p> <p>Deposit the mkd. stone in mound alongside the iron post.</p>	
19.52	<p>N. $89^{\circ} 59'$ E., beginning new measurement.</p> <p>Point for the E $\frac{1}{16}$ sec. cor. of secs. 1 and 12.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;">E $\frac{1}{16}$ $\frac{S 1}{S 12}$</p> <p style="text-align: center;">1978</p> <p>Raise a mound of stone, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high to S.</p>	
40.89	<p>The closing cor. of secs. 1 and 12, on the E. bdy. of sec. 6, T. 41 S., R. 12 W., heretofore described.</p> <p>From this point the angle point bet. secs. 6 and 12, bears S. $0^{\circ} 07'$ E., 0.95 chs. dist., heretofore described.</p>	
39.77	<p>From the cor. of secs. 1 and 12.</p> <p>N. $0^{\circ} 04'$ W., along the W. bdy. of sec. 1.</p> <p>Asc. SE slope.</p> <p>The $\frac{1}{4}$ sec. cor. of sec. 1 only, monumented with a sandstone, 36 x 15 x 8 ins., firmly set in a mound of stone, and plainly mkd. $\frac{1}{4}$ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., on solid rock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;"> $\frac{1}{4}$</p> <p style="text-align: center;"> S 1</p> <p style="text-align: center;">1978</p>	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS		
	<p>Deposit the mkd. stone alongside the iron post.</p> <p style="text-align: center;">_____</p> <p>N. 0° 01' W., beginning new measurement.</p> <p>Asc. SE slope.</p>	
41.40	<p>The cor. of secs. 1 and 2 on the Eighth Standard Parallel South, common with the standard cor. of secs. 35 and 36, T. 40 S., R. 13 W., heretofore described.</p>	
33.00	<p>From the cor. of secs. 34 and 35, on the S. bdy. of the Tp., heretofore described.</p> <p>N. 0° 15' W., bet. secs. 34 and 35.</p> <p>Within the Hurricane City limits; along E side of street.</p> <p>Utah State Highway No. 9, bears E and W.</p>	
40.05	<p>The $\frac{1}{4}$ sec. cor. of secs. 34 and 35, monumented with a metal survey marker, 4 ins. square, set flush with the surface of the ground, mkd.</p> <p style="text-align: center;"> 34 35 </p>	
39.95	<p>This position is accepted as the best available evidence of the position of the original corner.</p> <p>Cor. is located at the NW cor. of city block.</p> <p style="text-align: center;">_____</p> <p>N. 0° 10' W., beginning new measurement.</p>	
	<p>The cor. of secs. 26, 27, 34, and 35, mkd. by a wooden stake, set flush with the surface of road, from which a Washington County survey peg, nailed to a power pole and mkd. R P SEC. COR. 61.2 FT., bears N. 89° 50' W., 0.927 chs. dist., and is accepted as the best available evidence of the position of the original corner.</p> <p>From the corner point</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 58° 37' W., 1.082 chs. dist., with brass cap mkd. RM T41S R13W S34 71.4 FT 1979 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">A valve on top of fire hydrant, bears N. 50° 29' W., 1.148 chs. dist.</p> <p>Cor. point is located in dirt road, under construction, bears E and W.</p>	
	<p>From the cor. of secs. 25, 26, 35, and 36.</p> <p>N. 89° 59' W., bet. secs. 26 and 35.</p>	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS	
33.00	Over broken mountainous land, through sagebrush, shadscale and creosote brush; desc. NW slope. Utah State Highway No. 9, bears NE and SW.
40.25	The $\frac{1}{4}$ sec. cor. of secs. 26 and 35, monumented with a metal survey marker, 2 ins. square, set flush with the surface of driveway, mkd. <div style="text-align: center;"> $\frac{S\ 26}{S\ 35}$ </div> <p>Cor. is located in private driveway, bears N and S, and is accepted as the best available evidence of the position of the original corner.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89° 45' W., beginning new measurement.</p>
39.99	The cor. of secs. 26, 27, 34, and 35.
40.00	N. 0° 10' W., bet. secs. 26 and 27. Over rolling land, within the city limits of Hurricane, Utah. The $\frac{1}{4}$ sec. cor. of secs. 26 and 27, monumented with an iron post, 2 $\frac{1}{2}$ ins. diam., set flush with surface of paved road, bears N and S, with Washington County brass cap mkd. <div style="text-align: center;"> <p>T 41 S</p> $\begin{array}{c} \frac{1}{4} \\ 27 \mid 26 \\ \end{array}$ <p>R 13 W 1974</p> </div> <p>This position is accepted as the best available evidence of the position of the original corner.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 45' W., beginning new measurement.</p>
40.08	The cor. of secs. 22 and 27 only, monumented with an iron post, 2 $\frac{1}{2}$ ins. diam., extending 6 ins. above ground, with Washington County brass cap mkd. <div style="text-align: center;"> <p>T 41 S R 13 W</p> $\frac{S\ 22 \mid}{S\ 27 \mid} S\ 26$ <p>LS 4266 UT 1978</p> </div> <p>This position is accepted as the best available evidence of the position of the original corner.</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS	
	<p>From the cor. of secs. 23 and 24 only.</p> <p>S. 89° 53' W., along the S. bdy. of sec. 23.</p> <p>Over rolling land, within the city limits of La Verkin, Utah.</p>
38.86	<p>The $\frac{1}{4}$ sec. cor. of sec. 26 only, monumented with an iron post, 2½ ins. diam., set flush with road, with Washington County brass cap, mkd.</p> <p style="text-align: center;">T 41 S R 13 W ----- $\frac{1}{4}$ S 26 1978</p> <p>This position is accepted as the best available evidence of the position of the original corner.</p>
39.94	<p>The $\frac{1}{4}$ sec. cor. of sec. 23 only, monumented with an iron post, 2½ ins. diam., set in concrete, with Washington County brass cap, mkd.</p> <p style="text-align: center;">T 41 S R 13 W ----- S 23 $\frac{1}{4}$ 1974</p> <p>Cor. is located on steep W slope, and is accepted as the best available evidence of the position of the original corner.</p> <p style="text-align: center;">-----</p> <p>N. 89° 53' W., beginning new measurement.</p>
16.00	<p>Virgin River, drains N. 25° W.</p>
38.88	<p>The closing cor. of secs. 22 and 26, hereinafter described.</p>
39.03	<p>The witness cor. to the SW cor. of sec. 23, monumented with an iron post, 2½ ins. diam., extending 6 ins. above ground, with Washington County brass cap, mkd.</p> <p style="text-align: center;">T 41 S R 13 W W C ----- ← S 23 1978</p>
39.93	<p>True point for the SW cor. of sec. 23, as determined by the Washington County surveyors, falls in Virgin River, draining S. 20° W.</p> <p>This position is accepted as the best available evidence of the position of the original corner. The original witness cor. to the SW cor. of sec. 13 was not found.</p>
	<p>From the cor. of secs. 22 and 27.</p> <p>N. 0° 47' W., bet. secs. 22 and 26.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS	
	<p>Over bottom land along river.</p> <p>5.46 The closing cor. of secs. 22 and 26, on the S. bdy. of sec. 23, monumented with an iron post, 2½ ins. diam., extending 8 ins. above ground, with Washington County brass cap, mkd.</p> <div style="text-align: center;"> <p>T 41 S R 13 W</p> <p>C C</p> <p>X Sec 26</p> <p> </p> <p> 26</p> </div> <p>1978</p> <p>This position is accepted as the best available evidence of the position of the original corner.</p> <p>From this cor., the witness cor. to the SW cor. of sec. 23, bears N. 89° 53' W., 15 lks. dist., heretofore described.</p>
	<p>From the true point for the SW cor. of sec. 23.</p> <p>N. 0° 17' E., bet. secs. 22 and 23.</p> <p>Over broken mountainous land, through sagebrush, shadscale and creosote brush.</p> <p>2.00 Right bank of Virgin River, bears N. 20° E. and S. 20° W.; asc. SE slope.</p> <p>34.55 Point for the ¼ sec. cor. of sec. 22 only.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 41 S R 13 W</p> <p>¼ </p> <p>S 22 </p> </div> <p>1978</p>
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <p>40.15 The original ¼ sec. cor. of secs. 22 and 23, monumented with a limestone, 18 x 12 x 7 ins., firmly set in a mound of stone and plainly mkd. ¼ on W face. This cor. will now function as the ¼ sec. cor. of sec. 23 only, identical with the SE cor. of the NE¼ of sec. 22.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 41 S R 13 W</p> <p>¼ </p> <p> S 23</p> </div> <p>1978</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS

Deposit the mkd. stone and set a steel fence post
alongside the iron post.

Cor. is located at the base of hill, bears E and NW.

N. 0° 13' W., beginning new measurement.

Over rolling land.

40.23 The cor. of secs. 14, 15, 22, and 23, monumented with a
yellow limestone, 12 x 6 x 8 ins., firmly set 8 ins. in
the ground and plainly mkd. 3 notches on S and 2 notches
on the E edges.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins.
in the ground to bedrock, in a mound of stone, 3½ ft.
base, to top of brass cap, mkd.

T 41 S R 13 W

S 15	S 14
S 22	S 23

1978

Deposit the mkd. stone and set a cedar post, 9 ft. long,
alongside the iron post.

(Restoring the 1877 Survey by J.G. Burrill and
T.C. Bailey)

From the cor. of secs. 13, 14, 23, and 24.

N. 89° 32' W., bet. secs. 14 and 23.

Over broken land, through sagebrush, shadscale and
creosote brush; desc. SW slope.

25.00 La Verkin Creek, 10 lks. wide, 8 ins. deep, drains
S; over rolling land.

39.87 The ¼ sec. cor. of secs. 14 and 23, monumented with an
iron post, 2½ ins. diam., extending 5 ins. above ground,
set in cement and in a collar of stone, with Washington
County brass cap, mkd.

T 41 S

¼	S 14
	S 23

R 13 W
1975

This position is accepted as the best available evidence
of the position of the original corner.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS	
<p>22.00</p> <p>39.90</p>	<p>N. 89° 35' W., beginning new measurement.</p> <p>Asc. E slope.</p> <p>Ash Creek, 10 lks. wide, 6 ins. deep, drains S. 35° W.; asc. gentle E slope.</p> <p>The cor. of secs. 14, 15, 22, and 23.</p>
<p>39.99</p> <p>37.98</p>	<p>N. 0° 16' W., bet. secs. 14 and 15.</p> <p>Over series of broken spurs and washes, projecting SE; through sagebrush, shadscale and creosote brush.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 14 and 15, mkd. with a $\frac{1}{4}$ chiseled on nearly level sandstone outcrop and witnessed by a mound of stone to W.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., over the $\frac{1}{4}$ mkd. on surface of rock, in a mound of stone, 5 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;"> $\frac{1}{4}$ S 15 S 14 </p> <p style="text-align: center;">1978</p> <p style="text-align: center;">_____</p> <p style="text-align: center;">(Restoring the 1870 Survey by Joseph Gorlinski)</p> <p style="text-align: center;">_____</p> <p>N. 0° 18' W., beginning new measurement.</p> <p>The cor. of secs. 10, 11, 14, and 15, monumented with a lava stone, 18 x 10 x 9 ins., firmly set 8 ins. in the ground and plainly mkd. 4 notches on the S and 2 notches on the E edges.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 2 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;"> S 10 S 11 S 15 S 14 </p> <p style="text-align: center;">1978</p> <p>Deposit the mkd. stone and set a steel fence post alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS

(Restoring the 1870 Survey by J. Gorlinski and the
Retracement by Jenkins and West)

N. 0° 05' W., bet. secs. 10 and 11.

Over rolling land, through sagebrush, shadscale and
creosote brush; asc. SE slope.

40.89 The $\frac{1}{4}$ sec. cor. of secs. 10 and 11, monumented with a
lava stone, 16 x 12 x 9 ins., firmly set 10 ins. in the
ground and dimly mkd. $\frac{1}{4}$ on W face.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 11 ins.
in the ground to bedrock, in a mound of stone, 3 $\frac{1}{2}$ ft.
base, to top of brass cap, mkd.

T 41 S R 13 W

S 10		S 11

1978

Deposit the mkd. stone alongside the iron post.

N. 0° 14' W., beginning new measurement.

40.02 The cor. of secs. 2, 3, 10, and 11, monumented with a
lava stone, 20 x 14 x 8 ins., firmly set 10 ins. in the
ground and plainly mkd. 5 notches on the S and 2 notches
on the E edges.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 14 ins.
in the ground to bedrock, in a mound of stone, 4 ft.
base, to top of brass cap, mkd.

T 41 S R 13 W

S 3		S 2
S 10		S 11

1978

Deposit the mkd. stone in mound alongside the iron post.

Cor. is located in fence line, bears E and W.

N. 0° 07' W., bet. secs. 2 and 3.

Over rolling land, through sagebrush, shadscale and
creosote brush.


40.74 Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3, at propor-
tionate distance; there is no remaining evidence of the
original corner.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.

T 41 S R 13 W



1978

Cor. is located in pasture land.

81.19 The cor. of secs. 2 and 3, common with the standard cor. of secs. 34 and 35, T. 40 S., R. 13 W., heretofore described.

From the cor. of secs. 33 and 34, on the S. bdy. of the Tp., heretofore described.

N. 0° 21' W., Bet. secs. 33 and 34.

Over gentle rolling land, within the city limits of Hurricane, Utah.

32.00 Utah State Highway No. 9, bears E and W.

40.03 The ¼ sec. cor. of secs. 33 and 34, monumented with a Washington County brass cap, set flush with surface of road and cemented in, mkd.

¼



1974


Cor. is located in road, bears N and S, and is accepted as the best available evidence of the position of the original corner.

N. 0° 13' W., beginning new measurement.

Asc. gentle SW slope.

39.92 The cor. of secs. 27, 28, 33, and 34, monumented with an iron post, 2½ ins. diam., extending 14 ins. above ground, set in concrete and in a mound of stone, 3½ ft. base, to top, with a Washington County brass cap, mkd.

T 41 S



R 13 W

1974

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS	
40.00	<p>Cor. is located in fence line, projecting E, W, and S, and is accepted as the best available evidence of the position of the original corner.</p> <hr/> <p>From the cor. of secs. 26, 27, 34, and 35.</p> <p>S. 89° 51' W., bet. secs. 27 and 34.</p> <p>Over rolling desert land, through sagebrush, shadscale, and creosote brush; along S side of road.</p> <p>The ¼ sec. cor. of secs. 27 and 34, monumented with a lava stone, 16 x 9 x 8 ins., firmly set 10 ins. in the ground and plainly mkd. ¼ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;">¼ $\frac{S\ 27}{S\ 34}$</p> <p style="text-align: center;">1978</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 2 ft. base, 1½ ft. high, N of cor.</p> <p>Cor. is located 30 lks. S of dirt road, bears E and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 51' W., beginning new measurement.</p>
40.02	<p>The cor. of secs. 27, 28, 33, and 34.</p> <hr/> <p>N. 0° 17' W., bet. secs. 27 and 28.</p> <p>Over rolling desert land, through sagebrush, shadscale, and creosote brush.</p> <p>39.98 The ¼ sec. cor. of secs. 27 and 28, monumented with a lava stone, 16 x 8 x 8 ins., firmly set 8 ins. in the ground and plainly mkd. ¼ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;">¼ S 28 S 27 </p> <p style="text-align: center;">1978</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS		
	<p>Deposit the mkd. stone and set a steel fence post alongside the iron post.</p>	
20.01	<p>N. 0° 17' W., beginning new measurement.</p> <p>Point for the N 1/16 sec. cor. of secs. 27 and 28.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 41 S R 13 W N 1/16</p> <p style="text-align: center;">S 28 S 27</p> <p style="text-align: center;">1978</p> <p>Cor. is located on steep N slope of canyon.</p>	
22.50	<p>Virgin River, drains S. 85° W.; asc. broken SW slope.</p>	
40.02	<p>The cor. of secs. 21, 22, 27, and 28, mkd. with a cross 6 ins. long, with 3 grooves on the E and 2 grooves on the S of cross, on a white sandstone boulder, 3 x 2 x 1 ft. above ground.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., over cross in a mound of stone, 6½ ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;">S 21 S 22 S 28 S 27</p> <p style="text-align: center;">1978</p> <p>Cor. is located on steep broken SW slope of canyon.</p>	
4.00	<p>From the cor. of secs. 22 and 27 only.</p> <p>S. 89° 46' W., bet. secs. 22 and 27.</p> <p>Over broken mountainous canyon land, through sagebrush, shadscale and creosote brush.</p> <p>Virgin River, drains S. 30° W.; asc. broken SE slope.</p>	
40.03	<p>The ¼ sec. cor. of secs. 22 and 27, monumented with a lava stone, 16 x 10 x 6 ins., firmly set in a mound of stone and plainly mkd. ¼ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., on solid rock, in a mound of stone, 4 ft. base, to top of brass cap mkd.</p> <p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;">¼ S 22 S 27</p> <p style="text-align: center;">1978</p>	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS	
19.84	<p>Deposit the mkd. stone in mound alongside the iron post.</p> <p>Cor. is located on rim of ledges, bears S. 80° W. and N. 80° E.</p> <hr/> <p>S. 89° 51' W., beginning new measurement.</p> <p>Along broken S slope of canyon.</p> <p>Point for the W 1/16 sec. cor. of secs. 22 and 27.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;">W 1/16 $\frac{S\ 22}{S\ 27}$</p> <p style="text-align: center;">1978</p>
37.50	Rim of canyon, bears NW and SE; desc. broken SW slope.
39.68	The cor. of secs. 21, 22, 27, and 28.
1.50 11.00 39.88	<p>N. 0° 25' W., bet. secs. 21 and 22.</p> <p>Over broken mountainous land, through sagebrush, shade scale and creosote brush; asc. steep SW slope.</p> <p>Rim of canyon, bears NW and SE; asc. gradual SW slope.</p> <p>Top of hill, bears NE and SW; desc. NW slope.</p> <p>The ¼ sec. cor. of secs. 21 and 22, monumented with a sandstone, 14 x 10 x 6 ins., firmly set 8 ins. in the ground and plainly mkd. ¼ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;">¼ S 21 S 22 </p> <p style="text-align: center;">1978</p> <p>Deposit the mkd. stone in mound alongside the iron post.</p> <hr/> <p>N. 0° 24' W., beginning new measurement.</p> <p>Asc. gradual SE slope.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS		
39.82	<p>The closing cor. of secs. 16 and 21, on the W. bdy. of sec. 22, monumented with a sandstone, 18 x 9 x 8 ins., firmly set 10 ins. in the ground and dimly mkd. CC on W face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C C T 41 S R 13 W</p> <p style="text-align: center;">S 16 S 21 S 22</p> <p style="text-align: center;">1978</p> <p>Deposit the mkd. stone and a squared pine post, 4 ft. long, alongside the iron post.</p>	
39.92	<p>Point for the 80 1/16 sec. cor. of sec. 22 only.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 41 S R 13 W 80 1/16</p> <p style="text-align: center;"> S 22</p> <p style="text-align: center;">1978</p>	
46.18	<p>The cor. of secs. 15 and 22 only, monumented with a sandstone, 15 x 12 x 10 ins., firmly set in a mound of stone and plainly mkd. 3 notches on the S and E edges.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;">S 16 S 15 S 22</p> <p style="text-align: center;">1978</p> <p>Deposit the mkd. stone in mound alongside the iron post.</p>	
38.85	<p>From the cor. of secs. 14, 15, 22, and 23.</p> <p>S. 89° 44' W., bet. secs. 15 and 22.</p> <p>Over broken mountainous land, through sagebrush, shade-scale and creosote brush; asc. W slope.</p> <p>The ¼ sec. cor. of secs. 15 and 22, monumented with a sandstone, 19 x 10 x 9 ins., firmly set 8 ins. in the ground and plainly mkd. ¼ on N face.</p> <p>At the corner point</p>	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 41 S R 13 W

¼ $\frac{S\ 15}{S\ 22}$

1978

Deposit the mkd. stone alongside the iron post.

Raise a mound of stone, 2 ft. base, 1½ ft. high N of cor.

West, beginning new measurement.

20.18 Point for the W 1/16 sec. cor. of secs. 15 and 22.

Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd.

T 41 S R 13 W

W 1/16 $\frac{S\ 15}{S\ 22}$

1978

Set a cedar post alongside the iron post.

40.36 The cor. of secs. 15 and 22 only.

N. 0° 42' W., along the W. bdy. of sec. 15.

Over broken mountainous land, through lightly scattering juniper growth; asc. SE slope.

33.41 Point for the ¼ sec. cor. of sec. 16 only.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 41 S R 13 W

¼ |
S 16 |

1978

39.96 Point for the ¼ sec. cor. of sec. 15 only, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS		
	<p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;"> 1/4 S 15</p> <p style="text-align: center;">1978</p>	
60.00	<p>Set a cedar post, alongside the iron post. Over rolling sandhills.</p>	
73.18	<p>Point for the closing cor. of secs. 9 and 16, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;">Cc S 9 S 15 S 16 </p> <p style="text-align: center;">1978</p>	
79.98	<p>Set a cedar post alongside the cor.</p> <p>Point for the cor. of secs. 10 and 15 only, at proportionate distance latitudinally and at record distance of westing from the cor. of secs. 10, 11, 14, and 15. There is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;">S 9 S 10 S 15</p> <p style="text-align: center;">1978</p>	
	<p>Set a cedar post alongside the iron post. Cor. is located in rolling sanddunes.</p>	
39.91	<p style="text-align: center;">(Restoring the 1877 Survey by T.C. Bailey and J.G. Burrill)</p> <hr style="width: 20%; margin: auto;"/> <p>From the cor. of secs. 10, 11, 14, and 15. N. 88° 41' W., bet. secs. 10 and 15. Over broken mountainous land, through lightly scattering juniper growth; asc. SE slope.</p> <p>Point for the 1/4 sec. cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of the original corner.</p>	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS		
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., on solid sandstone, in a mound of stone, 4½ ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;"> $\frac{1}{4} \frac{S 10}{S 15}$ </p> <p style="text-align: center;">1978</p>	
<p>59.865</p>	<p>Point for the W 1/16 sec. cor. of secs. 10 and 15.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;"> W 1/16 $\frac{S 10}{S 15}$ </p> <p style="text-align: center;">1978</p> <p>Set a cedar post alongside the iron post.</p> <p>Cor. is located on low sandy ridge, bears N and S.</p>	
<p>79.82</p>	<p>The cor. of secs. 10 and 15 only.</p>	
<p>32.95</p>	<p>(Restoring the 1877 Survey by Bailey and Burrill and the 1897 Retracement by W. Jenkin and J.A. West</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 40' W., bet. secs. 9 and 10.</p> <p>Over rolling desert land, through lightly scattering juniper growth.</p> <p>Point for the ¼ sec. cor. of sec. 9 only.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base to top of brass cap, mkd.</p> <p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;"> $\frac{1}{4} \frac{S 9}{S 9}$ </p> <p style="text-align: center;">1978</p>	
<p>40.10</p>	<p>Point for the ¼ sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the original corner. This corner now functions as the ¼ sec. cor. of sec. 10 only, identical with the SE cor. of the NE¼ of sec. 9.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS		
80.43	<p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;"> ¼ S 10 </p> <p style="text-align: center;">1978</p> <p>Cor. is located on gentle E slope.</p> <p>The cor. of secs. 3, 4, 9, and 10, monumented with a sandstone, 20 x 12 x 6 ins., firmly set 8 ins. in the ground and plainly mkd. 5 notches on the S and 3 notches on the E edges.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;">S 4 S 3 S 9 S 10</p> <p style="text-align: center;">1978</p> <p>Deposit the mkd. stone and set a cedar post alongside the iron post.</p> <p>Cor. is located in rolling sanddunes.</p>	
40.21	<p style="text-align: center;">(Restoring the 1870 Survey by Joseph Gorlinski)</p> <hr style="width: 20%; margin: auto;"/> <p>From the cor. of secs. 2, 3, 10, and 11.</p> <p>N. 89° 01' W., bet. secs. 3 and 10.</p> <p>Over rolling land, through lightly scattering juniper growth.</p> <p>Point for the ¼ sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground,, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;">¼ S 3 S 10</p> <p style="text-align: center;">1978</p> <hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">(Restoring the 1877 Survey by J.G. Burrill and T.C. Bailey)</p> <hr style="width: 20%; margin: auto;"/>	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS	
80.42	The cor. of secs. 3, 4, 9, and 10.
	N. 1° 18' W., bet. secs. 3 and 4.
	Over rolling sandy land, through lightly scattering juniper growth.
20.12	Point for the S 1/16 sec. cor. of secs. 3 and 4.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 S R 13 W
	S 1/16
	S 4 S 3
	1978
	Set a cedar post, 6 ft. long, alongside the cor.
40.24	The ¼ sec. cor. of secs. 3 and 4, monumented with a sandstone, 16 x 12 x 4 ins., firmly set 8 ins. in the ground and plainly mkd. ¼ on N face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, to top of brass cap, mkd.
	T 41 S R 13 W
	¼
	S 4 S 3
	1978
	Deposit the mkd. stone alongside the iron post.
	N. 1° 00' W., beginning new measurement.
20.15	Point for the N 1/16 sec. cor. of secs. 3 and 4.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 S R 13 W
	N 1/16
	S 4 S 3
	1978
	Set a cedar post alongside the iron post.
	Cor. is located in large draw, drains E.
40.10	The cor. of secs. 3 and 4, on the N. bdy. of the Tp., heretofore described.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS	
	<p>(Restoring the 1897 Survey by W. Jenkins and J.A. West)</p>
	<p>From the cor. of secs. 32 and 33, on the S. bdy. of the Tp., heretofore described.</p>
	<p>N. 0° 17' W., bet. secs. 32 and 33.</p>
	<p>Over rolling desert land, through sagebrush, shadscale, and creosote brush.</p>
31.00	<p>State Highway No. 9, bears E and W.</p>
40.08	<p>The $\frac{1}{4}$ sec. cor. of secs. 32 and 33, monumented with a Washington County survey marker, set in concrete, with brass cap mkd.</p>
	<p style="text-align: center;">T 41 S $\frac{1}{4}$ S 32 S 33</p>
	<p style="text-align: center;">R 13 W 1974</p>
	<p>Cor. is located at the cor. of fence, projecting N, S, and E, and is accepted as the best available evidence of the position of the original corner.</p>
	<p>N. 0° 14' W., beginning new measurement.</p>
39.75	<p>The cor. of secs. 28, 29, 32, and 33, monumented with a Washington County survey marker, set in concrete and in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T 41 S 29 28 32 33</p>
	<p style="text-align: center;">R 13 W 1974</p>
	<p>Cor. is located at the cor. of fence, projecting S and E, and is accepted as the best available evidence of the position of the original corner.</p>
	<p>From the cor. of secs. 27, 28, 33, and 34.</p>
	<p>S. 89° 55' W., bet. secs. 28 and 33.</p>
	<p>Over rolling mountainous land, through sagebrush, shadscale, and creosote brush.</p>
39.99	<p>The $\frac{1}{4}$ sec. cor. of secs. 28 and 33, monumented with a lava stone, 14 x 10 x 9 ins., firmly set 6 ins. in the ground and plainly mkd. $\frac{1}{4}$ on N face.</p>
	<p>At the corner point</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;">¼ $\frac{S\ 28}{S\ 33}$</p> <p style="text-align: center;">1978</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p style="text-align: center;">_____</p> <p>S. 89° 54' W., beginning new measurement.</p>
39.94	<p>The cor. of secs. 28, 29, 32, and 33.</p>
40.07	<p>N. 0° 14' W., bet. secs. 28 and 29.</p> <p>Over broken land, through sagebrush, shadscale, and creosote brush.</p> <p>The ¼ sec. cor. of secs. 28 and 29, monumented with a lava stone, 16 x 9 x 9 ins., firmly set 8 ins. in the ground and plainly mkd. ¼ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;">¼ S 29 S 28</p> <p style="text-align: center;">1978</p> <p>Deposit the mkd. stone and set a steel fence post alongside the iron post.</p> <p style="text-align: center;">_____</p>
19.94	<p>N. 0° 23' W., beginning new measurement.</p> <p>True point for the N 1/16 sec. cor. of secs. 28 and 29, falls on steep W slope of ledges.</p>
20.11	<p>Point selected for the witness cor. to the N 1/16 sec. cor. of secs. 28 and 29.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS	
	W C T 41 S R 13 W N 1/16 S 29 S 28 ↓ 1978
	Cor. is located on shelf in ledges above river.
32.00	Virgin River, drains W; asc. steep S slope.
37.00	Rim of canyon, bears W and SE; asc. broken SW slope.
39.88	Point for the cor. of secs. 20, 21, 28, and 29, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to solid sandstone, over a cross (X) and in a mound of stone, 4 ft. base, to top of brass cap, mkd.
	T 41 S R 13 W S 20 S 21 S 29 S 28 1978
	Cor. is located in small draw, drains S.
	From the cor. of secs. 21, 22, 27, and 28.
	S. 89° 51' W., bet. secs. 21 and 28.
	Over broken mountainous land, through sagebrush, shade-scale and creosote brush; desc. broken SW slope.
17.00	Virgin River, drains N. 45° W.; asc. NE slope.
19.99	Point for the E 1/16 sec. cor. of secs. 21 and 28.
	Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base, to top of brass cap, mkd.
	T 41 S R 13 W E 1/16 $\frac{S 21}{S 28}$ 1978
38.00	Enter bottom land along river.
39.98	Point for the ¼ sec. cor. of secs. 21 and 28, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS	
<p>59.97</p> <p>64.11</p>	<p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;">$\frac{1}{4} \frac{S 21}{S 28}$</p> <p style="text-align: center;">1978</p> <p>Set a cottonwood post, 10 ft. long, alongside the cor.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.</p> <p>True point for the W 1/16 sec. cor. of secs. 21 and 28, falls in Virgin River, drains S; asc. broken E slope.</p> <p>Point selected for the witness cor. to the W 1/16 sec. cor. of secs. 21 and 28.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p>
<p>76.00</p> <p>79.96</p>	<p style="text-align: center;">W C</p> <p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;">$W 1/16 \frac{S 21}{S 28}$</p> <p style="text-align: center;">1978</p> <p>Cor. is located on rim of canyon above river, bears N and S.</p> <p>Over rolling land.</p> <p>Desc. SW slope.</p> <p>The cor. of secs. 20, 21, 28, and 29.</p>
<p>39.89</p> <p>40.87</p>	<p>N. 0° 12' W., bet. secs. 20 and 21.</p> <p>Over broken mountainous land, through sagebrush, shade-scale and creosote brush; asc. SW slope.</p> <p>True point for the ¼ sec. cor. of secs. 20 and 21, at proportionate distance, falls on steep face of sandstone ledges; there is no remaining evidence of the original corner.</p> <p>Point selected for the witness cor. to the ¼ sec. cor. of secs. 20 and 21.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., on solid sandstone, in a mound of stone, 4½ ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">W C</p> <p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;">$\frac{1}{4}$</p> <p style="text-align: center;">S 20 S 21</p> <p style="text-align: center;">↓</p> <p style="text-align: center;">1978</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS					
<p>42.87</p> <p>79.78</p>	<p>Cor. is located on small sandstone shelf.</p> <p>Top of sandstone spur, slopes W; desc. steep NW slope.</p> <p>The cor. of secs. 16, 17, 20, and 21, monumented with a sandstone, 16 x 9 x 5 ins., firmly set 6 ins. in the ground and plainly mkd. 4 notches on E and 3 notches on the S edges.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 S R 13 W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 17</td> <td style="padding: 0 5px;">S 16</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 20</td> <td style="padding: 0 5px;">S 21</td> </tr> </table> <p style="text-align: center;">1978</p> <p>Deposit the mkd. stone and set a steel fence post alongside the iron post.</p>	S 17	S 16	S 20	S 21
S 17	S 16				
S 20	S 21				
<p>39.96</p>	<p>N. 89° 55' E., bet. secs. 16 and 21.</p> <p>Over rolling sandy land, through sagebrush, shadscale and creosote brush; asc. gentle E slope.</p> <p>Point for the ¼ sec. cor. of secs. 16 and 21, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 41 S R 13 W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">¼</td> <td style="padding: 0 5px;">S 16</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">S 21</td> </tr> </table> <p style="text-align: center;">1978</p>	¼	S 16		S 21
¼	S 16				
	S 21				
<p>79.60</p>	<p>Cor. is located on SW slope of hill.</p> <p>Asc. broken W slope.</p> <p>The closing cor. of secs. 16 and 21, heretofore described.</p> <p>From this point the 80 1/16 sec. cor. of sec. 22, bears N. 0° 24' W., 0.10 chs. dist., heretofore described.</p>				
<p>39.85</p>	<p>From the cor. of secs. 16, 17, 20, and 21.</p> <p>N. 0° 17' W., bet. secs. 16 and 17.</p> <p>Over rolling sandy land, through sagebrush, shadscale and creosote brush.</p> <p>The ¼ sec. cor. of secs. 16 and 17, monumented with a white sandstone, 12 x 7 x 6 ins., firmly set in a mound of stone and plainly mkd. ¼ on W face.</p>				

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 41 S R 13 W

$$\begin{array}{c} \frac{1}{4} \\ | \\ \text{S } 17 \quad | \quad \text{S } 16 \\ | \end{array}$$

1978

Deposit the mkd. stone and set a cedar post, 6 ft. long, alongside the iron post.

N. 1° 22' W., beginning new measurement.

40.24

The cor. of secs. 9 and 16 only, monumented with an iron post, 2½ ins. diam., extending 6 ins. above ground, with a Washington County brass cap mkd.

T 41 S

$$\begin{array}{c} \text{S } 17 \quad | \quad \text{S } 9 \\ \hline \quad \quad | \quad \text{S } 16 \end{array}$$

R 13 W
1974

Cor. is located in rolling sanddunes, and is accepted as the best available evidence of the position of the original corner.

S. 89° 38' E., bet. secs. 9 and 16.

Over rolling sandy land, through sagebrush, shadscale and creosote brush; desc. gentle SE slope.

40.79

The ¼ sec. cor. of secs. 9 and 16, monumented with a red sandstone, 22 x 12 x 10 ins., firmly set 8 ins. in the ground and plainly mkd. ¼ on N face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd.

T 41 S R 13 W

$$\begin{array}{c} \frac{1}{4} \quad \text{S } 9 \\ \hline \quad \quad \text{S } 16 \end{array}$$

1978

Deposit the mkd. stone alongside the iron post.

Cor. is located at base of hill, bears N and S.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS	
	S. 89° 40' E., beginning new measurement.
	Asc. broken W slope.
38.96	The closing cor. of secs. 9 and 16, heretofore described.
	From this point the cor. of secs. 10 and 15, bears N. 0° 42' W., 6.80 chs. dist., heretofore described.
	From the cor. of secs. 3, 4, 9, and 10.
	N. 89° 34' W., along the S. bdy. of sec. 4.
	Over broken mountainous land, through lightly scattering juniper growth; asc. gradual SE slope.
39.60	Point for the ¼ sec. cor. of sec. 9 only.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 41 S R 13 W</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">¼ S 9</p> <p style="text-align: center;">1978</p>
	Set a cedar post, 6 ft. long, alongside the cor.
40.19	Point for the ¼ sec. cor. of sec. 4 only, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 41 S R 13 W</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">¼ S 4</p> <p style="text-align: center;">1978</p>
	Set a cedar post alongside the iron post.
78.35	Point for the closing cor. of secs. 8 and 9, hereinafter described.
80.38	The cor. of secs. 4 and 5 only, monumented with a red sandstone, 24 x 12 x 4 ins., firmly set 10 ins. in the ground and plainly mkd. 5 notches on the S edge and 4 grooves on the E face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 41 S R 13 W</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">S 5 S 4</p> <p style="text-align: center;">S 8</p> <p style="text-align: center;">1978</p>
	Deposit the mkd. stone alongside the iron post.
	Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS	
	<p>(Restoring the 1877 Survey by Bailey and Burrill and the 1897 Retracement by Jenkins and West)</p> <hr/> <p>S. 88° 29' W., bet. secs. 5 and 8.</p> <p>Over rolling sandy land, through lightly scattering juniper growth.</p>
22.00	<p>Point for the E 1/16 sec. cor. of sec. 5 only.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 S R 13 W E 1/16 S 5 1978</p> <p>Set a steel fence post alongside the cor.</p>
43.80	Dirt road, bears N and S.
44.00	<p>The ¼ sec. cor. of secs. 5 and 8, monumented with an iron post, 2½ ins. diam., extending 6 ins. above ground, with Washington County brass cap mkd.</p> <p style="text-align: center;">T 41 S ¼ S 5 S 8 R 13 W 1974</p> <p>This position is accepted as the best available evidence of the position of the original corner.</p> <hr/> <p>S. 88° 26' W., beginning new measurement.</p>
43.61	<p>The cor. of secs. 5, 6, 7, and 8, monumented with an iron post, 2 ins. diam., extending 8 ins. above ground and in a collar of stone, with brass cap mkd. as described in the official record of the 1931 resurvey.</p> <hr/> <p>(Restoring the 1897 Survey by W. Jenkins and J.A. West)</p> <hr/> <p>From the cor. of secs. 9 and 16 only.</p> <p>N. 0° 15' E., along the W. bdy. of sec. 9.</p> <p>Over rolling sandy land, through lightly scattering juniper growth.</p>
4.87	<p>The closing cor. of secs. 8 and 17, monumented with an iron post, 2½ ins. diam., extending 6 ins. above ground, with a Washington County brass cap mkd.</p> <p style="text-align: center;">T 41 S CC S 8 S 9 S 17 R 13 W 1974</p>

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS		
	<p>This position is accepted as the best available evidence of the position of the original corner.</p> <p>Set a steel fence post alongside the cor.</p>	
25.48	<p>Point for the S 1/16 sec. cor. of sec. 8 only.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T 41 S R 13 W S 1/16 S 8 1978</p>	
39.77	<p>Set a pine post, 4 x 4 ins. square, alongside the cor.</p> <p>The ¼ sec. cor. of sec. 9 only, monumented with a sandstone, 16 x 10 x 5 ins., firmly set and dimly mkd. ¼ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T 41 S R 13 W ¼ S 9 1978</p>	
	<p>Deposit the mkd. stone alongside the iron post.</p> <p>Set a pine post, 5 ft. long, alongside the cor.</p>	
	<p style="text-align: center;">—————</p> <p>N. 0° 15' E., beginning new measurement.</p>	
6.32	<p>The ¼ sec. cor. of sec. 8 only, monumented with an iron post, 2½ ins. diam., extending 6 ins. above ground, with a Washington County brass cap mkd.</p>	
	<p style="text-align: center;">T 41 S ¼ S 8 R 13 W 1974</p>	
	<p>This position is accepted as a careful and faithful determination of the position of the corner.</p>	
39.77	<p>Point for the 80 1/16 sec. cor. of sec. 9 only.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base, to top of aluminum cap, mkd.</p>	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS	
47.50	<p style="text-align: center;">T 41 S R 13 W 80 1/16</p> <p style="text-align: center;"> S 9</p> <p style="text-align: center;">1978</p> <p>Intersect the S. bdy. of sec. 4.</p> <p>Point for the closing cor. of secs. 8 and 9.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C C T 41 S R 13 W</p> <p style="text-align: center;">S 4 ----- S 8 S 9 </p> <p style="text-align: center;">1978</p> <p>From this point an iron post, 2½ ins. diam., extending 8 ins. above ground, with Washington County brass cap mkd. T41S R13W C C S8 S9 1974, bears N. 0° 15' E., 0.07 chs. dist. Add the letters AM to the brass cap.</p> <p>This position is accepted as the best available evidence of the position of the original closing corner.</p> <p>From this same point the cor. of secs. 4 and 5 only, bears N. 89° 34' W., 2.03 chs. dist., heretofore described.</p>
40.10	<p style="text-align: center;">(Restoring the 1877 Survey by T.C. Bailey and J.G. Burrill)</p> <hr style="width: 20%; margin: auto;"/> <p>From the cor. of secs. 4 and 5 only.</p> <p>N. 2° 10' W., bet. secs. 4 and 5.</p> <p>Over rolling sandy land, through lightly scattering juniper growth.</p> <p>Point for the ¼ sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;">¼ S 5 S 4 </p> <p style="text-align: center;">1978</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS	
<p>60.15</p>	<p>Cor. is located on sandy NW slope.</p> <p>Point for the N 1/16 sec. cor. of secs. 4 and 5.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 S R 13 W N 1/16</p> <p style="text-align: center;">S 5 S 4</p> <p style="text-align: center;">1978</p> <p>Set a steel fence post alongside the cor.</p>
<p>74.50</p>	<p>Old highway, bears N. 52° E. and S. 52° W.</p>
<p>79.95</p>	<p>Fence on right-of-way line of Interstate 15, bears N. 41° 26' E. and S. 41° 26' W.</p>
<p>80.10</p>	<p>The cor. of secs. 4 and 5, on the N. bdy. of the Tp., heretofore described.</p>
	<p style="text-align: center;">(Restoring the 1897 Survey by Jenkins and West)</p> <hr style="width: 20%; margin: auto;"/> <p>From the cor. of secs. 31 and 32, on the S. bdy. of the Tp., heretofore described.</p> <p>N. 0° 14' W., bet. secs. 31 and 32.</p> <p>Along rolling W slope, through sagebrush and native grasses.</p> <p>13.00 Utah State Highway No. 9, bears E and W.</p> <p>40.01 The ¼ sec. cor. of secs. 31 and 32, monumented with a lava rock, 16 x 8 x 8 ins., firmly set in a mound of stone and plainly mkd. ¼ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;">¼ S 31 S 32 </p> <p style="text-align: center;">1978</p> <p>Deposit the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS						
39.94	<p>N. 0° 15' W., beginning new measurement.</p> <p>The cor. of secs. 29, 30, 31, and 32, monumented with a black lava rock, 18 x 10 x 10 ins., firmly set 10 ins. in the ground and plainly mkd. 1 notch on S and 5 notches on E edges.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 41 S R 13 W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 30</td> <td style="padding: 0 5px;">S 29</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 31</td> <td style="padding: 0 5px;">S 32</td> </tr> </table> <p style="text-align: center;">1978</p> <p>Deposit the mkd. stone alongside the iron post.</p>	S 30	S 29	S 31	S 32	
S 30	S 29					
S 31	S 32					
39.95	<p>From the cor. of secs. 28, 29, 32, and 33.</p> <p>N. 89° 58' W., bet. secs. 29 and 32.</p> <p>Over rolling sandy land and lava flows, through sagebrush and native grasses.</p> <p>The ¼ sec. cor. of secs. 29 and 32, monumented with a black lava rock, 16 x 10 x 8 ins., firmly set 10 ins. in the ground and plainly mkd. ¼ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 S R 13 W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 0 5px;">¼</td> <td style="border-right: 1px solid black; padding: 0 5px;">S 29</td> <td style="padding: 0 5px;">S 32</td> </tr> </table> <p style="text-align: center;">1978</p> <p>Deposit the mkd. stone alongside the iron post.</p>	¼	S 29	S 32		
¼	S 29	S 32				
40.14	<p>N. 89° 58' W., beginning new measurement.</p> <p>The cor. of secs. 29, 30, 31, and 32.</p>					
10.00	<p>S. 89° 55' W., bet. secs. 30 and 31.</p> <p>Desc. W slope over lava flow and sandy land, through sagebrush and native grasses.</p> <p>Over nearly level land.</p>					

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS		
39.92	<p>The $\frac{1}{4}$ sec. cor. of secs. 30 and 31, monumented with a lava rock, 16 x 12 x 12 ins., firmly set 8 ins. in the ground and plainly mkd. $\frac{1}{4}$ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;">$\frac{1}{4} \frac{S 30}{S 31}$</p> <p style="text-align: center;">1978</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high to N.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. $89^{\circ} 57'$ W., beginning new measurement.</p>	
39.87	<p>Point for the 80 $\frac{1}{16}$ sec. cor. of secs. 30 and 31.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;">$\frac{1}{16} \frac{S 30}{S 31} 80$</p> <p style="text-align: center;">1978</p> <p>Cor. is located on ledges above Virgin River, bears NE and SE.</p>	
51.95	<p>Intersect the E. bdy. of sec. 25, T. 41 S., R. 14 W. Point for the closing cor. of secs. 30 and 31, at proportionate distance.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 41 S R 14 W R 13 W</p> <p style="text-align: center;">$S 25 \left \frac{S 30}{S 31} \right. CC$</p> <p style="text-align: center;">1978</p> <p>Set 5 ft. cedar post alongside the iron post.</p> <p>From this cor., the angle point for secs. 25 and 31, on the E. bdy. of T. 41 S., R. 14 W., bears S. $0^{\circ} 10'$ W., 3.895 chs. dist., as described in the concurrent resurvey of T. 41 S., R. 14 W.</p>	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS

Point for the W $\frac{1}{4}$ sec. cor. of sec. 31, on the E. bdy. of T. 41 S., R. 14 W., and midpoint bet. the closing cor. of secs. 30 and 31, and the closing cor. of Tps. 41 and 42 S. R. 13 W.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 41 S
R 14 W R 13 W

| $\frac{1}{4}$
|
| S 31

1978

From this point, the $\frac{1}{4}$ sec. cor. of sec. 36, T. 41 S., R. 14 W., bears S. $0^{\circ} 22'$ W., 5.25 chs. dist., set and mkd. as described in the field notes of the concurrent resurvey of T. 41 S., R. 14 W.

Cor. is located 1 lk. W and 5 lks. N of four strand barb wire fence cor., bears N, S, and E.

From the cor. of secs. 29, 30, 31, and 32.

N. $0^{\circ} 15'$ W., bet. secs. 29 and 30.

Over rolling NW slope, through sagebrush and native grasses.

19.99 Point for the S $\frac{1}{16}$ sec. cor. of secs. 29 and 30.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, $4\frac{1}{2}$ ft. base, to top of brass cap, mkd.

T 41 S R 13 W
S $\frac{1}{16}$

S 30 | S 29

1978

39.98 The $\frac{1}{4}$ sec. cor. of secs. 29 and 30, monumented with a lava rock, 12 x 10 x 8 ins., firmly set 10 ins. in the ground and plainly mkd. $\frac{1}{4}$ on W face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 41 S R 13 W

| $\frac{1}{4}$
|
S 30 | S 29

1978

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS		
	<p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3½ ft. base, 1½ ft. high to W.</p> <p>Cor. is located in a fence line, bears N and S.</p>	
	<p>N. 0° 15' W., beginning new measurement.</p>	
7.75	<p>Rim of perpendicular cliffs above Virgin River, bears E and W.</p>	
11.00	<p>N bank of Virgin River, drains W; asc. S slope.</p>	
19.94	<p>Point for N 1/16 sec. cor. of secs. 29 and 30.</p>	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T 41 S R 13 W N 1/16</p>	
	<p style="text-align: center;">S 30 S 29</p>	
	<p style="text-align: center;">1978</p>	
	<p>Set 6 ft. steel fence post alongside the iron post.</p>	
39.88	<p>The cor. of secs. 19, 20, 29, and 30, monumented with a black lava rock, 18 x 10 x 8 ins., firmly set 10 ins. in the ground and plainly mkd. 2 notches on S and 5 notches on E edges.</p>	
	<p>At the corner point</p>	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p>	
	<p style="text-align: center;">T 41 S R 13 W</p>	
	<p style="text-align: center;">S 19 S 20 S 30 S 29</p>	
	<p style="text-align: center;">1978</p>	
	<p>Deposit the mkd. stone and set a 6 ft. steel fence post, alongside the iron post.</p>	
	<p>From the cor. of secs. 20, 21, 28, and 29.</p>	
	<p>S. 89° 59' W., bet. secs. 20 and 29.</p>	
	<p>Along gently rolling S slope, through sagebrush and native grasses.</p>	
40.00	<p>Point for the ¼ sec. cor. of secs. 20 and 29, at proportionate distance; there is no remaining evidence of the original corner.</p>	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS	
	<p>T 41 S R 13 W</p> <p>$\frac{1}{4}$ $\frac{S\ 20}{S\ 29}$</p> <p>1978</p>
46.00	Right bank of Virgin River, drains NW.
48.00	Left bank of Virgin River, drains NW, along S. bank of flood area.
60.00	Point for the W 1/16 sec. cor. of secs. 20 and 29.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>T 41 S R 13 W</p> <p>W 1/16 $\frac{S\ 20}{S\ 29}$</p> <p>1978</p>
	From which 6 ft. steel fence post, bears North 0.05 chs. dist.
64.00	Virgin River, drains S.
80.00	The cor. of secs. 19, 20, 29, and 30.
	S. 89° 57' W., bet. secs. 19 and 30.
	Over a series of ridges, spurs and draws, draining SW; through sagebrush and native grasses.
18.71	Intersect line 1-4, M.S. No. 6849 Utah lode at a point from which Cor. No. 1 bears N. 35° 51' E., 2.03 chs. dist. monumented with an iron pipe, 2 ins. diam., extending 24 ins. out of a mound of stone and punch marked U-1-6849.
	From the same point of intersection Cor. No. 4, Utah lode M.S. No. 6849, bears S. 35° 51' W., 20.706 chs. dist., monumented with an iron post, 2 ins. diam., extending 3½ ft. out of ground and punch marked U-4-6849; from which
	Cor. No. 2, Lot No. 68 Stormont Mill site bears S. 6° 40' E., 18.73 chs. dist., monumented with a squared decayed pine post, in a mound of stone, scribed Lot 68.
39.88	The ¼ sec. cor. of secs. 19 and 30, monumented with a red sandstone, 16 x 12 x 9 ins., firmly set 10 ins. in the ground and plainly mkd. ¼ on N face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>T 41 S R 13 W</p> <p>$\frac{1}{4}$ $\frac{S\ 19}{S\ 30}$</p> <p>1978</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS

Deposit the mkd. stone and set a 6 ft. steel fence post alongside the iron post.

Raise a mound of stone, 3 ft. base, 1½ ft. high to N.

S. 89° 53' W., beginning new measurement.

1.283 Intersect line 2-3, M.S. No. 6849 Maud lode at a point from which Cor. No. 2 bears N. 35° 51' E., 4.172 chs. dist., monumented with an iron post, 2 ins. diam., extending 2 ft. out of ground, mkd. M2 6849.

From this same point of intersection, Cor. No. 3, identical with Cor. No. 2 of the Arizona lode, M.S. No. 6849, bears S. 35° 51' W., 18.565 chs. dist., monumented with an iron pipe, 2 ins. diam., extending 2 ft. out of ground, punch mkd. A2 M3 6849.

39.94 Point for the 80 1/16 sec. cor. of secs. 19 and 30.

Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.

T 41 S R 13 W
1/16 $\frac{S 19}{S 30}$ 80
1978

51.16 The closing cor. of secs. 19 and 30, on the E. bdy. of T. 41 S., R. 14 W., monumented with a sandstone, 24 x 9 x 9 ins., firmly set in a mound of stone and plainly mkd. 4 notches on N and 2 notches on S edges with CC on E face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., over cross on solid rock, in a mound of stone, 4½ ft. base, to top of brass cap mkd.

C C
T 41 S
R 14 W R 13 W
S 24 $\frac{| S 19}{| S 30}$
1978

Deposit the mkd. stone in mound alongside the iron post.

From this cor., the cor. of secs. 24 and 25, T. 41 S., R. 14 W., bears S. 0° 26' W., 0.80 chs. dist., set and mkd. as described in the concurrent resurvey of T. 41 S., R. 14 W.

True point for the ¼ sec. cor. of sec. 30, on the E. bdy. of T. 41 S., R. 14 W., and mid point bet. closing cors. falls in Virgin River.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS

From which point selected for its witness cor., bear
N. 0° 10' E., 2.945 chs. dist.

Set an iron post, 28 ins. long, 2½ ins. diam., on solid
sandstone, in a mound of stone, 3½ ft. base, to top of
brass cap, mkd.

W C
T 41 S
R 14 W R 13 W
¼

↓ S 30
1978

From the true cor. point, the witness cor. to the
¼ sec. cor. of sec. 25, T. 41 S., R. 14 W., bears
N. 0° 10' E., 3.38 chs. dist., set and mkd. as described
in the concurrent resurvey of T. 41 S., R. 14 W.

From the cor. of secs. 19, 20, 29, and 30.

N. 0° 12' W., bet. secs. 19 and 20.

Over series of draws and spurs, draining SW, through
sagebrush and native grasses.

23.00 Dirt road, bears NE and SW.

29.99 Intersect line 1-4, M.S. No. 6849 Nevada lode at a point
from which Cor. No. 1 bears N. 42° 33' E., 1.39 chs.
dist., monumented with an iron pipe, 2 ins. diam., extend-
ing 30 ins. out of ground and punch marked N 1 6849.

From this same point of intersection, Cor. No. 4, identical
with Cor. No. 1 of Rough Rider No. 2, M.S. No. 6849 bears
S. 42° 33' W., 21.34 chs. dist., monumented with an iron
pipe, 2 ins. diam., extending 30 ins. out of mound of
stone, punch marked R-1 N-4 6849.

31.65 Intersect line 1-2 M.S. No. 6849 Nevada lode at a point
from which Cor. No. 1 bears S. 56° 04' E., 1.14 chs. dist.,
heretofore described.

From this same point of intersection, Cor. No. 2 M.S.
No. 6849 Nevada lode, bears N. 56° 04' W., 8.05 chs. dist.,
monumented with an iron pipe, 2 ins. diam., extending 30
ins. out of ground, punch marked N-2 6849.

35.37 Top of sandstone ridge, bears NE and SW. Desc. broken
NW slope.

37.38 Intersect line 3-4 M.S. No. 24, Lot No. 60 of the Requa
Mine, from which Cor. No. 3, bears N. 59° 51' W., 4.44
chs. dist., monumented with a 4 x 4 ins. pine post,
extending 4 ft. out of mound of stone. The old pine post,
with scribe marks US60 was lying in mound alongside the
post.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS	
	<p>From which</p> <p>A sandstone boulder, 6 ft. long, 5 ft. high, mkd. No. 3 US 60 BO., bears N. 67° 30' W., 95.7 ft. dist.</p> <p>A cedar tree, 9 ins. diam., blazed and mkd. No. 3 US 60 BO., bears S. 5° 30' E., 46.2 ft. dist.</p> <p>From this same point of intersection, Cor. No. 4 M.S. No. 24, Lot 60 of the Requa Mine, bears S. 59° 51' E., 3.71 chs. dist., monumented with a decayed pine stake in mound of stone, mkd. with faint scribe marks.</p> <p>From which</p> <p>A sandstone boulder, 1 ft. above ground, mkd. US60BO, bears N. 53° E., 277 ft. dist.</p>
39.90	<p>The ¼ sec. cor. of secs. 19 and 20, monumented with a red sandstone, 16 x 8 x 6 ins., firmly set 10 ins. in the ground and plainly mkd. ¼ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 41 S R 13 W</p> <p>¼</p> <p>S 19 S 20</p> <p>1978</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p> <p>From this point, U.S. mineral monument No. 2, bears N. 48° 37' E., 39.46 chs. dist., monumented with a squared pine post in a mound of stone, with faint scribe marks. Cor. is located on top of an old volcanic mountain.</p>
2.76	<p>N. 0° 19' W., beginning new measurement.</p> <p>Intersect line 2-3 M.S. No. 24 lot 60 of the Requa Mine at a point from which Cor. No. 2 bears N. 51° 24' E., 7.39 chs. dist., monumented with a 4 x 4 ins. pine post, extending 2 ft. out of a mound of stone, with scribe marks lot 60 on SE face.</p> <p>From this same point of intersection, Cor. No. 3 M.S. No. 24, lot 60 of Requa Mine bears S. 51° 24' W., 4.88 chs. dist., heretofore described.</p>
39.83	<p>The cor. of secs. 17, 18, 19, and 20, monumented with a sandstone, 14 x 6 x 6 ins., firmly set in a mound of stone and plainly mkd. 3 notches on S and 5 notches on E edges.</p> <p>At the corner point</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS		
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;"> $\begin{array}{c c} \hline \text{S 18} & \text{S 17} \\ \hline \text{S 19} & \text{S 20} \\ \hline \end{array}$ </p> <p style="text-align: center;">1978</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3 x 2 ft. high to W.</p>	
<p>32.00</p> <p>40.25</p>	<p>From the cor. of secs. 16, 17, 20, and 21.</p> <p>S. 89° 56' W., bet. secs. 17 and 20.</p> <p>Over rolling sandy land, through sagebrush and native grasses.</p> <p>Dirt road, bears N and S.</p> <p>The ¼ sec. cor. of secs. 17 and 20, monumented with a sandstone, 20 x 12 x 4 ins., firmly set 10 ins. in the ground and plainly mkd. ¼ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;"> $\frac{1}{4} \frac{\text{S 17}}{\text{S 20}}$ </p> <p style="text-align: center;">1978</p> <p>Deposit the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 56' W., beginning new measurement.</p> <p>Over rolling sandy land.</p> <p>The cor. of secs. 17, 18, 19, and 20.</p>	
<p>39.77</p>	<p>S. 89° 56' W., bet. secs. 18 and 19.</p> <p>Asc. broken SE slope, through sagebrush and native grasses.</p> <p>Point for the ¼ sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., on solid sandstone, in a mound of stone, 4½ ft. base, to top of brass cap, mkd.</p>	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS	
	<p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;">$\frac{1}{4} \frac{S 18}{S 19}$</p> <p style="text-align: center;">1978</p>
53.82	<p>The original witness point bet. secs. 18 and 19, monumented with a sandstone, 18 x 8 x 6 ins., firmly set 8 ins. in the ground and plainly mkd. WP on N face.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">A P</p> <p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;">$\frac{S 18}{S 19}$</p> <p style="text-align: center;">1978</p>
	<p>This cor. will now function as an angle point only.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Cor. is located on rim of basin, bears NW and SE; desc. W slope.</p>
	<p style="text-align: center;">S. 89° 45' W., beginning new measurement.</p>
25.68	<p>Point for the 80 1/16 sec. cor. of secs. 18 and 19.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;">80 1/16 $\frac{S 18}{S 19}$</p> <p style="text-align: center;">1978</p>
	<p>Raise a mound of stone, 4½ ft. base, 3 ft. high to N.</p>
36.35	<p>The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., set and mkd. as described in the concurrent resurvey of T. 41 S., R. 14 W.</p>
	<p>From the cor. of secs. 17, 18, 19, and 20.</p> <p>N. 0° 13' W., bet. secs. 17 and 18.</p> <p>Asc. SE slope, through sagebrush and native grasses.</p>
19.96	<p>Point for the S 1/16 sec. cor. of secs. 17 and 18.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, to top of brass cap, mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS

T 41 S R 13 W
S 1/16

S 18 | S 17

1978

39.92 The $\frac{1}{4}$ sec. cor. of secs. 17 and 18, monumented with a granite stone, 18 x 8 x 6 ins., firmly set 10 ins. in the ground and plainly mkd. $\frac{1}{4}$ on W face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 41 S R 13 W

$\frac{1}{4}$
|
S 18 | S 17

1978

Deposit the mkd. stone alongside the iron post.

Raise a mound of stone, 3 ft. base, 2 ft. high to W.

N. $90^{\circ} 53'$ W., beginning new measurement.

Along broken W slope.

44.43 Intersect the S. bdy. of sec. 8.

Point for the closing cor. of secs. 17 and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd.

T 41 S R 13 W

S 8

S 18 | S 17

C C
1978

From this point the cor. of secs. 7 and 8, bears S. $88^{\circ} 05'$ W., 1.82 chs. dist., hereinafter described.

From the cor. of secs. 7, and 8, monumented with an iron post, $2\frac{1}{2}$ ins. diam., set in concrete extending 10 ins. out of ground, with Washington County brass cap, mkd.

T 41 S

S 7 | S 8

S 18

R 13 W
1974

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS	
	<p>This point is accepted as the best available evidence of the position of the original cor.</p>
	<p>N. 89° 05' E., along the S. bdy. of sec. 8.</p>
	<p>Desc. broken E slope.</p>
1.82	<p>The closing cor. of secs. 17 and 18, heretofore described.</p>
23.52	<p>Point for the W 1/16 sec. cor. of sec. 17 only.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to shale rock, in a mound of stone, 3½ ft. base, to top of brass cap, mkd.</p>
	<p>T 41 S R 13 W <hr/> W 1/16 S 17 1978</p>
	<p>Cor. is located on S slope.</p>
41.86	<p>The ¼ sec. cor. of sec. 8 only, monumented with an iron post, 2½ ins. diam., in a mound of stone, 3 ft. base, extending 15 ins. out of ground, with Washington County brass cap mkd.</p>
	<p>T 41 S <hr/> ¼ S 8 R 13 W 1974</p>
	<p>This position is accepted as the best available evidence of the position of the original corner.</p>
	<p>N. 89° 06' E., beginning new measurement.</p>
3.36	<p>Point for the ¼ sec. cor. of sec. 17 only.</p>
	<p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p>
	<p>T 41 S R 13 W <hr/> ¼ S 17 1978</p>
16.00	<p>Dirt road, bears N and S.</p>
23.38	<p>Point for the E 1/16 sec. cor. of sec. 8 only.</p>
	<p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>
	<p>T 41 S R 13 W <hr/> E 1/16 S 8 1978</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

CHAINS	
46.76	<p>Set 1 in. pipe, 5 ft. long, alongside the aluminum post.</p> <p>The closing cor. of secs. 8 and 17, heretofore described.</p> <p>From this point the cor. of secs. 9 and 16 bears S. 0° 15' W., 4.87 chs. dist., heretofore described.</p>
S. 89° 12'	<p>(Restoring the 1877 Survey by Bailey and Burrill and the 1897 Retracement by Jenkins and West)</p> <hr/> <p>From the cor. of secs. 7 and 8.</p> <p>12' W., bet. secs. 7 and 18.</p> <p>Asc. NE slope, through sagebrush, scattered cedar trees and native grasses.</p>
20.425	<p>Point for the E 1/16 sec. cor. of secs. 7 and 18.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base, to top of aluminum cap, mkd.</p> <p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;">E 1/16 $\frac{S 7}{S 18}$</p> <p style="text-align: center;">1978</p>
40.85	<p>The ¼ sec. cor. of secs. 7 and 18, monumented with an iron post, 2½ ins. diam., extending 1 ft. out of the ground and in a mound of stone, with Washington County brass cap, mkd.</p> <p style="text-align: center;">T 41 S</p> <p style="text-align: center;">$\frac{¼ S 7}{S 18}$</p> <p style="text-align: center;">1974</p>
20.35	<p>A sandstone, 18 x 12 x 5 ins., plainly mkd. ¼ is in the mound alongside the iron post.</p> <p>Cor. is located 2 lks. N of E - W four-strand barbwire fence line and on top of ridge bears N and S.</p> <hr/> <p>S. 89° 15' W., beginning new measurement.</p> <p>Desc. NW slope.</p>
	<p>Point for the W 1/16 sec. cor. of secs. 7 and 18.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., on solid sandstone and over a cross (X), in a mound of stone, 5 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 41 S R 13 W</p> <p style="text-align: center;">W 1/16 $\frac{S 7}{S 18}$</p> <p style="text-align: center;">1978</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 41 S., R. 13 W., Salt Lake Meridian, Utah

<p>CHAINS</p> <p>40.70</p>	<p>Point for the cor. of secs. 7, 12, 13, and 18, as described in the concurrent resurvey of T. 41 S., R. 14 W.</p> <hr/> <p style="text-align: center;">General Description</p> <p>Township 41 South, Range 13 West, is situated about 10 miles NE of St. George, Utah, with the towns of Leeds, La Verkin, Toquerville, and Hurricane located within the township. The elevation varies from 2800 to 4400 ft. above sea level. The soil is mostly sandy, with clay on the brakes in the E and W portion of the township.</p> <p>The Virgin River crosses the township in the south portion from E to W, with Ash Creek and La Verkin Creek draining into it from N to S in the east part of the township.</p> <p>An abandon mining operation is situated in secs. 19, 20 and 30. No other mining deposits of value were noted. There is no timber in the township.</p> <p>Interstate Highway 15 crosses the NE cor. of the township and State Highway No. 9 crosses the south and east portion of the township. There are numerous other improved and unimproved roads throughout the township.</p> <p>The mean magnetic declination is 14° 30' E., as taken from U.S. geological map 1-911.</p>	
----------------------------	--	--

CERTIFICATE OF SURVEY

XXX(We), Craig P. Sylvester, Gail E. Reynolds and Ferrel D. Reynolds, Cadastral Surveyors, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 29th day

of March, 1978, XX(We) have dependently resurveyed a portion of the south boundary of T. 40 S., R. 13 W., (Eighth Standard Parallel South) a portion of the south, and east boundaries and a portion of the subdivisional lines of Township 41 South, Range 13 West,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by XXX(us) and under XXX(our) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

October 9, 1980 (Date) [Signature: Craig P. Sylvester] (Cadastral Surveyor)
October 9, 1980 (Date) [Signature: Gail E. Reynolds] (Supervisor)
October 9, 1980 (Date) [Signature: Ferrel D. Reynolds] (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the south boundary of T. 40 S., R. 13 W., (Eighth Standard Parallel South) a portion of the south and east boundaries and a portion of the subdivisional lines of Township 41 South, Range 13 West, Salt Lake Meridian, Utah

executed by Craig P. Sylvester, Supervisory Cadastral Surveyor
Gail E. Reynolds, Supervisory Cadastral Surveyor
Ferrel D. Reynolds, Cadastral Surveyor
having been critically examined and found correct, are hereby approved.

MAR 17 1982 (Date) [Signature: Faustin B. Padilla] ACTING (Chief, Cadastral Survey Examination and Approval Staff)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

[Signature line for transcript certification]

INDEX DIAGRAM

Township 41 S., Range 14 W.

6	5	4	3	2	1
7	8	9	10	11 12	12
18	17	16	15 11	14 8 11	13 4 7
19	20	21	22 10	23 6 9	24 3 6
30	29	28	27	26	25 2
31	32	33	34	35	36 2

Township 41 South, Range 14 West, Salt Lake Meridian, Utah

CHAINS

T. 41 S., R. 14 W.

History of Surveys

Surveyed by Retr. or Resurveyed by

NORTH BOUNDARY (Eighth Standard Parallel South)

E. 1 mile	Bailey and Burrill	1877	
E. 1 mile		H.D. Heist	1902
W. 5 miles	H.D. Heist	1902	
S. Bdy., Secs. 31, 32, 34, 35		H.G. Mason	1918-1919
E. 1 mile		R.C. Yundt	1949

EAST BOUNDARY (Second Guide Meridian West)

All	Joseph Gorlinski	1870	
N. 1 mile		Bailey and Burrill	1877
All		Jenkins and West	1897
S. 2 miles		H.G. Mason	1918-1919
W. Bdy., secs. 7 and N $\frac{1}{2}$ mile of W. Bdy., Sec. 18, T. 41 S., R. 13 W.		A. Nelson	1931
N. 2 $\frac{1}{2}$ miles		R.C. Yundt	1949

SOUTH BOUNDARY

All	Julien Bausman	1870	
All		M.H. Dalley	1899
All except S. Bdy., Sec. 34		H.G. Mason	1918-1919

WEST BOUNDARY

All	Stewart and Snow	1909	
N. 1 mile		H.G. Mason	1918-1919

SUBDIVISION

Portion	Joseph Gorlinski	1870	
Portion		Bailey and Burrill	1877
Portion	Bailey and Burrill	1877	
Completion	H.G. Mason	1918-1919	
Portion		R.C. Yundt	1949

The following field notes are those of the dependent re-survey of the south 4 miles of the east boundary, (Second Guide Meridian West) and a portion of the subdivisional lines of Township 41 South, Range 14 West, Salt Lake Meridian, Utah.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated March 29, 1978.

The directions of the lines of this survey were determined by reference to the true meridians established on line by hour angle observations on Polaris. They were carried forward by sustained angulation, being supplemented by numerous other observations on Polaris taken throughout the progress of the survey.

Township 41 South, Range 14 West, Salt Lake Meridian, Utah

CHAINS

The distances along surveyed lines were determined by electronic measurement.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the southeast corner of sec. 24, as scaled from the Hurricane Quadrangle Map, 1954, 15' series; is as follows:

Latitude 37°12.2' N. Longitude 113°21.7' W.

The mean magnetic declination of 14° 30' E., was computed from U.S. Geological Survey map "1-911.

Dependent Resurvey of the Second Guide Meridian West, (E. Bdy., T. 41 S., R. 14 W.,) Salt Lake Meridian, Utah

(Restoring the 1870 Survey of J. Gorlinski and the 1918-19 Resurvey of H.G. Mason)

Beginning at the cor. of Tps. 41 and 42 S., R. 14 W., monumented with an iron post, 3 ins. diam., extending 10 ins. above ground, with brass cap mkd. as described in the official record of the 1918 resurvey.

N. 0°07' E., along E. bdy. of sec. 36.

Over gently rolling sandy land, through sagebrush and native grasses.

6.91 The closing cor. of secs. 6 and 31, Tps. 41 and 42 S., R. 13 W., set and mkd. as described in the concurrent resurvey of T. 41 S., R. 13 W.

41.68 The ¼ sec. cor. of sec. 36, monumented with an iron post, 1 in. diam., extending 12 ins. above concrete, with brass cap mkd. as described in the official record of the 1918 resurvey.

N. 0°22' E., beginning new measurement.

Over gently rolling land.

5.25 The ¼ sec. cor. of sec. 31, T. 41 S., R. 13 W., set and mkd. as described in the concurrent resurvey of T. 41 S., R. 13 W.

38.55 The cor. of secs. 25 and 36, monumented with an iron post, 2 ins. diam., extending 10 ins. above ground, with brass cap mkd. as described in the official record of the 1918 resurvey.

N. 0°23' E., along E. bdy. of sec. 25.

Over nearly level cleared field.

Dependent Resurvey of the Second Guide Meridian West,
(E. Bdy., T. 41 S., R. 14 W.) Salt Lake Meridian, Utah

CHAINS	
2.82	<p>Point for the angle point for secs. 25 and 31, at proportionate distance based on the irregular boundary method; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">AP T 41 S R 14 W R 13 W</p> <p style="text-align: center;">S 25 S 31</p> <p style="text-align: center;">1978</p>
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high to W.</p>
	<p>N. 0°10' E., beginning new measurement.</p>
3.895	<p>The closing cor. of secs. 30 and 31, T. 41 S., R. 13 W., set and mkd. as described in the concurrent resurvey of T. 41 S., R. 13 W.</p>
26.00	<p>Left bank of Virgin River, bears NE and SW, through river bottom.</p>
37.33	<p>True point for the ¼ sec. cor. of sec. 25, at proportionate distance, falls in river bottom and cannot be monumented.</p>
43.79	<p>True point for the ¼ sec. cor. of sec. 30, T. 41 S., R. 13 W., falls in river.</p>
44.50	<p>Right bank of Virgin River, bears NE and SW; asc. broken SE slope.</p>
46.735	<p>The witness cor. to the ¼ sec. cor. of sec. 30, T. 41 S., R. 13 W., set and mkd. as described in the concurrent resurvey of T. 41 S., R. 13 W.</p>
47.17	<p>The original witness cor. to the ¼ sec. cor. of sec. 25, monumented with an iron post, 1 in. diam., extending 14 ins. above ground, with brass cap mkd. as described in the official record of the 1918 resurvey.</p>
	<p>N. 0°34' E., beginning new measurement.</p>
	<p>Asc. broken SE slope.</p>
35.72	<p>The cor. of secs. 24 and 25, monumented with an iron post, 3 ft. long, 2 ins. diam. set on solid rock and in a mound of stone, 4 ft. base, to top of brass cap, mkd. as described in the official record of the 1918 resurvey.</p>
	<p style="text-align: center;">(Restoring the 1870 Survey by J. Gorlinski and the 1897 Resurvey by Jenkins and West)</p>
	<p>N. 0°26' E., along E. bdy. of sec. 24.</p>
	<p>Desc. N slope over broken sandstone ledges.</p>

Dependent Resurvey of the Second Guide Meridian West,
(E. Bdy., T. 41 S., R. 14 W.,) Salt Lake Meridian, Utah

CHAINS

0.80 The closing cor. of secs. 19 and 30, T. 41 S., R. 13 W., set and mkd. as described in the concurrent resurvey of T. 41 S., R. 13 W.

24.81 The original witness cor. to the 1/4 sec. cor. of secs. 19 and 24, monumented with a black sandstone, 30 x 16 x 8 ins., firmly set in crack on edge of ledge, plainly mkd. 1/4 on W face. Add the marks AP to top of original stone cor. This point is not suitable for remonumentation and will act as an angle point only.


N. 0°20' E., beginning new measurement.

Desc. N slope through nearly barren land.

15.76 Point for the 1/4 sec. cor. of secs. 19 and 24, at proportionate distance.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 41 S
R 14 W R 13 W



1978


Cor. is located on steep N slope of small gypsum hill.

55.58 The cor. of secs. 13, 18, 19, and 24, monumented with a sandstone, 20 x 9 x 7 ins., firmly set 10 ins. in the ground and plainly mkd. 3 notches on N and S edges.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd.

T 41 S
R 14 W R 13 W



1978

Deposit the mkd. stone alongside the iron post.

Cor. is located on small spur, slopes SE.

N. 3°44' W., bet. secs. 13 and 18.

Asc. broken S slope over sandstone ledges.

14.23 The original witness cor. to the cor. of secs. 13, 18, 19, and 24, monumented with a sandstone, 24 x 9 x 9 ins., firmly set in a mound of stone and plainly mkd. WC on S face. No other marks identified. This cor. will now act as an angle point bet. secs. 13 and 18.

Dependent Resurvey of the Second Guide Meridian West,
(E. Bdy., T. 41 S., R. 14 W.,) Salt Lake Meridian, Utah

CHAINS

At the angle point

Set an iron post, 28 ins. long, 2½ ins. diam., on solid rock and in a mound of stone, 5 ft. base, to top of brass cap, mkd.

AP
T 41 S
R 14 W R 13 W

S 13 | S 18

1978

Deposit the mkd. stone alongside the iron post.

The angle point is located on top of ledges, bears E and W.

N. 0°02' W., beginning new measurement.

Asc. rolling S slope, through sagebrush and widely scattered juniper trees.

27.62 The ¼ sec. cor. of secs. 13 and 18, monumented with an iron post, 1 in. diam., extending 12 ins. above ground and in a mound of stone, 3 ft. base, to top of brass cap, mkd. as described in the official record of the 1949 resurvey.

(Restoring the 1870 Survey by J. Gorkinski and
the 1949 Resurvey by R.C. Yundt)

N. 0°02' W., beginning new measurement.

Desc. NW slope.

20.48 Point for the N 1/16 sec. cor. of secs. 13 and 18.

Set an iron post, 28 ins. long, 2½ ins. diam., 9 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base, to top of brass cap, mkd.

T 41 S
R 14 W R 13 W

N 1/16
S 13 | S 18

1978

Cor. is located on NW slope.

31.00 Base of mountain, bears NE and SW; enter orchard and cultivated land.

40.96 Point for the cor. of secs. 7, 12, 13, and 18, determined from a reference monument established in the 1949 resurvey.

Dependent Resurvey of the Second Guide Meridian
West, (E. Bdy., T. 41 S., R. 14 W.,) Salt Lake Meridian

CHAINS	
	<p>from which</p> <p>An iron post, 1 in. diam., extending 8 ins. above ground, bears S. 89°56' W., 130 lks. dist., with brass cap mkd. RM S12 S13 1949, and an arrow pointing to the true cor. point.</p> <p>An iron post, 2½ ins. diam., extending 8 ins. above ground bears North 139 lks. dist., with Washington County brass cap, mkd. RM.</p>
	<p>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 41 S., R. 14 W., Salt Lake Meridian, Utah</p>
	<p>(Restoring the 1877 Survey by T.C. Bailey and the 1918-19 Resurvey by H.G. Mason)</p> <hr/> <p>From the cor. of secs. 24 and 25, on the E. bdy. of the Tp., heretofore described.</p> <p>N. 88°27' W., bet. secs. 24 and 25.</p> <p>Over broken SE slope, through sagebrush, shadscale, and creosote brush.</p>
40.40	<p>The ¼ sec. cor. of sec. 24, monumented with an iron post, 1 in. diam., projecting 24 ins. above ground and in a mound of stone, with brass cap mkd. as described in the official record of the 1919 resurvey.</p> <hr/> <p>N. 88°28' W., beginning new measurement.</p>
0.44	<p>The ¼ sec. cor. of sec. 25, monumented with a black lava stone, 18 x 10 x 8 ins., firmly set in a mound of stone and plainly mkd. ¼ on S face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 5 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 41 S R 14 W</p> <hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">¼ S 25</p> <p style="text-align: center;">1978</p> <p>Deposit the mkd. stone alongside the iron post.</p>
40.41	<p>The cor. of secs. 23, 24, 25, and 26, monumented with an iron post, 2 ins. diam., projecting 12 ins. above ground and in a collar of stone, with brass cap mkd. as described in the official record of the 1918 resurvey.</p>
	<p>(Restoring the 1877 Survey by T.C. Bailey)</p> <hr/> <p>N. 0°21' W., bet. secs. 23 and 24.</p> <p>Over broken mountainous land; asc. SW slope, through scattering undergrowth.</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 41 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS	
40.58	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 41 S R 14 W</p> <p style="text-align: center;"> $\frac{1}{4}$ S 23 S 24 1978 </p> <p>Cor. is located on NW slope of ridge.</p>
81.16	<p>The cor. of secs. 13, 14, 23, and 24, monumented with a sandstone, 30 x 12 x 6 ins., firmly set and plainly mkd. 3 notches on the S and 1 notch on the E edges.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., on solid rock, over a cross (X), in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 41 S R 14 W</p> <p style="text-align: center;"> <u>S 14 S 13</u> <u>S 23 S 24</u> 1978 </p> <p>Deposit the mkd. stone in mound alongside the iron post.</p> <p>Cor. is located on W slope of hill.</p>
	<p>From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., heretofore described.</p> <p>N. $87^{\circ}51'$ W., bet. secs. 13 and 24.</p> <p>Over broken mountainous land, through scattering undergrowth; asc. SE slope.</p>
41.02	<p>The $\frac{1}{4}$ sec. cor. of secs. 13 and 24, monumented with a sandstone, 26 x 12 x 8 ins., firmly set in a mound of stone and plainly mkd. $\frac{1}{4}$ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 41 S R 14 W</p> <p style="text-align: center;"> $\frac{1}{4}$ <u>S 13</u> <u>S 24</u> 1978 </p> <p>Deposit the mkd. stone alongside the iron post.</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 41 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS		
40.86	<p>Cor. is located on NW slope of hill.</p> <hr style="width: 20%; margin: 0 auto;"/> <p>N. 87°59' W., beginning new measurement.</p> <p>The cor. of secs. 13, 14, 23, and 24.</p>	
3.00 20.33	<p>N. 0°16' E., bet. secs. 13 and 14.</p> <p>Over mountainous land, through scattering undergrowth; desc. NW slope.</p> <p>Creek, 10 lks. wide, 2 ins. deep, drains SW; asc. SE slope.</p> <p>Point for the S 1/16 sec. cor. of secs. 13 and 14.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 5 ft. base, to top of brass cap, mkd.</p>	
	<p>T 41 S R 14 W S 1/16</p> <p>S 14 S 13</p> <p>1978</p>	
23.32	<p>Intersect Interstate 15 highway right-of-way line, from which right-of-way marker Station No. 771+10 bears N. 35°35' E., 0.047 chs. dist., and right-of-way marker Station No. 758+00 bears S. 35°35' W., 19.427 chs. dist.</p>	
28.15	<p>Center line of N bound lane, bears N. 40°12' E., and S. 40°12' W.</p>	
32.35	<p>Center line of S bound lane, bears N. 43°37' E. and S. 43°37' W.</p>	
35.20	<p>Intersect Interstate 15 highway right-of-way line, from which right-of-way marker Station No. 777+00 bears N. 38°36' E., 0.024 chs. dist., and right-of-way marker Station No. 753+20.8 bears S. 38°36' W., 36.534 chs. dist.</p>	
40.66	<p>The ¼ sec. cor. of secs. 13 and 14, monumented with a red sandstone, 20 x 12 x 2 ins., firmly set and plainly mkd. ¼ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 41 S R 14 W</p> <p style="text-align: center;">¼</p> <p style="text-align: center;">S 14 S 13</p> <p style="text-align: center;">1978</p> <p>Deposit the mkd. stone in mound alongside the iron post.</p>	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 41 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS	
	Cor. is located on small spur, projecting SW.
	N. 0°31' E., beginning new measurement.
20.03	Point for the N 1/16 sec. cor. of secs. 13 and 14.
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.
	<p style="text-align: center;">T 41 S R 14 W N 1/16</p>
	<p style="text-align: center;">S 14 S 13</p>
	<p style="text-align: center;">1978</p>
40.06	The cor. of secs. 11, 12, 13, and 14, monumented with an iron post, 2 ins. diam., projecting 10 ins. above ground and in a collar of stone, with brass cap mkd. as described in the official record of the 1949 resurvey.
	<p style="text-align: center;">(Restoring the 1877 Survey by T.C. Bailey and the 1918-19 Resurvey by H.G. Mason)</p>
	From the cor. of secs. 23, 24, 25, and 26.
	N. 82°36' W., bet. secs. 23 and 26.
	Over broken mountainous land, through scattering undergrowth; desc. gentle SW slope.
22.00	Trail road, bears NW and SE; over bottom land
24.00	Quail Creek, 10 lks. wide, 4 ins. deep, flows S.
39.58	The ¼ sec. cor. of secs. 23 and 26, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, with brass cap mkd. as described in the official record of the 1918 resurvey.
	Cor. is located on broken NW slope of hill.
	<p style="text-align: center;">(Restoring the 1870 Survey by J. Gorlinski and the 1918-19 Resurvey by H.G. Mason)</p>
	S. 84°34' W., beginning new measurement.
13.00	Cottonwood Canyon, drains N. 5° E., over rolling land.
17.70	Intersect Interstate 15 highway right-of-way line, from which right-of-way marker Station No. 758+00 bears N. 27°55' E., 96.48 chs. dist., and right-of-way marker Station No. 659+38 bears S. 27°55' W., 52.718 chs. dist.
21.30	Center line of N bound lane, bears N. 26°55' E. and S. 26°55' W.
33.10	Center line of S bound lane, bears N. 31°22' E. and S. 31°22' W.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 41 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS		
36.65	Intersect Interstate 15 highway right-of-way line, from which right-of-way marker Station No. 701+68.11 bears N. 31°25' E., 22.975 chs. dist., and right-of-way marker Station No. 679+00 bears S. 31°25' W., 10.448 chs. dist.	
41.18	The cor. of secs. 22, 23, 26, and 27, monumented with an iron post, 2 ins. diam., projecting 14 ins. above ground and in a mound of stone, with brass cap mkd. as described in the official record of the 1918 resurvey.	
	N. 0°43' W., bet. secs. 22 and 23. Over rolling land, through scattering undergrowth; asc. gentle SE slope.	
19.94	Point for the S 1/16 sec. cor. of secs. 22 and 23. Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd.	
	T 41 S R 14 W S 1/16 S 22 S 23 1978	
	Cor. is located on gentle SE slope of clay bench.	
39.88	The ¼ sec. cor. of secs. 22 and 23, monumented with an iron post, 1 in. diam., projecting 10 ins. above ground and in a collar of stone, with brass cap mkd. as described in the official record of the 1918 resurvey.	
	N. 0°42' W., beginning new measurement.	
39.88	The cor. of secs. 14, 15, 22, and 23, monumented with an iron post, 2 ins. diam., projecting 1 ft. above ground and in a scattered collar of stone, with brass cap mkd. as described in the official record of the 1918 resurvey.	
	From the cor. of secs. 13, 14, 23, and 24. N. 89°48' W., bet. secs. 14 and 23. Over gentle rolling mountainous land, through scattering undergrowth; desc. NW slope.	
1.00	Creek, 10 lks. wide, 2 ins. deep, flows SW; asc. SE slope.	
15.15	Intersect Interstate 15 highway right-of-way line, from which right-of-way marker Station No. 758+00 bears N. 27°55' E., 8.446 chs. dist. and right-of-way marker Station No. 659+38 bears S. 27°55' W., 140.752 chs. dist.	
18.65	Center line of N bound lane, bears N. 31°21'30" E. and S. 31°21'30" W.	
22.95	Center line of S bound lane, bears N. 31°21'30" E. and S. 31°21'30" W.	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 41 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS	
26.50	<p>Intersect Interstate 15 highway right-of-way line, from which right-of-way marker Station No. 753+20.8 bears N. 30°32' E., 7.618 chs. dist. and right-of-way marker Station No. 702+15.32 bears S. 30°32' W., 69.607 chs. dist.</p> <p>NOTE: From right-of-way marker station No. 701+68.11, right-of-way marker station No. 702+15.32 bears N. 88°08' E., 1.38 chs. dist.</p>
41.34	Fence, 4 strand, bears N and S.
41.36	<p>The ¼ sec. cor. of secs. 14 and 23, monumented with a sandstone, 18 x 12 x 3 ins., firmly set 8 ins. in the ground and plainly mkd. ¼ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 41 S R 14 W</p> <p style="text-align: center;">¼ $\frac{S\ 14}{S\ 23}$</p> <p style="text-align: center;">1978</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p style="text-align: center;">_____</p> <p>S. 89°34' W., beginning new measurement.</p>
32.00	Quail Creek, 10 lks. wide, 3 ins. deep, flows S; asc. gentle E slope.
39.33	The cor. of secs. 14, 15, 22, and 23.
20.23	<p style="text-align: center;">(Restoring the 1877 Survey by T.C. Bailey and the 1918-19 Resurvey by H.G. Mason)</p> <p style="text-align: center;">_____</p> <p>N. 0°48' E., bet. secs. 14 and 15.</p> <p>Over rolling mountainous land, through scattering undergrowth.</p> <p>Point for the S 1/16 sec. cor. of secs. 14 and 15.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 41 S R 14 W S 1/16</p> <p style="text-align: center;">S 15 S 14</p> <p style="text-align: center;">1978</p> <p>Set a steel fence post alongside the iron post.</p>
40.46	The ¼ sec. cor. of secs. 14 and 15, monumented with an iron post, 1 in. diam., projecting 20 ins. above ground and in a mound of stone, 4 ft. base, to top of brass cap mkd. as described in the official record of the 1918 resurvey.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 41 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS		
	<p>Cor. is located on gentle SE slope.</p> <hr/> <p>N. 0°46' E., beginning new measurement.</p>	
8.50	Quail Creek, 10 lks. wide, 3 ins. deep, flows S-SE.	
39.77	The original witness cor. to the cor. of secs. 10, 11, 14, and 15, monumented with an iron post, 2 ins. diam., 36 ins. long, set on solid rock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd. as described in the official record of the 1918 resurvey.	
39.97	True point for the cor. of secs. 10, 11, 14, and 15, at record bearing and distance from its witness cor., falls on steep SE slope of sandstone ledges.	
	<p>From the cor. of secs. 11, 12, 13, and 14.</p> <p>S. 89°47' W., bet. secs. 11 and 14.</p> <p>Over rolling mountainous land, through sagebrush, shad-scale, and scattered juniper growth.</p>	
1.50	Small creek, 5 lks. wide, 1 in. deep, flows SW; asc. SE slope.	
11.50	White Reef, bears NE and SW; desc. NW slope.	
18.00	Leeds Creek, 15 lks. wide, 6 ins. deep, flows SW; asc. SE slope.	
39.38	<p>The ¼ sec. cor. of secs. 11 and 14, monumented with an iron post, 1 in. diam., projecting 18 ins. above ground and in a mound of stone, 3½ ft. base, to top of brass cap mkd. as described in the official record of the 1918 resurvey.</p> <p>Cor. is located on gentle NW slope.</p> <hr/> <p>S. 89°29' W., beginning new measurement.</p>	
40.73	True point for the cor. of secs. 10, 11, 14, and 15.	
	<p style="text-align: center;">General Description</p> <p>The area resurveyed in T. 41 S., R. 14 W., secs. 14, 23, and 24, is mostly mountainous. The elevation is about 3200 ft. above sea level. The soil varies from sandy clay loam to very rocky at the higher elevations. The vegetation consists of sagebrush, shadscale, greasewood, native grasses, creosote brush and a few scattered juniper. The general drainage is to the SE, into the Virgin River. Access is by Interstate 15, which enters the east boundary of sec. 14 and leaves on the south boundary of sec. 23. The principal use is livestock grazing.</p>	

CERTIFICATE OF SURVEY

(We), Craig P. Sylvester, Gail E. Reynolds and Ferrel D. Reynolds, Cadastral Surveyors, CERTIFY upon honor that, in pursuance of special instructions bearing date of the 29th day of March, 1978, (We) have dependently resurveyed the south 4 miles of the east boundary (Second Guide Meridian West), and a portion of the subdivisional lines of Township 41 South, Range 14 West,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (us) and under (our) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

September 23, 1980 (Date)
September 23, 1980
September 23, 1980 (Date)

Craig P. Sylvester (Cadastral Surveyor)
Gail E. Reynolds (Supervisory)
Ferrel D. Reynolds (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Denver, Colorado

The foregoing field notes of the dependent resurvey of the south 4 miles of the east boundary (Second Guide Meridian West), and a portion of the subdivisional lines of T. 41 S., R. 14 W., of the Salt Lake Meridian, Utah

executed by Craig P. Sylvester, Supervisory Cadastral Surveyor
Ferrel D. Reynolds, Cadastral Surveyor
Gail E. Reynolds, Supervisory Cadastral Surveyor
having been critically examined and found correct, are hereby approved.

MAR 17 1982 (Date)

ACTING (Chief, Cadastral Survey Examination and Approval Staff)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

(Date) (Chief, Cadastral Survey Examination and Approval Staff)

R602

ORIGINAL
FIELD NOTES

OF THE
DEPENDENT RESURVEY
OF THE
NORTH, AND SOUTH BOUNDARIES,
THE SECOND GUIDE MERIDIAN WEST ALONG THE EAST BOUNDARY,
A PORTION OF THE WEST BOUNDARY,
AND THE SUBDIVISIONAL LINES
OF
TOWNSHIP 42 SOUTH, RANGE 14 WEST

Of the Salt Lake Meridian,
In the State of Utah

EXECUTED BY

Craig P. Sylvester, Supervisory Cadastral Surveyor
Gail E. Reynolds, Supervisory Cadastral Surveyor
Ferrel D. Reynolds, Cadastral Surveyor

Under special instructions dated March 29, 1978, approved April 3, 1978,

_____, which provided for the surveys included under ~~U.S. Survey~~/Group
Number 578, and assignment instructions dated April 4, 1978.

Survey commenced April 11, 1978

Survey completed June 16, 1978

INDEX DIAGRAM

Township 42 South, Range 14 West

20	19	18	17	15	14
13 6 74	5 57	4 46	3 38	2 28	1 11
73	72	55	46	37	28
12 7 71	8 55	9 45	10 35	11 27	12 10
70	69	54	44	34	26
71 18 68	17 53	16 42	15 33	14 25	13 9
66	65	52	42	33	24
68 19 64	20 51	21 41	22	32 28 24	24 8
62	62	50	40	31	23
64 30 61	29 49	28 40	27 31	26 22	25 8
59	58	49	39	30	22
61 31 58	32 48	33 38	34 29	35 21	36 7
5	5	4	3	3	2

Township 42 South, Range 14 West, Salt Lake Meridian, Utah

CHAINS

The south boundary was surveyed by M.H. Dalley in 1899, and retraced by Stewart and Snow in 1909. The east boundary (Second Guide Meridian West) was surveyed by Julien Bausman in 1870, retraced by Jenkins and West in 1897, and the north 1 mile retraced by M.H. Dalley in 1899. The west boundary was surveyed by Joseph Gorlinski in 1870, retraced by M.H. Dalley in 1899, and the south 4 miles resurveyed by Craig P. Sylvester in 1973. The north boundary was surveyed by Julien Bausman in 1870, retraced by M.H. Dalley in 1899, and with the exception of the south boundary of sec. 34, retraced by H.G. Mason in 1918 and 1919. The northwest portion of the subdivisional lines were surveyed by Joseph Gorlinski in 1870, and retraced and the remainder of the subdivisional lines surveyed by M.H. Dalley in 1899.

The following field notes are those of a dependent resurvey of the south and north boundaries, the Second Guide Meridian West along the east boundary, a portion of the west boundary, and the subdivisional lines of Township 42 South, Range 14 West, Salt Lake Meridian, Utah

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions 1973, and the Special Instructions for Group 578, Utah, dated March 29, 1978.

The directions of the lines of this survey were determined by reference to true meridians established on line by hour angle observations on Polaris. They were carried forward by sustained angulation, being supplemented by numerous other observations on Polaris taken throughout the progress of the survey.

Measurements were determined by electronic means.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position for the southeast corner of the township, as determined by ties to U.S.G.S. triangulation station "Wash" located in sec. 31, T. 41 S., R. 14 W., is as follows:

Latitude 37° 05' 00" N. Longitude 113° 21' 59" W.

The mean magnetic declination is 14° 30' E., as computed from U.S.G.S. Map 1-911.

Dependent Resurvey of the South Boundary of
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

(Restoring the 1899 Survey Executed by M.H. Dalley
and the 1909 Retracement Executed by A.J. Stewart
and L.A. Snow)

Dependent Resurvey of the South Boundary of
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS

Beginning at the cor. of Tps. 42 and 43 S., Rs. 13 and 14 W., monumented with a sandstone, 16 x 10 x 5 ins., firmly set in a mound of stone and plainly mkd. 6 notches on 4 edges.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.

T 42 S
R 14 W R 13 W

S 36		S 31
S 1		S 6

T 43 S
1978

Deposit the mkd. stone in mound alongside the iron post.

S. 89° 49' W., bet. secs. 1 and 36.

Over sandy land with sandstone outcrops; asc. NE slope.

40.08

Point for the ¼ sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 42 S R 14 W

¼	S 36		S 36
	S 1		S 1

T 43 S R 14 W
1978

Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.

80.14

The cor. of secs. 1, 2, 35, and 36, monumented with a sandstone, 20 x 14 x 6 ins., firmly set 10 ins. in the ground and plainly mkd. 1 notch on E and 5 notches on W edges.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.

T 42 S R 14 W

S 35		S 36
S 2		S 1

T 43 S
1978

Place the mkd. stone in mound alongside the iron post.

Dependent Resurvey of the South Boundary of
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS

S. 89° 52' W., bet. secs. 2 and 35.

Over sandy hills, draining NE.

40.06

The $\frac{1}{4}$ sec. cor. of secs. 2 and 35, monumented with a lava stone, 18 x 10 x 4 ins., firmly set in a mound of stone and plainly mkd. $\frac{1}{4}$ on N face.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.

T 42 S R 14 W

$$\frac{1}{4} \frac{S 35}{S 2}$$

T 43 S
1978

Place the mkd. stone in mound alongside the iron post.

S. 89° 51' W., beginning new measurement.

Over sandy land, draining N.

40.09

Point for the cor. of secs. 2, 3, 34, and 35, at proportionate distance based on the irregular boundary method; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 42 S R 14 W

$$\frac{S 34 \mid S 35}{S 3 \mid S 2}$$

T 43 S R 14 W
1978

S. 89° 50' W., bet. secs. 3 and 34.

Over sandy land, draining N.

40.22

Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 34, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 42 S R 14 W

$$\frac{1}{4} \frac{S 34}{S 3}$$

T 43 S R 14 W
1978

Dependent Resurvey of the South Boundary of
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS

Set a cedar post alongside the iron post.

41.10 Wash in sandy swale, drains N.

80.26 The cor. of secs. 3, 4, 33, and 34, monumented with a sandstone, 30 x 20 x 6 ins., firmly set 10 ins. in the ground and plainly mkd. 3 notches on E and W edges.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 42 S R 14 W

S 33	S 34
S 4	S 3

T 43 S R 14 W
1978

Bury the mkd. stone alongside the iron post.

S. 89° 52' W., bet. secs. 4 and 33.

Over sandy rolling land; asc. gentle NE slope.

40.12 Point for the ¼ sec. cor. of secs. 4 and 33, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 42 S R 14 W

¼ S 33
S 4

T 43 S R 14 W
1978

Cor. is located 14 lks. N of E and W fence; no other accessories.

80.24 The cor. of secs. 4, 5, 32, and 33, monumented with a sandstone, 24 x 14 x 6 ins., firmly set 10 ins. in the ground and plainly mkd. 4 notches on E and 2 notches on W edges.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 42 S R 14 W

S 32	S 33
S 5	S 4

T 43 S R 14 W
1978

Dependent Resurvey of the South Boundary of
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS	
	<p>Bury the mkd. stone alongside the iron post, no other accessories available.</p> <hr/> <p>S. 89° 57' W., bet. secs. 5 and 32.</p> <p>Over sandy land on top of spur.</p> <p>39.69 The $\frac{1}{4}$ sec. cor. of secs. 5 and 32, monumented with a sandstone, 24 x 14 x 8 ins., firmly set 10 ins. in the ground, and plainly mkd. $\frac{1}{4}$ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 42 S R 14 W</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S\ 32}{S\ 5}$</p> <p style="text-align: center;">T 43 S R 14 W 1978</p> <p>from which</p> <p style="padding-left: 40px;">The SW face of a boulder, 10 x 10 x 10 ft., above ground, bears N. 72° 22' E., 54 lks. dist., mkd. BO X.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 89° 44' W., beginning new measurement.</p> <p>Desc. over NW slope, on broken bench.</p>
40.06	<p>The cor. of secs. 5, 6, 31, and 32, monumented with a sandstone, 20 x 12 x 6 ins., firmly set 10 ins. in the ground and plainly mkd. 1 notch on W and 5 notches on E edges.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 42 S R 14 W</p> <p style="text-align: center;">$\frac{S\ 31}{S\ 6} \mid \frac{S\ 32}{S\ 5}$</p> <p style="text-align: center;">T 43 S R 14 W 1978</p> <p>Deposit the mkd. stone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <hr/> <p>S. 89° 50' W., bet. secs. 6 and 31.</p> <p>Over broken bench; desc. over NW slope.</p>

Dependent Resurvey of the South Boundary of
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS

39.97

The $\frac{1}{4}$ sec. cor. of secs. 6 and 31, monumented with a sandstone, 20 x 12 x 6 ins., firmly set in a mound of stone and plainly mkd. $\frac{1}{4}$ on N face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., on solid sandstone, over a cross (X) and in a mound of stone, 5 ft. base, to top of brass cap, mkd.

T 42 S R 14 W

$\frac{1}{4}$ $\frac{S\ 31}{S\ 6}$

T 43 S R 14 W
1978

Place the mkd. stone in mound alongside the iron post.

S. 89° 50' W., beginning new measurement.

Asc. over steep E slope.

39.76

Point for the 80 $\frac{1}{16}$ sec. cor. of sec. 31 only.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 42 S R 14 W

$\frac{1}{16}$ S 31 80

T 43 S
1978

44.74

The closing cor. of Tps. 14 and 15 S., R. 14 W., on the E. bdy. of T. 42 S., R. 15 W., monumented with a sandstone, 18 x 8 x 8 ins., firmly set and plainly mkd. 6 grooves on S face, 6 grooves and 14W on E face, and 6 grooves and 42S on N face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 42 S
R 15 W R 14 W

S 36 $\frac{S\ 31}{S\ 6}$ C

T 43 S
1978

Bury the mkd. stone alongside the iron post and raise a mound of stone, 2 ft. base, 2 ft. high, E of cor.

Dependent Resurvey of the South Boundary of
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS

From this cor., the cor. of Tps. 42 and 43 S., R. 15 W., bears S. $0^{\circ} 36'$ E., 6.69 chs. dist., monumented with an iron post, $2\frac{1}{2}$ ins. diam., extending 8 ins. above ground, mkd. as described in the official record of the 1973 resurvey of a portion of the E. bdy. of T. 42 S., R. 15 W.

From this same closing cor., the $\frac{1}{4}$ sec. cor. of sec. 36, T. 42 S., R. 15 W., bears N. $0^{\circ} 36'$ W., 33.57 chs. dist., monumented with an iron post, $2\frac{1}{2}$ ins. diam., extending 8 ins. above ground, mkd. as described in the official record of the 1973 resurvey of a portion of the E. bdy. of T. 42 S., R. 15 W.

Dependent Resurvey of the Second Guide Meridian West
along the East Boundary of T. 42 S., R. 14 W.,
Salt Lake Meridian, Utah

(Restoring the 1870 Survey Executed by
J. Bausman and the 1897 Retracement Executed by
J.A. West and Washington Jenkins)

From the cor. of Tps. 42 and 43 S., Rs. 13 and 14 W.,
heretofore described.

N. $0^{\circ} 09'$ W., bet. secs. 31 and 36.

Over sandy land with patches of exposed sandstone; desc.
over NW slope.

39.91 Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 36.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, and in a collar of stone, with brass cap
mkd.

T 42 S
R 14 W R 13 W

$\frac{1}{4}$
|
S 36 | S 31

1978

Desc. over gentle N slope, over sand hills.

79.82 The cor. of secs. 25, 30, 31, and 36, monumented with a
sandstone, 16 x 12 x 6 ins., firmly set 10 ins. in the
ground and plainly mkd. 1 notch on S and 5 notches on
N edges.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

Dependent Resurvey of the Second Guide Meridian West
along the East Boundary of T. 42 S., R. 14 W.,
Salt Lake Meridian, Utah

CHAINS		
	<p style="text-align: center;">T 42 S R 14 W R 13 W</p> <p style="text-align: center;">S 25 S 30 S 36 S 31</p> <p style="text-align: center;">1978</p> <p>Bury the mkd. stone and set a cedar post alongside the iron post.</p>	
39.98	<p>N. 0° 02' W., bet. secs. 25 and 30.</p> <p>Over rolling sandy land, covered with shadscale and scattered bunch grass.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 30.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 42 S R 14 W R 13 W</p> <p style="text-align: center;">$\frac{1}{4}$ S 25 S 30 </p> <p style="text-align: center;">1978</p>	
79.96	<p>The cor. of secs. 19, 24, 25, and 30, monumented with a black lava stone, 20 x 8 x 6 ins., firmly set 12 ins. in the ground and plainly mkd. 2 notches on S and 4 notches on N edges.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 42 S R 14 W R 13 W</p> <p style="text-align: center;">S 24 S 19 S 25 S 30</p> <p style="text-align: center;">1978</p> <p>Bury the mkd. stone and set a cedar post alongside the iron post.</p>	
39.93	<p>N. 0° 03' W., bet. secs. 19 and 24.</p> <p>Over rolling sandy land, covered with shadscale and scattered bunch grass.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 24.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p>	

Dependent Resurvey of the Second Guide Meridian West
along the East Boundary of T. 42 S., R. 14 W.,
Salt Lake Meridian, Utah

CHAINS

T 42 S
R 14 W R 13 W

$\frac{1}{4}$
S 24 | S 19

1978

Desc. over rocky NW slope.

79.86 The cor. of secs. 13, 18, 19, and 24, monumented with a lava stone, 16 x 10 x 8 ins., firmly set 8 ins. in the ground and plainly mkd. 3 notches on N and S edges. Also Washington County brass cap mkd. for this cor. set alongside.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 42 S
R 14 W R 13 W

S 13 | S 18
S 24 | S 19

1978

Bury the mkd. stone and the Washington County marker inverted alongside the iron post.

N. 0° 05' E., bet. secs. 13 and 18.

Desc. NW slope of terrace.

40.06 The ¼ sec. cor. of secs. 13 and 18, monumented with a Washington County marker, properly mkd. for this cor., and is accepted as a careful and faithful determination of the position of the cor.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 42 S
R 14 W R 13 W

$\frac{1}{4}$
S 13 | S 18

1978

Set the Washington County marker inverted and a steel fence post alongside the iron post.

Dependent Resurvey of the Second Guide Meridian West
 along the East Boundary of T. 42 S., R. 14 W.,
 Salt Lake Meridian, Utah

CHAINS						
<p>40.08</p>	<p>N. 0° 06' E., beginning new measurement.</p> <p>Along E side of trail road.</p> <p>The cor. of secs. 7, 12, 13, and 18, monumented with a Washington County survey marker, properly mkd. for this cor., and is accepted as a careful and faithful perpetuation of the position of the original cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 42 S R 14 W R 13 W</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 12</td> <td style="padding: 0 5px;">S 7</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 13</td> <td style="padding: 0 5px;">S 18</td> </tr> </table> <p>1978</p> </div> <p>Set Washington County marker inverted alongside the iron post.</p>	S 12	S 7	S 13	S 18	
S 12	S 7					
S 13	S 18					
<p>0.08</p> <p>40.06</p> <p>60.09</p>	<p>N. 0° 02' E., bet. secs. 7 and 12.</p> <p>Over rolling land, along E side of graded field road.</p> <p>An iron post, 1 in. diam., extending 12 ins. above ground, with General Land Office brass cap, no marks.</p> <p>Point for the ¼ sec. cor. of secs. 7 and 12.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 42 S R 14 W R 13 W</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 12</td> <td style="padding: 0 5px;">S 7</td> </tr> </table> <p>1978</p> </div> <p>Set a small wood post alongside the iron post.</p> <p>Point for the N 1/16 sec. cor. of secs. 7 and 12, falls in road.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 36 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 42 S R 14 W R 13 W N 1/16</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 12</td> <td style="padding: 0 5px;">S 7</td> </tr> </table> <p>1978</p> </div>	S 12	S 7	S 12	S 7	
S 12	S 7					
S 12	S 7					

Dependent Resurvey of the Second Guide Meridian West
 along the East Boundary of T. 42 S., R. 14 W.,
 Salt Lake Meridian, Utah

CHAINS					
80.12	<p>From which</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 45° E., 75 lks. dist., with brass cap mkd. N1/16 S7 T42S R13W 49.5 FT RM 1978 and an arrow pointing to the cor.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 45° W., 75 lks. dist., with brass cap mkd. N1/16 S12 T42S R14W 49.5 FT RM 1978 and an arrow pointing to the cor.</p> <p>The cor. of secs. 1, 6, 7, and 12, monumented with a lava stone, 16 x 10 x 6 ins., firmly set in a mound of stone and plainly mkd. 1 notch on N and 5 notches on S edges.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 42 S R 14 W R 13 W</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 1</td> <td style="padding: 0 5px;">S 6</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 12</td> <td style="padding: 0 5px;">S 7</td> </tr> </table> <p style="text-align: center;">1978</p> <p>Place the mkd. stone in mound alongside the iron post.</p> <p>Cor. is located on small knoll.</p>	S 1	S 6	S 12	S 7
S 1	S 6				
S 12	S 7				
29.40 34.05	<p style="text-align: center;">(Restoring the 1870 Survey Executed by J. Bausman, the 1897 Retracement by J.A. West and W. Jenkins, and the 1899 Retracement by M.H. Dalley)</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 15' E., bet. secs. 1 and 6.</p> <p>Over rolling land.</p> <p>Graded gravel road, bears N. 52° W. and S. 52° E.</p> <p>The original ¼ sec. cor. of secs. 1 and 6, monumented with a lava stone, 16 x 12 x 6 ins., in a small mound of stone, plainly mkd. ¼ on W face. This cor. now functions as an angle point and the letters AP were added to the stone.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 13' E., beginning new measurement.</p> <p>Begin ascent of S slope of sand and lava spur.</p>				
1.21	<p>Point for the ¼ sec. cor. of sec. 1 only.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>				

Dependent Resurvey of the Second Guide Meridian West
 along the East Boundary of T. 42 S., R. 14 W.,
 Salt Lake Meridian, Utah

CHAINS

T 42 S
 R 14 W R 13 W

¼ |
 S 1 |

1978

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

NOTE: There is no remaining evidence of the ¼ sec. cor. established by M.H. Dalley in 1899.

- 4.20 Sand and lava spur, slopes W; thence over spur.
- 39.05 Highway right-of-way, bears N. 73° 30' E. and S. 73° 30' W.
- 40.20 Highway, No. 9, bears N. 73° 30' E. and S. 73° 30' W.
- 41.43 The cor. of Tps. 41 and 42 S., R. 14 W., monumented with an iron post, 3 ins. diam., extending 10 ins. above ground, mkd. as described in the official record of the 1918 resurvey of the S. bdy. of T. 41 S., R. 14 W. This cor. is located at fence cor., fences bear W and N.

Dependent Resurvey of a Portion of the West Boundary,
 T. 42 S., R. 14 W., Salt Lake Meridian, Utah

(Restoring the 1870 Survey Executed by J. Gorlinski
 and the 1899 Retracement Executed by M.H. Dalley)

From the cor. of secs. 12 and 13, on the E. bdy. of T. 42 S., R. 15 W., monumented with an iron post, 2½ ins. diam., extending 8 ins. above ground, with brass cap mkd. as described in the official record of the 1973 resurvey of a portion of the E. bdy. of T. 42 S., R. 15 W.

N. 0° 11' W., along the E. bdy. of T. 42 S., R. 15 W.

Over rolling sand dunes, covered with scattered creosote bushes and shadscale.

- 5.09 The closing cor. of secs. 7 and 18, T. 42 S., R. 14 W., monumented with a lava stone, 18 x 8 x 8 ins., firmly set 10 ins. in the ground and plainly mkd. 4 notches on S and 2 notches on N edges and CC on E face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 42 S
 R 15 W R 14 W

S 12 | S 7 C
 | S 18 C

1978

Dependent Resurvey of a Portion of the West Boundary,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS								
40.40	<p>Bury the mkd. stone alongside the iron post.</p> <p>Thence bet. secs. 7 and 12.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 7 and 12, monumented with a lava stone, 18 x 10 x 10 ins., firmly set 8 ins. in the ground and plainly mkd. $\frac{1}{4}$ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 42 S R 15 W R 14 W</p> <table style="margin: auto;"> <tr> <td style="text-align: center;">$\frac{1}{4}$</td> <td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td> <td style="text-align: center;">$\frac{1}{4}$</td> </tr> <tr> <td style="text-align: center;">S 12</td> <td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td> <td style="text-align: center;">S 7</td> </tr> </table> <p>1978</p> </div> <p>Bury the mkd. stone alongside the iron post.</p>	$\frac{1}{4}$		$\frac{1}{4}$	S 12		S 7	
$\frac{1}{4}$		$\frac{1}{4}$						
S 12		S 7						
40.44	<p>N. $0^{\circ} 11' W.$, beginning new measurement.</p> <p>Over rolling sandy land, draining SE.</p> <p>The cor. of secs. 1, 6, 7, and 12, monumented with a limestone, 24 x 14 x 4 ins., firmly set 10 ins. in the ground and plainly mkd. 5 notches on S and 1 notch on N edges.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 42 S R 15 W R 14 W</p> <table style="margin: auto;"> <tr> <td style="text-align: center;">S 1</td> <td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td> <td style="text-align: center;">S 6</td> </tr> <tr> <td style="text-align: center;">S 12</td> <td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> </td> <td style="text-align: center;">S 7</td> </tr> </table> <p>1978</p> </div> <p>Bury the mkd. stone alongside the iron post.</p>	S 1		S 6	S 12		S 7	
S 1		S 6						
S 12		S 7						
6.52	<p>N. $0^{\circ} 03' W.$, bet. secs. 1 and 6.</p> <p>Over broken land, covered with sand and exposed sandstone; asc. over SE slope.</p> <p>Fence on the right-of-way line of Interstate 15, bears N. $37^{\circ} 46' E.$ and S. $37^{\circ} 46' W.$</p>							
8.97	<p>Center line of north-bound-lane of Interstate 15, bears N. $37^{\circ} 49' E.$ and S. $37^{\circ} 49' W.$</p>							

Dependent Resurvey of a Portion of the West Boundary,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah


CHAINS

- 10.47 Center line of south-bound-lane of Interstate 15, bears N. 39° 47' E. and S. 39° 47' W.
- 13.32 Fence on right-of-way of Interstate 15, bears N. 36° 47' E. and S. 36° 47' W.; thence over broken bench.
- 40.06 The ¼ sec. cor. of secs. 1 and 6, monumented with a lava stone, 14 x 8 x 6 ins., firmly set 8 ins. in the ground and plainly mkd. ¼ on W face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 42 S
R 15 W R 14 W



1978

Bury the mkd. stone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

N. 9° 23' W., beginning new measurement.

Continue over broken bench.

- 40.88 The cor. of Tps. 41 and 42 S., Rs. 14 and 15 W., monumented with an iron post, 3 ins. diam., extending 15 ins. above a mound of stone, with brass cap mkd. as described in the official record of the 1909 survey of the E. bdy. of T. 41 S., R. 15 W.

Dependent Resurvey of the North Boundary,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

(Restoring the 1870 Survey by J. Bausman,
the 1899 Resurvey by M.H. Dalley, and the
1918 - 19 Resurvey by H.G. Mason)

From the cor. of Tps. 41 and 42 S., R. 14 W., heretofore described.

N. 89° 55' W., bet. secs. 1 and 36.

Over rolling bench land.

- 40.13 The ¼ sec. cor. of secs. 1 and 36, monumented with an iron post, 1 in. diam., extending 12 ins. above ground, mkd. as described in the official record of the 1918 - 19 resurvey of the S. bdy. of T. 41 S., R. 14 W.

Dependent Resurvey of the North Boundary,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS						
	<p>N. 89° 53' W., beginning new measurement.</p>					
	<p>Continue over bench.</p>					
39.00	<p>Point selected for the witness cor. to the cor. of secs. 1, 2, 35, and 36. This cor. will also function as the witness meander cor. for the left bank of the Virgin River.</p>					
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>					
	<p>W C T 41 S R 14 W</p> <table border="1" style="margin: auto;"> <tr> <td>S 35</td> <td>S 36</td> </tr> <tr> <td>S 2</td> <td>S 1</td> </tr> </table> <p>T 42 S R 14 W 1978</p>	S 35	S 36	S 2	S 1	
S 35	S 36					
S 2	S 1					
	<p>Cor. is located in fence line, which bears N and S along bank above river.</p>					
	<p>Desc. over broken bank, through dense willows.</p>					
39.15	<p>Point for the original witness cor. to the cor. of secs. 1, 2, 35, and 36, at proportionate distance; there is no remaining evidence of the original corner.</p>					
39.57	<p>Point for the original witness cor. to the meander cor. of secs. 1 and 36, on the left bank of the Virgin River at proportionate distance; there is no remaining evidence of the original corner.</p>					
39.82	<p>Present mean high water mark, on the left bank of the Virgin River, bears S. 10° 15' E. and N. True point for the original meander cor. of secs. 1 and 36, at proportionate distance, falls on broken bank and cannot be monumented; thence across river.</p>					
40.12	<p>True point for the cor. of secs. 1, 2, 35, and 36, at proportionate distance based on the irregular boundary method, falls in Virgin River.</p>					
	<p>N. 89° 54' W., along the S. bdy. of sec. 35, T. 41 S., R. 14 W.</p>					
	<p>Over Virgin River.</p>					
4.62	<p>Present mean high water mark, on the right bank of the Virgin River, bears S. 14° 15' E. and N. 7° W. Point for the original meander cor. of secs. 2 and 35, at proportionate distance; there is no remaining evidence of the original corner.</p>					
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>					

Dependent Resurvey of the North Boundary,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS

T 41 S R 14 W

S 35		M
S 2		C

T 42 S R 14 W
1978

Asc. gentle E slope over small farms.

40.00

The 1/4 sec. cor. of sec. 35 only, monumented with a sandstone, 24 x 8 x 8 ins., firmly set 10 ins. in the ground and plainly mkd. 1/4 on N face.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd.

T 41 S R 14 W

1/4	S 35
-----	------

T 42 S R 14 W
1978

Place the mkd. stone in mound alongside the iron post.

N. 88° 03' W., beginning new measurement.

Desc. over W slope.

0.02

The 1/4 sec. cor. of sec. 2 only, monumented with a Washington County survey marker with brass cap mkd.

N 1/4	S 2
-------	-----

T 42 S R 14 W
1974

This position is accepted as a careful and faithful determination of the position of the corner.

3.44

The angle point bet. secs. 2 and 35, monumented with a sandstone, 18 x 8 x 8 firmly set 8 ins. in the ground and mkd. AP on S face.

At the angle point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.

A P
T 41 S R 14 W

S 35	S 2
------	-----

T 42 S R 14 W
1978

Place the mkd. stone in mound alongside the iron post.

Dependent Resurvey of the North Boundary,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS

S. 89° 58' W., beginning new measurement.

36.60 The closing cor. of secs. 2 and 3, monumented with a sandstone, 20 x 8 x 6 ins., firmly set 10 ins. in the ground and plainly mkd. 4 notches on the W and 2 notches on the E edges and CC on S face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 41 S R 14 W

S 35	
S 3	S 2

C C

T 42 S R 14 W

1978

41.16 The cor. of secs. 34 and 35, T. 41 S., R. 14 W., monumented with an iron post, 2 ins. diam., extending 8 ins. above ground, mkd. as described in the official record of the 1918 resurvey of a portion of the S. bdy. of T. 41 S., R. 14 W.

(Restoring the 1870 Survey by J. Bausman, and
the 1899 Resurvey by M.H. Dalley)

N. 89° 31' W., bet. secs. 3 and 34.

Over broken gypsum hills, draining SE.

35.99 A black sandstone, 20 x 8 x 8 ins., firmly set in a mound of stone and plainly mkd. ¼ on W face bears South 0.11 chs. dist. This stone appears to be of local origin and is 5.56 chs. to the east and is not accepted as the ¼ sec. cor.

41.55 Point for the ¼ sec. cor. of secs. 3 and 34, at proportionate distance, based on the irregular boundary method; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 41 S R 14 W

¼	S 34
	S 3

T 42 S R 14 W

1978

Cor. is located on W side of wash, in small ravine, which drains S.

Dependent Resurvey of the North Boundary,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS	
	WEST, beginning new measurement.
20.665	Point for the W 1/16 sec. cor. of secs. 3 and 34.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 41 S R 14 W
	W 1/16 $\frac{S\ 34}{S\ 3}$
	T 42 S R 14 W
	1978
	Over rolling sandy land.
40.90	Old highway, bears N. 40° 30' E. and S. 40° 30' W.
41.33	The cor. of secs. 3, 4, 33, and 34, monumented with a Washington County survey marker, set in concrete, with brass cap mkd.
	T 41 S
	$\frac{S\ 33}{S\ 4} \mid \frac{S\ 34}{S\ 3}$
	R 14 W
	T 42 S
	1974
	This cor. is accepted as a careful and faithful perpetuation of the position of the original corner.
	(Restoring the 1870 Survey by J. Bausman, the 1899 Resurvey by M.H. Dalley and the 1918 - 19 Resurvey by H.G. Mason)
	S. 89° 39' W., bet. secs. 4 and 33.
	Over rolling sandy desert land.
20.605	Point for the E 1/16 sec. cor. of secs. 4 and 33.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T 41 S R 14 W
	E 1/16 $\frac{S\ 33}{S\ 4}$
	T 42 S R 14 W
	1978
	Asc. SE slope, over broken desert land.
41.21	The ¼ sec. cor. of secs. 4 and 33, monumented with a Washington County survey marker, set in concrete, with brass cap mkd.

Dependent Resurvey of the North Boundary,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS	
	<p style="text-align: center;">T 41 S $\frac{1}{4}$ $\frac{S\ 33}{S\ 4}$ T 42 S R 14 W 1974</p> <p>A sandstone, 16 x 10 x 9 ins., mkd. $\frac{1}{4}$ is buried alongside the Washington County survey marker,</p> <p>Steel fence post set alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>West, beginning new measurement.</p> <p>Over broken desert land, draining SE.</p>
38.62	The cor. of secs. 32 and 33, T. 41 S., R. 14 W., monumented with an iron post, 2 ins. diam., extending 9 ins. above ground, with brass cap mkd. as described in the official record of the 1918 resurvey of a portion of the S. bdy. of T. 41 S., R. 14 W.
41.15	The cor. of secs. 4 and 5, T. 42 S., R. 14 W., monumented with a Washington County survey marker, set in concrete with a collar of stone around marker, brass cap mkd.
	<p style="text-align: center;">T 41 S S 32 S 5 S 4 T 42 S R 14 W 1974</p> <p>This cor. is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>Steel fence post set alongside the corner.</p> <hr/> <p>N. 89° 54' W., along the N. bdy. of sec. 5.</p> <p>Over broken desert land, over sand and exposed sandstone outcrop.</p>
5.19	Fence on the right-of-way line of Interstate 15, bears N. 61° 59' E. and S. 61° 59' W.
11.59	North-bound-lane of Interstate 15, bears N. 61° 58' E. and S. 61° 58' W.
19.39	South-bound-lane of Interstate 15, bears N. 63° 36' E. and S. 63° 36' W.
26.19	Fence on the right-of-way line of Interstate 15, bears N. 60° 18' E. and S. 60° 18' W.
37.44	The $\frac{1}{4}$ sec. cor. of sec. 32, T. 41 S., R. 14 W., monumented with an iron post, 1 in. diam., extending 8 ins. above a mound of stone, with brass cap mkd. as described in the official record of the 1918 resurvey of a portion of the S. bdy. of T. 41 S., R. 14 W.

Dependent Resurvey of the North Boundary,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS		
41.08	<p>The $\frac{1}{4}$ sec. cor. of sec. 5, only, monumented with a sandstone, 24 x 12 x 4 ins., set in a mound of stone and plainly mkd. $\frac{1}{4}$ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., on solid sandstone, over a cross (X), in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 41 S R 14 W</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">$\frac{1}{4}$ S 5</p> <p style="text-align: center;">T 42 S R 14 W 1978</p> <p>Place the mkd. stone in mound alongside the iron post.</p> <p style="text-align: center;">_____</p> <p>S. $89^{\circ} 57'$ W., beginning new measurement.</p> <p>Over broken sandy land.</p>	
36.34	<p>The cor. of secs. 31 and 32, T. 41 S., R. 14 W., monumented with an iron post, 1 in. diam., extending 8 ins. above a mound of stone, with brass cap mkd. as described in the official record of the 1918 resurvey of a portion of the S. bdy. of T. 41 S., R. 14 W.</p>	
41.11	<p>The cor. of secs. 5 and 6,, monumented with a sandstone, 36 x 12 x 8 ins., set in a mound of stone and plainly mkd. 1 notch on W and 5 notches on E edges.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., on solid sandstone, over a cross (X), in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 41 S R 14 W</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">S 6 S 5</p> <p style="text-align: center;">T 42 S R 14 W 1978</p> <p>Place the mkd. stone in mound alongside the iron post.</p>	
	<p>S. $89^{\circ} 59'$ W., along the N. bdy. of sec. 6.</p> <p>Over broken land, across sand and sandstone outcrops; asc. over E slope.</p>	
35.16	<p>The $\frac{1}{4}$ sec. cor. of sec. 31, T. 41 S., R. 14 W., monumented with an iron post, 1 in. diam., extending 12 ins. above a mound of stone, with brass cap mkd. as described in the official record of the 1918 resurvey of a portion of the S. bdy. of T. 41 S., R. 14 W.</p>	
41.03	<p>The $\frac{1}{4}$ sec. cor. of sec. 6 only, monumented with a sandstone, 24 x 18 x 6 ins., firmly set 10 ins. in the ground and plainly mkd. $\frac{1}{4}$ on N face.</p>	

Dependent Resurvey of the North Boundary,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 41 S R 14 W

¼ S 6

T 42 S R 14 W

1978

Deposit the mkd. stone inverted alongside the iron post.

N. 89° 50' W., beginning new measurement.

Over broken desert land, draining S.

38.00 Wash in ravine, drains S. 18° E.

41.16 The cor. of Tps. 41 and 42 S., Rs. 14 and 15 W., heretofore described.

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

(Restoring the 1899 Survey by M.H. Dalley)

From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp.

N. 0° 02' W., bet. secs. 35 and 36.

Over broken sandy hills and spurs, through sagebrush, shadscale and greasewood; desc. gentle N. slope.

40.10 The ¼ sec. cor. of secs. 35 and 36, monumented with a sandstone, 18 x 12 x 5 ins., firmly set in a mound of stone and plainly mkd. ¼ on W face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., on solid rock over a cross (X), in a mound of stone, 4½ ft. base, to top of brass cap, mkd.

T 42 S R 14 W

¼
S 35 | S 36

1978

Deposit the mkd. stone alongside the iron post.

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS						
40.05	<p>N. 0° 03' W., beginning new measurement.</p> <p>The cor. of secs. 25, 26, 35, and 36, monumented with a sandstone, 20 x 8 x 6 ins., firmly set in a mound of stone and plainly mkd. 1 notch on the S and E edges.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., on broken sandstone, in a mound of stone, 5½ ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 42 S R 14 W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 26</td> <td style="padding: 0 5px;">S 25</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 35</td> <td style="padding: 0 5px;">S 36</td> </tr> </table> <p style="text-align: center;">1978</p> <p>Deposit the mkd. stone in mound alongside the iron post.</p> <p>Cor. is located on broken NW slope of hill.</p>	S 26	S 25	S 35	S 36	
S 26	S 25					
S 35	S 36					
39.98	<p>From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., heretofore described.</p> <p>N. 89° 56' W., bet. secs. 25 and 36.</p> <p>Over rolling sandy desert land; asc. gentle NE slope.</p> <p>The ¼ sec. cor. of secs. 25 and 36, monumented with a broken sandstone, 20 x 16 x 5 ins., firmly set in a mound of stone and plainly mkd. ¼ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., on solid rock, over a cross (X), in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 42 S R 14 W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">¼</td> <td style="padding: 0 5px;">S 25</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">S 36</td> </tr> </table> <p style="text-align: center;">1978</p> <p>Deposit the mkd. stone in mound alongside the iron post.</p>	¼	S 25		S 36	
¼	S 25					
	S 36					
40.02	<p>N. 89° 57' W., beginning new measurement.</p> <p>The cor. of secs. 25, 26, 35, and 36.</p>					
40.15	<p>N. 0° 03' W., bet. secs. 25 and 26.</p> <p>Over broken land, through sagebrush, shadscale and greasewood; desc. NW slope.</p> <p>Point for the ¼ sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.</p>					

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 42 S R 14 W

¼
|
S 26 | S 25

1978

Cor. is located in rolling sand dunes.

80.30 The cor. of secs. 23, 24, 25, and 26, monumented with a broken sandstone, 14 x 12 x 4 ins., firmly set 8 ins. in the ground and dimly mkd. 2 notches on the S and 1 notch on the E edges.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 42 S R 14 W

S 23 | S 24
S 26 | S 25

1978

Deposit the mkd. stone alongside the iron post.

Cor. is located in rolling sand dunes.

From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., heretofore described.

N. 89° 42' W., bet. secs. 24 and 25.

Over rolling desert land, through sagebrush, shadscale and creosote brush.

32.00 Trail road, bears N and S.

40.01 The ¼ sec. cor. of secs. 24 and 25, monumented with a sandstone, 20 x 12 x 5 ins., firmly set 10 ins. in the ground and plainly mkd. ¼ on N face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 42 S R 14 W

¼ S 24
 S 25

1978

Deposit the mkd. stone alongside the iron post.

Cor. is located in rolling sand dunes.

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS	
40.01	<p>N. 89° 42' W., beginning new measurement.</p> <p>The cor. of secs. 23, 24, 25, and 26.</p>
39.96	<p>N. 0° 04' W., bet. secs. 23 and 24.</p> <p>Over rolling desert land, through sagebrush, shadscale and creosote brush.</p> <p>The ¼ sec. cor. of secs. 23 and 24, monumented with a sandstone, 30 x 15 x 8 ins., firmly set 10 ins. in the ground and dimly mkd. ¼ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 42 S R 14 W</p> <p>¼</p> <p>S 23 S 24</p> <p>1978</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p>
40.07	<p>N. 0° 03' W., beginning new measurement.</p> <p>The cor. of secs. 13, 14, 23, and 24, monumented with a broken sandstone, a portion firmly set 6 ins. in the ground and dimly mkd. 3 notches on the S and 1 notch on the E edges.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 42 S R 14 W</p> <p>S 14 S 13</p> <p>S 23 S 24</p> <p>1978</p> </div> <p>Deposit broken remains of the stone cor. alongside the iron post.</p> <p>Cor. is located on NW slope of sandy hill.</p>
	<p>From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., heretofore described.</p> <p>N. 89° 34' W., bet. secs. 13 and 24.</p> <p>Over rolling desert land, through sagebrush, shadscale and creosote brush.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS	
0.50	Road, graded gravel, bears N and S. 10° W.
23.00	Dirt road, bears N. 30° E. and S. 30° W.
40.01	Point for the ¼ sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 42 S R 14 W
	$\frac{1}{4} \frac{S \ 13}{S \ 24}$
	1978
	Deposit broken glass alongside the iron post.
80.02	The cor. of secs. 13, 14, 23, and 24.
	N. 0° 05' W., bet. secs. 13 and 14.
	Over rolling desert land, through sagebrush, shadscale and creosote brush; desc. NW slope.
39.99	The ¼ sec. cor. of secs. 13 and 14, monumented with an iron post, 2 ins. diam., extending 6 ins. above ground, with a Washington Co. brass cap, mkd. ¼ S13 and S14, a sandstone, 12 x 6 x 4 ins., dimly mkd. ¼ on W face, was buried alongside the iron post.
	At the corner point (Washington County brass cap)
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 42 S R 14 W
	$\frac{1}{4}$ $S \ 14 \ \ S \ 13$
	1978
	Invert and deposit the Washington brass cap and the mkd. stone alongside the iron post.
	Cor. is located in E - W fence line.
	N. 0° 02' W., beginning new measurement.
2.00	Dirt road, bears NE and SW.
40.03	The cor. of secs. 11, 12, 13, and 14, monumented with an iron post, 2 ins. diam., extending 6 ins. above ground, with a Washington Co. brass cap, mkd. T42S R14W S11, S12, S13, and S14, a sandstone, 24 x 12 x 5 ins., mkd. 4 notches on the S and 1 notch on the E edges was buried alongside the iron post.
	At the corner point (Washington County brass cap)

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 42 S R 14 W

S 11	S 12
S 14	S 13

1978

Invert and deposit the Washington Co. brass cap, the mkd. stone and a steel fence post alongside the iron post.

From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., heretofore described.

N. 89° 39' W., bet. secs. 12 and 13.

Over gentle rolling desert land, through sagebrush, shadscale and creosote brush.

0.25 Dirt road, bears N and S.

20.05 Point for the E 1/16 sec. cor. of secs. 12 and 13.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 42 S R 14 W

E 1/16	S 12	S 13
--------	------	------

1978

Set a steel fence post alongside the iron post.

40.10 The ¼ sec. cor. of secs. 12 and 13, monumented with an iron post, 2½ ins. diam., extending 8 ins. above ground, with a Washington Co. brass cap mkd. T42S R14W ¼ S12 S13 1973.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 42 S R 14 W

¼	S 12	S 13
---	------	------

1978

Invert and deposit the Washington Co. brass cap alongside the iron post.

This position is accepted as a careful and faithful perpetuation of the position of the original corner.

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS

- N. 89° 40' W., beginning new measurement.
- 26.00 Trail road, bears N. 30° W. and S. 30° E.
- 40.10 The cor. of secs. 11, 12, 13, and 14.
-
- N. 0° 07' W., bet. secs. 11 and 12.
- Over rolling desert land, through sagebrush, shadscale and creosote brush.
- 31.00 Dirt road, bears N. 30° W. and S. 30° E.
- 40.06 The $\frac{1}{4}$ sec. cor. of secs. 11 and 12, monumented with an iron post, 2 $\frac{1}{2}$ ins. diam., extending 8 ins. above ground, with a Washington Co. brass cap mkd. T42S R14W $\frac{1}{4}$ S11 S12 1973, a sandstone, 24 x 12 x 4 ins., plainly mkd. $\frac{1}{4}$ on W face was buried alongside the iron post.
- At the corner point (Washington County brass cap)
- Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
- T 42 S R 14 W
- $\frac{1}{4}$
 |
 S 11 | S 12
 |
 1978
- Invert and deposit the Washington Co. brass cap and mkd. stone alongside the iron post.
-
- N. 0° 01' W., beginning new measurement.
- 40.03 The cor. of secs. 1, 2, 11, and 12, monumented with an iron post, 2 $\frac{1}{2}$ ins. diam., extending 8 ins. above ground, with Washington Co. brass cap mkd. T42S R14W S1 S2 S11 S12 1976, a lava stone, 28 x 14 x 10 ins., plainly mkd. 5 notches on the S and 1 notch on the E edges, was buried alongside the iron post.
- At the corner point (Washington County brass cap)
- Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
- T 42 S R 14 W
- $\frac{S 2}{S 11}$ | $\frac{S 1}{S 12}$
 1978
- Deposit the mkd. stone, a steel fence post and the Washington Co. brass cap inverted alongside the iron post.
- Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS	
40.17	<p>From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., heretofore described.</p> <p>N. 89° 40' W., bet. secs. 1 and 12.</p> <p>Over rolling desert land, through sagebrush, shadscale, and creosote brush.</p> <p>The ¼ sec. cor. of secs. 1 and 12, monumented with a lava stone, 20 x 12 x 10 ins., firmly set 10 ins. in the ground and plainly mkd. ¼ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 42 S R 14 W</p> <p style="text-align: center;">¼ $\frac{S 1}{S 12}$</p> <p style="text-align: center;">1978</p> <p>Deposit the mkd. stone and set a steel fence post alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 42' W., beginning new measurement.</p>
40.17	<p>The cor. of secs. 1, 2, 11, and 12.</p>
35.08	<p>N. 0° 12' E., bet. secs. 1 and 2.</p> <p>Over rolling desert land, through sagebrush, shadscale and creosote brush.</p> <p>Point for the ¼ sec. cor. of sec. 1 only, at proportionate dist.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 42 S R 14 W</p> <p style="text-align: center;">¼ S 1 </p> <p style="text-align: center;">1978</p>
40.06	<p>The ¼ sec. cor. of sec. 2 only, monumented with a lava stone, 20 x 12 x 9 ins., firmly set 10 ins. in the ground and plainly mkd. ¼ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS

T 42 S R 14 W

$\frac{1}{4}$
 S 2

1978

Deposit the mkd. stone alongside the iron post.

N. $0^{\circ} 25'$ E., beginning new measurement.

- 9.00 State Highway No. 9, bears N. 70° E. and S. 60° W.
- 13.67 Present mean high water mark, on the left bank of the Virgin River, bears N. 65° E. and S. 72° W. Point for the original meander cor. at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

M C
 S 2 | S 1

T 42 S R 14 W
1978

- 17.33 Present mean high water mark, on the right bank of the Virgin River, bears N. $14^{\circ} 15'$ W. and S. $78^{\circ} 45'$ W. Point for the original meander cor. at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 42 S R 14 W

S 2 | S 1

M C
1978

- 35.12 True point for the cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., heretofore described.

From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., heretofore described.

N. $0^{\circ} 12'$ W., bet. secs. 34 and 35.

Over rolling sand dunes, through sagebrush, shadscale, and creosote brush; desc. gentle NE slope.


- 40.06 Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 42 S R 14 W




1978

80.12 The cor. of secs. 26, 27, 34, and 35, monumented with a sandstone, 36 x 14 x 5 ins., firmly set 12 ins. in the ground and plainly mkd. 2 notches on the E and 1 notch on the S edges.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 42 S R 14 W



1978

Deposit the mkd. stone alongside the iron post.

Cor. is located in rolling sand dunes.

From the cor. of secs. 25, 26, 35, and 36.

S. 89° 39' W., bet. secs. 26 and 35.


Over series of broken spurs and washes, through sagebrush, shadscale and creosote brush; asc. NE slope.

40.22 The ¼ sec. cor. of secs. 26 and 35, monumented with a sandstone, 22 x 12 x 5 ins., firmly set in a mound of stone and plainly mkd. ¼ on N face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to broken sandstone, and in a mound of stone, 4 ft. base to top of brass cap, mkd.

T 42 S R 14 W



1978

Deposit the mkd. stone in mound alongside the iron post.

N. 89° 57' W., beginning new measurement.

40.11 The cor. of secs. 26, 27, 34, and 35.

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS

N. 0° 19' W., bet. secs. 26 and 27.

Over broken land, through sagebrush, shadscale and creosote brush; desc. N slope.

40.06 Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27, at proportionate distance, falls in dirt road, bears N and S; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. below surface of road, with brass cap mkd.

T 42 S R 14 W

S 27		S 26

1978

from which

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 45° E., 40.9 lks. dist., with brass cap mkd. RM T42S R14W $\frac{1}{4}$ S26 27 FT 1978, and an arrow pointing to the cor.

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 45° W., 40.9 lks. dist., with brass cap mkd. RM T42S R14W $\frac{1}{4}$ S27 27 FT 1978, and an arrow pointing to the cor.

80.12 The cor. of secs. 22, 23, 26, and 27, monumented with a sandstone, 14 x 12 x 4 ins., firmly set 10 ins. in the ground and dimly mkd. 2 notches on the S and E edges.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 42 S R 14 W

S 22		S 23
S 27		S 26

1978

Deposit the mkd. stone alongside the iron post.

Cor. is located in 4 strand fence line, bears E and W.

From the cor. of secs. 23, 24, 25, and 26.

S. 89° 41' W., bet. secs. 23 and 26.

Over rolling desert land, through sagebrush, shadscale and creosote brush.

40.42 The $\frac{1}{4}$ sec. cor. of secs. 23 and 26, monumented with a sandstone, 24 x 14 x 4 ins., firmly set 12 ins. in the ground and plainly mkd. $\frac{1}{4}$ on N face.

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 42 S R 14 W

¼ $\frac{S\ 23}{S\ 26}$

1978

Deposit the mkd. stone alongside the iron post.

Cor. is located in 4 strand fence line, bears E and W.

S. 89° 44' W., beginning new measurement.

26.00 Dirt road, bears N. 20° E. and S. 20° W.

40.30 The cor. of secs. 22, 23, 26, and 27.

N. 0° 02' E., bet. secs. 22 and 23.

Over rolling desert land, through sagebrush, shadscale and creosote brush.

40.02 The ¼ sec. cor. of secs. 22 and 23, monumented with a sandstone, 16 x 12 x 4 ins., firmly set 10 ins. in the ground and dimly mkd. ¼ on W face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 42 S R 14 W

¼
S 22 | S 23

1978

Deposit the mkd. stone alongside the iron post.

N. 0° 03' E., beginning new measurement.

40.02 The cor. of secs. 14, 15, 22, and 23, monumented with a sandstone, 24 x 12 x 4 ins., firmly set 12 ins. in the ground and plainly mkd. 3 notches on the S and 2 notches on the E edges.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS					
	<p style="text-align: center;">T 42 S R 14 W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 15</td> <td style="padding: 0 5px;">S 14</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 22</td> <td style="padding: 0 5px;">S 23</td> </tr> </table> <p style="text-align: center;">1978</p> <p>Deposit the mkd. stone and set a steel fence post alongside the iron post.</p>	S 15	S 14	S 22	S 23
S 15	S 14				
S 22	S 23				
<p>21.00</p> <p>40.27</p>	<p>From the cor. of secs. 13, 14, 23, and 24.</p> <p>S. 89° 43' W., bet. secs. 14 and 23.</p> <p>Over rolling desert land, through sagebrush, shadscale and creosote brush.</p> <p>Dirt road, bears N. 30° E. and S. 30° W.</p> <p>The ¼ sec. cor. of secs. 14 and 23, monumented with a broken sandstone, 18 x 12 x 7 ins., firmly set 8 ins. in the ground and plainly mkd. ¼ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>				
<p>40.27</p>	<p style="text-align: center;">T 42 S R 14 W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">¼</td> <td style="padding: 0 5px;">S 14</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">S 23</td> </tr> </table> <p style="text-align: center;">1978</p> <p>Deposit the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 43' W., beginning new measurement.</p> <p>The cor. of secs. 14, 15, 22, and 23.</p>	¼	S 14		S 23
¼	S 14				
	S 23				
<p>20.05</p>	<p>N. 0° 01' E., bet. secs. 14 and 15.</p> <p>Over rolling desert land, through sagebrush, shadscale and creosote brush.</p> <p>Point for the S 1/16 sec. cor. of secs. 14 and 15.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>				
<p>40.10</p>	<p style="text-align: center;">T 42 S R 14 W</p> <p style="text-align: center;">S 1/16</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 15</td> <td style="padding: 0 5px;">S 14</td> </tr> </table> <p style="text-align: center;">1978</p> <p>The ¼ sec. cor. of secs. 14 and 15, monumented with a sandstone, 26 x 16 x 4 ins., firmly set 12 ins. in the ground and plainly mkd. ¼ on W face.</p>	S 15	S 14		
S 15	S 14				

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS		
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 42 S R 14 W</p> <p style="text-align: center;"> $\frac{1}{4}$ S 15 S 14 </p> <p style="text-align: center;">1978</p> <p>Deposit the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 03' W., beginning new measurement.</p>	
<p>19.85</p>	<p>Point for the N 1/16 sec. cor. of secs. 14 and 15.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 42 S R 14 W N 1/16</p> <p style="text-align: center;">S 15 S 14</p> <p style="text-align: center;">1978</p>	
<p>39.70</p>	<p>The cor. of secs. 10, 11, 14, and 15, monumented with an iron post, 2½ ins. diam., extending 12 ins. above ground, with a Washington County brass cap mkd.</p> <p style="text-align: center;">T 42 S</p> <p style="text-align: center;"> $\frac{S\ 10}{S\ 15}$ $\frac{S\ 11}{S\ 14}$ </p> <p style="text-align: center;">R 14 W 1973</p> <p>A lava stone, 18 x 12 x 10 ins., dimly mkd. 4 notches on the S and 2 notches on the E edges, was buried alongside the Washington Co. cor.</p>	
<p>20.11</p>	<p>From the cor. of secs. 11, 12, 13, and 14. ...</p> <p>S. 89° 49' W., bet. secs. 11 and 14.</p> <p>Over rolling desert land, through sagebrush, shadscale and creosote brush.</p> <p>Point for the E 1/16 sec. cor. of secs. 11 and 14.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 42 S R 14 W</p> <p style="text-align: center;">E 1/16 $\frac{S\ 11}{S\ 14}$</p> <p style="text-align: center;">1978</p>	


Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS		
40.22	<p>The $\frac{1}{4}$ sec. cor. of secs. 11 and 14, monumented with an iron post, $2\frac{1}{2}$ ins. diam., extending 8 ins. above ground, with Washington Co. brass cap mkd.</p> <p style="text-align: center;">T 42 S R 14 W</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S 11}{S 14}$</p> <p style="text-align: center;">1973</p> <p>A sandstone, 30 x 16 x 4 ins., plainly mkd. $\frac{1}{4}$ on one face, was buried alongside the corner.</p> <p style="text-align: center;">_____</p> <p>S. $89^{\circ} 19'$ W., beginning new measurement.</p>	
20.115	<p>Point for the W $1/16$ sec. cor. of secs. 11 and 14.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 42 S R 14 W</p> <p style="text-align: center;">W $1/16$ $\frac{S 11}{S 14}$</p> <p style="text-align: center;">1978</p>	
40.23	<p>The cor. of secs. 10, 11, 14, and 15.</p>	
20.16	<p>N. $0^{\circ} 01'$ E., bet. secs. 10 and 11.</p> <p>Over rolling desert land, through sagebrush, shadscale and creosote brush; desc. gentle NW slope.</p> <p>Point for the S $1/16$ sec. cor. of secs. 10 and 11.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 42 S R 14 W S $1/16$</p> <p style="text-align: center;">S 10 S 11</p> <p style="text-align: center;">1978</p> <p>Cor. is located on N edge of dirt road, bears E and W.</p>	
40.32	<p>The $\frac{1}{4}$ sec. cor. of secs. 10 and 11, monumented with a lava stone, 27 x 15 x 6 ins., firmly set in a mound of stone and plainly mkd. $\frac{1}{4}$ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground to solid bedrock, over a cross (X), and in a mound of stone, $4\frac{1}{2}$ ft. base to top of brass cap, mkd.</p>	

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS

T 42 S R 14 W



1978


Deposit the mkd. stone in mound alongside the iron post.

Cor. is located in 5 strand fence line, bears E and W.

N. 0° 08' E., beginning new measurement.

24.33 Present mean high water mark, on the left bank of the Virgin River, bears N. 20° 30' E. and S. 27° W. Point for the original meander cor. at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.



1978

30.99 Point for the original meander cor. of secs. 10 and 11 at the present mean high water mark, on the right bank of the Virgin River, bears N. 37° 05' E. and S. 27° W., at proportionate distance; there is no remaining evidence of the original corner. This point falls on loose sandy bank and cannot be monumented.

31.18 Point selected for the witness cor. to the meander cor. of secs. 10 and 11, on the right bank of the Virgin River.

Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.

T 42 S R 14 W

S 10 | S 11



WMC

1978

Asc. broken SE slope.

40.12 The cor. of secs. 2, 3, 10, and 11, monumented with a sandstone, 20 x 15 x 5 ins., firmly set in a mound of stone and plainly mkd. 5 notches on the S and 2 notches on the E edges.

At the corner point

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., on solid rock, over a cross (X), in a mound of stone, 5 ft. base, to top of brass cap, mkd.

T 42 S R 14 W

S 3	S 2
S 10	S 11

1978

Set the mkd. stone and a steel fence post alongside the iron post.

Cor. is located on broken SE slope of hill.

From the cor. of secs. 1, 2, 11, and 12.

N. 89° 59' W., bet. secs. 2 and 11.

Over rolling desert land, through sagebrush, shadscale and creosote brush.

14.50 Dirt road, bears N and S.

40.27 The ¼ sec. cor. of secs. 2 and 11, monumented with a lava stone, 25 x 12 x 4 ins., firmly set 12 ins. in the ground and plainly mkd. ¼ on N face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 42 S R 14 W

¼	S 2	S 11
	S 11	

1978

Deposit the mkd. stone alongside the iron post.

Cor. is located in old fence line, bears E and W.

S. 89° 38' W., beginning new measurement.

29.50 Present mean high water mark, on the left bank of the Virgin River, bears N. 30° 30' E. and S. 39° 15' W. Point for the original meander cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original cor. Point falls on loose sandy bank and cannot be monumented.

33.06 Present mean high water mark, on the right bank of the Virgin River, bears N. 39° 45' E. and S. 37° 05' W. Point for the original meander cor. of secs. 2 and 11, on the right bank of the Virgin River, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines,
T. 42 S.; R. 14 W., Salt Lake Meridian, Utah

CHAINS		
	<p style="text-align: center;">T 42 S R 14 W</p> <p style="text-align: center;"> $\frac{S\ 2}{S\ 11} \diagup MC$ </p> <p style="text-align: center;">1978</p>	
<p>39.97</p> <p>40.09</p> <p>29.25</p> <p>35.55</p>	<p>The cor. of secs. 2, 3, 10, and 11.</p> <hr/> <p>N. 0° 26' E., bet. secs. 2 and 3.</p> <p>Over broken mountainous land, through sagebrush, shade-scale and creosote brush; asc. SE slope.</p> <p>The ¼ sec. cor. of secs. 2 and 3, monumented with an iron post, 2½ ins. diam., set in a mound of stone, 3 ft. base, to top, with Washington Co. brass cap mkd.</p> <p style="text-align: center;">T 42 S</p> <p style="text-align: center;"> $\frac{1}{4}$ $S\ 3 \mid S\ 2$ $LS\ 426\ UT$ </p> <p style="text-align: center;">1978</p> <p>This position is accepted as a careful and faithful perpetuation of the position of the original cor.</p> <p>Set a steel fence post alongside the iron post.</p> <hr/> <p>N. 0° 27' E., beginning new measurement.</p> <p>State Highway No. 9, bears S. 87° W. and E.</p> <p>The closing cor. of secs. 2 and 3, on the N. bdy. of the Tp., heretofore described.</p>	
<p>40.09</p>	<p>From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., heretofore described.</p> <p>N. 0° 08' W., bet. secs. 33 and 34.</p> <p>Over broken mountainous land, through sagebrush, shade-scale and creosote brush; desc. sandy N slope.</p> <p>The ¼ sec. cor. of secs. 33 and 34, monumented with a red sandstone, 24 x 24 x 5 ins., firmly set 6 ins. in the ground and in a mound of stone, plainly mkd. ¼ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, to top of brass cap, mkd.</p>	

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS

T 42 S R 14 W

$$\begin{array}{c} \frac{1}{4} \\ | \\ \text{S } 33 \quad | \quad \text{S } 34 \\ | \end{array}$$

1978

Deposit the mkd. stone in mound alongside the cor.

N. $0^{\circ} 07' W.$, beginning new measurement.

- 40.10 The cor. of secs. 27, 28, 33, and 34, monumented with a sandstone, 30 x 14 x 6 ins., firmly set 12 ins. in the ground and plainly mkd. 3 notches on the E and 1 notch on the S edges.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 42 S R 14 W

$$\begin{array}{c} \text{S } 28 \quad | \quad \text{S } 27 \\ \text{S } 33 \quad | \quad \text{S } 34 \end{array}$$

1978

Deposit the mkd. stone alongside the iron post.

Cor. is located on steep sandy NE slope of hill.

From the cor. of secs. 26, 27, 34, and 35.

S. $89^{\circ} 38' W.$, bet. secs. 27 and 34.

Over rolling sandy mountainous land, through sagebrush, shadscale and creosote brush.

- 40.11 The $\frac{1}{4}$ sec. cor. of secs. 27 and 34, monumented with a sandstone, 30 x 14 x 6 ins., firmly set 12 ins. in the ground and plainly mkd. $\frac{1}{4}$ on N face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, $3\frac{1}{2}$ ft. base, to top of brass cap, mkd.

T 42 S R 14 W

$$\frac{1}{4} \begin{array}{c} \text{S } 27 \\ \text{S } 34 \end{array}$$

1978

Deposit the mkd. stone in mound alongside the iron post.

N. $89^{\circ} 52' W.$, beginning new measurement.

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS		
39.99	The cor. of secs. 27, 28, 33, and 34.	
40.14	<p>N. 0° 09' W., bet. secs. 27 and 28.</p> <p>Over broken mountainous land, through sagebrush, shad-scale and creosote brush; desc. NE slope.</p> <p>The ¼ sec. cor. of secs. 27 and 28, monumented with a sandstone, 20 x 14 x 10 ins., firmly set 10 ins. in the ground and plainly mkd. ¼ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 42 S R 14 W</p> <div style="text-align: center;"> $\begin{array}{c} \frac{1}{4} \\ \\ \text{S } 28 \quad \quad \text{S } 27 \\ \end{array}$ </div> <p style="text-align: center;">1978</p> <p>Deposit the mkd. stone alongside the iron post.</p>	
40.11	<p>N. 0° 08' W., beginning new measurement.</p> <p>The cor. of secs. 21, 22, 27, and 28, monumented with a broken sandstone, 16 x 10 x 4 ins., firmly set 8 ins. in the ground and dimly mkd. 3 notches on the E and 2 notches on the S edges.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 42 S R 14 W</p> <div style="text-align: center;"> $\begin{array}{c} \text{S } 21 \quad \quad \text{S } 22 \\ \text{S } 28 \quad \quad \text{S } 27 \end{array}$ </div> <p style="text-align: center;">1978</p> <p>Deposit the mkd. stone alongside the iron post.</p>	
39.93	<p>From the cor. of secs. 22, 23, 26, and 27.</p> <p>S. 89° 59' W., bet. secs. 22 and 27.</p> <p>Over rolling sandy desert land, through sagebrush, shad-scale and creosote brush; along E-W fence line.</p> <p>Point for the ¼ sec. cor. of secs. 22 and 27, at proportionate distance; there is no remaining evidence of the original corner.</p>	

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS		
79.86	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 42 S R 14 W</p> <p style="text-align: center;">¼ $\frac{S\ 22}{S\ 27}$</p> <p style="text-align: center;">1978</p> <p>Cor. is located 15 lks. dist. N of fence line, bears E and W.</p> <p>The cor. of secs. 21, 22, 27, and 28.</p>	
40.16	<p>N. 0° 07' W., bet. secs. 21 and 22.</p> <p>Over rolling sandy desert land, through sagebrush, shade-scale and creosote brush; asc. gentle SE slope.</p> <p>The ¼ sec. cor. of secs. 21 and 22, monumented with a sandstone, 24 x 12 x 10 ins. firmly set 8 ins. in the ground and plainly mkd. ¼ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 42 S R 14 W</p> <p style="text-align: center;">¼ S 21 S 22</p> <p style="text-align: center;">1978</p> <p>Deposit the mkd. stone in mound and set a steel fence post alongside the iron post.</p> <p>Cor. is located on top of sandridge, bears NE and SW.</p> <p style="text-align: center;">—————</p> <p>N. 0° 09' W., beginning new measurement.</p> <p>Desc. broken NW slope.</p>	
28.00	<p>Dirt road, bears NE and SW.</p>	
40.12	<p>The cor. of secs. 15, 16, 21, and 22, monumented with a sandstone, 22 x 10 x 8 ins., firmly set 10 ins. in the ground and plainly mkd. 3 notches on the S and E edges.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS						
	<p style="text-align: center;">T 42 S R 14 W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 16</td> <td style="padding: 0 5px;">S 15</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 21</td> <td style="padding: 0 5px;">S 22</td> </tr> </table> <p style="text-align: center;">1978</p> <p>Deposit the mkd. stone and set a steel fence post alongside the iron post.</p>	S 16	S 15	S 21	S 22	
S 16	S 15					
S 21	S 22					
<p>40.08</p>	<p>From the cor. of secs. 14, 15, 22, and 23.</p> <p>N. 89° 46' W., bet. secs. 15 and 22.</p> <p>Over rolling desert land, through sagebrush, shadscale and creosote brush.</p> <p>The ¼ sec. cor. of secs. 15 and 22, marked by a cross (X) on solid sandstone, 8 ins. long, with a ¼ on N side of the cross.</p> <p>At the corner point</p> <p>Set an iron post, 12 ins. long, 1 in. diam., drilled 8 ins. in solid sandstone, at the exact cor. point, with brass cap mkd.</p> <p style="text-align: center;">T 42 S R 14 W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 0 5px;">¼</td> <td style="border-right: 1px solid black; padding: 0 5px;">S 15</td> <td style="padding: 0 5px;">S 22</td> </tr> </table> <p style="text-align: center;">1978</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 51' W., beginning new measurement.</p>	¼	S 15	S 22		
¼	S 15	S 22				
<p>31.50</p> <p>40.03</p> <p>20.03</p>	<p>Dirt road, bears N and S.</p> <p>The cor. of secs. 15, 16, 21, and 22.</p> <p>N. 0° 13' W., bet. secs. 15 and 16.</p> <p>Over broken desert land, through sagebrush, shadscale and creosote brush.</p> <p>Point for the S 1/16 sec. cor. of secs. 15 and 16.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 42 S R 14 W</p> <p style="text-align: center;">S 1/16</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 16</td> <td style="padding: 0 5px;">S 15</td> </tr> </table> <p style="text-align: center;">1978</p> <p>Cor. is located on W slope of terrace, along river bottom.</p>	S 16	S 15			
S 16	S 15					

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS		
40.06	<p>The $\frac{1}{4}$ sec. cor. of secs. 15 and 16, monumented with a Washington Co. corner, set in concrete, with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$</p> <p style="text-align: center;">S 16 S 15</p> <p style="text-align: center;">T 42 S R 14 W S.L.B.M. 1976</p> <p>This position is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. $0^{\circ} 13' W.$, beginning new measurement.</p>	
10.51	<p>Point selected for the witness cor. to the original meander cor. of secs. 15 and 16, on the left bank of the Virgin River.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">W M C S 16 ↑ S 15</p> <p style="text-align: center;">T 42 S R 14 W 1978</p>	
12.01	<p>Present mean high water mark, on the left bank of the Virgin River, bears N. $54^{\circ} 30' E.$ and S. $47^{\circ} 55' W.$ True point for the original meander cor. of secs. 15 and 16, at proportionate distance falls on loose sandy bank and cannot be monumented; there is no remaining evidence of the original corner.</p>	
15.35	<p>Present mean high water mark, on the right bank of the Virgin River, bears N. $56^{\circ} 15' E.$ and S. $62^{\circ} W.$ Point for the original meander cor. of secs. 15 and 16 at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 42 S R 14 W</p> <p style="text-align: center;">S 16 S 15</p> <p style="text-align: center;">M C 1978</p>	
40.04	<p>Point for the cor. of secs. 9, 10, 15, and 16, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p>	

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS						
	<p style="text-align: center;">T 42 S R 14 W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 9</td> <td style="padding: 0 5px;">S 10</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 16</td> <td style="padding: 0 5px;">S 15</td> </tr> </table> <p style="text-align: center;">1978</p> <p>Cor. is located on S side of wash in ravine, drains SW.</p>	S 9	S 10	S 16	S 15	
S 9	S 10					
S 16	S 15					
20.105	<p>From the cor. of secs. 10, 11, 14, and 15.</p> <p>N. 89° 37' W., bet. secs. 10 and 15.</p> <p>Over rolling desert land, through sagebrush, shadscale, and creosote brush.</p> <p>Point for the E 1/16 sec. cor. of secs. 10 and 15.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 42 S R 14 W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">E 1/16</td> <td style="padding: 0 5px;">S 10</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">S 15</td> </tr> </table> <p style="text-align: center;">1978</p>	E 1/16	S 10		S 15	
E 1/16	S 10					
	S 15					
40.21	<p>Point for the ¼ sec. cor. of secs. 10 and 15, at proportionate distance; falls in dirt road, bears N and S; there is no remaining evidence of the original corner.</p> <p>Deposit broken glass 12 ins. below surface of road.</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 67° 15' E., 48.5 lks. dist., with brass cap mkd. RM T42S R14W ¼ S10 32 FT 1978 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 65° 15' E., 48.5 lks. dist., with brass cap mkd. RM T42S R14W ¼ S15 32 FT 1978 and an arrow pointing to the cor.</p> <p>Cor. is located in thick tamarack.</p>					
53.44	<p>Present mean high water mark, on the left bank of the Virgin River, bears N. 40° 15' E. and S. 38° W. Point for the original meander cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 42 S R 14 W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">M</td> <td style="padding: 0 5px;">S 10</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">C</td> <td style="padding: 0 5px;">S 15</td> </tr> </table> <p style="text-align: center;">1978</p>	M	S 10	C	S 15	
M	S 10					
C	S 15					

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS							
56.62	<p>Cor. is located in thick tamarack.</p> <p>Present mean high water mark, on the right bank of the Virgin River, bears N. 40° 45' E. and S. 40° 45' W. Point for the original meander cor. of secs. 10 and 15 at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 42 S R 14 W</p> <p style="text-align: center;"> <table style="margin: auto;"> <tr> <td style="text-align: center;">S 10</td> <td style="text-align: center;">/</td> <td style="text-align: center;">M</td> </tr> <tr> <td style="text-align: center;">S 15</td> <td style="text-align: center;">/</td> <td style="text-align: center;">C</td> </tr> </table> </p> <p style="text-align: center;">1978</p>	S 10	/	M	S 15	/	C
S 10	/	M					
S 15	/	C					
80.42	<p>The cor. of secs. 9, 10, 15, and 16.</p> <hr/> <p>N. 0° 01' W., bet. secs. 9 and 10.</p> <p>Over broken mountainous land, through sagebrush, shade-scale and creosote brush; desc. NW slope.</p> <p>The ¼ sec. cor. of secs. 9 and 10, monumented with a sandstone, 20 x 10 x 8 ins., firmly set 10 ins. in the ground and plainly mkd. ¼ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 42 S R 14 W</p> <p style="text-align: center;"> <table style="margin: auto;"> <tr> <td style="text-align: center;">¼</td> <td style="text-align: center;"> </td> <td style="text-align: center;">¼</td> </tr> <tr> <td style="text-align: center;">S 9</td> <td style="text-align: center;"> </td> <td style="text-align: center;">S 10</td> </tr> </table> </p> <p style="text-align: center;">1978</p>	¼		¼	S 9		S 10
¼		¼					
S 9		S 10					
39.89	<p>Deposit the mkd. stone alongside the iron post.</p> <p>Cor. is located at the cor. of fence, projecting N, E, W and S. 45° E.</p> <p style="text-align: center;">_____</p> <p>N. 0° 05' W., beginning new measurement.</p> <p>Along fence line.</p> <p>The cor. of secs. 9 and 10 only, monumented with a limestone, 20 x 10 x 6 ins., firmly set 10 ins. in the ground and dimly mkd. 5 notches on the S and 3 notches on the E edges.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground,, and in a collar of stone, with brass cap mkd.</p>						

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS		
	<p style="text-align: center;">T 42 S R 14 W</p> <p style="text-align: center;"> $\begin{array}{r} S 3 \\ \hline S 9 \quad \quad S 10 \end{array}$ </p> <p style="text-align: center;">1978</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Cor. is located at the cor. of fence, bears S and W.</p> <p>From this cor., the closing cor. of secs. 3 and 4, bears N. 89° 46' W., 5.60 chs. dist., hereinafter described.</p>	
39.88	<p>From the cor. of secs. 2, 3, 10, and 11.</p> <p>S. 89° 22' W., bet. secs. 3 and 10.</p> <p>Over broken mountainous land, through sagebrush, shade-scale and creosote brush; asc. SE slope.</p> <p>The $\frac{1}{4}$ sec. cor. of sec. 10 only, monumented with a red sandstone, 24 x 8 x 6 ins., firmly set 12 ins. in the ground and plainly mkd. $\frac{1}{4}$ on S face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap mkd.</p>	
4.93	<p style="text-align: center;">T 42 S R 14 W</p> <p style="text-align: center;"> $\begin{array}{r} \frac{1}{4} \quad S 10 \\ \hline \end{array}$ </p> <p style="text-align: center;">1978</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p style="text-align: center;">_____</p> <p>N. 89° 17' W., beginning new measurement.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of sec. 3 only, at proportionate distance.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	
40.69	<p style="text-align: center;">T 42 S R 14 W</p> <p style="text-align: center;"> $\begin{array}{r} \frac{1}{4} \quad S 3 \\ \hline \end{array}$ </p> <p style="text-align: center;">1978</p> <p>The cor. of secs. 9 and 10 only.</p>	
	<p>From the cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., heretofore described.</p> <p>S. 0° 48' E., bet. secs. 3 and 4.</p>	

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS		
	Over rolling desert land, through sagebrush, shadscale and creosote brush.	
0.50	Old Highway, bears N. 40° 30' E. and S. 40° 30' W.	
20.05	Point for the N 1/16 sec. cor. of secs. 3 and 4.	
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.	
	<p style="text-align: center;">T 42 S R 14 W N 1/16</p> <p style="text-align: center;">S 4 S 3</p> <p style="text-align: center;">1978</p>	
31.00	State Highway No. 9, bears N. 56° E. and S. 56° W.	
35.04	The ¼ sec. cor. of sec. 3 only, monumented with an iron post, 2½ ins. diam., extending 12 ins. above ground, with Washington Co. brass cap mkd.	
	<p style="text-align: center;">T 42 S R 14 W</p> <p style="text-align: center;"> ¼ S 3</p> <p style="text-align: center;">1974</p>	
	This position is accepted as a careful and faithful determination of the position of the corner.	
40.10	The ¼ sec. cor. of sec. 4 only, monumented with an iron post, 2½ ins. diam., extending 12 ins. above ground, with Washington Co. brass cap mkd. T42S R14W ¼ S4 1974. A sandstone, 14 x 10 x 4 ins., plainly mkd. ¼ on one face was buried alongside.	
	At the corner point (Washington County brass cap)	
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.	
	<p style="text-align: center;">T 42 S R 14 W</p> <p style="text-align: center;">¼ S 4 </p> <p style="text-align: center;">1978</p>	
	Invert and deposit the Washington Co. brass cap and the mkd. stone alongside the iron post.	
	S. 0° 13' E., beginning new measurement.	
35.22	The original closing cor. of secs. 3 and 4, monumented with an iron post, 2½ ins. diam., extending 6 ins. above ground, with Washington Co. brass cap mkd. T42S R14W CC S3 S4 1974. A white sandstone, 15 x 7 x 6 ins., plainly mkd. was buried alongside. Mark both corners with the letters AM.	

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS		
35.30	<p>Intersect the N. bdy. of sec. 9.</p> <p>Point for the closing cor. of secs. 3 and 4.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C C T 42 S R 14 W</p> <p style="text-align: center;"><u>S 4 S 3</u> S 9</p> <p style="text-align: center;">1978</p> <p>Set a cedar post, 6 ft. long, alongside the cor.</p>	
40.03	<p>From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., heretofore described.</p> <p>N. 0° 04' W., bet. secs. 32 and 33.</p> <p>Over rolling sand on top of Sand Mountain.</p> <p>The ¼ sec. cor. of secs. 32 and 33, monumented with a sandstone, 24 x 14 x 4 ins., set in a mound of stone on exposed sandstone and plainly mkd. ¼ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., on solid sandstone, over a cross (X), in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 42 S R 14 W</p> <p style="text-align: center;">¼ S 32 S 33 </p> <p style="text-align: center;">1978</p> <p>Place the mkd. stone in mound alongside the iron post.</p> <p>N. 0° 03' W., beginning new measurement.</p> <p>Desc. over broken NW slope.</p>	
39.95	<p>The cor. of secs. 28, 29, 32, and 33, monumented with a sandstone, 18 x 12 x 4 ins., firmly set 10 ins. in the ground and plainly mkd. 1 notch on S and 4 notches on E edges.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 42 S R 14 W</p> <p style="text-align: center;"><u>S 29 S 28</u> <u>S 32 S 33</u></p> <p style="text-align: center;">1978</p>	

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS	
	Place the mkd. stone in collar of stone alongside the iron post.
40.05	<p>From the cor. of secs. 27, 28, 33, and 34.</p> <p>S. 89° 44' W., bet. secs. 28 and 33.</p> <p>Over broken desert land; asc. over sandy NE slope.</p> <p>Point for the ¼ sec. cor. of secs. 28 and 33, at proportionate distance.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 42 S R 14 W</p> <p style="text-align: center;">¼ $\frac{S\ 28}{S\ 33}$</p> <p style="text-align: center;">1978</p> <p>A sandstone, 20 x 12 x 5 ins., mkd. ¼ on one face was found lying loose down hill, and was placed in the collar of stone.</p>
80.10	<p>The cor. of secs. 28, 29, 32, and 33.</p> <p>N. 0° 07' W., bet. secs. 28 and 29.</p> <p>Over broken and ledgy desert land; desc. along W slope.</p> <p>39.80 The ¼ sec. cor. of secs. 28 and 29, monumented with a sandstone, 20 x 10 x 5 ins., firmly set 10 ins. in the ground and plainly mkd. ¼ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 42 S R 14 W</p> <p style="text-align: center;">¼ S 29 S 28</p> <p style="text-align: center;">1978</p> <p>Deposit the mkd. stone inverted alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>North, beginning new measurement.</p> <p>Desc. over broken general W slope.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS		
40.26	<p>The cor. of secs. 20, 21, 28, and 29, monumented with an iron post, 2½ ins. diam., set in concrete, with Washington Co. brass cap mkd.</p> <p style="text-align: center;">T 42 S</p> <p style="text-align: center;">S 20 S 21 S 29 S 28</p> <p style="text-align: center;">R 14 W 1974</p> <p>A sandstone, 24 x 12 x 5 ins., mkd. with 2 and 4 notches was buried alongside the iron post.</p>	
	<p>From the cor. of secs. 21, 22, 27, and 28.</p> <p>S. 89° 27' W., bet. secs. 21 and 28.</p> <p>Over sandy rolling land on bench.</p>	
19.985	<p>Point for the E 1/16 sec. cor. of secs. 21 and 28.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 42 S R 14 W</p> <p style="text-align: center;">E 1/16 $\frac{S 21}{S 28}$</p> <p style="text-align: center;">1978</p> <p>Set a wooden stake, 4 x 4 ins., 4 ft. high, alongside the iron post.</p>	
39.97	<p>The ¼ sec. cor. of secs. 21 and 28, monumented with a red sandstone, 24 x 10 x 10 ins., firmly set 10 ins. in the ground and plainly mkd. ¼ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 42 S R 14 W</p> <p style="text-align: center;">¼ $\frac{S 21}{S 28}$</p> <p style="text-align: center;">1978</p> <p>Deposit the mkd. stone in mound alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 43' W., beginning new measurement.</p> <p>Desc. over broken W slope.</p>	
20.00	<p>Point for the W 1/16 sec. cor. of secs. 21 and 28.</p>	

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS		
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 42 S R 14 W</p> <p style="text-align: center;">W 1/16 $\frac{S\ 21}{S\ 28}$</p> <p style="text-align: center;">1978</p> <p>Cor. falls on top of spur, which slopes N. Bury a sandstone, 18 x 10 x 10 ins., alongside the iron post.</p> <p>40.00 The cor. of secs. 20, 21, 28, and 29.</p>	
	<p>N. 0° 03' W., bet. secs. 20 and 21.</p>	
	<p>Over rolling sandy land, through tall creosote bushes.</p>	
10.00	<p>Graded dirt road, bears NE and SW.</p>	
15.00	<p>Point for the original witness cor. to the meander cor. of secs. 20 and 21, on the left bank of the Virgin River, at proportionate distance. Canal work has destroyed this monument.</p>	
15.14	<p>Point selected for the witness cor. to the S 1/16 sec. cor. of secs. 20 and 21.</p>	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>	
	<p style="text-align: center;">W C T 42 S R 14 W S 1/16 S 20 ↑ S 21 1978</p>	
16.10	<p>This cor. will also function as the witness cor. to the meander cor. of secs. 20 and 21, on the left bank of the Virgin River.</p> <p>Washington Canal, flows SW.</p>	
20.14	<p>True point for the S 1/16 sec. cor. of secs. 20 and 21, falls in dense willows and wash area used for over flow from canal back to river, and cannot be monumented.</p>	
24.17	<p>Present mean high water mark on the left bank of the Virgin River, bears N. 67° W. and S. 67° E. True point for the original meander cor. at proportionate distance, falls on loose sandy bank.</p>	
30.61	<p>Present mean high water mark on the right bank of the Virgin River, bears N. 57° W. and S. 56° 30' E. Point for the original meander cor. of secs. 21 and 28, at proportionate distance.</p>	

246

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS		
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	
	<p>T 42 S R 14 W</p>	
	<p>S 20 S 21</p>	
	<p>MC</p>	
	<p>1978</p>	
32.63	<p>Point for the original witness cor. to the meander cor. of secs. 21 and 28, on the right bank of the Virgin River at proportionate distance; there is no remaining evidence of the original cor.</p>	
40.28	<p>The ¼ sec. cor. of secs. 21 and 28, monumented with an iron post, 2½ ins. diam., set in concrete, with Washington Co. brass cap mkd.</p>	
	<p>T 42 S</p>	
	<p>¼</p>	
	<p>S 20 S 21</p>	
	<p>R 14 W</p>	
	<p>1974</p>	
	<p>A limestone, 24 x 12 x 3 ins., mkd. ¼ on one face was buried alongside the iron post.</p>	
	<p>Set a steel fence post alongside the iron post.</p>	
	<p>N. 0° 05' W., beginning new measurement.</p>	
	<p>Asc. gentle S slope, over bench land.</p>	
40.15	<p>The cor. of secs. 16, 17, 20, and 21, monumented with an iron post, 2½ ins. diam., set in concrete, with Washington Co. brass cap mkd.</p>	
	<p>T 42 S</p>	
	<p>S 17 S 16</p>	
	<p>S 20 S 21</p>	
	<p>R 14 W</p>	
	<p>1974</p>	
	<p>A limestone, 18 x 8 x 6 ins., mkd. with 3 and 4 notches was buried alongside the iron post.</p>	
	<p>From the cor. of secs. 15, 16, 21, and 22.</p>	
	<p>S. 89° 41' W., bet. secs. 16 and 21.</p>	
	<p>Over broken gravelly bench.</p>	
14.11	<p>Point selected for the witness cor. to the meander cor. of secs. 16 and 21, on the left bank of the Virgin River.</p>	

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 42 S R 14 W</p> <p style="text-align: center;">WMC ↙ S 16 ↘ S 21</p> <p style="text-align: center;">1978</p>
18.51	<p>Present mean high water mark on the left bank of the Virgin River, bears N 19° 15' W. and S. 19° 15' E. True point for the original meander cor. of secs. 16 and 21, at proportionate distance, falls on eroding bank and cannot be monumented. There is no remaining evidence of the original cor.</p>
24.68	<p>Present mean high water mark on the right bank of the Virgin River, bears S. 6° W. and on bend to N. 6° E. Point for the original meander cor. of secs. 16 and 21, at proportionate distance, falls on eroding bank. There is no remaining evidence of the original cor. Point not monumented.</p>
39.89	<p>The ¼ sec. cor. of secs. 16 and 21, monumented with a sandstone, 20 x 12 x 6 ins., firmly set 10 ins. in the ground and plainly mkd. ¼ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 42 S R 14 W</p> <p style="text-align: center;">¼ S 16 S 21</p> <p style="text-align: center;">1978</p>
	<p>Deposit the mkd. stone in mound alongside the iron post.</p> <p style="text-align: center;">_____</p> <p>S. 89° 42' W., beginning new measurement.</p> <p>Asc. over rocky E slope.</p>
19.98	<p>Point for the W 1/16 sec. cor. of secs. 16 and 21.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T 42 S R 14 W</p> <p style="text-align: center;">W 1/16 S 16 S 21</p> <p style="text-align: center;">1978</p>
39.96	<p>The cor. of secs. 16, 17, 20, and 21.</p>
	<p>N. 0° 03' W., bet. secs. 16 and 17.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS		
<p>39.64</p>	<p>Over broken desert land; asc. over SE slope across clay and gypsum hills.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 16 and 17, monumented with a limestone, 18 x 14 x 6 ins., firmly set in a mound of stone and plainly mkd. $\frac{1}{4}$ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., on solid rock, over a cross (X), in a mound of stone, 5 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 42 S R 14 W</p> <p style="text-align: center;"> $\frac{1}{4}$ S 17 S 16 </p> <p style="text-align: center;">1978</p> <p>Deposit the mkd. stone in mound alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 28' W., beginning new measurement.</p> <p>Asc. over rocky SE slope.</p>	
<p>39.40</p> <p>40.03</p> <p>40.01</p>	<p>Bull dozed road to oil well, bears E and W.</p> <p>Point for the cor. of secs. 8, 9, 16, and 17, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 42 S R 14 W</p> <p style="text-align: center;"> S 8 S 9 S 17 S 16 </p> <p style="text-align: center;">1978</p> <hr/> <p>From the cor. of secs. 9, 10, 15, and 16.</p> <p>S. 89° 32' W., bet. secs. 9 and 16.</p> <p>Over broken desert land.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 9 and 16, monumented with a limestone, 14 x 4 x 4 ins., firmly set 10 ins. in the ground and plainly mkd. $\frac{1}{4}$ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 42 S R 14 W</p> <p style="text-align: center;"> $\frac{1}{4}$ S 9 S 16 </p> <p style="text-align: center;">1978</p>	

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS

Deposit the mkd. stone alongside the iron post and raise a mound of stone, 2 ft. base, 2 ft. high, N of cor.

Cor. is located 1.00 ch. West of a wash, 2 ft. deep, 10 lks. wide, drains S.

S. 89° 13' W., beginning new measurement.

Asc. over gentle E slope.

39.83 The cor. of secs. 8, 9, 16, and 17.

N. 0° 25' E., bet. secs. 8 and 9.

Over rolling land, covered with shadscale; desc. over gentle NW slope.

40.03 The $\frac{1}{4}$ sec. cor. of secs. 8 and 9, monumented with a sandstone, 16 x 10 x 6 ins., firmly set 10 ins. in the ground and plainly mkd. $\frac{1}{4}$ on W face.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 42 S R 14 W

$\frac{1}{4}$
 |
 S 8 | S 9

1978

Deposit the mkd. stone alongside the iron post and raise a mound of stone, 2 ft. base, 2 ft. high, W of cor..

N. 0° 06' W., beginning new measurement.

Asc. over SE slope, across clay and gypsum hills.

40.55 The cor. of secs. 8 and 9, monumented with an iron post, 2 $\frac{1}{2}$ ins. diam., set in concrete, with Washington Co. brass cap mkd.

T 42 S

$\frac{S}{S} \frac{4}{8} \frac{S}{S} \frac{9}{9}$

R 14 W
1974

A sandstone, 20 x 14 x 6 ins., mkd. 4 and 5 notches, was buried alongside the iron post.

From the cor. of secs. 9 and 10.

N. 89° 46' W., along the N. bdy. of sec. 9.

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS

From this cor., the closing cor. of secs. 4 and 8, on the E. bdy. of sec. 5, bears S. $89^{\circ} 26'$ W., 8.05 chs. dist., monumented with a Washington County survey marker, a brass tablet cemented flush with hard surface of old highway, which bears N. $37^{\circ} 45'$ E., and S. $37^{\circ} 45'$ W., the brass tablet mkd.

T 42 S

S 5		S 4
		S 8

R 14 W
1974

This position is accepted as a careful and faithful perpetuation of the position of the original cor.

From the SE cor. of sec. 5, monumented with an iron post, $2\frac{1}{2}$ ins. diam., set in concrete with Washington Co. brass cap mkd.

T 42 S

S 5		
		R 14 W

1974

A sandstone, 12 x 10 x 8 ins., mkd. as the SE cor. of sec. 5 was buried alongside the iron post.

N. $0^{\circ} 50'$ W., along the E. bdy. of sec. 5.

Over desert land, covered with creosote bush; asc. over general S slope.

- 4.97 The closing cor. of secs. 4 and 8, heretofore described.
- 37.30 State Highway No. 9 through cut in spur, bears S. $50^{\circ} 26'$ E. and N. $50^{\circ} 26'$ W.
- 40.23 The $\frac{1}{4}$ sec. cor. of secs. 4 and 5, monumented with an iron post, $2\frac{1}{2}$ ins. diam., set in concrete, with Washington Co. brass cap mkd.

T 42 S

		$\frac{1}{4}$
S 5		S 4

R 14 W
1974

A black lava stone, 18 x 14 x 6 ins., plainly mkd. $\frac{1}{4}$ was buried alongside the iron post.

N. $0^{\circ} 50'$ W., beginning new measurement.

Desc. along W slope of spur.

- 40.23 The cor. of secs. 4 and 5, on the N. bdy. of the Tp., heretofore described.

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS

From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., heretofore described.

N. 0° 07' W., bet. secs. 31 and 32.


Over broken desert land, covered with shadscale.

40.04 The ¼ sec. cor. of secs. 31 and 32, monumented with a quartzite stone, 20 x 16 x 6 ins., firmly set 10 ins. in the ground and plainly mkd. ¼ on W face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 42 S R 14 W



1978

Deposit the mkd. stone alongside the iron post.

N. 0° 05' W., beginning new measurement.


Asc. along gentle E slope.

39.99 The cor. of secs. 29, 30, 31, and 32, monumented with a granite stone, 30 x 15 x 12 ins., firmly set in a mound of stone and plainly mkd. 1 notch on S and 5 notches on E edges.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., on solid rock over a cross (X) in a mound of stone, 4 ft. base, to top of brass cap, mkd.

T 42 S R 14 W



1978

Place the mkd. stone in mound of stone alongside the iron post.

Cor. is located on SE slope, 40 lks. from top of ridge.

From the cor. of secs. 28, 29, 32, and 33.

S. 89° 58' W., bet. secs. 29 and 32.

Over broken hills, across sand and exposed sandstone outcrops.

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS		
39.69	<p>The $\frac{1}{4}$ sec. cor. of secs. 29 and 32, monumented with a white sandstone, 18 x 10 x 4 ins., firmly set 8 ins. in the ground and plainly mkd. $\frac{1}{4}$ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to bedrock; in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 42 S R 14 W</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S\ 29}{S\ 32}$</p> <p style="text-align: center;">1978</p>	
	<p>Place the mkd. stone in mound alongside the iron post.</p>	
	<p>S. $89^{\circ} 47'$ W., beginning new measurement.</p>	
16.00	<p>Dirt road, bears N. 33° E. and S. 33° W.; asc. over sandy E slope.</p>	
20.05	<p>Point for the W $1/16$ sec. cor. of secs. 29 and 32.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 42 S R 14 W</p> <p style="text-align: center;">W $1/16$ $\frac{S\ 29}{S\ 32}$</p> <p style="text-align: center;">1978</p>	
	<p>Set a wood stake, 2 x 4 ins., 5 ft. high alongside the iron post.</p>	
40.10	<p>The cor. of secs. 29, 30, 31, and 32.</p>	
	<p>S. $89^{\circ} 55'$ W., bet. secs. 30 and 31.</p>	
	<p>Over broken land; asc. over SE slope.</p>	
0.50	<p>Narrow top of Warner Ridge, bears NE and SW; desc. over steep and ledgy NW slope.</p>	
35.50	<p>Trail road, bears NE and SW.</p>	
40.18	<p>The $\frac{1}{4}$ sec. cor. of secs. 30 and 31, monumented with a granite stone, 20 x 8 x 6 ins., firmly set 10 ins. in the ground and plainly mkd. $\frac{1}{4}$ on N face.</p>	
	<p>At the corner point</p>	
	<p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap, mkd.</p>	

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS

T 42 S R 14 W

$\frac{1}{4}$ $\frac{S 30}{S 31}$

1978

Deposit the mkd. stone alongside the iron post.

N. 89° 53' W., beginning new measurement.

Over rolling land.

39.76 Point for the 80 1/16 sec. cor. of secs. 30 and 31.

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd.

T 42 S R 14 W

80 1/16 $\frac{S 30}{S 31}$

1978

Cor. is located on top of small spur which slopes SE.

45.08 The closing cor. of secs. 30 and 31, on the W. bdy. of the Tp., monumented with a granite stone, 24 x 12 x 8 ins. set in a mound of stone and plainly mkd. 1 notch on S and 5 notches on N edges, also CC on E face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., on solid rock, over a cross (X), in a mound of stone, 4 ft. base, to top of brass cap, mkd.

T 42 S
R 15 W R 14 W

S 25 | $\frac{S 30}{S 31}$ C

1978

Place the mkd. stone in mound alongside the iron post.

From this cor., the cor. of secs. 25 and 36, T. 42 S., R. 15 W., bears S. 0° 31' E., 6.57 chs. dist., monumented with an iron post, 2½ ins. diam., in a mound of stone, with brass cap mkd. as described in the official record of the 1973 resurvey of a portion of the E. bdy. of T. 42 S., R. 15 W.

From this same closing cor., the ¼ sec. cor. of sec. 25, T. 42 S., R. 15 W., bears N. 0° 31' W., 33.42 chs. dist., monumented with an iron post, 2½ ins. diam., extending 6 ins. above ground, with brass cap mkd. as described in the official record of the 1973 resurvey of a portion of the E. bdy. of T. 42 S., R. 15 W.

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS

Point for the $\frac{1}{4}$ sec. cor. of sec. 31 only, on the W. bdy. of the Tp., and midpoint bet. closing cors.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 42 S
R 15 W R 14 W

| $\frac{1}{4}$
|
| S 31

1978

From this cor., the $\frac{1}{4}$ sec. cor. of sec. 36, T. 42 S., R. 15 W., bears S. $0^{\circ} 25'$ E., 6.575 chs. dist., monumented with an iron post, $2\frac{1}{2}$ ins. diam., extending 8 ins. above ground, with brass cap mkd. as described in the official record of the 1973 resurvey of a portion of the E. bdy. of T. 42 S., R. 15 W.

From this same cor., the cor. of secs. 25 and 36, T. 42 S., R. 15 W., bears N. $0^{\circ} 25'$ W., 33.575 chs. dist., heretofore described.

From the cor. of secs. 29, 30, 31, and 32.

N. $0^{\circ} 13'$ W., bet. secs. 29 and 30.

Over broken mountain land; asc. over SE slope.

0.45 Narrow top of Warner Ridge, bears NE and SW; desc. over steep and ledgy NW slope.

40.12 Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 30, at proportionate distance; there is no remaining evidence of the original cor.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 42 S R 14 W

| $\frac{1}{4}$
|
S 30 | S 29

1978

40.90 Dirt road, bears NE and SW.

80.24 The cor. of secs. 19, 20, 29, and 30, monumented with an iron post, $2\frac{1}{2}$ ins. diam., set in concrete, with Washington Co. brass cap mkd.

T 42 S

S 19 | S 20
S 30 | S 29

R 14 W

1974

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS		
	<p>A flint stone, 16 x 10 x 8 ins., mkd. 2 and 5 notches was buried alongside the iron post.</p> <p>Set a steel fence post alongside the cor. and raise a mound of stone N of cor.</p>	
7.50	<p>From the cor. of secs. 20, 21, 28, and 29.</p> <p>N. 89° 56' W., bet. secs. 20 and 29.</p> <p>Over sandy land in bottom of small valley.</p> <p>Graded dirt road, bears N and S.</p>	
39.92	<p>The $\frac{1}{4}$ sec. cor. of secs. 20 and 29, monumented with an iron post, 2½ ins. diam., extending 6 ins. above ground, with Washington Co. brass cap mkd.</p> <p style="text-align: center;">T 42 S</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S\ 20}{S\ 29}$</p> <p style="text-align: center;">R 14 W 1974</p> <p>A lava stone, 20 x 8 x 6 ins., plainly mkd. $\frac{1}{4}$ was buried alongside the iron post.</p> <p>Set a steel fence post alongside the cor. and raise a mound of stone, N of cor.</p>	
15.20	<p>S. 89° 56' W., beginning new measurement.</p> <p>Continue along N slope.</p> <p>Dirt road, bears N. 34° E. and S. 34° W.</p>	
40.08	<p>The cor. of secs. 19, 20, 29, and 30.</p>	
39.65	<p>S. 89° 27' W., bet. secs. 19 and 30.</p> <p>Over broken hills, covered with shadscale; asc. over E slope.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 19 and 30, monumented with a gray limestone, 18 x 8 x 6 ins., firmly set 8 ins. in the ground and plainly mkd. $\frac{1}{4}$ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 42 S R 14 W</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S\ 19}{S\ 30}$</p> <p style="text-align: center;">1978</p>	

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS

Place the mkd. stone in mound alongside the iron post.
Cor. is located on W slope of small spur, which slopes N.

N. 89° 43' W., beginning new measurement.

Desc. along general N slope, over sandy hills.

20.105 Point for the W 1/16 sec. cor. of secs. 19 and 30.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 42 S R 14 W

W 1/16 $\frac{S 19}{S 30}$

1978

Over sandy hills draining N.

40.21 Point for the 80 1/16 sec. cor. of secs. 19 and 30.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 42 S R 14 W

80 1/16 $\frac{S 19}{S 30}$

1978

45.89 The closing cor. of secs. 19 and 30, on the W. bdy. of the Tp., monumented with a sandstone, 20 x 12 x 8 ins., firmly set 10 ins. in the ground and plainly mkd. 2 notches on S and 4 notches on W edges, also CC on E face. Cor. in N and S fence.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 42 S
R 15 W R 14 W

S 24 $\left| \begin{array}{l} S 19 \\ S 30 \end{array} \right. \begin{array}{l} C \\ C \end{array}$

1978

Deposit the mkd. stone alongside the iron post.

From this cor., the cor. of secs. 24 and 25, T. 42 S., R. 15 W., bears S. 0° 44' E., 5.91 chs. dist., monumented with an iron post, 2½ ins. diam., extending 6 ins. above ground, with brass cap mkd. as described in the official record of the 1973 resurvey of a portion of the E. bdy. of T. 42 S., R. 15 W.

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah


CHAINS

From this same closing cor., the $\frac{1}{4}$ sec. cor. of sec. 24, T. 42 S., R. 15 W., bears N. $0^{\circ} 44' W.$, 34.36 chs. dist., monumented with an iron post, $2\frac{1}{2}$ ins. diam., extending 8 ins. above ground, with brass cap mkd. as described in the official record of the 1973 resurvey of a portion of the E. bdy. of T. 42 S., R. 15 W.

The point for the $\frac{1}{4}$ sec. cor. of sec. 30, only, on the W. bdy. of the Tp., and midpoint bet. closing cors.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 42 S
R 15 W R 14 W



1978

From this cor., the $\frac{1}{4}$ sec. cor. of sec. 25, T. 42 S., R. 15 W., bears S. $0^{\circ} 17' E.$, 6.595 chs. dist., heretofore described.

From this same $\frac{1}{4}$ sec. cor., the N $1/16$ sec. cor. of sec. 25, T. 42 S., R. 15 W., bears N. $0^{\circ} 17' W.$, 13.755 chs. dist., monumented with an iron post, $2\frac{1}{2}$ ins. diam., extending 8 ins. above ground, with brass cap mkd. as described in the official record of the 1973 resurvey of a portion of the E. bdy. of T. 42 S., R. 15 W.

From the cor. of secs. 19, 20, 29, and 30.

N. $0^{\circ} 02' W.$, bet. secs. 19 and 20.

Over broken land, covered with shadscale desc. over N slope.

17.00 Washington Canal, flows W.


18.00 Gravel road, bears E and W.

20.03 Point for the original witness cor. to the meander cor. of secs. 19 and 20, at proportionate distance; there is no remaining evidence of the original cor.

40.07 Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 20, at proportionate distance.



Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 42 S R 14 W



1978

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS	
42.37	<p>Cor. is located at bottom of field, thence over sandy land through dense growth of willows.</p> <p>Present mean high water mark on the left bank of the Virgin River, bears N. 55° 45' E. and S. 55° 45' W., the point for the original meander cor. of secs. 19 and 20, at proportionate distance.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">  <p>T 42 S R 14 W</p> <p>1978</p> </div>
45.63	<p>Present mean high water mark on the right bank of the Virgin River, bears N. 70° 30' E. and S. 61° W., the point for the original meander cor. of secs. 19 and 20, at proportionate distance falls on loose sandy bank.</p>
45.71	<p>Point selected for the witness cor. to the meander cor. of secs. 19 and 20, on the right bank of the Virgin River.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">  <p>T 42 S R 14 W</p> <p>1978</p> </div>
46.08	<p>Point for the original witness cor. to the ¼ sec. cor. of secs. 19 and 20, at proportionate distance; there is no remaining evidence of the original cor.</p>
69.00	<p>Gravel road, bears NE and SW.</p>
80.14	<p>The cor. of secs. 17, 18, 19, and 20, monumented with a flintstone, 20 x 8 x 6 ins., firmly set 8 ins. in the ground and plainly mkd. 3 notches on the S and 5 notches on the E edges. This cor. is located on N bank of wash, which is being eroded away, and would not be safe for a permanent monument; therefore a witness cor. was established N. 0° 05' W., 0.45 chs. dist., hereinafter described.</p>
39.90	<p>From the cor. of secs. 16, 17, 20, and 21.</p> <p>S. 89° 51' W., bet. secs. 17 and 20.</p> <p>Over broken desert land, covered with shadscale; along gentle S slope.</p> <p>The ¼ sec. cor. of secs. 17 and 20, monumented with an iron post, 2½ ins. diam., set in concrete, with Washington Co. brass cap mkd.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS		
	<p style="text-align: center;">T 42 S</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S\ 17}{S\ 20}$</p> <p style="text-align: center;">R 14 W 1974</p> <p>A limestone, 20 x 10 x 6 ins., plainly mkd. $\frac{1}{4}$ was buried alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 48' W., beginning new measurement.</p>	
20.02	<p>Point for the W 1/16 sec. cor. of secs. 17 and 20.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 42 S R 14 W</p> <p style="text-align: center;">W 1/16 $\frac{S\ 17}{S\ 20}$</p> <p style="text-align: center;">1978</p> <p>Cor. is located 6 lks. N of steel fence cor., fences bear E and S. 10° E.</p>	
25.50	Dirt road, bears NW and SE.	
31.40	Graded dirt road, bears N. 10° E. and S. 10° W.	
40.04	The cor. of secs. 17, 18, 19, and 20.	
40.57	<p>S. 89° 58' W., bet. secs. 18 and 19.</p> <p>Over desert land, covered with shadscale, draining S.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 18 and 19, monumented with a sandstone, 20 x 12 x 6 ins., firmly set 10 ins. in the ground and plainly mkd. $\frac{1}{4}$ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 42 S R 14 W</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S\ 18}{S\ 19}$</p> <p style="text-align: center;">1978</p> <p>Place the mkd. stone in mound alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 58' W., beginning new measurement.</p>	

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS

- Asc. over steep and ledgy SE slope.
- 19.85 Point for the W 1/16 sec. cor. of secs. 18 and 19.
Set an iron post, 28 ins. long, 2½ ins. diam., on solid rock, over a cross (X), in a mound of stone, 4 ft. base, to top of brass cap, mkd.
- T 42 S R 14 W
- W 1/16 $\frac{S 18}{S 19}$
- 1978
- 39.70 Point for the 80 1/16 sec. cor. of secs. 18 and 19.
Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.
- T 42 S R 14 W
- 80 1/16 $\frac{S 18}{S 19}$
- 1978
- 45.88 The closing cor. of secs. 18 and 19, on the W. bdy. of the Tp., monumented with a sandstone, 30 x 10 x 8 ins., set in a mound of stone and plainly mkd. 3 notches on N and S edges, CC on E face.
- At the corner point
- Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.
- T 42 S
R 15 W R 14 W
- S 13 $\frac{S 18}{S 19}$ C
- 1978
- Place the mkd. stone in mound alongside the iron post.
- From this cor., the cor. of secs. 13 and 24, T. 42 S., R. 15 W., bears S. 0° 18' E., 5.09 chs. dist., monumented with an iron post, 2½ ins. diam., set in a mound of stone, with brass cap mkd. as described in the official record of the 1973 resurvey of a portion of the E. bdy. of T. 42 S., R. 15 W.
- From this same cor., the ¼ sec. cor. of sec. 13, T. 42 S., R. 15 W., bears N. 0° 18' W., 34.91 chs. dist., monumented with an iron post, 2½ ins. diam., set in a collar of stone, with brass cap mkd. as described in the 1973 resurvey of a portion of the E. bdy. of T. 42 S., R. 15 W.

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS

The point for the $\frac{1}{4}$ sec. cor. of sec. 19 only, on the W. bdy. of the Tp., and midpoint bet. the closing cors.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 42 S
R 15 W R 14 W

| $\frac{1}{4}$
| S 19

1978

From this cor., the $\frac{1}{4}$ sec. cor. of sec. 24, T. 42 S., R. 15 W., bears S. $0^{\circ} 42' E.$, 5.735 chs. dist., heretofore described.

From this same cor., the cor. of secs. 13 and 24, T. 42 S., R. 15 W., bears N. $0^{\circ} 42' W.$, 35.005 chs. dist., heretofore described.

Also at this point there is a sandstone, 30 x 8 x 8 ins., firmly set and plainly mkd. $\frac{1}{4}$ on W and CC on E face, there is no record of this monument, the stone is buried upside down alongside the iron post.

From the cor. of secs. 17, 18, 19, and 20.

N. $0^{\circ} 05' W.$, bet. secs. 17 and 18.

Over broken desert land, draining S.

0.45 Point selected for the witness cor. to the cor. of secs. 17, 18, 19, and 20.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

W C
T 42 S R 14 W

S 18 | S 17
S 19 | S 20

1978

Set a cedar post alongside the iron post.

40.08 The $\frac{1}{4}$ sec. cor. of secs. 17 and 18, monumented with a sandstone, 20 x 14 x 6 ins., firmly set 10 ins. in the ground and plainly mkd. $\frac{1}{4}$ on W face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS

T 42 S R 14 W

$$\begin{array}{c} \frac{1}{4} \\ | \\ \text{S } 18 \quad | \quad \text{S } 17 \\ | \end{array}$$

1978

Bury the mkd. stone inverted and set a cedar post
alongside the iron post.

North, beginning new measurement.

Asc. over broken SE slope.

16.40 Hard surface road, bears N. 53° 30' E. and S. 53° 30' W.,
also base of steep ascent, bears NE and SW; asc. over
steep rocky SE slope.

40.10 Point for the cor. of secs. 7, 8, 17, and 18, at propor-
tionate distance; there is no remaining evidence of the
original cor.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 42 S R 14 W

$$\begin{array}{c} \text{S } 7 \quad | \quad \text{S } 8 \\ \hline \text{S } 18 \quad | \quad \text{S } 17 \end{array}$$

1978

Raise a mound of stone, 2 ft. base, 2 ft. high, W of cor.

From the cor. of secs. 8, 9, 16, and 17.

S. 89° 52' W., bet. secs. 8 and 17.

Over broken desert land; desc. over gentle W slope.

39.75 The ¼ sec. cor. of secs. 8 and 17, monumented with a
sandstone, 26 x 10 x 4 ins., firmly set 10 ins. in the
ground and plainly mkd. ¼ on N face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 42 S R 14 W

$$\frac{1}{4} \begin{array}{c} \text{S } 8 \\ \hline \text{S } 17 \end{array}$$

1978

Bury the mkd. stone alongside the iron post and raise a
mound of stone, 2 ft. base, 2 ft. high, N of cor.

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS		
39.89	<p>N. 89° 28' W., beginning new measurement. Over broken gypsum hills. The cor. of secs. 7, 8, 17, and 18.</p>	
4.00 20.90 26.65	<p>S. 89° 51' W., bet. secs. 7 and 18. Over broken desert land; desc. over NW slope in small valley. Hard surface road to gravel pit, bears N. 48° E. and S. 48° W. Old highway, bears N. 66° 30' E. and S. 66° 30' W. Point for the E 1/16 sec. cor. of sec. 7 only. Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p>	
40.10	<p style="text-align: center;">T 42 S R 14 W <u>E 1/16 S 7</u> 1978</p> <p>Point for the ¼ sec. cor. of sec. 18 only, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p>	
46.70	<p style="text-align: center;">T 42 S R 14 W <u>¼ S 18</u> 1978</p> <p>Point for the ¼ sec. cor. of sec. 7 only. Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p>	
80.20	<p style="text-align: center;">T 42 S R 14 W <u>¼ S 7</u> 1978</p> <p>Point for the 80 1/16 sec. cor. of sec. 18 only, falls in large wash, which drains S, and cannot be monumented. Asc. over E slope.</p>	
80.85	<p>Point selected for the witness cor. to the 80 1/16 sec. cor. of sec. 18 only. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>	

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah


CHAINS	
86.80	<p style="text-align: center;">W C T 42 S R 14 W → 80 1/16 S 18 1978</p> <p>The closing cor. of secs. 7 and 18, on the W. bdy. of the Tp., heretofore described.</p>
	<p>The point for the 1/4 sec. cor. of sec. 18 only, on the W. bdy. of the Tp., and midpoint bet. closing cors.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 42 S R 15 W R 14 W 1/4 S 18 1978</p> <p>From this cor., the 1/4 sec. cor. of sec. 13, T. 42 S., R. 15 W., bears S. 0° 20' E., 5.09 chs. dist., heretofore described.</p> <p>From this same cor., the cor. of secs. 12 and 13, T. 42 S., R. 15 W., bears N. 0° 20' W., 34.91 chs. dist., heretofore described.</p>
3.80 9.90 35.70	<p>From the cor. of secs. 7, 8, 17, and 18. N. 0° 09' E., bet. secs. 7 and 8. Over rolling desert land, draining S; up small valley.</p> <p>Hard surface road to gravel pit, bears N. 48° E. and S. 48° W.</p> <p>Old highway, bears N. 67° 30' E. and S. 67° 30' W.</p> <p>Point for the 1/4 sec. cor. of sec. 7 only.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 42 S R 14 W 1/4 S 7 1978</p>
39.60	<p>Point selected for the witness cor. to the 1/4 sec. cor. of sec. 8 only.</p>

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

W C
T 42 S R 14 W



1978


40.10 True point for the ¼ sec. cor. of sec. 8 only, at proportionate distance, falls in large wash which drains SE; there is no remaining evidence of the original cor.

75.80 Intersect the S. bdy. of sec. 5.

Point for the closing cor. of secs. 7 and 8, at proportionate distance; there is no remaining evidence of the original cor.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 42 S R 14 W



From the SE cor. of sec. 5.

N. 89° 28' W., along the S. bdy. of sec. 5.

Over broken desert land, draining S.

3.80 Old highway, bears N. 38° E. and S. 38° W.

31.84 Point for the ¼ sec. cor. of sec. 8 only.

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.

T 42 S R 14 W



1978

40.34 Point for the ¼ sec. cor. of sec 5 only, at proportionate distance, based on the irregular boundary method; there is no remaining evidence of the original cor.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS

T 42 S R 14 W

 $\frac{1}{4}$ S 5

1978

Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.

N. 89° 43' W., beginning new measurement.

Over broken desert land.

31.32 The closing cor. of secs. 7 and 8, heretofore described.

40.37 The cor. of secs. 5 and 6 only, monumented with an iron post, 2½ ins. diam., set in concrete, with Washington Co. brass cap mkd.

T 42 S

S 6 | S 5

S 7

R 14 W

1974

An iron stone, 14 x 10 x 6 ins., mkd. for secs. 5 and 6 only was buried alongside the iron post.

S. 89° 44' W., along the S. bdy. of sec. 6.

Over broken desert land, draining S.

20.085 Point for the E 1/16 sec. cor. of secs. 6 and 7.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 42 S R 14 W

E 1/16 $\frac{S 6}{S 7}$

1978

Asc. over steep and rocky NE slope.

40.17 The ¼ sec. cor. of secs. 6 and 7, monumented with an iron post, 2½ ins. diam., set in concrete, with Washington Co. brass cap mkd.

T 42 S

 $\frac{1}{4}$ $\frac{S 6}{S 7}$

R 14 W

1975

A lava stone, 20 x 12 x 6 ins., plainly mkd. ¼, was buried alongside the iron post.

Set a steel fence post alongside the corner.

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS	
38.02	<p>S. 89° 46' W., beginning new measurement. Over Black Ridge. The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., heretofore described.</p>
39.64	<p>From the cor. of secs. 5 and 6. N. 2° 24' W., bet. secs. 5 and 6. Over broken desert land, draining SE. The ¼ sec. cor. of secs. 5 and 6, monumented with an iron post, 2½ ins. diam., set in concrete, with Washington Co. brass cap mkd.</p> <div style="text-align: center;"> <p>T 42 S</p> <p>¼</p> <p> </p> <p>S 6 S 5</p> <p> </p> <p>R 14 W</p> <p>1975</p> </div> <p>A lava stone, 18 x 10 x 6 ins., plainly mkd. ¼, was buried alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1° 26' W., beginning new measurement. Asc. over SE slope;</p> <p>0.92 Fence on the right-of-way line of Interstate 15, bears N. 66° 21' E. and S. 66° 21' W.</p> <p>4.12 Center line of north-bound-line of Interstate 15, bears N. 66° 15' E. and S. 66° 15' W.</p> <p>7.02 Center line of south-bound-lane of Interstate 15, bears N. 66° 15' E. and S. 66° 15' W.</p> <p>10.29 Fence on the right-of-way line of Interstate 15, bears N. 64° 15' E. and S. 64° 15' W.</p> <p>40.36 The cor. of secs. 5 and 6, on the N. bdy. of the Tp., heretofore described.</p>
	<p style="text-align: center;">General Description</p> <p>Township 42 South, Range 14 West is located about 6 miles east of St. George, Utah. The township consists of sandy broken desert land covered with shadscale, with several lava reefs and outcrops. The main water is the Virgin River, which enters the township on the north boundary of sec. 2, flows SW and leaves the township on the west boundary of sec. 19. There are numerous small springs and wells within the township used for agriculture</p>

Dependent Resurvey of the Subdivisional Lines,
T. 42 S., R. 14 W., Salt Lake Meridian, Utah

CHAINS

and culinary use. Interstate 15 enters the township on the west boundary of sec. 6, bears NE and leaves the township on the north boundary of sec. 5. There are numerous other roads within the township leading to farms, homes gravel pits and other developments. The elevation varies from about 2650 ft. to 3500 ft. above sea level.

CERTIFICATE OF SURVEY

~~(XX)~~(We), Craig Sylvester, Gail E. Reynolds and Ferrel D. Reynolds, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 29th day

of March, 1978, ~~(XX)~~(We) have dependently resurveyed the north, and south boundaries, the Second Guide Meridian West along the east boundary, a portion of the west boundary, and the subdivisional lines of Township 42 South, Range 14 West,

of the Salt Lake Meridian, in the State of Utah, which

are represented in the foregoing field notes as having been executed by ~~(XX)~~ (us) and under ~~(XXX)~~ (our) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

<u>January 26, 1981</u> (Date)	<u><i>Craig P. Sylvester</i></u> (Cadastral Surveyor) Supervisory
<u>January 26, 1981</u>	<u><i>Gail E. Reynolds</i></u> (Supervisory Cadastral Surveyor)
<u>January 26, 1981</u> (Date)	<u><i>Ferrel D. Reynolds</i></u> (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Denver, Colorado

The foregoing field notes of the dependent resurvey of the north, and south boundaries, the Second Guide Meridian West along the east boundary, a portion of the west boundary, and the subdivisional lines of Township 42 South, Range 14 West, Salt Lake Meridian, Utah

Craig P. Sylvester, Supervisory Cadastral Surveyor
executed by Gail E. Reynolds, Supervisory Cadastral Surveyor
Ferrel D. Reynolds, Cadastral Surveyor
having been critically examined and found correct, are hereby approved.

MAR 17 1982
(Date) *Faustin B. Padilla*
ACTING (Chief, Cadastral Survey Examination and Approval Staff)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.~~

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
ORIGINAL

R602

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

A PORTION OF THE SUBDIVISIONAL LINES

AND THE

SURVEY OF THE SUBDIVISION OF SECTION 22,

TOWNSHIP 11 NORTH, RANGE 18 WEST

Of the Salt Lake Meridian,

In the State of Utah

EXECUTED BY

Craig P. Sylvester Supervisory Cadastral Surveyor

Under special instructions dated December 18, 1978, approved January 10, 1979,

_____, which provided for the surveys included under ~~U.S. Survey~~/Group
Number 586, and assignment instructions dated April 9, 1979.

Survey commenced April 10, 1979

Survey completed April 23, 1979

INDEX DIAGRAM

Township 11 North, Range 18 West

6	5	4	3	2	1
7	8	9	10 7	11	12
13	14	15 7 8	16 3 6	17	18
19	20	21 5	22 1 3	23	24
29	30	31	32	33	34
35	36	37	38	39	40

Subdivision of Section 22

- Page 9

Township 11 North, Range 18 West, Salt Lake Meridian, Utah

CHAINS

The following field notes are those of a dependent resurvey of a portion of the subdivisional lines, and the survey of the subdivision of section 22, Township 11 North, Range 18 West, Salt Lake Meridian, Utah.

The subdivisional lines of Township 11 North, Range 18 West, were surveyed by Henry Fitzhugh in 1883.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 586, Utah, dated December 18, 1978.

The directions of the lines of this survey were determined by references to true meridians established on line by hour angle observations on Polaris. They were carried forward by sustained angulation being supplemented by numerous other observations on Polaris taken throughout the progress of the survey.

Measurements were determined by electronic means.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the southeast corner of section 22, as scaled from U.S.G.S. Quadrangle "Grouse Creek" is as follows:

Latitude $41^{\circ} 39' 15''$ N. Longitude $113^{\circ} 53' 11''$ W.

The mean magnetic declination is 17° E.

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 11 N., R. 18 W., Salt Lake Meridian, Utah

(Restoring the Survey Executed by
Henry Fitzhugh in 1883)

Beginning at the cor. of secs. 22, 23, 26, and 27, monumented with a black granite stone, 8 x 8 x 4 ins., firmly set 4 ins. in the ground and plainly mkd. 2 grooves on E and S faces.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 11 N R 18 W

S 22	S 23
S 27	S 26

1979

Bury the mkd. stone alongside the iron post.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 11 N., R. 18 W., Salt Lake Meridian, Utah

CHAINS	
	N. 1° 55' W., bet. secs. 22 and 23.
	Over brush covered bench land, draining W.
14.50	Red Butte Creek, small stream, course SW.
17.40	Dirt road, bears NE and SW.
39.20	The ¼ sec. cor. of secs. 22 and 23, monumented with a granite stone, 10 x 8 x 4 ins., firmly set 4 ins. in the ground, dimly mkd. ¼ on W face. This position is also in line with fence lines to N.
	At the corner point
	Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	<p style="text-align: center;">T 11 N R 18 W</p> <div style="text-align: center;"> $\frac{1}{4}$ S 22 S 23 </div> <p style="text-align: center;">1979</p>
	Bury the mkd. stone and set a juniper post alongside the aluminum post.
	N. 0° 54' E., beginning new measurement.
4.80	Low spur, slopes W; continue along W slope.
20.365	Point for the N 1/16 sec. cor. of secs. 22 and 23, determined by fence cor., from which fences bear W and N. This position is accepted as a careful and faithful determination of the position of the cor.
	At the corner point
	Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	<p style="text-align: center;">T 11 N R 18 W N 1/16</p> <div style="text-align: center;"> S 22 S 23 </div> <p style="text-align: center;">1979</p>
	N. 0° 54' E., beginning new measurement.
	Thence along N and S fence.
20.485	The cor. of secs. 14, 15, 22, and 23, determined by fence cor., and a mound of stone. Fences bear N, S and W and is accepted as the best available evidence of the position of the original corner.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 11 N., R. 18 W., Salt Lake Meridian, Utah

CHAINS					
	<p style="text-align: center;">T 11 N R 18 W</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 15</td> <td style="padding: 0 5px;">S 14</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 22</td> <td style="padding: 0 5px;">S 23</td> </tr> </table> <p style="text-align: center;">1979</p>	S 15	S 14	S 22	S 23
S 15	S 14				
S 22	S 23				
38.25	<p>N. 1° 24' W., bet. secs. 14 and 15.</p> <p>Over rolling W. slope, along fence which bears irregularly N.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 14 and 15, monumented with a quartzite stone, 15 x 8 x 4 ins., firmly set 8 ins. in the ground and plainly mkd. $\frac{1}{4}$ on W face.</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 11 N R 18 W</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 15</td> <td style="padding: 0 5px;">S 14</td> </tr> </table> <p style="text-align: center;">1979</p> <p>Bury the mkd. stone and reset a juniper post alongside the aluminum post.</p> <p>Cor. is located on W side of fence.</p> <p style="text-align: center;">_____</p> <p>N. 0° 25' E., beginning new measurement.</p>	S 15	S 14		
S 15	S 14				
40.34	<p>The cor. of secs. 10, 11, 14, and 15, monumented with a quartzite stone, 18 x 8 x 6 ins., mkd. 4 notches on S and 2 notches on E edges, firmly set 8 ins. in the ground alongside a fence cor., from which fences bear E, W, and S</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 11 N R 18 W</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 10</td> <td style="padding: 0 5px;">S 11</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 15</td> <td style="padding: 0 5px;">S 14</td> </tr> </table> <p style="text-align: center;">1979</p> <p>Bury the mkd. stone alongside the aluminum post.</p>	S 10	S 11	S 15	S 14
S 10	S 11				
S 15	S 14				
18.00	<p>From the cor. of secs. 22, 23, 26, and 27.</p> <p>N. 89° 34' W., bet. secs. 22 and 27.</p> <p>Over rolling brush covered land in Grouse Creek Valley.</p> <p>Red Butte Creek, drains SW.</p>				
19.99	<p>Point for the E 1/16 sec. cor. of secs. 22 and 27.</p>				

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 11 N., R. 18 W., Salt Lake Meridian, Utah

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 11 N R 18 W</p> <p style="text-align: center;">E 1/16 $\frac{S 22}{S 27}$</p> <p style="text-align: center;">1979</p> <p>Cor. is located on S side of dirt road which bears W and curves NE. Thence along road.</p>
39.00	Graded gravel road to Grouse Creek, bears N. 4° E. and S. 4° W.; thence along fence, enter farm land.
39.98	<p>The ¼ sec. cor. of secs. 22 and 27, monumented with a granite stone, 14 x 10 x 4 ins., plainly mkd. ¼ on N face, firmly set in a fence cor., from which fences bear E, W, N, and S.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 11 N R 18 W</p> <p style="text-align: center;">¼ $\frac{S 22}{S 27}$</p> <p style="text-align: center;">1979</p> <p>Bury the mkd. stone alongside the iron post.</p> <p style="text-align: center;">_____</p> <p>N. 89° 25' W., beginning new measurement.</p> <p>Thence along E and W fence.</p>
19.945	<p>Point for the W 1/16 sec. cor. of secs. 22 and 27.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 11 N R 18 W</p> <p style="text-align: center;">W 1/16 $\frac{S 22}{S 27}$</p> <p style="text-align: center;">1979</p> <p>Cor. is located in E and W fence line.</p>
32.50	Grouse Creek, flows SW; asc. gentle E slope.
39.89	<p>The cor. of secs. 21, 22, 27, and 28, monumented with a mound of stone, no marks identified, and in a fence cor., from which fences bear E and S and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 11 N., R. 18 W., Salt Lake Meridian, Utah

CHAINS	
	<p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">T 11 N R 18 W</p> <p style="text-align: center;">S 21 S 22 S 28 S 27</p> <p style="text-align: center;">1979</p>
38.21	<p>N. 3° 39' W., bet. secs. 21 and 22.</p> <p>Along gentle E slope of bench, over reseeded area.</p> <p>The ¼ sec. cor. of secs. 21 and 22, monumented with a granite stone, 12 x 8 x 4 ins., plainly mkd. ¼ on W face, firmly set in a small mound of stone.</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">T 11 N R 18 W</p> <p style="text-align: center;">¼ S 21 S 22</p> <p style="text-align: center;">1979</p> <p>Bury the mkd. stone alongside the aluminum post.</p> <p>N. 2° 42' E., beginning new measurement.</p> <p>Along gentle E slope, over reseeded area.</p>
19.96	<p>Point for the N 1/16 sec. cor. of secs. 21 and 22.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 11 N R 18 W N 1/16</p> <p style="text-align: center;">S 21 S 22</p> <p style="text-align: center;">1979</p>
31.50	<p>Dirt road, bears irregularly E and W.</p>
39.92	<p>Point for the cor. of secs. 15, 16, 21, and 22, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 11 N., R. 18 W., Salt Lake Meridian, Utah

CHAINS					
	<p>T 11 N R 18 W</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 16</td> <td style="padding: 0 5px;">S 15</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 21</td> <td style="padding: 0 5px;">S 22</td> </tr> </table> <p>1979</p>	S 16	S 15	S 21	S 22
S 16	S 15				
S 21	S 22				
	<p>From the cor. of secs. 14, 15, 22, and 23.</p> <p>N. 89° 58' W., bet. secs. 15 and 22.</p> <p>Over rolling land; desc. over gentle W slope, along fence line.</p>				
20.00	Point for the E 1/16 sec. cor. of secs. 15 and 22, point not monumented.				
30.50	Grouse Creek, flows S; asc. gentle E slope.				
39.10	Graded gravel road to Grouse Creek, on curve, bears NE and SSE for about 2.00 chs.; thence S.				
40.00	<p>The ¼ sec. cor. of secs. 15 and 22, monumented with a granite stone, 16 x 10 x 4 ins., firmly set 8 ins. in the ground and plainly mkd. ¼ on N face, with a mound of stone and steel fence post S of cor.</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>				
	<p>T 11 N R 18 W</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">¼ S 15</td> <td style="padding: 0 5px;">S 22</td> </tr> </table> <p>1979</p>	¼ S 15	S 22		
¼ S 15	S 22				
	<p>Bury the mkd. stone alongside the aluminum post.</p> <p>S. 88° 07' W., beginning new measurement.</p> <p>Over valley land; asc. gentle E slope.</p>				
3.00	Dirt road, bears NW and SE.				
19.87	<p>Point for the W 1/16 sec. cor. of secs. 15 and 22.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>				
	<p>T 11 N R 18 W</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">W 1/16 S 15</td> <td style="padding: 0 5px;">S 22</td> </tr> </table> <p>1979</p>	W 1/16 S 15	S 22		
W 1/16 S 15	S 22				
39.74	<p>Asc. over gentle E slope.</p> <p>The cor. of secs. 15, 16, 21, and 22.</p>				

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 11 N., R. 18 W., Salt Lake Meridian, Utah

CHAINS

N. 2° 15' W., bet. secs. 15 and 16.

Over rolling brush covered bench land; along gentle E slope.

39.91 The ¼ sec. cor. of secs. 15 and 16, monumented with a quartzite stone, 14 x 8 x 5 ins., firmly set 6 ins. in the ground and plainly mkd. ¼ on W face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 11 N R 18 W

¼
|
S 16 | S 15

1979

Bury the mkd. stone alongside the iron post.

N. 0° 33' E., beginning new measurement.

Along brush covered E slope.

12.30 Dirt road, bears NW and SE; desc. over gentle NE slope.

39.87 The cor. of secs. 9, 10, 15, and 16, monumented with a quartzite stone, 14 x 8 x 4 ins., firmly set 7 ins. in the ground, and plainly mkd. 4 notches on S edge and 3 grooves on E face.

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 11 N R 18 W

S 9 | S 10
S 16 | S 15

1979

Bury the mkd. stone and set squared post, 5 ft. long, alongside the aluminum post.

From the cor. of secs. 10, 11, 14, and 15.

N. 88° 39' W., bet. secs. 10 and 15.

Over rolling land in Grouse Creek Valley.

13.00 Grouse Creek, small stream, flows SE.

21.60 Graded gravel road, bears N and S; asc. over E slope.

26.00 Crest of ascent, bears N and S; thence over brush covered bench.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 11 N., R. 18 W., Salt Lake Meridian, Utah

CHAINS		
38.82	<p>The $\frac{1}{4}$ sec. cor. of secs. 10 and 15, monumented with a quartzite stone, 14 x 8 x 4 ins., firmly set 7 ins. in the ground, and plainly mkd. $\frac{1}{4}$ on N face.</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">T 11 N R 18 W</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S 10}{S 15}$</p> <p style="text-align: center;">1979</p> <p>Bury the mkd. stone alongside the aluminum post.</p> <p style="text-align: center;">_____</p> <p>S. $88^{\circ} 36'$ W., beginning new measurement.</p> <p>Over brush covered bench, draining S.</p>	
20.755	<p>Point for the W $\frac{1}{16}$ sec. cor. of secs. 10 and 15.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 11 N R 18 W</p> <p style="text-align: center;">W $\frac{1}{16}$ $\frac{S 10}{S 15}$</p> <p style="text-align: center;">1979</p> <p>Set 2' x 4' post, 5 ft. long, alongside the iron post.</p>	
41.51	<p>The cor. of secs. 9, 10, 15, and 16.</p>	
	<p>From the cor. of secs. 15, 16, 21, and 22.</p> <p>S. $89^{\circ} 17'$ W., bet. secs. 16 and 21.</p> <p>Over rolling bench land, across reseeded area.</p>	
39.91	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 21, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">T 11 N R 18 W</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S 16}{S 21}$</p> <p style="text-align: center;">1979</p>	
59.00	<p>Dirt road, bears WNW and ESE.</p>	

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 11 N., R. 18 W., Salt Lake Meridian, Utah

CHAINS										
79.82	<p>The cor. of secs. 16, 17, 20, and 21, monumented with a granite stone, 14 x 10 x 8 ins., plainly mkd. 3 grooves on S face, firmly set in a fence cor., from which fences bear E and N.</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 11 N R 18 W</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 17</td> <td style="padding: 0 5px;">S 16</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 20</td> <td style="padding: 0 5px;">S 21</td> </tr> </table> <p style="text-align: center;">1979</p> <p>Bury the mkd. stone alongside the aluminum post.</p>	S 17	S 16	S 20	S 21					
S 17	S 16									
S 20	S 21									
<p>Subdivision of Section 22, T. 11 N., R. 18 W., Salt Lake Meridian, Utah</p>										
38.72	<p>From the ¼ sec. cor. of secs. 22 and 27.</p> <p>N. 0° 31' W., on the N and S center line of sec. 22.</p> <p>Point for the center ¼ sec. cor. of sec. 22, at intersection with the E and W center line.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 11 N R 18 W</p> <p style="text-align: center;">C ¼ S 22</p> <p style="text-align: center;">1979</p>									
51.50	<p>Grouse Creek, flows SW.</p>									
59.225	<p>Point for the center north 1/16 sec. cor. of sec. 22.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 11 N R 18 W</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">C</td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">C</td> </tr> <tr> <td style="padding: 0 5px;">N 1/16</td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">S 22</td> </tr> <tr> <td style="padding: 0 5px;"></td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">C</td> </tr> </table> <p style="text-align: center;">1979</p> <p>Cor. is located on N side of driveway and in old E and W fence.</p>	C		C	N 1/16		S 22			C
C		C								
N 1/16		S 22								
		C								
61.50	<p>Dirt road, bears E and W.</p>									
70.00	<p>Graded gravel road, bears S. 13° E. and curves N; thence along road.</p>									
77.00	<p>Same graded gravel road, bears S, NW and NE.</p>									

Subdivision of Section 22,
T. 11 N., R. 18 W., Salt Lake Meridian, Utah

CHAINS	
79.73	<p>The $\frac{1}{4}$ sec. cor. of secs. 15 and 22.</p> <hr/> <p>From the $\frac{1}{4}$ sec. cor. of secs. 22 and 23. S. $89^{\circ} 46'$ W., on the E and W center line of sec. 22.</p>
19.50	<p>Point for the center east $\frac{1}{16}$ sec. cor. of sec. 22.</p> <p>Set an aluminum post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">T 11 N R 18 W E $\frac{1}{16}$ C ————— C S 22 1979</p>
33.00	Graded gravel road, bears NNW and SSE.
39.00	The center $\frac{1}{4}$ sec. cor. of sec. 22.
52.50	Grouse Creek, flows SW.
59.985	<p>Point for the center west $\frac{1}{16}$ sec. cor. of sec. 22.</p> <p>Set an aluminum post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">T 11 N R 18 W W $\frac{1}{16}$ C ————— C S 22 1979</p>
80.97	<p>The $\frac{1}{4}$ sec. cor. of secs. 21 and 22.</p> <hr/> <p>From the center east $\frac{1}{16}$ sec. cor. of sec. 22. N. $0^{\circ} 11'$ E., on the N and S center line of the NE $\frac{1}{4}$ of sec. 22.</p>
20.435	<p>Point for the north east $\frac{1}{16}$ sec. cor. of sec. 22, at intersection with the E and W center line of the NE $\frac{1}{4}$.</p> <p>Set an aluminum post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 11 N R 18 W NE $\frac{1}{16}$ S 22 1979</p> <p>Set a juniper post alongside the aluminum post. Cor. is located 3 lks. S of fence, bearing E and W.</p>
40.93	Point for the E $\frac{1}{16}$ sec. cor. of secs. 15 and 22, not monumented.

Subdivision of Section 22,
T. 11 N., R. 18 W., Salt Lake Meridian, Utah

CHAINS	
19.75	<p>From the N 1/16 sec. cor. of secs. 22 and 23. S. 89° 59' W., on the E and W center line of the NE$\frac{1}{4}$ of sec. 22, along old fence line.</p> <p>The north east 1/16 sec. cor. of sec. 22.</p> <p>Grouse Creek, flows SW.</p> <p>Graded gravel road, bears N 13° W. and S. 13° E.</p> <p>The center north 1/16 sec. cor. of sec. 22.</p>
0.80	<p>From the E 1/16 sec. cor. of secs. 22 and 27. N. 1° 13' W., on the N and S center line of the SE$\frac{1}{4}$ of sec. 22.</p> <p>Dirt road, bears NE and W.</p> <p>The center east 1/16 sec. cor. of sec. 22.</p>
20.50	<p>From the W 1/16 sec. cor. of secs. 22 and 27. N. 2° 05' W., on the N and S center line of the SW$\frac{1}{4}$ of sec. 22.</p> <p>Grouse Creek, flows SW.</p> <p>The center west 1/16 sec. cor. of sec. 22.</p>
20.725	<p>From the center west 1/16 sec. cor. of sec. 22. N. 1° 05' E., on the N and S center line of the NW$\frac{1}{4}$ of sec. 22.</p> <p>Point for the north west 1/16 sec. cor. of sec. 22, determined at fence corner from which fences bear E and S and is accepted as a careful and faithful determination of the position of the corner.</p> <p>Set an aluminum post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">T 11 N R 18 W NW 1/16 S 22 1979</p> <p>N. 1° 05' E., beginning new measurement.</p> <p>Dirt road, bears E and W.</p> <p>The W 1/16 sec. cor. of secs. 15 and 22.</p>
	<p>From the center north 1/16 sec. cor. of sec. 22. N. 89° 37' W., on the E and W center line of the NW$\frac{1}{4}$ of sec. 22, using fence line and north side of corrals and farm yard as alignment, thence along old fence line.</p>

Subdivision of Section 22,
T. 11 N., R. 18 W., Salt Lake Meridian, Utah

CHAINS			
20.41	The north west 1/16 sec. cor. of sec. 22.		
	S. 87° 34' W., beginning new measurement.		
20.45	The N 1/16 sec. cor. of secs. 21 and 22.		
General Description			
<p>Sections 15 and 22, T. 11 N., R. 18 W., consist of pastures and small farms in the bottom of Grouse Creek Valley with brush covered bench land on the east and west sides. A graded gravel road bears N and S irregularly through the sections. Red Butte Creek flows through the SE portion of sec. 22. There are several wells and ponds in the valley bottom. The only habitation is a farm home in the NW¼ of sec. 22. Sections 15 and 22 are located about 3 miles south of the town of Grouse Creek, Utah.</p>			

CERTIFICATE OF SURVEY

(I) ~~WEX~~ Craig P. Sylvester, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 18th day of December, 19 78, (I) ~~WEX~~ have dependently resurveyed a portion of the subdivisional lines and surveyed the subdivision of section 22, Township 11 North, Range 18 West

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), ~~WEX~~ and under (my) ~~WEX~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

May 22, 1981
(Date)

Craig P. Sylvester
(Cadastral Surveyor)
Supervisory

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines and the survey of the subdivision of section 22, Township 11 North, Range 18 West, Salt Lake Meridian, Utah

executed by Craig P. Sylvester, Supervisory Cadastral Surveyor having been critically examined and found correct, are hereby approved.

MAR 26 1982
(Date)

Janis D. Bell
ACTING (Chief, Cadastral Survey Examination and Approval Staff)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

(Date)

(Chief, Cadastral Survey Examination and Approval Staff)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

R602

288

ORIGINAL
FIELD NOTES

OF THE

RETRACEMENT OF A PORTION OF

THE COLORADO-UTAH BOUNDARY

AND

A PORTION OF THE SUBDIVISIONAL LINES

WITH THE

SUBDIVISION OF SECTIONS 11 AND 14

TOWNSHIP 3 SOUTH, RANGE 25 EAST

Of the Salt Lake Meridian,
In the State of Utah

EXECUTED BY

Douglas A. Cody / Supervisory
Cadastral Surveyor

Under special instructions dated May 21, 1970, approved May 26, 1970,

_____, which provided for the surveys included under U.S. Survey/Group
Number 528, and assignment instructions dated May 21, 1970.

Survey commenced June 22, 1970

Survey completed July 20, 1970

INDEX DIAGRAM

Township 3 South, Range 25 East

6	5	4	3	2	1	MP 249
				5	2	
					3	
7	8	9	10	11	7	MP 248
					12	
18	17	16	15	14	8	
	7	6	5	4	13	
19	20	21	22	23	24	
30	29	28	27	26	25	
31	32	33	34	35	36	

Township 3 South, Range 25 East, Salt Lake Meridian, Utah

CHAINS

The following field notes are those of the retracement of a portion of the Colorado-Utah State boundary, and a portion of the subdivisional lines, with the subdivision of sections 11 and 14, Township 3 South, Range 25 East, Salt Lake Meridian, Utah.

History of prior surveys is as follows:

<u>Lines Surveyed</u>	<u>By Whom</u>		<u>Date</u>
Colorado-Utah State Line (E. bdy.)	R. J. Reeves	Survey	1879
	Edgar F. Harmston	Resurvey	1903
	A. Parker Warner	Resurvey	1922
Bdy. Dinosaur Natl. Monument	J. C. Clark and Elliot Bird	Survey	1939-1942
S. bdy.	Edgar F. Harmston	Survey	1903
	A. Parker Warner	Survey & Resurvey	1922
W. bdy. (Ashley Guide Meridian)	A. D. Ferron	Survey	1878
	Edgar F. Harmston	Resurvey	1900
N. bdy.	Edgar F. Harmston	Survey	1903
Subdivisional Lines	Edgar F. Harmston	Survey	1903
	A. Parker Warner	Survey	1922
	J. C. Clark and Elliot Bird	Resurvey	1939-1942
Meander Lines	Edgar F. Harmston	Survey	1903

These surveys were executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and Special Instructions dated May 21, 1970.

The directions of the lines of this survey were determined by altitude observations on the sun. The lines were carried forward by sustained angulation being supplemented by other altitude observations on the sun taken throughout the progress of the survey.

All original corners were found and used in this resurvey; where necessary, these points were rehabilitated.

The geographic position of the 1/4 section corner of sections 14 and 23, as scaled from U. S. Geological Survey, "Jones Hole, Utah-Colorado", Quadrangle Map, 1955, 7 1/2' series, is as follows:

Latitude: 40° 33.1' N.
Longitude: 109° 04.7' W.

The mean magnetic declination is 15° E.

Retracement of a Portion of
the Colorado-Utah State Boundary
From Mile Post 248 to Mile Post 249
Township 3 South, Range 25 East
Salt Lake Meridian, Utah

CHAINS

Retracement of a Portion of
the Colorado-Utah State Boundary
From Mile Post 248 to Mile Post 249
Township 3 South, Range 25 East
Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
A. Parker Warner, Cadstral Engineer,
in 1922

Beginning at the witness corner for Mile Post 248, monu-
mented with an iron post, 3 ins. diam., firmly set,
projecting 2 ft. above ground, in a mound of stone, 3 ft.
base, 2 ft. high, with brass cap mkd. as described in the
official record of the 1922 resurvey.

N. 1°21' E., along the Colorado-Utah State Line.

Desc. steep, rocky N. slope, through scattered pinon and
juniper.

- 2.08 True point for Mile Post 248 at proportionate dist., falls
on steep rocky N slope.
- 4.53 The original witness cor. to the closing cor. of secs. 1
and 12, T. 3 S., R. 25 E., S.L.M., Utah bears east 0.055
chs. dist., hereinafter described.
- 5.08 The witness cor. to the closing cor. of secs. 2 and 11,
T. 7 N., R. 104 W., of the 6th Prin. Mer., Colo., bears
east, 6.39 chs. dist., monumented with an iron post,
2 ins. diam., firmly set, projecting 30 ins. above the
ground, in a mound of stone, 3 ft. base, 2 ft. high, with
brass cap mkd. as described in the official record of the
1922 resurvey.
- 6.00 Drain, course W., ascend vertical rocky ledges.
- 6.66 True point for the closing corner of secs. 1 and 12,
T. 3 S., R. 25 E., of the Salt Lake Meridian, Utah,
hereinafter described.
- 82.14 Mile Post, 249, monumented with an iron post, 3 ins.
diam., firmly set, projecting 12 ins. above the ground,
with brass cap mkd. as described in the official record
of the 1922 resurvey.
- from which original bearing trees
- A juniper, 8 ins. diam., bears S. 2° 30' E., 13 lks.
dist., mkd. 249M COLO BT.
- A juniper, 15 ins. diam., bears S. 42° 45' W., 27
lks. dist., mkd. 249M UTAH BT.
- A juniper, 8 ins. diam., bears N. 15° 30' W.,
28 lks. dist., mkd. 249M UTAH BT.
- Cor. situated on steep N. slope, 25 lks. S. of drain,
course W.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 3 South, Range 25 East
Salt Lake Meridian, Utah

CHAINS

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 3 South, Range 25 East
Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by E.F. Harmston
in 1903 and the Dependent Resurvey Executed by
J. C. Clark and Elliot Bird in 1939

From the corner of secs. 1, 2, 11 and 12, monumented
with an iron post, 2 ins. diam., firmly set, projecting
36 ins. above the ground, in a mound of stone, 6 ft.
base to top of brass cap, mkd. as described in the
official record of the 1939 resurvey.

from which the 1939 bearing trees

A pinon, 6 ins. diam., bears N. 29°45' E.,
26 lks. dist., mkd. BT.

A juniper, 10 ins. diam., bears S. 14°45' E.,
30 lks. dist., mkd. BT. (Record, pinon pine)

A pinon, 12 ins. diam., bears S. 14°30' W., 30
lks. dist., mkd. DNM T3S R25E S11 BT.

A pinon, 10 ins. diam., bears N. 46°15' W., 53 lks.
dist., mkd. T3S R25E S2 BT.

N. 88°58' E., bet. secs. 1 and 12.

Over mountainous land, through juniper and pinon timber.

39.97 The 1/4 sec. cor. of secs. 1 and 12, monumented with an
iron post, 1 in. diam., firmly set, projecting 12 ins.
above the ground, with brass cap mkd. as described in the
official record of the 1939 resurvey.

from which the original bearing trees

A pinon, 12 ins. diam., bears N. 54° E., 12 lks.
dist., mkd. 1/4 S1 BT.

A pinon, 11 ins. diam., bears S. 39°30' W., 27 lks.
dist., mkd. DNM 1/4 S12 BT.

Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of
cor.

S. 89°56' E., beginning new measurement.

Descending steep E slope.

26.00 Jones Hole Creek, course S., end of descent.

27.00 Trail road, bears N and S; ascent W slope.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 3 South, Range 25 East
Salt Lake Meridian, Utah

CHAINS		
49.42	<p>True point for the closing corner of secs. 1 and 12, at the intersection with the Colorado-Utah State boundary, and at record dist. northing from its witness cor., falls on steep W. slope, impractical for monumentation.</p> <p>From this point the original witness cor. to the closing corner of secs. 1 and 12, bears S. 0°11' E., 2.13 chs. dist., monumented with an iron post, 2 ins. diam., projecting 24 ins. above the ground, firmly set in a mound of stone, 3 ft. base, 2 ft. high, with brass cap mkd. as described in the official record of the 1939 resurvey.</p> <p>from which the original bearing trees</p> <p style="padding-left: 40px;">A pinon, 10 ins. diam., bears S. 69°45' W., 61 lks. dist., mkd. WC T3S R25E S12 CC DNM BT.</p> <p style="padding-left: 40px;">A juniper, 5 ins. diam., bears N. 52°15' W., 35 lks. dist., mkd. BT.</p>	
	<p>From the 1/4 sec. cor. of secs. 14 and 23, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above the ground, in a mound of stone, 2 ft. base to top of brass cap, mkd. as described in the official record of the 1939 resurvey.</p> <p>from which the original bearing trees</p> <p style="padding-left: 40px;">A juniper, 10 ins. diam., bears S. 35°10' W., 32 lks. dist., mkd. DNM S23 BT.</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears N. 2°20' W., 24 lks. dist., mkd. 1/4 S14 BT.</p> <p>Corner is located on steep NW slope, 20 feet above bottom of draw, course SW.</p> <p>West, between secs. 14 and 23.</p> <p>Over rough mountainous land, through dense juniper.</p>	
0.93	<p>Draw, drains SW., ascend W slope.</p>	
39.64	<p>The cor. of secs. 14, 15, 22, and 23, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above the ground, in a mound of stone, 3 ft. base, 1½ ft. high, W of the corner, with brass cap mkd. as described in the official record of the 1939 resurvey.</p> <p>from which the original bearing trees</p> <p style="padding-left: 40px;">A juniper, 12 ins. diam., bears N. 32°20' E., 37 lks. dist., mkd. T3S R25E S14 BT.</p> <p style="padding-left: 40px;">A juniper, 16 ins. diam., bears S. 68° E., 49 lks. dist., mkd. DNM T3S R25E S23 BT.</p> <p style="padding-left: 40px;">A juniper, 10 ins. diam., bears S. 72°53' W., 35 lks. dist., mkd. DNM T3S R25E S22 BT.</p> <p style="padding-left: 40px;">A juniper, 9 ins. diam., bears N. 21°25' W., 72 lks. dist., mkd. T3S R25E S15 BT.</p>	

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 3 South, Range 25 East
Salt Lake Meridian, Utah

CHAINS		
	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>S. 88°59' W., bet. secs. 2 and 11.</p> <p>Over rough mountainous land, through dense pinon and juniper.</p> <p>4.95 Draw, drains S., ascend steep slope.</p> <p>27.95 Bottom of canyon, 300 ft. deep, drains S.</p> <p>39.25 Draw, drains S.</p> <p>39.95 The 1/4 sec. cor. of secs. 2 and 11, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above the ground, in a mound of stone, 4 ft. base to top of brass cap, mkd. as described in the official record of the 1939 resurvey.</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A pinon, 10 ins. diam., bears S. 59°15' W., 54 lks. dist., mkd. 1/4 S11 BT.</p> <p style="padding-left: 40px;">A pinon, 12 ins. diam., bears N. 10° W., 72 lks. dist., mkd. 1/4 S2 BT.</p>	
	<p>From the cor. of secs. 14, 15, 22, and 23.</p> <p>S. 89°50' W., between secs. 15 and 22.</p> <p>Descend E. slope, through sage and juniper.</p> <p>28.59 Sage Creek, 2 lks. wide, 3 ins. deep, flows S., in wash, 40 lks. wide, 10 feet deep.</p> <p>39.75 The 1/4 sec. cor. of secs. 15 and 22, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above the ground, a deteriorated mound of stone N., with brass cap mkd. as described in the official record of the 1939 resurvey.</p> <p>from which the 1939 bearing tree</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears N. 53°02' E., 326 lks. dist., mkd. 1/4 S15 BT.</p> <p>Rebuild the mound of stone, 3 ft. base, 2 ft. high, N of the corner.</p> <p style="text-align: center;">_____</p> <p>S. 89°57' W., beginning new measurement.</p> <p>39.65 The cor. of secs. 15, 16, 21, and 22, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the 1939 resurvey.</p> <p>from which the original bearing trees</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears N. 77°45' E., 99 lks. dist., mkd. T3S R25E S15 BT.</p>	

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 3 South, Range 25 East
Salt Lake Meridian, Utah

CHAINS		
	<p>A juniper, 24 ins. diam., bears S. 65°15' W., 84 lks. dist., mkd. T3S R25E S21 BT DNM.</p> <p>A juniper, 12 ins. diam., bears N. 76°21' W., 170 lks. dist., mkd. T3S R25E S16 BT.</p>	
	<p>S. 89°57' W., bet. secs. 16 and 21.</p> <p>Over rolling land, through scattered sagebrush and juniper.</p> <p>8.13 Jones Hole Trail, 10 lks. wide, bears NE and SW.</p> <p>40.02 The 1/4 sec. cor. of secs. 16 and 21, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the official record of the 1939 resurvey.</p> <p>from which an original bearing tree</p> <p>A juniper, 12 ins. diam., bears S. 2° W., 12 lks. dist., mkd. DNM 1/4 S21 BT.</p> <p>a new bearing tree</p> <p>A juniper, 6 ins. diam., bears N. 27°30' E., 48 lks. dist., mkd. 1/4 S16 BT.</p> <p>S. 89°56' W., beginning new measurement.</p> <p>Over rough, mountainous land, through dense pinon and juniper.</p>	
2.36	Ascend vertical, sandstone cliff.	
26.80	Red Wash Canyon, 80 ft. deep, drains S.	
39.62	<p>The cor. of secs. 16, 17, 20, and 21, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above the ground, in a mound of stone, 3 ft. base to top of brass cap, mkd. as described in the official record of the 1939 resurvey.</p> <p>from which the original bearing trees</p> <p>A pinon, 8 ins. diam., bears N. 25°15' E., 69 lks. dist., mkd. T3S R25E S16 BT.</p> <p>A pinon, 6 ins. diam., bears S. 24°45' E., 9 lks. dist., mkd. DNM BT.</p> <p>A juniper, 15 ins. diam., bears S. 24°30' W., 29 lks. dist., mkd. DNM T3S R25E S20 BT.</p> <p>A pinon, 8 ins. diam., bears N. 63°45' W., 46 lks. dist., mkd. T3S R25E S17 BT.</p>	

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 3 South, Range 25 East
Salt Lake Meridian, Utah

CHAINS	
	S. 89°47' W., bet. secs. 17 and 20.
	Over mountainous land, through dense pinon and juniper.
39.68	The 1/4 sec. cor. of secs. 17 and 20, monumented with an iron post, 1 ins. diam., firmly set, projecting 5 ins. above the ground, in a mound of stone, 3 ft. base to top of brass cap, mkd. as described in the official record of the 1939 resurvey.
	from which the original bearing trees
	A juniper, 10 ins. diam., bears S. 14°30' E., 20 lks. dist., mkd. DNM 1/4 S20 BT.
	A juniper, 5 ins. diam., bears N. 46°08' W., 32 lks. dist., mkd. 1/4 S17 BT.
	N. 89°57' W., beginning new measurement.
	Descending into rugged gulch.
0.82	Rugged gulch, 20 lks. wide, drains SSE., ascend.
36.02	Bottom of East Fork Limekiln Canyon, course S., ascend.
40.03	The cor. of secs. 17, 18, 19, and 20, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above the ground, in a mound of stone, 2 ft. base to top of brass cap, mkd. as described in the official record of the 1939 resurvey.
	from which the original bearing trees
	A juniper, 8 ins. diam., bears N. 56°15' E., 96 lks. dist., mkd. T3S R25E S17 BT.
	A juniper, 5 ins. diam., bears S. 47°54' E., 169 lks. dist., mkd. DNM T3S R25E S20 BT.
	A juniper, 8 ins. diam., bears N. 28°05' W., 37 lks. dist., mkd. T3S R25E S18 BT.
	a new bearing tree
	A juniper, 8 ins. diam., bears S. 49°15' W., 160 lks. dist., mkd. T3S R25E S19 BT.
	Corner is located on steep E slope.
	Subdivision of Section 11 Township 3 South, Range 25 East Salt Lake Meridian, Utah
	From the 1/4 sec. cor. of secs. 11 and 14, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above the ground, in a mound of stone, 2 ft. base to top of brass cap, mkd. as described in the official record of the 1939 resurvey.

Subdivision of Section 11
Township 3 South, Range 25 East
Salt Lake Meridian, Utah

CHAINS		
	<p>from which the 1939 bearing trees</p> <p>A pine, 6 ins. diam., bears S. 9°30' E., 23 lks. dist., mkd. 1/4 S14 DNM BT.</p> <p>A pine, 5 ins. diam., bears N. 53°15' W., 18 lks. dist., mkd. 1/4 S11 BT.</p> <p>N. 0°04' E., along the N and S center line of sec. 11.</p> <p>Descend precipitous cliff.</p> <p>6.30 Bottom of Big Draw Canyon, 10 lks. wide, drains E., ascent N canyon wall.</p> <p>31.49 Selected point for a witness point on the N and S center line of sec. 11.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base to top of brass cap, mkd.</p> <p style="text-align: center;">W P C S 11 C 1970</p> <p>31.60 S. rim of labyrinths, descend.</p> <p>40.00 Ely Creek, dry, drains E., in bottom of sandstone canyon, thence ascend along bottom of canyon.</p> <p>80.48 The 1/4 sec. cor. of secs. 2 and 11.</p>	
<p>Subdivision of Section 14 Township 3 South, Range 25 East Salt Lake Meridian, Utah</p>		
	<p>From the 1/4 sec. cor. of secs. 14 and 23.</p> <p>N. 0°03' E., along the N. and S. center line of sec. 14.</p> <p>Descend through widely scattered juniper and pinon.</p> <p>0.75 Draw, course W., ascend steep S slope.</p> <p>16.80 Spur of Squaw Hill, slopes SW., enter dense juniper and pinon.</p> <p>41.58 Selected point for a witness point on the N and S center line of sec. 14.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of brass cap, mkd.</p> <p style="text-align: center;">W P C S 14 C 1970</p>	

Subdivision of Section 14
Township 3 South, Range 25 East
Salt Lake Meridian, Utah

CHAINS	
53.90	Jones Hole Trail, bears E and W.
78.00	Rim of Big Draw Canyon, descend precipitous cliff.
80.09	The 1/4 sec. cor. of secs. 11 and 14.
<p>General Description</p> <p>The land encompassed in this survey is in the vicinity of the Jones Hole Ranger Station, and near the Colorado-Utah State Line. The average elevation of the survey area is 5,800 feet above sea level; however, there are many canyons and draws, crossed by the resurveyed lines.</p> <p>The only development in the area is the Jones Hole Ranger Station and Fish Hatchery in section 12. The main use of the area is livestock grazing.</p> <p>The area is drained by small creeks, which flow into the Green River to the South.</p> <p>The general terrain of the area is rough, broken terrain, with many rocky ledges and vertical rock faces. The soil varies from sandy loam to open rock surfaces. The vegetation consists of sparse scattered sagebrush, juniper and pinon.</p> <p>The average of a number of readings along the lines resurveyed gives a mean magnetic declination of 15°00' E., with a range of 1°00' in local attraction.</p>	

CERTIFICATE OF SURVEY

(I) ~~(We)~~, Douglas A. Cody, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 21st day of May, 1970, (I) ~~(We)~~ have retraced a portion of the Colorado-Utah State boundary and a portion of the subdivisional lines, and subdivided sections 11 and 14, Township 3 South, Range 25 East,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

February 19, 1981
(Date)

Douglas A. Cody
Supervisory (Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
~~Washington, D.C.~~
~~Denver, Colorado~~

The foregoing field notes of the retracement of a portion of the Colorado-Utah State boundary and a portion of the subdivisional lines, with the subdivision of sections 11 and 14, Township 3 South, Range 25 East, Salt Lake Meridian, Utah

executed by Douglas A. Cody, Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

MAR 30 1982
(Date)

Mary S. Smith
Chief, Department of Cadastral Surveys

Acting Chief, Cadastral Survey Examination and Approval Staff

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

(Date)

(Chief, Department of Cadastral Surveys)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL
FIELD NOTES
OF THE

DEPENDENT RESURVEY OF
 A PORTION OF THE NORTH BOUNDARY
 OF T. 5 S., R. 23 E.,
 AND A
 DEPENDENT RESURVEY OF
 A PORTION OF THE SUBDIVISIONAL LINES,
 THE SURVEY OF
 A PORTION OF THE SUBDIVISIONAL LINES
 AND
 THE SUBDIVISION OF CERTAIN SECTIONS
 TOWNSHIP 4 SOUTH, RANGE 23 EAST

Of the Salt Lake Meridian,
 In the State of Utah

EXECUTED BY

Douglas A. Cody Cadastral Surveyor

Gail E. Reynolds Supervisory Cadastral Surveyor

Under special instructions dated May 21, 1970, approved May 26, 1970,

_____, which provided for the surveys included under U.S. Survey/Group
 Number 528, and assignment instructions dated May 21,, 1970
 and April 20, 1982

Survey commenced May 25, 1970

Survey completed April 23, 1982

INDEX DIAGRAM

Township 4 South, Range 23 East

6	5	4 4	3	2	1
7	8	9 6	10	11	12
18	17	16 5	15	14	13
19	20	21 3	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

2 1

- Subdivision of Sec. 9 - Page 7
- Subdivision of Sec. 16 - Page 7
- Subdivision of Sec. 21 - Page 8
- Subdivision of Sec. 28 - Page 8
- Subdivision of Sec. 33 - Page 9

Township 4 South, Range 23 East, Salt Lake Meridian, Utah

CHAINS

The following field notes are those of the dependent resurvey of a portion of the north boundary of T. 5 S., R. 23 E., and a dependent resurvey of a portion of the subdivisional lines, the survey of a portion of the subdivisional lines and the subdivision of certain sections in T. 4 S., R. 23 E., SLM, Utah.

The south boundary was surveyed by A. D. Ferron, in 1878. Jessen and Harmston resurveyed the south boundary in 1900, and surveyed a portion of the subdivisional lines and meanders of Green River in 1906. Portions of the subdivisional lines were resurveyed and portions surveyed by J. C. Clark and Elliot Bird, from 1939 to 1942. The south boundary was resurveyed in 1949 by Elliot Bird, Cadastral Engineer.

These surveys were executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated May 21, 1970.

The directions of the lines of this survey were determined by altitude observations on the sun. The lines were carried forward by sustained angulation being supplemented by other altitude observations on the sun taken throughout the progress of the survey.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the North $\frac{1}{4}$ sec. cor. of sec. 3, T. 5 S., R. 23 E., as scaled from U.S.G.S. Quadrangle map "Dinosaur Quarry, Utah" 1965, 7 $\frac{1}{2}$ ' series, is as follows:

Latitude 40°25.3' N. Longitude 109°19.0' W.

The mean magnetic declination is 14 $\frac{1}{2}$ ° E.

Dependent Resurvey of a Portion
of the North Boundary,
T. 5 S., R. 23 E., Salt Lake Meridian, Utah

(Reestablishment of the Survey Executed by
A. D. Ferron in 1878, and the Resurvey Executed by
Jessen and Harmston in 1900, and the
Resurvey Executed by Elliot Bird in 1949)

Beginning at the $\frac{1}{4}$ sec. cor. of sec. 3, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. as described in the official record of the 1949 resurvey.

S. 89° 23' W., along the N. bdy. of sec. 3.

Over rolling bench through scattered sage.

37.23

Point selected for the witness cor. to the meander cor. of sec. 3 only, the meander cor. of sec. 34 only, and also for the cor. of secs. 3 and 4.

Dependent Resurvey of a Portion of the North Boundary,
T. 5 S., R. 23 E., Salt Lake Meridian, Utah

CHAINS								
	<p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">W C T 4 S R 23 E</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 2px;">W</td> <td style="padding: 2px;">S 34</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;">M</td> <td style="padding: 2px;">S 4 S 3</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;">C</td> <td style="padding: 2px;"> </td> </tr> </table> <p style="text-align: center;">T 5 S 1982</p>	W	S 34	M	S 4 S 3	C		
W	S 34							
M	S 4 S 3							
C								
39.67	Left bank of the Green River; point for the meander cor. of sec. 3 only, at proportionate distance; there is no remaining evidence of the original cor., falls on unstable river bank.							
40.10	Point for the cor. of secs. 3 and 4, and the meander cor. of sec. 34 only, on the left bank of the Green River, at proportionate distance, falls in river.							
	<p>S. 89° 23' W., along the N. bdy. of sec. 4.</p> <p>Across the Green River.</p>							
2.44	Point for the closing cor. of secs. 33 and 34, T. 4 S., R. 23 E., at proportionate distance, falls in Green River.							
7.90	Present right bank of the Green River, bears N and S.							
8.27	Point for the meander cor. of secs. 4 and 33, on the right bank of the Green river, at proportionate distance. Point not monumented.							
40.54	<p>The ¼ sec. cor. of sec. 4, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, and in a mound of stone, 3 ft. base, to top of brass cap, mkd. as described in the official record of the 1949 survey.</p> <p style="text-align: center;">_____</p> <p>S. 89°40' W., beginning new measurement.</p>							
0.70	Center line of Utah State Highway 149, bears N. 22°15' E. and S. 22°15' W.							
2.50	<p>Point for the ¼ sec. cor. of sec. 33, T. 4 S., R. 23 E., at mid point between closing cors.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 4 S R 23 E</p> <p style="text-align: center;">¼ S 33</p> <p style="text-align: center;">1970</p>							
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.							
3.80	Power line, bears S. 25° E. and N. 25° W.							
13.35	Buried gas pipeline, bears S. 24° E. and N. 24° W.							

Dependent Resurvey of a Portion of the North Boundary,
T. 5 S., R. 23 E., Salt Lake Meridian, Utah

CHAINS	
15.85	Trail road, bears N. and S.
22.18	Fall, 5 lks. S. of an axle, 2 ins. diam., firmly set, projecting 3 ins. above the ground.
22.40	Trail road, 20 lks. wide, bears N. and S.
40.64	<p>The cor. of secs. 4 and 5, monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above the ground, and in a mound of stone, 2½ ft. base, 1 ft. high, N. of the cor., with brass cap mkd. as described in the official record of the 1949 resurvey.</p> <p>From this cor., the closing cor. of secs. 32 and 33, T. 4 S., R. 23 E., bears S. 88°54' W., 2.46 chs. dist., monumented with an iron post, 2 ins. diam., firmly set, projecting 16 ins. above the ground, in a mound of stone, 2½ ft. base, to top of brass cap, mkd. as described in the official record of the 1949 survey.</p>
<p>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 4 S., R. 23 E., Salt Lake Meridian, Utah</p>	
<p>(Reestablishment of the Survey Executed Jessen and Harmston in 1906)</p>	
<p>From the cor. of secs. 21, 22, 27, and 28, monumented with a cross (+), on the face of a sandstone butte, mkd. with 3 grooves to the E. and 2 grooves to the S. of cross.</p> <p>from which the original bearing trees</p> <p>A juniper, 12 ins. diam., bears S. 20° E., 49 lks. dist., mkd. T4S R23E S27 BT.</p> <p>A juniper, 6 ins. diam., bears S. 37°30' W., 65 lks. dist., mkd. T4S R23E S28 BT.</p> <p>S. 89°59' W., bet. secs. 21 and 28.</p>	
39.20	Top of sandstone wall, descend.
39.75	Enter wash, with sandstone floor.
39.83	<p>Point for the ¼ sec. cor. of sec. 21, at 40 chs. Easting from the cor. of secs. 20, 21, 28, and 29.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 4 S R 23 E</p> <p style="text-align: center;"><u>¼ S 21</u></p> <p style="text-align: center;">1970</p>
<p>from which</p> <p>A juniper, 12 ins. diam., bears N. 43° E., 70 lks. dist., mkd. ¼ S21 BT.</p> <p>A juniper, 8 ins. diam., bears N. 21½° W., 56 lks. dist., mkd. ¼ S21 BT.</p>	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 4 S., R. 23 E., Salt Lake Meridian, Utah

CHAINS

40.39

The $\frac{1}{4}$ sec. cor. of sec. 28, determined by record bearing and distance from the original bearing trees

A juniper, 12 ins. diam., bears N. 86° E., 11 lks. dist., mkd. $\frac{1}{4}$ S21 BT.

A juniper, 6 ins. diam., bears S. $44^{\circ}45'$ E., 82 lks. dist., mkd. $\frac{1}{4}$ S28 BT.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.

$\frac{1}{4}$ S 28

T 4 S R 23 E

1970

S. $88^{\circ}14'$ W., beginning new measurement.

Over sandstone bottom of wash.

1.00

Ascend vertical sandstone wall, enter scattered juniper and sage.

39.46

The cor. of secs. 20, 21, 28, and 29, monumented with an iron post, 2 ins. diam., firmly set, projecting 5 ins. above the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor., with brass cap mkd. as described in the official record of the 1939 resurvey.

from which the original bearing trees

A juniper, 10 ins. diam., bears N. $25^{\circ}37'$ E., 42 lks. dist., mkd. T4S R23E S21 BT.

A juniper, 12 ins. diam., bears S. $85^{\circ}05'$ E., 72 lks. dist., mkd. T4S R23E S28 BT.

A juniper, 9 ins. diam., bears S. $56^{\circ}22'$ W., 135 lks. dist., mkd. T4S R23E S29 BT.

A juniper, 12 ins. diam., bears N. 52° W., 143 lks. dist., mkd. T4S R23E S20 BT.

From the $\frac{1}{4}$ sec. cor. of secs. 4 and 9, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above the ground, at the cor. of fences, extending E. and S., with brass cap mkd. as described in the official record of the 1939 survey.

This cor. now functions as the $\frac{1}{4}$ sec. cor. of sec. 4, only. I change the marks on the brass cap to read.

T 4 S R 23 E

$\frac{1}{4}$ S 4

1970

1939

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 4 S., R. 23 E., Salt Lake Meridian, Utah

CHAINS

from which 1939 bearing tree

A juniper, 8 ins. diam., bears N. 18°40' W., 65 lks. dist., mkd. ¼ S4 BT.

new bearing tree

A juniper, 6 ins. diam., bears N. 62° E., 65 lks. dist., mkd. ¼ S4 BT.

West, bet. secs. 4 and 9.

Asc. E. slope through scattered juniper.

2.48 Point for the ¼ sec. cor. of sec. 9 only, 40 chs. East of the cor. of secs. 4, 5, 8, and 9.

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.

¼ S 9
T 4 S R 23 E
1970

from which

A juniper, 5 ins. diam., bears S. 1° E., 40 lks. dist., mkd. ¼ S9 BT.

A juniper, 10 ins. diam., bears S. 57° 30' W., 110 lks. dist., mkd. ¼ S9 BT.

42.48 The cor. of secs. 4, 5, 8, and 9, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the official record of the 1939 survey.

from which the 1939 bearing trees

A juniper, 7 ins. diam., bears N. 59°50' E., 12 lks. dist., mkd. T4S R23E S4 BT.

A juniper, 15 ins. diam., bears S. 20°25' E., 48 lks. dist., mkd. DNM T4S R23E S9 BT.

A juniper, 4 ins. diam., bears S. 4°37' W., 102 lks. dist., mkd. BT.

A juniper, 10 ins. diam., bears N. 31° 08' W., 160 lks. dist., mkd. T4S R23E S5 BT.

Survey of a Portion of the Subdivisional Lines, T. 4 S., R. 23 E., Salt Lake Meridian, Utah

From the cor. of secs. 16, 17, 20, and 21, monumented with an iron post, 2 ins. diam., firmly set in a mound of stone, 5 ft. base, 2 ft. high, with brass cap mkd. as described in the official record of the 1939 survey.

from which the original bearing trees

A juniper, 8 ins. diam., bears N. 56°25' E., 92 lks. dist., mkd. DNM T4S R23E S16 BT.

Survey of a Portion of the Subdivisional Lines,
T. 4 S., R. 23 E., Salt Lake Meridian, Utah

CHAINS		
40.00	<p>A juniper, 12 ins. diam., bears S. 79°53' E., 43 lks. dist., mkd. DNM T4S R23E S21 BT.</p> <p>A juniper, 8 ins. diam., bears S. 53°08' W., 110 lks. dist., mkd. T4S R23E S20 BT.</p> <p>A juniper, 8 ins. diam., bears N. 73° W., 40 lks. dist., mkd. T4S R23E S17 BT.</p> <p>East, bet. secs. 16 and 21.</p> <p>Over rolling land, through scattered juniper and sage.</p> <p>Point for the ¼ sec. cor. of secs. 16 and 21.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 4 S R 23 E</p> <p style="text-align: center;">¼ $\frac{S 16}{S 21}$</p> <p style="text-align: center;">1970</p> <p>from which</p> <p>A juniper, 5 ins. diam., bears N. 37° E., 83 lks. dist., mkd. ¼ S16 BT.</p> <p>A juniper, 7 ins. diam., bears S. 29°30' W., 73 lks. dist., mkd. ¼ S21 BT.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.</p>	
40.00	<p>From the cor. of secs. 8, 9, 16, and 17, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. as described in the official record of the 1939 survey.</p> <p>from which the original bearing trees</p> <p>A juniper, 12 ins. diam., bears N. 66° 40' E., 122 lks. dist., mkd. DNM T4S R23E S9 BT.</p> <p>A juniper, 8 ins. diam., bears S. 57°30' E., 69 lks. dist., mkd. DNM T4S R23E S16 BT.</p> <p>A juniper, 6 ins. diam., bears S. 36°45' W., 169 lks. dist., mkd. T4S R23E S17 BT.</p> <p>A juniper, 6 ins. diam., bears N. 0°40' W., 69 lks. dist., mkd. T4S R23E S8 BT.</p> <p>East, bet. secs. 9 and 16.</p> <p>Over rolling land through scattered juniper and sage.</p> <p>Point for the ¼ sec. cor. of secs. 9 and 16.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p>	

Survey of a Portion of the Subdivisional Lines,
T. 4 S., R. 23 E., Salt Lake Meridian, Utah

CHAINS		
	<p style="text-align: center;">T 4 S R 23 E</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S 9}{S 16}$</p> <p style="text-align: center;">1970</p> <p>from which</p> <p>A juniper, 5 ins. diam., bears S. 45°30' W., 67 lks. dist., mkd. $\frac{1}{4}$ S16 BT.</p> <p>A juniper, 5 ins. diam., bears N. 46°45' W., 63 lks. dist., mkd. $\frac{1}{4}$ S9 BT.</p>	
	<p>Subdivision of Section 9, T. 4 S., R. 23 E., Salt Lake Meridian, Utah</p>	
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 9 and 16.</p> <p>N. 0°06' W., on the N-S centerline of sec. 9.</p> <p>1.00 Desc. into canyon through scattered juniper.</p> <p>2.80 Bottom of canyon, 2 chs. wide, 60 ft. deep, course SW.</p> <p>40.49 Point for witness point.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">WP C S 9 C</p> <p style="text-align: center;">1970</p> <p>82.52 The $\frac{1}{4}$ sec. cor. of sec. 9 only.</p>	
	<p>Subdivision of Section 16, T. 4 S., R. 23 E., Salt Lake Meridian, Utah</p>	
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 16 and 21.</p> <p>N. 0°08' W., on the N-S centerline of sec. 16.</p> <p>Asc. rolling S. slope, through dense sage and juniper.</p> <p>42.20 Point for witness point.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">WP C S 16 C</p> <p style="text-align: center;">1970</p>	

Subdivision of Section 16,
T. 4 S., R. 23 E., Salt Lake Meridian, Utah

CHAINS		
80.08	The $\frac{1}{4}$ sec. cor. of secs. 9 and 16.	
	Subdivision of Section 21, T. 4 S., R. 23 E., Salt Lake Meridian, Utah	
38.80	<p>From the $\frac{1}{4}$ sec. cor. of sec. 21 only.</p> <p>N. $0^{\circ}10'$ W., on the N-S centerline of sec. 21.</p> <p>Ascend S. slope through scattered juniper and sage.</p> <p>Point for witness point.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WP C S 21 C 1970</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, N. of cor.</p>	
78.89	<p>The $\frac{1}{4}$ sec. cor. of secs. 16 and 21.</p> <p style="text-align: center;">Subdivision of Section 28, T. 4 S., R. 23 E., Salt Lake Meridian, Utah</p>	
37.91	<p>From the $\frac{1}{4}$ sec. cor. of secs. 28 and 33, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, and in a mound of stone, 2 ft. base, to top of brass cap, mkd. as described in the official record of the 1939 survey.</p> <p>N. $0^{\circ}08'$ W., on the N-S centerline of sec. 28.</p> <p>Over open rolling clay hills.</p> <p>Point for witness point.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WP C S 28 C 1970</p> <p>Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.</p>	
79.30	Wash, 1 ch. wide, 30 ft. deep, course SSE.	
80.65	The $\frac{1}{4}$ sec. cor. of sec. 28 only.	

Subdivision of Section 33,
T. 4 S., R. 23 E., Salt Lake Meridian, Utah

CHAINS	Subdivision of Section 33, T. 4 S., R. 23 E., Salt Lake Meridian, Utah
42.80	<p>From the $\frac{1}{4}$ sec. cor. of sec. 33 only, on the south boundary of the township, heretofore described.</p> <p>N. $0^{\circ}26'$ W., on the N-S center line of sec. 33.</p> <p>Over rolling bottom land, through scattered sagebrush.</p> <p>Point for the $C\frac{1}{4}$ sec. cor. of sec. 33, at the intersection with the E and W center line of the sec.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 4 S R 23 E C$\frac{1}{4}$ S33 1970</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
82.52	<p>The $\frac{1}{4}$ sec. cor. of secs. 28 and 33.</p> <p>From the $\frac{1}{4}$ sec. cor. of secs. 33 and 34, monumented with a sandstone, 12 x 7 x 4 ins., set 4 ins. in the ground, mkd. $\frac{1}{4}$ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 4 S R 23 E $\frac{1}{4}$ S 33 S 34 1970</p> <p>Bury the mkd. stone, set a wood post, 6 ft. long, 4 ins. diam., alongside; and raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W of cor.</p> <p>S. $89^{\circ}40'$ W., on the E-W Center line of sec. 33.</p>
0.50	<p>Present left bank of the Green River, bears S. 8° E., and N. 8° W.</p>
7.30	<p>Present right bank of the Green River bears S. 10° E., and N. 10° W.</p>
7.51	<p>Point for witness point.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WP C ——— C S 33 1970</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>

Subdivision of Section 33,
T. 4 S., R. 23 E., Salt Lake Meridian, Utah

CHAINS	
18.48	Fence, on highway right-of-way bears N. 23° E. and S. 23° W.
19.73	Point for the center E 1/16 sec. cor. of sec. 33, not monumented.
20.14	Centerline of Utah Highway 149, blacktop, bears N. 21°38' E. and S. 21°38' W.
22.67	Power line, bears N. 19°20' E. and S. 19°20' W.
39.46	Center ¼ sec. cor. of sec. 33.
59.20	Trail road, 15 lks. wide, bears N. and S.
69.45	Buried gas pipeline, bears S. 26°30' E. and N. 26°30' W.
79.70	The ¼ sec. cor. of secs. 32 and 33, monumented with a sandstone, 12 x 7 x 4 ins., set 4 ins. in the ground, mkd. ¼ on W face.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.
	<pre> T 4 S R 23 E ¼ S 32 S 33 1970 </pre>
	Bury the mkd. stone alongside the iron post.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	<p>General Description</p> <p>The land encompassed in this survey is approximately 17 miles northeast of Vernal, Utah. The main access to the area is by Utah State Highway No. 149, with several jeep trails throughout the area, a buried gas pipeline crosses the west half of Section 33. The Green River flows through the east half of Section 33. The elevation of the area surveyed ranges from 4700 feet above sea level in Section 33 to 6000 feet above sea level in Section 9.</p> <p>The terrain of the area varies from river bottom land in Section 33, to rough, broken, mountainous land throughout the other area of the survey. The soil also varies from silt along the river bottom to open sandstone faces. The vegetation consists of sparse, scattered sagebrush, and juniper.</p> <p>No mineral formations of consequence were noted during the survey.</p> <p>The average of a number of readings along the lines resurveyed gives a mean magnetic declination of 14°30' E.; with a range of 1°00' in local attraction.</p>

CERTIFICATE OF SURVEY

~~XXX~~We), Douglas A. Cody and Gail E. Reynolds, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 21st day of May, 1970, ~~XXX~~We) have dependently resurveyed a portion of the north boundary of T. 5 S., R. 23 E., and dependently resurveyed a portion of the subdivisional lines, surveyed a portion of the subdivisional lines and subdivided certain sections in Township 4 South, Range 23 East,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by ~~XXX~~ (us) and under ~~XX~~ (our) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

June 15, 1982 (Date) Douglas A. Cody (Cadastral Surveyor)

June 15, 1982 (Date) Gail E. Reynolds (Cadastral Surveyor) Supervisory

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the north boundary of T. 5 S., R. 23 E., and the dependent resurvey of a portion of the subdivisional lines, the survey of a portion of the subdivisional lines and the subdivision of certain sections in T. 4 S., R. 23 E., SLM, Utah

executed by Douglas A. Cody, Cadastral Surveyor Gail E. Reynolds, Supervisory Cadastral Surveyor having been critically examined and found correct, are hereby approved.

June 23, 1982 (Date) Glen B. Hatch (Chief Cadastral Survey Examination and Approval Staff) Chief Cadastral Surveyor for Utah

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in T. 4 S., R. 23 E., Salt Lake Meridian, Utah is a true copy of the original field notes.

(Date) (Chief Cadastral Survey Examination and Approval Staff) Chief Cadastral Surveyor for Utah

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

R602

314

ORIGINAL
FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

A PORTION OF THE SOUTH BOUNDARY (FIRST STANDARD PARALLEL SOUTH)

OF

TOWNSHIP 5 SOUTH, RANGE 3 WEST,

A PORTION OF THE EAST BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES,

A PORTION OF THE OLD FT. CRITTENDEN MILITARY RESERVATION BOUNDARY

AND

PORTIONS OF MINERAL SURVEYS

OF

TOWNSHIP 6 SOUTH, RANGE 3 WEST

Of the Salt Lake Meridian,

In the State of Utah

EXECUTED BY

Glen B. Hatch Supervisory Cadastral Surveyor

Under special instructions dated June 6, 19 73, approved June 6, 1973,

_____, which provided for the surveys included under ~~U.S. Survey~~/Group
Number 547, and assignment instructions dated June 22, 19 73.

Survey commenced July 3, 19 73

Survey completed April 10, 19 81

INDEX DIAGRAM

Township 6 South, Range 3 West

		4		4		3		2	
		75		76		50		38	
6	5	4	3	2	1	8			
		75		49		37		36	
		73		48		35		7	
7	8	9	10	11	12				
102		70		68		47		35	
		66		46		33		6	
18	17	16	15	14	13				
99		84		65		46		33	
98		95		83		46			
		59		45		32		5	
19	20	21	22	23	24				
94		82		58		44		31	
92		91		81		44			
		53		41		30		25	
30	29	28	27	26	25				
89		78		52		40			
89		87		78		40			
		51		38		29		26	
31	32	33	34	35	36				
86		76		51		29		26	

Fort Crittenden Military Boundary
Mineral Surveys

- Pages 10 - 28
- Pages 103 - 127

Township 6 South, Range 3 West, Salt Lake Meridian, Utah

CHAINS

The history of surveys of Township 6 South, Range 3 West, Salt Lake Meridian, Utah, is as follows:

Surveyed by Retr. or Resurveyed by

NORTH BOUNDARY (First Standard Parallel South)

E. 3 miles	Robert Gorlinski		
		1887	
W. 3 miles	Robert Gorlinski		
		1892	
All			Ralph Gentry 1926 - 28

EAST BOUNDARY

S. 5 miles	Joseph Troskolawski		
		1856	
N. 1 mile	Robert Gorlinski		
		1887	
S. 5 miles			Robert Gorlinski 1887
S. 1 mile			Joseph C. Thoma 1918

SOUTH BOUNDARY

West portion	C.L. Craig	1856	
E. 1½ miles	Joseph Troskolawski		
		1856	
W. 2 miles			A.D. Ferron 1871
E. portion			Robert Gorlinski 1887
Portions of secs. 34 and 35	Robert Gorlinski		
		1887	
W. portion Sec. 33 and E½, sec. 36			Robert Gorlinski 1892
S. Bdy., Secs. 31, 32, 34, and 35			Joseph C. Thoma 1918
			Glen B. Hatch 1973

WEST BOUNDARY

S. 2 miles	C.L. Craig	1856	
N. 4 miles	Robert Gorlinski		
		1892	
S. 2 miles			Robert Gorlinski 1892
N. 4 miles			Ralph Gentry 1926
S. 2 miles			Elliot Bird, et al 1943

BOUNDARY OF Ft. CRITTENDEN MILITARY RESERVATION

All	Robert Gorlinski		
		1887	

SUBDIVISION

SW portion	C.L. Craig	1856	
SE portion	Joseph Troskolawski		
		1856	
NE portion	Robert Gorlinski		
		1887	
SE portion			Robert Gorlinski 1887
NW portion	Robert Gorlinski		
		1892	
SW portion			Robert Gorlinski 1892

Township 6 South, Range 3 West, Salt Lake Meridian, Utah

CHAINS

The following field notes are those of the dependent resurvey of a portion of the south boundary (First Standard Parallel South), Township 5 South, Range 3 West, a portion of the East boundary, a portion of the subdivisional lines, a portion of the old Ft. Crittenden Military Reservation Boundary and portions of Mineral Surveys of Township 6 South, Range 3 West of the Salt Lake Meridian, Utah.

The resurveys were executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and Special Instructions for Group No. 547, Utah, dated June 6, 1973.

Before restoring the corners, the lines of the original surveys were retraced and diligent search made for any evidence of the original corners or other calls of the original field note records. When duly identified, the original corners were remonumented (except for some mineral survey corners) in their original position; lost section and $\frac{1}{4}$ section corners were restored by proportionate measurement. Lost mile corners, half mile corners and angle points along the old military reservation boundary were restored by the Grant Boundary method. Lost mineral survey corners were restored by the proportionate method that best restored them to their original positions.

The directions of the lines of these resurveys were determined by reference to the true meridian established on line by hour angle observations on Polaris. The lines were carried forward by sustained angulation, being supplemented by numerous other hour angle observations on Polaris taken throughout the progress of the resurveys. Distances were determined by chaining, triangulation and by electronic telemetry.

The geographic position for the southeast corner of section 35, as determined from section line ties to U.S.G.S. triangulation station "Sec. Cor. 36/6S/4W" (southwest corner of the township), at Latitude $40^{\circ} 14' 51.933''$ North and Longitude $112^{\circ} 13' 50.053''$ West, is as follows:

Latitude $40^{\circ} 14' 50''$ N. Longitude $112^{\circ} 08' 30''$ W.

The magnetic declination was read at several stations throughout the township and the average was found to be $16^{\circ} 00'$ East.

Dependent Resurvey of a Portion of the S. Bdy.,
(First Standard Parallel South), T. 5 S., R. 3 W.,
Salt Lake Meridian, Utah

(Reestablishment of the Survey Executed by
Robert Gorlinski in 1887, and the Resurvey by
Executed by Ralph Gentry, from 1926 - 28)

Beginning at the standard cor. of Tps. 5 S., Rs. 2 and 3 W., monumented with an iron post, 3 ins. diam., extending 10 ins. above ground, with brass cap mkd. as described in the official record of the 1926 resurvey.

N. $89^{\circ} 47'$ W., along the S. bdy. of sec. 36.

Over mountainous land, through dense timber; along N slope.

Dependent Resurvey of a Portion of the S. Bdy.,
(First Standard Parallel South), T. 5 S., R. 3 W.,
Salt Lake Meridian, Utah

CHAINS	
12.25	Small draw, drains N. 57° E.; asc. SE slope.
13.35	Point for the closing cor. of Tps. 6 S., Rs. 2 and 3 W., hereinafter described. Asc. 500 ft. over steep SE slope.
36.00	Top of ascent slopes S; desc. 100 ft. over steep SW slope.
39.86	The standard ¼ sec. cor. of sec. 36, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, 3 ft. base, 2 ft. high, in draw, draining S. 60° E., with brass cap mkd. as described in the official record of the 1926 resurvey.
	N. 89° 49' W., beginning new measurement.
	Asc. 680 ft. over steep, general SE slope.
10.00	Timber becomes scattered, enter oak brush.
13.75	Point for the N ¼ sec. cor. of sec. 1, T. 6 S., R. 3 W., hereinafter described.
22.50	High spur, slopes S. 20° W.; desc. NW slope.
29.00	Draw, drains S. 45° W.; asc. SE slope.
39.92	The standard cor. of secs. 35 and 36, monumented with an iron post, 2 ins. diam., extending 12 ins. above ground, and in a mound of stone, with brass cap mkd. as described in the official record of the 1926 resurvey.
	from which the bearing trees mkd. in 1926
	A juniper, 5 ins. diam., bears N. 21° 45' E., 96 lks. dist., mkd. BT.
	A juniper, 18 ins. diam., bears N. 50° W., 170 lks. dist., mkd. T5S R3W S35 SC BT.
	N. 89° 43' W., along the S. bdy. of sec. 35.
	Over mountainous land, through scattered timber and dense oak brush undergrowth. Asc. SE slope.
3.50	Spur, slopes S. 45° W.; desc. NW slope.
12.50	Draw, drains S. 40° W.; asc. SE slope.
14.10	The closing cor. of secs. 1 and 2, T. 6 S., R. 3 W., hereinafter described.
16.50	Point of low spur, slopes S; desc. SW slope.
18.50	Draw, drains S. 45° E.; asc. SE slope.
26.00	Spur, slopes S. 20 E.; desc. SW slope.
35.00	Head of draw, drains S. 20° E.; asc. SE slope.
39.50	Spur, slopes sharply S. 40° W.; desc. W slope.
39.83	The standard ¼ sec. cor. of sec. 35, monumented with an iron post, 1 in. diam., extending 18 ins. above ground, and in a mound of stone, with brass cap mkd. as described in the official record of the 1926 resurvey.

Dependent Resurvey of a Portion of the S. Bdy.,
(First Standard Parallel South), T. 5 S., R. 3 W.,
Salt Lake Meridian, Utah

CHAINS	
	N. 89° 59' W., beginning new measurement. Desc. over W slope.
10.00	Draw, drains S. 25° W.; asc. slong S slope.
14.50	Point of spur, slopes S; desc. SW slope.
14.59	Point for the N ¼ sec. cor. of sec. 2, T. 6 S., R. 3 W., hereinafter described.
22.50	Pole Canyon, drains S. 35° E.; asc. NE slope.
30.00	Pole Canyon, trail road, bears N. 40° W. and S. 40° E.; leave scattered timber, enter dense oak brush.
40.07	The standard cor. of secs. 34 and 35, monumented with an iron post, 2 ins. diam., extending 12 ins. above ground, and in a collar of stone, with brass cap mkd. as described in the official record of the 1926 resurvey.
	N. 89° 59' W., along the S. bdy. of sec. 34. Over mountainous land, through dense oak brush. Asc. NE slope.
14.85	Point for the closing cor. of secs. 2 and 3, T. 6 S., R. 3 W., hereinafter described.
23.00	Top of ascent slopes SE; desc. NW slope.
39.93	The standard ¼ sec. cor. of sec. 34, monumented with an iron post, 1 in. diam., extending 12 ins. above ground, with a mound of stone to N, brass cap mkd. as described in the official record of the 1926 resurvey.
	N. 89° 50' W., beginning new measurement.
1.50	Draw, drains N. 60° E.; asc. 1200 ft. over steep SE slope.
14.69	Point for the N ¼ sec. cor. of sec. 3, T. 6 S., R. 3 W., hereinafter described.
38.49	The standard cor. of secs. 33 and 34, on high ridge bearing N. 35° W. and S. 35° E., monumented with an iron post, 2 ins. diam., firmly set in a mound of stone, 3 ft. base, 2 ft. high, with brass cap mkd. as described in the official record of the 1926 resurvey.
	N. 89° 42' W., along the S. bdy. of sec. 33. Over mountainous land, through dense oak brush. Along S slope.
15.50	Divide, between Rush and Cedar Valleys, curves S. 65° W. and N. 30° E.
15.98	The original standard closing cor. of sec. 33, identical with an angle point on the old Ft. Crittenden Military Reservation Boundary and also identical with the closing cor. of secs. 3 and 4, T. 6 S., R. 3 W., monumented with a sandstone, 20 x 12 x 4 ins., firmly set 6 ins. in the ground, and plainly mkd. 3 grooves on E and W faces, SC on N face, CC on S face and X on top.

Dependent Resurvey of a Portion of the S. Bdy.,
(First Standard Parallel South), T. 5 S., R. 3 W.,
Salt Lake Meridian, Utah

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, to top of brass cap, mkd.

S C		
T 5 S R 3 W		
S 33 C		
S 4	S 3	C
C	C	AP-1
T 6 S R 3 W OMRB		

1975

Place the mkd. stone in mound of stone, alongside the iron post.

Dependent Resurvey of a Portion of the E. Bdy.,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

(Reestablishment of the Survey Executed by
Joseph Trokolawski in 1856 and the Resurvey
Executed by Robert Gorkinski in 1887)

From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., monumented with a Utah County brass tablet, 3 ins. diam., set in a concrete block, 3 ins. square, 4 ins. high, mkd. "Utah County Land Survey Marker".

T 6 S			
R 3 W R 2 W			
S 24	S 19		
S 25	S 30		

1958

A sandstone, 18 x 10 x 9 ins., plainly mkd. 2 notches on S and 4 notches on N edges, buried alongside.

N. 0° 02' W., bet. secs. 19 and 24.

Over nearly level cultivated land.

- 5.20 Fence, bears N. 32° E. and S. 32° W.
- 5.40 Gravel road, bears N. 32° E. to State Highway No. 73, and S. 32° W. to Mercur.
- 27.00 Leave cultivated land, bears E and W; asc. S slope.
- 31.30 Low rocky spur, slopes E; desc. along E slope.
- 40.37 The ¼ sec. cor. of secs. 19 and 24, monumented with a Utah County brass tablet, 3 ins. diam., set in a concrete block, 6 ins. square, 4 ins. high, mkd, "Utah County Land Survey Marker."

Dependent Resurvey of Portion of the E. Bdy.,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS		
	<p style="text-align: center;">T 6 S R 3 W R 2 W</p> <p style="text-align: center;"> $\frac{1}{4}$ S 24 S 19 </p> <p style="text-align: center;">1958</p> <p>A sandstone, 20 x 5 x 4 ins., plainly mkd. $\frac{1}{4}$, buried alongside.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 03' E., beginning new measurement.</p> <p>Over gently rolling land.</p>	
20.47	<p>Point for the N 1/16 sec. cor. of secs. 19 and 24.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 3 W R 2 W N 1/16</p> <p style="text-align: center;">S 24 S 19</p> <p style="text-align: center;">1973</p> <p>Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor.</p>	
22.25	<p>Enter cultivated land, bears W and SE.</p>	
40.94	<p>The cor. of secs. 13, 18, 19, and 24, monumented with a sandstone, 15 x 10 x 6 ins., firmly set 6 ins. in the ground, in fence line, bearing N. 89° 48' W., and S. 89° 48' E., plainly mkd. 3 notches on N and S edges.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 3 W R 2 W</p> <p style="text-align: center;"> $\frac{S\ 13\ \ S\ 18}{S\ 24\ \ S\ 19}$ </p> <p style="text-align: center;">1973</p> <p>Bury the mkd. stone alongside the iron post.</p>	
8.00	<p>Enter sagebrush, bears E and W.</p>	
20.07	<p>Cor. of fence, with fences extending E, W, and N, thence along fence line.</p>	
26.00	<p>Draw, drains S. 30° E.</p>	

Dependent Resurvey of a Portion of the E. Bdy.,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
40.14	<p>The $\frac{1}{4}$ sec. cor. of secs. 13 and 18, monumented with a Utah County brass tablet, 3 ins. diam., in a concrete block, 6 ins. square, 4 ins. high, mkd. "Utah County Land Survey Marker."</p> <div style="text-align: center;"> <p>T 6 S R 3 W R 2 W</p> <p>$\frac{1}{4}$</p> <p>S 13 S 18</p> <p>1958</p> </div> <p>A limestone, 12 x 10 x 8 ins., plainly mkd. $\frac{1}{4}$ buried alongside.</p> <hr style="width: 20%; margin: auto;"/> <p>N. $0^{\circ} 09'$ E., beginning new measurement.</p> <p>Continue over gently rolling land along fence line.</p>
30.00	Enter scatted timber.
38.00	Enter dense timber, bears E and SW.
40.69	<p>The cor. of secs. 7, 12, 13, and 18, at cor. of fences, extending S. $0^{\circ} 09'$ W., N. $89^{\circ} 45'$ W., and S. $89^{\circ} 45'$ E., monumented with a Utah County brass tablet, 3 ins. diam., in a concrete block, 6 ins. square, 4 ins. high, mkd. "Utah County Land Survey Marker."</p> <div style="text-align: center;"> <p>T 6 S R 3 W R 2 W</p> <p>S 12 S 7 S 13 S 18</p> <p>1958</p> </div> <p>A sandstone, 16 x 10 x 6 ins., plainly mkd. 4 notches on S and 2 notches on N edges, buried alongside.</p> <hr style="width: 50%; margin: auto;"/> <p>N. $0^{\circ} 09'$ E., bet. secs. 7 and 12.</p> <p>Over rolling land, through dense timber.</p>
23.00	Pole Canyon, drains S. 45° E. from N. 45° W.
33.00	Wash, drains S. 40° E. from N, thence along canyon wash.
38.00	Leave wash, drains S from N. 10° E.
39.92	<p>The $\frac{1}{4}$ sec. cor. of secs. 7 and 12, monumented with a sandstone, 20 x 12 x 6 ins., firmly set in a mound of stone, 3 ft. base, 1 ft. high, and plainly mkd. $\frac{1}{4}$ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the E. Bdy.,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS		
	<p style="text-align: center;">T 6 S R 3 W R 2 W</p> <p style="text-align: center;"> $\frac{1}{4}$ S 12 S 7 </p> <p style="text-align: center;">1974</p> <p>Bury the mkd. stone alongside the iron post, and raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <hr/> <p>N. 0° 05' E., beginning new measurement.</p> <p>0.50 Wash, drains S. 10° E. from N. 30° W.</p> <p>3.00 Pole Canyon road, bears N. 44° W. and S. 44° E.</p> <p>9.00 Trail road, bears N. 55° E. to Cedar Fort, and S. 55° W. about 4.00 chs. to junction with Pole Canyon road. Timber becomes scattered.</p> <p>31.00 Draw, drains E.</p> <p>36.00 Small spur, slopes E.</p> <p>38.00 Small draw, drains E; asc. S slope.</p> <p>40.07 The cor. of secs. 1, 6, 7, and 12, monumented with a broken sandstone, 6 x 3 x 2 ins., in small mound of stone, mkd. 1 notch on N and 3 notches on S edges, other notches have been obliterated.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 3 W R 2 W</p> <p style="text-align: center;"> S 1 S 6 S 12 S 7 </p> <p style="text-align: center;">1974</p> <p>Bury the broken mkd. stone alongside the iron post.</p>	
	<p style="text-align: center;">(Reestablishment of the Survey Executed by Robert Gorlinski in 1887)</p> <hr/> <p>North, bet. secs. 1 and 6.</p> <p>Over mountainous land through scattered timber.</p> <p>3.00 Small spur, slopes S. 50° E.</p> <p>10.00 Draw, drains S. 40° E.; asc. over SW slope.</p> <p>13.00 Narrow spur, slopes S. 40° E.; desc. over NE slope.</p>	

Dependent Resurvey of a Portion of the E. Bdy.,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
16.00	Head of draw, drains SE; asc. steep SE slope.
27.50	Spur, slopes E; desc. over steep NE slope.
31.00	Head of draw, drains E, thence along E slope.
37.00	Head of draw, drains E; asc. SE slope.
39.98	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6 at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.
	<p style="text-align: center;">T 6 S R 3 W R 2 W</p> <p style="text-align: center;">$\frac{1}{4}$ S 1 S 6 </p> <p style="text-align: center;">1974</p>
	Asc. steep SE slope.
49.00	High spur, slopes N. 55° E.; desc. over N slope.
55.00	Draw, drains N. 55° E.; asc. SE slope.
65.00	Spur, slopes N. 60° E.; desc. N slope; enter dense timber.
71.50	Underground water line and trail road, bears N. 82° E. and S. 82° W., 4.00 chs. to spring.
73.50	Draw, drains N. 60° E.; asc. SE slope.
74.17	The closing cor. of Tps. 6 S., Rs. 2 and 3 W., monumented with a Utah County brass tablet, 3 ins. diam., in a concrete block, 6 ins. square, 4 ins. high, mkd. "Utah County Land Survey Marker."
	<p style="text-align: center;">T 5 S S 36 ----- 1 6 R 3 W R 2 W T 6 S 1969</p>
	A sandstone, 16 x 10 x 8 ins., plainly mkd. 6 notches on E and W edges, buried alongside.
	I add the marks "AM" to the original cor. stone.
74.26	Intersect the First Standard Parallel South.
	Point for the closing cor. of Tps. 6 S., Rs. 2 and 3 W.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the E. Bdy.,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

T 5 S R 3 W
 S 36
 S 1 | S 6
 C | C
 R 3 W R 2 W
 T 6 S
 1974

From this cor., the standard cor. of Tps. 5 S., Rs. 2 and 3 W., bears S. 89° 47' E., 13.35 chs. dist., heretofore described.

Dependent Resurvey of a Portion of the old
Ft. Crittenden Military Reservation Boundary,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

(Reestablishment of the Survey Executed by
Robert Gorlinski in 1887)

From angle point No. 9, on the old Ft. Crittenden Military Reservation Boundary, identical with the closing cor. of secs. 8 and 9, monumented with a broken limestone, 14 x 7 x 6 ins., firmly set in a mound of stone, 1½ ft. base, 1 ft. high, plainly mkd. OMR on NE face and 3 notches on E edge.

At the angle corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 6 S R 3 W
 C C
 |
 S 8 | AP-9
 | S 9
 | OMRB
 1973

Bury the mkd. stone alongside the iron post.

S. 58° 11' E., along the 37th mile.

Asc. along high divide between Rush and Cedar Valleys, through sagebrush and oak brush undergrowth.

2.27 The closing cor. of secs. 8 and 17, hereinafter described.

9.24 Intersect line 3-4, Sue N lode, mineral survey No. 3504 at a point from which Cor. No. 3, bears N. 25° 24' E., 3.21 chs. dist., monumented with a mound of stone only, and is accepted as the best remaining evidence of the original claim cor.

At the claim corner point

Set a Copperweld monument, 30 ins. long, 5/8 ins. diam., 3 ins. in the ground to bedrock, in a mound of stone, 2 ft. base, to top of brass cap, mkd.

Dependent Resurvey of a Portion of the Old
Ft. Crittenden Military Reservation Boundary,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS




3504
SN-3

From the same point of intersection, Cor. No. 4, same survey, identical with Cor. No. 5, Genevieve lode, mineral survey No. 3511, bears S. 25° 24' W., 5.97 chs. dist., monumented with a rotted pine stake, 2 ins. square, 15 ins. long, in small mound of stone, and is accepted as the best available evidence of the original claim cor.

At the claim corner point

Set a Copperweld monument, 30 ins. long, 5/8 ins. diam., 20 ins. in the ground, with brass cap mkd.




3504
SN-4
G-5
3511

- 9.49 Angle point No. 10, identical with the closing cor. of secs. 9 and 16, monumented with a limestone, 24 x 10 x 4 ins., firmly set in a mound of stone, 2 ft. base, and plainly mkd. CC OMR on NE face, and 4 notches on S and E edges.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, to top of brass cap, mkd.



T 6 S R 3 W
AP-10
S 17 / S 9 C
S 16 C
OMRB
1973


Place the mkd. stone in mound of stone alongside the iron post.

S. 50° 36' E., beginning new measurement.

- 0.54 The 37th mile cor., monumented with a limestone, 18 x 16 x 3 ins., set in a mound of stone, 1 ft. base, and plainly mkd. 37 OMR on E face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.



T 6 S R 3 W
37 M
S 17 / S 16
OMRB
1973

Place the mkd. stone in mound of stone, alongside the iron post.

S. 50° 47' E., along the 38th mile.

Dependent Resurvey of a Portion of the old
 Ft. Crittenden Military Reservation Boundary,
 T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
	<p>Desc. along high divide between Rush and Cedar Valleys, enter scattered timber.</p>
<p>10.08</p>	<p>Point for the closing cor. of secs. 16 and 17, hereinafter described.</p>
<p>12.09</p>	<p>Angle point No. 11 monumented with an old mound of stone, and is accepted as the best available evidence of the position of the original angle point.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T 6 S R 3 W</p>
	<p style="text-align: center;">AP-11</p>
	<p style="text-align: center;">S 16 \ OMRB</p>
	<p style="text-align: center;">1974</p> <hr style="width: 20%; margin: auto;"/>
	<p>S. 9° 02' E., beginning new measurement.</p>
	<p>Continue descent along divide.</p>
<p>6.87</p>	<p>Point for angle point No. 12 at proportionate distance; there is no remaining evidence of the original angle point cor.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T 6 S R 3 W</p>
	<p style="text-align: center;">AP-12</p>
	<p style="text-align: center;">S 16 \ OMRB</p>
	<p style="text-align: center;">1974</p> <hr style="width: 20%; margin: auto;"/>
	<p>S. 32° 47' E., beginning new measurement.</p>
<p>4.58</p>	<p>Intersect line 2-3, Mercur Boy No. 1 lode, mineral survey No. 3620, at a point from which Cor. No. 2, identical with Cor. No. 3, Mercur Boy No. 5 lode, same survey, bears S. 16° 44' E., 2.50 chs. dist., reestablished from the remaining bearing tree</p>
	<p style="padding-left: 40px;">An oak, 5 ins. diam., bears S. 45° W., 34 lks. dist., scribed 2-3 3620 BT on partially overgrown blaze.</p>
	<p>At the claim corner point</p>
	<p>Set a Copperweld monument, 30 ins. long, 5/8 ins. diam., 10 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">3620</p>
	<p style="text-align: center;">MB-1</p>
	<p style="text-align: center;">2</p>
	<p style="text-align: center;">3</p>
	<p style="text-align: center;">MB-5</p>

Dependent Resurvey of a Portion of the old
Ft. Crittenden Military Reservation Boundary,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

From this cor., Cor. No. 2, Mercur Boy No. 5,
identical with Cor. No. 3, Mercur Boy No. 3, same
survey, bears S. 22° 32' E., 5.76 chs. dist.,
hereinafter described.

From the same point of intersection, Cor. No. 3, Mercur
Boy No. 1 lode, identical with Cor. No. 5, Mercur Boy
No. 4 lode, same survey, bears N. 16° 44' W., 18.25 chs.
dist., monumented with a Copperweld monument, hereinafter
described.

15.62 Point for angle point No. 13, is determined at record
bearing and distance from Cor. No. 2, Mercur Boy No. 5
lode, identical with Cor. No. 3, Mercur Boy No. 3 lode,
mineral survey No. 3620.


A decayed post, 4 x 4 ins., 4 ft. long, in a small
mound of stone, bears N. 62° 43' W., 3.44 chs.
dist., from which the original bearing trees

A juniper, 16 ins. diam., bears N. 34° 30' W.,
81½ lks. dist., scribed 2-3 3620 BT.

A pinon, 10 ins. diam., bears N. 28° 10' W.,
35 lks. dist., scribed 2-3 3620 BT.


At the claim corner point

Set a Copperweld monument, 30 ins. long, 5/8 ins.
diam., 20 ins. in the ground, and in a collar of
stone, with brass cap mkd.



At angle point No. 13

Set an iron post, 28 ins. long, 2½ ins. diam., 4 ins.
in the ground to bedrock, in a mound of stone, 3½ ft.
base, to top of brass cap, mkd.



S. 2° 18' W., beginning new measurement.

2.61 Intersect line 2-3, Mercur Boy No. 3 lode, mineral survey
No. 3620, at a point from which Cor. No. 3, identical
with Cor. No. 2, Mercur Boy No. 5 lode, same survey,
bears N. 35° 12' W., 5.12 chs. dist., monumented with a
squared wooden post, set in a mound of stone, with
illegible scribe marks.

From the same point of intersection, point for Cor. No. 2,
Mercur Boy No. 3 lode, same survey, bears S. 35° 12' E.,
3.25 chs. dist., reestablished from the original bearing
tree

A juniper, 12 ins. diam., bears N. 37° 30' W., 135½
lks. dist., scribed 3620 on partially healed blaze.

Dependent Resurvey of a Portion of the Old
Ft. Crittenden Military Reservation Boundary,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

At the claim corner point

Set a Copperweld monument, 30 ins. long, 5/8 ins. diam.,
20 ins. in the ground, with brass cap mkd.

3620

MB-3

2

- 5.65 The 37½ mile cor., monumented with a limestone,
14 x 10 x 10 ins., firmly set 4 ins. in the ground, and
plainly mkd. ½M on E face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins.
in the ground to bedrock, in a mound of stone, 3 ft.
base, to top of brass cap, mkd.

T 6 S R 3 W

37½M

S 16 | OMRB

1974

Bury the mkd. stone alongside the iron post.

From this cor., Cor. No. 2, Mercur Boy No. 3 lode, mineral
survey No. 3620, bears N. 78° 53' E., 2.04 chs. dist.,
hereinbefore described.

S. 2° 51' W., beginning new measurement.

Continue descent along divide, through saddle.

- 6.02 Intersect line 2-3, Superior No. 2 lode, mineral survey
No. 4935, at a point from which Cor. No. 2, bears
N. 30° 34' W., 7.33 chs. dist., monumented with a
partially decayed wood post, 4 x 4 ins., 4 ft. long,
scribed 2-4935.

At the claim corner point

Set a Copperweld monument, 30 ins. long, 5/8 ins. diam.,
20 ins. in the ground, with brass cap mkd.

2

S - 2

4935

Reset the mkd. wood post alongside Copperweld monument.

From the same point of intersection, Cor. No. 3, Superior
No. 2 lode, identical with Cor. No. 3, Doe Run No. 3
lode, same survey, bears S. 30° 34' E., 14.00 chs. dist.,
monumented with a partially decayed post, 4x4 ins., 4 ft.
long, with illegible scribe marks, lying alongside mound
of stone, 2 ft. base, 1 ft. high. Reset wood post in
mound of stone.

- 19.13 Point for angle point No. 14 at proportionate distance;
there is no remaining evidence of the original angle
point corner.

Dependent Resurvey of a Portion of the old
Ft. Crittenden Military Reservation Boundary,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 6 S R 3 W

AP-14

S 16 | OMRB

1974

From this cor., Cor. No. 4, Superior No. 2 lode, identical with Cor. No. 2, Doe Run No. 3 lode, Cor. No. 3, Southern Cross No. 2 lode, and Cor. No. 4, Matchless Mine lode, all of mineral survey No. 4935, bears S. 34° 50' W., 0.81 chs. dist., monumented with a wood post, 4 x 4 ins., 4 ft. long firmly set in mound of stone, 3 ft. base, 1½ ft. high, scribed 2-3-4935 on SE face.

S. 33° 24' E., beginning new measurement.

- 9.08 Angle Point No. 15, monumented with a badly decayed cedar post, 4 ins. diam., 3 ft. long, with squared top, lying in a mound of stone, 2 ft. base, 1 ft. high. This point is harmoniously related to existing original corners along the old military reservation boundary and is accepted as the best existing evidence of the original angle point cor.

At the angle corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 6 S R 3 W

AP-15

S 16 | OMRB

1974

Set the decayed cedar post alongside iron post.

S. 44° 24' E., beginning new measurement.

- 6.34 Point for angle point No. 16 at proportionate distance; there is no remaining evidence of the original angle point corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 6 S R 3 W

AP-16

S 16 | OMRB

1974

Dependent Resurvey of a Portion of the old
 Ft. Crittenden Military Reservation Boundary,
 T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

S. 13° 09' E., beginning new measurement.

Desc. sharply along divide.

- 5.91 The 38th mile cor., monumented with a limestone,
 12 x 12 x 8 ins., firmly set 6 ins. in the ground, and
 plainly mkd. 38M on E face.

At the mile corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins.
 in the ground to bedrock, in a mound of stone, 3½ ft.
 base, to top of brass cap, mkd.

T 6 S R 3 W
 38M
 S 16 \ OMRB
 1974

Bury the mkd. stone alongside the iron post.

S. 11° 11' E., along the 39th mile.

Continue sharp descent along divide.

- 4.08 Point for angle point No. 17, at proportionate distance;
 there is no remaining evidence of the original angle
 point corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins.
 in the ground to bedrock, in a mound of stone, 4 ft.
 base, to top of brass cap, mkd.

T 6 S R 3 W
 AP-17
 S 16 > OMRB
 1974

S. 38° 19' W., beginning new measurement.

- 2.63 Point for the closing cor. of secs. 16 and 21, from the
 W, hereinafter described.

- 7.40 The closing cor. of secs. 16 and 21, from the E, herein-
 after described.

- 8.02 Angle point No. 18, monumented with a juniper post, 3 ins.
 diam., 4 ft. long, with squared top, set in small mound
 of earth and stone. This point is harmoniously related
 to existing original corners along the old military
 reservation boundary and is accepted as the original
 angle point cor.

At the angle point corner

Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins.
 in the ground to bedrock, in a mound of stone, 3 ft.
 base, to top of brass cap, mkd.

Dependent Resurvey of a Portion of the old
Ft. Crittenden Military Reservation Boundary,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

T 6 S R 3 W

AP-18

OMRB

S 21

1974

Set the juniper post alongside the iron post.

S. 13° 44' E., beginning new measurement.

Along nearly level ridge top.

10.00 Ridge turns to S. 20° E.; desc. along W slope.

16.53 Intersect line 1-4, Dividend No. 0 lode, mineral survey No. 4935, at a point from which Cor. No. 1, bears N. 19° 50' W., 3.14 chs. dist., monumented with a wood post, 4 x 4 ins., 4 ft. long, firmly set in mound of stone, 2 ft. base, 1 ft. high, scribed 1-4935 on SE face.

From the same point of intersection, Cor. No. 4, Dividend No. 0 lode, identical with Cor. No. 1, Dividend No. 00 lode, same survey, bears S. 19° 50' E., 5.94 chs. dist., hereinafter described.

20.00 Head of draw, drains S. 65° W.; asc. NW slope.

24.96 Point for angle point No. 19, is determined at record bearing and distance from Cor. No. 4, Dividend No. 0 lode, identical with Cor. No. 1, Dividend No. 00 lode, mineral survey No. 4935.

A wood post, 4 x 4 ins., 4 ft. long, badly decayed and lying on a small mound of stone, bears N. 0° 15' E., 2.61 chs. dist., from which the original bearing tree

A juniper, 12 ins. diam., bears S. 25° 12' E., 147½ lks. dist., scribed 1-4-4935 BT.

At angle point No. 19

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.

T 6 S R 3 W

AP-19

S 21 OMRB


1974

S. 51° 54' W., beginning new measurement.

3.20 Point for the 38½ mile cor. at proportionate distance; there is no remaining evidence of the original 38½ mile cor.

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.

Dependent Resurvey of a Portion of the old
 Ft. Crittenden Military Reservation Boundary,
 T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS		
7.68	<p style="text-align: center;"> T 6 S R 3 W 38½M S 21 / OMRB 1974 </p> <p>Angle point No. 20, monumented with a mound of stone. This point is harmoniously related to existing original corners along the old military reservation boundary and is accepted as the best available evidence of the original angle point cor.</p> <p>At the angle point corner</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>	
10.20	<p style="text-align: center;"> T 6 S R 3 W AP-20 S 21 / OMRB 1974 </p> <hr style="width: 20%; margin: auto;"/> <p>S. 9° 50' E., beginning new measurement.</p> <p>Intersect line 2-3, Red Jacket lode, mineral survey No. 3239, at a point from which Cor. No. 2, bears N. 34° 23' W., 1.51 chs. dist., monumented with a decayed wood post, lying on small mound of stone, from which the original bearing trees</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears S. 31° 30' W., 217 lks. dist., scribed 3239 BT on partially healed blaze.</p> <p style="padding-left: 40px;">A juniper, 7 ins. diam., bears S. 36° W., 248½ lks. dist., scribed 2-3239 BT.</p> <p>From same point of intersection, point for Cor. No. 3, Red Jacket lode, bears S. 34° 23' E., 14.41 chs. dist., restored from the remaining original bearing tree</p> <p style="padding-left: 40px;">A dead pinon, 10 ins. diam., bears S. 40° 15' W., 53 lks. dist., scribed 3-3239 BT.</p> <p>At the claim corner point</p> <p>Set a Copperweld monument, 30 ins. long, 5/8 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">  </p>	
11.79	<p>Point for angle point No. 21 at proportionate distance; there is no remaining evidence of the original angle point corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>	

Dependent Resurvey of a Portion of the old
Ft. Crittenden Military Reservation Boundary,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

AP-21
S 21 } OMRB
1974

S. 24° 25' W., beginning new measurement.

Asc. along dividing ridge, enter medium timber.

7.53 Point for angle point No. 22, is determined at record bearing and distance from Cor. No. 4, Wall lode, mineral survey No. 3239.

A partially decayed wood post, 4 x 4 ins., 4 ft. long, set in a mound of stone, 2½ ft. base, dimly scribed W 3239, bears N. 42° E., 107.3 lks. dist., from which an original bearing tree

A juniper, 15 ins. diam., bears S. 17° W., 67 lks. dist., scribe marks visible on partially healed blaze.

At angle point No. 22.

Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, to top of brass cap, mkd.

T 6 S R 3 W
AP-22
S 21 } OMRB
1974

S. 2° 07' W., beginning new measurement.

Desc. along dividing ridge through dense timber.

16.38 The 39th mile cor., monumented with a limestone, 25 x 13 x 4 ins., firmly set 6 ins. in the ground, and plainly mkd. 39M OMR on E face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.



T 6 S R 3 W
39M
S 21 | OMRB
1974

Bury the mkd. stone alongside the iron post.

From this cor., the discovery point for Mary K No. 2 lode, mineral survey No. 3239, bears N. 59° 51' E., 1.91 chs. dist., monumented with remains of rotted wood post in mound of stone, from which an original bearing tree

A juniper, 14 ins. diam., bears N. 56° 30' E., 76 lks. dist., scribed DIS 3239 BT.


Dependent Resurvey of a Portion of the old
Ft. Crittenden Military Reservation Boundary,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
	<p>S. 1° 05' W., along the 40th mile, beginning new measurement.</p> <p>Along wide flat dividing ridge through dense timber.</p>
12.03	The closing cor. of secs. 21 and 28, from the W., hereinafter described.
17.21	The closing cor. of secs. 21 and 28, from the E., hereinafter described.
31.00	Trail road, curves N. 80° W., from N. 10° E.
31.99	<p>Angle point No. 23, monumented with a mound of stone only. This point is harmoniously related to existing original corners along the old military reservation boundary, and is accepted as the best available evidence of the original angle point cor.</p> <p>At the angle corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, to top of brass cap, mkd.</p> <div style="text-align: center;"> <p>T. 6 S R 3 W</p> <p>AP-23</p>  <p>S 28 / OMRB</p> <p>1974</p> </div>
	<p>S. 40° 51' W., beginning new measurement.</p> <p>Asc. along dividng ridge top.</p>
8.00	<p>The 39½ mile post, monumented with a limestone, 6 x 5 x 5 ins., firmly set in a small mound of stone, with illegible chisel marks on one face, and is accepted as the original half mile corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p> <div style="text-align: center;"> <p>T. 6 S R 3 W</p> <p>39½M</p>  <p>S 28 / OMRB</p> <p>1974</p> </div> <p>Bury the mkd. stone alongside the iron post.</p>
	<p>S. 40° 58' W., beginning new measurement.</p>
3.00	Top of ascent slopes NE and SW; desc. along S slope.
3.91	Point for angle point No. 24 at proportionate distance; there is no remaining evidence of the original angle point corner.

Dependent Resurvey of a Portion of the old
Ft. Crittenden Military Reservation Boundary,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top of brass cap, mkd.



S. 28° 58' W., beginning new measurement.


Desc. abruptly along dividing ridge.

8.00 Head of draw, drains S. 50° W., ridge turns S. 10° W.; asc. along NW slope.

12.07 Intersect line 4-1, Keystone No. 4 lode, mineral survey No. 4495 at a point from which Cor. No. 4, bears N. 13° 55' W., 14.31 chs. dist., reestablished at a point S. 1° 11' E., 1.75 chs. dist., (record tie) from Cor. No. 16, Sunshine No. 2 lode, identical with Cor. No. 12, Gold Point lode, mineral survey No. 3072, and Cor. No. 3, Tribune No. 2 lode, mineral survey No. 3088.

At the claim corner point

Set a Copperweld monument, 30 ins. long, 5/8 ins. diam., 18 ins. in the ground, with brass cap mkd.



From the same point of intersection, Cor. No. 1, bears S. 13° 55' E., 8.47 chs. dist., monumented with a wood post, 4 x 4 ins., 4 ft. long, scribed 1-4495.

from which the original bearing tree

A cedar, 12 ins. diam., bears N. 34° 40' W., 15 lks. dist., scribed 1-4495 BT.

14.22 Intersect line 16-17, Sunshine No. 2 lode, mineral survey No. 3072, at a point from which Cor. No. 17, bears S. 7° 56' E., 2.72 chs. dist., monumented with a wood post, 4 x 4 ins., 4 ft. long, in mound of stone, scribed 17-3072.

from which the original bearing trees

A juniper, 24 ins. diam., bears N. 46° 30' E., 42½ lks. dist., scribed 17-3072 BT.

A juniper, 15 ins. diam., bears S. 89° 30' W., 47½ lks. dist., scribed 17-3072 BT.

From the same point of intersection, Cor. No. 16, identical with Cor. No. 12, Gold Point lode, same survey, and Cor. No. 3, Tribune No. 2 lode, mineral survey No. 3088, bears N. 7° 56' W., 17.68 chs. dist., monumented with a mound of stone only.

Dependent Resurvey of a Portion of the old
 Ft. Crittenden Military Reservation Boundary,
 T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS		
	<p>from which the original bearing trees</p> <p>A juniper, 14 ins. diam., bears S. 36° W., 77½ lks. dist., scribed 16-3072 BT.</p> <p>A pinon, 10 ins. diam., bears N. 80° W., 48½ lks. dist., scribed 12-3072 BT. (Record, N. 13° 25' W., 79 lks. dist.).</p>	
15.47	Point for the closing cor. of secs. 28 and 29 from the N, hereinafter described.	
18.31	<p>Angle point No. 25, monumented with a mound of stone only. This point is harmoniously related to existing original corners along the old military reservation boundary, and is accepted as the best available evidence of the original angle point corner.</p> <p>At the angle corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p> <div style="text-align: center;"> <p>T 6 S R 3 W</p> <p>AP-25</p> <p>S 29 / OMRB</p> <p>1974</p> </div> <p>From this angle point, Cor. No. 17, Sunshine No. 2 lode, mineral survey No. 3072, bears N. 69° 18' E., 2.52 chs. dist., hereinbefore described. (Record, N. 70° 30' E., 2.51 chs. dist.)</p> <hr style="width: 20%; margin: auto;"/> <p>S. 16° 16' E., beginning new measurement.</p> <p>Along nearly level ridge top through dense timber.</p>	
1.69	The closing cor. of secs. 28 and 29 from the S., hereinafter described.	
2.87	<p>Angle point No. 26, monumented with a mound of stone only. This point is harmoniously related to existing original corners along the old military reservation boundary and is accepted as the best remaining evidence of the original angle point corner.</p> <p>At the angle corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p> <div style="text-align: center;"> <p>T 6 S R 3 W</p> <p>AP-26</p> <p>S 28 / OMRB</p> <p>1974</p> </div> <hr style="width: 20%; margin: auto;"/>	

Dependent Resurvey of a Portion of the old
Ft. Crittenden Military Reservation Boundary,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
	S. 10° 59' E., beginning new measurement.
	Desc. along rocky ridge top through medium dense timber.
14.84	The 40th mile cor., monumented with a limestone, 14 x 14 x 12 ins., set 3 ins. in the ground, and dimly mkd. 40M on E face.
	At the mile corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	<p style="text-align: center;">T 6 S R 3 W 40M S 28 \ OMRB 1975</p>
	Bury the mkd. stone alongside the iron post.
	From this mile cor., Cor. No. 2, Malvern No. 2 lode, identical with Cor. No. 6, Malvern lode, mineral survey No. 3433, bears S. 48° 43' W., 1.50 chs. dist., (record, S. 51° 50' W., 1.76 chs. dist.) monumented with a squared cedar post, 3 ins. diam., 4 ft. long, in mound of stone, scribed 6-3433.
	from which the original bearing trees
	A juniper, 12 ins. diam., bears S. 53° E., 12½ lks. dist., scribed 3433 BT.
	A juniper, 15 ins. diam., bears S. 46° 50' W., 18 lks. dist., scribed 2-6-3433 BT.
	From the same mile cor., Cor. No. 4, Gladys lode, mineral survey No. 3749, bears N. 40° 50' E., 2.86 chs. dist., (record, N. 40° 26' E., 2.833 chs. dist.), monumented with a wood post, 4 x 4 ins. square, 4 ft. long in mound of stone, scribed 4-3749.
	from which the original bearing trees
	A juniper, 8 ins. diam., bears S. 69° 15' E., 82 lks. dist., scribed BT 4-3749. (Record, S. 69° 09' E.)
	A juniper stump, 10 ins. diam., 2 ft. high bears S. 47° 29' E., 171 lks. dist., scribed BT.
	S. 11° 00' E., along the 41st mile, beginning new measurement.
	Desc. along E slope of ridge through medium dense timber.
7.06	Intersect line 1-2, Fellowship lode, mineral survey No. 3433, at a point from which Cor. No. 1, identical with Cor. No. 1, Campus lode, same survey, bears S. 79° 26' W., 12.59 chs. dist., monumented with a mound of stone only.

Dependent Resurvey of a Portion of the old
Ft. Crittenden Military Reservation Boundary,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

from which the original bearing trees

A juniper, 15 ins. diam., bears N. 78° E., 75
lks. dist., scribed 3433 BT.

A juniper, 15 ins. diam., bears S. 74° E., 84
lks. dist., scribed 1-1-3433 BT.

From the same point of intersection, Cor. No. 2, Fellow-
ship lode, same survey, bears N. 79° 26' E., 9.57 chs.
dist., monumented with a mound of stone only.

from which the original bearing trees

A juniper, 20 ins. diam., bears S. 71° E., 112
lks. dist., scribed 2-3433 BT.

A juniper, 24 ins. diam., bears S. 74° 35' W., 85
lks. dist., scribed 2-3433 BT.


Asc. over NE slope.

12.96

Angle point No. 27, on top of small knoll on ridge, monu-
mented with a mound of stone only. This point is
harmoniously related to existing original corners along
the old military reservation boundary, and is accepted as
the best available evidence of the original angle point
corner.

At the angle corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins.
in the ground to bedrock, in a mound of stone, 4 ft.
base, to top of brass cap, mkd.



From this cor., Cor. No. 2, Fellowship lode, mineral
survey No. 3433, bears N. 47° 40' E., 11.21 chs. dist.,
hereinbefore described.


S. 37° 16' E., beginning new measurement.

0.61



Angle point No. 28, monumented with a mound of stone only.
This point is harmoniously related to existing original
corners along the old military reservation boundary, and
is accepted as the best available evidence of the original
angle point corner.

At the angle corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins.
in the ground to bedrock, in a mound of stone, 3½ ft.
base, to top of brass cap, mkd.



Dependent Resurvey of a Portion of the old
 Ft. Crittenden Military Reservation Boundary,
 T. 6 S., R. 3 W., Salt Lake Meridian, Utah


CHAINS	
	S. 40° 31' E., beginning new measurement.
	Desc. along rocky ridge top through dense timber.
4.78	The closing cor. of secs. 28 and 33 from the W, hereinafter described.
5.58	Intersect line 4-1, Gladys lode, mineral survey No. 3749, at a point from which Cor. No. 1, bears S. 13° 11' E., 1.73 chs. dist., monumented with a badly rotted 4 x 4 ft. post, and small mound of stone.
	from which the original bearing trees
	A juniper, 6 ins. diam., bears S. 28° E., 73½ lks. dist., scribed 1-3749 BT.
	A juniper, 14 ins. diam., bears S. 57° W., 72 lks. dist., scribed 1-3749 BT.
	At the claim corner point
	Set a Copperweld monument, 30 ins. long, 5/8 ins. diam., 20 ins. in the ground, with brass cap mkd.
	
	From the same point of intersection, Cor. No. 4, bears N. 13° 11' W., 20.13 chs. dist., heretofore described.
7.06	Intersect line 1-2, Gladys Lode, mineral survey No. 3749, at a point from which Cor. No. 1, bears S. 45° 44' W., 0.80 chs. dist., hereinbefore described.
	From the same point of intersection, Cor. No. 2, Gladys Lode, identical with Cor. No. 1, Keystone No. 1 lode, same survey, bears N. 45° 44' E., 9.36 chs. dist., monumented with a decayed wood post and small mound of stone.
	from which the original bearing trees
	A juniper, 18 ins. diam., bears S. 9° 46' E., 49.7 lks. dist., scribed 2-1-3749 BT.
	A juniper, 11 ins. diam., bears S. 69° 30' W., 67½ lks. dist., scribed 2-1-3749 BT. (Record, S. 69° 24' W.)
	At the claim corner point
	Set a Copperweld monument, 30 ins. long, 5/8 ins. diam., 20 ins. in the ground, with brass cap mkd.
	
13.17	The closing cor. of secs. 28 and 33, from the E, hereinafter described.
26.37	Point for the 40½ mile cor. at proportionate distance; there is no remaining evidence of the original ½ mile cor.

Dependent Resurvey of a Portion of the old
Ft. Crittenden Military Reservation Boundary,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS		
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 6 S R 3 W 40½M S 33 \ OMRB 1975</p>	
29.47	<p>Point for angle point No. 29 at proportionate distance; there is no remaining evidence of the original angle point corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 6 S R 3 W AP-29 S 33 \ OMRB 1975</p> <hr style="width: 20%; margin: auto;"/>	
	<p>S. 61° 01' E., beginning new measurement.</p> <p>Desc. gradually along ridge through medium dense timber.</p>	
10.54	<p>Angle point No. 30, monumented with a mound of stone only. This point is harmoniously related to existing original corners along the old military reservation boundary, and is accepted as the best available evidence of the original angle point corner.</p> <p>At the angle corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 3 W AP-30 S 33 \ OMRB 1975</p> <hr style="width: 20%; margin: auto;"/>	
	<p>S. 11° 12' E., beginning new measurement.</p> <p>Over gently rolling land through scattered timber.</p>	
14.00	Trail road, curves N from S. 30° W.	
14.16	<p>Point for angle point No. 31 at proportionate distance; there is no remaining evidence of the original angle point corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>	

Dependent Resurvey of a Portion of the old
Ft. Crittenden Military Reservation Boundary,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS




S. $32^{\circ} 18'$ W., beginning new measurement.

2.00 Trail road, curves N. 30° E. from S. 24° W.

3.52 Angle point No. 32, monumented with a mound of stone only. This point is harmoniously related to existing original corners along the old military reservation boundary, and is accepted as the best available evidence of the original angle point corner.

At the angle corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.




S. $22^{\circ} 01'$ E., beginning new measurement.

Along W side of trail road, through scattered timber.

8.83 The 41st mile cor., monumented with a limestone, 21 x 10 x 5 ins., firmly set 8 ins. in the ground, and plainly mkd. 41M OMR on E face.

At the mile corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



Bury the mkd. stone alongside the iron post.

This mile cor. is located 25 lks. W of trail road, bearing N. 22° W. and S. 22° E.

S. $19^{\circ} 57'$ E., along the 42nd mile.

Over gently rolling land through scattered timber.

8.50 Trail road, bears S. 45° W. curving W and N. 45° E., 2.00 chs. to junction with trail road bearing N. 30° W. and S. 30° E.; asc. gentle N slope. Leave timber.


Dependent Resurvey of a Portion of the old
Ft. Crittenden Military Reservation Boundary,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

24.08 Angle point No. 33, on small knoll, monumented with a mound of stone only. This point is harmoniously related to existing original corners along the old military reservation boundary, and is accepted as the best available evidence of the original angle point cor.

At the angle corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.



S. 23° 17' E., beginning new measurement.


Desc. S slope.

10.10 The closing cor. of secs. 4 and 33 from the W, on the S. bdy. of the Tp., monumented with an iron post, 2 ins. diam., extending 15 ins. above ground and in a mound of stone, with brass cap mkd. as described in the official record of the 1918 resurvey.

16.18 The 4½ mile cor., monumented with a limestone, 15 x 9 x 7 ins., firmly set 10 ins. in the ground, and plainly mkd. 4½M on E face.

At the ½ mile corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.



Bury the mkd. stone alongside the iron post.

From this cor., the closing cor. of secs. 4 and 33 from the E, on the S. bdy. of the Tp., bears S. 23° 17' E., 0.57 chs. dist., monumented with an iron post, 2 ins. diam., extending 12 ins. above the ground, and in a collar of stone, with brass cap mkd. as described in the official record of the 1918 resurvey.

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

(Reestablishment of the Survey executed by
Joseph Troskolawski in 1856 and the Resurvey
Executed by Robert Gorlinski in 1887)

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
	<p>From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., 6 ins. above ground, with brass cap mkd. as described in the official record of the 1973 resurvey.</p>
	<p>N. 0° 06' W., bet. secs. 35 and 36.</p>
	<p>Over nearly level cultivated land.</p>
24.60	<p>Old Salt Lake and Western Railroad grade, bears N. 31° 30' E. and S. 31° 30' W.</p>
40.32	<p>Point for the ¼ sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T 6 S R 3 W</p> <p style="text-align: center;"> $\frac{1}{4}$ S 35 S 36 1973 </p>
40.40	<p>Wells Canyon, 20 lks. wide, 10 ft. deep, drains E.</p>
53.25	<p>Graded dirt road, bears E and W, leave cultivated land; asc. S slope.</p>
60.48	<p>Point for the N 1/16 sec. cor. of secs. 35 and 36.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 6 S R 3 W N 1/16</p> <p style="text-align: center;">S 35 S 36</p> <p style="text-align: center;">1973</p>
	<p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.</p>
	<p>From this cor., U.S.M.M. No. 5, bears N. 55° 42' W., 21.82 chs. dist., monumented with a squared cedar post, 4 ins. diam., in mound of stone, 5 ft. base, 2½ ft. high.</p>
	<p>Enter scattered timber.</p>
74.20	<p>Spur, slopes S. 60° E.; desc. over NE slope.</p>
80.64	<p>The cor. of secs. 25, 26, 35, and 36, monumented with a limestone, 20 x 8 x 6 ins., firmly set 10 ins. in the ground, at cor. of old abandoned fence bearing N and E, and plainly mkd. 1 notch on S and E edges, and witnessed by a mound of stone alongside.</p>
	<p>At the corner point</p>

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 3 W</p> <p style="text-align: center;">S 26 S 25 S 35 S 36</p> <p style="text-align: center;">1973</p> <p>Bury the mkd. stone alongside the iron post.</p>
	<p style="text-align: center;">(Reestablishment of the Survey Executed by Robert Gorlinski in 1887)</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 07' E., bet. secs. 25 and 26.</p> <p>Over gently rolling land through widely scattered timber. Desc. gentle NE slope, along old abandoned fence line.</p> <p>4.60 Graded dirt road, bears N. 62° W. to Mercur and S. 62° E. to State Highway No. 73. Leave timber and enter sagebrush.</p> <p>20.29 Point for the S 1/16 sec. cor. of secs. 25 and 26, at edge of cultivated land bearing SE and curving N. Abandoned fence line ends.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 3 W S 1/16</p> <p style="text-align: center;">S 26 S 25</p> <p style="text-align: center;">1973</p> <p>Over cultivated land.</p> <p>40.58 Point for the ¼ sec. cor. of secs. 25 and 26, at proportionate distance falls at edge of cultivated land bearing SW curving S and SE. A sandstone, 8 x 8 x 5 ins., plainly mkd. ¼ and was found lying loose on the ground in cultivated area.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 3 W</p> <p style="text-align: center;">¼ S 26 S 25 </p> <p style="text-align: center;">1973</p> <p>Bury the mkd. stone alongside the iron post.</p> <p>Continue over gently rolling land through sagebrush undergrowth.</p> <p>42.85 Clay Canyon, 25 lks. wide, 5 ft. deep, drains S. 50° E.</p>

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS					
56.50	Manning Canyon, 20 lks. wide, 5 ft. deep, drains S. 42° E., enter cultivated land, edge follows along wash.				
66.75	Leave cultivated land, edge bears NW and SE.				
72.70	E edge of small stock pond, 1.00 ch. diam.				
80.50	Gravel road, bears N. 40° W. to Mercur and S. 40° E. curving E to State Highway No. 73.				
81.16	Point for the cor. of secs. 23, 24, 25, and 26, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.				
	<p style="text-align: center;">T 6 S R 3 W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 23</td> <td style="padding: 0 5px;">S 24</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 26</td> <td style="padding: 0 5px;">S 25</td> </tr> </table> <p style="text-align: center;">1973</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p>	S 23	S 24	S 26	S 25
S 23	S 24				
S 26	S 25				
	<p style="text-align: center;">(Reestablishment of the Survey Executed by Joseph Trokolawski in 1856 and the Resurvey Executed by Robert Gorlinski in 1887)</p> <hr style="width: 20%; margin: auto;"/> <p>From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., hereinbefore described.</p> <p>S. 89° 57' W., bet. secs. 24 and 25.</p> <p>Over cultivated land.</p> <p>3.28 Fence, bears N. 32° E. and S. 32° W. curving W, leave cultivated land.</p> <p>3.55 Gravel road, bears N. 32° E. to State Highway No. 73, and curves W to Mercur, thence over rolling land through widely scattered timber.</p> <p>12.95 Same gravel road, bears SE and NW.</p> <p>15.00 Wash, drains S. 70° E.</p> <p>27.45 Same gravel road, bears N. 87° E. and S. 87° W.</p> <p>40.43 The ¼ sec. cor. of secs. 24 and 25, monumented with a limestone, 12 x 10 x 5 ins., firmly set 4 ins. in the ground and plainly mkd. ¼ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 3 W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">¼ S 24</td> <td style="padding: 0 5px;">S 25</td> </tr> </table> <p style="text-align: center;">1973</p>	¼ S 24	S 25		
¼ S 24	S 25				

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
	<p>Bury the mkd. stone alongside the iron post, and raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.</p> <p style="text-align: center;">(Reestablishment of the Survey Executed by Robert Gorlinski in 1887)</p> <p>N. 89° 04' W., beginning new measurement.</p>
17.85	Trail road, bears N and S, 1.00 ch. to gravel road bearing N. 87° E. and S. 87° W.
36.00	Small wash, drains S. 20° E.
40.39	The cor. of secs. 23, 24, 25, and 26.
	<p>N. 0° 14' W., bet. secs. 23 and 24.</p> <p>Over rolling land, through widely scattered timber and dense sagebrush.</p>
5.50	Small wash, drains irregularly S. 20° E.; asc. SW slope.
15.00	Enter dense timber, bears NW and SE.
26.15	Spur, slopes S. 45° E.; desc. NE slope.
40.58	Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 3 W</p> <p style="text-align: center;"> $\frac{1}{4}$ S 23 S 24 1973 </p>
	<p>Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor.</p>
40.80	Wash, 15 lks. wide, 3 ft. deep, drains S. 80° E.; asc. over rolling land, through scattered timber.
49.15	Trail road, bears N. 37° W. and S. 37° E.
58.15	Wash, drains S. 30° E.; asc. over SW slope.
75.30	Point of low spur, slopes S. 80° W.; desc. over NW slope.
80.60	Wash, 15 lks. wide, 2 ft. deep, drains S. 75° W.
81.16	Point for the cor. of secs. 13, 14, 23, and 24, at proportionate distance; there is no remaining evidence of the original corner.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS		
	<p style="text-align: center;">T 6 S R 3 W</p> <p style="text-align: center;">S 14 S 13 S 23 S 24</p> <p style="text-align: center;">1974</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p>	
41.02	<p style="text-align: center;">(Reestablishment of the Survey Executed by Joseph Troskolawski in 1856 and the Resurvey Executed by Robert Gorlinski in 1887)</p> <hr/> <p>From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89° 48' W., bet. secs. 13 and 24.</p> <p>Over gently rolling land along fence line. Land to S cultivated.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 24, at intersection of fences extending S. 89° 48' E., N and S. This point is harmoniously related to existing original corners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>	
26.10	<p style="text-align: center;">T 6 S R 3 W</p> <p style="text-align: center;">$\frac{1}{4}$ S 13 S 24</p> <p style="text-align: center;">1973</p> <hr/> <p style="text-align: center;">(Reestablishment of the Survey Executed by Robert Gorlinski in 1887)</p> <hr/> <p>N. 89° 32' W., beginning new measurement.</p> <p>Asc. over steep E slope, enter widely scattered timber. Leave cultivated land to S.</p>	
39.25	Ridge, bears S. 40° E. from N; desc. over NW slope.	
40.26	Wash, 15 lks. wide, 2 ft. deep, drains S. 65° W. from N. 35° E.	
	<p>The cor. of secs. 13, 14, 23, and 24.</p> <hr/> <p>N. 0° 51' E., bet. secs. 13 and 14.</p> <p>Over mountainous land, through scattered timber. Asc. over SW slope.</p>	

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
24.50	Ridge, bears N. 80° W., and curves S. 40° E.; desc. over NE slope.
36.00	Draw, drains E; asc. over SE slope.
40.59	The ¼ sec. cor. of secs. 13 and 14, monumented with a sandstone, 16 x 16 x 4 ins., firmly set 6 ins. in the ground and plainly mkd. ¼ on W face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, to top of brass cap, mkd.
	<p style="text-align: center;">T 6 S R 3 W</p> <p style="text-align: center;"> $\frac{1}{4}$ S 14 S 13 1973 </p>
	Place the mkd. stone in mound of stone alongside the iron post.
	N. 0° 12' E., beginning new measurement.
	Asc. over SE slope, enter medium dense timber.
10.00	Small draw, drains S. 45° E.; asc. over SW slope.
28.15	Ridge, bears E and curves NW; desc. over NE slope.
36.00	Head of draw, drains E; asc. over SE slope.
39.00	Top of ascent, slopes E; desc. over NE slope.
39.93	The cor. of secs. 11, 12, 13, and 14, monumented with a sandstone, 20 x 8 x 4 ins., set in a mound of stone and plainly mkd. 4 notches on S and 1 notch on E edges.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.
	<p style="text-align: center;">T 6 S R 3 W</p> <p style="text-align: center;"> S 11 S 12 S 14 S 13 1973 </p>
	Place the mkd. stone in mound of stone, alongside the iron post.
<p>(Reestablishment of the Survey Executed by Joseph Trokolawski in 1856 and the Resurvey Executed by Robert Gorlinski in 1887)</p>	

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
	<p>From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., hereinbefore described.</p>
	<p>N. 89° 45' W., bet. secs. 12 and 13.</p>
	<p>Over gently rolling land through dense timber and along fence line.</p>
40.66	<p>The ¼ sec. cor. of secs. 12 and 13, monumented with a sandstone, 18 x 8 x 3 ins., firmly set 4 ins. in the ground, in fence line extending 1.00 ch. to W., and plainly mkd. ¼ on N face.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 6 S R 3 W</p>
	<p style="text-align: center;">¼ $\frac{S\ 12}{S\ 13}$</p>
	<p style="text-align: center;">1974</p>
	<p>Bury the mkd. stone alongside the iron post.</p>
	<p>N. 89° 56' W., beginning new measurement.</p>
1.00	<p>End of fence line from E.</p>
2.00	<p>Draw, drains S. 20° E.; asc. over SE slope.</p>
34.00	<p>Draw, drains S. 70° E.; asc. over NE slope.</p>
40.01	<p>The cor. of secs. 11, 12, 13, and 14.</p>
<p>(Reestablishment of the Survey Executed by Robert Gorlinski in 1887)</p>	
	<p>N. 0° 38' W., bet. secs. 11 and 12.</p>
	<p>Over mountainous land, through medium dense timber; desc. over NE slope.</p>
4.00	<p>Draw, drains S. 60° E.; asc. over SW slope.</p>
11.00	<p>Spur, slopes S. 50° E.; thence along E slope.</p>
16.00	<p>Spur, slopes N. 70° E.; desc. over NW slope.</p>
25.00	<p>Draw, drains N. 45° E.; thence along rolling E slope.</p>
39.96	<p>The ¼ sec. cor. of secs. 11 and 12, monumented with a sandstone, 20 x 14 x 8 ins., firmly set 3 ins. in the ground, and plainly mkd. ¼ on W face.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p>

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

T 6 S R 3 W

$$\begin{array}{c} \frac{1}{4} \\ | \\ \text{S } 11 \quad | \quad \text{S } 12 \\ | \end{array}$$

1973

Place the mkd. stone in mound of stone alongside the iron post.

N. $0^{\circ} 59'$ E., beginning new measurement.

- 1.50 Draw, drains S. 60° E.; asc. over SW slope.
- 18.00 Spur, slopes S. 40° E.; desc. over NE slope.
- 35.00 Trail road, at base of ridge, bears N. 27° W. and S. 27° E.; enter sagebrush.
- 39.75 Point for the cor. of secs. 1, 2, 11, and 12, at proportionate distance falls in large flat wash, 1.40 chs. wide, draining S. 40° E.; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

T 6 S R 3 W

$$\begin{array}{c} \text{S } 2 \quad | \quad \text{S } 1 \\ \text{S } 11 \quad | \quad \text{S } 12 \end{array}$$

1973

Raise a mound of stone, 5 ft. base, 3 ft. high, NW of cor.

From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., heretofore described.

N. $89^{\circ} 37'$ W., bet. secs. 1 and 12.

Over mountainous land through scattered timber and dense undergrowth.

- 2.00 Small draw, drains S. 50° E.; asc. over NE slope.
- 17.70 Spur, slopes S. 25° E.; desc. over SW slope.
- 33.00 Draw, drains S. 35° E.; thence over rolling land.
- 39.25 Trail road, bears N. 30° W. to Pole Canyon and S. 30° E.
- 40.00 The $\frac{1}{4}$ sec. cor. of secs. 1 and 12, monumented with a sandstone, 14 x 10 x 8 ins., set in a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, plainly mkd. $\frac{1}{4}$ on N face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

T 6 S R 3 W

$$\frac{1}{4} \frac{S 1}{S 12}$$

1973

Bury the mkd. stone alongside the iron post, and raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.

S. 89° 21' W., beginning new measurement.

Over rolling land through dense timber.

7.65 Leave dense timber, bears NW and SW; enter oak brush.

14.65 Pole Canyon, drains S. 15° E.

16.65 Pole Canyon trail road, bears N. 48° W. and S. 48° E.; enter scattered timber.

40.64 The cor. of secs. 1, 2, 11, and 12.

N. 0° 09' E., bet. secs. 1 and 2.

Over rolling land through scattered timber and scattered patches of dense oak brush.

Leave wash.

4.95 Trail road, bears N. 40° E. and S. 40° W.

18.10 Trail road, bears N. 57° W. and S. 57° E., on low spur, slopes SE; desc. over NE slope.

29.00 Pole Canyon, 50 lks. wide, 4 ft. deep, drains S. 35° E.; asc. over rolling SW slope.

34.00 Pole Canyon trail road, bears nearly E and W.

39.75 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 6 S R 3 W

$$\frac{1}{4} \begin{array}{c} | \\ S 2 \quad | \quad S 1 \\ | \end{array}$$

1973

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.



40.50 Wash, 40 lks. wide, 6 ft. deep, drains S. 20° W. from irregularly N, thence asc. along wash.

44.00 Leave wash, drains irregularly S from N. 10° W.; asc. along general W slope.

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS										
53.00	Same wash, drains S. 20° W.									
64.00	Same wash, drains S. 35° E.									
74.00	Same wash, drains S. 35° W.; asc. over SE slope.									
74.65	Intersect the First Standard Parallel South.									
	Point for the closing cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.									
	Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in rock slide area, and in a mound of stone, 4 ft. base, to top of brass cap, mkd.									
	<p style="text-align: center;">T 5 S R 3 W</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">S 35</td></tr> <tr><td style="text-align: center;">S 2</td><td style="text-align: center;">S 1</td></tr> <tr><td colspan="2" style="text-align: center;"> </td></tr> <tr><td colspan="2" style="text-align: center;">C C</td></tr> </table> <p style="text-align: center;">T 6 S R 3 W 1973</p>	S 35		S 2	S 1			C C		
S 35										
S 2	S 1									
C C										
	From this cor., the standard cor. of secs. 35 and 36, T. 5 S., R. 3 W., bears S. 89° 43' E., 14.10 chs. dist., hereinbefore described.									
	<p>Point for the N ¼ sec. cor. of sec. 1, on the N. bdy. of the Tp., at mid point longitudinally between the closing cor. of secs. 1 and 2, and the closing cor. of Tps. 6 S., Rs. 2 and 3 W.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 5 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 5 S R 3 W</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">¼ S 1</td></tr> </table> <p style="text-align: center;">T 6 S R 3 W 1974</p>	¼ S 1								
¼ S 1										
	From this cor., the standard ¼ sec. cor. of sec. 36, T. 5 S., R. 3 W., bears S. 89° 49' E., 13.75 chs. dist., hereinbefore described.									
	<p>From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., extending 6 ins. above ground, with brass cap mkd. as described in the official record of the 1973 resurvey.</p> <p>N. 0° 02' W., bet. secs. 34 and 35.</p> <p>Over mountainous land, through scattered timber. Desc. over general N slope.</p>									
28.00	Draw, drains E; asc. over SE slope.									
34.00	Low spur, slopes E; desc. over NE slope.									
40.96	The ¼ sec. cor. of secs. 34 and 35, monumented with a limestone, 14 x 10 x 4 ins., set 4 ins. in the ground, and plainly mkd. ¼ on W face.									

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 6 S R 3 W</p> <div style="text-align: center;">  </div>
	<p style="text-align: center;">1973</p>
	Bury the mkd. stone alongside the iron post.
	N. 0° 05' W., beginning new measurement.
	Over gently rolling land through widely scattered timber.
6.25	Low spur, slopes E.
19.00	Wells Canyon, 20 lks. wide, 3 ft. deep, drains S. 65° E.
19.65	Trail road, bears N. 65° W. and S. 65° E.
19.96	Point for the N 1/16 sec. cor. of secs. 34 and 35.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	<p style="text-align: center;">T 6 S R 3 W</p> <p style="text-align: center;">N 1/16</p> <div style="text-align: center;">  </div>
	<p style="text-align: center;">1973</p>
	From this cor., Cor. No. 4, Michigan lode, mineral survey No. 3690, bears S. 76° 50' E., 13.35 chs. dist., reestablished from the only remaining bearing tree
	A juniper, 6 ins. diam., bears N. 22° 27' E., 280½ lks. dist., scribed 3690 BT on partially healed blaze.
	At the claim corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;">  </div>
	<p style="text-align: center;">1974</p>
39.92	The cor. of secs. 26, 27, 34, and 35, monumented with a limestone, 14 x 10 x 6 ins., set 3 ins. in the ground, plainly mkd. 1 notch on S and 2 notches on E edges, and witnessed by a small mound of stone to W.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS						
	<p>T 6 S R 3 W</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 27</td> <td style="padding: 0 5px;">S 26</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 34</td> <td style="padding: 0 5px;">S 35</td> </tr> </table> <p>1973</p> <p>Bury the mkd. stone alongside the iron post, and rebuild mound of stone, 3 ft. base, 1½ ft. high, W of cor.</p> <p>From this cor., Cor. No. 2, Guelph No. 1 lode, of cancelled mineral survey No. 3143, bears N. 72° 40' E., 6.44 chs. dist., monumented with a wood post, 4 x 4 ins., 4 ft. long, in mound of stone, scribed 2-3143.</p> <p>from which the original bearing trees</p> <p style="padding-left: 40px;">A juniper, 4 ins. diam., bears S. 89° 15' E., 123 lks. dist., scribed 2-3143 BT.</p> <p style="padding-left: 40px;">A juniper, 14 ins. diam., bears S. 6° W., 129 lks. dist., scribed 2-3143 BT.</p>	S 27	S 26	S 34	S 35	
S 27	S 26					
S 34	S 35					
	<p>From the cor. of secs. 25, 26, 35, and 36.</p> <p>N. 89° 22' W., bet. secs. 26 and 35.</p> <p>Over mountainous land, through dense timber; asc. over NE slope.</p>					
14.00	Spur, slopes N; desc. over W slope.					
16.50	Draw, drains N. 40° W.; asc. over NE slope.					
20.12	Point for the E 1/16 sec. cor. of secs. 26 and 35.					
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 6 S R 3 W</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">E 1/16</td> <td style="padding: 0 5px;">S 26</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">S 35</td> </tr> </table> <p style="text-align: center;">1973</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears S. 80° E., 15 lks. dist., scribed E 1/16 S35 BT.</p>	E 1/16	S 26		S 35	
E 1/16	S 26					
	S 35					
31.00	Ridge, bears N. 30° W. and S. 60° E.; desc. over SW slope.					
36.00	Head of draw, drains S; asc. over steep SE slope.					
40.24	<p>The ¼ sec. cor. of secs. 26 and 35, monumented with a limestone, 14 x 14 x 6 ins., set 5 ins. in the ground, and plainly mkd. ¼ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p>					

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah


CHAINS		
	<p>T 6 S R 3 W</p> <p>$\frac{1}{4} \frac{S 26}{S 35}$</p> <p>1973</p> <p>Place the mkd. stone in mound of stone, alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89° 56' W., beginning new measurement.</p> <p>Asc. over SE slope.</p> <p>2.50 Top of ascent, slopes S; desc. over SW slope.</p> <p>11.00 Draw, drains S. 25° E.; asc. over SE slope.</p> <p>20.06 Point for the W 1/16 sec. cor. of secs. 26 and 35.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, to top of brass cap, mkd.</p>	
	<p>T 6 S R 3 W</p> <p>W 1/16 $\frac{S 26}{S 35}$</p> <p>1973</p> <p>20.15 Spur, slopes S.; desc. over SW slope.</p> <p>25.50 Head of draw, drains S; asc. over SE slope.</p> <p>32.00 Spur, slopes S. 55° W; desc. over NW slope.</p> <p>40.12 The cor. of secs. 26, 27, 34, and 35.</p>	
	<p>North, bet. secs. 26 and 27.</p> <p>Over mountainous land through scattered timber.</p> <p>0.30 Wash, 10 lks. wide, 3 ft. deep, drains S. 20° W.; asc. over SE slope.</p> <p>21.21 Intersect line 10-11, Emma lode, mineral survey No. 3154, at a point from which Cor. No. 10, bears S. 80° 17' W., 6.88 chs. dist., monumented with a partially rotted wood post, 4 x 4 ins., 4 ft. long, in mound of stone, with scribe marks 1 and 4 visible, other marks are illegible.</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 12 ins. diam., with blazed face and axe marks near base, bears N. 34° E., 41 lks. dist. (Record, N. 44° E., 26 ft.)</p> <p>Note: Cors. Nos. 9 and 10, Emma lode, mineral survey No. 3154, were found to be located on the ground approximately 300 ft. farther South than the record indicates. A thorough search at the record positions failed to find any evidence of these cors.</p>	

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS		
	From the same point of intersection, Cor. No. 11, Emma lode, same survey, bears N. 80° 17' E., 15.49 chs. dist., hereinafter described.	
23.00	Top of ascent, slopes E; desc. over NE slope.	
29.77	Intersect line 9-12, Emma lode, mineral survey No. 3154, at a point from which Cor. No. 9, bears S. 82° 29' W., 10.19 chs. dist., monumented with a partially decayed wood post, 4 x 4 ins., 4 ft. long, in mound of stone, with scribe marks 9, 3--4 visible on one side. from which A juniper, an original bearing tree, 12 ins. diam., with blazed face, bears N. 58° W., 63 lks. dist. (Record, N. 58° 10' W.). Cor. No. 10, Emma Lode, bears S. 21° 36' E., 9.02 chs. dist., hereinbefore described. From the same point of intersection, Cor. No. 12, bears N. 82° 29' E., 12.39 chs. dist., monumented with a decayed wood post, in mound of stone. At the claim corner point Set a Copperweld monument, 30 ins. long, 5/8 ins. diam., 20 ins. in the ground, with brass cap mkd. <div style="border: 1px solid black; padding: 2px; margin: 10px auto; width: fit-content;"> 12 E-3154 </div>	
32.00	Draw, drains S. 35° E.; asc. over SW slope.	
33.06	Intersect line 6-7, Gold Dust No. 1 lode, mineral survey No. 3154, at a point from which Cor. No. 6, bears N. 87° 53' W., 8.04 chs. dist., monumented with a badly decayed wood post, 4 x 4 ins., 4 ft. long, in mound of stone. At the claim corner point Set a Copperweld monument, 30 ins. long, 5/8 ins. diam., 20 ins. in the ground, with brass cap mkd. <div style="border: 1px solid black; padding: 2px; margin: 10px auto; width: fit-content;"> 3154 GD-1 6 </div> From this cor., Cor. No. 5, identical with Cor. No. 2, May Bell Lode, same survey, monumented with a wood post, 4 x 4 ins., 4 ft. long, in a mound of stone, scribed 3154-2-5, bears N. 21° 50' W., 9.04 chs. dist. From the same point of intersection, Cor. No. 7, identical with Cor. No. 2, Golden Rule No. 4 lode, mineral survey No. 3160, bears S. 87° 53' E., 14.66 chs. dist., monumented with a decayed wood post, 4 x 4 ins., 4 ft. long, in small mound of stone. At the claim corner point Set a Copperweld monument, 30 ins. long, 5/8 ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, with brass cap mkd.	

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS



39.99 The $\frac{1}{4}$ sec. cor. of secs. 26 and 27, monumented with a limestone, 10 x 10 x 5 ins., firmly set 5 ins. in the ground, and witnessed by a small mound of stone to W, and plainly mkd. $\frac{1}{4}$ on W face.


From which the original bearing tree

A juniper, 20 ins. diam., bears N. 10° W.,
46 lks. dist., scribed $\frac{1}{4}$ SBT.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.

T 6 S R 3 W



1973

Bury the mkd. stone alongside the iron post.

N. $0^{\circ} 07'$ W., beginning new measurement.


Asc. over SW slope.

3.00 Ridge, bears W and curves S. 25° E.; desc. over N slope.

9.66 Intersect line 4-1, May Bell lode, mineral survey No. 3154, at a point from which Cor. No. 1, bears N. $87^{\circ} 48'$ W., 14.81 chs. dist., monumented with a decayed post, 4 x 4 ins., 4 ft. long, in mound of stone, scribe marks illegible.

At the claim corner point


Set a Copperweld monument, 30 ins. long, $\frac{5}{8}$ ins. diam., 20 ins. in the ground, with brass cap mkd.



From this cor., Cor. No. 2 of May Bell Lode, identical to Cor. No. 5 of Gold Dust No. 1 Lode, same survey, bears S. $22^{\circ} 00'$ E., 9.13 chs. dist., hereinbefore described.

From the same point of intersection, Cor. No. 4, bears S. $87^{\circ} 48'$ E., 7.63 chs. dist., monumented with a partially decayed wood post, 4 x 4 ins., 4 ft. long, scribe marks 3--4 visible.

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS								
	<p>from which an original bearing tree</p> <p>A juniper, 10 ins. diam., bears S. 89° E., 156 lks. dist., scribed 4-3154 BT.</p> <p>At the claim corner point</p> <p>Set a Copperweld monument, 30 ins. long, 5/8 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">  </div>							
30.00	Clay Canyon, 20 lks. wide, 4 ft. deep, drains E.							
38.85	Gravel road, bears N. 75° W. to Mercur and S. 75° E. to State Highway No. 73.							
40.25	<p>The cor. of secs. 22, 23, 26, and 27, monumented with a limestone, 10 x 10 x 10 ins., firmly set 7 ins. in the ground, and plainly mkd. 2 notches on S and E edges, and witnessed by a small mound of stone to W.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 6 S R 3 W</p> <table border="1" style="margin: auto;"> <tr> <td>S 22</td> <td> </td> <td>S 23</td> </tr> <tr> <td>S 27</td> <td> </td> <td>S 26</td> </tr> </table> <p>1973</p> </div> <p>Bury the mkd. stone alongside the iron post, and rebuild mound of stone, 2½ ft. base, 1½ ft. high, W of cor.</p>	S 22		S 23	S 27		S 26	
S 22		S 23						
S 27		S 26						
	<p>From the cor. of secs. 23, 24, 25, and 26.</p> <p>S. 89° 23' W., bet. secs. 23 and 26.</p> <p>Over gently rolling land through sagebrush undergrowth.</p>							
0.55	Gravel road, bears N. 40° W. to Mercur and S. 40° E. to State Highway No. 73.							
20.50	Manning Canyon, 40 lks. wide, 6 ft. deep, drains S. 28° E.							
24.30	Enter scattered timber.							
38.70	Wash, 50 lks. wide, 10 ft. deep, drains S. 30° E.							
40.32	<p>The ¼ sec. cor. of secs. 23 and 26, monumented with a sandstone, 8 x 8 x 6 ins., set in a mound of stone, and plainly mkd. ¼ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>							

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
	<p style="text-align: center;">T 6 S R 3 W</p> <p style="text-align: center;"> $\frac{1}{4}$ $\frac{S\ 23}{S\ 26}$ </p> <p style="text-align: center;">1973</p> <p>Bury the mkd. stone alongside the iron post, and raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor., a mine shaft, 25 lks. diam., about 15 ft. deep, bears S. 88° 46' W., 19.40 chs. dist.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89° 57' W., beginning new measurement.</p> <p>39.50 Trail road, bears N. 50° W. and S. 50° E.</p> <p>40.34 The cor. of secs. 22, 23, 26, and 27.</p>
	<p>N. 0° 05' W., bet. secs. 22 and 23.</p> <p>Over gently rolling land through scattered timber.</p> <p>0.70 Trail road, bears N. 50° W. and S. 50° E.</p> <p>9.50 Wash, drains N. 70° E.; enter dense timber.</p> <p>40.47 The ¼ sec. cor. of secs. 22 and 23, monumented with a sandstone, 12 x 10 x 3 ins., firmly set 6 ins. in the ground, and plainly mkd. ¼ on W face, and witnessed by a small mound of stone alongside.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 3 W</p> <p style="text-align: center;"> $\frac{1}{4}$ S 22 S 23 </p> <p style="text-align: center;">1973</p> <p>Bury the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 01' W., beginning new measurement.</p> <p>16.75 Wash, drains S. 55° E., timber becomes scattered.</p> <p>29.00 Manning Canyon, 50 lks. wide, 6 ft. deep, drains S. 55° E.</p> <p>40.59 The cor. of secs. 14, 15, 22, and 23, monumented with a limestone, 20 x 10 x 10 ins., firmly set in a small mound of stone, plainly mkd. 3 notches on S and 2 notches on E edges.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS						
	<p>T 6 S R 3 W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 15</td> <td style="padding: 0 5px;">S 14</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 22</td> <td style="padding: 0 5px;">S 23</td> </tr> </table> <p>1973</p>	S 15	S 14	S 22	S 23	
S 15	S 14					
S 22	S 23					
	<p>Bury the mkd. stone alongside the iron post, and raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.</p>					
	<p>From the cor. of secs. 13, 14, 23, and 24.</p> <p>S. 89° 23' W., bet. secs. 14 and 23.</p> <p>Over mountainous land through medium dense timber.</p>					
15.30	<p>Wash, 30 lks. wide, 3 ft. deep, drains S. 60° E.</p>					
23.05	<p>Trail road, bears N. 50° W. and S. 50° E.; asc. over NE slope. Enter dense timber.</p>					
29.50	<p>Rocky ridge, bears N. 30° W. and S. 30° E.; desc. over rocky SW slope.</p>					
40.06	<p>The ¼ sec. cor. of secs. 14 and 23, monumented with a limestone, 22 x 12 x 8 ins., plainly mkd. ¼ on N face, and firmly set 6 ins. in the ground, alongside the original bearing tree - a juniper, 10 ins. diam., scribed ¼S BT.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 6 S R 3 W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">¼</td> <td style="padding: 0 5px;">S 14</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">S 23</td> </tr> </table> <p style="text-align: center;">1973</p> <p>Place the mkd. stone in mound of stone, alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 58' W., beginning new measurement.</p> <p>Desc. over general SW slope.</p>		¼	S 14		S 23
¼	S 14					
	S 23					
24.00	<p>Wash, drains S. 55° E.; thence over gently rolling land.</p>					
27.90	<p>Gravel road, bears N. 40° W. to Mercur and S. 40° E. to State Highway No. 73.</p>					
40.38	<p>The cor. of secs. 14, 15, 22, and 23.</p>					
	<p>N. 0° 04' W., bet. secs. 14 and 15.</p> <p>Over gently rolling land through dense timber.</p>					
14.90	<p>Gravel road, bears N. 40° W. to Mercur and S. 40° E. to State Highway No. 73; asc. over S slope.</p>					

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
39.80	Point of rocky spur, slopes sharply S from N. 20° E.; thence along E slope.
40.11	The ¼ sec. cor. of secs. 14 and 15, marked by a cross (X) and ¼ on E face of vertical ledge, 3 ft. high, bearing N and S, with a small mound of stone on top of ledge above cross.
	from which the original bearing tree
	A juniper, 20 ins. diam., bears N. 28° E., 100 lks. dist., with healed blaze.
	Alongside the cross (X) on face of vertical ledge.
	Set an iron post, 28 ins. long, 2½ ins. diam., over a cross (X) on solid stone, in a mound of stone, 4 ft. base, to top of brass cap, mkd.
	<p style="text-align: center;">T 6 S R 3 W</p> <p style="text-align: center;"> $\frac{1}{4}$ S 15 S 14 </p> <p style="text-align: center;">1973</p> <hr style="width: 20%; margin: auto;"/>
	N. 0° 22' W., beginning new measurement.
2.00	Spur, slopes S. 25° W., thence along general W slope.
16.00	Head of draw, drains S. 50° W.; asc. over S slope.
39.78	The cor. of secs. 10, 11, 14, and 15, monumented with a limestone, 24 x 14 x 10 ins., firmly set 10 ins. in the ground, plainly mkd. 4 notches on the S and 2 notches on the E edges, and witnessed by a small mound of stone to the W.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, to top of brass cap, mkd.
	<p style="text-align: center;">T 6 S R 3 W</p> <p style="text-align: center;"> S 10 S 11 S 15 S 14 </p> <p style="text-align: center;">1974</p> <p>Place the mkd. stone in mound of stone, alongside the iron post, and rebuild mound of stone, 2½ ft. base, 1½ ft. high, W of cor.</p>
	From the cor. of secs. 11, 12, 13, and 14.
	S. 89° 14' W., bet. secs. 11 and 14.
	Over mountainous land, through dense timber; asc. over NE slope.
10.20	Ridge, bears N. 45° W. and S. 45° E.; desc. over steep SW slope.

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
32.40	Deep draw, drains S. 48° E.; asc. over steep NE slope.
40.69	Point for the ¼ sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap mkd.
	<p>T 6 S R 3 W</p> <p>¼ $\frac{S 11}{S 14}$</p> <p>1973</p>
	Continue ascent over steep NE slope.
54.10	High, rocky ridge, bears N. 10° W. and S. 50° E.; desc. over steep SW slope.
67.40	Small draw, drains S. 45° W.
70.40	Small draw, drains S.; asc. over SE slope.
72.40	Point of spur, slopes S; desc. along S slope.
81.38	The cor. of secs. 10, 11, 14, and 15.
	N. 0° 42' E., bet. secs. 10 and 11.
	Over mountainous land through dense timber; asc. over steep SW slope.
39.78	Point for the ¼ sec. cor. of secs. 10 and 11 at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., over a cross (X) on solid stone, in a mound of stone, 4 ft. base, to top of brass cap, mkd.
	<p>T 6 S R 3 W</p> <p>¼</p> <p>S 10 S 11</p> <p>1973</p>
40.50	High, rocky ridge, bears N. 20° W. and S. 20° E.; asc. along E slope. Leave timber, follows ridges, enter dense oak brush.
48.00	Head of draw, drains S. 65° E.; asc. over S slope.
56.00	High ridge, between Manning and Pole Canyons, bears E and W; desc. over steep N slope.
70.00	Deep draw, drains N. 15° E.; desc. over NE slope.

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS					
79.56	<p>The cor. of secs. 2, 3, 10, and 11, monumented with a mound of stone, 2 ft. base, 1½ ft. high. This point is harmoniously related to existing original corners and is accepted as the best available evidence of the original corner.</p> <p>At the corner point (center of mound)</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 6 S R 3 W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 3</td> <td style="padding: 0 5px;">S 2</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 10</td> <td style="padding: 0 5px;">S 11</td> </tr> </table> <p style="text-align: center;">1973</p>	S 3	S 2	S 10	S 11
S 3	S 2				
S 10	S 11				
1.75	<p>From the cor. of secs. 1, 2, 11, and 12.</p> <p>S. 89° 11' W., bet. secs. 2 and 11.</p> <p>Over mountainous land through dense oak brush; asc. over steep NE slope. Leave wash.</p>				
22.15	<p>Trail road, bears NE and SE.</p>				
32.00	<p>Rocky ridge, bears N. 45° W. and S. 45° E.; desc. over SW slope.</p>				
40.30	<p>Head of draw, drains S. 50° E.; asc. over steep E slope.</p>				
58.15	<p>Point for the ¼ sec. cor. of secs. 2 and 11 at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 6 S R 3 W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">¼</td> <td style="padding: 0 5px;">S 2</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">S 11</td> </tr> </table> <p style="text-align: center;">1973</p> <p>Asc. over steep E slope.</p>	¼	S 2		S 11
¼	S 2				
	S 11				
76.00	<p>Point of high spur, slopes sharply N. 50° E.; desc. over steep NW slope.</p>				
80.60	<p>Deep draw, drains N. 30° E.; asc. over NE slope.</p>				
	<p>The cor. of secs. 2, 3, 10, and 11.</p>				
3.00	<p>N. 0° 06' E., bet. secs. 2 and 3.</p> <p>Over mountainous land through dense oak brush; desc. over steep NE slope.</p>				
9.00	<p>Small draw, drains E; asc. along E slope.</p>				
	<p>Low spur, slopes E; desc. over NE slope.</p>				


Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

- 13.00 Draw, drains S. 50° E.; asc. over S slope.
- 18.00 Rocky spur, slopes S. 60° E.; asc. along rocky E slope.
- 26.00 Rocky spur, slopes E; desc. over steep N slope.
- 37.50 Deep draw, drains E; asc. over steep S slope.
- 40.07 Point for the ¼ sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.

T 6 S R 3 W



1973


Continue ascent over steep S slope.

- 54.50 High, rocky spur, slopes S. 60° E.; desc. over steep NE slope.
- 76.06 Intersect the First Standard Parallel South.

Point for the closing cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, to top of brass cap, mkd.

T 5 S R 3 W



T 6 S R 3 W

1973

From this cor., the standard cor. of secs. 34 and 35, T. 5 S., R. 3 W., bears S. 89° 59' E., 14.85 chs. dist., hereinbefore described.

Point for the N ¼ sec. cor. of sec. 2, on the First Standard Parallel South, at mid point longitudinally between the closing cor. of secs. 1 and 2, and the closing cor. of secs. 2 and 3.

Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, to top of brass cap, mkd.

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

T 5 S R 3 W

 $\frac{1}{4}$ S 2

T 6 S R 3 W

1973

From this cor., the standard $\frac{1}{4}$ sec. cor. of sec. 35,
T. 5 S., R. 3 W., bears S. $89^{\circ} 59'$ E., 14.59 chs. dist.,
hereinbefore described.

(Reestablishment of the Survey Executed by
C.L. Craig in 1856 and the Resurvey Executed
by Robert Gorlinski in 1887)

From the cor. of secs. 3, 4, 33, and 34, on the S. bdy.
of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam.,
extending 8 ins. above ground, and in a collar of stone,
with brass cap mkd. as described in the official record
of the 1918 resurvey.

N. $0^{\circ} 02'$ W., bet. secs. 33 and 34.

Over rolling land through widely scattered timber and
dense sagebrush.

- 0.90 Trail road, bears N. 48° W. and S. 48° E.
2.90 Wash, 30 lks. wide, 6 ft. deep, drains N. 80° E.
40.12 Point selected for the witness cor. to the $\frac{1}{4}$ sec. cor.
of secs. 33 and 34.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, and in a collar of stone, with brass cap
mkd.

W C
T 6 S R 3 W

$\frac{1}{4}$
↑
S 33 | S 34
|

1973

- 40.32 Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34 at propor-
tionate distance, falls in wash, 30 lks. wide, 6 ft.
deep, draining S. 15° W.; there are no remaining evidence
of the original corner.
- 46.15 Trail road, bears N. 25° E. and S. 25° W.; asc. over
gently rolling SE slope.
- 68.00 Point of spur, slopes S, thence along E slope.
- 80.64 The cor. of secs. 27, 28, 33, and 34, monumented with a
limestone, 14 x 10 x 4 ins., firmly set 5 ins. in the
ground, plainly mkd. 1 notch on S and 3 notches on
E edges.

from which an original bearing tree

A juniper, 6 ins. diam., bears S. $32^{\circ} 45'$ E.,
66 lks. dist., scribed T6S R3W S34 BT. (Record,
70 lks.)

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 3 W</p> <p style="text-align: center;">S 28 S 27 S 33 S 34</p> <p style="text-align: center;">1973</p> <p>Bury the mkd. stone alongside the iron post.</p>
	<p>(Reestablishment of the Survey Executed by Robert Gorlinski in 1887)</p>
	<p>From the cor. of secs. 26, 27, 34, and 35.</p> <p>S. 89° 56' W., bet. secs. 27 and 34.</p> <p>Over rolling land through scattered timber.</p>
0.10	Wash, 10 lks. wide, 3 ft. deep, drains S. 20° W.
7.00	Trail road, bears N. 25° W. and S. 25° E.
30.00	Wells Canyon, 25 lks. wide, 4 ft. deep, drains S. 60° E.
31.50	Trail road, bears N. 60° W. and S. 60° E.
40.20	Wash, 10 lks. wide, 2 ft. deep, drains N. 30° E.
40.27	Point for the ¼ sec. cor. of secs. 27 and 34 at proportionate distance; there is no remaining evidence of the original corner.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 3 W</p> <p style="text-align: center;">¼ S 27 S 34</p> <p style="text-align: center;">1973</p>
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.</p>
65.15	Trail road, bears N. 50° W. and S. 50° E.; thence over gently rolling land.
80.54	The cor. of secs. 27, 28, 33, and 34.
	<p>S. 89° 48' W., bet. secs. 28 and 33.</p> <p>Over rolling land through scattered timber.</p>
9.00	Small draw, drains S.
16.20	Spur, slopes S; thence along general S slope.
30.20	Spur, slopes S; desc. over SW slope.

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

- 40.21 The $\frac{1}{4}$ sec. cor. of secs. 28 and 33, monumented with a limestone, 16 x 8 x 8 ins., firmly set 6 ins. in the ground, plainly mkd. $\frac{1}{4}$ on N face, and witnessed by a small mound of stone to the N.
- At the corner point
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.
- T 6 S R 3 W
- $\frac{1}{4}$ $\frac{S\ 28}{S\ 33}$
- 1975
- Bury the mkd. stone alongside the iron post.
- _____
- N. $89^{\circ} 28'$ W., beginning new measurement.
- 1.20 Wash, 25 lks. wide, 3 ft. deep, drains S. 50° E.; asc. over NE slope.
- 10.28 The closing cor. of secs. 28 and 33, on the old Ft. Crittenden Military Reservation Boundary, monumented with a limestone, 20 x 20 x 12 ins., firmly set 6 ins. in the ground, and plainly mkd. CC on NE face, with 3 notches on E and 1 notch on S edges.
- At the corner point
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
- T 6 S R 3 W
- $\begin{array}{c} S\ 28 \\ \diagdown \\ S\ 33 \end{array} \begin{array}{c} C \\ C \\ OMRB \end{array}$
- 1975
- Bury the mkd. stone alongside the iron post.
- From this cor., angle point No. 28, on the old Ft. Crittenden Military Reservation Boundary bears N. $40^{\circ} 31'$ W., 13.17 chs. dist., hereinbefore described.
-
- From the cor. of secs. 27, 28, 33, and 34.
- N. $0^{\circ} 01'$ W., bet. secs. 27 and 28.
- Over rolling land through scattered timber.
- 21.10 Trail road, bears N. 70° W. and S. 70° E.
- 26.60 Spur, slopes E from NW; desc. over NE slope.
- 30.10 Draw, drains S. 65° E.; asc. over SW slope.
- 39.45 Narrow spur, slopes S. 80° E.; desc. over NE slope.

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
40.09	<p>The $\frac{1}{4}$ sec. cor. of secs. 27 and 28, monumented with a limestone, 16 x 9 x 8 ins., firmly set 4 ins. in the ground, and plainly mkd. $\frac{1}{4}$ on W face.</p> <p>from which the remaining original bearing tree</p> <p>A juniper, 6 ins. diam., bears S. $5^{\circ} 30'$ W., 74 lks. dist., scribed $\frac{1}{4}$ SBT.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 6 S R 3 W</p> <p style="text-align: center;"> $\frac{1}{4}$ S 28 S 27 1973 </p> <p>Bury the mkd. stone alongside the iron post.</p> <p>N. $0^{\circ} 06'$ E., beginning new measurement.</p> <p>Continue descent over NE slope.</p>
2.50	Draw, drains S. 75° E.; asc. over S slope.
5.63	<p>Intersect line 4-5, Gold Point No. 2 lode, mineral survey No. 3139, at a point from which Cor. No. 4, identical with Cor. No. 1, Gold Point No. 3 lode, mineral survey No. 3150, bears S. $89^{\circ} 20'$ E., 2.72 chs. dist.; monumented with a wood post, 4 x 4 ins., 4 ft. long, in a mound of stone, scribed 1-3150 on NE face.</p> <p>from which an original bearing tree</p> <p>A pinon, 8 ins. diam., bears N. 19° W., 153 lks. dist., scribe marks 39 BT visible on partially healed blaze.</p> <p>From the same point of intersection, Cor. No. 5, bears N. $89^{\circ} 20'$ W., 14.47 chs. dist., monumented with a mound of stone.</p> <p>from which the original bearing trees</p> <p>A juniper, 14 ins. diam., bears N. $46^{\circ} 15'$ E., 65 lks. dist., scribed 5-3139 BT.</p> <p>A juniper, 11 ins. diam., bears N. $11^{\circ} 45'$ W., $29\frac{1}{2}$ lks. dist., scribed 5-3139 BT.</p>
12.00	Spur, slopes E; desc. over NE slope. Thence dense timber.
17.50	Draw, drains S. 70° E.; asc. over SW slope.
20.00	Spur, slopes E; desc. over NE slope.

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

27.27

Intersect line 3-4, Gold Point No. 3 lode, mineral survey No. 3150, at a point from which Cor. No. 3, bears N. 89° 08' W., 0.39 chs. dist., monumented with a partially decayed wood post, 4 x 4 ins. 4 ft. long, in mound of stone, with illegible scribe marks visible on SE face.

from which

A juniper, the original bearing tree, 8 ins. diam., bears N. 79° E., 35 lks. dist., scribed 3-3150 BT.

Cor. No. 2, Gold Point lode, mineral survey No. 3138, bears N. 11° 42' E., 0.32 chs. dist., monumented with a badly decayed wood post, 4 x 4 ins., 4 ft. long, in mound of stone.

From the same point of intersection, Cor. No. 4, bears S. 89° 08' E., 4.78 chs. dist., monumented with a wood post, 4 x 4 ins., 4 ft. long, in mound of stone, scribed 4-3150.

from which the original bearing trees

A juniper stump, 12 ins. diam., 4 ft. high, bears N. 11° E., 10 lks. dist., scribed 4-3150 BT.

A juniper limb, 10 ins. diam., bears S. 87° W., 71 lks. dist., scribed 4-3150 BT.

28.50 Draw, drains N. 80° E.; asc. over SE slope.

31.00 Low spur, slopes E; desc. over NE slope.

34.50 Wells Canyon, 15 lks. wide, 4 ft. deep, drains S. 75° E., asc. over SW slope.

40.18 The cor. of secs. 21, 22, 27, and 28, monumented with a limestone, 14 x 10 x 8 ins., firmly set 10 ins. in the ground, plainly mkd. 2 notches on S and 3 notches on E edges, and witnessed by a small mound of stone to the W.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 6 S R 3 W

S 21	S 22
S 28	S 27

1973

Bury the mkd. stone alongside the iron post, and rebuild mound of stone, 2½ ft. base, 1½ ft. high, W of cor.

From this cor., a brass tablet, 3 ins. diam., set in a concrete block, 6 ins. square, 4 ins. above ground, bears N. 74° 16' E., 0.37 chs. dist., mkd. "Utah County Land Survey Marker".

T 6 S R 3 W

S 21	S 22
S 28	S 27

1961

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah


CHAINS	
	<p>From the cor. of secs. 22, 23, 26, and 27. S. 89° 44' W., bet. secs. 22 and 27. Over rolling land through medium dense timber.</p>
5.00	Graded dirt road, bears N. 73° W. to Mercur and S. 73° E. to State Highway No. 73.
9.50	Trail road, bears S. 60° W. and N. 60° E., 1.00 ch to junction with graded road to Mercur.
37.80	Spur, slopes S. 45° E.; desc. over SW slope.
40.19	<p>The ¼ sec. cor. of secs. 22 and 27, monumented with a Utah County brass tablet, 3 ins. diam., set in a concrete block, 6 ins. square, 4 ins. above ground, mkd. "Utah County Land Survey Marker".</p> <p style="text-align: center;">T 6 S R 3 W</p> <p style="text-align: center;"> $\frac{S\ 22}{S\ 27} \quad \frac{1}{4}COR$ </p> <p style="text-align: center;">1961</p> <p>A limestone, 12 x 6 x 4 ins., plainly mkd. ¼ buried alongside.</p> <p>from which the original bearing tree</p> <p style="text-align: center;">A juniper stump, 6 ins. diam., 3 ft. high, bears N. 85° W., 51 lks. dist., scribed BT. (Record, 50 lks.)</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89° 54' W., beginning new measurement.</p> <p>Desc. over SW slope.</p>
3.75	Trail road, bears N. 25° W., and S. 25° E.
6.50	Wash, 50 lks. wide, 6 ft. deep, drains S. 10° E.
7.57	<p>Intersect line 1-4, Little Green Monster lode, mineral survey No. 7207, at a point from which Cor. No. 1, bears S. 44° 31' W., 1.99 chs. dist., monumented with an iron post, 3 ins. diam., extending 20 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">1-7207</p> <p>From the same point of intersection, Cor. No. 4, bears N. 44° 31' E., 20.77 chs. dist., monumented with an iron post, 3 ins. diam., extending 30 ins. above ground, with cap mkd.</p> <p style="text-align: center;">7207 4</p> <p>from which an original bearing tree</p> <p style="text-align: center;">A juniper, 5 ins. diam., bears S. 40° W., 1 lk. dist., scribed 4-7207 BT.</p>

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

10.41 Intersect line 1-2, Little Green Monster lode, mineral survey No. 7207, at a point from which Cor. No. 1, bears S. 45° 28' E., 2.03 chs. dist., hereinbefore described.


From the same point of intersection, Cor. No. 2, bears N. 45° 28' W., 7.05 chs. dist., monumented with an iron post, 2 ins. diam., extending 24 ins. above ground, with cap mkd.




11.50 Clay Canyon, 30 lks. wide, 3 ft. deep, drains S. 60° E.; asc. over NE slope. Enter dense timber.

16.50 Trail road, bears N. 65° W. and S. 65° E.

19.71 Intersect line 2-3, Bow Wow lode, mineral survey No. 3412, at a point from which Cor. No. 3, bears N. 25° 35' E., 3.93 chs. dist., monumented with an iron post, 1 in. diam., extending 12 ins. above ground, with brass cap mkd.



From the same point of intersection Cor. No. 2, bears S. 25° 35' W., 5.13 chs. dist., monumented with an iron post, 1 in. diam., extending 12 ins. above ground, with brass cap mkd.




27.12 Intersect line 1-2, Bow Wow lode, mineral survey No. 3412, at a point from which Cor. No. 2, bears S. 48° 13' E., 6.96 chs. dist., hereinbefore described.

From the same point of intersection, Cor. No. 1, identical with Cor. No. 1, Lightning Rod lode, same survey, bears N. 48° 13' W., 15.71 chs. dist., monumented with a partially decayed wood post, 4 x 4 ins., 4 ft. long, in mound of stone, with illegible scribe marks on NE face.

from which

An iron post, 1 in. diam., extending 15 ins. above ground, bears N. 64° 42' E., 45 lks. dist., with brass cap mkd.

RE-SURV



38.50 Spur, slopes S. 60° E.; thence along S slope.

40.24 The cor. of secs. 21, 22, 27, and 28.

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
	N. 89° 48' W., bet. secs. 21 and 28. Over mountainous land through dense timber; asc. along general S slope.
5.00	Top of ascent slopes S; desc. over SW slope.
11.00	Head of Wells Canyon, drains S. 65° E.; asc. over NE slope.
28.00	Ridge, bears N and S; desc. over W slope.
29.51	Intersect line 12, Columbian lode, mineral survey No. 3183, at a point from which Cor. No. 1, bears N. 2° 30' W., 9.24 chs. dist., monumented with a partially decayed wood post, 4 x 4 ins., 4 ft. long, in mound of stone from which the original bearing trees A juniper, 10 ins. diam., bears N. 89° E., 24 lks. dist., scribed 1-3183 BT. A juniper, 6 ins. diam., bears S. 49° 30' E., 42½ lks. dist., scribed 1-3183 BT. From the same point of intersection, Cor. No. 2, bears S. 2° 30' E., 5.94 chs. dist., monumented with a badly decayed post in a small mound of stone. from which the remaining original bearing tree A burned juniper stump, 12 ins. diam., 3 ft. high, bears N. 22° W., 13½ lks. dist., scribe marks BT visible.
36.00	Trail road, bears N and S, 1.00 ch.; thence SW.
37.20	Wash, 20 lks. wide, 4 ft. deep, drains S.
39.45	Same trail road, bears S. 50° W. and N. 50° E.
39.70	Point for the ¼ sec. cor. of secs. 21 and 28, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 6 S R 3 W S 21 ¼ ——— S 28 1975 From this cor., Cor. No. 6, Columbian lode, mineral survey No. 3183, bears N. 32° 25' E., 5.10 chs. dist., monumented with a decayed wood post, 4 x 4 ins., 4 ft. long, in mound of stone, scribed 6-3183.

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

from which the original bearing trees

A juniper, 8 ins. diam., bears N. 36° E., $29\frac{1}{2}$ lks. dist., scribed 6-3183 BT.

A juniper, 8 ins. diam., bears S. 52° W., $53\frac{1}{2}$ lks. dist., scribed 6-3183 BT. (Record, S. $51^{\circ} 56'$ E., 35.5 ft.)

From this same cor., Cor. No. 5, Columbian lode, same survey, bears S. $10^{\circ} 10'$ E., 7.41 chs. dist., monumented with a badly decayed wood post, 4 x 4 ins., 4 ft. long, in mound of stone.

from which a bearing tree of no record

A juniper limb, 2 ins. diam., bears S. 50° W., 10 lks. dist., scribed 3183 BT.

Asc. over SE slope.

47.00 Top of ascent, slopes S; thence along S slope.

48.49 The closing cor. of secs. 21 and 28, on the old Ft. Crittenden Military Reservation Boundary, monumented with a mound of stone only. This point is harmoniously related to existing original corners and is accepted as the best available evidence of the original closing corner.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 6 S R 3 W

S 28	S 21	C
	S 28	C
	OMRB	

1974

Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, E of cor

From this cor., the 39th mile post on the old Ft. Crittenden Military Reservation Boundary, bears N. $1^{\circ} 05'$ E., 17.21 chs. dist., hereinbefore described.

From the cor. of secs. 21, 22, 27, and 28.

North, bet. secs. 21 and 22.

Over mountainous land through dense timber; asc. over S slope.

3.65 Ridge, bears W and S. 50° E.; desc. over NE slope.

11.10 Intersect line 1-2, Lightning Rod lode, mineral survey No. 3412, at a point from which Cor. No. 1, identical with Cor. No. 1, Bow Wow lode, same survey, bears S. $65^{\circ} 12'$ E., 1.56 chs. dist., heretofore described.

From the same point of intersection, Cor. No. 2, bears N. $65^{\circ} 12'$ W., 18.89 chs. dist., monumented with an iron post, 1 in. diam., extending 12 ins. above ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

ORIG SURV



Remains of original wood post, 4 x 4 x 18 ins., lying alongside, scribed 2-3412

from this cor., an iron post, 1 in. diam., extending 15 ins. above ground, bears N. 81° 20' E., 0.485 chs. dist., with brass cap mkd.

RE - SURV



12.50 Trail road, bears E and W; leave dense timber.

14.00 Clay Cayon, 30 lks. wide, 4 ft. deep, drains S. 85° E.; asc. over S slope, enter scattered timber.

28.00 E side of saddle on spur, slopes S. 60° E.; desc. over NE slope.


39.33 Intersect line 3-4, Bruno No. 1 lode, mineral survey No. 3412, at a point from which Cor. No. 3, bears N. 64° 41' W., 6.71 chs. dist., monumented with a squared cedar post, 2 ins. diam., 3 ft. long, in small mound of stone.

from which the original bearing tree

A juniper, 12 ins. diam., bears S. 15° W., 142½ lks. dist., scribed 3-3412 BT.

At the claim corner point

Set a Copperweld monument, 30 ins. long, 5/8 ins. diam., 18 ins. in the ground, in a mound of stone, 2 ft. base, with brass cap mkd.



from which

An iron post, 1 in. diam., extending 12 ins. above ground, bears N. 80° 22' E., 0.61 chs. dist., with brass cap mkd.

RE-SURV



From the same point of intersection, Cor. No. 2, Clinton lode, mineral survey No. 3169, identical with Cor. No. 4, Bruno No. 2 lode, mineral survey No. 3412, on line 3-4 of Bruno No. 1 lode, same survey, bears S. 64° 41' E., 2.04 chs. dist., monumented with a mound of stone only.

from which the original bearing tree


A juniper, 12 ins. diam., bears S. 30° 30' W., 248½ lks. dist., scribed BT-4-3412-2-3169. (Record, S. 30° 25' W.).

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah


CHAINS

At the claim corner point

Set a Copperweld monument, 30 ins. long, 5/8 ins. diam.,
24 ins. in the ground, with brass cap mkd.



From this cor., an iron post, 1 in. diam., extending 18
ins. above ground, in wash draining SE, bears
N. 82° 36' E., 0.60 chs. dist., with brass cap mkd.




40.82

The 1/4 sec. cor. of secs. 21 and 22, monumented with a
mound of stone, 1 1/2 ft. base, 1 ft. high. This point is
harmoniously related to existing original corners and
is accepted as the best available evidence of the original
corner.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.
in the ground, and in a collar of stone, with brass cap
mkd.

T 6 S R 3 W




North, beginning new measurement.

0.60 Wash, 30 lks. wide, 6 ft. deep, drains S. 45° E.; asc.
over SW slope.

1.87 Intersect line 2-3, Clinton lode, mineral survey No.
3169, at a point from which Cor. No. 2, bears
S. 23° 31' E., 4.60 chs. dist., hereinbefore described.

From the same point of intersection, Cor. No. 3, bears
N. 23° 31' W., 0.05 chs. dist., the cor. point is at
proportionate distance based on the Grant Boundary method;
there is no remaining evidence of the original corner.

Set a Copperweld monument, 30 ins. long, 5/8 ins. diam.,
20 ins. in the ground, with brass cap mkd.



1.92 Intersect line 3-4, Clinton lode, mineral survey No. 3169,
at a point from which Cor. No. 3, bears N. 84° 37' W.,
0.02 chs. dist., hereinbefore described.

From the same point of intersection, Cor. No. 4, identical
with Cor. No. 5, Mugwump No. 1 lode, same survey, bears
S. 84° 37' E., 11.38 chs. dist., reestablished from the
original bearing trees

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah


CHAINS

A juniper stump, 12 ins. diam., 3 ft. high, bears
N. $34^{\circ} 46'$ E., 52 lks. dist., scribed
BT-3412-3-5-4-1 3169.

A juniper, 12 ins. diam., bears N. $82^{\circ} 45'$ W., 97
lks. dist., scribed BT-3412-3-5-4-1 3169. (Record,
N. $82^{\circ} 38'$ W.).

At the corner point

Set a Copperweld monument, 30 ins. long, $5/8$ ins. diam.,
24 ins. in the ground, with brass cap mkd.




From this cor., Cor. No. 1, Clinton lode, same survey,
bears S. $24^{\circ} 25'$ E., 0.24 chs. dist., reestablished from
the original bearing trees

A juniper stump, 12 ins. diam., 3 ft. high, bears
N. $16^{\circ} 30'$ E., 68 lks. dist., scribed
BT-3412-3-5-4-1 3169.

A juniper, 12 ins. diam., bears N. 72° W., 112
lks. dist., scribed BT-3412-3-5-4-1 3169. (Record,
N. $72^{\circ} 03'$ W.).


At the claim corner point

Set a Copperweld monument, 30 ins. long, $5/8$ ins. diam.,
24 ins. in the ground, with brass cap mkd.



4.05 Intersect line 6-7, Mugwump No. 1 lode, mineral survey
No. 3169, at a point from which Cor. No. 6, bears
S. $23^{\circ} 47'$ E., 2.42 chs. dist., at a single proportionate
distance; there is no remaining evidence of the original
corner.

Set a Copperweld monument, 30 ins. long, $5/8$ ins. diam.,
20 ins. in the ground, with brass cap mkd.



From this cor., Cor. No. 3, Clinton lode, same survey,
bears N. $84^{\circ} 37'$ W., 1.01 chs. dist., hereinbefore
described.


From the same point of intersection, Cor. No. 7, identical
with Cor. No. 13, Mugwump No. 2 lode, and Cor. No. 14,
Alpha No. 1 lode, same survey, bears N. $23^{\circ} 47'$ W., 20.16
chs. dist., monumented with a partially decayed wood post,
4 x 4 ins., 4 ft. long, in small mound of stone, scribed
7-13-14-3169.

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

- from which the original bearing trees
- A juniper, 12 ins. diam., bears S. 14° W., 46 lks. dist., scribed 7-13-14-3169 BT. (Record, S. 13° 50' W.).
- A leaning juniper, 10 ins. diam., bears N. 13° W., 23½ lks. dist., scribed 7-3169 BT on partially healed blaze. (Record, N. 12° 55' W.).
- 22.30 Point of spur, slopes S. 45° E.; desc. over NE slope.
- 25.58 Intersect line 9-10, Mugwump No. 2 lode, mineral survey No. 3169, at a point from which Cor. No. 9, identical with Cor. No. 8, Mugwump No. 1 lode, same survey, bears S. 28° 46' E., 4.29 chs. dist., monumented with a wood post, 4 x 4 ins., 4 ft. long, set in a mound of stone, scribed 8-9-3169.
- from which an original bearing tree
- A juniper, 12 ins. diam., bears S. 2° 45' E., 80 lks. dist., scribed 8-9-3169 BT.
- From this cor., Cor. No. 5, Mugwump No. 1 lode, identical with Cor. No. 4, Clinton Lode, same survey, bears S. 23° 50' E., 22.92 chs. dist., hereinbefore described.
- From the same point of intersection, Cor. No. 10, bears N. 28° 46' W., 17.90 chs. dist., hereinafter described.
- 26.15 Intersect line 4-5, Moonshine lode, mineral survey No. 3668, at a point from which Cor. No. 4, bears N. 55° 29' W., 0.61 chs. dist., at proportionate distance; there is no remaining evidence of the original corner.
- Set a Copperweld monumented, 30 ins. long, 5/8 ins. diam., 24 ins. in the ground, with brass cap mkd.
- 3668
4 M
- From this cor., Cor. No. 9, Mugwump No. 2 lode, survey No. 3169, bears S. 28° 46' E., 5.33 chs. dist., hereinbefore described.
- From the same point of intersection, Cor. No. 5, identical with Cor. No. 2, Bloomers lode, same survey, bears S. 55° 29' E., 2.80 chs. dist., monumented with a hewed cedar post, 4 ins. diam., 4 ft. long, in mound of stone, scribed 5-2-3668.
- from which the original bearing trees
- A juniper, 6 ins. diam., bears S. 25° 40' E., 30½ lks. dist., scribed 5-2-3668 BT.
- A juniper, 7 ins. diam., bears S. 24° 46' W., 21 lks. dist., scribed 5-2-3668 BT.
- 28.80 Draw, drains E; asc. over SE slope.
- 36.96 Intersect line 1-2, Moonshine lode, mineral survey No. 3668, at a point from which Cor. No. 2, bears N. 54° 49' W., 5.33 chs. dist., monumented with a partially decayed squared cedar post, 3 ins. diam., in small mound of earth and stones, dimly scribed 3668.

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS						
	<p>At the claim corner point</p> <p>Set a Copperweld monument, 30 ins. long, 5/8 ins. diam., 18 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">  <p>M 2 3668</p> </div> <p>From this cor., point for Cor. No. 3, on line 9-10, Mugwump No. 2 lode, mineral survey No. 3169, bears S. 44° 34' W., 3.28 chs. dist., hereinafter described.</p> <p>From the same point of intersection, Cor. No. 1, identical with Cor. No. 1, Bloomers lode, same survey, bears S. 54° 49' E., 10.72 chs. dist., monumented with a squared cedar post, 3 ins. diam., 3 ft. long, in mound of stone, scribed 1-1-3668.</p> <p>37.60 Spur, slopes E; desc. over N slope.</p> <p>40.72 The cor. of secs. 15, 16, 21, and 22, monumented with a limestone, 14 x 8 x 3 ins., firmly set 10 ins. in the ground, and plainly mkd. 3 notches on S and E edges, and witnessed by a small mound of stone to the W.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p> <div style="text-align: center;"> <p>T 6 S R 3 W</p> <table border="1" style="margin: auto;"> <tr> <td>S 16</td> <td>S 15</td> </tr> <tr> <td>S 21</td> <td>S 22</td> </tr> </table> <p>1973</p> </div> <p>Bury the mkd. stone alongside the iron post.</p>	S 16	S 15	S 21	S 22	
S 16	S 15					
S 21	S 22					
	<p>From the cor. of secs. 14, 15, 22, and 23.</p> <p>N. 89° 51' W., bet. secs. 15 and 22.</p> <p>Over gently rolling land through widely scattered timber.</p> <p>5.90 Manning Canyon, 30 lks. wide, 5 ft. deep, drains S. 25° E.</p> <p>24.70 Gravel road, bears N. 20° E. to Mercur and S. 20° W. to State Highway No. 73, enter medium dense timber.</p> <p>28.00 Trail road, bears N. 55° W. and S. 55° E.</p> <p>38.00 Wash, drains SE.</p> <p>40.17 Point for the ¼ sec. cor. of secs. 15 and 22 at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>					

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
	<p style="text-align: center;">T 6 S R 3 W</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S 15}{S 22}$</p> <p style="text-align: center;">1973</p>
	<p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor Asc. over steep E slope.</p>
76.15	Spur, slopes N. 80° E; thence along N slope.
80.34	The cor. of secs. 15, 16, 21, and 22.
	<p>S. 89° 59' W., bet. secs. 16 and 21.</p> <p>Over mountainous land through scattered timber. Desc. along N slope.</p>
8.31	<p>Intersect line 9-10, Mugwump No. 2 lode, mineral survey No. 3169, at a point from which Cor. No. 10, bears N. 28° 46' W., 0.63 chs. dist., reestablished from the original bearing tree</p> <p style="padding-left: 40px;">A dead pinon, 30 ins. diam., bears N. 73° 54' W., 199½ lks. dist., scribed 10-3169 BT.</p> <p>At the claim corner point</p> <p>Set a Copperweld monument, 30 ins. long, 5/8 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> </div> <p>From this cor., Cor. No. 11, Mugwump No. 2 lode, same survey, bears N. 84° 41' W., 8.28 chs. dist., monumented with a wood post, 4 x 4 ins., 4 ft. long, scribed 11-3169.</p> <p>from which the remaining original bearing tree</p> <p style="padding-left: 40px;">A juniper, 12 ins. diam., bears S. 32° 15' E., 56½ lks. dist., scribed 11-3169 BT. (Record, S. 32° 20' E.)</p> <p>From the same point of intersection, Cor. No. 9, bears S. 28° 46' E., 21.56 chs. dist., hereinbefore described.</p> <p>From the same point of intersection, point for Cor. No. 3, Moonshine lode, mineral survey No. 3668, bears S. 28° 46' E., 3.45 chs. dist., at proportionate distance; there is no remaining evidence of the original corner. Point not monumented.</p> <p>Asc. over steep NE slope.</p>
15.40	Spur, slopes S. 45° E. from nearly W; desc. along S slope.
23.50	Spur, slopes S; desc. over W slope.
30.00	Draw, drains S; asc. over SE slope.
39.00	Top of ascent slopes S; desc. over SW slope.

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS		
39.42	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 21, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 6 S R 3 W</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S\ 16}{S\ 21}$</p> <p style="text-align: center;">1975</p> <p>Continue descent over SW slope.</p>	
42.50	Head of draw, drains S. 45° E.; asc. over E slope.	
45.50	Ridge, bears S and curves NE.	
45.83	<p>The closing cor. of secs. 16 and 21, on the old Ft. Crittenden Military Reservation Boundary, monumented with a mound of stone. This point is harmoniously related to existing original corners, and is accepted as the best available evidence of the original closing corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 6 S R 3 W</p> <p style="text-align: center;">S 21 $\frac{S\ 16\ C}{S\ 21\ C}$ OMRB</p> <p style="text-align: center;">1974</p> <p>From this cor., angle point No. 18, on the old Ft. Crittenden Military Reservation boundary, bears S. $38^\circ 19'$ W., 0.62 chs. dist., hereinbefore described.</p>	
3.50 13.00 20.00 28.00 31.00 37.90	<p>From the cor. of secs. 15, 16, 21, and 22.</p> <p>N. $0^\circ 11'$ E., bet. secs. 15 and 16.</p> <p>Over mountainous land through scattered timber. Desc. over steep N slope.</p> <p>Deep draw, drains N. 60° E.; asc. over steep SE slope.</p> <p>Spur, slopes N. 55° E.; desc. over NW slope.</p> <p>Draw, drains N. 27° E.; asc. over SE slope.</p> <p>Point of spur, slopes N. 45° E.; desc. over N slope.</p> <p>Draw, drains E; asc. over S slope.</p> <p>Spur, slopes S. 60° E.; desc. over NE slope.</p>	

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

39.89

The $\frac{1}{4}$ sec. cor. of secs. 15 and 16, monumented with a limestone, 16 x 12 x 4 ins., set 3 ins. in the ground, plainly mkd. $\frac{1}{4}$ on W face.

from which the original bearing trees

A juniper stump, 24 ins. diam., 12 ins. high, bears N. $26^{\circ} 30'$ E., 40 lks. dist., scribed BT. (Record, 42 lks.)

A juniper stump, 10 ins. diam., 15 ins. high, bears S. 74° E., 30 lks. dist., scribe marks T, remaining.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, $3\frac{1}{2}$ ft. base, to top of brass cap, mkd.

T 6 S R 3 W

$\frac{1}{4}$
S 16 | S 15

1973

Bury the mkd. stone alongside the iron post.

N. $0^{\circ} 07'$ W., beginning new measurement.

Continue descent over NE slope.

7.00 Draw, drains N. 45° E.

15.00 Draw, drains E.; desc. along general E slope.

22.00 Draw, drains S. 75° E.; asc. over S slope.

26.00 Gravel road, on curve, bears NW to State Highway No. 73 and curves SW to Mercur, also, point of spur, slopes E, desc. over NE slope.

33.70 Intersect line 14-15, Blucher lode, mineral survey No. 3157, at a point from which Cor. No. 14, bears S. $78^{\circ} 43'$ W., 1.52 chs. dist., reestablished from the remaining original bearing tree

A juniper stump, 3 ins. diam., 10 ins. high, bears S. $73^{\circ} 25'$ E., $95\frac{1}{2}$ lks. dist., scribed BT-3157-14.

At the claim corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

COR-14
BLUCHER
3157

1974

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS								
	<p>From the same point of intersection, Cor. No. 15, Blucher lode, same survey, identical with Cor. No. 1, W K No. 5 lode, mineral survey No. 3357, bears N. 78° 43' E., 7.54 chs. dist., monumented with a badly decayed wood post, 4 x 4 ins., 4 ft. long, in a mound of stone.</p>							
37.00	Wash, drains E.							
40.30	Gravel road, bears S. 32° W. to Mercur and curves NE to State Highway No. 73.							
40.42	<p>Point for the cor. of secs. 9, 10, 15, and 16, falls in gravel road reestablished from the remaining original bearing tree</p> <p>A juniper stump, 8 ins. diam., bears S. 31° W., 96 lks. dist., with blaze on NE face.</p> <p>Point verified by tie made to Cor. No. 14, Blucher lode, mineral survey No. 3157, which bears S. 11° 52' W., 7.17 chs. dist., hereinbefore described. (Record, 473 ft.)</p> <p>At the corner point</p> <p>Set a brass tablet, 3 ins. diam., 12 ins. below surface of gravel road, mkd.</p> <div style="text-align: center;"> <p>T 6 S R 3 W</p> <table border="1" style="margin: auto;"> <tr> <td>S 9</td> <td> </td> <td>S 10</td> </tr> <tr> <td>S 16</td> <td> </td> <td>S 15</td> </tr> </table> <p>1973</p> </div> <p>from which</p> <p>A juniper limb, 8 ins. diam., bears N. 88° 30' E., 128 lks. dist., scribed T6S R3W S10 BT.</p> <p>A juniper, 10 ins. diam., bears S. 29° W., 104 lks. dist., scribed T6S R3W S16 BT.</p>	S 9		S 10	S 16		S 15	
S 9		S 10						
S 16		S 15						
	<p>From the cor. of secs. 10, 11, 14, and 15.</p> <p>N. 89° 06' W., bet. secs. 10 and 15.</p> <p>Over mountainous land, through medium dense timber. Desc. over NW slope.</p>							
7.00	Draw, drains S; asc. over SE slope.							
9.00	Point of spur, slopes S; desc. over SW slope.							
13.00	Draw, drains S; asc. over steep SE slope.							
33.50	Small knoll, on point of spur, slopes W; desc. over steep W slope.							
39.78	<p>The ¼ sec. cor. of secs. 10 and 15, monumented with a limestone, 24 x 14 x 12 ins., firmly set 10 ins. in the ground and plainly mkd. ¼ on N face.</p> <p>At the corner point</p>							

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 6 S R 3 W

¼ $\frac{S\ 10}{S\ 15}$

1973

Bury the mkd. stone alongside the iron post, and raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.

From this cor., a capped spring and water tank, bears S. 2° E., 16.00 chs. dist.

N. 89° 51' W., beginning new measurement.

Continue descent over steep W slope. Timber becomes widely scattered.

6.63 Intersect line 1-4, Solution lode, mineral survey No. 4498, at a point from which Cor. No. 4, bears N. 38° 12' W., 12.63 chs. dist., hereinafter described.

From the same point of intersection, Cor. No. 1, identical with Cor. No. 1, Zinc lode, and Cor. No. 1, Cyanide lode, same survey, bears S. 38° 12' E., 10.07 chs. dist., hereinafter described.

7.50 Draw, drains S. 18° W., thence over rolling land. Enter sagebrush and scattered patches of oak brush.

18.00 Wash, 30 lks. wide, 4 ft. deep, drains S. 10° E.

18.19 Intersect line 2-3, Solution lode, mineral survey No. 4498, at a point from which Cor. No. 3, bears N. 38° 13' W., 4.67 chs. dist., hereinafter described.

From the same point of intersection, Cor. No. 2, identical with Cor. No. 2, Cyanide lode, same survey, bears S. 38° 13' E., 18.08 chs. dist., hereinafter described.

27.00 Gravel road, bears N. 48° W. to Mercur and S. 48° E. to State Highway No. 73.

27.60 Intersect line 3-4, W.K. No. 5 lode, mineral survey No. 3357, at a point from which Cor. No. 4, bears S. 27° 20' E., 4.29 chs. dist., monumented with a decayed wood post, 4 x 4 ins., 4 ft. long, in small mound of stone.

At the claim corner point

Set a Copperweld monument, 30 ins. long, 5/8 ins. diam., 20 ins. in the ground, with brass cap mkd.



W K-5
3357

4

From the same point of intersection, Cor. No. 3, identical with Cor. No. 4, W. K. No. 4 lode, same survey, bears N. 27° 20' W., 14.45 chs. dist., monumented with remains of wood post, in mound of stone.

At the claim corner point

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah


CHAINS		
	<p>Set a Copperweld monument, 30 ins. long, 5/8 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> 	
30.50	Manning Canyon, 20 lks. wide, 6 ft. deep, drains S. 30° E.; asc. over SE slope.	
40.17	The cor. of secs. 9, 10, 15, and 16.	
	N. 89° 58' W., bet. secs. 9 and 16.	
	Over mountainous land through dense oak brush undergrowth and scattered timber. Asc. over E slope.	
4.76	Intersect line 13-14, Blucher lode, mineral survey No. 3157, at a point from which Cor. No. 14, bears S. 25° 06' E., 7.75 chs. dist., hereinbefore described.	
	From the same point of intersection, Cor. No. 13, bears N. 25° 06' W., 10.80 chs. dist., monumented with a badly decayed wood post, 4 x 4 ins., 3 ft. long, with scribe marks 13 visible on one face.	
	from which an original bearing tree	
	A juniper stump, 8 ins. diam., bears N. 22° 30' E., 106 lks. dist., with scribe marks BT remaining.	
6.00	Wash, drains S. 55° E.; asc. over NE slope.	
6.54	Intersect line 11-12, Radatzky lode, mineral survey No. 3157, at a point from which Cor. No. 12, bears N. 25° 00' W., 10.41 chs. dist., monumented with a wood post, 4 x 4 ins., 4 ft. long, in a mound of stone, with scribe marks decayed away.	
	From the same point of intersection, Cor. No. 11, bears S. 25° 00' E., 10.68 chs. dist., at proportionate distance based on the Grant Boundary method; there is no remaining evidence of the original claim corner.	
	Set a Copperweld monument, 30, ins. long, 5/8 ins. diam., 24 ins. in the ground, with brass cap mkd.	
		
	from which	
	A juniper, 4 ins. diam., bears N. 82° E., 49½ lks. dist., scribed 11-3157 BT.	
12.00	Gravel road, bears S. 30° E. to State Highway No. 73 and N. 30° W. to Mercur.	
15.42	Intersect line 9-10, Radatzky lode, mineral survey No. 3157, at a point from which Cor. No. 9, bears N. 22° 02' W., 8.51 chs. dist., monumented with a badly decayed wood post, 4 x 4 ins., 4 ft. long, in small mound of stone.	

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

At the claim corner point


Set a Copperweld monument, 30 ins. long, 5/8 ins. diam.,
18 ins. in the ground, with brass cap mkd.



From Cor. No. 9 of Radaztky lode, Cor. No. 12, bears
N. 78° 37' E., 7.83 chs. dist., hereinbefore
described.

From the same point of intersection, Cor. No. 10, bears
S. 22° 02' E., 12.35 chs. dist., at proportionate distance
based on the Grant Boundary method; there is no remaining
evidence of the original claim corner.

Set a Copperweld monument, 30 ins. long, 5/8 ins. diam.,
20 ins. in the ground, and in a collar of stone, with
brass cap mkd.




From Cor. No. 10 of Radaztky lode, Cor. No. 11, bears
N. 78° 37' E., 8.94 chs. dist., hereinbefore
described.

- 18.77 Intersect line 1-2, Thomas Gundry lode, mineral survey
No. 3250, at a point from which Cor. No. 1, identical
with Cor. No. 2, Brooklin lode, same survey, bears
N. 16° 10' E., 2.75 chs. dist., reestablished at a point
S. 6° 34' E., 5.28 chs. (record, 348.6 ft.) dist. from
Cor. No. 9, Radaztky lode, mineral survey No. 3157,
hereinbefore described.

At the claim corner point


Set a Copperweld monument, 30 ins. long, 5/8 ins. diam.,
24 ins. in the ground, with brass cap mkd.



From the same point of intersection, Cor. No. 2, bears
S. 16° 10' W., 1.37 chs. dist., monumented with a charred
post, 4 x 4 ins., 2 ft. long, in mound of stone.

At the claim corner point

Set a Copperweld monument, 30 ins. long, 5/8 ins. diam.,
20 ins. in the ground, with brass cap mkd.



Asc. over NE slope.


- 32.65 Intersect line 3-4, Thomas Gundry lode, mineral survey
No. 3250, at a point from which Cor. No. 3, bears
S. 63° 58' E., 11.61 chs. dist., monumented with a decayed
post, 4 x 4 ins., 3 ft. long, in small mound of earth
and stones.

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

At the claim corner point


Set a Copperweld monument, 30 ins. long, 5/8 ins. diam.,
18 ins. in the ground, with brass cap mkd.



From the same point of intersection, Cor. No. 4, bears
N. 63° 58' W., 8.69 chs. dist., reestablished at a point
N. 45° 04' E., 3.88 chs. (record, 256.1 ft.) dist., from
Cor. No. 6, Red Bird No. 2 lode, mineral survey No. 3620,
monumented with a wood post, 4 x 4 ins., 4 ft. long, with
illegible scribing visible.

At the claim corner point

Set a Copperweld monument, 30 ins. long, 5/8 ins. diam.,
24 ins. in the ground, with brass cap mkd.



33.00 Top of ascent, slopes N; desc. along N slope.

39.52 The 1/4 sec. cor. of secs. 9 and 16, monumented with a
limestone, 24 x 10 x 3 ins., firmly set 8 ins. in the
ground, and plainly mkd. 1/4 on N face.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins.
in the ground, and in a collar of stone, with brass cap
mkd.

T 6 S R 3 W

1/4 $\frac{S 9}{S 16}$


1974

Bury the mkd. stone alongside the iron post.

From this corner, Cor. No. 6, Red Bird No. 2 lode, mineral
survey No. 3620, bears N. 74° 33' W., 3.84 chs. dist.,
monumented with a wood post, 4 x 4 ins., 4 ft. long,
in mound of earth, scribed 6-3620 on SW face.

At the claim corner point


Set a Copperweld monument, 30 ins. long, 5/8 ins. diam.,
20 ins. in the ground alongside wood post, with brass cap
mkd.



N. 89° 51' W., beginning new measurement.

Continue descent along N slope, changing to NW slope.

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah


CHAINS	
2.00	Head of draw, drains NE; asc. over steep NE slope.
3.44	<p>Intersect line 1-6, Red Bird No. 2 lode, mineral survey No. 3620, at a point from which Cor. No. 6, bears N. 14° 16' W., 1.05 chs. dist., hereinbefore described.</p> <p>From the same point of intersection, Cor. No. 1, bears S. 14° 16' E., 8.05 chs. dist., monumented with a mound of stone.</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears S. 69° 30' W., 117 lks. dist., scribed 1-3620 BT.</p> <p>At the claim corner point</p> <p>Set a Copperweld monument, 30 ins. long, 5/8 ins. diam., 12 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;">  </div>
24.05	<p>Intersect line 5-6, Mercur Boy No. 4 lode, mineral survey No. 3620, at a point from which Cor. No. 5, identical with Cor. No. 3, Mercur Boy No. 1 lode, same survey, bears S. 33° 22' E., 1.36 chs. dist., hereinafter described.</p> <p>From the same point of intersection, Cor. No. 6, bears N. 33° 22' W., 5.54 chs. dist., monumented with a Copperweld monument, hereinafter described.</p>
31.40	<p>The closing cor. of secs. 9 and 16, identical with angle point No. 10, on the old Ft. Crittenden Military Reservation Boundary, hereinbefore described.</p>
<p>From the cor. of secs. 9, 10, 15, and 16.</p>	
<p>N. 0° 23' E., bet. secs. 9 and 10.</p>	
<p>Over rolling land through dense oak brush and scattered timber.</p>	
9.00	Low spur, slopes E; desc. over NE slope.
19.00	Trail road, bears N. 60 W. and S. 60° E.
23.00	Manning Canyon, 40 lks. wide, 6 ft. deep, drains S. 25° E.; asc. over SW slope. Enter medium dense timber.
23.33	<p>Intersect line 1-4, W.K. No. 4 lode, mineral survey No. 3357, at a point from which Cor. No. 4, identical with Cor. No. 3, W.K. No. 5 lode, same survey, bears S. 28° 46' E., 12.00 chs. dist., hereinbefore described.</p>
<p>From the same point of intersection, Cor. No. 1, identical with Cor. No. 5, W.K. No. 3 lode, same survey, bears N. 28° 46' W., 9.83 chs. dist., reestablished at a point (record tie) S. 30° 26' W., 9.56 chs. dist., (record, 631.2 ft.) from the ¼ sec. cor. of secs. 9 and 10.</p>	

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

At the claim corner point

Set a Copperweld monument, 30 ins. long, 5/8 ins. diam.,
24 ins. in the ground, with brass cap mkd.




36.00 Draw, drains S. 60° W.; asc. over SW slope.

40.19 The 1/4 sec. cor. of secs. 9 and 10, monumented with a
limestone, 20 x 18 x 6 ins., firmly set 10 ins. in the
ground, and plainly mkd. 1/4 on W face, and witnessed by
a small mound of stone to the W.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 12 ins.
in the ground to bedrock, in a mound of stone, 3 1/2 ft.
base, to top of brass cap, mkd.

T 6 S R 3 W



1973

Place the mkd. stone in mound of stone alongside the
iron post.

N. 0° 08' W., beginning new measurement.

1.00 Draw, drains S. 45° W.; asc. over SW slope.

15.00 Spur, slopes W; desc. over N slope.

23.00 Deep draw, drains W; asc. over steep S slope.


37.50 High spur ridge, slopes W; desc. over N slope.

39.24 The cor. of secs. 3, 4, 9, and 10, monumented with a
sandstone, 16 x 10 x 8 ins., firmly set 5 ins. in the
ground and plainly mkd. 5 notches on S and 3 notches on
E edges.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 10 ins.
in the ground to bedrock, in a mound of stone, 3 1/2 ft.
base, to top of brass cap, mkd.

T 6 S R 3 W



1975

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
	Place the mkd. stone in mound of stone alongside the iron post.
	From the cor. of secs. 2, 3, 10, and 11. N. 89° 38' W., bet. secs. 3 and 10. Over mountainous land, through dense oak brush. Asc. over steep NE slope.
18.00	High ridge, between Manning and Pole Canyons, bears S and N. 50° W.; desc. along S slope.
28.00	Spur, slopes S. 60° W.; desc. over NW slope.
40.42	Point for the ¼ sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.
	T 6 S R 3 W ¼ $\frac{S\ 3}{S\ 10}$ 1975
	Continue descent over NW slope.
47.00	Draw, drains S. 60° W.; asc. over SE slope.
64.00	Spur, slopes W from N. 65° E.; desc. along N slope.
80.84	The cor. of secs. 3, 4, 9, and 10.
	N. 1° 03' E., bet. secs. 3 and 4. Over mountainous land through dense oak brush. Desc. over steep N slope.
5.50	Draw, drains W; asc. over S slope.
10.00	Point of spur, slopes S. 30° E. from N; asc. along E slope.
16.00	Draw, drains S. 10° E. from N. 25° E.
39.67	Point for the ¼ sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, to top of brass cap, mkd.
	T 6 S R 3 W ¼ S 4 S 3 1975


Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS		
75.70	<p>Continue ascent along spur.</p> <p>The closing cor. of secs. 3 and 4, on the First Standard Parallel South, identical with an angle point on the old Ft. Crittenden Military Reservation Boundary and also identical with the original standard closing cor. of sec. 33, T. 5 S., R. 3 W., hereinbefore described.</p>	
	<p>Point for the N $\frac{1}{4}$ sec. cor. of sec. 3, on the First Standard Parallel South, at mid point between the closing corner of secs. 2 and 3, and the closing cor. of secs. 3 and 4.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 3$\frac{1}{2}$ ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 5 S R 3 W ----- $\frac{1}{4}$ S 3 ----- T 6 S R 3 W 1975</p> <p>From this cor., the standard $\frac{1}{4}$ sec. cor. of sec. 34, T. 5 S., R. 3 W., bears S. 89° 50' E., 14.69 chs. dist., hereinbefore described.</p>	
	<p style="text-align: center;">(Reestablishment of the Survey Executed by C.L. Craig in 1856 and the Resurvey Executed by Robert Gorkinski in 1892)</p> <p>From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., monumented with an iron post, 2 ins. diam., extending 6 ins. above ground, with brass cap mkd. as described in the official record of the 1918 resurvey.</p> <p>N. 0° 08' E., bet. secs. 32 and 33.</p> <p>Over rolling land through scattered timber.</p> <p>0.10 Wash, 10 lks. wide, 3 ft. deep, drains S. 40° W.</p> <p>26.50 Trail road, on curve, bears N. 43° W. and S. 65° E.</p> <p>40.17 The $\frac{1}{4}$ sec. cor. of secs. 32 and 33, monumented with a sandstone, 15 x 10 x 6 ins., firmly set in a small mound of stone, plainly mkd. $\frac{1}{4}$ on W face.</p> <p>from which the original bearing trees</p> <p style="padding-left: 40px;">A juniper, 8 ins. diam., bears S. 15° W., 69 lks. dist., scribed $\frac{1}{4}$ S BT.</p> <p style="padding-left: 40px;">A juniper, 10 ins. diam., bears S. 87° 30' W., 59 lks. dist., scribed $\frac{1}{4}$ S BT.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

T 6 S R 3 W



1974

Bury the mkd. stone alongside the iron post, and raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.


From this cor., Cor. No. 3, Katie No. 1 lode, mineral survey No. 3137, bears S. 83° 13' W., 17.91 chs. dist., reestablished from the original bearing trees

A juniper, 15 ins. diam., bears N. 39° 15' W., 163½ lks. dist., scribed 3-3137 BT.

A juniper, 15 ins. diam., bears N. 31° W., 194½ lks. dist., scribed 3-3137 BT. (Record, N. 30° 50' W.)

At the claim corner point

Set a Copperweld monument, 30 ins. long, 5/8 ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.



N. 0° 05' E., beginning new measurement.

Asc. over S slope.

- 6.40 Trail road, on spur, bears N. 50° E. and S. 50° W.; desc. over NW slope.
- 10.00 Draw, drains S. 50° W.; asc. over SE slope.
- 15.00 Small spur, slopes S. 40° W.; desc. over NW slope.
- 20.00 Draw, drains S. 25° W.; asc. over SE slope.
- 27.10 Spur, slopes S. 40° W.; desc. along W slope.
- 39.00 Head of draw, drains S. 45° W.; asc. over S slope.
- 40.48 Point for the cor. of secs. 28, 29, 32, and 33, reestablished from the original bearing trees
 - A juniper, 18 ins. diam., bears N. 35° E., 28 lks. dist., scribed T6S R3W S28 BT.
 - A juniper, 8 ins. diam., bears S. 80° E., 14 lks. dist., scribed T6S R3W S33 BT.
 - A juniper, 8 ins. diam., bears S. 87° W., 30 lks. dist., scribed T6S R3W S32 BT.
 - A juniper, 10 ins. diam., bears N. 50° W., 49 lks. dist., scribed T6S R3W S29 BT.

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.

T 6 S R 3 W

S 29		S 28
S 32		S 33

1974

From this cor., Cor. No. 1, Fellowship lode, mineral survey No. 3433, identical with Cor. No. 1, Campus lode, same survey, bears N. 43° 00' W., 10.34 chs. dist., hereinbefore described.

(Reestablishment of the Survey Executed by
Robert Gorlinski in 1892)

S. 89° 50' E., bet. secs. 28 and 33.

Over mountainous land through medium dense timber.

1.00 Head of draw, drains S. 30° W.; asc. over NW slope.

6.00 Spur, slopes S; thence along general S slope.

9.92 The closing cor. of secs. 28 and 33, on the old Ft. Crittenden Military Reservation Boundary, monumented with a limestone, 16 x 11 x 10 ins., set in a mound of stone, 2 ft. base, plainly mkd. CC on NW face, with 1 notch on S and 3 notches on E edges.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 2 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.

T 6 S R 3 W

C	S 28	S 28
C	S 33	OMRB

1975

Place the mkd. stone in mound of stone alongside the iron post.

From this cor., angle point No. 28, on the old Ft. Crittenden Military Reservation Boundary, bears N. 40° 31' W., 4.78 chs. dist., hereinbefore described.

From the cor. of secs. 28, 29, 32, and 33.

N. 1° 28' E., bet. secs. 28 and 29.

Over mountainous land through dense timber; asc. over steep S slope.

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

3.50 Spur, slopes S. 60° W.; thence along W slope.

6.50 Head of draw, drains S. 65° W.; asc. over SE slope.

8.93 Intersection line 1-2, Fellowship lode, mineral survey No. 3433, at a point from which Cor. No. 1, identical with Cor. No. 1, Campus lode, same survey, bears S. 79° 26' W., 7.41 chs. dist., hereinbefore described.

From the same point of intersection, Cor. No. 2, bears N. 79° 26' E., 14.75 chs. dist., hereinbefore described.

11.00 High spur, slopes S. 70° W.; desc. over NW slope.

15.00 Head of draw, drains W; asc. over steep SW slope.


32.53 Point for the closing cor. of secs. 28 and 29, on the old Ft. Crittenden Military Reservation Boundary, reestablished from the original bearing trees

A juniper, 8 ins. diam., bears S. 32° W., 53 lks. dist., scribed T5S R3W S29 CC BT.

A juniper stump, 10 ins. diam., 4 ft. high, bears N. 54° W., 12 lks. dist., scribed T6S R3W S29 CC BT.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.



1974

From this closing cor., angle point No. 26, on the old Ft. Crittenden Military Reservation Boundary, bears S. 16° 16' E., 1.18 chs. dist., hereinbefore described.


Point for the cor. of secs. 20, 21, 28, and 29, reestablished from the remaining original bearing trees

A juniper, 8 ins. diam., bears S. 31° 15' W., 18 lks. dist., scribed T6S R3W S29 BT.

A juniper, 6 ins. diam., bears N. 23° W., 11 lks. dist., scribed T6S R3W S20 BT.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.



1974

395

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS		
	<p>From this cor., U.S.M.M. No. 3, bears N. 32° 00' W., 19.37 chs. dist., reestablished in center of mound of stone, 5 ft. base, 3 ft. high, from which the remaining original bearing tree</p> <p>A juniper, 10 ins. diam., bears N. 68° 40' W., 85½ lks. dist., scribed USMM#3 BT.</p> <p>From the same cor., Cor. No. 10, Gold Point lode, mineral survey No. 3072, bears N. 51° 34' W., 2.01 chs. dist., monumented with a small mound of stone, from which an original bearing tree</p> <p>A juniper, 8 ins. diam., bears S. 12° 45' W., 36 lks. dist., scribed 10-3072 BT.</p> <p>S. 0° 06' W., bet. secs. 28 and 29.</p> <p>Over mountainous land through dense timber. Desc. over SW slope.</p>	
10.00	Leave timber, bears NW and SE.	
12.50	Trail road, bears N. 50° W. and S. 50° E.	
16.00	Wash, 20 lks. wide, 4 ft. deep, drains W; asc. over N slope.	
20.00	Enter dense timber, bears E and W.	
28.00	Spur, slopes W; desc. over SW slope.	
33.07	Intersect line 4-1, Keystone No. 4 lode, mineral survey No. 4495 at a point from which Cor. No. 4, bears N. 13° 55' W., 7.42 chs. dist., hereinbefore described.	
	From the same point of intersection, Cor. No. 1, bears S. 13° 55' E., 15.36 chs. dist., hereinbefore described.	
37.00	Draw, drains S. 65° W.; asc. over NW slope.	
37.14	Intersect line 16-17, Sunshine No. 2 lode, mineral survey No. 3072, at a point from which Cor. No. 16, identical with Cor. No. 12, Gold Point lode, same survey, and identical with Cor. No. 3, Tribune No. 2 lode, mineral survey No. 3088, bears N. 7° 56' W., 13.15 chs. dist., hereinbefore described.	
	From the same point of intersection, Cor. No. 17, Sunshine No. 2 lode, mineral survey No. 3072, bears S. 7° 56' E., 7.25 chs. dist., hereinbefore described.	
40.44	<p>The ¼ sec. cor. of secs. 28 and 29, monumented with a limestone, 16 x 14 x 10 ins., set 6 ins. in the ground, plainly mkd. ¼ on W face.</p> <p>from which the original bearing trees</p> <p>A juniper, 6 ins. diam., bears N. 39° E., 12 lks. dist., scribed ¼ S BT.</p> <p>A juniper, 8 ins. diam., bears S. 51° W., 10 lks. dist., scribed ¼ S BT.</p> <p>At the corner point</p>	

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, to top of brass cap, mkd.

T 6 S R 3 W

$$\begin{array}{c} \frac{1}{4} \\ | \\ \text{S } 29 \quad | \quad \text{S } 28 \end{array}$$

1974

Place the mkd. stone in mound of stone, alongside the iron post.

S. 0° 19' E., beginning new measurement.

Continue ascent over NW slope.

2.25 Intersect the old Ft. Crittenden Military Reservation Boundary.

Point for the closing cor. of secs. 28 and 29.

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.

T 6 S R 3 W

$$\begin{array}{c} \text{C} \quad | \quad \text{C} \\ \text{S } 29 \quad | \quad \text{S } 28 \end{array}$$

OMRB
1974

From this closing cor., angle point No. 25, on the old Ft. Crittenden Military Reservation Boundary, bears S. 28° 58' W., 2.84 chs. dist., hereinbefore described.

2.35 The original closing cor. of secs. 28 and 29, monumented with a limestone, 20 x 12 x 12 ins., set 14 ins. in the ground, plainly mkd. CC on NE face, with 2 notches on S edge. This corner will now function as an amended monument and I added the marks "AM" to the S face.

from which the original bearing trees

A juniper, 14 ins. diam., bears N. 13° E., 65 lks. dist., scribed T6S R3W S28 CC BT. (Record, 60 lks.)

A dead and fallen pinon, 10 ins. diam., bears N. 60° W., 42 lks. dist., scribed T6S R3W S29 CC BT. (Record, N. 55° W., 36 lks. dist.)

From the cor. of secs. 20, 21, 28, and 29.

S. 89° 29' E., bet. secs. 21 and 28.

Over mountainous land through dense timber. Asc over SW slope.

397

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS					
2.90	Spur, slopes S. 15° W.; desc. over SE slope.				
9.00	Draw, drains S. 30° W.; asc. over NW slope.				
15.00	Ridge, bears N and S.				
15.60	The closing cor. of secs. 21 and 28, monumented with a limestone, 16 x 10 x 10 ins., firmly set 5 ins. in the ground, plainly mkd. CC on NW face, with 2 notches on S and 4 notches on E edges, and witnessed by a mound of stone to W. This cor. will now function as an amended monument, and I add the marks "AM" to the SE face.				
15.63	<p>Intersect the old Ft. Crittenden Military Reservation Boundary.</p> <p>Point for the closing cor. of secs. 21 and 28.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 6 S R 3 W</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">C S 21</td> <td style="padding: 0 5px;">S 21</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">C S 28</td> <td style="padding: 0 5px;">OMRB</td> </tr> </table> <p style="text-align: center;">1974</p> <p>From this closing cor., the 39th mile cor. of the old Ft. Crittenden Military Reservation Boundary, bears N. 1° 05' E., 12.03 chs. dist., hereinbefore described.</p>	C S 21	S 21	C S 28	OMRB
C S 21	S 21				
C S 28	OMRB				
5.15	<p>From the cor. of secs. 20, 21, 28, and 29.</p> <p>N. 0° 23' E., bet. secs. 20 and 21.</p> <p>Over mountainous land through dense timber; asc. over SW slope.</p> <p>W edge of old mine tailings; desc. along W slope, timber becomes scattered.</p>				
9.00	Trail road, on curve, bears N. 20° E. and S. 30° W.				
17.25	Same trail road, bears N. 20° W. and S. 20° E.; asc. over rolling land.				
21.50	Same trail road, bears N. 25° E. and S. 25° W.				
27.50	Same trail road, bears N. 70° E. and S. 70° W.				
28.50	Point of spur, slopes S. 40° W.; desc. over NW slope.				
30.00	Same trail road, bears N. 40° E. and S. 40° W.				
33.00	Wash, 15 lks. wide, 4 ft. deep, drains S. 45° W., 50 lks. to Sunshine Canyon, draining S. 40° W.; asc. over SE slope.				
39.73	Point for the ¼ sec. cor. of secs. 20 and 21, is determined at record bearing and distance from Cor. No. 12, Annie Laurie No. 3 lode, mineral survey No. 3047.				

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

A squared cedar post, 4 ins. diam., 4 ft. long, in a mound of stone, scribed 12-3047, bears N. $78^{\circ} 21'$ W., 3.25 chs. dist., (record, 214.5 ft. from which an original bearing tree

A juniper, 10 ins. diam., bears N. $9^{\circ} 45'$ W., $99\frac{1}{2}$ lks. dist., scribed 12-3047 BT.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 6 S R 3 W

$\frac{1}{4}$
 |
 S 20 | S 21
 |

1975

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

N. $0^{\circ} 25'$ E., beginning new measurement.

Asc. along general E slope.

35.00 Spur, slopes S from N. 15° E.; desc. over NW slope.

40.30 The cor. of secs. 16, 17, 20, and 21, monumented with a lime conglomerate stone, 20 x 10 x 8 ins., set in a mound of stone, plainly mkd. 3 notches on S and 4 notches on E edges.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 6 S R 3 W

S 17 | S 16
 S 20 | S 21

1975

Bury the mkd. stone alongside the iron post, and raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W of cor.

From this cor., Cor. No. 1, Sundown Mine lode, mineral survey No. 3239, bears N. $58^{\circ} 15'$ W., 1.24 chs. dist., monumented with a decayed wood post, 4 x 4 ins., 4 ft. long, in mound of stone.

From this same cor., Cor. No. 2, Molly Gibson lode, mineral survey No. 3925, bears S. $89^{\circ} 27'$ W., 2.29 chs. dist., monumented with a partially decayed wood post, 4 x 4 ins., 4 ft. long, in small mound of stone.

S. $89^{\circ} 35'$ E., bet. secs. 16 and 21.

Over mountainous land, through oak brush undergrowth and scattered timber; asc. over W slope.

1.25 Center of prospect cut, 4 ft. wide, 6 ft. long, 4 ft. deep.

399

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS											
1.50	Spur, slopes S. 20° W.; desc. over E slope.										
7.50	Draw, drains S; asc. over SW slope.										
14.00	Trail road, bears N. 22° W. and S. 22° E.										
20.26	The closing cor. of secs. 16 and 21, monumented with a limestone, 20 x 15 x 8 ins., firmly set 12 ins. in the ground, plainly mkd. CC on NW face, with 3 notches on S and 4 notches on E edges. This cor. will now function as an amended monument only and I add the marks "AM" to the SW face.										
20.43	<p>Intersect the old Ft. Crittenden Military Reservation Boundary.</p> <p>Point for the closing cor. of secs. 16 and 21.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p> <div style="text-align: center;"> <p>T 6 S R 3 W</p> <table style="margin: auto;"> <tr> <td style="border: none;">C</td> <td style="border: none;">S 16</td> <td style="border: none;">S 16</td> </tr> <tr> <td style="border: none;">C</td> <td style="border: none;">S 21</td> <td style="border: none;">OMRB</td> </tr> </table> <p>1974</p> </div> <p>From this closing cor., angle point No. 17, on the old Ft. Crittenden Military Reservation Boundary, bears N. 38° 19' E., 2.63 chs. dist., hereinbefore described.</p>	C	S 16	S 16	C	S 21	OMRB				
C	S 16	S 16									
C	S 21	OMRB									
	<p>From the cor. of secs. 16, 17, 20, and 21.</p> <p>N. 0° 04' E., bet. secs. 16 and 17.</p> <p>Over mountainous land through scattered timber and dense sagebrush undergrowth; desc. over NW slope.</p> <tr> <td data-bbox="293 1714 380 1736">1.50</td> <td data-bbox="418 1701 1344 1768">Sunshine Canyon, 15 lks. wide, 3 ft. deep, drains S. 40° W. from N. 10° E.; asc. along canyon.</td> </tr> <tr> <td data-bbox="293 1814 380 1835">16.50</td> <td data-bbox="418 1800 1344 1835">Trail road, bears N. 25° W. and S. 25° E.</td> </tr> <tr> <td data-bbox="293 1876 380 1897">28.00</td> <td data-bbox="418 1862 1344 1929">Sunshine Canyon, drains S. 30° E. turning S; asc. over SW slope.</td> </tr> <tr> <td data-bbox="293 1970 380 1991">35.00</td> <td data-bbox="418 1956 1344 1991">Enter medium dense timber, bears E and W.</td> </tr> <tr> <td data-bbox="293 2032 380 2053">40.01</td> <td data-bbox="418 2018 1344 2601"> <p>The ¼ sec. cor. of secs. 16 and 17, monumented with a broken limestone, 10 x 5 x 5 ins., in mound of stone, plainly mkd. ¼ on W face.</p> <p>from which the original bearing trees</p> <p style="padding-left: 40px;">A juniper, 12 ins. diam., bears S. 54° 45' E., 114 lks. dist., scribed ¼ S BT.</p> <p style="padding-left: 40px;">A juniper, 12 ins. diam., bears N. 10° 30' W., 12 lks. dist., scribed ¼ S BT.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p> </td> </tr>	1.50	Sunshine Canyon, 15 lks. wide, 3 ft. deep, drains S. 40° W. from N. 10° E.; asc. along canyon.	16.50	Trail road, bears N. 25° W. and S. 25° E.	28.00	Sunshine Canyon, drains S. 30° E. turning S; asc. over SW slope.	35.00	Enter medium dense timber, bears E and W.	40.01	<p>The ¼ sec. cor. of secs. 16 and 17, monumented with a broken limestone, 10 x 5 x 5 ins., in mound of stone, plainly mkd. ¼ on W face.</p> <p>from which the original bearing trees</p> <p style="padding-left: 40px;">A juniper, 12 ins. diam., bears S. 54° 45' E., 114 lks. dist., scribed ¼ S BT.</p> <p style="padding-left: 40px;">A juniper, 12 ins. diam., bears N. 10° 30' W., 12 lks. dist., scribed ¼ S BT.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p>
1.50	Sunshine Canyon, 15 lks. wide, 3 ft. deep, drains S. 40° W. from N. 10° E.; asc. along canyon.										
16.50	Trail road, bears N. 25° W. and S. 25° E.										
28.00	Sunshine Canyon, drains S. 30° E. turning S; asc. over SW slope.										
35.00	Enter medium dense timber, bears E and W.										
40.01	<p>The ¼ sec. cor. of secs. 16 and 17, monumented with a broken limestone, 10 x 5 x 5 ins., in mound of stone, plainly mkd. ¼ on W face.</p> <p>from which the original bearing trees</p> <p style="padding-left: 40px;">A juniper, 12 ins. diam., bears S. 54° 45' E., 114 lks. dist., scribed ¼ S BT.</p> <p style="padding-left: 40px;">A juniper, 12 ins. diam., bears N. 10° 30' W., 12 lks. dist., scribed ¼ S BT.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p>										

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

T 6 S R 3 W

$\frac{1}{4}$
 S 17 | S 16

1975

Bury the mkd. stone alongside the iron post.

From this cor., Cor. No. 1, Superior No. 2 lode, mineral survey No. 4935, identical with Cor. No. 1, Matchless Mine lode, same survey, bears N. $58^{\circ} 12'$ W., 2.69 chs. dist., monumented with a badly decayed wood post, 4 x 4 ins., 4 ft. long, in small mound of earth and stone.

from which an original bearing tree

A juniper, 12 ins. diam., bears S. $32^{\circ} 15'$ W., $88\frac{1}{2}$ lks. dist., scribed 1-1-4935 BT.

At the claim corner point

Set a Copperweld monument, 30 ins. long, $\frac{5}{8}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

1
 MM 1 S-2
 4935

N. $1^{\circ} 00'$ E., beginning new measurement.

Continue ascent over SW slope.

1.85 Intersect line 1-2, Superior No. 2 lode, mineral survey No. 4935, at a point from which Cor. No. 1, identical with Cor. No. 1, Matchless Mine lode, same survey, bears S. $79^{\circ} 24'$ W., 2.36 chs. dist., hereinbefore described.

From the same point of intersection, Cor. No. 2, bears N. $79^{\circ} 24'$ E., 7.43 chs. dist., hereinbefore described.

13.00 Spur, slopes S. 40° W.; asc. along general W slope.

21.00 Head of draw, drains S. 10° W.; asc. over SW slope.

29.74 Intersect the old Ft. Crittenden Military Reservation Boundary.

Point for the closing cor. of secs. 16 and 17.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, $3\frac{1}{2}$ ft. base, to top of brass cap, mkd.

T 6 S R 3 W

OMRB S16

S 17 | S 16
 C | C
 1974

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
	<p>From this closing cor., angle point No. 11, on the old Ft. Crittenden Military Reservation Boundary, bears S. 50° 47' E., 2.01 chs. dist., hereinbefore described.</p>
30.67	<p>The original closing cor. of secs. 16 and 17, monumented with a limestone, 24 x 10 x 5 ins., firmly set 12 ins. in the ground, plainly mkd. CC on SE face, with 4 notches on S and E edges. This cor. will now function as an amended monument only, and I add the marks "AM" to the N face.</p>
	<p>(Reestablishment of the Survey Executed by C.L. Craig in 1856 and the Resurvey Executed by Robert Gorlinski in 1892)</p>
	<p>From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., extending 6 ins. above ground, with brass cap mkd. as described in the 1973 resurvey of the N. bdy. of T. 7 S., R. 3 W.</p>
	<p>N. 0° 26' E., bet. secs. 31 and 32.</p>
	<p>Over gently rolling land through sagebrush undergrowth.</p>
12.00	<p>Trail road, bears N. 30° E. and S. 30° W.</p>
25.50	<p>Wash, 20 lks. wide, 4 ft. deep, drains S. 25° W.</p>
40.37	<p>The ¼ sec. cor. of secs. 31 and 32, monumented with a limestone, 20 x 10 x 10 ins., firmly set 6 ins. in the ground, plainly mkd. ¼ on W face.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p>T 6 S R 3 W</p>
	<p>¼</p>
	<p>S 31 S 32</p>
	<p>1974</p>
	<p>Bury the mkd. stone alongside the iron post.</p>
	<p>N. 0° 27' E., beginning new measurement.</p>
40.42	<p>The cor. of secs. 29, 30, 31, and 32, monumented with a limestone, 12 x 10 x 9 ins., set 4 ins. in the ground, plainly mkd. 1 notch on S and 5 notches on E edges.</p>
	<p>from which the remaining original bearing tree</p>
	<p>A juniper, 10 ins. diam., bears S. 7° 30' E., 121 lks. dist., scribed T6S R3W S32 BT.</p>
	<p>At the corner point</p>

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 6 S R 3 W

S 30		S 29
S 31		S 32

1974

Bury the mkd. stone alongside the iron post.

From this cor., Cor. No. 4, Molly Bawn lode, mineral survey No. 3512, bears N. 80° 05' W., 9.63 chs. dist., monumented with a squared cedar post, 3 ins. diam., firmly set in a mound of stone, 3 ft. base, 2 ft. high.

(Reestablishment of the Survey Executed by
Robert Gorlinski in 1892)

From the cor. of secs. 28, 29, 32, and 33.

S. 89° 14' W., bet. secs. 29 and 32.

Over mountainous land through medium dense timber. Asc. over SE slope.

4.50 Spur, slopes S. 50° W.; desc. over NW slope.

8.50 Draw, drains S. 45° W.; asc. over SE slope.

13.96 Intersect line 1-2, Campus lode, mineral survey No. 3433, at a point from which Cor. No. 2, identical with Cor. No. 3, Old Horseshoe lode, same survey, bears S. 41° 43' W., 10.98 chs. dist., monumented with a mound of stone, 2½ ft. base, 1½ ft. high.

from which an original bearing tree

A juniper, 12 ins. diam., bears N. 60° 15' W., 51 lks. dist., scribed 2-3-3433 BT.

From the same point of intersection, Cor. No. 1, identical with Cor. No. 1, Fellowship lode, same survey, bears N. 41° 43' E., 10.38 chs. dist., hereinbefore described.

16.70 Spur, slopes S. 37° W.; desc. over NW slope.

34.00 Draw, drains S. 45° W.

38.75 Wash, 10 lks. wide, 3 ft. deep, drains S; asc. over SE slope.

40.25 The ¼ sec. cor. of secs. 29 and 32, monumented with a limestone, 15 x 7 x 4 ins., firmly set 6 ins. in the ground and in a mound of stone, plainly mkd. ¼ on N face.

from which the original bearing trees

A juniper, 12 ins. diam., bears N. 13° 30' E., 125 lks. dist., scribed ¼ SBT. (Record, 120 lks.)

403

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

A juniper, 7 ins. diam., bears N. $36^{\circ} 30'$ W., 32
lks. dist., scribed $\frac{1}{4}$ SBT. (Record, 50 lks.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins.
in the ground to bedrock, in a mound of stone, 3 ft.
base, to top of brass cap, mkd.

T 6 S R 3 W

$\frac{1}{4}$ $\frac{S 29}{S 32}$

1974

Bury the mkd. stone alongside the iron post.

S. $89^{\circ} 15'$ W., beginning new measurement.

Continue ascent over SE slope.

6.74 Intersect line 3-4, Lehi Lode, mineral survey No. 3433,
at a point from which Cor. No. 3, bears N. $24^{\circ} 22'$ W.,
4.52 chs. dist., monumented with a mound of stone, 2 ft.
base, $1\frac{1}{2}$ ft. high.

from which the original bearing trees

A juniper, 10 ins. diam., bears S. $34^{\circ} E.$, $20\frac{1}{2}$
lks. dist., scribed BT-3-3433.

A juniper stump, 6 ins. diam., 4 ft. high, bears
N. $24^{\circ} 15'$ W., 10 lks. dist., scribed BT-3-3433.

From the same point of intersection, Cor. No. 4, identical
with Cor. No. 1, Old Horseshoe lode, same survey, bears
S. $24^{\circ} 22'$ E., 14.58 chs. dist., monumented with a squared
cedar post, 3 ins. diam., 3 ft. long, in mound of stone,
scribed 1-4-3433.

from which the original bearing trees

A juniper, 6 ins. diam., bears S. $61^{\circ} E.$, 35
lks. dist., scribed BT-1-4-3433.

A juniper, 10 ins. diam., bears S. $59^{\circ} 15'$ W., 22
lks. dist., scribed BT-1-4-3433.

8.50 Spur, slopes S. $15^{\circ} W.$ from N. $60^{\circ} E.$; desc. over NW
slope.

18.50 Wash, 30 lks. wide, 4 ft. deep, drains S. $10^{\circ} W.$; asc.
over SE slope.

26.10 Spur, slopes S; desc. over W slope.

39.20 Wash, 50 lks. wide, 3 ft. deep, drains S. $10^{\circ} E.$

39.81 The cor. of secs. 29, 30, 31, and 32.

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

(Reestablishment of the Survey Executed by
C.L. Craig in 1856 and the Resurvey Executed
by Robert Gorlinski in 1892)

S. 88° 59' W., bet. secs. 30 and 31.

Over rolling land through scattered timber.

11.50 Trail road, bears N. 26° W. and S. 26° E.

40.24 The ¼ sec. cor. of secs. 30 and 31, monumented with a
limestone, 20 x 14 x 9 ins., set in a mound of stone,
2½ ft. base, 1½ ft. high, plainly mkd. ¼ on N face.

from which the remaining original bearing tree

A juniper, 5 ins. diam., bears S. 43° 30' E., 170
lks. dist., scribed ¼ S BT.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, and in a collar of stone, with brass cap
mkd.

T 6 S R 3 W

¼ $\frac{S\ 30}{S\ 31}$

1974

Bury the mkd. stone alongside the iron post.

S. 88° 56' W., beginning new measurement.

23.30 Wash, 15 lks. wide, 4 ft. deep, drains S. 35° W.

41.07 The cor. of secs. 25, 30, 31, and 36, on the W. bdy.
of the Tp., monumented with an iron post, 2 ins. diam.,
extending 12 ins. above ground, with brass cap mkd. as
described in the official record of the 1943 resurvey.

From the cor. of secs. 29, 30, 31, and 32.

N. 0° 20' E., bet. secs. 29 and 30.

Over rolling land through scattered timber.

0.50 Wash, drains S. 20° E.; asc. over general SW slope.

20.16 Point for the S 1/16 sec. cor. of secs. 29 and 30.

Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins.
in the ground to bedrock, in a mound of stone, 3½ ft.
base, to top of brass cap, mkd.

T 6 S R 3 W
S 1/16

S 30 | S 29

1974

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
23.40	Spur, slopes S. 50° W.; desc. over NW slope.
30.00	Draw, drains S. 55° W.; asc. over SE slope.
34.20	Rocky spur, slopes S. 75° W.; desc. over NW slope.
38.30	Trail road, bears N. 65° E. and S. 65° W.
39.30	Sunshine Canyon, 30 lks. wide, 6 ft. deep, drains irregularly S. 65° W.; asc. over SE slope.
40.32	The ¼ sec. cor. of secs. 29 and 30, monumented with a limestone, 18 x 10 x 6 ins., set in a mound of stone, 2 ft. base, 1 ft. high, on solid surface rock, plainly mkd. ¼ on W face.
	<p>from which the original bearing trees</p> <p style="padding-left: 40px;">A juniper stump, 10 ins. diam., 3 ft. high, bears S. 44° 30' W., 67 lks. dist., scribed BT.</p> <p style="padding-left: 40px;">A juniper, 12 ins. diam., bears N. 47° 30' W., 57 lks. dist., scribed ¼ SBT.</p>
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., over a cross (X), on solid rock, and in a mound of stone, 4 ft. base, to top of brass cap mkd.</p>
	<p>T 6 S R 3 W</p> <p style="margin-left: 100px;">¼</p> <p style="margin-left: 100px;">S 30 S 29</p> <p style="margin-left: 100px;"> </p> <p>1974</p>
	<p>Place the mkd. stone in mound of stone, alongside the iron post.</p>
	<p>(Reestablishment of the Survey Executed by Robert Gorlinski in 1892)</p>
	<p>N. 0° 26' E., beginning new measurement.</p>
	<p>Continue ascent over SE slope.</p>
1.00	Low spur, slopes S. 45° W.; desc. along W slope.
12.00	Draw, drains S. 60° W.; asc. over SE slope. Enter dense timber, bears NW and SE.
22.60	Spur, slopes S. 75° W.; desc. over NW slope.
28.00	Alma Young Canyon, 30 lks. wide, 4 ft. deep, drains S. 45° W. from N. 5° E.; asc. along W side of canyon.
40.39	The cor. of secs. 19, 20, 29, and 30, monumented with a limestone, 18 x 12 x 9 ins., firmly set in a small mound of stone, plainly mkd. 2 notches on S and 5 notches on E edges.

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

from which the original bearing trees

A juniper, 8 ins. diam., bears N. 30° E., 56 lks.
dist., scribed BT T6S R3W S20. (Record, 54 lks.)

A pinon, 8 ins. diam., bears S. 22° 15' E. 49 lks.
dist., scribed BT T6S R3W S29.

A juniper, 6 ins. diam., bears S. 7° W., 68 lks.
dist., scribed BT T6S R3W S30.

A juniper, 6 ins. diam., bears N. 26° W., 24 lks.
dist., scribed BT T6S R3W S19. (Record, 22 lks.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins.
in the ground to bedrock, in a mound of stone, 3 ft.
base, to top of brass cap, mkd.

T 6 S R 3 W

S 19	S 20
S 30	S 29

1974

Bury the mkd. stone alongside the iron post.

From the cor. of secs. 20, 21, 28, and 29.

N. 89° 42' W., bet. secs. 20 and 29.

Over mountainous land through dense timber. Desc. over
SW slope.

- 4.75 Trail road, bears N. 25° E. and S. 5° W.
- 5.20 Sunshine Canyon, 20 lks. wide, 5 ft. deep, drains
S. 25° W.; asc. over SE slope.
- 22.00 Spur, slopes S. 45° E.; asc. along S slope.
- 28.50 Draw, drains S. 40° E.; asc. over E slope.
- 35.60 Spur, slopes S.; desc. over SW slope.
- 40.71 The ¼ sec. cor. of secs. 20 and 29, monumented with a
limestone, 13 x 12 x 5 ins., set 10 ins. in the ground,
plainly mkd. ¼ on N face, and witnessed by a small mound
of stone to the N.

from which the original bearing trees

A juniper, 6 ins. diam., bears S. 52° W., 21 lks.
dist., scribed ¼ SBT. (Record, 24 lks.)

A juniper, 6 ins. diam., bears N. 50° W., 65 lks.
dist., scribed ¼ S BT.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins.
in the ground to bedrock, in a mound of stone, 3½ ft.
base, to top of brass cap, mkd.

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS		
	<p>T 6 S R 3 W</p> <p>$\frac{1}{4} \frac{S 20}{S 29}$</p> <p>1975</p>	
	Bury the mkd. stone alongside the iron post.	
	N. 89° 50' W., beginning new measurement.	
1.61	Intersect line 4-1, Ouida lode, mineral survey No. 3707, at a point from which Cor. No. 1, bears N. 22° 59' E., 5.36 chs. dist., monumented with a cedar post, 4 ins. diam., 4 ft. long, in a mound of stone, scribed 1-3707.	
	from which the original bearing trees	
	A pinon, 14 ins. diam., bears S. 75° 30' E., 39 lks. dist., scribed 1-1-3707 BT.	
	A juniper, 12 ins. diam., bears N. 21° W., 31 lks. dist., scribed 1-3707 BT.	
	From the same point of intersection, Cor. No. 4, bears S. 22° 59' W., 3.52 chs. dist., monumented with a wood post, 4 x 4 ins., 4 ft. long, partially decayed on one side.	
	from which the original bearing trees	
	A juniper, 12 ins. diam., bears N. 27° E., 30 lks. dist., scribed 4-3707 BT.	
	A juniper, 10 ins. diam., bears S. 89° W., 17 lks. dist., scribed 4-3707 BT.	
9.00	Deep draw, drains S; asc. over steep SE slope.	
17.00	Spur, slopes S; desc. along S slope.	
26.00	Spur, slopes S. 25° W.; desc. over W slope.	
39.60	Alma Young Canyon, 30 lks. wide, 3 ft. deep, drains S.	
40.59	The cor. of secs. 19, 20, 29, and 30.	
	S. 88° 53' W., bet. secs. 19 and 30.	
	Over mountainous land, through dense timber. Asc. over steep E slope.	
5.30	Spur, slopes S; desc. over NW slope.	
17.00	Mitchell Canyon, 20 lks. wide, 3 ft. deep, drains S. 23° W.; asc. over SE slope. Leave timber.	
27.00	Top of ascent, slopes S; desc. over SW slope.	
35.75	Wash, 20 lks. wide, 6 ft. deep, drains S; asc. over E slope. Enter scattered timber.	
40.52	The $\frac{1}{4}$ sec. cor. of secs. 19 and 30, monumented with a limestone, 18 x 9 x 5 ins., plainly mkd. $\frac{1}{4}$ on N face and firmly set in a mound of stone.	

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

from which the original bearing trees

A juniper, 5 ins. diam., bears S. 42° W., 10 lks.
dist., scribed $\frac{1}{4}$ S BT.

A pinon, 4 ins. diam., bears N. 60° 30' W., 87 lks.
dist., scribed BT on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., over a
cross (X) on solid rock, in a mound of stone, 4 ft.
base, to top of brass cap, mkd.

T 6 S R 3 W

$\frac{1}{4}$ $\frac{S 19}{S 30}$

1974

Place the mkd. stone in mound of stone, alongside the
iron post.

S. 88° 53' W., beginning new measurement.

Continue ascent over E slope.

- 0.75 Spur, slopes S; desc. over W slope.
- 10.00 Wash, drains S. 55° W.; thence over rolling land.
- 17.50 Wash, drains S.
- 20.00 Point of small spur, slopes S; desc. over SW slope.
- 24.65 Intersect line 2-3, Buffalo lode, mineral survey No.
3512, at a point from which Cor. No. 2, bears
N. 38° 51' W., 12.37 chs. dist., monumented with a
mound of stone, 2½ ft. base, 1 ft. high.
- from which the original bearing trees
- A juniper, 10 ins. diam., bears S. 15° 30' W.,
59 lks. dist., scribed 2-3512 BT.
- A juniper, 8 ins. diam., bears S. 80° 30' W.,
47½ lks. dist., scribed 2-3512 BT.
- From the same point of intersection, Cor. No. 3, identical
with Cor. No. 2, My Emma lode, same survey, bears
S. 38° 51' E., 10.13 chs. dist., monumented with a wood
post, 4 x 4 ins., 4 ft. long, in mound of stone, scribed
3-2-3512.
- from which an original bearing tree
- A juniper, 4 ins. diam., bears S. 38° 45' W.,
143½ lks. dist., scribed 3-2-3512 BT.
- 34.50 Wash, drains S. 30° W.
- 36.47 Intersect line 4-1, Buffalo lode, mineral survey No.
3512, at a point from which Cor. No. 1, identical with
Cor. No. 4, Buffalo Fraction lode, same survey, bears
N. 39° 00' W., 5.59 chs. dist., monumented with a mound
of stone, 2 ft. base, 1 ft. high.

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
	<p>from which an original bearing tree</p> <p>A juniper, 6 ins. diam., bears N. 72° 45' W., 124 lks. dist., scribed BT-4-1-3512.</p> <p>From the same point of intersection, Cor. No. 4, identical with Cor. No. 1, Emma lode, and identical with Cor. No. 2, Frances lode, same survey, bears S. 39° 00' E., 16.94 chs. dist., monumented with a badly decayed wood post, 4 x 4 ins. 4 ft. long, in mound of stone.</p> <p>from which the original bearing trees</p> <p>A juniper, 10 ins. diam., bears S. 79° 15' W., 56 lks. dist., scribed 1-2-4-3512 BT.</p> <p>A juniper, 8 ins. diam., bears N. 28° 15' W., 45½ lks. dist., scribed 1-2-4-3512 BT.</p>
38.50	<p>Low spur, slopes S. 30° W.; desc. over NW slope.</p>
41.14	<p>The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., extending 12 ins. above ground, with brass cap mkd. as described in the official record of the 1926 resurvey.</p> <p>From this cor., Cor. No. 1, Buffalo lode, mineral survey No. 3512, identical with Cor. No. 4, Buffalo Fraction lode, same survey, bears N. 17° 54' E., 4.67 chs. dist., hereinbefore described.</p>
20.00	<p>From the cor. of secs. 19, 20, 29, and 30.</p> <p>N. 0° 04' W., bet. secs. 19 and 20.</p> <p>Over mountainous land through dense timber. Asc. along W side of Alma Young Canyon.</p>
30.00	<p>Spur, slopes S. 20° W. turning S; asc. along W slope.</p>
37.00	<p>Top of ascent, slopes W; desc. over NW slope.</p>
40.38	<p>Leave timber, edge bears E and S. 45° W.</p> <p>The ¼ sec. cor. of secs. 19 and 20, monumented with a limestone, 20 x 14 x 10 ins., firmly set in a mound of stone, 2½ ft. base, plainly mkd. ¼ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p>
	<p style="text-align: center;">T 6 S R 3 W</p> <p style="text-align: center;"> ¼ S 19 S 20 1975 </p>
	<p>Bury the mkd. stone alongside the iron post.</p>

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS							
	N. 0° 45' E., beginning new measurement.						
0.10	Wash, 10 lks. wide, 2 ft. deep, drains W; asc. over SW slope.						
3.00	Enter timber, edge, bears N. 50° E. and S. 50° W.						
5.00	Top of ascent, slopes W; thence along W slope.						
11.50	Mitchell Canyon, 20 lks. wide, 4 ft. deep, drains S. 35° W. from N. 70° E.; asc. over steep, rocky SE slope.						
33.05	Ledgy point on spur, slopes S. 10° W.; asc. along rocky E slope.						
40.43	The cor. of secs. 17, 18, 19, and 20, monumented with a limestone, 20 x 16 x 10 ins., set in a small mound of stone, plainly mkd. 3 notches on S and 5 notches on E edges.						
	from which the original bearing trees						
	A juniper, 10 ins. diam., bears N. 70° 30' E., 70 lks. dist., scribed T6S R3W S17 BT.						
	A juniper, 15 ins. diam., bears S. 46° E., 63 lks. dist., scribed T6S R3W S20 BT.						
	A juniper, 8 ins. diam., bears S. 71° 15' W., 84 lks. dist., scribed BT.						
	A juniper, 12 ins. diam., bears N. 39° 45' W., 75 lks. dist., scribed T6S R3W S18 BT.						
	At the corner point						
	Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base, to top of brass cap, mkd.						
	T 6 S R 3 W						
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 2px;">S 18</td> <td style="padding: 2px;"> </td> <td style="padding: 2px;">S 17</td> </tr> <tr> <td style="padding: 2px;">S 19</td> <td style="padding: 2px;"> </td> <td style="padding: 2px;">S 20</td> </tr> </table>	S 18		S 17	S 19		S 20
S 18		S 17					
S 19		S 20					
	1975						
	Place the mkd. stone in mound of stone, alongside the iron post.						
	From the cor. of secs. 16, 17, 20, and 21.						
	N. 89° 16' W., bet. secs. 17 and 20.						
	Over mountainous land through medium dense timber. Desc. over W slope.						
2.30	Sunshine Canyon, 20 lks. wide, 3 ft. deep, drains irregularly S; asc. over SE slope.						
18.27	Intersect line 4-5, Golden Wedge lode, mineral survey No. 3925, at a point from which Cor. No. 5, bears S. 6° 07' E., 7.80 chs. dist., monumented with a mound of stone.						

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

from which the original bearing trees

A pinon, 24 ins. diam., bears S. 0° 15' E., 57½ lks. dist., incorrectly scribed 4-3925 BT.

A pinon, 15 ins. diam., bears S. 29° 30' W., 72 lks. dist., incorrectly scribed 4-3925 BT.

From the same point of intersection, Cor. No. 4, identical with Cor. No. 5, Golden Era lode, same survey, bears N. 6° 07' W., 6.34 chs. dist., monumented with a wood post, 4 x 4 ins. 4 ft. long, set in mound of stone, scribed 4-5-3925.

22.40 Ridge, bears N. 20° E. and S. 20° W.; desc. over NW slope.

28.00 Draw, drains S. 50° W.; asc. over SE slope.

33.50 Top of ascent, slopes S; desc. over SW slope.

40.19 The ¼ sec. cor. of secs. 17 and 20, monumented with a limestone, 14 x 12 x 10 ins., firmly set in a mound of stone, plainly mkd. ¼ on N face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.

T 6 S R 3 W

¼ $\frac{S 17}{S 20}$

1975

Place the mkd. stone in mound of stone, alongside the iron post.

N. 89° 17' W., beginning new measurement.

0.30 Draw, drains S.; asc. over E slope.

0.84 Intersect line 25-26, Gold Blossom No. 2 lode, (amended) mineral survey No. 3047, at a point from which Cor. No. 25, identical with Cor. No. 29, Gold Blossom No. 1 lode, (amended) same survey, bears N. 16° 22' W., 2.29 chs. dist., monumented with a mound of stone.

from which the original bearing trees

A pinon, 8 ins. diam., bears S. 69° E., 18½ lks. dist., scribed 25-3047 BT.

A pinon, 6 ins. diam., bears S. 24° W., 26 lks. dist., scribed 25-3047 BT.

From the same point of intersection, Cor. No. 26, identical with Cor. No. 21, Gold Blossom No. 3 lode (amended), same survey, bears S. 16° 22' E., 16.58 chs. dist., monumented with a badly decayed wood post, in mound of stone.

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

from which the original bearing trees

A juniper, 18 ins. diam., bears N. 6° 00' E., 32 lks. dist., scribed 31-3047 BT. (Record, N. 1° 15' W., 16.5 ft.)


A pinon, 24 ins. diam., bears S. 23° 15' W., 94 lks. dist., scribed 21-3047 BT. (Record, 52.2 ft.)

A pinon, 20 ins. diam., bears S. 43° 15' W., 72 lks. dist., scribed 26-3047 BT. (Record, 70.5 ft.)

A pinon, 24 ins. diam., bears N. 88° W., 135 lks. dist., scribed 26-3047 BT. (Record, 90.4 ft.)

At the claim corner point

Set a Copperweld monument, 30 ins. long, 5/8 ins. diam., 20 ins. in the ground, with brass cap mkd.



4.70 Intersect the westerly side line of Afix Lode, unsurveyed, at a point from which NW cor., identical with the SW cor. of Monta No. 1 Lode, unsurveyed, same survey, bears N. 13° 04' E., 3.01 chs. dist., hereinafter described.

From the same point of intersection, the SW cor. bears S. 13° 04' W., 16.34 chs. dist., hereinafter described.

5.50 Point of spur, slopes S; desc. over SW slope.

10.25 Intersect line 27-28, Gold Blossom No. 2 lode (amended), mineral survey No. 3047, at a point from which Cor. No. 27, identical with Cor. No. 24, Gold Blossom No. 3 lode (amended), same survey, bears S. 16° 57' E., 18.50 chs. dist., monumented with a mound of stone.

from which the original bearing trees


A pinon stump, 10 ins. diam., 6 ft. high, bears N. 26° 30' E., 123 lks. dist, scribed 27-3047 BT. (Record, N. 34° 05' E., 74.5 ft.)

A juniper, 18 ins. diam., bears S. 11° E., 65 lks. dist., scribed 27-3047 BT. (Record, N. 10° 20' E., 45.2 ft.)

A juniper, 10 ins. diam., bears N. 53° W., 44 lks. dist., scribe marks visible on partially healed blaze. (Record, N. 56° 40' W., 29 ft.)

At the claim corner point

Set a Copperweld monument, 30 ins. long, 5/8 ins. diam., 18 ins. in the ground, with brass cap mkd.



Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
	<p>From the same point of intersection, Cor. No. 28, identical with Cor. No. 34, Gold Blossom No. 1 lode (amended), same survey, bears N. 16° 57' W., 0.43 chs. dist., monumented with a mound of stone.</p>
	<p>from which the original bearing trees</p>
	<p>A pinon, 12 ins. diam., bears N. 81° E., 31 lks. dist., with healed blaze. (Record, 17.1 ft.)</p>
	<p>A juniper stump, 18 ins. diam., bears S. 89° E., 24½ lks. dist., scribed 34-3047 BT. (Record, 14.2 ft.)</p>
	<p>A pinon, 14 ins. diam., bears S. 20° 15' W., 11 lks. dist., scribed 34-3047 BT.</p>
<p>22.00</p>	<p>Mitchell Canyon, drains S. 40° W.; asc. over steep SE slope.</p>
<p>41.14</p>	<p>The cor. of secs. 17, 18, 19, and 20.</p>
	<p>S. 89° 12' W., bet. secs. 18 and 19.</p>
	<p>Over mountainous land through dense timber. Asc. over SE slope.</p>
<p>0.50</p>	<p>Spur, slopes S. 10° W.; desc. over W slope.</p>
<p>7.00</p>	<p>Draw, drains S. 20° W.; asc. over steep SE slope.</p>
<p>23.50</p>	<p>Spur, slopes S. 50° W.; desc. over NW slope.</p>
<p>30.50</p>	<p>McFait Canyon, drains S about 2.00 chs., thence turns W; asc. over SE slope.</p>
<p>35.50</p>	<p>Top of ascent, slopes S; desc. over W slope.</p>
<p>41.37</p>	<p>The ¼ sec. cor. of secs. 18 and 19, monumented with a limestone, 15 x 12 x 7 ins., set in a small mound of stone, plainly mkd. ¼.</p>
	<p>from which the original bearing trees</p>
	<p>A juniper limb, 6 ins. diam., bears N. 65° E., 23 lks. dist., scribed ¼S18BT. (Record, 16 lks.)</p>
	<p>A juniper, 9 ins. diam., bears S. 41° E., 24 lks. dist., scribed ¼ S19 BT. (Record, 22 lks.)</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., over a cross (X) on solid stone, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p>
	<p>T 6 S R 3 W</p>
	<p>¼ $\frac{S\ 18}{S\ 19}$</p>
	<p>1975</p>
	<p>Place the mkd. stone in mound of stone, alongside the iron post.</p>

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS		
	S. 89° 00' W., beginning new measurement.	
0.10	Top of ledge, 20 ft. high, bears N and S; desc. abruptly.	
1.00	McFait Canyon, drains N. 60° W.; asc. abruptly.	
1.50	Top of ledge, 20 ft. high, bears N. 60° W. and S. 60° E.	
4.00	Point of spur, slopes sharply N. 40 W.; desc. over ledgy NW slope.	
4.50	McFait Canyon, drains S. 30° W.; asc. over steep, rocky SE slope.	
10.00	Spur, slopes S; desc. over SW slope.	
16.50	Head of draw, drains S; asc. over SE slope.	
22.00	Spur, slopes S; desc. over SW slope.	
28.00	Head of draw, drains S; asc. over SE slope.	
40.00	Spur, slopes S. 45° W.	
40.76	The cor. of secs. 18 and 19, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., extending 6 ins. above mound of stone, 3½ ft. base, 2 ft. high, with brass cap mkd. as described in the official record of the 1926 resurvey.	
	from which the original bearing trees	
	A juniper, 10 ins. diam., bears N. 41° E., 41 lks. dist., scribed T6S R3W S18. (Record, 37 lks.)	
	A juniper, 10 ins. diam., bears S. 80° W., 12 lks. dist., scribed BT T6S R4W S24. (Record, 15 lks.)	
	A juniper limb, 5 ins. diam., bears N. 12° W., 38 lks. dist., scribed BT T6S R4W S13.	
	I added 1975 to the brass cap markings.	
	From the cor. of secs. 17, 18, 19, and 20.	
	N. 0° 01' E., bet. secs. 17 and 18.	
	Over mountainous land through dense timber. Asc. along rocky E slope.	
1.00	Spur, slopes S. 10° W.; asc. along W slope.	
7.50	Head of draw, drains S. 50° W.; asc. over SE slope.	
23.50	Spur, slopes S. 55° W. from N; asc. along W slope of spur.	
39.50	Trail road, on curve, bears N. 40° W. and S. 40° E. curving N.	
40.42	The ¼ sec. cor. of secs. 17 and 18, is determined at record bearing and distance from the remaining original bearing tree	
	A pinon, 9 ins. diam., bears S. 26° 45' E., 22 lks. dist., scribed ¼ S17 BT.	

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 6 S R 3 W

$\frac{1}{4}$
 |
 S 18 | S 17
 |

1975

Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W of cor.

N. $0^{\circ} 22'$ E., beginning new measurement.

Continue ascent along W slope of spur.

- 7.00 Spur, slopes S. 5° E., leave timber, bears NW and SE; asc. over SE slope through oak brush undergrowth.
- 13.50 Trail road, bears N. 35° E. and S. 35° W.
- 16.00 Trail road, bears N. 67° E. and S. 67° W.
- 23.27 Intersect line 3-4, Sage Hen lode, mineral survey No. 4251, at a point from which Cor. No. 3, identical with Cor. No. 5, Mattie No. 3 lode, same survey, bears S. $68^{\circ} 20'$ E., 2.10 chs. dist., monumented with a mound of stone.

At the claim corner point

Set a Copperweld monument, 30 ins. long, $\frac{5}{8}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

4251
 S H | M-3
 |
 3 | 5
 \ /

From the same point of intersection, Cor. No. 4, identical with Cor. No. 2, May Day lode, same survey, bears N. $68^{\circ} 20'$ W., 4.68 chs. dist., monumented with a badly decayed post in mound of stone.

At the claim corner point

Set a Copperweld monument, 30 ins. long, $\frac{5}{8}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

4251
 M D | S H
 |
 2 | 4
 / \

Asc. over S slope.

- 28.80 Ridge, bears N. 55° E. and S. 55° W., with trail road along top; desc. over NW slope.

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS					
33.00	Head of draw, drains W; asc. over SW slope.				
38.80	Eagle Hill ridge, bears E and W; desc. over steep N slope.				
39.96	<p>The cor. of secs. 7, 8, 17, and 18, monumented with a mound of stone. This point is harmoniously related to existing original corners and is accepted as the best available evidence of the original corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p> <div style="text-align: center;"> <p>T 6 S R 3 W</p> <table border="1" style="margin: auto;"> <tr> <td style="padding: 2px;">S 7</td> <td style="padding: 2px;">S 8</td> </tr> <tr> <td style="padding: 2px;">S 18</td> <td style="padding: 2px;">S 17</td> </tr> </table> <p>1975</p> </div>	S 7	S 8	S 18	S 17
S 7	S 8				
S 18	S 17				
	<p>S. 88° 07' E., bet. secs. 8 and 17.</p> <p>Over mountainous land through oak brush undergrowth. Asc. along steep N slope.</p>				
11.00	Eagle Hill ridge, bears nearly E and W; thence along ridge.				
28.20	Ridge, turns to N. 60° E.; desc. over SE slope.				
37.50	Trail road, bears N and S.				
40.83	<p>The ¼ sec. cor. of secs. 8 and 17, monumented with a limestone, 16 x 10 x 3 ins., firmly set 5 ins. in the ground, plainly mkd. ¼ on N face, and witnessed by a small mound of stone to the N.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 6 S R 3 W</p> <table border="1" style="margin: auto;"> <tr> <td style="padding: 2px;">¼</td> <td style="padding: 2px;">S 8</td> </tr> <tr> <td></td> <td style="padding: 2px;">S 17</td> </tr> </table> <p>1975</p> </div>	¼	S 8		S 17
¼	S 8				
	S 17				
	<p>Bury the mkd. stone alongside the iron post, and rebuild mound of stone, 2½ ft. base, 1½ ft. high, N of cor.</p>				
	<p>N. 89° 36' E., beginning new measurement.</p>				
	<p>Asc. along general S slope.</p>				
24.15	Trail road, bears N. 30° W. and curves S.				
26.38	<p>The closing cor. of secs. 8 and 17, on the old Ft. Crittenden Military Reservation Boundary, monumented with a limestone, 20 x 10 x 6 ins., set 10 ins. in the ground, mkd. CC on W face, with 4 notches on SE edge, and witnessed by a small mound of stone to the W.</p>				

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 6 S R 3 W

C S8 / S9
C S17 / OMRB

1973

Bury the mkd. stone alongside the iron post, and rebuild mound of stone, 2½ ft. base, 1½ ft. high, W of cor.

From this cor., angle point No. 9, on the old Ft. Crittenden Military Reservation Boundary, bears N. 58° 11' W., 2.27 chs. dist., hereinbefore described.

From this same cor., angle point No. 10, on the old Ft. Crittenden Military Reservation Boundary, bears S. 58° 11' E., 7.22 chs. dist., hereinbefore described.

From the cor. of secs. 7, 8, 17, and 18.

S. 89° 37' W., bet. secs. 7 and 18.

Over mountainous land through scattered timber and dense oak brush undergrowth; desc. along steep N slope.

- 2.50 Spur, slopes N. 80° W.; desc. over NW slope.
- 22.00 Draw, drains W; desc. along draw.
- 27.00 Draw, drains to N. 50° W.; desc. over NW slope.
- 33.00 Intersect line 11-12, Herchel No. 4 lode, mineral survey No. 3084, at a point from which Cor. No. 11, bears S. 2° 08' E., 18.00 chs. dist., monumented with a wood post, 4 x 4 ins., 4 ft. long, set in a mound of stone, scribed 11-3084.

from which the original bearing trees

A juniper limb, 8 ins. diam., bears S. 12° 15' W., 213 lks. dist., scribed 11-3084 BT.

A pinon, ins. diam., bears N. 87° W., 65 lks. dist., scribed 11-3084 BT.

From the same point of intersection, Cor. No. 12, identical with Cor. No. 13, Herchel No. 3 lode, same survey, bears N. 2° 08' W., 4.03 chs. dist., monumented with a wood post, 4 x 4 ins., 4 ft. long, in mound of stone, scribed 12-13-3084.

from which the original bearing trees

A pinon, 6 ins. diam., bears N. 86° E., 22 lks. dist., scribed 13-12-3084 BT.

A pinon, 10 ins. diam., bears S. 46° 15' W., 51 lks. dist., scribed 13-12-3084 BT.

Dependent Resurvey of a Portion of the Subdivision,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
40.36	<p>The $\frac{1}{4}$ sec. cor. of secs. 7 and 18, monumented with a limestone, 14 x 12 x 10 ins., set 6 ins. in the ground, plainly mkd. $\frac{1}{4}$ on N face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 3 W</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S 7}{S 18}$</p> <p style="text-align: center;">1975</p> <p>Bury the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89° 34' W., beginning new measurement.</p> <p>Continue descent over NW slope.</p>
2.15	Small draw, drains N, thence along steep, general N slope.
35.90	Spur, slopes N. 55° W.; desc. over SW slope.
41.98	<p>The cor. of secs. 7 and 18, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., extending 12 ins. above ground, with brass cap mkd. as described in the official record of the 1926 resurvey.</p> <p>from which the remaining original bearing trees</p> <p style="padding-left: 40px;">A dead juniper, 12 ins. diam., bears S. 70° E., 28 lks. dist., scribed BT T6S R3W S18. (Record, 35 lks.)</p> <p style="padding-left: 40px;">A juniper, 14 ins. diam., bears S. 5° W., 34$\frac{1}{2}$ lks. dist., scribed BT T6S R3W S13. (Record, 25 lks.)</p> <p>I added 1975 to the brass cap markings.</p>
<p>NOTE: A dependent resurvey of a portion of mineral survey Nos. 3047, 3072, 3133, 3153, 3154, 3157, 3160, 3169, 3239, 3433, 3620, 3707, 3925, 4250, 4498, and 4935, was necessary to properly determine the points of intersection and closures of the section lines with privately owned mineral claims in T. 6 S., R. 3 W.</p>	
<p style="text-align: center;">Dependent Resurvey of a Portion of Mineral Survey No. 3047, T. 6 S., R. 3 W., Salt Lake Meridian, Utah</p>	
<p style="text-align: center;">(Reestablishment of the Mineral Survey Executed by John T. Breckon in 1895)</p> <hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">GOLD BLOSSOM NO. 4 LODGE</p> <p>From Cor. No. 20, monumented with a decayed wood post, 4 x 4 ins., 2 ft. long, in a small mound of stone, with no visible scribe marks.</p>	

419

Dependent Resurvey of a Portion of
Mineral Survey No. 3047,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
	<p>From which an original bearing tree</p> <p>A pine, 9 ins. diam., bears S. 74° W., 37 lks. dist., scribed 20-3047 BT.</p> <p>From this cor., Cor. No. 1 of Annie Laura No. 1 lode, same survey, bears S. 37° 45' E., 11.89 chs. dist., hereinafter described.</p> <p>Thence,</p> <p>S. 5° 08' W., along the easterly end line.</p>
9.31	<p>Cor. No. 19, monumented with a decayed wood post, 4 x 4 ins., 3 ft. long, in a mound of stone, with no visible scribe marks.</p> <p>Thence,</p> <p>N. 37° 39' W., along the southerly side line.</p>
5.71	<p>Intersect line 1-2, Apex lode, mineral survey 3707, from which Cor. No. 1, identical to Cor. No. 5, Old Fred No. 2 Lode, same survey, bears S. 27° 47' W., 15.91 chs. dist., hereinafter described.</p> <p>From this intersection point, Cor. No. 2 of the Apex Lode, M.S. 3047, bears N. 27° 47' E., 2.25 chs. dist., monumented with a wood post, 4 x 4 ins., 4 ft. long, in a mound of stone, scribed 3707-2.</p> <p>from which the original bearing trees</p> <p>A juniper, 4 ins. diam., bears N. 15° E., 35 lks. dist., scribed 2-3707 BT.</p> <p>A juniper, 20 ins. diam., bears N. 75° W., 59 lks. dist., scribed 2-3707 BT.</p> <p>NOTE: Cor. No. 2 of the Apex Lode, M.S. 3047, should be on line bet. Cors. 18 and 19 of the Gold Blossom No. 4 lode, mineral survey 3047 according to the record.</p>
10.94	<p>Cor. No. 18, monumented with a wood post, 4 x 4 ins., 4 ft. long, in a mound of stone, scribed 3047-18.</p> <p>from which the bearing trees</p> <p>A pine, 8 ins. diam., bears N. 68° E., 6 lks. dist., scribed 3047-18.</p> <p>A pine, 10 ins. diam., bears S. 50° W., 15 lks. dist., scribed 3047-18.</p> <p>Thence,</p> <p>N. 5° 46' E., along the westerly end line.</p>
9.17	<p>Cor. No. 17, monumented with a wood post, 4 x 4 ins., 3½ ft. long, in a mound of stone, with no visible scribe marks.</p> <p>from which the original bearing trees</p>

Dependent Resurvey of a Portion of
Mineral Survey No. 3047,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

A juniper, 13 ins. diam., bears S. 51° W., 20 lks. dist., scribed 3047-17.

A juniper, 16 ins. diam., bears N. 70° W., 34 lks. dist., scribed 3047-17.

ANNIE LAURA NO. 1 LODE

From Cor. No. 1 monumented with a decayed wood post, 4 x 4 ins., 4 ft. long in a mound of stone, with no visible scribe marks.

From which the original bearing tree and object

A juniper stump, 24 ins. diam., bears N. 3° E., 46 lks. dist., with no visible scribe marks.

A juniper, 12 ins. diam., bears N. 45° E., 47.5 lks. dist., scribed 1-3047 BT.

Thence,

N. 38° 29' E., along the southerly end line.

9.04 Cor. No. 4 identical to Cor. No. 5 of Annie Laura lode, same survey, monumented with a wood post, 4 x 4 ins., 4 ft. long, in a mound of stone, scribed 5-3047.

from which an original bearing tree

A juniper, 8 ins. diam., bears N. 87° W., 39 lks. dist., scribed 3047-4.

ANNIE LAURA LODE

From Cor. No. 5 identical to Cor. No. 4 of Annie Laura No. 1 lode, same survey, hereinbefore described.

Thence,

N. 38° 14' E., along the southerly end line.

9.32 Cor. No. 8 identical to Cor. No. 9 of Annie Laura No. 3 lode, same survey, monumented with a decayed wood post, 4 x 4 ins., 3 ft. long, in a mound of stone, with no visible scribe marks.

from which an original bearing tree

A pine, 14 ins. diam., bears S. 58° 50' E., 186 lks. dist., scribed 9-BT.

ANNIE LAURA NO. 3 LODE

From Cor. No. 9 identical to Cor. No. 8 of Annie Laura lode, same survey, hereinbefore described.

Thence,

N. 38° 19' E., along the southerly end line.

5.67 Intersect line 2-3 of Bethel lode, mineral survey 3239, hereinafter described.

Dependent Resurvey of a Portion of
Mineral Survey No. 3047,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
6.22	<p>Cor. No. 12, hereinbefore described.</p> <p>Thence, N. 38° 03' W., along the easterly side line.</p>
0.28	<p>Intersect line 2-3, Bethel lode, mineral survey 3239, hereinafter described.</p>
22.08	<p>Cor. No. 11 monumented with a wood post, 4 x 4 ins., 3 ft. long, in a mound of stone with no visible scribe marks.</p> <p>from which an original bearing object</p> <p style="padding-left: 40px;">A pine stump, 10 ins. diam., bears N. 45° E., 15 lks dist., scribed 11-3047 BT.</p> <p>From this cor., Cor. No. 13 of Annie Laura No. 2 lode, same survey, bears S. 38° 39' W., 1.82 chs. dist., hereinafter described.</p>
ANNIE LAURA NO. 2 LODE	
	<p>From Cor. No. 14 identical to Cor. No. 2 Annie Laura No. 1 lode, same survey, monumented with a wood post, 4 x 4 ins., 4 ft. long in a mound of stone, scribed 14-3047 and 2-3047.</p> <p>from which the original bearing trees</p> <p style="padding-left: 40px;">A juniper, 12 ins. diam., bears S. 68° E., 35.5 lks. dist., scribed 2-3047 BT.</p> <p style="padding-left: 40px;">A juniper, 12 ins. diam., bears N. 52° E., 62 lks. dist., scribed 2-3047 BT.</p> <p>Thence, N. 33° 52' W., along the westerly end line.</p>
0.44	<p>Cor. No. 17 of Gold Blossom No. 4 lode, same survey, hereinbefore described.</p> <p>N. 37° 21' W., beginning new measurement.</p>
4.85	<p>Intersect line 22 - 23, Gold Blossom No. 3 lode, same survey, hereinafter described.</p>
8.73	<p>Cor. No. 15 monumented with a wood post, 4 x 4 ins., 4 ft. long in a mound of stone, dimly scribed.</p> <p>from which the original bearing trees</p> <p style="padding-left: 40px;">A juniper, 16 ins. diam., bears S. 30° 30' W., 9 lks. dist., scribed 15-3047 BT.</p> <p style="padding-left: 40px;">A pine, 13 ins. diam., bears N. 81° 35' W., 6 lks. dist., scribed 15-3047 BT.</p> <p>Thence, N. 38° 22' E., along the northerly side line.</p>
7.57	<p>Intersect line 21 - 22, Gold Blossom No. 3 lode, same survey, hereinafter described.</p>

Dependent Resurvey of a Portion of
Mineral Survey No. 3047,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
22.57	<p>Cor. No. 16, monumented with a wood post, 4 x 4 ins., 4 ft. long, in a mound of stone, with illegible scribe marks.</p> <p>from which the original bearing trees</p> <p>A pine, 24 ins. diam., bears N. 36° E., 8 lks. dist., scribed 16-3047 BT.</p> <p>A juniper, 36 ins. diam., bears S. 38° E., 31 lks. dist., scribed 16-3047 BT.</p> <p>Thence,</p> <p>S. 37° 50' E., along the easterly end line.</p>
9.24	<p>Cor. No. 13, monumented with a wood post, 4 x 4 ins., 4 ft. long, in a mound of stone with no visible scribe marks.</p> <p>from which the original bearing tree and object</p> <p>A juniper, 36 ins. diam., bears S. 40° E., 61 lks. dist., scribed with faint marks.</p> <p>A pine stump, 20 ins. diam., bears S. 53° W., 76 lks. dist., scribed 13-30.</p>
GOLD BLOSSOM NO. 3 LODGE	
<p>From Cor. No. 21, identical with Cor. No. 26 of Gold Blossom No. 2 Amended lode, same survey, hereinbefore described.</p>	
<p>Thence,</p> <p>S. 13° 57' E., along the easterly side line.</p>	
13.19	<p>Intersect line 15 - 16, Annie Laura No. 2 lode, same survey, hereinbefore described.</p>
21.88	<p>Cor. No. 22, monumented with a wood post, 4 x 4 ins., 4½ ft. long in a mound of stone, scribed 22-3047.</p> <p>Thence,</p> <p>S. 82° 28' W., along the southerly end line.</p>
4.48	<p>Intersect the line between Cor. No. 15 of Annie Laura No. 2 lode and Cor. No. 17 of Gold Blossom No. 4 lode, same survey, hereinbefore described.</p>
6.40	<p>Cor. No. 23 monumented with a decayed wood post, 4 x 4 ins., 4 ft. long, in a mound of stone with no visible scribe marks.</p> <p>Thence,</p> <p>N. 20° 29' W., along the westerly side line.</p>
21.77	<p>Cor. No. 24 identical to Cor. No. 27 of Gold Blossom No. 2 Amended lode, same survey, hereinbefore described.</p>

Dependent Resurvey of a Portion of
Mineral Survey No. 3047,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

GOLD BLOSSOM NO. 2 AMENDED LODE

Note: This amended resurvey was made for the purpose of showing the areas in conflict with the Afix and Monta No. 1 lodes unsurveyed by judgement rendered December 29, 1897 and excluding areas in conflict between said lodes and Gold Blossom No. 1 lode and Compromise area in conflict with the Afix unsurveyed and the Gold Blossom No. 2 lodes.

From Cor. No. 28, identical with Cor. No. 34 of Gold Blossom No. 1 amended lode, same survey, hereinbefore described.

Thence,

N. 79° 27' E., along the northerly end line.

6.16 Intersect the westernly side line of Afix lode, unsurveyed, hereinbefore described.

9.05 Cor. No. 25, identical to Cor. No. 29 of Gold Blossom No. 1 amended lode, same survey, hereinbefore described.

AFIX LODE (UNSURVEYED)

From the NW cor., Afix lode (unsurveyed) identical to SW cor. of Monta No. 1 lode (unsurveyed, same survey, monumented with a wood post, 3 x 3 ins., 5 ft. long, in a mound of stone, with no visible scribe marks.

At the claim corner

Set an aluminum post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

S 17 | M-1
SW

AFIX
NW

1980

Thence,

S. 13° 04' W., along the westernly side line of Afix lode (unsurveyed).

1.35 Intersect line 25 - 28 of Gold Blossom No. 2 amended lode, identical with line 29 - 34 of Gold Blossom No. 1 amended lode, same survey, hereinbefore described.


3.01 Intersect the line between secs. 17 and 20, hereinbefore described.

11.07 Point for the SW cor. of the compromise area, at single proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, to top of aluminum cap, mkd.

Dependent Resurvey of a Portion of
Mineral Survey No. 3047,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS




1980

From this cor., the SW cor. of Afix lode, bears S. 13° 04' W., 8.28 chs. dist., monumented with a decayed wood post, 4 x 4 ins., 4 ft. long, in a mound of stone, with no visible scribe marks.

At the claim corner

Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.



1980

Thence,

N. 82° 53' E.,

7.75

Intersect line 25 - 26 of Gold Blossom No. 2 lode, mineral survey 3047, at midpoint, from which Cor. No. 26, bears S. 16° 22' E., 9.435 chs. dist., hereinbefore described.

Dependent Resurvey of a Portion of
Mineral Survey No. 3072,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

(Reestablishment of the Mineral Survey
Executed by John T. Breckon in 1895)

LOST LINK LODE

From Cor. No. 1 hereinafter described.

Thence,

S. 0° 49' E., along the westerly side line.

0.98

Intersect line 1 - 2, Accident lode, mineral survey 4250, hereinafter described.

20.57

Cor. No. 2 identical to Cor. No. 20 Excess lode, same survey, monumented with a pine post, 4 x 4 ins., 3½ ft. long, in a mound of stone, with faint illegible scribe marks.

From which the original bearing trees

A pine, 12 ins. diam., bears N. 16° E., 45 lks. dist., scribed 2-3072 BT.

A juniper, 15 ins. diam., bears S. 19° 15' W., 1.00 chs. dist., scribed 20-3072 BT.

Dependent Resurvey of a Portion of
Mineral Survey No. 3072,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

EXCESS LODE

From Cor. No. 20 identical to Cor. No. 2 Lost Link lode, same survey, hereinbefore described.

Thence,

S. 18° 13' E., along the westerly end line.

6.17 Cor. No. 19 identical to Cor. No. 4 of Free Coinage lode, mineral survey 3433, monumented with a rotted pine post in a mound of stone, no visible scribe marks.

from which the original bearing trees

A juniper, 11 ins. diam., bears N. 80° W., 13.3 lks. dist., scribed 19-3072.

A juniper, 18 ins. diam., bears S. 41° 35' E., 64 lks. dist., scribed 4-3433.

At the claim corner point

Set an iron T stake, 24 ins. long, 1 in. diam., 18 ins. in the ground, in a mound of stone, with rotted pine post alongside and steel cap mkd.

3072
19 E
4 FC
3433

Dependent Resurvey of a Portion of
Mineral Survey No. 3133,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

(Reestablishment of the Mineral Survey
Executed by John T. Breckon in 1895)

RED CLOUD LODE

From Cor. No. 1 monumented with a decayed wood post, 2 x 2 ins., 2 ft. long, in a mound of stone, with no visible scribe marks.

From this cor., the sec. cor. of secs. 20, 21, 28, and 29, bears S. 51° 46' E., 1.99 chs. dist., hereinbefore described.

Thence,

N. 69° 53' W., along the northerly end line.

6.78 Intersect line 2 - 3, Armstrong lode, mineral survey 3239, hereinafter described.

9.07 Point for Cor. No. 4 reestablished from an original bearing tree.

A juniper, 12 ins. diam., bears S. 74° 40' W., 1.35 chs. dist., scribed 4-3707 BT.

Dependent Resurvey of a Portion of
Mineral Survey No. 3133,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

At the claim corner point

Set an iron T stake, 24 ins. long, 1 in. diam., 18 ins. in. the ground, with steel cap mkd.




Thence,

S. 21° 10' W., along the westerly side line.

3.00 Point for Cor. No. 1 of Old Fred lode, mineral survey 3707, at single proportionate distance; there is no remaining evidence of the original claim cor.

Set an iron T stake, 24 ins. long, 1 in. diam., 18 ins. in the ground, with steel cap mkd.



Raise a mound of stone, 3 ft. base, 2½ ft. high, N of cor.

22.63 Cor. No. 3 identical to Cor. No. 2 Old Fred lode, mineral survey 3707, monumented with a decayed wood post, 4 x 4 ins., 3½ ft. long, in a mound of stone, with no visible scribe marks.

Dependent Resurvey of Portions of
Mineral Surveys No. 3154, 3160 and 3153,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

(Reestablishment of the Mineral Survey
Executed by E.M. LeProhon in 1895)

GOLDEN RULE NO. 3 LODE (3153)

From Cor. No. 3 monumented with a wood post, 4 ft. long, 4 x 4 ins., in a mound of stone, with no visible scribe marks.


From this cor., Cor. No. 6 of Gold Rule No. 4 lode, mineral survey 3160, bears N. 76° 22' W., 3.20 chs. dist., hereinafter described.

Thence,



N. 21° 43' W., along the easterly side line.

23.15 Point for the Cor. No. 4, at proportionate distance based on the Grant Boundary method; there is no remaining evidence of the original corner.

Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.



Dependent Resurvey of Portions of
Mineral Surveys No. 3154, 3160, and 3153,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
9.26	<p>Thence, N. 87° 43' W., along the northerly end line. Cor. No. 1, monumented with a wood post, 4 ft. long, 4 x 4 ins., in a mound of stone, with no visible scribe marks. From this cor., Cor. No. 4 of May Bell lode, mineral survey 3154, bears S. 22° 00' E., 9.00 chs. dist., here- tofore described.</p>
<p>Dependent Resurvey of a Portion of Mineral Survey No. 3160, T. 6 S., R. 3 W., Salt Lake Meridian, Utah</p>	
<p>(Reestablishment of the Mineral Survey Executed by E.M. LeProhon in 1895)</p>	
<p>GOLDEN RULE NO. 4 LODGE (3160)</p>	
<p>From the point for Cor. No. 3, at single proportionate distance on line between Cor. No. 6 and Cor. No. 7 of Gold Dust No. 1 lode, mineral survey 3154; there is no remaining evidence of the original claim corner.</p>	
<p>Set a Copperweld monument, 30 ins. long, 5/8 ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p>	
	
<p>From this cor., Cor. No. 2, same survey, identical with Cor. No. 7, Gold Dust No. 1, mineral survey 3154, bears S. 87° 53' E., 2.84 chs. dist., hereinbefore described.</p>	
<p>Thence, S. 21° 15' E., along the westerly side line.</p>	
1.32	<p>Cor. No. 12 of Emma lode, same survey, mineral survey 3154, hereinbefore described. S. 21° 28' E., beginning new measurement.</p>
8.13	<p>Point for cor. No. 11 of Emma lode, mineral survey 3154, at single proportionate distance; there is no remaining evidence of the original claim cor. Set a Copperweld monument, 30 ins. long, 5/8 ins. diam., 2 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p>
	
15.18	<p>Cor. No. 4, monumented with a decayed wood post in small mound of stone.</p>

Dependent Resurvey of a Portion of
Mineral Survey No. 3160,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS


Thence,

S. 86° 19' E., along the southerly end line.

8.47

Point for Cor. No. 5, at proportionate distance based on the Grant Boundary method; there is no remaining evidence of the original claim corner.

Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with a collar of stone and aluminum cap mkd.



Thence,

N. 20° 19' W., along the easterly side line.

21.17

Cor. No. 6, monumented with a wood post, 4 x 4 ins., 4 ft. long, in a mound of stone, with no visible scribe marks.

Dependent Resurvey of a Portion
of Mineral Survey No. 3169,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

ALPHA LODE

From Cor. No. 18, monumented with a decayed wood post, 4 x 4 ins. in mound of stone.

from which

A juniper, an original bearing tree, 8 ins. diam., bears N. 73° 15' E., 98 lks. dist., scribed 18-3169 BT.

Cor. No. 11, Mugwump No. 2 lode, same survey, bears N. 54° 20' E., 12.68 chs. dist., hereinbefore described.

N. 3° 00' E., along the westerly end line.

6.08

Intersect the line bet. secs. 16 and 21, at a point from which the ¼ sec. cor. of secs. 16 and 21, bears S. 89° 59' W., 13.58 chs. dist., hereinbefore described.


6.49

Intersect line 2 - 3, Doe Run No. 4, mineral survey 4935, hereinafter described.

7.41

Point for Cor. No. 19, at proportionate distance based on the Grant Boundary method; there is no remaining evidence of the original claim corner.

Set a Copperweld monument, 30 ins. long, 5/8 ins. diam., 20 ins. in the ground, with brass cap mkd.




Thence,

N. 52° 11' E., along the northerly side line.

Dependent Resurvey of a Portion of
Mineral Survey No. 3169,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

- 19.73 Point for Cor. No. 20 at proportionate distance based on the Grant Boundary method; there is no remaining evidence of the original claim corner.
- Set a Copperweld monument, 30 ins. long, 5/8 ins. diam., 20 ins. in the ground, with brass cap mkd.



Thence,

S. 2° 07' W., along the easterly end line.

- 8.26 Cor. No. 21, monumented with a charred wood post, 4 x 4 ins., 4 ft. long, in mound of stone,

from which the original bearing trees

A juniper, 10 ins. diam., bears N. 31° 15' W., 80 lks. dist., scribed 21-3169 BT. (Record, N. 28° 41' W., 53.6 ft.)

A pinon, 12 ins. diam., bears N. 65° E., 150 lks. dist., scribed 21-3169 BT. (Record, N. 65° 23' E., 96.8 ft.)

At the claim corner point

Set a Copperweld monument, 30 ins. long, 5/8 ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.



From this cor., Cor. No. 11, Mugwump No. 2 lode, same survey, bears S. 54° 23' W., 6.58 chs. dist., hereinbefore described.

Dependent Resurvey of a Portion of
Mineral Survey No. 3239,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

(Reestablishment of the Mineral Survey
Executed by Frank Anderson in 1896)

ARMSTRONG LODE

From Cor. No. 3 monumented with a wood post, 3 x 3 ins., 4 ft. long, in a mound of stone, with no visible scribe marks.

From this cor., the sec. cor. of secs. 20, 21, 28, and 29, bears S. 72° 10' E., 8.59 chs. dist., hereinbefore described.

Thence,

N. 14° 40' E., along the westerly end line.

- 0.97 Intersect line 1 - 4 of Red Cloud lode, mineral survey No. 3133, hereinbefore described.

Dependent Resurvey of a Portion of
Mineral Survey No. 3239,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS		
3.50	<p>Cor. No. 2, on line 1 - 4, Silver Hill lode, same survey, monumented with a wood post, 4 x 4 ins., 4 ft. long, in a mound of stone, with faint scribe marks.</p>	
	<p style="text-align: center;">SILVER HILL LODE</p> <p>From Cor. No. 4 monumented with a wood post, 4 x 4 ins., 3½ ft. long, in a mound of stone, with no visible scribe marks.</p> <p>from which the original bearing trees</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears N. 15° E., 46 lks. dist., scribed 4-3239 BT. (Record, N. 16° 13' E.)</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears S. 84° E., 48 lks. dist., scribed 4-3239 BT. (Record, S. 89° 01' E.)</p> <p>From this cor., Cor. No. 2 of Armstrong lode, same survey, bears S. 35° 14' E., 15.94 chs. dist., heretofore described.</p> <p>Thence,</p> <p>N. 50° 30' E., along the northerly end line.</p>	
8.19	<p>Cor. No. 3 monumented with a wood post, 4 x 4 ins., 4 ft. long, in a mound of stone, with no visible scribe marks.</p> <p>From this cor., Cor. No. 5 of Tamar lode, same survey, bears S. 32° 35' E., 1.08 chs. dist., hereinafter described.</p>	
	<p style="text-align: center;">TAMAR LODE</p> <p>From Cor. No. 5 monumented with a wood post, 4 x 4 ins., 4 ft. long, in a mound of stone, with no visible scribe marks.</p> <p>Thence,</p> <p>N. 21° 54' E., along the westerly side line.</p>	
15.21	<p>Cor. No. 6, identical to Cor. No. 2 of Bethel lode, same survey, monumented with a wood post, 4 x 4 ins., 18 ins. long, in a mound of stone, scribed MS-3239.</p> <p>from which an original bearing tree</p> <p style="padding-left: 40px;">A juniper, 12 ins. diam., bears S. 35° 14' E., 195 lks. dist., scribed 3239-6 BT.</p>	
	<p style="text-align: center;">BETHEL LODE</p> <p>From Cor. No. 2, identical to Cor. No. 6 of Tamar lode, same survey, hereinbefore described.</p> <p>Thence,</p> <p>N. 14° 41' E., along the westerly side line.</p>	
2.60	<p>Intersect line 9 - 12 of Annie Laura No. 3 lode, mineral survey 3047, hereinbefore described.</p>	

Dependent Resurvey of a Portion of
Mineral Survey No. 3239,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
3.26	Intersect line 11 - 12 of Annie Laura No. 3 lode, mineral survey 3047, hereinbefore described.
16.55	Intersect line 2 - 3 of David S. lode, same survey, hereinafter described.
16.89	Intersect the line between secs. 20 and 21, at a point from which the $\frac{1}{4}$ sec. cor. of secs. 20 and 21, bears S. $0^{\circ} 25'$ W., 14.06 chs. dist., hereinbefore described.
22.63	Cor. No. 3, monumented with a wood post, 4 x 4 ins., 2 ft. long, in a mound of stone, scribed B.
DAVID S. LODE	
From Cor. No. 2 identical to Cor. No. 3 of Sun Down Mine lode, same survey, monumented with a wood post, 4 x 4 ins., 2 ft. long, in a mound of stone, scribed 3-3239.	
Thence,	
S. $29^{\circ} 42'$ W., along the southerly end line.	
3.13	Intersect the line between secs. 20 and 21, at a point from which the $\frac{1}{4}$ sec. cor. of secs. 20 and 21, bears S. $0^{\circ} 25'$ W., 13.88 chs. dist., hereinbefore described.
3.30	Intersect line 2 - 3 of Bethel lode, same survey, hereinbefore described.
7.03	Cor. No. 3, monumented with a wood post, 4 x 4 ins., 2 ft. long, in a mound of stone, scribed 3-3239.
Thence,	
N. $8^{\circ} 41'$ W., along the westerly side line.	
13.80	Cor. No. 4, monumented with a wood post, 4 x 4 ins., 3 ft. long, in a mound of stone, with no visible scribe marks.
from which an original bearing tree	
A dead pine, 10 ins. diam., bears N. 41° E., 71 lks. dist., scribed 4-3239 BT.	
Thence,	
N. $29^{\circ} 48'$ E., along the northerly end line.	
1.73	Cor. No. 1, monumented with a wood post, 4 x 4 ins., 2 ft. long, in a mound of stone, scribed 1-3239 BT.
from which the original bearing trees	
A pine, 10 ins. diam., bears N. 55° E., 32 lks. dist., scribed 1-3239 BT.	
A pine, 11 ins. diam., bears S. 4° W., 30 lks. dist., scribed 1-3239 BT. (Record, S. $3^{\circ} 40'$ W.)	
From this cor., Cor. No. 4 of Sun Down Mine lode, same survey, bears N. $27^{\circ} 13'$ W., 12.54 chs. dist., monumented with a wood post, 4 x 4 ins., 4 ft. long, in a mound of stone, scribed 3239-4 on E face and 3925-2 on W face.	

Dependent Resurvey of a Portion of
Mineral Survey No. 3239,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

from which an original bearing tree

A pine, 20 ins. diam., bears S. 40° 27' W.,
56 lks. dist., scribed 4-3239 BT.

Dependent Resurvey of a Portion of
Mineral Survey No. 3433,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

(Reestablishment of the Mineral Survey
Executed by John T. Breckon in 1897)

FREE COINAGE LODE

From Cor. No. 4, identical to Cor. No. 19 of Excess lode,
mineral survey 3072, hereinbefore described.

Thence,

S. 23° 01' E., along the westerly side line.

4.92

Cor. No. 3 of Lower Reef lode, same survey, monumented
with a pine post, 4 x 4 ins., 4 ft. long, in a mound of
stone, no visible scribe marks.

from which an original bearing tree

A juniper, 13 ins. diam., bears S. 3° 20' E.,
23.5 lks. dist., scribed BT 3-3433.

LOWER REEF LODE

From Cor. No. 3, hereinbefore described.

Thence,

S. 46° 56' W., along the westerly side line.

20.83

Cor. No. 4, monumented with a cedar post, 4 x 4 ins.,
3½ ft. long, in a mound of stone, scribed 4-3433.

from which the original bearing trees

A juniper, 8 ins. diam., bears N. 30° 30' E.,
9 lks. dist., scribed BT 4-3433.

A juniper, 8 ins. diam., bears S. 37° W., 27 lks.
dist., scribed BT 4-3433.

from the same corner point

Cor. No. 3 of Ot lode, same survey, bears
N. 24° 34' W., 15 lks. dist., hereinafter described.

OT LODE

From Cor. No. 3, monumented with a cedar post, 4 x 4 ins.,
3½ ft. long, in a mound of stone, scribed 3-3433.

Thence,

S. 50° 22' W., along the westerly end line.


Dependent Resurvey of a Portion of
Mineral Survey No. 3433,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
9.12	Cor. No. 2, identical to Cor. No. 2 of Lehi lode, same survey, monumented with a pine post, 4 x 4 ins., 4 ft. long, in a mound of stone, no visible scribe marks.
LEHI LODE	
From Cor. No. 2, identical to Cor. No. 2 of Ot lode, same survey, hereinbefore described.	
Thence,	
S. 49° 45' W., along the westerly end line.	
8.43	Cor. No. 3, hereinbefore described.
Dependent Resurvey of a Portion of Mineral Survey No. 3620, T. 6 S., R. 3 W., Salt Lake Meridian, Utah	
(Reestablishment of the Mineral Survey Executed by Vivian P. Strange in 1898)	
MERCUR BOY NO. 1 LODE	
From Cor. No. 2, identical with Cor. No. 3, Mercur Boy No. 5 lode, same survey, hereinbefore described.	
N. 16° 44' W., along the westerly side line.	
2.50	Intersect the old Ft. Crittenden Military Reservation Boundary, hereinbefore described.
20.75	Point for Cor. No. 3, identical with Cor. No. 5, Mercur Boy No. 4 lode, same survey, at proportionate distance based on the Grant Boundary method; there is no remaining evidence of the original claim corner.
Set a Copperweld monument, 30 ins. long, 5/8 ins. diam., 20 ins. in the ground, with brass cap mkd.	
$\begin{array}{r} 3620 \\ 5 \text{ MB-4} \\ \hline 3 \text{ MB-1} \end{array}$	
MERCUR BOY NO. 4 LODE	
From Cor. No. 5, identical with Cor. No. 3, Mercur Boy No. 1 lode, same survey, hereinbefore described.	
N. 33° 22' W., along the westerly end line.	
1.36	Intersect the line bet. secs. 9 and 16, at a point from which the closing cor. of secs. 9 and 16, identical with angle point No. 10, on the old Ft. Crittenden Military Reservation Boundary, bears N. 89° 51' W., 7.35 chs. dist., hereinbefore described.
6.90	Point for Cor. No. 6 at proportionate distance based on the Grant boundary method; there is no remaining evidence of the original claim corner.

Dependent Resurvey of a Portion of
Mineral Survey No. 3620,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

Set a Copperweld monument, 30 ins. long, 5/8 ins. diam.,
24 ins. in the ground, with brass cap mkd.



From this cor., the closing cor. of secs. 9 and 16,
identical with angle point No. 10, on the old Ft.
Crittenden Military Reservation Boundary, bears
S. 43° 03' W., 6.30 chs. dist., hereinbefore described.


Thence,

N. 79° 50' E., along the northerly side line.

16.98 Cor. No. 1, monumented with a rotted wood post, 4 x 4 ins.,
2 ft. long, in small mound of stone.

At the claim corner point

Set a Copperweld monument, 30 ins. long, 5/8 ins. diam.,
24 ins. in the ground, with brass cap mkd.



Thence,

S. 32° 53' E., along the easterly side line.

3.74 Cor. No. 2, monumented with a wood post, 4 x 4 ins.,
in mound of stone, with illegible scribe marks.

from which the original bearing trees

A dead juniper, 10 ins. diam., bears N. 45° E.,
100 lks. dist., scribed 2-3620 BT.

A dead pinon, 10 ins. diam., bears S. 87° 45' W.,
90 lks. dist., scribed 2-3620 BT.


Thence,

S. 4° 40' E., along the easterly side line.

4.53 Cor. No. 3, identical with Cor. No. 5 Red Bird No. 2 lode,
same survey, monumented with a rooted wood post, 4 x 4
ins., in small mound of stone.

At the claim corner point

Set a Copperweld monument, 30 ins. long, 5/8 ins. diam.,
24 ins. in the ground, with brass cap mkd.



From this cor., Cor. No. 6, Red Bird No. 2 lode, same
survey, bears N. 76° 50' E., 4.39 chs. dist., hereinbefore
described.

Dependent Resurvey of a Portion of
Mineral Survey No. 3707,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	<p>Dependent Resurvey of a Portion of Mineral Survey No. 3707, T. 6 S., R. 3 W., Salt Lake Meridian, Utah</p>
	<p>(Reestablishment of the Mineral Survey Executed by John T. Breckon in 1898)</p> <p style="text-align: center;">OLD FRED LODE</p> <p>From Cor. No. 1, hereinbefore described.</p> <p>Thence, N. 52° 17' W., along the northerly end line.</p> <p>8.45 Cor. No. 5, monumented with a decayed wood post, 3 x 3 ins., 4 ft. long, in a small mound of stone, with no visible scribe marks.</p> <p>from which the original bearing trees</p> <p style="padding-left: 40px;">A juniper, 15 ins. diam., bears N. 23° E., 26 lks. dist., scribed 5-3707 BT.</p> <p style="padding-left: 40px;">A juniper, 8 ins. diam., bears S. 88° 40' E., 11 lks. dist., scribed 5-3707 BT.</p> <p>Thence, S. 23° 03' W., along a portion of the westerly side line.</p> <p>3.77 Cor. No. 3 of Home Stake lode, same survey, on line 4 - 5, Old Fred lode, monumented with a wood post, 4 x 4 ins., 4 ft. long, in a mound of stone, scribed 3-3707.</p> <p>from which an original bearing tree</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears S. 31° 40' W., 14 lks. dist., scribed 3707 BT.</p>
	<p style="text-align: center;">HOME STAKE LODE</p> <p>From Cor. No. 3, hereinbefore described.</p> <p>Thence, N. 38° 10' W., along the northerly side line.</p> <p>12.94 Cor. No. 4, identical with Cor. No. 4 Apex lode, same survey, monumented with a wood post, 4 x 4 ins., 3½ ft. long, in a mound of stone, with illegible scribe marks.</p>
	<p style="text-align: center;">APEX LODE</p> <p>From Cor. No. 19 of Gold Blossom No. 4 lode, mineral survey 3047, hereinbefore described.</p> <p>S. 40° 39' E., along the northerly end line of Apex lode.</p>


Dependent Resurvey of a Portion of
Mineral Survey No. 3707,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

2.71

Point for Cor. No. 3, at proportionate distance based on the Grant Boundary method; there is no remaining evidence of the original claim corner.

Set an iron T stake, 24 ins. long, 1 in. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of steel cap mkd.



Thence,

S. 26° 09' W., along the easterly side line.

6.40

Cor. No. 4, identical to Cor. No. 4 of Home Stake lode, same survey, hereinbefore described.

OLD FRED NO. 2 LODE

From Cor. No. 5, identical to Cor. No. 1 of Apex Lode, same survey, monumented with a wood post, 4 x 4 ins., 4 ft. long, in a mound of stone, with no visible scribe marks.

from which the original bearing trees

A pine, 12 ins. diam., bears S. 19° W., 19 lks. dist., scribed 5-1-3707.

A juniper, 13 ins. diam., bears S. 39° E., 26 lks. dist., scribed 5-1-3707.

Thence,

S. 22° 53' W., along the westerly end line.

7.35

Cor. No. 1, monumented with a wood post, 4 x 4 ins., 4 ft. long, in a mound of stone, scribed 3707-1.

From this cor., Cor. No. 1 of Ouida lode, same survey, bears N. 39° 26' W., 31 lks. dist., hereinbefore described.

Dependent Resurvey of a Portion of
Mineral Survey No. 3925,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

(Reestablishment of the Mineral Survey
Executed by John T. Breckon in 1899)

GOLDEN WEDGE LODE

From Cor. No. 1, monumented with a wood post, 4 x 4 ins., 3½ ft. long, in a mound of stone, scribed 1-3925.

From this cor., Cor. No. 4 of Sun Down Mine lode, mineral survey 3239, bears N. 14° 56' W., 2.85 chs. dist., hereinbefore described.

Thence,

S. 82° 00' W., along the southerly end line.

9.19

Cor. No. 5, hereinbefore described.


437
 Dependent Resurvey of a Portion of
 Mineral Survey No. 4250,
 T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	<p>Dependent Resurvey of a Portion of Mineral Survey No. 4250, T. 6 S., R. 3 W., Salt Lake Meridian, Utah</p>
	<p>(Reestablishment of the Mineral Survey Executed by E.M. LeProhon in 1899)</p>
	<p>ORIENT LODE</p>
	<p>From Cor. No. 1, monumented with a pine post, 4 x 4 ins., 3 ft. long, in a mound of stone, scribed 4250-1.</p>
	<p>Thence, N. 89° 35' W., along the northern end line.</p>
4.26	<p>Intersect line 3 - 4 of Ouida lode, mineral survey 3707, from which Cor. No. 4 bears N. 43° 49' W., 6.11 chs. dist., hereinbefore described.</p>
9.10	<p>Cor. No. 4, monumented with a pine post, 4 x 4 ins., 5 ft. long, with faint illegible scribe marks, in a mound of stone.</p>
	<p>Thence, S. 0° 07' W., along the westerly side line.</p>
14.53	<p>Cor. No. 3, monumented with a pine post, 4 x 5 ins., 4 ft. long, in a mound of stone scribed 4250-3. from which an original bearing tree A juniper, 24 ins. diam., bears S. 54° W., 29.7 lks. dist., scribed BT-3-4250.</p>
	<p>Thence, N. 88° 37' E., along the southerly end line.</p>
0.35	<p>Cor. No. 4, Pinto lode, same survey, monumented with a pine post, 4 x 4 ins., 4 ft. long, in a mound of stone, scribed 4-4250.</p>
	<p>S. 89° 36' E., beginning new measurement.</p>
8.83	<p>Cor. No. 2, monumented with a pine post, 4 x 4 ins., 3½ ft. long, in a mound of stone, scribed 4250-2.</p>
	<p>Thence, N. 0° 40' W., along the easterly side line.</p>
5.22	<p>Cor. No. 4, Accident lode, same survey, monumented with a pine post, 4 x 4 ins., 4 ft. long, in a mound of stone, no visible scribe marks.</p>
	<p>N. 0° 04' E., beginning new measurement.</p>
4.90	<p>Intersect line 3 - 4 of Ouida lode, mineral survey 3707, from which Cor. No. 3 bears S. 43° 49' E., 9.64 chs. dist., monumented with a pine post, 4 x 4 ins., 4 ft. long, in a mound of stone scribed 3707-3.</p>

Dependent Resurvey of a Portion of
Mineral Survey No. 4250,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
9.31	<p>from which the original bearing trees</p> <p>A juniper, 13 ins. diam., bears S. 3° E., 51 lks. dist., scribed BT 3-3707.</p> <p>A juniper, 7 ins. diam., bears N. 82° W., 21 lks. dist., scribed BT 3-3707.</p> <p>Cor. No. 1, hereinbefore described.</p>
	<p style="text-align: center;">ACCIDENT LODE</p> <p>From Cor. No. 1, monumented with a pine post, 4 x 4 ins., 3 ft. long, in a mound of stone, scribed 1-4250.</p> <p>Thence,</p> <p>S. 0° 42' W., along the easterly side line.</p> <p>3.82 Intersect line 1 - 2 of Lost Link lode, mineral survey 3072, from which Cor. No. 1 bears N. 0° 49' W., 0.98 chs. dist., monumented with a pine post, 4 x 4 ins., 4 ft. long, in a mound of stone, with illegible scribe marks visible.</p> <p>19.41 Cor. No. 2, monumented with a pine post, 4 x 4 ins., 3 ft. long, in a mound of stone, with no visible scribe marks.</p> <p>from which an original bearing tree</p> <p>A juniper, 12 ins. diam., bears S. 67° W., 30 lks. dist., scribed BT 2-4250.</p> <p>Thence,</p> <p>S. 88° 45' W., along the southerly end line.</p> <p>0.63 Intersect line 1 - 4 of Pinto lode, same survey, hereinafter described.</p> <p>8.90 Cor. No. 3, monumented with a pine post, 4 x 4 ins., 3½ ft. long, in a mound of stone scribed 3-4250.</p> <p>from which the original bearing trees</p> <p>A juniper, 15 ins. diam., bears S. 0° 20' W., 84.9 lks. dist., scribed BT 3-4250.</p> <p>A juniper, 12 ins. diam., bears S. 60° E., 45.4 lks. dist., scribed BT 3-4250.</p> <p>Thence,</p> <p>N. 0° 09' E., along the westerly side line.</p> <p>7.04 Intersect line 1 - 4 of Pinto lode, same survey, hereinbefore described.</p> <p>14.29 Cor. No. 2 of Orient lode, same survey, hereinbefore described.</p> <p>From Cor. No. 4, hereinbefore described.</p> <p>Thence,</p> <p>N. 89° 24' E., along the northerly end line.</p>

Dependent Resurvey of a Portion of
Mineral Survey No. 4250,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
4.67	Intersect line 3 - 4 of Ouida lode, mineral survey 3707, from which Cor. No. 3 bears S. 43° 49' E., 2.91 chs. dist., hereinbefore described.
9.16	Cor. No. 1, hereinbefore described.
PINTO LODE	
From Cor. No. 1, monumented with a mound of stone.	
from which an original bearing tree	
A juniper, 12 ins. diam., bears N. 47° 30' E., 12.7 lks. dist., scribed BT 4250-1.	
At the corner point	
Set an iron T stake, 24 ins. long, 1 in. diam., 18 ins. in the ground, with steel cap mkd.	
	
Thence,	
S. 9° 46' E., along the easterly end line.	
9.03	Cor. No. 2, monumented with a pine post, 4 x 4 ins., 3 ft. long, in a mound of stone, with no visible scribe marks.
from which the original bearing trees	
A juniper, 12 ins. diam., bears N. 9° W., 24 lks. dist., scribed BT 2-4250.	
A juniper, 11 ins. diam., bears S. 33° E., 87 lks. dist., scribed 2-4250.	
Thence,	
N. 50° 22' W., along the southerly side line.	
22.47	Cor. No. 3, monumented with a pine post, 4 x 4 ins., 3 ft. long, in a mound of stone, with illegible scribe marks visible.
Thence,	
N. 10° 39' W., along the westerly end line.	
9.24	Cor. No. 4, hereinbefore described.
Thence,	
S. 50° 18' E., along the northerly side line.	
11.45	Intersect the line between Cor. No. 3 of Accident lode and Cor. No. 2 of Orient lode, same survey, hereinbefore described.
22.18	Intersect line 2 - 3 of Accident lode, same survey, hereinbefore described.
22.72	Cor. No. 1, hereinbefore described.

Dependent Resurvey of a Portion of
Mineral Survey No. 4498,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS


Dependent Resurvey of a Portion of
Mineral Survey No. 4498,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

(Reestablishment of the Mineral Survey
Executed by James C. Dick in 1900)

SOLUTION LODGE

From Cor. No. 1, identical with Cor. No. 1, Zinc lode,
and Cor. No. 1 Cyanide lode, same survey, reestablished
by three point control.

Set a Copperweld monument, 30 ins. long, 5/8 ins. diam.,
24 ins. in the ground, with brass cap mkd.




From this cor., Cor. No. 2, Zinc lode, same survey, bears
N. 45° 50' E., 9.10 chs. dist., monumented with a wood
post, 4 x 4 ins. 4 ft. long, in mound of stone, scribed
2-4498.

From this same cor., Cor. No. 4, Zinc lode, identical
with Cor. No. 7, Cyanide lode, same survey, bears
S. 37° 22' E., 22.70 chs. dist., monumented with a mound
of stone only.

At the claim corner point

Set a Copperweld monument, 30 ins. long, 5/8 ins. diam.,
20 ins. in the ground, with brass cap mkd.




N. 38° 12' W., along the easterly side line.

10.07 Intersect the line bet. secs. 10 and 15, at a point from
which the 1/4 sec. cor. of secs. 10 and 15, bears
S. 89° 51' E., 6.63 chs. dist., hereinbefore described.

22.70 Cor. No. 4, monumented with a badly rotted wood post
in small mound of stone.

At the claim corner point

Set a Copperweld monument, 30 ins. long, 5/8 ins. diam.,
24 ins. in the ground, with brass cap mkd.




Thence,

S. 46° 49' W., along the northerly end line.

9.10 Cor. No. 3, monumented with a wood post, 4 x 4 ins.,
4 ft. long, in mound of stone, scribed 3-4498.

Dependent Resurvey of a Portion of
Mineral Survey No. 4498,
T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS	
	<p>Thence, S. 38° 13' E., along the westerly side line.</p>
4.67	Intersect the line bet. secs. 10 and 15, at a point from which the ¼ sec. cor. of secs. 10 and 15, bears S. 89° 51' E., 18.19 chs. dist., hereinbefore described.
22.75	<p>Point for Cor. No. 2, identical with Cor. No. 2, Cyanide lode, same survey, at proportionate distance based on the Grant Boundary method.</p> <p>Set a Copperweld monument, 30 ins. long, 5/8 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">  </div> <p>Cor. is located at east edge of gravel road, bearing N. 40° W. to Mercur and S. 40° E. to State Highway No. 73.</p> <p>Thence, N. 46° 34' E., along the southerly end line.</p>
9.10	Cor. No. 1, identical with Cor. No. 1, Zinc lode, and Cor. No. 1 Cyanide lode, same survey, hereinbefore described.
<p>Dependent Resurvey of a Portion of Mineral Survey No. 4935, T. 6 S., R. 3 W., Salt Lake Meridian, Utah</p>	
<p>(Reestablishment of the Mineral Survey Executed by R.E.L. Collier in 1902</p>	
	<p>From Cor. No. 3, Doe Run No. 3, identical with Cor. No. 3, Superior No. 2, same survey hereinbefore described.</p> <p>Thence, S. 35° 15' E., along the easterly side line of Doe Run No. 3 lode.</p>
22.12	<p>Cor. No. 4, Doe Run No. 3, identical with Cor. No. 2, Doe Run No. 4, same survey, monumented with a squared pine, 3 ft. long, with faint scribe mark on one face.</p> <p>Thence, S. 28° 20' E., along the easterly side line of Doe Run No. 4 lode.</p>
11.58	Intersect line 18 - 19 Alpha lode, mineral survey 3169, hereinbefore described.
12.05	Intersect line bet. secs. 16 and 21, at a point from which the ¼ sec. cor. of secs. 16 and 21, bears S. 89° 59' W., 12.83 chs. dist., hereinbefore described.
16.69	Intersect line 18 - 21 of Alpha lode, mineral survey 3169, from which Cor. No. 18 bears S. 54° 20' W., 3.40 chs. dist., hereinbefore described.

127
 Dependent Resurvey of a Portion of
 Mineral Survey No. 4935,
 T. 6 S., R. 3 W., Salt Lake Meridian, Utah

CHAINS

22.84

Cor. No. 3, Doe Run No. 4 lode, identical with Cor. No. 2, Dividend No. 0 lode, same survey, monumented with 2" x 2" x 4" boards nailed together, 4 ft. long, scribed 2-3 4935.

From this cor., Cor. No. 18, Alpha lode, mineral survey No. 3169, bears N. 58° 53' W., 6.64 chs. dist., hereinbefore described.

General Description

This township is located just southwest of Cedar Fort, on the south end of the Oquirrh mountain range. It is mostly mountainous terrain covered with dense oak brush, service berry and sagebrush on the higher elevations, with pinon and juniper timber at the lower elevations. The main divide between Rush and Cedar Valleys bears north and south through the central portion of the township. The western portion is drained in a westerly direction by Mercur and Sunshine Canyons and their tributaries and the east portion in a southeasterly direction by Manning and Pole Canyons and their tributaries.

The remains of the old township of Mercur is located in sections 5, 6, 7, and 8, and the old Manning Mill site is located in section 15, and has one small building and a water storage tank remaining.

There are numerous abandoned mine shafts and diggings located in the township and some mining activity is presently being conducted in the northwest portion of the township.

An improved dirt and gravel road enters the township in section 24, bearing northwesterly along Manning Canyon, crosses the main divide in section 4, and thence bears south westerly along Mercur Canyon, leaving the township in section 7. There are numerous unimproved dirt roads and jeep trails located throughout the township.

A motorcycle course is located on and around the old Manning Mill site in section 15.

The old abandoned Salt Lake and Western Railroad grade is located in sections 25, 36, and 35.

Portions of sections 24, 25, 35, and 36, are presently under dry farm cultivation.

Elevation varies from 5,080 ft. in section 36, to 8,400 ft. above sea level on the main divide in section 3.

The mean of a number of readings of observations of the magnetic declination was found to be 16° 00' East.

Form 9600-11
(August 1979)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Craig P. Sylvester	Supervisory Cadastral Surveyor
Jerry L. Thomas	Supervisory Cadastral Surveyor
Milton R. Workman	Supervisory Cadastral Surveyor
Ferrel D. Reynolds	Supervisory Surveying Technician
Gail E. Reynolds	Surveying Technician
T. Stewart Burt	Surveying Technician
Frank C. Profaizer	Surveying Technician
Daniel T. Mates	Surveying Technician
Gregory K. Landheim	Survey Aid
Steven Rivas	Survey Aid
Ronald Collings	Survey Aid
Dale Swain	Survey Aid
Craig Kennedy	Survey Aid
Donald A. Buhler	Survey Aid
John Alsup	Survey Aid
Tim Bailey	Survey Aid
LeRoy Anderson	Survey Aid

444

CERTIFICATE OF SURVEY

(I) ~~(W&X)~~ Glen B. Hatch, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 6th day of June, 1973, (I) ~~(W&X)~~ have dependently resurveyed a portion of the South Boundary (First Standard Parallel South), Township 5 South, Range 3 West, a portion of the East Boundary, a portion of the subdivisional lines, a portion of the old Ft. Crittenden Military Reservation Boundary and portions of Mineral Surveys of Township 6 South, Range 3 West,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), ~~(W&X)~~ and under (my) ~~(W&X)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

May 20, 1982
(Date)

Glen B Hatch
(Cadastral Surveyor)
Supervisory

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the South Boundary (First Standard Parallel South), Township 5 South, Range 3 West, a portion of the East Boundary, a portion of the subdivisional lines, a portion of the old Ft. Crittenden Military Reservation Boundary and portions of Mineral Surveys of Township 6 South, Range 3 West, Salt Lake Meridian, Utah,

executed by Glen B. Hatch, Supervisory Cadastral Surveyor having been critically examined and found correct, are hereby approved.

June 3, 1982
(Date)

Glen B Hatch
(Chief, Cadastral Survey Examination and Approval Staff)
Chief Cadastral Surveyor for Utah

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

(Date)

(Chief, Cadastral Survey Examination and Approval Staff)
Chief Cadastral Surveyor for Utah

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL
FIELD NOTES

OF THE

DEPENDENT RESURVEY OF THE

FIRST STANDARD PARALLEL SOUTH ALONG THE

SOUTH BOUNDARY OF TOWNSHIPS 5 SOUTH, RANGE 3 EAST,

AND A PORTION OF RANGE 4 EAST,

A PORTION OF THE EAST BOUNDARIES OF

TOWNSHIPS 6 SOUTH, RANGES 2 AND 3 EAST,

AND

A PORTION OF THE SUBDIVISIONAL LINES;

AND

THE SURVEY OF

THE SUBDIVISION OF CERTAIN SECTIONS

OF

TOWNSHIP 6 SOUTH, RANGE 3 EAST

Of the Salt Lake Meridian,

In the State of Utah

EXECUTED BY

Glen B. Hatch Supervisory Cadastral Surveyor

Ray Harpin Supervisory Cadastral Surveyor

Under special instructions dated August 11, 19 69, approved August 15, 1969,

_____, which provided for the surveys included under ~~U.S. Survey~~/Group
Number 513, and assignment instructions dated August 11, 19 69.
and August 1, 1978

Survey commenced August 11, 19 69

Survey completed September 6, 19 79

INDEX DIAGRAM

Township 6 South, Range 3 East
 14 12 11 9 7 3 2

21 34	6 34	34	5 33	30	4 30	28 27	8 25	2 26	24	1 24	20
7 31	32	8 28	9	10	11 23	12 17	21	16	13	18	17
18	17	16	15	14	13	16	13	18	17	16	13
19	20	21	22	23	24	25	26	27	28	29	24
30	29	28	27	26	25	24	23	22	21	20	25
31	32	33	34	35	36	37	38	39	40	41	36

- Subdivision of Section 4 - Page 35
- Subdivision of Section 5 - Page 36
- Subdivision of Section 6 - Page 38
- Subdivision of Section 7 - Page 39
- Subdivision of Section 8 - Page 40
- Subdivision of Section 12 - Page 41

Township 6 South, Range 3 East, Salt Lake Meridian, Utah

CHAINS

The following field notes describe the dependent resurvey of the First Standard Parallel South, along the south boundary of Townships 5 South, Range 3 East, and a portion of Range 4 East, a portion of the east boundaries of Tps. 6 S., Rs. 2 and 3 East, and a portion of the subdivisional lines; and the survey of the subdivision of certain sections of Township 6 South, Range 3 East of the Salt Lake Meridian, Utah.

The First Standard Parallel South was surveyed by Andrew J. Stewart in 1877 and retraced by Scott P. and John R. Stewart in 1900. The west boundary of Township 6 South, Range 4 East was surveyed by Henry and Nicholas Fitzhugh, in 1895 and resurveyed by Scott P and John R. Stewart in 1900. A portion of the west boundary of Township 6 South, Range 3 East was surveyed by C.L. Craig in 1856. The remaining portion was surveyed by J. Fenson Smith in 1871. The west boundary was resurveyed by Andrew J. Stewart Jr. in 1881. Portions of the subdivisional lines were surveyed by C.L. Craig in 1856, J. Fenson Smith in 1871, and Andrew J. Stewart in 1881. Henry and Nicholas Fitzhugh completed the subdivisional lines in 1895. Certain corners were remonumented in 1970 by Ferrel D. Reynolds under the remonumentation cooperative agreement between the U.S. Forest Service and the BLM.

The resurvey was executed in accordance with the specifications set forth in the Manuals of Surveying Instructions, 1947 and 1973, and the Special Instructions for Group 513, Utah, dated August 11, 1969.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original records. The retracement data were thoroughly verified and only the true line field notes are given herein.

The direction of lines were determined by solar observations and were carried forward by sustained angulation.

The geographic position of the southeast cor. of sec. 12, on the east boundary of the township, as scaled from the U.S. Geological Survey quadrangle map "Bridal Veil Falls," prepared in 1948 and revised in 1969, is as follows:

Latitude $40^{\circ} 18.3' N.$ Longitude $111^{\circ} 32.6' W.$

The mean magnetic declination is $15^{\circ} 45' E.$

Dependent Resurvey of the First Standard Parallel South,
S. Bdy., T. 5 S., R. 4 E., Salt Lake Meridian, Utah

((Restoring the 1877 Survey by Andrew J. Stewart, Jr.,
and the Retracement by
Scott P. and John R. Stewart in 1900))

Dependent Resurvey of the First Standard Parallel South,
S. Bdy., T. 5 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS

Beginning at the original standard cor. of secs. 31 and 32, monumented with a sandstone, 17 x 15 x 7 ins., loosely set in a fence extending E and W, mkd. SC on N face, 5 notches on the E face, and 1 notch on the W face, and 6 notches on the N face. This cor. now functions as an Angle Point.

At the angle point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

AP
T 5 S R 4 E

S 32
—
S 6

T 6 S
1969

Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor.

Deposit the mkd. stone in mound of stone.

S. 89° 57' W., on the S. bdy. of sec. 31.

70.63 The closing cor. of secs. 1 and 6, Tps. 6 S., Rs. 3 and 4 E., monumented with a mound of stone, 2½ ft. base, 1 ft. high, the position is accepted as the best available evidence of the position of the original corner.

At the corner point (center of mound)

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 5 S R 4 E

S 31
—
S 1 | S 6
R 3 E | R 4 E

T 6 S
C C
1969

Raise a mound of stone, 2½ ft. base, 1½ ft. high, S of cor.

There are no suitable bearing trees within limits.

This monument is located on a steep E slope.

77.65 Point for the original standard cor. of secs. 31 and 36, Tps. 5 S., Rs. 3 and 4 E., at proportionate distance; there is no remaining evidence of the original corner. This cor. now functions as an Angle Point. No permanent monument is established.

S. 89° 57' W., on the S. bdy. of sec. 31.

Dependent Resurvey of the First Standard Parallel South,
S. Bdy., T. 5 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS

3.82 The standard closing cor. of secs. 31 and 36, Tps. 5 S.,
Rs. 3 and 4 E., monumented with a mound of stone, 2½ ft.
base, 1½ ft. high, this position is accepted as the best
available evidence of the position of the original corner.

At the corner point (center of mound)

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

S C
C C

T 5 S	
R 3 E	R 4 E
S 36	S 31

1969

Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.

There are no suitable bearing trees within limits.

Dependent Resurvey of the First Standard Parallel South,
S. Bdy., T. 5 S., R. 3 E., SLM, Utah

Thence along the S. bdy. of sec. 36, with continuous
measurement.

24.95 Point for the standard E 1/16 sec. cor. of sec. 36.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

E 1/16 S 36

1971

from which

A pine, 11 ins. diam., bears N. 85° 45' E., 66 lks.
dist., mkd. E 1/16 S36 BT.

A pine, 11 ins. diam., bears N. 48° 45' E., 63 lks.
dist., mkd. X BT.

This monument is located on a steep NE slope on the
W. edge of dense stand of spruce.

34.89 Point for the standard W - E 1/64 sec. cor. of sec. 36.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

W-E 1/64 S 36

1971

Raise a mound of stone, 2½ ft. base, 1½ ft. high, to the
north.

Dependent Resurvey of the First Standard Parallel South,
S. Bdy., T. 5 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
35.10	<p>Point for the $\frac{1}{4}$ sec. cor. of sec. 1 only, on the N. bdy. of sec. 1, T. 6 S., R. 3 E., established at mid point between closing cors.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ S 1 T 6 S R 3 E 1969 </p> <p>from which</p> <p style="padding-left: 40px;">A pine, 14 ins. diam., bears S. $0^{\circ} 45'$ W., 43 lks. dist., mkd. $\frac{1}{4}$ S1 BT.</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears N. 80° W., 16 lks. dist., mkd. X BT.</p>
40.22	<p>Point for the original standard $\frac{1}{4}$ sec. cor. of sec. 36, at proportionate distance; there is no remaining evidence of the original corner. This corner now functions as an Angle Point, no permanent monument established.</p>
42.99	<p>Point for the $\frac{1}{1024}$ cor. of sec. 1 only, on the N. bdy. of sec. 1, T. 6 S., R. 3 E.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{1024}$ S 1 1971 </p> <p>from which</p> <p style="padding-left: 40px;">A pine, 13 ins. diam., bears S. $89^{\circ} 45'$ E., 119 lks. dist., mkd. $\frac{1}{1024}$ S1 BT.</p>
44.84	<p>Point for the standard $\frac{1}{4}$ sec. cor. of sec. 36, established at proportionate point between closing corners.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground to bedrock, in a mound of stone, $2\frac{1}{2}$ ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;"> S C T 5 S R 3 E $\frac{1}{4}$ S 36 1971 </p> <p>Raise a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, to the north.</p> <p>There are no suitable bearing trees within limits.</p> <p>This monument is located at a high bank of Bunnells Fork.</p>
54.78	<p>Point for the standard E - W $\frac{1}{64}$ sec. cor. of sec. 36.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the First Standard Parallel South,
S. Bdy., T. 5 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS		
	<p style="text-align: center;"><u>E - W 1/64 S 36</u></p> <p style="text-align: center;">1971</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, to the north.</p> <p>There are no suitable bearing trees within limits.</p>	
56.16	<p>Point for the W 1/16 sec. cor. of sec. 1 only, on the N. bdy. of sec. 1, T. 6 S., R. 3 E.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;"><u>W 1/16 S 1</u></p> <p style="text-align: center;">1969</p> <p>Raise a mound of stone, 3 ft. base, 1½ ft. high, to the south.</p> <p>There are no suitable bearing trees within limits.</p> <p>This monument is located on a steep SE slope.</p>	
64.72	<p>Point for the standard W 1/16 sec. cor. of sec. 36.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base, to top of brass cap, mkd.</p>	
	<p style="text-align: center;"><u>W 1/16 S 36</u></p> <p style="text-align: center;">1971</p> <p>There are no suitable bearing trees within limits.</p>	
66.69	<p>Point for the W - W 1/64 sec. cor. of sec. 1 only, on the N. bdy. of sec. 1, T. 6 S., R. 3 E.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;"><u>W - W 1/64 S 1</u></p> <p style="text-align: center;">1969</p> <p>Raise a mound of stone, 3 ft. base, 1½ ft. high, to the S.</p> <p>There are no suitable bearing trees within limits.</p>	
77.22	<p>The closing cor. of secs. 1 and 2, T. 6 S., R. 3 E., monumented with a mound of stone, 2½ ft. base, 1½ ft. high; this position is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point (center of mound)</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	

Dependent Resurvey of the First Standard Parallel South,
S. Bdy., T. 5 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS

T 5 S	
S 36	

S 2	S 1
T 6 S	R 3 E
C C	

1969

Raise a mound of stone, 3 ft. base, 1½ ft. high, to the southwest.

There are no suitable bearing trees within limits.

This monument is located on a steep SE slope.

- 80.81 The original standard cor. of secs. 35 and 36, monumented with a white limestone, 24 x 8 x 5 ins., firmly set 12 ins. in the ground, mkd. SC on the N face, 1 notch on the E face, and 5 notches on the W face. This cor. now functions as an Angle Point.

At the angle point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

A P	
T 5 S	R 3 E

S 36	

S 2	

1969

from which

A high mountain, bears S. 5° E. (Record, S. 5° W.)

A high round mountain, bears N. 41° E. (Record)

Raise a mound of stone, 3 ft. base, 1½ ft. high, to the N.

Deposit the mkd. stone alongside the iron post.

N. 89° 52' W., along the south boundary of sec. 36.

Asc. steep SE slope through dense oak brush.

- 3.80 The standard closing cor. of secs. 35 and 36, monumented with a quartzite stone, 26 x 12 x 5 ins., mkd. CC on N face, 1 notch on the E face and 5 notches on the W face, firmly set 12 ins. in the ground.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

S C	
T 5 S	R 3 E

C	C
-----	-----
S 35	S 36

1971

Dependent Resurvey of the First Standard Parallel South,
S. Bdy., T. 5 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS

- Raise a mound of stone, 3 ft. base, 1½ ft. high, to the S. of the cor.
- There are no suitable bearing trees within limits.
- Deposit the mkd. stone in the mound of stone.
- This monument is located on a steep S slope.
- Thence along the S. bdy. of sec. 35, with continuous measurement.
- Asc. steep SE slope through dense oak brush.
- 36.46 Point for the ¼ sec. cor. of sec. 2 only, established at proportionate point between closing cors. and on the north boundary of sec. 2, T. 6 S., R. 3 E.
- Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd.
- T 5 S R 3 E

¼ S 2

T 6 S R 3 E

1978
- There are no suitable bearing trees within limits.
- 40.12 Point for the original standard ¼ sec. cor. of sec. 35, at proportionate distance; there is no remaining evidence of the original corner. This cor. now functions as an angle point.
- Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of brass cap, mkd.
- A P
T 5 S R 3 E

S 35

S 2

T 6 S R 3 E

1978
- There are no suitable bearing trees within limits.
- 43.60 Point for the standard ¼ sec. cor. of sec. 35, established at midpoint between closing cors.
- Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of brass cap, mkd.
- S C
T 5 S R 3 E

¼ S 35

1978

Dependent Resurvey of the First Standard Parallel South,
S. Bdy., T. 5 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS

There are no suitable bearing trees within limits.

Cor. is located on a spur ridge sloping east, curving to the NE, in dense undergrowth.

80.24 Point for the original standard cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner. This cor. now functions as an angle point.

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.

A P
T 5 S R 3 E

S 35
—
S 2

1978

There are no suitable bearing trees available.

N. 89° 52' W., on the S. bdy. of sec. 35.

1.25 Point for the closing cor. of secs. 2 and 3, T. 6 S., R. 3 E., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T 5 S R 3 E

S 35
—
S 3 | S 2
C | C

T 6 S R 3 E
1978

from which

An aspen, 10 ins. diam., bears S. 80° E., 4 lks. dist., mkd. T6S R3E S2 CC BT.

A spruce, 12 ins. diam., bears S. 70° W., 20 lks. dist., mkd. T6S R3E S3 CC BT.

3.17 Point for the standard closing cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.

S C
C C
T 5 S R 3 E
—
S 34 | S 35

1978

Dependent Resurvey of the First Standard Parallel South,
S. Bdy., T. 5 S., R 3 E., Salt Lake Meridian, Utah

CHAINS

from which

A pine, 10 ins. diam., bears N. 35° E., 33.5 lks.
dist., mkd. T5S R3E SC CC BT.

An aspen, 5 ins. diam., bears N. 10° W., 20.5 lks.
dist., mkd. T5S R3E CC SC BT.

Thence along the S. bdy. of sec. 34, with continuous
measurement.

- 40.12 Point for the original standard $\frac{1}{4}$ sec. cor. of sec. 34,
at proportionate distance; there is no remaining
evidence of the original corner. This cor. now functions
as an angle point.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins.
in the ground to bedrock, in a mound of stone, 3 ft.
base, to top of brass cap, mkd.

A P
T 5 S R 3 E

S 34
S 3

1978

There are no suitable bearing trees within limits.

- 41.67 Point for the $\frac{1}{4}$ sec. cor. of sec. 3, T. 6 S., R. 3 E.,
established at mid point between the closing cors.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins.
in the ground to solid bedrock, in a mound of stone, 3
ft. base, to top of brass cap, mkd.

T 5 S R 3 E

$\frac{1}{4}$ S 3

T 6 S R 3 E

1978

There are no suitable bearing trees within limits.

Cor. is located on steep W facing slope with dense
undergrowth.

- 43.00 Point for the standard $\frac{1}{4}$ sec. cor. of sec. 34, established
at mid point between the closing cors.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins.
in the ground to bedrock, in a mound of stone, 3 ft. base,
to top of brass cap, mkd.

S C
T 5 S R 3 E

$\frac{1}{4}$ S 34

1978

There are no suitable bearing trees within limits.


Cor. is located on steep W facing slope, with dense
undergrowth.

Dependent Resurvey of the First Standard Parallel South,
S. Bdy., T. 5 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
80.24	<p>Point for the original standard cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner. This cor. now functions as an angle point.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p> <div style="text-align: center;"> <p>A P</p> <p>T 5 S R 3 E</p> <hr style="width: 50px; margin: 0 auto;"/> <p>S 34</p> <p>S 3</p> <p>T 6 S R 3 E</p> <p>1978</p> </div> <p>There are no suitable bearing trees within limits.</p> <p>Cor. is located on steep W slope.</p>
	<p>N. 89° 52' W., on the S. bdy. of sec. 34.</p>
1.86	<p>True point for the closing cor. of secs. 3 and 4, T. 6 S., R. 3 E., at proportionate distance, falls on very steep and inaccessible cliffs and ledges, where it is impractical to establish a permanent monument; there is no remaining evidence of the original corner.</p> <p>Asc. E facing face of cliffs and ledges.</p>
2.19	<p>Point selected for the witness cor. to the closing cor. of secs. 3 and 4, T. 6 S., R. 3 E.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., on solid rock over a cross (X), in a mound of stone, 3½ ft. base, to top of brass cap, mkd.</p> <div style="text-align: center;"> <p>W C</p> <p>T 5 S R 3 E</p> <hr style="width: 50px; margin: 0 auto;"/> <p>C C →</p> <p>S 4 S 3</p> <p>T 6 S</p> <p>1978</p> </div> <p>There are no suitable bearing trees within limits.</p> <p>Cor. is located on narrow ledge 19 lks. wide on the E sloping ledges and cliffs.</p>
2.34	<p>Point selected for the witness cor. to the standard closing cor. of secs. 33 and 34.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., on solid rock over a cross (X) in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p>

Dependent Resurvey of the First Standard Parallel South,
S. Bdy., T. 5 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS



1978

There are no suitable bearing trees within limits.

Cor. is located on a narrow rock ledge, 19 lks. wide, near top of an E sloping cliff.

- 2.55 True point for the standard closing cor. of secs. 33 and 34, at proportionate distance; falls on very steep and inaccessible cliffs and ledges, where it is impracticable to establish a permanent monument; there is no remaining evidence of the original corner.

Thence along the S. bdy. of sec. 33, with continuous measurement.

- 40.12 The original standard $\frac{1}{4}$ sec. cor. of sec. 33, monumented with a white sandstone, 16 x 10 x 12 ins., mkd. SC $\frac{1}{4}$ on N face and firmly set 6 ins. in the ground, in a mound of stone, 3 ft. base, 12 ins. high. This cor. now functions as an angle point.

At the angle point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

A P
T 5 S R 3 E

S 33
S 4

T 6 S
1971

Raise a mound of stone, 3 ft. base, 3 ft. high, N of monument.

Deposit the mkd. stone alongside the iron post.

N. 89° 55' W., beginning new measurement.

- 1.56 Point for the $\frac{1}{4}$ sec. cor. of sec. 4, T. 6 S., R. 3 E., established at mid point between the closing cors.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.

T 5 S R 3 E

$\frac{1}{4}$ S 4

T 6 S R 3 E
1978

There are no suitable bearing trees within limits.

458

Dependent Resurvey of the First Standard Parallel South,
S. Bdy., T. 5 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
39.69	<p>Cor. is located in thick oak brush, 5 lks. E of a power line running NE and SW.</p> <p>The original standard cor. of secs. 32 and 33, monumented with a sandstone, 18 x 12 x 10 ins., mkd. SC and 6 notches on the W face, firmly set in a mound of stone, 3 ft. base, 1½ ft. high. This cor. now functions as an angle point.</p> <p>At the angle point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>A P</p> <p>T 5 S R 3 W</p> <hr style="width: 50px; margin: auto;"/> <p>S 33</p> <p>S 4</p> <p>T 6 S</p> <p>1971</p> </div> <p>Raise a mound of stone, 3 ft. base, 3 ft. high, to the N. of cor.</p> <p>There are no suitable bearing trees within limits.</p> <p>Deposit the mkd. stone alongside the iron post.</p>
1.68	<p>S. 89° 15' W., on the S. bdy. of sec. 32.</p> <p>Over rolling land through scattered oak and sagebrush.</p> <p>Point for the closing cor. of secs. 4 and 5, T. 6 S., R. 3 E., at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 5 S R 3 E</p> <hr style="width: 50px; margin: auto;"/> <p>S 5 S 4</p> <p style="text-align: center;"> </p> <p>C C</p> <p>T 6 S</p> <p>1971</p> </div> <p>There are no suitable bearing trees within limits.</p> <p>Raise a mound of stone, 3 ft. base, 2½ ft. high, to S.</p>
39.87	<p>The original standard ¼ sec. cor. of sec. 32, monumented with a white limestone, 24 x 12 x 4 ins., mkd. ¼ on N face, firmly set 10 ins. in the ground, in a mound of stone, 2 ft. base, 1 ft. high. This cor. now functions as an angle point.</p> <p>At the angle point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of the First Standard Parallel South,
S. Bdy., T. 5 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS

A P
T 5 S R 3 E

S 32
S 5

T 6 S
1971

Raise a mound of stone, 3 ft. base, 2 ft. high, to the N.

There are no suitable bearing trees within limits.

Deposit the mkd. stone alongside the iron post.

S. 89° 39' W., beginning new measurement.

Asc. NE slope through dense oak.

1.43 Point for the ¼ sec. cor. of sec. 5, T. 6 S., R. 3 E.,
established at mid point between the closing corners.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

¼ S 5

T 6 S R 3 E

1971

Raise a mound of stone, 3 ft. base, 2½ ft. high, to the S.

There are no suitable bearing trees within limits.

39.80 The original standard cor. of secs. 31 and 32, monumented
with a blue limestone, 14 x 12 x 9 ins., mkd. 1 notch
on the W face, no other marks visible, loosely set in a
mound of stone, 2½ ft. base. This cor. now functions as
an Angle Point.

At the angle point

Set an iron post, 28 ins. long, 2½ ins. diam., 23 ins.
in the ground, with brass cap mkd.

A P
T 5 S R 3 E

S 32
S 5

T 6 S
1971

Raise a mound of stone, 2½ ft. base, 2 ft. high, to the N
of cor.

There are no suitable bearing trees within limits.

Deposit the mkd. stone in mound of stone.

Dependent Resurvey of the First Standard Parallel South,
S. Bdy., T. 5 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
1.15	<p>N. 89° 58' W., on the S. bdy. of sec. 32.</p> <p>Asc. an E to SE slope through dense to scattered oak.</p> <p>The standard closing cor. of secs. 31 and 32, monumented with a sandstone, 18 x 7 x 7 ins., mkd. CC on the N face, 5 grooves on the E face and 1 groove on the W face, loosely set in a mound of stone, 3 ft. base.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>S C C C T 5 S R 3 E</p> <hr style="width: 100px; margin: auto;"/> <p>S 31 S 32</p> <p>1971</p> </div> <p>Raise a mound of stone, 2½ ft. base, 2 ft. high, to the N.</p> <p>There are no suitable bearing trees within limits.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Thence along the S. bdy. of sec. 31, with continuous measurement.</p>
1.24	<p>Point for the closing cor. of secs. 5 and 6, T. 6 S., R. 3 E., at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 5 S R 3 E</p> <hr style="width: 100px; margin: auto;"/> <p>S 31 S 6 S 5 C C</p> <p>T 6 S R 3 E 1971</p> </div> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, to the S. of cor.</p> <p>There are no suitable bearing trees within limits.</p>
20.96	<p>Point for the E 1/16 sec. cor. of sec. 6 only, T. 6 S., R. 3 E.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <hr style="width: 100px; margin: auto;"/> <p>E 1/16 S 6</p> <p>T 6 S R 3 E 1971</p> </div>

Dependent Resurvey of the First Standard Parallel South,
S. Bdy., T. 5 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS

Raise a mound of stone, 3 ft. base, 3 ft. high, to the S. of cor.

There are no suitable bearing trees within limits.

40.13 The original standard $\frac{1}{4}$ sec. cor. of sec. 31, monumented with a quartzite stone, 16 x 11 x 9 ins., mkd. $\frac{1}{4}$ on N face, firmly set 2 ins. in the ground and in a mound of stone, 2 $\frac{1}{2}$ ft. base, 1 ft. high. This cor. now functions as an Angle Point.

At the angle point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

A P
T 5 S R 3 E

S 31
—
S 6

T 6 S
1971

Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, to the N. of cor.

There are no suitable bearing trees within limits.

Deposit the mkd. stone alongside the iron post.

S. 88° 39' W., beginning new measurement.

Desc. W slope through dense oak.

0.50 Point for the standard $\frac{1}{4}$ sec. cor. of sec. 31, established at proportionate distance.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 5 S R 3 E

$\frac{1}{4}$ S 31
—

1971

Raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 2 ft. high, to the N. of cor.

There are no suitable bearing trees within limits.

0.55 Point for the $\frac{1}{4}$ sec. cor. of sec. 6, T. 6 S., R. 3 E., at proportionate distance.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ S 6
—

T 6 S R 3 E
1971

Dependent Resurvey of the First Standard Parallel South,
S. Bdy., T. 5 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS

Raise a mound of stone, 2½ ft. base, 2 ft. high, to the S. of cor.

There are no suitable bearing trees within limits.

39.99 The cor. of secs. 1, 6, 31, and 36, Tps. 5 and 6 S., Rs. 2 and 3 E., monumented with an iron post, 3 ins. diam., firmly set and projecting 14 ins. above ground, and in a mound of stone, 3 ft. base, to top of brass cap mkd. as described in the official record of the 1914 resurvey.


Dependent Resurvey of a Portion of the East Boundary,
T. 6 S., R. 3 E., Salt Lake Meridian, Utah

(Restoring the 1895 Survey by Henry and Nicholas Fitzhugh and the 1900 Retracement Survey by Scott P. and John R. Stewart)

From the ¼ sec. cor. of sec. 13, on the E. bdy. of the Tp., monumented with a quartzite stone, 20 x 10 x 8 ins., mkd. ¼ on the W face, firmly set 10 ins. in the ground.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.



1974

from which

A spruce, 13 ins. diam., bears S. 7° 15' E., 33 lks. dist., mkd. X BT.

A spruce, 10 ins. diam., bears S. 20° W., 44 lks. dist., mkd. ¼ S13 BT.

Deposit the mkd. stone alongside the iron post.

N. 0° 35' W., along the E. bdy. of sec. 13.

Desc. steep NE slope through dense aspen and scattering spruce.

32.54 The closing cor. of secs. 7 and 18, T. 6 S., R. 4 E., monumented with a granite stone, 18 x 10 x 6 ins., mkd. 4 grooves on the S face, 2 grooves on the N face, and CC on the E face, firmly set 10 ins. in the ground, in a scattering mound of stone. There is no remaining evidence of the original bearing trees.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

Dependent Resurvey of a Portion of the East Boundary,
T. 6 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS

T 6 S		
S 13	S 7	C
	S 18	C
	R 4 E	

1974

Raise a mound of stone, 2½ ft. base, 1½ ft. high, to the E. of cor.

Deposit the mkd. stone alongside the iron post.

There are no suitable bearing trees within limits.

40.41

The cor. of secs. 12 and 13, monumented with a quartzite stone, 14 x 10 x 5 ins., mkd. 2 notches on the N and 4 notches on the S edges, firmly set 8 ins. in the ground with a mound of stone, 3 ft. base, 1 ft. high, to the W. There is no remaining evidence of the original bearing trees.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 6 S	T 6 S
S 12	R 4 E
S 13	S 7
R 3 E	

1974

from which

A spruce, 8 ins. diam., bears S. 2° 30' W., 67 lks. dist., mkd. X BT.

A spruce, 6 ins. diam., bears S. 43° 13' W., 76 lks. dist., mkd. T6S R3E S13 BT.

Raise a mound of stone, 2½ ft. base, 1½ ft. high, to the W. of cor.

Deposit the mkd. stone alongside the iron post.

N. 0° 59' W., along the E. bdy. of sec. 12.

Desc. NW slope through dense to scattering oak and maple.

11.74

Point for the S 1/16 sec. cor. of sec. 7, T. 6 S., R. 4 E.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

S 1/16
S 7

1974

Dig pits, 18 x 18 x 12 ins., N and S of the iron post, 3 ft. dist.

Dependent Resurvey of a Portion of the East Boundary,
T. 6 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS		
19.77	<p>No suitable trees within limits and no stones. This monument is located on a steep SW slope. Point for the S 1/16 sec. cor. of sec. 12 only. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S 12 </p> <p style="text-align: center;">1974</p> <p>Dig pits, 18 x 18 x 12 ins., N and S of the iron post, 3 ft. dist. No suitable bearing trees within limits. No stones are available for a mound.</p>	
31.35	<p>Point for the ¼ sec. cor. of sec. 7, T. 6 S., R. 4 E. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 3 E R 4 E ¼ S 7</p> <p style="text-align: center;">1974</p> <p>from which</p> <p style="padding-left: 40px;">A spruce, 15 ins. diam., bears N. 37° 15' E., 48 lks. dist., mkd. ¼ S7 BT.</p> <p style="padding-left: 40px;">A spruce, 12 ins. diam., bears N. 44° 45' W., 14 lks. dist., mkd. X BT.</p>	
39.54	<p>The ¼ sec. cor. of sec. 12 only, monumented with a sandstone, 30 x 18 x 12 ins., mkd. ¼ on W face, firmly set 12 ins. in the ground, with a mound of stone, 2 ft. base, 1½ ft. high, W. There is no remaining evidence of the original bearing trees.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 2½ ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 6 S R 3 E ¼ S 12 </p> <p style="text-align: center;">1970</p> <p>Restore the mound of stone, 3 ft. base, 2 ft. high, to the W. of cor.</p>	

Dependent Resurvey of a Portion of the East Boundary,
T. 6 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS

Deposit the mkd. stone alongside the iron post.

N. $1^{\circ} 28'$ W., beginning new measurement.

Desc. NE slope through dense oak, maple and aspen.

9.89 Point for the S - N $1/64$ sec. cor. of sec. 12 only.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 23 ins. in the ground, with brass cap mkd.

S - N |
1/64 |
S 12 |

1974

Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, on the W. of cor.

There are no suitable bearing trees within limits.

19.78 Point for the N $1/16$ sec. cor. of sec. 12 only.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

N $1/16$ |
S 12 |

1970

31.03 Point for the closing cor. of secs. 6 and 7, T. 6 S., R. 4 E., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 6 S
R 3 E R 4 E
| S 6 C
S 12 | S 7 C

1970

Asc. steep SE slope through dense oak.

39.56 The cor. of secs. 1 and 12, monumented with a sandstone, 18 x 12 x 10 ins., faintly mkd. 1 notch on the N face, loosely set 4 ins. in the ground.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 6 S
R 3 E R 4 E
| S 1
S 12 | S 6

1970

466

Dependent Resurvey of a Portion of the East Boundary,
T. 6 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
	<p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, to W of cor.</p> <p>Deposit the mkd. stone alongside the iron post.</p>
11.23	<p>N. 0° 15' E., along the E. bdy. of sec. 1.</p> <p>Along a steep E slope through dense maple and aspen.</p> <p>Point for the S 1/16 sec. cor. of sec. 6 only, T. 6 S., R. 4 E.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> S 1/16 S 6 1971</p>
30.99	<p>Point for the ¼ sec. cor. of sec. 6, T. 6 S., R. 4 E.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T 6 S R 4 E ¼ S 6 1971</p>
39.61	<p>Cor. falls on steep NE slope of spur in dense undergrowth.</p> <p>Point for the ¼ sec. cor. of sec. 1, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 3 E ¼ S 1 1971</p>
77.12	<p>from which</p> <p>An aspen, 3 ins. diam., bears S. 30° W., 25 lks. dist., mkd. X BT.</p> <p>An Aspen, 8 ins. diam., bears N. 85° 15' W., 39 lks. dist., mkd. ¼ S1 BT.</p> <p>This monument is located on a steep NW slope.</p> <p>Desc. steep NNW slope through dense oak and aspen.</p> <p>The closing cor. of secs. 1 and 6, on the First Standard Parallel North, heretofore described.</p> <p>From this closing cor., the point for the angle point bet. secs. 1 and 31, bears S. 89° 57' W., 7.02 chs. dist., heretofore described.</p>

Dependent Resurvey of a Portion of the West Boundary,
T. 6 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS

Dependent Resurvey of a Portion of the West Boundary,
T. 6 S., R. 3 E., Salt Lake Meridian, Utah

(Restoring the 1871 Survey by J. Fenson Smith and
the 1881 Resurvey by Andrew J. Stewart, Jr.)

From the cor. of secs. 1, 6, 7, and 12, on the west
boundary of the Tp., monumented with a concrete post,
6 x 6 ins., firmly set flush with the ground as set by the
Utah County Surveyor, and substantiated by abandoned
fences extending S and W, with 3 in. brass tablet mkd.

UTAH COUNTY	
T 6 S	
R 2 E	R 3 E
S 1	S 6
S 12	S 7

LAND SURVEY
1961

This position is accepted as the best available evidence
of the original cor. position.

N. 0° 25' W., bet. secs. 1 and 6.

Asc. S slope through scattering oak.

40.00 The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, monumented with an
iron post, 2 $\frac{1}{2}$ ins. diam., firmly set and projecting 3
ins. above ground, with brass cap mkd. as described in
the official record of the 1970 remonumentation.

Raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 2 ft. high, to the
W. of cor.

N. 0° 35' W., beginning new measurement.

Asc. rolling S slope through scattering oak.

39.91 The cor. of secs. 1, 6, 31, and 36, Tps. 5 and 6 S.,
Rs. 2 and 3 E., heretofore described.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 6 S., R. 3 E., Salt Lake Meridian, Utah

(Restoring the 1895 Survey by
Henry and Nicholas Fitzhugh)

Beginning at the cor. of secs. 12 and 13 only, on the
east bdy. of the Tp., heretofore described.

N. 88° 26' W., bet. secs. 12 and 13.

Asc. steep NE slope through dense aspen, oak and
scattering spruce.

20.58 Point for the E 1/16 sec. cor. of secs. 12 and 13.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 6 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS		
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 $\frac{S\ 12}{S\ 13}$</p> <p style="text-align: center;">1974</p>	
30.87	<p>Set a maple post, 4½ ft. long, 4 ins. diam., N 2 ft. dist. There are no suitable bearing trees within limits.</p> <p>Point for the W - E 1/64 sec. cor. of secs. 12 and 13.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 12 W - E 1/64 S 13</p> <p style="text-align: center;">1974</p>	
	<p>from which</p> <p style="padding-left: 40px;">An aspen, 5 ins. diam., bears N. 74° 45' E., 14 lks. dist., mkd. W - E 1/64 S12 BT.</p> <p style="padding-left: 40px;">An aspen, 6 ins. diam., bears S. 38° E., 12 lks. dist., mkd. W - E 1/64 S13 BT.</p>	
41.16	<p>The ¼ sec. cor. of secs. 12 and 13, monumented with a sandstone, 14 x 10 x 6 ins., firmly set 6 ins. in the ground, with a scattering mound of stone, 3 ft. base, with 4 faintly mkd. on the N face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 6 S R 3 E</p> <p style="text-align: center;">¼ $\frac{S\ 12}{S\ 13}$</p> <p style="text-align: center;">1974</p>	
	<p>Deposit the mkd. stone alongside the iron post.</p> <p>There are no suitable bearing trees within limits.</p> <p style="text-align: center;">_____</p> <p>S. 87° 59' W., beginning new measurement.</p> <p>Asc. steep NW slope through dense aspen, maple, and oak brush.</p>	
40.72	<p>The cor. of secs. 11, 12, 13, and 14, monumented with a sandstone, 14 x 10 x 6 ins., firmly set 6 ins. in the ground, mkd. 4 notches on the S, and 1 notch on the E edges with a scattering mound of stone, 3 ft. base, W of cor.</p> <p>At the corner point</p>	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 6 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top of brass cap, mkd.

T 6 S R 3 E

S 11	S 12
S 14	S 13

1974

There are no suitable bearing trees within limits.

Deposit the mkd. stone alongside the iron post.

N. 0° 27' W., bet. secs. 11 and 12.

Along an E slope through oak, maple, and scattering aspen.

40.00

The ¼ sec. cor. of secs. 11 and 12, monumented with a quartzite stone, 10 x 10 x 8 ins., firmly set 6 ins. in the ground, faintly mkd. ¼ on W face, with a scattering mound of stone, 2 ft. base, W of cor.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 6 S R 3 E

S 11	¼ ¼	S 12
------	-------------	------

1974

Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor.

There are no suitable bearing trees within limits.

Deposit the mkd. stone alongside the iron post.

N. 1° 09' W., beginning new measurement.

39.22

Point for the cor. of secs. 1, 2, 11, and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T 6 S R 3 E

S 2	S 1
S 11	S 12

1979

from which

A pine, 6 ins. diam., bears S. 21° 31' E., 14 lks. dist., mkd. T6S R3E S12 BT.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 6 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
	<p>A pine, 11 ins. diam., bears S. 56° W., 5.7 lks. dist., mkd. T6S R3E S11 BT.</p> <p>Cor. is located on NW facing slope, in dense undergrowth.</p>
20.07	<p>From the cor. of secs. 1 and 12 only, on the E. bdy. of the Tp., heretofore described.</p> <p>S. 88° 37' W., bet. secs. 1 and 12.</p> <p>Asc. steep NE slope through dense oak and maple brush.</p> <p>Point for the E 1/16 sec. cor. of secs. 1 and 12.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> $E \frac{1}{16} \frac{S \ 1}{S \ 12}$ <p>1974</p> <p>Raise a mound of stone, 3 ft. base, 1½ ft. high, to the N.</p> <p>There are no suitable bearing trees within limits.</p>
40.14	<p>The ¼ sec. cor. of secs. 1 and 12, monumented with a sandstone, 15 x 10 x 6 ins., firmly set 8 ins. in the ground, faintly mkd. with 4 on the N face with a scattering mound of stone N of cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> $T \ 6 \ S \ R \ 3 \ E$ $\frac{1}{4} \frac{S \ 1}{S \ 12}$ <p>1974</p> <p>Restore the mound of stone, 2½ ft. base, 1½ ft. high, N. of the cor.</p> <p>There are no suitable bearing trees within limits.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>N. 88° 51' W., beginning new measurement.</p>
40.92	<p>The cor. of secs. 1, 2, 11, and 12.</p>
39.24	<p>N. 2° 05' W., bet. secs. 1 and 2.</p> <p>Point for the ¼ sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, encircled by a collar of stone, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 6 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS

T 6 S R 3 E

$$\begin{array}{c} \frac{1}{2} \\ | \\ \text{S } 2 \quad | \quad \text{S } 1 \\ | \end{array}$$

1978

There are no suitable bearing trees within limits.

58.86 Point for the N 1/16 sec. cor. of sec. 1 and 12.

Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a mound of stone, 3 ft. base, to top of cap, mkd.

T 6 S R 3 E
N 1/16

$$\begin{array}{c} | \\ \text{S } 2 \quad | \quad \text{S } 1 \\ | \end{array}$$

1978

from which

A pine, 6 ins. diam., bears N. 38° 30' W.,
79.4 lks. dist., mkd. N 1/16 S2 BT.

A pine, 10 ins. diam., bears N. 2° W., 32.8 lks.
dist., mkd. N 1/16 X BT.

77.30 The closing cor. of secs. 1 and 2, heretofore described.

From this closing cor., the angle point bet. secs. 2 and 36, bears S. 89° 57' W., 3.59 chs. dist., heretofore described.

From the point for the SE cor. of sec. 3, established at record easting from the cor. of secs. 4, 5, 8, and 9, hereinafter described; and at record southing from the closing cor. of secs. 2 and 3, heretofore described.

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in 3 ft. diam collar of stone, with brass cap mkd.

T 6 S R 3 E

$$\begin{array}{c} | \\ \text{S } 3 \quad | \\ | \end{array}$$

S 10
1978

There are no suitable bearing trees within limits.

N. 1° 31' W., bet. secs. 3 and 10.

0.75 Point for the closing cor. of secs. 2 and 10, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 6 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS		
40.01	<p style="text-align: center;">T 6 S R 3 E</p> $S 3 \left \begin{array}{l} S 2 \\ S 10 \end{array} \right. C$ <p style="text-align: center;">1978</p> <p>There are no suitable bearing trees within limits.</p> <p>Raise a mound of stone, 3 ft. base, 3 ft. high, E of cor.</p> <p>Thence bet. secs. 2 and 3, with continuous measurement.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	
79.17	<p style="text-align: center;">T 6 S R 3 E</p> $S 3 \left \begin{array}{c} \frac{1}{4} \\ S 2 \end{array} \right.$ <p style="text-align: center;">1978</p> <p>Raise a mound of stone, 3 ft. base, 3 ft. high, E of cor.</p> <p>There are no suitable bearing trees within limits.</p> <p>The closing cor. of secs. 2 and 3, heretofore described.</p> <p>From this closing cor., the angle point bet. secs. 2 and 35, bears S. $89^{\circ} 52'$ E., 1.25 chs. dist., heretofore described.</p>	
40.81	<p>From the cor. of secs. 1, 2, 11, and 12.</p> <p>S. $89^{\circ} 30'$ W., bet. secs. 2 and 11.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, encircled by a 4 ft. diam. collar of stone, with aluminum cap mkd.</p>	
82.10	<p style="text-align: center;">T 6 S R 3 E</p> $\frac{1}{4} \frac{S 2}{S 11}$ <p style="text-align: center;">1979</p> <p>There are no suitable bearing trees within limits.</p> <p>Cor. falls in a hollow that is 50 lks. wide and 20 lks. deep, which drains S. 75° E.</p> <p>Point for the closing cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original corner.</p>	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 6 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS

Set an aluminum post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, encircled by a 3 ft. diam. collar of stone, with aluminum cap mkd.

T 6 S R 3 E

S 2	
S 10	S 11
C C	

1978

There are no suitable bearing trees within limits.

Thence, bet. secs. 2 and 10, with continuous measurement.

85.77 The closing cor. of secs. 2 and 10, heretofore described.

From the SE cor. of sec. 3.

S. 89° 50' W., bet. secs. 3 and 10.

40.00 Point for the ¼ sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.

T 6 S R 3 E

¼	S 3	S 10

1978

There are no suitable bearing trees within limits.

Cor. is located W. 30 lks. from a spur ridge bearing N. 24° W.

80.00 Point for the cor. of secs. 3, 4, 9, and 10, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, encircled in a collar of stone, with aluminum cap mkd.

T 6 S R 3 E

S 4	S 3	S 10
S 9		

1978

There are no suitable bearing trees within limits.

Cor. is located 3 chs. N of a W slope spur ridge, on a steep N slope.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 6 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
39.38	<p>From this point, the cor. of secs. 16 and 21 only, bears S. 1° 12' E., 158.01 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. as described in the official record of the 1977 resurvey of portions of T. 6 S., R. 3 E.</p> <p>This control line was fully retraced and careful search was made for evidence of intervening corners, none of which was recovered.</p> <p>N. 2° 06' W., bet. secs. 3 and 4.</p> <p>Point for the ¼ sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with the aluminum cap mkd.</p> <p style="text-align: center;">T 6 S R 3 E</p> <p style="text-align: center;"> $\frac{1}{4}$ S 4 S 3 1978 </p> <p>from which</p> <p>A pine, 5 ins. diam., bears N. 18° W., 33 lks. dist., mkd. ¼ S4 BT.</p> <p>Raise a mound of stone, 3 ft. base, 4½ ft. high, W of cor.</p>
79.59	<p>True point for the closing cor. of secs. 3 and 4, heretofore described.</p> <p>From the true point for the closing cor. of secs. 3 and 4, the angle point bet. secs. 3 and 34, bears S. 89° 52' E., 1.86 chs. dist., heretofore described.</p> <p style="text-align: center;">(Restoring the 1881 Survey by Andrew J. Stewart Jr.)</p> <p>From the cor. of secs. 8, 9, 16, and 17, monumented with an iron post, 2½ ins. diam., projecting 6 ins. above ground, with brass cap mkd. as described in the official record of the 1977 resurvey.</p> <p>from which</p> <p>A maple, 6 ins. diam., bears N. 39° E., 107 lks. dist., mkd. T6S R3E S9 BT.</p> <p>A maple, 5 ins. diam., bears S. 10° 45' E., 19 lks. dist., mkd. X BT.</p> <p>A maple, 5 ins. diam., bears S. 73° W., 31 lks. dist., mkd. X BT.</p> <p>A maple, 7 ins. diam., bears N. 28° 30' W., 43 lks. dist., mkd. T6S R3E S8 BT.</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 6 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS

- N. $0^{\circ} 05'$ W., bet. secs. 8 and 9.
- Desc. steep rolling N slope through dense to scattering oak and maple.
- 39.84 Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
- T 6 S R 3 E
- $\frac{1}{4}$
 |
 S 8 | S 9
 |
 1971
- from which
- An oak, 6 ins. diam., bears S. $62^{\circ} 30'$ E., 30 lks. dist., mkd. $\frac{1}{4}$ S9 BT.
- A maple, 6 ins. diam., bears N. 82° W., 31 lks. dist., mkd. $\frac{1}{4}$ S8 BT.
- Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W of cor.
- 59.76 Point for the N $\frac{1}{16}$ sec. cor. of secs. 8 and 9.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
- T 6 S R 3 E
N $\frac{1}{16}$
- S 8 | S 9
- 1971
- from which
- An oak, 5 ins. diam., bears S. 52° W., 9 lks. dist., mkd. X BT.
- An extant wooden post, 4 x 4 ins., firmly set and projecting 2 ft. from the ground, bears N. $8^{\circ} 40'$ W., 15 lks. dist.
- 79.68 The cor. of secs. 4, 5, 8, and 9, monumented with a limestone, 18 x 15 x 6 ins., mkd. 5 notches on the S face, firmly set 10 ins. in the ground.
- At the corner point
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.
- T 6 S R 3 E
- S 5 | S 4
 S 8 | S 9
 1971

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 6 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS		
	<p>Deposit the mkd. stone alongside the iron post. Raise a mound of stone, 4 ft. base, 1½ ft. high, W of cor. There are no suitable bearing trees within limits.</p>	
40.00	<p>From the cor. of secs. 3, 4, 9, and 10. N. 89° 24' W., bet. secs. 4 and 9. Point for the ¼ sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap mkd.</p> <p style="text-align: center;">T 6 S R 3 E</p> <p style="text-align: center;">¼ $\frac{S\ 4}{S\ 9}$</p> <p style="text-align: center;">1978</p> <p>There are no suitable bearing trees within limits.</p> <p>Cor. is located on a steep W slope, 20 lks. N of the N edge of a rock slide, and 250 lks. W of the base of a near vertical ledge 200+ ft. high, bearing N - S.</p>	
60.00	<p>Point for the W 1/16 sec. cor. of secs. 4 and 9. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, encircled in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 3 E</p> <p style="text-align: center;">W 1/16 $\frac{S\ 4}{S\ 9}$</p> <p style="text-align: center;">1978</p> <p>There are no suitable bearing trees within limits.</p>	
80.00	<p>The cor. of secs. 4, 5, 8, and 9.</p>	
19.90	<p>N. 0° 31' W., bet. secs. 4 and 5. Desc. NW slope through dense to scattering oak and maple. Point for the S 1/16 sec. cor. of secs. 4 and 5. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 3 E</p> <p style="text-align: center;">S 1/16</p> <p style="text-align: center;">S 5 S 4</p> <p style="text-align: center;">1971</p> <p>Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 6 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS


There are no suitable bearing trees within limits.

39.80 The 1/4 sec. cor. of secs. 4 and 5, monumented with a granite stone, 24 x 12 x 10 ins., mkd. 1/4 on the W face, firmly set 10 ins. in the ground, in a mound of stone, 3 ft. base, and in an old fence extending N and S.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 6 S R 3 E



1971

Raise a mound of stone, 3 ft. base, 3 ft. high, W of cor.

There are no suitable bearing trees within limits.

Deposit the mkd. stone alongside the iron post.

N. 3° 12' W., beginning new measurement.

39.13 The closing cor. of secs. 4 and 5, heretofore described.

From this closing cor., the angle point bet. secs. 4 and 33, bears N. 89° 15' E., 1.68 chs. dist., heretofore described.


From the cor. of secs. 7, 8, 17, and 18, monumented with an iron post, 1 3/4 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. as described in the official record of the 1977 resurvey.

S. 89° 14' W., bet. secs. 7 and 18.

Over rolling S slope through scattering oak and sagebrush.

19.82 Point for the E 1/16 sec. cor. of secs. 8 and 17.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.



1974

from which

A granite stone, 12 x 10 x 8 ins., mkd. 1/16 on N face, loosely set in cor. of fence extending S and W, bears WEST, 13 lks. dist.

There are no suitable bearing trees within limits.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 6 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
39.64	<p>The ¼ sec. cor. of secs. 7 and 18, monumented with an iron post, 2 ins. diam., firmly set and projecting 4 ins. above ground, in a mound of stone, 3 ft. base, with a flintstone, 18 x 11 x 8 ins., mkd. ¼ in the mound of stone, and in a power line extending SE and NW. A brass cap, 3 ins. diam., attached to the iron pipe, reads:</p> <p style="text-align: center;">UTAH COUNTY T 6 S R 3 E</p> <p style="text-align: center;"> $\begin{array}{r} 7 \\ \hline 18 \\ 1955 \end{array}$ LAND SURVEY </p> <p style="text-align: center;">(Restoring the 1856 Survey by C.L. Craig and the 1881 Resurvey by Andrew J. Stewart Jr.)</p>
40.45	<p>S. 89° 43' W., beginning new measurement.</p> <p>The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., monumented with a brass tablet, 3 ins. diam., set in a concrete post, 7 x 7 ins., firmly set and projecting 3 ins. above ground, mkd.</p> <p style="text-align: center;">UTAH COUNTY T 6 S</p> <p style="text-align: center;"> R2E $\frac{12}{13}$ $\frac{7}{18}$ R3E 1955 LAND SURVEY </p> <p>This cor. is accepted as the best available evidence of the position of the original cor.</p>
39.22	<p style="text-align: center;">(Restoring the 1881 Survey by Andrew J. Stewart Jr.)</p> <p>From the cor. of secs. 7, 8, 17, and 18.</p> <p>N. 0° 43' W., bet. secs. 7 and 8.</p> <p>Asc. SW slope through scattering oak.</p> <p>The ¼ sec. cor. of secs. 7 and 8, monumented with a limestone, 12 x 10 x 8 ins., mkd. ¼ on the W face, firmly set 6 ins. in the ground, with a mound of stone, 3 ft. base, 1 ft. high, W.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 3 E</p> <p style="text-align: center;"> $\begin{array}{c} \frac{1}{4} \\ \\ S 7 \quad \quad S 8 \\ \end{array}$ 1974 </p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 6 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
42.73	<p>Restore the mound of stone, 2½ ft. base, 1½ ft. high, W of cor.</p> <p>There are no suitable bearing trees within limits.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p style="text-align: center;">_____</p> <p>N. 1° 26' W., beginning new measurement.</p> <p>Desc. rolling NW slopes through dense to scattering oak.</p> <p>The cor. of secs. 5, 6, 7, and 8, monumented with an iron post, 2½ ins. diam., firmly set, and projecting 6 ins. above ground, with brass cap mkd. as described in the official record of the 1970 remonumentation.</p>
19.91	<p>From the cor. of secs. 4, 5, 8, and 9.</p> <p>N. 88° 05' W., bet. secs. 5 and 8.</p> <p>Desc. NW slope through dense oak and maple.</p> <p>Point for the E 1/16 sec. cor. of secs. 5 and 8.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 3 E</p> <p style="text-align: center;">E 1/16 $\frac{S 5}{S 8}$</p> <p style="text-align: center;">1971</p> <p>from which</p> <p style="padding-left: 40px;">An elm, 11 ins. diam., bears S. 37° E. 44 lks. dist., mkd. E 1/16 S8 BT.</p> <p style="padding-left: 40px;">A maple, 7 ins. diam., bears N. 73° 15' W., 9 lks. dist., mkd. E 1/16 S5 BT.</p>
39.82	<p>Raise a mound of stone, 4 ft. base, 1½ ft. high, S of cor.</p> <p>The ¼ sec. cor. of secs. 5 and 8, monumented with a granite stone, 20 x 9 x 5 ins., mkd. ¼ on the N face, firmly set 10 ins. in the ground, and in a mound of stone, 4 ft. base, 1 ft. high.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 6 S R 3 E</p> <p style="text-align: center;">¼ $\frac{S 5}{S 8}$</p> <p style="text-align: center;">1971</p> <p>There are no suitable bearing trees within limits.</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 6 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS		
39.50	<p>Deposit the mkd. stone alongside the iron post.</p> <p style="text-align: center;">_____</p> <p>S. 88° 12' W., beginning new measurement.</p> <p>Desc. rolling N. slope through dense to scattering oak and maple.</p> <p>The cor. of secs. 5, 6, 7, and 8.</p>	
39.88	<p>S. 89° 26' W., bet. secs. 6 and 7.</p> <p>Desc. rolling W slope through dense to scattering oak.</p> <p>The ¼ sec. cor. of secs. 6 and 7, monumented with a brass tablet, 3 ins. diam., in a concrete post, 6 x 6 ins., firmly set flush with the ground, mkd.</p> <p style="text-align: center;">UTAH COUNTY</p> <p style="text-align: center;">¼ $\frac{S\ 6}{S\ 7}$</p> <p style="text-align: center;">1965 LAND SURVEY</p> <p>This cor. is accepted as the best available evidence of the position of the original corner.</p> <p style="text-align: center;">_____</p> <p style="text-align: center;">(Restoring the 1871 Survey by J. Fenson Smith and the 1881 Resurvey by Andrew J. Stewart Jr.)</p> <p style="text-align: center;">_____</p> <p>S. 86° 54' W., beginning new measurement.</p> <p>Over nearly level land.</p>	
3.40	<p>Center line of U.S. Highway No. 189, 60 lks. wide, bears NW and SE, thence over rolling mountainous land.</p>	
40.83	<p>The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., heretofore described.</p> <p style="text-align: center;">_____</p> <p style="text-align: center;">(Restoring the 1881 Survey by Andrew J. Stewart Jr.)</p> <p style="text-align: center;">_____</p> <p>From the cor. of secs. 5, 6, 7, and 8.</p> <p>N. 0° 52' W., bet. secs. 5 and 6.</p> <p>Desc. NW slope through dense to scattering oak brush.</p>	
40.25	<p>The ¼ sec. cor. of secs. 5 and 6, monumented with an iron pipe, 1½ in. diam., firmly set and projecting 6 ins. above ground, with a steel fence post alongside, with brass cap mkd.</p> <p style="text-align: center;">¼ S 6 S 5 </p> <p style="text-align: center;">1951</p>	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 6 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
18.55	<p>This cor. is harmoniously related to identified original cors., and is accepted as the best available evidence of the original cor. position.</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.</p> <p>There are no suitable bearing trees within limits.</p> <p style="text-align: center;">_____</p> <p>N. 2° 42' W., beginning new measurement.</p> <p>Desc. N slope through dense to scattering oak.</p> <p>Point for the N 1/16 sec. cor. of secs. 5 and 6.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S 6 S 5</p> <p style="text-align: center;">1971</p> <p>Raise a mound of stone, 3 ft. base, 2½ ft. high, W of cor.</p> <p>There are no suitable bearing trees within limits.</p>
37.94	<p>The closing cor. of secs. 5 and 6, heretofore described.</p> <p>From this closing cor., the angle point bet. secs. 5 and 32, bears S. 89° 58' E., 1.24 chs. dist., heretofore described.</p>
<p>Subdivision of Section 4, T. 6 S., R. 3 E., Salt Lake Meridian, Utah</p>	
39.62	<p>From the ¼ sec. cor. of secs. 4 and 9.</p> <p>N. 1° 59' W., on the N and S center line of sec. 4.</p> <p>Point for the center ¼ sec. cor. of sec. 4, at intersection with the E and W center line.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 3 E</p> <p style="text-align: center;">C ¼ S 4</p> <p style="text-align: center;">1979</p> <p>There are no suitable bearing trees within limits.</p> <p>Cor. is located 90 lks. W of 50 ft. cliff, on a steep oak brush covered slope, with a talus slope intermingled in the brush.</p>
79.22	<p>The ¼ sec. cor. of sec. 4, on the N. bdy. of the Tp., heretofore described.</p>

Subdivision of Section 4,
T. 6 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
<p>39.92</p> <p>59.42</p>	<p>From the 1/4 sec. cor. of secs. 3 and 4.</p> <p>N. 88° 51' W., on the E and W center line of sec. 4.</p> <p>The center 1/4 sec. cor. of sec. 4.</p> <p>Point for the center west 1/16 sec. cor. of sec. 4.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, encircled with a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 3 E</p> <p style="text-align: center;">C $\frac{W 1/16}{S 4}$ C</p> <p style="text-align: center;">1978</p> <p>There are no suitable bearing trees within limits.</p> <p>Cor. is located on a steep NE slope, in dense undergrowth.</p> <p>78.92 The 1/4 sec. cor. of secs. 4 and 5.</p>
<p>39.71</p>	<p>From the W 1/16 sec. cor. of secs. 4 and 9.</p> <p>N. 1° 15' W., on the N and S center line of the SW 1/4 of sec. 4.</p> <p>The centerwest 1/16 sec. cor. of sec. 4.</p>
	<p style="text-align: center;">Subdivision of Section 5, T. 6 S., R. 3 E., Salt Lake Meridian, Utah</p>
<p>19.37</p> <p>38.74</p>	<p>From the 1/4 sec. cor. of secs. 5 and 8.</p> <p>N. 1° 42' W., on the N and S center line of sec. 5.</p> <p>Point for the centersouth 1/16 sec. cor. of sec. 5.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C</p> <p style="text-align: center;">S 1/16 S 5</p> <p style="text-align: center;">C</p> <p style="text-align: center;">1971</p> <p>There are no suitable bearing trees within limits.</p> <p>Raise a mound of stone, 3 1/2 ft. base, 2 ft. high, 1 lk. west of cor.</p> <p>A paved road, bears North 78.5 lks.</p> <p>Point for the center 1/4 sec. cor. of sec. 5, at intersection with the E and W center line.</p>

Subdivision of Section 5,
T. 6 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T 6 S R 3 E

C ¼ S 5

1971

from which

A maple, 5 ins. diam., bears N. 33° 45' E., 124 lks. dist., mkd. X BT.

A maple, 10 ins. diam., bears N. 49° 15' W., 45 lks. dist., mkd. C ¼ S 5 BT.

Cor. is located on steep N facing slope.

77.12 The ¼ sec. cor. of sec. 5, on the N. bdy. of the Tp., heretofore described.

From the ¼ sec. cor. of secs. 4 and 5.

N. 89° 41' W., on the E and W center line of sec. 5.

20.32 Point for the centereast 1/16 sec. cor. of sec. 5.

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 3½ ft. base, to top of brass cap, mkd.

$$\frac{E \ 1/16}{S \ 5} \ C$$

1971

There are no suitable bearing trees within limits.

40.64 The center ¼ sec. cor. of sec. 5.

79.57 The ¼ sec. cor. of secs. 5 and 6.

From the east 1/16 sec. cor. of secs. 5 and 8.

N. 1° 13' W., on the N and S center line of the SE¼ of sec. 5.

19.63 Point for the SE 1/16 sec. cor. of sec. 5, at intersection with the E and W center line of the SE¼ of sec. 5.

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

$$\frac{SE \ 1/16}{S \ 5}$$

1971

from which

A maple, 6 ins. diam., bears S. 63° 45' W., 39 lks. dist., mkd. SE 1/16 S 5 BT.

Subdivision of Section 5,
T. 6 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
	<p>A maple, 4 ins. diam., bears N. 61° 45' W.; 19 lks. dist., mkd. X BT.</p>
39.25	<p>The centereast 1/16 sec. cor. of sec. 5.</p>
	<p>From the south 1/16 sec. cor. of secs. 4 and 5. N. 88° 47' W., on the E and W center line of the SE$\frac{1}{4}$ of sec. 5.</p>
20.10	<p>The SE 1/16 sec. cor. of sec. 5.</p>
40.14	<p>The centersouth 1/16 sec. cor. of sec. 5.</p>
	<p>Subdivision of Section 6, T. 6 S., R. 3 E., Salt Lake Meridian, Utah</p>
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 6 and 7. N. 1° 27' W., on the N and S center line of sec. 6.</p>
39.25	<p>Point for the center $\frac{1}{4}$ sec. cor. of sec. 6, at the inter- section with the E and W center line.</p>
	<p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T 6 S R-3 E</p>
	<p style="text-align: center;">C $\frac{1}{4}$ S 6</p>
	<p style="text-align: center;">1971</p>
	<p>There are no suitable bearing trees within limits. Cor. is set 33 lks. S of the center line of a road bearing east and west, 15 lks. wide.</p>
58.72	<p>Point for the centernorth 1/16 sec. cor. of sec. 6.</p>
	<p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">C</p>
	<p style="text-align: center;">N 1/16 S 6</p>
	<p style="text-align: center;">C</p>
	<p style="text-align: center;">1971</p>
	<p>There are no suitable bearing trees within limits. Raise a mound of stone, 2$\frac{1}{2}$ ft. base, 2 ft. high, W of cor.</p>
78.62	<p>The $\frac{1}{4}$ sec. cor. of sec. 6, on the N. bdy. of the Tp., heretofore described.</p>
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 5 and 6.</p>
	<p>S. 87° 57' W., on the E and W center line of sec. 6.</p>

Subdivision of Section 6,
T. 6 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
20.14	<p>Point for the centereast 1/16 sec. cor. of sec. 6.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C $\frac{E\ 1/16}{S\ 6}$ C</p> <p style="text-align: center;">1971</p> <p>There are no suitable bearing trees within limits.</p> <p>Raise a mound of stone, 2½ ft. base, 2 ft. high, N of cor.</p>
40.28	The center ¼ sec. cor. of sec. 6.
80.36	The ¼ sec. cor. of sec. 6, on the W. bdy. of the Tp., heretofore described.
19.02	<p>From the centereast 1/16 sec. cor. of sec. 6.</p> <p>N. 2° 04' W., on the N and S center line of the NE¼ of sec. 6.</p> <p>Point for the NE 1/16 sec. cor. of sec. 6, at intersection with the E and W center line of the NE¼.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16</p> <p style="text-align: center;">S 6</p> <p style="text-align: center;">1971</p> <p>There are no suitable bearing trees within limits.</p> <p>Raise a mound of stone, 2½ ft. base, 2 ft. high, W of cor.</p>
38.67	The E 1/16 sec. cor. of sec. 6, on the N. bdy. of the Tp., heretofore described.
19.99	<p>From the N 1/16 sec. cor. of secs. 5 and 6.</p> <p>S. 89° 21' W., on the E and W center line of the NE¼ of sec. 6.</p> <p>The NE 1/16 sec. cor. of sec. 6.</p>
39.86	The centernorth 1/16 sec. cor. of sec. 6.
	<p>Subdivision of Section 7, T. 6 S., R. 3 E., Salt Lake Meridian, Utah</p>
	<p>From the ¼ sec. cor. of secs. 7 and 18.</p> <p>N. 1° 14' W., on the N and S center line of sec. 7.</p>

Subdivision of Section 7,
T. 6 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
39.90	<p>Point for the center $\frac{1}{4}$ sec. cor. of sec. 7, at intersection with the E and W center line.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 3 E</p> <p style="text-align: center;">C $\frac{1}{4}$ S 7</p> <p style="text-align: center;">1974</p> <p>There are no suitable bearing trees within limits.</p> <p>Cor. is set on the W edge of a 12 ft. wide trail, bears SE and NW.</p>
82.16	<p>The $\frac{1}{4}$ sec. cor. of secs. 6 and 7.</p> <hr/> <p>From the $\frac{1}{4}$ sec. cor. of secs. 7 and 8.</p> <p>N. $89^{\circ} 50'$ W., on the E and W center line of sec. 7.</p>
19.99	<p>Point for the centereast $\frac{1}{16}$ sec. cor. of sec. 7.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C $\frac{E \frac{1}{16}}{S 7}$ C</p> <p style="text-align: center;">1974</p> <p>There are no suitable bearing trees within limits.</p> <p>Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N of cor.</p> <p>Cor. is set on a steep SW facing slope.</p>
39.98	<p>The center $\frac{1}{4}$ sec. cor. of sec. 7.</p>
80.40	<p>The $\frac{1}{4}$ sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp., monumented with a brass cap set in concrete, mkd. with a cross (X).</p> <p>from which</p> <p style="padding-left: 40px;">A cross (X) on curb in parking lot, bears N. $48^{\circ} 52'$ E., 69 lks. dist.</p> <p style="padding-left: 40px;">A cross (X) on curb in parking lot, bears N. $21^{\circ} 47'$ W., 16 lks. dist.</p> <p>This cor. is accepted as the best available evidence of the position of the original corner.</p> <hr/> <p style="text-align: center;">Subdivision of Section 8, T. 6 S., R. 3 E., Salt Lake Meridian, Utah</p> <hr/> <p>From the $\frac{1}{4}$ sec. cor. of secs. 8 and 17, monumented with an iron post, $2\frac{1}{2}$ ins. diam., projecting 18 ins. above ground with brass cap mkd. as described in the official record of the 1977 resurvey.</p>

Subdivision of Section 8,
T. 6 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
	N. 0° 05' E., on the N and S center line of sec. 8.
38.68	Point for the center $\frac{1}{4}$ sec. cor. of sec. 8, at the intersection with the E and W center line. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. T 6 S R 3 E C $\frac{1}{4}$ S 8 1974 There are no suitable bearing trees within limits. Raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft. high, W of cor.
60.00	Point for the centernorth $\frac{1}{16}$ sec. cor. of sec. 8. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. C N $\frac{1}{16}$ S 8 C 1974 There are no suitable bearing trees within limits. Raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 2 ft. high, W of cor.
81.32	The $\frac{1}{4}$ sec. cor. of secs. 5 and 8.
	From the $\frac{1}{4}$ sec. cor. of secs. 8 and 9. S. 88° 02' W., on the E and W center line of sec. 8.
39.96	The center $\frac{1}{4}$ sec. cor. of sec. 8.
78.33	The $\frac{1}{4}$ sec. cor. of secs. 7 and 8.
	From the north $\frac{1}{16}$ sec. cor. of secs. 8 and 9. S. 89° 58' W., on the E and W center line of the NE $\frac{1}{4}$ of sec. 8.
39.87	The centernorth $\frac{1}{16}$ sec. cor. of sec. 8.
	Subdivision of Section 12, T. 6 S., R. 3 E., Salt Lake Meridian, Utah
	From the $\frac{1}{4}$ sec. cor. of secs. 12 and 13. N. 0° 30' W., on the N and S center line of sec. 12.
19.23	Point for the centersouth $\frac{1}{16}$ sec. cor. of sec. 12.

Subdivision of Section 12,
T. 6 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">C S 1/16 S 12 C 1974</p> <p>from which</p> <p>A spruce, 8 ins. diam., bears N. 53° 45' E., 101 lks. dist., mkd. C S 1/16 S12 BT.</p> <p>A spruce, 4 ins. diam., bears N. 89° 15' W., 51 lks. dist., mkd. X BT.</p>
38.46	<p>Point for the center ¼ sec. cor. of sec. 12, at intersection with the E and W center line.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 6 S R 3 E C ¼ S 12 1974</p> <p>There are no suitable bearing trees within limits.</p>
57.71	<p>Point for the centernorth 1/16 sec. cor. of sec. 12.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16 S 12 C 1974</p> <p>Dig pits, 18 x 18 x 12 ins., N and S of cor., 3 ft. dist.</p> <p>There are no suitable bearing trees within limits.</p> <p>Cor. is located on a steep SE facing slope.</p>
76.96	<p>The ¼ sec. cor. of secs. 1 and 12.</p>
10.20	<p>From the ¼ sec. cor. of sec. 12, on the E. bdy. of the Tp., heretofore described.</p> <p>N. 89° 56' W., on the E and W center line of sec. 12.</p> <p>Point for the center E - E 1/64 sec. cor. of sec. 12.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Subdivision of Section 12,
T. 6 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
	$C \frac{E - E \frac{1}{64}}{S \ 12} C$ <p style="text-align: center;">1974</p> <p>There are no suitable bearing trees within limits.</p> <p>Set a 3 in. diam., oak post, 5 ft. long, S of cor.</p>
20.40	<p>Point for the centereast 1/16 sec. cor. of sec. 12.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	$C \frac{E \ 1/16}{S \ 12} C$ <p style="text-align: center;">1974</p> <p>There are no suitable bearing trees within limits.</p> <p>Set a 4 in. diam., oak post, 5 ft. long, west of cor.</p>
40.80	The center ¼ sec. cor. of sec. 12.
81.52	The ¼ sec. cor. of secs. 11 and 12.
	<p>From the centereast 1/16 sec. cor. of sec. 12.</p> <p>N. 1° 03' W., on the N and S center line of the NE¼ of sec. 12.</p>
9.75	Point for the centersouth NE 1/64 sec. cor. of sec. 12. Point not monumented.
19.50	<p>Point for the NE 1/16 sec. cor. of sec. 12, at intersection with the E and W center line of the NE¼ of sec. 12.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p>
	<p>NE 1/16 S 12</p> <p style="text-align: center;">1974</p> <p>There are no suitable bearing trees within limits.</p> <p>Set a 3 ins. diam., oak post, 5 ft. long, to the W of cor.</p>
39.00	The east 1/16 sec. cor. of secs. 1 and 12.
	<p>From the north 1/16 sec. cor. of sec. 12, on the E. bdy. of the Tp., heretofore described.</p> <p>S. 89° 21' W., on the E and W center line of the NE¼ of sec. 12.</p>
10.12	Point for the centereast NE 1/64 sec. cor. of sec. 12. Point not monumented.
20.24	The NE 1/16 sec. cor. of sec. 12.
40.49	The centernorth 1/16 sec. cor. of sec. 12.

490

Subdivision of Section 12,
T. 6 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS		
9.81	<p>From the center E - E 1/64 sec. cor. of sec. 12.</p> <p>N. 1° 15' W., on the N and S center line of the SE$\frac{1}{4}$ of the NE$\frac{1}{4}$ of sec. 12.</p> <p>Point for the southeast NE 1/64 sec. cor. of sec. 12, at intersection with the E and W center line of the SE$\frac{1}{4}$ of the NE$\frac{1}{4}$ of sec. 12.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 12 SE - NE 1/64 1974</p>	
19.62	<p>There are no suitable bearing trees within limits.</p> <p>Set a 4 in. diam., maple post, 5 ft. long, W of cor.</p> <p>Point for the centereast NE 1/64 sec. cor. of sec. 12.</p>	
10.16 20.32	<p>From the south N 1/64 sec. cor. of sec. 12, on the E. bdy. of the Tp., heretofore described.</p> <p>S. 89° 42' W., on the E and W center line of the SE$\frac{1}{4}$ of the NE$\frac{1}{4}$ of sec. 12.</p> <p>The southeast NE 1/64 sec. cor. of sec. 12.</p> <p>Point for the centersouth NE 1/64 sec. cor. of sec. 12.</p>	
19.49	<p>From the east 1/16 sec. cor. of sec. 12 and 13.</p> <p>N. 0° 42' W., on the N and S center line of the SE$\frac{1}{4}$ of sec. 12.</p> <p>Point for the SE 1/16 sec. cor. of sec. 12.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S 12 1974</p> <p>from which</p> <p style="padding-left: 40px;">A spruce, 8 ins. diam., bears N. 37° E., 79 lks. dist., mkd. SE 1/16 S12 BT.</p> <p style="padding-left: 40px;">A maple, 4 ins. diam., bears S. 64° 30' E., 24 lks. dist., mkd. X BT.</p>	
39.00	<p>Set a 2½ in. maple post, 5 ft. long, W of cor.</p> <p>The center east 1/16 sec. cor. of sec. 12.</p> <p>From the south 1/16 sec. cor. of sec. 12 on the E. bdy. of the Tp., heretofore described.</p>	

Subdivision of Section 12,
T. 6 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS

- N. 89° 09' W., on the E and W center line of the SE $\frac{1}{4}$ of sec. 12.
- 20.49 The southeast 1/16 sec. cor. of sec. 12.
- 30.74 Point for the centerwest SE 1/64 sec. cor. of sec. 12.
Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
- S 12
C - W - SE
1/64
1974
- from which
- An aspen, 7 ins. diam., bears N. 70° 15' E.,
9 lks. dist., mkd. X BT.
- A pine, 4 ins. diam., bears S. 86° 15' W., 96 lks.
dist., mkd. X BT.
- 40.99 The center south 1/16 sec. cor. of sec. 12.

General Description

The land encompassed in this survey is located in the foothills and mountains north and east of Provo, Utah, county, Utah. For the most part the land is part of Uinta National Forest, with the elevation ranging from 4700+ in sec. 7 to 10,908 ft. in sec. 10.

Generally speaking the terrain is mountainous, with numerous steep ledges and cliffs, particularly on the Cascade Mountain, which is situated in the center of the township. The terrain east and west of this mountainous ridge is steep, rolling hills, covered with thick oak brush. The higher elevations have aspen, pine, and spruce generating into high alpine vegetation.

Drainage is to the north and west, draining into the Provo River drainage.

U.S. Highway No. 189 runs north along the west side of this township, intersecting with Utah State Highway 52 in the west side of sec. 7. The highway then proceeds north and east into Provo Canyon, traversing through secs. 4, 5, 6, and 7, and exiting the township at the north boundary of sec. 4. There is a major graded dirt road junctioning with U.S. 189 in sec. 5, then proceeding southeasterly along Pole Canyon which is on a large bench, separating the Cascade Mountain and the steep foothills just above Provo. This dirt road provides the only access to the interior of this township.

The principal use of the area is for recreation by hunters, campers and picnickers.

The mean of a considerable number of observations of the magnetic declination is 15° 45' E.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Johnnie R. Mendez	Cadastral Surveyor
Everett E. Gorgen	Survey Aid
Richard P. Godesiabois	Survey Aid
Richard G. Foutch	Survey Aid
Thomas C. Maguire	Survey Aid
Thomas P. McCarty	Survey Aid
James L. MacPherson, Jr.	Survey Aid
Louis J. Scheeler	Survey Aid
John Hales	Surveying Technician
Mark McKay	Survey Aid
Blaine Tew	Survey Aid

CERTIFICATE OF SURVEY

~~XX~~(We), Glen B. Hatch and Ray Harpin, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 11th day of August, 1969, ~~XX~~We have dependently resurveyed the First Standard Parallel South along the south boundary of Tps. 5 S., Range 3 East and portions of Range 4 East, a portion of the east boundaries of Tps. 6 S., Rgs. 2 and 3 E., and a portion of the subdivisional lines; and the survey of the subdivision of certain sections of T. 6 S., R. 3 E.,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by ~~XX~~ (us) and under ~~XX~~ (our) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

January 21, 1982 (Date) [Signature: Ray Harpin] (Cadastral Surveyor) Supervisory
January 21, 1982 (Date) [Signature: Glen B Hatch] (Cadastral Surveyor) Supervisory

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Denver, Colorado

The foregoing field notes of the dependent resurvey of the First Standard Parallel South along the south boundary of Tps. 5 S., R. 3 E., and portions of R. 4 E., a portion of the east boundaries of Tps. 6 S., Rgs. 2 and 3 E., and a portion of the subdivisional lines; and the survey of the subdivision of certain sections of T. 6 S., R. 3 E., Salt Lake Meridian, Utah

executed by Glen B. Hatch, Supervisory Cadastral Surveyor
Ray Harpin, Supervisory Cadastral Surveyor
having been critically examined and found correct, are hereby approved.

June 15, 1982 (Date) [Signature: Glen B Hatch] ~~(Cadastral Surveyor)~~
Chief Cadastral Surveyor for Utah

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____ is a true copy of the original field notes.

(Date) (Chief, Cadastral Survey Examination and Approval Staff)

INDEX DIAGRAM

Township 5 South, Range 24 East

6	5	4	3	4	2	1
				2		
7	8	9	10	11	12	
18	17	16	15	14	13	
19	20	21	22	23	24	
30	29	28	27	26	25	
31	32	33	34	35	36	

Township 5 South, Range 24 East
Salt Lake Meridian, Utah

CHAINS

The following field notes are those of the subdivision of sections 2 and 3, Township 5 South, Range 24 East, Salt Lake Meridian, Utah.

In 1879, E. Buettner, Deputy Surveyor, surveyed the First Standard Parallel South, and the south boundary. In 1916, Ralph Gentry, resurveyed the First Standard Parallel South, the west boundary, and surveyed the east and north boundaries, the subdivisional lines, except the line between sections 35 and 36, and meandered the Green River. In 1922, A. Parker Warner surveyed the section line between sections 35 and 36.

These surveys were executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and Special Instructions dated May 21, 1970.

All original corners were recovered. Where necessary, these points were rehabilitated.

The direction of the lines of this survey were determined by altitude observations on the sun. The lines were carried forward by sustained angulation and supplemented by other altitude observations on the sun taken throughout the progress of the survey. They refer to the true meridian.

The geographic position of the 1/4 section corner of sections 1 and 2, as scaled from U. S. Geological Survey, "Split Mountain, Utah", quadrangle map, 1955, 7½' series, is as follows:

Latitude 40° 24.9' N.
Longitude 109° 10.4' W.

The observed mean magnetic declination is 15° E.

Subdivision of Section 2
Township 5 South, Range 24 East
Salt Lake Meridian, Utah

Beginning at the 1/4 sec. cor. of secs. 1 and 2, monumented with an iron post, 1 in. diam., firmly set, projecting 20 ins. above the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.

1/4 |
S 2 | S 1

1916

from which an original bearing tree

A juniper, 5 ins. diam., bears S. 88½° E., 76 lks. dist., mkd. 1/4 S1 BT.

new bearing tree:

A juniper, 5 ins. diam., bears S. 40° W., 59 lks. dist., mkd. 1/4 S2 BT.

Corner is located on a steep N. slope.

Subdivision of Section 2
Township 5 South, Range 24 East
Salt Lake Meridian, Utah

CHAINS	
	S. 89° 58' W., along the E. and W. center line of sec. 2.
	Through scattered juniper and pinon.
17.85	Ascend precipitous E. slope.
18.21	Rugged sandstone spur, slopes S.
40.12	Point for a witness point on the E. and W. center line of sec. 2.
	Set an iron post, 30 ins. long, 2½ ins. diam., 2 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with brass cap mkd.
	W P
	C — S 2 — C
	1970
42.12	Rim of canyon.
47.20	Bottom of canyon, 2 chains wide, drains W.
49.10	Rim of canyon, bears E. and W., ascend steep NE. slope.
63.70	Descend rocky SW. slope.
75.17	Creek, 2 lks. wide, 1 in. deep, flows NW., in channel, 30 lks. wide, 15 ft. deep.
77.52	Ascend steep vertical bank.
80.12	The 1/4 sec. cor. of secs. 2 and 3, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd.
	S 3 S 2 1/4
	1916
Subdivision of Section 3 Township 5 South, Range 24 East Salt Lake Meridian, Utah	
	From the 1/4 sec. cor. of secs. 3 and 10, monumented with an iron post, 1 in. diam., firmly set, projecting 13 ins. above the ground, with brass cap mkd.
	1/4 S 3 S 10
	1916
	from which the original bearing trees

Subdivision of Section 3
Township 5 South, Range 24 East
Salt Lake Meridian, Utah

CHAINS	
	<p>A juniper, 6 ins. diam., bears N. $82\frac{1}{2}^{\circ}$ E., 60 lks. dist., mkd. 1/4 S3 BT.</p> <p>A juniper, 8 ins. diam., bears S. 20° E., 44 lks. dist., mkd. 1/4 S10 BT.</p> <p>N. $0^{\circ} 13'$ E., along the N. and S. center line of sec. 3.</p> <p>Descend gentle, rolling N. slope, through dense sage and scattered juniper.</p>
4.10	Trail road, 10 lks. wide, bears SE. and NW.
14.88	Descend steep slope and enter dense juniper.
24.10	Wash, 30 lks. wide, 5 ft. deep, drains W.
29.90	Same wash, 40 lks. wide, 4 ft. deep, drains NE.
32.00	Same wash, 20 lks. wide, 3 ft. deep, drains NW.
39.87	<p>The center 1/4 sec. cor. of sec. 3, monumented with a steel pipe, 1/2 in. diam., with $1\frac{1}{2}$ in. diam. cap, firmly set, projecting 12 ins. above the ground, in a mound of stone, $1\frac{1}{2}$ ft. base to top, no markings on the cap.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground to bedrock, in a collar of stone, $3\frac{1}{2}$ ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T5S R24E C 1/4 S 3</p> <p style="text-align: center;">1970</p> <p>from which</p> <p>A juniper, 6 ins. diam., bears N. $30\frac{1}{2}^{\circ}$ E., 43 lks. dist., mkd. C 1/4 S3 BT.</p> <p>A juniper, 15 ins. diam., bears N. $68\frac{1}{2}^{\circ}$ W., 40 lks. dist., mkd. C 1/4 S3 BT.</p> <p>Deposit the original steel pipe inside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. $0^{\circ} 13'$ E., beginning new measurement.</p>
2.20	South rim of sandstone canyon, 100 ft. deep, drains WNW.
6.10	North rim of sandstone canyon.
15.20	Saddle of ridge, bears E. and W.
20.90	Wash, 10 lks. wide, 3 ft. deep, drains NW.
25.60	Power line, bears S. $71\frac{1}{2}^{\circ}$ E. and N. $71\frac{1}{2}^{\circ}$ W.
26.30	Graded road, 30 lks. wide, bears E. and W. on a curve.
28.40	Creek, 5 lks. wide, 4 ins. deep, flows W. in channel, 60 lks. wide, 20 ft. deep, with many large cottonwoods along both banks; ascend through scattered sage and juniper.

Subdivision of Section 3
 Township 5 South, Range 24 East
 Salt Lake Meridian, Utah

CHAINS	
32.20	Spur, slopes W.
34.70	Wash, 100 lks. wide, 25 ft. deep, drains SW.
35.00	Begin along fence, bears N.
38.70	The 1/4 sec. cor. of secs. 3 and 34, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd.
	$1/4 \frac{S \ 34}{S \ 3}$
	1916
	from which the 1916 bearing tree
	A juniper, 18 ins. diam., bears S. 64 3/4° W., 81 lks. dist., mkd. 1/4 S3 BT. (Record, S. 66° W., 72 lks. dist.)
	new bearing tree
	A juniper, 14 ins. diam., bear N. 42 1/2° W., 108 lks. dist., mkd. 1/4 S34 BT.
	Corner is located in fence line bearing N. and S.
	From the 1/4 sec. cor. of secs. 2 and 3.
	WEST, along the E. and W. center line of sec. 3.
	Through dense sagebrush and scattering juniper.
0.03	Power line, bears S. 41° E. and N. 41° W.
1.000	Graded road, 20 lks. wide, bears SW.
5.700	Ascend sandstone cliff, 70 ft. high.
6.30	Top of sandstone cliff, thence along sandstone spur, slopes N.
13.500	Descend sandstone cliff.
15.500	Wash, 10 lks. wide, drains N.
17.600	Ascend sandstone cliff, 100 ft. high.
30.850	Descend steep sandstone NW. slope.
34.600	Wash, 20 lks. wide, drains NW.
39.94	The center 1/4 sec. cor. of sec. 3.

	WEST, beginning new measurement.
1.20	Spur, slopes N.
3.60	Wash, 21 lks. wide, drains NW.

Subdivision of Section 3
Township 5 South, Range 24 East
Salt Lake Meridian, Utah

CHAINS	
8.50	Canyon, 5 chains wide, 70 ft. deep.
13.90	Spur, slopes N.
17.60	Wash, 50 lks. wide, 10 ft. deep, drains NW.
26.40	Trail road, 15 lks. wide, bears N. and S.
30.00	Wash, 90 lks. wide, 15 ft. deep, drains NE.
33.90	Spur, slopes N.
37.90	Wash, 30 lks. wide, 5 ft. deep, drains NW.
39.87	The 1/4 sec. cor. of secs. 3 and 4, monumented with an iron post, 1 in. diam., firmly set, projecting 36 ins. above the ground, in a mound of stone, 4 ft. base, 2½ ft. high, with brass cap mkd.
	<p style="text-align: center;">1/4 S 4 S 3 1916</p>
	<p>from which</p> <p style="padding-left: 40px;">A juniper, 8 ins. diam., bears S. 72° E., 79 lks. dist., mkd. 1/4 S3 BT.</p> <p style="padding-left: 40px;">A juniper, 8 ins. diam., bears N. 69½° W., 41 lks. dist., mkd. 1/4 S4 BT.</p>
	<p style="text-align: center;">General Description</p> <p>The land encompassed in this survey falls a half-mile south of the Morris Ranch. The elevation ranges from 4800 feet above sea level at the west boundary of section 3 to 5400 feet above sea level at the east boundary of section 2. The north half of sections 2 and 3 are drained by Cub Creek. Its drainage being generally to the west, into the Green River.</p> <p>The general terrain of the area is rough, broken terrain, with many rocky ledges and vertical rock faces. The soil varies from sandy loam to open rock surfaces. The vegetation consists of sparse scattered sagebrush and juniper. There are scattered cottonwoods along Cub Creek.</p>

CERTIFICATE OF SURVEY

(I) ~~(We)~~, Douglas A. Cody, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 21st day of May, 19 70, (I) ~~(We)~~ have surveyed a portion of the subdivision of sections 2 and 3, Township 5 South, Range 24 East,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

September 13, 1976 (Date) Douglas A. Cody Supervisory (Cadastral Surveyor) Douglas A. Cody (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Washington, D.C. Denver, Colorado

The foregoing field notes of the Survey of a portion of the subdivision of sections 2 and 3, Township 5 South, Range 24 East, Salt Lake Meridian, Utah.

executed by Douglas A. Cody Supervisory Cadastral Surveyor having been critically examined and found correct, are hereby approved.

MAR 30 1982 (Date) Acting Chief, Cadastral Survey Examination and Approval Staff (Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes.

(Date) (Chief, Division of Cadastral Survey) GPO 849-626

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
ORIGINAL

R602

503

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF A PORTION OF THE SUBDIVISIONAL LINES

AND

THE SURVEY OF THE SUBDIVISIONS OF SECTIONS 8, 9 AND 17

OF

TOWNSHIP 3 SOUTH, RANGE 20 EAST

Of the Salt Lake Meridian,
In the State of Utah

EXECUTED BY

Gail E. Reynolds Supervisory Cadastral Surveyor

Under special instructions dated September 21, 19 79, approved September 27, 1979

_____, which provided for the surveys included under ~~USS Survey~~ Group
Number 593, and assignment instructions dated July 14, 19 80.

Survey commenced July 24, 19 80

Survey completed November 25, 19 80

INDEX DIAGRAM

Township 3 South, Range 20 East

6	5 14	4 9	3 3	2	1
7 13	8 7 12	9 1 7	10	11	12
18 11	17 6 9	16 5	15	14	13
19	20 4	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision of Section 8
 Subdivision of Section 9
 Subdivision of Section 17

- Page 15
 - Page 16
 - Page 17

Township 3 South, Range 20 East, Salt Lake Meridian, Utah

CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, and the survey of the subdivisions of secs. 8, 9 and 17 of T. 3 S., R. 20 E., Salt Lake Meridian, Utah.

The resurvey and survey were executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and special instructions for Group No. 593, Utah, dated September 21, 1979. A portion of the subdivisional lines was surveyed by A.D. Ferron and E. Buettner in 1879. S.P. and J.R. Stewart surveyed a portion of the subdivisional lines and retraced the W 4 miles of the E - W center line of the township in 1906.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of all lines were determined by observation of Polaris and carried forward by sustained angulation; the distances were determined by a Hewlett-Packard 3820A electronic distance meter.

The geographic position of the closing corner of secs. 20 and 21 is at Latitude $40^{\circ} 32' 15.56''$ N. and Longitude $109^{\circ} 41' 28.66''$ W., as computed by a tie to U.S.G.S. triangulation station "Little Mountain" at Latitude $40^{\circ} 32' 17.63''$ N. and Longitude $109^{\circ} 41' 55.25''$ W., located N. $84^{\circ} 09' 49''$ W., 31.272 chs. dist., from this closing cor. Station is a $\frac{1}{2}$ in. bolt cemented in sandstone boulder; no marks identified.

The mean magnetic declination is $14\frac{1}{4}^{\circ}$ E.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

(Reestablishment of the Survey Executed by
A.D. Ferron and E. Buettner in 1879)

Beginning from the cor. of secs. 9, 10, 15, and 16, monumented with a Uintah engineering aluminum cap on $\frac{1}{2}$ in. aluminum rod, 2 ft. long, extending 6 ins. out of the ground, with cap mkd. Uintah eng. L.S.3. A sandstone, 24 x 18 x 12 ins., plainly mkd. 3 notches on E and 4 notches on S edges was found buried alongside the aluminum rod.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground over Uintah engineering cor., in a collar of stone, to top of brass cap, mkd.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

CHAINS	
	<p style="text-align: center;">T 3 S R 20 E</p> <p style="text-align: center;">S 9 S 10 S 16 S 15</p> <p style="text-align: center;">1980</p>
	<p>Deposit the mkd. stone alongside the iron post.</p> <p>Cor. is located in cultivated land, 4 lks. S of net wire fence cor., which bears N, E and W.</p> <p>N. 1° 54' W., bet. secs. 9 and 10.</p> <p>Over mountainous land, through dense juniper.</p>
4.00	<p>Dry Fork, drains E.</p>
5.50	<p>Red Cloud Loop Road, gravel, bears E and W.</p>
19.89	<p>Point for the S 1/16 sec. cor. of secs. 9 and 10.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, to top of brass cap, mkd.</p>
	<p style="text-align: center;">T 3 S R 20 E</p> <p style="text-align: center;">S 1/16</p> <p style="text-align: center;">S 9 S 10</p> <p style="text-align: center;">1980</p>
39.78	<p>Cor. is located on gentle SE slope in dense juniper.</p> <p>The ¼ sec. cor. of secs. 9 and 10, determined from the remains of the original bearing trees:</p> <p style="padding-left: 40px;">A juniper, 14 ins. diam., bears S. 52° E., 16 lks. dist., mkd. with a blaze and scribed ¼ S10 BT.</p> <p style="padding-left: 40px;">A sawed juniper stump, 14 ins. diam., bears N. 83° W., 27 lks. dist.</p> <p>At the corner point</p>
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T 3 S R 20 E</p> <p style="text-align: center;">¼ S 9 S 10</p> <p style="text-align: center;">1980</p>
	<p>Cor. is located on gentle SE slope in small draw, draining SE in dense juniper.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 52' E., beginning new measurement.</p> <p>Over mountainous land, through dense juniper.</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

CHAINS

40.88

Point for the cor. of secs. 3, 4, 9, and 10, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 24 ins. long, 1 in. diam., drilled 8 ins. in solid sandstone, in a mound of stone, 3 ft. base, to top of brass cap, mkd.

T 3 S R 20 E

S 4	S 3
S 9	S 10

1980

Cor. is located on SE slope in dense juniper.

From the cor. of secs. 2, 3, 10, and 11, monumented with a sandstone, 17 x 8 x 8 ins., firmly set 9 ins. in the ground and plainly mkd. 2 notches on E and 5 notches on S edges. From which the original bearing trees:

A cedar, 18 ins. diam., bears S. 80° E., 14 lks. dist., mkd. S11 BT. (Record, S. 65° E.)

A cedar, 12 ins. diam., bears S. 14° W., 17 lks. dist., mkd. S10 BT. (Record, S. 15° W., 10 lks. dist.).

There is no remaining evidence of other bearing trees.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 3 S R 20 E

S 3	S 2
S 10	S 11

1980

Deposit the mkd. stone alongside the iron post.

Cor. is located on steep rocky SE slope in dense juniper.

S. 88° 48' W., bet. secs. 3 and 10.

Over broken mountainous land, through dense juniper.

39.40

Point for the ¼ sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E

¼	S 3	S 10
---	-----	------

1980

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

CHAINS	
78.80	<p>Cor. is located on gentle SE slope in dense juniper.</p> <p>The cor. of secs. 3, 4, 9, and 10.</p>
40.96	<p>N. 3° 33' W., bet. secs. 3 and 4.</p> <p>Over mountainous land, through dense juniper and sagebrush.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 3 and 4, monumented with a sandstone, 24 x 10 x 10 ins., firmly set and plainly mkd. $\frac{1}{4}$ on W face, with small mound of stone to W.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4$\frac{1}{2}$ ft. base, to top of brass cap, mkd.</p> <div style="text-align: center;"> <p>T 3 S R 20 E</p> <p>$\frac{1}{4}$</p> <p>S 4 S 3</p> <p>1980</p> </div> <p>from which</p> <p>Middle Spring, bears S. 57 3/4° E., 7.70 chs. dist.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Cor. is located on gentle SE slope in sagebrush.</p>
<p>(Reestablishment of the Survey Executed by S.P. and J.R. Stewart in 1906)</p>	
	<p>From the closing cor. of secs. 20 and 21, monumented with a sandstone, 12 x 12 x 8 ins., firmly set 6 ins. in the ground and plainly mkd. 4 notches on E and 2 on S edges, with CC on N face and FTMR on S face, with a mound of stone, 3 ft. base, 1$\frac{1}{2}$ ft. high, N of cor.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p> <div style="text-align: center;"> <p>T 3 S R 20 E</p> <p>CC</p> <p>S 20 S 21</p> <p>FTMR</p> <p>S 20</p> <p>1980</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 4$\frac{1}{2}$ ft. base, 3 ft. high, N of cor.</p> <p>Cor. is located on N slope in sagebrush.</p> <p>N. 0° 27' E., bet. secs. 20 and 21.</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

CHAINS

Over rolling mountain land, through sagebrush.

17.00 Trail road, bears NW and SE.

23.68 The $\frac{1}{4}$ sec. cor. of secs. 20 and 21, monumented with a quartzite stone, 16 x 14 x 7 ins., firmly set 8 ins. in the ground and dimly mkd. $\frac{1}{4}$ on W face.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground to bedrock, and in a collar of stone, to top of brass cap, mkd.

T 3 S R 20 E

$\frac{1}{4}$
 |
 S 20 | S 21

1980

Deposit the mkd. stone alongside the iron post.

Cor. is located in small saddle, bears E and W on E edge of trail road, bears N and S.

N. $0^{\circ} 02'$ W., beginning new measurement.

27.40 Desc. over steep N slope, through sagebrush and juniper trees.

39.73 Point for the cor. of secs. 16, 17, 20, and 21, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 3 S R 20 E

S 17 | S 16
 S 20 | S 21

1980

Cor. is located on spur ridge, slopes N, and 48 lks. W of four strand barb wire fence, bearing N and S.

(Reestablishment of the Survey Executed by Ferron and
Buettner in 1879 and the Retracement Executed by
S.P. and J.R. Stewart in 1906)

From the $\frac{1}{4}$ sec. cor. of secs. 16 and 21, monumented with sandstone, 24 x 24 x 8 ins., firmly set 12 ins. in the ground and plainly mkd. $\frac{1}{4}$ on N face.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

CHAINS	
39.86	<p style="text-align: center;">T 3 S R 20 E</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S\ 16}{S\ 21}$</p> <p style="text-align: center;">1980</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Cor. is located 1.00 ch. W of spur that slopes N in buck brush and scattered pines.</p> <p>S. 89° 32' W., bet. secs. 16 and 21.</p> <p>Over broken mountainous land, through buck brush, sagebrush, choke cherries, and scattered pine.</p> <p>The cor. of secs. 16, 17, 20, and 21.</p>
	<p style="text-align: center;">(Reestablishment of the Survey Executed by A.D. Ferron and E. Buettner in 1879)</p>
19.865	<p>N. 0° 26' W., bet. secs. 16 and 17.</p> <p>Over mountainous land, through buck brush and sagebrush.</p> <p>Point for the S 1/16 sec. cor. of secs. 16 and 17, not monumented.</p>
39.73	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p>
59.595	<p style="text-align: center;">T 3 S R 20 E</p> <p style="text-align: center;">$\frac{1}{4}$</p> <p style="text-align: center;">S 17 S 16</p> <p style="text-align: center;">1980</p> <p>Cor. is located in small draw, draining N and 98 lks. E of 4 strand barb wire fence, bearing N and S.</p> <p>Point for the N 1/16 sec. cor. of secs. 16 and 17.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">T 3 S R 20 E N 1/16</p> <p style="text-align: center;">S 17 S 16</p> <p style="text-align: center;">1980</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

CHAINS						
62.00	Graded road, bears E and W.					
79.46	<p>The cor. of secs. 8, 9, 16, and 17, monumented with a limestone, 22 x 12 x 12 ins., firmly set 10 ins. in the ground and plainly mkd. 4 notches on S and E edges.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 3 S R 20 E</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 8</td> <td style="padding: 0 5px;">S 9</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 17</td> <td style="padding: 0 5px;">S 16</td> </tr> </table> <p style="text-align: center;">1980</p> <p>Deposit the mkd. stone and set a 5 ft. steel fence post alongside the iron post.</p> <p>Cor. is located on E edge of dirt road, bearing N and S.</p>	S 8	S 9	S 17	S 16	
S 8	S 9					
S 17	S 16					
15.50	<p>From the cor. of secs. 9, 10, 15, and 16.</p> <p>S. 89° 39' W., bet. secs. 9 and 16.</p> <p>Over residential and cultivated land.</p>					
29.00	Dry Fork, drains NE.					
40.16	Dry Fork, drains SE.					
40.16	<p>Point for the ¼ sec. cor. of secs. 9 and 16, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 3 S R 20 E</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">¼</td> <td style="border-right: 1px solid black; padding: 0 5px;">S 9</td> <td style="padding: 0 5px;">S 16</td> </tr> </table> <p style="text-align: center;">1980</p> <p>Set 4 ft. juniper post, alongside the iron post.</p> <p>Cor. is located in cultivated land, 5 lks. N of ditch, bearing E and W.</p>	¼	S 9	S 16		
¼	S 9	S 16				
80.32	The cor. of secs. 8, 9, 16, and 17.					
12.00	<p>N. 0° 48' W., bet. secs. 8 and 9.</p> <p>Over bottom land, through cottonwoods and scattered juniper trees.</p>					
16.00	Dry Fork, drains E.					
16.00	Red Cloud Loop Road, graded, bears NW and SE.					

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

CHAINS	
20.11	<p>Point for the S 1/16 sec. cor. of secs. 8 and 9.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 23 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S 8 S 9 1980</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 7 ins. diam., bears N. 85° E., 8 lks. dist., mkd. S 1/16 S9 BT.</p> <p>Cor. is located on steep W slope in scattered juniper.</p>
20.70	<p>Draw, drains S. 45° W., over mountainous land, through juniper trees.</p>
40.22	<p>The ¼ sec. cor. of secs. 8 and 9, monumented with a sandstone, 24 x 8 x 3 ins., firmly set in a mound of stone, and plainly mkd. ¼ on W face. A steel fence post, extending 1½ ft. out of the ground is alongside the cor.</p> <p>from which the 1879 bearing trees:</p> <p style="padding-left: 40px;">A juniper, 14 ins. diam., bears N. 16° E., 21 lks. dist., mkd. ¼ S 9 BT. (Record, N. 25° E., 20 lks. dist.).</p> <p style="padding-left: 40px;">A juniper, 14 ins. diam., bears S. 20° W., 39 lks. dist., mkd. ¼ S8 BT. (Record, S. 17° W., 25 lks. dist.).</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to sandstone, in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 3 S R 20 E ¼ S 8 S 9 1980</p> <p>Deposit the mkd. stone and reset the steel fence post alongside the iron post.</p> <p>Cor. is located on SE slope in dense juniper trees.</p> <p style="text-align: center;">—————</p> <p>N. 1° 20' E., beginning new measurement.</p> <p>Over mountainous land, through dense juniper trees.</p>
40.60	<p>The cor. of secs. 4, 5, 8, and 9, monumented with a limestone, 16 x 12 x 8 ins., firmly set 8 ins. in the ground and plainly mkd. 4 notches on E and 5 notches on S edges, with a steel fence post, extending 1½ ft. out of the ground alongside the cor.</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

CHAINS

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 3 S R 20 E

S 5	S 4
S 8	S 9

1980

Deposit the mkd. stone and reset the steel fence post alongside the iron post.

Cor. is located on steep W slope in sagebrush and scattered juniper trees.

From the cor. of secs. 3, 4, 9, and 10.

S. 89° 46' W., bet. secs. 4 and 9.

Over mountainous land, through dense juniper trees.

39.62 Point for the ¼ sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 3 S R 20 E

¼	S 4	
	S 9	

1980

Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.

Cor. is located on gentle S slope in scattered juniper trees and sagebrush.

79.24 The cor. of secs. 4, 5, 8, and 9.

(Reestablishment of the Survey Executed by Ferron and Buettner in 1879 and the Retracement Executed by S.P. and J.R. Stewart in 1906)

From the cor. of secs. 16, 17, 20, and 21.

S. 88° 29' W., bet. secs. 17 and 20.

Over broken mountainous land, through sagebrush, buck brush, choke cherry, and scattered patches of pine.

19.30 Spur, slopes N.

19.84 Point for the E 1/16 sec. cor. of sec. 17 only.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

CHAINS		
39.68	<p style="text-align: center;">T 3 S R 20 E <u>E 1/16 S 17</u> 1980</p> <p>Raise a mound of stone, 4 ft. base, 2 ft. high, N of cor. Cor. is located on W slope in buck brush.</p> <p>Point for the 1/4 sec. cor. of sec. 17 only, at proportion- ate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>	
40.00	<p style="text-align: center;">T 3 S R 20 E <u>1/4 S 17</u> 1980</p> <p>from which</p> <p style="padding-left: 40px;">A douglas fir, 25 ins. diam., bears North, 147 lks. dist., mkd. 1/4 S17 BT.</p> <p>Cor. is located on NW slope in buck brush.</p> <p>Draw, drains NW.</p>	
59.22	<p>Point for the W 1/16 sec. cor. of sec. 17 only.</p> <p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>	
76.785	<p style="text-align: center;">T 3 S R 20 E <u>W 1/16 S 17</u> 1980</p> <p>Cor. is located on steep E slope in buck brush and scattered pines.</p> <p>The closing cor. of secs. 19 and 20, monumented with a quartzite stone, 18 x 8 x 5 ins., firmly set 10 ins. in the ground and plainly mkd. 5 notches on E and 3 notches on S edges, with CC on S face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 3 S R 20 E <u>S 17</u> S 19 S 20 CC 1980</p>	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

CHAINS

78.76	<p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3½ ft. base, 2 ft. high, S of cor.</p> <p>The cor. of secs. 17 and 18, monumented with a quartzite stone, 18 x 10 x 8 ins., firmly set 10 ins. in the ground and plainly mkd. 5 notches on E and 3 notches on S edges.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 3 S R 20 E</p> <p style="text-align: center;">S 18 S 17 S 19</p> <p style="text-align: center;">1980</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Cor. is located on spur ridge, sloping NW in sagebrush.</p>
<p>(Reestablishment of the Survey Executed by A.D. Ferron and E. Buettner in 1879)</p>	
19.90	<p>N. 1° 26' W., bet. secs. 17 and 18.</p> <p>Over mountainous land, through sagebrush, buck brush and scattered patches of pine.</p> <p>Ledge facing N, 40 ft. high, bears E and W.</p>
20.26	<p>Point for the S 1/16 sec. cor. of secs. 17 and 18.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 3 S R 20 E S 1/16</p> <p style="text-align: center;">S 18 S 17</p> <p style="text-align: center;">1980</p> <p>Cor. is located on N slope in buck brush.</p>
40.52	<p>Point for the ¼ sec. cor. of secs. 17 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 3 S R 20 E</p> <p style="text-align: center;">¼ S 18 S 17</p> <p style="text-align: center;">1980</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

CHAINS					
	Cor. is located on steep N slope in buck brush.				
50.00	Graded road, bears E and W.				
60.78	Point for the N 1/16 sec. cor. of secs. 17 and 18, not monumented.				
81.04	The cor. of secs. 7, 8, 17, and 18, monumented with a sandstone, 15 x 10 x 4 ins., firmly set 6 ins. in the ground and dimly mkd. 4 notches on S edge. Other marks have been obliterated.				
	At the corner point				
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd.				
	<p style="text-align: center;">T 3 S R 20 E</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 7</td> <td style="padding: 0 5px;">S 8</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 18</td> <td style="padding: 0 5px;">S 17</td> </tr> </table> <p style="text-align: center;">1980</p>	S 7	S 8	S 18	S 17
S 7	S 8				
S 18	S 17				
	Deposit the mkd. stone alongside the iron post.				
	Cor. is located on small spur, sloping E.				
	From the cor. of secs. 8, 9, 16, and 17.				
	S. 89° 37' W., bet. secs. 8 and 17.				
	Over rolling land, through sagebrush and scattered juniper trees.				
40.05	The ¼ sec. cor. of secs. 8 and 17, monumented with a limestone, 18 x 10 x 5 ins., firmly set 10 ins. in the ground and plainly mkd. ¼ on N face.				
	At the corner point				
	Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, to top of brass cap, mkd.				
	<p style="text-align: center;">T 3 S R 20 E</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">¼</td> <td style="padding: 0 5px;">S 8</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">S 17</td> </tr> </table> <p style="text-align: center;">1980</p>	¼	S 8		S 17
¼	S 8				
	S 17				
	Deposit the mkd. stone alongside the iron post.				
	Cor. is located on gentle SE slope in scattered juniper				
	S. 89° 36' W., beginning new measurement.				
20.045	Point for the W 1/16 sec. cor. of secs. 8 and 17, not monumented.				
40.09	The cor. of secs. 7, 8, 17, and 18.				

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

CHAINS	
	N. 0° 15' W., bet. secs. 7 and 8.
	Over rolling land, through widely scattered juniper trees.
35.00	Ridge, bears E and W, over mountainous land, through juniper trees.
40.02	The ¼ sec. cor. of secs. 7 and 8, monumented with a sandstone, 19 x 9 x 5 ins., firmly set 11 ins. in the ground and plainly mkd. ¼ on W face. Witnessed by a steel fence post extending 2 ft. out of the ground.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.
	<p style="text-align: center;">T 3 S R 20 E</p> <p style="text-align: center;"> $\frac{1}{4}$ S 7 S 8 1980 </p>
	Deposit the mkd. stone alongside the iron post.
	Cor. is located on rocky steep NE slope in scattered juniper trees.
	N. 3° 59' W., beginning new measurement.
	Over mountainous land, through juniper trees.
20.71	Point for the N 1/16 sec. cor. of secs. 7 and 8.
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.
	<p style="text-align: center;">T 3 S R 20 E</p> <p style="text-align: center;">N 1/16</p> <p style="text-align: center;">S 7 S 8</p> <p style="text-align: center;">1980</p>
	from which
	A juniper, 6 ins. diam., bears S. 76° E., 22 lks. dist., mkd. N 1/16 S8 BT.
	A juniper, 14 ins. diam., bears S. 40° W., 7 lks. dist., mkd. N 1/16 S7 BT.
	Cor. is located on steep SW slope in dense juniper trees.
40.20	Ledge facing N 120 ft. high, bears E and W.
41.42	The cor. of secs. 5, 6, 7, and 8, monumented with a limestone, 36 x 30 x 28 ins., firmly set 20 ins. in the ground and dimly mkd. 5 notches on E face and 1 notch identified on S face.
	At the corner point

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

CHAINS	
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 3 S R 20 E</p> <p style="text-align: center;"> $\begin{array}{r l} \text{S } 6 & \text{S } 5 \\ \text{S } 7 & \text{S } 8 \end{array}$ </p> <p style="text-align: center;">1980</p> <p>from which</p> <p style="padding-left: 40px;">A douglas fir, 4 ins. diam., bears N. 66° E., 11 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A douglas fir, 8 ins. diam., bears S. 2° E., 20 lks. dist., mkd. S 8 BT.</p> <p style="padding-left: 40px;">A douglas fir, 14 ins. diam., bears S. 31° W., 30 lks. dist., mkd. S 7 BT.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Cor. is located on steep rocky NNE slope in douglas fir.</p>
43.41	<p>From the cor. of secs. 4, 5, 8, and 9.</p> <p>N. 88° 00' W., bet. secs. 5 and 8.</p> <p>Over broken mountainous land, through sagebrush and juniper trees.</p> <p>The ¼ sec. cor. of secs. 5 and 8, monumented with a sandstone, 18 x 12 x 12 ins. firmly set in the ground, marks have been obliterated, witnessed by a mound of stone, 2 ft. base, 1 ft. high, N of cor.</p> <p>from which an unrecorded bearing tree</p> <p style="padding-left: 40px;">A juniper, 18 ins. diam., bears S. 41° E., 75 lks. dist., mkd. 1921 LRBTDT.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 3½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 4½ ft. base, to top of aluminum cap, mkd.</p> <p style="text-align: center;">T 3 S R 20 E</p> <p style="text-align: center;"> $\frac{1}{4} \begin{array}{r l} \text{S } 5 \\ \text{S } 8 \end{array}$ </p> <p style="text-align: center;">1980</p> <p>Deposit the cor. stone in mound alongside the iron post.</p> <p>Cor. is located on gentle S slope in sagebrush and scattered juniper trees.</p> <p style="text-align: center;">_____</p> <p>S. 87° 50' W., beginning new measurement.</p>
20.105	<p>Point for the W 1/16 sec. cor. of secs. 5 and 8, not monumented.</p>
22.00	<p>Red Cloud Loop Road, gravel, bears NW and SE.</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

CHAINS	
25.50	Dry Fork, drains SE.
40.21	The cor. of secs. 5, 6, 7, and 8.
Survey of the Subdivision of Section 8, T. 3 S., R. 20 E., Salt Lake Meridian, Utah	
40.13	<p>From the $\frac{1}{4}$ sec. cor. of secs. 8 and 17.</p> <p>N. $2^{\circ} 03'$ W., on the N and S center line of sec. 8.</p> <p>Point for the center $\frac{1}{4}$ sec. cor. of sec. 8, at inter- section with the E and W center line.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 3 S R 20 E</p> <p style="text-align: center;">C $\frac{1}{4}$ S 8</p> <p style="text-align: center;">1980</p> <p>Cor. is located at base of ledge, 200 ft. high, projects NE.</p>
46.50	Dry Fork, drains SE.
48.00	Red Cloud Loop Road, gravel, bears NW and SE.
61.385	Point for the center N $\frac{1}{16}$ sec. cor. of sec. 8, not monumented.
82.64	The $\frac{1}{4}$ sec. cor. of secs. 5 and 8.
27.00	<p>From the $\frac{1}{4}$ sec. cor. of secs. 8 and 9.</p> <p>S. $89^{\circ} 28'$ W., on the E and W center line of sec. 8.</p> <p>Red Cloud Loop Road, gravel, bears NW and SE.</p> <p>Dry Fork, drains SE.</p> <p>The center $\frac{1}{4}$ sec. cor. of sec. 8.</p> <p>Small draw, drains SE.</p> <p>Point for the center W $\frac{1}{16}$ sec. cor. of sec. 8.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">C $\frac{W \frac{1}{16}}{S 8}$ C</p> <p style="text-align: center;">1980</p> <p>From which</p> <p>A juniper, 6 ins. diam., bears S. 39° W., 13 lks. dist., mkd. CW $\frac{1}{16}$ S8 BT.</p>

Survey of the Subdivision of Section 8,
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

CHAINS	
79.75	<p>Cor. is located on E slope in dense juniper trees.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 7 and 8.</p>
20.98	<p>From the center W $\frac{1}{16}$ sec. cor. of sec. 8.</p> <p>N. $3^{\circ} 00'$ W., on the N and S center line of the NW $\frac{1}{4}$ of sec. 8.</p>
35.50	<p>True point for the NW $\frac{1}{16}$ sec. cor. of sec. 8, at intersection with the E and W center line of the NW $\frac{1}{4}$, falls on inaccessible ledges.</p>
39.50	<p>Dry Fork, drains SE.</p>
41.96	<p>Red Cloud Loop Road, gravel, bears NW and SE.</p>
41.96	<p>The point for the W $\frac{1}{16}$ sec. cor. of secs. 5 and 8.</p>
11.00	<p>From the point for the center N $\frac{1}{16}$ sec. cor. of sec. 8.</p> <p>S. $88^{\circ} 38'$ W., on the E and W center line of the NW $\frac{1}{4}$ of sec. 8.</p>
13.50	<p>Red Cloud Loop Road, gravel, bears N and S.</p>
16.26	<p>Dry Fork drains S.</p>
16.26	<p>Point selected for the witness cor. for the NW $\frac{1}{16}$ sec. cor. of sec. 8.</p> <p>Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p>
17.30	<p style="text-align: center;">W C</p> <p style="text-align: center;">← NW $\frac{1}{16}$ S 8</p> <p style="text-align: center;">1980</p> <p>Cor. is located on NE slope in sagebrush.</p>
19.76	<p>Base of ledges, 200 ft. high, bears N and S.</p>
39.52	<p>True point for the NW $\frac{1}{16}$ sec. cor. of sec. 8.</p>
39.52	<p>The N $\frac{1}{16}$ sec. cor. of secs. 7 and 8.</p>
	<p style="text-align: center;">Survey of the Subdivision of Section 9, T. 3 S., R. 20 E., Salt Lake Meridian, Utah</p>
2.00	<p>From the $\frac{1}{4}$ sec. cor. of secs. 9 and 16.</p> <p>N. $0^{\circ} 07'$ W., on the N and S center line of sec. 9.</p> <p>Over mountainous land, through juniper and sagebrush.</p>
3.00	<p>Dry Fork, drains E.</p>
19.995	<p>Red Cloud Loop Road, gravel, bears E and W.</p>
19.995	<p>Point for the center S $\frac{1}{16}$ sec. cor. of sec. 9.</p>

Survey of the Subdivision of Section 9,
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

CHAINS	
	<p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, to top of aluminum cap, mkd.</p> <div style="text-align: center;"> <p>C</p> <p> </p> <p>S 1/16 S 9</p> <p> </p> <p>C</p> <p>1980</p> </div> <p>from which</p> <p style="padding-left: 40px;">A juniper, 18 ins. diam., bears S. 6° W., 5 lks. dist., mkd. C S 1/16 S9.</p> <p>Cor. is located on gentle SE slope in dense juniper trees.</p>
39.99	<p>Point for the center ¼ sec. cor. of sec. 9, at intersection with the E and W center line.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3½ ft. base, to top of brass cap, mkd.</p> <div style="text-align: center;"> <p>T 3 S R 20 E</p> <p>C ¼ S 9</p> <p>1980</p> </div> <p>Cor. is located on rocky SE slope in new growth of juniper trees.</p>
80.72	<p>The ¼ sec. cor. of secs. 4 and 9.</p> <hr/> <p>From the ¼ sec. cor. of secs. 9 and 10.</p> <p>S. 89° 58' W., on the E and W center line of sec. 9.</p> <p>Over mountainous land.</p>
38.92	<p>The center ¼ sec. cor. of sec. 9.</p>
79.56	<p>The ¼ sec. cor. of secs. 8 and 9.</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 9 and 10.</p> <p>S. 89° 49' W., on the E and W center line of the SE ¼ of sec. 9.</p>
39.54	<p>The center S 1/16 sec. cor. of sec. 9.</p> <hr/> <p>S. 89° 49' W., on the E and W center line of the SW ¼ of sec. 9.</p>
40.40	<p>The S 1/16 sec. cor. of secs. 8 and 9.</p> <hr/> <p style="text-align: center;">Survey of the Subdivision of Section 17, T. 3 S., R. 20 E., Salt Lake Meridian, Utah</p> <hr/> <p>From the ¼ sec. cor. of sec. 17 only.</p>

Survey of the Subdivision of Section 17,
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

CHAINS	
	N. $0^{\circ} 42'$ W., on the N and S center line of sec. 17.
20.06	Point for the center S $1/16$ sec. cor. of sec. 17.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd.
	from which
	A juniper, 9 ins. diam., bears S. 45° W., 14 lks. dist., mkd. S $1/16$ S 17.
	Cor. is located on W slope in sagebrush and scattered juniper trees.
40.12	Point for the center $\frac{1}{4}$ sec. cor. of sec. 17, at intersection with the E and W center line.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	<p>T 3 S R 20 E</p> <p>C $\frac{1}{4}$ S 17</p> <p>1980</p>
	from which
	A juniper, 7 ins. diam., bears N. 14° W., 35 lks. dist., mkd. C $\frac{1}{4}$ S 17.
	Cor. is located on E edge of a wash, 15 ft. deep, draining NW.
45.00	Gravel road, bears N and SE.
60.185	Point for the center N $1/16$ sec. cor. of sec. 17.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	Cor. is located on nearly level land in sagebrush.
60.27	Four strand barb wire fence line, bears E and W.
60.67	Improved dirt road, bears E and W.
80.25	The $\frac{1}{4}$ sec. cor. of secs. 8 and 17.

Survey of the Subdivision of Section 17,
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

CHAINS		
19.93	<p>From the $\frac{1}{4}$ sec. cor. of secs. 16 and 17. S. $89^{\circ} 03' W.$, on the E and W center line of sec. 17.</p> <p>Point for the center E $\frac{1}{16}$ sec. cor. of sec. 17.</p> <p>Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">C $\frac{E \frac{1}{16}}{S 17}$ C</p> <p style="text-align: center;">1980</p> <p>from which</p> <p style="padding-left: 40px;">A boulder, 30 x 25 x 15 ft., bears N. $75^{\circ} 41' E.$, 49 lks. dist., to a XBO mkd. on boulder.</p> <p>Cor. is located on NW slope in sagebrush.</p>	
39.86	The center $\frac{1}{4}$ sec. cor. of sec. 17.	
59.65	<p>Point for the center W $\frac{1}{16}$ sec. cor. of sec. 17.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">C $\frac{W \frac{1}{16}}{S 17}$ C</p> <p style="text-align: center;">1980</p> <p>Cor. is located at base of steep N slope, 1.00 ch. S of draw, draining E in sagebrush.</p>	
79.44	The $\frac{1}{4}$ sec. cor. of secs. 17 and 18.	
17.50	<p>From the N $\frac{1}{16}$ sec. cor. of secs. 16 and 17.</p> <p>S. $89^{\circ} 20' W.$, on the E and W center line of the NE $\frac{1}{4}$ of sec. 17.</p> <p>Gravel road, bears NE and SW.</p>	
39.95	The center N $\frac{1}{16}$ sec. cor. of sec. 17.	
19.965	<p>From the E $\frac{1}{16}$ sec. cor. of sec. 17 only.</p> <p>N. $0^{\circ} 34' W.$, on the N and S center line of the SE $\frac{1}{4}$ of sec. 17.</p> <p>Point for the SE $\frac{1}{16}$ sec. cor. of sec. 17, at intersection with the E and W center line of the SE $\frac{1}{4}$.</p> <p>Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">SE $\frac{1}{16}$ S 17 1980</p>	

Survey of the Subdivision of Section 17,
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

CHAINS	
39.93	<p>Cor. is located 20 lks. W of sandstone outcrop on SW slope in scattered juniper trees.</p> <p>The center E 1/16 sec. cor. of sec. 17.</p>
19.885	<p>From the point for the S 1/16 sec. cor. of secs. 16 and 17.</p> <p>S. 88° 46' W., on the E and W center line of SE ¼ of sec. 17.</p> <p>The SE 1/16 sec. cor. of sec. 17.</p>
39.77	<p>The center S 1/16 sec. cor. of sec. 17.</p> <p>From the W 1/16 sec. cor. of sec. 17 only.</p> <p>N. 1° 04' W., on the N and S center line of the SW ¼ of sec. 17.</p> <p>20.16 Point for the SW 1/16 sec. cor. of sec. 17, at intersection with the E and W center line of the SW ¼.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the soft sandstone, and in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">SW 1/16 S 17 1980</p> <p>40.32 Cor. is located on sandstone spur, sloping N.</p> <p>The center W 1/16 sec. cor. of sec. 17.</p>
1.50	<p>From the center S 1/16 sec. cor. of sec. 17.</p> <p>S. 88° 46' W., on the E and W center line of the SW ¼ of sec. 17.</p> <p>Draw, drains N.</p> <p>19.665 The SW 1/16 sec. cor. of sec. 17.</p> <p>39.33 The S 1/16 sec. cor. of secs. 17 and 18.</p>
6.50	<p>From the center W 1/16 sec. cor. of sec. 17.</p> <p>N. 1° 04' W., on the N and S center line of the NW ¼ of sec. 17.</p> <p>Gravel road, bears E and W.</p> <p>20.16 Point for the NW 1/16 sec. cor. of sec. 17, at intersection with the E and W center line of the NW ¼.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S 17 1980</p>

Survey of the Subdivision of Section 17,
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

CHAINS	
	Set a 6 ft. pine post, alongside the iron post.
	Cor. is located on rolling land in sagebrush.
20.37	Four strand barb wire fence line, bears E and W, 17 lks. dist., thence N.
40.32	The point for the W 1/16 sec. cor. of secs. 8 and 17.
	From the center N 1/16 sec. cor. of sec. 17.
	S. 89° 20' W., on the E and W center line of the NW ¼ of sec. 17.
19.92	The NW 1/16 sec. cor. of sec. 17.
39.84	The point for the N 1/16 sec. cor. of secs. 17 and 18.
	General Description
	<p>The area surveyed and resurveyed within T. 3 S., R. 20 E., varies from mountainous in the N and S portion to gently rolling in the central portion. The elevation varies from 6500 ft. to 8300 ft. The valley portion consist of mostly pasture land, with some cultivated farms. The mountains on the N are covered with juniper tree growth and the mountains on the S with sagebrush, buck brush, oakbrush and broken patches of douglas fir and pine. Dry Fork Creek drains from the NW to the SE and is used for irrigation purposes throughout the valley.</p>

CERTIFICATE OF SURVEY

(~~IXXX~~), Gail E. Reynolds, HEREBY
 CERTIFY upon honor that, in pursuance of special instructions bearing date of the 21st day
 of September, 1979, (I) (~~XXX~~) have dependently resurveyed a portion
 of the subdivisional lines and surveyed the subdivisions of sections
 8, 9, and 17 of Township 3 South, Range 20 East,

of the Salt Lake Meridian, in the State of Utah, which
 are represented in the foregoing field notes as having been executed by (me), (~~XXX~~) and under (my)
 (~~XXX~~) direction; and that said survey has been made in strict conformity with said special instruc-
 tions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in
 specific manner described in the foregoing field notes.

January 25, 1982
 (Date)

Gail E. Reynolds
 (Cadastral Surveyor)
 Supervisory

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
 Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the subdivisional
 lines and the survey of the subdivisions of section 8, 9, and 17 of
 Township 3 South, Range 20 East, Salt Lake Meridian, Utah

executed by Gail E. Reynolds, Supervisory Cadastral Surveyor
 having been critically examined and found correct, are hereby approved.

MAR 31 1982
 (Date)

Mary S. Speight
 ACTING (Chief, Cadastral Survey Examination and Approval Staff)

~~CERTIFICATE OF TRANSCRIPT~~

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in
 is a true copy of the original field notes.

(Date)

(Chief, Cadastral Survey Examination and Approval Staff)

