Form 9600-9
(December 1979)
(formerly 9180-6)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

R606

01

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

A PORTION OF THE SUBDIVISIONAL LINES

WITH A SUBDIVISIONAL SURVEY OF SECTION 27,

TOWNSHIP 37 SOUTH, RANGE 22 EAST

Of the Salt Lake Meridian,

In the State of Utah.

EXECUTED BY

Gary L. Kratz Supervisory Cadastral Surveyor

Under special instructions dated April 6, 19 83, approved April 8, 1983,

_____, which provided for the surveys included under U.S. Survey/Group

Number 629, and assignment instructions dated April 8, 19 83.

Survey commenced April 12, 19 83

Survey completed April 16, 19 83

Form 9600-9
(December 1979)
(formerly 9180-6)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

R606

01

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

A PORTION OF THE SUBDIVISIONAL LINES

WITH A SUBDIVISIONAL SURVEY OF SECTION 27,

TOWNSHIP 37 SOUTH, RANGE 22 EAST

Of the Salt Lake Meridian,

In the State of Utah.

EXECUTED BY

Gary L. Kratz Supervisory Cadastral Surveyor

Under special instructions dated April 6, 19 83, approved April 8, 1983,

_____, which provided for the surveys included under U.S. Survey/Group

Number 629, and assignment instructions dated April 8, 19 83.

Survey commenced April 12, 19 83

Survey completed April 16, 19 83

02

INDEX DIAGRAM

Township 37 South, Range 22 East,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21 5	22 4	23	24
30	29	28 3	27 1 2	26	25
31	32	33	34	35	36

Subdivision of Section 27 - Page 5

Township 37 South, Range 22 East, Salt Lake Meridian, Utah

CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, with a subdivisional survey of section 27, Township 37 South, Range 22 East, Salt Lake Meridian, Utah.

The subdivisional lines were surveyed by U.S. Deputy Surveyor Andrew P. Hanson in 1907.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated April 6, 1983.

The directions of the lines were determined by azimuth taken from U.S.C. & G.S. triangulation station "TROY". The lines were carried forward by sustained angulation throughout the progress of the survey.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the ¼ sec. cor. of secs. 26 and 27, was determined from a tie made to U.S.C. & G.S. triangulation station "TROY", located in the NE portion of sec. 27, is as follows:

Latitude 37° 32' 27.98" N. Longitude 109° 28' 30.97" W.

The mean magnetic declination is 13° E.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 37 S., R. 22 E., Salt Lake Meridian, Utah

---

(Restoring the Survey Executed by Andrew P. Hanson in 1907)

Beginning at the ¼ sec. cor. of secs. 26 and 27, monumented with a broken sandstone, 13 x 6 x 5 ins., firmly set 8 ins. in the ground, surrounded by a collar of stone, faintly mkd. ¼ on W face.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, surrounded by a collar of stone, with aluminum cap mkd.

T 37 S R 22 E
¼
S 27 | S 26
1983

Bury the mkd. stone alongside the aluminum post.

N. 0° 13' E., bet. secs. 26 and 27.

04

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 37 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
	Over rolling land.
41.63	The cor. of secs. 22, 23, 26, and 27, monumented with a sandstone, 20 x 6 x 6 ins., firmly set 8 ins. in the ground, mkd. 2 grooves on E face and 2 notches on S edge. At the corner point Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, surrounded by a collar of stone, with aluminum cap mkd. T 37 S R 22 E S 22 | S 23 S 27 | S 26 1983 Bury the mkd. stone alongside the aluminum post. From this cor., U.S.C. & G.S. triangulation station "TROY", bears S. 11° 56' W., 11.147 chs. dist., monumented with a standard brass tablet, firmly set in a concrete post, 8 ins. square, flush with the ground, with brass cap mkd. TROY 1966.
	From the ¼ sec. cor. of secs. 27 and 34, monumented with a sandstone, 16 x 12 x 7 ins., firmly set 6 ins. in the ground, surrounded by a collar of stone, mkd. ¼ on N face. At the corner point Set an aluminum post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, surrounded by a mound of stone, 4 ft. base, to top of aluminum cap, mkd. T 37 S R 22 E ¼ S 27 S 34 1983 Incorporate mkd. stone in mound. S. 89° 20' W., bet. secs. 27 and 34. Over rolling land.
9.80	Corral Creek, drains S.
19.81	Point for the W 1/16 sec. cor. of secs. 27 and 34. Set an aluminum post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, surrounded by a mound of stone, 5 ft. base, to top of aluminum cap, mkd. T 37 S R 22 E W 1/16 S 27 S 34 1983 Cor. is located 8 lks. E of a wash, that drains N.
39.62	The cor. of secs. 27, 28, 33, and 34, determined latitudinally by the projection of a fence line that extends W and longitudinally by the intersection of the center line of U.S. Highway No. 163, that bears N and S.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	At the corner point Set a railroad spike flush with the surface of U.S. Highway No. 163 from which An aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, for a reference monument, bears N. 45° E., 100 lks. dist., with aluminum cap, mkd. RM T37S R22E S27 66 FT 1983, and an arrow pointing to the cor. An aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, for a reference monument, bears S. 45° E., 100 lks. dist., mkd. RM T37S R22E S34 66 FT 1983, and an arrow pointing to the cor.
	N. 0° 10' E., bet. secs. 27 and 28. Thence along U.S. Highway No. 163.
22.50	U.S. Highway No. 163, on curve, bears NNE and S.
26.145	Intersect fence line, bears NNE and SSW. Point for witness point to secs. 27 and 28. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. W P S 28 | S 27 1983 Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
40.07	Point for the ¼ sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 37 S R 22 E ¼ S 28 | S 27 1983 Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
60.105	Point for the N 1/16 sec. cor. of secs. 27 and 28. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 37 S R 22 E N 1/16 S 28 | S 27 1983

CHAINS

Raise a mound of stone, 3 ft. base, 1½ ft. high and set a steel fence post, W of cor.

From this cor., a ½ in. rebar, firmly set projecting 4 ins. above the ground, surrounded by a collar of stone, with aluminum cap, mkd. ENERGY FUELS .3. bears N. 10° 43' E., 23 lks. dist.

80.14 Point for the cor. of secs. 21, 22, 27, and 28, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 37 S R 22 E
S 21 | S 22
S 28 | S 27
1983

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

From this cor., a rebar, ½ in. diam., firmly set in a collar of stone, bears N. 24° 57' E., 76 lks. dist., with aluminum cap mkd.

21 | 22
28 | 27

This position was not accepted as the cor. because of improper methods used to establish this position.

From this same cor., a fence bearing E and W, bears North, 40.07 chs. dist.; this fence was used to control the latitudinal proportioned distance only.

From the cor. of secs. 22, 23, 26, and 27.

S. 87° 29' W., bet. secs. 22 and 27.

Over rolling land.

40.14 The ¼ sec. cor. of secs. 22 and 27, monumented with a sandstone, 24 x 18 x 8 ins., set on a rock ledge, surrounded by a mound of stone, mkd. ¼ on N face.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., over a cross (X) chiseled in solid rock, surrounded by a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 37 S R 22 E
¼ S 22
S 27
1983

Cor. falls 8 lks. E of Corral Creek on a rock ledge 6 ft. above the water.

Incorporate mkd. stone in mound.

☆U.S. Government Printing Office: 1980—778-251/292

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 37 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
	N. 89° 55' W., beginning new measurement.
	Over gently rolling land.
19.92	Point for the W 1/16 sec. cor. of secs. 22 and 27.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.
	T 37 S R 22 E W 1/16 S 22 / S 27 1983
27.90	Center of U.S. Highway No. 163, bears N. 12° E. and S. 12° W.
39.84	The cor. of secs. 21, 22, 27, and 28.
	S. 89° 44' W., bet. secs. 21 and 28.
	Over gently rolling land.
40.05	The ¼ sec. cor. of secs. 21 and 28, monumented with a sandstone, 17 x 10 x 6 ins., firmly set 12 ins. in the ground, faintly mkd. ¼ on N face.
	At the corner point
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T 37 S R 22 E ¼ S 21 / S 28 1983
	Bury the mkd. stone alongside the aluminum post.
	Raise a mound of stone, 3 ft. base, 1½ ft. high, N of cor.
	Survey of the Subdivision of Section 27, T. 37 S., R. 22 E., Salt Lake Meridian, Utah
	From the ¼ sec. cor. of secs. 27 and 34.
	N. 0° 20' E., on the N-S center line of sec. 27.
39.67	Point for the center ¼ sec. cor. of sec. 27, at intersection with the E and W center line.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T 37 S R 22 E C ¼ S 27 1983
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

CHAINS	
59.64	Point for the N 1/16 sec. cor. on the N-S center line of sec. 27. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. C N 1/16 | S 27 C 1983 Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.
79.61	The ¼ sec. cor. of secs. 22 and 27.
	From the ¼ sec. cor. of secs. 26 and 27. S. 89° 54' W., on the E-W center line of sec. 27.
40.18	The center ¼ sec. cor. of sec. 27.
50.70	Corral Creek, drains S.
60.045	Point for the center W 1/16 sec. cor. of sec. 27. Set an aluminum post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock, surrounded by a mound of stone, 4 ft. base, to top of aluminum cap, mkd. W 1/16 C ——— C S 27 1983
76.30	Center of U.S. Highway No. 163, bears N. 12° E. and S. 12° W.
76.996	Intersect the line between the witness point on the W. bdy. of sec. 27, hereinbefore described, and the witness point on the E-W center line of the NW¼, hereinafter described. Intersection point not monumented. From the point of intersection, the witness point on the W. bdy. of sec. 27, bears S. 11° 58' 30" W., 14.24 chs. dist.
79.91	The ¼ sec. cor. of secs. 27 and 28.
	From the W 1/16 sec. cor. of secs. 27 and 34. N. 0° 15' E., on the N-S center line of the SW¼ of sec. 27.
39.87	The center W 1/16 sec. cor. of sec. 27.
	From the center W 1/16 sec. cor. of sec. 27. N. 0° 15' E., on the N-S center line of the NW¼ of sec. 27.
20.00	Point for the NW 1/16 sec. cor. of sec. 27.

☆U.S. Government Printing Office: 1980—778-251/292

Survey of the Subdivision of Section 27,
T. 37 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. NW 1/16 S 27 1983 Raise a mound of stone, 2 ft. base, 1 ft. high, and set a steel fence post, W of cor.
40.00	The W 1/16 sec. cor. of secs. 22 and 27.
	From the center N 1/16 sec. cor. of sec. 27.
	West, on the E-W center line of the NW¼ of sec. 27.
4.60	Corral Creek, drains SSW.
19.895	The NW 1/16 sec. cor. of sec. 27.
32.01	Center of U.S. Highway No. 163, bears N. 12° E. and S. 12° W.
32.685	Point for the witness point on the E-W center line of the NW¼ of sec. 27. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. W P S 27 1983 Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor. From this cor., the witness point bet. secs. 27 and 28, bears S. 11° 58' 30" W., 34.715 chs. dist., hereinbefore described.
39.79	The N 1/16 sec. cor. of secs. 27 and 28.

General Description

The area surveyed lies about 5 miles south of Blanding, Utah, in rolling to gently rolling terrain at an elevation of about 5600 ft. above sea level.

Vegetation consists mainly of junipers, cottonwood, sagebrush and grasses. Corral Creek drains southerly through section 27.

U.S. Highway 163 crosses the area from north to south.

There are no permanent residents in section 27.

The mean magnetic declination was transcribed from a recent isometric chart.

Form 9600-11
(August 1979)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Richard A. Zaninovich	Supervisory Cadastral Surveyor
Gregg Ostergaard	Survey Aid

CERTIFICATE OF SURVEY

(I) (~~WE~~), Gary L. Kratz, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 6th day of April, 1983, (I) (~~WE~~) have dependently resurveyed a portion of the subdivisional lines with a subdivisional survey of section 27, T. 37 S., R. 22 E.,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), (~~US~~) and under (my) (~~OUR~~) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

May 4, 1983 (Date) — Gary L. Kratz (Cadastral Surveyor) Supervisory

(Date) — (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines with a subdivisional survey of section 27, T. 37 S., R. 22 E., Salt Lake Meridian, Utah

executed by Gary L. Kratz, Supervisory Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

May 13, 1983 (Date) — Glen B. Hatch (~~Cadastral Survey Examiner and Approving Officer~~) Chief Cadastral Surveyor for Utah

~~CERTIFICATE OF TRANSCRIPT~~

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____ is a true copy of the original field notes.

(Date) — ~~Cadastral Survey Examiner and Approving Officer~~ Chief Cadastral Surveyor for Utah

Form 9600–9
(December 1979)
(formerly 9180–6)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
ORIGINAL

R606

12

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

A PORTION OF THE EAST BOUNDARY

AND

THE SUBDIVISIONAL LINES

AND THE SURVEY OF THE SUBDIVISION OF SECTIONS 12, 13 AND 25

OF

TOWNSHIP 36 SOUTH, RANGE 22 EAST

Of the Salt Lake Meridian,

In the State of Utah.

EXECUTED BY

Jerry L. Thomas Supervisory Cadastral Surveyor

Under special instructions dated September 25, 1978, approved September 26, 1978,

_____, which provided for the surveys included under U.S. Survey/Group Number 582, and assignment instructions dated September 25, 1978.

Survey commenced October 3, 1978

Survey completed June 14, 1979

INDEX DIAGRAM

Township 36 South, Range 22 East,

6	5	4	3 24	2 18	1 14
7	8	9 23	10 18 22	11 13 17	12 6 12
18	17	16 22	15 17 21	14 10 16	13 4 10
19	20	21 20	22 15 19	23 9	24 3 8
30	29	28	27	26 8	25 1 7
31	32	33	34	35	36

Subdivision of Section 12 - Page 25
Subdivision of Section 13 - Page 27
Subdivision of Section 25 - Page 29

GPO 855-927

Township 36 South, Range 22 East, Salt Lake Meridian, Utah

CHAINS

The east boundary (Colorado Guide Meridian) was surveyed by Ferdinand Dickert in 1878. In 1907, Andrew P. Hanson resurveyed the east boundary and surveyed the south boundary and a portion of the subdivisional lines. A portion of the north boundary (Seventh Standard Parallel South), was surveyed by Melvin D. Heist and Eben B. Andrews in 1911, and a portion surveyed by Joseph C. Thoma in 1912. The east boundaries of sections 1 and 12 were retraced, a portion of the subdivisional lines were surveyed and a portion retraced by Daniel B. Miller and Joseph C. Thoma in 1912. A portion of the subdivisional lines were resurveyed by Robert C. Yundt in 1939.

The following field notes are those of the dependent resurvey of a portion of the east boundary, a portion of the subdivisional lines and the survey of the subdivision of sections 12, 13 and 25 of T. 36 S., R. 22 E., Salt Lake Meridian, Utah.

The survey was executed in accordance with specificiations set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 582, Utah, dated September 25, 1978.

Preliminary to the resurvey the lines of the original survey were retraced and a search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The direction of lines were determined by solar instrument methods and by means of fore- and backsights and angular deflections from azimuths obtained by direct solar and Polaris observations.

The geographic position of the southeast corner of sec. 25 as determined by a tie to the United States Coast and Geodetic Survey triangulation station "Blanding" located in section 22, is as follows:

Latitude 37° 37' 14.4" N. Longitude 109° 26' 19.6' W.

The mean magnetic declination is 13° 30' E.

Dependent Resurvey of a Portion of the E. Bdy., (Colorado Guide Meridian), T. 36 S., R. 22 E., Salt Lake Meridian, Utah

---

(Restoring the 1878 Survey by Ferdinand Dickert and the 1907 Resurvey by Andrew P. Hanson)

Beginning at the cor. of secs. 25, 30, 31, and 36, monumented with a quartzite, 24 x 14 x 5 ins., dimly mkd. 3 notches on N edge, firmly set in a mound of stone, from which the remains of the original 1907 bearing trees

A cedar, 16 ins. diam., bears N. 36½° E., 82 lks. dist., mkd. T36S R23E S30 BT. (Record, 74 lks.)

15

Dependent Resurvey of a Portion of the E. Bdy., (Colorado Guide Meridian), T. 36 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS

A cedar, 12 ins. diam., bears S. 58° E., 17 lks. dist., mkd. T36S R23E S31 BT. (Record, S. 3° 05' E., 16 lks.)

A stump hole of fallen cedar, bears N. 73° W., 46 lks. dist., cedar mkd. T36S R22E S25 BT. (Record, N. 69° 30' W., 47 lks.)

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., over cross (X) chiseled in solid sandstone, and in a mound of stone, 5 ft. base, to top of brass cap, mkd.

T 36 S
R 22 E | R 23 E
S 25 | S 30
S 36 | S 31
1978

Deposit the mkd. stone alongside the iron post.

Cor. is located 15 lks. W of stream bed, drains SE.

N. 0° 16' W., bet. secs. 25 and 30.

Over broken land, along bottom of draw.

0.20 Stream bed, 150 lks. wide, drains SE; asc. over broken SW slope.

19.85 Point for the S 1/16 sec. cor. of secs. 25 and 30.

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd.

T 36 S
R 22 E | R 23 E
S 1/16
S 25 | S 30
1978

Cor. is located on E edge of small wash, draining SE.

39.70 The ¼ sec. cor. of secs. 25 and 30, monumented with a sandstone, 17 x 8 x 6 ins., mkd. ¼ on W face, firmly set 10 ins. in the ground, from which the 1907 bearing trees

A cedar, 8 ins. diam., bears S. 34° E., 30 lks. dist., mkd. ¼ S30 BT.

A cedar, 12 ins. diam., bears N. 21° W., 35 lks. dist., mkd. ¼ S25 BT. (Record, N. 16° 00' W., 33 lks. dist.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS

T 36 S
R 22 E | R 23 E
¼
S 25 | S 30
1978

Deposit the mkd. stone alongside the iron post.

Raise a mound of stone, 3½ ft. base, 1½ ft. high, W of cor.

N. 0° 02' E., beginning new measurement.

Over broken bench land.

39.88 The cor. of secs. 19, 24, 25, and 30, monumented with a sandstone, 26 x 16 x 6 ins., mkd. 4 notches on N and 2 notches on S edge, firmly set in a mound of stone, from which the 1907 bearing trees

A cedar, 20 ins. diam., bears N. 46° E., 29 lks. dist., mkd. T36S R23E S19 BT.

A cedar, 6 ins. diam., bears S. 50° E., 10 lks. dist., mkd. T36S R23E S30 BT.

A pinon, 12 ins. diam., bears S. 66° W., 34 lks. dist., mkd. T36S R22E S25 BT.

A cedar, 14 ins. diam., bears N. 16½° W., 17 lks. dist., mkd. T36S R22E S24 BT.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., over cross (X) chiseled in solid sandstone, and in a mound of stone, 4½ ft. base, to top of brass cap, mkd.

T 36 S
R 22 E | R 23 E
S 24 | S 19
S 25 | S 30
1978

Deposit the mkd. stone alongside the iron post.

Cor. is located on sandstone rim, bears NW and SE.

N. 0° 13' E., bet. secs. 19 and 24.

Along broken rim of "Recapture Wash."

39.91 The ¼ sec. cor. of secs. 19 and 24, monumented with a porphyry stone, 18 x 12 x 6 ins., mkd. ¼ on W face, firmly set 9 ins. in the ground, from which the remains of the 1907 bearing trees

A cedar, 12 ins. diam., bears S. 83° E., 24 lks. dist., mkd. ¼ S19 BT.

A fallen pinon, 12 ins. diam., bears S. 57° W., 50 lks. dist., mkd. ¼ S24 BT.

17

Dependent Resurvey of a Portion of the E. Bdy., (Colorado Guide Meridian), T. 36 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 36 S
R 22 E | R 23 E
¼
S 24 | S 19
1978

Deposit the mkd. stone alongside the iron post.

Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of the iron post.

Cor. is located on NW slope, 95 lks. N of small spur, sloping E.

N. 0° 09' W., beginning new measurement.

Over broken E slope.

39.93 The cor. of secs. 13, 18, 19, and 24, monumented with a sandstone, 18 x 12 x 4 ins., mkd. 3 notches on the N and S edges, firmly set, 6 ins. in the ground, from which the 1907 bearing trees

A cedar, 8 ins. diam., bears N. 14° E., 22 lks. dist., mkd. T36S R22E S18 BT.

A cedar, 8 ins. diam., bears S. 85° E., 32 lks. dist., mkd. T36S R23E S19 BT.

A fallen pinon, 4 ins. diam., bears S. 63° W., 46 lks. dist., mkd. T36S R22E S24 BT.

A cedar, 10 ins. diam., bears N. 32° W., 32 lks. dist., mkd. T36S R22E S13 BT.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 4½ ft. base, to top of brass cap, mkd.

T 36 S
R 22 E | R 23 E
S 13 | S 18
S 24 | S 19
1978

Deposit the mkd. stone alongside the iron post.

Cor. is located on NE slope.

N. 0° 07' W., bet. secs. 13 and 18.

Along broken E slope of "Recapture Wash."

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
39.87	The ¼ sec. cor. of secs. 13 and 18, determined from the remains of the 1907 bearing tree A cedar, 8 ins. diam., bears S. 45° E., 10 lks. dist., mkd. ¼ S18 BT. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, to top of brass cap, mkd. T 36 S R 22 E R 23 E ¼ S 13 | S 18 1978 Cor. is located on left bank of canal.
	N. 0° 41' E., beginning new measurement. Along broken E slope.
0.49	Canal, 25 lks. wide, course S. 10° E.
22.00	Power line, bears N. 42° E. and S. 42° W.
40.10	The cor. of secs. 7, 12, 13, and 18, monumented with a sandstone, 24 x 10 x 6 ins., mkd. 4 notches on S and 2 notches on N edge, from which the 1907 bearing trees A cedar stump, 12 ins. diam., bears S. 33° E., 28 lks. dist., dimly mkd. A cedar, 10 ins. diam., bears S. 55½° W., 44 lks. dist., mkd. T36S R22E S13 BT. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, to top of brass cap, mkd. T 36 S R 22 E R 23 E S 12 | S 7 S 13 | S 18 1978 Deposit the mkd. stone alongside the iron post.
	(Reestablishment of the Survey Executed by Ferdinand Dickert, Deputy Surveyor in 1878, the Resurvey Executed by Andrew P. Hanson, Deputy Surveyor in 1907, and the Retracement Executed by Daniel B. Miller and Joseph C. Thoma, Deputy Surveyors, in 1912)

19

Dependent Resurvey of a Portion of the E. Bdy., (Colorado Guide Meridian), T. 36 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
	N. 0° 14' W., bet. secs. 7 and 12.
	Over bottom of "Recapture Creek."
9.50	Bottom of "Recapture Creek," 150 lks. wide, drains NE.
20.50	U.S. Highway No. 163, bears E and W; asc. over SW slope.
40.11	The ¼ sec. cor. of secs. 7 and 12, monumented with a sandstone, 20 x 13 x 6 ins., mkd. ¼ on W face, firmly set 12 ins. in the ground, from which the 1907 bearing trees
	A cedar, 14 ins. diam., bears S. 2° E., 30 lks. dist., mkd. ¼ S7 BT.
	A cedar, 14 ins. diam., bears N. 17° W., 8½ lks. dist., mkd. ¼ S12 BT.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, to top of brass cap, mkd.

T 36 S
R 22 E R 23 E
¼
S 12 | S 7
1978

Deposit the mkd. stone alongside the iron post.

	N. 0° 13' W., beginning new measurement.
	Over broken bench land.
40.00	The cor. of secs. 1, 6, 7, and 12, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above a mound of stone, with brass cap mkd.

T 36 S
R 22 E R 23 E
S 1 | S 6
S 12 | S 7
1939

from which the bearing trees mkd. in 1907

A juniper, 16 ins. diam., bears N. 45½° E., 28 lks. dist., mkd. T36S R23E S6 BT.

A juniper, 10 ins. diam., bears S. 14° E., 11 lks. dist., mkd. T36S R23E S7 BT.

A juniper, 6 ins. diam., bears S. 89° W., 21 lks. dist., mkd. T36S R22E S12 BT.

A juniper, 3 ins. diam., bears N. 24° W., 5 lks. dist., mkd. BT.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	Dependent Resurvey of a Portion of the Subdivisional Lines, T. 36 S., R. 22 E., Salt Lake Meridian, Utah
	(Reestablishment of the Survey Executed by Andrew P. Hanson, Deputy Surveyor, in 1907)
	From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp.
	N. 88° 07' W., bet. secs. 25 and 36.
	Asc. over NE slope of draw.
20.07	Point for the E 1/16 sec. cor. of secs. 25 and 36.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	E 1/16 S 25 / S 36
	1978
	Set a cedar post, 5 ft. long, ½ lk. S of iron post.
	Over gentle rolling land.
40.14	The ¼ sec. cor. of secs. 25 and 36, monumented with a sandstone, 14 x 8 x 6 ins., mkd. ¼ on N face, firmly set 10 ins. in the ground, from which the original bearing tree
	A cedar, 14 ins. diam., bears N. 69½° W., 18½ lks. dist., mkd. ¼ S25 BT. (Record, 12 lks.)
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 36 S R 22 E ¼ S 25 / S 36 1978
	Deposit the mkd. stone alongside the iron post.
	Cor. is located on E edge of barn yard and 30 lks. N of dirt road.
	S. 89° 06' W., beginning new measurement.
0.54	Power line, bears N. 30° E. and S. 30° W.
40.02	The cor. of secs. 25, 26, 35, and 36, monumented with a local aluminum disc imbedded in concrete, accepted as the best available evidence of the original corner position, with aluminum disc mkd.
	RLS 4946 T 36 S R 22 E S 26 | S 25 S 35 | S 36

CHAINS	
	Cor. is set by cor. of fences bearing N and E and in line with fences extending W and S.
	N. 0° 15' W., bet. secs. 25 and 26.
	Over nearly level farm land.
40.32	The ¼ sec. cor. of secs. 25 and 26, monumented with a sandstone, 17 x 8 x 4 ins., mkd. ¼ on W face, firmly set 10 ins. in the ground.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 36 S R 22 E ¼ S 26 | S 25 1978
	Deposit the mkd. stone alongside the iron post.
	Cor. is set alongside cor. post of fences extending S and W, and row of fence posts extending N.
	N. 0° 03' E., beginning new measurement.
	Along bottom of draw, drains SE.
1.10	Dam of stock pond.
39.87	The cor. of secs. 23, 24, 25, and 26, monumented with a sandstone, 15 x 12 x 4 ins., mkd. 2 notches on S edge and 1 notch on E edge, firmly set 10 ins. in the ground, from which the remains of the original bearing tree
	A cedar, 16 ins. diam., bears S. 72½° W., 21 lks. dist., mkd. T36S R22E S26 BT.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 36 S R 22 E S 23 | S 24 S 26 | S 25 1978
	Deposit the mkd. stone alongside the iron post.
	From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp.
	N. 88° 39' W., bet. secs. 24 and 25.
	Over broken bench land.

☆U.S. Government Printing Office: 1980—778-251/292

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 36 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
40.19	The ¼ sec. cor. of secs. 24 and 25, determined from the remains of the original bearing tree The stump hole of a downed pinon, 4 ins. diam., bears N. 15° E., 34 lks. dist., the tree mkd. ¼ S24 BT on an open blaze. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T 36 S R 22 E ¼ S 24 / S 25 1978 N. 89° 30' W., beginning new measurement. Over broken land.
39.91	The cor. of secs. 23, 24, 25, and 26.
	N. 0° 13' W., bet. secs. 23 and 24. Over rolling land.
32.70	Paved road, bears W and curves NE.
40.22	The ¼ sec. cor. of secs. 23 and 24, monumented with a sandstone, 18 x 12 x 4 ins., mkd. ¼ on W face, firmly set 8 ins. in the ground. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 36 S R 22 E ¼ S 23 | S 24 1978 Deposit the mkd. stone alongside the iron post. Cor. is set alongside cor. post of fences extending N, S and W. N. 0° 34' E., beginning new measurement. Over rolling land.
10.00	Power line, bears N. 42° E. and S. 42° W.
40.25	The cor. of secs. 13, 14, 23, and 24, monumented with a sandstone, 21 x 8 x 4 ins., mkd. 3 notches on S edge and 1 notch on E edge. At the corner point

23

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 36 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 36 S R 22 E S 14 | S 13 S 23 | S 24 1978 Deposit the mkd. stone alongside the iron post. Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor. Cor. is set in fence line extending N and S.
	From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp. N. 87° 46' W., bet. secs. 13 and 24. Over broken land.
39.86	The ¼ sec. cor. of secs. 13 and 24, monumented with a sandstone, 24 x 10 x 8 ins., mkd. ¼ on N face, firmly set 14 ins. in the ground, from which the original bearing trees A pinon, 8 ins. diam., bears N. 30° E., 5½ lks. dist., mkd. ¼ S13 BT. (Record, N. 16° E.) A juniper, 12 ins. diam., bears S. 39° W., 53½ lks. dist., mkd. ¼ S24 BT. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 36 S R 22 E ¼ S 13 S 24 1978 Deposit the mkd. stone alongside the iron post.
	N. 89° 28' W., beginning new measurement. Over rolling land.
13.50	Power line, bears N. 42° E. and S. 42° W.
40.06	The cor. of secs. 13, 14, 23, and 24.
	N. 0° 20' E., bet. secs. 13 and 14. Over rolling land; along W edge of gravel road.
29.00	U.S. Highway No. 163, bears N. 23° E. and S. 23° W.
46.12	Center of old dirt road (Monticello to Grayson), bears N. 21° E. and S. 21° W.

☆U.S. Government Printing Office: 1980—778-251/292

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 36 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
50.06	The ¼ sec. cor. of secs. 13 and 14, monumented with a sandstone, 14 x 9 x 4 ins., mkd. ¼ on W face, firmly set 8 ins. in the ground, from which the original bearing trees A cedar, 14 ins. diam., bears West, 14½ lks. dist., mkd. ¼ S14 BT. (Record, 35 lks. dist.) A cedar, 8 ins. diam., bears S. 57½° E., 35 lks. dist., mkd. ¼ S13 BT. (Record, 15 lks. dist.) At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 36 S R 22 E ¼ S 14 | S 13 1978 Deposit the mkd. stone alongside the iron post. Raise a mound of stone, 2½ ft. base, 1½ ft. high. W of cor.
	N. 0° 14' E., beginning new measurement. Over rolling land.
20.15	Point for the North 1/16 sec. cor. of secs. 13 and 14. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. N 1/16 S 14 | S 13 1978 Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor. Cor. is located on gentle SW slope, 30 lks. E of fence line, bears N. 0° 42' E. and S. 0° 42' W.
40.30	The cor. of secs. 11, 12, 13, and 14, monumented with a sandstone, 15 x 8 x 6 ins., dimly mkd. and firmly set, 10 ins. in the ground. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 36 S R 22 E S 11 | S 12 S 14 | S 13 1978 Deposit the mkd. stone alongside the iron post.

CHAINS	
	Cor. is located on ridge top, in fence line, bears N. 0° 42' E. and S. 0° 42' W.
	From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp.
	N. 72° 54' W., bet. secs. 12 and 13.
	Over broken land; asc. over NE slope of "Recapture Wash."
19.00	Canal, 25 lks. wide, drains SE.
23.50	U.S. Highway No. 163, bears N and S.
41.51	The ¼ sec. cor. of secs. 12 and 13, monumented with a sandstone, 16 x 10 x 6 ins., mkd. ¼ on N face, firmly set 14 ins. in the ground, from which the remains of the original bearing trees
	The stump hole of a downed pinon, 8 ins. diam., bears S. 19½° E., 24 lks. dist., the tree mkd. ¼ S13 BT on an opened blaze.
	The opened blaze of a downed pinon, 6 ins. diam., bears N. 28° W., 17 lks. dist., mkd. ¼ S12 BT. (Record, N. 18° 40' W., 27 lks. dist.)
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 36 S R 22 E ¼ S 12 / S 13 1978
	Deposit the mkd. stone alongside the iron post.
	from which new bearing trees
	A juniper, 5 ins. diam., bears N. 20° E., 46½ lks. dist., mkd. ¼ S12 BT.
	A juniper, 8 ins. diam., bears S. 57½° W., 44 lks. dist., mkd. ¼ S13 BT.
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.
	Cor. is located on S slope, 113 lks. N of draw, drains E, and 88 lks. S of old bulldozed road, bears NE and SW.
	N. 89° 51' W., beginning new measurement.
	Asc. along S slope.
0.96	Old bulldozed road, bears NE and SW.
10.03	Point for the E-W 1/64 sec. cor. of secs. 12 and 13.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd. S 12 E-W 1/64 S 13 1979
20.06	Point for the W 1/16 sec. cor. of secs. 12 and 13. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. W 1/16 S 12 / S 13 1979 Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor
40.12	The cor. of secs. 11, 12, 13, and 14.
	N. 0° 06' E., bet. secs. 11 and 12. Over rolling ridge top.
2.00	Begin descent over N slope.
20.19	Point for the S 1/16 sec. cor. of secs. 11 and 12. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. S 1/16 S 11 | S 12 1979 Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor
40.38	The ¼ sec. cor. of secs. 11 and 12, monumented with a sandstone, 18 x 14 x 7 ins., mkd. ¼ on W face, firmly set, 9 ins. in the ground, from which the original bearing trees A cedar, 12 ins. diam., bears S. 52½° E., 47 lks. dist., mkd. ¼ S12 BT. (Record, pinon, S. 58¼° E., 32 lks. dist.) A pinon, 8 ins. diam., bears S. 15° W., 54 lks. dist., mkd. ¼ S11 BT. (Record, cedar, S. 36° W., 28 lks. dist.) At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 36 S R 22 E ¼ S 11 | S 12 1978

CHAINS	
	Deposit the mkd. stone alongside the iron post.
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.
	N. 0° 27' E., beginning new measurement.
	Desc. over N slope.
10.00	Canal, 25 lks. wide, drains SE.
14.50	"Recapture Creek," 20 lks. wide, 12 ins. deep, flows SE; asc. over SW slope.
39.91	The cor. of secs. 1, 2, 11, and 12, monumented with an iron post, 2 ins. diam., firmly set in a mound of stone, projecting 6 ins. above ground, with brass cap mkd. as described in the official record of the 1939 resurvey.
	(Reestablishment of the Survey Executed by Andrew P. Hanson, Deputy Surveyor in 1907, and the Resurvey by Robert C. Yundt in 1939)
	From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp.
	N. 73° 05' W., bet. secs. 1 and 12.
	Over rolling land.
17.00	Spur, slopes S.
20.52	Point for the E 1/16 sec. cor. of secs. 1 and 12, falls near the edge of a ledge, where it is unsafe to establish a permanent monument.
	At the corner point, chisel a cross (X) in solid sandstone, from which
	An iron post, 30 ins. long, 2½ ins. diam., set on solid sandstone, and in a mound of stone, 4 ft. base, to top of brass cap, for a reference monument, bears S. 73° E., 3.5 lks. dist., with brass cap mkd. E 1/16 S12 RM 1978 and an arrow pointing to the cor. point
41.04	The ¼ sec. cor. of secs. 1 and 12, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, with brass cap mkd.
	¼ S 1 / S 12 1939
	N. 89° 13' W., beginning new measurement.
	Over rolling land.
1.00	Gravel road, bears N and S.
1.80	Fence, bears N and S.

☆U.S. Government Printing Office: 1980—778-251/292

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 36 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
7.10	Fence, bears N and S.
8.00	Bull Dog Canyon, drains S.
11.20	Telephone line, bears N. 35° E. and S. 35° W.
19.935	Point for the W 1/16 sec. cor. of secs. 1 and 12, falls on edge of a sandstone boulder and is impossible to establish a permanent monument. At the corner point, chisel a cross (X) in solid sandstone boulder, from which An iron post, 30 ins. long, 2½ ins. diam., set 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, for a reference monument, bears S. 89° 13' E., 22 lks. dist., with brass cap mkd. RM W 1/16 S12 1978 and an arrow pointing to true cor. point.
26.30	Spur, slopes SE.
39.87	The cor. of secs. 1, 2, 11, and 12.

(Reestablishment of the Survey Executed by
Andrew P. Hanson, Deputy Surveyor in 1907)

CHAINS	
	From the cor. of secs. 22, 23, 26, and 27, monumented with a mound of stone. No mkd. stone found. This is accepted as the best available evidence of the position of the original corner. At the corner point (center of mound) Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 36 S R 22 E S 22 | S 23 S 27 | S 26 1978 Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor. Cor. is located 44 lks. W of center line of paved road, bears N and S. N. 0° 04' E., bet. secs. 22 and 23. Over gentle rolling land.
39.89	The ¼ sec. cor. of secs. 22 and 23, monumented with a sandstone, 17 x 14 x 5 ins., mkd. ¼ on W face, firmly set 17 ins. in the ground. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

CHAINS	
	T 36 S R 22 E ¼ S 22 | S 23 1978
	Deposit the mkd. stone alongside the iron post.
	Cor. is located in fence line, bearing E and W, and approximately 6.00 chs. W of paved road, bears N and S.
	N. 0° 03' W., beginning new measurement.
	Over gentle rolling land.
40.12	Point for the cor. of secs. 14, 15, 22, and 23, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 36 S R 22 E S 15 | S 14 S 22 | S 23 1978
	Set a red aluminum post, 5 ft. long, alongside the iron post.
	This cor. is located in cultivated land, 9.72 chs. W of paved road, bears N and S.
	From the cor. of secs. 13, 14, 23, and 24.
	S. 89° 50' W., bet. secs. 14 and 23.
	Over rolling land.
10.50	U.S. Highway No. 163, bears S. 20° W. and N. 20° E.
39.86	Point for the ¼ sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 36 S R 22 E S 14 ¼ S 23 1978
	Cor. is located on N edge of cultivated land.
	Set a red aluminum post, 5 ft. long, alongside the iron post.
70.00	Center line of paved road, bears N and S.
79.72	The cor. of secs. 14, 15, 22, and 23.

☆U.S. Government Printing Office: 1980—778-251/292

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 36 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS

N. 0° 01' E., bet. secs. 14 and 15.

Over gentle rolling land.

40.12 The ¼ sec. cor. of secs. 14 and 15, determined from the remains of the original bearing tree

A dead cedar, 4 ins. diam., bears S. 37½° W., 8 lks. dist., mkd. ¼ S15 BT.

There is no remaining evidence of the other bearing tree.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 36 S R 22 E
¼
S 15 | S 14
1978

from which

The SW cor. of barn, bears N. 43° W., 6.12 chs. dist.

Cor. is located 2 lks. N of fence, bears E and W.

N. 0° 01' E., beginning new measurement.

Over gentle rolling land.

40.11 Point for the cor. of secs. 10, 11, 14, and 15, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 36 S R 22 E
S 10 | S 11
S 15 | S 14
1978

Set a red aluminum post, 5 ft. long, alongside the iron post.

From the cor. of secs. 11, 12, 13, and 14.

S. 82° 38' W., bet. secs. 11 and 14.

Over rolling land

40.42 Point for the ¼ sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

CHAINS	
	T 36 S R 22 E ¼ S 11 / S 14 1978
	Set a cedar post, 5 ft. long, alongside the iron post.
	Cor. is located in grassy area, 75 lks. N of wash, drains SW.
69.00	Paved road, bears NNW and SSE.
80.84	The cor. of secs. 10, 11, 14, and 15.
	N. 0° 12' W., bet. secs. 10 and 11.
	Over rolling land.
39.17	Point selected for the witness ¼ sec. cor. of secs. 10 and 11.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	W C T 36 S R 22 E ¼ S 10 | S 11 1978
	Set a red aluminum post, 5 ft. long, alongside the iron post.
	Cor. is located on dam of stock pond.
40.11	True point for the ¼ sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original corner. The cor. point falls in middle of stock pond and is impossible to perpetuate.
43.20	Fence line, bears E and W.
55.00	Paved road, bears NNW and SSE.
80.22	The cor. of secs. 2, 3, 10, and 11, monumented with an iron post, 2 ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the official record of the 1939 resurvey.
	(Reestablishment of the Survey Executed by Andrew P. Hanson, Deputy Surveyor in 1907 and the Resurvey Executed by Robert C. Yundt in 1939)
	From the cor. of secs. 1, 2, 11, and 12, hereinbefore described.
	S. 82° 38' W., bet. secs. 2 and 11.
	Over rolling land.
19.90	Point selected for the witness E 1/16 sec. cor. of secs. 2 and 11.

☆U.S. Government Printing Office: 1980—778-251/292

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 36 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. E 1/16 < W C / S 2 / S 11 / 1978
20.34	True point for the E 1/16 sec. cor. of secs. 2 and 11, falls in stream bed of "Recapture Creek," flowing SE, and is impossible to establish a permanent monument.
40.68	The ¼ sec. cor. of secs. 2 and 11, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, with brass cap mkd. as described in the official record of the 1939 resurvey.
	S. 82 42' W., beginning new measurement.
	Over rolling land.
29.30	Ridge, bears NW and SE.
40.82	The cor. of secs. 2, 3, 10, and 11.
	From the cor. of secs. 22, 23, 26, and 27.
	N. 89° 47' W., bet. secs. 22 and 27.
	Over gentle rolling land.
40.01	The ¼ sec. cor. of secs. 22 and 27, monumented with a large spike in center of the south bound lane of paved road, bearing N and S. This spike appears to be of local origin, has been used by many private surveyors, and is accepted as the best available evidence of the original corner position. from which An iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, for a reference monument, bears S. 51° W., 46.1 lks. dist., with brass cap mkd. T36S R22E RM ¼ S27 1978, and an arrow pointing to the cor. An iron post, 30 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 56° W., 43.9 lks. dist., with brass cap mkd. T36S R22E RM ¼ S22 1978, and an arrow pointing to the cor.
	N. 89° 47' W., beginning new measurement.
34.50	Westwater Creek, drains S.
40.01	The cor. of secs. 21, 22, 27, and 28, monumented with a sandstone, 16 x 7 x 5 ins., mkd. 3 notches on E and S edges, firmly set 10 ins. in the ground, from which the original bearing tree A pinon, 10 ins. diam., bears S. 60° E., 23 lks. dist., mkd. T36S R22E S27 BT.

CHAINS

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd.

T 36 S R 22 E
S 21 | S 22
S 28 | S 27
1978

Deposit the mkd. stone alongside the iron post.

N. 0° 12' W., bet. secs. 21 and 22.

Over broken land; asc. over SE slope.

40.20 The ¼ sec. cor. of secs. 21 and 22, monumented with a sandstone, 16 x 12 x 4 ins., mkd. ¼ on W face, firmly set 10 ins. in the ground. There is no remaining evidence of the original bearing trees.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 36 S R 22 E
¼
S 21 | S 22
1978

Deposit the mkd. stone alongside the iron post and raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.

From this cor., United States Coast and Geodetic Survey triangulation station "BLANDING," bears S. 89° 33' E., 41.155 chs. dist., monumented with a standard brass tablet, firmly set in concrete, with brass cap mkd. BLANDING 1949-1954.

Cor. is located 11 lks. E of dirt road, bearing N and S.

N. 0° 12' E., beginning new measurement.

Along broken E slope of "Westwater Creek."

10.00 "Westwater Creek," 15 lks. wide, drains S. 25° E.; thence along creek bottom.

15.00 Same creek, drains SW.

23.25 Same creek, drains S. 20° E.

40.13 The cor. of secs. 15, 16, 21, and 22, monumented with a sandstone, 17 x 12 x 4 ins., no visible markings, firmly set 8 ins. in the ground and in a collar of stone, from which the original bearing trees

A pinon, 16 ins. diam., bears N. 62° E., 51½ lks. dist., mkd. T36S R22E S15 BT.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	A pinon, 18 ins. diam., bears S. 65° E., 58 lks. dist., mkd. T36S R22E S22 BT. A pinon stump, 16 ins. diam., bears S. 55° W., 79 lks. dist., mkd. T36S R22E S21 BT. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 4½ ft. base, to top of brass cap, mkd. T 36 S R 22 E S 16 | S 15 S 21 | S 22 1978 Deposit the unmkd. stone alongside the iron post.
	From the cor. of secs. 14, 15, 22, and 23. N. 89° 33' W., bet. secs. 15 and 22. Over gentle rolling land.
20.01	Point for the E 1/16 sec. cor. of secs. 15 and 22. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. E 1/16 S 15 / S 22 1978 Set a red aluminum post, 5 ft. long, alongside the iron post. from which A cor. of fences, extending S and W, bears S. 24° W., 34½ lks. dist.
40.02	Point for the ¼ sec. cor. of secs. 15 and 22, at proportionate distance, falls in paved county road which bears WNE and SE; there is no remaining evidence of the original corner. Drive a spike flush with surface of the road. from which An iron post, 30 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 34½° W., 85 lks. dist., with brass cap mkd. T36S R22E ¼ S22 RM 1978 and an arrow pointing to the cor. An iron post, 30 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 42¼° W., 79½ lks. dist., with brass cap mkd. T36S R22E ¼ S15 RM 1978 and an arrow pointing to the cor.
80.04	The cor. of secs. 15, 16, 21, and 22.

CHAINS

(Reestablishment of the Survey Executed by Andrew P. Hanson, Deputy Surveyor in 1907, and the Retracement by D.B. Miller and J.C. Thoma in 1912)

N. 1° 14' W., bet. secs. 15 and 16.

Over rolling land; asc. over S slope.

40.22 The ¼ sec. cor. of secs. 15 and 16, determined from the remains of the original bearing tree

A pinon, 12 ins. diam., bears S. 43½° W., 21 lks. dist., mkd. ¼ S16 BT.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 36 S R 22 E
¼
S 16 | S 15
1978

Set a cedar post, 5 ft. long, alongside the iron post.

N. 0° 47' E., beginning new measurement.

Asc. over SW slope.

39.92 Point for the cor. of secs. 9, 10, 15, and 16, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 36 S R 22 E
S 9 | S 10
S 16 | S 15
1978

Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor

From this point, the ¼ sec. cor. of secs. 9 and 16, bears S. 89° 41' W., 39.83 chs. dist., monumented with an iron post, 1 in. diam., firmly set with brass cap mkd. as described in the field notes of the resurvey of a portion of the subdivisional lines in 1912.

(Reestablishment of the Survey Executed by Andrew P. Hanson, Deputy Surveyor in 1907)

From the cor. of secs. 10, 11, 14, and 15.

N. 89° 24' W., bet. secs. 10 and 15.

Over rolling land.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
40.24	The ¼ sec. cor. of secs. 10 and 15, monumented with a sandstone, 20 x 12 x 6 ins., mkd. ¼ on N face, firmly set 10 ins. in the ground. There is no remaining evidence of the original bearing trees. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 36 S R 22 E ¼ S 10 / S 15 1978 Deposit the mkd. stone alongside the iron post. Set a cedar post, 5 ft. long, 1 lk. N of iron post. from this corner A cor. of fences, extending S. 37° E. and N. 59° E., bears S. 84° E., 1.67 chs. dist.
	N. 89° 51' W., beginning new measurement. Over rolling land.
4.00	Paved road, bears NW and SE.
20.07	Point for the W 1/16 sec. cor. of secs. 10 and 15. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. W 1/16 S 10 / S 15 1978 from which A steel rod by cor. of fence extending N and E, bears N. 47½° W., 22½ lks. dist. Cor. is located on gentle W slope near top of ridge, bears N and S.
40.14	The cor. of secs. 9, 10, 15, and 16.
	N. 0° 19' W., bet. secs. 9 and 10. Over rolling land.
39.88	The ¼ sec. cor. of secs. 9 and 10, monumented with an unmkd. wooden stake, 2 ins. square, projecting 8 ins. above ground at cor. of fences extending N and W. This position is harmoniously related to existing original cors., and is accepted as the best available evidence of the original corner position. The remains of the original bearing tree is dead and fallen over. At the corner point

37

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 36 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 36 S R 22 E ¼ S 9 | S 10 1978
	N. 0° 38' W., beginning new measurement.
	Asc. over SW slope.
39.62	The cor. of secs. 3, 4, 9, and 10, determined from the remains of the original bearing tree A pinon, 6 ins. diam., bears S. 84½° W., 34 lks. dist., mkd. T36S R22E S9 BT on open blaze.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 3½ ft. base, to top of brass cap, mkd. T 36 S R 22 E S 4 | S 3 S 9 | S 10 1978
	Cor. is located on E slope, 52 lks. W of dirt road, bears S and curves NW.
	(Reestablishment of the Survey Executed by Andrew P. Hanson, Deputy Surveyor in 1907, and the Retracement by D.B. Miller and J.C. Thoma in 1912)
	From the cor. of secs. 2, 3, 10, and 11.
	N. 89° 58' W., bet. secs. 3 and 10.
	Over rolling land.
8.00	Paved road, bears NNW and SSE.
20.09	Point for the E 1/16 sec. cor. of secs. 3 and 10.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. E 1/16 S 3 / S 10 1978
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.
40.18	The ¼ sec. cor. of secs. 3 and 10, monumented with a sandstone, 16 x 8 x 5 ins., mkd. ¼ on N face, firmly set 8 ins. in the ground, from which the remains of the original bearing tree

☆U.S. Government Printing Office: 1980—778-251/292

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 36 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
	A cedar, 12 ins. diam., bears N. 77½° W., 15 lks. dist., mkd. ¼ S3 BT. (Record, N. 31° 29' E., 26 lks. dist.)
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 36 S R 22 E ¼ S 3 / S 10 1978
	Deposit the mkd. stone alongside the iron post.
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor
	S. 89° 43' W., beginning new measurement.
	Over rolling land.
40.08	Dirt road, bears S and curves NW; fence line projects W.
40.60	The cor. of secs. 3, 4, 9, and 10.
	Subdivision of Section 12, T. 36 S., R. 22 E., Salt Lake Meridian, Utah
	From the ¼ sec. cor. of secs. 12 and 13.
	N. 0° 04' E., on the N and S center line of sec. 12.
	Asc. over S slope
6.15	Top of ridge, bears NW and SE; desc. over NE slope.
17.07	Point for the center-south 1/16 sec. cor. of sec. 12.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	C S 1/16 | S 12 C 1979
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor
17.87	Canal, 25 lks. wide, course SE.
25.50	"Recapture Creek," 25 lks. wide, flows SE.
34.14	Point for the center ¼ sec. cor. of sec. 12, at the intersection with the E-W center line of sec. 12.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

39

Subdivision of Section 12,
T. 36 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
	T 36 S R 22 E. C¼ S 12 1979
	Set a red aluminum post, 5 ft. long, alongside the corner.
44.00	Gravel road, bears NW and SE.
79.84	The ¼ sec. cor. of secs. 1 and 12.
	From the ¼ sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp.
	N. 81° 01' W., on the E and W center line of sec. 12.
	Over rolling land.
34.00	Gravel road, bears NW and curves SE.
39.96	The center ¼ sec. cor. of sec. 12.
46.00	Bull Dog Canyon, drains S.
52.00	"Recapture Creek," 25 lks. wide, flows SE.
60.27	Point for the center-west 1/16 sec. cor. of sec. 12.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 4½ ft. base, to top of aluminum cap, mkd. W 1/16 C S 12 C 1979
68.00	Canal, 25 lks. wide, course SE.
80.58	The ¼ sec. cor. of secs. 11 and 12.
	From the west 1/16 sec. cor. of secs. 12 and 13.
	N. 0° 06' E., on the N and S center line of the SW¼ of sec. 12.
	Over rolling land.
18.625	Point for the SW 1/16 sec. cor. of sec. 12, at the intersection with the E-W center line of the SW¼ of sec. 12.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. SW 1/16 S 12 1979
32.50	Canal, 25 lks. wide, course SE.
37.25	The center-west 1/16 sec. cor. of sec. 12.

☆U.S. Government Printing Office: 1980—778-251/292

Subdivision of Section 12,
T. 36 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
	From the center-south 1/16 sec. cor. of sec. 12.
	N. 85° 24' W., on the E and W center line of the SW¼ of sec. 12.
	Asc. over NE slope.
20.12	The southwest 1/16 sec. cor. of sec. 12.
40.24	The south 1/16 sec. cor. of secs. 11 and 12.

Subdivision of Section 13,
T. 36 S., R. 22 E., Salt Lake Meridian, Utah

	From the ¼ sec. cor. of secs. 13 and 24.
	N. 0° 21' E., on the N and S center line of sec. 13.
	Over rolling land.
15.50	Power line, bears N. 42° E. and S. 42° W.
44.32	Point for the center ¼ sec. cor. of sec. 13, at the intersection with the E-W center line of sec. 13.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 36 S R 22 E C¼ S 13 1979
	Set a red aluminum post, 5 ft. long, alongside the iron post.
67.21	U.S. Highway No. 163, bears E and W.
67.47	Point for the center-north 1/16 sec. cor. of sec. 13.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with aluminum cap mkd. C N 1/16 | S 13 C 1979
74.12	Center of old dirt road (Monticello to Grayson), bears E and W.
79.045	Point for the center-north-north 1/64 sec. cor. of sec. 13.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. S 13 C-N-N 1/64 1979

41

Subdivision of Section 13,
T. 36 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor
90.62	The ¼ sec. cor. of secs. 12 and 13.
	From the ¼ sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp.
	N. 81° 20' W., on the E and W center line of sec. 13.
	Over rolling land.
0.42	Canal, 25 lks. wide, course S. 10° E.
17.00	Power line, bears N. 42° E. and S. 42° W.
39.94	The center ¼ sec. cor. of sec. 13.
60.19	Point for the center-west 1/16 sec. cor. of sec. 13.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	W 1/16 C ——— C S 13 1979
	Set a red aluminum post, 5 ft. long, alongside the aluminum post.
72.41	U.S. Highway No. 163, bears N. 22° E. and S. 22° W.
76.32	Center of old dirt road (Monticello to Grayson, bears NE and SW.
80.44	The ¼ sec. cor. of secs. 13 and 14.
	From the center-west 1/16 sec. cor. of sec. 13.
	N. 0° 18' E., on the N and S center line of the NW¼ sec. cor. of sec. 13.
19.42	U.S. Highway No. 163, curves N. 63° E. and S. 63° W.
21.22	Right of way fence, curves S. 31° W. and N. 31° E.
21.65	Point for the northwest 1/16 sec. cor. of sec. 13, at the intersection with the E-W center line of the NW¼ of sec. 13.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	NW 1/16 S 13 1979
	from which
	Tower of Radio Station "KUTA," bears N. 44½° W., 4.91 chs. dist.

☆U.S. Government Printing Office: 1980—778-251/292

Subdivision of Section 12,
T. 36 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
32.475	Point for the center-north-northwest 1/64 sec. cor. of sec. 13. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. 1/64 C-N-NW S 13 1979 Set a red aluminum post, 5 ft. long, alongside the aluminum post.
43.30	The west 1/16 sec. cor. of secs. 12 and 13.
	From the center-north 1/16 sec. cor. of sec. 13. N. 85° 34' W., on the E and W center line of the NW¼ sec. cor. of sec. 13.
0.62	U.S. Highway No. 163, bears N. 68° W. and S. 68° E.
10.00	Dirt road, bears N and curves E.
10.055	Point for the center-east-northwest 1/64 sec. cor. of sec. 13. Bury an aluminum post, 30 ins. long, 2½ ins. diam., 6 ins. below surface of dirt road, from which An aluminum post, 30 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 26° W., 75½ lks. dist., with aluminum cap mkd. C-E-NW 1/64 S13 RM 49.8 FT 1979 and an arrow pointing to the cor.
15.93	U.S. Highway No. 163, curves E and SW.
20.11	The northwest 1/16 sec. cor. of sec. 13.
40.22	The north 1/16 sec. cor. of secs. 13 and 14.
	From the center-east-northwest 1/64 sec. cor. of sec. 13. N. 0° 19' E., on the N and S center line of the NE¼ of the NW¼ of sec. 13.
1.38	U.S. Highway No. 163, bears E and W.
22.40	The east-west 1/64 sec. cor. of secs. 12 and 13.
	Subdivision of Section 25, T. 36 S., R. 22 E., Salt Lake Meridian, Utah
	From the ¼ sec. cor. of secs. 25 and 36. N. 0° 10' W., on the N and S center line of sec. 25.

43

Subdivision of Section 25,
T. 36 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
0.94	Power line, bears N. 30° E. and S. 30° W.
19.52	Point for the center-south 1/16 sec. cor. of sec. 25.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. C S 1/16 | S 25 C 1978
	Set a cedar post, 5 ft. long, alongside the iron post.
39.04	Point for the center ¼ sec. cor. of sec. 25, at the intersection with the E-W center line of sec. 25.
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 3½ ft. base, to top of brass cap, mkd. T 36 S R 22 E C¼ S 25 1978
	Cor. is located 10 lks. S of small wash, drains NE.
79.22	The ¼ sec. cor. of secs. 24 and 25.
	From the ¼ sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp.
	N. 89° 04' W., on the E and W center line of sec. 25.
20.02	Point for the center-east 1/16 sec. cor. of sec. 25.
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base, to top of brass cap, mkd. E 1/16 C ——— C S 25 1978
40.04	The center ¼ sec. cor. of sec. 25.
79.00	Creek, drains SE.
80.15	The ¼ sec. cor. of secs. 25 and 26.
	From the E 1/16 sec. cor. of secs. 25 and 36.
	N. 0° 13' W., on the N and S center line of the SE¼ of sec. 25.
19.69	Point for the southeast 1/16 sec. cor. of sec. 25, at the intersection with the E-W center line of the SE¼ of sec. 25.

☆U.S. Government Printing Office: 1980—778-251/292

Subdivision of Section 25,
T. 36 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. SE 1/16 S 25 1978 Cor. is located on W bank of main draw, drains SE.
39.38	The center-east 1/16 sec. cor. of sec. 25.
	From the S 1/16 sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp. N. 88° 36' W., on the E and W center line of the SE¼ of sec. 25.
20.04	The southeast 1/16 sec. cor. of sec. 25.
40.08	The center-south 1/16 sec. cor. of sec. 25.
	General Description Township 36 South, Range 22 East, is situated in and around Blanding, Utah. The elevation varies from 5950 to 6600 feet above sea level. The soil is mostly loam with several sandstone outcroppings along the "Recapture Wash" area. "Recapture Creek" crosses the northeast corner of the township. There are several small stock ponds scattered over most of the area surveyed. There are 3 gravel pit operations, one each, in sections 13, 15 and 24, and an oil well located in section 25. The principal users of this portion of the township are farmers and stockmen. The U.S. Highway No. 163, enters the township through the east boundary of section 12 and exits through the south boundary of section 34. Further access to the township is provided by numerous secondary roads.

Form 9600–11
(August 1979)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Donald A. Buhler	Surveying Technician
Brian Seibold	Surveying Technician
Donzil Worthington	Surveying Technician

46

CERTIFICATE OF SURVEY

(I) ~~XXX~~, Jerry L. Thomas, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 25th day of September, 1978, (I) ~~XXX~~ have dependently resurveyed a portion of the east boundary, a portion of the subdivisional lines, and surveyed the subdivision of sections 12, 13, and 25 of Township 36 South, Range 22 East,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), ~~XXX~~ and under (my) ~~XXX~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

May 25, 1983 (Date)

Jerry L. Thomas (Cadastral Surveyor)
Supervisory

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the east boundary, a portion of the subdivisional lines and the survey of the subdivision of sections 12, 13, and 25 of Township 36 South, Range 22 East, Salt Lake Meridian, Utah

executed by Jerry L. Thomas, Supervisory Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

June 10, 1983 (Date)

Glen B Hatch
~~(Chief, Cadastral Survey, Examining and Approval Staff)~~
Chief Cadastral Surveyor for Utah

~~CERTIFICATE OF TRANSCRIPT~~

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in , is a true copy of the original field notes.

(Date)

~~(Chief, Cadastral Survey, Examining and Approval Staff)~~
Chief Cadastral Surveyor for Utah

Form 9600–9
(December 1979)
(formerly 9180–6)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

R606

47

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF A

PORTION OF THE SUBDIVISIONAL LINES,

A PORTION OF SECTIONS 37, 38 and 39,

AND

THE SURVEY OF THE SUBDIVISION OF CERTAIN SECTIONS

AND TRACT 40

OF

TOWNSHIP 5 SOUTH, RANGE 3 EAST

Of the Salt Lake Meridian,

In the State of Utah.

EXECUTED BY

Donald A. Buhler Supervisory Cadastral Surveyor

Ray Harpin Cadastral Surveyor

Under special instructions dated August 11, 19 69, approved August 15, 1969,

, which provided for the surveys included under U.S. Survey/Group

Number 513, and assignment instructions dated August 11, 19 69.

and October 10, 1979

Survey commenced August 11, 19 69

Survey completed June 25, 19 82

INDEX DIAGRAM

Township 5 South, Range 3 East,

6	5	4	3	2	1
7	8	9	10	11	12 10
18	17	16	15	14 9	13 8
19	20	21	22	23 7	24 6
30	29	28	27 13	26 5 11	25 2
31	32	33 13	34 12	35 1	36

Section 37 - Page 14
Section 38 - Page 15
Section 39 - Page 19

Subdivision of Sec. 13 - Page 24
Subdivision of Sec. 36 - Page 26

GPO 855-927

CHAINS

The following field notes describe the dependent resurvey of a portion of the subdivisional lines and a portion of sections 37, 38 and 39, and the survey of certain sections and Tract 40 of Township 5 South, Range 3 East, Salt Lake Meridian, Utah.

A portion of the subdivisional lines were surveyed by Scott P. and John R. Stewart in 1900. Sections 37, 38 and 39 were also surveyed by Scott P. and John R. Stewart in 1900. Certain corners were remonumented in 1970 by Ferrel D. Reynolds under the remonumentation cooperative agreement between the U.S. Forest Service and the BLM.

The resurvey was executed in accordance with the specifications set forth in the Manuals of Surveying Instructions, 1947 and 1973, and the Special Instructions for Group 513, Utah, dated August 11, 1969.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The direction of lines were determined by solar and Polaris observations and were carried forward by sustained angulation.

The geographic position of the southeast cor. of sec. 36, on the east boundary of the township, as calculated from a tie to U.S. Geological Survey station "Hobble" in sec. 35, T. 5 S., R. 4 E., is as follows:

Latitude 40° 20' 02.4" N. Longitude 111° 32' 40.8" W.

The mean magnetic declination is 15° 30' E.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 5 S., R. 3 E., Salt Lake Meridian, Utah

---

(Restoring the 1900 Survey by Scott P. and John R. Stewart)

Beginning at the cor. of secs. 25, 26, 35, and 36, monumented with a blue limestone, 14 x 8 x 6 ins., mkd. 1 notch on S edge and 1 notch on E edge, firmly set in a mound of stone, 4 ft. base.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 5 S R 3 E
S 26 | S 25
S 35 | S 36
1971

Deposit the mkd. stone alongside the iron post.

S. 1° 13' W., bet. secs. 35 and 36.

CHAINS	
9.77	Point for the closing cor. of secs. 35 and 36, at the intersection of the S. bdy. of special section 38, at proportionate distance, hereinafter described. There is no remaining evidence of the original corner.
	S. 0° 13' E., beginning new measurement.
30.42	The ¼ sec. cor. of secs. 35 and 36, monumented with a limestone, 22 x 10 x 5 ins., mkd. ¼ on W face, firmly set 12 ins. in the ground, with a scattered mound of stone W of cor. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 2½ ft. base, to top of brass cap, mkd. T 5 S R 3 E ¼ S 35 | S 36 1971 from which A pine, 10 ins. diam., bears S. 68½° E., 41 lks. dist., mkd. ¼ S36 BT. A pine, 13 ins. diam., bears N. 72° W., 46 lks. dist., mkd. ¼ S35 BT. Deposit the mkd. stone alongside the iron post.
	S. 0° 15' E., beginning new measurement.
19.97	Point for the S 1/16 sec. cor. of secs. 35 and 36. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. S 1/16 S 35 | S 36 1971 from which A pine, 8 ins. diam., bears N. 85° E., 36 lks. dist., mkd. S 1/16 S36 BT. A pine, 3 ins. diam., bears N. 60° E., 4 lks. dist., mkd. X BT.
39.23	The closing cor. of secs. 35 and 36, on the First Standard Parallel South, set, mkd. and described in the concurrent resurvey of T. 6 s., R. 3 E.
	From the cor. of secs. 25, 26, 35, and 36.
	N. 89° 52' E., bet. secs. 25 and 36.
16.57	South Fork of Provo River, 15 lks. wide, 6 ins. deep, drains NW.

☆U.S. Government Printing Office: 1980—778-251/292

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 5 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
31.10	Center line of asphalt road, bears NW and SE.
33.16	Point for angle point No. 10 of section 38, hereinafter described.
40.03	The ¼ sec. cor. of secs. 25 and 36, monumented with an iron post, 2½ ins. diam., firmly set and projecting 8 ins. above the ground, and in a mound of stone, 2½ ft. base, to top of brass cap, mkd. as described in the official record of the 1970 remonumentation notes. A steel fence post is located along N side of iron post.
	S. 89° 49' E., beginning new measurement.
9.39	The closing cor. of secs. 25 and 36, on the W. bdy. of sec. 39, hereinafter described.
	N. 89° 47' E., beginning new measurement.
6.50	Asphalt road, bears ENE and WSW.
29.50	Asphalt road, bears NW and SE.
31.16	The closing cor. of secs. 25 and 36, on the E. bdy. of the Tp., as shown to me by Mr. Long, who knew the position of the stone which had been recently destroyed by dozing. This positions was verified by close proximity of measurements of the original record and is accepted as the position of the original corner. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 5 S R 3 E R 4 E C S 25 | C S 36 | S 30 1969 from which A maple, 17 ins. diam., bears N. 16½° W., 27 lks. dist., mkd. T5S R3E S25 CC BT. Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor. From this cor., the cor. of secs. 30 and 31, on the W. bdy. of T. 5 S., R. 4 E., identical with cor. No. 2 of the Private Land Claim Survey of Joshua J. Meacham, identical with sec. 39 in T. 5 S., R. 3 E., bears S. 0° 13' E., 1.70 chs. dist., set, mkd. and described in the concurrent resurvey of T. 5 S., R. 4 E. From this same cor., cor. No. 1 of the Private Land Claim Survey of Joshua J. Mecham, identical with sec. 39, on the E. bdy. of the Tp., bears N. 0° 13' W., 2.99 chs. dist., hereinafter described.

52

Dependent Resurvey of a Portion of the Subdivisional Lines
of T. 5 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS

Point for the ¼ sec. cor. of sec. 36 only, on the E. bdy. of the Tp., at proportionate distance.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 5 S |
¼ |
S 36 |
R 3 E |
1969

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

This cor. is located in a fence line, extending N and S.

From this cor., the ¼ sec. cor. of sec. 31 only, on the W. bdy. of T. 5 S., R. 4 E., bears S. 0° 13' E., 1.43 chs. dist., set, mkd. and described in the concurrent resurvey of the W. bdy. of T. 5 S., R. 4 E.

From this same cor., the N 1/16 sec. cor. of sec. 31 only, on the W. bdy. of T. 5 S., R. 4 E., bears N. 0° 13' W., 18.50 chs. dist., set, mkd. and described in the concurrent resurvey of the W. bdy. of T. 5 S., R. 4 E.

Point for the S 1/16 sec. cor. of sec. 36 only, on the E. bdy. of the Tp., at proportionate distance.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

S 1/16 |
S 36 |
1969

from which

A pine, 8 ins. diam., bears N. 86 3/4° E., 70 lks. dist., mkd. X BT.

Raise a mound of stone, 3 ft. base, 3 ft. high, NW of cor.

This cor. is located on steep E slope.

From this cor., the closing cor. of secs. 31 and 36, on the First Standard Parallel South bears S. 0° 12' E., 19.36 chs. dist., set, mkd. and described in the concurrent resurvey of the W. bdy. of T. 6 S., R. 3 E.

From this same cor., the ¼ sec. cor. of sec. 31 only, on the W. bdy. of T. 5 S., R. 4 E., bears N. 0° 12' W., 18.63 chs. dist., set, mkd. and described in the concurrent resurvey of the W. bdy. of T. 5 S., R. 4 E.

Point for the N 1/16 sec. cor. of sec. 36 only, on the E. bdy. of the Tp., at proportionate distance.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

N 1/16 |
S 36 |
1969

☆U.S. Government Printing Office: 1980—778-251/292

Dependent Resurvey of a Portion of the Subdivisional Lines
of T. 5 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
	Raise a mound of stone, 2½ ft. base, 2 ft. high, W of cor.
	This cor. is located on the western edge of a trail road, 10 ft. wide, extending N and S.
	From this cor., the N 1/16 sec. cor. of sec. 31 only, on the W. bdy. of T. 5 S., R. 4 E., bears S. 0° 13' E., 1.56 chs. dist., set, mkd. and described in the concurrent resurvey of the W. bdy. of T. 5 S., R. 4 E.
	From this same point, the cor. of secs. 30 and 31, on the W. bdy. of T. 5 S., R. 4 E., bears N. 0° 13' W., 18.37 chs. dist., set, mkd. and described in the concurrent resurvey of T. 5 S., R. 4 E.
	From the cor. of secs. 25, 26, 35, and 36.
	N. 0° 12' W., bet. secs. 25 and 26.
12.65	South Fork of Provo River, 20 lks wide, 6 ins. deep, drains NW.
14.00	Asphalt road, 25 lks. wide, bears SE and NW.
14.61	Angle point No. 8 of section 38, hereinafter described.
29.30	Angle point No. 7 of section 38, hereinafter described.
39.20	The ¼ sec. cor. of secs. 25 and 26, monumented with a sandstone, 16 x 9 x 5 ins., firmly set 12 ins. in the ground, mkd. ¼ on W face.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 5 S R 3 E ¼ S 26 | S 25 1971
	Deposit the mkd. stone alongside the iron post.
	Raise a mound of stone, 2½ ft. base, 2 ft. high, W of cor.
	This cor. is located on steep S slope in dense oak and maple.
	N. 0° 10' W., beginning new measurement.
25.00	Denver and Rio Grande Western Railroad, bears NE and SW.
26.00	Provo River, drains SW.
28.00	U.S. Highway No. 189, bears NE and SW.
40.05	The cor. of secs. 23, 24, 25, and 26, monumented with an iron post, 2 ins. diam., firmly set in a mound of stone, 3 ft. base, to top of brass cap, mkd.

54

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 5 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
	UTAH CO. LAND SURVEY T 5 S R 3 E 23 | 24 26 | 25 1977 This cor. is located on a steep SE slope in dense oak and maple and is accepted as a careful and faithful perpetuation of the position of the original corner.
	N. 89° 50' E., bet. secs. 24 and 25.
20.00	U.S Highway No. 189, bears NE and SW.
22.00	Provo River, drains SW.
24.00	Denver and Rio Grande Western Railroad, bears NE and SW.
39.80	Point for the ¼ sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a mound of stone, 3½ ft. base, to top of aluminum cap, mkd. T 5 S R 3 E ¼ S 24 S 25 1981 Cor. is located on steep NW slope in scattered oak and maple.
79.42	Point for the closing cor. of secs. 24 and 25, on the E. bdy. of the Tp., at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 21 ins. in the ground, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd. T 5 S R 3 E R 4 E C S 24 | S 19 C S 25 | 1981 Cor. is located on steep W slope in scattered oak and maple. From this cor., the cor. of secs. 19 and 30, on the W. bdy. of T. 5 S., R. 4 E., bears S. 1° 01' E., 3.76 chs. dist., set, mkd. and described in the concurrent resurvey of T. 5 S., R. 4 E. From this same cor., the ¼ sec. cor. of sec. 19 only, on the W. bdy. of T. 5 S., R. 4 E., bears N. 1° 01' W., 34.86 chs. dist., set, mkd. and described in the concurrent resurvey of the W. bdy. of T. 5 S., R. 4 E.
	Point for the ¼ sec. cor. of sec. 25 only, at midpoint on the E. bdy. of sec. 25.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, 2½ ft. base, to top of aluminum cap, mkd.

T 5 S
R 3 E R 4 E
¼ |
S 25 |
1981

Cor. is located on steep S slope in scattered oak and maple.

From this cor., the ¼ sec. cor. of sec. 30 only, on the W. bdy. of T. 5 S., R. 4 E., bears S. 1° 01' E., 2.73 chs. dist., set, mkd. and described in the concurrent resurvey of the W. bdy. of T. 5 S., R. 4 E.

From this same cor., the cor. of secs. 19 and 30, on the W. bdy. of T. 5 S., R. 4 E., bears N. 1° 01' W., 35.89 chs. dist., set, mkd. and described in the concurrent resurvey of the W. bdy. of T. 5 S., R. 4 E.

From the cor. of secs. 23, 24, 25, and 26.

N. 0° 01' W., bet. secs. 23 and 24.

39.74 The ¼ sec. cor. of secs. 23 and 24, monumented with a brass tablet, 3 ins. diam., firmly set in concrete 2 ins. below the ground, with brass cap mkd.

¼
23 | 24
T 5 S R 3 E

Cor. is located 33 lks. SW of centerline of Utah State Highway No. 80 and is accepted as a careful and faithful perpetuation of the position of the original corner.

N. 0° 32' W., beginning new measurement.

38.89 The cor. of secs. 13, 14, 23, and 24, monumented with a sandstone, 15 x 10 x 5 ins., set 10 ins. in the ground, in a scattered mound of stone, plainly mkd. 3 notches on S and 1 notch on E edges.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 5 S R 3 E
S 14 | S 13
S 23 | S 24
1982

from which

A pine, 23 ins. diam., bears S. 78° E., 46 lks. dist., mkd. X BT.

Deposit the mkd. stone alongside the iron post.

CHAINS	
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	N. 89° 05' E., bet. secs. 13 and 24.
19.90	Point for the W 1/16 sec. cor. of secs. 13 and 24.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap, mkd.
	T 5 S R 3 E W 1/16 S 13 / S 24 1982
	Cor. is located on E slope in thick aspen.
39.80	Point for the ¼ sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T 5 S R 3 E ¼ S 13 / S 24 1982
	from which
	An iron post, 30 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears S. 83° 01' E., 1.507 chs. dist., with brass cap, mkd. T5S R3E RM 99.45 FT S24 1982 and an arrow pointing to the corner.
	An iron post, 30 ins. long, 2½ ins. diam., set 24 ins. in the ground, and in a collar of stone for a reference monument, bears S. 35° 02' E., 1.685 chs. dist., with brass cap, mkd. T5S R3E 111.14 FT RM S24 1982 and an arrow pointing to the corner.
	Cor. is located on NW edge of U.S. Highway No. 189.
42.00	Denver and Rio Grande Western Railroad, bears N and S.
44.50	Provo River, drains S.
78.38	Point for the closing cor. of secs. 13 and 24, on the E. bdy. of the Tp., at proportionate distance; there is no remaining evidence of the original corner.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap, mkd.
	T 5 S R 3 E R 4 E C S 13 | S 18 C S 24 | 1981
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS

Cor. is located 4 lks. S of fence line, extending E and W.

From this cor., the cor. of secs. 18 and 19, on the W. bdy. of T. 5 S., R. 4 E., bears S. 1° 01' E., 6.17 chs. dist., set, mkd. and described in the concurrent resurvey of the W. bdy. of T. 5 S., R. 4 E.

From this same cor., the ¼ sec. cor. of sec. 18 only, on the W. bdy. of T. 5 S., R. 4 E., bears N. 1° 01' W., 32.45 chs. dist., set, mkd. and described in the concurrent resurvey of the W. bdy. of T. 5 S., R. 4 E.

Point for the ¼ sec. cor. of sec. 24 only, on the E. bdy. of the Tp., at midpoint on the E. bdy. of sec. 24.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.

T 5 S
R 3 E | R 4 E
¼ |
S 24 |
1981

Cor. is located on steep S slope in oak brush.

From this cor., the ¼ sec. cor. of sec. 19 only, on the W. bdy. of T. 5 S., R. 4 E., bears S. 1° 01' E., 4.97 chs. dist., set, mkd. and described in the concurrent resurvey of the W. bdy. of T. 5 S., R. 4 E.

From this same cor., the cor. of secs. 18 and 19, on the W. bdy. of T. 5 S., R. 4 E., bears N. 1° 01' W., 33.65 chs. dist., set, mkd. and described in the concurrent resurvey of the W. bdy. of T. 5 S., R. 4 E.

From the cor. of secs. 13, 14, 23, and 24.

N. 0° 27' W., bet. secs. 13 and 14.

39.89 The ¼ sec. cor. of secs. 13 and 14, monumented with a sandstone, 20 x 13 x 10 ins., plainly mkd. ¼ on W face and firmly set in a scattered mound of stone.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 5 S R 3 E
¼
|
S 14 | S 13
|
1982

Deposit the mkd. stone alongside the iron post.

Cor. is located on E slope in thick oak and maple.

58

Dependent Resurvey of a Portion of the Subdivisional Lines
of T. 5 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
	N. 0° 02' E., beginning new measurement.
40.23	The cor. of secs. 11, 12, 13, and 14, monumented with a limestone, 15 x 8 x 6 ins., plainly mkd. 4 notches on S edge and 1 notch on E edge, firmly set 7 ins. in the ground, in a scattered mound of stone. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T 5 S R 3 E S 11 | S 12 S 14 | S 13 1982 Deposit the mkd. stone alongside the iron post.
	N. 89° 27' E., bet. secs. 12 and 13.
19.98	Point for the W 1/16 sec. cor. of secs. 12 and 13. Set an aluminum post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a collar of stone, with brass cap mkd. T 5 S R 3 E W 1/16 S 12 / S 13 1982 Cor. is located on N edge of a clearing in oak and maple.
39.96	Point for the ¼ sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 5 S R 3 E ¼ S 12 / S 13 1982 Cor. is located on NE slope in thick undergrowth and maple.
57.59	Point for the closing cor. of secs. 12 and 13, at the intersection of the W. bdy. of sec. 37, hereinafter described.
	N. 89° 55' E., beginning new measurement.
2.21	Point for the E 1/16 sec. cor. of secs. 12 and 13, not monumented.
19.71	Point for the closing cor. of secs. 12 and 13, on the E. bdy. of the Tp., at proportionate distance; there is no remaining evidence of the original corner. Point falls in man made pond.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	Set a rebar, 18 ins. long, 3/4 ins. diam., 12 ins. in the ground. from which An aluminum post, 30 ins. long, 2½ ins. diam., set 28 ins. in the ground in the dam of the pond, for a reference monument, bears S. 4° 01' W., 1.29 chs. dist., with aluminum cap mkd. RM T5S R3E 85.20 FT S13 1981 and an arrow pointing to the cor. An aluminum post, 30 ins. long, 2½ ins. diam., set 24 ins. in the ground in a collar of stone, for a reference monument, bears N. 47° 07' W., 1.12 chs. dist., with aluminum cap mkd. RM T5S R3E 74.13 FT S12 1981 and an arrow pointing to the cor. From the cor. point, the cor. of secs. 7 and 18, on the E. bdy. of T. 5 S., R. 4 E., bears S. 0° 38' E., 8.85 chs. dist., set, mkd. and described in the concurrent resurvey of the W. bdy. of T. 5 S., R. 4 E. From this same cor. point, the ¼ sec. cor. of sec. 7 only, on the E. bdy. of T. 5 S., R. 4 E., bears N. 0° 38' W., 32.22 chs. dist., set, mkd. and described in the concurrent resurvey of the W. bdy. of T. 5 S., R. 4 E.
	Point for the ¼ sec. cor. of sec. 13 only, at mid point and on the E. bdy. of sec. 13. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 5 S R 3 E R 4 E ¼ | S 13 | 1981 Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor. From this cor., the ¼ sec. cor. of sec. 18 only, on the W. bdy. of T. 5 S., R. 4 E., bears S. 0° 58' E., 7.28 chs. dist., set, mkd. and described in the concurrent resurvey of the W. bdy. of T. 5 S., R. 4 E. From this same cor., cor. No. 1 of the Private Land Claim Survey of John W. Hoover, identical with sec. 37, bears N. 0° 58' W., 27.84 chs. dist., hereinafter described.
	From the cor. of secs. 25, 26, 35, and 36. S. 89° 55' W., bet. secs. 26 and 35.
39.67	Point for the ¼ sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a mound of stone, 2½ ft. base, to top of aluminum cap, mkd.

CHAINS

T 5 S R 3 E
¼ S 26
S 35
1982

from which

A pine, 20 ins. diam., bears N. 24° 17' E., 0.18 chs. dist., mkd. ¼ S26 BT.

Cor. is located on steep NE slope in thick pines.

79.34 The cor. of secs. 26, 27, 34, and 35, monumented with a blue limestone, 18 x 8 x 5 ins., plainly mkd. 1 notch on S edge and 2 notches on E edge, firmly set 10 ins. in the ground with scattered mound of stone, W of cor.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.

T 5 S R 3 E
S 27 | S 26
S 34 | S 35
1982

from which

A pine, 10 ins. diam., bears S. 73° W., 23.5 lks. dist., mkd. S34 BT.

Deposit the mkd. stone alongside the aluminum post.

Cor. is located on steep NW slope in scattered oak.

S. 0° 06' E., bet. secs. 34 and 35.

39.64 The ¼ sec. cor. of secs. 34 and 35, monumented with a quartzite stone, 20 x 8 x 6 ins., plainly mkd. ¼ on W face, with a scattered mound of stone, W of cor.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 5 S R 3 E
¼
S 34 | S 35
1982

Deposit the mkd. stone alongside the aluminum post.

Cor. is located on steep W slope in scattered oak.

S. 0° 06' W., beginning new measurement.

39.42 The closing cor. of secs. 34 and 35, on the First Standard Parallel South, set, mkd. and described in the concurrent resurvey of T. 6 S., R. 3 E.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	From this closing cor., the angle point bet. secs. 2 and 35 bears S. 89° 52' E., 3.17 chs. dist., described in the concurrent resurvey of T. 6 S., R. 3 E.
	From the cor. of secs. 26, 27, 34, and 35. S. 89° 50' W., bet. secs. 27 and 34.
23.50	Denver and Rio Grande Western Railroad, bears NE and SW.
27.00	Provo River, drains SW.
31.00	U.S. Highway No. 189, bears NE and SW.
39.71	Point for the ¼ sec. cor. of secs. 27 and 34, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd. T 5 S R 3 E ¼ S 27 / S 34 1982 Cor. is located on E and W trail road, 10 ft. wide, in the S track of road.
79.42	The cor. of secs. 27, 28, 33, and 34, monumented with an iron post, 2 ins. diam., projecting 6 ins. above the ground, and in a collar of stone, with brass cap mkd. as described in the official record of the 1940 resurvey.
	S. 0° 15' E., bet. secs. 33 and 34.
19.84	Point for the N 1/16 sec. cor. of secs. 33 and 34. Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd. N 1/16 S 33 | S 34 1971 Raise a mound of stone, 3½ ft. base, 3 ft. high, W of cor.
35.00	U.S. Highway No. 189, bears NE and SW.
37.50	Provo River, drains SW.
39.68	The ¼ sec. cor. of secs. 33 and 34, monumented with a brass tablet, 3 ins. diam., set in concrete with brass cap mkd. ¼ S 33 | S 34 1930 Cor. is located between the railroad tracks (Heber Creeper) on the S edge of the Provo River and is accepted as a careful and faithful perpetuation of the position of the original corner.

62

Dependent Resurvey of a Portion of the Subdivisional Lines
of T. 5 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS

S. 0° 33' W., beginning new measurement.

38.97 True point for the closing cor. of secs. 33 and 34, on the First Standard Parallel South, set, mkd. and described in the concurrent resurvey of T. 6 S., R. 3 E.

From this closing cor., the angle point bet. secs. 3 and 34 bears S. 89° 52' E., 2.55 chs. dist., described in the concurrent resurvey of T. 6 S., R. 3 E.

Dependent Resurvey of a Portion of a Private Land
Claim for John W. Hoover Identical with Section 37,
Located in Section 13,
T. 5 S., R. 3 E., Salt Lake Meridian, Utah

(Restoring the Survey Executed by
Scott P. and John R. Stewart in 1900)

From cor. No. 1 of the Private Land Claim survey of John W. Hoover, identical with section 37, and on the E. bdy. of the Tp., monumented with a limestone, 24 x 15 x 8 ins., plainly mkd. JWH.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

```
      T 5 S
R 3 E | R 4 E
S 13  |
------| S 18
COR1  |
 JWH  |
     1981
```

Deposit the mkd. stone alongside the aluminum post.

Cor. is located in dense undergrowth and scattered maple.

Thence N. 89° 32' W., along line 1 - 2 of section 37.

17.63 Point for the crossing closing cor. of the N and S center lines of the NE¼ of sec. 13, at intersection with the S. bdy. of section 37, hereinafter described.

19.96 Point for angle point No. 2 of the Private Land Claim survey of John W. Hoover identical with Special Section 37 at proportionate distance based on the Grant Boundary Method; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

```
T 5 S R 3 E
      | SS 37
S 13  | JWH
      | AP 2
     1982
```

Cor. is located 7 lks. W of fence, extending N and S.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS

Thence N. 0° 28' E., along line 2 - 3 of section 37.

11.70 Point for the closing corner of secs. 12 and 13, at the intersection of the W. bdy. of section 37, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 5 S R 3 E
S 12 C | SS 37
S 13 C | JWH
1982

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

19.96 The 1/2 mile post of the Private Land Claim survey of John W. Hoover identical with section 37, monumented with a limestone, 24 x 16 x 10 ins., plainly mkd. ½ M JWH on the E face, set 6 ins. in the ground with a scattered mound of stone E of cor.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 5 S R 3 E
S 12 | 1/2 M
| JWH
| SS 37
1982

Deposit the mkd. stone alongside the iron post.

Dependent Resurvey of a Portion of the Private Land Claim of George J. Duke, Identical with Section 38, which is Located in Sections 25, 26, 35, and 36, T. 5 S., R. 3 E., Salt Lake Meridian, Utah

---

From angle point No. 3 of the Private Land Claim survey of George J. Duke, identical with section 38, monumented with a quartzite stone, 18 x 12 x 6 ins., in a scattered mound of stone. This is accepted as the best available evidence of the original corner.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

T 5 S R 3 E
| SS 38
| AP 3
1971

from which

A pine, 18 ins. diam., bears South 22 lks. dist., mkd. X BT.

A pine, 22 ins. diam., bears S. 86 3/4° W., 25 lks. dist., mkd. X BT.

CHAINS	
	Deposit unmkd. stone in mound of stone.
	Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.
	Thence S. 89° 45' E., along line 2 - 3 of section 38.
10.60	Point for the closing cor. of secs. 35 and 36, at intersection with the S. bdy. of section 38, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 5 S R 3 E SS 38 S 35 | S 36 C|C 1971
	from which
	A fir, 16 ins. diam., bears N. 24½° E., 38 lks. lks. dist., mkd. X BT.
	A fir, 11 ins. diam., bears N. 62¼° W., 61 lks. dist., mkd. X BT.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	From this cor., the cor. of secs. 25, 26, 35, and 36, bears N. 1° 13' E., 9.77 chs. dist., hereinbefore described.
30.00	The 1/2 mile post for the Private Land Claim survey of George J. Dukes, identical with section 38, monumented with a quartzite stone, 20 x 12 x 6 ins., plainly mkd. ½ MGHD on N face and firmly set 14 ins. in the ground.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 5 S R 3 E 1/2 M SS 38 S 36 1971
	Deposit the mkd. stone in mound of stone alongside the iron post.
	Raise a mound of stone, 2½ ft. base, 2 ft. high, W of cor.
50.81	Intersect the N and S center line of sec. 36.
	From this intersection point, the ¼ sec. cor. of secs. 25 and 36, bears N. 0° 10' E., 10.04 chs. dist., hereinbefore described.
60.20	Angle point No. 2 of the Private Land Claim survey of George J. Dukes, identical with section 38, on the W. bdy. of section 39, monumented with a quartzite stone, 18 x 10 x 6 ins., plainly mkd. L2GJD on the N face, and firmly set 10 ins. in the ground in a mound of stone.

☆U.S. Government Printing Office: 1980 – 778-251/292

CHAINS	
	At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 5 S R 3 E S 38 | AP 2 | SS 39 S 36 | 1971 Deposit the mkd. stone in mound alongside the iron post. Raise a mound of stone, 2½ ft. base, 2 ft. high, NW of cor Cor. is located 13 lks. W of fence, extending N and S.
	Thence N. 0° 08' E., along line 1 - 2 of section 38, identical with line 8 - 9 of section 39.
4.00	South Fork of Provo River, drains W.
8.00	Asphalt road, bears E and W.
10.05	Cor. No. 1 of the Private Land Claim survey of George J. Duke, identical with section 38 on the W. bdy. of section 39, monumented with a quartzite stone, 20 x 10 x 8 ins., mkd. BEG COR GJD on W face and CC GHD on E face, firmly set 12 ins. in the ground in a scattered mound of stone. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 5 S R 3 E S 25 C C | SS 38 | SS 39 1971 Deposit the mkd. stone in mound alongside the iron post. Raise a mound of stone, 3 ft. base, 2½ ft. high, W of cor. Thence N. 89° 49' W., along line 1 - 10, section 38, identical with the S. bdy. of sec. 25.
9.39	The ¼ sec. cor. of secs. 25 and 36.
	S. 89° 52' W., beginning new measurement.
6.87	Point for angle point No. 10 of the Private Land Claim survey of George J. Duke, identical with section 38, monumented with a quartzite stone, 18 x 12 x 6 ins., plainly mkd. CC GJD on N face and L10GJD on S face, in a mound of stone. This cor. is located on a steep highway out bank and is impractical to monument.
	Thence N. 0° 35' W., along line 9 - 10 of section 38.

66

Dependent Resurvey of a Portion of the Private Land Claim of George J. Duke, Identical with Section 38, which is Located in Section 25, 26, 35, and 36, T. 5 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
0.14	Point selected for the witness cor. for angle point 10 of the Private Land Claim survey of George J. Duke, identical with section 38. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 5 S R 3 E | | S 25 AP 10 | S 36 SS 38 ↓ W C 1971 Deposit the mkd. stone in mound of stone alongside the iron post. Raise a mound of stone, 2 ft. base, 1 ft. high, W of cor.
14.88	Point for angle point No. 9 of the Private Land Claim survey of George J. Duke, identical with section 38, at proportionate distance based on the Grant Boundary method; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 5 S R 3 E S 25 AP 9 | SS 38 | 1971 Cor. is located on SW slope. Thence S. 89° 25' W., along line 8 - 9 of section 38.
27.56	Point for the 2 mile post of the Private Land Claim survey of George J. Duke, identical with section 38, at proportionate distance; there is no remaining evidence of the original corner. Not monumented.
33.05	Angle point No. 8 of the Private Land Claim survey of George J. Duke, identical with section 38 on the W. bdy. of sec. 25, monumented with a quartzite stone, 22 x 11 x 6 ins., mkd. L8GJD on the SW face and CC on the N face, firmly set 14 ins. in the ground in a scattered mound of stone. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. T 5 S R 3 E | S 25 SS 38 AP 8 1971 Deposit the mkd. stone in mound of stone alongside the iron post.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	Thence, N. 0° 12' W., bet. secs. 25 and 26, identical with line 7 - 8 of section 38.
14.69	Angle point No. 7 of the Private Land Claim survey of George J. Duke, identical with section 38, monumented with a quartzite stone, 18 x 9 x 7 ins., plainly mkd. L7GJD on S face and CC on N face, firmly set 10 ins. in the ground in a scattered mound of stone. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. T 5 S R 3 E S 26 | S 25 AP 7 | SS 38 | 1971 Deposit the mkd. stone in mound of stone alongside the iron post. Raise a mound of stone, 2½ ft. base, 2 ft. high, W of cor.

Dependent Resurvey of a Portion of the Private Land
Claim of Joshua J. Mecham, Identical with Section 39,
Located in Sections 25 and 36,
T. 5 S., R. 3 E., Salt Lake Meridian, Utah

	From angle point No. 3, identical with the one half mile cor. of the Private Land Claim survey of Joshua J. Mecham, identical with section 39, and on the E. bdy. of the Tp., monumented with a quartzite stone, 14 x 5 x 5 ins., mkd. JJM 3 on the NW face, firmly set 8 ins. in the ground and in a fence extending N and S. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 5 S R 3 E | SS 39 | AP 3 | S 31 S 36 | 1971 Deposit the mkd. stone alongside the iron post. Raise a mound of stone, 4 ft. base, 2 ft. high, W of cor. From this cor., the ¼ sec. cor. of sec. 36 only, bears S. 0° 13' E., 3.23 chs. dist., hereinbefore described. S. 89° 36' W., along line 3 - 4 of section 39.
4.96	Angle point No. 4 of the Private Land Claim survey of Joshua J. Mecham, identical with section 39, monumented with a quartzite stone, 18 x 14 x 6 ins., mkd. JJ M on E face, firmly set 4 ins. in the ground. At the corner point

CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

```
T 5 S R 3 E
   SS 39
AP 4
      | S 36
      |
    1971
```

Deposit the mkd. stone alongside the iron post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

Thence, S. 0° 26' E., along line 4 - 5 of sec. 39.

3.21 Intersect the E-W center line of sec. 36, at a point from which the ¼ sec. cor. of sec. 36 only on the E. bdy. of the Tp., bears N. 89° 50' E., 4.95 chs. dist., hereinbefore described.

19.71 Angle point No. 5 of the Private Land Claim survey of Joshua J. Mecham, identical with section 39, monumented with a quartzite stone, 18 x 10 x 6 ins., no visible marks, in a scattered mound of stone.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd.

```
T 5 S R 3 E
 SS 39 |
  AP 5 |
       S 36
     1971
```

Deposit the unmkd. stone alongside the iron post.

Cor. falls on a steep W slope in scattered spruce and dense oak brush.

Thence, S. 89° 25' W., along line 5 - 6 of sec. 39.

13.33 Angle point No. 6 of the Private Land Claim survey of Joshua J. Mecham, identical with section 39, monumented with a quartzite stone, 24 x 8 x 7 ins., mkd. 75 JJM (record, 65JM) on the N face, firmly set 14 ins. in the ground, with a scattered mound of stone N of cor.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

```
T 5 S R 3 E
      | SS 39
      | AP 6
S 36
    1971
```

Deposit the mkd. stone alongside the iron post.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	Thence, N. 0° 18' W., along line 6 - 7 of sec. 39.
1.46	The one mile cor. of the Private Land Claim survey of Joshua J. Mecham, identical with section 39, monumented with a quartzite stone, 18 x 16 x 8 ins., mkd. 1M JJM on E face, loosely set with a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.
15.55	Angle point 7 of the Private Land Claim survey of Joshua J. Mecham, identical with section 39, monumented with a quartzite stone, 20 x 12 x 6 ins., mkd. 677M (record, 7JJM), firmly set 13 ins. in the ground, with a flattened mound of stone, 3 ft. base, N of cor.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T 5 S R 3 E SS 39 AP 7 S 36 | 1971
	Deposit the mkd. stone alongside the iron post.
	Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.
	Thence, N. 89° 52' W., along line 7 - 8 of sec. 39.
2.68	Intersect the N-S center line of the SE¼ of section 36.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 5 S R 3 E SS 39 E S 36 | CC E 1971
	from which
	A maple, 3 ins. diam., bears N. 61° E., 18.5 lks. dist., mkd. X BT.
	A maple, 4 ins. diam., bears N. 64° E., 23 lks. dist., mkd. S36 CC BT.
	The SE 1/16 sec. cor. of sec. 36, bears S. 0° 08' W., 19.01 chs. dist., hereinafter described.
12.32	Angle point No. 8 of the Private Land Claim survey of Joshua J. Mecham, identical with section 39, monumented with a quartzite stone, 18 x 10 x 6 ins., mkd. JJM on N face, firmly set 14 ins. in the ground.
	This cor. also functions as Angle Point No. 4 of Tract 40.

Dependent Resurvey of a Portion of the Private Land
Claim of Joshua J. Mecham, Identical with Section 39,
Located in Sections 25 and 36,
T. 5 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.



Deposit the mkd. stone alongside the iron post.

Raise a mound of stone, 2½ ft. base, 2 ft. high, NE of cor.

from this corner

Angle point No. 1 of tract 40 on the E. bdy. of the Tp., bears N. 51° 34' E., 39.01 chs. dist.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.



Raise a mound of stone, 3 ft. base, 3 ft. high, W of cor.

This point is located in an old abandoned fence, extending N and S on the W edge of trail road.

From angle point No. 1 of Tract 40, the N 1/16 sec. cor. of sec. 36 only, bears S. 0° 13' E., 3.06 chs. dist., hereinbefore described.

Thence, N. 0° 21' W., along line 8 - 9 of section 39.

0.97 Intersect the E-W center line of section 36, at a point from which the center ¼ sec. cor. of sec. 36, bears S. 89° 50' W., 10.23 chs. dist., hereinafter described.

13.42 The one and one half mile post of the Private Land Claim survey of Joshua J. Mecham, identical with section 39, monumented with a quartzite stone, 18 x 10 x 8 ins., 1½M JJM on E face, firmly set 12 ins. in the ground, with a small scattered mound to the East.

This cor. is also designated as angle point 3 of tract 40.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	T 5 S R 3 E | TR 40 S 36 | AP 3 | 1971
	Deposit the mkd. stone alongside the iron post.
	Raise a mound of stone, 2½ ft. base, 2 ft. high, E of cor.
	Thence, N. 2° 16' W., beginning new measurement.
10.63	Point for Angle Point No. 2 of Tract 40.
	Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 2½ ft. base, to top of brass cap, mkd.
	T 5 S R 3 E | SS 39 S 36 | AP 2 | TR 40 1971
	From this cor., Angle Point No. 1 of Tract 40, bears N. 89° 45' E., 30.97 chs. dist., hereinbefore described.
17.61	Angle point No. 2 of the Private Land Claim survey of George J. Duke, identical with section 38, hereinbefore described.
	Thence, N. 0° 08' E., beginning new measurement.
10.05	Cor. No. 1 of the Private Land Claim survey of George A. Duke, identical with section 38, hereinbefore described.
13.03	Angle point No. 9 of the Private Land Claim survey of Joshua J. Mecham, identical with section 39, monumented with a quartzite stone, 18 x 8 x 7 ins., mkd. 9JJM on E face, firmly set 10 ins. in the ground.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 5 S R 3 E S 25 | AP 9 | SS 39 1971
	Deposit the mkd. stone alongside the iron post.
	Raise a mound of stone, 2½ ft. base, 2 ft. high, W of cor.
	Cor. falls on steep talus S slope.
	Thence, N. 89° 45' E., along line 9 - 10.
8.56	Point for the 2 mile post at proportionate distance; there is no remaining evidence of the original corner, not monumented.

Dependent Resurvey of a Portion of the Private Land Claim of Joshua J. Mecham, Identical with Section 39, Located in Sections 25 and 36, T. 5 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
31.14	Cor. No. 1 of the Private Land Claim survey of the survey of Joshua J. Mecham, identical with section 39, on the E. bdy. of the Tp., monumented with a quartzite stone, 25 x 9 x 3 ins., mkd. BEG COR 1 JJM on the SW face, firmly set 6 ins. in the ground, E of mound of stone, 2½ ft. base, 1 ft. high. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd. T 5 S R 3 E | R 4 E S 25 | S 30 COR 1 | JJM | SS 39 | 1969 Deposit the mkd. stone in a mound of stone, alongside the iron post. Raise a mound of stone, 2½ ft. base, 2 ft. high, W of cor. From this cor., the cor. of secs. 30 and 31, T. 5 S., R. 4 E., bears S. 0° 13' E., 4.69 chs. dist., described in the concurrent resurvey of T. 5 S., R. 4 E.
	Survey of the Subdivision of Section 13, T. 5 S., R. 3 E., Salt Lake Meridian, Utah
	From the ¼ sec. cor. of secs. 13 and 24. N. 0° 04' W., on the N and S center line of sec. 13.
39.81	Point for the center ¼ sec. cor. of sec. 13, at the intersection with the E and W center line of sec. 13. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 5 S R 3 E C ¼ S 13 1982 Cor. is located on ridge, bearing N and S, between Provo Canyon and Long Hollow.
79.86	The ¼ sec. cor. of secs. 12 and 13.
	From the ¼ sec. cor. of sec. 13 only, on the E. bdy. of the Tp., hereinbefore described. S. 89° 13' W., on the E and W center line of section 13.
18.04	True point for the center East 1/16 sec. cor. of sec. 13, falls in the Provo River, where it is impractical to establish a permanent monument.

☆U.S. Government Printing Office: 1980—778-251/292

Survey of the Subdivision of Section 13,
T. 5 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
19.23	Point selected for the witness cor. for the center East 1/16 sec. cor. of sec. 13. Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd. W C T 5 S R 3 E E 1/16 C ——— C S 13 1982 Cor. is located about 80 lks. W and 20 lks. N of the right bank of the Provo River.
37.92	The center ¼ sec. cor. of sec. 13.
57.94	Point for the center West 1/16 sec. cor. of sec. 13. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 5 S R 3 E W 1/16 C ——— C S 13 1982 Cor. is located on NE slope in scattered maple.
77.96	The ¼ sec. cor. of secs. 13 and 14.
	From the true point for the center east 1/16 sec. cor. of section 13. N. 0° 07' W., along the N and S center line of the NE¼ of section 13.
28.23	Point for the crossing closing corner at intersection with the S. bdy. of section 37. Set a steel Bathey, 24 ins. long, 1 in. diam., 18 ins. in the ground, with steel cap mkd. SS 37 E CC | S 13 | E
39.95	Point for the E 1/16 sec. cor. of secs. 12 and 13, not monumented.
	From the W 1/16 sec. cor. of secs. 13 and 24. N. 0° 15' W., along the N and S center line of the SW¼ of sec. 13.
39.85	The center W 1/16 sec. cor. of sec. 13.

74

Survey of the Subdivision of Section 13,
T. 5 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
	From the center W 1/16 sec. cor. of section 13.
	North along the N and S center line of the NW¼ of section 13.
40.14	The W 1/16 sec. cor. of secs. 12 and 13.

Survey of the Subdivision of Section 36,
T. 5 S., R. 3 E., Salt Lake Meridian, Utah

	From the standard ¼ sec. cor. of sec. 36, on the First Standard Parallel South, set, mkd. and described in the concurrent resurvey of T. 6 S., R. 3 E.
	N. 0° 10' E., along the N-S center line of section 36.
19.32	Point for the center S 1/16 sec. cor. of sec. 36.
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a collar of stone, with brass cap mkd. C - S 1/16 S 36 1971
39.33	Point for the center ¼ sec. cor. of sec. 36, at intersection with the E-W center line of sec. 36.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 5 S R 3 E C ¼ S 36 1971
	from which
	A maple, 4 ins. diam., bears N. 82° W., 27 lks. dist., mkd. X BT.
	A maple, 7 ins. diam., bears N. 34° W., 25 lks. dist., mkd. C¼ S36 BT.
	Raise a mound of stone, 2½ ft. base, 2 ft. high, W of cor.
69.45	Intersect the S. bdy. of sec. 38, at a point from which angle point No. 2, bears S. 89° 45' E., 9.39 chs. dist., hereinbefore described.
76.00	South Fork of Provo River, drains W.
77.00	Asphalt road, bears E and W.
79.49	The ¼ sec. cor. of secs. 25 and 36.
	From the ¼ sec. cor. of sec. 36 only, on the E. bdy. of the Tp., hereinbefore described.
	S. 89° 50' W., along the E-W center line of section 36.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
4.95	Intersect section 39, at a point from which angle point No. 4 bears N. 0° 26' W., 3.21 chs. dist., hereinbefore described.
20.91	Point for the center E 1/16 sec. cor. of sec. 36, not monumented.
29.33	Intersect line 4 - 1 of tract 40 at a point from which angle point No. 4 identical with angle point No. 8 of section 39 bears S. 51° 34' W., 1.57 chs. dist., hereinbefore described.
30.56	Intersect line 3 - 4 of tract 40 at a point from which angle point No. 4 identical with angle point No. 8 section 39, bears S. 0° 21' E., 0.97 chs. dist., hereinbefore described.
40.79	The center ¼ sec. cor. of sec. 36.
60.805	Point for the center W 1/16 sec. cor. of sec. 36. Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd. C - W 1/16 S 36 1971 from which A pine, 9 ins. diam., bears S. 77° E., 37 lks. dist., mkd. CW 1/16 S36 BT. A pine, 6 ins. diam., bears N. 66° W., 20 lks. dist., mkd. X BT.
80.82	The ¼ sec. cor. of secs. 35 and 36.
	From the standard E 1/16 sec. cor. of sec. 36 only, on the First Standard Parallel South, set, mkd. and described in the concurrent resurvey of T. 6 S., R. 3 E. N. 0° 08' E., on the N-S center line of the SE¼ of sec. 36.
19.34	Point for the SE 1/16 sec. cor. of sec. 36 at the intersection with the E-W center line of the SE¼ of sec. 36. Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd. SE 1/16 S 36 1971 from which A fir, 9 ins. diam., bears S. 70° W., 8.5 lks. dist., mkd. X BT.
38.35	Intersect the line between angle point Nos. 7 and 8 of section 39, from which angle point No. 7 bears S. 89° 52' E., 2.68 chs. dist., hereinbefore described.

76

Survey of the Subdivision of Section 36,
T. 5 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
39.37	Point for the center E 1/16 sec. cor. of sec. 36.
	From the S 1/16 sec. cor. of sec. 36 only on the E. bdy. of the Tp., hereinbefore described. S. 89° 53' W., along the E-W center line of the SE¼ of sec. 36.
21.02	The SE 1/16 sec. cor. of sec. 36.
30.965	Point for the center-west 1/64 sec. cor. of the SE¼ of sec. 36. Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd. C-W-SE 1/64 S 36 1971 from which A maple, 7 ins. diam., bears East, 62 lks. dist., mkd. CW-SE 1/64 S36 BT. A spruce, 10 ins. diam., bears N. 29 3/4° W., 71 lks. dist., mkd. CW-SE 1/64 S36 BT.
40.91	The center S 1/16 sec. cor. of sec. 36.
	From the standard W-E 1/64 sec. cor. of sec. 36 only, on the First Standard Parallel South, set, mkd. and described in the concurrent resurvey of T. 6 S., R. 3 E. N. 0° 07' E., along the N-S center line of the SW¼ of the SE¼ of sec. 36.
19.33	The center W 1/64 sec. cor. of the SE¼ of sec. 36.
	From the standard W 1/16 sec. cor. of sec. 36 only, on the First Standard Parallel South, set, mkd. and described in the concurrent resurvey of T. 6 S., R. 3 E. N. 0° 04' W., along the N-S center line of the SW¼ of sec. 36.
19.30	Point for the SW 1/16 sec. cor. of sec. 36, at the intersection with the E - W center line of the SW¼ of sec. 36. Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd. SW 1/16 S 36 1971 Cor. falls on steep E slope covered with dense oak and maple.
39.29	The center W 1/16 sec. cor. of sec. 36.

☆U.S. Government Printing Office: 1980—778-251/292

Survey of the Subdivision of Section 36,
T. 5 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
	From the center S 1/16 sec. cor. of sec. 36.
	S. 89° 54' W., along the E-W center line of the SW¼ of sec. 36.
9.98	Point for the center E 1/64 sec. cor. of the SW¼ of sec. 36.
	Set an iron post, 30 ins. long, 2½ ins. diam., 23 ins. in the ground, and in a collar of stone, with brass cap mkd. C-E-SW-1/64 S 36 1971
19.96	The SW 1/16 sec. cor. of sec. 36.
39.91	The S 1/16 sec. cor. of secs. 35 and 36.
	From the E-W 1/64 sec. cor. of sec. 36 only, on the First Standard Parallel South, set, mkd. and described in the concurrent resurvey of T. 6 S., R. 3 E.
	N. 0° 02' E., along the N-S center line of the SE¼ of the SW¼ of sec. 36.
19.31	The center east 1/64 sec. cor. of the SW¼ of sec. 36.

General Description

The land encompassed in this survey is located in Provo Canyon, Utah, and Wasatch Counties, Utah. For the most part the land is part of the Uinta National Forest, with the elevations ranging from 5100 ft. in sec. 34 to 8835 ft. in sec. 35.

Generally speaking the terrain is mountainous with numerous steep ledges and cliffs, particularly on the N end of Cascade Mountain located in secs. 34 and 35. The terrain is covered with thick oak and maple in the lower elevations and aspen, pine and spruce at the higher alpine elevations. There is a considerable number of cottonwood trees along the Provo River and its tributaries.

Drainages are into the Provo River from the north and south.

U.S. Highway No. 189, runs northeasterly through this township. The highway traverses through secs. 33, 34, 27, 26, 25, and 24; and exiting the township at the west boundary of sec. 13. Utah State Highway 80 junctioning with U.S. 189 in sec. 24 and runs northwesterly along the North Fork of the Provo River. A major paved road junctioning with U.S. 189 in sec. 26 runs southeasterly along the South Fork of the Provo River.

The principal use of this area is for recreation by hunters, campers, fishermen, and picknickers. There are numerous homes along the Provo River and its tributaries.

The mean of a considerable number of observations of the magnetic declination is 15° 30' E.

CERTIFICATE OF SURVEY

XX(We), Ray Harpin and Donald A. Buhler , HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 11th day of August , 19 69 XXX(We) have dependently resurveyed a portion of the subdivisional lines and a portion of sections 37, 38, and 39, and surveyed certain sections and Tract 40 of Township 5 South, Range 3 East,

of the Salt Lake Meridian, in the State of Utah , which are represented in the foregoing field notes as having been executed by ~~(me)~~, (us) and under ~~(my)~~ (our) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

June 7, 1983
(Date)

Ray Harpin
(Cadastral Surveyor)

June 7, 1983
(Date)

Donald A. Buhler
(Cadastral Surveyor)
Supervisory

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines and a portion of sections 37, 38, and 39, and the survey of certain sections and Tract 40 of Township 5 South, Range 3 East of the Salt Lake Meridian, Utah

executed by Ray Harpin, Cadastral Surveyor
Donald A. Buhler, Supervisory Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

August 15, 1983
(Date)

Glen B. Hatch
~~(Chief, Cadastral Surveys Branch, Technical Staff)~~
Chief Cadastral Surveyor for Utah

~~CERTIFICATE OF TRANSCRIPT~~

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in , is a true copy of the original field notes.

~~(Date)~~

~~(Chief, Cadastral Surveys Branch, Technical Staff)~~
Chief Cadastral Surveyor for Utah

Form 9600-11
(August 1979)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Frank C. Profaizer	Surveying Technician
Douglas A. Cody	Surveying Technician
Barry B. Babbett	Surveying Technician
Julian J. Cordova	Surveying Technician
Michael K. Davis	Survey Aid
Patrick E. Dawson	Survey Aid
Emanuel Ehrlich	Survey Aid
Everett E. Gorgen	Survey Aid
Lon G. Hill	Survey Aid
Ronald E. Lorensen	Survey Aid
William L. McDorman	Survey Aid
Alan N. Pike	Survey Aid
Donald J. Stathis, Jr.	Survey Aid
Charles C. Stevens	Survey Aid
Victor E. Templeton	Survey Aid
Roy J. Vincent	Survey Aid
Gary Gogos	Student Surveying Technician
Rex Smith	Surveying Technician
Peter Coffey	Surveying Technician
John Mavor	Survey Aid
John Zwahlen	Surveying Technician
Jeff Peyton	Surveying Technician
Donzil Worthington	Surveying Technician
Terry Christensen	Surveying Technician

Form 9600-9
(December 1979)
(formerly 9180-6)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

R606

ORIGINAL

80

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

THE FIRST STANDARD PARALLEL SOUTH,

THROUGH A PORTION OF RANGE 4 EAST,

AND

A PORTION OF THE WEST BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES

AND

THE SURVEY OF CERTAIN SECTIONS AND PARCELS

OF

TOWNSHIP 5 SOUTH, RANGE 4 EAST

Of the Salt Lake Meridian,

In the State of Utah.

EXECUTED BY

Ray Harpin Supervisory Cadastral Surveyor

Donald A. Buhler Cadastral Surveyor

Under special instructions dated August 11, 19 69, approved August 11, 1969,

, which provided for the surveys included under U.S. Survey/Group

Number 513, and assignment instructions dated August 11, 19 69

and October 10, 1979

Survey commenced August 11, 19 69

Survey completed June 25, 19 82

INDEX DIAGRAM

Township 5 South, Range 4 East,

6 32	5 25 32	4 24	3	2	1
13 7 31 31	8 24 30	9 24	10	11	12
12 18 30 30	17 23 29	16 20 23	15 20	14	13
11 19 29 28	20 22 28	21 19 22	22 17 19	23 16	24
10 30 27 27	29 21 26	28 18 21	27 16 18	26 14 15	25
9 31 25 8	32 20 7	33 17 6	34 15 4	35 3	36 1

Subdivision of Section 31 - Page 33
Subdivision of Section 32 - Page 36
Parcel A - Page 38

GPO 855-927

Township 5 South, Range 4 East, Salt Lake Meridian, Utah

CHAINS

The following field notes describe the dependent resurvey of the First Standard Parallel South, through a portion of Range 4 East, a portion of the west boundary, a portion of the subdivisional lines, and the survey of certain sections and parcels of Township 5 South, Range 4 East, Salt Lake Meridian, Utah.

The First Standard Parallel South was surveyed by Andrew J. Stewart Jr., in 1877 and a portion was retraced by Scott P. and John R. Stewart in 1900. The west boundary was surveyed by Andrew J. Stewart Jr., in 1881 and a portion was retraced by Scott P. and John R. Stewart in 1900. A portion of the subdivisional lines were surveyed by Joseph Gorlinski in 1869. A portion of the subdivisional lines were surveyed by Andrew J. Stewart Jr. in 1881.

The resurvey was executed in accordance with the specifications set forth in the Manuals of Surveying Instructions 1947 and 1973, and the Special Instructions for Group No. 513, Utah, dated August 11, 1969.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The direction of the lines were determined by solar and Polaris observations and were carried forward by sustained angulation.

The geographic position of the angle point between sections 2 and 36, on the First Standard Parallel South as calculated from a tie to the U.S. Coast and Geodetic Survey station "Hobble", in section 36, T. 5 S., R. 4 E., is as follows:

Latitude 40° 20' 03.57" N. Longitude 111° 27' 04.18" W.

The mean magnetic declination is 15° 30' E.

Dependent Resurvey of the First Standard Parallel South, through a Portion of R. 4 E., Salt Lake Meridian, Utah

---

(Restoring the 1877 Survey by Andrew J. Stewart Jr.)

Beginning at the original standard cor. of secs. 35 and 36, monumented with a sandstone, 30 x 18 x 4 ins., plainly mkd 6 notches on the N face and SC on E face, firmly set in a mound of stone, 3 ft. base, 1½ ft. high. This cor. now functions as an angle point only.

At the angle point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

83 Dependent Resurvey of the First Standard Parallel South, Through a Portion of Range 4 East, Salt Lake Meridian, Utah

CHAINS	
	AP T 5 S R 4 E S 36 S 2 T 6 S 1981
	Angle point is located on the ridge line of Wallsburg Ridge.
	from which
	United States Coast and Geodetic Survey triangulation station "Hobble", bears N. 30° 58' W., 5.85 chs. dist., monumented with a 2 x 2 ins. wooden hub firmly set in the ground
	from which
	A standard brass cap, 3½ ins. diam., firmly set in a rock outcrop, bears S. 24° 20' W., 79.2 lks. dist., mkd. NO 1 1964.
	A standard brass cap, 3½ ins. diam., firmly set in a rock outcrop, bears N. 23° 53' W., 114.4 lks. dist., mkd. NO 2 1964.
	Deposit the mkd. stone alongside the aluminum post.
	S. 89° 35' W., along the S. bdy. of sec. 36.
5.81	The standard closing cor. of secs. 35 and 36, monumented with a mound of stone, 4 ft. base, 2 ft. high. This position is accepted as the best available evidence of the position of the original corner.
	At the corner point (center of mound)
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.
	T 5 S R 4 E C C S 35 | S 36 T 6 S 1982
	Cor. is located on SW slope in scattered oak and sagebrush.
	Thence, along the S. bdy. of sec. 35, with continuous measurement.
39.55	Point for the original standard ¼ sec. cor. of sec. 35, at proportionate distance; there is no remaining evidence of the original corner. This point now functions as an angle point. Not monumented.
45.21	Point for the standard ¼ sec. cor. of sec. 35, at mid point between closing corners.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base, to top of aluminum cap, mkd.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS

T 5 S R 4 E
¼ S 35
T 6 S
1982

Cor. is located on SW slope in scattered oak.

45.88 The closing cor. of secs. 2 and 3, T. 6 S., R. 4 E., set, mkd. and described in the concurrent resurvey of T. 6 S., R. 4 E.

79.11 The original standard cor. of secs. 34 and 35, monumented with a broken sandstone, 22 x 22 x 12 ins., plainly mkd. 4 notches on W face and 2 notches on E face, firmly set 12 ins. in the ground and in a mound of stone, 3 ft. base, 2 ft. high. This cor. now functions as an angle point only.

At the angle point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

AP
T 5 S R 4 E
S 35
S 3
T 6 S
1981

Deposit the mkd. stone alongside the aluminum post.

Cor. is located on SW slope in scattered oak and maple.

N. 89° 45' W., along the S. bdy. of sec. 35.

5.50 The standard closing cor. of secs. 34 and 35, monumented with a sandstone, 20 x 12 x 8 ins., plainly mkd. CC on N face, 4 notches on W face and 2 notches on E face.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.

T 5 S R 4 E
C | C
S 34 | S 35
T 6 S
1981

Deposit the mkd. stone alongside the aluminum post.

Cor. is located on SW slope in scattered oak.

Thence, along the S. bdy. of sec. 34 with continuous measurement.

6.08 The ¼ sec. cor. of sec. 3, T. 6 S., R. 4 E., set, mkd. and described in the concurrent resurvey of T. 6 S., R. 4 E.

85 Dependent Resurvey of the First Standard Parallel South,
Through a Portion of Range 4 East,
Salt Lake Meridian, Utah

CHAINS	
39.09	The original standard ¼ sec. cor. of sec. 34, monumented with a sandstone, 17 x 10 x 5 ins., plainly mkd. ¼ on N face and in a mound of stone. This cor. now functions as an angle point only. At the angle point Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd. AP T 5 S R 4 E S 34 S 3 T 6 S 1981 Deposit the mkd. stone alongside the aluminum post. Cor. is located on W slope in scattered oak.
	N. 89° 23' W., beginning new measurement.
5.46	Point for the standard ¼ sec. cor. of sec. 34, at mid point between closing corners. Set an aluminum post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 5 S R 4 E ¼ S 34 T 6 S 1981 Cor. is located on W slope in scattered oak.
6.27	The closing cor. of secs. 3 and 4, T. 6 S., R. 4 E., set, mkd. and described in the concurrent resurvey of T. 6 S., R. 4 E.
39.96	The original standard cor. of secs. 33 and 34, monumented with a sandstone, 18 x 8 x 6 ins., plainly mkd. SC and 6 grooves on N face, 3 notches on E and W edges, firmly set 10 ins. in the ground. This corner now functions as an angle point only. At the angle point Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd. AP T 5 S R 4 E S 34 S 4 T 6 S 1969 Deposit the mkd. stone alongside the iron post. Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.
	S. 89° 06' W., along the S. bdy. of sec. 34.

☆U.S. Government Printing Office: 1980—778-251/292

Dependent Resurvey of the First Standard Parallel South,
Through a Portion of Range 4 East,
Salt Lake Meridian, Utah

CHAINS	
4.55	The closing cor. of secs. 33 and 34, monumented with a granite stone, 30 x 14 x 10 ins., plainly mkd. C on N face and firmly set 10 ins. in the ground. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. C C T 5 S R 4 E S 33 | S 34 1969 Deposit the mkd. stone in the mound of stone. Raise a mound of stone, 3 ft. base, 2½ ft. high, N of cor. Thence, along the S. bdy. of sec. 33 with continuous measurement.
5.75	The ¼ sec. cor. of sec. 4, T. 6 S., R. 4 E., set, mkd. and described in the concurrent resurvey of T. 6 S., R. 4 E.
38.97	Point for the original standard ¼ sec. cor. of sec. 33, at proportionate distance; there is no remaining evidence of the original corner. This corner now functions as an angle point. Not monumented.
44.16	Point for the standard ¼ sec. cor. of sec. 33, at mid point between closing corners. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 5 S R 4 E ¼ S 33 1969 Raise a mound of stone, 3 ft. base, 2½ ft. high, N of cor.
45.17	The closing cor. of secs. 4 and 5, identical with angle point No. 1 of tract 48 in T. 6 S., R. 4 E., set, mkd. and described in the concurrent resurvey of T. 6 S., R. 4 E.
64.21	The E 1/16 sec. cor. of sec. 5, T. 6 S., R. 4 E., set, mkd. and described in the concurrent resurvey of T. 6 S., R. 4 E.
77.94	The original standard cor. of secs. 32 and 33, identical with angle point No. 2 of tract 48 in T. 6 S., R. 4 E., monumented with a sandstone, 30 x 18 x 4 ins., plainly mkd. SC and 6 notches on N face and 4 notches on E face, in a mound of stone, 3 ft. base, 1 ft. high. This corner now functions as an angle point only. At the angle point Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of brass cap, mkd.

CHAINS	
	AP T 5 S R 4 E S 33 S 5 T 6 S 1969 Deposit the mkd. stone alongside the iron post.
	(Restoring the 1877 Survey by Andrew J. Stewart Jr. and the 1900 Retracement Survey by Scott P. and John R. Stewart)
	S. 89° 35' W., along the S. bdy. of sec. 33.
5.31	The ¼ sec. cor. of sec. 5, T. 6 S., R. 4 E., set, mkd. and described in the concurrent resurvey of T. 6 S., R. 4 E.
5.83	The closing cor. of secs. 32 and 33, monumented with a sandstone, 24 x 10 x 8 ins., plainly mkd. CC on N face, 2 notchces on W face and 4 notches on E face, and in a mound of stone, 3 ft. base, 1 ft. high. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd. C C T 5 S R 4 E S 32 | S 33 1969 Deposit the mkd. stone in a mound of stone. Raise a mound of stone, 3 ft. base, 1½ ft. high, N of cor.
	Thence, along the S. bdy. of sec. 32, with continuous measurement.
35.88	Angle point No. 3 of tract 48, identical with angle point No. 2 of sec. 38 in T. 6 S., R. 4 E., set, mkd. and described in the concurrent resurvey of T. 6 S., R. 4 E.
38.78	Point for the original standard ¼ sec. cor. of sec. 32, at proportionate distance; there is no remaining evidence of the original corner. This corner now functions as an angle point. Not monumented.
43.39	The closing cor. of secs. 5 and 6, T. 6 S., R. 4 E., set, mkd. and described in the concurrent resurvey of T. 6 S., R. 4 E.
44.35	Point for the ¼ sec. cor. of sec. 32, at mid point between closing corners. Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd. T 5 S R 4 E ¼ S 32 1969 Set an oak post, 3 ins. diam., 6 ft. long, alongside the iron post.

☆U.S. Government Printing Office: 1980—778-251/292

Dependent Resurvey of the First Standard Parallel South,
Through a Portion of Range 4 East,
Salt Lake Meridian, Utah

CHAINS	
58.00	Graded road, bears NW and SE.
60.00	South Fork of Provo River, drains NW.
63.61	Point for the W 1/16 sec. cor. of sec. 32 only.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	W 1/16 S 32 1969
	from which
	A willow, 20 ins. diam., bears N. 37° 45' E., 38 lks. dist., mkd. W 1/16 S32 BT.
	A rebar, 3/4 in. diam., bears N. 62° 12' E., 81 lks. dist.
	A maple, 12 ins. diam., bears N. 61° 25' W., 87 lks. dist., mkd. W 1/16 S32 BT.
	Cor. is located in a pasture.
77.56	The original standard cor. of secs. 31 and 32, identical with angle point No. 2 of sec. 39 in T. 6 S., R. 4 E., monumented with a sandstone, 17 x 15 x 7 ins., loosely set in a fence extending E and W, mkd. SC on N face, 5 notches on E face, 1 notch on W face, and 6 notches on N face. This corner now functions as an angle point only.
	At the angle point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	AP T 5 S R 4 E S 32 S 6 T 6 S 1969
	Deposit the mkd. stone in a mound of stone.
	Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor.
	S. 89° 57' W., along the S. bdy. of sec. 32.
5.19	The ¼ sec. cor. of sec. 6 only, set, mkd. and described in the concurrent resurvey of T. 6 S., R. 4 E.
5.31	Point for the standard closing cor. of secs. 31 and 32, at intersection with the First Standard Parallel South.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	SC T 5 S | R 4 E C | C S 31 | S 32 1969

CHAINS	
	Raise a mound of stone, 3 ft. base, 1½ ft. high, N of cor.
	There are no suitable bearing trees within limits.
	From the point of intersection, a granite stone, 28 x 18 x 18 ins., firmly set 10 ins. in the ground, mkd. CC on N face, with 5 notches on E face, and 1 notch on W face, set in a mound of stone, 3 ft. base, 1 ft. high, 1 lk. N of a fence, extending E and W, bears N. 0° 03' W., 0.264 lks. dist. I mkd. the stone with AM.
	Thence, along the S. bdy. of sec. 31.
24.87	The W 1/16 sec. cor. of sec. 6, T. 6 S., R. 4 E., set, mkd. and described in the concurrent resurvey of T. 6 S., R. 4 E.
38.82	Point for the original standard ¼ sec. cor. of sec. 31, at proportionate distance; there is no remaining evidence of the original corner. This corner now functions as an angle point only. Not monumented.
44.08	Point for the ¼ sec. cor. of sec. 31 only, on the S. bdy. of sec. 31.
	Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 5 S R 4 E ¼ S 31 1969
	from which
	A spruce, 8 ins. diam., bears S. 31° E., 27 lks. dist., mkd. X BT.
	Raise a mound of stone, 3 ft. base, 1½ ft. high, N of cor.
63.47	Point for the W 1/16 sec. cor. of sec. 31 only, on the S. bdy. of sec. 31.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	W 1/16 S 31 1969
	There are no suitable bearing trees within limits.
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.
70.63	Point for the closing cor. of Tps. 6 S., Rs. 3 and 4 E. only, set, mkd. and described in the concurrent resurvey of T. 6 S., R. 3 E.
77.65	Point for the original standard cor. of secs. 31 and 36, Tps. 5 S., Rs. 3 and 4 E., described in the concurrent resurvey of the N. bdy. of T. 6 S., R. 3 E. This cor. now functions as an angle point.

Dependent Resurvey of the First Standard Parallel South,
Through a Portion of Range 4 East,
Salt Lake Meridian, Utah

From this point, the closing cor. of T. 5 S., Rs. 3 and 4 E., on the First Standard Parallel South, bears S. 89° 57' W., 3.82 chs. dist. as described in the concurrent resurvey of the N. bdy. of T. 6 S., R. 3 E.

Dependent Resurvey of a Portion of the West Boundary,
T. 5 S., R. 4 E., Salt Lake Meridian, Utah

(Restoring the 1881 Survey by Andrew J. Stewart Jr. and the 1900 Retracement by Scott P. and John R. Stewart)

From the closing cor. of secs. 31 and 36, Tps. 5 S., Rs. 3 and 4 E., on the First Standard Parallel South, set, mkd. and described in the concurrent resurvey of T. 6 S., R. 3 E.

N. 0° 12' W., along the W. bdy. of sec. 31.

CHAINS	
19.36	The S 1/16 sec. cor. of sec. 36, T. 5 S., R. 3 E., set, mkd. and described in the concurrent resurvey of T. 5 S., R. 3 E.
37.99	The ¼ sec. cor. of sec. 31 only, on the W. bdy. of the Tp., as determined at the cor. of old fences extending N and E. This position is accepted as the best available evidence of the original corner position.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 2½ ft. base, to top of brass cap, mkd.

T 5 S
| ¼
| S 31
| R 4 E
1969

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

N. 0° 13' W., beginning new measurement.

1.43	The ¼ sec. cor. of sec. 36, T. 5 S., R. 3 E., set, mkd. and described in the concurrent resurvey of T. 5 S., R. 3 E.
4.66	Angle Point 3 identical with one half mile cor. of the Private Land Claim Survey of Joshua J. Mecham, identical with sec. 39, T. 5 S., R. 3 E., set, mkd. and described in the concurrent resurvey of T. 5 S., R. 3 E.
19.93	Point for the N 1/16 sec. cor. of sec. 31 only.

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

| N 1/16
| S 31
1969

CHAINS	
	Raise a mound of stone, 4 ft. base, 2 ft. high, W of cor.
	Cor. is located 3 ft. W of the westerly limit of a trail road, 10 ft. wide and extending N and S along a fence.
21.49	The N 1/16 sec. cor. of sec. 36, T. 5 S., R. 3 E., set, mkd. and described in the concurrent resurvey of T. 5 S., R. 3 E.
24.55	Angle Point No. 1 of tract 40, T. 5 S., R. 3 E., set, mkd. and described in the concurrent resurvey of T. 5 S., R. 3 E.
39.00	South Fork Provo River, drains W.
39.86	Point for the cor. of secs. 30 and 31 only, identical with cor. No. 2 of the Private Land Claim Survey of Joshua J. Meacham, identical with sec. 39, T. 5 S., R. 4 E., at proportionate distance; and longitudinally substantiated by Mr. Long, an adjacent landowner, as verified the line was between 2 trees and there was evidence of an old cut line and accepted as the best available evidence of the position of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 5 S R 3 E | R 4 E S 36 | S 30 | S 31 1969
	Raise a mound of stone, 3 ft. base, 2 ft. high, E of cor.
	N. 0° 13' W., along the W. bdy. of sec. 30.
0.50	Graded road, bears WNW and ESE.
1.70	The closing cor. of secs. 25 and 36, T. 5 S., R. 3 E., set, mkd. and described in the concurrent resurvey of T. 5 S., R. 3 E.
4.69	Cor. No. 1 of the Private Land Claim survey of Joshua J. Mecham, identical with sec. 39 in T. 5 S., R. 3 E., set, mkd. and described in the concurrent resurvey of T. 5 S., R. 3 E.
	N. 1° 01' W., beginning new measurement.
33.94	Point for the ¼ sec. cor. of sec. 30 only, on the W. bdy. of the Tp., at proportionate distance; there is no remaining evidence of the original corner.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T 5 S R 3 E | R 4 E | ¼ | S 30 1981

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	Raise a mound of stone, 3 ft. base, 1½ ft. high, E of cor.
36.67	The ¼ sec. cor. of sec. 25, T. 5 S., R. 3 E., set, mkd. and described in the concurrent resurvey of T. 5 S., R. 3 E.
72.56	Point for the cor. of secs. 19 and 30 only, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 5 S R 3 E | R 4 E | S 19 S 25 | S 30 1981 Raise a mound of stone, 3 ft. base, 2½ ft. high, E of cor. Cor. is located on steep NW slope.
	N. 1° 01' W., along the W. bdy. of sec. 19.
3.76	Point for the closing cor. of secs. 24 and 25, T. 5 S., R. 3 E., set, mkd. and described in the concurrent resurvey of T. 5 S., R. 3 E.
38.62	Point for the ¼ sec. cor. of sec. 19 only, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 21 ins. in the ground, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd. T 5 S R 3 E | R 4 E | ¼ | S 19 1981 Cor. is located on steep SW slope in scattered oak and maple.
43.59	The ¼ sec. cor. of sec. 24 only, T. 5 S., R. 3 E., set, mkd. and described in the concurrent resurvey of T. 5 S., R. 3 E.
77.24	Point for the cor. of secs. 18 and 19 only, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd. T 5 S R 3 E | R 4 E | S 18 S 24 | S 19 1981

93

Dependent Resurvey of a Portion of the West Boundary,
T. 5 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	from which A pine, 7 ins. diam., bears N. 68° E., 17 lks. dist., mkd. T5S R4E S18 BT. A pine, 20 ins. diam., bears N. 58° 03' W., 106 lks. dist., mkd. X BT. Cor. is located on steep NE slope in thick oak, maple and pine, and on the W side of a rock slide.
	N. 1° 01' W., along the W. bdy. of sec. 18.
6.17	The closing cor. of secs. 13 and 24, T. 5 S., R. 3 E., set, mkd. and described in the concurrent resurvey of T. 5 S., R. 3 E.
38.62	Point for the ¼ sec. cor. of sec. 18 only, at proportionate distance based on the irregular boundary method; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 5 S R 3 E | R 4 E | ¼ | S 18 1981 from which A pine, 12 ins. diam., bears N. 5° 25' E., 170 lks. dist., mkd. ¼ S18 BT. A juniper, 16 ins. diam., bears N. 36° 30' E., 157 lks. dist., mkd. ¼ S18 BT. Cor. is located on E edge of a trail road, 10 ft. wide. Raise a mound of stone, 2½ ft. base, 1½ ft. high, E of cor.
	N. 0° 58' W., beginning new measurement.
7.28	The ¼ sec. cor. of sec. 13 only, T. 5 S., R. 3 E., set, mkd. and described in the concurrent resurvey of T. 5 S., R. 3 E.
18.00	Provo River, drains SW.
20.00	Denver and Rio Grande Western Railroad, bears NE and SW.
22.00	U.S. Highway No. 189, bears NNE and SW.
35.12	Cor. No. 1 of the Private Land Claim survey of John W. Hoover, identical with sec. 37 in T. 5 S., R. 3 E., set, mkd. and described in the concurrent resurvey of T. 5 S., R. 3 E.
	N. 1° 06' W., beginning new measurement.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS

3.04 Point for the cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 5 S
R 3 E | R 4 E
S 13 | S 7
| S 18
1981

Deposit a steel post, 4 ft. long, 2½ ins. diam., alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor.

N. 0° 38' W., along the W. bdy. of sec. 7.

8.85 The closing cor. of secs. 12 and 13, T. 5 S., R. 3 E., set, mkd. and described in the concurrent resurvey of T. 5 S., R. 3 E.

41.07 The ¼ sec. cor. of sec. 7 only, monumented with a limestone, 13 x 11 x 4 ins., plainly mkd. ¼ on W face, firmly set 5 ins. in the ground, with a mound of stone, 2½ ft. base, 1 ft. high, W of cor.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 5 S
R 3 E | R 4 E
| ¼
| S 7
1981

Deposit the mkd. stone alongside the iron post.

N. 0° 05' W., beginning new measurement.

39.63 The cor. of secs. 6 and 7 only, monumented with a granite stone, 18 x 12 x 5 ins., plainly mkd. 5 notches on S edge and firmly set in a mound of stone, 2½ ft. base, 1 ft. high.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 5 S
R 3 E | R 4 E
S 12 | S 6
| S 7
1981

Deposit the mkd. stone alongside the aluminum post.

CHAINS

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 5 S., R. 4 E., Salt Lake Meridian, Utah

(Restoring the 1881 Survey by Andrew J. Stewart Jr.)

From the cor. of secs. 25, 26, 35, and 36, monumented with a sandstone, 24 x 13 x 9 ins., dimly mkd. 1 notch on S edge and firmly set in a mound of stone, 2½ ft. base, 1 ft. high.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 5 S R 4 E
S 26 | S 25
S 35 | S 36
1982

Deposit the mkd. stone alongside the aluminum post.

Cor. is located on SE slope in scattered oak.

N. 2° 20' E., bet. secs. 25 and 26.

39.60 Point for the ¼ sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 5 S R 4 E
¼
S 26 | S 25
1982

Cor. is located on NE slope in thick underbrush.

79.20 The cor. of secs. 23, 24, 25, and 26, monumented with a sandstone, 20 x 16 x 8 ins., plainly mkd. 2 notches on S edge and 1 notch on E edge, set in a small mound of stone.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 5 S R 4 E
S 23 | S 24
S 26 | S 25
1982

Deposit the mkd. stone alongside the aluminum post.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS

from which

An aspen, 4 ins. diam., bears N. 5° E., 21 lks. dist., mkd. T5S R4E S24 BT.

An aspen, 5 ins. diam., bears S. 40° E., 18 lks. dist., mkd. T5S R4E S25 BT.

An aspen, 8 ins. diam., bears S. 10° W., 25 lks. dist., mkd. T5S R4E S26 BT.

An aspen, 6 ins. diam., bears N. 65° W., 8 lks. dist., mkd. T5S R4E S23 BT.

Cor. is located on NE slope in scattered maple, oak and aspen.

From the closing cor. of secs. 34 and 35, on the S. bdy. of the Tp., hereinbefore described.

N. 1° 10' E., bet. secs. 34 and 35.

34.34 Point for the ¼ sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.

T 5 S R 4 E
¼
S 34 | S 35
1982

Cor. is located on NW slope in scattered oak.

74.04 Point for the cor. of secs. 26, 27, 34, and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 5 S R 4 E
S 27 | S 26
S 34 | S 35
1982

Cor. is located about 8 chs. dist. W of the Wallsburg Ridge.

From the cor. of secs. 25, 26, 35, and 36.

N. 89° 13' W., bet. secs. 26 and 35.

39.27 Point for the ¼ sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original corner.

97

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a mound of stone, 4½ ft. base, to top of aluminum cap, mkd. T 5 S R 4 E ¼ S 26 / S 35 1982 Cor. is located on NE slope in aspen.
78.54	The cor. of secs. 26, 27, 34, and 35.
	N. 1° 51' E., bet. secs. 26 and 27.
39.71	Point for the ¼ sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 5 S R 4 E ¼ S 27 | S 26 1982 Cor. is located 1.5 chs. dist. N of a ridge which bears NE and SW.
79.42	Point for the cor. of secs. 22, 23, 26, and 27, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 5 S R 4 E S 22 | S 23 S 27 | S 26 1982
	From the cor. of secs. 23, 24, 25, and 26. N. 89° 02' W., bet. secs. 23 and 26.
39.60	Point for the ¼ sec. cor. of secs. 23 and 26, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd. T 5 S R 4 E ¼ S 23 / S 26 1982

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	Cor. is located about 2 chs. E of the bottom of Billy Haws Canyon, in scattered maple and aspen.
79.20	The cor. of secs. 22, 23, 26, and 27.
	N. 2° 21' E., bet. secs. 22 and 23.
39.72	Point for the ¼ sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T 5 S R 4 E ¼ S 22 | S 23 1982
	Cor. is located on NE slope in scattered oak and maple.
79.44	The cor. of secs. 14, 15, 22, and 23, monumented with a sandstone, 12 x 8 x 7 ins., plainly mkd. 3 notches on S face and 2 notches on E face, firmly set in a mound of stone, 2 ft. base, 2 ft. high, E of cor.
	from which
	A pine, 16 ins. diam., bears N. 18° W., 35 lks. dist., with a U.S. Forest Service bearing tree tag, dated August 13, 1974, nailed on the tree.
	At the corner point
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a collar of stone, with aluminum cap mkd.
	T 5 S R 4 E S 15 | S 14 S 22 | S 23 1981
	Deposit the mkd. stone alongside the aluminum post.
	From the closing cor. of secs. 33 and 34, on the S. bdy. of the Tp., hereinbefore described.
	N. 1° 40' E., bet. secs. 33 and 34.
35.35	Point for the ¼ sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.
	T 5 S R 4 E ¼ S 33 | S 34 1982

CHAINS	
	Cor. is located on steep SE slope in scattered oak brush.
75.29	Point for the cor. of secs. 27, 28, 33, and 34, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 5 S R 4 E S 28 | S 27 S 33 | S 34 1982 Cor. is located about 2 chs. dist. W of the bottom of draw, draining SE.
	From the cor. of secs. 26, 27, 34, and 35. N. 88° 43' W., bet. secs. 27 and 34.
38.71	Point for the ¼ sec. cor. of secs. 27 and 34, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 5 S R 4 E ¼ S 27 S 34 1982 Cor. is located on NE slope in scattered oak.
77.42	The cor. of secs. 27, 28, 33, and 34.
	N. 0° 30' E., bet. secs. 27 and 28.
39.93	Point for the ¼ sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 5 S R 4 E ¼ S 28 | S 27 1982 Cor. is located on W slope.
79.86	Point for the cor. of secs. 21, 22, 27, and 28, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	T 5 S R 4 E S 21 | S 22 S 28 | S 27 1982 Cor. is located on SW slope in scattered oak.
	From the cor. of secs. 22, 23, 26, and 27. N. 88° 24' W., bet. secs. 22 and 27.
39.63	Point for the ¼ sec. cor. of secs. 22 and 27, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 5 S R 4 E ¼ S 22 S 27 1982 Cor. is located on NE slope in scattered aspen.
79.27	The cor. of secs. 21, 22, 27, and 28.
	N. 1° 30' E., bet. secs. 21 and 22.
39.95	Point for the ¼ sec. cor. of secs. 21 and 22, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd. T 5 S R 4 E ¼ S 21 | S 22 1982 Cor. is located on NE slope in scattered aspen.
79.90	Point for the cor. of secs. 15, 16, 21, and 22, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 5 S R 4 E S 16 | S 15 S 21 | S 22 1982 Cor. is located 1 ch. dist. W of draw which drains NE and in scattered aspen and dense underbrush.

101

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	From the cor. of secs. 14, 15, 22, and 23.
	N. 88° 04' W., bet. secs. 15 and 22.
40.22	Point for the ¼ sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original corner.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base, to top of aluminum cap, mkd.
	T 5 S R 4 E ¼ S 15 S 22 1982
	Cor. is located on SE slope in scattered oak brush.
80.44	The cor. of secs. 15, 16, 21, and 22.
	N. 6° 08' W., bet. secs. 15 and 16.
40.17	Point for the ¼ sec. cor. of secs. 15 and 16, at proportionate distance; there is no remaining evidence of the original corner.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.
	T 5 S R 4 E ¼ S 16 | S 15 1982
	Cor. is located 1.5 chs. dist. W of draw which drains NE and in oak brush.
80.34	The cor. of secs. 9, 10, 15, and 16, monumented with a granite stone, 15 x 9 x 4 ins., plainly mkd. 4 notches on S edge and 3 notches on E edge, set in a small mound of stone.
	At the corner point
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.
	T 5 S R 4 E S 9 | S 10 S 16 | S 15 1981
	Cor. is located on NE slope in scattered oak and maple brush.
	From the closing cor. of secs. 32 and 33, on the S. bdy. of the Tp., hereinbefore described.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	N. 3° 14' E., bet. secs. 32 and 33.
34.88	Point for the ¼ sec. cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 5 S R 4 E ¼ S 32 | S 33 1970 Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.
73.42	The cor. of secs. 28, 29, 32, and 33, monumented with a sandstone, 20 x 16 x 7 ins., plainly mkd. 4 notches on E edge, firmly set 4 ins. in the ground. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 5 S R 4 E S 29 | S 28 S 32 | S 33 1970 Deposit the mkd. stone alongside the aluminum post. Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.
	From the cor. of secs. 27, 28, 33, and 34. S. 87° 42' W., bet. secs. 28 and 33.
38.70	Point for the ¼ sec. cor. of secs. 28 and 33, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 5 S R 4 E ¼ S 28 S 33 1982 Cor. is located on E slope in thick maple.
77.41	The cor. of secs. 28, 29, 32, and 33.
	N. 0° 43' W., bet. secs. 28 and 29.
39.90	Point for the ¼ sec. cor. of secs. 28 and 29, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a mound of stone, 2½ ft. base, to top of aluminum cap, mkd.

CHAINS	
	T 5 S R 4 E ¼ S 29 | S 28 1982 Cor. is located on SW slope in oak and maple brush.
79.80	Point for the cor. of secs. 20, 21, 28, and 29, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 5 S R 4 E S 20 | S 21 S 29 | S 28 1982 Cor. is located on NE slope in oak and maple brush.
	From the cor. of secs. 21, 22, 27, and 28. S. 87° 42' W., bet. secs. 21 and 28.
39.55	Point for the ¼ sec. cor. of secs. 21 and 28, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 5 S R 4 E S 21 ¼ S 28 1982 Cor. is located on NE slope in aspen grove.
79.11	The cor. of secs. 20, 21, 28, and 29.
	N. 0° 31' E., bet. secs. 20 and 21.
39.90	Point for the ¼ sec. cor. of secs. 20 and 21, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 5 S R 4 E ¼ S 20 | S 21 1982 Cor. is located on NW slope in dense oak brush.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
79.80	Point for the cor. of secs. 16, 17, 20, and 21, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 5 S R 4 E S 17 | S 16 S 20 | S 21 1982 Cor. is located on SW slope in scattered oak brush.
	From the cor. of secs. 15, 16, 21, and 22. S. 87° 41' W., bet. secs. 16 and 21.
40.23	Point for the ¼ sec. cor. of secs. 16 and 21, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 2½ ft. base, to top of aluminum cap, mkd. T 5 S R 4 E ¼ S 16 S 21 1982
80.46	The cor. of secs. 16, 17, 20, and 21.
	N. 4° 29' W., bet. secs. 16 and 17.
40.02	Point for the ¼ sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 5 S R 4 E ¼ S 17 | S 16 1982 Cor. is located on SE slope in scattered oak brush.
80.04	Point for the cor. of secs. 8, 9, 16, and 17, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd. T 5 S R 4 E S 8 | S 9 S 17 | S 16 1982 Cor. is located on top of spur, which projects N.

105

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS

From the cor. of secs. 9, 10, 15, and 16.

S. 87° 33' W., bet. secs. 9 and 16.

39.06 Point for the ¼ sec. cor. of secs. 9 and 16, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 5 S R 4 E
S 9
¼ S 16
1982

Cor. is located on steep NE slope in scattered oak.

78.12 The cor. of secs. 8, 9, 16, and 17.

N. 0° 58' E., bet. secs. 8 and 9.

39.90 Point for the ¼ sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3½ ft. base, to top of aluminum cap, mkd.

T 5 S R 4 E
¼
S 8 | S 9
1982

Cor. is located on NE slope in scattered oak, maple and aspen.

79.80 Point for the cor. of secs. 4, 5, 8, and 9, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 3½ ft. base, to top of aluminum cap, mkd.

T 5 S R 4 E
S 5 | S 4
S 8 | S 9
1982

Cor. is located on N slope in thick oak and service berry.

From the cor. of secs. 3, 4, 9, and 10, monumented with a sandstone, firmly set, projecting 12 x 9 x 9 ins., out of concrete, plainly mkd. 5 notches on S edge and 3 notches on E edge, with a rebar 1 in. diam., alongside. This cor. was not remonumented.

S. 89° 22' W., bet. secs. 4 and 9.

39.58 Point for the ¼ sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original corner.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd. T 5 S R 4 E ¼ S 4 / S 9 1982 Cor. is located on NW slope in scattered oak and service berry.
79.16	The cor. of secs. 4, 5, 8, and 9.
	N. 1° 09' W., bet. secs. 4 and 5.
34.00	U.S. Highway No. 189, bears E and W.
39.91	The ¼ sec. cor. of secs. 4 and 5, as determined from a U.S. Forest Service location post. (The original cor. as described in the U.S.F.S. Corner Record Search Form 7100-52(3/68) dated August 2, 1974, states the original cor. was destroyed by a Utah State Land Contractor in 1975. This same form describes this lost corner as a granite stone, 20 x 14 x 6 ins., mkd. ¼ and projecting 5 ins. above the ground and in good condition.) from which An oak, 2½ ins. diam., bears S. 50° W., 147 lks. dist., (97 ft.), mkd. with a U.S.F.S. Location poster nailed on the tree. At the corner point Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 5 S R 4 E ¼ S 5 | S 4 1982 Cor. is located 4 lks. dist. W of the ranger's residence of Deer Creek State Park, Utah.
	From the closing cor. of secs. 31 and 32, on the S. bdy. of the Tp., hereinbefore described. N. 0° 03' W., bet. secs. 31 and 32.
0.264	The original closing cor. now an amended monument, hereinbefore described.
16.865	Point for the S 1/16 sec. cor. of secs. 31 and 32. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. S 1/16 S 31 | S 32 1969 Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor.

CHAINS	
	From this cor., Angle Point 1 of Parcel A, bears N. 59° 07' E., 5.84 chs. dist., hereinafter described.
21.00	South Fork Provo River, drains W.
24.00	Graded road, bears WNW and ESE.
35.84	Point for the ¼ sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 5 S R 4 E ¼ S 31 | S 32 1969 Cor. is located on steep SW slope.
54.815	Point for the N 1/16 sec. cor. of secs. 31 and 32. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. N 1/16 S 31 | S 32 1969 Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.
73.79	The cor. of secs. 29, 30, 31, and 32, monumented with a blue limestone, 20 x 10 x 8 ins., mkd. 3 notches and 1 broken notch on E edge and 1 notch on S edge, set in a scattered mound of stone, 2½ ft. base. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 5 S R 4 E S 30 | S 29 S 31 | S 32 1969 Deposit the mkd. stone in the mound of stone. Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.
	From the cor. of secs. 28, 29, 32, and 33. S. 89° 55' W., bet. secs. 29 and 32.
40.65	Point for the ¼ sec. cor. of secs. 29 and 32, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

☆U.S. Government Printing Office: 1980—778-251/292

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	T 5 S R 4 E ¼ S 29 / S 32 1970
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.
	Cor. is located on steep NW slope.
81.30	The cor. of secs. 29, 30, 31, and 32.
	N. 87° 03' W., bet. secs. 30 and 31.
18.98	Point for the E 1/16 sec. cor. of secs. 30 and 31.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	E 1/16 S 30 / S 31 1970
	Raise a mound of stone, 3½ ft. base, 2½ ft. high, W of cor.
37.96	Point for the ¼ sec. cor. of secs. 30 and 31, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 5 S R 4 E ¼ S 30 / S 31 1970
	Raise a mound of stone, 3½ ft. base, 2 ft. high, N of cor.
56.94	Point for the W 1/16 sec. cor. of secs. 30 and 31.
	Set an iron post, 30 ins. long, 2½ ins. diam., on solid rock over a cross (X) chisled on the S edge of a large boulder and in a mound of stone, 5 ft. base, to top of brass cap, mkd.
	W 1/16 S 30 / S 31 1970
75.00	Graded road, bears SE and W.
76.50	The cor. of secs. 30 and 31 only, on the W. bdy. of the Tp., hereinbefore described.
	From the cor. of secs. 29, 30, 31, and 32.
	N. 1° 10' E., bet. secs. 29 and 30.
39.65	Point for the ¼ sec. cor. of secs. 29 and 30, at proportionate distance; there is no remaining evidence of the original corner.

109

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 5 S R 4 E ¼ S 30 | S 29 1982 Cor. is located on S slope in scattered oak.
79.30	Point for the cor. of secs. 19, 20, 29, and 30, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 5 S R 4 E S 19 | S 20 S 30 | S 29 1982 Cor. is located on NE slope in thick oak brush.
	From the cor. of secs. 20, 21, 28, and 29. S. 89° 32' W., bet. secs. 20 and 29.
39.32	Point for the ¼ sec. cor. of secs. 20 and 29, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 5 S R 4 E S 20 ¼ S 29 1982 Cor. is located 2 chs. dist. from a draw, draining NW and on NW slope in thick oak brush.
78.65	The cor. of secs. 19, 20, 29, and 30.
	N. 88° 36' W., bet. secs. 19 and 30.
39.46	Point for the ¼ sec. cor. of secs. 19 and 30, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 5 S R 4 E S 19 ¼ S 30 1982

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor
	Cor. is located on N slope in scattered aspen.
79.39	The cor. of secs. 19 and 30 only, on the W. bdy. of the Tp., hereinbefore described.
	From the cor. of secs. 19, 20, 29, and 30.
	N. 0° 45' W., bet. secs. 19 and 20.
39.64	Point for the ¼ sec. cor. of secs. 19 and 20, at proportionate distance; there is no remaining evidence of the original corner.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T 5 S R 4 E ¼ S 19 | S 20 1982
	Cor. is located on SW slope in thick oak brush.
79.28	Point for the cor. of secs. 17, 18, 19, and 20, at proportionate distance; there is no remaining evidence of the original corner.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.
	T 5 S R 4 E S 18 | S 17 S 19 | S 20 1982
	Cor. is located on SW slope in scattered oak and maple.
	From the cor. of secs. 16, 17, 20, and 21.
	S. 89° 11' W., bet. secs. 17 and 20.
40.20	Point for the ¼ sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T 5 S R 4 E ¼ S 17 S 20 1982
	Cor. is located on SW slope in thick oak brush.
80.40	The cor. of secs. 17, 18, 19, and 20.

111

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	S. 89° 55' W., bet. secs. 18 and 19.
40.19	Point for the ¼ sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 5 S R 4 E S 18 ¼ S 19 1982 Cor. is located on SW slope in thick maple.
79.68	The cor. of secs. 18 and 19 only, on the W. bdy. of the Tp., hereinbefore described.
	From the cor. of secs. 17, 18, 19, and 20. N. 2° 45' W., bet. secs. 17 and 18.
39.69	Point for the ¼ sec. cor. of secs. 17 and 18, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a mound of stone, 3½ ft. base, to top of aluminum cap, mkd. T 5 S R 4 E ¼ S 18 | S 17 1982 Cor. is located on SW slope in scattered oak.
79.38	Point for the cor. of secs. 7, 8, 17, and 18, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 5 S R 4 E S 7 | S 8 S 18 | S 17 1982 Raise a mound of stone, 2½ ft. base, 1½ ft. high, S of cor. Cor. is located on S slope in scattered oak.
	From the cor. of secs. 8, 9, 16, and 17. S. 88° 47' W., bet. secs. 8 and 17.
38.97	Point for the ¼ sec. cor. of secs. 8 and 17, at proportionate distance; there is no remaining evidence of the original corner.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 5 S R 4 E ¼ S 8 / S 17 1982 Cor. is located on SE slope in oak brush.
77.94	The cor. of secs. 7, 8, 17, and 18.
	S. 88° 04' W., bet. secs. 7 and 18.
38.75	Point for the ¼ sec. cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 5 S R 4 E ¼ S 7 / S 18 1982 Cor. is located on NW slope in scattered pine and thick underbrush.
63.00	Provo River, drains SW.
65.00	Denver and Rio Grande Western Railroad, bears NE and SW.
69.00	U.S. Highway No. 189, bears NE and SE.
77.26	The cor. of secs. 7 and 18, on the W. bdy. of the Tp., hereinbefore described.
	From the cor. of secs. 7, 8, 17, and 18.
	N. 0° 38' E., bet. secs. 7 and 8.
39.64	Point for the ¼ sec. cor. of secs. 7 and 8, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 5 S R 4 E ¼ S 7 | S 8 1982 Cor. is located on steep NW slope in scattered oak. Cor. is also located West, 50 lks. dist., from a steep rock slide.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
79.28	The cor. of secs. 5, 6, 7, and 8, monumented with a rebar, 1 in. diam., projecting 6 ins. above the ground, with evidence of use by local surveyors. This position is harmoniously related to existing original corners and a tie made by the Denver and Rio Grande Western R.R. Co. in 1945 to the original corner is in agreement with this position. From which the 1945 railroad ties: The station 60+83 of the Denver and Rio Grande Western R.R. Co., bears N. 78° 33' W., 2135.86 ft. dist., a nail and washer in the center of the rails. (Record, N. 78° 37' W., 2139.8 ft. dist.) obtained from the Right of Way Tract Map, Provo Canyon Branch, 0+00 to 199+25.5 dated July 2, 1945. At the corner point Set an aluminum post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base, to top of aluminum cap, mkd. T 5 S R 4 E S 6 | S 5 S 7 | S 8 1981 Cor. is located at the foot of the Deer Creek Dam, Provo Canyon, Utah.
	From the cor. of secs. 4, 5, 8, and 9. S. 88° 25' W., bet. secs. 5 and 8.
39.20	Point for the ¼ sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 5 S R 4 E S 5 ¼ S 8 1982 Cor. is located on steep NW slope in thick oak brush.
78.40	The cor. of secs. 5, 6, 7, and 8.
	S. 89° 07' W., bet. secs. 6 and 7.
7.50	Provo River, drains S.
14.50	U.S. Highway No. 189, bears N and S.
37.00	Denver and Rio Grande Western Railroad, bears N and S.
39.40	Point for the ¼ sec. cor. of secs. 6 and 7, at proportionate distance; there is no remaining evidence of the original corner.

☆U.S. Government Printing Office: 1980—778-251/292

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 5 S R 4 E ¼ S 6 / S 7 1981 Cor. is located on N slope in scattered sagebrush, oak and maple.
78.60	The cor. of secs. 6 and 7 only, on the W. bdy. of the Tp., hereinbefore described.
	Survey of the Subdivision of Section 31, T. 5 S., R. 4 E., Salt Lake Meridian, Utah
	From the ¼ sec. cor. of sec. 31 only, on the S. bdy. of the Tp., hereinbefore described. N. 0° 34' E., along the N and S center line of sec. 31.
36.77	Point selected for the witness cor. for the center ¼ sec. cor. of sec. 31. Set an iron post, 30 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd. T 5 S R 4 E W C ↑ C ¼ S 31 1970 Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.
36.87	Point for the center ¼ sec. cor. of sec. 31, at intersection with the E and W center line. This point falls in the South Fork of the Provo River, 15 lks. wide, and 20 ins. deep, course W, and is impractical to monument.
39.00	Graded road, bears WNW and ESE.
56.33	Point for the center N 1/16 sec. cor. of sec. 31. Set an iron post, 30 ins. long, 2½ ins. diam., 2 ins. in the ground to chiseled cross (X) on bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd. C-N 1/16 S 31 1970
75.78	The ¼ sec. cor. of secs. 30 and 31.
	From the ¼ sec. cor. of secs. 31 and 32. N. 88° 27' W., along the E and W center line of sec. 31.

115 Survey of the Subdivision of Section 31,
T. 5 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
16.01	Point selected for a witness point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. W P C S C 31 1970
19.185	Point for the center E 1/16 sec. cor. of sec. 31. Set an iron post, 30 ins. long, 2½ ins. diam., flush with the lawns surface, with brass cap mkd. C-E 1/16 S 31 1970 from which The NE cor. of a frame house, 54 x 28 ft., bears N. 6° 24' W., 252.7 lks. dist. An iron pipe, 1 in. diam., set in rock for a fountain, bears N. 56° 47' W., 186.6 lks. dist. Cor. is located in the lawn of a residential home.
23.00	Graded road, bears WNW and ESE.
38.37	The center ¼ sec. cor. of sec. 31.
57.11	Point for the center W 1/16 sec. cor. of sec. 31. Set an iron post, 30 ins. long, 2½ ins. diam., flush with the ground surface, with brass cap mkd. C-W 1/16 S 31 1970 from which The NW cor. of a frame house, 29 x 24 ft., bears N. 62° E., 9 lks. dist. The SW cor. of the same house, bears S. 47° 37' E., 38.7 lks. dist. The most easterly cor. of a shed, bears S. 80° 45' W., 23 lks. dist. An iron pipe, 2 ins. diam., firmly set in concrete, 10 ins. diam., projecting 14 ins. above the ground, bears N. 32° 55' W., 13.56 chs. dist., with brass cap, mkd. STATION ONE with a cross (X) in the center.
76.32	The ¼ sec. cor. of sec. 31 only, on the W. bdy. of the Tp., hereinbefore described.

☆U.S. Government Printing Office: 1980—778-251/292

Survey of the Subdivision of Section 31,
T. 5 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	From the center E 1/16 sec. cor. of sec. 31.
	N. 0° 16' E., along the N and S center line of the NE¼ of sec. 31.
19.21	Point for the NE 1/16 sec. cor. of sec. 31, at intersection with the E and W center line of the NE¼.
	Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	N-E 1/16 S 31 1970
	Raise a mound of stone, 2½ ft. base, 2 ft. high, W of cor.
38.43	The E 1/16 sec. cor. of secs. 30 and 31.
	From the N 1/16 sec. cor. of secs. 31 and 32.
	N. 87° 45' W., along the E and W center line of the NE¼ of sec. 31.
19.08	The NE 1/16 sec. cor. of sec. 31.
38.16	The center N 1/16 sec. cor. of sec. 31.
	From the W 1/16 sec. cor. of sec. 31 only, on the S. bdy. of the Tp.
	N. 1° 36' E., along the N and S center line of the SW¼ of sec. 31.
37.44	The center W 1/16 sec. cor. of sec. 31.
	From the center W 1/16 sec. cor. of sec. 31.
	N. 0° 15' E., along the N and S center line of the NW¼ of sec. 31.
17.00	South Fork Provo River, drains NW.
18.50	Graded road, bears NW and SE.
19.69	Point for the NW 1/16 sec. cor. of sec. 31, at intersection with the E and W center line of the NW¼.
	Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	NW 1/16 S 31 1970
	Set an oak post, 4 ins. diam., 5 ft. long, alongside the iron post.
	Cor. is located on steep S slope.
39.38	The W 1/16 sec. cor. of secs. 30 and 31.

117

Survey of the Subdivision of Section 31,
T. 5 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	From the center N 1/16 sec. cor. of sec. 31.
	N. 87° 45' W., along the E and W center line of the NW¼ of sec. 31.
18.86	The NW 1/16 sec. cor. of sec. 31.
20.00	Graded road, bears NW and SE.
21.00	South Fork Provo River, drains NW.
38.24	The N 1/16 sec. cor. of sec. 31 only, on the W. bdy. of the Tp.

Survey of the Subdivision of Section 32,
T. 5 S., R. 4 E., Salt Lake Meridian, Utah

	From the ¼ sec. cor. of sec. 32 only, on the S. bdy. of the Tp., hereinbefore described.
	N. 1° 37' E., along the N and S center line of sec. 32.
16.19	Point for the center S 1/16 sec. cor. of sec. 32.
	Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd. C-S 1/16 S 32 1970
	from which
	A juniper, 18 ins. diam., bears S. 51° E., 23 lks. dist., mkd. C-S 1/16 S32 BT.
	A juniper, 14 ins. diam., bears N. 65° W., 25 lks. dist., mkd. X BT.
35.40	Point for the center ¼ sec. cor. of sec. 32, at intersection with the E and W center line.
	Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd. T 5 S R 4 E C ¼ S 32 1970
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.
	Cor. is located on steep N slope.
73.63	The ¼ sec. cor. of secs. 29 and 32.
	From the ¼ sec. cor. of secs. 32 and 33.
	N. 89° 40' W., along the E and W center line of sec. 32.

☆U.S. Government Printing Office: 1980—778-251/292

Survey of the Subdivision of Section 32,
T. 5 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
39.49	The center ¼ sec. cor. of sec. 32.
59.29	Point for the center W 1/16 sec. cor. of sec. 32.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. C-W 1/16 S 32 1970
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.
	Cor. is located on steep NW slope.
79.09	The ¼ sec. cor. of secs. 31 and 32.
	From the W 1/16 sec. cor. of secs. 32 only, on the S. bdy. of the Tp., hereinbefore described.
	N. 0° 47' E., along the N and S center line of the SW¼ of sec. 32.
4.00	South Fork Provo River, drains NW.
6.00	Graded road, bears NW and SE.
16.53	Point for the SW 1/16 sec. cor. of sec. 32, at intersection with the E and W center line.
	Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 2½ ft. base, to top of brass cap, mkd. SW 1/16 S 32 1970
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.
	From this cor., a rebar, ½ in. diam., firmly set and projecting 1 in. above the ground, bears N. 39° 47' E., 56.7 lks. dist.
35.63	The center W 1/16 sec. cor. of sec. 32.
	From the center S 1/16 sec. cor. of sec. 32.
	N. 89° 20' W., along the E and W center line of the SW¼ of sec. 32.
19.51	The SW 1/16 sec. cor. of sec. 32.
29.00	Graded road, bears WNW and SE.
33.00	South Fork Provo River, drains NW.
39.00	The S 1/16 sec. cor. of secs. 31 and 32.

CHAINS	
	Dependent Resurvey of Parcel A, Located in Sec. 32, T. 5 S., R. 4 E., Salt Lake Meridian, Utah
	From Angle Point No. 1, monumented with a wooden fence post in corner of fences, extending NE and SW. No additional monuments established.
	from which
	The S 1/16 sec. cor. of secs. 31 and 32, bears S. 59° 07' W., 5.84 chs. dist.
	S. 68° 01' E., along line 1 and 2.
	Along fence on the N right of way of county road.
4.58	Angle Point No. 2, monumented with a wooden fence post. No additional monument established.
	Thence, N. 4° 44' W., along line 2 and 3.
	Along fence.
3.09	Angle Point No. 3, monumented with a wooden fence post. No additional monuments established.
	Thence, N. 66° 37' W., along line 3 and 4.
	Along fence.
2.61	Angle Point No. 4, monumented with a wooden fence post. No additional monuments established.
	Thence S. 33° 47' W., along line 4 and 1.
	Along fence.
2.88	Angle Point No. 1, the point of beginning.
	General Description
	The land encompassed in this survey is located in the foothills and mountains of Provo Canyon and Wallsburg Ridge area, Utah and Wasatch Counties, Utah. For the most part the land is in the Uinta National Forest, with the elevation ranging from 5,240± in sec. 18 to 9,150 ft. in sec. 35.
	Generally speaking the terrain is mountainous particularly in the center of the township. The terrain on either side of the Wallsburg Ridge is steep, rolling hills covered with thick oak brush. The higher elevations have aspen, pine, and spruce generating into high alpine vegetation.
	Drainage is in all directions from the Wallsburg Ridge, draining into the Provo River drainage.
	U.S. Highway No. 189, runs northeasterly through this township. The highway traverses through secs. 3, 4, 5, 6, 7, and 18. A county road, along the South Fork of the Provo River, traverses through secs. 30 and 31, exiting the township in sec. 32. There are numerous dirt roads used for access by stockmen.

☆U.S. Government Printing Office: 1980—778-251/292

T. 5 S., R.4 E., Salt Lake Meridin, Utah

CHAINS	
	The principle use of this area is for recreation by hunters, campers, fishermen, and picnickers. Sheep are grazed during the summer months. There are numerous homes along the Provo River and the South Fork of the Provo River. The mean of a considerable number of observations of the magnetic declination is 15° 30' E.

Form 9600-11
(August 1979)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Frank C. Profaizer	Surveying Technician
Douglas A. Cody	Surveying Technician
Barry B. Babbitt	Surveying Technician
Julian J. Cordova	Surveying Technician
Michael K. Davis	Survey Aid
Patrick E. Dawson	Survey Aid
Emanuel Ehrlich	Survey Aid
Everett E. Gorgen	Survey Aid
Lon G. Hill	Survey Aid
Ronald E. Lorensen	Survey Aid
William L. McDorman	Survey Aid
Alan N. Pike	Survey Aid
Donald J. Stathis, Jr.	Survey Aid
Charles C. Stevens	Survey Aid
Victor E. Templeton	Survey Aid
Roy J. Vincent	Survey Aid
Gary Gogos	Student Surveying Technician
Rex Smith	Surveying Technician
Peter Coffey	Surveying Technician
John Mavor	Survey Aid
John Zwhalen	Surveying Technician
Jeff Peyton	Surveying Technician
Donzil Q. Worthington	Surveying Technician
Terry Christensen	Surveying Technician

122

CERTIFICATE OF SURVEY

~~(I)~~ (We), Ray Harpin and Donald A. Buhler, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 11th day of August, 1969, ~~(I)~~ (We) have dependently resurveyed the First Standard Parallel South, through a portion of Range 4 East, and a portion of the west boundary, a portion of the subdivisional lines and surveyed certain sections and parcels of T. 5 S., R. 4 E.,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by ~~(me)~~, (us) and under ~~(my)~~ (our) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

May 4, 1983 — Ray Harpin
(Date) — (Cadastral Surveyor)
Supervisory

May 4, 1983 — Donald A. Buhler
(Date) — (Cadastral Surveyor)
Supervisory

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Denver, Colorado

The foregoing field notes of the dependent resurvey of the First Standard Parallel South, through a portion of Range 4 East, and a portion of the west boundary, a portion of the subdivisional lines and the survey of certain sections and parcels of T. 5 S., R. 4 E. of Salt Lake Meridian, Utah

executed by Ray Harpin and Donald A. Buhler, Supervisory Cadastral Surveyors having been critically examined and found correct, are hereby approved.

August 15, 1983 — Glen B. Hatch
(Date) — ~~(Chief, Cadastral Survey Examination and Approval Staff)~~
Chief Cadastral Surveyor for Utah

~~CERTIFICATE OF TRANSCRIPT~~

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

~~(Date)~~ — ~~(Chief, Cadastral Survey Examination and Approval Staff)~~
Chief Cadastral Surveyor for Utah

GPO 852-326

Form 9600–9
(December 1979)
(formerly 9180–6)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

R606

ORIGINAL

FIELD NOTES

123

OF THE

DEPENDENT RESURVEY

OF

A PORTION OF THE SUBDIVISIONAL LINES

AND

THE SURVEY OF

THE SUBDIVISION OF CERTAIN SECTIONS AND TRACTS

OF

TOWNSHIP 6 SOUTH, RANGE 4 EAST

Of the Salt Lake Meridian,

In the State of Utah.

EXECUTED BY

Ray Harpin Cadastral Surveyor

Donald A. Buhler Cadastral Surveyor

Under special instructions dated August 11, 19 69, approved August 15, 1969,

, which provided for the surveys included under U.S. Survey/Group

Number 513, and assignment instructions dated August 11, 19 69.

and October 10, 1979

Survey commenced August 11, 19 69

Survey completed June 25, 19 82

INDEX DIAGRAM

Township 6 South, Range 4 East,

6 15 14	5 8 13	4 5 8	3 2 5	2	1
7 12 11	8 7 10	9 4 7	10 1 3	11	12
18	17 6	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Section 37 - Page 18
Section 39 - Page 21
Subdivision of Sec. 5 - Page 21
Subdivision of Sec. 6 - Page 25
Tract 48 - Page 27
Tract 49 - Page 30

GPO 855-927

Township 6 South, Range 4 East, Salt Lake Meridian, Utah

CHAINS

The following field notes describe the dependent resurvey of a portion of the subdivisional lines and the survey of the subdivision of certain sections and tracts of Township 6 South, Range 4 East of the Salt Lake Meridian, Utah.

The subdivisional lines were surveyed by Scott P. and John R. Stewart in 1900.

The resurvey was executed in accordance with the specifications set forth in the Manuals of Surveying Instructions, 1947 and 1973, and the Special Instructions for Group No. 513, Utah, dated August 11, 1969.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The direction of lines were determined by solar and Polaris observations and were carried forward by sustained angulation.

The geographic position of the southeast corner of section 10 as calcuated from a tie to the U.S. Coast and Geodetic Survey station "Hobble" located in section 36, T. 5 S., R. 4 E., is as follows:

Latitude 40° 18' 14.61" N. Longitude 111° 27' 39.28" W.

The mean magnetic declination is 15° 30' E.

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 6 S., R. 4 E., Salt Lake Meridian, Utah

---

Beginning at the cor. of secs. 10, 11, 14, and 15, monumented with a quartzite stone, 14 x 8 x 7 ins., dimly mkd. 2 notches on S edge and embedded in the ground with a scattered mound of stone W of cor.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 6 S R 4 E
S 10 | S 11
S 15 | S 14
1982

Deposit the mkd. stone alongside the aluminum post.

Cor. is located on E slope, 2 chs. dist. east of a ridge, bears NW and SE.

N. 1° 05' W., bet. secs. 10 and 11.

40.55 The ¼ sec. cor. of secs. 10 and 11, monumented with a quartzite stone, 18 x 10 x 6 ins., plainly mkd. ¼ on W face, firmly set 10 ins. in the ground, from which the original bearing trees

126

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 6 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS

An aspen, 10 ins. diam., bears East, 14 lks. dist., mkd. with a healed blaze (rescribe ¼ S11 BT).

An aspen, 10 ins. diam., bears N. 40° W., 28 lks. dist., mkd. with a healed blaze (rescribe ¼ S10 BT).

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 6 S R 4 E
¼
S 10 | S 11
1982

Deposit the mkd. stone alongside the aluminum post.

Cor. is located on N slope in thick aspen.

N. 0° 43' E., beginning new measurement.

39.87 The cor. of secs. 2, 3, 10, and 11, monumented with a sandstone, 18 x 10 x 6 ins., plainly mkd. 5 notches on S edge and 2 notches on E edge, firmly set in a mound of stone, 2½ ft. base.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 6 S R 4 E
S 3 | S 2
S 10 | S 11
1981

Deposit the mkd. stone alongside the aluminum post.

Cor. is located on N slope in scattered oak, aspen and maple.

N. 2° 55' W., bet. secs. 2 and 3.

40.10 Point for the ¼ sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 6 S R 4 E
¼
S 3 | S 2
1982

Cor. is located on S slope in thick oak brush.

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 6 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
86.51	Point for the closing cor. of secs. 2 and 3, at intersection with the First Standard Parallel South and at proportionate distance; there is no remaining evidence of the original corner.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.
	T 5 S R 4 E S 3 | S 2 C | C T 6 S R 4 E 1982
	Cor. is located on SW slope in scattered oak brush.
	From this cor., the angle point bet. secs. 3 and 35 on the First Standard Parallel South, bears S. 89° 35' W., 33.23 chs. dist., set, mkd. and described in the concurrent resurvey of T. 5 S., R. 4 E.
	From this same cor., the point for the angle point bet. secs. 2 and 35, on the First Standard Parallel South, bears N. 89° 35' E., 6.33 chs. dist., described in the concurrent resurvey of T. 5 S., R. 4 E.
	From the cor. of secs. 10, 11, 14, and 15.
	N. 89° 33' W., bet. secs. 10 and 15.
41.12	The ¼ sec. cor. of secs. 10 and 15, monumented with a quartzite stone, 12 x 8 x 6 ins., faintly mkd. ¼ on N face, embedded in a mound of stone, 3 ft. base.
	At the corner point
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.
	T 6 S R 4 E S 10 ¼ S 15 1982
	Deposit the mkd. stone alongside the aluminum post.
	Cor. is located on W slope in scattered oak and aspen.
	N. 89° 53' W., beginning new measurement.
39.27	The cor. of secs. 9, 10, 15, and 16, monumented with a quartzite stone, 18 x 10 x 9 ins., dimly mkd. 3 notches on E edge and 2 notches on S edge, firmly set 9 ins. in the ground.
	At the corner point

Dependent Resurvey of a Portion of the Subdivisional Lines
of T. 6 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS

Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with aluminum cap mkd.

T 6 S R 4 E
S 9 | S 10
S 16 | S 15
1982

Cor. is located on NNE slope about 2 chs. dist. W of draw that drains NNE.

N. 0° 10 E., bet. secs. 9 and 10.

39.62 The ¼ sec. cor. of secs. 9 and 10, monumented with a quartzite stone, 18 x 14 x 6 ins., plainly mkd. ¼ on W face, set 5 ins. in the ground.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 6 S R 4 E
¼
S 9 | S 10
1982

from which

An aspen, 7 ins. diam., bears N. 73° E., 61.5 lks. dist., mkd. ¼ S10 BT.

An aspen, 6 ins. diam., bears N. 61° W., 61 lks. dist., mkd. ¼ S9 BT.

Deposit the mkd. stone alongside the aluminum post.

Cor. is located 61 lks. W and S of dry creek, draining NW.

N. 0° 16' E., beginning new measurement.

40.13 Point for the cor. of secs. 3, 4, 9, and 10, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 3½ ft. base, to top of aluminum cap, mkd.

T 6 S R 4 E
S 4 | S 3
S 9 | S 10
1982

Cor. is located on SW slope in scattered oak.

Dependent Resurvey of a Portion of the Subdivisional Lines
of T. 6 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	From the cor. of secs. 2, 3, 10, and 11.
	S. 89° 22' W., bet. secs. 3 and 10.
40.28	The ¼ sec. cor. of secs. 3 and 10, monumented with a sandstone, 15 x 8 x 8 ins., plainly mkd. ¼ on N face, firmly set 10 ins. in the ground.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T 6 S R 4 E ¼ S 3 / S 10 1981
	Deposit the mkd. stone alongside the iron post.
	Cor. is located on NW slope in thick maple.
	N. 89° 44' W., beginning new measurement.
39.53	The cor. of secs. 3, 4, 9, and 10.
	N. 2° 08' W., bet. secs. 3 and 4.
40.16	Point for the ¼ sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T 6 S R 4 E ¼ S 4 | S 3 1982
	Cor. is located on S slope in scattered oak brush and about 1.5 chs. dist., south of a ridge, extending E and W.
86.71	Point for the closing cor. of secs. 3 and 4, at intersection with the First Standard Parallel South, at proportionate distance; there is no remaining evidence of the original corner.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.
	T 5 S S 4 | S 3 C C T 6 S R 4 E 1982
	Cor. is located on SW slope in scattered oak brush.

CHAINS

From this cor., the angle point bet. secs. 3 and 34, on the First Standard Parallel South, bears S. 89° 23' E., 6.27 chs. dist., set, mkd. and described in the concurrent resurvey of T. 5 S., R. 4 E.

From this same cor., the angle point bet. secs. 4 and 34, on the First Standard Parallel South, bears N. 89° 23' W., 33.69 chs. dist., set, mkd. and described in the concurrent resurvey of T. 5 S., R. 4 E.

Point for the ¼ sec. cor. of sec. 3 only, on the First Standard Parallel South, is at midpoint on the N. bdy. of sec. 3.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a mound of stone, 3½ ft. base, to top of aluminum cap, mkd.

T 5 S

¼ S 3

T 6 S R 4 E

1981

Cor. is located on SW slope in scattered oak brush.

From this cor., the angle point bet. secs. 3 and 35, on the First Standard Parallel South, bears S. 89° 45' E., 6.08 chs. dist., set, mkd. and described in the concurrent resurvey of T. 5 S., R. 4 E.

From this same cor., the angle point bet. secs. 3 and 34, on the First Standard Parallel South, bears N. 89° 45' W., 33.01 chs. dist., set, mkd. and described in the concurrent resurvey of T. 5 S., R. 4 E.

From the cor. of secs. 16, 17, 20, and 21, as determined from an original bearing tree

An aspen, 10 ins. diam., bears N. 40° E., 50 lks. dist., mkd. BT with a healed blaze.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 6 S R 4 E

S 17	S 16
S 20	S 21

1982

from which

A spruce, 8 lks. diam., bears N. 14° 30' W., 32.2 lks. dist., mkd. T6S R4E BT.

Cor. is located on NW slope in aspen and pine.

N. 0° 40' E., bet. secs. 16 and 17.

39.96 Point for the ¼ sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original corner.

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 6 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 6 S R 4 E ¼ S 17 | S 16 1982 Cor. is located on NW slope in aspen.
79.92	Point for the cor. of secs. 8, 9, 16, and 17, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 6 S R 4 E S 8 | S 9 S 17 | S 16 1982 Cor. is located on N slope in scattered oak and maple.
	From the cor. of secs. 9, 10, 15, and 16. S. 89° 46' W., bet. secs. 9 and 16.
39.90	Point for the ¼ sec. cor. of secs. 9 and 16, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 6 S R 4 E S 9 ¼ S 16 1982 Cor. is located on SE slope in oak, maple and aspen.
79.80	The cor. of secs. 8, 9, 16, and 17.
	N. 0° 40' E., bet. secs. 8 and 9.
39.96	Point for the ¼ sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 6 S R 4 E ¼ S 8 | S 9 1982 Cor. is located on SE slope in scattered oak brush.

CHAINS	
79.92	The cor. of secs. 4, 5, 8, and 9, monumented with a sandstone, 18 x 10 x 6 ins., faintly mkd. 2 notches on E edge and 1 notch on S edge, firmly set 6 ins. in the ground, with a scattered mound of stone, 2 ft. base, 1 ft. high, W of cor. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd. T 6 S R 4 E S 5 | S 4 S 8 | S 9 1982 Deposit the mkd. stone in mound of stone. Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	From the cor. of secs. 3, 4, 9, and 10. S. 89° 53' W., bet. secs. 4 and 9.
39.58	Point for the ¼ sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 6 S R 4 E ¼ S 4 S 9 1982 Cor. is located on steep N slope in aspen, oak, pine and maple.
79.16	The cor. of secs. 4, 5, 8, and 9.
	N. 0° 30' W., bet. secs. 4 and 5.
10.04	Point for the S - S 1/64 sec. cor. of secs. 4 and 5. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. S-S 1/64 S 5 | S 4 1970 Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor. Cor. is located on steep NE slope in dense oak and maple brush.
20.08	Point for the S 1/16 sec. cor. of secs. 4 and 5. Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines
of T. 6 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	S 1/16 S 5 | S 4 1970
32.99	Point for Angle Point No. 11 of Tract 48, hereinafter described.
40.16	The ¼ sec. cor. of secs. 4 and 5, identical with Angle Point No. 12 of Tract 48, monumented with a sandstone, 16 x 8 x 6 ins., faintly mkd. ¼ on W face, firmly set 6 ins. in the ground, with a scattered mound of stone, 2½ ft. base, 1 ft. high, W of cor. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 2½ ft. base, to top of brass cap, mkd. T 6 S R 4 E ¼ S 5 | S 4 1970 Deposit the mkd. stone in mound of stone. Raise a mound of stone, 2½ ft. base, 1 ft. high, W of cor. N. 3° 22' W., beginning new measurement.
20.03	Point for the N 1/16 sec. cor. of secs. 4 and 5. Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd. N 1/16 S 5 | S 4 1970 from which A spruce, 19 ins. diam., bears S. 2½° W., 106 lks. dist., mkd. N 1/16 S5 BT. Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor. Cor. is located on steep N slope.
38.33	Angle Point No. 4 of the Private Land Claim survey of Moses H. Draper, identical with sec. 37, hereinafter described.
46.31	Point for the closing cor. of secs. 4 and 5, identical with Angle Point No. 1 of Tract 48, at intersection with the First Standard Parallel South, and at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

134

Dependent Resurvey of a Portion of the Subdivisional Lines
of T. 6 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	T 5 S S 33 S 5 | S 4 T 6 S | R 4 E C | C 1969 Raise a mound of stone, 2½ ft. base, 1½ ft. high, S of cor. Cor. is located on an open SE slope. From this cor., the angle point bet. secs. 5 and 33, identical with Angle Point No. 2 of Tract 48, on the First Standard Parallel South, bears S. 89° 06' W., 32.77 chs. dist., set, mkd. and described in the concurrent resurvey of T. 5 S., R. 4 E. From this same cor., the angle point bet. secs. 4 and 33, on the First Standard Parallel South, bears N. 89° 06' E., 6.20 chs. dist., described in the concurrent resurvey of T. 5 S., R. 4 E.
	Point for the ¼ sec. cor. of sec. 4 only, on the First Standard Parallel South is at midpoint on the N. bdy. of sec. 4. Set an aluminum post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4½ ft. base, to top of aluminum cap, mkd. T 5 ¼ S 4 T 6 S R 4 E 1981 Cor. is located on SE slope in scattered oak brush. From this cor., the angle point bet. secs. 4 and 34, on the First Standard Parallel South, bears N. 89° 06' E., 5.75 chs. dist., set, mkd. and described in the concurrent resurvey of T. 5 S., R. 4 E. From this same cor., the angle point bet. secs. 4 and 33, on the First Standard Parallel South, bears S. 89° 06' W., 33.22 chs. dist., described in the concurrent resurvey of T. 5 S., R. 4 E.
	From the cor. of secs. 8, 9, 16, and 17. S. 89° 31' W., bet. secs. 8 and 17.
39.78	Point for the ¼ sec. cor. of secs. 8 and 17, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 6 ft. base, to top of aluminum cap, mkd. T 6 S R 4 E ¼ S 8 S 17 1982 Cor. is located on rock outcrop projecting to the W.

Dependent Resurvey of a Portion of the Subdivisional Lines
of T. 6 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
79.56	The cor. of secs. 7, 8, 17, and 18, monumented with a sandstone, 18 x 8 x 5 ins., plainly mkd. 5 notches on E edge and 4 notches on S edge, firmly set in a small mound of stone, 1½ ft. base. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 6 S R 4 E S 7 | S 8 S 18 | S 17 1971 from which An aspen, 7 ins. diam., bears N. 47° E., 24 lks. dist., mkd. T6S R4E S8 BT. An aspen, 5 ins. diam., bears S. 16¼° E., 25 lks. dist., mkd. T6S R4E S17 BT. An aspen, 4 ins. diam., bears S. 79¼° W., 13½ lks. dist., mkd. X BT. An aspen, 5 ins. diam., bears N. 46¼ W., 19 lks. dist., mkd. T6S R4E S7 BT. Deposit the mkd. stone alongside the iron post. Raise a mound of stone, 2 ft. base, 1½ ft. high, W of cor.
	N. 89° 17' W., bet. secs. 7 and 18.
40.64	The ¼ sec. cor. of secs. 7 and 18, monumented with a limestone, 18 x 10 x 7 ins., faintly mkd. with a 4 on the N face, with a scattered mound of stone, N of cor. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. T 6 S R 4 E S 7 ¼ S 18 1974 from which A spruce, 8 ins. diam., bears South, 5 lks. dist., mkd. ¼ S18 BT. Deposit the mkd. stone in mound of stone. Raise a mound of stone, 2½ ft. base, 1½ ft. high, E of cor. Cor. is located on steep SE slope.
	N. 88° 55' W., beginning new measurement.

CHAINS	
56.88	Point for the 100-1/16 sec. cor. of secs. 7 and 18. Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground to bedrock, and in a mound of stone, 2½ ft. base, to top of brass cap, mkd. 1/16 S 7 / S 18 100 1974 from which A spruce, 3 ins. diam., bears S. 34¼° E., 26 lks. dist., mkd. X BT. A spruce, 7 ins. diam., bears S. 67° 45' W., 26 lks. dist., mkd. 1/16 S18 100 BT.
61.75	The closing cor. of secs. 7 and 18, on the W. bdy. of the Tp., set, mkd. and described in the concurrent resurvey of T. 6 S., R. 3 E. From this closing cor., the cor. of secs. 12 and 13, T. 6 S., R. 3 E., bears N. 0° 35' W., 7.87 chs. dist., set, mkd. and described in the concurrent resurvey of T. 6 S., R. 3 E.
	From the cor. of secs. 7, 8, 17, and 18. N. 0° 37' E., bet. secs. 7 and 8.
40.11	Point for the ¼ sec. cor. of secs. 7 and 8, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd. T 6 S R 4 E ¼ S 7 | S 8 1971 from which An aspen, 6 ins. diam., bears S. 49½° E., 56 lks. dist., mkd. ¼ S8 BT. An aspen, 6 ins. diam., bears S. 15½° W., 75 lks. dist., mkd. ¼ S7 BT.
60.165	Point for the N 1/16 sec. cor. of secs. 7 and 8. Set an iron post, 30 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd. N 1/16 S 7 | S 8 1971

CHAINS

from which

A rebar of unknown original, firmly set and projecting 4 ins. above the ground, bears N. 58° 51' E., 29 lks. dist.

A spruce, 8 ins. diam., bears S. 23° E., 23 lks. dist., mkd. ¼ S8 BT.

A pine, 8 ins. diam., bears S. 80½° W., 48 lks. dist., mkd. ¼ S7 BT.

80.22 The cor. of secs. 5, 6, 7, and 8, monumented with a rebar, 3/4 in. diam., firmly set flush with the ground. This position is accepted as the best available evidence of the original corner and is harmoniously related to existing corners.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

T 6 S R 4 E
S 6 | S 5
S 7 | S 8
1970

Deposit the rebar alongside the iron post.

Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.

From the cor. of secs. 4, 5, 8, and 9.

West, bet. secs. 5 and 8.

19.90 Point for the E 1/16 sec. cor. of secs. 5 and 8.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

E 1/16 S 5
S 8
1970

Raise a mound of stone, 3 ft. base, 1½ ft. high, N of cor.

39.80 The ¼ sec. cor. of secs. 5 and 8, monumented with a sandstone, 16 x 6 x 6 ins., plainly mkd. ¼ on N face, firmly set 6 ins. in the ground, with a mound of stone, 2 ft. base, 1 ft. high, N of cor.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.

T 6 S R 4 E
¼ S 5
S 8
1970

Deposit the mkd. stone in the mound of stone.

Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 6 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	Cor. is located on steep NE slope.
	S. 89° 28' W., beginning new measurement.
19.89	Point for the W 1/16 sec. cor. of secs. 5 and 8.
	Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.
	W 1/16 S 5 / S 8 / 1970
	Raise a mound of stone, 3 ft. base, 1½ ft. high, N of cor.
	Cor. is located on SW slope.
28.50	South Fork of Provo River, drains N.
30.00	Graded road, bears N and S.
39.78	The cor. of secs. 5, 6, 7, and 8.
	N. 89° 36' W., bet. secs. 6 and 7.
2.00	Point for Angle Point No. 8 of Tract 49, hereinafter described.
19.44	Point for the E 1/16 sec. cor. of secs. 6 and 7.
	Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.
	E 1/16 S 6 / S 7 / 1970
	Raise a mound of stone, 2½ ft. base, 2 ft. high, N of cor.
38.88	The ¼ sec. cor. of secs. 6 and 7, identical with Angle Point No. 7 of Tract 49, monumented with a sandstone, 14 x 10 x 8 ins., plainly mkd. ¼ on N face, set 3 ins. in the ground.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T 6 S R 4 E / ¼ S 6 / S 7 / 1970
	Deposit the mkd. stone alongside the iron post.
	Raise a mound of stone, 2½ ft. base, 2 ft. high, N of cor.
	S. 89° 43' W., beginning new measurement.
19.94	Point for the W 1/16 sec. cor. of secs. 6 and 7.

Dependent Resurvey of a Portion of the Subdivisional Lines
of T. 6 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. W 1/16 S 6 / S 7 / 1970 Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.
39.88	Point for the 80 1/16 sec. cor. of secs. 6 and 7. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. 1/16 S 6 / S 7 / 1970 80 from which A fir, 10 ins. diam., bears S. 55½° W., 17 lks. dist., mkd. X BT. A fir, 7 ins. diam., bears N. 41¼° W., 20 lks. dist., mkd. X BT.
59.82	Point for the 100 1/16 sec. cor. of secs. 6 and 7. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. 1/16 S 6 / S 7 / 1970 100 Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.
65.79	The closing cor. of secs. 6 and 7, at intersection with the W. bdy. of the Tp., set, mkd. and described in the concurrent resurvey of T. 6 S., R. 3 E. From this closing cor., the cor. of secs. 1 and 12, T. 6 S., R. 3 E., bears N. 1° 28' W., 8.53 chs. dist., set, mkd. and described in the concurrent resurvey of T. 6 S., R. 3 E.
	From the cor. of secs. 5, 6, 7, and 8. N. 0° 49' W., bet. secs. 5 and 6.
19.66	Point for the S 1/16 sec. cor. of secs. 5 and 6. Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd. S 1/16 S 6 | S 5 1970 from which The NE cor. of a small wooden saddle shed, bears S. 17° 05' W., 280.5 lks. dist. Deposit a wood gate post alongside the iron post.

140

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 6 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
37.25	The crossing closing cor. of secs. 5 and 6, at intersection with the Private Land Claim survey of James R. Hook, identical with sec. 38, monumented with a sandstone, 16 x 14 x 10 ins., set 6 ins. in the ground and mkd. CC JRH on top of stone. This cor. was not remonumented.
	N. 10° 00' E., beginning new measurement.
2.79	The ¼ sec. cor. of secs. 5 and 6, monumented with a sandstone, 16 x 10 x 4 ins., plainly mkd. ¼ on W face, firmly set in a mound of stone, 2½ ft. base, 1 ft. high.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 6 S R 4 E ¼ S 6 | S 5 1970
	Deposit the mkd. stone in mound of stone.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	N. 0° 22' E., beginning new measurement.
19.79	Point for the N 1/16 sec. cor. of secs. 5 and 6.
	Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.
	N 1/16 S 6 | S 5 1970
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.
31.00	South Fork of Provo River, drains NW.
36.50	Graded road, bears NW and SE.
45.91	The closing cor. of secs. 5 and 6, at intersection with the First Standard Parallel South, monumented with a concrete post, 6 x 6 ins., firmly set and projecting 4 ins. above the ground, with brass tablet, 2 ins. diam., mkd.
	UTAH COUNTY T 5 S R 4 E C C S 32 S 6 | S 5 1962 T 6 S R 4 E LAND SURVEY
	(A piece of stone mkd. 2 notches on an edge is found alongside the concrete post.)

CHAINS

From this cor., the angle point bet. secs. 5 and 32, on the First Standard Parallel South, bears N. 89° 35' E., 4.61 chs. dist., set, mkd. and described in the concurrent resurvey of T. 5 S., R. 4 E.

From this same cor., the angle point bet. secs. 6 and 32, identical with Angle Point No. 2 of Sec. 39, on the First Standard Parallel South, bears S. 89° 35' W., 34.17 chs. dist., set, mkd. and described in the concurrent resurvey of T. 6 S., R. 3 E.

Point for the ¼ sec. cor. of sec. 5 only, on the First Standard Parallel South, is at midpoint and on the N. bdy. of sec. 5.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

¼ S 5
T 6 S R 4 E
1969

Raise a mound of stone, 2½ ft. base, 1½ ft. high, S of cor.

From this cor., the angle point bet secs. 5 and 32, identical with Angle Point No. 2 of Tract 48, on the First Standard Parallel South, bears N. 89° 35' E., 5.31 chs. dist., set, mkd. and described in the concurrent resurvey of T. 5 S., R. 4 E.

From this same cor., point for angle point bet. secs. 5 and 32, on the First Standard Parallel South, bears S. 89° 35' W., 33.47 chs. dist., set, mkd. and described in the concurrent resurvey of T. 5 S., R. 4 E.

Point for the E 1/16 sec. cor. of sec. 5 only, on the First Standard Parallel South.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

E 1/16 S 5
1969

Raise a mound of stone, 3 ft. base, 1½ ft. high, S of cor.

From this cor., the closing cor. of secs. 4 and 5, identical with Angle Point No. 1 of Tract 48, on the First Standard Parallel South bears N. 89° 06' E., 19.04 chs. dist., hereinbefore described.

Angle Point No. 3 of Tract 48, identical to Angle Point No. 2 of the Private Land Claim survey of James R. Hooks, identical to sec. 38, monumented with a sandstone, 18 x 12 x 6 ins., plainly mkd. ∠2 JRH on the SW face and firmly set in the ground.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

142

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 6 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS

T 5 S R 4 E
S 32
S 38 | S 5
T 6 S
1970

Deposit the mkd. stone in mound of stone.

Raise a mound of stone, 2½ ft. base, 1½ ft. high, S of cor.

From this point, the closing cor. of secs. 5 and 6, on the First Standard Parallel South, bears S. 89° 35' W., 7.51 chs. dist., hereinbefore described.

Point for the ¼ sec. cor. of sec. 6 only on the First Standard Parallel South, at proportionate distance.

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of brass cap, mkd.

¼ S 6
T 6 S R 4 E
1969

From this cor., the angle point bet. secs. 6 and 32, identical with Angle Point No. 2 of sec. 39, on the First Standard Parallel South, bears N. 89° 57' E., 5.19 chs. dist., set, mkd. and described in the concurrent resurvey of T. 6 S., R. 3 E.

From this same cor., the closing cor. of secs. 1 and 6, on the First Standard Parallel South, bears S. 89° 57' W., 65.44 chs. dist., set, mkd. and described in the concurrent resurvey of T. 6 S., R. 3 E.

Point for the W 1/16 sec. cor. of sec. 6, only, on the First Standard Parallel South.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16 S 6
1969

From this cor., the ¼ sec. cor. of sec. 6 only, on the First Standard Parallel South, bears N. 89° 57' E., 19.58 chs. dist., hereinbefore described.

Dependent Resurvey of Section 37, Located in Sec. 5, T. 6 S., R. 4 E., Salt Lake Meridian, Utah

---

From Angle Point No. 1 of the Private Land Claim survey of Moses H. Draper, identical to sec. 37, monumented with a quartzite stone, 9 x 8 x 4 ins., above the ground, firmly set, plainly mkd. BEG COR 1 MHD, with a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.

Dependent Resurvey of Section 37, Located in Sec. 5,
T. 6 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	Thence
	S. 89° 57' W., along line 1 - 2 of sec. 37.
10.00	Angle Point No. 2 of sec. 37, identical to Angle Point No. 3 of the Private Land Claim survey of James R. Hooks, identical to sec. 38, monumented with a sandstone, 10 x 8 x 8 ins., above the ground, firmly set and plainly mkd. ∠2 MHD on the E face and ∠3 JRH on the W face, with a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.
	Cor. is located at the cor. of a fence, extending N and E.
	A power pole, bears South 2 ft. dist.
	Thence
	N. 0° 11' W., along line 2 - 3 of sec. 37.
1.00	Graded road, bears NE and SW.
1.50	South Fork of Provo River, drains NE.
2.79	Intersect the E and W center line of sec. 5 at a point from which the ¼ sec. cor. of secs. 5 and 6, bears S. 89° 40' W., 7.96 chs. dist., hereinafter described.
32.00	Graded road, bears SSE and NW, and South Fork of Provo River, drains W.
40.17	Point for Angle Point No. 3 of sec. 37, identical with Angle Point No. 4 of Tract 48, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of brass cap, mkd.
	T 6 S R 4 E TR 48 AP 4 S 38 | S 37 1970
	From this point, Angle Point No. 2 of sec. 38, bears N. 0° 11' W., 8.54 chs. dist., hereinafter described.
	Thence
	N. 88° 53' E., along line 3 - 4 of sec. 37.
30.68	Point for the crossing closing cor. at intersection with the N and S center line of sec. 5.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 6 S R 4 E C S | 5 C | C C S 37 1971

144

Dependent Resurvey of Section 37, Located in Sec. 5,
T. 6 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.
49.10	Angle Point No. 5 of Tract 48, hereinafter described.
69.10	Angle Point No. 4 on the section line bet. secs. 4 and 5, monumented with a sandstone, 12 x 10 x 5 ins., above the ground, firmly set and plainly mkd. ∠ 4½ M MHD, with a mound of stone, 2½ ft. base, 1½ ft. high, SW of cor.
	Thence
	S. 1° 28' E., along line 4 - 5 of sec. 37.
20.00	Point for Angle Point No. 5, determined by the Grant Boundary Method; there is no remaining evidence of the original corner.
	Monument the cor. point with a mound of stone, 2 ft. base, 1½ ft. high.
	Thence
	S. 88° 32' W., along line 5 - 6 of sec. 37.
20.00	Point for Angle Point No. 6 of Tract 48, hereinafter described.
38.62	Point for the crossing closing cor. at intersection with the N and S center line of sec. 5.
	Set an iron post, 30 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.

T 6 S R 4 E
S 37
C
CC | AP 7
S 5 | TR 48
C
1971

from which

A chokecherry, 8 ins. diam., bears S. 74° E., 156 lks. dist., mkd. S37 CC BT.

A maple, 12 ins. diam., bears S. 17° 30' W., 25 lks. dist., mkd. S5 CC BT.

Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.

This cor. also functions as Angle Point No. 7 of Tract 48.

60.00 Point for Angle Point No. 6, determined by the Grant Boundary Method; there is no remaining evidence of the original corner. Not monumented.

Thence

S. 1° 28' E., along line 6 - 1 of sec. 37.

Dependent Resurvey of Section 37, Located in Sec. 5,
T. 6 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
17.16	Intersect the E and W center line of sec. 5, at a point from which the center W 1/16 sec. cor. bears N. 89° 40' E., 1.69 chs. dist., hereinafter described.
20.00	Angle Point No. 1 and point of beginning

Dependent Resurvey of a Portion of Section 39,
T. 6 S., R. 4 E., Salt Lake Meridian, Utah

From the mile post No. 1 of the Private Land Claim survey of James H. Snyder, identical to sec. 39, monumented with a sandstone, 12 x 10 x 6 ins., above the ground, firmly set and mkd. JHS 1 M on the W face, with a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.

Thence

S. 0° 09' E., along line 2 - 3 of sec. 39.

6.00	Angle Point No. 2 of Tract 49, at intersection with the E and W center line of the SE ¼ of sec. 6, hereinafter described.

From this point the center S 1/16 sec. cor. of sec. 6, bears N. 89° 26' W., 5.56 chs. dist., hereinafter described.

9.76	Angle Point No. 3 of Tract 40, hereinafter described.
19.76	Angle Point No. 3 of sec. 39, monumented with a sandstone, 18 x 9 x 6 ins., firmly set 10 ins. in the ground and mkd. ∠3 JHS on the NW face, with a mound of stone, 3 ft. base, 2 ft. high, W of cor.

Thence

N. 89° 29' W., along line 3 - 4 of sec. 39.

5.56	Angle Point No. 6 of Tract 49, at intersection with the N and S center line of sec. 6, hereinafter described.

From this point the ¼ sec. cor. of secs. 6 and 7, bears S. 0° 09' E., 6.00 chs. dist., hereinafter described.

10.00	Angle Point No. 5 of Tract 49, hereinafter described.
20.29	Angle Point No. 4, identical to mile post 1½ of sec. 39, monumented with a quartzite stone, 30 x 10 x 8 ins., firmly set in a mound of stone, 2½ ft. base, 2 ft. high, and plainly mkd. ∠4 ½ JHS on the N face.

Survey of the Subdivision of Section 5,
T. 6 S., R. 4 E., Salt Lake Meridian, Utah

From the ¼ sec. cor. of secs. 5 and 8.

N. 0° 55' W., along the N and S center line of sec. 5.

19.945	Point for the center S 1/16 sec. cor. of sec. 5.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

CHAINS	
	C | S 1/16 | S 5 | C 1971
	from which
	An oak, 5 ins. diam., bears S. 81° 45' E., 156 lks. dist., mkd. X BT.
	An oak, 9 ins. diam., bears S. 0° 45' E., 124 lks. dist., mkd. C-S 1/16 S5 BT.
	Cor. is located on N slope on S edge of hay meadow.
37.72	Point for Angle Point No. 8 of Tract 48, hereinafter described.
39.89	Point for the center ¼ sec. cor. of sec. 5, at intersection with the E and W center line of sec. 5.
	Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd.
	T 6 S R 4 E C ¼ S 5 1971
	Cor. is located on steep S slope.
57.48	Point for the crossing closing cor. at intersection with line 5 - 6 of sec. 37, identical with Angle Point No. 7 of Tract 48, hereinbefore described.
77.73	Point for the crossing closing cor. at intersection with line 3 - 4 of sec. 37, hereinbefore described.
85.89	The ¼ sec. cor. of sec. 5 only, on the First Standard Parallel South.
	From the ¼ sec. cor. of secs. 4 and 5, identical with Angle Point No. 12 of Tract 48.
	S. 89° 40' W., along the E and W center line of sec. 5.
20.04	Point for the center E 1/16 sec. cor. of sec. 5.
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top of brass cap, mkd.
	E 1/16 C ——— C S 5 1971
	from which
	A juniper, 4 ins. diam., bears N. 73½° E., 57 lks. dist., mkd. X BT.
	A juniper, 7 ins. diam., bears N. 46° 45' W., 89 lks. dist., mkd. C-E 1/16 S5 BT.

Survey of the Subdivision of Section 5,
T. 6 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
40.08	The center ¼ sec. cor. of sec. 5.
59.67	Point for the center W 1/16 sec. cor. of sec. 5.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. C-W 1/16 S 5 1971
	from which
	A maple, 6 ins. diam., bears N. 48° E., 25 lks. dist., mkd. C-W 1/16 S5 BT.
	A maple, 4 ins. diam., bears S. 8½° E., 12 lks. dist., mkd. X BT.
61.36	Intersect line 1 - 6 of sec. 37. Not monumented.
70.00	Graded road, bears N and S, and South Fork of Provo River, drains N.
71.30	Intersect the boundary bet. secs. 37 and 38. Not monumented.
79.26	The ¼ sec. cor. of secs. 5 and 6.
	From the E 1/16 sec. cor. of secs. 5 and 8.
	N. 0° 45' W., along the N and S center line of the SE¼ of sec. 5.
10.005	Point for the center South SE 1/64 sec. cor. of sec. 5.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. C-S-SE 1/64 S 5 1971
	from which
	An oak, 4 ins. diam., bears S. 89° W., 27 lks. dist., mkd. X BT.
	A maple, 5 ins. diam., bears N. 40° W., 44 lks. dist., mkd. C-S-SE 1/64 S5 BT.
20.01	Point for the SE 1/16 sec. cor. at intersection with the E and W center line of the SE¼ of sec. 5.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. SE 1/16 S 5 1971
	from which
	An oak, 4 ins. diam., bears S. 77° 45' E., 27 lks. dist., mkd. X BT.

148

Survey of the Subdivision of Section 5,
T. 6 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	A maple, 4 ins. diam., bears S. 54½° W., 6 lks. dist., mkd. SE 1/16 S5 BT.
32.85	Point for Angle Point No. 10 of Tract 48, hereinafter described.
37.85	Point for Angle Point No. 9 of Tract 48, hereinafter described.
40.02	The center E 1/16 sec. cor. of sec. 5.
	From the S 1/16 sec. cor. of secs. 4 and 5.
	S. 89° 47' W., along the E and W center line of the SE¼ of sec. 5.
19.97	The SE 1/16 sec. cor. of sec. 5.
39.94	The center S 1/16 sec. cor. of sec. 5.
	From the SS 1/64 sec. cor. of secs. 4 and 5.
	S. 89° 54' W., along the E and W center line of the SE¼ of the SE¼.
19.94	The center South SE 1/64 sec. cor. of sec. 5.
	From the W 1/16 sec. cor. of secs. 5 and 8.
	N. 0° 30' W., along the N and S center line of the SW¼ of sec. 5.
19.81	Point for the SW 1/16 sec. cor. at intersection with the E and W center line of the SW¼ of sec. 5.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. SW 1/16 S 5 1971
39.94	The center W 1/16 sec. cor. of sec. 5.
	From the center S 1/16 sec. cor. of sec. 5.
	S. 89° 03' W., along the E and W center line of the SW¼ of sec. 5.
19.75	The SW 1/16 sec. cor. of sec. 5.
37.00	South Fork of Provo River, drains N.
39.00	Graded road, bears N and S.
39.75	The S 1/16 sec. cor. of secs. 5 and 6.

Survey of the Subdivision of Section 6,
T. 6 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	From the ¼ sec. cor. of secs. 6 and 7, identical with Angle Point No. 7 of Tract 49.
	N. 0° 09' W., along the N and S center line of sec. 6.
6.00	Intersect line 3 and 4 of sec. 39, identical to Angle Point No. 6 of Tract 49, hereinafter described.
16.00	Intersect line 3 and 4 of Tract 49, hereinafter described.
19.765	Point for the center S 1/16 sec. cor. of sec. 6.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	C S 1/16 | S 6 C 1971
	Raise a mound of stone, 3 ft. base, 2½ ft. high, W of cor.
39.53	Point for the center ¼ sec. cor. of sec. 6, at intersection with the E and W center line of sec. 6.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 6 S R 4 E C ¼ S 6 1971
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	Cor. is located on steep W slope.
85.39	The ¼ sec. cor. of sec. 6 only, on the First Standard Parallel South.
	From the ¼ sec. cor. of secs. 5 and 6.
	S. 89° 45' W., along the E and W center line of sec. 6.
19.455	Point for the center E 1/16 sec. cor. of sec. 6.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	C — E 1/16 / S 6 — C 1971
	Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.
38.91	The center ¼ sec. cor. of sec. 6.
58.77	Point for the center W 1/16 sec. cor. of sec. 6.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

150

Survey of the Subdivision of Section 6,
T. 6 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	C $\frac{\text{W } 1/16}{\text{S } 6}$ C 1971
	Raise a mound of stone, 2½ ft. base, 2 ft. high, N of cor.
78.63	Point for the center 80 1/16 sec. cor. of sec. 6.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	C $\frac{1/16}{\text{S } 6}$ 80 1971
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.
104.73	The ¼ sec. cor. of sec. 6 only, on the W. bdy. of the Tp., set, mkd. and described in the concurrent resurvey of T. 6 S., R. 3 E.
	From the S 1/16 sec. cor. of secs. 5 and 6.
	N. 89° 26' W., along the E and W center line of the SE¼ of sec. 6.
2.00	Angle Point No. 1 of Tract 49, hereinafter described.
33.08	Intersect line 2 - 3 of sec. 39, and Angle Point No. 2 of Tract 49, hereinafter described.
38.64	The center S 1/16 sec. cor. of sec. 6.
	From the W 1/16 sec. cor. of secs. 6 and 7.
	N. 0° 02' W., along the N and S center line of the SW¼ of sec. 6.
19.74	Point for the SW 1/16 sec. cor. of sec. 6, at intersection with the E and W center line of the SW¼ of sec. 6. Not monumented.
39.52	The center W 1/16 sec. cor. of sec. 6.
	From the 80 1/16 sec. cor. of secs. 6 and 7.
	N. 0° 07' E., along the N and S 80 1/16 line of sec. 6.
19.76	Point for the south 80 1/16 sec. cor. of sec. 6, at intersection with the E and W center line of the SW¼ of sec. 6.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	S $\frac{1/16}{\text{S } 6}$ 80 1971
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.
39.53	The center 80 1/16 sec. cor. of sec. 6.

Survey of the Subdivision of Section 5,
T. 6 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	From the center S 1/16 sec. cor. of sec. 6.
	S. 89° 44' W., along the E and W center line of the SW¼ of sec. 6.
19.89	Point for the SW 1/16 sec. cor. of sec. 6.
39.78	The south 80 1/16 sec. cor. of sec. 6.
65.93	The S 1/16 sec. cor. of sec. 6 only, on the W. bdy. of the Tp., set, mkd. and described in the concurrent resurvey of T. 6 S., R. 3 E.
	From the center W 1/16 sec. cor. of sec. 6.
	N. 0° 03' E., along the N and S center line of the NW¼ of sec. 6.
45.94	The W 1/16 sec. cor. of sec. 6 only, on the First Standard Parallel South.
	Survey of Tract 48, T. 6 S., R. 4 E., Salt Lake Meridian, Utah
	From Angle Point No. 1, identical with the closing cor. of secs. 4 and 5 at intersection with the First Standard Parallel South, hereinbefore described.
	Thence
	S. 89° 06' W., along line 1 - 2 of Tract 48, identical with a portion of the First Standard Parallel South.
19.04	The E 1/16 sec. cor. of sec. 5 only, hereinbefore described.
32.77	Angle point bet. secs. 5 and 32, set, mkd. and described in the concurrent resurvey of T. 5 S., R. 4 E. This cor. will also function as Angle Point No. 2 of Tract 48.
	Thence
	S. 89° 35' W., along line 2 - 3 of Tract 48, identical with a portion of the First Standard Parallel South.
5.31	The ¼ sec. cor. of sec. 5 only, hereinbefore described.
5.83	The closing cor. of secs. 32 and 33, set, mkd. and described in the concurrent resurvey of T. 5 S., R. 4 E.
35.88	Angle Point No. 3 of Tract 48, identical with Angle Point No. 2 of the Private Land Claim survey of James R. Hooks, identical to sec. 38, hereinbefore described.
	Thence
	S. 0° 11' E., along line 3 - 4 of Tract 48, identical to the E. bdy. of sec. 38.

CHAINS	
8.54	Angle Point No. 3 of sec. 37, hereinbefore described. This cor. will also function as Angle Point No. 4 of Tract 48.
	Thence
	N. 88° 53' E., along line 4 - 5 of Tract 48, identical with a portion of line 3 - 4 of sec. 37.
30.68	The crossing closing cor. at intersection with the N and S center line of sec. 5 and line 3 - 4 of sec. 37, hereinbefore described.
49.10	Angle Point No. 5 of Tract 48, at record distance (20.00 chs.) from Angle Point No. 4 of sec. 37.
	Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	T 6 S R 4 E TR 48 S 37 | AP 5 1971
	Raise a mound of stone, 3 ft. base, 1½ ft. high, SW of cor.
	Thence
	S. 1° 28' E., along line 5 - 6 of Tract 48.
20.12	Angle Point No. 6 of Tract 48, at intersection with line 5 - 6 of sec. 37.
	Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of brass cap, mkd.
	T 6 S R 4 E S 37 | TR 48 AP 6 1970
	Cor. is located on steep N slope.
	Thence
	S. 88° 32' W., along line 6 - 7 of Tract 48, identical with a portion of line 5 - 6 of sec. 37.
18.62	The crossing closing cor. at intersection with the N and S center line of sec. 5 and line 5 - 6 of sec. 37, hereinbefore described. This cor. will also function as Angle Point No. 7 of Tract 48.
	Thence
	S. 0° 55' E., along line 7 - 8 of Tract 48, identical with a portion of the N and S center line of sec. 5.
17.59	The center ¼ sec. cor. of sec. 5.
19.76	Angle Point No. 8 of Tract 48, at record distance.

CHAINS	
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 6 S R 4 E C | TR 48 | AP 8 | C S 5 1971
	Thence N. 89° 40' E., along line 8 - 9 of Tract 48.
20.04	Angle Point No. 9 of Tract 48, at intersection with the N and S center line of the SE¼ of sec. 5. Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 6 S R 4 E TR 48 AP 9 S 5 | 1971
	Thence S. 0° 45' E., along line 9 - 10 of Tract 48, identical with a portion of the N and S center line of the SE¼ of sec. 5.
5.00	Angle Point No. 10, at record distance. Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of brass cap, mkd. T 6 S R 4 E E | TR 48 | AP 10 | S 5 E 1971 Cor. is located on steep S slope.
	Thence N. 89° 40' E., along line 10 - 11 of Tract 48.
20.00	Angle Point No. 11 of Tract 48, at intersection with the sec. line between secs. 4 and 5. Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.

154

Survey of Tract 48,
T. 6 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	T 6 S R 4 E TR 48 | S 4 AP 11 | S 5 | 1971
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.
	Thence
	N. 0° 30' W., along line 11 - 12 of Tract 48, identical with a portion of the sec. line between secs. 4 and 5.
7.17	The ¼ sec. cor. of secs. 4 and 5, this cor. will also function as Angle Point No. 12 of Tract 48.
	Thence
	N. 3° 22' W., along line 12 - 1 of Tract 48, identical with a portion of the sec. line between secs. 4 and 5.
38.33	Angle Point No. 4 of sec. 37, hereinbefore described.
46.31	Angle Point No. 1 and point of beginning.

Survey of Tract 49,
T. 6 S., R. 4 E., Salt Lake Meridian, Utah

From Angle Point No. 1, at record distance (2.00 chs.) W of the sec. line of secs. 5 and 6, and on the E and W center line of the SE¼ of sec. 6.

Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

T 6 S R 4 E
S 6
AP 1 \|
TR 49 \|
1971

from which

A rebar, 3/4 ins. diam., projecting 3 ins. above the ground, bears East 1.8 lks. dist.

Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.

Cor. is located at the base of a steep E slope on the W side of dirt road.

Thence

N. 89° 26' W., along line 1 - 2 of Tract 49, identical with a portion of the E and W center line of the SE¼ of sec. 6.

31.08 Angle Point No. 2 at intersection with line 2 - 3 of sec. 39.

Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.

CHAINS

T 6 S R 4 E
S 6

AP 2
TR 49
1971

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

Thence

S. 0° 09' E., along line 2 - 3 of Tract 49, identical with a portion of line 2 - 3 of sec. 39.

3.76 Angle Point No. 3 of Tract 49, at record distance (10.00 chs.) from the S. bdy. of sec. 39.

Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.

T 6 S R 4 E
S 6 | TR 49
AP 3
1982

Raise a mound of stone, 3 ft. base, 2½ ft. high, W of cor.

Cor. is located on steep E slope in dense maple and oak.

Thence

N. 89° 29' W., along line 3 - 4 of Tract 49.

5.56 Intersect the N and S center line of sec. 6. Not monumented.

10.00 Angle Point No. 4 at record distance (10.00 chs.) from the E. bdy. of sec. 39.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 6 S R 4 E
S 6

AP 4
TR 49
1971

Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.

Cor. is located on steep W slope in dense oak and maple.

Thence

S. 0° 09' E., along line 4 - 5 of Tract 49.

10.00 Angle Point No. 5 of Tract 49, at intersection with the S. bdy. of sec. 39.

Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.

Survey of Tract 49,
T. 6 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	T 6 S R 4 E | TR 49 S 6 | AP 5 1971
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.
	Cor. is located on steep W slope in dense oak and maple.
	Thence
	S. 89° 29' E., along line 5 - 6 of Tract 49, identical with a portion of line 3 - 4 of sec. 39.
4.44	Angle Point No. 6 of Tract 49, at intersection with the N and S center line of sec. 6.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 6 S R 4 E TR 49 S 6 | AP 6 1971
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.
	Thence
	S. 0° 09' E., along line 6 - 7 of Tract 49, identical with a portion of the N and S center line of sec. 6.
6.00	The ¼ sec. cor. of secs. 6 and 7, this cor. will also function as Angle Point No. 7 of Tract 49.
	Thence
	S. 89° 36' E., along line 7 - 8 of Tract 49, identical with a portion of the sec. line between secs. 6 and 7.
19.44	The E 1/16 sec. cor. of sec. 6 and 7, hereinbefore described.
36.88	Angle Point No. 8, at record distance (2.00 chs.) from the sec. line between secs. 5 and 6.
	Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.
	T 6 S R 4 E TR 49 | AP 8 | S 6 S 7 1970
	from which
	A rebar, 3/4 ins. diam., projecting 3 ins. above the ground, bears S. 45° E., 2.3 lks. dist.

Survey of Tract 49,
T. 6 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	Thence
	N. 0° 49' W., along line 8 - 1 of Tract 49.
19.66	Angle Point No. 1 and point of beginning.

General Description

The land encompassed in this survey is located in the mountains of the South Fork of the Provo River about 3½ miles SE of the Provo River. For the most part the elevations of the land is in the Uinta National Forest, range from 5680 ± in sec. 6 to 8920 ± in sec. 10.

Generally speaking the terrain is mountainous with deep canyons. The vegetation varies from large cottonwood trees in the canyon bottoms, to oak and maple brush, aspen, pine and spruce in the higher elevations.

Drainage is in all directions into the South Fork of the Provo River which flows NW through the township.

A county road runs along the South Fork of the Provo River. This paved road traverses through secs. 5, 6, and 7. There are numerous dirt roads used for access for recreation.

The principle use of this are is for recreation by hunters, campers, fishermen and picnickers and for stock grazing during the summer months. There are a few homes along the South Fork of the Provo River.

The mean of a considerable number of observations of the magnetic declination is 15° 30' E.

Form 9600-11
(August 1979)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Frank C. Profaizer	Cadastral Surveyor
Douglas A. Cody	Cadastral Surveyor
Johnnie R. Mendez	Cadastral Surveyor
Victor E. Templeton	Survey Aid
Richard L. White	Survey Aid
Paul S. Howard	Survey Aid
Thomas C. Maguire	Survey Aid
Everett E. Gorgen	Survey Aid
Arthur J. Saiz	Survey Aid
Richard G. Foutch	Survey Aid
Emanual Erlich	Survey Aid
Patrick E. Dawson	Survey Aid
Lon G. Hill	Survey Aid
Gary Gogos	Surveying Technician
Rex Smith	Survey Aid
Terry Christensen	Survey Aid
Peter Coffey	Survey Aid
John Mavor	Survey Aid
John Zwahlen	Survey Aid
Jeff Peyton	Survey Aid
Donzil Worthington	Survey Aid

159

CERTIFICATE OF SURVEY

(IXX)(We), Ray Harpin and Donald A. Buhler , HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 11th day of August , 19 69 XXX(We) have dependently resurveyed a portion of the subdivisional lines and surveyed the subdivision of certain sections and tracts of Township 6 South, Range 4 East

of the Salt Lake Meridian, in the State of Utah , which are represented in the foregoing field notes as having been executed by (XXX) (us) and under (XXX) (our) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

August 10, 1983
(Date)

Ray Harpin
(Cadastral Surveyor)

August 10, 1983
(Date)

Donald A. Buhler
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines and the survey of the subdivision of certain sections and tracts of T. 6 S., R. 4 E. of the Salt Lake Meridian, Utah

executed by Ray Harpin and Donald A. Buhler, Cadastral Surveyors

having been critically examined and found correct, are hereby approved.

August 15, 1983
(Date)

Glen B. Hatch
(CXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX)
Chief Cadastral Surveyor for Utah

~~CERTIFICATE OF TRANSCRIPT~~

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in ______ is a true copy of the original field notes.

~~(Date)~~

(CXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX)
Chief Cadastral Surveyor for Utah

Form 9600-9
(December 1979)
(formerly 9180-6)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
ORIGINAL

R606

FIELD NOTES

160

OF THE

DEPENDENT RESURVEY

OF

A PORTION OF THE EIGHTH STANDARD PARALLEL SOUTH,

THE EAST AND NORTH BOUNDARIES,

A PORTION OF THE SUBDIVISIONAL LINES,

A PARTIAL SUBDIVISION OF SECTIONS 25, 33 AND 34,

AND

THE MEANDER LINES OF THE RIGHT BANK OF THE SAN JUAN RIVER

OF

TOWNSHIP 40 SOUTH, RANGE 21 EAST

Of the Salt Lake Meridian,

In the State of Utah.

EXECUTED BY

Jerry L. Thomas Supervisory Cadastral Surveyor

Under special instructions dated May 2, 19 79, approved May 3, 1979,

_____, which provided for the surveys included under ~~XXXXXXX~~/Group

Number 592, and assignment instructions dated May 7, 19 79.

Survey commenced May 25, 1979

Survey completed May 7, 1982

INDEX DIAGRAM

Township 40 South, Range 21 East,

6	5	4 22 25	3 16 21	6 2 11 16	6 1 5 11
7	8	9 21 25	10 15 20	11 10 15	12 5 10
18	17	16 20 25	15 14 19	14 9 14	13 4 9
19	20 24 26	21 19 24	22 13 18	23 8 13	24 8
30	29 24 26	28 18 23	27 12 18	26 7 12	25 3 7
31	32 22 2	33 17 2	34 12	35 7	36 3

Subdivision of Section 25 - Page 27
Subdivision of Section 33 - Page 28
Subdivision of Section 34 - Page 30

Meanders of the right bank of the San Juan River - Page 31

GPO 855-927

Township 40 South, Range 21 East, Salt Lake Meridian Utah

CHAINS

The following field notes are those of the dependent resurvey of a portion of the Eighth Standard Parallel South, the east and north boundaries, a portion of the subdivisional lines, a partial subdivision of sections 25, 33, and 34, and the meander lines of the right bank of the San Juan River of T. 40 S., R. 21 E., Salt Lake Meridian, Utah.

History of Surveys

	Surveyed by		Retr. or Resurveyed by	
SOUTH BOUNDARY				
All	A.D. Ferron	1884		
West 2 miles and 9.00 chs.			H.D. Page and J.M. Lentz	1898
West 1 mile and 77.27 chs.			C.F. Moore and R.C. Yundt	1929
East 4 miles and 7.73 chs.			A. Nelson	1953
EAST BOUNDARY				
All	A.D. Ferron	1884		
East Bdy. to right bank of the San Juan River in Sec. 25			H.D. Page and J.M. Lentz	1898
East Bdy. of Secs. 24, 25 and 30			A. Nelson	1953
NORTH BOUNDARY				
Secs. 1 and 2	A.D. Ferron	1884		
			H.D. Page and J.M. Lentz	1899
			R.C. Yundt	1947
Subdivisional and Meander Lines	H.D. Page and J.M. Lentz	1899		
A portion of the Subdivisional Lines			C.F. Moore and R.C. Yundt	1929

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and special instructions for Group No. 592, Utah, dated May 2, 1979.

The direction of lines were determined by reference to the true meridian established on line by hour angle observations on Polaris and altitude observations on the sun. The lines were carried forward by sustained angulation being supplemented by numerous hour angle observations on Polaris.

163

Township 40 South, Range 21 East, Salt Lake Meridian, Utah

CHAINS	
	Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein. The Geographic Position of the corner of sections 25, 30, 31, and 36, on the east boundary of the township, as determined from a tie made to U.S.G.S. bench mark "Bluff" located in section 10 of T. 40 S., R. 22 E., is: Latitude 37° 16' 22.9" N. Longitude 109° 32' 52.9" W. The mean magnetic declination is 13° 30' E.
	Dependent Resurvey of the Eighth Standard Parallel South, through a Portion of Range 21 East, Salt Lake Meridian, Utah
	(Reestablishment of the Independent Resurvey Executed by C.F. Moore and R.C. Yundt in 1929 and the Resurvey Executed by Andrew Nelson in 1953)
	Beginning at the witness meander cor. established in 1929 by C. Moore and R. Yundt, monumented with an iron post, 1 in. diam., firmly set, with a brass cap mkd. as described in the official record. This cor. will also function as the witness cor. to the standard cor. of secs. 32 and 33. The marks 1981 were added to the brass cap. S. 89° 58' E., along the S. bdy. of sec. 32.
2.73	True point for the standard cor. of secs. 32 and 33, at record bearing and distance falls in bottom land that is subject to flooding. Not monumented.
	S. 89° 58' E., along the S. bdy. of sec. 33.
11.36	Point for the meander cor. on the present right bank of the San Juan River falls in bottom land that is subject to flooding. Not monumented.
	Dependent Resurvey of a Portion of the East Boundary of T. 40 S., R. 21 E., Salt Lake Meridian, Utah
	(Reestablishment of the Independent Resurvey Executed by Andrew Nelson in 1953)
	From the witness cor. for secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., projecting 12 ins. above the ground, and in a mound of stone, with brass cap mkd.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	T 40 S W C R 21 E | R 22 E S 25 | S 30 S 36 | S 31 1953
	This cor. will now function as an angle point only.
	North, between secs. 31 and 36.
0.25	Mean high water mark of the left bank of the San Juan River.
5.00	True point for the meander cor. of secs. 31 and 36, on the right bank of the San Juan River, falls on unstable river bank.
5.07	Point selected for the witness meander cor. of secs. 31 and 36.
	Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	W C T 40 S R 21 E R 22 E S 36 | S 31 M C 1981
5.85	Point for the cor. of secs. 25, 30, 31, and 36.
	Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T 40 S R 21 E R 22 E S 25 | S 30 S 36 | S 31 1981
	North, bet. secs. 25 and 30.
35.00	Point for the meander cor. at record bearing and distance; there is no remaining evidence of the original corner. Not monumented.
40.00	Point for the ¼ sec. cor. of secs. 25 and 30, at proportionate distance; there is no remaining evidence of the original corner.
	Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T 40 S R 21 E R 22 E ¼ S 25 | S 30 1981

165

Dependent Resurvey of a Portion of the East Boundary of
T. 40 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
	(Reestablishment of the Independent Resurvey Executed by H.D. Page and J.M. Lentz in 1899 and the Dependent Resurvey Executed by Andrew Nelson in 1953)
76.00	Center line of U.S. Highway No. 163, bears E and W.
80.00	The cor. of secs. 19, 24, 25, and 30, monumented with an iron post, 2½ ins. diam., projecting 6 ins. above the ground, with brass cap mkd. T 40 S R 21 E | R 22 E S 24 | S 19 S 25 | S 30 1953
	(Reestablishment of the Independent Resurvey Executed by H.D. Page and J.M. Lentz in 1898)
	From the cor. of secs. 13, 18, 19, and 24, monumented with an iron post, 2½ ins. diam., projecting 21 ins. above the ground, with brass cap, mkd. Also a mound of stone, 3 ft. base, 2 ft. high, W of cor. T 40 S R 21 E | R 22 E S 13 | S 18 S 24 | S 19 1953
	N. 0° 06' E., bet. secs. 13 and 18.
10.47	Power line, bears N. 27° 44' E. and S. 27° 44' W.
40.00	The ¼ sec. cor. of secs. 13 and 18, monumented with a sandstone, 12 x 6 x 6 ins., badly deteriorated, and in a mound of stone. This position is harmoniously related to existing corners and is accepted as the best available evidence of the original corner. At the corner point Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 40 S R 21 E | R 22 E ¼ S 13 | S 18 1979
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.
	N. 0° 01' W., beginning new measurement.
40.01	The cor. of secs. 7, 12, 13, and 18, monumented with a sandstone, 14 x 13 x 6 ins., firmly set in a mound of stone, mkd. 4 notches on S and 2 notches on N edges.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., over a cross (X) chiseled in sandstone, and in a mound of stone, 4½ ft. base, to top of aluminum cap, mkd.

T 40 S
R 21 E | R 22 E
S 12 | S 7
S 13 | S 18
1979

Bury the mkd. stone alongside the aluminum post.

North, bet. secs. 7 and 12.

40.05 The ¼ sec. cor. of secs. 7 and 12, monumented with a broken sandstone, 8 x 6 x 6 ins., dimly mkd. ¼ on W face, firmly set in a mound of stone.

At the corner point

Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 40 S
R 21 E | R 22 E
¼
S 12 | S 7
1979

Bury the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 ft. base, 1½ ft. high, W of cor.

N. 0° 03' E., beginning new measurement.

40.04 The cor. of secs. 1, 6, 7, and 12, monumented with a small mound of stone, 2 ft. base, 1½ ft. high, foreign to the area. This position is harmoniously related to existing corners and is accepted as the best available evidence of the original corner.

At the corner point (center of mound)

Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 40 S
R 21 E | R 22 E
S 1 | S 6
S 12 | S 7
1979

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

N. 0° 04' E., bet. secs. 1 and 6.

39.91 The ¼ sec. cor. of secs. 1 and 6, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, with brass cap mkd.

Dependent Resurvey of a Portion of the East Boundary of
T. 40 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS

¼
S 1 | S 6
1947|

This position is harmoniously related to existing corners and is accepted as the best available evidence of the original corner. There is no official record of the iron post.

N. 0° 08' E., beginning new measurement.

40.10 The cor. of Tps. 39 and 40 S., Rs. 21 and 22 E., monumented with an iron post, 3 ins. diam., firmly set and projecting 6 ins. above the ground, with brass cap mkd. as described in the official record of the 1912 resurvey of the north boundary of T. 40 S., R. 22 E.

Dependent Resurvey of a Portion of the North Boundary
of T. 40 S., R. 21 E., Salt Lake Meridian, Utah

(Reestablishment of the Independent Resurvey Executed by H.D. Page and J.M. Lentz in 1899 and the Dependent Resurvey Executed by R.C. Yundt in 1947)

From the ¼ sec. cor. of secs. 1 and 36, monumented with an iron post, 1 in. diam., firmly set and projecting 6 ins. above the ground, with brass cap mkd. as described in the official record of the 1947 resurvey of the N. bdy. of T. 40 S., R. 21 E.

S. 89° 55' W., bet. secs. 1 and 36.

40.60 The cor. of secs. 1, 2, 35, and 36, monumented with an iron post, 2 ins. diam., firmly set projecting 6 ins. above the ground, with brass cap mkd.

T 39 S R 21 E
S 35 | S 36
S 2 | S 1
T 40 S
1947

I added the marks 1979 to the brass cap.

S. 89° 55' W., bet. secs. 2 and 35.

39.74 The ¼ sec. cor. of secs. 2 and 35, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, with brass cap mkd. as described in the official record of the 1947 dependent resurvey of the N. bdy. of T. 40 S., R. 21 E.

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 40 S., R. 21 E., Salt Lake Meridian, Utah

(Reestablishment of the Survey Executed by
H.D. Page and J.M. Lentz in 1899)

☆U.S. Government Printing Office: 1980—778-251/292

Dependent Resurvey of a Portion of the Subdivisional Lines of
T. 40 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
	From the cor. of secs. 25, 26, 35, and 36, monumented with a steel fence post, projecting 4 ins. above a mound of stone. This position is harmoniously related to existing corners and is accepted as the best available evidence of the original corner. Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 40 S R 21 E S 26 | S 25 S 35 | S 36 1981 S. 0° 01' E., bet. secs. 35 and 36.
2.50	Intersect the present mean high water mark of the right bank of the San Juan River (at record bearing and distance). There is no remaining evidence of the original corner. Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 40 S R 21 E S 35 | S 36 M C 1981
	From the cor. of secs. 25, 26, 35, and 36. East, bet. secs. 25 and 36.
6.00	Intersect the present mean high water mark of the right bank of the San Juan River at record bearing and distance. There is no remaining evidence of the original corner. Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 40 S R 21 E S 25 | M C S 36 | 1982
	From the cor. of secs. 25, 26, 35, and 36. N. 0° 01' E., bet. secs. 25 and 26.
20.00	Point for the S 1/16 sec. cor. of secs. 25 and 26. Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 40 S R 21 E S 1/16 S 26 | S 25 1981

CHAINS	
	Deposit a steel fence post, 6 ft. long, alongside the aluminum post.
40.00	Point for the ¼ sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner. Not monumented.
47.50	Center line of U.S. Highway No. 163, bears E and W.
67.00	Power line, bears NE and SW.
80.00	The cor. of secs. 23, 24, 25, and 26, monumented with a steel rod, 1½ in. diam., projecting 6 ins. above the ground, firmly set in a mound of stone. This position is harmoniously related to existing corners and is accepted as the best available evidence of the original corner. At the corner point Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 40 S R 21 E S 23 | S 24 S 26 | S 25 1979 Bury the steel rod alongside the aluminum post. Raise a mound of stone, 3½ ft. base, 1½ ft. high, W of cor.
	From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., hereinbefore described. N. 89° 35' W., bet. secs. 24 and 25.
26.80	Enter the cemetery in the town of Bluff.
40.04	The ¼ sec. cor. of secs. 24 and 25, determined at the cor. of fences, bearing W and NE. This position is harmoniously related to existing corners and is accepted as the best available evidence of the original corner. At the corner point Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 40 S R 21 E ¼ S 24 S 25 1979
	S. 89° 59' W., beginning new measurement.
18.50	Power line, bears NE and SW.
40.06	The cor. of secs. 23, 24, 25, and 26.
	North, bet. secs. 23 and 24.
39.99	Point for the ¼ sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.

☆U.S. Government Printing Office: 1980—778-251/292

Dependent Resurvey of a Portion of the Subdivisional Lines of
T. 40 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
	Set an iron post, 8 ins. long, 1 ins. diam., 6 ins. into solid sandstone, and in a collar of stone, with brass cap mkd. T 40 S R 21 E ¼ S 23 | S 24 1979 Cor. is located on S slope of exposed sandstone.
79.98	Point for the cor. of secs. 13, 14, 23, and 24, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 S R 21 E S 14 | S 13 S 23 | S 24 1979 Deposit a cedar post, 6 ft. long, alongside the iron post.
	From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., hereinbefore described. N. 89° 49' W., bet. secs. 13 and 24.
5.50	Power line, bears N. 27° 44' E., to substation and S. 27° 44' W. to the town of Bluff.
40.04	Point for the ¼ sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 12 ins. diam., 1 in. diam., 10 ins. into solid sandstone, with brass cap mkd. T 40 S R 21 E ¼ S 13 S 24 1979 Raise a mound of stone, 3 ft. base, 2 ft. high, NE of cor.
80.08	The cor. of secs. 13, 14, 23, and 24.
	North, bet. secs. 13 and 14.
39.99	Point for the ¼ sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

CHAINS	
	T 40 S R 21 E ¼ S 14 | S 13 1979 Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.
79.98	Point for the cor. of secs. 11, 12, 13, and 14, at proportionate distance; there is no remaining evidence of the original corner. Cor. point falls on the main stream bed of "Cottonwood Creek" and is impossible to perpetuate.
	From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., hereinbefore described. N. 89° 58' W., bet. secs. 12 and 13.
40.04	The ¼ sec. cor. of secs. 12 and 13, monumented with a sandstone, 14 x 8 x 6 ins., firmly set 6 ins. in the ground and dimly mkd. ¼ on N face, with a mound of stone to the N. At the corner point Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 40 S R 21 E S 12 ¼ S 13 1979 Deposit the mkd. stone alongside the aluminum post. Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.
	N. 89° 41' W., beginning new measurement.
40.08	The cor. of secs. 11, 12, 13, and 14.
	N. 0° 01' W., bet. secs. 11 and 12.
1.14	Point selected for the witness cor. to the cor. of secs. 11, 12, 13, and 14. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 S R 21 E W C S 11 | S 12 S 14 | S 13 ↓ 1979
39.99	Point for the ¼ sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.

☆U.S. Government Printing Office: 1980—778-251/292

Dependent Resurvey of a Portion of the Subdivisional Lines of
T. 40 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 40 S R 21 E ¼ S 11 | S 12 1979
79.98	Point for the cor. of secs. 1, 2, 11, and 12, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 10 ins. long, 1 in. diam., 8 ins. into solid sandstone, with brass cap mkd. T 40 S R 21 E S 2 | S 1 S 11 | S 12 1979 Cor. is located on steep SE slope of ravine, 25 ft. above wash bottom, bearing NE.
	From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., hereinbefore described. N. 89° 56' W., bet. secs. 1 and 12.
40.06	Point for the ¼ sec. or. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 S R 21 E ¼ S 1 S 12 1979 Deposit a cottonwood stake, 7 ft. long, alongside the iron post. Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor. Cor. is located 1 ch. N of Cottonwood Creek stream bed, drains E.
80.12	The cor. of secs. 1, 2, 11, and 12.
	N. 0° 27' W., bet. secs. 1 and 2.
39.99	Point for the ¼ sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd.

CHAINS	
	T 40 S R 21 E ¼ S 2 | S 1 1979
	Cor. is located on N slope.
79.98	The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., hereinbefore described.
	From the cor. of secs. 25, 26, 35, and 36.
	N. 89° 56' W., bet. secs. 26 and 35.
39.96	Point for the ¼ sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original corner. Not monumented.
79.92	Point for the cor. of secs. 26, 27, 34, and 35, at proportionate distance; there is no remaining evidence of the original corner.
	Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T 40 S R 21 E S 27 | S 26 S 34 | S 35 1981
	S. 0° 01' E., bet. secs. 34 and 35.
37.50	Point for the meander cor. at record bearing and distance; there is no remaining evidence of the original corner. Not monumented.
	From this point, the special meander cor. on the E-W center line of sec. 34, bears S. 76° 28' W., 10.45 chs. dist., hereinafter described.
	From the cor. of secs. 26, 27, 34, and 35.
	N. 0° 01' W., bet. secs. 26 and 27.
12.91	Center line of U.S. Highway No. 163, bears E and W.
16.57	Powerline, bears N. 58° 33' E. and S. 58° 33' W.
40.00	Point for the ¼ sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original corner.
	Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T 40 S R 21 E ¼ S 27 | S 26 1981

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
80.00	The cor. of secs. 22, 23, 26, and 27, monumented with a rebar, 5/8 ins. diam., projecting 6 ins. above the ground, with a mound of stone to the W. This position is harmoniously related to existing corners and is accepted as the best available evidence of the original corner. Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 40 S R 21 E S 22 | S 23 S 27 | S 26 1979 Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	From the cor. of secs. 23, 24, 25, and 26. N. 89° 57' W., bet. secs. 23 and 26.
39.96	Point for the ¼ sec. cor. of secs. 23 and 26, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 40 S R 21 E ¼ S 23 S 26 1979
79.92	The cor. of secs. 22, 23, 26, and 27.
	N. 0° 04' W., bet. secs. 22 and 23.
39.94	Point for the ¼ sec. cor. of secs. 22 and 23, at proportionate distance. Cor. point falls on perpendicular cliff; there is no remaining evidence of the original witness corner.
44.93	Point selected for the witness cor. to the ¼ sec. cor. of secs. 22 and 23. Set an aluminum post, 28 ins. long, 2½ ins. diam., over a cross (X) chiseled on solid sandstone, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd. W C T 40 S R 21 E ¼ S 22 | S 23 ↓ 1979
79.88	Point for the cor. of secs. 14, 15, 22, and 23, at proportionate distance; there is no remaining evidence of the original witness corner. Set an iron post, 10 ins. long, 1 in. diam., 8 ins. into solid sandstone, with brass cap mkd.

175 Dependent Resurvey of a Portion of the Subdivisional Lines of T. 40 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
	T 40 S R 21 E S 15 | S 14 S 22 | S 23 1979 Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor. Cor. is located on steep SE facing sandstone slope, 30 lks. W of vertical ledge.
	From the cor. of secs. 13, 14, 23, and 24. S. 89° 39' W., bet. secs. 14 and 23.
40.06	The ¼ sec. cor. of secs. 14 and 23, monumented with a sandstone, 10 x 10 x 6 ins., plainly mkd. 1 groove on N face, with a piece of sandstone, 4 x 10 x 6 ins., plainly mkd. 4, both firmly set in a mound of stone. At the corner point Set an aluminum post, 28 ins. long, 2½ ins. diam., over a cross (X) chiseled on solid sandstone, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd. T 40 S R 21 E ¼ S 14 S 23 1979 Deposit the mkd. sandstone alongside the aluminum post. N. 89° 40' W., beginning new measurement.
39.97	The cor. of secs. 14, 15, 22, and 23.
	N. 0° 04' E., bet. secs. 14 and 15.
39.94	Point for the ¼ sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 S R 21 E ¼ S 15 | S 14 1979
79.88	The cor. of secs. 10, 11, 14, and 15, monumented with a sandstone, 16 x 10 x 7 ins., firmly set and plainly mkd. 4 notches on S and 2 notches on E edges. At the corner point Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

☆U.S. Government Printing Office: 1980—778-251/292

Dependent Resurvey of a Portion of the Subdivisional Lines of
T. 40 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
	T 40 S R 21 E S 10 | S 11 S 15 | S 14 1979 Deposit the mkd. stone alongside the aluminum post. Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor.
	From the cor. of secs. 11, 12, 13, and 14. S. 89° 45' W., bet. secs. 11 and 14.
40.08	The ¼ sec. cor. of secs. 11 and 14, monumented with a sandstone, 16 x 12 x 6 ins., firmly set in a mound of stone, dimly mkd. ¼ on N face. At the corner point Set an aluminum post, 28 ins. long, 2½ ins. diam., over a cross (X) chiseled in sandstone, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd. T 40 S R 21 E ¼ S 11 S 14 1979 Deposit the mkd. stone alongside the aluminum post.
	N. 89° 57' W., beginning new measurement.
39.80	The cor. of secs. 10, 11, 14, and 15.
	N. 0° 01' W., bet. secs. 10 and 11.
39.97	Point for the ¼ sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 40 S R 21 E ¼ S 10 | S 11 1979
79.94	The cor. of secs. 2, 3, 10, and 11, monumented with a sandstone, 16 x 10 x 5 ins., firmly set 4 ins. in the ground and plainly mkd. 5 notches on S and 2 notches on E edges. At the corner point Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

177

Dependent Resurvey of a Portion of the Subdivisional Lines of
T. 40 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
	T 40 S R 21 E S 3 | S 2 S 10 | S 11 1979 Deposit the mkd. stone alongside the aluminum post.
	From the cor. of secs. 1, 2, 11, and 12. S. 89° 56' W., bet. secs. 2 and 11.
39.97	The ¼ sec. cor. of secs. 2 and 11, monumented with a mound of stone foreign to the area. This position is harmonously related to existing corners and is accepted as the best available evidence of the original corner. At the corner point (center of mound) Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 40 S R 21 E ¼ S 2 S 11 1979 Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.
	N. 89° 59' W., beginning new measurement.
39.90	The cor. of secs. 2, 3, 10, and 11.
	N. 0° 17' W., bet. secs. 2 and 3.
40.02	The ¼ sec. cor. of secs. 2 and 3, monumented with a broken sandstone, dimly mkd. ¼ on broken pieces. At the corner point Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 40 S R 21 E ¼ S 3 | S 2 1979 Deposit the mkd. broken stones and a cottonwood stake, 5 ft. long, alongside the aluminum post.
	N. 0° 16' W., beginning new measurement.
39.97	The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set with brass cap, mkd. as described in the official record of the 1929 resurvey.

☆U.S. Government Printing Office: 1980—778-251/292

Dependent Resurvey of a Portion of the Subdivisional Lines of
T. 40 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
	From the cor. of secs. 27, 28, 33, and 34, monumented with a sandstone, 8 x 7 x 5 ins., dimly mkd. 1 notch on S edge and firmly set in a mound of stone. At the corner point Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 40 S R 21 E S 28 | S 27 S 33 | S 34 1979 Deposit the mkd. stone alongside the aluminum post. Raise a mound of stone, 3 ft. base, 2½ ft. high, W of cor. S. 0° 03' W., bet. secs. 33 and 34.
26.84	Center line of U.S. Highway No. 163, bears N. 63° 30' E. and S. 63° 30' W.
32.15	Power line, bears N. 51° 45' E. and S. 51° 45' W.
39.93	The ¼ sec. cor. of secs. 33 and 34, monumented with a cobblestone, firmly set and plainly mkd. ¼ on W face. At the corner point Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 40 S R 21 E ¼ S 33 | S 34 1979 Deposit the mkd. stone alongside the aluminum post. Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor. S. 0° 02' E., beginning new measurement.
12.25	Point selected as the witness meander cor. for secs. 33 and 34, set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. W C T 40 S R 21 E S 33 | S 34 M C 1981 Deposit a cottonwood post, 5 ft. long, 4 ins. diam., alongside the aluminum post.
14.41	Intersect the mean high water mark of the right bank of the San Juan River. True point for the meander cor. of secs. 33 and 34 falls on unstable river bank.

179

Dependent Resurvey of a Portion of the Subdivisional Lines of
T. 40 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
	From the cor. of secs. 26, 27, 34, and 35.
	S. 89° 52' W., bet. secs. 27 and 34.
27.29	Power line, bears N. 58° 33' E. and S. 58° 33' W.
37.06	Center line of U.S. Highway No. 163, bears NE and SW.
39.96	The ¼ sec. cor. of secs. 27 and 34, monumented with a sandstone, 14 x 12 x 5 ins., firmly set 6 ins. in the ground and dimly mkd. ¼ on N face. At the corner point Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 40 S R 21 E ¼ S 27 / S 34 1979 Deposit the mkd. stone alongside the aluminum post.
	S. 89° 56' W., beginning new measurement.
39.97	The cor. of secs. 27, 28, 33, and 34.
	N. 0° 04' W., bet. secs. 27 and 28.
40.01	Point for the ¼ sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a mound of stone, 3½ ft. base, to top of aluminum cap, mkd. T 40 S R 21 E ¼ S 28 | S 27 1979
80.02	Point for the cor. of secs. 21, 22, 27, and 28, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 28 ins. long, 2½ ins. diam., over a cross (X) chiseled in solid sandstone, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd. T 40 S R 21 E S 21 | S 22 S 28 | S 27 1979
	From the cor. of secs. 22, 23, 26, and 27.
	N. 89° 54' W., bet. secs. 22 and 27.

☆U.S. Government Printing Office: 1980—778-251/292

Dependent Resurvey of a Portion of the Subdivisional Lines of
T. 40 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
39.96	The ¼ sec. cor. of secs. 22 and 27, monumented with a sandstone, 15 x 10 x 3 ins., firmly set 6 ins. in the ground and dimly mkd. ¼ on N face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 S R 21 E ¼ S 22 / S 27 1979 Deposit the mkd. stone alongside the iron post. Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.
	S. 89° 42' W., beginning new measurement.
40.04	The cor. of secs. 21, 22, 27, and 28.
	N. 0° 02' W., bet. secs. 21 and 22.
40.01	The ¼ sec. cor. of secs. 21 and 22, monumented with a sandstone, 12 x 10 x 4 ins., firmly set 4 ins. in the ground and plainly mkd. ¼ on W face. At the corner point Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 40 S R 21 E ¼ S 21 | S 22 1979 Deposit the mkd. stone alongside the aluminum post.
	N. 0° 02' W., beginning new measurement.
40.04	Point for the cor. of secs. 15, 16, 21, and 22, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 40 S R 21 E S 16 | S 15 S 21 | S 22 1979
	From the cor. of secs. 14, 15, 22, and 23.
	S. 89° 52' W., bet. secs. 15 and 22.
39.92	The ¼ sec. cor. of secs. 15 and 22, monumented with a cross (X) and ¼ chiseled on solid sandstone.

181

Dependent Resurvey of a Portion of the Subdivisional Lines of
T. 40 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
	At the corner point Set an aluminum post, 28 ins. long, 2½ ins. diam., over the cross (X) and in a mound of stone, 4½ ft. base, to top of aluminum cap, mkd. T 40 S R 21 E ¼ S 15 / S 22 1979
	N. 89° 56' W., beginning new measurement.
40.04	The cor. of secs. 15, 16, 21, and 22.
	N. 0° 02' W., bet. secs. 15 and 16.
40.04	The ¼ sec. cor. of secs. 15 and 16, monumented with a sandstone, 16 x 10 x 6 ins., firmly set 4 ins. in the ground and plainly mkd. ¼ on N face with a mound of stone to the W. At the corner point Set an aluminum post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4½ ft. base, to top of aluminum cap, mkd. T 40 S R 21 E ¼ S 16 | S 15 1979 Deposit the mkd. stone alongside the aluminum post.
	N. 0° 06' W., beginning new measurement.
39.89	The cor. of secs. 9, 10, 15, and 16, monumented with a small mound of stone foreign to the area. This position is harmoniously related to existing corners and is accepted as the best available evidence of the original corner. At the corner point (center of mound) Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 40 S R 21 E S 9 | S 10 S 16 | S 15 1979 Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.
	From the cor. of secs. 10, 11, 14, and 15. West, bet. secs. 10 and 15.

☆U.S. Government Printing Office: 1980—778-251/292

Dependent Resurvey of a Portion of the Subdivisional Lines of
T. 40 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
40.03	The ¼ sec. cor. of secs. 10 and 15, monumented with a sandstone, 14 x 8 x 8 ins., firmly set 4 ins. in the ground and plainly mkd. ¼ on N face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 S R 21 E S 10 ¼ S 15 1979 Deposit the mkd. stone alongside the iron post.
	West, beginning new measurement.
40.07	The cor. of secs. 9, 10, 15, and 16.
	N. 0° 05' W., bet. secs. 9 and 10.
40.06	Point for the ¼ sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 S R 21 E ¼ S 9 | S 10 1979
80.12	The cor. of secs. 3, 4, 9, and 10, monumented with a mound of stone foreign to the area. This position is harmoniously related to existing corners and is accepted as the best available evidence of the original corner. At the corner point (center of mound) Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 40 S R 21 E S 4 | S 3 S 9 | S 10 1979
	From the cor. of secs. 2, 3, 10, and 11. N. 89° 49' W., bet. secs. 3 and 10.
40.09	Point for the ¼ sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

183

Dependent Resurvey of a Portion of the Subdivisional Lines of
T. 40 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
	T 40 S R 21 E ¼ S 3 / S 10 1979
80.18	The cor. of secs. 3, 4, 9, and 10.
	N. 0° 02' E., bet. secs. 3 and 4.
40.01	The ¼ sec. cor. of secs. 3 and 4, monumented with a sandstone, 16 x 10 x 5 ins., firmly set 6 ins. in the ground and plainly mkd. ¼ on W face, with a mound of stone W of cor. At the corner point Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 40 S R 21 E ¼ S 4 | S 3 1979 Deposit the mkd. stone alongside the aluminum post. Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	N. 0° 03' W., beginning new measurement.
39.74	The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, with brass cap mkd. as described in the official record of the 1929 dependent resurvey.
	From the true point for the standard cor. of secs. 32 and 33, on the S. bdy. of the Tp., hereinbefore described. N. 0° 01' W., bet. secs. 32 and 33.
20.03	Point for the S 1/16 sec. cor. of secs. 32 and 33. Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 40 S R 21 E S 1/16 S 32 | S 33 1981
35.51	Intersect power line, bears E and W.
40.06	The ¼ sec. cor. of secs. 32 and 33, monumented with a broken sandstone, plainly mkd. ¼ on a fragmented piece of stone. At the corner point Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

☆U.S. Government Printing Office: 1980—778-251/292

Dependent Resurvey of a Portion of the Subdivisional Lines of
T. 40 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
	T 40 S R 21 E ¼ S 32 | S 33 1979 Deposit the mkd. stone alongside the aluminum post. Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor. During the course of completing this project a new relocation of U.S. Highway No. 163 was built over the cor. which necessitated reference monuments for the preservation of this cor. from Hubs established by the road contractor. The cors. may or may not have been buried under new asphalt road. from the corner point An aluminum post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 37° 52' E., 223 lks. dist., with aluminum cap mkd. RM T40S R21E ¼ S33 147 FT 1981 and an arrow pointing to the true corner point. An aluminum post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 51° 25' W., 223 lks. dist., with aluminum cap mkd. RM T40S R21E ¼ S32 147 FT 1981 and an arrow pointing to the true corner point. N. 0° 04' W., beginning new measurement.
40.01	Point for the cor. of secs. 28, 29, 32, and 33, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 40 S R 21 E S 29 | S 28 S 32 | S 33 1979 Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.
	From the cor. of secs. 27, 28, 33, and 34. N. 89° 56' W., bet. secs. 28 and 33.
40.06	The ¼ sec. cor. of secs. 28 and 33, monumented with a sandstone, 14 x 10 x 10 ins., firmly set 6 ins. in the ground and plainly mkd. ¼ on N face, with a mound of stone N of cor. At the corner point Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

CHAINS	
	T 40 S R 21 E ¼ S 28 S 33 1979 Deposit the mkd. stone alongside the aluminum post.
	N. 89° 56' W., beginning new measurement.
40.02	The cor. of secs. 28, 29, 32, and 33.
	N. 0° 05' W., bet. secs. 28 and 29.
40.01	Point for the ¼ sec. cor. of secs. 28 and 29, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 28 ins. long, 2½ ins. diam., on solid clay and in a mound of stone, 4½ ft. base, to top of aluminum cap, mkd. T 40 S R 21 E ¼ S 29 | S 28 1979
80.02	Point for the cor. of secs. 20, 21, 28, and 29, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 40 S R 21 E S 20 | S 21 S 29 | S 28 1979
	From the cor. of secs. 21, 22, 27, and 28. N. 89° 54' W., bet. secs. 21 and 28.
40.04	Point for the ¼ sec. cor. of secs. 21 and 28, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 40 S R 21 E ¼ S 21 S 28 1979
80.08	The cor. of secs. 20, 21, 28, and 29.
	N. 0° 01' W., bet. secs. 20 and 21.

☆U.S. Government Printing Office: 1980—778-251/292

Dependent Resurvey of a Portion of the Subdivisional Lines of
T. 40 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
40.01	Point for the ¼ sec. cor. of secs. 20 and 21, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 28 ins. long, 2½ ins. diam., over a cross (X) chiseled on solid sandstone, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd. T 40 S R 21 E ¼ S 20 | S 21 1979
80.02	The cor. of secs. 16, 17, 20, and 21, monumented with an iron post, 2 ins. diam., firmly set, with brass cap, mkd. as described in the official record of the 1929 resurvey.
	From the cor. of secs. 15, 16, 21, and 22. N. 89° 57' W., bet. secs. 16 and 21.
40.04	The ¼ sec. cor. of secs. 16 and 21, monumented with a broken sandstone, plainly mkd. ¼ on a fragmented piece of stone. At the corner point Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 40 S R 21 E S 16 ¼ S 21 1979 Deposit the mkd. stone alongside the aluminum post. N. 89° 57' W., beginning new measuremement.
40.03	The cor. of secs. 16, 17, 20, and 21.
	From the cor. of secs. 9, 10, 15, and 16. S. 89° 56' W., bet. secs. 9 and 16.
39.67	The ¼ sec. cor. of secs. 9 and 16, monumented with an iron post, 1 in. diam., firmly set, with brass cap, mkd. as described in the official record of the 1929 resurvey.
	From the cor. of secs. 3, 4, 9, and 10. West, bet. secs. 4 and 9.
39.57	The ¼ sec. cor. of secs. 4 and 9, monumented with an iron post, 1 in. diam., firmly set, with brass cap mkd. as described in the official record of the 1929 resurvey.

CHAINS	
	From the cor. of secs. 28, 29, 32, and 33.
	West, bet. secs. 29 and 32.
40.02	Point for the ¼ sec. cor. of secs. 29 and 32, at proportionate distance; there is no remaining evidence of the original corner.
	Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T 40 S R 21 E ¼ S 29 / S 32 1979
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.
80.04	The cor. of secs. 29, 30, 31, and 32, monumented with an iron post, 2 ins. diam., firmly set, with brass cap mkd. as described in the official record of the 1929 resurvey.
	From the cor. of secs. 20, 21, 28, and 29.
	N. 89° 30' W., bet. secs. 20 and 29.
40.07	The ¼ sec. cor. of secs. 20 and 29, monumented with a flintstone, 10 x 8 x 6 ins., firmly set 4 ins. in the ground and plainly mkd. ¼ on N face, with a mound of stone N of cor.
	At the corner point
	Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T 40 S R 21 E ¼ S 20 / S 29 1979
	Deposit the mkd. stone alongside the aluminum post.
	Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.
	S. 89° 29' W., beginning new measurement.
39.95	The cor. of secs. 19, 20, 29, and 30, monumented with a cross (X) chiseled in solid sandstone, 5 notches on E and 2 notches on S edges. There is no remaining evidence of the 1929 iron post.
	At the corner point
	Set an aluminum post, 28 ins. long, 2½ ins. diam., over the cross (X) chiseled on solid sandstone, and in a mound of stone, 4½ ft. base, to top of aluminum cap, mkd.
	T 40 S R 21 E S 19 | S 20 S 30 | S 29 1979

☆U.S. Government Printing Office: 1980 – 778-251/292

CHAINS	
	Survey of the Subdivision of Section 25, T. 40 S., R. 21 E., Salt Lake Meridian, Utah
	From the ¼ sec. cor. of secs. 24 and 25.
	S. 0° 01' W., on the N-S centerline of sec. 25.
40.15	Point for the center ¼ sec. cor. of sec. 25, at intersection with the E-W centerline. Not monumented.
54.58	Intersect the adjusted record meander line of the 1899 survey of the right bank of the San Juan River. Not monumented.
	From the ¼ sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp., hereinbefore described.
	N. 89° 48' W., on the E-W centerline of sec. 25.
40.05	Point for the center ¼ sec. cor. of sec. 25.
60.08	Point for the center W 1/16 sec. cor. of sec. 25. Not monumented.
80.11	The ¼ sec. cor. of secs. 25 and 26.
	From the point for the center W 1/16 sec. cor. of sec. 25.
	S. 0° 01' W., on the N-S centerline of the SW¼ of sec. 25.
20.00	Point for the SW 1/16 sec. cor. of sec. 25, at intersection with the E-W centerline of the SW¼.
	Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 40 S R 21 E SW 1/16 S 25 1981
	Cor. is set in N-S fence line.
22.74	Point for the special meander cor. of sec. 25, at intersection with the adjusted record meander line of the 1899 survey of the right bank of the San Juan River.
	Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 40 S R 21 E W S 25 | SMC W 1982
	Thence, S. 0° 01' W., on a partition line between private and federally accretion lands.

189

Survey of the Subdivision of Section 25,
T. 40 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
17.24	Point for the special meander cor. at intersection with the present mean high water mark of the right bank of the San Juan River. Not monumented.
	From the S 1/16 sec. cor. of secs. 25 and 26.
	S. 89° 48' E., along the E-W centerline of the SW¼ of sec. 25.
20.03	The SW 1/16 sec. cor. of sec. 25.
	Survey of the Subdivision of Section 33, T. 40 S., R. 21 E., Salt Lake Meridian, Utah
	From the ¼ sec. cor. of secs. 28 and 33.
	South, on the N-S centerline of sec. 33.
38.00	Center line of U.S. Highway No. 163, bears E and W.
39.97	Point for the center ¼ sec. cor. of sec. 33, at intersection with the E-W centerline.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 S R 21 E C¼ S 33 1981
	Cor. is located on the NW edge of the Utah Department of Transportation asphalt mix circle.
42.30	Power line, bears N. 86° 34' E. and S. 86° 34' W.
60.00	Point for the center S 1/16 sec. cor. of sec. 33, at intersection with the E-W centerline of the S½ of sec. 33.
	Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd. C | S 1/16 | S 33 C 1981
63.35	Point for the special meander cor. at the present mean high water mark of the right bank of the San Juan River. Not monumented.
	From the ¼ sec. cor. of secs. 33 and 34.
	N. 89° 59' W., on the E-W centerline of sec. 33.
14.70	Power line, bears N. 58° 33' E. and S. 58° 33' W.
20.01	Point for the center E 1/16 sec. cor. of sec. 33.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. E 1/16 C ——— C S 33 1981
40.02	The center ¼ sec. cor. of sec. 33.
60.01	Point for the center W 1/16 sec. cor. of sec. 33.
	Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. W 1/16 C ——— C S 33 1981
	Deposit a lodge pole pine post, 6 ft. long, alongside the aluminum post.
80.00	The ¼ sec. cor. of secs. 32 and 33.
	From the center W 1/16 sec. cor. of sec. 33.
	S. 0° 01' E., on the N-S centerline of the SW¼ of sec. 33.
3.55	Power line, bears N. 86° 34' E. and S. 86° 34' W.
20.03	Point for the SW 1/16 sec. cor. of sec. 33, at intersection with the E-W centerline of the SW¼, falls on the N edge of a gravel road and is impractical to monument
	from which
	An aluminum post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, bears N. 45° E., 50 lks. dist., with aluminum cap mkd. RM SW 1/16 S33 33 FT 1981.
	An aluminum post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, bears N. 45° W., 50 lks. dist., with aluminum cap mkd. RM SW 1/16 S33 33 FT 1981.
31.07	Point for the special meander cor. at the present mean high water mark of the right bank of the San Juan River. Not monumented.
	From the center S 1/16 sec. cor. of sec. 33.
	N. 89° 59' W., on the E-W centerline of the SW¼ of sec. 33, which is parallel to the centerline of the section.
19.99	The SW 1/16 sec. cor. of sec. 33.
39.98	The S 1/16 sec. cor. of secs. 32 and 33.

191

Survey of the Subdivision of Section 34,
T. 40 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS	
	Survey of the Subdivision of Section 34, T. 40 S., R. 21 E., Salt Lake Meridian, Utah
	From the ¼ sec. cor. of secs. 27 and 34.
	South, on the N-S centerline of sec. 34.
2.00	Center line of U.S. Highway No. 163, bears NE and SW.
7.72	Power line, bears N. 58° 33' E. and S. 58° 33' W.
39.91	Point for the center ¼ sec. cor. of sec. 34, at intersection with the E-W centerline.
	Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 40 S R 21 E C¼ S 34 1981
54.37	Point for the special meander cor. at the present mean high water mark of the right bank of the San Juan River. Not monumented.
	From the ¼ sec. cor. of secs. 33 and 34.
	N. 89° 54' E., on the E-W centerline of sec. 34.
40.00	The center ¼ sec. cor. of sec. 34.
69.83	Point for the special meander cor. of sec. 34, at intersection with the adjusted record meander line of the 1899 survey of the right bank of the San Juan River.
	Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 40 S R 21 E C S 34 C SMC 1981
	Thence, S. 3° 59' E., along the partition line between federal and private owned accretion land.
20.36	Point for the special meander cor. of sec. 34, at proportionate distance, marking the S terminal line of the partition line between private and federally owned accretion lands.
	Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 40 S R 21 E S 34 | SMC 1982

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS

Portion of the Meanders of
T. 40 S., R. 21 E., Salt Lake Meridian, Utah

From the true point for the meander cor. of sec. 31, T. 40 S., R. 22 E., hereinbefore described.

Thence, with an informative traverse of the present right bank of the San Juan River through sec. 25.

N. 70° 14' W., 12.74

N. 85° 45' W., 7.02 chs.

S. 79° 41' W., 35.16 chs.

N. 68° 45' W., 6.99 — Point for the special meander cor. of sec. 25, hereinbefore described.

Thence, with the meanders of the present right bank of the San Juan River through sec. 25.

N. 68° 45' W., 0.82 chs.

N. 37° 47' W., 0.88 chs.

S. 85° 50' W., 12.76 chs. — To meander cor. of secs. 25 and 36, hereinbefore described.

Thence, with an informative traverse of the present right bank of the San Juan River.

S. 67° 23' W., 6.50 chs. — To the meander cor. of secs. 35 and 36, hereinbefore described.

S. 40° 06' W., 14.36 chs.

S. 55° 13' W., 11.82 chs.

S. 31° 56' W., 7.15 chs.

S. 47° 04' W., 8.80 chs.

S. 62° 35' W., 4.63 chs.

S. 82° 23' W., 26.90 chs.

S. 73° 57' W., 3.87 chs.

S. 53° 27' W., 7.97 chs.

S. 29° 10' W., 7.90 chs.

S. 59° 54' W., 6.83 chs.

S. 54° 55' W., 10.69 chs. — The special meander cor. of sec. 34 hereinbefore described.

Portion of the Meanders of
T. 40 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS		
	Thence, with the meanders of the present right bank of the San Juan River through sec. 34.	
	S. 54° 55' W., 0.96 chs.	
	S. 67° 18' W., 3.07 chs.	
	S. 33° 46' W., 2.70 chs.	
	S. 84° 35' W., 6.30 chs.	
	N. 62° 26' W., 51.48 chs.	At 22.40 chs. on this course intersect the N-S centerline of sec. 34. At 33.47 chs. on this course, intersect the adjusted original (1899) meander in sec. 34.
	S. 41° 11' W., 6.49 chs.	
	S. 64° 25' W., 3.47 chs.	
	S. 43° 53' W., 9.83 chs.	True point for the meander cor. of secs. 33 and 34.
	Thence, with the meanders of the present right bank of the San Juan River through sec. 33.	
	S. 75° 23' W., 5.34 chs.	
	S. 49° 13' W., 9.70 chs.	
	N. 86° 38' W., 4.69 chs.	
	N. 80° 50' W., 13.42 chs.	At 2.85 chs. on this course intersect the N-S centerline of the SE¼ of sec. 33.
	S. 65° 41' W., 8.46 chs.	
	S. 83° 37' W., 8.59 chs.	At 1.89 chs. on this course point for the special meander cor. on the N-S center line of sec. 33.
	S. 32° 45' W., 2.86 chs.	
	S. 56° 40' W., 3.99 chs.	
	S. 74° 28' W., 10.82	At 8.76 chs. on this course. Point for the special meander cor. on the N-S center line of the SW¼ of sec. 33.
	S. 13° 26' W., 2.71 chs.	
	S. 46° 08' W., 8.36 chs.	True point for the meander cor. of sec. 33 on the S. bdy. of the Tp., hereinbefore described.

☆U.S. Government Printing Office: 1980—778-251/292

Portion of the Meanders of
T. 40 S., R. 21 E., Salt Lake Meridian, Utah

CHAINS

Thence by calculation with the adjusted original (1899) meanders of the right bank of the San Juan River through sec. 25.

From a point for the record meander cor. of secs. 25 and 30 on the E. bdy. of the Tp., hereinbefore described.

Thence,

S. 53° 00' W., 6.30 chs.

S. 54° 59' W., 6.50 chs.

S. 62° 59' W., 5.41 chs.

N. 80° 06' W., 11.24 chs.

S. 73° 58' W., 5.51 chs.

N. 85° 05' W., 6.32 chs.

S. 83° 12' W., 13.03 chs. At 2.23 chs. on this course intersect the N-S centerline of sec. 25.

S. 59° 44' W., 8.01 chs.

S. 39° 14' W., 3.79 chs. The special meander cor. on the N-S centerline of the SW ¼ of sec. 25, hereinbefore described.

S. 39° 14' W., 22.19 chs. The meander cor. of secs. 25 and 36, hereinbefore described.

Thence by calculation with the adjusted original (1899) meanders of the right bank of the San Juan River through sec. 35.

From a point for the record meander cor. of secs. 35 and 36, hereinbefore described.

Thence,

S. 81° 49' W., 8.89 chs.

N. 82° 55' W., 10.87 chs.

S. 66° 02' W., 18.47 chs.

S. 51° 45' W., 7.79 chs.

S. 67° 47' W., 8.98 chs.

S. 76° 03' W., 3.99 chs.

S. 23° 12' W., 4.19 chs.

S. 52° 01' W., 4.49 chs.

S. 42° 29' W., 4.79 chs.

S. 57° 31' W., 8.68 chs.

CHAINS			
	S. 69° 32' W.,	9.98 chs.	Point for the meander cor. of secs. 34 and 35, hereinbefore described.
	Thence by calculation with the adjusted original (1899) meanders of the right bank of the San Juan River through sec. 34.		
	S. 76° 28' W.,	16.79 chs.	At 10.45 chs. on this course the special meander cor. of sec. 34 on the E-W center line of sec. 34, hereinbefore described.
	N. 85° 02' W.,	11.29 chs.	
	S. 80° 28' W.,	15.69 chs.	
	S. 41° 27' W.,	5.40 chs.	
	S. 54° 42' W.,	11.80 chs.	At 3.89 chs. on this course the point of intersection with the present meander of the right bank of the San Juan River.
	S. 78° 43' W.,	11.29 chs.	
	S. 55° 27' W.,	5.50 chs.	
	S. 82° 28' W.,	8.19 chs.	Intersect the sec. line of secs. 33 and 34, at a record bearing and distance (S. 0° 02' E., 20.25 chs. dist.) from the ¼ cor. of secs. 33 and 34.

General Description

The elevation is about 5,000 feet above sea level. The soil varies from silt along the river bottoms to sand dunes in many areas. The San Juan River crosses the township from east to west. U.S. Highway No. 163 crosses the southern portion of the township.

☆U.S. Government Printing Office: 1980—778-251/292

Form 9600-11
(August 1979)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Donzil Worthington	Surveying Technician
Larry Judd	Surveying Technician
John Mavor	Survey Aid
Richard Zaninovich	Supervisory Cadastral Surveyor
Don Buhler	Supervisory Cadastral Surveyor

197

CERTIFICATE OF SURVEY

(I) (~~We~~) Jerry L. Thomas, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 3rd day of May, 1979, (I) (~~We~~) have dependently resurveyed a portion of the Eighth Standard Parallel South, the east and north boundaries, a portion of the subdivisional lines, a partial subdivision of sections 25, 33, and 34, and the meander lines of the right bank of the San Juan River of T. 40 S., R. 21 E.,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), (~~us~~) and under (my) (~~our~~) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

April 27, 1983 (Date)

Jerry L. Thomas (Cadastral Surveyor)
Supervisory

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the Eighth Standard Parallel South, the east and north boundaries, a portion of the subdivisional lines, a partial subdivision of sections 25, 33, and 34, and the meander lines of the right bank of the San Juan River of T. 40 S., R. 21 E., Salt Lake Meridian, Utah

executed by Jerry L. Thomas, Supervisory Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

August 15, 1983 (Date)

Glen B Hatch (~~Chief, Cadastral Survey Examination and Approval Staff~~)
Chief Cadastral Surveyor for Utah

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in~~

~~, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief, Cadastral Survey Examination and Approval Staff)~~
Chief Cadastral Surveyor for Utah

Form 9600-9
(December 1979)
(formerly 9180-6)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

R606

ORIGINAL

198

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF THE NORTH BOUNDARY,

A PORTION OF THE EAST BOUNDARY (COLORADO GUIDE MERIDIAN)

A PORTION OF THE SUBDIVISIONAL LINES,

A SURVEY OF A PORTION OF THE SOUTH BOUNDARY

OF

SECTION 30,

A PARTIAL SUBDIVISIONAL SURVEY

OF

SECTIONS 28, 29 AND 30,

AND THE MEANDERS OF THE RIGHT BANK

OF THE SAN JUAN RIVER

IN

TOWNSHIP 40 SOUTH, RANGE 22 EAST

Of the Salt Lake Meridian,

In the State of Utah.

EXECUTED BY

Jerry L. Thomas Supervisory Cadastral Surveyor

Under special instructions dated May 2, 19 79, approved May 3, 1979,

, which provided for the surveys included under U.S. Survey/Group

Number 592, and assignment instructions dated May 7, 19 79.

Survey commenced August 14, 19 79

Survey completed October 23, 19 81

INDEX DIAGRAM

Township 40 South, Range 22 East,

8 6	7 5 25 25	7 4 22 25	6 3 18 21	5 2 13 17	5 1 4 13
7	8 24	9 21 23	10 16 20	11 12 16	12 3 11
18	17	16 20	15 15 19	14 11	13 2 10
19 27	20 26	21 22	22 14 18	23 10 14	24 2 9
30 27 28	29 23	28 18	27 14	26 9	25
31	32	33	34	35	36

Subdivision of Section 28 - Page 28
Subdivision of Section 29 - Page 29
Subdivision of Section 30 - Page 30
Meander Lines - Page 32

GPO 855-927

Township 40 South, Range 22 East, Salt Lake Meridian, Utah

CHAINS

The following field notes are those of the dependent resurvey of the north boundary, a portion of the east boundary (Colorado Guide Meridian), a portion of the subdivisional lines, a survey of a portion of the south boundary of section 30, a partial subdivisional survey of sections 28, 29 and 30, and the meanders of the right bank of the San Juan River in Township 40 South, Range 22 East, Salt Lake Meridian, Utah.

T. 40 S., R. 22 E.

	Surveyed by	Retr. or Resurveyed by	
NORTH BOUNDARY			
All	A.D. Ferron 1883		
All		Page and Lentz	1899
All		Miller and Thomas	1912
EAST BOUNDARY (Colorado Guide Meridian)			
All	Ferdinand Dickert 1878		
All		A.D. Ferron	1883
North of the San Juan River S½ of Sec. 24		Page and Lentz	1899
Portion		Andrew Nelson	1953

WEST BOUNDARY

See history of survey in T. 40 S., R. 21 E., surveyed concurrently.

SUBDIVISION

North of the San Juan River Page and Lentz 1899

Meanders of the San Juan River Right Bank Page and Lentz 1899

NOTE: The corner of Tps. 39 and 40 S., Rs. 22 and 23 E., reestablished in 1883 by A.D. Ferron was accepted in 1899 by Page and Lentz as the beginning point for their independent resurvey of the north and east boundaries of T. 40 S., R. 22 E.

The survey was executed in accordance with the specifications set forth in the Manual of Survey Instructions, 1973, and the Special Instructions dated May 2, 1979.

The directions of lines refer to the true meridian as determined by observations of Polaris and direct altitude observations of the sun, projected by fore- and backsights.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

201

Township 40 South, Range 22 East, Salt Lake Meridian, Utah

CHAINS

The geographic position of the corner of sections 24 and 25, T. 40 S., R. 22 E., and sections 19 and 30, T. 40 S., R. 23 E., as determined by ties to the U.S.C. and G.S. triangulation station "BLUFF" and "UMA" is as follows:

Latitude 37° 17' 15.3" N. Longitude 109° 26' 21.4" W.

The mean magnetic declination is 13° 30' E.

Dependent Resurvey of a Portion of the East Boundary, T. 40 S., R. 22 E., Salt Lake Meridian, Utah

---

(Reestablishment of the Independent Resurvey Executed by Hubert D. Page and James M. Lentz in 1899)

Beginning at the ¼ sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., projecting 6 ins. above the ground, with a brass cap, mkd. as described in the official record of the 1953 resurvey executed by Andrew Nelson.

N. 0° 02' W., bet. secs. 19 and 24.

Over gently rolling land, through low brush.

39.91 The cor. of secs. 13, 18, 19, and 24, monumented with a mound of stone. No mkd. stone found. This is accepted as the best available evidence of the position of the original cor.

At the corner point (center of mound)

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 40 S
R 22 E | R 23 E
S 13 | S 18
S 24 | S 19
1979

Raise a mound of stone, 3½ ft. base, 2½ ft. high, W of cor.

North, bet. secs. 13 and 18.

Over rolling foothills, through low brush.

39.96 The ¼ sec. cor. of secs. 13 and 18, monumented with a sandstone, 16 x 10 x 6 ins., firmly set, 8 ins. in the ground, mkd. ¼ on W face.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 40 S
R 22 E | R 23 E
¼
S 13 | S 18
1979

CHAINS

Bury the mkd. stone alongside the iron post.

Raise a mound of stone, 3½ ft. base, 2½ ft. high, W of cor.

N. 0° 06' E., beginning new measurement.

39.94 The cor. of secs. 7, 12, 13, and 18, monumented with a sandstone, 15 x 6 x 5 ins., firmly set, 6 ins. in the ground, mkd. 2 notches on N edge and 4 notches on S edge.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 40 S
R 22 E | R 23 E
S 12 | S 7
S 13 | S 18
1979

Bury the mkd. stone alongside the iron post.

Raise a mound of stone, 3½ ft. base, 2½ ft. high, W of cor.

North, bet. secs. 7 and 12.

Over broken foothills.

39.96 Point for the ¼ sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, and in a mound of stone, 4½ ft. base, to top of aluminum cap, mkd.

T 40 S
R 22 E | R 23 E
¼
S 12 | S 7
1979

79.92 The cor. of secs. 1, 6, 7, and 12, monumented with a sandstone, 20 x 14 x 8 ins., firmly set, 8 ins. in the ground, mkd. 1 notch on N edge and 5 notches on S edge.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 40 S
R 22 E | R 23 E
S 1 | S 6
S 12 | S 7
1979

Bury the mkd. stone alongside the aluminum post.

Raise a mound of stone, 3½ ft. base, 2½ ft. high, W of cor.

203

Dependent Resurvey of a Portion of the East Boundary,
T. 40 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
	N. 0° 02' E., bet. secs. 1 and 6.
	Over rolling land, through low brush.
40.05	The ¼ sec. cor. of secs. 1 and 6, monumented with a sandstone, 17 x 10 x 4 ins., firmly set, 6 ins. in the ground, mkd. ¼ on W face.
	At the corner point
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 40 S
R 22 E R 23 E
¼
S 1 | S 6
1979

Bury the mkd. stone alongside the aluminum post.

Raise a mound of stone, 3½ ft. base, 2½ ft. high, W of cor.

N. 0° 04' E., beginning new measurement.

39.98 The cor. of Tps. 39 and 40 S., Rs. 22 and 23 E., monumented with a sandstone, 30 x 18 x 8 ins., firmly set, 10 ins. in the ground, mkd. 6 notches on N, E, S, and W edges, COLO GM on the N face, R23E on the E face, and R22E on the W face.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., on solid sandstone, and in a mound of stone, 4½ ft. base, to top of aluminum cap, mkd.

T 39 S
R 22 E R 23 E
S 36 | S 31
S 1 | S 6
T 40 S
1979

Bury the mkd. stone in mound, alongside the aluminum post.

Cor. is located 15 lks. W of a wash, 15 lks. wide, draining SE.

Dependent Resurvey of the North Boundary of
T 40 S., R. 22 E., Salt Lake Meridian, Utah

(Reestablishment of the Independent Resurvey
Executed by Hubert D. Page and James M. Lentz in 1899
and the Retracement Executed by Danial B. Miller
and Joseph C. Thoma in 1912)

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	N. 89° 53' W., bet. secs. 1 and 36.
	Over broken foothills.
39.64	The ¼ sec. cor. of secs. 1 and 36, monumented with a sandstone, 18 x 12 x 3 ins., firmly set, 6 ins. in the ground, mkd. ¼ on N face.
	At the corner point
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 3 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.
	T 39 S R 22 E ¼ S 36 / S 1 T 40 S 1979
	Bury the mkd. stone in mound, alongside the aluminum post.
	S. 89° 54' W., beginning new measurement.
39.90	The cor. of secs. 1, 2, 35, and 36, monumented with a cobblestone, 16 x 12 x 6 ins., firmly set, 6 ins. in the ground, mkd. 1 notch on E edge and 5 notches on W edge.
	At the corner point
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T 39 S R 22 E S 35 | S 36 S 2 | S 1 T 40 S 1979
	Bury the mkd. stone alongside the aluminum post.
	Raise a mound of stone, 3½ ft. base, 1½ ft. high, W of cor.
	Cor. falls 55 lks. E of top of a knoll, on the E side of Recapture Wash.
	N. 89° 50' W., bet. secs. 2 and 35.
	Over broken sandstone.
40.00	The ¼ sec. cor. of secs. 2 and 35, monumented with a sandstone, 11 x 7 x 6 ins., firmly set, 5 ins. in the ground, dimly mkd. ¼ on N face.
	At the corner point
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 3 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.
	T 39 S R 22 E ¼ S 35 / S 2 T 40 S 1979

CHAINS	
	Bury the mkd. stone in mound, alongside the aluminum post.
	S. 89° 52' W., beginning new measurement.
40.04	The cor. of secs. 2, 3, 34, and 35, monumented with a sandstone, 18 x 13 x 3 ins., firmly set, 6 ins. in the ground, mkd. 2 notches on E edge and 4 notches on W edge. At the corner point Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 39 S R 22 E S 34 | S 35 S 3 | S 2 T 40 S 1979 Bury the mkd. stone alongside the aluminum post. Raise a mound of stone, 3½ ft. base, 2½ ft. high, W of cor. Cor. is located 1.00 ch. W of wash in the bottom of Chimney Rock Draw, draining SE.
	N. 89° 49' W., bet. secs. 3 and 34. Over broken sandstone.
40.00	The ¼ sec. cor. of secs. 3 and 34, monumented with a sandstone, 13 x 9 x 3 ins., firmly set, 6 ins. in the ground, mkd. ¼ on N face. At the corner point Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 39 S R 22 E S 34 ¼ S 3 T 40 S 1979 Bury the mkd. stone alongside the aluminum post. Raise a mound of stone, 3½ ft. base, 2½ ft. high, N of cor.
	West, beginning new measurement.
40.05	The cor. of secs. 3, 4, 33, and 34, monumented with a sandstone, 17 x 10 x 5 ins., firmly set, 5 ins. in the ground, mkd. 3 notches on E and W edges. At the corner point Set an aluminum post, 30 ins. long, 2½ ins. diam., 17 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base, to top of aluminum cap, mkd.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	T 39 S R 22 E S 33 | S 34 S 4 | S 3 T 40 S 1979 Bury the mkd. stone alongside the aluminum post. Raise a mound of stone, 3½ ft. base, 2½ ft. high, W of cor. Cor. is located 1.00 ch. E of rim of draw, draining SE.
	N. 89° 53' W., bet. secs. 4 and 33. Over broken sandstone.
39.90	The ¼ sec. cor. of secs. 4 and 33, monumented with a sandstone, 17 x 10 x 5 ins., firmly set, 8 ins. in the ground, mkd. ¼ on N face. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 39 S R 22 E ¼ S 33 S 4 T 40 S 1979 Bury the mkd. stone alongside the iron post. Raise a mound of stone, 3½ ft. base, 2½ ft. high, N of cor.
	N. 89° 56' W., beginning new measurement.
40.04	The cor. of secs. 4, 5, 32, and 33, monumented with a sandstone, 16 x 8 x 4 ins., firmly set, 6 ins. in the ground, mkd. 4 notches on E edge and 2 notches on W edge. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 39 S R 22 E S 32 | S 33 S 5 | S 4 T 40 S 1979 Bury the mkd. stone alongside the iron post. Raise a mound of stone, 3½ ft. base, 2½ ft. high, W of cor.
	N. 89° 53' W., bet. secs. 5 and 32. Over rolling land, through low brush.
29.95	Center of U.S. Highway No. 163, bears N and S.

CHAINS	
39.98	The ¼ sec. cor. of secs. 5 and 32, monumented with an iron pipe, 1½ ins. diam., projecting 18 ins. above the ground, with an unmkd. brass cap. Alongside the iron pipe is a sandstone, 16 x 10 x 4 ins., mkd. ¼. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 39 S R 22 E ¼ S 32 / S 5 T 40 S 1979 Bury 1½ in. pipe and the mkd. stone alongside the iron post. Raise a mound of stone, 3½ ft. base, 2½ ft. high, N of cor.
	S. 89° 49' W., beginning new measurement.
1.18	Power line, bears NE and SW.
6.26	Power line, bears N and S.
39.87	The cor. of secs. 5, 6, 31, and 32, monumented with an iron pipe, 1½ ins. diam., projecting 14 ins. above the ground, with an unmkd. brass cap. Alongside the iron pipe is a sandstone, 12 x 10 x 3 ins., mkd. 2 notches on one edge, other marks have been obliterated. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 39 S R 22 E S 31 | S 32 S 6 | S 5 T 40 S 1979 Bury the 1½ in. pipe and mkd. stone alongside the iron post.
	N. 88° 33' W., bet. secs. 6 and 31. Over rolling land, through low brush.
40.21	The ¼ sec. cor. of secs. 6 and 31, monumented with a sandstone, 22 x 20 x 6 ins., firmly set, 8 ins. in the ground, mkd. ¼ on N face. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS

T 39 S R 22 E
¼ S 31 / S 6
T 40 S
1979

Bury the mkd. stone alongside the iron post.

S. 88° 34' W., beginning new measurement.

39.46 The cor. of Tps. 40 S., Rs. 21 and 22 E., set and mkd. as described in the field notes of the concurrent resurvey of T. 40 S., R. 21 E.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 40 S., R. 22 E., Salt Lake Meridian, Utah

---

(Reestablishment of the Survey Executed by Hubert D. Page and James M. Lentz in 1899)

From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., and in a mound of stone, with brass cap mkd. as described in the official record of the 1953 resurvey executed by Andrew Nelson.

N. 89° 52' W., bet. secs. 24 and 25.

Over rolling land, through low brush.

39.99 Point for the ¼ sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 40 S R 22 E
¼ S 24 / S 25
1979

79.94 The cor. of secs. 23, 24, 25, and 26, monumented with a mound of stone, no mkd. stone found; this is accepted as the best available evidence of the position of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 40 S R 22 E
S 23 | S 24
S 26 | S 25
1979

Raise a mound of stone, 3½ ft. base, 2½ ft. high, W of cor.

S. 0° 01' E., bet. secs. 25 and 26.

Over level river bottom, through dense brush.

CHAINS	
33.93	Point for the new meander cor. of secs. 25 and 26, on the present right bank of the San Juan River. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 S R 22 E S 26 | S 25 | MC 1979 No evidence of original meander corner.
	From the cor. of secs. 23, 24, 25, and 26. N. 0° 01' W., bet. secs. 23 and 24. Over broken sandstone.
40.00	Point for the ¼ sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., on solid sandstone, mkd. with a cross (X), and in a mound of stone, 4½ ft. base, to top of brass cap, mkd. T 40 S R 22 E ¼ | S 23 | S 24 | 1979
80.00	The cor. of secs. 13, 14, 23, and 24, determined from the original bearing object. A cross (X) chiseled on the east face of a sandstone ledge, bears West, 14 lks. dist. True point for the cor. falls in Recapture Wash and is not monumented. from which An X BO chiseled on the E face of a sandstone ledge, 11 ft. above the stream bed of Recapture Creek, bears S. 62° 25' W., 30 lks. dist. An X BO chiseled on the E face of a sandstone ledge, 12 ft. above the stream bed of Recapture Creek, bears N. 36° 13' W., 39 lks. dist.
	From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., hereinbefore described. N. 89° 30' W., bet. secs. 13 and 24.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	Over rolling land, through low brush.
39.73	The ¼ sec. cor. of secs. 13 and 24, monumented with a cross (X) on solid sandstone, with a mound of stone to the N. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., on solid sandstone, and in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 40 S R 22 E ¼ S 13 / S 24 1979
	S. 89° 47' W., beginning new measurement.
40.20	The cor. of secs. 13, 14, 23, and 24.
	N. 0° 53' W., bet. secs. 13 and 14. Along W edge of Recapture Wash.
39.96	Point for the ¼ sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 S R 22 E ¼ S 14 | S 13 1979
	Raise a mound of stone, 3½ ft. base, 2½ ft. high, W of cor.
79.92	Point for the cor. of secs. 11, 12, 13, and 14, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., on solid sandstone, mkd. with a cross (X), and in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 40 S R 22 E S 11 | S 12 S 14 | S 13 1979
	From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., hereinbefore described. N. 89° 04' W., bet. secs. 12 and 13. Over rolling land, through low brush.

211 Dependent Resurvey of a Portion of the Subdivisional Lines, T. 40 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
41.16	The ¼ sec. cor. of secs. 12 and 13, monumented with a sandstone, 11 x 8 x 4 ins., firmly set, 6 ins. in the ground, mkd. ¼ on N face. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 S R 22 E ¼ S 12 / S 13 1979 Bury the mkd. stone alongside the iron post.
	S. 89° 16' W., beginning new measurement.
40.09	The cor. of secs. 11, 12, 13, and 14.
	N. 1° 57' E., bet. secs. 11 and 12. Along W edge of Recapture Wash.
39.96	The ¼ sec. cor. of secs. 11 and 12, monumented with a cobblestone, 20 x 13 x 6 ins., firmly set, 8 ins. in the ground, mkd. ¼ on W face. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 S R 22 E ¼ S 11 | S 12 1979 Bury the mkd. stone alongside the iron post. Raise a mound of stone, 3½ ft. base, 2½ ft. high, W of cor. Cor. is located on top of a ledge on the W side of Recapture Wash.
	N. 0° 02' E., beginning new measurement.
40.04	The cor. of secs. 1, 2, 11, and 12, monumented with a sandstone, 10 x 8 x 3 ins., firmly set, 4 ins. in the ground, mkd. 1 notch on E edge and 5 notches on S edge. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 S R 22 E S 2 | S 1 S 11 | S 12 1979

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	Bury the mkd. stone alongside the iron post.
	Raise a mound of stone, 3½ ft. base, 2½ ft. high, W of cor.
	From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., hereinbefore described.
	N. 89° 55' W., bet. secs. 1 and 12.
	Over rolling land, through low brush.
39.51	The ¼ sec. cor. of secs. 1 and 12, monumented with a sandstone, 14 x 7 x 4 ins., firmly set, 6 ins. in the ground, mkd. ¼ on N face.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 40 S R 22 E ¼ S 1 / S 12 1979
	Bury the mkd. stone alongside the iron post.
	Raise a mound of stone, 3½ ft. base, 2½ ft. high, N of cor.
	N. 89° 46' W., beginning new measurement.
40.36	The cor. of secs. 1, 2, 11, and 12.
	N. 2° 07' W., bet. secs. 1 and 2.
	Over broken foothills on the E side of Recapture Creek.
41.77	The ¼ sec. cor. of secs. 1 and 2, monumented with a sandstone, 15 x 8 x 3 ins., firmly set, 4 ins. in the ground, mkd. ¼ on W face.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd.
	T 40 S R 22 E ¼ S 2 | S 1 1979
	Bury the mkd. stone in mound, alongside the iron post.
	N. 2° 49' E., beginning new measurement.
38.14	The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., hereinbefore described.

213 Dependent Resurvey of a Portion of the Subdivisional Lines, T. 40 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
	From the cor. of secs. 23, 24, 25, and 26.
	N. 89° 59' W., bet. secs. 23 and 26.
	Over level land, through dense brush.
35.10	Point selected for the witness cor. to the ¼ sec. cor. of secs. 23 and 26.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	W C T 40 S R 22 E ¼ < S 23 / S 26 1979
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.
39.99	True point for the ¼ sec. cor. of secs. 23 and 26, at proportionate distance falls in Recapture Creek; there is no remaining evidence of the original corner.
79.98	Point for the cor. of secs. 22, 23, 26, and 27, at proportionate distance longitudinally and record distance latitudinally from the ¼ sec. cor. of secs. 22 and 23; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., on bedrock, and in a mound of stone, 3½ ft. base, to top of brass cap, mkd.
	T 40 S R 22 E S 22 | S 23 S 27 | S 26 1979
	S. 0° 01' E., bet. secs. 26 and 27.
	Over level river bottom, through dense brush.
11.75	Point for the new meander cor. of secs. 26 and 27, on the present right bank of the San Juan River.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 40 S R 22 E S 27 | S 26 MC 1979
	Cor. falls 30 lks. S of the base of sandstone ledge, bearing NE and SW.
	From the cor. of secs. 22, 23, 26, and 27.
	N. 0° 01' W., bet. secs. 22 and 23.

☆U.S. Government Printing Office: 1980—778-251/292

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 40 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
	Asc. from San Juan River bottom.
40.00	The ¼ sec. cor. of secs. 22 and 23, monumented with a cobblestone, 17 x 8 x 6 ins., firmly set, 6 ins. in the ground, mkd. ¼ on W face. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 S R 22 E ¼ S 22 | S 23 1979 Bury the mkd. stone alongside the iron post. Raise a mound of stone, 3½ ft. base, 2½ ft. high, W of cor
	From the cor. of secs. 14, 15, 22, and 23, monumented with a sandstone, 15 x 8 x 6 ins., firmly set, 8 ins. in the ground, mkd. 2 notches on E edge and 3 notches on S edge. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 S R 22 E S 15 | S 14 S 22 | S 23 1979 Bury the mkd. stone alongside the iron post. N. 0° 18' E., bet. secs. 14 and 15. Over rolling land, through low brush.
40.14	The ¼ sec. cor. of secs. 14 and 15, monumented with a sandstone, 18 x 9 x 9 ins., firmly set, 8 ins. in the ground, mkd. ¼ on W face. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 S R 22 E ¼ S 15 | S 14 1979 Bury the mkd. stone alongside the iron post. Raise a mound of stone, 3½ ft. base, 2½ ft. high, W of cor

215

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 40 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
	N. 0° 38' W., beginning new measurement.
38.56	The cor. of secs. 10, 11, 14, and 15, monumented with a mound of stone. No mkd. stone found. This is accepted as the best available evidence of the position of the original corner. At the corner point (center of mound) Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4½ ft. base, to top of brass cap, mkd. T 40 S R 22 E S 10 | S 11 S 15 | S 14 1979 Cor. is located on N slope.
	From the cor. of secs. 11, 12, 13, and 14. N. 89° 50' W., bet. secs. 11 and 14. Ascend.
40.03	The ¼ sec. cor. of secs. 11 and 14, monumented with a sandstone, 17 x 8 x 6 ins., firmly set, 8 ins. in the ground, mkd. ¼ on N face and a mound of stone to the N. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 S R 22 E ¼ S 11 S 14 1979 Bury the mkd. stone alongside the iron post. Raise a mound of stone, 3½ ft. base, 2½ ft. high, N of cor.
	S. 87° 50' W., beginning new measurement.
38.98	The cor. of secs. 10, 11, 14, and 15.
	N. 0° 49' E., bet. secs. 10 and 11. Over broken sandstone.
41.38	The ¼ sec. cor. of secs. 10 and 11, monumented with a sandstone, 20 x 18 x 4 ins., firmly set, 8 ins. in the ground, mkd. ¼ on W face. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	T 40 S R 22 E ¼ S 10 | S 11 1979 Bury the mkd. stone alongside the iron post. Raise a mound of stone, 3½ ft. base, 2½ ft. high, W of cor Cor. is located near S edge of low ridge top, bears E and W.
	N. 0° 01' E., beginning new measurement.
40.01	The cor. of secs. 2, 3, 10, and 11, monumented with a sandstone, 16 x 8 x 4 ins., firmly set, 6 ins. in the ground, mkd. 2 notches on E edge and 5 notches on S edge. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T 40 S R 22 E S 3 | S 2 S 10 | S 11 1979 Bury the mkd. stone alongside the iron post.
	From the cor. of secs. 1, 2, 11, and 12. N. 89° 59' W., bet. secs. 2 and 11. Descend.
39.82	The ¼ sec. cor. of secs. 2 and 11, monumented with a sandstone, 18 x 12 x 5 ins., firmly set, 6 ins. in the ground, mkd. ¼ on N face. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd. T 40 S R 22 E S 2 ¼ S 11 1979 Bury the mkd. stone alongside the iron post. Cor. is located 55 lks. S of wash, draining N. 70° E.
	N. 89° 58' W., beginning new measurement.
39.95	The cor. of secs. 2, 3, 10, and 11.

217

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 40 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
	N. 0° 02' E., bet. secs. 2 and 3.
	Over rolling land, through low brush.
39.92	Point for the ¼ sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 40 S R 22 E ¼ S 3 | S 2 1979
	Raise a mound of stone, 3½ ft. base, 2½ ft. high, W of cor.
79.84	The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., hereinbefore described.
	From the cor. of secs. 22, 23, 26, and 27.
	S. 89° 56' W., bet. secs. 22 and 27.
	Asc. sandstone ledges.
39.97	Point for the ¼ sec. cor. of secs. 22 and 27, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., on solid sandstone, mkd. with a cross (X), and in a mound of stone, 4½ ft. base, to top of brass cap, mkd.
	T 40 S R 22 E ¼ S 22 / S 27 1979
	Cor. is located on W slope of draw, draining S.
79.94	The cor. of secs. 21, 22, 27, and 28, monumented with a mound of stone. No mkd. stone found. This is accepted as the best available evidence of the position of the original corner.
	At the corner point (center of mound)
	Set an iron post, 30 ins. long, 2½ ins. diam., on solid sandstone, mkd. with a cross (X), and in a mound of stone, 4½ ft. base, to top of brass cap, mkd.
	T 40 S R 22 E S 21 | S 22 S 28 | S 27 1979
	S. 0° 01' E., bet. secs. 27 and 28.
	Over rolling land, through low brush.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
39.95	The ¼ sec. cor. of secs. 27 and 28, monumented with a broken sandstone, mkd. ¼ and in a mound of stone. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 S R 22 E ¼ S 28 | S 27 1979 Bury the mkd. stone alongside the iron post. S. 0° 02' E., beginning new measurement.
3.00	Point for the new meander cor. of secs. 27 and 28, on the present right bank of the San Juan River; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 40 S R 22 E S 28 | S 27 MC 1979
	From the cor. of secs. 14, 15, 22, and 23. N. 89° 40' W., bet. secs. 15 and 22. Over rolling land, through low brush.
39.80	The ¼ sec. cor. of secs. 15 and 22, monumented with a sandstone, 10 x 8 x 5 ins., firmly set 4 ins. in the ground mkd. ¼ on N face. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T 40 S R 22 E ¼ S 15 / S 22 1979 Bury the mkd. stone alongside the iron post. S. 89° 57' W., beginning new measurement.
39.96	The cor. of secs. 15, 16, 21, and 22, monumented with a sandstone, 17 x 10 x 4 ins., set alongside a fence cor., mkd. 3 notches on E edge, 3 notches on S edge; T40S on N face; and R22E on S face.

219

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 40 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
	At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T 40 S R 22 E S 16 | S 15 S 21 | S 22 1979 Bury the mkd. stone alongside the iron post.
	N. 0° 09' E., bet. secs. 15 and 16. Over rolling land, through low brush.
40.60	The ¼ sec. cor. of secs. 15 and 16, monumented with a limestone, 18 x 9 x 8 ins., firmly set 6 ins. in the ground, mkd. ¼ on W face. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 S R 22 E ¼ S 16 | S 15 1979 Bury the mkd. stone alongside the iron post. Cor. falls in a fence line, bears N and S.
	N. 0° 08' W., beginning new measurement.
39.44	The cor. of secs. 9, 10, 15, and 16, monumented with a limestone, 12 x 8 x 5 ins., loosely set 4 ins. in the ground, mkd. 2 notches on E edge. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 S R 22 E S 9 | S 10 S 16 | S 15 1979 Bury the mkd. stone alongside the iron post. Cor. is located at the cor. of fences, projecting E, W and S.
	From the cor. of secs. 10, 11, 14, and 15. N. 88° 54' W., bet. secs. 10 and 15.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	Over broken sandstone.
39.77	Point for the ¼ sec. cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 40 S R 22 E ¼ S 10 / S 15 1979 Cor. is located on rocky W slope, 6 ft. below rim of spur, projects S.
79.54	The cor. of secs. 9, 10, 15, and 16.
	N. 0° 03' E., bet. secs. 9 and 10. Ascend
40.04	Point for the ¼ sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 40 S R 22 E ¼ S 9 | S 10 1979 from which U.S.G.S. triangulation station, "BLUFF", bears S. 77° 39' 18" E., 16.048 chs. dist., monumented with a standard brass tablet set in concrete, mkd. BLUFF 1936.
80.08	The cor. of secs. 3, 4, 9, and 10, monumented with a sandstone, 15 x 8 x 5 ins., firmly set, 6 ins. in the ground, mkd. 3 notches on E edge and 5 notches on S edge. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T 40 S R 22 E S 4 | S 3 / S 9 | S 10 1979 Bury the mkd. stone alongside the iron post.
	From the cor. of secs. 2, 3, 10, and 11.

221 Dependent Resurvey of a Portion of the Subdivisional Lines, T. 40 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
	S. 89° 56' W., bet. secs. 3 and 10.
	Asc. over broken sandstone.
40.04	The ¼ sec. cor. of secs. 3 and 10, monumented with a sandstone, 18 x 14 x 6 ins., firmly set 6 ins. in the ground, mkd. ¼ on N face.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T 40 S R 22 E ¼ S 3 / S 10 1979
	Bury the mkd. stone alongside the iron post.
	N. 89° 39' W., beginning new measurement.
40.00	The cor. of secs. 3, 4, 9, and 10.
	N. 0° 04' E., bet. secs. 3 and 4.
	Descend.
39.86	Point for the ¼ sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T 40 S R 22 E ¼ S 4 | S 3 1979
79.72	The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., hereinbefore described.
	From the cor. of secs. 21, 22, 27, and 28.
	S. 89° 47' W., bet. secs. 21 and 28.
	Over rolling land, through low brush.
39.98	The ¼ sec. cor. of secs. 21 and 28, monumented with a sandstone, 16 x 12 x 3 ins., firmly set, 8 ins. in the ground, mkd. ¼ on N face, and a mound of stone to the N.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	T 40 S R 22 E ¼ S 21 / S 28 1979 Bury the mkd. stone alongside the iron post. Raise a mound of stone, 3½ ft. base, 2½ ft. high, N of cor.
	N. 89° 47' W., beginning new measurement.
19.98	Point for the W 1/16 sec. cor. of secs. 21 and 28. Set an iron post, 30 ins. long, 2½ ins. diam., on solid sandstone, mkd. with a cross (X), and in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 40 S R 22 E W 1/16 S 21 / S 28 1979 Cor. is located in the bottom of small basin, draining S.
39.96	The cor. of secs. 20, 21, 28, and 29, monumented with a mound of stone. No mkd. stone found. This is accepted as the best available evidence of the position of the original corner. At the corner point (center of mound) Set an aluminum post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4½ ft. base, to top of aluminum cap, mkd. T 40 S R 22 E S 20 | S 21 S 29 | S 28 1979 Cor. is located on W slope, 50 ft. below the rim of a ledge, bears N and S.
	S. 0° 03' E., bet. secs. 28 and 29. Descend.
26.80	Point for the original meander cor. of secs. 28 and 29 at intersection with the adjusted record meander line; there is no remaining evidence of the original corner. Point not monumented.
	From the cor. of secs. 9, 10, 15, and 16. S. 89° 59' W., bet. secs. 9 and 16. Over rolling land, through low brush.
40.22	Point for the ¼ sec. cor. of secs. 9 and 16, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

223

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 40 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
	T 40 S R 22 E S 9 ¼ S 16 1979
	Cor. is located 1 lk. N of fence line, bears E and W.
80.44	The cor. of secs. 8, 9, 16, and 17, determined by the cor. of old fences extending E and S, and is accepted as the best available evidence of the position of the original corner.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T 40 S R 22 E S 8 | S 9 S 17 | S 16 1979
	N. 1° 06' E., bet. secs. 8 and 9.
	Over rolling land, through low brush.
40.10	The ¼ sec. cor. of secs. 8 and 9, monumented with a sandstone, 16 x 6 x 6 ins., firmly set, 8 ins. in the ground, mkd. ¼ on W face.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 40 S R 22 E ¼ S 8 | S 9 1979
	Bury the mkd. stone alongside the iron post.
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.
	N. 0° 21' W., beginning new measurement.
39.94	Point for the cor. of secs. 4, 5, 8, and 9, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 40 S R 22 E S 5 | S 4 S 8 | S 9 1979
	Set a steel fence post alongside the iron post.
	Raise a mound of stone, 3½ ft. base, 2½ ft. high, W of cor.
	Cor. is located on the W edge of bulldozed road, bears N and S.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	From the cor. of secs. 3, 4, 9, and 10.
	S. 89° 56' W., bet. secs. 4 and 9.
	Ascend.
40.00	Point for the ¼ sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 4½ ft. base, to top of brass cap, mkd.
	T 40 S R 22 E ¼ S 4 / S 9 1979
	Cor. is located near the top of spur, slopes S.
80.00	The cor. of secs. 4, 5, 8, and 9.
	S. 89° 54' W., bet. secs. 5 and 8.
	Over rolling land, through low brush.
32.50	Center of U.S. Highway No. 163, bears NE and SW.
40.01	Point for the ¼ sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 40 S R 22 E ¼ S 5 / S 8 1979
	Set a cottonwood post alongside the iron post.
	Cor. is located 39 lks. W of a telephone line that bears N and S.
80.02	The cor. of secs. 5, 6, 7, and 8, monumented with a sandstone, 12 x 10 x 6 ins., firmly set 6 ins. in the ground, mkd. 5 notches on E edge and 5 notches on S edge.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 40 S R 22 E S 6 | S 5 S 7 | S 8 1979
	Bury the mkd. stone alongside the iron post.
	From the cor. of secs. 4, 5, 8, and 9.
	N. 0° 06' E., bet. secs. 4 and 5.

225 Dependent Resurvey of a Portion of the Subdivisional Lines, T. 40 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
	Over rolling land, through low brush.
39.94	The ¼ sec. cor. of secs. 4 and 5, monumented with a sandstone, 12 x 6 x 4 ins., firmly set, 6 ins. in the ground, mkd. ¼ on W face.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 40 S R 22 E ¼ S 5 | S 4 1979
	Bury the mkd. stone alongside the iron post.
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.
	N. 0° 05' W., beginning new measurement.
40.00	The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., hereinbefore described.
	From the cor. of secs. 20, 21, 28, and 29.
	N. 89° 37' W., bet. secs. 20 and 29.
	Over level land, through low brush.
39.96	The ¼ sec. cor. of secs. 20 and 29, monumented with a sandstone, 26 x 8 x 5 ins., firmly set, 8 ins. in the ground, mkd. ¼ S on N face.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., on solid sandstone, mkd. with a cross (X), and in a mound of stone, 4 ft. base, to top of brass cap, mkd.
	T 40 S R 22 E ¼ S 20 / S 29 1979
	Deposit the mkd. stone in mound alongside the iron post.
	S. 89° 16' W., beginning new measurement.
19.98	Point for the W 1/16 sec. cor. of secs. 20 and 29.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 40 S R 22 E W 1/16 S 20 / S 29 1979

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
39.96	The cor. of secs. 19, 20, 29, and 30, monumented with a sandstone, 9 x 8 x 6 ins., firmly set, 4 ins. in the ground, mkd. 3 notches on E edge and 1 notch on S edge. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 S R 22 E S 19 | S 20 S 30 | S 29 1979 Bury the mkd. stone alongside the iron post. Raise a mound of stone, 3½ ft. base, 2½ ft. high, W of cor.
	S. 0° 03' E., bet. secs. 29 and 30. Over level land, through low brush.
16.65	Center of paved road, bears N. 89° E. and S. 89° W.
17.15	Barbed wire right of way fence, bears NE and SW.
20.00	Point for the N 1/16 sec. cor. of secs. 29 and 30. Set an aluminum post, 30 ins. long, 2½ ins. diam., 28 ins. in the ground, with aluminum cap mkd. T 40 S R 22 E N 1/16 S 30 | S 29 1979 Set a steel fence post alongside the iron post.
40.00	Point for the ¼ sec. cor. of secs. 29 and 30, at record bearing and distance; there is no remaining evidence of the original corner. Point not monumented.
58.00	Point for the original meander cor. of secs. 29 and 30, at record distance, on the right bank of the San Juan River; there is no remaining evidence of the original corner. Not monumented.
	From the cor. of secs. 19, 20, 29, and 30. S. 89° 56' W., bet. secs. 19 and 30. Over rolling land, through low brush.
19.975	Point for the E 1/16 sec. cor. of secs. 19 and 30. Set an iron post, 15 ins. long, 1 in. diam., 12 ins. in solid sandstone, with brass cap mkd. T 40 S R 22 E E 1/16 S 19 / S 30 1981

227 Dependent Resurvey of a Portion of the Subdivisional Lines, T. 40 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
39.95	The ¼ sec. cor. of secs. 19 and 30, monumented with a cross (X) chiseled in solid sandstone. At the corner point Set an iron post, 15 ins. long, 1 ins. diam., 8 ins. in solid sandstone, with brass cap mkd. T 40 S R 22 E S 19 ¼ S 30 1979 Raise a mound of stone, 3½ ft. base, 2½ ft. high, N of cor. From this point, a ¼ chiseled in solid sandstone, with a nail in the center, origin unknown, bears N. 73° 41' W., 36 lks. dist.
	N. 89° 42' W., beginning new measurement.
17.60	Center of U.S. Highway No. 163, bears NE and SW.
39.84	The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., set and mkd. as described in the official record of the concurrent resurvey of T. 40 S., R. 21 E.
	Survey of a Portion of the South Boundary of Sec. 30, T. 40 S., R. 22 E., Salt Lake Meridian, Utah
	From the true point for the cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., described in the official record of the concurrent resurvey of T. 40 S., R. 21 E. East, bet. secs. 30 and 31. Over level river bottom, through dense brush.
19.88	Point for the meander cor. of secs. 30 and 31, at intersection with the present right bank of the San Juan River. Point not monumented.
	Partial Subdivision of Section 28, T. 40 S., R. 22 E., Salt Lake Meridian, Utah
	From the W 1/16 sec. cor. of secs. 21 and 28. S. 0° 03' E., on the N-S center line of the NW¼ of sec. 28.
33.015	Point for the special meander cor. at the intersection with the adjusted record meander line. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

☆U.S. Government Printing Office: 1980—778-251/292

Partial Subdivision of Section 28,
T. 40 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
	W S | 28 W SMC 1981
	Cor. is located 2 lks. S of the cor. of fences, projecting W and SE.
	Thence, S. 0° 03' E., on a partition line bet. privately and federally owned accretion lands.
11.68	Point for the special meander cor. at the intersection with the present right bank of the San Juan River. Point not monumented.

Partial Subdivision of Section 29,
T. 40 S., R. 22 E., Salt Lake Meridian, Utah

	From the ¼ sec. cor. of secs. 20 and 29.
	S. 0° 03' E., on the N-S center line of sec. 29.
9.57	Center of paved road, bears N. 79° E. and S. 79° W.
10.07	Barbed wire right-of-way fence, bears N. 79° E. and S. 79° W.
12.005	Point for the special meander cor. at the intersection with the adjusted record meander line.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 30 ins. in the ground, with aluminum cap mkd.
	T 40 S R 22 E C S 29 | C SMC 1981
	Cor. is located 1.5 lks. W of fence line, bears N and S.
	Thence, S. 0° 03' E., on a partition line bet. privately and federally owned accretion lands.
52.57	Point for the special meander cor. at the intersection with the present right bank of the San Juan River. Point not monumented.
	From the W 1/16 sec. cor. of secs. 20 and 29.
	S. 0° 03' E., on the N-S center line of the W½ of sec. 29.
13.11	Center of paved road, bears N. 79° E. and S. 79° W.
13.61	Barbed wire right-of-way fence, bears N. 79° E. and S. 79° W.

229

Partial Subdivision of Section 29,
T. 40 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
56.14	Point for the special meander cor. at the intersection with the adjusted record meander line. Set an aluminum post, 30 ins. long, 2½ ins. diam., 30 ins. in the ground, with aluminum cap mkd. T 40 S R 22 E W S 29 W SMC 1981 from which The cor. of fences, bears Southeast, 39 lks. dist. Thence, S. 0° 03' E., on a partition line bet. privately and federally owned accretion lands.
13.18	Point for the special meander cor. at the intersection with the present right bank of the San Juan River. Point not monumented.

Partial Subdivision of Section 30,
T. 40 S., R. 22 E., Salt Lake Meridian, Utah

	From the ¼ sec. cor. of secs. 19 and 30. S. 0° 01' E., on the N-S center line of sec. 30.
14.950	Point for the C-S-N-N 1/256 sec. cor. of sec. 30. Set an alunimum post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a collar of stone, with aluminum cap mkd. S 30 C-S-N-N 1/256 1981
17.36	Center of paved road, bears N. 89° E. and S. 89° W.
17.86	Barbed wire right-of-way fence, bears N. 89° E. and S. 89° W.
19.935	Point for the center north 1/16 sec. cor. of sec. 30. Point not monumented.
39.87	Point for the center ¼ sec. cor. of sec. 30, at intersection with the E-W center line. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 40 S R 22 E C ¼ S 30 1981

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	From the point for the ¼ sec. cor. of secs. 29 and 30.
	N. 89° 53' W., on the E-W center line of sec. 30.
19.99	Point for the center east 1/16 sec. cor. of sec. 30.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	S 30 C E 1/16 C 1981
	Set a cottonwood post alongside the iron post.
	Cor. is located in a cultivated field.
39.98	The center ¼ sec. cor. of sec. 30.
79.83	The ¼ sec. cor. of sec. 25 and 30, on the W. bdy. of the Tp., set and mkd. as described in the official record of the concurrent resurvey of T. 40 S., R. 21 E.
	From the center east 1/16 sec. cor. of sec. 30.
	N. 0° 02' W., on the N-S center line of the NE¼ of sec. 30.
19.968	Point for the NE 1/16 sec. cor. of sec. 30. At intersection with the E-W center line. Point not monumented.
24.960	Point for the C-S-N-NE 1/256 sec. cor. of sec. 30. Point not monumented.
22.43	Barbed wire right-of-way fence, bears N. 89° E. and S. 89° W.
22.93	Center of paved road, bears N. 89° E. and S. 89° W.
39.936	The E 1/16 sec. cor. of secs. 19 and 30.
	From the N 1/16 sec. cor. of secs. 29 and 30.
	N. 89° 59' W., on the E-W center line of the NE¼ of sec. 30.
14.987	Point for the C-W-E-NE 1/256 sec. cor. of sec. 30.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	S 30 C-W-E-NE 1/256 1981
	Set a cottonwood post alongside the aluminum post.
19.983	Point for the NE 1/16 sec. cor. of sec. 30.
39.966	Point for the center north 1/16 sec. cor. of sec. 30.

Partial Subdivision of Section 30,
T. 40 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
	From the C-W-E-NE 1/256 sec. cor. of sec. 30.
	N. 0° 02' W., on the N-S center line of the SW¼, NE¼NE¼ of sec. 30.
2.56	Barbed wire right-of-way fence, bears N. 89° E. and S. 89° W.
3.06	Center of paved road, bears N. 89° E. and S. 89° W.
4.994	Point for the SW-NE-NE 1/256 sec. cor. of sec. 30.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a collar of stone, with aluminum cap mkd. S 30 SW-NE-NE 1/256 1981
	West, on the E-W center line of the SW¼NE¼NE¼ of sec. 30.
4.995	Point for the C-S-N-NE 1/256 sec. cor. of sec. 30.
	From the center east 1/16 sec. cor. of sec. 30.
	S. 0° 02' E., on the N-S center line of the SE¼ of sec. 30.
8.73	Point for the special meander cor. at the intersection with the adjusted record meander line.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. E S | 30 E SMC 1981
	from which the cor. of fences, bears South, 25 lks. dist.
	Thence, S. 0° 02' E., on a partition line, bet. privately and federally owned accretion lands.
7.71	Point for the special meander cor. at the intersection with the present right bank of the San Juan River. Point not monumented.
	Meanders of the Right Bank of the San Juan River, Through T. 40 S., R. 22 E., Salt Lake Meridian, Utah
	From the true point for the meander cor. of the right bank of the San Juan River bet. secs. 25 and 30, on the E. bdy. of the Tp., 5 lks. S of the witness meander cor. of secs. 25 and 30, an iron post, 2½ ins. diam., projecting 6 ins. above the ground, with a brass cap mkd. as described in the official record of the 1953 resurvey by Andrew Nelson.

☆U.S. Government Printing Office: 1980—778-251/292

Meanders of the Right Bank of the San Juan River,
Through T. 40 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS		
	Thence, with the meanders of the present right bank of the San Juan River through sec. 25.	
	N. 84° 05' W., 4.00 chs.	
	N. 83° 35' W., 3.60 chs.	
	N. 84° 30' W., 6.10 chs.	
	S. 86° 05' W., 2.30 chs.	
	S. 88° 55' W., 1.55 chs.	
	S. 79° 15' W., 4.75 chs.	
	S. 66° 55' W., 6.65 chs.	
	S. 56° 35' W., 6.60 chs.	
	S. 79° 20' W., 4.40 chs.	
	N. 63° 35' W., 11.35 chs.	
	N. 10° 35' E., 11.25 chs.	
	N. 47° 30' W., 4.50 chs.	
	N. 32° 40' W., 2.55 chs.	
	N. 53° 40' W., 3.40 chs.	
	N. 46° 20' W., 6.35 chs.	
	N. 59° 00' W., 11.55 chs.	
	N. 65° 20' W., 7.60 chs.	
	N. 38° 45' W., 7.80 chs.	To the meander cor. of secs. 25 and 26, hereinbefore described.
	Thence, with the meanders of the present right bank of the San Juan River through sec. 26.	
	N. 38° 45' W., 4.10 chs.	
	N. 34° 50' W., 7.95 chs.	
	N. 44° 05' W., 6.55 chs.	
	N. 72° 20' W., 5.15 chs.	
	S. 83° 30' W., 13.05 chs.	
	N. 75° 45' W., 6.00 chs.	
	S. 89° 35' W., 7.00 chs.	
	S. 60° 35' W., 7.15 chs.	
	N. 58° 35' W., 8.75 chs.	
	N. 63° 35' W., 12.65 chs.	
	N. 88° 45' W., 11.75 chs.	

233

Meanders of the Right Bank of the San Juan River,
Through T. 40 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS		
	S. 52° 15' W., 1.10 chs.	To the meander cor. of secs. 26 and 27, hereinbefore described.
	Thence, with the meanders of the present right bank of the San Juan River through sec. 27.	
	S. 52° 15' W., 3.95 chs.	
	S. 51° 30' W., 6.60 chs.	
	S. 47° 00' W., 2.60 chs.	
	S. 40° 50' W., 2.05 chs.	
	S. 38° 35' W., 7.65 chs.	
	N. 86° 55' W., 20.55 chs.	
	N. 49° 30' W., 3.30 chs.	
	N. 83° 40' W., 9.20 chs.	
	S. 67° 05' W., 4.80 chs.	
	S. 45° 40' W., 1.90 chs.	
	S. 51° 05' W., 3.80 chs.	
	S. 59° 30' W., 1.80 chs.	
	S. 37° 20' W., 3.55 chs.	
	S. 55° 45' W., 8.80 chs.	
	S. 58° 20' W., 3.05 chs.	
	S. 67° 10' W., 9.95 chs.	To the meander cor. of secs. 27 and 28, hereinbefore described.
	Thence, with the meanders of the present right bank of the San Juan River through sec. 28.	
	S. 80° 55' W., 13.27 chs.	
	N. 73° 43' W., 8.40 chs.	
	N. 73° 44' W., 12.27 chs.	
	S. 51° 40' W., 3.38 chs.	
	S. 37° 32' W., 3.24 chs.	
	S. 86° 16' W., 3.46 chs.	
	N. 84° 07' W., 6.98 chs.	
	N. 74° 06' W., 2.93 chs.	
	S. 78° 57' W., 6.48 chs.	
	S. 72° 12' W., 2.96 chs.	Point for the special meander cor. on the N-S center line of the SW¼ of sec. 28, hereinbefore described.

☆U.S. Government Printing Office: 1980—778-251/292

Meanders of the Right Bank of the San Juan River,
Through T. 40 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS		
	Thence, with an informative traverse	
	S. 72° 12' W., 0.12 chs.	
	S. 65° 54' W., 8.66 chs.	
	S. 58° 56' W., 4.19 chs.	
	S. 80° 32' W., 8.47 chs.	
	S. 66° 27' W., 2.60 chs.	
	S. 68° 06' W., 3.12 chs.	
	S. 78° 30' W., 15.65 chs.	
	S. 65° 28' W., 10.24 chs.	
	S. 74° 18' W., 10.29 chs.	
	S. 73° 40' W., 0.16 chs.	Point for the special meander cor. on the N-S center line of sec. 29, hereinbefore described.
	Thence, with the meander of the present right bank of the San Juan River through sec. 29.	
	S. 73° 40' W., 15.91 chs.	
	S. 78° 51' W., 3.16 chs.	
	N. 87° 25' W., 1.63 chs.	Point for the special meander cor. on the N-S center line of the SW¼ of sec. 29, hereinbefore described.
	Thence, with an informative traverse	
	N. 87° 25' W., 6.97 chs.	
	N. 71° 30' W., 6.87 chs.	
	N. 69° 28' W., 6.87 chs.	
	N. 67° 40' W., 19.60 chs.	
	N. 80° 45' W., 1.99 chs.	Point for the special meander cor. on the N-S center line of the SE¼ of sec. 30, hereinbefore described.
	Thence, with the meanders of the present right bank of the San Juan River through sec. 30.	
	N. 80° 45' W., 6.56 chs.	
	N. 85° 30' W., 6.10 chs.	
	S. 77° 30' W., 10.30 chs.	
	S. 44° 20' W., 18.90 chs.	
	S. 23° 45' W., 10.08 chs.	Point for the meander cor. of secs. 30 and 31, hereinbefore described.

235

Meanders of the Right Bank of the San Juan River,
Through T. 40 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS		
	Thence, with the meanders of the present right bank of the San Juan River through sec. 31.	
	S. 23° 45' W., 3.22 chs.	
	S. 44° 40' W., 2.50 chs.	
	S. 82° 40' W., 1.15 chs.	
	N. 79° 20' W., 10.10 chs.	
	N. 69° 30' W., 6.15 chs.	The meander cor. of secs. 31 and 36, on the W. bdy. of the Tp., set and mkd. as described in the official record of the concurrent resurvey of T. 40 S., R. 21 E.
	Adjusted Original (1899) Meanders of the Right Bank of the San Juan River, T. 40 S., R. 22 E., Salt Lake Meridian, Utah	
	From the meander cor. of secs. 27 and 28, hereinbefore described.	
	Thence, by calculation with the adjusted original (1899) meanders of the right bank of the San Juan River through sec. 28.	
	N. 77° 02' W., 12.73 chs.	
	N. 88° 49' W., 19.56 chs.	At 19.01 chs. on this course intersect the present right bank of the San Juan River, bears S. 73° 44' E. and N. 73° 44' W.
	N. 85° 18' W., 11.53 chs.	At 1.39 chs. on this course intersect the present right bank of the San Juan River, bears N. 51° 40' E. and S. 51° 40' W.
	N. 72° 32' W., 4.69 chs.	
	N. 70° 32' W., 19.72 chs.	At 12.75 chs. on this course the special meander cor. of sec. 28 at intersection with the N-S centerline of the NW¼ of sec. 28, hereinbefore described.
	N. 73° 32' W., 13.98 chs.	To the point for the original meander cor. of secs. 28 and 29, hereinbefore described.
	Thence, by calculation with the adjusted original (1899) meanders of the right bank of the San Juan River through sec. 29.	
	N. 35° 04' W., 6.49 chs.	

☆U.S. Government Printing Office: 1980—778-251/292

Adjusted Original (1899) Meanders of the Right Bank
of the San Juan River, T. 40 S., R. 22 E.,
Salt Lake Meridian, Utah

CHAINS		
	N. 83° 42' W., 9.47 chs.	
	N. 60° 08' W., 18.45 chs.	
	N. 83° 27' W., 7.73 chs.	
	S. 66° 44' W., 11.23 chs.	At 3.43 chs. on this course, the special meander cor. of sec. 29, at intersection with the N-S center line of sec. 29, hereinbefore described.
	S. 40° 42' W., 18.73 chs.	
	S. 1° 31' W., 13.21 chs.	
	S. 34° 16' E., 8.92 chs.	
	S. 20° 41' W., 3.75 chs.	
	S. 52° 12' W., 11.58 chs.	At 4.95 chs. on this course, the special meander cor. of sec. 29, at intersection with the N-S center line of the SW¼ of sec. 29, hereinbefore described.
	S. 83° 16' W., 9.18 chs.	
	N. 61° 43' W., 6.38 chs.	Point for the original meander cor. of secs. 29 and 30, hereinbefore described.
	Thence, by calculation with the adjusted original (1899) meanders of the right bank of the San Juan River through sec. 30.	
	N. 89° 08' W., 6.29 chs.	
	N. 40° 33' W., 1.95 chs.	
	N. 73° 53' W., 4.25 chs.	
	N. 51° 53' W., 14.86 chs.	At 10.62 chs. on this course, the special meander cor. of sec. 30, at intersection with the N-S center line of the SE¼ of sec. 30, hereinbefore described.
	N. 86° 33' W., 13.94 chs.	
	N. 81° 48' W., 14.89 chs.	
	N. 75° 53' W., 8.20 chs.	
	S. 68° 20' W., 5.49 chs.	
	S. 89° 06' W., 7.79 chs.	
	S. 77° 21' W., 7.19 chs.	True point for the original meander cor. of secs. 25 and 30, on the E. bdy. of the Tp., as described in the official record of the concurrent resurvey of T. 40 S., R. 21 E.

Township 40 South, Range 22 East, Salt Lake Meridia, Utah

	CHAINS	General Description	
		The elevation is about 5,000 feet above sea level. The soil varies from silt along the river bottoms to sand dunes in many areas. The San Juan River crosses the township from east to west. U.S. Highway No. 163 crosses the western portion of the township.	

☆U.S. Government Printing Office: 1980—778-251/292

Form 9600–11
(August 1979)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

238

FIELD ASSISTANTS

NAMES	CAPACITY
Donzil Worthington	Surveying Technician
Larry Judd	Survey Aid
John Mavor	Survey Aid
Richard Zaninovich	Supervisory Cadastral Surveyor
Donald Buhler	Supervisory Cadastral Surveyor

CERTIFICATE OF SURVEY

(I) ~~(We)~~, Jerry L. Thomas, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 2nd day

of May, 1979, (I)~~(We)~~ have dependently resurveyed the north boundary; a portion of the east boundary (Colorado Guide Meridian); a portion of the south boundary of section 30; a partial subdivisional survey of sections 28, 29 and 30, and the meanders of the right bank of the San Juan River in Township 40 South, Range 22 East

of the Salt Lake Meridian, in the State of Utah, which

are represented in the foregoing field notes as having been executed by (me), (~~us~~) and under (my) (~~our~~) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

November 21, 1982 — Jerry L. Thomas
(Date) — (Cadastral Surveyor)
Supervisory

(Date) — (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Denver, Colorado

The foregoing field notes of thedependent resurvey of the north boundary; a portion of the east boundary (Colorado Guide Meridian); a portion of the south boundary of section 30, a partial subdivisional survey of sections 28, 29 and 30, and the meanders of the right bank of the San Juan River in Township 40 South, Range 22 East, Salt Lake Meridian, Utah

executed by Jerry L. Thomas, Supervisory Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

August 15, 1983 — Glen B. Hatch
(Date) — ~~(Chief, Cadastral Survey Examination and Approval Staff)~~
Chief Cadastral Surveyor for Utah

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in~~

~~, is a true copy of the original field notes.~~

~~(Date)~~ — ~~(Chief, Cadastral Survey Examination and Approval Staff)~~
Chief Cadastral Surveyor for Utah

Form 9600–9
(December 1979)
(formerly 9180–6)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

R606

ORIGINAL

240

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

A PORTION OF THE WEST BOUNDARY OF THE NAVAJO INDIAN RESERVATION,

A PORTION OF THE NORTH AND EAST BOUNDARIES,

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SURVEY OF THE SUBDIVISION OF SECTIONS 4, 9, 10, AND 11,

AND

A PORTION OF THE MEANDER LINES

OF

TOWNSHIP 40 SOUTH, RANGE 23 EAST

Of the Salt Lake Meridian,

In the State of Utah.

EXECUTED BY

Donald A. Buhler Supervisory Cadastral Surveyor

Under special instructions dated May 2, 1979, approved May 3, 1979,

_____, which provided for the surveys included under U.S. Survey/Group Number 592, and assignment instructions dated April 2, 1980.

Survey commenced April 8, 1980

Survey completed November 20, 1980

241

INDEX DIAGRAM

Township 40 South, Range 23 East,

7 6 32 32	6 5 27 32	5 4 22 26	3 22	2 17	1
7 31 31	8 25 31	9 21 25	10 16 21	11 12 16	12 12
18 30 29	17 25 29	16 20 24	15 15 20	14 11 15	13 4 11
19 28 28	20 24 27	21 19 23	22 15 19	23 10 14	24 4 9
28 30	29 23	28 18 22	27 14 17	26 9 13	25 3 8
31	32	33 18	34 13	35 9	36

Navajo Indian Boundary - Page 2
Subdivision of Section 4 - Page 33
Subdivision of Section 9 - Page 34
Subdivision of Section 10 - Page 35
Subdivision of Section 11 - Page 36
Meander Lines - Page 37

GPO 855-927

Township 40 South, Range 23 East, Salt Lake Meridian, Utah

CHAINS

History of Surveys

	Surveyed by	Retr. or Resurveyed by
BOUNDARY OF NAVAJO INDIAN RESERVATION		
Portion	Robert C. Yundt 1942-44	
EAST BOUNDARY		
Portion	A.D. Ferron 1884	
Portion		H.D. Page and J.M. Lentz 1899
Portion		Andrew Nelson and Robert C. Yundt 1953
NORTH BOUNDARY		
All	A.D. Ferron 1884	
All		H.D. Page and J.M. Lentz 1899
All		D.B. Miller and J.C. Thoma 1912
SOUTH BOUNDARY		
All	Andrew Nelson and Robert C. Yundt 1953	
WEST BOUNDARY		
All	Ferdinand Dickert 1878	
Portion		A.D. Ferron 1884
Portion		H.D. Page and J.M. Lentz 1898
Portion		Andrew Nelson and Robert C. Yundt 1953
SUBDIVISIONAL LINES		
Portion	H.D. Page and J.M. Lentz 1899	

The following field notes are those of the dependent resurvey of a portion of the west boundary of the Navajo Indian Reservation, a portion of the north and east boundaries, a portion of the subdivisional lines, and the survey of the subdivision of sections 4, 9, 10, and 11, and a portion of the meander lines of Township 40 South, Range 23 East, Salt Lake Meridian, Utah.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated May 2, 1979.

The direction of lines were determined by reference to true meridians established on line by hour angle observations on Polaris and altitude observations on the sun. The lines were carried forward by sustained angulation being supplemented by other numerous hour angle observations on Polaris.

Township 40 South, Range 23 East, Salt Lake Meridian, Utah

CHAINS

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the southeast corner of sec. 25, as determined from a tie made to U.S.G.S. triangulation station "UMA," located in sec. 11, is as follows:

Latitude 37° 16' 22.9" N. Longitude 109° 19' 50.1" W.

The mean magnetic declination is 13° 30' East.

Dependent Resurvey of a Portion of the West Boundary of the Navajo Indian Reservation, T. 40 S., R. 23 E., Salt Lake Meridian, Utah

---

(Reestablishment of the Survey Executed by Robert C. Yundt in 1942-44)

Beginning at angle point No. 28 in sec. 19 of T. 40 S., R. 24 E., monumented with an iron post, 1 in. diam., projecting 18 ins. above the ground, and in a collar of stone, with brass cap mkd. as described in the official record of the 1942 survey of the W. bdy. of the Navajo Indian Reservation.

Thence, S. 28° 59' W.

16.115 Intersect the section line bet. secs. 19 and 24, on the E. bdy. of the Tp.

From this point, the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., bears N. 0° 04' E., 25.24 chs. dist., hereinafter described.

40.23 Point for angle point No. 29, at proportionate distance, based on the Grant Boundary Method; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd.

T 40 S R 23 E
S 24
AP29
NIR
1980

Thence, S. 15° 29' W.

9.91 The 8th mile post and angle point No. 30, monumented with an iron post, 3 ins. diam., projecting 10 ins. above the ground, and in a collar of stone, with brass cap mkd. as described in the official record of the 1942 survey of the W. bdy. of the Navajo Indian Reservation.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	Thence, S. 15° 28' W.
25.29	Intersect the section line bet. secs. 24 and 25.
	From this point, the ¼ sec. cor. of secs. 24 and 25, bears N. 89° 53' W., 18.76 chs. dist., hereinafter described.
70.01	The angle point No. 31, monumented with a mound of stone, 4 ft. base, 3 ft. high. No marked iron post was found. This position is harmoniously related to existing original cors. and is accepted as the best available evidence of the original corner.
	At the corner point (center of mound)
	Set an iron post, 30 ins. long, 2½ ins. diam., over a cross (X) chiseled on solid sandstone, and in a mound of stone, 4½ ft. base, to top of brass cap, mkd.
	T 40 S R 23 E S 25 / AP31 NIR 1980
	Thence, S. 41° 43' E.
9.96	The 9th mile post of the boundary, monumented with an iron post, 3 ins. diam., firmly set in a mound of stone, 4 ft. base, to top of brass cap, mkd. as described in the official record of the 1942 survey of the W. bdy. of the Navajo Indian Reservation.
	Thence, S. 41° 49' E.
39.46	The cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., monumented with an iron post, 3 ins. diam., projecting 10 ins. above the ground, with brass cap, mkd. as described in the official record of the 1942 survey of the W. bdy. of the Navajo Indian Reservation.
	Dependent Resurvey of a Portion of the East Boundary, T. 40 S., R. 23 E., Salt Lake Meridian, Utah
	(Reestablishment of the Survey Executed by A.D. Ferron in 1884, the Resurvey by H.D. Page and J.M. Lentz in 1899, and the Retracement by R.C. Yundt in 1944)
	From the cor. of secs. 25, 30, 31, and 36, hereinbefore described.
	N. 0° 01' W., bet. secs. 25 and 30.
40.00	The ¼ sec. cor. of secs. 25 and 30, monumented with an iron post, 1 in. diam., projecting 15 ins. above the ground, and in a mound of stone, 2½ ft. base, to top of brass cap mkd. as described in the official record of the 1942 resurvey of the W. bdy.

Dependent Resurvey of a Portion of the East Boundary,
T. 40 S., R. 23 E., Salt Lake Meridian, Utah

CHAINS	
	North, beginning new measurement.
39.89	The cor. of secs. 19, 24, 25, and 30, monumented with a sandstone, 17 x 6 x 5 ins., firmly set in a mound of stone, mkd. 4 notches on the N and 2 notches on the S faces. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 S R 23 E | R 24 E S 24 | S 19 S 25 | S 30 1980 Deposit the mkd. stone alongside the iron post. Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	N. 0° 04' E., bet. secs. 19 and 24.
40.15	Point for the ¼ sec. cor. of secs. 19 and 24, at proportionate distance; there is no remaining evidence of the original cor; not monumented.
55.06	Intersect line bet. angle points No. 28 and 29 of the Navajo Indian Reservation boundary. From this intersection point, angle point No. 28 of Navajo Indian Reservation boundary, bears N. 28° 59' E., 16.115 chs. dist., hereinbefore described.
80.30	The cor. of secs. 13, 18, 19, and 24, monumented with a sandstone, 12 x 10 x 8 ins., firmly set in a mound of stone, no visible markings on the stone. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 40 S R 23 E | R 24 E S 13 | S 18 S 24 | S 19 1980 Deposit the unmkd. stone alongside the iron post. Cor. is located on E edge of sandstone ledge, bearing N and SW.
	N. 0° 01' W., bet. secs. 13 and 18.
40.03	Point for the ¼ sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

☆U.S. Government Printing Office: 1980—778-251/292

Dependent Resurvey of a Portion of the East Boundary,
T. 40 S., R. 23 E., Salt Lake Meridian, Utah

CHAINS

T 40 S
R 23 E | R 24 E
¼
S 13 | S 18
1980

Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.

80.06 The cor. of secs. 7, 12, 13, and 18, monumented with a mound of stone, 3 ft. base, 2 ft. high. No marked stone found. This position is harmoniously related to existing cors. and is accepted as the best available evidence of the original cor.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 40 S
R 23 E | R 24 E
S 12 | S 7
S 13 | S 18
1980

Cor. is set in fence, bearing N and S.

Dependent Resurvey of a Portion of the North Boundary,
T. 40 S., R. 23 ., Salt Lake Meridian, Utah

(Reestablishment of the Survey Executed by A.D. Ferron in 1884, the Resurvey by H.D. Page and J.M. Lentz in 1898, and the Resurvey by D.B. Miller and J.C. Thoma in 1912)

From the cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., monumented with a sandstone, 14 x 12 x 8 ins., plainly mkd. 3 notches on the E and W edges, firmly set in a mound of stone, 3 ft. base, 1½ ft. high.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd.

T 39 S R 23 E
S 33 | S 34
S 4 | S 3
T 40 S R 23 E
1980

Deposit the mkd. stone alongside the iron post.

S. 89° 53' W., along the N. bdy. of sec. 4.

39.57 The ¼ sec. cor. of secs. 4 and 33, monumented with a sandstone, 18 x 12 x 6 ins., plainly mkd. with ¼ on N face, set alongside an iron post, 2½ ins. diam., projecting 14 ins. above the ground, and in a collar of stone. The iron cap mkd.

247

Dependent Resurvey of a Portion of the North Boundary,
T. 40 S., R. 23 E., Salt Lake Meridian, Utah

CHAINS	
	¼ SEC 33 / SEC 4 L.S. 2334
	N. 89° 59' W., beginning new measurement.
19.88	Point for the W 1/16 sec. cor. of sec. 4. Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd. W 1/16 S 4 T 40 S R 23 E 1980
39.76	The cor. of secs. 4 and 5, T. 40 S., R. 23 E., monumented with a cross chiseled on a sandstone ledge, with a mound of stone, 2½ ft. base, 1½ ft. high, N of cor. At the corner point Set an iron post, 12 ins. long, 1 in. diam., 8 ins. in in solid sandstone, with brass cap mkd. T 39 S R 23 E S 5 | S 4 T 40 S R 23 E 1980 Rebuild the mound of stone, 3 ft. base, 2 ft. high, S of cor.
	N. 89° 41' W., along the N. bdy. of sec. 5.
0.63	The cor. of secs. 32 and 33, T. 39 S., R. 23 E., monumented with a sandstone, 18 x 12 x 5 ins., plainly mkd. 2 notches on the E and 4 notches on the W edges, set alongside an iron pipe, 2½ ins. diam., and in a mound of stone, 4 ft. base, to top of iron cap, mkd. T 39 S R 23 E 32 | 33 5 L.S. 2334
40.08	Point selected for the witness cor. to the ¼ sec. cor. of sec. 5. Set an iron post, 30 ins. long, 2½ ins. diam., over a cross (X) chiseled on solid sandstone, and in a mound of stone, 4½ ft. base, to top of brass cap, mkd. W C ← ¼ S 5 T 40 S R 23 E 1980
40.28	True point for the ¼ sec. cor. of sec. 5, at proportionate distance; there is no remaining evidence of the original corner. The corner point falls on a steep slope and is impossible to perpetuate or occupy.

☆U.S. Government Printing Office: 1980—778-251/292

Dependent Resurvey of a Portion of the North Boundary,
T. 40 S., R. 23 E., Salt Lake Meridian, Utah

CHAINS	
41.025	Point for the ¼ sec. cor. of sec. 32, T. 39 S., R. 23 E., at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 39 S R 23 E ¼ S 32 1980
80.56	The cor. of secs. 5 and 6, monumented with a sandstone, 10 x 8 x 6 ins., set in a mound of stone, 3½ ft. base, 2½ ft. high. No visible markings on stone. This is accepted as the best available evidence of the position of the original corner. At the corner point Set an aluminum post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 4½ ft. base, to top of aluminum cap, mkd. T 39 S S 6 | S 5 T 40 S R 23 E 1980 Deposit the unmkd. stone alongside the aluminum post.
	S. 89° 44' W., along the N. bdy. of sec. 6.
0.86	The cor. of secs. 31 and 32, T. 39 S., R. 23 E., monumented with a sandstone, 30 x 12 x 10 ins., plainly mkd. 2 notches on the W and 4 notches on the E edges, firmly set in a mound of stone, 3 ft. base, 2 ft. high. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 39 S R 23 E S 31 | S 32 1980 Deposit the mkd. stone alongside the iron post.
39.88	Point for the ¼ sec. cor. of sec. 6, T. 40 S., R. 23 E., at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd. T 39 ¼ S 6 T 40 S R 23 E 1980

CHAINS	
40.36	Point for the ¼ sec. cor. of sec. 31, T. 39 S., R. 23 E., at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 39 S R 23 E ¼ S 31 1980
79.21	The cor. of Tps. 39 and 40 S., Rs. 22 and 23 E., set and mkd. as described in the official record of the dependent resurvey of the E. bdy. of T. 40 S., R. 22 E., resurveyed concurrently under this same group.
	Dependent Resurvey of a Portion of the Subdivisional Lines of T. 40 S., R. 23 E., Salt Lake Meridian, Utah
	(Reestablishment of the Survey Executed by H.D. Page and J.M. Lentz in 1898)
	From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., hereinbefore described. N. 89° 55' W., bet. secs. 25 and 36.
40.39	Point for the ¼ sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 S R 23 E ¼ S 25 S 36 1980 Set a steel fence post, 6 ft. long, alongside the iron post. Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.
80.78	The cor. of secs. 25, 26, 35, and 36, monumented with a sandstone, 20 x 12 x 3 ins., plainly mkd. 1 notch on S and E edges and set in a mound of stone, 3 ft. base, 1½ ft. high. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 40 S R 23 E S 26 | S 25 S 35 | S 36 1980

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS

Deposit the mkd. stone alongside the iron post.

S. 0° 01' E., bet. secs. 35 and 36.

28.64 Point selected for the witness cor. to the meander cor. of secs. 35 and 36, on the right bank of the San Juan River.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 40 S R 23 E
S 35 | S 36
WMC
1980

28.78 Point for the meander cor. of secs. 35 and 36, on the right bank of the San Juan River, falls on unstable river bank.

From the cor. of secs. 25, 26, 35, and 36.

N. 0° 43' E., bet. secs. 25 and 26.

39.81 Point for the ¼ sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 40 S R 23 E
¼
S 26 | S 25
1980

Deposit a steel fence post, 6 ft. long, alongside the iron post.

79.62 Point for the cor. of secs. 23, 24, 25, and 26, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 40 S R 23 E
S 23 | S 24
S 26 | S 25
1980

Cor. is located 1.2 chs. E of bottom of Bucket Canyon.

From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., hereinbefore described.

251

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 40 S., R. 23 E., Salt Lake Meridian, Utah

CHAINS	
	N. 89° 53' W., bet. secs. 24 and 25.
21.00	Intersect the line bet. angle points No. 30 and 31 of the Navajo Indian Reservation boundary.
	From this intersection point, angle point No. 30 of the Navajo Indian Reservation boundary, bears N. 15° 28' E., 25.29 chs. dist., hereinbefore described.
39.76	The ¼ sec. cor. of secs. 24 and 25, monumented with a sandstone, 20 x 10 x 6 ins., plainly mkd. ¼ on N face, set, 5 ins. in the ground with a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd.
	T 40 S R 23 E ¼ S 24 / S 25 1980
	Deposit the mkd. stone alongside the iron post.
	S. 89° 39' W., beginning new measurement.
40.00	The cor. of secs. 23, 24, 25, and 26.
	N. 0° 41' W., bet. secs. 23 and 24.
39.81	The ¼ sec. cor. of secs. 23 and 24, monumented with a sandstone, 18 x 12 x 5 ins., plainly mkd. ¼ on N face, and firmly set 6 ins. in the ground.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4½ ft. base, to top of brass cap, mkd.
	T 40 S R 23 E ¼ S 23 | S 24 1980
	Deposit the mkd. stone alongside the iron post.
	Cor. falls on steep W facing slope.
	N. 0° 46' E., beginning new measurement.
40.26	Point for the cor. of secs. 13, 14, 23, and 24, at proportionate distance; there is no remaining evidence of the original corner.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base, to top of brass cap, mkd. T 40 S R 23 E S 14 | S 13 S 23 | S 24 1980
	From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp. N. 89° 57' W., bet. secs. 13 and 24.
39.86	The ¼ sec. cor. of secs. 13 and 24, monumented with a mound of stone, 3 ft. base, 1½ ft. high. No mkd. stone was found. This position is harmoniously related to existing cors. and is accepted as the best available evidence of the original corner. At the corner point (center of mound) Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4½ ft. base, to top of brass cap, mkd. T 40 S R 23 E ¼ S 13 S 24 1980
	S. 89° 22' W., beginning new measurement.
39.92	The cor. of secs. 13, 14, 23, and 24.
	N. 0° 11' W., bet. secs. 13 and 14.
40.26	Point for the ¼ sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4½ ft. base, to top of brass cap, mkd. T 40 S R 23 E ¼ S 14 | S 13 1980
80.52	Point for the cor. of secs. 11, 12, 13, and 14, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., over a cross (X) chiseled on solid sandstone boulder, 30 x 20 x 10 ft., and in a mound of stone, 4½ ft. base, to top of brass cap, mkd.

253

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 40 S., R. 23 E., Salt Lake Meridian, Utah

CHAINS	
	T 40 S R 23 E S 11 | S 12 S 14 | S 13 1980 from which The U.S.G.S. triangulation station "UMA", monumented with a power pole, 1 ft. in diam., bears N. 55° 36' W., 25.536 chs. dist. latitude 37° 19' 09.16" longitude 109° 21' 12.66". Reference mark No. 1 monumented with a brass tablet, 4 ins. diam., in concrete, mkd. No. 1 1961 bears S. 24° 05' 28" E., 0.519 chs. dist., (Record, 34.25 ft. from station in azimuth 335° 54' 32")
	From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., hereinbefore described. N. 89° 59' W., bet. secs. 12 and 13.
40.02	Point for the ¼ sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T 40 S R 23 E ¼ S 12 S 13 1980
80.04	The cor. of secs. 11, 12, 13, and 14.
	N. 0° 06' W., bet. secs. 11 and 12.
20.13	Point for the S 1/16 sec. cor. of secs. 11 and 12. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T 40 S R 23 E S1/16 S 11 | S 12 1980
40.26	The ¼ sec. cor. of secs. 11 and 12, monumented with a sandstone, 16 x 8 x 6 ins., firmly set in a collar of stone and dimly mkd. ¼ on W face. Not remonumented.
	N. 0° 03' E., beginning new measurement.
39.95	The cor. of secs. 1, 2, 11, and 12, monumented with a sandstone, 20 x 12 x 4 ins., above the ground, firmly set, and mkd. 5 notches on the S and 1 notch on the W edges. A steel fence post, projecting 5 ft., set alongside cor., and a mound of stone, 2½ ft. base, 1½ ft. high, W of cor. Not remonumented.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	From the cor. of secs. 25, 26, 35, and 36.
	S. 89° 55' W., bet. secs. 26 and 35.
39.90	The ¼ sec. cor. of secs. 26 and 35, monumented with a sandstone, 16 x 12 x 6 ins., dimly mkd. ¼ on N face and set in a mound of stone.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T 40 S R 23 E ¼ S 26 S 35 1980
	Deposit the mkd. stone alongside the iron post.
	S. 89° 55' W., beginning new measurement.
39.93	The cor. of secs. 26, 27, 34, and 35, monumented with a sandstone, 18 x 8 x 5 ins., firmly set 6 ins. in the ground and plainly mkd. 2 notches on the E and 1 on the S edges, with a mound of stone, 2 ft. base, 1½ ft. high, W of cor.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 40 S R 23 E S 27 | S 26 S 34 | S 35 1980
	Deposit the mkd. stone alongside the iron post.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	S. 0° 01' E., bet. secs. 34 and 35.
26.90	Point for the meander cor. on the right bank of the San Juan River at record distance; there is no remaining evidence of the original corner.
29.22	Point selected for the witness cor. to the meander cor. of secs. 34 and 35 on the right bank of the San Juan River.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 40 S R 23 E S 34 | S 35 WMC 1980
29.59	Point for the meander cor. of secs. 34 and 35, on the right bank of the San Juan River falls on unstable river bank.

CHAINS	
	From the cor. of secs. 26, 27, 34, and 35.
	N. 1° 08' E., bet. secs. 26 and 27.
40.44	The ¼ sec. cor. of secs. 26 and 27, monumented with a sandstone, 20 x 8 x 4 ins., plainly mkd. ¼ on W face and firmly set 10 ins. in the ground.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 40 S R 23 E ¼ S 27 | S 26 1980
	Deposit the mkd. stone alongside the iron post.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	N. 0° 01' E., beginning new measurement.
40.03	The cor. of secs. 22, 23, 26, and 27, monumented with a sandstone, 13 x 8 x 5 ins., plainly mkd. 2 notches on S and E edges, and set in a mound of stone.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 40 S R 23 E S 22 | S 23 S 27 | S 26 1980
	Deposit the mkd. stone alongside the iron post.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	From the cor. of secs. 23, 24, 25, and 26.
	N. 89° 28' W., bet. secs. 23 and 26.
40.00	Point for the ¼ sec. cor. of secs. 23 and 26, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 12 ins. long, 1 in. diam., 8 ins. in solid sandstone, with brass cap mkd.
	T 40 S R 23 E S 23 ¼ S 26 1980
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.
80.00	The cor. of secs. 22, 23, 26, and 27.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	N. 0° 17' W., bet. secs. 22 and 23.
39.99	The ¼ sec. cor. of secs. 22 and 23, monumented with a sandstone, 18 x 8 x 8 ins., plainly mkd. ¼ on W face, firmly set in a mound of stone, with a mound of stone W of cor. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base, to top of brass cap, mkd. T 40 S R 23 E ¼ S 22 | S 23 1980 Deposit the mkd. stone alongside the iron post.
	N. 0° 32' E., beginning new measurement.
40.49	The cor. of secs. 14, 15, 22, and 23, monumented with a mound of stone, 3 ft. base, 1½ ft. high. No mkd. stone found. This is accepted as the best available evidence of the position of the original corner. At the corner point (center of mound) Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 40 S R 23 E S 15 | S 14 S 22 | S 23 1980
	From the cor. of secs. 13, 14, 23, and 24. N. 89° 10' W., bet. secs. 14 and 23.
39.94	Point for the ¼ sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base, to top of brass cap, mkd. T 40 S R 23 E ¼ S 14 S 23 1980
79.88	The cor. of secs. 14, 15, 22, and 23.
	N. 0° 20' W., bet. secs. 14 and 15.
38.69	Point for the ¼ sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original corner.

257

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 40 S., R. 23 E., Salt Lake Meridian, Utah

CHAINS	
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a collar of stone, with brass cap mkd. T 40 S R 23 E ¼ S 15 | S 14 1980
77.38	The cor. of secs. 10, 11, 14, and 15, monumented with a sandstone, 14 x 8 x 4 ins., firmly set 6 ins. in the ground and plainly mkd. 2 notches on E and 1 notch on S edges, with a mound of stone, W of cor. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 S R 23 E S 10 | S 11 S 15 | S 14 1980 Deposit the mkd. stone alongside the iron post. Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	From the cor. of secs. 11, 12, 13, and 14. S. 88° 35' W., bet. secs. 11 and 14.
20.02	Point for the E 1/16 sec. cor. of secs. 11 and 14. Not monumented.
40.04	Point for the ¼ sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 2½ ft. base, to top of brass cap, mkd. T 40 S R 23 E ¼ S 11 S 14 1980
80.08	The cor. of secs. 10, 11, 14, and 15.
	N. 0° 15' E., bet. secs. 10 and 11.
40.81	Point for the ¼ sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	T 40 S R 23 E ¼ S 10 | S 11 1980
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
81.62	The cor. of secs. 2, 3, 10, and 11, monumented with a mound of stone, 3 ft. base, 2 ft. high. No mkd. stone was found. This is accepted as the best available evidence of the position of the original corner.
	At the corner point (center of mound)
	Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4½ ft. base, to top of brass cap, mkd.
	T 40 S R 23 E S 3 | S 2 S 10 | S 11 1980
	From the cor. of secs. 1, 2, 11, and 12.
	S. 89° 35' W., bet. secs. 2 and 11.
19.91	Point for the E 1/16 sec. cor. of secs. 2 and 11.
	Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd.
	T 40 S R 23 E E 1/16 S 2 S 11 1980
39.82	Point for the ¼ sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4½ ft. base, to top of brass cap, mkd.
	T 40 S R 23 E ¼ S 2 S 11 1980
79.64	The cor. of secs. 2, 3, 10, and 11.
	From the cor. of secs. 26, 27, 34, and 35.
	N. 89° 54' W., bet. secs. 27 and 34.
39.98	The ¼ sec. cor. of secs. 27 and 34, monumented with a sandstone, 16 x 10 x 6 ins., plainly mkd. ¼ on N face, and firmly set 8 ins. in the ground.
	At the corner point

CHAINS	
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 S R 23 E ¼ S 27 / S 34 1980 Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.
	N. 89° 38' W., beginning new measurement.
39.57	Point for the cor. of secs. 27, 28, 33, and 34, at record bearing and 40.00 chs. dist., from the ¼ sec. cor. of secs. 27 and 28. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 S R 23 E S 28 | S 27 S 33 | S 34 1980 This cor. will also function as a witness cor. for the meander cor. bet. secs. 33 and 34.
	S. 0° 02' E., bet. secs. 33 and 34.
2.34	True point for the meander cor. of secs. 33 and 34, on the right bank of the San Juan River, falls on unstable river bank.
	From the cor. of secs. 27, 28, 33, and 34.
	N. 0° 02' W., bet. secs. 27 and 28.
22.15	Point for the original meander cor. of secs. 27 and 28; there is no remaining evidence of the original corner. Not monumented.
40.00	The ¼ sec. cor. of secs. 27 and 28, monumented with a mound of stone, 2½ ft. base, 1½ ft. high. No mkd. stone was found. This is accepted as the best available evidence of the position of the original corner. At the corner point (center of mound) Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 S R 23 E ¼ S 28 | S 27 1980 Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	N. 0° 04' E., beginning new measurement.
39.85	The cor. of secs. 21, 22, 27, and 28, monumented with a sandstone, 16 x 7 x 6 ins., plainly mkd. 3 notches on the E and 2 notches on the S edges and firmly set 8 ins. in the ground, with a mound of stone, 2½ ft. base, 1½ ft. high, W of cor. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 S R 23 E S 21 | S 22 S 28 | S 27 1980 Deposit the mkd. stone alongside the iron post. Rebuild the mound of stone, 3 ft. base, 2 ft. high, W of cor.
	From the cor. of secs. 22, 23, 26, and 27. ~~N~~ S. 89° 48' W., bet. secs. 22 and 27.
40.14	Point for the ¼ sec. cor. of secs. 22 and 27, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base, to top of brass cap, mkd. T 40 S R 23 E ¼ S 22 S 27 1980
80.28	The cor. of secs. 21, 22, 27, and 28.
	N. 0° 07' E., bet. secs. 21 and 22.
40.01	Point for the ¼ sec. cor. of secs. 21 and 22, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4½ ft. base, to top of brass cap, mkd. T 40 S R 23 E ¼ S 21 | S 22 1980
80.02	The cor. of secs. 15, 16, 21, and 22, monumented with a sandstone, 24 x 12 x 8 ins., plainly mkd. "40E" on the NE and "23E" on the SE faces and firmly set 10 ins. in the ground.

CHAINS	
	At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 S R 23 E S 16 | S 15 S 21 | S 22 1980 Deposit the mkd. stone alongside the iron post. Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	From the cor. of secs. 14, 15, 22, and 23. S. 89° 28' W., bet. secs. 15 and 22.
40.14	Point for the ¼ sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T 40 S R 23 E ¼ S 15 S 22 1980
80.28	The cor. of secs. 15, 16, 21, and 22.
	N. 0° 05' W., bet. secs. 15 and 16.
39.76	The ¼ sec. cor. of secs. 15 and 16, monumented with a X¼ chiseled on sandstone ledge. The X part of the marking has fallen away from the ledge. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd. T 40 S R 23 E ¼ S 16 | S 15 1980
	N. 0° 02' E., beginning new measurement.
39.89	The cor. of secs. 9, 10, 15, and 16, monumented with a sandstone, 24 x 6 x 4 ins., firmly set 8 ins. in the ground, and plainly mkd. 4 notches on S and 3 notches on E edges. At the corner point

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 S R 23 E S 9 | S 10 S 16 | S 15 1980 Deposit the mkd. stone and a steel fence post, 6 ft. long, alongside the iron post.
	From the cor. of secs. 10, 11, 14, and 15. N. 88° 47' W., bet. secs. 10 and 15.
39.87	The ¼ sec. cor. of secs. 10 and 15, monumented with a sandstone, 18 x 8 x 4 ins., plainly mkd. ¼ on N face and projecting 10 ins. above the ground, with a mound of stone, N of cor. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 40 S R 23 E ¼ S 10 S 15 1980 Deposit the mkd. stone alongside the iron post.
	N. 89° 02' W., beginning new measurement.
19.99	Point for the W 1/16 sec. cor. of secs. 10 and 15. Not monumented.
39.98	The cor. of secs. 9, 10, 15, and 16.
	N. 1° 39' E., bet. secs. 9 and 10.
19.63	Point for the S 1/16 sec. cor. of secs. 9 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 40 S R 23 E S 1/16 S 9 | S 10 1980
39.26	The ¼ sec. cor. of secs. 9 and 10, monumented with a cross (X) chisled on solid sandstone, with a chiseled ¼ N of the cross. At the corner point

CHAINS	
	Set an iron post, 30 ins. long, 2½ ins. diam., on solid rock over a chiseled cross, and in a mound of stone, 4½ ft. base, to top of brass cap, mkd. T 40 S R 23 E ¼ S 9 | S 10 1980
	N. 1° 41' W., beginning new measurement.
40.40	The cor. of secs. 3, 4, 9, and 10, monumented with an iron post, 2½ ins. diam., projecting 10 ins. above a mound of stone, 4 ft. base, with iron cap mkd. T 40 S R 23 E 4 | 3 9 | 10 L.S. 2334 This monument is accepted as a careful and faithful perpetuation of the position of the original corner position.
	From the cor. of secs. 2, 3, 10, and 11. S. 89° 41' W., bet. secs. 3 and 10.
40.12	Point for the ¼ sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd. T 40 S R 23 E ¼ S 3 S 10 1980
80.24	The cor. of secs. 3, 4, 9, and 10.
	N. 0° 06' E., bet. secs. 3 and 4.
40.28	Point for the ¼ sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner. Not monumented.
80.56	The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., hereinbefore described.
	From the cor. of secs. 27, 28, 33, and 34. S. 89° 56' W., bet. secs. 28 and 33.
13.03	Intersect the mean high water mark of the right bank of the San Juan River. Not monumented.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	From the cor. of secs. 21, 22, 27, and 28.
	N. 89° 57' W., bet. secs. 21 and 28.
39.82	The ¼ sec. cor. of secs. 21 and 28, monumented with an iron post, 2½ ins. diam., projecting 8 ins. above the ground, with iron cap mkd. ¼ SEC21 / SEC28 LS2334 A sandstone, 12 x 8 x 4 ins., plainly mkd. ¼ was set alongside the iron post.
	N. 89° 59' W., beginning new measurement.
40.10	The cor. of sec. 20, 21, 28, and 29, monumented with a cross (X) chiseled on a steep sandstone ledge, facing W, 4 notches chiseled E and 2 notches chiseled S of the X. from which An iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top for a reference monument, bears S. 2° 30' E., 0.211 chs. dist., with brass cap mkd. RM T40S R23E S28 13.92 FT 1980 and an arrow pointing to the true corner point. An iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, for a reference monument, bears N. 10° W., 0.196 chs. dist., with brass cap mkd. RM T40S R23E S20 12.92 FT 1980 and an arrow pointing to the true corner point.
	S. 0° 03' E., bet. secs. 28 and 29 on record bearing.
40.00	Point for the ¼ sec. cor. of secs. 28 and 29. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 40 S R 23 E ¼ S 29 | S 28 1980
55.50	Point for the original meander cor. of secs. 28 and 29, on the right bank of the San Juan River; there is no remaining evidence of the original corner.
61.41	Point selected for the witness cor. to the meander cor. of secs. 28 and 29. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

CHAINS	
	T 40 S R 23 E | S 29 | S 28 WMC 1980
62.31	True point for the meander cor. of secs. 28 and 29, on the right bank of the San Juan River, falls on unstable river bank.
	From the cor. of secs. 20, 21, 28, and 29.
	N. 0° 03' E., bet. secs. 20 and 21.
40.61	The ¼ sec. cor. of secs. 20 and 21, monumented with a sandstone, 16 x 12 x 4 ins., plainly mkd. ¼ on W face and firmly set in a mound of stone.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base, to top of brass cap, mkd.
	T 40 S R 23 E ¼ | S 20 | S 21 | 1980
	N. 0° 08' E., beginning new measurement.
39.32	The cor. of secs. 16, 17, 20, and 21, monumented with a 2 x 2 in. pine post projecting 6 ft. above a mound of stone, 3 ft. base, 2 ft. high. No mkd. stone found. This is accepted as the best available evidence of the position of the original corner.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd.
	T 40 S R 23 E S 17 | S 16 S 20 | S 21 1980
	From the cor. of secs. 15, 16, 21, and 22.
	S. 89° 58' W., bet. secs. 16 and 21.
39.98	Point for the ¼ sec. cor. of secs. 16 and 21, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	T 40 S R 23 E ¼ S 16 / S 21 1980
79.96	The cor. of secs. 16, 17, 20, and 21.
	N. 0° 19' W., bet. secs. 16 and 17.
40.00	True point for the ¼ sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original corner. Corner point falls on a steep loose clay slope and is impossible to perpetuate or occupy.
40.10	Point selected for the witness cor. to the ¼ sec. cor. of secs. 16 and 17. Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd. W C T 40 S R 23 E ¼ S 17 | S 16 1980
80.00	Point for the cor. of secs. 8, 9, 16, and 17, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base, to top of brass cap, mkd. T 40 S R 23 E S 8 | S 9 / S 17 | S 16 1980
	From the cor. of secs. 9, 10, 15, and 16. N. 89° 48' W., bet. secs. 9 and 16.
40.17	Point for the ¼ sec. cor. of secs. 9 and 16, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 S R 23 E ¼ S 9 / S 16 1980
80.34	The cor. of secs. 8, 9, 16, and 17.
	N. 0° 39' E., bet. secs. 8 and 9.
40.00	The ¼ sec. cor. of secs. 8 and 9, monumented with a sandstone, 22 x 8 x 6 ins., plainly mkd. ¼ on W face and firmly set 12 ins. in a collar of stone.

CHAINS	
	At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of brass cap, mkd. T 40 S R 23 E ¼ S 8 | S 9 1980 Deposit the mkd. stone alongside the iron post.
	N. 0° 07' E., beginning new measurement.
19.98	Point for the N 1/16 sec. cor. of secs. 8 and 9. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 40 S R 23 E N 1/16 S 8 | S 9 1980
39.96	The cor. of secs. 4, 5, 8, and 9, monumented with an iron post, 2½ ins. diam., projecting 14 ins. above the ground, with iron cap, mkd. T 40 S R 23 E 5 | 4 8 | 9 L.S. 2334 This monument is accepted as a careful and faithful perpetutation of the original corner position.
	From the cor. of secs. 3, 4, 9, and 10. N. 89° 12' W., bet. secs. 4 and 9.
39.89	The ¼ sec. cor. of secs. 4 and 9, monumented with an iron post, 2½ ins. diam., projecting 12 ins. above the ground, with iron cap, mkd. ¼ SEC 4 / SEC 9 L.S. 2334 A sandstone, 14 x 7 x 5 ins., plainly mkd. ¼ was set alongside the iron post. Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.
	N. 89° 56' W., beginning new measurement.
19.92	Point for the W 1/16 sec. cor. of secs. 4 and 9. Not monumented.
39.84	The cor. of secs. 4, 5, 8, and 9.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	N. 0° 23' E., bet. secs. 4 and 5.
39.95	Point for the ¼ sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 4½ ft. base, to top of aluminum cap, mkd. T 40 S R 23 E ¼ S 5 | S 4 1980
79.90	The cor. of secs. 4 and 5, on the N. bdy. of the Tp., hereinbefore described.
	From the cor. of secs. 20, 21, 28, and 29. S. 89° 55' W., bet. secs. 20 and 29.
40.04	The ¼ sec. cor. of secs. 20 and 29, monumented with a sandstone, 14 x 10 x 4 ins., dimly mkd. ¼ on N face and firmly set in a mound of stone, 3 ft. base, 1½ ft. high. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 S R 23 E ¼ S 20 / S 29 1980 Deposit the mkd. stone alongside the iron post. Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.
	S. 89° 33' W., beginning new measurement.
39.82	The cor. of secs. 19, 20, 29, and 30, monumented with a sandstone, 16 x 14 x 6 ins., plainly mkd. 5 notches on the E and 2 notches on S edges, firmly set 8 ins. in the ground. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 S R 23 E S 19 | S 20 S 30 | S 29 1980 Deposit the mkd. stone alongside the iron post. Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

269

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 40 S., R. 23 E., Salt Lake Meridian, Utah

CHAINS	
	S. 0° 03' E., bet. secs. 29 and 30.
19.81	Point selected for the witness cor. to the meander cor. of secs. 29 and 30. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 S R 23 E S 30 | S 29 WMC 1980
20.81	True point for the meander cor. of secs. 29 and 30, on the right bank of the San Juan River, falls on unstable river bank.
	From the cor. of secs. 19, 20, 29, and 30. N. 89° 46' W., bet. secs. 19 and 30.
39.79	Point for the ¼ sec. cor. of secs. 19 and 30, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 S R 23 E ¼ S 19 S 30 1980 Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.
79.45	The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set in the ground, with brass cap mkd. as described in the official record of the 1953 dependent resurvey of the E. bdy. of T. 40 S., R. 22 E.
	From the cor. of secs. 19, 20, 29, and 30. N. 0° 20' W., bet. secs. 19 and 20.
39.90	The ¼ sec. cor. of secs. 19 and 20, monumented with a sandstone, 18 x 10 x 4 ins., plainly mkd. ¼ on W face and firmly set 8 ins. in the ground. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd. T 40 S R 23 E ¼ S 19 | S 20 1980

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	Deposit the mkd. stone alongside the iron post.
	N. 0° 34' E., beginning new measurement.
40.17	Point for the cor. of secs. 17, 18, 19, and 20, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 S R 23 E S 18 | S 17 S 19 | S 20 1980 Deposit a steel fence post, 6 ft. long, alongside the iron post.
	From the cor. of secs. 16, 17, 20, and 21.
	N. 89° 57' W., bet. secs. 17 and 20.
40.15	The ¼ sec. cor. of secs. 17 and 20, monumented with a sandstone, 24 x 9 x 3 ins., plainly mkd. ¼ on N face and set in a collar of stone. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a collar of stone, with brass cap mkd. T 40 S R 23 E ¼ S 17 S 20 1980 Deposit the mkd. stone alongside the iron post.
	S. 89° 37' W., beginning new measurement.
39.65	The cor. of secs. 17, 18, 19, and 20.
	N. 89° 33' W., bet. secs. 18 and 19.
39.63	The ¼ sec. cor. of secs. 18 and 19, monumented with a sandstone, 20 x 12 x 6 ins., set 6 ins. in the ground, with a mound of stone, 2½ ft. base, 1½ ft. high, N of cor. Marks have been obliterated. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 40 S R 23 E ¼ S 18 S 19 1980

CHAINS	
	Deposit the found stone alongside the iron post.
	S. 89° 56' W., beginning new measurement.
39.99	The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set in the ground, with brass cap, mkd. as described in the official record of the dependent resurvey of the E. bdy. of T. 40 S., R. 22 E., resurveyed concurrently under this same group.
	From the cor. of secs. 17, 18, 19, and 20.
	N. 0° 04' W., bet. secs. 17 and 18.
40.17	The ¼ sec. cor. of secs. 17 and 18, monumented with a broken sandstone, 10 x 6 x 4 ins., plainly mkd. ¼ on N face, and set 5 ins. in the ground, with a mound of stone, 2 ft. base, 1½ ft. high, W of cor.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T 40 S R 23 E ¼ S 18 | S 17 1980
	Deposit the mkd. stone alongside the iron post.
	Rebuild the mound of stone, 3 ft. base, 2 ft. high, W of cor.
	N. 0° 02' W., beginning new measurement.
39.97	The cor. of secs. 7, 8, 17, and 18, monumented with a sandstone, 16 x 8 x 6 ins., plainly mkd. 5 notches on the E and 4 notches on the S edges, firmly set 8 ins. in the ground, with a mound of stone, 2 ft. base, 1 ft. high, W of cor.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base, to top of brass cap, mkd.
	T 40 S R 23 E S 7 | S 8 S 18 | S 17 1980
	Deposit the mkd. stone alongside the iron post.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	From the cor. of secs. 8, 9, 16, and 17.
	S. 89° 50' W., bet. secs. 8 and 17.
40.17	The ¼ sec. cor. of secs. 8 and 17, monumented with a sandstone, 14 x 8 x 6 ins., marks have been obliterated, firmly set 6 ins. in the ground, with a mound of stone, 3 ft. base, 2 ft. high, N of cor.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 40 S R 23 E ¼ S 8 / S 17 1980
	Deposit the found stone alongside the iron post.
	Rebuild the mound of stone, 3 ft. base, 2 ft. high, N of cor.
	S. 89° 57' W., beginning new measurement.
39.25	The cor. of secs. 7, 8, 17, and 18.
	N. 89° 58' W., bet. secs. 7 and 18.
39.86	Point for the ¼ sec. cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base, to top of brass cap, mkd.
	T 40 S R 23 E ¼ S 7 / S 18 1980
79.45	The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set in the ground, with brass cap mkd. as described in the official record of the dependent resurvey of the E. bdy. of T. 40 S., R. 22 E., resurveyed concurrently under this same group.
	From the cor. of secs. 7, 8, 17, and 18.
	N. 0° 08' E., bet. secs. 7 and 8.
39.95	Point for the ¼ sec. cor. of secs. 7 and 8, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., over a cross (X) chiseled in solid sandstone, and in a mound of stone, 4 ft. base, to top of brass cap, mkd.

273

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 40 S., R. 23 E., Salt Lake Meridian, Utah

CHAINS	
	T 40 S R 23 E ¼ S 7 | S 8 1980
79.90	The cor. of secs. 5, 6, 7, and 8, monumented with an iron post, 2½ ins. diam., and in a mound of stone, 4½ ft. base, to top of iron cap, mkd. T 40 S R 23 E 6 | 5 7 | 8 LS2334 A sandstone, 20 x 10 x 10 ins., plainly mkd. 5 notches on two edges was set alongside the iron post.
	From the cor. of secs. 4, 5, 8, and 9. S. 89° 55' W., bet. secs. 5 and 8.
39.86	Point for the ¼ sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., over a cross (X) chiseled on solid sandstone, and in a mound of stone, 4½ ft. base, to top of brass cap, mkd. T 40 S R 23 E ¼ S 5 / S 8 1980
79.72	The cor. of secs. 5, 6, 7, and 8.
	N. 89° 57' W., bet. secs. 6 and 7.
39.98	Point for the ¼ sec. cor. of secs. 6 and 7, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 40 S R 23 E ¼ S 6 / S 7 1980
79.62	The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set in the ground, with brass cap mkd. as described in the official record of the dependent resurvey of the E. bdy. of T. 40 S., R. 22 E., resurveyed concurrently under this same group.
	From the cor. of secs. 5, 6, 7, and 8.

☆U.S. Government Printing Office: 1980—778-251/292

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 40 S., R. 23 E., Salt Lake Meridian, Utah

CHAINS	
	N. 0° 14' W., bet. secs. 5 and 6.
40.23	True point for the ¼ sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner. The cor. point falls on a steep sandstone boulder, 30 x 50 x 50 ft., and is impossible to perpetuate or occupy.
42.78	Point selected for the witness cor. to the ¼ sec. cor. of secs. 5 and 6. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. W C T 40 S R 23 E ¼ S 6 | S 5 1980 Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
80.46	The cor. of secs. 5 and 6, on the N. bdy. of the Tp., hereinbefore described.
	Partial Subdivisional Survey of Section 4, T. 40 S., R. 23 E., Salt Lake Meridian, Utah
	From the ¼ sec. cor. of secs. 4 and 9. N. 0° 19' E., on the N-S center line of sec. 4.
39.86	Point for the center ¼ sec. cor. of sec. 4, at intersection with the E-W center line. Not monumented.
79.93	The ¼ sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp., hereinbefore described.
	From the point for the ¼ sec. cor. of secs. 3 and 4. N. 89° 48' W., on the E-W center line of sec. 4.
39.73	Point for the center ¼ sec. cor. of sec. 4.
59.63	Point for the center W 1/16 sec. cor. of sec. 4. Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of brass cap, mkd. W 1/16 C S 4 C 1980
79.53	The ¼ sec. cor. of secs. 4 and 5.

275

Partial Subdivisional Survey of Section 4,
T. 40 S., R. 23 E., Salt Lake Meridian, Utah

CHAINS	
	From the center W 1/16 sec. cor. of sec. 4.
	N. 0° 21' E., on the N-S center line of the NW¼ of sec. 4.
40.01	The W 1/16 sec. cor. of sec. 4, on the N. bdy. of the Tp., hereinbefore described.

Partial Subdivisional Survey of Section 9,
T. 40 S., R. 23 E., Salt Lake Meridian, Utah

	From the ¼ sec. cor. of secs. 9 and 16.
	N. 0° 09' E., on the N-S center line of sec. 9.
19.82	Point for the center S 1/16 sec. cor. of sec. 9.
	Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd.
	C | S 1/16 | S 9 | C 1980
39.64	Point for the center ¼ sec. cor. of sec. 9, at intersection with the E-W center line.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 40 S R 23 E C ¼ S 9 1980
	Deposit a steel fence post, 6 ft. long, alongside the iron post.
59.85	Point for the center N 1/16 sec. cor. of sec. 9. Not monumented.
80.06	The ¼ sec. cor. of secs. 4 and 9.
	From the ¼ sec. cor. of secs. 9 and 10.
	N. 89° 16' W., on the E-W center line of sec. 9.
41.19	The center ¼ sec. cor. of sec. 9.
61.10	Point for the center W 1/16 sec. cor. of sec. 9.
	Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd.
	W 1/16 C ——— C S 9 1980

☆U.S. Government Printing Office: 1980—778-251/292

Partial Subdivisional Survey of Section 9,
T. 40 S., R. 23 E., Salt Lake Meridian, Utah

CHAINS	
81.01	The ¼ sec. cor. of secs. 8 and 9.
	From the center W 1/16 sec. cor. of sec. 9.
	N. 0° 08' E., on the N-S center line of the NW¼ of sec. 9.
20.09	Point for the NW 1/16 sec. cor. of sec. 9, at intersection with the E-W center line of the NW¼.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	NW 1/16 S 9 1980
40.18	Point for the W 1/16 sec. cor. of secs. 4 and 9.
	From the center N 1/16 sec. cor. of sec. 9.
	N. 89° 36' W., on the E-W center line of the NW¼ of sec. 9.
19.92	The NW 1/16 sec. cor. of sec. 9.
39.84	The N 1/16 sec. cor. of secs. 8 and 9.
	Partial Subdivisional Survey of Section 10, T. 40 S., R. 23 E., Salt Lake Meridian, Utah
	From the ¼ sec. cor. of secs. 10 and 15.
	N. 0° 04' E., on the N-S center line of sec. 10.
19.97	Point for the center S 1/16 sec. cor. of sec. 10. Not monumented.
39.94	Point for the center ¼ sec. cor. of sec. 10, at intersection with the E-W center line.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T 40 S R 23 E C¼ S 10 1980
	Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.
80.54	The ¼ sec. cor. of secs. 3 and 10.
	From the ¼ sec. cor. of secs. 10 and 11.
	S. 89° 59' W., on the E-W center line of sec. 10.
39.99	The center ¼ sec. cor. of sec. 10.
59.44	Point for the center W 1/16 sec. cor. of sec. 10.

277

Partial Subdivisional Survey of Section 10,
T. 40 S., R. 23 E., Salt Lake Meridian, Utah

CHAINS	
	Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd. W 1/16 C ——— C S 10 1980
78.89	The ¼ sec. cor. of secs. 9 and 10.
	From the point for the W 1/16 sec. cor. of secs. 10 and 15. N. 0° 51' E., on the N-S center line of the SW¼ of sec. 10.
19.80	Point for the SW 1/16 sec. cor. of sec. 10, at intersection with the E-W center line of the SW¼. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. SW 1/16 S 10 1980
39.60	The center W 1/16 sec. cor. of sec. 10.
	From the point for the center S 1/16 sec. cor. of sec. 10. N. 89° 31' W., on the E-W center line of the SW¼ of sec. 10.
19.72	The SW 1/16 sec. cor. of sec. 10.
39.44	The S 1/16 sec. cor. of secs. 9 and 10.
	Partial Subdivisional Survey of Section 11, T. 40 S., R. 23 E., Salt Lake Meridian, Utah
	From the ¼ sec. cor. of secs. 11 and 14. N. 0° 07' E., on the N-S center line of sec. 11.
20.27	Point for the center S 1/16 sec. cor. of sec. 11. Not monumented.
40.54	Point for the center ¼ sec. cor. of sec. 11, at intersection with the E-W center line. Not monumented.
80.91	The ¼ sec. cor. of secs. 2 and 11.
	From the ¼ sec. cor. of secs. 11 and 12. S. 88° 58' W., on the E-W center line of sec. 11.
19.94	Point for the center E 1/16 sec. cor. of sec. 11. Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	E 1/16 C ——— C S 11 1980
39.88	Point for the center ¼ sec. cor. of sec. 11.
79.80	The ¼ sec. cor. of secs. 10 and 11.
	From the center E 1/16 sec. cor. of sec. 11.
	N. 0° 05' E., on the N-S center line of the NE¼ of sec. 11.
40.17	The E 1/16 sec. cor. of secs. 2 and 11.
	From the point for the E 1/16 sec. cor. of secs. 11 and 14.
	North, on the N-S center line of the SE¼ of sec. 11.
20.13	Point selected for the witness cor. to the SE 1/16 sec. cor. of sec. 11.
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.
	W C SE 1/16 S 11 ↑ 1980
20.20	True point for the SE 1/16 sec. cor. of sec. 11, at intersection with the E-W center line of the SE¼, falls on a steep sandstone ledge and is impossible to perpetuate or occupy.
40.40	The center E 1/16 sec. cor. of sec. 11.
	From the S 1/16 sec. cor. of secs. 11 and 12.
	S. 88° 47' W., on the E-W center line of the SE¼ of sec. 11.
19.98	The SE 1/16 sec. cor. of sec. 11.
39.96	Point for the center S 1/16 sec. cor. of sec. 11.
	Portion of the Meander Lines of T. 40 S., R. 23 E., Salt Lake Meridian, Utah
	From the point for the meander cor. of secs. 35 and 36, hereinbefore described.
	Thence, with the meanders of the present right bank of the San Juan River downstream through sec. 35.
	S. 65° 41' W., 8.49 chs.
	S. 51° 40' W., 8.15 chs.

279

Portion of the Meander Lines of
T. 40 S., R. 23 E., Salt Lake Meridian, Utah

CHAINS		
	S. 64° 40' W., 7.12 chs.	
	S. 57° 19' W., 5.84 chs.	
	S. 62° 04' W., 6.02 chs.	
	S. 64° 20' W., 9.94 chs.	
	N. 58° 51' W., 4.58 chs.	
	N. 65° 20' W., 17.82 chs.	
	N. 60° 50' W., 22.88 chs.	True point for the meander cor. of secs. 34 and 35, hereinbefore described.
	Thence, with the meanders of the present right bank of the San Juan River downstream through sec. 34.	
	N. 68° 15' W., 4.94 chs.	
	S. 81° 11' W., 9.95 chs.	
	N. 81° 59' W., 6.65 chs.	
	N. 65° 17' W., 3.94 chs.	
	N. 56° 47' W., 11.90 chs.	
	N. 64° 21' W., 18.49 chs.	
	N. 43° 25' W., 4.41 chs.	
	N. 71° 59' W., 13.94 chs.	
	N. 59° 28' W., 5.46 chs.	
	N. 81° 00' W., 3.23 chs.	
	S. 81° 30' W., 4.20 chs.	True point for the meander cor. of secs. 33 and 34, hereinbefore described.
	Thence, with the meanders of the present right bank of the San Juan River downstream through sec. 33.	
	S. 83° 14' W., 7.37 chs.	
	N. 60° 49' W., 6.55 chs.	Point for the meander cor. of secs. 28 and 33, hereinbefore described.
	Thence with the meanders of the present right bank of the San Juan River downstream through section 28.	
	N. 60° 06' W., 7.72 chs.	
	N. 55° 10' W., 30.13 chs.	
	S. 63° 17' W., 7.82 chs.	
	S. 73° 52' W., 4.79 chs.	
	S. 88° 34' W., 9.20 chs.	

☆U.S. Government Printing Office: 1980—778-251/292

Portion of the Meander Lines of
T. 40 S., R. 23 E., Salt Lake Meridian, Utah

CHAINS		
	N. 83° 42' W., 14.74 chs.	True point for the meander cor. of secs. 28 and 29, hereinbefore described.
	Thence, with the meanders of the present right bank of the San Juan River downstream through sec. 29.	
	N. 84° 29' W., 4.84 chs.	
	N. 77° 16' W., 16.86 chs.	
	N. 52° 39' W., 24.79 chs.	
	N. 12° 47' W., 6.30 chs.	
	N. 10° 35' W., 18.58 chs.	
	S. 79° 33' W., 18.85 chs.	
	N. 86° 38' W., 15.56 chs.	True point for the meander cor. of secs. 29 and 30, hereinbefore described.
	Thence, with the meanders of the present right bank of the San Juan River downstream through sec. 30.	
	N. 86° 38' W., 31.95 chs.	
	S. 76° 23' W., 16.68 chs.	
	S. 49° 03' W., 4.61 chs.	
	S. 26° 26' W., 5.73 chs.	
	S. 15° 27' W., 7.61 chs.	
	S. 9° 33' E., 7.65 chs.	
	S. 17° 18' E., 10.34 chs.	
	S. 14° 55' W., 5.64 chs.	
	S. 35° 01' W., 5.85 chs.	
	S. 64° 19' W., 8.36 chs.	
	N. 89° 42' W., 11.93 chs.	
	S. 89° 22' W., 3.39 chs.	True point for the meander cor. of secs. 25 and 30, on the W. bdy. of the Tp., at a point South, 0.05 chs. distance from the witness meander cor., monumented with an iron post, 2½ ins. diam., firmly set, with brass cap mkd. as described in the official record of the 1953 resurvey.

281

Township 40 South, Range 23 East, Salt Lake Meridian, Utah

CHAINS

General Description

Township 40 South, Range 23 East, is situated about 29 miles SE of Blanding, Utah. The town of Montezuma Creek, Utah is located in sections 25 and 36. The elevation varies from 4350 to 5350 feet above sea level. The soil varies from silt along the river bottoms to sand dunes in many areas of the township.

The San Juan River crosses the township from the east to the west. McCracken Canyon and Bucket Canyon drain from the north into the San Juan River, but were dry during the survey.

Numerous oil and natural gas pumps and drilling rigs are present throughout the township. Utah State Highway No. 262 crosses through sections 1 and 12. Further access to the township is provided by numerous secondary roads and trails. A gas pipeline crosses the township from east to west. There is a store and several homes in section 36 and several homes in section 25.

☆U.S. Government Printing Office: 1980—778-251/292

Form 9600-11
(August 1979)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

282

FIELD ASSISTANTS

NAMES	CAPACITY
Jerry L. Thomas	Supervisory Cadastral Surveyor
Donzil Worthington	Surveying Technician
Larry Judd	Surveying Technician
John Mavor	Surveying Technician
Richard A. Zaninovich	Supervisory Cadastral Surveyor

CERTIFICATE OF SURVEY

(I) (~~WE~~) Donald A. Buhler, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 2nd day of May, 1979, (I) (~~WE~~) have dependently resurveyed a portion of the west boundary of the Navajo Indian Reservation; a portion of the north and east boundaries; a portion of the subdivisional lines, and surveyed the subdivisions of sections 4, 9, 10, and 11, and a portion of the meander lines of Township 40 South, Range 23 East

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), (~~us~~) and under (my) (~~our~~) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

April 27, 1983
(Date)

/s/ Donald A. Buhler
(Cadastral Surveyor)
Supervisory

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the west boundary of the Navajo Indian Reservation, a portion of the north and east boundaries, a portion of the subdivisional lines, the survey of the subdivision of sections 4, 9, 10, and 11, and a portion of the meander lines of Township 40 South, Range 23 East of the Salt Lake Meridian, Utah

executed by Donald A. Buhler, Supervisory Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

August 15, 1983
(Date)

Glen B Hatch
(~~Chief, Cadastral Survey Examination and Approval Staff~~)
Chief Cadastral Surveyor for Utah

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in , is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief, Cadastral Survey Examination and Approval Staff)~~
Chief Cadastral Surveyor for Utah

Form 9600-9
(December 1979)
(formerly 9180-6)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

R606

284

ORIGINAL
FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF THE NORTH 5 MILES OF THE SALT LAKE MERIDIAN

IN TOWNSHIP 28 SOUTH, AND THE NORTH BOUNDARY OF SECTION 1,

AND

THE SURVEY OF SECTIONS 1, 11, 12, 13, 14, 23, 24, 25, AND 26

OF

TOWNSHIP 28 SOUTH, RANGE 1 WEST

Of the Salt Lake Meridian,

In the State of Utah.

EXECUTED BY

Gail E. Reynolds Supervisory Cadastral Surveyor

Under special instructions dated January 26, 19 83, approved January 27, 1983,

, which provided for the surveys included under U.S. Survey/Group

Number 626, and assignment instructions dated May 25, 19 83.

Survey commenced June 10, 19 83

Survey completed June 27, 19 83

285

INDEX DIAGRAM

Township 28 S., Range 1 W.,

6	5	4	3	2	7 1 6 9
7	8	9	10 14	11 13	12 5 9
18	17	16	15 13	14 12	13 4 8
19	20	21	22 11	23 11	24 3 8
30	29	28	27 10	26	25 2
31	32	33	34	35	36

GPO 855-927

Township 28 South, Range 1 West, Salt Lake Meridian Utah

CHAINS

HISTORY OF SURVEYS

	Surveyed by		Retr. or Resurveyed by	
EAST BOUNDARY (Salt Lake Meridian)				
All	T.C. Bailey	1874		
All			Breckon and McCarty	1897
All			S.P. Stewart	1915
S. 1 mile			G.F. Rigby	1922
NORTH BOUNDARY				
E. 5 miles	T.C. Bailey	1874		
W. 1 mile	Breckon and McCarty	1897		
E. 5 miles			Breckon and McCarty	1897
E. 2 miles			G.W. Hochstrasser	1969
SUBDIVISION				
Portion	T.C. Bailey	1874		
Portion	Breckon and McCarty	1897		
Portion	G.F. Rigby	1923		
Portion	W.H. Sylvester	1961		
Portion	G.W. Hochstrasser	1969		

The following field notes are those of the dependent resurvey of the north 5 miles of the Salt Lake Meridian in Tp. 28 S., and the north boundary of section 1 and the survey of sections 1, 11, 12, 13, 14, 23, 24, 25, and 26 of T. 28 S., R. 1 W., Salt Lake Meridian, Utah.

The resurvey and survey were exected in accordance with the specificiations set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated January 26, 1983.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The direction of all lines were determined from observations of Polaris and carried forward by sustained angulation and the distances were determined by electronic measuring equipment.

The geographic position of the corner of sections 30 and 31, T. 28 S., R. 1 E., is at Latitude 38° 20' 22.87" N., and Longitude 111° 50' 44.95" W., as computed by traverse and section line ties to U.S.C. and G.S. triangulation station Sec Cor 36-1/4E/28S/1W identical with the 1/4 sec. cor. of section 36 only, T. 28 S., R. 1 W., located S. 1° 25' 21' E., 42.454 chains dist. at Latitude 38° 19' 55.168" N. and Longitude 111° 50' 44.079" W. station occupied.

The magnetic declination is 14° 00' E.

287

Dependent Resurvey of a Portion of the Salt Lake Meridian of T. 28 S., R. 1 W. and R. 1 E., Salt Lake Meridian, Utah

CHAINS

Dependent Resurvey of a Portion of the Salt Lake Meridian of T. 28 S., R. 1 W. and R. 1 E., Salt Lake Meridian, Utah

(Restoring the Resurvey Executed by T.C. Bailey in 1874 and the Retracement of Breckon and McCarty in 1897 and the Resurvey by S.P. Stewart in 1915)

Beginning at the cor. of secs. 30 and 31, T. 28 S., R. 1 E., monumented with an iron post, 3 ins. diam., extending 12 ins. out of the ground, with brass cap mkd. as described in the official record of the 1922 resurvey.

From this cor., the cor. of secs. 25 and 36, T. 28 S., R. 1 W., monumented with an iron post, 3 ins. diam., extending 12 ins. out of the ground, with brass cap, mkd. as described in the official record of the 1922 resurvey, bears S. 1° 25' 21" E., 2.45 chs. dist.

From this same cor., the ¼ sec. cor. of sec. 36, T. 28 S., R. 1 W., which has been designated as the U.S. Coast and Geodetic Survey triangulation station Sec Cor 36-1/4E/28S/1W, monumented with an iron post, 1 in. diam., extending 10 ins. out of the ground, with brass cap, mkd. as described in the official record of the 1915 resurvey, bears S. 1° 25' 21" E., 42.454 chs. dist.

Cor. is located in 5 strand barbwire fence cor., fences bear E and S.

N. 1° 22' W., on the Salt Lake Meridian.

Over rolling mountain land, through sagebrush.

22.00 Draw, drains NE.

37.56 Point for the ¼ sec. cor. of sec. 25 only.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 28 S
R 1 W R 1 E
¼ |
S 25 |
1983

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

Cor. is located on spur, slopes NE in low sagebrush and native grasses.

40.01 The ¼ sec. cor. of secs. 25 and 30, monumented with an iron post, 1 in. diam., extending 10 ins. out of the ground, with brass cap, mkd. as described in the official record of the 1915 resurvey. I remove markings for sec. 25 and add 1983 to brass cap. This cor. will now function as the ¼ sec. cor. of sec. 30 only.

CHAINS

N. 1° 23' W., beginning new measurement.

Over rolling mountain land, through sagebrush and native grasses.

37.56 Point for the cor. of secs. 24 and 25.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 28 S
R 1 W | R 1 E
S 24 | S 30
S 25 |
1983

Raise a mound of stone, 3½ ft. base, 2 ft. high, W of cor.

Cor. is located in small draw, drains NE.

39.93 The cor. of secs. 19, 24, 25, and 30, monumented with an iron post, 3 ins. diam., extending 12 ins. out of the ground, with brass cap, mkd. as described in the official record of the 1915 resurvey. This cor. will now function as the cor. of secs. 19 and 30 only. I remove markings for secs. 24 and 25 and add 1983 to brass cap.

N. 1° 22' W., on the Salt Lake Meridian.

Over rolling mountain land, through sagebrush and native grasses.

36.85 Small draw, drains NE.

37.64 Point for the ¼ sec. cor. of sec. 24 only.

Set an aluminum post. 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 28 S
R 1 W | R 1 E
¼ |
S 24 |
1983

Raise a mound of stone, 3½ ft. base, 2 ft. high, W of cor.

Cor. is located on rolling mountain land in sagebrush and native grasses.

39.92 The ¼ sec. cor. of secs. 19 and 24, monumented with an iron post, 1 in. diam., extending 18 ins. out of the ground and in a mound of stone, with brass cap, mkd. as described in the official record of the 1915 resurvey. This cor. will now function as the ¼ sec. cor. of sec. 19 only. I remove markings for sec. 24 and add 1983 to brass cap.

N. 1° 24' W., beginning new measurement.

Over rolling mountain land, through sagebrush and native grasses.

CHAINS	
37.73	Point for the cor. of secs. 13 and 24. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 28 S R 1 W R 1 E S 13 | S 19 S 24 | 1983 Raise a mound of stone, 4 ft. base, 2½ ft. high, W of cor. Cor. is located on gently rolling land in sagebrush and native grasses.
40.03	The cor. of secs. 13, 18, 19, and 24, monumented with an iron post, 3 ins. diam., extending 12 ins. out of the ground, with brass cap, mkd. as described in the official record of the 1915 resurvey. This cor. will now function as the cor. of secs. 18 and 19 only. I remove the markings for secs. 13 and 24 and add 1983 to brass cap.
	N. 1° 24' W., on the Salt Lake Meridian. Over rolling mountain land, through sagebrush and native grasses.
37.71	Point for the ¼ sec. cor. of sec. 13 only. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 28 S R 1 W R 1 E ¼ | S 13 | 1983 Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor. Cor. is located on gently rolling land in sagebrush and native grasses.
38.56	Trail road, bears NE and SW.
39.99	The ¼ sec. cor. of secs. 13 only, monumented with an iron post, 1 in. diam., extending 10 ins. out of the ground with brass cap, mkd. as described in the official record of the 1915 resurvey. This cor. will now function as the ¼ sec. cor. of sec. 18, T. 28 S., R. 1 E., only. I remove the markings for sec. 13 and add the marks ¼ S18 and 1983 to the brass cap.
	N. 1° 23' W., beginning new measurement. Over rolling mountain land, through sagebrush and native grasses.
37.73	Point for the cor. of secs. 12 and 13.

CHAINS	
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd. T 28 S R 1 W R 1 E S 12 | S 18 S 13 | 1983 Raise a mound of stone, 4 ft. base, 2 ft. high, W of cor. Cor. is located on W edge of trail road, bears N and S.
39.93	The cor. of secs. 12 and 13, monumented with an iron post, 3 ins. diam., extending 12 ins. out of the ground with brass cap, mkd. as described in the official record of the 1915 resurvey. This cor. will now function as an angle point only. I remove the markings for sec. 13 and add the marks S18 AP and 1983 to brass cap.
	N. 1° 24' W., on the Salt Lake Meridian. Over rolling mountain land, through sagebrush and native grasses.
0.48	The closing cor. of secs. 7 and 18, monumented with an iron post, 2 ins. diam., extending 18 ins. out of the ground, with brass cap, mkd. as described in the official record of the 1915 resurvey.
2.50	Trail road, bears SE and NW; enter juniper and scattered aspen growth.
37.81	Point for the ¼ sec. cor. of sec. 12 only. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 28 S R 1 W R 1 E ¼ | S 12 | 1983 Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
39.94	The ¼ sec. cor. of sec. 12 only, monumented with an iron post, 1 in. diam., extending 10 ins. out of the ground with brass cap, mkd. as described in the official record of the 1915 resurvey. This cor. will now function as an angle point only. I remove the ¼ markings and add the marks AP and 1983 to brass cap.
	N. 1° 23' W., beginning new measurement.
0.59	Point for the ¼ sec. cor. of sec. 7 only, at midpoint between closing cors. Set an aluminum post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 4½ ft. base, to top of aluminum cap mkd.

291

Dependent Resurvey of a Portion of the Salt Lake Meridian of T. 28 S., R. 1 W. and R. 1 E., Salt Lake Meridian, Utah

CHAINS	
	T 28 S R 1 W R 1 E | ¼ | S 7 1983
	Leave timber.
37.88	Point for the cor. of secs. 1 and 12. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T 28 S R 1 W R 1 E S 1 | S 7 S 12 | 1983
	Raise a mound of stone, 4 ft. base, 2 ft. high, W of cor.
39.99	The cor. of secs. 1 and 12, monumented with an iron post, 3 ins. diam., extending 12 ins. out of the ground with brass cap, mkd. as described in the official record of the 1915 resurvey. This cor. will now function as an angle point only. I remove the markings for sec. 12 and add the markings S7 AP and 1983 to brass cap.
	N. 1° 19' W., on the Salt Lake Meridian. Over rolling mountain land, through sagebrush and native grasses.
0.66	The closing cor. of secs. 6 and 7, T. 28 S., R. 1 E., monumented with an iron post, 2 ins. diam., extending 24 ins. out of the ground and in a mound of stone, 3½ ft. base to brass cap, mkd. as described in the official record of the 1915 resurvey.
37.90	Point for the ¼ sec. cor. of sec. 1 only. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T 28 S R 1 W R 1 E ¼ | S 1 | 1983
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
40.04	The ¼ sec. cor. of sec. 1 only, monumented with an iron post, 1 in. diam., extending 10 ins. out of the ground, with brass cap, mkd. as described in the official record of the 1915 resurvey. This cor. will now function as an angle point only. I remove the ¼ markings and add the marks S6 AP and 1983 to brass cap.
	N. 1° 19' W., beginning new measurement. Over rolling mountain land, through sagebrush and native grasses.

Dependent Resurvey of a Portion of the Salt Lake Meridian
of T. 28 S., R. 1 W. and R. 1 E., Salt Lake Meridian, Utah

CHAINS	
0.66	Point for the ¼ sec. cor. of sec. 6 only, at proportionate distance. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 28 S R 1 W | R 1 E | ¼ | S 6 1983 Raise a mound of stone, 2½ ft. base, 1 ft. high, W of cor.
39.94	The cor. of Tps. 27 and 28 S., Rs. 1 E. and 1 W., monumented with an iron post, 3 ins. diam., extending 16 ins. out of the ground, with brass cap, mkd. as described in the official record of the 1915 resurvey.

Dependent Resurvey of the North Boundary of Section 1,
T. 28 S., R. 1 W., Salt Lake Meridian, Utah

(Restoring the Survey Executed by T.C. Bailey in 1874
and the Resurvey by Breckon and McCarty in 1897
and the Resurvey by G.W. Hochstrasser in 1969)

	From the cor. of Tps. 27 and 28 S., Rs. 1 E. and 1 W., hereinbefore described. S. 89° 37' W., on the N. bdy. of sec. 1. Over rolling mountain land, through sagebrush and native grasses.
28.27	Point for the ¼ sec. cor. of sec. 1 only. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 27 S ¼ S 1 T 28 S R 1 W 1983 Raise a mound of stone, 4 ft. base, 2 ft. high, S of cor. Cor. is located on gentle S slope in sagebrush and native grasses.
35.00	Road, bears N. 20° E. and S. 20° W.
40.05	The ¼ sec. cor. of sec. 36, T. 27 S., R. 1 W., monumented with an iron post, 2½ ins. diam., extending 10 ins. out of the ground, and in a mound of stone to brass cap, mkd. as described in the official record of the 1969 resurvey. S. 89° 33' W., beginning new measurement.

293

Dependent Resurvey of the North Boundary of Section 1,
T. 28 S., R. 1 W., Salt Lake Meridian, Utah

CHAINS	
28.22	The closing cor. of secs. 1 and 2, monumented with an iron post, 2½ ins. diam., extending 10 ins. out of the ground and in a mound of stone to brass cap, mkd. as described in the official record of the 1969 resurvey.

Survey of a Portion of the Subdivisional Lines of
T. 28 S., R. 1 W., Salt Lake Meridian, Utah

From the cor. of secs. 24 and 25, on the E. bdy. of the Tp., hereinbefore described.

S. 89° 54' W., bet. secs. 24 and 25.

Over rolling mountain land, through sagebrush and native grasses.

23.00 Draw, drains NE.

36.12 Point for the ¼ sec. cor. of secs. 24 and 25.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to rock, and in a mound of stone, 3½ ft. base, to top of aluminum cap, mkd.

T 28 S R 1 W
¼ S 24 / S 25
1983

Cor. is located on SE slope in sagebrush and native grasses.

71.00 Trail road, bears NW and SE.

76.12 The cor. of secs. 23, 24, 25, and 26, monumented with an iron post, 2½ ins. diam., extending 12 ins. out of the ground, and in a mound of stone, with brass cap, mkd. as described in the official record of the 1969 survey.

From the cor. of secs. 13 and 24, on the E. bdy. of the Tp., hereinbefore described.

S. 89° 53' W., bet. secs. 13 and 24.

Over rolling mountain land, through sagebrush and native grasses.

30.50 Trail road, bears NE and SW.

34.14 Point for the ¼ sec. cor. of secs. 13 and 24.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 28 S R 1 W
¼ S 13 / S 24
1983

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

Survey of a Portion of the Subdivisional Lines of
T. 28 S., R. 1 W., Salt Lake Meridian, Utah

CHAINS	
74.14	The cor. of secs. 13, 14, 23, and 24, monumented with an iron post, 2½ ins. diam., extending 15 ins. out of the ground and in a mound of stone, to brass cap, mkd. as described in the official record of the 1969 survey.
	From the cor. of secs. 12 and 13, on the E. bdy. of the Tp., hereinbefore described. S. 89° 51' W., bet. secs. 12 and 13. Over rolling mountain land, through sagebrush and native grasses.
32.11	Point for the ¼ sec. cor. of secs. 12 and 13. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 28 S R 1 W ¼ S 12 / S 13 1983 Raise a mound of stone, 3½ ft. base, 2 ft. high, N of cor. Cor. is located on gentle NE slope in sagebrush and native grasses.
72.11	The cor. of secs. 11, 12, 13, and 14, monumented with an iron post, 2½ ins. diam., extending 12 ins. out of the ground, and in a collar of stone, with brass cap, mkd. as described in the official record of the 1969 survey. from which U.S. Geological Survey triangulation station "Antelope", monumented with a brass cap, 3 ins. diam., cemented in lava rock boulder, bears S. 13° 46' 52" W., 46.13 chs. dist., brass cap mkd. ANTELOPE 1968.
	From the cor. of secs. 1 and 12, on the E. bdy. of the Tp., hereinbefore described. S. 89° 51' W., bet. secs. 1 and 12. Over rolling mountain land, through sagebrush and native grasses.
30.18	Point for the ¼ sec. cor. of secs. 1 and 12. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 28 S R 1 W ¼ S 1 / S 12 1983 Raise a mound of stone, 3½ ft. base, 2 ft. high, N of cor.

CHAINS	
	Cor. is located on gently rolling land in sagebrush and native grasses.
43.00	Trail road, bears NW and SE.
67.00	Trail road, bears NNE and SSW.
70.18	The cor. of secs. 1, 2, 11, and 12, monumented with an iron post, 2½ ins. diam., extending 28 ins. out of the ground, and in a mound of stone to brass cap, mkd. as described in the official record of the 1969 survey.
	From the cor. of secs. 26, 27, 34, and 35, monumented with an iron post, 2½ ins. diam., extending 8 ins. out of the ground, with brass cap, mkd. as described in the official record of the 1961 survey. from which An aspen, 8 ins. diam., bears N. 32° 30' E., 33 lks. dist., mkd. T28S R1W S26 BT. An aspen, 9 ins. diam., bears S. 61° 30' E., 57 lks. dist., mkd. T28S R1W S35 BT. An aspen, 9 ins. diam., bears S. 30° 15' W., 56 lks. dist., mkd. T28S R1W S34 BT. An aspen, 8 ins. diam., bears N. 82° 45' W., 27 lks. dist., mkd. T28S R1W S27 BT. N. 0° 01' W., bet. secs. 26 and 27. Over broken mountain land, through dense aspen and fir.
18.80	Top of ridge, bears E and W, over broken NW slope.
40.00	Point for the ¼ sec. cor. of secs. 26 and 27. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 28 S R 1 W ¼ S 27 | S 26 1983 from which A fir, 14 ins. diam., bears N. 26° E., 13½ lks. dist., mkd. ¼ S26 BT. A fir, 10 ins. diam., bears N. 82° W., 35½ lks. dist., mkd. ¼ S27 BT. Raise a mound of stone, 3½ ft. base, 2 ft. high, W of cor. Cor. is located on steep NW slope in dense fir and aspen.
80.00	Point for the cor. of secs. 22, 23, 26, and 27.

Survey of a Portion of the Subdivisional Lines of
T. 28 S., R. 1 W., Salt Lake Meridian, Utah

CHAINS	
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground, and in a mound of stone, 6 ft. base, to top of aluminum cap, mkd. T 28 S R 1 W S 22 | S 23 S 27 | S 26 1983 from which A mahogany, 8 ins. diam., bears S. 54° E., 23 lks. dist., mkd. BT. A fir, 14 ins. diam., bears N. 27° W., 47 lks. dist., mkd. S27 BT. Raise a mound of stone, 4 ft. base, 2 ft. high, W of cor. Cor. is located on steep W slope in mahogany and scattered pinon.
	From the cor. of secs. 23, 24, 25, and 26. N. 89° 53' W., bet. secs. 23 and 26. Over rolling mountain land, through sagebrush and scattered patches of aspen.
12.50	Trail road, bears NE and SW.
39.93	Point for the ¼ sec. cor. of secs. 23 and 26. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 28 S R 1 W S 23 ¼ S 26 1983 Raise a mound of stone, 3½ ft. base, 2 ft. high, N of cor. Cor. is located on rolling E slope in sagebrush and native grasses.
64.00	Trail road, bears S and N.
72.65	Top of ridge, bears N and S; desc. W slope.
79.86	The cor. of secs. 22, 23, 26, and 27.
	N. 0° 01' W., bet. secs. 22 and 23. Over broken W slope, through mahogany and scattered pinon.
40.00	Point for the ¼ sec. cor. of secs. 22 and 23. Set an aluminum post. 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

297

Survey of a Portion of the Subdivisional Lines of
T. 28 S., R. 1 W., Salt Lake Meridian, Utah

CHAINS	
	T 28 S R 1 W ¼ S 22 | S 23 1983 from which A fir, 8 ins. diam., bears N. 82° E., 34 lks. dist., mkd. ¼ S BT. A juniper, 6 ins. diam., bears N. 56° W., 19 lks. dist., mkd. ¼ BT. Raise a mound of stone, 4 ft. base, 2 ft. high, W of cor. Cor. is located on gentle W slope in mahogany, fir, and juniper growth.
80.00	Point for the cor. of secs. 14, 15, 22, and 23. Set an aluminum post. 30 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd. T 28 S R 1 W S 15 | S 14 S 22 | S 23 1983 Cor. is located on W slope in dense juniper and pinon tree growth.
	From the cor. of secs. 13, 14, 23, and 24. N. 89° 53' W., bet. secs. 14 and 23. Over rolling mountain land, through sagebrush and native grasses.
39.94	Point for the ¼ sec. cor. of secs. 14 and 23. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 28 S R 1 W S 14 ¼ S 23 1983 Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor. Cor. is located on gently rolling mountain land, in sagebrush and native grasses.
44.00	Trail road, bears N and S.
45.00	Ridge, bears N and S; desc. broken W slope, through pinon, juniper, and mahogany.
79.88	The cor. of secs. 14, 15, 22, and 23.

CHAINS	
	N. 0° 01' W., bet. secs. 14 and 15.
	Over broken W slope, through pinon, juniper, mahogany tree growth.
40.00	Point for the ¼ sec. cor. of secs. 14 and 15.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 28 S R 1 W
¼
S 15 | S 14
1983

	Raise a mound of stone, 3½ ft. base, 2 ft. high, W of cor.
	Cor. is located on broken NE slope in light juniper, pinon, and mahogany tree growth.
80.00	Point for the cor. of secs. 10, 11, 14, and 15.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 28 S R 1 W
S 10 | S 11
S 15 | S 14
1983

	Cor. is located on W slope in scattered pinon and juniper tree growth.
	From the cor. of secs. 11, 12, 13, and 14.
	N. 89° 52' W., bet. secs. 11 and 14.
	Over rolling mountain land, through sagebrush and native grasses.
10.00	Trail road, bears NE and SW.
39.94	Point for the ¼ sec. cor. of secs. 11 and 14.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 28 S R 1 W
S 11
¼
S 14
1983

	Raise a mound of stone, 3½ ft. base, 2 ft. high, N of cor.
	Cor. is located on top of ridge, bears N and S in sagebrush and native grasses.
41.80	Trail road, bears N and S; desc. broken W slope, through juniper and pinon tree growth.
79.88	The cor. of secs. 10, 11, 14, and 15.

299

Survey of a Portion of the Subdivisional Lines of
T. 28 S., R. 1 W., Salt Lake Meridian, Utah

CHAINS	
	N. 0° 02' W., bet. secse. 10 and 11.
	Over broken W slope, through pinon and juniper tree growth.
39.91	Point for the ¼ sec. cor. of secs. 10 and 11.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 6 ft. base, to top of aluminum cap, mkd.
	T 28 S R 1 W ¼ S 10 | S 11 1983
	Cor. is located on broken W slope in pinon and juniper growth.
79.82	The cor. of secs. 2, 3, 10, and 11, monumented with an iron post, 2½ ins. diam., extending 16 ins. out of the ground, and in a mound of stone, to brass cap, mkd. as described in the official record of the 1969 survey.
	from which
	A pinon, 11 ins. diam., bears N. 32° 45' E., 11 lks. dist., mkd. T28S R1W S2 BT.
	A pinon, 16 ins. diam., bears S. 52¼° W., 11 lks. dist., mkd. T28S R1W S10 BT.

General Description

The area surveyed is located about 16 miles west of Loa, Utah, on the Parker Mountains.

In the portion surveyed the vegetation consist of mostly sagebrush in the eastern portion; aspen, fir, pinon, juniper, and mahogany in the south and west portions. The general elevation varies between 7,600 ft. to 9,600 ft. above sea level. The soil is a sandy loam and lava rock. No mineral activity was noted in the area.

There are numerous trail roads throughout the area. The area is used principally for grazing of cattle, sheep, antelope, elk, and deer. There are no permanent residents in the area.

300

Form 9600-11
(August 1979)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Richard Zaninovich	Supervisory Cadastral Surveyor
Ferrel D. Reynolds	Supervisory Surveying Technician
Rex Smith	Surveying Technician
John B. Julander	Surveying Technician
Joel B. Nystrom	Survey Aid

301

CERTIFICATE OF SURVEY

(I)XXX), Gail E. Reynolds, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 26th day of January, 1983, (I) (XXX) have dependently resurveyed the north 5 miles of the Salt Lake Meridian in Tp. 28 S., and the north boundary of section 1, and surveyed sections 1, 11, 12, 13, 14, 23, 24, 25, and 26 of Township 28 South, Range 1 West,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), (us) and under (my) (your) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

July 21, 1983
(Date)

Gail E. Reynolds
(Cadastral Surveyor)
Supervisory

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Denver, Colorado

The foregoing field notes of the dependent resurvey of the north 5 miles of the Salt Lake Meridian in Tp. 28 S., and the north boundary of section 1, and the survey of sections 1, 11, 12, 13, 14, 23, 24, 25, and 26 of T. 28 S., R. 1 W., Salt Lake Meridian, Utah

executed by Gail E. Reynolds, Supervisory Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

July 29, 1983
(Date)

Glen B Hatch
(Chief, Cadastral Survey, Examination and Approval Section)
Chief Cadastral Surveyor for Utah

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

(Date)

(Chief, Cadastral Survey, Examination and Approval Section)
Chief Cadastral Surveyor for Utah

Vol. R606

302

Form 9600-9
(December 1979)
(formerly 9180-6)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF THE

FIFTH STANDARD PARALLEL SOUTH,

THROUGH A PORTION OF RANGE 5 WEST,

A PORTION OF THE SUBDIVISIONAL LINES

AND

THE SURVEY OF THE SUBDIVISION

OF

SECTIONS 33 AND 34

OF

TOWNSHIP 25 SOUTH, RANGE 5 WEST

Of the Salt Lake Meridian,

In the State of Utah.

EXECUTED BY

Craig P. Sylvester Supervisory Cadastral Surveyor

Under special instructions dated January 19, 19 81, approved January 19, 1981,

_____, which provided for the surveys included under U.S. Survey/Group

Number 605, and assignment instructions dated January 19, 19 81.

Survey commenced January 22, 19 81

Survey completed May 1, 19 81

INDEX DIAGRAM

Township 25 South, Range 5 West,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28 7	27 5	26	25
31	32 6	33 4 2	34 3 1	35	36

Subdivision of Section 33 - Page 7
Subdivision of Section 34 - Page 9

Township 25 South, Range 5 West, Salt Lake Meridian, Utah

CHAINS

The following field notes are those of the dependent resurvey of the Fifth Standard Parallel South through a portion of Range 5 West, a portion of the subdivisional lines and the survey of the subdivision of sections 33 and 34 of Township 25 South, Range 5 West, Salt Lake Meridian, Utah.

The south boundary (Fifth Standard Parallel South) was surveyed by Henry Fitzhugh in 1882, and resurveyed by Page and Erwin in 1900. The subdivisional lines were surveyed by Henry Fitzhugh in 1882.

Certain corners were remonumented in 1970 under the remonumentation cooperative agreement between the U.S. Forest Service and the BLM.

The resurvey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group 605, Utah, dated January 19, 1981.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of the lines of this survey were determined by reference to true meridians established on line by hour angle observations on Polaris. They were carried forward by sustained angulation, being supplemented by numerous other observations on Polaris taken throughout the progress of the survey. Distances were determined by electronic means along survey lines where accessible.

The geographic position of the southeast corner of section 34, as scaled from U.S.G.S. quadrangle sheet "Trail Mountain", 7½' series, is as follows:

Latitude 38° 34.3' N. Longitude 112° 26.3' W.

The mean magnetic declination is 14° 30' E.

Dependent Resurvey of the Fifth Standard Parallel South,
Through a Portion of Range 5 West,
Salt Lake Meridian, Utah

(Restoring the Survey Executed by Henry Fitzhugh in 1882, and the Resurvey Executed by Page and Erwin in 1900)

Beginning at the standard cor. of secs. 34 and 35, on the S. bdy. of the Tp., monumented with a granite stone, 18 x 10 x 10 ins., firmly set and plainly mkd. 2 notches on E edge and SC on N face, other marks broken off. Also mound of stone and steel fence post alongside corner.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top of brass cap, mkd.

Dependent Resurvey of the Fifth Standard Parallel South,
Through a Portion of Range 5 West,
Salt Lake Meridian, Utah

CHAINS	
	S C T 25 S R 5 W S 34 | S 35 S 10 T 26 S R 5 W 1981
	Deposit the mkd. stone and set steel fence post alongside the iron post.
	N. 89° 55' W., along the S. bdy. of sec. 34.
	Over mountain land covered with juniper and pinon.
39.92	The standard ¼ sec. cor. of sec. 34, monumented with a lava stone, 20 x 14 x 8 ins., firmly set and mkd. SC, and ¼ on N face. Also steel fence post alongside corner.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	S C T 25 S R 5 W ¼ S 34 1981
	Deposit the mkd. stone alongside the iron post.
	N. 89° 38' W., beginning new measurement.
	Continue over mountain land.
12.43	Fence on the right-of-way line of Interstate 70, bears N. 60° 52' W. and S. 60° 52' E., thence over freeway. Under construction.
28.965	Fence on the right-of-way line of Interstate 70, bears N. 60° 52' W. and S. 60° 52' E., continue over mountain land.
41.17	The standard cor. of secs. 33 and 34, monumented with an iron post, 2½ ins. diam., firmly set in a collar of stone, with brass cap mkd. as described in the remonumentation of corners in T. 25 S., R. 5 W. in 1970.
	S. 89° 44' W., along the S. bdy. of sec. 33.
	Over mountain land, covered with juniper and pinon.
11.00	Power line, bears WNW and ESE.
19.79	Point for the standard E 1/16 sec. cor. of sec. 33.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap, mkd.
	S C T 25 S R 5 W E 1/16 S 33 1981
23.80	Shingle Creek, 12 lks. wide, drains NE.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS

39.58 Point for the standard ¼ sec. cor. of sec. 33, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 3½ ft. base, to top of aluminum cap, mkd.

S C
T 25 S R 5 W
¼ S 33
1981

Cor. is located on rocky SE slope of spur, which slopes S.

79.16 The standard cor. of secs. 32 and 33, monumented with a granite stone, 24 x 12 x 6 ins., plainly mkd. 2 notches on W and 4 notches on E edges, and CC on N face.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

S C
T 25 S R 5 W
S 32 | S 33
S 8
T 26 S R 5 W
1981

Deposit the mkd. stone alongside the aluminum post.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 25 S., R. 5 W., Salt Lake Meridian, Utah

---

(Restoring the Survey Executed by Henry Fitzhugh in 1882)

From the standard cor. of secs. 34 and 35, on the S. bdy. of the Tp., hereinbefore described.

N. 2° 41' W., bet. secs. 34 and 35.

Over mountain land, covered with juniper and pinon.

40.42 Point for the ¼ sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 25 S R 5 W
¼
S 34 | S 35
1981

CHAINS	
	Cor. is located on NE slope of spur, about 100 ft. below top of spur, which slopes N. 10° W.
56.00	Clear Creek, drains irregularly E.
58.00	Center line of Utah State Highway No. 70 in bottom of Clear Creek Canyon, bears SNE and NSW
80.84	The cor. of secs. 26, 27, 34, and 35, monumented with a lava stone, 18 x 8 x 4 ins., firmly set in a small mound of stone and plainly mkd. 1 notch on S and 2 notches on E edges. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd. T 25 S R 5 W S 27 | S 26 S 34 | S 35 1981 Deposit the mkd. stone alongside the iron post. Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	From the standard cor. of secs. 33 and 34, on the S. bdy. of the Tp., hereinbefore described. N. 4° 52' W., bet. secs. 33 and 34. Over mountain land.
5.63	Fence on the right-of-way line of Interstate 70, bears SE and NE on curve, thence over construction work on freeway.
14.50	Fence on the right-of-way line of Interstate 70, bears SE and NW on curve.
19.815	Point for the S 1/16 sec. cor. of secs. 33 and 34, falls on small sandstone ledges. Set an iron post, 12 ins. long, 1 in. diam., 9 ins. into a hole drilled into solid sandstone, with brass cap mkd. T 25 S R 5 W S 1/16 S 33 | S 34 1981
25.90	Shingle Creek, drains NE.
39.63	The ¼ sec. cor. of secs. 33 and 34, monumented with a granite stone, 18 x 9 x 9 ins., firmly set in a mound of stone and plainly mkd. ¼ on W face. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	T 25 S R 5 W ¼ S 33 | S 34 1981
	Deposit the mkd. stone alongside the iron post.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	Cor. is located in an E - W fence line.
	N. 0° 05' E., beginning new measurement.
	Continue over mountain land.
11.80	Clear Creek, drains SE.
13.20	Center line of Utah State Highway No. 70 in Clear Creek Canyon, bears E and W.
20.31	Point for the N 1/16 sec. cor. of secs. 33 and 34.
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T 25 S R 5 W N 1/16 S 33 | S 34 1981
40.62	The cor. of secs. 27, 28, 33, and 34, monumented with a sandstone, 17 x 11 x 5 ins., in a small mound of stone, mkd. 3 notches on E and 1 notch on S edges.
	At the corner point
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.
	T 25 S R 5 W S 28 | S 27 S 33 | S 34 1981
	Deposit the mkd. stone alongside the aluminum post.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	From the cor. of secs. 26, 27, 34, and 35.
	S. 89° 52' W., bet. secs. 27 and 34.
	Over mountain land, covered with juniper and pinon, along general S slope.
40.33	The ¼ sec. cor. of secs. 27 and 34, monumented with a lava stone, 17 x 14 x 6 ins., firmly set and plainly mkd. ¼ on N face.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T 25 S R 5 W ¼ S 27 / S 34 1981
	Deposit the mkd. stone alongside the iron post.
	Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.
	S. 89° 41' W., beginning new measurement.
	Continue over mountain land, along S slope.
20.14	Point for the W 1/16 sec. cor. of secs. 27 and 34.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.
	T 25 S R 5 W W 1/16 S 27 / S 34 1981
	Continue along general S slope.
40.28	The cor. of secs. 27, 28, 33, and 34.
	From the standard cor. of secs. 32 and 33, on the S. bdy. of the Tp., hereinbefore described.
	N. 3° 51' W., bet. secs. 32 and 33.
	Over mountain land, through juniper and pinon.
34.00	Power line, bears SNW and NSE.
34.54	Fence on the right-of-way line of Interstate 70, bears N. 64° 38' W. and S. 64° 38' E., thence over freeway under construction.
40.55	Point for the ¼ sec. cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T 25 S R 5 W ¼ S 32 | S 33 1981
	Cor. is located on steep S slope of cut, on N side of Interstate 70.

☆U.S. Government Printing Office: 1980—778-251/292

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
43.37	Fence on the right-of-way line of Interstate 70, bears N. 64° 38' W. and S. 64° 38' E.; thence over mountain land.
81.10	The cor. of secs. 28, 29, 32, and 33, monumented with a granite stone, 22 x 19 x 10 ins., set in a scattered mound of stone, marks have been obliterated. At the corner point Set an aluminum post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd. T 25 S R 5 W S 29 | S 28 S 32 | S 33 1981
	From the cor. of secs. 27, 28, 33, and 34. N. 89° 42' W., bet. secs. 28 and 33. Over mountain land, covered with juniper and pinon.
27.60	Center line of Utah State Highway No. 70 in Clear Creek Canyon, bears NW and SE.
31.00	Clear Creek, drains SE.
40.65	Point for the ¼ sec. cor. of secs. 28 and 33, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., on solid rock, over a cross (X) and in a mound of stone, 6 ft. base, to top of aluminum cap, mkd. T 25 S R 5 W ¼ S 28 S 33 1981 Continue over mountain land.
81.30	The cor. of secs. 28, 29, 32, and 33.
	Survey of the Subdivision of Section 33, T. 25 S., R.5 W., Salt Lake Meridian, Utah
	From the standard ¼ sec. cor. of sec. 33, on the S. bdy. of the Tp., hereinbefore described. N. 3° 06' W., on the N and S center line of sec. 33. Over mountain land.
14.00	Power line, bears SNW and NSE.
15.68	Fence on the right-of-way line of Interstate 70, bears SE and NW on curve; thence over freeway under construction.

Survey of the Subdivision of Section 33,
T. 25 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
20.01	Point for the center South 1/16 sec. cor. of sec. 33, falls within the freeway construction area and was not monumented.
22.44	Fence on the right-of-way line of Interstate 70, bears NW and SE on curve.
40.02	Point for the center ¼ sec. cor. of sec. 33, at intersection with the E and W center line. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 25 S R 5 W C ¼ S 33 1981
80.62	The ¼ sec. cor. of secs. 28 and 33.
	From the ¼ sec. cor. of secs. 33 and 34. N. 89° 34' W., on the E and W center line of sec. 33. Over mountain land.
19.195	Point for the center East 1/16 sec. cor. of sec. 33. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T 25 S R 5 W E 1/16 C ——— C S 33 1981
38.39	The center ¼ sec. cor. of sec. 33.
72.68	Fence on the right-of-way line of Interstate 70, bears N. 64° 38' W. and S. 64° 38' E., thence over freeway under construction.
78.52	The ¼ sec. cor. of secs. 32 and 33.
	From the standard E 1/16 sec. cor. of sec. 33, on the S. bdy. of the Tp., hereinbefore described. N. 3° 59' W., on the N and S center line of the SE¼ of sec. 33. Over mountain land in Shingle Creek Canyon.
4.50	Power line, bears SNW and NSE.
7.80	Enter construction area of Interstate 70 bridge over Shingle Creek Canyon, drains NE.
19.91	Point for the SE 1/16 sec. cor. of sec. 33, at intersection with the E and W center line. Set an iron post, 30 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.

★U.S. Government Printing Office: 1980—778-251/292

Survey of the Subdivision of Section 33,
T. 25 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
	SE 1/16 S 33 1981
	Cor. is located under a gate in Interstate 70 fence line.
39.82	The center East 1/16 sec. cor. of sec. 33.
	From the South 1/16 sec. cor. of secs. 33 and 34.
	N. 89° 55' W., on the E and W center line of the SE¼ of sec. 33.
	Over mountain land.
8.00	Shingle Creek, drains NE.
19.495	The SE 1/16 sec. cor. of sec. 33.
30.025	Fence on the right-of-way line of Interstate 70, on curve NW and SE; thence over freeway under construction.
38.99	Point for the center South 1/16 sec. cor. of sec. 33, falls within the freeway construction area and was not monumented.
	Survey of the Subdivision of Section 34, T. 25 S., R. 5 W., Salt Lake Meridian, Utah
	From the standard ¼ sec. cor. of sec. 34, on the S. bdy. of the Tp., hereinbefore described.
	N. 2° 58' W., on the N and S center line of sec. 34.
	Over mountain land, through juniper and pinon.
20.05	Point for the center South 1/16 sec. cor. of sec. 34.
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top of brass cap, mkd.
	T 25 S R 5 W C S 1/16 | S 34 C 1981
	From this cor., an old fence cor. bears N. 88° 58' W., 2.87 chs. dist., fences bear N and W.
40.10	Point for the center ¼ sec. cor. of sec. 34, at intersection with the E and W center line.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.
	T 25 S R 5 W C ¼ S 34 1981
	Cor. is located 1.20 chs. E of old N and S fence.

Survey of the Subdivision of Section 34,
T. 25 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
48.20	Clear Creek, drains E.
49.50	Center line of Utah State Highway No. 70 in Clear Creek Canyon, bears E and W, in canyon.
60.405	Point for the center North 1/16 sec. cor. of sec. 34.
	Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T 25 S R 5 W C N 1/16 | S 34 C 1981
80.71	The ¼ sec. cor. of secs. 27 and 34.
	From the ¼ sec. cor. of secs. 34 and 35.
	S. 89° 36' W., along the E and W center line of sec. 34.
	Over mountain land, through juniper and pinon.
40.11	The center ¼ sec. cor. of sec. 34.
61.335	Point for the center West 1/16 sec. cor. of sec. 34.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.
	T 25 S R 5 W W 1/16 C ——— C S 34 1981
67.70	Shingle Creek, drains NE.
82.56	The ¼ sec. cor. of secs. 33 and 34.
	From the center South 1/16 sec. cor. of sec. 34.
	S. 89° 59' W., on the E and W center line of the SW¼ of sec. 34.
	Over mountain land.
41.81	The S 1/16 sec. cor. of secs. 33 and 34.
	From the center West 1/16 sec. cor. of sec. 34.
	N. 1° 27' W., on the N and S center line of the NW¼ of sec. 34.
	Over mountain land.

★U.S. Government Printing Office: 1980 – 778-251/292

Survey of the Subdivision of Section 34,
T. 25 S., R. 5 W., Salt Lake Meridian, Utah

CHAINS	
4.50	Shingle Creek, drains NE.
8.50	Clear Creek, drains E.
9.70	Center line of Utah State Highway No. 70 in Clear Creek Canyon, bears E and W.
20.31	Point for the NW 1/16 sec. cor. of sec. 34, at intersection with the E and W center line. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 25 S R 5 W NW 1/16 S 34 1981
40.62	The W 1/16 sec. cor. of secs. 27 and 34.
	From the center North 1/16 sec. cor. of sec. 34. S. 89° 39' W., on the E and W center line of the NW¼ of sec. 34. Over mountain land.
20.68	The NW 1/16 sec. cor. of sec. 34.
41.36	The N 1/16 sec. cor. of secs. 33 and 34.
	From the center south 1/16 sec. cor. of sec. 34. S. 89° 59' W., on the E and W center line of the SW¼ of sec. 34. Over mountain land.
41.81	The S 1/16 sec. cor. of secs. 33 and 34.
	General Description The portion of T. 25 S., R. 5 W., covered by this survey consists of mountain land covered with juniper, pinon, and oak brush, with small grass meadows along Shingle Creek. Utah State Highway No. 70 bears E and W in Clear Creek Canyon, through sections 33 and 34, and a new freeway, Interstate 70, under construction through the south portion of sections 33 and 34. The elevations varies from about 6400 to 7000 ft. above sea level. There is no permanent habitat within sections 33 and 34.

Form 9600-11
(August 1979)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Ferrel D. Reynolds	Supervisory Surveying Technician
Gail E. Reynolds	Supervisory Cadastral Surveyor
John Julander	Survey Aid

316

CERTIFICATE OF SURVEY

(I)(XXX), Craig P. Sylvester, Supervisory Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 19th day of January, 1981, (I) (XXX) have dependently resurveyed the Fifth Standard Parallel South, through a portion of Range 5 West, a portion of the subdivisional lines and surveyed the subdivision of sections 33 and 34 of T. 25 S., R. 5 W.

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), (XXX) and under (my) (XXX) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

February 8, 1982
(Date)

Craig P. Sylvester
(Cadastral Surveyor)
Supervisory

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Denver, Colorado

The foregoing field notes of the dependent resurvey of the Fifth Standard Parallel South, through a portion of Range 5 West, a portion of the subdivisional lines and the survey of the subdivision of sections 33 and 34 of T. 25 S., R. 5 W. Salt Lake Meridian, Utah

executed by Craig P. Sylvester, Supervisory Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

November 7, 1983
(Date)

Glen B Hatch
~~(Chief, Cadastral Survey, Examination and Approval Staff)~~
Chief, Cadastral Surveyor for Utah

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.~~

~~(Date)~~

~~Chief, Cadastral Surveyor for Utah~~

Vol. R606 317

Form 9600-9
(December 1979)
(formerly 9180-6)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

THE NORTH BOUNDARY,

AND A

PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SURVEY OF A PARTIAL SUBDIVISION

OF SECTIONS 3, 4, AND 5

OF

TOWNSHIP 43 SOUTH, RANGE 1 WEST

Of the Salt Lake Meridian,

In the State of Utah.

EXECUTED BY

Gail E. Reynolds Supervisory Cadastral Surveyor

Under special instructions dated May 4, 19 81, approved May 4, 1981,

_____, which provided for the surveys included under U.S. Survey/Group

Number 608, and assignment instructions dated May 5, 19 81.

Survey commenced June 8, 19 81

Survey completed June 26, 19 81

INDEX DIAGRAM

Township 43 South, Range 1 West,

4 6 10	4 5 10 10	3 4 8 9	3 3 7 7	2 2 6 6	2 1 5
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision of Section 3 - Page 11
Subdivision of Section 4 - Page 12
Subdivision of Section 5 - Page 13

GPO 855-927

Township 43 South, Range 1 West, Salt Lake Meridian, Utah

CHAINS

T. 43 S., R. 1 W.

History of Surveys

	Surveyed by	Retr. or Resurveyed by
NORTH BOUNDARY		
All	J.G. Burrill 1877	
E. 4 miles		Thoma and Johnston 1916
EAST BOUNDARY (Salt Lake Meridian)		
Portion	J.G. Burrill 1877	
Portion	A. Nelson and E. Bird 1917	
Portion		A. Nelson and E. Bird 1918
Portion		J. Thomas 1976
WEST BOUNDARY		
N. 1 mile	J.G. Burrill 1877	
S. 5 miles	W.H. Miller 1917	
N. 1 mile		A. Nelson and W. Miller 1917
SUBDIVISION		
Portion	J.G. Burrill 1877	
Portion	A. Nelson and E. Bird 1917	
Portion		E. Bird 1917

The following field notes are those of the dependent resurvey of the north boundary, a portion of the subdivisional lines, and the survey of a partial subdivision of sections 3, 4, and 5 of Township 43 South, Range 1 West, Salt Lake Meridian, Utah.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated May 4, 1981.

The directions of the lines of this survey were determined by reference to the true meridians established on line by hour angle observations on Polaris. They were carried forward by sustained angulation, being supplemented by numerous other observations on Polaris taken throughout the progress of the survey.

The distances along surveyed lines were determined by electronic measurement. The distances to topography on lines run by traverse due to rough terrain, timber and private property are approximately as scaled from U.S.G.S. topographic sheets.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

CHAINS	
	The geographic position of the corner of Tps. 42 and 43 S., Rs. 1 E. and 1 W. (Salt Lake Guide Meridian) is identical with U.S.G.S. triangulation station "TPS. COR T42 & 43 S., R. 1 W. and R. 1 E.; and is at Latitude 37° 06' 27.36" N., and Longitude 111° 51' 02.38" W. The mean magnetic declination is 13° 45' E.
	Dependent Resurvey of the North Boundary of T. 43 S., R. 1 W., Salt Lake Meridian, Utah
	(Restoring the 1877 Survey by J.G. Burrill and the Resurvey Executed by Thoma and Johnston in 1916) Beginning at the cor. of Tps. 42 and 43 S., Rs. 1 E. and 1 W., monumented with an iron post, 3 ins. diam., projecting 12 ins. above ground, with brass cap, mkd. as described in the official record of the 1916 resurvey of the S. bdy. of T. 42 S., R. 1 W. N. 89° 51' W., bet. secs. 1 and 36. Over broken mountainous land, through sage, shadscale, and lightly scattered juniper growth.
40.09	Point for the ¼ sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 42 S R 1 W ¼ S 36 / S 1 T 43 S R 1 W 1981 Cor. is located on a small sandy knoll.
80.18	The cor. of secs. 1, 2, 35, and 36, monumented with an iron post, 2 ins. diam., projecting 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1916 resurvey of the S. bdy. of T. 42 S., R. 1 W.
	N. 89° 41' W., bet. secs. 2 and 35. Over broken mountainous land, through sagebrush, shadscale and lightly scattered juniper growth.
36.79	The witness cor. to the ¼ sec. cor. of secs. 2 and 35, monumented with an iron post, 1 in. diam., projecting 1 ft. above ground, with brass cap, mkd. as described in the official record of the 1916 resurvey of the S. bdy. of T. 42 S., R. 1 W.
	N. 89° 36' W., beginning new measurement.
2.24	True point for the ¼ sec. cor. of secs. 2 and 35, at proportionate distance. (Same as record.)

Dependent Resurvey of the North Boundary of
T. 43 S., R. 1 W., Salt Lake Meridian, Utah

CHAINS	
33.44	Point for the original witness to the cor. of secs. 2, 3, 34, and 35, at proportionate distance; there is no remaining evidence of the original witness cor.
42.32	Point for the cor. of secs. 2, 3, 34, and 35, at proportionate distance. Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 42 S R 1 W S 34 | S 35 S 3 | S 2 T 43 S R 1 W 1981 Cor. is located on shelf, on SE slope of spur, which slopes SW.
	N. 89° 36' W., bet. secs. 3 and 34. Over broken mountainous land, through sagebrush, shadscale, and lightly scattered juniper growth.
10.00	Leave broken mountainous land, thence over rolling desert land.
40.08	The ¼ sec. cor. of secs. 3 and 34, monumented with an iron post, 1 in. diam., projecting 1 ft. above ground, with brass cap, mkd. as described in the official record of the 1916 resurvey of the S. bdy. of T. 42 S., R. 1 W.
	N. 89° 33' W., beginning new measurement.
36.15	The witness cor. to the cor. of secs. 3, 4, 33, and 34, monumented with an iron post, 2 ins. diam., projecting 15 ins. above ground, with brass cap, mkd. as described in the official record of the 1916 resurvey of the S. bdy. of T. 42 S., R. 1 W.
	N. 89° 58' W., beginning new measurement.
4.24	True point for the cor. of secs. 3, 4, 33, and 34, at proportionate distance.
	N. 89° 58' W., bet. secs. 4 and 33. Over rolling desert land, through sagebrush, shadscale, Russian olive and scattered cottonwood growth.
7.00	Paria River, course SSE.
15.00	Center line of U.S. Highway No. 89, bears NSE and SNW.
40.81	The ¼ sec. cor. of secs. 4 and 33, monumented with an iron post, 1 in. diam., projecting 1 ft. above ground, with brass cap, mkd. as described in the official record of the 1916 resurvey of the S. bdy. of T. 42 S., R. 1 W.

Dependent Resurvey of the North Boundary of
T. 43 S., R. 1 W., Salt Lake Meridian, Utah

CHAINS	
	N. 89° 16' W., beginning new measurement.
40.09	The cor. of secs. 4, 5, 32, and 33, monumented with an iron post, 2 ins. diam., projecting 20 ins. above ground, with brass cap, mkd. as described in the official record of the 1916 resurvey of the S. bdy. of T. 42 S., R. 1 W.
	(Restoring the 1877 Resurvey Executed by J.G. Burrill)
	N. 89° 41' W., bet. secs. 5 and 32.
	Over rolling desert land, through sagebrush, shadscale and lightly scattered juniper growth.
39.86	Point for the ¼ sec. cor. of secs. 5 and 32, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T 42 S R 1 W S 32 ¼ S 5 T 43 S R 1 W 1981
	Set a steel fence post, 6 ft. long, alongside the iron post.
	Cor. is located on gentle NE slope.
79.72	Point for the cor. of secs. 5, 6, 31, and 32, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 42 S R 1 W S 31 | S 32 S 6 | S 5 T 43 S R 1 W 1981
	Set a steel fence post, 6 ft. long, alongside the iron post.
	Cor. is located on nearly level land.
	N. 89° 41' W., bet. secs. 6 and 31.
	Over rolling sandy desert land, through sagebrush, shadscale and lightly scattered juniper growth.
39.86	The ¼ sec. cor. of secs. 6 and 31, monumented with a sandstone, 24 x 12 x 6 ins., firmly set 15 ins. in the ground and plainly mkd. ¼ on N face, from which the original bearing tree
	A juniper, 12 ins. diam., bears N. 10° E., 60 lks. dist., mkd. ¼ S BT.

CHAINS

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 42 S R 1 W
S 31
¼
S 6
T 43 S R 1 W
1981

Deposit the mkd. stone and set a steel fence post, 6 ft. long,. alongside the cor.

Cor. is located on sandy NW slope.

N. 89° 05' W., beginning new measurement.

18.00 Enter mountainous land.

40.01 The cor. of Tps. 42 and 43 S., Rs. 1 and 2 W., monumented with an iron post, 3 ins. diam., projecting 2 ft. above ground, with brass cap, mkd. as described in the official record of the 1917 resurvey.

(Dependent Resurvey of a Portion of the Subdivisional Lines, T. 43 S., R. 1 W., Salt Lake Meridian, Utah

---

(Restoring the 1877 Survey Executed by J.G. Burrill)

From the cor. of secs. 6 and 7, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set in a mound of stone, with brass cap, mkd. as described in the official record of the 1976 resurvey of the Salt Lake Meridian in T. 43 S., Rs. 1 E. and 1 W.

I remark the brass cap to read as follows:

T 43 S
R 1 W | R 1 E
S 1 | S 6
S 12 | S 7
1976
1981

Note: The ¼ sec. cor. of sec. 6 on the W. bdy. of T. 43 S., R. 1 E. will now function as a common ¼ sec. cor. for both sides. I added the marks S1 1981 to the brass cap.

N. 89° 44' W., bet. secs. 1 and 12.

Over mountainous land, through sagebrush, shadscale and lightly scattered juniper growth.

39.89 Point selected for the witness cor. to the ¼ sec. cor. of secs. 1 and 12.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 43 S., R. 1 W., Salt Lake Meridian, Utah

CHAINS	
	W C T 43 S R 1 W ¼ < S 1 / S 12 1981
40.19	True point for the ¼ sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original cor. The cor. point falls in wash, 30 lks. wide, 4 ft. deep, drains NW. Point unsuitable for monumentation.
80.38	The cor. of secs. 1, 2, 11, and 12, monumented with an iron post, 2 ins. diam., projecting 12 ins. above ground, with brass cap, mkd. as described in the official record of the 1917 resurvey of a portion of the subdivision.
	N. 0° 38' E., bet. secs. 1 and 2.
	Over mountainous land, through sagebrush, shadscale, and lightly scattered juniper growth.
34.50	Center line of U.S. Highway No. 89, on curve, bears NW and E.
39.83	Point for the ¼ sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base, to top of brass cap, mkd.
	T 43 S R 1 W ¼ S 2 | S 1 1981
	Cor. is located on gentle SW slope, 25 lks. dist., N of right-of-way fence, bears E and W.
79.74	The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., hereinbefore described.
	From the cor. of secs. 1, 2, 11, and 12.
	N. 89° 43' W., bet. secs. 2 and 11.
	Over broken mountainous land, through sagebrush, shadscale and very scattered juniper growth.
39.38	Point selected for the witness cor. to the ¼ sec. cor. of secs. 2 and 11.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4½ ft. base, to top of aluminum cap, mkd.
	W C T 43 S R 1 W ¼ < S 2 / S 11 1981

CHAINS	
	Cor. is located on broken W slope.
39.88	True point for the ¼ sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original cor. Cor. point falls in steep slide area. Not suitable for monumentation.
79.76	The cor. of secs. 2, 3, 10, and 11, monumented with an iron post, 2 ins. diam., projecting 14 ins. above ground with brass cap, mkd. as described in the official record of the 1917 resurvey of T. 43 S., R. 1 W.
	N. 0° 22' E., bet. secs. 2 and 3.
	Over mountainous land, through sagebrush, shadscale, and scattered juniper growth.
39.76	The ¼ sec. cor. of secs. 2 and 3, monumented with a cedar post, 4 ins. diam., 4 ft. high, firmly set 2 ft. in the ground, with faint scribe marks on W side.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 43 S R 1 W ¼ S 3 | S 2 1981
	Deposit the cedar post alongside the iron post.
	Cor. is located in rolling sand dunes, gentle NW slope.
	N. 1° 48' E., beginning new measurement.
20.00	Center line of U.S. Highway No. 89, bears SNW and NSE.
40.09	The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., hereinbefore described.
	(Restoring the 1877 Survey Executed by J.G. Burrill and the 1917 Resurvey Executed by E. Bird)
	From the cor. of secs. 2, 3, 10, and 11.
	N. 89° 20' W., bet. secs. 3 and 10.
	Over mountainous land, through sagebrush, shadscale, and scattered juniper growth.
40.19	The ¼ sec. cor. of secs. 3 and 10, monumented with an iron post, 1 in. diam., projecting 12 ins. above ground, with brass cap, mkd. as described in the official record of the 1917 resurvey.
	N. 89° 24' W., beginning new measurement.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 43 S., R. 1 W., Salt Lake Meridian, Utah

CHAINS	
1.00	Enter bottom land along the Paria River, bears NW and SE.
6.00	Paria River, 2 chs. wide, 6 ins. deep, course SE.
20.20	Point for the W 1/16 sec. cor. of secs. 3 and 10.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T 43 S R 1 W W 1/16 S 3 / S 10 1981
	Set a juniper post, 6 ft. long, alongside the cor.
	Cor. is located on nearly level bottom land, in thick tamarack growth.
38.00	Leave bottom land, bears NW and SE; over rolling sandy desert land.
40.40	The cor. of secs. 3, 4, 9, and 10, monumented with an iron post, 2 ins. diam., projecting 8 ins. above ground, with brass cap, mkd. as described in the official record of the 1917 resurvey of T. 43 S., R. 1 W.
	(Restoring the 1877 Survey Executed by J.G. Burrill)
	N. 1° 10' E., bet. secs. 3 and 4.
	Over rolling desert land, through sagebrush and shadscale.
17.00	Paria River, course SE.
19.85	Point for the S 1/16 sec. cor. of secs. 3 and 4. Not monumented.
39.70	Point for the ¼ sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.
	T 43 S R 1 W ¼ S 4 | S 3 1981
	Cor. is located on gentle W slope.
50.50	Paria River, course SW.
61.00	Paria River, course SE.
77.00	Center line of U.S. Highway No. 89, bears NSE and SNW.
79.56	True point for the cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., hereinbefore described.

CHAINS	
	(Restoring the 1877 Survey Executed by J.G. Burrill and the 1917 Resurvey Executed by Elliot Bird)
	From the cor. of secs. 3, 4, 9, and 10.
	S. 89° 13' W., bet. secs. 4 and 9.
	Over rolling desert land, through sagebrush and shadscale.
20.215	Point for the E 1/16 sec. cor. of secs. 4 and 9.
	Set an iron post, 30 ins. long, 2½ ins. diam., 13 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of brass cap, mkd.
	T 43 S R 1 W E 1/16 S 4 / S 9 1981
	Set a steel fence post, 6 ft. long, alongside the iron post.
37.935	The witness cor to the ¼ sec. cor. of secs. 4 and 9, monumented with an iron post, 1 in. diam., projecting 8 ins. above ground, with brass cap, mkd. as described in the official record of the 1917 resurvey.
	S. 89° 23' W., beginning new measurement.
2.495	True point for the ¼ sec. cor. of secs. 4 and 9, at proportionate distance falls in edge of wash where corner could not be perpetuated.
	Enter mountainous land, through scattered juniper growth.
22.17	The angle point for secs. 4 and 9, monumented with a sandstone, 18 x 10 x 6 ins., firmly set in a small mound of stone, mkd. with 4 grooves on E face, 5 notches on S edge and AP on E face.
	At the angle point
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.
	A P T 43 S R 1 W S 4 / S 9 1981
	Deposit the mkd. stone and set a steel fence post, 6 ft. long, alongside the aluminum post.
	Cor. is located at base of steep E slope.
	N. 89° 35' W., beginning new measurement.
19.895	The cor. of secs. 4, 5, 8, and 9, monumented with an iron post, 2 ins. diam., firmly set and projecting 12 ins. above ground with brass cap, mkd. as described in the official record of the 1917 resurvey.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 43 S., R. 1 W., Salt Lake Meridian, Utah

CHAINS	
	N. 0° 30' E., bet. secs. 4 and 5.
	Over mountainous land, through sagebrush, shadscale, and scattered juniper growth.
40.35	The ¼ sec. cor. of secs. 4 and 5, monumented with an iron post, 1 in. diam., firmly set and projecting 12 ins. above ground with brass cap, mkd. as described in the official record of the 1917 resurvey.
	N. 0° 29' E., beginning new measurement.
40.35	The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., hereinbefore described.
	From the cor. of secs. 4, 5, 8, and 9.
	N. 89° 51' W., bet. secs. 5 and 8.
	Over mountainous land, through sagebrush, shadscale and lightly scattered juniper growth.
39.55	The ¼ sec. cor. of secs. 5 and 8, monumented with an iron post, 1 in. diam., firmly set and projecting 16 ins. above ground, with brass cap, mkd. as described in the official record of the 1917 resurvey.
	N. 87° 28' W., beginning new measurement.
40.22	The cor. of secs. 5, 6, 7, and 8, monumented with an iron post, 2 ins. diam., firmly set and projecting 12 ins. above ground, with brass cap mkd. as described in the official record of the 1917 resurvey.
	(Restoring the Survey Executed by J.G. Burrill in 1877)
	N. 0° 31' E., bet. secs. 5 and 6.
	Over mountainous land, through sagebrush, shadscale and lightly scattered juniper growth.
39.63	The ¼ sec. cor. of secs. 5 and 6, monumented with a sandstone, 16 x 10 x 4 ins., firmly set 10 ins. in the ground and dimly mkd. ¼ on W face.
	At the corner point
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T 43 S R 1 W ¼ S 6 | S 5 1981
	Deposit the mkd. stone alongside the aluminum post.
	Cor. is located 40 lks. dist. N of small draw, drains N. 70° E.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 43 S., R. 1 W., Salt Lake Meridian, Utah

CHAINS	
	N. 0° 30' E., beginning new measurement.
39.64	The cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the Tp., hereinbefore described.

Survey of the Subdivision of Section 3,
T. 43 S., R. 1 W., Salt Lake Meridian, Utah

	From the ¼ sec. cor. of secs. 3 and 10.
	N. 1° 10' E., on the N and S center line of sec. 3.
19.855	Point for the center south 1/16 sec. cor. of sec. 3.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground, and in a collar of stone, with aluminum cap mkd.
	C S 1/16 | S 3 C 1981
	Cor. is located on top of spur, slopes SE.
39.71	Point for the center ¼ sec. cor. of sec. 3, at intersection with E and W center line.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T 43 S R 1 W C ¼ S 3 1981
	Cor. is located on nearly level land.
70.00	Center line of U.S. Highway No. 89, bears NSE and SNW.
79.67	The ¼ sec. cor. of secs. 3 and 34.
	From the ¼ sec. cor. of secs. 2 and 3.
	N. 89° 25' W., on the E and W center line of sec. 3.
39.63	The center ¼ sec. cor. of sec. 3.
59.825	Point for the center W 1/16 sec. cor. of sec. 3. Not monumented.
80.02	The ¼ sec. cor. of secs. 3 and 4.
	From the W 1/16 sec. cor. of secs. 3 and 10.
	N. 1° 10' E., on the N and S center line of the SW¼ of sec. 3.
1.00	Paria River, course E.
19.855	Point for the SW 1/16 sec. cor. of sec. 3, at intersection with the E and W center line of the SW¼.

Survey of the Subdivision of Section 3,
T. 43 S., R. 1 W., Salt Lake Meridian, Utah

CHAINS	
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 43 S R 1 W SW 1/16 S 3 1981 Set a steel fence post, 6 ft. long, alongside the aluminum post.
39.71	The point for the center west 1/16 sec. cor. of sec. 3.
	From the center south 1/16 sec. cor. of sec. 3.
	N. 89° 24' W., on the E and W center line of the SW¼ of sec. 3.
20.20	The SW 1/16 sec. cor. of sec. 3.
40.40	The Point for the S 1/16 sec. cor. of secs. 3 and 4.

Survey of the Subdivision of Section 4,
T. 43 S., R. 1 W., Salt Lake Meridian, Utah

	From the true point for the ¼ sec. cor. of secs. 4 and 9.
	N. 0° 52' E., on the N and S center line of sec. 4.
20.135	Point for the center south 1/16 sec. cor. of sec. 4, falls in wash, 10 lks. wide, 2 ft. deep, drains SE.
	From which its witness cor. bears N. 89° 39' E., 0.30 chs. dist., hereinafter described.
40.27	Point for the center ¼ sec. cor. of sec. 4, at intersection with the E and W center line.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 43 S R 1 W C ¼ S 4 1981 Set a steel fence post, 6 ft. long, alongside the aluminum post. Raise a mound of stone, 2 ft. base, 1½ ft. high, W of cor.
80.13	The ¼ sec. cor. of secs. 4 and 33.
	From the ¼ sec. cor. of secs. 3 and 4.
	N. 89° 58' W., on the E and W center line of sec. 4.
8.50	Paria River, course SW.
20.305	Point for the center east 1/16 sec. cor. of sec. 4. Not monumented.
40.61	The center ¼ sec. cor. of sec. 4.
80.43	The ¼ sec. cor. of secs. 4 and 5.

Survey of the Subdivision of Section 4,
T. 43 S., R. 1 W., Salt Lake Meridian, Utah

CHAINS	
	From the E 1/16 sec. cor. of secs. 4 and 9.
	N. 1° 04' E., on the N and S center line of the SE¼ of sec. 4.
19.99	Point for the SE 1/16 sec. cor. of sec. 4, at intersection with the E and W center line of the SE¼.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. SE 1/16 S 4 1981
	Set a steel fence post, 6 ft. long, alongside the iron post.
39.98	Point for the center E 1/16 sec. cor. of sec. 4.
	From the point for the S 1/16 sec. cor. of secs. 3 and 4.
	S. 89° 39' W., on the E and W center line of the SE¼ of sec. 4.
1.50	Paria River, course S.
20.275	The SE 1/16 sec. cor. of sec. 4.
40.215	Point selected for the witness cor. to the center south 1/16 sec. cor. of sec. 4.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. W C T 43 S R 1 W C ← S 1/16 | S 4 C 1981
	Set a steel fence post, 6 ft. long, alongside the iron post.
40.515	True point for the center south 1/16 sec. cor. of sec. 4.
	Survey of the Subdivision of Section 5, T. 43 S., R. 1 W., Salt Lake Meridian, Utah
	From the ¼ sec. cor. of secs. 5 and 8.
	N. 0° 16' E., on the N and S center line of sec. 5.
40.82	Point for the center ¼ sec. cor. of sec. 5, at intersection with the E and W center line.
	Set an iron post, 24 ins. long, 1 in. diam., 6 ins. in sand and drilled 8 ins. in solid sandstone, with brass cap mkd.

Survey of the Subdivision of Section 5,
T. 43 S., R. 1 W., Salt Lake Meridian, Utah

CHAINS	
	T 43 S R 1 W C ¼ S 5 1981
	Cor. is located on SE slope of hill.
80.82	The ¼ sec. cor. of secs. 5 and 32.
	From the ¼ sec. cor. of secs. 4 and 5.
	N. 89° 10' W., on the E and W center line of sec. 5.
39.71	The center ¼ sec. cor. of sec. 5.
79.73	The ¼ sec. cor. of secs. 5 and 6.

General Description

The area resurveyed within T. 43 S., R. 1 W., Salt Lake Meridian, varies from broken mountainous land in the NE and SW portions to bottom land along the Paria River. The elevation ranges from 4,350 to 4,700 ft. above sea level. The soil is mostly sandy clay loam, with some exposed sandstone ledges. The vegetation consists mostly of sagebrush, shadscale and scattered juniper growth.

The Paria River enters on the north boundary of section 4, flowing SE and leaving on the south boundary of section 3.

Access is by State Highway No. 89, which enters on the north boundary of section 4 and leaves on the east boundary of section 1. There are several dirt and trail roads throughout the work. The principal use is livestock grazing.

The average of a number of readings along the lines resurveyed gives a mean magnetic declination of 13° 45' E.

Form 9600-11
(August 1979)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Ferrel Reynolds	Supervisory Surveying Technician
Larry Judd	Surveying Technician
Donzil Q. Worthington	Surveying Technician
John B. Julander	Survey Aid
Gary Gogos	Surveying Technician

CERTIFICATE OF SURVEY

(I) ~~(We)~~ Gail E. Reynolds , HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 4th day of May , 19 81, (I) ~~(We)~~ have dependently resurveyed the north boundary and a portion of the subdivisional lines and surveyed a partial subdivision of sections 3, 4, and 5 of T. 43 S., R. 1 W.,

of the Salt Lake Meridian, in the State of Utah , which are represented in the foregoing field notes as having been executed by (me), (us) ~~and~~ under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

November 3, 1983
(Date)

Gail E. Reynolds
(Cadastral Surveyor)
Supervisory

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Denver, Colorado

The foregoing field notes of the dependent resurvey of the north boundary and a portion of the subdivisional lines and the survey of a partial subdivision of sections 3, 4, and 5 of T. 43 S., R. 1 W., Salt Lake Meridian, Utah

executed by Gail E. Reynolds, Supervisory Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

November 7, 1983
(Date)

Glen B Hatch
~~(Chief, Cadastral Survey Examination and Approval Staff)~~
Chief Cadastral Surveyor for Utah

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in , is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief, Cadastral Survey Examination and Approval Staff)~~
Chief Cadastral Surveyor for Utah

Vol. R606 335

Form 9600-9
(December 1979)
(formerly 9180-6)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF THE

SEVENTH STANDARD PARALLEL SOUTH,

THROUGH A PORTION OF RANGE 3 EAST,

THE WEST BOUNDARY,

A PORTION OF THE NORTH AND EAST BOUNDARIES

AND

A PORTION OF THE SUBDIVISIONAL LINES

AND

THE SURVEY OF THE SECTION LINE BETWEEN SECTIONS 30 AND 31,

AND THE SURVEY OF THE SUBDIVISION

OF

SECTIONS 5, 6, 7, 9, 18, 19, 22, 27, 29, 30, 33, AND 35

OF

TOWNSHIP 35 SOUTH, RANGE 3 EAST

Of the Salt Lake Meridian,

In the State of Utah.

EXECUTED BY

Gail E. Reynolds Supervisory Cadastral Surveyor

Under special instructions dated August 29, 1980, approved August 29, 1980,

_____, which provided for the surveys included under U.S. Survey/Group Number 603, and assignment instructions dated September 23, 1980.

Survey commenced September 23, 1980

Survey completed June 2, 1983

INDEX DIAGRAM

Township 35 South, Range 3 East,

18 17 **6** 44 44	18 **5** 36 43	**4** 35	**3**	**2**	**1**
15 **7** 43 42	**8** 34	**9** 31 33	**10**	**11**	**12**
14 **18** 41 41	**17**	**16** 30	**15** 30	**14**	**13** 10
13 **19** 40 39	**20** 39	**21** 29	**22** 25 28	**23** 24	**24** 9 21
12 **30** 38 37	**29** 33 36	**28** 27 33	**27** 23 26	**26** 20 22	**25** 8 19
11 **31** 5	**32** 32	**33** 26 5	**34** 22 4	**35** 18 3	**36** 7 2

Subdivision of Section 5 - Page 45
Subdivision of Section 6 - Page 46
Subdivision of Section 7 - Page 46
Subdivision of Section 9 - Page 48
Subdivision of Section 18 - Page 49
Subdivision of Section 19 - Page 50
Subdivision of Section 22 - Page 52
Subdivision of Section 27 - Page 53
Subdivision of Section 29 - Page 56
Subdivision of Section 30 - Page 57
Subdivision of Section 33 - Page 58
Subdivision of Section 35 - Page 59

GPO 855-927

Township 35 South, Range 3 East, Salt Lake Meridian, Utah

CHAINS

The following field notes are those of a dependent resurvey of the Seventh Standard Parallel South through a portion of Range 3 East, the west boundary, a portion of the north and east boundaries and a portion of the subdivisional lines and the survey of the section line between sections 30 and 31, and the survey of the subdivision of sections 5, 6, 7, 9, 18, 19, 22, 27, 29, 30, 33, and 35 of Township 35 South, Range 3 East, Salt Lake Meridian, Utah.

T. 35 S., R. 3 E.

	Surveyed by		Retr. or Resurveyed by	
SOUTH BOUNDARY				
All	Wm. Lewman	1893		
Portion			Thoma and Bunbury	1913
Portion			Rigby and Smith	1922
Portion			G.D. Voorhees, et al	1959
WEST BOUNDARY				
All	Wm. Lewman	1893		
EAST BOUNDARY				
All	Wm. Lewman	1893		
N. 2 miles			G.D. Voorhees, et al	1959
NORTH BOUNDARY				
All	Wm. Lewman	1893		
All			G.D. Voorhees, et al	1959
SUBDIVISIONAL LINES				
Portion	Wm. Lewman	1893		
Portion	G.D. Voorhees	1959		

The cor. of sections 7, 12, 13, and 18, on the W. bdy. and the 1/4 section cor. of sections 7 and 18 were remonmented on September 11, 1964 by persons unknown.

The surveys were executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated August 29, 1980.

The direction of the lines of this survey were determined by reference to true meridians established on line by direct observations on Polaris. The lines were carried forward by sustained angulation being supplemented by other observations on Polaris taken throughout the progress of the survey.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Township 35 South, Range 3 East, Salt Lake Meridian, Utah

CHAINS	
	The geographic position of the southeast corner of the township as determined from a tie made to U.S.G.S. triangulation station "ESCALANTE RIM", located in section 31, is: Latitude 37° 42' 49.70" N. Longitude 111° 30' 48.34" W. The mean magnetic declination is 14° E.
	Dependent Resurvey of the Seventh Standard Parallel South Through a Portion of Range 3 East, Salt Lake Meridian, Utah
	(Reestablishment of the Survey Executed by Wm. Lewman, Deputy Surveyor in 1893 and the Retracement Executed by Thoma and Bunbury, Deputy Surveyors in 1913)
	Beginning at the standard cor. of Tps. 35 S., Rs. 3 and 4 East, monumented with a limestone, 26 x 6 x 5 ins., firmly set 24 ins. in the ground and plainly mkd. 6 notches on E, W and N edges. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. S C T 35 S R 3 E R 4 E S 36 | S 31 1980 Deposit the mkd. stone alongside the iron post. S. 89° 35' W., on the S. bdy. of sec. 36. Over rolling desert land, through pinon and cedar.
8.15	Improved gravel road, bears S. 28° E. and N. 28° W.
17.48	The closing cor. of Tps. 36 S., Rs. 3 and 4 E., monumented with an iron post, 2 ins. diam., with brass cap, mkd. as described in the official record of the 1913 resurvey, bears North, 8 lks. dist.
44.32	Point for the standard ¼ sec. cor. of sec. 36, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. S C T 35 S R 3 E ¼ S 36 1981
88.64	The standard cor. of secs. 35 and 36, monumented with a limestone, 20 x 14 x 4 ins., firmly set 10 ins. in the ground and plainly mkd. 1 notch on E edge and 5 notches on W edge, from which the 1893 bearing tree

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	A juniper, 10 ins. diam., bears N. 40° E., 44 lks. dist., mkd. T35S R3E S36 BT. (Record, N. 39° E.) At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. S C T 35 S R 3 E S 35 | S 36 1980 Deposit the mkd. stone alongside the iron post.
	S. 89° 47' W., on the S. bdy. of sec. 35.
8.84	The closing cor. of secs. 1 and 2, T. 36 S., R. 3 E., monumented with an iron post, 2 ins. diam., with brass cap, mkd. as described in the official record of the 1913 resurvey.
20.00	Point for the standard E 1/16 sec. cor. of sec. 35. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. S C T 35 S R 3 E E 1/16 S 35 1980
40.00	The standard cor. of sec. 35, monumented with a sandstone, 20 x 10 x 5 ins., firmly set 10 ins. in the ground, and plainly mkd. ¼ on N face. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. S C T 35 S R 3 E ¼ S 35 1980 Deposit the mkd. stone alongside the iron post.
	S. 89° 39' W., beginning new measurement.
18.95	Alvey Wash, 1.00 ch. wide, 1 ft. deep, with small stream of water, drains S.
20.15	Point for the standard W 1/16 sec. cor. of sec. 35. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. S C T 35 S R 3 E W 1/16 S 35 1980

CHAINS	
	Set a 6 ft. cedar post alongside the iron post. Cor. is located in four strand barbwire fence line, bears E and W.
40.30	The standard cor. of secs. 34 and 35, determined at the cor. of fences, which is a steel pipe, 3½ ins. diam., firmly set in concrete, extending 4 ft. above the ground, from which fences bear N, E, and W. This position is accepted as the best available evidence of the original corner position. Set an iron post, 30 ins. long, 2½ ins. diam., wired alongside the steal pipe, with brass cap mkd. S C T 35 S R 3 E S 34 | S 35 1980 Cor. is located in cultivated land.
	S. 89° 30' W., along the S. bdy. of sec. 34. Over cultivated land.
8.32	The closing cor. of secs. 2 and 3, T. 36 S., R. 3 E., monumented with an iron post, 2 ins. diam., firmly set, with brass cap mkd. as described in the official record of the 1913 resurvey, bears South, 5 lks. dist.
32.00	The standard ¼ sec. cor. of sec. 34, determined at the cor. of fences, which is a steel pipe, 4 ins. diam., firmly set in concrete, extending 4 ft. above the ground, from which fences bear N, E and W. This position is accepted as the best available evidence of the original corner position. At the corner point Set an aluminum post, 30 ins. long, 2½ ins. diam., inside steel pipe, with aluminum cap, mkd. S C T 35 S R 3 E ¼ S 34 1981 Cor. is located in cultivated land.
	S. 89° 37' W., beginning new measurement.
19.28	Point for the standard W 1/16 sec. cor. of sec. 34. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. S C T 35 S R 3 E W 1/16 S 34 1980 Cor. is located in netwire fence cor., bears N, E and W.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
38.56	Point for the standard cor. of secs. 33 and 34, at proportionate distance based on the irregular boundary method; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. S C T 35 S R 3 E S 33 | S 34 1980 Cor. is located in gently rolling desert land.
	S. 89° 28' W., along the S. bdy. of sec. 33. Over rolling desert land.
17.41	The closing cor. of secs. 3 and 4, T. 36 S., R. 3 E., monumented with an iron post, 2 ins. diam., firmly set, with brass cap mkd. as described in the official record of the 1913 resurvey, bears South, 2 lks. dist.
39.98	The standard ¼ sec. cor. of sec. 33, monumented with an iron post, 2½ ins. diam., extending 8 ins. out of the ground, with brass cap, mkd. as described in the official record of the 1959 resurvey. Cor. is located on gently rolling desert land.
	(Reestablishment of the Survey Executed by Wm. Lewman, Deputy Surveyor in 1893, the Retracement Executed by Thoma and Bunbury, Deputy Surveyors in 1913, and the Dependent Resurvey Executed by G.D. Voorhees, Cadastral Surveyor in 1959)
	S. 89° 39' W., beginning new measurement.
40.06	The point for the standard cor. of secs. 32 and 33, as determined latitudinally by fences projecting from the east and west and longitudinally at record distance (40 lks.) west of four strand barbwire fence cor., bears N and W. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. S C T 35 S R 3 E S 32 | S 33 1980 Set a 6 ft. steel fence post alongside the aluminum post. Cor. is located on W edge of improved gravel road, bears N and S.
	From the witness cor. to the closing cor. of secs. 31 and 32, on the south boundary of the Tp., monumented with an iron post, 2½ ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the official record of the 1959 resurvey.

CHAINS	
	S. 89° 46' W., along the S. bdy. of sec. 31.
8.38	The closing cor. of secs. 5 and 6, T. 36 S., R. 3 E., monumented with an iron post, 2 ins. in diam., projecting 8 ins. above the ground, with brass cap, mkd. as described in the official record of the 1922 survey.
32.09	True point for the standard ¼ sec. cor. of sec. 31, falls on a ledge where a cor. cannot be perpetuated.
32.26	Point selected for the witness cor. to the standard ¼ sec. cor. of sec. 31. Set an aluminum post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd. W S C T 35 S R 3 E ¼ S 31 1983
32.79	The ¼ sec. cor. set by Rigby and Smith, monumented with an iron post, 1 in. diam., projecting 6 ins. above ground, with brass cap mkd. as described in the official record of the 1922 survey. The marks were changed to read A P S C S 31 S 6 1922 1983
	S. 89° 36' W., beginning new measurement.
37.60	The closing cor. of Tps. 36 S., Rs. 2 and 3 E., monumented with an iron post, 3 ins. diam., projecting 18 ins. above the ground, and in a mound of stone, with brass cap mkd. as described in the official record of the 1922 survey of the E. bdy. of T. 36 S., R. 2 E.
39.34	The standard cor. of Tps. 35 S., Rs. 2 and 3 E., monumented with a sandstone, 33 x 16 x 14 ins. firmly set in a mound of stone and plainly mkd. 6 grooves and SC T35S on N face, R3E on E face, T36S and 6 grooves on S face and R2E with 6 grooves on W face, from which original bearing tree and bearing object A cross on ledge, 20 ft. high, bears N. 39° W., 11 lks. dist., mkd. WTP X cor. A juniper, 17 ins. diam., bears S. 88° E., 28 lks. dist., mkd. SC T35S R2 and 3 E BT. At the corner point Set an aluminum post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock, over a cross (X) and in a mound of stone, 5 ft. base, to top of aluminum cap, mkd.

☆U.S. Government Printing Office: 1980—778-251/292

Dependent Resurvey of the Seventh Standard Parallel South
Through a Portion of Range 3 East,
Salt Lake Meridian, Utah

CHAINS	
	S C T 35 S R 2 E R 3 E S 36 | S 31 S 1 T 36 S 1980 Deposit the mkd. stone alongside the aluminum post.
	Dependent Resurvey of a Portion of the East Boundary, T. 35 S., R. 3 E., Salt Lake Meridian, Utah
	(Reestablishment of the Survey Executed by Wm. Lewman, Deputy Surveyor in 1893)
	From the standard cor. of Tps. 35 S., Rs. 3 and 4 E. N. 0° 04' E., bet. secs. 31 and 36. Over rolling desert land, through pinon and juniper trees.
39.78	The ¼ sec. cor. of secs. 31 and 36, monumented with a limestone, 24 x 10 x 3 ins., loosely set and plainly mkd. ¼ on W face, from which the original bearing trees A juniper, 12 ins. diam., bears S. 58° E., 43 lks. dist., mkd. ¼ S BT. A juniper, 20 ins. diam., bears N. 53° W., 53 lks. dist., mkd. ¼ S BT. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd. T 35 S R 3 E R 4 E ¼ S 36 | S 31 1980 Deposit the mkd. stone alongside the iron post.
	N. 0° 15' W., beginning new measurement.
40.20	The cor. of secs. 25, 30, 31, and 36, monumented with a limestone, 22 x 9 x 3 ins., firmly set 12 ins. in the ground and plainly mkd. 5 notches on N and 1 notch on S edges. From which the original bearing trees A juniper, 17 ins. diam., bears N. 49° E., 50 lks. dist., mkd. T35S R4E S30 BT. (Record, 47 lks. dist.) A juniper, 8 ins. diam., bears S. 4° E., 23½ lks. dist., mkd. T35S R3E S31 BT. (Record, pinon, 20 lks. dist.)

CHAINS

A juniper, 8 ins. diam., bears S. 72° W., 34 lks. dist., mkd. T35S R3E S36 BT. (Record, 37½ lks. dist.)

A juniper, 8 ins. diam., bears N. 77° W., 41 lks. dist., mkd. T35S R3E S25 BT. (Record, 46 lks. dist.)

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 35 S
R 3 E | R 4 E
S 25 | S 30
S 36 | S 31
1980

Deposit the mkd. stone alongside the iron post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

N. 0° 10' E., bet. secs. 25 and 30.

Over rolling desert land, through pinon and juniper.

39.66 The ¼ sec. cor. of secs. 25 and 30, monumented with a limestone, 24 x 7 x 3 ins., firmly set 12 ins. in the ground and plainly mkd. ¼ on W face, from which the original bearing tree

A juniper, 10 ins. diam., bears N. 1° E., 39 lks. dist., mkd. BT. (Record, N. 10° W., 37 lks. dist.)

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 35 S
R 3 E | R 4 E
¼
S 25 | S 30
1980

Deposit the mkd. stone alongside the iron post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

N. 0° 03' W., beginning new measurement.

39.96 The cor. of secs. 19, 24, 25, and 30, monumented with a limestone, 18 x 8 x 4 ins., firmly set 10 ins. in the ground and plainly mkd. 4 grooves on N face and 2 grooves on S faces, from which the original bearing trees

A juniper, 9 ins. diam., bears N. 19° E., 43 lks. dist., mkd. with a healed blaze. (Record, 39 lks. dist.)

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS

A juniper, 15 ins. diam., bears S. 64° E., 25 lks. dist., mkd. T35S R4E S30 BT. (Record, 24 lks. dist.)

A juniper, 14 ins. diam., bears S. 63° W., 99 lks. dist., mkd. T35S R3E S25 BT. (Record, 100 lks. dist.)

A juniper, 10 ins. diam., bears N. 21° W., 107½ lks. dist., mkd. T35S R3E S24 BT. (Record, 104 lks. dist.)

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 35 S
R 3 E | R 4 E
S 24 | S 19
S 25 | S 30
1980

Deposit the mkd. stone alongside the iron post.

N. 0° 18' W., bet. secs. 19 and 24.

Over rolling desert land, through pinon and juniper.

40.02 The ¼ sec. cor. of secs. 19 and 24, monumented with a limestone, 18 x 5 x 3 ins., firmly set 10 ins. in the ground and plainly mkd. ¼ on W face, from which the original bearing trees

A pinon, 16 ins. diam., bears N. 45° E., 53 lks. dist., mkd. ¼ S BT. (Record, 51 lks. dist.)

A juniper, 6 ins. diam., bears S. 58° W., 38 lks. dist., mkd. ¼ S BT.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 35 S
R 3 E | R 4 E
¼
S 24 | S 19
1980

Deposit the mkd. stone alongside the iron post.

Set a steel fence post, 6 ft. long, alongside the iron post.

N. 0° 03' E., beginning new measurement.

35.39 Power line, bears S. 57° 15' E. and N. 57° 15' W.

Dependent Resurvey of a Portion of the East Boundary,
T. 35 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
40.01	The cor. of secs. 13, 18, 19, and 24, monumented with a limestone, 18 x 10 x 4 ins., firmly set 10 ins. in the ground and plainly mkd. 3 grooves on N and S faces, from which the original bearing trees A juniper, 12 ins. diam., bears N. 76° E., 91 lks. dist., mkd. T35S R4E S18 BT. (Record, 90 lks. dist.) A pinon, 12 ins. diam., bears S. 52° E., 65 lks. dist., mkd. T35S R4E S19 BT. (Record, 63 lks. dist.) A pinon, 12 ins. diam., bears S. 47° W., 20 lks. dist., mkd. T35S R3E S24 BT. (Record, 19 lks. dist.) A juniper, 10 ins. diam., bears N. 32° W., 85 lks. dist., mkd. T35S R3E S13 BT. (Record, 84 lks. dist.) At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 35 S R 3 E | R 4 E S 13 | S 18 S 24 | S 19 1980 Deposit the mkd. stone alongside the iron post. Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor. Set a steel post, 6 ft. long, alongside the iron post.
	North, bet. secs. 13 and 18. Over rolling desert land, through pinon and juniper trees.
40.00	The ¼ sec. cor. of secs. 13 and 18, monumented with a sandstone, 20 x 12 x 3 ins., firmly set 10 ins. in the ground and plainly mkd. ¼ on W face, from which the original bearing trees A juniper, 7 ins. diam., bears S. 84° E., 39 lks. dist., mkd. ¼ S BT. (Record, 41 lks. dist.) A juniper, 7 ins. diam., bears N. 17° W., 15 lks. dist., mkd. ¼ S BT. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a collar of stone, with brass cap mkd. T 35 S R 3 E | R 4 E ¼ S 13 | S 18 1980

Dependent Resurvey of a Portion of the East Boundary,
T. 35 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
	Deposit the mkd. stone alongside the iron post.
	N. 0° 01' W., beginning new measurement.
39.60	The cor. of secs. 7, 12, 13, and 18, monumented with an iron post, 2½ ins. diam., firmly set, with brass cap, mkd. as described in the official record of the 1959 independent resurvey.

Dependent Resurvey of the West Boundary,
T. 35 S., R. 3 E., Salt Lake Meridian, Utah

(Reestablishment of the Survey Executed by
Wm. Lewman, Deputy Surveyor in 1893)

CHAINS	
	From the standard cor. of Tps. 35 S., Rs. 2 and 3 E., hereinbefore described.
	N. 1° 44' W., bet. secs. 31 and 36.
	Over broken mountainous land, through juniper and pinon trees.
40.94	Point for the ¼ sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 18 ins. long, 1 in. diam., drilled 8 ins. in solid sandstone, with brass cap mkd.

T 35 S
R 2 E R 3 E
¼
S 36 | S 31
1981

CHAINS	
	Cor. is located on W slope near top of spur, slopes SW on sandstone boulder, 12 ft. high, 20 ft. wide and 40 ft. long.
80.70	Point for the closing cor. for secs. 30 and 31, hereinafter described.
81.88	The cor. of secs. 25, 30, 31, and 36, monumented with a sandstone, 24 x 16 x 10 ins., firmly set in a mound of stone and plainly mkd. 5 grooves on N and 1 groove on S faces. This cor. will now function for the cor. of secs. 25 and 36 only, T. 35 S., R. 2 E. From which the original bearing tree
	A pinon, 14 ins. diam., bears S. 89° E., 36 lks. dist., mkd. T35S R3E S31 BT. (Record, S. 75° E.)
	At the corner point
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

CHAINS

T 35 S
R 2 E | R 3 E
S 25 / S 36 | S 30
1981

Cor. is located on SW slope, between two sandstone boulders. Boulder to N, 10 x 10 x 8 ft., the one to S, 8 x 6 x 6 ft.

N. 4° 28' E., bet. secs. 25 and 30.

Over broken mountainous land, through pinon and juniper.

37.86 The ¼ sec. cor. of secs. 25 and 30, monumented with a sandstone, 24 x 14 x 5 ins., firmly set, 12 ins. in the ground and plainly mkd. ¼ on W face. This cor. will now function for the ¼ sec. cor. of sec. 25 only, T. 35 S., R. 2 W. From which the original bearing trees

A pinon, 10 ins. diam., bears N. 15° E., 20 lks. dist., mkd. ¼ S BT.

A juniper, 14 ins. diam., bears S. 10° W., 6 lks. dist., mkd. ¼ S BT.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 35 S
R 2 E | R 3 E
¼ |
S 25 |
1980

Deposit the mkd. stone alongside the aluminum post.

Cor. is located on N slope in scattered pinon and juniper.

N. 0° 18' E., beginning new measurement.

0.78 Point for the ¼ sec. cor. of sec. 30 only, at 40.00 chs. of southing from the true cor. point of secs. 19, 24, 25, and 30.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 35 S
R 2 E | R 3 E
| ¼
| S 30
1981

Cor. is located on N slope in pinon and juniper growth.

38.28 Point selected for the witness cor. to the cor. for secs. 19, 24, 25 and 30.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

W C
T 35 S
R 2 E | R 3 E
S 24 | S 19
S 25 | S 30
1980

Cor. is located on S bank of Alvey Wash, drains E.

40.78 True point for the cor. of secs. 19, 24, 25, and 30, at proportionate distance; falls in Alvey Wash and is unsuitable for monumentation; there is no remaining evidence of the original corner.

N. 0° 18' E., bet. secs. 19 and 24.

Over rolling desert land, through scattered juniper and pinon growth.

20.39 Point for the S 1/16 sec. cor. of secs. 19 and 24.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 35 S
R 2 E R 3 E
S 1/16
S 24 | S 19
1980

Set 6 ft. steel fence post alongside the iron post.

Cor. is located in open pasture land.

40.78 The ¼ sec. cor. of secs. 19 and 24, monumented with a sandstone, 18 x 14 x 6 ins., firmly set 10 ins. in the ground and dimly mkd. ¼ on W face.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 35 S
R 2 E R 3 E
¼
S 24 | S 19
1980

Deposit the mkd. stone alongside the aluminum post.

Cor. is located on gentle E slope in scattered pinon growth.

CHAINS	
	N. 1° 10' E., beginning new measurement.
19.955	Point for the N 1/16 sec. cor. of secs. 19 and 24. Set an aluminum post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd. T 35 S R 2 E R 3 E N 1/16 S 24 | S 19 1980 from which A 1 in. aluminum cap, extending 4 ins. out of the ground, mkd. Surveying Asso. N 1/16 secs. 19 and 24, bears N. 74° 09' W., 71 lks. dist. This cor. was established using improper procedures and is not utilized in the course of this survey. Cor. is located in shallow drainage, drains S in scattered pinon growth.
39.91	The cor. of secs. 13, 18, 19, and 24, monumented with a sandstone, 20 x 10 x 6 ins., firmly set 10 ins. in the ground and plainly mkd. 3 notches on N and S edges, from which the original bearing trees A juniper, 14 ins. diam., bears N. 80° 48' E., 70 lks. dist., mkd. T35S R3E S18 BT. (Recoard, N. 80° E., 71 lks.) A pinon, 16 ins. diam., bears S. 48° 41' E., 167½ lks. dist., mkd. T35S R3E S19 BT. (Record, S. 49½° E., 146 lks. dist.) A pinon, 15 ins. diam., bears S. 40° 31' E., 323 lks. dist., mkd. T35S R2E S24 BT. (Record, S. 1½° W., 268 lks. dist.) A juniper, 10 ins. diam., bears N. 15° W., 3 lks. dist., mkd. T35S R2E S13 BT. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground to bedrock, and in a collar of stone, with brass cap mkd. T 35 S R 2 E R 3 E S 13 | S 18 S 24 | S 19 1980 Deposit the mkd. stone alongside the iron post. Cor. is located on gently rolling land in juniper and pinon growth.
	N. 0° 46' W., bet. secs. 13 and 18. Over rolling desert land, through pinon and juniper trees.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
39.92	The ¼ sec. cor. of secs. 13 and 18, monumented with a sandstone, 30 x 8 x 5 ins., firmly set 14 ins. in the ground and plainly mkd. ¼ on W face, from which the original bearing trees A juniper, 10 ins. diam., bears S. 10½° E., 56 lks. dist., mkd. ¼ S BT. A juniper, 12 ins. diam., bears S. 28° W., 44½ lks. dist., mkd. ¼ S BT. (Record, 43½ lks. dist.) At the corner point Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 35 S R 2 E R 3 E ¼ S 13 | S 18 1980 Deposit the mkd. stone alongside the aluminum post. Cor. is located on gently rolling land in scattered pinon and juniper growth.
	N. 0° 21' E., beginning new measurement. Over rolling desert land, through pinon and juniper growth.
39.97	The cor. of secs. 7, 12, 13, and 18, monumented with an iron post, 2½ ins. diam., firmly set and extending 6 ins. above the ground, with brass cap, mkd. as described in the official record Book No. A-238, page 248, shown as being remonumented on September 11, 1964.
	N. 0° 10' E., bet. secs. 7 and 12. Over broken desert land, through pinon and juniper growth.
20.29	The S 1/16 sec. cor. of secs. 7 and 12, monumented with an aluminum pipe, 1/2 in. diam., firmly set in the ground, with aluminum cap, mkd. State Park Boundary S 1/16 S7, S12, and is accepted as a careful and faithful determination of the position of the corner. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd. T 35 S R 2 E R 3 E S 1/16 S 12 | S 7 1980

CHAINS	
	Deposit the state park marker alongside the iron post.
	N. 0° 10' E., beginning new measurement.
20.29	The ¼ sec. cor. of secs. 7 and 12, as determined from U.S. Forest Service reference monuments, from which A 2 in. aluminum post, extending 4 ins. out of the ground, with cap, mkd. RM 100 ft. with an arrow pointing NE, bears S. 56° 35' W., 151.5 lks. dist. A 2 in. aluminum post, extending 4 ins. out of the ground, with cap, mkd. RM 100 ft. with an arrow pointing SE, bears N. 47° 10' W., 151.5 lks. dist. This point is accepted as a careful and faithful determination of the position of the corner. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 35 S R 2 E R 3 E ¼ S 12 | S 7 1981 Set 6 ft. steel fence post alongside the iron post. Cor. is located in cultivated land.
	N. 0° 10' E., beginning new measurement. Over cultivated land.
20.29	Point for the N 1/16 sec. cor. of secs. 7 and 12. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 35 S R 2 E R 3 E N 1/16 S 12 | S 7 1980 Set 6 ft. cedar post alongside the iron post. Cor. is located on gentle S slope in native grasses.
40.58	The cor. of secs. 1, 6, 7, and 12, monumented with a U.S. Forest Service aluminum post, 2½ ins. diam., set in a mound of stone, 3 ft. base, 1 ft. high and is accepted as a careful and faithful determination of the position of the cor, from which the original bearing trees A juniper, 16 ins. diam., bears N. 50° E., 20 lks. dist., mkd. T35S R3E S6 BT. (Record, N. 78½° E.)

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS

A pinon, 14 ins. diam., bears S. 42½° E., 56 lks. dist., mkd. T35S R3E S7 BT.

A pinon, 10 ins. diam., bears S. 77° W., 29 lks. dist., mkd. T35S R2E S12 Bt.

A pinon, 12 ins. diam., bears N. 53° W., 17 lks. dist., mkd. T35S R3E S1 BT.

Aluminum cap mkd.

T 35 S
R2E S 1 | S 6 R3E
S 12 | S 7
LS 4266 UT
1979

Cor. is located on S slope in juniper and pinon growth.

N. 0° 12' E., bet. secs. 1 and 6.

Over broken desert land, through pinon and juniper growth.

39.03 Point for the ¼ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 5 ft. base, to top of aluminum cap, mkd.

T 35 S
R 2 E R 3 E
¼
S 1 | S 6
1980

from which

A pinon, 5 ins. diam., bears N. 5° W., 24 lks. dist., mkd. X BT.

Cor. is located on gentle N slope in pinon and juniper growth.

78.06 The cor. of Tps. 34 and 35 S., Rs. 2 and 3 E., monumented with an iron post, 2½ ins. diam., extending 18 ins. out of the ground, firmly set with brass cap, mkd. as described in the official record of the 1959 dependent resurvey of the N. bdy. of T. 35 S., R. 3 E.

Dependent Resurvey of a Portion of the North Boundary,
T. 35 S., R. 3 E., Salt Lake Meridian, Utah

(Reestablishment of the Survey Executed by Wm. Lewman, Deputy Surveyor in 1893 and the Dependent Resurvey Executed by G.D. Voorhees, Cadastral Surveyor in 1959)

Dependent Resurvey of a Portion of the North Boundary, T. 35 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
	From the cor. of secs. 4 and 5, on the N. bdy. of T. 35 S., R. 3 E., monumented with an iron post, 2½ ins. diam., extending 18 ins. above the ground, firmly set with brass cap, mkd. as described in the official record of the 1959 dependent resurvey.
	S. 88° 49' W., on the N. bdy. of sec. 5.
	Over broken mountainous land, through pinon and juniper growth.
41.18	The ¼ sec. cor. of sec. 5 only, monumented with an iron post, 1 in. diam., buried 12 ins. in the ground, with brass cap, mkd. and referenced as described in the official record of the field notes of the 1959 dependent resurvey.
	N. 88° 46' W., beginning new measurement.
39.74	The cor. of secs. 5 and 6, monumented with an iron post, 2½ ins. diam., extending 20 ins. above the ground, and in a mound of stone, firmly set, with brass cap, mkd. as described in the official record of the field notes of the 1959 dependent resurvey.
	N. 89° 35' W., along the N. bdy. of sec. 6.
	Over mountainous land, through pinon and juniper growth.
39.96	The ¼ sec. cor. of sec. 6 only, monumented with an iron post, 2½ ins. diam., firmly set in a mound of stone, with brass cap, mkd. as described in the official record of the 1959 dependent resurvey.
	S. 89° 54' W., beginning new measurement.
39.84	The cor. of Tps. 34 and 35 S., Rs. 2 and 3 E., hereinbefore described.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 35 S., R. 3 E., Salt Lake Meridian, Utah

(Reestablishment of the Survey Executed by Wm. Lewman, Deputy Surveyor in 1893)

	From the cor. of secs. 35 and 36, on the S. bdy. of the Tp., hereinbefore described.
	N. 12° 25' E., bet. secs. 35 and 36.
	Over rolling desert land, through sagebrush, native grasses and widely scattered pinon and juniper growth.
40.25	The ¼ sec. cor. of secs. 35 and 36, monumented with a limestone, 33 x 10 x 3 ins., firmly set 10 ins. in the ground and dimly mkd. ¼ on W face, from which the original bearing trees

☆U.S. Government Printing Office: 1980—778-251/292

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 35 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS

A juniper stump, bears N. 17° E., 113 lks. dist. (Record, 110½ lks. dist.)

A fallen pinon, 18 ins. diam., bears S. 59° W., 91 lks. dist.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 35 S R 3 E
¼
S 35 | S 36
1980

Deposit the mkd. stone alongside the aluminum post.

Cor. is located on gentle S slope.

N. 0° 23' E., beginning new measurement.

41.00 The cor. of secs. 25, 26, 35, and 36, monumented with a sandstone, 24 x 10 x 3 ins., firmly set 12 ins. in the ground and plainly mkd. 1 groove on E and S face, from which the original bearing trees

A juniper, 14 ins. diam., bears N. 80° E., 63 lks. dist., mkd. T35S R3E S25 BT. (Record, 60 lks. dist.)

A juniper, 10 ins. diam., bears S. 42° W., 22½ lks. dist., mkd. T35S R3E S35 BT. (Record, 21½ lks. dist.)

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 35 S R 3 E
S 26 | S 25
S 35 | S 36
1980

Deposit the mkd. stone alongside the iron post.

Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor.

Cor. is located on gentle S slope in pinon and juniper growth.

From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., hereinbefore described.

S. 89° 47' W., bet. secs. 25 and 36.

Over rolling desert land, through pinon and juniper growth.

CHAINS	
40.23	The ¼ sec. cor. of secs. 25 and 36, monumented with a mound of stone; no marked stone found. From which the original bearing trees A pinon, 10 ins. diam., bears N. 35° E., 30 lks. dist., mkd. ¼ S BT. A fallen and badly decayed pinon, 14 ins. diam., bears approximately S. 45° W., 43 lks. dist. No evidence of stump hole. This bearing tree was not used to establish the ¼ sec. cor. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 4½ ft. base to top of brass cap, mkd. T 35 S R 3 E ¼ S 25 / S 36 1980 Cor. is located on rolling S slope in pinon and juniper growth. S. 89° 46' W., beginning new measurement.
39.35	The cor. of secs. 25, 26, 35, and 36.
	N. 0° 02' E., bet. secs. 25 and 26. Over rolling desert land, through pinon and juniper growth.
39.83	The ¼ sec. cor. of secs. 25 and 26, monumented with a limestone, 20 x 6 x 6 ins., firmly set 10 ins. in the ground and plainly mkd. ¼ on W face, from which the original bearing trees A pinon, 3 ins. diam., bears S. 60° E., 27 lks. dist., mkd. ¼ BT. A pinon, 12 ins. diam., bears N. 14° W., 35 lks. dist., mkd. ¼ S BT. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd. T 35 S R 3 E ¼ S 26 | S 25 1980 Deposit the mkd. stone alongside the iron post. Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor. Cor. is located on general S slope in pinon and juniper growth.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	N. 0° 02' E., beginning new measurement.
39.62	The cor. of secs. 23, 24, 25, and 26, monumented with a limestone, 14 x 8 x 6 ins., firmly set 8 ins. in the ground and plainly mkd. 1 groove on E face and 2 grooves on S face, from which the original bearing trees A pinon, 12 ins. diam., bears N. 86° E., 35½ lks. dist., mkd. T35S R3E S24 BT. A pine, 14 ins. diam., bears S. 47° E., 30 lks. dist., mkd. T35S R3E S25 BT. A pinon, 12 ins. diam., bears S. 46° W., 41 lks. dist., mkd. T35S R3E S26 BT. A pinon, 14 ins. diam., bears N. 51° W., 45½ lks. dist., mkd. T35S R3E S23 BT. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base, to top of brass cap, mkd. T 35 S R 3 E S 23 | S 24 S 26 | S 25 1980 Deposit the mkd. stone alongside the iron post. Cor. is located on SW slope in pinon and juniper growth.
	From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., hereinbefore described. S. 89° 39' W., bet. secs. 24 and 25. Over rolling and broken desert land, through pinon and juniper growth.
39.83	Point for the ¼ sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4½ ft. base, to top of aluminum cap, mkd. T 35 S R 3 E ¼ S 24 S 25 1980 Cor. is located between sandstone ledge and boulder, 4 ft. high, on gentle SE slope.
79.66	The cor. of secs. 23, 24, 25, and 26.

CHAINS

From the standard cor. of secs. 34 and 35, on the S. bdy. of the Tp., hereinbefore described.

N. 12° 47' E., bet. secs. 34 and 35.

Over rolling farm land.

41.39 The ¼ sec. cor. of secs. 34 and 35, monumented with a limestone, 14 x 8 x 4 ins., firmly set 8 ins. in the ground and plainly mkd. ¼ on W face.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 35 S R 3 E
¼
S 34 | S 35
1980

Deposit the mkd. stone alongside the aluminum post.

Cor. is located in 5 strand barbwire fence cor., bears N, S and W.

N. 0° 18' E., beginning new measurement.

39.92 Point for the cor. of secs. 26, 27, 34, and 35, at proportionate distance; there is no remaining evidence of the original corner position.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 35 S R 3 E
S 27 | S 26
S 34 | S 35
1980

Set 6 ft. cedar post alongside the aluminum post.

Cor. is located 17 lks. N and 24 lks. E of 5 strand barbwire fence cor., bears E, W and S.

From the cor. of secs. 25, 26, 35, and 36.

N. 89° 49' W., bet. secs. 26 and 35.

Over rolling desert land, through sagebrush and scattered pinon and juniper growth.

40.00 The ¼ sec. cor. of secs. 26 and 35, as determined from original bearing trees

A pinon, 12 ins. diam., bears S. 23° E., 26 lks. dist., mkd. ¼ S BT.

A pinon, 9 ins. diam., bears N. 4° W., 53 lks. dist., mkd. ¼ S BT.

☆U.S. Government Printing Office: 1980—778-251/292

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 35 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
	At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd. T 35 S R 3 E ¼ S 26 / S 35 1980 Cor. is located on gently rolling land in scattered pinon and juniper growth.
	S. 89° 13' W., beginning new measurement.
39.81	The cor. of secs. 26, 27, 34, and 35.
	N. 0° 54' E., bet. secs. 26 and 27. Over rolling desert land, through sagebrush and widely scattered pinon and juniper growth.
19.96	Point for the S 1/16 sec. cor. of secs. 26 and 27. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 35 S R 3 E S 1/16 S 27 | S 26 1980 Set a 4 ft. squared pine post, alongside the aluminum post. Cor. is located on gently rolling land in sagebrush.
39.92	The ¼ sec. cor. of secs. 26 and 27, as determined from the original bearing trees A juniper, 10 ins. diam., bears S. 76° W., 52 lks. dist., mkd. ¼ S BT. A pinon, 10 ins. diam., bears N. 41° W., 55 lks. dist., mkd. ¼ S BT. At the corner point Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 35 S R 3 E ¼ S 27 | S 26 1980 Cor. is located on gently rolling land in scattered pinon and juniper growth.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 35 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
	N. 0° 57' W., beginning new measurement.
19.955	Point for the N 1/16 sec. cor. of secs. 26 and 27, falls on S shoulder of State Highway No. 54.
	At the corner point
	Drove ½ in. rebar 12 ins. in the ground.
	Rebar is located 21 lks. S of S edge of highway, bears SE and NW.
39.91	The cor. of secs. 22, 23, 26, and 27, monumented with a limestone, 20 x 5 x 3 ins., firmly set 10 ins. in the ground and plainly mkd. 2 grooves on E and S faces, from which the original bearing trees
	A pinon, 14 ins. diam., bears N. 19° E., 52 lks. dist., mkd. T35S R3E S23 BT.
	A pinon, 10 ins. diam., bears S. 15° E., 13 lks. dist., mkd. T35S R3E S26 BT.
	A pinon, 15 ins. diam., bears S. 50° W., 108 lks. dist., mkd. T35S R3E S27 BT.
	A pinon, 12 ins. diam., bears N. 49° W., 48 lks. dist., mkd. T35S R3E S22 BT.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 35 S R 3 E S 22 | S 23 S 27 | S 26 1980
	Deposit the mkd. stone alongside the iron post.
	Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor.
	Cor. is located in small draw, drains SW.
	From the cor. of secs. 23, 24, 25, and 26.
	S. 88° 44' W., bet. secs. 23 and 26.
	Over broken desert land, through pinon and juniper growth.
41.28	Point selected for the witness cor. to the ¼ sec. cor. of secs. 23 and 26.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., over a cross (X) on solid sandstone ledge, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.
	W C T 35 S R 3 E S 23 ¼ < S 26 1980

CHAINS	
41.43	The ¼ sec. cor. of secs. 23 and 26, monumented with a limestone, 20 x 10 x 3 ins., loosely set and dimly mkd. ¼ on N face, from which the original bearing trees A juniper, 11 ins. diam., bears N. 31° E., 60 lks. dist., dimly mkd. (Record, N. 46° E.) A pinon, 10 ins. diam., bears S. 83° E., 23 lks. dist., dimly mkd. (Record, S. 86° E., 23 lks. dist.) Cor. is located near edge of ledge and is unsuitable to remonument.
	N. 88° 43' W., beginning new measurement.
38.47	The cor. of secs. 22, 23, 26, and 27.
	North, bet. secs. 22 and 23. Over broken desert land, through pinon and juniper growth.
40.00	Point for the ¼ sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., over a cross (X) chiseled on solid sandstone, and in a mound of stone, 6 ft. base, to top of aluminum cap, mkd. T 35 S R 3 E ¼ S 22 | S 23 1980 Cor. is located on W slope on E edge of draw, drains S.
80.00	Point for the cor. of secs. 14, 15, 22, and 23, at record distance northing from the cor. of secs. 22, 23, 26, and 27, and record easting from the cor. of secs. 15, 16, 21, and 22; there is no remaining evidence of the original cor. Set an aluminum post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone, 5 ft. base, to top of aluminum cap, mkd. T 35 S R 3 E S 15 | S 14 S 22 | S 23 1980 from which A ponderosa pine, 14 ins. diam., bears N. 80° E., 38 lks. dist., mkd. X BT. A ponderosa pine, 10 ins. diam., bears S. 45° W., 2 lks. dist., mkd. BT. Cor. is located on rolling land in scattered pinon, juniper and ponderosa pine.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 35 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
	From the standard cor. of secs. 33 and 34, on the S. bdy. of the Tp., hereinbefore described.
	N. 0° 05' W., bet. secs. 33 and 34.
	Over rolling desert land, through sagebrush and native grasses.
20.12	Point for the S 1/16 sec. cor. of secs. 33 and 34.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 35 S R 3 E S 1/16 S 33 | S 34 1980
	Cor. is located in 4 strand barbwire fence cor., that bears N and E.
40.24	The ¼ sec. cor. of secs. 33 and 34, monumented with a limestone, 20 x 10 x 6 ins., firmly set 10 ins. in the ground. No visible marks could be found.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 35 S R 3 E ¼ S 33 | S 34 1980
	Cor. is located in 4 strand barbwire fence cor., that bears N, E, S, and W.
	N. 0° 05' W., beginning new measurement.
39.98	The cor. of secs. 27, 28, 33, and 34, determined at the cor. of fences, from which fences bear N, S, and W. This position is accepted as the best available evidence of the original corner position.
	At the corner point
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T 35 S R 3 E S 28 | S 27 S 33 | S 34 1980
	Cor. is located on gently rolling desert land in native grasses.
	From the cor. of secs. 26, 27, 34, and 35.
	S. 89° 42' W., bet. secs. 27 and 34.

CHAINS	
	Over rolling desert land, through sagebrush and native grasses.
19.90	Point for the E 1/16 sec. cor. of secs. 27 and 34.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T 35 S R 3 E E 1/16 S 27 / S 34 1980
	Cor. is located on gently rolling land in sagebrush and native grasses.
39.80	The ¼ sec. cor. of secs. 27 and 34, monumented with a sandstone, 20 x 10 x 4 ins., firmly set 10 ins. in the ground and plainly mkd. ¼ on N face.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 35 S R 3 E ¼ S 27 / S 34 1980
	Deposit the mkd. stone alongside the iron post.
	Cor. is located 16 lks. N of 4 strand barbwire fence, that bears E and W and 9 lks. E of a power line, that bears N and S in sagebrush and native grasses.
	S. 89° 26' W., beginning new measurement.
40.26	The cor. of secs. 27, 28, 33, and 34.
	N. 0° 05' W., bet. secs. 27 and 28.
	Over rolling desert land, through sagebrush and native grasses.
40.16	Point for the ¼ sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T 35 S R 3 E ¼ S 28 | S 27 1980
	Deposit 6 ft. cottonwood post alongside the aluminum post.
	Cor. is located 101 lks. S of old fence line, bears E and W, and 56 lks. W of gate in N and S fence line.

364

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 35 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
60.24	Point for the N 1/16 sec. cor. of secs. 27 and 28. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 35 S R 3 E N 1/16 S 28 | S 27 1980 Cor. is located 1 lk. W of 4 strand barbwire fence line, bears N and S.
80.32	The cor. of secs. 21, 22, 27, and 28, monumented with a broken limestone, 30 x 11 x 3 ins., firmly set and plainly mkd. 3 notches on E and 2 notches on S edges. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 35 S R 3 E S 21 | S 22 S 28 | S 27 1980 Deposit the broken mkd. stone alongside the iron post. Cor. is located in 4 strand barbwire fence cor., bears N, E and S in sagebrush and native grasses.
	From the cor. of secs. 22, 23, 26, and 27. S. 89° 59' W., bet. secs. 22 and 27. Over rolling desert land, through pinon and juniper growth.
19.99	Point for the E 1/16 sec. cor. of secs. 22 and 27. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 35 S R 3 E E 1/16 S 22 / S 27 1980 Set 6 ft. steel fence post alongside the aluminum post. Cor. is located on gently rolling land in pinon and juniper growth.
39.98	The ¼ sec. cor. of secs. 22 and 27, monumented with a sandstone, 20 x 10 x 3 ins., firmly set 10 ins. in the ground and dimly mkd. ¼ on N face. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS

T 35 S R 3 E
S 22
¼ S 27
1980

Deposit the mkd. stone alongside the iron post.

Cor. is located in 4 strand barbwire fence, bears N and S in scattered pinon and juniper trees.

S. 89° 47' W., beginning new measurement.

20.05 Point for the W 1/16 sec. cor. of secs. 22 and 27.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 35 S R 3 E
S 22
W 1/16 S 27
1980

Set 6 ft. steel fence post alongside the aluminum post.

Cor. is located on gently rolling land in scattered pinon and juniper growth.

40.10 The cor. of secs. 21, 22, 27, and 28.

N. 0° 08' W., bet. secs. 21 and 22.

Over rolling desert land, through sagebrush and native grasses.

40.10 Point for the ¼ sec. cor. of secs. 21 and 22, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 35 S R 3 E
¼
S 21 | S 22
1980

Cor. is located 35 lks. S of old fence line, bears E and W in sagebrush and native grasses.

80.20 The cor. of secs. 15, 16, 21, and 22, determined from the original bearing trees

A pinon, 12 ins. diam., bears N. 58° E., 86 lks. dist., mkd. T35S R3E S15 BT.

A pinon, 8 ins. diam., bears S. 48° E., 23 lks. dist., mkd. T35S R3E S22 BT.

A pinon, 14 ins. diam., bears S. 38° W., 78 lks. dist., mkd. T35S R3E S21 BT.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 35 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
	At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd. T 35 S R 3 E S 16 | S 15 S 21 | S 22 1980 Cor. is located on W slope in pinon and juniper growth.
	From the cor. of secs. 14, 15, 22, and 23. N. 89° 59' W., bet. secs. 15 and 22. Over broken desert land, through pinon, juniper and scattered ponderosa pine.
40.15	Point for the ¼ sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 35 S R 3 E S 15 ¼ S 22 1980 Cor. is located on rolling S slope in scattered pinon and juniper growth.
80.30	The cor. of secs. 15, 16, 21, and 22.
	N. 0° 03' W., bet. secs. 15 and 16. Over broken desert land, through pinon and juniper growth.
39.61	The ¼ sec. cor. of secs. 15 and 16, determined at record distance from the original bearing trees A pinon, 6 ins. diam., bears N. 80° E., 33 lks. dist., mkd. with a blaze. (Record, N. 85° E.) A standing dead pinon, 10 ins. diam., bears S. 32½° W., 24 lks. dist., dimly mkd. ¼ S BT. (Record, S. 24° W.) At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., over a cross (X) chiseled on solid sandstone, and in a mound of stone, 5 ft. base, to top of brass cap, mkd. T 35 S R 3 E ¼ S 16 | S 15 1981

CHAINS

from which

A powerpole, (No. 191), bears S. 08° 53' W., 48½ lks. dist., mkd. X BT.

Cor. is located on spur ridge, slopes SW in scattered pinon and ponderosa trees.

N. 0° 32' E., beginning new measurement.

39.24 Point for the cor. of secs. 9, 10, 15, and 16, at proportionate distance latitudinally and record distance easting from the ¼ sec. cor. of secs. 9 and 16.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base, to top of aluminum cap, mkd.

T 35 S R 3 E
S 9 | S 10
S 16 | S 15
1981

Cor. is located on small spur, slopes SW in scattered pinon and juniper growth.

N. 4° 22' E., bet. secs. 9 and 10.

Over broken desert land, through pinon and juniper growth.

39.35 Point for the ¼ sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 14 ins. long, 1 in. diam., drilled 6 ins. in solid sandstone, with brass cap mkd.

T 35 S R 3 E
¼
S 9 | S 10
1981

Cor. is located on NW slope of solid sandstone.

78.70 The cor. of secs. 3, 4, 9, and 10, as determined from original bearing tree

A ponderosa pine, 20 ins. diam., bears N. 74° W., 48 lks. dist., dimly mkd.

At the corner point

Set an iron post, 12 ins. long, 1 in. diam., drilled 8 ins. in solid sandstone, with brass cap mkd.

T 35 S R 3 E
S 4 | S 3
S 9 | S 10
1981

Cor. is located on SE slope on solid sandstone.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 35 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
	N. 0° 25' E., bet. secs. 3 and 4.
	Over broken desert land, through scattered pinon, juniper and ponderosa pine.
38.49	The ¼ sec. cor. of secs. 3 and 4, monumented with an iron post, 2½ ins. diam., firmly set, with brass cap, mkd. as described in the official record of the 1959 dependent resurvey.
	(Reestablishment of the Survey Executed by Wm. Lewman, Deputy Surveyor in 1894 and the Resurvey Executed by G.D. Voorhees in 1959)
	From the standard cor. of secs. 32 and 33, on the S. bdy. of the Tp.
	N. 0° 25' W., bet. secs. 32 and 33.
	Over rolling desert land, through sagebrush and native grasses, along graveled road.
39.99	The ¼ sec. cor. of secs. 32 and 33, determined longitudinally from ties to fences made in 1959 (fence, bearing N and S is East 85 lks. and fence, bearing N and S, is West, 18 lks. dist.) and latitudinally in line with fence extending N. 89° 23' E. This point is harmoniously related to existing cors., and is accepted as the best available evidence of the corner position. No remaining evidence of the 1959 iron post monument.
	from which
	A fence, bearing N and S is located 85 lks. E.
	A fence, bearing N and S is located 18 lks. W.
	At the corner point
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T 35 S R 3 E ¼ S 32 | S 33 1980
	Set 6 ft. steel fence post alongside the aluminum post.
	Cor. is located on W side of graveled road, bears N and S.
	N. 0° 22' W., beginning new measurement.
	Alongside graveled road.
40.44	The cor. of secs. 28, 29, 32, and 33, marked, and referenced as described in the official record of the field notes of the 1959 dependent resurvey.
	(Reestablishment of the Survey Executed by Wm. Lewman, Deputy Surveyor in 1894)

CHAINS	
	From the cor. of secs. 27, 28, 33, and 34.
	S. 89° 41' W., bet. secs. 28 and 33.
	Over rolling desert land, through sagebrush and native grasses.
40.25	The ¼ sec. cor. of secs. 28 and 33, monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above the ground, with brass cap, mkd. as described in the official record of the field notes of the 1959 dependent resurvey.
	(Reestablishment of the Survey Executed by Wm. Lewman, Deputy Surveyor in 1894 and the Resurvey Executed by G.D. Voorhees in 1959)
	N. 89° 45' W., beginning new measurement.
40.22	The cor. of secs. 28, 29, 32, and 33.
	N. 0° 52' E., bet. secs. 28 and 29.
	Over rolling desert land, through sagebrush and native grasses.
40.23	The ¼ sec. cor. of secs. 28 and 29, monumented with a sandstone, 20 x 10 x 6 ins., firmly set 10 ins. in the ground and plainly mkd. ¼ on W face.
	At the corner point
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 35 S R 3 E ¼ S 29 | S 28 1980
	Deposit the mkd. stone alongside the iron post.
	Cor. is located 2 lks. S and 38 lks. W of fence cor.
	N. 0° 49' W., beginning new measurement.
40.23	The cor. of secs. 20, 21, 28, and 29, monumented with an iron post, 2½ ins. diam., firmly set and extending 6 ins. above the ground, with brass cap, mkd. as described in the official record of the 1959 dependent resurvey.
	(Reestablishment of the Survey Executed by Wm. Lewman, Deputy Surveyor in 1894)
	From the cor. of secs. 9, 10, 15, and 16.
	N. 88° 56' W., bet. secs. 9 and 16.

CHAINS

Over broken desert land, through pinon and juniper growth.

40.11 The ¼ sec. cor. of secs. 9 and 16, monumented with a limestone, 28 x 10 x 4 ins., firmly set 15 ins. in the ground and plainly mkd. ¼ on N face, from which the original bearing trees

A pinon, 8 ins. diam., bears N. 26° E., 41 lks. dist., mkd. ¼ S9 BT. (Record, N. 33° E., 48 lks. dist.)

A standing dead pinon, 10 ins. diam., bears S. 50° W., 35 lks. dist., mkd. ¼ S16 BT. (Record, S. 44° W. 27 lks. W.)

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 35 S R 3 E
¼ S 9 / S 16
1980

Deposit the mkd. stone alongside the aluminum post.

Cor. is located on steep E slope in scattered pinon and juniper trees.

S. 89° 51' W., beginning new measurement.

40.13 The cor. of secs. 8, 9, 16, and 17, monumented with a sandstone, 24 x 8 x 6 ins., firmly set in a mound of stone and plainly mkd. 2 grooves on E face and 4 grooves on S face.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 35 S R 3 E
S 8 | S 9
S 17 | S 16
1980

Deposit the mkd. stone alongside the iron post.

Raise a mound of stone, 2½ ft. base, 1 ft. high, W of cor.

Cor. is located on nearly level land.

N. 1° 14' E., bet. secs. 8 and 9.

Over gently rolling land, through native grasses.

39.78 Point for the ¼ sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original corner.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 35 S R 3 E
¼
S 8 | S 9
1980

Cor. is located in cultivated land, 25 lks. N and 58 lks. W of new netwire fence cor., bears N, E and W.

79.56 The cor. of secs. 4, 5, 8, and 9, monumented with a porphyry stone, 36 x 10 x 4 ins., firmly set, 24 ins. in the ground and plainly mkd. 4 notches on E and 5 notches on S edges.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 35 S R 3 E
S 5 | S 4
S 8 | S 9
1980

Deposit the mkd. stone alongside the iron post.

Cor. is located in fence corner, barbwire, bears N, E, S, and W.

From the cor. of secs. 3, 4, 9, and 10.

S. 88° 31' W., bet. secs. 4 and 9.

Over broken desert land, through scattered pinon and juniper growth.

54.14 The ¼ sec. cor. of secs. 4 and 9, monumented with a sandstone, 32 x 20 x 10 ins., firmly set 10 ins. in the ground and plainly mkd. ¼ on N face, from which the original bearing trees

A ponderosa pine, 30 ins. diam., bears S. 37° W., 8½ lks. dist., mkd. ¼ S BT. (Record, 7 lks. dist.)

A standing dead ponderosa pine, 13 ins. diam., bears N. 50° W., 13 lks. dist., mkd. ¼ S BT. (Record, 15 lks. dist.)

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 35 S R 3 E
¼ S 4
S 9
1981

Cor. is located on steep N slope, 1.00 ch. S of deep canyon, drains W, in scattered ponderosa pine.

372

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 35 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
	N. 84° 11' W., beginning new measurement.
15.26	Point for the W 1/16 sec. cor. of secs. 4 and 9.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T 35 S R 3 E W 1/16 S 4 / S 9 1981
	Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.
	Cor. is located on W slope in pinon and juniper growth.
30.52	The cor. of secs. 4, 5, 8, and 9.
	N. 0° 04' E., bet. secs. 4 and 5.
	Over rolling desert land, through pinon and juniper growth.
40.04	The ¼ sec. cor. of secs. 4 and 5, monumented with a sandstone, 26 x 10 x 6 ins., firmly set in a mound of stone and plainly mkd. ¼ on W face.
	At the corner point
	Set an aluminum post, 30 ins. long, 2½ ins. diam., over a cross (X) chiseled on solid sandstone, and in a mound of stone, 4½ ft. base, to top of aluminum cap, mkd.
	T 35 S R 3 E ¼ S 5 | S 4 1980
	Cor. is located on exposed sandstone on SW slope.
	N. 0° 18' E., beginning new measurement.
	Over broken desert land, through scattered pinon, juniper and ponderosa pine.
38.76	The cor. of secs. 4 and 5, on the N. bdy. of the Tp., hereinbefore described.
	From the cor. of secs. 28, 29, 32, and 33.
	S. 89° 35' W., bet. secs. 29 and 32.
	Over rolling desert land, through sagebrush and native grasses.
	Along graveled road.
39.86	The witness ¼ sec. cor. for secs. 29 and 32, monumented with an iron post, 2½ ins. diam. firmly set, extending 6 ins. above the ground, with brass cap, mkd. as described in the official record of the 1959 dependent resurvey.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 35 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
40.22	True point for the ¼ sec. cor. of secs. 29 and 32, falls in stock pond and cannot be monumented.
	S. 89° 35' W., beginning new measurement.
20.11	Point for the W 1/16 sec. cor. of secs. 29 and 32.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 35 S R 3 E W 1/16 S 29 / S 32 1981
	Set a pine post alongside the iron post.
	Cor. is located 25 lks. S and 14 lks. E of barbwire fence cor., bears N, E and W.
40.22	The cor. of secs. 29, 30, 31, and 32, monumented with an iron post, 2½ ins. diam., firmly set, with brass cap, mkd. as described in the official record of the 1959 dependent resurvey.
	From this point, U.S.G.S. triangulation station "Escalante Rim," a brass cap, set on solid sandstone ledge, mkd. Forest Service bears S. 55° 46' W., 42.79 chs. dist.
	Survey of the Section Line Between Sections 30 and 31, T. 35 S., R. 3 E., Salt Lake Meridian, Utah
	West, bet. secs. 30 and 31.
	Over broken mountainous land, through pinon and juniper growth.
40.00	Point for the ¼ sec. cor. of secs. 30 and 31.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base, to top of aluminum cap, mkd.
	T 35 S R 3 E ¼ S 30 / S 31 1981
	Cor. is located on steep E slope in pinon and juniper growth.
47.73	Top of ridge, bears SE and NW.
82.49	Intersect the E. bdy. of sec. 36, T. 35 S., R. 2 E.
	Point for the closing cor. of secs. 30 and 31.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

Survey of the Section Line Between Sections 30 and 31, T. 35 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS

T 35 S
R 2 E | R 3 E
S 36 | S 30 C
| S 31 C
1981

From this closing cor., the cor. of secs. 25 and 36, T. 35 S., R. 2 E., bears N. 1° 44' W., 1.18 chs. dist., and the ¼ sec. cor. of secs. 31 and 36, T. 35 S., Rs. 2 and 3 E., bears S. 1° 44' E., 39.76 chs. dist.

Cor. is located on gentle W slope in boulders and scattered pinon and juniper.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 35 S., R. 3 E., Salt Lake Meridian, Utah

---

(Reestablishment of the Survey Executed by Wm. Lewman, Deputy Surveyor in 1894)

From the cor. of secs. 29, 30, 31, and 32.

N. 0° 31' E., bet. secs. 29 and 30.

Over rolling desert land, through sagebrush and scattered pinon and juniper growth.

40.41 The ¼ sec. cor. of secs. 29 and 30, monumented with a sandstone, 20 x 10 x 4 ins., firmly set 10 ins. in the ground and plainly mkd. ¼ on W face, from which the original bearing tree

A juniper, 12 ins. diam., bears S. 51° W., 295 lks. dist., mkd. ¼ S BT.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 35 S R 3 E
¼
S 30 | S 29
1980

Deposit the mkd. stone alongside the aluminum post.

Cor. is located in four strand barbwire fence cor., bears N and E.

N. 0° 35' W., beginning new measurement.

20.06 Point for the N 1/16 sec. cor. of secs. 29 and 30.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 35 S R 3 E
N 1/16
S 30 | S 29
1981

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 35 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
	Set 6 ft. juniper post alongside the iron post. Cor. is located 9 lks. N of four strand barbwire fence cor., bears E and S.
40.12	The cor. of secs. 19, 20, 29, and 30, monumented with a sandstone, 22 x 14 x 6 ins., firmly set 12 ins. in the ground and plainly mkd. 5 grooves on E face and 2 grooves on S face. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T 35 S R 3 E S 19 | S 20 S 30 | S 29 1980 Deposit the mkd. stone alongside the iron post. Cor. is located in four strand barbwire fence cor., bears N, E and W.
	From the cor. of secs. 20, 21, 28, and 29. S. 89° 38' W., bet. secs. 20 and 29 Over cultivated land.
40.25	Point for the ¼ sec. cor. of secs. 20 and 29, at proportionate distance; there is no remaining evidence of the original cor. This point falls in cultivated land and is not monumehted.
80.50	The cor. of secs. 19, 20, 29, and 30.
	N. 89° 54' W., bet. secs. 19 and 30. Over rolling desert land, through sagebrush and scattered pinon and juniper growth.
19.81	Point for the E 1/16 sec. cor. of secs. 19 and 30. Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd. T 35 S R 3 E E 1/16 S 19 / S 30 1981 Cor. is located 11 lks. N of four strand barbwire fence, bears E and W in the S wheel tract of trail road along fence.
39.62	The ¼ sec. cor. of secs. 19 and 30, monumented with a sandstone, 20 x 8 x 3 ins., firmly set 10 ins. in the ground and plainly mkd. ¼ on N face.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 35 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
	At the corner point Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 35 S R 3 E ¼ S 19 / S 30 1980 Deposit the mkd. stone alongside the aluminum post. Cor. is located on nearly level land in scattered pinon and juniper growth.
	S. 88° 43' W., beginning new measurement.
20.04	Point for the W 1/16 sec. cor. of secs. 19 and 30. Not monumented.
39.66	True point for the cor. of secs. 19, 24, 25, and 30, from which its witness cor., bears S. 0° 18' W., 2.50 chs. dist., hereinbefore described.
	From the cor. of secs. 19, 20, 29, and 30.
	N. 0° 03' W., bet. secs. 19 and 20.
	Over rolling desert land, through sagebrush and native grasses.
40.09	The ¼ sec. cor. of secs. 19 and 20, monumented with a sandstone, 20 x 10 x 4 ins., firmly set 10 ins. in the ground and dimly mkd. ¼ on W face.
	At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 35 S R 3 E ¼ S 19 | S 20 1980 Deposit the mkd. stone alongside the iron post. Cor. is located in four strand barbwire fence cor., bears E, S and W.
	N. 0° 49' E., beginning new measurement.
40.06	The cor. of secs. 17, 18, 19, and 20, monumented with a sandstone, 18 x 10 x 5 ins., firmly set 10 ins. in the ground and plainly mkd. 5 notches on E edge and 3 notches on S edge.

☆U.S. Government Printing Office: 1980—778-251/292

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 35 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
	At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 35 S R 3 E S 18 | S 17 S 19 | S 20 1980 Deposit the mkd. stone alongside the iron post. Cor. is located on gently rolling land in native grasses.
	S. 89° 48' W., bet. secs. 18 and 19. Over gently rolling desert land, through native grasses.
39.60	Point for the ¼ sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 35 S R 3 E ¼ S 18 S 19 1980 Set a 6 ft. steep fence post alongside the iron post. Cor. is located on gently rolling land in native grasses.
59.40	Point for the W 1/16 sec. cor. of secs. 18 and 19. Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd. T 35 S R 3 E W 1/16 S 18 S 19 1980 Cor. is located on E slope in pinon and juniper growth.
78.76	The cor. of secs. 13, 18, 19, and 24, on the W. bdy., hereinbefore described.
	From the cor. of secs. 17, 18, 19, and 20. N. 0° 01' W., bet. secs. 17 and 18. Over gently rolling desert land, through native grasses.
40.26	Point for the ¼ sec. cor. of secs. 17 and 18, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 35 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
	T 35 S R 3 E ¼ S 18 | S 17 1980 Cor. is located in pasture. Over pasture and residential area of Escalante, Utah.
80.52	The cor. of secs. 7, 8, 17, and 18, monumented with an iron post, 3 ins. diam., extending 18 ins. above the ground, with unmkd. brass cap, with a lava stone, 20 x 12 x 8 ins., firmly set alongside, plainly mkd. 5 grooves on E face and 4 grooves on S face. I mkd. brass cap T 35 S R 3 E S 7 | S 8 S 18 | S 17 1980 Cor. is located in residential area.
	S. 89° 07' W., bet. secs. 7 and 18. Over residential area.
40.29	The ¼ sec. cor. of secs. 7 and 18, monumented with an iron post, 2½ ins. diam., extending 5 ins. above the ground, with brass cap as in the official record book No. A-238, page 316, shown as being monumented on September 11, 1964. Cor. is located in fence cor., four strand barbwire, bears N and W.
	S. 89° 33' W., beginning new measurement. Over broken desert land, through pinon and juniper growth.
19.665	Point for the W 1/16 sec. cor. of secs. 7 and 18. Set an iron post, 30 ins. long, 2½ ins. diam.; over a cross (X) chiseled on solid rock, and in a mound of stone, 5 ft. base, to top of brass cap, mkd. T 35 S R 3 E W 1/16 S 7 S 18 1980 from which A ½ in. aluminum cap on rebar, bears S. 81° 32' W., 63 lks. dist., mkd. Park Bdy. Surveyors Asso. This cor. was established using improper procedure and is not utilized in the course of this resurvey.
38.75	The cor. of secs. 7, 12, 13, and 18, on the W. bdy., hereinbefore described.

☆U.S. Government Printing Office: 1980—778-251/292

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 35 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
	From the cor of secs. 7, 8, 17, and 18.
	N. 0° 36' E., bet. secs. 7 and 8.
	Over residential area.
40.09	The ¼ sec. cor. of secs. 7 and 8, monumented with an aluminum post, 2½ ins. diam., extending 3 ins. above the ground. This aluminum cap set by U.S. Forest Service and is accepted as a careful and faithful reestablishment of the original corner position, with aluminum cap mkd. T 35 S R 3 E ¼ S 7 | S 8 LS4266UT 1979
	Cor. is located in bottom land.
	N. 0° 36' E., beginning new measurement.
	Over pasture and cultivated land.
40.10	The cor. of secs. 5, 6, 7, and 8, monumented by U.S. Forest Service with an aluminum post, 2½ ins. diam., extending 3 ins. above the ground and is accepted as a careful and faithful reestablishment of the position of the original corner, with aluminum cap mkd. T 35 S R 3 E S 6 | S 5 S 7 | S 8 LS4266UT 1979
	Cor. is located on gentle SE slope.
	From the cor. of secs. 4, 5, 8, and 9.
	N. 88° 53' W., bet. secs. 5 and 8.
	Over rolling desert land, through sagebrush and native grasses.
40.94	The ¼ sec. cor. of secs. 5 and 8, monumented by U.S. Forest Service with an aluminum post, 2½ ins. diam., set in a mound of stone, and is accepted as a careful and faithful reestablishment of the position of the original corner, with aluminum cap mkd. T 35 S R 3 E ¼ S 5 / S 8 LS4266UT 1979
	Cor. is located on rolling desert land.
	N. 89° 49' W., beginning new measurement.
40.15	The cor. of secs. 5, 6, 7, and 8.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 35 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
	N. 89° 57' W., bet. secs. 6 and 7.
	Over broken desert land, through pinon and juniper growth.
40.09	The ¼ sec. cor. of secs. 6 and 7, monumented by U.S. Forest Service, with an aluminum post, 2½ ins. diam., extending 6 ins. above the ground and is accepted as a careful and faithful reestablishment of the position of the original corner, with aluminum cap mkd. T 35 S R 3 E ¼ S 6 / S 7 LS4266UT 1979
	Cor. is located in hollow, drains SE.
	N. 89° 58' W., beginning new measurement.
20.05	Point for the W 1/16 sec. cor. of secs. 6 and 7.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 35 S R 3 E W 1/16 S 6 / S 7 1980
	Cor. is located on spur, slopes SE in scattered pinon and juniper growth.
39.54	The cor. of secs. 1, 6, 7, and 12, on the W, bdy., hereinbefore described.
	From the cor. of secs. 5, 6, 7, and 8.
	N. 1° 26' W., bet. secs. 5 and 6.
	Over broken desert land, through pinon and juniper growth.
40.12	The ¼ sec. cor. of secs. 5 and 6, monumented with an aluminum post, 2 ins. diam., extending 6 ins. above the mound of stone, 3½ ft. base, 1 ft. high to U.S. Forest Service aluminum cap
	from which original bearing trees
	A pinon, 12 ins. diam., bears S. 53° E., 10 lks. dist., mkd. ¼ S BT. (Record, S. 42° E., 8 lks. dist.)
	A pinon, 12 ins. diam., bears S. 75° W., 20 lks. dist., mkd. ¼ S BT. (Record, S. 86° W., 21 lks. dist.)
	Aluminum cap mkd. T 35 S R 3 E S 6 | S 5 ¼ | LS4266UT 1979

☆U.S. Government Printing Office: 1980—778-251/292

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 35 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
	This cor. is accepted as a careful and faithful reestablishment of the position of the original corner.
	Cor. is located on N slope in pinon and juniper.
	N. 2° 11' E., beginning new measurement.
37.81	The cor. of secs. 5 and 6, on the N. bdy., hereinbefore described.
	Survey of the Subdivision of Section 5, T. 35 S., R. 3 E., Salt Lake Meridian, Utah
	From the ¼ sec. cor. of secs. 5 and 8.
	N. 0° 01' E., on N-S center line of sec. 5.
39.74	Point for the center ¼ sec. cor. of sec. 5, at intersection with the E and W center line.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 35 S R 3 E C ¼ S 5 1980
	Set 6 ft. cedar post alongside the aluminum post.
	Cor. is located on gentle E slope in sagebrush.
77.16	The ¼ sec. cor. of sec. 5 only, on the N. bdy. of the Tp., hereinbefore described.
	From the ¼ sec. cor. of secs. 4 and 5.
	N. 89° 19' W., on the E-W center line of sec. 5.
20.485	Point for the center E 1/16 sec. cor. of sec. 5.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 35 S R 3 E E 1/16 C ——— C S 5 1980
	Set 6 ft. steel fence post alongside the aluminum post.
	Cor. is located 28 lks. W of N and S fence line on the W. edge of graveled road, bears N and S.
40.97	The center ¼ sec. cor. of sec. 5.
82.14	The ¼ sec. cor. of secs. 5 and 6.

CHAINS	
	Survey of the Subdivision of Section 6, T. 35 S., R. 3 E., Salt Lake Meridian, Utah
	From the ¼ sec. cor. of secs. 6 and 7.
	N. 0° 25' E., on the N and S center line of sec. 6.
39.57	Point for the center ¼ sec. cor. of sec. 6, at intersection with the E and W center line.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 35 S R 3 E C ¼ S 6 1980
	Set 6 ft. steel fence post alongside the aluminum post.
78.15	The ¼ sec. cor. of sec. 6 only, on the N. bdy. of the Tp., hereinbefore described.
	From the ¼ sec. cor. of secs. 5 and 6.
	S. 89° 15' W., on the E and W center line of sec. 6.
38.80	The center ¼ sec. cor. of sec. 6.
78.49	The ¼ sec. cor. of secs. 1 and 6, on the W. bdy. of the Tp., hereinbefore described.
	Survey of the Subdivision of Section 7, T. 35 S., R. 3 E., Salt Lake Meridian, Utah
	From the ¼ sec. cor. of secs. 7 and 18.
	N. 0° 44' E., on the N and S center line of sec. 7.
20.25	Point for the center S 1/16 sec. cor. of sec. 7. Not monumented.
40.50	Point for the center ¼ sec. cor. of sec. 7, at intersection with the E and W center line.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 35 S R 3 E C ¼ S 7 1981
60.67	Point for the center N 1/16 sec. cor. of sec. 7. Not monumented.
80.84	The ¼ sec. cor. of secs. 6 and 7.
	From the ¼ sec. cor. of secs. 7 and 8.
	S. 89° 42' W., on the E and W center line of sec. 7.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
40.19	The center ¼ sec. cor. of sec. 7.
60.05	Point for the center W 1/16 sec. cor. of sec. 7. Not monumented.
79.34	The ¼ sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp.
	From the W 1/16 sec. cor. of secs. 7 and 18. N. 0° 27' E., on the N and S center line of the SW¼ of sec. 7.
20.27	True point for the SW 1/16 sec. cor. of sec. 7, at intersection with the E and W center line of the SW¼, falls in bottom of draw, drains N and is unsafe to monument.
21.60	Point selected for the witness cor. to the SW 1/16 sec. cor. of sec. 7. Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 4½ ft. base, to top of brass cap, mkd. W C T 35 S R 3 E SW 1/16 S 7 ↓ 1981
40.54	Point for the center W 1/16 sec. cor. of sec. 7.
	From the point for the center S 1/16 sec. cor. of sec. 7. S. 89° 38' W., on the E and W center line of the SW¼ of sec. 7.
19.76	True point for the SW 1/16 sec. cor. of sec. 7.
38.95	The S 1/16 sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp.
	From the point for the center W 1/16 sec. cor. of sec. 7. N. 0° 28' E., on the N and S center line of the NW¼ of sec. 7.
20.23	Point for the NW 1/16 sec. cor. of sec. 7, at intersection with the E and W center line of the NW¼. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 35 S R 3 E NW 1/16 S 7 1981 Set 6 ft. cedar post alongside the iron post.
40.46	The W 1/16 sec. cor. of secs. 6 and 7.

Survey of the Subdivision of Section 7,
T. 35 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
	From the point for the center N 1/16 sec. cor. of sec. 7.
	S. 89° 52' W., on the E and W center line of the NW¼ of sec. 7.
19.955	The NW 1/16 sec. cor. of sec. 7.
39.34	The N 1/16 sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp.

Survey of the Subdivision of Section 9,
T. 35 S., R. 3 E., Salt Lake Meridian, Utah

	From the ¼ sec. cor. of secs. 9 and 16.
	N. 6° 01' W., on the N and S center line of sec. 9.
39.38	Point for the center ¼ sec. cor. of sec. 9, at intersection with the E and W center line.
	Set an iron post, 18 ins. long, 1 in. diam., drilled 10 ins. in solid sandstone, with brass cap mkd. T 35 S R 3 E C ¼ S 9 1981
	Raise a mound of stone, 3½ ft. base, 1½ ft. high, W of cor.
	Cor. is located on sandstone spur, projecting E.
76.76	The ¼ sec. cor. of secs. 4 and 9.

	From the ¼ sec. cor. of secs. 9 and 10.
	N. 89° 11' W., on the E and W center line of sec. 9.
47.22	The center ¼ sec. cor. of sec. 9.
64.79	Point for the center W 1/16 sec. cor. of sec. 9.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 35 S R 3 E W 1/16 C ——— C S 9 1981
	Set 6 ft. juniper post alongside the aluminum post.
	Cor. is located on gentle S slope.
82.36	The ¼ sec. cor. of secs. 8 and 9.

	From the center W 1/16 sec. cor. of sec. 9.
	N. 2° 17' W., on the N and S center line of the NW¼ of of sec. 9.
38.50	The W 1/16 sec. cor. of secs. 4 and 9.

CHAINS	
	Survey of the Subdivision of Section 18, T. 35 S., R. 3 E., Salt Lake Meridian, Utah
	From the ¼ sec. cor. of secs. 18 and 19.
	N. 0° 30' W., on the N and S center line of sec. 18.
40.09	Point for the center ¼ sec. cor. of sec. 18, at intersection of the E and W center line.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 35 S R 3 E C ¼ S 18 1981
	Cor. is located on gently rolling land in sagebrush and scattered juniper growth.
80.04	The ¼ sec. cor. of secs. 7 and 18.
	From the ¼ sec. cor. of secs. 17 and 18.
	S. 89° 33' W., on the E and W center line of sec. 18.
39.94	The center ¼ sec. cor. of sec. 18.
59.87	Point for the center W 1/16 sec. cor. of sec. 18.
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top of brass cap, mkd. T 35 S R 3 E W 1/16 C ——— C S 18 1981
	from which
	A ½ in. rebar with 1 in. aluminum cap, mkd. Surveyors Associates, bears N. 80° 47' E., 48 lks. dist.
	This cor. was established using improper procedures and is not utilized in the course of this survey.
	Continue on the E and W center line of sec. 18.
79.29	The ¼ sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp., hereinbefore described.
	From the W 1/16 sec. cor. of secs. 18 and 19.
	N. 0° 41' W., on the N and S center line of the SW¼ of sec. 18.
40.01	The center W 1/16 sec. cor. of sec. 18.

Survey of the Subdivision of Section 18,
T. 35 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
	From the center W 1/16 sec. cor. of sec. 18.
	N. 0° 08' W., on the N and S center line of the NW¼ of sec. 18.
39.96	The W 1/16 sec. cor. of secs. 7 and 18.

Survey of the Subdivision of Section 19,
T. 35 S., R. 3 E., Salt Lake Meridian, Utah

	From the ¼ sec. cor. of secs. 19 and 30.
	N. 0° 23' E., on the N and S center line of sec. 19.
19.975	Point for the center S 1/16 sec. cor. of sec. 19. Not monumented.
39.95	Point for the center ¼ sec. cor. of sec. 19, at intersection with the E and W center line.
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a collar of stone, with brass cap mkd. T 35 S R 3 E C ¼ S 19 1981
	Cor. is located on small spur, slopes NW in scrub pinon and juniper trees.
59.94	Point for the center N 1/16 sec. cor. of sec. 19. Not monumented.
79.93	The ¼ sec. cor. of secs. 18 and 19.

	From the ¼ sec. cor. of secs. 19 and 20.
	S. 89° 54' W., on the E and W center line of sec. 19.
19.65	Point for the center E 1/16 sec. cor. of sec. 19.
	Set an iron post, 30 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd. E 1/16 C S 19 C 1981
	Cor. is located in E and W trail road, 14 lks. N of 5 strand barbwire fence line, bears E and W.
39.30	The center ¼ sec. cor. of sec. 19.
59.37	Point for the center W 1/16 sec. cor. of sec. 19.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. W 1/16 C S 19 C 1981

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	Cor. is located on gently rolling sandy land, 1.50 chs. E of Alvey wash, drains N irregulary.
79.01	The ¼ sec. cor. of secs. 19 and 24, on the W. bdy. of the Tp., hereinbefore described.
	From the E 1/16 sec. cor. of secs. 19 and 30. N. 0° 10' E., on the N and S center line of the SE¼ of sec. 19.
40.02	The center E 1/16 sec. cor. of sec. 19.
	From point for the W 1/16 sec. cor. of secs. 19 and 30. N. 0° 20' E., on the N and S center line of the SW¼ of sec. 19.
20.185	Point for the SW 1/16 sec. cor. of sec. 19, at intersection with the E and W centerline of the SW¼. Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 5 ft. base, to top of brass cap, mkd. T 35 S R 3 E SW 1/16 S 19 1981 from which A 1 in. aluminum cap on ½ in. rebar, bears N. 75° 26' W., 86 lks. dist., mkd. Surveying Associates Utah state park boundary. This cor. was established using improper procedures and is not utilized in the course of this survey.
40.37	The center W 1/16 sec. cor. of sec. 19.
	From the point for the center S 1/16 sec. cor. of sec. 19. S. 89° 18' W., on the E and W center line of the SW¼ of sec. 19.
20.055	The SW 1/16 sec. cor. of sec. 19.
39.68	The S 1/16 sec. cor. of secs. 19 and 24, on the W. bdy. of the Tp., hereinbefore described.
	From the center W 1/16 sec. cor. of sec. 19. N. 0° 46' E., on the N and S center line of the NW¼ of sec. 19.
19.97	Point for the NW 1/16 sec. cor. of sec. 19, at intersection with the E and W center line of the NW¼. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

388

Survey of the Subdivision of Section 19,
T. 35 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
	NW 1/16 S 19 1981
	Set 6 ft. hardwood post alongside the iron post.
	Cor. is located on nearly level land in sagebrush.
39.94	The W 1/16 sec. cor. of secs. 18 and 19.
	From the point for the center N 1/16 sec. cor. of sec. 19.
	S. 89° 51' W., on the E and W center line of the NW¼ of sec. 19.
19.935	The NW 1/16 sec. cor. of sec. 19.
39.43	The N 1/16 sec. cor. of secs. 19 and 24, on the W. bdy. of the Tp., hereinbefore described.

Survey of the Subdivision of Section 22,
T. 35 S., R. 3 E., Salt Lake Meridian, Utah

	From the ¼ sec. cor. of secs. 22 and 27.
	N. 0° 07' W., on the N and S center line of sec. 22.
39.99	Point for the center ¼ sec. cor. of sec. 22, at intersection with the E and W center line of sec. 22.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd. T 35 S R 3 E C ¼ S 22 1981
80.03	The ¼ sec. cor. of secs. 15 and 22.
	From the ¼ sec. cor. of secs. 22 and 23.
	S. 89° 56' W., on the E and W center line of sec. 22.
40.06	The center ¼ sec. cor. of sec. 22.
60.12	Point for the center W 1/16 sec. cor. of sec. 22.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with aluminum cap mkd. T 35 S R 3 E W 1/16 C ——— C S 22 1981
	Set 6 ft. juniper post alongside the aluminum post.
80.18	The ¼ sec. cor. of secs. 21 and 22.

☆U.S. Government Printing Office: 1980—778-251/292

Survey of the Subdivision of Section 22,
T. 35 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
	From the W 1/16 sec. cor. of secs. 22 and 27.
	N. 0° 07' W., on the N and S center line of the SW¼ of sec. 22.
40.04	The center W 1/16 sec. cor. of sec. 22.

Survey of the Subdivision of Section 27,
T. 35 S., R. 3 E., Salt Lake Meridian, Utah

	From the ¼ sec. cor. of secs. 27 and 34.
	N. 0° 10' W., on the N and S center line of sec. 27.
19.955	Point for the center S 1/16 sec. cor. of sec. 27.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 35 S R 3 E C S 1/16 | S 27 C 1980
	Set 5 ft. juniper post alongside the aluminum post.
39.91	Point for the center ¼ sec. cor. of sec. 27, at intersection with the E and W center line of sec. 27.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 35 S R 3 E C ¼ S 27 1980
49.935	Point for the center S-N 1/64 sec. cor. of sec. 27.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 35 S R 3 E C S-N 1/64 | S 27 C 1980
	Set 5 ft. juniper post alongside the aluminum post.
59.96	Point for the center N 1/16 sec. cor. of sec. 27.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 35 S R 3 E C N 1/16 | S 27 C 1980
	Set 6 ft. juniper post alongside the aluminum post.

CHAINS	
80.01	The ¼ sec. cor. of secs. 22 and 27.
	From the ¼ sec. cor. of secs. 26 and 27.
	S. 89° 42' W., on the E and W center line of sec. 27.
20.26	Point for the center E 1/16 sec. cor. of sec. 27.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T 35 S R 3 E E 1/16 C ——— C S 27 1980
30.39	Point for the center W-E 1/64 sec. cor. of sec. 27.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T 35 S R 3 E W-E 1/64 C ——— C S 27 1980
	Set 6 ft. juniper post alongside the aluminum post.
40.52	The center ¼ sec. cor. of sec. 27.
60.62	Point for the center W 1/16 sec. cor. of sec. 27.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T 35 S R 3 E W 1/16 C ——— C S 27 1980
	Set 5 ft. juniper post alongside the aluminum post.
80.72	The ¼ sec. cor. of secs. 27 and 28.
	From the center east 1/16 sec. cor. of sec. 27.
	N. 0° 35' W., on the N and S center line of the NE¼ of sec. 27.
10.00	Point for the center south-northeast 1/64 sec. cor. of sec. 27. Not monumented.
20.00	Point for the NE 1/16 sec. cor. of sec. 27, at intersection with the E and W center line of the NE¼. Not monumented.
40.00	The E 1/16 sec. cor. of secs. 22 and 27.
	From the N 1/16 sec. cor. of secs. 26 and 27.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	S. 89° 51' W., on the E and W center line of the NE¼ of sec. 27.
20.12	Point for the NE 1/16 sec. cor. of sec. 27.
30.18	Point for the center west-northeast 1/64 sec. cor. of sec. 27. Not monumented.
	Continue on the E and W center line of the NE¼ of sec. 27.
40.24	The center N 1/16 sec. cor. of sec. 27.
	From the center west-east 1/64 sec. cor. of sec. 27.
	N. 0° 22' W., on the N and S center line of the SW¼ of the NE¼ of sec. 27.
10.01	Point for the southwest-northeast 1/64 sec. cor. of sec. 27, at intersection with the E and W center line of the SW¼ of the NE¼.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 35 S R 3 E S 27 SW-NE 1/64 1980
	Set 7 ft. juniper post alongside the aluminum post.
20.02	The point for the center west-northeast 1/64 sec. cor. of sec. 27.
	From the point for the center south-northeast 1/64 sec. cor. of sec. 27.
	S. 89° 46' W., on the E and W center line of the SW¼ of the NE¼ of sec. 27.
10.10	The southwest-northeast 1/64 sec. cor. of sec. 27.
20.20	The center south-north 1/64 sec. cor. of sec. 27.
	From the E 1/16 sec. cor. of secs. 27 and 34.
	N. 0° 22' E., on the N and S center line of the SE¼ of sec. 27.
19.96	Point for the SE 1/16 sec. cor. of sec. 27, at intersection with the E and W center line of the SE¼.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 35 S R 3 E SE 1/16 S 27 1980
	Set a steel fence post, 6 ft. long, alongside the aluminum post.

Survey of the Subdivision of Section 27,
T. 35 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
39.92	The center E 1/16 sec. cor. of sec. 27.
	From the S 1/16 sec. cor. of secs. 26 and 27.
	S. 89° 43' W., on the E and W center line of the SE¼ of sec. 27.
20.08	The SE 1/16 sec. cor. of sec. 27.
40.16	The center S 1/16 sec. cor. of sec. 27.
	From the center W 1/16 sec. cor. of sec. 27.
	N. 0° 07' W., on the N and S center line of the NW¼ of sec. 27.
20.065	Point for the NW 1/16 sec. cor. of sec. 27, at intersection with the E and W center line of the NW¼.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T 35 S R 3 E NW 1/16 S 27 1980
40.13	The W 1/16 sec. cor. of secs. 22 and 27.
	From the center N 1/16 sec. cor. of sec. 27.
	S. 89° 43' W., on the E and W center line of the NW¼ of sec. 27.
20.075	The NW 1/16 sec. cor. of sec. 27.
40.15	The N 1/16 sec. cor. of secs. 27 and 28.

Survey of the Subdivision of Section 29,
T. 35 S., R. 3 E., Salt Lake Meridian, Utah

	From the ¼ sec. cor. of secs. 29 and 32.
	North, on the N and S center line of sec. 29.
40.31	Point for the center ¼ sec. cor. of sec. 29, at intersection with the E and W center line of sec. 29.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T 35 S R 3 E C ¼ S 29 1980
80.48	The ¼ sec. cor. of secs. 20 and 29.
	From the true point for the ¼ sec. cor. of secs. 28 and 29.
	S. 89° 43' W., on the E and W center line of sec. 29.

Survey of the Subdivision of Section 29,
T. 35 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
40.83	The center ¼ sec. cor. of sec. 29.
60.75	Point for the center W 1/16 sec. cor. of sec. 29. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 35 S R 3 E W 1/16 C ——— C S 29 1980
80.67	The ¼ sec. cor. of secs. 29 and 30.
	From the W 1/16 sec. cor. of secs. 29 and 32. N. 0° 16' E., on the N and S center line of the SW¼ of sec. 29.
40.36	The center W 1/16 sec. cor. of sec. 29.
	Survey of the Subdivision of Section 30, T. 35 S., R. 3 E., Salt Lake Meridian, Utah
	From the ¼ sec. cor. of secs. 30 and 31. N. 0° 14' E., on the N and S center line of sec. 30.
40.06	Point for the center ¼ sec. cor. of sec. 30, at intersection with the E and W center line. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T 35 S R 3 E C ¼ S 30 1981
60.33	Point for the center N 1/16 sec. cor. of sec. 30. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 35 S R 3 E C N 1/16 | S 30 C 1981
80.60	The cor. of secs. 19 and 30.
	From the ¼ sec. cor. of secs. 29 and 30. S. 89° 30' W., on the E and W center line of sec. 30.
20.10	Point for the center E 1/16 sec. cor. of sec. 30.

Survey of the Subdivision of Section 30,
T. 35 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 35 S R 3 E E 1/16 C ——— C S 30 1981
40.20	The center ¼ sec. cor. of sec. 30.
79.90	The ¼ sec. cor. of sec. 30 only, on the W. bdy. of the Tp., hereinbefore described.
	From the center E 1/16 sec. cor. of sec. 30.
	N. 0° 10' W., on the N and S center line of the NE¼ of sec. 30.
20.165	Point for the NE 1/16 sec. cor. of sec. 30, at intersection with the E and W center line of the NE¼.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base, to top of aluminum cap, mkd. T 35 S R 3 E NE 1/16 S 30 1981
	Deposit broken glass at base of aluminum post.
40.33	The E 1/16 sec. cor. of secs. 19 and 30.
	From the N 1/16 sec. cor. of secs. 29 and 30.
	S. 89° 48' W., on the E and W center line of the NE¼ of sec. 30.
19.955	Point for the NE 1/16 sec. cor. of sec. 30.
39.91	The center N 1/16 sec. cor. of sec. 30.
	Survey of the Subdivision of Section 33, T. 35 S., R. 3 E., Salt Lake Meridian, Utah
	From the standard ¼ sec. cor. of sec. 33, on the S. bdy. of the Tp., hereinbefore described.
	N. 0° 17' W., on the N and S center line of sec. 33.
40.17	Point for the center ¼ sec. cor. of sec. 33, at intersection with the E and W center line.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 35 S R 3 E C ¼ S 33 1980

☆U.S. Government Printing Office: 1980—778-251/292

Survey of the Subdivision of Section 33,
T. 35 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
	Cor. is located in 5 strand barbwire fence cor., bears N, E, S, and W.
80.36	The ¼ sec. cor. of secs. 28 and 33.
	From the ¼ sec. cor. of secs. 33 and 34.
	S. 89° 23' W., on the E and W center line of sec. 33.
40.12	The center ¼ sec. cor. of sec. 33.
80.31	The ¼ sec. cor. of secs. 32 and 33.

Survey of the Subdivision of Section 35,
T. 35 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
	From the standard ¼ sec. cor. of sec. 35, on the S. bdy. of the Tp., hereinbefore described.
	N. 6° 19' E., on the N and S center line of sec. 35.
40.07	Point for the center ¼ sec. cor. of sec. 35, at intersection with the E and W center line.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 35 S R 3 E C ¼ S 35 1981
	Set 6 ft. juniper post alongside the iron post.
81.09	The ¼ sec. cor. of secs. 26 and 35.
	From the ¼ sec. cor. of secs. 35 and 36.
	N. 89° 32' W., on the E and W center line of sec. 33.
22.12	Point for the center E 1/16 sec. cor. of sec. 35.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 35 S R 3 E E 1/16 C ——— C S 35 1981
	Raise a mound of stone, 3 ft. base, 1½ ft. high, N of cor.
	Cor. is located on E edge of draw, drains SW.
44.24	The center ¼ sec. cor. of sec. 35.
62.01	Point for the center W 1/16 sec. cor. of sec. 35.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

CHAINS	
	T 35 S R 3 E W 1/16 C ——— C S 35 1981 Set 6 ft. juniper post alongside the iron post. Cor. is located on small spur slopes E in scattered juniper trees.
79.78	The ¼ sec. cor. of secs. 34 and 35.
	From the standard E 1/16 sec. cor. of sec. 35, on the S. bdy. of the Tp., hereinbefore described. N. 9° 22' E., on the N and S center line of the SE¼ of sec. 35.
40.10	The center E 1/16 sec. cor. of sec. 35.
	From the standard W 1/16 sec. cor. of sec. 35, on the S. bdy. of the Tp., hereinbefore described. N. 9° 36' E., on the N and S center line of the SW¼ of sec. 35.
40.66	The center W 1/16 sec. cor. of sec. 35.
	General Description Township 35 South, Range 3 East, is located around the town of Escalante, Utah. The elevation varies from 5500 to 7100 ft. above sea level. The soil varies from clay on the slopes to sandy loam in the valley. The SW and the NE portion in the area resurveyed is broken mountainous land with a valley lying in between, used as farm land and grazing land. The Escalante River flows from west to east through the northern portion of the township. Highway 54 enters the township in section 7, entering the town of Escalante and leaving the township in sec. 25. No mineral activity was noted in the township, but indications of coal were sighted throughout the township. The Escalante Petrified Forest State Park is located in the north and west portion of the township. The mean magnetic declination is 14° E.

☆U.S. Government Printing Office: 1980—778-251/292

397

Form 9600-11
(August 1979)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Craig P. Sylvester	Supervisory Cadastral Surveyor
Ferrel D. Reynolds	Supervisory Surveying Technician
Donzil Q. Worthington	Surveying Technician
Gary Gogos	Surveying Technician
John B. Julander	Survey Aid
Larry Judd	Survey Aid

398

CERTIFICATE OF SURVEY

(I) (~~We~~), Gail E. Reynolds, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 29th day of August, 1980, (I) ~~(We)~~ have dependently resurveyed the Seventh Standard Parallel South, through a portion of Range 3 East, the west boundary, a portion of the north and east boundaries and a portion of the subdivisional lines and surveyed the section line between sections 30 and 31, and surveyed the subdivision of sections 5, 6, 7, 9, 18, 19, 22, 27, 29, 30, 33, and 35 of Township 35 South, Range 3 East

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

October 3, 1983
(Date)

Gail E Reynolds
(Cadastral Surveyor)
Supervisory

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Denver, Colorado

The foregoing field notes of the dependent resurvey of the Seventh Standard Parallel South, through a portion of Range 3 East, the west boundary, a portion of the north and east boundaries and a portion of the subdivisional lines and the survey of the section line between sections 30 and 31, the survey of the subdivision of sections 5, 6, 7, 9, 18, 19, 22, 27, 29, 30, 33, and 35 of Township 35 South, Range 3 East, Salt Lake Meridian, Utah

executed by Gail E. Reynolds, Supervisory Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

November 7, 1983
(Date)

Glen B Haloff
~~(Chief, Cadastral Survey Examination and Approval Staff)~~
Chief Cadastral Surveyor for Utah

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief, Cadastral Survey Examination and Approval Staff)~~
Chief Cadastral Surveyor for Utah

Form 9600-9
(December 1979)
(formerly 9180-6)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

R606
Page 399
399

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF A PORTION OF THE SOUTH BOUNDARY,

THE EAST BOUNDARY

AND A PORTION OF THE SUBDIVISIONAL LINES

AND

THE SUBDIVISIONAL SURVEY OF SECTIONS 12, 13, 26, AND 35

OF

TOWNSHIP 8 SOUTH, RANGE 3 EAST

Of the Salt Lake Meridian,

In the State of Utah.

EXECUTED BY

Gail E. Reynolds Supervisory Cadastral Surveyor

Under special instructions dated April 25, 19 80, approved April 28, 1980.

_____, which provided for the surveys included under U.S. Survey/Group Number 599, and assignment instructions dated April 28, 19 80.

Survey commenced May 12, 19 80

Survey completed October 3, 19 81

400

INDEX DIAGRAM

Township 8 South, Range 3 East,

6	5	4	3	2	1 10 18
7	8	9	10	11 17	12 9 16
18	17	16	15	14 16	13 8 15
19	20	21	22	23 15 20	24 7 14
30	29	28	27 20	26 13 19	25 6 13
31	32	33	34 18 2	35 12 3	36 5 4 4

Subdivision of Section 12 - Page 21
Subdivision of Section 13 - Page 25
Subdivision of Section 26 - Page 25
Subdivision of Section 35 - Page 26

GPO 855-927

Township 8 South, Range 3 East, Salt Lake Meridian, Utah

CHAINS

The following field notes are those of the dependent resurvey of a portion of the south boundary, the east boundary and a portion of the subdivisional lines and the subdivisional survey of sections 12, 13, 26, and 35 of Township 8 South, Range 3 East of the Salt Lake Meridian, Utah.

History of Surveys

	Surveyed by		Retr. or Resurveyed by	
EAST BOUNDARY				
N. 3 miles	J.T. Breckon	1891		
S. 3 miles	S. and J. Stewart	1899		
SOUTH BOUNDARY				
Portion	C.L. Craig	1856		
Portion	E.H. Hesse	1883		
Portion			E.H. Hesse	1883
E. 1 mile	J.T. Breckon	1891		
East 1/2 mile			A.J. Stewart	1899
E. 1 mile			A.J. Stewart	1914
SUBDIVISION				
Portion	C.L. Craig	1856		
Portion			A.J. Stewart	1872
Portion	J.T. Breckon	1891		
Portion			J.T. Breckon	1891
Portion	S. and J. Stewart	1899		

These surveys were executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and Special Instructions dated April 25, 1980.

The direction of the lines of this survey were determined by reference to true meridians established on line by direct solar observations. The lines were carried forward by sustained angulation, being supplemented by other solar observations taken throughout the progress of the survey.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the southwest corner of Township 8 South, Range 4 East, was computed by using an existing tie to U.S.C. and G.S. triangulation station "Heaven", from the SE cor. of section 31, T. 7 S., R. 4 E.

Latitude 40° 03' 40.89" N. Longitude 111° 32' 29.15" W.

The mean magnetic declination is 14 3/4° E.

CHAINS

Dependent Resurvey of a Portion of the South Boundary,
T. 8 S., R. 3 E., Salt Lake Meridian, Utah

(Reestablishment of the Surveys Executed by
C.L. Craig in 1856 and E.H. Hesse in 1883 and the
Resurvey Executed by J.T. Breckon,
Deputy Surveyor in 1891)

Beginning at the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., monumented with a Utah County brass cap, set flush with the ground in concrete with a sandstone, 12 x 6 x 5 ins., plainly mkd. 3 notches on E and W edges, lying loosely alongside. Brass cap mkd.

T 8 S R 3 E
S 33 S 34
19 66
S 4 S 3
T 9 S R 3 E

Cor. is located on E side of draw, drains N on gentle N slope in sagebrush and scattered oak brush.

S. 89° 38' E., bet. secs. 3 and 34.

Over mountainous land, through sagebrush and oak brush.

38.30 Canal, 1.00 ch. wide, 4 ft. deep, drains NW.

38.82 Point for the ¼ sec. cor. of secs. 3 and 34, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.

T 8 S R 3 E
S 34
¼
S 3
T 9 S R 3 E
1980

Cor. is located on E bank of canal in roadway.

Continue over gently rolling bench and bottom land.

77.64 Point for the cor. of secs. 2, 3, 34, and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 8 S R 3 E
S 34 | S 35
S 3 | S 2
T 9 S R 3 E
1980

Cor. is located on nearly level pasture land on S side of Diamond Fork River.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS

S. 89° 38' E., bet. secs. 2 and 35.

Over bottom land and steep mountainous land, through sagebrush and scattered oak brush.

19.41 Point for the W 1/16 sec. cor. of secs. 2 and 35.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 8 S R 3 E
W 1/16 S 35 / S 2
T 9 S R 3 E
1980

from which

A cedar, 6 ins. diam., bears S. 10° W., 3 lks. dist., mkd. S2 BT.

Cor. is located on steep SW slope in sagebrush and scattered cedar trees.

38.82 Point for the ¼ sec. cor. of secs. 2 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to shale rock, and in a mound of stone, 3½ ft. base, to top of aluminum cap, mkd.

T 8 S R 3 E
¼ S 35 / S 2
T 9 S R 3 E
1980

Cor. is located on steep spur ridge, slopes SW in native grasses.

77.64 Point for the cor. of secs. 1, 2, 35, and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base, to top of aluminum cap, mkd.

T 8 S R 3 E
S 35 | S 36
S 2 | S 1
T 9 S R 3 E
1980

Cor. is located on steep S slope in the northeast cor. of a small opening in maple and oak brush.

(Reestablishment of the Survey Executed by J.T. Breckon in 1891, the Resurvey Executed by Stewart and Stewart in 1899, and the Retracement Executed A.J. Stewart, Deputy Surveyor, in 1914)

404

Dependent Resurvey of a Portion of the South Boundary,
T. 8 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
	S. 88° 23' E., bet. secs. 1 and 36.
	Over steep mountainous land, through dense maple and oak brush.
38.95	Point for the ¼ sec. cor. of secs. 1 and 36, at proportionate distance; the original corner, a quartzite stone, 15 x 9 x 6 ins., dimly mkd. was found lying loose on the ground.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.
	T 8 S R 3 E ¼ S 36 / S 1 T 9 S 1980
	Deposit the mkd. stone alongside the aluminum post.
	Cor. is located on steep S slope in dense oak and maple growth.
77.88	Point for the cor. of Tps. 8 and 9 S., R. 3 E. only, hereinafter described.

Dependent Resurvey of a Portion of the West Boundary,
T. 8 S., R. 4 E., Salt Lake Meridian, Utah

(Reetablishment of the Survey Executed by
Stewart and Stewart in 1899 and the Resurvey Executed
by A.J. Stewart in 1914)

CHAINS	
	From the SW Tp. cor. of T. 8 S., R. 4 E., monumented with an iron post, 3 ins. diam., set and mkd. as described in the official record of the 1914 resurvey field notes of T. 9 S., R. 4 E., Salt Lake Meridian, Utah.
	N. 0° 29' E., along the W. bdy. of sec. 31.
	Over mountainous land, through dense maple and oak brush.
20.80	Point for the cor. of Tps. 8 and 9 S., R. 3 E., at proportionate distance; there is no remaining evidence of the original corner.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.
	T 8 S R 3 E R 4 E S 36 / S 1 | S 31 T 9 S 1980
	Cor. is located on steep SW slope in dense chokecherry and oak brush.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS

Dependent Resurvey of the East Boundary of
T. 8 S., R. 3 E., Salt Lake Meridian, Utah

(Reestablishment of the Survey Executed by
Stewart and Stewart, Deputy Surveyors in 1899)

N. 0° 29' E., along the E. bdy. of sec. 36.

Over mountainous land, through dense chokecherry, maple, and oak brush.

13.19 Point for the ¼ sec. cor. of sec. 31 only, T. 8 S., R. 4 E., at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

```
      T 8 S
R 3 E  R 4 E
       | ¼
       | S 31
      1980
```

Cor. is located on W slope in chokecherry and oak brush.

41.24 Point for the ¼ sec. cor. of sec. 36 only.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

```
      T 8 S
R 3 E  R 4 E
    ¼ |
 S 36 |
      1980
```

Cor. is located on steep W slope in buckbrush.

47.18 Point for the cor. of secs. 30 and 31 only, T. 8 S., R. 4 E., at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

```
      T 8 S
R 3 E  R 4 E
       | S 30
 S 36  |-------
       | S 31
      1980
```

Cor. is located in small draw, drains SW in oak brush.

82.48 Point for the closing cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

406

Dependent Resurvey of the East Boundary of
T. 8 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
	T 8 S R 3 E R 4 E C S 25 | S 30 C S 36 | 1980 from which A douglas fir, 12 ins. diam., bears S. 6° W., 36 lks. dist., mkd. T8S R3E S36 CC BT. Raise a mound of stone, 3½ ft. base, 2 ft. high, W of cor. Cor. is located on steep N slope in small opening in pine and aspen growth.
	N. 0° 29' E., along the E. bdy. of sec. 25. Over mountainous land, through pine, aspen, maple, and oak brush.
6.05	Point for the ¼ sec. cor. of sec. 30 only, T. 8 S., R. 4 E., at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 8 S R 3 E R 4 E | ¼ | S 30 1980 Cor. is located on NW slope in aspen and dense undergrowth.
8.50	Crowd Canyon, drains W.
40.50	Ridge, bears E and W.
41.29	Point for the ¼ sec. cor. of sec. 25 only. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T 8 S R 3 E R 4 E ¼ | S 25 | 1980 from which A fir, 20 ins. diam., bears S. 45° E., .005 lks. dist., mkd BT.
47.39	Point for the cor. of secs. 19 and 30 only, T. 8 S., R. 4 E., at proportionate distance; there is no remaining evidence of the original corner.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 8 S R 3 E R 4 E S 25 | S 19 | S 30 1980 from which A balsam pine, 10 ins. diam., bears N. 71° E., 44 lks. dist., mkd. T8S R4E S19 BT. A balsam pine, 10 ins. diam., bears S. 39° E., 9 lks. dist., mkd. T8S R4E S30 BT. A balsam pine, 14 ins. diam., bears N. 62° W., 10 lks. dist., mkd. T8S R3E S25 BT. Cor. is located on steep NW slope in balsam pine and dense undergrowth.
80.09	Draw, drains NW.
82.58	Point for the closing cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 8 S R 3 E R 4 E C S 24 | S 19 C S 25 | 1981 Cor. is located on SW slope in dense maple and oak brush.
	N. 0° 29' E., along the E. bdy. of sec. 24. Over mountainous land, through pine, aspen, maple, and oak brush.
0.50	Small spur, slopes W.
2.00	Draw, drains NW.
41.34	Point for the ¼ sec. cor. of sec. 24 only. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 8 S R 3 E R 4 E ¼ | S 24 | 1981 Cor. is located on small spur, slopes W in bottom of draw, drains W in dense maple and oak brush.

CHAINS

82.68 Point for the cor. of secs. 13 and 24 only, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 8 S
R 3 E | R 4 E
S 13 / S 24 | S 18
1981

Cor. is located on small spur, slopes NW in draw, drains NW in maple and oak brush.

(Reestablishment of the Survey Executed by
J.T. Breckon, Deputy Surveyor in 1891)

N. 0° 29' E., along E. bdy. of sec. 13.

Over mountainous land, through maple and oak brush.

41.34 Point for the ¼ sec. cor. of sec. 13 only, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 8 S
R 3 E | R 4 E
¼ |
S 13 |
1980

Cor. is located on SW slope in scattered oak brush.

42.00 Spur, ridge, bears E and W.

81.75 Paved road, bears E and W on N side of Maple Creek, drains W.

82.68 The cor. of secs. 12 and 13 only, monumented with a limestone, 24 x 12 x 8 ins., firmly set 18 ins. in the ground and dimly mkd. 2 notches on N and 4 notches on S edges.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 8 S
R 3 E | R 4 E
S 12 / S 13 | S 7
1980

Cor. is located on gentle S slope in scattered patches of oak brush.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	N. 0° 03' W., along the E. bdy. of sec. 12.
	Over mountainous land, through oak brush and maple.
5.64	The beginning cor. of Edwin M. Whiting private land claim monumented with a Utah County monument extending 8 ins. out of the ground in concrete, improperly mkd. T8S Rs. 3 and 4 E., Secs. 12 and 13 and CC on east side, dated 1961. Also found a slate stone, 16 x 8 x 8 ins., plainly mkd. BEGCORE MW lying alongside the Utah County monument.
	At the corner point
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.
	T 8 S R 3 E R 4 E S 12 | S 7 | EMW 1980
	Deposit the stone cor. and Utah County monument alongside the aluminum post.
	Cor. is located on S slope in oak brush.
	N. 0° 13' W., along the E. bdy. of sec. 12, beginning new measurement.
	Over mountainous land, through maple and oak brush.
13.995	Point for the S 1/16 sec. cor. of sec. 12 only. Not monumented.
33.63	Point for the ¼ sec. cor. of sec. 12 only, at proportionate distance; there is no remaining evidence of the original corner.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.
	T 8 S R 3 E R 4 E ¼ | S 12 | 1980
	Cor. is located on steep W slope in dense oak brush.
39.19	Point for the closing cor. of secs. 6 and 7, T. 8 S., R. 4 E., at proportionate distance; there is no remaining evidence of the original corner.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.
	T 8 S R 3 E R 4 E S 12 | S 6 C | S 7 C 1982

410

Dependent Resurvey of the East Boundary of
T. 8 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
	Cor. is located on steep W slope in native grasses.
53.25	Point for the N 1/16 sec. cor. of sec. 12 only. Not monumented.
72.87	Point for the cor. of secs. 1 and 12 only, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 5½ ft. base, to top of aluminum cap, mkd. T 8 S R 3 E | R 4 E S 1 | S 6 S 12 | 1980 Cor. is located on W slope in native grasses.
	N. 0° 13' W., along the E. bdy. of sec. 1. Over mountainous land, through maple and oak brush.
5.56	Point for the ¼ sec. cor. of sec. 6 only, T. 8 S., R. 4 E., at proportionate distance. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 8 S R 3 E | R 4 E | ¼ | S 6 1982 Cor. is located on steep N slope in scrub oak brush.
19.62	Point for the S 1/16 sec. cor. of sec. 1 only. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 8 S R 3 E | R 4 E S 1/16 | S 1 | 1982 Cor. is located on steep NW slope in dense maple and oak.
25.335	Point for the N 1/16 sec. cor. of sec. 6 only, T. 8 S., R. 4 E. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 8 S R 3 E | R 4 E | N 1/16 | S 6 1982

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	Cor. is located on steep N slope in maple and oak brush.
35.00	Base of mountain, bears NE and SW; thence over nearly level land.
39.24	The ¼ sec. cor. of sec. 1 only, monumented with a ½ in. rebar and a survey stake, mkd. ¼ cor. and set in a mound of stone. This point is accepted as a careful and faithful perpetuation of the position of the original corner.
	At the corner point
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.
	T 8 S R 3 E R 4 E ¼ | S 1 | 1981
	Set 6 ft. steel fence post alongside cor. located on nearly level land in police pistol range and Fish and Game experimental farm.
	N. 0° 09' W., beginning new measurement.
	Over nearly level land.
5.77	Point for the 80 1/16 sec. cor. of sec. 6 only, T. 8 S., R. 4 E.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T 8 S R 3 E R 4 E | 80 | 1/16 | S 6 1982
	Set a 4 x 4 in. post, 5 ft. long, alongside the corner.
6.25	Hobble Creek, 2 ft. deep, 70 lks. wide, drains W; over mountainous land.
25.44	Point for the 100 1/16 sec. cor. of sec. 6 only, T. 8 S., R. 4 E.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.
	T 8 S R 3 E R 4 E | 100 | 1/16 | S 6 1982
	Cor. is located on steep S slope in native grasses.

Dependent Resurvey of the East Boundary of
T. 8 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
39.53	The cor. of Tps. 7 and 8 S., Rs. 3 and 4 E., an aluminum post, 2½ ins. diam., extending 4 ins. out of the ground, set and mkd. as described in the official record of the 1979 resurvey of T. 7 S., R. 3 E., Salt Lake Meridian, Utah.

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 8 S. R. 4 E., Salt Lake Meridian, Utah

(Restoring the Survey Executed by
J.T. Breckon, Deputy Surveyor in 1891)

From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., hereinbefore described.

N. 0° 50' E., bet. secs. 35 and 36.

Over mountainous land, through pine, aspen, maple, and oak brush.

40.90 Point for the ¼ sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base, to top of aluminum cap, mkd.

T 8 S R 3 E
¼
S 35 | S 36
1981

Cor. is located on spur ridge, slopes W in oak brush.

61.35 Point for the N 1/16 sec. cor. of secs. 35 and 36. Not monumented.

81.80 Point for the cor. of secs. 25, 26, 35, and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 8 S R 3 E
S 26 | S 25
S 35 | S 36
1980

Cor. is located on steep W slope in dense oak brush.

(Restoring the Survey Executed by
Stewart and Stewart, Deputy Surveyors in 1899)

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	S. 88° 53' E., bet. secs. 25 and 36.
	Over mountainous land, through pine, aspen, maple, and oak brush.
38.67	Point for the ¼ sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.
	T 8 S R 3 E ¼ S 25 / S 36 1981
	from which
	An aspen, 7 ins. diam., bears S. 30° W., 13 lks. dist., mkd. ¼ S36 BT.
	An aspen, 7 ins. diam., bears N. 20° W., 30 lks. dist., mkd. ¼ S25 BT.
	Cor. is located on steep NW slope in aspen and dense undergrowth.
77.34	The closing cor. of secs. 25 and 36, on the E. bdy. of the Tp., hereinbefore described.
	(Restoring the Survey Executed by J.T. Breckon, Deputy Surveyor in 1891)
	From the cor. of secs. 25, 26, 35, and 36.
	N. 0° 29' E., bet. secs. 25 and 26.
	Over mountainous land, through aspen, pine, maple, and oak brush.
20.45	Point for the S 1/16 sec. cor. of secs. 25 and 26.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.
	T 8 S R 3 E S 1/16 S 26 | S 25 1981
	Cor. is located on steep N slope in dense oak and maple.
21.20	Draw in bottom of Crowd Canyon, drains W.
40.90	Point for the ¼ sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.

414

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 8 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd. T 8 S R 3 E ¼ S 26 | S 25 1981 Cor. is located on steep SW slope in native grasses and scattered patches of oak brush.
81.30	Spur, slopes W.
81.80	Point for the cor. of secs. 23, 24, 25, and 26, at proportionate distance; a sandstone, 24 x 10 x 6 ins., plainly mkd. 1 notch on E and 2 notches on S edges was found lying loose on the ground. Set an aluminum post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 8 S R 3 E S 23 | S 24 S 26 | S 25 1981 Deposit the mkd. stone alongside the aluminum post. Cor. is located on NW slope in scrub oak brush.
	(Reestablishment of the Survey Executed by Stewart and Stewart in 1899)
	S. 89° 28' E., bet. secs. 24 and 25. Over mountainous land, through aspen, pine, maple, and oak brush.
38.66	Point for the ¼ sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base, to top of aluminum cap, mkd. T 8 S R 3 E ¼ S 24 S 25 1981 Cor. is located on steep N slope in dense balsam pine.
77.32	The closing cor. of secs. 24 and 25, hereinbefore described.
	(Reestablishment of the Survey Executed by J.T. Breckon, Deputy Surveyor in 1891)

☆U.S. Government Printing Office: 1980—778-251/292

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 8 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
	From the cor. of secs. 23, 24, 25, and 26.
	N. 4° 27' E., bet. secs. 23 and 24.
	Over mountainous land, through pine, maple, and oak brush.
41.02	The ¼ sec. cor. of secs. 23 and 24, monumented with a Utah County brass cap, 3 ins. diam., set in concrete extending 4 ins. out of the ground, and in a collar of stone. Accepted as the best available evidence of the original corner position. Brass cap mkd. T 8 S R 3 E S 23 | S 24 | ¼ 1966 Cor. is located on spur ridge, bears E and W in opening of scattered patches of oakbrush.
	N. 1° 46' W., beginning new measurement.
	Over mountainous land, through maple and oak brush.
40.51	The cor. of secs. 13, 14, 23, and 24, monumented with a Utah County brass cap, 3 ins. diam., set in concrete even with the ground in fence cor., 4 strand barbwire, bears irregularly E, S, and W and is accepted as the best available evidence of the original corner position. Brass cap mkd. T 8 S R 3 E S 14 | S 13 S 23 | S 24 1963 Cor. is located on W slope in oak brush.
	From the cor. of secs. 13 and 24, on the E. bdy. of the Tp., hereinbefore described.
	S. 89° 35' W., bet. secs. 13 and 24.
	Over mountainous land, through pine, maple, and oak brush.
38.03	Point for the ¼ sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 8 S R 3 E ¼ S 13 S 24 1980 Cor. is located on steep NW slope in dense maple and oak brush and scattered pine.
76.06	The cor. of secs. 13, 14, 23, and 24.

CHAINS	
	N. 0° 42' W., bet. secs. 13 and 14.
	Over rolling bench land, through dense maple and oak brush.
19.87	Point for the S 1/16 sec. cor. of secs. 13 and 14.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 8 S R 3 E S 1/16 S 14 | S 13 1980
	Cor. is located S. 78° 09' E., 0.146 chs. dist., from a fence cor., a four strand barbwire, bears E and a 8 ft. chain link bears N, in maple and oak.
39.74	The ¼ sec. cor. of secs. 13 and 14, monumented with a Utah County brass cap set in concrete in net wire fence cor., bears N, S and W, with cap mkd. T 8 S R 3 E ¼ S 14 | S 13 1968
	Cor. is located on NE cor. of cultivated land in oak brush and is accepted as the best available evidence of the original corner position.
	N. 0° 10' W., beginning new measurement.
	Over rolling bench land and pasture.
40.31	The cor. of secs. 11, 12, 13, and 14, monumented with an iron post, 2 ins. diam., extending 12 ins. out of a mound of stone, 4½ ft. base, with a G.L.O. type brass cap mkd. T 8 S R 3 E S 11 | S 12 S 14 | S 13 1915
	Cor. is located on N edge of dirt road, bears E and W and on S edge of orchard, and is accepted as the best available evidence of the original corner position.
	From the cor. of secs. 12 and 13 only, on the E. bdy. of the Tp., hereinbefore described.
	S. 87° 37' W., bet. secs. 12 and 13.
	Over creek bottom and bench land, through maple and oak brush.
18.795	Point for the E 1/16 sec. cor. of secs. 12 and 13.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T 8 S R 3 E E 1/16 S 12 / S 13 1980 Cor. is located on steep S slope of bank of dry Maple Creek, drains W and 93 lks. S of paved road, bears E and W irregularly in maple and oak brush.
37.59	The ¼ sec. cor. of secs. 12 and 13, monumented with a 2 in. iron post, extending 10 ins. out of the ground and in a collar of stone, with G.L.O. type brass cap mkd. T 8 S R 3 E ¼ S 12 / S 13 1915 Cor. is located on steep N slope in old downed fence line, bears E and W in oak brush, and is accepted as the best available evidence of the corner position.
	S. 87° 40' W., beginning new measurement. Over bench land and orchard.
39.79	The cor. of secs. 11, 12, 13, and 14.
	N. 0° 35' W., bet. secs. 11 and 12. Over orchards and residential areas.
39.96	The ¼ sec. cor. of secs. 11 and 12, monumented with a Utah County brass cap set in concrete flush with the ground. This cor. is accepted as the best available evidence of the original cor. position. Brass cap mkd. T 8 S R 3 E ¼ COR S 11 | S 12 1955 Cor. is located on W side of paved road, bears N and S.
	N. 0° 14' W., beginning new measurement. Over residential and orchard areas.
40.40	The cor. of secs. 1, 2, 11, and 12, monumented with a Utah County brass cap set in concrete 8 ins. below surface of paved road, bears E and W, in 10 in. manhole with lid over top. This cor. is accepted as the best available evidence of the original corner position. Brass cap mkd.

CHAINS

T 8 S R 3 E
S 2 | S 1
S 11 | S 12
1955

Cor. is located near center of 800 N., Mapleton, Utah.

(Reestablishment of the Survey of A.J. Stewart in 1872 and the Resurvey of E. Breckon in 1891)

N. 88° 24' E., bet. secs. 1 and 12.

Over residential and bench land area.

40.08 The ¼ sec. cor. of secs. 1 and 12, monumented with an iron post, 2 ins. diam., extending 12 ins. out of the ground and in a collar of stone to a G.L.O. type brass cap. This cor. is accepted as the best available evidence of the original corner position. Brass cap mkd.

T 8 S R 3 E
¼ S 1
S 12
1915

Cor. is located on nearly level bench land in oak brush.

N. 89° 39' E., beginning new measurement.

Over mountainous land, through oak brush.

18.765 Point for the E 1/16 sec. cor. of secs. 1 and 12.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap mkd.

T 8 S R 3 E
E 1/16 S 1
S 12
1980

Cor. is located on W slope in scrub oak brush.

37.53 The cor. of secs. 1 and 12, hereinbefore described.

(Reestablishment of the Survey of C.L. Craig in 1856 and the Resurvey of J. Breckon in 1891)

From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., hereinbefore described.

N. 4° 05' E., bet. secs. 34 and 35.

Over bottom land, pasture and bench land, through maple and oak brush.

40.24 The ¼ sec. cor. of secs. 34 and 35, monumented with a Utah County brass cap set in concrete, extending 8 ins. out of the ground. This cor. is accepted as the best available evidence of the original corner position. Brass cap mkd.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	T 8 S R 3 E ¼ S 34 | S 35 1966 Cor. is located on W slope in oak brush.
	N. 1° 52' W., beginning new measurement.
1.25	Draw, drains W.
40.04	The cor. of secs. 26, 27, 34, and 35, monumented with an iron post, 2½ ins. diam., 36 ins. long, set 16 ins. in the ground and properly mkd. and dated 1916. Also found sandstone, 10 x 8 x 5 ins., mkd. 1 notch on S and 2 notches on E edges alongside the iron post. Iron post in badly deteriorated condition. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. T 8 S R 3 E S 27 | S 26 S 34 | S 35 1980 Deposit the mkd. stone and the iron post alongside the iron post. Cor. is located on bench land in scattered clumbs of oak.
	From the cor. of secs. 25, 26, 35, and 36. S. 89° 09' W., bet. secs. 26 and 35. Over mountainous land, through maple and oak brush.
19.31	Point for the E 1/16 sec. cor. of secs. 26 and 35. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 8 S R 3 E E 1/16 S 26 S 35 1980 Cor. is located on steep NW slope in oak brush.
38.62	Point for the ¼ sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

420

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 8 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
	T 8 S R 3 E ¼ S 26 S 35 1980
	Cor. is located on steep NW slope in scrub oak brush.
77.24	The cor. of secs. 26, 27, 34, and 35.
	N. 0° 12' W., bet. secs. 26 and 27.
	Over rolling bench land, through maple and oak brush.
40.80	The ¼ sec. cor. of secs. 26 and 27, monumented with an iron post, 2 ins. diam., extending 12 ins. out of the ground with a cobble stone, 15 x 7 x 3 ins., plainly mkd. ¼ on W face alongside. Brass cap mkd.
	¼ S 27 | S 26 1916
	Cor. is located on gentle W slope in netwire fence line bears N and S in oak brush.
	N. 0° 06' W., beginning new measurement.
	Over rolling bench land, through maple and oak brush.
40.98	The cor. of secs. 22, 23, 26, and 27, monumented with an iron post, 2 ins. diam., extending 12 ins. out of the ground with a G.L.O. type brass cap. This cor. is accepted as the best available evidence of the original corner position. Brass cap mkd.
	T 8 S R 3 E S 22 | S 23 S 27 | S 26 1916
	Cor. is located in netwire fence cor., bears E, S, and W on NE slope in oak brush.
	From the cor. of secs. 23, 24, 25, and 26.
	S. 88° 50' W., bet. secs. 23 and 26.
	Over mountain land, through maple and oak brush.
38.66	The ¼ sec. cor. of secs. 23 and 26, monumented with a Utah County brass cap set in concrete, extending 6 ins. out of the ground, with a sandstone, 12 x 8 x 1 ins., plainly mkd. ¼ on N face alongside. Brass cap mkd.
	T 8 S R 3 E S 23 ¼ S 26 COR 1968
	Cor. is located in netwire fence cor., bears N, E, and W, on W slope in oak brush.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	S. 89° 28' W., beginning new measurement.
	Over rolling bench land, through maple and oak brush.
39.47	The cor. of secs. 22, 23, 26, and 27.
	Survey of the Subdivision of Section 12, T. 8 S., R. 3 E., Salt Lake Meridian, Utah
	From the ¼ sec. cor. of secs. 12 and 13.
	N. 0° 11' W., on the N and S center line of sec. 12.
19.82	Point for the center S 1/16 sec. cor. of sec. 12.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	C S 12 | S 1/16 C 1980
	Cor. is located on spur ridge, slopes N in scrub oak brush.
24.775	Point for the center south north south 1/256 sec. cor. of sec. 12.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	C-S-N-S 1/256 S 12 1980
	Cor. is located on W slope in oak brush.
29.73	Point for the center north south 1/64 sec. cor. of sec. 12. Not monumented.
39.64	Point for the center ¼ sec. cor. of sec. 12, at intersection with the E and W center line.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 8 S R 3 E C ¼ S 12 1980
	Raise a mound of stone, 3 ft. base, 1½ ft. high, N of cor.
59.75	Point for the center N 1/16 sec. cor. of sec. 12. Not monumented.
79.86	The ¼ sec. cor. of secs. 1 and 12.

422

Survey of the Subdivision of Section 12,
T. 8 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
	From the ¼ sec. cor. of sec. 12 only, on the E. bdy. of the Tp., hereinbefore described.
	S. 88° 09' W., on the E and W center line of sec. 12.
18.78	Point for the center E 1/16 sec. cor. of sec. 12.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	E 1/16 C ——— C S 12 1980
	Raise a mound of stone, 3 ft. base, 1½ ft. high, N of cor.
	Cor. is located on W slope in opening in oak brush.
28.17	Point for the center west east 1/64 sec. cor. of sec. 12. Not monumented.
37.56	The center ¼ sec. cor. of sec. 12.
77.63	The ¼ sec. cor. of secs. 11 and 12.
	From the center E 1/16 sec. cor. of sec. 12.
	N. 0° 12' W., on the N and S center line of the NE¼ of sec. 12.
9.935	Point for the center south northeast 1/64 sec. cor. of sec. 12.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.
	C-S-NE 1/64 S 12 1980
	Raise a mound of stone, 3 ft. base, 1 ft. high, N of cor.
19.87	True point for the NE 1/16 sec. cor. of sec. 12, at intersection with the E and W center line of the NE¼ of sec. 12, falls on point of outcrop, 4 ft. high, and is impractical to monument.
20.17	Point selected for the witness cor. to the NE 1/16 sec. cor. of sec. 12.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.
	W C ↓ NE 1/16 S 12 1980

☆U.S. Government Printing Office: 1980—778-251/292

Survey of the Subdivision of Section 12,
T. 8 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
	Cor. is located on SW slope in nearly bare area.
29.80	Point for the center north northeast 1/64 sec. cor. of sec. 12.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of sotne, with aluminum cap mkd. C-N-NE 1/64 S 12 1980
	Cor. is located on SW slope in maple and oak brush, 20 lks. N of small draw, drains NW and 35 lks. E of same, 1.20 chs. S of main draw, drains W.
39.73	The E 1/16 sec. cor. of secs. 1 and 12.
	From the point for the N 1/16 sec. cor. of sec. 12 only on the E. bdy. of the Tp., hereinbefore described.
	S. 88° 54' W., on the E and W center line of the NE¼ of sec. 12.
18.775	True point for the NE 1/16 sec. cor. of sec. 12.
37.55	Point for the center N 1/16 sec. cor. of sec. 12.
	From the E 1/16 sec. cor. of secs. 12 and 13.
	N. 0° 11' W., on the N and S center line of the SE¼ of sec. 12.
19.73	Point for the SE 1/16 sec. cor. of sec. 12, at intersection with the E and W center line of the SE¼ of sec. 12.
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd. SE 1/16 S 12 1980
	Cor. is located on SW slope in native grasses.
29.59	Point for the center north southeast 1/64 sec. cor. of sec. 12. Not monumented.
39.45	The center E 1/16 sec. cor. of sec. 12.
	From point for the S 1/16 sec. cor. of sec. 12, on the E. bdy. of the Tp., hereinbefore described.
	S. 87° 52' W., on the E and W center line of the SE¼ of sec. 12.
18.80	The SE 1/16 sec. cor. of sec. 12.
28.20	Point for the center west southeast sec. cor. of sec. 12.

424

Survey of the Subdivision of Section 12,
T. 8 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. C-W-SE 1/64 S 12 1980 Raise a mound of stone, 3 ft. base, 1½ ft. high, N of cor. Cor. is located on W slope in scrub oak brush.
37.60	The center S 1/16 sec. cor. of sec. 12.
	From the center west 1/64 sec. cor. of the SE¼ of sec. 12. N. 0° 12' W., on the N and S center line of the NW¼ of the SE¼ of sec. 12.
4.94	Point for the center south northwest southeast 1/256 sec. cor. of sec. 12. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. C-S-NW-SE 1/256 S 12 1980 Cor. is located on N slope in dense oak brush on S edge of draw, drains W.
9.88	Point for the NW-SE 1/64 sec. cor. of sec. 12, at intersection with the E and W center line of the NW¼ of the SE¼ of sec. 12. Not monumented.
19.76	Point for the center west east 1/64 sec. cor. of sec. 12.
	From the point for the center north southeast 1/64 sec. cor. of sec. 12. S. 88° 00' W., along the E and W center line of the NW¼ of the SE¼ of sec. 12.
9.395	The point for the northwest southeast 1/64 sec. cor. of sec. 12.
18.79	The point for the center north south 1/64 sec. cor. of sec. 12.
	From the center south northwest southeast 1/256 sec. cor. of sec. 12. S. 87° 56' W., along the E and W center line of the SW¼ of the NW¼ of the SE¼ of sec. 12.
9.395	The center south north south 1/256 sec. cor. of sec. 12.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	Survey of the Subdivision of Section 13, T. 8 S., R. 3 E., Salt Lake Meridian, Utah
	From the ¼ sec. cor. of sec. 13 and 24. N. 0° 48' E., on the N and S center line of sec. 13.
20.28	Point for the S 1/16 sec. cor. of sec. 13. Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 8 S R 3 E C S 1/16 | S 13 C 1980 Cor. is located on steep N slope in maple, oak brush and scattered pine.
40.56	Point for the center ¼ sec. cor. of sec. 13, at intersection with the E and W center line of sec. 13. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 8 S R 3 E C ¼ S 13 1980 Cor. is located on steep W slope in oak brush.
81.40	The ¼ sec. cor. of secs. 12 and 13.
	From the ¼ sec. cor. of sec. 13 only, on the E. bdy. of the Tp., hereinbefore described. S. 88° 23' W., on the E and W center line of sec. 13.
37.81	The center ¼ sec. cor. of sec. 13.
76.90	The ¼ sec. cor. of secs. 13 and 14.
	From the center S 1/16 sec. cor. of sec. 13. S. 88° 59' W., on the E and W center line of the SW¼ of sec. 13.
38.56	The S 1/16 sec. cor. of secs. 13 and 14.
	Survey of the Subdivision of Section 26, T. 8 S., R. 3 E., Salt Lake Meridian, Utah
	From the ¼ sec. cor. of secs. 26 and 35. N. 0° 27' E., on the N and S center line of sec. 26.
20.425	Point for the center S 1/16 sec. cor. of sec. 26. Not monumented.

426

Survey of the Subdivision of Section 26,
T. 8 S., R. 3 E., Salt Lake Meridian, Utah

CHAINS	
40.85	Point for the center ¼ sec. cor. of sec. 26, at intersection with the E and W center line of sec. 26. Set an aluminum post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base, to top of aluminum cap, mkd. T 8 S R 3 E C ¼ S 26 1981 Cor. is located on steep S slope in cheat grass.
81.57	The ¼ sec. cor. of secs. 23 and 26.
	From the ¼ sec. cor. of secs. 25 and 26. S. 89° 05' W., on the E and W center line of sec. 26.
19.32	Point for the center E 1/16 sec. cor. of sec. 26. Not monumented.
38.64	The center ¼ sec. cor. of sec. 26.
77.72	The ¼ sec. cor. of secs. 26 and 27.
	From the E 1/16 sec. cor. of secs. 26 and 35. N. 0° 28' E., on the N and S center line of the SE¼ of sec. 26.
20.435	Point for the SE 1/16 sec. cor. of sec. 26, at intersection with the E and W center line of the SE¼ of sec. 26. Set an aluminum post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 8 S R 3 E SE 1/16 S 26 1981 Cor. is located on steep N slope in dense oak brush.
40.87	Point for the center E 1/16 sec. cor. of sec. 26.
	From the S 1/16 sec. cor. of secs. 25 and 26. S. 89° 07' W., on the E and W center line of the SE¼ of sec. 26.
19.315	The SE 1/16 sec. cor. of sec. 26.
38.63	Point for the center S 1/16 sec. cor. of sec. 26.
	Survey of the Subdivision of Section 35, T. 8 S., R. 3 E., Salt Lake Meridian, Utah
	From the ¼ sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp., hereinbefore described. N. 0° 58' E., on the N and S center line of sec. 35.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
40.52	Point for the center ¼ sec. cor. of sec. 35, at intersection with the E and W center line of sec. 35. Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 8 S R 3 E C ¼ S 35 1980 Cor. is located on NW slope in maple and oak brush.
60.755	Point for the center N 1/16 sec. cor. of sec. 35. Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd. C N 1/16 | S 35 C 1980 Cor. is located on NW slope in oak brush.
80.99	The ¼ sec. cor. of secs. 26 and 35.
	From the ¼ sec. cor. of secs. 35 and 36. S. 89° 47' W., on the E and W center line of sec. 35.
19.36	Point for the center E 1/16 sec. cor. of sec. 35. Not monumented.
38.72	The center ¼ sec. cor. of sec. 35.
57.04	Point for the center E 1/16 sec. cor. of sec. 35. Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 8 S R 3 E W 1/16 C ——— C S 35 1981 Cor. is located on steep W slope, 5 lks. N of small draw, drains W in oak brush.
75.36	The ¼ sec. cor. of secs. 34 and 35.
	From the point for the center E 1/16 sec. cor. of sec. 35. N. 0° 54' E., on the N and S center line of the NE¼ of sec. 35.
20.345	Point for the NE 1/16 sec. cor. of sec. 35, at intersection with the E and W center line of the NE¼ of sec. 35.

CHAINS	
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base, to top of aluminum cap, mkd. NE 1/16 S 35 1980 Cor. is located in small wash, drains W in oak brush.
40.69	The E 1/16 sec. cor. of secs. 26 and 35.
	From the point for the N 1/16 sec. cor. of secs. 35 and 36. S. 89° 29' W., on the E and W center line of the NE¼ of sec. 35.
19.335	The NE 1/16 sec. cor. of sec. 35.
38.67	The center N 1/16 sec. cor. of sec. 35.
	From the W 1/16 sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp., hereinbefore described. N. 2° 31' E., on the N and S center line of the SW¼ of sec. 35.
40.36	The center W 1/16 sec. cor. of sec. 35.
	General Description The area resurveyed within T. 8 S., R. 3 E., varies from mountainous in the east portion to nearly level in the west portion. The elevation ranges from 4700 to 9200 ft. above sea level. The vegetation consists of maple, oak, fir, aspen, and dense undergrowth. The Hobble Creek drains from east to west in the north portion of the township and the Diamond Fork River drains east to west in the south portion. The Denver and Rio Grande Western Railroad crosses the SW portion of the township Highway 89 follows the railroad up Diamond Fork Canyon. The city of Mapleton, is located in the north part of the township. An explosives manufacturing plant is located in the east portion of sec. 35. The mean magnetic declination is 14 3/4° E. as taken from the U.S.G.S. map Spanish Fork Peak.

☆U.S. Government Printing Office: 1980—778-251/292

429

Form 9600–11
(August 1979)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Jerry L. Thomas	Supervisory Cadastral Surveyor
Ronald K. Baugh	Land Surveyor
Ferrel D. Reynolds	Supervisory Surveying Technician
Donald Buhler	Surveying Technician
John Hales	Surveying Technician
John Mavor	Survey Aid
Scott McMullin	Surveying Technician
Terry Christensen	Survey Aid
Glen B. Hatch	Supervisory Cadastral Surveyor

430

CERTIFICATE OF SURVEY

(I) XXX), Gail E. Reynolds, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 25th day

of April, 19 80, (I) (XXX) have dependently resurveyed a portion of the south boundary, the east boundary, and a portion of the subdivisional lines and subdivided sections 12, 13, 26, and 35 of Township 8 South, Range 3 East

of the Salt Lake Meridian, in the State of Utah, which

are represented in the foregoing field notes as having been executed by (me), (us) XX and under (my)

XXXX (our) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in

specific manner described in the foregoing field notes.

January 17, 1984 (Date)

Gail E. Reynolds (Cadastral Surveyor)
Supervisory

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the south boundary, the east boundary, and a portion of the subdivisional lines and subdivided sections 12, 13, 26, and 35 of T. 8 S., R. 3 E. of the Salt Lake Meridian, Utah

executed by Gail E. Reynolds, Supervisory Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

January 26, 1984 (Date)

Glen B. Hatch
(~~Chief, Cadastral Survey Examination and Approval Staff~~)
Chief Cadastral Surveyor for Utah

~~CERTIFICATE OF TRANSCRIPT~~

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in

is a true copy of the original field notes.

(Date)

(~~Chief, Cadastral Survey Examination and Approval Staff~~)
Chief Cadastral Surveyor for Utah

Form 9600-9
(December 1979)
(formerly 9180-6)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

R606

431

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF A PORTION OF THE SOUTH BOUNDARY

OF T. 7 S., R. 4 E.

AND

A PORTION OF THE SUBDIVISIONAL LINES

AND

A SURVEY OF

THE SUBDIVISION OF SECTION 6,

TOWNSHIP 8 SOUTH, RANGE 4 EAST

Of the Salt Lake Meridian,

In the State of Utah.

EXECUTED BY

Gail E. Reynolds Supervisory Cadastral Surveyor

Under special instructions dated April 25, 1980, approved April 28, 1980.

_____, which provided for the surveys included under U.S. Survey/Group

Number 599, and assignment instructions dated April 28, 1980

Survey commenced June 9, 1982

Survey completed July 7, 1982

INDEX DIAGRAM

Township 8 South, Range 4 East,

2 6 4 3	2 5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision of Section 6 - Page 5

GPO 855-927

Township 8 South, Range 4 East, Salt Lake Meridian, Utah

CHAINS

The following field notes are those of a dependent resurvey of a portion of the south boundary of T. 7 S., R. 4 E., and a portion of the subdivisional lines and a survey of the subdivision of section 6 of T. 8 S., R. 4 E., Salt Lake Meridian, Utah.

History of Surveys

	Surveyed by		Retr. or Resurveyed by	
WEST BOUNDARY				
Portion	J.T. Breckon	1891		
Portion	S. and J. Stewart	1899		
NORTH BOUNDARY				
Portion	S. and J. Stewart	1899		
Portion			D.A. Cody	1971
SUBDIVISIONAL LINES				
Portion	S. and J. Stewart	1899		
PRIVATE LAND CLAIMS				
Portion	S. and J. Stewart	1899		
			D.A. Cody	1971

These surveys were executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and Special Instructions dated April 25, 1980.

The direction of the lines of this survey were determined by reference to true meridians established on line by direct solar observations on Polaris. The lines were carried forward by sustained angulation, being supplemented by other solar observations taken throughout the progress of the survey. All distances were made with electronic measuring equipment and a one chain standard and reduce to horizontal distances.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the southeast corner of section 6 was computed by using an existing tie to the U.S.C. & G.S. Triangulation Station "Heaven" from the SE cor. of section 31, T. 7 S., R. 4 E.

Latitude 40° 08' 23.34" N. Longitude 111° 30' 54.54" W.

The mean magnetic declination, as projected from the U.S.G.S. magnetic declination of 1980, is 14½° E.

434

Dependent Resurvey of a Portion of the South Boundary,
T. 7 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	Dependent Resurvey of a Portion of the South Boundary, T. 7 S., R. 4 E., Salt Lake Meridian, Utah
	(Restoring the Survey Executed by S. and J. Stewart in 1899 and the Resurvey Executed by Douglas A. Cody in 1971)
	Beginning at the closing cor. of secs. 5 and 32, Tps. 7 and 8 S., R. 4 E., identical with AP No. 12 of Tract 37, monumented with an iron post, 2½ ins. diam., firmly set protruding 6 ins. out of the ground, with brass cap mkd. as described in the official record of the 1971 resurvey.
	S. 89° 23' W., along the S. bdy. of sec. 32.
	Over valley floor, through oak and maple.
9.99	The closing cor. of secs. 5 and 6, T. 8 S., R. 4 E., identical with AP No. 13 of Tract 37, monumented with a 2½ ins. iron post, set 6 ins. below surface of Tee area in Hobble Creek Golf Course, with brass cap mkd. as described in the official record of the 1971 resurvey.
12.01	The cor. of secs. 31 and 32 only, T. 7 S., R. 4 E., identical with AP No. 1 of Tract 37, monumented with an iron post, 2½ ins. diam., set 4 ins. below surface of the fairway of Hobble Creek Golf Course, with brass cap mkd. as described in the official record of the 1971 resurvey.
	S. 89° 23' W., along the S. bdy. of sec. 31.
	Over golf course, under repair.
17.69	Angle Point No. 6 of Tract 37, monumented with an iron post, 2½ ins. diam., extending 6 ins. out of the ground, firmly set, with brass cap mkd. as described in the official record of the 1971 survey of Tract 37.
	Leave golf course; along S slope of mountain.
37.98	Point for the ¼ sec. cor. of sec. 6 only.
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a collar of stone, with brass cap mkd. T 7 S R 4 E ¼ S 6 T 8 S R 4 E 1982
	Cor. is located on steep S slope in oakbrush.
40.02	The ¼ sec. cor. of sec. 31 only, T. 7 S., R. 4 E., monumented with an iron post, 2½ ins. diam., extending 5 ins. out of the ground, with brass cap mkd. as described in the official record of the 1971 survey of Tract 37.

☆U.S. Government Printing Office: 1980—778-251/292

Dependent Resurvey of a Portion of the South Boundary,
T. 7 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	(Restoring the Survey Executed by Stewart and Stewart, Deputy Surveyors in 1899)
	S. 89° 46' W., beginning new measurement.
	Over broken S slope, through oakbrush.
37.42	Point for the 80 1/16 sec. cor. of sec. 6 only.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.
	T 7 S R 4 E 80 1/16 S 6 T 8 S R 4 E 1982
	Cor. is located in dense oak on S slope.
57.15	Point for the 100 1/16 sec. cor. of sec. 6 only.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 5 ft. base, to top of aluminum cap, mkd.
	T 7 S R 4 E 100 1/16 S 6 T 8 S R 4 E 1982
	Cor. is located on steep S slope in native grasses.
61.03	The cor. of Tps. 7 and 8 S., Rs. 3 and 4 E., monumented with an aluminum post, 2½ ins. diam., extending 4 ins. out of the ground, with cap mkd. as described in the official record of the 1979 resurvey of a portion of T. 7 S., R. 3 E.
	Dependent Resurvey of the Subdivisional Lines of Section 6, T. 8 S., R. 4 E., Salt Lake Meridian, Utah
	From the cor. of secs. 5, 6, 7, and 8, monumented with an old survey stake in a scattered mound of stone, and is accepted as the best available evidence of the original cor. position.
	At the corner point
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.
	T 8 S R 4 E S 6 | S 5 S 7 | S 8 1982
	Cor. is located on steep SW slope in native grasses.
	S. 88° 11' W., bet. secs. 6 and 7.

436

Dependent Resurvey of the Subdivisional Lines
of Section 6, T. 8 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	Over broken mountainous land, through oak and maple.
41.77	Point for the ¼ sec. cor. of secs. 6 and 7, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground and in a mound of stone, 3½ ft. base, to top of aluminum cap, mkd. T 8 S R 4 E ¼ S 6 / S 7 1982
	Cor. is located on steep SE slope in oak and maple.
83.54	Point for the 80 1/16 sec. cor. of secs. 6 and 7. Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 8 S R 4 E 80 1/16 S 6 / S 7 1982
	Cor. is located on steep SW slope in dense sagebrush.
104.425	Point for the 100 1/16 sec. cor. of secs. 6 and 7. Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 8 S R 4 E 100 1/16 S 6 / S 7 1982
	Cor. is located on steep W slope in sagebrush.
108.75	The closing cor. of secs. 6 and 7, monumented with an aluminum post, described in the concurrent resurvey of T. 8 S., R. 3 E. From this closing cor., the ¼ sec. cor. of sec. 12, on the E. bdy. of T. 8 S., R. 3 E., bears S. 0° 13' E., 5.56 chs. dist., described in the concurrent resurvey of T. 8 S., R. 3 E.
	From the cor. of secs. 5, 6, 7, and 8. N. 3° 08' W., bet. secs. 5 and 6. Over mountainous land, through oak and maple.
38.52	Point for the ¼ sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.

☆U.S. Government Printing Office: 1980—778-251/292

Dependent Resurvey of the Subdivisional Lines
of Section 6, T. 8 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 3½ ft. base, to top of aluminum cap, mkd. T 8 S R 4 E ¼ S 6 | S 5 1982 Cor. is located on steep E slope in scattered oakbrush.
38.75	Spur, slopes E.
77.04	Point for the 80 1/16 sec. cor. of secs. 5 and 6.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 8 S R 4 E 80 1/16 S 6 | S 5 1982 Cor. is located on steep NW slope in oak and maple.
96.30	Point for the 100 1/16 sec. cor. of secs. 5 and 6.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 8 S R 4 E 100 1/16 S 6 | S 5 1982 Cor. is located on steep NE slope in dense oak and maple.
108.355	Intersect Tract 37.
	From this point, Angle Point No. 10, an iron post, 2½ ins. diam., extending 5 ins. out of the ground, bears N. 88° 34' W., 8 lks. dist., set and mkd. as described in the 1971 survey of Tract 37, T. 8 S., R. 4 E., Salt Lake Meridian, Utah.
	From this same point, Angle Point No. 11, an iron post, 2½ ins. diam., extending 5 ins. out of the ground, bears S. 88° 34' E., 9.93 chs. dist., set and mkd. as described in the official field note record of the 1971 survey of Tract 37, T. 8 S., R. 4 E., Salt Lake Meridian, Utah.
109.88	The closing cor. of secs. 5 and 6, heretofore described.
	From this point, the cor. of secs. 31 and 32, T. 7 S., R. 4 E., heretofore described, bears S. 89° 23' W., 2.02 chs. dist.

The Subdivision of Section 6,
T. 8 S., R. 4 E., Salt Lake Meridian, Utah

438

The Subdivision of Section 6,
T. 8 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	From the ¼ sec. cor. of secs. 6 and 7.
	N. 2° 12' W., on the N and S center line of section 6.
	Over mountainous land, through oak and maple.
38.82	Point for the center ¼ sec. cor. of sec. 6, at intersection with the E and W center line of sec. 6.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.
	T 8 S R 4 E C ¼ S 6 1982
	Cor. is located 1.00 ch. E of draw which drains NE on steep N slope in maple and oak.
77.57	Point for the center 80 1/16 sec. cor. of sec. 6. Not monumented.
110.69	The ¼ sec. cor. of sec. 6 only.
	From the ¼ sec. cor. of secs. 5 and 6.
	S. 88° 38' W., on the E and W center line of sec. 6.
	Over mountainous land, through oak and maple.
41.14	The center ¼ sec. cor. of sec. 6.
82.11	Point for the center 80 1/16 sec. cor. of sec. 6. Not monumented.
102.595	Point for the center 100 1/16 sec. cor. of sec. 6. Not monumented.
106.76	The ¼ sec. cor. of sec. 6 only, on the E. bdy. of sec. 1, T. 8 S., R. 3 E., described in the concurrent resurvey of T. 8 S., R. 3 E.
	From the point for the center 80 1/16 sec. cor. on the E - W center line of sec. 6.
	N. 1° 00' W., on the N and S 80 1/16 line of sec. 6.
	Over mountainous land, through oak and maple.
19.56	Point for the N 80 1/16 sec. cor. of sec. 6.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4½ ft. base, to top of aluminum cap, mkd.
	T 8 S R 4 E N - 80 1/16 S 6 1982
	Cor. is located on steep NW slope.

☆U.S. Government Printing Office: 1980—778-251/292

The Subdivision of Section 6,
T. 8 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
39.12	Point for the 80-80 1/16 sec. cor. of sec. 6, at intersection with the E and W 80 1/16 sec. line.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4½ ft. base, to top of aluminum cap, mkd. T 8 S R 4 E 80-80 1/16 S 6 1982
	Cor. is located on steep NW slope in scattered oak and native grasses.
58.67	Point for the 100-80 1/16 sec. cor. of sec. 6. Not monumented.
72.62	The 80 1/16 sec. cor. of sec. 6 only, on the N. bdy. of sec. 6.
	From the point for the center 80 1/16 sec. cor. on the N - S center line of sec. 6.
	S. 89° 09' W., on the E and W 80 1/16 line.
	Over mountainous land, through oak and maple.
40.15	The 80-80 1/16 sec. cor. of sec. 6.
60.25	Point for the 80-100 1/16 sec. cor. of sec. 6.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd. T 8 S R 4 E 80-100 1/16 S 6 1982
	Set a 6 in. x 6 in. x 4 ft. pine post, alongside the cor.
	Cor. is located on nearly level land on W edge of Fish and Game bitter brush patch.
64.26	The 80 1/16 sec. cor. of sec. 6 only, on the E. bdy. of sec. 1, T. 8 S., R. 3 E., described in the concurrent resurvey of T. 8 S., R. 3 E.
	From the point for the center 100 1/16 sec. cor. on the E-W center line of sec. 6.
	N. 0° 26' W., on the N and S 100 1/16 line.
	Over mountainous land, through oak and maple.
19.65	Point for the N - 100 1/16 sec. cor. of sec. 6, at intersection with the E and W N 1/16 sec. line of sec. 6. Not monumented.
39.30	The 80-100 1/16 sec. cor. of sec. 6.

440

The Subdivision of Section 6,
T. 8 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	From the N - 80 1/16 sec. cor. of sec. 6.
	S. 88° 53' W., on the E and W N 1/16 sec. line of sec. 6.
	Over mountainous land, through oak and maple.
20.29	Point for the N - 100 1/16 sec. cor. of sec. 6.
24.38	The N 1/16 sec. cor. of sec. 6 only, on the E. bdy. of sec. 1, T. 8 S., R. 3 E., described in the concurrent resurvey of T. 8 S., R. 3 E.
	From the 80 - 100 1/16 sec. cor. of sec. 6.
	N. 0° 22' W., on the N and S 100 1/16 sec. line of sec. 6.
	Over mountainous land, through oak and maple.
19.65	Point for the 100 - 100 1/16 sec. cor. of sec. 6, at intersection with the E and W 100 1/16 sec. line of sec. 6.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd. T 8 S R 4 E 100 - 100 1/16 S 6 1982
	Cor. is located on steep SE slope in native grasses.
33.72	The 100 1/16 sec. cor. of sec. 6 only, on the N. bdy. of sec. 6., hereinbefore described.
	From the point for the 100 - 80 1/16 sec. cor. of sec. 6.
	S. 89° 26' W., on the E and W 100 1/16 sec. line of sec. 6.
19.88	The 100 - 100 1/16 sec. cor. of sec. 6.
23.82	The 100 1/16 sec. cor. of sec. 6 only, on the E. bdy. of sec. 1, described in the concurrent resurvey of T. 8 S., R. 3 E.
	General Description
	This survey is situated 4 miles east of Springville, Utah, at the base of the Wasatch Front, between Hobble Creek Canyon and Maple Creek Canyon.
	The land is broken mountainous, with the elevation ranging between 5,000 ft. and 6,600 ft.
	The vegetation consists of oak and maple.
	Hobble Creek Golf Course is located in the north portion of the section, with Whiting Scout Camp in the south part of the section.

☆U.S. Government Printing Office: 1980—778-251/292

441

Form 9600–11
(August 1979)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Jerry L. Thomas	Supervisory Cadastral Surveyor
Frank C. Profaizer Jr.	Supervisory Cadastral Surveyor
Don Buhler	Surveying Technician
John Mavor	Survey Aid
John B. Julander	Survey Aid
Ferrel D. Reynolds	Supervisory Surveying Technician

442

CERTIFICATE OF SURVEY

(I) (~~We~~) Gail E. Reynolds, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 25th day of April, 19 80, (I) (~~We~~) have dependently resurveyed a portion of the south boundary of T. 7 S., R. 4 E., and a portion of the subdivisional lines and surveyed the subdivision of section 6 of T. 8 S., R. 4 E.,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

January 2, 1983
(Date)

Gail E. Reynolds
(Cadastral Surveyor)
Supervisory

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the south boundary of T. 7 S., R. 4 E., and a portion of the subdivisional lines and a survey of the subdivision of section 6 of T. 8 S., R. 4 E., Salt Lake Meridian, Utah

executed by Gail E. Reynolds, Supervisory Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

January 26, 1984
(Date)

G Lee B Hatch
(~~Chief Cadastral Surveyor~~)
Chief Cadastral Surveyor for Utah

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in~~

~~, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief Cadastral Surveyor)~~
~~Cheif Cadastral Surveyor for Utah~~

Form 9600-9
(December 1979)
(formerly 9180-6)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

R606

ORIGINAL

443

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF A

PORTION OF THE SOUTH BOUNDARY

AND A

PORTION OF THE SUBDIVISIONAL LINES

AND THE

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES

AND A

PARTIAL SUBDIVISIONAL SURVEY OF SECTION 28,

TOWNSHIP 36 SOUTH, RANGE 16 EAST

Of the Salt Lake Meridian,

In the State of Utah.

EXECUTED BY

Richard A. Zaninovich Supervisory Cadastral Surveyor

Under special instructions dated April 13, 1982, approved April 13, 1982.

AND SUPPLEMENTAL SPECIAL INSTRUCTIONS DATED MAY 3, 1982

, which provided for the surveys included under U.S. Survey/Group

Number 610, and assignment instructions dated April 14, 1982.

Survey commenced April 14, 1982

Survey completed May 12, 1982

444

INDEX DIAGRAM

Township 36 South, Range 16 East,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20 5	21 7	22	23	24
30	29 5 4	28 4 6	27	26	25
31 4	32 3 2	33 1	34	35	36

Subdivision of Section 28 - Page 8

GPO 855-927

Township 36 South, Range 16 East, Salt Lake Meridian, Utah

CHAINS

The following field notes are those of the dependent resurvey of a portion of the south boundary and a portion of the subdivisional lines and the survey of a portion of the subdivisional lines and a partial subdivisional survey of section 28, Township 36 South, Range 16 East, Salt Lake Meridian, Utah.

HISTORY OF SURVEYS

	Surveyed by
SOUTH BOUNDARY	Phil D. Smith in 1956
SUBDIVISION	
Portion	Phil D. Smith in 1956
Portion	Leslie H. Godwin in 1958

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No 610, Utah, dated April 13, 1982 and the Supplemental Special Instructions dated May 3, 1982.

The direction of lines refer to the true meridians determined by observations of Polaris and direct altitude observation of the sun, and projected by sustained angulation throughout the survey.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the southeast corner of sec. 33 as scaled from the U.S.G.S. 15 minute quadrangle "Natural Bridges " is as follows:

Latitude: 37° 36.4' N. Longitude: 110° 08.9' W.

The mean magnetic declination is 13 1/2° E.

Dependent Resurvey of a Portion of the South Boundary, T. 36 S., R. 16 E., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by Phil D. Smith in 1956.

Beginning at the cor. of secs. 3, 4, 33, and 34 on the S bdy. of the Tp. monumented with an iron post, 2 1/2 ins. diam., firmly set, in a mound of stone 3 ft. base to top of brass cap mkd. as described in the official record of the 1956 survey.

N. 89° 48' W., bet. secs. 4 and 33.

40.00 Point for the 1/4 sec. cor. of sec. 33 only established at 40.00 chs. dist. of westing from the cor. of secs. 3, 4, 33, and 34.

446

Dependent Resurvey of a Portion of the South Boundary,
T. 36 S., R. 16 E., Salt Lake Meridian, Utah

CHAINS	
	Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in solid sandstone, and in a mound of stone, 5 ft. base, to top of aluminum cap, mkd. T36S R16E 1/4 S33 T37S R16E 1982 from which A juniper, 6 ins. diam., bears N. 76° 20' E. 34 lks. dist., mkd. 1/4 S33 BT. A pinon, 7 ins. diam., bears N. 14° 00' W., 44 lks. dist., mkd. 1/4 S33 BT.
40.78	The 1/4 sec. cor. of secs. 4 and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, 2 ft. base to top of brass cap mkd. T36S R16E 1/4 S33 S4 T37S 1956 I remark cap as follows: T36S R16E 1/4 S4 T37S R17S 1982 1956 This cor will now function as the 1/4 sec. cor. of sec. 4 only, T. 37 S., R. 16 E.
	N. 89° 54' W., beginning new measurement.
39.94	The cor. of secs. 4, 5, 32, and 33 monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, in a collar of stone, with brass cap mkd. as described in the official record of the 1956 survey.
	N. 89° 53' W., bet. secs. 5 and 32.
40.10	The 1/4 sec. cor. of secs. 5 and 32, monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, 3 ft. base to top of brass cap mkd. as described in the official record of the 1956 survey.
	N. 89° 52' W., beginning new measurement.
41.20	True point for the cor. of secs. 5, 6, 31, and 32 from which the witness cor. bears N. 89° 52' W., 0.10 chs. dist., monumented with an iron post, 2 1/2 ins. diam. firmly set, in a mound of stone, 4 ft. base, to top of brass cap mkd. as described in the official record of the 1956 survey.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	Reestablishment of the Survey Executed by Phil D. Smith in 1956
	From the sec. cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., hereinbefore described.
	N. 0° 02' W., bet. secs. 32 and 33.
39.47	The 1/4 sec. cor. of secs. 32 and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, 4 ft. base to top of brass cap mkd. T 36 S R 16 E 1/4 S 32 S 33 1956 I remark cap as follows T36S R16E 1/4 S32 1982 1956 This cor. will now function as the 1/4 sec. cor. of sec. 32 only.
	N. 0° 04' W., beginning new measurement
0.53	Point for the 1/4 sec. cor. of secs. 33 only established at 40.00 chs. dist. of northing from the cor. of secs. 4, 5, 32, and 33 on the S bdy. of the Tp. Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd. T36S R16E 1/4 S33 1982 from which A pinon, 6 ins. diam., bears N. 83° 00' E., 43 lks. dist., mkd. 1/4 S33 BT. Raise a mound of stone, 3 ft. base 2 ft. high E of cor.
39.75	The cor. of secs. 28, 29, 32, and 33 monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, 3 ft. base to top of brass cap mkd. T36S R16E S29 | S28 S32 | S33 1956 I remark cap as follows: T36S R16E S32 | S33 1982 1956

CHAINS	
	This cor. will now function as the cor. of secs. 32 and 33 only.
	From the true point for the cor of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp.
	N. 1° 18' E., bet. secs. 31 and 32.
40.35	The 1/4 sec. cor. of secs. 31 and 32, monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, 4 ft. base to top of brass cap mkd. as described in the official record of the 1956 survey.
	N. 0° 06' E., beginning new measurement.
39.77	The cor. of secs. 29, 30, 31, and 32 monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, 3 ft. base to top of brass cap mkd. as described in the official record of the 1956 survey.
	From the cor of secs. 32 and 33 only.
	N. 88° 44' W., bet. secs. 29 and 32.
40.30	The 1/4 sec. cor. of secs. 29 and 32, monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, 4 ft. base to top of brass cap mkd. as described in the official record of the 1956 survey.
	N. 89° 46' W., beginning new measurement.
39.92	The cor. of secs. 29, 30, 31 and 32.
	Reestablishment of the Survey Executed by Leslie H. Godwin in 1958
	From the cor. of secs. 27, 28, 33 and 34 monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, 3 ft. base to top of brass cap mkd. as described in the official record of the 1958 survey.
	N. 0° 03' W., bet. secs. 27 and 28.
39.97	The 1/4 sec. cor. of secs. 27 and 28, monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, 2 ft. base to top of brass cap mkd. as described n the official record of the 1958 survey.
	N. 0° 03' W., beginning new measurement.
20.01	Point for the N 1/16 sec. cor. of secs. 27 and 28.
	Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a collar of stone, with aluminum cap, mkd.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS

T36S R16E
N 1/16
S28 | S27
1982

40.02 The cor. of secs. 21, 22, 27, and 28, moumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, 4 ft. base to top of brass cap mkd. as described in the official record of the 1958 survey.

Survey of a Portion of the Subdivisional
Lines, T. 36 S., R. 16 E., Salt Lake Meridian, Utah

From the cor. of secs. 16, 17, 20 and 21 monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the official record of the 1958 survey.

S. 0° 03' E., bet. secs. 20 and 21.

23.61 Center line of Utah State Highway No. 95.

40.00 Point for the 1/4 sec. cor. of secs. 20 and 21.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T36S R16E
1/4
S20 | S21
1982

from which

A pinon, 8 ins. diam., bears S. 73° 10' E., 34 lks. dist., mkd. 1/4 S21 BT.

A juniper, 8 ins. diam., bears N. 87° 20' W. 21 1/2 lks. dist., mkd. 1/4 S20 BT.

Raise a mound of stone, 3 ft. base, 2 ft. high W of cor.

80.00 Point for the cor. of secs. 20, 21, 28, and 29.

Set an iron post, 30 ins. long, 2 1/2 ins. diam. 14 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap mkd.

T36S R16E
S20 | S21
S29 | S28
1982

S. 0° 03' E., bet. secs. 28 and 29.

40.00 Point for the 1/4 sec. cor. of secs. 28 and 29.

Set an iron post, 10 ins. long, 1 in. diam., in a hole drilled 8 ins. into a sandstone boulder, 8x6x5 ft., with brass cap mkd.

450

Survey of a Portion of the Subdivisional Lines, T. 36 S., R. 16 E., Salt Lake Meridian, Utah

CHAINS

T36S R16E
1/4
S29 | S28
1982

from which

A pinon, 8 ins. diam., bears N. 41° 50' E., 58 lks. dist., mkd. 1/4 S28 BT.

A pinon, 15 ins. diam., bears S. 19° 10' W. 71 lks. dist., mkd. 1/4 S29 BT.

80.00 Point for the cor. of secs. 28 and 33 only.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 4 ft. base to top of brass cap mkd.

T36S
S28
S29
S33
R16E
1982

from which

A twin pinon, 8 ins. diam., bears N. 15° 00' E. 26 1/2 lks. dist., mkd. T36S R16E S28 BT.

A pinon, 4 ins. diam., bears S. 39° 00' E. 20 lks. dist., mkd. X BT.

S. 0° 03' E., bet. secs. 29 and 33.

0.75 Point for the cor. of sec. 29 only at intersection with a line projected from the 1/4 sec. cor. of secs. 29 and 32 through the cor. of secs. 32 and 33 only.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T36S
R16E
S29
S33
1982

Raise a mound of stone, 3 ft. base, 2 ft. high W of cor.

N. 88° 44' W., bet. secs. 29 and 33.

0.74 The cor. of secs. 32 and 33 only.

From the cor. of secs. 27, 28, 33, and 34.

N. 89° 53' W., bet. secs. 28 and 33.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
39.99	Point for the 1/4 sec. cor. of secs. 28 and 33. Set an iron post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock in a mound of stone 3 ft. base to top of brass cap mkd. T36S R16E 1/4 S28/S33 1982
79.98	The cor. of secs. 28 and 33 only.
	From the cor. of secs. 21, 22, 27, and 28. N. 89° 53' W., bet. secs. 21 and 28.
19.99	Point for the E 1/16 sec. cor. of secs. 21 and 28. Set an iron post, 10 ins. long, 1 in. diam., in a hole drilled 8 ins. into solid sandstone, with brass cap mkd. T36S R16E E 1/16 S21/S28 1982 Raise a mound of stone, 3 ft. base, 2 ft. high N of cor.
29.985	Point for the W-E 1/64 sec. cor. of secs. 21 and 28. Drive a railroad spike flush with the surface of Utah State Highway No. 95. from which An iron post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground in a collar of stone for a reference monument, bears S. 45° 00' E., 60 lks. dist. with brass cap mkd. T36S R16E S28 W-E 1/64 39.5 FT RM 1982 and an arrow pointing to the corner. An iron post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a collar of stone, for a reference monument, bears S. 45° 0' W., 45 lks. dist., with brass cap mkd. T36S R16E S28 W-E 1/64 29.5 FT RM 1982 and an arrow pointing to the corner.
39.98	Point for the 1/4 sec. cor. of secs. 21 and 28. Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T36S R16E 1/4 S21/S28 1982 Raise a mound of stone, 3 ft. base, 2 ft. high N. of cor.
79.96	The cor. of secs. 20, 21, 28, and 29.

452

Partial Subdivision Survey
of Section 28,
T. 36 S., R. 16 E., Salt Lake Meridian, Utah

CHAINS	
	Partial Subdivision Survey of Sec. 28 T. 36 S., R. 16 E., S.L.M., Ut.
	From the 1/4 sec. cor. of secs. 28 and 33.
	N. 0° 03' W., on the N and S center line of sec. 28.
39.98	Point for the center 1/4 sec. cor. of sec. 28 at intersection with the E and W center line.
	Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T36S R16E C 1/4 S28 1982
	Raise a mound of stone, 3 ft. base, 2 ft. high W of cor.
49.985	Point for the center-S-N 1/64 sec. cor. of sec. 28, not monumented.
54.9875	Point for the center N-S-N 1/256 sec. cor. of sec. 28.
	Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd. C N-S-N 1/256 S28 C 1982
59.99	Point for the center N 1/16 sec. cor. of sec. 28.
	Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. C N 1/16 S28 C 1982
	from which
	The north side of a storage tank and water well bears East, 85.5 lks. dist.
69.995	Point for the center N-N 1/64 sec. cor. of sec. 28.
	Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd. C N-N 1/64 S28 C 1982

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	from which
	The westerly corner of Fry Canyon store bears N. 26° 18' 30" E., 6.24 chs. dist.
	The westerly cor. of house; bears N. 45° 00' E., 4.12 chs. dist.
	The center of the northwest side of U.D.W.R. cabin bears S. 26° 46' E., 7.095 chs. dist.
	The northwest corner of generator shed bears S. 7° 35' W., 5.78 chs. dist.
80.00	The 1/4 sec. cor. of secs. 21 and 28.
	From the 1/4 sec. cor. of secs. 27 and 28.
	N. 89° 52' W., on the E and W center line of sec. 28.
19.99	Point for the center E 1/16 sec. cor of sec. 28.
	Set a railroad spike 6 ins. below the surface of a graded road.
	from which
	An iron post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground for a reference monument, bears North., 45 1/2 lks. dist., with brass cap mkd. E 1/16 S28 30 FT. RM 1982 and an arrow pointing to the corner.
	An iron post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground for a reference monument, bears South, 45 1/2 lks. dist., with brass cap mkd. E 1/16 S28 30 FT. RM 1982 and an arrow pointing to the cor.
29.985	Point for the center W-E 1/64 sec. cor. of sec. 28.
	Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	C W-E 1/64 / S28 1982 C
39.98	The center 1/4 sec. cor. of sec. 28.
79.96	The 1/4 sec. cor. of secs. 28 and 29.
	From the center E 1/16 sec. cor. of sec. 28.
	N. 0° 03' W., on the N and S center line of the NE 1/4 of sec. 28.
10.005	Point for the center S-NE 1/64 sec. cor. of sec. 28, not monumented.
20.01	Point for the NE 1/16 sec. cor. of sec. 28 at intersection with the E and W center line of the NE 1/4

454

Partial Subdivision of Section 28,
T. 36 S., R. 16 E., Salt Lake Meridian, Utah

CHAINS	
	Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd. NE 1/16 S28 1982
30.015	Point for the center N-NE 1/64 sec. cor. of sec. 28, not monumented.
40.02	The E 1/16 sec. cor. of secs. 21 and 28.
	From the N 1/16 sec. cor. of secs. 27 and 28. N. 89° 52' W., on the E and W center line of the NE 1/4 of sec. 28.
19.99	The NE 1/16 sec. cor. of sec. 28.
29.985	Point for the center W-NE 1/64 sec. cor. of sec. 28.
	Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd. SEC 28 C-W-NE 1/64 1982
39.98	The center N 1/16 sec. cor. of sec. 28.
	From the center W-E 1/64 sec. cor. of sec. 28. N. 0° 03' W., on the N and S center line of the SW 1/4 of the NE 1/4 of sec. 28
10.005	Point for the SW-NE 1/64 sec. cor. of sec. 28, not monumented.
15.0075	Point for the center N-SW-NE 1/256 sec. cor. of sec. 28.
	Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground with aluminum cap mkd. S28 C-N-SW-NE 1/256 1982
20.01	The center W-NE 1/64 sec. cor. of sec. 28.
	From the point for the center S-NE 1/64 sec. cor. of sec. 28. N. 89° 52' W., on the E and W center line of the SW 1/4 of the NE 1/4 of sec 28
9.995	Point for the SW-NE 1/64 sec. cor. of sec. 28.
19.99	Point for the center S-N 1/64 sec. cor. of sec. 28, not monumented.

☆U.S. Government Printing Office: 1980—778-251/292

Partial Subdivision Survey of Section 28,
T. 36 S., R. 16 E., Salt Lake Meridian, Utah

CHAINS	
	From the center N-SW-NE 1/256 sec. cor. of sec. 28.
	N. 89° 52' W., on the E and W center line of the NW 1/4 of the SW 1/4 of the NE 1/4.
9.995	The center N-S-N 1/256 sec. cor. of sec. 28.
	From the center W-NE 1/64 sec. cor. of sec. 28.
	N. 0° 03' W., on the N and S center line of the NW 1/4 of the NE 1/4 of sec. 28.
10.005	Point for the NW-NE 1/64 sec. cor. of sec. 28 at intersection with the E and W center line of the NW 1/4 the NE 1/4.
	Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd. S28 NW-NE 1/64 1982
20.01	The W-E 1/64 sec. cor. of secs. 21 and 28.
	From the point for the center N-NE 1/64 sec. cor. of sec. 28.
	N. 89° 53' W., on the E and W center line of the NW 1/4 of the NE 1/4 of sec. 28.
9.995	The NW-NE 1/64 sec. cor. of sec. 28.
19.99	The center N-N 1/64 sec. cor. of sec. 28.

General Description

The area surveyed and resurveyed within T. 36 S., R. 16 E. is situated approximately 36 miles west of Blanding, Utah. The elevation varies from 7000 ft. on a pinon and juniper covered mesa in sections 32 and 33 to 5200 ft. at the bottom of Fry Canyon as it passes through section 21. General drainage is northeast to Fry Canyon, a tributary of White Canyon. Utah State Highway No. 95 passes through sections 21 and 28. The Fry Canyon store is located in the NW 1/4 of the NE 1/4 of sec. 28. There are numerous inactive uranium mining sites in the area.

The mean magnetic declination is 13 1/2° East.

Form 9180-8
(March 1969)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Gary L. Kratz	Supervisory Cadastral Surveyor
Donzil Worthington	Surveying Technician
Gary D. Gogos	Surveying Technician

457

CERTIFICATE OF SURVEY

(I) (~~We~~) Richard A. Zaninovich, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 13th day of April, 19 82, (I) (~~We~~) have dependently resurveyed a portion of the south boundary and a portion of the subdivisional lines and surveyed a portion of the subdivisional line and a partial subdivisional survey of section 28 of T. 36 S., R. 16 E.,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me) (~~us~~) and under (my) (~~our~~) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

January 19, 1984
(Date)

(Cadastral Surveyor)
Supervisory

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Washington, D.C.

The foregoing field notes of the dependent resurvey of a portion of the south boundary and a portion of the subdivisional lines and the survey of a portion of the subdivisional lines and a partial subdivisional survey of section 28 of T. 36 S., R. 16 E., Salt Lake Meridian, Utah

executed by Richard A. Zaninovich, Supervisory Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

January 26, 1984
(Date)

Glen B. Hatch
~~Chief, Division of Cadastral Surveys~~
Chief Cadastral Surveyor for Utah

~~CERTIFICATE OF TRANSCRIPT~~

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

(Date)

~~Chief, Division of Cadastral Surveys~~
Chief Cadastral Surveyor for Utah

Form 9600–9
(December 1979)
(formerly 9180–6)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

R606

458

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF A PORTION OF THE SOUTH BOUNDARY

OF T. 15 S., R. 4 W.,

(THIRD STANDARD PARALLEL SOUTH)

AND

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES

AND A PARTIAL SUBIVISIONAL SURVEY

OF

SECTIONS 2, 3, 4, AND 11,

TOWNSHIP 16 SOUTH, RANGE 4 WEST

Of the Salt Lake Meridian,

In the State of Utah.

EXECUTED BY

Richard A. Zaninovich Supervisory Cadastral Surveyor

Under special instructions dated May 12, 1982, approved May 12, 1982.

_____, which provided for the surveys included under ~~U.S. Survey~~/Group Number 614, and assignment instructions dated May 12, 1982.

Survey commenced May 20, 19 82

Survey completed June 18, 19 82

INDEX DIAGRAM

Township 16 South, Range 4 West,

6	5 4	3 4 6 5	2 3 7 7	2 2 10 8	1
7	8 4	9 11 11	10 8 10	11 9 9	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision of Section 2 - Page 11
Subdivision of Section 3 - Page 13
Subdivision of Section 4 - Page 13
Subdivision of Section 11 - Page 14

GPO 855-927

Township 16 South, Range 4 West, Salt Lake Meridian, Utah

CHAINS

The following field notes are those of the dependent resurvey of a portion of the south boundary of T. 15 S. R. 4 W., (Third Standard Parallel South) and a portion of the subdivisional lines; and the survey of a portion of the subdivisional lines and a partial subdivisional survey of sections 2, 3, 4, and 11 of Township 16 South, Range 4 West, Salt Lake Meridian, Utah.

History of Surveys

	Surveyed by		Retr. or Resurveyed by	
NORTH BOUNDARY				
Portion	F. Dickert	1870		
Portion	Miller and Hayes	1915		
Portion			Miller and Hayes	1915
SUBDIVISION				
Portion	F. Dickert	1870		

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated May 12, 1982.

The directions of lines refer to the true meridian as determined by observations of Polaris and direct altitude observations of the sun, projected by fore- and backsights.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the southeast corner of section 11 as determined from a tie made to the U.S.C. and G.S. station "Fool", is as follows:

Latitude 39° 26' 13.73" N. Longitude 112° 15' 17.81" W.

The mean magnetic declination as projected from the U.S. Geological Survey magnetic declination map of 1980 is 14 1/2°

Dependent Resurvey of a Portion of the South Boundary (Third Standard Parallel South), T. 15 S., R. 4 W., Salt Lake Meridian, Utah

---

(Reestablishment of the Survey Executed by Ferdinand Dickert in 1870)

Beginning at the standard cor. of secs. 35 and 36, T. 15 S., R. 4 W., monumented with an iron post, 3 ins. diam., firmly set in a mound of stone, 3 ft. base to top of brass cap, mkd. as described in the official record of the 1915 survey.

461

Dependent Resurvey of a Portion of the South Boundary (Third Standard Parallel South), T. 15 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS	
	N. 89° 06' W., along the S. bdy. of 35.
5.28	Point for the closing cor. of secs. 1 and 2, T. 16 S., R. 4 W., hereinafter described.
20.09	Point for the E 1/16 sec. cor. of sec. 2 only, T. 16 S., R. 4 W., at 20.00 chs. of easting from the 1/4 sec. cor. of secs. 2 and 35 on the N. bdy. of the Tp. Set an iron post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top of brass cap, mkd. E 1/16 S 2 1982
40.09	The 1/4 sec. cor. of secs. 2 and 35, on the N. bdy. of the Tp., at the cor. of fences projecting E, W, and S. This is accepted as the best available evidence of the original corner position. Set an iron post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd. T 15 S R 4 W S 35 1/4 S 2 T 16 S 1982
	N. 89° 57' W., beginning new measurement.
40.51	The cor. of secs. 2, 3, 34, and 35, at the cor. of fences projecting N, S, E, and W. This is accepted as the best available evidence of the original corner position. Set an iron post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd. T 15 S R 4 W S 34 | S 35 S 3 | S 2 T 16 S 1982
	(Reestablishment of the Survey Executed by Ferdinand Dickert in 1870 and the Resurvey Executed by Miller and Hayes in 1915)
	S. 89° 42' W., bet. secs. 3 and 34.
40.76	Point for the 1/4 sec. cor. of secs. 3 and 34, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

☆U.S. Government Printing Office: 1980—778-251/292

Dependent Resurvey of a Portion of the South
Boundary (Third Standard Parallel South),
T. 15 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS	
	T 15 S R 4 W S 34 1/4 S 3 T 16 S 1982
81.52	The cor. of secs. 33 and 34, monumented with an iron post, 3 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. T 15 S R 4 W S 33 | S 34 1915 I remark cap as follows T 15 S R 4 W S 33 | S 34 S 4 | S 3 T 16 S 1982 1915 This cor. will now function as the cor. of secs. 3, 4, 33, and 34.
	S. 88° 47' W., bet. secs. 4 and 33. Over level land.
40.99	The 1/4 sec cor. of sec. 33, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. 1/4 S 33 1915 I remark cap as follows S 33 1/4 S 4 1982 1915 This cor. will now function as the 1/4 sec. cor. of secs. 4 and 33.
	N. 89° 33' W., beginning new measurement.
40.61	The cor. of secs. 4 and 5, T. 16 S., R. 4 W., monumented with an iron post, 3 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the official record of the 1915 resurvey. from which A juniper, 20 ins. diam., bears S. 74° E., 96 lks. dist., with a partially opened blaze and illegible scribe marks.

CHAINS

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 16 S., R. 4 W., Salt Lake Meridian, Utah

(Reestablishment of the Survey Executed by Ferdinand Dickert in 1870)

From the cor. of secs. 4 and 5 on the N. bdy. of the Tp., hereinbefore described.

S. 1° 04' W., bet. secs. 4 and 5.

40.76 Point for the 1/4 sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 in. in the ground, with brass cap mkd.

T 16 S R 4 W
1/4
S 5 | S 4
1982

81.62 The cor. of secs. 4, 5, 8, and 9. monumented with a copperweld, firmly set, projecting 18 ins. above the ground, with cap mkd.

S 5 | S 4
S 8 | S 9

Alongside which is a squared pine post projecting 3 ft. above ground, firmly set, no marks visible, and a squared juniper post, 2 ft. long, lying loosely, no marks visible. This is accepted as the best available evidence of the original corner position.

At the corner point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 16 S R 4 W
S 5 | S 4
S 8 | S 9
1982

Bury copperweld, pine and juniper posts alongside the iron post.

S. 0° 03' E., bet. secs. 8 and 9.

40.00 Point for the 1/4 sec. cor. of sec. 9 only, at 40.00 chs. southing from the cor. of secs. 4, 5, 8, and 9.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 16 S R 4 W
| 1/4 S 9
1982

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	Raise a mound of stone, 3 ft. base, 2 ft. high, E of cor.
40.73	The 1/4 sec. cor. of secs. 8 and 9, monumented with a squared juniper post, 24 ins. long, firmly set, projecting 12 ins. above the ground. No marks visible. This is accepted as the best available evidence of the original corner position. This cor. will now function as the 1/4 sec. cor. of sec. 8 only.
	At the corner point
	Set an iron post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T 16 S R 4 W 1/4 | S 8 | 1982
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	Bury the juniper post alongside the iron post.
	S. 0° 09' E., beginning new measurement.
36.87	Point for the closing cor. of secs. 9 and 16, hereinafter described.
	Thence bet. secs. 8 and 16, with continuous measurement.
40.82	The cor. of secs. 8, 9, 16, and 17, monumented with a squared juniper post, 22 ins. long, firmly set, projecting 12 ins. above the ground. No marks visible. This cor. will now function as the cor. of secs. 8 and 17 only and is accepted as the best available evidence of the original corner position.
	At the corner point
	Set an iron post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.
	T 16 S S 8 | S 17 | S 16 R 4 W 1982
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	From the cor. of secs. 4, 5, 8, and 9, hereinbefore described.
	N. 88° 17' E., bet . secs. 4 and 9.
40.02	Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

465 Dependent Resurvey of a Portion of the Subdivisional Lines, T. 16 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS	
	T 16 S R 4 W S 4 1/4 S 9 1982
	Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, N of cor.
	Cor. falls on top of ridge, bears N and S.
60.03	Point for the E 1/16 sec. cor. of secs. 4 and 9.
	Set an iron post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	S 4 E 1/16 S 9 1982
80.04	Point for the cor. of secs. 3, 4, 9, and 10, at record latitude from the cor. of secs. 3, 4, 33, and 34, and record departure from the cor. of secs. 4, 5, 8, and 9. There is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T 16 S R 4 W S 4 | S 3 S 9 | S 10 1982
	N. 2° 15' E., bet. secs. 3 and 4.
20.015	Point for the S 1/16 sec. cor. of secs. 3 and 4.
	Set an iron post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	S 1/16 S 4 | S 3 1982
40.03	Point for the 1/4 sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T 16 S R 4 W 1/4 S 4 | S 3 1982
79.81	The cor. of secs. 3, 4, 33, and 34, on N. bdy. of Tp., hereinbefore described.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	From the cor. of secs. 3, 4, 9, and 10.
	East, bet. secs. 3 and 10.
40.00	Point for the 1/4 sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd. T 16 S R 4 W S 3 1/4 S 10 1982
80.00	Point for the cor. of secs. 2, 3, 10, and 11, at record latitude from the cor. of secs. 2, 3, 34, and 35 and record departure from the cor. of secs. 3, 4, 9, and 10. There is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd. T 16 S R 4 W S 3 | S 2 S 10 | S 11 1982
	N. 3° 20' E., bet. secs. 2 and 3.
20.035	Point for the S 1/16 sec. cor. of secs. 2 and 3. Set an iron post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd. S 1/16 S 3 | S 2 1982
40.07	Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd. T 16 S R 4 W 1/4 S 3 | S 2 1982
80.32	The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., hereinbefore described.

467

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 16 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS	
	From the cor. of secs. 2, 3, 10, and 11.
	East, bet. secs. 2 and 11.
40.00	Point for the 1/4 sec. cor. of secs. 2 and 11, at record bearing and distance from the cor. of secs. 2, 3, 10, and 11. There is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T 16 S R 4 W S 2 1/4 S 11 1982

Survey of a Portion of the Subdivisional Lines, T. 16 S., R. 4 W., Salt Lake Meridian, Utah

	East, bet. secs. 2 and 11.
40.00	Point for the cor. of secs. 2 and 11 only, established at a point East, 40.00 chs. from the 1/4 sec. cor. of secs. 2 and 11.
	Set an iron post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of brass cap, mkd.
	T 16 S R 4 W S 2 | S 11 | 1982
	from which
	A juniper, 4 ins. diam., bears S. 40° W., 26.5 lks. dist., mkd. X BT.
	A juniper, 8 ins. diam., bears N. 46° W., 41.5 lks. dist., mkd. T16S R4W S2 BT.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 16 S., R. 4 W., Salt Lake Meridian, Utah

	From the cor. of secs. 2, 3, 10, and 11.
	South, bet. secs. 10 and 11.
40.00	Point for the 1/4 sec. cor. of secs. 10 and 11, at record bearing and distance from the cor. of secs. 2, 3, 10, and 11. There is no remaining evidence of the original corner.
	Set an iron post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	T 16 S R 4 W 1/4 S 10 | S 11 1982
80.00	The cor. of secs. 10 and 11 only, reestablished at record bearing and distance from the cor. of secs. 2, 3, 10, and 11; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd. T 16 S R 4 W S 10 | S 11 1982
	East, along the S. bdy. of sec. 11.
40.00	Point for the 1/4 sec. cor. of sec. 11 only, at record bearing and distance from the cor. of secs. 10 and 11; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of brass cap, mkd. T 16 S R 4 W 1/4 S 11 1982
	Survey of a Portion of the Subdivisional Lines, T. 16 S., R. 4 W., Salt Lake Meridian, Utah
	East, along the S. bdy. of sec. 11.
40.00	Point for the cor. of sec. 11 only, established at a point East, 40.00 chs. from the 1/4 sec. cor. of sec. 11 only, on the S. bdy. of the sec. Set an iron post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd. T 16 S R 4 W S 11 | 1982 from which A juniper, 4 ins. diam., bears N. 88° W., 26 lks. dist., mkd. X BT. A juniper, 8 ins. diam., bears N. 41° W., 45 lks. dist., mkd. T16S R4W S11 BT.
	N. 0° 01' E., along the E. bdy. of sec. 11.
40.00	Point for the 1/4 sec. cor. of sec. 11 only.

CHAINS	
	Set an iron post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd. T 16 S R 4 W 1/4 S 11 | 1982 Raise a mound of stone, 3 1/2 ft. base, 2 ft. high, W of cor.
80.00	Cor. of secs. 2 and 11, heretofore described.
	North, along the E. bdy. of sec. 2.
40.00	Point for the 1/4 sec. cor. of sec. 2 only. Set an iron post, 30 ins. long, 2 1/2 ins. diam., over a cross (X) chiseled on solid rock, and in a mound of stone, 5 ft. base, to top of brass cap, mkd. T 16 S R 4 W 1/4 S 2 | 1982
79.60	Point for the closing cor. of secs. 1 and 2, at intersection with the N. bdy. of the Tp. (Third Standard Parallel South). Set an iron post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top of brass cap, mkd. T 15 S R 4 W S 35 S 2 | S 1 T 16 S C C 1982 From this cor., the cor. of secs. 35 and 36, T. 15 S., R. 4 W., bears S. 89° 06' E., 5.28 chs. dist. hereinbefore described.
	From the cor. of secs. 10 and 11 only. West, along the S. bdy. of sec. 10.
40.00	Point for the 1/4 sec. cor. of sec. 10 only. Set an iron post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top of brass cap, mkd. T 16 S R 4 W 1/4 S 10 1982
80.00	Point for the cor. of secs. 9 and 10 only. Set an iron post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top of brass cap, mkd.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS

T 16 S R 4 W
S 9 | S 10
1982

From the cor. of secs. 9 and 10 only.

West, along the S. bdy. of sec. 9.

39.90 Point for the 1/4 sec. cor. of secs. 9 and 16, at 40.00 chs. Easting from the closing cor. of secs. 9 and 16.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top of brass cap, mkd.

T 16 S R 4 W
S 9
1/4 S 16
1982

From this cor., the U.S.C. and G.S. triangulation station "Fool" bears N. 37° 48' W., 16.52 chs. dist.

79.90 Point for the closing cor. of secs. 9 and 16, at intersection with the E. bdy. of sec. 8.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone 4 ft. base, to top of brass cap, mkd.

T 16 S
S 9
S 8 | S 16 CC
R 4 W
1982

From this cor., the cor. of secs. 8 and 17 only, bears S. 0° 09' E., 3.95 chs. dist.

From the cor. of secs. 9 and 10 only.

N. 0° 01' W., bet. secs. 9 and 10.

40.00 Point for the 1/4 sec. cor. of secs. 9 and 10, at 40.00 chs. northing from the cor. of secs. 9 and 10 only.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 16 S R 4 W
1/4
S 9 | S 10
1982

80.00 The cor. of secs. 3, 4, 9, and 10.

Partial Subdivisional Survey of Section 2,
T. 16 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS	
	From the 1/4 sec. cor. of secs. 2 and 11.
	N. 3° 42' E., on the N and S center line of sec. 2.
40.08	Point for the center 1/4 sec. cor. of sec. 2, at intersection with the E and W center line.
	Set an iron post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd. T 16 S R 4 W C 1/4 S 2 1982
	Cor. falls 5 lks. N of a barbed wire fence, bears E and W.
80.31	The 1/4 sec. cor. of secs. 2 and 35, hereinbefore described.
	From the 1/4 sec. cor. of sec. 2 only, on the E. bdy. of the Tp., hereinbefore described.
	West, on the E and W center line of sec. 2.
17.41	Point for the center east 1/16 sec. cor. of sec. 2, at 20.00 chs. Easting from the center 1/4 sec. cor. of sec. 2.
	Chisel a cross (X) on a boulder, 4 x 3 x 1 ft. above the ground.
	from which
	An iron post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, for a reference monument, bears N. 45° 00' E., 50 lks. dist., with brass cap mkd. CE 1/16 S2 33 FT RM 1982 and an arrow pointing to the cor.
	An iron post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, for a reference monument, bears S. 45° 00' W., 50 lks. dist., with brass cap mkd. CE 1/16 S2 33 FT RM 1982 and an arrow pointing to the cor.
37.41	The center 1/4 sec. cor. of sec. 2, at intersection with the N and S center line.
77.67	The 1/4 sec. cor. of secs. 2 and 3.
	From the center E 1/16 sec. cor. of sec. 2.
	N. 3° 44' E., along the N and S center line of the NE 1/4 of sec. 2.
39.92	The east 1/16 sec. cor. of sec. 2 only, on the N. bdy. of the Tp., hereinbefore described.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	Partial Subdivisional Survey of Section 3, T. 16 S., R. 4 W., Salt Lake Meridian, Utah
	From the 1/4 sec. cor. of secs. 3 and 10.
	N. 2° 47' E., on the N and S center line of sec. 3.
20.025	Point for the center south 1/16 sec. cor. of sec. 3.
	Set an iron post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	C S 1/16 | S 3 C 1982
	Raise a mound of stone, 3 1/2 ft. base, 2 ft. high, W of cor.
40.05	Point for the center 1/4 sec. cor. of sec. 3, at intersection with the E and W center line. Not monumented.
80.06	The 1/4 sec. cor. of secs. 3 and 34, on the N. bdy. of the Tp., hereinbefore described.
	From the 1/4 sec. cor. of secs. 2 and 3.
	West, on the E and W center line of sec. 3.
40.37	Point for the center 1/4 sec. cor. of sec. 3.
80.75	The 1/4 sec. cor. of secs. 3 and 4.
	From the S 1/16 sec. cor. of secs. 2 and 3.
	West, on the E and W center line of the SE 1/4 of sec. 3.
40.19	The center south 1/16 sec. cor. of sec. 3.
	Partial Subdivisional Survey of Section 4, T. 16 S., R. 4 W., Salt Lake Meridian, Utah
	From the 1/4 sec. cor. of secs. 4 and 9.
	N. 1° 32' E., on the N and S center line of sec. 4.
12.53	Well, bears East, 42 lks. dist.
20.22	Point for the center south 1/16 sec. cor. of sec. 4.
	Set an iron post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	C S 1/16 | S 4 C 1982

473

Partial Subdivisional Survey of Section 4,
T. 16 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS	
40.44	Point for the center 1/4 sec. cor. of sec. 4, at intersection with the E and W center line. Not monumented.
80.11	The 1/4 sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp., hereinbefore described.
	From the 1/4 sec. cor. of secs. 3 and 4.
	S. 88° 54' W., on the E an W center line of sec. 4.
20.245	Point for the center east 1/16 sc. cor. of sec. 4. Not monumented.
40.49	Point for the center 1/4 sec. cor. of sec. 4.
80.81	The 1/4 sec. cor. of secs. 4 and 5.
	From the E 1/16 sec. cor. of secs. 4 and 9.
	N. 1° 53' E., on the N and S center line of the SE 1/4 of sec. 4.
20.12	Point for the SE 1/16 sec. cor. of sec. 4, at intersection with the E and W center line of the SE 1/4 of sec. 4.
	Set an iron post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd. SE 1/16 S 4 1982
40.24	Point for the center east 1/16 sec. cor. of sec. 4.
	From the S 1/16 sec. cor. of secs. 3 and 4.
	S. 88° 36' W., on the E and W center line of the SE 1/4 of sec. 4.
20.13	The SE 1/16 sec. cor. of sec. 4.
40.26	The center south 1/16 sec. cor. of sec. 4.
	Partial Subdivisional Survey of Section 11, T. 16 S., R. 4 W., Salt Lake Meridian, Utah
	From the 1/4 sec. cor. of sec. 11 only, on the S. bdy. of sec. 11.
	North, on the N and S center line of sec. 11.
40.00	Point for the center 1/4 sec. cor. of sec. 11, at intersection with the E and W center line.
	Set an iron post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

☆U.S. Government Printing Office: 1980—778-251/292

CHAINS	
	T 16 S R 4 W C 1/4 S 11 1982
	Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W of cor.
80.00	The 1/4 sec. cor. of secs. 2 and 11.
	From the 1/4 sec. cor. of sec. 11 only, on the E. bdy. of sec. 11.
	West, on the E and W center line of sec. 11.
40.00	The center 1/4 sec. cor. of sec. 11.
80.00	The 1/4 sec. cor. of secs. 10 and 11.

General Description

The area surveyed and resurveyed within Township 16 South, Range 4 West, is situated about 6 miles NE of Oak City, Utah. The elevation varies from 5800 feet in the foothills of the canyon mountains in the SE portion to 4900 feet in the nearly level NW portion of the area surveyed. The general drainage is to the NW. State Highway No. 125 passes through sections 3, 4, 8, and 9. The main use of the land in this area is as pasture.

475

Form 9180–8
(March 1969)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Gary L. Kratz	Supervisory Cadastral Surveyor
Donzil Q. Worthington	Surveying Technician
Gary D. Gogos	Surveying Technician

CERTIFICATE OF SURVEY

(I)XWX), Richard A. Zaninovich , HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 12th day of May , 19 82, (I) (WX)have dependently resurveyed a portion of the south boundary of T. 15 S., R. 4 W., (Third Standard Parallel South) and a portion of the subdivisional lines; and surveyed a portion of the subdivisional lines and a portion of the subdivision of sections 2, 3, 4, and 11 of T. 16 S., R. 4 W.,

of the Salt Lake Meridian, in the State of Utah , which are represented in the foregoing field notes as having been executed by (me), (XX) and under (my) XXX) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

January 31, 1984
(Date)

(Cadastral Surveyor)
Supervisory

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Washington, D.C.

The foregoing field notes of the dependent resurvey of a portion of the south boundary of T. 15 S., R. 4 W., (Third Standard Parallel South) and a portion of the subdivisional lines; the survey of a portion of the subdivisional lines and a partial subdivisional survey of sections 2, 3, 4, and 11 of T. 16 S., R. 4 W., Salt Lake Meridian, Utah

executed by Richard A. Zaninovich, Supervisory Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

February 14, 1984
(Date)

Glen B. Hatch
XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX (Chief, Division of Cadastral Survey)
Chief Cadastral Surveyor for Utah

~~CERTIFICATE OF TRANSCRIPT~~

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in , is a true copy of the original field notes.

~~(Date)~~

~~XXX(Chief, Division of Cadastral Survey)XXXXXXXX~~
Chief Cadastral Surveyor for Utah

Form 9600-9
(December 1979)
(formerly 9180-6)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

R606

477

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF A

PORTION OF THE SUBDIVISIONAL LINES

AND

A PARTIAL SUBDIVISIONAL SURVEY

OF SECTION 4,

TOWNSHIP 17 SOUTH, RANGE 4 WEST

Of the Salt Lake Meridian,

In the State of Utah.

EXECUTED BY

Richard A. Zaninovich Supervisory Cadastral Surveyor

Under special instructions dated May 12, 19 82, approved May 12, 1982.

_____, which provided for the surveys included under ~~U.S. Survey~~/Group Number 614, and assignment instructions dated May 12, 1982.

Survey commenced May 28, 19 82

Survey completed June 2, 19 82

478

INDEX DIAGRAM

Township 17 South, Range 4 West,

6	5	4 3 1 2	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision of Section 4 - Page 3

GPO 855-927

Township 17 South, Range 4 West Salt Lake Meridian, Utah

CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines and a partial subdivisional survey of section 4 of T. 17 S., R. 4 E., Salt Lake Meridian, Utah.

History of Surveys

	Surveyed by		Retr. or Resurveyed by	
NORTH BOUNDARY				
Portion	F. Dickert	1870		
Portion	Gentry and Nelson	1934		
SUBDIVISION				
Portion	F. Dickert	1870		
Portion	Gentry and Nelson	1934		
Portion			Gentry and Nelson	1934

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated May 12, 1982.

The directions of lines refer to the true meridian as determined by observations of Polaris and direct altitude observations of the sun, projecting by fore- and backsights.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the southeast corner of section 4 as scaled from the U.S.G.S. 15 minute quadrangle "Oak City" is as follows:

Latitude 39° 21.7" N. Longitude 112° 17.5' W.

The mean magnetic declination, as projected from the U.S. Geological Survey magnetic declination map of 1980, is 14 1/2° E.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 17 S., R. 4 W., Salt Lake Meridian, Utah

---

(Reestablishment of the Survey Executed by Gentry and Nelson in 1934)

Beginning at the cor. of secs. 4 and 9 only, monumented with an iron post, 2 ins. diam., projecting 10 ins. above the ground, with brass cap mkd. as described in the official record of the 1934 resurvey.

CHAINS	
	N. 0° 04' W., bet. secs. 3 and 4.
19.995	Point for the S 1/16 sec. cor. of sec. 4 only. Set an iron post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top of brass cap, mkd. S 1/16 | S 4 | 1982
33.09	The 1/4 sec. cor. of sec. 3 only, monumented with an iron post, 1 in. diam., projecting 18 ins. above the ground, and in a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. as described in the official record of the 1934 survey.
39.99	The 1/4 sec. cor. of sec. 4 only, monumented with an iron post, 1 in. diam., projecting 14 ins. above the ground, and in a mound of stone, 2 ft. base, 1 ft. high, with brass cap mkd. as described in the official record of the 1934 survey.
	(Reestablishment of the Survey Executed by Ferdinand Dickert in 1870 and the Resurvey Executed by Gentry and Nelson in 1934)
	From the cor. of secs. 4 and 9 only. N. 88° 32' W., bet. secs. 4 and 9.
20.31	Point for the E 1/16 sec. cor. of secs. 4 and 9. Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. S 4 / E 1/16 / S 9 / 1982
40.62	The 1/4 sec. cor. of secs. 4 and 9, monumented with an iron post, 1 in. diam., projecting 10 ins. above the ground with brass cap mkd. as described in the official record of the 1934 resurvey.
	N. 88° 32' W., beginning new measurement.
20.31	Point for the W 1/16 sec. cor. of secs. 4 and 9. Not monumented.
40.62	The cor. of secs. 4, 5, 8, and 9, monumented with an iron post, 2 ins. diam., projecting 8 ins. above the ground, with brass cap mkd. as described in the official record of the 1934 resurvey.

☆U.S. Government Printing Office: 1980—778-251/292

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 17 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS	
	N. 0° 24' W., bet. secs. 4 and 5.
19.99	Point for the S 1/16 sec. cor. of secs. 4 and 5. Not monumented.
39.98	The 1/4 sec. cor. of secs. 4 and 5, monumented with an iron post, 1 in. diam., projecting 8 ins. above the ground, with brass cap mkd. as described in the official record of the 1934 resurvey.

Partial Subdivisional Survey of Section 4, T. 17 S., R. 4 W., Salt Lake Meridian, Utah

	From the 1/4 sec. cor. of secs. 4 and 9.
	N. 0° 48' W., on the N and S center line of sec. 4.
20.00	Point for the center S 1/16 sec. cor. of sec. 4.
	Set an iron post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

C
S 1/16 | S 4
C
1982

	Raise a mound of stone, 4 ft. base, 2 ft. high, W of cor.
40.00	Point for the center 1/4 sec. cor. of sec. 4, at intersection with the E and W center line.
	Set an iron post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 17 S R 4 W
C 1/4 S 4
1982

	Raise a mound of stone, 4 ft. base, 2 ft. high, W of cor.
80.98	The 1/4 sec. cor. of sec. 4 only, on the N. bdy. of the Tp., monumented with an iron post, 1 in. diam., projecting 18 ins. above the ground, and in a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. as described in the official record of the 1934 survey.

	From the 1/4 sec. cor. of sec. 4 only, on the E. bdy. of sec. 4.
	N. 88° 33' W., on the E and W center line of sec. 4.
21.14	Point for the center E 1/16 sec. cor. of sec. 4 at proportionate distance.

Partial Subdivisional Survey of Section 4,
T. 17 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS	
	Set an iron post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top of brass cap, mkd. E 1/16 C S 4 C 1982
41.13	The center 1/4 sec. cor. of sec. 4.
61.30	Point for the center W 1/16 sec. cor. of sec. 4. Set an iron post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd. W 1/16 C S 4 C 1982 Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, N of cor.
81.47	The 1/4 sec. cor. of secs. 4 and 5.
	From the E 1/16 sec. cor. of secs. 4 and 9. N. 1° 15' W., on the N and S center line of the SE 1/4 of sec. 4.
20.01	Point for the SE 1/16 sec. cor. of sec. 4, at intersection with the E and W center line of the SE 1/4 of sec. 4. Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. SE 1/16 S 4 1982
40.02	The center E 1/16 sec. cor. of sec. 4.
	From the S 1/16 sec. cor. of sec. 4 only, on the E. bdy. of sec. 4. N. 88° 33' W., on the E and W center line of the SE 1/4 of sec. 4.
20.73	The SE 1/16 sec. cor. of sec. 4, at intersection with the N and S center line of the SE 1/4 of sec. 4.
40.88	The center S 1/16 sec. cor. of sec. 4.
	From the point for the W 1/16 sec. cor. of secs. 4 and 9. N. 0° 36' W., on the N and S center line of the SW 1/4 of sec. 4.

☆U.S. Government Printing Office: 1980—778-251/292

Partial Subdivision Survey of Section 4,
T. 17 S., R. 4 W., Salt Lake Meridian, Utah

CHAINS	
19.995	Point for the SW 1/16 sec. cor. of sec. 4, at intersection with the E and W center line of the SW 1/4 of sec. 4. Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. SW 1/16 S 4 1982 Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.
39.99	The center W 1/16 sec. cor. of sec. 4.
	From the center S 1/16 sec. cor. of sec. 4. N. 88° 33' W., on the E and W center line of the SW 1/4 of sec. 4.
20.24	The SW 1/4 sec. cor. of sec. 4, at intersection with the N and S center line of the SW 1/4 of sec. 4.
40.48	Point for the S 1/16 sec. cor. of secs. 4 and 5.

General Description

The area surveyed and resurveyed within Township 17 South, Range 4 West is situated about 1 1/2 miles SE of Oak City, Utah. The elevation varies from 5800 feet in the foothills of the canyon mountains in the north portion of section 4 to 5350 feet where Oak Creek passes through the SW corner of section 4. The general drainage is to the west. The road from Oak City to Oak Creek Canyon passes through the SW cor. of section 4. The main use of the land in this area is as pasture.

Form 9180–8
(March 1969)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Gary L. Kratz	Supervisory Cadastral Surveyor
Donzil Q. Worthington	Surveying Technician
Gary D. Gogos	Surveying Technician

485

CERTIFICATE OF SURVEY

(I) XXXX Richard A. Zaninovich , HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 12th day of May , 19 82, (I) (XXX) have dependently resurveyed a portion of the subdivisional lines and surveyed a portion of the subdivision of section 4 of T. 17 S., R. 4 W.,

of the Salt Lake Meridian, in the State of Utah , which are represented in the foregoing field notes as having been executed by (me), (uXXX and under (my) XXXX direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

January 12, 1984
(Date)

(Cadastral Surveyor)
Supervisory

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Washington, D.C.

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines and the survey of a portion of the subdivision of section 4 of T. 17 S., R. 4 W. of the Salt Lake Meridian, Utah

executed by Richard A. Zaninovich, Supervisory Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

February 14, 1984
(Date)

Glen B. Hatch
(~~Chief, Division of Cadastral Survey~~)
Chief Cadastral Surveyor for Utah

~~CERTIFICATE OF TRANSCRIPT~~

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in , is a true copy of the original field notes.

~~(Date)~~

~~(Chief, Division of Cadastral Survey)~~
Chief Cadastral Surveyor for Utah

Form 9600–9
(December 1979)
(formerly 9180–6)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
ORIGINAL

R606

486

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

A PORTION OF THE SUBDIVISIONAL LINES,

A PORTION OF THE SUBDIVISION OF SECTION 26,

AND

THE SURVEY OF TRACT 37

OF

TOWNSHIP 40 SOUTH, RANGE 7 WEST

Of the Salt Lake Meridian,

In the State of Utah.

EXECUTED BY

Milton R. Workman Cadastral Surveyor

Under special instructions dated September 29, 19 82, approved September 29, 1982 and supplemental special instructions dated and approved October 5, 1982

, which provided for the surveys included under U.S. Survey/Group Number 622, and assignment instructions dated September 30, 19 82

Survey commenced October 4, 19 82

Survey completed October 19, 19 82

CHAINS

A portion of the subdivisional lines were surveyed by T.C. Bailey in 1876, a portion surveyed and resurveyed by R.E.L. Collier in 1895, a portion surveyed and resurveyed by Nelson, Bird, and Miller in 1931, and in 1941 Nelson and Bird resurveyed a portion of the subdivisional lines and subdivided section 26, T. 40 S., R. 7 W., Salt Lake Meridian, Utah.

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, a portion of the subdivision of section 26, and the survey of Tract 37, T. 40 S., R. 7 W., Salt Lake Meridian, Utah.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, the Special Instructions dated September 29, 1982, and Supplemental Special Instructions dated October 5, 1982.

The directions of the lines refer to the true meridian, determined by sustained angulation from azimuths obtained from hour angle observations on Polaris, and only true line bearings are given in these field notes.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the N 1/16 sec. cor. of secs. 25 and 26 as scaled from U.S.G.S. Orderville Quadrangle is:

Latitude 37° 18.5' N. Longitude 112° 35.5' W.

The mean magnetic declination is 14¼° East.

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 40 S., R. 7 W., Salt Lake Meridian, Utah

---

(Reestablishment of the Survey Executed by T.C Bailey in 1876 and the Resurvey Executed by Bird and Nelson in 1941)

Beginning from the N 1/16 sec. cor. of secs. 25 and 26, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. as described in the official record of the 1941 resurvey.

N. 0° 31' E., bet. secs. 25 and 26.

18.52 Point for Angle Point No. 4, Tract 37.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

AP-4
T 40 S R 7 W
TR-37 | S 25
S 26 |
1982

488

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 40 S., R. 7 W., Salt Lake Meridian, Utah

CHAINS	
20.02	The cor. of secs. 23, 24, 25, and 26, monumented with an iron post, 2 ins. diam., projecting 10 ins. above ground, with brass cap mkd. as described in the official record of the 1941 resurvey. from which A power pole, bears N. 20° E., 6 lks. dist. This cor. will now also function as Angle Point No. 1, Tract 37. I added AP-1 TR-37 1982 to brass cap.
	(Reestablishment of the Survey Executed by T.C. Bailey in 1876) N. 0° 19' E., bet. secs. 23 and 24.
19.87	Point for the S 1/16 sec. cor. of secs. 23 and 24. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 S R 7 W S 1/16 S 23 | S 24 1982 from which A power pole, bears South, 21 lks. dist. Cor. is located 20 lks. North of the top of spur that slopes W.
39.74	The ¼ sec. cor. of secs. 23 and 24, monumented with a limestone, 12 x 6 x 6 ins., firmly set 8 ins. in the ground, and plainly mkd. ¼ on W face. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 S R 7 W ¼ S 23 | S 24 1982 Deposit the mkd. stone alongside the iron post.
	(Reestablishment of the Survey Executed by T.C. Bailey in 1876 and the Resurvey Executed by Bird and Nelson in 1941 From the cor. of secs. 23, 24, 25, and 26. West, bet. secs. 23 and 26.

☆U.S. Government Printing Office: 1980—778-251/292

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 40 S., R. 7 W., Salt Lake Meridian, Utah

CHAINS	
12.83	Intersect the easterly right-of-way line of U.S. Highway No. 89. Point for Angle Point No. 2, Tract 37. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 S R 7 W S 23 AP-2 S 26 | TR-37 1982
16.98	Point for witness point Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. W P T 40 S R 7 W S 23 S 26 1982
18.96	Intersect the westerly right-of-way line of U.S. Highway No. 89. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. A P T 40 S R 7 W S 23 S 26 1982
19.90	The E 1/16 sec. cor. of secs. 23 and 26, monumented with an iron post, 2 ins. diam., projecting 8 ins. above ground, with brass cap mkd. as described in the official record of the 1941 resurvey.

Dependent Resurvey of a Portion of the Subdivision of Sec. 26, T. 40 S., R. 7 W., Salt Lake Meridian, Utah

(Reestablishment of the Survey Executed by Bird and Nelson in 1941)

	From the CE 1/16 sec. cor. of sec. 26, monumented with an iron post, 2 ins. diam., projecting 10 ins. above ground, with brass cap mkd. as described in the official record of the 1941 survey. N. 0° 34' E., along the N-S center line of the NE¼ of sec. 26.
33.10	Intersect the westerly right-of-way line of U.S. Highway No. 89. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

CHAINS	
	A P T 40 S R 7 W S 26 | 1982
40.02	The E 1/16 sec. cor. of secs. 23 and 26. Note: The NE 1/16 sec. cor. of sec. 26 was removed by highway construction.
	Survey of Tract 37, T. 40 S., R. 7 W., Salt Lake Meridian, Utah
	From Angle Point No. 1, Tract 37, identical with the sec. cor. of secs. 23, 24, 25, and 26, hereinbefore described. West, along line 1-2, identical with a portion of the sec. line bet. secs. 23 and 26.
12.83	Angle Point No. 2, hereinbefore described. Thence, southerly on a curve to the right with a central angle of 1° 04' and a radius of 5408.79 ft. (81.95 chs.)
0.437	A highway right-of-way marker established by the Utah Highway Department in 1962.
1.527	Point for Angle Point No. 3. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. T 40 S R 7 W | TR-37 S 26 | AP-3 1982 Thence, East, along line 3-4.
13.10	Angle Point No. 4, hereinbefore described. Thence, N. 0° 31' E., along line 4-1, identical with a portion of the sec. line bet. secs. 25 and 26.
1.50	Angle Point No. 1 and point of beginning.
	General Description The land encompassed in this survey is adjacent to the S and E boundaries of the city of Glendale. The timber is mainly juniper and pinon. The elevation is about 5800 ft. above sea level.

☆U.S. Government Printing Office: 1980—778-251/292

Form 9600-11
(August 1979)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Ronald K. Baugh	Land Surveyor
Donald A. Buhler	Land Surveyor
Lanny Talbot	Engineering Technician

492

CERTIFICATE OF SURVEY

(I) (~~WE~~), Milton R. Workman, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 29th day of September, 1982, and Supplemental Special Instructions bearing date of the 5th of October, 1982, (I) (~~WE~~) have dependently resurveyed a portion of the subdivisional lines, a portion of the subdivision of section 26, and surveyed Tract 37 of Township 40 South, Range 7 West,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me) (~~XXX~~) and under (my) (~~XXX~~) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

February 9, 1984 — Milton R. Workman
(Date) — (Cadastral Surveyor)

(Date) — (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines, a portion of the subdivision of section 26, and the survey of Tract 37 of Township 40 South, Range 7 West, Salt Lake Meridian, Utah

executed by Milton R. Workman, Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

February 14, 1984 — Glen B Hatch
(Date) — (~~Chief, Cadastral Survey Examination and Approval Staff~~)
Chief Cadastral Surveyor for Utah

~~CERTIFICATE OF TRANSCRIPT~~

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in T. 40 S., R. 7 W., Salt Lake Meridian, Utah is a true copy of the original field notes.

(Date) — (~~Chief, Cadastral Survey Examination and Approval Staff~~)
Chief Cadastral surveyor for Utah

```
2008.11.20 06:29 B T:\field_notes\rectangular_ notes\r0606\r0606-0000.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0000.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0001.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0001.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0002.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0002.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0003.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0003.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0004.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0004.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0005.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0005.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0006.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0006.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0007.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0007.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0008.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0008.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0009.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0009.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0010.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0010.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0011.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0011.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0012.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0012.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0013.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0013.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0014.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0014.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0015.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0015.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0016.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0016.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0017.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0017.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0018.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0018.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0019.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0019.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0020.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0020.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0021.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0021.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0022.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0022.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0023.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0023.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0024.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0024.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0025.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0025.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0026.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0026.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0027.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0027.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0028.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0028.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0029.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0029.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0030.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0030.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0031.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0031.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0032.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0032.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0033.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0033.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0034.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0034.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0035.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0035.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0036.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0036.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0037.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0037.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0038.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0038.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0039.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0039.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0040.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0040.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0041.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0041.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0042.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0042.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0043.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0043.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0044.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0044.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0045.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0045.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0046.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0046.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0047.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0047.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0048.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0048.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0049.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0049.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0050.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0050.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0051.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0051.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0052.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0052.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0053.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0053.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0054.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0054.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0055.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0055.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0056.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0056.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0057.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0057.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0058.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0058.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0059.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0059.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0060.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0060.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0061.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0061.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0062.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0062.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0063.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0063.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0064.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0064.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0065.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0065.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0066.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0066.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0067.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0067.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0068.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0068.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0069.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0069.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0070.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0070.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0071.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0071.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0072.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0072.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0073.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0073.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0074.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0074.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0075.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0075.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0076.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0076.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0077.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0077.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0078.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0078.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0079.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0079.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0080.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0080.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0081.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0081.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0082.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0082.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0083.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0083.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0084.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0084.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0085.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0085.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0086.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0086.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0087.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0087.tif
2008.11.20 06:30 B T:\field_notes\rectangular_ notes\r0606\r0606-0088.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0088.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0089.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0089.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0090.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0090.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0091.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0091.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0092.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0092.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0093.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0093.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0094.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0094.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0095.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0095.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0096.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0096.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0097.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0097.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0098.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0098.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0099.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0099.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0100.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0100.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0101.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0101.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0102.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0102.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0103.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0103.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0104.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0104.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0105.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0105.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0106.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0106.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0107.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0107.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0108.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0108.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0109.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0109.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0110.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0110.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0111.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0111.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0112.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0112.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0113.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0113.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0114.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0114.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0115.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0115.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0116.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0116.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0117.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0117.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0118.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0118.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0119.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0119.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0120.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0120.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0121.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0121.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0122.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0122.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0123.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0123.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0124.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0124.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0125.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0125.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0126.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0126.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0127.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0127.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0128.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0128.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0129.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0129.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0130.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0130.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0131.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0131.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0132.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0132.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0133.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0133.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0134.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0134.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0135.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0135.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0136.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0136.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0137.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0137.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0138.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0138.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0139.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0139.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0140.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0140.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0141.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0141.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0142.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0142.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0143.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0143.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0144.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0144.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0145.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0145.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0146.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0146.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0147.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0147.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0148.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0148.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0149.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0149.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0150.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0150.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0151.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0151.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0152.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0152.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0153.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0153.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0154.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0154.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0155.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0155.tif
2008.11.20 06:31 B T:\field_notes\rectangular_ notes\r0606\r0606-0156.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0156.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0157.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0157.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0158.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0158.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0159.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0159.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0160.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0160.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0161.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0161.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0162.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0162.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0163.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0163.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0164.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0164.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0165.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0165.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0166.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0166.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0167.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0167.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0168.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0168.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0169.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0169.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0170.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0170.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0171.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0171.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0172.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0172.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0173.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0173.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0174.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0174.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0175.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0175.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0176.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0176.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0177.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0177.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0178.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0178.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0179.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0179.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0180.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0180.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0181.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0181.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0182.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0182.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0183.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0183.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0184.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0184.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0185.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0185.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0186.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0186.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0187.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0187.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0188.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0188.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0189.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0189.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0190.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0190.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0191.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0191.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0192.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0192.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0193.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0193.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0194.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0194.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0195.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0195.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0196.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0196.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0197.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0197.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0198.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0198.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0199.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0199.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0200.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0200.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0201.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0201.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0202.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0202.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0203.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0203.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0204.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0204.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0205.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0205.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0206.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0206.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0207.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0207.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0208.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0208.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0209.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0209.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0210.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0210.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0211.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0211.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0212.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0212.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0213.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0213.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0214.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0214.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0215.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0215.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0216.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0216.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0217.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0217.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0218.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0218.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0219.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0219.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0220.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0220.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0221.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0221.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0222.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0222.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0223.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0223.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0224.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0224.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0225.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0225.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0226.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0226.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0227.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0227.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0228.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0228.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0229.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0229.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0230.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0230.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0231.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0231.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0232.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0232.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0233.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0233.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0234.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0234.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0235.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0235.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0236.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0236.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0237.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0237.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0238.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0238.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0239.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0239.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0240.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0240.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0241.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0241.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0242.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0242.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0243.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0243.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0244.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0244.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0245.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0245.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0246.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0246.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0247.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0247.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0248.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0248.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0249.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0249.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0250.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0250.tif
2008.11.20 06:32 B T:\field_notes\rectangular_ notes\r0606\r0606-0251.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0251.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0252.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0252.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0253.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0253.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0254.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0254.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0255.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0255.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0256.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0256.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0257.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0257.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0258.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0258.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0259.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0259.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0260.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0260.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0261.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0261.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0262.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0262.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0263.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0263.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0264.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0264.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0265.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0265.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0266.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0266.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0267.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0267.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0268.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0268.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0269.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0269.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0270.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0270.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0271.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0271.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0272.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0272.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0273.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0273.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0274.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0274.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0275.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0275.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0276.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0276.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0277.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0277.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0278.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0278.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0279.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0279.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0280.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0280.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0281.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0281.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0282.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0282.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0283.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0283.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0284.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0284.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0285.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0285.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0286.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0286.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0287.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0287.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0288.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0288.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0289.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0289.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0290.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0290.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0291.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0291.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0292.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0292.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0293.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0293.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0294.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0294.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0295.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0295.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0296.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0296.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0297.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0297.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0298.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0298.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0299.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0299.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0300.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0300.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0301.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0301.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0302.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0302.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0303.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0303.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0304.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0304.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0305.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0305.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0306.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0306.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0307.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0307.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0308.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0308.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0309.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0309.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0310.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0310.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0311.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0311.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0312.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0312.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0313.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0313.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0314.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0314.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0315.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0315.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0316.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0316.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0317.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0317.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0318.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0318.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0319.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0319.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0320.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0320.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0321.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0321.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0322.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0322.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0323.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0323.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0324.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0324.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0325.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0325.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0326.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0326.tif
2008.11.20 06:33 B T:\field_notes\rectangular_ notes\r0606\r0606-0327.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0327.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0328.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0328.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0329.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0329.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0330.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0330.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0331.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0331.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0332.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0332.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0333.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0333.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0334.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0334.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0335.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0335.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0336.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0336.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0337.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0337.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0338.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0338.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0339.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0339.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0340.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0340.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0341.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0341.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0342.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0342.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0343.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0343.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0344.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0344.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0345.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0345.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0346.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0346.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0347.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0347.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0348.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0348.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0349.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0349.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0350.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0350.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0351.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0351.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0352.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0352.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0353.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0353.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0354.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0354.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0355.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0355.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0356.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0356.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0357.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0357.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0358.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0358.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0359.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0359.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0360.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0360.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0361.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0361.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0362.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0362.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0363.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0363.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0364.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0364.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0365.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0365.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0366.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0366.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0367.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0367.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0368.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0368.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0369.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0369.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0370.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0370.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0371.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0371.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0372.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0372.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0373.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0373.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0374.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0374.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0375.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0375.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0376.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0376.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0377.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0377.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0378.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0378.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0379.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0379.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0380.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0380.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0381.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0381.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0382.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0382.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0383.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0383.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0384.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0384.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0385.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0385.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0386.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0386.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0387.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0387.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0388.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0388.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0389.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0389.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0390.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0390.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0391.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0391.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0392.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0392.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0393.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0393.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0394.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0394.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0395.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0395.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0396.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0396.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0397.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0397.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0398.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0398.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0399.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0399.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0400.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0400.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0401.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0401.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0402.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0402.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0403.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0403.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0404.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0404.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0405.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0405.tif
2008.11.20 06:34 B T:\field_notes\rectangular_ notes\r0606\r0606-0406.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0406.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0407.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0407.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0408.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0408.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0409.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0409.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0410.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0410.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0411.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0411.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0412.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0412.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0413.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0413.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0414.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0414.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0415.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0415.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0416.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0416.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0417.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0417.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0418.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0418.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0419.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0419.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0420.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0420.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0421.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0421.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0422.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0422.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0423.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0423.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0424.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0424.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0425.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0425.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0426.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0426.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0427.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0427.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0428.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0428.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0429.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0429.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0430.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0430.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0431.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0431.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0432.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0432.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0433.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0433.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0434.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0434.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0435.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0435.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0436.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0436.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0437.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0437.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0438.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0438.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0439.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0439.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0440.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0440.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0441.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0441.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0442.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0442.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0443.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0443.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0444.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0444.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0445.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0445.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0446.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0446.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0447.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0447.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0448.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0448.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0449.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0449.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0450.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0450.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0451.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0451.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0452.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0452.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0453.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0453.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0454.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0454.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0455.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0455.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0456.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0456.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0457.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0457.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0458.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0458.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0459.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0459.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0460.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0460.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0461.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0461.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0462.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0462.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0463.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0463.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0464.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0464.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0465.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0465.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0466.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0466.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0467.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0467.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0468.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0468.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0469.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0469.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0470.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0470.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0471.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0471.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0472.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0472.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0473.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0473.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0474.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0474.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0475.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0475.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0476.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0476.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0477.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0477.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0478.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0478.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0479.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0479.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0480.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0480.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0481.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0481.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0482.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0482.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0483.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0483.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0484.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0484.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0485.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0485.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0486.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0486.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0487.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0487.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0488.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0488.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0489.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0489.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0490.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0490.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0491.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0491.tif
2008.11.20 06:35 B T:\field_notes\rectangular_ notes\r0606\r0606-0492.tif --> ut.wc.blm.gov /ext/doc/LandRecords/Survey_Plats/fieldnotes r0606-0492.tif
```