





# INDEX DIAGRAM

Township 13 South, Range 17 East,

2						
6	8	5	4	3	2	1
8		7				
7	7	8	9	10	11	12
6		6				
18	5	17	16	15	14	13
5		5				
19	4	20	21	22	23	24
4		3				
30	3	29	28	27	26	25
2						
31	2	32	33	34	35	36

Subdivision of Section 19 - Page 9

## Township 13 South, Range 17 East, Salt Lake Meridian, Utah

## CHAINS

The following field notes are those of the dependent resurvey of a portion of the south boundary of T. 12 S., R. 17 E., a portion of the subdivisional lines, the survey of a portion of the subdivisional lines and the subdivision of section 19 in T. 13 S., R. 17 E., Salt Lake Meridian, Utah.

History of Surveys

	<u>Surveyed by</u>	<u>Retr. or Resurveyed by</u>
--	--------------------	-------------------------------

NORTH BOUNDARY

W. 2 miles	C.P. Sylvester	1961
------------	----------------	------

SOUTH BOUNDARY

W. 2 miles	C.P. Sylvester	1961
------------	----------------	------

EAST BOUNDARY

A11	M. R. Workman and R. Harpin	1969 1981
-----	--------------------------------	--------------

WEST BOUNDARY

A11	C.P. Sylvester	1961
-----	----------------	------

SUBDIVISIONAL LINES

Portion	C.P. Sylvester	1961
---------	----------------	------

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 630, Utah, dated May 23, 1983.

The directions of all lines were determined by observations on Polaris and direct altitude observations of the Sun. The lines were carried forward by sustained angulation throughout the township.

Preliminary to the resurvey the lines of the original survey were retraced and search made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the southeast corner of sec. 30, as determined by a tie to the United States Coast and Geodetic Survey triangulation station "ROCK" is as follows:

Latitude 39° 39' 28.588" N. Longitude 110° 02' 39.418" W.

NOTE: Tie to "ROCK" was made in the concurrent resurvey of T. 13 S., R. 16 E.

The mean magnetic declination is 14° East.

Dependent Resurvey of the South Boundary of Section 31,  
T. 12 S., R. 17 E., Salt Lake Meridian, Utah

Dependent Resurvey of the South Boundary of Section 31,  
T. 12 S., R. 17 E., Salt Lake Meridian, Utah

CHAINS	
	<p>From the corner. of secs. 5, 6, 31, and 32, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above a mound of stone, with brass cap, mkd. as described in the official record of the 1961 survey of a portion of the S. bdy. of T. 12 S., R. 17 E. I remarked the brass cap to function as the cor of secs. 31 and 32 only, T. 12 S., R. 17 E.</p> <p>West, along the S. bdy. of sec. 31.</p>
0.37	Point for the closing cor. of secs. 5 and 6, T. 13 S., R. 17 E., hereinafter described.
40.00	The ¼ sec. cor. of secs. 6 and 31. I remarked this cor. to function as the S¼ sec. cor. of sec. 31, T. 12 S., R. 17 E.
40.37	Point for the N¼ sec. cor. of sec. 6, T. 13 S., R. 17 E., hereinafter described.
78.15	The cor. of Tps. 12 and 13 S., Rs. 16 and 17 E., monumented with an iron post, 2½ ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the official record of the 1961 survey of the S. bdy. of T. 12 S., R. 16 E.
<p>Dependent Resurvey of the North Half Mile Between Sections 31 and 32, T. 13 S., R. 17 E., Salt Lake Meridian, Utah</p>	
	<p>From the ¼ sec. cor. of secs. 31 and 32, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1961 survey.</p> <p>N. 0° 04' E., bet. secs. 31 and 32.</p>
39.82	The cor. of secs. 29, 30, 31, and 32, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1961 survey.
<p>Survey of a Portion of the Subdivisional Lines, T. 13 S., R. 17 E., Salt Lake Meridian, Utah</p>	
	<p>From the cor. of secs. 29, 30, 31, and 32.</p> <p>N. 89° 47' W., bet. secs. 30 and 31.</p> <p>Over rough and broken land, through scattered juniper and pinon timber.</p>
40.00	Point for the ¼ sec. cor. of secs. 30 and 31.
	<p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 13 S R 17 E S 30 ¼ <u>    </u> S 31 1983</p>

Survey of a Portion of the Subdivisional Lines,  
T. 13 S., R. 17 E., Salt Lake Meridian, Utah

CHAINS	
78.02	<p>Raise a mound of stone, 3½ ft. base, 1½ ft. high, N of cor.</p> <p>The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1961 survey of the E. bdy. of T. 13 S., R. 16 E.</p>
40.00	<p>From the cor. of secs. 29, 30, 31, and 32.</p> <p>N. 0° 10' E., bet. secs. 29 and 30.</p> <p>Over broken land, through scattered juniper and pinon timber.</p> <p>Point for the ¼ sec. cor. of secs. 29 and 30.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 13 S R 17 E</p> <p>       </p> <p>      ¼</p> <p>       </p> <p>S 30   S 29</p> <p>       </p> <p>      1983</p> </div>
80.00	<p>Raise a mound of stone, 3½ ft. base, 1½ ft. high, W of cor.</p> <p>Cor. is located on a steep and rocky N slope.</p> <p>Point for the cor. of secs. 19, 20, 29, and 30.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4½ ft. base, to top of aluminum cap, mkd.</p> <div style="text-align: center;"> <p>T 13 S R 17 E</p> <p>S 19   S 20</p> <p>S 30   S 29</p> <p>      1983</p> </div>
40.02	<p>From the cor. of secs. 20, 21, 28, and 29, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above a mound of stone, with brass cap, mkd. as described in the official record of the 1961 survey of a portion of the subdivisional lines of T. 13 S., R. 17 E.</p> <p>S. 89° 56' W., bet. secs. 20 and 29.</p> <p>Over broken land, through scattered juniper and pinon timber.</p> <p>Point for the ¼ sec. cor. of secs. 20 and 29.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.</p>

Survey of a Portion of the Subdivisional Lines,  
T. 13 S., R. 17 E., Salt Lake Meridian, Utah

CHAINS		
80.04	<p style="text-align: center;">T 13 S R 17 E  <math>\frac{1}{4}</math> <math>\frac{S 20}{S 29}</math>            1983</p> <p>The cor. of secs. 19, 20, 29, and 30.</p>	
40.00	<p>N. 89° 47' W., bet. secs. 19 and 30.</p> <p>Over rough and broken land, through scattered juniper and pinon timber.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 19 and 30.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.</p> <p style="text-align: center;">T 13 S R 17 E  <math>\frac{1}{4}</math> <math>\frac{S 19}{S 30}</math>            1983</p>	
78.00	<p>The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the official record of the 1961 survey of the E. bdy. of T. 13 S., R. 16 E.</p> <p>From the cor. of secs. 19, 20, 29, and 30.</p> <p>N. 0° 10' E., bet. secs. 19 and 20.</p> <p>Over rough and broken land, through scattered juniper and pinon timber.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 19 and 20, falls on sandstone boulder and cannot be monumented.</p> <p>Point selected for the witness cor. to the <math>\frac{1}{4}</math> sec. cor. of secs. 19 and 20.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4½ ft. base, to top of aluminum cap, mkd.</p> <p style="text-align: center;">W C            T 13 S R 17 E  <math>\frac{1}{4}</math>            S 19   S 20            ↓            1983</p> <p>Point for the cor. of secs. 17, 18, 19, and 20.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.</p> <p style="text-align: center;">T 13 S R 17 E            S 18   S 17            S 19   S 20            1983</p>	

Survey of a Portion of the Subdivisional Lines,  
T. 13 S., R. 17 E., Salt Lake Meridian, Utah

CHAINS		
40.03	<p>From the true point for the cor. of secs. 16, 17, 20, and 21, from which the witness cor., monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above a mound of stone, with brass cap, mkd. as described in the official record of the 1961 survey of a portion of the subdivisional lines of T. 13 S., R. 17 E., bears S. 0° 10' W., 3.90 chs. dist.</p> <p>N. 89° 55' W., bet. secs. 17 and 20.</p> <p>Over rough and broken land, through scattered juniper and pinon timber.</p> <p>Point for the ¼ sec. cor. of secs. 17 and 20.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">T 13 S R 17 E           S 17 ¼     S 20           1983</p>	
80.06	<p>The cor. of secs. 17, 18, 19, and 20.</p> <p>N. 89° 52' W., bet. secs. 18 and 19.</p> <p>Over rough and broken land, through scattered juniper and pinon timber.</p> <p>40.00 Point for the ¼ sec. cor. of secs. 18 and 19.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">T 13 S R 17 E           S 18 ¼     S 19           1983</p>	
77.97	<p>The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1961 survey of the E. bdy. of T. 13 S., R. 16 E.</p> <p>From the cor. of secs. 17, 18, 19, and 20.</p> <p>N. 0° 10' E., bet. secs. 17 and 18.</p> <p>Over rough and broken land, through scattered juniper and pinon timber.</p> <p>39.84 Point selected for the witness cor. to the ¼ sec. cor. of secs. 17 and 18.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.</p>	

Survey of a Portion of the Subdivisional Lines,  
T. 13 S., R. 17 E., Salt Lake Meridian, Utah

CHAINS	
<p>40.00</p> <p>80.00</p>	<div style="text-align: center;"> <p>W C</p> <p>T 13 S R 17 E</p> <p>↑</p> <p>1/4</p> <p>S 18   S 17</p> <p>1983</p> </div> <p>Point for the 1/4 sec. cor. of secs. 17 and 18, falls on face of small ledge and cannot be monumented.</p> <p>Point for the cor. of secs. 7, 8, 17, and 18.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 13 S R 17 E</p> <p>S 7   S 8</p> <p>S 18   S 17</p> <p>1983</p> </div> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.</p> <p>Cor. is located on gentle S slope, 40 lks. N of dirt road, bears E and W.</p>
<p>40.06</p>	<p>From the cor. of secs. 8, 9, 16, and 17, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above mound of stone, with brass cap, mkd. as described in the official record of the 1961 survey of a portion of the subdivisional lines in T. 13 S., R. 17 E.</p> <p>S. 89° 53' W., bet. secs. 8 and 17.</p> <p>Over rough and broken land, through scattered juniper and pinon timber.</p> <p>Point for the 1/4 sec. cor. of secs. 8 and 17.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 13 S R 17 E</p> <p>S 8</p> <p>1/4 — S 17</p> <p>1983</p> </div> <p>The cor. of secs. 7, 8, 17, and 18.</p>
<p>40.00</p>	<p>N. 89° 58' W., bet. secs. 7 and 18.</p> <p>Over rough and broken land, through scattered juniper and pinon timber.</p> <p>Point for the 1/4 sec. cor. of secs. 7 and 18.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p>

Survey of a Portion of the Subdivisional Lines,  
T. 13 S., R. 17 E., Salt Lake Meridian, Utah

CHAINS		
77.94	<p style="text-align: center;">T 13 S R 17 E  <math>\frac{1}{4}</math> <math>\frac{S 7}{S 18}</math>            1983</p> <p>The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1961 survey of the E. bdy. of T. 13 S., R. 16 E.</p>	
40.00	<p>From the cor. of secs. 7, 8, 17, and 18.</p> <p>N. 0° 10' E., bet. secs. 7 and 8.</p> <p>Over rough and broken land, through scattered juniper and pinon timber.</p> <p>Point for the ¼ sec. cor. of secs. 7 and 8, falls on steep and ledgy N slope of "Jack Canyon" and cannot be monumented.</p>	
48.81	<p>Point selected for a witness point bet. secs. 7 and 8.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.</p> <p style="text-align: center;">W P            T 13 S R 17 E                         S 7   S 8                         1983</p>	
80.00	<p>True point for the cor. of secs. 5, 6, 7, and 8, falls near face of ledge and is unsafe to monument.</p> <p>From the true point for the cor. of secs. 4, 5, 8, and 9, from which the witness cor., an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above mound of stone, with brass cap, mkd. as described in the official record of the 1961 survey of a portion of the subdivisional lines of T. 13 S., R. 17 E., bears N. 0° 12' E., 2.04 chs. dist.</p> <p>N. 89° 59' W., bet. secs. 5 and 8.</p> <p>Over rough and broken land, through scattered juniper and pinon timber.</p>	
40.04	<p>True point for the ¼ sec. cor. of secs. 5 and 8, falls on edge of boulder and cannot be monumented.</p>	
40.09	<p>Point selected for the witness cor. to the ¼ sec. cor. of secs. 5 and 8.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 5 ft. base, to top of aluminum cap, mkd.</p>	

Survey of a Portion of the Subdivisional Lines,  
T. 13 S., R. 17 E., Salt Lake Meridian, Utah

CHAINS		
80.08	<p style="text-align: center;">W C T 13 S R 17 E <math>\frac{1}{4}</math> <math>\frac{S 5}{S 8}</math> <math>\rightarrow</math> 1983</p> <p>True point for the cor. of secs. 5, 6, 7, and 8.</p>	
40.00	<p>N. 89° 58' W., bet. secs. 6 and 7.</p> <p>Over rough and broken land, through scattered juniper and pinon timber.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 6 and 7.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 15 ins in the ground to bedrock, and in a mound of stone, 3½ ft. base, to top of aluminum cap mkd.</p>	
77.90	<p style="text-align: center;">T 13 S R 17 E <math>\frac{1}{4}</math> <math>\frac{S 6}{S 7}</math> 1983</p> <p>Cor. is located on steep E slope.</p> <p>The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1961 survey of the E. bdy. of T. 13 S., R. 16 E.</p>	
0.15	<p>From the true point for the cor. of secs. 5, 6, 7, and 8.</p> <p>N. 0° 10' E., bet. secs. 5 and 6.</p> <p>Over rough and broken land, through scattered juniper and pinon timber.</p> <p>Point selected for the witness cor. to the cor. of secs. 5, 6, 7, and 8.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.</p>	
39.87	<p style="text-align: center;">W C T 13 S R 17 E <math>\frac{S 6}{S 7}</math>   <math>\frac{S 5}{S 8}</math> 1983</p> <p>Witness cor. is located on steep E slope of side canyon which drains SE into Jack Canyon.</p> <p>Intersect the S. bdy. of sec. 31, T. 12 S., R. 17 E.</p> <p>Point for the closing cor. of secs. 5 and 6.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base, to top of aluminum cap, mkd.</p>	

Survey of a Portion of the Subdivisional Lines,  
T. 13 S., R. 17 E., Salt Lake Meridian, Utah

CHAINS	
	<p style="text-align: center;">T 12 S R 17 E S 31 ----- S 6   S 5   C C T 13 S 1983</p> <p>From this point, the cor. of secs. 31 and 32 only, T. 12 S., R. 17 E., hereinbefore described, bears East, 0.37 chs. dist.</p>
	<p>Point for the <math>\frac{N}{4}</math> sec. cor. of sec. 6, is 40.00 chs. West of the closing cor. of secs. 5 and 6.</p> <p>Set an aluminum post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.</p> <p style="text-align: center;">T 12 S R 17 E ----- <math>\frac{1}{4}</math> S 6 T 13 S 1983</p> <p>From this cor., the <math>S\frac{1}{4}</math> sec. cor. of sec. 31, T. 12 S., R. 17 W., hereinbefore described bears East, 0.37 chs. dist.</p>
	<p style="text-align: center;">Subdivision of Section 19, T. 13 S., R. 17 E., Salt Lake Meridian, Utah</p>
39.97	<p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 19 and 30.</p> <p>N. <math>0^{\circ} 10'</math> E., on the N and S center line of sec. 19.</p> <p>Over broken land, through scattered juniper and pinon timber.</p> <p>Point for the center <math>\frac{1}{4}</math> sec. cor. of sec. 19, at intersection with the E and W center line.</p> <p>Set an aluminum post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 5 ins. in the ground to bedrock, and in a mound of stone, 5 ft. base, to top of aluminum cap, mkd.</p>
79.94	<p style="text-align: center;">T 13 S R 17 E C <math>\frac{1}{4}</math> S 19 1983</p> <p>The <math>\frac{1}{4}</math> sec. cor. of secs. 18 and 19.</p>
40.00	<p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 19 and 20.</p> <p>N. <math>89^{\circ} 49'</math> W., on the E and W center line of sec. 19.</p> <p>Over broken land, through scattered juniper and pinon timber.</p> <p>The center <math>\frac{1}{4}</math> sec. cor. of sec. 19.</p>

Subdivision of Section 19,  
T. 13 S., R. 17 E., Salt Lake Meridian, Utah

<p>CHAINS</p> <p>77.99</p>	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 19 and 24, on the W. bdy. of the Tp., monumented with an iron post, <math>2\frac{1}{2}</math> ins. diam., firmly set, projecting 6 ins. above a mound of stone, with brass cap, mkd. as described in the official record of the 1961 survey of the E. bdy. of T. 13 S., R. 16 E.</p>	
	<p style="text-align: center;">General Description</p> <p>The land in the west portion of T. 13 S., R. 17 E., is mostly rough and broken terrain. The elevation ranges from 4400 ft. to 6800 ft. above sea level. There is scattered juniper and pinon timber over most of this portion of the township. The area is drained in an easterly direction by Flat Canyon, Cedar Ridge and Jack Creek, all draining into the Green River which flows southerly through the central portion of the township. There is one road in the township which is located in the central portion, along the top of Cedar Ridge and bears easterly to the west rim of the Green River.</p>	





UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

R608

15

ORIGINAL  
FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

A PORTION OF THE NORTH BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES

AND

THE SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,

OF

TOWNSHIP 13 SOUTH, RANGE 16 EAST

Of the Salt Lake Meridian,

In the State of Utah

EXECUTED BY

Jerry L. Thomas Supervisory Cadastral Surveyor

Under special instructions dated May 23, 1983, approved May 24, 1983

, which provided for the surveys included under ~~U.S. Survey~~/Group  
Number 630, and assignment instructions dated May 24, 1983.

Survey commenced June 6, 19 83

Survey completed July 13, 19 83

UNITED STATES DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SECTION 16

# INDEX DIAGRAM

Township 13 South, Range 16 East,

			2		
6	5	4 9	8 17	2 3	1 13
7	8	9 8 9	10 17 17	11 13 16	12 12
18	17	16 7	15 16 15	14 12 15	13 11
19	20	21 6	22 14 5	23 11 14	24 11
30	29	28	27 4	26 10 14	25
31	32	33	34 3	35	36

## Township 13 South, Range 16 East, Salt Lake Meridian, Utah

## CHAINS

The following field notes are those of the dependent resurvey of a portion of the north boundary, a portion of the subdivisional lines, and the survey of a portion of the subdivisional lines in T. 13 S., R. 16 E., Salt Lake Meridian, Utah.

History of Surveys

<u>Surveyed by</u>	<u>Retr. or Resurveyed by</u>
--------------------	-------------------------------

NORTH BOUNDARY

Portion	H.D. Heist and J.H. Winwood	1908
Portion	C.P. Sylvester	1961

SOUTH BOUNDARY

Portion	H.D. Heist and J.H. Winwood	1908
Portion	C.P. Sylvester	1961

EAST BOUNDARY

All	C.P. Sylvester	1961
-----	----------------	------

WEST BOUNDARY

Portion	H.D. Heist and J.H. Winwood	1908
---------	--------------------------------	------

SUBDIVISIONAL LINES

Portion	H.D. Heist and J.H. Winwood	1908
Portion	C.P. Sylvester	1961

The resurvey and survey were executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 630, Utah, dated May 23, 1983.

The directions of all lines were determined by observations on Polaris and direct altitude observations of the Sun. The lines were carried forward by sustained angulation throughout the township.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the southeast corner of section 26, as determined by a tie to the United States Coast and Geodetic Survey triangulation station "ROCK" is as follows:

Latitude 39° 39' 28.83" N. Longitude 110° 04' 52.74" W.

The mean magnetic declination is 14° E.

Dependent Resurvey of the North Boundary of Section 3,  
T. 13 S., R. 16 E., Salt Lake Meridian, Utah

CHAINS

Dependent Resurvey of the North Boundary of Section 3,  
T. 13 S., R. 16 E., Salt Lake Meridian, Utah

(Restoring the Survey Executed by  
H.D. Heist and J.H. Winwood in 1908)

Beginning at the cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1961 survey of a portion of the N. bdy. of T. 13 S., R. 16 E.

N. 89° 57' W., bet. secs. 3 and 34.

Over broken land.

40.75 The ¼ sec. cor. of secs. 3 and 34, monumented with a sandstone, 11 x 10 x 9 ins., firmly set, projecting 6 ins. above ground, plainly mkd. ¼ on N face, from which the original bearing trees

A pinon, 5 ins. diam., bears S. 25° E., 4 lks. dist., mkd. ¼ S3 BT.

A juniper, 12 ins. diam., bears N. 25° W., 36½ lks. dist., mkd. ¼ S34 BT.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 12 S R 16 E  
¼ S 34  
S 3  
T 13 S  
1983

Deposit the mkd. stone alongside the iron post.

N. 89° 57' W., beginning new measurement.

40.01 The cor. of secs. 3, 4, 33, and 34, monumented with a sandstone, 12 x 8 x 4 ins., firmly set, projecting 6 ins. above ground, plainly mkd. 5 notches on S and 3 notches on E edge, from which the original bearing trees

A pinon, 14 ins. diam., bears N. 75° E., 60 lks. dist., mkd. T12S R16E S34 BT. (Record, N. 61° E.)

A pinon, 10 ins. diam., bears S. 74° W., 29 lks. dist., mkd. T13S R16E S4 BT. (Record, S. 74° 30' W., 28 lks. dist.)

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

Dependent Resurvey of the North Boundary of Section 3,  
T. 13 S., R. 16 E., Salt Lake Meridian, Utah

CHAINS	
	<p style="text-align: center;">T 12 S R 16 E S 33   S 34 S 4   S 3 T 13 S 1983</p>
	<p>Deposit the mkd. stone alongside the aluminum post.</p>
	<p style="text-align: center;">Dependent Resurvey of a Portion of the Subdivisional Lines, T. 13 S., R. 16 E., Salt Lake Meridian, Utah</p> <p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 2 and 11, monumented with an iron post, <math>2\frac{1}{2}</math> ins. diam., firmly set, projecting 6 ins. above a mound of stone, with brass cap, mkd. as described in the official record of the 1961 survey. I destroyed the markings pertaining to sec. 11. This cor. now functions as the S <math>\frac{1}{4}</math> sec. cor. of sec. 2. I add the marks 1983 to the brass cap.</p> <p>S. <math>89^{\circ} 58' W.</math>, bet. secs. 2 and 11.</p>
0.68	<p>Point for the N <math>\frac{1}{4}</math> sec. cor. of sec. 11, at 40.00 chs. easting from the closing cor. of secs. 10 and 11, hereinafter described.</p>
39.96	<p>The cor. of secs. 2, 3, 10, and 11, monumented with an iron post, <math>2\frac{1}{2}</math> ins. diam., firmly set, projecting 6 ins. above a mound of stone, with brass cap, mkd. as described in the official record of the 1961 survey. I destroyed the markings pertaining to secs. 10 and 11. This cor. now functions as the cor. of secs. 2 and 3 only. I add the marks 1983 to brass cap.</p> <p>From this cor., U.S.C. &amp; G.S. triangulation station "ROCK", bears N. <math>58^{\circ} 39' 43'' E.</math>, 145.663 chs.</p>
40.11	<p>From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., monumented with an iron post, <math>2\frac{1}{2}</math> ins. diam., projecting 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1961 survey of a portion of the S. bdy. of T. 13 S., R. 16 E.</p> <p>N. <math>0^{\circ} 04' W.</math>, bet. secs. 34 and 35.</p> <p>Over broken land, through thick pinon and juniper timber.</p> <p>The <math>\frac{1}{4}</math> sec. cor. of secs. 34 and 35, monumented with a sandstone, 12 x 8 x 4 ins., firmly set, projecting 6 ins. above ground, plainly mkd. <math>\frac{1}{4}</math> on W face, from which the original bearing trees</p> <p style="padding-left: 40px;">A pinon, 24 ins. diam., bears S. <math>42^{\circ} E.</math>, 13 lks. dist., mkd. <math>\frac{1}{4}</math> S35 BT. (Record, S. <math>48^{\circ} E.</math>, 12 lks. dist.).</p> <p style="padding-left: 40px;">A cedar, 15 ins. diam., bears N. <math>40^{\circ} W.</math>, 23 lks. dist., mkd. <math>\frac{1}{4}</math> S34 BT. (Record, N. <math>45^{\circ} W.</math>).</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 13 S., R. 16 E., Salt Lake Meridian, Utah

CHAINS

T 13 S R 16 E  
 $\frac{1}{4}$   
 S 34 | S 35  
 1983

Deposit the mkd. stone alongside the aluminum post.

Cor. is located 3.00 chs. N of draw, drains SE.

N. 0° 02' E., beginning new measurement.

40.05 The cor. of secs. 26, 27, 34, and 35, monumented with a sandstone, 8 x 6 x 4 ins., firmly set, projecting 4 ins. above ground, plainly mkd. 2 notches on E and 1 notch on S edge, from which the original bearing trees

A pinon, 14 ins. diam., bears N. 68° E., 32 lks. dist., mkd. T13S R16E S26 BT. (Record, N. 67° E., 31 lks. dist.).

A pinon, 10 ins. diam., bears S. 66° E., 44 lks. dist., mkd. T13S R16E S35 BT. (Record, S. 69° E.).

A cedar, 12 ins. diam., bears S. 33° W., 3 lks. dist., mkd. T13S R16E S34 BT. (Record, S. 27° W.).

A fallen dead pinon, the stumphole bears N. 8° W., 29 lks. dist. (Record, 30 lks. dist.).

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base, to top of aluminum cap, mkd.

T 13 S R 16 E  
 S 27 | S 26  
 S 34 | S 35  
 1983

Deposit the mkd. stone alongside the aluminum post.

N. 0° 05' E., bet. secs. 26 and 27.

Over broken bench land, through thick juniper and pinon timber.

40.08 The ¼ sec. cor. of secs. 26 and 27, monumented with a sandstone, 15 x 10 x 4 ins., firmly set, projecting 3 ins. above ground, plainly mkd. ¼ on W face, from which the original bearing trees

A pinon, 12 ins. diam., bears N. 23° E., 43 lks. dist., mkd. ¼ S26 BT. (Record, N. 18° E.).

A pinon, 18 ins. diam., bears S. 79° W., 80½ lks. dist., mkd. ¼ S27 BT. (Record, S. 80° W., 80 lks. dist.).

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 13 S., R. 16 E., Salt Lake Meridian, Utah

CHAINS

T 13 S R 16 E

	¼	
S 27		S 26
	1983	

Deposit the mkd. stone alongside the aluminum post.

N. 0° 03' W., beginning new measurement.

40.00 The cor. of secs. 22, 23, 26, and 27, monumented with a limestone, 15 x 12 x 5 ins., firmly set, projecting 5 ins. above ground, plainly mkd. 2 notches on S and E edges, from which the original bearing trees

A pinon, 13 ins. diam., bears N. 8° E., 60 lks.  
dist., mkd. T13S R16E S23 BT.

A pinon, 12 ins. diam., bears S. 19° E., 74 lks.  
dist., mkd. T13S R16E S26 BT. (Record, 73 lks.).

A pinon, 14 ins. diam., bears S. 12° W., 64 lks.  
dist., mkd. T13S R16E S27 BT.

A pinon, 7 ins. diam., bears N. 73° W., 57 lks.  
dist., mkd. T13S R16E S22 BT.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base, to top of aluminum cap, mkd.

T 13 S R 16 E

S 22		S 23
S 27		S 26
	1983	

Deposit the mkd. stone alongside the aluminum post.

S. 89° 32' W., bet. secs. 22 and 27.

Over broken land, through thick juniper and pinon timber.

40.17 The ¼ sec. cor. of secs. 22 and 27, monumented with a sandstone, 15 x 12 x 4 ins., firmly set, projecting 8 ins. above ground, dimly mkd. ¼ on N face, from which the original bearing trees

A pinon, 16 ins. diam., bears N. 27° E., 66½ lks.  
dist., mkd. ¼ S22 BT. (Record, N. 26° E., 68 lks.  
dist.).

A cedar, 14 ins. diam., bears S. 37° E., 13 lks.  
dist., mkd. ¼ S27 BT.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base, to top of aluminum cap mkd.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 13 S., R. 16 E., Salt Lake Meridian, Utah

CHAINS

T 13 S R 16 E  
 $\frac{1}{4}$   $\frac{S 22}{S 27}$   
 1983

Deposit the dimly mkd. stone alongside the aluminum post.

S. 89° 57' W., beginning new measurement.

40.22 The cor. of secs. 21, 22, 27, and 28, monumented with a sandstone, 10 x 6 x 5 ins., projecting 6 ins. above ground, plainly mkd. 2 notches on S and 3 notches on E edges, from which the original bearing trees

A pinon, 7 ins. diam., bears N. 86° E., 50 lks.  
 dist., mkd. T13S R16E S22 BT. (Record, N. 87° E.).

A pinon, 9 ins. diam., bears S. 60° E., 34 lks.  
 dist., mkd. T13S R16E S27 BT. (Record, S. 59° E.).

A pinon, 7 ins. diam., bears S. 21° W., 8 lks.  
 dist., mkd. T13S R16E S28 BT. (Record, S. 19° W.).

A juniper, 6 ins. diam., bears N. 55° W., 19 lks.  
 dist., mkd. T13S R16E S21 BT. (Record, N. 60° W.).

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 13 S R 16 E  
 $\frac{S 21}{S 28}$  |  $\frac{S 22}{S 27}$   
 1983

Deposit the mkd. stone alongside the aluminum post.

N. 0° 01' W., bet. secs. 21 and 22.

Over broken land, through thick juniper and pinon timber.

40.04 The ¼ sec. cor. of secs. 21 and 22, monumented with a sandstone, 15 x 12 x 4 ins., firmly set, projecting 3 ins. above ground, plainly mkd. ¼ on W face, from which an original bearing tree

A cedar, 10 ins. diam., bears S. 28° E., 23 lks.  
 dist., mkd. ¼ S22 BT.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base, to top of aluminum cap, mkd.

T 13 S R 16 E  
 $\frac{1}{4}$  |  
 $\frac{S 21}{S 22}$   
 1983

Deposit the mkd. stone alongside the aluminum post.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 13 S., R. 16 E., Salt Lake Meridian, Utah

## CHAINS

N. 0° 01' E., beginning new measurement.

40.43 The cor. of secs. 15, 16, 21, and 22, monumented with a sandstone, 15 x 14 x 8 ins., firmly set, projecting 6 ins. above ground, plainly mkd. 3 notches on S and E edges, from which the original bearing trees

A pinon, 9 ins. diam., bears N. 26° E., 54 lks.  
dist., mkd. T13S R16E S15 BT.

A pinon, 9 ins. diam., bears S. 2° E., 18 lks.  
dist., mkd. T13S R16E S22 BT.

A cedar, 9 ins. diam., bears S. 74° W., 57 lks.  
dist., mkd. T13S R16E S21 BT. (Record, S. 73° W.).

A pinon, 12 ins. diam., bears N. 70° W., 50 lks.  
dist., mkd. T13S R16E S16 BT. (Record, 49 lks.  
dist.).

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base, to top of aluminum cap mkd.

T 13 S R 16 E
S 16   S 15
S 21   S 22
1983

Deposit the mkd. stone alongside the aluminum post.

N. 0° 08' W., bet. secs. 15 and 16.

Over broken land, through scattered juniper and pinon timber.

40.04 The ¼ sec. cor. of secs. 15 and 16, monumented with a sandstone, 10 x 8 x 5 ins., firmly set, projecting 4 ins. above ground, plainly mkd. ¼ on W face, from which the original bearing trees

A pine, 17 ins. diam., bears S. 41° E., 33 lks.  
dist., mkd. ¼ S15 BT. (Record, 32 lks. dist.).

A pine, 14 ins. diam., bears N. 53° W., 36 lks.  
dist., mkd. ¼ S16 BT. (Record, 34 lks. dist.).

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base, to top of aluminum cap, mkd.

T 13 S R 16 E
¼
S 16   S 15
1983

Deposit the mkd. stone alongside the aluminum post.

Cor. is located on steep N slope, 50 lks. S of Jack Creek stream bed.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 13 S., R. 16 E., Salt Lake Meridian, Utah

CHAINS						
39.43	<p>N. 0° 38' E., beginning new measurement.</p> <p>Point for the cor. of secs. 9, 10, 15, and 16, at record distance longitudinally and at proportionate distance latitudinally; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T 13 S R 16 E</td></tr> <tr><td>S 9   S 10</td></tr> <tr><td>S 16   S 15</td></tr> <tr><td>1983</td></tr> </table> </div> <p>Raise a mound of stone, 3½ ft. base, 1½ ft. high, W of cor.</p>	T 13 S R 16 E	S 9   S 10	S 16   S 15	1983	
T 13 S R 16 E						
S 9   S 10						
S 16   S 15						
1983						
39.43	<p>N. 0° 16' E., bet. secs. 9 and 10.</p> <p>Over rough and broken land through scattered juniper and pinon timber.</p> <p>The ¼ sec. cor. of secs. 9 and 10, monumented with a sandstone, 16 x 10 x 8 ins., firmly set, projecting 5 ins. above ground, plainly mkd. ¼ on W face.</p> <p>This line being out of limits for proper closure makes it necessary to establish a double set of ¼ corners. This cor. will now function as the E ¼ sec. cor. of sec. 9.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4½ ft. base, to top of aluminum cap, mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T 13 S R 16 E</td></tr> <tr><td>¼  </td></tr> <tr><td>S 9  </td></tr> <tr><td>1983</td></tr> </table> </div> <p>Deposit the mkd. stone alongside the aluminum post.</p>	T 13 S R 16 E	¼	S 9	1983	
T 13 S R 16 E						
¼						
S 9						
1983						
0.72	<p>N. 0° 04' W., beginning new measurement.</p> <p>Point for the W ¼ sec. cor. of sec. 10, at midpoint bet. the cor. of secs. 3, 4, 9, and 10, and the cor. of secs. 9, 10, 15, and 16.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T 13 S R 16 E</td></tr> <tr><td>  ¼</td></tr> <tr><td>  S 10</td></tr> <tr><td>1983</td></tr> </table> </div> <p>Raise a mound of stone, 3½ ft. base, 1½ ft. high, E of cor.</p>	T 13 S R 16 E	¼	S 10	1983	
T 13 S R 16 E						
¼						
S 10						
1983						
40.87	<p>The cor. of secs. 3, 4, 9, and 10, monumented with a sandstone, 12 x 9 x 5 ins., firmly set, projecting 8 ins. above ground, plainly mkd. 5 notches on S and 3 notches on E edges, from which the original bearing trees</p>					

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 13 S., R. 16 E., Salt Lake Meridian, Utah

## CHAINS

A pinon, 12 ins. diam., bears N. 87° E., 70 lks.  
dist., mkd. T13S R16E S3 BT. (Record, N. 82° E.,  
69 lks. dist.).

A pinon, 6 ins. diam., bears S. 19° E., 29 lks.  
dist., mkd. T13S R16E S10 BT. (Record,  
S. 86° 30' E.).

A pinon, 14 ins. diam., bears S. 17° W., 66 lks.  
dist., mkd. T13S R16E S9 BT. (Record, S. 16° 30' W.,  
65 lks. dist.).

A pinon, 12 ins. diam., bears N. 68° W., 16½ lks.  
dist., mkd. T13S R16E S4 BT. (Record, N. 66° 30' W.,  
15 lks. dist.).

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 18  
ins. in the ground to bedrock, and in a collar of stone,  
with aluminum cap mkd.

T 13 S R 16 E
S 4   S 3
S 9   S 10
1983

Deposit the mkd. stone alongside the aluminum post.

N. 0° 12' E., bet. secs. 3 and 4.

Over rough and broken land, through scattered juniper  
and pinon timber.

39.86 The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of  
the Tp., hereinbefore described.

From the cor. of secs. 9, 10, 15, and 16.

N. 89° 51' W., bet. secs. 9 and 16.

Over broken land, through scattered juniper and pinon  
timber.

40.02 Point for the ¼ sec. cor. of secs. 9 and 16, at pro-  
portionate distance; there is no remaining evidence of  
the original corner.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 18  
ins. in the ground to bedrock, and in a collar of stone,  
with aluminum cap mkd.

T 13 S R 16 E
S 9
¼ S 16
1983

80.04 The cor. of secs. 8, 9, 16, and 17, monumented with a  
sandstone, 14 x 12 x 6 ins., firmly set, projecting 6  
ins. above ground, plainly mkd. 4 notches on E and S  
edge, from which the original bearing trees

A pinon, 6 ins. diam., bears N. 26° E., 21½ lks.  
dist., mkd. T13S R16E S19 BT. (Record, N. 32° E.,  
19 lks. dist.).

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 13 S., R. 16 E., Salt Lake Meridian, Utah

## CHAINS

A pinon, 14 ins. diam., bears S. 77° E., 32 lks.  
dist., mkd. T13S R16E S16 BT. (Record, S. 79° E.).

A pinon, 14 ins. diam., bears S. 50° W., 71½ lks.  
dist., mkd. T13S R16E S17 BT. (Record, S. 52° W.,  
69 lks. dist.).

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins.  
in the ground, with aluminum cap mkd.

T 13 S R 16 E
S 8   S 9
S 17   S 16
1983

Deposit the mkd. stone alongside the aluminum post.

Cor. is located near S rim of mesa on gentle S slope.

Survey of a Portion of the Subdivisional Lines,  
T. 13 S., R. 16 E., Salt Lake Meridian, Utah

From the cor. of secs. 25, 26, 35, and 36, monumented  
with an iron post, 2½ ins. diam., firmly set, projecting  
6 ins. above ground, with brass cap, mkd. as described  
in the 1961 survey of a portion of the subdivisional  
lines in T. 13 S., R. 16 E.

N. 0° 08' E., bet. secs. 25 and 26.

Over rough and broken land, through scattered juniper  
and pinon timber.

40.00 Point for the ¼ sec. cor. of secs. 25 and 26.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 3 ins.  
in the ground to bedrock, and in a mound of stone, 4 ft.  
base, to top of aluminum cap, mkd.

T 13 S R 16 E
¼
S 26   S 25
1983

80.00 Point for the cor. of secs. 23, 24, 25, and 26.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 14  
ins. in the ground to bedrock, and in a mound of stone,  
3½ ft. base, to top of aluminum cap, mkd.

T 13 S R 16 E
S 23   S 24
S 26   S 25
1983

Cor. is located on SE slope of draw, draining NE.

Survey of a Portion of the Subdivisional Lines,  
T. 13 S., R. 16 E., Salt Lake Meridian, Utah

## CHAINS

From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1961 survey of the E. bdy. of T. 13 S., R. 16 E.

West, bet. secs. 24 and 25.

Over rough and broken land, through scattered juniper and pinon timber.

40.03 Point for the ¼ sec. cor. of secs. 24 and 25.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4½ ft. base, to top of aluminum cap, mkd.

$$\begin{array}{c} \text{T 13 S R 16 E} \\ \frac{1}{4} \quad \frac{\text{S 24}}{\text{S 25}} \\ 1983 \end{array}$$

Cor. is located 50 lks. S of ledge, which bears NW and SE

80.06 The cor. of secs. 23, 24, 25, and 26.

N. 0° 08' E., bet. secs. 23 and 24.

Over rough and broken land, through scattered juniper and pinon timber.

40.00 Point for the ¼ sec. cor. of secs. 23 and 24.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

$$\begin{array}{c} \text{T 13 S R 16 E} \\ \frac{1}{4} \\ \text{S 23} \quad | \quad \text{S 24} \\ 1983 \end{array}$$

80.00 Point for the cor. of secs. 13, 14, 23, and 24.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, and in a mound of stone, 4½ ft. base, to top of aluminum cap, mkd.

$$\begin{array}{c} \text{T 13 S R 16 E} \\ \frac{\text{S 14} \quad | \quad \text{S 13}}{\text{S 23} \quad | \quad \text{S 24}} \\ 1983 \end{array}$$

From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1961 survey of the E. bdy. of T. 13 S., R. 16 E.

N. 89° 55' W., bet. secs. 13 and 24.\*

Survey of a Portion of the Subdivisional Lines,  
T. 13 S., R. 16 E., Salt Lake Meridian, Utah

CHAINS		
	Over rough and broken land, through scattered juniper and pinon timber.	
40.05	Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 24.	
	Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.	
	$\begin{array}{cccc} T & 13 & S & R & 16 & E \\ & & S & 13 & & \\ \frac{1}{4} & & S & 24 & & \\ & & & 1983 & & \end{array}$	
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N of cor.	
80.10	The cor. of secs. 13, 14, 23, and 24.	
	N. $0^{\circ} 08'$ E., bet. secs. 13 and 14.	
	Over rough and broken land, through scattered juniper and pinon timber.	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 14.	
	Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.	
	$\begin{array}{cccc} T & 13 & S & R & 16 & E \\ & & \frac{1}{4} & & & \\ & &   & & & \\ & S & 14 &   & S & 13 \\ & & &   & & \\ & & & 1983 & & \end{array}$	
80.00	Point for the cor. of secs. 11, 12, 13, and 14.	
	Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, and in a collar of stone, with aluminum cap mkd.	
	$\begin{array}{cccc} T & 13 & S & R & 16 & E \\ & S & 11 &   & S & 12 \\ & S & 14 &   & S & 13 \\ & & & & & 1983 \end{array}$	
	Raise a mound of stone, $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W of cor.	
	From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1961 survey of the E. bdy. of T. 13 S., R. 16 E.	
	N. $89^{\circ} 47'$ W., bet. secs. 12 and 13.	
	Over rough and broken land, through scattered juniper and pinon timber.	
40.07	Point for the $\frac{1}{4}$ sec. cor. of secs. 12 and 13.	

Survey of a Portion of the Subdivisional Lines,  
T. 13 S., R. 16 E., Salt Lake Meridian, Utah

CHAINS	
80.14	<p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 3½ ft. base, to top of aluminum cap mkd.</p> <p style="text-align: center;">T 13 S R 16 E S 12 ¼ S 13 1983</p> <p>The cor. of secs. 11, 12, 13, and 14.</p>
39.99 40.09	<p>N. 0° 20' E., bet. secs. 11 and 12.</p> <p>Over rough and broken land, through thick juniper and pinon timber.</p> <p>Point for the ¼ sec. cor. of secs. 11 and 12, falls on face of small ledge and is unsafe to monument.</p> <p>Point selected for the witness cor. to the ¼ sec. cor. of secs. 11 and 12.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap mkd.</p> <p style="text-align: center;">W C T 13 S R 16 E ¼ S 11   S 12 ↓ 1983</p> <p>The cor. of secs. 1, 2, 11, and 12, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1961 survey of a portion of the subdivisional lines of T. 13 S., R. 16 E.</p>
39.93 79.86	<p>From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1961 survey of the E. bdy. of T. 13 S., R. 16 E.</p> <p>N. 89° 55' W., bet. secs. 1 and 12.</p> <p>Over rough and broken land, through scattered juniper and pinon timber.</p> <p>Point for the ¼ sec. cor. of secs. 1 and 12.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.</p> <p style="text-align: center;">T 13 S R 16 E S 1 ¼ S 12 1983</p> <p>The cor. of secs. 1, 2, 11, and 12.</p>

Survey of a Portion of the Subdivisional Lines,  
T. 13 S., R. 16 E., Salt Lake Meridian, Utah

CHAINS	
39.59	<p>From the cor. of secs. 25, 26, 35, and 36.</p> <p>N. 89° 52' W., bet. secs. 26 and 35.</p> <p>Over broken land, through scattered juniper and pinon timber.</p> <p>Point selected for the witness cor. to the <math>\frac{1}{4}</math> sec. cor. of secs. 26 and 35.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>W C</p> <p>T 13 S R 16 E</p> <p><math>\frac{1}{4}</math> ← <math>\frac{S 26}{S 35}</math></p> <p>1983</p> </div> <p>Raise a mound of stone, 3½ ft. base, 1½ ft. high, N of cor.</p>
40.09	<p>True point for the <math>\frac{1}{4}</math> sec. cor. of secs. 26 and 35, falls in deep gully and is unsafe to monument.</p>
80.18	<p>The cor. of secs. 26, 27, 34, and 35, hereinbefore described.</p>
40.17	<p>From the cor. of secs. 23, 24, 25, and 26.</p> <p>N. 89° 50' W., bet. secs. 23 and 26.</p> <p>Over broken land, through scattered juniper and pinon timber.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 23 and 26.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 13 S R 16 E</p> <p><math>\frac{1}{4}</math> <math>\frac{S 23}{S 26}</math></p> <p>1983</p> </div> <p>Raise a mound of stone, 3½ ft. base, 2½ ft. high, N of cor.</p> <p>Cor. is located on S slope, near top of spur, projecting E.</p>
80.34	<p>The cor. of secs. 22, 23, 26, and 27.</p>
40.00	<p>N. 0° 07' E., bet. secs. 22 and 23.</p> <p>Over rough and broken land, through thick juniper and pinon timber.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 22 and 23.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>

Survey of a Portion of the Subdivisional Lines,  
T. 13 S., R. 16 E., Salt Lake Meridian, Utah

CHAINS	
80.00	<p style="text-align: center;">T 13 S R 16 E  <math>\frac{1}{4}</math>            S 22   S 23            1983</p> <p>Raise a mound of stone, 3½ ft. base, 1½ ft. high, W of cor.</p> <p>Point for the cor. of secs. 14, 15, 22, and 23.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 13 S R 16 E            S 15   S 14            S 22   S 23            1983</p> <p>from which</p> <p style="padding-left: 40px;">A pinon, 14 ins. diam., bears N. 52° W., 55 lks. dist., mkd. T13S R16E S15 BT.</p> <p>Raise a mound of stone, 3½ ft. base, 1½ ft. high, W of cor.</p>
40.17	<p>From the cor. of secs. 13, 14, 23, and 24.</p> <p>N. 89° 49' W., bet. secs. 14 and 23.</p> <p>Over rough and broken land, through scattered juniper and pinon timber.</p> <p>Point for the ¼ sec. cor. of secs. 14 and 23.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 13 S R 16 E  <math>\frac{1}{4}</math> S 14            S 23            1983</p> <p>Raise a mound of stone, 3½ ft. base, 1½ ft. high, N of cor.</p> <p>Cor. is located 25 lks. E of small wash, drains NW.</p>
80.34	<p>The cor. of secs. 14, 15, 22, and 23.</p> <p>N. 89° 54' W., bet. secs. 15 and 22.</p> <p>Over broken land, through scattered juniper and pinon timber.</p> <p>Point for the ¼ sec. cor. of secs. 15 and 22.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.</p>

Survey of a Portion of the Subdivisional Lines,  
T. 13 S., R. 16 E., Salt Lake Meridian, Utah

CHAINS		
	<p style="text-align: center;">T 13 S R 16 E  <math>\frac{1}{4}</math> <math>\frac{S 15}{S 22}</math>            1983</p> <p>from which</p> <p style="padding-left: 40px;">A pinon, 16 ins. diam., bears N. 17° W., 17½ lks. dist., mkd. X BT.</p>	
<p>80.54</p> <p>40.00</p> <p>80.00</p>	<p>The cor. of secs. 15, 16, 21, and 22, hereinbefore described.</p> <hr/> <p>From the cor. of secs. 14, 15, 22, and 23.</p> <p>N. 0° 07' E., bet. secs. 14 and 15.</p> <p>Over rough and broken land, through scattered juniper and pinon timber.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 14 and 15.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 13 S R 16 E  <math>\frac{1}{4}</math>            S 15   S 14            1983</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.</p> <p>Point for the cor. of secs. 10, 11, 14, and 15.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap mkd.</p> <p style="text-align: center;">T 13 S R 16 E            S 10   S 11            S 15   S 14            1983</p> <p>Cor. is located on steep NE slope, in scattered pinon and juniper, and about 5.00 chs. NE of ridge top.</p>	
<p>40.17</p>	<p>From the cor. of secs. 11, 12, 13, and 14.</p> <p>N. 89° 50' W., bet. secs. 11 and 14.</p> <p>Over rough and broken land, through scattered juniper and pinon timber.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 11 and 14.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 5 ft. base, to top of aluminum cap, mkd.</p> <p style="text-align: center;">T 13 S R 16 E  <math>\frac{1}{4}</math> <math>\frac{S 11}{S 14}</math>            1983</p>	

Survey of a Portion of the Subdivisional Lines,  
T. 13 S., R. 16 E., Salt Lake Meridian, Utah

CHAINS	
80.34	The cor. of secs. 10, 11, 14, and 15.
	<p>S. 89° 40' W., bet. secs. 10 and 15.</p> <p>Over rough and broken land, through scattered juniper and pinon timber.</p>
40.17	Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 15.
	<p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone, 4½ ft. base, to top of aluminum cap, mkd.</p> <p style="text-align: center;">T 13 S R 16 E  <math>\frac{1}{4}</math> <math>\frac{S 10}{S 15}</math>  1983</p>
80.34	The cor. of secs. 9, 10, 15, and 16, hereinbefore described.
	<p>From the cor. of secs. 2 and 3, hereinbefore described.</p> <p>N. 89° 59' W., along S. bdy. of sec. 3.</p> <p>Over rough and broken land, through scattered juniper and pinon timber.</p>
0.72	Point for the closing cor. of secs. 10 and 11, hereinafter described.
41.04	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 10.
	<p>Set an aluminum post, 30 ins. long, 2½ ins. diam., on solid sandstone, and in a mound of stone, 5 ft. base, to top of aluminum cap, mkd.</p> <p style="text-align: center;">T 13 S R 16 E  <math>\frac{1}{4}</math> <math>\frac{S 3}{S 10}</math>  1983</p>
81.04	The cor. of secs. 3, 4, 9, and 10, hereinbefore described
	<p>From the cor. of secs. 10, 11, 14, and 15.</p> <p>N. 0° 07' E., bet. secs. 10 and 11.</p> <p>Over rough and broken land, with scattered juniper and pinon timber.</p>
39.90	Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11.
	<p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">T 13 S R 16 E  <math>\frac{1}{4}</math>  S 10   S 11  1983</p>

Survey of a Portion of the Subdivisional Lines,  
T. 13 S., R. 16 E., Salt Lake Meridian, Utah

## CHAINS

79.80

Intersect the S. bdy. of sec. 3.

Point for the closing cor. of secs. 10 and 11.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 5 ft. base, to top of aluminum cap, mkd.

T 13 S R 16 E
S 3
-----
S 10   S 11
C   C
1983

From this point, the cor. of secs. 2 and 3, hereinbefore described, bears S. 89° 59' E., 0.72 chs. dist.

Point for the N ¼ sec. cor. of sec. 11, at 40.00 chs. Easting from the closing cor. of secs. 10 and 11, and on the S. bdy. of sec. 2.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 13 S R 16 E
-----
¼ S 11
1983

From this point, the S ¼ sec. cor. of sec. 2, hereinbefore described, bears N. 89° 58' E., 0.68 chs. dist.

## General Description

Township 13 South, Range 16 East is mountainous land covered with medium to dense timber of pinon, juniper and pine. The area is drained in an easterly direction by numerous canyons and draws, and varies in elevation from 6,000 ft. to 7,200 ft. above sea level. Jack Creek in the bottom of Jack Creek Canyon is located in the northern portion of the township and flows in a north-eastern direction. There are several unimproved roads in the area for the development of oil and gas wells, as well as being used by livestock ranchers. The soil is rocky, sandy loam.





UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

R608

ORIGINAL

37

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

THE WEST BOUNDARIES OF SECTIONS 7 AND 18,

TOWNSHIP 14 SOUTH, RANGE 15 EAST,

A PORTION OF THE SUBDIVISIONAL LINES OF SECTIONS 11, 12, 13, AND 14,

AND THE

SURVEY OF THE REMAINING SUBDIVISIONAL LINES

OF SECTIONS 11, 12, 13, AND 14,

OF

TOWNSHIP 14 SOUTH, RANGE 14 EAST

Of the Salt Lake Meridian,

In the State of Utah

EXECUTED BY

Jerry L. Thomas Cadastral surveyor

Under special instructions dated May 23, 19 83, approved May 24, 1983

\_\_\_\_\_, which provided for the surveys included under ~~U.S. Survey~~/Group  
Number 630, and assignment instructions dated May 24, 19 83.

Survey commenced July 25, 19 83

Survey completed August 17, 19 83

# INDEX DIAGRAM

Township 14 South, Range 14 East

6	5	4	3	2	1
				8	8
7	8	9	10 7	11 11	12 3
				11	10
18	17	16	15 6	14 9	13 2
				5	4
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

## Township 14 South, Range 14 East, Salt Lake Meridian, Utah

## CHAINS

The following field notes are those of the dependent resurvey of the west boundaries of sections 7 and 18, T. 14 S., R. 15 E., a portion of the subdivisional lines of sections 11, 12, 13, and 14, and the survey of the remaining subdivisional lines of sections 11, 12, 13, and 14 of T. 14 S., R. 14 E., Salt Lake Meridian, Utah.

History of Surveys

	<u>Surveyed by</u>	<u>Retr. or Resurveyed by</u>
--	--------------------	-------------------------------

NORTH BOUNDARY

All	A.D. Ferron	1884
All		Anderson and Ware 1898
All		J.R. Stewart 1902

SOUTH BOUNDARY

All	A.D. Ferron	1884
All		Anderson and Ware 1898

EAST BOUNDARY

All	A.D. Ferron	1884
All		Anderson and Ware 1898
All		J.R. Stewart 1902

WEST BOUNDARY

All	A.D. Ferron	1884
All		Anderson and Ware 1898
All		H.D. Heist and J.H. Winwood 1908
Portion		J.C. Clark 1934

SUBDIVISIONAL LINES

Portion	Anderson and Ware	1898
Portion	H.D. Heist and J.H. Winwood	1908
Portion	R. Gentry, E. Bird A. Nelson and J.C. Clark	1941

The resurvey and survey were executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 630, Utah, dated May 23, 1983.

The directions of all lines were determined by observations on Polaris and direct altitude observations of the Sun. The lines were carried forward by sustained angulation throughout the township.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

## Township 14 South, Range 14 East, Salt Lake Meridian, Utah

## CHAINS

The geographic position of the southeast corner of section 13, as determined by a tie to the United States Coast and Geodetic Survey triangulation station "BRUIN" is as follows:

Latitude 39° 35' 59.28" N. Longitude 110° 17' 16.95" W.

The mean magnetic declination is 14° E.

Dependent Resurvey of a Portion of the West Boundary,  
T. 14 S., R. 15 E., Salt Lake Meridian, Utah

(Restoring the Survey Executed by A.D. Ferron in 1884,  
the Resurvey by Anderson and Ware in 1898, and  
the Retracement by J.R. Stewart in 1902)

Beginning at the cor. of secs. 13, 18, 19, and 24, monumented with a sandstone, 18 x 9 x 4 ins., loosely set and mkd. 1 notch on N and 2 notches on S, from which the original bearing trees

A pine, 20 ins. diam., bears S. 52° E., 70 lks. dist., with healed blaze. (Record, S. 52° 35' E., 67 lks. dist.).

A dead pine, 20 ins. diam., bears N. 45° W., 86½ lks. dist., mkd. T14S R14E S13 BT. (Record, N. 51° 25' W., 83.4 lks. dist.).

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 14 S			
R 14 E		R 15 E	
S 13		S 18	
S 24		S 19	
1983			

Deposit the mkd. stone alongside the aluminum post.

From this cor., U.S.C. and G.S. triangulation station "BRUIN" bears N. 45° 57' 36" W., 352.61 chs. dist., monumented with a standard disk cemented in bedrock.

N. 0° 07' E., along the W. bdy. of sec. 18.

Over rugged mountainous land.

28.00 Dirt road, bears NW and SE.

40.04 The ¼ sec. cor. of sec. 18 only, monumented with a sandstone, 20 x 6 x 6 ins., firmly set, projecting 8 ins. above ground, and plainly mkd. ¼ on W face.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Dependent Resurvey of a Portion of the West Boundary,  
T. 14 S., R. 15 E., Salt Lake Meridian, Utah

CHAINS	
	<p style="text-align: center;">T 14 S R 14 E R 15 E             S 18       1983</p> <p>Deposit the mkd. stone alongside the aluminum post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 33' E., beginning new measurement.</p> <p>1.04 Point for the E<sup>1</sup>/<sub>4</sub> sec. cor. of sec. 13, T. 14 S., R. 14 E. hereinafter described.</p> <p>11.00 Dirt road, bears E and W.</p> <p>39.88 The cor. of secs. 7 and 18 only, monumented with a sandstone, 20 x 9 x 4 ins., firmly set, projecting 10 ins. above ground, and plainly mkd. 4 grooves on S and 2 grooves on N face.</p> <p>There is no remaining evidence of the original bearing tree.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">T 14 S R 14 E R 15 E       S 13   S 7       S 18       1983</p> <p>Deposit the mkd. stone alongside the aluminum post.</p> <p>Cor. is located on S edge of pine and aspen grove.</p>
	<p>N. 0° 11' E., along the W. bdy. of sec. 7.</p> <p>Over rolling mountainous land, through thick aspen and pine timber.</p> <p>1.16 Point for the closing cor. of secs. 12 and 13, T. 14 S., R. 14 E., hereinafter described.</p> <p>39.93 The ¼ sec. cor. of sec. 7 only, monumented with a sandstone, 24 x 12 x 4 ins., firmly set, projecting 10 ins. above ground, and plainly mkd. ¼ on W face.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 14 S R 14 E R 15 E             S 7       1983</p>

Dependent Resurvey of a Portion of the West Boundary,  
T. 14 S., R. 15 E., Salt Lake Meridian, Utah

## CHAINS

Deposit the mkd. stone alongside the aluminum post.

N.  $0^{\circ} 19'$  W., beginning new measurement.

1.23 Point for the  $E\frac{1}{4}$  sec. cor. of sec. 12, T. 14 S.,  
R. 14 E., hereinafter described.

2.50 Dirt road, bears NE and SW.

40.09 The cor. of secs. 1, 6, 7, and 12, monumented with a  
sandstone, 20 x 14 x 6 ins., firmly set, projecting 12  
ins. above ground and plainly mkd. 5 grooves on S and  
1 groove on N face.

There is no remaining evidence of the original bearing  
trees.

At the corner point

Set an aluminum post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24  
ins. in the ground, with aluminum cap mkd.

T 14 S	
R 14 E	R 15 E
<u>S 1</u>	<u>S 6</u>
S 12	S 7
1983	

Deposit the mkd. stone alongside the iron post.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 14 S., R. 14 E., Salt Lake Meridian, Utah

(Restoring the Survey Executed by  
Anderson and Ware in 1899)

From the cor. of secs. 13, 18, 19, and 24, on the E. bdy.  
of the Tp., hereinbefore described.

N.  $88^{\circ} 17'$  W., bet. secs. 13 and 24.

Over rugged mountainous land; desc. over steep SE slope.

39.69 The  $\frac{1}{4}$  sec. cor. of secs. 13 and 24, monumented with a  
sandstone, 15 x 8 x 4 ins., firmly set, projecting 2 ins.  
above ground, plainly mkd.  $\frac{1}{4}$  on N face, from which the  
original bearing tree

An aspen, 16 ins. diam., bears N.  $54^{\circ}$  E.,  $6\frac{1}{2}$  lks.  
dist., with healed blaze. (Record, N.  $20^{\circ} 40'$  E.,  
6 lks. dist.).

At the corner point

Set an aluminum post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24  
ins. in the ground, with aluminum cap mkd.

T 14 S R 14 E	
$\frac{1}{4}$	<u>S 13</u>
	S 24
1983	

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 14 S., R. 14 E., Salt Lake Meridian, Utah

CHAINS					
	<p>from which I mark</p> <p>A balsam tree, 12 ins. diam., bears S. 36° W., 7 lks. dist., mkd. T14S R14E ¼ S24 BT.</p> <p>Deposit the mkd. stone alongside the aluminum post.</p> <hr/> <p>S. 89° 50' W., beginning new measurement.</p>				
9.30	<p>Bottom of Range Creek Canyon, drains S; asc. over steep E slope.</p>				
40.17	<p>The cor. of secs. 13, 14, 23, and 24, monumented with a sandstone, 15 x 12 x 6 ins., firmly set, projecting 6 ins. above ground, plainly mkd. 3 notches on S and 1 notch on E edge, from which the remaining original bearing tree</p> <p>A pine, 32 ins. diam., bears S. 10° W., 28 lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T 14 S R 14 E</td></tr> <tr><td>S 14   S 13</td></tr> <tr><td>S 23   S 24</td></tr> <tr><td>1983</td></tr> </table> <p>Deposit the mkd. stone alongside the aluminum post.</p>	T 14 S R 14 E	S 14   S 13	S 23   S 24	1983
T 14 S R 14 E					
S 14   S 13					
S 23   S 24					
1983					
39.97	<p>S. 89° 58' W., bet. secs. 14 and 23.</p> <p>Over rugged mountainous land; asc. over steep NE slope.</p> <p>Point for the ¼ sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td>T 14 S R 14 E</td></tr> <tr><td>¼ S 14</td></tr> <tr><td>¼ S 23</td></tr> <tr><td>1983</td></tr> </table> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.</p> <p>Cor. is located on E slope, approximately 1.50 chs. W of draw, draining N into main draw.</p>	T 14 S R 14 E	¼ S 14	¼ S 23	1983
T 14 S R 14 E					
¼ S 14					
¼ S 23					
1983					
79.94	<p>The cor. of secs. 14, 15, 22, and 23, monumented with a sandstone, 24 x 14 x 4 ins., firmly set, projecting 8 ins. above ground, dimly mkd. 2 grooves on E and 4 grooves on S face.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>				

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 14 S., R. 14 E., Salt Lake Meridian, Utah

CHAINS

T 14 S R 14 E  
S 15 | S 14  
S 22 | S 23  
1983

from which I mark

An aspen, 4 ins. diam., bears N. 52° E., 5 lks.  
dist., mkd. X BT.

An aspen, 5 ins. diam., bears S. 60° W., 16 lks.  
dist., mkd. X BT.

Deposit the dimly mkd. stone alongside the aluminum post.

(Restoring the Survey Executed by  
H.D. Heist and J.H. Winwood in 1908)

N. 0° 22' E., bet. secs. 14 and 15.

Over mountainous land; asc. over SE slope.

40.09 Point for the  $\frac{1}{4}$  sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 14 S R 14 E  
       $\frac{1}{4}$   
S 15 | S 14  
      |  
      1983

from which

An aspen, 7 ins. diam., bears N. 77° E., 25 lks.  
dist., mkd. X BT.

An aspen, 8 ins. diam., bears S. 36° W., 28½ lks.  
dist., mkd. X BT.

Raise a mound of stone, 3½ ft. base, 1½ ft. high, W of cor.

Cor. is located on gentle N slope near S edge of aspen grove.

80.18 The cor. of secs. 10, 11, 14, and 15, monumented with a sandstone, 16 x 10 x 8 ins., firmly set, projecting 8 ins. above ground, plainly mkd. 4 notches on S and 2 notches on E edge, from which the original bearing trees

A dead pine, 20 ins. diam., bears S. 87° E., 61½ lks. dist., mkd. T14S R14E S14 BT.

A dead pine, 30 ins. diam., bears S. 44° W., 110½ lks. dist., mkd. T14S R14E S15 BT.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 14 S., R. 14 E., Salt Lake Meridian, Utah

## CHAINS

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 14 S R 14 E
S 10   S 11
S 15   S 14
1983

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 3½ ft. base, 1½ ft. high, W of cor.

N. 0° 10' W., bet. secs. 10 and 11.

Over rolling mountainous land.

39.27

Point for the ¼ sec. cor. of sec. 10 only, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 14 S R 14 E
¼
S 10
1983

from which

A balsam tree, 24 ins. diam., bears N. 68° W., 23½ lks. dist., mkd. T14S R14E ¼ S10 BT.

Raise a mound of stone, 3½ ft. base, 1½ ft. high, W of cor.

40.00

Point for the ¼ sec. cor. of sec. 11 only, hereinafter described.

78.54

The cor. of secs. 2, 3, 10, and 11, monumented with a sandstone, 30 x 14 x 12 ins., firmly set, projecting 10 ins. above ground, plainly mkd. 5 notches on S and 2 notches on E edge, from which an original bearing tree

A dead aspen, 12 ins. diam., bears N. 50° E., 34 lks. dist., mkd. T14S R14E S2 BT. (Record, N. 45° 20' E., 32.5 lks. dist.).

There is no remaining evidence of the other bearing trees

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 14 S R 14 E
S 3   S 2
S 10   S 11
1983

Deposit the mkd. stone alongside the aluminum post.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 14 S., R. 14 E., Salt Lake Meridian, Utah

## CHAINS

(Restoring the Survey Executed by  
Anderson and Ware in 1899)

From the cor. of secs. 1, 6, 7, and 12, on the E. bdy.  
of the Tp., hereinbefore described.

N. 89° 55' W., bet. secs. 1 and 12.

Over mountainous land.

40.03 Point for the  $\frac{1}{4}$  sec. cor. of secs. 1 and 12, at propor-  
tionate distance; there is no remaining evidence of the  
original corner.

Set an aluminum post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24  
ins. in the ground, with aluminum cap mkd.

T 14 S R 14 E  
 $\frac{1}{4}$   $\frac{S 1}{S 12}$   
1983

Raise a mound of stone,  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, N of  
cor.

80.06 The cor. of secs. 1, 2, 11, and 12, monumented with a  
sandstone, 18 x 14 x 4 ins., firmly set, projecting 10  
ins. above ground, plainly mkd. 5 grooves on S and 1  
groove on E face.

There is no remaining evidence of the original bearing  
trees.

At the corner point

Set an aluminum post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24  
ins. in the ground, with aluminum cap mkd.

T 14 S R 14 E  
S 2 | S 1  
S 11 | S 12  
1983

Deposit the mkd. stone alongside the aluminum post.

S. 89° 36' W., bet. secs. 2 and 11.

Over rolling mountainous land.

4.00 Dirt road, bears NW and SE.

39.36 The  $\frac{1}{4}$  sec. cor. of secs. 2 and 11, monumented with a  
sandstone, 20 x 14 x 7 ins., firmly set, projecting 8 ins.  
above ground, plainly mkd.  $\frac{1}{4}$  on N face.

There is no remaining evidence of the original bearing  
trees.

At the corner point

Set an aluminum post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 20  
ins. in the ground, and in a collar of stone, with  
aluminum cap mkd.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 14 S., R. 14 E., Salt Lake Meridian, Utah

CHAINS

T 14 S R 14 E  
 $\frac{1}{4}$   $\frac{S 2}{S 11}$   
 1983

Deposit the mkd. stone alongside the aluminum post.

S. 89° 57' W., beginning new measurement.

9.00 Range Creek, drains SE.

40.46 The cor. of secs. 2, 3, 10, and 11.

Survey of a Portion of the Subdivisional Lines of  
T. 14 S., R. 14 E., Salt Lake Meridian, Utah

From the cor. of secs. 13, 14, 23, and 24.

N. 0° 06' E., bet. secs. 13 and 14.

Over rugged mountainous land; desc. over steep N slope.

7.00 Main draw, drains E.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 13 and 14.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 14 S R 14 E  
 $\frac{1}{4}$   
 S 14 | S 13  
 1983

Desc. along steep broken E slope of Range Creek Canyon.

79.50 Point selected for the witness cor. to the cor. of secs. 11, 12, 13, and 14.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

W C  
 T 14 S R 14 E  
 $\frac{S 11 \uparrow S 12}{S 14 | S 13}$   
 1983

Raise a mound of stone, 3½ ft. base, 1½ ft. high, W of cor.

Cor. is located 10 lks. E of old trail road and 40 lks. W of Range Creek stream bed, flows S. 15° E., in bottom of Range Creek Canyon.

80.00 True point for the cor. of secs. 11, 12, 13, and 14, falls in creek bottom and cannot be monumented.

Survey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 14 E., Salt Lake Meridian, Utah

CHAINS		
	East, bet. secs. 12 and 13.	
	Asc. over steep SE slope of Range Creek Canyon.	
40.08	Point for the $\frac{1}{4}$ sec. cor. of secs. 12 and 13.	
	Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.	
	$\begin{array}{r} T\ 14\ S\ R\ 14\ E \\ \frac{1}{4} \quad \frac{S\ 12}{S\ 13} \\ 1983 \end{array}$	
	Cor. is located on S slope in scattered pine timber.	
50.00	W rim of Cottonwood Ridge; over ridge top.	
52.00	Dirt road, bears NW and SE.	
69.00	Dirt road, bears NNE and SSW.	
80.16	Intersect the W. bdy. of sec, 7, T. 14 S., R. 15 E.	
	Point for the closing cor. of secs. 12 and 13, T. 14 S., R. 14 E.	
	Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.	
	$\begin{array}{r} T\ 14\ S \\ R\ 14\ E\ R\ 15\ E \\ C\ S\ 12\   \\ C\ S\ 13\   \quad S\ 7 \\ 1983 \end{array}$	
	From this point, the cor. of secs. 7 and 18, T. 14 S., R. 15 E., heretofore described, bears S. $0^{\circ} 11' W.$ , 1.16 chs. dist.	
	Point for the $E\frac{1}{4}$ sec. cor. of sec. 13, T. 14 S., R. 14 E., is at 40.00 chs. latitudinally S of the closing cor. of secs. 12 and 13, and on the W. bdy. of sec. 18, T. 14 S., R. 15 E.	
	Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.	
	$\begin{array}{r} T\ 14\ S \\ R\ 14\ E\ R\ 15\ E \\ \frac{1}{4} \quad   \\ S\ 13 \quad   \\ 1983 \end{array}$	
	From this point, the $W\frac{1}{4}$ sec. cor. of sec. 18, T. 14 S., R. 15 E., heretofore described, bears S. $0^{\circ} 33' W.$ , 1.04 chs. dist.	
	Point for the $E\frac{1}{4}$ sec. cor. of sec. 12, T. 14 S., R. 14 E., is at 40.00 chs. latitudinally N of the closing cor. of secs. 12 and 13, and on the W. bdy. of sec. 7, T. 14 S., R. 15 E.	

Survey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 14 E., Salt Lake Meridian, Utah

CHAINS	
	<p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">           T 14 S            R 14 E R 15 E                ¼              S 12                  1983         </p> <p>From this point, the W¼ sec. cor. of sec. 7, T. 14 S., R. 15 E., heretofore described, bears S. 0° 19' E., 1.23 chs. dist.</p>
<p>40.00</p>	<p>From the true point for the cor. of secs. 11, 12, 13, and 14.</p> <p>North, bet. secs. 11 and 12.</p> <p>Over mountainous land; along E side of canyon bottom.</p> <p>Point for the ¼ sec. cor. of secs. 11 and 12.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">           T 14 S R 14 E                ¼              S 11   S 12                1983         </p> <p>Cor. is located on W slope in scattered aspen timber, 1.75 chs. E of Range Creek stream bed.</p> <p>75.00 Dirt road, bears SE and NW.</p> <p>78.97 The cor. of secs. 1, 2, 11, and 12.</p>
<p>39.79</p>	<p>From the true point for the cor. of secs. 11, 12, 13, and 14.</p> <p>N. 89° 55' W., bet. secs. 11 and 14.</p> <p>Over mountainous land; asc. over steep NE slope.</p> <p>Point for the ¼ sec. cor. of secs. 11 and 14.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">           T 14 S R 14 E                S 11              ¼ ———                S 14                1983         </p> <p>from which</p> <p style="padding-left: 40px;">An aspen, 9 ins. diam., bears N. 25° E., 5½ lks. dist., mkd. T14S R14E ¼ S11 BT.</p> <p style="padding-left: 40px;">A balsam, 6 ins. diam., bears S. 41° E., 9 lks. dist., mkd. X BT.</p>

Survey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 14 E., Salt Lake Meridian, Utah

CHAINS	
79.58	<p>Cor. is located on steep NE slope, in scattered aspen and balsam timber.</p> <p>The cor. of secs. 10, 11, 14, and 15.</p> <hr/> <p>Point for the <math>W\frac{1}{4}</math> sec. cor. of sec. 11, T. 14 S., R. 14 E., is at 40.00 chs. latitudinally N of the cor. of secs. 10, 11, 14, and 15, and on the E. bdy. of sec. 10.</p> <p>Set an aluminum post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 14 S R 14 E</p> <p>  <math>\frac{1}{4}</math></p> <p>  S 11</p> <p>1983</p> </div> <p>From this point, the <math>E\frac{1}{4}</math> sec. cor. of sec. 10, bears S. <math>0^{\circ} 10'</math> E., 0.73 chs. dist., heretofore described.</p>
	<p style="text-align: center;">General Description</p> <p>Township 14 South, Range 14 East, is situated south of Bruin Point. The elevation varies from 8,400 ft. to 10,200 ft. above sea level. The soil is mostly mountain loam with some sandstone outcroppings.</p> <p>The head of Range Creek begins in the north end of section 3 and flows in a southeasterly direction through the township.</p> <p>Access to the township is by way of Sunnyside, Utah, and throughout the township by only two dirt roads, one on each side of Range Creek Canyon.</p>





R 608

# FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF A PORTION OF THE SOUTH AND WEST BOUNDARIES,

AND A

SURVEY OF THE FIRST LATITUDINAL LINE

AND THE

LINE BETWEEN SECTIONS 31 AND 32,

TOWNSHIP 4 SOUTH, RANGE 7 WEST

Of the Salt Lake Meridian,

In the State of Utah

## EXECUTED BY

Gary L. Kratz Supervisory Cadastral Surveyor

Under special instructions dated September 4, 1984, approved September 4, 1984

\_\_\_\_\_, which provided for the surveys included under U.S. Survey/Group  
Number 659, and assignment instructions dated September 10, 1984.

Survey commenced September 17, 1984

Survey completed September 28, 1984

# INDEX DIAGRAM

Township 4 South, Range 7 West

	6	5	4	3	2	1
	7	8	9	10	11	12
	18	17	16	15	14	13
	19	20	21	22	23	24
4	30 7	29 7	28 6	27 5	26 5	25 4
3	31 2	8 32	33	34	35	36

## Township 4 South, Range 7 West, Salt Lake Meridian, Utah

## CHAINS

The following field notes are those of a dependent resurvey of a portion of the south and west boundaries, the survey of the first latitudinal line and the line between sections 31 and 32 of Township 4 South, Range 7 West, Salt Lake Meridian, Utah.

History of Earlier Surveys

Surveyed by                      Retr. or Resurveyed by

SOUTH BOUNDARY

W. 1 mile Joseph Gorlinski 1871  
E. 5 miles Alonzo J. Stookey 1899

WEST BOUNDARY

A11                      Joseph Gorlinski 1871

EAST BOUNDARY

A11                      Stewart and Dalton                      1913

SUBDIVISION

Unsurveyed

The surveys were executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated September 4, 1984.

The direction of the lines of this survey were determined by reference to true meridians established on line by direct observations on Polaris. The lines were carried forward by sustained angulation being supplemented by other observations on Polaris taken throughout the progress of the survey.

Preliminary to the resurvey the lines of the original survey were retraced and a search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record.

The geographic position of the corner of sections 25 and 36, on the east boundary of the township as determined from a tie made to U.S.G.S. triangulation station "DESERET," is:

Latitude  $40^{\circ} 26' 02.685''$  N. Longitude  $112^{\circ} 34' 28.711''$  W.

---

Dependent Resurvey of a Portion of the South Boundary,  
T. 4 S., R. 7 W., Salt Lake Meridian, Utah

---

(Reestablishment of the Survey Executed by  
Joseph Gorlinski in 1871)

---

Dependent Resurvey of a Portion of the South Boundary,  
T. 4 S., R. 7 W., Salt Lake Meridian, Utah

## CHAINS

Beginning at the cor. of secs. 5, 6, 31, and 32, Tps. 4 and 5 S., R. 7 W., monumented with a white quartzite stone, 18 x 10 x 7 ins., firmly set 12 ins. in the ground and plainly mkd. 5 notches on the E and 1 on the W edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top, with aluminum cap mkd.

T 4 S R 7 W
S 31   S 32
S 6   S 5
T 5 S
1984

Deposit the mkd. stone alongside the aluminum post.

S. 89° 50' W., bet. secs. 6 and 31.

Over broken mountainous land, through scattered pinon and juniper growth.

3.00 Indian Hickman Canyon, drains SW.

40.18 The 1/4 sec. cor. of secs. 6 and 31, monumented with a quartzite stone, 30 x 18 x 10 ins., firmly set 12 ins. in the ground and plainly mkd. 1/4 on N face, from which an original bearing tree

A juniper, 16 ins. diam., bears S. 33° 28' E.,  
69 1/2 lks. dist., mkd. 1/4 S. (Record,  
N. 34 1/2° E., 72 lks. dist.).

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with aluminum cap mkd.

T 4 S R 7 W
1/4 S 31
S 6
T 5 S
1984

Incorporate mkd. stone in mound.

S. 89° 47' W., beginning new measurement.

40.23 The cor. of Tps. 4 and 5 S., Rs. 7 and 8 W., determined at the cor. of fences, from which fences bear N and W. This position is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Dependent Resurvey of a Portion of the South Boundary,  
T. 4 S., R. 7 W., Salt Lake Meridian, Utah

CHAINS	<p style="text-align: center;">T 4 S R 8 W R 7 W S 36   S 31 S 1   S 6 T 5 S 1984</p>
	<p style="text-align: center;">Dependent Resurvey of a Portion of the West Boundary, T. 4 S., R. 7 W., Salt Lake Meridian, Utah</p>
	<p style="text-align: center;">(Reestablishment of the Survey Executed by Joseph Gorlinski in 1871)</p>
	<p>From the cor. of Tps. 4 and 5 S., Rs. 7 and 8 W. N. 0° 17' E., bet. secs 31 and 36. Over rolling land, through scattered pinon and juniper growth.</p>
40.16	<p>The 1/4 sec. cor. of sec. 36 only, T. 4 S., R. 8 W., monumented with a flintstone, 18 x 10 x 8 ins., firmly set in a mound of stone and dimly mkd. 1/4 on W face. At the corner point Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p>
	<p style="text-align: center;">T 4 S R 8 W R 7 W 1/4   S 36   1984</p>
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor. Bury mkd. stone.</p>
	<p>N. 0° 24' E., beginning new measurement.</p>
4.82	<p>Point for the 1/4 sec. cor. of sec. 31 only, T. 4 S., R. 7 W., at 40.00 chs. of southing from the closing cor. of secs. 30 and 31. Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top, with aluminum cap mkd.</p>
	<p style="text-align: center;">T 4 S R 8 W R 7 W   1/4   S 31 1984</p>
	<p>Cor. is located 6 lks. W of N-S fence line.</p>
29.00	<p>Antelope Canyon, drains SW.</p>
40.43	<p>The cor. of secs. 25 and 36, T. 4 S., R. 8 W., monumented with a quartzite stone, 20 x 18 x 8 ins., firmly set and plainly mkd. 1 notch on the S and 5 on the N edges</p>

Dependent Resurvey of a Portion of the West Boundary,  
T. 4 S., R. 7 W., Salt Lake Meridian, Utah

## CHAINS

from which an original bearing tree

A cedar, 10 ins. diam., bears N. 68 1/4° W., 32 lks. dists., with faint scribe marks.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 4 ins. in the ground to solid rock, and in a mound of stone, 5 ft. base, to top, with aluminum cap mkd.

T 4 S  
R 8 W R 7 W  
S 25 | S 31  
S 36 |  
1984

Incorporate the mkd. stone in mound alongside the cor

N. 0° 38' E., on the E. bdy. of sec. 25, T. 4 S.,  
R. 8 W.

4.39 Point for the closing cor. of secs. 30 and 31,  
hereinafter described in the notes of the Sectional  
Correction Line.

40.03 The 1/4 sec. cor. of sec. 25 only, T. 4 S., R. 8 W.,  
monumented with a limestone, 17 x 11 x 7 ins., firmly  
set 10 ins. in the ground and dimly mkd. 1/4 on W face.  
From which an original bearing tree

A cedar, 10 ins. diam., bears S. 56° E., 27 lks.  
dist., with faint scribe marks.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24  
ins. in the ground, with aluminum cap mkd.

T 4 S  
R 8 W R 7 W  
1/4 |  
S 25 |  
1984

Survey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 7 W., Salt Lake Meridian, Utah

Beginning at the cor. of secs. 25 and 36, on the E. bdy.  
of the Tp., monumented with an iron post, 3 ins. diam.,  
projecting 24 ins. above ground, and in a mound of  
stone, 3 ft. base, to top of brass cap, mkd. as  
described in the official record of the 1913 survey.

West, bet. secs. 25 and 36, on a Sectional Correction  
Line.

Over broken mountainous land, through pinon and juniper  
growth.

32.00 Bear Fork Canyon, drains SE.

Survey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 7 W., Salt Lake Meridian, Utah

CHAINS		
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 36.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> $\begin{array}{r} T\ 4\ S\ R\ 7\ W \\ \quad \quad S\ 25 \\ 1/4 \quad \quad \hline \quad \quad S\ 36 \\ \quad \quad \quad 1984 \end{array}$	
43.40	Trail road, bears irregularly NE and SW.	
80.00	<p>Point for the cor. of secs. 25, 26, 35, and 36.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> $\begin{array}{r} T\ 4\ S\ R\ 7\ W \\ S\ 26 \quad   \quad S\ 25 \\ S\ 35 \quad   \quad S\ 36 \\ \quad \quad \quad 1984 \end{array}$	
40.00	<p>West, on the Sectional Correction Line, bet. secs. 26 and 35.</p> <p>Over broken mountainous land, through pinon and juniper growth.</p> <p>Point for the 1/4 sec. cor. of secs. 26 and 35.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top, with aluminum cap mkd.</p> $\begin{array}{r} T4S\ R7W \\ \quad \quad S\ 26 \\ 1/4 \quad \quad \hline \quad \quad S\ 35 \\ \quad \quad \quad 1984 \end{array}$	
80.00	<p>Cor. is located on ridge, bears N and S.</p> <p>From this point, U.S.G.S. triangulation station "DESERET", a copper bolt set in drill hole in bedrock, bears N. 33° 54' 27" W., 169.5295 chs. dist.</p> <p>Point for the cor. of secs. 26, 27, 34, and 35.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to solid rock, and in a mound of stone, 6 ft. base, to top, with aluminum cap mkd.</p> $\begin{array}{r} T\ 4\ S\ R\ 7\ W \\ S\ 27 \quad   \quad S\ 26 \\ S\ 34 \quad   \quad S\ 35 \\ \quad \quad \quad 1984 \end{array}$	
	<p>West, on the Sectional Correction Line, bet. secs. 27 and 34.</p>	

Survey of a Portion of the Subdivisional Lines,  
~~T. 4 S., R. 7 W., Salt Lake Meridian, Utah~~

CHAINS	
	Over broken mountainous land, through pinon pine and juniper growth.
33.00	Indian Hickman Canyon, drains SW.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 34.
	Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to bedrock and in a mound of stone, 6 ft. base, to top, with aluminum cap mkd.
	$\begin{array}{r} T\ 4\ S\ R\ 7\ W \\ \quad \quad S\ 27 \\ 1/4 \quad \frac{S\ 34}{1984} \end{array}$
	Cor. is located on SE slope.
80.00	Point for the cor. of secs. 27, 28, 33, and 34.
	Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 6 ft. base, to top, with aluminum cap mkd.
	$\begin{array}{r} T\ 4\ S\ R\ 7\ W \\ S\ 28\   \ S\ 27 \\ S\ 33\   \ S\ 34 \\ \quad \quad 1984 \end{array}$
	Cor. is located on broken SW slope.
	West, on the Sectional Correction line, bet. secs. 28 and 33.
	Over broken mountainous land, through pine, pinon and juniper growth.
40.00	Point for the 1/4 sec. cor. of secs. 28 and 33.
	Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, 3 ft. base, to top, with aluminum cap mkd.
	$\begin{array}{r} T\ 4\ S\ R\ 7\ W \\ \quad \quad S\ 28 \\ 1/4 \quad \frac{S\ 33}{1984} \end{array}$
	Cor. is located on broken S slope.
58.00	Spur, slopes S.
80.00	Point for the cor. of secs. 28, 29, 32, and 33.
	Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{r} T\ 4\ S\ R\ 7\ W \\ S\ 29\   \ S\ 28 \\ S\ 32\   \ S\ 33 \\ \quad \quad 1984 \end{array}$
	Raise a mound of stone, 4 ft. base, 2 ft. high, W of cor.

Survey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 7 W., Salt Lake Meridian, Utah

CHAINS		
	West, on the Sectional Correction Line, bet. secs. 29 and 32.	
	Over broken mountainous land, through pinon, pine, and juniper growth.	
35.00	Spur, slopes S; desc. SW slope.	
40.00	Point for the 1/4 sec. cor. of secs. 29 and 32.	
	<p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to solid rock, and in a mound of stone, 3 ft. base, to top, with aluminum cap mkd.</p> $\begin{array}{c} T\ 4\ S\ R\ 7\ W \\ \quad S\ 29 \\ 1/4\ \frac{S\ 32}{1984} \end{array}$	
	Cor. is located on steep W slope.	
75.70	Point for the closing cor. of secs. 31 and 32, hereinafter described.	
80.00	Point for the cor. of secs. 29 and 30.	
	<p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with aluminum cap mkd.</p> $\begin{array}{c} T\ 4\ S\ R\ 7\ W \\ S\ 30\   \ S\ 29 \\ \quad S\ 31 \\ \quad 1984 \end{array}$	
	Cor. is located in slide area, bears W.	
	West, on the Sectional Correction Line, along the S. bdy. of sec. 30.	
	Over broken mountainous land, through pinon and juniper growth.	
35.70	Point for the 1/4 sec. cor. of sec. 31 only, at 40.00 chs. of westing from the closing cor. of secs. 31 and 32, falls on sloping ledge and deemed unsafe to monument	
35.88	Point selected for the witness cor. to the 1/4 sec. cor. of sec 31 only.	
	<p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top, with aluminum cap mkd.</p> $\begin{array}{c} W\ C \\ T\ 4\ S\ R\ 7\ W \\ \quad \frac{1/4\ S\ 31}{1984} \end{array}$	
	Cor. is located on broken SW slope.	
40.00	Point for the 1/4 sec. cor. of sec. 30 only.	

Survey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 7 W., Salt Lake Meridian, Utah

CHAINS	
	<p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 7 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top, with aluminum cap mkd.</p>
	<p style="text-align: center;">T 4 S R 7 W 1/4 S 30 1984</p>
	<p>Cor. is located on broken SW slope.</p>
58.00	<p>Antelope Canyon, drains SW.</p>
75.45	<p>Intersect the E. bdy. of secs. 30 and 31, T. 4 S., R. 7 W.</p>
	<p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top, with aluminum cap mkd.</p>
	<p style="text-align: center;">T 4 S R 8 W R 7 W S 25   S 30 C S 31 C 1984</p>
	<p>From this cor., the cor. of secs. 25 and 36, T. 4 S., R. 8 W., bears S. 0° 38' W., 4.39 chs. dist.</p>
	<p>From this same cor., the 1/4 sec. cor. of sec. 25, T. 4 S., R. 8 W., bears N. 0° 38' E., 35.64 chs. dist.</p>
	<p>From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., heretofore described.</p>
	<p>N. 0° 04' W., bet. secs. 31 and 32.</p>
	<p>Over broken mountainous land, through pinon and juniper growth.</p>
3.00	<p>Indian Hickman Canyon, drains S. 60° W., asc.</p>
41.04	<p>Set a bathey, 24 ins. long, 12 ins. in the ground, for a witness point, mkd. W P.</p>
44.72	<p>Point for the 1/4 sec. cor. of secs. 31 and 32, at 40.00 chs. of southing from the closing cor. of secs. 31 and 32.</p>
	<p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top, with aluminum cap mkd.</p>
	<p style="text-align: center;">T 4 S R 7 W 1/4 S 31   S 32 1984</p>
75.56	<p>Set a bathey, 24 ins. long, 12 ins. in the ground, for a witness point, mkd. W P.</p>
84.72	<p>Intersect the S. bdy. of sec. 29, T. 4 S., R. 7 W.</p>
	<p>Point for the closing cor. of secs. 31 and 32.</p>

Survey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 7 W., Salt Lake Meridian, Utah

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., on solid rock, and in a mound of stone, 4 ft. base, to top, with aluminum cap mkd.

$$\begin{array}{r} T\ 4\ S\ R\ 7\ W \\ \quad S\ 29 \\ \hline S\ 31\ | \ S\ 32 \\ \quad C\ \quad C \\ \quad 1984 \end{array}$$

From this cor., the cor. of secs. 29 and 30, bears West, 4.30 chs. dist.

From this same cor., the 1/4 sec. cor. of secs. 29 and 32, bears East, 35.70 chs. dist.

---

General Description

The area surveyed straddles the Stansbury Mountains approximately 45 miles west of Salt Lake City, Utah. The elevation ranges from 5400 to 9500 ft. above sea level. The terrain is rugged and access is very poor. Indian Hickman and Antelope Canyons drain the westerly slopes and Bear Fork drains the east side. Juniper, aspen and sagebrush dominate the vegetation. There are no improvements, buildings or residents in the surveyed area.





UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

R608

66

ORIGINAL  
**FIELD NOTES**  
OF THE

DEPENDENT RESURVEY

OF A PORTION OF THE WEST BOUNDARY

(FIRST GUIDE MERIDIAN EAST),

A PORTION OF THE SUBDIVISIONAL LINES,

WITH A SUBDIVISIONAL SURVEY

OF

SECTION 18,

TOWNSHIP 29 SOUTH, RANGE 5 EAST

Of the Salt Lake Meridian,

In the State of Utah

EXECUTED BY

Gail E. Reynolds

Cadastral Surveyor

Under special instructions dated September 20, 19 85, approved September 20, 1985  
and Supplemental Special Instructions dated September 23, 1985

, which provided for the surveys included under ~~U.S.~~ <sup>XXXXXXXXXX</sup> Survey/Group  
Number 678, and assignment instructions dated September 20, 19 85.

Survey commenced September 23, 19 85

Survey completed September 30, 19 85

67

# INDEX DIAGRAM

Township 29 South, Range 5 East

6	5	4	3	2	1
7	8	9	10	11	12
2 18 3	4 17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision of Section 18 - Page 4

## Township 29 South, Range 5 East, Salt Lake Meridian, Utah

CHAINS

The following field notes describe the dependent resurvey of a portion of the west boundary (First Guide Meridian East), a portion of the subdivisional lines, with a subdivisional survey of section 18, T. 29 S., R. 5 E., Salt Lake Meridian, Utah.

History of Surveys

	<u>Surveyed by</u>	<u>Retr. or Resurveyed by</u>	
--	--------------------	-------------------------------	--

SOUTH BOUNDARY

Portion	A. Jessen	1891	
Portion	Ferron and Jessen	1895	
		J.P. Walker	1904
Portion		E. Bird	1920
Portion		G.E. Reynolds	1983

EAST BOUNDARY

All	Ferron and Jessen	1892	
Portion		E. Bird	1920

WEST BOUNDARY (First Guide Meridian East)

All	A.D. Ferron	1883	
Portion	A. Jessen	1891	
Portion		C.P. Sylvester	1976

NORTH BOUNDARY

Portion	Ferron and Jessen	1895	
Portion	E. Bird	1920	
Portion		E. Bird	1920

SUBDIVISION

Portion	A. Jessen	1891	
Portion	Ferron and Jessen	1895	
Portion	E. Bird	1920	

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated September 20, 1985 and Supplemental Special Instructions dated September 23, 1985 for Group No. 678, Utah.

The directions of lines were determined by means of fore- and backsights and angular deflections from azimuths obtained by direct solar observations..

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions, lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the southwest corner of section 18, as determined from a tie to U.S.G.S. triangulation station "TORREY" located in section 8, T. 29 S., R. 5 E., is as follows:.

Latitude 38° 16' 51.217" N. Longitude 111° 24' 48.174" W.

## Township 25 South, Range 5 East, Salt Lake Meridian, Utah

## CHAINS

The mean magnetic declination as projected from the U.S.G.S. "Magnetic Declination Map of 1980", is 13 3/4° E.

Dependent Resurvey of the West Boundary,  
T. 29 S., R. 5 E., Salt Lake Meridian, Utah

(Reestablishment of the Survey Executed by  
A.D. Ferron in 1883)

Beginning at the cor. of secs. 13, 18, 19, and 24,  
T. 29 S., Rs. 4 and 5 E., monumented with an iron post,  
2 1/2 ins. diam., set 10 ins. in the ground and in a  
mound of stone, 3 1/2 ft. base, to top of brass cap, mkd.  
as described in the official record of the 1976 resurvey  
of a portion of the west boundary.

From this cor., U.S.C. & G.S. triangulation station  
"TORREY 1952", bears N. 37° 54' 55" E., 141.164 chs.  
dist., a bronze disk, seated in a boulder. The elevation  
to this point is a plus 5.23 ft.

N. 0° 13' E., bet. secs. 13 and 18.

Over broken land, through pinon and juniper growth.

19.94 Point for the S 1/16 sec. cor. of secs. 13 and 18.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 5  
ins. in the ground, and in a mound of stone, 4 ft. base,  
to top of aluminum cap, mkd.

T 29 S  
R 4 E R 5 E  
S 1/16  
S 13 | S 18  
1985

Cor. is located on NW slope of draw, drains W.

29.88 Point for the N-S 1/64 sec. cor. of secs. 13 and 18.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20  
ins. in the ground, and in a collar of stone, with  
aluminum cap mkd.

T 29 S  
R 4 E R 5 E  
N-S 1/64  
S 13 | S 18  
1985

Cor. is located on benchland.

39.88 The 1/4 sec. cor. of secs. 13 and 18, monumented with a  
sandstone, 24 x 7 x 7 ins., firmly set in a mound of  
stone, and plainly mkd. 1/4 on N face; there is no  
remaining evidence of the original bearing trees.

At the corner point

Dependent Resurvey of the West Boundary,  
T. 29 S., R. 5 E., Salt Lake Meridian, Utah

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., on solid rock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 29 S  
R 4 E R 5 E  
1/4  
S 13 | S 18  
1985

Deposit the mkd. stone in mound alongside the aluminum post.

Cor. is located on rocky sandstone ridge, bears E and W.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 29 S., R. 5 E., Salt Lake Meridian, Utah

(Reestablishment of the Survey Executed by  
A. Jessen, Deputy Surveyor in 1891)

From the cor. of secs. 17, 18, 19, and 20, monumented with a sandstone, 20 x 14 x 6 ins., firmly set in a mound of stone and plainly mkd. 5 notches on E edge and 3 on S edge.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 29 S R 5 E  
S 18 | S 17  
S 19 | S 20  
1985

Deposit the mkd. stone in mound alongside the aluminum post.

Cor. is located in a 4 strand fence line, bears N and S.  
N. 89° 40' W., bet. secs. 18 and 19.

Over broken land, through pinon and juniper growth.

40.29

The 1/4 sec. cor. of secs. 18 and 19, monumented with a sandstone, 24 x 12 x 4 ins., firmly set 14 ins. in the ground and plainly mkd. 1/4 on N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 29 S R 5 E  
S 18  
1/4 S 19  
1985

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 29 S., R. 5 E., Salt Lake Meridian, Utah

CHAINS		
	<p>Deposit the mkd. stone alongside the aluminum post. Cor. is located on S edge of cultivated field.</p> <hr/> <p>S. 89° 31' W., beginning new measurement.</p>	
20.61	<p>Point for the W 1/16 sec. cor. of secs. 18 and 19.</p> <p>Set an iron post, 14 ins. long, 1 in. diam., drilled 12 ins. in solid sandstone, with brass cap mkd.</p> <p style="text-align: center;">T 29 S R 5 E           S 18 W 1/16   S 19           1985</p>	
40.60	<p>Cor. is located on sandstone outcropping, facing SE.</p> <p>The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., heretofore described.</p>	
	<p style="text-align: center;">(Reestablishment of the Survey Executed by A.D. Ferroon and A. Jessen, Deputy Surveyors in 1895)</p> <hr/>	
	<p>From the cor. of secs. 17, 18, 19, and 20.</p> <p>N. 0° 25' E., bet. secs. 17 and 18.</p> <p>Over broken land, through scattered pinon and juniper growth.</p>	
40.02	<p>The 1/4 sec. cor. of secs. 17 and 18, monumented with a volcanic stone, 20 x 12 x 10 ins., firmly set 14 ins. in the ground and plainly mkd. 1/4 on W face, from which the one remaining original bearing tree</p> <p style="padding-left: 40px;">A pinon, 16 ins. diam., bears N. 71° 45' W., 97 lks. dist., mkd. 1/4 S18 BT. (Same as record.)</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">T 29 S R 5 E           1/4           S 18   S 17           1985</p>	
	<p>Deposit the mkd. stone alongside the aluminum post.</p> <p>Cor. is located on gentle SE slope.</p>	
	<p style="text-align: center;">Survey of a Portion of the Subdivision of Section 18, T. 29 S., R. 5 E., Salt Lake Meridian, Utah</p>	

Survey of a Portion of the Subdivision of Section 18,  
T. 29 S., R. 5 E., Salt Lake Meridian, Utah

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 18 and 19. N. 0° 22' E., on the N-S center line of sec. 18.</p>
19.83	<p>Point for the center S 1/16 sec. cor. of sec. 18, not monumented.</p>
39.66	<p>Point for the center 1/4 sec. cor. of sec. 18 at intersection with the E and W center line.</p>
	<p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 29 S R 5 E C 1/4 S 18 1985</p>
	<p>Cor. is located alongside Allen Engineering aluminum cap, 1 in. diam., and 4 lks. north of netwire fence line, bears E and W irregularly and 8 lks. east of netwire fence line, bears N and S irregularly in pasture.</p>
80.21	<p>The 1/4 sec. cor. of secs. 7 and 18, established at intersection of fences, bearing N, E, S, and W, with Allen Engineering aluminum cap 1 in. diameter alongside.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">T 29 S R 5 E S 7 1/4 S 18 1985</p>
	<p>From the 1/4 sec. cor. of secs. 17 and 18. S. 89° 50' W., on the E-W center line of sec. 18.</p>
40.32	<p>The center 1/4 sec. cor. of sec. 18.</p>
60.90	<p>Point for the center W 1/16 sec. cor. of sec. 18.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to solid rock, and in a mound of stone, 4 1/2 ft. base, to top of aluminum cap, mkd.</p>
	<p style="text-align: center;">T 29 S R 5 E W 1/16</p> <p style="text-align: center;">C ——— S 18 ——— C 1985</p>
71.03	<p>Cor. is located on top of bench land in juniper and pinon.</p> <p>Point for the center W-W 1/64 sec. cor. of sec. 18.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p>

Survey of a Portion of the Subdivision of Section 18,  
T. 29 S., R. 5 E., Salt Lake Meridian, Utah

CHAINS	
81.03	<p style="text-align: center;">T 29 S R 5 E C-W-W 1/64 S 18 1985</p> <p>Set 6 ft. steel fence post alongside.</p> <p>Cor. is located on bench land in pinon and juniper growth.</p> <p>The 1/4 sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp., heretofore described</p>
19.89	<p>From the W 1/16 sec. cor. of secs. 18 and 19.</p> <p>N. 0° 24' E., on the N-S center line of the SW 1/4 of sec. 18.</p> <p>Point for the SW 1/16 sec. cor. of sec. 18, at intersection with the E-W center line of the SW 1/4 of sec. 18.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 30 ins. in the ground, with 6 ft. steel fence post alongside the aluminum cap mkd.</p>
39.78	<p style="text-align: center;">T 29 S R 5 E SW 1/16 S 18 1985</p> <p>Cor. falls in cultivated land.</p> <p>The center W 1/16 sec. cor. of sec. 18.</p>
20.60	<p>From the point for the center S 1/16 sec. cor. of sec. 18.</p> <p>S. 89° 40' W., on the E-W center line of the SW 1/4 of sec. 18.</p> <p>The SW 1/16 sec. cor. of sec. 18.</p>
40.66	<p>The S 1/16 sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp., heretofore described.</p>
10.00	<p>From the center W-W 1/64 sec. cor. of sec. 18.</p> <p>S. 0° 13' W., on a N-S line through original Lot 3 of sec. 18, parallel with the W bdy.</p> <p>Point selected for the NW-SW 1/64 sec. cor. of sec. 18.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 4 1/2 ft. base, to top of aluminum cap, mkd.</p> <p style="text-align: center;">T 29 S R 5 E NW-SW 1/64 S 18 1985</p> <p>Cor. is located on bench land in pinon and juniper growth.</p>

Survey of a Portion of the Subdivision of Section 18,  
T. 29 S., R. 5 E., Salt Lake Meridian, Utah

<p>CHAINS</p> <p>10.00</p>	<p>S. 89° 50' W., on an E-W line through original Lot 3 of sec. 18, parallel with the E-W center line of the sec.</p> <p>The N-S 1/64 sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp., heretofore described.</p> <hr/> <p style="text-align: center;">General Description</p> <p>The area surveyed and resurveyed within T. 29 S., R. 5 E., varies from broken sandstone ledges at higher elevations to rolling cultivated land in the draws. The elevation varies from 6700 to 6900 ft. above sea level. The soil varies from sandy clay loam at lower elevations to rocky at higher elevations. The vegetation consists of pinon, juniper and sagebrush. The NW 1/4 of the SW 1/4 has been generally used as the Torrey Town dump.</p>	
----------------------------	--	--



CERTIFICATE OF SURVEY

(I) ~~(We)~~, Gail E. Reynolds, Cadastral Surveyor, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 20th day of September 19 85 ~~(I) ~~(We)~~~~ have dependently resurveyed a portion of the west boundary (First Guide Meridian East), a portion of the subdivisional lines with a subdivision survey of section 18 in T. 29 S., R. 5 E.,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me) ~~(XX)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

October 30, 1985 (Date) [Signature] (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the west boundary (First Guide Meridian East), a portion of the subdivisional lines with a subdivision survey of section 18 in T. 29 S., R. 5 E., Salt Lake Meridian, Utah

executed by Gail E. Reynolds, Cadastral Surveyor having been critically examined and found correct, are hereby approved.

November 1, 1985 (Date) [Signature] Chief Cadastral Surveyor for Utah

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

[Signature] Chief Cadastral Surveyor for Utah

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

R 608

ORIGINAL

77

FIELD NOTES  
OF THE

DEPENDENT RESURVEY

OF A PORTION OF THE SOUTH BOUNDARY,  
AND A PORTION OF THE SUBDIVISIONAL LINES,  
WITH A SUBDIVISIONAL SURVEY

OF

SECTIONS 8, 17, 20, 29, AND 32

OF

TOWNSHIP 4 SOUTH, RANGE 2 EAST

Of the Salt Lake Meridian,  
In the State of Utah

EXECUTED BY

Gary L. Kratz Supervisory Cadastral Surveyor

Under special instructions dated May 26, 19 83, approved May 26, 1983

\_\_\_\_\_, which provided for the surveys included under U.S. Survey Group  
Number 631, and assignment instructions dated May 26, 19 83

Survey commenced May 29, 19 83

Survey completed November 4, 19 83

# INDEX DIAGRAM

Township 4 South, Range 2 East

6	5 8	4	3	2	1
7 7	8 7	9	10	11	12
16 7	17 3 6	16	15	14	13
19 5	20 5	21	22	23	24
28 4	29 3 4	28	27	26	25
31 4	32 2 2	33	34	35	36

- Subdivision of Section 8 - Page 8
- Subdivision of Section 17 - Page 10
- Subdivision of Section 20 - Page 10
- Subdivision of Section 29 - Page 12
- Subdivision of Section 32 - Page 12

## Township 4 South , Range 2 East, Salt Lake Meridian, Utah

CHAINS	The following field notes describe the dependent resurvey of a portion of the south boundary, and a portion of the subdivisional lines with a subdivisional survey of sections 8, 17, 20, 29, and 32, T. 4 S., R. 2 E., Salt Lake Meridian, Utah.			
	<u>History of Surveys</u>			
	<u>Surveyed by</u>	<u>Retr. or Resurveyed by</u>		
	<u>SOUTH BOUNDARY</u>			
Portion	C.L. Craig	1856		
Portion	J.F. Smith	1871		
			J.F. Smith	1871
Portion	A.D. Ferron	1891		
			A.D. Ferron	1891
Portion	J.P. Stewart	1914		
			J.P. Stewart	1914
Portion	Yundt, et al	1925- 1941		
			Yundt, et al	1925- 1941
	<u>WEST BOUNDARY</u>			
Portion	C.L. Craig	1856		
Portion	A.D. Ferron	1891		
Portion			A.D. Ferron	1891
Portion	Hanson and Giers	1900		
Portion			R. Gentry	1941
	<u>SUBDIVISION</u>			
Portion	C.L. Craig	1856		
Portion			J.F. Smith.	1871
Portion	A.D. Ferron	1872		
Portion	A.D. Ferron	1891		
Portion			A.D. Ferron	1891
Portion	R. Gentry	1941		
Portion			R. Gentry	1941
	The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group 631, Utah, dated May 26, 1983.			
	The directions of lines refer to true meridian, and were determined by direct solar observations. The lines were carried forward by sustained angulation.			
	Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions, lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.			
	The geographic position of the southeast corner of section 32, as determined from a tie to National Geodetic Survey station "Dry Creek", located in section 7, is.			
	Latitude 40° 25' 15.75" N. Longitude 111° 44' 04.32" W.			

## Township 4 South , Range 2 East, Salt Lake Meridian, Utah

CHAINS	<p>The mean magnetic declination as projected from U.S. Geological Survey "Magnetic Declination Map of 1980" is <math>14\ 1/2^{\circ}</math> E.</p> <hr/> <p>Dependent Resurvey of a Portion of the South Boundary, T. 4 S., R. 2 E., Salt Lake Meridian, Utah</p> <hr/> <p>(Reestablishment of the Survey Executed by J.R. Stewart in 1914)</p> <hr/> <p>Beginning at the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap, mkd. as described in the official record of the 1914 resurvey.</p> <p>N. <math>89^{\circ} 29''</math> W., bet. secs. 5 and 32.</p> <p>Desc. over mountainous terrain, through dense brush.</p> <p>40.58 The <math>1/4</math> sec. cor. of secs. 5 and 32, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, with brass cap, mkd. as described in the official record of the 1914 resurvey.</p> <p>Cor. falls in fence line, bears N and S.</p> <hr/> <p>S. <math>89^{\circ} 42'</math> W., beginning new measurement.</p> <p>40.09 The cor. of secs. 5, 6, 32, and 33, monumented with an iron post, 3 ins. diam., firmly set, projecting 20 ins. above ground, with brass cap, mkd. as described in the official record of the 1914 resurvey.</p> <p>Cor. is located alongside intersection of fences, bearing S and W.</p> <hr/> <p>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 4 S., R. 2 E., Salt Lake Meridian, Utah</p> <hr/> <p>(Reestablishment of the Survey Executed by Gentry, Nelson and Yundt from 1925 through 1941)</p> <hr/> <p>From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., heretofore described.</p> <p>N. <math>0^{\circ} 02'</math> W., bet. secs. 32 and 33.</p> <p>Asc. over mountainous terrain through dense brush.</p> <p>19.91 Point for the S <math>1/16</math> sec. cor. of secs. 32 and 33.</p> <p>Set an aluminum post, 30 ins. long, <math>2\ 1/2</math> ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p>
--------	--

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 4 S., R. 2 E., Salt Lake Meridian, Utah

CHAINS	
	<p style="text-align: center;">T 4 S R 2 E S 1/16 S 32   S 33 1983</p>
37.92	<p>The witness cor. to the 1/4 sec. cor. of secs. 32 and 33, monumented with an iron post, 1 in. diam., firmly set, projecting 26 ins. above ground, and in a mound of stone, 3 ft. base, to top of brass cap, mkd. as described in the official record of the 1925-41 resurvey.</p> <p style="text-align: center;">_____</p> <p style="text-align: center;">N. 0° 08' E., beginning new measurement.</p>
1.90	<p>True point for the 1/4 sec. cor. of secs. 32 and 33, at proportionate distance. This point falls on a rockface where it is impractical to establish a monument.</p>
41.94	<p>The cor. of secs. 28, 29, 32, and 33, monumented with an iron post, 2 ins. diam., firmly set, projecting 26 ins. above ground, and in a mound of stone, 3 ft. base, to top of brass cap, mkd. as described in the official record of the 1925-1941 resurvey.</p>
	<p>N. 0° 33' W., bet. secs. 28 and 29.</p> <p>Over steep and rocky mountainous terrain through scattered brush and juniper.</p>
40.91	<p>True point for the 1/4 sec. cor. of secs. 28 and 29, at proportionate distance. This point falls on a rockface where it is impractical to establish a monument.</p>
51.14	<p>The witness 1/4 sec. cor. of secs. 28 and 29, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, with brass cap, mkd. as described in the official record of the 1925-1941 resurvey</p> <p>from which</p> <p style="padding-left: 40px;">A pinon pine, 8 ins. diam., bears N. 24° E., 43 lks. dist., mkd. with an open blaze. (Record, N. 37° E., 42 lks. dist.).</p> <p style="padding-left: 40px;">A juniper, 12 ins. diam., bears S. 65° W., 50 1/2 lks. dist., with several axe marks. (Record, S. 67° W., 59 lks. dist.).</p>
40.70	<p>From the 1/4 sec. cor. of secs. 16 and 17, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap, mkd. as described in the official record of the 1925-1941 resurvey.</p> <p>N. 1° 03' W., bet. secs. 16 and 17.</p> <p>Over mountainous terrain, through dense brush.</p> <p>The cor. of secs. 8, 9, 16, and 17, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap, mkd. as described in the official record of the 1925-1941 resurvey.</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 4 S., R. 2 E., Salt Lake Meridian, Utah

CHAINS	
	<p>From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., heretofore described.</p> <p>N. 0° 06' E., bet. secs. 31 and 32.</p> <p>Over rolling bench land, through scattered brush.</p>
40.43	<p>The 1/4 sec. cor. of secs. 31 and 32, monumented with a concrete post, 6 ins. sq., firmly set, flush with the ground, with Utah County brass cap mkd.</p> <p style="text-align: center;">T 4 S R 2 E 1/4 COR S 31   S 32 1958</p> <p>from which</p> <p style="text-align: center;">A double-headed nail in a power pole, bears N. 7° W., 36 1/2 lks. dist.</p> <p>Cor. falls in the center of an unimproved road, bears E and W, and is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 13' E., beginning new measurement.</p>
40.54	<p>The cor. of secs. 29, 30, 31, and 32, monumented with an iron post, 2 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap, mkd. as described in the official record of the 1925-1941 resurvey.</p> <p>A mound of stone, 2 ft. base, 1 1/2 ft. high, W of cor.</p> <p>Cor. falls alongside the intersection of fences bearing N and E.</p>
40.27	<p>From the cor. of secs. 28, 29, 32, and 33.</p> <p>N. 89° 10' W., bet. secs. 29 and 32.</p> <p>Over steep and rocky mountainous terrain, through scattered brush.</p>
40.89	<p>True point for the 1/4 sec. cor. of secs. 29 and 32, at proportionate distance. This point falls on a rockface where it is impractical to establish a monument.</p> <p>The witness cor. to the 1/4 sec. cor. of secs. 29 and 32, monumented with an iron post, 1 in. diam., firmly set, projecting 28 ins. above the ground, and in a mound of stone, 3 1/2 ft. base, to top of brass cap, mkd. as described in the official record of the 1925-1941 resurvey.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89° 04' W., beginning new measurement.</p>
39.61	<p>The cor. of secs. 29, 30, 31, and 32.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 04' W., bet. secs. 29 and 30.</p> <p>Over rolling land, through scattered brush.</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 4 S., R. 2 E., Salt Lake Meridian, Utah

CHAINS	
40.38	<p>The 1/4 sec. cor. of secs. 29 and 30, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, and in a collar of stone, with brass cap, mkd. as described in the official record of the 1925-1941 resurvey.</p> <p>Cor. falls 33 lks. N of fence, bears E and W.</p> <p style="text-align: center;">_____</p> <p>N. 0° 15' W., beginning new measurement.</p>
40.30	<p>The cor. of secs. 19, 20, 29, and 30, monumented with an iron post, 2 ins. diam., firmly set, projecting 20 ins. above ground, and in a mound of stone, 3 ft. base, to top of brass cap, mkd. as described in the official record of the 1925-1941 resurvey.</p> <p>Cor. falls in a fence line, bears E and W.</p>
	<p>From the 1/4 sec. cor. of secs. 20 and 29, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap, mkd. as described in the official record of the 1925-1941 resurvey.</p> <p>N. 89° 02' W., bet. secs. 20 and 29.</p> <p>Desc. over mountainous land, through moderate undergrowth.</p>
20.09	<p>Point for the W 1/16 sec. cor. of secs. 20 and 29.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">T 4 S R 2 E S 20 W 1/16 S 29 1983</p>
40.18	<p>The cor. of secs. 19, 20, 29, and 30.</p> <p>N. 0° 09' E., bet. secs. 19 and 20.</p> <p>Over rolling land, through moderate brush.</p>
20.055	<p>Point for the S 1/16 sec. cor. of secs. 19 and 20, not monumented.</p>
40.11	<p>The 1/4 sec. cor. of secs. 19 and 20, monumented with a concrete post, 6 ins. sq., firmly set flush with the ground, with Utah County brass cap mkd.</p> <p style="text-align: center;">T 4 S R 2 E 19   20 1968</p> <p>from which</p> <p style="margin-left: 40px;">A fence post, firmly set, projecting 3 1/2 ft., above ground, bears West, 1 1/2 lks. dist.</p> <p style="margin-left: 40px;">A fence corner, with fences extending E, S, and W, bears N. 47° W., 22 1/2 lks. dist.</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 4 S., R. 2 E., Salt Lake Meridian, Utah

CHAINS

This point is accepted as a careful and faithful  
perpetuation of the position of the original corner.

\_\_\_\_\_

N. 0° 05' E., beginning new measurement.

0.11 The witness cor. to the 1/4 sec. cor. of secs. 19 and 20,  
monumented with an iron post, 1 in. diam., firmly set,  
projecting 14 ins. above ground, with brass cap, mkd. as  
described in the official record of the 1925-1941  
resurvey.

40.59 The cor. of secs. 17, 18, 19, and 20, monumented with a  
concrete post, 6 ins. sq., firmly set flush with ground,  
with Utah County brass cap mkd.

T 4 S R 2 E
S 18   S 17
S 19   S 20
1959

from which

A fence post, firmly set, projecting 3 1/2 ft.,  
bears West, 2 lks. dist.

Cor. falls 34 lks. S of dirt road, bears E and W.

This point is accepted as a careful and faithful  
perpetuation of the position of the original corner.

From the 1/4 sec. cor. of secs. 17 and 20, monumented  
with a mound of stone, 3 ft. base, 1 1/2 ft. high. There  
are no remains of the mkd. stone or iron post.

At the center of the mound of stone

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18  
ins. in the ground, and in a mound of stone, 3 ft. base,  
to top of aluminum cap, mkd.

T 4 S R 2 E
1/4 S 17
S 20
1983

N. 87° 46' W., bet. secs. 17 and 20.

Desc. over mountainous terrain, through scattered brush.

20.165 Point for the W 1/16 sec. cor. of secs. 17 and 20.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24  
ins. in the ground, with aluminum cap mkd.

T 4 S R 2 E
W 1/16 S 17
S 20
1983

Set a cedar post and raise a mound of stone, N of  
aluminum post.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 4 S., R. 2 E., Salt Lake Meridian, Utah

CHAINS	
40.33	The cor. of secs. 17, 18, 19, and 20.
	<hr/> <p>N. 0° 31' W., bet. secs. 17 and 18.</p> <p>Over rolling land, through scattered brush.</p>
40.26	<p>The 1/4 sec. cor. of secs. 17 and 18, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above the ground, and in a mound of stone, 4 ft. base, to top of brass cap, mkd. as described in the official record of the 1925-1941 resurvey.</p> <hr/> <p>N. 0° 29' W., beginning new measurement.</p>
40.36	<p>The cor. of secs. 7, 8, 17, and 18, monumented with an iron post, 2 ins. diam., firmly set, projecting 9 ins. above ground, and in a collar of stone, with brass cap, mkd. as described in the official record of the 1925-1941 resurvey.</p> <p>From this cor., National Geodetic Survey triangulation station Dry Creek, bears N. 54° 31' 26" W., 43.379 chs. dist.</p> <hr/> <p>From the cor. of secs. 8, 9, 16, and 17.</p> <p>N. 86° 08' W., bet. secs. 8 and 17.</p> <p>Desc. over steep, broken slope, through moderate brush.</p>
40.46	<p>The 1/4 sec. cor. of secs. 8 and 17, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above the ground, and in a mound of stone, 3 ft. base, to top of brass cap, mkd. as described in the official record of the 1925-1941 resurvey.</p> <hr/> <p>S. 89° 56' W., beginning new measurement.</p>
19.835	<p>Point for the W 1/16 sec. cor. of secs. 8 and 17; not monumented.</p>
39.67	<p>The cor. of secs. 7, 8, 17, and 18.</p> <hr/> <p>N. 0° 24' W., bet. secs. 7 and 8.</p> <p>Over rolling land, through moderate brush.</p>
19.85	<p>Point for the S 1/16 sec. cor. of secs. 7 and 8; not monumented.</p>
39.70	<p>The 1/4 sec. cor. of secs. 7 and 8, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above the ground, and in a mound of stone, 3 ft. base, to top of brass cap, mkd. as described in the official record of the 1925-1941 resurvey.</p> <hr/> <p>N. 0° 22' W., beginning new measurement.</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 4 S., R. 2 E., Salt Lake Meridian, Utah

<p>CHAINS 39.91</p>	<p>The cor. of secs. 7 and 8, monumented with an iron post, 2 ins. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd. as described in the official record of the 1925-1941 resurvey.</p> <p>A mound of stone, 3 ft. base, 2 ft. high, S of cor.</p>
<p>20.04</p>	<p>From the 1/4 sec. cor. of sec. 8, on the N. bdy. of the section, monumented with an iron post, 1 ins. diam., projecting 18 ins. above the ground, and in a mound of stone, 3 ft. base, to top of brass cap, mkd. as described in the official record of the 1925-1941 resurvey.</p> <p>S. 89° 19' W., bet. secs. 5 and 8.</p> <p>Over mountainous terrain, through moderate brush.</p>
<p>33.60</p>	<p>Point for the W 1/16 sec. cor. of sec. 8.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;"> <u>W 1/16 S 8</u>  <u>T 4 S R 2 E</u>  1983 </p>
<p>6.48</p>	<p>The cor. of secs. 5 and 6, monumented with an iron post, 2 ins. diam., firmly set, projecting 16 ins. above the ground, and in a mound of stone, 3 ft. base, to top of brass cap, mkd. as described in the official record of the 1925-1941 resurvey.</p> <p>S. 89° 52' W., bet. secs. 6 and 8.</p>
<p>19.635</p>	<p>The cor. of secs. 7 and 8.</p> <p style="text-align: center;"> Survey of the Subdivision of Section 8,  T. 4 S., R. 2 E., Salt Lake Meridian, Utah </p>
<p>39.27</p>	<p>From the 1/4 sec. cor. of secs. 8 and 17.</p> <p>N. 0° 05' W., on the N-S center line of sec. 8.</p> <p>Point for the center S 1/16 sec. cor. of sec. 8.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.</p> <p style="text-align: center;"> C     S 1/16   S 8     C  1983 </p>

Survey of the Subdivision of Section 8,  
T. 4 S., R. 2 E., Salt Lake Meridian, Utah

CHAINS	
79.97	<p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 4 S R 2 E C 1/4 S 8 1983</p> <p>The N 1/4 sec. cor. of sec. 8.</p>
40.27	<p>From the point for the E 1/4 sec. cor. of sec. 8., which is at record bearing and distance, South 0.385 chs. dist., from its witness cor., monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above the ground, with brass cap, mkd. as described in the official record of the 1925-1941 resurvey.</p> <p>N. 89° 27' W., on the E-W center line of sec. 8.</p>
60.21	<p>The center 1/4 sec. cor. of sec. 8.</p>
80.15	<p>Point for the center W 1/16 sec. cor. of sec. 8.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">W 1/16 C ——— S 8 ——— C 1983</p>
19.745	<p>The 1/4 sec. cor. of secs. 7 and 8.</p> <p>From the point for the W 1/16 sec. cor. of secs. 8 and 17.</p> <p>N. 0° 14' W., on the N-S center line of the SW 1/4 of sec. 8.</p>
39.49	<p>Point for the SW 1/16 sec. cor. of sec. 8, at intersection with the E-W center line of the SW 1/4.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">SW 1/16 S 8 1983</p>
19.885	<p>The center W 1/16 sec. cor. of sec. 8.</p> <p>From the center S 1/16 sec. cor. of sec. 8.</p> <p>N. 89° 46' W., on the E-W center line of the SW 1/4 of sec. 8.</p>
39.77	<p>The SW 1/16 sec. cor. of sec. 8.</p>
	<p>Point for the S 1/16 sec. cor. of secs. 7 and 8.</p> <p>From the center W 1/16 sec. cor. of sec. 8.</p> <p>N. 0° 13' W., on the N-S center line of the NW 1/4 of sec. 8.</p>

Survey of the Subdivision of Section 8,  
T. 4 S., R. 2 E., Salt Lake Meridian Utah

CHAINS		
40.27	The W 1/16 sec. cor. of sec. 8, on the N. bdy. of the sec.	
	<hr/> Survey of the Subdivision of Section 17, T. 4 S., R. 2 E., Salt Lake Meridian, Utah <hr/>	
	From the 1/4 sec. cor. of secs. 17 and 20. N. 0° 55' W., on the N-S center line of sec. 17.	
40.33	Point for the center 1/4 sec. cor. of sec. 17, at intersection with the E-W center line.  Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.	
	T 4 S R 2 E C 1/4 S 17 1983	
82.25	The 1/4 sec. cor. of secs. 8 and 17.	
	From the 1/4 sec. cor. of secs. 16 and 17. N. 87° 51' W., on the E-W center line of sec. 17.	
40.47	The center 1/4 sec. cor. of sec. 17.	
60.485	Point for the center W 1/16 sec. cor. of sec. 17.  Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.	
	W 1/16 C ——— S 17 ——— C 1983	
80.50	The 1/4 sec. cor. of secs. 17 and 18.	
	From the W 1/16 sec. cor. of secs. 17 and 20. N. 0° 43' W., on the N-S center line of the SW 1/4 of sec. 17.	
40.30	The center W 1/16 sec. cor. of sec. 17.	
	<hr/> Survey of the Subdivision of Section 20, T. 4 S., R. 2 E., Salt Lake Meridian, Utah <hr/>	
	From the 1/4 sec. cor. of secs. 20 and 29. N. 0° 13' E., on the N-S center line of sec. 20.	
19.87	Point for the center S 1/16 sec. cor. of sec. 20.	

Survey of the Subdivision of Section 20,  
T. 4 S., R. 2 E., Salt Lake Meridian, Utah

CHAINS	
	<p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.</p> <div style="text-align: center;"> <p>C   S 1/16   S 20   C 1983</p> </div>
39.74	<p>Point for the center 1/4 sec. cor. of sec. 20, at intersection with the E-W center line.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., over an X chiseled on a boulder, and in a mound of stone, 5 ft. base, to top of aluminum cap, mkd.</p> <div style="text-align: center;"> <p>T 4 S R 2 E C 1/4 S 20 1983</p> </div>
79.81	<p>The 1/4 sec. cor. of secs. 17 and 20.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 20 and 21, monumented the an iron post, 1 in. diam., firmly set, projecting 17 ins. above ground, and in a mound of stone, 3 ft. base, to top of brass cap, mkd. as described in the official record of the 1925-1941 resurvey.</p> <p>from which</p> <div style="text-align: center;"> <p>A spruce, 20 ins. diam., bears N. 55 1/2° W., 92 1/2 lks. dist., mkd. with a healed blaze. (Record, N. 57° W., 91 lks. dist.).</p> </div> <p>N. 88° 30' W., on the E-W center line of sec. 20.</p>
40.26	<p>The center 1/4 sec. cor. of sec. 20.</p>
60.375	<p>Point for the center W 1/16 sec. cor. of sec. 20.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>W 1/16 C ——— S 20 ——— C 1983</p> </div>
80.49	<p>True point for the 1/4 sec. cor. of secs. 19 and 20.</p> <hr/> <p>From the W 1/16 sec. cor. of secs. 20 and 29.</p> <p>N. 0° 11' E., on the N-S center line of the SW 1/4 of sec. 20.</p>
19.965	<p>Point for the SW 1/16 sec. cor. of sec. 20, at intersection with the E-W center line of the SW 1/4.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p>

Survey of the Subdivision of Section 20,  
T. 4 S., R. 2 E., Salt Lake Meridian, Utah

CHAINS		
	SW 1/16 S 20 1983	
39.93	The center W 1/16 sec. cor. of sec. 20.	
	From the center S 1/16 sec. cor. of sec. 20. N. 88° 46' W., on the E-W center line of the SW 1/4 of sec. 20.	
20.105	The SW 1/16 sec. cor. of sec. 20.	
40.21	The S 1/16 sec. cor. of secs. 19 and 20.	
	From the center W 1/16 sec. cor. of sec. 20. N. 0° 09' E., on the N-S center line of the NW 1/4 of sec. 20.	
40.33	The W 1/16 sec. cor. of secs. 17 and 20.	
	Survey of the Subdivision of Section 29, T. 4 S., R. 2 E., Salt Lake Meridian, Utah	
	From the true point for the 1/4 sec. cor. of secs. 29 and 32. N. 0° 11' W., on the N-S center line of sec. 29.	
40.68	Point for the center 1/4 sec. cor. of sec. 29, at inter- section with the E-W center line. Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.	
	T 4 S R 2 E C 1/4 S 29 1983	
	Cor. is located on N slope.	
80.65	The 1/4 sec. cor. of secs. 20 and 29.	
	From the true point for the 1/4 sec. cor. of secs. 28 and 29. N. 89° 29' W., on the E-W center line of sec. 29.	
40.00	The center 1/4 sec. cor. of sec. 29.	
80.14	The 1/4 sec. cor. of secs. 29 and 30.	
	Survey of the Subdivision of Section 32, T. 4 S., R. 2 E., Salt Lake Meridian, Utah	

Survey of the Subdivision of Section 32,  
T. 4 S., R. 2 E., Salt Lake Meridian, Utah

CHAINS	
19.92	<p>From the 1/4 sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp., heretofore described.</p> <p>N. 0° 16' E., on the N-S center line of sec. 32.</p> <p>Point for the center S 1/16 sec. cor. of sec. 32.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p>
39.84	<div style="text-align: center;"> <p>C</p> <p> </p> <p>S 1/16   S 32</p> <p> </p> <p>C</p> <p>1983</p> </div> <p>Set a wooden post alongside the aluminum post.</p> <p>Point for the center 1/4 sec. cor. of sec. 32, at intersection with the E-W center line.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.</p>
80.10	<div style="text-align: center;"> <p>T 4 S R 2 E</p> <p>C 1/4 S 32</p> <p>1983</p> </div> <p>The 1/4 sec. cor. of sec. 29 and 32.</p>
40.37	<p>From the true point for the 1/4 sec. cor. of secs. 32 and 33.</p> <p>N. 89° 27' W., on the E-W center line of sec. 32.</p> <p>The center 1/4 sec. cor. of sec. 32.</p>
80.57	<p>The 1/4 sec. cor. of secs. 31 and 32.</p>
40.47	<p>From the S 1/16 sec. cor. of secs. 32 and 33.</p> <p>N. 89° 28' W., on the E-W center line of the SE 1/4 of sec. 32.</p> <p>The center S 1/16 sec. cor. of sec. 32.</p>
	<p style="text-align: center;">General Description</p> <p>The area surveyed lies just east of Alpine, Utah, along the west face of the Wasatch Mountains. Elevation ranges from 5,000 to 8,000 ft. above sea level.</p> <p>American Fork Canyon and numerous smaller canyons drain westerly through the surveyed sections. Soil is generally shallow and rocky, supporting mainly sagebrush, oakbrush, maples and junipers. Numerous roads serving the residents of Alpine and surrounding farm lands provide easy access to the foothills.</p>



CERTIFICATE OF SURVEY

(I) ~~XXX~~, Gary L. Kratz, Supervisory Cadastral Surveyor, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 26th day

of May, 1983, (I) ~~XXX~~ have dependently resurveyed a portion of the south boundary, and a portion of the subdivisional lines with a subdivision survey of sections 8, 17, 20, 29, and 32 of T. 4 S., R. 2 E.,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), ~~XXX~~ and under (my) ~~XXX~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

May 9, 1985 (Date) Gary L. Kratz (Cadastral Surveyor) Supervisory

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT

The foregoing field notes of the dependent resurvey of a portion of the south boundary, and a portion of the subdivisional lines with a subdivision survey of sections 8, 17, 20, 29, and 32 of T. 4 S., R. 2 E., Salt Lake Meridian, Utah

executed by Gary L. Kratz, Supervisory Cadastral Surveyor having been critically examined and found correct, are hereby approved.

December 5, 1985 (Date) Glen B. Hatch Chief Cadastral Surveyor for Utah

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

(Date) (Signature of Authorized Officer)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
ORIGINAL

R 608

94

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF THE

SOUTH BOUNDARY OF T. 14 N., R. 4 E.,

THE NORTH 2 MILES OF THE EAST BOUNDARY OF T. 13 N., R. 3 E.,

THE NORTH 1 MILE OF THE EAST BOUNDARY,

AND THE

NORTH TIER OF THE SUBDIVISIONAL SECTION LINES

OF

TOWNSHIP 13 NORTH, RANGE 4 EAST

Of the Salt Lake Meridian,

In the State of Utah

EXECUTED BY

Frank C. Profaizer, Jr. Cadastral Surveyor

Under special instructions dated September 16, 1983, approved September 19, 1983

\_\_\_\_\_, which provided for the surveys included under <sup>XXXXXXXXXX</sup> U.S. Survey Group  
Number 640, and assignment instructions dated September 19, 1983.

Survey commenced September 19, 1983

Survey completed September 8, 1984

# INDEX DIAGRAM

Township 13 North, Range 4 East  
 8                      7                      6                      5                      3                      2

11	6 18	5 16	4 15	3 14	2 13	1 9
	18	17	15	14	13	12
10	7	8	9	10	11	12
	18	17	16	15	14	13
	19	20	21	22	23	24
	30	29	28	27	26	25
	31	32	33	34	35	36

## Township 13 North, Range 4 East, Salt Lake Meridian, Utah

## CHAINS

The following field notes describe the dependent resurvey of the south boundary of T. 14 N., R. 4 E., the north 2 miles of the east boundary of T. 13 N., R. 3 E., the north 1 mile of the east boundary, and the north tier of the subdivisional section lines of Township 13 North, Range 4 East, Salt Lake Meridian, Utah.

History of Surveys

<u>Surveyed by</u>	<u>Retr. or Resurveyed by</u>
--------------------	-------------------------------

NORTH BOUNDARY

All	J.H. Martineau	1881	
All			Hanson and Giers 1900
All			F.E. Joy 1904
Portion			F.C. Profzaizer 1982

EAST BOUNDARY

All	A.P. Hanson	1896	
Portion			Hanson and Giers 1900
All			F.E. Joy 1904

WEST BOUNDARY

All	J.H. Martineau	1881	
Portion			F.E. Joy 1904

SUBDIVISION

All Hanson and Giers 1900

Certain corners were remonumented in 1968 under the remonumentation cooperative agreement between the U.S. Forest Service and the Bureau of Land Management.

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group 640, Utah, dated September 16, 1983.

The direction of lines were determined by reference to true meridians established on line by altitude observations on the sun, and by hour angle observations on Polaris. The lines were carried forward by sustained angulations, being supplemented by other observations on Polaris taken throughout the progress of the survey. Distances were determined by electronic measurement.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions, lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Detectable Electronically Energized Particles (DEEP-1TM) were used to reference certain corner monuments, buried under the surface of the ground. The DEEP-1 is composed of strontium; encased in a color coded plastic container. The units are 1 inch in diameter, 2 1/2 ins. long, weight 2 1/2 ounces and are magnetically detectable to an average buried depth of 8 feet.

## Township 13 North, Range 4 East, Salt Lake Meridian, Utah

CHAINS		
	<p>The geographic position of the corner of secs. 1, 6, 7, and 12, on the E. bdy. of the township, as determined from a tie made to a standard U.S. Department of Agriculture, Forest Service triangulation station "SINKER", located in the SW1/4 of sec. 5, T. 13 N., R. 4 E., Salt Lake Meridian, Utah, is as follows:</p> <p>Latitude 41° 53' 24.04" N. Longitude 111° 26' 21.13" W.</p> <p>The mean magnetic declination is 15° E.</p>	
	<p>Dependent Resurvey of the South Boundary, T. 14 N., R. 4 E., Salt Lake Meridian, Utah</p>	
	<p>(Restoring the Survey Executed by J.H. Martineau in 1881 and the Retracement Executed by Hanson and Giers in 1900, F.E. Joy in 1904 and F.C. Profaizer in 1982)</p> <hr/> <p>Beginning at the SE cor. of T. 14 N., R. 4 E., monumented with a sandstone, 15 x 10 x 9 ins., firmly set, and projecting 6 ins. above ground, mkd. 6 notches on S, E, and W edges, and in a mound of stone, 3 1/2 ft. base, to top of mkd. stone.</p> <p>At the corner point</p> <p>Set a DEEP-1 magnetic marker buried 18 ins. in the ground, as a memorial at the base of mkd. stone.</p> <p>Note: This cor. and the 1/4 sec. cor. of sec. 31 were set by J.H. Martineau in 1881, and were not found by Hanson and Giers in their Retracement in 1900 or A.P. Hanson in 1896 and will now be used only to determine the true intersection of the Martineau survey of T. 14 N., R. 4 E., with the now controlling west boundary of T. 14 N., R. 5 E., established by A.P. Hanson in 1896.</p> <p>S. 89° 03.7' W., along the S. bdy of sec. 36.</p>	
38.923	<p>The 1/4 sec. cor. of sec. 36, monumented with a quartzite, 16 x 12 x 6 ins. mkd. 1/4 on N face, firmly set and projecting 8 ins. above ground, and in a mound of stone, 3 1/2 ft. base, to top of mkd. stone.</p> <p>At the corner point</p> <p>Set a DEEP-1 magnetic marker buried 18 ins. in the ground, as a memorial at the base of mkd. stone.</p>	
2.656	<p>S. 89° 48.1' W., beginning new measurement.</p> <p>Witness Corner Boundary Post No. 63, monumented with an iron post, 4 ins. diam., projecting 12 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">W C No. 63 RESERVE 1904</p> <p>As described in the official record of the 1904 retracement in establishment of U.S. Forest Reserve Boundary.</p>	

Dependent Resurvey of the South Boundary,  
T. 14 N., R. 4 E., Salt Lake Meridian, Utah

CHAINS 2.704	<p>Point for the closing cor. of secs. 1 and 36, at intersection with the W. bdy. of T. 13 N., R. 5 E., as established by A.P. Hanson in 1896.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 14 N R 4 E R 5 E C S 36   C S 1   S 31 T 13 N 1984</p> </div>
38.020	<p>Point for the 1/4 sec. cor. of sec. 1 only, at midpoint and on the N. bdy. of sec. 1.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of cap, mkd.</p> <div style="text-align: center;"> <p>T 14 N R 4 E <hr/>1/4 S 1 T 13 N R 4 E 1984</p> </div>
41.260	<p>Witness Corner Boundary Post No. 64, monumented with an iron post, 4 ins. diam., projecting 12 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>W C T 14 N R 4 E S 35   S 36 T 13 N R 4 E No. 64 RESERVE 1904</p> </div> <p>As described in the official record of the 1904 retracement in establishment of U.S. Forest Reserve Boundary.</p>
41.319	<p>The cor. of secs. 35 and 36 only, monumented with a sandstone, 21 x 10 x 8 ins., (record, 18 x 12 x 8 ins.) plainly mkd. 1 notch on E edge and 5 notches on W edge, firmly set and projecting 12 ins. above ground, and in a mound of stone, 3 ft. base, to top of mkd. stone.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 14 N R 4 E S 35   S 36 <hr/>S 1 T 13 N R 4 E 1984</p> </div> <p>Deposit the mkd. stone alongside the aluminum post.</p>
32.017	<p>S. 89° 08.9' W., along the S. bdy. of sec. 35.</p> <p>Point for the closing cor. of secs. 1 and 2, T. 13 N., R. 4 E., at proportionate distance; there is no remaining evidence of the original corner.</p>

Dependent Resurvey of the South Boundary,  
T. 14 N., R. 4 E., Salt Lake Meridian, Utah

## CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 14 N R 4 E  
S 35  
-----  
S 2 | S 1  
T 13 N R 4 E  
C C  
1984

40.075 The point for the 1/4 sec. cor. of sec. 35 only, at proportionate distance, based on the irregular boundary method, using the retracement executed by F.E. Joy in 1904; there is no remaining evidence of the original corner or original bearing trees.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 14 N R 4 E  
1/4 S 35  
-----  
T 13 N R 4 E  
1984

S. 89° 34.4' W., beginning new measurement.

32.946 Point for the 1/4 sec. cor. of sec. 2 only, at midpoint and on the N. bdy. of sec. 2.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 14 N R 4 E  
-----  
1/4 S 2  
T 13 N R 4 E  
1984

40.796 Witness Corner Boundary Post No. 65, monumented with an iron post, 4 ins. diam., projecting 12 ins. above ground, with brass cap mkd.

W C  
T 14 N R 4 E  
S 34 | S 35  
-----  
T 13 N R 4 E  
No. 65 RESERVE  
1904

As described in the official record of the 1904 retracement in establishment of U.S. Forst Reserve Boundary.

40.856 The cor. of secs. 34 and 35 only, monumented with a limestone, 16 x 12 x 7 ins., (record, 16 x 10 x 8 ins.) plainly mkd. 2 notches on E edge and 4 notches on W edge, firmly set, projecting 8 ins. above ground, and in a mound of stone, 2 1/2 ft. base, to top of mkd. stone.

from which

A fir, 17 ins. diam., bears N. 70° E., 12 1/2 lks. dist., mkd. T14N R4E S35 BT.

A spruce, 26 ins. diam., bears S. 14° E., 17 lks. dist., mkd. with a blaze.

Dependent Resurvey of the South Boundary,  
T. 14 N., R. 4 E., Salt Lake Meridian, Utah

CHAINS		
	<p>A dead spruce, 17 ins. diam., bears S. 57° W., 16 lks. dist., mkd. T13N R4E S2 BT.</p> <p>A fir, 19 ins. diam., bears N. 58° W., 20 lks. dist., mkd. T14N R4E S34 BT.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 14 N R 4 E S 34   S 35 S 2 T 13 N R 4 E 1984</p> <p>Deposit the mkd. stone alongside the aluminum post.</p>	
33.089	<p>S. 89° 09.2' W., along the S. bdy. of sec. 34.</p> <p>Point for the closing cor. of secs. 2 and 3, T. 13 N., R. 4 E., at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 14 N R 4 E S 34 S 3   S 2 T 13 N R 4 E C C 1984</p>	
41.182	<p>The 1/4 sec. cor. of sec. 34 only, monumented with an iron post, 2 1/2 ins. diam., firmly set, and projecting 10 ins. above ground, and in a collar of stone, with brass cap, mkd. as described in the official record of the 1968 remonumentation of T. 14 N., R. 4 E.</p>	
18.940	<p>S. 89° 12.2' W., beginning new measurement.</p> <p>Witness Corner Boundary Post No. 66, monumented with an iron post, 4 ins. diam., projecting 12 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">W C No. 66 RESERVE 1904</p> <p>As described in the official record of the 1904 retracement in establishment of U.S. Forest Reserve Boundary.</p>	
33.345	<p>Point for the 1/4 sec. cor. of sec. 3 only, at midpoint and on the N. bdy. of sec. 3.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 14 N R 4 E 1/4 S 3 T 13 N R 4 E 1984</p>	

Dependent Resurvey of the South Boundary,  
T. 14 S., R. 4 E., Salt Lake Meridian, Utah

<p>CHAINS 41.178</p>	<p>The cor. of secs. 33 and 34 only, on the S. bdy. of T. 14 N., R. 4 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, and projecting 15 ins. above ground, and in a mound of stone, 4 ft. base, to top of brass cap, mkd. as described in the official record of the 1968 remonumentation of T. 14 N., R. 4 E.</p>
<p>0.060</p>	<p>S. 89° 27.6' W., along the S. bdy. of sec. 33.</p> <p>Witness Corner Boundary Post No. 67, monumented with an iron post, 4 ins. diam., projecting 12 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">           W C            T 14 N R 4 E            S 33   S 34            T 13 N R 4 E            No. 67 RESERVE            1904         </p> <p>As described in the official record of the 1904 retracement in establishment of U.S. Forest Reserve.</p>
<p>33.607</p>	<p>Point for the closing cor. of secs. 3 and 4, T. 13 N., R. 4 E., at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">           T 14 N R 4 E            S 33            S 4   S 3            T 13 N R 4 E            C C            1984         </p>
<p>41.362</p>	<p>The 1/4 sec. cor. of sec. 33 only, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 15 ins. above ground, and in a mound of stone, 3 1/2 ft. base, to top of brass cap, mkd. as described in the official record of the 1968 remonumentation of T. 14 N., R. 4 E.</p>
<p>33.180</p>	<p>S. 89° 16.4' W., beginning new measurement.</p> <p>Point for the 1/4 sec. cor. of sec. 4 only, at midpoint and on the N. bdy. of sec. 4.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">           T 14 N R 4 E            1/4 S 4            T 13 N R 4 E            1984         </p>
<p>40.394</p>	<p>Witness Corner Boundary Post No. 68, monumented with an iron post, 4 ins. diam., projecting 12 ins. above ground, with brass cap mkd.</p>

Dependent Resurvey of the South Boundary,  
T. 14 N., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
40.457	<p style="text-align: center;">W C T 14 N R 4 E S 32   S 33 T 13 N R 4 E No. 68 RESERVE 1904</p> <p>As described in the official record of the 1904 retracement in establishment of U.S. Forest Reserve Boundary.</p> <p>The cor. of secs. 32 and 33 only, on the S. bdy. of T. 14 N., R. 4 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, and projecting 4 ins. above a collar of stone, with brass cap, mkd. as described in the official record of the 1968 remonumentation of T. 14 N., R. 4 E.</p>
33.658	<p>S. 88° 37.9' W., along the S. bdy. of sec. 32.</p> <p>Point for the closing cor. of secs. 4 and 5, T. 13 N., R. 4 E., at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>
40.859	<p style="text-align: center;">T 14 N R 4 E S 32 S 5   S 4 T 13 N R 4 E C C 1984</p> <p>The 1/4 sec. cor. of sec. 32 only, monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. above ground, and in a mound of stone, 3 ft. base, to top of brass cap, mkd. as described in the official record of the 1983 resurvey of the S. bdy. of T. 14 N., R. 4 E.</p> <p>N. 89° 44.2' W., beginning new measurement.</p>
33.168	<p>Point for the 1/4 sec. cor. of sec. 5 only, at midpoint and on the N. bdy. of sec. 5.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 14 N R 4 E 1/4 S 5 T 13 N R 4 E 1984</p>
40.834	<p>Witness Corner Boundary Post No. 69, monumented with an iron post, 4 ins. diam., projecting 18 ins. above ground, and in a mound of stone, 3 1/2 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">W C T 14 N R 4 E S 31   S 32 T 13 N R 4 E No. 69 RESERVE 1904</p>

Dependent Resurvey of the South Boundary,  
T. 14 N., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	As described in the official record of the 1904 retracement in establishment of U.S. Forest Reserve Boundary.
40.895	The cor. of secs. 31 and 32 only, on the S. bdy. of T. 14 N., R. 4 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above a collar of stone, 3 ft. base, with brass cap, mkd. as described in the official record of the 1968 remonumentation for T. 14 N., R. 4 E.
32.642	<p>S. 89° 06.5' W., along the S. bdy. of sec. 31.</p> <p>Point for the closing cor. of secs. 5 and 6, T. 13 N., R. 4 E., at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 14 N R 4 E S 31 ----- S 6   S 5 T 13 N R 4 E C C 1984</p>
39.661	<p>The 1/4 sec. cor. of sec. 31 only, monumented with a limestone, 17 x 9 x 7 ins., mkd. 1/4 on N face, firmly set, and projecting 8 ins. above ground, and in a mound of stone, 3 ft. base, to top of mkd. stone.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 14 N R 4 E 1/4 S 31 ----- T 13 N R 4 E 1984</p> <p>Deposit the mkd. stone alongside the aluminum post.</p> <p style="text-align: center;">-----</p> <p>S. 89° 32.3' W., beginning new measurement.</p>
32.043	<p>Point for the 1/4 sec. cor. of sec. 6 only, T. 13 N., R. 4 E., at proportionate distance.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 14 N R 4 E ----- 1/4 S 6 T 13 N R 4 E 1984</p>
38.469	The cor. of Tps. 13 and 14 N., Rs. 3 and 4 E., monumented with an iron post, 4 ins. diam., firmly set and projecting 16 ins. above the ground, and in a mound of stone, 3 ft. base, with brass cap, mkd. as described in the official record of the 1904 resurvey.

Dependent Resurvey of North 1 Mile of the East Boundary,  
T. 13 N., R. 4 E., Salt Lake Meridian, Utah

CHAINS	Dependent Resurvey of North 1 Mile of the East Boundary, T. 13 N., R. 4 E., Salt Lake Meridian, Utah
	<p>Restoring the Resurvey and Retracement by A.P. Hanson in 1896, Hanson and Giers in 1900, F.E. Joy in 1904, and Andrew Nelson in 1962)</p> <hr/> <p>From the cor. of secs. 1, 6, 7, and 12, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1962 remonumentation of corners in T. 13 N., R. 5 E.</p> <p>From which the Witness Corner Boundary Post No. 61, bears N. 35° E., 5 1/2 lks. dist., monmented with an iron post, 4 ins. diam., firmly set, projecting 18 ins. above ground, with brass cap, mkd. as described in the official record of the 1904 resurvey of the E. bdy. of T. 13 N., R. 4 E.</p> <p>N. 1° 09.3' E., bet. secs. 1 and 6.</p>
40.219	<p>The 1/4 sec. cor. of secs. 1 and 6, monumented with an iron post, 2 1/2 ins. diam., firmly set, and projecting 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1962 remonumentation of T. 13 N., R. 5 E.</p> <hr/> <p>N. 0° 05.0' E., beginning new measurement.</p>
12.869	<p>Witness Corner Boundary Post No. 62, monumented with an iron post, 4 ins. diam., projecting 12 ins. above ground, and in a mound of stone, 3 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">W C No. 62 RESERVE 1904</p> <p>As described in the official record of the 1904 retracement in establishment of U.S. Forest Reserve Boundary.</p>
47.682	<p>From this point the closing cor. of secs. 6 and 31, Tps. 13 and 14 N., R. 5 E., established by A.P. Hanson in 1896, bears East, 6 lks. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set and projecting 16 ins. above ground, and in a mound of stone, 3 ft. base, to top of brass cap, mkd. as described in the official record of the 1962 remonumentation of T. 13 N., R. 5 E.</p>
53.695	<p>Intersect the S. bdy. of T. 14 N., R. 4 E., established by J.H. Martineau in 1881.</p> <p>Point for the closing cor. of secs. 1 and 36 of Tps. 13 and 14 N., R. 4 E., heretofore described.</p>
66.969	<p>The closing cor. of secs. 1 and 6, T. 13 N., Rs. 4 and 5 E., established by A.P. Hanson in 1896, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 16 ins. above ground, with brass cap, mkd. as described in the official record of the 1962 remonumentation of T. 13 N., R. 5 E.</p>

Dependent Resurvey of the North 1 Mile of the East Boundary,  
T. 13 N., R. 4 E., Salt Lake Meridian, Utah

CHAINS

This cor. will now function as an angle point only on the W. bdy. of T. 14 N., R. 5 E., and was remarked.

A P  
T 14 N  
R 4 E | R 5 E  
S 36 | S 31  
1984  
1962

From which the cor. of T. 14 N., Rs. 4 and 5 E., as established by A.P. Hanson in 1896, bears S.  $89^{\circ} 30.5'$  E., 3.329 chs. dist., monumented with an iron post, 2 1/2 ins. diam., loosely set, projecting 12 ins. above ground, with brass cap, mkd. as described in the official record of the 1962 remonumentation of T. 14 N., R. 4 E. This cor. will function as an angle point only on the W. bdy. of T. 14 N., R. 5 E., and was remarked.

A P  
T 14 N  
R 4 E | R 5 E  
S 36 | S 31  
1984  
1962

Dependent Resurvey of the North 2 Miles  
of the East Boundary of T. 13 N., R. 3 E.,  
Salt Lake Meridian, Utah

(Restoring the Survey Executed by  
J.H. Martineau in 1881 and the Resurvey Executed by  
F.E. Joy in 1904)

From the cor. of secs. 12 and 13, monumented with a limestone, 18 x 12 x 7 ins., (record, 12 x 10 x 8 ins.) loosely set in the center of an old scattering mound of stone. No visible marks on the stone.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.

T 13 N  
R 3 E | R 4 E  
S 12 |  
S 13 | S 7  
1984

from which a bearing object

A limestone cliff, 30 ft. high, facing SW, bears N.  $55^{\circ}$  E., 22 1/2 lks. dist., mkd. BOX at base N.  $0^{\circ} 09.3'$  E., along the E. bdy. of sec. 12.

Dependent Resurvey of the North 2 Miles of the East Boundary,  
T. 13 N., R. 3 E., Salt Lake Meridian, Utah

CHAINS 40.435	<p>Point for the 1/4 sec. cor. of sec. 12 only, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 13 N R 3 E R 4 E 1/4   S 12   1984</p>
76.119	<p>Point for the closing cor. of secs. 6 and 7, on the W. bdy. of Tp. 13 N., R. 4 E., at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 13 S R 3 E R 4 E   S 6 C S 12   S 7 C 1984</p>
80.870	<p>Point for the cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 13 N R 3 E R 4 E S 1   S 12   S 6 1984</p>
34.961	<p>N. 0° 09.3' E., along the E. bdy. of sec. 1.</p> <p>Point for the 1/4 sec. cor. of sec. 6 only, T. 13 N., R. 4 E., at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 13 N R 3 E R 4 E   1/4   S 6 1984</p>
40.435	<p>The 1/4 sec. cor. of sec. 1 only, on E. bdy. of the Tp., monumented with a limestone, 12 x 10 x 4 ins., firmly set, and projecting 7 ins. above ground, mkd. 1/4 on W face, and in a small collar of stone.</p> <p>From which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A pine, 18 ins. diam., bears N. 45° E., 18 lks. dist., mkd. with blaze.</p> <p style="padding-left: 40px;">A pine, 29 ins. diam., bears S. 35° W., 22 lks. dist., mkd. with blaze.</p>

Dependent Resurvey of the North 2 Miles of the East Boundary,  
T. 13 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
38.909	<p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.</p> <p style="text-align: center;">T 13 N R 3 E R 4 E 1/4   S 1   1984</p> <p>Deposit the mkd. stone alongside the aluminum post.</p> <p>Cor. is located on NW slope, at S edge of thick stand of pines.</p> <p style="text-align: center;">_____</p> <p>N. 0° 55.4' E., beginning new measurement.</p> <p>The cor. of Tps. 13 and 14 N., Rs. 3 and 4 E., heretofore described.</p>
	<p style="text-align: center;">Dependent Resurvey of a Portion of the Subdivisional Lines, T. 13 N., R. 4 E., Salt Lake Meridian, Utah</p>
42.432	<p style="text-align: center;">(Restoring the Survey Executed by Hanson and Giers in 1900)</p> <p style="text-align: center;">_____</p> <p>From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., heretofore described.</p> <p>N. 89° 07.2' W., bet. secs. 1 and 12.</p> <p>Point for the 1/4 sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 13 N R 4 E S 1 1/4 — S 12 1984</p>
84.864	<p>The cor. of secs. 1, 2, 11, and 12, monumented with a quartzite stone, 18 x 11 x 5 ins., firmly set and projecting 9 ins. above ground, in the center of an old scattering mound of stone, mkd. 5 notches on S and 1 notch on E edge.</p> <p>from which the remains of the original bearing tree</p> <p style="text-align: center;">A pine, 16 ins. diam., bears S. 65° W., 88 lks. dist., mkd. T13N R4E S11 BT.</p> <p>At the corner point</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 13 N., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
41.608	<p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a mound of stone, 3 ft. base, to top of aluminum cap mkd.</p> <p style="text-align: center;">           T 13 N R 4 E            S 2   S 1            S 11   S 12            1984         </p> <p>Deposit the mkd. stone alongside the aluminum post.</p>
93.222	<p>N. 90° 18.9' E., bet. secs. 1 and 2.</p> <p>Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">           T 13 N R 4 E            1/4            S 2   S 1            1984         </p> <p>The closing cor. of secs. 1 and 2, T. 13 N., R. 4 E., heretofore described.</p>
40.006	<p>From the cor. of secs. 1, 2, 11, and 12.</p> <p>N. 86° 40.5' W., bet. secs. 2 and 11.</p> <p>The 1/4 sec. cor. of secs. 2 and 11, monumented with an aluminum post, 2 1/2 ins. diam., projecting 12 ins. above ground, and in a mound of stone, 3 1/2 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">           U.S. DEPT. OF AGRICULTURE            T 13 N R 4 E            S 2            1/4 S 11            1978            FOREST SERVICE         </p> <p>Forest Service determined the cor. position from the original limestone, 19 x 11 x 5 ins., mkd. 1/4 and deposit alongside of aluminum post.</p> <p>Cor. is located on SE slope at E edge of large open area.</p>
39.911	<p>S. 89° 24.6' W., beginning new measurement.</p> <p>The cor. of secs. 2, 3, 10, and 11, monumented with a quartzite stone, 17 x 10 x 6 ins., firmly set and projecting 8 ins. above ground and mkd. 5 notches on S edge and 2 notches on E edge.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 13 N., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	<p>from which the remains of the original bearing trees</p> <p>An aspen, 10 ins. diam., bears S. 74° W., 57 lks. dist., mkd. T13N R4E S10 BT.</p> <p>An aspen, 14 ins. diam., bears N. 63° W., 20 lks. dist., mkd. T13N R4E S3 BT.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.</p> $\begin{array}{c} T\ 13\ N\ R\ 4\ E \\ S\ 3\   \ S\ 2 \\ \hline S\ 10\   \ S\ 11 \\ 1983 \end{array}$ <p>Deposit the mkd. stone alongside the aluminum post.</p>
40.642	<p>N. 8° 14.7' E., bet. secs. 2 and 3.</p> <p>Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.</p> $\begin{array}{c} T\ 13\ N\ R\ 4\ E \\ 1/4 \\   \\ S\ 3\   \ S\ 2 \\   \\ 1984 \end{array}$
90.103	<p>The closing cor. of secs. 2 and 3, T. 13 N., R. 4 E., heretofore described.</p> <hr/> <p>From the cor. of secs. 2, 3, 10, and 11.</p> <p>S. 89° 24.4' W., bet. secs. 3 and 10.</p> <p>40.048 The 1/4 sec. cor. of secs. 3 and 10, monumented with a limestone, 18 x 8 x 6 ins., firmly set and projecting 9 ins. above ground, mkd. 1/4 on N face, and in a mound of stone, 2 1/2 ft. base.</p> <p>from which the remains of the original bearing tree</p> <p>A pine, 30 ins. diam., bears S. 25° W., 15 lks. dist., mkd. 1/4 S10 BT.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.</p> $\begin{array}{c} T\ 13\ N\ R\ 4\ E \\ S\ 3 \\ 1/4 \quad \hline S\ 10 \\ 1984 \end{array}$

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 13 N. R. 4 E., Salt Lake Meidian, Utah

CHAINS					
40.193	<p>Deposit the mkd. stone alongside the aluminum post.</p> <p>S. 89° 32.1' W., beginning new measurement.</p> <p>The cor. of secs. 3, 4, 9, and 10, monumented with a sandstone, 17 x 8 x 7 ins., firmly set and projecting 8 ins. above ground, mkd. 5 notches on S edge and 3 notches on E edge.</p> <p>from which the remains of the original bearing tree</p> <p style="padding-left: 40px;">A dead pine, 20 ins. diam., bears S. 85° 45' W., 36 lks. dist., mkd. T13N R4E S9 BT.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a mound of stone, 3 ft. base, to top of aluminum cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T 13 N R 4 E</td></tr> <tr><td>S 4   S 3</td></tr> <tr><td>S 9   S 10</td></tr> <tr><td>1983</td></tr> </table> </div> <p>Deposit the mkd. stone alongside the aluminum post.</p>	T 13 N R 4 E	S 4   S 3	S 9   S 10	1983
T 13 N R 4 E					
S 4   S 3					
S 9   S 10					
1983					
40.875	<p>N. 6° 35.4' E., bet. secs. 3 and 4.</p> <p>Point for the 1/4 sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td>T 13 N R 4 E</td></tr> <tr><td>1/4</td></tr> <tr><td>S 4   S 3</td></tr> <tr><td>1984</td></tr> </table> </div>	T 13 N R 4 E	1/4	S 4   S 3	1984
T 13 N R 4 E					
1/4					
S 4   S 3					
1984					
89.495	<p>The closing cor. of secs. 3 and 4, T. 13 N., R. 4 E., heretofore described.</p>				
40.098	<p>From the cor. of secs. 3, 4, 9, and 10.</p> <p>S. 89° 20.0' W., bet. secs. 4 and 9.</p> <p>The 1/4 sec. cor. of secs. 4 and 9, monumented with a limestone, 17 x 9 x 6 ins., firmly set and projecting 8 ins. above the ground, mkd. 1/4 on N face, and in a mound of stone, 2 1/2 ft. base.</p> <p>from which the remains of the original bearing tree</p> <p style="padding-left: 40px;">A pine, 30 ins. diam., bears S. 31° 32' W., for 26 lks. dist., mkd. 1/4 S9 BT.</p>				

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 13 N. R. 4 E., Salt Lake Meridian, Utah

CHAINS	
39.711	<p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a mound of stone, 3 ft. base, to top of aluminum cap mkd.</p> <p style="text-align: center;">T 13 N R 4 E S 4 1/4 S 9 1984</p> <p>Deposit the mkd. stone alongside the aluminum post.</p> <p>S. 89° 04.7' W., beginning new measurement.</p> <p>The cor. of secs. 4, 5, 8, and 9, monumented with a limestone, 20 x 11 x 3 ins., (record, 17 x 11 x 5 ins.) firmly set and projecting 11 ins. above ground, mkd. 5 notches on S edge and 4 notches on E edge.</p> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">As aspen, 10 ins. diam., bears N. 21° E., 36 lks. dist., mkd. S4 BT.</p> <p style="padding-left: 40px;">A pine, 18 ins. diam., bears S. 74° E., 44 lks. dist., mkd. with blaze.</p> <p style="padding-left: 40px;">An aspen, 11 ins. diam., bears N. 85° W., 29 1/2 lks. dist., mkd. S5 BT.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">T 13 N R 4 E S 5   S 4 S 8   S 9 1984</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 11 ins. diam., bears S. 17° W., 30 lks. dist., mkd. T13N R4 E S8 BT.</p> <p>Deposit the mkd. stone alongside the aluminum post.</p>
41.145	<p>N. 5° 17.0' E., bet. secs. 4 and 5.</p> <p>Point for the 1/4 sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a mound of stone, 3 ft. base, to top of aluminum cap mkd.</p> <p style="text-align: center;">T 13 N R 4 E 1/4 S 5   S 4 1984</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 13 N., R. 4 E., Salt Lake Meridian, Utah

<p>CHAINS 88.996</p>	<p>The closing cor. of secs. 4 and 5, T. 13 N., R. 4 E., heretofore described.</p>						
<p>40.130</p>	<p>From the cor. of secs. 4, 5, 8, and 9. N. 89° 46.9' W., bet. secs. 5 and 8.</p> <p>The 1/4 sec. cor. of secs. 5 and 8, monumented with a limestone, 19 x 9 x 9 ins., (record, 17 x 9 x 6 ins.) firmly set, and projecting 3 ins. above a mound of stone, 2 1/2 ft. base, mkd. 1/4 on N face at top of stone.</p> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">An aspen, 12 ins. diam., bears S. 45° W., 20 1/2 lks. dist., mkd. 1/4 S8 BT.</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears N. 11° W., 25 lks. dist., mkd. with blaze.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.</p> <div style="text-align: center;"> <p>T 13 N R 4 E</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td></td> <td style="text-align: center;">S 5</td> <td></td> </tr> <tr> <td style="text-align: center;">1/4</td> <td style="text-align: center;">S 8</td> <td></td> </tr> </table> <p>1984</p> </div> <p>Deposit the mkd. stone alongside the aluminum post.</p> <p>from which</p> <p style="padding-left: 40px;">United States Department of Agriculture Survey Triangulation Station "SINKER" bears N. 87° 52' 19" W., 13.785 chs. dist., monumented with a standard brass tablet, 3 ins. diam., firmly cemented into a drill hole in a rock outcrop with top mkd. U.S. Department of Agriculture SINKER 1960 Forest Service and a triangle. Point is located at N end of small ridge that bears NE and SW.</p>		S 5		1/4	S 8	
	S 5						
1/4	S 8						
<p>40.216</p>	<p>N. 89° 48.2' W., beginning new measurement.</p> <p>The cor. of secs. 5, 6, 7, and 8, monumented with a limestone, 16 x 9 x 7 ins., (record, 18 x 9 x 6 ins.) set in the center of an old scattered mound of stone. No visible marks on the stone.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.</p> <div style="text-align: center;"> <p>T 13 N R 4 E</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">S 6</td> <td style="text-align: center;">S 5</td> </tr> <tr> <td style="text-align: center;">S 7</td> <td style="text-align: center;">S 8</td> </tr> </table> <p>1984</p> </div> <p>Deposit the stone alongside the aluminum post.</p>	S 6	S 5	S 7	S 8		
S 6	S 5						
S 7	S 8						

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 13 N., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
33.098	<p>from which</p> <p>A balsam, 16 ins. diam., bears S. 13<sup>0</sup> E., 25 lks. dist., mkd. T13N R4E S8 BT.</p> <p>Cor. is located on SE slope approximately 3 chs. E and 2 1/2 chs. S of ravine, course S. 70<sup>0</sup> W.</p> <hr/> <p>N. 85<sup>0</sup> 03.3' W., bet. secs. 6 and 7.</p> <p>Point for the 1/4 sec. cor. of secs. 6 and 7, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.</p> <p style="text-align: center;">T 13 N R 4 E S 6 1/4 S 7 1984</p> <p>Cor. is located on SW slope, at head of draw that drains S.</p>
38.601	<p>The closing cor. of secs. 6 and 7, on the W. bdy. of T. 13 N., R. 4 E., heretofore described.</p> <hr/> <p>From the cor. of secs. 5, 6, 7, and 8.</p> <p>N. 5<sup>0</sup> 04.0' E., bet. secs. 5 and 6.</p>
41.351	<p>Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.</p> <p style="text-align: center;">T 13 N R 4 E 1/4 S 6   S 5 1984</p>
88.181	<p>from which</p> <p>A pine, 15 ins. diam., bears West, 3 lks. dist., mkd. 1/4 S6 BT.</p> <p>Cor. is located on crown of ridge.</p> <p>The closing cor. of secs. 5 and 6, T. 13 N., R. 4 E., heretofore described.</p>

## Township 13 North, Range 4 East, Salt Lake Meridian, Utah

CHAINS

## General Description

Township 13 North, Range 4 East is situated about 30 miles northeast of Logan, Utah, and located within the Cache National Forest and Cache County.

The general terrain is mountainous with drainage to the southeast by way of Burnt Fork and Richardson Fork.

The elevation varies from 6886 at the southeast corner of section 1 to 8580 ft. at the Forest Service triangulation station "SINKER" on the south boundary of section 5.

Access is by way of Utah State Highway No. 89.

There are scattering stands of timber including aspen, fir and pine with undergrowth consisting of mostly sagebrush.

The principal use of the area is for water shed, timber harvest, livestock grazing and recreation area.

The major improvements noted was the development of Middle Sink's graded logging road.

The mean magnetic declination as projected from the U.S. Geological Survey magnetic declination map of 1980 is 15° E.



CERTIFICATE OF SURVEY

(I) ~~(We)~~ Frank C. Profazer, Jr. , HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 16th day of September, 1983, (I) ~~(We)~~ have dependently resurveyed the south boundary of T. 14 N., R. 4 E., the north two miles of the east boundary of T. 13 N., R. 3 E., the north mile of the east boundary, and the north tier of the subdivisional section lines of T. 13 N., R. 4 E.,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

October 23, 1985 (Date) Frank C Profazer Jr (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Washington, D.C.

The foregoing field notes of the dependent resurvey of the south boundary of T. 14 N., R. 4 E., the north two miles of the east boundary of T. 13 N., R. 3 E., the north mile of the east boundary and the north tier of the subdivisional section lines of T. 13 N., R. 4 E., of the Salt Lake Meridian, Utah

executed by Frank C. Profazer, Jr., Cadastral Surveyor having been critically examined and found correct, are hereby approved.

November 18, 1985 (Date) Glen B Hatch Chief Cadastral Surveyor for Utah

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

(Date) Chief Cadastral Surveyor for Utah

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
ORIGINAL

R 608

FIELD NOTES  
OF THE

117

DEPENDENT RESURVEY

OF A PORTION OF THE SOUTH BOUNDARY,

A PORTION OF THE EAST BOUNDARY,

AND

A PORTION OF THE SUBDIVISIONAL LINES,

WITH A SUBDIVISIONAL SURVEY

OF

SECTIONS 12 AND 33,

TOWNSHIP 3 SOUTH, RANGE 1 EAST

Of the Salt Lake Meridian,  
Utah  
In the State of \_\_\_\_\_

EXECUTED BY

Gary L. Kratz

Cadastral Surveyor

Under special instructions dated February 25, 19 83, approved February 25, 1983

\_\_\_\_\_, which provided for the surveys included under U.S. Survey/Group  
Number 627, and assignment instructions dated March 21, 19 83  
XXXXXXXXXX

Survey commenced April 8, 19 83

Survey completed June 13, 19 84

# INDEX DIAGRAM

Township 3 South, Range 1 East

6	5	4	3	2	1
7	8	9	10	11 9	12 5
				13	8
18	17	16	15	14 7	13 3
				12	7
19	20	21	22 12	23 6	24
				11	
30	29	28	27 10	26	25
		15	14		
31	32	33 13	34 9	35	36
		3	2		

Subdivision of Section 12 - Page 15  
 Subdivision of Section 33 - Page 19

## Township 3 South, Range 1 East, Salt Lake Meridian, Utah

## CHAINS

The following field notes are those of the dependent resurvey of a portion of the south boundary, a portion of the east boundary and a portion of the subdivisional lines, with a subdivisional survey of sections 12 and 33, T. 3 S., R. 1 E., Salt Lake Meridian, Utah.

History of Surveys

	<u>Surveyed by</u>		<u>Retr. or Resurveyed by</u>	
--	--------------------	--	-------------------------------	--

SOUTH BOUNDARY

Portion	F.H. Burr	1856		
Portion			A.D. Ferron	1891
Portion	A.J. Stewart, Jr.	1896		

EAST BOUNDARY

Portion	A.D. Ferron	1872		
Portion	A.J. Stewart, Jr.	1896		
Portion			A.J. Stewart, Jr.	1896

NORTH BOUNDARY

Portion	F.H. Burr	1856		
Portion			A.D. Ferron	1870
Portion	A.D. Ferron	1870		
Portion			A.D. Ferron	1891

WEST BOUNDARY

All	F.H. Burr	1856		
All			A.D. Ferron	1870
Portion			A.D. Ferron	1891

SUBDIVISION

Portion	F.H. Burr	1856		
Portion	A.D. Ferron	1871		
Portion			A.D. Ferron	1871
Portion	A.J. Stewart, Jr.	1896		
Portion			A.J. Stewart, Jr.	1896

A portion of the subdivision of section 12 was surveyed by A.D. Ferron in 1872.

The meanders of the Little Cottonwood Creek through section 12 were surveyed by Ferdinand Dickert in 1871.

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group 627, Utah, dated February 25, 1983.

The directions of lines of this survey refer to the true meridian and were determined from horizontal control data obtained from the National Geodetic Survey. The lines were carried forward by sustained angulation and supplemented by other observations of the sun and Polaris taken throughout the progress of the survey.

## Township 3 South, Range 1 East, Salt Lake Meridian, Utah

## CHAINS

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions, lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the corner of sections 2, 3, 34, and 35, on the south boundary of the township, as determined from a tie to National Geodetic Survey Control station "CHERRY", located in section 33, is"

Latitude  $40^{\circ} 30' 27.86''$  N. Longitude  $111^{\circ} 48' 53.73''$  W.

The mean magnetic declination, as projected from U.S. Geological Survey Magnetic Declination Map of 1980, is  $14 \frac{3}{4}^{\circ}$  E.

Dependent Resurvey of a Portion of the South Boundary,  
T. 3 S., R. 1 E., Salt Lake Meridian, Utah.

Beginning at the cor. of secs. 2, 3, 34, and 35, Tps. 3 and 4 S., R. 1 E., monumented with a granite stone, 36 x 12 x 8 ins., firmly set 24 ins. in the ground, plainly mkd. 2 notches on E edge and 4 notches on W edge.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 3 S R 1 E
S 34   S 35
S 3   S 2
T 4 S
1983

Deposit the mkd. stone alongside the aluminum post.

S.  $89^{\circ} 15'$  W., bet. secs. 3 and 34.

Over mountainous terrain, through dense undergrowth.

19.85 Point for the E 1/16 sec. cor. of secs. 3 and 34.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 1 E
S 34
E 1/16   S 3
T 4 S
1983

Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.

39.70 The 1/4 sec. cor. of secs. 3 and 34, monumented with a granite stone, 24 x 12 x 4 ins., firmly set 16 ins. in the ground, and in a collar of stone, mkd. 1/4 on N face.

Dependent Resurvey of a Portion of the South Boundary,  
T. 3 S., R. 1 E., Salt Lake Meridian, Utah.

## CHAINS

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 3 S R 1 E  
S 34  
1/4      S 3  
T 4 S  
1983

Bury the mkd. stone and set 2 steel fence posts alongside the aluminum post.

N. 89° 54' W., beginning new measurement.

Desc. over mountainous terrain through scattered brush.

39.00 The cor. of secs. 3, 4, 33, and 34, monumented with a concrete post, 7 ins. diam., firmly set, projecting 16 ins. above the ground, with a Salt Lake County brass cap mkd.

+  
196

This monument is accepted as a careful and faithful perpetuation of the position of the original corner.

Raise a supporting mound of stone, 3 ft. base, to top of concrete post.

N. 89° 49' W., bet. secs. 4 and 33.

Desc. over bench area, through scattered brush.

19.835 Point for the E 1/16 sec. cor. of secs. 4 and 33; not monumented.

39.67 The 1/4 sec. cor. of secs. 4 and 33, monumented with a concrete post, 7 ins. diam., firmly set, projecting 10 ins. above the ground, with a Salt Lake County brass cap mkd.

+  
SET 196

This monument is accepted as a careful and faithful perpetuation of the position of the original corner.

Cor. is located 2 lks. S of an irrigation ditch.

Dependent Resurvey of a Portion of the East Boundary,  
T. 3 S., R. 1 E., Salt Lake Meridian, Utah.

From the cor. of secs. 13, 18, 19, and 24, T. 3 S., Rs. 1 and 2 E., monumented with a scattered mound of stone. This is accepted as the best available evidence of the position of the original corner.

Dependent Resurvey of a Portion of the East Boundary,  
T. 3 S., R. 1 E., Salt Lake Meridian, Utah.

## CHAINS

At the corner point, in the center of the mound of stone.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.

T 3 S	
R 1 E	R 2 E
S 13	S 18
S 24	S 19
1983	

Cor. is located on steep N slope.

N. 0° 22' W., bet. secs. 13 and 18.

Over steep mountainous terrain, through heavy timber.

39.76

The 1/4 sec. cor. of secs. 13 and 18, monumented with a granite stone, 20 x 8 x 6 ins., firmly set 16 ins. in the ground, mkd. 1/ on W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.

T 3 S	
R 1 E	R 2 E
1/4	
S 13	S 18
1983	

Deposit the mkd. stone alongside the aluminum post.

Cor. is located on very steep spur, bears NW.

N. 0° 07' E., beginning new measurement.

20.29

Point for the N 1/16 sec. cor. of secs. 13 and 18.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 3 S	
R 1 E	R 2 E
N 1/16	
S 13	S 18
1983	

Cor. is located on N bank of Bells Canyon Creek.

40.58

The cor. of secs. 7, 12, 13, and 18, monumented with a granite stone, 20 x 13 x 8 ins., firmly set 15 ins. in the ground, with 2 notches on N edge and 4 notches on S edge, with an embedded mound of stone, W of cor.

Dependent Resurvey of a Portion of the East Boundary,  
T. 3 S., R. 1 E., Salt Lake Meridian, Utah.

## CHAINS

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap mkd.

T 3 S	
R 1 E	R 2 E
S 12	S 7
S 13	S 18
1983	

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

N. 0° 02' W., bet. secs. 7 and 12.

Desc. over steep mountainous terrain, through dense undergrowth.

20.28 The S 1/16 sec. cor. of secs. 7 and 12, monumented with an embedded mound of stone. This monument is accepted as the best available evidence of the original corner.

At the corner point, in the center of the mound of stone.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.

T 3 S	
R 1 E	R 2 E
S 1/16	
S 12	S 7
1983	

N. 0° 03' W., beginning new measurement.

4.86 Point for the S-N-S 1/256 sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner. Not monumented.

9.98 Point for the N-S 1/64 sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.


N-S	
1/64	
S 12	S 7
1983	

Cor. is located in a rockslide.

20.22 The 1/4 sec. cor. of secs. 7 and 12, monumented with a Salt Lake County brass cap, set in concrete, flush with the ground, mkd.

Dependent Resurvey of a Portion of the East Boundary,  
T. 3 S., R. 1 E., Salt Lake Meridian, Utah.

CHAINS




This monument is accepted as a careful and faithful perpetuation of the original corner.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 1 E., Salt Lake Meridian, Utah

From the cor. of secs. 23, 24, 25, and 26, monumented with granite stone, 12 x 6 x 4 ins., firmly set 8 ins. in the ground, mkd. 2 notches on E edge and 1 notch on S edge.

At the corner point


Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.



N. 0° 36' E., bet. secs. 23 and 24.


19.825 Point for the S 1/16 sec. cor. of secs. 23 and 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.



39.65 Point for the 1/4 sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.



59.475 Point for the N 1/16 sec. cor. of secs. 23 and 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS		
79.30	<p style="text-align: center;">T 3 S R 1 E N 1/16 S 23   S 24 1983</p> <p>The cor. of secs. 13, 14, 23, and 24, monumented with a granite stone, 18 x 10 x 9 ins., firmly set 12 ins. in the ground, and in a mound of stone, with 1 notch on E edge and 3 notches on S edge.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">T 3 S R 1 E S 14   S 13 S 23   S 24 1983</p> <p>Deposit the mkd. stone alongside the aluminum post.</p>	
40.24	<p>From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., heretofore described.</p> <p>N. 89° 25' W., bet. secs. 13 and 24.</p> <p>Over mountainous land, through dense timber and undergrowth.</p> <p>Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">T 3 S R 1 E S 13 1/4 S 24 1983</p>	
80.48	<p>The cor. of secs. 13, 14, 23, and 24.</p> <p>N. 0° 45' E., bet. secs. 13 and 14.</p> <p>Over mountainous terrain, through dense brush.</p> <p>Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>	
39.89		

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS	
79.78	<p style="text-align: center;">T 3 S R 1 E 1/4 S 14   S 13 1984</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <p>True point for the cor. of secs. 11, 12, 13, and 14, at proportionate distance, based on previous ties made by Salt Lake County; there is no remaining evidence of the original corner. The cor. falls in Bells Canyon Reservoir and is impossible to monument at this time.</p>
19.925	<p>From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., heretofore described.</p> <p>N. 89° 17' W., bet. secs. 12 and 13.</p> <p>Point for the E 1/16 sec. cor. of secs. 12 and 13.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p>
39.85	<p style="text-align: center;">T 3 S R 1 E S 12 E 1/16 S 13 1983</p> <p>The 1/4 sec. cor. of secs. 12 and 13, monumented with a quartzite, 18 x 10 x 6 ins., firmly set 14 ins. in the ground, dimly mkd. 1/4 on N face, with an embedded mound of stone to the N.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with aluminum cap mkd.</p>
19.695	<p style="text-align: center;">T 3 S R 1 E S 12 1/4 S 13 1983</p> <p>Bury the mkd. stone alongside the aluminum post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 89° 38' W., beginning new measurement.</p> <p>Point for the W 1/16 sec. cor. of secs. 12 and 13.</p> <p>Set an iron post, 8 ins. long, 1 in. diam., 2 ins. in a boulder, 8 x 6 x 5 ft., with brass cap mkd.</p>
	<p style="text-align: center;">T 3 S R 1 E S 12 W 1/16 S 13 1984</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 1 E., Salt Lake Meridian, Utah

<p>CHAINS 39.39</p>	<p>True point for the cor. of secs. 11, 12, 13, and 14.</p>
	<p>N. 0° 27' W., bet. secs. 11 and 12. Over mountainous terrain, through dense undergrowth.</p>
<p>3.75</p>	<p>Point selected for a witness point between secs. 11 and 12. Set an iron rebar, 18 ins. long, 1/2 in. diam., 30 ins. below the surface, directly over which I set an aluminum post, 30 ins. long, 2 1/2 ins. diam., flush with the surface, with an aluminum cap mkd.</p>
	<p style="text-align: center;">       WP        T 3 S R 1 E                 S 11   S 12                 1984     </p> <p>Point falls on the N. edge of an improved road on the Bell Canyon dam.</p>
<p>19.835</p>	<p>Point for the S 1/16 sec. cor. of secs. 11 and 12, not monumented.</p>
<p>39.67</p>	<p>The 1/4 sec. cor. of secs. 11 and 12, monumented by the Salt Lake County Surveyor's Office with a nail in a large boulder. This monument is accepted as a careful and faithful perpetuation of the position of the original corner. Not remonumented.</p>
	<p>From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., heretofore described. N. 1° 23' E., bet. secs. 34 and 35. Over mountainous land, through dense undergrowth.</p>
<p>40.49</p>	<p>Point for the 1/4 sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner. Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p>
	<p style="text-align: center;">       T 3 S R 1 E        1/4                 S 34   S 35                 1983     </p>
<p>60.735</p>	<p>Point for the N 1/16 sec. cor. of secs. 34 and 35. Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p>
	<p style="text-align: center;">       T 3 S R 1 E        N 1/16        S 34   S 35        1983     </p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS  
80.98

The cor. of secs. 26, 27, 34, and 35, monumented with a granite stone, 16 x 6 x 6 ins., firmly set 12 ins. in the ground, mkd. 2 notches on E edge and 1 notch on S edge, with an embedded mound of stone, W of cor.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap mkd.

T 3 S R 1 E
S 27   S 26
S 34   S 35
1983

Bury the mkd. stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

Cor. is located on SW slope.

---

N. 0° 46' W., bet. secs. 26 and 27.

Over mountainous land, through dense undergrowth.

41.72

The 1/4 sec. cor. of secs. 26 and 27, monumented with a quartzite stone, 18 x 9 x 6 ins., firmly set 12 ins. in the ground, mkd. 1/4 on W face, with a mound of stone, W of cor.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap mkd.

T 3 S R 1 E
1/4
S 27   S 26
1983

Bury the mkd. stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

Cor is located on SW slope.

---

N. 0° 27' E., beginning new measurement.

19.455

Point for the N 1/16 sec. cor. of secs. 26 and 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap mkd.

T 3 S R 1 E
N 1/16
S 27   S 26
1983

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS  
38.91

The cor. of secs. 22, 23, 26, and 27, monumented with a granite stone, 16 x 16 x 6 ins., firmly set 12 ins. in the ground, and in a collar of concrete, plainly mkd. 2 notches on E edge and 2 notches on S edge.

Beneath the mkd. stone is a Salt Lake County brass cap, firmly set in concrete 16 ins. below the surface, mkd.

SEC COR	
22	23
27	26
T 3 S R 1 E	

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, directly over the Salt Lake County brass cap, and in a mound of stone, 2 1/2 ft. base, to top of aluminum cap, mkd.

T 3 S R 1 E	
S 22	S 23
S 27	S 26
1983	

Bury the mkd. stone alongside the aluminum post.

From the cor. of secs. 23, 24, 25, and 26.

S. 89° 13' W., bet. secs. 23 and 26.

20.075 Point for the E 1/16 sec. cor. of secs. 23 and 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 3 S R 1 E	
S 23	
E 1/16	S 26
1983	

40.15 The 1/4 sec. cor. of secs. 23 and 26, monumented with a scattered mound of stone, from which an original bearing tree

A mahogany, 11 ins. diam., bears North, 14 lks. dist., mkd. S BT.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.

T 3 S R 1 E	
S 23	
1/4	S 26
1983	

S. 89° 28' W., beginning new measurement.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 3 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS  
39.39


The cor. of secs. 22, 23, 26, and 27.

N. 0° 04' W., bet. secs. 22 and 23.

Over rolling bench land, through scattered brush and developed land.

40.14

The 1/4 sec. cor. of secs. 22 and 23, monumented with a concrete post, 7 ins. diam., firmly set flush with the ground, with a Salt Lake County brass cap mkd.




This monument is accepted as a careful and faithful reestablishment of the position of the original corner.

Cor. falls in a 10 foot high fence, bears E and W.

N. 0° 05' W., beginning new measurement.

40.01

The the cor. of secs. 14, 15, 22, and 23, monumented with a Salt Lake County brass cap, firmly set 4 ins. below the surface in concrete, mkd.



This monument is accepted as a careful and faithful reestablishment of the position of the original corner.

Cor. falls in asphalt road (Pepperwood Drive), bears E and W.

From the cor. of secs. 13, 14, 23, and 24.


N. 89° 50' W., bet. secs. 14 and 23.

Over rolling bench land, through thick undergrowth.

20.14

Point for the E 1/16 sec. cor. of secs. 14 and 23.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap mkd.



Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W of cor.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 1 E., Salt Lake Meridian, Utah

<p>CHAINS 40.28</p>	<p>The 1/4 sec. cor. of secs. 14 and 23, monumented with a quartzite stone, 16 x 16 x 6 ins., above ground, mkd. with an X on top. This monument has been adopted by local private and county surveyors and is accepted as the best available evidence of the position of the original corner. Not remonumented.</p> <p>Cor. falls in bottom of a wash, bears E and W.</p> <p>S. 89° 45' W., beginning new measurement.</p>
<p>40.18</p>	<p>The cor. of secs. 14, 15, 22, and 23.</p> <hr/> <p>From the cor. of secs. 11, 12, 13, and 14.</p> <p>N. 89° 59' W., bet. secs. 11 and 14.</p>
<p>7.00</p>	<p>Point selected for the witness cor. to the cor. of secs. 11, 12, 13, and 14.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, over an X chiseled in solid rock, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.</p>
<p>40.38</p>	<div style="text-align: center;"> <p>W C T 3 S R 1 E S 11   S 12 S 14   S 13 1984</p> </div> <p>The 1/4 sec. cor. of secs. 11 and 14, monumented with a concrete post, 7 ins. diam., firmly set flush with the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p><math>\frac{11}{14}</math> 1/4 COR</p> </div> <p>Cor. is located alongside fence cor., with chain link fences extending S and W, and is accepted as a careful and faithful reestablishment of the position of the original corner.</p>
<p>20.25</p>	<p>From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., heretofore described.</p> <p>N. 0° 02' W., bet. secs. 33 and 34.</p> <p>Over rolling bench land, through scattered brush.</p> <p>Point for the S 1/16 sec. cor. of secs. 33 and 34.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 3 S R 1 E S 1/16 S 33   S 34 1983</p> </div> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS  
40.50

The 1/4 sec. cor. of secs. 33 and 34, monumented with a granite stone, 20 x 14 x 8 ins., firmly set 14 ins. in the ground, plainly mkd. 1/4 on W face, with a mound of stone W.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 3 S R 1 E  
1/4  
S 33 | S 34  
1983

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

From this cor., the National Geodetic Survey Control station "CHERRY", bears S. 31° 30' 20" W., 2.847 chs. dist.

N. 0° 18' E., beginning new measurement.

41.24

The cor. of secs. 27, 28, 33, and 34, monumented with a concrete post, 7 ins. diam., firmly set 2 ins. below the surface, with a Salt Lake County brass cap, mkd.

SEC COR  
28 | 27  
33 | 34  
T 3 S R 1 E  
1974

from which

A steel fence post, firmly set, bears S. 71° W., 15 1/2 lks. dist.

A wooden corner fence post, with fences extending NW and W., bears N. 86° W., 17 1/2 lks. dist.

This monument is accepted as a careful and faithful reestablishment of the position of the original corner.

Cor. is located near the edge of a gravelled road, bears NW-SE, 15 1/2 lks. W of the center of the road.

From the cor. of secs. 26, 27, 34, and 35.

N. 89° 44' W., bet. secs. 27 and 34.

Over steep mountainous land, through dense brush.

40.57

The 1/4 sec. cor. of secs. 27 and 34, monumented with a granite stone, 20 x 12 x 4 ins., firmly set 12 ins. in the ground, plainly mkd. 1/4 on N face, with a small mound of stone to the N.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 3 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS	
	<p style="text-align: center;">T 3 S R 1 E  <math>\frac{S 27}{S 34}</math>                      1/4 1983</p> <p>Deposit the mkd. stone alongside the aluminum post.                      Raise a mound of stone, 4 ft. base, 3 ft. high, W of cor.</p> <hr/> <p>N. 89° 48' W., beginning new measurement.</p>
19.935	<p>Point for the W 1/16 sec. cor. of secs. 27 and 34.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.</p>
39.87	<p style="text-align: center;">T 3 S R 1 E  <math>\frac{S 27}{S 34}</math>                      W 1/16 1983</p> <p>The cor. of secs. 27, 28, 33, and 34.</p>
39.88	<p>N. 89° 54' W., bet. secs. 28 and 33.</p> <p>Over bench land, through scattered brush and residential area.</p> <p>The 1/4 sec. cor. of secs. 28 and 33, monumented with a concrete post, 7 ins. diam., firmly set projecting 3 ins. above the ground, with Salt Lake County brass cap mkd.</p> <p style="text-align: center;">4 COR  <math>\frac{28}{33}</math>                      T 3 S R 1 E</p> <p>Cor. is located in a small horse pasture, and is accepted as a careful and faithful reestablishment of the position of the original corner.</p>
19.90	<p style="text-align: center;">Survey of the Subdivision of Section 12,                      T. 3 S., R. 1 E., Salt Lake Meridian, Utah</p> <hr/> <p>From the 1/4 sec. cor. of secs. 12 and 13.</p> <p>N. 0° 21' E., on the N-S center line of sec. 12.</p> <p>Point for the center S 1/16 sec. cor. of sec. 12.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.</p> <p style="text-align: center;">C  <math>\frac{S 1/16}{S 12}</math>                      C                      1983</p>

Survey of the Subdivision of Section 12,  
T. 3 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS	
24.875	Point for the center S-N-S 1/256 sec. cor. of sec. 12, at proportionate distance; there is no remaining evidence of the original corner. Not monumented.
29.85	The center NS 1/64 sec. cor. of sec. 12, monumented with a granite stone, 12 x 10 x 8 ins., firmly set 8 ins. in the ground, mkd. + on the top.
	At the corner point
	Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.
	S 12 C-N-S 1/64 1983
	Deposit the mkd. stone alongside the aluminum post.
	N. 0° 14' W., beginning new measurement.
9.65	The center 1/4 sec. cor. of sec. 12, monumented with a concrete post, 7 ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.
	CENTER SEC. COR. 12 <hr/> 12 T 3 S R 1 E 1975
	Cor. falls on edge of cut bank
	This point is accepted as a careful and faithful reestablishment of the position of the original corner.
	From the 1/4 sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp., heretofore described.
	S. 89° 17' W., on the E-W center line of sec. 12.
9.92	Point for the center E-E 1/64 sec. cor. of sec. 12, at proportionate distance; there is no remaining evidence of the original corner. Not monumented.
19.84	Point for the center E 1/16 sec. cor. of sec. 12, at proportionate distance; there is no remaining evidence of the original corner. Not monumented.
29 76	Point for the center W-E 1/64 sec. cor. of sec. 12, at proportionate distance; there is no remaining evidence of the original corner. Not monumented.
39.68	The center 1/4 sec. cor. of sec. 12.
	S. 89° 52' W., beginning new measurement.
19.92	Point for the center W 1/16 sec. cor. of sec. 12. Not monumented.
39.84	The 1/4 sec. cor. of secs. 11 and 12.

Survey of the Subdivision of Section 12,  
T. 3 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS		
	<p>From the E 1/16 sec. cor. of secs. 12 and 13.</p> <p>N. 0° 05' E., on the N-S center line of the SE 1/4 of sec. 12.</p>	
20.09	<p>Point for the SE 1/16 sec. cor. of sec. 12, at the intersection with the E-W center line of the SE 1/4.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.</p> <p style="text-align: center;">SE 1/16 S 12 1983</p>	
24.97	<p>Point for the center S-N-SE 1/256 sec. cor. of sec. 12, at proportionate distance; there is no remaining evidence of the original corner. Not monumented</p>	
29.98	<p>Point for the center N-SE 1/64 sec. cor. of sec. 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.</p> <p style="text-align: center;">S 12 C-N-SE 1/64 1983</p>	
40.00	<p>Point for the center E 1/16 sec. cor. of sec. 12.</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp., heretofore described.</p> <p>N. 89° 49' W., on the E-W center line of the SE 1/4 of sec. 12.</p>	
19.88	<p>The SE 1/16 sec. cor. of sec. 12.</p>	
39.71	<p>The center S 1/16 sec. cor. of sec. 12.</p> <hr/> <p>From the N-S 1/64 sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp., heretofore described.</p> <p>S. 89° 55' W., on the E-W center line of the NE 1/4 of the SE 1/4 of sec. 12.</p>	
9.925	<p>Point for the NE-SE 1/64 sec. cor. of sec. 12, at proportionate distance; there is no remaining evidence of the original corner. Not monumented.</p>	
19.86	<p>The center N-SE 1/64 sec. cor. of sec. 12.</p> <hr/> <p>From the point for the NE-SE 1/64 sec. cor. of sec. 12.</p> <p>N. 0° 01' W., on the N-S center line of the NE 1/4 of the SE 1/4 of sec. 12.</p>	

Survey of the Subdivision of Section 12,  
T. 3 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS	
10.13	Point for the center E-E 1/64 sec. cor. of sec. 12.
	<p>From the point for the S-N-S 1/256 sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp., heretofore described.</p> <p>N. 89° 46' W., on the N. bdy. of Lot 4 of sec. 12.</p>
19.87	Point for the center S-N-SE 1/256 sec. cor. of sec. 12.
	<p>From the center N-SE 1/64 sec. cor. of sec. 12.</p> <p>N. 89° 39' W., on the E-W center line of the NW 1/4 of the SE 1/4 of sec. 12.</p>
9.89	Point for the NW-SE 1/64 sec. cor. of sec. 12, at proportionate distance; there is no remaining evidence of the original corner. Not monumented.
19.78	The center N-S 1/64 sec. cor. of sec. 12.
	<p>From the point for the NW-SE 1/64 sec. cor. of sec. 12.</p> <p>N. 0° 05' W., on the N-S center line of the NW 1/4 of the SE 1/4 of sec. 12.</p>
9.835	The center W-E 1/64 sec. cor. of sec. 12.
	<p>From the point for the center S-N-SE 1/256 sec. cor. of sec. 12.</p> <p>N. 89° 33' W., on the N. bdy. of Lot 3 of sec. 12.</p>
19.805	Point for the center S-N-S 1/256 sec. cor. of sec. 12.
	<p>From the W 1/16 sec. cor. of secs. 12 and 13.</p> <p>N. 0° 08' W., on the N-S center line of the SW 1/4 of sec. 12.</p>
19.87	Point for the SW 1/16 sec. cor. of sec. 12, at intersection with the E-W center line of the SW 1/4.
	<p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">SW 1/16 S 12 1983</p>
39.59	Point for the center W 1/16 sec. cor. of sec. 12.
	<p>From the center S 1/16 sec. cor. of sec. 12.</p> <p>S. 89° 32' W., on the E-W center line of the SW 1/4 of sec. 12.</p>
19.855	The SW 1/16 sec. cor. of sec. 12.

Survey of the Subdivision of Section 12,  
T. 3 S., R. 1 E., Salt Lake Meridian, Utah

CHAINS	
39.66	Point for the S 1/16 sec. cor. of secs. 11 and 12.
<p>Survey of the Subdivision of Section 33, T. 3 S., R. 1 E., Salt Lake Meridian, Utah</p>	
<p>From the 1/4 sec. cor. of secs. 4 and 33, on the S. bdy. of the Tp., heretofore described.</p>	
<p>N. 0° 01' W., on the N-S center line of sec. 33.</p>	
20.39	Point for the center S 1/16 sec. cor. of sec. 33. Not monumented.
40.78	Point for the center 1/4 sec. cor. of sec. 33, at intersection with the E-W center line.
<p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>	
<p>T 3 S R 1 E C 1/4 S 33 1983</p>	
<p>Set a wooden post alongside the aluminum post.</p>	
81.69	The 1/4 sec. cor. of secs. 28 and 33.
<p>From the 1/4 sec. cor. of secs. 33 and 34.</p>	
<p>N. 89° 25' W., on the E-W center line of sec. 33.</p>	
19.83	The center E 1/16 sec. cor. of sec. 33, monumented with an iron rebar, 1/2 ins. diam., firmly set in concrete, projecting 2 ins. above the ground. Not remonumented.
<p>This position is accepted as a careful and faithful determination of the position of the corner.</p>	
39.66	The center 1/4 sec. cor. of sec. 33.
79.66	The 1/4 sec. cor. of secs. 32 and 33, monumented with a concrete post, 7 ins. diam., firmly set 8 ins. below the surface, with a Salt Lake County brass cap mkd.
<p>1/4 COR 32 ——— 33 T 3 S R 1 E 196</p>	
<p>Cor. falls in the center of a blacktop road (Thirteenth East Street), 45 lks. wide, bears N and S and is accepted as a careful and faithful reestablishment of the position of the original corner.</p>	
<p>From the point for the E 1/16 sec. cor. of secs. 4 and 33, on the S. bdy. of the Tp., heretofore described.</p>	

Survey of the Subdivision of Section 33,  
T. 3 S., R. 1 E. Salt Lake Meridian, Utah

CHAINS		
	<p>N. 0° 02' W., on the N-S center line of the SE 1/4 of sec. 33.</p>	
20.32	<p>Point for the SE 1/16 sec. cor. of sec. 33, at intersection with the E-W center line of the SE 1/4.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">SE 1/16 S 33 1983</p>	
40.64	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor. The center E 1/16 sec. cor. of sec. 33.</p>	
19.835	<p>From the S 1/16 sec. cor. of secs. 33 and 34.</p> <p>N. 89° 37' W., on the E-W center line of the SE 1/4 of sec. 33.</p>	
39.67	<p>The SE 1/16 sec. cor. of sec. 33.</p> <p>Point for the center S 1/16 sec. cor. of sec. 33.</p>	
	<p style="text-align: center;">General Description</p> <p>The area surveyed lies along the west slope of the Wasatch Mountains east of Draper, Utah, between Little Cottonwood and Corner Canyons. The elevation varies from 4500 to 8000 ft. above sea level, with much of the terrain being steep and rugged. The soil is generally shallow and rocky, supporting mainly sagebrush, oakbrush, scrub maples, juniper and mahogany. There are a few stands of fir and pine on the north slopes. Runoff is drained westerly into the Valley. Numerous homes and developments are situated along the bench areas in sections 12, 23, and 33.</p>	



CERTIFICATE OF SURVEY

(I) ~~(X)~~ Gary L. Kratz, Cadastral Surveyor, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 25th day of February, 1983, (I) ~~(X)~~ have dependently resurveyed a portion of the south and east boundaries, a portion of the subdivisional lines, and surveyed the subdivisions of sections 12 and 33, T. 3 S., R. 1 E.,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

November 1, 1985 (Date)

Gary L. Kratz (Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT

The foregoing field notes of the dependent resurvey of a portion of the south and east boundaries, a portion of the subdivisional lines, and the subdivisional survey of sections 12 and 33, T. 3 S., R. 1 E., Salt Lake Meridian, Utah

executed by Gary L. Kratz, Cadastral Surveyor having been critically examined and found correct, are hereby approved.

November 26, 1985 (Date)

Glen B Hatch Chief Cadastral Surveyor for Utah

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

(Date)

Chief Cadastral Surveyor for Utah

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

R 608

ORIGINAL  
FIELD NOTES

141

OF THE

RETRACEMENT OF THE UTAH AND IDAHO STATE BOUNDARY LINE

BETWEEN THE 78TH and 80TH MILE POSTS,

THE DEPENDENT RESURVEY

OF A

PORTION OF THE SOUTH BOUNDARY,

A PORTION OF THE WEST BOUNDARY,

AND A

PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SURVEY OF THE SUBDIVISION OF SECTION 31,

TOWNSHIP 15 NORTH, RANGE 6 WEST

Of the Salt Lake Meridian,

In the State of Utah

EXECUTED BY

Richard A. Zaninovich Supervisory Cadastral Surveyor

Under special instructions dated October 19, 1983, approved October 25, 1983

\_\_\_\_\_, which provided for the surveys included under ~~U.S. Survey~~/Group  
Number 641, and assignment instructions dated October 26, 1983.

Survey commenced November 2, 1983

Survey completed August 9, 1984

# INDEX DIAGRAM

Township 15 North, Range 6 West,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30 8	29 8	28	27	26	25
5 31 3	6 32 3	33	34	35	36

Utah-Idaho State Line Between M.P. 78 and 80  
 Subdivision of Section 30

- Page 1  
 - Page 8

## Township 15 North, Range 6 West, Salt Lake Meridian, Utah

## CHAINS

The following field notes are those of the retracement of the Utah and Idaho state boundary line between the 78th and 80th mile posts, the dependent resurvey of a portion of the south boundary, a portion of the west boundary, and a portion of the subdivisional lines; and the survey of the subdivision of section 31, of Township 15 North, Range 6 West, Salt Lake Meridian, Utah.

## History of Earlier Surveys

Surveyed byRetr. or Resurveyed bySTATE BOUNDARY

All	D.G. Major	1871	
Portion			Ropp and Abbey 1913

SOUTH BOUNDARY

Portion	J. Troskowlawski	1856	
Portion	E.W. Koeber	1887	
Portion			A.P. Hanson 1896

WEST BOUNDARY

All	E.W. Koeber	1887	
All			A.P. Hanson 1896

SUBDIVISION

All	A.P. Hanson	1896	
-----	-------------	------	--

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 641, Utah, dated October 19, 1983.

The directions of the lines of this survey refer to the true meridian as determined by hour angle observations of Polaris. The lines were carried forward by sustained angulation.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the corner of sections 4, 5, 32, and 33 on the south boundary of the township, as determined by ties made to U.S. Geological Survey triangulation stations "WARD" and "SEC COR CC 25E/16S/33E", is as follows:

Latitude 41° 59' 3.76" N. Longitude 112° 33' 27.13" W.

The mean magnetic declination as projected from the U.S. Geological Survey "Magnetic Declination Map of 1980" is 15 1/2° E.

Retracement of the Utah and Idaho State Boundary Line,  
Between the 78th and 80th Mile Posts

Retracement of the Utah and Idaho State Boundary Line,  
Between the 78th and 80th Mile Posts

## CHAINS

Retracement of the Survey Executed by  
D.G. Major in 1871,  
and the Retracement Executed by Ropp and Abbey in 1913

Beginning at the 78th mile post on the Utah and Idaho  
State Boundary monumented with an iron post, 3 ins.  
diam., projecting 10 ins. above the ground, with brass  
cap mkd. as described in the official record of the 1913  
retracement of T. 16 S., R. 33 E., Boise Meridian, Idaho.

from which

The closing cor. of T. 16 S., Rs. 33 and 34 E.,  
Boise Meridian, Idaho, identical with U.S.  
Geological Survey triangulation station "SEC COR CC  
25E/16S/33E", monumented with an iron post, 3 ins.  
diam., projecting 14 ins. above the ground, with  
brass cap, mkd. as described in the official record  
of the 1913 retracement, bears N. 89° 42.3' E.,  
100.27 chs. dist.

Cor. falls in a fence line, bears E. and W.

S. 89° 45' W., on the 79th mile, along the Utah and Idaho  
State Boundary.

65.25 Point for the closing cor. of secs. 29 and 30,  
hereinafter described.

81.20 Point for the 79th mile post at proportionate distance;  
there is no remaining evidence of the position of the  
original cor.

Not monumented.

Point falls 1 lk. N. of a fence, bears E. and W.

S. 89° 18' W., on the 80th mile, along the Utah and Idaho  
State Boundary.

29.80 Point for the closing cor. of T. 15 N., Rs. 6 and 7 W.,  
hereinafter described.

80.25 The 80th mile post, monumented with an iron post, 2 1/2  
ins. diam., firmly set in a mound of stone built on top  
of a limestone boulder, 5 x 5 x 4 ft. above the ground,  
with brass cap, mkd. as described in the official record  
of the retracement of the Utah and Idaho State Boundary  
executed by Tuft and Cazier in 1959.

from which

A juniper, 8 ins. diam., bears N. 51° E., 16 1/2  
lks. dist., mkd. I 80M BT.

A juniper, 6 ins. diam., brs. S. 73 1/4° E., 8 lks.  
dist., mkd. U 80M BT.

Alongside the iron post is set a squared wood post, 5  
ins. diam., scribed U I 80M 42L.

Dependent Resurvey of a Portion of the South Boundary  
T. 15 N., R. 6 W., SLM, Utah

Dependent Resurvey of a Portion of the South Boundary  
T. 15 N., R. 6 W., Salt Lake Meridian, Utah

CHAINS

Reestablishment of the Survey Executed by  
E.W. Koeber in 1887

From the point for the cor. of secs. 4, 5, 32, and 33,  
on the S. bdy. of the Tp., determined latitudinally at  
the centerline of a fenced lane projecting E. and  
longitudinally at the midpoint of a break in a N. and S.  
fence.

At the corner point

Set an iron post, 30 ins. long, 2 1/2 ins. diam. 22  
ins. in the ground, with brass cap mkd.

T15N		R6W	
S 32		S 33	
S 5		S 4	

T14N  
1984

S. 86° 53' W., bet. secs. 5 and 32.

40.68 Point for the 1/4 sec. cor. of secs. 5 and 32, at  
proportionate distance; there is no remaining evidence  
of the original cor.

Not monumented.

81.36 Point for the cor. of secs. 31 and 32 only at propor-  
tionate distance; there is no remaining evidence of the  
original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12  
ins. in the ground to bedrock, and in a mound of stone,  
3 ft. base to top of aluminum cap, mkd.

T15N		R6W	
S 31		S 32	

T14N  
1984

Reestablishment of the Survey Executed by  
E.W. Koeber in 1887 and the Resurvey Executed by  
A.P. Hanson in 1896

S. 80° 48' W., on the S. bdy. of sec. 31.

20.58 Point for the E. 1/16 sec. cor. of sec. 31 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14  
ins. below the surface of the ground in a cultivated  
field, with cap mkd.

E 1/16    S 31

1984

Dependent Resurvey of a Portion of the South Boundary  
T. 15 N., R. 6 W., Salt Lake Meridian, Utah

## CHAINS

41.16

Point for the 1/4 sec. cor. of sec. 31 only, at proportionate distance; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to be bedrock, and in a mound of stone, 3 ft. base to top of aluminum cap, mkd.

T15N R6W

1/4 S 31

T14N

1984

49.58

Point for the cor. of Tps. 14 and 15 N., Rs. 6 and 7 W., determined latitudinally at proportionate dist. and longitudinally at record departure from the cor. of secs. 2, 3, 34, and 35, Tps. 14 and 15 N., R. 7 W.; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T15N

R7W R6W

S 36	S 31
S 1	S 6

T14N

1984

From this cor., the cor. of secs. 2, 3, 34, and 35, Tps. 14 and 15 N., R. 7 W., bears N. 88° 47.4' W., 159.88 chs. dist., monumented with a sandstone, 16 x 8 x 6 ins. mkd. with 2 notches on the E. and 4 notches on the W. edges, firmly set in a collar of stone.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap mkd.

T15N R7W

S 34	S 35
S 3	S 2

T14N

1984

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone W., of cor.

From the cor. of Tps. 14 and 15 N., Rs. 6 and 7 W., the 1/4 sec. cor. of secs. 7 and 12, T. 14 N., Rs. 6 and 7 W., bears S. 2° 04.8' E., 121.25 chs. dist., monumented with a sandstone, 10 x 8 x 6 ins., mkd. 40 CHS POINT; this is accepted as the best available evidence of the position of the original cor.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap mkd.

Dependent Resurvey of a Portion of the South Boundary  
T. 15 N., R. 6 W., Salt Lake Meridian, Utah

CHAINS

T14N  
R7W R6W  
1/4  
S 12 | S 7  
1984

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, W. of cor.

from which

U.S. Geological Survey triangulation station  
"WARD" bears S. 1° 34.3' W., 287.52 chs. dist.

These control lines were fully retraced and careful search was made for evidence of intervening corners, none of which was recovered.

Dependent Resurvey of a Portion of the West Boundary,  
T. 15 N., R. 6 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by  
E.W. Koeber in 1887 and the Resurvey Executed by  
A.P. Hanson in 1896

From the cor. of Tps. 14 and 15 N., Rs. 6 and 7 W.,  
hereinbefore described.

N. 1° 11' E., bet. secs. 31 and 36.

30.095 Point for the S. 1/16 sec. cor. of sec. 31.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22  
ins. in the ground, and in a collar of stone, with  
aluminum cap mkd.

| S 1/16  
| S 31  
1984

40.40 Point for the 1/4 sec. cor. of sec. 36 only, at  
proportionate distance based on the record of the 1887  
survey; there is no remaining evidence of the original  
cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22  
ins. in the ground, with aluminum cap mkd.

T 15 N  
R 7 W | R 6 W  
1/4 S 36 |  
1984

Raise a mound of stone, W. of cor.

52.885 Point for the 1/4 sec. cor. of sec. 31 only, at  
proportionate distance based on the record of the 1896  
resurvey; there is no remaining evidence of the original  
cor.

Dependent Resurvey of a Portion of the West Boundary,  
T. 15. N., R. 6 W., Salt Lake Meridian, Utah

## CHAINS

Set an aluminum post 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap mkd.

```

      T 15 N
    R 7 W | R 6 W
          |
          | 1/4 S 31
          |
          | 1984
  
```

Raise a mound of stone E. of cor.

80.80

Point for the cor. of secs. 25 and 36 only, at proportionate distance based on the record of the 1887 survey; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins diam., over a cross (X) chiseled in solid limestone, and in a mound of stone 6 ft. base, to top of aluminum cap, mkd.

```

      T 15 N
    R 7 W | R 6 W
      S 25 |
          | S 31
      S 36 |
          |
          | 1984
  
```

98.465

Point for the closing cor. of secs. 30 and 31; hereinafter described.

101.70

Intersect the Utah and Idaho State Boundary line at the point for the closing cor. of secs. 25 and 30, T. 15 N., Rs. 6 and 7 W., at proportionate distance based on the record of the 1887 survey; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap mkd.

```

      S 25 | S 30
    R 7 W | R 6 W
          |
          | T 15 N
          |
          | CC
          |
          | 1984
  
```

Raise a mound of stone, S. of cor.

From this cor. the 80th mile post on the Utah and Idaho State Boundary line, hereinbefore described, bears S. 89° 18' W., 50.45 chs. dist.

Dependent Resurvey of a Portion of the  
Subdivisional Lines, T. 15 N., R. 6 W., SLM, Utah

Reestablishment of the Survey Executed by  
A.P. Hanson in 1896

From the cor. of secs. 31 and 32 only on the S. bdy. of the Tp., hereinbefore described.

Dependent Resurvey of a Portion of the  
Subdivisional Lines, T. 15 N., R. 6 W., S.L.M., Utah

## CHAINS

N. 0° 29' W., bet. secs. 31 and 32.

22.85

Point for the S. 1/16 sec. cor. of secs. 31 and 32.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap mkd.

S 1/16  
S 31 | S 32  
1984

45.70

Point for the 1/4 sec. cor. of secs. 31 and 32 at proportionate distance; there is no remaining evidence of the original cor.

Set an aluminum post 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top of aluminum cap, mkd.

T 15 N R 6 W  
1/4  
S 31 | S 32  
1984

91.40

Point for the cor. of secs. 29, 30, 31, and 32 at proportionate distance; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top of aluminum cap, mkd.

T 15 N R 6 W  
S 30 | S 29  
S 31 | S 32  
1984

From this cor. the cor. of secs. 25, 30, 31, and 36, T. 15 N., Rs. 5 and 6 W., bears N. 89° 26.8' E., 404.97 chs. dist., monumented with a sandstone, 20 x 8 x 6 ins., mkd. with 5 notches on the N. and 1 notch on the S. edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap mkd.

T 15 N  
R 6 W | R 5 W  
S 25 | S 30  
S 36 | S 31  
1984

Raise a mound of stone W. of cor.

Cor. falls in an abandoned fence line, brs. N. and S.

Dependent Resurvey of a Portion of the  
Subdivisional Lines, T. 15 N., R. 6 W., SLM, Utah

## CHAINS

This control line was fully retraced and careful search was made for evidence of intervening corners, none of which was recovered.

S. 88° 55' W., bet. secs. 30 and 31.

40.46

Point for the 1/4 sec. cor. of secs. 30 and 31 at proportionate distance; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap mkd.

```

T 15 N R 6 W
  S 30
  1/4
  S 31
  1984

```

Raise a mound of stone, N. of cor.

46.14

Intersect the W. bdy. of the Tp. at the point for the closing cor. of secs. 30 and 31 at proportionate distance based on the record of the 1896 resurvey; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap mkd.

```

      T 15 N
R 7 W | R 6 W
      S 25 | S 30
      |-----| CC
      S 31
      1984

```

Raise a mound of stone, E. of cor.

From the cor. of secs. 29, 30, 31, and 32.

N. 6° 33' W., bet. secs. 29 and 30.

2.82

Intersect the Utah and Idaho State Boundary line at the point for the closing cor. of secs. 29 and 30 at proportionate distance; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long., 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap mkd.

```

  S 30 | S 29
T 15 N | R 6 W
      |-----|
      CC
      1984




```

Raise a mound of stone S. of cor.

From this cor. the 78TH mile post on the Utah and Idaho State Boundary Line, hereinbefore described, bears N. 89° 45' E., 65.25 chs. dist.

Survey of the Subdivision of Section 31,  
T. 15 N., R. 6 W., SLM, Utah

Survey of the Subdivision of Section 31,  
T. 15 N., R. 6 W., Salt Lake Meridian, Utah

CHAINS	
27.74	<p>From the 1/4 sec. cor. of sec. 31 only, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0° 21' W., on the N. and S. centerline of sec. 31.</p> <p>Point for the center S. 1/16 sec. cor of sec. 31.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;">  </div>
51.64	<p>Cor. falls in a cultivated field. Set a wood post 6 ft. long, 6 ins. diam. alongside aluminum post.</p> <p>Point for the center 1/4 sec. cor. of sec. 31, at intersection with the E. and W. centerline of sec. 31.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top of aluminum cap, mkd.</p> <div style="text-align: center;">  </div>
97.21	<p>The 1/4 sec. cor. of secs. 30 and 31.</p>
20.28	<p>From the 1/4 sec. cor. of secs. 31 and 32.</p> <p>S. 89° 06' W., on the E. and W. centerline of sec. 31.</p> <p>Point for the center E. 1/16 sec. cor. of sec. 31.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;">  </div>
40.56	<p>Raise a mound of stone, N. of cor.</p> <p>The center 1/4 sec. cor. of sec. 31.</p>
47.47	<p>The 1/4 sec. cor. of sec. 31 only, on the W. bdy. of the Tp., hereinbefore described.</p>
	<p>From the E. 1/16 sec. cor. of sec. 31 only on the S. bdy. of the Tp., hereinbefore described.</p>

Survey of the Subdivision of Section 31,  
T. 15 N., R. 6 W., Salt Lake Meridian, Utah

CHAINS	
25.29	<p>N. 0° 25' W., on the N. and S. centerline of the SE. 1/4 of sec. 31.</p> <p>Point for the SE. 1/16 sec. cor. of sec. 31 at intersection with the E. and W. centerline of the SE. 1/4.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">SE 1/16      S 31</p> <p style="text-align: center;">1984</p> <p>Raise a mound of stone, W. of cor.</p>
48.66	<p>The center E. 1/16 sec. cor. of sec. 31.</p> <hr/> <p>From the S. 1/16 sec. cor. of secs. 31 and 32.</p> <p>S. 87° 37' W., on the E. and W. centerline of the SE. 1/4 of sec. 31.</p>
20.32	<p>The SE. 1/16 sec. cor. of sec. 31.</p>
40.64	<p>The center S. 1/16 sec. cor. of sec. 31.</p> <hr/> <p>From the center S 1/16 sec. cor. of sec. 31.</p>
7.59	<p>N. 82° 26' W., on the E. and W. centerline of the SW 1/4 of sec. 31.</p> <p>The S 1/16 sec. cor. of sec. 31 only, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The area surveyed and resurveyed in T. 15 N. R. 6 W., is located approximately 8 miles ENE of the town of Snowville, Utah. The terrain consists of high rolling hills vegetated with sage and scattered juniper. There are cultivated fields in the basins between ridges. General drainage is to the south.</p>



CERTIFICATE OF SURVEY

(I) ~~(WEX)~~ Richard A. Zaninovich, Supervisory Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 19th day of October, 1983, (I) ~~(WEX)~~ have retraced the Utah and Idaho State boundary line between the 78th and 80th mile posts; dependently resurveyed a portion of the south and west boundaries, and a portion of the subdivisional lines, and surveyed the subdivision of section 31 in T. 15 N., R. 6 W.,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), ~~(US)~~ and under (my) ~~(WEX)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

November 6, 1985  
(Date)

*[Signature]*  
\_\_\_\_\_  
(Cadastral Surveyor)  
Supervisory

\_\_\_\_\_  
(Date)

\_\_\_\_\_  
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Washington, D.C.

The foregoing field notes of the retracement of the Utah and Idaho State boundary line between the 78th and 80th mile posts; the dependent resurvey of a portion of the south and west boundaries, and a portion of the subdivisional lines, and the survey of the subdivision of section 31 in T. 15 N., R. 6 W., Salt Lake Meridian, Utah

executed by Richard A. Zaninovich, Supervisory Cadastral Surveyor having been critically examined and found correct, are hereby approved.

November 20, 1985  
(Date)

*[Signature]*  
\_\_\_\_\_  
XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX  
Chief Cadastral Surveyor for Utah

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in \_\_\_\_\_ is a true copy of the original field notes.

\_\_\_\_\_  
(Date)

~~XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX~~  
\_\_\_\_\_  
Chief Cadastral Surveyor for Utah

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

R 608

ORIGINAL

155

FIELD NOTES  
OF THE

DEPENDENT RESURVEY

OF A PORTION OF THE WEST BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES,

AND

A SUBDIVISIONAL SURVEY

OF

SECTION 19,

TOWNSHIP 30 SOUTH, RANGE 1 WEST

Of the Salt Lake Meridian,

In the State of Utah

EXECUTED BY

Gail E. Reynolds

Cadastral Surveyor

Under special instructions dated September 18, 19 84, approved September 18, 1984.

\_\_\_\_\_, which provided for the surveys included under U.S. Survey Group  
Number 661, and assignment instructions dated September 18, 19 84.

Survey commenced September 24, 19 84

Survey completed October 18, 19 84

UNITED STATES DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
FIELD NOTES

# INDEX DIAGRAM

Township 30 South, Range 1 West

	6	5	4	3	2	1
	7	8	9	10	11	12
5	13	14	15	16	17	18
	19	20	21	22	23	24
2	25	26	27	28	29	30
	31	32	33	34	35	36

Subdivision of Section 19 - Page 5

## Township 30 South, Range 1 West, Salt Lake Meridian, Utah

## CHAINS

The following field notes are those of a dependent resurvey of a portion of the west boundary, a portion of the subdivisional lines and a subdivisional survey of section 19 of Township 30 South, Range 1 West, Salt Lake Meridian, Utah.

History of Surveys

	<u>Surveyed by</u>	<u>Retr. or Resurveyed by</u>
--	--------------------	-------------------------------

## WEST BOUNDARY

N. 2 1/2 mi.	T.C. Bailey	1874	
S. 3 1/2 mi.	Breckon and McCarty	1897	
All		G.E. Rigby	1922

## SUBDIVISION

All	G.F. Rigby	1922
-----	------------	------

The surveys were executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group 661, Utah, dated September 18, 1984.

The direction of the lines of this survey were determined by reference to true meridians established on line by direct observations on Polaris. The lines were carried forward by sustained angulations, being supplemented by other observations on Polaris taken throughout the progress of the survey.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions, lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the southwest corner of section 19, as determined from a tie made to U.S. Geological Survey triangulation station "NICKS POINT", 1969, located in section 21, is as follows:.

Latitude 38° 10' 48.888" N.  
Longitude 111° 57' 01.694" W

The mean magnetic declination as projected from the U.S. Geological Survey Magnetic Declination Map of 1980 is 13 3/4° E.

---

Dependent Resurvey of a Portion of the West Boundary,  
T. 30 S., R. 1 W., Salt Lake Meridian, Utah

---

(Reestablishment of the Survey Executed by  
Breckon and McCarty in 1897 and the  
Resurvey Executed by G.F. Rigby in 1922)

---

Dependent Resurvey of a Portion of the West Boundary,  
T. 30 S., R. 1 W., Salt Lake Meridian, Utah

## CHAINS

Beginning at the 1897 cor. of secs. 19, 24, 25, and 30, which was made an angle point in the 1922 resurvey, monumented with a trachyte stone, 16 x 12 x 6 ins., (record, 16 x 10 x 8 ins.), firmly set 10 ins. in the ground, and plainly mkd. 4 notches on N and 2 notches on S edges, with old bearing trees dead and on the ground.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

A P  
T 30 S  
R 2 W | R 1 W  
S 25 | S 30

1984

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 4 ft. base, 2 ft. high, W of cor.

Cor. is located on NW slope in pinon and juniper growth.

N. 0° 03.3' W., along the W. bdy. of sec. 30.

Over broken mountainous land, through sagebrush, shadscale, pinon, and juniper growth.

- 29.533 The closing cor. of secs. 19 and 30, monumented with an iron post, 2 ins. diam., extending 6 ins. above the ground, and in a collar of stone, with brass cap, mkd. as described in the official record of the 1922 resurvey. The elevation of this cor. is 7280 ft.

from which

U.S.G.S. triangulation station "NICKS POINT 1969" bears N. 79° 32' 15.6" E., 231.261 chs. dist., monumented with a standard tablet cap, 3 1/2 ins. diam., firmly cemented into a drill hole in solid rock outcrop with top mkd. NICKS POINT 1969, and a triangle.

Thence along the W. bdy. of sec. 19 with continuous measurement.

- 39.529 Point for the S-S 1/64 sec. cor. of sec. 19 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 30 S  
R 2 W | R 1 W  
|  
S-S  
| 1/64  
| S 19  
1984

Raise a mound of stone, 3 ft. base, 2 ft. high, E of cor.

Cor. is located on N slope in sagebrush.

Dependent Resurvey of a Portion of the West Boundary,  
T. 30 S., R. 1 W., Salt Lake Meridian, Utah

CHAINS  
39.834

The 1897 1/4 sec. cor. of secs. 19 and 24, which was made an angle point in the 1922 resurvey, monumented with a trachyte stone, 14 x 12 x 6 ins., (record, 16 x 10 x 8 ins.), firmly set 8 ins. in the ground and dimly mkd.

At the corner point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with iron cap mkd.

A P  
T 30 S  
R 2 W R 1 W  
S 24 | S 19  
1984

Deposit the mkd. stone alongside the iron post.

Raise a mound of stone, 3 ft. base, 2 ft. high W of cor.

Cor. is located on N slope in sagebrush and scrub pinon growth.

\_\_\_\_\_

N. 0° 03.3' W., beginning new measurement.

9.691 Point for the S 1/16 sec. cor. of sec. 19 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 30 S  
R 2 W R 1 W  
| S 1/16  
| S 19

1984

Raise a mound of stone, 3 ft. base, 2 ft. high, S of cor.

Cor. is located on SW slope in sagebrush.

29.683 The 1/4 sec. cor. of sec. 19 only, monumented with an iron post, 1 in. diam., extending 8 ins. out of the ground, with brass cap, mkd. as described in the official record of the 1922 resurvey.

\_\_\_\_\_

N. 0° 03.3' W., beginning new measurement.

Over rolling mountain land, through shadscale, sagebrush and scattered pinon and juniper growth.

10.494 The 1897 cor. of secs. 13, 18, 19, and 24, made an angle point in the 1922 resurvey, monumented with a trachyte stone, 20 x 12 x 8 ins. (record, 16 x 10 x 8 ins.), firmly set 10 ins. in the ground and plainly mkd. 3 notches on N and S edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

Dependent Resurvey of a Portion of the West Boundary,  
T. 30 S., R. 1 W., Salt Lake Meridian, Utah

CHAINS	
	<p style="text-align: center;">A P T 30 S R 2 W R 1 W S 24   S 19 1984</p> <p>Deposit the mkd. stone alongside the aluminum post.</p> <p>Cor. is located on gentle SW slope in scattered pinon and juniper growth.</p>
5.114	<p>N. 0° 42.0' W., on the W. bdy. of sec. 19.</p> <p>Over rolling mountain land, through sagebrush, sagebrush and scattered pinon and juniper growth.</p> <p>The closing cor. of secs. 13 and 24, T. 30 S., R. 2 W., monumented with a trachyte stone, 24 x 12 x 8 ins., firmly set 10 ins. in the ground and plainly mkd. 3 notches on N and S edges, with CC on W face.</p> <p>from which original bearing trees</p> <p style="padding-left: 40px;">A juniper, 18 ins. diam., bears S. 58° W., 27 lks. dist., mkd. S24 BT.</p> <p style="padding-left: 40px;">A standing dead pinon, 14 ins. diam., bears N. 65° W., 110 1/2 lks. dist., plainly mkd. S 13 BT.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 30 S R 2 W R 1 W C S 13   C S 24   S 19 1984</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Cor. is located on nearly level land in scattered pinon and juniper growth.</p>
9.500	<p>Point for the N 1/16 sec. cor. of sec. 19 only.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p>
29.494	<p style="text-align: center;">T 30 S R 2 W R 1 W   N 1/16 1984</p> <p>Cor. is located on N. slope, in scrub pinon and juniper growth.</p> <p>The closing cor. of secs. 18 and 19, monumented with an iron post, 2 ins. diam., extending 8 ins. above the ground, and in a mound of stone, 3 ft. base, 2 ft. high, E of cor., with brass cap, mkd. as described in the official record of the 1922 resurvey.</p>

Dependent Resurvey of a Portion of the West Boundary,  
T. 30 S., R. 1 W., Salt Lake Meridian, Utah

CHAINS

- Thence along the W. bdy. of sec. 18 with continuous measurement.
- 47.773 The 1/4 sec. cor. of sec. 13 only, monumented with an iron post, 1 in. diam., extending 8 ins. above the ground, with brass cap, mkd. as described in the official record of the 1922 resurvey.
- from which the original bearing trees
- A juniper, 16 ins. diam., bears S. 63° W.,  
125 lks. dist., mkd. 1/4 S13 BT.
- A pinon, 10 ins. diam., bears N. 31 1/4° W., 165  
lks. dist., mkd. 1/4 S13 BT.
- 
- Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 30 S., R. 1 W., Salt Lake Meridian, Utah
- 
- (Reestablishment of the Survey Executed by  
G.F. Rigby in 1922)
- 
- From the cor. of secs. 19, 20, 29, and 30, monumented with an iron post, 2 ins. diam., set in a mound of stone, 4 ft. base, 2 ft. high to top of brass cap, mkd. as described in the official record of the 1922 survey.
- from which the original bearing trees
- A pinon, 8 ins. diam., bears N. 30° E., 123 lks.  
dist., mkd. T30S R1W S20 BT.
- A pinon, 16 ins. diam., bears S. 84° E., 92 lks.  
dist., mkd. T30S R1W S29 BT.
- A pinon, 9 ins. diam., bears S. 41° W., 160 lks.  
dist., mkd. T30S R1W S30 BT.
- A pinon, 10 ins. diam., bears N. 65° W., 97 lks.  
dist., mkd. T30S R1W S19 BT.
- N. 89° 56.9' W., bet. secs. 19 and 30.
- Over mountainous land, through pinon and juniper growth.
- 19.997 Point for the E 1/16 sec. cor. of secs. 19 and 30.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.
- T 30 S R 1 W  
S 19  
E 1/16 S 30  
1984
- Raise a mound of stone, 4 ft. base, 2 ft. high, to W to protect the cor.
- Cor. is located on SW slope in pinon and juniper growth.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 30 S., R. 1 W., Salt Lake Meridian, Utah

CHAINS	
39.994	<p>The 1/4 sec. cor.. of secs. 19 and 30, monumented with an iron post, 1 ins. diam., extending 8 ins. above the ground, with a mound of stone, 2 ft. base, 1 1/2 ft. high to N, with brass cap, mkd. as described in the official record of the 1922 survey.</p>
20.008	<p>N. 89° 57.0' W., beginning new measurement.</p> <p>Point for the W 1/16 sec. cor. of secs. 19 and 30.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 30 S R 1 W S 19 W 1/16     S 30 1984</p> </div>
30.472	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <p>Cor. is located on N slope in sagebrush.</p> <p>The closing cor. of secs. 19 and 30, hereinbefore described.</p> <p>From this cor., the S-S 1/64 sec. cor. of sec. 19 only, on W. bdy., bears N. 0° 03.3' W., 9.996 chs. dist. hereinbefore described.</p> <p>From this same cor., an angle point bet. secs. 25 and 30, T. 30 S., Rs. 1 and 2 W., bears S. 0° 03.3' E., 29.533 chs. dist., hereinbefore described.</p>
20.019	<p>From the cor. of secs. 19, 20, 29, and 30.</p> <p>N. 0° 06.0' W., bet. secs. 19 and 20.</p> <p>Over broken mountainous land, through pinon, juniper and scattered ponderosa pine.</p> <p>Point for the S 1/16 sec. cor. of secs. 19 and 20.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.</p> <div style="text-align: center;"> <p>T 30 S R 1 W S 1/16 S 19   S 20 1984</p> </div>
40.038	<p>Cor. is located on gentle N slope in pinon and juniper growth.</p> <p>The 1/4 sec. cor. of secs. 19 and 20, monumented with an iron post, 1 ins. diam., extending 8 ins. above the ground, with brass cap, mkd. as described in the official record of the 1922 survey.</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 30 S., R. 1 W., Salt Lake Meridian, Utah

## CHAINS

from which the original bearing trees

A juniper, 26 ins. diam., bears S. 59 1/2° E.,  
38 lks. dist., mkd. 1/4 S20 BT.

A pinon, 15 ins. diam., bears S. 81° W.,  
20 lks. dist., mkd. 1/4 S19 BT.

N. 0° 04.8' W., beginning new measurement.

19.989 Point for the N 1/16 sec. cor. of secs. 19 and 20.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20  
ins. in the ground, and in a mound of stone, 3 1/2 ft.  
base, to top of aluminum cap, mkd.

T 30 S R 1 W  
N 1/16  
S 19 | S 20  
1984

Cor. is located on gentle W slope in pinon and juniper  
growth.

39.978 The cor. of secs. 17, 18, 19, and 20, monumented with an  
iron post, 2 ins. diam., extending 12 ins. above the  
ground, in a mound of stone, 4 ft. base, to top of brass  
cap, mkd. as described in the official record of the 1922  
survey.

from which the original bearing trees

A juniper, 20 ins. diam., bears N. 52° E.,  
15 lks. dist., mkd. T30S R1W S17 BT.

A pinon, 12 ins. diam., bears S. 65° E.,  
28 lks. dist., mkd. T30S R1W S20 BT.

A juniper, 12 ins. diam., bears S. 35° W.,  
72 lks. dist., mkd. T30S R1W S19 BT.

A juniper, 10 ins. diam., bears N. 46 1/2° W.,  
96 lks. dist., mkd. T30S R1W S18 BT.

N. 89° 57.8' W., bet. secs. 18 and 19.

Over mountainous land, through pinon, juniper, balsam  
pine, and scattered ponderosa pine.

20.043 Point for the E 1/16 sec. cor. of secs. 18 and 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14  
ins. in the ground to bedrock, and in a mound of stone, 6  
ft. base, to top of aluminum cap, mkd.

T 30 S R 1 W  
S 18  
E 1/16 S 19  
1984

Cor. is located on NW slope in pinon and juniper growth.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 30 S., R. 1 W., Salt Lake Meridian, Utah

CHAINS	
40.086	<p>The 1/4 sec. cor. of secs. 18 and 19, monumented with an iron post, 1 in. diam., extending 8 ins. above the ground, with brass cap, mkd. as described in the official record of the 1922 survey.</p> <p style="text-align: center;">_____</p> <p>S. 89° 59.3' W., beginning new measurement.</p> <p>Over rolling mountain land, through sagebrush, shadscale, and scattered pinon and juniper growth.</p>
20.028	<p>Point for the W 1/16 sec. cor. of secs. 18 and 19.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.</p> <p style="text-align: center;">T 30 S R 1 W S 18 W 1/16      S 19 1984</p> <p>Cor. is located on rolling W slope in sagebrush and scattered pinon and juniper growth.</p>
30.663	<p>The closing cor. of secs. 18 and 19, hereinbefore described.</p> <p>From this cor. the 1/4 sec. cor. of sec. 13 only, on the E. bdy. of T. 30 S., R. 2 W., bears N. 0° 42.0' W., 18.279 chs. dist., hereinbefore described.</p> <p>From this same cor., the N 1/16 sec. cor. of sec. 19 only, on the W. bdy. of the Tp., bears S. 0° 42.0' E., 19.994 chs. dist., hereinbefore described.</p> <hr/> <p style="text-align: center;">Survey of a Portion of the Subdivision of Section 19, T. 30 S., R. 1 W., Salt Lake Meridian, Utah</p> <hr/> <p>From the 1/4 sec. cor. of secs. 19 and 30.</p> <p>N. 0° 09.3' W., on the N-S center line of sec. 19.</p> <p>Over mountain land, through pinon and juniper growth.</p>
15.003	<p>Point for the center north-south-south 1/256 sec. cor. of sec. 19.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.</p> <p style="text-align: center;">T 30 S R 1 W C-N-S-S 1/256 S 19 1984</p> <p>Cor. is located on gentle S slope in pinon and juniper growth.</p>
20.004	<p>Point for the center S 1/16 sec. cor. of sec. 19.</p>

Survey of a Portion of the Subdivision of Section 19,  
T. 30 S., R. 1 W., Salt Lake Meridian, Utah

CHAINS	
30.006	<p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 30 S R 1 W C S 1/16   S 19 C 1984</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor. Cor. is located on W slope in pinon and juniper growth.</p> <p>Point for the center-north-south 1/64 sec. cor. of sec. 19.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">T 30 S R 1 W C-N-S 1/64 S 19 1984</p> <p>Cor. is located on S slope in small draw, drains SW in pinon and juniper growth.</p>
40.008	<p>Point for the center 1/4 sec. cor. of sec. 19, at intersection with the E and W center line.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 30 S R 1 W C 1/4 S 19 1984</p> <p>Set a juniper post, 6 ft. long, alongside the aluminum post.</p> <p>Cor. is located on N edge of meadow, bears E, W, and S of old shed.</p>
50.008	<p>Point for the center south-north 1/64 sec. cor. of sec. 19.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 30 S R 1 W C-S-N 1/64 S 19 1984</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor. Cor. is located on NW slope in pinon and juniper growth.</p>
60.008	<p>Point for the center north 1/16 sec. cor. of sec. 19.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>

Survey of a Portion of the Subdivision of Section 19,  
T. 30 S., R. 1 W., Salt Lake Meridian, Utah

CHAINS	
80.008	<p style="text-align: center;">T 30 S R 1 W C N 1/16   S 19 C 1984</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor. Cor. is located on W slope in sagebrush and scattered juniper growth.</p>
20.016	<p>The 1/4 sec. cor. of secs. 18 and 19.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 19 and 20. N. 89° 59.6' W., on the E-W center line of sec. 19. Over mountain land, through sagebrush, pinon and juniper growth.</p>
40.032	<p>Point for the center east 1/16 sec. cor. of sec. 19.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a mound of stone, 5 ft. base, to top of aluminum cap, mkd.</p> <p style="text-align: center;">T 30 S R 1 W E 1/16 C ——— S 19 ——— C 1984</p> <p>Cor. is located on NW slope in sagebrush.</p>
60.073	<p>The center 1/4 sec. cor. of sec. 19.</p> <p>Point for the center west 1/16 sec. cor. of sec. 19.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, with 5 ft. cedar post alongside, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.</p>
70.434	<p style="text-align: center;">T 30 S R 1 W W 1/16 C ——— S 19 ——— C 1984</p> <p>Cor. is located on gentle S slope in scattered pinon and juniper growth.</p> <p>The 1/4 sec. cor. of sec. 19 only, hereinbefore described.</p> <hr/> <p>From the center east 1/16 sec. cor. of sec. 19. N. 0° 07.1' W., on the N-S center line of the NE 1/4 of sec. 19. Over mountain land, through pinon and juniper growth.</p> <p>Point for the center-south-northeast 1/64 sec. cor. of sec. 19.</p>
9.997	

Survey of a Portion of the Subdivision of Section 19,  
T. 30 S., R. 1 W., Salt Lake Meridian, Utah

CHAINS	
	<p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 30 S R 1 W C-S-NE 1/64 S 19 1984</p> <p>Cor. is located in sagebrush flat.</p>
19.994	<p>Point for the northeast 1/16 sec. cor. of sec. 19, at intersection with the E and W center line of the NE 1/4.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.</p> <p style="text-align: center;">T 30 S R 1 W NE 1/16 S 19 1984</p> <p>Cor. is located 35 lks. W of trail road, bears N and S in small sagebrush flat and scattered juniper growth.</p>
39.988	<p>The E 1/16 sec. cor. of secs. 18 and 19.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 19 and 20.</p> <p>N. 89° 58.7' W., on the E-W center line of the NE 1/4 of sec. 19.</p> <p>Over mountain land, through sagebrush, pinon and juniper growth.</p>
20.030	<p>the northeast 1/16 sec. cor. of sec. 19.</p>
40.060	<p>The center north 1/16 sec. cor. of sec. 19.</p> <hr/> <p>From the center south-northeast 1/64 sec. cor. of sec. 19.</p> <p>N. 89° 59.1' W., on the E-W center line of the SW 1/4 of the NE 1/4 of sec. 19.</p> <p>Over mountain land, through sagebrush, pinon and juniper growth.</p>
20.023	<p>The center north-south 1/64 sec. cor. of sec. 19.</p> <hr/> <p>From the E 1/16 sec. cor. of secs. 19 and 30.</p> <p>N. 0° 07.7' W., on the N-S center line of the SE 1/4 of sec. 19.</p> <p>Over mountain land, through sagebrush, pinon and juniper growth.</p>
20.012	<p>Point for the southeast 1/16 sec. cor. of sec. 19, at intersection with the E-W center line of the SE 1/4.</p>

Survey of a Portion of the Subdivision of Section 19,  
T. 30 S., R. 1 W., Salt Lake Meridian, Utah

CHAINS	
30.018	<p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 30 S R 1 W SE 1/16 S 19 1984</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor. Cor. is located on NW slope in pinon and juniper growth.</p> <p>Point for the center north-southeast 1/64 sec. cor. of sec. 19.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 30 S R 1 W C-N-SE 1/64 S 19 1984</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor. Cor. is located on NW slope in pinon and juniper growth.</p> <p>The center E 1/16 sec. cor. of sec.19.</p>
20.007	<p>From the S 1/16 sec. cor. of secs. 19 and 20.</p> <p>N. 89° 58.3' W., on the E-W center line of the SE 1/4 of sec. 19.</p> <p>Over mountain land, through pinon and juniper growth.</p> <p>The southeast 1/16 sec. cor. of sec. 19.</p>
40.014	<p>The center S 1/16 sec. cor. of sec. 19.</p>
20.011	<p>From the center north-southwest 1/64 sec. cor. of sc. 19.</p> <p>N. 89° 59.0' W., on the E-W center line of the NW 1/4 of the SE 1/4 of sec. 19.</p> <p>Over mountain land, through sagebrush, pinon and juniper growth.</p> <p>The center south-north 1/64 sec. cor. of sec. 19.</p>
9.998	<p>From the W 1/16 sec. cor. of secs. 19 and 30.</p> <p>N. 0° 12.1' W., on the N-S center line of the SW 1/4 of sec. 19.</p> <p>Over mountain land, through sagebrush, pinon and juniper growth.</p> <p>Point for the center south-southwest 1/64 sec. cor. of sec. 19.</p>

Survey of a Portion of the Subdivision of Section 19,  
T. 30 S., R. 1 W., Salt Lake Meridian, Utah

CHAINS	
	<p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 4 1/2 ft. base, to top of aluminum cap, mkd.</p> <p style="text-align: center;">T 30 S R 1 W C-S-SW 1/64 S 19 1984</p> <p>Cor. is located in bottom of small draw, drains N in pinon and juniper growth.</p>
14.997	<p>Point for the center north-south-southwest 1/256 sec. cor. of sec. 19.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">T 30 S R 1 W C-N-S-SW 1/256 S 19 1984</p> <p>Set a 6 ft. juniper post alongside the aluminum post.</p> <p>Cor. is located in sagebrush flat, 1.50 chs. N of trail road, bears NE and SW.</p>
19.996	<p>Point for the southwest 1/16 sec. cor. of sec. 19, at intersection with the E-W center line.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 30 S R 1 W SW 1/16 S 19 1984</p> <p>from which</p> <p style="text-align: center;">A pinon, 14 ins. diam., bears S. 85° E., 13 lks. dist., mkd. SW 1/16 BT.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <p>Cor. is located on N slope of small knoll in scattered pinon and juniper.</p>
39.992	<p>The center W 1/16 sec. cor. of sec. 19.</p> <hr/> <p>From the center S 1/16 sec. cor. of sec. 19.</p> <p>N. 89° 58.3' W., on the E-W center line of the SW 1/4 of sec. 19.</p> <p>Over rolling mountain land, through sagebrush, pinon and juniper tree growth.</p>
20.024	<p>The SW 1/16 sec. cor. of sec. 19.</p>
30.437	<p>The S 1/16 sec. cor. of sec. 19 only.</p> <hr/> <p>From the center north-south-south 1/256 sec. cor. of sec. 19.</p>

Survey of a Portion of the Subdivision of Section 19,  
T. 30 S., R. 1 W., Salt Lake Meridian, Utah

CHAINS	
20.020	<p>N. 89° 57.9' W., on the E-W center line of the N 1/2 of the SE 1/4 of the SW 1/4 of sec. 19.</p> <p>Over rolling mountain land, through sagebrush and scattered pinon and juniper growth.</p> <p>The center north-south-southwest 1/256 sec. cor. of sec. 19.</p>
10.438	<p>From the center south-southwest 1/64 sec. cor. of sec. 19.</p> <p>N. 89° 57.6' W., on the E-W line through the original Lot 4, of sec. 19.</p> <p>Over rolling mountain land, through sagebrush and scattered pinon and juniper growth.</p> <p>The south-south 1/64 sec. cor. of sec. 19 only.</p>
9.998	<p>From the center west 1/16 sec. cor. of sec. 19.</p> <p>N. 0° 08.3' W., on the N-S center line of the NW 1/4 of sec. 19.</p> <p>Over rolling mountain land, through sagebrush and scattered pinon and juniper growth.</p> <p>Point for the center south-northwest 1/64 sec. cor. of sec. 19.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 30 S R 1 W C-S-NW 1/64 S 19 1984</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <p>Cor. is located on nearly level land, in sagebrush and scattered pinon and juniper growth.</p>
19.996	<p>Point for the northwest 1/16 sec. cor. of sec. 19, at intersection with the E-W center line of the NW 1/4, not monumented.</p>
39.992	<p>The west 1/16 sec. cor. of secs. 18 and 19.</p>
20.034	<p>From the center north 1/16 sec. cor. of sec. 19.</p> <p>S. 89° 59.8' W., on the E-W center line of the NW 1/4 of sec. 19.</p> <p>Over rolling mountain land, through sagebrush and scattered pinon and juniper growth.</p> <p>The NW 1/16 sec. cor. of sec. 19, not monumented.</p>
30.473	<p>The N 1/16 sec. cor. of sec. 19 only.</p>

Survey of a Portion of the Subdivision of Section 19,  
T. 30 S., R. 1 W., Salt Lake Meridian, Utah

<p>CHAINS</p> <p>20.037</p>	<p>From the center south-north 1/64 sec. cor. of sec. 19.</p> <p>N. 89° 59.9' W., on the E-W center line of the SE 1/4 of the NW 1/4 of sec. 19.</p> <p>Over rolling mountain land, through sagebrush and scattered pinon and juniper growth.</p> <p>The center south-northwest 1/64 sec.cor. of sec. 19.</p> <hr/> <p style="text-align: center;">General Description</p> <p>The area surveyed and resurveyed within Township 30 South, Range 1 West, varies from broken mountainous land at higher elevations to rolling rocky hills and knolls at lower elevations. The elevation ranges from 7200 to 7800 ft. above sea level. The soil varies from sandy clay loam at the lower elevations to very rocky lava formations at the upper elevations. The vegetation consists of shadscale, sagebrush, bunchgrass, and other native grasses. The area is generally covered with pinon and juniper growth. The general drainage is to the west. There are a few small meadows in the section used for grazing of livestock.</p>	
-----------------------------	---	--



CERTIFICATE OF SURVEY

(I) (W~~e~~)X Gail E. Reynolds, Cadastral Surveyor , HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 18th day of September , 19 84 , (I) (W~~e~~)X have dependently resurveyed a portion of the west boundary and a portion of the subdivisional lines with a subdivisional survey of section 19 of T. 30 S., R. 1 W.,

of the Salt Lake Meridian, in the State of Utah , which are represented in the foregoing field notes as having been executed by (me), (W~~e~~) and under (my) (W~~e~~) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

November 6, 1985 (Date) Gail E. Reynolds (Cadastral Surveyor)

(Date) (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the west boundary and a portion of the subdivisional lines with a subdivisional survey of section 19, T. 30 S., R. 1 W., of the Salt Lake Meridian, Utah

executed by Gail E. Reynolds, Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

November 8, 1985 (Date) Glen B Hatch Chief Cadastral Surveyor for Utah

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

(Date) Chief Cadastral Surveyor for Utah

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

R 608

ORIGINAL

174

FIELD NOTES  
OF THE

DEPENDENT RESURVEY

OF A PORTION OF THE SOUTH BOUNDARY,

A PORTION OF THE EAST BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES,

AND A PORTION OF THE PRIVATE LAND CLAIMS

WITH A SUBDIVISION SURVEY

OF

SECTION 34,

TOWNSHIP 6 SOUTH, RANGE 4 EAST

Of the Salt Lake Meridian,

In the State of Utah

EXECUTED BY

Gary L. Kratz Supervisory Cadastral Surveyor

Under special instructions dated May 23, 1983, approved May 24, 1983

\_\_\_\_\_, which provided for the surveys included under U.S. Survey/Group  
Number 632, and assignment instructions dated May 24, 1983.

Survey commenced July 17, 1983

Survey completed September 22, 1983

# INDEX DIAGRAM

Township 6 South, Range 4 East

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
		10	9	8	
31	32	33 8	34 7	35	36 6
	5	5	4	3	1

- Subdivision of Section 42 - Page 11
- Subdivision of Section 45 - Page 12
- Subdivision of Section 46 - Page 13
- Subdivision of Section 34 - Page 16

## Township 6 South, Range 4 East, Salt Lake Meridian, Utah

## CHAINS

The following field notes are those of the dependent resurvey of a portion of the south boundary, a portion of the east boundary, a portion of the subdivisional lines, and a portion of the private land claims with a subdivision survey of section 34, Township 6 South, Range 4 East, Salt Lake Meridian, Utah.

In 1899 S.P. Stewart and J.R. Stewart surveyed the south and east boundaries, the subdivisional lines and the private land claims. In 1910 A.P. Hanson retraced a portion of the south boundary.

Certain corners were remonumented in 1961 and 1962 under the remonumentation cooperative agreement between the U.S. Forest Service and the Bureau of Land Management.

The survey was executed in accordance with the Manual of Surveying Instructions, 1973, and the Special Instructions dated May 23, 1983.

The directions of the lines refer to the true meridian, and were determined from hour angle observations on the sun and Polaris. The lines were carried forward by sustained angulation.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the southeast corner of the township, as determined from a tie to U.S. Geological Survey triangulation station "Bartholomew", located in section 8, T. 7 S., R. 4 E., is:

Latitude  $40^{\circ} 14' 46.98''$  N. Longitude  $111^{\circ} 25' 25.19''$  W.

The mean magnetic declination, as projected from the U.S. Geological Survey "Magnetic Declination Map of 1980", is  $14 \frac{1}{2}^{\circ}$  E.

---

Dependent Resurvey of a Portion of the South Boundary,  
T. 6 S., R. 4 E., Salt Lake Meridian, Utah

---

(Reestablishment of the Survey Executed by  
S.P. Stewart and J.R. Stewart in 1899)

---

Beginning at the cor. of Tps. 6 and 7 S., Rs. 4 and 5 E., monumented with a limestone, 24 x 19 x 9 ins., firmly set 18 ins. in the ground, mkd. 6S on the NE, 5E on the SE, 7S on the SW and 4E on the NW faces, and 6 notches on the N, E, S, and W edges, with a mound of stone S of the cor., and a steel fence post alongside.

At the corner point

Dependent Resurvey of a Portion of the South Boundary,  
T. 6 S., R. 4 E., Salt Lake Meridian, Utah

## CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

$$\begin{array}{r} T 6 S \\ R 4 E \quad R 5 E \\ \hline S 36 \quad | \quad S 31 \\ \hline S 1 \quad | \quad S 6 \\ T 7 S \\ 1983 \end{array}$$

Bury the mkd. stone and reset the steel fence post alongside the aluminum post.

From this cor., the U.S. Geological Survey triangulation station "Bartholomew", bears S. 71° 48' 19" W., 353.208 chs. dist.

N. 89° 54' W., bet. secs. 1 and 36. Desc. over mountainous terrain, through moderate brush.

20.00 The E 1/16 sec. cor. of secs. 1 and 36, monumented by Parley Neeley, RLS No. 1722 in 1958, with an iron post, 2 ins. diam., firmly set, projecting 16 ins. above the ground, and in a mound of stone, with an iron cap mkd.

$$\begin{array}{r} 1722 \\ S 36 \quad T 6 S \\ \hline S 1 \quad T 7 S \\ E 1/16 \end{array}$$

A steel fence post is set alongside the iron pipe.

This monument is accepted as a careful and faithful determination of the position of the corner.

N. 89° 48' W., beginning new measurement.

19.88 The 1/4 sec. cor. of secs. 1 and 36, monumented with a sandstone, 20 x 12 x 5 ins., firmly set 12 ins. in the ground, and in a mound of stone, mkd. 1/4 on N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

$$\begin{array}{r} T 6 S R 4 E \\ \quad S 36 \\ 1/4 \quad \hline \quad S 1 \\ \quad T 7 S \\ \quad 1983 \end{array}$$

Bury the mkd. stone alongside the aluminum post.

N. 89° 44' W., beginning new measurement.

39.72 The cor. of secs. 1, 2, 35, and 36, monumented with a sandstone, 16 x 9 x 6 ins., firmly set 11 ins. in the ground, mkd. 1 notch on E and 5 notches on W edges, with a mound of stone W of cor.

Dependent Resurvey of a Portion of the South Boundary,  
T. 6 S., R. 4 E., Salt Lake Meridian, Utah

## CHAINS

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 6 S R 4 E  
S 35 | S 36  
S 2 | S 1  
T 7 S  
1983

Bury the mkd. stone alongside the aluminum post.

N. 89° 55' W., bet. secs. 2 and 35.

Desc. over mountainous terrain, through moderate brush and timber.

6.865 Point for the closing cor. of secs. 2 and 35, with line 4-5, Mary E. Whiting private land claim (sec. 44), at proportionate distance; there is no remaining evidence of the original corner. Not monumented.

38.64 Point selected for the witness cor. to the 1/4 sec. cor. of secs. 2 and 35.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

W C  
T 6 S R 4 E  
S 35  
1/4 ← S 2  
T 7 S  
1983

Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, N of cor.

39.64 True point for the 1/4 sec. cor. of secs. 2 and 35, at proportionate distance; there is no remaining evidence of the original corner. This point falls in Hobble Creek, where monumentation is impractical.

66.25 Point for the closing cor. of secs. 2 and 35, with line 1-2, Mary E. Whiting private land claim (sec. 44), at proportionate distance; there is no remaining evidence of the original corner. Not monumented.

79.28 Point for the cor. of secs. 2, 3, 34, and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. below the surface, with aluminum cap mkd.

T 6 S R 4 E  
S 34 | S 35  
S 3 | S 2  
T 7 S  
1983

Set a steel fence post N of the aluminum post.

Dependent Resurvey of a Portion of the South Boundary,  
T. 6 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	Cor. is located in a cultivated field.
	N. 89° 55' W., bet. secs. 3 and 34.
19.905	Point for the E 1/16 sec. cor. of secs. 3 and 34. Not monumented.
22.42	<p>The closing cor. of sec. 3 and 34, with line 3-4, John C. Whiting private land claim (sec. 43), identical with line 1-2, Moroni Miner private land claim (sec. 41), monumented with a quartzite stone, 24 x 10 x 8 ins., firmly set 16 ins. in the ground, plainly mkd. CC JCW on the E face, with a mound of stone to the N.</p> <p>This point will also function as an angle point.</p> <p>At the corner point</p> <p>Set an aluminum post. 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.</p> <div style="text-align: center;"> <p>AP T 6 S R 4 E S 34 <u>S 3</u> T 7 S 1983</p> </div> <p>Bury the mkd. stone alongside the aluminum post.</p>
	N. 89° 44' W., beginning new measurement.
17.39	<p>The 1/4 sec. cor. of secs. 3 and 34, monumented with a quartzite stone, 18 x 8 x 6 ins., firmly set 13 ins. in the ground, mkd. 1/4 on N face, with a mound of stone N of cor.</p> <p>At the corner point</p> <p>Set an aluminum post. 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 6 S R 4 E S 34 1/4 <u>S 3</u> T 7 S 1983</p> </div> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.</p> <p>Bury the mkd. stone alongside the aluminum post.</p> <p>Cor. is located 25 lks. E of center of an unimproved road, bears NW-SE.</p>
	S. 89° 58' W., beginning new measurement.
19.82	Point for the W 1/16 sec. cor. of secs. 3 and 34. Not monumented.

Dependent Resurvey of a Portion of the South Boundary,  
T. 6 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS 33.81	Point for Cor. No. 6, Moroni Miner private land claim (sec. 41), at proportionate distance; there is no remaining evidence of the original corner. Not monumented.
35.37	<p>The 1 1/2 Mile Cor., Moroni Miner private land claim (sec. 41), monumented with a sandstone, 16 x 9 x 8 ins., firmly set 8 ins. in the ground, mkd. 1/2MMM on the S face, with a mound of stone S of cor.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 6 S R 4 E S 34 ----- 1 1/2 M S 47 T 7 S 1983</p> <p>Bury the mkd. stone alongside the aluminum post.</p> <p>-----</p> <p>N. 89° 02' W., beginnig new measurement.</p>
4.27	<p>The cor. of secs. 4, 33, 34, 44, and 47, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 15 ins. above ground, and in a mound of stone, 3 ft. base, to top of brass cap, mkd. as described in the official record of the 1975 remonumentation.</p> <p>Cor. is located near W edge of a large level clearing.</p>
40.02	<p>N. 89° 49' W., bet. secs. 4 and 33.</p> <p>The 1/4 sec. cor. of secs. 4 and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above ground, and in a collar of stone, with brass cap, mkd. as described in the official record of the 1975 remonumentation.</p> <p>Cor. is located in dense oak and maple.</p> <p>-----</p> <p>N. 89° 57' W., beginning new measurement.</p>
39.57	<p>The cor. of secs. 4, 5, 32, and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 25 ins. above ground, and in a mound of stone, 4 ft. base, to top of brass cap, mkd. as described in the official record of the 1975 remonumentation.</p> <p>Cor. is located on E slope in oak brush.</p>
19.995	<p>S. 89° 57' W., bet. secs. 5 and 32.</p> <p>Point for the E 1/16 sec. cor. of secs. 5 and 32. Not monumented.</p>
39.99	<p>The 1/4 sec. cor. of secs. 5 and 32, monumented with a brass cap set in concrete, flush with the ground, with no marks; this monument is accepted as a careful and faithful reestablishment of the position of the original corner.</p>

Dependent Resurvey of a Portion of the South Boundary,  
T. 6 S., R. 4 E., Salt Lake Meridian, Utah

<p>CHAINS</p> <p>20.01</p> <p>19.98</p> <p>39.90</p>	<p>Cor. is located on NE slope approximately 1 chain E of dirt road, bears NW-SE.</p> <hr/> <p>N. 89° 58' W., beginning new measurement.</p> <p>The W 1/16 sec. cor. of secs. 5 and 32, monumented with a brass cap set in concrete flush with the ground, mkd.</p> $\text{W } 1/16 \quad \frac{32}{5}$ <p>This monument is accepted as a careful and faithful determination of the position of the corner and was re-marked</p> $\begin{array}{r} \text{T } 6 \text{ S } \text{ R } 4 \text{ E} \\ \text{S } 32 \\ \text{W } 1/16 \quad \text{S } 5 \\ \text{T } 7 \text{ S} \\ 1983 \end{array}$ <hr/> <p>N. 89° 55' W., beginning new measurement.</p> <p>The cor. of secs. 5, 6, 31, and 32, monumented with an iron rebar, 1/2 in. diam., 2 ft. long, 18 ins. in the ground; this monument was set by Parley Neeley, RLS No. 1722, in 1958 and is accepted as a careful and faithful reestablishment of the position of the original corner.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> $\begin{array}{r} \text{T } 6 \text{ S } \text{ R } 4 \text{ E} \\ \text{S } 31 \quad   \quad \text{S } 32 \\ \text{S } 6 \quad   \quad \text{S } 5 \\ \text{T } 7 \text{ S} \\ 1983 \end{array}$ <p>Cor. is located in a small draw, bears NE in very dense undergrowth.</p> <p>Bury iron rebar alongside the aluminum post.</p> <hr/> <p>Dependent Resurvey of a Portion of the East Boundary, T. 6 S., R. 4 E., Salt Lake Meridian, Utah</p> <hr/> <p>(Reestablishment of the Survey Executed by S.P. Stewart and J.R. Stewart in 1899)</p> <hr/> <p>From the cor. of Tps. 6 and 7 S., Rs. 4 and 5 E., heretofore described.</p> <p>N. 0° 03' E., bet. secs. 31 and 36.</p> <p>Point for the 1/4 sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p>
--	---

Dependent Resurvey of a Portion of the East Boundary,  
T. 6 S., R. 4 E., Salt Lake Meridian, Utah

## CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 6 S  
R 4 E R 5 E  
1/4  
S 36 | S 31  
1983

Cor. is located on a spur, bears S.

79.80

The cor. of secs. 25, 30, 31, and 36, monumented with a sandstone, 16 x 8 x 6 ins., firmly set 11 ins. in the ground, mkd. 5 notches on N and 1 notch on S edges, with a mound of stone to the W and a steel fence post alongside.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with an aluminum cap mkd.

T 6 S  
R 4 E R 5 E  
S 25 | S 30  
S 36 | S 31  
1983

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

Bury the mkd. stone and reset the steel fence post alongside the aluminum post.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 6 S., R. 4 E., Salt Lake Meridian, Utah

(Reestablishment of the Survey Executed by  
S.P. Stewart and J.R. Stewart in 1899)

From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., heretofore described.

N. 0° 09' W., bet. secs. 34 and 35.

11.40

Point for the original closing cor. of secs. 34 and 35, at intersection with the Joseph H. Curtis private land claim (sec. 42), at proportionate distance; there is no remaining evidence of the original corner; not monumented.

38.78

Point for the original closing cor. of secs. 34 and 35, with the A. Milton Curtis private land claim (sec. 40), at proportionate distance; there is no remaining evidence of the original corner; not monumented.

39.88

Point selected for the witness cor. to the 1/4 sec. cor. of secs. 34 and 35.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with aluminum cap mkd.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 6 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
	<div style="text-align: center;"> <p>W C T 6 S R 4 E 1/4 ↑ S 34   S 35 1983</p> </div> <p>Set a steel fence post alongside the aluminum post.</p> <p>Cor. is located on the N edge of an earthen dam.</p> <p>39.98 True point for the 1/4 sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original cor. This point falls in a small reservoir, where monumentation is impractical.</p> <p>59.97 Point for the N 1/16 sec. cor. of secs. 34 and 35.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.</p> <div style="text-align: center;"> <p>T 6 S R 4 E N 1/16 S 34   S 35 1983</p> </div>
	<p>79.96 The cor. of secs. 26, 27, 34, and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, and in a collar of stone, with brass cap, mkd. as described in the official record of the 1962 remonumentation.</p> <p>A mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <p>Cor. is located on the E edge of a bench.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 26 and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set in a collar of stone, projecting 6 ins. above the ground, with brass cap, mkd. as described in the official record of the 1962 remonumentation.</p> <p>A mound of stone, 3 ft. base, 2 ft. high, N of cor.</p> <p>N. 88° 29' W., bet. secs. 26 and 35.</p> <p>42.31 The cor. of secs. 26, 27, 34, and 35.</p>
	<p>From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., heretofore described.</p> <p>N. 0° 08' E., bet. secs. 33 and 34.</p> <p>19.97 The S 1/16 sec. cor. of secs. 33 and 34, monumented by Parley Neeley, RLS No. 1722 in 1950, with an iron pipe, 2 ins. diam., firmly set, projecting 6 ins. above the ground, and in a collar of stone, with an iron cap, mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 6 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS

S 1/16  
|  
S 33 | S 34  
|  
1722

A steel fence post is set alongside the iron post.

This monument is accepted as a careful and faithful  
determination of the position of the cor.

N. 0° 01' W., beginning new measurement.

19.87 The 1/4 sec. cor. of secs. 33 and 34, monumented with a  
quartzite stone, 20 x 8 x 5 ins., firmly set 18 ins. in  
the ground, and in a mound of stone, plainly mkd. 1/4 on  
W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22  
ins. in the ground, with aluminum cap mkd.

T 6 S R 4 E  
|  
1/4  
|  
S 33 | S 34  
|  
1983

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

Bury the mkd. stone alongside the aluminum post.

N. 0° 02' E., beginning new measurement.

39.94 The cor. of secs. 27, 28, 33, and 34, monumented with a  
quartzite stone, 14 x 14 x 6 ins., firmly set 8 ins. in  
the ground, mkd. 3 notches on E edge and 1 notch on S  
edge, with an embedded mound of stone, W of cor., and a  
steel fence post alongside.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22  
ins. in the ground, with aluminum cap mkd.

T 6 S R 4 E  
S 28 | S 27  
S 33 | S 34  
1983

Raise a mound of stone, 3 ft. base, 2 ft. high and reset  
the steel fence post, W of cor.

Bury the mkd. stone alongside the aluminum post.

From the cor. of secs. 26, 27, 34, and 35.

S. 89° 50' W., bet. secs. 27 and 34.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 6 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS  
19.815

Point for the E 1/16 sec. cor. of secs. 27 and 34; not monumented.

39.63

The 1/4 sec. cor. of secs. 27 and 34, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, and in a collar of stone, with brass cap, mkd. as described in the official record of the 1962 remonumentation.

Cor. is located on S slope.

N. 89° 53' W., beginning new measurement.

39.54

The cor. of secs. 27, 28, 33, and 34.

N. 89° 53' W., bet. secs. 28 and 33.

39.13

The 1/4 sec. cor. of secs. 28 and 33, monumented with a quartzite stone, 14 x 8 x 6 ins., firmly set 10 ins. in the ground, plainly mkd. 1/4 on N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.

	T 6 S R 4 E	
	S 28	
1/4	S 33	
	1983	

Set a steel fence post, N of cor.

Bury the mkd. stone alongside the aluminum post.

Cor. is located on S slope in oak brush.

N. 89° 51' W., beginning new measurement.

39.43

The cor. of secs. 28, 29, 32, and 33, monumented with a quartzite stone, 20 x 9 x 7 ins., firmly set 14 ins. in the ground, mkd. 4 notches on E and 1 notch on S edges, with a mound of stone, W of cor.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap mkd.

	T 6 S R 4 E	
	S 29   S 28	
	S 32   S 33	
	1983	

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor. Bury the mkd. stone alongside the aluminum post.

Cor. is located in NW end of a clearing in a fallen fence line, bears E and W.

Dependent Resurvey of a Portion of Section 42,  
T. 6 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	Dependent Resurvey of a Portion of Section 42, T. 6 S., R. 4 E., Salt Lake Meridian, Utah
	<p>(Reestablishment of the Survey Executed by S.P Stewart and J.R. Stewart in 1899)</p> <hr/> <p>From the 1 1/2 mile post of the Joseph H. Curtis private land claim (sec. 42), monumented with a quartzite stone, 15 x 9 x 8 ins., firmly set 12 ins. in the ground, mkd. 1/2 M JHC, with a mound of stone, S of cor.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, with aluminum cap, mkd.</p> <p style="text-align: center;">T 6 S R 4 E</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">1 1/2 M S 42 1983</p> <p>Bury the mkd. stone alongside the aluminum post.</p> <p>S. 89° 35' E., along line 7-1 of sec. 42.</p>
7.25	Intersect the N-S center line of sec. 34, hereinafter described.
27.12	Intersect the N-S center line of the SE 1/4 of sec. 34, hereinafter described.
29.09	<p>Cor. No. 2 of the A. Milton Curtis private land claim, (sec. 40), monumented with a quartzite stone, 17 x 10 x 6 ins., firmly set 12 ins. in the ground, mkd. 2AMC, with a mound of stone to the NE.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.</p> <p style="text-align: center;">T 6 S R 4 E</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">S 34   AP2 S 40   S 40 S 42 1983</p> <p>Bury the mkd. stone alongside the aluminum post.</p> <hr/> <p>N. 89° 51' E., beginning new measurement.</p>
12.01	Point for the 2 mile post of the Joseph H. Curtis private land claim (sec. 42), at proportionate distance; there is no remaining evidence of the original corner; not monumented.
17.895	Intersect the sec. line. bet. secs. 34 and 35; not monumented.

Dependent Resurvey of a Portion of Section 42,  
T. 6 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS  
19.94

Point for the beginning cor. of the A. Milton Curtis private land claim (sec. 40), identical with Cor. No. 5 of the A. Wayne Johnson private land claim (sec. 46), at proportionate distance based on the Grant Boundary Method; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.

T 6 S R 4 E  
AP 1 AP 5  
S 40 | S 46  
S 35  
1983

Set a steel fence post alongside the aluminum post.

Dependent Resurvey of a Portion of Section 45,  
T. 6 S., R. 4 E., Salt Lake Meridian, Utah

(Reestablishment of the Survey Executed by  
S.P. Stewart and J.R. Stewart in 1899)

From Cor. No. 5 of the Aaron Johnson private land claim (sec. 45), identical with Cor. No. 4 of the Fredrick W. Whiting private land claim (sec. 47), monumented with a quartzite stone, 16 x 9 x 9 ins., firmly set 12 ins. in the ground, mkd. 5AJ on the SW face and 4 FWW on the NW face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 6 S R 4 E  
AP 4 |  
S 47 | S 35  
AP 5  
S 45  
1983

Bury the mkd. stone alongside the aluminum post.

N. 76° 47' W., along line 5-4 of sec. 45.

9.01 Point for the 1 1/2 mile cor. of the Frederick W. Whiting private land claim (sec. 47), at proportionate distance; there is no remaining evidence of the original corner; not monumented.


29.855 Point for the 1/2 mile cor. of the Aaron Johnson private land claim (sec. 45); at proportionate distance; there is no remaining evidence of the original corner; not monumented.

40.17 Point for Cor. No. 4 of the Aaron Johnson private land claim (sec. 45), identical with Cor. No. 2 of the A. Wayne Johnson private land claim (sec. 46), identical with the beginning cor. of the Frederick W. Whiting private land claim (sec. 47). at proportionate distance based on the Grant Boundary Method; there is no remaining evidence of the original corner.

Dependent Resurvey of a Portion of Section 45,  
T. 6 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.



Set a steel fence post alongside the aluminum post.


Dependent Resurvey of a Portion of Section 46,  
T. 6 S., R. 4 E., Salt Lake Meridian, Utah

(Reestablishment of the Survey Executed by  
S.P. Stewart and J.R. Stewart in 1899)

From the beginning cor. of the A. Wayne Johnson private land claim (sec. 46), monumented with a sandstone, 20 x 10 x 8 ins., firmly set 12 ins. in the ground, mkd. BEG COR AWJ on the SW face, with a mound of stone SW of the cor., and a steel fence post alongside.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap mkd.



Raise a mound of stone, 3 ft. base, 2 ft. high, SW of cor.

Bury the mkd. stone alongside the aluminum post.

S. 21° 14' W., along line 1-2 of sec. 46.

- 5.655 Point for Cor. No. 2 of the Fredrick W. Whiting private land claim (sec. 47), at proportionate distance; there is no remaining evidence of the original corner. Not monumented.
- 6.025 Point for the 1/2 mile cor. of the Frederick W. Whiting private land claim (sec. 47), at proportionate distance; there is no remaining evidence of the original corner. Not monumented.
- 40.175 Point for the 1/2 mile cor. of the A. Wayne Johnson private land claim (sec. 46), at proportionate distance; there is no remaining evidence of the original corner. Not monumented.
- 46.20 Cor. No. 2 of the A. Wayne Johnson private land claim (sec. 46), identical with Cor. No. 4 of the Aaron Johnson private land claim (sec. 45), identical with Cor. No. 1 of the Frederick W. Whiting private land claim (sec. 47), hereinbefore described.

Dependent Resurvey of a Portion of Section 46,  
T. 6 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS																	
11.18	<p>S. 89° 40' W., along line 2-3 of sec. 46.</p> <p>Point for Cor. No. 3 of the A. Wayne Johnson private land claim (sec. 46), identical with Cor. No. 3 of the Aaron Johnson private land claim (sec. 45), at proportionate distance based on the Grant Boundary Method; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td></td><td> </td><td>AP 3</td></tr> <tr><td></td><td> </td><td>S 46</td></tr> <tr><td>S 42</td><td> </td><td>AP 3</td></tr> <tr><td></td><td> </td><td>S 45</td></tr> <tr><td></td><td></td><td>1983</td></tr> </table> <hr style="width: 10%; margin: 0 auto;"/> </div>			AP 3			S 46	S 42		AP 3			S 45			1983	
		AP 3															
		S 46															
S 42		AP 3															
		S 45															
		1983															
4.85	<p>N. 4° 05' E., along line 3-4 of sec. 46.</p> <p>Point for Cor. No. 4 of the A. Wayne Johnson private land claim (sec. 46), identical with Cor. No. 1 of the Joseph H. Curtis private land claim (sec. 42), at proportionate distance based on the Grant Boundary Method; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td></td><td></td><td>T 6 S R 4 E</td></tr> <tr><td></td><td></td><td>AP 4</td></tr> <tr><td></td><td>AP 1</td><td>  S 46</td></tr> <tr><td></td><td>S 42</td><td> </td></tr> <tr><td></td><td></td><td>1983</td></tr> </table> <hr style="width: 10%; margin: 0 auto;"/> </div>			T 6 S R 4 E			AP 4		AP 1	S 46		S 42				1983	
		T 6 S R 4 E															
		AP 4															
	AP 1	S 46															
	S 42																
		1983															
17.605	<p>S. 89° 40' W., along line 4-5 of sec. 46.</p> <p>Point for the 1 mile cor. of the A. Wayne Johnson private land claim (sec. 46) at proportionate distance; there is no remaining evidence of the original corner; not monumented.</p>																
21.76	<p>Point for Cor. No. 5 of the A. Wayne Johnson private land claim (sec. 46), identical with Cor. No. 1 of the A. Milton Curtis private land claim (sec. 40); heretofore described.</p>																
12.96	<p>N. 0° 10' W., along line 5-6 of sec. 46.</p> <p>Cor. No. 6 of the A. Wayne Johnson private land claim (sec. 46), identical with Cor. No. 8 of the A. Milton Curtis private land claim (sec. 40), monumented with a quartzite stone, 22 x 12 x 8 ins., firmly set 18 ins. in the ground, mkd. 6 AWJ on the E face, with an embedded mound of stone to the E.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td></td><td></td><td>T 6 S R 4 E</td></tr> <tr><td></td><td>AP 8</td><td>AP 6</td></tr> <tr><td></td><td>S 40</td><td>S 46</td></tr> <tr><td></td><td></td><td>1983</td></tr> </table> </div>			T 6 S R 4 E		AP 8	AP 6		S 40	S 46			1983				
		T 6 S R 4 E															
	AP 8	AP 6															
	S 40	S 46															
		1983															

Dependent Resurvey of a Portion of Section 46,  
T. 6 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS											
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, E of cor. Bury the mkd. stone alongside the aluminum post.</p> <hr/> <p>N. 13° 31' E., along line 6-7 of sec. 46.</p>										
22.53	<p>The 1 1/2 mile cor. of the A. Wayne Johnson private land claim (sec. 46), monumented with a sandstone, 18 x 8 x 6 ins., firmly set 12 ins. in the ground, mkd. 1/2 M AWJ on the E face.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T 6 S R 4 E</td><td></td></tr> <tr><td></td><td>  1 1/2</td></tr> <tr><td>S 40</td><td>  S 46</td></tr> <tr><td></td><td>1983</td></tr> </table> </div> <hr/> <p>N. 15° 12' E., beginning new measurement.</p>	T 6 S R 4 E			1 1/2	S 40	S 46		1983		
T 6 S R 4 E											
	1 1/2										
S 40	S 46										
	1983										
2.83	<p>Cor. No. 7 of the A. Wayne Johnson private land claim (sec. 46), monumented with a limestone, 18 x 10 x 8 ins., firmly set 12 ins. in the ground, dimly mkd. 7 AMC on the E face.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T 6 S R 4 E</td><td></td></tr> <tr><td></td><td>  S 35</td></tr> <tr><td>S 40</td><td>  AP 7</td></tr> <tr><td></td><td>  S 46</td></tr> <tr><td></td><td>1983</td></tr> </table> </div> <hr/> <p>Bury the mkd. stone alongside the aluminum post.</p>	T 6 S R 4 E			S 35	S 40	AP 7		S 46		1983
T 6 S R 4 E											
	S 35										
S 40	AP 7										
	S 46										
	1983										
37.12	<p>N. 88° 43' E., along line 7-1 of sec. 46.</p> <p>The 2 mile cor. of the A. Wayne Johnson private land claim (sec. 46), monumented with a sandstone, 26 x 12 x 8 ins., firmly set 18 ins. in the ground, mkd. 2 M AWJ on the S face, with a mound of stone to the S.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T 6 S R 4 E</td><td></td></tr> <tr><td></td><td>2 M</td></tr> <tr><td></td><td>S 46</td></tr> <tr><td></td><td>1983</td></tr> </table> </div> <hr/> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, S of cor.</p>	T 6 S R 4 E			2 M		S 46		1983		
T 6 S R 4 E											
	2 M										
	S 46										
	1983										

Dependent Resurvey of a Portion of Section 46,  
T. 6 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
6.24	<p>Invert the mkd. stone alongside the aluminum post.</p> <p style="text-align: center;">_____</p> <p>S. 89° 55' E., beginning new measurement.</p> <p>Cor. No. 1 of the A. Wayne Johnson private land claim (sec. 46).</p>
<p>Survey of the Subdivision of Section 34, T. 6 S., R. 4 E., Salt Lake Meridian, Utah</p>	
19.935	<p>From the 1/4 sec. cor. of secs. 3 and 34, Tps., 6 and 7 S., R. 4 E., heretofore described.</p> <p>N. 0° 01' W., on the N-S center line of sec. 34.</p> <p>Point for the S 1/16 sec. cor. of sec. 34; not monumented.</p>
38.77	<p>Intersect line 1-7 of the Joseph H. Curtis private land claim (sec. 42).</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 6 S R 4 E</p> <p>  C</p> <p>S   34</p> <p>S   42</p> <p>  C</p> <p>1983</p> </div>
39.87	<p>Point for the center 1/4 sec. cor. of sec. 34, at intersection with the E-W center line.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 6 S R 4 E</p> <p>  C 1/4 S 34</p> <p>1983</p> </div>
59.795	<p>Point for the center N 1/16 sec. cor. of sec. 34.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>  C</p> <p>N 1/16   S 34</p> <p>  C</p> <p>1983</p> </div> <p>From this cor., a galvanized pipe, 2 ins. diam., firmly set by Parley Neeley in 1959, LS No. 1722, projecting 8 ins. above the ground, with a galvanized cap mkd. 1722 CN 1/16 S34 T6S R4E 1959, bears S. 82° W., 25 lks. dist. This position was established using improper procedures and is not utilized in the course of this survey.</p>

Survey of the Subdivision of Section 34,  
T. 6 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	
79.72	The 1/4 sec. cor. of secs. 27 and 34.
19.865	<p>From the 1/4 sec. cor. of secs. 34 and 35 N. 89° 59' W., on the E-W center line of sec. 34.</p> <p>Point for the center E 1/16 sec. cor. of sec. 34.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">E 1/16 C ——— S 34 ——— C 1983</p> <p>Set a steel fence post alongside the aluminum post.</p> <p>From this cor., a steel pipe, 2 ins. diam., firmly set by Parley Neeley, R.L.S. No. 1722 in 1958, projecting 8 ins. above the ground, and in a collar of stone, with a steel cap mkd. 1722 CE 1/16 S34 T6S R4E, bears N. 58° E., 7 lks. dist. This position was established using improper procedures and is not utilized in the course of this survey.</p>
39.73	The center 1/4 sec. cor. of sec. 34.
59.505	<p>Point for the center W 1/16 sec. cor. of sec. 34.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">W 1/16 C ——— S 34 ——— C 1983</p> <p>From this cor., a galvanized pipe, 2 ins. diam., firmly set, projecting 8 ins. above the ground, with galvanized cap mkd. CW 1/16 S34 1722, bears N. 62° E., 23 lks. dist. This monument was established by Parley Neeley, R.L.S., No. 1722 in 1958 using improper procedures and is not utilized in the course of this survey.</p>
79.28	The 1/4 sec. cor. of secs. 33 and 34.
19.96	<p>From the center E 1/16 sec. cor. of sec. 34. N. 0° 09' W., on the N-S center line of the NE 1/4 of sec. 34.</p> <p>Point for the NE 1/16 sec. cor. of sec. 34, at intersection with the E-W center line of the NE 1/4.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">NE 1/16 S 34 1983</p>

Survey of the Subdivision of Section 34,  
T. 6 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS							
39.92	<p>From this cor., a galvanized pipe, 2 ins. diam., firmly set, projecting 6 ins. above the ground, and in a collar of stone, with galvanized cap mkd. 1722 NE 1/16 S34 1959, bears S. 25° W., 34 lks. dist. This monument was established by Parley Neeley, R.L.S. No. 1722, in 1959, using improper procedures and is not utilized in the course of this survey.</p> <p>Point for the E 1/16 sec. cor. of secs. 27 and 34.</p>						
19.84	<p>From the N 1/16 sec. cor. of secs. 34 and 35.</p> <p>S. 89° 52' W., on the E-W center line of the NE 1/4 of sec. 34.</p> <p>The NE 1/16 sec. cor. of sec. 34.</p>						
39.68	<p>The center N 1/16 sec. cor. of sec. 34.</p>						
38.72	<p>From the point for the E 1/16 sec. cor. of secs. 3 and 34, Tps. 6 and 7 S., R. 4 E., heretofore described.</p> <p>N. 0° 09' W., on the N-S center line of the SE 1/4 of sec. 34.</p> <p>Intersect line 7-1 of the Joseph H. Curtis private land claim (sec. 42).</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam. 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;"> <table border="1" style="margin-left: auto; margin-right: auto;"> <tr><td>S</td><td>34</td></tr> <tr><td>S</td><td>42</td></tr> <tr><td colspan="2" style="text-align: center;">1983</td></tr> </table> </p> <p>The center E 1/16 sec. cor. of sec. 34.</p>	S	34	S	42	1983	
S	34						
S	42						
1983							
19.93	<p>From the point for the W 1/16 sec. cor. of secs. 3 and 34, Tps. 6 and 7 S., R. 4 E., heretofore described.</p> <p>N. 0° 02' W., on the N-S center line of the SW 1/4 of sec. 34.</p> <p>Point for the SW 1/16 sec. cor. of sec. 34, at intersection with the E-W center line of the SW 1/4.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;"> <table border="1" style="margin-left: auto; margin-right: auto;"> <tr><td>SW 1/16</td><td>S 34</td></tr> <tr><td colspan="2" style="text-align: center;">1983</td></tr> </table> </p> <p>From this cor., a galvanized pipe, 2 ins. diam., firmly set, projecting 6 ins. above the ground, and in a collar of stone, with galvanized cap mkd. SW 1/16 S34 1722, bears N. 80° E., 20 lks. dist. This monument was established by Parley Neeley, R.L.S. No. 1722 in 1959, using improper procedures and is not utilized in the course of this survey.</p>	SW 1/16	S 34	1983			
SW 1/16	S 34						
1983							

Survey of the Subdivision of Section 34,  
T. 6 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS	The center W 1/16 sec. cor. of sec. 34.
39.86	From the point for the center S 1/16 sec. cor. of sec. 34. N. 89° 53' W., on the E-W center line of the SW 1/4 of sec. 34.
19.80	The SW 1/16 sec. cor. of sec. 34.
39.58	The S 1/16 sec. cor. of secs. 33 and 34.
General Description	
<p>The area surveyed lies in the Left Fork of Hobble Creek Canyon in the Wasatch Range approximately 8 miles NE of Springville, Utah. The elevation varies from 5800 to 8000 ft. above sea level. The terrain is mountainous with the exception of a cultivated field in section 35. Scrub oak dominates the vegetation. Whitemore, Dry and Berryport Canyons drain southerly through the surveyed area to the Left Fork of Hobble Creek.</p>	
<p>Improvements include two buildings and an earthen dam in Berryport Canyon and a water line in Hobble Creek Canyon.</p>	





CERTIFICATE OF SURVEY

(I) ~~was~~ Gary L. Kratz, Supervisory Cadastral Surveyor, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 23rd day

of May, 19 83, (I) ~~was~~ have dependently resurveyed a portion of the south boundary, a portion of the east boundary, a portion of the subdivisional lines and a portion of the private land claims with a subdivision survey of section 34 in T. 6 S., R. 4 E.,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), ~~was~~ and under (my) ~~was~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

June 15, 1985 (Date) [Signature of Gary L. Kratz] (Cadastral Surveyor) Supervisory

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Washington, D.C.

The foregoing field notes of the dependent resurvey of a portion of the south boundary, a portion of the east boundary, a portion of the subdivisional lines and a portion of the private land claims with a subdivision survey of section 34 in T. 6 S., R. 4 E., Salt Lake Meridian, Utah

executed by Gary L. Kratz, Supervisory Cadastral Surveyor having been critically examined and found correct, are hereby approved.

November 5, 1985 (Date) [Signature of Glen B. Hatch] Chief Cadastral Surveyor for Utah

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

[Signature] Chief Cadastral Surveyor for Utah

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

RG08

ORIGINAL  
FIELD NOTES

197

OF THE

DEPENDENT RESURVEY

OF THE

NORTH FIVE MILES OF THE WEST BOUNDARY

(THE GUIDE MERIDIAN WEST),

THE SOUTH BOUNDARY,

AND A PORTION OF THE NORTH BOUNDARY,

AND

PORTIONS OF THE SUBDIVISIONAL LINES,

OF

TOWNSHIP 11 NORTH, RANGE 14 WEST

Of the Salt Lake Meridian,

In the State of Utah

EXECUTED BY

Frank C. Profaizer, Jr. Supervisory Cadastral Surveyor

Under special instructions dated December 15, 19 82, approved December 17, 1982.

\_\_\_\_\_, which provided for the surveys included under U.S. ~~Survey~~ Group  
Number 625, and assignment instructions dated October 19, 19 83.

Survey commenced October 24, 19 83

Survey completed July 6, 19 84

# INDEX DIAGRAM

Township 11 North, Range 14 West

5 37	37 36	30 30	26 26	21 20	15 15
4 35	36 35	29 16	25 25	20 19	14 14
3 34	34 34	16	15 24	19 19	13 13
3 33	33 32	29 28	23 23	18 18	12 12
2 31	32 29	28 27	22 22	17 17	11 11
31 8	32 8	27 7	21 7	16 6	10 5

## Township 11 North, Range 14 West, Salt Lake Meridian, Utah

CHAINS

The following field notes describe the dependent resurvey of the north five miles of the west boundary (The Guide Meridian West), the south boundary, a portion of the north boundary, and portions of the subdivisional lines of Township 11 North, Range 14 West, Salt Lake Meridian, Utah.

History of Surveys

		<u>Surveyed by</u>	<u>Retr. or Resurveyed by</u>	
--	--	--------------------	-------------------------------	--

WEST BOUNDARY (Guide Meridian)

A11	G. Boutelle	1872		
-----	-------------	------	--	--

SOUTH BOUNDARY

A11	G. Boutelle	1875		
A11			H. Fitzhugh	1883

EAST BOUNDARY

A11	H. Fitzhugh	1883		
A11			F. Chappell	1967

NORTH BOUNDARY

A11	G. Boutelle	1872		
A11			H. Fitzhugh	1884
A11			F.C. Profaizer, Jr	Concurrently

SUBDIVISION

A11	H. Fitzhugh	1884		
-----	-------------	------	--	--

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group 625, Utah, dated December 15, 1982.

The directions of lines were determined by reference to true meridians established on line by altitude observations on the sun, and by hour angle observations on Polaris. The lines were carried forward by sustained angulations, being supplemented by other observations on Polaris taken throughout the progress of the survey. Distances were determined by electronic measurement.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions, lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the SE cor. of the township as determined from a tie made to U.S.G.S. triangulation station "ANTS 1957", located in section 20, T. 11 N., R. 14 W., Salt Lake Meridian, is as follows:

Latitude 41° 37' 40.209" N. Longitude 113° 23' 07.967" W.

## Township 11 North, Range 14 West, Salt Lake Meridian, Utah

## CHAINS

The mean magnetic declination, as projected from the U.S. Geological Survey Magnetic Declination Map of 1980, is 15° 30' E.

Dependent Resurvey of the North Five Miles of the West Boundary (The Guide Meridian West),  
T. 11 N., R. 14 W., Salt Lake Meridian, Utah

(Restoring the Survey Executed by  
G. Boutelle in 1872)

Beginning at the cor. of secs. 25, 30, 31, and 36, monumented with a sandstone, 26 x 20 x 7 ins., (record, 26 x 12 x 10 ins.), loosely set in a mound of stone, 2 1/2 ft. base. No visible marks on the stone.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a mound of stone, 2 1/2 ft. base, to top of aluminum cap, mkd.

T 11 N	
R 15 W	R 14 W
S 25	S 30
S 36	S 31
1983	

Deposit the mkd. stone alongside the aluminum post.

N. 0° 18.6' W., bet. secs. 25 and 30.

39.429 The 1/4 sec. cor. of secs. 25 and 30, monumented with a weathered wooden post, 29 ins. long, projecting 19 ins. above ground, mkd. 1/4 on E face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 11 N	
R 15 W	R 14 W
1/4	
S 25	S 30
1983	

Deposit the wooden post alongside the aluminum post.

N. 1° 24.3' W., beginning new measurement.

40.863 The cor. of secs. 19, 24, 25, and 30, monumented with a weathered wooden post, 26 ins. long, projecting 16 ins. above ground, with no visible marks on the post. Also found iron pipe, 1 1/2 ins. diam., projecting 2 ft. above ground alongside post.

Dependent Resurvey of the North Five Miles of the  
West Boundary (The Guide Meridian West),  
T. 11 N., R. 14 W., Salt Lake Meridian, Utah

CHAINS	
	<p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 11 N R 15 W R 14 W S 24   S 19 S 25   S 30 1983</p> </div> <p>Deposit the wooden post and pipe alongside the aluminum post.</p>
38.987	<p>N. 0° 03.4' E., bet. secs. 19 and 24.</p> <p>The 1/4 sec. cor. of secs. 19 and 24, monumented with a weathered wooden post, 2 ins. sq., 30 ins. long, projecting 18 ins. above ground. No visible marks on the post.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 11 N R 15 W R 14 W 1/4 S 24   S 19 1983</p> </div> <p>Deposit the wooden post alongside the aluminum post.</p>
40.025	<p>N. 0° 30.0' W., beginning new measurement.</p> <p>The cor. of secs. 13, 18, 19, and 24, monumented with a weathered wooden post, 18 ins. long, projecting 9 ins. above ground, with no visible marks on the post. Also found iron pipe, 1 1/2 ins. diam., projecting 2 ft. above ground alongside post.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 11 N R 15 W R 14 W S 13   S 18 S 24   S 19 1983</p> </div> <p>Deposit the wooden post and pipe alongside the aluminum post.</p>
39.993	<p>N. 0° 16.4' W., bet. secs. 13 and 18.</p> <p>The 1/4 sec. cor. of secs. 13 and 18, monumented with a weathered wooden post, 28 ins. long, projecting 16 ins. above ground, with no visible marks on the post.</p>

Dependent Resurvey of the North Five Miles of the  
West Boundary (The Guide Meridian West),  
T. 11 N., R. 14 W., Salt Lake Meridian, Utah

CHAINS	
40.190	<p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 11 N R 15 W R 14 W 1/4 S 13   S 18 1983</p> </div> <p>Deposit the wooden post alongside the aluminum post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 22.7' W., beginning new measurement.</p> <p>Point for the cor. of secs. 7, 12, 13, and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 11 N R 15 W R 14 W S 12   S 7 S 13   S 18 1983</p> </div>
40.176	<p>N. 0° 22.7' W., bet. secs. 7 and 12.</p> <p>The 1/4 sec. cor. of secs. 7 and 12, monumented with a weathered wooden post, 19 ins. long, projecting 10 ins. above ground, and mkd. 1/4 on E face.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 11 N R 15 W R 14 W 1/4 S 12   S 7 1983</p> </div> <p>Deposit the mkd. stone alongside the aluminum post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 16.0' W., beginning new measurement.</p> <p>The cor. of secs. 1, 6, 7, and 12, monumented with a weathered wooden post, 32 ins. long, projecting 20 ins. above ground, mkd. 5 grooves on S and 1 groove on N side. Also found iron pipe, 1 1/2 ins. diam., projecting 30 ins. above ground alongside wooden post.</p>

Dependent Resurvey of the North Five Miles of the  
West Boundary (The Guide Meridian West),  
T. 11 N., R. 14 W., Salt Lake Meridian, Utah

CHAINS

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 11 N  
R 15 W R 14 W  
S 1 | S 6  
S 12 | S 7  
1983

Deposit the wooden post and iron pipe alongside the aluminum post.

N. 0° 26.4' W., bet. secs. 1 and 6.

40.152

The 1/4 sec. cor. of secs. 1 and 6, monumented with a weathered wooden post, 22 ins. long, projecting 12 ins. above ground, mkd. 1/4 on E face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 11 N  
R 15 W R 14 W  
1/4  
S 1 | S 6  
1983

Deposit the wooden post alongside the aluminum post.

N. 0° 10.3' W., beginning new measurement.

40.126

The cor. of Tps. 11 and 12 N., Rs. 14 and 15 W., monumented with an aluminum post, 2 1/2 ins. diam., projecting 6 ins. above ground, with aluminum cap mkd. as described in the field notes of T. 12 N., R. 14 W., executed concurrently under this same group.

Dependent Resurvey of the South Boundary,  
T. 11 N., R. 14 W., Salt Lake Meridian, Utah

(Restoring the Survey Executed by  
G. Boutelle in 1875 and the Resurvey by  
H. Fitzhugh in 1883)

From the cor. of Tps. 10 and 11 N., Rs. 13 and 14 W., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap, mkd. as described in the official record of the 1967 resurvey.

S. 89° 01.7' W., bet. secs. 1 and 36.

Dependent Resurvey of the South Boundary,  
T. 11 N., R. 14 W., Salt Lake Meridian, Utah

CHAINS		
40.100	<p>Point for the 1/4 sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 11 N R 14 W S 36 1/4 <u>S T</u> T 10 N R 14 W 1984</p>	
80.200	<p>The cor. of secs. 1, 2, 35, and 36, monumented with a deteriorated wooden post, 36 ins. long, projecting 21 ins. above ground, mkd. T11N R14W.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 11 N R 14 W S 35   S 36 S 2   S 1 T 10 N R 14 W 1983</p> <p>Deposit the mkd. wooden post alongside the aluminum post.</p>	
40.680	<p>N. 89° 53.8' W., bet. secs. 2 and 35.</p> <p>The 1/4 sec. cor. of secs. 2 and 35, monumented with a lava stone, 10 x 7 x 4 ins., (record, 13 x 8 x 6 ins.), firmly set, projecting 5 ins. above ground, with no visible marks on stone, and in a collar of stone. This position is harmoniously related to existing original corners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 11 N R 14 W S 35 1/4 <u>S 2</u> T 10 N R 14 W 1983</p> <p>Deposit the stone alongside the aluminum post.</p>	
40.064	<p>S. 89° 15.6' W., beginning new measurement.</p> <p>The cor. of secs. 2, 3, 34, and 35, monumented with a lava stone, 19 x 7 x 5 ins., (record, 27 x 9 x 5 ins.), firmly set and projecting 7 ins. above ground, with no visible marks on the stone. Also found iron pipe, 1 1/2 ins. diam., projecting 2 ft. above ground alongside stone.</p>	

Dependent Resurvey of the South Boundary,  
T. 11 N., R. 14 W., Salt Lake Meridian, Utah

CHAINS

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

$$\begin{array}{r} T 11 N R 14 W \\ \hline S 34 \quad | \quad S 35 \\ \hline S 3 \quad | \quad S 2 \\ T 10 N R 14 W \\ 1983 \end{array}$$

Deposit the stone and pipe alongside the aluminum post.

N. 89° 27.3' W., bet. secs. 3 and 34.

40.025 The 1/4 sec. cor. of secs. 3 and 34, monumented with a limestone, 12 x 7x 7 ins., (record, 12 x 8 x 4 ins.), firmly set, projecting 6 ins. above ground, mkd. 1/4 on N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

$$\begin{array}{r} T 11 N R 14 W \\ \hline S 34 \\ 1/4 \quad \hline S 3 \\ T 10 N R 14 W \\ 1983 \end{array}$$

Deposit the mkd. stone alongside the aluminum post.

S. 89° 05.2' W., beginning new measurement.

40.018 Point for the cor. of secs. 3, 4, 33, and 34, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

$$\begin{array}{r} T 11 N R 14 W \\ \hline S 33 \quad | \quad S 34 \\ \hline S 4 \quad | \quad S 3 \\ T 10 N R 14 W \\ 1983 \end{array}$$

S. 89° 05.2' W., bet. secs. 4 and 33.

39.018 Point selected for the witness cor. to the 1/4 sec. cor. of secs. 4 and 33.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

$$\begin{array}{r} W C \\ T 11 N R 14 W \\ \hline S 33 \\ 1/4 \quad \leftarrow S 4 \\ T 10 N R 14 W \\ 1984 \end{array}$$

Dependent Resurvey of the South Boundary,  
T. 11 N., R. 14 W., Salt Lake Meridian, Utah

CHAINS	
40.018	<p>True point for the 1/4 sec. cor. of secs. 4 and 33, at proportionate distance; there is no remaining evidence of the original corner. The cor. point falls on rock outcrop unsuitable for monumentation.</p>
80.036	<p>Point for the cor. of secs. 4, 5, 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> $\begin{array}{r} T\ 11\ N\ R\ 14\ W \\ \hline S\ 32\   \ S\ 33 \\ \hline S\ 5\   \ S\ 4 \\ T\ 10\ N\ R\ 14\ W \\ 1984 \end{array}$
<p>S. 89° 05.2' W., bet. secs. 5 and 32.</p>	
40.018	<p>Point for the 1/4 sec. cor. of secs. 5 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> $\begin{array}{r} T\ 11\ N\ R\ 14\ W \\ \hline S\ 32 \\ 1/4 \quad \hline S\ 5 \\ T\ 10\ N\ R\ 14\ W \\ 1984 \end{array}$
80.036	<p>Point for the cor. of secs. 5, 6, 31, and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> $\begin{array}{r} T\ 11\ N\ R\ 14\ W \\ \hline S\ 31\   \ S\ 32 \\ \hline S\ 6\   \ S\ 5 \\ T\ 10\ N\ R\ 14\ W \\ 1984 \end{array}$
<p>S. 89° 05.2' W., bet. secs. 6 and 31.</p>	
40.018	<p>Point for the 1/4 sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> $\begin{array}{r} T\ 11\ N\ R\ 14\ W \\ \hline S\ 31 \\ 1/4 \quad \hline S\ 6 \\ T\ 10\ N\ R\ 14\ W \\ 1984 \end{array}$

Dependent Resurvey of the South Boundary,  
T. 11 N., R. 14 W., Salt Lake Meridian, Utah

<p>CHAINS 80.716</p>	<p>The cor. of Tps. 10 and 11 N., Rs. 14 and 15 W., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1967 resurvey of T. 10 N., R. 15 W.</p>
	<p>Dependent Resurvey of a Portion of the North Boundary, T. 11 N., R. 14 W., Salt Lake Meridian, Utah</p>
	<p>From the closing cor. of secs. 3 and 4, on the N. bdy. of the Tp., hereinafter described.  S. 89° 26.6' W., on the N. bdy. of sec. 4.</p>
<p>27.712</p>	<p>The 1/4 sec. cor. of secs. 33 only, monumented with an aluminum post, 2 1/2 ins. diam., projecting 6 ins. above ground, with aluminum cap, mkd. as described in T. 12 N., R. 14 W., executed concurrently under this same group.  S. 89° 22.9' W., beginning new measurement.</p>
<p>12.401</p>	<p>Point for the 1/4 sec. cor. of sec. 4 only, T. 11 N., R. 14 W., at midpoint on the N. bdy. of sec. 4.  Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.  T 12 N R 14 W <hr/>1/4 S 4 T 11 N R 14 W 1984</p>
<p>40.163</p>	<p>The cor. of secs. 32 and 33, monumented with an aluminum post, 2 1/2 ins. diam., projecting 6 ins. above ground, with aluminum cap, mkd. as described in T. 12 N., R. 14 W., executed concurrently under this same group.  S. 89° 22.9' W., on the N. bdy. of sec. 4.</p>
<p>12.351</p>	<p>The closing cor. of secs. 4 and 5, hereinafter described.  From the closing cor. of secs. 5 and 6, on the N. bdy. of the Tp., hereinafter described.  S. 89° 20.4' W., on the N. bdy. of sec. 6.</p>
<p>29.339</p>	<p>The 1/4 sec. cor. of sec. 31 only, monumented with an aluminum post, 2 1/2 ins. diam., projecting 6 ins. above ground, with aluminum cap, mkd. as described in T. 12 N., R. 14 W., executed concurrently under this same group.  S. 89° 19.8' W., beginning new measurement.</p>
<p>10.860</p>	<p>Point for the 1/4 sec. cor. of sec. 6 only, T. 11 N., R. 14 W., at proportionate distance and on the N. bdy. of sec. 6.</p>

Dependent Resurvey of a Portion of the North Boundary,  
T. 11 N., R. 14 W., Salt Lake Meridian, Utah

## CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 12 N R 14 W

1/4 S 6  
T 11 N R 14 W  
1984

48.515 The cor. of Tps. 11 and 12 N., Rs. 14 and 15 W., described in T. 12 N., R. 14 W., executed concurrently under this same group.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 11 N., R. 14 W., Salt Lake Meridian, Utah

(Restoring the Survey Executed by  
H. Fitzhugh in 1884)

From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., heretofore described.

N. 3° 18.4' W., bet. secs. 35 and 36.

41.411 The 1/4 sec. cor. of secs. 35 and 36, monumented with a lava stone, loosely set, 11 x 9 x 5 ins., projecting 5 ins. above ground, and mkd. 1/4 on W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 11 N R 14 W  
1/4  
S 35 | S 36  
1983

Deposit the mkd. stone alongside the aluminum post.

N. 0° 38.9' W., beginning new measurement.

40.388 The cor. of secs. 25, 26, 35, and 36, monumented with an unmkd. limestone, 12 x 9 x 4 ins., firmly set and projecting 6 ins. above ground, with 1 1/2 in. iron pipe alongside, projecting 30 ins. above ground.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 11 N R 14 W  
S 26 | S 25  
S 35 | S 36  
1983

Deposit the stone and iron pipe alongside the aluminum post.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 11 N., R. 14 W., Salt Lake Meridian, Utah

CHAINS	
	<p>From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap, mkd. as described in the official record of the 1967 resurvey of T. 11 N., R. 13 W.</p> <p>N. 89° 40.8' W., bet. secs. 25 and 36.</p>
40.366	<p>The 1/4 sec. cor. of secs. 25 and 36, monumented with a limestone, 9 x 5 x 3 ins., firmly set, projecting 4 ins. above ground, mkd. 1/4 on N face.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 11 N R 14 W</p> <p>    S 25</p> <hr style="width: 50px; margin: 0 auto;"/> <p>1/4     S 36</p> <p>          1983</p> </div> <p>Deposit the mkd. stone alongside the aluminum post.</p> <hr style="width: 200px; margin: 10px auto;"/> <p>S. 89° 21.5' W., beginning new measurement.</p>
40.993	<p>The cor. of secs. 25, 26, 35, and 36.</p>
40.077	<p>N. 0° 26.4' W., bet. secs. 25 and 26.</p> <p>Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 11 N R 14 W</p> <p>    1/4</p> <p>     </p> <p>S 26   S 25</p> <p>     </p> <p>    1984</p> </div>
80.154	<p>The cor. of secs. 23, 24, 25, and 26, monumented with a limestone, 15 x 6 x 4 ins., firmly set, projecting 8 ins. above ground, mkd. 2 notches on S and 1 notch on E, with 1 1/2 in. iron pipe alongside and projecting 22 ins. above ground.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 11 N R 14 W</p> <p>  S 23   S 24</p> <hr style="width: 50px; margin: 0 auto;"/> <p>  S 26   S 25</p> <p>          1983</p> </div>

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 11 N., R. 14 W., Salt Lake Meridian, Utah

CHAINS	
40.348	<p>Deposit the mkd. stone and iron pipe alongside the aluminum post.</p> <hr/> <p>From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set. projecting 6 ins. above ground, with brass cap, mkd. as described in the 1967 resurvey of T. 11 N., R. 13 W.</p> <p>S. 89° 36.5' W., bet. secs. 24 and 25.</p> <p>Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 11 N R 14 W</p> <p>1/4      S 24</p> <p>          S 25</p> <p>          1984</p> </div>
80.696	<p>The cor. of secs. 23, 24, 25, and 26.</p> <hr/> <p>N. 1° 01.1' W., bet. secs. 23 and 24.</p> <p>The 1/4 sec. cor. of secs. 23 and 24, monumented with a limestone, 9 x 8 x 8 ins., firmly set and projecting 4 ins. above ground, mkd. 1/4 on W face.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 11 N R 14 W</p> <p>1/4</p> <p>S 23   S 24</p> <p>1983</p> </div> <p>Deposit the mkd. stone alongside the aluminum post.</p> <p>From this point, a private survey cor. for the 1/4 sec. cor. of secs. 23 and 24, bears S. 85° E., 0.294 chs. dist., monumented with an iron post, 2 ins. diam., firmly set. projecting 4 ins. above ground, with 3 1/2 ins. brass cap, mkd.</p> <div style="text-align: center;"> <p>T 11 N R 14 W</p> <p>1/4</p> <p>S 23   S 24</p> <p>1979</p> <p>CJS-LS 2868</p> </div> <hr/> <p>N. 0° 07.8' W., beginning new measurement.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 11 N., R. 14 W., Salt Lake Meridian, Utah

CHAINS  
40.195

The cor. of secs. 13, 14, 23, and 24, monumented with a limestone, 11 x 6 x 5 ins., firmly set, projecting 6 ins. above ground, mkd. 3 grooves on S and 1 groove on E face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 11 N R 14 W  
S 14 | S 13  
S 23 | S 24  
1983

Deposit the mkd. stone alongside the aluminum post.

---

From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 14 ins. above ground, and in a collar of stone, with brass cap, mkd. as described in the official record of the 1967 resurvey of T. 11 N., R. 13 W.

S. 89° 47.0' W., bet. secs. 13 and 24.

40.359

Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 11 N R 14 W  
S 13  
1/4 S 24  
1983

80.729

The cor. of secs. 13, 14, 23, and 24.

---

N. 0° 58.0' W., bet. secs. 13 and 14.

40.147

The 1/4 sec. cor. of secs. 13 and 14, monumented with a limestone, 16 x 7 x 4 ins., mkd. 1/4 on W face, firmly set, projecting 7 ins. above ground, and in a collar of stone.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 11 N R 14 W  
1/4  
S 14 | S 13  
1984

Deposit the mkd. stone alongside the aluminum post.

---

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 11 N., R. 14 W., Salt Lake Meridian, Utah

CHAINS					
40.123	<p>N. 0° 25.8' W., beginning new measurement.</p> <p>The cor. of secs. 11, 12, 13, and 14, monumented with a limestone, 12 x 7 x 3 ins., mkd. 4 notches on S edge and 1 notch on E edge, firmly set, projecting 6 ins. above ground, and in a collar of stone.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T 11 N R 14 W</td></tr> <tr><td>S 11   S 12</td></tr> <tr><td>S 14   S 13</td></tr> <tr><td>1984</td></tr> </table> </div> <p>Deposit the mkd. stone alongside the aluminum post.</p>	T 11 N R 14 W	S 11   S 12	S 14   S 13	1984
T 11 N R 14 W					
S 11   S 12					
S 14   S 13					
1984					
40.152	<p>From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above ground, and in a collar of stone, with brass cap, mkd. as described in the official record of the 1967 resurvey of T. 11 N., R. 13 W.</p> <p>S. 89° 46.1' W., bet. secs. 12 and 13.</p> <p>The 1/4 sec. cor. of secs. 12 and 13, monumented with a limestone, 14 x 8 x 5 ins., mkd. 1/4 on N face, firmly set, projecting 7 ins. above ground, and in a collar of stone.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T 11 N R 14 W</td></tr> <tr><td>1/4 S 12</td></tr> <tr><td>S 13</td></tr> <tr><td>1984</td></tr> </table> </div> <p>Deposit the mkd. stone alongside the aluminum post.</p>	T 11 N R 14 W	1/4 S 12	S 13	1984
T 11 N R 14 W					
1/4 S 12					
S 13					
1984					
40.176	<p>S. 89° 30.2' W., beginning new measurement.</p> <p>The cor. of secs. 11, 12, 13, and 14.</p>				
40.143	<p>N. 0° 39.4' W., bet. secs. 11 and 12.</p> <p>Point for the 1/4 sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>				

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 11 N., R. 14 W., Salt Lake Meridian, Utah

CHAINS	
80.286	<p style="text-align: center;">T 11 N R 14 W 1/4 S 11   S 12 1984</p> <p>Point for the cor. of secs. 1, 2, 11, and 12, at proportionate distance; found limestone, 12 x 8 x 3 ins., mkd. 5 grooves on one face and 1 groove on another face, laying loose in agricultural activity of adjacent landowner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 11 N R 14 W S 2   S 1 S 11   S 12 1984</p> <p>Deposit the mkd. stone alongside the aluminum post.</p>
40.349	<p>From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 13 ins. above ground, and in a collar of stone, with brass cap, mkd. as described in the official record of the 1967 resurvey of T. 11 N., R. 13 W.</p> <p>S. 89° 24.7' W., bet. secs. 1 and 12.</p> <p>Point for the 1/4 sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>
80.708	<p style="text-align: center;">T 11 N R 14 W S 1 1/4     S 12 1984</p> <p>The cor. of secs. 1, 2, 11 and 12.</p>
40.147	<p>N. 1° 06.2' E., bet. secs. 1 and 2.</p> <p>The 1/4 sec. cor. of secs. 1 and 2, monumented with a weathered wooden post, 30 ins. long, shaved on one side, with no visible marks. Loosely set and projecting 15 ins. above ground. This point is accepted as a careful and faithful determination of the original corner position.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 11 N., R. 14 W., Salt Lake Meridian, Utah

CHAINS

T 11 N R 14 W  
1/4  
S 2 | S 1  
1984

Deposit the wooden post alongside the aluminum post.

N.  $0^{\circ}$  07.6' W., beginning new measurement.

36.282 The closing cor. of secs. 1 and 2, monumented with a sandstone, 19 x 8 x 3 ins., loosely set, projecting 9 ins. above ground, with no visible marks on stone. Also found weathered wooden post with 5 notches on S side and projecting 5 ft. above ground on side of stone. Bury the stone 6 ins. below the surface of the ground. This now becomes an amended monument.

36.898 Point for the closing cor. of secs. 1 and 2, at intersection with the S. bdy. of T. 12 N., R. 14 W.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 12 N R 14 W  
S 35  
S 2 | S 1  
T 11 N R 14 W.  
C C  
1984

Deposit the mkd. wooden post alongside the aluminum post.

From this cor., the cor. of secs. 35 and 36, T. 12 N., R. 14 W., bears N.  $89^{\circ}$  18.2' E., 9.628 chs. dist., described in the concurrent resurvey of T. 12 N., R. 14 W.

From this same cor., the 1/4 sec. cor. of sec. 35, T. 12 N., R. 14 W., bears S.  $89^{\circ}$  18.2' W., 30.465 chs. dist., described in the concurrent resurvey of T. 12 N., R. 14 W.

From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., heretofore described.

N.  $2^{\circ}$  19.8' W., bet. secs. 34 and 35.

40.789 Point for the 1/4 sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 11 N R 14 W  
1/4  
S 34 | S 35  
1984

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 11 N., R. 14 W., Salt Lake Meridian, Utah

<p>CHAINS 81.578</p>	<p>The cor. of secs. 26, 27, 34, and 35, monumented with a limestone, 14 x 10 x 4 ins., firmly set, projecting 7 ins. above ground, mkd. 1 notch on S edge and 2 notches on E edge with 1 1/2 ins. iron pipe projecting 24 ins. above ground on N side of stone.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 11 N R 14 W S 27   S 26 S 34   S 35 1983</p> </div> <p>Deposit the mkd. stone alongside the aluminum post.</p>
<p>40.598</p>	<p>From the cor. of secs. 25, 26, 35, and 36.</p> <p>S. 89° 32.0' W., bet. secs. 26 and 35.</p> <p>Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 11 N R 14 W S 26 1/4 ——— S 35 1984</p> </div>
<p>81.196</p>	<p>The cor. of secs. 26, 27, 34, and 35.</p>
<p>40.044</p>	<p>N. 0° 16.9' W., bet. secs. 26 and 27.</p> <p>Point for the 1/4 sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 11 N R 14 W 1/4 S 27   S 26 1983</p> </div>
<p>80.088</p>	<p>The cor. of secs. 22, 23, 26, and 27, monumented with a limestone, 12 x 9 x 8 ins., firmly set, projecting 6 ins. above ground, mkd. 2 notches on S edge and 2 notches on E edge, with 1 1/2 in. iron pipe projecting 32 ins. above ground.</p> <p>At the corner point</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 11 N., R. 14 W., Salt Lake Meridian, Utah

CHAINS	
	<p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> $\begin{array}{r} T\ 11\ N\ R\ 14\ W \\ S\ 22\   \ S\ 23 \\ \hline S\ 27\   \ S\ 26 \\ 1983 \end{array}$ <p>Deposit the mkd. stone alongside the aluminum post.</p>
40.479	<p>From the cor. of secs. 23, 24, 25, and 26.</p> <p>S. 89° 29.2' W., bet. secs. 23 and 26.</p> <p>Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> $\begin{array}{r} T\ 11\ N\ R\ 14\ W \\ \quad \quad \quad S\ 23 \\ 1/4 \quad \quad \quad \hline \quad \quad \quad S\ 26 \\ \quad \quad \quad 1984 \end{array}$
80.958	<p>The cor. of secs. 22, 23, 26, and 27.</p>
40.153	<p>N. 0° 28.6' W., bet. secs. 22 and 23.</p> <p>The 1/4 sec. cor. of secs. 22 and 23, monumented with a limestone, 9 x 6 x 6 ins., projecting 4 ins. above ground, mkd. 1/4 on W face.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> $\begin{array}{r} T\ 11\ N\ R\ 14\ W \\ \quad \quad \quad 1/4 \\ \quad \quad \quad   \\ S\ 22\   \ S\ 23 \\ \quad \quad \quad   \\ \quad \quad \quad 1983 \end{array}$ <p>Deposit the mkd. stone alongside the aluminum post.</p>
40.290	<p>N. 0° 10.1' W., beginning new measurement.</p> <p>Point for the cor. of secs. 14, 15, 22, and 23, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> $\begin{array}{r} T\ 11\ N\ R\ 14\ W \\ S\ 15\   \ S\ 14 \\ \hline S\ 22\   \ S\ 23 \\ 1984 \end{array}$

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 11 N., R. 14 W., Salt Lake Meridian, Utah

CHAINS																			
40.288	<p>From the cor. of secs. 13, 14, 23, and 24.</p> <p>S. 89° 34.2' W., bet. secs. 14 and 23.</p> <p>Point for the 1/4 sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td></td><td>T 11 N R 14 W</td><td></td></tr> <tr><td></td><td>  S 14</td><td></td></tr> <tr><td>1/4</td><td>  S 23</td><td></td></tr> <tr><td></td><td>1984</td><td></td></tr> </table> </div>		T 11 N R 14 W			S 14		1/4	S 23			1984							
	T 11 N R 14 W																		
	S 14																		
1/4	S 23																		
	1984																		
80.586	<p>The cor. of secs. 14, 15, 22, and 23.</p>																		
40.293	<p>N. 0° 39.6' W., bet. secs. 14 and 15.</p> <p>Point for the 1/4 sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td></td><td>T 11 N R 14 W</td><td></td></tr> <tr><td></td><td>  1/4</td><td></td></tr> <tr><td></td><td>   </td><td></td></tr> <tr><td></td><td>S 15   S 14</td><td></td></tr> <tr><td></td><td>   </td><td></td></tr> <tr><td></td><td>1984</td><td></td></tr> </table> </div>		T 11 N R 14 W			1/4						S 15   S 14						1984	
	T 11 N R 14 W																		
	1/4																		
	S 15   S 14																		
	1984																		
80.586	<p>The cor. of secs. 10, 11, 14, and 15, monumented with a limestone, 12 x 5 x 3 ins., firmly set, projecting 6 ins. above ground, plainly mkd. 4 grooves on S face and 2 grooves on E face.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td></td><td>T 11 N R 14 W</td><td></td></tr> <tr><td></td><td>  S 10   S 11</td><td></td></tr> <tr><td></td><td>  S 15   S 14</td><td></td></tr> <tr><td></td><td>1984</td><td></td></tr> </table> </div> <p>Deposit the mkd. stone alongside the aluminum post.</p>		T 11 N R 14 W			S 10   S 11			S 15   S 14			1984							
	T 11 N R 14 W																		
	S 10   S 11																		
	S 15   S 14																		
	1984																		
40.245	<p>From the cor. of secs. 11, 12, 13, and 14.</p> <p>S. 89° 59.3' W., bet. secs. 11 and 14.</p> <p>The 1/4 sec. cor. of secs. 11 and 14, monumented with a limestone, 10 x 4 x 4 ins., firmly set, projecting 5 ins. above ground, and in a collar of stone, mkd. 1/4 on N face.</p> <p>At the corner point</p>																		

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 11 N., R. 14 W., Salt Lake Meridian, Utah

CHAINS	
40.271	<p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> $\begin{array}{r} T\ 11\ N\ R\ 14\ W \\ \quad S\ 11 \\ 1/4 \quad \hline \quad S\ 14 \\ \quad 1984 \end{array}$ <p>Deposit the mkd. stone alongside the aluminum post.</p> <hr/> <p>S. 89° 36.1' W., beginning new measurement.</p> <p>The cor. of secs. 10, 11, 14, and 15.</p>
40.263	<p>N. 0° 21.0' W., bet. secs. 10 and 11.</p> <p>Point for the 1/4 sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> $\begin{array}{r} T\ 11\ N\ R\ 14\ W \\ \quad 1/4 \\ \quad   \\ S\ 10\   \quad S\ 11 \\ \quad   \\ \quad 1984 \end{array}$
80.526	<p>Point for the cor. of secs. 2, 3, 10, and 11, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> $\begin{array}{r} T\ 11\ N\ R\ 14\ W \\ \quad S\ 3\   \quad S\ 2 \\ \quad \hline S\ 10\   \quad S\ 11 \\ \quad 1984 \end{array}$
40.036	<p>From the cor. of secs. 1, 2, 11, and 12.</p> <p>S. 89° 58.0' W., bet. secs. 2 and 11.</p> <p>Point for the 1/4 sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> $\begin{array}{r} T\ 11\ N\ R\ 14\ W \\ \quad S\ 2 \\ 1/4 \quad \hline \quad S\ 11 \\ \quad 1984 \end{array}$
80.072	<p>The cor. of secs. 2, 3, 10, and 11.</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 11 N., R. 14 W., Salt Lake Meridian, Utah

CHAINS	
	N. 0° 05.5' W., bet. secs. 2 and 3.
40.262	<p>The 1/4 sec. cor. of secs. 2 and 3, monumented with a limestone, 14 x 11 x 3 ins., firmly set, projecting 7 ins. above ground, and in a collar of stone, mkd. 1/4 on W face.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>
	<p style="text-align: center;">T 11 N R 14 W 1/4   S 3   S 2   1984</p>
	Deposit the mkd. stone alongside the aluminum post.
	N. 0° 11.9' W., beginning new measurement.
34.545	<p>The closing cor. of secs. 2 and 3, perpetuated with a scattered mound of stone. No visible marks on the stones or remains of the original 4 ft. post. This point is accepted as a careful and faithful determination of the original corner position. I bury the stones 12 ins. below the surface of the ground. This now becomes an amended monument.</p>
35.933	<p>Point for the closing cor. of secs. 2 and 3, at the intersection with the N. bdy. of the Tp.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>
	<p style="text-align: center;">T 12 N R 14 W S 34 ----- S 3   S 2 T 11 N R 14 W C C 1984</p>
	<p>From this cor., the cor. of secs. 34 and 35, T. 12 N., R. 14 W., bears N. 89° 26.6' E., 10.424 chs. dist., described in the concurrent resurvey of T. 12 N., R. 14 W.</p>
	<p>From this same cor. the 1/4 sec. cor. of sec. 34, T. 12 N., R. 14 W., bears S. 89° 26.6' W., 29.593 chs. dist., described in the concurrent resurvey of T. 12 N., R. 14 W.</p>
	<p>From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., heretofore described.</p>
	N. 3° 36.8' W., bet. secs. 33 and 34.
40.559	<p>Point for the 1/4 sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 11 N., R. 14 W., Salt Lake Meridian, Utah

## CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 11 N R 14 W  
1/4  
S 33 | S 34  
1984

81.118 The cor. of secs. 27, 28, 33, and 34, monumented with a limestone, 18 x 9 x 5 ins., firmly set, projecting 9 ins. above ground, with 1 groove on S side and 3 notches on E edge, with a 1 1/2 in. iron pipe, on N side of stone, projecting 26 ins. above ground.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 11 N R 14 W  
S 28 | S 27  
S 33 | S 34  
1983

Deposit the mkd. stone alongside the aluminum post.

From the cor. of secs. 26, 27, 34, and 35.

S. 89° 22.8' W., bet. secs. 27 and 34.

40.935 The 1/4 sec. cor. of secs. 27 and 34, monumented with a 2 in. iron pipe, projecting 6 ins. above ground, with 3 1/2 ins. cap mkd.

CJS-LS  
2868  
T 11 N R 14 W  
S 27  
1/4 S 34  
1979

Land Surveyor No. 2868 determined the corner position from the original limestone, 12 x 8 x 5 ins., mkd. 1/4 and deposit alongside the iron pipe and buried below surface of ground.

S. 89° 29.0' W., beginning new measurement.

40.882 The cor. of secs. 27, 28, 33, and 34.

N. 0° 45.6' E., bet. secs. 27 and 28.

40.127 Point for the 1/4 sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 11 N., R. 14 W., Salt Lake Meridian, Utah

CHAINS	
80.254	<p style="text-align: center;">T 11 N R 14 W 1/4 S 28   S 27 1984</p> <p>The cor. of secs. 21, 22, 27, and 28, monumented with a limestone, 12 x 8 x 7 ins., firmly set, projecting 6 ins. above ground, mkd. 2 notches on S edge and 3 grooves on E face, with 1 1/2 in. iron pipe on N side of stone, projecting 34 ins. above ground.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 11 N R 14 W S 21   S 22 S 28   S 27 1983</p> <p>Deposit the mkd. stone and iron pipe alongside the aluminum post.</p>
40.202	<p>From the cor. of secs. 22, 23, 26, and 27.</p> <p>S. 89° 40.5' W., bet. secs. 22 and 27.</p> <p>The 1/4 sec. cor. of secs. 22 and 27, monumented with a quartzite stone, 10 x 7 x 6 ins., firmly set, projecting 4 ins. above ground, and in a collar of stone, mkd. 1/4 on N face.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 11 N R 14 W S 22 1/4 S 27 1984</p> <p>Deposit the mkd. stone alongside the aluminum post.</p> <p>Cor. is located at base of NW slope.</p>
40.139	<p>S. 89° 23.7' W., beginning new measurement.</p> <p>The cor. of secs. 21, 22, 27, and 28.</p>
40.511	<p>N. 1° 03.5' W., bet. secs. 21 and 22.</p> <p>The 1/4 sec. cor. of secs. 21 and 22, monumented with a limestone, 10 x 7 x 3 ins., firmly set, projecting 5 ins. above ground, mkd. 1/4 on W face.</p> <p>At the corner point</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 11 N., R. 14 W., Salt Lake Meridian, Utah

## CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 11 N R 14 W  
1/4  
S 21 | S 22  
1983

Deposit the mkd. stone alongside the aluminum post.

N. 0° 26.7' W., beginning new measurement.

40.671 The cor. of secs. 15, 16, 21, and 22, monumented with a limestone, 12 x 10 x 4 ins., firmly set, projecting 6 ins. above ground. The only visible marks on 2 notches on the S edge, with 1 1/2 in. iron pipe on N side of stone and projecting 28 ins. above ground.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 11 N R 14 W  
S 16 | S 15  
S 21 | S 22  
1983

Deposit the mkd. stone and iron pipe alongside the aluminum post.

From the cor. of secs. 14, 15, 22, and 23.

S. 89° 56.1' W., bet. secs. 15 and 22.

40.307 The 1/4 sec. cor. of secs. 15 and 22, monumented with a limestone, 13 x 8 x 6 ins., firmly set, projecting 7 ins. above ground with no visible marks. This position is harmoniously related to existing original corners and is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 11 N R 14 W  
S 15  
1/4 S 22  
1983

Deposit the mkd. stone alongside the aluminum post.

N. 89° 49.5' W., beginning new measurement.

40.623 The cor. of secs. 15, 16, 21, and 22.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 11 N., R. 14 W., Salt Lake Meridian, Utah

CHAINS	
40.195	<p>From the cor. of secs. 10, 11, 14, and 15.</p> <p>S. 89° 42.0" W., bet. secs. 10 and 15.</p> <p>The 1/4 sec. cor. of secs. 10 and 15, monumented with a limestone, 12 x 7 x 3 ins., (record, 17 x 8 x 5 ins.), firmly set, projecting 6 ins. above ground, and in a collar of stone, mkd. 1/4 on N face.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> $\begin{array}{r} T\ 11\ N\ R\ 14\ W \\ \quad \quad S\ 10 \\ 1/4 \quad \quad \quad S\ 15 \\ \quad \quad \quad \quad 1984 \end{array}$ <p>Deposit the mkd. stone alongside the aluminum post.</p> <hr/> <p>S. 89° 12.2' W., beginning new measurement.</p>
41.050	<p>The cor. of secs. 9, 10, 15, and 16, monumented with a limestone, 8 x 7 x 4 ins., firmly set, projecting 4 ins. above ground, mkd. 4 grooves on S face with no other visible marks. Found 1 1/2 in. iron pipe on N side of stone, projecting 30 ins. above ground.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> $\begin{array}{r} T\ 11\ N\ R\ 14\ W \\ S\ 9 \quad   \quad S\ 10 \\ \hline S\ 16 \quad   \quad S\ 15 \\ \quad \quad \quad 1983 \end{array}$ <p>Deposit the mkd. stone alongside the aluminum post.</p> <hr/> <p>N. 0° 18.6' E., bet. secs. 9 and 10.</p>
40.390	<p>Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> $\begin{array}{r} T\ 11\ N\ R\ 14\ W \\ \quad \quad 1/4 \\ \quad \quad   \\ S\ 9 \quad   \quad S\ 10 \\ \quad \quad   \\ \quad \quad 1984 \end{array}$
80.780	<p>The cor. of secs. 3, 4, 9, and 10, monumented with a limestone, 12 x 6 x 4 ins., firmly set, projecting 6 ins. above ground, mkd. 5 grooves on S face and 3 grooves on E face, with 1 1/2 in. iron pipe on N side of stone, and projecting 18 ins. above ground.</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 11 N., R. 14 W., Salt Lake Meridian, Utah

CHAINS	
	<p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> $\begin{array}{r} T\ 11\ N\ R\ 14\ W \\ S\ 4\   \ S\ 3 \\ \hline S\ 9\   \ S\ 10 \\ 1983 \end{array}$ <p>Deposit the mkd. stone alongside the aluminum post.</p>
40.147	<p>From the cor. of secs. 2, 3, 10, and 11.</p> <p>S. 89° 37.5' W., bet. secs. 3 and 10.</p> <p>Point for the 1/4 sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> $\begin{array}{r} T\ 11\ N\ R\ 14\ W \\ S\ 3 \\ 1/4 \quad \hline S\ 10 \\ 1984 \end{array}$
80.294	<p>The cor. of secs. 3, 4, 9, and 10.</p>
39.726	<p>N. 1° 22.6' W., bet. secs. 3 and 4.</p> <p>Point for the 1/4 sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> $\begin{array}{r} T\ 11\ N\ R\ 14\ W \\ 1/4 \\ S\ 4\   \ S\ 3 \\ \hline 1984 \end{array}$
75.947	<p>Intersect the S. bdy. of sec. 33, T. 12 N., R. 14 W.</p> <p>Point for the closing cor. of secs. 3 and 4, T. 11 N., R. 14 W., at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> $\begin{array}{r} T\ 12\ N\ R\ 14\ W \\ S\ 33 \\ \hline S\ 4\   \ S\ 3 \\ T\ 11\ N\ R\ 14\ W \\ C\ C \\ 1984 \end{array}$

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 11 N., R. 14 W., Salt Lake Meridian, Utah

## CHAINS

From this cor., the cor. of secs. 33 and 34, T. 12 N., R. 14 W., bears N.  $89^{\circ} 26.6'$  E., 12.305 chs. dist., described in the concurrent resurvey of T. 12 N., R. 14 W.

From this same cor., the 1/4 sec. cor. of sec. 33, T. 12 N., R. 14 W., bears S.  $89^{\circ} 26.6'$  W., 27.712 chs. dist., described in the concurrent resurvey of T. 12 N., R. 14 W.

From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., heretofore described.

N.  $2^{\circ} 57.5'$  W., bet. secs. 32 and 33.

40.987 Point for the 1/4 sec. cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

```

T 11 N R 14 W
  1/4
  |
S 32 | S 33
  |
  1984

```

81.974 The cor. of secs. 28, 29, 32, and 33, monumented with a limestone, 20 x 15 x 5 ins., firmly set, projecting 10 ins. in a mound of stone, 3 1/2 ft. base, mkd. 1 notch on S edge and 4 grooves on E face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

```

T 11 N R 14 W
  S 29 | S 28
  S 32 | S 33
      1984

```

Deposit the mkd. stone alongside the aluminum post.

From the cor. of secs. 27, 28, 33, and 34.

S.  $89^{\circ} 44.1'$  W., bet. secs. 28 and 33.

39.557 Point for the 1/4 sec. cor. of secs. 28 and 33, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

```

T 11 N R 14 W
  S 28
  1/4 S 33
      1984

```

79.124 The cor. of secs. 28, 29, 32, and 33.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 11 N., R. 14 W., Salt Lake Meridian, Utah

CHAINS	
	N. 0° 41.0' W., bet. secs. 28 and 29.
39.975	Point for the 1/4 sec. cor. of secs. 28 and 29, at proportionate distance; there is no remaining evidence of the original corner.  Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.
79.950	<div style="text-align: center;"> <p>T 11 N R 14 W 1/4 S 29   S 28 1984</p> </div> <p>The cor. of secs. 20, 21, 28, and 29, monumented with a limestone, 16 x 13 x 7 ins., firmly set, projecting 6 ins. above ground, plainly mkd. 2 notches on S edge and 4 grooves on E face, with 5/8 in. rebar on N side, projecting 20 ins. above ground.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 11 N R 14 W S 20   S 21 S 29   S 28 1984</p> </div> <p>Deposit the mkd. stone alongside the aluminum post.</p>
40.184	<p>From the cor. of secs. 21, 22, 27, and 28.</p> <p>S. 89° 18.6' W., bet. secs. 21 and 28.</p> <p>The 1/4 sec. cor. of secs. 21 and 28, monumented with a sandstone, 10 x 9 x 3 ins., mkd. 1/4 on N face, firmly set and projecting 5 ins. above ground, and in a collar of stone.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 11 N R 14 W S 21 1/4 S 28 1984</p> </div> <p>Deposit the mkd. stone alongside the aluminum post.</p>
40.940	<p>S. 89° 44.5' W., beginning new measurement.</p> <p>The cor. of secs. 20, 21, 28, and 29.</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 11 N., R. 14 W., Salt Lake Meridian, Utah

CHAINS	
40.380	<p>N. 0° 27.8' W., bet. secs. 20 and 21.</p> <p>The 1/4 sec. cor. of secs. 20 and 21, monumented with a limestone, 10 x 6 x 4 ins., firmly set, projecting 7 ins. above ground, dimly mkd. 1/4 on W face.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 11 N R 14 W</p> <p>1/4</p> <p>S 20   S 21</p> <p>1984</p> </div> <p>Deposit the mkd. stone alongside the aluminum post.</p>
40.417	<p>N. 0° 23.8' E., beginning new measurement.</p> <p>The cor. of secs. 16, 17, 20, and 21, monumented with a limestone, 13 x 10 x 5 ins. firmly set, projecting 7 ins. above ground, plainly mkd. 4 grooves on S side and 4 grooves on E face, with 1 1/2 in. iron pipe on N side of stone and projecting 25 ins. above ground.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 11 N R 14 W</p> <p>S 17   S 16</p> <p>S 20   S 21</p> <p>1984</p> </div> <p>Deposit the mkd. stone alongside the aluminum post.</p>
	<p>From the cor. of secs. 8, 9, 16, and 17, monumented with a sandstone, 13 x 7 x 5 ins., mkd. 4 notches on S edge and 3 grooves on E face, projecting 7 ins. above ground.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 11 N R 14 W</p> <p>S 8   S 9</p> <p>S 17   S 16</p> <p>1983</p> </div> <p>Deposit the mkd. stone alongside the aluminum post.</p>
40.645	<p>N. 0° 08.3' E., bet. secs. 8 and 9.</p> <p>Point for the 1/4 sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original corner.</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 11 N., R. 14 W., Salt Lake Meridian, Utah

CHAINS	
81.290	<p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 11 N R 14 W 1/4 S 8   S 9 1984</p> <p>The cor. of secs. 4, 5, 8, and 9, perpetuated with a 1 1/2 in. iron pipe, projecting 24 ins. above ground, with cap mkd. 4-5-8-9 and a cross (X), found a limestone, 10 x 7 x 2 ins., deposit alongside iron pipe mkd. 5 grooves on small side.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 11 N R 14 W S 5   S 4 S 8   S 9 1984</p> <p>Deposit the mkd. stone and pipe alongside the aluminum post.</p>
39.800	<p>From the cor. of secs. 3, 4, 9, and 10.</p> <p>N. 89° 52.7' W., bet. secs. 4 and 9.</p> <p>Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 11 N R 14 W S 4 1/4 S 9 1984</p>
79.600	<p>The cor. of secs. 4, 5, 8, and 9.</p> <p>N. 1° 53.0' W., bet. secs. 4 and 5.</p> <p>Point for the 1/4 sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 11 N R 14 W 1/4 S 5   S 4 1984</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 11 N., R. 14 W., Salt Lake Meridian, Utah

CHAINS	
74.962	<p>Intersect the S. bdy. of sec. 32, T. 12 N., R. 14 W.</p> <p>Point for the closing cor. of secs. 4 and 5, T. 11 N., R. 14 W., at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 12 N R 14 W S 32</p> <hr style="width: 50%; margin: auto;"/> <p>S 5   S 4 T 11 N R 14 W C C 1984</p> </div> <p>From this cor., the cor. of secs. 32 and 33, T. 12 N., R. 14 W., bears N. 89° 22.9' E., 12.351 chs. dist., described in the concurrent resurvey of T. 12 N., R. 14 W.</p> <p>From this same cor., the 1/4 sec. cor. of sec. 32, T. 12 N., R. 14 W., bears S. 89° 22.9' W., 27.812 chs. dist., described in the concurrent resurvey of T. 12 N., R. 14 W.</p>
40.318	<p>From the cor. of secs. 29, 30, 31, and 32, perpetuated with a 1 1/2 in. iron pipe, projecting 24 ins. above ground, loosely set in a mound of stone, 3 ft. base, with cap mkd. 29-30-31-32 and a cross (X). This point is accepted as a careful and faithful determination of the original corner position by local surveyors.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 11 N R 14 W S 30   S 29 S 31   S 32 1984</p> </div> <p>Deposit the iron post inside the aluminum post.</p> <p>S. 89° 52.6' W., bet. secs. 30 and 31.</p> <p>The 1/4 sec. cor. of secs. 30 and 31, monumented with a limestone, 11 x 7 x 7 ins., firmly set, projecting 5 ins. above ground, and in a collar of stone, dimly mkd. 1/4 on N face.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 11 N R 14 W S 30 1/4     S 31 1984</p> </div>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 11 N., R. 14 W., Salt Lake Meridian, Utah

CHAINS	
37.179	<p>Deposit the mkd. stone alongside the aluminum post.</p> <p>Cor. is located on SE slope.</p> <hr/> <p>S. 83° 13.2' W., beginning new measurement.</p> <p>The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., heretofore described.</p>
40.134	<p>From the cor. of secs. 29, 30, 31, and 32.</p> <p>N. 0° 35.4' W., bet. secs. 29 and 30.</p> <p>The 1/4 sec. cor. of secs. 29 and 30, monumented with a limestone, 8 x 8 x 7 ins., firmly set, projecting 4 ins. above ground, and in a collar of stone, dimly mkd. 1/4 on W face.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 11 N R 14 W</p> <p>1/4</p> <p>S 30   S 29</p> <p>1984</p> </div> <p>Deposit the mkd. stone alongside the aluminum post.</p> <hr/> <p>N. 1° 06.0' E., beginning new measurement.</p>
39.673	<p>Point for the cor. of secs. 19, 20, 29, and 30, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 11 N R 14 W</p> <p>S 19   S 20</p> <p>S 30   S 29</p> <p>1984</p> </div>
39.435	<p>From the cor. of secs. 20, 21, 28, and 29.</p> <p>S. 89° 52.7' W., bet. secs. 20 and 29.</p> <p>Point for the 1/4 sec. cor. of secs. 20 and 29, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 11 N R 14 W</p> <p>S 20</p> <p>1/4   S 29</p> <p>1984</p> </div>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 11 N., R. 14 W., Salt Lake Meridian, Utah

CHAINS	
78.880	The cor. of secs. 19, 20, 29, and 30.
	S. 87° 05.8' W., bet. secs. 19 and 30.
39.676	Point for the 1/4 sec. cor. of secs. 19 and 30, at proportionate distance; there is no remaining evidence of the original corner.
	Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	$\begin{array}{c} \text{T 11 N R 14 W} \\ \text{S 19} \\ \hline \text{1/4 S 30} \\ \text{1984} \end{array}$
78.886	The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., heretofore described.
	From the cor. of secs. 19, 20, 29, and 30.
	N. 1° 42.3' W., bet. secs. 19 and 20.
39.684	Point for the 1/4 sec. cor. of secs. 19 and 20, at proportionate distance; there is no remaining evidence of the original corner.
	Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	$\begin{array}{c} \text{T 11 N R 14 W} \\ \text{1/4} \\ \text{S 19} \quad   \quad \text{S 20} \\ \text{1984} \end{array}$
	from which
	U.S.G.S. triangulation station "ANTS 1957", bears S. 65° 35' 27" E., 7.966 chs. dist., monumented with a standard aluminum cap, 3 1/2 ins. diam., firmly cemented into a drill hole in solid rock outcrop, with top mkd. ANTS 1957 and a triangle.
79.368	The cor. of secs. 17, 18, 19, and 20, monumented with a limestone, 11 x 7 x 5 ins., firmly set, projecting 6 ins. above ground, with 2 grooves on S face and 5 grooves on E face.
	At the corner point
	Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	$\begin{array}{c} \text{T 11 N R 14 W} \\ \text{S 18} \quad   \quad \text{S 17} \\ \hline \text{S 19} \quad   \quad \text{S 20} \\ \text{1983} \end{array}$
	Deposit the mkd. stone alongside the aluminum post.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 11 N., R. 14 W., Salt Lake Meridian, Utah

CHAINS	
40.596	<p>From the cor. of secs. 16, 17, 20, and 21.</p> <p>S. 88° 51.0' W., bet. secs. 17 and 20.</p> <p>Point for the 1/4 sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 11 N R 14 W</p> <p>S 17</p> <hr style="width: 50px; margin: 0 auto;"/> <p>1/4 S 20</p> <p>1984</p> </div>
81.192	<p>The cor. of secs. 17, 18, 19, and 20.</p> <hr/> <p>S. 86° 46.8' W., bet. secs. 18 and 19.</p>
38.806	<p>Point for the 1/4 sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 11 N R 14 W</p> <p>S 18</p> <hr style="width: 50px; margin: 0 auto;"/> <p>1/4 S 19</p> <p>1984</p> </div>
76.836	<p>The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., heretofore described.</p> <hr/> <p>From the cor. of secs. 17, 18, 19, and 20.</p> <p>N. 0° 11.5' E., bet. secs. 17 and 18.</p>
40.645	<p>Point for the 1/4 sec. cor. of secs. 17 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 11 N R 14 W</p> <p>1/4</p> <p style="margin-left: 40px;"> </p> <p>S 18   S 17</p> <p style="margin-left: 40px;"> </p> <p>1984</p> </div>
81.290	<p>The cor. of secs. 7, 8, 17, and 18, monumented with a limestone, 13 x 8 x 5 ins., firmly set, projecting 7 ins. above ground, 4 grooves on S face and 5 notches on E edge.</p> <p>from which</p> <p style="margin-left: 40px;">A juniper, 32 ins. diam., bears S. 11° E., 9 1/2 lks. dist., mkd. on open blaze. (Record, 13 lks. dist.)</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 11 N., R. 14 W., Salt Lake Meridian, Utah

CHAINS

A juniper, 38 ins. diam., bears S. 13° W., 93 1/2  
lks. dist., faintly mkd. on open blaze.  
(Record, S. 15° W., 103 lks. dist.)

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24  
ins. in the ground, with aluminum cap mkd.

T 11 N R 14 W	
S 7	S 8
S 18	S 17
1983	

Deposit the mkd. stone alongside the aluminum post.

From the cor. of secs. 8, 9, 16, and 17.

S. 89° 21.9' W., bet. secs. 8 and 17.

40.007 The 1/4 sec. cor. of secs. 8 and 17, monumented with a  
limestone, 11 x 9 x 4 ins., firmly set, projecting 4 ins.  
above ground, and mkd. 1/4 on N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24  
ins. in the ground, with aluminum cap mkd.

T 11 N R 14 W	
S 8	
1/4	S 17
1983	

Deposit the mkd. stone alongside the aluminum post.

S. 89° 32.4' W., beginning new measurement.

40.318 The cor. of secs. 7, 8, 17, and 18.

S. 88° 47.6' W., bet. secs. 7 and 18.

39.959 The 1/4 sec. cor. of secs. 7 and 18, monumented with a  
limestone, 14 x 5 x 4 ins., firmly set, projecting 7 ins.  
above ground, plainly mkd. 1/4 on N face, and in a collar  
of stone.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24  
ins. in the ground, with aluminum cap mkd.

T 11 N R 14 W	
S 7	
1/4	S 18
1984	

Deposit the mkd. stone alongside the aluminum post.

From this cor., a 1 1/2 in. iron pipe projecting 24 ins.  
above ground, with cap mkd. 1/4 7-18 bears West, 7 lks.  
dist.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 11 N., R. 14 W., Salt Lake Meridian, Utah

CHAINS	
37.753	<p>S. 83° 01.7' W., beginning new measurement.</p> <p>The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., heretofore described.</p>
40.542	<p>From the cor. of secs. 7, 8, 17, and 18.</p> <p>N. 0° 42.9' W., bet. secs. 7 and 8.</p> <p>The 1/4 sec. cor. of secs. 7 and 8, monumented with a limestone, 12 x 9 x 6 ins., firmly set, projecting 6 ins. above ground, dimly mkd. 1/4 on W face, and in a collar of stone.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 11 N R 14 W</p> <p>1/4</p> <p> </p> <p>S 7   S 8</p> <p> </p> <p>1984</p> </div> <p>Deposit the mkd. stone alongside the aluminum post.</p>
40.726	<p>N. 1° 04.0' W., beginning new measurement.</p> <p>The cor. of secs. 5, 6, 7, and 8, monumented with a limestone, 13 x 7 x 5 ins., (record, 16 x 10 x 8 ins.), mkd. 5 notches on S edge and 5 notches on E edge, firmly set, projecting 7 ins. above ground, and in a collar of stone.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 11 N R 14 W</p> <p>S 6   S 5</p> <p>S 7   S 8</p> <p>1984</p> </div> <p>Deposit the mkd. stone alongside the aluminum post.</p>
40.883	<p>From the cor. of secs. 4, 5, 8, and 9.</p> <p>S. 89° 26.4' W., bet. secs. 5 and 8.</p> <p>Point for the 1/4 sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 11 N R 14 W</p> <p>S 5</p> <p>1/4 — S 8</p> <p>1984</p> </div>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 11 N., R. 14 W., Salt Lake Meridian, Utah

CHAINS	
81.766	The cor. of secs. 5, 6, 7, and 8.
39.348	<p>S. 85° 17.2' W., bet. secs. 6 and 7.</p> <p>Point for the 1/4 sec. cor. of secs. 6 and 7, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 11 N R 14 W S 6 1/4     S 7 1984</p>
76.856	The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., heretofore described.
38.328	<p>From the cor. of secs. 5, 6, 7, and 8.</p> <p>N. 0° 38.7' E., bet. secs. 5 and 6.</p> <p>Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 11 N R 14 W 1/4 S 6   S 5 1984</p>
74.443	The closing cor. of secs. 5 and 6, monumented with a limestone, 16 x 13 x 2 ins., loosely set, projecting 8 ins. above ground and plainly mkd. 5 grooves on E side and 1 groove on W side. Add the marks AM and bury the stone 6 ins. below the surface of the ground.
74.871	<p>Point for the closing cor. of secs. 5 and 6, at intersection with the S. bdy. of T. 12 N., R. 14 W.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 12 N R 14 W S 31 S 6   S 5 T 11 N R 14 W C C 1984</p> <p>From this cor., the cor. of secs. 31 and 32, T. 12 N., R. 14 W., bears N. 89° 20.4' E., 10.468 chs. dist., described in the concurrent resurvey of T. 12 N., R. 14 W.</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 11 N., R. 14 W., Salt Lake Meridian, Utah

## CHAINS

From this same cor., the 1/4 sec. cor. of sec. 31, T. 12 N., R. 14 W., bears S. 89° 20.4' W., 29.339 chs. dist., described in the concurrent resurvey of T. 12 N., R. 14 W.

General Description

The land encompassed in this survey is located within Box Elder County, three miles west and six miles south of Park Valley.

Drainage is generally to the northeast by way of Runswick Wash.

The elevation varies from 4890 ft. at the northeast township corner to 5826 ft. at triangulation station "ANTS", located in section 20 of the township.

Access is by way of State Highway No. 30. Further access to the township is provided by numerous secondary and desert trail roads.

The vegetation consists of scattering stands of juniper trees and shadscale, budsage, sagebrush, and sparse native grasses.

The principal use of the area is for livestock grazing and dry farming with some recreation hunting.

The improvements noted were development of cultivation on ranches within sections 2 and 3.



CERTIFICATE OF SURVEY

(I) (W~~o~~), Frank C. Profaizer, Jr., Supervisory Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 15th day of December, 1982, (I) (W~~o~~) have dependently resurveyed the north five miles of the west boundary (the Guide Meridian West), the south boundary, a portion of the north boundary and portions of the subdivisional lines of T. 11 N., R. 14 W.,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), (W~~o~~) and under (my) (W~~o~~) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

May 2, 1985 (Date) Frank C. Profaizer, Jr. (Cadastral Surveyor) Supervisory

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Washington, D.C.

The foregoing field notes of the dependent resurvey of the north five miles of the west boundary (the Guide Meridian West), the south boundary, a portion of the north boundary, and portions of the subdivisional lines of T. 11 N., R. 14 W., Salt Lake Meridian, Utah

executed by Frank C. Profaizer, Jr., Supervisory Cadastral Surveyor having been critically examined and found correct, are hereby approved.

January 16, 1986 (Date) Glenn B. Hatch (Chief Cadastral Surveyor for Utah)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

(Date) (Chief, Division of Cadastral Survey) GPO 847526

R608

# FIELD NOTES

OF THE

239

DEPENDENT RESURVEY

OF A

PORTION OF THE SOUTH BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES

AND A

SURVEY OF THE SUBDIVISION OF SECTIONS 21, 27, 28, 33, AND 34

OF

TOWNSHIP 36 SOUTH, RANGE 22 EAST

Of the Salt Lake Meridian,

In the State of Utah

## EXECUTED BY

Richard A. Zaninovich Cadastral Surveyor

Under special instructions dated January 20, 19 84, approved February 17, 1984

\_\_\_\_\_, which provided for the surveys included under U.S. Survey Group  
Number 644, and assignment instructions dated January 23, 19 84

Survey commenced March 14, 19 84

Survey completed April 6, 19 84

240

JAN 1910

# INDEX DIAGRAM

Township 36 South, Range 22 East

6	5	4	3	2	1
7	8	9	10	11	12
13	14	15	16	17	18
19	20	21	22	23	24
25	26	27	28	29	30
31	32	33	34	35	36

Subdivision of Section 21  
 Subdivision of Section 27  
 Subdivision of Section 28  
 Subdivision of Section 33  
 Subdivision of Section 34

- Page 10  
 - Page 11  
 - Page 12  
 - Page 15  
 - Page 16

## Township 36 South, Range 22 East, Salt Lake Meridian, Utah

CHAINS

The following field notes are those of the dependent resurvey of a portion of the south boundary and a portion of the subdivisional lines, and the survey of the subdivision of sections 21, 27, 28, 33, and 34 of Township 36 South Range 22 East, Salt Lake Meridian, Utah.

History of Earlier Surveys

Surveyed by                      Retr. or Resurveyed by

SOUTH BOUNDARY

All            A.P. Hanson            1907

SUBDIVISIONAL LINES

Portion	A.P. Hanson	1907	
Portion	Miller and Thoma	1912	
Portion		Miller and Thoma	1912
Portion		J.L. Thomas	1978-79

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group 644, Utah, dated January 20, 1984.

The directions of the lines of this survey refer to the true meridian as determined by hour angle observations of Polaris. The lines were carried forward by sustained angulation.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the 1/4 sec. cor. of secs. 2 and 35 on the S. bdy. of the Tp. as determined by a tie made to U.S. Coast and Geodetic Survey triangulation station "BLANDING", is as follows:

Latitude 37° 36' 22.99" N.    Longitude 109° 27' 57.94" W.

The mean magnetic declination as projected from the U.S. Geological Survey "Magnetic Declination Map of 1980" is 13° E.

Dependent Resurvey of a Portion of the South Boundary,  
T. 36 S., T 22 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by  
A.P. Hanson in 1907

Beginning at the 1/4 sec. cor of secs. 2 and 35 on the S. bdy. of the Tp., determined at the cor. of fences projecting N, S, E, and W.; this is accepted as the best available evidence of the position of the original cor.

Dependent Resurvey of a Portion of the South Boundary,  
T. 36 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
40.07	<p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins in the ground, with aluminum cap mkd..</p> $\begin{array}{r} T\ 36\ S\ R\ 22 \\ S\ 35 \\ \hline 1/4\ \quad S\ 2 \\ T\ 37\ S \\ 1984 \end{array}$ <p>S. 89° 53' W., bet. secs. 2 and 35.</p> <p>Point for the cor of secs. 2, 3, 34, and 35 on the S. bdy. of the Tp. at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Not monumented</p>
40.07	<p>S. 89° 53' W., bet. secs. 3 and 34.</p> <p>The 1/4 sec. cor. of secs. 3 and 34, monumented with a sandstone, 24 x 20 x 6 ins., mkd. 1/4, buried alongside the cor. of fences projecting N, E, and W.</p> <p>from which</p> <p style="padding-left: 40px;">A juniper stump, 12 ins. diam., blazed on the NW and SW faces, no scribe marks visible, bears East 15 lks. dist.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap mkd.</p> $\begin{array}{r} T\ 36\ S\ R\ 22\ E \\ S\ 34 \\ \hline 1/4\ \quad S\ 3 \\ T\ 37\ S \\ 1984 \end{array}$ <p>Deposit the mkd. stone alongside the aluminum post.</p>
40.10	<p>N. 89° 38' W., beginning new measurement.</p> <p>The cor. of secs. 3, 4, 33, and 34, monumented with a sandstone, 24 x 6 x 6 ins., (record, porphyry) mkd. with 3 notches on E and W edges, projecting 8 ins. above a collar of stone.</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 10 ins. diam., bears S. 87 1/4° E., 48 lks. dist., mkd. T36S R22E S34 BT (record, N. 87° 35' E., 49 lks. dist.).</p> <p style="padding-left: 40px;">A standing dead pine, 6 ins. diam., bears S. 27 3/4° E., 5 lks. dist., mkd. T37S R22E S3 BT. (Record, S. 21° E., 5 lks. dist.).</p>

Dependent Resurvey of a Portion of South Boundary,  
T. 36 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS

A juniper, 12 ins. diam., at the cor. of fences projecting N, E, and W, bears West, 13 1/2 lks. dist., mkd. T37S R22E S4 BT. (Record, S. 89° 15' W, 15 lks. dist.).

A pine, 8 ins. diam., bears N. 54 3/4° W., 25 lks. dist., mkd. T36S R22E S33 BT. (Record, N. 55° 02' W., 26 lks. dist.).

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

$$\begin{array}{r} T\ 36\ S\ R\ 22\ E \\ S\ 33\ | \ S\ 34 \\ \hline S\ 4\ | \ S\ 3 \\ T\ 37\ S \\ 1984 \end{array}$$

Deposit the mkd. stone alongside the aluminum post.

N. 89° 16' W., bet. secs. 4 and 33.

20.01

Point for the E 1/16 sec. cor. of secs. 4 and 33.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with aluminum cap mkd.

$$\begin{array}{r} E\ 1/16\ \frac{S\ 33}{S\ 4} \\ 1984 \end{array}$$

40.02

The 1/4 sec. cor. of secs. 4 and 33, monumented with a sandstone 20 x 8 x 6 ins., (record, quartzite, 18 x 12 x 7 ins.) projecting 6 ins. above the ground mkd. 1/4 on the N. face

from which

A juniper, 12 ins. diam., bears S. 8° W., 32 lks. dist., mkd. 1/4 S4 BT. (Record, S. 06° 15' W., 32 lks. dist.).

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap mkd.

$$\begin{array}{r} T\ 36\ S\ R\ 22\ E \\ S\ 33 \\ 1/4\ \frac{S\ 4}{S\ 4} \\ T\ 37\ S \\ 1984 \end{array}$$

Deposit the mkd. stone alongside the aluminum post.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 36 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	Dependent Resurvey of a Portion of the Subdivisional Lines, T. 36 S., R. 22 E., Salt Lake Meridian, Utah
	<p>From the point for the cor. of secs. 2, 3, 34, and 35 on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0° 04' E., bet secs. 34 and 35.</p>
40.02	<p>Point for the 1/4 sec. cor. of secs. 34 and 35 at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Not monumented.</p>
80.04	<p>Point for the cor. of secs. 26, 27, 34, and 35 as determined by Richard L. Johnston, Utah RLS No. 4946, from record ties to Blanding City streets and blocks.</p> <p>Point falls inside the foundation line of a house and therefore is not monumented.</p> <p>from which</p> <p style="padding-left: 40px;">A 5/8 in. spike set flush with the surface of an asphalt road at the intersection of the centerlines of Third South and First East streets, bears N. 46° 10' W., 1.996 chs. dist.</p> <p style="padding-left: 40px;">The 1/4 sec. cor. of secs. 26 and 35, monumented with a rebar, alongside of which is a quartzite projecting 14 x 8 x 6 ins above the ground, mkd 1/4 on the N face bears N. 89° 51' E., 39.91 chs. dist.</p> <p>This point is accepted as a careful and faithful reestablishment of the position of the original corner.</p>
	<p>North, bet secs. 26 and 27.</p>
40.02	<p>The 1/4 sec. cor. of secs. 26 and 27, monumented with a 5/8 in. spike set flush with the surface of the ground by Richard L. Johnston, Utah RLS No. 4946; this is accepted as a careful and faithful reestablishment of the position of the original cor.</p>
	<p>North, beginning new measurement.</p>
40.04	<p>The cor. of secs. 22, 23, 26, and 27 monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. above the ground, with brass cap mkd. as described in the official record of the dependent resurvey of a portion of the subdivisional lines executed by J.L. Thomas in 1978, and a mound of stone W. of the cor.</p>
	<p>From the cor. of secs. 3, 4, 33, and 34 on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0° 13' E., bet. secs. 33 and 34.</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 36 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
40.04	<p>The 1/4 sec. cor. of secs. 33 and 34 monumented with a sandstone 20 x 8 x 6 ins., (record, 18 x 8 x 4 ins.), projecting 4 ins. above the ground, mkd. 1/4 on the W. face.</p> <p>from which the original bearing tree</p> <p style="padding-left: 40px;">A juniper stump, 12 ins. diam., bears N. 77° W., 36 lks. dist., mkd. 1/4 S33 BT (Record, S. 77° 30' W., 37 lks.)</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with a aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 36 S R 22 E</p> <p>1/4</p> <p> </p> <p>S 33   S 34</p> <p> </p> <p>1984</p> </div> <p>Cor. falls in a fence line bears E. and W.</p> <p>Raise a mound of stone W of cor.</p> <p>Deposit the mkd. stone alongside the aluminum post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 08' W., beginning new measurement.</p>
39.98	<p>The cor of secs. 27, 28, 33, and 34, monumented with a 1/2 in. diam. rebar set by Donald V. Blake, Utah RLS No. 2759; this is accepted as a careful and faithful reestablishment of the position of the original cor.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 36 S R 22 E</p> <p>S 28   S 27</p> <p>S 33   S 34</p> <p>1984</p> </div> <p>Deposit rebar inside aluminum post.</p> <p>Raise a mound of stone, W of cor.</p>
40.09	<p>From the point for the cor. of secs. 26, 27, 34, and 35.</p> <p>N. 89° 55' W., bet. secs. 27 and 34.</p> <p>The 1/4 sec. cor. of secs. 27 and 34, monumented with an aluminum disk, 2 ins. diam., set in concrete, mkd.</p> <div style="text-align: center;"> <p>RLS</p> <p>1/4</p> <p>4946</p> </div> <p>This is accepted as a careful and faithful perpetuation of the position of the original cor.</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 36 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
20.05	<p>Cor. falls in a fence line bears N. and S., 46 lks. S. of the cor. of fences projecting S, E, and W.</p> <p style="text-align: center;">_____</p> <p>N. 89° 51' W, beginning new measurement.</p> <p>Point for the W 1/16 sec. cor. of secs. 27 and 34.</p> <p>Set an iron post, 12 ins. long, 1 in. diam., drilled 8 ins in solid sandstone, with brass cap mkd.</p> <p style="text-align: center;">           W 1/16    <math>\frac{S\ 27}{S\ 34}</math>                              1984         </p>
40.10	<p>The cor. of secs. 27, 28, 33, and 34.</p> <hr/> <p>N. 0° 07' W., bet. secs. 27 and 28.</p>
20.02	<p>Point for the S 1/16 sec. cor. of secs. 27 and 28.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">           S 1/16            S 28   S 27                      1984         </p>
40.04	<p>The 1/4 sec. cor. of secs. 27 and 28 monumented with an aluminum disk, 2 ins. diam., set in solid sandstone, mkd.</p> <p style="text-align: center;">           RLS            1/4            28   27                  4946         </p> <p>This is accepted as a careful and faithful reestablishment of the position of the original corner.</p> <p>from which</p> <p style="padding-left: 40px;">An aluminum disc, 2 ins. diam., set in solid sandstone for a reference monument, bears N. 18° E., 23 lks. dist., mkd. RM No. 2.</p> <p style="padding-left: 40px;">An aluminum disc, 2 ins. diam., set in solid sandstone for a reference monument, bears S. 54° W., 30 lks. dist., mkd. RM No. 1.</p> <p style="padding-left: 40px;">Raise a mound of stone W. of cor.</p>
20.08	<p>N. 0° 18' E., beginning new measurement.</p> <p>Point for the N 1/16 sec. cor. of secs. 27 and 28.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">           N 1/16            S 28   S 27                  1984         </p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 36 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
40.16	<p>The cor. of secs. 21, 22, 27, and 28, monumented with an iron post 2 1/2 ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the official record of the dependent resurvey of a portion of the subdivisional lines executed by J.L. Thomas in 1978.</p>
	<p style="text-align: center;">Reestablishment of the Survey Executed by Miller and Thoma in 1912</p> <hr style="width: 20%; margin: auto;"/> <p>From the 1/4 sec. cor of secs. 32 and 33 monumented with an iron post, 1 in. diam., firmly set in a mound of stone, with brass cap mkd. as described in the official record of the 1912 survey.</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 8 ins. diam., bears S. 33° W., 41 lks. dist., mkd. 1/4 S32 BT (Record S. 30° W., 38 lks.)</p> <p>N. 0° 17' E., bet. secs 32 and 33.</p>
39.81	<p>The cor. of secs 28, 29, 32, and 33 monumented with an iron post, 2 ins. diam., firmly set in a mound of stone, with brass cap mkd as described in the official record of the 1912 survey.</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 12 ins. diam., bears S. 4 1/2° E., 89 1/2 lks. dist., mkd. T36S R22E S33 BT (Record, S. 4° E., 125 lks.)</p>
	<p>From the cor. of secs. 27, 28, 33, and 34.</p> <p>N. 89° 39' W., bet. secs. 28 and 33.</p>
19.955	<p>Point for the E 1/16 sec. cor. of secs. 28 and 33.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap mkd.</p> $\begin{array}{r} \text{S } 28 \\ \text{E } 1/16 \text{ } \frac{\text{S } 33}{1984} \end{array}$
39.91	<p>Point for the 1/4 sec. cor. of secs. 28 and 33, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap mkd.</p> $\begin{array}{r} \text{T } 36 \text{ S } \text{R } 22 \text{ E} \\ \text{S } 28 \\ 1/4 \text{ } \frac{\text{S } 33}{1984} \end{array}$
59.865	<p>Point for the W 1/16 sec. cor. of secs. 28 and 33.</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 36 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
79.82	<p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> $\begin{array}{r} \text{S } 28 \\ \hline \text{W } 1/16 \quad \text{S } 33 \\ 1984 \end{array}$ <p>The cor. of secs. 28, 29, 32, and 33.</p>
20.055	<p>N. 0° 20' W., bet. secs. 28 and 29.</p> <p>Point for the S 1/16 sec. cor. of secs. 28 and 29.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> $\begin{array}{c} \text{S } 1/16 \\   \\ \text{S } 29 \quad   \quad \text{S } 28 \\   \\ 1984 \end{array}$
40.11	<p>The 1/4 sec. cor. of secs. 28 and 29, monumented with an iron post, 1 in. diam., projecting 8 ins. above the ground, with brass cap, mkd. as described in the official record of the 1912 survey, and a mound of stone, W of cor.</p> <hr/> <p>N. 0° 08' E., beginning new measurement.</p>
19.925	<p>Point for the N 1/16 sec. cor. of secs. 28 and 29.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap mkd.</p> $\begin{array}{c} \text{N } 1/16 \\   \\ \text{S } 29 \quad   \quad \text{S } 28 \\   \\ 1984 \end{array}$
39.85	<p>The cor. of secs. 20, 21, 28, and 29, monumented with an iron post, 2 ins. diam., projecting 12 ins. above the ground, with brass cap, mkd. as described in the official record of the 1912 survey.</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 16 ins. diam., bears N. 28° E., 12 lks. dist., mkd. T36S R22E S21 BT. (Record, N. 28° E., 11 lks. dist.)</p>
20.025	<p>From the cor. of secs. 21, 22, 27, and 28.</p> <p>N. 89° 49' W., bet. secs. 21 and 28.</p> <p>Point for the E. 1/16 sec. cor. of secs. 21 and 28.</p> <p>Not monumented.</p>
40.05	<p>Point for the 1/4 sec. cor. of secs. 21 and 28, at proportionate distance; there is no remaining evidence of the original corner.</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 36 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
	<p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 36 S R 22 E S 21 1/4 S 28 1984</p> <p>Cor. falls in a fence line, bears N. and S.</p> <p>60.075 Point for the W 1/16 sec. cor of secs. 21 and 28. Not monumented.</p> <p>80.10 The cor. of secs. 20, 21, 28, and 29.</p>
	<p>N. 0° 13' E., bet. secs. 20 and 21.</p> <p>19.995 Point for the S. 1/16 sec. cor. of secs. 20 and 21.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">S 1/16 S 20   S 21 1984</p> <p>39.99 Point for the 1/4 sec. cor. of secs. 20 and 21, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 36 S R 22 E 1/4 S 20   S 21 1984</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears S. 45° W., 14 lks. dist., mkd. 1/4 S20 BT.</p> <p>Raise a mound of stone W of cor.</p>
79.98	<p>The cor. of secs. 16, 17, 20, and 21, monumented with an iron post, 2 ins. diam., firmly set in a mound of stone, with brass cap, mkd. as described in the official record of the 1912 survey.</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 14 ins. diam., bears N. 25° E., 54 1/2 lks. dist., with a partially healed blaze mkd. BT (Record, N. 10° E., 42 lks.).</p> <p style="padding-left: 40px;">A pine, 6 ins. diam., bears S. 50° E., 16 lks. dist., with a partially healed blaze mkd. BT (Record, S. 35° E., 20 lks.).</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears N. 54° W., 79 1/2 lks. dist., mkd. T36S R22E S17 BT (Record, N. 53° W., 82 lks.).</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 36 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
39.91	<p>From the 1/4 sec. cor. of secs. 16 and 21, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, with brass cap, mkd. as described in the official record of the 1912 survey.</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 8 ins. diam., bears N. 2 1/2° E., 272 1/2 lks. dist., mkd. 1/4 S16 BT (Record, N. 3 3/4° E., 300 lks. dist.).</p> <p style="padding-left: 40px;">A juniper, 8 ins. diam., bears S. 33 3/4° E., 74 1/2 lks. dist., mkd. 1/4 S21 BT. (Record, S. 36° E., 67 lks. dist.).</p> <p>S. 89° 53' W., bet. secs. 16 and 21</p> <p>The cor. of secs. 16, 17, 21, and 22.</p>
<p>Survey of the Subdivision of Section 21, T. 36 S., R.22 E., Salt Lake Meridian, Utah</p>	
20.055	<p>From the 1/4 sec. cor. of secs. 21 and 28.</p> <p>N. 0° 07' E., on the N. and S. centerline of sec. 21</p> <p>Point for the center S 1/16 sec. cor. of sec. 21.</p> <p>Not monumented.</p>
40.11	<p>Point for the center 1/4 sec. cor. of sec. 21, at intersection with the E. and W. centerline.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 36 S R 22 E C 1/4 S 21 1984</p> <p>Cor. falls in a cultivated field.</p>
80.19	<p>The 1/4 sec. cor. of secs. 16 and 21.</p>
39.83	<p>From the 1/4 sec. cor. of secs. 21 and 22, monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. above the ground, with brass cap, mkd. as described in the official record of the dependent resurvey of a portion of the subdivisional lines executed by J.L. Thomas in 1978, and a mound of stone W of cor.</p> <p>N. 89° 59' W., on the E. and W. centerline of sec. 21.</p> <p>The center 1/4 sec. cor. of sec. 21.</p>
59.82	<p>Point for the center W. 1/16 sec. cor. of sec. 21.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap mkd.</p>

Survey of the Subdivision of Section 21,  
T. 36 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
	<p style="text-align: center;">W 1/16 C _____ C S 21 1984</p>
79.81	The 1/4 sec. cor. of secs. 20 and 21.
	<p>From the point for the W. 1/16 sec. cor. of secs. 21 and 28.</p> <p>N. 0° 10' E., on the N and S centerline of the SW 1/4 of sec. 21.</p>
20.025	<p>Point for the SW 1/16 sec. cor. of sec. 21, at intersection with the E and W center line of the SW 1/4.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p>
	<p style="text-align: center;">SW 1/16 S 21 1984</p>
40.05	The center W 1/16 sec. cor. of sec. 21.
	<p>From the point for the center S 1/16 sec. cor. of sec. 21.</p> <p>N. 89° 54' W., on the E and W centerline of the SW 1/4 of sec. 21.</p>
20.01	The SW 1/16 sec. cor. of sec. 21.
40.02	The S 1/16 sec. cor. of secs. 20 and 21.
	<p style="text-align: center;">Survey of the Subdivision of Section 27, T. 36 S., R. 22 E., Salt Lake Meridian, Utah</p>
	<p>From the 1/4 sec. cor. of secs. 27 and 34.</p> <p>N. 0° 03' E., on the N and S centerline of sec. 27.</p>
20.03	Point for the center S 1/16 sec. cor. of sec. 21. Not monumented.
40.06	Point for the center 1/4 sec. cor. of sec. 27, at intersection with the E and W centerline.
	<p>Set a railroad spike flush with the surface of the ground at the SE cor. of the intersection of Second North and Fourth West streets.</p>
	From which
	<p style="padding-left: 40px;">The W. leg of mail box No. 44, bears N. 9 3/4° E., 89.9 lks. dist.</p>
	<p style="padding-left: 40px;">The NW cor. of a house, bears S. 35° E., 48 lks. dist.</p>
	<p style="padding-left: 40px;">The E. leg of a mail box No. 45, bears S. 85 1/2° W., 121.8 lks. dist.</p>

Survey of the Subdivision of Section 27,  
T. 36 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS		
80.16	<p>The 1/4 sec. cor. of secs. 22 and 27, monumented with a spike set flush with the street surface of Fourth West Street and referenced as described in the official record of the resurvey of a portion of the subdivisional lines executed by J.L. Thomas in 1978.</p> <p>From this cor., United States Coast and Geodetic Survey Triangulation station "Blanding" bears N. 1° 26' E., 40.04 chs. dist., monumented with a standard brass tablet, firmly set in concrete, with brass cap, mkd BLANDING 1949-1954.</p>	
	<p>From the 1/4 sec. cor. of secs. 26 and 27.</p> <p>N. 89° 52' W., on the E and W centerline of sec. 27.</p>	
40.06	The center 1/4 sec. cor. of sec. 27.	
60.16	<p>Point for the center W 1/16 sec. cor. of sec. 27.</p> <p>Not monumented.</p>	
80.26	The 1/4 sec. cor. of secs. 27 and 28.	
20.025	<p>From the W 1/16 sec. cor. of secs. 27 and 34.</p> <p>N. 0° 02' W., on the N and S centerline of the SW 1/4 of sec. 27.</p> <p>Point for the SW 1/16 sec. cor. of sec. 27, at intersection with the E and W centerline of the SW 1/4.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">SW 1/16    S 27 1984</p>	
40.05	Point for the center W 1/16 sec. cor. of sec. 27	
20.075	<p>From the point for the center S 1/16 sec. cor. of sec. 27.</p> <p>N. 89° 52' W., on the E and W centerline of the SW 1/4 of sec. 27.</p>	
	The SW 1/16 sec. cor. of sec. 27.	
40.15	The S 1/16 sec. cor. of secs. 27 and 28.	
20.035	<p style="text-align: center;">Survey of the Subdivision of Section 28, T. 36 S., R. 22 E., Salt Lake Meridian, Utah</p> <p>From the 1/4 sec. cor. of secs. 28 and 33.</p> <p>North on the N and S centerline of sec. 28.</p> <p>Point for the center S 1/16 sec. cor. of sec. 28.</p>	

Survey of the Subdivision of Section 28,  
T. 36 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
	<p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">C S 1/16   S 28 C 1984</p>
40.07	<p>Point for the center 1/4 sec. cor. of sec. 28, at intersection with the E and W centerline.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">T 36 S R 22 E C 1/4 S 28 1984</p> <p>From which</p> <p style="padding-left: 40px;">A juniper, 12 ins. diam., bears S. 52° W., 6 1/2 lks. dist. mkd. C 1/4 S28 BT.</p>
60.07	Point for the center N 1/16 sec. cor. of sec. 28. Not monumented.
80.07	The 1/4 sec. cor. of secs. 21 and 28.
19.925	<p>From the 1/4 sec. cor. of secs. 27 and 28.</p> <p>N. 89° 36' W., on the E and W centerline of sec. 28</p> <p>Point for the center E 1/16 sec. cor of sec. 28</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">E 1/16 C ————— C S 28 1984</p>
39.85	The center 1/4sec. cor. of sec. 28.
59.92	<p>Point for the center west 1/16 sec. cor. of sec. 28.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">W 1/16 C ————— C S 28 1984</p>
79.99	<p>The 1/4 sec. cor. of secs. 28 and 29.</p> <hr/> <p>From the center E 1/16 sec. cor. of sec. 28.</p> <p>N. 0° 09' E., on the N and S centerline of the NE 1/4 of sec. 28.</p>

Survey of the Subdivision of Section 28,  
T. 36 S., R. 22 E., Salt Lake Meridian, Utah

20.04 <sup>CHAINS</sup>	<p>Point for the NE 1/16 sec. cor. of sec. 28, at intersection with the E and W centerline of the NE 1/4.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">NE 1/16   S 28 1984</p>
40.08	<p>Point for the E 1/16 sec. cor. of secs. 21 and 28</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 27 and 28.</p> <p>N. 89° 42' W., on the E and W centerline of the NE 1/4 of sec. 28.</p>
19.975	<p>The NE 1/16 sec. cor. of sec. 28.</p>
39.95	<p>Point for the center N 1/16 sec. cor. of sec. 28</p> <hr/> <p>From the E 1/16 sec. cor. of secs. 28 and 33.</p> <p>N. 0° 03' W., on the N and S centerline of the SE 1/4 of sec. 28.</p>
40.06	<p>The center E 1/16 sec. cor. of sec. 28.</p> <hr/> <p>From the W 1/16 sec. cor. of secs. 28 and 33.</p> <p>N. 0° 10' W., on the N and S centerline of the SW 1/4 of sec. 28.</p>
20.045	<p>Point for the SW 1/16 sec. cor. of sec. 28, at intersection with the E and W centerline of the SW 1/4.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">SW 1/16   S 28 1984</p>
40.09	<p>The center W 1/16 sec. cor. of sec. 28.</p> <hr/> <p>From the center S 1/16 sec. cor. of sec. 28.</p> <p>N. 89° 37' W., on the E and W centerline of the SW 1/4 of sec. 28.</p>
20.015	<p>The SW 1/16 sec. cor. of sec. 28.</p>
40.03	<p>The S 1/16 sec. cor. of secs. 28 and 29.</p> <hr/> <p>From the center west 1/16 sec. cor. of sec. 28</p> <p>N. 0° 04' E., on the N and S centerline of the NW 1/4 of sec. 28.</p>

Survey of the Subdivision of Section 28,  
T. 36 S., R. 22 E., Salt Lake Meridian, Utah

19.96	<p>CHAINS</p> <p>Point for the NW 1/16 sec. cor. of sec. 28, at intersection with the E and W centerline of the NW 1/4.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">NW 1/16 S 28 1984</p>
39.92	<p>Point for the W 1/16 sec. cor. of secs. 21 and 28.</p> <hr/> <p>From the point for the center N 1/16 sec. cor. of sec. 28.</p> <p>N. 89° 42' W., on the E and W centerline of the NW 1/4 of sec. 28.</p>
20.05	<p>The NW 1/16 sec. cor. of sec. 28.</p>
40.10	<p>The N 1/16 sec. cor. of secs. 28 and 29.</p> <hr/> <p style="text-align: center;">Survey of the Subdivision of Section 33, T. 36 S., R. 22 E., Salt Lake Meridian, Utah</p> <hr/> <p>From the 1/4 sec. cor. of secs. 4 and 33 on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0° 07' E., on the N and S centerline of sec. 33.</p>
39.86	<p>Point for the center 1/4 sec. cor. of sec. 33, at intersection with the E and W centerline of sec. 33.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 36 S R 22 E C 1/4   S 33 1984</p>
79.76	<p>The 1/4 sec. cor. of secs. 28 and 33.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 33 and 34.</p> <p>N. 89° 31' W., on the E and W centerline of sec. 33.</p>
20.05	<p>Point for the center east 1/16 sec. cor. of sec. 33.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">E 1/16 C ————— C S 33 1984</p>
40.10	<p>The center 1/4 sec. cor. of sec. 33.</p>

Survey of the Subdivision of Section 33,  
T. 36 S., R. 22 E., Salt Lake Meridian, Utah

CHAINS	
80.14	The 1/4 sec. cor. of secs. 32 and 33.
	From the E 1/16 sec. cor. of secs. 4 and 33, on the S. bdy. of the Tp., hereinbefore described.
	N. 0° 10' E., on the N and S centerline of the SE 1/4 of sec. 33.
39.95	The center E 1/16 sec. cor of sec. 33.
	Survey of the Subdivision of Section 34, T. 36 S., R. 22 E., Salt Lake Meridian, Utah
	From the 1/4 sec. cor. of secs. 3 and 34, on the S. bdy. of the Tp., hereinbefore described.
	N. 0° 02' E., on the N and S centerline of sec. 33.
40.20	Point for the center 1/4 sec. cor. of sec. 34, at intersection with the E and W centerline.
	Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a collar of stone, with aluminum cap mkd.
	T 36 S R 22 E C 1/4   S 34 1984
80.17	The 1/4 sec. cor. of secs. 27 and 34.
	From the point for the 1/4 sec. cor. of secs. 34 and 35.
	N. 89° 52' W., on the E and W centerline of sec. 34.
40.08	The center 1/4 sec. cor. of sec. 34.
60.065	Point for the center W 1/16 sec. cor. of sec. 34.
	Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top of aluminum cap, mkd.
	W 1/16 C ————— C S 34 1984
80.05	The 1/4 sec. cor. of secs. 33 and 34.
	From the center west 1/16 sec. cor. of sec. 33.
	N. 0° 03' W., on the N and S centerline of the NW 1/4 of sec. 34.
39.97	The W 1/16 sec. cor. of secs. 27 and 34.

## Township 36 South, Range 22 East, Salt Lake Meridian, Utah

CHAINS

## GENERAL DESCRIPTION

The area surveyed and resurveyed in T. 36 S., R. 22 E. is situated surrounding and immediately west of the city of Blanding, Utah. The city is located in sections 27 and 34. This area is located on a rolling mesa, vegetated with scattered to dense stands of pinon and juniper and draining to Westwater Creek. Westwater Creek bisects the area surveyed and drains south to Cottonwood Wash. The average elevation is approximately 6000 ft. U.S. Highway No. 163 passes through sections 27 and 34.



CERTIFICATE OF SURVEY

(I) ~~XXX~~, Richard A. Zaninovich, Cadastral Surveyor, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 20th day

of January, 1984, (I) ~~XXX~~ have dependently resurveyed a portion of the south boundary and a portion of the subdivisional lines, and a survey of the subdivision of sections 21, 27, 28, 33, and 34, T. 36 S., R. 22 E.,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), ~~XXX~~ and under (my) ~~XXX~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

January 2, 1986 (Date)

[Signature] (Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Washington, D.C.

The foregoing field notes of the dependent resurvey of a portion of the south boundary, a portion of the subdivisional lines and the survey of the subdivisional sections 21, 27, 28, 33, and 34 of T. 36 S., R. 22 E., Salt Lake Meridian, Utah

executed by Richard A. Zaninovich, Cadastral Surveyor having been critically examined and found correct, are hereby approved.

January 17, 1986 (Date)

[Signature] Chief Cadastral Surveyor for Utah

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

(Date)

[Signature] Chief Cadastral Surveyor for Utah

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

R 608

260

**ORIGINAL**  
**FIELD NOTES**  
OF THE

SURVEY OF THE WEST 1/2 MILE

BETWEEN

SECTIONS 5 AND 8,

TOWNSHIP 33 SOUTH, RANGE 4 1/2 WEST

Of the Salt Lake Meridian,  
Utah  
In the State of \_\_\_\_\_

EXECUTED BY

Val H. Schultz

Cadastral Surveyor

Under special instructions dated April 16, 1984, approved April 16, 1984

\_\_\_\_\_, which provided for the surveys included under U.S. Survey/Group  
Number 652, and assignment instructions dated April 17, 1984

Survey commenced April 18, 1984

Survey completed April 20, 1984

**JAMBIRO****INDEX DIAGRAM**Township 33 South, Range 4 1/2 West,

6	5 1	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

## Township 33 South, Range 4 1/2 West, Salt Lake Meridian, Utah

CHAINS

The following field notes describe the survey of the west 1/2 mile between sections 5 and 8, T. 33 S., R. 4 1/2 W., Salt Lake Meridian, Utah.

History of Surveys

<u>Surveyed by</u>	<u>Retr. or Resurveyed by</u>
--------------------	-------------------------------

WEST BOUNDARY (Panguitch Guide Meridian)

A11	Bailey and Burrill	1874	
A11			C.P. Sylvester and G.E. Reynolds 1978

NORTH BOUNDARY

Portion	J.G. Burrill	1874
---------	--------------	------

SOUTH BOUNDARY

Portion	J.G. Burrill	1874
---------	--------------	------

SUBDIVISION

Portion	J.G. Burrill	1874
---------	--------------	------

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group 652, Utah, dated April 6, 1984.

The geographic position of the corner to sections 5, 6, 7, and 8, was computed from a tie to a BLM corner marked T32S R5W S36 S31 S1 S6 T33S R5W R4 1/2W 1964 projecting 0.9 feet above the ground and was designated as a tri-station by the U.S.G.S. in 1966.

Latitude 37° 57' 49.64" N. Longitude 112° 20' 19.51" W.

The mean magnetic declination, as projected from the U.S. Geological Survey Magnetic Declination Map of 1980, is 14° E.

Survey of the West 1/2 Mile Between Sections 5 and 8,  
T. 33 S., R. 4 1/2 W., Salt Lake Meridian, Utah

Beginning at the cor. of secs. 5, 6, 7, and 8, monumented with a granite stone firmly set and plainly mkd., projecting 5 ins. above the ground, as described in the official record of the 1874 survey.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, and in a collar of rock and stone, with aluminum cap mkd.

T	33	S	R	4 1/2	W
	S	6		S	5
	S	7		S	8
				1984	

Survey of the West 1/2 Mile Between Sections 5 and 8,  
T. 33 S., R. 4 1/2 W., Salt Lake Meridian, Utah

CHAINS	
	<p>from which</p> <p>U.S.G.S. triangulation station "SEC COR 36/32S/5W", bears N. 43° 54' 29" W., 113..689 chs. dist., monumented with a BLM brass cap.</p> <p>Bury mkd. stone upside down alongside aluminum post.</p> <p>No suitable bearing trees within limits.</p> <p>East on true line between secs. 5 and 8.</p> <p>Over mountainous land, covered with pinon and juniper.</p>
4.60	Base of hill; asc. 100 ft. over SW slope.
15.20	Spur, bears SW and NE; desc. 130 ft.
25.80	Wash, drains SW. Ascend.
36.20	Top of ascent, large rock outcrop. Descend.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 8.
	<p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, and in a collar of earth and stone, with an aluminum cap mkd.</p> <p style="text-align: center;">           T 33 S R 4 1/2 W                      S 5            1/4     — S 8                      1984         </p> <p>No suitable bearing trees within limits.</p>



265

CERTIFICATE OF SURVEY

(I ~~was~~), Val H. Schultz, Cadastral Surveyor, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 16th day of April, 1984, (I ~~was~~) have surveyed the west one-half mile between sections 5 and 8, T. 33 S., R. 4 1/2 W.,

of the Salt Lake Base and Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), (I) and under (my) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

December 9, 1985 (Date)

Val H. Schultz (Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Washington, D.C.

The foregoing field notes of the survey of the west one-half mile between sections 5 and 8, T. 33 S., R. 4 1/2 W., Salt Lake Base and Meridian, Utah

executed by Val H. Schultz, Cadastral Surveyor having been critically examined and found correct, are hereby approved.

February 13, 1986 (Date)

Glen B Hatch Chief Cadastral Surveyor for Utah

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey)



ORIGINAL

267

# INDEX DIAGRAM

Township 39 South, Range 15 West

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	3	4
29	28	27	26	25	24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision of Section 23  
Tract 37

- Page 4  
- Page 7

## Township 39 South, Range 15 West, Salt Lake Meridian, Utah

## CHAINS

The following field notes describe the retracement of boundaries and partial subdivision of section 23, and the metes and bounds survey of Tract No. 37 in Section 23, Township 39 South, Range 15 West, Salt Lake Meridian, Utah.

History of Surveys

		<u>Surveyed by</u>		<u>Retr. or Resurveyed by</u>	
--	--	--------------------	--	-------------------------------	--

SOUTH BOUNDARY

Portion	H.D. Heist	1903			
Portion			Price and Bird	1918	

EAST BOUNDARY

Portion	T.C. Bailey	1877			
Portion			C.P. Sylvester	1963	

WEST BOUNDARY

Portion	T.C. Bailey	1877			
Portion	Price and Bird	1918			
Portion			Hatch and Sylvester	1970-71	

NORTH BOUNDARY

All	T.C. Bailey	1881			
All			Price and Bird	1918	

SUBDIVISION

Portion	Bailey and Burrill	1877			
Portion			C.P. Sylvester	1963	

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group 674, Utah, dated July 25, 1985.

The directions of lines were determined by solar instrument methods and by means of fore- and backsights and angular deflections from azimuths obtained by direct solar observations.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions, lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

In the subdivision of this section the legal center of section was first determined by running a straight line between the east and west quarter-section corners. A line was then run southerly on a bearing determined by meaning the bearings of the north half of the east and west section lines. The point of intersection of the lines thus run determine the legal point for the interior-quarter section corner.

## Township 39 South, Range 15 West, Salt Lake Meridian, Utah

## CHAINS

The sixteenth-section corners are established midway between section corners and quarter-section corners on the boundaries of the section or accepted in previous set position.

The subdivision of quarter sections into quarter-quarter sections is determined by running straight lines between opposite corresponding sixteenth-section corners. The point of intersection of the lines thus run determine the legal point for the interior sixteenth-section corners.

The geographic position of the 1/4 section corner of sections 23 and 24 was computed from a tie to U.S.G.S. monument 2-94X set in 1954, which is a cross chiseled on a boulder.

Latitude 37° 22' 48.71" N. Longitude 113° 29' 51.48" W.

The mean magnetic declination is determined to be 14° East from 1980 isogonic map.

---

Dependent Resurvey and Partial Section Subdivision  
of Section 23,  
T. 39 S., R. 15 W., Salt Lake Meridian, Utah

---

(Restoring the Survey Executed by Bailey and Burrill  
in 1888 and the Resurvey by  
C.P. Sylvester in 1967)

---

Beginning at the cor. of secs. 14, 15, 22, and 23, monumented with an iron post, 2 1/2 ins. diam., set and mkd. as described in the official record of the 1963 resurvey of a portion of T. 39 S., R. 15 W.

Over brushy, rough bench land.

S. 0° 02' W., bet. secs. 22 and 23.

7.50 Base of mountain, bears W and SE; asc. 150 ft. over northeast slope, through dense growth of mahogany.

19.993 The N 1/16 sec. cor. of secs. 22 and 23, monumented with an iron post, 2 1/2 ins. diam., set and mkd. as described in the official record of the 1963 resurvey of a portion of T. 39 S., R. 15 W.

---

S. 0° 02' E., beginning new measurement.

Asc. 40 ft. over NE slope, through dense mahogany.

5.00 Spur slopes E.; thence along broken E slope.

19.922 The 1/4 sec. cor. of secs. 22 and 23, monumented with an iron post, 2 1/2 ins. diam., set and mkd. as described in the official record of the 1963 resurvey of a portion of T. 39 S., R. 15 W.

---

Dependent Resurvey and Partial Section Subdivision  
of Section 23,  
T. 39 S., R. 15 W., Salt Lake Meridian, Utah

CHAINS	
	From the cor. of secs. 14, 15, 22, and 23, heretofore described.
	S. 89° 21' E., bet. secs. 14 and 23.
	Desc. 80 ft. over brushy mountain land.
7.70	E edge of pond, enter farm ground.
13.90	Fence bears NE and SW.
28.00	Wash, drains N.
35.27	Forest trail, bears SE from Pine Valley.
39.972	The 1/4 sec. cor. of secs. 14 and 23, monumented with an iron post, 2 1/2 ins. diam., set and mkd. as described in the official record of the 1963 resurvey of a portion of T. 39 S., R. 15 W.
	_____
	N. 89° 59' E., beginning new measurement.
17.46	Fence, bears NW and SE parallel to road.
17.505	U.S. Forest Service aluminum right-of-way marker.
18.724	Center line of asphalt road, bet. Pine Valley and Pine Valley Campground, on curve, from which tangent lines bear N. 65° 37' W. and S. 65° 37' E., not monumented.
19.867	The E 1/16 sec. cor. of secs. 14 and 23, monumented with a U.S. Forest Service aluminum post, 3 ins. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd.
	T 39 S R 15 W S 14 E 1/16    S 23 1985
	from which
	U.S. Geological Survey triangulation station, "2-94X", a cross chiseled on a boulder, bears N. 79° 20' 05" W., 5.395 chs. dist.
	This is accepted as a careful and faithful determination of the position of the corner.
	_____
	N. 89° 59' E., beginning new measurement.
	Over pasture land in Pine Valley.
0.059	U.S. Forest Service aluminum right-of-way marker.
9.35	Fence, bears N and S.
17.28	Fence, bears N and S.

Dependent Resurvey and Partial Section Subdivision  
of Section 23,  
T. 39 S., R. 15 W., Salt Lake Meridian, Utah

CHAINS	
19.867	The cor. of secs. 13, 14, 23, and 24, monumented with an iron post, 2 1/2 ins. diam., set and mkd. as described in the official record of the 1963 resurvey of a portion of T. 39 S., R. 15 W.
	S. 0° 40' W. bet. secs. 23 and 24.
9.679	U.S. Forest Service aluminum right-of-way marker.
9.70	Fence cor., with fences bearing NW parallel to road and N parallel to section line.
10.234	Center line of asphalt road, bet. Pine Valley and Pine Valley Campground, bears N. 63° 40' W., and S. 63° 40' E. Point for Cor. No. 1, Tract 37, sec. 23, hereinafter described.
10.789	U.S. Forest Service aluminum right-of-way marker, at cor. of fences bearing NW parallel to road and S on section line.
19.986	The N 1/16 sec. cor. of secs. 23 and 24, monumented with an iron post, 2 1/2 ins. diam., set and mkd. as described in the official record of the 1963 resurvey of a portion of T. 39 S., R. 15 W.
	S. 0° 39' W., beginning new measurement.
0.50	Fence cor., with fences bearing N on section line and E.
3.10	Road, 20 lks. wide, bears E and W.
13.70	Enter thick oakbrush.
19.979	The 1/4 sec. cor. of secs. 23 and 24, monumented with an iron post, 2 1/2 ins. diam., set and mkd. as described in the official record of the 1963 resurvey of a portion of T. 39 S., R. 15 W.
	Survey of a Portion of the Subdivision of Section 23, T. 39 S., R. 15 W., Salt Lake Meridian, Utah
	From the 1/4 sec. cor. of secs. 23 and 24.
	N. 89° 39' W., along the E-W center line of sec. 23.
	Across sagebrush bench.
12.10	Wash, drains NE. Ascend.
19.781	The CE 1/16 sec. cor. of sec. 23, monumented with a 1/2 in. rebar. This position is accepted as a careful and faithful determination of the position of the corner.
	Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

Survey of a Portion of the Subdivision of Section 23,  
T. 39 S., R. 15 W., Salt Lake Meridian, Utah

CHAINS

T 39 S R 15 W  
CE 1/16  
S 23

C ————— C  
1985

N. 89° 39' W., beginning new measurement.

Asc. over broken bench land covered with thick mahogany and oakbrush.

- 3.10 Wash, drains NE.  
4.50 Base of hill, bears NE and SW; asc. 80 ft.  
16.60 Edge of spur, slopes NW; desc. 70 ft.  
19.719 Point for the C 1/4 sec. cor. of the N 1/2 of sec. 23, at the intersection with the N-S center line of the N 1/2 of sec. 23.  
Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 35 S R 15 W

C  
|  
S 23 | C 1/4  
|  
C

C ————— C  
1985

from which

A mahogany, 6 ins. diam., bear N. 88° 15' E.,  
22.20 lks. dist., mkd. C 1/4 S23 BT.

A pinon pine, 10 ins. diam., bears N. 12° 15' W.  
40.10 lks. dist., mkd. C 1/4 S23 BT.

Across broken bench land covered with thick mahogany and oakbrush.

- 26.50 Wash, drains NE.  
32.00 Forest Service trail runs N and S.  
42.40 Wash, drains NE.  
56.80 Base of hill, asc. 100 ft. over E slope.  
59.456 The 1/4 sec. cor. of secs. 22 and 23, heretofore described.

From the 1/4 sec. cor. of secs. 14 and 23, heretofore described.

S. 0° 08' E., on the N-S center line of sec. 23.

Asc. over moderate N slope, across sagebrush bench.

Survey of a Portion of the Subdivision of Section 23,  
T. 39 S., R. 15 W., Salt Lake Meridian, Utah

12.50 <sup>CHAINS</sup>	Irrigation ditch, drains SW.
19.856	The CN 1/16 sec. cor. of sec. 23, monumented with a U.S. Forest Service iron pipe, 2 1/2 ins. diam., projecting 8 ins. above ground, with brass cap mkd.
	This position is accepted as a careful and faithful determination of the position of the corner.
	_____
	S. 0° 48' W., beginning new measurement.
0.20	Fence, bears N and S.
9.80	Enter thick mahogany and oakbrush.
19.848	The C 1/4 sec. cor. of sec. 23, heretofore described.
	From the CE 1/16 sec. cor. of sec. 23, heretofore described.
	N. 0° 33' E., along the N-S center line of the NE 1/4 of sec. 23, through sagebrush, scattered pinon and cedar tree parallel to barbed wire fence running N and S.
19.911	Point for the NE 1/16 sec. cor. of sec. 23, at the intersection with the E-W center line of the NE 1/4.
	Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a mound of earth and stone, 2 ft. base, to top of aluminum cap, mkd.
19.99	Fence, bears E and W.
38.81	Fence, bears NW and SE.
39.311	Center line of asphalt road, bet. Pine Valley and Pine Valley Campground, on curve, from which tangent lines bear N. 65° 12' W. and S. 65° 12' E., not monumented.
	From this point, the P.C. of the curve bears S. 64° 26' E., 4.657 chs. dist., hereinafter described.
39.81	Fence, bears NW and SE.
39.832	The E 1/16 sec. cor. of secs. 14 and 23, heretofore described.
	_____
	From the N 1/16 sec. cor. of secs. 23 and 24.
	N. 89° 50' W. on the E-W center line of the NE 1/4 of sec. 23, over sagebrush land along a barbed wire fence running E and W.

Survey of a Portion of the Subdivision of Section 23,  
T. 39 S., R. 15 W., Salt Lake Meridian, Utah

19.79 <sup>CHAINS</sup>	Fence, bears N and S.
19.821	Intersect the NE 1/16 sec. cor. of sec. 23, heretofore described.
31.12	Enter mahogany and oakbrush.
39.451	The CN 1/16 sec. cor. of sec. 23, heretofore described.
From the CN 1/16 sec. cor. of sec. 23.	
N. 89° 33' W., on the E-W center line of the NW 1/4.	
8.50	Wash, drains NNW.
10.30	Forest trail, bears S.
13.50	Wash, drains NNE.
40.027	The N 1/16 sec. cor. of secs. 22 and 23.

Survey of Tract 37,  
T. 39 S., R. 15 W., Salt Lake Meridian, Utah


Point for Cor. No. 1, Tract 37, falls in asphalt road bet. Pine Valley and Pine Valley Campground, and on the section line bet. secs. 23 and 24.

At the corner point

Set a PK nail flush with asphalt.

from which

An aluminum post, 30 ins. long, 2 1/2 ins. diam., set 30 ins. in the ground for a reference monument, bears N. 26° 20' E., 50 lks. dist. with aluminum cap mkd.




This RM is located in parking lot of Branding Iron Steak House.

An aluminum post, 30 ins. long, 2 1/2 ins. diam., set 17 ins. in the ground for a reference monument, bears S. 26° 20' W., 50 lks. dist. with aluminum cap mkd.

Survey of Tract 37,  
T. 39 S., R. 15 W., Salt Lake Meridian, Utah

CHAINS



N.  $63^{\circ} 40'$  W., on line 1-2 of Tract 37, along asphalt road.


16.576 Point for Cor. No. 2, Tract 37, Sec. 23, falls in asphalt road bet. Pine Valley and Pine Valley Campground.

At the corner point


Set a PK nail flush with asphalt.

from which

An aluminum post, 30 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground for a reference monument, bears N.  $26^{\circ} 20'$  E., 50 lks. dist. with aluminum cap mkd.



An aluminum post, 30 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground for a reference monument, bears S.  $26^{\circ} 20'$  W., 50 lks. dist. with aluminum cap mkd.



From this point, the P.C. of a curve to the left of the center line of asphalt road bet. Pine Valley and Pine Valley Campground, with a radius of 173.707 chs., bears N.  $63^{\circ} 40'$  W., 0.775 chs. dist., not monumented. This point was established with use of U.S. Forest Service Highway Information data.

S.  $0^{\circ} 33'$  W., on line 2-3 of Tract 37, parallel to the N-S center line of NE 1/4 sec. 23, T. 39 S., R. 15 W.

0.56 Fence, bears NW and SE parallel to road.

17.04 Fence, bears E and W.

Survey of Tract 37,  
T. 39 S., R. 15 W., Salt Lake Meridian, Utah

<p>CHAINS 17.061</p>	<p>The point for Cor. No. 3 of Tract 37 Sec. 23, at intersection with the E-W center line of the NE 1/4 of sec. 23.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of earth and stone, 2 ft. base, to top of aluminum cap, mkd.</p>
<p>14.904</p>	<p style="text-align: center;">T 39 S R 15 E TR-37</p> <p style="text-align: center;">  3 ----- 1985</p> <hr/> <p>S. 89° 50' E., on line 3-4 of Tract 37, along E-W center line of the NE 1/4, sec. 23, T. 39 S., R. 15 W.</p> <p>The N 1/16 sec. cor. of secs. 23 and 24, heretofore described which is also the point for Cor. No. 4, Tract 37, sec. 23. Therefore, I add the marks</p>
<p>9.752</p>	<p style="text-align: center;">TR-37 Cor 4 1985</p> <hr/> <p>N. 0° 40' E., on line 4-1 of Tract 37 identical with the section line bet. secs. 23 and 24.</p> <p>Cor. No. 1, Tract 37, Sec. 23, T. 39 S., R. 15 W. Point of beginning.</p>



CERTIFICATE OF SURVEY

(I) ~~(We)~~, Val H. Schultz, Cadastral Surveyor, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 25th day of July, 1985, (I) ~~(We)~~ have surveyed the boundaries and partial subdivision of section 23, T. 39 S., R. 15 W., and the metes and bounds survey of Tract No. 37 in section 23, T. 39 S., R. 15 W.,

of the Salt Lake Base and Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

December 6, 1985  
(Date)

*Val H. Schultz*  
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Washington, D.C.

The foregoing field notes of the survey of the boundaries and partial subdivision of section 23, T. 39 S., R. 15 W., and the metes and bounds survey of Tract No. 37 in section 23, T. 39 S., R. 15 W., SLB&M, Utah

executed by Val H. Schultz, Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

February 13, 1986  
(Date)

*Glen B. Hales*  
XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX  
Chief Cadastral Surveyor for Utah

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in \_\_\_\_\_ is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

R608

ORIGINAL

FIELD NOTES  
OF THE

279

DEPENDENT RESURVEY

OF A

PORTION OF THE EAST BOUNDARY (SECOND GUIDE MERIDIAN EAST),

THE SOUTH BOUNDARY OF SECTION 34,

THE EAST 1/2 MILE OF THE NORTH BOUNDARY OF SECTION 1,

A PORTION OF THE SUBDIVISIONAL LINES,

AND THE

SURVEY OF A PORTION OF THE SUBDIVISION

OF SECTIONS 1, 12, 13, 14, 22, 23, 24, 25, 26, 27, 34, AND 35

OF

TOWNSHIP 19 SOUTH, RANGE 7 EAST,

Of the Salt Lake Meridian,

In the State of Utah

EXECUTED BY

Jerry L. Thomas

Supervisory Cadastral Surveyor

Under special instructions dated September 1, 19 82, approved September 2, 1982

\_\_\_\_\_, which provided for the surveys included under ~~U.S. Survey~~ <sup>XXXXXX</sup> Group  
Number 619, and assignment instructions dated September 10, 1982

Survey commenced September 13, 19 82

Survey completed May 4, 19 84

# INDEX DIAGRAM

Township 19 South, Range 7 East,

6	5	4	3	2	5 1	3
7	8	9	10	11 9 13	12 8	3
18	17	16	15	14 12	13	
19	20	21 15	22 12	23 7	24 3	
			16	11	7	
30	29	28 14	27 11	26 6	25 2	
			14	10	5	
31	32	33 13	34 9 4	35	36	

- Subdivision of Section 1 - Page 16
- Subdivision of Section 12 - Page 17
- Subdivision of Section 13 - Page 18
- Subdivision of Section 14 - Page 19
- Subdivision of Section 22 - Page 21
- Subdivision of Section 23 - Page 21
- Subdivision of Section 24 - Page 23
- Subdivision of Section 25 - Page 25
- Subdivision of Section 26 - Page 26
- Subdivision of Section 27 - Page 27
- Subdivision of Section 34 - Page 28
- Subdivision of Section 35 - Page 30

## Township 19 South, Range 7 East, Salt Lake Meridian, Utah

CHAINS

The following field notes describe the dependent resurvey of a portion of the east boundary (Second Guide Meridian East), the south boundary of section 34, the east 1/2 mile of the north boundary of section 1, a portion of the subdivisional lines and the survey of a portion of the subdivision of sections 1, 12, 13, 14, 22, 23, 24, 25, 26, 27, 34, and 35, Township 19 South, Range 7 East, Salt Lake Meridian, Utah.

History of Surveys

<u>Surveyed by</u>	<u>Retr. or Resurveyed by</u>
--------------------	-------------------------------

EAST BOUNDARY (Second Guide Meridian East)

All	A.D. Ferron	1873	
All		J.L. Thomas	1975

SOUTH BOUNDARY

E. 4 miles	A.D. Ferron	1873	
W. 2 miles	J.W. Dougall	1911	
Portion		J.W. Dougall	1911
E. 2 miles		Hatch and Tuft	1962

NORTH BOUNDARY

E. 2 miles	A.D. Ferron	1873	
Portion	F.W. Hanson	1905	
Portion		F.W. Hanson	1905
W. 2 miles	J.W. Dougall	1911	
Portion		J.W. Dougall	1911
E. 2 miles		J.T. Thomas	1975

SUBDIVISION

E. portion	A.D. Ferron	1873	
W. portion	J.W. Dougall	1911	
Portion		J.W. Dougall	1911
Secs. 13 and 35		J.L. Thomas	1975

The resurvey and survey were executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group 619, Utah, dated September 1, 1982.

The directions of lines were determined by reference to true meridians established on line by altitude observations on the sun, and by hour angle observations on Polaris. The lines were carried forward by sustained angulations, being supplemented by other observations on Polaris taken throughout the progress of the survey. Distances were determined by electronic measurement.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions, lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic coordinates of the cors. of Tps. 19 and 20 S., Rs. 7 and 8 E., and secs. 1, 2, 35, and 36, on the N. bdy. of the township, as determined by satellite methods, are as follows:

## Township 19 South, Range 7 East, Salt Lake Meridian, Utah

## CHAINS

Latitude  $39^{\circ} 07' 03.395''$  N. Longitude  $111^{\circ} 04' 28.752''$  W.  
 Latitude  $39^{\circ} 12' 20.084''$  N. Longitude  $111^{\circ} 05' 41.744''$  W.

These corners are designated as BLM control stations.

The geographic coordinates of the cor. of sections 25, 30, 31 and 36, on the E. bdy. of the Tp., as determined by calculations from the BLM control stations, are as follows:

Latitude  $39^{\circ} 07' 55.96''$  N. Longitude  $111^{\circ} 04' 29.39''$  W.

The mean magnetic declination as projected from U.S. Geological Survey "Magnetic Declination Map of 1980," is  $14^{\circ}$  E.

Dependent Resurvey of a Portion of the East Boundary  
 (2nd Guide Meridian East),  
 T. 19 S., R. 7 E., Salt Lake Meridian, Utah

(Restoring the Survey Executed by A.D. Ferron in 1873  
 and the Retracement by J.L. Thomas in 1975)

From the cor. of secs. 25, 30, 31, and 36, monumented with an iron post, 2 1/2 ins. diam., buried 6 ins. below surface of gravel road, with brass cap, mkd. as described in the official record of the 1975 retracement of a portion of the E. bdy. of T. 19 S., R. 7 E.

N.  $0^{\circ} 28'$  W., bet. secs. 25 and 30.

Over gentle rolling land.

40.05

The 1/4 sec. cor. of secs. 25 and 30, monumented with an unmkd. wooden stake, 2 ins. sq., projecting 3 ins. above ground at cor. of fences extending N, S, and W. This position is harmoniously related to existing original cors., and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 19 S  
 R 7 E R 8 E  
 1/4  
 S 25 | S 30  
 1983

N.  $0^{\circ} 28'$  W., beginning new measurement.

40.74

The cor. of secs. 19, 24, 25, and 30, monumented with a brass cap, 3 ins. diam., imbedded in concrete cylinder, 6 ins. diam., with brass cap mkd. T19S R7E R8E S19 S24 S25 S30 1975 King RLS 1929, and is accepted as a careful and faithful perpetuation of the position of the original corner.

Dependent Resurvey of a Portion of the East Boundary  
(Second Guide Meridian East),  
T. 19 S., R. 7 E., Salt Lake Meridian, Utah

CHAINS	
	<p>N. 0° 28' W., bet. secs. 19 and 24.</p> <p>Over rolling land.</p>
20.38	<p>The S 1/16 sec. cor. of secs. 19 and 24, monumented with an aluminum post, 2 1/2 ins. diam., protruding 6 ins. above ground, and mkd. T19S R7E R8E S 1/16 S24 S19 1975 King RLS 1929, and is accepted as a careful and faithful determination of the cor. position.</p>
	<p>N. 0° 28' W., beginning new measurement.</p>
20.38	<p>The 1/4 sec. cor. of secs. 19 and 24, monumented with a brass cap, 3 ins. diam., imbedded in concrete cylinder, 6 ins. diam., projecting 6 ins. above ground, and mkd. T19S R7E R8E 1/4 S19 S24 1975 King RLS 1929, and is accepted as a careful and faithful perpetuation of the position of the original corner.</p>
	<p>N. 0° 28' W., beginning new measurement.</p>
40.76	<p>The cor. of secs. 13, 18, 19, and 24, monumented with an iron post, 2 1/2 ins. diam., buried 6 ins. below surface of dirt road, with brass cap, mkd. as described in the official record of the 1975 resurvey of a portion of the E. bdy. of T. 19 S., R. 7 E.</p>
	<p>From the cor. of secs. 7, 12, 13, and 18, monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1975 resurvey of the E. bdy. of T. 19 S., R. 7 E.</p>
	<p>N. 0° 26' W., bet. secs. 7 and 12.</p>
	<p>Over rolling bench land.</p>
19.98	<p>Point for the S 1/16 sec. cor. of secs. 7 and 12.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>
	<p style="text-align: center;">T 19 S R 7 E R 8 E S 1/16 S 12   S 7 1983</p>
39.96	<p>The 1/4 sec. cor. of secs. 7 and 12, monumented with an iron post, 2 1/2 ins. diam., projecting 4 ins. above ground, with brass cap, mkd. as described in the official record of the 1975 resurvey of a portion of the E. bdy. of T. 19 S., R. 7 E.</p>
	<p>From the 1/4 sec. cor. of secs. 1 and 6, monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1975 resurvey of a portion of the E. bdy. of T. 19 S., R. 7 E.</p>
	<p>N. 0° 35' W., bet. secs. 1 and 6.</p>
	<p>Over nearly level land.</p>

Dependent Resurvey of a Portion of the East Boundary  
(Second Guide Meridian East),  
T. 19 S., R. 7 E., Salt Lake Meridian, Utah

CHAINS

- 20.27 Point for the N 1/16 sec. cor. of secs. 1 and 6.  
Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.
- T 19 S  
R 7 E R 8 E  
N 1/16  
S 1 | S 6  
1983
- Cor. is located 6 lks. E of N and S fence line.
- 40.54 The cor. of Tps. 18 and 19 S., Rs. 7 and 8 E., monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1975 resurvey of a portion of the E. bdy. of T. 19 S., R. 7 E.
- 
- Dependent Resurvey of a Portion of the South Boundary,  
T. 19 S., R. 7 E., Salt Lake Meridian, Utah
- 
- (Restoring the Survey Executed by A.D. Ferron in 1873  
and the Resurvey by Hatch and Tuft in 1962).
- 
- Beginning at the cor. of secs. 2, 3, 34, and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap, mkd. as described in the official record of the 1962 resurvey of the N. bdy. of T. 20 S., R. 7 E.
- N. 89° 47' W., bet. secs. 3 and 34.
- Over rolling land.
- 20.23 Point for the E 1/16 sec. cor. of secs. 3 and 34.  
Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.
- T 19 S R 7 E  
S 34  
E 1/16     S 3  
T 20 S  
1983
- 40.46 The 1/4 sec. cor. of secs. 3 and 34, monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1962 resurvey of the N. bdy. of T. 20 S., R. 7 E.
- 
- N. 89° 47' W., beginning new measurement.
- 20.69 Point for the W 1/16 sec. cor. of secs. 3 and 34.  
Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.
- T 19 S R 7 E  
S 34  
W 1/16     S 3  
T 20 S  
1983

Dependent Resurvey of a Portion of the South Boundary,  
T. 19 S., R. 7 E., Salt Lake Meridian, Utah

CHAINS	
41.38	<p>The cor. of secs. 3, 4, 33, and 34, monumented with an iron post, 2 1/2 ins. diam., set flush with surface of ground, with brass cap, mkd. as described in the official record of the 1962 resurvey of the N. bdy. of T. 20 S., R. 7 E.</p>
	<p>Dependent Resurvey of a Portion of the North Boundary, T. 19 S., R. 7 E., Salt Lake Meridian, Utah</p>
	<p>From the cor. of Tps. 18 and 19 S., Rs. 7 and 8 E. N. 89° 56' W., bet. secs. 1 and 36. Over nearly level land.</p>
20.72	<p>Point for the E 1/16 sec. cor. of secs. 1 and 36. Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 18 S R 7 E S 36 E 1/16 S 1 T 19 S 1983</p> </div>
41.44	<p>The 1/4 sec. cor. of secs. 1 and 36, monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1975 resurvey of a portion of the N. bdy. of T. 19 S., R. 7 E.</p>
	<p>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 19 S., R. 7 E., Salt Lake Meridian, Utah</p>
	<p>(Restoring the Survey Executed by A.D. Ferron in 1873)</p>
	<p>From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., heretofore described. N. 89° 59' W., bet. secs. 25 and 36. Along gravel road.</p>
39.50	<p>The 1/4 sec. cor. of secs. 25 and 36, determined latitudinally by dirt road, bears E and W, and longitudinally by fence lines extending N and S. Set a spike, 8 ins. long, flush with surface of road. from which An aluminum post, 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 45° 00' E., 62 lks. dist., with aluminum cap, mkd. T19S R7E S25 RM 1983 and an arrow pointing to the cor.</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 19 S., R. 7 E., Salt Lake Meridian, Utah

CHAINS	
	<p>An aluminum post, 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 45° 00' E., 54 1/2 lks. dist., with aluminum cap, mkd. T19S R7E S36 RM 1983 and an arrow pointing to the cor.</p>
	<p>An aluminum post, 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 45° 00' W., 55 1/2 lks. dist., with aluminum cap, mkd. T19S R7E S36 RM 1983 and an arrow pointing to the cor.</p>
	<p>An aluminum post, 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 45° 00' W., 90 lks. dist., with aluminum cap, mkd. T19S R7E S25 RM 1983 and an arrow pointing to the cor.</p>
	<p>N. 89° 59' W., beginning new measurement.</p>
40.24	<p>The cor. of secs. 25, 26, 35, and 36, monumented with a spike buried 6 ins. below the surface of the road, and two reference monuments, set and mkd. as described in the official record of the 1975 resurvey of a portion of the subdivisional lines of T. 19 S., R. 7 E</p>
	<p>N. 0° 56' W., bet. secs. 25 and 26.</p>
	<p>Over nearly level land.</p>
41.14	<p>Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>
	<p style="text-align: center;">T 19 S R 7 E 1/4 S 26   S 25 1983</p>
	<p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.</p>
61.71	<p>Point for the N 1/16 sec. cor. of secs. 25 and 26.</p>
	<p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>
	<p style="text-align: center;">T 19 S R 7 E N 1/16 S 26   S 25 1983</p>
82.28	<p>The cor. of secs. 23, 24, 25, and 26, monumented with a brass cap, 3 ins. diam., imbedded in concrete, flush with surface of road, with brass cap, mkd. T19S R7E S23 S24 S25 S26 1975 King RLS 1929, and is accepted as a careful and faithful perpetuation of the position of the original corner. No improvements are necessary.</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 19 S., R. 7 E., Salt Lake Meridian, Utah

CHAINS	
	<p>From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., heretofore described.</p> <p>N. 88° 58' W., bet. secs. 24 and 25.</p> <p>Over rolling bench land.</p>
20.11	<p>Point for the E 1/16 sec. cor. of secs. 24 and 25.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 19 S R 7 E S 24 E 1/16 <u>S 25</u> 1983</p>
40.22	<p>The 1/4 sec. cor. of secs. 24 and 25, monumented with a brass cap, 3 ins. diam., imbedded in concrete, flush with surface of road and mkd. T19S R7E 1/4 S24 S25 1975 King RLS 1929, and is accepted as a careful and faithful perpetuation of the position of the original corner. No improvements are necessary.</p> <p style="text-align: center;">N. 88° 55' W., beginning new measurement.</p>
20.12	<p>Point for the W 1/16 sec. cor. of secs. 24 and 25.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 19 S R 7 E S 24 W 1/16 <u>S 25</u> 1983</p>
40.24	<p>The cor. of secs. 23, 24, 25, and 26.</p> <p style="text-align: center;">N. 1° 00' W., bet. secs. 23 and 24.</p> <p>Over gentle rolling land.</p>
20.36	<p>Point for the S 1/16 sec. cor. of secs. 23 and 24.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">T 19 S R 7 E S 1/16 S 23   S 24 1983</p>
40.72	<p>The 1/4 sec. cor. of secs. 23 and 24, monumented with a rebar, projecting 6 ins. above ground. This point was shown to me by local surveyors and is the position of the 1/4 sec. cor. according to a local resident of the area, is harmoniously related to identified original cors., and is accepted as the best available evidence of the original corner position.</p> <p>At the corner point</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 19 S., R. 7 E., Salt Lake Meridian, Utah

## CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 19 S R 7 E  
1/4  
S 23 | S 24  
1983

N. 1° 00' W., beginning new measurement.

Over gentle rolling land

40.77

The cor. of secs. 13, 14, 23, and 24, monumented with a brass tablet, imbedded in a cylinder of concrete, 6 ins. diam., projecting 6 ins. above ground, as described in the official record of the 1975 resurvey of a portion of the subdivisional lines of T. 19 S., R. 7 E.

From the 1/4 sec. cor. of secs. 13 and 14, monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. above ground, with brass cap mkd. as described in the official record of the 1975 resurvey of a portion of the subdivisional lines of T. 19 S., R. 7 E.

N. 0° 40' W., bet. secs. 13 and 14.

Over nearly level land.

20.46

Point for the N 1/16 sec. cor. of secs. 13 and 14.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 19 S R 7 E  
N 1/16  
S 14 | S 13  
1983

40.92

The cor. of secs. 11, 12, 13, and 14, monumented with an iron post, 2 ins. diam., projecting 10 ins. above ground, with brass cap mkd. as described in the official record of the 1911 resurvey of a portion of the subdivisional lines of T. 19 S., R. 7 E.

(Restoring the Survey Executed by  
A.D. Ferron in 1873, and the Resurvey by  
J.L. Thomas in 1975)

From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., heretofore described.

N. 88° 19' W., bet. secs. 12 and 13.

Over gentle rolling land.

20.205

Point for the E 1/16 sec. cor. of secs. 12 and 13.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 19 S., R. 7 E., Salt Lake Meridian, Utah

CHAINS	
40.41	<p style="text-align: center;">T 19 S R 7 E S 12 E 1/16 S 13 1983</p> <p>The 1/4 sec. cor. of secs. 12 and 13, monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1975 resurvey of a portion of the subdivisional lines of T. 19 S., R. 7 E.</p> <hr/> <p style="text-align: center;">(Restoring the Survey Executed by A.D. Ferron in 1873, and the Resurvey by J.W. Dougall in 1911)</p> <hr/> <p>From the cor. of secs. 11, 12, 13, and 14. N. 0° 51' W., bet. secs. 11 and 12. Over rolling bench land.</p>
20.20	<p>Point for the S 1/16 sec. cor. of secs. 11 and 12. Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 19 S R 7 E S 1/16 S 11   S 12 1983</p> <p>Cor. is located alongside fence cor. post, with fences bearing S and E.</p>
40.40	<p>The 1/4 sec. cor. of secs. 11 and 12, monumented with an iron post, 1 in. diam., projecting 10 ins. above ground, with brass cap, mkd. as described in the official record of the 1911 resurvey of a portion of the subdivisional lines of T. 19 S., R. 7 E.</p> <hr/> <p style="text-align: center;">(Restoring the Survey Executed by A.D. Ferron in 1873 and the Resurvey by J.L. Thomas in 1975)</p> <hr/> <p>From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1962 resurvey of the N. bdy. of T. 20 S., R. 7 E. N. 0° 11' W., bet. secs. 34 and 35. Over rolling land.</p>
20.14	<p>Point for the S 1/16 sec. cor. of sec. 34 and 35. Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 19 S R 7 E S 1/16 S 34   S 35 1983</p>

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 19 S., R. 7 E., Salt Lake Meridian, Utah

CHAINS	
40.28	<p>The 1/4 sec. cor. of secs. 34 and 35, monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1975 resurvey of a portion of the subdivisional lines of T. 19 S., R. 7 E.</p> <p style="text-align: center;">_____</p> <p>N. 0° 11' W., beginning new measurement.</p> <p>Asc. over S slope.</p>
10.07	<p>Point for the south north 1/64 sec. cor. of secs. 34 and 35.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">S-N 1/64 S 34   S 35 1982</p>
20.14	<p>True point for the N 1/16 sec. cor. of secs. 34 and 35, falls on steep S slope of spur, and is unsafe to monument.</p>
21.24	<p>Point selected for the witness cor. to the N 1/16 sec. cor. of secs. 34 and 35.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">W C T 19 S R 7 E N 1/16 S 34   S 35 ↓ 1982</p>
40.28	<p>The cor. of secs. 26, 27, 34, and 35, monumented with an iron post, 2 ins. diam., projecting 12 ins. above ground, with brass cap, mkd. as described in the official record of the 1911 resurvey of a portion of the subdivisional lines of T. 19 S., R. 7 E.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 26 and 35, monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1975 resurvey of a portion of the subdivisional lines of T. 19 S., R. 7 E.</p> <p>S. 89° 58' W., bet. secs. 26 and 35.</p> <p>Over rolling land.</p> <p>20.60 Point for the W 1/16 sec. cor. of secs. 26 and 35.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 19 S R 7 E S 26 W 1/6 — S 35 1982</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 19 S., R. 7 E., Salt Lake Meridian, Utah

CHAINS	
41.20	The cor. of secs. 26, 27, 34, and 35.
	(Restoring the Survey Executed by A.D. Ferron in 1873 and the Resurvey Executed by S.W. Dougall in 1911)
	N. 0° 10' E., bet. secs. 26 and 27 Over rolling land.
20.775	Point for the S 1/16 sec. cor. of secs. 26 and 27.
	Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	$\begin{array}{c} T\ 19\ S\ R\ 7\ E \\ S\ 1/16 \\ S\ 27\   \ S\ 26 \\ 1982 \end{array}$
41.55	The 1/4 sec. cor. of secs. 26 and 27, monumented with the bottom portion of an iron post, 1 in. diam. in place, and the top portion with brass cap and badly rusted pipe, laying alongside.
	At the corner point
	Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	$\begin{array}{c} T\ 19\ S\ R\ 7\ E \\ 1/4 \\ S\ 27\   \ S\ 26 \\ 1982 \end{array}$
	Deposit the remains of the original iron post alongside the aluminum post.
	N. 0° 10' E., beginning new measurement.
41.54	The cor. of secs. 22, 23, 26, and 27, monumented with an iron post, 2 ins. diam., set flush with the surface of dirt road, with brass cap, mkd. as described in the official record of the 1911 resurvey of a portion of the subdivisional lines of T. 19 S., R. 7 E.
	From the cor. of secs. 23, 24, 25, and 26.
	N. 89° 22' W., bet. secs. 23 and 26.
	Over gentle rolling land.
39.94	The 1/4 sec. cor. of secs. 23 and 26, monumented with an iron post, 2 ins. diam., projecting 14 ins. above ground, with brass cap, mkd. as described in the official record of the 1911 resurvey of a portion of the subdivisional lines of T. 19 S., R. 7 E.
	N. 89° 27' W. beginning new measurement.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 19 S., R. 7 E., Salt Lake Meridian, Utah

CHAINS	
39.94	<p>The cor. of secs. 22, 23, 26, and 27.</p> <hr/> <p>N. 0° 58' W., bet. secs. 22 and 23.</p> <p>Over rolling land.</p>
20.265	<p>Point for the S 1/16 sec. cor. of secs. 22 and 23.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 19 S R 7 E S 1/16 S 22   S 23 1983</p> </div> <p>Cor. is located 2 lks. W of fence cor., fence bears S and E.</p>
40.53	<p>True point for the 1/4 sec. cor. of secs. 22 and 23, from which the witness cor., an iron post, 2 ins. diam., projecting 12 ins. above ground, with brass cap, mkd. as described in the official record of the 1911 resurvey of a portion of the subdivisional lines of T. 19 S., R. 7 E., bears E, 45 lks. dist.</p> <hr/> <p>N. 0° 58' W., beginning new measurement.</p> <p>Over rolling land.</p>
20.25	<p>Point for the N 1/16 sec. cor. of sec. 23 only.</p> <p>Set a PVC post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 19 S R 7 E   N 1/16   S 23 1983</p> </div>
36.49	<p>The closing cor. of secs. 15 and 22, monumented with an iron post, 2 ins. diam., projecting 14 ins. above ground, with brass cap, mkd. as described in the official record of the 1911 resurvey of a portion of the subdivisional lines of T. 19 S., R. 7 E.</p>
40.50	<p>The cor. of secs. 14 and 23, monumented with an iron post, 2 ins. diam., projecting 12 ins. above ground, with brass cap, mkd. as described in the official record of the 1911 resurvey of a portion of the subdivisional lines of T. 19 S., R. 7 E.</p> <hr/> <p>From the cor. of secs. 13, 14, 23, and 24.</p> <p>N. 89° 46' W., bet. secs. 14 and 23.</p> <p>Over nearly level land.</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 19 S., R. 7 E., Salt Lake Meridian, Utah

CHAINS	
39.91	<p>True point for the 1/4 sec. cor. of secs. 14 and 23, at proportionate distance, falls in irrigation ditch and cannot be monumented; there is no remaining evidence of the original corner.</p>
40.10	<p>Point selected for the witness cor. to the 1/4 sec. cor. of secs. 14 and 23.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> $\begin{array}{r} \text{W C} \\ \text{T 19 S R 7 E} \\ \text{S 14} \\ \text{1/4 } \frac{\text{S 23}}{\text{1983}} \end{array}$ <p>Cor. is located in fence line, bears E and W.</p>
59.865	<p>Point for the W 1/16 sec. cor. of secs. 14 and 23.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> $\begin{array}{r} \text{T 19 S R 7 E} \\ \text{S 14} \\ \text{W 1/16 } \frac{\text{S 23}}{\text{1983}} \end{array}$ <p>Cor. is located near S edge of dirt road.</p>
79.82	<p>The cor. of secs. 14 and 23.</p> <hr/> <p>From the cor. of secs. 11, 12, 13, and 14.</p> <p>N. 89° 57' W., bet. secs. 11 and 14.</p> <p>Over rolling land.</p>
20.015	<p>Point for the E 1/16 sec. cor. of secs. 11 and 14.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> $\begin{array}{r} \text{T 19 S R 7 E} \\ \text{S 11} \\ \text{E 1/16 } \frac{\text{S 14}}{\text{1983}} \end{array}$
40.03	<p>The 1/4 sec. cor. of secs. 11 and 14, monumented with an iron post, 1 ins. diam., projecting 12 ins. above ground, with brass cap, mkd. as described in the official record of the 1911 resurvey of a portion of the subdivisional lines of T. 19 S., R. 7 E.</p> <hr/> <p>From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., heretofore described.</p> <p>N. 0° 04' W., bet. secs. 33 and 34.</p> <p>Over gently rolling land.</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 19 S., R. 7 E., Salt Lake Meridian, Utah

CHAINS	
19.50	<p>Point selected for the witness cor. to the S 1/16 sec. cor. of secs. 33 and 34.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.</p> <p style="text-align: center;">W C T 19 S R 7 E S 1/16 S 33 ↑ S 34 1983</p>
20.07	<p>True point for the S 1/16 sec. cor. of secs. 33 and 34, falls on S face of clay butte and cannot be monumented.</p>
40.14	<p>The 1/4 sec. cor. of secs. 33 and 34, monumented with an iron post, 1 in. diam., projecting 12 ins. above ground, with brass cap, mkd. as described in the official record of the 1911 resurvey of a portion of the subdivisional lines of T. 19 S., R. 7 E.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 04' W., beginning new measurement.</p>
40.14	<p>The cor. of secs. 27, 28, 33, and 34, monumented with an iron post, 2 ins. diam. projecting 12 ins. above ground, with brass cap, mkd. as described in the official record of the 1911 resurvey of a portion of the subdivisional lines of T. 19 S., R. 7 E.</p>
	<hr/> <p>From the cor. of secs. 26, 27, 34, and 35.</p> <p>S. 89° 59' W., bet. secs. 27 and 34.</p> <p>Over rolling land.</p>
20.41	<p>Point for the E 1/16 sec. cor. of secs. 27 and 34.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 19 S R 7 E S 27 E 1/16    <u>S 34</u> 1983</p>
40.82	<p>The 1/4 sec. cor. of secs. 27 and 34, monumented with an iron post, 1 in. diam. projecting 10 ins. above ground, with brass cap, mkd. as described in the official record of the 1911 resurvey of a portion of the subdivisional lines of T. 19 S., R. 7 E.</p> <hr/> <p style="text-align: center;">(Restoring the Survey Executed by J.W. Dougall in 1911)</p> <hr/> <p>From the cor. of secs. 27, 28, 33, and 34.</p> <p>N. 0° 01' E., bet. secs. 27 and 28, along Sectional Guide Meridian.</p> <p>Over rolling bench land.</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 19 S., R. 7 E., Salt Lake Meridian, Utah

CHAINS	
40.02	<p>The 1/4 sec. cor. of secs. 27 and 28, monumented with an iron post, 1 in. diam. projecting 10 ins. above ground, with brass cap, mkd. as described in the official record of the 1911 resurvey of a portion of the subdivisional lines of T. 19 S., R. 7 E. I destroy the marks pertaining to sec. 27. This cor. now functions as the 1/4 sec. cor. of sec. 28 only. Add the marks 1983 on the brass cap.</p>
	<p>N. 0° 01' W., beginning new measurement.</p>
1.50	<p>Point for the west 1/4 sec. cor. of sec. 27 only, based on the plat of the 1911 resurvey.</p>
	<p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>
	<p style="text-align: center;">T 19 S R 7 E   1/4   S 27 1983</p>
40.04	<p>The cor. of secs. 21 and 28, monumented with an iron post, 1 in. diam. projecting 12 ins. above ground, with brass cap, mkd. as described in the official record of the 1911 resurvey of a portion of the subdivisional lines of T. 19 S., R. 7 E.</p>
	<p>N. 0° 02' W., on the E. bdy. of sec. 21, along Sectional Guide Meridian.</p>
	<p>Over rolling bench land.</p>
2.98	<p>The closing cor. of secs. 22 and 27, monumented with an iron post, 2 in. diam. projecting 12 ins. above ground, with brass cap, mkd. as described in the official record of the 1911 resurvey of a portion of the subdivisional lines of T. 19 S., R. 7 E.</p>
40.09	<p>The 1/4 sec. cor. of secs. 21 and 22, monumented with an iron post, 1 in. diam. projecting 12 ins. above ground, with brass cap, mkd. as described in the official record of the 1911 resurvey of a portion of the subdivisional lines of T. 19 S., R. 7 E. I destroy marks pertaining to sec. 22. This cor. now function as the 1/4 cor. of sec. 21 only. Add the marks 1983 on the brass cap.</p>
	<p>N. 0° 02' E., beginning new measurement.</p>
2.92	<p>Point for the 1/4 sec. cor. of sec. 22 only, based on the plat of the 1911 resurvey.</p>
	<p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>
	<p style="text-align: center;">T 19 S R 7 E   1/4   S 22 1983</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 19 S., R. 7 E., Salt Lake Meridian, Utah

CHAINS	
39.97	<p>The cor. of secs. 15, 16, 21 and 22, monumented with an iron post, 2 in. diam. projecting 14 ins. above ground, with brass cap, mkd. as described in the official record of the 1911 resurvey of a portion of the subdivisional lines of T. 19 S., R. 7 E.</p> <hr/> <p>(Restoring the Survey Executed by A.D. Ferron in 1873 and the Resurvey Executed by J.W. Dougall in 1911)</p> <hr/> <p>From the cor. of secs. 22, 23, 26, and 27. S. 89° 58' W., bet. secs. 22 and 27. Over gentle rolling land.</p>
40.96	<p>The 1/4 sec. cor. of secs. 22 and 27, monumented with an iron post, 1 in. diam. projecting 14 ins. above ground, with brass cap, mkd. as described in the official record of the 1911 resurvey of a portion of the subdivisional lines of T. 19 S., R. 7 E.</p> <hr/> <p>(Restoring the Survey Executed by J.W. Dougall in 1911)</p> <hr/> <p>N. 89° 57' W., beginning new measurement.</p>
40.92	<p>The closing cor. of secs. 22 and 27, hereinbefore described.</p> <hr/> <p>Partial Subdivisional Survey of Section 1, T. 19 S., R. 7 E., Salt Lake Meridian, Utah</p> <hr/> <p>From the 1/4 sec. cor. of secs. 1 and 12. N. 0° 54' W., on the N and S center line of sec. 1.</p>
40.40	<p>Point for the center 1/4 sec. cor. of sec. 1, at intersection with the E and W center line. Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.</p> <p style="text-align: center;">T 19 S R 7 E C 1/4 S 1 1983</p>
60.555	<p>Point for the center north 1/16 sec. cor. of sec. 1. Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">C N 1/16   S 1 C 1983</p>

Partial Subdivisional Survey of Section 1,  
T. 19 S., R. 7 E., Salt Lake Meridian, Utah

CHAINS	
79.98	<p>Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W of cor.</p> <p>The 1/4 sec. cor. of secs. 1 and 36, on the N. bdy. of the Tp., heretofore described.</p>
20.63	<p>From the 1/4 sec. cor. of sec. 1 and 6, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 88° 34' W., on the E and W center line of sec. 1.</p> <p>Point for the center east 1/16 sec. cor. of sec. 1.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;"> <math display="block">C \frac{E \ 1/16}{S \ 1} C</math>                     1983                 </p>
41.26	<p>The center 1/4 sec. cor. of sec. 1.</p>
82.08	<p>The 1/4 sec. cor. of secs. 1 and 2, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap, mkd. as described in the official record of the 1911 resurvey.</p>
20.205	<p>From the center east 1/16 sec. cor. of sec. 1.</p> <p>N. 0° 44' W., on the N and S center line of the NE 1/4 of sec. 1.</p> <p>Point for the NE 1/16 sec. cor. of sec. 1, at intersection with the E and W center line of the NE 1/4.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;"> <math display="block">NE \ 1/16 \ S \ 1</math>                     1983                 </p>
40.07	<p>The E 1/16 sec. cor. of secs. 1 and 36, on the N. bdy. of the Tp., heretofore described.</p>
20.675	<p>From the N 1/16 sec. cor. of secs. 1 and 6, on the E. bdy. of the Tp., heretofore described.</p> <p>N. 89° 15' W., on the E and W center line of the NE 1/4 of sec. 1.</p>
41.35	<p>The NE 1/16 sec. cor. of sec. 1.</p> <p>The center north 1/16 sec. cor. of sec. 1.</p>
<p>Partial Subdivision Survey of Section 12, T. 19 S., R. 7 E., Salt Lake Meridian, Utah</p>	
<p>From the 1/4 sec. cor. of secs. 12 and 13.</p>	

Partial Subdivision Survey of Section 12,  
T. 19 S., R. 7 E., Salt Lake Meridian, Utah

CHAINS	
19.96	<p>N. 0° 49' W., on the N and S center line of sec. 12.</p> <p>Point for the center south 1/16 sec. cor. of secs. 12.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>
	<pre> C   S 1/16   S 12   C 1983                     </pre>
39.92	<p>Point for the center 1/4 sec. cor. of sec. 12, at intersection with the E and W center line.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>
	<pre> T 19 S R 7 E C 1/4 S 12 1983                     </pre>
80.27	<p>The 1/4 sec. cor. of secs. 1 and 12.</p>
	<p>From the 1/4 sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp., heretofore described.</p> <p>N. 88° 32' W., on the E and W center line of sec.12.</p>
40.66	<p>The center 1/4 sec. cor. of sec. 12</p>
81.65	<p>The 1/4 sec. cor. of secs. 11 and 12.</p>
	<p>From the S 1/16 sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 88° 21' W., on the E and W center line of the SE 1/4 of sec. 12.</p>
40.54	<p>The center south 1/16 sec. cor. of sec. 12.</p>
	<p>N. 88° 52' W., on the E and W center line of the SW 1/4 of sec. 12.</p>
40.95	<p>The S 1/16 sec. cor. of secs. 11 and 12.</p>
	<p>Partial Subdivision Survey of Section 13 T.19 S., R.7 E., Salt Lake Meridian,Utah.</p>
	<p>From the 1/4 sec. cor. of secs. 13 and 24, monumented with an iron post, 2 1/2 in. diam., firmly set, projecting 6 in. above ground, with brass cap, mkd. as described in the official record of the 1975 resurvey.</p>
	<p>N. 0° 20' W., on the N and S center line of sec. 13</p>

Partial Subdivision Survey of Section 13,  
T. 19 S., R. 7 E., Salt Lake Meridian, Utah

CHAINS	
40.41	<p>Point for the center 1/4 sec. cor. of sec. 13, at intersection with the E and W center line.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 19 S R 7 E C 1/4 S 13 1983</p>
81.63	<p>The 1/4 sec. cor. of secs. 12 and 13.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 in. diam., firmly set, projecting 6 in. above ground, with brass cap mkd. as described in the official record of the 1975 resurvey.</p> <p>N. 88° 41' W., on the E and W centerline of sec. 13.</p>
20.29	<p>Point for the center east 1/16 sec. cor. of sec. 13.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">E 1/16 C ——— S 13 C 1983</p>
40.58	<p>The center 1/4 sec. cor. of sec. 13.</p>
81.31	<p>The 1/4 sec. cor. of secs. 13 and 14.</p> <hr/> <p>From the center east 1/16 sec. cor. of sec. 13.</p> <p>N. 0° 28' W., on the N and S centerline of the NE 1/4 of sec. 13.</p>
41.09	<p>The E 1/16 sec. cor. of secs. 12 and 13.</p> <hr/> <p style="text-align: center;">Partial Subdivision Survey of Section 14, T. 19 S., R. 7 E., Salt Lake Meridian, Utah.</p> <hr/> <p>From the true point for the 1/4 sec. cor. of secs. 14 and 23.</p> <p>N. 0° 45' W., on the N and S center line of sec. 14.</p>
40.61	<p>Point for the center 1/4 sec. cor. of sec. 14 at intersection with the E and W centerline.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 19 S R 7 E C 1/4 S 14 1983</p>
61.015	<p>Point for the center north 1/16 sec. cor. of sec. 14.</p>

Partial Subdivision Survey of Section 14,  
T. 19 S., R. 7 E., Salt Lake Meridian, Utah

CHAINS	
81.42	<p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;"> <math display="block">\begin{array}{c} C \\ N1/16 \mid S14 \\ C \\ 1983 \end{array}</math> </p> <p>The 1/4 sec. cor. of secs. 11 and 14.</p>
19.99	<p>From the 1/4 sec. cor. of secs. 13 and 14.</p> <p>N.89° 49' W., on the E and W center line of sec. 14.</p> <p>Point for the center east 1/16 sec. cor. of sec. 14.</p>
39.98	<p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;"> <math display="block">\begin{array}{c} E \ 1/16 \\ C \ \overline{\quad S \ 14 \quad} \ C \\ 1983 \end{array}</math> </p> <p>The center 1/4 sec. cor. of sec. 14.</p>
59.925	<p>Point for the center west 1/16 sec. cor. of sec. 14.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;"> <math display="block">\begin{array}{c} W \ 1/16 \\ C \ \overline{\quad S \ 14 \quad} \ C \\ 1983 \end{array}</math> </p>
20.43	<p>The 1/4 sec. cor. of secs. 14 and 15.</p> <p>From the center east 1/16 sec. cor. of sec. 14.</p> <p>N.0° 43' W., on the N and S center line of the NE 1/4 of sec. 14.</p> <p>Point for the NE 1/16 sec. cor. of sec. 14, at intersection with the E and W center line of the NE 1/4.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;"> <math display="block">\begin{array}{c} NE \ 1/16 \\ S \ 14 \\ 1983 \end{array}</math> </p>
40.86	<p>The E 1/16 sec. cor. of secs. 11 and 14.</p>
20.00	<p>From the N 1/16 sec. cor. of secs. 13 and 14.</p> <p>N. 89° 53' W., on the E and W center line of the NE 1/4 of sec. 1.</p> <p>The NE 1/16 sec. cor. of sec. 14.</p>

Partial Subdivision Survey of Section 22,  
T. 19 S., R. 7 E., Salt Lake Meridian, Utah

CHAINS	
40.00	<p>The center north 1/16 sec. cor. of sec. 14.</p> <hr/> <p>From the W 1/16 sec. cor. of secs. 14 and 23.</p> <p>N. 0° 44' W., on the N and S center line of the SW 1/4 of sec. 14.</p>
40.59	<p>The center west 1/16 sec. cor. of sec. 14.</p> <hr/> <p>Partial Subdivision Survey of Section 22, T. 19 S., R. 7 E., Salt Lake Meridian, Utah</p> <hr/> <p>From the 1/4 sec. cor. of secs. 22 and 27.</p> <p>N. 0° 42' W., on the N and S center line of sec. 22.</p>
20.135	<p>Point for the center south 1/16 sec. cor. of sec. 22.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>C</p> <p> </p> <p>S 1/16   S 22</p> <p> </p> <p>C</p> <p>1983</p> </div>
40.27	<p>Point for the center 1/4 sec. cor. of sec. 22, at intersection with the E and W center line.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 19 S R 7 E</p> <p>C 1/14 S 22</p> <p>1983</p> </div>
77.03	<p>The 1/4 sec. cor. of secs. 15 and 22.</p> <hr/> <p>From true point for the 1/4 sec. cor. of secs. 22 and 23.</p> <p>S. 89° 40' W., on the E and W center line of sec. 22.</p>
40.76	<p>The center 1/4 sec. cor. of sec. 22.</p>
81.22	<p>The 1/4 sec. cor. of sec. 22.</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 22 and 23.</p> <p>S. 89° 47' W., on the E and W center line of the SE 1/4 of sec. 22.</p>
40.86	<p>The center south 1/16 sec. cor. of sec. 22.</p> <hr/> <p>Partial Subdivision Survey of Section 23, T. 19 S., R. 7 E., Salt Lake Meridian, Utah</p> <hr/>

Partial Subdivision Survey of Section 23,  
T. 19 S., R. 7 E., Salt Lake Meridian, Utah

CHAINS	
40.60	<p>From the 1/4 sec. cor. of secs. 23 and 26.</p> <p>N. 0° 57' W., on the N and S center line of sec. 23.</p> <p>Point for the center 1/4 sec. cor. of sec. 23, at intersection with the E and W center line.</p> <p>Set a PVC post, 30 ins. long, 2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 19 S R 7 E C 1/4 S 23 1983</p>
60.91	<p>Raise a mound of stone, 3 1/2 ft. base, 1 1/2 high, W of cor.</p> <p>Point for the center north 1/16 sec. cor. of sec. 23.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">C   N 1/16   S 23   C 1983</p>
81.22	<p>True point for the 1/4 sec. cor. of secs. 14 and 23.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 23 and 24.</p> <p>N. 89° 31' W., on the E and W center line of sec. 23.</p>
39.94	<p>The center 1/4 sec. cor. of sec. 23.</p>
59.93	<p>Point for the center west 1/16 sec. cor. of sec. 23.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">W 1/16 C ——— C S 23 1983</p>
79.92	<p>True point for the 1/4 sec. cor. of secs. 22 and 23.</p> <hr/> <p>From the center west 1/16 sec. cor. of sec. 23.</p>
20.275	<p>N. 0° 57' W., on the N and S center line of the NW 1/4 of sec. 23.</p> <p>Point for the NW 1/16 sec. cor. of sec. 23, at intersection with the E-W center line of the NW 1/4.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">NW 1/16 S 23 1983</p>
40.55	<p>The W 1/16 sec. cor. of secs. 14 and 23.</p>

Partial Subdivision Survey of Section 23,  
T. 19 S., R. 7 E., Salt Lake Meridian, Utah

CHAINS	
19.985	<p>From the center north 1/16 sec. cor. of sec. 23.</p> <p>N. 89° 39' W., on the E and W center line of sec. 23.</p> <p>The NW 1/16 sec. cor. of sec. 23.</p>
39.97	<p>The N 1/16 sec. cor. of sec. 23 only.</p> <hr/> <p style="text-align: center;">Partial Subdivision Survey of Section 24, T. 19 S., R. 7 E., Salt Lake Meridian, Utah</p> <hr/> <p>From the 1/4 sec. cor. of secs. 24 and 25.</p> <p>N. 0° 47' W., on the N and S center line of sec. 24.</p>
20.38	<p>Point for the center south 1/16 sec. cor. of sec. 24.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>C</p> <p> </p> <p>S 1/16   S 24</p> <p> </p> <p>C</p> <p>1983</p> </div>
40.76	<p>Point for the center 1/4 sec. cor. of sec. 24, at intersection with the E and W center line.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.</p> <div style="text-align: center;"> <p>T 19 S R 7 E</p> <p>C 1/4 S 24</p> <p>1983</p> </div>
81.54	<p>The 1/4 sec. cor. of secs. 13 and 24.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp., heretofore described.</p> <p>N. 88° 59' W., on the E and W center line of sec. 24.</p>
20.225	<p>True point for the center east 1/16 sec. cor. of secs. 24, falls in bottom of Rock Creek, 20 lks. wide, 2 ins. deep, flowing E. Point is unsuitable for monumentation.</p>
21.555	<p>Point selected for the witness cor. to the center east 1/16 sec. cor. of sec. 24.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>W C</p> <p>E 1/16</p> <p>C —————&gt; C</p> <p>S 24</p> <p>1983</p> </div>
40.45	<p>The center 1/4 sec. cor. of sec. 24.</p>

Partial Subdivision Survey of Section 24,  
T. 19 S., R. 7 E., Salt Lake Meridian, Utah

CHAINS	
60.635	<p>Point for the center west 1/16 sec. cor. of sec. 24.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;"> <math display="block">\begin{array}{c} \text{W } 1/16 \\ \text{C} \quad \frac{\quad}{\text{S } 24} \quad \text{C} \\ 1983 \end{array}</math> </p>
80.82	<p>The 1/4 sec. cor. of secs. 23 and 24.</p> <hr/> <p>From the E 1/16 sec. cor. of secs. 24 and 25.</p> <p>N. 0° 37' W., on the N and S center line of the SE 1/4 of sec. 24.</p>
20.38	<p>Point for the SE 1/16 sec. cor. of sec. 24, at intersection with the E and W center line.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;"> <math display="block">\begin{array}{c} \text{SE } 1/16 \\ \text{S } 24 \\ 1983 \end{array}</math> </p>
40.76	<p>True point for the center east 1/16 sec. cor. of sec. 24.</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp., heretofore described.</p> <p>N. 88° 58' W., on the E and W center line of the SE 1/4 of sec. 24.</p>
20.17	<p>The SE 1/16 sec. cor. of sec. 24.</p>
40.34	<p>The center south 1/16 sec. cor. of sec. 24.</p> <hr/> <p>From the W 1/16 sec. cor. of secs. 24 and 25.</p> <p>N. 0° 53' W., on the N and S center line of the SW 1/4 of sec. 24.</p>
20.37	<p>Point for the SW 1/16 sec. cor. of sec. 24, at intersection with the E and W center line of the SW 1/4.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;"> <math display="block">\begin{array}{c} \text{SW } 1/16 \\ \text{S } 24 \\ 1983 \end{array}</math> </p>
40.74	<p>The center west 1/16 sec. cor. of sec. 24.</p> <hr/> <p>From the center south 1/16 sec. cor. of sec. 24.</p> <p>N. 88° 57' W., on the E and W center line of the SW 1/4 of sec. 24.</p>

Partial Subdivision Survey of Section 24,  
T. 19 S., R. 7 E., Salt Lake Meridian, Utah

## CHAINS

- 20.15 The SW 1/16 sec. cor. of sec. 24.
- 40.30 The S 1/16 sec. cor. of secs. 23 and 24.
- 
- Partial Subdivision Survey of Section 25,  
T. 19 S., R. 7 E., Salt Lake Meridian, Utah
- 
- From the 1/4 sec. cor. of secs. 25 and 36.
- N.0° 58' W., on the N and S center line of sec. 25.
- 40.59 Point for the center 1/4 sec. cor. of sec. 25, at intersection with the E and W center line.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.
- T 19 S R 7 E  
C 1/4 S 25  
1983
- 61.05 Point for the center north 1/16 sec. cor. of sec. 25.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.
- C  
N 1/16 | S 25  
C  
1983
- Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W of cor.
- 81.51 The 1/4 sec. cor. of secs. 24 and 25.
- 
- From the 1/4 sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp., heretofore described.
- N. 89° 12' W., on the E and W center line of sec. 25.
- 39.86 The center 1/4 sec. cor. of sec. 25.
- 59.98 Point for the center west 1/16 sec. cor. of sec. 25.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.
- W 1/16  
C      C  
S 25  
1983
- Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, N of cor.
- 80.10 The 1/4 sec. cor. of secs. 25 and 26.
-

Partial Subdivision Survey of Section 25,  
T. 19 S., R. 7 E., Salt Lake Meridian, Utah

CHAINS	
20.515	<p>From center west 1/16 sec. cor. of sec. 25.</p> <p>N. 0° 57' W., on the N and S center line of of the NW 1/4 of sec. 25.</p> <p>Point for the NW 1/16 sec. cor. of sec. 25, at intersection with the E and W center line of the NW 1/4.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">NW 1/16 S 25 1983</p>
41.03	<p>The W 1/16 sec. cor. of secs. 24 and 25.</p>
20.12	<p>From the center north 1/16 sec. cor. of sec. 25.</p> <p>N. 89° 04' W., on the E and W center line of the NW 1/4 of sec. 25.</p> <p>The NW 1/16 sec. cor. of sec. 25.</p>
40.24	<p>The N 1/16 sec. cor. of secs. 25 and 26.</p>
<p>Partial Subdivision Survey of Section 26, T. 19 S., R. 7 E., Salt Lake Meridian, Utah</p>	
20.645	<p>From the 1/4 sec. cor. of secs. 26 and 35.</p> <p>N. 0° 41' W., on the N and S center line of sec. 26.</p> <p>Point for the center south 1/16 sec. cor. of sec. 26.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">C S 1/16   S 26 C 1983</p>
41.29	<p>Point for the center 1/4 sec. cor. of sec. 26, at intersection with the E and W center line.</p> <p>Set an PVC post, 30 ins. long, 2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 19 S R 7 E C 1/4 S 26 1983</p>
61.98	<p>Point for the center north 1/16 sec. cor. of sec. 26.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">C N 1/16   S 26 C 1983</p>

Partial Subdivision Survey of Section 26,  
T. 19 S., R. 7 E., Salt Lake Meridian, Utah

CHAINS	
82.67	The 1/4 sec. cor. of secs. 23 and 26.
	From the 1/4 sec. cor. of secs. 25 and 26.
	N. 89° 42' W., on the E and W center line of sec. 26.
40.11	The center 1/4 sec. cor. of sec. 26.
80.67	The 1/4 sec. cor. of secs. 26 and 27.
	From the N 1/16 sec. cor of secs. 25 and 26.
	N. 89° 32' W., on the E and W center line of the NE 1/4 of sec. 26.
40.025	The center north 1/16 sec. cor. of sec. 26.
	From the center south 1/16 sec. cor. of sec. 26.
	N. 89° 52' W., on the E and W center line of the SW 1/4 of sec. 26.
40.88	The S 1/16 sec. cor. of secs. 26 and 27.
	Partial Subdivision Survey of Section 27, T. 19 S., R. 7 E., Salt Lake Meridian, Utah
	From the 1/4 sec. cor. of secs. 27 and 34.
	N. 0° 06' E., on the N and S center line of sec. 27.
20.18	Point selected for the witness cor. to the center south 1/16 sec. cor. of sec. 27.
	Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.
	<pre>                     W C                     C                     ↑                 S 1/16   S 27                     ↓                     C                     1983                     </pre>
20.76	True point for the center south 1/16 sec. cor. of sec. 27, falls on face of clay ridge. Unsuitable for monumentation.
41.52	Point for the center 1/4 sec. cor. of sec. 27, at intersection with the E and W center line.
	Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.
	<pre>                     T 19 S R 7 E                     C 1/4 S 27                     1983                     </pre>

Partial Subdivision Survey of Section 27,  
T. 19 S., R. 7 E., Salt Lake Meridian, Utah

CHAINS	
83.04	The 1/4 sec. cor. of sec. 27 only.
	From the 1/4 sec. cor. of secs. 26 and 27.
	S. 89° 58' W., on the E and W center line of sec. 27.
20.435	Point for the center east 1/16 sec. cor. of sec. 27.
	Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	<div style="text-align: center;">           E 1/16            C ————— C            S 27            1983         </div>
40.87	The center 1/4 sec. cor. of sec. 27.
81.76	The 1/4 sec. cor. of secs. 22 and 27.
	From the E 1/16 sec. cor. of secs. 27 and 34.
	N. 0° 08' E., on the N and S center line of the SE 1/4 of sec. 27.
20.77	Point for the SE 1/16 sec. cor. of sec. 27, at intersection with the E and W center line of the SE 1/4.
	Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	<div style="text-align: center;">           SE 1/16            S 27            1983         </div>
41.54	The center east 1/16 sec. cor. of sec. 27.
	From the south 1/16 sec. cor. of secs. 26 and 27.
	S. 89° 59' W., on the E and W center line of the SE 1/4 of sec. 27.
20.42	The SE 1/16 sec. cor. of sec. 27.
40.84	True point for the center south 1/16 sec. cor. of sec. 27.
	<div style="text-align: center;">           Partial Subdivision Survey of Section 34,            T. 19 S., R. 7 E., Salt Lake Meridian, Utah         </div>
	From the 1/4 sec. cor. of secs. 3 and 34, on the S. bdy. of the Tp., heretofore described.
	N. 0° 26' W., on the N and S center line of sec. 34.
20.105	Point for the center south 1/16 sec. cor. of sec. 34.
	Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Partial Subdivision Survey of Section 34,  
T. 19 S., R. 7 E., Salt Lake Meridian, Utah

CHAINS		
	$\begin{array}{c} C \\   \\ S \ 1/16 \quad   \quad S \ 34 \\   \\ C \\ 1983 \end{array}$	
40.21	<p>Point for the center 1/4 sec. cor. of sec. 34, at intersection with the E and W center line.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> $\begin{array}{c} T \ 19 \ S \ R \ 7 \ E \\ C \ 1/4 \ S \ 34 \\ 1983 \end{array}$	
80.39	<p>The 1/4 sec. cor. of secs. 27 and 34.</p>	
	<hr/> <p>From the 1/4 sec. cor. of secs. 34 and 35.</p> <p>N. 89° 52' W., on the E and W center line of sec. 34.</p>	
20.32	<p>Point for the center east 1/16 sec. cor. of sec. 34.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> $\begin{array}{c} E \ 1/16 \\ C \ \frac{\quad}{S \ 34} \ C \\ 1983 \end{array}$	
40.64	<p>The center 1/4 sec. cor. of sec. 34.</p>	
61.20	<p>Point for the center west 1/16 sec. cor. of sec. 34.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.</p> $\begin{array}{c} W \ 1/16 \\ C \ \frac{\quad}{S \ 34} \ C \\ 1983 \end{array}$	
81.76	<p>The 1/4 sec. cor. of secs. 33 and 34.</p>	
20.12	<hr/> <p>From the E 1/16 sec. cor. of secs. 33 and 34, on the S. bdy. of the Tp., heretofore described.</p> <p>N. 0° 19' W., on the N and S center line of the SE 1/4 of sec. 34.</p> <p>Point for the SE 1/16 sec. cor. of sec. 34, at intersection with the E and W center line of the SE 1/4.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>	

Partial Subdivision Survey of Section 34,  
T. 19 S., R. 7 E., Salt Lake Meridian, Utah

CHAINS	
	SE 1/16 S 34 1983
	Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W of cor.
40.24	The center east 1/16 sec. cor. of sec. 34.
	From the S 1/16 sec. cor. of secs. 34 and 35.
	N. 89° 50' W., on the E and W center line of the SE 1/4 of sec. 34.
20.28	The SE 1/16 sec. cor. of sec. 34.
40.56	The center south 1/16 sec. cor. of sec. 34.
	From the W 1/16 sec. cor. of secs. 3 and 34, on the S. bdy. of the Tp., heretofore described.
	N. 0° 15' W., on the N and S center line of the SW 1/4 of sec. 34.
20.095	Point for the SW 1/16 sec. cor. of sec. 34, at intersection with the E and W center line of the SW 1/4.
	Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.
	SW 1/16 S 34 1983
40.19	The center west 1/16 sec. cor. of sec. 34.
	From the center south 1/16 sec. cor. of sec. 34.
	N. 89° 50' W., on the E and W center line of the SW 1/4 of sec. 34.
20.625	The SW 1/16 sec. cor. of sec. 34.
41.25	True point for the S 1/16 sec. cor. of secs. 33 and 34.
	Partial Subdivision Survey of Section 35, T. 19 S., R. 7 E., Salt Lake Meridian, Utah
	From the 1/4 sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, protruding 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1962 resurvey.
	N. 0° 20' E., on the N and S center line of sec. 35.
40.34	Point for the center 1/4 sec. cor. of sec. 35, at intersection with the E and W center line.

Partial Subdivision Survey of Section 35,  
T. 19 S., R. 7 E., Salt Lake Meridian, Utah

CHAINS	
	<p>T 19 S R 7 E C 1/4 S 35 1983</p>
60.55	True point for the center north 1/16 sec. cor. of sec. 35, falls near edge of State Highway No. 10, and is unsafe to monument.
60.81	Point selected for the witness cor. to the center north 1/16 sec. cor. of sec. 35.  Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	<p>W C C   N 1/16   S 35 ↓ C 1982</p>
80.76	The 1/4 sec. cor. of secs. 26 and 35.
	<hr/> <p>From the 1/4 sec. cor. of secs. 35 and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set, protruding 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1975 resurvey.  N. 89° 54' W., on the E and W center line of sec. 35.</p>
40.35	The center 1/4 sec. cor. of sec. 35.
60.77	Point for the center west 1/16 sec. cor. of sec. 35.  Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	<p>W 1/16 C ——— S 35 ——— C 1982</p>
70.98	Point for the C-W-W 1/64 sec. cor. of sec. 35.  Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	<p>C W W 1/64 S 35 1982</p>
81.19	The 1/4 sec. cor. of secs. 34 and 35.
	<hr/> <p>From the center west 1/16 sec. cor. of sec. 35.  N. 0° 05' E., on the N and S center line of the NW 1/4 of sec. 35.</p>
10.075	Point for the C-S-NW 1/64 sec. cor. of sec. 35.

Partial Subdivision Survey of Section 35,  
T. 19 S., R. 7 E., Salt Lake Meridian, Utah

CHAINS	
	<p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">C-S-NW 1/64 S 35 1982</p>
20.15	<p>Point for the NW 1/16 sec. cor. of sec. 35, at intersection with the E and W center line of the NW 1/4.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">NW 1/16 S 35 1982</p>
40.30	<p>The W 1/16 sec. cor. of secs. 26 and 35.</p>
20.51	<p>From the true point for the center north 1/16 sec. cor. of sec. 35.</p> <p>N. 89° 58' W., on the E and W center line of the NW 1/4 of sec. 35.</p> <p>The NW 1/16 sec. cor. of sec. 35.</p>
30.765	<p>Point for the C-W-NW 1/64 sec. cor. of sec. 35.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">C-W-NW 1/64 S 35 1982</p>
41.02	<p>True point for the N 1/16 sec. cor. of secs. 34 and 35.</p>
10.075	<p>From the C-W-W 1/64 sec. cor. of sec. 35.</p> <p>N. 0° 03' W., on the N and S center line of the SW 1/4 of the NW 1/4 of sec. 35.</p> <p>Point for the SW-NW 1/64 sec. cor. of sec. 35, at intersection with the E and W center line of the SW 1/4 of the NW 1/4.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">SW-NW 1/64 S 35 1982</p>
20.15	<p>The C-W-NW 1/64 sec. cor. of sec. 35.</p>
	<p>From the C-S-NW 1/64 sec. cor. of sec. 35.</p> <p>N. 89° 56' W., on the E and W center line of the SW 1/4 of the NW 1/4 of sec. 35.</p>

Partial Subdivision Survey of Section 35,  
T. 19 S., R. 7 E., Salt Lake Meridian, Utah

CHAINS	
10.23	The SW-NW 1/64 sec. cor. of sec. 35.
20.46	The S-N 1/64 sec. cor. of secs. 34 and 35.
<p>General Description</p> <p>The area resurveyed within Township 19 South, Range 7 East, is situated in and around the townsite of Clawson, Utah. The elevation varies from 5900 ft. above sea level to 6200 ft. above sea level. General drainage is to the north and south into Rock Creek which flows east through section 24. Utah State Highway No. 10 passes through the southeast corner of the township.</p> <p>Main usage of the area surveyed is farming and livestock grazing.</p> <p>The mean magnetic declination is 14° East.</p>	



CERTIFICATE OF SURVEY

(I) ~~(Wa)~~, Jerry L. Thomas, Supervisory Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 2nd day

of September, 1982, (I) ~~(Wa)~~ have dependently resurveyed a portion of the east boundary (Second Guide Meridian East), the south boundary of section 34, the E 1/2 mile of the north boundary of section 1, and a portion of the subdivisional lines, and surveyed a portion of the subdivision of sections 1, 12, 13, 14, 22, 23, 24, 25, 26, 27, 34, and 35 of T. 19 S., R. 7 E.,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), ~~(X)~~ and under (my) ~~(X)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

February 27, 1986 (Date) [Signature: Jerry L. Thomas] (Cadastral Surveyor) Supervisory (Date) (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the east boundary (Second Guide Meridian East), the south boundary of section 34, the E 1/2 mile of the north boundary of section 1, and the survey of a portion of the subdivision of sections 1, 12, 13, 14, 22, 23, 24, 25, 26, 27, 34, and 35 of T. 19 S., R. 7 E., Salt Lake Meridian, Utah

executed by Jerry L. Thomas, Supervisory Cadastral Surveyor having been critically examined and found correct, are hereby approved.

March 10, 1986 (Date) [Signature: Glen B. Hatch] ~~(X)~~ Chief Cadastral Surveyor for Utah

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

(Date) (Chief, Cadastral Survey Examination and Approval Staff)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
ORIGINAL

R608

FIELD NOTES  
OF THE

316

DEPENDENT RESURVEY

OF THE

SOUTH 1/2 MILE ON THE WEST BOUNDARY OF SECTION 6,  
THE WEST 1/2 MILE ON THE NORTH BOUNDARY OF SECTION 5,

A PORTION OF THE SUBDIVISIONAL LINES

AND THE

SUBDIVISIONAL SURVEY OF CERTAIN SECTIONS

OF

TOWNSHIP 17 SOUTH, RANGE 8 EAST

Of the Salt Lake Meridian,

In the State of Utah

EXECUTED BY

Jerry L. Thomas

Supervisory Cadastral Surveyor

Under special instructions dated September 17, 1982, approved September 20, 1982.

\_\_\_\_\_, which provided for the surveys included under ~~USA~~ ~~Survey~~ ~~Group~~

Number 621, and assignment instructions dated September 20, 1982

Survey commenced September 23, 1982

Survey completed April 26, 1983

# INDEX DIAGRAM

Township 17 South, Range 8 East

2	6 37	5 30	4 24	3 19	2 10	1
36	33	29	24	18	9	
7 34	8 29	9 23	10 17	11 8	12	19
31	32	27	22	17	7	
18	17 28	16 21	15 16	14 6	13	18
	26	25	20	15		
19	20	21	22	13 28 5	24	
				13		
30	29	28	27	12 26 4	25	
				11		
31	32	33	34 11	35	36	

- Subdivision of Section 1 - Page 38
- Subdivision of Section 5 - Page 39
- Subdivision of Section 6 - Page 41
- Subdivision of Section 8 - Page 44
- Subdivision of Section 9 - Page 49
- Subdivision of Section 10 - Page 52
- Subdivision of Section 11 - Page 53
- Subdivision of Section 12 - Page 54
- Subdivision of Section 14 - Page 56
- Subdivision of Section 15 - Page 58
- Subdivision of Section 23 - Page 59
- Subdivision of Section 26 - Page 62

## Township 17 South, Range 8 East, Salt Lake Meridian, Utah

## CHAINS

The following field notes describe the dependent resurvey of the west 1/2 mile of the north boundary of section 5, the south 1/2 mile of the west boundary of section 6, a portion of the subdivisional lines, and the subdivisional survey of certain sections in T. 17 S., R. 8 E., Salt Lake Meridian, Utah.

History of SurveysSurveyed byRetr. or Resurveyed bySOUTH BOUNDARY

All A.D. Ferron 1873

Portion  
Portion

J.C. Dick 1900  
Glen B. Hatch 1970

EAST BOUNDARY

All A.D. Ferron 1873

Portion

C.P. Sylvester 1969-70

WEST BOUNDARY

Portion A.D. Ferron 1882

Portion J.C. Dick 1900

All

J.C. Dick 1900  
J.L. Thomas 1968-69

NORTH BOUNDARY

Portion A.D. Ferron 1881

Portion A.D. Ferron 1882

Portions J.C. Dick 1900

All

J.C. Dick 1900  
G.E. Reynolds 1976

SUBDIVISION

Portion A.D. Ferron 1881

Portion A.D. Ferron 1882

Portion J.C. Dick 1900

J.C. Dick 1900

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group 621, Utah, dated September 17, 1982.

The directions of lines were determined by means of angular deflections from azimuths obtained by direct solar and Polaris observations.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions, lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the southeast corner of section 26, as determined by calculation from U.S.G.S. tri-station, "SEC COR WC 31/16S/9E", is as follows:

Latitude 39° 18' 28.91" N. Longitude 110° 58' 56.34" W.

The mean magnetic declination as projected from U.S. Geological Survey "Magnetic Declination Map of 1980" is 14 1/4° E.

Dependent Resurvey of the South 1/2 Mile on the  
West Boundary of Section 6,  
T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS

Dependent Resurvey of the South 1/2 Mile on the  
West Boundary of Section 6,  
T. 17 S., R. 8 E., Salt Lake Meridian, Utah

(Restoring the Survey Executed by A.D. Ferron in 1882,  
The Retracement Executed by J.C. Dick in 1900,  
and the Resurvey Executed by J.L. Thomas in 1968-69)

Beginning at the cor. of secs. 6 and 7, T. 17 S., R. 8 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1968 resurvey of the E. bdy. of sec. 1, T. 17 S., R. 7 E.

Add the marks 1982 on the brass cap.

Cor. is located on gradual N slope, alongside cor. post of fences, which bear N, S and W irregularly.

N. 0° 07' E., along W. bdy. of sec. 6.

Desc. over gradual N slope.

20.61 Point for the S 1/16 sec. cor. of sec. 6 only, T. 17 S., R. 8 E.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.

```

      T 17 S
     R 7 E R 8 E
       |
       S 6
       |
     1982
  
```

41.22 The 1/4 sec. cor. of sec. 6, T. 17 S., R. 8 E., monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1968 resurvey of the E. bdy. of sec. 1, T. 17 S., R. 7 E.

Add the marks 1982 on the brass cap.

Dependent Resurvey of the West 1/2 Mile on the  
North Boundary of Section 5,  
T. 17 S., R. 8 E., Salt Lake Meridian, Utah

(Restoring the Survey Executed by J.C. Dick in 1900  
and the Resurvey Executed by G.E. Reynolds in 1976)

From the 1/4 sec. cor. of sec. 5 only, T. 17 S., R. 8 E., monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. above a mound of stone, with brass cap, mkd. as described in the official record of the 1976 resurvey of the N. bdy. of T. 17 S., R. 8 E., from which the bearing tree mkd. in 1976

Dependent Resurvey of the West 1/2 Mile on the  
North Boundary of Section 5,  
T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS	
	<p>A pinon, 11 ins. diam., bears S. 45° E., 19 lks. dist., mkd. 1/4 S5 BT.</p>
	<p>Add the marks 1982 on the brass cap.</p>
	<p>N. 89° 37' W., along the N. bdy. of sec. 5.</p>
	<p>Desc. over SW slope, through sagebrush.</p>
1.50	<p>Bottom of Fish Creek Canyon, drains S. 50° E.; asc. over NE slope.</p>
5.00	<p>Improved gravel road, bears N. 50° W. and S. 50° E.</p>
21.635	<p>Point for the W 1/16 sec. cor. of sec. 5 only, T. 17 S., R. 8 E.</p>
	<p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.</p>
	<p style="text-align: center;">T 16 S</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">W 1/16 S 5 T 17 S R 8 E 1982</p>
	<p>Raise a mound of stone, 3 1/2 ft. base, 2 1/2 ft. high, S of cor.</p>
43.27	<p>The cor. of secs. 5 and 6, T. 17 S., R. 8 E., monumented with an iron post, 2 1/2 ins. diam., set inside a steel pipe, 4 ins. diam., projecting 4 ft. above ground, with brass cap, mkd. as described in the official record of the 1976 resurvey of the N. bdy. of T. 17 S., R. 8 E.</p> <p>Add the marks 1982 on the brass cap.</p>
	<p style="text-align: center;">Dependent Resurvey of a Portion of the Subdivisional Lines, T. 17 S., R. 8 E., Salt Lake Meridian, Utah</p>
	<p style="text-align: center;">(Restoring the Survey Executed by A.D. Ferron in 1881)</p>
	<p>From the cor. of secs. 25, 26, 35, and 36, determined longitudinally by a fence line projecting N and the center of a gravel road winding around a wash and bearing S, and latitudinally by fence lines projecting W and E. This point falls in grassy swamp land in the bottom of a wash. There is no remaining evidence of the original monument.</p>
	<p>At the corner point</p>
	<p>Deposit a steel fence post, 5 ft. long, projecting 3 ft. above ground, from which</p>
	<p>An aluminum post, 30 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 46° E., 88.2 lks. dist., with aluminum cap, mkd. T17S R8E S36 RM 1982 58.2 FT and an arrow pointing to the cor.</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS	
	<p>An aluminum post, 30 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 54 1/4° E., 113.9 lks. dist., with aluminum cap, mkd. T17S R8E S35 RM 1982 75.2 FT and an arrow pointing to the cor.</p> <p>N. 0° 58' W., bet. secs. 25 and 26.</p> <p>Over cultivated land.</p>
40.51	<p>Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 30 ins. deep, flush with the surface of ground, aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 17 S R 8 E</p> <p>1/4</p> <p>S 26   S 25</p> <p>1983</p> </div>
60.765	<p>Cor. is located in gate entrance to field and in line with fences projecting N, S and E.</p> <p>Point for the N 1/16 sec. cor. of secs. 25 and 26, falls in the center line of a gravel road, 25 lks. wide, bearing E and W.</p> <p>Set a steel rod, 18 ins. long, 18 ins. in the ground, flush with surface of gravel road, from which</p> <p>An aluminum post, 30 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 4 1/4° E., 27.3 lks. dist., with aluminum cap, mkd. T17S R8E N1/16 S25 RM 1983 18 FT and an arrow pointing to the cor.</p> <p>An aluminum post, 30 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 72 1/4° W., 78.8 lks. dist., with aluminum cap, mkd. T17S R8E N1/16 S26 RM 1983 52 FT and an arrow pointing to the cor.</p>
81.02	<p>Point for the cor. of secs. 23, 24, 25, and 26, determined longitudinally by proportionate measurement and latitudinally by fence line projecting W.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 17 S R 8 E</p> <p>S 23   S 24</p> <p>S 26   S 25</p> <p>1983</p> </div>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS

from this point

The point for the cor. of secs. 19, 24, 25, and 30,  
T. 17 S., Rs. 8 and 9 E., determined by center of  
intersection of State Highway No. 10, bearing N  
and S, and a Huntington City street, bearing E  
and W, bears N.  $89^{\circ} 18'$  E., 80.65 chs. dist.

Cor. point is not monumented.

N.  $0^{\circ} 43'$  W., bet. secs. 23 and 24.

Over cultivated land.

20.19

Point for the S 1/16 sec. cor. of secs. 23 and 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26  
ins. in the ground, with aluminum cap mkd.

```

T 17 S R 8 E
  S 1/16
    |
  S 23 | S 24
    |
    1983
  
```

Cor. is located under pole fence, with fences projecting  
N, S and E.

40.38

Point for the 1/4 sec. cor. of secs. 23 and 24,  
determined by cor. of fences, extending E, W and S. This  
position has long been recognized as the cor. by adjacent  
landowners, and is accepted as the best available  
evidence of the position of the original corner.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26  
ins. in the ground, with aluminum cap mkd.

```

T 17 S R 8 E
  1/4
    |
  S 23 | S 24
    |
    1983
  
```

N.  $0^{\circ} 26'$  W., beginning new measurement.

Over cultivated land.

20.14

Point for the N 1/16 sec. cor. of secs. 23 and 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26  
ins. in the ground, with aluminum cap mkd.

```

T 17 S R 8 E
  N 1/16
    |
  S 23 | S 24
    |
    1983
  
```

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 17 S., R. 8 E., Salt Lake Meridian, Utah

## CHAINS

40.28

Point for the cor. of secs. 13, 14, 23, and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.

T 17 S R 8 E  
S 14 | S 13  
S 23 | S 24  
1983

From this point, the cor. of secs. 13, 18, 19, and 24, T. 17 S., Rs. 8 and 9 E., bears N. 89° 27' E., 80.51 chs. dist., monumented with an aluminum post, 2 1/2 ins. diam., projecting 4 ins. above ground, with aluminum cap, properly mkd. This cor. was set by the Emery County Surveyor in 1981.

The control line was fully retraced, and no evidence of the intervening cor. was found.

N. 0° 30' W., bet. secs. 13 and 14.

Over cultivated land.

20.14

Point for the S 1/16 sec. cor. of secs. 13 and 14.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.

T 17 S R 8 E  
S 1/16  
S 14 | S 13  
1983

From this point, fence line bears N and S.

30.05

Utah State Highway No. 31, bears N. 31° 30' W. and S. 31° 30' E.

40.28

Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.

T 17 S R 8 E  
1/4  
S 14 | S 13  
1983

Cor. is located on N slope of clay bank, near creek bottom.

44.00

Huntington Creek, drains SE.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS						
79.35	Gravel road, bears E and W.					
79.85	Base of dam for irrigation pond; asc. over S slope of dam.					
80.56	<p>Point for the cor. of secs. 11, 12, 13, and 14, determined longitudinally by an old fence projecting N and latitudinally by an old fence projecting W.</p> <p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T 17 S R 8 E</td></tr> <tr><td>S 11   S 12</td></tr> <tr><td>S 14   S 13</td></tr> <tr><td>1982</td></tr> </table> </div> <p>Cor. is located on E end and near top of earthen dam.</p>	T 17 S R 8 E	S 11   S 12	S 14   S 13	1982	
T 17 S R 8 E						
S 11   S 12						
S 14   S 13						
1982						
40.29	<p>From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1969-70 resurvey of the W. bdy., T. 17 S., R. 9 E.</p> <p>S. 89° 11' W., bet. secs. 12 and 13.</p> <p>Over cultivated land.</p> <p>Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T 17 S R 8 E</td></tr> <tr><td>S 12</td></tr> <tr><td>1/4     S 13</td></tr> <tr><td>1982</td></tr> </table> </div>	T 17 S R 8 E	S 12	1/4     S 13	1982	
T 17 S R 8 E						
S 12						
1/4     S 13						
1982						
60.435	<p>Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, N of cor.</p> <p>Over rolling bench land.</p> <p>True point for the W 1/16 sec. cor. of secs. 12 and 13, falls in irrigation canal, 20 lks. wide, flows SW irregularly, and cannot be monumented.</p>					
60.74	<p>Point selected for the witness cor. to the W 1/16 sec. cor. of secs. 12 and 13.</p> <p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>W C</td></tr> <tr><td>T 17 S R 8 E</td></tr> <tr><td>S 12</td></tr> <tr><td>W 1/16     S 13 →</td></tr> <tr><td>1982</td></tr> </table> </div>	W C	T 17 S R 8 E	S 12	W 1/16     S 13 →	1982
W C						
T 17 S R 8 E						
S 12						
W 1/16     S 13 →						
1982						
80.58	The cor. of secs. 11, 12, 13, and 14.					

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS	
	<p>N. <math>0^{\circ} 08'</math> W., bet. secs. 11 and 12. Over rolling bench land.</p>
20.45	<p>Point for the S <math>1/16</math> sec. cor. of secs. 11 and 12. Set an aluminum post, 30 ins. long, 2 <math>1/2</math> ins. diam., 26 ins. in the ground, with aluminum cap mkd.</p>
	<p style="text-align: center;">T 17 S R 8 E S <math>1/16</math>   S 11   S 12   1982</p>
40.90	<p>The <math>1/4</math> sec cor. of secs. 11 and 12, monumented with a sandstone, 12 x 10 x 6 ins., firmly set, projecting 6 ins. above ground, and mkd. <math>1/4</math> on W face. At the corner point Set an iron post, 30 ins. long, 2 <math>1/2</math> ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 17 S R 8 E 1/4   S 11   S 12   1982</p> <p>Deposit the mkd. stone alongside the iron post. Cor. is located 2 lks. S of fence line, bears E and W.</p>
	<p>N. <math>1^{\circ} 20'</math> W., beginning new measurement. Asc. over S slope.</p>
20.15	<p>Point for the N <math>1/16</math> sec. cor. of secs. 11 and 12, falls near edge of dirt road. Bury a steel spike, 8 ins. long, 6 ins. below surface of road, from which An iron post, 30 ins. long, 2 <math>1/2</math> ins. diam., set 26 ins. in the ground, for a reference monument, bears N. <math>86^{\circ}</math> W., 50.6 lks. dist., with aluminum cap mkd. T17S R8E N1/16 S11 RM 1982 33.4 FT and an arrow pointing to the corner.</p>
	<p>A boulder, 6 x 4 ft., projecting 3 ft. above ground, mkd. X B0 at center, bears N. <math>34^{\circ}</math> E., 8.3 lks. dist.</p>
35.00	<p>Top of ridge, bears NW and SE; desc. over NE slope.</p>
40.30	<p>The cor. of secs. 1, 2, 11, and 12, monumented with a sandstone, 16 x 12 x 6 ins., firmly set, projecting 6 ins. above ground, mkd. 1 notch on E and 5 notches on S edge.</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS

At the corner point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T 17 S R 8 E
S 2   S 1
S 11   S 12
1982

Deposit the mkd. stone alongside the iron post.

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W of cor.

---

(Restoring the Survey Executed by A.D. Ferron in 1881  
and the Retracement Executed by J.C. Dick in 1900)

From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1969-70 resurvey of the W. bdy. of T. 17 S., R. 9 E.

from which

United States Geological Survey triangulation station "SEC COR WC 31/16S/9E", identical with the witness corner for secs. 5, 6, 31, and 32, on the S. bdy. of T. 16 S., R. 9 E., bears N. 46° 46' 35" E., 119.235 chs. dist., monumented with an iron post, 2 ins. diam., protruding 6 ins. above ground, with brass cap mkd. T16S R9E S31 S32 WC S6 S5 T17S 1940.

N. 89° 06' W., bet. secs. 1 and 12.

Over rolling bench land.

41.58 The 1/4 sec. cor. of secs. 1 and 12, monumented with a mound of stone. No mkd. stone found. This is accepted as the best available evidence of the position of the original corner.

At the corner point (center of mound)

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.

T 17 S R 8 E
S 1
1/4   S 12
1982

Raise a mound of stone, 3 ft. base, 1 ft. high, N of cor.

S. 88° 23' W., beginning new measurement.

19.74 Point for the W 1/16 sec. cor. of secs. 1 and 12.

Set a PVC post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS	
39.48	<p style="text-align: center;">T 17 S R 8 E W 1/16 <math>\frac{S 1}{S 12}</math> 1982</p> <p>The cor. of secs. 1, 2, 11, and 12.</p>
20.18	<p style="text-align: center;">(Restoring the Survey Executed by A.D. Ferron in 1881)</p> <hr/> <p>N. 0° 30' W., bet. secs. 1 and 2. Desc. over NE slope.</p> <p>Point for the S 1/16 sec. cor. of secs. 1 and 2.</p> <p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a mound of stone, 3 1/2 ft. base, to top of brass cap, mkd.</p>
40.36	<p style="text-align: center;">T 17 S R 8 E S 1/16 S 2   S 1 1982</p> <p>The 1/4 sec. cor. of secs. 1 and 2, monumented with a sandstone, 14 x 8 x 6 ins., firmly set, projecting 6 ins. above ground, mkd. 1/4 on W face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
40.28	<p style="text-align: center;">T 17 S R 8 E 1/4 S 2   S 1 1982</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W of cor.</p> <hr/> <p>N. 0° 08' E., beginning new measurement.</p> <p>Over rolling bench land.</p> <p>The cor. of secs. 1 and 2, on the N. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1976 resurvey of the N. bdy. of T. 17 S., R. 8 E.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS

(Restoring the Survey Executed by A.D. Ferron in 1881 and the Retracement Executed by J.C. Dick in 1900)

From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap, mkd. as described in the official record of the 1970 resurvey of the N. bdy. of T. 18 S., R. 8 E.


N. 0° 14' W., bet. secs. 34 and 35.

Over gentle rolling bench land.

0.15 Dirt road, bears E and curves S.

40.13 Point for the 1/4 sec. cor. of secs. 34 and 35, determined latitudinally by fence line bearing E and W, and proportioned longitudinally.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.




Cor. is located 3 lks. N of large cottonwood tree.

N. 0° 14' W., beginning new measurement.

40.47 The cor. of secs. 26, 27, 34, and 35, monumented with a sandstone, which is broken into 2 pieces, with bottom portion in place and scattered mound of stone to W.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.



Deposit broken portions of sandstone alongside the aluminum post.

(Restoring the Survey Executed by A.D. Ferron in 1881)

From the cor. of secs. 25, 26, 35, and 36.

S. 89° 31' W., bet. secs. 26 and 35.

Over cultivated farmland.

40.09 Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS	
80.18	<p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 17 S R 8 E S 26 1/4 S 35 1983</p> <p>Cor. is located 61 lks. E and 12 lks. N of fence cor.</p> <p>The cor. of secs. 26, 27, 34, and 35.</p>
39.81	<p style="text-align: center;">(Restoring the Survey Executed by A.D. Ferron in 1881 and the Retracement Executed by J.C. Dick in 1900)</p> <hr/> <p>N. 1° 42' W., along the W. bdy. of sec. 26.</p> <p>Over gentle rolling land.</p> <p>Point for the 1/4 sec. cor. of sec. 27 only. Not monumented.</p>
40.88	<p>The 1/4 sec. cor. of sec. 26 only, monumented with a sandstone, 14 x 10 x 4 ins., projecting 10 ins. above ground, and plainly mkd. 1/4 on W face.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.</p> <p style="text-align: center;">T 17 S R 8 E 1/4   S 26   1982</p>
38.74	<p>Deposit the mkd. stone alongside the aluminum post.</p> <hr/> <p>N. 0° 52' W., beginning new measurement.</p> <p>Point for the closing cor. of secs. 22 and 27, at proportionate distance; there is no remaining evidence of the original cor. Not monumented.</p>
40.47	<p>The cor. of secs. 23 and 26, monumented with a sandstone, 8 x 7 x 5 ins., above ground, plainly mkd. 2 notches on S and E edges.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">T 17 S R 8 E S 23 S 22   S 26 1982</p> <p>Deposit the mkd. stone alongside the aluminum post.</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS	
	<p>(Restoring the Survey Executed by A.D. Ferron in 1881)</p> <hr/> <p>From the cor. of secs. 23, 24, 25, and 26. S. 89° 44' W., bet. secs. 23 and 26. Over rolling land.</p>
20.16	<p>Point for the E 1/16 sec. cor. of secs. 23 and 26. Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 17 S R 8 E           S 23 E 1/16    S 26           1982</p>
40.32	<p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.</p> <p>Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 17 S R 8 E           S 23 1/4       S 26           1982</p>
60.48	<p>Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, N of cor.</p> <p>Point for the W 1/16 sec. cor. of secs. 23 and 26. Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 17 S R 8 E           S 23 W 1/16   S 26           1982</p>
80.64	<p>Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, N of cor.</p> <p>The cor. of secs. 23 and 26.</p>
	<p>(Restoring the Survey Executed by A.D. Ferron in 1881 and the Retracement Executed by J.C. Dick in 1900)</p> <hr/> <p>N. 0° 32' W., along the W. bdy. of sec. 23. Over rolling bench land.</p>
20.125	<p>Point for the S 1/16 sec. cor. of sec. 23 only.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS	
	<p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 17 S R 8 E S 1/16   S 23 1982</p>
	<p>Raise a mound of stone, 2 1/2 ft. base, 1 ft. high, W of cor.</p>
	<p>Cor. is located on N slope of clay spur; spur slopes E.</p>
37.74	<p>Point for the 1/4 sec. cor. of sec. 22 only, at proportionate distance based on lottings shown on the plat accepted November 2, 1901. Not monumented.</p>
40.25	<p>The 1/4 sec. cor. of secs. 22 and 23, monumented with a sandstone, 14 x 12 x 6 ins., set firmly in mound of stone, dimly mkd. 1/4 on W face.</p>
	<p>NOTE: This 1/4 sec. cor. will be used to control the S. bdy. of the NE 1/4 of sec. 22 as shown on the plat accepted November 2, 1901.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T 17 S R 8 E 1/4   S 22   S 23 1982</p>
	<p>Deposit the mkd. stone alongside the iron post.</p>
	<p>N. 0° 29' W., beginning new measurement.</p>
	<p>Over rolling bench land.</p>
20.155	<p>Point for the N 1/16 sec. cor. of secs. 22 and 23.</p>
	<p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 17 S R 8 E N 1/16 S 22   S 23 1982</p>
	<p>Raise a mound of stone, 3 1/2 ft. base, 2 1/2 ft. high, W of cor.</p>
40.31	<p>The cor. of secs. 14, 15, 22, and 23, monumented with a sandstone, 16 x 12 x 8 ins., firmly set, projecting 10 ins. above ground, plainly mkd. 4 notches on S and 2 notches on E edge.</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 17 S., R. 8 E., Salt Lake Meridian, Utah

## CHAINS

At the corner point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} T 17 S R 8 E \\ S 15 | S 14 \\ \hline S 22 | S 23 \\ 1982 \end{array}$$

Deposit the mkd. stone alongside the iron post.

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W of cor.

(Restoring the Survey Executed by  
A.D. Ferron in 1881)

From the cor. of secs. 13, 14, 23, and 24.

S. 89° 40' W., bet. secs. 14 and 23.

Over cultivated land.

20.135 Point for the E 1/16 sec. cor. of sec. 14 and 23.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.

$$\begin{array}{r} T 17 S R 8 E \\ S 14 \\ E 1/16 \quad \hline S 23 \\ 1983 \end{array}$$

23.50 Leave cultivated land.

40.27 Point for the 1/4 sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.

$$\begin{array}{r} T 17 S R 8 E \\ S 14 \\ 1/4 \quad \hline S 23 \\ 1983 \end{array}$$

60.405 Point for the W 1/16 sec. cor. of secs. 14 and 23.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.

$$\begin{array}{r} T 17 S R 8 E \\ S 14 \\ W 1/16 \quad \hline S 23 \\ 1983 \end{array}$$

80.54 The cor. of secs. 14, 15, 22, and 23.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 17 S., R. 8 E., Salt Lake Meridian, Utah

## CHAINS

(Restoring the Survey Executed by A.D. Ferron in 1881  
and the Retracement Executed by A.D. Ferron in 1882).

N. 0° 29' W., bet. secs. 14 and 15.

Over rolling land.

20.115 Point for the S 1/16 sec. cor. of secs. 14 and 15.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26  
ins. in the ground, with aluminum cap mkd.

T 17 S R 8 E  
S 1/16  
S 15 | S 14  
1983

40.23 Point for the 1/4 sec. cor. of secs. 14 and 15, at  
proportionate distance; there is no remaining evidence of  
the original corner.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins.  
in the ground, with brass cap mkd.

T 17 S R 8 E  
1/4  
S 15 | S 14  
1983

Cor. is located 31 lks. N of irrigation canal, which flows  
E.

41.00 Gravel road, bears W and curves SE; enter Huntington Creek  
bottom.

47.00 Huntington Creek, drains SE.

75.25 Utah State Highway No. 31, bears S. 31° 30' E. and curves  
NW.

80.46 The cor. of secs. 10, 11, 14, 15, determined by a fence  
cor., with fences bearing E, W and S. This position is  
harmoniously related to existing original corners and is  
accepted as the best available evidence of the original  
corner.

At the corner point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins.  
in the ground, with brass cap mkd.

T 17 S R 8 E  
S 10 | S 11  
S 15 | S 14  
1982

Cor. is located about 1.50 chs. NE of Fish and Game  
building.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS

(Restoring the Survey Executed by A.D. Ferron in 1881)

From the cor. of secs. 11, 12, 13, and 14.

S. 89° 15' W., bet. secs. 11 and 14.

Over rolling bench land; along N side of gravel road.

39.83

The 1/4 sec. cor. of secs. 11 and 14, determined by a fence cor., with fences bearing N, S and E. This position is harmoniously related to existing original corners and is accepted as the best available evidence of the original corner.

At the corner point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T 17 S R 8 E  
S 11  
1/4 S 14  
1982

West, beginning new measurement.

40.66

The cor. of secs. 10, 11, 14, and 15.

(Restoring the Survey Executed by A.D. Ferron in 1881 and the Retracement Executed by A.D. Ferron in 1882)

N. 0° 29' W., bet. secs. 10 and 11.

Over rolling bench land.

20.12

Point for the S 1/16 sec. cor. of secs. 10 and 11.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T 17 S R 8 E  
S 1/16  
S 10 | S 11  
1982

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W of cor.

40.24

The 1/4 sec. cor. of secs. 10 and 11, monumented with a sandstone, 15 x 8 x 6 ins., firmly set, protruding 8 ins. above ground, and plainly mkd. 1/4 on W face.

At the corner point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS

T 17 S R 8 E  
1/4  
S 10 | S 11  
1982

Deposit the mkd. stone alongside the iron post.

N. 0° 36' W., beginning new measurement.

Asc. over gradual S slope.

40.38

The cor. of secs. 10 and 11 only, monumented with a sandstone, 20 x 10 x 5 ins., firmly set, protruding 10 ins. above ground, plainly mkd. 5 notches on S and 2 notches on E edge.

At the corner point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of brass cap, mkd.

T 17 S R 8 E  
S 3  
S 10 | S 11  
1982

Deposit the mkd. stone alongside the iron post.

(Restoring the Survey Executed by A.D. Ferron in 1881  
and the Retracement by J.C. Dick in 1900)

From the cor. of secs. 1, 2, 11, and 12.

S. 88° 20' W., bet. secs. 2 and 11.

Over rolling bench land.

19.995

Point for the E 1/16 sec. cor. of secs. 2 and 11.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.

T 17 S R 8 E  
S 2  
E 1/16 | S 11  
1982

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, N of cor.

39.99

The 1/4 sec. cor. of secs. 2 and 11, monumented with a sandstone, 16 x 10 x 6 ins., firmly set, protruding 8 ins. above ground, and plainly mkd. 1/4 on N face.

At the corner point

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T 17 S R 8 E  
S 2  
1/4 S 11  
1982

Deposit the mkd. stone alongside the iron post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.

N. 89° 52' W., beginning new measurement.

Over rolling bench land.

39.60 The closing cor. of secs. 2 and 3, hereinafter described.

40.18 The cor. of secs. 10 and 11.

(Restoring the Survey Executed by  
J.C. Dick in 1900)

From the cor. of secs, 2 and 3, N. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1976 resurvey of the S. bdy. of T. 16 S., R. 8 E.

S. 0° 03' E., bet. secs. 2 and 3.

Over rolling bench land.

39.99 The 1/4 sec. cor. of secs. 2 and 3, monumented with a sandstone, 14 x 10 x 6 ins., firmly set, protruding 8 ins. above ground, and plainly mkd. 1/4 on W face.

At the corner point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 17 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of brass cap, mkd.

T 17 S R 8 E  
1/4  
S 3 | S 2  
1982

Deposit the mkd. stone alongside the iron post.

S. 0° 07' W., beginning new measurement.

Desc. over gradual S slope.

41.77 The closing cor. of secs. 2 and 3, monumented with a sandstone, 16 x 8 x 6 ins., firmly set, protruding 10 ins. above ground, and plainly mkd. CC on N face, and 2 notches on E edge.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 17 S., R. 8 E., Salt Lake Meridian, Utah

## CHAINS

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.

T 17 S R 8 E  
CC  
S 3 | S 2  
S 11  
1982

Deposit the mkd. stone alongside the aluminum post.

From this closing cor., the cor. of secs. 10 and 11, bears N 89° 48' W., 0.58 chs. dist., heretofore described.

(Restoring the Survey Executed by A.D. Ferron 1882  
and the Retracement Executed by J.C. Dick in 1900)

From the cor. of secs. 14, 15, 22, and 23.

S. 89° 58' W., bet. secs. 15 and 22.

Over rolling bench land.

40.65

Point for the 1/4 sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T 17 S R 8 E  
S 15  
1/4 S 22  
1982

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, S of cor.

77.61

The closing cor. of secs. 16 and 22, hereinafter described.

81.48

The SW cor. of sec. 15, monumented with a sandstone, 16 x 14 x 10 ins., firmly set, protruding 10 ins. above ground, and plainly mkd. 3 notches on S and E edges.

At the corner point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T 17 S R 8 E  
| S 15  
1982

Deposit the mkd. stone alongside the iron post.

(Restoring the Survey Executed by  
J.C. Dick in 1900)

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 17 S., R. 8 E., Salt Lake Meridian, Utah

## CHAINS

From the 1/4 sec. cor. of secs. 21 and 22, monumented with a broken sandstone, 10 x 8 x 6 ins., a portion firmly set in the ground and the broken portion dimly mkd. 1/4.

At the corner point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T 17 S R 8 E  
1/4  
S 21 | S 22  
1982

Deposit the broken sandstone alongside the iron post.

N. 0° 02' W., bet. secs. 21 and 22.

Over gentle rolling land

39.66 Point for the closing cor. of secs. 16 and 21, hereinafter described.

42.97 The closing cor. of secs. 16 and 22, monumented with a sandstone, 18 x 9 x 6 ins., firmly set, protruding 10 ins. above ground, and plainly mkd. CC and 3 grooves on S face, and 3 grooves on E face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.

T 17 S R 8 E  
S 15  
S 16 | S 22  
CC  
1982

Deposit the mkd. stone alongside the aluminum post.

From the closing cor., the SW cor. of sec. 15, bears S. 89° 58' W., 3.87 chs. dist., heretofore described.

(Restoring the Survey Executed by A.D. Ferron in 1882  
and the Retracement Executed by J.C. Dick in 1900)

From the SW cor. of sec. 15.

North, bet. secs. 15 and 16.

Over rolling bench land, through scattered juniper and pinon.

40.91 The 1/4 sec. cor. of secs. 15 and 16, monumented with a sandstone boulder, 3 x 2 x 1 ft. above ground, plainly mkd. 1/4 on SW face.

from which new bearing trees

A pinon, 8 ins. diam., bears N. 78 1/2° E., 50 lks. dist., mkd. 1/4 S15 BT.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS	
	<p>A pinon, 10 ins. diam., bears S. 36° W., 64 lks. dist., mkd. 1/4 S16 BT.</p>
	<p>No other improvements can be made on this corner.</p>
	<p>N. 0° 47' E., beginning new measurement.</p>
	<p>Asc. over S slope.</p>
20.075	<p>Point for the N 1/16 sec. cor. of secs. 15 and 16.</p>
	<p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.</p>
	<p style="text-align: center;">T 17 S R 8 E N 1/16 S 16   S 15 1982</p>
28.30	<p>Gravel road, bears E and curves NW: enter cultivated land.</p>
40.15	<p>The cor. of secs. 9, 10, 15, and 16, monumented with a sandstone, 10 x 6 x 4 ins., firmly set, protruding 6 ins. above ground, and plainly mkd. 4 notches on S and 3 notches on E edges</p>
	<p>At the corner point</p>
	<p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 17 S R 8 E S 9   S 10 S 16   S 15 1982</p>
	<p>Deposit the mkd. stone alongside the iron post.</p>
	<p>Cor. is located 1 lk. W of N-S fence line.</p>
	<p style="text-align: center;">(Restoring the Survey Executed by A.D. Ferron in 1882)</p>
	<p>From the cor. of secs. 10, 11, 14, and 15.</p>
	<p>N. 89° 37' W., bet. secs. 10 and 15.</p>
	<p>Over cultivated land.</p>
11.00	<p>Utah State Highway No. 31, bears N. 70° W. and S. 70° E.</p>
40.12	<p>Point for the 1/4 sec. cor. of secs. 10 and 15, at proportionate distance, falls in cultivated land; there is no remaining evidence of the original corner. Cor. point is not monumented.</p>
56.50	<p>Huntington Creek, flows irregularly SE.</p>
80.24	<p>The cor. of secs. 9, 10, 15, and 16.</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS	
	N. 0° 04' W., bet. secs. 9 and 10.
	Over cultivated land.
10.00	Huntington Creek, flows SE; asc. over gradual S slope.
13.50	Utah State Highway No. 31, bears N. 70° W. and S. 70° E.
19.94	Point for the S 1/16 sec. cor. of secs. 9 and 10.
	Set a PVC post, 30 ins. long, 2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.
	<p style="text-align: center;">T 17 S R 8 E S 1/16 S 9   S 10 1982</p>
	Cor. is located 3 lks. W of N-S fence line.
39.88	The 1/4 sec. cor. of secs. 9 and 10, monumented with a sandstone, 16 x 10 x 6 ins., firmly set, protruding 8 ins. above ground, plainly mkd. 1/4 on W face.
	At the corner point
	Set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T 17 S R 8 E 1/4 S 9   S 10 1982</p>
	Deposit the mkd. stone alongside the iron post.
	N. 0° 26' E., beginning new measurement.
	Asc. over gradual S slope.
20.295	Point for the N 1/16 sec. cor. of secs. 9 and 10.
	Set an iron post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of brass cap, mkd.
	<p style="text-align: center;">T 17 S R 8 E N 1/16 S 9   S 10 1982</p>
40.59	The cor. of secs. 3, 4, 9, and 10, monumented with a sandstone, 16 x 12 x 8 ins., firmly set, protruding 10 ins. above ground, plainly mkd. 5 notches on S and 3 notches on E edges.
	At the corner point

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 17 S., R. 8 E., Salt Lake Meridian, Utah

## CHAINS

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 17 S R 8 E  
S 4 | S 3  
S 9 | S 10  
1982

Deposit the mkd. stone alongside the iron post.

(Restoring the Survey Executed by A.D. Ferron in 1882  
and the Retracement Executed by J.C. Dick in 1900)

From the cor. of secs. 10 and 11.

N. 89° 48' W., bet. secs. 3 and 10.

Over rolling bench land.

39.66 The 1/4 sec. cor. of sec. 10, monumented with a sandstone, 14 x 10 x 5 ins., firmly set, protruding 7 ins. above ground, plainly mkd. 1/4 on S face.

At the corner point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 17 S R 8 E  
1/4 S 10  
1982

Deposit the mkd. stone alongside the iron post.

N. 89° 38' W., beginning new measurement.

39.54 The cor. of secs. 3, 4, 9, and 10.

(Restoring the Survey Executed by  
J.C. Dick in 1900)

N. 0° 23' E., bet. secs. 3 and 4.

Over rolling bench land.

41.48 The 1/4 sec. cor. of secs. 3 and 4, monumented with a sandstone, 16 x 8 x 6 ins., firmly set, protruding 8 ins. above ground, plainly mkd. 1/4 on W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS

T 17 S R 8 E  
1/4  
S 4 | S 3  
1982

Deposit the mkd. stone alongside the aluminum post.

N. 0° 12' E., beginning new measurement.

39.84

The cor. of secs. 3 and 4, N. bdy. of the Tp., monumented with an iron pot, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1976 resurvey of the S. bdy. of T. 16 S., R. 8 E.

The point for the 1/4 sec. cor. of sec. 3 only, is at midpoint on the S. bdy. of sec. 3.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 17 S R 8 E  
1/4 S 3  
1982

From this point, the 1/4 sec. cor. of sec. 10 only, bears N. 89° 48' W., 0.35 chs. dist., heretofore described.

From the cor. of secs. 20 and 21, monumented with a sandstone, 16 x 6 x 6 ins., firmly set, protruding 9 ins. above ground, plainly mkd. 3 notches on S and 4 notches on E edge.

At the corner point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T 17 S R 8 E  
S 16  
S 20 | S 21  
1982

Deposit the mkd. stone alongside the iron post.

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, S of cor.

N. 89° 53' E., bet. secs. 16 and 21.

13.50

Power transmission line, bear N. 56° W. and S. 56° E.

17.00

Power transmission line, bear N. 56° W. and S. 56° E.

19.50

Power transmission line, bear N. 56° W. and S. 56° E.

35.98

Point for the 1/4 sec. cor. of sec. 16 only, at proportionate dist.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS	
	<p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.</p> <p style="text-align: center;">T 17 S R 8 E <u>1/4 S 16</u> 1982</p>
39.91	<p>Point for the 1/4 sec. cor. of sec. 21, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 17 S R 8 E <u>1/4 S 21</u> 1982</p>
79.52	<p>Intersect the W. bdy. of sec. 22.</p> <p>Point for the closing cor. of secs. 16 and 21.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 17 S R 8 E C S 16   C S 21   S 22 1982</p>
79.82	<p>The original closing cor. of secs. 16 and 21, monumented with a sandstone, 16 x 9 x 8 ins., firmly set, protruding 10 ins. above ground, plainly mkd. CC and 3 grooves on S and 3 grooves on E face. Add the marks AM on W face and bury the stone in place, 6 ins. below surface.</p>
3.98	<p>From the cor. of secs. 20 and 21.</p> <p>S. 89° 54' W., along the N. bdy. of sec. 20.</p> <p>Over rolling bench land.</p>
39.88	<p>The closing cor. of secs. 16 and 17, hereinafter described.</p>
39.88	<p>The 1/4 sec. cor. of sec. 20, monumented with a sandstone, 18 x 12 x 4 ins., firmly set, protruding 10 ins. above ground, and plainly mkd. 1/4 on W face.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of brass cap, mkd.</p> <p style="text-align: center;">T 17 S R 8 E <u>1/4 S 20</u> 1982</p> <p>Deposit the mkd. stone alongside the iron post.</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS

(Restoring the Survey Executed by A.D. Ferron in 1882  
and the Retracement Executed by J.C. Dick in 1900)

From the cor. of secs. 9, 10, 15, and 16.

N. 89° 59' W., bet. secs. 9 and 16.

Over rolling bench land.

20.285 Point for the E 1/16 sec. cor. of secs. 9 and 16.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins.  
in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T 17 S R 8 E} \\ \text{S 9} \\ \hline \text{E 1/16 S 16} \\ \text{1982} \end{array}$$

23.50 Gravel road, bears NW and SE.

40.57 The 1/4 sec. cor. of secs. 9 and 16, monumented with a  
sandstone, 18 x 14 x 4 ins., firmly set, protruding 8 ins.  
above ground, plainly mkd. 1/4 on N face.

At the corner point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins.  
in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T 17 S R 8 E} \\ \text{S 9} \\ \hline \text{1/4 S 16} \\ \text{1982} \end{array}$$

Deposit the mkd. stone alongside the iron post.

N. 89° 52' W., beginning new measurement.

Asc. over gradual E slope.

39.89 The cor. of secs. 9 and 16, monumented with a sandstone,  
14 x 10 x 8 ins., firmly set, protruding 5 ins. above  
ground, plainly mkd. 4 notches on S and E edges.

At the corner point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins.  
in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T 17 S R 8 E} \\ \text{S 8} \left| \begin{array}{l} \text{S 9} \\ \hline \text{S 16} \end{array} \right. \\ \text{1982} \end{array}$$

Deposit the mkd. stone alongside the iron post.

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, E  
of cor.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS	
	<p>S. 0° 12' E., along the W. bdy. of sec. 16. Over rolling bench land.</p>
4.69	<p>The closing cor. of secs. 8 and 17, hereinafter described.</p>
40.12	<p>Point for the 1/4 sec. cor. of sec. 16 only, at proportionate distance; there is no remaining evidence of the original corner.</p>
	<p>Set a PVC post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 17 S R 8 E 1/4   S 16 1982</p>
	<p>Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W of cor.</p>
44.69	<p>Point for the 1/4 sec. cor. of sec. 17 only, at midpoint and on line bet. the closing cor. of secs. 16 and 17, and the closing cor. of secs. 8 and 17, falls in bottom of draw and is unsafe to monument.</p>
45.27	<p>Point selected for the witness cor. to the 1/4 sec. cor. of sec. 17.</p>
	<p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p>
	<p style="text-align: center;">W C T 17 S R 8 E 1/4 ↑ S 17   1982</p>
68.95	<p>Power transmission line, bears N. 56° W. and S. 56° E.</p>
70.55	<p>Power transmission line, bears N. 56° W. and S. 56° E.</p>
72.95	<p>Power transmission line, bears N. 56° W. and S. 56° E.</p>
84.66	<p>The closing cor. of secs. 16 and 17, monumented with a sandstone, 16 x 10 x 4 ins., firmly set, protruding 10 ins. above ground, plainly mkd. CC on N face, 3 grooves on S face, and 4 grooves on E face.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of brass cap, mkd.</p>
	<p style="text-align: center;">T 17 S R 8 E C C   S 17   S 16 S 20 1982</p>
	<p>Deposit the mkd. stone alongside the iron post.</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS	
	<p>From this point, the cor. of secs. 20 and 21, bears N. 89° 54' E., 3.98 chs. dist., heretofore described.</p>
	<p>From the cor. of secs. 9 and 16. N. 0° 08' W., bet. secs. 8 and 9. Over rolling bench land.</p>
41.00	<p>Point for the 1/4 sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of brass cap, mkd.</p> <div style="text-align: center;"> <p>T 17 S R 8 E 1/4 S 8   S 9 1982</p> </div>
55.00	<p>Huntington Creek, drains E.</p>
56.75	<p>Utah State Highway No. 31, bears E and W.</p>
61.04	<p>Point for the N 1/16 sec. cor. of secs. 8 and 9.</p> <p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 17 S R 8 E N 1/16 S 8   S 9 1982</p> </div>
	<p>Cor. is located in apple orchard owned by Drannen Seeley.</p>
76.08	<p>Point for the witness cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original corner. Cor. point is not monumented.</p>
81.08	<p>The cor. of secs. 8 and 9, monumented with an aluminum post, 2 1/2 ins. diam., and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd. Emery County Survey T17S R8E SLBM 5 8 9 1982. No other improvements can be made on this corner.</p>
	<p>From the cor. of secs. 3, 4, 9, and 10. N. 89° 29' W., bet. secs. 4 and 9. Over rolling bench land.</p>
20.125	<p>Point for the E 1/16 sec. cor. of sec. 9.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS	
40.25	<p style="text-align: center;">T 17 S R 8 E ----- E 1/16 S 9 1982</p> <p>Point for the 1/4 sec. cor. of sec. 9 only, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>
60.55	<p style="text-align: center;">T 17 S R 8 E ----- 1/4 S 9 1982</p> <p>Point for the W 1/16 sec. cor. of sec. 9 only.</p> <p>Set a PVC post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.</p>
79.50	<p style="text-align: center;">T 17 S R 8 E ----- W 1/16 S 9 1982</p> <p>The closing cor. of secs. 4 and 5, hereinafter described.</p>
80.85	<p>The cor. of secs. 8 and 9:</p>
39.86	<p style="text-align: center;">(Restoring the Survey Executed by J.C. Dick in 1900)</p> <hr/> <p>From the cor. of secs. 4 and 5, N. bdy. of Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1976 resurvey of the S. bdy. of T. 16 S., R. 8 E.</p> <p>S. 0° 02'W., bet. secs. 4 and 5.</p> <p>Over rolling bench land.</p> <p>The 1/4 sec cor. of secs. 4 and 5, monumented with a sandstone, 18 x 12 x 10 ins., firmly set, protruding 10 ins. above ground, plainly mkd. 1/4 on W face.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.</p> <p style="text-align: center;">T 17 S R 8 E 1/4   S 5   S 4   1982</p> <p>Deposit the mkd. stone alongside the aluminum post.</p> <hr/>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS	
40.66	<p>S. 0° 15' W., beginning new measurement.</p> <p>The closing cor. of secs. 4 and 5, monumented with an aluminum post, 2 1/2 ins. diam, and in a mound of stone, 3 ft. base, 1 ft. high, with aluminum cap, mkd. Emery County Survey T17S R8E SLBM 4 5 9 CC 1982. No other improvements can be made on this corner.</p> <p>From this point, the cor. of secs. 8 and 9, bears N. 89° 29' W., 1.35 chs. dist., heretofore described.</p>
	<p>The point for the 1/4 sec cor. of sec. 4 only, is at midpoint on the S. bdy. of sec. 4.</p> <p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 17 S R 8 E 1/4 S 4 1982</p> <p>Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, N of cor.</p> <p>From this point, the 1/4 sec. cor. of sec. 9 only, bear N. 89° 29' W., 0.50 chs. dist., heretofore described.</p>
41.47	<p>From the cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, protruding 4 ins. above mound of stone, with brass cap, mkd. as described in the official record of the 1968 resurvey of the E. bdy. of T. 17 S., R. 7 E.</p> <p>N. 89° 07' E., bet. secs. 7 and 18.</p> <p>Over rolling bench land.</p> <p>Point for the 1/4 sec. cor. of sec. 18 only, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a PVC post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.</p> <p style="text-align: center;">T 17 S R 8 E 1/4 S 18 1982</p>
68.50	Power transmission line, bears N. 42° W. and S. 42° E.
71.50	Power transmission line, bears N. 42° W. and S. 42° E.
73.50	Power transmission line, bears N. 42° W. and S. 42° E.
79.22	The closing cor. of secs. 7 and 8, hereinafter described.
81.27	The cor. of secs. 17 and 18, determined from the remains of the tree, mkd. as the sec. cor., the root hole of a downed pinon tree, 5 ins. diam., with dim scribe markings on open blaze. There is no remaining evidence of the original bearing trees

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.

$$\begin{array}{c} T\ 17\ S\ R\ 8\ E \\ S\ 8 \\ \hline S\ 18\ | \ S\ 17 \\ 1982 \end{array}$$

S. 89° 56' E. bet. secs. 8 and 17.

Over rolling bench land.

39.29

The 1/4 sec. cor. of sec. 17 only, monumented with a sandstone, 14 x 10 x 6 ins., loosely set 4 ins. in the ground, dimly mkd. 1/4 on S face, from which the original bearing tree

A juniper, 25 ins. diam., bears S. 60° W., 4 lks. dist., mkd. 1/4 S17 BT.

At the corner point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.

$$\begin{array}{c} T\ 17\ S\ R\ 8\ E \\ \hline 1/4\ S\ 17 \\ 1982 \end{array}$$

Deposit the dimly mkd. stone alongside the iron post.

N. 89° 52' E., beginning new measurement.

40.35

The closing cor. of secs. 8 and 17, monumented with a sandstone, 18 x 14 x 2 ins., firmly set, protruding 10 ins. above ground, and plainly mkd. CC on W face, and 4 grooves on S and E faces.

At the corner point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} T\ 17\ S\ R\ 8\ E \\ C\ S\ 8\ | \\ C\ S\ 17\ | \ S\ 16 \\ 1982 \end{array}$$

Deposit the mkd. stone alongside the iron post.

Raise a mound of stone, 3 1/2 ft base, 1 1/2 ft. high, W of cor.

From this point, the cor. of secs. 9 and 16, bears N. 0° 12' W., 4.69 chs. dist., heretofore described.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS	
	<p>(Restoring the Survey Executed by A.D. Ferron in 1882 and the Retracement Executed by J.C. Dick in 1900)</p> <hr/> <p>From the cor. of secs. 8 and 9. N. 89° 51' W., bet. secs. 5 and 8. Over rolling bench land.</p>
20.815	<p>Point for the E 1/16 sec. cor. of sec. 8 only. Set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 17 S R 8 E <hr/>E 1/16 S 8 1982</p> <p>Raise a mound of stone, 3 1/2 ft base, 1 1/2 ft. high, S of cor.</p>
41.63	<p>The 1/4 sec. cor. of secs. 5 and 8, monumented with a spike imbedded in asphalt on north edge of Utah State Highway No. 31. This position is harmoniously related to existing original cors., has been used by local surveyors, and is accepted as the best available evidence of the original cor. position.</p> <p>from which I set</p> <p style="text-align: center;">An iron post, 30 ins. long, 2 1/2 ins. diam., set 12 ins. in the ground to bedrock, and in a mound of stone, 4 ft base to top for a reference monument, bears S. 89° 51' E., 172 lks. dist., with brass cap, mkd. T17S R8E 1/4 S5 S8 RM 1983 and an arrow pointing to the cor.</p> <hr/> <p>S. 89° 20' W., beginning new measurement.</p>
0.20	Center line of Utah State Highway No. 31, curves NW and S.
2.40	Huntington Creek flows irregularly SE.
9.96	Point for the east west 1/64 sec. cor. of secs. 5 and 8. Point not monumented.
19.92	<p>Point for the W 1/16 sec. cor. of secs. 5 and 8. Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.</p> <p style="text-align: center;">T 17 S R 8 E S 5 W 1/16 <hr/>S 8 1982</p>
39.84	The cor. of secs. 5, 6, 7, and 8, monumented with a sandstone, 22 x 12 x 8 ins., firmly set, protruding 10 ins. above ground, plainly mkd. 5 notches on S and E edge.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.

T 17 S R 8 E  
S 6 | S 5  
S 7 | S 8  
1982

Deposit the mkd. stone alongside the aluminum post.

S. 0° 03' E., bet. secs. 7 and 8.

Over rolling bench land, through scattered juniper and pinon.

19.97 Point for the N 1/16 sec. cor. of secs. 7 and 8.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.

T 17 S R 8 E  
N 1/16  
S 7 | S 8  
1982

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W of cor.

39.94 The 1/4 sec. cor. of secs. 7 and 8, monumented with a sandstone, 16 x 10 x 6 ins., firmly set, protruding 8 ins. above ground, plainly mkd. 1/4 on W face, from which the original bearing trees

A juniper, 14 ins. diam., bears S. 77 1/2° E., 17 lks. dist., mkd. 1/4 S8 BT.

A pinon (dead), 10 ins. diam., bears S. 21° W., 14 lks. dist., mkd. 1/4 S7 BT.

At the corner point

Set a PVC post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.

T 17 S R 8 E  
1/4  
S 7 | S 8  
1982

Deposit the mkd. stone alongside the PVC post.

(Restoring the Survey Executed by  
J.C. Dick in 1900)

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS

S.  $0^{\circ} 05'$  W., beginning new measurement.

Asc. over gradual N slope.

45.53

The closing cor. of secs. 7 and 8, monumented with a sandstone, 18 x 14 x 10 ins., firmly set, protruding 10 ins. above ground, plainly mkd. CC on N, 4 grooves on S, and 5 grooves on E face, from which the remains of the original bearing tree

A pinon, 14 ins. diam., bears N.  $28 \frac{1}{2}^{\circ}$  E.,  
8 lks. dist., mkd. T17S R8E S8 BT.

There is no remaining evidence of the other bearing tree.

At the corner point

Set an iron post, 30 ins. long,  $2 \frac{1}{2}$  ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone,  $3 \frac{1}{2}$  ft. base, to top of brass cap, mkd.

T 17 S R 8 E  
C C  
S 7 | S 8  
S 18  
1982

Deposit the mkd. stone alongside the iron post.

From this point, the cor. of secs. 17 and 18, bears N.  $89^{\circ} 07'$  E., 2.05 chs. dist., heretofore described.

The point for the 1/4 sec. cor. of sec. 8 only, is at midpoint on the S. bdy. of sec. 8.

Set an aluminum post, 30 ins. long,  $2 \frac{1}{2}$  ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone,  $3 \frac{1}{2}$  ft. base, to top of aluminum cap, mkd.

T 17 S R 8 E  
1/4 S 8  
1982

From this point, the 1/4 sec. cor. of sec. 17 only, bears S.  $89^{\circ} 56'$  E., 0.50 chs. dist., heretofore described.

The point for the 1/4 sec. cor of sec. 7 only, is at proportionate distance based on the original plat, and on the S. bdy. of sec. 7.

At the corner point

Set an aluminum post, 30 ins. long,  $2 \frac{1}{2}$  ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone,  $3 \frac{1}{2}$  ft. base, to top of aluminum cap, mkd.

T 17 S R 8 E  
1/4 S 7  
1982

From this point, the 1/4 sec cor. of sec. 18 only, bears N.  $89^{\circ} 07'$  E., 2.05 chs. dist., heretofore described.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS	
	<p>(Restoring the Survey Executed by A.D. Ferron in 1882, and the Retracement Executed by J.C. Dick in 1900)</p>
	<p>From the cor. of secs. 5, 6, 7, and 8.</p>
	<p>N. 89° 57' W., bet. secs. 6 and 7.</p>
	<p>Over rolling bench land; asc. over steep NE slope.</p>
19.94	<p>Point for the E 1/16 sec. cor. of secs. 6 and 7.</p>
	<p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14</p>
	<p>ins. in the ground to bedrock, and in a mound of stone,</p>
	<p>4 1/2 ft. base, to top of aluminum cap, mkd.</p>
	<p style="text-align: center;">T 17 S R 8 E</p>
	<p style="text-align: center;">E 1/16    <math>\frac{S 6}{S 7}</math></p>
	<p style="text-align: center;">1982</p>
32.50	<p>Top of ridge, bears NW and SE; asc. over gradual NE slope.</p>
39.88	<p>The 1/4 sec. cor. of secs. 6 and 7, monumented with a</p>
	<p>sandstone, 15 x 9 x 4 ins., firmly set, protruding 10 ins.</p>
	<p>above ground, plainly mkd. 1/4 on N face.</p>
	<p>At the corner point</p>
	<p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26</p>
	<p>ins. in the ground, with aluminum cap mkd.</p>
	<p style="text-align: center;">T 17 S R 8 E</p>
	<p style="text-align: center;">1/4    <math>\frac{S 6}{S 7}</math></p>
	<p style="text-align: center;">1982</p>
	<p>Deposit the mkd. stone alongside the aluminum post.</p>
	<p>Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, N</p>
	<p>of cor.</p>
	<p>S. 89° 48' W., beginning new measurement.</p>
	<p>Asc. over gradual NE slope.</p>
19.895	<p>Point for the W 1/16 sec. cor. of sec. 7.</p>
	<p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins.</p>
	<p>in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 17 S R 8 E</p>
	<p style="text-align: center;">W 1/16    <math>\frac{S 7}{S 7}</math></p>
	<p style="text-align: center;">1982</p>
	<p>Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, N</p>
	<p>of cor.</p>
20.57	<p>Point for the W 1/16 sec. cor. of sec. 6.</p>
	<p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16</p>
	<p>ins. in the ground to bedrock, and in a mound of stone, 4</p>
	<p>ft. base, to top of aluminum cap, mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 17 S., R. 8 E., Salt Lake Meridian, Utah


CHAINS	
	<p style="text-align: center;">T 17 S R 8 E W 1/16 S 6 1982</p>
39.39	<p>The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, protruding 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1968 resurvey of the E. bdy. of T. 17 S., R. 7 E.</p>
6.00	<p>From the cor. of secs. 5, 6, 7, and 8. North, bet. secs. 5 and 6. Over gentle rolling bench land; desc. over N slope. Huntington Creek, flows irregularly SE.</p>
18.75	<p>Utah State Highway No. 31, curves NW and E.</p>
20.095	<p>Point for the S 1/16 sec. cor. of secs. 5 and 6. Set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 17 S R 8 E S 1/16 S 6   S 5 1982</p>
40.19	<p>The 1/4 sec. cor. of secs. 5 and 6, monumented with a sandstone, 18 x 12 x 10 ins., firmly set, protruding 10 ins. above ground, plainly mkd. 1/4 on W face. At the corner point Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 2 1/2 ft. base, to top of aluminum cap, mkd.</p>
	<p style="text-align: center;">T 17 S R 8 E 1/4   S 6   S 5 1982</p> <p>Deposit the mkd. stone alongside the aluminum post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 16' E., beginning new measurement. Asc. over gradual S slope.</p>
20.375	<p>Point for the N 1/16 sec. cor. of secs. 5 and 6. Set a PVC post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.</p>
	<p style="text-align: center;">T 17 S R 8 E N 1/16 S 6   S 5 1982</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS	
40.75	<p>Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W of cor.</p> <p>The cor. of secs. 5 and 6, N. bdy. of Tp., heretofore described.</p>
<p>Subdivision of Section 1, T. 17 S., R. 8 E., Salt Lake Meridian, Utah</p>	
19.805	<p>From the 1/4 sec. cor. of secs. 1 and 12.</p> <p>N. 0° 30' E., on the N and S center line of sec. 1.</p> <p>Over gentle rolling land.</p>
19.805	<p>Point for the center south 1/16 sec. cor. of sec. 1.</p> <p>Set a PVC post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.</p>
<pre>       C         S 1/16   S 1               C             1982           </pre>	
39.61	<p>Point for the center 1/4 sec. cor. of sec. 1, at intersection with the E-W center line.</p> <p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
<pre>     T 17 S R 8 E       C 1/4       S 1       1982           </pre>	
79.92	<p>The 1/4 sec. cor. of sec. 1 only, on the N. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., protruding 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1976 resurvey of the N. bdy. of T. 17 S., R. 8 E.</p>
40.90	<p>From the 1/4 sec. cor. of secs. 1 and 6, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., protruding 6 ins. above ground, mkd. as described in the official record of the 1970 resurvey of the W. bdy. of T. 17 S., R. 9 E.</p> <p>S. 89° 31' W., on the E and W center line of sec. 1.</p> <p>Over rolling bench land.</p>
40.90	<p>The center 1/4 sec. cor. of sec. 1.</p>
60.98	<p>Point for the center west 1/16 sec. cor. of sec. 1.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.</p>

Subdivision of Section 1,  
T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS



81.06


The 1/4 sec. cor. of secs. 1 and 2.

From the W 1/16 sec. cor. of secs. 1 and 12.  
North, on the N and S center line of the SW 1/4 of sec. 1.  
Over gentle rolling land.

19.995

Point for the SW 1/16 sec. cor. of sec. 1, at intersection with the E-W center line of the SW 1/4

Set an PVC post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.



39.99

The center west 1/16 sec. cor. of sec. 1.

From the center south 1/16 sec cor. of sec 1.  
S. 88° 57' W., on the E and W center line of the SW 1/4 of sec. 1.

19.915

The SW 1/16 sec. cor. of sec. 1.

39.83

The S 1/16 sec cor. of secs. 1 and 2.


Subdivision of Section 5,  
T. 17 S., R. 8 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 5 and 8.  
N. 20° 35' E., on the N and S center line of sec. 5.  
Over rolling bench land.

20.08

Point for the center south 1/16 sec. cor. of sec. 5.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.



40.16

Point for the center 1/4 sec. cor. of sec. 5, at intersection with the E-W center line.

Subdivision of Section 5,  
T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS	
	<p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 17 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.</p> <p style="text-align: center;">T 17 S R 8 E C 1/4 S 5 1982</p>
60.20	<p>Point for the center north 1/16 sec. cor. of sec 5.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">C N 1/16   S 5 C 1983</p>
80.24	<p>The 1/4 sec. cor. of sec. 5 only, on the N. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., protruding 6 ins. above ground, mkd. as described in the official record of the 1976 resurvey of the N. bdy. of T. 17 S., R. 8 E.</p>
41.32	<p>From the 1/4 sec. cor. of secs. 4 and 5.</p> <p>S. 89° 27' W., on the E and W center line of sec. 5.</p> <p>Over rolling bench land.</p>
62.145	<p>The center 1/4 sec. cor. of sec. 5.</p>
82.97	<p>Point for the center west 1/16 sec. cor. of sec. 5.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">C      W 1/16       S 5      C       1983</p>
2.00	<p>The 1/4 sec. cor. of secs. 5 and 6.</p> <p>From the W 1/16 sec. cor. of secs. 5 and 8.</p> <p>N. 1° 17' E., on the N and S center line of the SW 1/4 of sec. 5.</p> <p>Over rolling bench land.</p>
8.50	<p>Huntington Creek, drains E.</p>
20.09	<p>Utah State Highway No. 31, bear N. 80° W. and S. 80° E.</p>
	<p>Point for the SW 1/16 sec. cor. of sec. 5, at intersection with the E-W center line of the SW 1/4.</p>

Subdivision of Section 5,  
T. 17 S., R. 8 E., Salt Lake Meridian, Utah

## CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.

SW 1/16  
S 5  
1983

40.18 The center west 1/16 sec. cor. of sec. 5.

From the center south 1/16 sec. cor. of sec. 5.

S. 89° 24' W., on the E and W center line of the SW 1/4 of sec. 5.

Over rolling bench land; desc. over SW slope.

20.37 The southwest 1/16 sec. cor. of sec. 5.

40.74 The south 1/16 sec cor. of secs. 5 and 6.

From the center west 1/16 sec. cor. of sec. 5.

N. 1° 25' E., on the N and S center line of the NW 1/4 of sec. 5.

Over rolling bench land.

20.205 Point for the NW 1/16 sec. cor. of sec. 5, at intersection with the E-W center line of the NW 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

NW 1/16  
S 5  
1983

40.41 The W 1/16 sec. cor. of sec. 5 only, on the N. bdy. of the Tp., heretofore described.

From the center north 1/16 sec. cor. of sec. 5.

S. 89° 55' W., on the E and W center line of the NW 1/4 of sec. 5.

Over rolling bench land.

21.23 The NW 1/16 sec. cor. of sec. 5.

42.46 The N 1/16 sec. cor. of secs. 5 and 6.

Subdivision of Section 6  
T. 17 S., R. 8 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 6 and 7.

N. 0° 33' W., on the N and S center line of sec. 6.

Subdivision of Section 6,  
T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS	
	Over rolling bench land.
20.31	Point for the center south 1/16 sec. cor. of sec. 6.
	Set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, and in a collar of stone, with brass cap mkd.
	$\begin{array}{c} C \\   \\ S \ 1/16 \quad   \quad S \ 6 \\   \\ C \\ 1982 \end{array}$
	Cor. is located on steep N slope.
40.62	Point for the center 1/4 sec. cor. of sec. 6, at the intersection with the E-W center line.
	Set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} T \ 17 \ S \ R \ 8 \ E \\ C \ 1/4 \\ S \ 6 \\ 1982 \end{array}$
	Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W of cor.
53.90	Huntington Creek, flows SW.
54.90	Utah State Highway No. 31, curves NW and SE.
80.89	The 1/4 sec. cor. of sec. 6, T. 17 S., R. 8 E., monumented with a sandstone boulder, 10 x 8 x 5 ft. above ground, plainly mkd. 1/4 on top of boulder.
	from which the witness corner
	An iron post, 2 1/2 ins. diam., protruding 6 ins. above mound of stone, with brass cap, mkd. as described in the official record of the dependent resurvey of the N. bdy. of T. 17 S., R. 8 E., bears N. 89° 52' E., 0.05 chs. dist.
	From the 1/4 sec. cor. of secs. 5 and 6.
	N. 89° 20' W., on the E and W center line of sec. 6.
	Over rolling bench land.
18.70	Utah State Highway No. 31, bears NW and SE.
20.135	Point for the center east 1/16 sec. cor. of sec. 6.
	Set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, and in a collar of stone, with brass cap mkd.
	$\begin{array}{c} E \ 1/16 \\ C \ \frac{\quad}{S \ 6} \ C \\ 1982 \end{array}$

Subdivision of Section 6,  
T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS	
22.00	Huntington Creek, drains SE.
40.27	The center 1/4 sec. cor. of sec. 6.
60.61	<p>Point for the center west 1/16 sec. cor. of sec. 6.</p> <p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>
	$\begin{array}{c} \text{W } 1/16 \\ \text{C} \frac{\text{S } 6}{1982} \text{C} \end{array}$
79.18	<p>The 1/4 sec. cor. of sec. 6 only, on the W. bdy. of the Tp., heretofore described.</p>
	<hr/> <p>From the E 1/16 sec. cor. of secs. 6 and 7.</p>
	<p>N. 0° 17' W., on the N and S center line of the SE 1/4 of sec. 6.</p>
	<p>Desc. over NE slope.</p>
20.20	<p>Point for the SE 1/16 sec. cor. of sec. 6, at the intersection with the E-W center line of the SE 1/4.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.</p>
	$\begin{array}{c} \text{T } 17 \text{ S } \text{ R } 8 \text{ E} \\ \text{SE } 1/16 \\ \text{S } 6 \\ 1982 \end{array}$
36.50	Huntington Creek, flows SE.
40.40	The center east 1/16 sec. cor. of sec. 6.
	<hr/> <p>From the S 1/16 sec. cor. of secs. 5 and 6.</p>
	<p>N. 89° 38' W., on the E and W center line of the SE 1/4 of sec. 6.</p>
	<p>Over rolling bench land; desc. over SW slope.</p>
5.50	Utah State Highway No. 31, bears NW and curves SE.
7.00	Huntington Creek, flows SE.
20.04	The SE 1/16 sec. cor. of sec. 6.
40.08	The center south 1/16 sec. cor. of sec. 6.
	<hr/> <p>From the W 1/16 sec. cor. of secs. 6 and 7.</p>
	<p>N. 0° 14' W., on the N and S center line of the SW 1/4 of sec. 6.</p>
	<p>Over rolling bench land; desc. over NW slope.</p>
20.46	<p>Point for the SW 1/16 sec. cor. of sec. 6, at intersection with the E-W center line of the SW 1/4.</p>

Subdivision of Section 6,  
T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.

T 17 S R 8 E  
SW 1/16  
S 6  
1982

40.92

The center west 1/16 sec. cor. of sec. 6.

From the center south 1/16 sec. cor. of sec. 6.

N. 89° 46' W. on the E and W center line of the SW 1/4 of sec. 6.

Over rolling bench land.

20.455

The SW 1/16 sec. cor. of sec. 6.

39.15

The S 1/16 sec. cor. of sec. 6 only, W. bdy.

Subdivision of Section 8,  
T. 17 S., R. 8 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of sec. 8 only, on the S. bdy. of sec. 8.

N. 0° 39' W., on the N and S center line of sec. 8.

Over rolling bench land.

45.63

Point for the center 1/4 sec. cor. of sec. 8, at the intersection with the E-W center line.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T 17 S R 8 E  
C 1/4  
S 8  
1982

63.00

Huntington Creek, drains SE.

65.79

Point for the center north 1/16 sec. cor. of sec. 8.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a mound of stone, 4 ft. base, to top of brass cap, mkd.

T 17 S R 8 E  
C  
N 1/16 | S 8  
C  
1982

70.83

Point for the center south-north-north 1/256 sec. cor. of sec. 8. Not monumented.

75.87

Point for the center north-north 1/64 sec. cor. of sec. 8. Not monumented.

Subdivision of Section 8,  
T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS	
80.00	Huntington Creek, drains SW.
83.50	Huntington Creek, drains SE.
85.95	The 1/4 sec. cor. of secs. 5 and 8.
<hr/> <p>From the 1/4 sec. cor. of secs. 8 and 9. S. 89° 50' W., on the E and W center line of sec. 8. Over gentle rolling land.</p>	
20.63	Point for the center east 1/16 sec. cor. of sec. 8.
<p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>	
$C \frac{E \ 1/16}{S \ 8} C$ <p style="text-align: center;">1982</p>	
<p>Cor. is located 3 lks. S of fence cor., fences bear E, W and N. 15° E.</p>	
41.26	The center 1/4 sec. cor. of sec. 8.
61.385	Point for the center west 1/16 sec. cor. of sec. 8.
<p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of brass cap, mkd.</p>	
$C \frac{W \ 1/16}{S \ 8} C$ <p style="text-align: center;">1982</p>	
81.51	The 1/4 sec. cor. of secs. 7 and 8.
<hr/> <p>From the center east 1/16 sec. cor. of sec. 8. N. 0° 23' W., on the N and S center line of the NE 1/4 of sec. 8. Over gentle rolling land.</p>	
14.00	Huntington Creek, flows irregularly E.
16.75	Utah State Highway No. 31, bears E and W.
20.09	Point for the NE 1/16 sec. cor. of sec. 8, at intersection with the E-W center line of the NE 1/4.
<p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of brass cap, mkd.</p>	
$NE \ 1/16$ $S \ 8$ <p style="text-align: center;">1982</p>	

Subdivision of Section 8,  
T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS	
40.18	<p>Cor. is located in N and S fence line, near rim of ledge overlooking Utah State Highway No. 31.</p> <p>The E 1/16 sec. cor. of sec. 8 only, on the N. bdy. of sec. 8.</p>
13.00	<p>From the N 1/16 sec. cor. of secs. 8 and 9.</p> <p>N. 89° 59' W., on the E and W center line of the NE 1/4 of sec. 8.</p> <p>Through apple orchard.</p> <p>Base of ledge; asc. over SE slope.</p>
20.72	The NE 1/16 sec. cor. of sec. 8.
34.10	Utah State Highway No. 31, curves NW and SE.
41.44	The center north 1/16 sec. cor. of sec. 8.
20.06	<p>From the center west 1/16 sec. cor. of sec. 8.</p> <p>N. 0° 21' W., on the N and S center line of the NW 1/4 of sec. 8.</p> <p>Over gentle rolling land.</p> <p>Point for the NW 1/16 sec. cor. of sec. 8, at the intersection with the E-W center line of the NW 1/4.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p>
25.075	<p style="text-align: center;">NW 1/16 S 8 1982</p> <p>Point for the center south-north-northwest 1/256 sec. cor. of sec. 8. Not monumented.</p>
30.09	Point for the center north-northwest 1/64 sec. cor. of sec. 8. Point not monumented.
40.12	The W 1/16 sec. cor. of secs. 5 and 8.
3.50	<p>From the center north 1/16 sec. cor. of sec. 8.</p> <p>S. 89° 33' W., on the E and W center line of the NW 1/4 of sec. 8.</p> <p>Over gentle rolling land.</p> <p>Huntington Creek, drains SE.</p>
5.005	<p>Point for the center east-east-northwest 1/256 sec. cor. of sec. 8.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>

Subdivision of Section 8,  
T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS	
	C E E NW 1/256 S 8 1983
10.01	Point for the center east-northwest 1/64 sec. cor. of sec. 8. Point not monumented.
15.015	Point for the center west-east-northwest 1/256 sec. cor. of sec. 8.  Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.
	C-W-E-NW 1/256 S 8 1983
20.02	The NW 1/16 sec. cor. of sec. 8.
40.04	The N 1/16 sec. cor. of secs. 7 and 8.
	<hr/> From the point for the center east-northwest 1/64 sec. cor. of sec. 8.  N. 0° 30' W., on the N and S center line of the NE 1/4 of the NW 1/4 of sec. 8.  Over gentle rolling land.
5.03	Point for the center south-northeast-northwest 1/256 sec. cor. of sec. 8. Point not monumented.
10.06	Point for the northeast-northwest 1/64 sec. cor. of sec. 8, at the intersection with the E-W center line of the NE 1/4 of the NW 1/4. Point not monumented.
20.12	Point for the east-west 1/64 sec. cor. of secs. 5 and 8.
	<hr/> From the center north-north 1/64 sec. cor. of sec 8.  S. 89° 28' W., on the E and W center line of the NE 1/4 of the NW 1/4 of sec. 8.
3.00	Huntington Creek, drains S.
4.995	Point for the center east-northeast-northwest 1/256 sec. cor. of sec. 8. Point not monumented.
9.99	The point for the northeast-northwest 1/64 sec. cor. of sec. 8.
14.985	Point for the center west-northeast-northwest 1/256 sec. cor. of sec. 8. Point not monumented.
19.98	The point for the center north-northwest 1/64 sec. cor. of sec. 8.

Subdivision of Section 8,  
T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS	
5.035	<p>From the center east-east-northwest 1/256 sec. cor. of sec. 8.</p> <p>N. 0° 35' W., on the N and S center line of the SE 1/4, NE 1/4, NW 1/4 of sec. 8.</p> <p>Point for the southeast-northeast-northwest 1/256 sec. cor. of sec. 8, at the intersection with the E-W center line of the SE 1/4 of the NE 1/4 of the NW 1/4.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">SE-NE-NW 1/256 S 8 1983</p>
10.07	<p>The point for the center east-northeast-northwest 1/256 sec. cor. of sec. 8.</p>
5.00	<p>From a point for the center south-north-north 1/256 sec. cor. of sec. 8.</p> <p>S. 89° 30' W., on the E and W center line of the SE 1/4, NE 1/4, NW 1/4 of sec. 8.</p> <p>The southeast-northeast-northwest 1/256 sec. cor. of sec. 8.</p>
10.00	<p>The point for the center south-northeast-northwest 1/256 sec. cor. of sec. 8.</p>
5.02	<p>From the center west-east-northwest 1/256 sec. cor. of sec. 8.</p> <p>N. 0° 26' W., on the N and S center line of the SW 1/4, NE 1/4, NW 1/4 of sec. 8.</p> <p>Point for the southwest-northeast-northwest 1/256 sec. cor. of sec. 8, at the intersection with the E-W center line of the SW 1/4 of the NE 1/4 of the NW 1/4.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">SW-NE-NW 1/256 S 8 1983</p>
10.04	<p>The point for the center west-northeast-northwest 1/256 sec. cor. of sec. 8.</p> <p>From a point for the center south-northeast-northwest 1/256 sec. cor. of sec. 8.</p> <p>S. 89° 30' W., on the E and W center line of the SW 1/4, NE 1/4, NW 1/4 of sec. 8.</p>

Subdivision of Section 8,  
T. 17 S., R. 8 E., Salt Lake Meridian, Utah

## CHAINS

- 5.00 The southwest-northeast-northwest 1/256 sec. cor. of sec. 8.
- 10.00 The point for the center south-north-northwest 1/256 sec. cor. of sec. 8.
- 
- Subdivision of Section 9,  
T. 17 S., R. 8 E., Salt Lake Meridian, Utah
- 
- From the 1/4 sec. cor. of secs. 9 and 16.  
N. 0° 25' E., on the N and S center line of sec. 9.  
Over rolling bench land.
- 20.225 Point for the center south 1/16 sec. cor. of sec. 9.  
Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.
- C  
|  
S 1/16 | S 9  
|  
C  
1983
- 34.50 Huntington Creek, flows SE.
- 37.00 Utah State Highway No. 31, bears NW and SE.
- 40.45 Point for the center 1/4 sec. cor. of sec. 9, at the intersection with the E-W center line.  
Set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
- T 17 S R 8 E  
C 1/4  
S 9  
1982
- 60.635 Point for the center north 1/16 sec. cor. of sec. 9.  
Set an iron post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.
- C  
|  
N 1/16 | S 9  
|  
C  
1982
- 80.82 The 1/4 sec. cor. of sec. 9 only, on the N. bdy. of sec. 9.
- 
- From the 1/4 sec. cor. of secs. 9 and 10.

Subdivision of Section 9,  
T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS	
	<p>N. 89° 10' W. on the E and W center line of sec. 9. Over rolling bench land.</p>
20.125	<p>Point for the center east 1/16 sec. cor. of sec. 9. Set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	$C \frac{E \ 1/16}{S \ 9} C$ <p style="text-align: center;">1982</p>
40.25	<p>The center 1/4 sec. cor. of sec. 9.</p>
42.50	<p>Utah State Highway No. 31, bears NW and SE.</p>
60.365	<p>Point for the center west 1/16 sec. cor. of sec. 9. Set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	$C \frac{W \ 1/16}{S \ 9} C$ <p style="text-align: center;">1982</p>
71.50	<p>Huntington Creek, flows SE.</p>
80.48	<p>The 1/4 sec. cor. of secs. 8 and 9.</p>
20.03	<p>From the center east 1/16 sec. cor. of sec. 9. N. 0° 26' E., on the N and S center line of the NE 1/4 of sec. 9. Point selected for the witness cor. to the NE 1/16 sec. cor. of sec. 9. Set an iron post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of brass cap, mkd.</p>
	$W \ C$ $NE \ 1/16$ $\uparrow$ $S \ 9$ <p style="text-align: center;">1982</p>
20.23	<p>True point for the NE 1/16 sec. cor. of sec. 9, at the intersection with the E-W center line of the NE 1/4, falls on crumbling broken ledge, and is unsafe to monument.</p>
40.46	<p>The E 1/16 sec. cor. of sec. 9 only, on the N. bdy. of sec. 9.</p>
	<p>From the N 1/16 sec. cor. of secs. 9 and 10. N. 89° 20' W., on the E and W center line of the NE 1/4 of sec. 9. Over rolling bench land.</p>

Subdivision of Section 9,  
T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS	
20.11	True point for the NE 1/16 sec. cor. of sec. 9.
40.22	The center north 1/16 sec. cor. of sec. 9.
<hr/> <p>From the E 1/16 sec. cor. of secs. 9 and 16. N. 0° 10'E., on the N and S center line of the SE 1/4 of sec. 9.</p>	
15.50	Huntington Creek, flows SE.
18.00	Utah State Highway No. 31, bears SE and curves NW.
20.08	Point for the SE 1/16 sec. cor. of sec. 9, at the intersection with the E-W center line of the SE 1/4.
<p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p>	
<p style="text-align: center;">SE 1/16 S 9 1982</p>	
40.16	The center east 1/16 sec. cor. of sec. 9.
<hr/> <p>From the S 1/16 sec. cor. of secs. 9 and 10. N. 89° 35' W., on the E and W center line of the SE 1/4 of sec. 9.</p>	
<p>Over rolling bench land.</p>	
20.205	The SE 1/16 sec. cor. of sec. 9.
24.00	Utah State Highway No. 31, curves NW and SE.
27.50	Huntington Creek, flows SE.
35.50	Dirt road, bears NW and SE.
40.41	The center south 1/16 sec. cor. of sec. 9.
<hr/> <p>From the center west 1/16 sec. cor. of sec. 9. N. 0° 10' E., on the N and S center line of the NW 1/4 of sec. 9. Over cultivated land.</p>	
15.00	Utah State Highway No. 31, curves W and SE.
20.125	Point for the NW 1/16 sec. cor. of sec. 9, at the intersection with the E-W center line of the NW 1/4.
<p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	
<p style="text-align: center;">NW 1/16 S 9 1982</p>	

Subdivision of Section 9,  
T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS	
40.25	The W 1/16 sec. cor. of sec. 9 only, on the N. bdy. of sec. 9.
<hr/> From the center north 1/16 sec. cor. of sec. 9. N. 89° 20' W., on the E and W center line of the NW 1/4 of sec. 9. Over rolling bench land.	
20.215	The NW 1/16 sec. cor. of sec. 9.
20.70	Enter cultivated land.
40.43	The N 1/16 sec. cor. of secs. 8 and 9.
<hr/> <p style="text-align: center;">Subdivision of Section 10, T. 17 S., R. 8 E., Salt Lake Meridian, Utah</p> <hr/>	
From the point for the 1/4 sec. cor. of secs. 10 and 15. N. 0° 13' W., on the N and S center line of sec. 10. Over cultivated land.	
5.50	Utah State Highway No. 31, bears N. 79° W. and S. 79° E.
20.025	Point for the center south 1/16 sec. cor. of sec. 10. Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.
<div style="text-align: center;"> <p style="margin: 0;">C   S 1/16   S 10   C 1982</p> </div>	
40.05	Point for the center 1/4 sec. cor. of sec. 10, at the intersection with the E-W center line. Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.
<div style="text-align: center;"> <p style="margin: 0;">T 17 S R 8 E C 1/4 S 10 1982</p> </div>	
80.46	The 1/4 sec. cor. of sec. 10 only, on the N. bdy. of sec. 10.
<hr/> From the 1/4 sec. cor. of secs. 10 and 11. N. 89° 52' W., on the E and W center line of sec. 10. Over rolling land.	

Subdivision of Section 10,  
T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS	
39.97	The center 1/4 sec. cor. of sec. 10.
79.96	The 1/4 sec. cor. of secs. 9 and 10.
40.05	<p>From the S 1/16 sec. cor. of secs. 10 and 11. N. 89° 44' W., on the E and W center line of the SE 1/4 of sec. 10. Over rolling land.</p>
40.06	<p>From the center south 1/16 sec. cor. of sec. 10. N. 89° 44' W., on the E and W center line of the SW 1/4 of sec. 10. Over rolling land.</p>
40.06	The S 1/16 sec. cor. of secs. 9 and 10.
40.82	<p style="text-align: center;">Subdivision of Section 11, T. 17 S., R. 8 E., Salt Lake Meridian, Utah</p> <p>From the 1/4 sec. cor. of secs. 11 and 14. N. 0° 53' W., on the N and S center line of sec. 11. Over rolling land.</p> <p>Point for the center 1/4 sec. cor. of sec. 11, at the intersection with the E-W center line. Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 17 S R 8 E C 1/4 S 11 1983</p>
60.68	<p>Point for the center north 1/16 sec. cor. of sec. 11. Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">C N 1/16   S 11 C 1983</p>
80.54	<p>The 1/4 sec. cor. of secs. 2 and 11.</p> <p>From the 1/4 sec. cor. of secs. 11 and 12. S. 89° 10' W., on the E and W center line of sec. 11.</p>

Subdivision of Section 11,  
T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS	
	Over gentle rolling land.
20.165	Point for the center east 1/16 sec. cor. of sec. 11.
	Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.
	$C \frac{E \ 1/16}{S \ 11} C$ <p style="text-align: center;">1983</p>
40.33	The center 1/4 sec. cor. of sec. 11.
80.66	The 1/4 sec. cor. of secs. 10 and 11.
	From the center east 1/16 sec. cor. of sec. 11.
	N. 1° 05' W., on the N and S center line of the NE 1/4 of sec. 11.
	Over rolling land.
20.005	Point for the NE 1/16 sec. cor. of sec. 11, at the intersection with the E-W center line of the NE 1/4.
	Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, with aluminum cap mkd.
	$NE \ 1/16$ $S \ 11$ <p style="text-align: center;">1983</p>
40.01	The E 1/16 sec. cor. of secs. 2 and 11.
	From the N 1/16 sec. cor. of secs. 11 and 12.
	N. 88° 45' W. on the E and W center line of the NE 1/4 of sec. 11.
	Over rolling land.
20.08	The NE 1/16 sec. cor. of sec. 11.
40.16	The center north 1/16 sec. cor. of sec. 11.
	<p style="text-align: center;">Subdivision of Section 12, T. 17 S., R. 8 E., Salt Lake Meridian, Utah.</p>
	From the 1/4 sec. cor. of secs. 12 and 13.
	N. 1° 18' W., on the N and S center line of sec. 12.
	Over rolling bench land.
20.31	Point for the center south 1/16 sec. cor. of sec. 12.
	Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.

Subdivision of Section 12,  
T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS

$$\begin{array}{c} \text{C} \\ | \\ \text{S } 1/16 \quad | \quad \text{S } 12 \\ | \\ \text{C} \\ 1983 \end{array}$$

40.62

Point for the center 1/4 sec. cor. of sec. 12, at the intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.

$$\begin{array}{c} \text{T } 17 \text{ S } \text{ R } 8 \text{ E} \\ \text{C } 1/4 \\ \text{S } 12 \\ 1983 \end{array}$$

61.195

Point for the center north 1/16 sec. cor. of sec. 12.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.

$$\begin{array}{c} \text{C} \\ | \\ \text{N } 1/16 \quad | \quad \text{S } 12 \\ | \\ \text{C} \\ 1983 \end{array}$$

81.77

The 1/4 sec. cor. of secs. 1 and 12.

From the 1/4 sec. cor. of secs. 7 and 12, E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., protruding 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1970 resurvey of the W. bdy. of T. 17 S., R. 9 E.

S. 89° 34' W., on the E and W center line of sec. 12.

Over rolling bench land.

40.92

The center 1/4 sec. cor. of sec. 12.

60.65

Point for the center west 1/16 sec. cor. of sec. 12.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.

$$\begin{array}{c} \text{W } 1/16 \\ \text{C } \frac{\text{S } 12}{\text{C}} \\ 1983 \end{array}$$

Cor. is located in fence line, which bears N and S.

80.38

The 1/4 sec. cor. of secs. 11 and 12.

From true point for the W 1/16 sec. cor. of secs. 12 and 13.

Subdivision of Section 12,  
T. 17 S., R. 8 E., Salt Lake Meridian, Utah

## CHAINS

	<p>N. 0° 43' W., on the N and S center line of the SW 1/4 of sec. 12.</p> <p>Over rolling bench land.</p>
20.38	<p>Point for the SW 1/16 sec. cor. of sec. 12, at the intersection with the E-W center line of the SW 1/4.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.</p>
40.76	<p style="text-align: center;">SW 1/16 S 12 1983</p> <p>The center west 1/16 sec. cor. of sec. 12.</p>
19.935	<p>From the center south 1/16 sec. cor. of sec. 12.</p> <p>S. 89° 23' W., on the E and W center line of the SW 1/4 of sec. 12.</p> <p>Over rolling land.</p>
39.87	<p>The SW 1/16 sec. cor. of sec. 12.</p> <p>The S 1/16 sec. cor. of secs. 11 and 12.</p>
40.73	<p>From the center west 1/16 sec. cor. of sec. 12.</p> <p>N. 1° 19' W., on the N and S center line of the NW 1/4 of sec. 12.</p> <p>Over gentle rolling land.</p> <p>The W 1/16 sec. cor. of secs. 1 and 12.</p>
	<p style="text-align: center;">Subdivision of Section 14, T. 17 S., R. 8 E., Salt Lake Meridian, Utah</p>
20.135	<p>From the 1/4 sec. cor. of secs. 14 and 23.</p> <p>N. 0° 11' W., on the N and S center line of sec. 14.</p> <p>Over rolling bench land.</p> <p>Point for the center south 1/16 sec. cor. of sec. 14.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">C   S 1/16   S 14   C 1983</p>

Subdivision of Section 14,  
T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS	
40.27	<p>Point for the center 1/4 sec. cor. of sec. 14, at the intersection with the E-W center line.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 17 S R 8 E C 1/4 S 14 1983</p>
45.00	<p>Huntington Creek, flows NE.</p>
53.00	<p>Utah State Highway No. 31, bears N. 60° W. and S. 60° E.</p>
80.26	<p>The 1/4 sec. cor. of secs. 11 and 14.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 14.</p> <p>S. 89° 40' W., on the E and W center line of sec. 14.</p> <p>Over gentle rolling land.</p>
19.00	<p>Utah State Highway No. 31, bears N. 60° W. and S. 60° E.</p>
20.03	<p>Point for the center east 1/16 sec. cor. of sec. 14.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">E 1/16 C ——— C S 14 1983</p>
40.06	<p>The center 1/4 sec. cor. of sec. 14.</p>
52.00	<p>Huntington Creek, flows NE.</p>
55.00	<p>Huntington Creek, flows S.</p>
70.00	<p>Dirt road, bears S and curves W.</p>
80.51	<p>The 1/4 sec. cor. of secs. 14 and 15.</p> <hr/> <p>From the E 1/16 sec cor. of secs. 14 and 23.</p> <p>N. 0° 21' W., on the N and S center line of the SE 1/4 of sec. 14.</p>
20.135	<p>Point for the SE 1/16 sec cor. of sec. 14, at the intersection with the E-W center line of the SE 1/4.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">SE 1/16 S 14 1983</p>
40.27	<p>The center east 1/16 sec. cor. of sec. 14.</p> <hr/>



Subdivision of Section 15,  
T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS		
40.39 81.14	<p>From the 1/4 sec. cor. of secs. 14 and 15. N. 89° 34' W., on the E and W center line of sec. 15. Over rolling bench land.</p> <p>The center 1/4 sec. cor. of sec. 15.</p> <p>The 1/4 sec. cor. of secs. 15 and 16.</p>	
40.44	<p>From the center north 1/16 sec. cor. of sec. 15. N. 89° 35' W., on the E and W center line of the NW 1/4 of sec. 15. Over rolling bench land.</p> <p>The N 1/16 sec. cor. of secs. 15 and 16.</p>	
<p>Subdivision of Section 23, T. 17 S., R. 8 E., Salt Lake Meridian, Utah</p>		
20.165 40.33	<p>From the 1/4 sec. cor. of secs. 23 and 26. N. 0° 33' W. on the N and S center line of sec. 23.</p> <p>Point for the center south 1/16 sec. cor. of sec. 23. Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>C   S 1/16   S 23   C 1983</p> </div> <p>Point for the center 1/4 sec. cor. of sec. 23, at the intersection with the E-W center line. Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 17 S R 8 E C 1/4 S 23 1983</p> </div>	
60.475	<p>Point for the center north 1/16 sec. cor. of sec. 23. Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>C   N 1/16   S 23   C 1983</p> </div>	

Subdivision of Section 23,  
T. 17 S., R. 8 E., Salt Lake Meridian, Utah

## CHAINS

80.62	The 1/4 sec. cor. of secs. 14 and 23.
	From the 1/4 sec. cor. of secs. 23 and 24. S. 89° 39' W., on the E and W center line of sec. 23. Over gentle rolling land.
20.10	Point for the center east 1/16 sec. cor. of sec. 23. Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.
	$\begin{array}{c} \text{E } 1/16 \\ \text{C } \frac{\text{S } 23}{1983} \text{ C} \end{array}$
40.20	The center 1/4 sec. cor. of sec. 23.
60.355	Point for the center west 1/16 sec. cor. of sec. 23. Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.
	$\begin{array}{c} \text{W } 1/16 \\ \text{C } \frac{\text{S } 23}{1983} \text{ C} \end{array}$
80.51	The 1/4 sec. cor. of secs. 22 and 23.
	From the center east 1/16 sec. cor. of sec. 23. N. 0° 30' W., on the N and S center line of the NE 1/4 of sec. 23. Over gentle rolling land.
20.145	Point for the NE 1/16 sec. cor. of sec. 23, at the intersection with the E-W center line of the NE 1/4. Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.
	$\begin{array}{c} \text{NE } 1/16 \\ \text{S } 23 \\ 1983 \end{array}$
40.29	The E 1/16 sec. cor. of secs. 14 and 23.
	From the N 1/16 sec. cor. of secs. 23 and 24. S. 89° 40' W. on the E and W center line of the NE 1/4 of sec. 23. Over nearly level land.
20.12	The NE 1/16 sec. cor. of sec. 23.
40.24	The center north 1/16 sec. cor. of sec. 23.

Subdivision of Section 23,  
T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS	
20.19	<p>From the E 1/16 sec. cor. of secs. 23 and 26.</p> <p>N. 0° 38' W., on the N and S center line of the SE 1/4 of sec. 23.</p> <p>Over nearly level land.</p> <p>Point for the SE 1/16 sec. cor. of sec. 23, at the intersection with the E-W center line of the SE 1/4.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">SE 1/16 S 23 1983</p>
40.38	<p>The center east 1/16 sec. cor. of sec. 23.</p>
20.13	<p>From the S 1/16 sec. cor. of secs. 23 and 24.</p> <p>S. 89° 43' W., on the E and W center line of the SE 1/4 of sec. 23.</p> <p>Over nearly level land.</p> <p>The SE 1/16 sec. cor. of sec. 23.</p>
40.26	<p>The center south 1/16 sec. cor. of sec. 23.</p>
20.16	<p>From the W 1/16 sec. cor. of secs. 23 and 26.</p> <p>N. 0° 32' W., on the N and S center line of the SW 1/4 of sec. 23.</p> <p>Over gentle rolling land.</p> <p>Point for the SW 1/16 sec. cor. of sec. 23, at the intersection with the E-W center line of the SW 1/4.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">SW 1/16 S 23 1983</p>
40.32	<p>The center west 1/16 sec. cor. of sec. 23.</p>
20.165	<p>From the center south 1/16 sec. cor. of sec. 23.</p> <p>S. 89° 43' W. on the E and W center line of the SW 1/4 of sec. 23.</p> <p>Over nearly level land.</p> <p>The SW 1/16 sec. cor. of sec. 23.</p>
40.33	<p>The S 1/16 sec. cor. of secs. 22 and 23.</p>

Subdivision of Section 23,  
T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS		
20.155	<p>From the center west 1/16 sec. cor. of sec. 23.</p> <p>N. 0° 31' W., on the N and S center line of the NW 1/4 of sec. 23.</p> <p>Over rolling land.</p> <p>Point for the NW 1/16 sec. cor. of sec. 23, at the intersection with the E-W center line of the NW 1/4.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">NW 1/16 S 23 1983</p>	
40.31	<p>The W 1/16 sec. cor. of secs. 14 and 23.</p> <hr/> <p>From the center north 1/16 sec. cor. of sec. 23.</p> <p>S. 89° 39' W., on the E and W center line of the NW 1/4 of sec. 23.</p> <p>Over gentle rolling land.</p>	
20.145	<p>The NW 1/16 sec. cor. of sec. 23.</p>	
40.29	<p>The N 1/16 sec. cor. of secs. 22 and 23.</p>	
<p>Subdivision of Section 26, T. 17 S., R. 8 E., Salt Lake Meridian, Utah</p>		
40.69	<p>From the 1/4 sec. cor. of secs. 26 and 35.</p> <p>N. 1° 08' W., on the N and S center line of sec. 26.</p> <p>Over nearly level land.</p> <p>Point for the center 1/4 sec cor. of sec. 26, at the intersection with the E-W center line.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 17 S R 8 E C 1/4 S 26 1983</p>	
60.935	<p>Cor. is located 3 lks. E of N and S fence line.</p> <p>Point for the center north 1/16 sec. cor. of sec. 26.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p>	

Subdivision of Section 26,  
T. 17 S., R. 8 E., Salt Lake Meridian, Utah

CHAINS	
	<div style="text-align: center;">           C                         N 1/16   S 26                         C            1983         </div>
81.18	The 1/4 sec. cor. of secs. 23 and 26.
	<hr/> From the 1/4 sec. cor. of secs. 25 and 26. S. 89° 46' W., on the E and W center line of sec. 26. Over nearly level land.
20.105	Point for the center east 1/16 sec. cor. of sec. 26. Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.
	<div style="text-align: center;"> <u>E 1/16</u>            S 26            1983         </div>
40.21	The center 1/4 sec. cor. of sec. 26.
80.71	The 1/4 sec. cor. of secs. 26 and 27.
	<hr/> From the center east 1/16 sec. cor. of sec. 26. N. 1° 02' W., on the N and S center line of the NE 1/4 of sec. 26. Over nearly level land.
20.25	Point for the NE 1/16 sec. cor. of sec. 26, at the intersection with the E-W center line of the NE 1/4. Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.
	<div style="text-align: center;">           NE 1/16            S 26            1983         </div> <p>Cor. is located on N edge of dirt road, bears E and W, and in alignment with fence lines projecting N and S.</p>
40.50	The E 1/16 sec. cor. of secs. 23 and 26.
	<hr/> From the N 1/16 sec. cor. of secs. 25 and 26. S. 89° 45' W., on the E and W center line of the NE 1/4 of sec. 26. Over nearly level land.
20.13	The NE 1/16 sec. cor. of sec. 26.
40.26	The center north 1/16 sec. cor. of sec. 26.

Township 17 South, Range 8 East, Salt Lake Meridian, Utah

CHAINS

#### General Description

Township 17 South, Range 8 East, is situated along the west side of State Highway No. 10, with the east boundary of the township being common with the main street of the city of Huntington, Utah. The elevation varies from 5,900 to 7,000 feet above sea level. The soil is mostly loam on the north and east portion and clay on the southwest portion of the township.

The Huntington Creek crosses the township from west to east, and is bordered by agriculture lands on both sides. The principal users of the township are farmers and cattlemen.

Access to the township is by State Highway No. 10 along the east boundary, and State Highway No. 31 from Huntington west through Huntington Canyon.





UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
ORIGINAL

R 608

384

FIELD NOTES

OF THE

CORRECTIVE RESURVEY

OF THE

SECTION LINE BETWEEN SECTIONS 19 AND 20

OF

TOWNSHIP 1 NORTH, RANGE 25 EAST

Of the Salt Lake Meridian,

In the State of Utah

EXECUTED BY

Jerry L. Thomas

Cadastral Surveyor

Under special instructions dated \_\_\_\_\_, 19\_\_\_\_; approved \_\_\_\_\_,

**UNDER SUPPLEMENTAL SPECIAL INSTRUCTIONS DATED AND APPROVED JULY 25, 1985**

\_\_\_\_\_, which provided for the surveys included under ~~U.S. Survey~~ <sup>XXXXXXXXX</sup> Group  
Number 456, and assignment instructions dated July 26, 1985.

Survey commenced July 30, 1985

Survey completed July 30, 1985

385

# INDEX DIAGRAM

Township \_\_\_\_\_, Range \_\_\_\_\_

6	5	4	3	2	1
7	8	9	10	11	12
13	14	15	16	17	18
19	20	21	22	23	24
25	26	27	28	29	30
31	32	33	34	35	36

## Township 1 North, Range 25 East, Salt Lake Meridian, Utah

CHAINS

The following field notes are those of the corrective resurvey of the section line between sections 19 and 20, T. 1 N., R. 25 E., Salt Lake Meridian, Utah.

The corrective resurvey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and Supplemental Special Instructions dated July 25, 1985.

The direction of the lines of this corrective resurvey was determined by hour angle observations on Polaris. The distances were determined by EDM.

The mean magnetic declination as protracted from a U.S. Geological Survey "Magnetic Declination Map of 1980", is  $14\ 3/4^{\circ}$  E.

---

Corrective Resurvey of the Section Line Between Sections 19 and 20, T. 1 N., R. 25 E., Salt Lake Meridian, Utah.

---

Beginning at the cor. of secs. 19, 20, 29, and 30, monumented with an iron post, 2 1/2 ins. diam., protruding 6 ins. above mound of stone, with brass cap mkd. as described in the official record of the 1963 resurvey.

Add the date 1985 on the brass cap.

N.  $9^{\circ} 36'$  W., bet. secs. 19 and 20.

Desc. over steep N slope.

33.52

The 1/4 sec. cor. of secs. 19 and 20, monumented with and aluminum pipe, 30 ins. long, 2 1/2 ins. diam., loosely set in mound of stone. This point was determined from the original bearing trees

A pinon, 14 ins. diam., bears S.  $34^{\circ} 30'$  E., 38 lks. dist., mkd. 1/4.

A pinon, 14 ins. diam., bears S.  $22^{\circ} 10'$  W., 58 lks. dist., mkd. BT.

An iron post, 2 1/2 ins. diam., protruding 6 ins. above mound of stone, and mkd. T1N R25E 1/4 S19 S20 1963, bears N.  $20^{\circ} 08'$  E., 6.131 chs. dist. I remove this iron post.

At the corner point

I reset the aluminum post at the same point, 4 ins. in the ground, in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 1 N R 25 E  
S 19 | S 20  
1/4  
1985  
RLS 4806

---

Corrective Resurvey of the Section Line Between  
Sections 19 and 20, T. 1 N., R. 25 E.,  
Salt Lake Meridian, Utah

CHAINS

42.98

N. 0° 17' W., beginning new measurement.

The cor. of secs. 17, 18, 19, and 20, monumented with an iron post, 2 1/2 ins. diam., protruding 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1963 resurvey.

Add the date 1985 on the brass cap.



UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
ORIGINAL

R608

390

FIELD NOTES  
OF THE

DEPENDENT RESURVEY

OF

A PORTION OF THE WEST BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE PARTIAL SUBDIVISIONAL SURVEY OF SECTIONS 6, 7, 18, AND 19,

TOWNSHIP 13 SOUTH, RANGE 5 EAST

Of the Salt Lake Meridian,

In the State of Utah

EXECUTED BY

JERRY L. THOMAS Supervisory Cadastral Surveyor

Under special instructions dated August 29, 1983, approved August 29, 1983

\_\_\_\_\_, which provided for the surveys included under ~~XXXXXX~~/Group  
Number 639, and assignment instructions dated September 6, 1983.

Survey commenced September 7, 1983

Survey completed November 4, 1983

## INDEX DIAGRAM

Township 13 South, Range 5 East,

4 6 11	12 5	4	8	2	1
3 7 9	10 8	9	10	11	12
3 18 7	8 17	16	15	14	13
2 19 5	6 20	21	22	23	24
30	5 29	28	27	26	25
31	32	33	34	35	36

Subdivision of Section 6 - Page 12  
 Subdivision of Section 7 - Page 13  
 Subdivision of Section 18 - Page 14  
 Subdivision of Section 19 - Page 15

## Township 13 South, Range 5 East, Salt Lake Meridian, Utah

## CHAINS

The following field notes describe the dependent resurvey of a portion of the west boundary, a portion of the subdivisional lines, and the partial subdivisional survey of sections 6, 7, 18, and 19, Township 13 South, Range 5 East, Salt Lake Meridian, Utah.

## History of Surveys

	<u>Surveyed by</u>	<u>Retr. or Resurveyed by</u>	
<u>WEST BOUNDARY</u>			
Portion	Charles Mogo (Cancelled)	1856	
All	A.D. Ferron	1871	
<u>NORTH BOUNDARY</u>			
All	A.D. Ferron	1871	J.C. Clark 1928-29
<u>SUBDIVISION</u>			
Portion	Charles Mogo (Cancelled)	1856	
Portion	A.D. Ferron	1871	
Portion	H.D. Page and J.M. Lentz	1903	

Certain corners were remonumented in 1970 under the remonumentation cooperative agreement between the U.S. Forest Service and the Bureau of Land Management.

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group 639, Utah, dated August 29, 1983.

The directions of lines refer to the true meridians determined by observations of Polaris and direct altitude observations of the sun, projected by sustained angulation throughout the survey.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions, lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic coordinates of the corners of Tps. 12 and 13 S., Rs. 4 and 5 E., and sections 19, 24, 25, and 30, on the east boundary of the township, as determined by satellite methods, are as follows:

Latitude 39° 43' 30.574" N. Longitude 111° 24' 56.531" W.  
Latitude 39° 40' 08.061" N. Longitude 111° 18' 17.620" W.

These corners have been designated as BLM control stations.

The geographic coordinates of sections 19, 20, 29, and 30, as determined by calculations from the BLM control stations, are as follows:

Latitude 39° 40' 02.81" N. Longitude 111° 23' 48.54" W.

Dependent Resurvey of a Portion of the West Boundary,  
T. 13 S., R. 5 E., Salt Lake Meridian, Utah

## CHAINS

The mean magnetic declination as projected from the U.S. Geological Survey Magnetic Declination Map of 1980 is 14° E.

Dependent Resurvey of a Portion of the West Boundary,  
T. 13 S., R. 5 E., Salt Lake Meridian, Utah

(Reestablishment of the Survey Executed by  
A.D. Ferron, Deputy Surveyor in 1971)

Beginning at the cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., at intersection of barbed wire fences extending N, S, E, and W. This is the position of the sec. cor. according to local residents of the area, is harmoniously related to identified original cors., and is accepted as the best available evidence of the original cor. position.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 13 S	
R 4 E	R 5 E
S 24	S 19
S 25	S 30
1983	

N. 0° 25' W., bet. secs. 19 and 24.

39.69 Point for the 1/4 sec. cor. of secs. 19 and 24, at proportionate distance falls in cultivated land; there is no remaining evidence of the original corner.

Cor. point not monumented.

79.38 The cor. of secs. 13, 18, 19, and 24, monumented with a sandstone, 15 x 9 x 8 ins., protruding 8 ins. above ground, plainly mkd. 3 notches on S and N edge, and in a mound of stone.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.

T 13 S	
R 4 E	R 5 E
S 13	S 18
S 24	S 19
1983	

Deposit the mkd. stone alongside the aluminum post.

From this point, fence cor. with fences projecting S and E, bears S. 38° E., 0.36 chs. dist.

Dependent Resurvey of a Portion of the West Boundary,  
T. 13 S., R. 5 E., Salt Lake Meridian, Utah

## CHAINS

- 39.79 N. 0° 23' W., bet. secs. 13 and 18.  
Point for the 1/4 sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.  
Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, surrounded by a mound of stone, with aluminum cap mkd.
- ```

T 13 S
R 4 E R 5 E
  1/4
S 13 | S 18
    |
    1983
  
```
- 79.58 The cor. of secs. 7, 12, 13, and 18, monumented with a broken sandstone, 14 x 10 x 7 ins., firmly set, protruding 6 ins. above ground, and mkd. 4 notches on S and 2 notches on N edge.  
At the corner point  
Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, surrounded by a mound of stone, with aluminum cap mkd.
- ```

T 13 S
R 4 E R 5 E
S 12 | S 7
S 13 | S 18
    |
    1983
  
```
- Deposit the mkd. stone alongside the aluminum post.  
Cor. is set alongside fence cor., with fences extending N, S and W.
- 
- 39.89 N. 0° 28' W. bet. secs. 7 and 12.  
Point for the 1/4 sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.  
Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.
- ```

T 13 S
R 4 E R 5 E
  1/4
S 12 | S 7
    |
    1983
  
```
- From this cor. point, a N-S fence line, bears W, 4 1/2 lks. dist.  
Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W of cor.

Dependent Resurvey of a Portion of the West Boundary,  
T. 13 S., R. 5 E., Salt Lake Meridian, Utah

## CHAINS

79.78

Point for the cor. of secs. 1, 6, 7, and 12, determined longitudinally by fence line bearing N and S, and latitudinally by center of right-of-way fences, bearing W. This position is harmoniously related to existing original cors., and is accepted as the best available evidence of the original corner.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

|        |       |
|--------|-------|
| T 13 S |       |
| R 4 E  | R 5 E |
| S 1    | S 6   |
| S 12   | S 7   |
| 1983   |       |

N. 0° 23' W., bet. secs. 1 and 6.

39.87

Point for the 1/4 sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

|        |       |
|--------|-------|
| T 13 S |       |
| R 4 E  | R 5 E |
| 1/4    |       |
| S 1    | S 6   |
| 1983   |       |

From this cor. point, a N-S fence line bears E, 38 lks. dist.

79.74

The Tp. cor. of Tps. 12 and 13 S., Rs. 4 and 5 E., monumented with a sandstone, 18 x 15 x 6 ins., firmly set, protruding 8 ins. above ground, mkd. 6 notches on N, S, E, and W edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

|        |       |
|--------|-------|
| T 12 S |       |
| R 4 E  | R 5 E |
| S 36   | S 31  |
| S 1    | S 6   |
| T 13 S |       |
| 1983   |       |

Deposit the mkd. stone alongside the aluminum post.

Cor. is located in fence cor., with fences projecting E, W and S.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 13 S., R. 5 E., Salt Lake Meridian, Utah

CHAINS

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 13 S., R. 5 E., Salt Lake Meridian, Utah

(Reestablishment of the Survey Executed by  
A.D. Ferron in 1871, and the Resurvey Executed by  
H.D. Page and J.M. Lentz in 1902)

From the 1/4 sec. cor. of secs. 29 and 30, monumented  
with a sandstone, 18 x 12 x 6 ins., firmly set,  
protruding 8 ins. above ground, and plainly mkd. 1/4 on W  
face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24  
ins. in the ground, with aluminum cap mkd.

```

T 13 S R 5 E
  1/4
  |
S 30 | S 29
  |
  1983

```

Deposit the mkd. stone alongside the aluminum post.

From the cor. point, an old fence line extends N.

N. 60° 09' W., bet. secs. 29 and 30.

39.91

Point for the cor. of secs. 19, 20, 29, and 30, at  
proportionate distance; there is no remaining evidence of  
the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24  
ins. in the ground, with aluminum cap mkd.

```

T 13 S R 5 E
S 19 | S 20
S 30 | S 29
  1983

```

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W  
of cor.

From this point, the cor. of secs. 19, 24, 25, and 30, on  
the E. bdy. of the Tp., bears N. 88° 47.5' E., 392.385  
chs. dist., monumented with an iron post, 2 1/2 ins.  
diam., firmly set, projecting 6 ins. above ground, with  
brass cap, mkd. as described in the official record of  
the remonumentation of certain identified corners  
selected by the U.S. Forest Service in 1970.

The control line was fully retraced and no evidence of  
the intervening cors. was found.

(Reestablishment of the Survey Executed by  
A.D. Ferron in 1817)

N. 89° 54' W., bet. secs. 19 and 30.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 13 S., R. 5 E., Salt Lake Meridian, Utah

| CHAINS |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|--------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 39.19  | <p>Point for the 1/4 sec. cor. of secs. 19 and 30, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 13 S R 5 E<br/>S 19<br/>1/4 <u>S 30</u><br/>1983</p> <p>Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, N of cor.</p>                                                                                       |
| 78.38  | <p>The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., hereinbefore described.</p> <hr/> <p>From the cor. of secs. 19, 20, 29, and 30.</p> <p>N. 1° 28' W., bet. secs. 19 and 20.</p>                                                                                                                                                                                                                                                                                                       |
| 39.80  | <p>Point for the 1/4 sec. cor. of secs. 19 and 20, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 13 S R 5 E<br/>1/4<br/>S 19   S 20<br/>1983</p> <p>Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W of cor.</p> <p>Cor. is located on S slope, approximately 4.50 chs. S of "Dry Creek Canyon" bottom.</p> |
| 59.70  | <p>Point for the N 1/16 sec. cor. of secs. 19 and 20.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.</p> <p style="text-align: center;">T 13 S R 5 E<br/>N 1/16<br/>S 19   S 20<br/>1983</p> <p>Cor. is located on SW slope, 49 1/2 lks. N of E-W fence line.</p>                                                                                                                  |
| 79.60  | <p>Point for the cor. of secs. 17, 18, 19, and 20, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>                                                                                                                                                                                                                                                      |

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 13 S., R. 5 E., Salt Lake Meridian, Utah

CHAINS

|              |
|--------------|
| T 13 S R 5 E |
| S 18   S 17  |
| S 19   S 20  |
| 1983         |

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W  
of cor.

From this cor., the cor. of secs. 14, 15, 22, and 23,  
bears N. 87° 34.3' E., 231.446 chs. dist., determined  
from the remains of an original bearing tree.

An aspen, 14 ins. diam., bears N. 20° W., 15 lks.  
dist., mkd. T13S R5E S15 BT.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24  
ins. in the ground, with aluminum cap mkd.

|              |
|--------------|
| T 13 S R 5 E |
| S 15   S 14  |
| S 22   S 23  |
| 1983         |

from which new bearing trees

An aspen, 6 ins. diam., bears N. 68° E., 32 lks.  
dist., mkd. X BT.

An aspen, 12 ins. diam., bears S. 60° E., 61 1/2  
lks. dist., mkd. T13S R5E S23 BT.

An aspen, 8 ins. diam., bears S. 32° W., 66 lks.  
dist., mkd. T13S R5E S22 BT.

The control line was fully retraced and no evidence of  
the intervening cors. was found.

S. 89° 58' W., bet. secs. 18 and 19.

19.23

Point for the E 1/16 sec. cor. of secs. 18 and 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24  
ins. in the ground, with aluminum cap mkd.

|                |
|----------------|
| T 13 S R 5 E   |
| S 18           |
| E 1/16    S 19 |
| 1983           |

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, N  
of cor.

38.46

Point for the 1/4 sec. cor. of secs. 18 and 19, at  
proportionate distance; there is no remaining evidence of  
the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20  
ins. in the ground, and in a collar of stone, with  
aluminum cap mkd.

|                 |
|-----------------|
| T 13 S R 5 E    |
| S 18            |
| 1/4        S 19 |
| 1983            |

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 13 S., R. 5 E., Salt Lake Meridian, Utah

## CHAINS

- 76.92 Cor. is located on NW slope and in scattered oak brush.  
The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., hereinbefore described.
- 
- (Reestablishment of the Survey Executed by  
A.D. Ferron in 1871 and the Resurvey Executed by  
H.D. Page and J.M. Lentz in 1902)
- 
- 20.005 From the cor. of secs. 17, 18, 19, and 20.  
N. 2° 51' W., bet. secs. 17 and 18.  
Point for the S 1/16 sec. cor. of secs. 17 and 18.  
Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.
- T 13 S R 5 E  
S 1/16  
S 18 | S 17  
1983
- from which bearing trees
- An aspen, 12 ins. diam., bears North, 40 lks. dist., mkd. S17 BT.
- An aspen, 10 ins. diam., bears S. 72° W., 25 1/2 lks. dist., mkd. S18 BT.
- 40.01 Point for the 1/4 sec. cor. of secs. 17 and 18, at proportionate distance; there is no remaining evidence of the original corner.  
Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.
- T 13 S R 5 E  
1/4  
S 18 | S 17  
1983
- 60.015 Cor. is located on W slope, in dense oak brush and near top of mountain ridge.  
Point for the N 1/16 sec. cor. of secs. 17 and 18.  
Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.
- T 13 S R 5 E  
N 1/16  
S 18 | S 17  
1983

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 13 S., R. 5 E., Salt Lake Meridian, Utah

## CHAINS

80.02

Point for the cor. of secs. 7, 8, 17, and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

|              |
|--------------|
| T 13 S R 5 E |
| S 7   S 8    |
| S 18   S 17  |
| 1983         |

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W of cor.

From this cor., the cor. of secs. 8, 9, 16, and 17, bears N. 81° 52' E., 73.82 chs. dist., monumented with a sandstone, 15 x 10 x 8 ins., mkd. 4 notches on E and S edges, firmly set and projecting 6 ins. above ground.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

|              |
|--------------|
| T 13 S R 5 E |
| S 8   S 9    |
| S 17   S 16  |
| 1983         |

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W of cor.

The control line was fully retraced and no evidence of the intervening cors. was found.

(Reestablishment of the Survey Executed by  
A.D. Ferron in 1871)

S. 89° 42' W., bet. secs. 7 and 18.

18.37

Point for the E 1/16 sec. cor. of secs. 7 and 18.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

|               |
|---------------|
| T 13 S R 5 E  |
| S 7           |
| E 1/16   S 18 |
| 1983          |

36.74

Point for the 1/4 sec. cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

|              |
|--------------|
| T 13 S R 5 E |
| S 7          |
| 1/4   S 18   |
| 1983         |

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 13 S., R. 5 E., Salt Lake Meridian, Utah

| CHAINS |                                                                                                                                                                                                                                                                                                         |
|--------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|        | Cor. is located on steep N slope, 8.00 chs. S of Dry Creek.                                                                                                                                                                                                                                             |
| 73.48  | The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., hereinbefore described.                                                                                                                                                                                                                 |
|        | <p>From the cor. of secs. 7, 8, 17, and 18.<br/>N. 10° 04' E., bet. secs. 7 and 8.</p>                                                                                                                                                                                                                  |
| 18.805 | <p>Point selected for the witness cor. to the S 1/16 sec. cor. of secs. 7 and 8.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>                                                                                                         |
|        | <p style="text-align: center;">W C<br/>T 13 S R 5 E<br/>S 1/16<br/>S 7 ↑ S 8<br/>1983</p>                                                                                                                                                                                                               |
| 19.905 | True point for the S 1/16 sec. cor. of secs. 7 and 8, falls in swamp area that is unsuitable for monumentation.                                                                                                                                                                                         |
| 39.81  | <p>Point for the 1/4 sec. cor. of secs. 7 and 8, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p>                             |
|        | <p style="text-align: center;">T 13 S R 5 E<br/>1/4<br/>S 7   S 8<br/>1983</p>                                                                                                                                                                                                                          |
| 59.715 | True point for the N 1/16 sec. cor. of secs. 7 and 8, falls on broken ledge slope and is unsafe to monument.                                                                                                                                                                                            |
| 59.79  | <p>Point selected for the witness cor. to the N 1/16 sec. cor. of secs. 7 and 8.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p>                                                                               |
|        | <p style="text-align: center;">W C<br/>T 13 S R 5 E<br/>N 1/16<br/>S 7 ↓ S 8<br/>1983</p>                                                                                                                                                                                                               |
| 79.62  | <p>Cor. is located on steep S slope of white clay spur.</p> <p>Point for cor. of secs. 5, 6, 7, and 8, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> |

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 13 S., R. 5 E., Salt Lake Meridian, Utah

CHAINS

|              |
|--------------|
| T 13 S R 5 E |
| S 6   S 5    |
| S 7   S 8    |
| 1983         |

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W  
of cor.

From this cor., the cor. of secs. 3, 4, 9, and 10, bears  
N. 85° 44.7' E., 152.019 chs. dist., monumented with a  
limestone, 16 x 14 x 4 ins., plainly mkd. 5 notches on S  
edge and 2 notches on the deteriorated E edge firmly set  
and projecting 5 ins. above ground.

from which the remaining original bearing tree

An aspen, 14 ins. diam., bears N. 80° 45' W.,  
62 1/2 lks. dist., mkd. with illegible scribe  
marks.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24  
ins. in the ground, with aluminum cap mkd.

|              |
|--------------|
| T 13 S R 5 E |
| S 4   S 3    |
| S 9   S 10   |
| 1983         |

from which new bearing trees

An aspen, 14 ins. diam., bears N. 33° E., 23 lks.  
dist., mkd. T13S R5E S3 BT.

An aspen, 10 ins. diam., bears S. 70 3/4° W.,  
68 1/2 lks. dist., mkd. T13S R5E S9 BT.

Deposit the mkd. stone alongside the aluminum post.

The control line was fully retraced and no evidence of  
the intervening cors. was found.

(Reestablishment of the Survey Executed by  
A.D. Ferron in 1871, and the Resurvey Executed by  
H.D. Page and J.M. Lentz in 1902)

S. 89° 50' W., bet. secs. 6 and 7.

37.71

Point for the 1/4 sec. cor. of secs. 6 and 7, at  
proportionate distance; there is no remaining evidence of  
the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24  
ins. in the ground, with aluminum cap mkd.

|              |
|--------------|
| T 13 S R 5 E |
| S 6          |
| 1/4 S 7      |
| 1983         |

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, N  
of cor.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 13 S., R. 5 E., Salt Lake Meridian, Utah

| CHAINS |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|--------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 75.61  | <p>Cor. is located 2 lks. W of rock outcrop.</p> <p>The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., hereinbefore described.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| 40.04  | <p>From the cor. of secs. 5, 6, 7, and 8.</p> <p>N. 2° 04' E., bet. secs. 5 and 6.</p> <p>Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 13 S R 5 E</p> <p>1/4</p> <p>S 6   S 5</p> <p>1983</p> </div> <p>from which a bearing tree</p> <p>An aspen, 5 ins. diam., bears N. 89° E., 26 lks. dist., mkd. T13S R5E 1/4 S5 Bt.</p> <p style="text-align: center;">(Reestablishment of the Survey Executed by<br/>A.D. Ferron in 1871)</p> |
| 79.89  | <p>The cor. of secs. 5, 6, 31, and 32, on the N. bdy., monumented with an iron post, 2 ins. diam. firmly set, protruding 10 ins. above ground, with brass cap, mkd. as described in the official record of the 1929 resurvey of the S. bdy. of T. 12 S., R. 5 E.</p> <p style="text-align: center;">Partial Subdivision Survey of Section 6,<br/>T. 13 S., R. 5 E., Salt Lake Meridian, Utah</p>                                                                                                                                                                                                                                                                              |
| 39.94  | <p>From the 1/4 sec. cor. of secs. 6 and 7.</p> <p>N. 1° 01' E., on the N and S center line of sec. 6.</p> <p>Point for the center 1/4 sec. cor. of sec. 6, at intersection with the E and W center line.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 13 S R 5 E</p> <p>C 1/4 S 6</p> <p>1983</p> </div>                                                                                                                                                                                                                                  |
| 79.82  | <p>The 1/4 sec. cor. of secs. 6 and 31, on the N. bdy., monumented with an iron post, 1 in. diam., firmly set, protruding 10 ins. above ground, with brass cap, mkd. as described in the official record of the 1929 resurvey of the S. bdy. of T. 12 S., R. 5 E.</p>                                                                                                                                                                                                                                                                                                                                                                                                         |

Partial Subdivision Survey of Section 6,  
T. 13 S., R. 5 E. Salt Lake Meridian, Utah


| CHAINS                                                                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <p>38.87</p> <p>77.74</p>                                                                      | <p>From the 1/4 sec. cor. of secs. 5 and 6.</p> <p>S. 89° 45' W. on the E and W center line of sec. 6.</p> <p>The center 1/4 sec. cor. of sec. 6.</p> <p>The 1/4 sec. cor. of secs. 1 and 6, on the W. bdy. of the Tp., hereinbefore described.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <p>Partial Subdivision Survey of Section 7,<br/>T. 13 S., R. 5 E. Salt Lake Meridian, Utah</p> |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <p>39.85</p> <p>59.775</p> <p>79.70</p>                                                        | <p>From the 1/4 sec. cor. of secs. 7 and 18.</p> <p>N. 0° 21' E. on the N and S center line of sec. 7.</p> <p>Point for the center 1/4 sec. cor. of sec. 7. at intersection with the E and W center line.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 13 S R 5 E<br/>C 1/4 S 7<br/>1983</p> <p>Point for the center north 1/16 sec. cor. of sec. 7.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">C<br/>N 1/16   S 7<br/>1983</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.</p> <p>The 1/4 sec. cor. of secs. 6 and 7.</p> |
| <p>37.22</p> <p>74.53</p>                                                                      | <p>From the 1/4 sec. cor. of secs. 7 and 8.</p> <p>S. 89° 46' W., on the E and W center line of sec. 7.</p> <p>The center 1/4 sec. cor. of sec. 7.</p> <p>The 1/4 sec. cor. of secs 7 and 12, on the W. bdy. of the Tp., hereinbefore described.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <p>37.46</p>                                                                                   | <p>From the true point for the N 1/16 sec. cor. of secs. 7 and 8.</p> <p>S. 89° 48' W., on the E and W center line of the NE 1/4 of sec. 7.</p> <p>The center N 1/16 sec. cor. of sec. 7.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |

Partial Subdivision Survey of Section 18,  
T. 13 S., R. 5 E., Salt Lake Meridian, Utah


CHAINS

Partial Subdivision Survey of Section 18,  
T. 13 S., R. 5 E., Salt Lake Meridian, Utah


19.945 From the 1/4 sec. cor. of secs. 18 and 19.  
N. 1° 37' W., on the N and S center line of sec. 18.  
Point for the center south 1/16 sec. cor. of sec. 18.  
Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.



39.89 Cor. is located in slide area on SW slope.  
Point for the center 1/4 sec. cor. of sec. 18, at intersection with the E and W center line.  
Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.




59.835 Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high. W of cor.  
Point for the center north 1/16 sec. cor. of sec. 18.  
Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.



79.78 The 1/4 sec. cor. of secs. 7 and 18.

18.80 From the 1/4 sec. cor. of secs. 17 and 18.  
S. 89° 50' W. on the E and W center line of sec. 18.  
Point for the center east 1/16 sec. cor. of sec. 18.  
Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.



Cor. is located on W slope in scattered oak brush.

Partial Subdivision Survey of Section 18,  
T. 13 S., R. 5 E., Salt Lake Meridian, Utah

| CHAINS                                                                                           |                                                                                                                                                               |
|--------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 37.60                                                                                            | The center 1/4 sec. cor. of sec. 18.                                                                                                                          |
| 75.20                                                                                            | The 1/4 sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp., hereinbefore described.                                                                      |
| <p>Partial Subdivision Survey of Section 19,<br/>T. 13 S., R. 5 E., Salt Lake Meridian, Utah</p> |                                                                                                                                                               |
|                                                                                                  | From the 1/4 sec. cor. of secs. 19 and 30.                                                                                                                    |
|                                                                                                  | N. 0° 57' W., on the N and S center line of sec. 19.                                                                                                          |
| 39.74                                                                                            | Point for the center 1/4 sec. cor. of sec. 19, at intersection with the E and W center line.                                                                  |
|                                                                                                  | Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.                                                           |
|                                                                                                  | <p>T 13 S R 5 E<br/>C 1/4 S 19<br/>1983</p>                                                                                                                   |
|                                                                                                  | Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W of cor.                                                                                             |
| 59.61                                                                                            | Point for the center north 1/16 sec. cor. of sec. 19.                                                                                                         |
|                                                                                                  | Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd. |
|                                                                                                  | <p>C<br/>N 1/16   S 19<br/>1983</p>                                                                                                                           |
|                                                                                                  | Cor. is located on SW slope, 49 1/2 lks. N of E-W fence line.                                                                                                 |
| 79.48                                                                                            | The 1/4 sec. cor. of secs. 18 and 19.                                                                                                                         |
|                                                                                                  | From the 1/4 sec. cor. of secs. 19 and 20.                                                                                                                    |
|                                                                                                  | N. 89° 58' W., on the E and W center line of sec. 19.                                                                                                         |
| 19.415                                                                                           | Point for the center east 1/16 sec. cor. of sec. 19.                                                                                                          |
|                                                                                                  | Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.                                                           |
|                                                                                                  | <p>E 1/16<br/>C S 19 C<br/>1983</p>                                                                                                                           |
| 38.83                                                                                            | The center 1/4 sec. cor. of sec. 19, at intersection with the N and S center line.                                                                            |
| 77.66                                                                                            | The 1/4 sec. cor. of secs. 19 and 24, on the W. bdy. of the Tp., hereinbefore described.                                                                      |

## Township 13 South, Range 5 East, Salt Lake Meridian, Utah

CHAINS

## General Description

The area resurveyed within Township 13 South, Range 5 East, is situated 1/2 mile east of Milburn, Utah. The elevation varies from 6600 ft. to 9000 ft. above sea level. General drainage of this portion of the township is west. There is some ranching along Oak Creek, located in section 19, and some mining activity in section 7. The remaining portion of the area surveyed is used for livestock grazing.

The mean magnetic declination is 14° East.





UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

R608

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF THE

EAST BOUNDARY,

A PORTION OF THE NORTH BOUNDARY,

AND A

PORTION OF THE SUBDIVISIONAL LINES

OF

TOWNSHIP 14 NORTH, RANGE 4 EAST

Of the Salt Lake Meridian,

In the State of Utah

EXECUTED BY

Donald A. Buhler

Cadastral Surveyor

Under special instructions dated June 7, 19 83, approved June 27, 1983.

and Supplemental Special Instructions dated October 25, 1983 and approved

August 3, 1984

, which provided for the surveys included under ~~US Survey~~ Group

Number 634, and assignment instructions dated August 25, 19 83.

Survey commenced August 29, 19 83

Survey completed August 30, 19 84

# INDEX DIAGRAM

Township 14 North, Range 4 East

|    |    |    |    |       |                |
|----|----|----|----|-------|----------------|
| 6  | 5  | 4  | 3  | 2 15  | 7<br>1 6<br>14 |
| 7  | 8  | 9  | 10 | 11 14 | 12 5<br>13     |
| 16 | 17 | 16 | 15 | 14 12 | 18 5<br>12     |
| 19 | 20 | 21 | 22 | 23 11 | 24 5<br>10     |
| 30 | 29 | 28 | 27 | 26 10 | 25 4<br>9      |
| 31 | 32 | 33 | 34 | 35 8  | 36 4           |

## Township 14 North, Range 4 East, Salt Lake Meridian, Utah

CHAINS

The following field notes describe the dependent resurvey of the east boundary, a portion of the north boundary, and a portion of the subdivisional lines of Township 14 North, Range 4 East, Salt Lake Meridian, Utah.

History of SurveysSurveyed byRetr. or Resurveyed bySOUTH BOUNDARY

|     |                                                              |      |                   |              |
|-----|--------------------------------------------------------------|------|-------------------|--------------|
| All | J.H. Martineau                                               | 1881 |                   |              |
| All |                                                              |      | Hanson and Giers  | 1900         |
| All | (Establishment of U.S. Forest Reserve Boundary)              |      | F.E. Joy          | 1904         |
|     | Closing Cor. T. 13 N., Rs. 4-5 E., SE cor. T. 14 N., R. 4 E. |      | A. Nelson         | 1962         |
|     | Several cors. remonumented                                   |      | F.D. Reynolds     | 1968         |
| All |                                                              |      | F. Profaizer, Jr. | concurrently |

EAST BOUNDARY

|     |                            |      |               |      |
|-----|----------------------------|------|---------------|------|
| All | J.H. Martineau             | 1881 |               |      |
| All |                            |      | A.P. Hanson   | 1896 |
|     | Several cors. remonumented |      | A. Nelson     | 1962 |
|     | Several cors. remonumented |      | F.D. Reynolds | 1968 |

NORTH BOUNDARY

|     |                |      |  |  |
|-----|----------------|------|--|--|
| All | J.H. Martineau | 1881 |  |  |
|-----|----------------|------|--|--|

SUBDIVISION

|     |                |      |  |  |
|-----|----------------|------|--|--|
| All | J.H. Martineau | 1881 |  |  |
|-----|----------------|------|--|--|

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, the Special Instructions dated June 7, 1983 and the Supplemental Special Instructions dated October 25, 1983 for Group 634, Utah.

The direction of lines of this survey was determined by hour angle observations on Polaris. The lines were carried forward by sustained angulations, being supplemented by other hour observations on Polaris throughout the progress of the survey.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions, lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the east angle point of sections 31 and 36, on the east boundary of the township as determined from a tie made to U.S. Forest Service triangulation station "SINKER", located in section 5, T. 13 N., R. 4 E., is as follows:

Latitude 41° 54' 33.46" N. Longitude 111° 26' 17.27" W.

The mean magnetic declination as projected from the U.S. Geological Survey Magnetic Declination Map of 1980 is 15° E.

## Township 14 North, Range 4 East, Salt Lake Meridian, Utah

## CHAINS

Detectable Electronically Energized Particles (DEEP-I TM) were used as accessories to certain corner monuments. The DEEP-I is composed of strontium encased in a plastic container, 1 in. diam., 2 1/2 ins. long and are magnetically detectable.

An investigation revealed the existence of an overlap between the east tier of sections in T. 14 N., R. 4 E. and the west tier of sections in T. 14 N., R. 5 E. The W. bdy. of T. 14 N., R. 5 E. of Hanson's resurvey shall be the boundary between T. 14 N., R. 4 E. and T. 14 N., R. 5 E. The found corners pertaining to T. 14 N., R. 4 E., along this boundary now functions as angle points. Closing corners for T. 14 N., R. 4 E. are established along this boundary at intersection of the east-west section lines of the east tier of sections in T. 14 N., R. 4 E.

A dependent resurvey of the east meridional line along with a retracement survey of the remaining lines of the east tier of sections of T. 14 N., R. 4 E. is used to determine the intersect points. All found corners of the retracement survey are buried.

Retracement of the East Boundary,  
T. 14 N., R. 4 E., Salt Lake Meridian, Utah

(Retracement of the Survey Executed by  
J.H. Martineau in 1881)

Beginning at the SE Tp. cor. of T. 14 N., R. 4 E., monumented with a sandstone, 15 x 10 x 9 ins., mkd. 6 notches on the S, E, and W edges and set in a mound of stone. This cor. is buried with a DEEP-I underneath.

from which

The 1/4 sec. cor. of secs. 1 and 36, on the S. bdy. of the Tp., bears S. 89° 03.7' W., 38.923 chs. dist., set and mkd. as described in the concurrent resurvey of T. 13 N., R. 4 E.

N. 0° 09.8' E., along the E. bdy. of sec. 36, T. 14 N., R. 4 E.

39.902 Point for the 1/4 sec. cor. of secs. 31 and 36, on the E. bdy. of the Tp., at proportionate distance; there is no remaining evidence of the original corner.

79.804 Point for the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., at proportionate distance; there is no remaining evidence of the original corner.

N. 0° 09.8' E., along the E. bdy. of sec. 25, T. 14 N. R. 4 E.

39.902 Point for the 1/4 sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp., at proportionate distance; there is no remaining evidence of the original corner.

Retracement of the East Boundary,  
T. 14 N., R. 4 E., Salt Lake Meridian, Utah

| CHAINS |                                                                                                                                                                                                                  |
|--------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 79.804 | Point for the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., at proportionate distance; there is no remaining evidence of the original corner.                                                     |
|        | N. 00 09.8' E., along the E. bdy. of sec. 24, T. 14 N., R. 4 E.                                                                                                                                                  |
| 39.902 | Point for the 1/4 sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp., at proportionate distance; there is no remaining evidence of the original corner.                                                     |
| 79.804 | Point for the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., at proportionate distance; there is no remaining evidence of the original corner.                                                     |
|        | N. 00 09.8' E., along the E. bdy. of sec. 13, T. 14 N., R. 4 E.                                                                                                                                                  |
| 39.902 | Point for the 1/4 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp., at proportionate distance; there is no remaining evidence of the original corner.                                                     |
| 79.804 | Point for the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., at proportionate distance; there is no remaining evidence of the original corner.                                                      |
|        | N. 00 09.8' E., along the E. bdy. of sec. 12, T. 14 N., R. 4 E.                                                                                                                                                  |
| 39.902 | Point for the 1/4 sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp., at proportionate distance; there is no remaining evidence of the original corner.                                                      |
| 79.804 | Point for the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., at proportionate distance; there is no remaining evidence of the original corner.                                                        |
|        | N. 00 09.8' E., along the E. bdy. of sec. 1, T. 14 N., R. 4 E.                                                                                                                                                   |
| 39.902 | The 1/4 sec. cor. of secs. 1 and 6, on the E. bdy. of the Tp., monumented with a limestone, 20 x 16 x 8 ins., plainly mkd. 1/4 on N face, and in a mound of stone. This cor. is buried with a DEEP-I underneath. |
|        | N. 00 14.8' E., beginning new measurement.                                                                                                                                                                       |
| 40.428 | The NE Tp. cor., monumented with a limestone, 16 x 10 x 6 ins., mkd. 6 notches on S and W edges, and a mound of stone. This cor. is buried with a DEEP-I underneath.                                             |
|        | from which                                                                                                                                                                                                       |
|        | The 1/4 sec. cor. of secs. 1 and 36, on the N. bdy. of the Tp., bears N. 89° 53.2' W., 40.023 chs. dist., hereinafter described                                                                                  |
|        | Dependent Resurvey of the East Boundary,<br>T. 14 N., R. 4 E., Salt Lake Meridian, Utah                                                                                                                          |
|        | (Reestablishment of the Survey Executed by J.H. Martineau in 1881 and the Resurvey Executed by A.P. Hanson in 1896)                                                                                              |

Dependent Resurvey of the East Boundary,  
T. 14 N., R. 4 E., Salt Lake Meridian, Utah

| CHAINS |                                                                                                                                                                                                                                                                                                                                                                                                                   |
|--------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|        | <p>From the original closing cor. of T. 13 N., Rs. 4 and 5 E., which now functions as the angle point of sec. 36, T. 14 N., R. 4 E., and sec. 31, T. 14 N., R. 5 E., as described in the concurrent resurvey of T. 13 N., R. 4 E.</p> <p>S. 89° 30.5' E., along the W. bdy. of sec. 36.</p>                                                                                                                       |
| 3.329  | <p>The east angle point of sec. 36, T. 14 N., R. 4 E. and sec. 31, T. 14 N., R. 5 E., described in the concurrent resurvey of T. 13 N., R. 4 E.</p> <hr/> <p>N. 2° 17.1' W., beginning new measurement.</p>                                                                                                                                                                                                       |
| 27.512 | <p>Point for the 1/4 sec. cor. of sec. 36 only, at midpoint latitudinally between closing cors. hereinafter described.</p>                                                                                                                                                                                                                                                                                        |
| 39.777 | <p>Point for the original 1/4 sec. cor. of sec. 36 only, at proportionate distance; there is no remaining evidence of the original cor. Not monumented.</p>                                                                                                                                                                                                                                                       |
| 68.295 | <p>Point for the closing cor. of secs. 25 and 36, hereinafter described.</p> <p>Thence along the E. bdy. of sec. 25 with continuous measurement.</p>                                                                                                                                                                                                                                                              |
| 79.554 | <p>The original cor. of secs. 25 and 36, monumented with an iron post, set, mkd. and described in the remonumentation of T. 14 N., R. 4 E. in 1962. This cor. now functions as an angle point and remark the brass cap as follows:</p> <div style="text-align: center;"> <p>AP<br/>T 14 N R 5 E<br/>S 25   S 30<br/>R 4 E  <br/>1962<br/>84</p> </div> <hr/> <p>N. 0° 02.9' E., beginning new measurement.</p>    |
| 29.003 | <p>Point for the 1/4 sec. cor. of sec. 25 only, at midpoint latitudinally between closing corners, hereinafter described.</p>                                                                                                                                                                                                                                                                                     |
| 39.976 | <p>The original 1/4 sec. cor. of sec. 25 only, monumented with an iron post, set, mkd. and described in the remonumentation of T. 14 N. R. 4 E. in 1968. This cor. now functions as an angle point and remark the brass cap as follows:</p> <div style="text-align: center;"> <p>AP<br/>T 14 N<br/>R 4 E R 5 E<br/>S 25   S 30<br/>1968<br/>84</p> </div> <hr/> <p>N. 0° 03.8' W., beginning new measurement.</p> |
| 29.280 | <p>Point for the closing cor. of secs. 24 and 25, hereinafter described.</p>                                                                                                                                                                                                                                                                                                                                      |

Dependent Resurvey of the East Boundary,  
T. 14 N., R. 4 E., Salt Lake Meridian, Utah

## CHAINS

- Thence along the E. bdy. of sec. 24, with continuous measurement.
- 39.736 Point for the original cor. of secs. 24 and 25 only, at proportionate distance; there is no remaining evidence of the original corner. Not monumented.
- 68.854 Point for the 1/4 sec. cor. of sec. 24 only, at midpoint latitudinally between closing cors., hereinafter described.
- 79.472 The original 1/4 sec. cor. of sec. 24 only, monumented with an iron post, set, mkd. and described in the remonumentation of T. 14 N., R. 4 E., in 1968. This cor. now functions as an angle point and remark the brass cap as follows:
- AP  
T 14 N  
R 4 E R 5 E  
S 24 | S 19  
1968  
84
- 
- N. 0° 02.8' W., beginning new measurement.
- 28.956 Point for the closing cor. of secs. 13 and 24, hereinafter described.
- Thence along the E. bdy. of sec. 13, with continuous measurement.
- 40.790 Point for the original cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner. Not monumented.
- 69.305 Point for the 1/4 sec. cor. of sec. 13 only, at midpoint latitudinally between closing cors., hereinafter described.
- 81.580 Point for the original 1/4 sec. cor. of sec. 13 only, at proportionate distance; there is no remaining evidence of the original corner. Not monumented.
- 109.654 Point for the closing cor. of secs. 12 and 13, hereinafter described.
- Thence along the E. bdy. of sec. 12, with continuous measurement.
- 122.370 The original cor. of secs. 12 and 13 only, monumented with an embedded mound of stone. This is accepted as the best available evidence of the original corner. This corner now functions as an angle point.
- At the corner point
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

Dependent Resurvey of the East Boundary,  
T. 14 N., R. 4 E., Salt Lake Meridian, Utah

| CHAINS | <p style="text-align: center;">T 14 N<br/>R 4 E R 5 E<br/>AP<br/>S 12   S 7<br/>1984</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|--------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|        | <p>N. 0° 28.9' W., beginning new measurement.</p> <p>28.262 Point for the 1/4 sec. cor. of sec. 12 only, at midpoint latitudinally between closing cors., hereinafter described.</p> <p>39.473 The original 1/4 sec. cor. of sec. 12 only, monumented with a limestone, 16 x 12 x 6 ins., plainly mkd. 1/4 on W face and a mound of stone to the W. The cor. now functions as an angle point.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">T 14 N<br/>R 4 E R 5 E<br/>AP<br/>S 12   S 7<br/>1984</p> <p>Deposit the mkd. stone alongside the aluminum post.</p>                                                 |
|        | <p>N. 0° 11.9' E., beginning new measurement.</p> <p>29.767 Point for the closing cor. of secs. 1 and 12, hereinafter described.</p> <p>Thence along the E. bdy. of sec. 1, with continuous measurement.</p> <p>39.170 Point for the original cor. of secs. 1 and 12 only, at proportionate distance; there is no remaining evidence of the original corner. Not monumented.</p> <p>67.855 Point for the 1/4 sec. cor. of sec. 1 only, at midpoint latitudinally between closing cors., hereinafter described.</p> <p>78.340 The original 1/4 sec. cor. of sec. 1 only, monumented with an iron post, set, mkd. and described in the remonumentation of T. 14 N., R. 4 E. in 1968. This cor. now functions as an angle point and remark the brass cap as follows:</p> |

Dependent Resurvey of the East Boundary,  
T. 14 N., R. 4 E., Salt Lake Meridian, Utah

CHAINS

T 14 N  
R 4 E R 5 E  
AP  
S 1 | S 6  
1968  
84

N. 0° 02.0' E., beginning new measurement.

27.607 Point for the closing cor. of secs. 1 and 36, on the N. bdy. of the Tp., hereinafter described.

39.900 The original Tp. cor. of Tps. 14 and 15 N., R. 4 E., monumented with an unmkd. limestone, 18 x 10 x 10 ins., firmly set in a mound of stone. This cor. now functions as an angle point.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 15 N  
R 4 E R 5 E  
AP  
S 36 | S 31  
1984

Deposit the unmkd. stone alongside the aluminum post.

Dependent Resurvey of a Portion of the North Boundary,  
T. 14 N., R. 4 E., Salt Lake Meridian, Utah

From the cor. of secs. 1, 2, 35 and 36, monumented with a limestone, 18 x 14 x 8 ins., plainly mkd. 4 notches on W edge and set in a mound of stone.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.

T 15 N  
S 35 | S 36  
S 2 | S 1  
T 14 N R 4 E  
1984

from which

A spruce, 8 ins. diam., bears N. 21° E.,  
85 lks. dist., scribed X BT.

A spruce, 10 ins. diam., bears N. 62° W.,  
300 lks. dist., scribed X BT.

Deposit the mkd. stone alongside the aluminum post.

Dependent Resurvey of a Portion of the North Boundary,  
T. 14 N., R. 4 E., Salt Lake Meridian, Utah

## CHAINS

N. 88° 15.6' E., bet. secs. 1 and 36.

35.764

Point for the closing cor. of secs. 1 and 36, at intersection with the E bdy. of Tps. 14 and 15 N., R. 4 E.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

|   |      |        |       |  |
|---|------|--------|-------|--|
|   |      | T 15 N |       |  |
|   |      | R 4 E  | R 5 E |  |
| C | S 36 |        | S 6   |  |
| C | S 1  |        | S 6   |  |
|   |      | T 14 N |       |  |
|   |      | 1984   |       |  |

from which

A lodgepole pine, 9 ins. diam., bears N. 81° W., 28.5 lks. dist., scribed X BT.

38.793

The original 1/4 sec. cor. of secs. 1 and 36, monumented with a sandstone, 18 x 12 x 8 ins., mkd. 1/4 on N face, set in a mound of stone. This cor. is buried with a DEEP-I underneath.

from which

A lodgepole pine, 13 ins. diam., bears N. 89° E., 11.6 lks. dist., scribed X BT.

A lodgepole pine, 12 ins. diam., bears N. 58° W., 3.0 lks. dist., scribed X BT S31.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 14 N., R. 4 E., Salt Lake Meridian, Utah

(Reestablishment of the Survey Executed by  
J.H. Martineau in 1881)

From the cor. of secs. 35 and 36, on the S. bdy. of the Tp., set, mkd. and described in the concurrent resurvey of T. 13 N., R. 4 E.

from which

The U.S. Forest Service triangulation station "SINKER 1960" with geographic coordinates Latitude 41° 53' 25.186" N. and Longitude 111° 31' 51.311" W., bears S. 74° 58' 09" W., 352.993 chs. dist., monumented with a bronze tablet cemented in a drill hole in solid rock outcrop, mkd. "SINKER 1960."

N. 0° 22.1' E., bet. secs. 35 and 36.

40.602

The 1/4 sec. cor. of secs. 35 and 36, monumented with an embedded mound of stone. This is accepted as the best available evidence of the original corner.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 14 N., R. 4 E., Salt Lake Meridian, Utah

## CHAINS

At the corner point (center of mound)

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.

|              |      |
|--------------|------|
| T 14 N R 4 E |      |
| 1/4          |      |
| S 35         | S 36 |
| 1983         |      |

N. 0° 41.8' W., beginning new measurement.

42.057

The cor. of secs. 25, 26, 35, and 36, monumented with a sandstone, 16 x 10 x 10. ins., firmly set in a mound of stone, and mkd. 1 notch on S and E edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

|              |      |
|--------------|------|
| T 14 N R 4 E |      |
| S 26         | S 25 |
| S 35         | S 36 |
| 1983         |      |

Deposit the mkd. stone alongside the aluminum post.

39.522

S. 88° 32.1' E., bet. secs. 25 and 36.

Point for the closing cor. of secs. 25 and 36, at intersection with the E. bdy. of the Tp.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.

|             |  |
|-------------|--|
| T 14 N      |  |
| R 4 E R 5 E |  |
| C S 25      |  |
| C S 36      |  |
| 1984        |  |

from which

The point for the cor. of secs. 25, 30, 31, and 36 of the retracement of the E. bdy., bears S. 88° 32.1'E., 41.222 chs. dist., heretofore described.

The control line was fully retraced and no evidence of the intervening cor. was found.

Point for the 1/4 sec. cor. of sec. 36 only, at midpoint between closing cors. on the E. bdy. of sec. 36.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a collar of stone, to top of aluminum cap, mkd.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 14 N., R. 4 E., Salt Lake Meridian, Utah

CHAINS

T 14 N  
R 4 E R 5 E  
1/4 |  
S 36 |  
1984

From this point, the east angle point of secs. 31 and 36,  
on the E. bdy. of sec. 36, heretofore described, bears  
S. 2° 17.1' E., 27.512 chs. dist.

From the cor. of secs. 25, 26, 35, and 36.

N. 0° 13.7' W., bet. secs 25 and 26.

39.012 The 1/4 sec. cor. of secs. 25 and 26, monumented with a  
conglomerate stone, 18 x 10 x 10 ins. firmly set in a  
mound of stone and plainly mkd. 1/4 on W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22  
ins. in the ground, and in a collar of stone, with  
aluminum cap mkd.

T 14 N R 4 E  
1/4  
S 26 | S 25  
1983

Deposit the mkd. stone alongside the aluminum post.

N. 0° 17.7' W., beginning new measurement.

40.236 The cor. of secs. 23, 24, 25, and 26, monumented with a  
sandstone, 16 x 10 x 8 ins., firmly set in a mound of  
stone and mkd. 2 notches on S edge and 1 notch on E edge.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20  
ins. in the ground, and in a collar of stone, with  
aluminum cap mkd.

T 14 N R 4 E  
S 23 | S 24  
S 26 | S 25  
1983

Deposit the mkd. stone alongside the aluminum post.

N. 89° 38.5' E., bet. secs. 24 and 25.

39.426 Point for the closing cor. of secs. 24 and 25, at  
intersection with the E. bdy. of the Tp.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18  
ins. in the ground to bedrock, and in a collar of stone,  
with aluminum cap, mkd.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 14 N., R. 4 E., Salt Lake Meridian, Utah

CHAINS

T 14 N  
R 4 E R 5 E  
C S 24 |  
C S 25 | S 19  
1984

39.726

The 1/4 sec. cor. of secs. 24 and 25, monumented with a sandstone, 18 x 18 x 16 ins., firmly set in a mound of stone and plainly mkd. 1/4 on N face. This cor. is buried with DEEP-I underneath.

Point for the 1/4 sec. cor. of sec. 25 only, at midpoint between closing cors. on the E. bdy. of sec. 25.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 14 N  
R 4 E R 5 E  
1/4 |  
S 25 |  
1984

From this point, the north angle point of sec. 25 and 30, on the E. bdy. of the Tp., heretofore described, bears N. 0° 02.9' E., 10.973 chs. dist.

From the cor. of secs. 23, 24, 25, and 26.

N. 0° 30.8' W., bet. secs. 23 and 24.

40.219

Point for the 1/4 sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 14 N R 4 E  
1/4  
|  
S 23 | S 24  
1983

80.438

The cor. of secs. 13, 14, 23, and 24, monumented with a limestone, 14 x 11 x 10 ins., firmly set in a mound of stone, dimly mkd. 3 notches on S edge and 1 notch on E edge.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.

T 14 N R 4 E  
S 14 | S 13  
S 23 | S 24  
1983

Deposit the mkd. stone alongside the aluminum post.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 14 N., R. 4 E., Salt Lake Meridian, Utah

CHAINS

40.079 S.  $88^{\circ} 30.6'$  E., bet. secs. 13 and 24.  
Point for the closing cor. of secs. 13 and 24, at intersection with the E. bdy. of the Tp.  
Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 4 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

```

      T 14 N
    R 4 E R 5 E
  C   S 13 |
  C   S 24 |   S 18
      1984
  
```

from which

The point for the cor. of secs. 13, 18, 19, and 24 (of the retracement of the E. bdy.), bears S.  $88^{\circ} 30.6'$  E., 42.202 chs. dist., heretofore described.

The control line was fully retraced and no evidence of the intervening cor. was found.

Point for the 1/4 sec. cor. of sec. 24 only, at midpoint between closing cors. on the E. bdy. of sec. 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

```

      T 14 N
    R 4 E R 5 E
      1/4 |
    S 24 |
      1984
  
```

Cor. is located 4 lks. E of broken down fence.

From this point, the angle point of secs. 19 and 24, on the E. bdy. of the Tp., heretofore described, bears N.  $0^{\circ} 03.8'$  W., 10.618 chs. dist.

From the cor. of secs. 13, 14, 23, and 24.

N.  $0^{\circ} 30.8'$  W., bet. secs. 13 and 14.

40.423 The 1/4 sec. cor. of secs. 13 and 14, monumented with a limestone, 24 x 20 x 8 ins. firmly set in a mound of stone and dimly mkd. with a 1.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a mound of stone, 4 1/2 ft. base, to top of aluminum cap, mkd.

```

      T 14 N R 4 E
          1/4
          |
    S 14 | S 13
          |
          1983
  
```

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 14 N., R. 4 E., Salt Lake Meridian, Utah

CHAINS

Deposit the mkd. stone alongside the aluminum post.

N.  $0^{\circ} 00.7'$  E., beginning new measurement.

41.126 The cor. of secs. 11, 12, 13, and 14, monumented with a limestone, 16 x 12 x 6 ins., firmly set in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.

|              |  |
|--------------|--|
| T 14 N R 4 E |  |
| S 11   S 12  |  |
| S 14   S 13  |  |
| 1983         |  |

Deposit the mkd. stone alongside the aluminum post.

Cor. is located on top of spur, bears ESE.

40.397 S.  $87^{\circ} 19.0'$  E., bet. secs. 12 and 13.

Point for the closing cor. of secs. 12 and 13, at intersection with the E. bdy. of the Tp.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

|             |     |  |
|-------------|-----|--|
| T 14 N      |     |  |
| R 4 E R 5 E |     |  |
| C S 12      |     |  |
| C S 13      | S 7 |  |
| 1984        |     |  |

from which

The point for the cor. of secs. 7, 12, 13, and 18, (of the retracement of the E. bdy.) bears S.  $87^{\circ} 19.0'$  E., 42.527 chs. dist., heretofore described.

The control line was fully retraced and no evidence of the intervening cor. was found.

Point for the 1/4 sec. cor. of sec. 13 only, at midpoint between closing cors. on the E. bdy. of sec. 13.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 3 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.

|             |  |
|-------------|--|
| T 14 N      |  |
| R 4 E R 5 E |  |
| 1/4         |  |
| S 13        |  |
| 1984        |  |

From this point, the closing cor. of secs. 12 and 13, on the E. bdy. heretofore described, bears N.  $0^{\circ} 02.8'$  W., 40.349 chs. dist.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 14 N., R. 4 E., Salt Lake Meridian, Utah

## CHAINS

From the cor. of secs. 11, 12, 13, and 14.

N.  $0^{\circ}$  10.5' E., bet. secs. 11 and 12.

41.953

Point for the 1/4 sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

```

T 14 N R 4 E
  1/4
  |
S 11 | S 12
  |
  1984

```

from which

A spruce, 8 ins. diam., bear N.  $73^{\circ}$  E., 18.3 lks. dist., scribed X BT.

A spruce, 16 ins. diam., bear S.  $88^{\circ}$  W., 21.1 lks. dist., scribed T14N R4E S11 1/4 BT.

83.906

The cor. of secs. 1, 2, 11, and 12, monumented with a limestone, 16 x 15 x 8 ins., mkd. 4 notches on S edge and firmly set in a mound of stone.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.

```

T 14 N R 4 E
S 2 | S 1
S 11 | S 12
  1984

```

Deposit the mkd. stone alongside the aluminum post.

S.  $84^{\circ}$  29.6' E., bet. secs. 1 and 12.

40.040

Point for the closing cor. of secs. 1 and 12, at intersection with the E. bdy. of the Tp.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

```

T 14 N
R 4 E R 5 E
C S 1 |
C S 12 | S 6
  1984

```

from which

The point for the cor. of secs. 1, 6, 7, and 12, (of the retracement of the E. bdy.), bears S.  $84^{\circ}$  29.6' E., 43.146 chs. dist., heretofore described.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 14 N., R. 4 E., Salt Lake Meridian, Utah

## CHAINS

The control line was fully retraced and no evidence of the intervening cor. was found.

Point for the 1/4 sec. cor. of sec. 12 only, at midpoint between closing cors. on the E. bdy. of sec. 12.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar stone, to top of aluminum cap, mkd.

T 14 N  
R 4 E R 5 E  
1/4 |  
S 12 |  
1984

From this point, the north angle point of secs. 7 and 12, on the E. bdy. of the Tp., heretofore described, bears N. 0° 28.9' W., 11.211 chs. dist.

Point for the 1/4 sec. cor. of sec. 1 only, at midpoint between the closing cors. on the E. bdy. of sec. 1.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 14 N  
R 4 E R 5 E  
1/4 |  
S 1 |  
1984

From this point, the angle point of secs. 1 and 6, on the E. bdy. of the Tp., heretofore described, bears N. 0° 11.9' E., 10.485 chs. dist.

From the cor. of secs. 1, 2, 11, and 12.

N. 3° 26.8' E., bet. secs. 1 and 2.

35.511

Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.

T 14 N R 4 E  
1/4  
S 2 | S 1  
1984

71.378

The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., heretofore described.

## Township 14 North, Range 4 East, Salt Lake Meridian, Utah

CHAINS

## General Description

The land encompassed in this survey is located approximately 2 miles west of the town of Garden City, Utah. The elevation above sea level varies from 6040 ft. in section 6 of T. 14 N. R. 5 E., to 7640 ft. in section 1 of T. 14 N., R. 4 E.

Generally speaking the terrain is mountainous with deep canyons and rolling hills. The vegetation varies from grassland and sagebrush to thick stands of oak, maple, mountain mahogany, aspen and fir trees.

U.S. Highway No. 89 runs through section 25. There are numerous dirt roads throughout the area.

The principle use of this area is livestock grazing and recreational use. The main development of this area is in sections 6, 19, and 30 of T. 14 N., R. 5 E., where a few residential subdivisions are located. These developments are east of the area surveyed.



CERTIFICATE OF SURVEY

(I) ~~(We)~~, Donald A. Buhler, Cadastral Surveyor, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 7th day of June, 1983, (I) ~~(We)~~ have dependently resurveyed the east boundary, a portion of the north boundary and a portion of the subdivisional lines of T. 14 N., R. 4 E.,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by (me), ~~(XX)~~ and under (my) ~~(XX)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

January 6, 1986 (Date) Donald A. Buhler (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Washington, D.C.

The foregoing field notes of the dependent resurvey of the east boundary, a portion of the north boundary and a portion of the subdivisional lines of T. 14 N., R. 4 E., Salt Lake Meridian, Utah

executed by Donald A. Buhler, Cadastral Surveyor having been critically examined and found correct, are hereby approved.

April 23, 1986 (Date) Glenn B. Hatch Chief Cadastral Surveyor for Utah

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

(Date) Chief Cadastral Surveyor for Utah

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

R608

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF

THE SOUTH AND EAST BOUNDARIES,

A PORTION OF THE SUBDIVISIONAL LINES

AND

THE SURVEY OF THE SUBDIVISION OF SECTIONS 26, 35 AND 36

OF

TOWNSHIP 33 SOUTH, RANGE 4 EAST

Of the Salt Lake Meridian,

In the State of Utah

EXECUTED BY

Ronald K. Baugh Supervisory Cadastral Surveyor

Under special instructions dated April 2, 1984, approved April 4, 1984

\_\_\_\_\_, which provided for the surveys included under ~~XIX SX SXV~~/Group  
Number 650, and assignment instructions dated April 13, 1984

Survey commenced April 17, 1984

Survey completed May 4, 1984

# INDEX DIAGRAM

Township 33 South, Range 4 East,

|    |    |    |    |    |    |
|----|----|----|----|----|----|
| 6  | 5  | 4  | 3  | 2  | 1  |
| 7  | 8  | 9  | 10 | 11 | 12 |
| 18 | 17 | 16 | 15 | 14 | 13 |
| 19 | 20 | 21 | 22 | 23 | 24 |
| 30 | 29 | 28 | 27 | 26 | 25 |
| 31 | 32 | 33 | 34 | 35 | 36 |

Subdivision of Section 26 - Page 11  
 Subdivision of Section 35 - Page 17  
 Subdivision of Section 36 - Page 18

## Township 33 South, Range 4 East, Salt Lake Meridian, Utah

CHAINS

The following field notes describe the dependent resurvey of a portion of the south and east boundaries, and a portion of the subdivisional lines and the subdivision survey of sections 26, 35 and 36 of Township 33 South, Range 4 East, Salt Lake Meridian, Utah.

History of Surveys

|  | <u>Surveyed by</u> | <u>Retr. or Resurveyed by</u> |
|--|--------------------|-------------------------------|
|--|--------------------|-------------------------------|

SOUTH BOUNDARY

|         |             |                         |
|---------|-------------|-------------------------|
| Portion | J.P. Walker | 1904                    |
| Portion |             | Thoma and Johnston 1916 |

EAST BOUNDARY

|         |                    |      |
|---------|--------------------|------|
| Portion | F.T. Roberts       | 1908 |
| Portion | Thoma and Johnston | 1906 |

SUBDIVISION

|         |              |                                 |
|---------|--------------|---------------------------------|
| Portion | F.T. Roberts | 1908                            |
| Portion |              | Thoma, Johnston and Nelson 1917 |
| Portion |              | Elliot Bird 1935                |

Boulder Townsite

|  |         |      |
|--|---------|------|
|  | E. Bird | 1935 |
|--|---------|------|

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, the Special Instructions dated April 2, 1984 for Group 650, Utah.

The direction of lines refer to the true meridian as determined by observations on Polaris and direct altitude observations of the sun, projected by fore- and backsights.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions, lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the southeast corner of the township as determined from a tie made to U.S. Geological Survey triangulation station "NEW HOME BENCH" located in section 33, T. 33 S., R. 4 E., and "BOULDER" located in section 4, T. 34 S., R. 5 E., is as follows:.

Latitude  $37^{\circ} 53' 11.58''$  N. Longitude  $111^{\circ} 24' 16.50''$  W.

The mean magnetic declination as projected from the U.S. Geological Survey Magnetic Declination Map of 1964 is  $15 \frac{1}{2}^{\circ}$  E.

Dependent Resurvey of a Portion of the South Boundary,  
T. 33 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS

Dependent Resurvey of a Portion of the South Boundary,  
T. 33 S., R. 4 E., Salt Lake Meridian, Utah

(Reestablishment of the Survey Executed by  
John P. Walker, Deputy Surveyor, in 1904)

Beginning at the cor. of Tps. 33 and 34 S., Rs. 4 and 5 E., identical with Mile Post No. 38 of the Aquarius Forest Reserve Boundary, monumented with an iron post, 3 ins. diam., firmly set in a mound of stone, with brass cap, mkd. as described in the official record of the 1904 survey of the S. bdy., from which the 1904 bearing trees

A pine, 21 ins. diam., bears S.  $5\frac{3}{4}^{\circ}$  E.,  
234 lks. dist., mkd. T34S R5E S6 BT on open blaze

A juniper, 21 ins. diam., bears N.  $44\frac{1}{4}^{\circ}$  W.,  
52 lks. dist., mkd. T33S R4E S36 BT on open blaze

There is no remaining evidence of the other two bearing trees.

N.  $89^{\circ} 59.2'$  W., bet. secs. 1 and 36.

Over gently rolling land.

20.004 Point for the E  $\frac{1}{16}$  sec. cor. of secs. 1 and 36. Not monumented.

36.80 Improved gravel road, bears N and S.

40.008 The  $\frac{1}{4}$  sec. cor. of secs. 1 and 36, monumented with an iron post,  $2\frac{1}{2}$  ins. diam., firmly set and exposed 4 ins. above the ground, with brass cap mkd.

1967  
1/4 36  
I

HANSON  
ENG.

There is no remaining evidence of the original bearing trees. This corner is accepted as a careful and faithful reestablishment of the position of the original corner and is located in an E and W fence line.

N.  $89^{\circ} 58.4'$  W., beginning new measurement.

Over gently rolling land.

40.020 The cor. of secs. 1, 2, 35, and 36, identical with Mile Post No. 37 of the Aquarius Forest Reserve Boundary, monumented with an iron post, 3 ins. diam., firmly set in a mound of stone, with brass cap, mkd. as described in the official record of the 1904 survey of the S. bdy., from which the 1904 bearing trees

A juniper, 13 ins. diam., bears S.  $58^{\circ}$  E., 121 lks. dist., (record, S.  $61\frac{3}{4}^{\circ}$  E., 116 lks. dist.), mkd. T34S R4E S1 BT on an open blaze.

Dependent Resurvey of a Portion of the South Boundary,  
T. 33 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS

A juniper, 18 ins. diam., bears S. 55° W., 145 lks. dist., (record, S. 51 1/2° E.), mkd. T34S R4E S2 BT on an open blaze.

From this same cor., U.S.G.S. triangulation station "BOULDER" bears S. 88° 41.7' E., 239.935 chs. dist., monumented with a standard brass tablet stamped BOULDER 1953.

S. 89° 58.8' W., bet. secs. 2 and 35.

Over gently rolling land.

39.822 Point for the 1/4 sec. cor. of secs. 2 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 33 S R 4 E  
S 35  
1/4 — S 2  
T 34 S  
1984

Deposit a steel fence post alongside the aluminum post.

57.00 Boulder Creek, 1 1/2 ft. deep, 70 lks. wide, course S.

59.233 Point selected for the witness cor. to the W 1/16 sec. cor. of secs. 2 and 35.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

W C  
T 33 S R 4 E  
S 35  
W 1/16 ← S 2  
T 34 S  
1984

59.733 True point for the W 1/16 sec. cor. of secs. 2 and 35, falls on a ledge. Point unsuitable for monumentation.

79.644 The cor. of secs. 2, 3, 34, and 35, identical with Mile Post No. 36, of the Aquarius Forest Reserve Boundary; monumented with an iron post, .3 ins. diam., firmly set in a mound of stone, with brass cap, mkd. as described in the official record of the 1904 survey of the S. bdy.

from which

U.S.G.S. triangulation station "NEW HOME BENCH" bears N. 70° 28.0' W., 132.557 chs. dist., monumented with a standard brass tablet stamped NEW HOME BENCH 1929.

Dependent Resurvey of a Portion of the East Boundary,  
T. 33 S., R. 4 E., Salt Lake Meridian, Utah

Dependent Resurvey of a Portion of the East Boundary,  
T. 33 S., R. 4 E., Salt Lake Meridian, Utah

| CHAINS |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|--------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|        | <p>(Reestablishment of the Survey Executed by<br/>F.T. Roberts in 1908)</p> <hr/> <p>From the cor. of Tps. 33 and 34 S., Rs. 4 and 5 E.,<br/>hereinbefore described.</p> <p>N. 0° 06.6' E., bet. secs. 31 and 36.</p> <p>Over rolling land.</p>                                                                                                                                                                                                                                                                                              |
| 19.947 | <p>Point for the S 1/16 sec. cor. of secs. 31 and 36.</p> <p>Set an iron post, 13 ins. long, 1 in. diam. 9 ins. in a<br/>drill hole in solid sandstone, with brass cap mkd.</p> <p style="text-align: center;">T 33 S<br/>R 4 E R 5 E<br/>S 1/16<br/>S 36   S 31<br/>1984</p>                                                                                                                                                                                                                                                                |
| 33.00  | <p>Asphalt surfaced road, bears SSE and NNW.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| 39.894 | <p>The 1/4 sec. cor. of secs. 31 and 36, determined from the<br/>only remaining bearing tree</p> <p style="padding-left: 40px;">A pine, 17 ins. diam., bears S. 82° 25' E.,<br/>59 lks. dist., mkd. T33S R5E S31 BT on an open<br/>blaze.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16<br/>ins. in the ground to bedrock, and in a mound of stone, 4<br/>ft. base, to top of aluminum cap, mkd.</p> <p style="text-align: center;">T 33 S<br/>R 4 E R 5 E<br/>1/4<br/>S 36   S 31<br/>1984</p> |
|        | <p>Deposit a steel fence post alongside the aluminum post.</p> <hr/>                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|        | <p>N. 0° 06.0' E., beginning new measurement.</p> <p>Over gently rolling land.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| 10.010 | <p>Point for the south-north 1/64 sec. cor. of secs. 31 and<br/>36.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18<br/>ins. in the ground to bedrock, and in a mound of stone, 3<br/>ft. base, to top of aluminum cap, mkd.</p> <p style="text-align: center;">T 33 S<br/>R 4 E R 5 E<br/>S-N 1/64<br/>S 36   S 31<br/>1984</p>                                                                                                                                                                                             |
| 15.015 | <p>Point for the north-south-north 1/256 sec. cor. of secs.<br/>31 and 36; not monumented.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                               |

Dependent Resurvey of a Portion of the East Boundary,  
T. 33 S., R. 4 E., Salt Lake Meridian, Utah

| CHAINS                                                                                                                                                                                                                                              |                                                                                                                                                                                                                                  |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 20.020                                                                                                                                                                                                                                              | Point for the N 1/16 sec. cor. of secs. 31 and 36; not monumented.                                                                                                                                                               |
| 30.030                                                                                                                                                                                                                                              | Point for the north-north 1/64 sec. cor. of secs. 31 and 36; not monumented.                                                                                                                                                     |
| 40.040                                                                                                                                                                                                                                              | The cor. of secs. 25, 30, 31, and 36, monumented with an iron post, 2 ins. diam., firmly set n a mound of stone, with brass cap, mkd. as described in the official record of the 1935 resurvey of the Townsite of Boulder, Utah. |
| <p>Dependent Resurvey of a Portion of the Subdivisional<br/>Lines, T. 33 S., R. 4 E., Salt Lake Meridian, Utah</p>                                                                                                                                  |                                                                                                                                                                                                                                  |
| <p>(Reestablishment of the Survey Executed by F.T. Roberts<br/>in 1908 and the Resurvey Executed by Thoma and Johnston<br/>in 1917 and E. Bird in 1935)</p>                                                                                         |                                                                                                                                                                                                                                  |
| <p>From the cor. of secs. 1, 2, 35, and 36, on the S. bdy.<br/>of the Tp., hereinbefore described.</p>                                                                                                                                              |                                                                                                                                                                                                                                  |
| <p>N. 0° 03.5' W., bet. secs. 35 and 36.</p>                                                                                                                                                                                                        |                                                                                                                                                                                                                                  |
| <p>Over gently rolling land.</p>                                                                                                                                                                                                                    |                                                                                                                                                                                                                                  |
| 39.993                                                                                                                                                                                                                                              | <p>The 1/4 sec. cor. of secs. 35 and 36, monumented with a<br/>volcanic stone, 20 x 16 x 9 ins., firmly set in a mound<br/>of stone, mkd. 1/4 on W face.</p>                                                                     |
| <p>There is no remaining evidence of the original bearing<br/>tree.</p>                                                                                                                                                                             |                                                                                                                                                                                                                                  |
| <p>At the corner point</p>                                                                                                                                                                                                                          |                                                                                                                                                                                                                                  |
| <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24<br/>ins. in the ground, with aluminum cap mkd.</p>                                                                                                                                      |                                                                                                                                                                                                                                  |
| <p>T 33 S R 4 E<br/>1/4<br/>S 35   S 36<br/>1984</p>                                                                                                                                                                                                |                                                                                                                                                                                                                                  |
| <p>Deposit the mkd. stone alongside the aluminum post.</p>                                                                                                                                                                                          |                                                                                                                                                                                                                                  |
| <p>N. 0° 01.2' E., beginning new measurement.</p>                                                                                                                                                                                                   |                                                                                                                                                                                                                                  |
| <p>Over gently rolling land.</p>                                                                                                                                                                                                                    |                                                                                                                                                                                                                                  |
| 39.987                                                                                                                                                                                                                                              | <p>Point for the cor. of secs. 25, 26, 35, and 36, at<br/>proportionate distance; falls in the S edge of asphalt<br/>surfaced road, bearing E and W; there is no remaining<br/>evidence of the original corner.</p>              |
| <p>Drive a nail, 6 ins. long, flush with the surface of the<br/>road, with a cross (X) mkd. on top.</p>                                                                                                                                             |                                                                                                                                                                                                                                  |
| <p>from which</p>                                                                                                                                                                                                                                   |                                                                                                                                                                                                                                  |
| <p>An aluminum post, 30 ins. long, 2 1/2 ins. diam.,<br/>set 24 ins. in the ground for a reference<br/>monument, bears S. 31° 47' W., 62.3 lks. dist.,<br/>with aluminum cap mkd. RM T33S R4E S35 1984 and<br/>an arrow pointing to the corner.</p> |                                                                                                                                                                                                                                  |

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 33 S., R. 4 E., Salt Lake Meridian, Utah

| CHAINS      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |  |              |  |      |             |      |  |      |
|-------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--------------|--|------|-------------|------|--|------|
|             | <p>An aluminum post, 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 50° 27' W., 39 lks. dist., with aluminum cap mkd. RM T33S R4E S26 1984 and an arrow pointing to the corner.</p> <p>From this same cor., the S 1/16 sec. cor. of sec. 26 only, identical to angle point No. 8 of the Boulder Townsite, monumented with an iron post, 1 in. diam., firmly set and exposed 12 ins. above the ground, with brass cap, mkd. as described in the official record of the 1935 survey of the Boulder Townsite, bears N. 0° 01.1' W., 19.478 chs. dist.</p> |  |              |  |      |             |      |  |      |
|             | <p>From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89° 59.3' W., bet. secs. 25 and 36.</p> <p>Over gently rolling land.</p>                                                                                                                                                                                                                                                                                                                                                                                                                  |  |              |  |      |             |      |  |      |
| 10.016      | Point for the E-E 1/64 sec. cor. of secs. 25 and 36; not monumented.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |  |              |  |      |             |      |  |      |
| 15.024      | Point for the W-E-E 1/256 sec. cor. of secs. 25 and 36.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |  |              |  |      |             |      |  |      |
|             | Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |  |              |  |      |             |      |  |      |
|             | <table border="0"> <tr><td></td><td>T 33 S R 4 E</td></tr> <tr><td></td><td>  S 25</td></tr> <tr><td>W-E-E 1/256</td><td>  S 36</td></tr> <tr><td></td><td>1984</td></tr> </table>                                                                                                                                                                                                                                                                                                                                                                                                                   |  | T 33 S R 4 E |  | S 25 | W-E-E 1/256 | S 36 |  | 1984 |
|             | T 33 S R 4 E                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |  |              |  |      |             |      |  |      |
|             | S 25                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |  |              |  |      |             |      |  |      |
| W-E-E 1/256 | S 36                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |  |              |  |      |             |      |  |      |
|             | 1984                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |  |              |  |      |             |      |  |      |
| 20.032      | Point for the E 1/16 sec. cor. of secs. 25 and 36.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |  |              |  |      |             |      |  |      |
|             | Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |  |              |  |      |             |      |  |      |
|             | <table border="0"> <tr><td></td><td>T 33 S R 4 E</td></tr> <tr><td></td><td>  S 25</td></tr> <tr><td>E 1/16</td><td>  S 36</td></tr> <tr><td></td><td>1984</td></tr> </table>                                                                                                                                                                                                                                                                                                                                                                                                                        |  | T 33 S R 4 E |  | S 25 | E 1/16      | S 36 |  | 1984 |
|             | T 33 S R 4 E                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |  |              |  |      |             |      |  |      |
|             | S 25                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |  |              |  |      |             |      |  |      |
| E 1/16      | S 36                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |  |              |  |      |             |      |  |      |
|             | 1984                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |  |              |  |      |             |      |  |      |
| 27.00       | Asphalt surfaced road on curve, bears W and SE.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |  |              |  |      |             |      |  |      |
| 35.056      | Point for the W-W-E 1/256 sec. cor. of secs. 25 and 36, falls in an asphalt surfaced road bearing E and W.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |  |              |  |      |             |      |  |      |
|             | Drive a nail, 6 ins. long, flush with the surface of the road, with a cross (X) mkd. on top.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |  |              |  |      |             |      |  |      |
|             | from which                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |  |              |  |      |             |      |  |      |
|             | Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument bears N. 53° 28' E., 69.3 lks. dist., with aluminum cap mkd. RM W-W-E 1/256 S25 1984 and an arrow pointing to the corner.                                                                                                                                                                                                                                                                                                                                                                  |  |              |  |      |             |      |  |      |
|             | Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument bears S. 36° 20' E., 57.0 lks. dist., with aluminum cap mkd. RM W-W-E 1/256 S36 1984 and an arrow pointing to the corner                                                                                                                                                                                                                                                                                                                                                                   |  |              |  |      |             |      |  |      |

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 33 S., R. 4 E., Salt Lake Meridian, Utah

| CHAINS                                                                                                                                                                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 40.064                                                                                                                                                                                   | <p>The 1/4 sec. cor. of secs. 25 and 36, monumented with a rebar, 1/2 in. diam., set 3 ins. below an asphalt surfaced road, bearing E and W, and is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p> <p>Set a (T) iron, 10 ins. long, alongside the rebar 3" below the surface of asphalt road.</p> <p>from which</p> <p style="padding-left: 40px;">An aluminum post, 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 44° 44' E., 65.4 lks. dist., with aluminum cap mkd. RM T33S R4E S25 1984 and an arrow pointing to the corner.</p> <p style="padding-left: 40px;">An aluminum post, 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 45° 20' E., 46.2 lks. dist., with aluminum cap mkd. RM T33S R4E S36 1984 and an arrow pointing to the corner.</p> <p style="text-align: center;">—————</p> <p>N. 89° 54.8' W., beginning new measurement.</p> <p>Over gently rolling land.</p> |
| 15.00                                                                                                                                                                                    | <p>Intersection of gravel road, bears N and S, and asphalt surfaced road, bears E and W.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| 40.126                                                                                                                                                                                   | <p>The cor. of secs. 25, 26, 35, and 36.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <p>(Reestablishment of the Survey Executed by<br/>F.T. Roberts in 1908 and the Resurvey Executed by<br/>Thoma, Johnston and Nelson in 1917)</p> <p style="text-align: center;">—————</p> |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| 20.003                                                                                                                                                                                   | <p>From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0° 01.0' E., bet. secs. 34 and 35.</p> <p>Over gently rolling land.</p> <p>Point for the S 1/16 sec. cor. of secs. 34 and 35.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| 40.006                                                                                                                                                                                   | <p style="text-align: center;">S 1/16<br/>S 34   S 35<br/>1984</p> <p>The 1/4 sec. cor. of sec. 34 and 35, monumented with a rebar in a mound of stone. This position is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |

Dependent Resurvey of a Portion of the Subdivisional  
 Lines, T. 33 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.

T 33 S R 4 E  
 1/4  
 S 34 | S 35  
 1984

N. 0° 01.0' E., beginning new measurement.

Over gently rolling land.

13.75 Utah State Highway No. 12 (approximate), bears NE and SW.

40.005 The cor. of secs. 26, 27, 34, and 35, monumented with a sandstone, 20 x 18 x 10 ins., firmly set in a mound of stone, mkd. 2 notches on S and E edges, from which the 1909 bearing trees

A dead pinon, 14 ins. diam., bears N. 57° 22' E., 58 lks. dist., with illegible scribing visible on open blaze.

A dead pinon, 14 ins. diam., bears S. 67° 04' E., 27 lks. dist., with illegible scribing visible on open blaze.

A pinon, 11 ins. diam., bears S. 15° 30' W., 41 lks. dist., with illegible scribing visible on open blaze.

There is no remaining evidence of the NW bearing tree

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.

T 33 S R 4 E  
 S 27 | S 26  
 S 34 | S 35  
 1984

Deposit the mkd. stone alongside the aluminum post.

(Reestablishment of the Survey Executed by F.T. Roberts in 1908 and the Resurvey Executed by E. Bird in 1935)

From the cor. of secs. 25, 26, 35, and 36.

N. 89° 59.9' W., bet. secs. 26 and 35.

Over gently rolling to rolling land.

39.792 Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate distance; falls in asphalt surfaced road, Utah State Highway No. 12, bearing E and W. There is no remaining evidence of the original corner.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 33 S., R. 4 E., Salt Lake Meridian, Utah

CHAINS

- Set a nail, 6 ins. long, 2 ins. below the surface of road, from which
- An aluminum post, 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 48° 05' W., 86 lks. dist., with aluminum cap mkd. RM 1/4 S35 1984 and an arrow pointing to the corner.
- An aluminum post, 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 40° 42' E., 109.4 lks. dist., with aluminum cap mkd. RM 1/4 S26 1984 and an arrow pointing to the corner.
- 57.00 Boulder Creek, 40 lks. wide, 2 ft. deep, course S.
- 59.688 Point for the W 1/16 sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original corner.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with aluminum cap mkd.
- T 33 S R 4 E  
S 26  
W 1/16 S 35  
1984
- Deposit a steel fence post alongside the the aluminum post.
- Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor. Over mountainous land.
- 62.50 Gravel road, bears NNW and SSE.
- 64.662 Point for the E-W-W 1/256 sec. cor. of secs. 26 and 35; not monumented.
- 69.636 Point for the W-W 1/64 sec. cor. of secs. 26 and 35; not monumented.
- 79.584 The cor. of secs. 26, 27, 34, and 35.
- 
- (Reestablishment of the Survey Executed by F.T. Roberts in 1908 and the Resurvey Executed by Thoma, Johnston and Nelson in 1917 and E. Bird in 1935)
- N. 0° 12.5' W., bet. secs. 26 and 27.
- Over mountainous land.
- 9.971 Point for the S-S 1/64 sec. cor. of secs. 26 and 27.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., on solid sandstone over a cross (X), and in a mound of stone, 5 ft. base, to top of aluminum cap, mkd.
- T 33 S R 4 E  
S-S 1/64  
S 27 | S 26  
1984

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 33 S., R. 4 E., Salt Lake Meridian, Utah

| CHAINS |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|--------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 19.942 | <p>Point for the S 1/16 sec. cor. of secs. 26 and 27.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">T 33 S R 4 E<br/>S 1/16<br/>S 27   S 26<br/>1984</p>                                                                                                                                                                                                                                                                                                                                                    |
| 29.913 | <p>Point for the N-S 1/64 sec. cor. of secs. 26 and 27: not monumented.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| 39.884 | <p>The 1/4 sec. cor. of secs. 26 and 27, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, with brass cap, mkd. as described in the official record of the 1935 resurvey.</p> <p>from which the 1935 bearing trees</p> <p style="padding-left: 40px;">A pinon, 8 ins. diam., bears N. 27° E., 76 lks. dist., mkd. 1/4 S26 BT on an open blaze.</p> <p style="padding-left: 40px;">A pinon, 20 ins. diam., bears N. 62 1/2° W., 48 lks. dist., mkd. 1/4 S27 BT on an open blaze.</p> <p style="text-align: center;">_____</p> <p>N. 0° 08.8' W., beginning new measurement.</p> <p>Over mountainous land.</p> |
| 2.006  | <p>The angle point for secs. 26 and 27, monumented with a sandstone, 18 x 10 x 10 ins., firmly set in a mound of stone, mkd. as described in the official record of the 1935 resurvey of a portion of the subdivisional lines.</p> <p style="text-align: center;">_____</p> <p>N. 0° 49.9' W., beginning new measurement.</p>                                                                                                                                                                                                                                                                                                         |
| 7.756  | <p>Point for the S-N 1/64 sec. cor. of sec. 26 only.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., on solid sandstone over a cross (X), and in a mound of stone, 5 ft. base, to top of aluminum cap, mkd.</p> <p style="text-align: center;">T 33 S R 4 E<br/>S-N 1/64<br/>  S 26<br/>1984</p>                                                                                                                                                                                                                                                                                                                         |
| 17.518 | <p>Point for the N 1/16 sec. cor. of sec. 26 only.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., on solid sandstone over a cross (X), and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.</p> <p style="text-align: center;">T 33 S R 4 E<br/>  N 1/16<br/>  S 26<br/>1984</p>                                                                                                                                                                                                                                                                                                                           |

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 33 S., R. 4 E., Salt Lake Meridian, Utah

| CHAINS |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|--------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 37.042 | <p>The cor. of secs. 23 and 26 only, monumented with an iron post, 2 ins. diam., firmly set projecting 18 ins. above the ground, with brass cap, mkd. as described in the official record of the 1935 resurvey of the Boulder Townsite survey, from which the 1935 bearing tree</p> <p style="padding-left: 40px;">A pinon, 20 ins. diam., bears S. 18 3/4° E., 58 lks. dist. (record, S. 19° 30' E., 59 lks. dist.), mkd. with illegible scribing on partially healed blaze.</p> <p>There is no remaining evidence of the other bearing tree.</p> |
|        | <p>(Reestablishment of the Survey Executed by F.T. Roberts in 1908 and the Resurvey Executed by E. Bird in 1935)</p>                                                                                                                                                                                                                                                                                                                                                                                                                               |
|        | <p>From the 1/4 sec. cor. of secs. 23 and 26, monumented with an iron post, 1 in. diam., firmly set and exposed 12 ins. above the ground, with brass cap, mkd. as described in the official record of the 1935 resurvey of the Boulder Townsite survey.</p>                                                                                                                                                                                                                                                                                        |
|        | <p>S. 89° 54.1' W., bet. secs. 23 and 26.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| 14.943 | <p>Point for the W-E-W 1/256 sec. cor. of secs. 23 and 26.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p>                                                                                                                                                                                                                                                                                                                                                |
|        | <p style="text-align: center;">T 33 S R 4 E<br/>S 23<br/>W-E-W 1/256    S 26<br/>1984</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| 16.70  | <p>Boulder Creek, 50 lks. wide, 2 ft. deep, course S; enter rolling to mountainous land.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| 19.924 | <p>Point for the W 1/16 sec. cor. of secs. 23 and 26.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 5 ft. base, to top of aluminum cap, mkd.</p>                                                                                                                                                                                                                                                                                                                         |
|        | <p style="text-align: center;">T 33 S R 4 E<br/>S 23<br/>W 1/16        S 26<br/>1984</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| 39.848 | <p>The cor. of secs. 23 and 26 only.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|        | <p style="text-align: center;">Dependent Resurvey of a Portion of the<br/>Subdivision of Section 26,<br/>T. 33 S., R. 4 E., Salt Lake Meridian, Utah</p>                                                                                                                                                                                                                                                                                                                                                                                           |
|        | <p style="text-align: center;">(Reestablishment of the Survey Executed by<br/>E. Bird in 1935)</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                 |

Dependent Resurvey of a Portion of the Subdivision  
of Section 26,  
T. 33 S., R. 4 E., Salt Lake Meridian, Utah

| CHAINS |                                                                                                                                                                                                               |
|--------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|        | From the center 1/4 sec. cor. of sec. 26, monumented with an iron post, 1 in. diam., firmly set and exposed 2 ins. above the ground, with brass cap, mkd. as described in official record of the 1935 survey. |
|        | N. 89° 20.5' W., along the E-W center line of sec. 26.                                                                                                                                                        |
|        | Over gently rolling land.                                                                                                                                                                                     |
| 6.50   | Boulder Creek, course S.                                                                                                                                                                                      |
| 19.816 | Point for the center W 1/16 sec. cor. of sec. 26. Not monumented.                                                                                                                                             |
| 29.724 | Point for the center W-W 1/64 sec. cor. of sec. 26.                                                                                                                                                           |
|        | Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.                                                                                                           |
|        | C-W-W 1/64                                                                                                                                                                                                    |
|        | S 26                                                                                                                                                                                                          |
|        | 1984                                                                                                                                                                                                          |
| 39.632 | The 1/4 sec. cor. of secs. 26 and 27, hereinbefore described.                                                                                                                                                 |
|        | Subdivisional Survey of a Portion of Section 26,<br>T. 33 S., R. 4 E., Salt Lake Meridian, Utah                                                                                                               |
|        | From the W 1/16 sec. cor. of secs. 26 and 35.                                                                                                                                                                 |
|        | N. 0° 19.5' W., along the N-S center line of the SW 1/4 of sec. 26.                                                                                                                                           |
| 4.957  | Point for the center S-S-SW 1/256 sec. cor. of the SW 1/4 of sec. 26.                                                                                                                                         |
|        | Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.                                                                                                           |
|        | C-S-S-SW 1/256                                                                                                                                                                                                |
|        | S 26                                                                                                                                                                                                          |
|        | 1984                                                                                                                                                                                                          |
| 9.914  | Point for the center S-SW 1/64 sec. cor. of sec. 26. Not monumented.                                                                                                                                          |
| 19.828 | Point for the SW 1/16 sec. cor. of sec. 26, at intersection with the E-W center line of the SW 1/4. Not monumented.                                                                                           |
| 24.785 | Point for the center S-N-SW 1/256 sec. cor. of sec. 26. Not monumented.                                                                                                                                       |
| 29.742 | Point for the center N-SW 1/64 sec. cor. of sec. 26. Not monumented.                                                                                                                                          |
| 39.656 | Point for the center west 1/16 sec. cor. of sec. 26.                                                                                                                                                          |

Subdivisional Survey of a Portion of Section 26,  
T. 33 S., R. 4 E., Salt Lake Meridian, Utah

| CHAINS |                                                                                                                                                                                                                                                                                                             |
|--------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|        | <p>From the center south 1/16 sec. cor. of sec. 26, monumented with an iron post, 1 in. diam., firmly set and exposed 2 ins. above the ground, with brass cap, mkd. as described in the official record of the 1935 survey.</p> <p>N. 89° 40.3' W., along the E-W center line of the SW 1/4 of sec. 26.</p> |
| 10.75  | Boulder Creek, course S.                                                                                                                                                                                                                                                                                    |
| 19.856 | Point for the SW 1/16 sec. cor. of sec. 26.                                                                                                                                                                                                                                                                 |
| 24.820 | Point for the center E-W-SW 1/256 sec. cor. of sec. 26.                                                                                                                                                                                                                                                     |
|        | <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">C-E-W-SW<br/>1/256<br/>S 26<br/>1984</p>                                                                                                                          |
| 29.784 | Point for the center W-SW 1/64 sec. cor. of sec. 26. Not monumented.                                                                                                                                                                                                                                        |
| 39.712 | Point for the S 1/16 sec. cor. of secs. 26 and 27.                                                                                                                                                                                                                                                          |
|        | <p>From the point for the W-W 1/64 sec. cor. of secs. 26 and 35.</p> <p>N. 0° 16.0' W., along the N-S center line of the SW 1/4 of sec. 26.</p>                                                                                                                                                             |
| 4.971  | Point for the center S-SW-SW 1/256 sec. cor. of sec. 26. Not monumented.                                                                                                                                                                                                                                    |
| 9.942  | Point for the SW-SW 1/64 sec. cor., at intersection with the E-W center line of the SW 1/4 of the SW 1/4 of sec. 26. Not monumented.                                                                                                                                                                        |
| 19.884 | Point for the center W-SW 1/64 sec. cor. of sec. 26.                                                                                                                                                                                                                                                        |
|        | <p>From the point for the center S-SW 1/64 sec. cor. of sec. 26.</p> <p>N. 89° 50.1' W., along the E-W center line of the SW 1/4 of the SW 1/4 of sec. 26.</p>                                                                                                                                              |
| 4.969  | Point for the center E-SW-SW 1/256 sec. cor. of sec. 26. Not monumented.                                                                                                                                                                                                                                    |
| 9.938  | Point for the SW-SW 1/64 sec. cor. of sec. 26.                                                                                                                                                                                                                                                              |
| 19.876 | The S-S 1/64 sec. cor. of secs. 26 and 27.                                                                                                                                                                                                                                                                  |
|        | <p>From the point for the center E-SW-SW 1/256 sec. cor. of sec. 26.</p> <p>N. 0° 17.7' W., along the N-S center line of the NE 1/4 of the SW 1/4 of the SW 1/4 of sec. 26.</p>                                                                                                                             |
| 9.928  | The center E-W-SW 1/256 sec. cor. of sec. 26.                                                                                                                                                                                                                                                               |

Subdivisional Survey of a Portion of Section 26,  
T. 33 S., R. 4 E., Salt Lake Meridian, Utah

| CHAINS |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|--------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 4.964  | <p>From the E-W-W 1/256 sec. cor. of secs. 26 and 35.</p> <p>N. 0° 17.7' W., along the N-S center line of the SE 1/4 of the SW 1/4 of the SW 1/4 of sec. 26.</p> <p>Point for the SE-SW-SW 1/256 sec. cor., at intersection with the E-W center line of the SE 1/4 of the SW 1/4 of the SW 1/4 of sec. 26; falls in gravel road, bearing N and SSE.</p> <p>Set a nail 6 ins. long, 2 ins. below the surface of the gravel road.</p> <p>from which</p> <p style="padding-left: 40px;">An aluminum post, 30 ins. long, 2 1/2 ins. diam., set 15 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to cap, for a reference monument, bears S. 37° 23' W., 99.6 lks. dist., with aluminum cap mkd. RM 1/256 S26 1984 and an arrow pointing to the corner.</p> <p style="padding-left: 40px;">An aluminum post, 30 ins. long, 2 1/2 ins. diam., set 12 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to cap, for a reference monument, bears N. 52° 49' W., 83.7 lks. dist., with aluminum cap mkd. RM 1/256 S26 1984 and an arrow pointing to the corner.</p> |
| 9.928  | <p>The center E-SW-SW 1/256 sec. cor. of sec. 26.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| 4.971  | <p>From the center S-S-SW 1/256 sec. cor. of sec. 26.</p> <p>N. 89° 55.0' W., along the E-W center line of the SE 1/4 of the SW 1/4 of the SW 1/4 of sec. 26.</p> <p>The SE-SW-SW 1/256 sec. cor. of sec. 26.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| 9.942  | <p>The center S-SW-SW 1/256 sec. cor., of sec. 26.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| 4.971  | <p>From the center W-SW 1/64 sec. cor. of sec. 26.</p> <p>N. 0° 16.0' W., along the N-S center line of the NW 1/4 of the SW 1/4 of sec. 26.</p> <p>Point for the center S-NW-SW 1/256 sec. cor. of sec. 26.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">C-S-NW-SW<br/>1/256<br/>S 26<br/>1984</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| 9.942  | <p>Point for the NW-SW 1/64 sec. cor., at intersection with the E-W center line of the NW 1/4 of the SW 1/4 of sec. 26. Not monumented.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| 19.884 | <p>The center W-W 1/64 sec. cor. of sec. 26.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |

Subdivisional Survey of a Portion of Section 26,  
T. 33 S., R. 4 E., Salt Lake Meridian, Utah

| CHAINS |                                                                                                                                        |
|--------|----------------------------------------------------------------------------------------------------------------------------------------|
|        | From the center N-SW 1/64 sec. cor. of sec. 26.                                                                                        |
|        | N. 89° 30.4' W., along the E-W center line of the NW 1/4 of the SW 1/4 of sec. 26.                                                     |
| 4.959  | Point for the center E-NW-SW 1/256 sec. cor., of sec. 26. Not monumented.                                                              |
| 9.918  | Point for the NW-SW 1/64 sec. cor. of sec. 26.                                                                                         |
| 19.836 | Point for the S-N 1/64 sec. cor. of secs. 26 and 27.                                                                                   |
|        | From the center E-W-SW 1/256 sec. cor. of sec. 26.                                                                                     |
|        | N. 0° 17.7' W., along the N-S center line of the SE 1/4 of the NW 1/4 of the SW 1/4 of sec. 26.                                        |
| 4.964  | Point for the SE-NW-SW 1/256 sec. cor., at intersection with the E-W center line of the SE 1/4 of the NW 1/4 of the SW 1/4 of sec. 26. |
|        | Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.                                    |
|        | SE-NW-SW 1/256                                                                                                                         |
|        | S 26                                                                                                                                   |
|        | 1984                                                                                                                                   |
| 9.928  | Point for the center E-NW-SW 1/256 sec. cor. of sec. 26.                                                                               |
|        | From the center S-N-SW 1/256 sec. cor. of sec. 26.                                                                                     |
|        | N. 89° 35.3' W., along the E-W center line of the SE 1/4 of the NW 1/4 of the SW 1/4 of sec. 26.                                       |
| 4.961  | The SE-NW-SW 1/256 sec. cor. of sec. 26.                                                                                               |
| 9.922  | The center S-NW-SW 1/256 sec. cor. of sec. 26.                                                                                         |
|        | From the center W 1/16 sec. cor. of sec. 26.                                                                                           |
|        | N. 0° 37.9' W., along the N-S center line of the NW 1/4 of sec. 26.                                                                    |
| 9.827  | Point for the center S-NW 1/64 sec. cor. of sec. 26. Not monumented.                                                                   |
| 19.654 | Point for the NW 1/16 sec. cor., at intersection with the E-W center line of the NW 1/4 of sec. 26.                                    |
|        | Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.                                    |
|        | NW 1/64                                                                                                                                |
|        | S 26                                                                                                                                   |
|        | 1984                                                                                                                                   |
| 39.306 | The W 1/16 sec. cor. of secs. 23 and 26.                                                                                               |

Subdivisional Survey of a Portion of Section 26,  
T. 33 S., R. 4 E., Salt Lake Meridian, Utah

| CHAINS |                                                                                                                                                                                                                                                                                                                                      |
|--------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|        | <p>From the center N 1/16 sec. cor. of sec. 26, monumented with a rebar, 5/8 ins. diam., firmly set 6 ins. below surface of gravel road, bearing NNW and SSE. There is no remaining evidence of the original brass cap. This position is accepted as a careful and faithful perpetuation of the position of the original corner.</p> |
|        | <p>N. 89° 43.3' W., along the E-W center line of the NW 1/4 of sec. 26.</p>                                                                                                                                                                                                                                                          |
| 3.75   | Boulder Creek, course S.                                                                                                                                                                                                                                                                                                             |
| 14.901 | <p>Point for the center W-E-NW 1/256 sec. cor., of sec. 26.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>                                                                                                                                                           |
|        | <p style="text-align: center;">C-W-E-NW<br/>1/256<br/>S 26<br/>1984</p>                                                                                                                                                                                                                                                              |
| 19.868 | The NW 1/16 sec. cor. of sec. 26.                                                                                                                                                                                                                                                                                                    |
| 24.835 | <p>Point for the center E-W-NW 1/256 sec. cor., of sec. 26.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>                                                                                                                                                           |
|        | <p style="text-align: center;">C-E-W-NW<br/><br/>1/256<br/>S 26<br/>1984</p>                                                                                                                                                                                                                                                         |
| 29.802 | Point for the center W-NW 1/64 sec. cor. of sec. 26. Not monumented.                                                                                                                                                                                                                                                                 |
| 39.736 | The N 1/16 sec. cor. of secs. 26 and 27.                                                                                                                                                                                                                                                                                             |
|        | <p>From the center W-E-NE 1/256 sec. cor. of sec. 26.</p> <p>N. 0° 35.4' W., on the N-S center line of the W 1/2 of the NE 1/4 of the NW 1/4 of sec. 26.</p>                                                                                                                                                                         |
| 17.50  | Boulder Creek, course SE.                                                                                                                                                                                                                                                                                                            |
| 19.686 | The W-E-W 1/256 sec. cor. of secs. 23 and 26.                                                                                                                                                                                                                                                                                        |
|        | <p>From the center W-W 1/64 sec. cor. of sec. 26.</p> <p>N. 0° 42.5' W., along the N-S center line of the SW 1/4 of the NW 1/4 of sec. 26.</p>                                                                                                                                                                                       |
| 9.794  | <p>Point for the SW-NW 1/64 sec. cor. at intersection with the E-W center line of the SW 1/4 of the NW 1/4 of sec. 26.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>                                                                                                |
|        | <p style="text-align: center;">SW-NW 1/64<br/>S 26<br/>1984</p>                                                                                                                                                                                                                                                                      |

Subdivisional Survey of a Portion of Section 35,  
T. 33 S., R. 4 E., Salt Lake Meridian, Utah

| CHAINS |                                                                                                     |
|--------|-----------------------------------------------------------------------------------------------------|
| 19.588 | Point for the center W-NW 1/64 cor. of sec. 26.                                                     |
|        | From the point for the center S-NW 1/64 sec. cor. of sec. 26.                                       |
|        | N. 89° 31.9' W., along the E-W center line of the SW 1/4 of the NW 1/4 of sec. 26.                  |
| 4.962  | Point for the center E-SW-NW 1/256 sec. cor. of sec. 26.                                            |
|        | Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd. |
|        | C-E-SW-NW                                                                                           |
|        | 1/256                                                                                               |
|        | S 26                                                                                                |
|        | 1984                                                                                                |
| 9.924  | The SW-NW 1/64 sec. cor. of sec. 26.                                                                |
| 19.848 | The S-N 1/64 sec. cor. of secs. 26 and 27.                                                          |
|        | From the center E-SW-NW 1/256 sec. cor. of sec. 26.                                                 |
|        | N. 0° 40.2' W., along the N-S center line of the NE 1/4 of the SW 1/4 of the NW 1/4 of sec. 26.     |
| 9.810  | The center E-W-NW 1/256 sec. cor. of sec. 26.                                                       |
|        | Subdivisional Survey of a Portion of Section 35,<br>T. 33 S., R. 4 E., Salt Lake Meridian, Utah     |
|        | From the 1/4 sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp., hereinbefore described.        |
|        | N. 0° 00.3' W., along the N-S center line of sec. 35.                                               |
| 20.000 | Point for the center S 1/16 sec cor. of sec. 35. Not monumented.                                    |
| 40.000 | Point for the center 1/4 sec. cor. at intersection with the E-W center line of sec. 35.             |
|        | Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd. |
|        | T 33 S R 4 E                                                                                        |
|        | C 1/4 S 35                                                                                          |
|        | 1984                                                                                                |
| 80.000 | The 1/4 sec. cor. of secs. 26 and 35.                                                               |
|        | From the 1/4 sec. cor. of secs. 35 and 36.                                                          |
|        | S. 89° 59.3' W., along the E-W center line of sec. 35.                                              |
| 39.773 | The center 1/4 sec. cor. of sec. 35.                                                                |
| 59.673 | Point for the center W 1/16 sec. cor. of sec. 35. Not monumented.                                   |

Subdivisional Survey of a Portion of Section 35,  
T. 33 S., R. 4 E., Salt Lake Meridian, Utah

| CHAINS                                                                                                  |                                                                                                                                                                                                   |
|---------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 62.20                                                                                                   | Boulder Creek, 70 lks. wide, 1 1/2 ft. deep, course SSW.                                                                                                                                          |
| 79.573                                                                                                  | The 1/4 sec. cor. of secs. 34 and 35.                                                                                                                                                             |
|                                                                                                         | <p>From the true point for the W 1/16 sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0° 00.3' E., on the N-S center line of the SW 1/4 of sec. 35.</p> |
| 7.90                                                                                                    | Boulder Creek, 70 lks. wide, 1 1/2 ft. deep, course SE.                                                                                                                                           |
| 20.001                                                                                                  | Point for the SW 1/16 sec. cor. at intersection with the E-W center line of the SW 1/4 of sec. 35.                                                                                                |
|                                                                                                         | Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.                                                                                               |
|                                                                                                         | <p style="text-align: center;">SW 1/16<br/>S 35<br/>1984</p>                                                                                                                                      |
| 40.002                                                                                                  | Point for the center W 1/16 sec. cor. of sec. 35.                                                                                                                                                 |
|                                                                                                         | <p>From the point for the center S 1/16 sec. cor. of sec. 35.</p> <p>S. 89° 59.1' W., along the E-W center line of the SW 1/4 of sec. 35.</p>                                                     |
| 19.905                                                                                                  | The SW 1/16 sec. cor. of sec. 35.                                                                                                                                                                 |
| 24.70                                                                                                   | Boulder Creek, 50 lks. wide, 2 ft. deep, course SSE.                                                                                                                                              |
| 39.810                                                                                                  | The S 1/16 sec. cor. of secs. 34 and 35.                                                                                                                                                          |
| <p>Subdivisional Survey of a Portion of Section 36,<br/>T. 33 S., R. 4 E., Salt Lake Meridian, Utah</p> |                                                                                                                                                                                                   |
|                                                                                                         | <p>From the 1/4 sec. cor. of secs. 1 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0° 03.9' E., along the N-S center line of sec. 36.</p>                                  |
| 16.60                                                                                                   | Improved graveled road, bears E and W.                                                                                                                                                            |
| 19.974                                                                                                  | Point for the center S 1/16 sec. cor. of sec. 36.                                                                                                                                                 |
|                                                                                                         | Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.                                                                                               |
|                                                                                                         | <p style="text-align: center;">T 33 S R 4 E<br/>C<br/>S 1/16   S 36<br/>C<br/>1984</p>                                                                                                            |
| 39.948                                                                                                  | Point for the center 1/4 sec. cor. at intersection with the E-W center line of sec. 36.                                                                                                           |

Subdivisional Survey of a Portion of Section 36,  
T. 33 S., R. 4 E., Salt Lake Meridian, Utah

| CHAINS |                                                                                                                                                                                                                                                 |
|--------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|        | <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 33 S R 4 E<br/>C 1/4<br/>S 36<br/>1984</p>                                                          |
| 59.943 | Point for the center N 1/16 sec. cor. of sec. 36. Not monumented.                                                                                                                                                                               |
| 79.938 | The 1/4 sec. cor. of secs. 25 and 36.                                                                                                                                                                                                           |
|        | <p>From the 1/4 sec. cor. of secs. 31 and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89° 54.6' W., along the E-W center line of sec. 36.</p>                                                                              |
| 3.50   | Asphalt surfaced road, bears SSE and NNW.                                                                                                                                                                                                       |
| 10.010 | Point for the center E-E 1/64 sec. cor. of sec. 36. Not monumented.                                                                                                                                                                             |
| 20.020 | Point for the center E 1/16 sec. cor. of sec. 36. Not monumented.                                                                                                                                                                               |
| 35.035 | <p>Point for the center W-W-E 1/256 sec. cor. of sec. 36.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">C-W-W-E<br/>1/256<br/>S 36<br/>1984</p> |
| 40.040 | The center 1/4 sec. cor. of sec. 36.                                                                                                                                                                                                            |
| 48.90  | Improved gravel road, bears SSE and NNW.                                                                                                                                                                                                        |
| 80.134 | The 1/4 sec. cor. of secs. 35 and 36.                                                                                                                                                                                                           |
|        | <p>From the point for the center E 1/16 sec. cor. of sec. 36</p> <p>N. 0° 04.9' E. along the N-S center line of the NE 1/4 of sec. 36.</p>                                                                                                      |
| 10.004 | Point for the center S-NE 1/64 sec. cor. of sec. 36. Not monumented.                                                                                                                                                                            |
| 20.008 | Point for the NE 1/16 sec. cor., at intersection with the E-W center line of the NE 1/4 of sec. 36. Not monumented                                                                                                                              |
| 25.010 | Point for the center S-N-NE 1/256 sec. cor. of sec. 36. Not monumented.                                                                                                                                                                         |
| 30.012 | Point for the center N-NE 1/64 sec. cor. of sec. 36. Not monumented.                                                                                                                                                                            |
| 34.00  | Asphalt surfaced road on curve, bears NW and S.                                                                                                                                                                                                 |
| 40.016 | The E 1/16 sec. cor. of secs. 25 and 36.                                                                                                                                                                                                        |

Subdivisional Survey of a Portion of Section 36,  
T. 33 S., R. 4 E., Salt Lake Meridian, Utah

| CHAINS |                                                                                                                                      |
|--------|--------------------------------------------------------------------------------------------------------------------------------------|
|        | From the point for the N 1/16 sec. cor. of secs. 31 and 36, on the E. bdy. of the Tp., hereinbefore described.                       |
|        | N. 89° 56.8' W. along the E-W center line of the NE 1/4 of sec. 36.                                                                  |
| 5.006  | Point for the center E-E-NE 1/256 sec. cor. of sec. 36. Not monumented.                                                              |
| 10.012 | Point for the center E-NE 1/64 sec. cor. of sec. 36.                                                                                 |
|        | Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.                                  |
|        | <p style="text-align: center;">C-E-NE 1/64<br/>S 36<br/>1984</p>                                                                     |
| 13.50  | Asphalt surfaced road, bears NW and SE.                                                                                              |
| 15.018 | Point for the center W-E-NE 1/256 sec. cor. of sec. 36. Not monumented.                                                              |
| 20.024 | Point for the NE 1/16 sec. cor.                                                                                                      |
| 35.042 | Point for the center W-W-NE 1/256 sec. cor. of sec. 36. Not monumented.                                                              |
| 40.048 | Point for the center N 1/16 sec. cor. of sec. 36.                                                                                    |
|        | From the center E-NE 1/64 sec. cor. of sec. 36.                                                                                      |
|        | N. 0° 05.5' E., along the N-S center line of the NE 1/4 of the NE 1/4 of sec. 36.                                                    |
| 5.004  | Point for the center S-NE-NE 1/256 sec. cor. of sec. 36.                                                                             |
|        | Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.                                  |
|        | <p style="text-align: center;">C-S-NE-NE<br/>1/256<br/>S 36<br/>1984</p>                                                             |
| 10.008 | Point for the NE-NE 1/64 sec. cor., at intersection with the E-W center line of the NE 1/4 of the NE 1/4 of sec. 36. Not monumented. |
| 20.016 | Point for the E-E 1/64 sec. cor. of secs. 25 and 36.                                                                                 |
|        | From the point for the N-N 1/64 sec. cor. of secs. 31 and 36, on the E. bdy. of the Tp., hereinbefore described.                     |
|        | N. 89° 58.0' W. along the E-W center line of the NE 1/4 of the NE 1/4 of sec. 36.                                                    |
| 10.014 | Point for the NE-NE 1/64 sec. cor. of sec. 36.                                                                                       |
| 15.021 | Point for the center W-NE-NE 1/256 sec. cor. of sec. 36. Not monumented.                                                             |

Subdivisional Survey of a Portion of Section 36,  
T. 33 S., R. 4 E., Salt Lake Meridian, Utah

| CHAINS |                                                                                                                                       |
|--------|---------------------------------------------------------------------------------------------------------------------------------------|
| 19.25  | Asphalt surfaced road, bears N and S.                                                                                                 |
| 20.028 | Point for the center N-NE 1/64 sec. cor. of sec. 36.                                                                                  |
|        | From the point for the center W-E-NE 1/256 sec. cor. of sec. 36.                                                                      |
|        | N. 0° 05.2' E., along the N-S center line of the SW 1/4 of the NE 1/4 of the NE 1/4 of sec. 36.                                       |
| 2.50   | Asphalt surfaced road, bears NW and SE.                                                                                               |
| 5.003  | Point for the SW-NE-NE 1/256 sec. cor. at intersection with the E-W center line of the SW 1/4 of the NE 1/4 of the NE 1/4 of sec. 36. |
|        | Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.                                   |
|        | SW-NE-NE<br>1/256<br>S 36<br>1984                                                                                                     |
| 10.006 | Point for the center W-NE-NE 1/256 sec. cor. of sec. 36.                                                                              |
|        | From the center S-NE-NE 1/256 sec. cor. of sec. 36.                                                                                   |
|        | N. 89° 57.4' W., along the E-W center line of the SW 1/4 of the NE 1/4 of the NE 1/4 of sec. 36.                                      |
| 5.007  | The SW-NE-NE 1/256 sec. cor. of sec. 36.                                                                                              |
| 7.00   | Asphalt surfaced road, bears NW and SE.                                                                                               |
| 10.014 | The point for the center S-N-NE 1/256 sec. cor. of sec. 36.                                                                           |
|        | From the center W-NE-NE 1/256 sec. cor. of sec. 36.                                                                                   |
|        | N. 0° 05.2' E., on the N-S center line of the NW 1/4 of the NE 1/4 of the NE 1/4 of sec. 36.                                          |
| 10.006 | The W-E-E 1/256 sec. cor. of secs. 25 and 36.                                                                                         |
|        | From the center E-E 1/64 sec. cor. of sec. 36.                                                                                        |
|        | N. 0° 05.5' E., along the N-S center line of the SE 1/4 of the NE 1/4 of sec. 36.                                                     |
| 10.006 | Point for the SE-NE 1/64 sec. cor., at intersection with the E-W center line of the SE 1/4 of the NE 1/4 of sec. 36. Not monumented   |
| 15.009 | Point for the center N-SE-NE 1/256 sec. cor. of sec. 36.                                                                              |
|        | Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.                                   |
|        | C-N-SE-NE<br>1/256<br>S 36<br>1984                                                                                                    |

Subdivisional Survey of a Portion of Section 36,  
T. 33 S., R. 4 E., Salt Lake Meridian, Utah

| CHAINS                                                                                                                    |                                                                                                                                        |
|---------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| 16.00                                                                                                                     | Asphalt surfaced road, bears NW and SE.                                                                                                |
| 20.012                                                                                                                    | The center E-NE 1/64 sec. cor. of sec. 36.                                                                                             |
| <hr/> From the S-N 1/64 sec. cor. of secs. 31 and 36, on the E. bdy. of the Tp., hereinbefore described.                  |                                                                                                                                        |
| N. 89° 55.7' W., along the E-W center line of the SE 1/4 of the NE 1/4 of sec. 36.                                        |                                                                                                                                        |
| 5.006                                                                                                                     | Point for the C-E-SE-NE 1/256 sec. cor. of sec. 36.                                                                                    |
| Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.                       |                                                                                                                                        |
| C-E-SE-NE<br>1/256<br>S 36<br>1984                                                                                        |                                                                                                                                        |
| 6.75                                                                                                                      | Asphalt surfaced road, bears NW and SE.                                                                                                |
| 10.012                                                                                                                    | Point for the SE-NE 1/64 sec. cor. of sec. 36                                                                                          |
| 20.024                                                                                                                    | Point for the center S-NE 1/64 sec. cor. of sec. 36.                                                                                   |
| <hr/> From the center E-SE-NE 1/256 sec. cor. of sec. 36.                                                                 |                                                                                                                                        |
| N. 0° 05.7' E., along the N-S center line of the NE 1/4 of the SE 1/4 of the NE 1/4 of sec. 36.                           |                                                                                                                                        |
| 5.004                                                                                                                     | Point for the NE-SE-NE 1/256 sec. cor., at intersection with the E-W center line of the NE 1/4 of the SE 1/4 of the NE 1/4 of sec. 36. |
| Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.                       |                                                                                                                                        |
| NE-SE-NE<br>1/256<br>S 36<br>1984                                                                                         |                                                                                                                                        |
| 10.008                                                                                                                    | Point for the center E-E-NE 1/256 sec. cor. of sec. 36.                                                                                |
| <hr/> From the point for the N-S-N 1/256 sec. cor. of secs. 31 and 36, on the E. bdy. of the Tp., hereinbefore described. |                                                                                                                                        |
| N. 89° 56.3' W., along the E-W center line of the NE 1/4 of the SE 1/4 of the NE 1/4 of sec. 36.                          |                                                                                                                                        |
| 5.006                                                                                                                     | The NE-SE-NE 1/256 sec. cor. of sec. 36.                                                                                               |
| 9.25                                                                                                                      | Asphalt surfaced road, bears NW and SE.                                                                                                |
| 10.012                                                                                                                    | The center N-SE-NE 1/256 sec. cor. of sec. 36.                                                                                         |
| <hr/> From the center W-W-E 1/256 sec. cor. of sec. 36.                                                                   |                                                                                                                                        |

Subdivisional Survey of a Portion of Section 36,  
T. 33 S., R. 4 E., Salt Lake Meridian, Utah

| CHAINS |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|--------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 19.998 | <p>N. 0° 04.1' E., on the N-S center line of the W 1/2 of the SW 1/4 of the NE 1/4 of sec. 36.</p> <p>Point for the center W-W-NE 1/256 sec. cor. of sec. 36.</p>                                                                                                                                                                                                                                                                                                                                                                                                                               |
| 19.998 | <p>From the center W-W-NE 1/256 sec. cor. of sec. 36.</p> <p>N. 0° 04.1' E., on the N-S center line of the W 1/2 of the NW 1/4 of the NE 1/4 of sec. 36.</p> <p>The W-W-E 1/256 sec. cor. of secs. 25 and 36.</p>                                                                                                                                                                                                                                                                                                                                                                               |
| 19.961 | <p>From the point for the E 1/16 sec. cor. of secs. 1 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0° 05.2' E., along the N-S center line of the SE 1/4 of sec. 36.</p> <p>Point for the SE 1/16 sec. cor., at intersection with the E-W center line of the SE 1/4 of sec. 36. Not monumented.</p>                                                                                                                                                                                                                                                                      |
| 39.922 | <p>Point for the center E 1/16 sec. cor. of sec. 36.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| 20.012 | <p>From the S 1/16 sec. cor. of secs. 31 and 36, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 89° 56.9' W. along the E-W center line of the SE 1/4 of sec. 36.</p> <p>Point for the SE 1/16 sec. cor. of sec. 36.</p>                                                                                                                                                                                                                                                                                                                                                           |
| 35.021 | <p>Point for the center W-W-SE 1/256 sec. cor. of sec. 36.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">C-W-W-SE<br/>1/256<br/>S 36<br/>1984</p>                                                                                                                                                                                                                                                                                                                                               |
| 40.024 | <p>The center S 1/16 sec. cor. of sec. 36.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| 19.971 | <p>From the center W-W-SE 1/256 sec. cor. of sec. 36.</p> <p>N. 0° 04.2' E., on the N-S center line of the W 1/2 of the NW 1/4 of the SE 1/4 of sec. 36.</p> <p>The center W-W-E 1/256 sec. cor. of sec. 36.</p>                                                                                                                                                                                                                                                                                                                                                                                |
|        | <p style="text-align: center;">General Description</p> <p>The area surveyed and resurveyed within T. 33 S., R. 4 E., varies from mountainous to gently rolling. The elevation ranges from about 6400 ft. to 6950 ft. above sea level. The soil varies from sandy clay loam in the bottom land to sandy clay loam and very rocky in the higher elevation. The vegetation consists of juniper, pinon, sagebrush, meadow grass and other sparse native grasses.</p> <p>The town of Boulder, Utah, is situated in section 25 and 26, with other ranch houses scattered throughout the township.</p> |





