

Survey of a Portion of the Subdivisional Lines of
T. 39 S., R. 13 E., Salt Lake Meridian, Utah

T 39 S R 13 E
S 11 | S 12
S 14 | S 13
1986

Set a juniper post, 6 ft. long, alongside the cor.

From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., hereinbefore described.

S. 89° 51.6' W., bet. secs. 12 and 13.

Over rolling desert land, through scattered pinon and juniper growth.

39.937 Point for the 1/4 sec. cor. of secs. 12 and 13.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 39 S R 13 E
S 12
1/4 S 13
1986

Set a juniper post, 6 ft. long, alongside the cor.

Cor. is located on gentle N. slope, in sagebrush and native grasses.

79.874 The cor. of secs. 11, 12, 13, and 14.

N. 0° 07.3' W., bet. secs. 11 and 12.

Over rolling desert land, through scattered pinon and juniper growth.

22.500 Center line of Utah State Highway No. 263, bears ENE and WSW (scaled).

39.992 Point for the 1/4 sec. cor. of secs. 11 and 12.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

Survey of a Portion of the Subdivisional Lines of
T. 39 S., R. 13 E., Salt Lake Meridian, Utah

T 39 S R 13 E
1/4
S 11 | S 12
1986

Cor. is located on steep E. slope of sandstone ledges.

59.988 Point for the N 1/16 sec. cor. of secs. 11 and 12.

Set an iron post, 14 ins. long, 1 inch diam., drilled 10 ins. in solid sandstone, with brass cap mkd.

T 39 S R 13 E
N 1/16
S 11 | S 12
1986

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.

Cor. is located on E. slope of sandstone ledges.

79.984 The cor. of secs. 1, 2, 11, and 12, monumented with an iron post, 2 1/2 ins. diam., with brass cap, mkd. as described in the official record of the 1957 survey of sec. 2.

From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., hereinbefore described.

S. 89° 53.9' W., bet. secs. 1 and 12.

Over rolling desert land, through scattered pinon and juniper growth.

20.000 Point for the E 1/16 sec. cor. of secs. 1 and 12.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 39 S R 13 E
S 1
E 1/16 S 12
1986

Set a steel fence post, 6 ft. long, alongside the cor.

Cor. is located on sandy E. slope.

Survey of a Portion of the Subdivisional Lines of
T. 39 S., R. 13 E., Salt Lake Meridian, Utah

40.000 Point for the 1/4 sec. cor. of secs. 1 and 12.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 39 S R 13 E
S 1
1/4 S 12
1986

Cor. is located on rolling sandy land, in sagebrush and native grasses.

50.000 Point for the E-W 1/64 sec. cor. of secs. 1 and 12.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 39 S R 13 E
S 1
E-W 1/64 S 12
1986

Set a juniper post, 6 ft. long, alongside the cor.

Cor. is located on rolling sandy land, in sagebrush and native grasses.

60.000 Point for the W 1/16 sec. cor. of secs. 1 and 12.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 39 S R 13 E
S 1
W 1/16 S 12
1986

Cor. is located on rolling land, in sagebrush, scattered pinon, juniper and native grasses.

80.000 The cor. of secs. 1, 2, 11, and 12.

Survey of the Subdivision of Section 1,
T. 39 S., R. 13 E., Salt Lake Meridian, Utah

Survey of the Subdivision of Section 1,
T. 39 S., R. 13 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 1 and 12.

N. 0° 00.3' W., on the N-S center line of sec. 1.

Over rolling desert land, through scattered pinon and juniper growth.

39.970 Point for the center 1/4 sec. cor. of sec. 1, at intersection with the E and W center line of sec. 1.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 39 S R 13 E
C 1/4 S 1
1986

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.

Cor. is located at base of sandstone ledges, bears NE and SW.

79.969 The 1/4 sec. cor. of secs. 1 and 36, on the N. bdy. of the Tp., hereinbefore described.

From the 1/4 sec. cor. of secs. 1 and 6, on the E. bdy. of the Tp., hereinbefore described.

S. 89° 55.1' W., on the E-W center line of sec. 1.

Over rolling desert land, through scattered pinon and juniper growth.

39.980 The center 1/4 sec. cor. of sec. 1.

79.968 The 1/4 sec. cor. of secs. 1 and 2.

Survey of the Subdivision of Section 12.
T. 39 S., R. 13 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 12 and 13.

N. 0° 04.4' W., on the N-S center line of sec. 12.

Over rolling dessert land, through scattered pinon and juniper growth.

Survey of the Subdivision of Section 12.
T. 39 S., R. 13 E., Salt Lake Meridian, Utah

- 37.500 Center line of Utah State Highway No. 263, bears NE and SW (scaled).
- 39.979 Point for the center 1/4 sec. cor. of sec. 12, at intersection with the E-W center line of sec. 12.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 39 S R 13 E
C 1/4 S 12
1986

Set a juniper post, 6 ft. long, alongside the cor.

Cor. is located on gentle S. slope.

- 49.974 Point for the center-south-north 1/64 sec. cor. of sec. 12.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 39 S R 13 E
C-S-N 1/64 S 12
1986

Set a squared cedar post, alongside the cor.

Cor. is located on rolling sandy land, in sagebrush and native grasses.

- 59.969 Point for the center N 1/16 sec. cor. of sec. 12.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 39 S R 13 E
C
N 1/16 | S 12
C
1986

Set a squared cedar post, alongside the cor.

Cor. is located on gentle rolling land, in sagebrush and native grasses.

- 79.959 The 1/4 sec. cor. of secs. 1 and 12.
-

Survey of the Subdivision of Section 12.
T. 39 S., R. 13 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp., hereinbefore described.

S. 89° 52.7' W., on the E-W center line of sec. 12.

Over rolling desert land, through scattered pinon and juniper growth.

18.000 Center line of Utah State Highway No. 263, bears ESE and WNW (scaled).

19.984 Point for the center E 1/16 sec. cor. of sec. 12.

Set an iron post, 14 ins. long, 1 inch diam., drilled 10 ins. in solid sandstone, with brass cap mkd.

$$\begin{array}{r} \text{T 39 S R 13 E} \\ \text{E 1/16} \\ \hline \text{C S 12 C} \\ \text{1986} \end{array}$$

Raise a mound of stone, 3 1/2 ft. base, 2 ft. high, N of the cor.

Cor. is located 44 lks. S. of the center line of Utah State Highway No. 263.

35.000 Center line of Utah State Highway No. 263, bears NE and SW (scaled).

39.968 The center 1/4 sec. cor. of sec. 12.

59.952 Point for the center W 1/16 sec. cor. of sec. 12.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

$$\begin{array}{r} \text{T 39 S R 13 E} \\ \text{W 1/16} \\ \hline \text{C S 12 C} \\ \text{1986} \end{array}$$

Cor. is located on rolling land, in sagebrush and native grasses.

79.936 The 1/4 sec. cor. of secs. 11 and 12.

Survey of the Subdivision of Section 12.
T. 39 S., R. 13 E., Salt Lake Meridian, Utah

From the center E 1/16 sec. cor. of sec. 12.

N. $0^{\circ} 02.9'$ W., on the N and S center line of the NE 1/4 of sec. 12.

- 19.986 Point for the NE 1/16 sec. cor. of sec. 12, at intersection with the E and W center line of the NE 1/4 of sec. 12.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 39 S R 13 E
NE 1/16 S 12
1986

Set a squared cedar post, 6 ft. long, alongside the cor.

- 39.972 The E 1/16 sec. cor. of secs. 1 and 12.

From the N 1/16 sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp., hereinbefore described.

S. $89^{\circ} 53.5'$ W., on the E and W center line of the NE 1/4 of sec. 12.

- 19.991 The NE 1/16 sec. cor. of sec. 12.

- 39.982 The center N 1/16 sec. cor. of sec. 12.

From the center W 1/16 sec. cor. of sec. 12.

N. $0^{\circ} 05.8'$ W., on the N and S center line of the NW 1/4 of sec. 12.

- 9.996 Point for the center-south-northwest 1/64 sec. cor. of sec. 12.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 39 S R 13 E
C-S-NW 1/64 S 12
1986

Set a juniper post, 5 ft. long, alongside the cor.

Survey of the Subdivision of Section 12.
T. 39 S., R. 13 E., Salt Lake Meridian, Utah

- 19.992 Point for the NW 1/16 sec. cor. of sec. 12, at intersection with the E and W center line of the NW 1/4 of sec. 12.

Set an iron post, 14 ins. long, 1 inch diam., drilled 10 ins. in solid sandstone, with brass cap mkd.

T 39 S R 13 E
NW 1/16 S 12
1986

Raise a mound of stone, 3 ft. base, 2 ft. high, NE of the cor.

Cor. is located in bottom of draw, drains S.

- 39.985 The W 1/16 sec. cor. of secs. 1 and 12.
-

From the center N 1/16 sec. cor. of secs. 12.

S. 89° 53.1' W., on the E and W center line of the NW 1/4 of sec. 12.

- 9.996 Point for the center-east-northwest 1/64 sec. cor. of sec. 12.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 39 S R 13 E
C-E-NW 1/64 S 12
1986

Set a squared cedar post, 6 ft. long, alongside the cor.

- 19.992 The NW 1/16 sec. cor. of sec. 12.

- 39.983 The N 1/16 sec. cor. of secs. 11 and 12.
-

From the center-east-northwest 1/64 sec. cor. of sec. 12.

N. 0° 05.1' W., on the N and S center line of the NE 1/4 of the NW 1/4 of sec. 12.

- 19.991 The E-W 1/64 sec. cor. of secs. 1 and 12.
-

From the center-south-north 1/64 sec. cor. of sec. 12.

Survey of the Subdivision of Section 12.
T. 39 S., R. 13 E., Salt Lake Meridian, Utah

S. $89^{\circ} 52.9'$ W., on the E and W center line of the SE 1/4 of the NW 1/4 of sec. 12.

19.988 The center-south-northwest 1/64 sec. cor. of sec. 12.

General Description

Township 39 South, Range 13 East, is located on rolling desert land, with numerous small draws draining to the southwest. The elevation varies from about 5200 to 6000 ft. above sea level. The soil is mostly sandy with some exposed sandstone outcroppings. There is lightly scattered pinon and juniper growth throughout the portions surveyed. Utah State Highway No. 263 enters section 12 in the SW 1/4 and leaves the township in the SE 1/4 of section 12. The main use at this time is livestock grazing, with some recreational activity.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Ferrel D. Reynolds	Surveying Technician
Larry V. Judd	Surveying Technician

CERTIFICATE OF SURVEY

I, **Gail E. Reynolds, Cadastral Surveyor**, HEREBY

CERTIFY upon honor that, in pursuance of special instructions date of

the 20th day of March, 1986, I have dependently resurveyed a portion of the north and east boundaries, surveyed a portion of the subdivisional lines, and surveyed the subdivision of sections 1 and 12 in T. 39 S., R. 13 E.,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

May 21, 1987
(Date)


(Cadastral Surveyor)

CERTIFICATE OF APPROVAL


BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the dependent resurvey of a portion of the north and east boundaries, the survey of a portion of the subdivisional lines, and the survey of the subdivision of sections 1 and 12 in T. 39 S., R. 13 E., Salt Lake Meridian, Utah

executed by Gail E. Reynolds, Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

August 27, 1987
(Date)


(Chief, Cadastral Surveyor for Utah)