

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF A

PORTION OF THE SOUTH BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES,

AND A

SUBDIVISIONAL SURVEY OF SECTIONS 28 AND 33,

IN

TOWNSHIP 42 SOUTH, RANGE 1 WEST

Of the Salt Lake Meridian,  
In the State of Utah.

EXECUTED BY

Richard A. Zaninovich Cadastral Surveyor

Under special instructions dated March 6, 1987, approved March 6, 1987.

which provided for the surveys included under Group Number 701, and assignment instructions dated March 10, 1987.

Survey commenced March 10, 1987

Survey completed March 18, 1987



## INDEX DIAGRAM

Township 42 South, Range 1 West

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
		8			
30	29 7	28 4	27	26	25
	6	5	3		
31	32 4	33 2	34	35	36
		2			

Subdivision of Section 28  
 Subdivision of Section 33

- Page 9  
 - Page 10

## Township 42 South, Range 1 West, Salt Lake Meridian, Utah

The following field notes are those of the dependent resurvey of a portion of the south boundary, a portion of the subdivisional lines and the survey of the subdivision of sections 28 and 33 in T. 42 S., R. 1 W., Salt Lake Meridian, Utah.

History of Earlier Surveys

	<u>Surveyed by</u>	<u>Retr. or Resurveyed by</u>	
<u>SOUTH BOUNDARY</u>			
All	J.G. Burrill	1877	
Portion		Thoma and Johnston	1916
All		G.E. Reynolds	1981
<u>SUBDIVISION</u>			
Portion	Bailey and Burrill	1877	
Portion		J.C. Thoma, et al	1918
Portion	Thoma and Johnston	1918	

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 701, Utah, dated March 6, 1987.

The directions of the lines were determined by reference to true meridians established by hour angle observations of Polaris. The lines were carried forward by sustained angulations.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions, lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic coordinates of the witness corner to the corner of secs. 3, 4, 33, and 34, as determined by a tie made to the U.S. Geological Survey station identical with the southeast corner of the township, are as follows:

Latitude 37° 06' 28.15" N.      Longitude 111° 54' 14.19" W.  
N.A.D. 1927

The mean magnetic declination, as projected from the U.S. Geological Survey Magnetic Declination Map of 1980, is 13 1/2° E.

---

Dependent Resurvey of a Portion of the South Boundary,  
T. 41 S., R. 1 W., Salt Lake Meridian, Utah

Dependent Resurvey of a Portion of the South Boundary,  
T. 41 S., R. 1 W., Salt Lake Meridian, Utah

---

(Reestablishment of the Survey Executed by J.G. Burrill  
in 1877 and the Resurveys Executed by Thoma and Johnston  
in 1916 and G. Reynolds in 1981)

---

Beginning at the witness cor. to the cor. of secs. 3, 4, 33, and 34, monumented with an iron post, 2 ins. diam., projecting 8 ins. above the ground, with brass cap, mkd. as described in the official record of the 1916 resurvey.

N. 89° 58' W., bet. secs. 3 and 34.

4.24 True point for the cor. of secs. 3, 4, 33, and 34.

Continue bet. secs. 4 and 33.

11.24 Paria River, drains SSE.

19.24 Center line of U.S. Highway No. 89, bears WNW and ESE.

45.05 The 1/4 sec. cor. of secs. 4 and 33, monumented with an iron post, 1 in. diam., projecting 8 ins. above the ground, with brass cap, mkd. as described in the official record of the 1916 resurvey.

---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 41 S., R. 1 W., Salt Lake Meridian, Utah

---

(Reestablishment of the Survey Executed by  
Bailey and Burrill in 1877)

---

From the true point for the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., hereinbefore described.

N. 0° 35' W., bet. secs. 33 and 34.

39.59 Point for the 1/4 sec. cor. of secs. 33 and 34, at proportionate dist.; a sandstone, 14x12x6 ins. mkd. 1/4 was found lying loosely on the ground at the base of a steep unstable W. slope.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 42 S., R. 1 W., Salt Lake Meridian, Utah

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone 3 ft. base to top of brass cap, mkd.

T 42 S R 1 W  
1/4  
S 33 | S 34  
1987

Deposit the mkd. stone alongside the stainless steel post.

79.18 Point for the cor. of secs. 27, 28, 33, and 34, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground in a mound of stone 3 ft. base to top of brass cap mkd.

T 42 S R 1 W  
S 28 | S 27  
S 33 | S 34  
1987

---

From the cor. of secs. 26, 27, 34, and 35, monumented with an iron post, 2 ins. diam., projecting 8 ins. above the ground, with brass cap, mkd. as described in the official record of the 1918 resurvey executed by J.C. Thoma, et al and a mound of stone W. of the cor.

From this cor. the SE. cor. of the Tp. bears S. 63° 12.5' E., 179.541 chs. dist. This cor. has been designated as a U.S.G.S. tri-station.

S. 89° 36' W., bet. secs. 27 and 34.

40.14 Point for the 1/4 sec. cor. of secs. 27 and 34 at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 42 S R 1 W  
S 27  
1/4 S 34  
1987

Raise a mound of stone N. of the cor.

80.27 The cor. of secs. 27, 28, 33, and 34.

---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 42 S., R. 1 W., Salt Lake Meridian, Utah

N. 0° 50' W., bet. secs. 27 and 28.

39.59 The 1/4 sec. cor. of secs. 27 and 28 monumented with a sandstone,  
14x12x6 ins., mkd. 1/4 on W face.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam. 22 ins.  
in the ground, with brass cap mkd.

T 42 S R 1 W  
1/4  
S 28 | S 27  
1987

Deposit the mkd. stone alongside the stainless steel post.

Raise a mound of stone W. of the cor.

N. 0° 15' W., beginning new measurement.

39.51 The cor. of secs. 21, 22, 27, and 28, monumented with a sandstone,  
8x4x2 ft. above ground, mkd. with 2 notches on the S., 3 notches  
on the E. and a cross (X) at the exact cor. point; the iron post  
set in 1918 was not found.

Raise a mound of stone W. of the cor.

From the cor. of secs. 4, 5, 32, and 33 on the S. bdy. of the Tp.,  
monumented with an iron post, 2 ins. diam., projecting 8 ins.  
above the ground, with brass cap, mkd. as described in the  
official record of the 1916 resurvey.

N. 0° 01' E., bet. secs. 32 and 33.

11.00 Center line of U.S. Highway No. 89, bears WNW and ESE (scaled).

25.00 Sand Gulch, drains ENE (scaled).

40.19 The 1/4 sec. cor. of secs. 32 and 33, monumented with a sandstone,  
10x8x6 ins., mkd. 1/4 on W face.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 22  
ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 42 S., R. 1 W., Salt Lake Meridian, Utah

T 42 S R 1 W  
1/4  
S 32 | S 33  
1987

Deposit the mkd. stone alongside the stainless steel post.

Cor. falls 15 lks. W. of a N.-S. fence.

N. 0° 20' W., beginning new measurement.

- 7.51 The witness cor. to the cor. of secs. 28, 29, 32, and 33,  
monumented with the mks.

W C  
29 | 28  
32 | 33

chisled on a south facing sandstone ledge 3 ft. above the  
ground.

This cor. will now function as an angle point only.

N. 0° 05' E., beginning new measurement.

- 31.97 Point for the cor. of secs. 28, 29, 32, and 33 at proportionate  
dist.

Set a stainless steel post, 30 ins. long, 2 1/2 ins., diam., 22  
ins. in the ground, with brass cap mkd.

T 42 S R 1 W  
S 29 | S 28  
S 32 | S 33  
1987

Cor. falls on a steep SW. slope.

From the cor. of secs. 27, 28, 33, and 34.

N. 89° 15' W., bet. secs. 28 and 33.

- 20.02 Point for the E. 1/16 sec. cor. of secs. 28 and 33.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 22  
ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 42 S., R. 1 W., Salt Lake Meridian, Utah

T 42 S R 1 W  
 $\frac{S 28}{S 33}$   
 E 1/16 1987

Cor. falls on the E. bank of the Paria River.

23.00 Paria River, drains SSW.

40.04 Point for the 1/4 sec. cor. of secs. 28 and 33, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 42 S R 1 W  
 $\frac{S 28}{S 33}$   
 1/4 1987

48.50 W. channel of Paria River, drains S (scaled).

52.00 Dirt road, bears N and S (scaled).

60.06 Point for the W. 1/16 sec. cor. of secs. 28 and 33.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground in a collar of stone, with brass cap mkd.

T 42 S R 1 W  
 $\frac{S 28}{S 33}$   
 W 1/16 1987

Cor. falls in a gravel pit; there is no remaining evidence of the witness cor. to the cor. of secs. 28, 29, 32, and 33.

80.08 The cor. of secs. 28, 29, 32, and 33.

---

N. 89° 12' W., bet. secs. 29 and 32.

40.04 Point for the 1/4 sec. cor. of secs. 29 and 32, at proportionate distance.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground in a collar of stone, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 42 S., R. 1 W., Salt Lake Meridian, Utah

T 42 S R 1 W  
 $\frac{S 29}{S 32}$   
 1/4  
 1987

- 68.07 The witness cor. to the 1/4 sec. cor. of secs. 29 and 32, monumented with a quartzite, 16x8x6 ins., mkd. WC 1/4.

This cor. will now function as an angle point only.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 42 S R 1 W  
 AP  
 $\frac{S 29}{S 32}$   
 1987

Deposit the mkd. stone alongside the stainless steel post.

Raise a mound of stone N. of the cor.

---

From the cor. of secs. 28, 29, 32, and 33.

N. 1° 01' E., bet. secs. 28 and 29.

- 39.23 The 1/4 sec. cor. of secs. 28 and 29, monumented with a sandstone, 18x8x8 ins., mkd. 1/4 on W face.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground in a collar of stone, with brass cap mkd.

T 42 S R 1 W  
 1/4  
 S 29 | S 28  
 1987

Deposit the mkd. stone alongside the stainless steel post.

---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 42 S., R. 1 W., Salt Lake Meridian, Utah

From the cor. of secs. 21, 22, 27, and 28.

N. 88° 36' W., bet. secs. 21 and 28.

38.90 Point for the 1/4 sec. cor. of secs. 21 and 28 at proportionate dist.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, in a mound of stone 5 ft. base to top of brass cap mkd.

T 42 S R 1 W  
S 21  
1/4 S 28  
1987

46.19 The witness cor. to the 1/4 sec. cor. of secs. 21 and 28, monumented with a sandstone, 4x2x1 ft., mkd. 1/4

This cor. will now function as an angle point only.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins., diam., 22 ins. in the ground, with brass cap mkd.

T 42 S R 1 W  
AP  
S 21  
1/4 S 28  
1987

Deposit the mkd. stone alongside the stainless steel post.

Raise a mound of stone N. of the cor.

---

Survey of the Subdivision of Section 28,  
T. 42 S., R. 1 W., Salt Lake Meridian, Utah

---

Survey of the Subdivision of Section 28,  
T. 42 S., R. 1 W., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 28 and 33.

N. 0° 17' E., on the N. and S. center line of sec. 28.

29.50 Paria River, drains ESE.

39.40 Point for the center 1/4 sec. cor. of sec. 28, at intersection  
with the E and W center line.

Set an stainless steel post, 30 ins. long, 2 1/2 ins. diam., 22  
ins. in the ground, with brass cap mkd.

T 42 S R 1 W  
C 1/4 S 28  
1987

79.51 The 1/4 sec. cor. of secs. 21 and 28.

---

From the 1/4 sec. cor. of secs. 27 and 28.

N. 89° 30' W., on the E and W center line of sec. 28.

19.635 Point for the center E. 1/16 sec. cor. of sec. 28.

Set an stainless steel post, 30 ins. long, 2 1/2 ins. diam., 22  
ins. in the ground, with brass cap mkd.

T 42 S R 1 W  
E 1/16  
C S 28 C  
1987

Raise a mound of stone N. of the cor.

39.27 The center 1/4 sec. cor. of sec. 28.

57.50 Paria River, drains SE (scaled).

59.035 Point for the center W. 1/16 sec. cor. of sec. 28

Set an stainless steel post, 30 ins. long, 2 1/2 ins. diam., 22  
ins. in the ground, with brass cap mkd.

T 42 S R 1 W  
W 1/16  
C S 28 C  
1987

Survey of the Subdivision of Section 28,  
T. 42 S., R. 1 W., Salt Lake Meridian, Utah

Cor. falls between seasonal channels of the Paria River.

70.50 W. channel of Paria River, drains SE (scaled).

78.80 The 1/4 sec. cor. of secs. 28 and 29.

---

From the E. 1/16 sec. cor. of secs. 28 and 33.

N. 0° 16' W., on the N. and S. center line of the SE. 1/4 of sec. 28.

39.50 The center E. 1/16 sec. cor. of sec. 28.

---

From the W. 1/16 sec. cor. of secs. 28 and 33.

N. 0° 39' E., on the N. and S. center line of the SW. 1/4 of sec. 28.

26.50 Dirt road, bears NW and SE (scaled).

32.50 W. channel of Paria River, drains ESE (scaled).

39.32 The center W. 1/16 sec. cor. of sec. 28.

---

Survey of the Subdivision of Section 33,  
T. 42 S., R. 1 W., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 4 and 33 on the S. bdy. of the Tp., hereinbefore described.

N. 0° 01' W., on the N and S center line of sec. 33.

4.00 Center line of U.S. Highway No. 89, bears WNW and ESE (scaled).

20.50 Sand Gulch, drains E (scaled).

40.12 Point for the center 1/4 sec. cor. of sec. 33, at intersection with the E. and W. center line.

Set an stainless steel post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

Survey of the Subdivision of Section 33,  
T. 42 S., R. 1 W., Salt Lake Meridian, Utah

T 42 S R 1 W  
C 1/4 S 33  
1987

79.65 The 1/4 sec. cor. of secs. 28 and 33.

---

From the 1/4 sec. cor. of secs. 33 and 34.

N. 89° 10' W., on the E. and W. center line of sec. 33.

20.215 Point for the center E. 1/16 sec. cor. of sec. 33.

Cor. falls on the E. bank of the Paria River in an area subject to frequent flooding.

28.865 Point selected for the witness cor. to the center E. 1/16 sec. cor. of sec. 33.

Set an stainless steel post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

W C  
T 42 S R 1 W  
E 1/16  
C ——— S 33 ———> C  
1987

Cor. set atop dike which bears N. 64° W. and S. 64° E.

40.43 The center 1/4 sec. cor. of sec. 33.

50.00 W. channel of Paria River, drains SSW (scaled).

58.50 Dirt road, bears NE and SW (scaled).

60.465 Point for the center W 1/16 sec. cor. of sec. 33.

Set an stainless steel post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 42 S R 1 W  
W 1/16  
C ——— S 33 ——— C  
1987

Raise a mound of stone N. of the cor.

Survey of the Subdivision of Section 33,  
T. 42 S., R. 1 W., Salt Lake Meridian, Utah

80.50 The 1/4 sec. cor. of secs. 32 and 33.

---

From the true point for the center E. 1/16 sec. cor. of sec. 33.  
N. 0° 18' W., on the N. and S. center line of the NE. 1/4 of sec.  
33.

14.00 Paria River, drains SW (scaled).

22.00 Paria River, drains E (scaled).

39.56 The E. 1/16 sec. cor. of secs. 28 and 33.

---

From the center W. 1/16 sec. cor. of sec. 33.

North, on the N. and S. center line of the NW. 1/4 of sec. 33.

39.50 The W. 1/16 sec. cor. of secs. 28 and 33.

---

#### GENERAL DESCRIPTION

The area surveyed in Township 42 South, Range 1 West is located approximately 14 miles west of the town of Big Water, Utah. U.S. Highway No. 89 passes through section 33. The elevation varies from 5000 feet on rolling benchlands in the eastern portion of section 28 to 4400 feet where the Paria River leaves the township near the southeast corner of section 33. The native vegetation consists of low sage on the higher clay benches and big sagebrush, willow, and cottonwood along the river bottom. The entire area drains to the Paria River which runs from northwest to southeast through sections 28 and 33. The level portions of these sections are used as pasture with small areas under cultivation.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Ferrel D. Reynolds	Surveying Technician
Larry V. Judd	Surveying Technician

## CERTIFICATE OF SURVEY

I, Richard A. Zaninovich, Cadastral Surveyor, HEREBY


CERTIFY upon honor that, in pursuance of special instructions date of

the 6th day of March, 1987, I have dependently resurveyed a portion of the south boundary, a portion of the subdivisional lines and surveyed the subdivision of sections 28 and 33 in T. 42 S., R. 1 W

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

August 26, 1987

(Date)

  
(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah


The foregoing field notes of the dependent resurvey of a portion of the south boundary, a portion of the subdivisional lines, and the survey of the subdivision of sections 28 and 33 in T. 42 S., R. 1 W., Salt Lake Meridian, Utah

executed by Richard A. Zaninovich, Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

October 11, 1988

(Date)

  
(Chief, Cadastral Surveyor for Utah)



INDEX DIAGRAM

Township 29 South, Range 3 West

6	5	4	3	2	1
7	8 13	9	10	11	12
18 13	17 9 12	16	15	14	13
19 11	20 8 10	21	22	23	24
30	29 7	28 6	27	26	25
31	32 5	33 4 3	34 2	35	36

- Subdivision of Section 17 - Page 14
- Subdivision of Section 20 - Page 16
- Subdivision of Section 28 - Page 18
- Subdivision of Section 33 - Page 22
- Subdivision of Section 34 - Page 23

## Township 29 South, Range 3 West, Salt Lake Meridian, Utah

The following field notes describe the dependent resurvey of a portion of the south boundary, a portion of the section lines, and a subdivisional survey of sections 17, 20, 28, 33, and 34 in Township 29 South, Range 3 West, Salt Lake Meridian, Utah.

## History of Surveys

	<u>Surveyed by</u>		<u>Retr. or Resurveyed by</u>	
<u>SOUTH BOUNDARY</u>				
Portion	Joseph Gorlinski	1871		
Portion	Breckon and McCarty	1897		
Portion			G.E. Reynolds	1985
<u>SUBDIVISION</u>				
Portion	Joseph Gorlinski	1871		
Portion	Breckon and McCarty	1897		
Portion			Breckon and McCarty	1897
Portion			G.E. Reynolds	1985

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 710, Utah, dated May 27, 1987.

The directions of lines were determined by reference to true meridians established on line by altitude observations on the sun, and by hour angle observations on Polaris. The lines were carried forward by sustained angulations, being supplemented by other observations on Polaris taken throughout the progress of the survey. Distances were determined by electronic measurement.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions, lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the southeast corner of section 34 as determined from a tie made to U.S.G.S. triangulation station "Lake 1944", located in section 28, T. 28 S., R. 3 W., and a tie made to the corner of sections 9, 10, 15 and 16, T. 29 S., R. 3 W., "B.L.M. Control Station 1985" is

Latitude  $38^{\circ} 14' 15.44''$  N.      Longitude  $112^{\circ} 10' 37.98''$  W.  
N.A.D. 1927

Township 29 South, Range 3 West, Salt Lake Meridian, Utah

The mean magnetic declination, as projected from the U.S. Geological Survey Magnetic Declination Map of 1980, is 14° E.

---

Dependent Resurvey of a Portion of the South Boundary,  
T. 29 S., R. 3 W., Salt Lake Meridian, Utah

---

(Reestablishment of the Survey Executed by  
Joseph Gorlinski, Deputy Surveyor in 1871)

---

Beginning at the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., set in a mound of stone, with brass cap mkd. as described in the official record of the 1985 resurvey of a portion of the S. bdy. executed by G.E. Reynolds.

N. 88° 58' W., bet. secs. 3 and 34.

Over rolling benchland, through sagebrush and shadscale.

20.325 Point for the E 1/16 sec. cor. of secs. 3 and 34.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

	T 29 S R 3 W
	S 34
E 1/16	S 3
	T 30 S
	1987

Raise a mound of stone, 3 ft. base, 2 ft. high, N of the corner.

34.00 East Shore of Piute Reservoir peninsula, bears NNE and SSW (scaled).

40.65 Point for the 1/4 sec. cor. of secs. 3 and 34, falls in flood plain of Sevier River (south end of reservoir), not monumented.

41.00 East Shore of Piute Reservoir peninsula, bears NNE and SSW (scaled).

48.00 West Shore of Piute Reservoir peninsula, bears N and S (scaled).

52.50 West Shore of Piute Reservoir, bears NE and SW (scaled).

60.975 Point for the W 1/16 sec. cor. of secs. 3 and 34.

Dependent Resurvey of a Portion of the South Boundary,  
T. 29 S., R. 3 W., Salt Lake Meridian, Utah

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 6 ft. base, to top of aluminum cap, mkd.

T 29 S R 3 W  
S 34  
W 1/16 S 3  
T 30 S  
1986

- 81.30 Point for the cor. of secs. 3, 4, 33, and 34, determined latitudinally by the center of dirt road to the west and longitudinally by proportionate measurement.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 5 ft. base, to top of aluminum cap, mkd.

T 29 S R 3 W  
S 33 | S 34  
S 4 | S 3  
T 30 S  
1987

S. 89° 23' W., bet. secs. 4 and 33.

Over nearly level land.

- 40.64 Point for the 1/4 sec. cor. of secs. 4 and 33, at proportionate distance; there is no remaining evidence of the original corner.

Set a bathey, 24 ins. long, 26 ins. in the ground (in road), with cap mkd.

1/4  
S 33  
S 4

from which

A stainless steel post, 30 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground, for a reference monument, bears S. 44° 23' W., 42.4 lks. dist., with brass cap mkd. RM T30S R3W 1/4 S4 28 FT. 1987 and an arrow pointing to the corner.

Dependent Resurvey of a Portion of the South Boundary,  
T. 29 S., R. 3 W., Salt Lake Meridian, Utah

A stainless steel post, 30 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground, for a reference monument, bears N. 45° 37' W., 21.2 lks. dist., with brass cap mkd. RM T29S R3W 1/4 S 33 14 FT. 1987 and an arrow pointing to the corner.

Both reference monuments are located in E-W fence lines.

81.28 The cor. of secs. 4, 5, 32, and 33, determined latitudinally by the center of dirt road, bears E and W, and longitudinally by a fence line, projecting N.

At the corner point

Set a bathey, 24 ins. long, 26 ins. in the ground, with cap mkd.

32	33
5	4

from which

A stainless steel post, 30 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground, for a reference monument, bears S. 54° 23' W., 33.0 lks. dist., with brass cap mkd. RM T30S R3W S5 21.8 FT. 1987 and an arrow pointing to the corner.

A stainless steel post, 30 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground, for a reference monument, bears N. 45° 37' W., 50.0 lks. dist., with brass cap mkd. RM T29S R3W S32 33 FT. 1987 and an arrow pointing to the corner.

---

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 29 S., R. 3 W., Salt Lake Meridian, Utah

---

(Reestablishment of the Survey Executed by  
J. Gorlinski, Deputy Surveyor, in 1871)

---

From the cor. of secs. 3, 4, 33, and 34 on the S bdy. of the Tp., hereinbefore described.

N. 1° 18' W., bet. secs. 33 and 34.

Over rolling hills, through sagebrush and shadscale.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 29 S., R. 3 W., Salt Lake Meridian, Utah

20.285 Point for the S 1/16 sec. cor. of secs. 33 and 34.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 3 W  
S 1/16  
S 33 | S 34  
1987

Raise a mound of stone, 3 ft. base, 2 ft. high, W of the corner.

40.57 The 1/4 sec. cor. of secs. 33 and 34, monumented with an aluminum post, 2 1/2 ins. diam., set in a mound of stone, with aluminum cap mkd. as described in the official record of the 1985 resurvey.

---

From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., hereinbefore described.

N. 0° 34' W., bet. secs. 32 and 33.

Over nearly level farm land.

40.56 The 1/4 sec. cor. of secs. 32 and 33, determined latitudinally by the center of dirt road east and west, and longitudinally by fences to the N and S.

At the corner point

Set a bathey, 18 ins. long, 20 ins. in the ground, with cap mkd.

1/4  
32 | 33

from which

A stainless steel post, 30 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground, for a reference monument, bears N. 44° 23' E., 33 lks. dist., with brass cap mkd. RM T29S R3W 1/4 S33 21.8 FT 1987 and an arrow pointing to the corner.

A stainless steel post, 30 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground, for a reference monument, bears S. 45° 37' E., 33 lks. dist., with brass cap mkd. RM T29S R3W 1/4 S33 21.8 FT 1987 and an arrow pointing to the corner.

---

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 29 S., R. 3 W., Salt Lake Meridian, Utah

N.  $0^{\circ} 54'$  W., beginning new measurement.

- 40.21 The cor. of secs. 28, 29, 32, and 33, marked by the cor. of fence, projecting north and west.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 3 W	
S 29	S 28
S 32	S 33
1987	

Raise a mound of stone, 3 ft. base, 2 ft. high, E of the corner.

---

From the 1/4 sec. cor. of secs. 28 and 33, monumented with an aluminum post, 2 1/2 ins. diam., set in a mound of stone, 5 ft. base, with aluminum cap mkd. as described in the official record of the 1985 resurvey.

S.  $89^{\circ} 18'$  W., bet. secs. 28 and 33.

- 15.48 Point for the west-east-west 1/256 sec. cor. of secs. 28 and 33.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 3 W	
W-E-W 1/256	
S 28	
S 33	
1987	

Raise a mound of stone, 3 ft. base, 2 ft. high, N of the corner.

- 20.64 Point for the W 1/16 sec. cor. of secs. 28 and 33.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 3 W	
S 28	
W 1/16	S 33
1987	

Raise a mound of stone, 3 ft. base, 2 ft. high, N of the corner.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 29 S., R. 3 W., Salt Lake Meridian, Utah

41.28 The cor. of secs. 28, 29, 32, and 33.

---

N. 0° 45' W., bet. secs. 28 and 29.

Over gentle rolling land.

20.155 Point for the S 1/16 sec. cor. of secs. 28 and 29.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 3 W  
S 1/16  
S 29 | S 28  
1987

Set a steal fence post, 6 ft. long, alongside the corner.

Cor. is located in field.

40.31 Point for the 1/4 sec. cor. of secs. 28 and 29, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 3 W  
1/4  
S 29 | S 28  
1987

Raise a mound of stone, 3 ft. base, 2 ft. high, W of the corner.

60.465 Point for the N 1/16 sec. cor. of secs. 28 and 29.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 3 W  
N 1/16  
S 29 | S 28  
1987

60.645 Fence line, bears E and W.

80.62 The cor. of secs. 20, 21, 28, and 29, monumented with an iron post, 2 1/2 ins. diam., set in a collar of stone, with brass cap mkd. as described in the official record of the 1985 resurvey.

---

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 29 S., R. 3 W., Salt Lake Meridian, Utah

N.  $0^{\circ} 57'$  W., bet. secs. 20 and 21.

Over rolling hills, through sagebrush and shadscale.

20.205 Point for the S  $1/16$  sec. cor. of secs. 20 and 21.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 3 W  
S  $1/16$   
S 20 | S 21  
1987

40.41 The  $1/4$  sec. cor. of secs. 20 and 21, monumented with a lava stone, 18x14x10 ins., firmly set and plainly mkd.  $1/4$  on W face.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 3 W  
 $1/4$   
S 20 | S 21  
1987

Deposit the mkd. stone alongside the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of the corner.

N.  $0^{\circ} 56'$  W., beginning new measurement.

40.41 The cor. of secs. 16, 17, 20, and 21, monumented with a lava stone, 10x10x10 ins., firmly set in a mound of stone and plainly mkd. with 4 notches on the E and 3 on the S edges.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 3 W  
S 17 | S 16  
S 20 | S 21  
1987

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 29 S., R. 3 W., Salt Lake Meridian, Utah

Deposit the mkd. stone alongside the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of the corner.

---

N. 0° 17' W., bet. secs. 16 and 17.

Over rolling hills, through sagebrush and shadscale.

17.50 West Shore of Piute Reservoir, bears E and W (scaled).

40.09 Point for the 1/4 sec. cor. of secs. 16 and 17, falls in Piute Reservoir (west shore), not monumented.

55.50 West Shore of Piute Reservoir, bears NNE and SW (scaled).

60.135 Point for the N 1/16 sec. cor. of secs. 16 and 17.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 3 W  
N 1/16  
S 17 | S 16  
1987

Raise a mound of stone, 3 ft. base, 2 ft. high, W of the corner.

80.18 The cor. of secs. 8, 9, 16, and 17, monumented with a granite stone, 18x8x6 ins., firmly set and plainly mkd. with 4 notches on the S and E edges.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 3 W  
S 8 | S 9  
S 17 | S 16  
1987

Deposit the mkd. stone alongside the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of the corner.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 29 S., R. 3 W., Salt Lake Meridian, Utah

from this corner

U.S.G.S. triangulation station " Lake 1944 ", a standard  
tablet, set in a boulder, bears N.  $50^{\circ} 42.3'$  E., 247.688  
chs. dist.

The corner of secs. 9, 10, 15, and 16 (B.L.M. Control  
Station), an aluminum post, 2 1/2 ins. diam., set in a  
collar of stone, bears S.  $89^{\circ} 14.9'$  E., 82.373 chs. dist.

From the cor. of secs. 20, 21, 28, and 29.

S.  $89^{\circ} 26'$  W., bet. secs. 20 and 29.

Over rolling land, through sagebrush and shadscale.

20.135 Point for the E 1/16 sec. cor. of secs. 20 and 29.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24  
ins. in the ground, with brass cap mkd.

	T 29 S R 3 W
	S 20
E 1/16	<u>S 29</u>
	1987

Raise a mound of stone, 3 ft. base, 2 ft. high, N of the corner.

26.50 Center line of U.S. Highway No. 89, bears N.  $8^{\circ}$  W. and S.  $8^{\circ}$  E.  
(scaled).

40.27 Point for the 1/4 sec. cor. of secs. 20 and 29, at proportionate  
distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 18  
ins. in the ground to bedrock, and in a mound of stone, 3 ft.  
base, to top of aluminum cap, mkd.

	T 29 S R 3 W
	S 20
1/4	<u>S 29</u>
	1987

80.54 The cor. of secs. 19, 20, 29, and 30, monumented with a lava  
stone, 12x12x10 ins., firmly set and plainly mkd. with 5 notches  
on the E and 2 on the S edges.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 29 S., R. 3 W., Salt Lake Meridian, Utah

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 3 W	
S 19	S 20
S 30	S 29
1987	

Deposit the mkd. stone alongside the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of the corner.

---

N. 0° 38' W., bet. secs. 19 and 20.

Over rolling land, through sagebrush and shadscale.

- 40.28 The 1/4 sec. cor. of secs. 19 and 20, monumented with a sandstone, 10x8x8 ins., firmly set and plainly mkd. 1/4 on W face.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 3 W	
1/4	
S 19	S 20
1987	

Deposit the mkd. stone alongside the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of the corner.

---

N. 0° 33' W., beginning new measurement.

- 40.28 The cor. of secs. 17, 18, 19, and 20, monumented with a sandstone, 10x10x8 ins., firmly set and plainly mkd. with 5 notches on the E and 3 on the S edges.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 29 S., R. 3 W., Salt Lake Meridian, Utah

T 29 S R 3 W
S 18   S 17
S 19   S 20
1987

Deposit the mkd. stone alongside the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of the corner.

---

From the cor. of secs. 16, 17, 20, and 21.

S. 89° 15' W., bet. secs. 17 and 20.

Over rolling land, through sagebrush and shadscale.

20.01 Point for the E 1/16 sec. cor. of secs. 17 and 20.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 3 W
E 1/16    S 17
S 20
1987

Raise a mound of stone, 3 ft. base, 2 ft. high, N of the corner.

36.50 Center line of U.S. Highway No. 89, bears N. 8° W. and S. 8° E. (scaled).

40.02 Point for the 1/4 sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 3 W
1/4        S 17
S 20
1987

Raise a mound of stone, 3 ft. base, 2 ft. high, N of the corner.

80.04 The cor. of secs. 17, 18, 19 and 20.

---

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 29 S., R. 3 W., Salt Lake Meridian, Utah

N. 0° 49' W., bet. secs. 17 and 18.

Over rolling hills, through sagebrush and shadscale.

- 40.43 The 1/4 sec. cor. of secs. 17 and 18, monumented with a lava stone, 18x12x12 ins., firmly set and plainly mkd. 1/4 on W face.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 3 W  
1/4  
S 18 | S 17  
1987

Deposit the mkd. stone alongside the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of the corner.

N. 0° 08' E., beginning new measurement.

- 40.12 The cor. of secs. 7, 8, 17, and 18, monumented with a granite stone, 18x10x4 ins., firmly set in a mound of stone and plainly mkd. with 5 notches on the E and 4 on the S edges. There is no remaining evidence of the original bearing tree.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., on bedrock, and in a mound of stone, 6 ft. base, to top of aluminum cap, mkd.

T 29 S R 3 W  
S 7 | S 8  
S 18 | S 17  
1987

From the cor. of secs. 8, 9, 16, and 17.

S. 89° 31' W., bet. secs. 8 and 17.

Over rolling land, through sagebrush and shadscale.

- 20.025 Point for the E 1/16 sec. cor. of secs. 8 and 17.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 29 S., R. 3 W., Salt Lake Meridian, Utah

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24  
ins. in the ground, with brass cap mkd.

T 29 S R 3 W  
S 8  
E 1/16  $\frac{S 17}{1987}$

Raise a mound of stone, 3 ft. base, 2 ft. high, N of the corner.

38.00 Center line of U.S. Highway No. 89, bears N and S (scaled).

40.05 Point for the 1/4 sec. cor. of secs. 8 and 17, at proportionate  
distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24  
ins. in the ground, with brass cap mkd.

T 29 S R 3 W  
S 8  
1/4  $\frac{S 17}{1987}$

Raise a mound of stone, 3 ft. base, 2 ft. high, N of the corner.

80.10 The cor. of secs. 7, 8, 17 and 18.

Survey of the Subdivision of Section 17,  
T. 29 S., R. 3 W., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 17 and 20.

N. 0° 19' W., on the N-S center line of sec. 17.

40.26 Point for the center 1/4 sec. cor. of sec. 17, at intersection  
with the E and W center line.

Set a rebar on the W edge of U.S. Highway No. 89, flush with the  
surface.

from which

A stainless steel post, 30 ins. long, 2 1/2 ins. diam.,  
set 22 ins. in the ground, for a reference monument, bears  
N. 45° 30' W., 175.8 lks. dist., with brass cap mkd. RM  
T29S R3W C 1/4 S17 116 FT 1987 and an arrow pointing to  
the corner.

Survey of the Subdivision of Section 17,  
T. 29 S., R. 3 W., Salt Lake Meridian, Utah

A stainless steel post, 30 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground, for a reference monument, bears S. 49° 30' W., 154.5 lks. dist., with brass cap mkd. RM T29S R3W C 1/4 S17 102 FT 1987 and an arrow pointing to the corner.

60.31 Point for the center N 1/16 sec, cor. of sec. 17.

Set a rebar on the W edge of U.S. Highway No. 89, flush with the surface.

from which

A stainless steel post, 30 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground, with a mound of stone, 3 ft. base, 2 ft. high, W of the corner, for a reference monument, bears S. 45° W., 121.2 lks. dist., with brass cap mkd. RM T29S R3W CN 1/16 S17 80 FT 1987 and an arrow pointing to the corner.

A stainless steel post, 30 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground and in a collar of stone, for a reference monument, bears N. 45° W., 100.0 lks. dist., with brass cap mkd. RM T29S R3W CN 1/16 S17 66 FT 1987 and an arrow pointing to the corner.

80.36 The 1/4 sec. cor. of secs. 8 and 17.

---

From the point for the 1/4 sec. cor. of secs. 16 and 17.

S. 89° 30' W., on the E-W center line of sec. 17.

2.00 West Shore of Piute Reservoir, bears N and S (scaled).

20.015 Point for the center E 1/16 sec. cor. of sec. 17.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{T 29 S R 3 W} \\ \text{E 1/16} \\ \hline \text{C S 17 C} \\ \text{1987} \end{array}$$

Raise a mound of stone, 3 ft. base, 2 ft. high, N of the corner.

40.03 The center 1/4 sec. cor. of sec. 17.

80.40 The 1/4 sec. cor. of secs. 17 and 18.

---

Survey of the Subdivision of Section 17,  
T. 29 S., R. 3 W., Salt Lake Meridian, Utah

From the center E 1/16 sec. cor. of sec. 17.

N. 0° 18' W., on the N-S center line of the NE 1/4 of sec. 17.

- 20.05 Point for the NE 1/16 sec. cor. of sec. 17, at intersection with the E and W center line of the NE 1/4.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 3 W  
NE 1/16 S 17  
1987

Raise a mound of stone, 3 ft. base, 2 ft. high, W of the corner.

- 40.10 The E 1/16 sec. cor. of secs. 8 and 17.
- 

From the N 1/16 sec. cor. of secs. 16 and 17.

S. 89° 30' W., on the E-W center line of the NE 1/4 of sec. 17.

- 20.02 The NE 1/16 sec. cor. of sec. 17.

- 40.04 The center N 1/16 sec. cor. of sec. 17.
- 

From the E 1/16 sec. cor. of secs. 17 and 20.

N. 0° 18' W., on the N-S center line of the SE 1/4 of sec. 17.

- 40.18 The center E 1/16 sec. cor. of sec. 17.
- 

Survey of the Subdivision of Section 20,  
T. 29 S., R. 3 W., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 20 and 29.

N. 0° 46' W., on the N-S center line of sec. 20.

- 20.17 Point for the center S 1/16 sec. cor. of sec. 20.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivision of Section 20,  
T. 29 S., R. 3 W., Salt Lake Meridian, Utah

T 29 S R 3 W  
C  
S 1/16 | S 20  
C  
1987

Raise a mound of stone, 3 ft. base, 2 ft. high, W of the cor.

- 40.34 Point for the center 1/4 sec. cor. of sec. 20, at intersection with the E and W center line.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 3 W  
C 1/4 S 20  
1987

Raise a mound of stone, 3 ft. base, 2 ft. high, W of the corner.

- 80.69 The 1/4 sec. cor. of secs. 17 and 20.

From the 1/4 sec. cor. of secs. 20 and 21.

S. 89° 20' W., on the E-W center line of sec. 20.

- 20.07 Point for the center E 1/16 sec. cor. of secs. 20.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 3 W  
E 1/16  
C ——— S 20 C  
1987

Raise a mound of stone, 3 ft. base, 2 ft. high, N of the corner.

- 31.50 Center line of U.S. Highway No. 89, bears N. 8° W. and S. 8° E. (scaled).

- 40.14 The center 1/4 sec. cor. of sec. 20.

- 80.32 The 1/4 sec. cor. of secs. 19 and 20.

Survey of the Subdivision of Section 20,  
T. 29 S., R. 3 W., Salt Lake Meridian, Utah

From the E 1/16 sec. cor. of secs. 20 and 29.

N. 0° 52' W., on the N-S center line of the SE 1/4 of sec. 20.

- 20.19 Point for the SE 1/16 sec. cor. of sec. 20, at intersection with the E and W center line of the SE 1/4.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 3 W  
SE 1/16 S 20  
1987

Raise a mound of stone, 3 ft. base, 2 ft. high, N of the corner.

- 40.38 The center E 1/16 sec. cor. of sec. 20.

From the S 1/16 sec. cor. of secs. 20 and 21.

S. 89° 23' W., on the E-W center line of the SE 1/4 of sec. 20.

- 20.10 The SE 1/16 sec. cor. of sec. 20.

- 29.00 Center line of U.S. Highway No. 89, bears N. 8° W. and S. 8° E. (scaled).

- 40.20 The center S 1/16 sec. cor. of sec. 20.

Survey of the Subdivision of Section 28,  
T. 29 S., R. 3 W., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 28 and 33.

N. 1° 18' W., on the N-S center line of sec. 28.

- 19.91 Point for the center S 1/16 sec. cor. of sec. 28.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

Survey of the Subdivision of Section 28,  
T. 29 S., R. 3 W., Salt Lake Meridian, Utah

T 29 S R 3 W  
C  
S 1/16 | S 28  
C  
1987

Raise a mound of stone, 3 ft. base, 2 ft. high, W of the corner.

- 39.82 Point for the center 1/4 sec. cor. of sec. 28, at intersection with the E and W center line.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 3 W  
C 1/4 S 28  
1987

Raise a mound of stone, 3 ft. base, 2 ft. high, W of the corner.

- 59.855 Point for the center N 1/16 sec. cor. of sec. 28.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 5 ft. base, to top of aluminum cap, mkd.

T 29 S R 3 W  
C  
N 1/16 | S 28  
C  
1987

- 79.89 The 1/4 sec. cor. of secs. 21 and 28, monumented with an aluminum post, 2 1/2 ins. diam., set in a mound of stone, with aluminum cap mkd. as described in the official record of the 1985 resurvey.

---

From true point for the 1/4 sec. cor. of secs. 27 and 28 from which the witness cor. bears S. 10° 22.8' E., 1.000 ch. dist., monumented with an aluminum post, 2 1/2 ins. diam., set in a collar of stone, with aluminum cap mkd. as described in the official record of the 1985 resurvey.

West, on the E-W center line of sec. 28.

- 0.50 West Shore of Piute Reservoir, bears N and SE (scaled).

- 20.27 Point for the center E 1/16 sec. cor. of sec. 28.

Survey of the Subdivision of Section 28,  
T. 29 S., R. 3 W., Salt Lake Meridian, Utah

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{T 29 S R 3 W} \\ \text{E 1/16} \\ \hline \text{C S 28 C} \\ 1987 \end{array}$$

Raise a mound of stone, 3 ft. base, 2 ft. high, N of the corner.

40.54 The center 1/4 sec. cor. of sec. 28.

60.98 Point for the center W 1/16 sec. cor. of sec. 28.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{T 29 S R 3 W} \\ \text{W 1/16} \\ \hline \text{C S 28 C} \\ 1987 \end{array}$$

Raise a mound of stone, 3 ft. base, 2 ft. high, N of the corner.

81.42 The 1/4 sec. cor. of secs. 28 and 29.

From the center E 1/16 sec. cor. of sec. 28.

N. 1° 21' W., on the N-S center line of the NE 1/4 of sec. 28.

19.975 Point for the NE 1/16 sec. cor. of sec. 28, at intersection with the E and W center line of the NE 1/4.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 5 ft. base, to top of aluminum cap, mkd.

$$\begin{array}{c} \text{T 29 S R 3 W} \\ \text{NE 1/16 S 28} \\ 1987 \end{array}$$

33.50 West Shore of Piute Reservoir, bears E and W (scaled).

39.95 The point for the E 1/16 sec. cor. of secs. 21 and 28, not monumented, as described in the official record of the 1985 resurvey.

Survey of the Subdivision of Section 28,  
T. 29 S., R. 3 W., Salt Lake Meridian, Utah

From the point for the N 1/16 sec. cor. of secs. 27 and 28, not monumented, as described in the official record of the 1985 resurvey

- N. 89° 50' W., on the E-W center line of the NE 1/4 of sec. 28.
- 10.50 West Shore of Piute Reservoir, bears N and S (scaled).
- 20.26 The NE 1/16 sec. cor. of sec. 28.
- 40.52 The center N 1/16 sec. cor. of sec. 28.
- 

From the W 1/16 sec. cor. of secs. 28 and 33.

- N. 1° 02' W., on the N-S center line of the SW 1/4 of sec. 28.
- 20.03 Point for the SW 1/16 sec. cor. of sec. 28, at intersection with the E and W center line of the SW 1/4.
- Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 3 W  
SW 1/16 S 28  
1987

- Raise a mound of stone, 3 ft. base, 2 ft. high, W of the corner.
- 40.06 The center W 1/16 sec. cor. of sec. 28.
- 

From the center S 1/16 sec. cor. of sec. 28.

- S. 89° 39' W., on the E-W center line of the SW 1/4 of sec. 28.
- 15.405 Point for the center-west-east-southwest 1/256 sec. cor. of sec. 28.
- Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 3 W  
C-W-E-SW 1/256  
S 28  
1987

- Raise a mound of stone, 3 ft. base, 2 ft. high, N of the corner.
- 20.54 The SW 1/16 sec. cor. of sec. 28.

Survey of the Subdivision of Section 28,  
T. 29 S., R. 3 W., Salt Lake Meridian, Utah

41.08 The S 1/16 sec. cor. of secs. 28 and 29.

---

From the center W 1/16 sec. cor. of sec. 28.

N. 1° 02' W., on the N-S center line of the NW 1/4 of sec. 28.

20.095 Point for the NW 1/16 sec. cor. of sec. 28, at intersection with the E and W center line of the NW 1/4.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 3 W  
NW 1/16 S 28  
1987

Raise a mound of stone, 3 ft. base, 2 ft. high, W of the corner.

40.19 The W 1/16 sec. cor. of secs. 21 and 28, monumented with a stainless steel post, 2 1/2 ins. diam., projecting 6 ins. above ground, with brass cap as described in the official record of the 1985 resurvey.

---

From the center N 1/16 sec. cor. of sec. 28.

N. 89° 50' W., on the E-W center line of the NW 1/4 of sec. 28.

20.34 The NW 1/16 sec. cor. of sec. 28.

40.68 The N 1/16 sec. cor. of secs. 28 and 29.

---

Survey of the Subdivision of Section 33,  
T. 29 S., R. 3 W., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 4 and 33, on the S. bdy. of the Tp., hereinbefore described.

N. 0° 17' W., on the N-S center line of sec. 33.

40.57 Point for the center 1/4 sec. cor. of sec. 33, at intersection with the E and W center line.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 30 ins. in the ground, with brass cap mkd.

T 29 S R 3 W  
C 1/4 S 33  
1987

Survey of the Subdivision of Section 33,  
T. 29 S., R. 3 W., Salt Lake Meridian, Utah

Cor. is located in dirt road, bears E and W, and at S edge of cultivated field.

60.70 Point for the center N 1/16 sec. cor. of sec. 33.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 3 W  
C  
N 1/16 | S 33  
C  
1987

Raise a mound of stone, 3 ft. base, 2 ft. high, W of the corner.

80.83 The 1/4 sec. cor. of secs. 28 and 33.

---

From the 1/4 sec. cor. of secs. 33 and 34.

S. 89° 23' W., on the E-W center line of sec. 33.

39.92 The center 1/4 sec. cor. of sec. 33.

80.76 The 1/4 sec. cor. of secs. 32 and 33.

---

From the N 1/16 sec. cor. of secs. 33 and 34, monumented with a stainless steel post, 2 1/2 ins. diam., projecting 6 ins. above the ground, with brass cap mkd. as described in the official record of the 1985 resurvey.

S. 89° 42' W., on the E-W center line of the NE 1/4 of sec. 33.

40.27 The center N 1/16 sec. cor. of sec. 33.

---

Survey of the Subdivision of Section 34,  
T. 29 S., R. 3 W., Salt Lake Meridian, Utah

---

From the point for the 1/4 sec. cor. of secs. 3 and 34, on the S. bdy. of the Tp., hereinbefore described.

N. 0° 29' W., on the N-S center line of sec. 34.

1.00 East Shore of Piute Reservoir peninsula, bears NE and SW (scaled).

8.00 North Shore of Piute Reservoir peninsula, bears W and SE (scaled).

Survey of the Subdivision of Section 34,  
T. 29 S., R. 3 W., Salt Lake Meridian, Utah

- 20.165 Point for the center S 1/16 sec. cor. of sec. 34, falls in Piute Reservoir, not monumented.
- 40.33 Point for the center 1/4 sec. cor. of sec. 34, at intersection with the E and W center line, falls in Piute Reservoir, not monumented.
- 51.50 East Shore of Piute Reservoir, bears NNW and SSE (scaled).
- 59.18 Point for the center N 1/16 sec. cor. of sec. 34.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 3 W  
C  
N 1/16 | S 34  
C  
1987

Raise a mound of stone, 3 ft. base, 2 ft. high, W of the corner.

- 78.03 The 1/4 sec. cor. of secs. 27 and 34, monumented with an iron post, 2 1/2 ins. diam., set in a collar of stone, with brass cap mkd. as described in the official record of the 1985 resurvey.

From the 1/4 sec. cor. of secs. 34 and 35, monumented with an iron post, 2 1/2 ins. diam., set in a mound of stone, with brass cap mkd. as described in the official record of the 1985 resurvey.

N. 88° 40' W., on the E-W center line of sec. 34.

- 20.155 Point for the center E 1/16 sec. cor. of secs. 34.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 3 W  
E 1/16  
C ——— C  
S 34  
1987

Raise a mound of stone, 3 ft. base, 2 ft. high, N of the corner.

- 35.00 East Shore of Piute Reservoir, bears NNW and SSE (scaled).
- 40.31 The point for the center 1/4 sec. cor. of sec. 34.

Survey of the Subdivision of Section 34,  
T. 29 S., R. 3 W., Salt Lake Meridian, Utah

- 60.925 Point for the center W 1/16 sec. cor. of sec. 34, falls in Piute Reservoir, not monumented.
- 63.00 West Shore of Piute Reservoir, bears NNW and SSE (scaled).
- 81.54 The 1/4 sec. cor. of secs. 33 and 34.

From the center E 1/16 sec. cor. of sec. 34.

N. 0° 44' W., on the N-S center line of the NE 1/4 of sec. 34.

- 19.46 Point for the NE 1/16 sec. cor. of sec. 34, at intersection with the E and W center line of the NE 1/4.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 3 W  
NE 1/16 S 34  
1987

Raise a mound of stone, 3 ft. base, 2 ft. high, N of the corner.

- 38.92 The E 1/16 sec. cor. of secs. 27 and 34, monumented with a stainless steel post, 2 1/2 ins. diam., projecting 6 ins. above the ground, with brass cap mkd. as described in the official record of the 1985 resurvey.

From the N 1/16 sec. cor. of secs. 34 and 35, monumented with a stainless steel post, 2 1/2 ins. diam., projecting 6 ins. above the ground, with brass cap mkd. as described in the official record of the 1985 resurvey.

S. 89° 36' W., on the E-W center line of the NE 1/4 of sec. 34.

- 20.055 The NE 1/16 sec. cor. of sec. 34.

- 40.11 The center N 1/16 sec. cor. of sec. 34.

From the E 1/16 sec. cor. of secs. 3 and 34, on the S. bdy. of the Tp., hereinbefore described.

N. 0° 44' W., on the N-S center line of the SE 1/4 of sec. 34.

- 40.24 The center E 1/16 sec. cor. of secs. 34.

Survey of the Subdivision of Section 34,  
T. 29 S., R. 3 W., Salt Lake Meridian, Utah

From the W 1/16 sec. cor. of secs. 3 and 34, on the S. bdy. of the Tp., hereinbefore described.

N. 0° 54' W., on the N-S center line of the SW 1/4 of sec. 34.

20.225 Point for the SW 1/16 sec. cor. of sec. 34, at intersection with the E and W center line of the SW 1/4.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 3 W  
SW 1/16 S 34  
1987

Raise a mound of stone, 3 ft. base, 2 ft. high, W of the corner.

30.50 West Shore of Piute Reservoir, bears NNW and SSE (scaled).

40.45 The point for the center W 1/16 sec. cor. of sec. 34.

From the point for the center S 1/16 sec. cor. of sec. 34.

N. 88° 49' W., on the E-W center line of the SW 1/4 of sec. 34.

17.50 West Shore of Piute Reservoir, bears N and S (scaled).

20.47 The SW 1/16 sec. cor. of sec. 34.

40.94 The S 1/16 sec. cor. of secs. 33 and 34.

#### General Description

The dependently resurveyed sections in T. 29 S., R. 3 W., contain gentle rolling benchland along the Piute Reservoir to broken and mountainous terrain at higher elevation. The elevation ranges from about 6000 ft. at the reservoir to 7000 ft. above sea level on the slopes. The soil varies from sandy clay loam at lower elevations to very rocky on the higher slopes. The vegetation consists of sagebrush, shadscale, native grasses, pinon, juniper and some cottonwood growth along the Sevier River, which flows in a northerly direction. There are several trail roads within the resurveyed area and U.S. Highway No. 89 runs nearly N and S through sections 17 and 20. The principal use appears to be livestock grazing.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

## FIELD ASSISTANTS

Ferrel D. Reynolds	Surveying Technician
Larry V. Judd	Surveying Technician
Lewis B. Roberts	Survey Aid

## CERTIFICATE OF SURVEY

I, Richard A. Zaninovich, Cadastral Surveyor , HEREBY

CERTIFY upon honor that, in pursuance of special instructions date of

the 27th day of May , 1987, I have dependently resurveyed a portion of the south boundary, a portion of the section lines, and surveyed the subdivision of sections 17, 20, 28, 33, and 34 in T. 29 S., R. 3 W.

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

September 27, 1988

(Date)

  
\_\_\_\_\_  
(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah


The foregoing field notes of the dependent resurvey of a portion of the south boundary, a portion of the section lines, and the survey of the subdivision of sections 17, 20, 28, 33, and 34 in T. 29 S., R. 3 W., Salt Lake Meridian, Utah

executed by Richard A. Zaninovich, Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

October 11, 1988

(Date)

  
\_\_\_\_\_  
(Chief, Cadastral Surveyor for Utah)



INDEX DIAGRAM

Township 17 South, Range 5 West

		7	7	6	
6	5 32	4 24	3 16	2	1
		31	23	16	10
					5
7	8 30	9 23	10 15	11 10	12
		30	22	14	9
18	17 29	16 21	15 13	14 9	13
		28	20	12	
19	20 28	21 19	22	23	24
		27	19		
30	29 26	28 18	27 11	26	25
		25	17		
31	32 24	33 16	34 11	35	36
		3	2		

- Subdivision of Section 3 - Page 32
- Subdivision of Section 4 - Page 33
- Subdivision of Section 9 - Page 34
- Subdivision of Section 10 - Page 35
- Subdivision of Section 11 - Page 36
- Subdivision of Section 12 - Page 38
- Subdivision of Section 14 - Page 40
- Subdivision of Section 15 - Page 41
- Subdivision of Section 21 - Page 43
- Subdivision of Section 27 - Page 45
- Subdivision of Section 28 - Page 48
- Subdivision of Section 33 - Page 50
- Subdivision of Section 34 - Page 53

## Township 17 South, Range 5 West, Salt Lake Meridian, Utah

The following field notes describe the dependent resurvey of portions of the north, south and east boundaries, portions of the subdivisional lines and the subdivision of sections 3, 4, 9, 10, 11, 12, 14, 15, 21, 27, 28, 33, and 34 of Township 17 South, Range 5 West, Salt Lake Meridian, Utah.

History of Surveys

		<u>Surveyed by</u>	<u>Retr. or Resurveyed by</u>	
<u>NORTH BOUNDARY</u>				
All	F. Dickert	1870	Thoma and Miller	1920
Portion				
<u>SOUTH BOUNDARY</u>				
Portion	F. Dickert	1870		
Portion	H.W. Miller	1920	Thoma and Miller	1920
Portion				
<u>EAST BOUNDARY</u>				
Portion	F. Dickert	1870		
Portion	H.W. Miller	1920	Thoma and Miller	1920
Portion				
<u>WEST BOUNDARY</u>				
All	J. Bausman	1869	J.C. Thoma	1920
All				
<u>SUBDIVISION</u>				
Portion	F. Dickert	1870		
Portion	Thoma and Miller	1920	Thoma and Miller	1920
Portion				

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 699, Utah, dated November 21, 1986.

The directions of lines were determined by reference to true meridians established on line by altitude observations on the sun, and by hour angle observations on Polaris. The lines were carried forward by sustained angulations, being supplemented by other observations on Polaris taken throughout the progress of the survey. Distances were determined by electronic measurement.

Township 17 South, Range 5 West, Salt Lake Meridian, Utah

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions, lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the southeast corner of sec. 34, as determined from a tie made to U.S.F.S and U.S.C. & G.S. Triangulation Station No. "M 11 1919", located in section 1, T. 18 S., R. 5 W., is:

Latitude  $39^{\circ} 17' 18.81''$  N.      Longitude  $112^{\circ} 23' 18.13''$  W.  
NAD 27

The mean magnetic declination, as projected from the U.S. Geological Survey Magnetic Declination Map of 1980, is  $14 \frac{1}{2}^{\circ}$  E.

Dependent Resurvey of a Portion of the South Boundary,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

(Reestablishment of the Survey Executed by  
J.C. Thoma and H.W. Miller, Deputy Surveyors in 1920)

Beginning at the cor. of secs. 2, 3, 34, and 35, monumented with an iron post, 2 ins. in diam., with brass cap, mkd. as described in the official record of the 1920 survey, from which the original bearing trees;

A cedar, 12 ins. diam., bears S.  $80^{\circ}$  E., 226 lks. dist.,  
mkd. T18S R5W S2 BT (record, S.  $38 \frac{3}{4}^{\circ}$  E.).

A cedar, 12 ins. diam., bears S.  $40^{\circ}$  W., 99 lks. dist.,  
mkd. T18S R5W S3 BT (record, S.  $58 \frac{1}{4}^{\circ}$  W.).

The north bearing trees have been railed out.

From this same corner

U.S.F.S. and U.S.C. & G.S. Triangulation Station No. "M 11",  
bears S.  $77^{\circ} 09'$  E., 79.55 chs. dist., a standard brass  
tablet mkd. U.S.F.S. No. M 11 1919.

N.  $89^{\circ} 52'$  W., bet. secs. 3 and 34.

Dependent Resurvey of a Portion of the South Boundary,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

Over rolling desert land, through sagebrush, shadscale and scattered juniper growth.

29.00 Asphalt road, bears N. 90° E. and S. 90° W (scaled).

40.12 The 1/4 sec. cor. of secs. 3 and 34, monumented with a cedar post, 18x2x2 ins., set 8 ins. in the ground, with faint scribe marks on the N edge.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

	T 17 S R 5 W
	S 34
1/4	S 3
	T 18 S
	1987

Deposit the mkd. post, alongside the aluminum post.

---

(Reestablishment of the Survey Executed by  
F. Dickert, Deputy Surveyor in 1870)

---

S. 89° 49' W.,. beginning new measurement.

40.25 Point for the cor. of secs. 3, 4, 33, and 34, at proportionate dist., there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

	T 17 S R 5 W
	S 33   S 34
	S 4   S 3
	T 18 S
	1987

---

S. 89° 49' W., bet. secs. 4 and 33.

Over rolling desert land, through sagebrush and shadscale.

20.125 Point for the E 1/16 sec. cor. of secs. 4 and 33.

Dependent Resurvey of a Portion of the South Boundary,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
S 33  
E 1/16 S 4  
T 18 S  
1987

40.25 Point for the 1/4 sec. cor. of secs. 4 and 33, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
S 33  
1/4 S 4  
T 18 S  
1987

60.375 Point for the W 1/16 sec. cor. of secs. 4 and 33.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
S 33  
W 1/16 S 4  
T 18 S  
1987

80.50 The cor. of secs. 4, 5, 32, and 33, mkd. by the cor. of fence, projecting west and north.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
S 32 | S 33  
S 5 | S 4  
T 18 S  
1987

Dependent Resurvey of a Portion of the South Boundary,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

From this cor., the cor. of Tps. 17 and 18 S., Rs. 5 and 6 W., bears N.  $89^{\circ} 38'$  W., 161.51 chs. dist., monumented with an iron post, 3 ins. diam., projecting 4 ins. above ground, with brass cap, mkd. as described in the official record of the 1941 survey. This cor. has been designated as a tri-station by U.S.G.S.

Cor. is located on N edge of dirt road, bears E and W.

---

Dependent Resurvey of a Portion of the East Boundary,  
T. 17 S., R. 5 W. Salt Lake Meridian, Utah

---

(Reestablishment of the Survey Executed by  
J.C. Thoma and H.W. Miller, Deputy Surveyors in 1920)

From the 1/4 sec. cor. of secs. 7 and 12, monumented with an aluminum post (Forest Service), with cap mkd.

T 17 S  
R 5 W R 4 W  
1/4  
S 12 | S 7  
L S 4876  
1981

This is accepted as a careful and faithful perpetuation of the original corner.

N.  $0^{\circ} 06'$  W., bet. secs. 7 and 12.

Over rolling desert land, through scattered juniper growth.

20.38 Point for the N 1/16 sec. cor. of secs. 7 and 12.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S  
R 5 W R 4 W  
N 1/16  
S 12 | S 7  
1987

39.75 Center line of Utah State Highway No. 125, bears N.  $60^{\circ}$  E. and S.  $60^{\circ}$  W. (scaled).

Dependent Resurvey of a Portion of the East Boundary,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

40.76 The cor. of secs. 1, 6, 7, and 12, monumented with an iron post, 2 ins. diam., with brass cap, mkd. as described in the official record of the 1920 survey, from which the original bearing trees

A juniper, 10 ins. diam., bears N. 36 1/2° E., 16 lks.  
dist., mkd. T17S R4W S6 BT.

A juniper, 14 ins. diam., bears N. 41 1/4° W., 100 lks.  
dist., mkd. T17S R5W S1 BT.

---

Dependent Resurvey of a Portion of the North Boundary,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

---

(Reestablishment of the Survey Executed by F. Dickert,  
Deputy Surveyor in 1870)

From the cor. of secs. 1, 2, 35, and 36, (Millard County Cor.) monumented with an iron post, 2 ins. diam., projecting 8 ins. above ground and in a collar of stone, also a quartzite stone, 14x12x10 ins., mkd. with 5 notches on the W and 1 on the E edges, set alongside the iron post. There is no remaining evidence of the original bearing trees. The brass cap is mkd.

R 5 W  
T 16 S  
S 35 | S 36  
S 2 | S 1  
T 17 S SLBM  
L S 1623  
1982

Cor. is located in fence line, bears E and W.

N. 89° 56' W., bet. secs. 2 and 35.

Over rolling desert land, through sagebrush and shadscale.

40.61 Point for the 1/4 sec. cor. of secs. 2 and 35, at proportionate distance; there is no remaining evidence of the original corner.

T 16 S R 5 W  
S 35  
1/4 S 2  
T 17 S  
1987

Raise a mound of stone, 3 ft. base, 2 ft. high, N of the cor.

Dependent Resurvey of a Portion of the North Boundary,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

- 81.22 Point for the cor. of secs. 2, 3, 34, and 35, at proportionate dist., there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 16 S R 5 W
S 34   S 35
<u>S 3   S 2</u>
T 17 S
1987

N. 89° 56' W., bet. secs. 3 and 34.

Over rolling desert land, through sagebrush and shadscale.

- 40.61 Point for the 1/4 sec. cor. of secs. 3 and 34, at proportionate distance; there is no remaining evidence of the original corner.

Set a steel fence post, 5 1/2 ft. long, flush with the surface and place an aluminum post, 30 ins. long, 2 1/2 ins. diam., over the steel post, with aluminum cap mkd.

T 16 S R 5 W
S 34
1/4 <u>S 3</u>
T 17 S
1987

Cor. is located on rolling sand dunes.

- 81.22 Point for the cor. of secs. 3, 4, 33, and 34, at proportionate dist., there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 16 S R 5 W
S 33   S 34
<u>S 4   S 3</u>
T 17 S
1987

N. 89° 56' W., bet. secs. 4 and 33.

Over rolling desert land, through sagebrush and shadscale.

Dependent Resurvey of a Portion of the North Boundary,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

- 40.61 Point for the 1/4 sec. cor. of secs. 4 and 33, at proportionate distance; there is no remaining evidence of the original corner.

$$\begin{array}{r} T 16 S R 5 W \\ \quad S 33 \\ 1/4 \quad \frac{S 4}{T 17 S} \\ \quad 1987 \end{array}$$

- 60.915 Point for the W 1/16 sec. cor. of secs. 4 and 33.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

$$\begin{array}{r} T 16 S R 5 W \\ \quad S 33 \\ W 1/16 \quad \frac{S 4}{T 17 S} \\ \quad 1987 \end{array}$$

- 81.22 Point for the cor. of secs. 4, 5, 32, and 33, at proportionate dist., there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

$$\begin{array}{r} T 16 S R 5 W \\ S 32 \quad | \quad S 33 \\ \frac{S 5 \quad | \quad S 4}{T 17 S} \\ 1987 \end{array}$$

From this cor., the cor. of secs. 5, 6, 31, and 32, monumented with an iron post, 2 ins. diam., with brass cap, mkd. as described in the official record of the 1920 survey, bears N. 89° 56' W., 81.22 chs. dist.

The control line was fully retraced and no evidence of the intervening cor. was found.

---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

---

(Reestablishment of the Survey executed by  
J.C. Thoma and H.W. Miller, Deputy Surveyors in 1920)

---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

From the cor. of secs. 14 and 23 only, monumented with an iron post, 2 ins. diam., with brass cap, mkd. as described in the official record of the 1920 survey.

N.  $0^{\circ} 39'$  E., bet. secs. 13 and 14.

Over rolling desert land, through sagebrush, shadscale and scattered juniper growth.

- 36.86 The 1/4 sec. cor. of secs. 13 only, monumented with an iron post, 1 inch in diam., 12 ins. above ground, with brass cap, mkd. as described in the official record of the 1920 survey.

---

N.  $3^{\circ} 54'$  E.,. beginning new measurement.

- 3.175 The 1/4 sec. cor. of sec. 14 only, monumented with an iron post, 1 inch in diam., 12 ins. above ground, with brass cap, mkd. as described in the official record of the 1920 survey.

---

N.  $0^{\circ} 48'$  W., beginning new measurement.

- 20.305 Point for the N 1/16 sec. cor. of sec. 14 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
N 1/16  
S 14 |  
1987

- 24.00 Asphalt road, bears N.  $28^{\circ}$  E. and S.  $28^{\circ}$  W. (scaled).

- 40.61 The cor. of secs. 11, 12, 13, and 14, monumented with an iron post, 2 ins. diam., 14 ins. above ground, with brass cap, mkd. as described in the official record of the 1920 survey, from which the original bearing tree

A standing dead juniper, 12 ins. diam., bears N.  $29^{\circ}$  E., 271 lks. dist, blazed and scribed, illegible.

---

From the 1/4 sec. cor. of secs. 12 and 13, monumented with an iron post, 1 inch in diam., 10 ins. above ground, with brass cap, mkd. as described in the official record of the 1920 survey.

N.  $89^{\circ} 21'$  W., bet. secs. 12 and 13.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

Over rolling desert land, through sagebrush, shadscale and scattered juniper growth.

32.00 Asphalt road, bears N. 28° E. and S. 28° W. (scaled).

40.40 The cor. of secs. 11, 12, 13, and 14.

N. 0° 22' E., bet. secs. 11 and 12.

Over rolling desert land, through sagebrush, shadscale and scattered juniper growth.

20.375 Point for the S 1/16 sec. cor. of secs. 11 and 12.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
S 1/16  
S 11 | S 12  
1987

40.75 Point for the 1/4 sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
1/4  
S 11 | S 12  
1987

42.66 Center line of Utah State Highway 125, bears E and W.

81.50 The cor. of secs. 1, 2, 11, and 12, monumented with an iron post, 2 ins. diam., 4 ins. above ground, with brass cap, mkd. as described in the official record of the 1920 survey.

From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., heretofore described.

S. 88° 16' W., bet. secs. 1 and 12.

Over rolling desert land, through scattered juniper growth.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

- 43.24 The 1/4 sec. cor. of secs. 1 and 12, monumented with an iron post, 1 inch in diam., 10 ins. above ground, with brass cap, mkd. as described in the official record of the 1920 survey.

Cor. is located 3 lks., E of N-S fence line.

---

S. 88° 14' W., beginning new measurement.

- 43.21 The cor. of secs. 1, 2, 11, and 12.
- 

From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., heretofore described.

N. 40° 28' E., bet. secs. 34 and 35.

Over rolling desert land, through sagebrush, shadscale and scattered juniper growth.

- 38.83 The 1/4 sec. cor. of secs. 34 and 35, monumented with an iron post, 1 inch in diam., 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1920 survey.
- 

N. 1° 03' W.,. beginning new measurement.

- 40.72 The cor. of secs. 26, 27, 34, and 35, monumented with an iron post, 2 ins. diam., 8 ins. above ground, with brass cap, mkd. as described in the official record of the 1920 survey, from which the original bearing tree:

A juniper, 18 ins. diam., bears S. 45 1/2° E., 191 lks.  
dist., mkd. 17S R5W S35 BT.

---

N. 0° 08' E., bet. secs. 26 and 27.

Over rolling desert land, through sagebrush, shadscale and scattered juniper growth.

- 20.365 Point for the S 1/16 sec. cor. of secs. 26 and 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

T 17 S R 5 W  
S 1/16  
S 27 | S 26  
1987

- 40.73 The 1/4 sec. cor. of secs. 26 and 27, monumented with an iron post, 1 inch in diam., 10 ins. above ground, with brass cap, mkd. as described in the official record of the 1920 survey.

---

N. 0° 04' W., beginning new measurement.

- 20.375 Point for the N 1/16 sec. cor. of secs. 26 and 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
N 1/16  
S 27 | S 26  
1987

- 31.00 Asphalt road, bears N. 28° E. and S. 28° W. (scaled).

- 40.75 The cor. of secs. 22, 23, 26, and 27, monumented with an iron post, 2 ins. diam., 12 ins. above ground, with brass cap, mkd. as described in the official record of the 1920 survey, from which the original bearing trees;

A juniper, 40 ins. diam., bears N. 55 3/4° E., 145 lks. dist., mkd. T17S R5W S23 BT.

A juniper, 36 ins. diam., bears S. 35° E., 42 lks. dist., mkd. T17S R5W S26 BT.

A juniper, 30 ins. diam., bears S. 44 1/2° W., 73 lks. dist., mkd. T17S R5W S27 BT.

---

From the cor. of secs. 14 and 23 only.

N. 89° 11' W., bet. secs. 14 and 23.

Over rolling desert land, through sagebrush and shadscale.

- 19.995 Point for the E 1/16 sec. cor. of secs. 14 and 23.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
S 14  
E 1/16 S 23  
1987

- 33.00 Asphalt road, bears N. 28° E. and S. 28° W. (scaled).
- 39.99 The 1/4 sec. cor. of secs. 14 and 23, monumented with an iron post, 1 inch in diam., 10 ins. above ground, with brass cap, mkd. as described in the official record of the 1920 survey, from which the original bearing trees;
- A standing dead juniper, 20 ins. diam., bears N. 36 1/2° E., 115 lks. dist, blazed. No marks visible.
- A standing dead juniper, 16 ins. diam., bears S. 10 1/2° E., 275 lks. dist, blazed. No marks visible.

---

S. 88° 45' W.,. beginning new measurement.

- 40.63 The cor. of secs. 14, 15, 22, and 23, monumented with an iron post, 2 ins. diam., with brass cap, mkd. as described in the official record of the 1920 survey.

---

(Reestablishment of the Survey Executed by  
F. Dickert, Deputy Surveyor in 1870)

---

N. 0° 13' W., bet. secs. 14 and 15.

Over rolling desert land, through sagebrush and shadscale.

- 40.66 Point for the 1/4 sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original corner.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
1/4  
S 15 | S 14  
1987

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

- 81.32 The cor. of secs. 10, 11, 14, and 15, monumented with a squared cedar post, 3 ft. long, 1 ft. above ground, with no visible markings.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 17 S R 5 W	
S 10	S 11
S 15	S 14
1987	

Deposit the squared post alongside the cor.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of the cor.

From the cor. of secs. 11, 12, 13, and 14.

N. 89° 44' W., bet. secs. 11 and 14.

Over rolling desert land, through sagebrush and shadscale.

- 20.245 Point for the E 1/16 sec. cor. of secs. 11 and 14.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W	
S 11	
E 1/16	S 14
1987	

- 40.49 Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W	
S 11	
1/4	S 14
1987	

- 60.735 Point for the W 1/16 sec. cor. of secs. 11 and 14.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

T 17 S R 5 W  
           S 11  
 W 1/16    S 14  
           1987

80.98 The cor. of secs. 10, 11, 14, and 15.

---

N. 1° 32' E., bet. secs. 10 and 11.

Over rolling desert land, through sagebrush and shadscale.

20.35 Point for the S 1/16 sec. cor. of secs. 10 and 11.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 17 S R 5 W  
           S 1/16  
 S 10 | S 11  
           1987

40.70 Point for the 1/4 sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 17 S R 5 W  
           1/4  
 S 10 | S 11  
           1987

41.04 Center line of Utah State Highway No. 125, bears E and W.

81.40 The cor. of secs. 2, 3, 10, and 11, monumented with a squared cedar post, 20x2x2 ins., firmly set, with no visible scribe marks.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
   S 3 | S 2  
 S 10 | S 11  
           1987

---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

From the cor. of secs. 1, 2, 11, and 12.

N. 89° 49' W., bet. secs. 2 and 11.

Over rolling desert land, through sagebrush and shadscale.

- 39.64 Point for the 1/4 sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
S 2  
1/4 S 11  
1987

- 79.28 The cor. of secs. 2, 3, 10, and 11.
- 

N. 10° 58' E., bet. secs. 2 and 3.

Over rolling desert land, through sagebrush and shadscale.

- 41.84 Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
1/4  
S 3 | S 2  
1987

- 84.31 The cor. of secs. 2, 3, 34, and 35 on the N. bdy. of the Tp., heretofore described.
- 

From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., heretofore described.

N. 0° 48' E., bet. secs. 33 and 34.

Over rolling desert land, through sagebrush and shadscale.

- 20.295 Point for the S 1/16 sec. cor. of secs. 33 and 34.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

T 17 S R 5 W  
S 1/16  
S 33 | S 34  
1987

- 40.59 Point for the 1/4 sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
1/4  
S 33 | S 34  
1987

- 60.885 Point for the N 1/16 secs. cor. of secs. 33 and 34.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
N 1/16  
S 33 | S 34  
1987

- 81.18 Point for the cor. of secs. 27, 28, 33, and 34, at proportionate dist., there is no remaining evidence of the original corner.

Set a steal fence post, 5 1/2 ft. long, flush with the surface and place an aluminum post, 30 ins. long, 2 1/2 ins. diam., over the steal post, with aluminum cap mkd.

T 17 S R 5 W  
S 28 | S 27  
S 33 | S 34  
1987

---

From the cor. of secs. 26, 27, 34, and 35.

N. 88° 48' W., bet. secs. 27 and 34.

Over rolling desert land, through sagebrush and shadscale.

- 19.00 Asphalt road, bears N. 90° E. and S. 90° W. (scaled).

- 20.375 Point for the E 1/16 sec. cor. of secs. 27 and 34.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
S 27  
E 1/16 S 34  
1987

- 40.75 Point for the 1/4 sec. cor. of secs. 27 and 34, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
S 27  
1/4 S 34  
1987

- 81.50 The cor. of secs. 27, 28, 33, and 34.

---

N. 0° 10' E., bet. secs. 27 and 28.

Over rolling desert land, through sagebrush and shadscale.

- 40.59 Point for the 1/4 sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner.

Set a steal fence post, 5 1/2 ft. long, flush with the surface and place an aluminum post, 30 ins. long, 2 1/2 ins. diam., over the steal post, with aluminum cap mkd.

T 17 S R 5 W  
1/4  
S 28 | S 27  
1987

Cor. is located in rolling sand dunes.

- 81.18 Point for the cor. of secs. 21, 22, 27, and 28, at proportionate dist., there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

T 17	S	R 5	W
S 21		S 22	
S 28		S 27	
1987			

---

From the cor. of secs. 22, 23, 26, and 27.

N. 89° 01' W., bet. secs. 22 and 27.

Over rolling desert land, through sagebrush and shadscale.

20.32 Point for the E 1/16 sec. cor. of secs. 22 and 27.

Set a steal fence post, 5 1/2 ft. long, flush with the surface and place an aluminum post, 30 ins. long, 2 1/2 ins. diam., over the steal post, with aluminum cap mkd.

	T 17	S	R 5	W
		S 22		
E 1/16		S 27		
1987				

Cor. is located in rolling sand dunes.

40.64 Point for the 1/4 sec. cor. of secs. 22 and 27, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

	T 17	S	R 5	W
		S 22		
1/4		S 27		
1987				

81.28 The cor. of secs. 21, 22, 27, and 28.

---

N. 0° 01' W., bet. secs. 21 and 22.

Over rolling desert land, through sagebrush and shadscale.

20.295 Point for the S 1/16 sec. cor. of secs. 21 and 22.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
S 1/16  
S 21 | S 22  
1987

- 40.59 The 1/4 sec. cor. of secs. 21 and 22, monumented with an iron post, 2 1/2 ins. diam., 8 ins. above ground, and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
1/4  
S 21 | S 22  
1987

Deposit the iron post, alongside the aluminum post.

---

N. 0° 17' W., beginning new measurement.

- 40.48 The cor. of secs. 15, 16, 21, and 22, monumented with an iron post, 2 1/2 ins. diam., 14 ins. above ground, and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
S 16 | S 15  
S 21 | S 22  
1987

Deposit the iron post, alongside the aluminum post.

---

From the cor. of secs. 14, 15, 22, and 23.

N. 89° 45' W., bet. secs. 15 and 22.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

Over rolling desert land, through sagebrush and shadscale.

- 40.68 Point for the 1/4 sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
S 15  
1/4 S 22  
1987

- 81.36 The cor. of secs. 15, 16, 21, and 22.

N. 0° 04' W., bet. secs. 15 and 16.

Over rolling desert land, through sagebrush and shadscale.

- 20.365 Point for the S 1/16 sec. cor. of secs. 15 and 16.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 17 S R 5 W  
S 1/16  
S 16 | S 15  
1987

- 40.73 Point for the 1/4 sec. cor. of secs. 15 and 16, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 17 S R 5 W  
1/4  
S 16 | S 15  
1987

- 61.095 Point for the N 1/16 sec. cor. of secs. 15 and 16.

Set a steal fence post, 5 1/2 ft. long, flush with the surface and place a stainless steel post, 30 ins. long, 2 1/2 ins. diam., over the fence post, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

T 17 S R 5 W  
N 1/16  
S 16 | S 15  
1987

Cor. is located in rolling sand dunes.

- 81.46 Point for the cor. of secs. 9, 10, 15, and 16, at proportionate dist., there is no remaining evidence of the original corner.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 17 S R 5 W  
S 9 | S 10  
S 16 | S 15  
1987

---

From the cor. of secs. 10, 11, 14, and 15.

N. 89° 40' W., bet. secs. 10 and 15.

Over rolling desert land, through sagebrush and shadscale.

- 20.28 Point for the E 1/16 sec. cor. of secs. 10 and 15.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 17 S R 5 W  
S 10  
E 1/16 S 15  
1987

- 40.56 Point for the 1/4 sec. cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 17 S R 5 W  
S 10  
1/4 S 15  
1987

- 60.84 Point for the W 1/16 sec. cor. of secs. 10 and 15.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 17 S R 5 W  
S 10  
W 1/16     S 15  
1987

81.12 The cor. of secs. 9, 10, 15, and 16.

---

N. 0° 51' E., bet. secs. 9 and 10.

Over rolling desert land, through sagebrush and shadscale.

39.30 Center line of Utah State Highway No. 125, bears E and W.

40.73 Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 17 S R 5 W  
1/4  
S 9 | S 10  
1987

81.46 The cor. of secs. 3, 4, 9, and 10, monumented with the remains of a cedar post, 6 ins. above ground, no visible scribe marks

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
S 4 | S 3  
S 9 | S 10  
1987

Deposit the cedar post, alongside the aluminum post.

---

From the cor. of secs. 2, 3, 10, and 11.

N. 89° 24' W., bet. secs. 3 and 10.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

Over rolling desert land, through sagebrush and shadscale.

- 41.13 The 1/4 sec. cor. of secs. 3 and 10, monumented with a squared cedar post, 18x3x3 ins., firmly set with no visible scribe marks, and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
S 3  
1/4 S 10  
1987

Deposit the cedar post, alongside the aluminum post.

N. 89° 48' W., beginning new measurement.

- 40.93 The cor. of secs. 3, 4, 9, and 10.

N. 2° 32' E., bet. secs. 3 and 4.

Over rolling desert land, through sagebrush and shadscale.

- 41.77 Point for the 1/4 sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
1/4  
S 4 | S 3  
1987

- 83.85 The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., heretofore described.

From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., heretofore described.

N. 0° 16' E., bet. secs. 32 and 33.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

Over rolling desert land, through sagebrush and shadscale.

- 20.23 Point for the S 1/16 sec. cor. of secs. 32 and 33, not monumented.  
40.46 Point for the 1/4 sec. cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.

T 17 S R 5 W  
1/4  
S 32 | S 33  
1987

Cor. is located 2 lks. dist., W of fence, bears N and S.

- 60.69 Point for the N 1/16 sec. cor. of secs. 32 and 33, not monumented.  
80.92 The cor. of secs. 28, 29, 32, and 33, monumented with an iron post, 2 1/2 ins. diam., 10 ins. above ground, and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
S 29 | S 28  
S 32 | S 33  
1987

Deposit the iron post, alongside the aluminum post.

From the cor. of secs. 27, 28, 33, and 34.

S. 89° 37' W., bet. secs. 28 and 33.

Over rolling desert land, through sagebrush and shadscale.

- 40.61 Point for the 1/4 sec. cor. of secs. 28 and 33, at proportionate distance; there is no remaining evidence of the original corner.  
Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

T 17 S R 5 W  
S 28  
1/4 S 33  
1987

60.915 Point for the W 1/16 sec. cor. of secs. 28 and 33.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
S 28  
W 1/16 S 33  
1987

81.22 The cor. of secs. 28, 29, 32, and 33.

---

N. 0° 16' W., bet. secs. 28 and 29.

Over rolling desert land, through sagebrush and shadscale.

20.505 Point for the S 1/16 sec. cor. of secs. 28 and 29.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
S 1/16  
S 29 | S 28  
1987

41.01 The 1/4 sec. cor. of secs. 28 and 29, monumented with an iron post, 2 ins. in diam., 6 ins. above ground, and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
1/4  
S 29 | S 28  
1987

Deposit the iron post, alongside the aluminum post.

---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

N. 0° 28' E., beginning new measurement.

20.195 Point for the N 1/16 sec. cor. of secs. 28 and 29, not monumented.

40.39 The cor. of secs. 20, 21, 28, and 29, monumented with an iron post, 2 1/2 ins. in diam., 6 ins. above ground, and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W			
S 20		S 21	
S 29		S 28	
1987			

Deposit the iron post, alongside the aluminum post.

---

From the cor. of secs. 21, 22, 27, and 28.

S. 89° 28' W., bet. secs. 21 and 28.

Over rolling desert land, through sagebrush and shadscale.

20.32 Point for the E 1/16 sec. cor. of secs. 21 and 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W			
		S 21	
E 1/16		S 28	
1987			

40.64 The 1/4 sec. cor. of secs. 21 and 28, monumented with an iron post, 6 ins. above ground, and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

T 17 S R 5 W  
S 21  
1/4 S 28  
1987

Deposit the iron post, alongside the aluminum post.

---

N. 89° 54' W., beginning new measurement.

- 20.33 Point for the W 1/16 sec. cor. of secs. 21 and 28, not monumented.  
40.66 The cor. of secs. 20, 21, 28, and 29.
- 

N. 0° 03' E., bet. secs. 20 and 21.

Over rolling desert land, through sagebrush and shadscale.

- 40.85 The 1/4 sec. cor. of secs. 20 and 21, monumented with an iron post, 2 1/2 ins. diam., 6 ins. below the surface, and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
1/4  
S 20 | S 21  
1987

Deposit the iron post, alongside the aluminum post.

---

From the cor. of secs. 15, 16, 21, and 22.

N. 89° 47' W., bet. secs. 16 and 21.

Over rolling desert land, through sagebrush and shadscale.

- 40.44 The 1/4 sec. cor. of secs. 16 and 21, monumented with an iron post, 2 1/2 ins. diam., 8 ins. above ground, and is accepted as the best available evidence of the position of the original corner.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
S 16  
1/4 S 21  
1987

Deposit the iron post, alongside the aluminum post.

From the 1/4 sec. cor. of secs. 16 and 17, monumented with a squared cedar post, 18x2x2 ins., firmly set, no visible scribe marks

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
1/4  
S 17 | S 16  
1987

Deposit the squared cedar post, alongside the aluminum post.

N. 0° 06' W., bet secs. 16 and 17.

Over rolling desert land, through sagebrush and shadscale.

40.90 Point for the cor. of secs. 8, 9, 16, and 17, at proportionate dist., there is no remaining evidence of the original corner.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 17 S R 5 W  
S 8 | S 9  
S 17 | S 16  
1987

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

From this cor;

The cor. of secs. 7, 8, 17, and 18, monumented with an iron post, 2 ins. diam., 12 ins. above ground, with brass cap, mkd. as described in the official record of the 1920 survey, bears S. 89° 42' W., 81.08 chs. dist.

The control line was fully retraced and no evidence of the intervening cor. was found.

From the cor. of secs. 9, 10, 15, and 16.

N. 89° 41' W., bet. secs. 9 and 16.

Over rolling desert land, through sagebrush and shadscale.

40.51 Point for the 1/4 sec. cor. of secs. 9 and 16, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 17 S R 5 W  
S 9  
1/4 S 16  
1987

81.02 The cor. of secs. 8, 9, 16, and 17.

N. 1° 11' E., bet. secs. 8 and 9.

Over rolling desert land, through sagebrush and shadscale.

37.08 Center line of Utah State Highway No. 125, bears E and W.

40.91 Point for the 1/4 sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 17 S R 5 W  
1/4  
S 8 | S 9  
1987

61.365 Point for the N 1/16 sec. cor. of secs. 8 and 9.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 17 S R 5 W  
N 1/16  
S 8 | S 9  
1987

81.82 The cor. of secs. 4, 5, 8, and 9, monumented with a squared cedar post, 16x2x2 ins., firmly set, no visible scribe marks

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
S 5 | S 4  
S 8 | S 9  
1987

Deposit the squared cedar post, alongside the aluminum post.

---

From the cor. of secs. 3, 4, 9, and 10.

N. 89° 29' W., bet. secs. 4 and 9.

Over rolling desert land, through sagebrush and shadscale.

40.37 The 1/4 sec. cor. of secs. 4 and 9, monumented with a squared cedar post, 24x4x4 ins., firmly set, no visible scribe marks

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
S 4  
1/4 S 9  
1987

Deposit the squared cedar post, alongside the aluminum post.

---

N. 89° 23' W., beginning new measurement.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

20.08 Point for the W 1/16 sec. cor. of secs. 4 and 9.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 17 S R 5 W  
S 4  
W 1/16 S 9  
1987

40.16 The cor. of secs. 4, 5, 8, and 9.

---

N. 2° 04' E., bet. secs. 4 and 5.

Over rolling desert land, through sagebrush and shadscale.

41.32 Point for the 1/4 sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
1/4  
S 5 | S 4  
1987

83.11 The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., heretofore described.

---

Survey of the Subdivision of Section 3,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 3 and 10.

N. 2° 21' E., on the N-S center line of sec. 3.

41.67 Point for the center 1/4 sec. cor. of sec. 3, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
C 1/4 S 3  
1987

Survey of the Subdivision of Section 3,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

83.95 The 1/4 sec. cor. of secs. 3 and 34, on the N. bdy. of the Tp., heretofore described.

---

From the 1/4 sec. cor. of secs. 2 and 3.

N. 89° 39' W., on the E-W center line of sec. 3.

40.88 The center 1/4 sec. cor. of sec. 3.

81.65 The 1/4 sec. cor. of secs. 3 and 4.

---

Survey of the Subdivision of Section 4,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 4 and 9.

N. 2° 22' E., on the N-S center line of sec. 4.

41.59 Point for the center 1/4 sec. cor. of sec. 4, at intersection with the E and W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
C 1/4 S4  
1987

83.53 The 1/4 sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp., heretofore described.

---

From the 1/4 sec. cor. of secs. 3 and 4.

N. 89° 45' W., on the E-W center line of sec. 4.

40.49 The center 1/4 sec. cor. of sec. 4.

60.685 Point for the center W 1/16 sec. cor. of sec. 4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
W 1/16  
C  $\frac{S 4}{1987}$  C

Survey of the Subdivision of Section 4,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

80.88 The 1/4 sec. cor. of secs. 4 and 5.

---

From the center W 1/16 sec. cor. of sec. 4.

N. 2° 13' E., on the N-S center line of the NW 1/4 of sec. 4.

41.87 The W 1/16 sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp.,  
heretofore described.

---

Survey of the Subdivision of Section 9,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 9 and 16.

N. 0° 57' E., on the N-S center line of sec. 9.

38.20 Center line of Utah State Highway No. 125, bears E and W (scaled).

40.82 Point for the center 1/4 sec. cor. of sec. 9, at intersection with  
the E and W center line.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24  
ins. in the ground, with brass cap mkd.

T 17 S R 5 W  
C 1/4 S9  
1987

61.21 Point for the center N 1/16 sec. cor. of sec. 9.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24  
ins. in the ground, with brass cap mkd.

T 17 S R 5 W  
C  
N 1/16 | S 9  
C  
1987

81.60 The 1/4 sec. cor. of secs. 4 and 9.

---

From the 1/4 sec. cor. of secs. 9 and 10.

N. 89° 33' W., on the E-W center line of sec. 9.

40.44 The center 1/4 sec. cor. of sec. 9.

Survey of the Subdivision of Section 9,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

60.61 Point for the center W 1/16 sec. cor. of sec. 9.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 17 S R 5 W  
W 1/16  
C ——— C  
S 9  
1987

80.78 The 1/4 sec. cor. of secs. 8 and 9.

---

From the center W 1/16 sec. cor. of sec. 9.

N. 1° 04' E., on the N and S center line of the NW 1/4 of sec. 9.

20.425 Point for the NW 1/16 sec. cor. of sec. 9, at intersection with the E-W center line of the NW 1/4.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 17 S R 5 W  
NW 1/16 S9  
1987

40.85 The W 1/16 sec. cor. of secs. 4 and 9.

---

From the center N 1/16 sec. cor. of sec. 9.

N. 89° 28' W., on the E-W center line of the NW 1/4 of sec. 9.

20.125 The NW 1/16 sec. cor. of sec. 9.

40.25 The N 1/16 sec. cor. of secs. 8 and 9.

---

Survey of the Subdivision of Section 10,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 10 and 15.

N. 1° 07' E., on the N and S center line of sec. 10.

40.20 Center line of Utah State Highway No. 125, bears E and W (scaled).

Survey of the Subdivision of Section 10,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

- 40.71 Point for the center 1/4 sec. cor. of sec. 10, at intersection with the E-W center line.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 17 S R 5 W  
C 1/4 S 10  
1987

- 81.56 The 1/4 sec. cor. of secs. 3 and 10.
- 

From the 1/4 sec. cor. of secs. 10 and 11.

N. 89° 37' W., on the E-W center line of sec. 10.

- 16.15 Center line of Utah State Highway No. 125, bears E and W (scaled).

- 40.85 The center 1/4 sec. cor. of sec. 10.

- 61.225 Point for the center W 1/16 sec. cor. of sec. 10.

Set a steal fence post, 5 1/2 ft. long, flush with the surface and place a stainless steal post, 30 ins. long, 2 1/2 ins. diam., over the fence post, with brass cap mkd.

T 17 S R 5 W  
W 1/16  
C  $\frac{\quad}{S 10}$  C  
1987

Cor. is located in rolling sand dunes.

- 81.60 The 1/4 sec. cor. of secs. 9 and 10.
- 

From the W 1/16 sec. cor. of secs. 10 and 15.

N. 0° 59' E., on the N and S center line of the SW 1/4 of sec. 10.

- 39.75 Center line of Utah State Highway No. 125, bears E and W (scaled).

- 40.72 The center W 1/16 sec. cor. of sec. 10.
- 

Survey of the Subdivision of Section 11,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

---

Survey of the Subdivision of Section 11,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 11 and 14.

N.  $0^{\circ} 57'$  E., on the N and S center line of sec. 11.

20.36 Point for the center S 1/16 sec. cor. of sec. 11, not monumented.

40.72 Point for the center 1/4 sec. cor. of sec. 11, at intersection with the E-W center line.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 17 S R 5 W  
C 1/4 S 11  
1987

41.81 Center line of Utah State Highway No. 125, bears E and W.

81.44 The 1/4 sec. cor. of secs. 2 and 11.

From the 1/4 sec. cor. of secs. 11 and 12.

N.  $89^{\circ} 46'$  W., on the E and W center line of sec. 11.

20.035 Point for the center E 1/16 sec. cor. of sec. 11, not monumented.

40.07 The center 1/4 sec. cor. of sec. 11.

60.105 Point for the center W 1/16 sec. cor. of sec. 11, not monumented.

80.14 The 1/4 sec. cor. of secs. 10 and 11.

From the E 1/16 sec. cor. of secs. 11 and 14.

N.  $0^{\circ} 39'$  E., on the N and S center line of the SE 1/4 of sec. 11.

20.37 Point for the SE 1/16 sec. cor. of sec. 11, at intersection with the E-W center line of the SE 1/4 of sec. 11.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 17 S R 5 W  
SE 1/16 S 11  
1987

40.74 The point for the center E 1/16 sec. cor. of sec. 11.

Survey of the Subdivision of Section 11,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

From the S 1/16 sec. cor. of secs. 11 and 12.

N. 89° 45' W., on the E-W center line of the SE 1/4 of sec. 11.

20.14 The SE 1/16 sec. cor. of sec. 11.

40.28 The point for the center S 1/16 sec. cor. of sec. 11.

---

From the W 1/16 sec. cor. of secs. 11 and 14.

N. 1° 14' E., on the N and S center line of the SW 1/4 of sec. 11.

20.355 Point for the SW 1/16 sec. cor. of sec. 11, at intersection with the E-W center line of the SW 1/4 of sec. 11.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 17 S R 5 W  
SW 1/16 S 11  
1987

40.71 The point for the center W 1/16 sec. cor. of sec. 11.

---

From the point for the center S 1/16 sec. cor. of sec. 11.

N. 89° 45' W., on the E-W center line of the SW 1/4 of sec. 11.

20.14 The SW 1/16 sec. cor. of sec. 11.

40.28 The S 1/16 sec. cor. of secs. 10 and 11.

---

Survey of the Subdivision of Section 12,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 12 and 13.

N. 2° 17' E., on the N and S center line of sec. 12.

42.50 Point for the center 1/4 sec. cor. of sec. 12, at intersection with the E-W center line.

Survey of the Subdivision of Section 12,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
C 1/4 S 12  
1987

58.00 Center line of Utah State Highway No. 125 on curve, bears NE and SW (scaled).

62.92 Point for the center N 1/16 sec. cor. of sec. 12.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
C  
N 1/16 | S 12  
C  
1987

83.34 The 1/4 sec. cor. of secs. 1 and 12.

---

From the 1/4 sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp., heretofore described.

S. 88° 16' W., on the E and W center line of sec. 12.

44.94 The center 1/4 sec. cor. of sec. 12.

58.00 Asphalt road, bears N. 28° E. and S. 28° W. (scaled).

86.79 The 1/4 sec. cor. of secs. 11 and 12.

---

From the N 1/16 sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp., heretofore described.

S. 88° 16' W., on the E and W center line of the NE 1/4 of sec. 12.

35.00 Center line of Utah State Highway No. 125, bears N. 60° E. and S. 60° W. (scaled).

44.09 The center N 1/16 sec. cor. of sec. 12.

---

Survey of the Subdivision of Section 14,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

Survey of the Subdivision of Section 14,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 14 and 23.

N.  $0^{\circ} 19'$  W., on the N and S center line of sec. 14.

- 39.62 Point for the center 1/4 sec. cor. of sec. 14, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
C 1/4 S 14  
1987

- 59.935 Point for the center N 1/16 sec. cor. of sec. 14.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
C  
N 1/16 | S 14  
C  
1987

- 80.25 The 1/4 sec. cor. of secs. 11 and 14.
- 

From the 1/4 sec. cor. of sec. 14 only.

N.  $89^{\circ} 46'$  W., on the E and W center line of sec. 14.

- 12.50 Asphalt road, bears N.  $28^{\circ}$  E. and S.  $28^{\circ}$  W. (scaled).

- 20.42 Point for the center E 1/16 sec. cor. of sec. 14.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
E 1/16  
C ——— C  
S 14  
1987

Survey of the Subdivision of Section 14,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

40.84 The center 1/4 sec. cor. of sec. 14.

81.39 The 1/4 sec. cor. of secs. 14 and 15.

---

From the center E 1/16 sec. cor. of sec. 14

N. 0° 33' W., on the N and S center line of the NE 1/4 of sec. 14.

20.31 Point for the NE 1/16 sec. cor. of sec. 14, at intersection with the E-W center line of the NE 1/4 of sec. 14.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
NE 1/16 S 14  
1987

40.62 The E 1/16 sec. cor. of secs. 11 and 14.

---

From the N 1/16 sec. cor. of sec. 14 only.

N. 89° 45' W., on the E and W center line of the NE 1/4 of sec. 14.

2.50 Asphalt road, bears N. 28° E. and S. 28° W. (scaled).

20.33 The NE 1/16 sec. cor. of sec. 14.

40.66 The center N 1/16 sec. cor. of sec. 14.

---

From the E 1/16 sec. cor. of secs. 14 and 23.

N. 0° 18' E., on the N and S center line of the SE 1/4 of sec. 14.

25.00 Asphalt road, bears N. 28° E. and S. 28° W. (scaled).

39.82 The center E 1/16 sec. cor. of sec. 14.

---

Survey of the Subdivision of Section 15  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

---

Survey of the Subdivision of Section 15,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 15 and 22.

N. 0° 09' W., on the N and S center line of sec. 15.

20.35 Point for the center S 1/16 sec. cor. of sec. 15.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 17 S R 5 W  
C  
S 1/16 | S 15  
C  
1987

40.70 Point for the center 1/4 sec. cor. of sec. 15, at intersection with the E-W center line.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 17 S R 5 W  
C 1/4 S 15  
1987

61.05 Point for the center N 1/16 sec. cor. of sec. 15, not monumented.

81.40 The 1/4 sec. cor. of secs. 10 and 15.

From the 1/4 sec. cor. of secs. 14 and 15.

N. 89° 42' W., on the E and W center line of sec. 15.

20.31 Point for the center E 1/16 sec. cor. of sec. 15.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 17 S R 5 W  
E 1/16  
C ——— S 15 ——— C  
1987

40.62 The center 1/4 sec. cor. of sec. 15.

60.93 Point for the center W 1/16 sec. cor. of sec. 15, not monumented.

81.24 The 1/4 sec. cor. of secs. 15 and 16.

Survey of the Subdivision of Section 15,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

From the center E 1/16 sec. cor. of sec. 15.

N. 0° 11' W., on the N and S center line of the NE 1/4 of sec. 15.

40.68 The E 1/16 sec. cor. of secs. 10 and 15.

---

From the center S 1/16 sec. cor. of sec. 15.

N. 89° 44' W., on the E and W center line of the SW 1/4 of sec. 15.

40.65 The S 1/16 sec. cor. of secs. 15 and 16.

---

From the point for the center W 1/16 sec. cor. of sec. 15.

N. 0° 07' W., on the N and S center line of the NW 1/4 of sec. 15.

20.355 Point for the NW 1/16 sec. cor. of sec. 15, at intersection with the E-W center line of the NW 1/4 of sec. 15.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 17 S R 5 W  
NW 1/16 S 15  
1987

40.71 The W 1/16 sec. cor. of secs. 10 and 15.

---

From the point for the center N 1/16 sec. cor. of sec. 15.

N. 89° 41' W., on the E and W center line of the NW 1/4 of sec. 15.

20.295 The NW 1/16 sec. cor. of sec. 15.

40.59 The N 1/16 sec. cor. of secs. 15 and 16.

---

Survey of the Subdivision of Section 21  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 21 and 28.

North, on the N and S center line of sec. 21.

Survey of the Subdivision of Section 21,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

20.475 Point for the center S 1/16 sec. cor. of sec. 21.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
C  
S 1/16 S | S 21  
C  
1987

40.95 Point for the center 1/4 sec. cor. of sec. 21, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
C 1/4 S 21  
1987

81.60 The 1/4 sec. cor. of secs. 16 and 21.

---

From the 1/4 sec. cor. of secs. 21 and 22.

S. 89° 58' W., on the E and W center line of sec. 21.

20.315 Point for the center E 1/16 sec. cor. of sec. 21.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
E 1/16  
C ——— S 21 ——— C  
1987

40.63 The center 1/4 sec. cor. of sec. 21.

81.25 The 1/4 sec. cor. of secs. 20 and 21.

---

From the E 1/16 sec. cor. of secs. 21 and 28.

N. 0° 01' W., on the N and S center line of the SE 1/4 of sec. 21.

Survey of the Subdivision of Section 21,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

20.385 Point for the SE 1/16 sec. cor. of sec. 21, at intersection with the E-W center line of the SE 1/4 of sec. 21.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
SE 1/16 S 21  
1987

40.77 The center E 1/16 sec. cor. of sec. 21.

---

From the S 1/16 sec. cor. of secs. 21 and 22.

S. 89° 43' W., on the E and W center line of the SE 1/4 of sec. 21.

20.32 The SE 1/16 sec. cor. of sec. 21.

40.64 The center S 1/16 sec. cor. of sec. 21.

---

Survey of the Subdivision of Section 27,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 27 and 34.

N. 0° 06' E., on the N and S center line of sec. 27.

20.33 Point for the center S 1/16 sec. cor. of sec. 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
C  
S 1/16 | S 27  
C  
1987

40.66 Point for the center 1/4 sec. cor. of sec. 27, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Survey of the Subdivision of Section 27,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

T 17 S R 5 W  
C 1/4 S 27  
1987

60.995 Point for the center N 1/16 sec. cor. of sec. 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
C  
N 1/16 | S 27  
C  
1987

81.33 The 1/4 sec. cor. of secs. 22 and 27.

---

From the 1/4 sec. cor. of secs. 26 and 27.

N. 88° 54' W., on the E and W center line of sec. 27.

13.00 Asphalt road on curve, bears N. 28° E. and S. 9° W. (scaled).

20.38 Point for the center E 1/16 sec. cor. of sec. 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
E 1/16  
C ——— S 27 ——— C  
1987

40.76 The center 1/4 sec. cor. of sec. 27.

81.46 The 1/4 sec. cor. of secs. 27 and 28.

---

From the center E 1/16 sec. cor. of sec. 27.

N. 0° 01' E., on the N and S center line of the NE 1/4 of sec. 27.

20.355 Point for the NE 1/16 sec. cor. of sec. 27, at intersection with the E-W center line of the NE 1/4 of sec. 27.

Survey of the Subdivision of Section 27,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
NE 1/16 S 27  
1987

40.71 The E 1/16 sec. cor. of secs. 22 and 27.

---

From the N 1/16 sec. cor. of secs. 26 and 27.

N. 88° 57' W., on the E and W center line of the NE 1/4 of sec. 27.

5.00 Asphalt road, bears N. 28° E. and S. 28° W. (scaled).

20.35 The NE 1/16 sec. cor. of sec. 27.

40.70 The center N 1/16 sec. cor. of sec. 27.

---

From the E 1/16 sec. cor. of secs. 27 and 34.

N. 0° 07' E., on the N and S center line of the SE 1/4 of sec. 27.

20.35 Point for the SE 1/16 sec. cor. of sec. 27, at intersection with the E-W center line of the SE 1/4 of sec. 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
SE 1/16 S 27  
1987

40.70 The center E 1/16 sec. cor. of sec. 27.

---

From the S 1/16 sec. cor. of secs. 26 and 27.

N. 88° 51' W., on the E and W center line of the SE 1/4 of sec. 27.

15.50 Asphalt road, bears N. 9° E. and S. 9° W. (scaled).

20.38 The SE 1/16 sec. cor. of sec. 27.

40.76 The center S 1/16 sec. cor. of sec. 27.

---

Survey of the Subdivision of Section 28,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

Survey of the Subdivision of Section 28,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 28 and 33.

N.  $0^{\circ} 09'$  E., on the N and S center line of sec. 28.

20.40 Point for the center S 1/16 sec. corner of sec. 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
C  
S 1/16 | S 28  
C  
1987

40.80 Point for the center 1/4 sec. cor. of sec. 28, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
C 1/4 S 28  
1987

60.925 Point for the center N 1/16 sec. cor. of sec. 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
C  
N 1/16 | S 28  
C  
1987

81.05 The 1/4 sec. cor. of secs. 21 and 28.

---

From the 1/4 sec. cor. of secs. 27 and 28.

S.  $89^{\circ} 55'$  W., on the E and W center line of sec. 28.

40.63 The center 1/4 sec. cor. of sec. 28.

Survey of the Subdivision of Section 28,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

61.075 Point for the center W 1/16 sec. cor. of sec. 28.

Set a steal fence post, 5 1/2 ft. long, flush with the surface and place an aluminum post, 30 ins. long, 2 1/2 ins. diam., over the steal post, with aluminum cap mkd.

T 17 S R 5 W  
W 1/16  
C ————— C  
S 28  
1987

Cor. is located in rolling sand dunes.

81.52 The 1/4 sec. cor. of secs. 28 and 29.

---

From the W 1/16 sec. cor. of secs. 28 and 33.

N. 0° 03' W., on the N and S center line of the SW 1/4 of sec. 28.

20.45 Point for the SW 1/16 sec. cor. of sec. 28, at intersection with the E-W center line of the SW 1/4 of sec. 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
SW 1/16 S 28  
1987

40.90 The center W 1/16 sec. cor. of sec. 28.

---

From the center S 1/16 sec. cor. of sec. 28.

S. 89° 46' W., on the E and W center line of the SW 1/4 of sec. 28.

20.375 The SW 1/16 sec. cor. of sec. 28.

40.75 The S 1/16 sec. cor. of secs. 28 and 29.

---

From the center W 1/16 sec. cor. of sec. 28.

N. 0° 18' E., on the N and S center line of the NW 1/4 of sec. 28.

Survey of the Subdivision of Section 28,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

- 20.16 Point for the NW 1/16 sec. cor. of sec. 28, at intersection with the E-W center line of the NW 1/4 of sec. 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
NW 1/16 S 28  
1987

- 40.32 The point for the W 1/16 sec. cor. of secs. 21 and 28.

---

From the center N 1/16 sec. cor. of sec. 28.

West, on the E and W center line of the NW 1/4 of sec. 28.

- 20.39 The NW 1/16 sec. cor. of sec. 28.

- 40.78 The point for the N 1/16 sec. cor. of secs. 28 and 29.

---

Survey of the Subdivision of Section 33,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 4 and 33, on the S. bdy. of the Tp., heretofore described.

N. 0° 32' E., on the N and S center line of sec. 33.

- 20.265 Point for the center S 1/16 sec. cor. of sec. 33.

Set a steal fence post, 5 1/2 ft. long, flush with the surface and place an aluminum post, 30 ins. long, 2 1/2 ins. diam., over the steal post, with aluminum cap mkd.

T 17 S R 5 W  
C  
S 1/16 | S 33  
C  
1987

Cor. is located in rolling sand dunes.

- 40.53 Point for the center 1/4 sec. cor. of sec. 33, at intersection with the E-W center line.

Survey of the Subdivision of Section 33,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
C 1/4 S 33  
1987

60.795 Point for the center N 1/16 sec. cor. of sec. 33.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
C  
N 1/16 | S 33  
C  
1987

81.06 The 1/4 sec. cor. of secs. 28 and 33.

---

From the 1/4 sec. cor. of secs. 33 and 34.

S. 89° 43' W., on the E and W center line of sec. 33.

40.43 The center 1/4 sec. cor. of sec. 33.

60.645 The point for the center W 1/16 sec. cor. of sec. 33.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
W 1/16  
C ——— S 33 ——— C  
1987

80.86 The 1/4 sec. cor. of secs. 32 and 33.

---

From the N 1/16 sec. cor. of secs. 33 and 34.

S. 89° 40' W., on the E and W center line of the NE 1/4 of sec. 33.

40.52 The center N 1/16 sec. cor. of sec. 33.

---

Survey of the Subdivision of Section 33,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

From the S 1/16 sec. cor. of secs. 33 and 34.

S. 89° 46' W., on the E and W center line of the SE 1/4 of sec. 33.

40.34 The center S 1/16 sec. cor. of sec. 33.

---

From the W 1/16 sec. cor. of secs. 4 and 33, on the S. bdy. of the Tp., heretofore described.

N. 0° 24' E., on the N and S center line of the SW 1/4 of sec. 33.

20.25 Point for the SW 1/16 sec. cor. of sec. 33, at intersection with the E-W center line of the SW 1/4 of sec. 33.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
SW 1/16 S 33  
1987

40.50 The center W 1/16 sec. cor. of sec. 33.

---

From the center S 1/16 sec. cor. of sec. 33.

S. 89° 46' W., on the E and W center line of the SW 1/4 of sec. 33.

20.17 The SW 1/16 sec. cor. of sec. 33.

40.34 The point for the S 1/16 sec. cor. of secs. 32 and 33.

---

From the center W 1/16 sec. cor. of sec. 33.

N. 0° 24' E., on the N and S center line of the NW 1/4 of sec. 33.

20.25 The point for the NW 1/16 sec. cor. of sec. 33, at intersection with the E-W center line of the NW 1/4 of sec. 33.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 17 S R 5 W  
NW 1/16 S 33  
1987

Survey of the Subdivision of Section 33,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

40.50 The W 1/16 sec. cor. of secs. 28 and 33.

---

From the center N 1/16 sec. cor. of sec. 33.

S.  $89^{\circ} 40'$  W., on the E and W center line of the NW 1/4 of sec. 33.

20.26 The NW 1/16 sec. cor. of sec. 33.

40.52 The point for the N 1/16 sec. cor. of secs. 32 and 33.

---

Survey of the Subdivision of Section 34,  
T. 17 S., R. 5 W., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 3 and 34, on the S. bdy. of the  
Tp., heretofore described.

N.  $1^{\circ} 10'$  E., on the N and S center line of sec. 34.

39.57 The point for the center 1/4 sec. cor. of sec. 34, at intersection  
with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in  
the ground, with aluminum cap mkd.

T 17 S R 5 W  
C 1/4 S 34  
1987

80.21 The 1/4 sec. cor. of secs. 27 and 34.

---

From the 1/4 sec. cor. of secs. 34 and 35.

N.  $88^{\circ} 44'$  W., on the E and W center line of sec. 34.

25.50 Asphalt road, bears N.  $9^{\circ}$  E. and S.  $9^{\circ}$  W. (scaled).

42.34 The center 1/4 sec. cor. of sec. 34.

82.83 The 1/4 sec. cor. of secs. 33 and 34.

---

## Township 17 South, Range 5 West, Salt Lake Meridian, Utah

## General Description

Township 17 South, Range 5 West, is located near Oak City, Utah. The elevation varies from about 4650 to 5400 ft. above sea level. The soil varies from rocky clay loam at higher elevations to rolling sand dunes at the lower areas. Utah State Highway No. 125 enters the township on the west boundary of section 7 and leaves the township on the east boundary of the NE 1/4 of section 12. An asphalt road connects to Highway No. 125 in the NW 1/4 of section 12 and exits the township on the south boundary of the SE 1/4 of section 34. The main use at this time appears to be livestock grazing.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

## FIELD ASSISTANTS

Larry V. Judd	Surveying Technician
Ferrel D. Reynolds	Surveying Technician


## CERTIFICATE OF SURVEY

I, Richard A. Zaninovich, Cadastral Surveyor, HEREBY

CERTIFY upon honor that, in pursuance of special instructions date of the 21th day of November, 1986, I have dependently resurveyed portions of the north, south, and east boundaries, portions of the subdivisional lines, and surveyed the subdivision of sections 3, 4, 9, 10, 11, 12, 14, 15, 21, 27, 28, 33, and 34 in T. 17 S., R. 5 W.,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

July 11, 1988  
(Date)

  
(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL


BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The foregoing field notes of the dependent resurvey of portions of the north, south, and east boundaries, portions of the subdivisional lines, and the survey of the subdivision of sections 3, 4, 9, 10, 11, 12, 14, 15, 21, 27, 28, 33, and 34 in T. 17 S., R. 5 W., Salt Lake Meridian, Utah

executed by Richard A. Zaninovich, Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

October 11, 1988  
(Date)

  
(Chief, Cadastral Surveyor for Utah)



INDEX DIAGRAM

Township 3 South, Range 22 West

6	5	4	3	2	1
7	8	9	10 1	11	12
18	17	16	15	14	13 8
19	20	21	22	23 6	24 4
30	29	28	27	26 3	25 2
31	32	33	34	35	36

Subdivision of Section 24  
 Subdivision of Section 25

- Page 9  
 - Page 15

## Township 3 South, Range 22 East, Salt Lake Meridian, Utah

The following field notes describe the dependent resurvey of a portion of the subdivisional lines and the subdivision of sections 24 and 25, Township 3 South, Range 22 East, Salt Lake Meridian, Utah.

History of Surveys

	<u>Surveyed by</u>		<u>Retr. or Resurveyed by</u>	
<u>SOUTH BOUNDARY</u>				
All	Jessen and Harmston	1900		
Portion			H.W. Miller	1911
<u>EAST BOUNDARY (Ashley Guide Meridian)</u>				
All	A.D. Ferron	1878		
All			Jessen and Harmston	1900
Portion			R. Zaninovich	1984
<u>WEST BOUNDARY</u>				
All	Jessen and Harmston	1900		
Portion			R. Gentry	1920
Portion			J.L. Thomas	1973
<u>NORTH BOUNDARY</u>				
All	Jessen and Harmston	1900		
Portion			H.W. Miller	1911
Portion			G.W. Hochstrasser	1965
<u>SUBDIVISION</u>				
Portion	Jessen and Harmston	1906		
Portion	H.W. Miller	1911		
Portion			H.W. Miller	1911
Portion			G.W. Hochstrasser	1965

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group 679, Utah, dated October 15, 1985.

The directions of lines were determined by reference to true meridians established on line by altitude observations on the sun, and by hour angle observations on Polaris. The lines were carried forward by sustained angulations, being supplemented by other observations on Polaris taken throughout the progress of the survey. Distances were determined by electronic measurement.

## Township 3 South, Range 22 East, Salt Lake Meridian, Utah

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions, lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the southwest cor. of section 25, which also functions as United States Geological Survey triangulation station "SEC COR 26/3S/22E" is:

Latitude  $40^{\circ} 31' 21.297''$  N. Longitude  $109^{\circ} 24' 12.884''$  W.  
N.A.D. 1927

The mean magnetic declination, as projected from the U.S. Geological Survey Magnetic Declination Map of 1980, is  $14^{\circ}$  E.

---

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 22 E., Salt Lake Meridian, Utah

---

(Reestablishment of the Survey Executed by  
E. F. Harmston in 1906)

---

Beginning at the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., monumented with an aluminum post, 2 1/2 ins. diam., set, mkd. and witnessed as described in the official record of the dependent resurvey of the W. bdy. of T. 3 S., R. 23 E. in 1984.

This cor. has been designated as a BLM control station with geographic coordinates:

Latitude  $40^{\circ} 31' 21.28''$  N. Longitude  $109^{\circ} 23' 04.04''$  W.  
N.A.D. 1927

N.  $88^{\circ} 56'$  W., bet. secs. 25 and 36.

Over rolling bench land.

17.75 Brush Creek, 30 lks. wide, flows SE.

40.51 The 1/4 sec. cor. of secs. 25 and 36, monumented with a sandstone, 18 x 14 x 10 ins., firmly set, projecting 8 ins. above ground, plainly mkd. 1/4 on N face.

At the corner point

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 22 E., Salt Lake Meridian, Utah

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 3 S R 22 E  
S 25  
1/4 S 36  
1985

Deposit the mkd. stone alongside the aluminum post.

Cor. is located in bottom of deep draw, which drains E.

S. 89° 01' W., beginning new measurement.

- 4.50 Center line of paved road, bears N and S.
- 40.09 The cor. of secs. 25, 26, 35, and 36, monumented with a sandstone, 14 x 8 x 8 ins., firmly set, projecting 10 ins. above ground, dimly mkd. 1 notch on the S and E edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 22 E  
S 26 | S 25  
S 35 | S 36  
1985

Deposit the mkd. stone alongside the aluminum post.

This cor. also functions as United States Geological Survey triangulation station "SEC COR 26/3S/22E". The aluminum post was set in exact center position of sandstone monument latitudinally and longitudinally, but 4 ins. lower in altitude.

N. 0° 01' W., bet. secs. 25 and 26.

Over gentle rolling bench land.

- 5.00 Dirt road, bears NE and SW.
- 32.75 Dirt road, bears NW and SE.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 22 E., Salt Lake Meridian, Utah

- 40.23 The 1/4 sec. cor. of secs. 25 and 26, monumented with a shale stone, 14 x 12 x 8 ins., firmly set, projecting 8 ins. above ground, plainly mkd. 1/4 on W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 22 E
1/4
S 26   S 25
1985

Deposit the mkd. stone alongside the aluminum post.

N. 0° 06' W., beginning new measurement.

- 40.28 The cor. of secs. 23, 24, 25, and 26, monumented with a sandstone, 15 x 8 x 5 ins., firmly set, projecting 8 ins. above ground, plainly mkd. 2 notches on the S and 1 notch on the E edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 22 E
S 23   S 24
S 26   S 25
1985

Deposit the mkd. stone alongside the aluminum post.

Cor. is located near E edge of draw, which drains NE.

From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., monumented with an aluminum post, 2 1/2 ins. diam., set, and mkd. as described in the official record of the dependent resurvey of the W. bdy. of T. 3 S., R. 23 E. in 1984.

N. 89° 53' W., bet. secs. 24 and 25.

Over rolling bench land.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 22 E., Salt Lake Meridian, Utah

20.14 Point for the E 1/16 sec. cor. of secs. 24 and 25.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 22 E  
          S 24  
E 1/16    S 25  
          1985

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, N of cor.

30.50 Center line of paved road, bears N and S.

40.28 True point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate distance, falls in Brush Creek, which flows SE irregularly; there is no remaining evidence of the original corner.

43.26 Point selected for the witness cor. to the 1/4 sec. cor. of secs. 24 and 25.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.

W C  
T 3 S R 22 E  
          S 24  
1/4      S 25 →  
          1985

46.00 Gravel road, bears N. 10° W. and S. 10° E.

50.35 Point for the E-W 1/64 sec. cor. of secs. 24 and 25.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

          S 24  
E-W 1/64   S 25  
          1985

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, N of cor.

60.42 Point for the W 1/16 sec. cor. of secs. 24 and 25.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 22 E., Salt Lake Meridian, Utah

T 3 S R 22 E  
S 24  
W 1/16  $\frac{S 25}{1985}$

- 80.56 Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, N of cor.  
The cor. of secs. 23, 24, 25, and 26.
- 

N. 0° 11' E., bet. secs. 23 and 24.

Over rolling bench land.

- 20.01 Point for the S 1/16 sec. cor. of secs. 23 and 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in  
the ground, with aluminum cap mkd.

T 3 S R 22 E  
S 1/16  
S 23 | S 24  
1985

- 40.02 The 1/4 sec. cor. of secs. 23 and 24, monumented with a limestone,  
14 x 12 x 10 ins., firmly set, projecting 8 ins. above ground,  
mkd. 1/4 on the W. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in  
the ground, with aluminum cap mkd.

T 3 S R 22 E  
1/4  
S 23 | S 24  
1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W of cor.

---

N. 0° 01' W., beginning new measurement.

- 20.13 Point for the N 1/16 sec. cor. of secs. 23 and 24.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 22 E., Salt Lake Meridian, Utah

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 22 E  
N 1/16  
S 23 | S 24  
1985

Raise a mound of stone, 2 1/2 base, 1 1/2 ft. high, W. of cor.

28.75 Gravel road, bears irregularly NW and SE.

29.00 Fence line, bears irregularly NW and SE; enter cultivated land.

30.195 Point for the N-N 1/64 sec. cor. of secs. 23 and 24.

Set an aluminum pipe, 2 1/2 ins. diam., 15 ins. long, 14 ins. below surface of cultivated land, with aluminum cap mkd.

N-N 1/64  
S 23 | S 24  
1985

From this cor. point, a fence line, which bears NW and SE, bears W, 1.225 chs. dist.

40.26 Point for the cor. of secs. 13, 14, 23, and 24, at proportionate distance; there is no remaining evidence of the original cor.

This cor. point falls in cultivated land and is not monumented.

From this cor. point, the 1/4 sec. cor. of secs. 13 and 14, monumented with a sandstone, 14 x 12 x 6 ins., firmly set, projecting 4 ins. above ground, plainly mkd. 1/4 on W face, bears N. 0° 11' E., 40.26 chs. dist.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 22 E  
1/4  
S 14 | S 13  
1985

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 22 E., Salt Lake Meridian, Utah

Deposit the mkd. stone alongside the aluminum post.

From this same cor. point, the 1/4 sec. cor. of secs. 14 and 23, monumented with a sandstone, 4 x 12 x 6 ins., firmly set, projecting 6 ins. above ground, plainly mkd. 1/4 on N. face, bears S. 89° 44' W., 40.085 chs. dist.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 22 E  
          S 14  
1/4     S 23  
          1985

Deposit the mkd. stone alongside the aluminum post.

---

From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., monumented with an aluminum post, 2 1/2 ins. diam., set, and mkd. witnessed as described in the official record of the dependent resurvey of the W. bdy. of T. 3 S., R. 23 E. in 1984.

S. 89° 54' W., bet. secs. 13 and 24.

Over broken bench land.

37.00 Center of paved road, bears irregularly S and curves NE.

40.15 The 1/4 sec. cor. of secs. 13 and 24, monumented with a sandstone, 14 x 12 x 6 ins., firmly set, projecting 8 ins. above ground, dimly mkd. 1/4 on N face and a scattered mound of stone to N.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 22 E  
          S 13  
1/4     S 24  
          1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.

---

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 22 E., Salt Lake Meridian, Utah

N. 89° 18' W., beginning new measurement.

20.125 Point for the W 1/16 sec. cor. of secs. 13 and 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in  
the ground, with aluminum cap mkd.

T 3 S R 22 E  
          S 13  
W 1/16    S 24  
          1985

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, N of cor.

32.00 Brush Creek, flows SE.

40.25 Point for the cor. of secs. 13, 14, 23, and 24.

Survey of the Subdivision of Section 24,  
T. 3 S., R. 22 E., Salt Lake Meridian, Utah

From true point for the 1/4 sec. cor. of secs. 24 and 25.

N. 0° 04' E., on the N. and S. center line of section 24.

Along bottom of Brush Creek.

9.99 Point for the C-S-S 1/64 sec. cor. of sec. 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in  
the ground, with aluminum cap mkd.

C-S-S 1/64 S24  
          1985


Cor. is located 15 lks. S. of fence line which bears E and W.

19.50 Brush Creek, flows SW.

19.98 Point for the C-S 1/16 sec. cor. of sec. 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in  
the ground, with aluminum cap mkd.

Survey of the Subdivision of Section 24,  
T. 3 S., R. 22 E., Salt Lake Meridian, Utah



Cor. is located on W side and near hairpin bend of Brush Creek, which flows irregularly SE.

39.90 Center of paved road, bears N and curves SE.

39.96 Point for the center 1/4 sec. cor. of sec. 24, at intersection with the E and W center line, falls in E edge of paved road.

At corner point, I set a nail, 4 ins. long, flush with surface of pavement, from which


An aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with mound of stone to W, for a reference monument, bears S. 45° E., 51 1/2 lks. dist. with aluminum cap, mkd. T3S R22E C 1/4 S24 RM 34.0 ft. 1985, and an arrow pointing to the cor.

An aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with mound of stone to W, for a reference monument, bears N. 45° E., 51 1/2 lks. dist. with aluminum cap, mkd. T3S R22E C 1/4 S24 RM 34.0 ft. 1985, and an arrow pointing to the cor.

55.50 Center of paved road, bears NNE and SSW.

59.91 Point for the C-N 1/16 sec. cor. of sec. 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.



Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W of cor.

Cor. is located 32 lks. W and 150 lks. N of paved road.

Survey of the Subdivision of Section 24,  
T. 3 S., R. 22 E., Salt Lake Meridian, Utah

79.86 The 1/4 sec. cor. of secs. 13 and 24.

---

From the 1/4 sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp., monumented with an aluminum post, 2 1/2 ins. diam., set and mkd. as described in the official record of the dependent resurvey of the W. bdy. of T. 3 S., R. 23 E. in 1984.

N. 89° 48' W., on the E and W center line of sec. 24.

Over broken bench land.

20.12 Point for the C-E 1/16 sec. cor. of sec. 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

S 24  
C-E 1/16 C  
1985

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, N of cor.

40.24 The center 1/4 sec. cor. of sec. 24.

40.30 Center of paved road, bears N and curves SE.

50.00 Brush Creek, flows SE.

55.00 Gravel road, bars SSE and NNW.

60.34 Point for the C-W 1/16 sec. cor. of sec. 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

S 24  
C-W 1/16 C  
1985

80.44 The 1/4 sec. cor. of secs. 23 and 24.

---

From the E 1/16 sec. cor. of secs. 24 and 25.

N. 0° 02' 30" E., on the N and S center line of the SE 1/4 of sec. 24.

Survey of the Subdivision of Section 24,  
T. 3 S., R. 22 E., Salt Lake Meridian, Utah

39.93 The C-E 1/16 sec. cor. of sec. 24.

---

From the W 1/16 sec. cor. of secs. 24 and 25.

N. 0° 08' E., on the N and S center line of the SW 1/4 of sec. 24.

10.00 Point for the C-S-SW 1/64 sec. cor. of sec. 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

C-S-SW 1/64

S 24

1985

20.00 Point for the SW 1/16 sec. cor. of sec. 24, at intersection with the E and W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

SW 1/16 S 24

1985

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W of cor.

40.00 The C-W 1/16 sec. cor. of sec. 24.

---

From the C-S 1/16 sec. cor. of sec. 24.

N. 89° 51' W., on the E and W center line of the SW 1/4 of sec. 24.

2.515 Point for the 1/1024 sec. cor. of sec. 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

1/1024

1985

10.06 Point for the C-E-SW 1/64 sec. cor. of sec. 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Survey of the Subdivision of Section 24,  
T. 3 S., R. 22 E., Salt Lake Meridian, Utah

C-E-SW 1/64  
S 24  
1985

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.

- 10.50 Gravel road, bears SSE and NNW.  
20.12 The SW 1/16 sec. cor. of sec. 24.  
40.24 The S 1/16 sec. cor. of secs. 23 and 24.

---

From the E-W 1/64 sec. cor. of secs. 24 and 25.

N. 0° 06' E., on the N and S center line of the SE 1/4 of the SW 1/4 of sec. 24.

- 9.995 Point for the SE-SW 1/64 sec. cor. of sec. 24, at intersection with the E and W center line of the SE 1/4 of the SW 1/4 of sec. 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

SE-SW 1/64 S 24  
1985

- 18.50 Gravel road, bears SSE and NNW.  
19.99 The C-E-SW 1/64 sec. cor. of sec. 24.

---

From the C-S-S 1/64 sec. cor. of sec. 24.

N. 89° 52' W., on the E and W center line of the SE 1/4 of the SW 1/4 of sec. 24.

- 2.515 Point for the 1/1024 sec. cor. of sec. 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

1/1024  
1985

- 5.50 Brush Creek, flows S.

Survey of the Subdivision of Section 24,  
T. 3 S., R. 22 E., Salt Lake Meridian, Utah

8.50 Gravel road, bears SSE and NNW.

10.06 The SE-SW 1/64 sec. cor. of sec. 24.

20.12 The C-S-SW 1/64 sec. cor. of sec. 24.

From the 1/1024 sec. cor. on the E-W center line of the SE 1/4 of the SW 1/4 of sec. 24.

N. 0° 04' E., on the N-S center line of the E 1/2 of the NE 1/4 of the SE 1/4 of the SW 1/4 of sec. 24.

8.50 Brush Creek, flows SW.

9.99 The 1/1024 sec. cor. on the E-W center line of the Sw 1/4 of sec. 24.

From the C-W 1/16 sec. cor. of sec. 24.

N. 0° 01' E., on the N and S center line of the NW 1/4 of sec. 24.

12.50 Gravel road, bears SSE and NNW.

15.00 Brush Creek, flows E.

20.04 Point for the NW 1/16 sec. cor. of sec. 24, at intersection with the E and W center line of the NW 1/4 of sec. 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 in the ground, with aluminum cap mkd.

NW 1/16 S 24  
1985

40.08 The W 1/16 sec. cor. of secs. 13 and 24.

From the C-N 1/16 sec. cor. of sec. 24.

N. 89° 33' W., on the E and W center line of the NW 1/4 of sec. 24.

20.11 The NW 1/16 sec. cor. of sec. 24.

22.00 Brush Creek, flows SSE.

24.50 Gravel road, bears NW and SE.

40.22 The N. 1/16 sec. cor. of secs. 23 and 24.

Survey of the Subdivision of Section 25,  
T. 3 S., R. 22 E., Salt Lake Meridian, Utah

Survey of the Subdivision of Section 25,  
T. 3 S., R. 22 E., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 25 and 36.

N. 0° 05' E., on the N and S center line of sec. 25.

Over rolling bench land, along N-S fence line.

- 39.48 Point for the center 1/4 sec. cor. of sec. 25, at intersection with the E and W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 22 E  
C 1/4 S 25  
1985

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W of cor.

Cor. is located 11 lks. W of N-S fence line.

- 59.62 Point for the C-N 1/16 sec. cor. of sec. 25, falls in Brush Creek and cannot be monumented.

- 60.855 Point selected for the witness cor. to the C-N 1/16 sec. cor. of sec. 25.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

W C  
C  
N 1/16 ↓ S 25  
C  
1985

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

- 61.50 Center of paved road, bears irregularly NE and S.

- 79.76 True point for the 1/4 sec. cor. of secs. 24 and 25.
- 

From the 1/4 sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp., monumented with an aluminum post, 2 1/2 ins. diam., set, and mkd. as described in the official record of the dependent resurvey of the W. bdy. of T. 3 S., R. 23 E. in 1984.

Survey of the Subdivision of Section 25,  
T. 3 S., R. 22 E., Salt Lake Meridian, Utah

N. 89° 54' W., on the E and W center line of sec. 25.

Over rolling bench land.

- 20.20 Point for the C-E 1/16 sec. cor. of sec. 25, not monumented.
- 25.50 Brush Creek, flows SW.
- 40.40 The center 1/4 sec. cor. of sec. 25.
- 42.00 Center of paved road, bears irregularly N and S.
- 47.00 Gravel road, bears ENE and WSW.
- 80.55 The 1/4 sec. cor. of secs. 25 and 26.

From the point for the C-E 1/16 sec. cor. of sec. 25.

N. 0° 01' W., on the N and S center line of the NE 1/4 of sec. 25.

- 20.135 Point for the NE 1/16 sec. cor. of sec. 25, at intersection with the E and W center line of the NE 1/4 of sec. 25.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

NE 1/16 S 25  
1985

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

- 40.27 The E 1/16 sec. cor. of secs. 24 and 25.

From the N 1/16 sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp., monumented with an aluminum post, 2 1/2 ins. diam., set and mkd. as described in the official record of the dependent resurvey of W. bdy. of T. 3 S., R. 23 E. in 1984.

N. 89° 54' W., on the E and W center line of the NE 1/4 of sec. 25.

- 20.17 The NE 1/16 sec. cor. of sec. 25.
- 35.50 Brush Creek, flows SSW.
- 37.50 Brush Creek, flows NE.
- 40.34 True point for the witness C-N 1/16 sec. cor. of sec. 25.

Township 3 South, Range 22 East, Salt Lake Meridian, Utah

#### GENERAL DESCRIPTION

Township 3 South, Range 22 East is situated about 7 miles north of Vernal, Utah. The elevation varies from 5,500 to 6,500 feet above sea level. The soil is mostly loam to rocky and clay loam.

Red Fleet Reservoir is located in the northwest portion of the township and there are several ranches located along the bottom of Brush Creek.

A paved road crosses the southeast portion of the township with a few gravel roads and some trail roads serving the northern portion.

The Brush Creek flow is regulated by the Red Fleet Reservoir and flows in a southeasterly direction through the township.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

## FIELD ASSISTANTS

Douglas Morlan	Survey Aid
Kenneth Chynoweth	Survey Aid

## CERTIFICATE OF SURVEY

I, Jerry L. Thomas, Cadastral Surveyor, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 15th day of October, 1985, I have dependently resurveyed a portion of the subdivisional lines and surveyed the subdivision of sections 24 and 25 of Township 3 South, Range 22 East,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

September 28, 1988  
(Date)

*Jerry L. Thomas*  
(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines and the subdivisional survey of sections 24 and 25 of Township 3 South, Range 22 East, Salt Lake Meridian, Utah

executed by Jerry L. Thomas, Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

October 18, 1988  
(Date)

*Glen B Hatch*  
(Chief, Cadastral Surveyor for Utah)



INDEX DIAGRAM

Township 3 South, Range 20 East

	6	6	5	4	3	2
18	6 92	5 80	4 73	3 66	2 58	1
	91			72	65	57
						30
17	7	8	9	10 65	11 56	12
				72	64	55
						29
15	18	17	16	15 63	14 54	13
	88	90	80	71	62	53
13	19 87	20 78	21 70	22 61	23 52	24
	86	85 86	77	69	32	31
						28
10	30 84	29 76	28 68	27 60	26 51	25
	83	82 83	75	66	59	50
		76				
8	31 81	32	33 67	34 58	35 48	36
	27	26 74	24	22	20	19

- FORT THORNBURG BOUNDARY
- Pages 31-48
  - Page 92
  - Page 95
  - Page 98
  - Page 99
  - Page 101
  - Page 104
  - Page 107
  - Page 110
  - Page 113
  - Page 114
  - Page 118
  - Page 120
  - Page 123
  - Page 127
  - Page 130
  - Page 131
  - Page 132
  - Page 135
  - Page 137

## Township 3 South, Range 20 East, Salt Lake Meridian, Utah

The following field notes describe the dependent resurvey of the north, south and west boundaries, a portion of the east boundary, a portion of the Fort Thornburg Military reservation boundary, a portion of the subdivisional lines and the survey of the subdivision of certain sections in T. 3 S., R. 20 E., Salt Lake Meridian, Utah.

History of Surveys

	<u>Surveyed by</u>		<u>Retr. or Resurveyed by</u>	
<u>SOUTH BOUNDARY</u>				
Portion	A. D. Ferron and E. Buettner	1879		
Portion	A. Jessen	1900		
Portion			A. Jessen	1900
Portion	S. P. Stewart J. R. Stewart	1906		
<u>EAST BOUNDARY</u>				
All	A.D. Ferron and E. Buettner	1879		
Portion			A. Jessen	1900
Portion			A. Jessen and Harmston	1900
All			J.L. Thomas	1973
<u>WEST BOUNDARY</u>				
All	A.D. Ferron and E. Buettner	1879		
Portion			S. P. Stewart and J. R. Stewart	1906
<u>NORTH BOUNDARY</u>				
All	A. D. Ferron and E. Buettner	1879		
<u>SUBDIVISION</u>				
Portion	A. D. Ferron and E. Buettner	1879		
Portion	A. Jessen	1900		
Portion			A. Jessen	1900
Portion			S. P. Stewart and J. R. Stewart	1906
Portion			G. E. Reynolds	1980

## Township 3 South, Range 20 East, Salt Lake Meridian, Utah

The portion of the Fort Thornburg Military Reservation Boundary which is located in this township was surveyed by A. Jessen in 1900.

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group 653, Utah, dated August 23, 1984.

The directions of lines were determined by reference to true meridians established on line by altitude observations on the sun, and by hour angle observations on Polaris. The lines were carried forward by sustained angulations, being supplemented by other observations on Polaris taken throughout the progress of the survey. Distances were determined by electronic measurement.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions, lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The southeast corner of the township, has been designated as a BLM control station and the geographic coordinates, as determined by satellite methods, are as follows:

Latitude  $40^{\circ} 30' 21.790''$  N. Longitude  $109^{\circ} 36' 52.312''$  W.  
N.A.D. 1927

The mean magnetic declination, as projected from the U.S. Geological Survey Magnetic Declination Map of 1980, is  $14^{\circ}$  E.

---

Dependent Resurvey of the North Boundary,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

---

(Restoring the Survey Executed by  
A. D. Ferron and E. Buettner in 1879)

---

Beginning at the cor. of Tps. 2 and 3 S., Rs. 20 and 21 E., monumented with an iron post, 3 ins. diam., firmly set, protruding 4 ins. above mound of stone, with brass cap, mkd. as described in the official record of the 1973 resurvey of the E. bdy. of T. 3 S., R. 20 E., from which the original bearing trees

A juniper, 5 ins. diam., bears N.  $40^{\circ}$  E., 41 lks.  
dist., mkd. T2S R21E S31 BT.

A juniper, 8 ins. diam., bears S.  $18 \frac{3}{4}^{\circ}$  E.,  
58 lks. dist., mkd. T3S R21E S6 BT.

Dependent Resurvey of the North Boundary,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

A juniper, 7 ins. diam., bears S. 20 1/2° W.,  
44 lks. dist., mkd. T3S R20E S1 BT.

A pinon, 18 ins. diam., bears N. 49 3/4° W.,  
23 lks. dist., mkd. T2S R20E S36 BT.

S. 88° 31' W., on the N. bdy. of sec. 1.

Over broken mountainous land through scattered juniper and pinon.

- 30.00 Ashley Creek in the bottom of Ashley Gorge, flows irregularly S;  
asc. over broken and steep E slope.
- 39.77 Point for the 1/4 sec. cor. of sec. 1 only, falls on inaccessible  
steep and rugged slope of Ashley Gorge Canyon. This corner point  
is not monumented.
- 65.00 W rim of canyon, bears NE and SW; asc. over SE slope.
- 79.54 Point for the cor. of secs. 1 and 2 only, at proportionate  
distance; there is no remaining evidence of the original cor.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in  
the ground to bedrock, and in a mound of stone, 4 1/2 ft. base, to  
top of aluminum cap, mkd.

---

S 2 | S 1  
T 3 S R 20 E  
1984

---

S. 88° 31' W., on the N. bdy. of sec. 2.

Over rolling mountainous land.

- 39.77 Point for the 1/4 sec. cor. of sec. 2 only, at proportionate  
distance; there is no remaining evidence of the original cor.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in  
the ground to bedrock, and in a mound of stone, 4 1/2 ft. base, to  
top of aluminum cap, mkd.

---

1/4 S 2  
T 3 S R 20 E  
1984

Dependent Resurvey of the North Boundary,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

- 79.54 The cor. of secs. 2 and 3 only, monumented with a sandstone, 14x10x8 ins., firmly set, protruding 10 ins. above ground, dimly mkd. 4 notches on the W and 2 notches on the E edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

S 3 | S 2  
T 3 S R 20 E  
1984

Deposit the mkd. stone alongside the aluminum post.

---

S. 89° 24' W., on the N. bdy. of sec. 3.

Over mountainous land.

- 39.44 Point for the 1/4 sec. cor. of sec. 3 only, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4 1/2 ft. base, to top of aluminum cap, mkd.

1/4 S 3  
T 3 S R 20 E  
1984

Cor. is located 17 1/2 lks. N of fence line, which bears E and W.

- 59.16 Point for the W 1/16 sec. cor. of sec. 3 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4 1/2 ft. base, to top of aluminum cap, mkd.

W 1/16 S 3  
T 3 S R 20 E  
1984

Dependent Resurvey of the North Boundary,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

- 78.88 The cor. of secs. 3 and 4 only, monumented with a sandstone, 18x10x6 ins., firmly set, protruding 8 ins. above ground, dimly mkd. 3 notches on the E and W edges.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

S 4	S 3
T 3 S R 20 E	
1984	

N. 89° 29' W., on the N. bdy. of sec. 4.

Over mountainous land.

- 39.44 The 1/4 sec. cor. of sec. 4 only, monumented with a quartzite stone, 22x15x12 ins., firmly set, protruding 12 ins. above ground, plainly mkd., 2 1/2 ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

1/4 S 4	
T 3 S R 20 E	
1984	

Deposit the mkd. stone alongside the aluminum post.

Cor. is located 15 lks. S of fence line, which bears E and W.

S. 89° 56' W., beginning new measurement.

Over broken mountainous land.

- 40.58 The cor. of secs. 4 and 5 only, monumented with a sandstone, 30x16x6 ins., firmly set, projecting 16 ins. above ground, dimly mkd. 2 notches on the W and 4 notches on the E edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

Dependent Resurvey of the North Boundary,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

S 5 | S 4  
T 3 S R 20 E  
1984

Deposit the mkd. stone alongside the aluminum post.

Cor. is located 3 lks. N of fence line, which bears E and W.

---

S. 89° 02' W., on the N bdy. of sec. 5.

Over rolling mountainous land.

- 40.06 Point for the 1/4 sec. cor. of sec. 5 only, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.

1/4 S 5  
T 3 S R 20 E  
1984

- 80.12 The cor. of secs. 5 and 6 only, monumented with a sandstone, 11x7x7 ins., firmly set, protruding 8 ins. above ground, dimly mkd. 1 notch on the W edge.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

S 6 | S 5  
T 3 S R 20 E  
1984

Deposit the mkd. stone alongside the aluminum post.

Cor. is located 25 lks. S of fence line, which bears E and W.

---

S. 89° 01' W., on the N. bdy. of sec. 6.

Over broken mountainous land.

Dependent Resurvey of the North Boundary,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

- 40.25 Point for the 1/4 sec. cor. of sec. 6 only, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

-----  
1/4 S 6  
T 3 S R 20 E  
1984

- 54.00 Red Cloud Loop Road, in the bottom of Dry Fork Canyon, bears NW and SE; asc. over steep NE slope.

- 78.70 Point for the Tp. cor. of T. 3 S., Rs. 19 and 20 E., at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

-----  
S 1 | S 6  
T 3 S  
R 19 E R 20 E  
1984

Cor. is located on steep and rocky N slope.

From this cor., the 1/4 sec. cor. of sec. 1 only, T. 3 S., R. 19 E., monumented with a sandstone, 20x10x8 ins., firmly set, protruding 10 ins. above ground, plainly mkd. 1/4 on N face, bears S. 89° 39' W., 40.24 chs. dist.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

-----  
1/4 S 1  
T 3 S R 19 E  
1984

Deposit the mkd. stone alongside the aluminum post.

---

Dependent Resurvey of the East Boundary,  
T. 3 S., R. 19 E., Salt Lake Meridian, Utah

Dependent Resurvey of the East Boundary,  
T. 3 S., R. 19 E., Salt Lake Meridian, Utah

---

(Restoring the Survey Executed by  
A. D. Ferron and E. Buettner in 1879 and  
S.P. and J.R. Stewart in 1906)

---

From the cor. of Tps. 3 and 4 S., R. 19 E., monumented with a sandstone, 20x14x8 ins., firmly set, protruding 12 ins. above ground, plainly mkd. 6 grooves on the N, S and W face, and a scattered mound of stone to the W.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

```

      T 3 S
      R 19 E R 20 E
      S 36 |
      S 1 | S 6
      T 4 S
      1984
  
```

Deposit the mkd. stone alongside the aluminum post.

N. 0° 09' W., on the E. bdy. of sec. 36.

Over mountainous land, through scattered juniper and pinon.

3.88 Point selected for the witness cor. to the closing Tp. cor. of Tps. 3 and 4 S., R. 20 E.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

```

      W C
      T 3 S
      R 19 E R 20 E
      S 36 | S 31 | C
      S 1 | S 6 | C
      T 4 S
      1984
  
```

Dependent Resurvey of the East Boundary,  
T. 3 S., R. 19 E., Salt Lake Meridian, Utah

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, E of cor.

- 4.58 True point for the closing Tp. cor. of Tps. 3 and 4 S., R. 20 E., determined from the remains of the original bearing trees, falls in bottom of wash, 5 ft. deep, 20 lks. wide, and was unsafe to monument. From this point the original bearing trees

A cedar, 20 ins. diam., bears N. 74° 15' E.,  
22 1/2 lks. dist., mkd. T3S R20E S31 BT.

A cedar, 24 ins. diam., bears S. 50° 00' E.,  
53 lks. dist., mkd. T4S R20E S BT.

- 40.21 The 1/4 sec. cor. of sec. 36 only, monumented with a sandstone, 18x10x6 ins., firmly set, protruding 8 ins. above ground, plainly mkd. 1/4 on W face, and a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.

T 3 S  
R 19 E R 20 E  
1/4 |  
S 36 |  
1984

Deposit the mkd. stone alongside the aluminum post.

N. 0° 07' E., beginning new measurement.

- 4.02 Point selected for the witness cor. to the 1/4 sec. cor. of sec. 31 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of aluminum cap, mkd.

W C  
T 3 S  
R 19 E R 20 E  
↑ 1/4  
| S 31  
1984

Dependent Resurvey of the East Boundary,  
T. 3 S., R. 19 E., Salt Lake Meridian, Utah

4.14 True point for the 1/4 sec. cor. of sec. 31 only, at midpoint on the W. bdy. of sec. 31, falls in bottom of wash and is unsafe to monument.

24.025 Point for the N 1/16 sec. cor. of sec. 31 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 3 S  
R 19 E R 20 E  
| N 1/16  
| S 31  
1984

39.93 The cor. of secs. 25 and 36 only, T. 3 S., R. 19 E., monumented with a sandstone, 16x12x10 ins., firmly set, protruding 10 ins. above ground, plainly mkd. 5 notches on N and 1 notch on S edge, from which the original bearing trees

A cedar, 22 ins. diam., bears S. 45° 00' W., 12 lks. dist., mkd. T3S R19E S36 BT.

A cedar, 16 ins. diam., bears N. 25° 00' W., 23 lks. dist., mkd. T3S R19E S25 BT.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 3 S  
R 19 E R 20 E  
S 25 |  
S 36 | S 31  
1984

Deposit the mkd. stone alongside the aluminum post.

---

N. 0° 36' W., on the E. bdy. of sec. 25.

Over mountainous land through scattered juniper and pinon.

3.98 The closing cor. of secs. 30 and 31, T. 3 S., R. 20 E., monumented with a limestone, 18x6x6 ins., firmly set, projecting 10 ins. above ground, plainly mkd. CC on E face, 1 notch on S and 5 notches on N edge, from which the original bearing trees

Dependent Resurvey of the East Boundary,  
T. 3 S., R. 19 E., Salt Lake Meridian, Utah

A cedar, 10 ins. diam., bears N.  $67^{\circ} 00'$  E.,  
18 lks. dist., mkd. T3S R20E CC S30 BT.

A cedar, 7 ins. diam., bears S.  $15^{\circ} 00'$  E., 50 lks.  
dist., mkd. T3S R20E CC S31 BT.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in  
the ground, with aluminum cap mkd.

T 3 S		
R 19 E	R 20 E	
S 25	S 30	C
	S 31	C
1984		

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, E of cor.

40.51 The 1/4 sec. cor. of sec. 25 only, T. 3 S., R. 19 E., determined  
from the original bearing trees, from which

A cedar, 12 ins. diam., bears S.  $43^{\circ} 00'$  E.  
25 lks. dist., mkd. 1/4 S BT.

A cedar, 30 ins. diam., bears S.  $60^{\circ} 00'$  W.,  
20 lks. dist., mkd. 1/4 S BT.

There is no remaining evidence of the mkd. rock.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in  
the ground to bedrock, and in a collar of stone, 3 1/2 ft. base,  
to top of aluminum cap, mkd.

T 3 S		
R 19 E	R 20 E	
1/4		
S 25		
1984		

---

N.  $0^{\circ} 14'$  W., beginning new measurement.

3.43 Point for the 1/4 sec. cor. of sec. 30 only, at midpoint on the W.  
bdy. of sec. 30.

Dependent Resurvey of the East Boundary,  
T. 3 S., R. 19 E., Salt Lake Meridian, Utah

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.

T 3 S  
R 19 E R 20 E  
| 1/4  
| S 30  
1984

19.93 Point for the N 1/16 sec. cor. of sec. 25 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.

T 3 S  
R 19 E R 20 E  
N 1/16 |  
S 25 |  
1984

23.405 Point for the N 1/16 sec. cor. of sec. 30 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 3 S  
R 19 E R 20 E  
| N 1/16  
| S 30  
1984

39.86 The cor. of secs. 24 and 25 only, T. 3 S., R. 19 E., monumented with a sandstone, 18x9x8 ins., firmly set, protruding 10 ins. above ground, dimly mkd. 4 notches on N edge.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.

T 3 S  
R 19 E R 20 E  
S 24 |  
S 25 | S 30  
1984

Dependent Resurvey of the East Boundary,  
T. 3 S., R. 19 E., Salt Lake Meridian, Utah

Deposit the mkd. stone alongside the aluminum post.

---

N. 0° 45' W., on the E. bdy. of sec. 24.

Over mountainous land through scattered juniper and pinon.

- 3.52 The closing cor. of secs. 19 and 30, T. 3 S., R. 20 E., monumented with a sandstone, 16x10x8 ins., firmly set, protruding 8 ins. above ground, plainly mkd. CC on E, 4 grooves on N and 2 grooves on S face, from which the original bearing trees

A cedar, 6 ins. diam., bears N. 60° 00' E., 6 lks.  
dist., mkd. T3S R20E S19 BT.

A cedar, 6 ins. diam., bears S. 25° 00' E., 30 lks.  
dist., mkd. T3S R20E S30 BT.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.

```

      T 3 S
    R 19 E R 20 E
      | S 19   C
    S 24 | S 30   C
          1984
  
```

Deposit the mkd. stone alongside the aluminum post.

- 23.495 Point for the S 1/16 sec. cor. of sec. 19 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 5 ft. base, to top of aluminum cap, mkd.

```

      T 3 S
    R 19 E R 20 E
      | S 1/16
      | S 19
          1984
  
```

- 40.34 The 1/4 sec. cor. of sec. 24 only, T. 3 S., R. 19 E., monumented with a gray sandstone, 20x12x6 ins., firmly set, protruding 3 ins. above ground, dimly mkd. 1/4 on W face.

Dependent Resurvey of the East Boundary,  
T. 3 S., R. 19 E., Salt Lake Meridian, Utah

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.

T 3 S  
R 19 E R 20 E  
1/4 |  
S 24 |  
1984

Deposit the mkd. stone alongside the aluminum post.

Cor. is located under fence line, bearing E and W, and 189 lks. W of fence cor., with fences bearing N and W.

N. 0° 26' W., beginning new measurement.

- 3.13 Point for the 1/4 sec. cor. of sec. 19 only, T. 3 S., R. 20 E., at proportionate distance and on the W. bdy. of sec. 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 3 S  
R 19 E R 20 E  
| 1/4  
| S 19  
1984

- 19.98 Point for the N 1/16 sec. cor. of sec. 24 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 3 S  
R 19 E R 20 E  
N 1/16 |  
S 24 |  
1984

Corner is located 4 lks. N and 14 1/2 lks. W of fence cor., from which fences bear N and W.

Dependent Resurvey of the East Boundary,  
T. 3 S., R. 19 E., Salt Lake Meridian, Utah

- 23.105 Point for the N 1/16 sec. cor. of sec. 19 only, T. 3 S., R. 20 E., at proportionate distance and on the W. bdy. of sec. 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 3 S  
R 19 E R 20 E  
| N 1/16  
| S 19  
1984

Cor. is located 15 1/2 lks. W of N and S fence line.

- 39.96 The cor. of secs. 13, 18, 19, and 24, monumented with a sandstone, 20x14x8 ins., firmly set, protruding 12 ins. above ground, plainly mkd. 3 notches on the N and S edges and a scattered mound of stone to the E.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 4 1/2 ft. base, to top of aluminum cap, mkd.

T 3 S  
R 19 E R 20 E  
S 13 | S 18  
S 24 | S 19  
1984

Deposit the mkd. stone alongside the aluminum post.

Cor. is located in fence line, which bears N and S.

(Restoring the Survey Executed by  
A.D. Ferron and E. Buettner in 1879)

N. 0° 50' W., bet. secs. 13 and 18.

Over broken mountainous land through scattered juniper and pinon.

- 20.07 Point for the S 1/16 sec. cor. of secs. 13 and 18.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Dependent Resurvey of the East Boundary,  
T. 3 S., R. 19 E., Salt Lake Meridian, Utah

T 3 S  
R 19 E R 20 E  
S 1/16  
S 13 | S 18  
1985

Cor. is located on gentle N slope, 5 1/2 lks. N of fence cor.,  
from which fences bear S and E.

33.50 Gravel road, bears E and W.

40.14 The 1/4 sec. cor. of secs. 13 and 18, monumented with a sandstone,  
10x10x6 ins., (record, 18x12x6 ins.), firmly set, protruding 4  
ins. above ground, plainly mkd. 1/4 on W face, from which the  
original bearing trees

A cedar, 20 ins. diam., bears S. 65° 00' W.,  
123 1/2 lks. dist., mkd. 1/4 S BT.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in  
the ground, with aluminum cap mkd.

T 3 S  
R 19 E R 20 E  
1/4  
S 13 | S 18  
1984

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

N. 10° 18' E., beginning new measurement.

20.055 Point selected for the witness cor. to the N 1/16 sec. cor. of  
secs. 13 and 18.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in  
the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to  
top of aluminum cap, mkd.

W C  
T 3 S  
R 19 E R 20 E  
N 1/16  
S 13 ↑ S 18  
1985

Dependent Resurvey of the East Boundary,  
T. 3 S., R. 19 E., Salt Lake Meridian, Utah

- 20.105 True point for the N 1/16 sec. cor. of secs. 13 and 18, falls in middle of large tree and cannot be monumented.
- 40.21 The cor. of secs. 7, 12, 13, and 18, monumented with a sandstone, 24x14x8 ins., firmly set in mound of stone, plainly mkd. 4 notches on S and 2 notches on N edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 3 S	
R 19 E	R 20 E
S 12	S 7
S 13	S 18
1984	

Deposit the mkd. stone alongside the aluminum post.

---

N. 10° 41' W., bet. secs. 7 and 12.

Over mountainous land, through scattered juniper and pinon.

- 40.48 The 1/4 sec. cor. of secs. 7 and 12, monumented with a sandstone, 25x22x12 ins., firmly set, protruding 15 ins. above ground, plainly mkd. 1/4 on E face, and scattered mound of stone to E.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.

T 3 S	
R 19 E	R 20 E
1/4	
S 12	S 7
1984	

Deposit the mkd. stone alongside the aluminum post.

This cor. has been designated as a BLM control station and the geographic coordinates, as determined by satellite methods, are as follows:

Latitude 40° 34' 14.322" N.      Longitude 109° 43' 44.900" W.  
N.A.D. 1927

---

Dependent Resurvey of the East Boundary,  
T. 3 S., R. 19 E., Salt Lake Meridian, Utah

N. 0° 06' W., beginning new measurement.

- 40.35 The cor. of secs. 1, 6, 7, and 12, monumented with a sandstone, 28x6x3 ins., firmly set, protruding 18 ins. above ground, dimly mkd. 5 notches on the S edge.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 3 S	
R 19 E	R 20 E
S 1	S 6
S 12	S 7
1984	

Deposit the mkd. stone alongside the aluminum post.

---

N. 0° 31' W., bet. secs. 1 and 6.

Over mountainous land through scattered juniper and pinon.

- 39.84 The 1/4 sec. cor. of secs. 1 and 6, monumented with a sandstone, 26x14x5 ins., firmly set, protruding 12 ins. above ground, dimly mkd. 1/4 on W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 3 S	
R 19 E	R 20 E
1/4	
S 1	S 6
1984	

Deposit the mkd. stone alongside the aluminum post.

---

N. 0° 25' W., beginning new measurement.

- 40.00 The Tp. cor. of Tp. 3 S., Rs. 19 and 20 E., hereinbefore described.
-

Dependent Resurvey of the South Boundary,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

Dependent Resurvey of the South Boundary,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

---

(Restoring the Survey Executed by A.D. Ferron  
and E. Buettner in 1879, and A. Jessen in 1900)

---

From the cor. of Tps. 3 and 4 S., Rs. 20 and 21 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, protruding 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1973 resurvey of the W. bdy. of T. 3 S., R. 21 E.

Note: This cor. has been designated a BLM control station, hereinbefore described.

S.89° 35' W., on the S. bdy. of sec. 36.

Over bench land through scattered juniper and pinon.

39.54 Point for the 1/4 sec. cor. of sec. 1 only, T. 4 S., R. 20 E., at midpoint and on the N. bdy. of sec. 1.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

---

1/4 S 1  
T 4 S R 20 E  
1984

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, S of cor.

Cor. is located 10 lks. E of wash, which drains S.

40.09 The 1/4 sec. cor. of sec. 36 only, monumented with a sandstone, 16x10x10 ins., firmly set, protruding 8 ins. above ground, mkd. 1/4 on N face, from which the remaining original bearing tree

A juniper, 24 ins. diam., bears N. 70° 00' E.,  
7 lks. dist., mkd. 1/4 S36 BT.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

---

T 3 S R 20 E  
1/4 S 36  
1984

Dependent Resurvey of the South Boundary,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.

N. 89° 31' W., beginning new measurement.

- 39.54 The closing cor. of secs. 1 and 2, T. 4 S., R. 20 E., monumented with a sandstone, 24x12x12 ins., firmly set, protruding 10 ins. above ground, plainly mkd. CC and 5 grooves on W face, and 1 groove on E face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, and in a collar of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
S 36  
-----  
S 2 | S 1  
C C  
T 4 S  
1984

Deposit the mkd. stone alongside the aluminum post.

- 40.30 The cor. of secs. 35 and 36 only, monumented with a sandstone, 30x18x7 ins., firmly set, protruding 15 ins. above ground, plainly mkd. 5 notches on W and 1 notch on E edge.

The original bearing trees have been destroyed.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 20 E  
S 35 | S 36  
-----  
1984

Deposit the mkd. stone alongside the aluminum post.

N. 89° 13' W., on the S. bdy. of sec. 35.

Over rolling bench land through scattered juniper and pinon.

Dependent Resurvey of the South Boundary,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

- 39.01 The 1/4 sec. cor. of sec. 35 only, monumented with a sandstone, 20x12x10 ins., loosely set, protruding 15 ins. above ground, plainly mkd. 1/4 on N face, from which the original bearing tree

A juniper, 12 ins. diam., bears N. 77° 00' W.,  
31 lks. dist., mkd. 1/4 S35 BT.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 4 1/2 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
-----  
1/4 S 35  
-----  
T 4 S  
1984

Deposit the mkd. stone alongside the aluminum post.

S. 89° 10' W., beginning new measurement.

- 40.25 The closing cor. of secs. 2 and 3, T. 4 S., R. 20 E., monumented with a sandstone, 10x10x6 ins., firmly set, protruding 4 ins. above ground, plainly mkd. 4 notches on W, 2 notches on E edges, and CC on S face, from which the original bearing tree

A juniper, 5 ins. diam., bears S. 55° 00' E.,  
17 1/2 lks. dist., mkd. T4S.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 20 E  
-----  
S 35  
-----  
S 3 | S 2  
-----  
C C  
T 4 S  
1984

Deposit the mkd. stone alongside the aluminum post.

- 40.92 The cor. of secs. 34 and 35 only, determined from the remaining original bearing tree

Dependent Resurvey of the South Boundary,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

A juniper, 8 ins. diam., bears N. 48° 00' W.,  
35 lks. dist., mkd. T3S R20E S34 BT.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in  
the ground, with aluminum cap mkd.

T 3 S R 20 E  
S 34 | S 35  
1984

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.

---

(Restoring the Survey Executed by  
A. Jessen in 1900)

---

S. 89° 22' W., on the S. bdy. of sec. 34.

Over rolling and broken bench land through scattered juniper and  
pinon.

36.03 Point for the 1/4 sec. cor. of sec. 3 only, T. 4 S., R. 20 E., at  
midpoint and on the N. bdy. of sec. 3.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in  
the ground to bedrock, and in a mound of stone, 4 ft. base, to top  
of aluminum cap, mkd.

1/4 S 3  
T 4 S R 20 E  
1984

39.97 Point for the 1/4 sec. cor. of sec. 34 only, at proportionate  
distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in  
the ground, with aluminum cap mkd.

T 3 S R 20 E  
1/4 S 34  
1984


Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.

Dependent Resurvey of the South Boundary,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

- 73.91 The closing cor. of secs. 3 and 34, Tps. 3 and 4 S., R. 20 E., on the Old Fort Thornburg Military Reservation Boundary, monumented with a sandstone, 15x12x8 ins., loosely set in a mound of stone, mkd. CC and 3 notches on W face and 3 notches on the E and W edge. The original bearing trees have been destroyed.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.



Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, E of cor.

---

(Restoring the Survey Executed by  
S.P. and J.R. Stewart in 1906)

---

S. 89° 04' W., beginning new measurement.

- 6.405 The cor. of secs. 33 and 34 only, monumented with a sandstone, 20x9x5 ins., firmly set, protruding 10 ins. above ground, plainly mkd. 3 notches on E and W edges, from which the original bearing tree

A juniper, 10 ins. diam., bears N. 24° 00' E.,  
64 lks. dist., mkd. T3S R20E S34 BT.

A juniper, 14 ins. diam., bears N. 56° 00' W.,  
71 lks. dist., mkd. T3S R20E S33 BT.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

Dependent Resurvey of the South Boundary,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

T 3 S R 20 E  
S 33 | S 34  
1984

Deposit the mkd. stone alongside the aluminum post.

---

N. 89° 56' W., on the S. bdy. of sec. 33.

Over mountainous land, through scattered juniper and pinon.

- 32.39 Point for the 1/4 sec. cor. of sec. 4 only, at midpoint and on the N. bdy. of sec. 4, T. 4 S., R. 20 E.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

1/4 S 4  
T 4 S R 20 E  
1985

- 39.85 The 1/4 sec. cor. of sec. 33 only, monumented with a sandstone, 16x10x6 ins., firmly set, protruding 10 ins. above ground, plainly mkd. 1/4 on the N face, from which the remaining original bearing tree

A juniper, 12 ins. diam., bears S. 18° 00' E.,  
35 lks. dist., mkd. 1/4 S BT.

The other bearing tree has been destroyed.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
1/4 S 33  
1984

Deposit the mkd. stone alongside the aluminum post.

---

Dependent Resurvey of the South Boundary,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

N.  $89^{\circ} 52'$  W., beginning new measurement.

19.955 Point for the W 1/16 sec. cor. of sec. 33 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 20 E  
W 1/16 S33  
1984

31.41 Dirt road, bears S and NE.

32.53 The closing cor. of secs. 4 and 5, T. 4 S., R. 20 E., monumented with a quartzite stone, 25x14x7 ins., firmly set, protruding 12 ins. above ground, plainly mkd. 4 grooves on E, 2 grooves on W, and CC on S face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 20 E  
S 33  
S 5 | S 4  
C C  
T 4 S  
1984

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, S of cor.

39.91 The cor. of secs. 32 and 33 only, monumented with a quartzite stone, 24x14x7 ins., firmly set, protruding 14 ins. above ground, plainly mkd. 4 notches on E and 2 notches on W edges, from which the original bearing trees

A juniper, 20 ins. diam., bears N.  $38^{\circ} 15'$  E.,  
144 lks. dist., mkd. T3S R20E S33 BT.

A juniper, 20 ins. diam., bears N.  $15^{\circ} 30'$  W.,  
58 lks. dist., mkd. T3S R20E S32 BT.

At the corner point

Dependent Resurvey of the South Boundary,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 4 1/2 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
S 32 | S 33  
1984

Deposit the mkd. stone alongside the aluminum post.

---

S. 89° 57' W., on the S. bdy. of sec. 32.

Over mountainous land, through scattered juniper and pinon.

32.475 Point for the 1/4 sec. cor. of sec. 5 only, at midpoint and on the N. bdy. of sec. 5, T. 4 S., R. 20 E.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

1/4 S 5  
T 4 S R 20 E  
1985

39.20 The 1/4 sec. cor. of sec. 32 only, monumented with a sandstone, 18x12x6 ins., loosely set in a mound of stone, plainly mkd. 1/4 on N face, from which the remaining original bearing tree

A juniper, 8 ins. diam., bears N. 79° 00' W.,  
66 lks. dist., mkd. 1/4 BT.

There is no remaining evidence of the other bearing tree.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
1/4 S 32  
1984

Deposit the mkd. stone alongside the aluminum post.

---

Dependent Resurvey of the South Boundary,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

N. 89° 52' W., beginning new measurement.

- 33.13 Point for the closing cor. of secs. 5 and 6, T. 4 S., R. 20 E., at proportionate distance; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 3 S
S 32
S 6   S 5
C C
T 4 S R 20 E
1984

Cor. is located on NE edge of old bulldozed road, which bears SE and W.

- 40.66 The cor. of secs. 31 and 32 only, monumented with a quartzite stone, 18x9x7 ins., firmly set, protruding 10 ins. above ground, plainly mkd. 5 notches on the E and 1 notch on W edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E
S 31   S 32
1984

Deposit the mkd. stone alongside the aluminum post.

---

N. 89° 47' W., on the S. bdy. of sec. 31.

Over rolling mountainous land.

- 32.57 Point for the 1/4 sec. cor. of sec. 6 only, T. 4 S., R. 20 E., at proportionate distance and on the N. bdy. of sec. 6.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Dependent Resurvey of the South Boundary,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

1/4 S 6  
T 4 S R 20 E  
1984

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, N of cor.

- 39.92 The 1/4 sec. cor. of sec. 31 only, monumented with a sandstone, 18x10x7 ins., firmly set, protruding 12 ins. above ground, plainly mkd. 1/4 on N face, and a scattered mound of stone to the N.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
1/4 S 31  
1984

Deposit the mkd. stone alongside the aluminum post.

N. 89° 54' W., beginning new measurement.

- 32.75 Point for the 80 1/16 sec. cor. of sec. 6 only, T. 4 S., R. 20 E., not monumented.
- 40.30 True point for the closing cor. of Tps. 3 and 4 S., R. 20 E., hereinbefore described.

---

Dependent Resurvey of a Portion of the East Boundary,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

---

(Restoring the Survey Executed by A.D. Ferron and  
E. Buettner in 1879, A. Jessen in 1900, and  
J. L. Thomas in 1973)

---

From the E 1/4 sec. cor. of sec. 25 only, monumented with an iron post, 2 1/2 ins. diam., firmly set, protruding 6 ins. above ground, with brass cap, mkd. as described in the official record of the dependent resurvey of the E. bdy. of T. 3 S., R. 20 E. in 1973.

Dependent Resurvey of a Portion of the East Boundary,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

N. 1° 47' W., on the E. bdy. of sec. 25.

- 8.00 Dry Fork Creek, 1.50 chs. wide, 6 ins. deep, flows SE.  
19.675 Point for the N 1/16 sec. cor. of sec. 25 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S  
R 20 E R 21 E  
N 1/16 |  
S 25 |  
1984

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

- 39.35 The cor. of secs. 24 and 25 only, T. 3 S., R. 20 E., monumented with an iron post, 2 1/2 ins., firmly set, protruding 6 ins. above mound of stone, with the brass cap, mkd. as described in the official record of the dependent resurvey of the E. bdy. of T. 3 S., R. 20 E. in 1973. This cor. also functions as Angle Point No. 2 of the Old Fort Thornburg Military Reservation Boundary.

---

(Restoring the Survey Executed by A. D. Ferron and  
E. Buettner in 1879, and the Dependent Resurvey  
by J. L. Thomas in 1973)

---

From the E 1/4 sec. cor. of sec. 13 only, monumented with an iron post, 2 1/2 ins. diam., firmly set, protruding 6 ins. above mound of stone, with brass cap, mkd. as described in the official record of the dependent resurvey of the E. bdy. of T. 3 S., R. 20 E. in 1973.

N. 0° 09' E., on the E. bdy. of sec. 13, T. 3 S., R. 20 E.

Over broken bench land.

- 4.59 The 1/4 sec. cor. of sec. 18 only, T. 3 S., R. 21 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, in a mound of stone, with brass cap, mkd. as described in the official record of the dependent resurvey of the E. bdy. of T. 3 S., R. 20 E. in 1973.  
19.065 Point for the N 1/16 sec. cor. of sec. 13 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Dependent Resurvey of a Portion of the East Boundary,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

T 3 S  
R 20 E R 21 E  
N 1/16 |  
S 13 |  
1984

- 38.13 The cor. of secs. 12 and 13 only, monumented with an iron post, 2 1/2 ins. diam., firmly set, protruding 6 ins. above ground, with brass cap, mkd. as described in the official record of the dependent resurvey of the E. bdy. of T. 3 S., R. 20 E., in 1973.

---

From the E 1/4 sec. cor. of sec. 12 only, T. 3 S., R. 20 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, protruding 6 ins. above mound of stone, with brass cap, mkd. as described in the official record of the dependent resurvey of the E. bdy. of T. 3 S., R. 20 E., in 1973.

N. 0° 08' W., on the E. bdy. of sec. 12.

Over broken bench land, through scattered juniper and pinon.

- 4.45 The witness cor. to the 1/4 sec. cor. of sec. 7 only, T. 3 S., R. 21 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, protruding 6 ins. above mound of stone, with brass cap, mkd. as described in the official record of the dependent resurvey of the E. bdy. of T. 3 S., R. 20 E., in 1973.
- 4.52 True point for the 1/4 sec cor. of sec. 7 only, T. 3 S., R. 21 E.
- 19.465 Point for the N 1/16 sec. cor. of sec. 12 only.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4 1/2 ft. base, to top of aluminum cap, mkd.

T 3 S  
R 20 E R 21 E  
N 1/16 |  
S 12 |  
1984

- 38.93 The cor. of secs. 1 and 12, T. 3 S., R. 20 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, protruding 6 ins. above mound of stone, with brass cap, mkd. as described in the official record of the dependent resurvey of the E. bdy. of T. 3 S., R. 20 E., in 1973.
-

Dependent Resurvey of a Portion of the  
Old Fort Thornburg Military Reservation Boundary,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

Dependent Resurvey of a Portion of the  
Old Fort Thornburg Military Reservation Boundary,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

---

(Restoring the Survey Executed by  
A.D. Ferron and E. Buettner in 1879,  
and A. Jessen in 1900)

---

From the cor. of secs. 24 and 25 only, T. 3 S., R. 20 E., which  
also functions as the Angle Point No. 2, on the Old Fort Thornburg  
Military Reservation Boundary, hereinbefore described.

S. 89° 19' W., along the N. bdy. of the Old Fort Thornburg  
Military Reservation Boundary and bet. secs. 24 and 25.

Over broken and exposed sandstone bench.

20.11 Point for the E 1/16 sec. cor. of secs. 24 and 25.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 4 ins. in  
the ground to bedrock, and in a mound of stone, 4 ft. base, to top  
of aluminum cap, mkd.

$$\begin{array}{r} T\ 3\ S\ R\ 20\ E \\ \quad S\ 24 \\ E\ 1/16\ \frac{S\ 25}{1984} \end{array}$$

Cor. is located in bottom of ravine, which drains SE.

37.00 Dry Fork Creek, 1.50 chs. wide, 6 ins. deep, flows SE.

38.74 Point for the 5 Mile Corner at proportionate distance; there is  
no remaining evidence of the original corner.

This corner point is not monumented.

40.22 Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate  
distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in  
the ground, with aluminum cap mkd.

$$\begin{array}{r} T\ 3\ S\ R\ 20\ E \\ \quad S\ 24 \\ 1/4\ \frac{S\ 25}{1984} \end{array}$$

Dependent Resurvey of a Portion of  
the Old Fort Thornburg Military Reservation Boundary,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.

54.00 Paved road along bottom of Dry Fork Canyon, bears NW and SE.

60.33 Point for the W 1/16 sec. cor. of secs. 24 and 25.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 20 E  
S 24  
W 1/16  $\frac{S 25}{1984}$

78.88 Point for the 5 1/2 Mile Corner at proportionate distance; there is no remaining evidence of the original corner.

This corner point is not monumented.

80.44 The cor. of secs. 23, 24, 25, and 26, monumented with a sandstone, 16x10x7 ins., firmly set, protruding 10 ins. above ground, plainly mkd. 2 notches on S and 1 notch on E edges, from which the remaining original bearing tree

A cedar, 8 ins. diam., bears N. 21° 30' W.,  
110 lks. dist., mkd. T3S R20E S23 BT.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 20 E  
S 23 | S 24  
S 26 | S 25  
1984

Deposit the mkd. stone alongside the aluminum post.

S. 89° 04' W., bet. secs. 23 and 26.

38.30 The 6 Mile Corner, monumented with a sandstone, 14x10x4 ins., firmly set, protruding 8 ins. above ground, mkd. 6 M, from which the original bearing trees

A cedar, 8 ins. diam., bears S. 54° 45' E.,  
21 lks. dist., mkd. 6M OMR BT.

Dependent Resurvey of a Portion of  
the Old Fort Thornburg Military Reservation Boundary,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

A cedar, 10 ins. diam., bears S. 30° 30' W.,  
5 1/2 lks. dist., mkd. 6M OMR BT.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in  
the ground to bedrock, and in a mound of stone, 4 ft. base, to top  
of aluminum cap, mkd.

T 3 S R 20 E  
S 23  

---

S 26  
6M OMRB  
1984

---

S. 89° 13' W., along the N. bdy. of the Old Fort Thornburg  
Military Reservation Boundary and bet. secs. 23 and 26.

- 1.31 The 1/4 sec. cor. of secs. 23 and 26, monumented with a sandstone,  
20x20x4 ins., firmly set, protruding 10 ins. above ground, mkd.  
1/4 on N face, from which the remaining original bearing tree

A juniper, 10 ins. diam., bears S. 15° 00' E.,  
11 lks. dist., mkd. 1/4 S26 BT.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in  
the ground to bedrock, and in a mound of stone, 5 ft. base, to top  
of aluminum cap, mkd.

T 3 S R 20 E  
S 23  
1/4 

---

S 26  
1984

Deposit the mkd. stone alongside the aluminum post.

- 21.45 Point for the W 1/16 sec. cor. of secs. 23 and 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in  
the ground, and in a collar of stone, with aluminum cap mkd.

T 3 S R 20 E  
S 23  
W 1/16 

---

S 26  
1985

Dependent Resurvey of a Portion of  
the Old Fort Thornburg Military Reservation Boundary,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

- 39.88 The 6 1/2 Mile Corner, monumented with a sandstone, 18x10x5 ins., firmly set, protruding 8 ins. above ground, mkd. 1/2 M OMB on S face and PL on N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 20 E
S 23
-----
S 26
1/2 M OMB
1984

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

---

S. 89° 19' W., along the N. bdy. of the Old Fort Thornburg Military Reservation Boundary and bet. secs. 23 and 26.

Over rolling bench land.

- 1.71 The cor. of secs. 22, 23, 26, and 27, which also functions as an Angle Point on the N. bdy. of the Old Fort Thornburg Military Reservation Boundary, monumented with a sandstone, 20x13x6 ins., firmly set, protruding 8 ins. above ground, mkd. OMR on S and PL on N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

A P
T 3 S R 20 E
S 22   S 23
-----
S 27   S 26

1984

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

---

Dependent Resurvey of a Portion of  
the Old Fort Thornburg Military Reservation Boundary,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

(Restoring the Survey Executed by  
A. Jessen in 1900)

Thence, N. 84° 18' W., beginning new measurement.

- 38.93 Point for the 7 Mile Corner, at proportionate distance; there is no remaining evidence of the original corner.


This corner point is not monumented.

- 40.29 Point for the closing cor. on the N and S center line from the S of sec. 22.

This corner point is not monumented.

- 40.68 Point for the closing cor. on the N and S center line from the N of sec. 22, and on the Old Fort Thornburg Military Reservation Boundary.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.



- 79.64 The 7 1/2 Mile Corner, monumented with a sandstone, 18x12x8 ins., firmly set, protruding 8 ins. above ground, mkd. 1/2 OMR on S face, from which the original bearing trees

A juniper, 11 ins. diam., bears N. 13° 00' E.,  
31 lks. dist., with illegible markings.

A juniper, 8 ins. diam., bears S. 63° 00' W.,  
45 lks. dist., mkd. 1/2 M OMR.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Dependent Resurvey of a Portion of  
the Old Fort Thornburg Military Reservation Boundary,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

T 3 S R 20 E  
S 22  
OMRB  
1/2 M  
1984

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.

N. 85° 27' W., beginning new measurement.

- 0.94 The closing cor. of secs. 21 and 22, from the S, monumented with a sandstone, 15x12x10 ins., firmly set, protruding 8 ins. above ground, mkd. CC 4 grooves on S and 4 grooves on E face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4 1/2 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
OMRB  
S 21 | S 22  
C C  
1984

Deposit the mkd. stone alongside the aluminum post.

- 1.715 The closing cor. of secs. 21 and 22, from the N, monumented with a sandstone, 14x10x8 ins., firmly set, protruding 10 ins. above ground, mkd. CC on N and 3 grooves on S face, from which the original bearing trees

A juniper, 20 ins. diam., bears N. 36° 00' E.,  
15 lks. dist., mkd. T3S R20E S22 CC BT. (Record, 29 lks.)

A juniper, 12 ins. diam., bears West, 12 lks.  
dist., mkd. T3S R20E CC S21 BT. (Record, N. 57° W., 19  
lks. dist.)

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

Dependent Resurvey of a Portion of  
the Old Fort Thornburg Military Reservation Boundary,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

T 3 S R 20 E  
C C  
S 21 | S 22  
OMRB  
1984

Deposit the mkd. stone alongside the aluminum post.

- 20.94 Point for the closing cor. on the N and S center line from the S,  
of the SE 1/4 of sec. 21, on the Old Fort Thornburg Military  
Reservation Boundary.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in  
the ground, and in a collar of stone, with aluminum cap mkd.

OMRB  
SE 1/4 | S 21  
C C  
1985

- 21.74 Point for the closing cor. on the N and S center line from the N,  
of the SE 1/4 of sec. 21, on the Old Fort Thornburg Military  
Reservation Boundary.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in  
the ground to bedrock, and in a mound of stone, 4 1/2 ft. base, to  
top of aluminum cap, mkd.

SE 1/4 | S 21  
C C  
OMRB  
1985

- 39.48 The 8 Mile Corner, monumented with a sandstone, 20x16x10 ins.,  
firmly set, protruding 8 ins. above ground, mkd. 8M OMB on S face  
and PL on N face, with a scattered mound of stone to W.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in  
the ground, and in a collar of stone, with aluminum cap mkd.

T 3 S R 20 E  
S 21  
8M OMRB  
1984

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.


---

Dependent Resurvey of a Portion of  
the Old Fort Thornburg Military Reservation Boundary,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

N. 84° 05' W., along the N. bdy. of the Old Fort Thornburg Military Reservation Boundary.


- 1.45 Point for the closing cor. on the N and S center line from the S of sec. 21 and on the Old Fort Thornburg Military Reservation Boundary.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.



- 2.255 Point for the closing cor. on the N and S center line from the N, of sec. 21 and on the Old Fort Thornburg Military Reservation Boundary.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.




- 25.00 Dirt road, bears irregularly N and S.

- 39.84 Point for the 8 1/2 Mile Corner, monumented with a sandstone, 20x16x12 ins., firmly set, protruding 8 ins. above ground, mkd. 1/2 OMR on N face, and a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.



Deposit the mkd. stone alongside the aluminum post.

Dependent Resurvey of a Portion of  
the Old Fort Thornburg Military Reservation Boundary,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

N. 84° 08' W., beginning new measurement.

- 1.615 The closing cor. of secs. 20 and 21 from the S, monumented with a sandstone, 16x12x8 ins., firmly set, protruding 10 ins. above ground, mkd. C on N and FTMR on S face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
-----  
OMRB  
S 20 | S 21  
C C  
1984

Deposit the mkd. stone alongside the aluminum post.


- 2.52 Point for the closing cor. of secs. 20 and 21 from the N, hereinafter described.

Asc. over steep NE slope.

- 33.87 Point for the NW cor. of the Old Fort Thornburg Military Reservation Boundary determined from a tie to U.S.G.S. "Little Mountain"; there is no remaining evidence of the original corner.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

A P  
T 3 S R 20 E  
S 20  
NW   
OMRB  
1988

From this point, a tie taken from U.S.G.S. Horizontal Control data, dated 1898, 1965 and 1971, to U.S.G.S. triangulation station "Little Mountain", monumented with a copper bolt, in chiseled triangle, cemented in sandstone and mkd. "USGS", bears N. 30° 26.0' E., 0.145 chs. dist.

This cor. will also function as an Angle Point.

Dependent Resurvey of a Portion of  
the Old Fort Thornburg Military Reservation Boundary,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

This angle point is located near the N end and on the highest point of Little Mountain.

Thence, S. 5° 05' E., along the W. bdy. of the Old Fort Thornburg Military Reservation Boundary.

- 6.26 The 9 Mile Corner, monumented with a sandstone, 20x10x8 ins., loosely set in the ground and mkd. 9M OMR on the E face and PL on the W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 20 E	
9M	O
S 21	M
	R
	B
1984	

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.

---

S. 5° 00' E., along the W. bdy. of the Old Fort Thornburg Military Reservation Boundary.

- 12.21 The closing cor. of secs. 20 and 29 from the W, monumented with a sandstone, 14x8x4 ins., firmly set, protruding 8 ins. above ground, mkd. CC and 2 grooves on W face, 2 grooves on S face, and FTMB on E face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 3 S R 20 E	
C S 20	O
C S 29	M
	R
	B
1984	

Deposit the mkd. stone alongside the aluminum post.

Dependent Resurvey of a Portion of  
the Old Fort Thornburg Military Reservation Boundary,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

- 12.62 The closing cor. of secs. 20 and 29 from the E, monumented with a sandstone, 16x8x8 ins., firmly set, protruding 10 ins. above ground, mkd. CC on E face and PL on W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

```
T 3 S R 20 E
O | S 20 C
M | S 29 C
R
B
```

1984

Deposit the mkd. stone alongside the aluminum post.

- 40.27 The 9 1/2 Mile Corner, monumented with a sandstone, 12x12x6 ins., firmly set, protruding 6 ins. above ground, mkd. 1/2 OMRB on the E face and PL on the W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

```
T 3 S R 20 E
9 1/2 M
OMRB \ S 29
1984
```

Deposit the mkd. stone alongside the aluminum post.

---

S. 5<sup>o</sup> 20' E., beginning new measurement.

- 11.875 Point for the closing cor. on the E-W center line of sec. 29, at mid point between closing cors.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 4 1/2 ft. base, to top of aluminum cap, mkd.

```
T 3 S R 20 E
S 29
C ——— CC \ CC ——— C
OMRB
1984
```

Dependent Resurvey of a Portion of  
the Old Fort Thornburg Military Reservation Boundary,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

Note: This point will function for a common closing cor. for the E and W portions of sec. 29.

- 39.12 The 10 Mile Corner, monumented with a sandstone, 20x12x10 ins., firmly set, protruding 10 ins. above ground, and plainly mkd. OMB 10M on E face, and PL on W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
OMRB |  
10M | S 29  
1984

Deposit the mkd. stone alongside the aluminum post.

S. 40° 30' E., along the W. bdy. of the Old Fort Thornburg Military Reservation Boundary.

Along E slope of Little Mountain.

- 12.28 Point for the closing cor. of secs. 29 and 32, from the E, at proportionate distance, falls on steep E slope, and is unsafe to monument.
- 12.48 Point selected for the witness cor. to the closing cor. of secs. 29 and 32, from the E.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 3 S R 20 E  
W C  
S 29 C  
S 32 C  
1984

- 12.69 Point for the closing cor. of secs. 29 and 32 from the W, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

Dependent Resurvey of a Portion of  
the Old Fort Thornburg Military Reservation Boundary,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

T 3 S R 20 E  
C S 29 |  
C S 32 |  
1984

- 39.92 The 10 1/2 Mile Corner, monumented with a sandstone, 20x12x6 ins., firmly set, protruding 4 ins. above ground, mkd. OMR 1/2 M on E face and PL on W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 4 1/2 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
S 32 | 0  
M 10 1/2 M  
R  
B  
1984

Deposit the mkd. stone alongside the aluminum post.

S. 40° 39' E., beginning new measurement.

- 16.62 The angle point and SW cor. of the Old Fort Thornburg Military Reservation Boundary, monumented with a sandstone, 20x16x8 ins., firmly set, protruding 12 ins. above ground, mkd. USMR.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

AP  
T 3 S R 20 E  
S 32 | 0  
M  
R  
B  
1984

Deposit the mkd. stone alongside the aluminum post.

Dependent Resurvey of a Portion of  
the Old Fort Thornburg Military Reservation Boundary,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

From this point, U.S. Coast and Geodetic Station "LITTLE", bears  
N.  $38^{\circ} 54.8'$  W., 59.508 chs. dist.

---

(Restoring the Survey Executed by  
A. Jessen in 1900 and S.P. and J.R. Stewart in 1906)

---

Thence, S.  $71^{\circ} 50'$  E., along the SW. bdy. of the Old Fort  
Thornburg Military Reservation Boundary.

Desc. over steep E slope of Little Mountain.

- 21.465 The closing cor. of secs. 32 and 33 from the N, monumented with a  
sandstone, 12x8x4 ins., firmly set, protruding 8 ins. above  
ground, mkd. CC on N face, 4 notches on E and 2 notches on W edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in  
the ground to bedrock, and in a mound of stone, 4 ft. base, to top  
of aluminum cap, mkd.

```

T 3 S R 20 E
  C C
S 32 | S 33
  _____

```

OMRB  
1984

Deposit the mkd. stone alongside the aluminum post.

- 23.31 The 11 Mile Corner, monumented with a sandstone, 16x8x5 ins.,  
firmly set, protruding 12 ins. above ground, mkd. 11M OMR on the N  
face and PL on the S face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in  
the ground to bedrock, and in a mound of stone, 4 ft. base, to top  
of aluminum cap, mkd.

```

T 3 S R 20 E
  S 33
  _____
11M OMRB
  1984

```

Deposit the mkd. stone alongside the aluminum post.

---

Dependent Resurvey of a Portion of  
the Old Fort Thornburg Military Reservation Boundary,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

S. 71° 31' E., along the SW bdy. of the Old Fort Thornburg  
Military Reservation Boundary.

Desc. over E slope.

- 0.205 The closing cor. of secs. 32 and 33 from the S, monumented with a sandstone, 20x8x6 ins., firmly set, protruding 8 ins. above ground, mkd. FTMR on N face, CC and 1 groove on S face, and 4 grooves on E face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E
OMRB
<u>S 32   S 33</u>
C C
1984

Deposit the mkd. stone alongside the aluminum post.

- 21.255 Point for the closing cor. of the N and S center line from the S, of the SW 1/4 of sec. 33.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

OMRB
<u>C   C</u>
SW 1/4   S 33
C
1986

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, S of cor.

- 40.09 The 11 1/2 Mile Corner, monumented with a sandstone, 16x12x12 ins., firmly set, protruding 10 ins. above ground, mkd. 1/2 M OMR on the N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Dependent Resurvey of a Portion of  
the Old Fort Thornburg Military Reservation Boundary,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

T 3 S R 20 E  
1/2 M OMRB  
S 33  
1984

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.

S. 70° 47' E., beginning new measurement.

- 2.21 Point for the closing cor. of the N and S center line of sec. 33 from the S.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

OMRB  
C | C  
S | 33  
C  
1985

- 39.83 The 12 Mile Corner, monumented with a sandstone, 18x12x6 ins., firmly set, protruding 8 ins. above ground, mkd. 12M OMR on the N face and PL on the S face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
S 33  
12M OMRB  
1984

Deposit the mkd. stone alongside the aluminum post.

S. 71° 17' E., along the SW. bdy. of the Old Fort Thornburg Military Reservation Boundary.

Dependent Resurvey of a Portion of  
the Old Fort Thornburg Military Reservation Boundary,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

- 2.17 The closing cor. of secs. 33 and 34 from the N, monumented with a sandstone, 16x10x9 ins., firmly set, protruding 6 ins. above ground, mkd. 3 grooves on the E and W face and CC on the N face, from which the original bearing trees

A juniper, 14 ins. diam., bears N.  $63^{\circ} 00'$  E.,  
125 lks. dist., mkd. T3S R20E S34 BT.

A juniper, 6 ins. diam., bears N.  $13^{\circ} 00''$  W.,  
69 lks. dist., mkd. T3S R20E S33 BT.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T	3	S	R	20	E
S	33		S	34	
	C		C		
OMRB					
1984					

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.

- 4.46 The closing cor. of secs. 33 and 34 from the S, monumented with a sandstone, 18x12x8 ins., firmly set, projecting 6 ins. above ground, plainly mkd. FTMR on N face and CC on S face, from which the original bearing trees

A juniper, 8 ins. diam., bears S.  $49^{\circ} 00'$  E.,  
25 lks. dist., mkd. T3S R20E S34 BT.

A juniper, 16 ins. diam., bears S.  $27^{\circ} 00'$  W.,  
26 lks. dist., mkd. T3S R20E S33 BT.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T	3	S	R	20	E
	C		C		
S	33		S	34	
1984					


Dependent Resurvey of a Portion of  
the Old Fort Thornburg Military Reservation Boundary,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

Deposit the mkd. stone alongside the aluminum post.

- 11.225 The closing cor. of secs. 3 and 34, Tps. 3 and 4 S., R. 20 E., on the Old Fort Thornburg Military Reservation Boundary, hereinbefore described.
- 12.495 The closing cor. of secs. 3 and 4, T. 4 S., R. 20 E., on the Old Fort Thornburg Military Reservation Boundary, monumented with an iron post, 2 ins. diam., firmly set, protruding 8 ins. above ground, with brass cap, mkd. as described in the dependent resurvey of a portion of the subdivisional lines of T. 4 S. R. 20 E., in 1943.
- 39.04 The 12 1/2 Mile Corner, monumented with a sandstone, 20x14x7 ins., firmly set, protruding 5 ins. above ground, mkd. 1/2 M on N face and PL on S face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.



Deposit the mkd. stone alongside the aluminum post.

---

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

---

(Restoring the Survey Executed by  
A. D. Ferron and E. Buettner in 1879,  
and A. Jessen in 1900)

From the cor. of secs. 35 and 36 only, on the S. bdy. of the Tp., hereinbefore described.

N. 0° 42' W., bet. secs. 35 and 36.

Asc. over gradual S slope.


Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

- 40.63 The 1/4 sec. cor. of secs. 35 and 36, monumented with a sandstone, 16x10x6 ins., firmly set, protruding 6 ins. above ground, mkd. 1/4 on W face, from which the remaining original bearing tree

A cedar, 6 ins. diam., bears S. 52° 00' E.,  
4 lks. dist., mkd. 1/4 S36 BT.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.



Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.

N. 1° 06' W., beginning new measurement.

- 40.26 The cor. of secs. 25, 26, 35, and 36, monumented with a sandstone, 18x12x8 ins. firmly set, protruding 8 ins. above ground, mkd. 1 notch on the S and E edges, from which the original bearing trees

A cedar, 14 ins. diam., bears N. 85° 00' E.,  
36 lks. dist., dimly mkd. BT.

A cedar, 8 ins. diam., bears S. 10° 30' E.,  
41 lks. dist., mkd. T3S R20E S36 BT.

A cedar, 8 ins. diam., bears S. 67° 30' W.,  
53 lks. dist., mkd. T3S R20E S35 BT.

The other bearing tree has been destroyed.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

T	3	S	R	20	E
S	26		S	25	
S	35		S	36	
1984					

Deposit the mkd. stone alongside the aluminum post.

---

From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, protruding 6 ins. above mound of stone, with brass cap, mkd. as described in the official record of the dependent resurvey of the E. bdy. of T. 3 S., R. 20 E., in 1973, from which the original bearing trees

A juniper, 10 ins. diam., bears N. 40° 00' E.,  
27 1/2 lks. dist., mkd. T3S R21E S30 BT.

A juniper, 10 ins. diam., bears S. 22° 00' E.,  
29 1/2 lks. dist., mkd. T3S R21E S31 BT.

A juniper, 12 ins. diam., bears S. 50° 45' W.,  
83 1/2 lks. dist., mkd. T3S R20E S36 BT.

A juniper, 10 ins. diam., bears N. 68° 00' W.,  
81 lks. dist., mkd. T3S R20E S30 BT.

S. 84° 35' W., bet. secs. 25 and 36.

Over broken bench land.

40.34 The 1/4 sec. cor. of secs. 25 and 36, monumented with a sandstone, 6x10x5 ins., firmly set, protruding 5 ins. above ground, mkd. 1/4 on the N face, from which the original bearing tree

A cedar, 8 ins. diam., bears N. 40° 00' E.,  
41 lks. dist., mkd. 1/4 S25 BT.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.

T	3	S	R	20	E
		S	25		
1/4			S	36	
1984					

Deposit the mkd. stone alongside the aluminum post.

---

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

N.  $85^{\circ} 14'$  W., beginning new measurement.

41.27 The cor. of secs. 25, 26, 35, and 36.

---

N.  $0^{\circ} 53'$  W., bet. secs. 25 and 26.

Over rolling bench land.

39.72 The  $1/4$  sec. cor. of secs. 25 and 26, monumented with a sandstone  
14x8x6 ins. firmly set, protruding 6 ins. above ground, plainly  
mkd.  $1/4$  on the W face, from which the original bearing trees

A cedar, 12 ins. diam., bears S.  $15^{\circ} 00'$  E.,  
7  $1/2$  lks. dist., mkd.  $1/4$  S26 BT.

The other bearing tree has been destroyed.

At the corner point

Set an aluminum post, 30 ins. long, 2  $1/2$  ins. diam., 24 ins. in  
the ground, with aluminum cap mkd.

T 3 S R 20 E  
   $1/4$   
  |  
S 26 | S 25  
  |  
  1984

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2  $1/2$  ft. base, 1  $1/2$  ft. high, W of cor.

---

N.  $1^{\circ} 03'$  W., beginning new measurement.

19.735 Point for the N  $1/16$  sec. cor. of secs. 25 and 26.

Set an aluminum post, 30 ins. long, 2  $1/2$  ins. diam., 24 ins. in  
the ground, with aluminum cap mkd.

T 3 S R 20 E  
  N  $1/16$   
  S 26 | S 25  
  1984

Raise a mound of stone, 2  $1/2$  ft. base, 1  $1/2$  ft. high, W of cor.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

- 39.47 The cor. of secs. 23, 24, 25, and 26, hereinbefore described in the dependent resurvey of the Old Fort Thornburg Military Reservation Boundary.

---

Note: The sec. line bet. secs. 24 and 25, was described in conjunction with the dependent resurvey of the Old Fort Thornburg Military Reservation Boundary.

---

(Restoring the Survey Executed by  
A. D. Ferron and E. Buettner in 1879)

---

N. 0° 18' W., bet. secs. 23 and 24.

Over broken bench land.

- 18.00 Narrow paved road, along S side of Dry Fork Valley, bears NW and SE.

- 19.95 Point for the S 1/16 sec. cor. of secs. 23 and 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with aluminum cap mkd.

T 3 S R 20 E  
S 1/16  
S 23 | S 24  
1984

- 39.90 Point for the 1/4 sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.

This cor. point is not monumented.

- 58.36 The original witness cor. for secs. 13, 14, 23, and 24, marked by a cross (X), chisled on face of sandstone ledge, with 1 groove E and 2 grooves S of cross, and a WC above cross.

No improvements can be made on this corner point. This will now function as an Angle Point only.

---

N. 0° 18' W., beginning new measurement.

Asc. over S face of sandstone ledge.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

- 1.35 Point selected for the witness cor. to the N 1/16 sec. cor. of  
secs. 23 and 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 4 ins. in  
the ground to bedrock, and in a mound of stone, 4 1/2 ft. base, to  
top of aluminum cap, mkd.

W C  
T 3 S R 20 E  
N 1/16  
S 23 ↑ S 24  
1984

- 1.475 True point for the N 1/16 sec. cor. of secs. 23 and 24, falls on  
face of sandstone ledge and cannot be monumented.

- 21.41 Point for the cor. of secs. 13, 14, 23, and 24, at proportionate  
distance latitude and on an extension of the line to the south.  
There is no remaining evidence of the other three witness corners.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in  
the ground, with aluminum cap mkd.

T 3 S R 20 E  
S 14 | S 13  
S 23 | S 24  
1984

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

From the cor. of secs. 13 and 24, on the E. bdy. of the Tp.,  
monumented with an iron post, 2 1/2 ins. diam., firmly set, in a  
mound of stone, 4 1/2 ft base, to top of brass cap, mkd. as  
described in the official record of the dependent resurvey of the  
E. bdy. of T. 3 S., R. 20 E., in 1973.

S. 87° 12' W., bet. secs. 13 and 24.

Over Ashley Creek bottom.

- 19.86 Point for the E 1/16 sec. cor. of secs. 13 and 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in  
the ground, and in a collar of stone, with aluminum cap mkd.

T 3 S R 20 E  
S 13  
E 1/16 S 24  
1984

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

- 39.72 Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 4 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
S 13  
1/4 S 24  
1984

- 59.58 Point for the W 1/16 sec. cor. of secs. 13 and 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 20 E  
S 13  
W 1/16 S 24  
1984

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, N of cor.

- 79.44 The cor. of secs. 13, 14, 23 and 24.
- 

N. 10° 09' W., bet. secs. 13 and 14.

Over rolling and broken bench land.

- 19.92 Point for the S 1/16 sec. cor. of secs. 13 and 14.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
S 1/16  
S 14 | S 13  
1985

- 39.84 Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 20 E  
1/4  
S 14 | S 13  
1985

79.68 The cor. of secs. 11, 12, 13, and 14, monumented with a sandstone, 23x12x4 ins., firmly set, protruding 10 ins. above mound of stone, with 4 notches on S and 1 notch on E edges, from which the remaining original bearing trees

A cedar, 18 ins. diam., bears S. 60° 00' E.,  
50 lks. dist., mkd. T3S R20E S13 BT.

A cedar, 24 ins. diam., bears N. 55° 00' W.,  
15 lks. dist., mkd. T3S R20E S11 BT.

The other bearing tree has been destroyed.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., over a cross (X) chisled in solid sandstone, and in mound of stone, 4 1/2 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
S 11 | S 12  
S 14 | S 13  
1984

Deposit the mkd. stone in the mound of stone alongside the aluminum post.

Cor. is located 20 lks. N of small wash, which drains E.

---

From the cor. of secs. 12 and 13, on the E. bdy. of the Tp., hereinbefore described.

S. 89° 37' W., bet. secs. 12 and 13.

Over Ashley Creek bottom.

7.50 Ashley Creek, 1.50 chs. wide, flows S.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

20.29 Point for the E 1/16 sec. cor. of secs. 12 and 13.

This corner point is not monumented.

30.435 Point for the W-E 1/64 sec. cor. of secs. 12 and 13.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

W-E 1/64  $\frac{S 12}{S 13}$   
1984

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of corner.

40.58 Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 1/2 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
1/4  $\frac{S 12}{S 13}$   
1984

81.16 The cor. of secs. 11, 12, 13, and 14.

---

N. 0° 11' W., bet. secs. 11 and 12.

Over broken bench land.

40.61 Point for the 1/4 sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 3 S R 20 E  
1/4  
S 11 | S 12  
1984

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

60.915 Point for the N 1/16 sec. cor. of secs. 11 and 12.

This corner point is not monumented.

81.22 Point for the cor. of secs. 1, 2, 11, and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 5 1/2 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E
S 2   S 1
S 11   S 12
1984

From the cor. of secs. 1 and 12, on the E. bdy. of the Tp., hereinbefore described.

N. 88° 04' W., bet. secs. 1 and 12.

Over broken mountainous land.

27.50 Ashley Creek 1.50 chs. wide, flows S.

40.29 Point for the 1/4 sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., over a cross (X) chisled in solid sandstone, in a mound of stone, 5 ft. base to top, with aluminum cap mkd.

T 3 S R 20 E
S 1
1/4 S 12
1984

60.435 Point for the W 1/16 sec. cor. of secs. 1 and 12.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E
S 1
W 1/16 S 12
1984

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

80.58 The cor. of secs. 1, 2, 11, and 12.

---

N. 0° 46' W., bet. secs. 1 and 2.

Over mountainous land.

40.61 Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 1/2 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
1/4  
S 2 | S 1  
1984

81.40 The cor. of secs. 1 and 2, on the N. bdy. of the Tp., hereinbefore described.

---

(Restoring the Survey Executed by  
A. D. Ferron and E. Buettner in 1879, and the  
Resurvey by A. Jessen in 1900)

---

From the cor. of secs. 34 and 35, on the S. bdy. of the Tp., hereinbefore described.

N. 0° 11' E., bet. secs. 34 and 35.

Over rolling bench land.

39.93 The 1/4 sec. cor. of secs. 34 and 35, monumented with a sandstone boulder, 3x2x1 ft. above ground, plainly mkd. with a cross (X) on the top of the boulder, from which the remaining original bearing tree

A cedar, 12 ins. diam., bears S. 40° 30' W.,  
12 lks. dist., mkd. 1/4 S BT.

There is no remaining evidence of the other bearing tree.

At the corner point

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 5 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
1/4  
S 34 | S 35  
1984

Place the mkd. stone boulder alongside the aluminum post as part of the mound.

---

N. 20° 34' W., beginning new measurement.

42.73 The cor. of secs. 26, 27, 34, and 35, determined from the original bearing trees

A cedar, 14 ins. diam., bears N. 69° 00' E.,  
12 lks. dist., dimly mkd.

A cedar, 12 ins. diam., bears S. 21° 00' E.,  
20 lks. dist., dimly mkd.

A cedar, 14 ins. diam., bears S. 22° 00' W.,  
27 lks. dist., dimly mkd. (Record, 33 lks. dist.)

A cedar, 10 ins. diam., bears N. 28° 00' W.,  
6 lks. dist., dimly mkd.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 9 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
S 27 | S 26  
S 34 | S 35  
1984

---

From the cor. of secs. 25, 26, 35, and 36.

N. 88° 27' W., bet. secs. 26 and 35.

Over rolling bench land.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

40.60 The 1/4 sec. cor. of secs. 26 and 35, monumented with a sandstone, 16x14x10 ins., firmly set, protruding 6 ins. above ground, plainly mkd. 1/4 on N face, from which the remaining original bearing tree

A cedar, 14 ins. diam., bears S. 35° 00' E.,  
21 lks. dist., mkd. 1/4 S26 BT. (Record bearing and dist.  
S. 8° 15' E., 27 lks.)

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 20 E  
S 26  
1/4 S 35  
1984

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

---

N. 89° 09' W., beginning new measurement.

39.86 The cor. of secs. 26, 27, 34, and 35.

---

N. 0° 41' W., bet. secs. 26 and 27.

Over broken bench land.

37.07 The 1/4 sec. cor. of secs. 26 and 27, monumented with a sandstone, 16x10x6 ins., firmly set, protruding 8 ins. above ground, plainly mkd. 1/4 on W face, from which the original bearing trees

A cedar, 14 ins. diam., bears S. 38° 30' E.,  
190 lks. dist., mkd. 1/4.

A cedar, 14 ins. diam., bears N. 88° 30' W.,  
200 lks. dist., mkd. 1/4 S BT.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

T 3 S R 20 E  
1/4  
S 27 | S 26  
1984

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W of cor.

---

N. 0° 28' W., beginning new measurement.

- 39.26 The cor. of secs. 22, 23, 26, and 27, hereinbefore described in the dependent resurvey of the Old Fort Thornburg Military Reservation Boundary.
- 

Note: The sec. line bet. secs. 23 and 26 was described in conjunction with the dependent resurvey of the Old Fort Thornburg Military Reservation Boundary.

---

(Restoring the Survey Executed by  
A. D. Ferron and E. Buettner in 1879)

---

N. 0° 21' W., bet. secs. 22 and 23.

Over rolling and broken bench land.

- 19.95 Point for the S 1/16 sec. cor. of secs. 22 and 23.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 20 E  
S 1/16  
S 22 | S 23  
1984

- 39.90 The 1/4 sec. cor. of secs. 22 and 23, monumented with a sandstone, 10x9x5 ins., firmly set, protruding 6 ins. above ground, dimly mkd. 1/4 on W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

T 3 S R 20 E  
1/4  
S 22 | S 23  
1984

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

N. 1° 01' W., beginning new measurement.

20.05 Point for the N 1/16 sec. cor. of secs. 22 and 23.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 3 S R 20 E  
N 1/16  
S 22 | S 23  
1984

30.00 Paved road, on S side of Dry Fork Valley, bears irregularly NW and SE.

40.10 The cor. of secs. 14, 15, 22, and 23, marked by a fence cor. and shown to me by property owner Morgan Hall, whose father had seen the original rock at this point. This is accepted as the best available evidence of the original corner.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 3 S R 20 E  
S 15 | S 14  
S 22 | S 23  
1984

There is a telephone pedestal along E side of aluminum post.

From the cor. of secs. 13, 14, 23, and 24.

S. 89° 19' W., bet. secs. 14 and 23.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

Over broken bench land.

- 20.11 Point for the E 1/16 sec. cor. of secs. 14 and 23.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
S 14  
E 1/16 S 23  
1985

Cor. is located on shelf near base of ledge, which bears NW and SE.

- 40.22 Point for the 1/4 sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original corner.

This corner point is not monumented.

- 60.33 Point for the W 1/16 sec. cor. of secs. 14 and 23.

This corner point is not monumented.

- 80.44 The cor. of secs. 14, 15, 22 and 23.

N. 0° 31' W., bet. secs. 14 and 15.

Over bottom of Dry Fork Valley.

- 20.055 Point for the S 1/16 sec. cor. of secs. 14 and 15.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 20 E  
S 1/16  
S 15 | S 14  
1984

- 40.11 The 1/4 sec. cor. of secs. 14 and 15, marked by a Uintah County Survey marker, a re-bar protruding 6 ins. above ground, with brass cap, 1 in. diam., mkd. Uintah County Surveyor. The brass cap has no other markings.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

T 3 S R 20 E  
1/4  
S 15 | S 14  
1984

Deposit the Uintah County Survey Marker, inverted and alongside  
the aluminum post.

---

N. 0° 43' W., beginning new measurement.

- 39.76 The cor. of secs. 10, 11, 14, and 15, monumented with a sandstone,  
24x18x6 ins., firmly set, protruding 15 ins. above ground, plainly  
mkd. 2 notches on the E and dimly mkd. 4 notches on the S edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in  
the ground, with aluminum cap mkd.

T 3 S R 20 E  
S 10 | S 11  
S 15 | S 14  
1984

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W of cor.

---

From the cor. of secs. 11, 12, 13, and 14.

S. 89° 27' W., bet. secs. 11 and 14.

Over broken bench land.

- 39.85 Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate  
distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in  
the ground, and in a collar of stone, with aluminum cap mkd.

T 3 S R 20 E  
S 11  
1/4 S 14  
1984

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

79.70 The cor. of secs. 10, 11, 14, and 15.

---

N. 0° 41' W., bet. secs. 10 and 11.

Over broken bench land.

40.00 The 1/4 sec. cor. of secs. 10 and 11, monumented with a sandstone, 12x10x8 ins., firmly set, protruding 8 ins. above ground, dimly mkd. 1/4 on W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

```

T 3 S R 20 E
  1/4
S 10 | S 11
     1984

```

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

---

N. 0° 28' W., beginning new measurement

20.75 Point for the N 1/16 sec. cor. of secs. 10 and 11.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

```

T 3 S R 20 E
  N 1/16
S 10 | S 11
     1984

```

41.50 The cor. of secs. 2, 3, 10, and 11, monumented with an iron post, 2 1/2 ins. diam., firmly set, protruding 6 ins. above mound of stone, with brass cap, mkd. as described in the dependent resurvey of a portion of the subdivisional lines in 1980.

---

From the cor. of secs. 1, 2, 11, and 12.

S. 89° 39' W., bet. secs. 2 and 11.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

- 40.12 Point for the 1/4 sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
S 2  
1/4 S 11  
1984

- 80.24 The cor. of secs. 2, 3, 10, and 11.
- 

N. 0° 16' W., bet. secs. 2 and 3.

Over rough and broken mountainous land.

- 39.84 Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 1/2 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
1/4  
S 3 | S 2  
1984

- 79.78 The cor. of secs. 2 and 3, on the N. bdy. of the Tp., hereinbefore described.
- 

(Restoring the Survey Executed by A. Jessen in 1900)

---

From the cor. of secs. 26, 27, 34, and 35.

S. 84° 55' W., bet. secs. 27 and 34.

Over rolling bench land.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

- 40.23 The 1/4 sec. cor. of secs. 27 and 34, monumented with a sandstone, 12x10x8 ins., firmly set, protruding 6 ins. above ground, mkd. 1/4 on N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

	T	3	S	R	20	E
			S	27		
1/4			S	34		
				1984		

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.

---

S. 89° 49' W., beginning new measurement.

- 40.17 The cor. of secs. 27, 28, 33, and 34, monumented with a sandstone, 12x9x7 ins., firmly set, protruding 4 ins. above ground, plainly mkd. 1 notch on the S and 3 notches on the E edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

	T	3	S	R	20	E
	S	28		S	27	
	S	33		S	34	
				1984		

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

---

S. 0° 20' W., bet. secs. 33 and 34.

Over rolling bench land.

- 39.54 Point for the 1/4 sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 20 E  
1/4  
S 33 | S 34  
1984

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

- 76.81 The closing cor. of secs. 33 and 34, on the Old Fort Thornburg Military Reservation Boundary, hereinbefore described.

---

From the cor. of secs. 33 and 34, on the S. bdy. of the Tp., hereinbefore described.

N. 0° 02' W., bet. secs. 33 and 34.

Over rolling bench land through thick juniper and pinon.

- 2.275 The closing cor. of secs. 33 and 34, on the Old Fort Thornburg Military Reservation Boundary, hereinbefore described.

---

From the cor. of secs. 27, 28, 33, and 34.

N. 0° 03' W., bet. secs. 27 and 28.

Over rolling bench land.

- 40.19 The 1/4 sec. cor. of secs. 27 and 28, monumented with a sandstone, 18x10x8 ins., firmly set, protruding 5 ins. above ground, plainly mkd. 1/4 on the W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 20 E  
1/4  
S 28 | S 27  
1984

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

---

N. 20° 25' W., beginning new measurement.

38.63 The cor. of secs. 21, 22, 27, and 28, monumented with a sandstone boulder, 3x3x2 ft., dimly mkd. with a cross (X), from which the original bearing trees

A cedar, 14 ins. diam., bears S. 75° 00' E.,  
38 lks. dist., mkd. T3S R20E S27 BT.

A cedar, 9 ins. diam., bears S. 37° 00' W.,  
90 lks. dist., mkd. T3S R20E S28 BT. (Record, dist. 60  
lks.)

The stump hole from a fallen dead cedar, 6 ins.  
diam., bears N. 70° 00' W., 8 lks. dist., cedar mkd. T3S  
R20E S21 BT.

There is no remaining evidence of the other bearing tree.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in  
the ground to bedrock, and in a mound of stone, 5 ft. base, to top  
of aluminum cap, mkd.

T 3 S R 20 E	
S 21	S 22
S 28	S 27
1984	

Deposit the dimly mkd. boulder alongside the aluminum post and in  
the mound of stone.

---

From the cor. of secs. 22, 23, 26, and 27.

S. 89° 47' W., bet. secs. 22 and 27.

Over rolling bench land.

40.06 The 1/4 sec. cor. of secs. 22 and 27, monumented with a sandstone,  
15x12x6 ins., firmly set, protruding 6 ins. above ground, plainly  
mkd. 1/4 on N face, from which the original bearing trees

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

A juniper, 15 ins. diam., bears N.  $66^{\circ} 00'$  E.,  
14 lks. dist., mkd.  $1/4$  S22 BT.

A juniper, 13 ins. diam., bears South, 10 lks.  
dist., mkd.  $1/4$  S27 BT.

At the corner point

Set an aluminum post, 30 ins. long,  $2\ 1/2$  ins. diam., 24 ins. in  
the ground, with aluminum cap mkd.

T 3 S R 20 E  
S 22  
 $1/4$   $\frac{S 27}{1984}$

Deposit the mkd. stone alongside the aluminum post.

---

S.  $88^{\circ} 29'$  W., beginning new measurement.

41.10 The cor. of secs. 21, 22, 27, and 28.

---

N.  $6^{\circ} 03'$  E., bet. secs. 21 and 22.

Over rough and broken bench land.

9.29 The closing cor. of secs. 21 and 22, on the Old Fort Thornburg  
Military Reservation Boundary, hereinbefore described.

---

(Restoring the Survey Executed by  
S.P. and J.R. Stewart in 1906)

---

From the  $1/4$  sec. cor. of secs. 21 and 22, monumented with a  
quartzite stone,  $14 \times 9 \times 6$  ins., firmly set, protruding 6 ins. above  
ground, mkd.  $1/4$  on W. face, from which the original bearing trees

A cedar, 8 ins. diam., bears N.  $70^{\circ} 00'$  E.,  
31 lks. dist., mkd.  $1/4$  S22 BT.

A cedar, 5 ins. diam., bears N.  $22^{\circ} 00'$  W.,  
 $17\ 1/2$  lks. dist., mkd.  $1/4$  S21 BT.

At the corner point

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
1/4  
S 21 | S 22  
1984

Deposit the mkd. stone alongside the aluminum post.

S. 1° 32' E., bet. secs. 21 and 22.

19.305 True point for the S 1/16 sec. cor. of secs. 21 and 22, falls on steep sandstone slope and cannot be monumented.

20.305 Point selected for the witness cor. to the S 1/16 sec. cor. of secs. 21 and 22.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.

W C  
T 3 S R 20 E  
S 1/16  
S 21 ↓ S 22  
1984

30.37 The closing cor. of secs. 21 and 22, on the Old Fort Thornburg Military Reservation Boundary, hereinbefore described.

---

(Restoring the Survey Executed by  
A.D. Ferron and E. Buettner in 1879, and the  
Resurvey by S.P. and J.R. Stewart in 1900)

---

From the cor. of secs. 14, 15, 22, and 23.

S. 89° 21' W., bet. secs. 15 and 22.

19.90 Point for the E 1/16 sec. cor. of secs. 15 and 22.

This corner point is not monumented.

24.50 Paved road on the S side of Dry Fork valley, bears NW and SE.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

- 39.80 The 1/4 sec. cor. of secs. 15 and 22, monumented with a sandstone boulder, 30x20x20 ins. above ground, mkd. 1/4 on N face, and a Uintah County Survey marker alongside, a rebar, protruding 6 ins. above ground, with brass cap, 1 in. diam., mkd. Uintah County Survey RLS.

No improvements were made on this corner point.

---

(Restoring the Survey Executed by  
A.D. Ferron and E. Buettner in 1879)

From the 1/4 sec. cor. of secs. 10 and 15, monumented with a rebar, 12x1/2 ins., firmly driven 8 ins. in the ground. This position is harmoniously related to existing original cors., has been recognized as the cor. by adjacent landowners, and is accepted as the best available evidence of the original cor. position.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 3 S R 20 E  
          S 10  
1/4    S 15  
          1984

S. 89° 14' W., bet. secs. 10 and 15.

- 19.70 Point for the W 1/16 sec. cor. of secs. 10 and 15. This corner point is not monumented.

- 39.40 The cor. of secs. 9, 10, 15, and 16, monumented with an iron post, 2 1/2 ins. diam., firmly set, protruding 6 ins. above mound of stone, with brass cap, mkd. as described in the official record of the dependent resurvey of a portion of the subdivisional lines in 1980.

---

(Restoring the Survey Executed by  
A.D. Ferron and E. Buettner in 1879 and the  
Resurvey by G. Reynolds in 1980)

From the cor. of secs. 2, 3, 10, and 11.

S. 88° 37' W., bet. secs. 3 and 10.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

Over rolling mountainous land.

- 19.75 Point for the E 1/16 sec. cor. of secs. 3 and 10.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 3 S R 20 E  
S 3  
E 1/16 S 10  
1984

- 39.50 The 1/4 sec. cor. of secs. 3 and 10, monumented with an iron post, 2 1/2 ins. diam., firmly set, protruding 6 ins. above ground, with brass cap, mkd. as described in the official record of the dependent resurvey of a portion of the subdivisional lines in 1980.

---

S. 88° 46' W., beginning new measurement.

- 19.69 Point for the W 1/16 sec. cor. of secs. 3 and 10.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
S 3  
W 1/16 S 10  
1984

- 39.38 The cor. of secs. 3, 4, 9, and 10, monumented with an iron post, 2 1/2 ins. diam., firmly set, protruding 6 ins. above ground, with brass cap, mkd. as described in the official record of the dependent resurvey of a portion of the subdivisional lines in 1980.

---

N. 30° 36' W., bet. secs. 3 and 4.

Over rolling mountainous land.

- 20.48 Point for the S 1/16 sec. cor. of secs. 3 and 4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
S 1/16  
S 4 | S 3  
1984

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

- 40.96 The 1/4 sec. cor. of secs. 3 and 4, monumented with an iron post, 2 1/2 ins. diam., firmly set, protruding 6 ins. above ground, with brass cap, mkd. as described in the official record of the dependent resurvey of a portion of the subdivisional lines in 1980.

---

(Restoring the Survey Executed by  
A.D. Ferron and E. Buettner in 1879)

---

N. 30° 07' W., beginning new measurement.

- 20.03 Point for the N 1/16 sec. cor. of secs. 3 and 4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 4 1/2 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
N 1/16  
S 4 | S 3  
1984

- 39.92 The cor. of secs. 3 and 4, on the N. bdy. of the Tp., hereinbefore described.

---

(Restoring the Survey Executed by  
S.P. and J.R. Stewart in 1906)

---

From the cor. of secs. 32 and 33, on the S. bdy. of the Tp., hereinbefore described.

N. 00° 11' E., bet. secs. 32 and 33.

Over mountainous land.

- 29.29 The closing cor. of secs. 32 and 33, on the Old Fort Thornburg Military Reservation Boundary, hereinbefore described.

---

(Restoring the Survey Executed by  
A. Jessen in 1900)

---

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

From the cor. of secs. 27, 28, 33, and 34.

N. 89° 57' W., bet. secs. 28 and 33.

Asc. over E slope of Little Mountain.

- 40.01 The 1/4 sec. cor. of secs. 28 and 33, monumented with a sandstone, 18x12x6 ins., firmly set, protruding 6 ins. above ground, plainly mkd. 1/4 on N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 5 ft. base, to top of aluminum cap, mkd.

	T 3 S R 20 E
	S 28
1/4	S 33
	1984

Deposit the mkd. stone alongside the aluminum post.

---

N. 89° 55' W., beginning new measurement.

- 12.50 Dirt road, bears irregularly NW and SE.

- 39.83 The cor. of secs. 28, 29, 32, and 33, monumented with a sandstone, 15x10x6 ins., firmly set, protruding 8 ins. above ground, mkd. 4 notches on the E and 1 notch on the S edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

	T 3 S R 20 E
	S 29   S 28
	S 32   S 33
	1984

Deposit the mkd. stone alongside the aluminum post.

---

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

S.  $0^{\circ} 02'$  E., bet. secs. 32 and 33.

Over mountainous land.

- 39.15 The  $1/4$  sec. cor. of secs. 32 and 33, monumented with a sandstone,  $15 \times 10 \times 6$  ins., firmly set, protruding 7 ins. above ground, mkd.  $1/4$  on W face.

At the corner point

Set an aluminum post, 30 ins. long,  $2 \frac{1}{2}$  ins. diam., 24 ins. in the ground, with aluminum cap mkd.

```

T 3 S R 20 E
  1/4
  |
S 32 | S 33
  |
  1984

```

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone,  $2 \frac{1}{2}$  ft. base,  $1 \frac{1}{2}$  ft. high, W of cor.

---

S.  $0^{\circ} 23'$  W., beginning new measurement.

- 10.63 The closing cor. of secs. 32 and 33, on the Old Fort Thornburg Military Reservation Boundary, hereinbefore described.

---

From the cor. of secs. 28, 29, 32, and 33.

N.  $0^{\circ} 01'$  W., bet. secs. 28 and 29.

Over mountainous land.

- 40.16 The  $1/4$  sec. cor. of secs. 28 and 29, monumented with a sandstone,  $15 \times 10 \times 9$  ins., firmly set, protruding 6 ins. above ground, mkd.  $1/4$  on the W face.

At the corner point

Set an aluminum post, 30 ins. long,  $2 \frac{1}{2}$  ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

T 3 S R 20 E  
1/4  
S 29 | S 28  
1984

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

N. 0° 55' W., beginning new measurement.

- 39.53 The cor. of secs. 20, 21, 28, and 29, monumented with a sandstone, 15x12x10 ins., firmly set, protruding 6 ins. above ground, mkd. 2 notches on S and 4 notches on E edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 20 E  
S 20 | S 21  
S 29 | S 28  
1984

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

From the cor. of secs. 21, 22, 27, and 28.

N. 87° 51' W., bet. secs. 21 and 28.

Over mountainous land.

- 19.635 Point for the E 1/16 sec. cor. of secs. 21 and 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 3 S R 20 E  
S 21  
E 1/16 | S 28  
1985

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

39.27 The 1/4 sec. cor. of secs. 21 and 28, monumented with a sandstone, 14x7x6 ins., firmly set, protruding 5 ins. above ground, mkd. 1/4 on N face, from which the original bearing trees

A cedar, 6 ins. diam., bears N. 62° 00' E.,  
27 lks. dist., mkd. 1/4 S21 BT.

A cedar, 13 ins. diam., bears S. 70° 00' E.,  
34 1/2 lks. dist., mkd. 1/4 S28 BT.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 4 1/2 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
          S 21  
1/4     S 28  
          1984

Deposit the mkd. stone alongside the aluminum post.

---

S. 89° 18' W., beginning new measurement.

39.56 The cor. of secs. 20, 21, 28, and 29.

---

N. 0° 27' E., bet. secs. 20 and 21.

Over mountainous land.

15.58 The closing cor. of secs. 20 and 21 on the Old Fort Thornburg Military Reservation Boundary, hereinbefore described.

---

(Restoring the Survey Executed by S.P.  
and J.R. Stewart in 1906, and the  
Resurvey by G. Reynolds in 1980)

---

From the cor. of secs. 16, 17, 20, and 21, monumented with an iron post, 2 1/2 ins. diam., firmly set, protruding 6 ins. above ground, with brass cap, mkd. as described in the official record of the dependent resurvey of a portion of the subdivision in 1980.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

S. 0° 01' E., bet. secs. 20 and 21.

Over mountainous land.

19.855 Point for the N 1/16 sec. cor. of sec. 21 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 20 E  
| N 1/16  
| S 21  
1985

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, E of cor.

38.70 Point for the 1/4 sec. cor. of sec. 20 only, at proportionate distance, based on the 1906 plat.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
1/4 |  
S 20 |  
1985

39.71 The 1/4 sec. cor. of secs. 20 and 21, monumented with an iron post, 2 1/2 ins. diam., firmly set, protruding 6 ins. above ground, with brass cap, mkd. as described in the official record of the dependent resurvey of a portion of the subdivisional lines in 1980.

The brass cap was remarked to function as the 1/4 sec. cor. of sec. 21 only. Add the marks 1985 on the brass cap.

---

S. 0° 27' W., beginning new measurement.

23.67 The original closing cor. of secs. 20 and 21, from the N, monumented with a sandstone, 12x12x8 ins., mkd. 4 notches on E and 2 notches on S edges, with CC on N face. Add the marks AM on N face and bury the stone in place, 6 ins. below surface.

I remove the iron post that was monumented at this point in the dependent resurvey of a portion of the subdivisional lines in 1980.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

23.82 Intersect the Old Fort Thornburg Military Reservation Boundary.

Point for the closing cor. of secs. 20 and 21.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
C C  
S 20 | S 21  
OFTM  
1985

From the 1/4 sec. cor. of secs. 16 and 21, monumented with an iron post, 2 1/2 ins. diam., firmly set, protruding 6 ins. above ground, with brass cap, mkd. as described in the official record of the dependent resurvey of a portion of the subdivisional lines in 1980.

S. 89° 12' W., bet. secs. 16 and 21.

Over broken mountainous land.

19.93 Point for the W 1/16 sec. cor. of secs. 16 and 21.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
S 16  
W 1/16 S 21  
1985

39.86 The cor. of secs. 16, 17, 20, and 21.

(Restoring the Survey Executed by  
A.D. Ferron and E. Buettner in 1879)

From the cor. of secs. 4, 5, 8, and 9, monumented with an iron post, 2 1/2 ins. diam., firmly set, protruding 6 ins. above ground, with brass cap, mkd. as described in the official record of the dependent resurvey of a portion of the subdivisional lines in 1980.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

N. 0° 49' W., bet. secs. 4 and 5.

Over mountainous land.

40.71 Point for the 1/4 sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 20 E  
1/4  
S 5 | S 4  
1984

Place a sandstone boulder, 3x3x2 ft., W of aluminum post.

Cor. is located on SE slope of hollow, 40 lks. W of wash, which drains S.

81.42 The cor. of secs. 4 and 5, on the N. bdy. of the Tp., hereinbefore described.

---

(Restoring the Survey Executed by  
S.P. and J.R. Stewart in 1906)

---

From the cor. of secs. 31 and 32, on the S. bdy. of the Tp., hereinbefore described.

N. 0° 03' E., bet. secs. 31 and 32.

Over mountainous land.

39.93 The 1/4 sec. cor. of secs. 31 and 32, monumented with a quartzite stone, 14x12x8 ins., firmly set, protruding 6 ins. above ground, mkd. 1/4 on the W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

T 3 S R 20 E  
1/4  
S 31 | S 32  
1984

Deposit the mkd. stone alongside the aluminum post.

---

N.  $0^{\circ} 01'$  E., beginning new measurement.

19.905 Point for the N 1/16 sec. cor. of secs. 31 and 32.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 3 S R 20 E  
N 1/16  
S 31 | S 32  
1984

39.81 The cor. of secs. 29, 30, 31, and 32, monumented with a quartzite stone, 16x10x7 ins., firmly set, protruding 8 ins. above ground, mkd. 5 notches on the E and 1 notch on the S edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 3 S R 20 E  
S 30 | S 29  
S 31 | S 32  
1984

Deposit the mkd. stone alongside the aluminum post.

---

N.  $89^{\circ} 33'$  E., bet. secs. 29 and 32.

Over mountainous land.

40.32 Point for the 1/4 sec. cor. of secs. 29 and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

T 3 S R 20 E  
 $\frac{S 29}{S 32}$   
 1/4 1984

- 54.08 The closing cor. of secs. 29 and 32 on the Old Fort Thornburg Military Reservation Boundary, hereinbefore described.

---

(Restoring the Survey Executed by  
A. Jessen in 1900)

---

From the cor. of secs. 28, 29, 32, and 33.

N. 87° 33' W., bet. secs. 29 and 32.

Over mountainous land.

- 23.96 True point for the closing cor. of secs. 29 and 32, on the Old Fort Thornburg Military Reservation Boundary, hereinbefore described.

---

From the cor. of secs. 29, 30, 31, and 32.

N. 89° 56' W., bet. secs. 30 and 31.

Over mountainous land.

- 20.375 Point for the E 1/16 sec. cor. of secs. 30 and 31.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 3 S R 20 E  
 $\frac{S 30}{S 31}$   
 E 1/16 1984

- 40.75 The 1/4 sec. cor. of secs. 30 and 31, monumented with a sandstone, 16x12x8 ins., firmly set, protruding 6 ins. above ground, mkd. 1/4 on the N face.

At the corner point

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 3 S R 20 E  
S 30  
1/4 S 31  
1984

Deposit the mkd. stone alongside the aluminum post.

S. 89° 55' W., beginning new measurement.

39.62 The closing cor. of secs. 30 and 31, on the W. bdy. of the Tp., hereinbefore described.

From the cor. of secs. 29, 30, 31, and 32.

N. 0° 01' E., bet. secs. 29 and 30.

Over mountainous land.

19.99 Point for the S 1/16 sec. cor. of secs. 29 and 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
S 1/16  
S 30 | S 29  
1984

39.98 Point for the 1/4 sec. cor. of secs. 29 and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
1/4  
S 30 | S 29  
1984

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

59.97 Point for the N 1/16 sec. cor. of secs. 29 and 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 20 E  
N 1/16  
S 30 | S 29  
1984

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

79.96 The cor. of secs. 19, 20, 29, and 30, monumented with a sandstone, 14x6x4 ins. firmly set, protruding 8 ins. above ground, mkd. 2 notches on S and 5 notches on the E edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
S 19 | S 20  
S 30 | S 29  
1984

Deposit the mkd. stone alongside the aluminum post.

---

N. 89° 57' E., bet. secs. 20 and 29.

Over mountainous land.

19.945 Point for the W 1/16 sec. cor. of secs. 20 and 29.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
S 20  
W 1/16 | S 29  
1984

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

- 39.89 The 1/4 sec. cor. of secs. 20 and 29, monumented with a sandstone, 12x8x7 ins., firmly set, protruding 6 ins. above ground, mkd. 1/4 on the N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 4 1/2 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
S 20  
1/4 S 29  
1984

Deposit the mkd. stone alongside the aluminum post.

---

S. 89° 54' E., beginning new measurement.

- 7.10 The closing cor. of secs. 20 and 29, on the Old Fort Thornburg Military Reservation Boundary, hereinbefore described.

---

From the cor. of secs. 20, 21, 28, and 29.

S. 89° 52' W., bet. secs. 20 and 29.

Over mountainous land.

- 30.30 The closing cor. of secs. 20 and 29, on the Old Fort Thornburg Military Reservation Boundary, hereinbefore described.

---

From the cor. of secs. 19, 20, 29, and 30.

S. 89° 51' W., bet. secs. 19 and 30.

Over mountainous land.

- 20.01 Point for the E 1/16 sec. cor. of secs. 19 and 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 9 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

T 3 S R 20 E  
S 19  
E 1/16 S 30  
1984

- 40.02 The 1/4 sec. cor. of secs. 19 and 30, monumented with a sandstone, 12x10x10 ins., firmly set, protruding 6 ins. above ground, mkd. 1/4 on the N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 3 S R 20 E  
S 19  
1/4 S 30  
1984

Deposit the mkd. stone alongside the aluminum post.

---

N. 89° 55' W., beginning new measurement.

- 19.975 Point for the W 1/16 sec. cor. of secs. 19 and 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 3 S R 20 E  
S 19  
W 1/16 S 30  
1984

- 40.99 The closing cor. of secs. 19 and 30, W bdy., hereinbefore described.

---

From the cor. of secs. 19, 20, 29, and 30.

N. 0° 02' E., bet. secs. 19 and 20.

- 40.05 The 1/4 sec. cor. of secs. 19 and 20, monumented with a quartzite stone, 14x10x6 ins., firmly set, protruding 10 ins. above ground, mkd. 1/4 on W face.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
1/4  
S 19 | S 20  
1984

Deposit the mkd. stone alongside the aluminum post.

Cor. is located 5 lks. SE of fence cor., with fences bearing S and W.

---

N. 0° 07' W., beginning new measurement.

Over rolling mountainous land.

18.98 Point for the N 1/16 sec. cor. of secs. 19 and 20, at proportionate distance.

This cor. point is not monumented.

36.72 The closing cor. of secs. 19 and 20, monumented with an iron post, 2 1/2 ins. diam., firmly set, protruding 6 ins. above ground, with brass cap, mkd. as described in the official record of the dependent resurvey of a portion of the subdivisional lines in 1980.

---

(Restoring the Survey and Resurvey Executed by  
A. D. Ferron and E. Buettner in 1879,  
and S.P. and J.R. Stewart in 1906)

From the cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., hereinbefore described.

East, bet. secs. 18 and 19.

Over rolling mountainous land.

39.34 Point for 1/4 sec. cor. of sec. 18 only, at proportionate distance; there is no remaining evidence of the original corner.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
1/4 S 18  
1984

Cor. is located 58 lks. W of N-S fence line.

41.54 Point for the 1/4 sec. cor. of sec. 19 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 4 1/2 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
1/4 S 19  
1984

59.565 Point for the E 1/16 sec. cor. of sec. 18 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 20 E  
E 1/16 S 18  
1985

61.655 Point for the E 1/16 sec. cor. of sec. 19 only.

This cor. point is not monumented.

79.79 The cor. of secs. 17 and 18, monumented with an iron post, firmly set, protruding 6 ins. above ground, with brass cap, mkd. as described in the official record of the dependent resurvey of a portion of the subdivisional lines in 1980.

---

(Restoring the Survey and the Resurvey Executed by  
A. D. Ferron and E. Buettner in 1879,  
by S.P. and J.R. Stewart in 1906,  
and by G. Reynolds in 1980)

---

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

N. 88° 30' E., along the S. bdy. of sec. 17.

Over mountainous land.

- 1.98 The closing cor. of secs. 19 and 20, hereinbefore described.
- 19.57 The W 1/16 sec. cor. of sec. 17 only, monumented with an iron post, 2 1/2 ins. diam., firmly set, protruding 6 ins. above ground, with brass cap, mkd. as described in the official record of the dependent resurvey of a portion of the subdivisional lines in 1980.

---

N. 88° 30' E., beginning new measurement.

- 2.355 Point for the W 1/16 sec. cor. of sec. 20 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E

W 1/16 S 20  
1985

- 19.51 The 1/4 sec. cor. of sec. 17, monumented with an iron post, 2 1/2 ins. diam., firmly set, protruding 6 ins. above ground, with brass cap, mkd. as described in the official record of the dependent resurvey of a portion of the subdivisional lines in 1980.

---

N. 88° 30' E., beginning new measurement.

- 0.495 Point selected for the witness cor. to the 1/4 sec. cor. of sec. 20 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

W C  
T 3 S R 20 E

1/4 S 20 →  
1984

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

- 2.79 Point for the 1/4 sec. cor. of sec. 20 only, falls on face of sandstone ledge and cannot be monumented
- 19.84 The E 1/16 sec. cor. of sec. 17, monumented with an iron post, 2 1/2 ins. diam., firmly set, protruding 6 ins. above ground, with brass cap, mkd. as described in the official record of the dependent resurvey of a portion of the subdivisional lines in 1980.

---

N. 88° 30' E., beginning new measurement.

- 19.85 The cor. of secs. 16, 17, 20, and 21.

---

(Restoring the Survey Executed by  
A. D. Ferron and E. Buettner in 1879)

From the cor. of secs. 5, 6, 7, and 8, monumented with an iron post, 2 1/2 ins. diam., firmly set, protruding 6 ins. above ground, with brass cap, mkd. as described in the official record of the dependent resurvey of a portion of the subdivisional lines in 1980.

S. 87° 52' W., bet. secs. 6 and 7.

Over broken mountainous land.

- 37.73 The 1/4 sec. cor. of secs. 6 and 7, monumented with a sandstone, 23x11x7 ins., firmly set, protruding 10 ins. above ground, dimly mkd. 1/4 on the N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
S 6  
1/4 S 7  
1984

Deposit the mkd. stone alongside the aluminum post.

---

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

N. 89° 41' W., beginning new measurement.

- 38.01 The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp.,  
hereinbefore described.

From the cor. of secs. 5, 6, 7, and 8.

N. 1° 15' E., bet. secs. 5 and 6.

Over broken mountainous land.

- 15.50 Dirt road in bottom of Dry Fork Canyon, bears NW and SE.

- 39.93 The 1/4 sec. cor. of secs. 5 and 6, monumented with a sandstone,  
10x10x7 ins., firmly set, protruding 5 ins. above ground and mkd.  
1/4 on the W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in  
the ground to bedrock, and in a mound of stone, 4 ft. base, to top  
of aluminum cap, mkd.

T 3 S R 20 E  
1/4  
|  
S 6 | S 5  
|  
1985

Deposit the mkd. stone alongside the aluminum post.

N. 2° 02' E., beginning new measurement.

- 40.12 The cor. of secs. 5 and 6, on the N. bdy. of the Tp., hereinbefore  
described.

Survey of the Subdivision of Section 3,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

Survey of the Subdivision of Section 3,  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 3 and 10.

N. 0° 12' W., on the N and S center line of sec. 3.

Over mountainous land.

20.21 Point for the C-S 1/16 sec. cor. of sec. 3.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4 1/2 ft. base, to top of aluminum cap, mkd.

C  
|  
S 1/16 | S 3  
|  
C  
1984

40.42 Point for the C 1/4 sec. cor. of sec. 3, at intersection with the E and W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 5 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
C 1/4 S3  
1984

60.375 Point for the C-N 1/16 sec. cor. of sec. 3.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 5 ft. base, to top of aluminum cap, mkd.

C  
|  
N 1/16 | S 3  
|  
C  
1984

80.31 The 1/4 sec. cor. of sec. 3 only, on the N. bdy. of the Tp., hereinbefore described.

---

Survey of the Subdivision of Section 3,  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 2 and 3.

S. 89° 29' W., on the E and W center line of sec. 3.

Over mountainous land.

39.46 The C 1/4 sec. cor. of sec. 3.

60.35 Point for the C-W 1/16 sec. cor. of sec. 3.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4 1/2 ft. base, to top of aluminum cap, mkd.

C  $\frac{W \ 1/16}{S \ 3}$  C  
1984

81.24 The 1/4 sec. cor. of secs. 3 and 4.

---

From the W 1/16 sec. cor. of secs. 3 and 10.

N. 1° 54' W., on the N and S center line of the SW 1/4 of sec. 3.

Over mountainous land.

20.33 Point for the SW 1/16 sec. cor. of sec. 3, at intersection with the E and W center line of the SW 1/4 of sec. 3.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 4 1/2 ft. base, to top of aluminum cap, mkd.

SW 1/16 S 3  
1984

40.66 The C-W 1/16 sec. cor. of sec. 3.

---

From the C-S 1/16 sec. cor. of sec. 3.

S. 89° 09' W., on the E and W center line of the SW 1/4 of sec. 3.

Over mountainous land.

20.29 The SW 1/16 sec. cor. of sec. 3.

Survey of the Subdivision of Section 3,  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

40.58 The S 1/16 sec. cor. of secs. 3 and 4.

---

From the C-W 1/16 sec. cor. of sec. 3.

N. 1° 28' E., on the N and S center line of the NW 1/4 of sec. 3.

Over mountainous land.

20.00 Point for the NW 1/16 sec. cor. of sec. 3, at intersection with the E and W center line of the NW 1/4 of sec. 3.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 5 ft. base, to top of aluminum cap, mkd.

NW 1/16 S 3  
1984

39.88 The W 1/16 sec. cor. of sec. 3, on the N. bdy. of the Tp., hereinbefore described.

---

From the C-N 1/16 sec. cor. of sec. 3.

S. 89° 34' W., on the E and W center line of the NW 1/4 of sec. 3.

Over mountainous land.

20.305 The NW 1/16 sec. cor. of sec. 3.

40.61 The N 1/16 sec. cor. of secs. 3 and 4.

---

Survey of the Subdivisional Lines of Section 10,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 10 and 15.

N. 0° 32' W., on the N and S center line of sec. 10.

Over rolling bench land.

19.92 Point for the C-S 1/16 sec. cor. of sec. 10.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

Survey of the Subdivision of Section 3,  
Lines, T. 3 S., R. 20 E., Salt Lake Meridian, Utah

C  
|  
S 1/16 | S 10  
|  
C  
1984

- 39.84 Point for the C 1/4 sec. cor. of sec. 10, at intersection with the E and W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 3 S R 20 E  
C 1/4 S 10  
1984

- 60.40 Point for the C-N 1/16 sec. cor. of sec. 10.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

C  
|  
N 1/16 | S 10  
|  
C  
1984

- 80.96 The 1/4 sec. cor. of secs. 3 and 10.
- 

From the 1/4 sec. cor. of secs. 10 and 11.

S. 89° 10' W., on the E and W center line of sec. 10.

Over rolling bench land.

- 19.72 Point for the C-E 1/16 sec. cor. of sec. 10.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

E 1/16  
C ——— C  
S 10  
1984

Survey of the Subdivision of Section 10,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

39.44 The C 1/4 sec. cor. of sec. 10.

59.63 Point for the C-W 1/16 sec. cor. of sec. 10.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

W 1/16  
C ——— S 10 ——— C  
1984

79.82 The 1/4 sec. cor. of secs. 9 and 10.

---

From the C-E 1/16 sec. cor. of sec. 10.

N. 0° 29' W., on the N and S center line of the NE 1/4 of sec. 10.

Over mountainous land.

20.65 Point for the NE 1/16 sec. cor. of sec. 10, at intersection with the E and W center line of the NE 1/4 of sec. 10.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 4 1/2 ft. base, to top of aluminum cap, mkd.

NE 1/16 S 10  
1984

41.30 The E 1/16 sec. cor. of secs. 3 and 10.

---

From the N 1/16 sec. cor. of secs. 10 and 11.

S. 88° 53' W., on the E and W center line of the NE 1/4 of sec. 10.

Over mountainous land.

19.73 The NE 1/16 sec. cor. of sec. 10.

39.46 The C-N 1/16 sec. cor. of sec. 10.

---

From the cor. point for the W 1/16 sec. cor. of secs. 10 and 15.

N. 1° 14' W., on the N and S center line of the SW 1/4 of sec. 10.

Over mountainous land.

Survey of the Subdivision of Section 10,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

- 19.90 Point for the SW 1/16 sec. cor. of sec. 10, at intersection with the E and W center line of the SW 1/4 of sec. 10.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

SW 1/16 S 10  
1984

- 39.80 The C-W 1/16 sec. cor. of sec. 10.

---

From the C-S 1/16 sec. cor. of sec. 10.

S. 89° 12' W., on the E and W center line of the Sw 1/4 of sec. 10.

- 19.94 The SW 1/16 sec. cor. of sec. 10.

- 39.88 The S 1/16 sec. cor. of secs. 9 and 10.

---

Survey of the Subdivision of Section 11,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 11 and 14.

N. 0° 23' W., on the N and S center line of sec. 11.

Over mountainous land.

- 40.31 Point for the C 1/4 sec. cor. of sec. 11, at intersection with the E and W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
C 1/4 S 11  
1984

- 81.36 The 1/4 sec. cor. of secs. 2 and 11.

---

From the 1/4 sec. cor. of secs. 11 and 12.

S. 89° 01' W., on the E and W center line of sec. 11.

Survey of the Subdivision of Section 11,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

Over mountainous land.

- 39.99 The C 1/4 sec. cor. of sec. 11.  
80.05 The 1/4 sec. cor. of secs. 10 and 11.

Survey of the Subdivision of Section 12,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 12 and 13.

N. 0° 25' W., on the N and S center line of sec. 12.

- 39.84 Point for the C 1/4 sec. cor. of sec. 12, at intersection with the  
E and W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in  
the ground, with aluminum cap mkd.

T 3 S R 20 E  
C 1/4 S 12  
1985

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

- 59.73 Point for the C-N 1/16 sec. cor. of sec. 12.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in  
the ground to bedrock, and in a mound of stone, 4 ft. base, to top  
of aluminum cap, mkd.

C  
N 1/16 | S 12  
C  
1985

- 79.62 The 1/4 sec. cor. of secs. 1 and 12.

From the 1/4 sec. cor. of sec. 12 only, on the E. bdy. of the Tp.,  
hereinbefore described.

N. 89° 17' W., on the E and W center line of sec. 12.

Over mountainous land.

Survey of the Subdivision of Section 12,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

40.11 The C 1/4 sec. cor. of sec. 12.

60.31 Point for the C-W 1/16 sec. cor. of sec. 12.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

$$\begin{array}{c} \text{W } 1/16 \\ \text{C } \frac{\text{S } 12}{1985} \text{ C} \end{array}$$

80.51 The 1/4 sec. cor. of secs. 11 and 12.

---

From the N 1/16 sec. cor. of sec. 12 only, on the E. bdy. of the Tp., hereinbefore described.

N. 88° 41' W., on the E and W center line of the NE 1/4 of sec. 12.

Over mountainous land.

40.20 The C-N 1/16 sec. cor. of sec. 12.

---

From the C-W 1/16 sec. cor. of sec. 12.

N. 0° 18' W., on the N and S center line of the NW 1/4 of sec. 12.

20.10 Point for the NW 1/16 sec. cor. of sec. 12, at intersection with the E and W center line of the NW 1/4 of sec. 12.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 4 ins. in the ground to bedrock, and in a mound of stone, 4 1/2 ft. base, to top of aluminum cap, mkd.

$$\begin{array}{c} \text{NW } 1/16 \text{ S } 12 \\ 1984 \end{array}$$

40.20 The W 1/16 sec. cor. of secs. 1 and 12.

---

From the C-N 1/16 sec. cor. of sec. 12.

N. 88° 41' W., on the E and W center line of the NW 1/4 of sec. 12.

20.17 The NW 1/16 sec. cor. of sec. 12.

40.34 Point for the N 1/16 sec. cor. of secs. 11 and 12.

---

Survey of the Subdivision of Section 13,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

Survey of the Subdivision of Section 13,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 13 and 24.

N. 0° 30' W., on the N and S center line of sec. 13.

Over rolling bench land.

- 38.98 Point for the C 1/4 sec. cor. of sec. 13, at intersection with the E and W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 3 S R 20 E  
C 1/4 S 13  
1984

- 48.725 Point for the C-S-N 1/64 sec. cor. of sec. 13.

This cor. point is not monumented.

- 58.47 Point for the C-N 1/16 sec. cor. of sec. 13.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

C  
|  
N 1/16 | S 13  
|  
C  
1985

- 77.96 The 1/4 sec. cor. of secs. 12 and 13.
- 

From the 1/4 sec. cor. of sec. 13 only, on the E. bdy. of the Tp., hereinbefore described.

S. 88° 23' W., on the E and W center line of sec. 13.

Over rolling bench land.

- 20.08 Point for the C-E 1/16 sec. cor. of sec. 13.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Survey of the Subdivision of Section 13,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

$$\begin{array}{c} \text{E } 1/16 \\ \hline \text{C } \quad \text{S } 13 \quad \text{C} \\ 1985 \end{array}$$

30.12 Point for the C-W-E 1/64 sec. cor. of sec. 13.

This corner point is not monumented.

40.16 The C 1/4 sec. cor. of sec. 13.

80.31 The 1/4 sec. cor. of secs. 13 and 14.

From the C-E 1/16 sec. cor. of sec. 13.

N. 0° 11' W., on the N and S center line of the NE 1/4 of sec. 13.

Over rolling bench land.

9.64 Point for the C-S-NE 1/64 sec. cor. of sec. 13.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

$$\begin{array}{c} \text{C-S-NE } 1/64 \\ \text{S } 13 \\ 1985 \end{array}$$

19.28 Point for the NE 1/16 sec. cor. of sec. 13, at intersection with the E and W center line of the NE 1/4 of sec. 13.

This corner point is not monumented.

38.55 Point for the E 1/16 sec. cor. of secs. 12 and 13.

From the N 1/16 sec. cor. of sec. 13 only, on the E. bdy. of the Tp., hereinbefore described.

S. 89° 00' W., on the E and W center line of the NE 1/4 of sec. 13.

Over rolling bench land.

20.18 Point for the NE 1/16 sec. cor. of sec. 13.

25.225 Point for the C-E-W-NE 1/256 sec. cor. of sec. 13.

Survey of the Subdivision of Section 13,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

C-E-W-NE  
1/256 S 13  
1985

30.27 Point for the C-W-NE 1/64 sec. cor. of sec. 13.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

C-W-NE 1/64  
1985

40.36 The C-N 1/16 sec. cor. of sec. 13.

---

From the point for the C-W-E 1/64 sec. cor. of sec. 13.

N. 0° 21' W., on the N and S center line of the SW 1/4 of the NE 1/4 of sec. 13.

9.69 Point for the SW-NE 1/64 sec. cor. of sec. 13, at intersection with the E and W center line of the SW 1/4 of the NE 1/4.

This cor. point is not monumented.

19.38 The C-W-NE 1/64 sec. cor. of sec. 13.

---

From the C-S-NE 1/64 sec. cor. of sec. 13.

S. 88° 41' W., on the E and W center line of the SW 1/4 of the NE 1/4 of sec. 13.

5.03 Point for the C-E-SW-NE 1/256 sec. cor. of sec. 13.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

C-E-SW-NE  
1/256 S 13  
1985

Survey of the Subdivision of Section 13,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

10.06 Point for the SW-NE 1/64 sec. cor. of sec. 13.

20.12 Point for the C-S-N 1/64 sec. cor. of sec. 13.

---

From the C-E-SW-NE 1/256 sec. cor. of sec. 13.

N. 0° 16' W., on the N-S center line of the NE 1/4 of the SW 1/4 of the NE 1/4 of sec. 13.

9.66 The C-E-W-NE 1/256 sec. cor. of sec. 13.

---

From the C-W-NE 1/64 sec. cor. of sec. 13.

N. 0° 21' W., on the N and S center line of the NW 1/4 of the NE 1/4 of sec. 13.

19.38 The W-E 1/64 sec. cor. of secs. 12 and 13.

---

From the E 1/16 sec. cor. of secs. 13 and 24.

N. 0° 11' W., on the N and S center line of the SE 1/4 of sec. 13.

Over rolling bench land.

38.56 The C-E 1/16 sec. cor. of sec. 13.

---

Survey of the Subdivision of Section 14,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

---

From the point for the 1/4 sec. cor. of secs. 14 and 23.

N. 0° 53' W., on the N and S center line of sec. 14.

Over Dry Fork Valley bottom.

19.99 Point for the C-S 1/16 sec. cor. of sec. 14.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Survey of the Subdivision of Section 14,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

C  
|  
S 1/16 | S 14  
|  
C  
1985

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

23.00 Asc. over broken SW slope of bench land.

39.98 Point for the C 1/4 sec. cor. of sec. 14, at intersection with the E and W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 20 E  
C 1/4 S 14  
1985

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high W of cor.

79.77 The 1/4 sec. cor. of secs. 11 and 14.

From the 1/4 sec. cor. of secs. 13 and 14.

S. 89° 31' W., on the E and W center line of sec. 14.

Over broken bench land.

20.015 Point for the C-E 1/16 sec. cor. of sec. 14.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 5 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

E 1/16  
C ——— C  
S 14  
1985


40.03 The C 1/4 sec. cor. of sec. 14.

60.015 True Point for the C-W 1/16 sec. cor. of sec. 14, falls on edge of sandstone boulder and cannot be monumented.

Survey of the Subdivision of Section 14,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

- 60.065 Point selected for the witness cor. to the C-W 1/16 sec. cor. of sec. 14.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a collar of stone, with aluminum cap mkd.



- 80.00 The 1/4 sec. cor. of secs. 14 and 15.
- 

From the E 1/16 sec. cor. of secs. 14 and 23.

N. 1° 01' W., on the N and S center line of the SE 1/4 of sec. 14.

Over broken bench land.

- 19.955 Point for the SE 1/16 sec. cor. of sec. 14, at intersection with the E and W center line of the SE 1/4 of sec. 14.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.

SE 1/16 S 14  
1985

- 39.91 The C-E 1/16 sec. cor. of sec. 14.
- 

From the S 1/16 sec. cor. of secs. 13 and 14.

S. 89° 25' W., on the E and W center line of the SE 1/4 of sec. 14.

Over rolling bench land.

- 20.06 The SE 1/16 sec. cor. of sec. 14.

- 40.12 The C-S 1/16 sec. cor. of sec. 14.
- 

From the point for the W 1/16 sec. cor. of secs. 14 and 23.

N. 0° 42' W., on the N and S center line of the SW 1/4 of sec. 14.

Survey of the Subdivision of Section 14,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

Over bottom of Dry Fork Valley.

- 20.025 Point for the SW 1/16 sec. cor. of sec. 14, at intersection with the E and W center line of the SW 1/4 of sec. 14.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 4 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

SW 1/16 S 14  
1985

- 40.05 True point for the C-W 1/16 sec. cor. of sec. 14.

---

From the C-S 1/16 sec. cor. of sec. 14.

S. 89° 25' W., on the E and W center line of the SW 1/4 of sec. 14.

Over rolling bench land.

- 20.045 The SW 1/16 sec. cor. of sec. 14.

- 40.09 The S 1/16 sec. cor. of secs. 14 and 15.

---

Survey of the Subdivision of Section 18,  
T. 3 S., R. 2 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of sec. 18 only.

N. 0° 37' W., on the N and S center line of sec. 18.

Over rolling mountainous land.

- 20.17 Point for the C-S 1/16 sec. cor. of sec. 18.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

C  
|  
S 1/16 | S 18  
|  
C  
1985

Survey of the Subdivision of Section 18,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

- 40.34 Point for the C 1/4 sec. cor. of sec. 18, at intersection with the E and W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
C 1/4 S 18  
1985

Cor. is located 96 lks. W of fence corner

- 55.00 Dirt road, bears NE and SW.

- 60.51 Point for the C-N 1/16 sec. cor. of sec. 18.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 4 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

C  
|  
N 1/16 | S 18  
|  
C  
1985

Cor. is located 50 lks. E of trail road, which bears NW and SE.

- 80.68 The 1/4 sec. cor. of secs. 7 and 18.

---

From the 1/4 sec. cor. of secs. 17 and 18, monumented with an iron post, 2 1/2 ins. diam., 6 ins. above ground, in a collar of stone, with brass cap, mkd. as described in the official record of the dependent resurvey of a portion of the subdivisional lines in 1980.

S. 89° 44' W., on the E and W center line of sec. 18.

Over rolling mountainous land.

- 19.955 Point for the C-E 1/16 sec. cor. of sec. 18.

This cor. point is not monumented.

- 39.91 The C 1/4 sec. cor. of sec. 18.

- 50.00 Dirt road, bears NE and SW.

Survey of the Subdivision of Section 18,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

- 79.41 The 1/4 sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp.,  
hereinbefore described.
- 

From the E 1/16 sec. cor. of sec. 18 only.

N. 1° 00' W., on the N and S center line of the SE 1/4 of sec. 18.

Over rolling mountainous land.

- 20.215 Point for the SE 1/16 sec. cor. of sec. 18, at the intersection  
with the E-W center line of the SE 1/4 of sec. 18.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in  
the ground, with aluminum cap mkd.

SE 1/16 S18  
1985

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

Cor. is located on sandy S slope of spur.

- 40.43 Point for the C-E 1/16 sec. cor. of sec. 18.
- 

From the S 1/16 sec. cor. of secs. 17 and 18, monumented with an  
iron post, 2 1/2 ins. diam., 6 ins. above ground, in a collar of  
stone, with brass cap, mkd. as described in the official record of  
the dependent resurvey of a portion of the subdivisional lines in  
1980.

S. 89° 53' W., on the E and W center line of the SE 1/4 of sec. 18.

Over rolling mountainous land.

- 20.09 The SE 1/16 sec. cor. of sec. 18.

- 40.18 The C-S 1/16 sec. cor. of sec. 18.
- 

From the C-S 1/16 sec. cor. of sec. 18.

S. 89° 53' W., on the E and W center line of the SW 1/4 of sec. 18.

Over mountainous land.

- 39.42 The S 1/16 sec. cor. of secs. 13 and 18, on the W. bdy. of the  
Tp., hereinbefore described.
-

Survey of the Subdivision of Section 18,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

From the C-N 1/16 sec. cor. of sec. 18.

S. 89° 38' W., on the E and W center line of the NW 1/4 of sec. 18.

Over rolling mountainous land.

- 38.83 True point for the N 1/16 sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp., hereinbefore described.

Survey of the Subdivision of Section 19,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 19 and 30.

N. 0° 12' W., on the N and S center line of sec. 19.

Over rolling mountainous land.

- 20.04 Point for the C-S 1/16 sec. cor. of sec. 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

```

      C
      |
S 1/16 | S 19
      |
      C
      |
    1985
  
```

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of corner.

- 40.08 The C 1/4 sec. cor. of sec. 19, at intersection with the E and W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

```


    T 3 S R 20 E
      C 1/4 S 19
      1985
  
```

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

Survey of the Subdivision of Section 19,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

59.52 Point for the C-N 1/16 sec. cor. of sec. 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.



Raise a mound of stone, 2 1/2 base, 1 1/2 ft. high, W of cor.

76.82 The 1/4 sec. cor. of sec. 19 only.

---


From the 1/4 sec. cor. of secs. 19 and 20.

S. 89° 54' W., on the E and W center line of sec. 19.

Over rolling mountainous land.

20.09 Point for the C-E 1/16 sec. cor. of sec. 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.




Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.

40.18 The C 1/4 sec. cor. of sec. 19.

60.275 Point for the C-W 1/16 sec. cor. of sec. 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.



Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.

Survey of the Subdivision of Section 19,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

- 81.55 The 1/4 sec. cor. of sec. 19 only, on the W. bdy. of the Tp.,  
hereinbefore described.
- 

From the C-E 1/16 sec. cor. of sec. 19.

N. 0° 09' W., on the N and S center line on the NE 1/4 of sec. 19.

Over rolling mountainous land.

- 19.21 Point for the NE 1/16 sec. cor. of sec. 19, at intersection with  
the E and W center line of the NE 1/4 of sec. 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in  
the ground, with aluminum cap mkd.

NE 1/16 S 19  
1984

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

- 36.71 Point for the E 1/16 sec. cor. of sec. 19 only.
- 

From the point for the N 1/16 sec. cor. of secs. 19 and 20.

N. 89° 27' W., on the E and W center line of the NE 1/4 of sec. 19.

Over rolling mountainous land.

- 20.105 The NE 1/16 sec. cor. of sec. 19.

- 40.21 The C-N 1/16 sec. cor. of sec. 19.
- 

From the W 1/16 sec. cor. of secs. 19 and 30.

N. 0° 21' W., on the N and S center line of the SW 1/4 of sec. 19.

Over rolling mountainous land.

- 20.01 Point for the SW 1/16 sec. cor. of sec. 19, at intersection with  
the E and W center line of the SW 1/4 of sec. 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in  
the ground to bedrock, and in a mound of stone, 4 ft. base, to top  
of aluminum cap, mkd.

Survey of the Subdivision of Section 19,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

SW 1/16 S 19  
1985

40.02 The C-W 1/16 sec. cor. of sec. 19.

---

From the C-S 1/16 sec. cor. of sec. 19.

S. 89° 59' W., on the E and W center line of the SW 1/4 of sec. 19.

Over rolling mountainous land.

20.035 The SW 1/16 sec. cor. of sec. 19.

41.19 The S 1/16 sec. cor. of sec. 19, on the W. bdy. of the Tp.,  
hereinbefore described.

---

From the C-N 1/16 sec. cor. of sec. 19.

N. 89° 23' W., on the E and W center line of the NW 1/4 of sec. 19.

Over rolling mountainous land.

41.47 The N 1/16 sec. cor. of sec. 19 only, on the W. bdy. of the Tp.,  
hereinbefore described.

---

Survey of the Subdivision of Section 20,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 20 and 29.

N. 0° 03' W., on the N and S center line of sec. 20.

Over rolling mountainous land.

40.01 Point for the C 1/4 sec. cor. of sec. 20, at intersection with the  
E and W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in  
the ground, and in a collar of stone, with aluminum cap mkd.

T 3 S R 20 E  
C 1/4 S 20  
1985

Survey of the Subdivision of Section 20,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

77.76 The 1/4 sec. cor. of sec. 20 only, on the N. bdy. of sec. 20.

---

From the 1/4 sec. cor. of sec. 20 only, on the E. bdy. of sec. 20.  
S. 89° 59' W., on the E and W center line of sec. 20.

Over rolling mountainous land.

36.88 The C 1/4 sec. cor. of sec. 20.

56.795 Point for the C-W 1/16 sec. cor. of sec. 20.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in  
the ground, and in a collar of stone, with aluminum cap mkd.

$$\begin{array}{c} \text{W } 1/16 \\ \hline \text{C } \text{S } 20 \text{ C} \\ 1985 \end{array}$$

76.71 The 1/4 sec. cor. of secs. 19 and 20.

---

From the W 1/16 sec. cor. of secs. 20 and 29.

North, on the N and S center line of the SW 1/4 of sec. 20.

Over rolling mountainous land.

40.02 The C-W 1/16 sec. cor. of sec. 20.

---

From the C-W 1/16 sec. cor. of sec. 20.

N. 0° 05' W., on the N and S center line of the NW 1/4 of sec. 20.

Over rolling mountainous land.

37.23 The W 1/16 sec. cor. of sec. 20 only, on the S. bdy. of sec. 17.

---

Survey of the Subdivision of Section 21,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

---

Survey of the Subdivision of Section 21,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 21 and 28.

N. 1° 58' E., on the N and S center line of sec. 21.

Over rolling and broken mountainous land.

- 10.975 The closing cor. on the Old Fort Thornburg Military Reservation Boundary, hereinbefore described.


From the 1/4 sec. cor. of secs. 16 and 21.

S. 0° 07' W., on the N and S center line of sec. 21.

Over rolling and broken mountainous land.

- 20.345 Point for the C-N 1/16 sec. cor. of sec. 21.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.



Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

- 40.69 Point for the C 1/4 sec. cor. of sec. 21, at intersection with the E and W center line.


Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

$$\begin{array}{c} \text{T } 3 \text{ S } \text{ R } 20 \text{ E} \\ \text{C } 1/4 \text{ S } 21 \\ 1985 \end{array}$$

- 60.645 Point for the C-S 1/16 sec. cor. of sec. 21.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Survey of the Subdivision of Section 21,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah



- 68.24 The closing cor. on the Old Fort Thornburg Military Reservation Boundary, hereinbefore described.
- 


From the 1/4 sec. cor. of secs. 21 and 22.

N. 89° 24' W., on the E and W center line of sec. 21.

Over rolling and broken mountainous land.

- 19.51 Point for the C-E 1/16 sec. cor. of sec. 21.


Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.



- 39.02 The C 1/4 sec. cor. of sec. 21, at intersection with the N and S center line.

- 58.905 Point for the C-W 1/16 sec. cor. of sec. 21.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.



Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of corner.

- 78.79 The 1/4 sec. cor. of sec. 21 only.
-

Survey of the Subdivision of Section 21,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

From the E 1/16 sec. cor. of secs. 21 and 28.

N. 30° 50' E., on the N and S center line of the SE 1/4 of sec. 21.

Over rolling and broken mountainous land.

- 10.11 The closing cor. on the Old Fort Thornburg Military Reservation Boundary, hereinbefore described.

From the C-E 1/16 sec. cor. of sec. 21.

S. 00° 43' E., on the N and S center line of the SE 1/4 of sec. 21.

Over rolling and broken mountainous land.

- 19.63 Point for the SE 1/16 sec. cor. of sec. 21, at intersection with the E and W center line, of the SE 1/4 of sec. 21, falls in bottom of deep ravine and is unsafe to monument.

- 20.88 Point selected for the witness cor. to the SE 1/16 sec. cor. of sec. 21.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

W C  
↑  
SE 1/16 S 21  
1985

- 28.98 The closing cor. on the Old Fort Thornburg Military Reservation Boundary, hereinbefore described.

From the true point for the S 1/16 sec. cor. of secs. 21 and 22.

S. 89° 39' W., on the E and W center line of the SE 1/4 of sec. 21.

Over rolling mountainous land.

- 19.78 True point for the SE 1/16 sec. cor. of sec. 21.

- 39.58 The C-S 1/16 sec. cor. of sec. 21.

From the C-W 1/16 sec. cor. of sec. 21.

Survey of the Subdivision of Section 21,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

N.  $0^{\circ} 03'$  E., on the N and S center line of the NW 1/4 of sec. 21.

Over rolling and broken mountainous land.

20.10 Point for the NW 1/16 sec. cor. of sec. 21, at intersection with the E and W center line of the NW 1/4 of sec. 21.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

NW 1/16 S 21  
1985

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

Cor. is located 32 lks. N of trail road.

40.20 The W 1/16 sec. cor. of secs. 16 and 21.

From the C-N 1/16 sec. cor. of sec. 21.

S.  $89^{\circ} 54'$  W., on the E and W center line of sec. 21.

Over rolling mountainous land.

19.905 The NW 1/16 sec. cor. of sec. 21.

39.81 The N 1/16 sec. cor. of sec. 21 only.

Survey of the Subdivision of Section 22,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 22 and 27.

N.  $0^{\circ} 26''$  W., on the N and S center line of sec. 22.

Over broken mountainous land.

4.16 The point for the closing cor. on the Old Fort Thornburg Military Reservation Boundary, hereinbefore described.

From the 1/4 sec. cor. of secs. 15 and 22.

S.  $0^{\circ} 12'$  E., on the N and S center line of sec. 22.

Over broken bench land.

Survey of the Subdivision of Section 22,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

20.19 Point for the C-N 1/16 sec. cor. of sec. 22.

This corner point is not monumented.

40.38 The C 1/4 sec. cor. of sec. 22, at intersection with the E and W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
C 1/4 S 22  
1985

75.50 The point for the closing cor. on the Old Fort Thornburg Military Reservation Boundary, hereinbefore described.

---

From the 1/4 sec. cor. of secs. 22 and 23.

S. 88° 57' W., on the E and W center line of sec. 22.

Over rolling bench land.

20.185 The point for the C-E 1/16 sec. cor. of sec. 22.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

C  $\frac{E\ 1/16}{S\ 22}$  C  
1985

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.

40.37 The C 1/4 sec. cor. of sec. 22.

81.55 The 1/4 sec. cor. of secs. 21 and 22.

---

From the C-E 1/16 sec. cor. of sec. 22.

N. 0° 37' W., on the N and S center line of the NE 1/4 of sec. 22.

Over rolling and broken bench land.

20.12 Point for the NE 1/16 sec. cor. of sec. 22, at intersection with the E and W center line of the NE 1/4 of sec. 22.

Survey of the Subdivision of Section 22,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

NE 1/16 S 22  
1985

40.24 The point for the E 1/16 sec. cor. of secs. 15 and 22.

---

From the N 1/16 sec. cor. of secs. 22 and 23.

S. 89° 09' E., on the E and W center line of the NE 1/4 of sec. 22.

Over rolling and broken bench land.

20.04 The NE 1/16 sec. cor. of sec. 22.

40.08 The point for the C-N 1/16 sec. cor. of sec. 22.

---

Survey of the Subdivision of Section 23,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 23 and 26.

N. 0° 45' W., on the N and S center line of sec. 23.

Over rolling bench land.

19.975 Point for the C-S 1/16 sec. cor. of sec. 23.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

C  
|  
S 1/16 | S 23  
|  
C  
1985

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

38.50 Paved road on S side of Dry Fork Valley, bears NW and SE; also gravel road, bears N into residential area.

Survey of the Subdivision of Section 23,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

39.95 Point for the C 1/4 sec. cor. of sec. 23, at intersection with the E and W center line.

Set a steel spike, 10 ins. long, 6 ins. below surface of gravel road.

59.945 Point for the C-N 1/16 sec. cor. of sec. 23, falls in bottom of Dry Fork Creek, which flows SE.

This cor. point is not monumented.

79.94 The point for the 1/4 sec. cor. of secs. 14 and 23.

---

From the point for the 1/4 sec. cor. of secs. 23 and 24.

S. 89° 09' W., on the E and W center line of sec. 23.

Over bottom of Dry Fork Valley.

39.91 The C 1/4 sec. cor. of sec. 23.

41.50 Paved road on the S side of Dry Fork Valley, bears NW and SE; asc. over NE slope of bench land.

59.92 Point for the C-W 1/16 sec. cor. of sec. 23.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

$$\begin{array}{c} \text{W } 1/16 \\ \text{C } \frac{\text{S } 23}{1985} \text{ C} \end{array}$$

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.

79.93 The 1/4 sec. cor. of secs. 22 and 23.

---

From the S 1/16 sec. cor. of secs. 23 and 24.

S. 89° 07' W., on the E and W center line of the SE 1/4 of sec. 23.

Over Dry Fork Valley bottom.

4.00 Paved road on S side of Dry Fork Valley, bears NW and SE.

39.76 The C-S 1/16 sec. cor. of sec. 23.

---

Survey of the Subdivision of Section 23,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

From the W 1/16 sec. cor. of secs. 23 and 26.

N. 0° 34' W., on the N and S center line of the SW 1/4 of sec. 23.

Over rolling bench land.

19.96 Point for the SW 1/16 sec. cor. of sec. 23, at intersection with the E and W center line of the SW 1/4 of sec. 23.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

SW 1/16 S 23  
1985

39.92 The C-W 1/16 sec. cor. of sec. 23.

---

From the C-S 1/16 sec. cor. of sec. 23.

S. 89° 12' W., on the E and W center line of the SW 1/4 of sec. 23.

Over rolling bench land.

20.075 The SW 1/16 sec. cor. of sec. 23.

40.15 The S 1/16 sec. cor. of secs. 22 and 23.

---

From the C-W 1/16 sec. cor. of sec. 23.

N. 0° 52' W., on the N and S center line of the NW 1/4 of sec. 23.

Over rolling bench land.

20.02 Point for the NW 1/16 sec. cor. of sec. 23, at intersection with the E and W center line of the NW 1/4 of sec. 23.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

NW 1/16 S 23  
1985

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

23.30 Paved road on S side of Dry Fork Valley, bears NW and SE; thence over valley bottomland.

Survey of the Subdivision of Section 23,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

- 38.50 Dry Fork Creek, 1.50 chs. wide, flows SE.  
40.04 The point for the W 1/16 sec. cor. of secs. 14 and 23.

---

From the point for the C-N 1/16 sec. cor. of sec. 23.  
S. 89° 14' W., on the E and W center line of the NW 1/4 of sec. 23.  
Over Dry Fork Valley.

- 16.70 Paved road on S side of Dry Fork Valley, bears NW and SE.  
20.06 The NW 1/16 sec. cor. of sec. 23.  
40.12 The N 1/16 sec. cor. of secs. 22 and 23.

---

Survey of the Subdivision of Section 24,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 24 and 25.  
N. 0° 40' W., on the N and S center line of sec. 24.  
Along bottom of Dry Fork Valley.

- 8.00 Dry Fork Creek, 1.50 chs. wide, flows irregularly SE.  
21.13 Point for the C-S 1/16 sec. cor. of sec. 24.  
Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in  
the ground, with aluminum cap mkd.

C  
|  
S 1/16 | S 24  
|  
C  
1985

- 31.695 Point for the C-N-S 1/64 sec. cor. of sec. 24.  
This cor. point is not monumented.  
42.26 Point for the C 1/4 sec. cor. of sec. 24, at intersection with the  
E and W center line.

Survey of the Subdivision of Section 24,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 20 E  
C 1/4 S 24  
1985

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

61.76 Point for the C-N 1/16 sec. cor. of sec. 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 4 ins. in the ground to bedrock, and in a mound of stone, 4 1/2 ft. base, to top of aluminum cap, mkd.

C  
|  
N 1/16 | S 24  
|  
C  
1985

81.26 The 1/4 sec. cor. of secs. 13 and 24.

---

From the 1/4 sec. cor. of sec. 24 only, on the E. bdy. of the Tp., an iron post, 2 1/2 ins. diam., in a mound of stone, 4 ft. base, to top of brass cap, mkd. as described in the official record of the dependent resurvey of the E. bdy. of T. 3 S., R. 20 E., in 1973.

S. 85° 56' W., on the E and W center line of sec. 24.

Over rolling and broken bench land.

39.20 The C 1/4 sec. cor. of sec. 24.

49.205 Point for the C-E-W 1/64 sec. cor. of sec. 24.

This cor. point is not monumented.

59.21 Point for the C-W 1/16 sec. cor. of sec. 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Survey of the Subdivision of Section 24,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

$$\begin{array}{c} \text{W } 1/16 \\ \hline \text{C } \text{S } 24 \text{ C} \\ 1985 \end{array}$$

- 79.22 Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.  
The point for the 1/4 sec. cor. of secs. 23 and 24.
- 
- From the W 1/16 sec. cor. of secs. 24 and 25.  
N. 0° 29' W., on the N and S center line of the SW 1/4 of sec. 24.  
Over Dry Fork Valley.
- 20.54 Point for the SW 1/16 sec. cor. of sec. 24, at intersection with  
the E and W center line of the SW 1/4 of sec. 24.  
This cor. point is not monumented.
- 30.81 Point for the C-N-SW 1/64 sec. cor. of sec. 24.  
Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in  
the ground, with aluminum cap mkd.
- $$\begin{array}{c} \text{C-N-SW } 1/64 \\ \text{S } 24 \\ 1985 \end{array}$$
- 41.08 Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.  
The C-W 1/16 sec. cor. of sec. 24.
- 
- From the C-S 1/16 sec. cor. of sec. 24.  
S. 87° 38' W., on the E and W center line of the SW 1/4 of sec. 24.  
Over rolling and broken bench land.
- 10.03 Point for the C-E-SW 1/64 sec. cor. of sec. 24.  
This cor. point is not monumented.
- 15.045 Point for the C-W-E-SW 1/256 sec. cor. of sec. 24.  
Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in  
the ground, with aluminum cap mkd.

Survey of the Subdivision of Section 24,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

C-W-E-SW 1/256  
S 24  
1985

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.

20.06 The point for the SW 1/16 sec. cor. of sec. 24.

40.12 The S 1/16 sec. cor. of secs. 23 and 24.

From a point for the C-E-SW 1/64 sec. cor. of sec. 24.

N. 0° 35' W., on the N and S center line of the NE 1/4 of the SW 1/4 of sec. 24.

Over broken and rolling bench land.

10.42 Point for the NE-SW 1/64 sec. cor. of sec. 24, at intersection with the E and W center line of the NE 1/4 of the SW 1/4 of sec. 24.

This cor. point is not monumented.

20.84 The point for the C-E-W 1/64 sec. cor. of sec. 24.

From the point for the C-N-S 1/64 sec. cor. of sec. 24.

S. 86° 47' W., on the E and W center line of the NE 1/4 of the SW 1/4 of sec. 24.

Over rolling and broken bench land.

10.02 The NE-SW 1/64 sec. cor. of sec. 24.

15.03 Point for the C-W-NE-SW 1/256 sec. cor. of sec. 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

C-W-NE-SW 1/256  
S 24  
1985

Survey of the Subdivision of Section 24,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

- 20.04 Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.  
The C-N-SW 1/64 sec. cor. of sec. 24.

---

From the C-W-E-SW 1/256 sec. cor. of sec. 24.

N. 0° 32' W., on the N-S center line of the SW 1/4 of the NE 1/4  
of the SW 1/4 of sec. 24.

- 10.345 The C-W-NE-SW 1/256 sec. cor. of sec. 24.

---

From the C-W 1/16 sec. cor. of sec. 24.

N. 0° 29' W., on the N and S center line of the NW 1/4 of sec. 24.

Over rolling and broken bench land.

- 19.715 Point for the NW 1/16 sec. cor. of sec. 24, at intersection with  
the E and W center line of the NW 1/4 of sec. 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in  
the ground to bedrock, and in a mound of stone, 4 ft. base, to top  
of aluminum cap, mkd.

NW 1/16 S 24  
1985

- 39.43 The W 1/16 sec. cor. of secs. 13 and 24.

---

From the C-N 1/16 sec. cor. of sec. 24.

S. 86° 34' W., on the E and W center line of sec. 24.

Over rolling and broken bench land.

- 19.935 The NW 1/16 sec. cor. of sec. 24.

- 39.87 True point for the N 1/16 sec. cor. of secs. 23 and 24.

---

Survey of the Subdivision of Section 25,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 25 and 36.

Survey of the Subdivision of Section 25,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

N. 1° 33' W., on the N and S center line of sec. 25.

Over rolling and broken bench land.

- 43.71 Point for the C 1/4 sec. cor. of sec. 25, at intersection with the E and W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 20 E  
C 1/4 S 25  
1985

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

- 63.415 Point for the C-N 1/16 sec. cor. of sec. 25, falls near edge of ledge and is unsafe to monument.

- 63.445 Point selected for the witness cor. to the C-N 1/16 sec. cor. of sec. 25.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 4 ins. in the ground to bedrock, and in a mound of stone, 4 1/2 ft. base, to top of aluminum cap, mkd.

W C  
C  
N 1/16 | S 25  
↓  
1985

- 68.00 Paved road on S side of Dry Fork Valley, bears NW and SE.

- 83.12 The 1/4 sec. cor. of secs. 24 and 25.

From the 1/4 sec. cor. of sec. 25 only, on the E. bdy. of the Tp., hereinbefore described.

S. 89° 14' W., on the E and W center line of sec. 25.

Along bottom of Dry Fork Valley.

- 20.18 Point for the C-E 1/16 sec. cor. of sec. 25.

Survey of the Subdivision of Section 25,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

$$\begin{array}{c} \text{E } 1/16 \\ \text{C} \frac{\text{S } 25}{1985} \text{C} \end{array}$$

40.36 The C 1/4 sec. cor. of sec. 25.

60.64 Point for the C-W 1/16 sec. cor. of sec. 25.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

$$\begin{array}{c} \text{W } 1/16 \\ \text{C} \frac{\text{S } 25}{1985} \text{C} \end{array}$$

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.

80.92 The 1/4 sec. cor. of secs. 25 and 26.

---

From the C-E 1/16 sec. cor. of sec. 25.

N. 1° 40' W., on the N and S center line of the NE 1/4 of sec. 25.

Over Dry Fork Valley.

19.69 Point for the NE 1/16 sec. cor. of sec. 25, at intersection with the E and W center line of the NE 1/4 of sec. 25.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

$$\begin{array}{c} \text{NE } 1/16 \text{ S } 25 \\ 1985 \end{array}$$

39.38 The E 1/16 sec. cor. of secs. 24 and 25.

---

From the N 1/16 sec. cor. of sec. 25, on the E. bdy. of the Tp., hereinbefore described.

S. 89° 16' W., on the E and W center line of the NE 1/4 of sec. 25.

Over Dry Fork Valley bottomland.

Survey of the Subdivision of Section 25,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

20.14 The NE 1/16 sec. cor. of sec. 25.

40.28 True point for the C-N 1/16 sec. cor. of sec. 25.

---

From the C-W 1/16 sec. cor. of sec. 25.

N. 1° 18' W., on the N and S center line of the NW 1/4 of sec. 25.

Over rolling and broken bench land.

19.72 Point for the NW 1/16 sec. cor. of sec. 25, at intersection with the E and W center line of the NW 1/4 of sec. 25.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

NW 1/16 S 25  
1985

Raise a mound of stone, 2 1/2 base, 1 1/2 ft. high, W of cor.

39.44 The W 1/16 sec. cor. of secs. 24 and 25.

---

From the true point for the C-N 1/16 sec. cor. of sec. 25.

S. 89° 16' W., on the E and W center line of the NW 1/4 of sec. 25.

Over rough and broken bench land.

20.195 The NW 1/16 sec. cor. of sec. 25.

40.39 The N 1/16 sec. cor. of secs. 25 and 26.

---

Survey of the Subdivision of Section 28,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 28 and 33.

N. 0° 39' W., on the N and S center line of sec. 28.

Over rolling mountainous land.

40.15 Point for the C 1/4 sec. cor. of sec. 28, at intersection with the E and W center line.

Survey of the Subdivision of Section 28,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 3 S R 20 E  
C 1/4 S 28  
1985

80.16 The 1/4 sec. cor. of secs. 21 and 28.

---

From the 1/4 sec. cor. of secs. 27 and 28.

N. 89° 58' W., on the E and W center line of sec. 28.

Over mountainous land.

20.21 Point for the C-E 1/16 sec. cor. of sec. 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

E 1/16  
C — S 28 — C  
1985

40.42 The C 1/4 sec. cor. of sec. 28.

52.00 Dirt road, bears irregularly NW and SE.

79.80 The 1/4 sec. cor. of secs. 28 and 29.

---

From the C-E 1/16 sec. cor. of sec. 28.

N. 1° 32' W., on the N and S center line of the NE 1/4 of sec. 28.

Over rolling mountainous land.

39.32 The E 1/16 sec. cor. of secs. 21 and 28.

---

Survey of the Subdivision of Section 29,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 29 and 32.

Survey of the Subdivision of Section 29,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

N. 0° 18' W., on the N and S center line of sec. 29.

Over rolling mountainous land.

39.85 Point for the C 1/4 sec. cor. of sec. 29, at intersection with the E and W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 20 E  
C 1/4 S 29  
1985

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

Cor. is located 20 lks. E of N and S fence line.

79.70 The 1/4 sec. cor. of secs. 20 and 29.

---

From the 1/4 sec. cor. of secs. 28 and 29.

N. 89° 31' W., on the E and W center line of sec. 29.

Over rolling mountainous land.

27.42 The closing cor. on the E and W center line from the E, on the Old Fort Thornburg Military Reservation Boundary, hereinbefore described.

---

From the 1/4 sec. cor. of secs. 29 and 30.

N. 89° 45' E., on the E and W center line of sec. 29.

Over rolling mountainous land.

40.10 The C 1/4 sec. cor. of sec. 29.

50.54 The closing cor. on the E and W center line from the W, identical with the closing cor. from the E, on the Old Fort Thornburg Military Reservation Boundary.

---

Survey of the Subdivision of Section 30,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

---

Survey of the Subdivision of Section 30,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 30 and 31.

N. 0° 33' E., on the N and S center line of sec. 30.

Over rolling mountainous land.

19.96 Point for the C-S 1/16 sec. cor. of sec. 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 3 S R 20 E  
C  
S 1/16 | S 30  
C  
1985

39.92 Point for the C 1/4 sec. cor. of sec. 30, at intersection with the E and W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 1/2 ft. base, to top of aluminum cap, mkd.

T 3 S R 20 E  
C 1/4 S 30  
1985

59.86 Point for the C-N 1/16 sec. cor. of sec. 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.

C  
N 1/16 | S 30  
C  
1985

79.80 The 1/4 sec. cor. of secs. 19 and 30.

---

From the 1/4 sec. cor. of secs. 29 and 30.

Survey of the Subdivision of Section 30,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah  
S. 89° 59' W., on the E and W center line of sec. 30.

Over rolling and broken mountainous land.

20.19 Point for the C-E 1/16 sec. cor. of sec. 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 4 ins. in the ground to bedrock, and in a mound of stone, 5 ft. base, to top of aluminum cap, mkd.

$$\begin{array}{c} \text{E } 1/16 \\ \text{C } \frac{\text{S } 30}{1985} \text{ C} \end{array}$$

40.38 The C 1/4 sec. cor. of sec. 30.

80.79 The 1/4 sec. cor. of sec. 30 only, on the W. bdy. of the Tp., hereinbefore described.

From the C-E 1/16 sec. cor. of sec. 30.

N. 0° 17' E., on the N and S center line of the NE 1/4 of sec. 30.

Over rolling and broken mountainous land.

19.965 Point for the NE 1/16 sec. cor. of sec. 30, at intersection with the E and W center line of the NE 1/4 of sec. 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

$$\begin{array}{c} \text{NE } 1/16 \text{ S } 30 \\ 1985 \end{array}$$

39.93 The E 1/16 sec. cor. of secs. 19 and 30.

From the N 1/16 sec. cor. of secs. 29 and 30.

S. 89° 55' W., on the E and W center line of the NE 1/4 of sec. 30.

Over rolling and broken mountainous land.

20.10 The NE 1/16 sec. cor. of sec. 30.

40.20 The C-N 1/16 sec. cor. of sec. 30.

Survey of the Subdivision of Section 30,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

From the E 1/16 sec. cor. of secs. 30 and 31.

N.  $0^{\circ} 17'$  E., on the N and S center line of the SE 1/4 of sec. 30.

Over rolling and broken mountainous land.

- 19.975 Point for the SE 1/16 sec. cor. of sec. 30, at intersection with the E and W center line of the SE 1/4 of sec. 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

SE 1/16 S 30  
1985

- 39.95 The C-E 1/16 sec. cor. of sec. 30.
- 

From the S 1/16 sec. cor. of secs. 29 and 30.

N.  $89^{\circ} 58'$  W., on the E and W center line of the SE 1/4 of sec. 30.

Over rolling and broken mountainous land.

- 20.28 The SE 1/16 sec. cor. of sec. 30.

- 40.56 The C-S 1/16 sec. cor. of sec 30.
- 

From the C-N 1/16 sec. cor. of sec. 30.

N.  $89^{\circ} 58'$  W., on the E and W center line of the NW 1/4 of sec. 30.

Over rolling and broken mountainous land.

- 40.68 The N 1/16 sec. cor. of sec. 30 only, on the W. bdy. of the Tp., hereinbefore described.
- 

Survey of the Subdivision of Section 31,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of sec. 31 only, on the S. bdy. of the Tp., hereinbefore described.

Survey of the Subdivision of Section 31,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

N.  $0^{\circ} 34'$  W., on the N and S center line of sec. 31.

Over rolling and broken mountainous land.

- 39.81 Point for the C 1/4 sec. cor. of sec. 31, at intersection with the E and W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 3 S R 20 E  
C 1/4 S 31  
1985

- 59.725 Point for the C-N 1/16 sec. cor. of sec. 31.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

C  
|  
N 1/16 | S 31  
|  
C  
1985

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

- 79.64 The 1/4 sec. cor. of secs. 30 and 31.

From the 1/4 sec. cor. of secs. 31 and 32.

N.  $89^{\circ} 59'$  W., on the E and W center line of sec. 31.

Over rolling and broken mountainous land.

- 40.35 The C 1/4 sec. cor. of sec. 31.

- 80.35 True point for the 1/4 sec. cor. of sec. 31 only, on the W. bdy. of the Tp., hereinbefore described.

From the N 1/16 sec. cor. of secs. 31 and 32.

N.  $89^{\circ} 58'$  W., on the E and W center line on the NE 1/4 of sec. 31.

Over rolling and broken mountainous land.

Survey of the Subdivision of Section 31,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

40.55 The C-N 1/16 sec. cor. of sec. 31.

---

S. 89° 58' W., on the E and W center line of the NW 1/4 of sec. 31.  
Over rolling and broken mountainous land.

39.81 The N 1/16 sec. cor. of sec. 31 only, on the W. bdy. of the Tp.,  
hereinbefore described.

---

Survey of the Subdivision of Section 33,  
T. 3 S., R. 20 E., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of sec. 33 only, on the S. bdy. of the Tp.,  
hereinbefore described.

N. 0° 21' E., on the N and S center line of sec. 33.

Over rolling mountainous land.

16.03 The closing cor. on the Old Fort Thornburg Military Reservation  
Boundary, hereinbefore described.

---

From the W 1/16 sec. cor. of sec. 33 only, on the S. bdy. of the  
Tp., hereinbefore described.

N. 0° 16' E., on the N and S center line of the SW 1/4 of sec. 33.

Over rolling mountainous land.

22.67 The closing cor. on the Old Fort Thornburg Military Reservation  
Boundary, hereinbefore described.

---

General Description

Township 3 South, Range 20 East, is situated about 6 miles  
northwest of Vernal, Utah. The elevation varies from 5920 to 8620  
feet above sea level. The township is mostly comprised of  
sandstone and shale.

Township 3 South, Range 20 East, Salt Lake Meridian, Utah

Dry Fork flows in a southeasterly direction, commencing on the north boundary of section 6 and exiting through the east boundary of section 25. Ashley Creek flows in a southerly direction, commencing on the north boundary of section 1 and exiting through the east boundary of section 13.

About the only habitation is at Dry Fork Townsite in the NW 1/4 of section 15. A paved county highway to Maeser and Vernal bears southeasterly and exits the township through section 25. Other private, BLM and county unimproved roads are also throughout this area.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

## FIELD ASSISTANTS

Donzil Q. Worthington	Surveying Technician
Kenneth L. Chynoweth	Survey Aid
Douglas Moreland	Survey Aid

## CERTIFICATE OF SURVEY

I, Jerry L. Thomas, Cadastral Surveyor , HEREBY

CERTIFY upon honor that, in pursuance of special instructions date of

the 23rd day of April , 1984, I have dependently resurveyed the north, south and west boundaries, a portion of the east boundary, a portion of the Forth Thornburg Military Reservation Boundary, and a portion of the subdivisional lines and surveyed the subdivision of certain sections of Township 3 South, Range 20 East

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

September 23, 1988  
(Date)

Jerry L. Thomas  
(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The foregoing field notes of the dependent resurvey of the north, south and west boundaries, a portion of the east boundary, a portion of the Forth Thornburg Military Reservation Boundary, and a portion of the subdivisional lines and the survey of the subdivision of certain sections of Township 3 South, Range 20 East, Salt Lake Meridian, Utah

executed by Jerry L. Thomas, Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

October 18, 1988  
(Date)

Glen B. Hated  
(Chief, Cadastral Surveyor for Utah)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF A

PORTION OF THE SOUTH AND EAST BOUNDARIES,

PORTION OF THE SUBDIVISIONAL LINES

AND THE

SURVEY OF THE SUBDIVISION OF SECTION 26

IN

TOWNSHIP 8 NORTH, RANGE 7 EAST

Of the                     Salt Lake                     Meridian,  
In the State of                     Utah                    .

EXECUTED BY

                    Jerry L. Thomas                    Cadastral Surveyor                    

Under special instructions dated May 27, 1986, approved May 27, 1986, which provided for the surveys included under Group Number 691, and assignment instructions dated May 27, 1986.

Survey commenced June 25, 1986  
Survey completed July 17, 1986

INDEX DIAGRAM

Township 8 North, Range 7 East

6	5	4	3	2	1 8
7	8	9	10	11	12 7
18	17	16	15	14	13 6
19	20	21	22	23 14	24 6
30	29	28	27 13 16	26 10 12	25 4 10
31	32	33 15 3	34 12 2	35 10	36

Township 8 North, Range 7 East, Salt Lake Meridian, Utah

The following field notes describe the dependent resurvey of a portion of the south and east boundaries, a portion of the subdivisional lines, and the survey of the subdivision of section 26 in T. 8 N., R. 7 E.

History of Surveys

Surveyed by                      Retr. or Resurveyed by

NORTH BOUNDARY (Second Standard Parallel North)

All                      Julien Bausman                      1869

SOUTH BOUNDARY

All                      Ferdinand Dickert 1870

EAST BOUNDARY

Portion                      Ferdinand Dickert 1870  
Portion                      J.C. Burrill                      1875

WEST BOUNDARY (Guide Meridian)

All                      Julien Bausman                      1869

SUBDIVISION

Portion                      Ferdinand Dickert 1870  
Portion                      J.C. Burrill                      1875

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 691, Utah, dated May 27, 1986.

The directions of lines were determined by reference to true meridians established on line by altitude observations on the sun, and by hour angle observations on Polaris. The lines were carried forward by sustained angulations, being supplemented by other observations on Polaris taken throughout the progress of the survey. Distances were determined by electronic measurement.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original

Township 8 North, Range 7 East, Salt Lake Meridian, Utah

positions, lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the southeast corner of section 25, as determined by a tie to U.S.C & G.S. triangulation station "COLES", is as follows:

Latitude  $41^{\circ} 23' 35.20''$  N. Longitude  $111^{\circ} 05' 22.04''$  W.  
N.A.D. 1927

The mean magnetic declination as projected from the U.S. Geological Survey magnetic declination map of 1980 is  $14 \frac{1}{2}^{\circ}$  E.

Dependent Resurvey of a Portion of the South Boundary,  
T. 8 N., R. 7 E., Salt Lake Meridian, Utah

(Restoring the Survey Executed by  
Ferdinand Dickert in 1870)

Beginning at the cor. of secs. 2, 3, 34, and 35, monumented with quartzite stone, 17x12x9 ins., firmly set, projecting 3 ins. above ground, plainly mkd. 2 notches on the E and 4 notches on the W edges, and 6 notches on the N and S edges.

At the corner point

Set an aluminum post, 30 ins. long,  $2 \frac{1}{2}$  ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 8 N R 7 E
S 34   S 35
S 3   S 2
T 7 N
1986

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone,  $2 \frac{1}{2}$  ft. base,  $1 \frac{1}{2}$  ft. high, W of the corner.

S.  $89^{\circ} 52'$  W., bet. secs. 3 and 34.

Over gentle rolling land.

Dependent Resurvey of a Portion of the South Boundary,  
T. 8 N., R. 7 E., Salt Lake Meridian, Utah

- 24.00 Shore line of the Neponset Reservoir, bears NE and SW.
- 40.98 Point for the 1/4 sec. cor. of secs. 3 and 34, at proportionate distance; this point is under water.
- 78.00 W. shore line of Neponset Reservoir, bears irregularly N and S.
- 81.96 The cor. of secs. 3, 4, 33, and 34, monumented with a broken sandstone, 12x8x3 ins., bottom portion still buried with top portion lying alongside and dimly mkd. 3 notches on the E and W edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 8 N R 7 E
<u>S 33   S 34</u>
S 4   S 3
1986
T 7 N
1986

Deposit the broken pieces alongside the aluminum post.

Raise a mound of stone, 2 1/2 ins. base, 1 1/2 ins. high, W of the corner.

S. 89° 48' W., bet. secs. 4 and 33.

Over gentle rolling land.

- 41.01 The 1/4 sec. cor. of secs. 4 and 33, monumented with a gray sandstone, 16x8x3 ins., firmly set, projecting 2 ins. above ground, plainly mkd. 1/4 on the N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 8 N R 7 E
<u>S 33</u>
1/4 S 4
T 7 N
1986

Dependent Resurvey of a Portion of the South Boundary,  
T. 8 N., R. 7 E., Salt Lake Meridian, Utah

Deposit the mkd. stone alongside the aluminum post.

---

S. 89° 48' W., beginning new measurement.

- 41.01 The cor. of secs. 4, 5, 32, and 33, monumented with a gray sandstone, 17x7x4 ins., firmly set, projecting 6 ins. above ground, plainly mkd. 4 notches on the E, 2 notches on the W, and 6 notches on the N and S edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 8 N R 7 E
S 32   S 33
S 5   S 4
T 7 N
1986

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

---

Dependent Resurvey of a Portion of the East Boundary,  
T. 8 N., R. 7 E., Salt Lake Meridian, Utah

---

(Reestablishment of the Survey Executed by  
Ferdinand Dickert in 1870)

From the cor. of secs. 25, 30, 31, and 36, monumented with a rebar, projecting 6 ins. above ground, set by local surveyors, in E and W fence line and old fence line projecting N. This point is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Dependent Resurvey of a Portion of the East Boundary,  
T. 8 N., R. 7 E., Salt Lake Meridian, Utah

T 8 N	
R 7 E	R 8 E
S 25	S 30
S 36	S 31
1986	

N. 0° 03' W., bet. secs. 25 and 30.

Over gentle rolling land.

- 41.07 The 1/4 sec. cor. of secs. 25 and 30, monumented with a quartzite stone, 12x8x5 ins., firmly set, projecting 4 ins. above ground, plainly mkd. 1/4 on W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 8 N	
R 7 E	R 8 E
1/4	
S 25	S 30
1986	

Deposit the mkd. stone alongside the aluminum post.

---

N. 0° 20' E., beginning new measurement.

- 40.62 The cor. of secs. 19, 24, 25, and 30, marked by a rebar, projecting 6 ins. above ground, set by private surveyors. This point is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 8 N	
R 7 E	R 8 E
S 24	S 19
S 25	S 30
1986	

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

---

Dependent Resurvey of a Portion of the East Boundary,  
T. 8 N., R. 7 E., Salt Lake Meridian, Utah

N. 0° 07' E., bet. secs. 19 and 24.

Over gentle rolling land.

- 40.16 Point for the 1/4 sec. cor. of secs. 19 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 8 N
R 7 E R 8 E
1/4
S 24   S 19
1986

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

Corner is located 21 1/2 lks. E of fence line, which bears N and S.

- 80.32 The cor. of secs. 13, 18, 19, and 24, monumented with a sandstone, 14x10x6 ins., firmly set, projecting 4 ins. above ground, dimly mkd. 3 notches on the N and S edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 8 N
R 7 E R 8 E
S 13   S 18
S 24   S 19
1986

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W of the corner.

N. 0° 15' E., bet. secs. 13 and 18.

Over gentle rolling land.

Dependent Resurvey of a Portion of the East Boundary,  
T. 8 N., R. 7 E., Salt Lake Meridian, Utah

- 41.68 Point for the 1/4 sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 8 N  
R 7 E R 8 E  
1/4  
S 13 | S 18  
1986

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

- 83.36 The cor. of secs. 7, 12, 13, and 18, monumented with a sandstone, 14x8x6 ins., firmly set, projecting 6 ins. above ground, plainly mkd. 2 notches on N, 4 notches on S, and 6 notches on the E and W edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 8 N  
R 7 E R 8 E  
S 12 | S 7  
S 13 | S 18  
1986

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

---

(Reestablishment of the Survey Executed  
by J. C. Burrill in 1875)

---

N. 2° 12' W., bet. secs. 7 and 12.

Over rolling land.

- 40.44 The 1/4 sec. cor. of secs. 7 and 12, monumented with a sandstone, 8x6x4 ins., firmly set, projecting 2 ins. above ground, dimly mkd. 1/4 on the W face.

Dependent Resurvey of a Portion of the East Boundary,  
T. 8 N., R. 7 E., Salt Lake Meridian, Utah

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam.,  
24 ins. in the ground, with aluminum cap mkd.

T 8 N  
R 7 E R 8 E  
1/4  
S 12 | S 7  
1986

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high,  
W of the corner.

---

N. 2° 12' W., beginning new measurement.

- 40.44 Point for the cor. of secs. 1, 6, 7, and 12, at  
proportionate distance; there is no remaining evidence  
of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam.,  
24 ins. in the ground, with aluminum cap mkd.

T 8 N  
R 7 E R 8 E  
S 1 | S 6  
S 12 | S 7  
1986

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high,  
W of the corner.

---

N. 2° 12' W., bet. secs. 1 and 6.

Over gentle rolling land.

- 2.50 Gravel road, bears S. 85° 00' W. to the Home Ranch and  
N. 85° 00' E to State Highway No. 16.
- 10.50 State Highway No. 16, bears NW and SE.
- 40.44 The 1/4 sec. cor. of secs. 1 and 6, monumented with a  
quartzite stone, 10x8x5 ins., firmly set, projecting 3  
ins. above ground, and plainly mkd. 1/4 on W face.

Dependent Resurvey of a Portion of the East Boundary,  
T. 8 N., R. 7 E., Salt Lake Meridian, Utah

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam.,  
24 ins. in the ground, with aluminum cap mkd.

T 8 N  
R 7 E R 8 E  
1/4  
S 1 | S 6  
1986

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high,  
W of the corner.

---

N. 4° 57' W., beginning new measurement.

- 34.44 The Tp. cor. of Tps. 8 and 9 N., Rgs. 7 and 8 E.,  
monumented with a quartzite stone, 16x9x6 ins., firmly  
set, projecting 6 ins. above ground, plainly mkd. 6  
notches on the N, S, E, and W edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam.,  
24 ins. in the ground, with aluminum cap mkd.

T 9 N  
R 7 E R 8 E  
S 36 | S 31  
S 1 | S 6  
T 8 N  
1986

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high,  
W of the corner.

---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 8 N., R. 7 E., Salt Lake Meridian, Utah

---

(Reestablishment of the Survey Executed by  
Ferdinand Dickert in 1870)

---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 8 N., R. 7 E., Salt Lake Meridian, Utah

From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., monumented with a gray sandstone, 15x7x5 ins., firmly set, projecting 5 ins. above ground, plainly mkd. 1 notch on the E and 5 notches on the W edges.

This cor. point is not remonumented.

N. 0° 20' E., bet. secs. 35 and 36.

Over gentle rolling land.

- 40.92 Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.

This corner point is not monumented.

- 81.84 Point for the cor. of secs. 25, 26, 35, and 36, at proportionate distance; there is no remaining evidence of the original corner.

This corner point is not monumented.

---

From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp., hereinbefore described.

N. 89° 47' W., bet. secs. 25 and 36.

Over rolling land.

- 40.65 Point for the 1/4 sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner.

This corner point is not monumented.

- 81.30 Point for the cor. of secs. 25, 26, 35, and 36.

---

N. 0° 06' W., bet. secs. 25 and 26.

Over rolling land.

- 20.46 Point for the S 1/16 sec. cor. of secs. 25 and 26.

This corner point is not monumented.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 8 N., R. 7 E., Salt Lake Meridian, Utah

- 40.92 Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.

This corner point is not monumented.

- 51.15 Point for the S-N 1/64 sec. cor. of secs. 25 and 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

S-N 1/64  
S 26 | S 25  
1986

- 61.38 Point for the N 1/16 sec. cor. of secs. 25 and 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

N 1/16  
S 26 | S 25  
1986

- 81.84 The cor. of secs. 23, 24, 25 and 26, monumented with a gray sandstone 16x14x5 ins., firmly set, projecting 10 ins. above ground, dimly mkd. 1 notch on the E and 2 notches on the S edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 8 N R 7 E  
S 23 | S 24  
S 26 | S 25  
1986

Deposit the mkd. stone alongside the aluminum post.

From this cor., U.S.C. & G.S. triangulation station "COLES", bears N. 87° 42' 17" E., 290.938 chs. dist., determined by satellite methods, monumented with a standard disk, stamped "COLES 1962", set in a concrete post.

---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 8 N., R. 7 E., Salt Lake Meridian, Utah

From the cor. of secs. 2, 3, 34, and 35, on the S. bdy.  
of the Tp., hereinbefore described.

N. 0° 27' E., bet. secs. 34 and 35.

Over gentle rolling land.

- 4.00 Present south shore line of the Neponset Reservoir.
- 41.23 Point for the 1/4 sec. cor. of secs. 34 and 35, at proportionate distance; falls in water.
- 62.00 Present north shore line of Neponset Reservoir.
- 82.46 The cor. of secs. 26, 27, 34, and 35, monumented with a sandstone, 16x10x5 ins., firmly set, projecting 6 ins. above ground, plainly mkd. 1 notch on the S and 2 notches on the E edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T	8	N	R	7	E
S	27		S	26	
S	34		S	35	
1986					

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

From the point for the cor. of secs. 25, 26, 35, and 36.

N. 89° 13' W., bet. secs. 26 and 35.

Over gentle rolling land.

- 20.29 Point for the E 1/16 sec. cor. of secs. 26 and 35.

This corner point is not monumented.

- 40.58 Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 8 N., R. 7 E., Salt Lake Meridian, Utah

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam.,  
24 ins. in the ground, with aluminum cap mkd.

T 8 N R 7 E  
          S 26  
1/4      S 35  
          1986

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high,  
N of the corner.

81.16 The cor. of secs. 26, 27, 34, and 35.

---

N. 0° 01' E., bet. secs. 26 and 27.

Over rolling land.

41.25 The 1/4 sec. cor. of secs. 26 and 27, monumented with a  
quartzite stone, 15x11x8 ins., firmly set, projecting 5  
ins. above ground, dimly mkd. 1/4 on the W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam.,  
24 ins. in the ground, with aluminum cap mkd.

T 8 N R 7 E  
          1/4  
S 27 | S 26  
          1986

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high,  
W of the corner.

---

N. 0° 02' E., beginning new measurement.

40.81 The cor. of secs. 22, 23, 26, and 27, monumented with a  
gray sandstone, 8x4x4 ins., firmly set, projecting 2  
ins. above ground, plainly mkd. 2 notches on the E and  
S edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam.,  
24 ins. in the ground, with aluminum cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 8 N., R. 7 E., Salt Lake Meridian, Utah

T 8 N R 7 E	
S 22	S 23
S 27	S 26
1986	

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high,  
W of the corner.

---

From the cor. of secs. 23, 24, 25, and 26.

N. 89° 03' W., bet. secs. 23 and 26.

Over rolling land.

20.25 Point for the E 1/16 sec. cor. of secs. 23 and 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam.,  
24 ins. in the ground, with aluminum cap mkd.

T 8 N R 7 E	
	<u>S 23</u>
E 1/16	S 26
	1986

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high,  
N of the corner.

40.50 Point for the 1/4 sec. cor. of secs. 23 and 26, at  
proportionate distance; there is no remaining evidence  
of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam.,  
24 ins. in the ground, with aluminum cap mkd.

T 8 N R 7 E	
	<u>S 23</u>
1/4	S 26
	1986

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high,  
N of the corner.

81.00 The cor. of secs. 22, 23, 26, and 27.

---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 8 N., R. 7 E., Salt Lake Meridian, Utah

From the cor. of secs. 3, 4, 33, and 34, on the S. bdy.  
of the Tp., hereinbefore described.

N. 0° 15' E., bet. secs. 33 and 34.

Over rolling land.

- 41.09 The 1/4 sec. cor. of secs. 33 and 34, monumented with a  
gray sandstone, 17x11x5 ins., firmly set, projecting 5  
ins. above ground, plainly mkd. 1/4 on the W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam.,  
24 ins. in the ground, with aluminum cap mkd.

T 8 N R 7 E
1/4
S 33   S 34
1986

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high,  
W of the corner.

N. 0° 16' W., beginning new measurement.

- 40.94 The cor. of secs. 27, 28, 33, and 34, monumented with a  
gray sandstone, 18x14x3 ins., firmly set, projecting 6  
ins. above ground, dimly mkd. 1 notch on S and 3  
notches on the E edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam.,  
24 ins. in the ground, with aluminum cap mkd.

T 8 N R 7 E
S 28   S 27
S 33   S 34
1986

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high,  
W of the corner.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 8 N., R. 7 E., Salt Lake Meridian, Utah

From the cor. of secs. 26, 27, 34, and 35.

S. 89° 55' W., bet. secs. 27 and 34.

Over gentle rolling land.

13.00 Present northeast shore line of Neponset Reservoir.

38.50 Present west shore line of Neponset Reservoir.

40.73 The 1/4 sec. cor. of secs. 27 and 34, monumented with a gray sandstone, 18x8x5 ins., firmly set, projecting 6 ins. above ground, plainly mkd. 1/4 on the N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

	T 8 N R 7 E
	S 27
1/4	S 34
	1986

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of the corner.

---

S. 89° 17' W., beginning new measurement.

41.88 The cor. of secs. 27, 28, 33, and 34.

---

Survey of the Subdivisional Lines of Section 26,  
T. 8 N., R. 7 E., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 26 and 35.

N. 0° 02' W., on the N and S center line of sec. 26.

Over gentle rolling land.

10.27 Point for the C-S-S 1/64 sec. cor. of sec. 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Survey of the Subdivisional Lines of Section 26,  
T. 8 N., R. 7 E., Salt Lake Meridian, Utah

C S S 1/64  
S 26  
1986

20.54 Point for the C-S 1/16 sec. cor. of sec. 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam.,  
24 ins. in the ground, with aluminum cap mkd.

T 8 N R 7 E  
C  
S 1/16 | S 26  
C  
1986

41.08 Point for the center 1/4 sec. cor. of sec. 26, at  
intersection with the E and W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam.,  
24 ins. in the ground, with aluminum cap mkd.

T 8 N R 7 E  
C 1/4 S 26  
1986

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high,  
W of the corner.

61.51 Point for the C-N 1/16 sec. cor. of sec. 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam.,  
24 ins. in the ground, with aluminum cap mkd.

T 8 N R 7 E  
C  
N 1/16 | S 26  
C  
1986

81.94 The 1/4 sec. cor. of secs. 23 and 26.

---

From the point for the 1/4 sec. cor. of secs. 25 and  
26.

N. 88° 59' W., on the E and W center line of sec. 26.

Over rolling land.

Survey of the Subdivisional Lines of Section 26,  
T. 8 N., R. 7 E., Salt Lake Meridian, Utah

20.27 Point for the C-E 1/16 sec. cor. of sec. 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam.,  
24 ins. in the ground, with aluminum cap mkd.

$$\begin{array}{c} \text{E } 1/16 \\ \hline \text{C } \quad \text{S } 26 \quad \text{C} \\ 1986 \end{array}$$

40.54 The center 1/4 sec. cor. of sec. 26, at intersection  
with the N and S center line.

81.09 The 1/4 sec. cor. of secs. 26 and 27.

---

From the C-E 1/16 sec. cor. of sec. 26.

N. 0° 04' W., on the N and S center line of the NE 1/4.

Over rolling land.

10.225 Point for the C-S-NE 1/64 sec. cor. of sec. 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam.,  
24 ins. in the ground, with aluminum cap mkd.

$$\begin{array}{c} \text{C S NE } 1/64 \\ \text{S } 26 \\ 1986 \end{array}$$

20.45 Point for the NE 1/16 sec. cor. of sec. 26, at  
intersection with the E-W center line of the NE 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam.,  
24 ins. in the ground, with aluminum cap mkd.

$$\begin{array}{c} \text{NE } 1/16 \text{ S } 26 \\ 1986 \end{array}$$

40.90 The E 1/16 sec. cor. of secs. 23 and 26.

---

From the N 1/16 sec. cor. of secs. 25 and 26.

N. 89° 01' W., on the E and W center line of the NE 1/4

Over rolling land.

20.26 The NE 1/16 sec. cor. of sec. 26.

Survey of the Subdivisional Lines of Section 26,  
T. 8 N., R. 7 E., Salt Lake Meridian, Utah

40.52 The C-N 1/16 sec. cor. of sec. 26.

---

From the S-N 1/64 sec. cor. of secs. 25 and 26.

N. 89° 00' W., on the E and W center line of the SE 1/4  
of the NE 1/4 of sec. 26.

Over rolling land.

20.26 The C-S-NE 1/64 sec. cor. of sec. 26.

---

From the point for the E 1/16 sec. cor. of secs. 26 and  
35.

N. 0° 04' W., on the N and S center line of the SE 1/4  
of sec. 26.

Over rolling land.

10.25 Point for the C-S-SE 1/64 sec. cor. of sec. 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam.,  
24 ins. in the ground, with aluminum cap mkd.

C S SE 1/64  
S 26  
1986

20.50 Point for the SE 1/16 sec. cor. of sec. 26, at  
intersection with the E and W center line of the  
SE 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam.,  
24 ins. in the ground, with aluminum cap mkd.

SE 1/16 S 26  
1986

41.00 The C-E 1/16 sec. cor. of sec. 26.

---

From the point for the S 1/16 sec. cor. of secs. 25 and  
26.

N. 89° 06' W., on the E and W center line of the SE 1/4  
of sec. 26.

Survey of the Subdivisional Lines of Section 26,  
T. 8 N., R. 7 E., Salt Lake Meridian, Utah

Over rolling land.

20.28 The SE 1/16 sec. cor. of sec. 26.

40.56 The C-S 1/16 sec. cor. of sec. 26.

---

From the C-S-SE 1/64 sec. cor. of sec. 26.

N. 89° 09' W., on the E and W center line of the SW 1/4  
of the SE 1/4 of sec. 26.

Over rolling land.

20.29 The C-S-S 1/64 sec. cor. of sec. 26.

---

#### GENERAL DESCRIPTION

Township 8 North, Range 7 East is situated about 4 miles south of Woodruff, Utah. The elevation varies from 6400 ft. above sea level to 6500 ft. above sea level. The soil is mostly loam to clay loam.

Neponset Reservoir covers most of sections 34 and 35 and the spillway drains into Dry Creek, which flows northeasterly and north.

Access to this portion of the township is by several dirt roads which branch off the main road into the Deseret Livestock Ranch. The land in this township is used mainly for livestock grazing.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

## FIELD ASSISTANTS

Gregg Ostergaard	Surveying Technician
Brent Thomas	Survey Aid

## CERTIFICATE OF SURVEY

I, Jerry L. Thomas, Cadastral Surveyor, HEREBY

CERTIFY upon honor that, in pursuance of special instructions date of the 27th day of May, 1986, I have dependently resurveyed a portion of the south and east boundaries, a portion of the subdivisional lines and surveyed the subdivision of section 26 in T. 8 N., R. 7 E.,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

October 3, 1988  
(Date)

Jerry L. Thomas  
(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The foregoing field notes of the dependent resurvey of a portion of the south and east boundaries, a portion of the subdivisional lines and the survey of the subdivision of section 26 in T. 8 N., R. 7 E.,

executed by Jerry L. Thomas, Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

May 5, 1989  
(Date)

Glen B. Habel  
(Chief, Cadastral Surveyor for Utah)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF A

PORTION OF THE SOUTH BOUNDARY,

A SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,

AND THE

PARTIAL SUBDIVISION OF SECTIONS 23

IN

TOWNSHIP 1 SOUTH, RANGE 13 WEST

Of the Salt Lake Meridian,  
In the State of Utah.

EXECUTED BY

Frank C. Profaizer Cadastral Surveyor

Under special instructions dated May 18, 1987, approved May 18, 1987.

which provided for the surveys included under Group Number 711, and assignment instructions dated May 18, 1987.

Survey commenced May 19, 1987

Survey completed June 26, 1987

INDEX DIAGRAM

Township 1 South, Range 13 West

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
			9	8	4
19	20	21	22 7	23 3	24
			7	6	3
30	29	28	27 6	26 2	25
			5	5	
31	32	33	34 4	35	36
			2	2	

Township 1 South, Range 13 West, Salt Lake Meridian, Utah

The following field notes describe the dependent resurvey of a portion of the south boundary and the survey of a portion of the subdivisional lines, and the partial subdivision of section 23 of T. 1 S., R. 13 W., Salt Lake Meridian, Utah.

The south and east boundaries and a portion of the subdivisional lines were surveyed by Craig P. Sylvester in 1960.

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 711, Utah, dated May 18, 1987.

The directions of lines were determined by reference to true meridians established on line by altitude observations on the sun, and carried forward by sustained angulations. Distances were determined by electronic measurement.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions, lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the southeast corner of section 26, T. 1 S., R. 13 W., as determined by a tie to the United States Coast and Geodetic Survey triangulation station "KNOLLS" located in section 2, T. 2 S., R. 13 W., is as follows:

Latitude  $40^{\circ} 41' 44.46''$  N.      Longitude  $113^{\circ} 16' 29.98''$  W.  
N.A.D. 1927

The mean magnetic declination, as projected from the U.S. Geological Survey Magnetic Declination Map of 1980, is  $15^{\circ}$  E.

---

Dependent Resurvey of a Portion of the South Boundary,  
T. 1 S., R. 13 W., Salt Lake Meridian, Utah

---

(Reestablishment of the Survey Executed by  
Craig P. Sylvester, Supervisory Land Surveyor in 1960)

---

Dependent Resurvey of a Portion of the South Boundary,  
T. 1 S., R. 13 W., Salt Lake Meridian, Utah

Beginning at the 1/4 sec. cor. of secs. 2 and 35, on the S. bdy. of T. 1 S., R. 13 W., monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. above ground, with brass cap, mkd. as described in the official record of the 1960 survey.

West, bet. secs. 2 and 35.

- 6.50 Dirt road, bears NNW and SSE (scaled).
- 40.00 Point for the cor. of secs. 2, 3, 34, and 35, at proportionate distance; there is no remaining evidence of the original corner.
- Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T	1	S	R	13	W
S	34		S	35	
S	3		S	2	
1987					

---

West, bet. secs. 3 and 34.

- 40.00 The 1/4 sec. cor. of secs. 3 and 34, monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. above ground, with a mound of stone to N., with brass cap, mkd. as described in the official record of the 1960 survey.

---

Survey of a Portion of the Subdivisional Lines,  
T. 1 S., R. 13 W., Salt Lake Meridian, Utah

---

From the cor. of secs. 25, 26, 35, and 36, monumented with a 4x4 ins. wood post, projecting 24 ins. above the ground, mkd. as described in the official record of the 1960 survey of the subdivisional lines of T. 1 S., R. 13 W.

From which the United States Coast and Geodetic Survey triangulation station "KNOLLS", bears S. 30° 07' 23" W., 131.535 chs. dist., monumented with an iron post, 2 1/2 ins. diam., projecting 14 ins. above the ground, with bronze cap, mkd. KNOLLS 1940 and a triangle encircled with the inscription United States Coast and Geodetic Survey.

N. 0° 01' W., bet. secs. 25 and 26.

Survey of a Portion of the Subdivisional Lines,  
T. 1 S., R. 13 W., Salt Lake Meridian, Utah

40.00 Point for the 1/4 sec. cor. of secs. 25 and 26.

Set a PVC post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 1 S R 13 W  
1/4  
s 26 | S 25  
1987

80.00 Point for the cor. of secs. 23, 24, 25, and 26.

Set a PVC post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 1 S R 13 W  
S 23 | S 24  
s 26 | S 25  
1987

---

From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., projecting 7 ins. above the ground, with brass cap, mkd. as described in the official record of the 1960 survey.

N. 89° 59' W., bet secs. 24 and 25.

40.02 Point for the 1/4 sec. cor. of secs. 24 and 25.

Set a PVC post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 1 S R 13 W  
S 24  
1/4 S 25  
1987

80.04 The cor. of secs. 23, 24, 25, and 26.

---

N. 0° 01' W., bet. secs. 23 and 24.

40.00 Point for the 1/4 sec. cor. of secs. 23 and 24.

Set a PVC post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Survey of a Portion of the Subdivisional Lines,  
T. 1 S., R. 13 W., Salt Lake Meridian, Utah

T 1 S R 13 W  
1/4  
S 23 | S 24  
1987

64.24 Center line of Western Pacific Railroad, bears N.  $88^{\circ} 08'$  W. and S.  $88^{\circ} 08'$  E.

80.00 Point for the cor. of secs. 13, 14, 23, and 24.

Set a PVC post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 1 S R 13 W  
S 14 | S 13  
S 23 | S 24  
1987

---

From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., monumented with an iron post,  $2\frac{1}{2}$  ins. diam., projecting 8 ins. above the ground, with brass cap, mkd. as described in the official record of the 1960 survey.

N.  $89^{\circ} 59'$  W., bet. secs. 13 and 24.

9.00 Asphalt access road, on curve, bears N and SW.

16.30 Asphalt access road, bears SE and NW.

40.015 Point for the 1/4 sec. cor. of secs. 13 and 24.

Set a PVC post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 1 S R 13 W  
S 13  
1/4 S 24  
1987

80.03 The cor. of secs. 13, 14, 23, and 24.

---

From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., heretofore described.

Survey of a Portion of the Subdivisional Lines,  
T. 1 S., R. 13 W., Salt Lake Meridian, Utah

N.  $0^{\circ} 01'$  W., bet. secs. 34 and 35.

40.00 Point for the 1/4 sec. cor. of secs. 34 and 35.

Set a PVC post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 1 S R 13 W  
1/4  
S 34 | S 35  
1987

80.00 Point for the cor. of secs. 26, 27, 34, and 35.

Set a PVC post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 1 S R 13 W  
S 27 | S 26  
S 34 | S 35  
1987

From the cor. of secs. 25, 26, 35, and 36.

S.  $89^{\circ} 59'$  W., bet. secs. 26 and 35.

39.98 Point for the 1/4 sec. cor. of secs. 26 and 35.

Set a PVC post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 1 S R 13 W  
S 26  
1/4 S 35  
1987

51.70 Dirt road, bears NNE and SSW.

79.96 The cor. of secs. 26, 27, 34, and 35.

N.  $89^{\circ} 58'$  W., bet. secs. 27 and 34.

40.01 Point for the 1/4 sec. cor. of secs. 27 and 34.

Survey of a Portion of the Subdivisional Lines,  
T. 1 S., R. 13 W., Salt Lake Meridian, Utah

Set a PVC post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 1 S R 13 W  
S 27  
1/4 S 34  
1987

- 80.02 The cor. of secs. 27, 28, 33, and 34, monumented with 4x4 ins. wood post, projecting 23 ins. above ground, scribed and mkd. as described in the official record of the 1960 survey of the subdivisional lines of T. 1 S., R. 13 W.

From the cor. of secs. 26, 27, 34, and 35.

N. 0° 01' W., bet. secs 26 and 27.

- 40.00 Point for the 1/4 sec. cor. of secs. 26 and 27.

Set a PVC post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 1 S R 13 W  
1/4  
S 27 | S 26  
1987

- 80.00 Point for the cor. of secs. 22, 23, 26, and 27.

Set a PVC post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 1 S R 13 W  
S 22 | S 23  
S 27 | S 26  
1987

From the cor. of secs. 23, 24, 25, and 26.

S. 89° 59' W., bet. secs. 23 and 26.

- 37.00 Dirt road, 30 lks. wide, bears N and S.

- 39.97 Point for the 1/4 sec. cor. of secs. 23 and 26.

Survey of a Portion of the Subdivisional Lines,  
T. 1 S., R. 13 W., Salt Lake Meridian, Utah

Set a PVC post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 1 S R 13 W  
S 23  
1/4 S 26  
1987

79.94 The cor. of secs. 22, 23, 26, and 27.

---

N. 89° 58' W., bet. secs. 22 and 27.

40.02 Point for the 1/4 sec. cor. of secs. 22 and 27.

Set a PVC post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 1 S R 13 W  
S 22  
1/4 S 27  
1987

80.04 The cor. of secs. 21, 22, 27, and 28, monumented with 4x4 ins. wood post, projecting 16 ins. above ground, mkd. as described in the official record of the 1960 survey of the subdivisional lines.

---

From the cor. of secs. 22, 23, 26, and 27.

N. 0° 01' W., bet. secs. 22 and 23.

40.00 Point for the 1/4 sec. cor. of secs. 22 and 23.

Set a PVC post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 1 S R 13 W  
1/4  
S 22 | S 23  
1987

60.00 Point for the N 1/16 sec. cor. of secs. 22 and 23.

Set a PVC post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 1 S R 13 W  
N 1/16  
S 22 | S 23  
1987

Survey of a Portion of the Subdivisional Lines,  
T. 1 S., R. 13 W., Salt Lake Meridian, Utah

- 66.60 Center line of side track for Western Pacific Railroad, bears  
N.  $88^{\circ} 08'$  W. and S.  $88^{\circ} 08'$  E.
- 66.845 Center line of main line for Western Pacific Railroad, bears  
N.  $88^{\circ} 08'$  W. and S.  $88^{\circ} 08'$  E.
- 69.70 Asphalt road, on curve, bears ENE and W.
- 80.00 Point for the cor. of secs. 14, 15, 22, and 23.  
Set a PVC post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the  
ground, with aluminum cap mkd.

T 1 S R 13 W
S 15   S 14
S 22   S 23
1987

From the cor. of secs. 13, 14, 23, and 24.

S.  $89^{\circ} 59'$  W., bet. secs. 14 and 23.

- 29.00 Asphalt road, bears ENE and WSW.
- 39.96 Point for the 1/4 sec. cor. of secs. 14 and 23.  
Set a PVC post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the  
ground, with aluminum cap mkd.

T 1 S R 13 W
S 14
1/4 <u>S 23</u>
1987

- 49.95 Point for the east-west 1/64 sec. cor. of secs. 14 and 23.  
Set a PVC post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the  
ground, with aluminum cap mkd.

T 1 S R 13 W
S 14
E-W 1/64
S 23
1987

Survey of a Portion of the Subdivisional Lines,  
T. 1 S., R. 13 W., Salt Lake Meridian, Utah

59.94 Point for the west 1/16 sec. cor. of secs. 14 and 23.

Set a PVC post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 1 S R 13 W  
          S 14  
W 1/16    S 23  
          1987

79.92 The cor. of secs. 14, 15, 22, and 23.

---

N. 89° 55' W., bet. secs. 15 and 22.

40.015 Point for the 1/4 sec. cor. of secs. 15 and 22.

Set a PVC post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 1 S R 13 W  
          S 15  
1/4       S 22  
          1987

80.03 The cor. of secs. 15, 16, 21, and 22, monumented with a 4x4 ins. wood post, projecting 24 ins. above ground, mkd. as described in the official record of the 1960 survey of the subdivisional lines of T. 1 S., R. 13 W.

---

Subdivision of Section 23,  
T. 1 S., R. 13 W., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 23 and 26.

N. 0° 01' W., along the N and S center line of sec. 23.

40.00 Point for the center 1/4 sec. cor. of sec. 23, at intersection of the E and W center line of sec. 23.

Set a PVC post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Subdivision of Section 23,  
T. 1 S., R. 13 W., Salt Lake Meridian, Utah

T 1 S R 13 W  
C 1/4 S 23  
1987

60.00 Point for the center N 1/16 sec. cor. of sec. 23, falls on dirt road, 30 lks. wide, bears N and S.

Set an iron railroad spike, flush with surface of grade, mkd. X on top.

65.295 Center line of side track for Western Pacific Railroad, bears N.  $88^{\circ} 08'$  W. and S.  $88^{\circ} 08'$  E.

65.54 Center line of main track for Western Pacific Railroad, bears N.  $88^{\circ} 08'$  W. and S.  $88^{\circ} 08'$  E.

70.00 Point for the center-N-N 1/64 sec. cor. of sec. 23.

Set a PVC post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 1 S R 13 W  
C-N-N  
1/64  
1987

76.50 Asphalt road, bears ENE and WSW.

80.00 The 1/4 sec cor. of secs. 14 and 23.

From the 1/4 sec. cor. of secs. 23 and 24.

S.  $89^{\circ} 59'$  W., along the E and W center line of sec. 23.

37.70 Dirt road, 30 lks. wide, bears N and S.

39.97 The center 1/4 sec. cor. of sec. 23.

59.95 Point for the center-W 1/16 sec. cor. of sec. 23.

Set a PVC post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 1 S R 13 W  
W 1/16  
C S 23 C  
1987

Subdivision of Section 23,  
T. 1 S., R. 13 W., Salt Lake Meridian, Utah

79.93 The 1/4 sec. cor. of secs. 22 and 23.

---

From the center-W 1/16 sec. cor. of sec. 23.

N. 0° 01' W., along the N and S center line of the NW 1/4 of sec. 23.

20.00 Point for the NW 1/16 sec. cor. of sec. 23, at the intersection of the E and W center line of the NW 1/4 of sec. 23.

Set a PVC post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 1 S R 13 W  
NW 1/16 S 23  
1987

25.00 Point for the center-S-N 1/256 sec. cor. of the NW 1/4 of sec. 23.

Set a PVC post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 1 S R 13 W  
S 23  
C-S-N-NW  
1/256  
1987

25.95 Center line of side track for Western Pacific Railroad, bears N. 88° 08' W. and S. 88° 08' E.

26.195 Center line of main track for Western Pacific Railroad, bears N. 88° 08' W. and S. 88° 08' E.

30.00 Point for the center-N-NW 1/64 sec. cor. of sec. 23.

Set a PVC post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 1 S R 13 W  
S 23  
C-N-NW  
1/64  
1987

From this point, the NW cor. of the Knolls Gas Station, bears S. 78° 29' E., 2.73 chs. dist. The rectangular building size from its NW cor. is N. 72° E., 53 lks. and S. 18° E., 48 lks.

Subdivision of Section 23,  
T. 1 S., R. 13 W., Salt Lake Meridian, Utah

From this same point, the NW cor. of the Knolls Garage, bears S.  $60^{\circ} 52'$  E., 0.91 chs. dist. The rectangular building size from its NW cor. is N.  $69^{\circ}$  E., 36 lks. and S.  $21^{\circ}$  E., 31 lks.

31.60 Asphalt road, on curve, bears ENE and W.

40.00 The W 1/16 sec. cor. of secs. 14 and 23.

From the center N 1/16 sec. cor. of sec. 23.

S.  $89^{\circ} 59'$  W., along the E and W center line of the NW 1/4 of sec. 23.

9.99 Point for the center-E-NW 1/64 sec. cor. of sec. 23.

Set a PVC post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 1 S R 13 W  
S 23  
C-E-NW  
1/64  
1987

19.98 The NW 1/16 sec. cor. of sec. 23.

39.96 The N 1/16 sec. cor. of secs. 22 and 23.

From the center-E-NW 1/64 sec. cor. of sec. 23.

N.  $0^{\circ} 01'$  W., on the N and S center line of the NE 1/4 of the NW 1/4 of sec. 23.

5.00 Point for the center-S-NE-NW 1/256 sec. cor. of sec. 23.

Set a PVC post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 1 S R 13 W  
S 23  
C-S-NE-NW  
1/256  
1987

Subdivision of Section 23,  
T. 1 S., R. 13 W., Salt Lake Meridian, Utah

- 5.625 Center line of side track for Western Pacific Railroad, bears N. 88° 08' W. and S. 88° 08' E.
- 5.87 Center line of main track for Western Pacific Railroad, bears N. 88° 08' W. and S. 88° 08' E.
- 10.00 Point for the NE-NW 1/64 sec. cor. of sec. 23, at intersection with the E-W center line of the NE 1/4 of the NW 1/4 of sec. 23.
- Set a PVC post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 1 S R 13 W  
S 23  
NE-NW  
1/64  
1987

- 13.75 Asphalt road, on curve, bears ENE and W.
- 20.00 The E-W 1/64 sec. cor. of secs. 14 and 23.

---

From the center-N-N 1/64 sec. cor. of sec. 23.

S. 89° 59' W., on the E and W center line of the NE 1/4 of the NW 1/4 of sec. 23.

- 1.00 Dirt road, 30 lks. wide, bears N and S.
- 9.99 The NE-NW 1/64 sec. cor. of sec. 23.
- 19.98 The center-N-NW 1/64 sec. cor. of sec. 23.

---

From the center S-NE-NW 1/256 sec. cor. of sec. 23.

S. 89° 59' W., on the E and W center line of the SW 1/4 of the NE 1/4 of the NW 1/4 of sec. 23.

- 9.99 The center-S-N-NW 1/256 sec. cor. of sec. 23.
- 

#### General Description

The land encompassed in this survey is located in the Great Salt Lake Desert approximately 80 miles west of Salt Lake City, Utah. Access is by way of Interstate Highway No. 80 at interchange Knolls.

Township 1 South, Range 13 West, Salt Lake Meridian, Utah

The Western Pacific Railroad parallels the highway east and west and enters the township on the east and west boundaries at sections 19 and 24.

The highway and railroad join at the abandoned railroad settlement consisting of a service station, cafe and railroad houses.

Most of the township can be traveled with 4-wheel drive vehicles in dry season.

The soil consists of alkali clay, salt flats, sand dunes, level and rock outcrops. As a nearly level area at the bottom of a desert basin, sometimes temporarily covered with water, it is classified as a "Playas" region. Within this arid region with closed basins and undrained flats is stratified sediment high in salt content. The undrained salt flats have 4 to 30 ins. of crystalline salt overlying stratified, very strong in alkaline sediments. This playas area is mostly devoid of vegetation, although some extremely salt tolerant species occur. They are subjected to wind blowing soil and a water table as shallow as 8 ins. at some period during the year.

The vegetation consists of shadscale, a salt tolerant and drought resistant plant. Some sagebrush occupies the low hills and sand dune areas.

The elevation varies from 4225 to 4452 feet above sea level. No springs or fresh water were noted during the survey.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

## FIELD ASSISTANTS

Charles Mark Gamble	Range Technician (Fire)

## CERTIFICATE OF SURVEY

I, Frank C. Profaizer, Cadastral Surveyor , HEREBY

CERTIFY upon honor that, in pursuance of special instructions date of

the 18th day of May , 1987, I have dependently resurveyed a portion of the south boundary; surveyed a portion of the subdivisional lines and partially surveyed the subdivision of section 23 in T. 1 S., R. 13 W

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

September 1, 1988  
(Date)

Frank C. Profaizer  
(Cadastral Surveyor) <sup>A</sup>

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The foregoing field notes of the dependent resurvey of a portion of the south boundary, the survey of a portion of the subdivisional lines and a partial survey of the subdivision of section 23 in T. 1 S., R. 13 W

executed by Frank C. Profaizer, Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

January 3, 1989  
(Date)

Glen B. Hated  
(Chief, Cadastral Surveyor for Utah)



## INDEX DIAGRAM

Township 4 South, Range 22 East

	20	19	18	16	15	14
12	6 67 67	5 60 66	4 51 59	3 43 51	2 32 42	1 9 31
10	7 65 63	8 58 62	9 50 57	10 41 48	11 30 40	12 8 28
	18 61	17 56 60	16 47 56	15 37 47	14 27 39	13 6 26
	19	20 55	21 46 54	22 35 46	23 25 36	24 4 24
	30	29 53	28 45 52	27 34 44	26 23 33	25 2 22
	31	32	33 44	34 32	35 20	36

Subdivision of Section 1	- Page 68
Subdivision of Section 7	- Page 70
Subdivision of Section 12	- Page 74
Subdivision of Section 13	- Page 75
Subdivision of Section 17	- Page 79
Subdivision of Section 24	- Page 80
Subdivision of Section 25	- Page 83
Subdivision of Section 26	- Page 86
Subdivision of Section 28	- Page 88
Subdivision of Section 34	- Page 89

## Township 4 South, Range 22 East, Salt Lake Meridian, Utah

The following field notes describe the dependent resurvey of the north boundary, a portion of the east boundary (Ashley Guide Meridian), a portion of the west boundary, a portion of the subdivisional lines, and the survey of the subdivision of certain sections in T. 4 S., R. 22 E., Salt Lake Meridian, Utah.

## History of Surveys

	<u>Surveyed by</u>	<u>Retr. or Resurveyed by</u>	
<u>NORTH BOUNDARY</u>			
All Portion	Jessen and Harmston	1900 H.W. Miller	1911
<u>SOUTH BOUNDARY</u>			
All Portion	A.D. Ferron	1878 E. Bird	1949
<u>EAST BOUNDARY (Ashley Guide Meridian)</u>			
All All	A.D. Ferron	1878 Jessen and Harmston	1900
<u>WEST BOUNDARY</u>			
Portion Portion Portion	A. D. Ferron E. Buettner	1878 1879 Jessen and Harmston	1906
<u>SUBDIVISION</u>			
Portion Portion Portion	Ferron and Buettner Jessen and Harmston	1879 1906 Jessen and Harmston	1906

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 677, Utah, dated September 11, 1985.

The directions of lines were determined by reference to true meridians established on line by altitude observations on the sun, and by hour angle observations on Polaris. The lines were carried forward by sustained angulations, being supplemented by other observations on Polaris taken throughout the progress of the survey. Distances were determined by electronic measurement.

Township 4 South, Range 22 East, Salt Lake Meridian, Utah

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions, lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The N.A.D. 1927 geographic position of the southeast corner of section 25 as determined from a tie made to U.S.C. & G.S. triangulation station "JENSEN", located in the SE 1/4 of section 26, T. 4 S., R. 22 E., is

Latitude 40° 26' 06.88" N. Longitude 109° 23' 03.90" W.

An average number of readings throughout the area surveyed gives a mean magnetic declination of 14° 30' E., with a range of 1° in local attraction.

---

Dependent Resurvey of a Portion of the East Boundary  
(Ashley Guide Meridian),  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

---

(Restoring the Survey Executed by A. D. Ferron in 1878,  
and the Resurvey by Jessen and Harmston in 1900)

---

Beginning at the cor. of secs. 25 and 36 only, on the E. bdy. of T. 4 S., R. 22 E., monumented with a sandstone, 16x14x7 ins., firmly set, projecting 10 ins. above ground, plainly mkd. 5 notches on N and 1 notch on S edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S
R 22 E R 23 E
S 25
S 36   S 31
1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W of cor.

N. 0° 09'E., along the E. bdy. of sec. 25.

Over bottom of Brush Creek draw.

Dependent Resurvey of a Portion of the East Boundary  
(Ashley Guide Meridian),  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

- 3.825 The closing cor. of secs. 30 and 31, T. 4 S., R. 23 E., monumented with a sandstone 14x7x4 ins., firmly set, projecting 8 ins. above ground, plainly mkd. 5 notches on the N, 1 notch on the S, and CC on the E face

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

```

      T 4 S
    R 22 E R 23 E
      |   S 30 C
    S 25 | S 31 C
      1985
  
```

Deposit the mkd. stone alongside the aluminum post.

Asc. over broken S slope.

- 20.34 Point for the S 1/16 sec. cor. of sec. 25 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., over cross (X) chisled in solid sandstone, in a mound of stone, 5 ft. base to top, with aluminum cap mkd.

```

      T 4 S
    R 22 E R 23 E
    S 1/16 |
    S 25 |
      1985
  
```

- 40.68 The 1/4 sec. cor. of sec. 25, monumented with a limestone, 30x10x10 ins., firmly set, projecting 18 ins. above ground, plainly mkd. 1/4 on W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.

```

      T 4 S
    R 22 E R 23 E
      1/4 |
    S 25 |
      1985
  
```

Dependent Resurvey of a Portion of the East Boundary  
(Ashley Guide Meridian),  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

Deposit the mkd. stone alongside the aluminum post.

---

N. 0° 12' W., beginning new measurement.

- 3.46 Point for the 1/4 sec. cor. of sec. 30 only, T. 4 S., R. 23 E., on the E. bdy. of sec. 25, at mid point bet. the closing cor. of secs. 30 and 31, T. 4 S., R. 23 E., and the closing cor. of secs. 19 and 30, T. 4 S., R. 23 E.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.

T 4 S  
R 22 E R 23 E  
| 1/4  
| S 30  
1985

Asc. over steep and broken SW slope.

- 40.66 The cor. of secs. 24 and 25 only, monumented with a sandstone, 14x10x7 ins., firmly set, projecting 7 ins. above ground, plainly mkd. 4 notches on the N and 2 notches on the S edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 4 1/2 ft. base, to top of aluminum cap, mkd.

T 4 S  
R 22 E R 23 E  
S 24 |  
S 25 | S 30  
1985

Deposit the mkd. stone alongside the aluminum post.

---

N. 0° 08' W., along the E. bdy. of sec. 24.

Along W slope of spur.

- 3.135 Point for the closing cor. of secs. 19 and 30, T. 4 S., R. 23 E., at proportionate distance; there is no remaining evidence of the original corner.

Dependent Resurvey of a Portion of the East Boundary  
(Ashley Guide Meridian),  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 4 S  
R 22 E R 23 E  
S 24 | S 19 C  
      | S 30 C  
1985

Desc. over broken W slope.

- 34.00 Rim of ridge top, bears NW and SE; desc. over steep NE slope.
- 39.97 Point for the 1/4 sec. cor. of sec. 24 only, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S  
R 22 E R 23 E  
1/4 |  
S 24 |  
1986

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W of cor.

- 43.45 Point for the 1/4 sec. cor. of sec. 19 only, T. 4 S., R. 23 E., on the E. bdy. of sec. 24, at mid point bet. the closing cor. of secs. 19 and 30, T. 4 S., R. 23 E., and the closing cor. of secs. 18 and 19, T. 4 S., R. 23 E.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 4 S  
R 22 E R 23 E  
      | 1/4  
      | S 19  
1986

Asc. over steep SE slope.

- 54.50 Rim of ledge, bears NE and SW; thence along gentle W slope.
- 79.94 The cor. of secs. 13 and 24 only, monumented with a sandstone, 13x7x6 ins. firmly set, projecting 6 ins. above ground, plainly mkd. 3 notches on the N and S edge.

Dependent Resurvey of a Portion of the East Boundary  
(Ashley Guide Meridian),  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S  
R 22 E R 23 E  
S 13 | S 19  
S 24 |  
1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W of cor.

---

North, along the E. bdy. of sec. 13.

Along broken W slope.

- 3.825 The closing cor. of secs. 18 and 19, T. 4 S., R. 23 E., monumented with a sandstone, 16x8x5 ins., firmly set, projecting 10 ins. above ground, mkd. 3 notches on the N and S edges, and dimly mkd. CC on E face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4 1/2 ft. base, to top of aluminum cap, mkd.

T 4 S  
R 22 E R 23 E  
S 13 | S 18 C  
S 19 | S 19 C  
1985

Deposit the mkd. stone alongside the aluminum post.

- 19.99 Point for the S 1/16 sec. cor. of sec. 13 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap, mkd.

Dependent Resurvey of a Portion of the East Boundary  
(Ashley Guide Meridian),  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

T 4 S  
R 22 E R 23 E  
S 1/16 |  
S 13 |  
1985

- 39.98 The 1/4 sec. cor. of sec. 13 only, monumented with a sandstone, 18x10x3 ins., firmly set, projecting 10 ins. above ground, dimly mkd. 1/4 on W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 4 S  
R 22 E R 23 E  
1/4 |  
S 13 |  
1986

Deposit the mkd. stone alongside the aluminum post.

N. 0° 02' E., beginning new measurement.

- 3.99 Point for the 1/4 sec. cor. of sec. 18 only, T. 4 S., R. 23 E., on the E. bdy. of sec. 13, at midpoint bet. the closing cor. of secs. 18 and 19, T. 4 S., R. 23 E., and the closing cor. of secs. 7 and 18, T. 4 S., R. 23 E.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S  
R 22 E R 23 E  
| 1/4  
| S 18  
1986

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, E of corner.

- 20.14 Point for the N 1/16 sec. cor. of sec. 13 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Dependent Resurvey of a Portion of the East Boundary  
 (Ashley Guide Meridian),  
 T. 4 S., R. 22 E., Salt Lake Meridian, Utah

T 4 S  
 R 22 E R 23 E  
 N 1/16 |  
 S 13 |  
 1985

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W of cor.

- 40.28 The cor. of secs. 12 and 13 only, monumented with a sandstone, 16x10x5 ins., firmly set, projecting 10 ins. above ground, mkd. 4 notches on the S and 2 notches on the N edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S  
 R 22 E R 23 E  
 S 12 |  
 S 13 | S 18  
 1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W of corner.

N. 0° 05' W., along the E. bdy. of sec. 12.

Along broken W slope.

- 3.86 Point for the closing cor. of secs. 7 and 18, T. 4 S., R. 23 E., at proportionate distance; there is no remaining evidence of the original corner.

This corner point is not monumented.

Also bottom of deep draw, drains W.

- 35.00 Enter cultivated land.

- 40.12 Point for the 1/4 sec. cor. of sec. 12 only, at proportionate distance; there is no remaining evidence of the original corner.

Dependent Resurvey of a Portion of the East Boundary  
 (Ashley Guide Meridian),  
 T. 4 S., R. 22 E., Salt Lake Meridian, Utah

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with aluminum cap mkd.

T 4 S  
 R 22 E R 23 E  
 1/4 |  
 S 12 |  
 1985

- 54.00 Brush Creek, drains SW.
- 59.00 Dirt road, bears NE and SW.
- 78.00 Dirt road, bears S and NW.
- 80.24 Point for the cor. of secs. 1 and 12 only, at proportionate distance; there is no remaining evidence of the original corner. This point falls in Brush Creek and is marked by a steel fence post, placed there by Uintah Engineering and Land Surveying. No other improvements were made on this corner point.

Brush Creek, drains SE from NE.

---

N. 0° 05' W., along the E. bdy. of sec. 1.

Along bottom of Brush Creek.

- 3.00 Brush Creek, drains W.
- 3.975 The closing cor. of secs. 6 and 7, T. 4 S., R. 23 E., monumented with an aluminum cap, set in N edge of dirt road that bears E and W, mkd. T4S R22E R23E CC S6 S7 1985 set by Uintah Engineering and Land Surveying.
- 8.00 Brush Creek, drains E.
- 25.00 Brush Creek, drains WSW.
- 40.12 Point for the 1/4 sec. cor. of sec. 1 only, at proportionate distance; there is no remaining evidence of the original corner. This corner point is not monumented.
- 80.24 Point for the Tp. cor. of Tps. 3 and 4 S., Rs. 22 and 23 E., at proportionate distance; there is no remaining evidence of the original corner. This corner point is not monumented.

Dependent Resurvey of a Portion of the East Boundary  
 (Ashley Guide Meridian),  
 T. 4 S., R. 22 E., Salt Lake Meridian, Utah

From this corner point, the 1/4 sec. cor. of secs. 6 and 31, T. 3 and 4 S., R. 23 E., monumented with an aluminum pipe, firmly set, projecting 2 ins. above mound of stone, with aluminum cap, mkd. as described in the official resurvey of the S. bdy., T. 3 S., R. 23 E., in 1984, bears N. 89° 54' E., 40.10 chs. dist.

The 1/4 sec. cor. of secs. 31 and 36, T. 3 S., Rs. 22 and 23 E., monumented with an aluminum pipe, firmly set, projecting 6 ins. above mound of stone, with aluminum cap, mkd. as described in the official resurvey of the W. bdy., T. 3 S., R. 23 E., in 1984, bears N. 0° 06' W., 40.12 chs. dist.

---

Dependent Resurvey of a Portion of the East Boundary,  
 T. 4 S., R. 21 E., Salt Lake Meridian, Utah

---

(Reestablishment of the Survey Executed by  
 A. D. Ferron in 1878, and the Retracement by  
 Jessen and Harmston in 1900)

The cor. of secs. 7, 12, 13, and 18, determined by a steel peg imbedded in asphalt near center of road intersection, with roads bearing N, S, E and W. This was established by the Uintah County Surveyor and is accepted as a careful and faithful reestablishment of the position of the original corner. No improvements on this corner point were made.

N. 0° 40' W., along the E. bdy. of sec. 12.

Along paved road in residential area.

24.765 Point for the S 1/16 sec. cor. of sec. 7 only, T. 4 S., R. 22 E.

This corner point is not monumented.

40.57 The 1/4 sec. cor. of sec. 12 only, T. 4 S., R. 21 E., marked by a steel peg imbedded in asphalt near center of road intersection, with roads bearing N, S and W. This point was established by the Uintah County Surveyor and is accepted as a careful and faithful reestablishment of the position of the original corner.

No improvements on this corner point were made.

---

Dependent Resurvey of a Portion of the East Boundary,  
T. 4 S., R. 21 E., Salt Lake Meridian, Utah

N. 0° 03' E., beginning new measurement.

- 4.52 Point for the 1/4 sec. cor. of sec. 7 only, T. 4 S., R. 22 E., falls in the middle of a paved road, which bears N and S.

Set a nail, 4 ins. long, flush with pavement, from which

An aluminum post, 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 45° 00' E., 58 lks. dist., with aluminum cap, mkd. T4S R22E 1/4 S7 1986 38.3 FT., and an arrow pointing to the cor.

An aluminum post, 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 45° 00' E., 60 lks. dist., with aluminum cap, mkd. T4S R22E 1/4 S7 1986 39.6 FT., and an arrow pointing to the cor.

- 24.845 Point for the N 1/16 sec. cor. of sec. 7 only, T. 4 S., R. 22 E.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

```

      T 4 S
    R 21 E R 22 E
      | N 1/16
      | S 7
      1985
  
```

- 40.66 The cor. of secs. 1 and 12 only, T. 4 S., R. 21 E., monumented with a small sandstone, 6x6x4 ins., loosely set and plainly mkd. 5 notches on the S and 1 notch on the N edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

```

      T 4 S
    R 21 E R 22 E
      S 1 |
      S 12 | S 7
      1985
  
```

Deposit the mkd. stone alongside the aluminum post.

This cor. is set in fence line, which bears N and S.

---

Dependent Resurvey of a Portion of the East Boundary,  
T. 4 S., R. 21 E., Salt Lake Meridian, Utah

N.  $0^{\circ} 52'$  W., along the E. bdy. of sec. 1.

Over rolling bench land.

- 4.51 Point for the closing cor. of secs. 6 and 7, T. 4 S., R. 22 E., at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

```

      T 4 S
    R 21 E R 22 E
      S 1 | S 6 C
          | S 7 C
          1985
  
```

- 19.94 Point for the S 1/16 sec. cor. of sec. 1 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

```

      T 4 S
    R 21 E R 22 E
    S 1/16 |
          S 1 |
          1985
  
```

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W of corner.

- 39.88 Point for the 1/4 sec. cor. of sec. 1 only, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

```

      T 4 S
    R 21 E R 22 E
      1/4 |
    S 1 |
      1985
  
```

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of corner.

- 44.39 Point for the 1/4 sec. cor. of sec. 6 only, T. 4 S., R. 22 E.

Dependent Resurvey of a Portion of the East Boundary,  
T. 4 S., R. 21 E., Salt Lake Meridian, Utah

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S  
R 21 E R 22 E  
| 1/4  
| S 6  
1985

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, E of corner.

- 79.28 The cor. of Tps. 3 and 4 S., R. 21 E., monumented with an iron post, 2 1/2 ins. diam., firmly set and mkd. as described in the official dependent resurvey of the S. bdy. of T. 3 S., R. 21 E., in 1973.

---

(Reestablishment of the Survey Executed  
by Jessen and Harmston in 1906 and  
the Resurvey by J. L. Thomas in 1973)

---

N. 0° 04' E., along the E. bdy. of sec. 36, T. 3 S., R. 21 E.

Over rolling bench land.

- 4.96 The closing cor. of Tps. 3 and 4 S., R. 22 E., monumented with a sandstone, 18x14x10 ins., firmly set in mound of stone, dimly mkd. CC on E face.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S  
R 21 E R 22 E  
| S 31 C  
S 36 | S 6 C  
1985

Deposit the mkd. stone alongside the aluminum post.

- 39.93 The 1/4 sec. cor. of sec. 36 only, T. 3 S., R. 21 E., monumented with an iron post, 2 1/2 ins. diam., firmly set and mkd. as described in the official record of the 1973 resurvey of a portion of the E. bdy., T. 3 S., R. 21 E.
-

Dependent Resurvey of the North Boundary,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

Dependent Resurvey of the North Boundary,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

---

(Reestablishment of the Survey Executed by  
Jessen and Harmston in 1900)

---

From the point for the cor. of Tps. 3 and 4 S., Rs. 22 and 23 E.,  
hereinbefore described.

S.  $89^{\circ} 57'$  W., bet. secs. 1 and 36.

Over rolling bench land.

11.00 Dirt road, bears N and S.

20.135 Point for the E 1/16 sec. cor. of secs. 1 and 36, falls near  
center of paved road.

At the cor. point, set a spike, 6 ins. long, flush with surface of  
road, from which

An aluminum post, 30 ins. long, 2 1/2 ins. diam., set 24  
ins. in the ground for a reference monument, bears  
S.  $45^{\circ} 00'$  E., 50 lks. dist., with aluminum cap, mkd. T4S  
R22E E 1/16 RM S1 1986 33 FT., and an arrow pointing to  
the cor.

An aluminum post, 30 ins. long, 2 1/2 ins. diam., set 24  
ins. in the ground for a reference monument, bears  
S.  $45^{\circ} 00'$  W., 50 lks. dist., with aluminum cap, mkd. T4S  
R22E E 1/16 RM S1 1986 33 FT., and an arrow pointing to  
the cor.

Thence along S edge of paved road.

40.27 The 1/4 sec. cor. of secs. 1 and 36, monumented with a limestone,  
18x10x8 ins., firmly set, projecting 10 ins. above ground, plainly  
mkd. 1/4 on the N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in  
the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to  
top of aluminum cap, mkd.

Dependent Resurvey of the North Boundary,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

T 3 S R 22 E  
S 36  
1/4 S 1  
T 4 S  
1985

Deposit the mkd. stone alongside the aluminum post.

---

S. 89° 55' W., beginning new measurement.

Over rolling bench land.

33.00 Paved road, bears NE and SW.

37.00 Paved road, bears NE and SW.

40.18 The cor. of secs. 1, 2, 35, and 36, monumented with a limestone, 14x12x10 ins., firmly set, projecting 7 ins. above ground, dimly mkd. 1 notch on E and 5 notches on W edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 22 E  
S 35 | S 36  
S 2 | S 1  
T 4 S  
1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of corner.

---

S. 89° 47' W., bet. secs. 2 and 35.

Over rolling clay hills.

39.88 The 1/4 sec. cor. of secs. 2 and 35, monumented with a sandstone, 18x16x6 ins., firmly set, projecting 8 ins. above ground, and plainly mkd. 1/4 on the N face.

At the corner point

Dependent Resurvey of the North Boundary,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 22 E  
S 35  
1/4    S 2  
T 4 S  
1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, N of corner.

---

N. 89° 56' W., beginning new measurement.

40.46 The cor. of secs. 2, 3, 34, and 35, monumented with a limestone, 18x16x4 ins., firmly set, projecting 10 ins. above ground, plainly mkd. 2 notches on E and 4 notches on the W edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 22 E  
S 34 | S 35  
S 3 | S 2  
T 4 S  
1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W of corner.

---

(Reestablishment of the Survey Executed by  
Jessen and Harmston in 1900 and the  
Retracement Executed by H.W. Miller in 1911)

S. 89° 25' W., bet. secs. 3 and 34.

Over rolling clay hills.

Dependent Resurvey of the North Boundary,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

- 40.68 The 1/4 sec. cor. of secs. 3 and 34, monumented with a quartzite stone, 18x14x8 ins., firmly set, projecting 10 ins. above ground, mkd. 1/4 on N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 22 E  
           S 34  
 1/4     S 3  
           T 4 S  
           1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of corner.

---

S. 89° 53' W., beginning new measurement.

- 40.10 The cor. of secs. 3, 4, 33, and 34, monumented with a sandstone, 18x9x5 ins., firmly set, projecting 8 ins. above ground, mkd. 3 notches on the E and W edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 22 E  
 S 33 | S 34  
 S 4 | S 3  
 T 4 S  
 1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W of corner.

---

(Reestablishment of the Survey Executed by  
Jessen and Harmston in 1900)

---

Dependent Resurvey of the North Boundary,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

S. 89° 58' W., bet. secs. 4 and 33.

Over rolling clay hills.

40.20 The 1/4 sec. cor. of secs. 4 and 33, monumented with a sandstone, 14x12x6 ins., firmly set, projecting 8 ins. above ground, plainly mkd. 1/4 on N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 22 E

1/4  $\frac{S\ 33}{S\ 4}$   
T 4 S  
1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of corner.

N. 89° 56' W., beginning new measurement.

40.20 The cor. of secs. 4, 5, 32, and 33, monumented with a limestone, 14x12x3 ins., loosely set, and dimly mkd. 4 notches on the E and 2 notches on the W edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 22 E  
 $\frac{S\ 32\ | \ S\ 33}{S\ 5\ | \ S\ 4}$   
T 4 S  
1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W of corner.

Dependent Resurvey of the North Boundary,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

S. 89° 58' W., bet. secs. 5 and 32.

Over rolling clay hills.

40.12 The 1/4 sec. cor. of secs. 5 and 32, monumented with a limestone, 16x12x4 ins., firmly set, projecting 6 ins. above ground, mkd. 1/4 on the N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 22 E  
S 32  
1/4 S 5  
T 4 S  
1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of corner.

S. 89° 59' W., beginning new measurement.

40.19 The cor. of secs. 5, 6, 31, and 32, monumented with a limestone, 14x10x8 ins., firmly set, projecting 8 ins. above ground, plainly mkd. 5 notches on the E and 1 notch on the W edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 3 S R 22 E  
S 31 | S 32  
S 6 | S 5  
T 4 S  
1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of corner.

Dependent Resurvey of the North Boundary,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

N. 89° 59' W., bet. secs. 6 and 31.

Over rolling land.

- 40.15 The 1/4 sec. cor. of secs. 6 and 31, monumented with a sandstone, 16x12x3 ins., firmly set, projecting 8 ins. above ground, plainly mkd. 1/4 on the N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

	T 3 S R 22 E
	S 31
1/4	S 6
	T 4 S
	1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, N of corner.

---

N. 89° 59" W., beginning new measurement.

- 8.40 Top of ridge, slopes N; desc. over steep W slope.
- 18.40 Enter bottom land of wide draw, draining SW.
- 44.24 The closing cor. of Tps. 3 and 4 S., R. 22 E., hereinbefore described.

---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

---

(Reestablishment of the Survey Executed by  
Ferron and Buettner in 1879)

---

From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap, mkd. as described in the official record of the 1949 dependent resurvey of a portion of the N. bdy., T. 5 S., R. 22 E.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

N. 0° 38' W., bet. secs. 35 and 36.

Over gentle rolling land.

- 40.47 Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
1/4  
S 35 | S 36  
1985

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W of corner.

Corner is located on steep N slope, 50 ft. below rim of spur.

- 80.94 The cor. of secs. 25, 26, 35, and 36, monumented with a quartzite stone, 10x8x4 ins., firmly set, projecting 6 ins. above ground, dimly mkd. 1 notch on E edge.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
S 26 | S 25  
S 35 | S 36  
1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W of corner.

---

(Reestablishment of the Survey Executed by  
Ferron and Buettner in 1879 and the Retracement Executed by  
Jessen and Harmston in 1906)

---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

From the cor. of secs. 25 and 36 only, on the E. bdy. of the Tp.,  
hereinbefore described.

S. 89° 27' W., bet. secs. 25 and 36.

Along bottom of Brush Creek Draw.

20.165 Point for the E 1/16 sec. cor. of secs. 25 and 36, falls in Brush  
Creek 2 feet deep, 25 lks. wide, flows SE.

21.165 Point selected for the witness cor. to the E 1/16 sec. cor. of  
secs. 25 and 36.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in  
the ground, with aluminum cap mkd.

W C  
T 4 S R 22 E  
S 25  
E 1/16 S 36 →  
1985

40.33 The 1/4 sec. cor. of secs. 25 and 36, monumented with a quartzite  
stone, 12x7x4 ins., firmly set, projecting 6 ins. above ground,  
plainly mkd. 1/4 on N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in  
the ground, with aluminum cap mkd.

T 4 S R 22 E  
S 25  
1/4 S 36  
1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of  
corner.

---

S. 88° 58' W., beginning new measurement.

5.50 Paved road, bears SE and NW.

39.76 The cor. of secs. 25, 26, 35, and 36.

---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

(Reestablishment of the Survey Executed by  
Jessen and Harmston in 1906)

---

N. 0° 21' W., bet. secs. 25 and 26.

Over rolling and broken land.

5.50 Paved road, bears NW and curves E.

21.225 Point for the S 1/16 sec. cor. of secs. 25 and 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in  
the ground, and in a collar of stone, with aluminum cap mkd.

T 4 S R 22 E  
S 1/16  
S 26 | S 25  
1985

41.24 The 1/4 sec. cor. of secs. 25 and 26, monumented with a sandstone,  
12x10x7 ins., firmly set, projecting 6 ins. above ground, plainly  
mkd. 1/4 on the W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in  
the ground, with aluminum cap mkd.

T 4 S R 22 E  
1/4  
S 26 | S 25  
1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. diam., 1 1/2 ft. high, W of  
corner.

---

N. 0° 04' W., beginning new measurement.

40.22 The cor. of secs. 23, 24, 25, and 26, monumented with a sandstone,  
16x15x7 ins. firmly set, projecting 8 ins. above ground, plainly  
mkd. 2 grooves on S and 1 groove on E face.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E
S 23   S 24
S 26   S 25
1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of corner.

From the cor. of secs. 24 and 25 only, on the E. bdy. of the Tp., hereinbefore described.

S. 89° 18' W., bet. secs. 24 and 25.

Desc. over steep W slope of main ridge.

40.17 Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 4 S R 22 E
1/4    S 24
S 25
1985

49.00 Enter Brush Creek bottom, drains S.

60.255 Point for the W 1/16 sec. cor. of secs. 24 and 25.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E
W 1/16    S 24
S 25
1985

80.34 The cor. of secs. 23, 24, 25, and 26.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

N. 0° 16' W., bet. secs. 23 and 24.

Over broken bench land.

20.10 Point for the S 1/16 sec. cor. of secs. 23 and 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
S 1/16  
S 23 | S 24  
1985

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of corner.

30.15 Point for the N - S 1/64 sec. cor. of secs. 23 and 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

N-S 1/64  
S 23 | S 24  
1985

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of corner.

40.20 The 1/4 sec. cor. of secs. 23 and 24, monumented with a sandstone, 12x9x6 ins., firmly set, projecting 8 ins. above ground, plainly mkd. 1/4 on the W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
1/4  
S 23 | S 24  
1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of corner.

---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

N.  $0^{\circ} 28'$  W., beginning new measurement.

0.35 Gravel road, bears NE and SW.

40.27 The cor. of secs. 13, 14, 23, and 24, monumented with a sandstone, 15x8x7 ins., firmly set, projecting 8 ins. above ground, plainly mkd. 3 notches on S and 1 notch on E edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E	
S 14	S 13
S 23	S 24
1985	

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of corner.

From the cor. of secs. 13 and 24 only, on the E. bdy. of the Tp., hereinbefore described.

S.  $89^{\circ} 36'$  W., bet. secs. 13 and 24.

Desc. over steep W slope of main ridge.

19.97 Point for the E 1/16 sec. cor. of secs. 13 and 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E	
<u>S 13</u>	
E 1/16	<u>S 24</u>
1985	

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of corner.

39.94 The 1/4 sec. cor. of secs. 13 and 24, monumented with a sandstone, 14x12x8 ins., firmly set, projecting 8 ins. above ground, plainly mkd. 1/4 on the N face.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap, mkd.

T 4 S R 22 E  
           S 13  
 1/4     S 24  
           1985

Deposit the mkd. stone alongside the aluminum post.

From this cor. point, a sandstone, 7x5x4 ins., firmly set, projecting 4 ins. above ground, plainly mkd. 1/4, alongside fence corner post, with fences bearing N, S, and W, bears N. 88° 45' W., 2.335 chs. dist. Bury the sandstone alongside the fence corner post and below the surface of the ground.

---

S. 89° 45' W., beginning new measurement.

- 8.00     Enter bottom of Brush Creek draw.
- 14.00    Brush Creek, drains SE.
- 20.36    Point for the W 1/16 sec. cor. of secs. 13 and 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
           S 13  
 W 1/16   S 24  
           1985

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of corner.

- 24.00    Gravel road, bears NE and SW.
- 40.72    The cor. of secs. 13, 14, 23, and 24.

---

N. 0° 06' W., bet. secs. 13 and 14.

Over rolling and broken bench land.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

40.03 The 1/4 sec. cor. of secs. 13 and 14, monumented with a red sandstone, 16x10x4 ins., firmly set, projecting 10 ins. above ground, plainly mkd. 1/4 on the W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
1/4  
S 14 | S 13  
1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of corner.

---

N. 0° 15' E., beginning new measurement.

40.98 The cor. of secs. 11, 12, 13, and 14, monumented with a sandstone, 16x12x8 ins., firmly set, projecting 8 ins. above ground, plainly mkd. 4 notches on S and 1 notch on the E edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
S 11 | S 12  
S 14 | S 13  
1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of corner.

---

From the cor. of secs. 12 and 13 only, on the E. bdy. of the Tp., hereinbefore described.

N. 89° 35' W., bet. secs. 12 and 13.

Desc. along broken NW slope.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

- 12.00 Enter bottom of Brush Creek draw.
- 20.26 Point for the E 1/16 sec. cor. of secs. 12 and 13.  
Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
          S 12  
E 1/16    S 13  
          1985

From the corner point, a fence line, bearing E and W, bears N. 5 1/2 lks. dist., and a rebar, 1/2 in. diam., projecting 8 ins. above ground, bears W, 2 lks. dist.

- 23.00 Brush Creek, drains S.
- 32.50 Dirt road, bears NE and SW.
- 40.52 The 1/4 sec. cor. of secs. 12 and 13, monumented with a sandstone, 16x14x12 ins., firmly set, projecting 8 ins. above ground, plainly mkd. 1/4 on the N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
          S 12  
1/4       S 13  
          1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of corner.

\_\_\_\_\_

N. 89° 59' W., beginning new measurement.

- 20.01 Point for the W 1/16 sec. cor. of secs. 12 and 13.  
Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

T 4 S R 22 E  
S 12  
W 1/16 S 13  
1985

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of corner.

40.02 The cor. of secs. 11, 12, 13, and 14.

---

N. 0° 02' E., bet. secs. 11 and 12.

Over rolling bench land.

40.05 The 1/4 sec. cor. of secs. 11 and 12, monumented with a sandstone, 18x12x10 ins., firmly set, projecting 8 ins. above ground, mkd. 1/4 on the W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
1/4  
S 11 | S 12  
1986

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of corner.

---

N. 0° 01' E., beginning new measurement.

39.92 The cor. of secs. 1, 2, 11, and 12, monumented with a limestone, 20x8x4 ins., firmly set, projecting 10 ins. above ground, mkd. 5 notches on the S and 1 notch on the E edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 4 1/2 ft. base, to top of aluminum cap, mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

T	4	S	R	22	E
S	2		S	1	
S	11		S	12	
1986					

Deposit the mkd. stone alongside the aluminum post.

---

From the cor. of secs. 1 and 12 only, on the E. bdy. of the Tp.,  
hereinbefore described.

N. 89° 55' W., bet. secs. 1 and 12.

Along bottom of Brush Creek.

1.50 Dirt road, bears NW and SE.

19.98 Point for the E 1/16 sec. cor. of secs. 1 and 12.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in  
the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to  
top of aluminum cap, mkd.

T	4	S	R	22	E
E	1/16				
1986					

39.96 The 1/4 sec. cor. of secs. 1 and 12, monumented with a sandstone,  
22x14x5 ins., firmly set, projecting 10 ins. above ground, plainly  
mkd. 1/4 on the N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in  
the ground to bedrock, and in a mound of stone, 3 ft. base, to top  
of aluminum cap, mkd.

T	4	S	R	22	E
1/4					
1986					

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of  
corner.

---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

S. 89° 57' W., beginning new measurement.

40.44 The cor. of secs. 1, 2, 11, and 12.

---

N. 0° 05' W., bet. secs. 1 and 2.

Over rolling and broken bench land.

40.14 The 1/4 sec. cor. of secs. 1 and 2, monumented with a limestone, 18x8x6 ins., firmly set, projecting 8 ins. above ground, plainly mkd. 1/4 on the W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
1/4  
S 2 | S 1  
1986

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of corner.

---

N. 0° 06' W., beginning new measurement.

33.00 Paved road, bears NE and SW.

36.50 Paved road, bears NE and SW.

40.02 The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., hereinbefore described.

---

(Reestablishment of the Survey Executed by  
Ferron and Buettner in 1879)

---

From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap, mkd. as described in the official record of the 1949 dependent resurvey of a portion of the N. bdy., T. 5 S., R. 22 E.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

N. 0° 28' W., bet. secs. 34 and 35.

Over gentle rolling land.

40.53 Point for the 1/4 sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
1/4  
S 34 | S 35  
1985

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of corner.

81.06 The cor. of secs. 26, 27, 34, and 35, monumented with a limestone, 14x12x6 ins., firmly set, projecting 7 ins. above ground, mkd. 1 notch on the S, and 2 notches on the E edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
S 27 | S 26  
S 34 | S 35  
1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

---

(Reestablishment of the Survey Executed by  
Ferron and Buettner in 1879 and the Retracement Executed by  
Jessen and Harmston in 1906)

---

From the cor. of secs. 25, 26, 35, and 36.

S. 89° 24' W., bet. secs. 26 and 35.

Over gentle rolling bench land.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

- 23.00 Dirt road, bears NW and SE.
- 39.86 The 1/4 sec. cor. of secs. 26 and 35, monumented with a sandstone, 12x8x5 ins., firmly set, projecting 6 ins. above ground, plainly mkd. 1/4 on the N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
           S 26  
 1/4       S 35    
           1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of the corner.

From this cor., U.S.C. & G.S. triangulation station "JENSEN" bears N. 11° 29.1' E., 23.296 chs. dist.

---

S. 89° 17' W., beginning new measurement.

- 40.10 The cor. of secs. 26, 27, 34, and 35.

---

N. 0° 51' W., bet. secs. 26 and 27.

Over gentle rolling land.

- 40.33 Point for the 1/4 sec. cor. of secs. 26 and 27, at proportionate distance based on the irregular boundary method; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
           1/4  
       S 27 | S 26  
           1985

---

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

N. 0° 29' W., beginning new measurement.

34.00 Paved road, bears NW and SE.

40.22 Point for the cor. of secs. 22 and 27 only, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E
S 22
S 27   S 26
1985

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

N. 0° 28' W., along the E. bdy. of sec. 22.

Over gentle rolling land.

0.515 Point for the closing cor. of secs. 23 and 26, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E
S 22   S 23 C
S 26   S 26 C
1985

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, E of the corner.

40.48 The 1/4 sec. cor. of secs. 22 only, monumented with a limestone, 8x6x4 ins., firmly set, projecting 4 ins. above ground, mkd. 1/4 on the W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E
1/4
S 22
1985

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

---

N. 0° 39' W., beginning new measurement.

0.52 Point for the 1/4 sec. cor. of sec. 23 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
| 1/4  
| S 23  
1985

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, E of the corner.

40.28 The cor. of secs. 15 and 22 only, monumented with a Uintah County Marker, a 1/2 in. rebar with aluminum cap, 1 in. diam., projecting 6 ins. above ground. This point is accepted as the best available evidence of the true corner position.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
S 15 |  
S 22 | S 23  
1985

Bury the rebar with aluminum cap, alongside the aluminum pipe.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

---

(Reestablishment of the Survey Executed by  
Jessen and Harmston in 1906)

---

From the cor. of secs. 23, 24, 25, and 26.

S. 89° 04' W., bet. secs. 23 and 26.

Over rolling bench land.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

2.50 Dirt road, bears N and S.

20.195 Point for the E 1/16 sec. cor. of secs. 23 and 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
           S 23  
 E 1/16    S 26  
           1986

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of the corner.

40.39 Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
           S 23  
 1/4       S 26  
           1986

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of the corner.

80.60 The closing cor. of secs. 23 and 26.

---

(Reestablishment of the Survey Executed by  
Ferron and Buettner in 1879 and the Retracement Executed by  
Jessen and Harmston in 1906)

---

From the cor. of secs. 15 and 22 only.

N. 0° 50' W., along the E. bdy. of sec. 15.

Over gentle rolling land.

0.725 Point for the closing cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

T 4 S R 22 E  
S 15 | S 14 C  
      | S 23 C  
      1985

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, E of the corner.

- 40.37 The 1/4 sec. cor. of sec. 15 only, monumented with a sandstone, 16x12x4 ins., firmly set, projecting 8 ins. above ground, mkd. 1/4 on the W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
1/4 |  
S 15 |  
      1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

---

N. 0° 29' W., beginning new measurement.

- 0.93 Point for the 1/4 sec. cor. of sec. 14.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
      | 1/4  
      | S 14  
      1985

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

- 40.09 The cor. of secs. 10 and 15 only, monumented with a limestone, 14x8x5 ins., firmly set, projecting 10 ins. above ground, plainly mkd. 2 grooves on E face, and 4 notches on the S edges.

At the corner point

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
S 10 |  
S 15 | S 14  
1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

---

N. 0° 29' W., beginning new measurement, along the E. bdy. of sec. 10.

- 1.415 The NW cor. of sec. 14, monumented with a limestone, 12x10x6 ins., firmly set, projecting 8 ins. above ground, plainly mkd. CC and 2 notches on the E and 4 notches on the S edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
| S 14  
| 1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, NW of the corner.

---

(Reestablishment of the Survey Executed by  
Jessen and Harmston in 1906)

---

From the cor. of secs. 13, 14, 23, and 24.

S. 89° 55' W., bet. secs. 14 and 23.

Over rolling bench land.

- 40.70 The 1/4 sec. cor. of secs. 14 and 23, monumented with a limestone, 14x10x8 ins., firmly set, projecting 8 ins. above ground, mkd. 1/4 on the N face.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
S 14  
1/4 S 23  
1986

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of the corner.

---

S. 88° 54' W., beginning new measurement.

40.15 The closing cor. of secs. 14 and 23.

---

From the cor. of secs. 11, 12, 13, and 14.

S. 89° 53' W., bet. secs. 11 and 14.

Over rolling bench land.

40.01 The 1/4 sec. cor. of secs. 11 and 14, monumented with a sandstone, 16x14x12 ins., firmly set, projecting 8 ins. above ground, plainly mkd. 1/4 on the N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
S 11  
1/4 S 14  
1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of the corner.

---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

S. 89° 09' W., beginning new measurement.

- 40.55 The closing cor. of secs. 10 and 11, monumented with a sandstone, 12x10x7 ins., firmly set, projecting 7 ins. above ground, plainly mkd. CC and 2 grooves on N face, and 2 notches on E edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
C C  
S 10 | S 11  
S 14  
1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of the corner.

- 41.84 The NW cor. of sec. 14.

---

From the closing cor. of secs. 10 and 11.

N. 0° 01' W., bet. secs. 10 and 11.

Over rolling bench land.

- 37.00 Dirt road, bears NE and SW.

- 40.18 The 1/4 sec. cor. of secs. 10 and 11, monumented with a limestone, 12x10x6 ins., loosely set, and plainly mkd. 1/4 on the W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
1/4  
S 10 | S 11  
1985

Deposit the mkd. stone alongside the aluminum post.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

---

N. 0° 01' W., beginning new measurement.

- 8.80 Paved road, bears NE and SW.
- 40.18 The cor. of secs. 2, 3, 10, and 11, monumented with a limestone, 12x10x8 ins., firmly set, projecting 8 ins. above ground, plainly mkd. 5 grooves on the S and 2 grooves on the E faces.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E
S 3   S 2
S 10   S 11
1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

---

From the cor. of secs. 1, 2, 11, and 12.

S. 89° 46' W., bet. secs. 2 and 11.

Over rolling bench land.

- 40.18 The 1/4 sec. cor. of secs. 2 and 11, monumented with a sandstone, 18x8x4 ins., firmly set, projecting 8 ins. above ground, plainly mkd. 1/4 on the N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E
1/4 S 2
1/4 S 11
1986

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of the corner.

---

S. 89° 49' W., beginning new measurement.

- 21.60 Dirt road, bears NW and SE.  
27.80 Paved road, bears NE and SW.  
40.44 The cor. of secs. 2, 3, 10, and 11.

---

N. 0° 02' E., bet. secs. 2 and 3.

Over rolling bench land.

- 40.19 The 1/4 sec. cor. of secs. 2 and 3, monumented with a sandstone, 24x10x3 ins., firmly set, projecting 16 ins. above ground, and plainly mkd. 1/4 on the W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
1/4  
S 3 | S 2  
1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

---

N. 0° 11' E., beginning new measurement.

- 40.19 The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., hereinbefore described.

---

(Reestablishment of the Survey Executed by  
Ferron and Buetter in 1879)

---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap, mkd. as described in the official record of the 1949 dependent resurvey of a portion of the N. bd. of T. 5 S., R. 22 E.

N. 0° 50' W., bet. secs. 33 and 34.

Over gentle rolling land.

- 40.39 Point for the 1/4 sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.

This corner point is not monumented.

- 80.78 Point for the cor. of secs. 27, 28, 33, and 34, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E
S 28   S 27
S 33   S 34
1985

From the cor. of secs. 26, 27, 34, and 35.

S. 89° 04' W., bet. secs. 27 and 34.

Over gentle rolling land.

- 40.37 Point for the 1/4 sec. cor. of secs. 27 and 34, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E
1/4 <u>S 27</u>
S 34
1985

- 60.555 Point for the W 1/16 sec. cor. of secs. 27 and 34.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

T 4 S R 22 E  
 $\frac{S 27}{S 34}$   
 W 1/16 1985

80.74 The cor. of secs. 27, 28, 33, and 34.

---

N. 0° 55' W., bet. secs. 27 and 28.

Over gentle rolling land.

20.195 Point for the S 1/16 sec. cor. of secs. 27 and 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
 $\frac{S 1/16}{S 28 | S 27}$   
 1985

40.39 Point for the 1/4 sec. cor. of secs. 27 and 28, at proportionate dist.; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
 $\frac{1/4}{S 28 | S 27}$   
 1985

80.78 Point for the cor. of secs. 21, 22, 27 and 28, at proportionate dist.; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
 $\frac{S 21 | S 22}{S 28 | S 27}$   
 1985

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

From the cor. of secs. 22 and 27 only, on the W. bdy. of sec. 26.  
S. 89° 13' W., bet. secs. 22 and 27.

Over gentle rolling land.

- 6.00 Paved road, bears NW and SE.
- 40.53 Point for the 1/4 sec. cor. of secs. 22 and 27, at proportionate distance; there is no remaining evidence of the original corner.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

	T 4 S R 22 E
	S 22
1/4	S 27
	1985

- 81.06 The cor. of secs. 21, 22, 27, and 28.
- 

N. 0° 48' W., bet. secs. 21 and 22.

Over rolling land.

- 40.39 Point for the 1/4 sec. cor. of secs. 21 and 22, at proportionate distance; there is no remaining evidence of the original corner.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

	T 4 S R 22 E
	1/4
	S 21   S 22
	1985

- 43.00 Dirt road, bears NE and SW.
- 80.78 Point for the cor. of secs. 15, 16, 21, and 22, at proportionate distance; there is no remaining evidence of the original corner.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

	T 4 S R 22 E
	S 16   S 15
	S 21   S 22
	1985

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

From the cor. of secs. 15 and 22 only, on the W. bdy. of sec. 23.  
S. 89° 14' W., bet. secs. 15 and 22.

Over gentle rolling land.

- 6.50 Dirt road, bears N and curves SW.
- 40.69 Point for the 1/4 sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original corner.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
S 15  
1/4 S 22  
1985

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of the corner.

- 78.00 Paved road, bears N. 80° W. and S. 80° E.
- 81.38 The cor. of secs. 15, 16, 21, and 22.

N. 0° 14' E., bet. secs. 15 and 16.

Over gentle rolling land.

- 1.50 Paved road, bears N. 80° W. and S. 80° E.
- 40.39 Point for the 1/4 sec. cor. of secs. 15 and 16, at proportionate distance; there is no remaining evidence of the original corner.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

T 4 S R 22 E  
1/4  
S 16 | S 15  
1985

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

- 80.78 The cor. of secs. 15 and 16 only, on the S. bdy. of sec. 9, monumented with a quartzite stone, 14x12x6 ins., firmly set, projecting 8 ins. above ground, plainly mkd. 4 notches on the S and 3 notches on the E edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
S 9  
S 16 | S 15  
1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, S of the corner.

---

(Reestablishment of the Survey Executed by  
Ferron and Buettner in 1879 and the Retracement by  
Jessen and Harmston in 1906)

---

From the cor. of secs. 10 and 15 only.

S. 89° 22' W., along the N. bdy. of sec. 15.

Over gentle rolling land.

- 9.00 Paved road, bears NE and SW.
- 38.84 Point for the 1/4 sec. cor. of sec. 10 only.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

T 4 S R 22 E  
1/4 S 10  
1985

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of the corner.

- 40.25 Point for the 1/4 sec. cor. of sec. 15 only, at proportionate distance based on the irregular boundary method; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
1/4 S 15  
1985

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, S of the corner.

---

S. 89° 33' W., beginning new measurement.

- 38.72 The closing cor. of secs. 9 and 10, monumented with a sandstone, 20x10x8 ins., firmly set, projecting 10 ins. above ground, plainly mkd. CC on N face and 4 notches on the S edge.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
C C  
S 9 | S 10  
S 15  
1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of the corner.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

39.87 The cor. of secs. 15 and 16.

---

(Restablishment of the Survey Executed by  
Jessen and Harmston in 1900)

---

From the closing cor. of secs. 9 and 10.

N. 0° 14' W., bet. secs. 9 and 10.

Over gentle rolling land.

3.00 Paved road, bears NE and SW.

42.25 The 1/4 sec. cor. of secs. 9 and 10, monumented with a limestone,  
20x12x8 ins., firmly set, projecting 10 ins. above ground, plainly  
mkd. 1/4 on the W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in  
the ground, with aluminum cap mkd.

T 4 S R 22 E  
1/4  
S 9 | S 10  
1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the  
corner.

---

N. 0° 12' W., beginning new measurement.

40.23 The cor. of secs. 3, 4, 9, and 10, monumented with a sandstone,  
12x10x8 ins., firmly set, projecting 8 ins. above ground, mkd. 5  
notches on the S and 3 notches on the E edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in  
the ground, with aluminum cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

T 4 S R 22 E  
S 4 | S 3  
S 9 | S 10  
1985

Deposit the mkd. stone alongside the aluminum post.

Corner is set alongside fence corner post, with fences projecting  
N and W.

---

From the cor. of secs. 2, 3, 10, and 11.

N. 89° 57' W., bet. 3 and 10.

Over rolling land.

- 40.30 The 1/4 sec. cor. of secs. 3 and 10, monumented with a limestone,  
20x12x8 ins., firmly set, projecting 10 ins. above ground, plainly  
mkd. 1/4 on the N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in  
the ground, with aluminum cap mkd.

T 4 S R 22 E  
S 3  
1/4 S 10  
1986

Deposit the mkd. stone alongside the aluminum post.

---

S. 89° 53' W., beginning new measurement.

- 40.24 The cor. of secs. 3, 4, 9, and 10.
- 

N. 0° 15' W., bet. secs. 3 and 4.

Over rolling land.

- 40.18 The 1/4 sec. cor. of secs. 3 and 4, monumented with a limestone,  
10x8x3 ins., firmly set, projecting 6 ins. above ground, mkd. 1/4  
on the W face.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
1/4  
S 4 | S 3  
1986

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

---

N. 0° 10' E., beginning new measurement.

39.76 The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., hereinbefore described.

---

(Reestablishment of the Survey Executed by  
Ferron and Buettner in 1879)

---

From the cor. of secs. 27, 28, 33, and 34.

N. 89° 58' W., bet. secs. 28 and 33.

40.30 The 1/4 sec. cor. of secs. 28 and 33, monumented with a sandstone, 10x8x6 ins., firmly set, projecting 6 ins. above ground, mkd. 1/4 on N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
S 28  
1/4 S 33  
1985

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

Deposit the mkd. stone alongside the aluminum post.

From the cor. of secs. 28, 29, 32, and 33, marked by a rebar, 5/8 ins. diam., set in center of gravel road, flush with surface, and in line with fence lines extending N and S. This point was established by the Uintah County Surveyor, and is accepted as the best available evidence of the true corner position. No other improvements were made on this cor. point.

Road bears W and curves NE.

N. 0° 44' W., bet. secs. 28 and 29.

Over rolling land.

20.265 Point for the S 1/16 sec. cor. of secs. 28 and 29.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
S 1/16  
S 29 | S 28  
1985

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

40.53 The 1/4 sec. cor. of secs. 28 and 29, monumented with a quartzite stone, 10x8x4 ins., firmly set, projecting 5 ins. above ground, plainly mkd. 1/4 on the W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
1/4  
S 29 | S 28  
1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

Corner is set alongside fence corner post, with fences extending S and W.

---

N. 1° 43' W., beginning new measurement.

- 40.36 The cor. of secs. 20, 21, 28, and 29, monumented with a quartzite stone, 18x12x4 ins., firmly set, projecting 10 ins. above ground, mkd. 2 notches on the S and 4 notches on the E edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E
S 20   S 21
S 29   S 28
1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

---

From the cor. of secs. 21, 22, 27, and 28.

S. 89° 50' W., bet. secs. 21 and 28.

Over rolling land.

- 13.50 Dirt road, bears N and curves SE.

- 40.64 Point for the 1/4 sec. cor. of secs. 21 and 28, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E
1/4 S 21
S 28
1985

- 81.28 The cor. of secs. 20, 21, 28, and 29.
-

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

N. 0° 51' W., bet. secs. 20 and 21.

Over gentle rolling land.

- 5.50 Dirt road, bears NE and S. 10° W.
- 40.51 The 1/4 sec. cor. of secs. 20 and 21, monumented with a sandstone, 10x7x5 ins., firmly set, projecting 5 ins. above ground, mkd. 1/4 on the W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
1/4  
S 20 | S 21  
1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

---

N. 0° 55' W., beginning new measurement.

- 7.00 Dirt road, bears NE and SW.
- 40.52 The cor. of secs. 16, 17, 20, and 21, monumented with a sandstone, 14x12x6 ins., firmly set, projecting 8 ins. above ground, mkd. 3 notches on the S and 4 notches on the E edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
S 17 | S 16  
S 20 | S 21  
1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

From the cor. of secs. 15, 16, 21, and 22.

N. 89° 59' W., bet. secs. 16 and 21.

Over gentle rolling land.

40.69 Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
S 16  
1/4 S 21  
1985

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of the corner.

61.00 Dirt road, bears N and S.

71.00 Dirt road, bears NNE and SSW.

81.38 The cor. of secs. 16, 17, 20, and 21.

N. 0° 51' E., bet. secs. 16 and 17.

Over gentle rolling land.

4.50 Paved road, bears E and W.

36.00 Paved road, bears NE and SW.

39.95 Point for the 1/4 sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
1/4  
S 17 | S 16  
1986

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

79.90 The cor. of secs. 16 and 17 only, on the S. bdy. of sec. 8, monumented with a broken limestone, 6x5x4 ins., dimly mkd. 4 notches on one side. The broken limestone was alongside the fence corner post, and is accepted as the best available evidence of the true corner position.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
S 8  
-----  
S 17 | S 16  
1985

Deposit the broken limestone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, S of the corner.

(Reestablishment of the Survey Executed by  
Ferron and Buettner in 1879 and the Retracement by  
Jessen and Harmston in 1906)

From the cor. of secs. 15 and 16, on the S. bdy. of sec. 9.

S. 89° 21' W., along the N. bdy. of sec. 16.

Over gentle rolling land.

6.00 Paved road, bears NE and SW.

39.15 Point for the 1/4 sec. cor. of sec. 9 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
1/4 S 9  
-----  
1985

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of the corner.

40.08 Point for the 1/4 sec. cor. of sec. 16, at proportionate distance based on the irregular boundary method; there is no remaining evidence of the original corner.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E

1/4 S 16  
1985

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, S of the corner.

S. 89° 27' W., beginning new measurement.

- 39.37 The closing cor. of secs. 8 and 9, monumented with a sandstone, 8x6x6 ins., firmly set, projecting 6 ins. above ground, mkd. CC on N face, 4 notches on E and 2 notches on W edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
C C  
S 8 | S 9  
S 16  
1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of the corner.

- 40.44 The cor. of secs. 16 and 17.

Reestablishment of the Survey Executed by  
Jessen and Harmston in 1906)

From the closing cor. of secs. 8 and 9.

N. 0° 11' W., bet., secs. 8 and 9.

Over gentle rolling land.

- 43.12 The 1/4 sec. cor. of secs. 8 and 9, monumented with a limestone, 12x10x7 ins., firmly set, projecting 6 ins. above ground, mkd. 1/4 on the W face.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
1/4  
S 8 | S 9  
1986

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

---

N. 0° 06' W., beginning new measurement.

- 40.27 The cor. of secs. 4, 5, 8, and 9, monumented with a sandstone, 18x12x10 ins., firmly set, projecting 10 ins. above ground, mkd. 5 notches on the S and 4 notches on the E edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
S 5 | S 4  
S 8 | S 9  
1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

---

From the cor. of secs. 3, 4, 9, and 10.

N. 89° 59' W., bet. secs. 4 and 9.

Over rolling land.

- 40.24 Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

T 4 S R 22 E  
 $\frac{S 4}{S 9}$   
 1/4  
 1986

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of the corner.

Corner is located 1 lk. N of fence corner post, with fences bearing E and S.

80.48 The cor. of secs. 4, 5, 8, and 9.

---

N. 0° 06' W., bet. secs. 4 and 5.

Over rolling land.

39.95 The 1/4 sec. cor. of secs. 4 and 5, monumented with a sandstone, 12x10x6 ins., firmly set, projecting 6 ins. above ground, mkd. 1/4 on the W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
 $\frac{1/4}{S 5 | S 4}$   
 1986

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

---

N. 0° 04' E., beginning new measurement.

39.97 The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., hereinbefore described.

---

(Reestablishment of the Survey Executed by  
 Ferron and Buettner in 1879)

---

From the cor. of secs. 16, 17, 20, and 21.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

S. 89° 01' W., bet. secs. 17 and 20.

Over gentle rolling land.

- 39.88 The 1/4 sec. cor. of secs. 17 and 20, monumented with a Uintah County Survey marker, a rebar, 5/8 ins. diam., with aluminum cap, 1 in. diam., projecting 4 ins. above ground, mkd. 1/4 17 20. This marker is accepted as the best available evidence to the position of the original corner.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
          S 17  
1/4     S 20  
          1985

Deposit the Uintah County Survey marker alongside the aluminum post.

---

From the cor. of secs. 17, 18, 19, and 20, marked by a bolt, imbedded in pavement, in center line of E - W road, and in line with fence projecting S. This point was established by the Uintah County Surveyor, and is accepted as the best available evidence of the original corner position. No other improvements were made.

N. 0° 27' E., bet. secs. 17 and 18.

Over nearly level pasture land.

- 40.19 Point for the 1/4 sec. cor. of secs. 17 and 18, at proportionate distance; there is no remaining evidence of the original corner, not monumented.

- 60.285 Point for the N 1/16 sec. cor. of secs. 17 and 18.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
          N 1/16  
S 18 | S 17  
          1986

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

- 80.38 The cor. of secs. 17 and 18 only, monumented with a sandstone, 10x8x4 ins., firmly set alongside fence cor. post, projecting 6 ins. above ground, plainly mkd. 4 notches on the S and 5 notches on the E edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
S 7  
S 18 | S 17  
1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, S of the corner.

From the fence cor., fences projects S and W.

(Reestablishment of the Survey Executed by  
Ferron and Buettner in 1879 and the Retracement Executed by  
Jessen and Harmston in 1906)

From the cor. of secs. 16 and 17, on the S. bdy. of sec. 8.

S. 89° 13' W., along the N. bdy. of sec. 17.

Over gentle rolling land.

- 39.13 Point for the 1/4 sec. cor. of sec. 8 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
1/4 S 8  
1985

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of the corner.

- 40.11 The 1/4 sec. cor. of sec. 17 only, on the S. bdy. of sec. 8, monumented with a sandstone, 14x8x6 ins., firmly set, projecting 9 ins. above ground, plainly mkd. 1/4 on the S face.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E

1/4 S 17

1985

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, S of the corner.

S. 89° 30' W., beginning new measurement.

- 39.22 The closing cor. of secs. 7 and 8, monumented with a sandstone, 16x10x8 ins., firmly set, projecting 10 ins. above ground, plainly mkd. CC on the N face, 5 notches on the E and 1 notch on the W edge.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E

CC

S 7 | S 8

S 17

1986

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of the corner.

- 40.17 The cor. of secs. 17 and 18 only, on the S. bdy. of sec. 7.

S. 89° 09' W., along the N. bdy. of sec. 18.

Over rolling land.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

18.955 Point for the E 1/16 sec. cor. of sec. 7 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
E 1/16 S 7

1986

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of the corner.

38.86 Point for the 1/4 sec. cor. of sec. 7 only.

Set a spike, 6 ins. long, flush with surface of paved road, which bears E and W, from which

An aluminum post, 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 35° 26' E., 45.7 lks. dist., with aluminum cap, mkd. T4S R22E 1/4 S7 RM 1986 30.16 FT., and an arrow pointing to the cor.

An aluminum post, 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 90° 34' W., 37.2 lks. dist., with aluminum cap, mkd. T4S R22E 1/4 S7 RM 1986 24.52 FT., and an arrow pointing to the cor.

39.38 The 1/4 sec. cor. of sec. 18 only, on the S. bdy. of sec. 7, marked by a steel bolt, imbedded in pavement, in center line of road, bearing E and W. This point was established by the Uintah County Surveyor, and is accepted as the best available evidence of the original corner position. No other improvements were made.

---

S. 89° 14' W., beginning new measurement.

19.385 Point for the W 1/16 sec. cor. of sec. 7 only.

Set a spike, 2 ins. long, flush with surface of paved road, which bears E and W.

No other improvements were made.

42.61 The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., hereinbefore described.

---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

(Reestablishment of the Survey Executed by  
Jessen and Harmston in 1906)

---

From the closing cor. of secs. 7 and 8.

N. 0° 02' W., bet. secs. 7 and 8.

Over rolling land.

24.06 Point for the S 1/16 sec. cor. of secs. 7 and 8.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in  
the ground, with aluminum cap mkd.

T 4 S R 22 E  
S 1/16  
S 7 | S 8  
1986

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the  
corner.

44.19 The 1/4 sec. cor. of secs. 7 and 8, monumented with a limestone,  
12x10x8 ins., firmly set, projecting 6 ins. above ground, plainly  
mkd. 1/4 on the W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in  
the ground, with aluminum cap mkd.

T 4 S R 22 E  
1/4  
S 7 | S 8  
1986

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the  
corner.

---

N. 0° 03' E., beginning new measurement.

40.21 The cor. of secs. 5, 6, 7, and 8, monumented with a limestone,  
18x12x10 ins., firmly set, projecting 12 ins. above ground, mkd. 5  
notches on the S and E edges.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

At the corner point  
Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in  
the ground, with aluminum cap mkd.

T 4 S R 22 E
S 6   S 5
S 7   S 8
1986

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the  
corner.

---

From the cor. of secs. 4, 5, 8, and 9.

S. 89° 49' W., bet. secs. 5 and 8.

Over rolling land.

40.07 The 1/4 sec. cor. of secs. 5 and 8, monumented with a limestone,  
14x8x4 ins., firmly set, projecting 10 ins. above ground, mkd. 1/4  
on the N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in  
the ground, with aluminum cap mkd.

T 4 S R 22 E
1/4 S 5
S 8
1986

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of the  
corner.

---

N. 89° 40' W., beginning new measurement.

40.09 The cor. of secs. 5, 6, 7, and 8.

---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

S. 89° 52' W., bet. secs. 6 and 7.

Over rolling land.

- 40.05 The 1/4 sec. cor. of secs. 6 and 7, monumented with a quartzite stone, 12x9x7 ins., firmly set, projecting 7 ins. above ground, mkd. 1/4 on the N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
S 6  
1/4 S 7  
1986

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of the corner.

---

N. 89° 42' W., beginning new measurement

- 19.865 Point for the W 1/16 sec. cor. of secs. 6 and 7.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
S 6  
W 1/16 S 7  
1986

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of the corner.

- 43.40 The closing cor. of secs. 6 and 7, on the W. bdy. of the Tp., hereinbefore described.

---

From the cor. of secs. 5, 6, 7, and 8.

N. 0° 06' W., bet. secs. 5 and 6.

Over rolling land.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

- 40.21 The 1/4 sec. cor. of secs. 5 and 6, monumented with a sandstone, 14x10x4 ins., firmly set, projecting 10 ins. above ground, mkd. 1/4 on the W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
1/4  
S 6 | S 5  
1986

Deposit the mkd. stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

N. 0° 08' W., beginning new measurement.

- 39.59 The cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the Tp., hereinbefore described.

---

Survey of the Subdivisional Lines of Section 1,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 1 and 12.

N. 0° 17' W., on the N and S center line of sec. 1.

Over gentle rolling land.

- 40.08 Point for the center 1/4 sec. cor. of sec. 1, at intersection with the E and W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
C 1/4 S 1  
1986

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 f.. high, W of the corner.

Survey of the Subdivisional Lines of Section 1,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

- 80.17 The 1/4 sec. cor. of secs. 1 and 36, on the N. bdy. of the Tp.,  
hereinbefore described.

---

From the point for the 1/4 sec. cor. of secs. 1 and 6, on the E.  
bdy. of the Tp., hereinbefore described.

N. 89° 58' W., on the E and W center line of sec. 1.

Over rolling land.

- 2.00 Dirt road, bears N and SSW.  
20.05 Point for the C-E 1/16 sec. cor. of sec. 1.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in  
the ground, with aluminum cap mkd.

$$\begin{array}{c} \text{E } 1/16 \\ \text{C} \quad \frac{\text{S } 1}{1986} \quad \text{C} \end{array}$$

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of the  
corner.

- 40.10 The center 1/4 sec. cor. of sec. 1.  
80.40 The 1/4 sec. cor. of secs. 1 and 2.

---

From the C-E 1/16 sec. cor. of sec. 1.

N. 0° 11' W., on the N and S center line of the NE 1/4 of sec. 1.

Over gentle rolling land.

- 40.10 The E 1/16 sec. cor. of secs. 1 and 36, on the N. bdy. of the Tp.,  
hereinbefore described.

---

From the E 1/16 sec. cor. of secs. 1 and 12.

N. 0° 11' W., on the N and S center line of the SE 1/4 of sec. 1.

Over rolling land.

- 40.10 The C-E 1/16 sec. cor. of sec. 1.
-

Survey of the Subdivisional Lines of Section 7,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

Survey of the Subdivisional Lines of Section 7,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of sec. 7 only, on the N. bdy. of sec. 18.  
N. 0° 09' W., on the N and S center line of sec. 7.

Over cultivated land.

24.41 Point for the C-S 1/16 sec. cor. of sec. 7.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in  
the ground, with aluminum cap mkd.

C  
S 1/16 | S 7  
C  
1986

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the  
corner.

44.65 Point for the center 1/4 sec. cor. of sec. 7, at intersection with  
the E and W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in  
the ground, with aluminum cap mkd.

T 4 S R 22 E  
C 1/4 S 7  
1986

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the  
corner.

64.78 Point for the C-N 1/16 sec. cor. of sec. 7.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in  
the ground, with aluminum cap mkd.

C  
N 1/16 | S 7  
C  
1986

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the  
corner.

Survey of the Subdivisional Lines of Section 7,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

84.91 The 1/4 sec. cor. of secs. 6 and 7.

---

From the 1/4 sec. cor. of secs. 7 and 8.

S. 89° 49' W., on the E and W center line of sec. 7.

Over rolling land.

19.95 Point for the C-E 1/16 sec. cor. of sec. 7.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

$$\begin{array}{c} \text{E } 1/16 \\ \hline \text{C } \quad \text{S } 7 \quad \text{C} \\ 1986 \end{array}$$

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of the corner.

39.90 The center 1/4 sec. cor. of sec. 7.

59.88 Point for the C-W 1/16 sec. cor. of sec. 7.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

$$\begin{array}{c} \text{W } 1/16 \\ \hline \text{C } \quad \text{S } 7 \quad \text{C} \\ 1986 \end{array}$$

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of the corner.

83.38 The 1/4 sec cor. of sec. 7 only, on the W. bdy. of the Tp., hereinbefore described.

---

From the E 1/16 sec. cor. of sec. 7 only, on the N. bdy. of sec. 18.

N. 0° 06' W., on the N and S center line of the SE 1/4 of sec. 7.

Over rolling land.

24.235 Point for the SE 1/16 sec. cor. of sec. 7, at intersection with the E and W center line of the SE 1/4 of sec. 7.

Survey of the Subdivisional Lines of Section 7,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

SE 1/16 S 7  
1986

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

44.42 The C-E 1/16 sec. cor. of sec. 7.

---

From the S 1/16 sec. cor. of secs. 7 and 8.

S. 89° 39' W., on the E and W center line of the SE 1/4 of sec. 7.  
Over rolling land.

19.93 The SE 1/16 sec. cor. of sec. 7.

39.86 The C-S 1/16 sec. cor. of sec. 7.

---

From the W 1/16 sec. cor. of sec. 7 only, on the N. bdy. of sec. 18.

N. 0° 15' W., on the N and S center line of the SW 1/4 of sec. 7.  
Over cultivated land.

24.575 Point for the SW 1/16 sec. cor. of sec. 7, at intersection with the E and W center line of the SW 1/4 of sec. 7.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

SW 1/16 S 7  
1986

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

44.85 The C-W 1/16 sec. cor. of sec. 7.

---

From the C-S 1/16 sec. cor. of sec. 7.

S. 89° 42' W., on the E and W center line of the SW 1/4 of sec. 7.

Survey of the Subdivisional Lines of Section 7,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

Over rolling land.

- 19.945 The SW 1/16 sec. cor. of sec. 7.  
43.35 The point for the S 1/16 sec. cor. of sec. 7 only, on the W. bdy. of the Tp., hereinbefore described.

From the C-W 1/16 sec. cor. of sec. 7.

NORTH, on the N and S center line of the NW 1/4 of sec. 7.

Over rolling land.

- 20.215 Point for the NW 1/16 sec. cor. of sec. 7, at intersection with the E and W center line of the NW 1/4 of sec. 7.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

NW 1/16  
S 7  
1986

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

Corner is located 2 lks. W of old N and S fence line.

- 40.43 The W 1/16 sec. cor. of secs. 6 and 7.

From the C-N 1/16 sec. cor. of sec. 7.

N. 89° 57' W., on the E and W center line of the NW 1/4 of sec. 7.

Over rolling land.

- 19.92 The NW 1/16 sec. cor. of sec. 7.  
43.40 The N 1/16 sec. cor. of sec. 7 only, on the W. bdy. of the Tp., hereinbefore described.

Survey of the Subdivisional Lines of Section 12,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

Survey of the Subdivisional Lines of Section 12,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 12 and 13.

N. 0° 21' E., on the N and S center line of sec. 12.

Over rolling land.

- 39.95 Point for the center 1/4 sec. cor. of sec. 12, at intersection with the E and W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
C 1/4 S 12  
1986

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

- 80.02 The 1/4 sec. cor. of secs. 1 and 12.
- 

From the 1/4 sec. cor. of sec. 12, on the E. bdy. of the Tp., hereinbefore described.

N. 89° 50' W., on the E and W center line of sec. 12.

Over rolling land.

- 18.00 Brush Creek, drains SW.

- 20.00 Center of dirt road, bears NE and SW.

- 20.11 Point for the C-E 1/16 sec. cor. of sec. 12, falls near W edge of road and is unsafe to monument.

From this point

An aluminum pipe, 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 0° 07' E., 50 lks. dist., with aluminum cap mkd. T4S R22E C-E 1/16 S12 RM 33 ft. 1986, and an arrow pointing to the true cor. point.

Survey of the Subdivisional Lines of Section 12,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

An aluminum pipe, 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 89° 50' W., 50 lks. dist., with aluminum cap mkd. T4S R22E C-E 1/16 S12 RM 33 ft. 1986, and an arrow pointing to the true cor. point.

40.22 The center 1/4 sec. cor. of sec. 12.

80.46 The 1/4 sec. cor. of secs. 11 and 12.

---

From the C-E 1/16 sec. cor. of sec. 12.

N. 0° 08' E., on the N and S center line of the NE 1/4 of sec. 12.

Over rolling land.

40.10 The E 1/16 sec. cor. of secs. 1 and 12.

---

From the E 1/16 sec. cor. of secs. 12 and 13.

N. 0° 08' E., on the N and S center line of the SE 1/4 of sec. 12.

Over rolling land.

39.50 Dirt road, bears NE and SW.

40.04 The C-E 1/16 sec. cor. of sec. 12.

---

Survey of the Subdivisional Lines of Section 13,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 13 and 24.

N. 0° 24' W., on the N and S center line of sec. 13.

Over rolling land.

20.03 Point for the C-S 1/16 sec. cor. of sec. 13.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

Survey of the Subdivisional Lines of Section 13,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

C  
S 1/16 | S 13  
C  
1986

- 40.06 Point for the center 1/4 sec. cor. of sec. 13, at intersection with the E and W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
C 1/4 S 13  
1986

- 59.20 Point selected for the witness cor. to the C-N 1/16 sec. cor. of sec. 13.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

W C  
C  
N 1/16 ↑ S 13  
C  
1986

Raise a mound of stone, 2 1/2 ft. base 1 1/2 ft. high, W of the corner.

- 60.45 True point for the C-N 1/16 sec. cor. of sec. 13, falls in Brush Creek and cannot be monumented. Brush Creek, drains SW.

- 67.35 Dirt road, bears NE and SW.

- 80.84 The 1/4 sec. cor. of secs. 12 and 13.

From the 1/4 sec. cor. of sec. 13 only, on the E. bdy. of the Tp., hereinbefore described.

S. 89° 44' W., on the E and W center line of sec. 13.

Over rolling land.

- 20.11 Point for the C-E 1/16 sec. cor. of sec. 13.

Survey of the Subdivisional Lines of Section 13,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., over cross (X) chisled in solid sandstone, in a mound of stone, 5 ft. base to top, with aluminum cap mkd.

$$\begin{array}{c} \text{E } 1/16 \\ \text{C} \frac{\text{S } 13}{\text{C}} \\ 1986 \end{array}$$

- 40.22 The center 1/4 sec. cor. of sec. 13.  
55.50 Brush Creek, drains SSW.  
60.47 Point for the C-W 1/16 sec. cor. of sec. 13.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

$$\begin{array}{c} \text{W } 1/16 \\ \text{C} \frac{\text{S } 13}{\text{C}} \\ 1986 \end{array}$$

- 63.50 Dirt road, bears N and S.  
80.72 The 1/4 sec. cor. of secs. 13 and 14.

From the C-E 1/16 sec. cor. of sec. 13.

N. 0° 11' W., on the N and S center line of the NE 1/4 of sec. 13.

Over rolling land.

- 20.265 Point for the NE 1/16 sec. cor. of sec. 13, at intersection with the E and W center line of the NE 1/4 of sec. 13.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 5 ft. base, to top of aluminum cap, mkd.

$$\begin{array}{c} \text{NE } 1/16 \text{ S } 13 \\ 1986 \end{array}$$

- 40.53 The E 1/16 sec. cor. of secs. 12 and 13.

From the N 1/16 sec. cor. of sec. 13 only, on the E. bdy. of the Tp., hereinbefore described.

Survey of the Subdivisional Lines of Section 13,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

N.  $89^{\circ} 55'$  W., on the E and W center line of the NE 1/4 of sec. 13.

Over rolling land.

20.185 The NE 1/16 sec. cor. of sec. 13.

40.37 True point for the C-N 1/16 sec. cor. of sec. 13.

---

From the E 1/16 sec. cor. of secs. 13 and 24.

N.  $0^{\circ} 12'$  W., on the N and S center line of the SE 1/4.

Over rolling land.

20.01 Point for the SE 1/16 sec. cor. of sec. 13, at intersection with the E and W center line of the SE 1/4 of sec. 13.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 5 ft. base, to top of aluminum cap, mkd.

SE 1/16 S 13  
1986

40.02 The C-E 1/16 sec. cor. of sec. 13.

---

From the S 1/16 sec. cor. of sec. 13 only, on the E. bdy. of the Tp., hereinbefore described.

S.  $89^{\circ} 40'$  W., on the E and W center line of the SE 1/4 of sec. 13.

Over rolling land.

20.04 The SE 1/16 sec. cor. of sec. 13.

40.08 The C-S 1/16 sec. cor. of sec. 13.

---

From the W 1/16 sec. cor. of secs. 13 and 24.

N.  $0^{\circ} 15'$  W., on the N and S center line of the SW 1/4 of sec. 13.

Over rolling land.

9.00 Dirt road, bears NE and SW.

Survey of the Subdivisional Lines of Section 13,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

- 19.00 Dirt road, bears NW and SE.  
40.04 The C-W 1/16 sec. cor. of sec. 13.

---

From the C-W 1/16 sec. cor. of sec. 13.

N. 0° 05' W., on the N and S center line of the NW 1/4 of sec. 13.

Over rolling land.

- 11.00 Dirt road, bears NE and SW.  
40.88 The W 1/16 sec. cor. of secs. 12 and 13.

---

Survey of the Subdivisional lines of Section 17,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 17 and 20.

N. 0° 41' E., on the N and S center line of sec. 17.

Over gentle rolling land.

- 3.50 Paved road, bears E and W.  
8.50 Paved road, bears NE and SW.  
40.06 Point for the center 1/4 sec. cor. of sec. 17, at intersection  
with the E and W center line.  
Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in  
the ground, with aluminum cap mkd.

T 4 S R 22 E  
C 1/4 S 17  
1986

- 60.055 Point for the C-N 1/16 sec. cor. of sec. 17.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in  
the ground, with aluminum cap mkd.

C  
N 1/16 | S 17  
C  
1986

Survey of the Subdivisional Lines of Section 17,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

80.05 The 1/4 sec. cor. of sec. 17 only, on the S. bdy. of sec. 8.

---

From the 1/4 sec. cor. of secs. 16 and 17.

S.  $89^{\circ} 12'$  W., on the E and W center line of sec. 17.

Over gentle rolling land.

39.99 The center 1/4 sec. cor. of sec. 17.

80.01 Point for the 1/4 sec. cor. of secs. 17 and 18.

---

From the C-N 1/16 sec. cor. of sec. 17.

S.  $89^{\circ} 21'$  W., on the E and W center line of the NW 1/4 of sec. 17.

Over rolling land.

40.10 The N 1/16 sec. cor. of secs. 17 and 18.

---

Survey of the Subdivisional Lines of Section 24,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 24 and 25.

N.  $0^{\circ} 02'$  E., on the N and S center line of sec. 24.

Over rolling land.

20.045 Point for the C-S 1/16 sec. cor. of sec. 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

C  
S 1/16 | S 24  
C  
1986

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

40.09 Point for the center 1/4 sec. cor. of sec. 24, at intersection with the E and W center line.

Survey of the Subdivisional Lines of Section 24,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
C 1/4 S 24  
1986

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

80.15 The 1/4 sec. cor. of secs. 13 and 24.

---

From the 1/4 sec. cor. of sec. 24 only, on the E. bdy. of the Tp., hereinbefore described.

S. 89° 28' W., on the E and W center line of sec. 24.

Over rolling land.

40.06 The center 1/4 sec. cor. of sec. 24.

54.00 Brush Creek, drains S.

60.240 Point for the C-W 1/16 sec. cor. of sec. 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

W 1/16  
C  $\frac{\quad}{S 24}$  C  
1986

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of the corner.

65.285 Point for the C-E-W-W 1/256 sec. cor. of sec. 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

C-E-W-W 1/256  
S 24  
1986

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of the corner.

Survey of the Subdivisional Lines of Section 24,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

80.42 The 1/4 sec. cor. of secs. 23 and 24.

---

From the W 1/16 sec. cor. of secs. 24 and 25.

N. 0° 07' W., on the N and S center line of the SW 1/4.

Over rolling land.

20.07 Point for the SW 1/16 sec. cor. of sec. 24, at intersection with the E and W center line of the SW 1/4 of sec. 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

SW 1/16 S 24  
1986

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

30.105 Point for the C-N-SW 1/64 sec. cor. of sec. 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

C-N-SW 1/64  
S 24  
1986

40.14 The C-W 1/16 sec. cor. of sec. 24.

---

From the C-S 1/16 sec. cor. of sec. 24.

S. 89° 23' W., on the E and W center line of the SW 1/4 of sec. 24.

Over rolling land.

14.50 Brush Creek, drains SE.

20.135 The SW 1/16 sec. cor. of sec. 24.

40.27 The S 1/16 sec. cor. of secs. 23 and 24.

---

From the C-N-SW 1/64 sec. cor. of sec. 24.

Survey of the Subdivisional Lines of Section 24,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

S. 89° 25' W., on the E and W center line of the NW 1/4, SW 1/4 of sec. 24.

Over rolling land.

5.04 Point for the C-E-NW-SW 1/256 sec. cor. of sec. 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

C-E-NW-SW 1/256  
S 24  
1986

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of the corner.

20.16 The N-S 1/64 sec. cor. of secs. 23 and 24.

---

From the C-E-NW-SW 1/256 sec. cor. of sec. 24.

N. 0° 09' W., on the N and S center line of the NE 1/4 of the NW 1/4 of the SW 1/4 of sec. 24.

Over rolling land.

10.04 The C-E-W-W 1/256 sec. cor. of sec. 24.

---

From the C-W 1/16 sec. cor. of sec. 24.

N. 0° 13' W., on the N and S center line of the NW 1/4 of sec. 24.

Over rolling land.

40.16 The W 1/16 sec. cor. of secs. 13 and 24.

---

Survey of the Subdivisional Lines of Section 25,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 25 and 36.

N. 0° 05' E., on the N and S center line of sec. 25.

Over rolling land.

Survey of the Subdivisional Lines of Section 25,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

11.00 Brush Creek, drains SE.

20.40 Point for the C-S 1/16 sec. cor. for the E side of sec. 25.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

C  
| S 1/16  
| S 25  
C  
1986

20.705 Point for the C-S 1/16 sec. cor. for the W side of sec. 25.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

C  
S 1/16 |  
S 25 |  
C  
1986

40.80 Point for the center 1/4 sec. cor. of sec. 25, at the intersection with the E and W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap mkd.

T 4 S R 22 E  
C 1/4 S 25  
1986

81.24 The 1/4 sec. cor. of secs. 24 and 25.

---

From the 1/4 sec. cor. of sec. 25 only, on the E. bdy. of the Tp., hereinbefore described.

S. 89° 36' W., on the E and W center line of sec. 25.

Over rolling land.

20.185 Point for the C-E 1/16 sec. cor. of sec. 25.

Set an iron post, 1 in. diam., 18 ins. long, in drill hole, 10 ins. deep, with brass cap mkd.

Survey of the Subdivisional Lines of Section 25,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

$$\begin{array}{c} \text{E } 1/16 \\ \hline \text{C } \text{S } 25 \text{ C} \\ 1986 \end{array}$$

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of the corner.

40.37 The center 1/4 sec. cor. of sec. 25.

50.50 Brush Creek, drains SW.

60.41 Point for the C-W 1/16 sec. cor. of sec. 25.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

$$\begin{array}{c} \text{W } 1/16 \\ \hline \text{C } \text{S } 25 \text{ C} \\ 1986 \end{array}$$

Corner is set alongside fence corner post, with fences bearing S and E.

80.45 The 1/4 sec. cor. of secs. 25 and 26.

---

From the true point for the E 1/16 sec. cor. of secs. 25 and 36.

N. 0° 07' E., on the N and S center line of the SE 1/4 of sec. 25.

Over rolling land.

20.37 Point for the SE 1/16 sec. cor. of sec. 25, at intersection with the E and W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

$$\begin{array}{c} \text{SE } 1/16 \text{ S } 25 \\ 1986 \end{array}$$

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

40.74 The C-E 1/16 sec. cor. of sec. 25.

---

From the S 1/16 sec. cor. of sec. 25 only, on the E. bdy. of the Tp., hereinbefore described.

Survey of the Subdivisional Lines of Section 25,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

S.  $89^{\circ} 31'$  W., on the E and W center line of the SE  $1/4$  of sec. 25.  
Over rolling land.

20.175 The SE  $1/16$  sec. cor. of sec. 25.

40.35 The C-S  $1/16$  sec. cor. of sec. 25, for the E side only.

---

From the C-S  $1/16$  sec. cor. of sec. 25, W side only.

S.  $89^{\circ} 43'$  W., on the E and W center line of the SW  $1/4$  of sec. 25.  
Over rolling land.

13.00 Brush Creek drains SE.

39.92 The S  $1/16$  sec. cor. of secs. 25 and 26.

---

From the C-W  $1/16$  sec. cor. of sec. 25.

N.  $0^{\circ} 01'$  E., on the N and S center line of the NW  $1/4$  of sec. 25.  
Over rolling land.

40.33 The W  $1/16$  sec. cor. of secs. 24 and 25.

---

Survey of the Subdivisional Lines of Section 26,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

---

From the  $1/4$  sec. cor. of secs. 26 and 35.

N.  $0^{\circ} 35'$  W., on the N and S center line of sec. 26.  
Over rolling land.

25.00 Dirt road, bears NW and SE.

40.74 Point for the center  $1/4$  sec. cor. of sec. 26, at intersection  
with the E and W center line.

Set an aluminum post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in  
the ground, with aluminum cap mkd.

Survey of the Subdivisional Lines of Section 26,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

T 4 S R 22 E  
C 1/4 S 26  
1986

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

- 54.00 Paved road, bears WNW and ESE.  
81.22 The 1/4 sec. cor. of secs. 23 and 26.

---

From the 1/4 sec. cor. of secs. 25 and 26.

S. 88° 42' W., on the E and W center line of sec. 26.

Over rolling land.

- 20.015 Point for the C-E 1/16 sec. cor. of sec. 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
E 1/16  
C S 26 C  
1986

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of the corner.

- 27.50 Paved road, bears N and SE.  
40.03 The center 1/4 sec. cor. of sec. 26.  
57.00 Paved road, bears NW and SE.  
80.32 The 1/4 sec. cor. of sec. 26 and 27.

---

From the C-E 1/16 sec. cor. of sec. 26.

N. 0° 20' W., on the N and S center line of the NE 1/4.

Over rolling land.

- 10.00 Dirt road, bears W and NE.  
40.35 The E 1/16 sec. cor. of secs. 23 and 26.
-

Survey of the Subdivisional Lines of Section 28,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

Survey of the Subdivisional Lines of Section 28,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 28 and 33.

N. 1° 10' W., on the N and S center line of sec. 28.

Over gentle rolling land.

20.135 Point for the C-S 1/16 sec. cor. of sec. 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

C  
S 1/16 | S 28  
C  
1985

25.00 Dirt road, bears WSW and ENE.

40.27 Point for the center 1/4 sec. cor. of sec. 28, at intersection with the E and W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 4 S R 22 E  
C 1/4 S 28  
1985

80.64 The 1/4 sec. cor. of secs. 21 and 28.

---

From the 1/4 sec. cor. of secs. 27 and 28.

S. 89° 53' W., on the E and W center line of sec. 28.

Over gentle rolling land.

15.00 Dirt road, bears NE and SW.

40.47 The center 1/4 sec. cor. of sec. 28.

80.71 The 1/4 sec. cor. of secs. 28 and 29.

---

Survey of the Subdivisional Lines of Section 28,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

From the S 1/16 sec. cor. of secs. 27 and 28.

S. 89° 58' W., on the E and W center line of the SE 1/4 of sec. 28.  
Over rolling land.

40.38 The C-S 1/16 sec. cor. of sec. 28.

---

S. 89° 43' W., on the E and W center line of the SW 1/4 of sec. 28.

Over gentle rolling land.

20.00 Dirt road, bear NE and SW.

40.39 The S 1/16 sec. cor. of secs. 28 and 29.

---

Survey of the Subdivisional Lines of Section 34,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 3 and 34, of the S. bdy. of the  
Tp., monumented with an iron post, 1 in. diam., firmly set,  
projecting 8 ins. above ground, with brass cap, mkd. as described  
in the official record of the 1949 dependent resurvey of a portion  
of the N. bdy. of T. 5 S., R. 22 E.

N. 0° 39' W., on the N and S center line of sec. 34.

Over gentle rolling land.

40.46 Point for the center 1/4 sec. cor. of sec. 34, at intersection  
with the E and W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in  
the ground, with aluminum cap mkd.

T 4 S R 22 E  
C 1/4 S 34  
1985

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the  
corner.

80.92 The 1/4 sec. cor. of secs. 27 and 34.

---

From the 1/4 sec. cor. of secs. 34 and 35.

Survey of the Subdivisional Lines of Section 34,  
T. 4 S., R. 22 E., Salt Lake Meridian, Utah

S. 89° 10' W., on the E and W center line of sec. 34.

Over gentle rolling land.

40.24 The center 1/4 sec. cor. of sec. 34.

60.36 Point for the C-W 1/16 sec. cor. of sec. 34.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

$$\begin{array}{c} \text{W } 1/16 \\ \hline \text{C } \text{S } 34 \text{ C} \\ 1985 \end{array}$$

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of the corner.

80.48 Point for the 1/4 sec. cor. of secs. 33 and 34.

From the C-W 1/16 sec. cor. of sec. 34.

N. 0° 44' W., on the N and S center line of the NW 1/4.

Over gentle rolling land.

40.42 The W 1/16 sec. cor. of secs. 27 and 34.

#### GENERAL DESCRIPTION

Township 4 South, Range 22 East, is situated about 2 miles east of Vernal, Utah. The elevation varies from 5200 to 5500 feet above sea level. The soil is mostly loam and clay loam over most of the township.

Brush Creek flows in a southerly direction through the eastern portion of the township. Most of the drainage is in a southerly direction.

There are some ranches scattered along Brush Creek, with several improved roads and numerous secondary roads through most of the township.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

## FIELD ASSISTANTS

Kenneth Chynoweth	Survey Aid
Larry V. Judd	Survey Aid
Douglas Morland	Survey Aid

## CERTIFICATE OF SURVEY

I, Jerry L. Thomas, Cadastral Surveyor, HEREBY

CERTIFY upon honor that, in pursuance of special instructions date of

the 11th day of September, 1985, I have dependently resurveyed the north boundary, a portion of the east boundary (Ashley Guide Meridian), a portion of the west boundary, a portion of the subdivisional lines and surveyed the subdivision of sections 1, 7, 12, 13, 17, 24, 25, 26, 28, and 34 in T. 4 S., R. 22 E.,

of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by me, and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

November 14, 1988  
(Date)

Jerry L. Thomas  
(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The foregoing field notes of the dependent resurvey of the north boundary, a portion of the east boundary (Ashley Guide Meridian), a portion of the west boundary, a portion of the subdivisional lines and the survey of the subdivision of sections 1, 7, 12, 13, 17, 24, 25, 26, 28, and 34 in T. 4 S., R. 22 E

executed by Jerry L. Thomas, Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

January 3, 1989  
(Date)

Glen B. Hatch  
(Chief, Cadastral Surveyor for Utah)

