

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T6S R20E
E 1/16 $\frac{S33}{S4}$
T7S
1988

- 40.29** The 1/4 sec. cor. of secs. 4 and 33, determined by fence cor., with fences projecting N, S and W, and is accepted as the best available evidence of the position of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T6S R20E
1/4 $\frac{S33}{S4}$
T7S
1988

S. 89° 29' W., beginning new measurement.

Over cultivated land, along fence line.

- 40.45** The cor. of secs. 4, 5, 32, and 33, mkd. by a cement nail in center of State Highway No. 88, which bears N and S. This point was established by Uintah Engineering, and is accepted as the best available evidence of the position of the original corner.

from this point

A stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 59° 36' E., 57 lks. dist., with brass cap mkd. T6S R20E S33 RM 1988 and an arrow pointing to the cor.

A stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 39° 08' W., 77 lks. dist., with brass cap mkd. T6S R20E S32 RM 1988 and an arrow pointing to the cor.

S. 89° 49' W., bet. secs. 5 and 32.

Over rolling land.

- 40.45** The 1/4 sec. cor. of secs. 5 and 32, mkd. by a galvanized pipe, 1 in. diam., projecting 12 ins. above ground. This point was established by private surveyors and is accepted as the best available evidence of the position of the original corner.

**DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T6S R20E
1/4 $\frac{S32}{S5}$
T7S
1988

Cor. is located in N and S fence line.

S. 89° 20' W., beginning new measurement.

Leave cultivated land.

- 20.16** The W 1/16 sec. cor. of secs. 5 and 32, monumented with a sandstone, 24x14x4 ins., set and dimly mkd. 1/16 on N face.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T6S R20E
W 1/16 $\frac{S32}{S5}$
T7S
1988

Deposit the mkd. stone alongside the stainless steel pipe.

S. 89° 38' W., beginning new measurement.

- 2.00** Dirt road, bears N and S.

- 9.50** Dirt road, bears NE and SW.

- 20.18** The cor. of secs. 5, 6, 31, and 32, monumented with a sandstone, 16x10x5 ins., firmly set, projecting 10 ins. above ground, mkd. 5 notches on E and 1 notch on W edges.

At the corner point

**DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T6S R20E	
<u>S31</u>	<u>S32</u>
S6	S5
T7S	
1988	

Deposit the mkd. stone alongside the stainless steel pipe.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

N. 88° 53' W., bet. secs. 6 and 31.

Over rolling and broken land.

20.175 Point for the E 1/16 sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T6S R20E	
E 1/16	<u>S31</u>
	S6
	T7S
	1988

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.

40.35 The 1/4 sec. cor. of secs. 6 and 31, monumented with a sandstone, 18x10x4 ins., firmly set, projecting 10 ins. above ground, dimly mkd. 1/4 on the N face.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T6S R20E	
1/4	<u>S31</u>
	S6
	T7S
	1988

Deposit the mkd. stone alongside the stainless steel pipe.

**DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

N. $89^{\circ} 03'$ W., beginning new measurement.

- 37.81** The cor. of Tps. 6 and 7 S., Rs. 19 and 20 E., monumented with an iron pipe, 3 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. as described in the official record of the 1925 resurvey.

Dependent Resurvey of the West Boundary,
T. 7 S., R. 20 E., Salt Lake Meridian, Utah

S. $0^{\circ} 37'$ E., bet. secs. 1 and 6, on the W. bdy. of the Tp.

Over cultivated land.

- 42.04** The 1/4 sec. cor. of secs. 1 and 6, monumented with a rebar and brass cap, 1 in. diam., firmly set, projecting 4 ins. above ground, mkd. 1/4 S1 S6. This point was established by the Uintah County Surveyor and is accepted as the best available evidence of the position of the original corner.

Cor. is located along N edge and E edge of road intersection, with roads projecting N, S and E.

S. $0^{\circ} 08'$ E., beginning new measurement.

Along paved road.

- 40.67** The cor. of secs. 1, 6, 7, and 12, mkd. by a cement nail imbedded in paved road, which bears N and S. This point was established by the Uintah Engineering and is accepted as the best available evidence of the position of the original corner.

from which

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. $88^{\circ} 34'$ E., 47 lks. dist., with brass cap mkd. T7S R20E S7 RM 1988, and an arrow pointing to the cor.

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. $88^{\circ} 34'$ W., 48 lks. dist., with brass cap mkd. T7S R19E S1 RM 1988, and an arrow pointing to the cor.

S. $0^{\circ} 49'$ E., bet. secs. 7 and 12.

Along paved road.

**DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

40.39 The 1/4 sec. cor. of secs. 7 and 12, mkd. by a cement nail imbedded in paved road, State Highway No. 88, which bears E and W. This position was established by the Uintah Engineering and is accepted as the best available evidence of the position of the original corner.

from which

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 45° 57' E., 72 lks. dist., with brass cap mkd. T7S R20E S7 RM 1988, and an arrow pointing to the cor.

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 48° 26' E., 74 lks. dist., with brass cap mkd. T7S R20E S7 RM 1988, and an arrow pointing to the cor.

S. 0° 32' E., beginning new measurement.

Along paved road.

40.17 The cor. of secs. 7, 12, 13, and 18, mkd. by a cement nail imbedded in paved road, State Highway No. 88, which bears N and S. This position was established by Uintah Engineering and is accepted as the best available evidence of the position of the original corner.

from which

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 42° 06' E., 74 lks. dist., with brass cap mkd. T7S R20E S7 RM 1988, and an arrow pointing to the cor.

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 48° 20' W., 69 lks. dist., with brass cap mkd. T7S R19E S12 RM 1988, and an arrow pointing to the cor.

S. 0° 32' E., bet. secs. 13 and 18.

Along paved road.

40.38 The 1/4 sec. cor. of secs. 13 and 18, determined latitudinally by projection of E and W fence lines, and longitudinally by centerline of paved road, which bears N and S.

At the corner point

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a spike, 8 ins. long, flush with surface of road.

from which

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. $73^{\circ} 27'$ E., 51 lks. dist., with brass cap mkd. T7S R20E 1/4 S18 RM 1988, and an arrow pointing to the cor.

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. $73^{\circ} 46'$ W., 52 1/2 lks. dist., with brass cap mkd. T7S R19E 1/4 S13 RM 1988, and an arrow pointing to the cor.

S. $0^{\circ} 28'$ E., beginning new measurement.

Along paved road.

40.33 The cor. of secs. 13, 18, 19, and 24, determined by center of 3-way intersection of roads. This point is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a spike, 8 ins. long, flush with surface of road.

from which

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. $48^{\circ} 35'$ E., 62 lks. dist., with brass cap mkd. T7S R20E S19 RM 1988, and an arrow pointing to the cor.

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. $47^{\circ} 38'$ W., 62 1/2 lks. dist., with brass cap mkd. T7S R19E S24 RM 1988, and an arrow pointing to the cor.

S. $0^{\circ} 29'$ E., bet. secs. 19 and 24.

Along dirt road.

40.11 The 1/4 sec. cor. of secs. 19 and 24, determined latitudinally by projection of E and W fence lines and longitudinally by road which bears N and SE. This point is accepted as the best available evidence of the position of the original corner.

**DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

Set a spike, 8 ins. long, flush with surface of road.

from which

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 86° 42' E., 26 1/2 lks. dist., with brass cap mkd. T7S R20E 1/4 S19 RM 1988, and an arrow pointing to the cor.

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 87° 35' W., 33 1/2 lks. dist., with brass cap mkd. T7S R19E 1/4 S24 RM 1988, and an arrow pointing to the cor.

S. 0° 44' E., beginning new measurement.

Over gentle rolling land.

23.55 The closing cor. of secs. 19 and 24, hereinbefore described.

Dependent Resurvey of the Subdivisional Lines,
T. 7 S., R. 20 E., Salt Lake Meridian, Utah

From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., hereinbefore described.

N. 1° 12' E., bet. secs. 35 and 36.

Over rolling land.

20.77 Point for the S 1/16 sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original cor.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

S 1/16
S 35 | S 36
1988

41.54 The 1/4 sec. cor. of secs. 35 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. as described in the official record of the 1950 resurvey.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 1° 12' E., beginning new measurement.

- 20.84** The N 1/16 sec. cor. of secs. 35 and 36, monumented with a partially rotted cottonwood stake, 3 ft. long, with dim scribe markings.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E
N 1/16
S35 | S36
1988

Deposit the dimly mkd. cottonwood stake alongside the stainless steel pipe.

N. 1° 12' E., beginning new measurement.

- 20.83** The cor. of secs. 25, 26, 35, and 36, monumented with an iron pipe, 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. as described in the official record of the 1950 resurvey of sec. 36, T. 7 S., R. 20 E.

N. 1° 29' W., bet. secs. 25 and 26.

Over rolling land.

- 20.48** Point for the S 1/16 sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner, not monumented.

- 40.96** The 1/4 sec. cor. of secs. 25 and 26, monumented with a cobblestone, 12x9x6 ins., firmly set, projecting 8 ins. above ground, mkd. 1/4 on the W face.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.

T7S R20E
1/4
S26 | S25
1988

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

Deposit the mkd. stone alongside the stainless steel pipe.

N. 0° 30' E., beginning new measurement.

0.75 Dirt road, bears E and W.

19.305 Point for the N 1/16 sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner, not monumented.

38.61 The cor. of secs. 23, 24, 25, and 26, monumented with a sandstone, 12x5x4 ins., firmly set, projecting 6 ins. above ground, mkd. 2 grooves on S and 1 groove on E faces.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E	
S23	S24
S26	S25
1988	

Deposit the mkd. stone alongside the stainless steel pipe.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

Cor. is located on E and W fence line.

From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., monumented with an iron pipe, 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. as described in the official record of the 1950 resurvey of the W. bdy., T. 7 S., R. 21 E.

S. 88° 24' W., bet. secs. 24 and 25.

Over bottom land along Green River.

39.64 The 1/4 sec. cor. of secs. 24 and 25, monumented with a partially rotted cottonwood stake, set in a mound of stone, dimly mkd. 1/4.

At the corner point

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E
1/4 $\frac{S24}{S25}$
1988

Deposit the cottonwood stake alongside the stainless steel pipe.

S. 89° 34' W., beginning new measurement.

- 5.16** Point selected for witness cor. to the meander cor. of secs. 24 and 25, on left bank of the Green River.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

W C
T17S R20E
M $\frac{S24}{S25}$
C 1988

- 5.66** Present left bank of river, course S.
- 6.405** Point for the meander cor. of secs. 24 and 25, for the 1882 resurvey, on the left bank of river, at proportionate distance, falls in river; there is no remaining evidence of the original corner.
- 14.45** Point for the meander cor. of secs. 24 and 25, for the 1882 resurvey, on the right bank of river, at proportionate distance, falls in river; there is no remaining evidence of the original corner.
- 14.96** Present right bank of river, course S, point for present meander cor.
- 15.15** Point selected for witness cor. to the meander cor. of secs. 24 and 25, on the right bank of the Green River.
- Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH

CHAINS

WC
T7S R20E
S24 | M
S25 | C
1988

39.38 The cor. of secs. 23, 24, 25, and 26.

N. 1° 00' W., bet. secs. 23 and 24.

Over rolling land.

42.25 Point for the 1/4 sec. cor. of secs. 23 and 24, determined by fence cor., with fences projecting N, S, E, and W. This position is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E
1/4
S23 | S24
1988

N. 1° 53' W., beginning new measurement.

20.395 Point for the N 1/16 sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the original corner, not monumented.

40.79 The cor. of secs. 13, 14, 23, and 24, mkd. by a cement nail imbedded in paved road which bears E and W. This point was established by Uintah Engineering and is accepted as the best available evidence of the position of the original cor.

from which

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 53° 00' W., 47 1/2 lks. dist., with brass cap mkd. T7S R20E S23 RM 1988, and an arrow pointing to the cor.

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 26° 00' W., 54 1/2 lks. dist., with brass cap mkd. T7S R20E S14 RM 1988, and an arrow pointing to the cor.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., hereinbefore described.

S. 87° 58' W., bet. secs. 13 and 24.

Over rolling land.

19.92 Point for the E 1/6 sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner, not monumented.

30.50 Dirt road, bears NW and SE.

39.84 The 1/4 sec. cor. of secs. 13 and 24, determined by fence cor., with fences projecting E, W and N. This position is accepted as the best available evidence of the position of the original cor.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E
1/4 $\frac{S13}{S24}$
1988

Cor. is located 35 lks. S of E and W dirt road.

S. 89° 57' W., beginning new measurement.

7.50 Dirt road, bears NE and SW.

20.695 Point for the W 1/16 sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner, not monumented.

25.00 Paved road, bears W and beginning of dirt road, bears SE.

41.39 The cor. of secs. 13, 14, 23, and 24.

N. 1° 27' W., bet. secs. 13 and 14.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

Over cultivated land.

20.18

The S 1/16 sec. cor. of secs. 13 and 14, determined by fence cor., with fences projecting E, W and S. This point is accepted as the best available evidence of the position of the original cor.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

S 1/16
S14 | S13
1988

N. 1° 23' W., beginning new measurement.

20.18

The 1/4 sec. cor. of secs. 13 and 14, monumented with a sandstone, 18x12x6 ins., firmly set, projecting 10 ins. above ground, mkd. 1/4 on W face.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E
1/4
S14 | S13
1988

Deposit the mkd. stone alongside the stainless steel pipe.

Cor. is located at base of sandstone ledge, 10 ft. high, bears E and W.

N. 0° 38' E., beginning new measurement.

Asc. over ledge.

20.04

The N 1/16 sec. cor. of secs. 13 and 14, monumented with a sandstone, 16x12x4 ins., firmly set, projecting 10 ins. above ground, mkd. 1/16 on the W face.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH

CHAINS

N 1/16
S14 | S13
1988

Deposit the mkd. stone alongside the stainless steel pipe.

N. 0° 38' E., beginning new measurement.

20.04

The cor. of secs. 11, 12, 13, and 14, monumented with a sandstone, 18x10x6 ins., firmly set, projecting 8 ins. above ground, plainly mkd. 4 notches on S and 1 notch on E edges.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E
S11 | S12
S14 | S13
1988

Deposit the mkd. stone alongside the stainless steel pipe.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

From the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp., monumented with an iron pipe, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, and brass cap mkd. as described in the official record of the 1953 resurvey of the W. bdy., T. 7 S., R. 21 E.

S. 88° 40' W., bet. secs. 12 and 13.

Over rolling and broken land.

12.50

Dirt road, bears N and S.

40.74

The 1/4 sec. cor. of secs. 12 and 13, monumented with a sandstone, 15x10x4 ins., firmly set, projecting 10 ins. above ground, dimly mkd. 1/4 on N face.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

T7S R20E
1/4 $\frac{S12}{S13}$
1988

Deposit the mkd. stone alongside the stainless steel pipe.

S. 89° 19' W., beginning new measurement.

20.47 The W 1/16 sec. cor. of secs. 12 and 13, monumented with a sandstone, 16x7x4 ins., firmly set, projecting 10 ins. above ground, mkd. 1/16 on N face.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16 $\frac{S12}{S13}$
1988

Deposit the mkd. stone alongside the stainless steel pipe.

S. 88° 54' W., beginning new measurement.

19.92 The cor. of secs. 11, 12, 13, and 14.

N. 0° 07' W., bet. secs. 11 and 12.

Over rolling land.

40.36 Point for the 1/4 sec. cor. of secs. 11 and 12, at proportionate distance based on the irregular boundary method; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E
1/4
S11 | S12
1988

N. 0° 02' E., beginning new measurement.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

- 20.115** The N 1/16 sec. cor. of secs. 11 and 12, monumented with a sandstone, 16x8x5 ins., firmly set, projecting 10 ins. above ground, dimly mkd. 1/16 on W face.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

N 1/16
S11 | S12
1988

Deposit the mkd. stone alongside the stainless steel pipe.

N. 1° 42' W., beginning new measurement.

- 20.365** The cor. of secs. 1, 2, 11, and 12, monumented with a sandstone, 18x10x6 ins., firmly set, projecting 8 ins. above ground, mkd. 4 notches on S and 1 notch on E edges.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E
S2 | S1
S11 | S12
1988

Deposit the mkd. stone alongside the stainless steel pipe.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp., monumented with an iron pipe, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, and brass cap mkd. as described in the official record of the 1953 resurvey of the W. bdy., T. 7 S., R. 21 E.

S. 88° 42' W., bet. secs. 1 and 12.

Over rolling and broken land.

- 40.31** The 1/4 sec. cor. of secs. 1 and 12, monumented with a sandstone, 24x10x8 ins., firmly set, projecting 10 ins. above ground, mkd. 1/4 on N face.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E
1/4 $\frac{S1}{S12}$
1988

Deposit the mkd. stone alongside the stainless steel pipe.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.

N. 89° 04' W., beginning new measurement.

19.00 Dirt road, bears NW and SE.

20.71 The W 1/16 sec. cor. of secs. 1 and 12, monumented with a broken sandstone, 18x10x3 ins., partially set and dimly mkd. 1/16.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16 $\frac{S1}{S12}$
1988

Deposit the mkd. stone alongside the stainless steel pipe.

S. 88° 55' W., beginning new measurement.

20.12 The cor. of secs. 1, 2, 11, and 12.

N. 0° 40' W., bet. secs. 1 and 2.

Over rolling and broken land.

18.00 Dirt road, bears E and W.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

- 40.00** The 1/4 sec. cor. of secs. 1 and 2, monumented with a sandstone, 20x12x8 ins., firmly set, projecting 10 ins. above ground, dimly mkd. 1/4 on W face.
- At the corner point
- Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
- T7S R20E
1/4
S2 | S1
1988
- Deposit the mkd. stone alongside the stainless steel pipe.
- Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.
-
- N. 0° 07' E., beginning new measurement.
- 40.67** The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., hereinbefore described.
-
- From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., hereinbefore described.
- N. 0° 39' W., bet. secs. 34 and 35.
- Over gentle rolling land.
- 40.94** Point for the 1/4 sec. cor. of secs. 34 and 35, at proportionate distance based on the irregular boundary method; there is no remaining evidence of the original corner.
- Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
- T7S R20E
1/4
S34 | S35
1988
-
- N. 0° 10' W., beginning new measurement.
- Over cultivated land.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

20.49 Point for the N 1/16 sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner, not monumented.

40.98 Point for the cor. of secs. 26, 27, 34, and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E	
S27	S26
S34	S35
1988	

From the cor. of secs. 25, 26, 35, and 36.

S. 84° 00' W., bet. secs. 26 and 35.

Over rolling land.

40.37 Point for the 1/4 sec. cor. of secs. 26 and 35, determined by fence cor., with fences projecting N and W. This position is accepted as the best available evidence of the position of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E	
1/4	S26
	S35
1988	

N. 89° 08' W., beginning new measurement.

Over nearly level land.

21.74 The W 1/16 sec. cor. of secs. 26 and 35, determined by fence cor., with fences projecting E and S. This position is accepted as the best available evidence of the position of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16	S26
	S35
1988	

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

N. 83° 24' W., beginning new measurement.

Over cultivated land.

20.26 The cor. of secs. 26, 27, 34, and 35.

N. 0° 24' W., bet. secs. 26 and 27.

Over cultivated land.

20.52 Point for the S 1/16 sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original corner, not monumented.

41.04 Point for the 1/4 sec. cor. of secs. 26 and 27, at proportionate distance based on the irregular boundary method; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E
1/4
S27 | S26
1988

N. 0° 13' W., beginning new measurement.

Over cultivated land.

20.53 Point for the N 1/16 sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original corner, not monumented.

41.06 The cor. of secs. 22, 23, 26, and 27, mkd. by a spike, buried flush with surface of ground. This point was established by Uintah Engineering and is accepted as the best available evidence of the position of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 30 ins. in the ground, with brass cap mkd.

T7S R20E
S22 | S23
S27 | S26
1988

Cor. is located along S edge of 3 way intersection of roads, with roads projecting E, W and N.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

From the cor. of secs. 23, 24, 25, and 26.

N. 89° 04' W., bet. secs. 23 and 26.

Over gentle rolling land.

40.84 Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate distance based on irregular boundary method; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 30 ins. in the ground, with brass cap mkd.

T7S R20E
1/4 S23
 S26
 1988

N. 89° 33' W., beginning new measurement.

Along dirt road.

40.86 The cor. of secs. 22, 23, 26, and 27.

N. 0° 40' W., bet. secs. 22 and 23.

Along dirt road.

40.14 The 1/4 sec. cor. of secs. 22 and 23, mkd. by a rebar, buried below surface of dirt road. This point was established by Uintah Engineering and is accepted as the best available evidence of the position of the original cor.

from which

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 89° 19' E., 48 1/2 lks. dist., with brass cap mkd. T7S R20E 1/4 S23 RM 1988, and an arrow pointing to the cor.

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 88° 14' W., 49 lks. dist., with brass cap mkd. T7S R20E 1/4 S22 RM 1988, and an arrow pointing to the cor.

N. 0° 58' W., beginning new measurement.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

Along dirt road.

20.59 Point for the N 1/16 sec. cor. of secs. 22 and 23, at proportionate distance, falls in dirt road; there is no remaining evidence of the original corner, not monumented.

41.18 The cor. of secs. 14, 15, 22, and 23, mkd. by a steel spike, imbedded in paved road of 3 way intersection. Paved roads project N and E, and dirt road projects S. This point was established by Uintah Engineering and is accepted as the best available evidence of the position of the original cor.

from which

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 50° 26' E., 61 1/2 lks. dist., with brass cap mkd. T7S R20E S14 RM 1988, and an arrow pointing to the cor.

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 51° 19' E., 62 1/2 lks. dist., with brass cap mkd. T7S R20E S23 RM 1988, and an arrow pointing to the cor.

From the cor. of secs. 13, 14, 23, and 24.

S. 89° 44' W., bet. secs. 14 and 23.

Over rolling land along paved road.

40.38 The 1/4 sec. cor. of secs. 14 and 23, determined latitudinally by centerline of E and W road, and longitudinally by fence line projecting S. This point is accepted as the best available evidence of the position of the original corner.

Set a spike, 8 ins. long, flush with surface of road.

from which

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 49° 30' E., 45 1/2 lks. dist., with brass cap mkd. T7S R20E 1/4 S14 RM 1988, and an arrow pointing to the cor.

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears South, 31 lks. dist., with brass cap mkd. T7S R20E 1/4 S23 RM 1988, and an arrow pointing to the cor.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

S. 89° 20' W., beginning new measurement.

Along paved road.

40.38 The cor. of secs. 14, 15, 22, and 23.

N. 0° 24' W., bet. secs. 14 and 15.

Over gentle rolling land; along paved road.

20.225 Point for the S 1/6 sec. cor. of secs. 14 and 15, at proportionate distance, falls near centerline of N and S road, and in alignment with fence line projecting W. There is no remaining evidence of the original corner, not monumented.

40.45 The 1/4 sec. cor. of secs. 14 and 15, mkd. by nail set by local surveyors and shown to me by interested property owners, is accepted as the best available evidence of the position of the original corner.

From this point

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears East, 49 1/2 lks. dist., with brass cap mkd. T7S R20E 1/4 S14 RM 1988, and an arrow pointing to the cor.

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears West, 49 1/2 lks. dist., with brass cap mkd. T7S R20E 1/4 S15 RM 1988, and an arrow pointing to the cor.

N. 0° 26' W., beginning new measurement.

20.17 Point for the N 1/16 sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original corner, not monumented.

40.34 The cor. of secs. 10, 11, 14, and 15, monumented with a sandstone, 16x9x8 ins., firmly set, projecting 8 ins. above ground, mkd. 4 notches on the S, and 2 notches on the E edges.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T7S R20E
S10 | S11
S15 | S14
1988

Deposit the mkd. stone alongside the stainless steel pipe.

Cor. is located by fence cor., with fences projecting E, W and N, and in bottom of ravine, which drains E.

From the cor. of secs. 11, 12, 13, and 14.

S. 89° 46' W., bet. secs. 11 and 14.

Over rolling and broken land.

20.455 The E 1/16 sec. cor. of secs. 11 and 14, monumented with a sandstone, 20x10x3 ins., set, projecting 10 ins. above ground, dimly mkd. 1/16 on N face.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

E 1/16 S11
S14
1988

Deposit the mkd. stone alongside the stainless steel pipe.

N. 89° 49' W., beginning new measurement.

Asc. over E slope.

19.62 The 1/4 sec. cor. of secs. 11 and 14, monumented with a sandstone, 14x8x4 ins., firmly set, projecting 10 ins. above ground, mkd. 1/4 on the N face.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E
1/4 S11
S14
1988

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposit the mkd. stone alongside the stainless steel pipe.

S. $89^{\circ} 31'$ W., beginning new measurement.

Desc. over broken W slope.

1.00 Wash in bottom of main canyon, drains SE.

20.18 The W 1/16 sec. cor. of secs. 11 and 14, monumented with a sandstone, 14x10x4 ins., firmly set, projecting 10 ins. above ground, dimly mkd. 1/16 on the N face.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16 $\frac{S11}{S14}$
1988

Deposit the mkd. stone alongside the stainless steel pipe.

S. $89^{\circ} 38'$ W., beginning new measurement.

20.51 The cor. of secs. 10, 11, 14, and 15.

N. $1^{\circ} 23'$ W., bet. secs. 10 and 11.

Over rolling and broken land; asc. over S slope.

40.40 The 1/4 sec. cor. of secs. 10 and 11, determined by fence cor., with fences projecting S and E. Also a galvanized pipe, 1 in. diam., projecting 6 ins. above ground and alongside the fence cor., was placed there by local surveyors and used as the corner point.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S 20E
1/4
S10 | S 11
1988

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

N. 1° 03' E., beginning new measurement.

20.53

The N 1/16 sec. cor. of secs. 10 and 11, monumented with a sandstone, 24x10x8 ins., firmly set, projecting 15 ins. above ground, dimly mkd. 1/16 on W face.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

N 1/16
S10 | S11
1988

Deposit the mkd. stone alongside the stainless steel pipe.

N. 1° 08' W., beginning new measurement.

19.86

The cor. of secs. 2, 3, 10, and 11, monumented with a sandstone, 20x8x6 ins., firmly set, projecting 10 ins. above ground, mkd. 5 notches on the S edge and 2 notches on the E edge.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E
S3 | S2
S10 | S11
1988

Deposit the mkd. stone alongside the stainless steel pipe.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

From the cor. of secs. 1, 2, 11, and 12.

S. 89° 43' W., bet. secs. 2 and 11.

Over rough and broken land.

20.41

The E 1/16 sec. cor. of secs. 2 and 11, monumented with a sandstone, 20x12x6 ins., firmly set, projecting 15 ins. above ground, dimly mkd. 1/16 on N face.

At the corner point

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 1/2 ft. base, to top of brass cap mkd.

E 1/16 $\frac{S2}{S11}$
1988

Deposit the mkd. stone alongside the stainless steel pipe.

S. 89° 22' W., beginning new measurement.

19.945 The 1/4 sec. cor. of secs. 2 and 11, monumented with a sandstone, 16x10x6 ins., firmly set, projecting 10 ins. above mound, dimly mkd. 1/4 on the N face.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E
1/4 $\frac{S2}{S11}$
1988

Deposit the mkd. stone alongside the stainless steel pipe.

S. 89° 55' W., beginning new measurement.

40.76 The cor. of secs. 2, 3, 10, and 11.

N. 0° 20' W., bet. secs. 2 and 3.

Over rolling and broken land.

20.145 Point for the S 1/16 sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner, not monumented.

40.29 The 1/4 sec. cor. of secs. 2 and 3, monumented with a sandstone, 20x8x6 ins., firmly set, projecting 10 ins. above ground, mkd. 1/4 on the W face.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T7S 20E
1/4
S3 | S2
1988

Deposit the mkd. stone alongside the stainless steel pipe.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

N. 2° 15' E., beginning new measurement.

- 20.33** The N 1/16 sec. cor. of secs. 2 and 3, monumented with a sandstone, 10x8x6 ins., firmly set, projecting 6 ins. above ground, dimly mkd. 1/16 on the W face.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

N 1/16
S3 | S2
1988

Deposit the mkd. stone alongside the stainless steel pipe.

N. 1° 06' W., beginning new measurement.

- 15.20** Dirt road, bears E and W.

- 20.19** The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., hereinbefore described.

From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., hereinbefore described.

N. 0° 44' W., bet. secs. 33 and 34.

Over gentle rolling land; along State Highway No. 88.

- 20.64** Point for the S 1/16 sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner, not monumented.

- 41.28** The 1/4 sec. cor. of secs. 33 and 34, determined longitudinally by center of right-of-way along State Highway No. 88, bearing N and S, and latitudinally by fence line projecting E.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

Set a spike, 8 ins. long, flush with surface of road.

from which

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 85° 00' E., 49 1/2 lks. dist., with brass cap mkd. T7S R20E 1/4 S34 RM 1988, and an arrow pointing to the cor.

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 55° 00' W., 68 lks. dist., with brass cap mkd. T7S R20E 1/4 S33 RM 1988, and an arrow pointing to the cor.

N. 0° 38' W., beginning new measurement.

Along State Highway No. 88.

20.63 Point for the N 1/16 sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner, not monumented

41.26 The cor. of secs. 27, 28, 33, and 34, determined longitudinally by State Highway No. 88, which bears N and S, and latitudinally by fence line projecting E.

Set a spike, 6 ins. long, flush with surface of road.

from which

A right-of-way marker, steel pipe, 2 ins. diam., firmly set, projecting 6 ins. above ground, cap not mkd., bears N. 36° 30' E., 83 1/2 lks. dist.

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 37° 00' W., 80 lks. dist., with brass cap mkd. T7S R20E S28 RM 1988, and an arrow pointing to the cor.

From the cor. of secs. 26, 27, 34, and 35.

S. 81° 46' W., bet. secs. 27 and 34.

Over cultivated land.

20.27 The E 1/16 sec. cor. of secs. 27 and 34, determined by fence cor., with fences projecting N, S and W. This position is accepted as the true corner position by adjacent land owners, and is accepted as the best available evidence of the position of the original corner.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

E 1/16 $\frac{S27}{S34}$
1988

N. 87° 02' W., beginning new measurement.

Along fence line.

19.97

The 1/4 sec. cor. of secs. 27 and 34, determined by fence cor., with fences projecting N, S, E, and W. This position is accepted as the true corner position by adjacent land owners, and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E
1/4 $\frac{S27}{S34}$
1988

N. 87° 25' W., beginning new measurement.

Along fence line.

40.58

The cor. of secs. 27, 28, 33, and 34.

N. 0° 30' W., bet. secs. 27 and 28.

Over gentle rolling land; along State Highway No. 88.

20.725

Point for the S 1/16 sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner, not monumented.

41.45

The 1/4 sec. cor. of secs. 27 and 28, determined longitudinally by centerline of State Highway No. 88, bearing N and S, and Latitudinally by fence line projecting E.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a spike, 6 ins. long, flush with surface of road.

from which

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears East, 58 lks. dist., with brass cap mkd. T7S R20E 1/4 S27 RM 1988, and an arrow pointing to the cor.

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 80° 00' W., 41 lks. dist., with brass cap mkd. T7S R20E 1/4 S28 RM 1988, and an arrow pointing to the cor.

N. 0° 33' W., beginning new measurement.

Along State Highway No. 88.

20.67 Point for the N 1/16 sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner.

Set a T-iron, 18 ins. long, flush with surface on W edge of paved road, with cadmium cap mkd.

N 1/16
S28 | S27
1988

41.34 The cor. of secs. 21, 22, 27, and 28, mkd. by a steel spike, flush with surface of road. This point was established by Uintah Engineering and is accepted as the best available evidence of the position of the original corner.

from which

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 67° 00' E., 118 1/2 lks. dist., with brass cap mkd. T7S R20E S22 RM 1988, and an arrow pointing to the cor.

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 19° 15' W., 50 1/2 lks. dist., with brass cap mkd. T7S R20E S21 RM 1988, and an arrow pointing to the cor.

From the cor. of secs. 22, 23, 26, and 27.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

N. 89° 29' W., bet. secs. 22 and 27.

Along dirt road.

- 40.29** The 1/4 sec. cor. of secs. 22 and 27, mkd. by a steel spike, flush with surface of road. This point was established by Uintah Engineering and is accepted as the best available evidence of the position of the original corner.

from which

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 49° 42' W., 64 1/2 lks. dist., with brass cap mkd. T7S R20E 1/4 S27 RM 1988, and an arrow pointing to the cor.

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 46° 30' W., 69 lks. dist., with brass cap mkd. T7S R20E 1/4 S22 RM 1988, and an arrow pointing to the cor.

N. 89° 33' W., beginning new measurement.

Along paved road.

- 40.52** The cor. of secs. 21, 22, 27, and 28.

N. 0° 40' W., bet. secs. 21 and 22.

Over nearly level land; along State Highway No. 88.

- 20.29** Point for the S 1/16 sec. cor. of secs. 21 and 22, at proportionate distance, falls in paved road; there is no remaining evidence of the original corner, not monumented.

- 40.58** The 1/4 sec. cor. of secs. 21 and 22, mkd. by a steel spike, flush with surface of road. This point was established by Uintah Engineering and is accepted as the best available evidence of the position of the original corner.

from which

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears East, 115 1/2 lks. dist., with brass cap mkd. T7S R20E 1/4 S22 RM 1988, and an arrow pointing to the cor.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears West, 26 1/2 lks. dist., with brass cap mkd. T7S R20E 1/4 S21 RM 1988, and an arrow pointing to the cor.

N. 0° 39' W., beginning new measurement.

Along State Highway No. 88.

20.30 Point for the N 1/16 sec. cor. of secs. 21 and 22, at proportionate distance, falls in paved road; there is no remaining evidence of the original corner, not monumented.

40.60 The cor. of secs. 15, 16, 21, and 22, mkd. by a steel bolt imbedded in paved road of State Highway No. 88. This point was established by local surveyors and is accepted as the best available evidence of the position of the original corner.

from which

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 43° 20' W., 70 lks. dist., with brass cap mkd. T7S R20E S21 RM 1988, and an arrow pointing to the cor.

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 44° 30' W., 70 1/2 lks. dist., with brass cap mkd. T7S R20E S16 RM 1988, and an arrow pointing to the cor.

From the cor. of secs. 14, 15, 22, and 23.

N. 89° 50' W., bet. secs. 15 and 22.

Over rolling land.

40.22 The 1/4 sec. cor. of secs. 15 and 22, mkd. by a rebar, 5/8 ins., diam., projecting 8 ins. above ground. This point was established by local surveyors and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

T7S R20E
1/4 $\frac{S15}{S22}$
1988

N. 89° 23' W., beginning new measurement.

20.17 Point for the W 1/16 sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16 $\frac{S15}{S22}$
1988

40.34 The cor. of secs. 15, 16, 21, and 22.

N. 0° 42' W., bet. secs. 15 and 16.

Over nearly level land, along dirt road.

39.89 The 1/4 sec. cor. of secs. 15 and 16, mkd. by a brass cap, 1 in. diam., flush with surface of ground, with brass cap mkd. 1/4 S15 S16 Uintah County Surveyor, and is accepted as the best available evidence of the position of the original cor.

No other improvements were made on this corner point.

N. 0° 40' W., beginning new measurement.

Along W edge of dirt road.

19.40 Curve in paved road, with roads projecting N and SE.

38.73 The cor. of secs. 9, 10, 15, and 16, mkd. by a spike imbedded in paved road. This point was established by Uintah Engineering and is accepted as the best available evidence of the position of the original corner.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

from which

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 88° 38' E., 46 lks. dist., with brass cap mkd. T7S R20E S15 RM 1988, and an arrow pointing to the cor.

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 86° 33' W., 48 lks. dist., with brass cap mkd. T7S R20E S9 RM 1988, and an arrow pointing to the cor.

From the cor. of secs. 10, 11, 14, and 15.

S. 88° 46' W., bet. secs. 10 and 15.

Over rolling and broken land; asc. over SE slope.

20.275 Point for the E 1/16 sec. cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

E 1/16 $\frac{S10}{S15}$
1988

40.55 The 1/4 sec. cor. of secs. 10 and 15, mkd. by a galvanized pipe, 1 in. diam., firmly set, projecting 8 ins. above ground, and mkd. 1/4 on N face. This point was established by local surveyors and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E
1/4 $\frac{S10}{S15}$
1988

S. 88° 53' W., beginning new measurement.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

- 40.35** The cor. of secs. 9, 10, 15, and 16.
-
- N. $0^{\circ} 37'$ W., bet. secs. 9 and 10.
- Over gentle rolling land, along paved road.
- 41.54** The 1/4 sec. cor. of secs. 9 and 10, mkd. by a steel bolt imbedded in the asphalt surface of the road. This point was established by Uintah Engineering and is accepted as the best available evidence of the position of the original corner.
- from which
- A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. $87^{\circ} 49'$ E., 48 1/2 lks. dist., with brass cap mkd. T7S R20E 1/4 S10 RM 1988, and an arrow pointing to the cor.
- A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. $89^{\circ} 14'$ W., 48 1/2 lks. dist., with brass cap mkd. T7S R20E 1/4 S9 RM 1988, and an arrow pointing to the cor.
-
- N. $0^{\circ} 33'$ W., beginning new measurement.
- Along paved road.
- 39.84** The cor. of secs. 3, 4, 9, and 10, mkd. by an brass cap, set on rebar, 1 in. diam., firmly set, projecting 2 ins. above ground, mkd. Uintah County Surveyor, S3, S4, S9 and S10, and is accepted as the best available evidence of the position of the original cor.
-
- From the cor. of secs. 2, 3, 10, and 11.
- S. $89^{\circ} 24'$ W., bet. secs. 3 and 10.
- Over rolling land, asc. over NE slope.
- 40.36** The 1/4 sec. cor. of secs. 3 and 10, monumented with a sandstone, 24x14x6 ins., firmly set, projecting 10 ins. above ground, dimly mkd. 1/4 on the N face.
- At the corner point
- Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T7S R20E
1/4 $\frac{S3}{S10}$
1988

Deposit the mkd. stone alongside the stainless steel pipe.

Cor. is located in N and S fence line.

S. 89° 06' W., beginning new measurement.

Asc. over NE slope.

40.32 The cor. of secs. 3, 4, 10, and 11.

N. 0° 15' E., bet. secs. 3 and 4.

Over rolling land.

40.66 The 1/4 sec. cor. of secs. 3 and 4, monumented with a sandstone, 18x8x6 ins., firmly set, projecting 10 ins. above ground and dimly mkd. 1/4 on the W face.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E
1/4
S4 | S3
1988

Deposit the mkd. stone alongside the stainless steel pipe.

Cor. is located in E and W fence line.

N. 0° 12' E., beginning new measurement.

40.48 The cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., hereinbefore described.

From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., hereinbefore described.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

N. 0° 45' W., bet. secs. 32 and 33.

Over cultivated land.

20.78 Point for the S 1/16 sec. cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original corner, not monumented.

41.56 Point for the 1/4 sec. cor. of secs. 32 and 33, at proportionate distance based on the irregular boundary method; there is no remaining evidence of the original corner.

Cor. point not monumented at the request of the private land owner.

N. 0° 42' W., beginning new measurement.

Over cultivated land.

20.79 Point for the N 1/16 sec. cor. of secs. 32 and 33, at proportionate distance, falls in alfalfa field; there is no remaining evidence of the original corner, not monumented.

41.58 The cor. of secs. 28, 29, 32, and 33, mkd. by a galvanized pipe, 1 in. diam., firmly set, projecting 8 ins. above ground. This point was established by local surveyors, and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E	
S29	S28
S32	S33
1988	

Cor. is located in N and S fence line.

From the cor. of secs. 27, 28, 33, and 34.

S. 89° 10' W., bet. secs. 28 and 33.

Over gentle rolling land, over cultivated land.

40.09 Point for the 1/4 sec. cor. of secs. 28 and 33, at proportionate distance based on the irregular boundary method; there is no remaining evidence of the original corner.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E
1/4 S28
 S33
 1988

S. 89° 33' W., beginning new measurement.

40.13 The cor. of secs. 28, 29, 32, and 33.

N. 1° 08' W., bet. secs. 28 and 29.

Over rolling land, along fence line.

20.645 The S 1/16 sec. cor. of secs. 28 and 29, mkd. by a galvanized pipe, 1 in. diam., firmly set, projecting 8 ins. above ground. This point was established by local surveyors, and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

S 1/16
S29 | S28
1988

N. 0° 50' W., beginning new measurement.

Asc. over gentle S slope.

20.67 The 1/4 sec. cor. of secs. 28 and 29, mkd. by a galvanized pipe, 1 in. diam., firmly set, projecting 8 ins. above ground. This point was established by local surveyors, and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

T7S R20E
1/4
S29 | S28
1988

N. 0° 16' W., beginning new measurement.

2.00 Waters edge, S end of Pelican Lake, bears NW and SE.

20.465 Point for the N 1/16 sec. cor. of secs. 28 and 29, at proportionate distance; there is no remaining evidence of the original corner, not monumented.

40.93 Point for the cor. of secs. 20, 21, 28, and 29, at proportionate distance, falls in lake; there is no remaining evidence of the original corner.

From the cor. of secs. 21, 22, 27, and 28.

S. 88° 56' W., bet. secs. 21 and 28.

1.50 Waters edge, E end of Pelican Lake, bears N and S.

40.14 Point for the 1/4 sec. cor. of secs. 21 and 28, at proportionate distance based on the irregular boundary method, falls in water; there is no remaining evidence of the original corner, not monumented.

S. 89° 02' W., beginning new measurement.

40.18 Point for the cor. of secs. 20, 21, 28, and 29.

N. 1° 16' W., bet. secs. 20 and 21.

Over water.

20.405 Point for the S 1/16 sec. cor. of secs. 20 and 21, at proportionate distance, falls in water; there is no remaining evidence of the original corner, not monumented.

40.81 Point for the 1/4 sec. cor. of secs. 20 and 21, at proportionate distance based on the irregular boundary method, falls in water; there is no remaining evidence of the original corner, not monumented.

N. 0° 49' W., beginning new measurement.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

Over water

20.395 Point for the N 1/16 sec. cor. of secs. 20 and 21, at proportionate distance, falls in water; there is no remaining evidence of the original corner, not monumented.

23.80 Waters edge, N end of Pelican Lake, bears E and W.

40.79 The cor. of secs. 16, 17, 20, and 21, mkd. by a steel spike, flush with surface of road. This point was established by Uintah Engineering and is accepted as the best available evidence of the position of the original corner.

from which

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 43° 00' W., 50 1/2 lks. dist., with brass cap mkd. T7S R20E S20 RM 1988, and an arrow pointing to the cor.

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 43° 17' W., 52 lks. dist., with brass cap mkd. T7S R20E S17 RM 1988, and an arrow pointing to the cor.

From the cor. of secs. 15, 16, 21, and 22.

S. 89° 14' W., bet. secs. 16 and 21.

Over nearly level land; along paved road.

36.00 Waters edge, N end of Pelican Lake.

40.40 Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate distance based on irregular boundary method, falls in water; there is no remaining evidence of the original corner, not monumented.

S. 89° 16' W., beginning new measurement.

Over water.

4.50 Waters edge, N end of Pelican Lake.

40.44 The cor. of secs. 16, 17, 20, and 21.

N. 0° 33' W., bet. secs. 16 and 17.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

Over nearly level land, along paved road.

- 19.49** Point for the S 1/16 sec. cor. of secs. 16 and 17, determined latitudinally by fence line projecting E, and longitudinally by center of N - S right-of-way. This point is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

S 1/16
S17 | S16
1988

From the cor. of secs. 9, 10, 15, and 16.

N. 89° 45' W., bet. secs. 9 and 16.

Over rolling land.

- 40.30** The 1/4 sec. cor. of secs. 9 and 16, monumented with a sandstone, 14x10x4 ins., firmly set, projecting 9 ins. above ground, mkd. 1/4 on N face.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E
1/4 S9
 S16
 1988

Deposit the mkd. stone alongside the stainless steel pipe.

Cor. is located by fence cor. pipe, with fences projecting E, W and N.

S. 89° 29' W., beginning new measurement.

- 23.00** State Highway No. 88, bears NW and SE.

- 40.34** The cor. of secs. 8, 9, 16, and 17, mkd. by a steel spike, flush with surface of road. This point was established by Uintah Engineering and is accepted as the best available evidence of the position of the original cor.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH

CHAINS

from which

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 50° 10' E., 62.1 lks. dist., with brass cap mkd. T7S R20E S9 RM 1988, and an arrow pointing to the cor.

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 64° 30' W., 90.9 lks. dist., with brass cap mkd. T7S R20E S8 RM 1988, and an arrow pointing to the cor.

N. 0° 39' W., bet. secs. 8 and 9.

Over nearly level land, along paved road.

13.00 State Highway No. 88, bears NW and SE.

20.17 Point for the S 1/16 sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original corner, not monumented.

27.50 Curve of State Highway No. 209, bears N and SE.

40.34 The 1/4 sec. cor. of secs. 8 and 9, determined latitudinally by fence line projecting E and W, and longitudinally by center of N - S right-of-way.

Set a spike, 6 ins. long, flush with surface of road.

from which

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 75° 47' E., 52 1/2 lks. dist., with brass cap mkd. T7S R20E 1/4 S9 RM 1988, and an arrow pointing to the cor.

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 79° 56' W., 50 lks. dist., with brass cap mkd. T7S R20E 1/4 S8 RM 1988, and an arrow pointing to the cor.

N. 0° 23' W., beginning new measurement.

Along paved road.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

40.24 The cor. of secs. 4, 5, 8, and 9, mkd. by a spike, flush with surface of road. This point was established by Uintah Engineering and is accepted as the best available evidence of the position of the original corner.

from which

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 50° 36' E., 61 lks. dist., with brass cap mkd. T7S R20E S4 RM 1988, and an arrow pointing to the cor.

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 58° 10' E., 61 lks. dist., with brass cap mkd. T7S R20E S9 RM 1988, and an arrow pointing to the cor.

From the cor. of secs. 3, 4, 9, and 10.

S. 89° 21' W., bet. secs. 4 and 9.

Over nearly level land, along paved road.

40.34 The 1/4 sec. cor. of secs. 4 and 9, mkd. by a spike, flush with surface of road. This point was established by Uintah Engineering and is accepted as the best available evidence of the position of the original corner.

from which

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 2° 21' E., 49 lks. dist., with brass cap mkd. T7S R20E 1/4 S9 RM 1988, and an arrow pointing to the cor.

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 2° 21' W., 62 lks. dist., with brass cap mkd. T7S R20E 1/4 S4 RM 1988, and an arrow pointing to the cor.

S. 89° 10' W., beginning new measurement.

Along paved road.

40.22 The cor. of secs. 4, 5, 8, and 9.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0° 01' E., bet. secs. 4 and 5.

Over gentle rolling land; along paved road.

40.88

The 1/4 sec. cor. of secs. 4 and 5, mkd. by a spike, flush with surface of road. This point was established by Uintah Engineering and is accepted as the best available evidence of the position of the original corner.

from which

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 88° 45' E., 52 lks. dist., with brass cap mkd. T7S R20E 1/4 S4 RM 1988, and an arrow pointing to the cor.

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears West, 50 lks. dist., with brass cap mkd. T7S R20E 1/4 S5 RM 1988, and an arrow pointing to the cor.

N. 0° 09' E., beginning new measurement.

Along State Highway No. 209.

40.35

The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., hereinbefore described.

From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., hereinbefore described.

N. 1° 41' W., bet. secs. 31 and 32.

Over gentle rolling land.

41.90

The 1/4 sec. cor. of secs. 31 and 32, monumented with a sandstone, 12x7x3 ins., firmly set, projecting 8 ins. above ground, dimly mkd. 1/4 on W face.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E
1/4
S31 | S32
1988

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposit the mkd. stone alongside the stainless steel pipe.

N. 0° 49' W., beginning new measurement.

- 20.455** The N 1/16 sec. cor. of secs. 31 and 32, monumented with a sandstone, 19x8x8 ins., firmly set, projecting 10 ins. above ground, dimly mkd. 1/16 on the W face.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

N 1/16
S31 | S32
1988

Deposit the mkd. stone alongside the stainless steel pipe.

N. 0° 42' W., beginning new measurement.

- 20.66** The cor. of secs. 29, 30, 31, and 32, monumented with a rebar encircled with a small mound of stone. This point was established by local surveyors and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E
S30 | S29
S31 | S32
1988

From the cor. of secs. 28, 29, 32, and 33.

S. 89° 36' W., bet. secs. 29 and 32.

Over rolling land.

- 20.125** The E 1/16 sec. cor. of secs. 29 and 32, monumented with a sandstone, 18x5x5 ins., firmly set, projecting 10 ins. above ground, dimly mkd. 1/16 on N face.

At the corner point

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

E 1/16 $\frac{S29}{S32}$
1988

Deposit the mkd. stone alongside the stainless steel pipe.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.

S. 89° 36' W., beginning new measurement.

10.00 Dirt road, bears NW and SE.

20.125 Point for the 1/4 sec. cor. of secs. 29 and 32, at proportionate distance based on the irregular boundary method; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E
1/4 $\frac{S29}{S32}$
1988

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.

S. 89° 24' W., beginning new measurement.

20.09 The W 1/16 sec. cor. of secs. 29 and 32, monumented with a sandstone, 17x5x5 ins., firmly set, projecting 10 ins. above ground, dimly mkd. 1/16 on N face.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16 $\frac{S29}{S32}$
1988

Deposit the mkd. stone alongside the stainless steel pipe.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

- S. 89° 22' W., beginning new measurement.
- 20.58** The cor. of secs. 29, 30, 31, and 32.
-
- S. 89° 36' W., bet. secs. 30 and 31.
- Over rolling land.
- 2.00** Dirt road, bears NE and SW.
- 36.92** The closing cor. of secs. 30 and 31, on the Uintah Indian Reservation, hereinbefore described.
-
- From the cor. of secs. 29, 30, 31, and 32.
- N. 0° 20' W., bet. secs. 29 and 30.
- Over rolling land.
- 0.28** Dirt road, bears NE and SW.
- 20.49** Point for the S 1/16 sec. cor. of secs. 29 and 30, at proportionate distance; there is no remaining evidence of the original corner, not monumented.
- 40.98** The 1/4 sec. cor. of secs. 29 and 30, mkd. with a partially rotted cottonwood stake, in mound of stone, is accepted as the best available evidence of the position of the original corner.
- At the corner point
- Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
- T7S R20E
1/4
S30 | S29
1988
- Deposit the rotted cottonwood stake alongside the stainless steel pipe.
-
- N. 0° 02' W., beginning new measurement.
- 41.04** Point for the cor. of secs. 19, 20, 29, and 30, at proportionate distance; there is no remaining evidence of the original corner.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E	
S19	S20
S30	S29
1988	

From a point for the cor. of secs. 20, 21, 28, and 29.

S. 89° 12' W., bet. secs. 20 and 29.

Over water.

- 40.15** Point for the 1/4 sec. cor. of secs. 20 and 29, at proportionate distance based on the irregular boundary method, falls in water; there is no remaining evidence of the original corner, not monumented.

S. 89° 31' W., beginning new measurement.

Over water.

- 36.20** W shore line of Pelican Lake, bears N and S.

- 40.15** The cor. of secs. 19, 20, 29, and 30.

N. 88° 39' W., bet. secs. 19 and 30.

Over gentle rolling land.

- 20.145** The E 1/16 sec. cor. of secs. 19 and 30, monumented with a sandstone, 12x7x4 ins., firmly set, projecting 6 ins. above ground, plainly mkd. 1/16 on the N face.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

E 1/16	S19
	S30
	1988

Deposit the mkd. stone alongside the stainless steel pipe.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

S. 89° 24' W., beginning new measurement.

- 19.895** The 1/4 sec. cor. of secs. 19 and 30, monumented with a sandstone, 12x6x4 ins., firmly set, projecting 6 ins. above ground, mkd. 1/4 on the N face. This stone appears to be of local origin, but is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E
1/4 S19
 S30
 1988

Deposit the mkd. stone alongside the stainless steel pipe.

S. 89° 18' W., beginning new measurement.

- 19.51** The W 1/16 sec. cor. of secs. 19 and 30, monumented with a sandstone, 14x8x8 ins., firmly set, projecting 8 ins. above ground, dimly mkd., 1/16 on N face.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16 S19
 S30
 1988

Deposit the mkd. stone alongside the stainless steel pipe.

S. 89° 54' W., beginning new measurement.

- 11.86** The closing cor. of secs. 19 and 30, on the Uintah Indian Reservation Boundary, hereinbefore described.
-

From the cor. of secs. 19, 20, 29, and 30.

N. 0° 48' W., bet. secs. 19 and 20.

Over gentle rolling land.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

- 25.00** W shore line of Pelican Lake, bears NW and SE.
- 40.72** Point for the 1/4 sec. cor. of secs. 19 and 20, at proportionate distance, falls in water; there is no remaining evidence of the original corner, not monumented.
-
- N. 1° 00' W., beginning new measurement.
- 5.00** W shore line of Pelican Lake, bears NE and SW.
- 20.35** Point for the N 1/16 sec. cor. of secs. 19 and 20, at proportionate distance; there is no remaining evidence of the original corner, not monumentd.
- 40.70** The cor. of secs. 17, 18, 19, and 20, determined latitudinally by center of E - W right-of-way, and longitudinally by fence lines projecting N - S. This point is accepted as the best available evidence of the position of the original corner.
- Set a spike 6 ins. long, flush with surface of road.
- from which
- A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears North, 36 1/2 lks. dist., with brass cap mkd. T7S R20E S17 RM 1988, and an arrow pointing to the cor.
- A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 2° 30' E., 36 1/2 lks. dist., with brass cap mkd. T7S R20E S20 RM 1988, and an arrow pointing to the cor.
-
- From the cor. of secs. 16, 17, 20, and 21.
- S. 89° 12' W., bet. secs. 17 and 20.
- Over nearly level land, along paved road.
- 40.02** The 1/4 sec. cor. of secs. 17 and 20, mkd. by a spike imbedded in paved road. This point is accepted as the best available evidence of the position of the original corner.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

from which

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears North, 37 1/2 lks. dist., with brass cap mkd. T7S R20E 1/4 S17 RM 1988, and an arrow pointing to the cor.

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears South, 33 1/2 lks. dist., with brass cap mkd. T7S R20E 1/4 S20 RM 1988, and an arrow pointing to the cor.

S. 89° 14' W., beginning new measurement.

40.12 The cor. of secs. 17, 18, 19, and 20.

S. 89° 34' W., bet. secs. 18 and 19.

Over gentle rolling land; along paved road.

40.23 The 1/4 sec. cor. of secs. 18 and 19, determined latitudinally by center of E - W right-of-way, and longitudinally by fence line projecting S.

Set a spike, 6 ins. long, flush with surface of road.

from which

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 15° 00' E., 35 1/2 lks. dist., with brass cap mkd. T7S R20E 1/4 S19 RM 1988, and an arrow pointing to the cor.

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, N. 15° 00' W., 37 1/2 lks. dist., with brass cap mkd. T7S R20E 1/4 S18 RM 1988, and an arrow pointing to the cor.

S. 89° 30' W., beginning new measurement.

Along paved road.

37.85 The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., hereinbefore described.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

From the cor. of secs. 17, 18, 19, and 20.

N. $0^{\circ} 48'$ W., bet. secs. 17 and 18.

Over gentle rolling land.

40.11

The 1/4 sec. cor. of secs. 17 and 18, monumented with a mound of stone in an E and W fence line. This point was shown to me by an interested property owner who testifies this point to be the true corner point.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E
1/4
S18 | S17
1988

N. $0^{\circ} 55'$ W., beginning new measurement.

40.22

The cor. of secs. 7, 8, 17, and 18, determined latitudinally by proportionate measurement, and longitudinally by E and W fence line.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E
S7 | S8
S18 | S17
1988

From the cor. of secs. 8, 9, 16, and 17.

S. $89^{\circ} 40'$ W., bet. secs. 8 and 17.

Over gentle rolling land; along dirt road.

20.08

Point for the E 1/16 sec. cor. of secs. 8 and 17, determined latitudinally by center of E - W right-of-way, and longitudinally by fence lines projecting N - S.

Set a spike, 6 ins. long, flush with surface of dirt road.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

from which

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears North, 50 lks. dist., with brass cap mkd. 1/16 S8 RM 1988, and an arrow pointing to the cor.

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, S. 12° 00' W., 48 1/2 lks. dist., with brass cap mkd. 1/16 S17 RM 1988, and an arrow pointing to the cor.

S. 89° 40' W., beginning new measurement.

Along dirt road.

20.15 Point for the 1/4 sec. cor. of secs. 8 and 17, determined latitudinally by center of E - W right-of-way, and longitudinally by fence lines projecting N and S.

Set a spike, 6 ins. long, flush with surface of dirt road.

from which

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears North, 47 lks. dist., with brass cap mkd. 1/4 S8 RM 1988, and an arrow pointing to the cor.

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears South, 24 1/2 lks. dist., with brass cap mkd. 1/4 S17 RM 1988, and an arrow pointing to the cor.

S. 89° 53' W., beginning new measurement.

Along dirt road.

20.15 The W 1/16 sec. cor. of secs. 8 and 17, monumented with a sandstone, 20x7x7 ins., firmly set 12 ins. below surface of road, plainly mkd. 1/16 on N face.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 30 ins. in the ground, flush with surface of dirt road, and brass cap mkd.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH

CHAINS

W 1/16 $\frac{S8}{S17}$
1988

Deposit the mkd. stone alongside the stainless steel pipe.

S. 89° 53' W., beginning new measurement.

Road curves N; enter cultivated land.

20.15 The cor. of secs. 7, 8, 17, and 18.

S. 89° 48' W., bet. secs. 7 and 18.

Over gentle rolling land; along fence line.

40.18 The 1/4 sec. cor. of secs. 7 and 18, monumented with a cobblestone, 14x10x4 ins., firmly set, projecting 10 ins. above ground, mkd. 1/4 on N face.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E
1/4 $\frac{S7}{S18}$
1988

Deposit the mkd. stone alongside the stainless steel pipe.

Cor. is located alongside fence cor. post, with fences projecting N, S, E, and W.

S. 89° 48' W., beginning new measurement.

Along fence line.

37.38 The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., hereinbefore described.

From the cor. of secs. 7, 8, 17, and 18.

N. 0° 05' W., bet. secs. 7 and 8.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

Over gentle rolling land.

20.22 Point for the S 1/16 sec. cor. of secs. 7 and 8, at proportionate distance; there is no remaining evidence of the original corner, not monumented.

40.44 Point for the 1/4 sec. cor. of secs. 7 and 8, determined latitudinally by center of E - W right-of-way, and longitudinally by fence lines projecting N and S.

Set a spike, 6 ins. long, flush with surface of dirt road.

from which

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 51° 30' E., 78 lks. dist., with brass cap mkd. 1/4 S8 RM 1988, and an arrow pointing to the cor.

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 21° 16' W., 47 lks. dist., with brass cap mkd. 1/4 S7 RM 1988, and an arrow pointing to the cor.

N. 0° 03' W., beginning new measurement.

Over cultivated land.

40.52 The cor. of secs. 5, 6, 7, and 8, monumented with a cobblestone, 12x8x6 ins., firmly set, projecting 6 ins. above ground, dimly mkd. with scattered mound of stone, W of cor.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E	
S6	S5
S7	S8
1988	

Deposit the mkd. stone alongside the stainless steel pipe.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

From the cor. of secs. 4, 5, 8, and 9.

N. 89° 55' W., bet. secs. 5 and 8.

Over rolling land.

39.99

The 1/4 sec. cor. of secs. 5 and 8, mkd. by a rebar, 5/8 ins. diam., firmly set, projecting 4 ins. above ground. This point was established by Uintah Engineering, and is accepted as the best available evidence to the position of the original corner.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E

1/4 $\frac{S5}{S8}$
1988

N. 89° 57' W., beginning new measurement.

19.93

Point for the W 1/16 sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16 $\frac{S5}{S8}$
1988

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.

39.86

The cor. of secs. 5, 6, 7, and 8.

S. 89° 30' W., bet. secs. 6 and 7.

Over cultivated land.

40.22

Point for the 1/4 sec. cor. of secs. 6 and 7, determined latitudinally by fence projecting W, and longitudinally by old fence line projecting N and S.

At the corner point

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E
1/4 $\frac{S6}{S7}$
1988

S. 89° 32' W., beginning new measurement.

Over cultivated land.

38.18 The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., hereinbefore described.

From the cor. of secs. 5, 6, 7, and 8.

N. 0° 40' W., bet. secs. 5 and 6.

Over rolling land.

20.08 Point for the S 1/16 sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

S 1/16
S6 | S5
1988

40.16 The 1/4 sec. cor. of secs. 5 and 6, monumented with a cobblestone, 16x8x5 ins., firmly set, projecting 10 ins. above ground, mkd. 1/4 on W face.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E
1/4
S6 | S5
1988

Deposit the mkd. stone alongside the stainless steel pipe.

**DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

N. 0° 23' W., beginning new measurement.

20.075 The N 1/16 sec. cor. of secs. 5 and 6, monumented with a sandstone, 20x10x8 ins., firmly set, projecting 10 ins. above ground, mkd. 1/4 on W face.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

N 1/16
S6 | S5
1988

Deposit the mkd. stone alongside the stainless steel pipe.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

N. 0° 35' W., beginning new measurement.

20.365 The cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the Tp., hereinbefore described.

Dependent Resurvey of the Subdivision of Section 3,
T. 7 S., R. 20 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 2 and 3.

S. 89° 32' W., on the E - W centerline of sec. 3.

Over rolling land.

40.14 Point for the center 1/4 sec. cor. of sec. 3, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3 1/2 ft. base, to top of brass cap, mkd.

T7S R20E
C 1/4 S3
1988

60.21 The center W 1/16 sec. cor. of sec. 3, monumented with a sandstone, 20x8x6 ins., firmly set, projecting 10 ins. above ground, mkd. 1/16 on the N face.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 3,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

$$C \frac{W \ 1/16}{S3} C$$

1988

Deposit the mkd. stone alongside the stainless steel pipe.

S. 89° 32' W., beginning new measurement.

20.05 The 1/4 sec. cor. of secs. 3 and 4.

From the point for the S 1/16 sec. cor. of secs. 2 and 3.

S. 89° 24' W., on the E - W centerline of the S 1/2 of sec. 3.

Over rolling land.

40.24 Point for the center S 1/16 sec. cor. of sec. 3, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

$$S \ 1/16 \begin{array}{c} C \\ | \\ C \end{array} S3$$

1988

Enter cultivated land.

80.48 Point for the S 1/16 sec. cor. of secs. 3 and 4.

From the 1/4 sec. cor. of secs. 3 and 10.

NORTH, on the N - S centerline of sec. 3.

Over rolling land.

20.13 The center S 1/16 sec. cor. of sec. 3.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 3,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

NORTH, beginning new measurement.

20.24 The center 1/4 sec. cor. of sec. 3.

Dependent Resurvey of the Subdivision of Section 4,
T. 7 S., R. 20 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 3 and 4.

S. 89° 26' W., on the E - W centerline of sec. 4.

Over rolling land.

20.345 The center E 1/16 sec. cor. of 4, determined by fence cor., with fences projecting E, W and N; is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C $\frac{E\ 1/16}{S4}$ C
1988

N. 0° 39' E., on the N - S centerline of the NE 1/4 of sec. 4.

Over rolling land.

20.375 The NE 1/16 sec. cor. of sec. 4, monumented with a sandstone, 10x8x3 ins., firmly set, projecting 5 ins. above ground, dimly mkd. 1/16.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

NE 1/16 S4
1988

Deposit the mkd. stone alongside the stainless steel pipe.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 4,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

S. 89° 53' W., on the E - W centerline of the N 1/2 of sec. 4.

Over rolling land.

- 20.195** The center N 1/16 sec. cor. of sec. 4, determined by fence cor., with fences projecting N, S and W, is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C
N 1/16 | S4
C
1988

N. 0° 16' W., on the N - S centerline of sec. 4.

Over rolling land.

- 19.875** The 1/4 sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp., hereinbefore described.

Dependent Resurvey of the Subdivision of Section 5,
T. 7 S., R. 20 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 4 and 5.

S. 89° 35' W., on the E - W centerline of sec. 5.

Over rolling land.

- 40.18** Point for the center 1/4 sec. cor. of 5, at proportionate distance, falls in alfalfa field; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E
C 1/4 S5
1988

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 5,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

Cor. is located N. 4° 30' W., 59 1/2 lks. from fence cor.

60.27 Point for the center W 1/16 sec. cor. of sec. 5, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

$$C \frac{W \ 1/16}{S5} C$$

1988

Cor. is located along W edge of dirt road, which bears N and S.

80.36 The 1/4 sec. cor. of secs. 5 and 6.

From the center N 1/16 sec. cor. of sec. 5, determined latitudinally by center of E - W dirt road, and longitudinally by projection of N and S fence line.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., flush with surface of road, with brass cap mkd.

$$C$$

$$N \ 1/16 \ | \ S5$$

$$C$$

1988

S. 89° 35' W., on the E - W centerline of the N 1/2 of sec. 5.

Over rolling land.

20.11 Point for the NW 1/16 sec. cor. of sec. 5, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

$$NW \ 1/16 \ S5$$

1988

Fence cor., bears S. 31° 12' E., 71 1/2 lks. dist.

40.22 The N 1/16 sec. cor. of secs. 5 and 6.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 5,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

From the 1/4 sec. cor. of secs. 5 and 8.

N. 0° 16' W., on the N - S centerline of sec. 5.

Over rolling land.

20.05

The center S 1/16 sec. cor. of sec. 5, determined by cor. of fences, with fences projecting S and E, is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C
S 1/16 | S5
C
1988

N. 0° 13' W., beginning new measurement.

20.445

The center 1/4 sec. cor. of sec. 5.

From the center N 1/16 sec. cor. of sec. 5.

N. 0° 16' W., on the N - S centerline of sec. 5.

Over rolling land.

20.44

The 1/4 sec. cor. of secs. 5 and 32, on the N. bdy. of the Tp., hereinbefore described.

From the center W 1/16 sec. cor. of sec. 5.

N. 0° 19' W., on the N - S centerline of the NW 1/4 of sec. 5.

Over rolling land.

20.08

The NW 1/16 sec. cor. of sec. 5.

Dependent Resurvey of the Subdivision of Section 6,
T. 7 S., R. 20 E., Salt Lake Meridian, Utah

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 6,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

From the N 1/16 sec. cor. of secs. 5 and 6.

S. 89° 44' W., on the E - W centerline of the N 1/2 of sec. 6.

Over rolling land.

20.135 Point for the NE 1/16 sec. cor. of sec. 6, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

NE 1/16 S6
1988

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

40.27 The center N 1/16 sec. cor. of sec. 6, monumented with a sandstone, 10x8x6 ins., firmly set, projecting 1 in. above ground, mkd. 1/16.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C
N 1/16 | S6
C
1988

Deposit the mkd. stone alongside the stainless steel pipe.

N. 0° 43' W., on the N - S centerline of sec. 6.

Over rolling land.

21.355 The 1/4 sec. cor. of secs. 6 and 31, on the N. bdy. of the Tp., hereinbefore described.

Dependent Resurvey of the Subdivision of Section 7,
T. 7 S., R. 20 E., Salt Lake Meridian, Utah

From the center 1/4 sec. cor. of sec. 7, determined latitudinally by centerline of Utah State Highway No. 88, and longitudinally by fence line projecting N.

DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 7,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a spike, 6 ins. long, flush with surface of road.

from which

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 35° 00' E., 69 lks. dist., with brass cap mkd. T7S R20E RM S7 C 1/4 1988, and an arrow pointing to the cor.

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, S. 47° 15' E., 55 lks. dist., with brass cap mkd. T7S R20E RM S7 C 1/4 1988, and an arrow pointing to the cor.

S. 89° 37' W., on the E - W centerline of sec. 7.

Along paved road.

19.86 Point for the center W 1/16 sec. cor. of sec. 7, at proportionate distance; there is no remaining evidence of the original corner.

Set a spike, 6 ins. long, flush with surface of road

from which

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 32° 22' E., 58 1/2 lks. dist., with brass cap mkd. CW 1/16 S7 RM 1988, and an arrow pointing to the cor.

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, S. 35° 56' E., 52 1/2 lks. dist., with brass cap mkd. CW 1/16 S7 RM 1988, and an arrow pointing to the cor.

37.73 The 1/4 sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp., hereinbefore described.

From the 1/4 sec. cor. of secs. 7 and 18.

N. 0° 04' W., on the N - S centerline of sec. 7.

Over gentle rolling land.

20.205 The center S 1/16 sec. cor. of sec. 7, monumented with a granite stone, 16x8x6 ins., firmly set, projecting 8 ins. above ground, mkd. 1/16 on W face.

DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 7,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH

CHAINS

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C
S 1/16 | S7
C
1988

Deposit the mkd. stone alongside the stainless steel pipe.

N. 0° 03' W., beginning new measurement.

Over gentle rolling land.

20.115 The center 1/4 sec. cor. of sec. 7.

Dependent Resurvey of the Subdivision of Section 8,
T. 7 S., R. 20 E., Salt Lake Meridian, Utah

From the center E 1/16 sec. cor. of sec. 8, determined by fence cor., with fences projecting N, S and E, is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C — E 1/16 — C
S8
1988

S. 89° 54' W., on the E - W centerline of sec. 8.

Over rolling land.

19.98 The center 1/4 sec. cor. of sec. 8, determined latitudinally by center of E - W right-of-way fences along Utah Highway No. 88, and longitudinally by fence lines projecting N and S.

At the corner point

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 8,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E
C 1/4 S8
1988

S. 89° 54' W., beginning new measurement.

2.00 Curve of State Utah Highway No. 88, bears W and SE.

19.965 The center W 1/16 sec. cor. of sec. 8, determined latitudinally by center of Utah Highway No. 88, and longitudinally by dirt road which bears S.

Set a spike, 6 ins. long, flush with surface of road

from which

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 45° 00' E., 68 1/2 lks. dist., with brass cap mkd. CW 1/16 S8 RM 1988, and an arrow pointing to the cor.

A stainless steel pipe 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 45° 00' W., 65 1/2 lks. dist., with brass cap mkd. CW 1/16 S8 RM 1988, and an arrow pointing to the cor.

From the point for the S 1/16 sec. cor. of secs. 8 and 9.

S. 89° 49' W., on the E - W centerline of the S 1/2 of sec. 8.

Over rolling land.

20.01 Point for the SE 1/16 sec. cor. of sec. 8, at proportionate distance, falls in alfalfa field; there is no remaining evidence of the original corner, not monumented.

60.03 The SW 1/16 sec. cor. of sec. 8, determined latitudinally by proportionate measurement, and longitudinally by center of N and S dirt road.

At the corner point

Set a spike, 6 ins. long, flush with surface of road

from which

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 8,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

Set a T-iron, 18 ins. long, 12 ins. in the ground, for a reference monument, bears East, 47 1/2 lks. dist., with cadmium cap mkd. SW 1/16 S8 RM 1988, and an arrow pointing to the cor.

Set a T-iron, 18 ins. long, 12 ins. in the ground, for a reference monument, bears West, 47 lks. dist., with cadmium cap mkd. SW 1/16 S8 RM 1988, and an arrow pointing to the cor.

80.31 Point for the S 1/16 sec. cor. of secs. 7 and 8.

From the E 1/16 sec. cor. of secs. 8 and 17.

N. 0° 28' W., on the N - S centerline of the SE 1/4 of sec. 8.

Over rolling land.

20.22 Point for the SE 1/16 sec. cor. of sec. 8.

N. 0° 01' W., beginning new measurement.

9.27 Centerline of Utah State Highway No. 88, bears NW and SE.

20.20 The center E 1/16 sec. cor. of sec. 8.

From the W 1/16 sec. cor. of secs. 8 and 17.

N. 0° 19' E., on the N - S centerline of the SW 1/4 of sec. 8.

Over rolling land, along dirt road.

20.245 The SW 1/16 sec. cor. of sec. 8.

N. 0° 13' E., beginning new measurement.

Along dirt road.

20.255 The center W 1/16 sec. cor. of sec. 8.

Dependent Resurvey of the Subdivision of Section 10,
T. 7 S., R. 20 E., Salt Lake Meridian, Utah

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 10,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

From the N 1/16 sec. cor. of secs. 10 and 11.

S. 89° 43' W., on the E - W centerline of the N 1/2 of sec. 10.

Over rolling land.

20.16 Point for the NE 1/16 sec. cor. of sec. 10, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

NE 1/16 S10
1988

Cor. is located 23 lks. S of E and W fence line.

40.32 The center N 1/16 sec. cor. of sec. 10, determined by fence cor., with fences projecting N and E, and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C
N 1/16 | S10
C
1988

N. 0° 38' E., on the N - S centerline of sec. 10.

Over rolling land.

20.19 The 1/4 sec. cor. of secs. 3 and 10.

Dependent Resurvey of the Subdivision of Section 13,
T. 7 S., R. 20 E., Salt Lake Meridian, Utah

From the center S 1/16 sec. cor. of sec. 13, monumented with sandstone, 14x9x4 ins., firmly set, projecting 8 ins. above ground, dimly mkd. 1/16 on W face.

At the corner point

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 13,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C
S 1/16 | S13
C
1988

Deposit the mkd. stone alongside the stainless steel pipe.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

S. 89° 34' W., on the E - W centerline of the S 1/2 of sec. 13.

Over rolling land.

20.20 Point for the SW 1/16 sec. cor. of sec. 13, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

SW 1/16 S13
1988

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

40.40 The S 1/16 sec. cor. of secs. 13 and 14.

From the 1/4 sec. cor. of secs. 13 and 24.

N. 4° 08' W., on the N - S centerline of sec. 13.

Over rolling land.

20.51 The center S 1/16 sec. cor. of sec. 13.

Dependent Resurvey of the Subdivision of Section 14,
T. 7 S., R. 20 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 13 and 14.

S. 89° 36' W., on the E - W centerline of sec. 14.

Over rolling land.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 14,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

20.01 Point for the center E 1/16 sec. cor. of sec. 14, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.

C — $\frac{E\ 1/16}{S14}$ — C
1988

40.03 Point for the center 1/4 sec. cor. of sec. 14, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E
C 1/4 S14
1988

80.06 The 1/4 sec. cor. of secs. 14 and 15.

From the S 1/16 sec. cor. of secs. 13 and 14.

S. 89° 34' W., on the E - W centerline of the S 1/2 of sec. 14.

Over rolling land.

20.10 Point for the SE 1/16 sec. cor. of sec. 14, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

SE 1/16 S14
1988

80.40 Point for the S 1/16 sec. cor. of secs. 14 and 15.

From the N 1/16 sec. cor. of secs. 13 and 14.

S. 89° 42' W., on the E - W centerline of the N 1/2 of sec. 14.

Over rolling land.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 14,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

40.22 Point for the center N 1/16 sec. cor. of sec. 14, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C
N 1/16 | S14
C
1988

60.33 Point for the NW 1/16 sec. cor. of sec. 14, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

NW 1/16 S14
1988

80.44 Point for the N 1/16 sec. cor. of secs. 14 and 15.

From the SE 1/16 sec. cor. of sec. 14.

N. 1° 10' E., on the N - S centerline of the SE 1/4 of sec. 14.

Over rolling land.

20.195 The center E 1/16 sec. cor. of sec. 14.

From the center 1/4 sec. cor. of sec. 14.

N. 0° 05' E., on the N - S centerline of sec. 14.

Over rolling land.

20.11 The center N 1/16 sec. cor. of sec. 14.

From the NW 1/16 sec. cor. of sec. 14.

N. 0° 50' E., on the N - S centerline of the NW 1/4 of sec. 14.

Over rolling land.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 14,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

20.155 The W 1/16 sec. cor. of secs. 11 and 14.

Dependent Resurvey of the Subdivision of Section 15,
T. 7 S., R. 20 E., Salt Lake Meridian, Utah

From the point for the N 1/16 sec. cor. of secs. 14 and 15.

S. 89° 48' W., on the E - W centerline of the N 1/2 of sec. 15.

Over rolling land.

20.255 Point for the NE 1/16 sec. cor. of sec. 15, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

NE 1/16 S15
1988

40.51 The center N 1/16 sec. cor. of sec. 15, determined by fence cor., with fences projecting N and E, is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C
N 1/16 | S15
C
1988

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

N. 0° 35' W., on the N - S centerline of sec. 15.

Over rolling land.

19.43 The 1/4 sec. cor. of secs. 10 and 15.

From the NE 1/16 sec. cor. of sec. 15.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 15,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

N. $0^{\circ} 29'$ W., on the N - S centerline of the NE $1/4$ of sec. 15.

19.80 The E $1/16$ sec. cor. of secs. 10 and 15.

Dependent Resurvey of the Subdivision of Section 17,
T. 7 S., R. 20 E., Salt Lake Meridian, Utah

From the S $1/16$ sec. cor. of secs. 16 and 17.

N. $89^{\circ} 38'$ W., on the E - W centerline of the S $1/2$ of sec. 17.

Over gentle rolling land; enter cultivated land.

20.045 The SE $1/16$ sec. cor. of sec. 17, determined by fence cor., with fences projecting N, S and W, and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 $1/2$ ins. diam., 24 ins. in the ground, with brass cap mkd.

SE $1/16$ S17
1988

N. $0^{\circ} 31'$ W., on the N - S centerline of the SE $1/4$ of sec. 17.

Over cultivated land.

19.895 The center E $1/16$ sec. cor. of sec. 17, determined by fence cor., with fences projecting N, S, E, and W, and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 $1/2$ ins. diam., 24 ins. in the ground, with brass cap mkd.

C $\frac{E\ 1/16}{S17}$ C
1988

N. $0^{\circ} 47'$ W., on the N - S centerline of the NE $1/4$ of sec. 17.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 17,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

Over cultivated land.

- 19.865** The NE 1/16 sec. cor. of sec. 17, determined by fence cor., with fences projecting N, S, E, and W, and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

NE 1/16 S17
1988

N. 0° 28' W., beginning new measurement.

Over cultivated land.

- 20.015** The E 1/16 sec. cor. of secs. 8 and 17.

Dependent Resurvey of the Subdivision of Section 19,
T. 7 S., R. 20 E., Salt Lake Meridian, Utah

From the point for the 1/4 sec. cor. of secs. 19 and 20.

N. 89° 42' W., on the E - W centerline of sec. 19.

Over pasture land.

- 20.02** Point for the center E 1/16 sec. cor. of sec. 19, determined latitudinally by an E and W fence line, and longitudinally by proportionate measurement.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C $\frac{E\ 1/16}{S19}$ C
1988

S. 89° 45' W., beginning new measurement.

- 20.02** The center 1/4 sec. cor. of sec. 19, monumented with a sandstone, 17x8x6 ins., firmly set, projecting 10 ins. above ground, dimly mkd.. 1/4 on W face.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 19,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E
C 1/4 S19
1988

Deposit the mkd. stone alongside the stainless steel pipe.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

S. 89° 41' W., beginning new measurement.

19.82

The center W 1/16 sec. cor. of sec. 19, determined by fence cor., with fences projecting E, W and NW, is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C $\frac{W\ 1/16}{S19}$ C
1988

S. 89° 51' W., beginning new measurement.

18.45

The 1/4 sec. cor. of secs. 19 and 24, on the W. bdy. of the Tp., hereinbefore described.

From the 1/4 sec. cor. of secs. 19 and 30.

N. 2° 20' W., on the N - S centerline of sec. 19.

Over nearly level land.

20.175

The center S 1/16 sec. cor. of sec. 19, monumented with a sandstone, 14x8x4 ins., firmly set, projecting 8 ins. above ground, dimly mkd. 1/16 on the W face.

At the corner point

DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 19,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C
S 1/16 | S19
C
1988

Deposit the mkd. stone alongside the stainless steel pipe.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.

N. 0° 21' E., beginning new measurement.

20.405 The center 1/4 sec. cor. of sec. 19.

From the E 1/16 sec. cor. of secs. 19 and 30.

N. 1° 24' W., on the N - S centerline of the SE 1/4 of sec. 19.

Over gentle rolling land.

20.175 The SE 1/16 sec. cor. of sec. 19, monumented with a sandstone, 12x6x4 ins., firmly set, projecting 8 ins. above ground, dimly mkd. 1/16 on N face.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

SE 1/16 S19
1988

Deposit the mkd. stone alongside the stainless steel pipe.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

N. 0° 14' W., beginning new measurement.

20.13 The center E 1/16 sec. cor. of sec. 19.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 20,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

From the point for the 1/4 sec. cor. of secs. 20 and 21.

S. $89^{\circ} 16'$ W., on the E - W centerline of sec. 20.

Over water.

20.03 Point for the center E 1/16 sec. cor. of sec. 20, at proportionate distance, falls in Pelican Lake, not monumented.

40.06 Point for the center 1/4 sec. cor. of sec. 20, at proportionate distance, falls in Pelican Lake, not monumented.

80.12 Point for the 1/4 sec. cor. of secs. 19 and 20.

From a point for the N 1/16 sec. cor. of secs. 20 and 21.

S. $89^{\circ} 14'$ W., on the E - W centerline of the N 1/2 of sec. 20.

20.03 Point for the NE 1/16 sec. cor. of sec. 20, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

NE 1/16 S20
1988

40.06 Point for the center N 1/16 sec. cor. of sec. 20, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C
N 1/16 | S20
C
1988

80.12 Point for the N 1/16 sec. cor. of secs. 19 and 20.

From a point for the center 1/4 sec. cor. of sec. 20.

N. $0^{\circ} 46'$ W., on the N - S centerline of sec. 20.

Over water.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 20,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

19.00 Waters edge on N shore line of Pelican Lake, bears E - W.

20.355 The center N 1/16 sec. cor. of sec. 20.

From the point for the center E 1/16 sec. cor. of sec. 20.

N. $0^{\circ} 46'$ W., on the N - S centerline of the NE 1/4 of sec. 20.

Over water.

10.00 Waters edge on N shore of Pelican Lake, bears NW and SE.

20.365 The NE 1/16 sec. cor. of sec. 20.

Dependent Resurvey of the Subdivision of Section 21,
T. 7 S., R. 20 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 21 and 22.

S. $89^{\circ} 08'$ W., on the E - W centerline of sec. 21.

Over nearly level land.

2.00 Waters edge, E shore line of Pelican Lake, bears N - S.

20.19 Point for the center E 1/16 sec. cor. of sec. 21, at proportionate distance, falls in Pelican Lake, not monumented.

80.76 Point for the 1/4 sec. cor. of secs. 20 and 21.

From the point for the S 1/16 sec. cor. of secs. 21 and 22.

S. $89^{\circ} 04'$ W., on the E - W centerline of the S 1/2 of sec. 21.

Over nearly level land.

6.00 Waters edge, E shore line of Pelican Lake, bears N - SW.

20.14 Point for the SE 1/16 sec. cor. of sec. 21, at proportionate distance, falls in Pelican Lake, not monumented.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 21,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

80.56 Point for the S 1/16 sec. cor. of secs. 20 and 21.

From the point for the SE 1/16 sec. cor. of sec. 21.

N. 0° 48' W., on the N - S centerline of the SE 1/4 of sec. 21.

Over water.

20.325 Point for the center E 1/16 sec. cor. of sec. 21.

Dependent Resurvey of the Subdivision of Section 22,
T. 7 S., R. 20 E., Salt Lake Meridian, Utah

From the center 1/4 sec. cor. of sec. 22, mkd. by a rebar, 5/8 ins. diam., projecting 8 ins. above ground, alongside cor. of fences, projecting N, S and E. This point was established by Uintah Engineering and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E
C 1/4 S22
1988

N. 89° 12' W., on the E - W centerline of sec. 22.

Over cultivated land.

20.255 Point for the center W 1/16 sec. cor. of sec. 22, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C $\frac{W\ 1/16}{S22}$ C
1988

40.51 The 1/4 sec. cor. of secs. 21 and 22.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 22,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

From a point for the N 1/16 sec. cor. of secs. 22 and 23.

N. 89° 24' W., on the E - W centerline of the N 1/2 of sec. 22.

Over gentle rolling land; enter cultivated land.

40.34 Point for the center N 1/16 sec. cor. of sec. 22, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C
N 1/16 | S22
C
1988

Cor. is located 10 lks. E of N and S fence line.

60.51 Point for the NW 1/16 sec. cor. of sec. 22, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

NW 1/16 S22
1988

Cor. is located 5 lks. E of N and S fence line.

80.68 Point for the N 1/16 sec. cor. of secs. 21 and 22.

From the center 1/4 sec. cor. of sec. 22.

N. 1° 07' W., on the N - S centerline of sec. 22.

Over rolling land; along fence line.

20.45 The center N 1/16 sec. cor. of sec. 22.

N. 0° 39' W., beginning new measurement.

20.28 The 1/4 sec. cor. of secs. 15 and 22.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 22,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

From the center W 1/16 sec. cor. of sec. 22.

N. 1° 16' W., on the N - S centerline of the NW 1/4 of sec. 22.

Over cultivated land.

20.38 The NW 1/16 sec. cor. of sec. 22.

N. 0° 39' W., beginning new measurement.

20.29 The W 1/16 sec. cor. of secs. 15 and 22.

Dependent Resurvey of the Subdivision of Section 24,
T. 7 S., R. 20 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 23 and 24.

N. 89° 11' E., on the E - W center line of sec. 24.

19.87 The center W 1/16 sec. cor. of sec. 24, monumented with a sandstone, 12x10x8 ins., firmly set, projecting 6 ins. above ground, dimly mkd. 1/16 on N face.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C $\frac{W\ 1/16}{S24}$ C
1988

Deposit the mkd. stone alongside the stainless steel pipe.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.

East, beginning new measurement.

Over nearly level land.

20.00 Point for the center 1/4 sec. cor. of sec. 24, at record bearing and distance; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 24,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T7S R20E
C 1/4 S24
1988

- 25.00** Point for the original meander cor. of the 1882 survey, not monumented.
-
- S. 26° 28' E., along the partition line between federal and private accreted land.

- 4.04** Point for the special meander cor. of sec. 24, at proportionate distance, not monumented.
-

From the N 1/16 sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp., hereinbefore described.

S. 89° 30' W., on the E - W centerline of the N 1/2 of sec. 24.

Over nearly level land.

- 20.115** The NE 1/16 sec. cor. of sec. 24, monumented with a sandstone, 10x7x3 ins., firmly set, projecting 6 ins. above ground, mkd. 1/16 on W face.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

NE 1/16 S24
1988

Deposit the mkd. stone alongside the stainless steel pipe.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

S. 89° 30' W., beginning new measurement.

Over rolling land.

- 20.115** The center N 1/16 sec. cor. of sec. 24 monumented with a sandstone, 16x8x4 ins., firmly set, projecting 8 ins. above ground, dimly mkd. 1/16 on W face.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 24,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH

CHAINS

C
N 1/16 | S24
C
1988

Deposit the mkd. stone alongside the stainless steel pipe.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

S. 87° 05' W., beginning new measurement.

20.175 Point for the NW 1/16 sec. cor. of sec. 24, at proportionate distance; there is no remaining evidence of the original corner, not monumented.

40.35 Point for the N 1/16 sec. cor. of secs. 23 and 24.

From the center 1/4 sec. cor. of sec. 24.

N. 0° 37' W., on the N - S centerline of sec. 24.

Over nearly level land.

22.16 The center N 1/16 sec. cor. of sec. 24.

From the NE 1/16 sec. cor. of sec. 24.

N. 0° 42' E., on the N - S center line of the NE 1/4 of sec. 24.

18.895 Point for the E 1/16 sec. cor. of secs. 13 and 24.

From the point for the NW 1/16 sec. cor. of sec. 24.

N. 0° 20' W., on the N - S center line of the NW 1/4 of sec. 24.

19.375 Point for the W 1/16 sec. cor. of secs. 13 and 24.

Dependent Resurvey of the Subdivision of Section 26,
T. 7 S., R. 20 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 25 and 26.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 26,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

S. $88^{\circ} 59'$ W., on the E - W centerline of sec. 26.

Over gentle rolling land.

40.62 Point for the center 1/4 sec. cor. of sec. 26, at proportionate distance, falls in alfalfa field; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E
C 1/14 S26
1988

Over cultivated land.

81.24 The 1/4 sec. cor. of secs. 26 and 27.

From a point for the S 1/16 sec. cor. of secs. 25 and 26.

S. $88^{\circ} 57'$ W., on the E - W centerline of the S 1/2 of sec. 26.

Over gentle rolling land.

40.82 Point for the center S 1/16 sec. cor. of sec. 26, at proportionate distance, falls on E edge of alfalfa field; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C
S 1/16 | S26
C
1988

Over cultivated land.

81.64 Point for the S 1/16 sec. cor. of secs. 26 and 27.

From a point for the N 1/16 sec. cor. of secs. 25 and 26.

S. $89^{\circ} 51'$ W., on the E - W centerline of the N 1/2 of sec. 26.

Over rolling land.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 26,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

- 19.50** Dirt road, bears NW and SE.
- 40.74** Point for the center N 1/16 sec. cor. of sec. 26, at proportionate distance, falls in alfalfa field; there is no remaining evidence of the original corner.
- Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
- $$\begin{array}{c} \text{C} \\ \text{N } 1/16 \text{ | S26} \\ \text{C} \\ 1988 \end{array}$$
- Over cultivated land.
- 81.48** Point for the N 1/16 sec. cor. of secs. 26 and 27.
-
- From the 1/4 sec. cor. of secs. 26 and 35.
- N. 2° 52' W., on the N - S centerline of sec. 26.
- Over cultivated land.
- 23.97** The center S 1/16 sec. cor. of sec. 26.
-
- N. 0° 58' W., beginning new measurement.
- Over cultivated land.
- 20.50** The center 1/4 sec. cor. of sec. 26.
-
- N. 0° 06' E., beginning new measurement.
- Over cultivated land.
- 19.92** The center N 1/16 sec. cor. of sec. 26.
-
- N. 0° 12' E., beginning new measurement.
- Over cultivated land.
- 20.09** The 1/4 sec. cor. of secs. 23 and 26.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 27,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

Dependent Resurvey of the Subdivision of Section 27,
T. 7 S., R. 20 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 26 and 27.

N. 89° 45' W., on the E - W centerline of sec. 27.

Over cultivated land.

20.15 Point for the center E 1/16 sec. cor. of sec. 27, at proportionate distance, falls in alfalfa field; there is no remaining evidence of the original corner, not monumented.

40.30 Point for the center 1/4 sec. cor. of sec. 27, at proportionate distance, falls in barn yard and is unsafe to monument; there is no remaining evidence of the original corner, not monumented.

80.60 The 1/4 sec. cor. of secs. 27 and 28.

From the point for the S 1/16 sec. cor. of secs. 26 and 27.

N. 89° 54' W., on the E - W centerline of the S 1/2 of sec. 27.

Over rolling land.

20.14 Point for the SE 1/16 sec. cor. of sec. 27, at proportionate distance, falls in alfalfa field; there is no remaining evidence of the original corner, not monumented.

40.28 Point for the center S 1/16 sec. cor. of sec. 27, at proportionate distance, falls in alfalfa field; there is no remaining evidence of the original corner, not monumented.

80.56 Point for the S 1/16 sec. cor. of secs. 27 and 28.

From the 1/4 sec. cor. of secs. 27 and 34.

N. 1° 06' W., on the N - S centerline of sec. 27.

Over cultivated land.

22.48 Point for the center S 1/16 sec. cor. of sec. 27.

N. 0° 28' W., beginning new measurement.

DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 27,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH

CHAINS

20.625 Point for the center 1/4 sec. cor. of sec. 27.

From the E 1/16 sec. cor. of secs. 27 and 34.

N. 0° 34' W., on the N - S centerline of the SE 1/4 of sec. 27.

Over cultivated land.

23.47 Point for the SE 1/16 sec. cor. of sec. 27.

N. 0° 27' W., beginning new measurement.

20.575 Point for the center E 1/16 sec. cor. of sec. 27.

Dependent Resurvey of the Subdivision of Section 28,
T. 7 S., R. 20 E., Salt Lake Meridian, Utah

From the N 1/16 sec. cor. of secs. 27 and 28.

S. 89° 36' W., on the E - W centerline of the N 1/2 of sec. 28.

Over cultivated land.

20.115 Point for the NE 1/16 sec. cor. of sec. 28, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

NE 1/16 S28
1988

30.00 Waters edge on S shore line of Pelican Lake, bears NE and SW.

80.46 Point for the N 1/16 sec. cor. of secs. 28 and 29.

Dependent Resurvey of the Subdivision of Section 29,
T. 7 S., R. 20 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 28 and 29.

DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 29,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH

CHAINS

WEST, on the E - W centerline of sec. 29.

Over gentle rolling land.

- 20.475** The center E 1/16 sec. cor. of sec. 29, monumented with a sandstone, 16x8x4 ins., firmly set, projecting 8 ins. above ground, dimly mkd. 1/16 on N face.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C $\frac{E\ 1/16}{S29}$ C
1988

Deposit the mkd. stone alongside the stainless steel pipe.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.

N. 89° 34' W., beginning new measurement.

- 19.99** The center 1/4 sec. cor. of sec. 29, monumented with a sandstone, 12x10x6 ins., firmly set, projecting 6 ins. above ground, dimly mkd. 1/4 on W face.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E
C 1/4 S29
1988

Deposit the mkd. stone alongside the stainless steel pipe.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

S. 89° 41' W., beginning new measurement.

Over gentle rolling land.

- 19.955** The center W 1/16 sec. cor. of sec. 29, monumented with a sandstone, 14x8x6 ins., firmly set, projecting 10 ins. above ground, dimly mkd. 1/16 on N face.

At the corner point

DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 29,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C $\frac{W 1/16}{S29}$ C
1988

Deposit the mkd. stone alongside the stainless steel pipe.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.

S. 86° 53' W., beginning new measurement.

11.00 Dirt road, bears NW and SE.

20.06 The 1/4 sec. cor. of secs. 29 and 30.

From the S 1/16 sec. cor. of secs. 28 and 29.

S. 89° 52' W., on the E - W centerline of the S 1/2 of sec. 29.

Over rolling land.

20.20 Point for the SE 1/16 sec. cor. of sec. 29, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

SE 1/16 S29
1988

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

40.40 The center S 1/16 sec. cor. of sec. 29, mkd. by a rebar, 5/8 ins. diam., projecting 6 ins. above ground. This point was established by private surveyors and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 29,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH

CHAINS

S 1/16 | S29
C
C
1988

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

S. 88° 54' W., beginning new measurement.

13.50 Dirt road, bears NW and SE.

20.12 Point for the SW 1/16 sec. cor. of sec. 29, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

SW 1/16 S29
1988

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

40.24 Point for the S 1/16 sec. cor. of secs. 29 and 30.

From the E 1/16 sec. cor. of secs. 29 and 32.

N. 1° 20' W., on the N - S centerline of the SE 1/4 of sec. 29.

Over rolling land.

20.74 The SE 1/16 sec. cor. of sec. 29.

From the SW 1/16 sec. cor. of sec. 29.

N. 0° 33' W., on the N - S centerline of the SW 1/4 of sec. 29.

Over rolling land.

8.00 Dirt road, bears NW and SE.

21.195 The center W 1/16 sec. cor. of sec. 29.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 33,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

Dependent Resurvey of the Subdivision of Section 33,
T. 7 S., R. 20 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 33 and 34.

S. 89° 09' W., on the E - W centerline of sec. 33.

Over cultivated land.

- 20.02** Point for the center E 1/16 sec. cor. of sec. 33, determined longitudinally by N and S fence line, and latitudinally by proportionate measurement.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C $\frac{E\ 1/16}{S33}$ C
1988

- 40.04** Point for the center 1/4 sec. cor. of sec. 33, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E
C 1/4 S33
1988

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

- 60.06** Point for the center W 1/16 sec. cor. of sec. 33, determined longitudinally by N and S fence line, and latitudinally by proportionate measurement.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C $\frac{W\ 1/16}{S33}$ C
1988

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.

- 80.15** Point for the 1/4 sec. cor. of secs. 32 and 33.
-

From a point for the S 1/16 sec. cor. of secs. 33 and 34.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 33,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

S. 89° 03' W., on the E - W centerline of the S 1/2 of sec. 33.

Over cultivated land.

- 20.04** Point for the SE 1/16 sec. cor. of sec. 33, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

SE 1/16 S33
1988

- 40.08** Point for the center S 1/16 sec. cor. of sec. 33, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C
S 1/16 | S33
C
1988

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

- 60.12** Point for the SW 1/16 sec. cor. of sec. 33, at proportionate distance; determined longitudinally by N and S fence line and latitudinally by proportionate measurement.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

SW 1/16 S33
1988

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

- 80.16** Point for the S 1/16 sec. cor. of secs. 32 and 33.

From the point for the N 1/16 sec. cor. of secs. 33 and 34.

S. 89° 15' W., on the E - W centerline of the N 1/2 of sec. 33.

Over cultivated land.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 33,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

40.06 Point for the center N 1/16 sec. cor. of sec. 28, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C
N 1/16 | S33
C
1988

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

60.09 Point for the NW 1/16 sec. cor. of sec. 33, determined longitudinally by N - S fence line, and latitudinally by proportionate measurement.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

NW 1/16 S33
1988

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

80.18 Point for the N 1/16 sec. cor. of secs. 32 and 33.

From the center 1/4 sec. cor. of sec. 33.

N. 0° 35' W., on the N - S centerline of sec. 33.

Over gentle rolling land.

20.71 The center N 1/16 sec. cor. of sec. 33.

From the SE 1/16 sec. cor. of sec. 33.

N. 0° 41' W., on the N - S centerline of the SE 1/4 of sec. 33.

Over gentle rolling land; along W edge of cultivated land.

20.67 The center E 1/16 sec. cor. of sec. 33.

From the SW 1/16 sec. cor. of sec. 33.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 33,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

N. $0^{\circ} 36'$ W., on the N - S centerline of the SW 1/4 of sec. 33.

Along fence line.

20.75 The center W 1/16 sec. cor. of sec. 33.

N. $0^{\circ} 36'$ W., on the N - S centerline of the NW 1/4 of sec. 33.

Over nearly level land; along fence line.

20.75 The NW 1/16 sec. cor. of sec. 33.

Dependent Resurvey of the Subdivision of Section 34,
T. 7 S., R. 20 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 34 and 35.

S. $89^{\circ} 47'$ W., on the E - W centerline of sec. 34.

Over gentle rolling land; over cultivated land.

20.06 Point for the center E 1/16 sec. cor. of sec. 34, at proportionate distance, falls in alfalfa field; there is no remaining evidence of the original corner, not monumented.

40.12 Point for the center 1/4 sec. cor. of sec. 34, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T7S R20E
C 1/4 S34
1988

Cor. is located near W edge of cultivated land.

80.24 The point for the 1/4 sec. cor. of secs. 33 and 34.

From a point for the N 1/16 sec. cor. of secs. 34 and 35.

S. $89^{\circ} 53'$ W., on the E - W centerline of the N 1/2 of sec. 34.

Over cultivated land.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 34,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

20.095 Point for the NE 1/16 sec. cor. of sec. 34, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C
N 1/16 | S34
C
1988

Cor. is located 13 1/2 lks. W of N and S fence line.,

40.19 Point for the center N 1/16 sec. cor. of sec. 34, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C
N 1/16 | S34
C
1988

80.38 Point for the N 1/16 sec. cor. of secs. 33 and 34.

From the center 1/4 sec. cor. of sec. 34.

N. 0° 26' W., on the N - S centerline of sec. 34.

Over cultivated land.

20.565 The center N 1/16 sec. cor. of sec. 34.

N. 0° 19' E., beginning new measurement.

Over cultivated land.

18.71 The 1/4 sec. cor. of secs. 27 and 34.

From the point for the center E 1/16 sec. cor. of sec. 34.

N. 0° 20' W., on the N - S centerline of the NE 1/4 of sec. 34.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 34,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

Over cultivated land.

20.53 The NE 1/16 sec. cor. of sec. 34.

N. 0° 10' W., beginning new measurement.

17.63 The E 1/16 sec. cor. of secs. 27 and 34.

Dependent Resurvey of the Subdivision of Section 35,
T. 7 S., R. 20 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 35 and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, set and mkd. as described in the dependent resurvey of sec. 36 in 1950.

S. 89° 22' W. on the E - W centerline of sec. 35.

Over rolling land.

60.795 Point for the center W 1/16 sec. cor. of sec. 35, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C $\frac{W\ 1/16}{S35}$ C
1988

Cor. is located 7 lks. E of N and S fence line.

Enter cultivated land.

81.06 The 1/4 sec. cor. of secs. 34 and 35.

From the N 1/16 sec. cor. of secs. 35 and 36.

S. 89° 08' W., on the E - W centerline of the N 1/2 of sec. 35.

Over rolling land.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 35,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

- 61.155** Point for the NW 1/16 sec. cor. of sec. 35, at proportionate distance; there is no remaining evidence of the original corner.
- Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
- NW 1/16
S35
1988
- Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.
- Over cultivated land.
- 81.54** Point for the N 1/16 sec. cor. of secs. 34 and 35.
-
- From the center W 1/16 sec. cor. of sec. 35.
- N. 0° 11' E., on the N - S centerline of the NW 1/4 of sec. 35.
- Over gentle rolling land.
- 20.575** The NW 1/16 sec. cor. of sec. 35.
-
- N. 1° 00' W., beginning new measurement.
- 17.86** The W 1/16 sec. cor. of secs. 26 and 35.
-
- Dependent Resurvey of the Subdivision of Section 36,
T. 7 S., R. 20 E., Salt Lake Meridian, Utah
-
- From the 1/4 sec. cor. of secs. 31 and 36, on the E. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. as described in the official record of the 1950 resurvey of sec. 36, T. 7 S., R. 20 E.
- N. 89° 10' W., on the E - W centerline of sec. 36.
- Over rolling land.
- 19.79** Point for the center E 1/16 sec. cor. of sec. 36, at proportionate distance; there is no remaining evidence of the original corner.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 36,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C $\frac{E \ 1/16}{S36}$ C
1988

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.

- 39.58** Point for the center 1/4 sec. cor. of sec. 36, at proportionate distance, falls in bottom of deep wash and is unsafe to monument; there is no remaining evidence of the original corner.

Asc. over steep clay.

- 41.58** Point selected for the witness cor. to the center 1/4 sec. cor. of sec. 36.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 3 1/2 ft. base, to top of brass cap mkd.

WC
T7S R20E
C 1/4 S36 →
1988

- 79.16** The 1/4 sec. cor. of secs. 35 and 36.

From the S 1/16 sec. cor. of secs. 31 and 36, on the E. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.

S 1/16
S36 | S31
1950

There is no record of this cor. being set, but is accepted as the cor.

N. 89° 01' W., on the E - W centerline of the S 1/2 of sec. 36.

Over gentle rolling land.

- 19.965** Point for the SE 1/16 sec. cor. of sec. 36, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 36,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH

CHAINS

SE 1/16 S36
1988

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

39.93 Point for the center S 1/16 sec. cor. of sec. 36, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C
S 1/16 | S36
C
1988

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

Cor. is located on steep N slope of spur.

79.86 The S 1/16 sec. cor. of secs. 35 and 36.

From the N 1/16 sec. cor. of secs. 31 and 36, on the E. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd. as described in the official record of the 1950 resurvey of sec. 36, T. 7 S., R. 20 E.

N. 88° 31' W., on the E - W centerline of the N 1/2 of sec. 36.

Over rolling land.

39.27 Point for the center N 1/16 sec. cor. of sec. 36, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C
N 1/16 | S36
C
1988

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.

78.54 The N 1/16 sec. cor. of secs. 35 and 36.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 36,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH**

CHAINS

From the 1/4 sec. cor. of secs. 1 and 36, on the S. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. as described in the official record of the 1950 resurvey of sec. 36, T. 7 S., R. 20 E.

N. 0° 16' E., on the N - S centerline of sec. 36.

Over rolling land.

18.87 The center S 1/16 sec. cor. of sec. 36.

N. 0° 12' E., beginning new measurement.

20.885 True point for the center 1/4 sec. cor. of sec. 36.

N. 0° 18' E., beginning new measurement.

20.395 The center N 1/6 sec. cor. of sec. 36.

N. 0° 30' E., beginning new measurement.

20.83 The 1/4 sec. cor. of secs. 25 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. as described in the official record of the 1950 resurvey of sec. 36, T. 7 S., R. 20 E.

From the SE 1/16 sec. cor. of sec. 36.

N. 0° 17' W. on the N - S center line of the SE 1/4 of sec. 36.

20.94 The center E 1/16 sec. cor. of sec. 36.

Meanders of the Green River, Section 25,
T. 7 S., R. 20 E., Salt Lake Meridian, Utah

From true point for the meander cor. of secs. 25 and 30, on the E. bdy. of the Tp., and on the right bank of the Green River, from which the witness meander cor., bears S. 0° 09' W., 1.00 ch. dist.

MEANDERS OF THE GREEN RIVER, SECTION 25,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH

CHAINS

An iron post, 2 ins. diam., firmly set, projecting 3 ins. above ground, set and mkd. as described in the official record of the 1950 dependent resurvey of the W. bdy. of T. 7 S., R. 21 E.

Thence, upstream with meanders of the right bank of the river, in sec. 25; over bottom land, along a well defined cutbank, 4 to 8 ft. high, through heavy brush.

N. 88° 31' W., 6.36 chs.

N. 79° 33' W., 3.12 chs.

N. 83° 31' W., 4.55 chs.

N. 75° 48' W., 7.15 chs.

N. 61° 27' W., 2.50 chs.

N. 57° 29' W., 2.84 chs.

N. 52° 33' W., 4.05 chs.

N. 59° 46' W., 7.03 chs.

N. 50° 22' W., 6.12 chs.

N. 46° 04' W., 5.72 chs.

N. 44° 07' W., 2.77 chs.

N. 43° 53' W., 3.15 chs.

N. 40° 20' W., 2.08 chs.

N. 34° 59' W., 2.37 chs.

N. 28° 50' W., 3.62 chs.

N. 21° 34' W., 1.93 chs.

N. 12° 23' W., 2.55 chs.

N. 20° 10' W., 1.54 chs.

N. 5° 40' E., 3.34 chs.

N. 0° 37' W., 5.96 chs.

N. 47° 12' W., 1.09 chs.

True point for the meander cor. of secs. 24 and 25, hereinbefore described.

MEANDERS OF THE GREEN RIVER, SECTION 25,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From true point for the meander cor. of secs. 24 and 25, on the N. bdy. of sec. 25, and the left bank of the Green River, hereinbefore described.

Thence, downstream with the meanders of the left bank of the river, in sec. 25; in bottom land, along a well defined cutbank, 6 to 12 ft. high, through heavy brush.

S. 2° 32' E., 0.72 chs.

S. 9° 27' W., 3.48 chs.

S. 3° 44' E., 6.93 chs.

S. 23° 58' E., 3.29 chs.

S. 33° 13' E., 7.06 chs.

S. 41° 49' E., 5.11 chs.

S. 57° 15' E., 9.09 chs.

S. 66° 20' E., 3.83 chs.

S. 72° 02' E., 8.25 chs.

S. 78° 13' E., 2.77 chs.

S. 83° 05' E., 4.91 chs.

N. 87° 00' E., 10.12 chs.

True point for the meander cor. of secs. 25 and 30, on the E. bdy. of the Tp. and on the left bank of the Green River, from which the witness meander cor., bears N. 0° 09' E., 0.21 chs. dist.

An iron post, 2 ins. diam., firmly set, projecting 2 ins. above ground, set and mkd. as described in the official record of the 1950 dependent resurvey of the W. bdy. of T. 7 S., R. 21 E.

Meanders of the Green River, Section 24,
T. 7 S., R. 20 E., Salt Lake Meridian, Utah

From the true point for the meander cor. of secs. 24 and 25, on the right bank of the Green River.

Thence, upstream with meanders of the right bank of the river, in sec. 24; over bottom land, along a well defined cutbank, 3 to 10 ft. high, through heavy brush.

MEADERS OF THE GREEN RIVER, SECTION 24,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 4° 03' W., 5.85 chs.

N. 13° 17' E., 8.17 chs.

N. 3° 14' E., 2.86 chs.

N. 12° 24' W., 2.11 chs.

N. 12° 45' E., 5.92 chs.

N. 24° 26' E., 6.44 chs.

N. 62° 32' E., 12.42 chs.

N. 63° 32' E., 13.64 chs.

At 5.99 chs., the special meander cor. of sec. 24,
hereinbefore described.

N. 17° 59' E., 2.32 chs.

N. 39° 45' E., 2.47 chs.

N. 68° 34' E., 4.43 chs.

N. 89° 23' E., 12.07 chs.

N. 87° 20' E., 7.84 chs.

The meander cor. of secs. 19 and 24, on the E. bdy.
of the Tp., hereinbefore described.

From the true point for the meander cor. of secs. 19 and 24, on the E. bdy. of the
Tp., and on the left bank of the Green River, from which the witness meander cor.
bears S. 0° 09' W., 0.30 chs. dist.

An iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground,
set and mkd. as described in the official record of the dependent resurvey
of the W. bdy. of T. 7 S., R. 21 E., in 1950.

Thence, downstream with the meanders of the left bank of the river, in sec. 24; over
bottom land, along a well defined cutbank, 5 to 10 ft. high, through sparsely
scattered brush.

S. 88° 54' W., 7.81 chs.

S. 67° 30' W., 11.10 chs.

MEADERS OF THE GREEN RIVER, SECTION 24,
T. 7 S., R. 20 E., SALT LAKE MERIDIAN, UTAH

CHAINS

S. 69° 56' W., 3.26 chs.

S. 63° 17' W., 4.73 chs.

S. 51° 07' W., 5.52 chs.

S. 44° 05' W., 10.44 chs.

S. 31° 09' W., 4.84 chs.

S. 26° 23' W., 7.73 chs.

S. 29° 20' W., 3.78 chs.

S. 21° 36' W., 1.79 chs.

True point for the meander cor. of secs. 24 and 25.

General Description

The area resurveyed and subdivided in T. 7 S. R. 20 E., varies with upland basins, bottoms, lakes, rivers, and streams. Pelican Lake is located primarily in secs. 20, 21, 28, and 29, and the Green River flows through secs. 24 and 25. The elevation range from a low of 4660 ft. at the SE cor. of sec. 36 to a high of 5180 ft. in the NE 1/4 of sec. 6.

The soil is somewhat sandy throughout the entire township. The vegetation consists of sagebrush, juniper, cottonwoods, willows, and native grasses.

The general drainage pattern is to the SE into Pelican Lake and the Green River. The area is used for grazing with some irrigated pasture and farm lands. The closest towns are Ouray, 5 miles south and Randlett, 5 miles west of the township.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Gregg Ostergaard	Surveying Technician
Milbert H. Krohn	Cadastral Surveyor
Merrill Cazier	Survey Aid

CERTIFICATE OF SURVEY

I, *Jerry L. Thomas, Cadastral Surveyor*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *22nd* day of *January, 1988*, I have *dependently resurveyed the Uintah Indian Reservation between mile posts 3 and 7, a portion of the south boundary, the north 1/2 mile of the east boundary of section 24, all of the west boundary, all of the north boundary, and most of the subdivisional lines, surveyed the subdivision of certain sections and the meander lines of the Green River through sections 24 and 25 in T. 7 S., R. 20 E.,*

of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

August 12, 1991

Date

Jerry L. Thomas

(Cadastral Surveyor)

Date

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of the Uintah Indian Reservation between mile posts 3 and 7, a portion of the south boundary, the north 1/2 mile of the east boundary of section 24, all of the west boundary, all of the north boundary, and most of the subdivisional lines, the survey of the subdivision of certain sections and the meander lines of the Green River through sections 24 and 25 in T. 7 S., R. 20 E., Salt Lake Meridian, Utah,*

executed by *Jerry L. Thomas, Cadastral Surveyor*

having been critically examined and found correct, are hereby approved.

August 15, 1991

Date

Donald A. Buhler

(Chief Cadastral Surveyor, Utah State Office)