

THE SUBDIVISION OF SECTION 6,
T. 12 S., R. 14 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T12S R14E
C 1/4 S6
1991

Corner is located on steep broken southwest slope.

80.854 The 1/4 section corner of section 6 only, as described in the concurrent resurvey of the south boundary of T. 11 S., R. 14 E., Group No. 750.

From the 1/4 section corner of sections 5 and 6.

N. 89° 45.6' W., on the E-W center line of section 6.

20.041 Point for the center E 1/16 section corner of section 6.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 17 ins. in the ground to bedrock, and in a mound of stone to top, with aluminum cap marked:

T12S R14E
C $\frac{E\ 1/16}{S6}$ C
1991

Corner is located on steep broken southeast slope.

40.082 The center 1/4 section corner of section 6.

77.868 The 1/4 section corner of section 6 only, hereinbefore described.

From the E 1/16 section corner of sections 6 and 7.

N. 0° 06.9' W., on the N-S center line of the SE 1/4 of section 6.

19.52 Point selected for the witness SE 1/16 section corner of section 6.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

W C
T12S R14E
SE 1/16 S6
1991

20.32 True point for the SE 1/16 section corner of section 6, falls in bottom of wash, drains southeast.

THE SUBDIVISION OF SECTION 6,
T. 12 S., R. 14 E., SALT LAKE MERIDIAN, UTAH

CHAINS
40.64

The center E 1/16 section corner of section 6.

From the S 1/16 section corner of sections 5 and 6.

N. 89° 33.1' W., on the E-W center line of the SE 1/4 of section 6.

20.069 True point for the SE 1/16 section corner of section 6.

40.138 The point for the center S 1/16 section corner of section 6.

The Subdivision of Section 7,
T. 12 S., R. 14 E., Salt Lake Meridian, Utah

From the 1/4 section corner of section 7 only, on the south boundary.

N. 0° 32.5' W., on the N-S center line of section 7.

20.184 Point for the center S 1/16 section corner of section 6.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T12S R14E
C
S 1/16 | S7
C
1991

Corner is located on steep north slope, in thick timber.

40.368 Point for the center 1/4 section corner, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R14E
C 1/4 S7
1991

Set a steel fence post alongside the aluminum post.

Corner is located on nearly level bottom land, 60 lks. distance, N. of Nine Mile Creek, flows northeast.

60.551 Point for the center N 1/16 section corner of section 7.

THE SUBDIVISION OF SECTION 7,
T. 12 S., R. 14 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 9 ins. in the ground to bedrock, and in a mound of stone, to top of aluminum cap marked:

T12S R14E
C
N 1/16 | S7
C
1991

Corner is located on broken southeast slope.

80.734 The 1/4 section corner of sections 6 and 7.

From the 1/4 section corner of sections 7 and 8.

N. 88° 43.8' W., on the E-W center line of section 7.

19.573 Point selected for the witness center E 1/16 section corner of section 7.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone, to top of aluminum cap marked:

T12S R14E
C $\frac{E\ 1/16}{S7}$ C
1991

Corner is located on steep broken northwest slope.

19.873 True point for the center E 1/16 section corner falls on a small ledge.

39.746 The center 1/4 section corner of section 7.

59.618 Point for the center W 1/16 section corner of section 7, falls on a large boulder 5x5x11 ft.

Drill 8 ins. hole for rebar with aluminum cap marked:

T12S R14E
C $\frac{W\ 1/16}{S7}$ C
1991

Corner is located in rolling sagebrush covered with bottom lands.

77.204 The 1/4 section corner of sections 7 and 12, hereinbefore described.

THE SUBDIVISION OF SECTION 7,
T. 12 S., R. 14 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the center E 1/16 section corner of section 7.

N. $0^{\circ} 51.8'$ E., on the N-S center line of the NE 1/4 of section 7.

20.290 Point for the NE 1/16 section corner of section 7, at intersection with the E-W center line of the NE 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 17 ins. in the ground to bedrock, and in a collar of stone, with aluminum cap marked:

T12S R14E
NE 1/16 S7
1991

Corner is located in rolling bottom land, approximately 25 lks. distance, E of underground gas line, bears NE and SW.

40.580 The E 1/16 section corner of sections 6 and 7.

From the N 1/16 section corner of sections 7 and 8.

N. $89^{\circ} 02.2'$ W., on the E-W center line of the NE 1/4 of section 7.

19.984 The NE 1/16 section corner of section 7.

39.968 The center N 1/16 section corner of section 7.

From the E 1/16 section corner of section 7 only, on the south boundary.

N. $0^{\circ} 51.8'$ E., on the N-S center line of the SE 1/4 of section 7.

20.291 Point for the SE 1/16 section corner of section 7, at intersection with the E-W center line of the SE 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, with aluminum cap marked:

T12S R14E
SE 1/16 S7
1991

Corner is located on northwest slope, near top of ridge, bears northeast and southwest.

40.581 The center E 1/16 section corner of section 7.

THE SUBDIVISION OF SECTION 7,
T. 12 S., R. 14 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the S 1/16 section corner of section 7 only, on the east boundary.

N. 88° 24.8' W., on the E-W center line of the SE 1/4 of section 7.

19.761 The SE 1/16 section corner of section 7.

39.522 The center S 1/16 section corner of section 7.

From the W 1/16 section corner of section 7 only, on the south boundary.

N. 0° 12.9' E., on the N-S center line of the SW 1/4 of section 7.

20.078 Point for the SW 1/16 section corner of section 7, at intersection with the E-W center line of the SW 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone to top, with aluminum cap marked:

T12S R14E
SW 1/16 S7
1991

Corner is located on steep north slope in dense undergrowth.

40.155 The center W 1/16 section corner of section 7.

From the center S 1/16 section corner of section 7.

N. 88° 25.2' W., on the E-W center line of the SW 1/4 of section 7.

19.761 The SW 1/16 section corner of section 7.

37.297 The S 1/16 section corner of sections 7 and 12.

From the center W 1/16 section corner of section 7, heretofore described.

N. 0° 12.9' E., on the N-S center line of the NW 1/4 of section 7.

20.076 Point for the NW 1/16 section corner of section 7, at intersection with the E-W center line of the NW 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone to top, with aluminum cap marked:

THE SUBDIVISION OF SECTION 7,
T. 12 S., R. 14 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T12S R14E
NW 1/16 S7
1991

Corner is located on a steep broken south slope.

40.152 The W 1/16 section corner of sections 6 and 7.

From the center N 1/16 section corner of section 7.

N. $89^{\circ} 02.2' W.$, on the E - W center line of the NW 1/4 of section 7.

19.984 The NW 1/16 section corner of section 7.

37.620 The Point for the N 1/16 section corner of sections 7 and 12, heretofore described.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Gail E. Reynolds	Cadastral Surveyor
Steven Oatman	Surveying Technician
Shawn Peterson	Surveying Technician
Shannon Serre	Survey Aid


CERTIFICATE OF SURVEY

I, *Ferrel D. Reynolds, Cadastral Surveyor*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *17th day of May, 1990*, I have *dependently resurveyed a portion of the west boundary, a portion of the subdivisional lines and the subdivision of sections 3, 4, 5, 6, and 7, in Township 12 South, Range 14 East,*

of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

September 26, 1995

Date


(Cadastral Surveyor)

Date

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah


The foregoing field notes of the *dependent resurvey of a portion of the west boundary, a portion of the subdivisional lines and the subdivision of sections 3, 4, 5, 6, and 7, Township 12 South, Range 14 East, Salt Lake Meridian, Utah,*

executed by *Ferrel D. Reynolds, Cadastral Surveyor*

having been critically examined and found correct, are hereby approved.

September 28, 1995

Date


(Chief, Cadastral Surveyor for Utah)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF
THE DEPENDENT RESURVEY OF
A PORTION OF THE SUBDIVISIONAL LINES
AND THE
SUBDIVISION OF CERTAIN SECTIONS
IN
TOWNSHIP 12 SOUTH, RANGE 12 EAST

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Jerry L. Thomas
Cadastral Surveyor

Under special instructions dated *May 31, 1990*, approved *May 31, 1990*, which provided for the surveys included under Group Number *751*, and assignment instructions dated *August 6, 1990*.

Survey commenced *July 2, 1991*

Survey completed *September 12, 1991*

INDEX DIAGRAM

Township 12 South , Range 12 East

6	5	4	3	2	1
7	8	9	10	11	12 6
18	17	16	15	14 4 11	13 4
19	20	21	22 9 14	23 3 9	24 3
30	29	28 12	27 7 11	26 2 6	25
31	32	33	34	35	36

The Survey of the Subdivision of Section 13.....Page 15

The Survey of the Subdivision of Section 23.....Page 16

The Survey of the Subdivision of Section 24.....Page 17

The Survey of the Subdivision of Section 26.....Page 20

The Survey of the Subdivision of Section 27.....Page 22

TOWNSHIP 12 SOUTH, RANGE 12 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

The following field notes describe the dependent resurvey of a portion of the subdivisional lines, and the subdivision of certain sections in Township 12 South, Range 12 East, Salt Lake Meridian, Utah.

History of Surveys

	<u>Surveyed by</u>		<u>Retr. or Resurveyed by</u>	
<u>NORTH BOUNDARY</u>				
All	A.D. Ferron	1885	Miller and Byergo	1919
<u>SOUTH BOUNDARY</u>				
All	A.D. Ferron	1885	J.R. Stewart	1902
<u>EAST BOUNDARY</u>				
Portion	A.D. Ferron	1878		
Portion	A.D. Ferron	1885	A.D. Ferron	1885
All			R. Gentry	1914
<u>WEST BOUNDARY</u>				
Portion	A.D. Ferron	1878	A.D. Ferron	1885
<u>SUBDIVISION</u>				
Portion	J.R. Stewart	1902		

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 751, dated May 31, 1990.

The directions of lines were determined by hour angle observations of the sun and Polaris, carried forward by sustained angulation. Distances were determined by electronic measurement.

Preliminary to the resurvey the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line notes are given herein.

The geographic position of the southwest corner of section 27, as determined by a tie made to U.S. Geological Survey triangulation station "MYRTLE" is as follows:

Latitude $39^{\circ} 44' 21.67''$ N. Longitude $110^{\circ} 34' 27.20''$ W.
N.A.D. 1927

TOWNSHIP 12 SOUTH, RANGE 12 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

The mean magnetic declination, as projected from the U.S. Geological Survey Magnetic Declination Map of 1985, is $13\ 1/2^\circ$ E.

Dependent Resurvey of a Portion of the Subdivisional Line,
T. 12 S., R. 12 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by A. D. Ferron in 1891

Beginning at the corner of sections 25, 26, 35, and 36, monumented with a sandstone, 16x12x6 ins., firmly set, projecting 10 ins. above ground, dimly marked 1 notch on the S and E edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R12E	
S26	S25
S35	S36
1991	

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone west of the corner.

N. $0^\circ\ 35'$ W., between sections 25 and 26.

Over rolling mountainous land.

39.66 Point for the 1/4 section corner of sections 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

T12S R12E	
1/4	
S26	S25
1991	

79.32 Point for the corner of sections 23, 24, 25, and 26, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 12 S., R. 12 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T12S R12E

S23	S24
S26	S25

 1991

Raise a mound of stone west of the corner.

Corner is located 1.50 chs. S of Nine Mile Creek.

From the 1/4 section corner of sections 24 and 25, marked by a sandstone boulder 5x4x3 ft. above ground, marked 1/4 on the north face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, underneath the 1/4 mark, with aluminum cap marked:

T12S R12E
 1/4

S24
S25

 1991

Raise a mound of stone north of the corner.

N. 88° 49' W., between sections 24 and 25.

Over rolling mountainous land.

40.10 The corner of sections 23, 24, 25, and 26.

N. 0° 57' E., between sections 23 and 24.

Over mountainous land.

5.50 Nine Mile road, bears E and W.

39.66 Point for the 1/4 section corner of sections 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R12E
 1/4

S23	S24
-----	-----

 1991

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 12 S., R. 12 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Raise a mound of stone west of the corner.

59.49 Point for the N 1/16 section corner of sections 23 and 24, not monumented.

79.32 Point for the section corner of sections 13, 14, 23, and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R12E	
S14	S13
S23	S24
1991	

Raise a mound of stone west of the corner.

From the corner of sections 13, 18, 19, and 24, on the east boundary of the township, set and marked as described in the concurrent resurvey of the West boundary of T. 12 S., R. 13 E.

S. 88° 39' W., between sections 13 and 24.

Over mountainous land.

0.75 Nine Mile road, bears NE and SW.

20.015 Point for the E 1/16 section corner of sections 13 and 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

E 1/16	S13
	S24
	1991

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of corner.

40.03 Point for the 1/4 section corner of sections 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 12 S., R. 12 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T12S R12E

1/4 S13
 S24
 1991

Raise a mound of stone north of the corner.

60.045 Point for the W 1/16 section corner of sections 13 and 24, not monumented.

80.06 The corner of sections 13, 14, 23, and 24.

N. 0° 25' E., between sections 13 and 14.

Over mountainous land.

39.66 Point for the 1/4 section corner of sections 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R12E

1/4
S14 | S13
1991

Raise a mound of stone west of the corner.

79.32 Point for the section corner of sections 11, 12, 13, and 14, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R12E

S11 | S12
S14 | S13
1991

Raise a mound of stone west of the corner.

From this corner point, the 1/4 section corner of sections 11 and 14, bears S. 89° 30' W., 39.455 chs. distance, monumented with a sandstone, 10x10x6 ins., firmly set, projecting 5 ins. above ground, and dimly marked 1/4 on the N face, with a mound of stone to the north.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 12 S., R. 12 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R12E
1/4 S11
 S14
 1991

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone north of the corner.

From the same corner point, the corner of sections 1, 2, 11, and 12, bears N. 0° 21' W., 79.32 chs. distance, monumented with a sandstone 24x14x14 ins., firmly set, projecting 14 ins. above ground, plainly marked 5 notches on the S, and 1 notch on the E edges, from which the original bearing trees

A pinon, 16 ins. diam., bears S. 26° E., 105 lks. dist.,
marked S12.

The remaining bearing tree has fallen over and is badly decayed.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R12E
S2 | S1
S11 | S12
1991

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone west of the corner.

This control line was fully retraced and a diligent search was made for intervening corners, none of which were found.

From the corner of sections 7, 12, 13, and 18, on the East boundary of the township, set and marked as described in the concurrent resurvey of the West boundary of T. 12 S., R. 13 E.

N. 89° 10' W., between sections 12 and 13.

Over mountainous land.

36.00

Minnie Maud road, bears NW and SE.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 12 S., R. 12 E., SALT LAKE MERIDIAN, UTAH

CHAINS
39.69

Point for the 1/4 section corner of sections 12 and 13, at intersection of fences extending S, W and NW. This position is harmoniously related to identified original corners, and is accepted as the best available evidence of the original corner position.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R12E
1/4 S12
 S13
 1991

Raise a mound of stone north of the corner.

Thence, S. 85° 57' W., beginning new measurement.

Along bottom of Minnie Maud Creek.

39.82

The corner of sections 11, 12, 13, and 14.

From the corner of sections 25, 26, 35, and 36.

N. 89° 53' W., between sections 26 and 35.

Over mountainous land; ascend over steep E slope.

40.19

True point for the 1/4 section corner of sections 26 and 35, at proportionate distance, falls on steep slope and cannot be monumented; there is no remaining evidence of the original corner; falls on steep slope, where it is impracticable to establish a permanent monument.

40.285

Point selected for the witness corner to the 1/4 section corner of sections 26 and 35.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

WC
T12S R12E
1/4 S26 →
 S35
 1991

Raise a mound of stone north of the corner.

60.285

Point for the W 1/16 section corner of sections 26 and 35.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 12 S., R. 12 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

W 1/16 $\frac{S26}{S35}$
1991

Raise a mound of stone north of the corner.

80.38

The corner of sections 26, 27, 34, and 35, monumented with a sandstone 10x8x6 ins., firmly set, projecting 6 ins. above ground, marked 1 notch on the S, and 2 notches on the E edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R12E
 $\frac{S27}{S34} \mid \frac{S26}{S35}$
1991

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone west of the corner.

N. 0° 34' W., between sections 26 and 27.

Over mountainous land.

19.89

Point for the S 1/16 section corner of sections 26 and 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

S 1/16
 $\frac{S27}{S34} \mid \frac{S26}{S35}$
1991

Raise a mound of stone west of the corner.

34.50

Nine Mile road, bears NE and SW.

39.78

Point for the 1/4 section corner of sections 26 and 27, at proportionate distance; there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 12 S., R. 12 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R12E
1/4
S27 | S26
1991

Raise a mound of stone west of the corner.

59.67 Point for the N 1/16 section corner of sections 26 and 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

N 1/16
S27 | S26
1991

Raise a mound of stone west of the corner.

79.56 Point for the corner of sections 22, 23, 26, and 27, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R12E
S22 | S23
S27 | S26
1991

Raise a mound of stone west of the corner.

From the corner of sections 23, 24, 25, and 26.

N. 89° 43' W., between sections 23 and 26.

Over mountainous land; along bottom of Nine Mile Canyon.

25.00 Nine Mile road, bears NE and SW.

40.19 Point for the 1/4 section corner of sections 23 and 26, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 12 S., R. 12 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T12S R12E

1/4 $\frac{S23}{S26}$
1991

Raise a mound of stone north of the corner.

60.285 Point for the W 1/16 section corner of sections 23 and 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

W 1/16 $\frac{S23}{S26}$
1991

Raise a mound of stone north of the corner.

Corner is located 20 lks. south of wash in the bottom of Indian Canyon.

80.38 The corner of sections 22, 23, 26, and 27.

N. 1° 06' E., between sections 22 and 23.

Over mountainous land.

39.78 True point for the 1/4 section corner of sections 22 and 23, at proportionate distance, falls on edge of sandstone boulder and cannot be monumented; there is no remaining evidence of the original corner, falls on edge of sandstone boulder, where it is impracticable to establish a permanent monument; there is no remaining evidence of the original corner.

40.33 Point selected for the witness corner to the 1/4 section corner of sections 22 and 23.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

WC
T12S R12E
1/4
S22 ↓ S23
1991

Raise a mound of stone west of the corner.

79.56 Point for the corner of sections 14, 15, 22, and 23, at proportionate distance; there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 12 S., R. 12 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R12E

S15	S14
S22	S23

 1991

Raise a mound of stone west of the corner.

From this corner point, the corner of sections 15, 16, 21, and 22, bears S. 89° 50' W., 80.02 chains distance, monumented with a sandstone 30x12x6 ins., firmly set, projecting 20 ins. above ground, and dimly marked, with a scattered mound of stone to the west.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R12E

S16	S15
S21	S22

 1991

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone west of the corner.

From this same corner point, the 1/4 section corner of sections 10 and 11, bears N. 0° 57' E., 119.32 chs. distance, monumented with a sandstone 18x10x4 ins., firmly set, projecting 10 ins. above ground, plainly marked 1/4 on the W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R12E
 1/4

S10	S11
-----	-----

 1991

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone west of the corner.

These control lines were fully retraced and a diligent search was made for intervening corners, none of which were found.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 12 S., R. 12 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the corner of sections 13, 14, 23, and 24.

N. $89^{\circ} 34'$ W., between sections 14 and 23.

Over mountainous land.

40.06 Point for the 1/4 section corner of sections 14 and 23, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T12S R12E
1/4	$\frac{S14}{S23}$
	1991

Raise a mound of stone north of the corner.

80.12 The corner of sections 14, 15, 22, and 23.

From the corner of sections 26, 27, 34, and 35.

S. $89^{\circ} 59'$ W., between sections 27 and 34.

Over mountainous land.

40.42 The 1/4 section corner of sections 27 and 34, monumented with a sandstone 16x10x8 ins., firmly set, projecting 10 ins. above ground, and plainly marked 1/4 on the N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T12S R12E
1/4	$\frac{S27}{S34}$
	1991

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone north of the corner.

N. $89^{\circ} 55'$ W., beginning new measurement.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 12 S., R. 12 E., SALT LAKE MERIDIAN, UTAH

CHAINS
40.52

The corner of sections 27, 28, 33, and 34, monumented with a sandstone 21x19x10 ins., firmly set, projecting 12 ins. above ground, and plainly marked 1 notch on the S, and 3 notches on the E edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R12E	
S28	S27
S33	S34
1991	

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone west of the corner.

From this corner, U.S. Geological Survey triangulation station "MYRTLE", bears N. 44° 12' 03" W., 178.571 chs. distance.

N. 0° 03' W., between sections 27 and 28.

Over rolling land.

7.00 Nine Mile road, bears E and W.

19.855 Point for the S 1/6 section corner of sections 27 and 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with aluminum cap marked:

S 1/16	
S28	S27
1991	

39.71 Point for the 1/4 section corner of sections 27 and 28, at proportionate distance, falls in deep ravine and is unsafe to monument; there is no remaining evidence of the original corner, falls in deep ravine, where it is impracticable.

40.21 Point selected for the witness corner to the 1/4 section corner of sections 27 and 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 12 S., R. 12 E., SALT LAKE MERIDIAN, UTAH

CHAINS

WC
T12S R12E
1/4
S28 ↓ S27
1991

Raise a mound of stone west of the corner.

59.565 Point for the N 1/16 section corner of sections 27 and 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

N 1/16
S28 | S27
1991

Raise a mound of stone west of the corner.

79.42 Point for the corner of sections 21, 22, 27, and 28, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

T12S R12E
S21 | S22
S28 | S27
1991

Raise a mound of stone west of the corner.

From this corner point, the corner of sections 20, 21, 28, and 29, bears N. 89° 22' W., 80.55 chains distance, monumented with a sandstone 20x10x10 ins., firmly set, projecting 14 ins. above ground, plainly marked 2 notches on the S, and 4 notches on the E edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R12E
S20 | S21
S29 | S28
1991

Deposit the marked stone alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 12 S., R. 12 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Raise a mound of stone west of the corner.

From this same corner point, the corner of sections 15, 16, 21, and 22, hereinbefore described, bears N. $1^{\circ} 14'$ E., 79.44 chains distance.

These control lines were fully retraced and a diligent search was made for intervening corners, none of which were found.

From the corner of sections 22, 23, 26, and 27.

S. $89^{\circ} 56'$ W., between sections 22 and 27.

Over mountainous land.

20.045 Point for the E 1/16 section corner of sections 22 and 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

E 1/16 $\frac{S22}{S27}$
1991

Raise a mound of stone north of the corner.

40.09 Point for the 1/4 section corner of sections 22 and 27, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R12E
1/4 $\frac{S22}{S27}$
1991

Raise a mound of stone north of the corner.

60.135 Point for the W 1/16 section corner of sections 22 and 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

W 1/16 $\frac{S22}{S27}$
1991

Raise a mound of stone north of the corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 12 S., R. 12 E., SALT LAKE MERIDIAN, UTAH

CHAINS
80.18

The corner of sections 21, 22, 27, and 28.

Survey of the Subdivision of Section 13,
T. 12 S., R. 12 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 13 and 24.

N. 0° 11' E., on the N - S center line of section 13.

Over mountainous land.

19.87

Point for the center S 1/16 section corner of section 13.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

C
S 1/16 | S13
C
1991

Raise a mound of stone west of the corner.

39.74

Point for the center 1/4 section corner of section 13, at intersection with the E - W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R12E
C 1/4 S13
1991

Raise a mound of stone west of the corner.

81.18

The 1/4 section corner of sections 12 and 13.

From the 1/4 section corner of sections 13 and 18, on the East boundary of the township, set and marked as described in the concurrent resurvey of the West boundary of T. 12 S., R. 13 E.

S. 88° 31' W., on the E - W center line of section 13.

Over mountainous land.

SURVEY OF THE SUBDIVISION OF SECTION 13,
T. 12 S., R. 12 E., SALT LAKE MERIDIAN, UTAH

CHAINS
39.92

The center 1/4 section corner of section 13.

79.795

The 1/4 section corner of sections 13 and 14.

From the S 1/16 section corner of sections 13 and 18, on the East boundary of the township, set and marked as described in the concurrent resurvey of the West boundary of T. 12 S., R. 13 E.

S. 88° 35' W., on the E - W center line of the SE 1/4 of section 13.

Over mountainous land.

39.97

The center S 1/16 section corner of section 13.

Survey of the Subdivision of Section 23,
T. 12 S., R. 12 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 23 and 26.

N. 1° 02' E., on the N - S center line of section 23.

Over mountainous land.

39.72

Point for the center 1/4 section corner of section 23, at intersection with the E - W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R12E
C 1/4 S23
1991

Raise a mound of stone west of the corner.

Set a steel fence post alongside the aluminum post.

79.44

The 1/4 section corner of sections 14 and 23.

From the 1/4 section corner of sections 23 and 24.

N. 89° 39' W., on the E - W center line of section 23.

Over mountainous land.

SURVEY OF THE SUBDIVISION OF SECTION 23,
T. 12 S., R. 12 E., SALT LAKE MERIDIAN, UTAH

CHAINS**40.12**

The center 1/4 section corner of section 23.

60.18

Point for the center W 1/16 section corner of section 23.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

$$C \frac{W \ 1/16}{S \ 23} C$$

1991

Raise a mound of stone north of the corner.

80.24

True point for the witness 1/4 section corner of sections 22 and 23.

From the W 1/16 section corner of sections 23 and 26.

N. 1° 04' E., on the N - S center line of the SW 1/4 of section 23.

Over mountainous land.

39.75

The center W 1/16 section corner of section 23.

Survey of the Subdivision of Section 24,
T. 12 S., R. 12 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 24 and 25.

N. 0° 52' E., on the N - S center line of section 24.

Over mountainous land.

17.00

Nine Mile road, bears NE and SW.

40.96

Point for the center 1/4 section corner of section 24, at intersection with the E - W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with aluminum cap marked:

$$T12S \ R12E$$

$$C \ 1/4 \ S24$$

1991

SURVEY OF THE SUBDIVISION OF SECTION 24,
T. 12 S., R. 12 E., SALT LAKE MERIDIAN, UTAH

CHAINS

61.025 Point for the center N 1/16 section corner of section 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with aluminum cap marked:

$$\begin{array}{c} C \\ N \ 1/16 \ | \ S24 \\ C \\ 1991 \end{array}$$

81.09 The 1/4 section corner of sections 13 and 24.

From the 1/4 section corner of section 24 only, on the East boundary of the township, set and marked as described in the concurrent resurvey of the West boundary of T. 12 S., R. 13 E.

S. 89° 19' W., on the E - W center line of section 24.

Over mountainous land.

19.815 Point for the center E 1/16 section corner of section 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

$$\begin{array}{c} C \ \frac{E \ 1/16}{S \ 24} \ C \\ 1991 \end{array}$$

Raise a mound of stone north of the corner.

31.50 Nine Mile road, bears N and S.

39.63 The center 1/4 section corner of section 24.

59.665 Point for the center W 1/16 section corner of section 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

$$\begin{array}{c} C \ \frac{W \ 1/16}{S \ 24} \ C \\ 1991 \end{array}$$

Raise a mound of stone north of the corner.

79.70 The 1/4 section corner of sections 23 and 24.

SURVEY OF THE SUBDIVISION OF SECTION 24,
T. 12 S., R. 12 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the center E 1/16 section corner of section 24.

N. $1^{\circ} 08'$ E., on the N - S center line of the NE 1/4 of section 24.

Over mountainous land.

11.00 Nine Mile road, bears NE and SW.

20.185 Point for the NE 1/16 section corner of section 24, at an intersection with the E - W center line of the NE 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

NE 1/16 S24
1991

Raise a mound of stone west of the corner.

40.37 Point for the E 1/16 section corner of sections 13 and 24.

From the N 1/16 section corner of section 24 only, on the East boundary of the township, set and marked as described in the concurrent resurvey of the West boundary of T. 12 S., R. 13 E.

S. $88^{\circ} 59'$ W., on the E - W center line of the NE 1/4 of section 24.

Over mountainous land.

11.00 Nine Mile road, bears NE and SW.

19.915 The NE 1/16 section corner of section 24.

39.83 The center N 1/16 section corner of section 24.

From the center W 1/16 section corner of section 24.

N. $0^{\circ} 54'$ E., on the N - S center line of the NW 1/4 of section 24.

Over mountainous land.

19.95 Point for the NW 1/16 section corner of section 24, at intersection with the E - W center line of the NW 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

SURVEY OF THE SUBDIVISION OF SECTION 24,
T. 12 S., R. 12 E., SALT LAKE MERIDIAN, UTAH

CHAINS

NW 1/16 S24
1991

Raise a mound of stone west of the corner.

39.90 Point for the W 1/16 section corner of sections 13 and 24.

From the center N 1/16 section corner of section 24.

S. $88^{\circ} 59'$ W., on the E - W center line of the NW 1/4 of section 24.

Over mountainous land.

20.025 The NW 1/16 section corner of section 24, at intersection with the N - S center line.

40.05 Point for the N 1/16 section corner of sections 23 and 24.

Survey of the Subdivision of Section 26,
T. 12 S., R. 12 E., Salt Lake Meridian, Utah

From the true point for the 1/4 section corner of sections 26 and 35.

N. $0^{\circ} 35'$ W., on the N - S center line of section 26.

Over mountainous land.

39.72 Point for the center 1/4 section corner of section 26, at intersection with the E - W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R12E
C 1/4 S26
1991

Raise a mound of stone west of the corner.

59.58 Point for the center N 1/16 section corner of section 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with aluminum cap marked:

SURVEY OF THE SUBDIVISION OF SECTION 26,
T. 12 S., R. 12 E., SALT LAKE MERIDIAN, UTAH

CHAINS

C
N 1/16 | S26
C
1991

66.50 Nine Mile road, bears NE and SW.

79.44 The 1/4 section corner of sections 23 and 26.

From the 1/4 section corner of sections 25 and 26.

N. 89° 48' W., on the E - W center line of section 26.

Over mountainous land.

40.19 The center 1/4 section corner of section 26.

60.285 Point for the center W 1/16 section corner of section 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

C — $\frac{W\ 1/16}{S\ 26}$ — C
1991

Raise a mound of stone north of the corner.

Corner is located on E slope, 10 ft. W of rim of ravine.

70.00 Nine Mile road, bears NE and SW.

80.38 The corner of sections 26 and 27.

From the W 1/16 section corner of sections 26 and 35.

N. 0° 35' W., on the N - S center line of the SW 1/4 of section 26.

Over mountainous land.

39.75 The center W 1/16 section corner of section 26.

N. 0° 35' W., on the N - S center line of the NW 1/4 of section 26.

Over mountainous land.

SURVEY OF THE SUBDIVISION OF SECTION 26,
T. 12 S., R. 12 E., SALT LAKE MERIDIAN, UTAH

CHAINS

- 7.50** Nine Mile road, bears NE and SW.
- 19.87** Point for the NW 1/16 section corner of section 26, at intersection with the E - W center line of the NW 1/4.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:
- NW 1/16 S26
1991
- Raise a mound of stone west of the corner.
- 39.74** The W 1/16 section corner of sections 23 and 26.
-
- From the center N 1/16 section corner of section 26.
- N. 89° 45' W., on the E - W center line of the NW 1/4 of section 26.
- Over mountainous land.
- 8.00** Nine Mile road, bears NE and SW.
- 20.095** The NW 1/16 section corner of section 26.
- 40.19** The N 1/16 section corner of sections 26 and 27.
-
- Survey of the Subdivision of Section 27,
T. 12 S., R. 12 E., Salt Lake Meridian, Utah
-
- From the 1/4 section corner of sections 27 and 34.
- N. 0° 20' W., on the N - S center line of section 27.
- Over mountainous land.
- 7.50** Nine Mile road, bears NE and SW.
- 19.895** Point for the center S 1/16 section corner of section 27.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

SURVEY OF THE SUBDIVISION OF SECTION 27,
T. 12 S., R. 12 E., SALT LAKE MERIDIAN, UTAH

CHAINS

C
S 1/16 | S27
C
1991

Raise a mound of stone west of the corner.

- 39.79** Point for the center 1/4 section corner of section 27, at intersection with the E - W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R12E
C 1/4 S27
1991

Raise a mound of stone west of the corner.

- 59.66** Point for the center N 1/16 section corner of section 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

C
N 1/16 | S27
C
1991

- 79.53** The 1/4 section corner of sections 22 and 27.

From the 1/4 section corner of sections 26 and 27.

S. 89° 59' W., on the E - W center line of section 27.

Over mountainous land.

- 20.13** Point for the center E 1/16 section corner of section 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

C $\frac{E\ 1/16}{S\ 27}$ C
1991

Raise a mound of stone north of the corner.

SURVEY OF THE SUBDIVISION OF SECTION 27,
T. 12 S., R. 12 E., SALT LAKE MERIDIAN, UTAH

CHAINS

- 40.26** The center 1/4 section corner of section 27.
- 60.405** Point for the center W 1/16 section corner of section 27.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a collar of stone to top, with aluminum cap marked:
- $$C \frac{W \ 1/16}{S \ 27} C$$
- 1991
- 80.55** True point for the 1/4 section corner of sections 27 and 28.
-
- From the center E 1/16 section corner of section 27.
- N. 0° 25' W., on the N - S center line of the NE 1/4 of section 27.
- Over mountainous land.
- 18.88** Point selected for the witness corner to the NE 1/16 section corner of section 27.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:
- $$\begin{array}{c} \uparrow \\ WC \\ NE \ 1/16 \ S27 \\ 1991 \end{array}$$
- Raise a mound of stone west of the corner.
- 19.88** True point for the NE 1/16 section corner of section 27, at intersection with the E - W center line of the NE 1/4, falls in wash where it is impracticable to establish a permanent monument.
- 39.76** The E 1/16 section corner of sections 22 and 27.
-
- From the N 1/16 section corner of sections 26 and 27.
- S. 89° 58' W., on the E - W center line of the NE 1/4 of section 27.
- Over mountainous land.
- 20.095** True point for the NE 1/16 section corner of section 27.
- 40.19** The center N 1/16 section corner of section 27.

SURVEY OF THE SUBDIVISION OF SECTION 27,
T. 12 S., R. 12 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the S 1/16 section corner of sections 26 and 27.

S. $89^{\circ} 59'$ W., on the E - W center line of the SE 1/4 of section 27.

Over mountainous land.

19.50 Nine Mile road, bears NE and SW.

40.34 The center S 1/16 section corner of section 27.

From the center W 1/16 section corner of section 27.

N. $0^{\circ} 11'$ W., on the N - S center line of the NW 1/4 of section 27.

Over mountainous land.

19.865 True point for the NW 1/16 section corner of section 27, at intersection with the E - W center line of the NW 1/4, falls in bottom of wash where it is impracticable to establish a permanent monument.

20.615 Point selected for the witness corner to the NW 1/16 section corner of section 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

WC
NW 1/16 S27
1991

Raise a mound of stone west of the corner.

39.73 The W 1/16 section corner of sections 22 and 27.

From the center N 1/16 section corner of section 27.

S. $89^{\circ} 58'$ W., on the E - W center line of the NW 1/4 of section 27.

Over mountainous land.

20.095 True point for the NW 1/16 section corner of section 27.

40.19 The N 1/16 section corner of sections 27 and 28.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Ferrel D. Reynolds	Surveying Technician
Shawn Peterson	Survey Aid
John Forsberg	Survey Aid
Shannon Serre	Survey Aid

CERTIFICATE OF SURVEY

I, *Jerry L. Thomas, Cadastral Surveyor*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *31st day of May, 1990*, I have *dependently resurveyed a portion of the subdivisional lines and subdivided certain sections, in Township 12 South, Range 12 East*,

of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

September 26, 1995

Date



(Cadastral Surveyor)

Date

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah


The foregoing field notes of the *dependent resurvey of a portion of the subdivisional lines and the subdivision of certain sections, Township 12 South, Range 12 East, Salt Lake Meridian, Utah*,

executed by *Jerry L. Thomas, Cadastral Surveyor*

having been critically examined and found correct, are hereby approved.

September 28, 1995

Date



(Chief Cadastral Surveyor for Utah)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF
THE DEPENDENT RESURVEY OF
A PORTION OF THE WEST BOUNDARY,
A PORTION OF THE SUBDIVISIONAL LINES,
AND THE
THE SUBDIVISION OF CERTAIN SECTIONS
IN
TOWNSHIP 12 SOUTH, RANGE 13 EAST

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Jerry L. Thomas
Cadastral Surveyor

Under special instructions dated *May 31, 1990*, approved *May 31, 1990*, which provided for the surveys included under Group Number *751*, and assignment instructions dated *August 6, 1990*.

Survey commenced *August 15, 1990*

Survey completed *July 18, 1991*

INDEX DIAGRAM

Township 12 South , Range 13 East

6	5	4	3	2	1
					8
7	8	9	10	11 7	12
17	16	12	12	9	6
3 18 16	17 13	16 11	15 9	14 5	13
15	14		10	8	4
1 19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

The Survey of the Subdivision of Section 12.....Page 18

The Survey of the Subdivision of Section 13.....Page 20

The Survey of the Subdivision of Section 14.....Page 22

The Survey of the Subdivision of Section 15.....Page 23

The Survey of the Subdivision of Section 17.....Page 25

The Survey of the Subdivision of Section 18.....Page 27

TOWNSHIP 12 SOUTH, RANGE 13 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

The following field notes describe the dependent resurvey of a portion of the west boundary, a portion of the subdivisional lines, and the subdivision of certain sections in Township 12 South, Range 13 East, Salt Lake Meridian, Utah.

History of Surveys

	<u>Surveyed by</u>		<u>Retr. or Resurveyed by</u>	
<u>west boundary</u>				
Portion	A.D. Ferron	1878	A.D. Ferron	1885
All			R. Gentry	1914

SUBDIVISION

Portion	A.D. Ferron	1878		
Portion	R. Gentry	1914	R. Gentry	1914

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 751, dated May 31, 1990.

The directions of lines were determined by hour angle observations of the sun and Polaris, carried forward by sustained angulation. Distances were determined by electronic measurement.

Preliminary to the resurvey the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line notes are given herein.

The geographic position of the northwest corner of section 18, as determined by a tie made to National Geodetic Survey tri-station "Flat" is as follows:

Latitude 39° 46' 58.10 N." Longitude 110° 31' 03.10 W"
N.A.D. 1927

The mean magnetic declination, as projected from the U.S. Geological Survey Magnetic Declination Map of 1985, is 13 1/2° E.

Dependent Resurvey of a Portion of the west boundary,
T. 12 S., R. 13 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by A. D. Ferron in 1878 and
the Resurvey in 1885, and the Resurvey by R. Gentry in 1914

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 12 S., R. 13 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Beginning at the closing corner of sections 19 and 30, monumented with an iron post, 2 ins. diam., in a mound of stone, with brass cap marked as described in the official record.

This point is near edge of steep ledge, and in danger of falling over.

I remove the old iron post marker, and replace with a rebar, 5/8 ins. diam., 18 ins. long, at the exact corner point, in a drill hole, 10 ins. deep, with aluminum cap marked.

		T12S	
		R12E R13E	
S25		S19	C
		S30	C
		1991	

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of corner.

N. 1° 25 E., on the west boundary of section 19.

Over mountainous land; along E slope.

9.83 The corner of sections 24 and 25 only, T. 12 S., R. 12 E., monumented with an iron post, 2 ins. diam., projecting 8 ins. above mound of stone, with brass cap marked as described in the official record.

40.06 Point for the 1/4 section corner of section 19 only, at proportionate distance, based on the 1914 survey plat.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with aluminum cap marked.

		T12S	
		R12E R13E	
		1/4	
		S19	
		1991	

50.44 Point for the 1/4 section corner of section 24 only, T. 12 S., R. 12 E., at proportionate distance; there is no remaining evidence of the iron post marker monumented in 1914.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 12 S., R. 13 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T12S
R12E R13E
1/4 |
S24
1991

Raise a mound of stone W of the corner.

70.745 Point for the N 1/16 section corner of section 24 only, T. 12 S., R. 12 E.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with aluminum cap marked:

T12S
R12E R13E
N 1/16 |
S24
1991

80.12 Point for the 80 1/16 section corner of section 19, at proportionate distance, based on the 1914 survey plat; this point falls in Nine Mile Creek and is unsafe to monument.

80.62 Point selected for the witness corner to the 80 1/16 section corner of section 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

WC
T12S
R12E R13E
↓ 80 1/16
S19
1991

91.05 Point for the corner of sections 13, 18, 19, and 24, at proportionate distance; there is no remaining evidence of the iron post marker set in the 1914 resurvey.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S
R12E R13E
S13 | S18
S24 | S19
1991

Raise a mound of stone W of the corner.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 12 S., R. 13 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From this corner point, right of way fence, bears East 17 lks. dist., and the Nine Mile road bears West, 25 lks. dist.

N. $0^{\circ} 02'$ E., between sections 13 and 18.

Along East edge of Nine Mile road.

4.00 Nine Mile road, bears S. 10° W. and N. 10° E.

19.915 Point for the S 1/16 section corner of sections 13 and 18.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with aluminum cap marked:

T12S
R1E R2E
S 1/16
S13 | S18
1991

39.83 The 1/4 section corner of sections 13 and 18, monumented with an iron post, 1 in. diam., projecting 6 ins. above ground, with brass cap marked as described in the official record.

N. $0^{\circ} 07'$ W., beginning new measurement.

Asc. over SE slope.

19.915 Point for the N 1/16 section corner of sections 13 and 18.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S
R1E R2E
N 1/16
S13 | S18
1991

Raise a mound of stone West of the corner.

22.00 Minnie Maud road, bears SE and W.

39.83 The corner of sections 7, 12, 13, and 18, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap marked as described in the official record.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 12 S., R. 13 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From this corner, U.S.G.S. triangulation station "FLAT", bears N. $24^{\circ} 33' 51''$ W., 218.118 chains distance.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 12 S., R. 13 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by A. D. Ferron in 1878,
and the Resurvey by R. Gentry in 1914

From the corner of sections 13, 18, 19, and 24, east boundary, set and marked as described in the concurrent resurvey of the west boundary of T. 12 S., R. 14 E., under Group No. 750.

N. $88^{\circ} 38'$ W., on the south boundary of section 13.

Over rough mountainous land.

39.24 Point for the 1/4 section corner of section 24 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R13E
1/4 S24
1991

Raise a mound of stone south of the corner.

40.23 The 1/4 section corner of section 13 only, monumented with an iron post, 1 in. diam., projecting 10 ins. above ground, with brass cap marked as described in the official record.

N. $88^{\circ} 16'$ W., beginning new measurement.

38.87 From this point, the closing corner of sections 23 and 24, bears N., 0.025 chs. distance, monumented with an iron post, 2 ins. diam., projecting 14 ins. above ground, with brass cap marked as described in the official record.

39.89 The corner of sections 13 and 14 only, monumented with an iron post, 2 ins. diam., projecting 10 ins. above ground, with brass cap marked as described in the official record.

Reestablishment of the Survey Executed by
A. D. Ferron in 1878

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 12 S., R. 13 E., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0° 25' E., between sections 13 and 14.

Over rough mountainous land.

37.15 Point for the 1/4 section corner of sections 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R13E
1/4
S14 | S13
1991

Raise a mound of stone west of the corner.

55.725 Point for the N 1/16 section corner of sections 13 and 14.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

N 1/16
S14 | S13
1991

Raise a mound of stone west of the corner.

74.30 The corner of sections 11, 12, 13, and 14, monumented with a sandstone 16x10x6 ins., firmly set in a mound of stone, marked 4 notches on the S and 1 notch on the E edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R13E
S11 | S12
S14 | S13
1991

Deposit the marked stone alongside the aluminum post.

There is no remaining evidence of the iron post marker that was monumented at this point in 1914.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 12 S., R. 13 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the corner of sections 7, 12, 13, and 18, on the east boundary of the township, set and marked as described in the concurrent resurvey of the west boundary of T. 12 S., R. 14 E., under Group No. 750.

N. 81° 46' W., between sections 12 and 13.

Over rough mountainous land.

20.165 Point for the E 1/16 section corner of sections 12 and 13, falls in bottom of deep ravine where it is impracticable to establish a permanent monument.

20.665 Point selected for the witness corner to the E 1/16 section corner of sections 12 and 13.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

E 1/16	WC <u>S12</u> S13 → 1991
--------	-----------------------------------

Raise a mound of stone north of the corner.

40.33 Point for the 1/4 section corner of sections 12 and 13, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

1/4	T12S R13E <u>S12</u> S13 1991
-----	--

Raise a mound of stone north of the corner.

60.495 Point for the W 1/16 section corner of sections 12 and 13.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

W 1/16	<u>S12</u> S13 1991
--------	---------------------------

Raise a mound of stone north of the corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 12 S., R. 13 E., SALT LAKE MERIDIAN, UTAH

CHAINS
80.66

The corner of sections 11, 12, 13, and 14.

Reestablishment of the Survey Executed by A. D. Ferron
in 1878, and the Resurvey by R. Gentry in 1914

N. 0° 04' W., between sections 11 and 12.

Over rough and broken land.

0.49 Mountain Fuel gas line, bears E and W.

1.23 Nine Mile road, bears W and curves NE.

19.995 Point for the S 1/16 section corner of sections 11 and 12.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with
aluminum cap marked:

S 1/16
S11 | S12
1991

Raise a mound of stone west of the corner.

39.99 The 1/4 section corner of sections 11 and 12, monumented with an iron post, 1 in.
diam., projecting 14 ins. above ground, with brass cap marked as described in the
official record.

N. 0° 05' E., beginning new measurement.

39.96 The corner of sections 1, 2, 11, and 12, monumented with an iron post, 2 ins. diam.,
projecting 10 ins. above ground, with brass cap marked as described in the official
record.

From the corner of sections 1, 6, 7, and 12, on the east boundary of the Tp., set
and marked as described in the concurrent resurvey of the west boundary of
T. 12 S., R. 14 E., under Group No. 750.

N. 81° 51' W., between sections 1 and 12.

Over rough and broken mountainous land.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 12 S., R. 13 E., SALT LAKE MERIDIAN, UTAH

CHAINS**40.47**

The 1/4 section corner of sections 1 and 12, monumented with an iron post, 1 in. diam., projecting 16 ins. above ground, with brass cap marked as described in the official record.

N. 81° 40' W., beginning new measurement.

40.25

The corner of sections 1, 2, 11, and 12.

From the corner of sections 13 and 14 only.

N. 88° 51' W., on the south boundary of section 14.

Over mountainous land.

38.98

Point for the 1/4 section corner of section 23 only, at midpoint and on the north boundary of section 23.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R13E
1/4 S23
1990

Raise a mound of stone south of the corner.

40.03

The 1/4 section corner of section 14 only, monumented with an iron post, 1 in. diam., projecting 8 ins. above ground, with brass cap marked as described in the official record.

N. 88° 03' W., beginning new measurement.

38.95

From this point, the closing corner of sections 22 and 23, bears S., 0.03 chs. dist., monumented with an iron post, 2 ins. diam., projecting 10 ins. above ground, and marked as described in the official record.

40.01

The corner of sections 14 and 15 only, monumented with an iron post, 2 ins. diam., projecting 10 ins. above ground, with brass cap marked as described in the official record.

N. 0° 05' W., between sections 14 and 15.

Over rough mountainous land.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 12 S., R. 13 E., SALT LAKE MERIDIAN, UTAH

CHAINS
38.83

Point for the 1/4 section corner of sections 14 and 15, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone, 4 1/2 ft. base to top, with aluminum cap marked:

T12S R13E
1/4
S15 | S14
1990

60.75 Nine Mile road, bears E and W.

77.66 The corner of sections 14 and 15 only, monumented with an iron post, 2 ins. diam., projecting 12 ins. above ground, with brass cap marked as described in the official record.

From the corner of sections 11, 12, 13, and 14.

N. 86° 06' W., between sections 11 and 14.

Over rough and broken land; along bottom of Nine Mile Canyon.

26.00 Nine Mile road, bears NE and SW.

39.71 The 1/4 section corner of section 14 only, monumented with an iron post, 1 in. diam., projecting 12 ins. above ground, with brass cap marked as described in the official record.

N. 86° 05' W., beginning new measurement.

0.16 Point selected for the witness corner to the 1/4 section corner of section 11 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone 4 1/2 ft. base to top, with aluminum cap marked:

WC
T12S R13E
← 1/4 S11
1990

0.19 True point for the 1/4 section corner of section 11 only, at proportionate distance, based on the 1914 survey plat, falls on the face of a small ledge where it is impracticable to establish a permanent monument.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 12 S., R. 13 E., SALT LAKE MERIDIAN, UTAH

CHAINS

20.545

Point for the W 1/16 section corner of section 14 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	<u>S11</u>
W 1/16	S14
	1990

Raise a mound of stone north of the corner.

40.08

From this point, the closing corner of sections 10 and 11, bears N., 0.08 chs. distance, monumented with an iron post, 2 ins. diam., projecting 10 ins. above ground, with brass cap marked as described in the official record.

41.09

The corner of sections 14 and 15 only.

From the corner of sections 14 and 15 only, on the north boundary of section 22.

N. 88° 10' W., on the south boundary of section 15.

Over mountainous land.

18.96

Point for the E 1/16 section corner of section 22 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with aluminum cap marked:

<u>E 1/16 S22</u>
1990

20.12

Point for the E 1/16 section corner of section 15 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with aluminum cap marked:

<u>E 1/16 S15</u>
1990

38.98

Point for the 1/4 section corner of section 22 only, at midpoint, and on the north boundary of section 22.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 12 S., R. 13 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T12S R13E

1/4 S22

1991

- 40.24** The 1/4 section corner of section 15 only, monumented with an iron post, 1 in. diam., projecting 15 ins. above ground, with brass cap marked as described in the official record.
-
- N. 88° 33' W., beginning new measurement.
- 38.79** From this point the closing corner of sections 21 and 22 only, bears S., 0.015 chs. distance, monumented with an iron post, 2 ins. diam., projecting 10 ins. above ground, with brass cap marked as described in the official record.
- 40.39** The corner of sections 15 and 16 only, on the South boundary, monumented with an iron post, 2 ins. diam., projecting 12 ins. above ground, with brass cap marked as described in the official record.
-
- N. 0° 08' E., between sections 15 and 16.
- Over rough mountainous land; desc. over steep NE slope.
- 20.29** Point for the S 1/16 section corner of sections 15 and 16.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:
- S 1/16
S16 | S15
1991
- 40.58** Point for the 1/4 section corner of sections 15 and 16, at proportionate distance; there is no remaining evidence of the original corner.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:
- T12S R13E
1/4
S16 | S15
1991
- Raise a mound of stone west of the corner.
- 43.00** Nine Mile road, bears E and W.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 12 S., R. 13 E., SALT LAKE MERIDIAN, UTAH

CHAINS

- 81.16** The corner of sections 15 and 16 only, monumented with an iron post, 2 ins. diam., projecting 10 ins. above ground, with brass cap marked as described in the official record.
-
- From the corner of sections 14 and 15 only, on the south boundary of section 10.
N. 85° 54' W., on the north boundary of section 15.
Over rough mountainous land.
- 39.15** Point for the 1/4 section corner of section 10 only, at mid point, and on the south boundary of section 10.
Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, in a mound of stone, 4 ft. base to top, with aluminum cap marked:
- T12S R13E
1/4 S10
1991
- 40.21** The 1/4 section corner of section 15 only, monumented with an iron pipe, 1 in. diam., projecting 15 ins. above ground, with brass cap marked as described in the official record.
-
- N. 85° 48' W., beginning new measurement.
- 20.15** Point for the W 1/16 section corner of section 15, falls in wash bed, and is unsafe to monument.
- 20.30** Point selected for the witness corner to the W 1/16 section corner of section 15.
Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap marked:
- WC
W 1/16 S15 →
1991
- 39.10** From this point the closing corner of sections 9 and 10, bears N., 0.07 chs. distance, monumented with an iron pipe, 2 ins. diam., projecting 10 ins. above ground, with brass cap marked as described in the official record.
- 40.30** The corner of sections 15 and 16 only.
-
- N. 86° 04' W., on the north boundary of section 16.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 12 S., R. 13 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Over rough mountainous land.

- 38.86** Point for the 1/4 section corner of section 9 only, at mid point, and on the South boundary of section 9.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R13E
1/4 S9
1991

Raise a mound of stone north of the corner.

- 40.22** The 1/4 section corner of section 16 only, monumented with an iron post, 1 in. diam., projecting 12 ins. above ground, with brass cap marked as described in the official record.

The original bearing trees have been destroyed by fire.

N. 85° 44' W., beginning new measurement.

- 38.71** From this point, the closing corner of sections 8 and 9, bears N., 0.14 chs. distance, monumented with an iron post, 2 ins. diam., projecting 12 ins. above ground, with brass cap marked as described in the official record.

- 40.43** The corner of sections 16 and 17 only, monumented with a sandstone 24x12x8 ins., firmly set, projecting 10 ins. above ground, marked 4 notches on the S and E edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R13E
S8
S17 | S16
1991

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone west of the corner

From the corner of sections 16 and 17 only, on the north boundary of section 20, monumented with an iron post, 2 ins. diam., projecting 10 ins. above ground, with brass cap marked as described in the official record.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 12 S., R. 13 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From this corner, the closing corner of sections 20 and 21, monumented with an iron post, 2 ins. diam., projecting 12 ins. above ground, with brass cap marked as described in the official record, bears N. $88^{\circ} 50'$ E., 1.99 chs. dist.

N. $0^{\circ} 01'$ E., between sections 16 and 17.

Over mountainous land.

- 42.33** The 1/4 section corner of sections 16 and 17, determined at intersection of barbed wire fences extending N, S, and W. This position is harmoniously related to identified original corners, and is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R13E
1/4
S17 | S16
1991

Raise a mound of stone west of the corner.

N. $0^{\circ} 02'$ E., beginning new measurement.

- 3.65** Nine Mile road, bears NW and SE.

- 21.10** Point for the N 1/16 section corner of sections 16 and 17.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

N 1/16
S17 | S16
1991

Raise a mound of stone west of the corner.

- 42.20** The corner of sections 16 and 17 only.
-

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 12 S., R. 13 E., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 88° 24' W., on the south boundary of section 17.

- 38.02** Point for the 1/4 section corner of section 20 only, at mid point and on the north boundary of section 20.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R13E
1/4 S20
1991

Raise a mound of stone south of the corner.

- 40.20** The 1/4 section corner of section 17 only, monumented with an iron post, 1 in. diam., projecting 12 ins. above ground, with brass cap marked as described in the official record.

N. 88° 13' W., beginning new measurement.

- 37.83** From this point, the closing corner of sections 19 and 20, bears N., 0.025 chs. distance, monumented with an iron post, 2 ins. diam., projecting 12 ins. above ground, with brass cap marked as described in the official record.

- 40.18** The corner of sections 17 and 18 only, monumented with an iron post, 2 ins. diam., projecting 12 ins. above ground, with brass cap marked as described in the official record.

N. 88° 34' W., on the south boundary of section 18.

Over rough mountainous land.

- 37.68** Point for the 1/4 section corner of section 19 only, at proportionate distance, based on the 1914 survey plat, and on the north boundary of section 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R13E
1/4 S19
1991

Raise a mound of stone south of the corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 12 S., R. 13 E., SALT LAKE MERIDIAN, UTAH

CHAINS
40.26

Point for the 1/4 section corner of section 18 only, monumented with an iron post, 1 in. diam., projecting 10 ins. above ground. The brass cap has been removed and was laying alongside the iron post.

At this point, I replace the old iron post.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R13E
1/4 S18
1991

Raise a mound of stone north of the corner.

N. 88° 12' W., beginning new measurement.

20.105

Point for the W 1/16 section corner of section 18 only, based on the 1878 survey plat.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

W 1/16 S18
1991

Raise a mound of stone north of the corner.

38.10

The corner of sections 13, 18, 19, and 24, on the west boundary of the township, hereinbefore described.

From the corner of sections 17 and 18 only, on the north boundary of section 19.

N. 0° 23' W., between sections 17 and 18.

Over mountainous land.

41.01

Point for the 1/4 section corner of sections 17 and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R13E
1/4
S18 | S17
1991

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 12 S., R. 13 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Raise a mound of stone west of the corner.

47.00 Nine Mile Road, bears E and W.

61.515 Point for the N 1/16 section corner of sections 17 and 18.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with aluminum cap marked:

N 1/16
S18 | S17
1991

82.02 The corner of sections 17 and 18 only, monumented with an iron post, 2 ins. diam., projecting 12 ins. above ground, with brass cap marked as described in the official record.

From the corner of sections 16 and 17 only, on the South boundary of section 8.

S. 89° 40' W., on the north boundary of section 17.

Over rough mountainous land.

38.28 Point for the 1/4 section corner of section 8 only, at mid point and on the south boundary of section 8.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with aluminum cap marked:

T12S R13E
1/4 S8
1991

40.53 The 1/4 section corner of section 17 only, monumented with an iron post, 1 in. diam., projecting 10 ins. above ground, with brass cap marked as described in the official record.

N. 89° 53' W., beginning new measurement.

37.75 From this point, the closing corner of sections 7 and 8, bears N., 0.025 chs. distance, monumented with an iron post, 2 ins. diam., projecting 10 ins. above ground, with brass cap marked as described in the official record.

40.39 The corner of sections 17 and 18 only.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 12 S., R. 13 E., SALT LAKE MERIDIAN, UTAH

CHAINS

S. $89^{\circ} 49'$ W., on the north boundary of section 18.

Over rough mountainous land.

37.31 Point selected for the witness corner to the 1/4 section corner of section 7.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with aluminum cap marked:

WC
T12S R13E
← 1/4 S7
1991

37.36 True point for the 1/4 section corner of section 7, based on the 1914 survey plat, falls near edge of ledge, where it is impracticable to establish a permanent monument.

39.90 The 1/4 section corner of section 18 only, monumented with an iron post, 1 in. diam., projecting 10 ins. above ground, with brass cap marked as described in the official record, from which the original bearing trees

A pinon, 14 ins. diam., bears S. $60 \frac{1}{4}^{\circ}$ E., 35 lks. dist.,
marked 1/4 S18 BT.

A cedar, 9 ins. diam., bears S. $10 \frac{1}{2}^{\circ}$ W., 82 lks. dist.,
marked 1/4 S18 BT.

S. $89^{\circ} 58'$ W., beginning new measurement.

37.90 The corner of sections 7, 12, 13, and 18, on the west boundary of the township, hereinbefore described.

Survey of the Subdivision of Section 12,
T. 12 S., R. 13 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 12 and 13.

N. $0^{\circ} 03'$ W., on the N - S center line of section 12.

Over mountainous land.

19.99 Point for the center S 1/16 section corner of section 12.

SURVEY OF THE SUBDIVISION OF SECTION 12,
T. 12 S., R. 13 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

$$\begin{array}{c} C \\ S \frac{1}{16} \mid S12 \\ C \\ 1991 \end{array}$$

Raise a mound of stone west of the corner.

39.98 Point for the center 1/4 section corner of section 12, at intersection with the E - W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

$$\begin{array}{c} T12S R13E \\ C \frac{1}{4} S12 \\ 1991 \end{array}$$

Raise a mound of stone west of the corner.

Corner is located 35 lks. south of Nine Mile Creek.

45.50 Nine Mile road, bears E and W.

79.89 The 1/4 section corner of sections 1 and 12.

From the 1/4 section corner of sections 7 and 12, on the east boundary of the township, set and marked as described in the concurrent resurvey of the west boundary of T. 12 S., R. 14 E., under Group No. 750.

N. 81° 46' W., on the E - W center line.

Along bottom of Nine Mile Canyon.

20.20 Point for the center E 1/16 section corner of section 12.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

$$\begin{array}{c} C \frac{E \frac{1}{16}}{S12} C \\ 1991 \end{array}$$

Raise a mound of stone north of the corner.

SURVEY OF THE SUBDIVISION OF SECTION 12,
T. 12 S., R. 13 E., SALT LAKE MERIDIAN, UTAH

CHAINS**40.40**

The center 1/4 section corner of section 12.

51.50

Nine Mile road, bears NE and SW.

60.57

Point for the center W 1/16 section corner of section 12.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, with aluminum cap marked:

$$C \frac{W \ 1/16}{S12} C$$

1991

80.74

The 1/4 section corner of sections 11 and 12.

From true point for the E 1/16 section corner of sections 12 and 13.

N. 0° 01' E., on the N - S center line of the SE 1/4.

Over rough mountainous land.

39.97

The center E 1/16 section corner of section 12.

From the W 1/16 section corner of sections 12 and 13.

N. 0° 03' W., on the N - S center line of the SW 1/4.

Over mountainous land.

19.495

Point selected for the witness corner to the SW 1/16 section corner of section 12.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

$$\begin{array}{c} \uparrow \\ WC \\ SW \ 1/16 \ S12 \\ 1991 \end{array}$$

Raise a mound of stone west of the corner.

19.995

True point for the SW 1/16 section corner of section 12, at intersection with the E - W center line of the SW 1/4, falls in Nine Mile Creek where it is impracticable to establish a permanent monument.

27.00

Nine Mile road, bears NE and SW.

SURVEY OF THE SUBDIVISION OF SECTION 12,
T. 12 S., R. 13 E., SALT LAKE MERIDIAN, UTAH

CHAINS
39.99

The center W 1/16 section corner of section 12.

From the center S 1/16 section corner of section 12.

N. 81° 46' W., on the E - W center line of the SW 1/4.

Over mountainous land.

20.165 True point for the SW 1/16 section corner of section 12.

22.50 Nine Mile road, bears N and S.

40.33 The S 1/16 section corner of sections 11 and 12.

Survey of the Subdivisional Lines of Section 13,
T. 12 S., R. 13 E., Salt Lake Meridian, Utah

From the 1/4 section corner of section 13 only, on the South boundary of the section.


N. 0° 29' E., on the N - S center line of section 13.

Over rough mountainous land.

30.90 True point for the center 1/4 section corner of section 13, at intersection with the E - W center line, falls in the bottom of narrow ravine where it is impracticable to establish a permanent monument.

46.32 Point selected for the witness corner to the center N 1/16 section corner of section 13.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:



Raise a mound of stone west of the corner.

50.32 True point for the center N 1/16 section corner of section 13, falls in the bottom of a narrow ravine where it is impracticable to establish a permanent monument.

SURVEY OF THE SUBDIVISION OF SECTION 13,
T. 12 S., R. 13 E., SALT LAKE MERIDIAN, UTAH

CHAINS
69.74

The 1/4 section corner of sections 12 and 13.

From the 1/4 section corner of sections 13 and 18, on the east boundary of the township, set and marked as described in the concurrent resurvey of the west boundary of T. 12 S., R. 14 E., under Group No. 750.

N. 79° 24' W., on the E - W center line of section 13.

Over rough mountainous land.

40.19 Point selected for the witness corner to the center 1/4 section corner of section 13.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with aluminum cap marked:

WC
T12S R13E
← C 1/4 S13
1991

Raise a mound of stone west of the corner.

40.69 True point for the center 1/4 section corner of section 13.

55.965 Point selected for the witness corner to the center W 1/16 section corner of section 13.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

WC
← C $\frac{W 1/16}{S13}$ C
1991

Raise a mound of stone north of the corner.

60.965 True point for the center W 1/16 section corner of section 13, falls in stream bed where it is impracticable to establish a permanent monument.

81.24 The 1/4 section corner of sections 13 and 14.

From the true point for the center W 1/16 section corner of section 13.

N. 0° 27' E., on the N - S center line of the NW 1/4 of section 13.

SURVEY OF THE SUBDIVISION OF SECTION 13,
T. 12 S., R. 13 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Over rough mountainous land.

- 18.995** Point for the NW 1/16 section corner of section 13, at intersection with the E - W center line of the NW 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap marked:

NW 1/16 S13
1991

- 37.99** The W 1/16 section corner of sections 12 and 13.

From the true point for the center N 1/16 section corner of section 13.

N. 80° 35' W., on the E - W center line of the NW 1/4 of section 13.

Over rough mountainous land.

- 20.22** The NW 1/16 section corner of section 13.

- 40.44** The N 1/16 section corner of sections 13 and 14.

Survey of the Subdivisional Lines of Section 14,
T. 12 S., R. 13 E., Salt Lake Meridian, Utah

From the 1/4 section corner of section 14 only, on the north boundary of section 23.

N. 0° 41' E., on the N and S center line of section 14.

Over mountainous land.

- 38.25** Point for the center 1/4 section corner of section 14, at intersection with the E - W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R13E
C 1/4 S14
1991

Raise a mound of stone west of the corner.

SURVEY OF THE SUBDIVISION OF SECTION 14,
T. 12 S., R. 13 E., SALT LAKE MERIDIAN, UTAH

CHAINS
57.225

Point for the center N 1/16 section corner of section 14.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

$$\begin{array}{c} \text{C} \\ \text{N } 1/16 \text{ | S14} \\ \text{C} \\ 1991 \end{array}$$

Raise a mound of stone west of the corner.

61.00 Nine Mile road, bears E and W.

76.20 The 1/4 section corner of section 14 only.

From the 1/4 section corner of sections 13 and 14.

N. 87° 16' W., on the E - W center line of section 14.

Over rough mountainous land.

39.86 The center 1/4 section corner of section 14.

60.13 Point for the center W 1/16 section corner of section 14.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

$$\begin{array}{c} \text{C} \text{---} \frac{\text{W } 1/16}{\text{S14}} \text{---} \text{C} \\ 1991 \end{array}$$

Raise a mound of stone north of the corner.

80.40 The 1/4 section corner of sections 14 and 15.

From the N 1/16 section corner of sections 13 and 14.

N. 86° 41' W., on the E - W center line of the NE 1/4 of section 14.

Over rough mountainous land.

39.78 The center N 1/16 section corner of section 14.

SURVEY OF THE SUBDIVISION OF SECTION 14,
T. 12 S., R. 13 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the center W 1/16 section corner of section 14.

N. 0° 18' E., on the N - S center line of the NW 1/4 of section 14.

Over rough mountainous land.

26.50 Nine Mile road, bears NW and SE.

38.39 The W 1/16 section corner of section 14 only.

Survey of the Subdivision of Section 15,
T. 12 S., R. 13 E., Salt Lake Meridian, Utah

From the 1/4 section corner of section 15 only, on the north boundary of section 22.

North, on the N - S center line of section 15.

Over rough mountainous land.

19.785 Point for the center S 1/16 section corner of section 15.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

C
S 1/16 | S15
C
1991

Raise a mound of stone west of the corner.

39.57 Point for the center 1/4 section corner of section 15, at intersection with the E - W center line, falls in Cow Canyon Creek where it is impracticable to establish a permanent monument.

40.07 Point selected for the witness corner to the center 1/4 section corner of section 15.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

WC
T12S R13E
C 1/4 S15
1991



SURVEY OF THE SUBDIVISION OF SECTION 15,
T. 12 S., R. 13 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Raise a mound of stone west of the corner.

59.50 Nine Mile road, bears NE and SW.

79.24 The 1/4 section corner of section 15 only.

From the 1/4 section corner of sections 14 and 15.

N. 87° 06' W., on the E - W center line of section 15.

Over rough mountainous land.

20.105 Point for the center E 1/16 section corner of section 15.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a collar of stone to top, with aluminum cap marked:

$$C \frac{E \ 1/16}{S15} C$$

1991

40.21 True point for the center 1/4 section corner of section 15.

58.00 Nine Mile road, bears NE and SW.

60.38 Point for the center W 1/16 section corner of section 15.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

$$C \frac{W \ 1/16}{S15} C$$

1991

Raise a mound of stone north of the corner.

66.00 Nine Mile road, bears NW and SE.

80.55 The 1/4 section corner of sections 15 and 16.

From the E 1/16 section corner of section 15 only, on the north boundary of section 22.

N. 0° 02' W., on the N - S center line of the SE 1/4 of section 15.

SURVEY OF THE SUBDIVISION OF SECTION 15,
T. 12 S., R. 13 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Over rough mountainous land.

39.20

The center E 1/16 section corner of section 15.

From the center S 1/16 section corner of section 15.

N. $87^{\circ} 50'$ W., on the E - W center line of the SW 1/4 of section 15.

Over rough mountainous land.

40.36

The S 1/16 section corner of sections 15 and 16.

From the center W 1/16 section corner of section 15.

N. $0^{\circ} 04'$ E., on the N - S center line of the NW 1/4 of section 15.

Over rough mountainous land.

40.13

True point for the W 1/16 section corner of section 15 only.

Survey of the Subdivisional Lines of Section 17,
T. 12 S., R. 13 E., Salt Lake Meridian, Utah

From the 1/4 section corner of section 17 only, on the north boundary of section 20.

N. $0^{\circ} 14'$ W., on the N - S center line of section 17.

Over rough mountainous land.

41.74

Point for the center 1/4 section corner of section 17, at intersection with the E - W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R13E
C 1/4 S17
1991

Raise a mound of stone west of the corner.

45.50

Nine Mile road, bears E and W.

SURVEY OF THE SUBDIVISION OF SECTION 17,
T. 12 S., R. 13 E., SALT LAKE MERIDIAN, UTAH

CHAINS
62.46

Point for the center N 1/16 section corner of section 17.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

C
N 1/16 | S17
C
1991

Raise a mound of stone west of the corner.

83.18

The 1/4 section corner of section 17 only, on the north boundary of the township.

From the 1/4 section corner of sections 16 and 17.

N. 89° 15' W., on the E - W center line of section 17.

40.37

Point for the center 1/4 section corner of section 17.

80.64

The 1/4 section corner of sections 17 and 18.

From the N 1/16 section corner of sections 16 and 17.

N. 89° 48' W., on the E - W center line of the NE 1/4 of section 17.

Over rough mountainous land.

40.45

The center N 1/16 section corner of section 17.

N. 89° 34' W., on the E - W center line of the NW 1/4 of section 17.

Over rough and broken land.

40.33

The N 1/16 section corner of sections 17 and 18.

Survey of the Subdivision of Section 18,
T. 12 S., R. 13 E., Salt Lake Meridian, Utah

From the 1/4 section corner of section 18 only, on the north boundary of section 19.

N. 0° 10' W., on the N - S center line of section 18.

SURVEY OF THE SUBDIVISION OF SECTION 18,
T. 12 S., R. 13 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Over rough mountainous land.

20.265 Point for the center S 1/16 section corner of section 18, not monumented.

39.50 Nine Mile road, bears NE and SW.

40.53 Point for the center 1/4 section corner of section 18, at intersection with the E - W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12S R13E
C 1/4 S18
1991

Raise a mound of stone west of the corner.

60.705 Point for the center N 1/16 section corner of section 18.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

C
N 1/16 | S18
C
1991

Raise a mound of stone west of the corner.

80.88 The 1/4 section corner of section 18 only.

From the 1/4 section corner of sections 17 and 18.

N. 89° 15' W., on the E - W center line of section 18.

Along bottom of Nine Mile Canyon.

39.00 Nine Mile road, bears NE and SW.

40.07 The center 1/4 section corner of section 18.

60.12 Point for the center W 1/16 section corner of section 18, not monumented.

64.00 Minnie Maud road, bears N and S.

SURVEY OF THE SUBDIVISION OF SECTION 18,
T. 12 S., R. 13 E., SALT LAKE MERIDIAN, UTAH

CHAINS
78.02

The 1/4 section corner of sections 13 and 18, on the west boundary of the township, hereinbefore described.

From the N 1/16 section corner of sections 17 and 18.

N. 89° 43' W., on the E - W center line of the NE 1/4 of section 18.

Over broken land.

39.98

The center N 1/16 section corner of section 18, hereinbefore described.

From the W 1/16 section corner of section 18 only, on the north boundary of section 19.

N. 0° 12' W., on the N - S center line of the SW 1/4 of section 18.

Over mountainous land.

20.09

Point for the SW 1/16 section corner of section 18, at intersection with the E - W center line of the SW 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

SW 1/16 S18
1991

Raise a mound of stone west of the corner.

32.00

Nine Mile road, bears NE and SW.

40.18

The point for the center W 1/16 section corner of section 18.

From the point for the center S 1/16 section corner of section 18.

N. 88° 43' W., on the E - W center line of the SW 1/4 of section 18.

Over rolling land.

20.075

The SW 1/16 section corner of section 18.

31.50

Nine Mile road, bears NE and SW.

SURVEY OF THE SUBDIVISION OF SECTION 18,
T. 12 S., R. 13 E., SALT LAKE MERIDIAN, UTAH

CHAINS
38.02

The S 1/16 section corner of sections 13 and 18, on the west boundary of the township, hereinbefore described.

From the center N 1/16 section corner of section 18.

N. 89° 38' W., on the E - W center line of the NW 1/4 of section 18.

Over rolling land.

36.00

Minnie Maud road, bears NW and SE.

37.92

The N 1/16 section corner of sections 13 and 18, on the west boundary of the township, hereinbefore described.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Ferrel D. Reynolds	Surveying Technician
Shawn Peterson	Survey Aid
John Forsberg	Survey Aid
Shannon Serre	Survey Aid


CERTIFICATE OF SURVEY

I, *Jerry L. Thomas, Cadastral Surveyor*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *31st day of May, 1990*, I have *dependently resurveyed a portion of the west boundary, a portion of the subdivisional lines and subdivided certain sections in Township 12 South, Range 13 East*,

of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

September 26, 1995

Date



(Cadastral Surveyor)

Date

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of a portion of the west boundary, a portion of the subdivisional lines and the subdivision of certain sections, Township 12 South, Range 13 East, Salt Lake Meridian, Utah*,

executed by *Jerry L. Thomas, Cadastral Surveyor*

having been critically examined and found correct, are hereby approved.

September 28, 1995

Date



(Chief Cadastral Surveyor for Utah)