



UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD ASSISTANTS**

---

Name	Capacity
Steve Oatman	Survey Technician
Shannon Serre	Survey Aid


## CERTIFICATE OF SURVEY

I, *Gail E. Reynolds, Cadastral Surveyor*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *9th day of June, 1992*, I have *dependently resurveyed a portion of the east and north boundaries, a portion of the subdivisional lines and the subdivision of sections, 1, 12, 13 and 24 in Township 18 South, Range 2 West*,

of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

May 22, 1996

Date

  
(Cadastral Surveyor)

Date

(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of a portion of the east and north boundaries, a portion of the subdivisional lines and the subdivision of sections, 1, 12, 13 and 24, in Township 18 South, Range 2 West, Salt Lake Meridian, Utah*,

executed by *Gail E. Reynolds, Cadastral Surveyor*

having been critically examined and found correct, are hereby approved.

May 22, 1996

Date

  
(Chief Cadastral Surveyor for Utah)

(Chief Cadastral Surveyor for Utah)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

# FIELD NOTES

OF

THE DEPENDENT RESURVEY

OF A PORTION

OF THE NORTH BOUNDARY,

AND SUBDIVISIONAL LINES

THE SURVEY OF SECTIONS 5, 8, 17, 20, AND 29,

AND

THE SUBDIVISION OF SECTIONS 5 AND 8

IN

TOWNSHIP 29 SOUTH, RANGE 3 EAST

OF THE SALT LAKE MERIDIAN  
IN THE STATE OF UTAH

EXECUTED BY

*Ferrel D. Reynolds and  
Ronald K. Baugh, Cadastral Surveyors*

Under special instructions dated *October 16, 1992*, approved *October 19, 1992*, which provided for the surveys included under Group Number *792*, and assignment instructions dated *October 26, 1992*.

Survey commenced *October 28, 1992*

Survey completed *November 18, 1992*

INDEX DIAGRAM

Township 29 South, Range 3 East

	2	2	2			
6	10	5	4	4	3	2
	9	10	4			1
7	9	8	4	9	10	11
	8	9	4			12
18	8	17		16	15	14
	7	7	7			13
19	7	20		21	22	23
	5	6	3			24
30	5	29		28	27	26
	5					25
31		32		33	34	35
						36

The Subdivision of Section 5.....Page 11

The Subdivision of Section 8.....Page 11

## TOWNSHIP 29 SOUTH, RANGE 3 EAST, SALT LAKE MERIDIAN, UTAH

## CHAINS

The following field notes describe the dependent resurvey of a portion of the north boundary, a portion of the subdivisional lines, the survey of sections 5, 8, 17, 20, and 29, and the subdivision of sections 5 and 8 in Township 29 South, Range 3 East, Salt Lake Meridian, Utah.

Portions of the north boundary were surveyed by Bailey and Burrill in 1876, Stewart and Thompson in 1915, and portions resurveyed by E. Bird in 1935 and F.R. Chappell in 1966.

Portions of the subdivisional lines were surveyed by Bailey and Burrill in 1876, surveyed and resurveyed by J.P. Walker in 1904, and surveyed and resurveyed by Glen B. Hatch in 1970.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 792, Utah, dated October 16, 1992.

The directions of lines were determined by hour angle observations of the sun and Polaris, carried forward by sustained angulation. Distances were determined by electronic measurement.

Preliminary to the resurvey the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line notes are given herein.

The geographic position of the corner of sections 8, 9, 16 and 17 as determined by a tie made to U.S. Geological Survey station "TEASDALE 1952", is as follows:

Latitude  $38^{\circ} 17' 42.04''$  N. Longitude  $111^{\circ} 35' 48.41''$  W.  
N.A.D. 1927

The mean magnetic declination as projected from the U.S. Geological Survey Magnetic Declination Map of 1985 is  $13 \frac{1}{4}^{\circ}$  E.

---

Dependent Resurvey of a Portion of the North Boundary,  
T. 29 S., R. 3 E., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by Bailey and Burrill in 1876  
and the Resurvey by F.R. Chappell in 1966

---

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 29 S., R. 3 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Beginning at the corner of sections 4, 5, 32, and 33, on the north boundary of the township, monumented with an iron post 2 1/2 inches diam., projecting 14 ins. above ground and in a mound of stone, with brass cap marked as described in the official record of the 1966 resurvey. I remarked the brass cap for sections 32 and 33 only.

N. 89°53.0' W., on the south boundary of section 32, over broken mountainous land, through scattered pinon and juniper growth.

**0.670** Point for the closing corner of sections 4 and 5.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T28S R3E  
      S32        
 S5 | S4  
 C C  
 T29S  
 1992

Corner is located on nearly level bench land.

**40.080** The 1/4 section corner of sections 5 and 32, monumented with an iron post, 2 1/2 ins. diam., projecting 10 ins. above ground, with brass cap marked as described in the official record of the 1966 resurvey. I remarked the brass cap for section 32 only.

N. 89°57.0' W., beginning new measurement.

**0.610** Point for the 1/4 section corner of section 5 only, at midpoint between closing corners.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

      T28S R3E        
 1/4 S5  
 T29S  
 1992

Set a steel fence post alongside the aluminum post.

**39.700** The corner of sections 5, 6, 31, and 32, monumented with an iron post, 2 1/2 ins. diam., projecting 14 ins. above ground and set in a mound of stone, with brass cap marked as described in the official record of the 1966 resurvey. I remarked the brass cap for sections 31 and 32 only.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 29 S., R. 3 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

N. 89°54.0' W., on the south boundary of section 31.

Over broken mountainous land, through scattered pinon and juniper growth.

**0.920** Point for the closing corner of sections 5 and 6.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone with aluminum cap marked:

T28S R3E  
 $\frac{S31}{S6 \mid S5}$   
 C C  
 T29S  
 1992

Corner is located on a gentle N slope, in sagebrush.

**39.900** The 1/4 section corner of sections 6 and 31, monumented with an iron post, 2 1/2 ins. diam., set in a mound of stone, with brass cap marked as describe in the official record of the 1966 resurvey.

---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 29 S., R. 3 E., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by J.P. Walker in 1904  
and the Resurvey by G.B. Hatch in 1970

---

From the corner of sections 20, 21, and 28, monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. above ground, with brass cap marked as described in the official record of the 1970 survey.

S. 89°56.0' W., between sections 20 and 28.

**4.410** The corner of sections 20, 28 and 29, monumented with an iron post, U.S. Forest Reserve Boundary Post No. 103, 3 ins. diam., projecting 18 ins. above ground and set in a mound of stone, with brass cap marked as described in the official record of the 1970 resurvey.

---

Survey of a Portion of the Subdivisional Lines,  
T. 29 S., R. 3 E., Salt Lake Meridian, Utah

---

SURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 29 S., R. 3 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the corner of sections 8, 9, 16, and 17, monumented with an iron post, 2 1/2 ins. diam., projecting 18 ins. above ground, set in a mound of stone, with brass cap marked as described in the official record of the 1970 survey by G.B. Hatch.

From which:

U.S. Geological Survey Triangulation Station "TEASDALE 1952", bears  
S. 80°20.3' E., 382.229 chains distance.

N. 0°02.0' E., between sections 8 and 9.

Over rolling mountainous land, through sagebrush and native grasses.

**40.000** Point for the 1/4 section corner of sections 8 and 9.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T29S R3E  
1/4  
S8 | S9  
1992

Set a steel fence post alongside the aluminum post.

**80.000** Point for the corner of sections 4, 5, 8, and 9.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T29S R3E  
S5 | S4  
S8 | S9  
1992

Set a steel fence post alongside the aluminum post.

Corner is located in small draw, drains NE.

---

N. 0°02.0' E., between sections 4 and 5.

Over rolling mountainous land, through scattered pinon and juniper growth.

**40.000** Point for the 1/4 section corner of sections 4 and 5.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with aluminum cap marked:

SURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 29 S., R. 3 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T29S R3E  
1/4  
S5 | S4  
1992

Set a steel fence post alongside the aluminum post.

Corner is located on a gentle rolling N slope, in scattered pinon and juniper growth.

**84.470** The closing corner of sections 4 and 5, hereinbefore described.

From the corner of sections 29, 30, 31, and 32, monumented with an iron post, 2 1/2 ins. diam., set in a mound of stone, with brass cap marked as described in the official record of the 1970 survey by G.B. Hatch.

N. 0°05.0' W., between sections 29 and 30.

Over rolling mountainous land, through scattered pinon and juniper growth.

**40.000** Point for the 1/4 section corner of sections 29 and 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T29S R3E  
1/4  
S30 | S29  
1992

Set a steel fence post alongside the aluminum post.

Corner is located on a gentle N slope, in pinon and juniper growth.

**80.000** Point for the corner of sections 29 and 30 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T29S R3E  
S19  
S30 | S29  
1992

Set a steel fence post alongside the aluminum post.

Corner is located on a rolling NW slope.

SURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 29 S., R. 3 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the corner of sections 20, 28, and 29, hereinbefore described on the north boundary of section 29.

N. 89°56.0' W., on the north boundary of section 29.

Over rolling mountainous land, through scattered pinon and juniper growth.

**35.590** Point for the 1/4 section corner of section 20 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T29S R3E  
1/4 S20  
1992

Raise a mound of stone N of the corner.

**40.035** Point for the 1/4 section corner of section 29 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T29S R3E  
1/4 S29  
1992

Corner is located on a N slope in pinon and juniper growth.

**75.590** Point for the corner of sections 19 and 20, on the north boundary of section 29.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T29S R3E  
S19 | S20  
S29  
1992

Raise a mound of stone N of the corner.

Corner is located on a rolling N slope.

**80.070** The corner of sections 29 and 30 only, hereinbefore described.

---

From the corner of sections 19 and 20 only, on the north boundary of section 29.

N. 0°01.0' E., between sections 19 and 20.

SURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 29 S., R. 3 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Over rolling mountainous land, through scattered pinon and juniper growth.

**40.000** Point for the 1/4 section corner of sections 19 and 20.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T29S R3E  
1/4  
S19 | S20  
1992

Set a steel fence post alongside the aluminum post.

Corner is located on a gentle rolling land.

**80.000** Point for the corner of sections 17, 18, 19, and 20.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T29S R3E  
S18 | S17  
S19 | S20  
1992

Set a steel fence post alongside the aluminum post.

Raise a mound of stone W of the corner.

Corner is located on a rolling SE slope.

---

From the corner of sections 16, 17, 20, and 21, monumented with an iron post, 2 1/2 ins. diam., projecting 10 ins. above ground, set in a mound of stone, with the brass cap marked as described in the official record of the 1970 survey by G.B. Hatch.

N. 89° 54.0' W., between sections 17 and 20.

Over rolling mountainous land.

**40.005** Point for the 1/4 section corner of sections 17 and 20.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

SURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 29 S., R. 3 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T29S R3E

1/4  $\frac{S17}{S20}$   
1992

Set a steel fence post alongside the aluminum post.

Corner is located on gentle rolling land, in native grasses.

**80.010** The corner of sections 17, 18, 19, and 20.

N. 0° 01.0' E., between sections 17 and 18.

Over rolling mountainous land.

**40.000** Point for the 1/4 section corner of sections 17 and 18.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T29S R3E  
1/4  
S18 | S17  
1992

Set a steel fence post alongside the aluminum post.

Raise a mound of stone W of the corner.

Corner is located on a rolling S slope.

**80.000** Point for the corner of sections 7, 8, 17, and 18.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T29S R3E  
S7 | S8  
S18 | S17  
1992

Set a steel fence post alongside the aluminum post.

Raise a mound of stone W of the corner.

Corner is located on a SE slope.

SURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 29 S., R. 3 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the corner of sections 8, 9, 16, and 17.

N. 89°53.0' W., between sections 8 and 17.

Over rolling mountainous land.

**40.010** Point for the 1/4 section corner of sections 8 and 17.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., on solid rock and in a mound of stone, 4 1/2 ft. base to top, with aluminum cap marked.

T29S R3E  
1/4     S8  
          S17  
          1992

Corner is located on a broken NE slope.

**40.300** Top of spur, projects SE.

**80.020** The corner of sections 7, 8, 17, and 18.

N. 0°01.0' E., between sections 7 and 8.

Over rolling mountainous land.

**40.000** Point for the 1/4 section corner of sections 7 and 8.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T29S R3E  
1/4  
S7 | S8  
1992

Set a steel fence post alongside the aluminum post.

Raise a mound of stone W of the corner.

Corner is located on the S edge of a draw, drains NE.

**80.000** Point for the corner of sections 5, 6, 7, and 8.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with aluminum cap marked:

SURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 29 S., R. 3 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T29S R3E	
S6	S5
S7	S8
1992	

Set a steel fence post alongside the aluminum post.

Raise a mound of stone W of the corner.

Corner is located on a broken N slope.

From the corner of sections 4, 5, 8, and 9.

N. 89° 53.0' W., between sections 5 and 8.

Over rolling mountainous land.

**40.015** Point for the 1/4 section corner of sections 5 and 8.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T29S R3E	
1/4	S5
	S8
1992	

Set a steel fence post alongside the aluminum post.

**80.030** The corner of sections 5, 6, 7, and 8.

N. 0° 01.0' E., between sections 5 and 6.

Over broken mountainous land, through scattered pinon and juniper growth.

**0.50** Dirt road, bears E and W.

**40.000** Point for the 1/4 section corner of sections 5 and 6.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T29S R3E	
	1/4
S6	S5
1992	

SURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 29 S., R. 3 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set a steel fence post alongside the aluminum post.

**84.430** The closing corner of sections 5 and 6, hereinbefore described.

---

The Subdivision of Section 5,  
T. 29 S., R. 3 E., Salt Lake Meridian, Utah.

---

From the 1/4 section corner of sections 5 and 8.

N. 0°02.0' E., on the N - S center line of section 5.

**40.000** Point for the center 1/4 section corner, at intersection with the E - W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T29S R3E  
C 1/4 S5  
1992

Set a steel fence post alongside the aluminum post.

**84.470** The 1/4 section corner of section 5 only the north boundary of the township.

---

From the 1/4 section corner of sections 4 and 5.

N. 89°53.0' W., on the E - W center line of section 5.

**40.020** The center 1/4 section corner of section 5.

**80.040** The 1/4 section corner of sections 5 and 6.

---

The Subdivision of Section 8,  
T. 29 S., R. 3 E., Salt Lake Meridian, Utah.

---

From the 1/4 section corner of sections 8 and 17.

N. 0°01.0' E., on the N - S center line of section 8.

**40.000** Point for the center 1/4 section corner, at intersection with the E - W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap marked:

THE SUBDIVISION OF SECTION 8,  
T. 29 S., R. 3 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

T29S R3E  
C 1/4 S8  
1992

Set a steel fence post alongside the aluminum post.

**80.000** The 1/4 section corner of sections 5 and 8.

---

From the 1/4 section corner of sections 8 and 9.

N. 89° 53.0' W., on the E - W center line of section 8.

**40.015** The center 1/4 section corner of section 8.

**80.030** The 1/4 section corner of sections 7 and 8.

---

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD ASSISTANTS**

---

Name	Capacity
Gail E. Reynolds	Cadastral Surveyor

## CERTIFICATE OF SURVEY

I, *Ferrel D. Reynolds and Ronald K. Baugh, Cadastral Surveyors*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *16th day of October, 1992*, I have *dependently resurveyed a portion of the north boundary, a portion of the subdivisional lines, surveyed sections 5, 8, 17, 20, and 29, and subdivided sections 5 and 8, in Township 29 South, Range 3 East,*

of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

April 18, 1996

Date

April 18, 1996

Date

*Ferrel D. Reynolds*

(Cadastral Surveyor)

*Ronald K. Baugh*

(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of a portion of the north boundary, a portion of the subdivisional lines, the survey of sections 5, 8, 17, 20, and 29, and the subdivision of sections 5 and 8, Township 29 South, Range 3 East, Salt Lake Meridian, Utah,*

executed by *Ferrel D. Reynolds and Ronald K. Baugh, Cadastral Surveyors*

having been critically examined and found correct, are hereby approved.

April 18, 1996

Date

*Donald A. Buhler*

(Chief Cadastral Surveyor for Utah)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF  
A PORTION OF THE WEST AND NORTH BOUNDARIES

A PORTION OF THE SUBDIVISIONAL LINES

AND THE

SUBDIVISION OF

SECTION 6

IN

TOWNSHIP 11 NORTH, RANGE 8 EAST

of the SALT LAKE Meridian  
In the State of UTAH

EXECUTED BY

*Gail E. Reynolds*  
*Cadastral Surveyor*

Under special instructions dated *June 7, 1993*, approved June 7, 1993, which provided for the surveys included under Group Number *804*, and assignment instructions dated *June 7, 1993*.

Survey commenced *June 15, 1993*

Survey completed *July 20, 1994*

INDEX DIAGRAM

Township 11 North, Range 8 East

	7	6	5	4	3			
2	6	9	5	4	3	2	1	
	8							
	7	8	9	10	11	12		
	18	17	16	15	14	13		
	19	20	21	22	23	24		
	30	29	28	27	26	25		
	31	32	33	34	35	36		

## TOWNSHIP 11 NORTH, RANGE 8 EAST, SALT LAKE MERIDIAN, UTAH

## CHAINS

The following field notes describe the dependent resurvey of a portion of the west and north boundaries, a portion of the subdivisional lines and the survey of the subdivision of section 6, Township 11 North, Range 8 East, Salt Lake Meridian, Utah.

Portions of the west boundary were surveyed by F. Dickert in 1870 and by A. P. Hanson in 1896, with a portion resurveyed by A.P. Hanson in 1896.

Portions of the north boundary were surveyed by F. Dickert in 1870 and by A.P. Hanson in 1896, with a portion resurveyed by A. P. Hanson in 1896.

Portions of the subdivisional lines were surveyed by F. Dickert in 1870 and by A.P. Hanson in 1896, with a portion resurveyed by A. P. Hanson in 1896.

A portion of the subdivisional lines closing with the boundary line between townships 11 and 12 north were surveyed by A.P. Hanson in 1896.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 804 dated June 7 1993.

The directions of lines were determined by hour angle observations of the sun and Polaris, carried forward by sustained angulation. Distances were determined by electronic measurement.

Preliminary to the resurvey the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line notes are given herein.

The geographic position of the closing corner of sections 32 and 33, Township 12 North, Range 8 East, as determined by B.L.M. Geographic Coordinate Data Base dated January 19, 1995, is:

Latitude  $41^{\circ} 43' 57.604''$  N.                      Longitude  $111^{\circ} 02' 54.859''$  W.  
N.A.D. 1927

The mean magnetic declination as projected from the U.S. Geological Survey Magnetic Declination Map of 1990 is  $14^{\circ}$  E.

---

Dependent Resurvey of a Portion of the West Boundary  
T. 11 N., R. 8 E., Salt Lake Meridian, Utah

---

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
T. 11 N., R. 8 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Reestablishment of the Survey Executed by F. Dickert  
in 1870 and the Resurvey by A.P. Hanson in 1896

Beginning at the corner of sections 1, 6, 7, and 12, T. 11 N., Rs., 7 and 8 E., monumented with a broken limestone, 14x8x6 ins., firmly set and plainly marked with 5 notches on the S and 1 notch on the N edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N  
R7E R8E  
S1 | S6  
S12 | S7  
1993

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

The corner is located in nearly level pasture land, alongside a fence post in an E and W fence line.

N. 0°23.8' E., between sections 1 and 6.

Over nearly level pasture land.

**40.766** Point for the 1/4 section corner of sections 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N  
R7E R8E  
1/4  
S1 | S6  
1993

Set a steel fence post alongside the aluminum post.

The corner is located 18 lks. dist., N of an E and W fence line, on nearly level pasture land.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
T. 11 N., R. 8 E., SALT LAKE MERIDIAN, UTAH

**CHAINS****81.532**

The corner of Townships 11 and 12 North, Ranges 7 and 8 East, monumented with a broken limestone, 10x8x8 ins., firmly set and dimly marked with 6 notches on the N, S, E and W edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12N  
R7E R8E  
S36 | S31  
S1 | S6  
T11N  
1993

Deposit the marked stone alongside the aluminum post.

The corner is located in an E and W fence line, on nearly level pasture land.

---

Dependent Resurvey of a Portion of the North Boundary,  
T. 11 N., R. 8 E., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by A.P. Hanson in 1896

---

Beginning at the corner of sections 4, 5, 32, and 33, monumented with a quartzite stone, 18x8x8 ins., firmly set and plainly marked with 4 notches on the E and 2 on the W edges. This corner was original set to function as the corner of sections 4, 5, 32, and 33, but has never functioned in this capacity, it will now function as an angle point only on the line between Townships 11 and 12 North.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone with aluminum cap marked:

A P  
T12N R8E  
S32  
S4  
T11N  
1993

Deposit the marked stone alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 11 N., R. 8 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From this corner:

The closing corner of sections 32 and 33, as set by A.P. Hanson in 1896, during the survey of the closing subdivisional lines of T. 12 N., R 8 E., monumented with a quartzite stone, 18x10x9 ins., firmly set and dimly marked with 2 notches on the W, and 4 notches on the E edges, bears N. 89°19.5' E., 1.523 chs. dist.; not remonumented.

N. 89°49.0' W., between sections 4 and 32.

Over rolling mountainous land.

**12.372** The closing corner of sections 4 and 5, monumented with a granite stone, 18x8x6 ins., firmly set and plainly marked with 4 grooves on the E and 2 grooves on the W edges, and a CC on the S face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T12N R8E  
  S32    
 S5 | S4  
 C C  
 T11N  
 1994

Deposit the marked stone alongside the aluminum post.

**27.327** Intersect line 1 - 2 of the Cheyenne Lode, Mineral Survey No. 5599; not monumented.

From this point:

Corner No. 1 of the Cheyenne lode, bears N. 13°44.0' E., 12.604 chains dist., monumented with a pine post, 6x2 ins., by 2 ft. high, set in a mound of stone, with no visible scribe marks.

Corner No. 2 of the Cheyenne lode, bears S. 13°44.0' W., 10.012 chains dist., monumented with a decayed pine post set in a mound of stone, with no visible scribe marks.

**35.665** Intersect line 3 - 4, of the Cheyenne lode, Mineral Survey No. 5599; not monumented.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 11 N., R. 8 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From this point:

Corner No. 4 of the Cheyenne lode, bears N.  $14^{\circ}03.5'$  E., 18.928 chains dist., monumented with an old post, set in the center of a mound of stone, with no visible scribe marks.

Corner No. 3 of the Cheyenne lode, bears S.  $14^{\circ}03.5'$  W., 3.828 chains dist., monumented with a pine post, 6x2 ins., set 2 ft. above ground, with no visible scribe marks.

**40.245** The 1/4 section corner of sections 5 and 32, monumented with a quartzite stone, 18x9x6 ins., firmly set and plainly marked 1/4. This corner was originally set as the 1/4 section corner of sections 5 and 32, but has never functioned in this capacity, it will now function as an angle point only on the line between Townships 11 and 12 North.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

A P  
T12N R8E  
S32  
S5  
T11N  
1994

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

The corner is located on a steep E slope, in sagebrush.

N.  $89^{\circ}59.0'$  W., beginning new measurement.

**0.415** Intersect line 1 - 2, of the Arapahoe lode, Mineral Survey No. 5599; not monumented.

From this point:

Corner No. 2, of the Arapahoe lode, bears N.  $16^{\circ}33.0'$  E., 16.168 chains dist., monumented with a post, 6x6 ins., 2 ft. above ground, with no visible scribe marks.

Corner No. 1, of the Arapahoe lode, bears S.  $16^{\circ}33.0'$  W., 6.586 chains dist., monumented with a 6x6 ins. post, 2 ft. above ground, with faint scribe marks visible.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 11 N., R. 8 E., SALT LAKE MERIDIAN, UTAH

**CHAINS****9.875**

Intersect line 3 - 4, of the Arapahoe lode, Mineral Survey No. 5599, not monumented.

From this point:

Corner No. 3, of the Arapahoe lode, bears N.  $16^{\circ}34.2'$  E., 18.136 chains dist., monumented with a 6x6 ins. post, set in a mound of stone, with scribe marks 5579 visible.

Corner No. 4, of the Arapahoe lode, bears S.  $16^{\circ}34.2'$  W., 4.608 chains dist., monumented with a large mound of stone (center of mound).

**39.937**

The corner of sections 31 and 32, monumented with a red sandstone, 15x8x6 ins., firmly set and dimly marked with 5 notches on the east and 1 notch on the west edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12N R8E
S31   S32
—
S5
T11N
1994

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner is located in nearly level pasture land.

---

Reestablishment of the Survey by F. Dickert in 1870,  
and the Resurvey by A.P. Hanson in 1896

---

N.  $89^{\circ}43.8'$  W., on the south boundary of section 31.

Over nearly level pasture land.

**2.934**

The closing corner of sections 5 and 6, monumented with a broken red sandstone, 16x8x6 ins., firmly set and dimly marked with 5 grooves on the E and 1 groove on the W edges and CC on the S face.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 11 N., R. 8 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12N R8E  
 $\frac{S31}{S6 \mid S5}$   
 C | C  
 T11N  
 1994

Deposit the marked stone alongside the aluminum post.

The corner is located at the corner of fences, projecting S and W.

**42.532** Point for the original 1/4 section corner of sections 6 and 31, at proportionate distance; no remaining evidence of the corner was found. This point will now function for the 1/4 section corner of section 31 only, T. 12 N., R. 8 E.; not remonumented.

**44.888** Point for the 1/4 section corner of section 6 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12N R8E  
 $\frac{1/4 S6}{T11N R8E}$   
 1993

Corner is located in an east and west fence line, on nearly level pasture land.

**85.064** The corner of Townships 11 and 12 North, Ranges 7 and 8 East, hereinbefore described.

---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 11 N., R. 8 E., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by F. Dickert in 1870  
and the Resurvey by A. P. Hanson in 1895

---

From the corner of sections 1, 6, 7, and 12, on the west boundary of the township, hereinbefore described.

S. 89°11.3' E., between sections 6 and 7.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 N., R. 8 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Over nearly level pasture land.

**40.000** Point for the 1/4 section corner of sections 6 and 7, established at record distance, from the west boundary. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R8E  
1/4     S6  
          S7  
          1993

Set a steel fence post alongside the aluminum post.

Corner is located in nearly level pasture land.

**59.350** Point selected for the witness corner to the E 1/16 section corner of sections 6 and 7.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

W C  
T11N R8E  
E 1/16     S6  
                  S7  
                  1993

Set a steel fence post alongside the aluminum post.

The corner is located on the W bank of the Bear River.

**60.000** True point for the E 1/16 section corner of sections 6 and 7, falls in the Bear River.

**76.20** Point for the closing corner of sections 5 and 7, established at record distance from the west boundary; no remaining evidence of this corner was found; not monumented.

**83.490** Point for the SE section corner of section 6, established at record distance from the west and north boundaries. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T11N R8E  
S6  
1994

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 N., R. 8 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Corner is located on a steep N slope.

---

Reestablishment of the Survey Executed by A.P. Hanson in 1895

---

N. 0°32.1' W., between sections 5 and 6.

**20.580** Point for the S 1/16 corner of section 6 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T11N R8E  
S1/16 |  
S6  
1994

Corner is located on steep west slope, in sagebrush.

**41.160** Point for the 1/4 section corner of section 6 only, established at record distance; no remaining evidence of the original corner was found. This point was not remonumented due to the extent of roads and ditches.

**82.320** The closing corner of sections 5 and 6, on the north boundary of the township, hereinbefore described.

---

The Subdivision of Section 6  
T. 11 N., R. 8 E., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 6 and 7.

N. 0°31.6' E., on the N - S center line of section 6.

**20.476** Point for the center S 1/16 section corner of section 6; not monumented.

**40.952** Point for the center 1/4 section corner, at intersection with the E - W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R8E  
C 1/4 S6  
1993

Set a steel fence post alongside the aluminum post.

THE SUBDIVISION OF SECTION 6,  
T. 11 N., R. 8 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

- The corner is located in nearly level pasture land, 45 lks. NW of canal.
- 81.908** The 1/4 section corner of section 6 only, on the north boundary of the township; hereinbefore described.
- 
- From the point for the east 1/4 section corner of section 6 only.
- N. 89°27.2' W., on the E - W center line of section 6.
- 22.679** Point for the center E 1/16 section corner of section 6, not monumented.
- 42.722** The C 1/4 section corner of section 6.
- 82.810** The 1/4 section corner of sections 1 and 6, on the west boundary of the township, hereinbefore described.
- 
- From the true point for the E 1/16 section corner of sections 6 and 7.
- N. 0°35.4' E., on the N - S center line of the SE 1/4 of section 6.
- 20.522** Point for the SE 1/16 section corner of section 6, at intersection with the E - W center line of the SE 1/4.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:
- T11N R8E  
SE 1/16 S6  
1993
- Set a steel fence post alongside the aluminum post.
- The corner is located on nearly level land, in willows and rosebushes.
- 41.044** Point for the center E 1/16 section corner of section 6.
- 
- From the S 1/16 section corner of section 6 only.
- N. 89°19.1' W., on the E - W center line of the SE 1/4 of section 6.
- 23.084** The SE 1/16 section corner of section 6.
- 43.106** The point for the center S 1/16 section corner of section 6.
-

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

## FIELD ASSISTANTS

---

Name	Capacity
Ferrel Reynolds	Land Surveyor
Philip Tobler	Survey Technician
Todd Snyder	Survey Aid

## CERTIFICATE OF SURVEY

I, *Gail E. Reynolds, Cadastral Surveyor*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *7th day of June, 1993*, I have *dependently resurveyed a portion of the west and north boundaries, a portion of the subdivisional lines and subdivided section 6, in Township 11 North, Range 8 East,*

of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

May 22, 1996

Date



(Cadastral Surveyor)

Date

(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of a portion of the west and north boundaries, a portion of the subdivisional lines and the subdivision of section 6, in Township 11 North, Range 8 East, Salt Lake Meridian, Utah,*

executed by *Gail E. Reynolds, Cadastral Surveyor*

having been critically examined and found correct, are hereby approved.

May 22, 1996

Date



(Chief Cadastral Surveyor for Utah)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

## FIELD NOTES

OF

THE DEPENDENT RESURVEY

OF A PORTION

OF THE WEST BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS

7, 8, 9, AND 17

IN

TOWNSHIP 33 SOUTH, RANGE 23 EAST

OF THE SALT LAKE MERIDIAN  
IN THE STATE OF UTAH

EXECUTED BY

*Ferrel D. Reynolds,  
Cadastral Surveyor*

Under special instructions dated *July 27, 1993*, approved *July 27, 1993*, which provided for the surveys included under Group Number *807*, and assignment instructions dated *July 30, 1993*.

Survey commenced *August 16, 1993*  
Survey completed *September 29, 1993*

INDEX DIAGRAM

Township 33 South, Range 23 East

			6			
6	5	4	3	2	1	
15 14	14	9	5			
			5			
3 7	8 8	9	10	11	12	
2 13	12	8	4			
		7				
18	17	16	15	14	13	
	10	6				
19	20	21	22	23	24	
30	29	28	27	26	25	
31	32	33	34	35	36	

The Subdivision of Section 7.....Page 15

The Subdivision of Section 8.....Page 16

The Subdivision of Section 9 .....Page 17

The Subdivision of Section 17.....Page 19

## TOWNSHIP 33 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

The following field notes describe the dependent resurvey of a portion of the west boundary, a portion of the subdivisional lines and the survey of the subdivision of sections 7, 8, 9 and 17, Township 33 South, Range 23 East, Salt Lake Meridian, Utah.

History of Surveys

	<u>Surveyed by</u>		<u>Retr. or Resurveyed by</u>	
<u>NORTH BOUNDARY</u>				
Portion	F. Dickert	1878		
Portion	E. Beuther	1884		
All			J.M. Lentz	1900-01
Portion			W.B. Rice	1915
All			R. Gentry	1917
<u>SOUTH BOUNDARY</u>				
Portion	E. Beuther	1884		
All			J.M. Lentz	1900-01
<u>EAST BOUNDARY</u>				
All	F. Dickert	1878		
All			J.M. Lentz	1900-01
<u>WEST BOUNDARY</u>				
All	E. Buether	1884		
All			J.M. Lentz	1900-01
Portion	Remonumentation		F.D. Reynolds	1970
<u>SUBDIVISION</u>				
All	J.M. Lentz	1900-01		
Portion	Remonumentation		F.D. Reynolds	1970

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 807, dated July 27, 1993.

The directions of lines were determined by hour angle observations of the sun and Polaris, carried forward by sustained angulation. Distances were determined by electronic measurement.

## TOWNSHIP 33 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

Preliminary to the resurvey the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line notes are given herein.

The geographic position of the corner of sections 9, 10, 15, and 16, as determined by using the Global Positioning System (G.P.S.), static relative positioning techniques, utilizing U.S. Coast and Geodetic Survey triangulation station "Indian 1953" is:

Latitude 37°54' 59.01" N.      Longitude 109°23' 28.02" W.  
N.A.D. 1927

This corner is now designated a B.L.M. control station.

---

Dependent Resurvey of a Portion of the West Boundary,  
T. 33 S., R. 23 E., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by E. Buether in 1884  
and the Resurvey by J. M. Lentz in 1900-01

---

Beginning at the corner of sections 7, 12, 13, and 18, T. 33 S., Rs. 22 and 23 E., monumented with a granite stone, 15x10x6 ins., firmly set and dimly marked with 4 notches on the S and 2 notches on the N edges, witnessed by a mound of stone W of the corner.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, with aluminum cap marked:

T33S  
R22E R23E  
S12 | S7  
S13 S18  
1993

Deposit the marked stone alongside the aluminum post.

Corner is located on a N slope, 86 lks. dist., N of an E and W fence line.

N. 0° 00.7' W., between sections 7 and 12.

Over mountainous land, through pinon, juniper, oak and serviceberry brush.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
T. 33 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

**40.194**

Point for the 1/4 section corner of sections 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T33S  
R22E R23E  
1/4  
S12 | S7  
1993

Corner is located in thick oak and serviceberry brush.

**80.388**

The corner of sections 1, 6, 7 and 12, monumented with a sandstone, 18x10x5 ins., firmly set and plainly marked 5 notches on the S and 1 notch on the N edges, witnessed by a mound of stone, W of the corner

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T33S  
R22E R23E  
S1 | S6  
S12 | S7  
1993

Deposit the marked stone alongside the aluminum post.

---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 33 S., R. 23 E., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by  
J. M. Lentz in 1900-01

---

From the corner of sections 9, 10, 15, and 16, as determined from the projection of a fence line from the south and at the center of road, 50 lks. wide running east and west.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone to top, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 33 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T33S R23E  
S9 | S10  
S16 | S15  
1993

This corner is now a B.L.M. control station, hereinbefore described.

Corner is located in a draw, drains N, and 25 lks. dist., S of a fence line, bears E and W.

N.  $0^{\circ} 10.3'$  W., between sections 9 and 10.

Over gentle rolling mountainous land, through scattered pinon, juniper and oak brush.

**39.741** The 1/4 section corner of sections 9 and 10, monumented with a sandstone, 16x10x8 ins., firmly set and plainly marked 1/4 on the W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T33S R23E  
1/4  
S9 | S10  
1993

Deposit the marked stone alongside the aluminum post.

Corner is located at the corner of fences, projecting E, W and S.

N.  $0^{\circ} 08.1'$  E., beginning new measurement.

**20.170** Point for the N 1/16 section corner of sections 9 and 10.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T33S R23E  
N 1/16  
S9 | S10  
1993

The corner of fences, projecting N and W, bears N.  $63^{\circ} 16'$  W., 21 lks. dist.

Set a steel fence post alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 33 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

**CHAINS****40.340**

Point for the corner of sections 3, 4, 9, and 10, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T33S R23E			
S4		S3	
S9		S10	
1993			

Set a steel fence post alongside the aluminum post.

Raise a mound of stone, W of the corner.

Corner is located in a draw, drains E.

From this corner, the corner of sections 2, 3, 10, and 11, monumented with a sandstone, 14x10x5 ins., firmly set and plainly marked with 2 notches on the E and 5 notches on the S edges, bears S. 89° 57.3' E., 79.720 chs. dist.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T33S R23E			
S3		S2	
S10		S11	
1993			

Deposit the marked stone alongside the aluminum post.

This control line was fully retraced and a careful search was made for the 1/4 section corner of sections 3 and 10 which was not recovered.

---

N. 0° 54.0' W., between sections 3 and 4.

Over rolling mountainous land, through scattered pinon, juniper and oak brush.

**40.342**

Point for the 1/4 section corner of sections 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 33 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T33S R23E

1/4

S4 | S3

1993

Set a steel fence post alongside the aluminum post.

Corner is located 38 lks. dist., W of 4 strand barb wire fence, bears N and S.

80.704

The corner of sections 3 and 4, on the north boundary of the township, monumented with a sandstone, 14x8x4 ins., firmly set and plainly marked with 3 notches on the E and W edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T32S R23E

S33

S4 | S3

T33S

1993

Deposit the marked stone alongside the aluminum post.

Corner is located in a fence line, bears E and W.

---

From the corner of sections 16, 17, 20, and 21, monumented with a mound of stone at the corner of fences, projecting S and W. No marked rock was found. This point is accepted as the best available evidence of the original corner.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, in a mound of stone to top, with aluminum cap marked:

T33S R23E

S17 | S16

S20 | S21

1993

N. 0° 47.1' E., between sections 16 and 17.

Over broken mountainous land, through pinon, juniper, oakbrush and serviceberry growth.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 33 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

**CHAINS****40.288**

The 1/4 section corner of sections 16 and 17, monumented with a sandstone, 17x12x5 ins., firmly set and plainly marked 1/4 17 on the W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T33S R23E  
1/4  
S17 | S16  
1993

Deposit the marked stone alongside the aluminum post.

---

N. 0° 43.7' W., beginning new measurement.

**20.152**

Point for the N 1/16 section corner of sections 16 and 17.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T33S R23E  
N 1/16  
S17 | S16  
1993

**40.304**

The corner of sections 8, 9, 16, and 17, monumented with a sandstone, 18x10x6 ins., firmly set and plainly marked with 4 notches on the E and S edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T33S R23E  
S8 | S9  
S17 | S16  
1993

Deposit the marked stone alongside the aluminum post.

Corner is located at the corner of fences projecting E, W and N.

---

From the corner of sections 9, 10, 15, and 16.

S. 89° 53.8' W., between sections 9 and 16.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 33 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Over gentle rolling mountainous land, through pinon, juniper, oak and seviceberry brush.

- 39.916** Point for the 1/4 section corner of sections 9 and 16, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

	T33S R23E
1/4	<u>S9</u>
	S16
	1993

Corner is located on SE slope, in a railed area, 63 lks. dist., N of an E and W fence line.

- 79.832** The corner of sections 8, 9, 16, and 17.

---

N. 0° 09.9' W., between sections 8 and 9.

Over rolling mountainous land, through pinon, juniper, oak and seviceberry brush.

- 40.106** Point for the 1/4 section corner of sections 8 and 9, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone to top, with aluminum cap marked:

	T33S R23E
	1/4
	S8   S9
	1993

- 80.212** The corner of sections 4, 5, 8, and 9, monumented with a sandstone, 14x10x5 ins., firmly set and plainly marked with 4 notches on the E and 5 notches on the S edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

	T33S R23E
	<u>S5   S4</u>
	S8   S9
	1993

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 33 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Deposit the marked stone alongside the aluminum post.

Corner is located in dense pinon and juniper growth.

---

From the corner of sections 3, 4, 9, and 10.

N. 89° 56.4' W., between sections 4 and 9.

Over mountainous land, through thick pinon and juniper growth.

**19.935** Point for the E 1/16 section corner of sections 4 and 9.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

	T33S R23E
E 1/16	<u>S4</u>
	S9
	1993

Corner is located on a SE slope.

**39.870** The 1/4 section corner of sections 4 and 9, monumented with a sandstone, 12x10x6 ins., firmly set and dimly marked 1/4 on the N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T33S R23E
1/4	<u>S4</u>
	S9
	1993

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone N of the corner.

---

S. 89° 55.3' W., beginning new measurement.

**40.152** The corner of sections 4, 5, 8, and 9.

---

From the corner of sections 16, 17, 20, and 21.

N. 88° 36.9' W., between sections 17 and 20.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 33 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Over mountainous land, through thick pinon, juniper, oak and serviceberry brush.

- 39.881** The 1/4 section corner of sections 17 and 20, monumented with an iron post, 2 1/2 ins. diam., set in a mound of stone, with brass cap marked.

T33S R23E  
1/4      S17  
          S20  
          1970

This corner was remonumented by F.D. Reynolds in 1970.

Corner is located in an E and W fence line.

---

S. 88° 37.7' W., beginning new measurement.

- 19.906** Point for the W 1/16 section corner of sections 17 and 20.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone to top, with aluminum cap marked:

T33S R23E  
W 1/16      S17  
                  S20  
                  1993

Corner is located in an E and W fence line.

- 39.812** The corner of sections 17, 18, 19 and 20, monumented with an iron post, 2 1/2 ins. diam., 6 ins. above ground, with brass cap marked.

T33S R23E  
S18 | S17  
S19 | S20  
1970

This corner was remonumented by F.D. Reynolds in 1970.

Corner is located at the corner of fences, projecting E and N.

---

N. 0° 02.8' W., between sections 17 and 18.

Over mountainous land, through pinon, juniper, oak and serviceberry brush.

- 20.101** Point for the S 1/16 section corner of sections 17 and 18.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 33 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T33S R23E  
S 1/16  
S18 | S17  
1993

Set a steel fence post alongside the aluminum post.

Corner is located 8 lks. dist., E of a 4 strand barb wire fence line, bears N and S.

**40.202** The 1/4 section corner of sections 17 and 18, monumented with an iron post, 2 1/2 ins. diam., 6 ins. above ground, with brass cap marked:

T33S R23E  
1/4  
S18 | S17  
1970

This corner was remonumented by F.D. Reynolds in 1970.

Corner is located in a N and S fence line.

N. 0°36.7' W., beginning new measurement.

**19.874** Point for the N 1/16 section corner of sections 17 and 18.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, in a mound of stone to top, with aluminum cap marked:

T33S R23E  
N 1/16  
S18 | S17  
1993

Corner is located 1 lk. dist., E of a 4 strand N and S fence line.

**39.748** The corner of sections 7, 8, 17, and 18, monumented with an iron post, 2 1/2 ins. diam., 6 ins. above ground, with brass cap marked.

T33S R23E  
S7 | S8  
S18 | S17  
1970

This corner was remonumented by F.D. Reynolds in 1970.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 33 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Corner is located at the corner of fences projecting N, S and W.

---

From the corner of sections 8, 9, 16, and 17.

S. 89° 33.1' W., between sections 8 and 17.

Over mountainous land, through pinon, juniper, oak and serviceberry brush.

**20.038** Point for the E 1/16 section corner of sections 8 and 17.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

	T33S R23E
E 1/16	<u>S8</u>
	S17
	1993

Corner is located in a N and S fence line.

**40.076** Point for the 1/4 section corner of sections 8 and 17, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, in a mound of stone to top, with aluminum cap marked:

	T33S R23E
1/4	<u>S8</u>
	S17
	1993

Corner is located 57 lks. dist., N of an E and W fence line.

**60.114** Point for the W 1/16 section corner of sections 8 and 17.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T33S R23E
W 1/16	<u>S8</u>
	S17
	1993

Corner is located in pasture land, 14 lks. dist., N of an E and W fence line.

**80.152** The corner of sections 7, 8, 17, and 18.

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 33 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

N. 89° 32.4' W., between sections 7 and 18.

Over mountainous land, through pinon, juniper, oak and serviceberry brush.

- 39.614** The 1/4 section corner of sections 7 and 18, monumented with an iron post, 2 1/2 ins. diam., 6 ins. above ground, with brass cap mkd.

T33S R23E  
1/4     S7  
          S18  
          1970

This corner was remonumented by F.D. Reynolds in 1970.

N. 89° 53.4' W., beginning new measurement.

- 20.006** Point for the W 1/16 section corner of sections 7 and 18.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T33S R23E  
W 1/16     S7  
                  S18  
                  1993

Corner is located on a spur, projecting NE, and 37 lks. dist., N of an E and W fence line.

- 38.532** The corner of sections 7, 12, 13, and 18, on the west boundary of the township, hereinbefore described.

From the corner of sections 7, 8, 17, and 18.

N. 0° 08.5' E., between sections 7 and 8.

Over mountainous land, through pinon, juniper, oak and serviceberry brush.

- 40.398** Point for the 1/4 section corner of sections 7 and 8, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone to top, with aluminum cap marked:

T33S R23E  
1/4  
S7 | S8  
1993

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 33 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Corner is located 3 lks. dist., N of an old E and W fence line.

- 80.796** The corner of sections 5, 6, 7, and 8, monumented with a sandstone, 16x10x6 ins., firmly set and plainly marked with 5 notches on the S and E edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, in a mound of stone to top, with aluminum cap marked:

T33S R23E	
S6	S5
S7	S8
1993	

Deposit the marked stone alongside the aluminum post.

---

From the corner of sections 4, 5, 8, and 9.

S. 89° 58.1' W., between sections 5 and 8.

Over mountainous land, through pinon, juniper, oak and serviceberry brush.

- 39.852** Point for the 1/4 section corner of sections 5 and 8, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone to top, with aluminum cap marked:

	T33S R23E	
1/4	S5	
	S8	
	1993	

Corner is located 32 lks. dist., E of a N and S fence line.

- 79.704** The corner of sections 5, 6, 7, and 8.

---

S. 89° 54.0' W., between sections 6 and 7.

Over mountainous land, through pinon, juniper, oak and serviceberry brush.

- 39.935** The 1/4 section corner of sections 6 and 7, monumented with a sandstone, 14x10x3 ins., firmly set and plainly marked 1/4 S6 on the N face.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 33 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone to top, with aluminum cap marked:

T33S R23E  
1/4      S6  
          S7  
          1993

Deposit the marked stone alongside the aluminum post.

---

N. 89° 55.1' W., beginning new measurement.

**19.990** Point for the W 1/16 section corner of sections 6 and 7.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T33S R23E  
W 1/16      S6  
                  S7  
                  1993

**38.411** The corner of sections 1, 6, 7, and 12, on the west boundary of the township, hereinbefore described.

---

The Subdivision of Section 7,  
T. 33 S., R. 23 E., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 7 and 18.

N. 0°05.5' W., on the N-S center line of section 7.

Over mountainous land, through pinon, juniper, oak and serviceberry brush.

**40.177** Point for the center 1/4 section corner, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T33S R23E  
C 1/4 S7  
1993

**80.407** The 1/4 section corner of sections 6 and 7.

---

THE SUBDIVISION OF SECTION 7,  
T. 33 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the 1/4 section corner of sections 7 and 8.

N. 89° 51.7' W., on the E-W center line of section 7.

Over mountainous land, through pinon, juniper, oak and serviceberry brush.

**39.774** The center 1/4 section corner of section 7.

**59.772** Point for the center W 1/16 section corner of section 7.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T33S R23E  
C —  $\frac{W\ 1/16}{S7}$  — C  
1993

**78.245** The 1/4 section corner of sections 7 and 12, on the west boundary of the township, hereinbefore described.

---

From the W 1/16 section corner of sections 7 and 18.

N. 0° 05.0' W., on the N-S center line of the SW 1/4 of section 7.

**40.186** The center W 1/16 section corner of section 7.

---

N. 0° 05.0' W., on the N-S center line of the NW 1/4 of section 7.

**40.210** The W 1/16 section corner of sections 6 and 7.

---

The Subdivision of Section 8,  
T. 33 S., R. 23 E., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 8 and 17.

N. 0° 00.6' W., on the N-S center line of section 8.

Over mountainous land, through pinon, juniper, oak and serviceberry brush.

**40.254** Point for the center 1/4 section corner, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

THE SUBDIVISION OF SECTION 8,  
T. 33 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T33S R23E  
C 1/4 S8  
1993

Corner is located on a SW slope of hill.

**80.504** The 1/4 section corner of sections 5 and 8.

---

From the 1/4 section corner of sections 8 and 9.

S. 89° 45.5' W., on the E-W center line of section 8.

**39.965** The center 1/4 section corner of section 8.

**79.929** The 1/4 section corner of sections 7 and 8.

---

The Subdivision of Section 9,  
T. 33 S., R. 23 E., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 9 and 16.

N. 0° 00.6' E., on the N-S center line of section 9.

Over rolling mountainous land, through pinon, juniper, oak and serviceberry brush.

**39.923** Point for the center 1/4 section corner, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, in a mound of stone to top, with aluminum cap marked:

T33S R23E  
C 1/4 S9  
1993

Set a steel fence post alongside the aluminum post.

Corner is located 95 lks. dist., S of a 4 strand fence line, bears E and W.

**60.058** Point for the center N 1/16 section corner of section 9.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

THE SUBDIVISION OF SECTION 9,  
T. 33 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T33S R23E  
C  
N 1/16 | S9  
C  
1993

Corner is located on a SE slope.

**80.193** The 1/4 section corner of sections 4 and 9.

From the 1/4 section corner of sections 9 and 10.

N. 89° 50.5' W., on the E-W center line of section 9.

**19.893** Point for the center E 1/16 section corner of section 9.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T33S R23E  
C — E 1/16 — C  
S9  
1993

Set a steel fence post alongside the aluminum post.

Corner is located 15 lks. dist., S of a 4 strand fence line, bears E and W.

**39.786** The center 1/4 section corner of section 9.

**79.820** The 1/4 section corner of sections 8 and 9.

From the center E 1/16 section corner of section 9.

N. 0° 04.3' E., on the N-S center line of the NE 1/4 of section 9.

**20.152** Point for the NE 1/16 section corner of section 9, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T33S R23E  
NE 1/16 S9  
1993

THE SUBDIVISION OF SECTION 9,  
T. 33 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set a steel fence post alongside the aluminum post.

From this point, the corner of fences projecting E and S, bears N. 36° 38' W., 48.6 lks. dist.

**40.304** The E 1/16 section corner of sections 4 and 9.

---

From the N 1/16 section corner of sections 9 and 10.

N. 89° 53.4' W., on the E-W center line of the NE 1/4 of section 9.

**19.914** The NE 1/16 section corner of section 9.

**39.828** The center N 1/16 section corner of section 9.

---

The Subdivision of Section 17,  
T. 33 S., R. 23 E., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 17 and 20.

N. 0° 07.5' W., on the N-S center line of section 17.

Over mountainous land, through pinon, juniper, oak and serviceberry brush.

**19.643** Point for the center S 1/16 section corner of section 17.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T33S R23E  
C  
S 1/16 | S17  
C  
1993

Corner is located on a SE slope.

**39.286** Point for the center 1/4 section corner, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T33S R23E  
C 1/4 S17  
1993

THE SUBDIVISION OF SECTION 17,  
T. 33 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

**CHAINS****59.298**

Point for the center N 1/16 section corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a collar of stone, with aluminum cap marked:

T33S R23E  
C  
N 1/16 | S17  
C  
1993

**79.310**

The 1/4 section corner of sections 8 and 17.

---

From the 1/4 section corner of sections 16 and 17.

S. 89° 56.9' W., on the E-W center line of section 17.

**20.251**

Point for the center E 1/16 section corner of section 17.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T33S R23E  
C — E 1/16 — C  
S17  
1993

**40.502**

The center 1/4 section corner of section 17.

**60.374**

Point for the center W 1/16 section corner of section 17.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone to top, with aluminum cap marked:

T33S R23E  
C — W 1/16 — C  
S17  
1993

Set a steel fence post alongside the aluminum post.

**80.246**

The 1/4 section corner of sections 17 and 18.

---

From the center E 1/16 section corner of section 17.

N. 0° 25.7' W., on the N-S center line of the NE 1/4 of section 17.

THE SUBDIVISION OF SECTION 17,  
T. 33 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

**20.082** Point for the NE 1/16 section corner of section 17, at intersection with the E-W center line.  
  
Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T33S R23E  
NE 1/16 S17  
1993

**40.164** The E 1/16 section corner of sections 8 and 17.

---

From the N 1/16 section corner of sections 16 and 17.

S. 89° 45.1' W., on the E-W center line of the NE 1/4 of section 17.

**20.144** The NE 1/16 section corner of section 17.

**40.288** The center N 1/16 section corner of section 17.

---

From the W 1/16 section corner of sections 17 and 20.

N. 0° 05.2' W., on the N-S center line of the SW 1/4 of section 17.

**19.872** Point for the SW 1/16 section corner of section 17, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, with aluminum cap marked:

T33S R23E  
SW 1/16 S17  
1993

**39.744** The center W 1/16 section corner of section 17.

---

From the center S 1/16 section corner of section 17.

S. 89° 17.1' W., on the E-W center line of the SW 1/4 of section 17.

**19.889** The SW 1/16 section corner of section 17.

**39.778** The S 1/16 section corner of sections 17 and 18.

---

THE SUBDIVISION OF SECTION 17,  
T. 33 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the center W 1/16 section corner of section 17.

N. 0°22.1' W., on the N-S center line of the NW 1/4 of section 17.

**19.943** Point for the NW 1/16 section corner of section 17, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T33S R23E  
NW 1/16 S17  
1993

Raise a mound of stone W of the corner.

Corner is located on a NW slope in thick pinon, juniper and oak brush.

**39.886** The W 1/16 section corner of sections 8 and 17.

---

From the center N 1/16 section corner of section 17.

S. 89° 44.8' W., on the E-W center line of the NW 1/4 of section 17.

**19.955** The NW 1/16 section corner of section 17.

**39.910** The N 1/16 section corner of sections 17 and 18.

---

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD ASSISTANTS**

---

Name	Capacity
Philip Tobler Shawn Peterson	Surveying Technician Surveying Technician

## CERTIFICATE OF SURVEY

I, *Ferrel D. Reynolds, Cadastral Surveyor*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *27th day of July, 1993*, I have *dependently resurveyed a portion of the west boundary, a portion of the subdivisional lines, and subdivided sections 7, 8, 9, and 17, in Township 33 South, Range 23 East*, of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

May 22, 1996

\_\_\_\_\_  
Date

  
\_\_\_\_\_  
(Cadastral Surveyor)

\_\_\_\_\_  
Date

\_\_\_\_\_  
(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of a portion of the west boundary, a portion of the subdivisional lines, and the subdivision of sections 7, 8, 9, and 17, in Township 33 South, Range 23 East, Salt Lake Meridian, Utah*,

executed by *Ferrel D. Reynolds, Cadastral Surveyor*

having been critically examined and found correct, are hereby approved.

May 22, 1996

\_\_\_\_\_  
Date

  
\_\_\_\_\_  
(Chief Cadastral Surveyor for Utah)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

# FIELD NOTES

OF  
THE RETRACEMENT OF

THE UTAH AND ARIZONA STATE BOUNDARY

FROM MILE POST 58 TO MILE POST 60.19,

THE DEPENDENT RESURVEY OF SUBDIVISIONAL LINES

AND THE

SUBDIVISION OF SECTIONS 26, 27, 28, 29, 33, AND 34,

IN

TOWNSHIP 43 SOUTH, RANGE 10 WEST

OF THE SALT LAKE MERIDIAN  
IN THE STATE OF UTAH

EXECUTED BY

*Larry V. Judd*  
*Cadastral Surveyor*

Under special instructions dated *March 7, 1994*, approved *April 12, 1994*, which provided for the surveys included under Group Number *813*, and assignment instructions dated *April 13, 1994*.

Survey commenced *October 3, 1994*  
Survey completed *November 23, 1994*

**INDEX DIAGRAM**

Township 43 South , Range 10 West

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	7 24
	24 26	22 23	18 19	12 13	7 8
30	24 29	22 28	18 27	12 26	6 25
	23	19 20	14 16	10 9	6
31	32	19 33	15 34	10 35	36
	3	3 3 3	4 4	5 5	
	(20)	(15)	(11)		

The Subdivision of Section 26.....Page 26

The Subdivision of Section 27.....Page 30

The Subdivision of Section 28.....Page 36

The Subdivision of Section 29.....Page 38

The Subdivision of Section 33.....Page 39

The Subdivision of Section 34.....Page 42

## TOWNSHIP 43 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

The following field notes describe the retracement of the Utah and Arizona State Boundary (south boundary) from Mile post 58 to Mile post 60.19, the dependent resurvey of a portion of the subdivisional lines and the subdivision of sections 26, 27, 28, 29, 33, and 34, in Township 43 South, Range 10 West, Salt Lake Meridian, Utah.

History of Surveys

<u>Surveyed by</u>		<u>Retr. or Resurveyed by</u>	
<u>SOUTH BOUNDARY</u> (Utah - Arizona State Boundary)			
All	H.B. Carpenter	1901	
Portion			R.E.L. Collier & R. Gentry 1909
Portion			B.E. Craig 1993
<u>EAST BOUNDARY</u>			
All	R.E.L. Collier & R. Gentry	1909	
All			Jenkins & West 1897
Portion			M.H. Dalley 1929
Portion			Bird & Nelson 1924
<u>WEST BOUNDARY</u>			
All	R.E.L. Collier & R. Gentry	1909	
<u>NORTH BOUNDARY</u>			
All	R.E.L. Collier & R. Gentry	1909	
Portion			B.S. Owens & D.A. Cannon 1959
<u>SUBDIVISION</u>			
Portion	R.E.L. Collier & R. Gentry	1909	

The survey by B.E. Craig, Cadastral Surveyor for the Arizona State Office of the Bureau of Land Management is currently under review at the present time.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group 813, Utah, dated March 7, 1994.

## TOWNSHIP 43 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH

## CHAINS

Section 27 was resurveyed and subdivided by Dean D. Holliday, R.L.S. No. 4666, for Washington County in 1978. The 1/4 section corner of sections 27 and 34, shown as being reestablished from the original bearing trees was not found. Using record information taken from the Washington County Area Reference Plat of Section 27 to reestablish the 1/4 section corner position, creates a large discrepancy in the bearings and distances to the original bearing trees. No field note record could be found of the Washington County survey and ties to the original bearing trees. The 1/4 section corner was reestablished from the record tie to the original standing bearing tree as shown in the body of these notes. No record information from the Washington County survey was used to reestablish the 1/4 corner position.

The center 1/4 section corner of section 27, also established by Dean D. Holliday, R.L.S. No. 4666 for Washington County in 1978, was found to be out of position, due to the discrepancy with the 1/4 section corner of sections 27 and 34, and was not utilized as the C 1/4 section corner position.

A portion of the south boundary and subdivisional lines were resurveyed by F. Campbell and J. Ballard of Ballard and Campbell Engineering of Hurricane Utah.

The directions of lines were determined by references to true meridians established on line by hour angle observations of the sun and Polaris. The lines were carried forward by sustained angulations, being supplemented by other observations taken throughout the progress of the survey. Distances were determined by electronic measurement.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. The retracement data were thoroughly verified and only the true line notes are given herein.

The geographic position of Mile Post No. 58 on the Utah - Arizona State boundary as determined by Belle A. Craig, Cadastral Surveyor for the Arizona State office of the Bureau of Land Management, during a dependent resurvey of a portion of the Utah - Arizona State boundary line, from August 16, 1993 to October 5, 1993 as determined by the technique of static differential positioning is as follows:

Latitude  $37^{\circ} 00' 00.62''$  N.      Longitude  $112^{\circ} 59' 54.92''$  W.  
N.A.D. 1927

The mean magnetic declination as projected from the U.S. Geological Survey "Magnetic Declination Map of 1990" is:  $13 \frac{1}{2}^{\circ}$  East.

---

Retracement of the Utah and Arizona State Line  
from Mile Post 58 to Mile Post 60.19  
T. 43 S., R. 10 W., Salt Lake Meridian, Utah

---

RETRACEMENT OF THE UTAH AND ARIZONA STATE LINE  
FROM MILE POST 58 TO MILE POST 60.19,  
T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Reestablishment of the Survey Executed by  
H.B. Carpenter in 1901, and the Resurvey  
by B.E. Craig in 1993.

Beginning at Mile Post 58 on the Utah - Arizona State boundary, monumented with an iron post, 2 ins. diam., firmly set, projecting 2 ins. above ground with brass cap marked, with raised letters, UTAH on the N. and ARIZ. on the S., 58M stamped in the center, and 1993.

from which

A stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, bears S.  $87^{\circ}53'$  E., 36.6 ft. dist., with cap marked RM 58M T42N R7W ARIZ 36.6 ft. TO COR 1993 and an arrow pointing to the corner.

A stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, bears N.  $8^{\circ}20'$  W., 66.8 ft. dist., with cap marked RM 58M T43S R10W UTAH 66.8 ft. TO COR 1993 and an arrow pointing to the corner.

Corner is located in barbed wire fence extending east and west, from which the center line of Uzona Ave., extending east and west, a graded dirt road, 60 lks. wide, bears south, 0.45 chs. dist.

N.  $89^{\circ}52.6'$  E., on the 59th mile.

- 2.38** Center line of Utah State road No. 59, and Arizona State road No 389, bears N.  $32^{\circ}34'$  W. and S.  $32^{\circ}34'$  E.
- 4.524** Intersect point for the closing corner of sections 32 and 33, on the south boundary of T. 43 S., R. 10 W., Salt Lake Meridian, Utah.
- From which the true monumented closing corner of sections 32 and 33, T. 43 S., R. 10 W., bears S.  $0^{\circ}05.3'$  E., 0.006 chs. dist., hereinafter described.
- 44.524** Point for the 1/4 section corner of section 33 only, on the south boundary of section 33, T. 43 S., R. 10 W.; not monumented.
- 80.563** Mile Post 59, monumented with a aluminum rod, 5/8 in. diam., found 18 ins. below the surface of Uzona Ave., with 2 1/2 in. diam., aluminum cap marked 59M T43S R10W S33 UTAH ARIZ S31 T42N R6W 1993.

RETRACEMENT OF THE UTAH AND ARIZONA STATE LINE  
FROM MILE POST 58 TO MILE POST 60.19,  
T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

from which

A stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, bears N.  $55^{\circ}55'$  E., 60.1 ft. dist., with cap marked RM 59M T43S R10W UTAH 60.1 ft. TO COR 1993 and an arrow pointing to the corner.

A stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, bears S.  $45^{\circ}20'$  E., 45.4 ft. dist., with cap marked RM 59M T42N R6W ARIZ 45.4 ft. TO COR 1993 and an arrow pointing to the corner.

The corner falls 20 lks. N. of the S. edge of Uzona Ave., a graded road, 45 lks. wide, bears E and W.

---

N.  $89^{\circ}52.6'$  E., on the 60th mile.

- 3.961** Point for the closing corner of sections 33 and 34, on the south boundary of T. 43 S., R. 10 W., Salt Lake Meridian, Utah, at proportionate distance, based on the official record of 1909 survey, hereinafter described.
- 31.380** Intersect point for the closing corner of sections 31 and 32, T. 42 N., R. 6 W., on the north boundary of T. 42 S., R. 6 W., Gila and Salt River Meridian, Arizona.
- From which the true monumented closing corner of sections 31 and 32, T. 42 S., R. 6 W., bears North, 0.02 chs. dist., monumented with an iron post, 2 ins. diam., firmly set flush with the ground, with brass cap marked AM CC S31 S32 T42N R6W 1916 1993.
- From which
- The northeast corner of house, bears S.  $8^{\circ}$  W., 0.044 chs. dist., and a rock retaining wall extending E and W, 2. ft. wide, 2 1/2 ft. high, bears South, 0.064 chs. dist.
- 43.882** Point for the 1/4 section corner of section 34 only, on the south boundary of section 34, T. 43 S., R. 10 W.; not monumented.
- 71.438** The 1/4 section corner of section 32 only, on the north boundary of T. 42 N., R. 6 W., Gila and Salt River Meridian, Arizona, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap marked UTAH 1/4 S32 T42N R6W 1993.

RETRACEMENT OF THE UTAH AND ARIZONA STATE LINE  
FROM MILE POST 58 TO MILE POST 60.19,  
T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

from which

A stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, bears N. 54° 30' E., 28.5 ft. dist., with cap marked RM T43S R6W 28.5 ft. TO COR 1993 and an arrow pointing to the corner.

A stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, bears S. 38° E., 23.0 ft. dist., with cap marked RM T42N R6W 23.0 ft. TO COR 1993 and an arrow pointing to the corner.

The corner falls 7 lks. S. of a E - W, 4 strand barbed wire fence.

**83.803** Point for the closing corner of sections 34 and 35, on the south boundary of T. 43 S., R. 10 W., Salt Lake Meridian, Utah, at proportionate distance based on the record of Campbell Engineering, hereinafter described.

**93.80** Trail road, 20 lks. wide, bears NE and SW.

**94.05** Center of canal, 25 lks. wide, 3 ft. deep, drains SW.

**95.276** Mile Post 60.19, monumented with stainless steel post, 2 1/2 ins. diam., firmly set in a mound of stone, with brass cap marked 60.19M T43S R10W S35 UTAH ARIZ T42N R6W S32 CPWA 1993.

from which

A juniper, 12 ins. diam., bears N. 74° E., 28 lks. dist., mkd. UTAH 60.19M BT, on partially healed blaze.  
( 1901 BT )

A pinon, 14 ins. diam., bears S. 64° 30' W., 23 lks. dist., mkd. UTAH 60.19M BT, on partially healed blaze.  
( 1901 BT )

A pinon, 10 ins. diam., bears S. 27° E., 77 lks. dist., mkd. ARIZ 60.19M BT. ( 1993 BT ).

---

Dependent Resurvey of a Portion of the Subdivisional Lines  
T. 43 S., R. 10 W., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by  
R.E.L. Collier and R. Gentry in 1909

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the corner of sections 25, 26, 35, and 36, monumented with a sandstone 22x8x6 ins., firmly set, plainly marked 1 notch on the E. and 1 notch on the S. edges.

from which

A pinon, 10 ins. diam., bears S. 30° E., 55 lks. dist.,  
mkd. T43S R10W S36 BT.

A pinon, 10 ins. diam., bears N. 25° W., 72 lks. dist.,  
(record N. 28° 20' W., 34 lks.) mkd. T43S R10W S26 BT.

The NE bearing tree was found at record bearing and distance,  
down and dead.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to  
bedrock, set in a mound of stone with aluminum cap marked:

T43S R10W	
S26	S25
S35	S36
1994	

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel  
post.

The corner falls on a gradual SW slope, 20 lks. E. of abrupt edge of broken  
sandstone ledges.

N. 0° 00.8' E., between sections 25 and 26.

On gradual to moderate westerly slope.

**19.967** Point for the S 1/16 section corner of sections 25 and 26, not monumented.

**39.934** The 1/4 section corner of sections 25 and 26, monumented with an iron post, 1 in.  
diam., firmly set, projecting 10 ins. above ground, with brass cap marked as  
described in the official record of the survey executed in 1909 by Collier and  
Gentry.

from which

A pinon, 8 ins. diam., bears S. 77° 20' E., 40 lks. dist.,  
marked 1/4 S25 BT.

A juniper, 10 ins. diam., bears S. 11° 45' W., 23 lks. dist.,  
marked 1/4 S26 BT.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Raise a mound of stone around the iron post, 4 ft. base to top of brass cap.

The corner falls, 15 lks. east of the top of a spur, on a slight easterly slope, in manzanetta undergrowth, with scattered pinon and juniper.

---

N. 0°09.2' W., beginning new measurement.

Descending ridge.

**19.938** Point selected for the witness corner to the N 1/16 section corner of sections 25 and 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, set in a mound of stone 5 ft. base to top of aluminum cap marked:

T43S R10W  
WC  
N 1/16  
S26 | S25  
1994

The corner falls at base of sandstone ledges on steep westerly slope.

**20.036** True point for the N 1/16 section corner of sections 25 and 26, falls on exposed sandstone ledges, unsuitable for permanent monumentation, not monumented.

**39.12** North bank of drainage, approximately 2 1/2 chs. wide, 25 ft. deep, drains NW.

**40.072** Point for the corner of sections 23, 24, 25, and 26, at proportionate distance. There is no remaining evidence of the position of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground over the top of a steel fence post, 5 1/2 ft. long driven 5 ft. into sandy ground, with aluminum cap marked:

T43S R10W  
S23 | S24  
S26 | S25  
1994

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the corner.

The corner falls on flat sandy ground, 8 lks. dist., S. of a 4 strand barbed wire fence, bears E - W.

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the 1/4 section corner of sections 24 and 25, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above a mound of stone, with brass cap marked as described in the official record of the survey executed in 1909 by Collier and Gentry.

from which

A pinon, 16 ins. diam., bears N.  $0^{\circ}40'$  E., 32 lks. dist.,  
marked 1/4 S24 BT.

The SE BT was found at record bearing and dist., down and dead.

The corner falls on gradual easterly slope.

S.  $89^{\circ}55.2'$  W., between sections 24 and 25.

Ascending on gradual easterly slope.

**15.60** Top of ridge and beginning of steep decent.

**19.969** Point for the W 1/16 section corner of sections 24 and 25.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, set in a mound of stone, 5 ft. base, to top of aluminum cap marked:

	T43S R10W
W 1/16	<u>S24</u>
	S25
	1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

The corner falls on gradual westerly slope on broken ground, 18 lks. W. of a trail, 4 lks. wide, bears NE and SW

**20.45** Top of vertical ledge, 20 ft. high, bears N - S.

**39.938** The corner of sections 23, 24, 25, and 26.

---

N.  $0^{\circ}01.7'$  W., between sections 23 and 24.

Through bottom lands of Short Creek.

**40.071** The 1/4 section corner of sections 23 and 24, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, with brass cap marked as described in the official record of the survey executed in 1909 by Collier and Gentry.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

from which

A pinon, 6 ins. diam., bears S.  $41^{\circ}40'$  E., 14 lks. dist.,  
with marks 4 BT, visible on partially cut out blaze.

The NW bearing tree was found at record bearing and  
dist., down and dead.

And a new tree.

A juniper 10 ins. diam., bears N.  $30^{\circ}$  W., 75 lks. dist.,  
marked 1/4 S23 BT.

The corner falls on a moderate E. slope.

---

From the corner of sections 25, 26, 35, and 36.

N.  $89^{\circ}56.5'$  W., between sections 26 and 35.

Descending on steep westerly slope.

**20.071** Point for the E 1/16 section corner of sections 26 and 35.

Set a 3/4 in. rebar, 12 ins. long, drilled 9 ins. into a sandstone boulder, 8 1/2 X 7 X  
11 ft. above ground, in crack of boulder, 2 ft. below the top, with 3 1/4 in. diam.,  
aluminum cap marked:

	T43S R10W
E 1/16	<u>S26</u>
	S35
	1994

**40.142** The 1/4 section corner of sections 26 and 35, monumented with an iron post, 1 in.  
diam., firmly set, projecting 5 ins. above ground, with brass cap marked as described  
in the official record of the survey executed in 1909 by Collier and Gentry.

from which

A oak, 10 ins. diam., bears N.  $21^{\circ}10'$  E., 69 lks. dist.,  
with scribe marks visible through partially healed  
blaze.

The SE bearing tree has been cut down.

And a new tree.

A juniper 6 ins. diam., bears S.  $63^{\circ}$  E., 35 1/2 lks. dist.,  
marked X BT.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

Raise a mound of stone, 2 1/2 base by 1 ft. high, N. of the corner.

The corner falls on flat bench land, in scattered juniper.

From the corner of sections 26, 27, 34, and 35, monumented with sandstone 20x14x6 ins., firmly set, plainly marked with 2 notches on the E. and 1 notch on the S. edges.

from which

A juniper, 16 ins. diam., bears N. 27° E., 57 lks. dist., marked T43S R10W S26 BT. (record N. 52° E., 35 lks. dist.)

A juniper, 12 ins. diam., bears S. 45° 30' E., 53 1/2 lks. dist., with scribe marks BT visible. ( record 19 lks. dist.)

A juniper, 26 ins. diam., bears S. 22° W., 54 1/2 lks. dist., marked T43S R10W S34 BT. ( record S. 30° W., 25 lks. dist. )

A juniper, 34 ins. diam., tied 8 in. diam., branch, bears N. 55° 30' W., 92 lks. dist., marked T43S R10W S27 BT. ( record N. 61° 30' W., 62 lks. dist. )

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T43S R10W	
S27	S26
S34	S35
1994	

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

Raise a mound of stone, 5 ft. base, 2 ft. high, W. of the corner.

The corner falls on a moderate easterly rocky slope in scattered juniper.

S. 0° 03.3' E., between sections 34 and 35

Over easterly slope and through residential area.

35.25

Record distance for the witness 1/4 section corner of sections 34 and 35, falls on the southerly side of a graded dirt road, on a curve in a area of disturbance. There is no remaining evidence of the original witness corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

35.45

Barbed wire fence along the westerly bank of Short Creek, bears N. 50° E. and S. 50° W.

36.179

Point selected for the witness 1/4 section corner to the corner of sections 34 and 35.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground over the top of a steel fence post, 5 1/2 ft long driven 5 ft. into sandy ground, with aluminum cap marked:

T43S R10W  
WC  
1/4  
S34 | S35  
1994

The corner falls on a narrow finger of sand, 12 lks. wide, projecting S. 40° W., into Short Creek.

39.999

Point for the 1/4 section corner of sections 34 and 35, at proportionate distance, falls within Short Creek.

58.898

Point for the closing corner of sections 34 and 35, at intersection with the Utah and Arizona State line. There is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T43S R10W  
CC  
S34 | S35  
T42N R6W  
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

Raise a mound of stone, 2 ft. base, 1 ft. high, N. of the corner.

The corner falls on flat ground, 3 1/2 lks. S. of a 4 strand barbed wire fence, bears E - W., and 4 1/2 lks., N. of the north edge of dirt road, 14 lks. wide, bears E - W.

From this corner point, the 60.19 mile post on the Utah - Arizona State line, bears N. 89° 52.6' E., 11.473 chs. dist., hereinbefore described.

From the corner of sections 26, 27, 34, and 35.

N. 0° 04.2' E., between sections 26 and 27.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Over northeasterly slope of ridge into bottom land.

**20.018** Point for the S 1/16 section corner of sections 26 and 27; not monumented.

**40.036** The 1/4 section corner of sections 26 and 27, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, 4 ft. base, 4 ft. high, with brass cap marked as described in the official record of the survey executed in 1909 by Collier and Gentry.

from which

A juniper, 10 ins. diam., bears S.  $69^{\circ}$  E., 43 lks. dist.,  
marked 1/4 S26 BT. ( record S.  $74^{\circ}20'$  E., 42 lks. dist. )

A juniper, 15 ins. diam., bears S.  $61^{\circ}$  W., 43 1/2 lks. dist.,  
marked 1/4 S27 BT. ( record S.  $66^{\circ}15'$  W., 41 lks. dist. )

The corner falls on a gradual SW slope on rocky ground.

---

N.  $0^{\circ}04.6'$  E., beginning new measurement.

**19.939** Point for the N 1/16 section corner of sections 26 and 27; not monumented.

**39.878** The corner of sections 22, 23, 26, and 27, monumented with a Washington County galvanized post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above a mound of stone, with brass cap marked T43S R10W SLB-M 22 23 26 27 1979.

This corner is accepted as a careful and faithful perpetuation of the position of the original corner.

from which

A pinon, 12 ins. diam., bears S.  $58^{\circ}$  E., 72 lks. dist., marked  
T43S R10W S26 BT ( record S.  $57^{\circ}30'$  E., 75 lks. dist. )

A pinon, 12 ins. diam., bears S.  $88^{\circ}$  W., 60 lks. dist.,  
marked T43S R10W ( record S.  $84^{\circ}30'$  W. )

A juniper, 22 ins. diam., bears N.  $20^{\circ}$  W., 38 lks. dist.,  
marked T43S R10W S22 BT ( record N.  $25^{\circ}30'$  W. )

The NE bearing tree was found down and dead.

The corner falls on a steep SE slope, near base of vertical ledges.

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the corner of sections 23, 24, 25, and 26.

N.  $89^{\circ}56.5'$  W., between sections 23 and 26.

Over bottom lands of Short Creek.

**19.969** Point for the E 1/16 section corner of sections 23 and 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T43S R10W
E 1/16	<u>S23</u>
	S26
	1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

Raise a mound of stone, 4 ft. base, 2 ft. high, N. of the corner.

The corner falls on flat ground, 7 lks. N. of a 4 strand barbed wire fence, bears E - W., and 3 lks., S. of the south edge of an A.T.V. trail, 6 lks. wide, bears E - W.

**39.938** The 1/4 section corner of sections 23 and 26, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground set in a collar of stone, with brass cap marked as described in the official record of the survey executed in 1909 by Collier and Gentry.

The corner falls on flat sandy ground, in sagebrush undergrowth, 1 1/2 lks. S. of fence corner of E - W - N projecting fences.

S.  $89^{\circ}54.2'$  W., beginning new measurement.

**19.976** Point for the W 1/16 section corner of sections 23 and 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T43S R10W
W 1/16	<u>S23</u>
	S26
	1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

Raise a mound of stone, 4 ft. base, 3 ft. high, N. of the corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

The corner falls on a gradual SW slope.

**21.50** Drainage, 30 lks. wide, bears N. 70 W., and S. 15° E.

**39.952** The corner of sections 22, 23, 26, and 27.

From the corner of sections 27, 28, 33, and 34, monumented with a sandstone, 28x12x8 ins., firmly set, plainly marked with 1 notch on the S. and 3 notches on the E. edges, with a mound of stone W. of the corner.

from which

A juniper, 10 ins. diam., bears S. 27° 55' E., 1.81 chs. dist.,  
marked T43S R10W S34 BT.

A juniper, 15 ins. diam., bears S. 41° W., 19 lks. dist.,  
with faint scribe marks visible ( record 17 lks. dist.)

A juniper, 10 ins. diam., bears N. 83° 20' W., 1.79 chs.  
dist., marked T43S R10W S28 BT.

The NE bearing tree was found down and dead, at record bearing and dist.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with  
aluminum cap marked:

T43S R10W	
S28	S27
S33	S34
1994	

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel  
post.

Raise a mound of stone, 4 ft. base, 2 ft. high, W. of the corner.

The corner falls on a steep SW slope.

S. 0° 07.6' E., between sections 33 and 34.

Descending on steep southerly slope.

**20.108** Point for the N 1/16 section corner of sections 33 and 34; not monumented.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

40.216

Point for the 1/4 section corner of sections 33 and 34, at proportionate distance; there is no remaining evidence of the position of the original corner.

Set a rebar 3/4 in. diam., 24 ins. long, 4 ins. below the surface of Utah Avenue, with 3 1/4 ins. diam., aluminum cap marked:

T43S R10W  
1/4  
S33 | S34  
1994

from which

An aluminum post, 30 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 42° 57' E., 52.6 ft. dist., with cap marked T43S R10W RM S34 52.6 FT. 1994 and an arrow pointing to the corner.

An aluminum post, 30 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 48° 28.5' W., 55.4 ft. dist., with cap marked T43S R10W RM S33 55.4 FT. 1994 and an arrow pointing to the corner.

Deposit a magnet, 1 x 1 x 1 7/8 ins. long beneath each of the aluminum posts.

The corner falls in the center of Utah Ave., a paved road, 36 lks. wide, bears E - W.

From this corner point, a bolt, 1 in. diam., set flush with the road surface, bears N. 5° W., 0.84 ft. dist., as set by Ballard and Campbell Engineering for the 1/4 section corner position, using improper methods, not utilized in the course of this survey.

58.926

Point for the closing corner of sections 33 and 34, at intersection with the Utah and Arizona State line. No remaining evidence of the original sandstone, 20x8x6 ins., was found.

This point was reestablished by Ballard and Campbell Engineering during the course of a survey, by proportionate distance. The original bearing tree was not searched for during this survey. This point is utilized as the closing corner position, with a new tie made to the original bearing tree. No remaining evidence of the monument set by Ballard and Campbell was found.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 1 ft. below the surface of Lauritzen street, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T43S R10W  
CC  
S33 | S34  
T42N R6W  
1994

from which the original bearing tree, with a new tie.

A juniper, 30 ins. diam., bears N.  $73^{\circ}02'$  W., 2.50 chs. dist., ( record,  
N.  $76^{\circ}15'$  W., 2.49 chs. ) marked CC T43S R10W S33 BT, visible on  
partially healed blaze.

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel  
post.

The corner falls 20 lks. W., of the E. edge of Laurtizen Street, a dirt road, 44 lks.  
wide, bears N - S, and 44 lks. W. of a 4 strand barbed wire fence, bears N - S.

From this corner point, the 59 mile post on the Utah - Arizona State line, bears  
S.  $89^{\circ}52.6'$  W., 3.961 chs. dist., hereinbefore described.

From the corner of sections 26, 27, 34, and 35.

S.  $89^{\circ}53.4'$  W., between sections 27 and 34.

**20.011** Point for the E 1/16 section corner of sections 27 and 34.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with  
aluminum cap marked:

T43S R10W  
E 1/16  $\frac{S27}{S34}$   
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel  
post.

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the corner.

The corner falls on a gradual N. slope, 65 lks. S., of the center of a trail road, 12  
lks. wide, bears N.  $82^{\circ}$  E.

**40.022** The corner for the 1/4 section corner of sections 27 and 34, is determined at record  
bearing and distance from the remains of the original bearing trees.

A juniper 7 ins. diam., bears N.  $67^{\circ}$  E., 36 lks. dist., marked  
1/4 S 27 BT.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

A pinon 10 ins. diam., laying dead on top of the ground, with no stump or stump hole to determine its original position. A tie to the trees approximate original location bears S. 69° W., 1.42 chs. dist.

There was no remaining evidence of the original iron post, set by Collier and Gentry in 1909, or the galvanized post set by Washington County in 1979. A steel fence post was found, 1 lk. W. of this corner position.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

T43S R10W  
1/4      $\frac{S27}{S34}$   
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

Raise a mound of stone, 4 ft. base, 3 ft. high N. of the corner.

The corner falls on a steep rocky SW slope.

S. 89°54.5' W., beginning new measurement.

**19.942** Point for the W 1/16 section corner of sections 27 and 34.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, set in a mound of stone, 4 ft. base, to top of aluminum cap marked:

T43S R10W  
W 1/16      $\frac{S27}{S34}$   
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

The corner falls on flat rocky ground, 3 lks. S., of the south edge of a drainage 10 feet deep, drains SE.

**39.884** The corner of sections 27, 28, 33, and 34.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

N.  $0^{\circ}03.0'$  E., between sections 27 and 28.

Over mountainous terrain.

39.904

The  $1/4$  section corner of sections 27 and 28, monumented with a Washington County galvanized post, 2  $1/2$  ins. diam., firmly set, projecting 2 ins. above ground, with steel fence post 1 lk. S. of the corner, with brass cap marked T43S R10W  $1/4$  S28 S27 1979. This corner is accepted as a careful and faithful reestablishment of the original corner. There was no remaining evidence of the original corner.

The corner falls on a steep NW slope.

N.  $0^{\circ}06.4'$  E., beginning new measurement.

39.911

The corner of sections 21, 22, 27, and 28, monumented with a sandstone, 20x10x8 ins., firmly set, plainly marked with 3 notches on the E., and 2 notches on the S. edges.

from which

A juniper, 21 ins. diam., bears N.  $66^{\circ}45'$  W., 20 lks. dist.,  
marked T43S R10W S21 BT, visible on partially healed blaze.

The remaining original bearing trees, were found at approximate record bearing and dist., all down and dead.

At the corner point

Set an aluminum post, 30 ins. long, 2  $1/2$  ins. diam., 24 ins. in the ground, with aluminum cap marked:

T43S R10W	
<u>S21</u>	<u>S22</u>
S28	S27
1994	

Deposit a magnet, 1 x 1 x  $1 \frac{7}{8}$  ins. in clear plastic case beneath the stainless steel post.

Raise a mound of stone, 5 ft. base, 2 ft. high W. of the corner.

The corner falls on the northerly side of a drainage, drains SW., on a moderate SW slope.

From the corner of sections 22, 23, 26, and 27.

S.  $89^{\circ}48.9'$  W., between sections 22 and 27.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Over mountainous terrain.

**19.973** Point for the E 1/16 section corner of sections 22 and 27; not monumented.

**39.946** The 1/4 section corner of sections 22 and 27, monumented with a Washington County galvanized post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground in a small mound of stone, with a steel fence post set 2 lks. NW of the corner. This corner is accepted as a careful and faithful perpetuation of the position of the original corner.

The original corner, an iron post, 3 ft. long, 1 in. diam., was found near the Washington County post, laying loose, 3 ins. below ground. I was unable to determine the true position of this corner, with no remaining evidence of the original bearing trees. I placed the iron post inside the Washington County galvanized post.

The corner falls on flat sandy ground at edge of large cactus patch, 1 ch. E., of the east bank of a drainage, 35 ft. deep, drains SE.

---

S. 89° 50.3' W., beginning new measurement.

**39.940** The corner of sections 21, 22, 27, and 28.

---

From the corner of sections 28, 29, 32, and 33, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap marked as described in the official record of the survey executed by Collier and Gentry in 1909.

The corner falls on the N edge of a dirt road, 24 lks. wide, bears E - W, in an old railed area. The original NE and SW bearing trees, were found railed out, down and dead. There was no remaining evidence of the SE and NW trees.

Raise a mound of stone around the iron post.

S. 0° 05.3' E., between sections 32 and 33.

Over flat sandy ground.

**20.016** Point for the N 1/16 section corner of sections 32 and 33; not monumented.

**40.032** Point for the 1/4 section corner of sections 32 and 33, as determined from record data taken from the plat of survey by Ballard and Campbell Engineering, in a resurvey of the line between sections 32 and 33, during which time the original 1/4 section corner was tied. There is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a rebar 3/4 in. diam., 24 ins. long, 4 ins. below the surface of Utah Avenue, with 3 1/4 ins. diam., aluminum cap marked:

T43S R10W  
1/4  
S32 | S33  
1994

from which

A 3/8 in. bolt, 4 ins. long, with 1 in. diam., washer, set in a power pole facing the corner, bears S.  $31^{\circ}51.7' W.$ , 55.60 ft. dist., with washer marked RM 1994

A 3/8 in. bolt, 4 ins. long, with 1 in. diam., washer, set in a power pole facing the corner, bears N.  $33^{\circ}15.7' W.$ , 53.30 ft. dist., with washer marked RM 1994.

The corner falls 3.5 lks. S. of the center of Utah Avenue, a paved road, 36 lks. wide, bears E - W.

**58.935** True point for the closing corner of sections 32 and 33, at intersection with Utah and Arizona State line, monumented with a rebar, 5/8 in. diam., firmly set with yellow plastic cap marked B & C Engineering LS 4490.

From this corner point, the original closing corner, monumented with an iron post, 2 ins. diam., firmly set, 1 ft. below ground and a steel fence post alongside, with brass cap marked as described in the official record of the survey executed in 1909 by Collier and Gentry, bears S.  $0^{\circ}05.3' E.$ , 0.006 chs. dist.

Add the marks AM 1994 to the brass cap.

The corner point falls on flat ground on the S. side of Uzona Ave., a graded dirt road, 60 lks. wide, bears E - W.

From this corner point, the 58 mile post on the Utah - Arizona State line, bears S.  $89^{\circ}52.6' W.$ , 4.524 chs. dist., hereinbefore described.

From the corner of sections 27, 28, 33, and 34.

S.  $89^{\circ}52.2' W.$ , between sections 28 and 33.

Over broken mountainous slope.

**40.007** The 1/4 section corner of sections 28 and 33, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, with brass cap marked as described in the official record of the survey executed in 1909 by Collier and Gentry.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

from which the original bearing trees

A pinon, 16 ins. diam., bears S.  $42^{\circ}$  E., 7 lks. dist., marked  
1/4 S33 BT.

A pinon, 8 ins. diam., bears N.  $85^{\circ}45'$  W., 58 lks. dist., marked  
1/4 S28 BT.

The corner falls on steep SW slope.

S.  $89^{\circ}53.8'$  W., beginning new measurement.

**19.971** Point for the W 1/16 section corner of sections 28 and 33.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with  
aluminum cap marked:

T43S R10W  
W 1/16     S28  
                  S33  
                  1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel  
post.

Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, N. of the corner.

The corner falls on flat sandy ground, 17 lks. north of the center of a trail road, 18  
lks. wide, bears E - W.

**39.942** The corner of sections 28, 29, 32, and 33.

N.  $0^{\circ}07.2'$  W., between sections 28 and 29.

Over gradual slope.

**19.28** Center of dirt trail road, 15, lks. wide, bears E - W.

**19.993** Point for the S 1/16 section corner of sections 28 and 29.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, set in a  
mound of stone, 5 ft. base, to top of aluminum cap marked:

T43S R10W  
S 1/16  
S29 | S28  
1994

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

The corner falls in the bottom of a drainage, 4 lks. wide, course S. 30° W.

**39.986** The 1/4 section corner of sections 28 and 29, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, with brass cap marked as described in the official record of the survey by Collier and Gentry in 1909.

from which the original bearing trees

A juniper, 16 ins. diam., bears S. 35° E., 35 lks. dist., marked  
1/4 S28 BT.

A pinon, 16 ins. diam., bears N. 74° W., 28 lks. dist.,  
( record N. 70°30' W., 27 lks. dist.) marked 1/4 S29 BT.

N. 0°17.2' W., beginning new measurement.

**32.669** The witness corner to the corner of sections 20, 21, 28, and 29, monumented with a sandstone boulder, 12x10x8 ft. above ground, with another sandstone boulder, 6x6x6 ft. on top, with illegible marks on the point of the boulder and a small mound of stone at the base of the boulder.

from which the original bearing tree

A juniper, 14 ins. diam., bears S. 25°44' E., 3.665 chs. dist.,  
( record S. 29° E., 3.78 chs. dist.) marked WC T43S R10W S28 BT.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, set in a mound of stone 5 ft. base to top of aluminum cap marked:

T43S R10W  
WC

S29 | S28  
1994

from which

A sandstone boulder 7x7x7 ft. above ground, marked X BO, bears  
N. 65° E., 13.5 lks. dist.

The corner falls at the base of the boulder on a steep south slope.

**33.02** Base of vertical sandstone face.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

39.869

Point for the corner of sections 20, 21, 28, and 29, at record dist., extending the line through the witness corner, falls in sandstone ledges. not monumented.

From the corner of sections 21, 22, 27, and 28.

S.  $89^{\circ}54.7'$  W., between sections 21 and 28.

Over broken mountainous terrain.

24.25

Record distance for the original witness corner to the 1/4 section corner of sections 21 and 28. There is no remaining evidence of the witness corner.

40.163

Point for the 1/4 section corner of sections 21 and 28, at proportionate distance.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, set in a mound of stone, 4 ft. base, to top of aluminum cap marked:

T43S R10W

1/4      $\frac{S21}{S28}$   
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

from which

A juniper, 32 ins. diam., bears S.  $53^{\circ}$  E., 59 lks. dist., marked  
1/4 S28 BT.

A pinon, 10 ins. diam., bears N.  $8^{\circ}$  W., 22 lks. dist., marked  
1/4 S21 BT.

The corner falls on a steep easterly slope.

80.326

True point for the corner of sections 20, 21, 28, and 29.

From the corner of sections 29, 30, 31, and 32, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground in a collar of stone, with brass cap marked as described in the official record of the survey by Collier and Gentry in 1909.

N.  $0^{\circ}06.3'$  W., between sections 29 and 30.

Over flat ground.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

- 0.115** State Road No. 59, right of way fence.
- 0.99** Center line of State Road No. 59, bears N 58° 17' W.
- 20.017** Point for the S 1/16 section corner of sections 29 and 30.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:
- T43S R10W  
S 1/16  
S30 | S29  
1994
- Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.
- Raise a mound of stone, 1 1/2 ft. by 1 ft. high, W. of the corner.
- Set a 6 ft. steel fence post, alongside.
- The corner falls in a N - S, 4 strand barbed wire fence on flat ground, in sagebrush undergrowth and scattered juniper.
- 40.034** The 1/4 section corner of sections 29 and 30, monumented with an iron post, 1 in. diam., firmly set, 1 ft. below ground and a steel fence post E. of the corner, with brass cap marked as described in the official record of the survey executed in 1909 by Collier and Gentry.
- from which
- A juniper, 12 ins. diam., bears S. 69° 50' W., 34 lks. dist., marked  
1/4 S30 BT. (record 32 lks.)
- There is no remaining evidence of the original NE bearing tree.
- Reset the post, to project 2 ins. above ground and raise a mound of stone, 3 ft. base, 2 ft. high W. of the corner.
- The corner falls in a N - S, 4 strand barbed wire fence.
- 
- N. 0° 05.6' W., beginning new measurement.
- 40.013** The corner of sections 19, 20, 29, and 30, monumented with a rusted off 2 in. diam., iron post, 2 ft. long, with top part of post and brass cap not found.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

from which the original bearing trees

A pinon, 16 ins. diam., bears N.  $31^{\circ}45'$  E., 47 lks. dist., marked  
T43S R10W S19 BT.

A pinon, 16 ins. diam., bears S.  $38^{\circ}50'$  E., 104 lks. dist., marked  
T43S R10W S29 BT.

A pinon, 16 ins. diam., bears S.  $19^{\circ}45'$  W., 26 lks. dist., marked  
T43S R10W S30 BT.

A juniper, 16 ins. diam., bears N.  $32^{\circ}40'$  W., 47 lks. dist., marked  
T43S R10W S19 BT.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with  
aluminum cap marked:

T43S R10W	
S19	S20
S30	S29
1994	

Deposit the remainder of the original iron post inside the aluminum post.

Raise a mound of stone, 5 ft. by 3 ft. high, W. of the corner.

The corner falls on a gradual easterly slope.

N.  $89^{\circ}50.2'$  E., between sections 20 and 29.

Over mountainous terrain.

**16.860** Found a 1 in. diam., iron post, firmly set, projecting 18 ins. above ground, with  
brass cap marked WC 1/4 S20 S29 1909.

There is no official record in the 1909 survey by Collier and Gentry of this corner  
being set.

Raise a mound around the iron post, 5 ft. base to top of brass cap.

**16.890** The point to the 1/4 section corner of sections 20 and 29, at the foot of vertical  
sandstone ledge, with the face of the sandstone ledge marked X S20 WC S29  
( record X WP 1/4 S20 S29 ).

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

from which the original bearing tree.

A juniper, 18 ins. diam., bears S.  $67^{\circ}40'$  W., 2.05 chs. dist.,  
marked WC 1/4 S29 BT. (record S.  $70^{\circ}$  W., 2.02 chs. dist.).

S  $89^{\circ}58.0'$  E., beginning new measurement.

**23.084** Point for the 1/4 section corner of sections 20 and 29, at proportionate distance.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with  
aluminum cap marked:

T43S R10W  
1/4      $\frac{S20}{S29}$   
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel  
post.

The corner falls on a steep SE slope in scattered pinon and juniper.

This corner was not set in the original survey. Proportionate measurement is based  
upon an 80 chain mile, between sections 20 and 29.

**62.970** True point for the corner of sections 20, 21, 28, and 29.

The Subdivision of Section 26,  
T. 43 S., R. 10 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 26 and 35.

N.  $0^{\circ}04.2'$  E., on the N - S center line of section 26.

**19.988** Point for the center S 1/16 section corner of section 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins in the ground to  
bedrock, set in a mound of stone, 5 ft. base, to top of aluminum cap marked:

T43S R10W  
C  
S 1/16 | S26  
C  
1994

THE SUBDIVISION OF SECTION 26,  
T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

The corner falls on a gradual easterly slope in sandy soil and rocky outcrops in scattered pinon and juniper.

**38.07** Westerly edge of canal, 36 lks. wide, drains S. 47° W.

**38.55** Top of sandy bank, 20 ft. high, bears S 47° W..

**39.976** Point for the center 1/4 section corner, at intersection with the E - W center line of section 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

T43S R10W  
C 1/4  
S26  
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

Raise a mound of stone, 3 1/2 ft. by 2 ft. high, W. of the corner.

The corner falls on flat sandy ground, on the W. edge of an A.T.V. trail, 10 lks. wide, bears N 20° E.

**59.990** Point for the center N 1/16 section corner of section 26; not monumented.

**80.004** The 1/4 section corner of sections 23 and 26.

---

From the 1/4 section corner of sections 25 and 26.

N. 89°52.8' W., on the E - W center line of section 26.

**20.049** Point for the center E 1/16 section corner of section 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T43S R10W  
C  $\frac{E\ 1/16}{S26}$  C  
1994

THE SUBDIVISION OF SECTION 26,  
T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

Raise a mound of stone, 4 ft. base, 3 ft. high N., of the corner.

The corner falls on a steep E. slope.

**38.00** Westerly edge of canal, 36 lks. wide, drains S. 47° W.

**38.70** Top of sandy bank, 20 ft. high, bears S 47° W.

**40.098** The center 1/4 section corner of section 26.

**59.41** Base of vertical ledges, 25 ft. high, bears NE and SW.

**60.078** Point for the center W 1/16 section corner of section 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

$$\begin{array}{c} \text{T43S R10W} \\ \text{C} \frac{\text{W 1/16}}{\text{S26}} \text{C} \\ 1994 \end{array}$$

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high N., of the corner.

The corner falls on a steep SW slope near the base of a ring of ledges, 25 ft. high, bears NE and SW.

**72.40** Top of ridge, bears NW and SE.

**80.058** The 1/4 section corner of sections 26 and 27.

---

From the center E 1/16 section corner of section 26.

N. 0°02.5' W., on the N - S center line of the NE 1/4 of section 26.

**20.025** Point for the NE 1/16 section corner at intersection with the E - W center line of the NE 1/4 of section 26.

THE SUBDIVISION OF SECTION 26,  
T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over the top of a steel fence post, 5 1/2 ft. long driven 5 ft. into sandy ground, with aluminum cap marked:

T43S R10W  
NE 1/16  
S26  
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high W., of the corner.

The corner falls on level sandy ground, 70 lks. N. and 93 lks. W. of the bottom of a drainage, 16 lks. wide at the bottom, drains SW.

**40.050** The E 1/16 section corner of sections 23 and 26.

---

From the true point for the N 1/16 section corner of sections 25 and 26.

N. 89°54.7' W., on the E - W center line of the NE 1/4 of section 26.

**20.009** The NE 1/16 section corner of section 26.

**40.018** Point for the center N 1/16 section corner of section 26.

---

From the E 1/16 section corner of sections 26 and 35.

N. 0°02.5' E., on the N - S center line of the SE 1/4 of section 26.

**19.978** Point for the SE 1/16 section corner at intersection with the E - W center line of the SE 1/4 of section 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T43S R10W  
SE 1/16  
S26  
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

Raise a mound of stone, 2 ft. base, 1 ft. high W., of the corner.

THE SUBDIVISION OF SECTION 26,  
T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

The corner falls on a gradual westerly slope on sandy ground, in scattered pinon and juniper.

**39.956** The center E 1/16 section corner of section 26.

---

From the point for the S 1/16 section corner of sections 25 and 26.

N. 89°54.7' W., on the E - W center line of the SE 1/4 of section 26.

**20.060** The SE 1/16 section corner of section 26.

**40.120** The center S 1/16 section corner of section 26.

---

From the center W 1/16 section corner of section 26.

N. 0°04.4' E., on the N - S center line of the NW 1/4 of section 26.

**39.953** The W 1/16 section corner of sections 23 and 26.

---

The Subdivision of Section 27,  
T. 43 S., R. 10 W., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 27 and 34.

N. 0°07.4' E., on the N - S center line of section 27.

**19.988** Point for the center S 1/16 section corner of section 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, set in a mound of stone, 4 ft. base, to top of aluminum cap marked:

T43S R10W  
C  
S 1/16 | S27  
C  
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

The corner falls on a steep NE slope at the base of a boulder.

**38.00** Top of finger ridge.

THE SUBDIVISION OF SECTION 27,  
T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

**CHAINS****39.976**

Point for the center 1/4 section corner, at intersection with the E - W center line of section 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T43S R10W  
C 1/4  
S27  
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

Raise a mound of stone, 4 ft. by 2 ft. high, W. of the corner.

The corner falls on flat top of a finger ridge.

From the corner, a Washington County galvanized post, 2 1/2 ins. diam., firmly set, projecting 14 ins. above ground, with steel fence post set 2 lks. S., bears N. 89° 16' E., 8 lks. dist., with brass cap marked WASHINGTON COUNTY SURVEY T43S R10W SLB - M C1/4 S27 1979 and a cross. This corner is not accepted or utilized during the course of this survey. ( see note page 2 of these notes.)

**40.60**

Top edge of finger ridge, bears E - W, begin decent.

**49.948**

Point for the C-S-N 1/64 section corner of section 27; not monumented.

**59.920**

Point for the center N 1/16 section corner of section 27; not monumented.

**79.864**

The 1/4 section corner of sections 22 and 27.

---

From the 1/4 section corner of sections 26 and 27.

S. 89° 48.2' W., on the E - W center line of section 27.

**19.951**

Found a rebar, 5/8 in. diam., firmly set, with 1 in. diam. plastic cap marked B & C Eng. LS 4099.

**19.992**

Point for the center E 1/16 section corner of section 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 27,  
T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

T43S R10W  
C  $\frac{E \ 1/16}{S27}$  C  
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high N., of the corner.

The corner falls, 35 lks. north of the N. edge of a graded dirt road, 35 lks. wide, bears N 65° W and S 65° E.

**21.50** North edge of same dirt road, bears E - W.

**22.491** Point for the center E-E-W-E 1/1024 section corner, on the E - W center line of section 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 1 lk. below the surface of a graded dirt road, 35 lks wide, bears E - W, with aluminum cap marked:

T43S R10W  
C-E-E-W-E  
1/1024  
S27  
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

Set a steel fence post, on the W. edge of the aluminum post.

The corner falls on the N. edge of the dirt road, 10 lks. S. of an E - W 4 strand barbed wire fence.

**27.489** Point for the center W-E-W-E 1/1024 section corner on the E - W center line of section 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., flush with the surface of the ground.

T43S R10W  
C-W-E-W-E  
1/1024  
S27  
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

THE SUBDIVISION OF SECTION 27,  
T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

- The corner falls 5 lks. north of the N. edge of a dirt road, 30 lks. wide, bears E - W.
- 29.988** Point for the center W-E 1/64 section corner on the E - W center line of section 27; not monumented.
- 38.35** Top of finger ridge, bears S. 30° W., and N. 34° W.
- 39.984** The center 1/4 section corner of section 27.
- 79.915** The 1/4 section corner of sections 27 and 28.
- 
- From the center E 1/16 section corner of section 27.  
N. 0°06.0' E., on the N - S center line of the NE 1/4 of section 27.
- 9.971** Point for the center S-NE 1/64 section corner of section 27; not monumented.
- 19.942** Point for the NE 1/16 section corner at intersection with the E - W center line of the NE 1/4 of section 27; not monumented.
- 39.884** Point for the E 1/16 section corner of sections 22 and 27.
- 
- From the point for the N 1/16 section corner of sections 26 and 27.  
S. 89°48.6' W., on the E - W center line of the NE 1/4 of section 27.
- 19.982** Point for the NE 1/16 section corner of section 27.
- 29.973** Point for the center W-NE 1/64 section corner; not monumented.
- 39.964** Point for the center N 1/16 section corner of section 27.
- 
- From the point for the center W-E 1/64 section corner on the E - W center line of section 27.  
N. 0°06.7' E., on the N - S center line of the SW 1/4, NE 1/4 of section 27.
- 9.971** Point for the SW-NE 1/64 section corner of section 27; not monumented.
- 19.942** Point for the center W-NE 1/64 section corner of section 27.
-

THE SUBDIVISION OF SECTION 27,  
T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the point for the center S-NE 1/64 section corner of section 27.

S. 89° 48.4' W., on the E - W center line of the SW 1/4, NE 1/4, of section 27.

**2.498** Point for the center E-E-SW-NE 1/1024 section corner of section 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T43S R10W  
C-E-E-SW-NE  
1/1024  
S27  
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

Raise a mound of stone, 4 ft. base, 3 ft. high W., of the corner.

The corner falls on a moderate SW slope.

From the corner, a rebar 5/8 in. diam., bears E., 3 lks. dist.

**7.494** Point for the center W-E-SW-NE 1/1024 section corner of section 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T43S R10W  
C-W-E-SW-NE  
1/1024  
S27  
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

Raise a mound of stone, 4 ft. base, 3 ft. high W., of the corner.

The corner falls on a moderate SW slope.

From the corner, a rebar 5/8 in. diam., bears N. 88° E., 4 lks. dist.

**9.992** Point for the SW-NE 1/64 section corner of section 27.

**19.986** Point for the center S-N 1/64 section corner of section 27.

THE SUBDIVISION OF SECTION 27,  
T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the center E-E-W-E 1/1024 section corner of section 27.

N.  $0^{\circ}06.2'$  E., on the N-S center line of the E 1/2 of the SE 1/4 of the SW 1/4 of the NE 1/4 of section 27.

**9.971** The center E-E-SW-NE 1/1024 section corner of section 27.

From the center W-E-SW-NE 1/1024 section corner of section 27.

N.  $0^{\circ}06.5'$  E., on the N-S center line of the W 1/2 of the SE 1/4 of the SW 1/4 of the NE 1/4 of section 27.

**9.971** The center W-E-SW-NE 1/1024 section corner of section 27.

From the E 1/16 section corner of sections 27 and 34.

N.  $0^{\circ}05.8'$  E., on the N-S center line of the SE 1/4 of section 27.

**19.35** Drainage, 17 lks. wide, bears N.  $39^{\circ}$  E.

**20.003** Point for the SE 1/16 section corner, at intersection with the E-W center line of the SE 1/4 of section 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T43S R10W  
SE 1/16 S27  
1994

Deposit a magnet, 1x1x1 7/8 ins. in clear plastic case beneath the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

The corner falls on flat sandy ground, in scattered cedar and pinon.

From this corner, the W edge of a drainage, 20 ft. deep, with rim bearing N and S, bears E., 13 lks.

**40.006** The center E 1/16 section corner of section 27.

From the point for the S 1/16 section corner of sections 26 and 27.

S.  $89^{\circ}50.8'$  W., on the E-W center line of the SE 1/4 of section 27.

THE SUBDIVISION OF SECTION 27,  
T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

**20.001** The SE 1/16 section corner of section 27.

**40.002** The center S 1/16 section corner of section 27.

---

The Subdivision of Section 28,  
T. 43 S., R. 10 W., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 28 and 33.

N.  $0^{\circ}02.4'$  W., on the N - S center line of section 28.

**19.977** Point for the center S 1/16 section corner of section 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins in the ground, with aluminum cap marked:

T43S R10W  
C  
S 1/16 | S28  
C  
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

Raise a mound of stone, 3 ft. base, 3 ft. high, W. of the corner.

The corner falls on flat ground, 40 lks. E. of a drainage, 25 lks. wide, drains S.  $42^{\circ}$  E.

**36.70** Drainage, 20 lks. wide, drains S.  $28^{\circ}$  E.

**39.954** Point for the center 1/4 section corner at intersection with the E - W center line of section 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T43S R10W  
C 1/4  
S28  
1994

The corner falls on a moderate W. slope, 70 lks. E. of a drainage, 15 lks. wide, drains S.  $45^{\circ}$  W.

THE SUBDIVISION OF SECTION 28,  
T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

**CHAINS****79.844**

The 1/4 section corner of sections 21 and 28.

---

From the 1/4 section corner of sections 27 and 28.

S. 89°56.5' W., on the E - W center line of section 28.

**40.066**

The C 1/4 section corner of section 28.

**60.063**

Point for the center W 1/16 section corner of section 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, set in a mound of stone, 4 ft. base, to top of aluminum cap marked:

T43S R10W  
C  $\frac{W\ 1/16}{S28}$  C  
1994

from which

A pinon, 12 ins. diam., bears S. 41° E., 44 1/2 lks. dist.,  
marked X BT.

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

The corner falls on the point of a ridge, 68 lks. N., and 20 lks. E., of top edge of rim of vertical ledge.

**80.060**

The 1/4 section corner of sections 28 and 29.

---

From the W 1/16 section corner of sections 28 and 33.

N. 0°04.8' W., on the N - S center line of the SW 1/4 of section 28.

**18.30**

Dirt road, 12 lks. wide, bears N 70° W.

**19.985**

Point for the SW 1/16 section corner, at intersection with the E - W center line of the SW 1/4 of section 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, set in a mound of stone, 3 ft. base to top of aluminum cap marked:

THE SUBDIVISION OF SECTION 28,  
T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T43S R10W  
SW 1/16  
S28  
1994

Raise a mound of stone, 4 ft. base, 3 ft. high, W of the corner.

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

The corner falls on flat ground, in a hollow.

**39.970** The center W 1/16 section corner of section 28.

---

From the center S 1/16 section corner of section 28.

S. 89°55.2' W., on the E - W center line of the SW 1/4 of section 28.

**19.984** The SW 1/16 section corner of section 28.

**39.968** The S 1/16 section corner of sections 28 and 29.

---

The Subdivision of Section 29,  
T. 43 S., R. 10 W., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 29 and 32, monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above ground, with brass cap marked as described in the official record of the survey in 1909 by Collier and Gentry.

N. 0°07.2' W., on the N - S center line of section 29.

**20.005** Point for the center S 1/16 section corner of section 29.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T43S R10W  
C  
S 1/16 | S29  
C  
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

The corner falls on flat sandy ground, scattered cedar.

THE SUBDIVISION OF SECTION 29,  
T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

**CHAINS****40.010**

Point for the center 1/4 section corner at intersection with the E - W center line of section 29.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T43S R10W  
C 1/4  
S29  
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the corner.

The corner falls on level sandy ground, scattered cedar.

**79.980**

The 1/4 section corner of sections 20 and 29.

---

From the 1/4 section corner of sections 28 and 29.

S. 89°53.2' W., on the E - W center line of section 29.

**40.005**

The center 1/4 section corner of section 29.

**80.002**

The 1/4 section corner of sections 29 and 30.

---

From the S 1/16 section corner of sections 28 and 29.

S. 89°52.2' W., on the E - W center line of the SE 1/4 of section 29.

**40.007**

The center S 1/16 section corner of section 29.

---

From the center S 1/16 section corner of section 29.

S. 89°52.2' W., on the E - W center line of the SW 1/4 of section 29.

**40.005**

The S 1/16 section corner of sections 29 and 30.

---

The Subdivision of Section 33,  
T. 43 S., R. 10 W., Salt Lake Meridian, Utah

---

THE SUBDIVISION OF SECTION 33,  
T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the point for the 1/4 section corner of section 33 only, at midpoint between the closing corners on the south boundary of section 33; not monumented.

N.  $0^{\circ}08.3'$  W., on the N - S center line of section 33.

**18.807** Point for the center 1/4 section corner, at intersection with the E - W center line of section 33.

Set a rebar 3/4 in. diam., 28 ins. long, 3 ins. below the surface of Utah Avenue, with 3 1/4 ins. diam., aluminum cap marked:

T43S R10W  
C 1/4  
S33  
1994

from which

An aluminum post, 30 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N.  $42^{\circ}08'$  E., 58.2 ft. dist., with cap marked T43S R10W RM 58.2 FT. 1994 and an arrow pointing to the corner. Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the aluminum post. The corner falls 1 lk. S. of an E - W, 4 strand barbed wire fence line.

An aluminum post, 30 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N.  $46^{\circ}32.3'$  W., 62.2 ft. dist., with cap marked T43S R10W RM 62.2 FT. 1994 and an arrow pointing to the corner. Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the aluminum post. The corner falls 2 lks. S. of a E - W, 4 strand barbed wire fence line.

The corner falls 2 ft. N. of the center of Utah Ave., a paved road, 36 lks. wide.

**37.95** Drainage, 9 lks. wide, drains S.  $40^{\circ}$  E.

**38.864** Point for the center N 1/16 section corner of section 33.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T43S R10W  
C  
N 1/16 | S33  
C  
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

THE SUBDIVISION OF SECTION 33,  
T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Raise a mound of stone, 4 ft. base, 2 ft. high, W. of the corner.

The corner falls on a gradual easterly slope, 45 lks. W., of a drainage, 5 lks. wide, drains S. 21° W.

**58.921** The 1/4 section corner of sections 28 and 33.

---

From the 1/4 section corner of sections 33 and 34.

N. 89°59.0' W., on the E - W center line of section 33.

**40.002** The C 1/4 section corner of section 33.

**59.993** Point for the center W 1/16 section corner of section 33; not monumented.

**79.984** The 1/4 section corner of sections 32 and 33.

---

From the point for the center W 1/16 section corner of section 33.

N. 0°06.8' W., on the N - S center line of the NW 1/4 of section 33.

**20.036** Point for the NW 1/16 section corner, at intersection with the E - W center line of the NW 1/4 of section 33.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T43S R10W  
NW 1/16  
S33  
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

Raise a mound of stone, 2 ft. base, 1 ft. high, W of the corner.

Set a steel fence post, N. of the aluminum post.

The corner falls on flat sandy ground.

**40.072** The W 1/16 section corner of sections 28 and 33.

---

THE SUBDIVISION OF SECTION 33,  
T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the center N 1/16 section corner of section 33.

S.  $89^{\circ}57.4'$  W., on the E - W center line of the NW 1/4 of section 33.

**19.981** The NW 1/16 section corner of section 33.

**39.962** Point for the N 1/16 section corner of sections 32 and 33.

---

The Subdivision of Section 34,  
T. 43 S., R. 10 W., Salt Lake Meridian, Utah

---

From the point for the 1/4 section corner of section 34 only, at midpoint between the closing corners on the south boundary of section 34; not monumented.

N.  $0^{\circ}09.5'$  W., on the N - S center line of section 34.

**18.805** Point for the center 1/4 section corner, at intersection with the E - W center line of section 34.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. below the surface of the ground, with aluminum cap marked:

T43S R10W  
C 1/4  
S34  
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

The corner falls 10 lks. north of the N. edge of a paved road, 36 lks. wide, bears E - W, and 3 lks. south of the S. edge of a asphalt sidewalk, 16 lks. wide, bears E - W.

**38.856** Point for the center N 1/16 section corner of section 34.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, set in a mound of stone 5 ft. base to top of aluminum cap marked:

T43S R10W  
C  
N 1/16 | S34  
C  
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

THE SUBDIVISION OF SECTION 34,  
T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

- The corner falls on flat ground in cove, at head of a canyon, bears E - W.
- 40.10** Bottom of drainage, drains E.
- 41.00** Base of ledges.
- 58.907** The 1/4 section corner of sections 27 and 34.
- 
- From the true point for the 1/4 section corner of sections 34 and 35.  
S. 89° 44.5' W., on the E - W center line of section 34.
- 39.954** The center 1/4 section corner of section 34.
- 59.909** Point for the center W 1/16 section corner of section 34.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 30 ins. deep, flush with the ground, with aluminum cap marked:
- $$\begin{array}{c} \text{T43S R10W} \\ \text{C} \frac{\text{W 1/16}}{\text{S34}} \text{C} \\ \text{1994} \end{array}$$
- Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.
- Set a steel fence post, alongside the aluminum post.
- 79.864** The 1/4 section corner of sections 33 and 34.
- 
- From the center W 1/16 section corner of section 34.  
N. 0° 08.5' W., on the N - S center line of the NW 1/4 of section 34.
- 2.50** Chain link fence, 6 ft. high, bears N. 85° E. and S. 85° W.
- 6.73** Chain link fence, 6 ft. high, bears E - W.
- 8.55** Top of earthen dike, 18 lks. wide, approximately 30 ft. high, bears N. 70° E. and S. 70° W.
- 20.079** Point for the NW 1/16 section corner, at intersection with the E - W center line of the NW 1/4 of section 34.

THE SUBDIVISION OF SECTION 34,  
T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, set in a mound of stone, 5 ft. base, to top of aluminum cap marked:

T43S R10W  
NW 1/16  
S34  
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

The corner falls on a steep S. rocky slope, 16 lks. N. of the top edge of a vertical sandstone ledge, 15 ft. high, bears E - W.

**40.158** The W 1/16 section corner of sections 27 and 34.

---

From the center N 1/16 section corner of section 34.

S. 89°49.5' W., on the E - W center line of the NW 1/4 of section 34.

**19.948** The NW 1/16 section corner of section 34.

**39.896** Point for the N 1/16 section corner of sections 33 and 34.

---

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

## FIELD ASSISTANTS

---

Name	Capacity
Shane Button	Survey Aid


---

## CERTIFICATE OF SURVEY

I, *Larry V. Judd, Cadastral Surveyor*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *7th day of March, 1994*, I have *retraced the Utah and Arizona State Boundary (south boundary) from Mile Post 58 to Mile Post 60.19, a dependent resurvey of a portion of the subdivisional lines and the subdivision of sections 26, 27, 28, 29, 33, and 34, in Township 43 South, Range 10 West,*

of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

3/26/96  
Date

  
Larry V. Judd  
(Cadastral Surveyor)

\_\_\_\_\_  
Date

\_\_\_\_\_  
(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL


BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The foregoing field notes of the *retracement of the Utah and Arizona State Boundary ( south boundary ) from Mile Post 58 to Mile Post 60.19, and the dependent resurvey of a portion of the subdivisional lines and the subdivision of sections 26, 27, 28, 29, 33, and 34, in Township 43 South, Range 10 West, Salt Lake Meridian, Utah,*

executed by *Larry V. Judd, Cadastral Surveyor*

having been critically examined and found correct, are hereby approved.

April 18, 1996  
Date

  
(Chief Cadastral Surveyor for Utah)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

## FIELD NOTES

OF  
THE DEPENDENT RESURVEY OF

PORTIONS OF THE NORTH BOUNDARY,

EAST BOUNDARY,

AND

INTERIOR SUBDIVISIONAL LINES

AND

SURVEY OF THE SUBDIVISION OF SECTIONS 1, 11, 13, 14, 23, AND 24,

IN

TOWNSHIP 26 SOUTH, RANGE 1 WEST

OF THE SALT LAKE MERIDIAN  
IN THE STATE OF UTAH

EXECUTED BY

*Ferrel D. Reynolds, Cadastral Surveyor*

Under special instructions dated *June 17, 1994*, approved *June 17, 1994*, which provided for the surveys included under Group Number *819*, and assignment instructions dated *June 24, 1994*.

Survey commenced *July 25, 1994*

Survey completed *May 23, 1995*

INDEX DIAGRAM

Township 26 South, Range 1 West

7 6 5

				22		14		
6	5	4	3	22	2	13	1	5
				20	20	13	13	4
7	8	9	10	19	11	12	12	4
				18	19	10	11	4
18	17	16	15	17	14	10	13	3
				16	17	8	9	3
19	20	21	22	15	23	8	24	2
				14	14	8	7	2
30	29	28	27		26		25	
31	32	33	34		35		36	

The Subdivision of Section 1.....Page 22  
 The Subdivision of Section 11.....Page 26  
 The Subdivision of Section 13.....Page 29  
 The Subdivision of Section 14.....Page 30  
 The Subdivision of Section 23.....Page 32  
 The Subdivision of Section 24.....Page 35

## TOWNSHIP 26 SOUTH, RANGE 1 WEST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

The following field notes describe the dependent resurvey of a portion of the north boundary, east boundary, and interior subdivisional lines, along with the subdivision of sections 1, 11, 13, 14, 23, and 24, within T. 26 S., R. 1 W., Salt Lake Meridian, Utah.

History of SurveysSurveyed byRetr. or Resurveyed byNORTH BOUNDARY (Fifth Standard Parallel South)

Portion	J.G. Burrill	1874		
All	A.P. Hanson	1891	A.P. Hanson	1891
Portion			W.H. Sylvester	1961

SOUTH BOUNDARY

Portion	Bailey and Burrill	1874		
Portion	Breckon and McCarty	1896	Breckon and McCarty	1896

EAST BOUNDARY (Salt Lake Meridian)

All	Bailey and Burrill	1874		
Portion			E. Bird	1932-34

WEST BOUNDARY

All	Breckon and McCarty	1897		
-----	------------------------	------	--	--

SUBDIVISION

Portion	J.G. Burrill	1874		
Portion	Breckon and McCarty	1897	Breckon and McCarty	1897

Remonumentation	F.D. Reynolds	1969		
Remonumentation	F.D. Reynolds	1970		
Remonumentation	F.D. Reynolds	1972		

The resurvey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 819, Utah, dated June 17, 1994.

The directions of lines were determined by solar and Polaris observations. Lines were carried out with backsights and foresights through intermediate transit stations.

## TOWNSHIP 26 SOUTH, RANGE 1 WEST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

Preliminary to the resurvey the lines of the original survey were retraced and a diligent search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the corner of sections 19, 24, 25 and 30, on the east township boundary, which will now function as a B.L.M. control station, was determined by the Global Positioning System (G.P.S.), static relative positioning techniques, utilizing U.S.G.S triangulation station "Bear Valley", and U.S.F.S triangulation station "Harem" is as follows:

Latitude: 38° 31' 38.37" N.      Longitude: 111° 50' 55.47" W.  
N.A.D. 1927

The mean magnetic declination as projected from the U.S. Geological Survey Magnetic Declination Map of 1990 is: 13 1/2° E.

---

Dependent Resurvey of a Portion of the East Boundary  
( Salt Lake Meridian )  
T. 26 S., R. 1 W., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by  
Bailey and Burrill in 1874, and  
the Resurvey by E. Bird in 1932-34

---

Beginning at the corner of sections 19, 24, 25, and 30, on the east boundary of T. 26 S., R. 1 W., (Salt Lake Meridian), monumented with an iron post, 2 ins. diam. 12 ins. above ground, and in a mound of stone, to top of brass cap, marked as described in the official record of the 1932-34 resurvey.

N. 0° 32.3' W., between sections 19 and 24, along the east boundary of the township.

Over rolling bench land, through lightly scattered pinon and juniper growth.

**19.914** Point for the S 1/16 section corner of sections 19 and 24; not monumented.

**39.828** The 1/4 section corner of sections 19 and 24, monumented with an iron post, 1 in. diam., 12 ins. above ground and in a mound of stone, with brass cap marked as described in the official record of the 1932-34 resurvey.

---

Reestablishment of the Survey Executed by  
Bailey and Burrill in 1874

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY  
(SALT LAKE MERIDIAN),  
T. 26 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

N. 0° 33.3' W., beginning new measurement.

**39.888** The corner of sections 13, 18, 19, and 24, monumented with a granite stone, 12x9x9 ins., firmly set and plainly marked, with 3 notches on the N and S edges.

At the corner point

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T26S  
R1W R1E  
S13 | S18  
S24 | S19  
1994

Deposit the marked stone alongside the corner.

Set a steel fence post alongside the corner.

---

N. 0° 27.5' W., between sections 13 and 18, along the east boundary of the township.

Over rolling bench land, through sagebrush.

**39.922** The 1/4 section corner of sections 13 and 18, monumented with a granite stone, 18x12x8 ins., firmly set and plainly marked 1/4 on W face.

At the corner point

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T26S  
R1W R1E  
1/4  
S13 | S18  
1994

Deposit the marked stone alongside the corner.

Set a steel fence post alongside the corner.

---

N. 0° 11.7' W., beginning new measurement.

**19.960** Point for the N 1/16 section corner of sections 13 and 18.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY  
(SALT LAKE MERIDIAN),  
T. 26 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T26S  
R1W R1E  
N 1/16  
S13 | S18  
1994

Corner is located 7 lks. distance, east of netwire fence line, bears N and S.

**39.920** The corner of sections 7, 12, 13, and 18, monumented with a granite stone, 12x10x10 ins. firmly set and plainly marked with 4 notches on the S and 2 notches on the N edges.

At the corner point

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T26S  
R1W R1E  
S12 | S7  
S13 | S18  
1994

Deposit the marked stone alongside the corner.

Corner is located at the corner of fence, projecting N, S, and W.

---

N. 0° 11.1' W., between sections 7 and 12, along the east boundary of the township.

Over rolling bench land (private land).

**39.656** Point for the 1/4 section corner of sections 7 and 12, at proportionate distance; not monumented (private property).

**79.312** Point for the corner of sections 1, 6, 7, and 12, at proportionate distance; not monumented (private property).

---

N. 0° 11.1' W., between sections 1 and 6, along the east boundary of the township.

**39.656** Point for the 1/4 section corner of sections 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY  
 ( SALT LAKE MERIDIAN ),  
 T. 26 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T26S  
 R1W R1E  
 1/4  
 S1|S6  
 1994

Set a steel fence post alongside the corner.

**49.570** Point for the S-N 1/64 section corner of sections 1 and 6.

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T26S  
 R1W R1E  
 S-N 1/64  
 S1|S6  
 1995

Set a steel fence post alongside the corner.

**59.484** Point for the N 1/16 section corner of sections 1 and 6; not monumented.

**69.398** Point for the N-N 1/64 section corner of sections 1 and 6; not monumented.

**69.918** Point for the SE corner of Lot 5, identical with the NE corner of Lot 8.

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T26S  
 R1W R1E  
 L5 |  
 L8 |  
 1995

Set a steel fence post alongside the corner.

**79.312** The corner of Tps. 25 and 26 S., Rs. 1 W. and 1 E., monumented with an iron post, 3 1/2 ins. diam., 8 ins. above ground, with brass cap, marked as described in the official record of the dependent resurvey of the north boundary of T. 26 S., R.1 E., in 1932-34.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY  
( FIFTH STANDARD PARALLEL SOUTH ),  
T. 26 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Dependent Resurvey of a Portion of the North Boundary  
(Fifth Standard Parallel South),  
T. 26 S., R. 1 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by  
Bailey and Burrill in 1874 and the  
Resurvey by W.H. Sylvester in 1961

From the corner of Tps. 25 and 26 S., Rs. 1 W. and 1 E.

N. 89° 36.9' W., on the south boundary of section 36, T. 25 S., R. 1 W.

Over mountainous land, through pinon and juniper growth.

**7.441** Point for the 1/1024 section corner of section 1 only; not monumented.

**9.921** Point for the E-E 1/64 section corner of section 1 only; not monumented.

**19.842** Point for the E 1/16 section corner of section 1 only.

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a collar of stone, with aluminum cap marked:

E 1/16 S1  
T26S R1W  
1994

Corner is located on steep E slope, in thick pinon and juniper growth.

**39.556** The standard 1/4 section corner of section 36 only, monumented with an iron post, 2 1/2 ins. diam., 12 ins. above ground, and in a mound of stone, with brass cap marked as described in the official record of the 1961 resurvey.

N. 89° 16.4' W., beginning new measurement.

**0.128** Midpoint for the 1/4 section corner of section 1 only.

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to bedrock, and in a mound of stone to top of aluminum cap marked:

1/4 S1  
T26S R1W  
1994

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY  
( FIFTH STANDARD PARALLEL SOUTH ),  
T. 26 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Corner is located on NE slope, in thick pinon and juniper growth.

- 39.814** The closing corner of sections 1 and 2, on the north boundary of the township, monumented with a granite stone, 15x8x6 ins., firmly set and dimly marked 5 notches on the W and 1 notch on E edges.

At the corner point

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

S36	
S2	S1
C	C
T26S R1W	
1994	

Deposit the marked stone alongside the corner.

Corner is located on steep SW slope, in scattered pinon and juniper growth.

- 39.904** The standard corner of sections 35 and 36, monumented with an iron post, 2 1/2 ins. diam., 12 ins. above ground, and in a mound of stone to top of brass cap, marked as described in the official record of the 1961 resurvey.

---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 26 S., R. 1 W., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by  
Bailey and Burrill in 1874

---

From the corner of sections 19, 24, 25, and 30, on the east boundary of the township, hereinbefore described.

N. 88° 28.3' W., between sections 24 and 25.

Over rolling bench land, through scattered pinon and juniper growth.

- 20.335** Point for the E 1/16 section corner of sections 24 and 25; not monumented.

- 40.670** Point for the 1/4 section corner of sections 24 and 25, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 26 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T26S R1W  
1/4 S24  
S25  
1994

Corner is located 87 lks. W of 6 strand fence line, bears N and S.

Enter private land.

**81.340** The corner of sections 23, 24, 25, and 26, monumented with a granite stone, 12x10x6 ins., firmly set and dimly marked 2 notches on S edge and 1 notch on the E edges.

At the corner point

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T26S R1W  
S23 | S24  
S26 | S25  
1994

Deposit the marked stone alongside the corner.

Corner is located at the corner of fence, projecting N, S and W.

---

N. 0° 44.4' W., between sections 23 and 24.

Over meadow land, private property.

**20.255** Point for the S 1/16 section corner of sections 23 and 24; not monumented.

**40.510** Point for the 1/4 section corner of sections 23 and 24, at proportionate distance; there is no remaining evidence of the original corner; not monumented.

**81.020** Point for the corner of sections 13, 14, 23, and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T26S R1W  
S14 | S13  
S23 | S24  
1994

Set a steel fence post alongside the corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 26 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Nearly level swamp land.

From the corner of sections 13, 18, 19, and 24, on the east boundary of the township, hereinbefore described.

N. 87° 33.6' W., between sections 13 and 24.

Over gentle rolling land.

**20.414** Point for the E 1/16 section corner of sections 13 and 24.

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

	T26S R1W
E 1/16	<u>S13</u>
	S24
	1994

Set a steel fence post alongside the corner.

Corner is located 7 lks. E and 8 lks. N of corner of netwire fence, projecting N, S and W.

Enter private land.

**40.828** Point for the 1/4 section corner of sections 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T26S R1W
1/4	<u>S13</u>
	S24
	1994

Corner is located 27 lks. N of netwire fence line, bears E and W.

**81.656** The corner of sections 13, 14, 23, and 24.

N. 1° 06.7' E., between sections 13 and 14.

Over nearly level swamp land.

**20.258** Point for the S 1/16 section corner of sections 13 and 14.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 26 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T26S R1W  
S 1/16  
S14 | S13  
1994

Set a steel fence post alongside the corner.

Gentle rolling bottom land.

**40.516**

The 1/4 section corner of sections 13 and 14, monumented with a limestone, 17x10x8 ins. firmly set in a mound of stone and dimly marked 1/4 on W face.

At the corner point

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone to top of aluminum cap marked:

T26S R1W  
1/4  
S14 | S13  
1994

Set a steel fence post alongside the corner.

Deposit the marked stone alongside the corner.

N. 0° 08.9' W., beginning new measurement.

**38.810**

The corner of sections 11, 12, 13, and 14, monumented with a granite stone, 16x8x6 ins. firmly set and plainly marked with 4 notches on the S edge and 1 notch on the E edge.

At the corner point

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T26S R1W  
S11 | S12  
S14 | S13  
1994

Deposit the marked stone alongside the corner.

Corner is located at the corner of fence, projecting N, S and E.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 26 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the corner of sections 7, 12, 13, and 18, on the east boundary of the township, hereinbefore described.

N. 87° 47.4' W., between sections 12 and 13.

Over nearly level bottom land, private property.

**20.105** Point for the E 1/16 section corner of sections 12 and 13; not monumented.

**40.210** The 1/4 section corner of sections 12 and 13, marked by fence corner projecting E, W and N.

At the corner point

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a collar of stone, with aluminum cap marked:

T26S R1W  
1/4    S12  
         S13  
         1994

Corner is located in pasture land.

---

N. 88° 00.1' W., beginning new measurement.

**40.270** The corner of sections 11, 12, 13, and 14.

---

N. 1° 04.4' W., between sections 11 and 12.

Over gentle rolling bench land.

**19.965** Point for the S 1/16 section corner of sections 11 and 12.

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T26S R1W  
S 1/16  
S11 | S12  
1995

Set a steel fence post alongside the corner.

**27.452** Point for the N-S-N-S 1/1024 section corner of sections 11 and 12.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 26 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

N-S-N-S  
1/1024  
S11 | S12  
1995

Set a steel fence post alongside the corner.

The corner falls 25 lks. dist., E of a N and S fence line.

**32.443** Point for the S-N-N-S 1/1024 section corner of sections 11 and 12.

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

S-N-N-S  
1/1024  
S11 | S12  
1995

Set a steel fence post alongside the corner.

The corner falls 31 lks. dist., E of a N and S fence line.

**39.930** Point for the 1/4 section corner of sections 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T26S R1W  
1/4  
S11 | S12  
1994

Set a steel fence post alongside the corner.

**79.860** The corner of sections 1, 2, 11, and 12, marked by a rebar and cap, marked Torgerson Eng. L.S. 6698; there is no remaining evidence of the original corner stone. This corner is accepted as a careful reestablishment of the original corner.

At the corner point

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 26 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T26S R1W  

S2	S1
S11	S12

 1994

Deposit rebar and cap alongside the corner.

Set a steel fence post alongside the corner.

Corner is located 21 lks. distance, S of dirt road, bears E and W.

---

At the 1/4 section corner of sections 1 and 12, marked by the corner of fence, projecting E, W and S, and with a Torgerson Eng. rebar and cap, marked L.S. 6698.

At the corner point

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a collar of stone, with aluminum cap marked:

T26S R1W  
 1/4 

S1
S12

 1994

Corner is located 44 lks. S of dirt road, bears E and W.

N. 86° 58.0' W., between sections 1 and 12, west half.

Over gentle rolling land.

**40.150** The corner of sections 1, 2, 11, and 12.

---

N. 1° 34.2' E., between sections 1 and 2.

Over rolling bench land, through lightly scattered pinon and juniper growth.

**39.404** The 1/4 section corner of sections 1 and 2, monumented with a granite stone, 16x12x10 ins., firmly set and plainly marked 1/4 on W face.

At the corner point

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 26 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T26S R1W

1/4

S2 | S1

1994

Deposit the marked stone alongside the corner.

Raise a mound of stone, 3 ft. base, 2 ft. high, W of corner.

Corner is located in N and S fence line.

N. 1° 26.'1 E., beginning new measurement.

**37.217** The closing corner of sections 1 and 2, hereinbefore described.

From the corner of sections 23, 24, 25, and 26.

S. 89° 28.9' W., between sections 23 and 26.

Over gentle rolling bottom land, private property.

**19.843** Point for the E 1/16 section corner of sections 23 and 26; not monumented.

**39.686** Point for the 1/4 section corner of sections 23 and 26, at proportionate distance; there is no remaining evidence of the original corner; not monumented.

**59.529** Point for the W 1/16 section corner of sections 23 and 26.

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T26S R1W

W 1/16 S23

S26

1994

Set a steel fence post alongside the corner.

Corner is located on gentle E slope, in sagebrush; leave private property.

**79.372** The corner of sections 23, 26 and 27, monumented with a granite stone, 12x10x7 ins., firmly set and plainly marked 2 notches on S and E edges.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 26 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a collar of stone, with aluminum cap marked:

	T26S R1W	
S27	S23	
	S26	
	1994	

Deposit the marked stone alongside the corner.

Set a steel fence post alongside the corner.

N. 1° 18.4' W., on the west boundary of section 23.

Over mountainous land, through scattered pinon and juniper growth.

**0.600** The closing corner of sections 22 and 27, monumented with a granite stone, 14x10x6 ins., firmly set and plainly marked 2 notches on S and E edges, CC on W face.

At the corner point

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap marked:

	T26S R1W	
CC	S22	S23
	S27	
	1994	

Deposit the marked stone alongside the corner.

Set a steel fence post alongside the corner.

Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W of corner.

**19.327** Point for the S 1/16 section corner of section 23 only; not monumented.

**38.654** The 1/4 section corner of section 23 only, monumented with a granite stone, 16x12x8 ins., firmly set and plainly marked 1/4.

At the corner point

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 26 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T26S R1W  
| 1/4  
| S23  
1994

Deposit the marked stone alongside the corner.

Set a steel fence post alongside the corner.

Corner is located 20 lks. N of trial road, bears E and W.

N. 3° 00.8' W., beginning new measurement.

**0.760** Point for the 1/4 section corner of section 22 only.

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone to top of aluminum cap marked:

T26S R1W  
1/4 |  
S22 |  
1994

**39.558** The corner of sections 14, 22, and 23, monumented with a flint rock, 18x8x6 ins., firmly set and dimly marked 3 notches on the S and 2 notches on the E edges.

At the corner point

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone to top of aluminum cap marked:

S22 | T26S R1W  
| S14  
| S23  
1994

Deposit the marked stone alongside the corner.

Corner is located on steep S slope of hill.

From the corner of sections 13, 14, 23, and 24.

S. 87° 28.4' W., between sections 14 and 23.

Over mountainous land, through lightly scattered pinon and juniper growth; private ground.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 26 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

20.336

Point for the E 1/16 section corner of sections 14, 22, and 23.

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

	T26S R1W
E 1/16	<u>S14</u>
	S23
	1994

Set a steel fence post alongside the corner.

Corner is located 1 1/2 chs. W of Utah State Highway No. 62, bears NE and SW.

Leave private land.

40.672

Point for the 1/4 section corner of sections 14 and 23, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., on solid rock, and in a mound of stone, 4 ft. base, to top of aluminum cap marked:

	T26S R1W
1/4	<u>S14</u>
	S23
	1994

Corner is located on SE slope.

81.344

The corner of sections 14, 22, and 23.

---

N. 1° 52.1' W., on the west boundary of section 14.

Over mountainous land, through pinon and juniper growth.

2.480

The closing corner of sections 15 and 22, monumented with an iron post, 2 1/2 ins. diam., 8 ins. above ground, and in a mound of stone to top of brass cap marked as described in the official record of the 1969 remonumentation.

40.052

The 1/4 section corner of section 14 only, monumented with an iron stone, 18x10x6 ins., firmly set in a mound of stone and plainly marked 1/4 on W face.

At the corner point

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 4 ins. in the ground to bedrock, and in a mound of stone, 5 ft. base, to top of aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 26 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T26S R1W  
|  
1/4  
|  
S14  
1994

Deposit the marked stone alongside the corner.

Corner is located on NE slope of hill.

---

N. 2° 12.7' W., beginning new measurement.

**2.063** Point for the 1/4 section corner of section 15 only (midpoint).

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap mkd.:

T26S R1W  
1/4 |  
S15 |  
1994

**39.538** The corner of sections 11, 14, and 15, monumented with a flint rock, firmly set and plainly marked 4 notches on the S edge and 2 notches on the E edge.

At the corner point

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone to top of aluminum cap marked:

S15 | T26S R1W  
| S11  
| S14  
1994

Deposit the marked stone alongside the corner.

Corner is located on NE slope of hill.

---

From the corner of sections 11, 12, 13, and 14.

S. 87° 43.7' W., between sections 11 and 14.

**21.208** Point for the E 1/16 section corner of sections 11 and 14; not monumented.

**42.416** Point for the 1/4 section corner of sections 11 and 14, at proportionate distance; there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 26 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

	T26S R1W	
1/4	<u>S11</u>	
	S14	
	1994	

Set a steel fence post alongside the corner.

Corner is located on E slope of hill.

**84.832** The corner of sections 11, 14, and 15.

---

N. 4° 05.4' E., on the west boundary of section 11.

Over mountainous land, through pinon and juniper growth.

**2.171** Point for the closing corner of sections 10 and 15, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of aluminum cap marked:

	T26S R1W	
CC	<u>S10</u>   S11	
	S15	
	1994	

Corner is located on NE slope of hill.

**41.480** Point for the 1/4 section corner of section 11, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base to top of aluminum cap marked:

	T26S R1W	
	1/4	
	S11	
	1994	

Corner is located on broken E slope.

**43.450** Point for the 1/4 section corner of section 10 only (midpoint).

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base, to top of aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 26 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T26S R1W  
1/4 |  
S10 |  
1994

Corner is located on the N edge of trail road, bears NE and SW.

**82.960** The corner of sections 2, 10, and 11, monumented with a flint stone, 16x12x6 ins., firmly set and plainly marked 5 notches on the S edge and 2 notches on the E 4 edge.

from which

A cedar stump, 16 ins. diam., bears N. 1° 45' W., 4.04 chs.  
distance (record, N. 2° 30' W., 4.40 chs.).

At the corner point

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T26S R1W  
S10 | S2  
| S11  
1994

Deposit the marked stone alongside the corner.

Set a steel fence post alongside the corner.

Corner is located on gentle E slope.

---

From the corner of sections 1, 2, 11, and 12.

S. 89° 23.1' W., between sections 2 and 11.

Over mountainous land, through scattered pinon and juniper growth.

**37.165** The 1/4 section corner of sections 2 and 11, monumented with a granite stone, 18x12x10 ins., firmly set and plainly marked 1/4 on N face.

At the corner point

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 26 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T26S R1W  
1/4  $\frac{S2}{S11}$   
1994

Deposit the marked stone alongside the corner.

Corner is located on NE slope of hill.

S. 89° 54.6' W., beginning new measurement.

**40.174** The corner of sections 2 and 11.

N. 0° 51.2' E., on the west boundary of section 2.

Over rolling mountainous land, through scattered pinon and juniper growth.

**1.770** The closing corner of sections 3 and 10, monumented with a granite stone, 14x10x4 ins., firmly set and plainly marked 5 notches on the S edge and 2 notches on the E edge, CC on W face.

At the corner point

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T26S R1W  
CC  $\frac{S3}{S10}$  | S2  
1994

Deposit the marked stone alongside the corner.

Set a steel fence post alongside the corner.

Corner is located on gentle E slope of hill.

**3.290** From this point, the erroneous marked common section corner identified by Forest Service Photogrammetry procedures and Bureau's Remonumentation Program has been found to be defective in position. The monuments as marked and described in the official record of 1972 bears East, 57 lks. distance, with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above ground. Recognized flintstone, 14x10x6 ins., incorrectly accepted as properly marked original corner was found alongside iron post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 26 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From which

A cedar stump, 16 ins. diam., bears N. 16° 31' W., 2.36 chs. distance.  
(Record, N. 2° 30' W., 4.40 chs.)

Brass cap was erroneously marked as common corner. Add marks AM for Amended monument and bury stone and iron post, 6 ins. below surface of ground.

**37.838** Point for the 1/4 section corner of sections 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap marked:

T26S R1W  
1/4  
S3 | S2  
1994

Corner is located 1 1/2 chs. distance south of trail road, bears E and W.

**74.257** The standard corner of sections 34 and 35, on the north boundary of the township, monumented with an iron post, 2 1/2 ins. diam., 12 ins. above ground and in a mound of stone, with brass cap marked as described in the official record of the 1961 resurvey of the 5th Standard Parallel South, remark brass cap:

SC  
T25S R1W  
S34 | S35  
S3 | S2  
1994

---

The Subdivision of Section 1,  
T. 26 S., R. 1 W., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 1 and 12.

N. 1° 10.6' E., on the N-S center line of section 1.

**39.930** Point for the center 1/4 section corner of section 1, at intersection with the E-W center line.

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

THE SUBDIVISION OF SECTION 1,  
T. 26 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T26S R1W  
C 1/4 S1  
1994

Set a steel fence post alongside the corner.

Corner is located 1 lk. W of Torgersen Eng. rebar and cap, marked L.S. 6698.

**59.650** Point for the center N 1/16 section corner; not monumented.

**78.232** The 1/4 section corner of section 1 only, on the north boundary of the township, hereinbefore described.

---

From the 1/4 section corner of sections 1 and 6, hereinbefore described.

N. 87° 42.4' W., on the E-W center line of section 1.

**10.159** Point for the C-E-E 1/64 section corner of section 1; not monumented.

**20.318** Point for the center E 1/16 section corner of section 1.

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T26S R1W  
C ——— E 1/16 ——— C  
S1  
1994

Set a steel fence post alongside the corner.

Corner is located on steep NE slope in sagebrush.

**40.636** The center 1/4 section corner of section 1.

**80.496** The 1/4 section corner of sections 1 and 2.

---

From the center E 1/16 section corner of section 1.

N. 0° 29.1' E., on the N-S center line of the NE 1/4 of section 1.

**9.886** Point for the C-S-NE 1/64 section corner of section 1; not monumented.

**19.772** Point for the NE 1/16 section corner, at intersection with the E-W center line of the NE 1/4; not monumented.

THE SUBDIVISION OF SECTION 1,  
T. 26 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

**29.658** Point for the C-N-NE 1/64 section corner of section 1; not monumented.

**38.976** The E 1/16 section corner of section 1 only, hereinbefore described.

---

From the point for the N 1/16 section corner of sections 1 and 6, on the east boundary of the township, hereinbefore described.

N. 87° 50.2' W., on the E-W center line of the NE 1/4 of section 1.

**7.530** Point for the 1/1024 section corner of section 1; not monumented.

**10.040** Point for the C-E-NE 1/64 section corner of section 1; not monumented.

**20.080** The point for the NE 1/16 section corner.

**40.160** The point for the center N 1/16 section corner.

---

From the point for the C-E-NE 1/64 section corner of section 1.

N. 0° 08.7' E., on the N-S center line of the NE 1/4, NE 1/4, of section 1.

**9.900** Point for the NE-NE 1/64 section corner, at intersection with the E-W center line of the NE 1/4, NE 1/4 of section 1; not monumented.

**19.516** The point for the E-E 1/64 section corner on the north boundary of section 1, hereinbefore described.

---

From the point for the N-N 1/64 section corner of sections 1 and 6 on the east boundary of the township; hereinbefore described.

N. 87° 54.0' W., on the E-W center line of the NE 1/4, NE 1/4, of section 1.

**7.485** Point for the 1/1024 section corner of section 1; not monumented.

**9.980** The point for the NE-NE 1/64 section corner.

**19.960** The point for the C-N-NE 1/64 section corner.

---

From the point for the 1/1024 section corner on the E-W center line of the NE 1/4, NE 1/4, of section 1.

THE SUBDIVISION OF SECTION 1,  
T. 26 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

N. 0° 03.7' E., on the N-S center line of the W 1/2, NE 1/4, NE 1/4, NE 1/4, of section 1.

**0.413** Point for the SW corner of Lot 5, identical with the NW corner of Lot 8.

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a collar of stone, with aluminum cap marked:

	T26S R1W
	<u>Lot 5</u>
Lot 6	Lot 8
	1995

Set a steel fence post alongside the corner.

**9.690** The point for the 1/1024 section corner on the north boundary of section 1, hereinbefore described.

---

From the SE corner of Lot 5, identical with the NE corner of Lot 8, on the east boundary of the township, hereinbefore described.

N. 88° 43.1' W., between Lots 5 and 8, on a mean bearing between the north boundary and the E-W center line of the NE 1/4 of section 1.

**7.480** The SW corner of Lot 5, identical with the NW corner of Lot 8.

---

From the point for the 1/1024 section corner on the E-W center line of the NE 1/4 of section 1.

N. 0° 03.7' E., on the N-S center line of the W 1/2, SE 1/4, NE 1/4, NE 1/4, of section 1.

**9.903** The point for the 1/1024 section corner on the E-W center line of the NE 1/4, NE 1/4, of section 1.

---

From the point for the C-E-E 1/64 section corner of section 1.

N. 0° 08.9' E., on the N-S center line of the SE 1/4, NE 1/4, of section 1.

**9.900** Point for the SE-NE 1/64 section corner, at intersection with the E-W center line of the SE 1/4, NE 1/4, of section 1; not monumented.

**19.800** The point for the C-E-NE 1/64 section corner.

---

THE SUBDIVISION OF SECTION 1,  
T. 26 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the S-N 1/64 section corner of sections 1 and 6, on the east boundary of the township, hereinbefore described.

N. 87° 46.1' W., on the E-W center line of the SE 1/4, NE 1/4, of section 1.

**7.575** Point for the 1/1024 section corner on the E-W center line of the SE 1/4, NE 1/4 of section 1.

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T26S R1W  
1/1024  
S1  
1995

Set a steel fence post alongside the corner.

**10.100** The point for the SE-NE 1/64 section corner.

**20.200** The point for the C-S-NE 1/64 section corner.

---

From the point for the 1/1024 section corner on the E-W center line of the SE 1/4, NE 1/4, of section 1.

N. 0° 03.9' E., on the N-S center line of the W 1/2, NE 1/4, SE 1/4, NE 1/4, of section 1.

**9.904** The point for the 1/1024 section corner on the E-W center line of the NE 1/4, of section 1.

---

The Subdivision of Section 11,  
T. 26 S., R. 1 W., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 11 and 14.

N. 2°37.4' E., on the N-S center line of section 11.

**20.355** Point for the center S 1/16 section corner; not monumented.

**40.710** Point for the center 1/4 section corner, at intersection with the E-W center line of section 11.

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

THE SUBDIVISION OF SECTION 11,  
T. 26 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

T26S R1W  
C 1/4 S11  
1995

**81.213** The 1/4 section corner of sections 2 and 11.

---

From the 1/4 section corner of sections 11 and 12.

S. 88°38.9' W., on the E-W center line of section 11.

**9.945** Point for the C-E-E 1/64 section corner of section 11; not monumented.

**19.890** Point for the center E 1/16 section corner of section 11.

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T26S R1W  
C ——— E 1/16 ——— C  
S11  
1995

Set a steel fence post alongside the corner.

**39.780** The center 1/4 section corner.

**81.074** The 1/4 section corner of section 11 only.

---

From the point for the E 1/16 section corner of sections 11 and 14.

N. 0° 47.6' E., on the N-S center line of the SE 1/4, of section 11.

**20.150** Point for the SE 1/16 section corner, at intersection with the E-W center line of the SE 1/4 of section 11.

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T26S R1W  
SE 1/16 S11  
1995

Set a steel fence post alongside the corner.

**40.300** The center E 1/16 section corner.

---

THE SUBDIVISION OF SECTION 11,  
T. 26 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

- From the S 1/16 section corner of sections 11 and 12.  
S. 88° 10.5' W., on the E- W center line of the SE 1/4, of section 11.
- 10.274** Point for the C-E-SE 1/64 section corner of section 11; not monumented.
- 20.548** The SE 1/16 section corner of section 11.
- 41.096** The point for the center S 1/16 section corner of section 11.
- 
- From the point for the C-E-SE 1/64 section corner of section 11.  
N. 0° 08.2' W., on the N-S center line of the NE 1/4, SE 1/4, of section 11.
- 7.520** Point for the C-N-S-NE-SE 1/1024 section corner of section 11.  
Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:
- C-N-S-NE-SE  
1/1024  
1995
- Set a steel fence post alongside the corner.
- 12.534** Point for the C-S-N-NE-SE 1/1024 section corner of section 11.  
Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:
- C-S-N-NE-SE  
1/1024  
1995
- Set a steel fence post alongside the corner.
- 20.054** The point for the C-E-E 1/64 section corner of section 11.
- 
- From the S-N-N-S 1/1024 section corner of sections 11 and 12.  
S. 88° 28.2' W., on the E-W center line of the S 1/2, NE 1/4, NE 1/4, SE 1/4, of section 11.
- 10.068** The C-S-N-NE-SE 1/1024 section corner of section 11.
-

THE SUBDIVISION OF SECTION 11,  
T. 26 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

- From the N-S-N-S 1/1024 section corner of sections 11 and 12.  
S. 88° 21.1' W., on the E-W center line of the N 1/2, SE 1/4, NE 1/4, SE 1/4, of section 11.
- 10.151** The C-N-S-NE-SE 1/1024 section corner of section 11.

---

The Subdivision of Section 13,  
T. 26 S., R. 1 W., Salt Lake Meridian, Utah

---

- From the 1/4 section corner of sections 13 and 24.  
N. 0° 06.4' E., on the N-S center line of section 13.  
Over private property.
- 40.222** Point for the center 1/4 section corner of section 13, at intersection with the E-W center line; not monumented.
- 59.937** Point for the center N 1/16 section corner of section 13; not monumented.
- 79.652** The 1/4 section corner of sections 12 and 13.

- 
- From the 1/4 section corner of sections 13 and 18, hereinbefore described.  
N. 87° 06.7' W., on the E-W center line of section 13.
- 20.222** Point for the center E 1/16 section corner of section 13.  
Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T26S R1W  
C ——— E 1/16 ——— C  
S13  
1994

- Set a steel fence post alongside the corner.  
Corner is located 10 lks. W of fence line, bears N and S.
- 40.444** The point for the center 1/4 section corner of section 13.
- 80.572** The 1/4 section corner of sections 13 and 14.
-

THE SUBDIVISION OF SECTION 13,  
T. 26 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the center E 1/16 section corner of section 13.

N. 0° 02.7' W., on the N-S center line of the NE 1/4 of section 13.

**19.837** Point for the NE 1/16 section corner of section 13, at intersection with the E-W center line.

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T26S R1W  
NE 1/16 S13  
1994

Set a steel fence post alongside the corner.

Corner is located in rolling pasture land.

**39.675** The point for the E 1/16 section corner of sections 12 and 13.

---

From the N 1/16 section corner of sections 13 and 18, hereinbefore described.

N. 87° 26.9' W., on the E-W center line of the NE 1/4 of section 13.

**20.163** The NE 1/16 section corner of section 13.

**40.326** The point for the center N 1/16 section corner of section 13.

---

From the E 1/16 section corner of sections 13 and 24.

N. 0° 10.5' W., on the N-S center line of the SE 1/4 of section 13.

**40.071** The center E 1/16 section corner of sections 13.

---

The Subdivision of Section 14,  
T. 26 S., R. 1 W., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 14 and 23.

N. 0° 46.4' W., on the N-S center line of section 14.

**20.130** Point for the center S 1/16 section corner of section 14; not monumented.

THE SUBDIVISION OF SECTION 14,  
T. 26 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS****40.260**

Point for the center 1/4 section corner of section 14, at intersection with the E-W center line.

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T26S R1W  
C 1/4 S14  
1994

Set a steel fence post alongside the corner.

Corner is located on SE slope in pinon and juniper growth.

**79.436**

The 1/4 section corner of sections 11 and 14.

---

From the 1/4 section corner of sections 13 and 14.

S. 87° 12.'6 W., on the E-W center line of section 14.

**21.004**

Point for the center E 1/16 section corner of section 14; not monumented.

**42.008**

The center 1/4 section corner of section 14.

**83.448**

The W 1/4 section corner of section 14 only.

---

From the E 1/16 section corner of sections 14 and 23.

N. 0° 10.3' E., on the N-S center line of the SE 1/4 of section 14.

**20.191**

Point for the SE 1/16 section corner of section 14, at intersection with the E-W center line.

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T26S R1W  
SE 1/16 S14  
1994

Set a steel fence post alongside the corner.

Corner is located on rolling E slope, in pinon and juniper growth.

**40.382**

Point for the center E 1/16 section corner of section 14.

---

THE SUBDIVISION OF SECTION 14,  
T. 26 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the S 1/16 section corner of sections 13 and 14.

S. 87° 20.5' W., on the E-W center line of the SE 1/4 of section 14.

**20.670** The SE 1/16 section corner of section 14.

**41.340** The point for the center S 1/16 section corner of section 14.

---

The Subdivision of Section 23,  
T. 26 S., R. 1 W., Salt Lake Meridian, Utah

---

From the point for the 1/4 section corner of sections 23 and 26.

N. 1° 26.5' W., on the N-S center line of section 23.

**19.789** Point for the center S 1/16 section corner of section 23.

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T26S R1W  
C  
S 1/16 | S23  
C  
1994

Set a steel fence post alongside the corner.

Corner is located on E bank of cement irrigation ditch, flows SW.

**39.578** Point for the center 1/4 section corner of section 23, at intersection with the E-W center line.

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T26S R1W  
C 1/4 S23  
1994

Set a steel fence post alongside the corner.

Corner is located 10 lks. S of trail road, bears NE and SW.

**79.606** The 1/4 section corner of sections 14 and 23.

---

THE SUBDIVISION OF SECTION 23,  
T. 26 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the point for the 1/4 section corner of sections 23 and 24.

S. 88° 08.7' W., on the E-W center line of section 23.

**20.087** Point for the center E 1/16 section corner of section 23.

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T26S R1W  
C     E 1/16     C  
          S23  
          1994

Set a steel fence post alongside the corner.

Corner is located on gentle E slope in sagebrush.

**40.174** The center 1/4 section corner of section 23.

**59.967** Point for the center W 1/16 section corner of section 23; not monumented.

**79.760** The W 1/4 section corner of section 23 only.

---

From the center E 1/16 section corner of section 23.

N. 1° 05.4' W., on the N-S center line of the NE 1/4 of section 23.

**40.268** The E 1/16 section corner of sections 14 and 23.

---

From the point for the E 1/16 section corner of sections 23 and 26.

N. 1° 05.3' W., on the N-S center line of the SE 1/4 of section 23.

**20.022** Point for the SE 1/16 section corner of section 23, at intersection with the E-W center line.

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T26S R1W  
SE 1/16 S23  
1994

Set a steel fence post alongside the corner.

THE SUBDIVISION OF SECTION 23,  
T. 26 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From this corner, Torgerson Eng. rebar and cap, marked L.S. 6698, and corner of fence, projecting E, W and N, bears S. 17° 34' E., 1.03 chs. dist.

**40.044** The center E 1/16 section corner of section 23.

From the point for the S 1/16 section corner of sections 23 and 24.

S. 88° 48.7' W., on the E-W center line of the SE 1/4 of section 23.

**19.964** The SE 1/16 section corner of section 23.

**39.928** The center S 1/16 section corner of section 23.

From the W 1/16 section corner of sections 23 and 26.

N. 1° 22.5' W., on the N-S center line of the SW 1/4 of section 23.

**19.558** Point for the SW 1/16 section corner of section 23, at intersection with the E-W center line.

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T26S R1W  
SW 1/16 S23  
1994

Set a steel fence post alongside the corner.

Located on rolling SE slope in sagebrush.

**39.116** The point for the center W 1/16 section corner of section 23.

From the center S 1/16 section corner of section 23.

S. 88° 48.7' W., on the E-W center line of the SW 1/4 of section 23.

**19.816** The SW 1/16 section corner of section 23.

**39.633** The point for the S 1/16 section corner of section 23 only.

THE SUBDIVISION OF SECTION 24,  
T. 26 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

The Subdivision of Section 24,  
T. 26 S., R. 1 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 24 and 25.

N. 0° 38.7' W., on the N-S center line of section 24.

**20.085** Point for the center S 1/16 section corner of section 24.

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T26S R1W  
C  
S 1/16 | S24  
C  
1994

Set a steel fence post alongside the corner.

Corner is located on E bank of irrigation ditch, flows S-SW.

**40.170** Point for the center 1/4 section corner of section 24, at intersection with the E-W center line; not monumented.

**80.369** The 1/4 section corner of sections 13 and 24.

From the 1/4 section corner of sections 19 and 24, hereinbefore described.

N. 87° 59.7' W., on the E-W center line of section 24.

**20.378** Point for the center E 1/16 section corner of section 24.

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T26S R1W  
C  $\frac{E\ 1/16}{S24}$  C  
1994

Set a steel fence post alongside the corner.

**40.756** Point for the center 1/4 section corner of section 24.

**81.504** The point for the 1/4 section corner of sections 23 and 24.

THE SUBDIVISION OF SECTION 24,  
T. 26 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the center E 1/16 section corner of section 24.

N. 0° 36.0' W., on the N-S center line of the NE 1/4 of section 24.

**40.044** The E 1/16 section corner of sections 13 and 24.

---

From the point for the E 1/16 section corner of sections 24 and 25.

N. 0° 35.5' W., on the N-S center line of the SE 1/4 of section 24.

**19.999** Point for the SE 1/16 section corner of section 24, at intersection with the E-W center line.

Set an aluminum pipe, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T26S R1W  
SE 1/16 S24  
1994

Set a steel fence post alongside the corner.

**39.998** The center E 1/16 section corner of section 24.

---

From the point for the S 1/16 section corner of sections 19 and 24, hereinbefore described.

N. 88° 14.0" W., on the E-W center line of the SE 1/4 of section 24.

**20.356** The SE 1/16 section corner of section 24.

**40.712** The center S 1/16 section corner of section 24.

---

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD ASSISTANTS**

---

Name	Capacity
Philip Tobler	Surveying Technician
Shawn Peterson	Surveying Technician


## CERTIFICATE OF SURVEY

I, *Ferrel D. Reynolds, Cadastral Surveyor*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *17th day of June, 1994*, I have *dependently resurveyed portions of the north boundary, east boundary, and interior subdivisional lines and surveyed the subdivision of sections 1, 11, 13, 14, 23, and 24, in Township 26 South, Range 1 West,*

of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

\_\_\_\_\_  
May 22, 1996

Date

  
\_\_\_\_\_  
(Cadastral Surveyor)

\_\_\_\_\_  
Date

\_\_\_\_\_  
(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of portions of the north boundary, east boundary, and interior subdivisional lines, and the survey of the subdivision of sections 1, 11, 13, 14, 23, and 24, Township 26 South, Range 1 West, Salt Lake Meridian, Utah,*

executed by *Ferrel D. Reynolds, Cadastral Surveyor*

having been critically examined and found correct, are hereby approved.

\_\_\_\_\_  
May 22, 1996

Date

  
\_\_\_\_\_  
(Chief Cadastral Surveyor for Utah)