

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF
THE DEPENDENT RESURVEY OF
THE SOUTH BOUNDARY,
A PORTION OF THE WEST AND NORTH BOUNDARIES,
A PORTION OF THE SUBDIVISIONAL LINES
AND THE
SUBDIVISION OF CERTAIN SECTIONS
IN
TOWNSHIP 23 SOUTH, RANGE 5 EAST

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Jerry L. Thomas
Cadastral Surveyor

Under special instructions dated *February 22, 1991*, approved *March 22, 1991*, which provided for the surveys included under Group Number 759, and assignment instructions dated *September 19, 1991*.

Survey commenced *October 15, 1991*

Survey completed *October 29, 1992*

TOWNSHIP 23 SOUTH, RANGE 5 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

The following field notes describe the dependent resurvey of the south boundary, a portion of the west and north boundaries, a portion of the subdivisional lines, and the subdivision of certain sections in T. 23 S., R. 5 E., Salt Lake Meridian, in the State of Utah.

History of Surveys

	<u>Surveyed by</u>		<u>Retr. or Resurveyed by</u>	
<u>NORTH BOUNDARY</u>				
Portion	A.D. Ferron	1881		
Portion			A.D. Ferron	1890
Portion	R. Gentry	1943	R. Gentry	1943
	E. Bird, A. Nelson, J.C. Clark, and R.C. Yundt		E. Bird, A. Nelson, J.C. Clark, and R.C. Yundt	
<u>SOUTH BOUNDARY</u>				
All	A.D. Ferron	1881		
Portion			A.D. Ferron	1890
<u>EAST BOUNDARY</u>				
Portion	A.D. Ferron	1873		
Portion	A.D. Ferron	1881	A.D. Ferron	1881
Portion			E. Bird	1937
Portion			G. Hatch and F. Reynolds	1978
<u>WEST BOUNDARY</u>				
Portion	A.D. Ferron	1881		
Portion	A.W. Miller and I. Hayes	1915		
Portion	R. Gentry	1942	R. Gentry and E. Bird	1942
Portion	E. Bird		R. Gentry, E. Bird, A. Nelson, J.C. Clark, and R.C. Yundt	1943
<u>SUBDIVISION</u>				
Portion	A.D. Ferron	1881		
Portion	R. Gentry	1943	R. Gentry	1943
	E. Bird, A. Nelson, J.C. Clark, and R.C. Yundt		E. Bird, A. Nelson, J.C. Clark, and R.C. Yundt	

TOWNSHIP 23 SOUTH, RANGE 5 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 759, dated February 22, 1991.

The directions of lines were determined by hour angle observations of the sun and Polaris, carried forward by sustained angulation. Distances were determined by electronic measurement.

Preliminary to the resurvey the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line notes are given herein.

The geographic position of the southeast corner of section 36, as determined by a tie made to National Geodetic Survey station "20SW/23S/6E-VC", is as follows:

Latitude $38^{\circ} 45' 49.77''$ Longitude $111^{\circ} 17' 52.82''$
N.A.D. 1927

The mean magnetic declination as determined from numerous readings throughout the survey is: $13 \frac{1}{2}^{\circ}$.

Dependent Resurvey of the South Boundary,
T. 23 S., R. 5 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
A.D. Ferron in 1881, and the Resurvey
by A.D. Ferron in 1890

Beginning at the corner of Tps. 23 and 24 S., Rs. 5 and 6 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap marked as described in the official record of the resurvey of the west boundary, T. 23 S., R. 6 E., in 1937.

N. $89^{\circ} 50' W.$, between sections 1 and 36, on the south boundary of the township.

Over gentle rolling land.

40.27

The 1/4 section corner of sections 1 and 36, monumented with a sandstone, 18x14x6 ins., firmly set, projecting 12 ins. above ground, plainly marked 1/4 on N. face.

At the corner point

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
1/4 S36
S1
T24S
1991

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone north of the corner.

N. 89° 32' W., beginning new measurement.

Asc. over NE. slope.

32.50 Gravel road, bears NE and SW.

40.47 The corner of sections 1, 2, 35, and 36, monumented with a trachyte stone, 12x12x12 ins., firmly set, projecting 10 ins. above ground, plainly marked 1 notch on the E. and 5 notches on the W. edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
S35 | S36
S2 | S1
T24S
1991

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone west of the corner.

N. 89° 16' W., between sections 2 and 35, on the south boundary of the township.

Over gentle rolling land.

39.83 Point for the 1/4 section corner of sections 2 and 35, at proportionate distance, falls in a graded road, bearing N. 85° E. and S. 85° W.

At the corner point

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a railroad spike, 8 ins. long, flush with surface of road, from which

An aluminum post, 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears North, 65 lks. dist., with brass cap marked T23S R5E 1/4 S35 RM 1991 and an arrow pointing to the corner.

An aluminum post, 30 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears South, 65 lks. dist., with brass cap marked T24S R5E 1/4 S2 RM 1991 and an arrow pointing to the corner.

79.66

The corner of sections 2, 3, 34, and 35, monumented with a trachyte stone 14x10x6 ins., firmly set, projecting 10 ins. above ground, plainly marked 2 notches on the E. and 4 notches on the W. edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
S34 S35
S3 S2
T24S
1991

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone west of the corner.

N. 89° 34' W., between sections 3 and 34, on the south boundary of the township.

Over nearly level land.

40.62

Point for the 1/4 section corner of sections 3 and 34, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
1/4 <u>S34</u>
S3
T24S
1992

Raise a mound of stone north of the corner.

50.775

Point for the E-W 1/64 section corner of sections 3 and 34.

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

E-W 1/64 $\frac{S34}{S3}$
1992

Raise a mound of stone north of the corner.

60.40 Gravel road, bears N. and curves SE.

60.93 Point for the W 1/16 section corner of sections 3 and 34.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

W 1/16 $\frac{S34}{S3}$
1992

Raise a mound of stone north of the corner.

Set a steel fence post alongside the aluminum post.

81.24 Point for the corner of sections 3, 4, 33, and 34, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
 $\frac{S33}{S4} \mid \frac{S34}{S3}$
T24S
1992

Raise a mound of stone west of the corner.

Set a steel fence post alongside the aluminum post.

N. 89° 34' W., between sections 4 and 33, on the south boundary of the township.

Over rolling land.

12.00 Utah State Highway No. 72, bears NE and SW.

17.00 East bound lane I-70, bears NE and SW.

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

21.00

West bound lane I-70, bears NE and SW.

40.62

The 1/4 section corner of sections 4 and 33, monumented with a trachyte stone, 11x6x4 ins., firmly set, projecting 8 ins. above ground, plainly marked 1/4 on the N. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
1/4 $\frac{S33}{S4}$
1991

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone north of the corner.

N. 89° 32' W., beginning new measurement.

40.27

The corner of sections 4, 5, 32, and 33, monumented with a sandstone, 12x6x4 ins., firmly set, projecting 8 ins. above ground, and plainly marked 4 notches on the E. and 2 notches on the W. edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
 $\frac{S32}{S5} \mid \frac{S33}{S4}$
T24E
1992

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone west of the corner.

Corner is located in fence line, which bears N. and S. 10° W.

N. 89° 28' W., between sections 5 and 32, on the south boundary of the township.

Over gentle rolling land.

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS
40.22

The 1/4 section corner of sections 5 and 32, monumented with a sandstone, 14x12x3 ins., firmly set, projecting 10 ins. above ground, dimly marked 1/4 on the N. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with aluminum cap marked:

T23S R5E
1/4 S32
 S5
T24S
1992

Deposit the marked stone alongside the aluminum post.

N. 89° 32' W., beginning new measurement.

40.37

The corner of sections 5, 6, 31, and 32, monumented with a sandstone, 18x6x6 ins., firmly set, projecting 12 ins. above ground, plainly marked 5 notches on the E. and 1 notch on the W. edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

T23S R5E
S31 | S32
S6 | S5
T24E
1992

Deposit the marked stone alongside the aluminum post.

S. 86° 50' W., between sections 6 and 31, on the south boundary of the township.

Over rolling land, through thick juniper and pinon.

39.20

The 1/4 section corner of sections 6 and 31, monumented with a broken sandstone, 20x18x18 ins., laying in a mound of stone, dimly marked 1/4.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with aluminum cap marked:

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T23S R5E
1/4 S31
S6
T24S
1992

Deposit the marked stone alongside the aluminum post.

S. 86° 38' W., beginning new measurement.

Asc. over rocky NE slope.

- 12.03** The witness point, which was the original closing township corner, monumented with a sandstone, 8x8x6 ins. above ground, marked WP on top, as described in the official record of the 1942 resurvey of the east boundary of T. 23 S., R. 4 E.
-

West, beginning new measurement.

- 0.52** The closing corner of Tps. 23 and 24 S., R. 5 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap marked as described in the official record of the 1942 resurvey of the east boundary of T. 23 S., R. 4 E.
-

Dependent Resurvey of a Portion of the East Boundary,
T. 25 S., R. 4 E., Salt Lake Meridian, Utah

Reestablishment of the Survey by A.D. Ferron in 1881,
and the Resurvey by Gentry and Bird in 1942

From the township corner of Tps. 23 and 24 S., R. 4 E., monumented with an iron post, 3 ins. diam., set, marked and witnessed as described in the official record of the 1942 resurvey of the east boundary of T. 23 S., R. 4 E.

N. 1° 04' W., on the east boundary of section 36.

Over rolling land; asc. over S. slope.

- 26.38** The closing township corner of Tps. 23 and 24 S., R. 5 E., hereinbefore described.

- 40.48** The 1/4 section corner of section 36 only, monumented with an iron post, 1 in. diam., set, marked and witnessed as described in the 1942 resurvey of the east boundary of T. 23 S., R. 4 E.
-

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 25 S., R. 4 E., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 1° 04' W., beginning new measurement.

6.76 Point for the S 1/16 section corner of section 31 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 4 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

T23S
R4E R5E
| S 1/16
| S31
1992

27.62 Point for the 1/4 section corner of section 31 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S
R4E R5E
| 1/4
| S31
1992

Raise a mound of stone east of the corner.

40.53 The corner of sections 25 and 36, is determined at record bearing and distance from the remains of the original bearing tree

A pinon, 12 ins. diam., bears S. 42° 45' W., 80 lks. dist., marked
T23S R5E S36 BT.

The other original bearing tree has been destroyed.

The iron post appears to have been taken out by a bulldozer.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S
R4E R5E
S25 | S31
S36 |
1992

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 25 S., R. 4 E., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 1° 14' E., along the east boundary of section 25.

Over gentle rolling land.

28.80 The closing corner of sections 30 and 31, monumented with an iron post, 2 ins. diam., set, marked and witnessed as described in the 1942 resurvey of the east boundary of T. 23 S., R. 4 E.

41.78 The 1/4 section corner of section 25 only, monumented with an iron post, 1 in. diam., set, marked and witnessed as described in the 1942 resurvey of the east boundary of T. 23 S., R. 4 E.

N. 1° 03' W., beginning new measurement.

27.45 Point for the 1/4 section corner of section 30 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S
R4E R5E
1/4
S30
1992

Raise a mound of stone east of the corner.

41.45 The corner of sections 24 and 25, monumented with an iron post, 2 ins. diam., set, marked and witnessed as described in the 1942 resurvey of the east boundary of T. 23 S., R. 4 E.

N. 0° 01' W., on the east boundary of section 24.

Over nearly level land.

6.225 Point for the N 1/16 section corner of section 30 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S
R4E R5E
N 1/16
S30
1992

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 25 S., R. 4 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Corner is located on spur top, which slopes E.

26.44 The closing corner of sections 19 and 30, monumented with an iron post, 2 ins. diam., set, marked and witnessed as described in the 1942 resurvey of the east boundary of T. 23 S., R. 4 E.

30.40 The 1/4 section corner of section 24 only, monumented with an iron post, 1 in. diam., set, marked and witnessed as described in the 1942 resurvey of the east boundary of T. 23 S., R. 4 E.

Dependent Resurvey of a Portion of the North Boundary,
T. 23 S., R. 5 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
A.D. Ferron in 1881, and the Resurvey by
Gentry, Bird, Nelson, and Clark in 1943

From the 1/4 section corner of sections 2 and 35, monumented with an iron post, 1 in. diam., set, marked and witnessed as described in the 1943 resurvey of the north boundary of T. 23 S., R. 5 E.

S. 89° 54' W., between sections 2 and 35.

Over rolling land.

20.09 Point for the W 1/16 section corner of sections 2 and 35.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

W 1/16 $\frac{S35}{S2}$
1991

Raise a mound of stone north of the corner.

40.18 The corner of sections 2, 3, 34, and 35, monumented with an iron post, 2 ins. diam., set, marked and witnessed as described in the 1943 resurvey of the north boundary of T. 23 S., R. 5 E.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 23 S., R. 5 E., Salt Lake Meridian, Utah

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Reestablishment of the Survey Executed by
A.D. Ferron in 1881

From the corner of sections 1, 2, 35, and 36, hereinbefore described.

N. $0^{\circ} 08'$ E., between sections 35 and 36.

Over rolling land.

8.00 Gravel road, bears NE and SW.

40.56 Point for the 1/4 section corner of sections 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E	
1/4	
S35	S36
1992	

Raise a mound of stone west of the corner.

73.50 East bound lane of I-70, bears NE and SW.

75.00 West bound lane of I-70, bears NE and SW.

81.12 Point for the corner of sections 25, 26, 35, and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E	
S26	S25
S35	S36
1992	

Raise a mound of stone west of the corner.

From this corner, the corner of sections 25 and 36, on the east boundary of the township, bears S. $89^{\circ} 18'$ E., 80.72 chs. dist. monumented with an iron post, 2 ins. diam., set, marked and witnessed as described in the 1937 resurvey of the west boundary of T. 23 S., R. 6 E.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the corner of sections 25 and 36, east boundary, the U.S. Geological Survey triangulation station "SEC COR 30SW/23S/6E/UC", bears S. $0^{\circ} 27'$ E., 0.509 chs. dist.

N. $1^{\circ} 29'$ E., between sections 25 and 26.

Over rolling land.

40.57

The 1/4 section corner of sections 25 and 26, monumented with a trachyte stone, 14x8x6 ins., firmly set, projecting 10 ins. above ground, marked 1/4 on the W. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
1/4
S26 S25
1992

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone west of the corner.

N. $0^{\circ} 20'$ E., beginning new measurement.

40.30

The corner of sections 23, 24, 25, and 26, monumented with a trachyte stone, 16x8x6 ins., firmly set, projecting 12 ins. above ground, dimly marked 2 notches on the S. and 1 notch on the E. edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
S23 S24
S26 S25
1992

Deposit the marked stone alongside the aluminum post.

N. $1^{\circ} 13'$ W., between sections 23 and 24.

Over rolling land.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS
40.05

The 1/4 section corner of sections 23 and 24, monumented with a trachyte stone, 16x8x6 ins., firmly set, projecting 10 ins. above ground, marked 1/4 on the W. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with aluminum cap marked:

T23S R5E
1/4
S23 | S24
1992

Deposit the marked stone alongside the aluminum post.

N. 2° 13' W., beginning new measurement.

20.13

Point for the N 1/16 section corner of sections 23 and 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

N 1/16
S23 | S24
1992

Set a steel fence post alongside the aluminum post.

40.26

The corner of sections 13, 14, 23, and 24, monumented with a trachyte stone, 14x7x6 ins., firmly set, projecting 10 ins. above ground, marked 3 notches on the S. and 1 notch on the E. edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
S14 | S13
S23 | S24
1992

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone west of the corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the corner of sections 13, 18, 19, and 24, on the east boundary of the township, monumented with an iron post, 2 1/2 ins. diam., set, marked and witnessed as described in the official record of the 1978 resurvey of the west boundary of T. 23 S., R. 6 E.

N. 89° 38' W., between sections 13 and 24.

Over rolling land.

40.40

The 1/4 section corner of sections 13 and 24, monumented with a trachyte stone, 16x10x6 ins., firmly set, projecting 10 ins. above ground, marked 1/4 on the N. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
1/4 $\frac{S13}{S24}$
1992

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone north of the corner.

N. 88° 52' W., beginning new measurement.

40.44

The corner of sections 13, 14, 23, and 24.

N. 0° 25' E., between sections 13 and 14.

Over rolling land.

39.76

The 1/4 section corner of sections 13 and 14, monumented with a sandstone, 15x11x8 ins., firmly set, projecting 10 ins. above ground, dimly marked 1/4 on the W. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
1/4
S14 | S13
1992

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone west of the corner.

N. $0^{\circ} 25'$ E., beginning new measurement.

40.26

The corner of sections 11, 12, 13, and 14, monumented with a sandstone, 16x10x6 ins., firmly set, projecting 10 ins. above ground, dimly marked 4 notches on the S. and 1 notch on the E. edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E	
<u>S11</u>	<u>S12</u>
S14	S13
1992	

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone west of the corner.

From the corner of sections 7, 12, 13, and 18, on the east boundary of the township, monumented with an iron post, 2 1/2 ins. diam., set, marked and witnessed as described in the official record of the 1978 resurvey of the west boundary of T. 23 S., R. 6 E.

N. $89^{\circ} 37'$ W., between sections 12 and 13.

Over rolling land.

40.17

The 1/4 section corner of sections 12 and 13, monumented with a sandstone, 10x9x6 ins., firmly set, projecting 8 ins. above ground, dimly marked 1/4 on the N. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E	
1/4	<u>S12</u>
	S13
1992	

Deposit the marked stone alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Raise a mound of stone north of the corner.

N. $89^{\circ} 37'$ W., beginning new measurement.

35.00 Paved road, bears NW and SE.

40.16 The corner of sections 11, 12, 13, and 14.

N. $1^{\circ} 37'$ E., between sections 11 and 12.

Over rolling land.

3.00 Paved road, bears NW and SE.

40.21 Point for the 1/4 section corner of sections 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
1/4
S11 | S12
1992

Raise a mound of stone west of the corner.

80.42 Point for the corner of sections 1, 2, 11, and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
S2 | S1
S11 | S12
1992

Set a steel fence post alongside the aluminum post.

From the corner of sections 1, 6, 7, and 12, on the east boundary of the township, monumented with an iron post, 2 1/2 ins. diam., set, marked and witnessed as described in the official record of the 1978 resurvey of the west boundary of T. 23 S., R. 6 E.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 87° 58' W., between sections 1 and 12.

Over rolling land.

37.89

The 1/4 section corner of sections 1 and 12, monumented with a sandstone, 18x12x3 ins., firmly set, projecting 10 ins. above ground, dimly marked 1/4 on the N. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
1/4 $\frac{S1}{S12}$
1992

Deposit the marked stone alongside the aluminum post.

S. 88° 19' W., beginning new measurement.

40.24

The corner of sections 1, 2, 11, and 12.

N. 1° 37' W., between sections 1 and 2.

Over rolling land.

2.00

Utah State Highway No. 10, bears NE and SW.

40.21

Point for the 1/4 section corner of sections 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with aluminum cap marked:

T23S R5E
1/4
S2 | S1
1992

80.61

The corner of sections 1, 2, 35, and 36, on the north boundary of the township, monumented with an iron post, 2 ins. diam., set, marked and witnessed as described in the official record of the 1943 resurvey of the north boundary of T. 23 S., R. 5 E.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the corner of sections 2, 3, 34, and 35, on the south boundary of the township, hereinbefore described.

N. 1° 22' W., between sections 34 and 35.

Over rolling land.

34.00 East bound lane of I-70, bears NE and SW.

35.50 West bound lane of I-70, bears NE and SW.

39.97 The $\frac{1}{4}$ section corner of sections 34 and 35, monumented with a trachyte stone, 11x10x6 ins., firmly set, projecting 9 ins. above ground, marked $\frac{1}{4}$ on the W. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
1/4
S34 | S35
1992

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone west of the corner.

N. 0° 44' E., beginning new measurement.

40.31 Point for the corner of sections 26, 27, 34, and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
S27 | S26
S34 | S35
1992

Raise a mound of stone west of the corner.

From the corner of sections 25, 26, 35, and 36.

N. 89° 53' W., between sections 26 and 35.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Over rolling land.

40.15 Point for the 1/4 section corner of sections 26 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
1/4 $\frac{S26}{S35}$
1992

Raise a mound of stone north of the corner.

80.30 The corner of sections 26, 27, 34, and 35.

N. 0° 04' E., between sections 26 and 27.

Over rolling land.

40.29 Point for the 1/4 section corner of sections 26 and 27 at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
1/4
S27 | S26
1992

Raise a mound of stone west of the corner.

80.58 Point for the corner of sections 22, 23, 26, and 27, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with aluminum cap marked.

T23S R5E
S22 | S23
S27 | S26
1992

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the corner of sections 23, 24, 25, and 26.

S. 89° 53' W., between sections 23 and 26.

Over rolling land.

40.71 Point for the 1/4 section corner of sections 23 and 26, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
1/4 $\frac{S23}{S26}$
1992

Raise a mound of stone north of the corner.

61.065 Point for the W 1/16 section corner of sections 23 and 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

W 1/16 $\frac{S23}{S26}$
1992

Set a steel fence post alongside the aluminum post.

81.42 The corner of sections 22, 23, 26, and 27.

N. 0° 48' W., between sections 22 and 23.

Over rolling land; desc. over steep NW slope.

20.145 Point for the S 1/16 section corner of sections 22 and 23.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

S 1/16
S22 | S23
1992

Raise a mound of stone west of the corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

40.29

Point for the 1/4 section corner of sections 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
1/4
S22 | S23
1992

Raise a mound of stone west of the corner.

80.58

Point for the corner of sections 14, 15, 22, and 23, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
S15 | S14
S22 | S23
1992

Raise a mound of stone west of the corner.

From the corner of sections 13, 14, 23, and 24.

S. 89° 32' W., between sections 14 and 23.

Over rolling land.

40.24

The 1/4 section corner of sections 14 and 23, monumented with a trachyte stone, 14x12x6 ins., firmly set, projecting 10 ins. above ground, plainly marked 1/4 on the N. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
1/4 S14
S23
1992

Deposit the marked stone alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Raise a mound of stone north of the corner.

N. $89^{\circ} 21'$ W., beginning new measurement.

39.87 The corner of sections 14, 15, 22, and 23.

N. $0^{\circ} 20'$ E., between sections 14 and 15.

Over rolling land.

5.00 Utah State Highway No. 10, bears NE and SW.

39.81 Point selected for the witness corner of sections 14 and 15.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

WC
T23S R5E
1/4
S15 \uparrow S14
1992

40.29 Point for the 1/4 section corner of sections 14 and 15, at proportionate distance, falls in deep wash, and is unsafe to monument.

60.435 Point for the N 1/16 section corner of sections 14 and 15.

Set an aluminum post, 30 ins. long, 2 1/2 diam., 24 ins. in the ground, with aluminum cap marked:

N 1/16
S15 | S14
1992

Set a steel fence post alongside the aluminum post.

68.80 Dirt road, bears E. and W.

80.58 The corner of sections 10, 11, 14, and 15, monumented with a sandstone boulder 10x5x2 ft. above ground, plainly marked with a cross (+), 4 grooves on the S. and 2 grooves on the E., near the E. edge of the boulder.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a re-bar, 12 ins. long, 5/8 ins. diam., in a drill hole, 8 ins. deep, with aluminum cap marked:

T23S R5E	
S10	S11
S15	S14
1992	

Raise a mound of stone, at the base, and near the E. edge of the boulder.

From the corner of sections 11, 12, 13, and 14.

N. 89° 31' W., between sections 11 and 14.

Over rolling land.

40.11 Point for the 1/4 section corner of sections 11 and 14, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E	
1/4	S11
S14	S14
1992	

Set a steel fence post alongside the aluminum post.

41.50 Utah State Highway No. 10, bears NE and SW.

80.22 The corner of sections 10, 11, 14, and 15.

N. 0° 55' E., between sections 10 and 11.

Over broken and rolling land; asc. over rocky SE slope.

40.65 Point for the 1/4 section corner of sections 10 and 11, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T23S R5E
1/4
S10 | S11
1992

- 81.30** The corner of sections 2, 3, 10, and 11, monumented with an iron post, 2 ins. diam., set, marked and witnessed as described in the official record of the 1943 resurvey of a portion of the subdivisional lines in T. 23 S., R. 5 E.

From the corner of sections 1, 2, 11, and 12.

N. 88° 53' W., between sections 2 and 11.

Over rolling land.

- 1.20** Utah State Highway No. 10, bears NE and SW.

- 40.51** Point selected for the witness corner of secs. 2 and 11.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

WC
T23S R5E
1/4 ← $\frac{S2}{S11}$
1992

- 40.59** True point for the 1/4 section corner of sections 2 and 11, at proportionate distance, falls on edge of sandstone boulder and cannot be monumented; there is no remaining evidence of the original corner.

- 81.18** The corner of sections 2, 3, 10, and 11.

Reestablishment of the Survey Executed by
Gentry, Bird, Nelson, and Clark in 1943

From the 1/4 section corner of section 2 only, monumented with an iron post, 1 ins. diam., set, marked, and witnessed as described in the 1943 survey of a portion of the subdivisional lines in T. 23 S., R. 5 E.

N. 1° 05' W., along the west boundary of section 2.

Over rolling land.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

0.73

The 1/4 section corner of section 3 only, monumented with an iron post, 1 in. diam., set, marked, and witnessed as described in the 1943 survey of a portion of the subdivisional lines in T. 23 S., R. 5 E.

19.645

Point for the N 1/16 section corner of section 2 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

| N 1/16
| S2
| 1991

Set a steel fence post alongside the aluminum post.

39.60

The corner of sections 2, 3, 34, and 35, hereinbefore described.

Reestablishment of the Survey Executed by
A.D. Ferron in 1881

From the corner of sections 3, 4, 33, and 34, on the south boundary of the township, hereinbefore described.

N. 0° 07' E., between sections 33 and 34.

Over rolling land.

0.50

Utah State Highway No. 72, bears NE and SW.

3.50

East bound lane, I-70, bears NE and SW.

5.50

West bound lane, I-70, bears NE and SW.

20.04

Point for the S 1/16 section corner of sections 33 and 34.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone to top, with aluminum cap marked:

S 1/16
S33 | S34
1992

40.08

The 1/4 section corner of sections 33 and 34, monumented with a trachyte stone, 14x12x4 ins., firmly set, projecting 10 ins. above ground, plainly marked 1/4 on the W. face.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
1/4
S33 | S34
1991

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone west of the corner.

N. 0° 11' E., beginning new measurement.

40.22

The corner of sections 27, 28, 33, and 34, monumented with a trachyte stone, 14x7x6 ins., firmly set, projecting 10 ins. above ground, marked 1 notch on the S. and 3 notches on the E. edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
S28 | S27
S33 | S34
1991

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone west of the corner.

From the corner of sections 26, 27, 34, and 35.

N. 89° 33' W., between sections 27 and 34.

Over rolling land.

40.28

Point for the 1/4 section corner of sections 27 and 34, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T23S R5E
1/4 $\frac{S27}{S34}$
1992

Raise a mound of stone north of the corner.

59.30 Utah State Highway No. 10, bears NW and SE.

60.42 Point for the W 1/16 section corner of sections 27 and 34.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

W 1/16 $\frac{S27}{S34}$
1992

Set a steel fence post alongside the aluminum post.

80.56 The corner of sections 27, 28, 33, and 34.

N. 0° 04' E., between sections 27 and 28.

Over rolling land.

20.45 Point for the S 1/16 section corner of sections 27 and 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

S 1/16
S28 | S27
1991

Raise a mound of stone west of the corner.

40.90 Point for the 1/4 section corner of sections 27 and 28, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
1/4
S28 | S27
1991

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Raise a mound of stone west of the corner.

81.80

The corner of sections 21, 22, 27, and 28, monumented with a sandstone, 18x10x6 ins., firmly set, projecting 12 ins. above ground, marked 3 notches on the E. edge.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone to top, with aluminum cap marked:

T23S R5E	
<u>S21</u>	<u>S22</u>
S28	S27
1992	

Deposit the marked stone alongside the aluminum post.

From the corner of sections 22, 23, 26, and 27.

N. 87° 41' W., between sections 22 and 27.

Over rolling land; desc. over NW slope.

20.40

Point for the E 1/16 section corner of sections 22 and 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

E 1/16	<u>S22</u>
	S27
	1992

Raise a mound of stone north of the corner.

40.80

The 1/4 section corner of sections 22 and 27, monumented with a sandstone, 17x7x5 ins., firmly set, projecting 12 ins. above ground, dimly marked 1/4 on the N. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E	
1/4	<u>S22</u>
	S27
	1992

Deposit the marked stone alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Raise a mound of stone north of the corner.

N. $89^{\circ} 42'$ W., beginning new measurement.

5.00 Utah State Highway No. 10, bears NE and SW.

19.91 Point for the W 1/16 section corner of sections 22 and 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

W 1/16 $\frac{S22}{S27}$
1992

Set a steel fence post alongside the aluminum post.

Raise a mound of stone north of the corner.

39.82 The corner of sections 21, 22, 27, and 28.

N. $0^{\circ} 15'$ W., between sections 21 and 22.

Over rolling land; asc. over steep SE slope.

20.05 Point for the S 1/16 section corner of sections 21 and 22.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

S 1/16
S21 | S22
1992

Raise a mound of stone west of the corner.

40.10 Point for the 1/4 section corner of sections 21 and 22, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
1/4
S21 | S22
1992

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Raise a mound of stone west of the corner.

60.15

Point for the N 1/16 section corner of sections 21 and 22.

Set a re-bar, 12 ins. long, 5/8 ins. diam., in a drill hole, 10 ins. deep, with aluminum cap marked:

N 1/16
S21 | S22
1992

Raise a mound of stone west of the corner.

80.20

The corner of sections 15, 16, 21, and 22, monumented with a small mound of stone, foreign to area, is accepted as the best available evidence to the true corner position.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
S16 | S15
S21 | S22
1992

Raise a mound of stone west of the corner.

From the corner of sections 14, 15, 22, and 23.

N. 88° 57' W., between sections 15 and 22.

Over rolling land.

3.00

Utah State Highway No. 10, bears NW and SE.

39.90

Point for the 1/4 section corner of sections 15 and 22, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
1/4 S15
S22
1992

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

- Raise a mound of stone north of the corner.
- 59.85** Point for the W 1/16 section corner of sections 15 and 22.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:
- W 1/16 $\frac{S15}{S22}$
1992
- Raise a mound of stone north of the corner.
- 79.80** The corner of sections 15, 16, 21, and 22.
-
- N. 0° 11' E., between sections 15 and 16.
- Over rolling land.
- 40.12** The 1/4 section corner of sections 15 and 16, monumented with an iron post, 1 in. diam., set, marked, and witnessed as described in the 1943 survey of a portion of the subdivisional lines.
-
- N. 0° 31' E., beginning new measurement.
- 40.00** The corner of sections 9, 10, 15, and 16, monumented with an iron post, 2 ins. diam., set, marked, and witnessed as described in the 1943 survey of a portion of the subdivisional lines.
-
- From the corner of sections 10, 11, 14, and 15.
- N. 88° 40' W., between sections 10 and 15.
- Over broken land; asc. over steep and ledgey E. slope.
- 39.57** The 1/4 section corner of sections 10 and 15, monumented with an iron post, 1 in. diam., set, marked, and witnessed as described in the official record of the 1943 survey of a portion of the subdivisional lines.
-
- N. 89° 53' W., beginning new measurement.
- 40.18** The corner of sections 9, 10, 15, and 16.
-

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the corner of sections 4, 5, 32, and 33, on the south boundary of the township, hereinbefore described.

N. $0^{\circ} 08'$ E., between sections 32 and 33.

Over rolling land.

39.31

The 1/4 section corner of sections 32 and 33, monumented with a trachyte stone, 14x9x6 ins., set, and dimly marked 1/4 on the W. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
1/4
S32 | S33
1992

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone west of the corner.

N. $0^{\circ} 11'$ E., beginning new measurement.

41.13

The corner of sections 28, 29, 32, and 33, monumented with a trachyte stone, 15x11x8 ins., surrounded by a mound of stone, dimly marked.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

T23S R5E
S29 | S28
S32 | S33
1992

Deposit the dimly marked stone alongside the aluminum post.

From the corner of sections 27, 28, 33, and 34.

N. $89^{\circ} 29'$ W., between sections 28 and 33.

Over rolling land.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS
37.10

Point selected for the witness 1/4 section corner of sections 28 and 33.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

WC
T23S R5E
1/4 ← $\frac{S28}{S33}$
1992

Raise a mound of stone north of the corner.

40.43

True point for the 1/4 section corner of sections 28 and 33, at proportionate distance, falls in deep ravine and is unsafe to monument; there is no remaining evidence of the original corner.

78.50

Top of high ridge, bears N. and S.; desc. over steep W. slope.

80.86

The corner of sections 28, 29, 32, and 33.

N. 0° 10' W., between sections 28 and 29.

Over mountainous land; desc. over NW slope, through thick juniper and pinon timber.

40.52

Point for the 1/4 section corner of sections 28 and 29, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

T23S R5E
1/4
S29 | S28
1992

60.78

Point for the N 1/16 section corner of sections 28 and 29.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

N 1/16
S29 | S28
1992

Set a steel fence post alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS
81.04

The corner of sections 20, 21, 28, and 29, monumented with a mound of stone foreign to area. This position is harmoniously related to identified original corners, and is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E	
<u>S20</u>	<u>S21</u>
S29	S28
1992	

Raise a mound of stone west of the corner.

From the corner of sections 21, 22, 27, and 28.

S. 89° 44' W., between sections 21 and 28.

Over rolling land.

41.06

The 1/4 section corner of sections 21 and 28, monumented with a sandstone, 15x11x5 ins., firmly set, projecting 10 ins. above ground, marked 1/4 on the N. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E	
1/4	<u>S21</u>
	S28
1992	

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone north of the corner.

N. 89° 47' W., beginning new measurement.

40.10

The corner of sections 20, 21, 28, and 29.

N. 0° 35' E., between sections 20 and 21.

Over rolling land.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

20.11

Point for the S 1/16 section corner of sections 20 and 21, not monumented.

40.22

Point for the 1/4 section corner of sections 20 and 21, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
1/4
S20 | S21
1992

Set a steel fence post alongside the aluminum post.

Raise a mound of stone west of the corner.

60.33

Point for the N 1/16 section corner of sections 20 and 21.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 2 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

N 1/16
S20 | S21
1992

80.44

The corner of sections 16, 17, 20, and 21, monumented with an iron post, 2 ins. diam., set, marked, and witnessed as described in the official record of the 1943 resurvey of a portion of the subdivisional lines of T. 23 S., R. 5 E.

From the corner of sections 15, 16, 21, and 22.

N. 89° 52' W., between sections 16 and 21.

Over rolling land.

20.005

Point for the E 1/16 section corner of sections 16 and 21.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

E 1/16 $\frac{S16}{S21}$
1992

40.01

Point for the 1/4 section corner of sections 16 and 21, at proportionate distance; there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
1/4 $\frac{S16}{S21}$
1992

Raise a mound of stone north of the corner.

60.015 Point for the W 1/16 section corner of sections 16 and 21, falls in wash and is unsafe to monument.

61.20 Point selected for the witness corner of secs. 16 and 21.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

WC
W 1/16 $\frac{S16}{S21}$ →
1992

Set a steel fence post alongside the aluminum post.

80.02 The corner of sections 16, 17, 20, and 21.

From the corner of sections 5, 6, 31, and 32, on the south boundary of the township, hereinbefore described.

N. 0° 04' E., between sections 31 and 32.

Over rolling land.

20.04 Point for the S 1/16 section corner of sections 31 and 32.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

S 1/16
S31 | S32
1992

Raise a mound of stone west of the corner.

40.08 Point for the 1/4 section corner of sections 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
1/4
S31 | S32
1992

Set a steel fence post alongside the aluminum post.

80.16

The corner of sections 29, 30, 31, and 32, monumented with a sandstone, 16x8x4 ins., firmly set, projecting 6 ins. above ground, dimly marked 5 notches on the E. and 1 notch on the S. edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
S30 | S29
S31 | S32
1992

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

From the corner of sections 28, 29, 32, and 33.

N. 89° 26' W., between sections 29 and 32.

Over mountainous land; desc. over rocky W. slope, through thick juniper and pinon timber.

40.41

The 1/4 section corner of sections 29 and 32, monumented with a broken sandstone, set in a mound of stone, dimly marked 1/4 on N. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
1/4 S29
 S32
 1992

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposit the broken marked stone alongside the aluminum post.

Raise a mound of stone north of the corner.

From the corner of sections 29, 30, 31, and 32.

N. $89^{\circ} 33'$ W., between sections 30 and 31.

Over rolling land.

39.57 Point for the 1/4 section corner of sections 30 and 31, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T23S R5E
1/4	<u>S30</u>
	S31
	1992

Set a steel fence post alongside the aluminum post.

52.15 The closing corner of sections 30 and 31, on the west boundary of the township, hereinbefore described.

From the corner of sections 29, 30, 31, and 32.

N. $0^{\circ} 02'$ W., between sections 29 and 30.

Over rolling land.

40. 68 Point for the 1/4 section corner of sections 29 and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

	T23S R5E
	1/4
	S30 S29
	1992

61.02 Point for the N 1/16 section corner of sections 29 and 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

N 1/16
S30 | S29
1992

Raise a mound of stone west of the corner.

- 81.36** The corner of sections 19, 20, 29, and 30, monumented with an iron post, 2 ins. diam., set, marked, and witnessed as described in the official record of the 1943 resurvey of a portion of the subdivisional lines in T. 23 S., R. 5 E.

From the corner of sections 20, 21, 28, and 29.

N. 89° 29' W., between sections 20 and 29.

Over rolling land.

- 20.12** Point for the E 1/16 section corner of sections 20 and 29, not monumented.

- 40.24** Point for the 1/4 section corner of sections 20 and 29, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
1/4 $\frac{S20}{S29}$
1992

Set a steel fence post alongside the aluminum post.

- 60.36** Point for the W 1/16 section corner of sections 20 and 29.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

W 1/16 $\frac{S20}{S29}$
1992

Set a steel fence post alongside the aluminum post.

- 80.48** The corner of sections 19, 20, 29, and 30.

S. 89° 48' W., between sections 19 and 30.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Over rolling land.

19.97

Point for the E 1/16 section corner of sections 19 and 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

E 1/16 $\frac{S19}{S30}$
 1992

39.94

The 1/4 section corner of sections 19 and 30, monumented with an iron post, 1 in. diam., set, marked, and witnessed as described in the official record of the 1943 resurvey of a portion of the subdivisional lines of T. 23 S., R. 5 E.

N. 89° 49' W., beginning new measurement.

12.61

The closing corner of sections 19 and 30, on the west boundary of the township, hereinbefore described.

From the corner of sections 16, 17, 20, and 21.

N. 89° 50' W., between sections 17 and 20.

Over rolling land.

19.88

Point for the E 1/16 section corner of sections 17 and 20, falls on large sandstone boulder.

Set a re-bar, 12 ins. long, 5/8 ins. diam., in drill hole, 8 ins. deep, with aluminum cap marked:

E 1/16 $\frac{S17}{S20}$
 1992

Raise a mound of stone north of the corner.

39.76

The 1/4 section corner of sections 17 and 20, monumented with an iron post, 1 in. diam., set, marked, and witnessed as described in the official record of the 1943 resurvey of a portion of the subdivisional lines of T. 23 S., R. 5 E.

The Subdivision of Section 2,
T. 23 S., R. 5 E., Salt Lake Meridian, Utah

THE SUBDIVISION OF SECTION 2,
T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

- From true point for the 1/4 section corner of sections 2 and 11.
N. 1° 21' W., on the N-S center line of section 2.
Over rolling and broken land.
- 39.74** Point for the center 1/4 section corner of section 2, at intersection with the E-W center line.
Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:
T23S R5E
C 1/4 S2
1992
- 59.61** Point for the center N 1/16 section corner of section 2, not monumented.
- 79.73** The 1/4 section corner of sections 2 and 35, on the north boundary of the township, hereinbefore described.

- From the 1/4 section corner of sections 1 and 2.
N. 89° 33' W., on the E-W center line of section 2.
Over rolling and broken land.
- 40.37** The center 1/4 section corner of section 2.
- 60.56** Point for the center W 1/16 section corner of section 2, not monumented.
- 80.75** The 1/4 section corner of section 2 only.

- From the point for the center W 1/16 section corner of section 2.
N. 1° 13' W., on the N-S center line of the NW 1/4 of section 2.
Over rolling and broken land.
- 19.775** Point for the NW 1/16 section corner of section 2, at intersection with the E-W center line of the NW 1/4.
Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 2,
T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

NW 1/16 S2
1992

39.79 The W 1/16 section corner of section 2 and 35, on the north boundary of the township, hereinbefore described.

From the point for the center N 1/16 section corner of section 2.

N. $89^{\circ} 52'$ W., on the E-W center line of the NW 1/4 of section 2.

Over rolling and broken land.

20.145 The NW 1/16 section corner of section 2.

40.29 The N 1/16 section corner of section 2 only.

The Subdivision of Section 14,
T. 23 S., R. 5 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 14 and 23.

N. $0^{\circ} 30'$ E., on the N-S center line of section 14.

Over rolling land.

38.84 Point for the witness corner to the center 1/4 section corner of section 14.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

↑
WC
T23S R5E
C 1/4 S14
1992

Set a steel fence post alongside the aluminum post.

40.42 True point for the center 1/4 section corner of section 14, falls in deep wash and is unsafe to monument.

60.555 Point for the center N 1/16 section corner of section 14.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 14,
T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

C
N 1/16 | S14
C
1992

Set a steel fence post alongside the aluminum post.

80.69 The 1/4 section corner of sections 11 and 14.

From the 1/4 section corner of sections 13 and 14.

N. 89° 32' W., on the E-W center line of section 14.

Over rolling and broken land.

40.17 True point for the center 1/4 section corner of section 14.

61.90 Utah State Highway No. 10, bears NE and SW.

80.16 True point for the 1/4 section corner of sections 14 and 15.

From the center N 1/16 section corner of section 14.

N. 89° 32' W., on the E-W center line of the NW 1/4 of section 14.

Over rolling land.

11.50 Utah State Highway No. 10, bears NE and SW.

40.05 The N 1/16 section corner of sections 14 and 15.

The Subdivision of Section 15,
T. 23 S., R. 5 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 15 and 22.

N. 0° 33' E., on the N-S center line of section 15.

Over rolling land.

40.20 Point for the center 1/4 section corner of section 15, at intersection with the E-W center line.

THE SUBDIVISION OF SECTION 15,
T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
C 1/4 S15
1992

Set a steel fence post alongside the aluminum post.

80.77 The 1/4 section corner of sections 10 and 15.

From true point for the 1/4 section corner of sections 14 and 15.

N. 89° 04' W., on the E-W center line of section 15.

Over rolling land.

39.73 The center 1/4 section corner of section 15.

79.87 The 1/4 section corner of sections 15 and 16.

The Subdivision of Section 20,
T. 23 S., R. 5 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 20 and 29.

N. 0° 56' E., on the N-S center line of section 20.

Over rolling land.

20.045 Point for the center S 1/16 section corner of section 20.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

C
S 1/16 | S20
C
1992

40.09 Point for the center 1/4 section corner of section 20, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 20,
T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T23S R5E
C 1/4 S20
1992

Set a steel fence post alongside the aluminum post.

60.14 Point for the center N 1/16 section corner of section 20.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., on solid bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

C
N 1/16 | S20
C
1992

80.19 The 1/4 section corner of sections 17 and 20.

From the 1/4 section corner of sections 20 and 21.

N. 89° 40' W., on the E-W center line of section 20.

Over rolling land.

20.005 Point for the center E 1/16 section corner of section 20.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

C — E 1/16 — C
S20
1992

Set a steel fence post alongside the aluminum post.

40.01 The center 1/4 section corner of section 20.

80.04 The 1/4 section corner of sections 19 and 20, monumented with an iron post, 1 in. diam., set, marked and witnessed as described in the official record of the 1943 resurvey of a portion of the subdivisional lines of T. 23 S., R. 5 E.

From the center E 1/16 section corner of section 20.

N. 0° 45' E., on the N-S center line of the NE 1/4 of section 20.

Over rolling land.

THE SUBDIVISION OF SECTION 20,
T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS**20.08**

Point for the NE 1/16 section corner of section 20, at intersection with the E-W center line of the NE 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

NE 1/16 S20
1992

40.16

The E 1/16 section corner of sections 17 and 20.

From the N 1/16 section corner of sections 20 and 21.

N. 89° 45' W., on the E-W center line of the NE 1/4 of section 20.

Over rolling land.

19.945

The NE 1/16 section corner of section 20.

39.89

The center N 1/16 section corner of section 20.

From a point for the E 1/16 section corner of sections 20 and 29.

N. 0° 45' E., on the N-S center line of the SE 1/4 of section 20.

Over rolling land.

20.08

Point for the SE 1/16 section corner of section 20, at intersection with the E-W center line of the SE 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

SE 1/16 S20
1992

Set a steel fence post alongside the aluminum post.

40.16

The center E 1/16 section corner of section 20.

From a point for the S 1/16 section corner of sections 20 and 21.

N. 89° 34' W., on the E-W center line of the SE 1/4 of section 20.

Over rolling land.

THE SUBDIVISION OF SECTION 20,
T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS**20.065**

The SE 1/16 section corner of section 20.

40.13

The center S 1/16 section corner of section 20.

The Subdivision of Section 21,
T. 23 S., R. 5 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 21 and 28.

N. 0° 31' E., on the N-S center line of section 21.

Over rolling land.

40.37

Point for the center 1/4 section corner of section 21, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
C 1/4 S21
1992

Set a steel fence post alongside the aluminum post.

60.445

Point for the center N 1/16 section corner of section 21, not monumented.

80.52

The 1/4 section corner of sections 16 and 21.

 From the 1/4 section corner of sections 21 and 22.

N. 89° 59' W., on the E-W center line of section 21.

Over rolling land.

20.275

Point for the center E 1/16 section corner of section 21.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

C — $\frac{E\ 1/16}{S21}$ — C
1992

Set a steel fence post alongside the aluminum post.

THE SUBDIVISION OF SECTION 21,
T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS**40.55**

The center 1/4 section corner of section 21.

60.58

Point for the center W 1/16 section corner of section 21, not monumented.

80.61

The 1/4 section corner of sections 20 and 21.

From the center E 1/16 section corner of section 21.

N. 0° 08' E., on the N-S center line of the NE 1/4 of section 21.

Over rolling land.

20.06

Point for the NE 1/16 section corner of section 21, at intersection with the E-W center line of the NE 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

NE 1/16 S21
1992

Set a steel fence post alongside the aluminum post.

40.12

The E 1/16 section corner of sections 16 and 21.

From the N 1/16 section corner of sections 21 and 22.

N. 89° 56' W., on the E-W center line of the NE 1/4 of section 21.

Over rolling land.

20.14

The NE 1/16 section corner of section of section 21.

40.28

Point for the center N 1/16 section corner of section 21.

From a point for the center W 1/16 section corner of section 21.

N. 0° 33' E., on the N-S center line of the NW 1/4 of section 21.

Over rolling land.

20.09

Point for the NW 1/16 section corner of section 21, at intersection with the E-W center line of the NW 1/4.

THE SUBDIVISION OF SECTION 21,
T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

NW 1/16 S21
1992

Set a steel fence post alongside the aluminum post.

40.18 The true point for the W 1/16 section corner of sections 16 and 21.

From a point for the center N 1/16 section corner of section 21.

N. 89° 56' W., on the E-W center line of the NW 1/4 of section 21.

Over rolling land.

20.015 The NW 1/16 section corner of section 21.

40.03 The N 1/16 section corner of sections 20 and 21.

The Subdivision of Section 22,
T. 23 S., R. 5 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 22 and 27.

N. 0° 11' W., on the N-S center line of section 22.

Over rolling land.

9.00 Utah State Highway No. 10, bears NE and SW.

19.74 Point for the center S 1/16 section corner of section 22.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

C
S 1/16 | S22
C
1992

Raise a mound of stone west of the corner.

39.48 Point for the center 1/4 section corner of section 22, at intersection with the E-W center line.

THE SUBDIVISION OF SECTION 22,
T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
C 1/4 S22
1992

Raise a mound of stone west of the corner.

59.58 Point for the center N 1/16 section corner of section 22, not monumented.

79.68 The 1/4 section corner of sections 15 and 22.

From the 1/4 section corner of sections 22 and 23.

N. 88° 48' W., on the E-W center line of section 22.

Over rolling land.

20.17 Point for the center E 1/16 section corner of section 22, not monumented.

34.00 Utah State Highway No. 10, bears NE and SW.

40.34 The center 1/4 section corner of section 22.

60.27 Point for the center W 1/16 section corner of section 22.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

C $\frac{W\ 1/16}{S22}$ C
1992

Raise a mound of stone north of the corner.

80.20 The 1/4 section corner of sections 21 and 22.

From the E 1/16 section corner of sections 22 and 27.

N. 0° 29' W., on the N-S center line of the SE 1/4 of section 22.

Over rolling land.

THE SUBDIVISION OF SECTION 22,
T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS**19.94**

Point for the SE 1/16 section corner of section 22, at intersection with the E-W center line of the SE 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

SE 1/16 S22
1992

Raise a mound of stone west of the corner.

39.88

Point for the center E 1/16 section corner of section 22.

From the S 1/16 section corner of sections 22 and 23.

N. 88° 14' W., on the E-W center line of the SE 1/4 of section 22.

Over rolling land.

20.285

The SE 1/16 section corner of section 22.

34.00

Utah State Highway No. 10, bears NE and SW.

40.57

The center S 1/16 section corner of section 22.

From the W 1/16 section corner of sections 22 and 27.

N. 0° 13' W., on the N-S center line of the SW 1/4 of section 22.

Over rolling land.

19.89

Point for the SW 1/4 section corner of section 22, at intersection with the E-W center line of the SW 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

SW 1/16
S22
1992

Raise a mound of stone west of the corner.

39.78

The center W 1/16 section corner of section 22.

THE SUBDIVISION OF SECTION 22,
T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the center S 1/16 section corner of section 22.

N. $89^{\circ} 15'$ W., on the E-W center line of the SW 1/4 of section 22.

Over rolling land.

19.92 The SW 1/16 section corner of section 22.

39.84 The S 1/16 section corner of sections 21 and 22.

From the center W 1/16 section corner of section 22.

N. $0^{\circ} 13'$ W., on the N-S center line of the NW 1/4 of section 22.

Over rolling land.

20.07 Point for the NW 1/16 section corner of section 22, at intersection with the E-W center line of the NW 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

NW 1/16 S22
1992

Set a steel fence post alongside the aluminum post.

20.17 Center of bulldozed road, bears E. and W.

40.14 The W 1/16 section corner of sections 15 and 22.

From a point for the center N 1/16 section corner of section 22.

N. $88^{\circ} 52'$ W., on the E-W center line of the NW 1/4 of section 22.

Over rolling land.

19.94 The NW 1/16 section corner of section 22.

39.88 The N 1/16 section corner of sections 21 and 22.

The Subdivision of Section 23,
T. 23 S., R. 5 E., Salt Lake Meridian, Utah

THE SUBDIVISION OF SECTION 23,
T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the 1/4 section corner of sections 23 and 26.

N. $1^{\circ} 23'$ W., on the N-S center line of section 23.

Over rolling land.

20.08

Point for the center S 1/16 section corner of section 23.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

$$\begin{array}{c} \text{C} \\ \text{S } 1/16 \text{ | } \text{S}23 \\ \text{C} \\ 1992 \end{array}$$

Set a steel fence post alongside the aluminum post.

40.16

Point for the center 1/4 section corner of section 23, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

$$\begin{array}{c} \text{T}23\text{S } \text{R}5\text{E} \\ \text{C } 1/4 \text{ S}23 \\ 1992 \end{array}$$

Raise a mound of stone west of the corner.

60.10

Point for the center N 1/16 section corner of section 23.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

$$\begin{array}{c} \text{C} \\ \text{N } 1/16 \text{ | } \text{S}23 \\ \text{C} \\ 1992 \end{array}$$

Set a steel fence post alongside the aluminum post.

80.04

The 1/4 section corner of sections 14 and 23.

From the 1/4 section corner of sections 23 and 24.

N. $89^{\circ} 56'$ W., on the E-W center line of section 23.

THE SUBDIVISION OF SECTION 23,
T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Over rolling land.

40.81 The center 1/4 section corner of section 23.

60.955 Point for the center W 1/16 section corner of section 23.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

$$C \frac{W \ 1/16}{S23} C$$

1992

Set a steel fence post alongside the aluminum post.

81.10 The 1/4 section corner of sections 22 and 23.

From the N 1/16 section corner of sections 23 and 24.

S. 89° 48' W., on the E-W center line of the NE 1/4 of section 23.

Over rolling land.

40.53 The center N 1/16 section corner of section 23.

From the W 1/16 section corner of sections 23 and 26.

N. 1° 05' W., on the N-S center line of the SW 1/4 of section 23.

Over rolling land.

20.115 Point for the SW 1/16 section corner of section 23, at intersection with the E-W center line of the SW 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

$$SW \ 1/16 \ S23$$

1992

Set a steel fence post alongside the aluminum post.

40.23 The center W 1/16 section corner of section 23.

From the center S 1/16 section corner of section 23.

THE SUBDIVISION OF SECTION 23,
T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

S. $89^{\circ} 58'$ W., on the E-W center line of the SW 1/4 of section 23.

Over rolling land.

20.245 The SW 1/16 section corner of section 23.

40.49 The S 1/16 section corner of sections 22 and 23.

The Subdivision of Section 27,
T. 23 S., R. 5 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 27 and 34.

N. $0^{\circ} 16'$ W., on the N-S center line of section 27.

Over rolling land.

20.195 Point selected for the witness center S 1/16 section corner of section 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

↑
 WC
 C
 S 1/16 | S27
 C
 1992

Set a steel fence post alongside the aluminum post.

20.295 True point for the center S 1/16 section corner of section 27, falls in small wash and unsafe to monument.

40.59 Point for the center 1/4 section corner of section 27, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
 C 1/4 S27
 1992

Raise a mound of stone west of the corner.

81.90 The 1/4 section corner of sections 22 and 27.

THE SUBDIVISION OF SECTION 27,
T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the 1/4 section corner of sections 26 and 27.

N. 89° 07' W., on the E-W center line of section 27.

Over rolling land.

40.52 The center 1/4 section corner of section 27.

60.54 Point for the center W 1/16 section corner of section 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

$$C \frac{W \ 1/16}{S27} C$$

1992

Raise a mound of stone north of the corner.

62.00 Utah State Highway No. 10, bears NE and curves S.

80.56 The 1/4 section corner of sections 27 and 28.

From the W 1/16 section corner of sections 27 and 34.

N. 0° 06' W., on the N-S center line of the SW 1/4 of section 27.

Over rolling land.

4.80 Utah State Highway No. 10, bears SE and curves N.

20.37 Point for the SW 1/16 section corner of section 27, at intersection with the E-W center line of the SW 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

$$SW \ 1/16 \ S27$$

1992

Set a steel fence post alongside the aluminum post.

40.74 The center W 1/16 section corner of section 27.

From the true point for the center S 1/16 section corner of section 27.

THE SUBDIVISION OF SECTION 27,
T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

- N. $89^{\circ} 20'$ W., on the E-W center line of the SW 1/4 of section 27.
Over rolling land.
- 20.08** The SW 1/16 section corner of section 27.
- 22.00** Utah State Highway No. 10, bears SE and curves N.
- 40.16** The S 1/16 section corner of sections 27 and 28.

- From the center W 1/16 section corner of section 27.
N. $0^{\circ} 06'$ W., on the N-S center line of the NW 1/4 of section 27.
Over rolling land.
- 10.00** Utah State Highway No. 10, bears S and NE.
- 41.10** The W 1/16 section corner of sections 22 and 27.

- The Subdivision of Section 29,
T. 23 S., R. 5 E., Salt Lake Meridian, Utah

- From the 1/4 section corner of sections 29 and 32.
N. $0^{\circ} 04'$ W., on the N-S center line of section 29.
Over rolling land.
- 40.40** Point for the center 1/4 section corner of section 29, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
C 1/4 S29
1992
- Set a steel fence post alongside the aluminum post.
- 60.70** Point for the center N 1/16 section corner of section 29, not monumented.
- 81.00** The 1/4 section corner of sections 20 and 29.

THE SUBDIVISION OF SECTION 29,
T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the 1/4 section corner of sections 28 and 29.

N. $89^{\circ} 37'$ W., on the E-W center line of section 29.

Over rolling land.

20.16

Point for the center E 1/16 section corner of section 29.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

$$C \frac{E \ 1/16}{S29} C$$

1992

Raise a mound of stone north of the corner.

40.32

The center 1/4 section corner of section 29.

60.45

Point for the center W 1/16 section corner of section 29, not monumented.

80.58

The 1/4 section corner of sections 29 and 30.

From the center E 1/16 section corner of section 29.

N. $0^{\circ} 07'$ W., on the N-S center line of the NE 1/4 of section 29.

Over rolling land.

20.28

Point for the NE 1/16 section corner of section 29, at intersection with the E-W center line of the NE 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

$$NE \ 1/16 \ S29$$

1992

Set a steel fence post alongside the aluminum post.

40.56

Point for the E 1/16 section corner of sections 20 and 29.

From the N 1/16 section corner of sections 28 and 29.

N. $89^{\circ} 33'$ W., on the E-W center line of the NE 1/4 of section 29.

THE SUBDIVISION OF SECTION 29,
T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Over rolling land.

20.14 The NE 1/16 section corner of section 29.

40.28 Point for the center N 1/16 section corner of section 29.

From the center W 1/16 section corner of section 29.

N. $0^{\circ} 03'$ W., on the N-S center line of the NW 1/4 of section 29.

Over rolling land.

40.64 The W 1/16 section corner of sections 20 and 29.

The Subdivision of Section 30,
T. 23 S., R. 5 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 30 and 31.

N. $0^{\circ} 19'$ W., on the N-S center line of section 30.

Over rolling land.

40.48 Point for the center 1/4 section corner of section 30, at intersection with the E-W center line, falls in deep wash and is unsafe to monument.

40.785 Point selected for the witness corner of the center 1/4 section corner of section 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:



WC
T23S R5E
C 1/4 | S30
1992

Raise a mound of stone west of the corner.

60.70 Point for the center N 1/16 section corner of section 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 30,
T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

C
N 1/16 | S30
C
1992

Raise a mound of stone west of the corner.

80.92 The 1/4 section corner of sections 19 and 30.

From the 1/4 section corner of sections 29 and 30.

N. 89° 50' W., on the E-W center line of section 30.

Over rolling land.

19.88 Point for the center E 1/16 section corner of section 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

C — $\frac{E\ 1/16}{S30}$ — C
1992

Raise a mound of stone north of the corner.

39.76 True point for the center 1/4 section corner of section 30.

52.34 The 1/4 section corner of section 30 only, on the west boundary of the township, hereinbefore described.

From the center E 1/16 section corner of section 30.

N. 0° 11' W., on the N-S center line of the NE 1/4 of section 30.

Over rolling land.

20.28 Point for the NE 1/16 section corner of section 30, at intersection with the E-W center line of the NE 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

NE 1/16 S30
1992

THE SUBDIVISION OF SECTION 30,
T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Raise a mound of stone west of the corner.

40.56

The E 1/16 section corner of sections 19 and 30.

From the N 1/16 section corner of sections 29 and 30.

S. 89° 59' W., on the E-W center line of the NE 1/4 of section 30.

Over rolling land.

19.925

The NE 1/16 section corner of section 30.

39.85

The center N 1/16 section corner of section 30.

N. 89° 50' W., on the E-W center line of the NW 1/4 of section 30.

Over rolling land.

12.71

The N 1/16 section corner of section 30 only, on the west boundary of the township, hereinbefore described.

The Subdivision of Section 31,
T. 23 S., R. 5 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 6 and 31, of the south boundary of the township, hereinbefore described.

N. 0° 14' W., on the N-S center line of section 31.

Over rolling land.

20.66

Point for the center S 1/16 section corner of section 31.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

C
S 1/16 | S31
C
1992

Set a steel fence post alongside the aluminum post.

THE SUBDIVISION OF SECTION 31,
T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS**41.32**

Point for the center 1/4 section corner of section 31, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
C 1/4 S31
1992

Set a steel fence post alongside the aluminum post.

82.64

The 1/4 section corner of sections 30 and 31.

From the 1/4 section corner of sections 31 and 32.

S. 88° 38' W., on the E-W center line of section 31.

Over rolling land.

39.36

The center 1/4 section corner of section 31.

52.50

The 1/4 section corner of section 31 only, on the west boundary of the township, hereinbefore described.

From the S 1/16 section corner of sections 31 and 32.

S. 87° 44' W., on the E-W center line of the SE1/4 of section 31.

Over rolling land.

39.28

The center S 1/16 section corner of section 31.

S. 87° 43' W., on the E-W center line of the SW 1/4 of section 31.

Over rolling land.

12.84

The S 1/16 section corner of section 31 only, on the west boundary of the township, hereinbefore described.

The Subdivision of Section 34,
T. 23 S., R. 5 E., Salt Lake Meridian, Utah

THE SUBDIVISION OF SECTION 34,
T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the 1/4 section corner of sections 3 and 34, on the south boundary of the township, hereinbefore described.

N. 0° 05' W., on the N-S center line of section 34.

Over rolling land.

13.90 East bound on ramp, of Utah Highway No. 10 and I-70.

14.20 East bound lane of I-70, bears NE and SW.

15.015 Point for the center N-S-S 1/256 section corner of section 34.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

CNSS 1/256
S34
1992

Set a steel fence post alongside the aluminum post.

16.22 West bound lane of I-70, bears NE and SW.

17.02 West bound off ramp of I-70 and Utah Highway No. 10.

20.02 Point for the center S 1/16 section corner of section 34.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

C
S1/16 | S34
C
1992

Set a steel fence post alongside the aluminum post.

40.04 Point for the center 1/4 section corner of section 34, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T23S R5E
C 1/4 S34
1992

THE SUBDIVISION OF SECTION 34,
T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

- Set a steel fence post alongside the aluminum post.
- 80.31** The 1/4 section corner of sections 27 and 34.
-
- From the 1/4 section corner of sections 34 and 35.
N. 89° 28' W., on the E-W center line of section 34.
Over rolling land.
- 39.72** The center 1/4 section corner of section 34.
- 49.84** Point for the center E-W 1/64 section corner of section 34.
Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:
- C-E-W 1/64
S34
1992
- Set a steel fence post alongside the aluminum post.
- 50.61** Utah State Highway No. 10, bears N. and S.
- 59.96** Point for the center W 1/16 section corner of section 34.
Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:
- C $\frac{W 1/16}{S34}$ C
1992
- 80.20** The 1/4 section corner of sections 33 and 34.
-
- From the W 1/16 section corner of sections 3 and 34, on the south boundary of the township, hereinbefore described.
N. 0° 01' E., on the N-S center line of the SW 1/4 of section 34.
Over rolling land.
- 1.45** Utah State Highway No. 72, bears W.

THE SUBDIVISION OF SECTION 34,
T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS

- 5.50** East bound off ramp of I-70 and Utah Highway No. 10.
- 8.35** East bound lane of I-70, bears NE and SW.
- 9.75** West bound lane of I-70, bears NE and SW.
- 13.50** West bound on ramp of Utah Highway No. 10 and I-70.
- 20.03** Point for the SW 1/16 section corner of section 34, at intersection with the E-W center line of the SW 1/4, falls in wash and is unsafe to monument.
- 40.06** The center W 1/16 section corner of section 34.
-
- From the center S 1/16 section corner of section 34.
- N. 89° 31' W., on the E-W center line of the SW 1/4 of section 34.
- Over rolling land.
- 10.135** Point for the center E-SW 1/64 section corner of section 34.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:
- C-E-SW 1/64
S34
1992
- Set a steel fence post alongside the aluminum post.
- 15.48** Utah State Highway No. 10, bears NE and SW.
- 20.27** True point for the SW 1/16 section corner of section 34.
- 21.16** Point selected for the witness corner to the SW 1/16 section corner of section 34.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:
- WC
SW 1/16 S34 →
1992
- Raise a mound of stone west of the corner.

THE SUBDIVISION OF SECTION 34,
T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS
40.54

The S 1/16 section corner of sections 33 and 34.

From the center E-SW 1/64 section corner of section 34.

N. 0° 02' W., on the N-S center line of the NE 1/4 of the SW1/4 of section 34.

Over rolling land.

20.03

The center E-W 1/64 section corner of section 34.

From the E-W 1/64 section corner of sections 3 and 34, on the south boundary of the township, hereinbefore described.

N. 0° 02' W., on the N-S center line of the SE 1/4 of the SW 1/4 of section 34.

Over rolling land.

9.10

East bound on ramp of Utah Highway No. 10 and I-70.

11.30

East bound lane of I-70, bears NE and SW.

13.10

West bound lane of I-70, bears NE and SW.

15.015

Point for the center N-SE-SW 1/256 section corner of section 34.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

C-N-SE-SW
1/256
S34
1992

Set a steel fence post alongside the aluminum post.

15.30

West bound off ramp of I-70 and Utah Highway No. 10.

20.02

The center E-SW 1/64 section corner of section 34.

From the center N-S-S 1/256 section corner of section 34.

N. 89° 31' W., on the E - W center line of the NE 1/4, of the SE 1/4, of the SW 1/4 of section 34.

THE SUBDIVISION OF SECTION 34,
T. 23 S., R. 5 E., SALT LAKE MERIDIAN, UTAH

CHAINS
10.14

The center N-SE-SW 1/256 section corner of section 34.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Joseph Dhaenens	Surveying Technician
Gina Yellowhair	Surveying Technician
Casey Toomer	Survey Aid


CERTIFICATE OF SURVEY

I, *Jerry L. Thomas, Cadastral Surveyor*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *22nd day of February, 1991*, I have *dependently resurveyed the south boundary, a portion of the west and north boundaries, a portion of the subdivisional lines and the subdivision of certain sections, in Township 23 South, Range 5 East*,

of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

September 26, 1995

Date



(Cadastral Surveyor)

Date

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of the south boundary, a portion of the west and north boundaries, a portion of the subdivisional lines, and the subdivision of certain sections, Township 23 South, Range 5 East, Salt Lake Meridian, Utah*,

executed by *Jerry L. Thomas, Cadastral Surveyor*

having been critically examined and found correct, are hereby approved.

September 28, 1995

Date



(Chief, Cadastral Surveyor for Utah)