

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF
THE DEPENDENT RESURVEY OF
THE SOUTH BOUNDARY (SECOND STANDARD PARALLEL SOUTH),

A PORTION OF THE EAST BOUNDARY,

A PORTION OF THE WEST BOUNDARY,

THE SUBDIVISIONAL LINES, AND THE

SUBDIVISION OF SECTIONS 12, 13, 28, 30, AND 34,

AND THE McCOOK ALLOTMENT

IN

TOWNSHIP 10 SOUTH, RANGE 23 EAST

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Jerry L. Thomas
Cadastral Surveyor

Under special instructions dated *March 1, 1993*, approved *March 1, 1993*, which provided for the surveys included under Group Number *763*, and assignment instructions dated *August 26, 1994*.

Survey commenced *September 7, 1994*

Survey completed *October 5, 1995*

INDEX DIAGRAM

Township 10 South, Range 23 East

| | | 57 | 45 | | 37 | | 28 | | 21 | | | |
|----|----|----|----|----|----|----|----|----|----|----|----|----|
| | 6 | 57 | 5 | 45 | 4 | 37 | 3 | 28 | 2 | 21 | 1 | |
| 56 | 56 | 55 | 55 | 44 | 45 | 36 | 37 | 27 | 28 | 20 | 20 | |
| | 7 | 55 | 8 | 44 | 9 | 36 | 10 | 27 | 11 | 20 | 12 | 11 |
| 54 | 54 | 53 | 53 | 43 | 43 | 35 | 35 | 26 | 26 | 18 | 19 | 11 |
| | 18 | 53 | 17 | 43 | 16 | 35 | 15 | 26 | 14 | 17 | 13 | |
| 52 | 52 | 51 | 51 | 42 | 42 | 33 | 34 | 25 | 25 | 16 | 16 | |
| | 19 | 51 | 20 | 41 | 21 | 33 | 22 | 25 | 23 | 15 | 24 | |
| 12 | 50 | 49 | 49 | 40 | 41 | 32 | 32 | 24 | 24 | 14 | 15 | |
| 50 | | | | | | | | | | | | |
| 11 | 30 | 48 | 29 | 40 | 28 | 31 | 27 | 23 | 26 | 14 | 25 | |
| 48 | 47 | 46 | 47 | 38 | 39 | 30 | 30 | 22 | 23 | 13 | 13 | |
| | 31 | 46 | 32 | 38 | 33 | 29 | 34 | 22 | 35 | 12 | 36 | |
| 10 | 10 | 9 | 9 | 8 | 8 | 7 | 7 | 6 | 5 | 4 | 3 | 2 |

The Subdivision of Section 12.....Page 57

The Subdivision of Section 13.....Page 59

The Subdivision of Section 28.....Page 62

The Subdivision of Section 30.....Page 64

The Subdivision of Section 34.....Page 66

McCook Allotment No. 278 and No. 31Page 70

TOWNSHIP 10 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

The following field notes describe the dependent resurvey of the south boundary (Second Standard Parallel South), a portion of the east boundary, a portion of the west boundary, the subdivisional lines, and the McCook Allotment, and the subdivision of sections 12, 13, 28, 30, and 34, in Township 10 South, Range 23 East, Salt Lake Meridian, Utah.

History of Surveys

| | <u>Surveyed by</u> | <u>Retr. or Resurveyed by</u> | |
|--|-----------------------------------|------------------------------------|------|
| <u>SOUTH BOUNDARY (Second Standard Parallel South)</u> | | | |
| All | A.R. Talamantes and H.D. Heist | | 1904 |
| Portion | | R.W. Hodges and R.C. Yundt | 1922 |
| <u>EAST BOUNDARY</u> | | | |
| All | A.R. Talamantes and H.D. Heist | | 1904 |
| All | | J.L. Thomas | 1975 |
| <u>WEST BOUNDARY</u> | | | |
| All | A.R. Talamantes and H.D. Heist | | 1904 |
| All | | R.A. Zaninovich | 1991 |
| <u>NORTH BOUNDARY</u> | | | |
| All | D.G. Major | | 1882 |
| All | A.R. Talamantes and H.D. Heist | | 1904 |
| All | | G.E. Reynolds and F.D. Reynolds | 1977 |
| <u>SUBDIVISION</u> | | | |
| All | A.R. Talamantes and H.D. Heist | | 1904 |
| <u>McCOOK Allotment No. 278 No. 31</u> | | | |
| All | A.R. Talamantes and H.D. Heist | | 1905 |

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 763, dated March 1, 1993.

TOWNSHIP 10 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

The directions of lines were determined by hour angle observations of the sun and Polaris, carried forward by sustained angulation. Distances were determined by electronic measurement.

Preliminary to the resurvey the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line notes are given herein.

The geographic position of the southeast corner of section 25 as determined by GPS using U.S.G.S. triangulation stations "JEK 7ET" and "JEK 19ET", and will now also function as a B.L.M. control station, is as follows:

Latitude: 39° 54' 45.83" N. Longitude: 109° 15' 55.18" W.
Elevation: 5069.3'
N.A.D. 1927

The mean magnetic declination as determined from numerous readings throughout the survey is: 13° East.

Dependent Resurvey of the South Boundary
(Second Standard Parallel South),
T. 10 S., R. 23 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed
by A.R. Talamantes and H.D. Heist in 1904

Beginning at the standard corner of Tps. 10 S., Rs. 23 and 24 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above mound of stone, with brass cap marked as described in the official record of the 1975 resurvey of the south boundary of T. 10 S., R. 24 E.

From this corner point

The closing corner of sections 5 and 6, T. 11 S., R. 24 E., bears East, 8.34 chains distance, monumented with a sandstone, 24x12x4 ins., firmly set, projecting 14 ins. above ground, plainly marked CC on S. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, in mound of stone, 4 ft. base to top, with aluminum cap marked:

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY
 (SECOND STANDARD PARALLEL SOUTH),
 T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T10S R24E
S31
 S6 | S5
 CC
 T11S R24E
 1995

Deposit the marked stone alongside the aluminum post.

S. 89° 58' W., along the south boundary of section 36.

Over rough and broken mountainous land.

32.02

The point for the 1/4 section corner of section 6 only, T. 11 S., R. 24 E., is at proportionate distance on the north boundary of section 6, falls on flat surface of a sandstone boulder.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., over a cross (+), in a mound of stone, 4 ft. base to top, with aluminum cap marked:

1/4 S6
 T11S R24E
 1995

Corner is located on top of narrow sandstone spur projecting E.

40.51

The standard 1/4 section corner of section 36 only, monumented with a sandstone 18x10x5 ins., firmly set, projecting 6 ins. above ground, plainly marked SC on N. face and a 1/4 on S. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 1/2 ft. base to top, with aluminum cap marked:

SC
 T10S R23E
1/4 S36
 1994

Deposit the marked stone alongside the aluminum post.

S. 89° 54' W., beginning new measurement.

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY
(SECOND STANDARD PARALLEL SOUTH),
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS**28.96**

Point selected for the witness corner to the closing corner of sections 1 and 6, Tps. 11 S., Rs. 23 and 24 E.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

WC
T10S R23E
S36
S1 | S6
CC
T11S
R23E R24E
1994

29.08

True point for the closing corner of T. 11 S., Rs. 23 and 24 E., monumented with a sandstone, 26x16x5 ins., set in a mound of stone near edge of sandstone ledge, 3 ft. high, where it is unsafe to monument an aluminum post.

from which

A cedar, 6 ins. diam., bears S. 2° W., 42 lks. distance, dimly marked T11S R23E S1 BT.

Reestablishment of the Survey Executed by A.R. Talamantes
and H.D. Heist in 1904, and the Resurvey by
R.W. Hodge and R.C. Yundt in 1922

40.10

The standard corner of sections 35 and 36, monumented with a sandstone, 30x10x4 ins., firmly set in a mound of stone, dimly marked 5 notches on the W. and 1 notch on the E. edges, from which the original bearing trees

A cedar, 14 ins. diam., bears N. 32° 30' E., 62 links distance,
marked SC T10S R23E S36 BT. (Record bearing and distance N. 41° E.,
83 lks.)

A cedar, 6 ins. diam., bears N. 66° 30' W., 83 lks. distance,
marked SC T10S R23E S35 BT. (Record bearing and distance N. 23° W.,
69 lks.)

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY
(SECOND STANDARD PARALLEL SOUTH),
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

SC
T10S R23E
S35 | S36
1994

Deposit the marked stone alongside the aluminum post.

Corner is located on steep W. slope, 12 ft. E. of draw, which drains NW.

N. 89° 59' W., along the south boundary of section 35.

Over rough and broken mountainous land.

29.61 The 1/4 section corner of section 1, T. 11 S., R. 23 E., monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap marked as described in the official record of the 1922 resurvey of the north boundary of T. 11 S., R. 23 E.

40.70 The standard 1/4 section corner of section 35, monumented with a sandstone, 24x10x6 ins., firmly set, projecting 14 ins. above ground, plainly marked 1/4 on S. face and SC on N. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

SC
T10S R23E
1/4 S35
1994

Deposit the marked stone alongside the aluminum post.

S. 89° 59' W., beginning new measurement.

27.45 The closing corner of sections 1 and 2, T. 11 S., R. 23 E., monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap marked as described in the official record of the 1922 resurvey of the north boundary of T. 11 S., R. 23 E.

39.73 The standard corner of sections 34 and 35, monumented with a sandstone 18x12x8 ins., firmly set, projecting 8 ins. above ground, plainly marked 4 notches on the W. and 2 notches on the E. edges, from which the original bearing trees

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY
(SECOND STANDARD PARALLEL SOUTH),
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

A cedar, 14 ins. diam., bears N. 23° W., 30 links distance, marked
T10S R23E S34 BT.

A cedar, 12 ins. diam., bears N. 18° 30' E., 12 links distance, marked
T10S R23E S35 BT.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone to top, with aluminum cap marked:

| |
|-------------------------|
| SC |
| T10S R23E |
| <u>S34</u> <u>S35</u> |
| 1994 |

Deposit the marked stone alongside the aluminum post.

S. 89° 57' W., along the south boundary of section 34.

Over rough and broken mountainous land.

19.53 Point for the E 1/16 section corner of section 34 only; not monumented.

27.86 The 1/4 section corner of section 2 only, T. 11 S., R. 23 E., monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap marked as described in the official record of the 1922 resurvey of the north boundary of T. 11 S., R. 23 E., from which the original bearing trees

A juniper, 14 ins. diam., bears S. 30° E., 2.82 chs. distance,
marked 1/4 S2 BT.

A juniper, 8 ins. diam., bears S. 46° W., 45 lks. distance, marked
1/4 S2 BT.

39.06 The standard 1/4 section corner of section 34 only, monumented with a sandstone, 18x8x6 ins., firmly set, projecting 10 ins. above ground, plainly marked SC on N. face and 1/4 on S. face, from which the original bearing trees

A cedar, 10 ins. diam., bears N. 48° E., 1.00 ch. distance, marked
SC 1/4 S BT.

A cedar, 8 ins. diam., bears N. 42° W., 1.08 chs. distance, marked
SC 1/4 S BT.

At the corner point

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY
(SECOND STANDARD PARALLEL SOUTH),
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

SC
T10S R23E
1/4 S34
1994

Deposit the marked stone alongside the aluminum post.

S. 89° 57' W., beginning new measurement.

29.17 The closing corner of sections 2 and 3, T. 11 S., R. 23 E., monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap marked as described in the official record of the 1922 resurvey of the subdivision of T. 11 S., R. 23 E.

39.96 The standard corner of sections 33 and 34, monumented with a sandstone, 18x10x8 ins., firmly set, projecting 10 ins. above ground, dimly marked SC on N face, and 3 notches on the E. and W. edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

SC
T10S R23E
S33 | S34
1995

Deposit the dimly marked stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of corner

N. 89° 59' W., along the south boundary of section 33.

Over rough and broken mountainous land.

28.99 The 1/4 section corner of section 3 only, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap marked as described in the official record of the 1922 resurvey of the north boundary of T. 11 S., R. 23 E.

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY
(SECOND STANDARD PARALLEL SOUTH),
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS**40.10**

The standard 1/4 section corner of section 33, monumented with a sandstone, 20x18x6 ins., firmly set, projecting 10 ins. above ground, dimly marked 1/4 on S. face, and an old cedar stake buried alongside.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

SC
T10S R23E
1/4 S33
1995

Deposit the dimly marked stone alongside the aluminum post.

S. 89° 58' W., beginning new measurement.

28.95

The closing corner of sections 3 and 4, T. 11 S., R. 23 E., monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap marked as described in the official record of the 1922 resurvey of the subdivision of T. 11 S., R. 23 E.

39.14

Point selected for the witness corner to the standard corner of sections 32 and 33.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

WC
SC
T10S R23E
S32 | S33
1995

Corner is located on point of small spur, projecting N.

39.89

True point for the standard corner of sections 32 and 33, falls on steep and crumbling slope, and is unsafe to monument.

S. 89° 58' W., along the south boundary of section 32.

Over rough and broken mountainous land.

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY
(SECOND STANDARD PARALLEL SOUTH),
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS**29.03**

The 1/4 section corner of section 4 only, T. 11 S., R. 23 E., monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap marked as described in the official record of the 1922 resurvey of the north boundary of T. 11 S., R. 23 E.

39.97

The standard 1/4 section corner of section 32 only, monumented with a sandstone, 24x8x6 ins., firmly set, projecting 10 ins. above ground, plainly marked SC on N. face, and 1/4 on S. face, from which the original bearing trees

A cedar, 7 ins. diam., bears N. 60° E., 76 links distance, marked
SC 1/4 S BT.

A cedar, 8 ins. diam., bears N. 58° W., 23 links distance, marked
SC 1/4 S BT.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

SC
T10S R23E
1/4 S32
1994

Deposit the marked stone alongside the aluminum post.

N. 89° 59' W., beginning new measurement.

29.18

The closing corner of sections 4 and 5, T. 11 S., R. 23 E., monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap marked as described in the official record of the 1922 resurvey of the subdivision of T. 11 S., R. 23 E.

39.90

The standard corner of sections 31 and 32, monumented with a sandstone, 24x12x8 ins., in a mound of stone with a re-bar alongside, dimly marked SC on the N. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

SC
T10S R23E
S31 | S32
1995

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY
 (SECOND STANDARD PARALLEL SOUTH),
 T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposit the dimly marked stone alongside the aluminum post.

S. 89° 44' W., along the south boundary of section 31.

Over rough and broken mountainous land.

29.27 The 1/4 section corner of section 5 only, T. 11 S., R. 23 E., monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap marked as described in the official record of the 1922 resurvey of the north boundary of T. 11 S., R. 23 E.

39.84 The standard 1/4 section corner of section 31, monumented with a sandstone, 18x12x8 ins., firmly set, projecting 8 ins. above ground, dimly marked 1/4 on S. face, from which the original bearing trees

A cedar, 8 ins. diam., bears N. 5° E., 57 links distance, marked
 SC 1/4 S31 BT. (Record, N. 2° E., 45 links)

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 3 1/2 ft. base, to top of aluminum cap marked:

SC
 T10S R23E
1/4 S31
 1995

Deposit the dimly marked stone alongside the aluminum post.

S. 89° 59' W., beginning new measurement.

29.71 The closing corner of sections 5 and 6, T. 11 S., R. 23 E., monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap marked as described in the official record of the 1922 resurvey of the subdivision of T. 11 S., R. 23 E.

40.00 The standard township corner of Tps. 10 S., Rs. 22 and 23 E., monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with aluminum cap marked as described in the official record of the 1991 resurvey of the south boundary of T. 10 S., R. 22 E.

Dependent Resurvey of a Portion of the East Boundary,
 T. 10 S., R. 23 E., Salt Lake Meridian, Utah

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Reestablishment of the Survey Executed by
A.R. Talamantes and H.D. Heist in 1904,
and the Resurvey by J.L. Thomas in 1975

From the corner of sections 7, 12, 13, and 18, on the east boundary of the township, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap marked as described in the official record of the 1975 resurvey of the west boundary of T. 10 S., R. 24 E.

N. 0° 15' E., between sections 7 and 12, east boundary.

Over rough and broken mountainous land.

20.16 Point for the S 1/16 section corner of sections 7 and 12.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

S 1/16
S12 | S7
1995

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of corner

40.32 The 1/4 section corner of sections 7 and 12, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap marked as described in the official record of the 1975 resurvey of the west boundary of T. 10 S., R. 24 E.

Dependent Resurvey of a Portion of the West Boundary,
T. 10 S., R. 23 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
A.R. Talamantes and H.D. Heist in 1904,
and the Resurvey by R.A. Zaninovich in 1991

From the 1/4 section corner of sections 25 and 30, on the west boundary of the township, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with aluminum cap marked as described in the official record of the 1991 resurvey of the east boundary of T. 10 S., R. 22 E..

N. 0° 11' E., between sections 25 and 30.

Over rough and broken mountainous land.

19.95 Point for the N 1/16 section corner of sections 25 and 30.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

N 1/16
S25 | S30
1995

- 39.90** The corner of sections 19, 24, 25, and 30, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with aluminum cap marked as described in the official record of the 1991 resurvey of the east boundary of T. 10 S., R. 22 E.

Dependent Resurvey of the Subdivisional Lines,
T. 10 S., R. 23 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
A.R. Talamantes and H.D. Heist in 1904

From the standard corner of sections 35 and 36, on the south boundary of the township, heretofore described.

N. 0° 27' E., between sections 35 and 36.

Over rough and broken mountainous land.

- 40.00** The 1/4 section corner of sections 35 and 36, monumented with a sandstone, 26x8x6 ins., firmly set, projecting 20 ins. above ground, with old cedar stake alongside and dimly marked 1/4 on the W. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

T10S R23E
1/4
S35 | S36
1995

Deposit the dimly marked stone alongside the aluminum post.

Corner is located near top of spur, and on a north slope.

N. 0° 03' W., beginning new measurement.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS
40.00

The corner of sections 25, 26, 35, and 36, on a sandstone ledge, marked by a cross (X) with 1 groove on S. and 1 groove on the E., and a mound of stone W. of the cross.

At the corner point

Set a rebar, 12 ins. long, 5/8 ins. diam., in a drill hole, 10 ins. deep, with aluminum cap marked:

| | |
|-----------|-----|
| T10S R23E | |
| S26 | S25 |
| S35 | S36 |
| 1994 | |

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of corner

Corner is located near top of tall pinnacle.

From the corner of sections 25, 30, 31, and 36, on the east boundary of the township, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap marked as described in the official record of the 1975 resurvey of the west boundary of T. 10 S., R. 24 E.

This corner will now function as a B.L.M. control station, hereinbefore described.

S. 89° 58' W., between sections 25 and 36.

Over rough and broken mountainous land.

40.38

The 1/4 section corner of sections 25 and 36, monumented with a sandstone, 30x8x8 ins., firmly set, projecting 20 ins. above ground, plainly marked 1/4 on the N. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

| | |
|-----------|-----|
| T10S R23E | |
| 1/4 | S25 |
| | S36 |
| 1995 | |

Deposit the marked stone alongside the aluminum post.

S. 89° 50' W., beginning new measurement.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS
39.89

The corner of sections 25, 26, 35, and 36.

N. 0° 06' E., between sections 25 and 26.

Over rough and broken mountainous land.

40.21

The 1/4 section corner of sections 25 and 26, monumented with a sandstone, 18x15x4 ins., firmly set, projecting 8 ins. above ground, plainly marked 1/4 on the W. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone to top, with aluminum cap marked:

| | |
|-----------|-----|
| T10S R23E | |
| 1/4 | |
| S26 | S25 |
| 1994 | |

Deposit the marked stone alongside the aluminum post.

N. 0° 04' W., beginning new measurement.

39.83

The corner of sections 23, 24, 25, and 26, monumented with a sandstone, 24x10x5 ins., firmly set, projecting 14 ins. above ground, plainly marked 2 notches on the S. and 1 notch on the E. edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

| | |
|-----------|-----|
| T10S R23E | |
| S23 | S24 |
| S26 | S25 |
| 1994 | |

Deposit the marked stone alongside the aluminum post.

From the corner of sections 19, 24, 25, and 30, on the east boundary of the township, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap marked as described in the official record of the 1975 resurvey of the west boundary of T. 10 S., R. 24 E.

S. 89° 38' W., between sections 24 and 25.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Over rough and broken mountainous land.

40.10 Point for the 1/4 section corner of sections 24 and 25, at proportionate distance, falls near edge of small ledge and cannot be monumented; there is no remaining evidence of the original corner.

At the true point, I mark a cross (X).

40.16 Point selected for the witness 1/4 section corner of sections 24 and 25.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

WC
T10S R23E
1/4 S24
S25
1995

Corner is located on steep west slope and near top of high ridge.

80.20 The corner of sections 23, 24, 25, and 26.

N. 0° 05' W., between sections 23 and 24.

Over rolling bench land.

39.94 The 1/4 section corner of sections 23 and 24, monumented with a sandstone, 16x10x4 ins., firmly set, projecting 10 ins. above ground. Markings have flaked off.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T10S R23E
1/4
S23 | S24
1994

Deposit the unmarked stone alongside the aluminum post.

N. 0° 51' E., beginning new measurement.

36.00 White River, 2 chs. wide, flows W.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS**40.02**

Point for the corner of sections 13, 14, 23, and 24, at proportionate distance; there is no remaining evidence of the original corner

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

| | |
|------------|------------|
| T10S | R23E |
| <u>S14</u> | <u>S13</u> |
| S23 | S24 |
| 1995 | |

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of the corner

From the corner of sections 13, 18, 19, and 24, on the east boundary of the township, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap marked as described in the official record of the 1975 resurvey of the west boundary of T. 10 S., R. 24 E.

N. 89° 56' W., between sections 13 and 24.

Over rough and broken mountainous land.

39.81

The 1/4 section corner of sections 13 and 24, monumented with a sandstone, 24x8x4 ins., firmly set, projecting 18 ins. above ground, plainly marked 1/4 on the N. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

| | | |
|------|------------|------|
| | T10S | R23E |
| 1/4 | <u>S13</u> | |
| | S24 | |
| 1994 | | |

Deposit the marked stone alongside the aluminum post.

N. 89° 41' W., beginning new measurement.

19.72

Point for the W 1/16 section corner of sections 13 and 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

| | |
|--------|------------|
| | <u>S13</u> |
| W 1/16 | S24 |
| 1995 | |

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a steel fence post, 6 ft. long, alongside the aluminum post.

28.00 White River, 2 chs. wide, flows SW.

39.44 The corner of sections 13, 14, 23, and 24.

N. 0° 37' W., between sections 13 and 14.

Along river bottom land.

20.005 Point for the S 1/16 section corner of sections 13 and 14, falls in bottom of deep ravine, and is unsafe to monument.

21.755 Point selected for the witness corner to the S 1/16 section corner of sections 13 and 14.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 2 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

WC
S 1/16
S14 | S13
1995

40.01 True point for the 1/4 section corner of sections 13 and 14, at proportionate distance.

41.52 The witness 1/4 section corner of sections 13 and 14, monumented with a sandstone, 16x14x4 ins., firmly set, projecting 12 ins. above ground and plainly marked WC 1/4 on the W. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

WC
T10S R23E
1/4
S14 | S13
1995

Deposit the marked stone alongside the aluminum post.

Corner is located on top of long spur, projecting E.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0° 20' E., beginning new measurement.

18.61 Point for the N 1/16 section corner of sections 13 and 14, falls on steep S. slope, and is unsafe to monument.

19.15 Point selected for the witness N 1/16 section corner of sections 13 and 14.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

WC
N 1/16
S14 | S13
1995

38.72 The corner of sections 11, 12, 13, and 14, monumented with a sandstone, 16x8x4 ins., firmly set, projecting 8 ins. above ground, plainly marked 1 notch on the E. edge, and in a mound of stone.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with aluminum cap marked:

T10S R23E
S11 | S12
S14 | S13
1995

Deposit the marked stone alongside the aluminum post.

From the corner of sections 7, 12, 13, and 18, on the east boundary of the township, hereinbefore described.

N. 89° 38' W., between sections 12 and 13.

Over gentle rolling land.

19.925 Point for the E 1/16 section corner of sections 12 and 13.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

E 1/16 S12
 S13
 1995

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS**22.29**

Intersect line 1-2, McCook Allotment, No. 278, No. 31.

35.44

Intersect line 1-4, McCook Allotment, No. 278, No. 31.

39.85

The 1/4 section corner of sections 12 and 13, monumented with a sandstone 16x12x5 ins., firmly set, projecting 6 ins. above ground, plainly marked 1/4 on the N. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

| | |
|-----|------------|
| | T10S R23E |
| 1/4 | <u>S12</u> |
| | S13 |
| | 1995 |

Deposit the marked stone alongside the aluminum post.

N. 89° 41' W., beginning new measurement.

19.90

Point for the W 1/16 section corner of sections 12 and 13.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

| | |
|--------|------------|
| W 1/16 | <u>S12</u> |
| | S13 |
| | 1995 |

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of corner

39.80

The corner of sections 11, 12, 13, and 14.

N. 0° 34' W., between sections 11 and 12.

Over rough and broken mountainous land.

40.24

The 1/4 section corner of sections 11 and 12, monumented with a sandstone, 16x6x6 ins., firmly set, projecting 6 ins. above ground, plainly marked 1/4 on the W. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, in a mound of stone 3 1/2 ft. base to top, with aluminum cap marked:

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T10S R23E
1/4
S11 | S12
1995

Deposit the marked stone alongside the aluminum post.

N. 0° 25' E., beginning new measurement.

39.74 The corner of sections 1, 2, 11, and 12, monumented with a sandstone, 16x7x5 ins., firmly set, projecting 8 ins. above ground, plainly marked 5 notches on the S. and 1 notch on the E. edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a collar of stone to top, with aluminum cap marked:

T10S R23E
S2 | S1
S11 | S12
1995

Deposit the marked stone alongside the aluminum post.

From the corner of sections 1, 6, 7, and 12, on the east boundary of the township, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap marked as described in the official record of the 1975 resurvey of the west boundary of T. 10 S., R. 24 E.

N. 89° 57' W., between sections 1 and 12.

Over rolling and broken mountainous land.

39.97 Point for the 1/4 section corner of sections 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

T10S R23E
1/4 S1
S12
1995

79.94 The corner of sections 1, 2, 11, and 12.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0° 07' W., between sections 1 and 2.

Over rolling land.

40.40

The 1/4 section corner of sections 1 and 2, monumented with a sandstone, 12x6x6 ins., firmly set, projecting 4 ins. above ground, plainly marked 1/4 on the W. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T10S R23E
1/4
S2 | S1
1995

Deposit the marked stone alongside the aluminum post.

From this point, U.S.G.S triangulation station "JEK 7 ET," bears N. 77° 32' W., 31.52 chains distance, an aluminum tablet, set in a rock outcrop, marked JEK 7 ET 1966.

N. 0° 20' E., beginning new measurement.

39.82

The corner of sections 1, 2, 35, and 36, north boundary, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap marked as described in the official record of the 1977 resurvey of the south boundary of T. 9 S., R. 23 E.

From the standard corner of sections 34 and 35, on the south boundary of the township, hereinbefore described.

N. 0° 09' E., between sections 34 and 35.

Over rough and broken mountainous land.

19.985

Point for the S 1/16 section corner of sections 34 and 35.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

S 1/16
S34 | S35
1995

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS
39.97

The 1/4 section corner of sections 34 and 35, monumented with a sandstone, 25x10x5 ins., firmly set, projecting 10 ins. above ground, plainly marked 1/4 on the W. face.

The original bearing trees have died, fallen and rotted.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

| | |
|------|------|
| T10S | R23E |
| 1/4 | |
| S34 | S35 |
| 1995 | |

Deposit the marked stone alongside the aluminum post.

N. 0° 59' E., beginning new measurement.

40.19

The corner of sections 26, 27, 34, and 35, monumented with an unmarked sandstone, 36x10x6 ins., in a mound of stone, with old cedar stake alongside, from which the original bearing trees

A cedar, 7 ins. diam., bears N. 4° W., 1.17 chs. distance,
marked T10S R23E S26 BT. (Record - N. 9° E., 1.26 chs. distance.)

A cedar, 11 ins. diam., bears S. 22° 30' W., 50 lks. distance,
marked T10S R23E S34 BT. (Record - S. 33° W., 42 lks. distance.)

A cedar, 10 ins. diam., bears N. 49° W., 1.26 chs. distance,
marked T10S R23E S27 BT. (Record - N. 28° W., 94 lks. distance.)

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

| | |
|------|------|
| T10S | R23E |
| S27 | S26 |
| S34 | S35 |
| 1995 | |

Deposit the unmarked stone alongside the aluminum post.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the corner of sections 25, 26, 35, and 36.

N. 89° 51' W., between sections 26 and 35.

Over rough and broken mountainous land.

- 39.94** The 1/4 section corner of sections 26 and 35, monumented with a sandstone 24x10x4 ins., firmly set, projecting 15 ins. above ground, plainly marked 1/4 on the N. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

T10S R23E
1/4 S26
S35
1995

Deposit the marked stone alongside the aluminum post.

N. 89° 55' W., beginning new measurement.

- 39.97** The corner of sections 26, 27, 34, and 35.
-

N. 0° 15' E., between sections 26 and 27.

Over rough and broken mountainous land.

- 39.79** Point for the 1/4 section corner of sections 26 and 27, at proportionate distance; there is no remaining evidence of the original corner

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

T10S R23E
1/4
S27 | S26
1995

- 79.58** The corner of sections 22, 23, 26, and 27, monumented with a sandstone, 30x10x6 ins., firmly set, projecting 20 ins. above ground, plainly marked 2 notches on the S. and E. edges.

At the corner point

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

| | |
|-----------|-----|
| T10S R23E | |
| S22 | S23 |
| S27 | S26 |
| 1995 | |

Deposit the marked stone alongside the aluminum post.

From the corner of sections 23, 24, 25, and 26.

S. 89° 47' W., between sections 23 and 26.

Over rolling land.

10.00 White River, 2 chs. wide, flows S.

39.80 Point for the 1/4 section corner of sections 23 and 26, at proportionate distance; there is no remaining evidence of the original corner

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

| | |
|-----------|-----|
| T10S R23E | |
| 1/4 | S23 |
| | S26 |
| 1995 | |

Set a cottonwood post, 6 ft. long, alongside the aluminum post.

41.00 White River, 2 chs. wide, flows N.

79.60 The corner of sections 22, 23, 26, and 27.

N. 0° 31' W., between sections 22 and 23.

Over rolling land.

40.59 The 1/4 section corner of sections 22 and 23, monumented with a sandstone, 18x12x7 ins., firmly set in a mound of stone, dimly marked 1/4 on the W. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T10S R23E
1/4
S22 | S23
1995

Deposit the dimly marked stone alongside the aluminum post.

N. 2° 19' E., beginning new measurement.

13.50 White River, 2 chs. wide, flows W.

40.09 True point for the corner of sections 14, 15, 22, and 23, at proportionate distance, falls in bottom of deep ravine and is unsafe to mon; there is no remaining evidence of the original corner.

From the corner of sections 13, 14, 23, and 24.

N. 89° 42' W., between sections 14 and 23.

Over river bottomland.

39.43 Point for the 1/4 section corner of sections 14 and 23, at proportionate distance; there is no remaining evidence of the original corner

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

1/4 T10S R23E
S14
S23
1995

78.86 True point for the corner of sections 14, 15, 22, and 23.

N. 2° 02' W., between sections 14 and 15.

Over rough and broken mountainous land.

40.09 The 1/4 section corner of sections 14 and 15, monumented with a sandstone, 16x14x3 ins., firmly set, projecting 10 ins. above ground, plainly marked 1/4 on the W. face.

At the corner point

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone to top, with aluminum cap marked:

T10S R23E
1/4
S15 | S14
1994

Deposit the marked stone alongside the aluminum post.

N. 0° 01' E., beginning new measurement.

39.98

The corner of sections 10, 11, 14, and 15, monumented with a sandstone, 14x10x6 ins., firmly set, projecting 8 ins. above mound of stone, dimly marked 2 notches on E. edge.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T10S R23E
S10 | S11
S15 | S14
1995

Deposit the dimly marked stone alongside the aluminum post.

From the corner of sections 11, 12, 13, and 14.

N. 89° 45' W., between sections 11 and 14.

Over rough and broken mountainous land.

40.17

The 1/4 section corner of sections 11 and 14, monumented with a sandstone, 20x8x6 ins., firmly set, projecting 10 ins. above ground, plainly marked 1/4 on the N. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a collar of stone to top, with aluminum cap marked:

T10S R23E
1/4 S11
 S14
 1995

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposit the marked stone alongside the aluminum post.

N. 89° 57' W., beginning new measurement.

39.89 The corner of sections 10, 11, 14, and 15.

N. 0° 03' E., between sections 10 and 11.

Over rolling land.

39.86 The 1/4 section corner of sections 10 and 11, monumented with a sandstone, 16x10x6 ins., firmly set, projecting 6 ins. above ground, plainly marked 1/4 on the W. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 4 1/2 ft. base to top, with aluminum cap marked:

| | |
|------|------|
| T10S | R23E |
| 1/4 | |
| S10 | S11 |
| 1995 | |

Deposit the marked stone alongside the aluminum post.

N. 0° 04' W., beginning new measurement.

39.94 The corner of sections 2, 3, 10, and 11, monumented with a broken sandstone, 24x10x6 ins., with bottom portion remaining firmly in the ground. Upper portion plainly marked 2 notches on the E. and 5 notches on the S. edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

| | |
|------|------|
| T10S | R23E |
| S3 | S2 |
| S10 | S11 |
| 1995 | |

Deposit the broken and marked stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of the corner

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the corner of sections 1, 2, 11, and 12.

N. 89° 58' W., between sections 2 and 11.

Over rolling land.

39.97 Point for the 1/4 section corner of sections 2 and 11, at proportionate distance; there is no remaining evidence of the original corner

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T10S R23E
1/4 $\frac{S2}{S11}$
1995

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of corner

79.94 The corner of sections 2, 3, 10, and 11.

N. 0° 10' E., between sections 2 and 3.

Over rolling land.

40.00 The 1/4 section corner of sections 2 and 3, monumented with a sandstone, 14x8x6 ins., firmly set, projecting 10 ins. above ground, plainly marked 1/4 on the W. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T10S R23E
1/4
S3 | S2
1995

Deposit the marked stone alongside the aluminum post.

N. 0° 10' E., beginning new measurement.

40.26 The corner of sections 2, 3, 34, and 35, on the north boundary of the township, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap marked as described in the official record of the 1977 resurvey of the south boundary of T. 9 S., R. 23 E.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the standard corner of sections 33 and 34, on the south boundary of the township, hereinbefore described.

N. 0° 05' W., between sections 33 and 34.

Over rough and broken mountainous land.

20.00 Point for the S 1/16 section corner of sections 33 and 34.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

S 1/16
S33 | S34
1995

Corner is located on top and at W. point of spur.

40.00 The 1/4 section corner of sections 33 and 34, monumented with a sandstone, 18x10x6 ins., firmly set, projecting 10 ins. above ground, plainly marked 1/4 on the W. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

T10S R23E
1/4
S33 | S34
1995

Deposit the marked stone alongside the aluminum post.

N. 0° 05' E., beginning new measurement.

19.995 Point for the N 1/16 section corner of sections 33 and 34.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

N 1/16
S33 | S34
1995

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS
39.99

The corner of sections 27, 28, 33, and 34, monumented with a sandstone, 28x18x6 ins., firmly set, projecting 20 ins. above ground, dimly marked 1 notch on the S. and 3 notches on the E. edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

| | |
|-----------|-----|
| T10S R23E | |
| S28 | S27 |
| S33 | S34 |
| 1995 | |

Deposit the dimly marked stone alongside the aluminum post.

From the corner of sections 26, 27, 34, and 35.

S. 89° 57' W., between sections 27 and 34.

Over rough and broken mountainous land.

40.34

The 1/4 section corner of sections 27 and 34, monumented with a sandstone, 24x12x10 ins., firmly set, projecting 13 ins. above ground, dimly marked 1/4 on the N. face, from which the original bearing trees

A cedar, 8 ins. diam., bears N. 61° E., 66 lks. distance,
marked 1/4 S 27 BT.

A cedar, 6 ins. diam., bears S. 35° 30' E., 73 lks. distance,
marked 1/4 S34 BT.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

| | |
|-----------|-----|
| T10S R23E | |
| 1/4 | S27 |
| | S34 |
| 1995 | |

Deposit the dimly marked stone alongside the aluminum post.

S. 89° 43' W., beginning new measurement.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

19.725 Point for the W 1/16 section corner of sections 27 and 34, falls on steep slope and is unsafe to monument.

20.305 Point selected for the witness corner to the W 1/16 section corner of sections 27 and 34.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

WC
W 1/16 $\frac{S27}{S34}$
1995

39.45 The corner of sections 27, 28, 33, and 34.

N. 0° 15' W., between sections 27 and 28.

Over rough and broken mountainous land.

39.44 The 1/4 section corner of sections 27 and 28, monumented with a sandstone, 32x10x8 ins., firmly set, projecting 15 ins. above ground, plainly marked 1/4 on W. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

T10S R23E
1/4
S28 | S27
1995

Deposit the marked stone alongside the aluminum post.

N. 0° 01' E., beginning new measurement.

38.00 Point selected for the witness corner of sections 21, 22, 27, and 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

WC
T10S R23E
S21 | S22
S28 | S27
1995

Set a cottonwood post, 6 ft. long, alongside the aluminum post.

38.88 Point for the witness corner of sections 21, 22, 27, and 28, at proportionate distance; there is no remaining evidence of the original corner.

This point is near the rivers edge and would be unsafe to monument.

40.71 True point for the corner of sections 21, 22, 27, and 28, falls in White River, drains W.

From the corner of sections 22, 23, 26, and 27.

S. 89° 59' W., between sections 22 and 27.

Over rough and broken mountainous land.

40.09 The 1/4 section corner of sections 22 and 27, monumented with a sandstone, 22x14x6 ins., firmly set, projecting 12 ins. above ground, dimly marked 1/4 on the N. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

T10S R23E
1/4 $\frac{S22}{S27}$
1995

Deposit the dimly marked stone alongside the aluminum post.

N. 89° 31' W., beginning new measurement.

40.19 True point for the corner of sections 21, 22, 27, and 28.

N. 0° 09' W., between sections 21 and 22.

Over river bottom land.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

40.71

The 1/4 section corner of sections 21 and 22, monumented with a sandstone, 16x8x6 ins., firmly set, projecting 8 ins. above ground, plainly marked 1/4 on the W. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a collar of stone, with aluminum cap marked:

T10S R23E
1/4
S21 | S22
1995

Deposit the marked stone alongside the aluminum post.

N. 0° 03' W., beginning new measurement.

40.46

The corner of sections 15, 16, 21, and 22, monumented with a sandstone, 16x12x5 ins., firmly set, projecting 10 ins. above ground, plainly marked 3 notches on the S. and E. edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone to top, with aluminum cap marked:

T10S R23E
S16 | S15
S21 | S22
1995

Deposit the marked stone alongside the aluminum post.

From true point for the corner of sections 14, 15, 22, and 23.

N. 89° 09' W., between sections 15 and 22.

Over rough and broken mountainous land.

0.25

Point selected for the witness corner of sections 14, 15, 22, and 23.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base, to top of aluminum cap, marked:

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

| | |
|-----------|-----|
| WC | |
| T10S R23E | |
| S15 | S14 |
| S22 | S23 |
| 1995 | |

39.34 True point for the 1/4 section corner of sections 15 and 22, at proportionate distance, falls on steep ledges and cannot be monumented.

57.61 The witness corner to the 1/4 section corner of sections 15 and 22, monumented with a sandstone, 18x12x5 ins., firmly set, projecting 15 ins. above ground, plainly marked WC 1/4 on the N. face.

I marked this corner to function as a witness point.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

| | |
|------------|--|
| WC | |
| T10S R23E | |
| <u>S15</u> | |
| S22 | |
| 1995 | |

Deposit the marked stone alongside the aluminum post.

S. 89° 57' W., beginning new measurement.

24.04 The corner of sections 15, 16, 21, and 22.

N. 0° 22' E., between sections 15 and 16.

Over broken mountainous land.

39.58 The 1/4 section corner of sections 15 and 16, monumented with a sandstone, 16x8x6 ins., firmly set, projecting 10 ins. above ground, plainly marked 1/4 on the W. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T10S R23E
1/4
S16 | S15
1995

Deposit the marked stone alongside the aluminum post.

N. 0° 13' W., beginning new measurement.

- 39.98** The corner of sections 9, 10, 15, and 16, monumented with a sandstone, 16x10x8 ins., firmly set, projecting 12 ins. above ground, plainly marked 4 notches on the S. and 3 notches on the E. edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

T10S R23E
S9 | S10
S16 | S15
1995

Deposit the marked stone alongside the aluminum post.

From the corner of sections 10, 11, 14, and 15.

N. 89° 28' W., between sections 10 and 15.

Over rolling mountainous land.

- 39.92** The 1/4 section corner of sections 10 and 15, monumented with a sandstone 24x8x6 ins., firmly set, projecting 12 ins. above ground, plainly marked 1/4 on the N. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a collar of stone to top, with aluminum cap marked:

T10S R23E
1/4 S10
S15
1995

Deposit the marked stone alongside the aluminum post.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

WEST, beginning new measurement.

40.19 The corner of sections 9, 10, 15, and 16.

N. 0° 04' E., between sections 9 and 10.

Over rolling and broken bench land.

39.79 The 1/4 section corner of sections 9 and 10, monumented with a sandstone, 16x10x6 ins., firmly set, projecting 10 ins. above ground, plainly marked 1/4 on the W. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., on solid bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

| | |
|------|------|
| T10S | R23E |
| | 1/4 |
| S9 | S10 |
| | 1995 |

Deposit the marked stone alongside the aluminum post.

N. 0° 02' E., beginning new measurement.

39.79 The corner of sections 3, 4, 9, and 10, monumented with a sandstone, 16x8x6 ins., firmly set, projecting 12 ins. above ground, plainly marked 5 notches on the S. and 3 notches on the E. edge.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

| | |
|------|------|
| T10S | R23E |
| S4 | S3 |
| S9 | S10 |
| | 1995 |

Deposit the marked stone alongside the aluminum post.

From the corner of sections 2, 3, 10, and 11.

N. 89° 53' W., between sections 3 and 10.

Over rolling bench land.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS**40.02**

The 1/4 section corner of sections 3 and 10, monumented with a sandstone, 20x8x6 ins., firmly set, projecting 16 ins. above ground, plainly marked 1/4 on W. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a collar of stone to top, with aluminum cap marked:

T10S R23E
1/4 S3
S10
1995

Deposit the marked stone alongside the aluminum post.

N. 89° 53' W., beginning new measurement.

40.00

The corner of sections 3, 4, 9, and 10.

N. 0° 12' E., between sections 3 and 4.

Over rolling bench land.

40.21

The 1/4 section corner of sections 3 and 4, monumented with a sandstone 16x8x6 ins., firmly set, projecting 10 ins. above ground, plainly marked 1/4 on the W. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone to top, with aluminum cap marked:

T10S R23E
1/4
S4 | S3
1995

Deposit the marked stone alongside the aluminum post.

N. 0° 01' W., beginning new measurement.

39.96

The corner of sections 3, 4, 33, and 34, on the north boundary of the township, firmly set, projecting 6 ins. above ground, with brass cap marked as described in the official record of the 1977 resurvey of the south boundary of T. 9 S., R. 23 E.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the true point for the standard corner of sections 32 and 33, on the south boundary of the township, hereinbefore described.

N. $0^{\circ} 13' W.$, between sections 32 and 33.

Over rough and broken mountainous land.

40.06

The $1/4$ section corner of sections 32 and 33, monumented with a sandstone, $20 \times 12 \times 8$ ins., firmly set, projecting 12 ins. above ground, plainly marked $1/4$ on the W. face, from which the original bearing trees

A cedar, 7 ins. diam., bears S. $14^{\circ} 30' E.$, 13 links distance,
marked $1/4$ S33 BT.

A cedar, 10 ins. diam., bears N. $65^{\circ} W.$, 50 links distance,
marked $1/4$ S32 BT.

At the corner point

Set an aluminum post, 30 ins. long, $2 \frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

T10S R23E
1/4
S32 | S33
1995

Deposit the marked stone alongside the aluminum post.

N. $0^{\circ} 05' W.$, beginning new measurement.

39.95

The corner of sections 28, 29, 32, and 33, monumented with a sandstone, $18 \times 15 \times 5$ ins., firmly set, projecting 14 ins. above ground, plainly marked 1 notch on the S. and 5 notches on the E. edges, from which the original bearing trees

A cedar, 12 ins. diam., bears N. $23^{\circ} E.$, 32 links distance,
marked T10S R23E S28 BT. (Record 53 links distance.)

A cedar, 10 ins. diam., bears S. $9^{\circ} 30' E.$, 24 links distance,
marked T10S R23E S33 BT. (Record 25 links distance.)

A cedar, 14 ins. diam., bears S. $82^{\circ} W.$, 52 links distance,
marked T10S R23E S32 BT. (Record 29 links distance.)

A cedar, 8 ins. diam., bears N. $59^{\circ} W.$, 27 links distance,
marked T10S R23E S29 BT. (Record 24 links distance.)

At the corner point

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

| | |
|------------|------------|
| T10S | R23E |
| <u>S29</u> | <u>S28</u> |
| S32 | S33 |
| 1995 | |

Deposit the marked stone alongside the aluminum post.

From the corner of sections 27, 28, 33, and 34.

N. 89° 58' W., between sections 28 and 33.

Over rough and broken mountainous land.

40.07 The 1/4 section corner of sections 28 and 33, monumented with a sandstone, 24x10x4 ins., firmly set, projecting 14 ins. above ground, plainly marked 1/4 on the N. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a collar of stone to top, with aluminum cap marked:

| | |
|------|------------|
| T10S | R23E |
| 1/4 | <u>S28</u> |
| | S33 |
| 1995 | |

Deposit the marked stone alongside the aluminum post.

S. 89° 59' W., beginning new measurement.

20.055 Point for the W 1/16 section corner of sections 28 and 33.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

| | |
|--------|------------|
| W 1/16 | <u>S28</u> |
| | S33 |
| 1995 | |

40.11 The corner of sections 28, 29, 32, and 33.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0° 05' W., between sections 28 and 29.

Over rough and broken mountainous land.

19.935 Point for the S 1/16 section corner of sections 28 and 29.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 2 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

| | |
|--------|-----|
| S 1/16 | |
| S29 | S28 |
| 1995 | |

Corner is located on very steep NE. slope.

39.87 Point for the 1/4 section corner of sections 28 and 29, at proportionate distance; there is no remaining evidence of the original corner

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

| | |
|-----------|-----|
| T10S R23E | |
| 1/4 | |
| S29 | S28 |
| 1995 | |

Corner is located on N. slope and 40 links S. from bottom of ravine, which drains E.

79.74 The corner of sections 20, 21, 28, and 29, monumented with a broken sandstone, bottom portion firmly set, with old cedar stake alongside.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. in diam., 24 ins. in the ground, with aluminum cap marked:

| | |
|----------|-----|
| T10S R23 | |
| S20 | S21 |
| S29 | S28 |
| 1995 | |

Deposit broken portion of buried sandstone alongside aluminum post.

From true point for the corner of sections 21, 22, 27, and 28.

S. 89° 26' W., between sections 21 and 28.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Along river bottom.

19.00 White River, 2 chs. wide, flows NW.

40.16 The 1/4 section corner of sections 21 and 28, monumented with a mound of stone, and used by local surveyors, is accepted as the best available evidence of the true corner position.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

T10S R23E
1/4 ~~S21~~
S28
1995

N. 89° 59' W., beginning new measurement.

39.97 The corner of sections 20, 21, 28, and 29.

N. 0° 08' E., between sections 20 and 21.

Over rough and broken mountainous land.

40.42 Point for the 1/4 section corner of sections 20 and 21, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

T10S R23E
1/4
S20 | S21
1995

64.00 White River, 2 chs. wide, flows W.

80.84 The corner of sections 16, 17, 20, and 21, monumented with a sandstone, 16x8x6 ins., firmly set, projecting 10 ins. above ground, plainly marked 4 notches on the E. and 3 notches on the S. edges.

At the corner point

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

| | |
|-----------|-----|
| T10S R23E | |
| S17 | S16 |
| S20 | S21 |
| 1995 | |

Deposit the marked stone alongside the aluminum post.

From the corner of sections 15, 16, 21, and 22.

N. 89° 53' W., between sections 16 and 21.

Over rough and broken mountainous land.

- 40.73** The 1/4 section corner of sections 16 and 21, monumented with a sandstone, 12x10x6 ins., firmly set, projecting 8 ins. above ground, plainly marked 1/4 on the N. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

| | |
|------------|-----|
| T10S R23E | |
| <u>S16</u> | |
| 1/4 | S21 |
| 1995 | |

Deposit the marked stone alongside the aluminum post.

S. 88° 49' W., beginning new measurement.

- 39.04** The corner of sections 16, 17, 20, and 21.
-

N. 0° 01' E., between sections 16 and 17.

Over rough and broken mountainous land.

- 40.20** The 1/4 section corner of sections 16 and 17, monumented with a sandstone, 17x6x5 ins., firmly set, projecting 12 ins. above ground, plainly marked 1/4 on the W. face.

At the corner point

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone to top, with aluminum cap marked:

T10S R23E
1/4
S17 | S16
1995

Deposit the marked stone alongside the aluminum post.

N. 0° 02' W., beginning new measurement.

40.06

The corner of sections 8, 9, 16, and 17, monumented with a sandstone, 16x10x6 ins., firmly set, projecting 10 ins. above ground, plainly marked 4 notches on the S. and E. edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone to top, with aluminum cap marked:

T10S R23E
S8 | S9
S17 | S16
1995

Deposit the marked stone alongside the aluminum post.

From the corner of sections 9, 10, 15, and 16.

S. 89° 59' W., between sections 9 and 16.

Over rough and broken bench land.

39.93

Point for the 1/4 section corner of sections 9 and 16, at proportionate distance; there is no remaining evidence of the original corner

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T10S R23E
1/4 S9
S16
1995

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of corner

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS
79.86

The corner of sections 8, 9, 16, and 17.

N. 0° 14' E., between sections 8 and 9.

Over broken bench land.

40.02

The 1/4 section corner of sections 8 and 9, monumented with a sandstone, 16x8x6 ins., set in a mound of stone, dimly marked 1/4 on the W. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., on solid bedrock, in a mound of stone, 4 1/2 ft. base to top, with aluminum cap marked:

| | |
|------|------|
| T10S | R23E |
| | 1/4 |
| S8 | S9 |
| | 1995 |

Deposit the dimly marked sandstone alongside the aluminum post.

N. 0° 22' W., beginning new measurement.

39.72

The corner of sections 4, 5, 8, and 9, monumented with a sandstone, 16x8x5 ins., firmly set, projecting 12 ins. above ground, plainly marked 5 notches on the S. and 4 notches on the E. edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone to top, with aluminum cap marked:

| | |
|------|------|
| T10S | R23E |
| S5 | S4 |
| S8 | S9 |
| | 1995 |

Deposit the marked stone alongside the aluminum post.

From the corner of sections 3, 4, 9, and 10.

S. 89° 56' W., between sections 4 and 9.

Over rolling bench land.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS**40.14**

The 1/4 section corner of sections 4 and 9, monumented with a sandstone, 16x6x6 ins., firmly set, projecting 12 ins. above ground, plainly marked 1/4 on the N. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

| | | |
|-----|-----------|------|
| | T10S | R23E |
| 1/4 | <u>S4</u> | |
| | S9 | |
| | 1995 | |

Deposit the marked stone alongside the aluminum post.

N. 89° 45' W., beginning new measurement.

39.87

The corner of sections 4, 5, 8, and 9.

N. 0° 04' E., between sections 4 and 5.

Over rolling bench land.

39.97

The 1/4 section corner of sections 4 and 5, monumented with a sandstone, 16x4x3 ins., firmly set, projecting 10 ins. above ground, plainly marked 1/4 on the W. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

| | | |
|--|------|------|
| | T10S | R23E |
| | 1/4 | |
| | S5 | S4 |
| | 1995 | |

Deposit the marked stone alongside the aluminum post.

N. 0° 07' E., beginning new measurement.

40.17

The corner of sections 4, 5, 32, and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap marked as described in the official record of the 1977 resurvey of the south boundary of T. 9 S., R. 23 E.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the standard corner of sections 31 and 32, on the south boundary of the township, hereinbefore described.

N. 0° 44' W., between sections 31 and 32.

Over rough and broken mountainous land.

39.44

The 1/4 section corner of sections 31 and 32, monumented with a sandstone, 20x10x8 ins., firmly set, projecting 10 ins. above ground, plainly marked 1/4 on the W. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

| | |
|-----------|-----|
| T10S R23E | |
| 1/4 | |
| S31 | S32 |
| 1995 | |

Deposit the marked stone alongside the aluminum post.

Corner is located on steep N. slope, approximately 1.00 chain below spur top, which slopes E.

N. 0° 29' W., beginning new measurement.

40.09

The corner of sections 29, 30, 31, and 32, monumented with a sandstone, 18x10x6 ins., firmly set, projecting 10 ins. above ground, plainly marked 1 notch on the S. and 5 notches on the E. edge.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

| | |
|------------|------------|
| T10S R23E | |
| <u>S30</u> | <u>S29</u> |
| S31 | S32 |
| 1995 | |

Deposit the marked stone alongside the aluminum post.

Corner is located 75 links S. of wash, with wash draining into Saddletree Draw.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the corner of sections 28, 29, 32, and 33.

S. 89° 31' W., between sections 29 and 32.

Over rough and broken mountainous land.

40.12

The 1/4 section corner of sections 29 and 32, monumented with a sandstone, 24x10x4 ins., firmly set, projecting 16 ins. above ground, dimly marked 1/4 on the W. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T10S R23E
1/4 $\frac{S29}{S32}$
1995

Deposit the dimly marked stone alongside the aluminum post.

Corner is located 3.00 chains E. of main wash in the bottom of Saddletree Draw.

S. 89° 46' W., beginning new measurement.

40.36

The corner of sections 29, 30, 31, and 32.

S. 89° 22' W., between sections 30 and 31.

Over rough and broken mountainous land.

39.90

The 1/4 section corner of sections 30 and 31, monumented with a sandstone, 24x12x6 ins., firmly set, projecting 18 ins. above ground, plainly marked 1/4 on the N. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

T10S R23E
1/4 $\frac{S30}{S31}$
1995

Deposit the marked stone alongside the aluminum post.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 89° 03' W., beginning new measurement.

39.23

The corner of sections 25, 30, 31, and 36, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with aluminum cap marked as described in the official record of the 1991 resurvey of the E. bdy. of T. 10 S., R. 22 E.

From the corner of sections 29, 30, 31, and 32.

North, between sections 29 and 30.

Over rough and broken mountainous land.

40.15

The 1/4 section corner of sections 29 and 30, monumented with a sandstone, 18x14x4 ins., firmly set, projecting 8 ins. above ground, dimly marked 1/4 on the W. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

T10S R23E
1/4
S30 | S29
1995

Deposit the marked stone alongside the aluminum post.

N. 0° 07' E., beginning new measurement.

20.025

Point for the N 1/16 section corner of sections 29 and 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., on solid bedrock, in a mound of stone, 4 1/2 ft. base to top, with aluminum cap marked:

N 1/16
S30 | S29
1994

40.05

The corner of sections 19, 20, 29, and 30, monumented with a sandstone, 16x12x4 ins., firmly set, projecting 10 ins. above ground, plainly marked 2 notches on the S. and 5 notches on the E. edges.

At the corner point

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

| | |
|-----------|-----|
| T10S R23E | |
| S19 | S20 |
| S30 | S29 |
| 1995 | |

Deposit the marked stone alongside the aluminum post.

From the corner of sections 20, 21, 28, and 29.

S. 89° 58' W., between sections 20 and 29.

Over rough and broken mountainous land.

40.21

The 1/4 section corner of sections 20 and 29, monumented with a sandstone, 16x12x6 ins., firmly set, projecting 10 ins. above ground, plainly marked 1/4 on the N. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

| | |
|-----------|-----|
| T10S R23E | |
| 1/4 | S20 |
| | S29 |
| 1995 | |

Deposit the marked stone alongside the aluminum post.

S. 89° 59' W., beginning new measurement.

40.06

The corner of sections 19, 20, 29, and 30.

West, between sections 19 and 30.

Over rough and broken mountainous land.

19.865

Point for the E 1/16 section corner of sections 19 and 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

E 1/16 $\frac{S19}{S30}$
1995

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of corner.

- 39.73** The 1/4 section corner of sections 19 and 30, monumented with a sandstone, 16x12x6 ins., firmly set, projecting 10 ins. above ground, plainly marked 1/4 on the N. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T10S R23E
1/4 $\frac{S19}{S30}$
1995

Deposit the marked stone alongside the aluminum post.

S. 89° 53' W., beginning new measurement.

- 19.87** Point for the W 1/16 section corner of sections 19 and 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

W 1/16 $\frac{S19}{S30}$
1995

- 39.58** The corner of sections 19, 24, 25, and 30, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with aluminum cap marked as described in the official record of the 1991 resurvey of the east boundary of T. 10 S., R. 22 E.

From the corner of sections 19, 20, 29, and 30.

N. 0° 10' E., between sections 19 and 20.

Over rough and broken mountainous land.

- 38.67** Point selected for the witness 1/4 section corner of sections 19 and 20.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

WC
T10S R23E
1/4
S19 | S20
1995

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of the corner.

40.17 True point for the 1/4 section corner of sections 19 and 20, at proportionate distance, falls in the White River. There is no remaining evidence of the original corner.

80.34 Point for the corner of sections 17, 18, 19, and 20, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

T10S R23E
S18 | S17
S19 | S20
1995

Corner is located on steep rocky W. slope, and near S. edge of large boulder, 6x6x4 ft. above ground.

From the corner of sections 16, 17, 20, and 21.

N. 89° 55' W., between sections 17 and 20.

Along river bottom land.

39.86 The 1/4 section corner of sections 17 and 20, monumented with a sandstone, 17x9x6 ins., firmly set, projecting 10 ins. above ground, dimly marked 1/4 on the N. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

T10S R23E
1/4 S17
S20
1995

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposit the dimly marked stone alongside the aluminum post.

S. 89° 11' W., beginning new measurement.

40.37 The corner of sections 17, 18, 19, and 20.

S. 89° 31' W., between sections 18 and 19.

Over rough and broken mountainous land.

40.31 The 1/4 section corner of sections 18 and 19, monumented with an unmarked sandstone, 14x10x8 ins., firmly set in a mound of stone, with old cottonwood stake alongside.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

T10S R23E
1/4 $\frac{S18}{S19}$
1995

Deposit the unmarked stone and old cottonwood stake alongside the aluminum post.

N. 89° 30' W., beginning new measurement.

14.70 White River, 2 chains wide, flows NW.

39.21 The corner of sections 13, 18, 19, and 24, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with aluminum cap marked as described in the official record of the 1991 resurvey of the east boundary of T. 10 S., R. 22 E.

From the corner of sections 17, 18, 19, and 20.

N. 0° 16' E., between sections 17 and 18.

Over rough and broken mountainous land.

40.17 True point for the 1/4 section corner of sections 17 and 18, at proportionate distance, falls on face of high ledge, and cannot be monumented.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS**41.17**

Point for the witness 1/4 section corner of sections 17 and 18, at proportionate distance; there is no remaining evidence of the original corner

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 4 1/2 ft. base to top, with aluminum cap marked:

WC
T10S R23E
1/4
S18 | S17
1995

80.34

The corner of sections 7, 8, 17, and 18, monumented with a sandstone, 16x10x5 ins., firmly set, projecting 10 ins. above ground, plainly marked 4 notches on the S. and 5 notches on the E. edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone to top, with aluminum cap marked:

T10S R23E
S7 | S8
S18 | S17
1995

Deposit the marked stone alongside the aluminum post.

From the corner of sections 8, 9, 16, and 17.

S. 89° 42' W., between sections 8 and 17.

Over rolling bench land.

39.83

The 1/4 section corner of sections 8 and 17, monumented with a sandstone, 14x10x6 ins., firmly set, projecting 6 ins. above mound of stone, dimly marked 1/4 on the N. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

T10S R23E
1/4 S8
S17
1995

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposit the dimly marked stone alongside the aluminum post.

S. 89° 41' W., beginning new measurement.

40.00 The corner of sections 7, 8, 17, and 18.

N. 89° 41' W., between sections 7 and 18.

Over rolling bench land.

39.95 The 1/4 section corner of sections 7 and 18, monumented with a sandstone, 16x6x3 ins., firmly set, projecting 10 ins. above ground, plainly marked 1/4 on the N. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone to top, with aluminum cap marked:

T10S R23E
1/4 $\frac{S7}{S18}$
1995

Deposit the marked stone alongside the aluminum post.

S. 89° 24' W., beginning new measurement.

39.86 The corner of sections 7, 12, 13, and 18, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with aluminum cap marked as described in the official record of the 1991 resurvey of the east boundary of T. 10 S., R. 22 E.

From the corner of sections 7, 8, 17, and 18.

N. 0° 04' W., between sections 7 and 8.

Over rolling bench land.

40.02 The 1/4 section corner of sections 7 and 8, monumented with a sandstone, 14x6x4 ins., firmly set, projecting 10 ins. above ground, plainly marked 1/4 on the W. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone to top, with aluminum cap marked:

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T10S R23E
1/4
S7 | S8
1995

Deposit the marked stone alongside the aluminum post.

N. 0° 02' W., beginning new measurement.

- 39.95** The corner of sections 5, 6, 7, and 8, monumented with a sandstone, 16x6x6 ins., firmly set, projecting 10 ins. above ground, plainly marked 5 notches on the S. and E. edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone to top, with aluminum cap marked:

T10S R23E
S6 | S5
S7 | S8
1995

Deposit the marked stone alongside the aluminum post.

From the corner of sections 4, 5, 8, and 9.

S. 89° 48' W., between sections 5 and 8.

Over rolling bench land.

- 39.37** The 1/4 section corner of sections 5 and 8, monumented with a sandstone, 16x5x3 ins., firmly set, projecting 10 ins. above ground, plainly marked 1/4 on the W. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T10S R23E
1/4 S5
S8
1995

Deposit the marked stone alongside the aluminum post.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

S. 89° 54' W., beginning new measurement

40.41

The corner of sections 5, 6, 7, and 8.

S. 89° 57' W., between sections 6 and 7.

Over rolling bench land.

39.93

The 1/4 section corner of sections 6 and 7, monumented with a sandstone, 16x6x3 ins., firmly set, projecting 10 ins. above ground, plainly marked 1/4 on the N. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T10S R23E
1/4 $\frac{S6}{S7}$
1995

Deposit the marked stone alongside the aluminum post.

S. 89° 43' W., beginning new measurement.

39.59

The corner of sections 1, 6, 7, and 12, on the west boundary, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with aluminum cap marked as described in the official record of the 1991 resurvey of the east boundary of T. 10 S., R. 22 E.

From the corner of sections 5, 6, 7, and 8.

N. 0° 02' W., between sections 5 and 6.

Over rolling bench land.

40.04

The 1/4 section corner of sections 5 and 6, monumented with a sandstone, 16x10x6 ins., firmly set, projecting 10 ins. above ground, dimly marked 1/4 on the W. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T10S R23E

1/4

S6 | S5

1995

Deposit the marked stone alongside the aluminum post.

N. 0° 02' W., beginning new measurement.

- 40.28** The corner of sections 5, 6, 31, and 32, on the north boundary of the township, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap marked as described in the official record of the 1977 resurvey of the south boundary of T. 9 S., R. 23 E.
-

The Subdivisional Lines of Section 12,
T. 10 S., R. 23 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 12 and 13.

N. 0° 03' E., on the N - S center line of section 12.

Over rolling and broken bottom land.

- 20.13** Point for the center S 1/16 section corner of section 12.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

C
S 1/16 | S12
C
1995

- 40.26** Point for the center 1/4 section corner of section 12, at intersection with the E - W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

T10S R23E
C 1/4 S12
1995

- 80.15** The 1/4 section corner of sections 1 and 12.
-

THE SUBDIVISIONAL LINES OF SECTION 12,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the 1/4 section corner of sections 7 and 12, on the east boundary of the township, hereinbefore described.

N. 89° 43' W., on the E - W center line of section 12.

Over rolling and broken mountainous land.

19.99 Point for the center E 1/16 section corner of section 12.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., on solid bedrock, in a mound of stone, 4 1/2 ft. base to top, with aluminum cap marked:

C $\frac{E\ 1/16}{S12}$ C
1995

39.98 The center 1/4 section corner of section 12.

80.21 The 1/4 section corner of sections 11 and 12.

From the E 1/16 section corner of sections 12 and 13.

N. 0° 09' E., on the N - S center line of the SE 1/4 of section 12.

Over rolling bottom land.

14.00 White River, 2 chains wide, flows SW.

20.145 Point for the SE 1/16 section corner of section 12, at intersection with the E - W center line of the SE 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

SE 1/16
S12
1995

40.29 The center E 1/16 section corner of section 12.

From the S 1/16 section corner of sections 7 and 12, on the east boundary of the township, hereinbefore described.

N. 89° 40' W., on the E - W center line of the SE 1/4 of section 12.

Over rolling and broken land.

THE SUBDIVISIONAL LINES OF SECTION 12,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS
19.96

The SE 1/16 section corner of section 12.

39.92

The center S 1/16 section corner of section 12.

The Subdivisional Lines of Section 13,
T. 10 S., R. 23 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 13 and 24.

N. 0° 08' E., on the N - S center line of section 13.

Over rolling river bottom land.

19.985

Point for the center S 1/16 section corner of section 13.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

C
S 1/16 | S13
C
1995

39.97

Point for the center 1/4 section corner of section 13, at intersection with the E - W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

T10S R23E
C 1/4 S13
1995

55.00

White River, 2.00 chains wide, flows SW.

55.59

Intersect line 3-4, McCook Allotment, No. 278, No. 31.

60.10

Point for the center N 1/16 section corner of section 13.

Corner point not monumented.

74.17

Intersect line 1-4, McCook Allotment, No. 278, No. 31.

80.23

The 1/4 section corner of sections 12 and 13.

THE SUBDIVISIONAL LINES OF SECTION 13,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From true point for the 1/4 section corner of sections 13 and 18, on the east boundary of the township, from which the witness corner bears S. 0° 15' W., 2.97 chs. dist., and is described in the official record of the 1975 resurvey of the west boundary of T. 10 S., R. 24 E.

N. 89° 37' W., on the E - W center line of section 13.

Over rough and broken mountainous land.

39.75 The center 1/4 section corner of section 13.

48.50 White River, 2.00 chs. wide, flows SW.

59.71 Point for the center W 1/16 section corner of section 13.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

$$\begin{array}{c} \text{C} \text{---} \frac{\text{W } 1/16}{\text{S13}} \text{---} \text{C} \\ 1995 \end{array}$$

79.67 True point for the 1/4 section corner of sections 13 and 14.

From the center W 1/16 section corner of section 13.

N. 0° 13' E., on the N - S center line of the NW 1/4 of section 13.

Over rolling river bottom land.

20.12 Point for the NW 1/16 section corner of section 13, at intersection with the E - W center line of the NW 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

$$\begin{array}{c} \text{NW } 1/16 \\ \text{S13} \\ 1995 \end{array}$$

40.24 The W 1/16 section corner of sections 12 and 13.

From the point for the center N 1/16 section corner of section 13.

N. 89° 39' W., on the E - W center line of the NW 1/4 of section 13.

THE SUBDIVISIONAL LINES OF SECTION 13,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

- Over rough and broken land.
- 3.685** Intersect line 3-4, McCook Allotment, No. 278, No. 31.
- 19.945** The NW 1/16 section corner of section 13.
- 39.89** True point for the N 1/16 section corner of sections 13 and 14.
-
- From the W 1/16 section corner of sections 13 and 24.
- N. 0° 13' W., on the N - S center line of the SW 1/4 of section 13.
- Over river bottom land.
- 19.995** Point for the SW 1/16 section corner of section 13, at intersection with the E - W center line of the SW 1/4.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:
- SW 1/16
S13
1995
- Corner is located in thick patch of tamarisk brush.
- 33.00** White River, 2.00 chains wide, flows S. 10° W.
- 39.99** The center W 1/16 section corner of section 13.
-
- From the center S 1/16 section corner of section 13.
- N. 89° 39' W., on the E - W center line of the SW 1/4 of section 13.
- Over river bottom land.
- 19.84** The SW 1/16 section corner of section 13.
- 25.00** White River, 2.00 chains wide, flows SW.
- 39.68** The S 1/16 section corner of sections 13 and 14.
-

THE SUBDIVISIONAL LINES OF SECTION 28,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

The Subdivisional Lines of Section 28,
T. 10 S., R. 23 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 28 and 33.

N. 0° 09' W., on the N - S center line of section 28.

Over broken mountainous land.

19.82 Point for the center S 1/16 section corner of section 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

C
S 1/16 | S28
C
1995

39.64 Point for the center 1/4 section corner of section 28, at intersection with the E - W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T10S R23E
C 1/4 S28
1995

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of corner.

Corner is located 70 links S. of old trail road, and 60 links N. of Atchees Wash.

79.72 The 1/4 section corner of sections 21 and 28.

From the 1/4 section corner of sections 27 and 28.

N. 89° 41' W., on the E - W center line of section 28.

Over rough and broken mountainous land.

40.03 The center 1/4 section corner of section 28.

60.05 Point for the center W 1/16 section corner of section 28.

THE SUBDIVISIONAL LINES OF SECTION 28,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

C $\frac{W \ 1/16}{S28}$ C
1995

Corner is located on top of flat spur, which projects E. into Atchee Draw, 8.00 chains distance.

80.07 The 1/4 section corner of sections 28 and 29.

From the W 1/16 section corner of sections 28 and 33.

N. 0° 05' W., on the N - S center line of the SW 1/4 of section 28.

Over rough and broken mountainous land.

19.88 Point for the SW 1/16 section corner of section 28, at intersection with the E - W center line of the SW 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 5 ft. base to top, with aluminum cap marked:

SW 1/16
S28
1995

39.76 The center W 1/16 section corner of section 28.

From the center S 1/16 section corner of section 28.

N. 89° 51' W., on the E - W center line of the SW 1/4 of section 28.

Over rough and broken mountainous land.

20.04 The SW 1/16 section corner of section 28.

40.08 The S 1/16 section corner of sections 28 and 29.

The Subdivisional Lines of Section 30,
T. 10 S., R. 23 E., Salt Lake Meridian, Utah

THE SUBDIVISIONAL LINES OF SECTION 30,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the 1/4 section corner of sections 30 and 31.

N. 0° 11' E., on the N - S center line of section 30.

Over rough and broken mountainous land.

40.63 Point for the center 1/4 section corner of section 30, at intersection with the E - W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., on solid bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

T10S R23E
C 1/4 S30
1995

60.64 True point for the center N 1/16 section corner of section 30, falls on steep ledgy slope, and is unsafe to monumented

63.14 Point selected for the witness center N 1/16 section corner of section 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

WC
C
N 1/16 | S30
C
1995

80.65 The 1/4 section corner of sections 19 and 30.

From the 1/4 section corner of sections 29 and 30.

N. 89° 57' W., on the E - W center line of section 30.

Over rough and broken mountainous land.

19.885 Point for the center E 1/16 section corner of section 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

C — E 1/16 — C
S30
1995

THE SUBDIVISIONAL LINES OF SECTION 30,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Corner is located on the E. edge of main drainage.

39.77 The center 1/4 section corner of section 30.

59.615 Point for the center W 1/16 section corner of section 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

C — $\frac{W\ 1/16}{S30}$ — C
1995

79.365 The 1/4 section corner of sections 25 and 30, on the west boundary of the township, hereinbefore described.

From the center E 1/16 section corner of section 30.

N. 0° 09' E., on the N - S center line of the NE 1/4 of section 30.

Over rough and broken mountainous land.

20.02 Point for the NE 1/16 section corner of section 30, at intersection with the E - W center line of the NE 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., on solid bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

NE 1/16
S30
1995

Corner is located on steep E. slope, approximately 4 chains W. of main drainage.

40.04 The E 1/16 section corner of sections 19 and 30.

From the N 1/16 section corner of sections 29 and 30.

N. 89° 59' W., on the E - W center line of the NE 1/4 of section 30.

Over rough and broken mountainous land.

19.875 The NE 1/16 section corner of section 30.

39.75 True point for the center N 1/16 section corner of section 30.

THE SUBDIVISIONAL LINES OF SECTION 30,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the center W 1/16 section corner of section 30.

N. 0° 09' E., on the N - S center line of the NW 1/4 of section 30.

Over rolling bench land.

19.93 Point selected for the witness NW 1/16 section corner of section 30.

Set an aluminum post, 30 ins. long, 8 ins. in the ground to bedrock, in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

WC
NW 1/16 S30
1995

19.98 True point for the NW 1/16 section corner of section 30, at intersection with the E - W center line of the NW 1/4, falls on face of sandstone ledge and cannot be monumented.

39.96 The W 1/16 section corner of sections 19 and 30.

From the center N 1/16 section corner of section 30.

S. 89° 58' W., on the E - W center line of the NW 1/4 of section 30.

Over rolling bench land.

19.86 True point for the NW 1/16 section corner of section 30.

39.59 The N 1/16 section corner of sections 25 and 30, east boundary of the township, hereinbefore described.

The Subdivisional Lines of Section 34,
T. 10 S., R. 23 E., Salt Lake Meridian, Utah

From the standard 1/4 section corner of section 34, on the south boundary of the township, hereinbefore described.

N. 0° 22' W., on the N - S center line of section 34.

Over rough and broken mountainous land.

19.995 Point for the center S 1/16 section corner of section 34.

THE SUBDIVISIONAL LINES OF SECTION 34,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone to top, with aluminum cap marked:

C
S 1/16 | S34
C
1995

39.99 True point for the center 1/4 section corner of section 34, at intersection with the E and W center line, falls on steep slope of high ridge, and is unsafe to monumented.

59.925 Point selected for the witness center N 1/16 section corner of section 34.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

WC
C
N 1/16 | S34
C
1995

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of the corner.

60.075 True point for the center N 1/16 section corner of section 34, falls in middle of cedar tree trunk and cannot be monumented

80.16 The 1/4 section corner of sections 27 and 34.

From the 1/4 section corner of sections 34 and 35.

S. 89° 58' W., on the E - W center line of section 34.

Over rough and broken mountainous land.

19.705 Point for the center E 1/16 section corner of section 34.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

C ——— E 1/16 ——— C
S34
1995

39.24 Point selected for the witness center 1/4 section corner of section 34, falls on solid sandstone surface.

THE SUBDIVISIONAL LINES OF SECTION 34,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a rebar, 12 ins. long, 5/8 ins. diam., in a drill hole, 8 ins. deep, with aluminum cap marked:

WC
T10S R23E
C 1/4 S34
1995

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of corner.

39.41 True point for the center 1/4 section corner of section 34.

59.29 Point for the center W 1/16 section corner of section 34.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

C ——— W 1/16 ——— C
S34
1995

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of corner.

79.17 The 1/4 section corner of sections 33 and 34.

From the center W 1/16 section corner of section 34.

N. 0° 09' W., on the N - S center line of the NW 1/4 of section 34.

Over rough and broken mountainous land.

20.04 Point for the NW 1/16 section corner of section 34, at intersection with the E - W center line of the NW 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 5 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

NW 1/16
S34
1995

40.08 The true point for the W 1/16 section corner of sections 27 and 34.

From the true point for the center N 1/16 section corner of section 34.

S. 89° 50' W., on the E - W center line of the NW 1/4 of section 34.

THE SUBDIVISIONAL LINES OF SECTION 34,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

- Over rough and broken mountainous land.
- 19.80** The NW 1/16 section corner of section 34.
- 39.60** The N 1/16 section corner of sections 33 and 34.
-
- From the center S 1/16 section corner of section 34.
- S. 89° 57' W., on the E - W center line of the SW 1/4 of section 34.
- Over rolling land.
- 39.86** The S 1/16 section corner of sections 33 and 34.
-
- From the point for the E 1/16 section corner of section 34, on the south boundary of the township, hereinbefore described.
- N. 0° 07' W., on the N - S center line of the SE 1/4 of section 34.
- Over rough and broken mountainous land.
- 19.99** Point for the SE 1/16 section corner of section 34, at intersection with the E - W center line of the SE 1/4.
- Set a rebar, 12 ins. long, 5/8 ins. diam., in a drill hole, 8 ins. deep, with aluminum cap marked:
- SE 1/16
S34
1995
- Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of corner
- 39.98** The center E 1/16 section corner of section 34.
-
- From the S 1/16 section corner of sections 34 and 35.
- S. 89° 57' W., on the E - W center line of the SE 1/4 of section 34.
- Over rough and broken mountainous land.
- 19.615** The SE 1/16 section corner of section 34.
- 39.23** The center S 1/16 section corner of section 34.
-

DEPENDENT RESURVEY OF MCCOOK ALLOTMENT No. 278, No. 31,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Dependent Resurvey of McCook Allotment No. 278, No. 31,
T. 10 S., R. 23 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
A.R. Talamantes and H.D. Heist in 1905

From Corner No. 1, monumented with a sandstone, boulder 12x10x10 ft. above ground, marked with a cross (X) for the exact corner point, and WRLM No 3 McC on W side of cross.

No improvements were made on this corner point.

From this corner point, the 1/4 section corner of sections 12 and 13, bears S. 51° 30' W., 13.59 chains distance.

S. 38° 53' E., along line 1 - 2.


4.00 White River, 2.00 chs. wide, flows SW.

11.03 Intersect the line between sections 12 and 13.

14.58 Corner No. 2, monumented with a sandstone, 16x10x4 ins., firmly set, projecting 10 ins. above ground, dimly marked McC Cor 2 on the W. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:



Deposit the marked stone alongside the aluminum post.

S. 35° 48' W., along line 2 - 3, continuing measurement.


39.56 The witness 1/2 mile marker of the McCook Allotment, monumented with a sandstone, 28x12x5 ins., firmly set, projecting 18 ins. above ground, dimly marked 1/2 on the W. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone to top, with aluminum cap marked:

DEPENDENT RESURVEY OF MCCOOK ALLOTMENT No. 278, No. 31,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS



Deposit the dimly marked stone alongside the aluminum post.

S. 36° 39' W., continuing measurement.

39.915 True point for the 1/2 mile marker of the McCook Allotment, at proportionate distance, falls in deep ravine and is unsafe to monument.

44.685 Corner No. 3, McCook Allotment, monumented with a sandstone, 24x12x8 ins., firmly set, projecting 14 ins. above ground, plainly marked McC Cor 3 on W. face.

This corner is in very good condition, well monumented and plainly marked. No other improvements were necessary.

Corner is located near edge of river bank.

N. 38° 56' W., along line 3 - 4, continuing measurement.

45.70 White River, 2.00 chains wide, flows SW.


48.105 Intersect the N-S center line of section 13.

53.925 Intersect the E-W center line of the NW 1/4 of section 13.

59.44 Corner No. 4, McCook Allotment, monumented with a sandstone 16x16x12 ins., firmly set, projecting 10 ins. above ground, plainly marked MCC Cor 4.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:



Deposit the marked stone alongside the aluminum post.

N. 36° 16' E., along line 4 - 1, continuing measurement.

DEPENDENT RESURVEY OF MCCOOK ALLOTMENT No. 278, No. 31,
T. 10 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

- | | |
|---------------|---|
| 71.55 | Intersect the N-S center line of section 13. |
| 79.03 | Intersect the line between sections 12 and 13. |
| 79.975 | Point for the 1 mile marker of the McCook Allotment at proportionate distance, monument not found and point not remonumented. |
| 89.56 | Corner No. 1. |
-

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

| Name | Capacity |
|-----------------|----------------------|
| Steven Oatman | Surveying Technician |
| Brandon Sanchez | Surveying Technician |
| Ryan Snow | Survey Aid |
| Eric Wilbanks | Survey Aid |

CERTIFICATE OF SURVEY

I, *Jerry L. Thomas, Cadastral Surveyor*, **HEREBY CERTIFY** upon honor that, in pursuance of special instructions bearing the date of the *1st day of March, 1993*, I have *dependently resurveyed the south boundary (Second Standard Parallel South), a portion of the east boundary, a portion of the west boundary, the subdivisional lines, and the McCook Allotment, and subdivided sections 12, 13, 28, 30, and 34, in Township 10 South, Range 23 East,*

of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

April 10, 1997

Date

Jerry L. Thomas

(Cadastral Surveyor)

Date

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of the south boundary (Second Standard Parallel South), a portion of the east boundary, a portion of the west boundary, the subdivisional lines, and the McCook Allotment, and the subdivision of sections 12, 13, 28, 30, and 34, Township 10 South, Range 23 East, Salt Lake Meridian, Utah,*

executed by *Jerry L. Thomas, Cadastral Surveyor*

having been critically examined and found correct, are hereby approved.

April 24, 1997

Date

Daniel W. Webb

(Chief Cadastral Surveyor for Utah)