

397

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

## FIELD NOTES

OF  
THE DEPENDENT RESURVEY

OF A PORTION OF THE SOUTH BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES,

AND THE SUBDIVISION OF SECTION 34,

AND RESURVEY OF PORTIONS OF

MINERAL SURVEY NUMBERS 3995, 3996, 3997, 3998, AND 7361,

LOCATED IN SECTIONS 27, 33, AND 34, T. 29 S., R. 24 E.,

AND IN SECTION 27, T. 29 1/2 S., R. 24 E.,

OF THE SALT LAKE MERIDIAN  
IN THE STATE OF UTAH

EXECUTED BY

*Jerry L. Thomas*  
*Cadastral Surveyor*

Under special instructions dated *December 10, 1991*, approved *December 10, 1991*, which provided for the surveys included under Group Number 780, and assignment instructions dated *December 10, 1991*.

Survey commenced *December 13, 1991*

Survey completed *July 14, 1996*

INDEX DIAGRAM

Township 29 South, Range 24 East

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	7 27	26	25
		7	7 6		
31	32	33	6 34	5 35	36
			5 4	3	

The Subdivision of Section 34.....Page 8  
 Mineral Survey No. 3995.....Page 9, 11, 12, 15, 16-20  
 Mineral Survey No. 3996.....Page 13  
 Mineral Survey No. 3997.....Page 12-15  
 Mineral Survey No. 3998.....Page 10

## TOWNSHIP 29 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

The following field notes describe the dependent resurvey of a portion of the south boundary, a portion of the subdivisional lines, and the subdivision of section 34, T. 29 S., R. 24 E., Salt Lake Meridian, Utah. The resurvey of portions of the following mineral surveys have been included for the segregation of public lands from private ownership.

M.S. NumbersNAME

3995	ANACONDA
3995	COPPER KING
3995	DANDY JIM
3995	DURANGO
3995	MINERAL POINT
3995	NEVADA
3995	PACIFIC
3995	TEXAS
3996	PIUTE PLACER
3997	MONO PLACER
3998	UTAH
7361	SMALL FRY No. 4
7361	SMALL FRY No. 5
7361	SMALL FRY No. 19
7361	SMALL FRY No. 20

This survey was commenced by Richard A. Zaninovich, Cadastral Surveyor in 1991, under this same group number, with the resurvey of Piute Placer, Mineral Survey No. 3996. This group project has been reassigned due to a volunteer transfer to the State of Nevada by Mr. Zaninovich and all of his work has been incorporated in this survey.

**History of Surveys**

	Surveyed by	Retr. or Resurveyed by	
<b>SOUTH BOUNDARY</b>			
All	Rathbone and Mason	1915-16	
Portion			Nelson and Terry 1919
<b>EAST BOUNDARY</b>			
All	E. Buettner	1880	
All			Rathbone and Mason 1915-16
<b>WEST BOUNDARY (Colorado Guide Meridian)</b>			
Portion	F. Dickert	1878	
Portion	E. Buettner	1884	
Portion			E. Buettner 1884

## TOWNSHIP 29 SOUTH, RANGE 24 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

All			H.D. Page	1902
All			Rathbone and Mason	
				1915-16

**NORTH BOUNDARY**

All	F. Dickert	1878		
All			E. Buettner	1880
All			Rathbone and Mason	
				1915-16

**SUBDIVISION**

Portion	F. Dickert	1878		
Portion	Rathbone and Mason	1915-16		
Portion			Rathbone and Mason	
				1915-16

**MINERAL SURVEYS**

3995 - 3998	W.A. Wilson	1899		
7361	W.G. Ladd	1981		

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 780, dated December 10, 1991.

The directions of lines were determined by hour angle observations of the sun and Polaris, carried forward by sustained angulation. Distances were determined by electronic measurement.

Note: Directions of lines between controlling mineral monuments are adjusted for increment of curvature with reference to geodetic mean bearing.

Preliminary to the resurvey the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line notes are given herein.

The geographic position of the witness corner of sections 34 and 35, as determined by ties made to U.S.G.S. triangulation station "LA SAL" is as follows:

Latitude: 38° 13' 47.27" N.      Longitude: 109° 15' 14.92" W.  
N.A.D. 1927

The mean magnetic declination, as projected from the U.S. Geological Survey Magnetic Declination Map of 1990, is 12 1/2° E.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 29 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Dependent Resurvey of a Portion of the South Boundary,  
T. 29 S., R. 24 E., Salt Lake Meridian, Utah

Reestablishment of the Survey  
Executed by Rathbone and Mason in 1915  
and Retracement by Nelson and Terry in 1919

Beginning at true point for the corner of sections 34 and 35 only, on the south boundary of the township, which falls in the bottom of a small drainage, not monumented.

N. 89° 59.2' W., along the south boundary of section 34.

Over nearly level land.

**0.300** The witness corner to sections 34 and 35, monumented with an iron post, 2 ins. diameter, firmly set, projecting 6 ins. above ground, and in a collar of stone, with brass cap marked as described in the official record of the survey of the south boundary in 1919.

**9.290** True point for the 1/4 section corner of section 26 only, T. 29 1/2 S., R. 24 E., at proportionate distance, falls in mine tailings pond. There is no remaining evidence of the original corner. It is impracticable to establish a permanent monument at this point; not monumented.

**12.00** Paved road, bears NW and SE.

**12.590** The witness corner to the 1/4 section corner of section 26 only, T. 29 1/2 S., R. 24 E.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 24 ins. in the ground, with aluminum cap marked:

WC  
 \_\_\_\_\_  
 1/4 S26 →  
 T29 1/2S R24E  
 1994

**39.764** The 1/4 section corner of section 34 only, is determined at record bearing and distance from the remains of the original bearing trees

A fallen dead pinon, 10 ins. diameter, bears S. 40° E., 28 links distance, marked 1/4 S3 BT.

A juniper, 12 ins. diameter, bears N. 50° E., 33 links distance, marked 1/4 S34 BT.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 29 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 24 ins. in the ground, with aluminum cap marked:

T29S R24E
<u>1/4 S34</u>
1994

Raise a mound of stone, 3 1/2 base, 1 1/2 ft. high, north of corner.

S. 89° 58.9' W., beginning new measurement.

- 9.476** The closing corner of sections 26 and 27, T. 29 1/2 S., R. 24 E., bears South, 0.045 links distance, monumented with an iron post, 2 ins. diameter, firmly set, projecting 6 ins. above ground, with brass cap marked and witnessed as described in the official record of the retracement of the south boundary in 1919.
- 15.607** Intersect line 1-2, SMALL FRY No. 19 lode, Mineral Survey No. 7361.
- From this point, Corner No. 2, bears S. 19° 11.5' E., 17.044 chains distance, monumented with an aluminum post, set, marked and witnessed as described in the official record of the 1981 survey.
- From this same point, Corner No. 1, bears N. 19° 11.5' W., 0.348 chains distance, established by the Grant Boundary Method. This corner has been destroyed and was not remonumented.
- 17.078** Intersect line 1-4, SMALL FRY No. 19 lode, Mineral Survey No. 7361.
- From this point, the point for Corner No. 1, bears N. 76° 09.5' E., 1.377 chains distance.
- From this same point, Corner No. 4 of SMALL FRY No. 20 lode, bears S. 76° 09.5' W., 1.500 chains distance, monumented with an aluminum post, set, marked and witnessed as described in the official record of the 1981 survey.
- 18.588** Intersect line 3-4, SMALL FRY No. 20 lode, Mineral Survey No. 7361.
- From this point, Corner No. 4, on line 4-1 of SMALL FRY NO. 20 lode, bears S. 11° 39.5' E., 0.366 chains distance.
- From this same point, Corner No. 3, bears N. 11° 39.5' W., 16.833 chains distance, monumented with an aluminum post, set, marked and witnessed as described in the official record of the 1981 survey.
- 31.60** Gravel road, bears NW and SE.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 29 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

CHAINS

40.110

The corner of sections 33 and 34 only, T. 29 S., R. 24 E., an iron post, 2 ins. diameter, firmly set, projecting 6 ins. above ground, with brass cap marked as described in the official record of the retracement of the south boundary in 1919.

From this corner, U.S. Geological Survey triangulation station "LA SAL," bears N. 0° 00.6' W., 42.368 chains distance, a brass tablet, 3 ins. diameter, seated in a solid sandstone surface.

---

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 29 S., R. 24 E., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by  
Rathbone and Mason in 1915

---

From true point for the corner of sections 34 and 35 only, on the south boundary of the township.

N. 0° 01.3' W., between sections 34 and 35.

Over gentle rolling land.

16.50

Gravel road, bears NW and SE.

39.936

The 1/4 section corner of sections 34 and 35, monumented with an iron post, 1 in. diameter, firmly set, projecting 6 ins. above ground, with brass cap marked as described in the official record of the survey of the subdivisional lines in 1915.

---

N. 0° 03.3' W., beginning new measurement.

39.900

The corner of sections 26, 27, 34, and 35, monumented with an iron post, 2 ins. diameter, firmly set, projecting 8 ins. above ground, with brass cap marked as described in the official record of the survey of the subdivisional lines in 1915.

From this point, U.S. Geological Survey triangulation station "LA SAL", bears S. 64° 51.1' W., 88.173 chains distance.

---

From the corner of sections 33 and 34 only.

N. 0° 06.2' W., between sections 33 and 34.

Over gentle rolling land.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 29 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

- 12.014** Intersect line 2-3, Small Fry No. 5 lode, Mineral Survey No. 7361.
- From this point, Corner No. 2, bears N.  $76^{\circ} 08.3'$  E., 3.458 chains distance, monumented with an aluminum post, set, marked and witnessed as described in the official record of the 1981 survey. Also, from Corner No. 2, Corner No. 3 of SMALL FRY 20 lode, same survey, bears N.  $76^{\circ} 07.8'$  E., 15.228 chains distance.
- From this same intersect point, Corner No. 3, bears S.  $76^{\circ} 08.3'$  W., 5.633 chains distance, monumented with an aluminum post, set, marked and witnessed as described in the official record of the 1981 survey.
- 16.00** Dirt road, bears NE and SW.
- 39.906** The 1/4 section corner of sections 33 and 34, monumented with an iron post, 1 in. diameter, firmly set, projecting 10 ins. above ground, with brass cap marked as described in the official record of the survey of the subdivisional lines in 1915, from which the original bearing tree
- A pinon, 14 ins. diameter, bears S.  $13^{\circ} 40'$  E., 70 links distance, marked 1/4 S34 BT. (1915 record: S.  $14^{\circ}$  E., 68 links distance.)
- 
- N.  $0^{\circ} 02.5'$  W., beginning new measurement.
- 39.979** True point for the corner of sections 27, 28, 33, and 34, at proportionate distance, falls in large open pit mine; there is no remaining evidence of the original corner. It is unsafe to monument the section corner at this point, not monumented.
- 
- From the corner of sections 26, 27, 34, and 35.
- N.  $89^{\circ} 49.3'$  W., between sections 27 and 34.
- Over rolling land.
- 25.00** Dirt road, bears N and S.
- 33.190** Intersect line 3-4, Anaconda lode, Mineral Survey No. 3995, hereinafter described.
- 40.005** The 1/4 section corner of sections 27 and 34, monumented with an iron post, 1 inch diameter, firmly set, projecting 6 ins. above ground, with brass cap marked as described in the official record of the survey of the subdivisional lines in 1915.
- 
- S.  $89^{\circ} 53.3'$  W., beginning new measurement.
- 16.234** Intersect line 2-3, Texas lode, Mineral Survey No. 3995, hereinafter described.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 29 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

CHAINS

**22.441** Intersect line 1-4, Nevada lode, Mineral Survey No. 3995, hereinafter described.

**29.734** Intersect line 3-4, Nevada lode, Mineral Survey No. 3995, hereinafter described.

**31.40** Paved road, bears NW and SE.

**39.900** Point for the true point for the corner of sections 27, 28, 33, and 34.

---

From the true point for the corner of sections 27, 28, 33, and 34.

N. 0° 10.7' W., between sections 27 and 28.

Over rolling land.

**6.000** Point selected for the witness corner of sections 27, 28, 33, and 34.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 20 ins. in the ground, and in a collar of stone, with aluminum cap marked:

WC	
T29S	R24E
S28	S27
S33	S34
↓	
1994	

**17.50** Paved road, bears NW and SE.

**39.981** The 1/4 section corner of sections 27 and 28, monumented with an iron post, 1 inch diameter, firmly set, projecting 8 ins. above ground, with brass cap marked as described in the official record of the survey of the subdivisional lines in 1915.

---

From true point for the corner of sections 27, 28, 33, and 34.

N. 89° 58.7' W., between sections 28 and 33.

Over rolling land.

**39.875** The 1/4 section corner of sections 28 and 33, monumented with an iron post, 1 inch diameter, firmly set, projecting 6 ins. above mound of stone, with brass cap marked as described in the official record of the survey of the subdivisional lines in 1915.

---

THE SUBDIVISION OF SECTION 34,  
T. 29 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

CHAINS

The Subdivision of Section 34,  
T. 29 S., R. 24 E., Salt Lake Meridian, Utah

From the 1/4 section corner of section 34 only, on the south boundary of the township.  
N. 0° 13.0' W., on the N-S center line of section 34.

**19.956** Point for the center S 1/16 section corner of section 34; not monumented.

**39.912** Point for the center 1/4 section corner of section 34, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T29S R24E  
C 1/4 S34  
1995

**42.454** Intersect line 3-4, Mono Placer, Mineral Survey No. 3997.

From this point, Corner No. 3, bears S. 48° 59.8' E., 4.822 chains distance, monumented with an aluminum post, hereinafter described.

From this same point, Corner No. 4, bears N. 48° 59.8' W., 16.593 chains distance, monumented with an aluminum post, hereinafter described.

**79.950** The 1/4 section corner of sections 27 and 34.

From the 1/4 section corner of sections 34 and 35.

S. 89° 58.7' W., on the E-W center line of section 34.

**19.948** Point for the center E 1/16 section corner of section 34; not monumented.

**24.081** Intersection line 1-2, Piute Placer, Mineral Survey No. 3996.

From this point, Corner No. 2, bears S. 37° 52.8' E., 13.006 chains distance.

From this same point, Corner No. 1, bears N. 37° 52.8' W., 6.997 chains distance.

**36.983** Intersect line 3-4, Mono Placer, Mineral Survey No. 3997.

From this point, Corner No. 3, bears S. 48° 59.8' E., 0.949 chains distance.

From this same point, Corner No. 4, bears N. 48° 59.8' W., 20.466 chains distance.

THE SUBDIVISION OF SECTION 34,  
T. 29 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

- 39.896** The center 1/4 section corner of section 34.
- 59.910** Point for the center W 1/16 section corner of section 34; not monumented.
- 79.923** The 1/4 section corner of sections 33 and 34.

---

Dependent Resurvey of a Portion of  
Mineral Survey Nos. 3995, 3996, 3997, and 3998,  
T. 29 S., R. 24 E., Salt Lake Meridian, Utah

---

Reestablishment of the Surveys Executed by  
William A. Wilson in 1899

---

Mineral Survey No. 3995

---


ANACONDA LODGE

Beginning at corner No. 3, identical with corner No. 4, Pacific Lode, same survey, marked by two 2x4's nailed together, in a mound of stone, with dim scribe markings, from which the original bearing tree

A cedar, 30 ins. diameter, dimly marked, bears N. 46° W.,  
23 links distance.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:



Deposit the dimly marked 2x4 alongside the aluminum post.

From this same point, the 1/4 section corner of sections 27 and 34, heretofore described bears S. 2° 57.7' E., 7.443 chains distance.

S. 44° 00.3' E., along line 3-4 of Anaconda lode.

- 10.363** Intersect the section line between sections 27 and 34.

DEPENDENT RESURVEY OF A PORTION OF  
MINERAL SURVEY NOS. 3995, 3996, 3997, AND 3998,  
T. 29 S., R. 24 E., SALT LAKE MERIDIAN, UTAH


## CHAINS

21.382

Corner No. 4, monumented with a pine post, 4 ft. long, 6 ins. square, with faint scribe marks. There is no remaining evidence of the original bearing trees.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 14 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:



Deposit the dimly marked post alongside the aluminum post.


---

S. 39° 05.2' W., along line 4-1.

8.794

Corner No. 1, identical with Corner No. 1, Durango lode, Mineral Survey No. 3995, and Corner No. 1, Utah lode, Mineral Survey No. 3998, at proportionate distance based on the Grant Boundary Method; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam. 24 ins. in the ground, with aluminum cap marked:




---

Mineral Survey No. 3998

---

UTAH LODGE

S. 44° 07.5' E., along line 1-2.


7.689

Corner No. 2, at proportionate distance, based on the Grant Boundary Method; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 28 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF  
MINERAL SURVEY NOS. 3995, 3996, 3997, AND 3998,  
T. 29 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

CHAINS




S.  $38^{\circ} 57.8'$  W., along line 2-3.

- 7.932** Corner No. 3, monumented with a pine post, 4 ft. long, 6 ins. square, in a mound of stone, with dim scribe marks. The bearing tree has died and rolled down the slope.

At the corner point


Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 20 ins. in the ground, and in a collar of stone, with aluminum cap marked:



N.  $44^{\circ} 05.8'$  W., along line 3-4.

- 3.370** Corner No. 1, Copper King lode, Mineral Survey No. 3995, at proportionate distance, based on the Grant Boundary Method; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 24 ins. in the ground, with aluminum cap marked:



Mineral Survey No. 3995

COPPER KING LODGE

S.  $39^{\circ} 07.0'$  W., along line 1-2.

DEPENDENT RESURVEY OF A PORTION OF  
 MINERAL SURVEY NOS. 3995, 3996, 3997, AND 3998,  
 T. 29 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

**4.032**

Corner No. 2, identical with Corner No. 1, Dandy Jim lode, at proportionate distance, based on the Grant Boundary Method; there is no remaining evidence of the original corner; not monumented.

---

Mineral Survey No. 3995

---

**DANDY JIM LODE**

S. 39° 03.7' W., along line 1-2.


**4.501**

Corner No. 2, identical with Corner No. 1, Mono Placer lode, Mineral Survey No. 3997, at proportionate distance, based on the Grant Boundary Method; this point falls in mine tailings pond and is unsafe to monument; there is no remaining evidence of the original corner.

**5.251**

Point selected for the witness corner of Corner No. 1, Mono Placer lode, Mineral Survey No. 3997.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 24 ins. in the ground, with aluminum cap marked:




---

Mineral Survey No. 3997

---

**MONO PLACER LODE**

From the true point for Corner No. 1.


S. 69° 09.3' E., along line 1-2.

DEPENDENT RESURVEY OF A PORTION OF  
 MINERAL SURVEY NOS. 3995, 3996, 3997, AND 3998,  
 T. 29 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**  
**10.812**

Corner No. 2, identical with Corner No. 1, Piute Placer lode, Mineral Survey No. 3996, determined at record bearing and distance from the remains of the original bearing tree, a dead, fallen pinon, 20 ins. diameter, decayed, but with the face of the original blaze intact and marked: X BT 1 3996 BT 2 3997; to perpetuate this point (the stump hole of the bearing tree) I set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 24 ins. in the ground, for a reference monument, with aluminum cap marked: RM 1-3996 2-3997 194.6 FT 1994 and an arrow pointing to the corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 24 ins. in the ground, with aluminum cap marked:



Deposit a magnet at base of aluminum post.

From this corner point, the reference monument bears N. 21° 18' E., 2.948 chains distance.

Corner is located in an old tailings pond.

From Corner No. 1, an iron post, 2 1/2 ins. diameter, set in concrete, with brass cap marked: US GOV LOC MON NO 1 JOB 10.M.77 RLS 2764, bears N. 13° 44' W., 19.70 chains distance; the position of this monument disagrees with record ties to several recovered corners throughout this project and is therefore not accepted as a reestablishment of the original U.S. Location Monument.

---

Mineral Survey No. 3996

---

PIUTE PLACER LODGE


From the true point for Corner No. 1, Piute Placer lode.

S. 37° 52.8' E., along line 1-2.

**6.997** Intersect the E-W center line of section 34.

**20.003** Point for Corner No. 2, at proportionate distance, based on the Grant Boundary Method; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 24 ins. in the ground, with aluminum cap marked:



DEPENDENT RESURVEY OF A PORTION OF  
 MINERAL SURVEY NOS. 3995, 3996, 3997, AND 3998,  
 T. 29 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposit a magnet at base of aluminum post.

---

S. 52° 06.5' W., along line 2-3.

**0.60** Center of gravel road, bears NW and SE.

**10.001** Point for corner No. 3, at proportionate distance, based on the Grant Boundary Method, falls in the paved surface of road; there is no remaining evidence of the original corner.

Set a PK nail in the surface of the road.

from which

An aluminum post, 30 ins. long, 2 1/2 ins. set 24 ins. in the ground, for a reference monument, bears N. 25° 36' E., 100 links distance, with aluminum cap marked: RM 3-3996 66 FT 1991 and an arrow pointing to the corner. Deposit a magnet at base of aluminum post.


An aluminum post, 30 ins. long, 2 1/2 ins. set 24 ins. in the ground, for a reference monument, bears N. 64° 24.0' W., 60.6 links distance, with aluminum cap marked: RM 3-3996 40 FT 1991 and an arrow pointing to the corner. Deposit a magnet at base of aluminum post.

---

N. 37° 53.3' W., along line 3-4.

**19.995** Point for Corner No. 4, identical with Corner No. 3 of Mono Placer lode, Mineral Survey No. 3997, at proportionate distance, based on the Grant Boundary method; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 24 ins. in the ground, with aluminum cap marked:



Deposit a magnet at base of aluminum post.

From this corner, the true point for Corner No. 1 of Piute Placer, Mineral Survey No. 3996, identical with Corner No. 2 of Mono Placer, Mineral Survey No. 3997, bears N. 52° 06.2' E., 10.000 chains distance.

---

DEPENDENT RESURVEY OF A PORTION OF  
MINERAL SURVEY NOS. 3995, 3996, 3997, AND 3998,  
T. 29 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Mineral Survey No. 3997

MONO PLACER LODE


N. 48° 59.8' W., along line 3-4.

**0.949** Intersect the E-W center line of section 34.

**4.822** Intersect the N-S center line of section 34.

**21.415** Corner No. 4, at proportionate distance, based on the Grant Boundary Method; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 24 ins. in the ground, with aluminum cap marked:




Deposit a magnet at base of aluminum post.

N. 52° 06.2' E., along line 4-5.

**7.370** Corner No. 5, on line 2-3, Jim Dandy lode, Mineral Survey No. 3995, at proportionate distance, based on the Grant Boundary method; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 24 ins. in the ground, with aluminum cap marked:



Mineral Survey No. 3995

DANDY JIM LODE

N. 43° 28.8' W., along line 2-3.


DEPENDENT RESURVEY OF A PORTION OF  
MINERAL SURVEY NOS. 3995, 3996, 3997, AND 3998,  
T. 29 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Over mine tailings.

- 10.938** Corner No. 3, on line 1-2 of Nevada lode, same survey, at proportionate distance, based on the Grant Boundary Method; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 24 ins. in the ground, with aluminum cap marked:




---

Mineral Survey No. 3995

---


NEVADA LODGE

S. 39° 00.2' W., along line 1-2.

Over mine tailings.

- 4.261** Corner No. 2, at proportionate distance, based on the Grant Boundary method; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 24 ins. in the ground, with aluminum cap marked:




---

N. 46° 43.8' W., along line 2-3.

- 13.00** Paved road, bears NW and SE.

- 21.083** Corner No. 3, at proportionate distance, based on the Grant Boundary Method; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 15 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:



DEPENDENT RESURVEY OF A PORTION OF  
MINERAL SURVEY NOS. 3995, 3996, 3997, AND 3998,  
T. 29 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS


Mineral Survey No. 3995

## COPPER KING LODE

N. 39° 00.2' E., along line 3-4.

- 4.525** Corner No. 4, on line 2-3, Mineral Point, same survey, at proportionate distance, based on the Grant Boundary Method; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:



Mineral Survey No. 3995

## MINERAL POINT LODE


N. 43° 58.3' W., along line 2-3.

- 2.930** Corner No. 3, identical with Corner No. 2, Texas lode, same survey, monumented with a pine post, 5 ft. long, 6 ins. square, and dimly marked, from which the original bearing tree:

A cedar, 14 ins. diameter, bears N. 89° 45' E., 16 links distance,  
marked C2 3995 BT.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:



Deposit the pine post alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF  
MINERAL SURVEY NOS. 3995, 3996, 3997, AND 3998,  
T. 29 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

## CHAINS


Mineral Survey No. 3995

## TEXAS LODGE

N. 44° 08.3' W., along line 2-3.

**7.698** Intersect the section line between sections 27 and 34.

**22.427** Corner No. 3, monumented with an iron post, 2 1/2 ins. diameter, firmly set, projecting 8 ins. above ground, with an unmarked brass cap, with a squared pine post, 4 ft. long, with faint scribe markings alongside, marked brass cap as follows:



From which the original bearing tree:


A cedar, 16 ins. diameter, bears N. 55° E., 80 links distance,  
marked C3 32995 BT.

N. 38° 56.7' E., along line 3-4.

**7.939** Corner No. 4, identical with Corner No. 2, Pacific lode, same survey, monumented with a rebar and rotted pine post in a mound of stone. This rebar is accepted as the corner point.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:



Bury the rebar alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF  
MINERAL SURVEY NOS. 3995, 3996, 3997, AND 3998,  
T. 29 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Mineral Survey No. 3995

PACIFIC LODE


N. 38° 55.7' E., along line 2-3.

**8.781** Corner No. 3, monumented with a rebar in a mound of stone, from which the bearing tree, stump of a dead and fallen pinon, 12 ins. diameter, bears S. 24° 24' W., 51 links distance, with blaze plainly marked.

This rebar is accepted as the best available evidence of the corner point.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 24 ins. in the ground, with aluminum cap marked:



Bury the rebar alongside the aluminum post.

S. 44° 04.3' E., along line 3-4.

**22.427** Corner No. 4, Pacific lode, identical with Corner No. 3, Anaconda lode, same survey, heretofore described.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD ASSISTANTS**

---

Name	Capacity
Robert Dalla	Surveying Technician
Shawn L. Peterson	Survey Aid

## CERTIFICATE OF SURVEY

I, *Jerry L. Thomas, Cadastral Surveyor*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *10th day of December, 1991*, I have *dependently resurveyed a portion of the south boundary, a portion of the subdivisional lines, and the subdivision of section 34, and resurveyed portions of Mineral Survey Nos. 3995, 3996, 3997, 3998, and 7361, located in sections 27, 33, and 34, T. 29 S., R. 24 E., and in section 27, T. 29 1/2 S., R. 24 E., under Group No. 780,*

of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

May 10, 1999

Date

*Jerry L. Thomas*

(Cadastral Surveyor)

Date

(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of a portion of the south boundary, a portion of the subdivisional lines, and the subdivision of section 34, and the resurvey of portions of Mineral Survey Nos. 3995, 3996, 3997, 3998, and 7361, located in sections 27, 33, and 34, in T. 29 S., R. 24 E., and in section 27, T. 29 1/2 S., R. 24 E., Salt Lake Meridian, Utah, under Group No. 780.*

executed by *Jerry L. Thomas, Cadastral Surveyor*

having been critically examined and found correct, are hereby approved.

May 14, 1999

Date

*Daniel W. Webb*

(Chief Cadastral Surveyor for Utah)