

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF  
A PORTION OF THE NORTH AND SOUTH BOUNDARIES,

A PORTION OF THE SUBDIVISIONAL LINES

AND THE

SUBDIVISION OF SECTIONS

4, 5, 8, 9, 17, 20, 21, 28, 33 AND 35

IN

TOWNSHIP 17 SOUTH, RANGE 1 WEST

OF THE SALT LAKE MERIDIAN  
IN THE STATE OF UTAH

EXECUTED BY

*Ferrel D. Reynolds*  
*Cadastral Surveyor*

Under special instructions dated *September 16, 1992*, approved September 16, 1992, which provided for the surveys included under Group Number *791*, and assignment instructions dated *September 16, 1992*.

Survey commenced *September 21, 1992*

Survey completed *April 16, 1993*

INDEX DIAGRAM

Township 17 South, Range 1 West

		4		8			
6	17	5	14	4	3	2	1
		17		7			
				13			
7	16	8	13	9	10	11	12
		16		13	12		
18		17	12	16	15	14	13
		15		11			
			11				
19	15	20		21	22	23	24
		15	10	6			
			10				
30		29	9	28	27	26	25
				9			
				6			
31		32	8	33	34	35	36
				5			
				5			
			4	3	3	3	2
							5

The Subdivision of Section 4 .....Page 17  
 The Subdivision of Section 5 .....Page 20  
 The Subdivision of Section 8 .....Page 22  
 The Subdivision of Section 9 .....Page 23  
 The Subdivision of Section 17.....Page 24  
 The Subdivision of Section 20.....Page 27  
 The Subdivision of Section 21.....Page 29  
 The Subdivision of Section 28.....Page 31  
 The Subdivision of Section 33.....Page 34  
 The Subdivision of Section 35.....Page 35

## TOWNSHIP 17 SOUTH, RANGE 1 WEST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

The following field notes describe the dependent resurvey of a portion of the north and south boundaries, a portion of the subdivisional lines and the subdivision of sections, 4, 5, 8, 9, 17, 20, 21, 28, 33 and 35, in T. 17 South, Range 1 West, Salt Lake Meridian, Utah.

History of SurveysSurveyed byRetr. or Resurveyed byNORTH BOUNDARY

Portion	C. Mogo	1856		
Portion	Stewart & Stewart	1898	Stewart & Stewart	1898
All			G.B. Hatch	1973-74

SOUTH BOUNDARY

Portion	C. Mogo	1856		
Portion	Stewart & Stewart	1898	Stewart & Stewart	1898
Portion			H.D. Heist & E.V. Woolley	1906
Portion			A.R. Talamantes	1906
All			C.P. Sylvester	1973-74

EAST BOUNDARY

Portion	C. Mogo	1856		
Portion	Stewart & Stewart	1898	Stewart & Stewart	1898
All			C.P. Sylvester	1973-74

WEST BOUNDARY

Portion	F. Dickert	1871		
Portion	S.M. Richardson	1883		
Portion	Stewart & Stewart	1898	Stewart & Stewart	1898
Portion			J.C. Thoma	1918-19
Portion			C.P. Sylvester	1973-74

SUBDIVISION

Portion	C. Mogo	1856		
Portion	Stewart & Stewart	1898	Stewart & Stewart	1898
All			C.P. Sylvester	1973-74

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group 791 Utah, dated September 16, 1992.

## TOWNSHIP 17 SOUTH, RANGE 1 WEST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

The directions of lines were determined by references to true meridians established on line by hour angle observations on Polaris. The lines were carried forward by sustained angulations, being supplemented by other observations taken throughout the progress of the survey. Distances were determined by electronic measurement.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. The retracement data were thoroughly verified and only the true line notes are given herein.

The geographic position of the 1/4 section corner of sections 7 and 8, as determined by a tie made to U.S. Coast and Geodetic Survey triangulation station "Yuba" is:

Latitude 39° 20' 39.18" N. Longitude 111° 57' 27.00" W.  
N.A.D. 1927

The mean magnetic declination as projected from the U.S. Geological Survey Magnetic Declination Map of 1990 is: 13 1/2° East.

---

Dependent Resurvey of a Portion of the South Boundary,  
T. 17 S., R. 1 W., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by C. Mogo in 1856,  
the Resurvey by S.P. Stewart and A.J. Stewart Jr. in 1898,  
and the Resurvey by C.P. Sylvester in 1973-74

---

Beginning at the corner of sections 1, 2, 35, and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.

The corner falls on a gradual W slope, located in a N and S barbwire fence line.

S. 88°18.8' W., between sections 2 and 35.

Over rolling land.

**19.837** The E 1/16 section corner of sections 2 and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set projecting 6 ins. above ground, with a steel fence post alongside and brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.

---

S. 88°18.1' W., beginning new measurement.

**19.835** Point for the 1/4 section corner of sections 2 and 35, at proportionate distance falls within the Sevier Bridge Reservoir; not monumented.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

**59.505**

Point for the corner of sections 2, 3, 34, and 35, at proportionate distance falls within the Sevier Bridge Reservoir; not monumented.

---

S. 88°18.1' W., between sections 3 and 34.

Over water.

**39.670**

Point for the 1/4 section corner of sections 3 and 34, at proportionate distance falls within the Sevier Bridge Reservoir; not monumented.

**79.340**

The corner of sections 3, 4, 33, and 34, monumented with an iron post, 2 1/2 ins diam., firmly set, projecting 6 ins. above ground with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.

The corner falls on a gradual E slope, located in a N and S barbwire fence line.

---

Reestablishment of the Survey Executed by C. Mogo in 1856,  
the Resurvey by S.P. Stewart and A.J. Stewart Jr. in 1898,  
the Retracement by H. D. Heist and E. V. Woolley in 1906,  
and the Resurvey by C.P. Sylvester in 1973-74.

---

S. 89°58.0' W., between sections 4 and 33.

On gradual easterly slope over mountainous land.

**20.000**

Point for the E 1/16 section corner of sections 4 and 33.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T17S R1W  
E 1/16  $\frac{S33}{S4}$   
T18S R1W  
1993

Raise a mound of stone, 3 ft. base by 2 ft. high, N of the corner.

**40.000**

The 1/4 section corner of sections 4 and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap marked as described in the official record of resurvey by C.P. Sylvester in 1973-74.

The corner falls on a gradual SE slope, in pinon and juniper.

---

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

S. 87° 30.1' W., beginning new measurement.

- 41.319** The corner of sections 4, 5, 32, and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap marked as described in the record of the resurvey by C.P. Sylvester in 1973-74.

---

Dependent Resurvey of a Portion of the North Boundary,  
T. 17 S., R. 1 W., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by C. Mogo in 1856,  
the Survey and Resurvey by S.P. Stewart and A.J. Stewart Jr. in 1898  
and the Resurvey by G.B. Hatch in 1973-74

---

From the corner of sections 4, 5, 32, and 33, on the north boundary of the township, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground with brass cap marked as described in the official record of the resurvey by G.B. Hatch in 1973-74.

S. 88°06.3' W., between sections 5 and 32.

Over level desert land.

- 19.940** Point for the E 1/16 section corner of sections 5 and 32 on the north boundary of the township; not monumented.

- 39.880** The 1/4 section corner of sections 5 and 32, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground in a collar of stone, with brass cap marked as described in the official record of the resurvey by G.B. Hatch in 1973-74.

---

S. 89°25.5' W., beginning new measurement.

- 39.936** The corner of sections 5, 6, 31, and 32, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap marked as described in the official record of the resurvey by G.B. Hatch in 1973-74.

---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 17 S., R. 1 W., Salt Lake Meridian, Utah

---

Reestablishment of the Survey executed by C. Mogo in 1856  
the Resurvey by S.P. Stewart and A.J. Stewart Jr. in 1898,  
and the Resurvey by C.P. Sylvester in 1973-74

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the corner of sections 1, 2, 35, and 36, on the south boundary of the township, hereinbefore described.

N. 1°15.4' W., between sections 35 and 36.

Over bench land.

- 40.360** The 1/4 section corner of sections 35 and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.

The corner is located on S slope, at the end of an old abandoned fence, bears W.

---

Reestablishment of the Survey Executed by C. Mogo in 1856  
and the Resurvey by C.P. Sylvester in 1973-74

---

From the point for the corner of sections 2, 3, 34, and 35, on the south boundary of the township, hereinbefore described.

N. 1°42.5' W., between sections 34 and 35.

Over water.

- 40.247** Point for the 1/4 section corner of sections 34 and 35, at proportionate distance falls within the Sevier Bridge Reservoir; not monumented.

- 80.444** The corner of sections 26, 27, 34, and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with a steel fence post alongside, and with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.

---

From the corner of sections 3, 4, 33, and 34, on the south boundary of the township, hereinbefore described.

N. 1°54.7' W., between sections 33 and 34.

Over rolling land.

- 40.167** The 1/4 section corner of sections 33 and 34, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.

The corner falls 9 lks. W of a barbwire fence corner, bears N and E.

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

N. 1°55.7' W., beginning new measurement.

- 40.228** The corner of sections 27, 28, 33, and 34, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.

The corner falls on gradual E slope, at the corner of fences N, S, E, and SW.

---

N. 2°00.6' W., between sections 27 and 28.

- 40.172** Point for the 1/4 section corner of sections 27 and 28, at proportionate distance falls within the Sevier Bridge Reservoir; not monumented.

- 60.258** Point for the N 1/16 section corner of sections 27 and 28, at proportionate distance, falls within the Sevier Bridge Reservoir; not monumented.

- 80.344** The corner of sections 21, 22, 27, and 28, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.

The corner is located in a small draw, course SW.

---

N. 1°49.9' W., between sections 21 and 22.

- 19.925** The S 1/16 section corner of sections 21 and 22, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.
- 

N. 1°51.6' W., beginning new measurement.

- 19.934** The 1/4 section corner of sections 21 and 22, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.
- 

From the corner of sections 9, 10, 15, and 16, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.

N. 0°31.5' W., between sections 9 and 10.

Over flat ground.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

**20.328**

The S 1/16 section corner of sections 9 and 10, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.

---

N. 0°29.2' W., beginning new measurement.

**20.320**

The 1/4 section corner of sections 9 and 10, monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.

---

N. 0°32.8' W., beginning new measurement.

**40.593**

The corner of sections 3, 4, 9 and 10, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.

---

Reestablishment of the Survey Executed by  
S.P. Stewart and A.J. Stewart Jr. in 1898,  
and the Resurvey by C.P. Sylvester in 1973-74

---

N. 0°02.5' E., between sections 3 and 4.

Over mountainous land.

**39.589**

The 1/4 section corner of sections 3 and 4, monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973.

from which the 1973 bearing trees.

A juniper, 10 ins. diam., bears N. 74° E., 28 lks. dist.,  
marked 1/4 S BT.

A juniper, 10 ins. diam., bears N. 50° W., 33 lks. dist.,  
marked 1/4 S BT. (Record S. 8 1/2° W., 35 lks. dist.)

---

N. 0°36.5' E., beginning new measurement.

**20.530**

The N 1/16 section corner of sections 3 and 4, monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, with a steel fence post alongside, with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973.

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

N. 0°14.3' E., beginning new measurement.

- 20.810** The closing corner of sections 3 and 4, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap marked and witnessed as described in the official record of the resurvey by C.P. Sylvester in 1973-74.

---

Reestablishment of the Survey executed by C. Mogo in 1856  
the Resurvey by S.P. Stewart and A.J. Stewart Jr. in 1898,  
and the Resurvey by C.P. Sylvester in 1973-74

---

From the corner of sections 4, 5, 32, and 33, on the south boundary of the township, hereinbefore described.

N. 1° 36.5' W., between sections 32 and 33.

On an easterly slope, over mountainous land.

- 40.040** The 1/4 section corner of sections 32 and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, and with a mound of stone to the W, with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.

---

N. 1°33.7' W., beginning new measurement.

- 40.221** The corner of sections 28, 29, 32 and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with a mound of stone to the W, with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973.

The corner falls on a gradual NE slope in pinon and juniper growth.

---

Reestablishment of the Survey Executed by C. Mogo in 1856  
and the Resurvey Executed by C.P. Sylvester in 1973-74

---

From the corner of sections 27, 28, 33, and 34.

S. 88°38.0' W., between sections 28 and 33.

On easterly slope over broken land.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS****20.136**

The E 1/16 section corner of sections 28 and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above ground, with a steel fence post alongside, with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.

---

S. 88°36.0' W., beginning new measurement.

**20.209**

The 1/4 section corner of sections 28 and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.

---

S. 88°37.8' W., beginning new measurement.

**40.470**

The corner of sections 28, 29, 32, and 33.

---

Reestablishment of the Survey executed by C. Mogo in 1856  
the Resurvey by S.P. Stewart and A.J. Stewart Jr. in 1898,  
and the Resurvey by C.P. Sylvester in 1973-74

---

N. 1°41.5' W., between sections 28 and 29.

Over mountainous land.

**40.120**

The 1/4 section corner of sections 28 and 29, monumented with an iron post, 2 1/2 ins. diam., firmly set in a collar of stone, projecting 8 ins. above ground, with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.

---

N. 1°39.3' W., beginning new measurement.

**40.064**

The corner of sections 20, 21, 28 and 29, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting, 4 ins above ground, with a steel fence post alongside and with a mound of stone W of the corner, and brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.

---

Reestablishment of the Survey Executed by C. Mogo in 1856  
and the Resurvey Executed by C.P. Sylvester in 1973-74

---

From the corner of sections 21, 22, 27, and 28.

S. 88°24.6' W., between sections 21 and 28.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Over desert land.

**20.113** Point for the E 1/16 section corner of sections 21 and 28, falls within the Sevier Bridge Reservoir; not monumented.

**40.226** The 1/4 section corner of sections 21 and 28, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with a mound of stone to the N, and with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.

---

S. 88°36.7' W., beginning new measurement.

**20.050** Point for the W 1/16 section corner of sections 21 and 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a mound of stone 3 ft. base to top of aluminum cap marked:

T17S R1W  
W 1/16 S21  
S28  
1993

**40.100** The corner of sections 20, 21, 28, and 29.

---

Reestablishment of the Survey Executed by C. Mogo in 1856,  
the Resurvey by S.P. Stewart and A.J. Stewart Jr. in 1898,  
and the Resurvey by C.P. Sylvester in 1973-74

---

N. 1°46.0' W., between sections 20 and 21.

Over rolling mountainous land.

**20.070** Point for the S 1/16 section corner of sections 20 and 21.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T17S R1W  
S 1/16  
S20 | S21  
1993

Raise a mound of stone, 3 ft. base by 2 ft. high, W of the corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS****40.140**

The 1/4 section corner of sections 20 and 21, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with a steel fence post alongside and brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.

The corner falls on a northeasterly slope in pinon and juniper.

---

N. 1°16.7' W., beginning new measurement.

**20.137**

The N 1/16 section corner of sections 20 and 21, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with a steel fence post alongside and with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.

---

N. 1°39.1' W., beginning new measurement.

**20.113**

Point for the corner of sections 16, 17, 20, and 21 at proportionate distance falls within the Sevier Bridge Reservoir; not monumented.

---

Reestablishment of the Survey Executed by C. Mogo in 1856  
and the Resurvey by C.P. Sylvester in 1973-74

---

From the 1/4 section corner of sections 16 and 21, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground with a steel fence post alongside and with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.

The corner falls at the SE edge of a reseeded area, bears E and W, on rolling northerly slope.

S. 88°55.8' W., between sections 16 and 21.

Over rolling open land.

**20.000**

Point for the W 1/16 section corner of sections 16 and 21, falls within the Sevier Bridge Reservoir; not monumented.

**40.000**

Point for the corner of sections 16, 17, 20, and 21.

---

Reestablishment of the Survey Executed by C. Mogo in 1856,  
the Resurvey by S.P. Stewart and A.J. Stewart Jr. in 1898,  
and the Resurvey by C.P. Sylvester in 1973-74

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

N. 1°25.5' W., between sections 16 and 17.

Over water.

**20.110** Point for the S 1/16 section corner of sections 16 and 17, falls within the Sevier Bridge Reservoir; not monumented.

**40.220** Point for the 1/4 section corner of sections 16 and 17, falls within the Sevier Bridge Reservoir; not monumented.

**60.330** Point for the N 1/16 section corner of sections 16 and 17.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a collar of stone, with aluminum cap marked:

T17S R1W  
N 1/16  
S17 | S16  
1993

The corner is located on a rolling E slope, in juniper.

**80.440** Point for the corner of sections 8, 9, 16 and 17, at proportionate distance falls within the Sevier Bridge Reservoir; not monumented.

---

Reestablishment of the Survey Executed by C. Mogo in 1856  
and the Resurvey by C.P. Sylvester in 1973-74

---

From the corner of sections 9, 10, 15, and 16.

S. 89°01.8' W., between sections 9 and 16.

Over gradual rolling westerly slope.

**19.844** The E 1/16 section corner of sections 9 and 16, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above ground with a steel fence post alongside and with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.

---

S. 89°00.0' W., beginning new measurement.

**19.888** The 1/4 section corner of sections 9 and 16, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins above ground with a steel fence alongside and with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

S. 88°55.1' W., beginning new measurement.

39.655 Point for the corner of sections 8, 9, 16, and 17.

Reestablishment of the Survey Executed by C. Mogo in 1856, the Resurvey by S.P. Stewart and A.J. Stewart Jr. in 1898, and the Resurvey by C.P. Sylvester in 1973-74

N. 1°27.5' W., between sections 8 and 9.

Over water.

40.240 Point for the 1/4 section corner of sections 8 and 9, at proportionate distance, falls within the Sevier Bridge Reservoir; not monumented.

80.380 The corner of sections 4, 5, 8, and 9, monumented with an iron post, 2 1/2 ins. diam., firmly set in a collar of stone, projecting 6 ins. above ground, with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.

From the corner of sections 3, 4, 9 and 10.

S. 88°18.9' W., between sections 4 and 9.

Over rolling slope.

40.297 The 1/4 section corner of sections 4 and 9, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground with a steel fence post alongside with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.

S. 88°24.0' W., beginning new measurement.

Over flat open ground.

20.198 Point for the W 1/16 section corner of sections 4 and 9.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T17S R1W  
W 1/16 S4  
S9  
1993

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set a steel fence post alongside.

The corner is located on a gradual SW slope.

**40.396** The corner of sections 4, 5, 8, and 9.

---

N. 1°17.3' W., between sections 4 and 5.

Over rolling open land.

**20.884** Point for the S 1/16 section corner of sections 4 and 5.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T17S R1W  
S 1/16  
S5 | S4  
1993

Set a steel fence post alongside the aluminum post.

**41.768** The 1/4 section corner of sections 4 and 5, monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.

---

N. 1°50.1' W., beginning new measurement.

**19.556** Point for the N 1/6 section corner of sections 4 and 5; not monumented.

**39.112** The corner of sections 4, 5, 32, and 33, on the north boundary of the township, hereinbefore described.

---

Reestablishment of the Survey Executed by,  
S.P. Stewart and A.J. Stewart Jr. in 1898,  
and the Resurvey by C.P. Sylvester in 1973-74

---

From the corner of sections 19 and 30 only, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.

N. 1°58.0' E., on the east boundary of section 19.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

- 1.498** The closing corner of sections 20 and 29, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.
- 38.560** The E 1/4 section corner of section 19 only, monumented with an iron post, 2 1/2 ins. diam., set in a mound of stone, with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.
- 
- N. 2°24.0' E., beginning new measurement.
- 1.837** The W 1/4 section corner of section 20 only, monumented with an iron post, 2 1/2 ins. diam., set in a mound of stone with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.
- 
- Reestablishment of the Survey Executed by C. Mogo in 1856,  
the Resurvey by S.P. Stewart and A.J. Stewart Jr. in 1898,  
and the Resurvey by C.P. Sylvester in 1973-74
- 
- From the corner of sections 20, 21, 28, and 29.
- S. 88°29.3' W., between sections 20 and 29.
- Over mountainous land.
- 39.704** The 1/4 section corner of sections 20 and 29, monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.
- No remaining evidence of the 1973 bearing tree was found.
- 
- N. 87°55.1' W., beginning new measurement.
- 38.910** The closing corner of sections 20 and 29.
- 
- From the point for the corner of sections 16, 17, 20, and 21.
- S. 88°39.2' W., between sections 17 and 20.
- 20.007** The E 1/16 section corner of sections 17 and 20, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with a steel fence post alongside and with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.
-

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

S. 88°34.6' W., beginning new measurement.

- 20.007** The 1/4 section corner of sections 17 and 20, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with a mound of stone to the north, and with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.

---

From the point for the corner of sections 8, 9, 16, and 17.

S. 88°08.5' W., between sections 8 and 17.

Over water.

- 20.502** Point for the E 1/16 section corner of sections 8 and 17, falls within the Sevier Bridge Reservoir; not monumented.

- 41.004** The 1/4 section corner of sections 8 and 17, monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.

---

S. 88°09.3' W., beginning new measurement.

- 40.234** The corner of sections 7, 8, 17, and 18, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with a mound of stone to the W, with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.

---

N. 0°58.5' W., between sections 7 and 8.

Over mountainous land.

- 20.445** The S 1/16 section corner of sections 7 and 8, monumented with an iron post, 2 1/2 ins. in diam., firmly set, projecting 6 ins. above ground, with a mound of stone to the W, and with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.

---

N. 0°59.1' W., beginning new measurement.

- 20.452** The 1/4 section corner of sections 7 and 8, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground with a mound of stone to the W, with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.

From this corner, U.S. Coast and Geodetic Survey Triangulation Station "YUBA", monumented with a standard bronze disk, bears N. 87°02.5' W., 171.631 chs. distance.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the corner of sections 4, 5, 8, and 9.

S. 89°10.0' W., between sections 5 and 8.

**40.266** Point for the 1/4 section corner of sections 5 and 8, at proportionate distance, falls within Sevier Bridge Reservoir; not monumented.

**80.532** The corner of sections 5, 6, 7, and 8, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with a steel fence post alongside and with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.

---

N. 1°49.3' W., between sections 5 and 6.

Over rolling land.

**39.165** Point for the 1/4 section corner of sections 5 and 6 at proportionate distance, falls within Sevier Bridge Reservoir; not monumented.

---

Reestablishment of the Survey Executed by  
S.P. Stewart and A.J. Stewart Jr. in 1898,  
and the Resurvey by C.P. Sylvester in 1973-74

---

N. 0°19.4' W., beginning new measurement.

**41.157** The corner of sections 5, 6, 31, and 32 on the north boundary of the township, hereinbefore described.

---

The Subdivision of Section 4,  
T. 17 S., R. 1 W., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 4 and 9.

N. 2°00.7' W., on the N - S center line of section 4.

**20.362** Point for the center S 1/16 section corner of section 4..

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, in a mound of stone, 4 ft. base to top of aluminum cap marked:

THE SUBDIVISION OF SECTION 4,  
T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T17S R1W  
C  
S 1/16 | S4  
C  
1993

The corner is located on a S slope, in sagebrush and scattered juniper.

**40.724** Point for the center 1/4 section corner, at intersection with the E - W center line of section 4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with aluminum cap marked:

T17S R1W  
C 1/4  
S4  
1993

Raise a mound of stone, 3 ft. base by 1 ft. high, W of the corner.

Set a steel fence post alongside the aluminum post.

**61.008** Point for the center N 1/16 section corner of section 4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground and in a collar of stone with aluminum cap marked:

T17S R1W  
C  
N 1/16 | S4  
C  
1993

Set a steel fence post alongside the aluminum post.

**81.292** The 1/4 section corner of sections 4 and 33 on the north boundary of the township, monumented with an iron post, 2 1/2 ins. diam., firmly set, with brass cap marked as described in the official record of the resurvey by G.B. Hatch in 1973-74.

---

From the 1/4 section corner of sections 3 and 4.

S. 89°53.9' W., on the E - W center line of section 4.

**41.734** The center 1/4 section corner.

**61.676** Point for the center W 1/16 section corner of section 4.

THE SUBDIVISION OF SECTION 4,  
T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T17S R1W  
C  $\frac{W\ 1/16}{S4}$  C  
1993

Set a steel fence post alongside the aluminum post.

The corner falls on a SW slope in juniper and pinon.

**81.618** The 1/4 section corner of sections 4 and 5.

---

From the N 1/16 section corner of sections 3 and 4.

S. 89°33.4' W., on the E - W center line of the NE 1/4 of section 4.

**42.663** The center N 1/16 section corner.

---

From the W 1/16 section corner of sections 4 and 9.

N. 1°38.7' W., on the N - S center line of the SW 1/4 of section 4.

**20.623** Point for the SW 1/16 section corner, at intersection with the E - W center line of the SW 1/4 of section 4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T17S R1W  
SW 1/16  
S4  
1993

Raise a mound of stone, 3 ft. base by 2 ft. high, W of the corner.

**41.246** The center W 1/16 section corner.

---

From the center S 1/16 section corner of section 4.

S. 89°08.6' W., on the E - W center line of the SW 1/4 of section 4.

**20.068** The SW 1/16 section corner.

THE SUBDIVISION OF SECTION 4,  
T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS****40.136**

The S 1/16 section corner of sections 4 and 5.

---

The Subdivision of Section 5,  
T. 17 S., R. 1 W., Salt Lake Meridian, Utah

---

From the point for the 1/4 section corner of sections 5 and 8.

N. 1°17.1' W., on the N - S center line of section 5.

**40.470**

Point for the center 1/4 section corner at intersection with the E - W center line of section 5.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground and set in a collar of stone, with aluminum cap marked:

T17S R1W  
C 1/4  
S5  
1993

The corner falls on a E slope in pinon and juniper.

**60.303**

Point for the center N 1/16 section corner of section 5.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with aluminum cap marked:

T17S R1W  
C  
N 1/16 | S5  
C  
1993

Raise a mound of stone, 3 ft. base by 2 ft. high, W of the corner.

**80.136**

The 1/4 section corner of sections 5 and 32, on the north boundary of the township, hereinbefore described.

---

From the 1/4 section corner of sections 4 and 5.

S. 87°19.2' W., on the E - W center line of section 5.

**20.135**

Point for the center E 1/16 section corner of section 5.

THE SUBDIVISION OF SECTION 5,  
T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T17S R1W  
C        E 1/16        C  
          S5  
          1993

Set a steel fence post alongside the aluminum post.

The corner falls on rolling land, 75 lks S of a draw, course SW.

**40.270** The center 1/4 section corner.

**80.910** Point for the 1/4 section corner of sections 5 and 6.

---

From the center E 1/16 section corner of section 5.

N. 1°33.5' W., on the N - S center line of the NE 1/4 of section 5.

**18.948** Point selected for the witness corner to the NE 1/16 section corner of section 5.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

WC  
T17S R1W  
NE 1/16  
S5  
1993

Set a steel fence post alongside the aluminum post.

**19.694** True point for the NE 1/16 section corner, at intersection with E - W center line of the NE 1/4 of section 5, falls in the bottom of a wash, drains SE.

**39.388** The point for the E 1/16 section corner of sections 5 and 32, on the north boundary of the township; hereinbefore described.

---

From the N 1/16 section corner of sections 4 and 5.

S. 87°42.6' W., on the E - W center line of the NE 1/4 of section 5.

**20.037** True point for the NE 1/16 section corner.

**40.074** The center N 1/16 section corner.

THE SUBDIVISION OF SECTION 8,  
T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

The Subdivision of Section 8,  
T. 17 S., R. 1 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 8 and 17.

N. 0°56.7' W., on the N - S center line of section 8.

**20.288** Point for the center S 1/16 section corner of section 8, falls within Sevier Bridge Reservoir; not monumented.

**40.576** Point for the center 1/4 section corner at intersection with the E - W center line of section 8.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with aluminum cap marked:

T17S R1W  
C 1/4  
S8  
1993

Set a steel fence post alongside the aluminum post.

The corner falls on a gradual NW slope, 25 lks. S of a trail road, course NW and SE.

**81.110** The point for the 1/4 section corner of sections 5 and 8.

From the point for the 1/4 section corner of sections 8 and 9.

S. 88°36.6' W., on the E - W center line of section 8.

**40.632** The center 1/4 section corner.

**80.883** The 1/4 section corner of sections 7 and 8.

From the point for the center S 1/16 section corner of section 8.

S. 88°22.5' W., on the E - W center line of the SW 1/4 of section 8.

**40.240** The S 1/16 section corner of sections 7 and 8.

The Subdivision of Section 9,  
T. 17 S., R. 1 W., Salt Lake Meridian, Utah

THE SUBDIVISION OF SECTION 9,  
T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the 1/4 section corner of sections 9 and 16.

N. 0°55.7' W., on the N - S center line of section 9.

**20.205** Point for the center S 1/16 section corner of section 9.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T17S R1W  
C  
S 1/16 | S9  
C  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on a gradual N slope, in sagebrush.

**40.410** Point for the center 1/4 section corner at intersection with the E - W center line of section 9.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with aluminum cap marked:

T17S R1W  
C 1/4  
S9  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on a gradual N slope, in greasewood.

**80.745** The 1/4 section corner of sections 4 and 9.

From the 1/4 section corner of sections 9 and 10.

S. 88°40.5' W., on the E - W center line of section 9.

**20.015** Point for the center E 1/16 section corner of section 5.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 9,  
T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T17S R1W  
C     E 1/16     C  
      S9  
      1993

Set a steel fence post alongside the aluminum post.

The corner falls on level land, in sagebrush.

**40.030** The center 1/4 section corner.

**80.055** The point for the 1/4 section corner of sections 8 and 9.

---

From the E 1/16 section corner of sections 9 and 16.

N. 0°44.9' W., on the N - S center line of the SE 1/4 of section 9.

**20.262** Point for the SE 1/16 section corner, at intersection with the E - W center line of the SE 1/4 of section 9.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone with aluminum cap marked:

T17S R1W  
SE 1/16  
S9  
1993

The corner falls on rolling land in hollow, drains NW.

**40.524** The center E 1/16 section corner.

---

From the S 1/16 section corner of sections 9 and 10.

S. 88°50.3' W., on the E - W center line of the SE 1/4 of section 9.

**19.923** The SE 1/16 section corner.

**39.874** The center S 1/16 section corner.

---

The Subdivision of Section 17,  
T. 17 S., R. 1 W., Salt Lake Meridian, Utah

---

THE SUBDIVISION OF SECTION 17,  
T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the 1/4 section corner of sections 17 and 20.

N. 2°08.2' W., on the N - S center line of section 17.

**19.487** Point for the center S 1/16 section corner of section 17.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T17S R1W  
C  
S 1/16 | S17  
C  
1993

Raise a mound of stone, 3 ft. base by 2 ft. high, W of the corner.

The corner is located on a gradual E slope, 70 lks. W of a draw, course N, in pinon and juniper growth.

**38.974** Point for the center 1/4 section corner at intersection with the E - W center line of section 17.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with aluminum cap marked:

T17S R1W  
C 1/4  
S17  
1993

Set a steel fence post alongside the aluminum post.

Raise a mound of stone, 3 ft. base by 2 ft. high, W of the corner.

The corner is located on a gradual SE slope, 10 lks. S of a 4 strand barbwire fence, projecting NE and SW.

**59.543** Point for the center N 1/16 section corner of section 17.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T17S R1W  
C  
N 1/16 | S17  
C  
1993

THE SUBDIVISION OF SECTION 17,  
T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

- Set a steel fence post alongside the aluminum post.
- 80.112** The 1/4 section corner of sections 8 and 17.
- 
- From the point for the 1/4 section corner of sections 16 and 17.
- S. 86°50.8' W., on the E - W center line of section 17.
- 20.257** Point for center E 1/16 section corner of section 17, falls within Sevier Bridge Reservoir; not monumented.
- 40.514** The center 1/4 section corner.
- 81.440** The 1/4 section corner of sections 17 and 18, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with a mound of stone W of the iron post, with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.
- 
- From the point for the center E 1/16 section corner of section 17.
- N. 1°47.2' W., on the N - S center line of the NE 1/4 of section 17.
- 20.338** Point for the NE 1/16 section corner at intersection with the E - W center line of the NE 1/4 of section 17, falls within Sevier Bridge Reservoir; not monumented.
- 40.676** Point for the E 1/16 section corner of sections 8 and 17.
- 
- From the N 1/16 section corner of sections 16 and 17.
- S. 87°30.0' W., on the E - W center line of the NE 1/4 of section 17.
- 20.378** Point for the NE 1/16 section corner.
- 40.756** The center N 1/16 section corner.
- 
- From the E 1/16 section corner of sections 17 and 20.
- N. 1°45.5' W., on the N - S center line of the SE 1/4 of section 17.
- 19.798** Point for the SE 1/16 section corner at intersection with the E - W center line of the SE 1/4 of section 17.

THE SUBDIVISION OF SECTION 17,  
T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T17S R1W  
SE 1/16  
S17  
1993

Set a steel fence post alongside the aluminum post.

The corner falls on a gradual E slope in sagebrush and juniper.

**39.596** Point for the center E 1/16 section corner.

---

From the point for the S 1/16 section corner of sections 16 and 17.

S. 87°43.6' W., on the E - W center line of the SE 1/4 of section 17.

**20.130** The SE 1/16 section corner of section 17.

**40.260** The center S 1/16 section corner of section 17.

---

The Subdivision of Section 20,  
T. 17 S., R. 1 W., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 20 and 29.

N. 1°50.5' W., on the N - S center line of section 20.

**40.730** Point for the center 1/4 section corner at intersection with the E - W center line of section 20.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground in a mound of stone, with aluminum cap marked:

T17S R1W  
C 1/4  
S20  
1993

The corner is located on a steep NW slope, in pinon and juniper.

**60.605** Point for the center N 1/16 section corner of section 20.

THE SUBDIVISION OF SECTION 20,  
T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T17S R1W  
C  
N 1/16 | S20  
C  
1993

Raise a mound of stone, 3 ft. base by 2 ft. high, W of the corner.

The corner falls on a N slope in dense pinon and juniper.

**80.480** The 1/4 section corner of sections 17 and 20.

---

From the 1/4 section corner of sections 20 and 21.

S. 89°20.2' W., on the E - W center line section 20.

**19.880** Point for the center E 1/16 section corner of section 20.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone with aluminum cap marked:

T17S R1W  
C ——— E 1/16 ——— C  
S20  
1993

The corner falls on top of spur ridge, slopes E in scattered pinon and juniper.

**39.760** The center 1/4 section corner.

**75.980** The 1/4 section corner of section 20 only.

---

From the center E 1/16 section corner of section 20.

N. 1°40.6' W., on the N -S center line of the NE 1/4 of section 20.

**20.006** Point for the NE 1/16 section corner, at intersection with the E - W center line of the NE 1/4 of section 20.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base to top of aluminum cap marked:

THE SUBDIVISION OF SECTION 20,  
T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T17S R1W  
NE 1/16  
S20  
1993

The corner falls on a steep NW slope in sagebrush and scattered pinon and juniper.

40.000 The E 1/16 section corner of sections 17 and 20.

---

From the N 1/16 section corner of sections 20 and 21.

S. 88°57.6' W., on the E - W center line of the NE 1/4 of section 20.

20.010 The NE 1/16 section corner.

39.952 The center N 1/16 section corner.

---

The Subdivision of Section 21,  
T. 17 S., R. 1 W., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 21 and 28.

N. 1°40.8' W., on the N - S center line of section 21.

20.035 Point for the center S 1/16 section corner of section 21.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T17S R1W  
C  
S 1/16 | S21  
C  
1993

Set a steel fence post alongside the aluminum post.

Raise a mound of stone, 3 ft. base by 2 ft. high NW of the corner.

The corner falls within a draw, drains SE in juniper growth.

40.070 Point for the center 1/4 section corner at intersection with the E - W center line of section 21.

THE SUBDIVISION OF SECTION 21,  
T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with aluminum cap marked:

T17S R1W  
C 1/4  
S21  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on a gradual N slope, in sagebrush.

**60.118** Point for the center N 1/16 section corner of section 21, falls with Sevier Bridge Reservoir; not monumented.

**80.166** The 1/4 section corner of sections 16 and 21.

---

From the 1/4 section corner of sections 21 and 22.

S. 88°42.6' W., on the E - W center line of section 21.

**40.104** The center 1/4 section corner.

**60.182** Point for the center W 1/16 section corner of section 21.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone 4 ft. base, to top of aluminum cap marked:

T17S R1W  
C  $\frac{W \ 1/16}{S21}$  C  
1993

The corner falls on a NW slope in scattered pinon and juniper.

**80.260** The 1/4 section corner of sections 20 and 21.

---

From the W 1/16 section corner of sections 21 and 28.

N. 1°43.4' W., on the N - S center line of the SW 1/4 of section 21.

**20.052** Point for the SW 1/16 section corner at intersection with the E - W center line of the SW 1/4 of section 21.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

THE SUBDIVISION OF SECTION 21,  
T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T17S R1W  
SW 1/16  
S21  
1993

The corner falls in a hollow, bears E, on a gradual E slope in sagebrush and scattered juniper.

**40.104** The center W 1/16 section corner.

---

From the center S 1/16 section corner of section 21.

S. 88°39.6' W., on the E - W center line of the SW 1/4 of section 21.

**20.064** The SW 1/16 section corner.

**40.128** The S 1/16 section corner of sections 20 and 21.

---

From the center W 1/16 section corner of section 21.

N. 1°34.3' W., on the N - S center line of the NW 1/4 of section 21.

**20.092** Point for the NW 1/16 section corner at intersection with the E - W center line of the NW 1/4 of section 21, falls within the Sevier Bridge Reservoir; not monumented.

**40.172** Point for the W 1/16 section corner of sections 16 and 21.

---

From the point for the center N 1/16 section corner of section 21.

S. 88°50.2' W., on the E - W center line of the NW 1/4 of section 21.

**20.040** Point for the NW 1/16 section corner.

**40.014** The N 1/16 section corner of sections 20 and 21.

---

The Subdivision of Section 28,  
T. 17 S., R. 1 W., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 28 and 33.

N. 1°56.0' W., on the N - S center line of section 28.

THE SUBDIVISION OF SECTION 28,  
T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS****40.153**

Point for the center 1/4 section corner at intersection with the E - W center line of section 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground in a collar of stone, with aluminum cap marked:

T17S R1W  
C 1/4  
S28  
1993

Set a steel fence post alongside the aluminum post.

The corner is located, 1.50 chs. N of a trail road in the bottom of a wash, drains E, in scattered pinon and juniper.

**60.176**

Point for the center N 1/16 section corner of section 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T17S R1W  
C  
N 1/16 | S28  
C  
1993

Set a steel fence post alongside the aluminum post.

The corner falls on a gradual N slope in sagebrush.

**80.199**

The 1/4 section corner of sections 21 and 28.

---

From the point for the 1/4 section corner of sections 27 and 28.

S. 88°35.2' W., on the E - W center line of section 28.

**20.143**

Point for the center E 1/16 section corner of section 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a collar of stone and with aluminum cap marked:

T17S R1W  
C ——— E 1/16 ——— C  
S28  
1993

THE SUBDIVISION OF SECTION 28,  
T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

- The corner falls on a E slope in scattered pinon and juniper.
- 40.286** The center 1/4 section corner of section 28.
- 80.582** The 1/4 section corner of sections 28 and 29.
- 
- From the center E 1/16 section corner of section 28.
- N. 1°58.3' W., on the N - S center line of the NE 1/4 of section 28.
- 20.055** Point for the NE 1/16 section corner at intersection with the E - W center line of the NE 1/4 of section 28.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:
- T17S R1W  
NE 1/16  
S28  
1993
- The corner falls underneath power lines on a gradual E slope in sagebrush.
- 40.110** The point for the E 1/16 section corner of sections 21 and 28.
- 
- From the point for the N 1/16 section corner of sections 27 and 28.
- S. 88°30.0' W., on the E - W center line of the NE 1/4 of section 28.
- 20.128** The NE 1/16 section corner.
- 40.256** The center N 1/16 section corner.
- 
- From the E 1/16 section corner of sections 28 and 33.
- N. 2°01.4' W., on the N - S center line of the SE 1/4 of section 28.
- 40.158** The center E 1/16 section corner.
-

THE SUBDIVISION OF SECTION 33,  
T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

The Subdivision of Section 33,  
T. 17 S., R. 1 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 4 and 33, on the south boundary of the township; hereinbefore described.

N. 2°11.3' W., on the N - S center line of section 33.

**39.232** Point for the center 1/4 section corner at intersection with the E - W center line of section 33.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground in a collar of stone, with aluminum cap marked:

T17S R1W  
C 1/4  
S33  
1993

Raise a mound of stone, 3 ft. base by 2 ft. high, W of the corner.

The corner falls on a E slope in pinon and juniper.

**79.456** The 1/4 section corner of sections 28 and 33.

From the 1/4 section corner of sections 33 and 34.

S.88°37.6' W., on the E - W center line of section 33.

**20.083** Point for the center E 1/16 section corner of section 33.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

T17S R1W  
C ——— E 1/16 ——— C  
S33  
1993

The corner falls on a E slope in pinon and juniper.

**40.166** The center 1/4 section corner of section 28.

**81.079** The 1/4 section corner of sections 32 and 33.

THE SUBDIVISION OF SECTION 33,  
T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the center E 1/16 section corner of section 33.

N. 2°00.5' W., on the N - S center line of the NE 1/4 of section 33.

**40.230** The E 1/16 section corner of section 28 and 33.

---

The Subdivision of Section 35,  
T. 17 S., R. 1 W., Salt Lake Meridian, Utah

---

From the point for the 1/4 section corner of sections 2 and 35, on the south boundary of the township; hereinbefore described.

N. 1°31.2' W., on the N - S center line of section 35.

**40.300** Point for the center 1/4 section corner at intersection with the E - W center line of section 35.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground in a collar of stone, with aluminum cap marked:

T17S R1W  
C 1/4  
S35  
1993

Set a steel fence post alongside the aluminum post.

The corner falls within plowed ground.

**80.180** The 1/4 section corner of sections 26 and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set in a collar of stone with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.

---

From the 1/4 section corner of sections 35 and 36.

S.88°13.5' W., on the E - W center line of section 35

**19.927** Point for the center E 1/16 section corner of section 35.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base to top of aluminum cap marked:

THE SUBDIVISION OF SECTION 35,  
T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

T17S R1W  
C  $\frac{E\ 1/16}{S35}$  C  
1993

The corner falls on a E slope in pinon and juniper.

**39.854** The center 1/4 section corner of section 35.

**79.654** The point for the 1/4 section corner of sections 34 and 35.

---

From the E 1/16 section corner of sections 2 and 35 on the south boundary of the township;  
hereinbefore described.

N. 1°23.3' W., on the N - S center line of the SE 1/4 of section 35.

**40.327** The center E 1/16 section corner of section 35.

---

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD ASSISTANTS**

---

Name	Capacity
Gail E. Reynolds	Cadastral Surveyor

### CERTIFICATE OF SURVEY

I, *Ferrel D. Reynolds, Cadastral Surveyor*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *16th day of September, 1992*, I have *dependently resurveyed a portion of the north and south boundaries, a portion of the subdivisional lines and subdivided sections 4, 5, 8, 9, 17, 20, 21, 28, 33, and 35, in Township 17 South, Range 1 West,*

of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

\_\_\_\_\_  
April 22, 1997

Date



\_\_\_\_\_  
(Cadastral Surveyor)

\_\_\_\_\_

Date

\_\_\_\_\_

(Cadastral Surveyor)

### CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of a portion of the north and south boundaries, a portion of subdivisional lines and subdivided sections 4, 5, 8, 9, 17, 20, 21, 28, 33 and 35, in Township 17 South, Range 1 West, Salt Lake Meridian, Utah,*

executed by *Ferrel D. Reynolds, Cadastral Surveyor*

having been critically examined and found correct, are hereby approved.

\_\_\_\_\_  
April 24, 1997

Date



\_\_\_\_\_  
(Chief Cadastral Surveyor for Utah)