

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE RETRACEMENT OF A PORTION OF

THE WEST BOUNDARY

THE DEPENDENT RESURVEY

OF PORTIONS

OF THE SOUTH BOUNDARY

AND SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS 19, 30, AND 31,

TOWNSHIP 16 SOUTH, RANGE 1 WEST

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

*Ferrel D. Reynolds,
Cadastral Surveyor*

Under special instructions dated *March 1, 1993*, approved *April 24, 1995*, which provided for the surveys included under Group Number *795*, and assignment instructions dated *April 25, 1995*.

Survey commenced *June 1, 1995*

Survey completed *August 1, 1995*

INDEX DIAGRAM

Township 16 South , Range 1 West

	6	5	4	3	2	1
	7	8	9	10	11	12
	18	17	16	15	14	13
4	13 12	11				
4	19	11 20	21	22	23	24
3	10 9	9				
3	30	9 29	28	27	26	25
3	8 7	7				
3	31	6 32	18 33	16 34	15 35	13 36
2	6 5	4				

The Subdivision of Section 19 Page 13

The Subdivision of Section 30 Page 19

The Subdivision of Section 31 Page 26

TOWNSHIP 16 SOUTH, RANGE 1 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

The following field notes describe the retracement of a portion of the west boundary, the dependent resurvey of portions of the south boundary, and subdivisional lines, and the subdivision of sections 19, 30 and 31, in Township 16 South, Range 1 West, Salt Lake Meridian, Utah.

History of Earlier Surveys

Surveyed by	Retr. or Resurveyed by
-------------	------------------------

NORTH BOUNDARY (Third Standard Parallel South)

Portion	C. Mogo	1856		
Portion	Stewart & Stewart	1898	Stewart & Stewart	1898
Portion			G.B. Hatch	1973

SOUTH BOUNDARY

Portion	C. Mogo	1856		
All	Stewart & Stewart	1898	Stewart & Stewart	1898
All			G.B. Hatch	1973

EAST BOUNDARY (Salt Lake Meridian)

Portion	C. Mogo	1856		
All	Stewart & Stewart	1898	Stewart & Stewart	1898
Portion			G.B. Hatch	1973

WEST BOUNDARY

All	F. Dickert	1871		
All			G.B. Hatch	1973
Portion			F.D. Reynolds	1991

SUBDIVISION

All	F. Dickert	1871		
All	Stewart & Stewart	1898	Stewart & Stewart	1898
Portion			G.B. Hatch	1973

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 795, dated March 1, 1993.

The directions of the lines were determined by hour angle observations of the sun and Polaris, carried forward by sustained angulation. Distances were determined by electronic measurement.

TOWNSHIP 16 SOUTH, RANGE 1 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Preliminary to the resurvey the lines of the original survey and resurveys were retraced and a diligent search was made for any evidence of the original and resurvey field note records. Identified corners, when appropriate were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original or resurvey record.

The retracement data were thoroughly verified and only the true line notes are given herein.

The geographic position of the corner of sections 5, 6, 31, and 32, T. 16 and 17 S., R. 1 W., as determined by a tie made to National Geodetic Survey Triangulation Station "YUBA" is as follows:

Latitude 39° 21'58.21" N. Longitude 111° 57'28.86" W.
N.A.D. 1927

The mean magnetic declination as projected from the U.S. Geological Survey Magnetic Declination Map of 1990 is 13 1/2° E.

Retracement of a Portion of the West Boundary,
T. 16 S., R. 1 W., Salt Lake Meridian, Utah.

Reestablishment of the Survey Executed by F. Dickert in 1898
and Resurveys Executed by G.B. Hatch in 1973
and F.D. Reynolds in 1991

Beginning at the closing corner of sections 6 and 31, T. 17 S. and T. 16 S., R. 1 W., on the west boundary of the township, monumented with an iron post, 2 1/2 ins. diam., extending 6 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey by G.B. Hatch.

From this corner

The 1/4 section corner of section 1 only, T. 17 S., R. 2 W., monumented with an iron post, 2 1/2 ins. diam., set 6 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey by G.B. Hatch, bears S. 0°16.3' W., 2.270 chains distance.

N. 0°16.3' E., on the east boundary of section 1, T. 17 S., R. 2 W.

19.9875 Point for the S 1/16 section corner of section 31 only, falls in Sevier Bridge Reservoir; not monumented.

37.848 Point for the corner of sections 1 and 36, T. 16 and 17 S., R. 2 W. falls in Sevier Bridge Reservoir; not monumented.

RETRACEMENT OF A PORTION OF THE WEST BOUNDARY,
T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0°16.3' E., on the east boundary of section 36, T. 16 S., R. 2 W.

- 2.127** Point for the 1/4 section corner of section 31 only, falls in Sevier Bridge Reservoir; not monumented.
- 22.1135** Point for the N 1/16 section corner of section 31 only, falls in Sevier Bridge Reservoir; not monumented.
- 40.098** Point for the 1/4 section corner of section 36 only, T. 16 S., R. 2 W., falls in Sevier Bridge Reservoir; not monumented.
- 42.100** Point for the closing corner of sections 30 and 31, falls in Sevier Bridge Reservoir; not monumented.
- 62.109** Point for the S 1/16 section corner of section 30 only, falls in Sevier Bridge Reservoir; not monumented.
- 80.177** Point for the corner of sections 25 and 36 only, T. 16 S., R. 2 W., falls in Sevier Bridge Reservoir; not monumented.

N. 0°16.3' E., on the east boundary of section 25, T. 16 S., R. 2 W.

- 1.941** Point for the 1/4 section corner of section 30 only, falls in Sevier Bridge Reservoir; not monumented.
- 21.950** Point for the N 1/16 section corner of section 30 only, falls in Sevier Bridge Reservoir; not monumented.
- 40.098** Point for the 1/4 section corner of section 25 only, T. 16 S., R. 2 W., falls in Sevier Bridge Reservoir; not monumented.
- 42.580** Point for the closing corner of sections 19 and 30, falls in Sevier Bridge Reservoir; not monumented.
- 62.5395** Point for the S 1/16 section corner of section 19 only, falls in Sevier Bridge Reservoir; not monumented.
- 80.117** Point for the corner of sections 24 and 25 only, T. 16 S., R. 2 W., falls in Sevier Bridge Reservoir; not monumented.

N. 0°16.3' E., on the east boundary of section 24, T. 16 S., R. 2 W.

RETRACEMENT OF A PORTION OF THE WEST BOUNDARY,
T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

- 2.382** The 1/4 section corner of section 19 only, monumented with an aluminum post, 2 1/2 ins. diam., set 2 ins. above ground, with aluminum cap marked as described in the official record of the 1991 resurvey by F.D. Reynolds.
- 22.340** Point for the N 1/16 section corner of section 19 only; not monumented.
- 40.138** The 1/4 section corner of section 24 only, T. 16 S., R. 2 W., monumented with an iron post, 2 1/2 ins. diam., set 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey by G.B. Hatch.
-
- N. 0°28.6' E., beginning new measurement.
- 2.160** The closing corner of sections 18 and 19 only, monumented with an iron post, 2 1/2 ins. diam., set 2 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey by G.B. Hatch.
- From this corner
- The corner of sections 13 and 24 only, T. 16 S., R. 2 W., monumented with an iron post, 2 1/2 ins. diam., set 8 ins. above ground, with brass cap marked as described in the official record of 1991 resurvey by F.D. Reynolds, bears N. 0°28.6' E., 38.232 chains dist.
-
- Dependent Resurvey of a Portion of the South Boundary,
T. 16 S., R. 1 W., Salt Lake Meridian, Utah.
-
- Reestablishment of the Survey Executed by Stewart and Stewart in
1898 and the Resurvey Executed by G.B. Hatch in 1973
-
- Beginning at the corner of sections 5, 6, 31, and 32, T. 16 and 17 S., R. 1 W., on the south boundary of the township, monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, with brass cap marked as described in the official record of the 1973 resurvey.
- From this corner, U.S. Coast and Geodetic Survey Triangulation Station "YUBA", bears S. 56°25.3' W., 203.079 chains dist.
- N. 89°38.5' W., between sections 6 and 31.
- Over mountainous land, through scattered pinon and juniper growth.
- 19.862** Point for the E 1/16 section corner of sections 6 and 31, not monumented.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

- 39.724** The 1/4 section corner of sections 6 and 31, monumented with an iron post, 2 1/2 ins. in diam., extending 10 ins. above ground, and in a mound of stone, with brass cap marked as described in the official record of the 1973 resurvey.
-
- N. 89°38.7' W., beginning new measurement.
- 19.950** Point for the W 1/16 section corner of sections 6 and 31, falls within the Sevier Bridge Reservoir; not monumented.
- 39.900** Point for the 80 1/16 section corner of sections 6 and 31, falls within the Sevier Bridge Reservoir; not monumented.
- 79.800** The 120 1/16 section corner of sections 6 and 31, monumented with an iron post, 2 1/2 ins. diam., set 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.
-
- N. 89°37.3' W., beginning new measurement.
- 39.910** The 160 1/16 section corner of sections 6 and 31, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.
-
- N. 89°38.4' W., beginning new measurement.
- 39.970** The 200 1/16 section corner of sections 6 and 31, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.
-
- N. 89°37.9' W., beginning new measurement.
- 19.958** The 220 1/16 section corner of sections 6 and 31, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked:

	T16S R1W	
	S31	
1/16	-----	220
	S6	
	T17S R1W	
	1973	

This corner was established by G.B. Hatch in 1973, but not recorded within the field note record. This corner is accepted as the 220 1/16 section corner of sections 6 and 31.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 89°38.1' W., beginning new measurement.

- 19.963** The 240 1/16 section corner of sections 6 and 31, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

N. 89°41.0' W., beginning new measurement.

- 4.992** The closing corner of sections 6 and 31, on the west boundary of the township, hereinbefore described.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 16 S., R. 1 W., Salt Lake Meridian, Utah.

Reestablishment of the Survey Executed by Stewart and Stewart in
1898 and the Resurvey Executed by G.B. Hatch in 1973

From the corner of sections 5, 6, 31, and 32, on the south boundary of the township, hereinbefore described.

N. 0°22.4' W., on the east boundary of section 31.

Over rolling mountainous land, through scattered pinon and juniper growth.

- 20.170** Point for the S 1/16 section corner of section 31 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone to top, with aluminum cap marked:

T16S R1W
S 1/16 |
S31 |
1995

The corner is located on a steep broken W slope.

- 40.340** The 1/4 section corner of section 31 only, monumented with an iron post, 2 1/2 ins. diam., set in a mound of stone, with brass cap marked as described in the official record of the 1973 resurvey.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0°55.9' W., beginning new measurement.

0.300 The 1/4 section corner of section 32 only, monumented with an iron post, 2 1/2 ins. diam., set in a mound of stone, with brass cap marked as described in the official record of the 1973 resurvey.

39.935 The corner of sections 29 and 31, on the east boundary of section 31, monumented with an iron post, 2 1/2 ins. diam., extending 10 ins. above ground and in a mound of stone, with brass cap marked as described in the official record of the 1973 resurvey.

S. 89°28.9' W., on the north boundary of section 31.

Over rolling mountainous land, through scattered pinon and juniper growth.

5.918 The closing corner of sections 29 and 30 only, monumented with an iron post, 2 1/2 ins. diam., set in a mound of stone, with brass cap marked as described in the official record of the 1973 resurvey.

39.983 The 1/4 section corner of section 31 only, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

N. 89°34.6' W., beginning new measurement.

5.785 The 1/4 section corner of section 30 only, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

N. 89°33.1' W., beginning new measurement.

19.900 The W 1/16 section corner of section 30 only, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

N. 89°31.1' W., beginning new measurement.

14.108 The 80 1/16 section corner of section 31 only, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

- N. 89°35.1' W., beginning new measurement.
- 5.799** Point for the 80 1/16 section corner of section 30 only, falls within the Sevier Bridge Reservoir; not monumented.
- 39.734** Point for the 120 1/16 section corner of section 31 only, falls within the Sevier Bridge Reservoir; not monumented.
- 45.573** The 120 1/16 section corner of section 30 only, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.
-
- N. 89°33.1' W., beginning new measurement.
- 19.901** Point for the 140 1/16 section corner of section 30 only, falls within the Sevier Bridge Reservoir; not monumented.
- 33.918** The 160 1/16 section corner of section 31 only, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.
-
- N. 89°40.1' W., beginning new measurement.
- 5.888** The 160 1/16 section corner of section 30 only, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.
-
- N. 89°32.1' W., beginning new measurement.
- 33.871** Point for the 200 1/16 section corner of section 31 only, falls within the Sevier Bridge Reservoir; not monumented.
- 39.793** Point for the 200 1/16 section corner of section 30 only, falls within the Sevier Bridge Reservoir; not monumented.
- 73.643** Point for the 240 1/16 section corner of section 31 only, falls within the Sevier Bridge Reservoir; not monumented.
- 77.814** Point for the closing corner of sections 30 and 31, on the west boundary of the township, hereinbefore described.
-

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the closing corner of sections 29 and 30, on the north boundary of section 31.

N. 0°38.9' W., between sections 29 and 30.

Over rolling mountainous land, through lightly scattered pinon and juniper growth.

20.129 The S 1/16 section corner of sections 29 and 30, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

N. 0°35.1' W., beginning new measurement.

20.180 The 1/4 section corner of sections 29 and 30, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

N. 0°18.7' W., beginning new measurement.

40.120 The corner of sections 19, 20, 29, and 30, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

S. 89°24.4' W., between sections 19 and 30.

Over rolling mountainous land, through pinon and juniper growth.

20.108 Point for the E 1/16 section corner of sections 19 and 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked.

	T16S R1W
E 1/16	<u>S19</u>
	S30
	1995

Set a steel fence post alongside the aluminum post.

40.216 The 1/4 section corner of sections 19 and 30, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 89°25.5' W., beginning new measurement.

39.730 The 80 1/16 section corner of sections 19 and 30, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

N. 89°26.0' W., beginning new measurement.

19.878 The 100 1/16 section corner of sections 19 and 30, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

N. 89°25.9' W., beginning new measurement.

19.883 The 120 1/16 section corner of sections 19 and 30, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

N. 89°25.5' W., beginning new measurement.

39.748 The 160 1/16 section corner of sections 19 and 30, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

N. 89°26.5' W., beginning new measurement.

19.860 The 180 1/16 section corner of sections 19 and 30, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

N. 89°28.5' W., beginning new measurement.

19.888 The 200 1/16 section corner of sections 19 and 30, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

N. 89°27.1' W., beginning new measurement.

36.762 Point for the closing corner of sections 19 and 30, on the west boundary of the township, hereinbefore described.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the corner of sections 19, 20, 29, and 30.

N. 1°55.0' W., between sections 19 and 20.

Over gentle rolling land.

- 20.476** The S 1/16 section corner of sections 19 and 20, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

N. 1°55.0' W., beginning new measurement.

- 20.471** The 1/4 section corner of sections 19 and 20, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

N. 0°53.6' W., beginning new measurement.

- 19.608** The N 1/16 section corner of section 19 only, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

N. 0°53.5' W., beginning new measurement.

- 1.135** The N 1/16 section corner of section 20 only, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

- 19.614** The corner of sections 18 and 19 only, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

S. 89°18.0' W., between sections 18 and 19.

Over rolling land.

- 20.486** Point for the E 1/16 section corner of sections 18 and 19.
Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T16S R1W

E 1/16

S18

S19

1995

Set a steel fence post alongside the aluminum post.

The corner is located on a NW slope.

40.972 The 1/4 section corner of sections 18 and 19, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

N. 89°30.2' W., beginning new measurement.

19.802 The W 1/16 section corner of sections 18 and 19, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

N. 89°29.4' W., beginning new measurement.

19.815 The 80 1/16 section corner of sections 18 and 19, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

N. 89°30.3' W., beginning new measurement.

19.802 The 100 1/16 section corner of sections 18 and 19, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

N. 89°28.8' W., beginning new measurement.

19.805 The 120 1/16 section corner of sections 18 and 19, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

N. 89°29.4' W., beginning new measurement.

39.614 The 160 1/16 section corner of sections 18 and 19, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 89°29.5' W., beginning new measurement.

39.607

The 200 1/16 section corner of sections 18 and 19, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

N. 89°28.8' W., beginning new measurement.

34.114

The closing corner of sections 18 and 19, on the west boundary of the township, hereinbefore described.

The Subdivision of Section 19,
T. 16 S., R. 1 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 19 and 30.

N. 1°57.8' W., on the N - S center line of section 19.

Over rolling mountainous land, through scattered pinon and juniper growth.

20.730

Point for the center S 1/16 section corner of section 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T16S R1W
C
S 1/16 | S19
C
1995

Set a steel fence post alongside the aluminum post.

41.460

Point for the center 1/4 section corner, at intersection with the E - W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, and in a mound of stone to top, with aluminum cap marked:

T16S R1W
C 1/4 S19
1995

Set a steel fence post alongside the aluminum post.

The corner is located on a W slope.

THE SUBDIVISION OF SECTION 19,
T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS**60.782**

Point for the center N 1/16 section corner of section 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T16S R1W
C
N 1/16 | S19
C
1995

Set a steel fence post alongside the aluminum post.

80.104

The 1/4 section corner of sections 18 and 19.

From the 1/4 section corner of sections 19 and 20.

N. 89°52.7' W., on the E - W center line of section 19.

Over rolling mountainous land, through scattered pinon and juniper growth.

19.400

Point for the center E 1/16 section corner of section 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T16S R1W
C ——— E 1/16 ——— C
S19
1995

Set a steel fence post alongside the aluminum post.

40.260

The center 1/4 section corner of section 19.

79.930

Point for the center 80 1/16 section corner of section 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T16S R1W
C ——— 80 1/16 ——— C
S19
1995

Set a steel fence post alongside the aluminum post.

THE SUBDIVISION OF SECTION 19,
T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

The corner is located on a SW slope.

99.765 Point for the center 100 1/16 section corner of section 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T16S R1W
C — $\frac{100 \frac{1}{16}}{S19}$ — C
1995

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level sagebrush flat.

119.600 Point for the center 120 1/16 section corner of section 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T16S R1W
C — $\frac{120 \frac{1}{16}}{S19}$ — C
1995

Set a steel fence post alongside the aluminum post.

The corner is located in rolling foothills.

179.105 Point for the center 180 1/16 section corner of section 19; not monumented.

234.365 The 1/4 section corner of section 19 only, on the west boundary of the township, hereinbefore described.

From the center E 1/16 section corner of section 19.

N. 2°29.8' W., on the N - S center line of the NE 1/4 of section 19.

19.480 Point for the NE 1/16 section corner at intersection with the E - W center line of the NE 1/4 of section 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

THE SUBDIVISION OF SECTION 19,
T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T16S R1W
NE 1/16 S19
1995

Set a steel fence post alongside the aluminum post.

38.957 The E 1/16 section corner of sections 18 and 19.

From the N 1/16 section corner of section 19 only, on the east boundary of section 19.

S. 89°43.2' W., on the E - W center line of the NE 1/4 of section 19.

19.943 The NE 1/16 section corner of section 19.

40.616 The center N 1/16 section corner of section 19.

From the E 1/16 section corner of sections 19 and 30.

N. 0°55.5' W., on the N - S center line of the SE 1/4 of section 19.

20.596 Point for the SE 1/16 section corner at intersection with the E - W center line of the SE 1/4 of section 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T16S R1W
SE 1/16 S19
1995

Set a steel fence post alongside the aluminum post.

41.184 The center E 1/16 section corner of section 19.

From the S 1/16 section corner of sections 19 and 20.

S. 89°46.1' W., on the E - W center line of the SE 1/4 of section 19.

19.754 The SE 1/16 section corner of section 19.

40.238 The center S 1/16 section corner of section 19.

THE SUBDIVISION OF SECTION 19,
T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the 100 1/16 section corner of sections 19 and 30.

N. 1°51.2' W., on the 100 1/16 line of the SW 1/4 of section 19.

20.501

Point for the S 100 1/16 section corner, at intersection with the E - W center line of the SW 1/4 of section 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

$$\begin{array}{r} \text{T16S R1W} \\ \text{S } \frac{1/16}{\text{S19}} \text{ 100} \\ \text{1995} \end{array}$$

Set a steel fence post alongside the aluminum post.

40.997

The center 100 1/16 section corner of section 19.

From the 180 1/16 sec. cor. of secs. 19 and 30.

N. 0°41.1' W., on the 180 1/16 line of the SW 1/4 of section 19.

20.186

Point for the S 180 1/16 section corner at intersection with the E - W center line of the SW 1/4 of section 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

$$\begin{array}{r} \text{T16S R1W} \\ \text{S } \frac{1/16}{\text{S19}} \text{ 180} \\ \text{1995} \end{array}$$

Set a steel fence post alongside the aluminum post.

40.372

Point for the center 180 1/16 section corner of section 19.

From the center S 1/16 section corner of section 19.

N. 89°39.5' W., on the E - W center line of the SW 1/4 of section 19.

59.556

The S 100 1/16 section corner of section 19.

138.971

The S 180 1/16 section corner of section 19.

THE SUBDIVISION OF SECTION 19,
T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS**194.926**

Point for the S 1/16 section corner of section 19 only, on the west boundary of the township, hereinbefore described.

From the center 100 1/16 section corner of section 19.

N. 1°49.3' W., on the 100 1/16 line of the NW 1/4 of section 19.

19.520

Point for the N 100 1/16 section corner at intersection with the E - W center line of the NW 1/4 of section 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

$$\begin{array}{c} \text{T16S R1W} \\ \text{N } \frac{1/16}{\text{S19}} \text{ 100} \\ \text{1995} \end{array}$$

Set a steel fence post alongside the aluminum post.

39.021

The 100 1/16 section corner of sections 18 and 19.

From the center 120 1/16 section corner of section 19.

N. 1°46.4' W., on the 120 1/16 line of the NW 1/4 of section 19.

19.586

Point for the N 120 1/16 section corner at intersection with the E - W center line of the NW 1/4 of section 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

$$\begin{array}{c} \text{T16S R1W} \\ \text{N } \frac{1/16}{\text{S19}} \text{ 120} \\ \text{1995} \end{array}$$

Set a steel fence post alongside the aluminum post.

39.156

The 120 1/16 section corner of sections 18 and 19.

From the center N 1/16 section corner of section 19.

N. 89°41.2' W., on the E - W center line of the NW 1/4 of section 19.

THE SUBDIVISION OF SECTION 19,
T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

- 59.462** The N 100 1/16 section corner of section 19.
- 79.281** The N 120 1/16 section corner of section 19.
- 193.332** Point for the N 1/16 section corner of section 19 only, on the west boundary of the township, hereinbefore described.

The Subdivision of Section 30,
T. 16 S., R. 1 W., Salt Lake Meridian, Utah

- From the 1/4 section corner of section 30 only, on the south boundary of the section.
N. 0°44.0' W., on the N - S center line of section 30.
- 20.376** Point for the center S 1/16 section corner of section 30.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, and in a mound of stone to top, with aluminum cap marked:
- T16S R1W
C
S 1/16 | S30
C
1995
- Set a steel fence post alongside the aluminum post.
- The corner is located on a SW slope, 25 lks. dist., N of a draw, drains NW.
- 40.752** Point for the center 1/4 section corner, at intersection with the E - W center line.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, and in a collar of stone, with aluminum cap marked:
- T16S R1W
C 1/4 S30
1995
- Set a steel fence post alongside the aluminum post.
- The corner is located in a small draw, drains SW.
- 60.163** Point for the center N 1/16 section corner of section 30.

THE SUBDIVISION OF SECTION 30,
T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T16S R1W
C
N 1/16 | S30
C
1995

Set a steel fence post alongside the aluminum post.

The corner is located on the SW slope of a hill.

80.282 The 1/4 section corner of sections 19 and 30.

From the 1/4 section corner of sections 29 and 30.

N. 89°45.6' W., on the E - W center line of section 30.

Over rolling mountainous land, through scattered pinon and juniper growth.

39.932 The center 1/4 section corner of section 30.

59.817 Point for the center W 1/16 section corner of section 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T16S R1W
C $\frac{W\ 1/16}{S30}$ C
1995

Set a steel fence post alongside the aluminum post.

79.702 Point for the center 80 1/16 section corner of section 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T16S R1W
C $\frac{1/16}{S30}$ 80
1995

Set a steel fence post alongside the aluminum post.

THE SUBDIVISION OF SECTION 30,
T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

The corner is located in the head of a small draw, drains SW.

119.472 Point for the center 120 1/16 section corner of section 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

$$C \quad \frac{T16S \ R1W}{\frac{1/16}{S30}} \quad 120$$

1995

Set a steel fence post alongside the aluminum post.

139.357 Point for the center 140 1/16 section corner of section 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

$$C \quad \frac{T16S \ R1W}{\frac{1/16}{S30}} \quad 140$$

1995

Set a steel fence post alongside the aluminum post.

159.242 Point for the center 160 1/16 section corner of section 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

$$C \quad \frac{T16S \ R1W}{\frac{1/16}{S30}} \quad 160$$

1995

Set a steel fence post alongside the aluminum post.

179.127 Point for the center 180 1/16 section corner of section 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

$$C \quad \frac{T16S \ R1W}{\frac{1/16}{S30}} \quad 180$$

1995

THE SUBDIVISION OF SECTION 30,
T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a steel fence post alongside the aluminum post.

199.012

Point for the center 200 1/16 section corner of section 30, falls within the Sevier Bridge Reservoir; not monumented.

236.396

Point for the 1/4 section corner of section 30 only, on the west boundary of the township, hereinbefore described.

From the W 1/16 section corner of section 30 only, on the south boundary of the section.

N. 0°43.0' W., on the N - S center line of the SW 1/4 of section 30.

20.340

Point for the SW 1/16 section corner at intersection with the E - W center line of the SW 1/4 of section 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T16S R1W
SW 1/16 S30
1995

Set a steel fence post alongside the aluminum post.

The corner is located in a large sandy draw, drains SW.

40.679

The center W 1/16 section corner of section 30.

From the point for the 80 1/16 section corner of section 30 only, on the south boundary of the section.

N. 0°41.3' W., on the 80 1/16 section line of the SW 1/4 of section 30.

20.303

Point for the S 80 1/16 section corner at intersection with the E - W center line of the SW 1/4 of section 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T16S R1W
S $\frac{1}{16}$ 80
S30
1995

THE SUBDIVISION OF SECTION 30,
T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a steel fence post alongside the aluminum post.

The corner is located on a rolling W slope.

40.605 The center 80 1/16 section corner of section 30.

From the 120 1/16 section corner of section 30 only, on the south boundary of the section.

N. 0°41.1' W., on the 120 section line of the SW 1/4 of section 30.

20.257 Point for the S 120 1/16 section corner at intersection with the E - W center line of the SW 1/4 of section 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T16S R1W	
S	<u>1/16</u>	120
	S30	
	1995	

Set a steel fence post alongside the aluminum post.

40.485 The center 120 1/16 section corner of section 30.

From the point for the 140 1/16 section corner of section 30 only, on the south boundary of the section.

N. 0°40.4' W., on the 140 section line of the SW 1/4 of section 30.

20.220 Point for the S 140 1/16 section corner, at intersection with the E - W center line of the SW 1/4 of section 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T16S R1W	
S	<u>1/16</u>	140
	S30	
	1995	

Set a steel fence post alongside the aluminum post.

The corner falls on nearly level desert land.

THE SUBDIVISION OF SECTION 30,
T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

- 40.411** The center 140 1/16 section corner of section 30.
-
- From the center S 1/16 section corner of section 30.
- N. 89°39.4' W., on the E - W center line of the SW 1/4 of section 30.
- 19.893** The SW 1/16 section corner of section 30.
- 39.782** The S 80 1/16 section corner of section 30.
- 79.561** The S 120 1/16 section corner of section 30.
- 99.455** The S 140 1/16 section corner of section 30.
- 196.834** The point for the S 1/16 section corner of section 30 only, on the west boundary of the township, hereinbefore described.
-
- From the center 120 1/16 section corner of section 30.
- N. 0°39.8' W., on the 120 section line of the NW 1/4 of section 30.
- 19.654** Point for the N 120 1/16 section corner, at intersection with the E - W center line of the NW 1/4 of section 30.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:
- | | | |
|---|-------------|-----|
| | T16S R1W | |
| N | <u>1/16</u> | 120 |
| | S30 | |
| | 1995 | |
- Set a steel fence post alongside the aluminum post.
- 39.979** The 120 1/16 section corner of sections 19 and 30.
-
- From the center 180 1/16 section corner of section 30.
- N. 0°35.8' W., on the 180 section line of the NW 1/4 of section 30.
- 19.837** Point for the N 180 1/16 section corner, at intersection with the E - W center line of the NW 1/4 of section 30.

THE SUBDIVISION OF SECTION 30,
T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T16S R1W
N $\frac{1/16}{S30}$ 180
1995

Set a steel fence post alongside the aluminum post.

40.325 The 180 1/16 section corner of sections 19 and 30.

From the point for the center 200 1/16 section corner of section 30.

N. 0°36.0' W., on the 200 1/16 section line of the NW 1/4 of section 30.

19.897 Point for the N 200 1/16 section corner, at intersection with the E - W center line of the NW 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T16S R1W
N $\frac{1/16}{S30}$ 200
1995

Set a steel fence post alongside the aluminum post.

The corner is located 50 lks. dist., E of the high water mark of Sevier Bridge Reservoir, bears NW and SE.

40.427 The 200 1/16 section corner of sections 19 and 30.

From the center N 1/16 section corner of section 30.

N. 89°35.2' W., on the E - W center line of the NW 1/4 of section 30.

79.516 The N 120 1/16 section corner of section 30.

139.148 The N 180 1/16 section corner of section 30.

159.035 The N 200 1/16 section corner of section 30.

196.113 Point for the N 1/16 section corner of section 30 only, on the west boundary of the township, hereinbefore described.

THE SUBDIVISION OF SECTION 31,
T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

The Subdivision of Section 31
T. 16 S., R. 1 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 6 and 31 on the south boundary of the township, hereinbefore described.

N. 0°50.8' W., on the N - S center line of section 31.

Over mountainous land, through scattered pinon and juniper growth.

20.149 Point for the center S 1/16 section corner of section 31.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, and in a mound of stone to top, with aluminum cap marked:

T16S R1W
C
S 1/16 | S31
C
1995

The corner is located on the NE slope of a hill, 50 lks. dist., N of the top of a ridge, bears NW and SE.

40.298 Point for the center 1/4 section corner, at intersection with the E - W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T16S R1W
C 1/4 S31
1995

Set a steel fence post alongside the aluminum post.

59.982 Point for the center N 1/16 section corner of section 31.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T16S R1W
C
N 1/16 | S31
C
1995

Set a steel fence post alongside the aluminum post.

THE SUBDIVISION OF SECTION 31,
T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

The corner is located on a gentle NW slope.

79.666

The 1/4 section corner of section 31 only, on the north boundary of the section.

From the 1/4 section corner of section 31 only, on the east boundary of the section.

N. 89°43.4' W., on the E - W center line of section 31.

20.027

Point for the center E 1/16 section corner of section 31.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

$$\begin{array}{c} \text{T16S R1W} \\ \text{C } \frac{\text{E } 1/16}{\text{S31}} \text{ C} \\ 1995 \end{array}$$

Set a steel fence post alongside the aluminum post.

40.054

The center 1/4 section corner of section 31.

59.974

Point for the center W 1/16 section corner of section 31.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

$$\begin{array}{c} \text{T16S R1W} \\ \text{C } \frac{\text{W } 1/16}{\text{S31}} \text{ C} \\ 1995 \end{array}$$

Set a steel fence post alongside the aluminum post.

79.894

Point for the 80 1/16 section corner of section 31, falls within the Sevier Bridge Reservoir; not monumented.

119.734

Point for the center 120 1/16 section corner of section 31, falls within the Sevier Bridge Reservoir; not monumented.

159.574

Point for the center 160 1/16 section corner of section 31, falls within the Sevier Bridge Reservoir; not monumented.

199.414

Point for the center 200 1/16 section corner of section 31, falls within the Sevier Bridge Reservoir; not monumented.

THE SUBDIVISION OF SECTION 31,
T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS**219.334**

Point for the center 220 1/16 section corner of section 31, falls within the Sevier Bridge Reservoir; not monumented.

243.836

Point for the 1/4 section corner of section 31 only, on the west boundary of the township, hereinbefore described.

From the point for the E 1/16 section corner of sections 6 and 31, on the south boundary of the township, hereinbefore described.

N. 0°36.6' W., on the N - S center line of the SE 1/4 of section 31.

20.159

Point for the SE 1/16 section corner, at intersection with the E - W center line of the SE 1/4 of section 31.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T16S R1W
SE 1/16 S31
1995

Set a steel fence post alongside the aluminum post.

40.318

The center E 1/16 section corner of section 31.

From the S 1/16 section corner of section 31 only, on the east boundary of the section.

N. 89°40.4' W., on the E - W center line of the SE 1/4 of section 31.

19.945

The SE 1/16 section corner of section 31.

39.890

The center S 1/16 section corner of section 31.

From the point for the W 1/16 section corner of sections 6 and 31, on the south boundary of the township, hereinbefore described.

N. 0°48.5' W., on the N - S center line of the SW 1/4 of section 31.

20.140

Point for the SW 1/16 section corner, at intersection with the E - W center line of the SW 1/4 of section 31.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 31,
T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T16S R1W
SW 1/16 S31
1995

Set a steel fence post alongside the aluminum post.

40.274 The center W 1/16 section corner of section 31.

From the 120 1/16 section corner of sections 6 and 31, on the south boundary of the township, hereinbefore described.

N. 0°41.7' W., on the 120 1/16 section line of the SW 1/4 of section 31.

20.108 Point for the S 120 1/16 section corner, at intersection with the E - W center line of the SW 1/4 of section 31.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T16S R1W
S $\frac{1/16}{S31}$ 120
1995

Set a steel fence post alongside the aluminum post.

The corner is located on a steep N slope, 60 lks. dist., S of the high water mark of the Sevier Bridge Reservoir, bears NE and SW in cove.

40.194 Point for the center 120 1/16 section corner of section 31.

From the 220 1/16 section corner of sections 6 and 31, on the south boundary of the township, hereinbefore described.

N. 0°22.1' W., on the 220 1/16 section line of the SW 1/4 of section 31.

20.010 Point for the S 220 1/16 section corner, at intersection with the E - W center line of the SW 1/4 of section 31.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T16S R1W
S $\frac{1/16}{S31}$ 220
1995

THE SUBDIVISION OF SECTION 31,
T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a steel fence post alongside the aluminum post.

The corner is located 55 lks. dist., S of the high water mark of Sevier Bridge Reservoir, bears E and W.

40.016 The point for the center 220 1/16 section corner of section 31.

From the center S 1/16 section corner of section 31.

N. 89°40.9' W., on the E - W center line of the SW 1/4 of section 31.

19.934 The SW 1/16 section corner of section 31.

79.736 The S 120 1/16 section corner of section 31.

179.454 The S 220 1/16 section corner of section 31.

204.182 Point for the S 1/16 section corner of section 31 only, on the west boundary of the township, hereinbefore described.

From the point for the center 80 1/16 section corner of section 31.

N. 0°46.9' W., on the N 80 1/16 section line of the NW 1/4 of section 31.

39.485 The 80 1/16 section corner of section 31 only on the north boundary of the section.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Philip Tobler	Surveying Technician

CERTIFICATE OF SURVEY

I, *Ferrel D. Reynolds, Cadastral Surveyor*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *1st day of March, 1993*, I have *retraced a portion of the west boundary, dependently resurveyed portions of the south boundary, and subdivisional lines, and subdivided sections 19, 30, and 31, in Township 16 South, Range 1 West,*

of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

April 10, 1997

Date



(Cadastral Surveyor)

Date

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the *retracement of a portion of the wset boundary, dependent resurvey of portions of the south boundary, and subdivisional lines, and the subdivision of sections 19, 30, and 31, in Township 16 South, Range 1 West, Salt Lake Meridian, Utah,*

executed by *Ferrel D. Reynolds, Cadastral Surveyor*

having been critically examined and found correct, are hereby approved.

April 24, 1997

Date



(Chief Cadastral Surveyor for Utah)