

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF
THE DEPENDENT RESURVEY OF

OF

PORTIONS OF THE SOUTH BOUNDARY

AND SUBDIVISIONAL LINES,

AND THE

SUBDIVISION OF SECTIONS 9, 15, 21, 22, 27, 28, AND 34

IN

TOWNSHIP 8 SOUTH, RANGE 19 WEST

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Larry V. Judd
Cadastral Surveyor

Under special instructions dated *March 1, 1993*, approved *March 23, 1993*, which provided for the surveys included under Group Number 796, and assignment instructions dated *March 23, 1993*.

Survey commenced *April 12, 1993*

Survey completed *May 20, 1993*

INDEX DIAGRAM

Township 8 South , Range 19 West

6	5 28	29 4 27 28	19 3 18 18	10 2 9	1
7	8 26	27 9 25 26	17 10 16 16	9 11 8	12
18	17	25 16 24 24	15 15 14 15	8 14 7	13
19	20 23	23 21 22 22	14 22 12 13	7 23 7	24
30	29	21 28 20 21	12 27 11 12	6 26 6	25
31	32	19 33 4 4	10 34 3 3	5 35 2	36

The Subdivision of Section 9.....Page 29

The Subdivision of Section 15.....Page 30

The Subdivision of Section 21.....Page 31

The Subdivision of Section 22.....Page 33

The Subdivision of Section 27.....Page 34

The Subdivision of Section 28.....Page 35

The Subdivision of Section 34.....Page 36

TOWNSHIP 8 SOUTH, RANGE 19 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

The following field notes describe the dependent resurvey of a portion of the south boundary and subdivisional lines and the subdivision of sections 9, 15, 21, 22, 27, 28, and 34, in T. 8 South, Range 19 West, Salt Lake Meridian, Utah.

History of Surveys

		<u>Surveyed by</u>		<u>Retr. or Resurveyed by</u>	
<u>NORTH BOUNDARY</u>					
All	T.C. Bailey	1882			
All			L.H. Godwin and W.H. Sylvester	1958	
<u>SOUTH BOUNDARY</u>					
Portion	J. Gorlinski	1875	T.C. Bailey	1882	
All	T.C. Bailey	1882			
<u>EAST BOUNDARY</u>					
All	T.C. Bailey	1882			
All			A. Nelson	1925	
<u>WEST BOUNDARY</u>					
All	T.C. Bailey	1882			
Portion			A.J. Stookey	1899	
<u>SUBDIVISION</u>					
All	T.C. Bailey	1882			

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group 796 Utah, dated March 1, 1993.

The directions of lines were determined by references to true meridians established on line by hour angle observations on Polaris. The lines were carried forward by sustained angulations, being supplemented by other observations taken throughout the progress of the survey. Distances were determined by electronic measurement.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. The retracement data were thoroughly verified and only the true line notes are given herein.

TOWNSHIP 8 SOUTH, RANGE 19 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

The geographic position of the corner of sections 2, 3, 34, and 35, on the south boundary, Tps. 8 and 9 S., R. 19 W., as determined by the Global Positioning System, static relative positioning techniques, utilizing U.S. Geological Survey triangulation stations "SHERIDAN" and "INDIAN". This corner is now a B.L.M. control station and the coordinates are as follows:

Latitude $40^{\circ} 04' 47.89''$ N. Longitude $113^{\circ} 57' 49.05''$ W.
N.A.D. 1927

The mean magnetic declination as projected from the U.S. Geological Survey "Magnetic Declination Map of 1990" is: $14 \frac{1}{2}^{\circ}$ East.

Dependent Resurvey of a Portion of the South Boundary,
T. 8 S., R. 19 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
T.C. Bailey, Deputy Surveyor in 1882

Beginning at the corner of sections 2, 3, 34, and 35, on the south boundary of Tps. 8 and 9 S., R. 19 W., monumented with an limestone, 24x12x8 ins., plainly marked 4 notches on one side and 1 notch on the opposite side, laying loose on top of the ground, next to a steel fence post, projecting 12 ins. above ground, with buried mound of stone around the fence post (record; limestone, 20x12x10 ins.).

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over the top of the steel fence post with aluminum cap marked:

T8S R19W	
S34	S35
S3	S2
T9S	
1993	

Raise a mound of stone, 3 ft. base, 2 ft. high, West of the corner.

Buried the marked stone alongside the aluminum post.

This corner will now function as a B.L.M. control station, hereinafter described.

N. $88^{\circ} 57'$ W., between sections 3 and 34.

Over open desert land.

3.10 Center line of Pony Express dirt road, 30 lks. wide, course N. 64° E. and S. 64° W.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 8 S., R. 19 W., SALT LAKE MERIDIAN, UTAH

CHAINS

18.85

Center line of paved Ibapah - Goshute road, 38 lks. wide, course N. 5° 15' E. and S. 5° 15' W.

19.93

Point for the E 1/16 section corner of sections 3 and 34.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T8S R19W
E 1/16	<u>S34</u>
	S3
	T9S
	1993

Raise a mound of stone, 3 1/2 ft. base, 2 ft. high, North of the corner.

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

39.86

Point for the 1/4 section corner of sections 3 and 34, at proportionate distance; there is no remaining evidence of the original corner (record: limestone, 10x12x8 ins.).

Set an aluminum post 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground over the top of a steel fence post, 6 ft. long, driven 5 1/2 ft. in the ground, and in a mound of stone, 4 1/2 feet base to top of aluminum cap marked:

	T8S R19W
1/4	<u>S34</u>
	S3
	T9S
	1993

The corner falls in a marshy area, set in 5 ins. of standing water.

79.72

The corner of sections 3, 4, 33, and 34, monumented with a basalt stone, 14x12x10 ins., lying loose next to a rebar 5/8 in. diam., set in a mound of stone, in a new N and S fence line (record: limestone, 14x12x12 ins.).

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T8S R19W
<u>S33</u>	<u>S34</u>
S4	S3
	T9S
	1993

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 8 S., R. 19 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Raise a mound of stone, 1 ft. base, 1 ft. high, South of the corner.

Buried the marked stone alongside the aluminum post.

N. $89^{\circ} 47'$ W., between sections 4 and 33.

Over open desert land.

40.17

The 1/4 section corner of sections 4 and 33, monumented with a basalt stone, 14x14x12 ins., laying loose in a scattered mound of stone, dimly marked 1/4 on one side (record: limestone, 20x14x14 ins.).

At the corner point.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T8S R19W
1/4	<u>S33</u>
	S4
	T9S
	1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 2 ft. base, 2 ft. high, North of the corner.

The corner falls on rolling open terrain in sagebrush.

S. $89^{\circ} 59.5'$ W., beginning new measurement.

40.055

The corner of sections 4, 5, 32, and 33, monumented with a basalt stone, 12x8x6 ins., firmly set, plainly marked with only 4 notches visible on one edge (record: limestone, 16x12x10 ins.).

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T8S R19W	
	<u>S32</u>	<u>S33</u>
	S5	S4
	T9S	
	1993	

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 8 S., R. 19 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 3 1/2 ft. base, 2 ft. high, North of the corner.

The corner falls on a gradual easterly slope.

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 8 S., R. 19 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
T.C. Bailey, Deputy Surveyor, in 1882

From the corner of sections 2, 3, 34, and 35, hereinbefore described.

N. 0° 07' E., between sections 34 and 35.

Over open rolling desert land.

1.50 Center line of Pony Express dirt road, 30 lks. wide, course N. 64° E. and
S. 64° W.

40.43 The 1/4 section corner of sections 34 and 35, monumented with a limestone, 14x8x6
ins., loosely set in the ground, dimly marked 1/4 on the W. face (record: limestone,
12x8x6 ins.).

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with
aluminum cap marked:

T8S R19W
1/4
S34 | S35
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 1 ft. high, West of the corner.

The corner falls on a gradual southerly slope, in sagebrush.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 8 S., R. 19 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0° 33' E., beginning new measurement.

20.40

Point for the N 1/16 section corner of sections 34 and 35.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T8S R19W
N 1/16
S34 | S35
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Raise a mound of stone, 3 ft. base, 1 ft. high, West of the corner.

The corner falls on flat open ground.

40.80

The corner of sections 26, 27, 34, and 35, monumented with a limestone, 10x8x6 ins., plainly marked with 2 notches on the E. edge and 1 notch on the S. edge, found laying loose in a mound of stone (record: limestone, 12x8x6 ins.).

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T8S R19W
S27 | S26
S34 | S35
1993

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, West of the corner.

The corner falls 4 lks. south of an E and W fence line.

N. 2° 05' W., between sections 26 and 27.

Over open rolling desert land.

39.455

The 1/4 section corner of sections 26 and 27, monumented with a limestone, 12x8x8 ins., firmly set, plainly marked 1/4 on the W. face (record: limestone, 18x8x8 ins.).

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 8 S., R. 19 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T8S R19W
1/4
S27 | S26
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 1 ft. high, West of the corner.

The corner falls on a gradual southerly slope, in sagebrush.

N. 1° 59.5' E., beginning new measurement.

40.675 The corner of sections 22, 23, 26, and 27, monumented with a limestone, 15x10x5 ins., firmly set, plainly marked with 2 notches on the S., and 2 notches on the E. edges, set in a mound of stone (record: limestone, 14x10x8 ins.).

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T8S R19W
S22 | S23
S27 | S26
1993

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, West of the corner.

N. 0° 33' W., between sections 22 and 23.

Over open rolling desert land.

39.375 The 1/4 section corner of sections 22 and 23, monumented with a limestone, 16x16x8 ins., firmly set, dimly marked 1/4 on the W. face (record: limestone, 18x15x12 ins.).

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 8 S., R. 19 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T8S R19W
1/4
S22 | S23
1993

Deposit a clear "Deep-1 magnet" and a glass bottle at the base of the aluminum post.

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, West of the corner.

The corner falls on a gradual southerly slope, in sagebrush.

N. 1° 24' E., beginning new measurement.

40.525 The corner of sections 14, 15, 22, and 23, monumented with a limestone 13x8x8 ins., firmly set, plainly marked with 3 notches on the S. and 2 notches on the E. edges (record: limestone, 10x10x10 ins.).

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T8S R19W
S15 | S14
S22 | S23
1993

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, West of the corner.

The corner falls on open ground in sagebrush.

N. 1° 05' W., between sections 14 and 15.

Over open rolling desert land.

39.915 The 1/4 section corner of sections 14 and 15, monumented with a limestone, 10x8x7 ins., firmly set, plainly marked 1/4 on the W. face, set in a small mound (record: limestone, 10x10x6 ins.).

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 8 S., R. 19 W., SALT LAKE MERIDIAN, UTAH

CHAINS

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T8S R19W
1/4
S15 | S14
1993

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 1 1/2 ft. base, 1 ft. high, West of the corner.

The corner falls on open ground in sagebrush.

N. 1° 21.5' E., beginning new measurement.

40.35

The corner of sections 10, 11, 14, and 15, monumented with a limestone, 12x10x8 ins., firmly set, plainly marked with 4 notches on the S. and 2 notches on the E. edges, set in a small mound of stone (record: limestone, 12x8x6 ins.).

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T8S R19W
S10 | S11
S15 | S14
1993

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 1 ft. high, West of the corner.

The corner falls on flat open ground in sagebrush.

N. 0° 29' W., between sections 10 and 11.

Over open rolling desert land.

40.19

The 1/4 section corner of sections 10 and 11, monumented with a limestone, 10x8x6 ins., firmly set, dimly marked 1/4 on the W. face, set in a scattered mound of stone (record: limestone, 10x10x8 ins.).

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 8 S., R. 19 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T8S R19W
1/4
S10 | S11
1993

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 2 ft. base, 1 ft. high, West of the corner.

The corner falls on open ground in sagebrush.

N. 6° 31' W., beginning new measurement.

39.795 The corner of sections 2, 3, 10, and 11, monumented with a limestone, 17x10x8 ins., firmly set, plainly marked with 5 notches on the S. and 2 notches on the E. edges, set in a small scattered mound of stone (record: limestone, 18x10x8 ins.).

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T8S R19W
S3 | S2
S10 | S11
1993

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 4 ft. base, 2 1/2 ft. high, West of the corner.

The corner falls in a saddle of a ridge.

N. 5° 52' E., between sections 2 and 3.

Over open rolling desert land.

40.885 The 1/4 section corner of sections 2 and 3, monumented with a lava stone, 15x12x9 ins., firmly set, plainly marked 1/4 on the W. face, set in a small mound of stone (record: limestone, 15x12x8 ins.).

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 8 S., R. 19 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T8S R19W
1/4
S3 | S2
1993

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, West of the corner.

The corner falls on flat ground in sagebrush.

N. 0° 39' W., beginning new measurement.

40.205 The corner of sections 2, 3, 34, and 35, on the north boundary of the township, monumented with an iron post 2 1/2 ins. diam., firmly set, in a mound of stone, with brass cap marked as described in the official record of the resurvey executed by L.H. Godwin and W.H. Silvester, Cadastral Surveyors, in 1958.

The corner is set on top of a ridge, bears NW and SE.

From the corner of sections 3, 4, 33, and 34, on the south boundary of the township, hereinbefore described.

N. 0° 16' W., between sections 33 and 34.

Over flat open range land.

39.96 The 1/4 section corner of sections 33 and 34, monumented with a basalt stone, 12x10x6 ins. laying loose in a mound of stone and plainly marked 1/4 (record: limestone, 14x10x6 ins.).

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, in a collar of stone, with aluminum cap marked:

T8S R19W
1/4
S33 | S34
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Buried the marked stone alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 8 S., R. 19 W., SALT LAKE MERIDIAN, UTAH

CHAINS

The corner falls 1 lk. E. of a fence projecting N. and S.

North, beginning new measurement.

39.99 New fence, bears W.

40.055 Point for the corner of sections 27, 28, 33, and 34, at proportionate distance latitudinally between found original corners and longitudinally at the extension of old N and S fence. There was no remaining evidence of the original corner (record: charred cedar post, 4 ft. long, 4x4 ins.).

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

T8S R19W	
S28	S27
S33	S34
1993	

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 ft. high, West of the corner.

The corner falls in a livestock lane, in line with the N - S fence.

From the corner of sections 26, 27, 34, and 35, hereinbefore described.

N. 89° 49' W., between sections 27 and 34.

Over rolling desert land and fenced pasture and farm ground.

20.095 Point for the E 1/16 section corner of sections 27 and 34.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, in a collar of stone, with aluminum cap marked:

E 1/16	S27
	S34
	1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

The corner falls in a newer E and W fence line.

23.25 Center line of paved Ibapah - Goshute road, 38 lks. wide, course N. 80° W. and S. 80° E.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 8 S., R. 19 W., SALT LAKE MERIDIAN, UTAH

CHAINS

40.04

Log corral fence, projecting N. and S. Set a 6 ft. steel fence post on the W edge of the fence.

40.19

Point for the 1/4 section corner of sections 27 and 34, at proportionate distance. There is no remaining evidence of the original corner (record: limestone, 12x10x8 ins.).

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., flush with the ground, with aluminum cap marked:

	T8S R19W
1/4	<u>S27</u>
	S34
	1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

The corner falls in an old log livestock corral.

80.37

The corner of sections 27, 28, 33, and 34.

N. 0° 04' E., between sections 27 and 28.

Over pasture and farm ground.

40.055

Point for the 1/4 section corner of sections 27 and 28, at proportionate distance. There is no remaining evidence of the original corner (record: charred cedar post, 3 ft. long, 3x3 ins.).

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

	T8S R19W
	1/4
	S28 S27
	1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

The corner falls 6 lks. East of a fence projecting N. and S., set in open pasture land.

80.11

The corner of sections 21, 22, 27, and 28, monumented with a limestone, 10x8x5 ins., laying at the corner of fences E, W and S, plainly marked with 2 notches on one edge and 3 notches on another (record: limestone, 12x8x6 ins.).

At the corner of fences.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 8 S., R. 19 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T8S R19W	
<u>S21</u>	<u>S22</u>
S28	S27
1993	

Buried the marked stone alongside the aluminum post.

Set a steel fence post alongside.

The E and W fence is a newer fence built over the top of an old E and W fence, and the S fence is an older fence.

From the corner of sections 22, 23, 26, and 27.

N. 89° 45' W., between sections 22 and 27.

Over rolling open desert land and pasture ground.

33.20 Center line of paved Ibapah - Goshute road, 38 lks. wide, course N. 3° 45' W. and S. 3° 45' E.

40.03 The 1/4 section corner of sections 22 and 27, monumented with a limestone, 16x10x8 ins., laying loose in a N and S fence line, with no visible scribe marks. This stone has been used by local landowners as the 1/4 section corner (record: limestone, 12x10x10 ins.).

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T8S R19W	
1/4	<u>S22</u>
	S27
1993	

Buried the stone alongside the aluminum post.

The corner falls in the N and S fence line.

N. 89° 52' W., beginning new measurement.

40.19 The corner of sections 21, 22, 27 and 28.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 8 S., R. 19 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0° 08' E., between sections 21 and 22.

Over pasture and farm ground.

40.22

Point for the 1/4 section corner of sections 21 and 22, at proportionate distance. There is no remaining evidence of the original corner (record: charred cedar post, 3 ft. long, 3x3 ins.).

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

T8S R19W
1/4
S21 | S22
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Set a 5 1/2 ft. steel fence post alongside the aluminum post.

The corner falls in an open pasture.

60.33

Point for the N 1/16 section corner of sections 21 and 22.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

T8S R19W
N 1/16
S21 | S22
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Set a 5 1/2 ft. steel fence post alongside the aluminum post.

The corner falls in an open pasture.

80.44

Point for the corner of sections 15, 16, 21, and 22, at proportionate distance, longitudinally between found original corners, and latitudinally held on an old E and W fence line. There is no remaining evidence of the original corner (record: charred cedar post, 4 ft long, 4x4 ins.).

This point falls on the south bank of a tributary of Deep creek, 10 lks. wide, course SE., and is unsuitable for permanent monumentation. At this true corner point I drive a steel fence post 5 1/2 ft. long, 4 1/2 ft. in the ground, set in the old E and W fence line.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 8 S., R. 19 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the corner of sections 14, 15, 22, and 23.

N. $88^{\circ} 28'$ W., between sections 15 and 22.

Over rolling open desert land and pasture ground.

40.005 The 1/4 section corner of sections 15 and 22, monumented with a limestone, 11x8x5 ins., firmly set, plainly marked 1/4 on the N. face and set in a small mound of stone (record: limestone, 12x10x6 ins.).

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T8S R19W
1/4	<u>S15</u>
	S22
	1993

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 1 1/2 ft. West of the corner.

S. $89^{\circ} 38'$ W., beginning new measurement.

3.50 Center line of paved Ibapah - Goshute road, 38 lks. wide, course N. $5^{\circ} 30'$ W. and S. $5^{\circ} 30'$ E.

38.64 Point selected for the witness corner to the corner of sections 15, 16, 21, and 22.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

	T8S R19W
	WC
	<u>S16</u> <u>S15</u>
	S21 S22
	1993

Raise a mound of stone, 3 ft. base, 1 ft. West of the corner.

The witness corner falls 1 lk. N. of the E and W fence.

40.64 True point for the corner of sections 15, 16, 21, and 22.

N. $0^{\circ} 14.5'$ W., between sections 15 and 16.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 8 S., R. 19 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Over pasture and farm ground.

40.43

Point for the 1/4 section corner of sections 15 and 16, at proportionate distance. There is no remaining evidence of the position of the original corner (record: charred cedar post, 3 ft. long, 3x3 ins.).

Set an aluminum post 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over the top of the steel fence post, 5 1/2 ft. long, driven 5 ft. in the ground and in a mound of stone, 4 ft. base to top of aluminum cap marked:

T8S R19W
1/4
S16 | S15
1993

The corner falls on the W. edge of a slough, 50 lks. wide, course NW and SE.

80.86

Corner of fences N, S, E, and W. This is accepted as the best available evidence of the position of the original corner of sections 9, 10, 15, and 16 (record: charred cedar post, 4 ft. long, 4x4 ins.).

At the corner of fences

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T8S R19W
S9 | S10
S16 | S15
1993

The N and W fence is a standing older fence, the S fence is a newer fence, believed to be built over a older fence and the fence projecting E. is a newer fence.

From the corner of sections 10, 11, 14, and 15.

N. 88° 59' W., between sections 10 and 15.

Over rolling open desert land and pasture ground.

40.58

Point for the 1/4 section corner of sections 10 and 15, at proportionate distance. There is no remaining evidence of the position of the original corner (record: charred cedar post, 3 ft. long, 3x3 ins.).

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 8 S., R. 19 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T8S R19W
1/4 $\frac{S10}{S15}$
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 ft. high, North of the corner.

The corner falls on flat open ground, in greasewood and sagebrush.

60.87 Point for the W 1/16 section corner of sections 10 and 15.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T8S R19W
W 1/16 $\frac{S10}{S15}$
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 ft. high, North of the corner.

The corner falls on flat open ground, in greasewood and sagebrush.

62.67 Center line of paved Ibapah - Goshute road, 38 lks. wide, course N. 21° 25 W. and S. 21° 25 E.

81.16 The corner of sections 9, 10, 15, and 16.

N. 0° 16.5' W., between sections 9 and 10.

Over flat ground.

40.34 Point for the 1/4 section corner of sections 9 and 10, at proportionate distance. There is no remaining evidence of the position of the original corner (record: limestone, 14x12x8 ins.).

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

T8S R19W
1/4
S9 | S10
1993

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 8 S., R. 19 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, West of the corner.

The corner falls approximately 1 ch. west of the paved Ibapah - Goshute road.

From the corner.

USGS Benchmark " P22 1924 ", bears S. $65^{\circ} 23.5'$ W., 38 lks. dist., monumented with a standard brass cap, firmly set, flush with the ground.

42.55 Center line of paved Ibapah - Goshute road, 38 lks wide, course N. $20^{\circ} 25'$ W. and S. $20^{\circ} 25'$ E.

60.51 Point for the N 1/16 section corner of sections 9 and 10.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

T8S R19W
N 1/16
S9 | S10
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, West of the corner.

80.68 The corner of sections 3, 4, 9, and 10, monumented with a limestone, 12x12x5 ins., firmly set, plainly marked with 5 notches on the S. and 2 notches on the E. edges, set in a small mound of stone (record: limestone, 14x12x10 ins.).

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T8S R19W
S4 | S3
S9 | S10
1993

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, West of the corner.

The geographic position of this corner, as determined by the Global Positioning System, static relative positioning techniques, utilizing U.S. Geological Survey triangulation stations "SHERIDAN" and "INDIAN" is as follows:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 8 S., R. 19 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Latitude $40^{\circ} 09' 11.03''$ N. Longitude $113^{\circ} 58' 57.25''$ W.
N.A.D. 1927

This corner is designated as a B.L.M. control station.

From the corner of sections 2, 3, 10, and 11.

N. $87^{\circ} 25'$ W., between sections 3 and 10.

Over rolling open desert land.

36.475 The 1/4 section corner of sections 3 and 10, monumented with a limestone, 14x10x6 ins., firmly set, dimly marked 1/4 on the N. face (record: limestone, 12x10x7 ins.).

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T8S R19W
1/4	<u>S3</u>
	S10
	1993

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 3 1/2 ft. base, 2 ft. high, North of the corner.

N. $88^{\circ} 56.5'$ W., beginning new measurement.

40.235 The corner of sections 3, 4, 9, and 10.

N. $0^{\circ} 04.5'$ W., between sections 3 and 4.

Over rolling open desert land.

39.95 Point for the 1/4 section corner of sections 3 and 4, at proportionate distance. There is no remaining evidence of the position of the original corner (record: limestone, 18x14x8 ins.).

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, and in a mound of stone 4 1/2 ft. base to top of aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 8 S., R. 19 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T8S R19W

1/4

S4 | S3

1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Raise a mound of stone 3 ft. base, 2 ft. high, West of the corner.

The corner falls on gradual easterly slope of a ridge, approximately 30 lks. west of the bottom of a draw, drains SW.

79.65

The corner of sections 3 and 4 only, on the north boundary of the township, firmly set in a mound of stone, with brass cap marked as described in the official record of the resurvey executed by L.H. Godwin and W.H. Sylvester, Cadastral Surveyors, in 1958.

From the corner of sections 4, 5, 32, and 33, the south boundary of the township, hereinbefore described.

N. 0° 43' W., between sections 32 and 33.

Over rolling open desert land.

39.985

The 1/4 section corner of sections 32 and 33, monumented with a basalt stone, 22x16x8 ins., firmly set, plainly marked 1/4 on the N. face (record: limestone, 20x14x10 ins.).

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T8S R19W

1/4

S32 | S33

1993

Buried the marked stone alongside the aluminum post.

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, West of the corner.

N. 0° 29.5' W., beginning new measurement.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 8 S., R. 19 W., SALT LAKE MERIDIAN, UTAH

CHAINS

40.225

The corner of sections 28, 29, 32, and 33, monumented with a basalt stone, 18x10x10 ins., firmly set, plainly marked, 1 notch on the S., and 4 notches on the E. edges, set in a scattered mound of stone (record, limestone, 20x10x8 ins.).

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T8S R19W	
<u>S29</u>	<u>S28</u>
S32	S33
1993	

Buried the marked stone alongside the aluminum post.

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, West of the corner.

From the corner of sections 27, 28, 33, and 34.

S. 89° 52.5' W., between sections 28 and 33.

Over flat open ground through farm and desert lands.

20.36

Point for the E 1/16 section corner of sections 28 and 33.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

E 1/16	<u>S28</u>
	S33
	1993

The corner falls on the N. edge of an E and W dirt road, 12 lks. wide running along a fence projecting E. and W.

Set a steel fence post alongside the corner.

40.72

The 1/4 section corner of sections 28 and 33, monumented with a basalt stone, 12x8x6 ins., firmly set, plainly dimly marked 1/4 on the N. face in a scattered mound of stone (record: limestone, 12x8x6 ins.).

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 8 S., R. 19 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T8S R19W

1/4 $\frac{S28}{S33}$
1993

Buried the marked stone alongside the aluminum post.

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 ft. high, North of the corner.

Set a steel fence post alongside the aluminum post.

The corner falls near the intersection of 2 dirt roads, 12 lks. wide, 17 lks. N., of one, course S. 40° W., and 17 lks. S., of the other course S. 70° W.

N. 89° 23' W., beginning new measurement.

40.15 The corner of sections 28, 29, 32, and 33.

N. 0° 02' E., between sections 28 and 29.

Over rolling open desert land.

40.24 Point for the 1/4 section corner of sections 28 and 29, at proportionate distance. There is no remaining evidence of the original corner (record: charred cedar post, 3 ft. long, 3x3 ins.).

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T8S R19W
1/4
S29 | S28
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, North of the corner.

The corner falls on flat open sage covered ground.

80.48 Point for the corner of sections 20, 21, 28, and 29, at proportionate distance. There is no remaining evidence of the original corner (record: limestone, 18x12x10 ins.).

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 8 S., R. 19 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T8S R19W
S20 | S21
S29 | S28
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Raise a mound of stone, 3 1/2 ft. base, 2 1/2 ft. high, West of the corner.

The corner falls on a gradual westerly slope.

From the corner of sections 21, 22, 27, and 28.

N. 89° 30' W., between sections 21 and 28.

Over open ground through farm and desert lands.

20.225 Point for the E 1/16 section corner of sections 21 and 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

E 1/16 S21
S28
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the corner.

Set a cedar post, 5 ins. diam., 6 ft. long, alongside the aluminum post.

40.45 Point for the 1/4 section corner of sections 21 and 28, at proportionate distance. There is no remaining evidence of the original corner (record: limestone, 12x10x8 ins.).

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T8S R19W
1/4 S21
S28
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, North of the corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 8 S., R. 19 W., SALT LAKE MERIDIAN, UTAH

CHAINS

The corner falls on flat open sage covered ground.

80.89

The corner of sections 20, 21, 28, and 29.

N. 89° 43.5' W., between sections 20 and 29.

40.37

The 1/4 section corner of sections 20 and 29, monumented with a limestone, 12x10x8 ins., firmly set in a mound of stone, plainly marked 1/4 on the N. face (record: limestone, 14x12x10 ins.).

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T8S R19W
1/4 S20
 S29
 1993

Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, North the corner.

The corner falls on flat open sage covered ground.

From the corner of sections 20, 21, 28, and 29.

N. 0° 11' W., between sections 20 and 21.

Over rolling open desert land.

40.24

The 1/4 section corner of sections 20 and 21, monumented with a basalt stone, 12x10x8 ins., firmly set, plainly marked 1/4 on the W. face, set in a mound of stone (record: limestone, 12x12x10 ins.).

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T8S R19W
1/4
S20 | S21
1993

Buried the marked stone alongside the aluminum post.

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 8 S., R. 19 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Raise a mound of stone, 3 ft. base, 2 ft. high, West of the corner.

The corner falls on top of a low open ridge.

N. $0^{\circ} 26.5'$ E., beginning new measurement.

40.225 The corner of sections 16, 17, 20, and 21, at the corner of fences bearing N, E, and W, monumented with a mound of scattered stone around the fence corner. This is accepted as the best available evidence of the position of the original corner. The original marked stone was not found (record: limestone, 18x8x8 ins.).

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T8S R19W	
<u>S17</u>	<u>S16</u>
S20	S21
1993	

Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, West of the corner.

From the true point for the corner of sections 15, 16, 21, and 22.

N. $89^{\circ} 56.5'$ W., between sections 16 and 21.

Over flat open range land.

20.335 Point for the E 1/6 section corner of sections 16 and 21.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

E 1/6	<u>S16</u>
	S21
	1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Set a steel fence post on the S. side of the aluminum post.

The corner falls 1.5 lks. S. of an E and W fence.

40.67 The 1/4 section corner of sections 16 and 21, monumented with a limestone, 22x16x8 ins., firmly set with no visible scribe marks (record: limestone, 20x13x6 ins.).

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 8 S., R. 19 W., SALT LAKE MERIDIAN, UTAH

CHAINS

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T8S R19W
1/4 S16
 S21
 1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Buried the stone alongside the aluminum post.

Raise a mound of stone, 1 ft. base, 1 ft. high, North of the corner.

N. 88° 59.5' W., beginning new measurement.

40.22 The corner of sections 16, 17, 20, and 21.

N. 0° 31.5' E., between sections 16 and 17.

Over flat open ground.

40.25 The 1/4 section corner of sections 16 and 17, monumented with a basalt stone, 16x12x10 ins., firmly set, plainly marked 1/4 on the W face, set in a scattered mound of stone (record: limestone, 14x12x9 ins.).

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T8S R19W
1/4
S17 | S16
1993

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 2 ft. base, 2 ft. high, West of the corner.

The corner falls 1 lk. west of a N and S fence line and 38 lks. east of a dirt road, 15 lks. wide, course N. and S.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 8 S., R. 19 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. $0^{\circ} 31'E.$, beginning new measurement.

40.635 Point for the corner of sections 8, 9, 16, and 17, at proportionate distance latitudinally between found original corners and longitudinally held on an old N and S fence line. There is no remaining evidence of the original corner (record: charred cedar post, 4 ft. long, 4x4 ins.).

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T8S R19W	
S8	S9
S17	S16
1993	

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, West of the corner.

The corner is set in a N and S fence line, and falls 52 lks. E of a dirt road, 15 lks. wide, course northerly and southerly.

From the corner of sections 9, 10, 15, and 16.

N. $89^{\circ} 27' W.$, between sections 9 and 16.

Over pasture lands.

39.90 Point for the 1/4 section corner of sections 9 and 16, at proportionate distance. There is no remaining evidence of the original corner (record: charred cedar post, 3 ft. long, 3x3 ins.).

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T8S R19W	
1/4	S9
	S16
1993	

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 ft. high, North of the corner.

The corner falls within pasture lands.

79.80 The corner of sections 8, 9, 16, and 17.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 8 S., R. 19 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. $89^{\circ} 46.5'$ W., between sections 8 and 17.

40.54

The 1/4 section corner of sections 8 and 17, monumented with squared cedar post, 3 ins. diam., 2 1/2 ft. long, firmly set, plainly scribed 1/4 S (record: charred cedar post, 3 ft. long, 3x3 ins.).

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T8S R19W
1/4	<u>S8</u>
	S17
	1993

Buried the original cedar post alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, North of the corner.

From the corner of sections 8, 9, 16, and 17.

N. $0^{\circ} 01'$ W., between sections 8 and 9.

Over flat open ground.

40.635

Point for the 1/4 section corner of sections 8 and 9, at proportionate distance. There is no remaining evidence of the original corner (record: charred cedar post, 3 ft. long, 3x3 ins.).

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T8S R19W
	1/4
	S8 S9
	1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 ft., West of the corner.

The corner falls on flat open ground, in greasewood and sagebrush.

From the corner, a dirt road, 12 lks. wide, course N. 18° W. and S. 18° E., bears east, 80 lks. dist.

80.77

Point selected for the witness corner to the corner of sections 4, 5, 8, and 9.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 8 S., R. 19 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T8S R19W
WC
S5 | S4
S8 | S9
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, West of the corner.

- 81.27** Point for the corner of sections 4, 5, 8, and 9, at proportionate distance. There is no remaining evidence of the original corner position (record: charred cedar post, 4 ft. long, 4x4 ins.).

The true point position falls within a small drainage 10 lks. wide, 2 ft. deep, drains westerly not suitable for permanent monumentation.

From the corner of sections 3, 4, 9, and 10.

N. 89° 01' W., between sections 4 and 9.

Over rolling open desert land.

- 28.40** Center line of paved Ibapah - Goshute road, 38 lks. wide, course N. 37° 30' W. and S. 37° 30' E.

- 39.72** Point for the 1/4 section corner of sections 4 and 9, at proportionate distance. There is no remaining evidence of the original corner (record: charred cedar post, 3 ft. long, 3x3 ins.).

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T8S R19W
1/4 S4
S9
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, North of the corner.

- 79.43** True point for the corner of sections 4, 5, 8, and 9.
-

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 8 S., R. 19 W., SALT LAKE MERIDIAN, UTAH

CHAINS

S. 88° 20' W., between sections 5 and 8.

- 39.73** The 1/4 section corner of sections 5 and 8, monumented with a partially squared cedar post, 5 ins. diam., 3 1/2 ft. long, laying loose on the ground with scribe marks 1/4 S visible (record: charred cedar post, 3 ft. long, 3x3 ins.).

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T8S R19W
1/4 $\frac{S5}{S8}$
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Buried the original cedar post alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, North of the corner.

From the true point for the corner of sections 4, 5, 8, and 9.

N. 2° 05' E., between sections 4 and 5.

Over flat open ground.

- 1.10** South edge of wash, 25 lks. wide, 12 ft. deep, course NE and SW 45°.
- 40.66** The 1/4 section corner of sections 4 and 5, monumented with a basalt, 16x6x6, firmly set, dimly marked 1/4 on the W. face, and a small mound east of the corner (record: limestone, 16x6x6 ins.).

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T8S R19W
1/4
S5 | S4
1993

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, West of the corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 8 S., R. 19 W., SALT LAKE MERIDIAN, UTAH

CHAINS

The corner falls 1 lk. west of a N and S fence line and 38 lks. east of a dirt road 15 lks. wide, course N. and S.

N. $2^{\circ} 43'$ W., beginning new measurement.

39.715

The corner of sections 4 and 5 only, on the north boundary of the township, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap marked as described in the official record of the resurvey executed by L.H. Godwin and W.H. Sylvester, Cadastral Surveyors, in 1958.

The Subdivision of Section 9,
T. 8 S., R. 19 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 9 and 16.

N. $0^{\circ} 09'$ W., on the N - S center line of section 9.

40.485

Point for the center 1/4 section corner, at intersection with the E - W center line of section 9.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with aluminum cap marked:

T8S R19W
C 1/4
S9
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Raise a mound of stone, 3 ft. base, 1 ft. high, West of the corner.

The corner falls in pasture.

60.73

Point for the center N 1/16 section corner of section 9.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with aluminum cap marked:

C
N 1/16 | S9
C
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

THE SUBDIVISION OF SECTION 9,
T. 8 S., R. 19 W., SALT LAKE MERIDIAN, UTAH

CHAINS

- Raise a mound of stone, 3 ft. base, 1 ft. high, West of the corner.
- 80.975** The 1/4 section corner of sections 4 and 9.
-
- From the 1/4 section corner of sections 9 and 10.
N. $89^{\circ} 14'$ W., on the E - W center line of section 9.
- 39.805** The center 1/4 section corner.
- 79.61** The 1/4 section corner of sections 8 and 9.
-
- From the N 1/16 section corner of sections 9 and 10.
N. $89^{\circ} 07.5'$ W., on the E - W center line of the NE 1/4 of section 9.
- 8.50** Center line of paved Ibapah - Goshute road, 38 lks. wide, course N. 20° W. and S. 20° E.
- 39.76** The center N 1/16 section corner.
-
- The Subdivision of Section 15,
T. 8 S., R. 19 W., Salt Lake Meridian, Utah
-
- From the 1/4 section corner of sections 15 and 22.
N. $0^{\circ} 17'$ W., on the N - S center line of section 15.
- 39.495** Point for the center 1/4 section corner at intersection with the E - W center line of section 15.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with aluminum cap marked:
- T8S R19W
C 1/4
S15
1993
- Deposit a clear "Deep-1 magnet" at the base of the aluminum post.
- Raise a mound of stone, 3 ft. base, 2 ft. high, West of the corner.
- 79.89** The 1/4 section corner of sections 10 and 15.

THE SUBDIVISION OF SECTION 15,
T. 8 S., R. 19 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the 1/4 section corner of sections 14 and 15.

N. $89^{\circ} 02'$ W., on the E - W center line of section 15.

39.43 The center 1/4 section corner.

48.85 Center line of paved Ibapah - Goshute road, 38 lks. wide, course N. 6° W. and S. 6° E.

58.00 Gate in a northwesterly and southeasterly 4 strand barb wire fence.

59.74 Point for the center W 1/16 section corner of section 15.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

$$C \frac{W \ 1/16}{S15} C$$

1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, North of the corner.

The corner falls on flat open ground.

80.05 The 1/4 section corner of sections 15 and 16.

From the center W 1/16 section corner of section 15.

N. $0^{\circ} 16'$ W., on the N - S center line of the NW 1/4 of section 15.

14.48 Fence, 4 strand barb wire, bears northwesterly and southeasterly.

33.60 Center line of paved Ibapah - Goshute road, 38 lks. wide, course N. 20° W. and S. 20° E.

40.41 The W 1/16 section corner of sections 10 and 15.

The Subdivision of Section 21,
T. 8 S., R. 19 W., Salt Lake Meridian, Utah

THE SUBDIVISION OF SECTION 21,
T. 8 S., R. 19 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the 1/4 section corner of sections 21 and 28.

N. $0^{\circ} 02'$ W., on the N - S center line of section 21.

40.23

Point for the center 1/4 section corner at intersection with the E - W center line of section 21.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground over the top of a steel fence post 5 1/2 ft. long, driven 5 ft. in the ground, with aluminum cap marked:

T8S R19W
C 1/4
S21
1993

Raise a mound of stone, 3 ft. base, 2 ft. high, West of the corner.

The corner falls within a sand dune area.

80.12

The 1/4 section corner of sections 16 and 21.

From the 1/4 section corner of sections 21 and 22.

N. $89^{\circ} 29'$ W., on the E - W center line of section 21.

20.28

Point for the center E 1/16 section corner of section 21.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

C $\frac{E\ 1/16}{S21}$ C
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, North of the corner.

The corner falls on flat open ground.

22.30

Fence 4 strand barbwire bears northerly and southerly.

40.56

The center 1/4 section corner.

81.115

The 1/4 section corner of sections 20 and 21.

THE SUBDIVISION OF SECTION 21,
T. 8 S., R. 19 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the center E 1/16 section corner of section 21.

N. $0^{\circ} 03'$ E., on the N - S center line of the NE 1/4 of section 21.

40.05 The E 1/16 section corner of sections 16 and 21.

From the E 1/16 section corner of sections 21 and 28.

N. $0^{\circ} 03'$ E., on the N - S center line of the SE 1/4 of section 21.

40.225 The center E 1/16 section corner.

The Subdivision of Section 22,
T. 8 S., R. 19 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 22 and 27.

N. $0^{\circ} 27.5'$ E., on the N - S center line of section 22.

39.745 Point for the center 1/4 section corner at intersection with the E - W center line of section 22.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with aluminum cap marked:

T8S R19W
C 1/4
S22
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Raise a mound of stone, 3 ft. base, 1 ft. high, West of the corner.

49.20 Center line of paved Ibapah - Goshute road, 38 lks. wide, course N. 6° W. and S. 6° E.

60.265 Point for the center N 1/16 section corner of section 22.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with aluminum cap marked:

C
N 1/16 | S22
C
1993

THE SUBDIVISION OF SECTION 22,
T. 8 S., R. 19 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Raise a mound of stone, 3 ft. base, 1 ft. high, West of the corner.

80.785 The 1/4 section corner of sections 15 and 22.

From the 1/4 section corner of sections 22 and 23.

N. $89^{\circ} 12'$ W., on the E - W center line of section 22.

38.30 Center line of paved Ibapah - Goshute road, 38 lks. wide, course N. 6° W. and S. 6° E.

39.335 The center 1/4 section corner.

79.75 The 1/4 section corner of sections 21 and 22.

From the center N 1/16 section corner of section 22.

N. $89^{\circ} 47'$ W., on the E - W center line of the NW 1/4 of section 22.

1.27 Center line of paved Ibapah - Goshute road, 38 lks. wide, course N. 6° W. and S. 6° E.

40.525 The N 1/6 section corner of sections 21 and 22.

The Subdivision of Section 27,
T. 8 S., R. 19 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 27 and 34.

N. $0^{\circ} 05'$ E., on the N - S center line of section 27.

39.735 Point for the center 1/4 section corner of at intersection with the E - W center line of section 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with aluminum cap marked:

T8S R19W
C 1/4
S27
1993

THE SUBDIVISION OF SECTION 27,
T. 8 S., R. 19 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, West of the corner.

80.13 The 1/4 section corner of sections 22 and 27.

From the 1/4 section corner of sections 26 and 27.

N. $89^{\circ} 22'$ W., on the E - W center line of section 27.

28.50 Center line of paved Ibapah - Goshute road, 38 lks. wide, course N. 9° W. and S. 9° E.

38.685 The center 1/4 section corner.

78.87 The 1/4 section corner of sections 27 and 28.

The Subdivision of Section 28,
T. 8 S., R. 19 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 28 and 33.

N. $0^{\circ} 15'$ E., on the N - S center line of section 28.

40.405 Point for the center 1/4 section corner at intersection with the E - W center line of section 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with aluminum cap marked:

T8S R19W
C 1/4
S28
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 ft. high, West of the corner.

80.55 The 1/4 section corner of sections 22 and 27.

From the 1/4 section corner of sections 27 and 28.

N. $89^{\circ} 37.5'$ W., on the E - W center line of section 28.

THE SUBDIVISION OF SECTION 28,
T. 8 S., R. 19 W., SALT LAKE MERIDIAN, UTAH

CHAINS**19.65**

Fence 4 strand barbwire, bears N. and S.

20.29

Point for the center E 1/16 section corner of section 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

$$\begin{array}{c} \text{T8S R19W} \\ \text{C} \frac{\text{E 1/16}}{\text{S28}} \text{C} \\ 1993 \end{array}$$

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, North of the corner.

40.58

The center 1/4 section corner.

80.88

The 1/4 section corner of sections 28 and 29.

From the center E 1/16 section corner of section 28.

N. 0° 10' E., on the N - S center line of the NE 1/4 of section 28.

40.10

The E 1/16 section corner of sections 21 and 28.

From the E 1/16 section corner of sections 28 and 33.

N. 0° 10' E., on the N - S center line of the SE 1/4 of section 28.

40.23

The center E 1/16 section corner.

The Subdivision of Section 34,
T. 8 S., R. 19 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 34 and 3, on the south boundary of the township, hereinbefore described.

N. 0° 06' E., on the N - S center line of section 34.

40.19

Point for the center 1/4 section corner at intersection with the E - W center line of section 34.

THE SUBDIVISION OF SECTION 34,
T. 8 S., R. 19 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with aluminum cap marked:

T8S R19W
C 1/4
S34
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, West of the corner.

60.405 Point for the center N 1/16 section corner of section 34.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground over the top of a steel fence post 7 ft. long, driven 6 ft. in the ground, and set in a mound of stone, 4 ft. base to top of aluminum cap marked:

C
N 1/16 | S34
C
1993

Raise a mound of stone, 3 ft. base, 2 ft. high, West of the corner.

The corner falls within the north end of a pasture in 8 ins. of standing water.

60.60 Fence 4 strand barbwire, projecting E. and W.

80.62 The 1/4 section corner of sections 27 and 34.

From the 1/4 section corner of sections 34 and 35.

N. 89° 17' W., on the E - W center line of section 34.

17.95 Center line of paved Ibapah - Goshute road, 38 lks. wide, course N. 7° W. and S. 7° E.

19.935 Point for the center E 1/16 section corner of section 34.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

C $\frac{E\ 1/16}{S34}$ C
1993

THE SUBDIVISION OF SECTION 34,
T. 8 S., R. 19 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, North of the corner.

20.65 Fence, projects N. and S.

39.87 The center 1/4 section corner.

79.985 The 1/4 section corner of sections 34 and 35.

From the center E 1/16 section corner of section 34.

N. 0° 19.5' E., on the N - S center line of the NE 1/4 of section 34.

20.305 Point for the NE 1/16 section corner at intersection with the E - W center line of the NE 1/4 of section 34.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

NE 1/16
S34
1993

Deposit a clear "Deep-1 magnet" at the base of the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, West of the corner.

22.50 Center line of paved Ibapah - Goshute road, 38 lks. wide, course NW and SE.

40.61 The E 1/16 section corner of sections 27 and 34.

From the N 1/16 section corner of sections 34 and 35.

N. 89° 33' W., on the E - W center line of the NE 1/4 of section 34.

19.65 Center line of paved Ibapah - Goshute road, 38 lks. wide, course N. 7° W. and S. 7° E.

20.01 The NE 1/16 section corner.

40.02 The center N 1/16 section corner.

THE SUBDIVISION OF SECTION 34,
T. 8 S., R. 19 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the E 1/16 section corner of sections 34 and 3, on the south boundary of the township.

N. $0^{\circ} 06.5' E.$, on the N - S center line of the SE 1/14 of section 34.

40.31

The center E 1/16 section corner.

General Description

This area surveyed in T., 8 S., R. 19 W., is located approximately 5 miles northerly of the town of Ibapah, Utah. The area surveyed lies along the Deep creek drainage in pasture lands and open rolling desert lands. The Ibapah - Goshute highway runs through the entire township.

The terrain varies from cultivated fields and pasture to open rolling desert lands vegetated with sagebrush, greasewood and native grasses.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Ronald K. Baugh	Land Surveyor
Jennifer Eames	Survey Technician
Joseph M. Dhaenens	Survey Technician
Shane Button	Survey Aid

CERTIFICATE OF SURVEY

I, *Larry V. Judd, Cadastral Surveyor*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *26th day of October, 1992*, I have *dependently resurveyed portions of the south boundary and subdivisional lines and subdivided certain sections in Township 8 South, Range 19 West*,

of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

6/20/95
Date

Larry V. Judd
(Cadastral Surveyor)

Date

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of portions of the south boundary and subdivisional lines and subdivided certain sections in Township 8 South, Range 19 West, Salt Lake Meridian, Utah*,

executed by *Larry V. Judd, Cadastral Surveyor*

having been critically examined and found correct, are hereby approved.

September 28, 1995
Date

Donald A. Buehler
(Chief Cadastral Surveyor for Utah)