

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF  
A PORTION OF  
THE SOUTH AND WEST BOUNDARIES  
A PORTION OF  
THE SUBDIVISIONAL LINES  
AND  
THE SUBDIVISION OF SECTIONS  
8, 9, 17, 20, 30 AND 31  
IN  
TOWNSHIP 14 SOUTH, RANGE 1 WEST

OF THE SALT LAKE MERIDIAN  
IN THE STATE OF UTAH

EXECUTED BY

*Ferrel D. Reynolds*  
*Cadastral Surveyor*

Under special instructions dated *April 8, 1993*, approved April 8, 1993, which provided for the surveys included under Group Number 797, and assignment instructions dated April 8, 1993.

Survey commenced *April 28, 1993*

Survey completed *April 19, 1994*

INDEX DIAGRAM

Township 14 South , Range 1 West

6	5 28 27	4 16	3	2	1
7 27	8 15 26	9 10 9 14	10	11	12
18 25	17 25	16 8	15	14	13
19 23 22 21	20 21	21	22	23	24
5 4 30 20 19	12 29 11 18	28	27	26	25
3 31 17 7 6	32	33	34	35	36

The Subdivision of Section 8.....Page 28

The Subdivision of Section 9.....Page 30

The Subdivision of Section 17.....Page 32

The Subdivision of Section 20.....Page 33

The Subdivision of Section 30.....Page 34

The Subdivision of Section 31.....Page 39

## TOWNSHIP 14 SOUTH, RANGE 1 WEST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

The following field notes describe the dependent resurvey of a portion of the south and west boundaries, a portion of the subdivisional lines, and the subdivision of sections 8, 9, 17, 20, 30 and 31, in Township 14 South, Range 1 West, Salt Lake Meridian, Utah.

**History of Surveys**

Surveyed by		Retr. or Resurveyed by	
<b>NORTH BOUNDARY</b>			
Portion	C. Mogo	1856	
Portion	E.W. Koeber	1884	E.W. Koeber 1884
Portion	Stewart & Stewart	1898	
<b>SOUTH BOUNDARY</b>			
Portion	C. Mogo	1856	
Portion	Stewart & Stewart	1898	Stewart & Stewart 1898
<b>EAST BOUNDARY</b>			
All	C. Mogo	1856	
All			A.D. Ferron 1882
<b>WEST BOUNDARY</b>			
Portion	F. Dickert	1871	
All	Stewart & Stewart	1898	Stewart & Stewart 1898
Portion			Stewart & Heist 1912
Portion			R.A. Zaninovich 1991
<b>SUBDIVISION</b>			
Portion	C. Mogo	1856	
Portion	Stewart & Stewart	1898	Stewart & Stewart 1898
Portion			Stewart & Stewart 1991

The closing subdivisional lines into the west boundary of T. 15 S., R. 1 1/2 W., were surveyed by Stewart and Stewart in 1898.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 797, dated April 8, 1993.

The directions of lines were determined by hour angle observations of the sun and Polaris, carried forward by sustained angulation. Distances were determined by electronic measurement.

## TOWNSHIP 14 SOUTH, RANGE 1 WEST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

Preliminary to the resurvey the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line notes are given herein.

The geographic position of the corner of sections 28, 29, 32, and 33, as determined by a tie made to U.S. Coast and Geodetic Survey triangulation station "Cedar" is as follows:

Latitude 39°33'26.37" N. Longitude 111°56'48.80" W.  
N.A.D. 1927

The mean magnetic declination as determined from the U.S. Geological Survey Magnetic Declination Map of 1990 is 14° E.

---

Dependent Resurvey of a Portion of the West Boundary,  
T. 14 S., R. 1 W., Salt Lake Meridian, Utah

---

Reestablishment of the Survey executed by F. Dickert in 1871,  
the Resurvey by Stewart and Stewart in 1898,  
and the Resurvey by Stewart and Heist in 1912

---

Beginning at the point for the closing corner of sections 2 and 31, Townships 14 and 15 South, Ranges 1 and 1 1/2 West respectively, at proportionate distance. No remaining evidence of the original corner was found; not monumented.

From this point:

The point for the corner of sections 1 and 12 only, T. 15 S., R. 2 W., at proportionate distance. No remaining evidence of the original corner or intervening corners were found, bears S. 0°10.5' W., 52.293 chains dist.

From this same point:

The closing corner of sections 2 and 11, on the west boundary of T. 15 S., R 1 1/2 W, monumented with a sandstone, 18x12x4 ins., firmly set and plainly marked with 1 groove on the N and 5 grooves on the S edge, with a CC on the E face, bears S. 0°14.1' W., 87.414 chains dist.; not remonumented.

N. 0°10.5' E., on the east boundary of section 1, T. 15 S., R. 2 W.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Over gently rolling cultivated land.

**20.196** Point for the S 1/16 section corner of section 31 only; T. 14 S., R. 2 W.; not monumented.

**28.209** Point for the corner of sections 1 and 36 only, Townships 14 and 15 South, Range 2 West, at proportionate distance. No remaining evidence of the original corner was found; not monumented.

---

N. 0°16.5' E., on the east boundary of section 36, T. 14 S., R. 2 W.

**12.183** Point for the W 1/4 section corner of section 31 only, at proportionate distance. No remaining evidence of the original corner was found; not monumented.

**40.100** Point for the E 1/4 section corner of section 36, T. 14 S., R. 2 W., at proportionate distance. No remaining evidence of the original corner was found; not monumented.

**52.575** Point for the closing corner of sections 30 and 31, on the west boundary of the township, as determined from the record bearing and distance from the original bearing tree ( S. 37°30' E., 1.20 chains dist.) and then with a cardinal offset to intersect the west boundary ( S. 89°52.8' E., 0.156 chains dist.) No remaining evidence of the original rock corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

		T14S	
		R2W	R1W
S36		S30	C
		S31	C
		1993	

Set a steel fence post alongside the aluminum post.

From which, the original bearing tree with new bearing and distance:

A juniper, 16 ins. diam., with scribe marks visible, bears  
S. 31°06' E., 1.11 chains distance.

**72.241** Point for the S 1/16 section corner of section 30 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T14S  
R2W R1W  
| S 1/16  
| S30  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on a gently rolling W slope in a fence corner, 4 strand barbwire, bears N and E, in sagebrush and scattered juniper.

**80.411** The corner of section 25 and 36 only, T. 14 S., R. 2 W., monumented with a Juab County aluminum post, 2 1/2 ins. in diam., extending 6 ins. out of ground, with the original marked stone found alongside, with aluminum cap marked.

JUAB COUNTY  
T14S  
R2W R1W  
S25 | S30  
S36 |  
1986

The corner is located in a fence corner, 4 strand barbwire, bears N and W, in sagebrush and scattered juniper growth.

N. 0°09.6' E., on the east boundary of section 25, T. 14 S., R. 2 W.

**11.496** Point for the W 1/4 section corner of section 30 only, at proportionate distance, no remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T14S  
R2W R1W  
| 1/4  
| S30  
1993

Set a steel fence post alongside the aluminum post.

The corner is located 10 lks. E of a fence line, 4 strand barbwire, bears N and S, on gentle W slope in sagebrush and scattered juniper growth.

**31.162** Point for the N 1/16 section corner of section 30 only; not monumented.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS****40.041**

The 1/4 section corner of section 25 only, T. 14 S., R. 2 W., monumented with a Juab County aluminum post, 2 1/2 ins. diam., extending 6 ins. out of the ground, with aluminum cap marked.

JUAB COUNTY  
T14S  
R2W R1W  
1/4 |  
S25 |  
1986

The corner is located in a fence corner, 4 strand barbwire, bears N, E, S, and W on a gentle W slope in sagebrush.

N. 0°03.2' W., beginning new measurement.

**10.787**

The closing corner of sections 19 and 30, monumented with an aluminum post, 2 1/2 ins. diam., extending 8 ins. above ground, with Juab County aluminum cap, marked:

JUAB COUNTY  
T14S  
R2W S25 | S19 R1W  
S30  
1986

The corner is located 5 lks. E of a fence line, 4 strand barbwire, bears N and S, on gently rolling land.

From this corner:

The corner of sections 24 and 25, T. 14 S., R. 2 W., bears N. 0°03.2' W., 29.268 chains dist., monumented with a Juab County aluminum post, 2 1/2 ins. diam., extending 6 ins. out of the ground, with aluminum cap, marked:

JUAB COUNTY  
T14S  
R2W S24 | R1W  
S25 |  
1986

The corner is located in a fence line, 4 strand barbwire, bears N and S.

Dependent Resurvey of a Portion of the South Boundary,  
T. 14 S., R. 1 W., Salt Lake Meridian, Utah

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Reestablishment of the Survey by Stewart and Stewart in 1898

From the corner of sections 5, 6, 31, and 32, Township 14 and 15 South, Range 1 West, monumented with a Juab County aluminum post, 2 1/2 ins. diam., extending 6 ins. out of the ground. This corner is accepted as a careful and faithful perpetuation of the position of the original corner. The aluminum cap is marked:

JUAB COUNTY  
T14S R1W  
S31 | S32  
S6 | S5  
T15S  
1990

No remaining evidence of the original rock corner or bearing trees were found.

The corner is located 15 lks. S of a fence corner, 4 strand barbwire, bears N, E and W, on gentle E slope in reseeded area.

N. 89°59.2' W., on the south boundary of section 31.

Over mountain land, through juniper and pinon growth.

11.00 Ridge, bears NE and SW

39.519 The 1/4 section corner of sections 6 and 31, monumented with a limestone, 20x12x4 ins., firmly set and plainly marked 1/4 on the N face.

From which the original bearing tree.

A juniper, 10 ins. diam., bears S. 65° W., 34 lks. dist., marked  
1/4 S6 BT.

No remaining evidence of the other original bearing tree was found.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

1/4 T14S R1W  
S31  
S6  
T15S R1W  
1993

Deposit the marked stone alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Raise a mound of stone N of the corner.

The corner is located on a SE slope, in pinon and juniper growth.

S. 89°32.6' W., beginning new measurement.

22.15 Top of high ridge or divide, bears NE and SW.

38.824 The closing corner of sections 1 and 6, T. 15 S., Rs. 1 and 1 1/2 W., monumented with a red sandstone, 18x14x8 ins., firmly set and plainly marked with 6 notches on the E, W, and S sides, with R 1 W on the E side and R 1 1/2 on the W side.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

```

T14S R1W
  S32
  S1 | S6
   C | C
R1 1/2 | R1W
  T15S
  1993
    
```

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone S of the corner.

The corner is located on a SW slope in scattered juniper growth.

79.928 Point for the 120 1/16 section corner of section 31 only; not monumented.

99.910 Point for the 140 1/16 section corner of section 31 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

```

T14S R1W

  1/16 S31 140
  T15S R1 1/2W

  1993
    
```

Set a steel fence post alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

The corner is located on a gentle W slope in native grasses.

**167.451**

Point for the closing corner of sections 2 and 31, Townships, 14 and 15 South, Ranges 1 and 1 1/2 West, hereinbefore described.

---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 1 W., Salt Lake Meridian, Utah

---

Reestablishment of the Survey by Stewart and Stewart in 1898.

---

From the W 1/4 section corner of section 15 only, monumented with a limestone, 18x10x10 ins., firmly set in a mound of stone and plainly marked 1/4 on the W face.

From which the original bearing trees;

A juniper, 10 ins. diam., bears N. 85° E., 18 lks. dist., marked  
S 15 BT.

A juniper, 12 ins. diam., bears N. 50° W., 22 lks. dist., marked  
S 16 BT.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with aluminum cap marked:

T14S R1W  
1/4  
| S15  
1993

The corner is located on a E slope in juniper growth.

N. 0°33.3' W., on the west boundary of section 15.

Over mountain land, through juniper and pinon growth.

**37.995**

The closing corner of sections 9 and 16, monumented with a trachyte stone, 18x10x8 ins., firmly set and plainly marked CC on the W face, 4 grooves on the S and 3 grooves on the E faces.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T14S R1W	
CC	— S9	S15
	S16	
	1993	

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone W of the corner.

The corner is located in the bottom of a draw, drains NE.

40.369

The corner of sections 10 and 15 only, monumented with a granite stone, 16x8x8 ins., firmly set and plainly marked with, 4 notches on the S and 3 notches on the E edges.

From which the original bearing tree:

A juniper, 8 ins. diam., bears S. 6° E., 69 lks. dist.,  
with scribe marks dimly visible.

No remaining evidence of the other original bearing trees were found.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T14S R1W	
S9	S10	S15
	S15	
	1993	

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone E of the corner.

The corner is located 3 lks. S of a fence line, 3 strand barbwire, bears E and W, on E slope in juniper growth.

---

N. 0°36.3' W., on the west boundary of section 10.

Over mountain land, through sagebrush and juniper growth.

37.166

Point for the E 1/4 section corner of section 9 only, at midpoint between closing corners.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T14S R1W  
1/4 |  
S 9 |  
1993

Raise a mound of stone W of the corner.

The corner is located on a steep SW slope in buckbrush and juniper growth.

**39.760** Point for the 1/4 section corner of section 10 only, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T14S R1W  
| 1/4  
| S10  
1993

Raise a mound of stone E of the corner.

The corner is located on a SW slope in buckbrush and juniper growth.

**56.936** Point for the N 1/16 section corner of section 9 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T14S R1W  
N 1/16 |  
S9 |  
1993

The corner is located on a SE slope in bitterbrush and scattered juniper growth.

**76.706** The closing corner of sections 4 and 9, monumented with a conglomerate stone, 15x8x6 ins., firmly set and plainly marked CC on the W face and 5 grooves on the S and 3 grooves on E face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top of aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

T14S R1W	
C S4	S10
C S9	
1993	

Deposit the marked stone alongside the aluminum post.

The corner is located on a broken SE slope in bitterbrush and juniper growth.

**79.520** The corner of sections 3 and 10, monumented with a granite stone, 16x10x8 ins., firmly set and plainly marked with 5 notches on the S and 3 notches on the E edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with aluminum cap marked:

T14S R1W	
S4	S3
	S10
1993	

Deposit the marked stone alongside the aluminum post.

No remaining evidence of the original bearing tree was found.

The corner is located on a E slope in bitterbrush and juniper growth.

---

From the corner of sections 28, 29, 32, and 33, monumented with a Juab County aluminum post, 2 1/2 ins. diam., extending 6 ins. out of ground, and is accepted as a careful and faithful perpetuation of the position of the original corner, with the aluminum cap marked:

JUAB COUNTY	
T14S R1W	
S29	S28
S32	S33
1990	

The corner is located in a fence corner, 4 strand barbwire, bears N, S, and W.

No remaining evidence of the original rock corner or bearing trees were found.

N. 0°10.2' W., between sections 28 and 29.

Over rolling bench land, through reseed area.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

**39.615** The 1/4 section corner of sections 28 and 29, monumented with a sandstone, 24x14x8 ins., firmly set in a mound of stone and plainly marked 1/4 on the W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a mound of stone, with aluminum cap marked:

T14S R1W  
1/4  
S29 | S28  
1993

Deposit the marked stone alongside the aluminum post.

No remaining evidence of the original bearing trees were found.

The corner is located 3 lks. E of a netwire fence line, bears N and S, on a S slope in native grasses.

---

N. 0°42.8' W., beginning new measurement.

**20.040** Point for the N 1/16 section corner of sections 28 and 29.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T14S R1W  
N 1/16  
S29 | S28  
1993

Set a steel fence post alongside the aluminum post.

The corner is located 17 lks. W of a netwire fence line, bears N and S, on rolling E slope in cultivated land.

**40.080** The corner of sections 20 and 29, monumented with a netwire fence corner, bears S and W, and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T14S R1W  
 $\frac{S20}{S29}$  | S28  
 1993

The corner is located on a gently rolling E slope, with cultivated land to the E and N of the corner.

---

From the E 1/4 section corner of section 17 only, monumented with a blue limestone, 16x8x6 ins., firmly set and plainly marked 1/4 on the W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T14S R1W  
 1/4  
 S17 |  
 1993

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone W of the corner.

Set a steel fence post alongside the aluminum post.

The corner is located on a gentle E slope in juniper growth.

---

N. 0°38.8' W., on the east boundary of section 17.

**40.035** The corner of sections 8, 9, 16 and 17, monumented with a limestone, 18x10x8 ins., firmly set in a mound of stone and plainly marked with, 4 notches on S and E edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T14S R1W  
 $\frac{S8}{S17}$  |  $\frac{S9}{S16}$   
 1993

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone W of the corner.

The corner is located on a NE slope in burned area.

---

N. 89°33.2' E., between sections 9 and 16.

Over mountainous land, through burned area.

**39.833**

The 1/4 section corner of sections 9 and 16, monumented with a limestone, 18x6x4 ins., firmly set and plainly marked 1/4 on the N face.

From which the original bearing tree.

A juniper, 10 ins. diam., bears N. 46° W., 3 lks. dist., marked with a blaze.

No remaining evidence of the other original bearing tree was found.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with aluminum cap marked:

	T14S R1W
1/4	<u>S9</u>
	S16
	1993

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone W of the corner.

The corner is located 1 chain S of a firebreak, bears E and W, on SW slope in juniper growth.

---

S. 89°31.3' E., beginning new measurement.

**38.697**

The closing corner of sections 9 and 16.

---

From the corner of sections 8, 9, 16, and 17.

N. 0°16.2' W., between sections 8 and 9.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Over mountainous land, through burned area and juniper growth.

**39.482** The 1/4 section corner of sections 8 and 9, monumented with a trachyte stone, 18x8x6 ins., firmly set and plainly marked 1/4 on the W face.

From which the original bearing trees:

A juniper, 10 ins. diam., bears S. 70° E., 15 lks. dist.,  
marked 1/4 S9 BT.

A juniper, 10 ins. diam., bears S. 53° W., 36 lks. dist., marked  
1/4 S8 BT.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T14S R1W  
1/4  
S8 | S9  
1993

Deposit the marked stone alongside the aluminum post.

The corner is located on a S slope in juniper growth.

N. 0°33.3' W., beginning new measurement.

**19.987** Point for the N 1/16 section corner of sections 8 and 9; not monumented.

**39.974** The corner of sections 4, 5, 8 and 9, monumented with a granite stone, 18x9x6 ins., firmly set and plainly marked, with 4 notches on the E and 5 notches on S edges.

From which the original bearing tree.

A juniper, 12 ins. diam., bears S. 70° W., 60 lks. dist., marked with faint scribe marks.

No remaining evidence of the other original bearing tree was found.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, and in a mound of stone, 4 ft. base to top, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

T14S R1W	
S5	S4
S8	S9
1993	

Deposit the marked stone alongside the aluminum post.

The corner is located on a SE slope in burned area.

From this corner, U.S. Coast and Geodetic Survey triangulation station "CEDAR",  
monumented with a standard bronze cap, bears N. 13°33.4' E., 55.987 chains distance.

S. 89°28.2' E., between sections 4 and 9.

Over mountain land, through juniper and burned areas.

**19.786** Point for the W 1/16 section corner of sections 4 and 9.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum  
cap marked:

T14S R1W	
W 1/16	<u>S4</u>
	S9
1993	

from which:

A small spring drains S, bears N. 78°47' W., 2.02 chains dist.

Raise a mound of stone N of the corner.

The corner is located on a SE slope in juniper growth.

**39.572** The 1/4 section corner of sections 4 and 9, monumented with a trachyte stone, 16x8x7 ins.,  
firmly set and plainly marked, 1/4 on the N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum  
cap marked:

T14S R1W	
1/4	<u>S4</u>
	S9
1993	

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone N of the corner.

The corner is located on a W slope in burned area.

S. 89°57.7' E., beginning new measurement.

**19.341** Point for the E 1/16 section corner of sections 4 and 9.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T14S R1W  
E 1/16 S4  
S9  
1993

Raise a mound of stone N of the corner.

The corner is located on a S slope in native grasses and juniper growth.

**38.682** The closing corner of sections 4 and 9.

From the corner of sections 5, 6, 31, and 32, on the south boundary of the township, hereinbefore described.

N. 0°38.0' E., between sections 31 and 32.

Over mountain land, through reseed area.

**39.407** The 1/4 section corner of sections 31 and 32, monumented with a Juab County aluminum post, 2 1/2 ins. diam., extending 6 ins. out of the ground. This corner is accepted as a careful and faithful perpetuation of the position of the original corner, with the aluminum cap marked.

JUAB COUNTY  
T14S R1W  
1/4 S31 | S32  
1990

No remaining evidence of the original bearing trees were found.

The corner is located on a SE slope in railed area.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

N. 0°37.8' E., beginning new measurement.

- 39.519** The corner of sections 29, 30, 31, and 32, monumented with a Juab County aluminum post, 2 1/2 ins. diam., extending 8 ins. out of the ground.

From which the original bearing tree.

A juniper, 12 ins. diam., bears S. 45° W., 33 lks. dist., marked  
T14S R1W S31 BT.

No remaining evidence of the other original bearing tree was found.

The aluminum cap is marked:

JUAB COUNTY	
T14S R1W	
S30	S29
S31	S32
1990	

The corner is located in a fence corner, 4 strand barbwire, bears S and E, on steep N slope in dense juniper growth.

---

From the corner of sections 28, 29, 32, and 33.

S. 89°45.5' W., between sections 29 and 32.

Over mountain land, through reseed area.

- 39.588** The 1/4 section corner of sections 29 and 32, monumented with a Juab County aluminum post, 2 1/2 ins. diam., extending 6 ins. out of the ground. This corner is accepted as a careful and faithful perpetuation of the position of the original corner, with the aluminum cap marked.

JUAB COUNTY	
T14S R1W	
1/4	S29
	S32
1990	

No remaining evidence of the original bearing trees were found.

The corner is located in a fence line, 4 strand barbwire, bears E and W, on gentle E slope in reseed area.

---

S. 89°45.5' W., beginning new measurement.

- 39.593** The corner of sections 29, 30, 31, and 32.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

N. 89°44.0' W., between sections 30 and 31.

Over mountain land, through juniper growth.

**38.875** Point for the 1/4 section corner of sections 30 and 31, as determined from the remains of the original bearing tree.

A juniper, 10 ins. in diam., bears S. 20° W., 110 lks. dist., dimly marked:

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T14S R1W  
1/4  $\frac{S30}{S31}$   
1993

The corner is located on W slope in scattered juniper growth.

N. 89°52.8' W., beginning new measurement.

**60.933** Point for the 100 1/16 section corner of sections 30 and 31; not monumented.

**81.244** Point for the 120 1/16 section corner of sections 30 and 31.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T14S R1W  
S30  
1/16  $\frac{\quad}{S31}$  120  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on a gentle W slope in cultivated land.

**101.555** Point for the 140 1/16 section corner of sections 30 and 31; not monumented.

**168.578** The closing corner of sections 30 and 31 on the west boundary of the township, hereinbefore described.

From the corner of sections 29, 30, 31, and 32.

N. 0°02.3' W., between sections 29 and 30.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Over mountain land, through juniper growth.

- 39.545** Point for the 1/4 section corner of sections 29 and 30, at proportionate distance; no remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, with aluminum cap marked:

T14S R1W	
1/4	
S30	S29
1993	

The corner is located on a SE slope in juniper growth.

- 79.090** Point for the corner of sections 19, 20, 29, and 30, as determined from the remains of a original bearing tree. The original rock corner, a trachyte, 18x10x5 ins., plainly marked with 5 notches on the E and 2 notches on the S edges was found lying loose on top of the ground.

The original bearing tree:

A juniper, 12 ins. diam., bears N. 69° E., 108 lks. dist. marked with faint scribe marks.

No remaining evidence of the other original bearing trees were found.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base, with aluminum cap marked:

T14S R1W	
S19	S20
S30	S29
1993	

Deposit the marked stone alongside the aluminum post.

The corner is located 68 lks. S of an old fence line, 4 strand barbwire, bears E and W, irregularly in small draw, drains SE.

---

From the corner of sections 20 and 29 only.

S. 89°34.7' W., between sections 20 and 29.

Over mountain land, through reseed area and burned area.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS****39.354**

The 1/4 section corner of sections 20 and 29, monumented with a limestone, 16x12x8 ins., firmly set and plainly marked 1/4 on the N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T14S R1W
1/4	<u>S20</u>
	S29
	1993

Raise a mound of stone N of the corner.

Set a steel fence post alongside the aluminum post.

The corner is located 24 lks. N of a fence line, 4 strand barbwire, bears E and W irregularly, on W slope in juniper growth.

---

S. 89°03.2' W., beginning new measurement.

**39.253**

The corner of sections 19, 20, 29, and 30.

---

N. 89°58.2' W., between sections 19 and 30.

Over mountain land, through juniper growth.

**40.326**

Point for the 1/4 section corner of sections 19 and 30, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T14S R1W
1/4	<u>S19</u>
	S30
	1993

Raise a mound of stone N of the corner.

Set a steel fence post alongside the aluminum post.

The corner is located on a W slope in reseed area.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS****60.489**

Point for the W 1/16 section corner of sections 19 and 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T14S R1W
W 1/16	<u>S19</u>
	S30
	1993

Raise a mound of stone N of the corner.

Set a steel fence post alongside the aluminum post.

The corner is located on a W slope in sagebrush and scattered juniper growth.

**100.815**

Point for the 100 1/16 section corner of sections 19 and 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap marked:

	T14S R1W
100 1/16	<u>S19</u>
	S30
	1993

The corner is located on a SE slope in sagebrush and scattered juniper.

**120.978**

Point for the 120 1/16 section corner of sections 19 and 30; not monumented.

**181.467**

Point for the 180 1/16 section corner of sections 19 and 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

	T14S R1W
180 1/16	<u>S19</u>
	S30
	1993

The corner is located on a S slope in juniper growth.

**201.630**

Point for the 200 1/16 section corner of sections 19 and 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

T14S R1W  
200 1/16  $\frac{S19}{S30}$   
1993

Raise a mound of stone N of the corner.

The corner is located on gentle NW slope in a burned area.

**207.125** The closing corner of sections 19 and 30, on the west boundary of the township, hereinbefore described.

---

From the corner of sections 19, 20, 29, and 30.

N. 0°19.1' W., between sections 19 and 20.

Over mountain land, through juniper growth.

**39.697** The 1/4 section corner of sections 19 and 20, monumented with a granite stone, 18x10x6 ins., firmly set and plainly marked 1/4 on the W face and witnessed by a mound of stone to the W.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T14S R1W  
1/4  
S19 | S20  
1993

Raise a mound of stone W of the corner.

Deposit the marked stone alongside the aluminum post.

The corner is located on a W slope in juniper growth.

---

N. 1°03.2' W., beginning new measurement.

**39.75** Low ridge bears E and W.

**40.775** The corner of sections 17, 18, 19 and 20, monumented with a trachyte stone, 16x10x5 ins. firmly set and plainly marked with 5 notches on the E and 3 notches on the S edges.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From which the original bearing trees:

A juniper, 12 ins. diam., bears N. 7° E., 25 lks. dist., marked  
T14S R1W S17 BT.

A juniper, 12 ins. diam., bears S. 49° E., 28 lks. dist., marked  
T14S R1W S20 BT.

A juniper, 5 in. limb, bears S. 25° W., 49 lks. dist., marked  
T14S R1W S19 BT.

A juniper, 8 ins. diam., bears N. 88°15' W., 15 lks. dist., marked  
T14S R1W S18 BT.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum  
cap marked:

T14S R1W	
S18	S17
S19	S20
1993	

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone W of the corner.

The corner is located on a NE slope in juniper growth.

From the corner of sections 17 and 20 only, monumented with a conglomerate stone,  
19x10x6 ins., firmly set and plainly marked with, 4 notches on the E and 3 notches on the  
S edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum  
cap marked:

T14S R1W	
S17	S21
S20	
1993	

Deposit the marked stone alongside the aluminum post.

No remaining evidence of the original bearing trees were found.

Raise a mound of stone W of the corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set a steel fence post alongside the aluminum post.

The corner is located on gentle E slope.

S. 89°43.8' W., between sections 17 and 20.

Over mountain land, through juniper growth.

**39.625** Point for the 1/4 section corner of sections 17 and 20, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with aluminum cap marked:

	T14S	R1W
1/4	<u>S17</u>	
	S20	
	1993	

The corner is located 30 lks. N of a draw, drains E, on steep S slope in scattered juniper growth.

**79.250** The corner of sections 17, 18, 19, and 20.

---

N. 0°06.7' W., between sections 17 and 18.

Over mountain land, through juniper growth.

**39.824** The 1/4 section corner of sections 17 and 18, monumented with a quartzite stone, 14x8x6 ins., firmly set and plainly marked 1/4 on the W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T14S	R1W
	1/4	
S18		S17
	1993	

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone W of the corner.

The corner is located on a W slope in sagebrush.

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

N. 0°27.1' W., beginning new measurement.

**40.213**

The corner of sections 7, 8, 17, and 18, monumented with an aluminum post, 2 1/2 ins. diam., extending 6 ins. out of the ground, with aluminum cap, marked as described in the official record of the 1991 resurvey by R. A. Zaninovich.

From the corner of sections 8, 9, 16, and 17.

S. 89°49.1' W., between sections 8 and 17.

Over mountain land, through juniper growth.

**19.720**

Point for the E 1/16 section corner of sections 8 and 17.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T14S R1W  
E 1/16  $\frac{S8}{S17}$   
1993

The corner is located on a gentle W slope in juniper growth.

**39.440**

The 1/4 section corner of sections 8 and 17, monumented with a flintstone, 20x16x12 ins., firmly set and plainly marked 1/4 on the N face, and witnessed by a mound of stone to W.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T14S R1W  
1/4  $\frac{S8}{S17}$   
1993

Raise a mound of stone W of the corner.

No remaining evidence of the original bearing trees were found.

The corner is located on a SW slope in juniper growth.

S. 89°46.0' W., beginning new measurement.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS****39.726**

The corner of sections 7, 8, 17 and 18.

---

Reestablishment of the Survey by Stewart and Stewart in 1898  
and the Resurvey by R.A. Zaninovich in 1991

---

From the 1/4 section corner of sections 7 and 8, monumented with an aluminum post, 2 1/2 ins. diam., extending 6 ins. out of the ground, with aluminum cap marked and witnessed as described in the official record of the 1991 resurvey by R. A. Zaninovich.

N. 2°04.9' W., beginning new measurement.

**19.622**

Point for the N 1/16 section corner of sections 7 and 8; not monumented.

**39.244**

The corner of sections 5, 6, 7, and 8, monumented with an aluminum post, 2 1/2 ins. diam., extending 6 ins. out of the ground, with aluminum cap, marked as described in the official record of the 1991 resurvey by R. A. Zaninovich.

---

Reestablishment of the Survey by Stewart and Stewart in 1898

---

From the corner of sections 4, 5, 8, and 9.

S. 89°45.0' W., between sections 5 and 8.

Over mountain land, through juniper growth.

**39.346**

The 1/4 section corner of sections 5 and 8, monumented with a limestone, 18x12x6 ins., firmly set and plainly marked 1/4 on the N face.

From which the original bearing trees:

A juniper, 10 ins. diam., bears N. 75° W., 65 lks. dist.,  
marked 1/4 S5 BT.

A juniper 10 ins. diam., bears S. 70° W., 65 lks. dist.,  
marked 1/4 S8 BT.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

T14S R1W  
1/4  $\frac{S5}{S8}$   
1993

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone W of the corner.

The corner is located on a gentle SW slope, in juniper growth.

S. 89°05.3' W., beginning new measurement.

**20.234** Point for the W 1/16 section corner of sections 5 and 8.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T14S R1W  
W 1/16  $\frac{S5}{S8}$   
1993

Set a steel fence post alongside the aluminum post.

The corner is located on a S slope in burned area.

**40.468** The corner of sections 5, 6, 7, and 8.

---

The Subdivision of Section 8,  
T. 14 S., R. 1 W., Salt Lake Meridian, Utah.

---

From the 1/4 section corner of sections 8 and 17.

N. 0°21.1' W., on the N - S center line of section 8.

**39.578** Point for the center 1/4 section corner, at intersection with the E - W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T14S R1W  
C 1/4 S8  
1993

THE SUBDIVISION OF SECTION 8,  
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

The corner is located on a W slope in juniper growth.

**59.493** Point for the center N 1/16 section corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, and in a mound of stone, 3 ft. base to top, with aluminum cap marked:

T14S R1W  
C  
N 1/16 | S8  
C  
1993

The corner is located on top of small spur, slopes SW in juniper growth.

**79.408** The 1/4 section corner of sections 5 and 8.

---

From the 1/4 section corner of sections 8 and 9.

S. 89°57.3' W., on the E - W center line of section 8.

**39.492** The center 1/4 section corner.

**59.136** Point for the center W 1/16 section corner; not monumented.

**78.780** The 1/4 section corner of sections 7 and 8.

---

From the point for the center W 1/16 section corner of section 8.

N. 01°12.6' W., on the N - S center line of the NW 1/4 of section 8.

**19.766** Point for the NW 1/16 section corner at intersection with the E - W center line of the NW 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T14S R1W  
NW 1/16 S8  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on a S slope in dense juniper growth.

**39.532** The W 1/16 section corner of sections 5 and 8.

THE SUBDIVISION OF SECTION 8,  
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the center N 1/16 section corner of section 8.

S. 89°30.8' W., on the E - W center line of the NW 1/4.

**19.939** The NW 1/16 section corner of section 8.

**39.878** Point for the N 1/16 section corner of sections 7 and 8.

---

The Subdivision of Section 9,  
T. 14 S., R. 1 W., Salt Lake Meridian, Utah.

---

From the 1/4 section corner of sections 9 and 16.

N. 0°36.1' W., on the N - S center line of section 9.

**39.197** Point for the center 1/4 section corner, at intersection with the E - W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, and in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

T14S R1W  
C 1/4 S9  
1993

The corner is located on a SW slope in juniper growth.

**58.989** Point for the center N 1/16 section corner of section 9.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T14S R1W  
C  
N 1/16 | S9  
C  
1993

from which:

An old fence corner, 3 strand barbwire, bears S. 32°38' W.,  
63 lks. dist., bears E and S.

The corner is located on E slope in native grasses, in partial burned area of juniper growth.

**78.781** The 1/4 section corner of sections 4 and 9.

THE SUBDIVISION OF SECTION 9,  
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the E 1/4 section corner of section 9 only.

S. 89°58.1' W., on the E - W center line of section 9.

**19.343** Point for the center E 1/16 section corner of section 9; not monumented.

**38.686** The center 1/4 section corner.

**58.488** Point for the center W 1/16 section corner of section 9; not monumented.

**78.290** The 1/4 section corner of sections 8 and 9.

---

From the point for the center E 1/16 section corner of section 9.

N. 0°36.1' W., on the N - S center line of the NE 1/4.

**19.781** Point for the NE 1/16 section corner at intersection with E - W center line of the NE 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T14S R1W  
NE 1/16 S9  
1993

Raise a mound of stone W of the corner.

Set a steel fence post alongside the aluminum post.

The corner is located 20 lks. S of an old fallen fence line, 3 strand barbwire, bears E and W and 1.00 ch. W of a trail road, bears SE and NW, on S slope in native grasses and juniper growth.

**39.562** The E 1/16 section corner of sections 4 and 9.

---

From the N 1/16 section corner of section 9 only.

N. 89°59.8' W., on the E - W center line of the NE 1/4.

**19.342** The NE 1/16 section corner of section 9.

**38.684** The center N 1/16 section corner of section 9.

---

THE SUBDIVISION OF SECTION 9,  
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the point for the center W 1/16 section corner of section 9.

N. 0°34.6' W., on the N - S center line of the NW 1/4.

**19.889**

Point for the NW 1/16 section corner of section 9, at intersection with the E - W center line of the NW 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., on solid rock and in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

T14S R1W  
NW 1/16 S9  
1993

The corner is located on a E slope in burned area.

**39.778**

The W 1/16 section corner of sections 4 and 9.

From the center N 1/16 section corner of section 9.

N. 89°45.0' W., on the E - W center line of the NW 1/4.

**19.794**

The NW 1/16 section corner of section 9.

**39.588**

The point for the N 1/16 section corner of sections 8 and 9.

The Subdivision of Section 17,  
T. 14 S., R. 1 W., Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 17 and 20.

N. 0°12.3' W., on the N - S center line of section 17.

**39.870**

Point for the center 1/4 section corner, at intersection with the E - W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., on solid rock and in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

T14S R1W  
C 1/4 S17  
1993

The corner is located on a steep broken SE slope in scattered juniper growth.

**80.011**

The 1/4 section corner of sections 8 and 17.

THE SUBDIVISION OF SECTION 17,  
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the E 1/4 section corner of section 17 only.

S. 89°39.8' W., on the E - W center line of section 17.

**19.877** Point for the center E 1/16 section corner of section 17.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T14S R1W  
C     E 1/16     C  
          S17  
          1993

Raise a mound of stone N of the corner.

The corner is located on a NW slope in burned area.

**39.754** The center 1/4 section corner of section 17.

**79.310** The 1/4 section corner of sections 17 and 18.

From the center E 1/16 section corner of section 17.

N. 0°25.5' W., on the N - S center line of the NE 1/4.

**40.086** The E 1/16 section corner of sections 8 and 17.

The Subdivision of Section 20,  
T. 14 S., R. 1 W., Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 20 and 29.

N. 0°25.1' W., on the N - S center line of section 20.

**39.614** Point for the center 1/4 section corner, at intersection with the E - W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a collar of stone to top, with aluminum cap marked:

T14S R1W  
C 1/4 S20  
          1993

THE SUBDIVISION OF SECTION 20,  
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set a steel fence post alongside the aluminum post.

The corner is located on a E slope in juniper growth.

**80.004** The 1/4 section corner of sections 17 and 20.

---

From the E 1/4 section corner of section 20 only, monumented with a limestone, 22x12x10 ins., firmly set and plainly marked 1/4 on the W face.

From which the original bearing tree.

A juniper, 8 ins. diam., bears S. 82° E., 48 lks. dist., marked  
1/4 S21 BT.

No remaining evidence of the other original bearing was found.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T14S R1W  
1/4  
S20 |  
1993

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

The corner is located on a gentle E slope in juniper growth.

S. 89°10.6' W., on the E - W center line of section 20.

**39.636** The center 1/4 section corner.

**78.814** The 1/4 section corner of sections 19 and 20.

---

The Subdivision of Section 30,  
T. 14 S., R. 1 W., Salt Lake Meridian, Utah.

---

From the 1/4 section corner of sections 30 and 31.

N. 1°05.9' W., on the N - S center line of section 30.

**19.721** Point for the center S 1/16 section corner of section 30; not monumented.

THE SUBDIVISION OF SECTION 30,  
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS****39.442**

Point for the center 1/4 section corner, at intersection with the E - W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T14S R1W  
C 1/4 S30  
1993

The corner is located on a steep NW slope in scattered juniper.

**59.198**

Point for the center N 1/16 section corner of section 30; not monumented.

**78.954**

The 1/4 section corner of sections 19 and 30.

---

From the 1/4 section corner of sections 29 and 30.

N. 89°54.6' W., on the E - W center line of section 30.

**39.600**

The center 1/4 section corner of section 30.

**59.822**

Point for the center W 1/16 section corner of section 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T14S R1W  
C  $\frac{W\ 1/16}{S30}$  C  
1993

**100.266**

Point for the center 100 1/16 section corner of section 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T14S R1W  
1/16  
C  $\frac{\quad}{S30}$  100  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level cultivated land.

**120.488**

Point for the center 120 1/16 section corner of section 30.

THE SUBDIVISION OF SECTION 30,  
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T14S R1W  
1/16  
C ————— 120  
S30  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level cultivated land.

**140.710** Point for the center 140 1/16 section corner of section 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T14S R1W  
1/16  
C ————— 140  
S30  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on a E slope in sagebrush and juniper growth.

**207.240** The 1/4 section corner of section 30 only, on the west boundary of the township, hereinbefore described.

From the point for the 100 1/16 section corner of sections 30 and 31.

N. 0°43.1' W., on the N - S 100 1/16 line of the SW 1/4 of section 30.

**19.700** Point for the S 100 1/16 section corner at the intersection with the E - W center line of the SW 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a mound of stone to top, with aluminum cap marked:

T14S R1W  
1/16  
S ————— 100  
S30  
1993

Set a steel fence post alongside the aluminum post.

THE SUBDIVISION OF SECTION 30,  
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

The corner is located on steep NW slope in burned area.

**39.400** The center 100 1/16 section corner.

---

From the 120 1/16 section corner of sections 30 and 31.

N. 0°35.5' W., on the N - S 120 1/16 line of the SW 1/4 of section 30.

**19.694** Point for the S 120 1/16 section corner at intersection with the E - W center line of the SW 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

	T14S R1W	
	1/16	
S	—————	120
	S30	
	1993	

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level cultivated land.

**39.388** The center 120 1/16 section corner of section 30.

---

From the point for the 140 1/16 section corner of sections 30 and 31.

N. 0°27.9' W., on the N - S 140 1/16 line of the SW 1/4 of section 30.

**19.687** Point for the S 140 1/16 section corner at intersection with the E - W center line of the SW 1/4 of section 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T14S R1W	
	1/16	
S	—————	140
	S30	
	1993	

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level cultivated land.

THE SUBDIVISION OF SECTION 30,  
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

- 39.374** The center 140 1/16 section corner of section 30.
- 
- From the point for the center S 1/16 section corner of section 30.
- N. 89°53.8' W., on the E - W center line of the SW 1/4 of section 30.
- 60.801** The S 100 1/16 section corner.
- 81.068** The S 120 1/16 section corner.
- 101.335** The S 140 1/16 section corner.
- 168.098** The S 1/16 section corner of section 30 only, on the west boundary of the township, hereinbefore described.
- 
- From the center W 1/16 section corner of section 30.
- N. 1°01.0' W., on the N - S center line of the NW 1/4 of section 30.
- 19.745** Point for the NW 1/16 section corner of section 30, at intersection with the E - W center line of the NW 1/4 of section 30; not monumented.
- 39.490** The W 1/16 section corner of sections 19 and 30.
- 
- From the center 100 1/16 section corner of section 30.
- N. 0°51.1' W., on the N - S 100 1/16 line of the NW 1/4 of section 30.
- 19.724** Point for the N 100 1/16 section corner at intersection with the E - W center line of the NW 1/4.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:
- T14S R1W  
1/16  
N ————— 100  
S30  
1993
- The corner is located 60 lks. N of a dry wash, drains SW on gently rolling land in sagebrush and scattered juniper.
- 39.448** The 100 1/16 section corner of sections 19 and 30.

THE SUBDIVISION OF SECTION 30,  
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the center 120 1/16 section corner of section 30.

N 0°46.2' W., on the N - S 120 1/16 line of the NW 1/4 of section 30.

**19.712** Point for the N 120 1/16 section corner at intersection with the E - W center line of the NW 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T14S R1W  
1/16  
N ————— 120  
S30  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on a SE slope in native grasses and scattered juniper growth.

**39.424** Point for the 120 1/16 section corner of sections 19 and 30.

---

From the point for the center N 1/16 section corner of section 30.

N. 89°56.5' W., on the E - W center line of the NW 1/4 of section 30.

**20.192** The point for the NW 1/16 section corner.

**60.577** The N 100 1/16 section corner.

**80.767** The N 120 1/16 section corner.

**167.197** The point for the N 1/16 section corner of section 30 only, on the west boundary of the township, hereinbefore described.

---

The Subdivision of Section 31,  
T. 14 S., R. 1 W., Salt Lake Meridian, Utah.

---

From the 1/4 section corner of sections 6 and 31 on the south boundary of the township, hereinbefore described.

N. 1°05.4' E., on the N - S center line of section 31.

**19.674** Point for the center S 1/16 section corner of section 31; not monumented.

THE SUBDIVISION OF SECTION 31,  
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

**39.348** Point for the center 1/4 section corner, at intersection with the E - W center line; not monumented.

**79.107** The 1/4 section corner of sections 30 and 31.

---

From the 1/4 section corner of sections 31 and 32.

S. 89°54.4' W., on the E - W center line of section 31.

**39.201** The point for the center 1/4 section corner of section 31.

**119.757** Point for the center 120 1/16 section corner of section 31.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T14S R1W  
1/16  
C ————— 120  
S31  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on a gentle W slope in native grasses.

**139.896** Point for the center 140 1/16 section corner of section 31; not monumented.

**207.234** The point for the 1/4 section corner of section 31 only, on the west boundary of the township, hereinbefore described.

---

From the point for the 120 1/16 section corner of section 31 only on the south boundary of the township, hereinbefore described.

N. 0°09.6' E., on the N - S 120 1/16 line of the SW 1/4 of section 31.

**19.920** Point for the S 120 1/16 section corner at intersection with the E - W center line of the SW 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, an in a collar of stone, with aluminum cap marked:

THE SUBDIVISION OF SECTION 31,  
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T14S R1W  
1/16  
S ————— 120  
S31  
1993

Set a steel fence post alongside the aluminum post.  
The corner is located on gentle W slope in native grasses.

**39.840** The center 120 1/16 section corner of section 31.

---

From the 140 1/16 section corner of section 31 only, on the south boundary of the township, hereinbefore described.

N. 0°04.1' W., on the N - S 140 1/16 line of the SW 1/4 of section 31.

**19.984** Point for the S 140 1/16 section corner of section 31, at intersection with the E - W center line of the SW 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, an in a collar of stone, with aluminum cap marked:

T14S R1W  
1/16  
S ————— 140  
S31  
1993

Set a steel fence post alongside the aluminum post.  
The corner is located on gentle W slope in native grasses.

**39.968** The point for the center 140 1/16 section corner of section 31.

---

From the point for the center S 1/16 section corner of section 31.

S. 89°43.4' W., on the E - W center line of the SW 1/4 of section 31.

**80.240** The S 120 1/16 section corner of section 31.

**100.300** The S 140 1/16 section corner of section 31.

**167.752** The point for the S 1/16 section corner of section 31 only on the west boundary of the township, hereinbefore described.

---

THE SUBDIVISION OF SECTION 31,  
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the center 120 1/16 section corner of section 31.

N. 0°05.1' E., on the N - S 120 1/16 line of the NW 1/4 of section 31.

**40.060**

The 120 1/16 section corner of sections 30 and 31.

---

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD ASSISTANTS**

---

Name	Capacity
Gail Reynolds	Land Surveyor
Shawn Peterson	Survey Technician


## CERTIFICATE OF SURVEY

I, *Ferrel D. Reynolds, Cadastral Surveyor*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *8th day of April, 1993*, I have dependently resurveyed a portion of the south and west boundaries, a portion of the subdivisional lines and subdivided sections 8, 9, 17, 20, 30 and 31 in Township 14 South, Range 1 West ,

of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

April 22, 1997

Date

  
 (Cadastral Surveyor)

Date

(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
 Salt Lake City, Utah


The foregoing field notes of the *dependent resurvey of a portion of the south and west boundaries, a portion of the subdivisional lines and the subdivision of sections 8, 9, 17, 20, 30 and 31 in Township 14 South, Range 1 West, Salt Lake Meridian, Utah*,

executed by *Ferrel D. Reynolds, Cadastral Surveyor*

having been critically examined and found correct, are hereby approved.

April 24, 1997

Date



(Chief Cadastral Surveyor for Utah)