

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF
THE DEPENDENT RESURVEY OF
A PORTION OF THE NORTH BOUNDARY,
A PORTION OF THE SAN PETE INDIAN RESERVATION BOUNDARY,
AND A
PORTION OF THE SUBDIVISIONAL LINES
AND THE
SUBDIVISION OF SECTIONS 3, 10, 14, 15, 22, 23, 27, AND 34
IN
TOWNSHIP 20 SOUTH, RANGE 1 WEST
OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Ferrel D. Reynolds
Cadastral Surveyor

Under special instructions dated *June 9, 1993*, approved *June 14, 1993*, which provided for the surveys included under Group Number *802*, and assignment instructions dated *June 15, 1993*.

Survey commenced *June 28, 1993*

Survey completed *August 12, 1993*

INDEX DIAGRAM

Township 20 South, Range 1 West

				2			
6	5	4	34	3	26	2	1
				15			
				33			
7	8	9	32	10	25	11	12
				13			
				32		25	
18	17	16	31	15	24	14	13
				11			
				30		23	
19	20	21	29	22	22	23	24
				7		19	
				29		22	
30	29	28	28	27	21	26	25
				4			
				27			
				3			
31	32	33	26	34	35		36

The Subdivision of Section 3.....Page 36
 The Subdivision of Section 10.....Page 36
 The Subdivision of Section 14.....Page 37
 The Subdivision of Section 15.....Page 38
 The Subdivision of Section 22.....Page 39
 The Subdivision of Section 23.....Page 39
 The Subdivision of Section 27.....Page 40
 The Subdivision of Section 34.....Page 42

TOWNSHIP 20 SOUTH, RANGE 1 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

The following field notes describe the dependent resurvey of a portion of the north boundary, a portion of the San Pete Indian Reservation Boundary and a portion of the subdivisional lines and the subdivision of sections 3, 10, 14, 15, 22, 23, 27, and 34, in Township 20 South, Range 1 West, Salt Lake Meridian, Utah.

History of Surveys

	Surveyed by		Rear. or Resurveyed by	
NORTH BOUNDARY				
Portion	C. Mogo	1856		
Portion			A.D. Ferron	1871
Portion	A. Jessen	1879	A. Jessen	1879
Portion	W.D. Heist and E.V. Woolley	1906	W.D. Heist and E.V. Woolley	1906
Portion			A. Talamantes	1909
Portion			G.E. Reynolds	1991
SOUTH BOUNDARY (Forth Standard Parallel South)				
Portion	C. Mogo	1856		
Portion	H. Fitzhugh	1882	H. Fitzhugh	1882
Portion			H.D. Heist and E.V. Woolley	1906
Portion			A. Talamantes	1909
Portion			H.W. Miller and I. Hayes	1915
Portion			G.E. Reynolds	1991-92
EAST BOUNDARY (Salt Lake Meridian)				
All	C. Mogo	1856		
Portion			A.D. Ferron	1871
Portion			A. Jessen	1879
WEST BOUNDARY				
All	W.D. Heist and E.V. Woolley	1906		
All			A. Talamantes	1909

TOWNSHIP 20 SOUTH, RANGE 1 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS**SUBDIVISION**

Portion	C. Mogo	1856		
Portion			A.D. Ferron	1871
Portion			A. Jessen	1879
Portion	W.D. Heist and E.V. Woolley	1906	W.D. Heist and E.V. Woolley	1906
Portion			A. Talamantes	1909

SAN PETE INDIAN RESERVATION BOUNDARY

All J.C. Clark 1866

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 802, dated June 9, 1993.

The directions of lines were determined by hour angle observations of the sun and Polaris, carried forward by sustained angulation. Distances were determined by electronic measurement.

Preliminary to the resurvey the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line notes are given herein.

The geographic position of the section corner of sections 3, 4, 33, and 34, on the south boundary of the township, as determined by ties made to U.S. Geological Survey triangulation station "BMX50", and U.S. Coast and Geodetic Survey triangulation station "REDMOND", is as follows:

Latitude 39° 01' 04.08" N. Longitude 111° 54' 28.79" W.
N.A.D. 1927

The mean magnetic declination as projected from the U.S. Geological Survey Magnetic Declination Map of 1990, is 13 1/2° E.

Dependent Resurvey of a Portion of the North Boundary,
T. 20 S., R. 1 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by C. Mogo in 1856,
and the Resurvey Executed by A. Jessen in 1879

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 20 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Note: There are numerous unrecorded corners located throughout the area being resurveyed, these are believed to have been set by John R. Stewart in 1915, for the State of Utah.

From the unrecorded corner of sections 2 and 3, on the north boundary of the township, monumented with an iron post, 2 ins. diam., 6 ins. above ground, set in cement, with brass cap marked:

<u>T19S</u>	<u>R1W</u>
S3	S2
T20S	R1W
1915	

This corner is accepted as the best available evidence of the original corner position, not remonumented.

S. 89° 29.5' W., on the north boundary of section 3.

8.911 The east closing corner of Tps. 19 and 20 S., R. 1 W., hereinafter described.

Dependent Resurvey of a Portion of the San Pete
Indian Reservation Boundary,
T. 20 S., R. 1 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
J.C. Clark in 1866

Note: While retracing the San Pete Indian Reservation Boundary, the following discrepancies were found, the closing corners from the west, established by A.D. Ferron in 1871 gave a tie to the south to the old original lot corners, these appear to fit fairly well. The closing corners from the east, established by A. Jessen in 1879 give a tie in the notes to Ferron's closing corners, on the ground it appears to have been a tie to the old original Indian Boundary corners, which makes the closing corners from the east actually south of Ferron's closing corners instead of north like the notes and plats state. The lot corners along this boundary that were not found, will serve no purpose and were not monumented.


Beginning at the southwest corner of lot 14 of the San Pete Indian Reservation Boundary, marked by an old mound of stone.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SAN PETE
 INDIAN RESERVATION BOUNDARY,
 T. 20 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS




Set a steel fence post alongside the aluminum post.

N. 0° 29.4' W., on the west boundary of the San Pete Indian Reservation.

Over gentle rolling bench land, through sagebrush and shadscale.

0.100 Point for the east closing corner of sections 27 and 34, on the S P I R B, at proportionate distance; there is no remaining evidence of the original corner.


Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:



Set a steel fence post alongside the aluminum post.

2.004 Point for the west closing corner of secs. 27 and 34 on the S P I R B, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:



Set a steel fence post alongside the aluminum post.

20.040 The corner of lot 14 on the S P I R B, monumented with a limestone, 18x12x10 ins., firmly set and dimly marked 1/2 on E face.

DEPENDENT RESURVEY OF A PORTION OF THE SAN PETE
INDIAN RESERVATION BOUNDARY,
T. 20 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

At the corner pont

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T20S R1W
S
P
S27 | I 1/2
R
B
1993

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 0° 31.4' W., on the west boundary of the San Pete Indian Reservation, beginning new measurement.

Over rolling bench land, through sagebrush and shadscale.

0.287 Point for the east witness point at the intersection of the E-W center line of the SE 1/4 of section 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T20S R1W
S27
S
P
I W P
R
B
1993

Set a steel fence post alongside the aluminum post.

2.028 Point for the west witness point at the intersection of the E-W center line of the SE 1/4 of section 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SAN PETE
 INDIAN RESERVATION BOUNDARY,
 T. 20 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T20S R1W
 S27
 |
 S
 P
 W P | I
 R
 B
 1993

Set a steel fence post alongside the aluminum post.

20.039 The corner of old lots 14 and 15, on the S P I R B, monumented with a limestone, 14x10x5 ins., firmly set and plainly marked 1 on east face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S R1W
 |
 S
 P
 S27 | I Cor 1
 R
 B
 1993

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 0° 28.1' W., on the west boundary of the San Pete Indian Reservation, beginning new measurement.

Over rolling bench land, through sagebrush and shadscale.

0.475 Point for the east witness point at the intersection of the E-W center line of section 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SAN PETE
INDIAN RESERVATION BOUNDARY,
T. 20 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T20S R1W
S27
|
S
P
I W P
R
B
1993

Set a steel fence post alongside the aluminum post.

2.053 Point for the west witness point at the intersection of the E-W center line of section 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T20S R1W
S27
|
S
P
W P I
R
B
1993

Set a steel fence post alongside the aluminum post.

20.038 The corner of lot 15, on the S P I R B, monumented with a limestone, 12x7x5 ins., firmly set and plainly marked 1/2 on E face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, with aluminum cap marked:

T20S R1W
|
S
P
S27 I 1/2
R
B
1993

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SAN PETE
INDIAN RESERVATION BOUNDARY,
T. 20 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0° 37.6' W., on the west boundary of the San Pete Indian Reservation, beginning new measurement.

Over rolling bench land, through sagebrush and shadscale.

- 20.893** Point for the east closing corner of sections 22 and 27, on the S P I R B, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 2 ins. below surface of old dirt road, bears NE and SW, with aluminum cap marked:

	T20S	R1W	
			S
			P
S27			I S22 C
			R S27 C
			B
			1993

- 22.145** Point for the west closing corner of sections 22 and 27, on the S P I R B, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

	T20S	R1W	
			S
			P
C S22			I S22
C S27			R
			B
			1993

Set a steel fence post alongside the aluminum post.

- 40.081** The corner of lot 49, on the S P I R B, monumented with a limestone, 20x16x8 ins., firmly set and plainly marked 1/2 on E face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SAN PETE
INDIAN RESERVATION BOUNDARY,
T. 20 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T20S R1W
S
P
S22 I 1/2
R
B
1993

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 0° 16.5' W., on the west boundary of the San Pete Indian Reservation, beginning new measurement.

Over rolling bench land, through sagebrush and shadscale.

20.057 The corner of lots 49 and 50, on the S P I R B, monumented with a limestone, 14x8x6 ins., firmly set and plainly marked 3 on the E face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S R1W
S
P
S22 I Cor 3
R
B
1993

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 0° 43.0' W., on the west boundary of the San Pete Indian Reservation, beginning new measurement.

Over rolling bench land, through sagebrush and shadscale.

1.012 Point for the east witness point at the intersection of the E-W center line of section 22.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SAN PETE
INDIAN RESERVATION BOUNDARY,
T. 20 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T20S R1W
S22
|
S
P
I W P
R
B
1993

Set a steel fence post alongside the aluminum post.

2.168 Point for the west witness point at the intersection of the E-W center line of section 22.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T20S R1W
S22
|
S
P
W P I
R
B
1993

Set a steel fence post alongside the aluminum post.

20.074 The corner of lot 50, on the S P I R B, monumented with a limestone, 14x8x6 ins., firmly set and plainly marked 1/2 on E face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T20S R1W
S22 | S
P
I 1/2
R
B
1993

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SAN PETE
 INDIAN RESERVATION BOUNDARY,
 T. 20 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0° 35.3' W., on the west boundary of the San Pete Indian Reservation, beginning new measurement.

Over rolling bench land, through sagebrush and shadscale.

20.018 The corner of lots 50 and 81, on the S P I R B, monumented with a limestone, 15x8x6 ins., firmly set and plainly marked 4 on E face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

```

T20S R1W
  |
  S
  P
S22 | I Cor 4
  |
  R
  B
    1993
    
```

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 0° 32.7' W., on the west boundary of the San Pete Indian Reservation, beginning new measurement.

Over rolling bench land, through sagebrush and shadscale.

1.213 The east closing corner of sections 15 and 22, on the S P I R B, monumented with a limestone, 18x10x10 ins., firmly set and plainly marked with a cross on the E face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

```

T20S R1W
  |
  S
  P
S22 | I S15 C
  |   |
  R   S22 C
  B
    1993
    
```

Deposit the marked stone alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SAN PETE
 INDIAN RESERVATION BOUNDARY,
 T. 20 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS


Raise a mound of stone E of the corner.

Set a steel fence post alongside the aluminum post.

2.273 The west closing corner of sections 15 and 22, on the S P I R B, monumented with a limestone, 14x10x4 ins., firmly set and plainly marked with a cross on the W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:



Deposit the marked stone alongside the aluminum post.


Raise a mound of stone W of the corner.

Set a steel fence post alongside the aluminum post.

40.101 The corner of lots 81 and 82, on the S P I R B, monumented with a limestone, 15x9x5 ins., firmly set and plainly marked 5 on E face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:



Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SAN PETE
 INDIAN RESERVATION BOUNDARY,
 T. 20 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0° 34.8' W., on the west boundary of the San Pete Indian Reservation, beginning new measurement.

Over rolling bench land, through sagebrush and shadscale.

1.339 Point for the east witness point at the intersection of the E-W center line of section 15.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S R1W
 S15
 |
 S
 |
 P
 |
 I W P
 |
 R
 |
 B
 |
 1993

Raise a mound of stone E of the corner.

Set a steel fence post alongside the aluminum post.

2.291 Point for the west witness point at the intersection of the E-W center line of section 15.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S R1W
 S15
 |
 S
 |
 P
 |
 I W P
 |
 R
 |
 B
 |
 1993

Raise a mound of stone W of the corner.

Set a steel fence post alongside the aluminum post.

41.567 The east closing corner of sections 10 and 15, on the S P I R B, monumented with a limestone, 18x10x4 ins., firmly set and plainly marked with a cross on E face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SAN PETE
INDIAN RESERVATION BOUNDARY,
T. 20 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

	T20S R1W		
		S	
		P	
S15		I	S10 C
		R	S15 C
		B	
		1993	

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

- 42.413** Point for the west closing corner of sections 10 and 15, on the S P I R B, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T20S R1W		
		S	
		P	
C S10		I	S10
C S15		R	
		B	
		1993	

Raise a mound of stone W of the corner.

Set a steel fence post alongside the aluminum post.

- 80.214** The corner of lots 114 and 115, on the S P I R B, monumented with a limestone, 10x10x3 ins., firmly set and plainly marked 7 on E face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

	T20S R1W		
		S	
		P	
S10		I	Cor 7
		R	
		B	
		1993	

Deposit the marked stone alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SAN PETE
 INDIAN RESERVATION BOUNDARY,
 T. 20 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a steel fence post alongside the aluminum post.

N. 0° 31.8' W., on the west boundary of the San Pete Indian Reservation, beginning new measurement.

Over rolling bench land, through sagebrush and shadscale.

1.703 Point for the east witness point at the intersection of the E-W center line of section 10.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S R1W
 S10
 |
 S
 |
 P
 |
 I W P
 |
 R
 |
 B
 1993

Raise a mound of stone E of the corner.

Set a steel fence post alongside the aluminum post.

2.337 Point for the west witness point at the intersection of the E-W center line of section 10.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S R1W
 S10
 |
 S
 |
 P
 |
 I W P
 |
 R
 |
 B
 1993

Raise a mound of stone W of the corner.

Set a steel fence post alongside the aluminum post.

40.133 The corner of lots 115 and 152, on the S P I R B, monumented with a limestone, 12x10x6 ins., firmly set and plainly marked 8 on E face.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SAN PETE
INDIAN RESERVATION BOUNDARY,
T. 20 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a collar of stone, with aluminum cap marked:

	T20S R1W	
	S	
	P	
S 10		Cor 8
	I	
	R	
	B	
	1993	

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 0° 38.0' W., on the west boundary of the San Pete Indian Reservation, beginning new measurement.

Over rolling bench land, through sagebrush and shadscale.

- 1.920** The east closing corner of sections 3 and 10, on the S P I R B, monumented with a limestone, 12x8x6 ins., firmly set and plainly marked with a cross on the E face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

	T20S R1W	
	S	
	P	
S 10		S 3 C
	I	
	R	S 10 C
	B	
	1993	

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.


- 2.341** The west closing corner of sections 3 and 10, on the S P I R B, monumented with a limestone, 15x8x6 ins., firmly set and plainly marked with a cross on the W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SAN PETE
 INDIAN RESERVATION BOUNDARY,
 T. 20 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS




Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

20.020 The corner of lot 152, on the S P I R B, monumented with a limestone, 12x8x5 ins., firmly set and plainly marked 1/2 on E face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:



Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 0° 31.3' W., on the west boundary of the San Pete Indian Reservation, beginning new measurement.

Over rolling bench land, through sagebrush and shadscale.

20.062 The corner of lots 152 and 153, on the S P I R B, monumented with a limestone 17x12x6 ins., firmly set and plainly marked with a 9 on the east face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SAN PETE
 INDIAN RESERVATION BOUNDARY,
 T. 20 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T20S R1W
 S
 P
 S 3 I COR 9
 R
 B
 1993

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

Raise a mound of stone E of the corner.

N. 0° 35.6' W., on the west boundary of the San Pete Indian Reservation, beginning new measurement.

Over rolling bench land, through sagebrush and shadscale.

2.556 Point for the west witness point at the intersection of the E-W center line of section 3, on the S P I R B.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T20S R1W
 S3
 S
 P
 W P I
 R
 B
 1993

Set a steel fence post alongside the aluminum post.

3.360 Point for the east witness point at the intersection of the E-W center line of section 3, on the S P I R B.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SAN PETE
 INDIAN RESERVATION BOUNDARY,
 T. 20 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T20S R1W
 S3
 |
 S
 P
 I W P
 R
 B
 1993

Set a steel fence post alongside the aluminum post.

20.038 The corner of lot 153, on the S P I R B, monumented with a limestone, 10x8x6 ins., firmly set and plainly marked 1/2 on east face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T20S R1W
 |
 S
 P
 S 3 | I 1/2
 R
 B
 1993

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 0° 38.2' W., on the west boundary of the San Pete Indian Reservation, beginning new measurement.

Over rolling bench land, through sagebrush and shadscale.

22.514 The west closing corner of Tps. 19 and 20 S., R. 1 W., monumented with an aluminum post, set 24 ins. in the ground, with aluminum cap marked as described in the official record of the 1991 resurvey of the south boundary of T. 19 S., R. 1 W.

N. 0° 39.3' W., on the San Pete Indian Reservation Boundary, and the township line of section 3 of T. 20 S., R. 1 W., and section 35, of T. 19 S., R. 1 W.

1.916 The east closing corner of Tsp. 19 and 20 S., R. 1 W., monumented with an iron post, 2 ins. diam., 6 ins. above ground with brass cap marked T 19 S R 1 W C C S 35 1915.

DEPENDENT RESURVEY OF A PORTION OF THE SUDIVISIONAL
LINES, T. 20 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 1 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by C. Mogo in 1856,
the Resurvey Executed by A. D. Ferron in 1871,
the Resurvey Executed by A. Jessen in 1879 and
the Resurvey Executed by A. J. Stewart in 1915, Unrecorded

From the point for the section corner of sections 23, 24, 25, and 26, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T20S	R1W
<u>S23</u>	<u>S24</u>
S26	S25
1993	

Set a steel fence post alongside the aluminum post.

From this corner, the unrecorded 1/4 section corner of sections 25 and 26, bears S. 0° 49.6' E., 40.522 chs. dist., monumented with an iron post, 2 ins. diam., 6 ins. above ground, set in cement, with brass cap marked:

	1/4	
S26		S25
1915		

This corner is accepted as the best available evidence of the original corner position; not remonumented.

Corner is located at the corner of fences, projecting east, west, and south.

From this same corner, sections 19, 24, 25, and 30, T. 20 S., Rs. 1 W. and 1 E., marked by the corner of fences, projecting north, south, and west, bears N. 89° 06.5' E., 81.020 chs. dist., and is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 20 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T20S	
R1W	R1E
S24	S19
S25	S30
1993	

This control line was fully retraced and a careful search was made for the 1/4 section corner, which was not recovered.

N. 0° 39.6' W., bet. sections 23 and 24.

Over rolling hills, through sagebrush and shadscale.

40.520 Point for the 1/4 section corner of sections 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T20S R1W	
1/4	
S23	S24
1993	

Set a steel fence post alongside the aluminum post.

Corner is located in rolling clay hills.

81.040 Point for the section corner of sections 13, 14, 23, and 24, at proportionate distance; there is no remaining evidence of the original corner. This point falls in large open pit salt mine in operation on private property; not monumented.

From this corner, the unrecorded 1/4 section corner of sections 13 and 24, bears N. 89° 55.6' E., 40.396 chs. dist., monumented with an iron post, 2 ins. diam., 6 ins. above ground, set in cement, with brass cap marked.

1/4	S13
	S24
1915	

This corner is accepted as the best available evidence of the original corner position; not remonumented.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 20 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From this same corner, the unrecorded 1/4 section corner of sections 13 and 14, bears N. 0° 07.8' E., 40.510 chs. dist., monumented with an iron post, 2 ins. diam., 6 ins. above ground, set in cement, with brass cap marked.

T20S R1W
1/4
S14 | S13
1915

This corner is accepted as the best available evidence of the original corner position; not remonumented.

Corner is located in E-W fence line.

From the unrecorded S 1/16 section corner of sections 26 and 27, monumented with a cedar post, set in cement. Corner is located at the corner of fences projecting E, W and S.

This corner is accepted as the best available evidence of the original corner position; not remonumented.

From this corner, unrecorded corner of sections 26, 27, 34, and 35, bears S. 0° 30.1' E., 20.084 chs. dist., monumented with an iron post, 2 ins. diam., 6 ins. above ground, set in cement, with brass cap marked:

T20S R1W
S27 | S26
S34 | S35
1915

This corner is accepted as the best available evidence of the original corner position; not remonumented.

Corner is located at the corner of fences projecting N, S and E.

N. 0° 27.6' W., between sections 26 and 27.

20.139

The unrecorded 1/4 section corner of sections 26 and 27, monumented with an iron post, 2 ins. diam., 6 ins. above ground, set in cement, with brass cap marked:

1/4
S27 | S26
1915

This corner is accepted as the best available evidence of the original corner position; not remonumented.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 20 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0° 39.2' W., beginning new measurement.

40.480 Point for the section corner of sections 22, 23, 26, and 27, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T20S	R1W
<u>S22</u>	<u>S23</u>
S27	S26
1993	

Set a steel fence post alongside the aluminum post.

Corner is located in small draw, drains south.

From the corner of sections 23, 24, 25, and 26.

S. 87° 45.9' W., bet. sections 23 and 26.

Over rolling land.

40.570 Point for the 1/4 section corner of sections 23 and 26, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T20S	R1W
1/4	<u>S23</u>
	S26
1993	

Set a steel fence post alongside the aluminum post.

Corner is located 30 lks. dist., E of N and S fence line.

Over rolling bench land, through sagebrush and shadscale.

81.140 The corner of sections 22, 23, 26, and 27.

From the corner of sections 22, 23, 26, and 27.

N. 0° 33.7' W., bet. sections 22 and 23.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 20 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Over rolling bench land, through sagebrush and shadscale.

- 40.475** The unrecorded 1/4 section corner of sections 22 and 23, monumented with an iron post, 2 ins. diam., 6 ins. above ground, set in cement, with brass cap marked.

$$\begin{array}{c} 1/4 \\ \text{S22} \mid \text{S23} \\ 1915 \end{array}$$

This corner is accepted as the best available evidence of the original corner position; not remonumented.

N. 0° 36.3' W., beginning new measurement.

- 39.811** The unrecorded corner of sections 14, 15, 22 and 23, monumented with an iron post, 2 ins. diam., 6 ins. above ground, set in cement, with brass cap marked.

$$\begin{array}{c} \text{T20S R1W} \\ \text{S15} \mid \text{S14} \\ \text{S22} \mid \text{S23} \\ 1915 \end{array}$$

This corner is accepted as the best available evidence of the original corner position; not remonumented.

From the unrecorded 1/4 section corner of sections 14 and 23, monumented with an iron post, 2 ins. diam., 6 ins. above ground, set in cement, with brass cap marked.

$$\begin{array}{c} \text{T20S R1W} \\ 1/4 \frac{\text{S14}}{\text{S23}} \\ 1915 \end{array}$$

This corner is accepted as the best available evidence of the original corner position; not remonumented.

From this corner, the point for the section corner of sections 13, 14, 23, and 24, bears N. 87° 48.1' E., 40.390 chs. dist.

S. 86° 39.7' W., between sections 14 and 23.

- 20.326** Point for the W 1/16 section corner of sections 14 and 23.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 20 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T20S R1W
W 1/16 $\frac{S14}{S23}$
1993

Raise a mound of stone N of the corner.

Set a steel fence post alongside the aluminum post.

40.652 The corner of sections 14, 15, 22, and 23.

N. 0° 08.1' W., bet. sections 14 and 15.

Over rolling bench land, through sagebrush and shadscale.

20.145 Point for the S 1/16 section corner of sections 14 and 15.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T20S R1W
S 1/16
S15 | S14
1993

Set a steel fence post alongside the aluminum post.

40.290 The unrecorded 1/4 section corner of sections 14 and 15, monumented with an iron post, 2 ins. diam., 10 ins. above ground, set in cement, with brass cap marked:

T20S R1W
1/4
S15 | S14
1915

This corner is accepted as the best available evidence of the original corner position; not remonumented.

Corner is located in draw, drains E-NE.

N. 0° 03.8' W., beginning new measurement.

40.278 The unrecorded corner of sections 10, 11, 14 and 15, monumented with an iron post, 2 ins. diam., 6 ins. above ground, set in cement, with brass cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 20 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T20S R1W
 $\frac{S10}{S15} \mid \frac{S11}{S14}$
 1915

This corner is accepted as the best available evidence of the original corner position;
not remonumented.

From the unrecorded 1/4 section corner of sections 11 and 14, monumented with an
iron post, 2 ins. diam., 6 ins. above ground, set in cement, with brass cap marked

1/4 $\frac{S11}{S14}$
 1915

This corner is accepted as the best available evidence of the original corner position;
not remonumented.

S. 87° 16.6' W., bet. sections 11 and 14.

Over rolling bench land, through sagebrush and shadscale.

20.268 Point for the W 1/16 section corner of sections 11 and 14.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of
stone, with aluminum cap marked:

T20S R1W
 W 1/16 $\frac{S11}{S14}$
 1993

Set a steel fence post alongside the aluminum post.

40.536 The corner of sections 10, 11, 14, and 15.

N. 0° 11.3' W., bet. sections 10 and 11.

Over rolling bench land, through sagebrush and shadscale.

40.318 The unrecorded 1/4 section corner of sections 10 and 11, monumented with an iron
post, 2 ins. diam., 6 ins. above ground, set in cement, with brass cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 20 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T20S R1W
1/4
S10 | S11
1915

This corner is accepted as the best available evidence of the original corner position;
not remonumented.

N. 0° 07.2' W., beginning new measurement.

- 40.279** The unrecorded corner of sections 2, 3, 10, and 11, monumented with an iron post, 2 ins. diam., 6 ins. above ground, set in cement, with brass cap marked

T20S R1W
S3 | S2
S10 | S11
1915

This corner is accepted as the best available evidence of the original corner position;
not remonumented.

N. 0° 43.5' W., bet. sections 2 and 3.

Over rolling bench land, through sagebrush and shadscale.

- 40.415** The unrecorded 1/4 section corner of sections 2 and 3, monumented with an iron post, 2 ins. diam., 6 ins. above ground, set in cement, with brass cap marked:

T20S R1W
1/4
S3 | S2
1915

This corner is accepted as the best available evidence of the original corner position;
not remonumented.

N. 0° 41.2' W., beginning new measurement.

- 42.212** The corner of sections 2 and 3, on the north boundary of the township, heretofore described.
-

From the unrecorded corner of sections 3, 4, 33, and 34, on the south boundary of the township, monumented with an iron post, 2 ins. diam., 4 ins. above ground, set in cement, with brass cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 20 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T20S R1W
S33 | S34
S4 | S3
T21S
1915

This corner position resurvey was accepted by G.E. Reynolds, 1991 to 1993.

Corner is located in E-W fence line.

From this corner, U.S. Geological Survey triangulation station "BM X50", bears S. 4° 34' 19" W., 312.587 chs. dist.

From this same corner, U.S. Coast and Geodetic Survey triangulation station "Redmond", bears S. 89° 03' 52" E., 411.471 chs. dist.

N. 0° 06.0' W., bet. sections 33 and 34.

Over rolling bench land, through sagebrush and shadscale .

39.490 The unrecorded 1/4 section corner of sections 33 and 34, monumented with an iron post, 2 ins. diam., 6 ins. above ground, set in cement, with brass cap marked:

1/4
S33 | S34
1915

This corner is accepted as the best available evidence of the original corner position; not remonumented.

N. 0° 03.6' W., beginning new measurement.

40.007 The unrecorded corner of sections 27, 28, 33, and 34, monumented with an iron post, 2 ins. diam., 6 ins. above ground, set in cement, with brass cap marked:

T20S R1W
S28 | S27
S33 | S34
1915

This corner is accepted as the best available evidence of the original corner position; not remonumented.

N. 89° 48.4' E., bet. sections 27 and 34.

Over rolling bench land, through sagebrush and shadscale.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 20 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

37.869 The unrecorded 1/4 section corner of sections 27 and 34, monumented with an iron post, 2 ins. diam., 6 ins. above ground, set in cement, with brass cap marked:

1/4 $\frac{S27}{S34}$
1915

This corner is accepted as the best available evidence of the original corner position; not remonumented.

N. 89° 44.6' E., beginning new measurement.

19.939 The unrecorded E 1/16 section corner of sections 27 and 34, monumented with a nail in center of cement block, 4 ins. above ground.

After an investigative survey, this corner was accepted as the E 1/16 corner of sections 27 and 34; not remonumented.

Set a steel fence post alongside the cement block.

N. 83° 01.7' E., beginning new measurement.

11.978 The west closing corner of sections 27 and 34, on the San Pete Indian Reservation Boundary, heretofore described.

From the corner of sections 27, 28, 33, and 34.

N. 0° 12.3' E., bet. sections 27 and 28.

Over rolling bench land, through sagebrush and shadscale.

40.008 The 1/4 section corner of sections 27 and 28, monumented with a limestone, 15x12x10 ins., firmly set, dimly marked and witnessed by a mound of stone to the west.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S R1W
1/4
S28 | S27
1993

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 20 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 0° 12.0' E., beginning new measurement.

39.990 The corner of sections 21, 22, 27, and 28, monumented with a limestone, 12x10x10 ins., firmly set and plainly marked with 3 notches on the E and 2 on the S edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a collar of stone, with aluminum cap marked:

T20S	R1W
S21	S22
S28	S27
1993	

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 88° 23.6' E., bet. sections 22 and 27.

Over rolling bench land, through sagebrush and shadscale.

36.381 Point for the 1/4 section corner of sections 22 and 27, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T20S	R1W
1/4	<u>S22</u>
	S27
1993	

Set a steel fence post alongside the aluminum post.

68.685 The west closing corner of sections 22 and 27, on the San Pete Indian Reservation Boundary, heretofore described.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 20 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the corner of sections 22, 23, 26, and 27.

S. 87° 36.9' W., bet. sections 22 and 27.

7.900 The east closing corner of sections 22 and 27, on the San Pete Indian Reservation Boundary, heretofore described.

From the corner of sections 21, 22, 27, and 28.

N. 0° 37.3' W., bet. sections 21 and 22.

Over rolling bench land, through sagebrush and shadscale.

40.396 The 1/4 section corner of sections 21 and 22, monumented with a limestone, 16x10x6 ins., firmly set and dimly marked 1/4 on W face, witnessed by a mound of stone west.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S R1W
1/4
S21 | S22
1993

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 0° 19.6' W., beginning new measurement.

40.648 The corner of sections 15, 16, 21, and 22, monumented with a limestone, 20x12x8 ins., firmly set and plainly marked with 3 notches on the S and E edges, witnessed by a mound of stone and a steel railroad rail, 8 ft. long, west of corner.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S R1W
S16 | S15
S21 | S22
1993

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 20 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposit the marked stone alongside the aluminum post.

N. 88° 57.8' E., bet. sections 15 and 22.

Over rolling bench land, through sagebrush and shadscale.

35.646 Point for the 1/4 section corner of sections 15 and 22, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, with aluminum cap marked:

	T20S R1W
1/4	<u>S15</u>
	S22
	1993

Set a steel fence post alongside the aluminum post.

Corner is located in draw, drains northeast.

68.555 The west closing corner of sections 15 and 22, on the San Pete Indian Reservation Boundary, heretofore described.

From the corner of sections 14, 15, 22, and 23.

S. 89° 31.0' W., bet. sections 15 and 22.

7.852 The east closing corner of sections 15 and 22, on the San Pete Indian Reservation Boundary, heretofore described.

From the corner of sections 15, 16, 21, and 22.

N. 0° 20.4' W., bet. sections 15 and 16.

Over rolling bench land, through sagebrush and shadscale.

40.533 The 1/4 section corner of sections 15 and 16, monumented with a limestone, 22x12x8 ins., firmly set and plainly marked 4 on W face, witnessed by a mound of stone and a steel railroad rail, 10 ft. long, W of the corner.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 20 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T20S R1W
1/4
S16 | S15
1993

Deposit the marked stone alongside the aluminum post.

N. 0° 22.6' W., beginning new measurement.

- 40.497** The corner of sections 9, 10, 15, and 16, monumented with a limestone, 18x10x6 ins., firmly set and plainly marked with 3 notches on the E and 4 on the S edges, witnessed by a steel railroad rail, 10 ft. long, alongside.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S R1W
S9 | S10
S16 | S15
1993

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone W of the corner.

N. 89°37.4' E., bet. sections 10 and 15.

Over rolling bench land, through sagebrush and shadscale.

- 34.934** Point for the 1/4 section corner of sections 10 and 15, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T20S R1W
1/4 S10
S15
1993

Set a steel fence post alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 20 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS**68.247**

The west closing corner of sections 10 and 15, on the San Pete Indian Reservation Boundary, heretofore described.

From the corner of sections 10, 11, 14, and 15.

S. 88° 46.7' W., bet. sections 10 and 15.

8.504

The east closing corner of sections 10 and 15, on the San Pete Indian Reservation Boundary, heretofore described.

From the corner of sections 9, 10, 15, and 16.

N. 0° 25.6' W., bet. sections 9 and 10.

Over rolling bench land, through sagebrush and shadscale.

40.435

The 1/4 section corner of sections 9 and 10, monumented with a sandstone, 24x14x10 ins., firmly set and plainly marked 4 on W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S R1W
1/4
S9 | S10
1993

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone W of the corner.

Set a steel fence post alongside the aluminum post.

N. 0° 28.9' W., beginning new measurement.

40.513

The corner of sections 3, 4, 9, and 10, monumented with a limestone, 20x12x8 ins., firmly set and plainly marked with 5 notches on the S and 3 on the E edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 20 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T20S	R1W
<u>S4</u>	<u>S3</u>
S9	S10
1993	

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

S. 89° 48.7' E., bet. sections 3 and 10.

Over rolling bench land, through sagebrush and shadscale.

34.286 Point for the 1/4 section corner of sections 3 and 10, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T20S	R1W
1/4	<u>S3</u>
	S10
1993	

Set a steel fence post alongside the aluminum post.

68.094 The west closing corner of sections 3 and 10, on the San Pete Indian Reservation Boundary, heretofore described.

From the corner of sections 2, 3, 10, and 11.

S. 89° 28.7' W., bet. sections 3 and 10.

9.068 The east closing corner of sections 3 and 10, on the San Pete Indian Reservation Boundary, heretofore described.

From the corner of sections 3, 4, 9, and 10.

N. 0° 20.7' W., bet. sections 3 and 4.

Over rolling bench land, through sagebrush and shadscale.

40.310 The 1/4 section corner of sections 3 and 4, monumented with sandstone, 16x10x5 ins., firmly set and dimly marked 1/4 on W face.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 20 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T20S R1W
1/4
S4 | S3
1993

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 0° 04.7' E., beginning new measurement.

- 39.968** The corner of sections 3, 4, 33, and 34, on the north boundary of the township, monumented with an aluminum post, 2 1/2 ins. diam., 4 ins. above ground, with aluminum cap marked as described in the official record of the 1991 dependent resurvey of a portion of the south boundary of T 19 S., R. 1 W.

Subdivision of Section 3,
T. 20 S., R. 1 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 2 and 3.

N. 83° 28.9' W., on the E-W center line of section 3.

- 9.031** The east witness point of section 3, on the San Pete Indian Reservation Boundary, heretofore described.

Subdivision of Section 10,
T. 20 S., R. 1 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 10 and 11.

S. 89° 00.7' W., on the E-W center line of section 10.

- 8.777** The east witness point of section 10, on the San Pete Indian Reservation Boundary, heretofore described.

SUBDIVISION OF SECTION 14,
T. 20 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Subdivision of Section 14,
T. 20 S., R. 1 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 14 and 23.

N. 0° 11.5' W., on the N-S center line of section 14.

19.990 Point for the center S 1/16 section corner of section 14, not monumented.

39.980 The unrecorded center 1/4 section corner of section 14, monumented with an iron post, 2 ins. diam., 6 ins. above ground, set in cement, with brass cap marked:

Center 14
1915

After an investigative survey, this corner was accepted as the center 1/4 section corner of section 14; not remonumented.

Corner is located in E-W fence line.

From this corner, the 1/4 section corner of sections 13 and 14, bears
N. 87° 04.0' E., 40.634 chs. dist.

From this same corner, the 1/4 section corner of sections 11 and 14, bears
N. 0° 07.7' W., 40.146 chs. dist.

S. 87° 05.7' W., on the E-W center line of section 14.

20.296 Point for the center W 1/16 section corner of section 14.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T20S R1W
C $\frac{W \ 1/16}{S14}$ C
1993

Set a steel fence post alongside the aluminum post.

Corner is located 15.5 lks. dist., S of E and W fence line.

40.592 The 1/4 section corner of sections 14 and 15.

SUBDIVISION OF SECTION 14,
T. 20 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

- From the W 1/16 section corner of sections 14 and 23.
- N. 0° 09.8' W., on the N-S center line of the SW 1/4 of section 14.
- 20.067** Point for the SW 1/16 section corner of section 14, at intersection with the E-W center line of the SW 1/4.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:
- T20S R1W
SW 1/16 S14
1993
- Set a steel fence post alongside the aluminum post.
- 40.135** The center W 1/16 section corner of section 14.
-
- From the point for the center S 1/16 section corner of section 14.
- S. 86° 52.7' W., on the E-W center line of the SW 1/4 of section 14.
- 20.311** The SW 1/16 section corner of section 14.
- 40.622** The S 1/16 section corner of sections 14 and 15.
-
- From the center W 1/16 section corner of section 14.
- N. 0° 05.8' W., on the N-S center line of the NW 1/4 of section 14.
- 40.212** The W 1/16 section corner of sections 11 and 14.
-
- Subdivision of Section 15,
T. 20 S., R. 1 W., Salt Lake Meridian, Utah
-
- From the 1/4 section corner of sections 14 and 15.
- S. 89° 04.9' W., on the E-W center line of section 15.
- 8.141** The east witness point of section 15, on the San Pete Indian Reservation Boundary, heretofore described.
-

SUBDIVISION OF SECTION 22,
T. 20 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Subdivision of Section 22,
T. 20 S., R. 1 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 22 and 23.

S. 85° 59.6' W., on the E-W center line of section 22.

- 7.834** The east witness point of section 22, on the San Pete Indian Reservation Boundary, heretofore described.
-

Subdivision of Section 23,
T. 20 S., R. 1 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 23 and 26.

N. 0° 32.3' W., on the N-S center line of section 23.

- 40.499** Point for the center 1/4 section corner of section 23, at intersection with the E-W center line of section 23.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T20S R1W
C 1/4 S23
1993

Set a steel fence post alongside the aluminum post.

Corner is located 30 lks. dist., E of N and S fence line.

- 81.069** The 1/4 section corner of sections 14 and 23.
-

From the 1/4 section corner of sections 23 and 24.

S. 87° 43.9' W., on the E-W center line of section 23.

- 40.481** The center 1/4 section corner of section 23.

- 60.772** Point for the center W 1/16 section corner of section 23.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

SUBDIVISION OF SECTION 23,
T. 20 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T20S R1W
C $\frac{W\ 1/16}{S23}$ C
1993

Set a steel fence post alongside the aluminum post.

81.063 The 1/4 section corner of sections 22 and 23.

From the center W 1/16 section corner of section 23.

N. 0° 34.2' W., on the N-S center line of the NW 1/4 of section 23.

40.190 The W 1/16 section corner of sections 14 and 23.

Subdivision of Section 27,
T. 20 S., R. 1 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 27 and 34.

N. 0° 51.5' W., on the N-S center line of section 27.

20.423 Point for the center S 1/16 section corner of section 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T20S R1W
C
S 1/16 | S27
C
1993

Set a steel fence post alongside the aluminum post.

40.846 Point for the center 1/4 section corner of section 27, at intersection with the E-W center line of section 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T20S R1W
C 1/4 S27
1993

SUBDIVISION OF SECTION 27,
T. 20 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a steel fence post alongside the aluminum post.

80.901 The 1/4 section corner of sections 22 and 27.

From the 1/4 section corner of sections 27 and 28.

N. 88° 31.1' E., on the E-W center line of section 27.

37.123 The center 1/4 section corner of section 27.

55.607 Point for the center E 1/16 section corner of section 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

$$\begin{array}{c} \text{T20S R1W} \\ \text{C} \quad \frac{\text{E } 1/16}{\text{S27}} \quad \text{C} \\ \text{1993} \end{array}$$

Set a steel fence post alongside the aluminum post.

69.217 The west witness point of section 27, on the San Pete Indian Reservation Boundary, heretofore described.

From the 1/4 section corner of sections 26 and 27.

S. 87° 48.8' W., on the E-W center line of section 27.

7.973 The east witness point of section 27, on the San Pete Indian Reservation Boundary, heretofore described.

From the S 1/16 section corner of sections 26 and 27.

S. 87° 09.6' W., on the E-W center line of the SE 1/4 of section 27.

7.955 The east witness point of the SE 1/4 of section 27, on the San Pete Indian Reservation Boundary, heretofore described.

From the E 1/16 section corner of sections 27 and 34.

N. 0° 40.2' W., on the N-S center line of the SE 1/4 of section 27.

SUBDIVISION OF SECTION 27,
T. 20 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

- 20.114** The unrecorded SE 1/16 section corner of section 27, monumented with a rock, 4 ins. above ground, set in cement (1915 survey).
- After an investigative survey, this corner was accepted as the SE 1/16 section corner of section 27; not remonumented.
- Set a steel fence post alongside the corner.
-
- N. 4° 58.2' W., beginning new measurement.
- 21.196** The center E 1/16 section corner of section 27.
-
- From the center S 1/16 section corner of section 27.
- S. 89° 22.4' E., on the E-W center line of the SE 1/4 of section 27.
- 20.010** The SE 1/16 section corner of section 27.
-
- N. 83° 17.9' E., beginning new measurement.
- 12.034** The west witness point of the SE 1/4 of section 27, on the San Pete Indian Reservation Boundary, heretofore described.
-
- Subdivision of Section 34,
T. 20 S., R. 1 W., Salt Lake Meridian, Utah
-
- From the 1/4 section corner of sections 3 and 34, on the south boundary of the township, monumented with an iron post, 2 ins. diam., 6 ins. above ground, set in cement, with brass cap marked:
- | | | |
|-----|------|---|
| | S | C |
| 1/4 | S34 | |
| | S3 | |
| | 1915 | |
- This corner position resurvey was accepted by G.E. Reynolds, 1991 to 1993.
- N. 1° 35.9' W., on the N-S center line of section 34.
- 39.633** The unrecorded center 1/4 section corner of section 34, monumented with an iron post, 2 ins. diam., 6 ins. above ground, set in cement, with brass cap marked:

SUBDIVISION OF SECTION 34,
T. 20 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

C 1/4 S34
1915

After an investigative survey, this corner was accepted as the center 1/4 section corner of section 34; not remonumented.

N. 1° 34.8' W., beginning new measurement.

19.954 The unrecorded center N 1/16 section corner of section 34, monumented with a cement block, 4 ins. above ground.

After an investigative survey, this corner was accepted as the center N 1/16 section corner of section 34; not remonumented.

Set a steel fence post alongside the cement block.

N. 1° 35.1' W., beginning new measurement.

19.954 The 1/4 section corner of sections 27 and 34.

From the unrecorded 1/4 section corner of sections 34 and 35, monumented with an iron post, 2 ins. diam., 6 ins. above ground, set in cement, with brass cap marked:

1/4
S34 | S35
1915

This corner is accepted as the best available evidence of the original corner position; not remonumented.

S. 89° 37.3' W., on the E-W center line of section 34.

19.940 Point for the center E 1/16 section corner of section 34, not monumented.

39.880 The center 1/4 section corner of section 34.

S. 89° 38.7' W., beginning new measurement.

38.932 The 1/4 section corner of sections 33 and 34.

From the point for the center E 1/16 section corner of section 34.

N. 1° 34.9' W., on the N-S center line of the NE 1/4 of section 34.

SUBDIVISION OF SECTION 34,
T. 20 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

19.926 Point for the NE 1/16 section corner of section 34, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T20S R1W
NE 1/16 S34
1993

Set a steel fence post alongside the aluminum post.

Corner is located 1.00 chs. dist., E of canal, flows N.

39.865 The E 1/16 section corner of sections 27 and 34.

From the unrecorded N 1/16 section corner of sections 34 and 35, monumented with a cedar post, set in cement. This corner is located at the corner of fences, projecting N, S, and E. After an investigative survey, this corner is accepted as the section corner of sections 34 and 35; not remonumented.

From this corner, the 1/4 section corner of sections 34 and 35, bears S. 1° 38.5' E., 19.898 chs. dist.

From this same corner, the section corner of sections 26, 27, 34, and 35, bears N. 1° 45.8' W., 19.928 chs. dist.

S. 89° 42.2' W., on the E-W center line of the NE 1/4 of section 34.

19.919 The NE 1/16 section corner of section 34.

39.858 The center N 1/16 section corner of section 34.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Shannon Sere	Surveying Technician
Philip Tobler	Survey Aid
Shawn Peterson	Survey Aid

CERTIFICATE OF SURVEY

I, *Ferrel D. Reynolds, Cadastral Surveyor*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *9th day of June, 1993*, I have *dependently resurveyed a portion of the north boundary, a portion of the San Pete Indian Reservation boundary, a portion of the subdivisional lines and the subdivision of sections 3, 10, 14, 15, 22, 23, 27, and 34,, in Township 20 South, Range 1 West,*

of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

September 21, 2000

Date



(Cadastral Surveyor)

Date

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah


The foregoing field notes of the *dependent resurvey of a portion of the north boundary, a portion of the San Pete Indian Reservation Boundary, a portion of the subdivisional lines, and the subdivision of sections 3, 10, 14, 15, 22, 23, 27, and 34, Township 20 South, Range 1 West, Salt Lake Meridian, Utah,*

executed by *Ferrel D. Reynolds, Cadastral Surveyor*

having been critically examined and found correct, are hereby approved.

September 27, 2000

Date



(Chief Cadastral Surveyor for Utah)