

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

# FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

PORTIONS OF THE

NORTH, WEST (GUIDE MERIDIAN)

AND SOUTH BOUNDARIES,

AND A PORTION OF THE SUBDIVISIONAL LINES,

AND THE

SUBDIVISION OF SECTIONS 3, 6, 7, 10, 15, 18, 21, 28, AND 32

IN

TOWNSHIP 11 NORTH, RANGE 18 WEST

OF THE SALT LAKE MERIDIAN  
IN THE STATE OF UTAH

EXECUTED BY

*Gail E. Reynolds*  
*Cadastral Surveyor*

Under special instructions dated *May 12, 1993*, approved *May 12, 1993*, which provided for the surveys included under Group Number *805*, and assignment instructions dated *June 7, 1993*.

Survey commenced June 29, 1993

Survey completed September 22, 1993

INDEX DIAGRAM

Township 11 North, Range 18 West

7	15	14	13	12		
6	6 39	5 29	4 21	3 17	2	1
	39 38	38	29 28	20	17	
6			28			
5	7 37	8	9 19	10 16	11	12
	37 36	36 35	27 26			
5						
4	18 34	17	16	15	14	13
	34	34	26			
4			26			
3	19 33	20	21	22	23	24
	33 32	32	25	25 24		
3						
2	30 31	29	28 18	27	26	25
		31 30	23 22			
	31	32	33	34	35	36
11	10	10	9	9	8	

The Subdivision of Section 3 ..... Page 40  
 The Subdivision of Section 6 ..... Page 41  
 The Subdivision of Section 7 ..... Page 43  
 The Subdivision of Section 10..... Page 45  
 The Subdivision of Section 15..... Page 48  
 The Subdivision of Section 18..... Page 49  
 The Subdivision of Section 21..... Page 50  
 The Subdivision of Section 28..... Page 52  
 The Subdivision of Section 32..... Page 54

## TOWNSHIP 11 NORTH, RANGE 18 WEST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

The following field notes describe the dependent resurvey of portions of the north, west (Guide Meridian), and south boundaries and a portion of the subdivisional lines, and the survey of the subdivision of sections 3, 6, 7, 10, 15, 18, 21, 28, and 32, in Township 11 North, Range 18 West, Salt Lake Meridian, Utah.

**HISTORY OF EARLIER SURVEYS**

Surveyed by		<u>Retr. or Resurveyed by</u>	
<b>NORTH BOUNDARY</b>			
All	F. Dickert	1882	
<b>SOUTH BOUNDARY</b>			
All	F. Dickert	1882	
<b>EAST BOUNDARY</b>			
All	F. Dickert	1882	
<b>WEST BOUNDARY (Guide Meridian)</b>			
All	F. Dickert	1882	
<b>SUBDIVISION</b>			
All	H. Fitzhugh	1883	
Portion			C.P. Sylvester 1979
Portion			R.A. Zaninovich 1990

The survey was executed in accordance with the specifications set forth in the Manual of Surveying instructions, 1973, and the Special Instructions for Group No. 805, dated May 12, 1993.

The directions of the lines were determined by hour angle observations of the sun and Polaris, carried forward by sustained angulation. Distances were determined by electronic measurement.

Preliminary to the resurvey the lines of the original survey and resurveys were retraced and a diligent search was made for any evidence of the original and resurvey field note records. Identified corners, when appropriate were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original or resurvey record. The retracement data were thoroughly verified and only the true line notes are given herein.

## TOWNSHIP 11 NORTH, RANGE 18 WEST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

The geographic position of the corner of sections 27, 28, 33, and 34, as determined by a tie made to N.G.S. Triangulation Station " VT BM L 59" is as follows:

Latitude 41°38'21.39" N. Longitude 113°54'23.95" W.  
N.A.D. 1927

The mean magnetic declination as projected from the U.S. Geological Survey Magnetic Declination Map of 1990, is 15° E.

---

Dependent Resurvey of the West Boundary (Guide Meridian)  
T. 11 N., R. 18 W., Salt Lake Meridian, Utah.

---

Reestablishment of the Survey Executed by F. Dickert in 1882

---

From the corner of sections 25, 30, 31, and 36, at the corner of fences, projecting E, S, and W. This fence corner is accepted as the best available evidence of the position of the original corner.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N	
R19W R18W	
S25	S30
S36	S31
1993	

Corner is located 40 lks. N of a wash, drains E in sagebrush.

N. 0°11.6' W., between sections 25 and 30.

Over rolling bench land, through sagebrush and widely scattered juniper.

**40.282** Point for the 1/4 section corner of sections 25 and 30, at proportionate distance. There is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap marked:

DEPENDENT RESURVEY OF THE WEST BOUNDARY  
 (GUIDE MERIDIAN)  
 T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

T11N  
 R19W R18W  
 1/4  
 S25 | S30  
 1993

Set a steel fence post alongside the aluminum post.

Corner is located on gently rolling land in sagebrush and widely scattered juniper growth.

Continue over rolling bench land and mountain land.

**80.564** The corner of sections 19, 24, 25, and 30, monumented with a trachyte stone, 30x30x24 ins., firmly set and dimly marked, with a mound of stone to the E.

At the corner point

Set an aluminum post, 30 ins. long, on solid rock and in a mound of stone, 5 ft. base, to top of aluminum cap marked:

T11N  
 R19W R18W  
 S24 | S19  
 S25 | S30  
 1993

Deposit the marked stone alongside the aluminum post.

The corner is located at base of a steep, N slope in sagebrush and juniper growth.

---

N. 0°21.8' W., between sections 19 and 24.

Over mountainous land, through juniper growth.

**39.348** The 1/4 section corner of sections 19 and 24, monumented with a trachyte stone, 24x24x18 ins., firmly set and dimly marked with a mound of stone to W, from which original bearing trees;

A juniper, 18 ins. diam., bears East, 30 lks. dist., with no visible marks.

A juniper, 36 ins. diam., bears West, 36 lks. dist., plainly marked 1/4 S BT.

At the corner point

DEPENDENT RESURVEY OF THE WEST BOUNDARY  
 (GUIDE MERIDIAN)  
 T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to solid rock and in a mound of stone, 5 ft. base, to top of aluminum cap marked:

T11N  
 R19W R18W  
 1/4  
 S24 | S19  
 1993

Deposit a magnet alongside the aluminum post.

Deposit the marked stone alongside the aluminum post.

Corner is located on nearly level land in juniper.

---

N. 0°44.1' E., beginning new measurement.

Over mountainous land, through juniper growth.

**39.922** Point for the corner of sections 13, 18, 19, and 24, at proportionate distance. No remaining evidence of the original corner was found. Point falls in cultivated land and is not monumented.

---

N. 0°44.1' E., between sections 13 and 18.

Over rolling land, through cultivated land, sagebrush, and juniper growth.

**39.922** Point for the 1/4 section corner of sections 13 and 18, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 30 ins. in the ground, with aluminum cap marked:

T11N  
 R19W R18W  
 1/4  
 S13 | S18  
 1993

Set a steel fence post alongside the aluminum post.

Corner is located on nearly level cultivated land.

**59.883** Point for the N 1/16 section corner of sections 13 and 18.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF THE WEST BOUNDARY  
 (GUIDE MERIDIAN)  
 T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T11N  
 R19W R18W  
 N 1/16  
 S13 | S18  
 1993

Set a steel fence post alongside the aluminum post.

Corner is located on gentle, S slope in sagebrush, 1.15 chains N of an improved gravel road bears SE and NW.

**79.844** The corner of sections 7, 12, 13, and 18, monumented with a mound of stone. This point is being utilized by local land owners and local surveyors as the section corner position, and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a mound of stone, 4 1/2 ft. base, to top of aluminum cap marked:

T11N  
 R19W R18W  
S12 | S7  
 S13 | S18  
 1993

The corner is located on a SE slope in scattered juniper growth.

---

N. 0°04.4' E., between sections 7 and 12.

Over mountainous land, through juniper growth.

**40.806** The 1/4 section corner of sections 7 and 12, monumented with a 1/2 inch diam. rebar with a 2 inch diam., unmarked, aluminum cap. This monument is accepted as a careful and faithful reestablishment of the 1/4 section corner position.

No remaining evidence of the original 1/4 section corner was found.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base to top of aluminum cap marked:

DEPENDENT RESURVEY OF THE WEST BOUNDARY  
 (GUIDE MERIDIAN)  
 T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

T11N  
 R19W R18W  
 1/4  
 S12 | S7  
 1993

Set a steel fence post alongside the aluminum post.

Deposit the rebar and aluminum cap alongside the aluminum post.

The corner is located on a rocky, SW slope.

---

N. 0°04.4' E., beginning new measurement.

**40.806** The corner of sections 1, 6, 7, and 12, monumented with a trachyte stone, 20x10x8 ins., firmly set and plainly marked with 1 notch on the N and 5 notches on the S edges, with mound of stone, 3 ft. base, by 1 1/2 ft. high to the E.

From which the original bearing tree and bearing object:

A granite boulder, 10x8x5 ft., bears North, 22 lks. dist., dimly marked.

A juniper, 12 ins. diam., bears N. 5° W., 42 lks. dist., plainly marked T11N R19W S1 BT.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N  
 R19W R18W  
 S1 | S6  
 S12 | S7  
 1993

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

The corner is located on a W slope in juniper growth.

---

N. 0°03.9' E., between sections 1 and 6.

Over rolling mountain land, through sagebrush and juniper growth.

**20.126** Point for the S 1/16 section corner of sections 1 and 6.

DEPENDENT RESURVEY OF THE WEST BOUNDARY  
 (GUIDE MERIDIAN)  
 T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N  
 R19W R18W  
 S 1/16  
 S1 | S6  
 1993

Set a steel fence post alongside the aluminum post.

The corner is located on a gentle, NE slope in sagebrush and scattered juniper growth.

40.252

Point for the 1/4 section corner of sections 1 and 6, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N  
 R19W R18W  
 1/4  
 S1 | S6  
 1993

Raise a mound of stone W of the corner.

Set a steel fence post alongside the aluminum post.

The corner is located on a gentle, NE slope in sagebrush and juniper growth.

80.504

The corner of Townships 11 and 12 North, Ranges 18 and 19 West, monumented with a quartzite stone, 10x8x6 ins., firmly set and plainly marked with 6 notches on the N, E, S, and W edges.

From which the original bearing trees:

A juniper, 8 ins. diam., bears S. 60° E., 18 lks. dist., marked with a blaze and visible scribe marks.

A juniper, 8 ins. diam., bears S. 45° W., 50 lks. dist., marked with a blaze and visible scribe marks.

A juniper, 6 ins. diam., bears N. 88° W., 18 lks. dist., marked with a blaze and visible scribe marks.

At the corner point

DEPENDENT RESURVEY OF THE WEST BOUNDARY  
(GUIDE MERIDIAN)  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T12N  
R19W R18W  
S36 | S31  
S1 | S6  
T11N  
R19W R18W  
1993

Deposit the marked stone alongside the aluminum post.

The corner is located on a SW slope in juniper growth.

---

Dependent Resurvey of a Portion of the South Boundary,  
T. 11 N., R. 18 W., Salt Lake Meridian, Utah.

---

Reestablishment of the Survey Executed by F. Dickert in 1882

---

From the corner of sections 3, 4, 33, and 34, monumented with an aluminum post, 2 1/2 ins. diam., projecting 6 ins. above the ground, with the aluminum cap marked as described in the official record of the resurvey executed by R.A. Zaninovich in 1990.

S. 89°48.0' W., between sections 4 and 33.

Over gently rolling land, through cultivated fields.

**20.137** Point for the E 1/16 section corner of sections 4 and 33.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
E 1/16 S33  
S4  
T10N R18W  
1993

Deposit a magnet alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level ground in sagebrush.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

**40.274** Point for the 1/4 section corner of sections 4 and 33, at proportionate distance. No remaining evidence of the original corner was found. Not monumented due to private land ownership.

**80.548** Point for the corner of sections 4, 5, 32, and 33, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W	
S32	S33
S5	S4
T10N R18W	
1993	

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level cultivated land.

---

S. 89°48.0' W., between sections 5 and 32.

Over gently rolling benchland, through sagebrush and native grasses.

**20.137** Point for the E 1/16 section corner of sections 5 and 32.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 30 ins. in the ground, with aluminum cap marked:

T11N R18W	
E 1/16	S32
	S5
T10N R18W	
1993	

Set a steel fence post alongside the aluminum post.

The corner is located in the center of an old trail road, bears E and W, in sagebrush.

**40.274** Point for the 1/4 section corner of sections 5 and 32, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T11N R18W  
1/4  $\frac{S32}{S5}$   
T10N R18W  
1993

The corner is located on nearly level ground in sagebrush.

**80.548** Point for the corner of sections 5, 6, 31, and 32, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
 $\frac{S31}{S6}$  |  $\frac{S32}{S5}$   
T10N R18W  
1993

Deposit a magnet alongside the aluminum post.

The corner is located 18 lks. dist. N of a steel gate in a 4 strand barbed-wire fence line, bears E and W on nearly level ground in sagebrush.

---

S. 89°48.0' W., between sections 6 and 31.

Over gently rolling land, through sagebrush and native grasses.

**40.274** Point for the 1/4 section corner of sections 6 and 31, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
1/4  $\frac{S31}{S6}$   
T10N R18W  
1993

Set a steel fence post alongside the aluminum post.

The corner is located 14 lks. dist. N of a 4 strand barbed-wire fence line, bears E and W, on nearly level land in sagebrush.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

CHAINS

79.743

The corner of Townships 10 and 11 North, Ranges 18 and 19 West, monumented with a dimly marked granite stone, 18x16x12 ins., firmly set in a 4 strand barbed-wire fence corner, bears N, S, E, and W.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N  
R19W R18W  
S36 | S31  
S1 | S6  
T10N  
R19W R18W  
1993

Deposit the marked stone alongside the aluminum post.

Deposit a magnet alongside the aluminum post.

The corner is located on nearly level ground in sagebrush.

---

Dependent Resurvey of a Portion of the North Boundary,  
T. 11 N., R. 18 W., Salt Lake Meridian, Utah.

---

Reestablishment of the Survey Executed by F. Dickert in 1882

---

From the corner of sections 2, 3, 34, and 35, Townships 11 and 12 North, Range 18 West, monumented with a granite stone, 10x6x5 ins., firmly set, and plainly marked with 2 notches on E and 4 notches on W edges.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T12N R18W  
S34 | S35  
S3 | S2  
T11N R18W  
1993

Deposit the marked stone alongside the aluminum post.

The corner is located on a SW slope in a 4 strand barbed-wire fence corner, bears E, S and W, in sagebrush and juniper growth.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

S. 89°30.7' W., between sections 3 and 34.

Over rolling mountain land, through sagebrush and juniper growth.

**40.184** The 1/4 section corner of sections 3 and 34, at the corner of fences, projecting N, E and W. This point is accepted as the best available evidence of the position of the original corner

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

	T12N R18W
1/4	<u>S34</u>
	S3
	T11N R18W
	1993

The corner is located on a gentle, S slope in juniper growth.

---

S. 89°32.2' W., beginning new measurement.

**40.070** The corner of sections 3, 4, 33, and 34, monumented with a conglomerate stone, 16x12x3 ins., firmly set, and plainly marked with 3 notches on the E and W edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

	T12N R18W
	<u>S33</u>   <u>S34</u>
	S4   S3
	T11N R18W
	1993

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone W of the corner.

The corner is located on a rolling S slope in a 4 strand barbed-wire fence corner, bears N, S and W., and with an old abandoned fence to the E, in sagebrush and juniper growth.

---

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

N. 89°51.7' W., between sections 4 and 33.

Over rolling mountain land, through sagebrush and juniper growth.

**19.950** Point for the E 1/16 section corner of sections 4 and 33.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12N R18W  
E 1/16  $\frac{S33}{S4}$   
T11N R18W  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on gentle rolling ground, 8 lks. N of a 4 strand barbed-wire fence line, bears E and W, in dense juniper growth.

**39.900** The 1/4 section corner of sections 4 and 33, monumented with a conglomerate stone, 10x8x8 ins., firmly set and plainly marked 1/4 on top of stone.

The original juniper bearing tree was found laying over and dead at record bearing and distance.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with aluminum cap marked:

T12N R18W  
1/4  $\frac{S33}{S4}$   
T11N R18W  
1993

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone N of the corner.

The corner is located on a gentle S slope in juniper growth.

S. 89°57.0' W., beginning new measurement.

**40.108** The corner of sections 4, 5, 32, and 33, monumented with a quartzite stone, 18x8x4 ins., firmly set, and plainly marked with 4 notches on E and 2 notches on W edges.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12N	R18W
S32	S33
S5	S4
T11N	R18W
1993	

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone N of the corner.

Set a steel fence post alongside the aluminum post.

The corner is located on a rolling, SE slope in sagebrush and scattered juniper growth.

---

N. 89°39.8' W., between sections 5 and 32.

Over rolling mountain land, through sagebrush and juniper growth.

**39.948** Point for the 1/4 section corner of sections 5 and 32, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12N	R18W
1/4	S32
	S5
T11N	R18W
1993	

Raise a mound of stone N of the corner.

The corner is located on a gentle, E slope in native grasses, sagebrush and scattered juniper growth.

**79.896** Point for the corner of sections 5, 6, 31, and 32, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T12N R18W  
S31 | S32  
 S6 | S5  
 T11N R18W  
 1993

The corner is located on nearly level land in native grasses, sagebrush and scattered juniper growth.

N. 89°39.8' W., between sections 6 and 31.

Over rolling mountain land, through sagebrush and juniper growth.

**39.948** Point for the 1/4 section corner of sections 6 and 31, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12N R18W  
 1/4 S31  
 S6  
 T11N R18W  
 1993

Raise a mound of stone N of the corner.

The corner is located on a NW slope in juniper growth.

**59.922** Point for the W 1/16 section corner of sections 6 and 31.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T12N R18W  
 W 1/16 S31  
 S6  
 T11N R18W  
 1993

Set a steel fence post alongside the aluminum post.

The corner is located on a rolling NW slope in sagebrush and juniper growth.

**79.197** The corner of Townships 11 and 12 North, Ranges 18 and 19 West, hereinbefore described.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 11 N., R. 18 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by H. Fitzhugh in 1883.

From the corner of sections 10, 11, 14, and 15, monumented with an aluminum post, 2 1/2 ins. in diam., extending 6 ins. out of the ground, with the aluminum cap marked as described in the official record of the resurvey by C. P. Sylvester in 1979.

N. 0°15.4' W., between sections 10 and 11.

Over pasture land.

**40.064** Point for the 1/4 section corner of sections 10 and 11, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N	R18W
	1/4
S10	S11
	1993

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level pasture land.

**80.128** Point for the corner of sections 2, 3, 10, and 11, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

T11N	R18W
S3	S2
S10	S11
	1993

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level pasture land.

From the 1/4 section corner of sections 2 and 11, monumented with a quartzite stone, 16x12x4 ins., firmly set, and plainly marked 1/4 on the N face.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

T11N R18W  
1/4    S2  
         S11  
         1993

Deposit the marked stone alongside the aluminum post.

The corner is located in a 4 strand barbed-wire fence line, bears E and W, on rolling W slope in sagebrush.

N. 89°12.1' W., between sections 2 and 11.

Over gently rolling, W slope, through sagebrush and pasture land.

**40.005** The corner of sections 2, 3, 10 and 11.

---

N. 0°21.9' E., between sections 2 and 3.

Over nearly level pasture land.

**40.064** Point for the 1/4 section corner of sections 2 and 3, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
1/4  
S3 | S2  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level pasture land.

Continue over pasture land and the residential area of Grouse Creek, Utah.

**80.828** The corner of sections 2, 3, 34, and 35, on north boundary of the township, hereinbefore described.

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Reestablishment of the Survey Executed by H. Fitzhugh in 1883  
and the Dependent Resurvey Executed by R. A. Zaninovich in 1990.

From the corner of sections 27, 28, 33, and 34, monumented with an aluminum post, 2 1/2 ins. diam., projecting 6 ins. above the ground, with aluminum cap, marked as described in the official record of the resurvey by R. A. Zaninovich in 1990.

From this corner:

National Geodetic Survey triangulation station "VT BM L59" bears N. 45°46.7' E., 55.627 chains distance.

N. 0°08.8' W., between sections 27 and 28.

Over gently rolling cultivated land.

**41.058** Point for the 1/4 section corner of sections 27 and 28, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 30 ins. in the ground, with aluminum cap marked:

T11N R18W  
1/4  
S28 | S27  
1993

Deposit a magnet alongside aluminum post.

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level cultivated land.

**82.116** The corner of sections 21, 22, 27, and 28, monumented with an aluminum post, projecting 8 ins. out of a collar of stone, with aluminum cap marked as described in the official record of the resurvey by C. P. Sylvester in 1979.

Reestablishment of the Survey Executed by H. Fitzhugh in 1883

From the corner of sections 9, 10, 15, and 16, monumented with an aluminum post, 2 1/2 ins. diam., projecting 9 ins. out of a collar of stone, with aluminum cap marked as described in the official record of the 1979 resurvey by C.P. Sylvester.

N. 0°12.7' W., between sections 9 and 10.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Over gently rolling bench land, through sagebrush and widely scattered juniper.

- 39.876** Point for the 1/4 section corner of sections 9 and 10, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
1/4  
S9 | S10  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on a rolling E slope in sagebrush and widely scattered juniper growth.

- 59.814** Point for the N 1/16 section corner of sections 9 and 10.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
N 1/16  
S9 | S10  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on a gentle S, slope in sagebrush.

- 79.752** The corner of sections 3, 4, 9, and 10, monumented with a quartzite stone, 18x12x3 ins., firmly set, and plainly marked with 3 notches on E and 5 notches on S edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
S4 | S3  
S9 | S10  
1993

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone W of the corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set a steel fence post alongside the aluminum post.

The corner is located on gently rolling S slope in sagebrush and scattered juniper growth.

---

From the corner of sections 2, 3, 10, and 11.

S. 89°47.7' W., between sections 3 and 10.

Over pasture land and rolling bench land.

**39.846** The 1/4 section corner of sections 3 and 10, monumented with a quartzite stone, 14x9x4 ins., firmly set and plainly marked 1/4 on N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T11N R18W
1/4	<u>S3</u>
	S10
	1993

Deposit the marked stone alongside the aluminum post.

The corner is located in a 4 strand barbed wire fence line, bears N and S in sagebrush to E and pasture to the W.

---

S. 89°32.6' W., beginning new measurement.

Over rolling bench land, through pasture land.

**20.186** Point for the W 1/16 section corner of sections 3 and 10.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T11N R18W
W 1/16	<u>S3</u>
	S10
	1993

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level, dry, pasture land on the N edge of an old abandoned road, bears NE and SW.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

**40.372**

The corner of sections 3, 4, 9, and 10.

---

N. 0°19.6' E., between sections 3 and 4.

Over rolling bench land, through sagebrush and juniper growth.

**40.064**

Point for the 1/4 section corner of sections 3 and 4, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
1/4  
S4 | S3  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level land in sagebrush, native grasses, and scattered juniper growth.

**60.096**

Point for the N 1/16 section corner of sections 3 and 4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
N 1/16  
S4 | S3  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level land in sagebrush.

**80.629**

The corner of sections 3, 4, 33, and 34 on the north boundary of the township, hereinbefore described.

---

From the corner of sections 4, 5, 32, and 33, on the south boundary of the township, hereinbefore described.

N. 0°05.6' W., between sections 32 and 33.

Over cultivated land.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

**40.018**

Point for the 1/4 section corner of sections 32 and 33, at proportionate distance. No remaining evidence of the original corner was found.

Point falls in cultivated land and is not monumented.

**80.036**

Point for the corner of sections 28, 29, 32, and 33, at proportionate distance. No remaining evidence of the original corner was found.

Point falls in cultivated land and is not monumented.

---

From the corner of sections 27, 28, 33, and 34

S. 89°44.4' W., between sections 28 and 33.

Over rolling cultivated land.

**20.093**

Point for the E 1/16 section corner of sections 28 and 33.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T11N R18W
E 1/16	<u>S28</u>
	S33
	1993

Set a steel fence post alongside the aluminum post.

The corner is located 2 lks. S of a 4 strand barbed-wire fence line, bears E and W, with cultivated land on the S side of the fence and sagebrush on the N.

**40.186**

Point for the 1/4 section corner of sections 28 and 33, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T11N R18W
1/4	<u>S28</u>
	S33
	1993

Set a steel fence post alongside the aluminum post.

The corner is located 2 1/2 lks. S of a 4 strand barbed-wire fence line, bears E and W, in sagebrush.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

**CHAINS****60.279**

Point for the W 1/16 section corner of sections 28 and 33.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T11N R18W
W 1/16	<u>S28</u>
	S33
	1993

Set a steel fence post alongside the aluminum post.

Deposit a magnet alongside the aluminum post.

The corner is located on gently rolling land in sagebrush.

**80.372**

The point for the corner of sections 28, 29, 32, and 33.

---

N. 0°54.6' E., between sections 28 and 29.

Over gently rolling cultivated land.

**20.012**

Point for the S 1/16 section corner of sections 28 and 29.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T11N R18W
	S 1/16
S29	S28
	1993

Deposit a magnet alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level pasture land.

**40.024**

The 1/4 section corner of sections 28 and 29, monumented with a quartzite stone, 14x10x6 ins., firmly set and plainly marked 1/4 on the W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T11N R18W  
1/4  
S29 | S28  
1993

From which

The SW corner of an old cemetery, bears N. 2° 36' E., 5.24 chs. dist.

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone W of the corner.

Set a steel fence post alongside the aluminum post.

The corner is located on a rolling, SE slope in sagebrush.

---

N. 0°19.8' W., beginning new measurement.

**39.716** The corner of sections 20, 21, 28, and 29, monumented with a quartzite stone, 18x10x4 ins., firmly set at a fence corner and plainly marked with 2 notches on S and 4 notches on E edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
S20 | S21  
S29 | S28  
1993

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone N of the corner.

The corner is located in a 4 strand barbwire fence corner, bears E and S.

---

From the corner of sections 21, 22, 27, and 28.

S. 88°01.6' W., between sections 21 and 28.

Over rolling bench land, through sagebrush and scattered juniper growth.

**39.892** Point for the 1/4 section corner of sections 21 and 28, at proportionate distance. No remaining evidence of the original corner was found.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T11N R18W  
1/4    S21  
         S28  
         1993

Set a steel fence post alongside the aluminum post.

The corner is located on a gentle, S slope in sagebrush and widely scattered juniper growth.

**59.838** Point for the W 1/16 section corner of sections 21 and 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
W 1/16    S21  
             S28  
             1993

Set a steel fence post alongside the aluminum post.

The corner is located on a gentle W slope, 20 lks. N of a fence line, 4 strand barbed wire, bears E and W, in sagebrush and widely scattered juniper growth.

**79.784** The corner of sections 20, 21, 28, and 29.

---

N. 0°27.8' W., between sections 20 and 21.

Over rolling bench land, through sagebrush and widely scattered juniper growth.

**39.876** Point for the 1/4 section corner of sections 20 and 21, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap marked:

T11N R18W  
          1/4  
S20 | S21  
          1993

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level cleared land.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

**CHAINS****79.752**

The corner of sections 16, 17, 20, and 21, monumented with an aluminum post, 2 1/2 ins. diam., projecting 6 ins. above the ground, with aluminum cap, marked as described in the official record of the resurvey by C.P. Sylvester in 1979.

The corner is located on nearly level land in a 4 strand barbed-wire fence corner, bears N and E.

---

Reestablishment of the Survey Executed by H. Fitzhugh in 1883 and  
the Resurvey Executed by Craig P. Sylvester in 1979

---

From the 1/4 section corner of sections 16 and 21, monumented with an aluminum post, 2 1/2 ins. in diam. projecting 6 ins. above the ground, with aluminum cap marked as described in the official record of the resurvey by C.P. Sylvester in 1979.

S. 89°15.8' W., between sections 16 and 21.

Over rolling bench land, through sagebrush.

**19.958**

Point for the W 1/16 section corner of sections 16 and 21.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T11N R18W
W 1/16	<u>S16</u>
	S21
	1993

Set a steel fence post alongside the aluminum post.

The corner is located on gently rolling land in sagebrush, 17 lks. N of a 4 strand barbed wire fence line, bears E and W.

**39.916**

The corner of sections 16, 17, 20, and 21.

---

Reestablishment of the Survey Executed by H. Fitzhugh in 1883.

---

From the corner of sections 9, 10, 15, and 16.

S. 89°22.3' W., between sections 9 and 16.

Over rolling bench land, through sagebrush and scattered juniper.

**39.691**

Point for the 1/4 section corner of sections 9 and 16, at proportionate distance. No remaining evidence of the original corner was found.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T11N R18W
1/4	<u>S9</u>
	S16
	1993

Raise a mound of stone N of the corner.

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level ground in sagebrush and scattered juniper.

**79.382**

Point for the corner of sections 8, 9, 16, and 17, at proportionate distance. No remaining evidence of the original corner was found.

The point falls in an improved gravel road, bears NE and SW. Set a spike flush with the road surface.

From which I set:

An aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, for a reference monument, bears S. 45° E., .758 chs. dist., with aluminum cap, marked: T11N R18W S16 N 45 W 50 FT. 1993.

An aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, for a reference monument, bears S. 45° W., .758 chs. dist., with aluminum cap marked: T11N R18W S17 N 45 E 50 ft. 1993

Set steel fence posts alongside the aluminum posts.

From this corner, the corner of sections 16, 17, 20 and 21, bears S. 0°32.3' E., 79.914 chains distance. The intervening 1/4 section corner was not found.

---

N. 0°14.7' W., between sections 8 and 9.

Over rolling bench land, through sagebrush and scattered juniper.

**39.956**

Point for the 1/4 section corner of sections 8 and 9, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T11N R18W  
1/4  
S8 | S9  
1993

Raise a mound of stone W of the corner.

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level ground in sagebrush.

**79.912** The corner of sections 4, 5, 8, and 9, monumented with a limestone, 18x15x10 ins., firmly set, and plainly marked with 4 notches on E and 5 notches on S edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with aluminum cap marked:

T11N R18W  
S5 | S4  
S8 | S9  
1993

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone W of the corner.

The corner is located on a gentle, SE slope in juniper growth.

From the corner of sections 3, 4, 9, and 10.

S. 89°29.1' W., between sections 4 and 9.

Over rolling bench land, through sagebrush and juniper growth.

**39.704** Point for the 1/4 section corner of sections 4 and 9, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
1/4    S4  
         S9  
         1993

The corner is located on nearly level ground in sagebrush and native grasses.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

**CHAINS****79.408**

The corner of sections 4, 5, 8, and 9.

---

N. 0°06.8' W., between sections 4 and 5.

Over rolling bench land, through sagebrush and juniper growth.

**40.198**

Point for the 1/4 section corner of sections 4 and 5, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with aluminum cap marked:

T11N R18W  
1/4  
S5 | S4  
1993

Raise a mound of stone W of the corner.

The corner is located on a low ridge, bears SE and NW, in juniper growth.

**81.401**

The corner of sections 4, 5, 32, and 33, on the north boundary of the township, hereinbefore described.

---

From the corner of sections 5, 6, 31, and 32, on the south boundary of the township, hereinbefore described.

N. 0°04.3' W., between sections 31 and 32.

Over gently rolling bench land, through sagebrush and native grasses.

**39.918**

Point for the 1/4 section corner of sections 31 and 32, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
1/4  
S31 | S32  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level ground in sagebrush and native grasses.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

**79.836**

Point for the section corner of sections 29, 30, 31, and 32, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N	R18W
<u>S30</u>	<u>S29</u>
S31	S32
1993	

Raise a mound of stone W of the corner.

Set a steel fence post alongside the aluminum post.

The corner is located on a S slope in sagebrush, 17 lks. S of a 4 strand barbed-wire fence line, bears E and W.

---

From the point for the corner of sections 28, 29, 32, and 33.

S. 89°39.5' W., between sections 29 and 32.

Over rolling cultivated land.

**20.126**

Point for the E 1/16 section corner of sections 29 and 32.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 30 ins. in the ground, with aluminum cap marked:

	T11N	R18W
E 1/16	<u>S29</u>	
	S32	
1993		

Deposit a magnet at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level cultivated land.

**40.252**

Point for the 1/4 section corner of sections 29 and 32, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T11N R18W  
1/4 S29  
S32  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level ground in sagebrush and native grasses.

**80.504** The corner of sections 29, 30, 31, and 32.

---

N. 89°45.6' W., between sections 30 and 31.

Over rolling bench land, through sagebrush and scattered juniper growth.

**40.086** Point for the 1/4 section corner of sections 30 and 31, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
1/4 S30  
S31  
1993

Set a steel fence post alongside the aluminum post.

The corner is located 17 lks. N of a 4 strand barbed wire fence line, bears E and W, on gentle, S slope in sagebrush and scattered juniper growth.

**80.472** The corner of sections 25, 30, 31, and 36, on the west boundary of the township, hereinbefore described.

---

From the corner of sections 29, 30, 31, and 32.

N. 0°04.0' W., between sections 29 and 30.

Over rolling bench land, through sagebrush and native grasses.

**39.918** Point for the 1/4 section corner of sections 29 and 30, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T11N R18W  
1/4  
S30 | S29  
1993

Raise a mound of stone W of the corner.

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level ground in sagebrush.

**79.836** Point for the corner of sections 19, 20, 29, and 30, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
S19 | S20  
S30 | S29  
1993

Raise a mound of stone W of the corner.

Set a steel fence post alongside the aluminum post.

The corner is located on a gentle, E slope in sagebrush.

---

From the corner of sections 20, 21, 28, and 29.

S. 89°44.0' W., between sections 20 and 29.

Over rolling bench land, through sagebrush and cultivated land.

**40.492** Point for the 1/4 section corner of sections 20 and 29, at proportionate distance. No remaining evidence of the original corner was found. Point falls on cultivated land and is not monumented.

**80.984** The corner of sections 19, 20, 29, and 30.

---

N. 89°14.7' W., between sections 19 and 30.

Over rolling bench land, through sagebrush.

**40.268** Point for the 1/4 section corner of sections 19 and 30, at proportionate distance. No remaining evidence of the original corner was found.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
1/4    S19  
          S30  
          1993

Raise a mound of stone N of the corner.

Set a steel fence post alongside the aluminum post.

The corner is located on a gentle, SE slope, in sagebrush and scattered juniper growth.

**80.636** The corner of sections 19, 24, 25, and 30, on the west boundary of the township, hereinbefore described.

---

From the corner of sections 19, 20, 29, and 30.

N. 0°04.7' E., between sections 19 and 20.

Over rolling bench land, through sagebrush and scattered juniper growth.

**39.918** Point for the 1/4 section corner of sections 19 and 20, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
          1/4  
S19 | S20  
          1993

Set a steel fence post alongside the aluminum post.

The corner is located on a gentle, N slope in sagebrush and scattered juniper growth.

Continue over benchland and cultivated land.

**79.836** Point for the corner of sections 17, 18, 19, and 20, at proportionate distance. No remaining evidence of the original corner was found.

Corner falls in cultivated land and is not monumented.

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the corner of sections 16, 17, 20, and 21.

S. 89°47.5' W., between sections 17 and 20.

Over cultivated and broken bench land, through pasture and juniper growth.

**40.106** Point for the 1/4 section corner of sections 17 and 20, at proportionate distance. No remaining evidence of the original corner was found.

Corner falls in cultivated land and is not monumented.

**80.212** The point for the corner of sections 17, 18, 19, and 20, not monumented.

---

N. 89°39.0' W., between sections 18 and 19.

Over cultivated and broken bench land, through pasture, sagebrush, and juniper growth.

**40.116** Point for the 1/4 section corner of sections 18 and 19, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with aluminum cap marked:

T11N R18W  
1/4    S18  
          S19  
          1993

The corner is located on a S slope in juniper growth.

**80.462** The point for the corner of sections 13, 18, 19, and 24 on the west boundary of the township, hereinbefore described.

---

From the point for the corner of sections 17, 18, 19, and 20.

N. 0°04.9' E., between sections 17 and 18.

Over gently rolling pasture land.

**39.918** The 1/4 section corner of sections 17 and 18, monumented with a quartzite stone, 14x8x5 ins., firmly set and plainly marked 1/4 on the W face.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W	
1/4	
S18	S17
1993	

Deposit the marked stone alongside the aluminum post.

The corner is located in a 4 strand barbed wire fence corner, bears N, E and W, on nearly level cultivated land.

---

N. 0°42.2' W., beginning new measurement.

**40.029** The corner of sections 7, 8, 17, and 18, monumented with a quartzite stone, 18x9x4 ins., firmly set, and plainly marked with 5 notches on E and 4 notches on S edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W	
S7	S8
S18	S17
1993	

Deposit the marked stone alongside the aluminum post.

The corner is located in a 4 strand barbed wire fence corner, bears E, S and W, on nearly level land in sagebrush and scattered juniper growth.

---

From the corner of sections 8, 9, 16, and 17.

S. 89°48.9' W., between sections 8 and 17.

Over rolling bench land, cultivated land and broken bench land, through sagebrush, pasture and scattered juniper

**39.938** Point for the 1/4 section corner of sections 8 and 17, at proportionate distance. The original corner a quartzite, 19x6x5 ins., plainly marked was found lying loose on the ground, (May have been disturbed by a bulldozer at one time).

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

T11N R18W

1/4    S8  
          S17  
          1993

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level land in sagebrush and native grasses.

**79.876** The corner of sections 7, 8, 17, and 18.

---

N. 89°43.3' W., between sections 7 and 18.

**19.746** Point for the E 1/16 section corner of sections 7 and 18.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W

E 1/16    S7  
                  S18  
                  1993

Set a steel fence post alongside the aluminum post.

The corner is located on a gentle, W slope in sagebrush and scattered juniper growth.

**39.492** Point for the 1/4 section corner of sections 7 and 18, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W

1/4    S7  
          S18  
          1993

Deposit a magnet at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

The corner is located on the W edge of a field, bears NW and SE.

Continue over broken bench land.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

**78.984**

The corner of sections 7, 12, 13, and 18, on the west boundary of the township, hereinbefore described.

From the corner of sections 7, 8, 17, and 18.

N. 0°07.3' W., between sections 7 and 8.

Over rolling bench land, through sagebrush and scattered juniper growth.

**40.040**

Point for the 1/4 section corner of sections 7 and 8, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post 30 ins. long, 2 1/2 ins. diam. 24 ins. in the ground with aluminum cap marked:

T11N	R18W
	1/4
S7	S8
	1993

Deposit a magnet at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level land in sagebrush.

**80.080**

The corner of sections 5, 6, 7, and 8, monumented with a quartzite stone, 20x8x8 ins. firmly set and plainly marked with 5 notches on the E and S edges.

At the corner point

Set an aluminum post 30 ins. long 2 1/2 ins. diam. 24 ins. in the ground with aluminum cap marked:

T11N	R18W
S6	S5
S7	S8
	1993

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone W of the corner.

Set a steel fence post alongside the aluminum post.

The corner is located on a gentle, W slope in sagebrush.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the corner of sections 4, 5, 8, and 9.

N. 89°57.0' W., between sections 5 and 8.

Over rolling bench land through sagebrush and juniper growth.

**39.702** The 1/4 section corner of sections 5 and 8, monumented with a conglomerate stone, 22x10x8 ins., firmly set and dimly marked 1/4 on the N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
1/4    S5  
          S8  
          1993

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone N of the corner.

The corner is located 20 lks. W of a draw, drains S, in sagebrush.

S. 89°48.4' W., beginning new measurement.

**39.986** The corner of sections 5, 6, 7, and 8.

N. 88°36.2' W., between sections 6 and 7.

Over rolling bench land, through sagebrush and scattered juniper growth.

**39.754** Point for the 1/4 section corner of sections 6 and 7, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
1/4    S6  
          S7  
          1993

Raise a mound of stone N of the corner.

The corner is located on nearly level land in sagebrush and native grasses.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

**CHAINS****59.631**

Point for the W 1/16 section corner of sections 6 and 7.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T11N R18W
W 1/16	<u>S6</u>
	S7
	1993

Set a steel fence post alongside the aluminum post.

The corner is located 29 lks. S of a 4 strand barbed-wire fence line, bears E and W, on E slope in sagebrush.

Continue over broken mountain land, through sagebrush and juniper growth.

**78.713**

The corner of sections 1, 6, 7, and 12, on the west boundary of the township, hereinbefore described.

---

From the corner of sections 5, 6, 7, and 8.

N. 0°16.2' W., between sections 5 and 6.

Over rolling bench land, through sagebrush and juniper growth.

**40.660**

Point for the 1/4 section corner of sections 5 and 6, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T11N R18W
	1/4
S6	S5
	1993

Raise a mound of stone W of the corner.

The corner is located on a S slope at the base of a small hill in sagebrush and scattered juniper growth.

**81.970**

The corner of sections 5, 6, 31, and 32, on the north boundary of the township, hereinbefore described.

---

THE SUBDIVISION OF SECTION 3,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

CHAINS

The Subdivision of Section 3,  
T. 11 N., R. 18 W., Salt Lake Meridian, Utah.

From the 1/4 section corner of section 3 and 10.

N. 0°07.2' E., on the N - S center line of section 3.

**39.977** Point for the center 1/4 section corner, at intersection with the E - W center line of section 3.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
C 1/4  
S3  
1993

Deposit a magnet at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

The corner is located S. 1°37' W., 29 lks. dist., of a fence corner bears N and W.

**60.003** Point for the center N 1/16 section corner of section 3.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
C  
N 1/16 | S3  
C  
1993

Set a steel fence post alongside the aluminum post.

The corner is located N. 1°38' E., 95 lks dist., of a 4 strand barbed-wire fence corner, bears E, S, and W.

**80.629** The 1/4 section corner of sections 3 and 34, on the north boundary of the township, hereinbefore described.

From the 1/4 section corner of sections 2 and 3.

S. 89°40.0' W., on the E - W center line of section 3.

THE SUBDIVISION OF SECTION 3,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

**CHAINS****40.014**

The center 1/4 section corner of section 3.

**60.125**

Point for the center W 1/16 section corner of section 3.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap marked:

T11N R18W  
C — W 1/16 — C  
S3  
1993

Set a steel fence post alongside the aluminum post.

The corner is located 31 1/2 lks. E of a 4 strand barbed wire fence line, bears N and S.

**80.236**

The 1/4 section corner of sections 3 and 4.

---

From the W 1/16 section corner of sections 3 and 10.

N. 0°13.4' E., on the N - S center line of the SW 1/4 of section 3.

**40.020**

The center W 1/16 corner of section 3.

---

From the center N 1/16 section corner of section 3.

S. 89°40.3' W., on the E - W center line of the NW 1/4 of section 3.

**40.146**

The N 1/16 section corner of sections 3 and 4.

---

The Subdivision of Section 6,  
T. 11 N., R. 18 W., Salt Lake Meridian, Utah.

---

From the 1/4 section corner of sections 6 and 7.

N. 0°25.3' W., on the N - S center line of section 6.

**20.230**

Point for the center S 1/16 section corner of section 6.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 6,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T11N R18W  
C  
S 1/16 | S6  
C  
1993

Set a steel fence post alongside the aluminum post.

The corner is located 6 1/2 lks. W of a 4 strand barbed wire fence line, bears N and S, on SW slope in dense juniper growth.

**40.460** Point for the center 1/4 section corner, at intersection with the E - W center line of section 6.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
C 1/4 S6  
1993

Set a steel fence post alongside the aluminum post.

Raise a mound of stone W of the corner.

The corner is located in the bottom of a draw, drains SW, in juniper growth.

**81.234** The 1/4 section corner of sections 6 and 31, on the north boundary of the township, hereinbefore described.

From the 1/4 section corner of sections 5 and 6.

N. 88°53.8' W., on the E - W center line of section 6.

**39.852** The center 1/4 section corner of section 6.

**51.778** Point selected for the witness corner to the center W 1/16 section corner section 6. The true point falls within a reservoir and cannot be monumented.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

WC  
T11N R18W  
C — W 1/16 — C  
S6  
1993

THE SUBDIVISION OF SECTION 6,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set a steel fence post alongside the aluminum post.

The corner is located in an old, trail road, bears N and S, on gentle, W slope in sagebrush.

**59.778** True point for the center W 1/16 section corner of section 6.

**78.459** The 1/4 section corner of sections 1 and 6, on the west boundary of the township, hereinbefore described.

---

From the W 1/16 section corner of sections 6 and 7.

N. 0°29.9' W. on the N - S center line of the SW 1/4 of section 6.

**20.180** Point for the SW 1/16 section corner, at intersection with the E -W center line of the SW 1/4 of section 6. Point falls in reservoir and is not monumented.

**40.359** True point for the center W 1/16 section corner of section 6.

---

From the center S 1/16 section corner of section 6.

N. 88°45.2' W. on the E - W center line of the SW 1/4 of section 6.

**19.902** The point for the SW 1/16 section corner of section 6.

**38.784** The S 1/16 section corner of sections 1 and 6, on the west boundary of the township, hereinbefore described.

---

From the true point for the center W 1/16 section corner of section 6.

N. 0°30.0' W. on the N - S center line of the NW 1/4 of section 6.

**40.506** The W 1/16 section corner of sections 6 and 31, on the north boundary of the township, hereinbefore described.

---

The Subdivision of Section 7,  
T. 11 N. R. 18 W. Salt Lake Meridian Utah.

---

From the 1/4 section corner of sections 7 and 18.

N. 0°18.3' W. on the N - S center line of section 7.

THE SUBDIVISION OF SECTION 7,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**  
**33.426**

Point for an Angle Point of private property corner.

Set an aluminum post 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

AP  
T11N R18W  
C  
S7 |  
C  
1993

Set a steel fence post alongside the aluminum post.

The corner is located 6 lks. N of a 4 strand barbed-wire fence line, bears E and W, irregularly on nearly level lands in sagebrush and cottonwood trees.

**40.426**

Point for the center 1/4 section corner at intersection with the E - W center line.

Set an aluminum post 30 ins. long 2 1/2 ins. diam. 24 ins. in the ground, with an aluminum cap marked:

T11N R18W  
C 1/4 S7  
1993

Set a steel fence post alongside the aluminum post.

Raise a mound of stone W of the corner.

The corner is located on a SE slope in sagebrush and juniper growth.

**80.856**

The 1/4 section corner of sections 6 and 7.

---

From the 1/4 section corner of sections 7 and 8.

N. 89°09.8' W., on the E - W center line of section 7.

**19.811**

Point for the center E 1/16 section corner of section 7.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
C — E 1/16 — C  
S7  
1993

THE SUBDIVISION OF SECTION 7,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

- The corner is located on gently rolling land in sagebrush and scattered juniper growth.
- 39.622** The center 1/4 section corner of section 7.
- 78.846** The 1/4 section corner of sections 7 and 12, on the west boundary of the township, hereinbefore described.
- 
- From the E 1/16 section corner of sections 7 and 18.
- N. 0°12.8' W., on the N - S center line of the SE 1/4 of section 7.
- 33.233** Point for an Angle Point of private property corner.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:
- AP  
T11N R18W  
S7  
  
1993
- Set a steel fence post alongside the aluminum post.
- The corner is located on a SW slope in sagebrush and scattered juniper growth.
- From this corner, the Angle Point on the N - S center line of the section, bears N. 89°09.6' W., 19.800 chains distance.
- 40.233** The center E 1/16 section corner of section 7.
- 
- The Subdivision of Section 10,  
T 11 N., R. 18 W., Salt Lake Meridian, Utah.
- 
- From the 1/4 section corner of sections 10 and 15, monumented with an aluminum post, 2 1/2 ins. diam., projecting 6 ins. above the ground and in a collar of stone, with the aluminum cap marked as described in the official record of the resurvey by C.P. Sylvester in 1979.
- N. 1°01.8' W., on the N - S center line of section 10.
- 39.006** Point for the center 1/4 section corner, at intersection with the E - W center line of section 10.

THE SUBDIVISION OF SECTION 10,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

T11N R18W  
C 1/4 S10  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on a E slope in juniper.

**59.037** Point for the center N 1/16 section corner of section 10; not monumented.

**79.068** The 1/4 section corner of sections 3 and 10.

---

From the 1/4 section corner of sections 10 and 11.

S. 89°48.2' W., on the E - W center line of section 10.

**39.316** The center 1/4 section corner of section 10.

**49.551** Point for the center E - W 1/64 section corner of section 10.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T11N R18W  
C  $\frac{E-W 1/64}{S10}$  C  
1993

Set a steel fence post alongside the aluminum post.

The corner is located in a dump site area, 50 lks. E of the N end of the pit, bears SW.

**59.786** Point for the center W 1/16 section corner of section 10.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
C  $\frac{W 1/16}{S10}$  C  
1993

Set a steel fence post alongside the aluminum post.

THE SUBDIVISION OF SECTION 10,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

- The corner is located on a NW slope in sagebrush.
- 80.256** The 1/4 section corner of sections 9 and 10.
- 
- From the center W 1/16 section corner of section 10.
- N. 0°37.1' W., on the N - S center line of the NW 1/4 of section 10.
- 19.984** Point for the NW 1/16 section corner, at intersection with the E - W center line of the NW 1/4 of section 10.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:
- T11N R18W  
NW 1/16 S10  
1993
- Set a steel fence post alongside the aluminum post.
- The corner is located 7 lks. N of a 4 strand barbed-wire fence line, bears E and W, on nearly level dry pasture.
- 39.968** The W 1/16 section corner of sections 3 and 10.
- 
- From the point for the center N 1/16 section corner of section 10.
- S. 89°40.3' W., on the E - W center line of the NW 1/4 of section 10.
- 10.164** Point for the center E - NW 1/64 section corner of section 10.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:
- T11N R18W  
C E NW 1/64 S10  
1993
- Set a steel fence post alongside the aluminum post.
- The corner is located 2 lks. N of a 4 strand barbed-wire fence line, bears E and W on gentle, SW slope in dry pasture.
- 20.328** The NW 1/16 section corner of section 10.
- 40.656** The N 1/16 section corner of sections 9 and 10.

THE SUBDIVISION OF SECTION 10,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the center E - W 1/64 section corner of section 10.

N. 0°49.3' W., on the N - S center line of the SE 1/4 of the NW 1/4 of section 10.

**20.007**

The center E - NW 1/64 section corner of section 10.

---

The Subdivision of Section 15,  
T. 11 N. R. 18 W. Salt Lake Meridian Utah

---

From the 1/4 section corner of sections 15 and 22, monumented with an aluminum post, 2 1/2 ins. diam., projecting 6 ins. above the ground, with aluminum cap marked as described in the official record of the resurvey by C.P. Sylvester in 1979.

N. 0°25.7' E., on the N - S center line of section 15.

**38.411**

Point for the center 1/4 section corner at intersection with the E - W center line of section 15.

Set an aluminum post 30 ins. long 2 1/2 ins. diam. 24 ins. in the ground with aluminum cap marked:

T11N R18W  
C 1/4 S15  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on gently rolling land in sagebrush.

**79.496**

The 1/4 section corner of sections 10 and 15.

---

From the 1/4 section corner of sections 14 and 15.

N. 89°43.5' W., on the E - W center line of section 15.

**38.807**

The center 1/4 section corner of section 15.

**59.597**

Point for the center W 1/16 section corner of section 15.

Set an aluminum post 30 ins. long 2 1/2 ins. diam. 24 ins. in the ground with aluminum cap marked:

THE SUBDIVISION OF SECTION 15,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T11N R18W  
C  $\frac{W 1/16}{S15}$  C  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on a gentle E slope in sagebrush.

- 80.387** The 1/4 section corner of sections 15 and 16, monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. above the ground, and in a collar of stone, with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1979.

From the W 1/16 section corner of sections 15 and 22, monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. above the ground, and in a collar of stone, with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1979.

N. 0°56.7' W., on the N - S center line of the SW 1/4 of section 15.

- 39.162** The center W 1/16 section corner of section 15.

N. 0°29.7' E., on the N - S center line of the NW 1/4 of section 15.

- 40.468** The W 1/16 section corner of sections 10 and 15, monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. out of the ground, with brass cap, marked as described in the official record of the resurvey by C.P. Sylvester in 1979.

The Subdivision of Section 18,  
T. 11 N., R. 18 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 18 and 19.

N. 0°07.7' E., on the N - S center line of section 18.

- 39.921** Point for the center 1/4 section corner, at intersection with the E - W center line of section 18.

Set an aluminum post, 30 ins. Long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 18,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T11N R18W  
C 1/4 S18  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on the W edge of an improved gravel road, bears N and S.

**59.906** Point for the center N 1/16 section corner of section 18.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
C  
N 1/16 | S18  
C  
1993

Set a steel fence post alongside the aluminum post.

**79.891** The 1/4 section corner of sections 7 and 18.

---

From the 1/4 section corner of sections 17 and 18.

N. 89°38.7' W., on the E - W center line of section 18.

**40.078** The center 1/4 section corner of section 18.

**79.997** The 1/4 section corner of sections 13 and 18, on the west boundary of the township, hereinbefore described.

---

From the center N 1/16 section corner of section 18.

N. 89°41.1' W., on the E - W center line of the NW 1/4 of section 18.

**39.706** The N 1/16 section corner of sections 13 and 18, on the west boundary of the township, hereinbefore described.

---

The Subdivision of Section 21,  
T 11 N., R. 18 W., Salt Lake Meridian Utah

---

From the 1/4 section corner of sections 21 and 28.

THE SUBDIVISION OF SECTION 21,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

N. 0°25.8' W., on the N - S center line of section 21.

**39.034** Point for the center 1/4 section corner at intersection with the E - W center line of section 21.

Set an aluminum post 30 ins. long 2 1/2 ins. diam. 24 ins. in the ground and in a collar of stone, with aluminum cap marked:

T11N R18W  
C 1/4 S21  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on a SW slope in sagebrush.

**78.890** The 1/4 section corner of sections 16 and 21.

---

From the 1/4 section corner of sections 21 and 22, monumented with an iron post 2 1/2 ins. diam., projecting 6 ins. above the ground, and in a collar of stone, with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1979.

S. 89°14.2' W., on the E - W center line of section 21.

**37.742** The center 1/4 section corner of section 21.

**57.690** Point for the center W 1/16 section corner of section 21.

Set an aluminum post 30 ins. long 2 1/2 ins. diam. 24 ins. in the ground with aluminum cap marked:

T11N R18W  
C  $\frac{W\ 1/16}{S21}$  C  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level land in cleared area with scattered juniper.

**77.638** The 1/4 section corner of sections 20 and 21.

---

From the W 1/16 section corner of sections 21 and 28.

N. 0°26.8' W., on the N - S center line of the SW 1/4 of section 21.

THE SUBDIVISION OF SECTION 21,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

**39.456**

The center W 1/16 section corner of section 21.

N. 0°26.8' W., on the N - S center line of the NW 1/4 of section 21.

**39.866**

The W 1/16 section corner of sections 16 and 21.

The Subdivision of Section 28,  
T. 11 N., R. 18 W., Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 28 and 33.

N. 0°04.2' E., on the N - S center line of section 28.

**20.267**

Point for the center S 1/16 section corner of section 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
C  
S 1/16 | S28  
C  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on gently rolling land in sagebrush.

**40.534**

Point for the center 1/4 section corner, at intersection with the E - W center line of section 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
C 1/4 S28  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on a gently, rolling SE slope in sagebrush.

**80.924**

The 1/4 section corner of sections 21 and 28.

THE SUBDIVISION OF SECTION 28,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the 1/4 section corner of sections 27 and 28.

S. 88°59.4' W., on the E - W center line of section 28.

**20.016** Point for the center E 1/16 section corner of section 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
C — E 1/16 — C  
S28  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on a rolling SE slope in sagebrush.

**40.032** The center 1/4 section corner of section 28.

**59.832** Point for the center W 1/16 section corner of section 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
C — W 1/16 — C  
S28  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on a gentle, W slope on top of low ridge, bears NE and SW, in sagebrush.

**79.632** The 1/4 section corner of sections 28 and 29.

---

From the E 1/16 section corner of sections 28 and 33.

N. 0°02.4' W., on the N - S center line of the SE 1/4 of section 28.

**40.796** The center E 1/16 section corner of section 28.

---

From the W 1/16 section corner of sections 28 and 33.

THE SUBDIVISION OF SECTION 28,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

N. 0°29.2' E., on the N - S center line of the SW 1/4 of section 28.

**20.138** Point for the SW 1/16 section corner of section 28, at intersection with the E - W center line of the SW 1/4 of section 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., ins. in the ground, with aluminum cap marked:

T11N R18W  
SW 1/16 S28  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on gently, rolling land in sagebrush.

**40.277** The center W 1/16 section corner of section 28.

---

From the center S 1/16 section corner of section 28.

S. 89°21.6' W., on the E - W center line of the SW 1/4 of section 28.

**19.946** The SW 1/16 section corner of section 28.

**39.892** The S 1/16 section corner of sections 28 and 29.

---

The Subdivision of Section 32,  
T. 11 N., R. 18 W., Salt Lake Meridian, Utah.

---

From the 1/4 section corner of sections 5 and 32, on the south boundary of the township, hereinbefore described.

N. 0°05.0' W., on the N - S center line of section 32.

**39.968** Point for the center 1/4 section corner, at intersection with the E - W center line of section 32.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
C 1/4 S32  
1993

Set a steel fence post alongside the aluminum post.

THE SUBDIVISION OF SECTION 32,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

- The corner is located on gently rolling land in sagebrush.
- 79.936** The 1/4 section corner of sections 29 and 32.
- 
- From the point for the 1/4 section corner of sections 32 and 33.
- S. 89°43.8' W., on the E - W center line of section 32.
- 20.131** Point for the center E 1/16 section corner of section 32.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:
- T11N R18W

C — E 1/16 — C

S32

1993
- Set a steel fence post alongside the aluminum post.
- 40.262** The center 1/4 section corner of section 32.
- 80.524** The 1/4 section corner of sections 31 and 32.
- 
- From the E 1/16 section corner of sections 5 and 32, on the south boundary of the township, hereinbefore described.
- N. 0°05.3' W., on the N - S center line of the SE 1/4 of section 32.
- 39.993** The center E 1/16 section corner of section 32.
- 
- N. 0°05.3' W., on the N - S center line of the NE 1/4 of section 32.
- 39.993** The E 1/16 section corner of sections 29 and 32.
-

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD ASSISTANTS**

---


Name	Capacity
Todd S. Snyder	Surveying Aid

### CERTIFICATE OF SURVEY

I, *Gail E. Reynolds, Cadastral Surveyor*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *12th day of May, 1993*, I have *dependently resurveyed portions of the north, west (Guide Meridian) and south boundaries, and a portion of the subdivisional lines, and subdivided sections 3, 6, 7, 10, 15, 18, 21, 28, and 32, in Township 11 North, Range 18 West,*

of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

April 22, 1997  
Date

  
(Cadastral Surveyor)

\_\_\_\_\_  
Date

\_\_\_\_\_  
(Cadastral Surveyor)

### CERTIFICATE OF APPROVAL


BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of portions of the north, west (Guide Meridian) and south boundaries, and a portion of the subdivisional lines and the subdivision of sections 3, 6, 7, 10, 15, 18, 21, 28, and 32, Township 11 North, Range 18 West, Salt Lake Meridian, Utah,*

executed by *Gail E. Reynolds, Cadastral Surveyor*

having been critically examined and found correct, are hereby approved.

April 24, 1997  
Date

  
(Chief Cadastral Surveyor for Utah)