

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF
THE RETRACEMENT OF
THE UTAH AND ARIZONA STATE BOUNDARY
FROM MILE POST 58 TO MILE POST 60.19,
THE DEPENDENT RESURVEY OF SUBDIVISIONAL LINES
AND THE
SUBDIVISION OF SECTIONS 26, 27, 28, 29, 33, AND 34,
IN
TOWNSHIP 43 SOUTH, RANGE 10 WEST
OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Larry V. Judd
Cadastral Surveyor

Under special instructions dated *March 7, 1994*, approved *April 12, 1994*, which provided for the surveys included under Group Number *813*, and assignment instructions dated *April 13, 1994*.

Survey commenced *October 3, 1994*
Survey completed *November 23, 1994*

INDEX DIAGRAM

Township 43 South , Range 10 West

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	7 24
	24 26	22 23	18 19	12 13	7 8
30	24 29	22 28	18 27	12 26	6 25
	23	19 20	14 16	10 9	6
31	32	19 33	15 34	10 35	36
	3	3 3 3	4 4	5 5	
	(20)	(15)	(11)		

The Subdivision of Section 26.....Page 26

The Subdivision of Section 27.....Page 30

The Subdivision of Section 28.....Page 36

The Subdivision of Section 29.....Page 38

The Subdivision of Section 33.....Page 39

The Subdivision of Section 34.....Page 42

TOWNSHIP 43 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

The following field notes describe the retracement of the Utah and Arizona State Boundary (south boundary) from Mile post 58 to Mile post 60.19, the dependent resurvey of a portion of the subdivisional lines and the subdivision of sections 26, 27, 28, 29, 33, and 34, in Township 43 South, Range 10 West, Salt Lake Meridian, Utah.

History of Surveys

<u>Surveyed by</u>		<u>Retr. or Resurveyed by</u>	
<u>SOUTH BOUNDARY</u> (Utah - Arizona State Boundary)			
All	H.B. Carpenter	1901	
Portion			R.E.L. Collier & R. Gentry 1909
Portion			B.E. Craig 1993
<u>EAST BOUNDARY</u>			
All	R.E.L. Collier & R. Gentry	1909	
All			Jenkins & West 1897
Portion			M.H. Dalley 1929
Portion			Bird & Nelson 1924
<u>WEST BOUNDARY</u>			
All	R.E.L. Collier & R. Gentry	1909	
<u>NORTH BOUNDARY</u>			
All	R.E.L. Collier & R. Gentry	1909	
Portion			B.S. Owens & D.A. Cannon 1959
<u>SUBDIVISION</u>			
Portion	R.E.L. Collier & R. Gentry	1909	

The survey by B.E. Craig, Cadastral Surveyor for the Arizona State Office of the Bureau of Land Management is currently under review at the present time.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group 813, Utah, dated March 7, 1994.

TOWNSHIP 43 SOUTH, RANGE 10 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Section 27 was resurveyed and subdivided by Dean D. Holliday, R.L.S. No. 4666, for Washington County in 1978. The 1/4 section corner of sections 27 and 34, shown as being reestablished from the original bearing trees was not found. Using record information taken from the Washington County Area Reference Plat of Section 27 to reestablish the 1/4 section corner position, creates a large discrepancy in the bearings and distances to the original bearing trees. No field note record could be found of the Washington County survey and ties to the original bearing trees. The 1/4 section corner was reestablished from the record tie to the original standing bearing tree as shown in the body of these notes. No record information from the Washington County survey was used to reestablish the 1/4 corner position.

The center 1/4 section corner of section 27, also established by Dean D. Holliday, R.L.S. No. 4666 for Washington County in 1978, was found to be out of position, due to the discrepancy with the 1/4 section corner of sections 27 and 34, and was not utilized as the C 1/4 section corner position.

A portion of the south boundary and subdivisional lines were resurveyed by F. Campbell and J. Ballard of Ballard and Campbell Engineering of Hurricane Utah.

The directions of lines were determined by references to true meridians established on line by hour angle observations of the sun and Polaris. The lines were carried forward by sustained angulations, being supplemented by other observations taken throughout the progress of the survey. Distances were determined by electronic measurement.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. The retracement data were thoroughly verified and only the true line notes are given herein.

The geographic position of Mile Post No. 58 on the Utah - Arizona State boundary as determined by Belle A. Craig, Cadastral Surveyor for the Arizona State office of the Bureau of Land Management, during a dependent resurvey of a portion of the Utah - Arizona State boundary line, from August 16, 1993 to October 5, 1993 as determined by the technique of static differential positioning is as follows:

Latitude $37^{\circ} 00' 00.62''$ N. Longitude $112^{\circ} 59' 54.92''$ W.
N.A.D. 1927

The mean magnetic declination as projected from the U.S. Geological Survey "Magnetic Declination Map of 1990" is: $13 \frac{1}{2}^{\circ}$ East.

Retracement of the Utah and Arizona State Line
from Mile Post 58 to Mile Post 60.19
T. 43 S., R. 10 W., Salt Lake Meridian, Utah

RETRACEMENT OF THE UTAH AND ARIZONA STATE LINE
FROM MILE POST 58 TO MILE POST 60.19,
T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Reestablishment of the Survey Executed by
H.B. Carpenter in 1901, and the Resurvey
by B.E. Craig in 1993.

Beginning at Mile Post 58 on the Utah - Arizona State boundary, monumented with an iron post, 2 ins. diam., firmly set, projecting 2 ins. above ground with brass cap marked, with raised letters, UTAH on the N. and ARIZ. on the S., 58M stamped in the center, and 1993.

from which

A stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, bears S. $87^{\circ}53'$ E., 36.6 ft. dist., with cap marked RM 58M T42N R7W ARIZ 36.6 ft. TO COR 1993 and an arrow pointing to the corner.

A stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, bears N. $8^{\circ}20'$ W., 66.8 ft. dist., with cap marked RM 58M T43S R10W UTAH 66.8 ft. TO COR 1993 and an arrow pointing to the corner.

Corner is located in barbed wire fence extending east and west, from which the center line of Uzona Ave., extending east and west, a graded dirt road, 60 lks. wide, bears south, 0.45 chs. dist.

N. $89^{\circ}52.6'$ E., on the 59th mile.

- 2.38** Center line of Utah State road No. 59, and Arizona State road No 389, bears N. $32^{\circ}34'$ W. and S. $32^{\circ}34'$ E.
- 4.524** Intersect point for the closing corner of sections 32 and 33, on the south boundary of T. 43 S., R 10 W., Salt Lake Meridian, Utah.
- From which the true monumented closing corner of sections 32 and 33, T. 43 S., R. 10 W., bears S. $0^{\circ}05.3'$ E., 0.006 chs. dist., hereinafter described.
- 44.524** Point for the 1/4 section corner of section 33 only, on the south boundary of section 33, T. 43 S., R. 10 W.; not monumented.
- 80.563** Mile Post 59, monumented with a aluminum rod, 5/8 in. diam., found 18 ins. below the surface of Uzona Ave., with 2 1/2 in. diam., aluminum cap marked 59M T43S R10W S33 UTAH ARIZ S31 T42N R6W 1993.

RETRACEMENT OF THE UTAH AND ARIZONA STATE LINE
FROM MILE POST 58 TO MILE POST 60.19,
T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

from which

A stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, bears N. $55^{\circ}55'$ E., 60.1 ft. dist., with cap marked RM 59M T43S R10W UTAH 60.1 ft. TO COR 1993 and an arrow pointing to the corner.

A stainless steel post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, bears S. $45^{\circ}20'$ E., 45.4 ft. dist., with cap marked RM 59M T42N R6W ARIZ 45.4 ft. TO COR 1993 and an arrow pointing to the corner.

The corner falls 20 lks. N. of the S. edge of Uzona Ave., a graded road, 45 lks. wide, bears E and W.

N. $89^{\circ}52.6'$ E., on the 60th mile.

- 3.961** Point for the closing corner of sections 33 and 34, on the south boundary of T. 43 S., R. 10 W., Salt Lake Meridian, Utah, at proportionate distance, based on the official record of 1909 survey, hereinafter described.
- 31.380** Intersect point for the closing corner of sections 31 and 32, T. 42 N., R. 6 W., on the north boundary of T. 42 S., R. 6 W., Gila and Salt River Meridian, Arizona.
- From which the true monumented closing corner of sections 31 and 32, T. 42 S., R. 6 W., bears North, 0.02 chs. dist., monumented with an iron post, 2 ins. diam., firmly set flush with the ground, with brass cap marked AM CC S31 S32 T42N R6W 1916 1993.
- From which
- The northeast corner of house, bears S. 8° W., 0.044 chs. dist., and a rock retaining wall extending E and W, 2. ft. wide, 2 1/2 ft. high, bears South, 0.064 chs. dist.
- 43.882** Point for the 1/4 section corner of section 34 only, on the south boundary of section 34, T. 43 S., R. 10 W.; not monumented.
- 71.438** The 1/4 section corner of section 32 only, on the north boundary of T. 42 N., R. 6 W., Gila and Salt River Meridian, Arizona, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap marked UTAH 1/4 S32 T42N R6W 1993.

RETRACEMENT OF THE UTAH AND ARIZONA STATE LINE
FROM MILE POST 58 TO MILE POST 60.19,
T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

from which

A stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, bears N. $54^{\circ}30'$ E., 28.5 ft. dist., with cap marked RM T43S R6W 28.5 ft. TO COR 1993 and an arrow pointing to the corner.

A stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, bears S. 38° E., 23.0 ft. dist., with cap marked RM T42N R6W 23.0 ft. TO COR 1993 and an arrow pointing to the corner.

The corner falls 7 lks. S. of a E - W, 4 strand barbed wire fence.

83.803 Point for the closing corner of sections 34 and 35, on the south boundary of T. 43 S., R. 10 W., Salt Lake Meridian, Utah, at proportionate distance based on the record of Campbell Engineering, hereinafter described.

93.80 Trail road, 20 lks. wide, bears NE and SW.

94.05 Center of canal, 25 lks. wide, 3 ft. deep, drains SW.

95.276 Mile Post 60.19, monumented with stainless steel post, 2 1/2 ins. diam., firmly set in a mound of stone, with brass cap marked 60.19M T43S R10W S35 UTAH ARIZ T42N R6W S32 CPWA 1993.

from which

A juniper, 12 ins. diam., bears N. 74° E., 28 lks. dist., mkd. UTAH 60.19M BT, on partially healed blaze.
(1901 BT)

A pinon, 14 ins. diam., bears S. $64^{\circ}30'$ W., 23 lks. dist., mkd. UTAH 60.19M BT, on partially healed blaze.
(1901 BT)

A pinon, 10 ins. diam., bears S. 27° E., 77 lks. dist., mkd. ARIZ 60.19M BT. (1993 BT).

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 43 S., R. 10 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
R.E.L. Collier and R. Gentry in 1909

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the corner of sections 25, 26, 35, and 36, monumented with a sandstone 22x8x6 ins., firmly set, plainly marked 1 notch on the E. and 1 notch on the S. edges.

from which

A pinon, 10 ins. diam., bears S. 30° E., 55 lks. dist.,
mkd. T43S R10W S36 BT.

A pinon, 10 ins. diam., bears N. 25° W., 72 lks. dist.,
(record N. 28° 20' W., 34 lks.) mkd. T43S R10W S26 BT.

The NE bearing tree was found at record bearing and distance,
down and dead.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, set in a mound of stone with aluminum cap marked:

T43S R10W	
S26	S25
S35	S36
1994	

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

The corner falls on a gradual SW slope, 20 lks. E. of abrupt edge of broken sandstone ledges.

N. 0° 00.8' E., between sections 25 and 26.

On gradual to moderate westerly slope.

19.967 Point for the S 1/16 section corner of sections 25 and 26, not monumented.

39.934 The 1/4 section corner of sections 25 and 26, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap marked as described in the official record of the survey executed in 1909 by Collier and Gentry.

from which

A pinon, 8 ins. diam., bears S. 77° 20' E., 40 lks. dist.,
marked 1/4 S25 BT.

A juniper, 10 ins. diam., bears S. 11° 45' W., 23 lks. dist.,
marked 1/4 S26 BT.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Raise a mound of stone around the iron post, 4 ft. base to top of brass cap.

The corner falls, 15 lks. east of the top of a spur, on a slight easterly slope, in manzanetta undergrowth, with scattered pinon and juniper.

N. 0°09.2' W., beginning new measurement.

Descending ridge.

19.938 Point selected for the witness corner to the N 1/16 section corner of sections 25 and 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, set in a mound of stone 5 ft. base to top of aluminum cap marked:

T43S R10W
WC
N 1/16
S26 | S25
1994

The corner falls at base of sandstone ledges on steep westerly slope.

20.036 True point for the N 1/16 section corner of sections 25 and 26, falls on exposed sandstone ledges, unsuitable for permanent monumentation, not monumented.

39.12 North bank of drainage, approximately 2 1/2 chs. wide, 25 ft. deep, drains NW.

40.072 Point for the corner of sections 23, 24, 25, and 26, at proportionate distance. There is no remaining evidence of the position of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground over the top of a steel fence post, 5 1/2 ft. long driven 5 ft. into sandy ground, with aluminum cap marked:

T43S R10W
S23 | S24
S26 | S25
1994

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the corner.

The corner falls on flat sandy ground, 8 lks. dist., S. of a 4 strand barbed wire fence, bears E - W.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the 1/4 section corner of sections 24 and 25, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above a mound of stone, with brass cap marked as described in the official record of the survey executed in 1909 by Collier and Gentry.

from which

A pinon, 16 ins. diam., bears N. $0^{\circ}40'$ E., 32 lks. dist.,
marked 1/4 S24 BT.

The SE BT was found at record bearing and dist., down and dead.

The corner falls on gradual easterly slope.

S. $89^{\circ}55.2'$ W., between sections 24 and 25.

Ascending on gradual easterly slope.

15.60 Top of ridge and beginning of steep decent.

19.969 Point for the W 1/16 section corner of sections 24 and 25.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, set in a mound of stone, 5 ft. base, to top of aluminum cap marked:

T43S R10W
W 1/16 $\frac{S24}{S25}$
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

The corner falls on gradual westerly slope on broken ground, 18 lks. W. of a trail, 4 lks. wide, bears NE and SW

20.45 Top of vertical ledge, 20 ft. high, bears N - S.

39.938 The corner of sections 23, 24, 25, and 26.

N. $0^{\circ}01.7'$ W., between sections 23 and 24.

Through bottom lands of Short Creek.

40.071 The 1/4 section corner of sections 23 and 24, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, with brass cap marked as described in the official record of the survey executed in 1909 by Collier and Gentry.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

from which

A pinon, 6 ins. diam., bears S. $41^{\circ}40'$ E., 14 lks. dist.,
with marks 4 BT, visible on partially cut out blaze.

The NW bearing tree was found at record bearing and
dist., down and dead.

And a new tree.

A juniper 10 ins. diam., bears N. 30° W., 75 lks. dist.,
marked 1/4 S23 BT.

The corner falls on a moderate E. slope.

From the corner of sections 25, 26, 35, and 36.

N. $89^{\circ}56.5'$ W., between sections 26 and 35.

Descending on steep westerly slope.

20.071 Point for the E 1/16 section corner of sections 26 and 35.

Set a 3/4 in. rebar, 12 ins. long, drilled 9 ins. into a sandstone boulder, 8 1/2 X 7 X
11 ft. above ground, in crack of boulder, 2 ft. below the top, with 3 1/4 in. diam.,
aluminum cap marked:

	T43S R10W
E 1/16	<u>S26</u>
	S35
	1994

40.142 The 1/4 section corner of sections 26 and 35, monumented with an iron post, 1 in.
diam., firmly set, projecting 5 ins. above ground, with brass cap marked as described
in the official record of the survey executed in 1909 by Collier and Gentry.

from which

A oak, 10 ins. diam., bears N. $21^{\circ}10'$ E., 69 lks. dist.,
with scribe marks visible through partially healed
blaze.

The SE bearing tree has been cut down.

And a new tree.

A juniper 6 ins. diam., bears S. 63° E., 35 1/2 lks. dist.,
marked X BT.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Raise a mound of stone, 2 1/2 base by 1 ft. high, N. of the corner.

The corner falls on flat bench land, in scattered juniper.

From the corner of sections 26, 27, 34, and 35, monumented with sandstone 20x14x6 ins., firmly set, plainly marked with 2 notches on the E. and 1 notch on the S. edges.

from which

A juniper, 16 ins. diam., bears N. 27° E., 57 lks. dist., marked
T43S R10W S26 BT. (record N. 52° E., 35 lks. dist.)

A juniper, 12 ins. diam., bears S. 45° 30' E., 53 1/2 lks. dist.,
with scribe marks BT visible. (record 19 lks. dist.)

A juniper, 26 ins. diam., bears S. 22° W., 54 1/2 lks. dist.,
marked T43S R10W S34 BT. (record S. 30° W., 25 lks. dist.)

A juniper, 34 ins. diam., tied 8 in. diam., branch, bears N. 55° 30' W.,
92 lks. dist., marked T43S R10W S27 BT. (record N. 61° 30' W.,
62 lks. dist.)

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with
aluminum cap marked:

T43S R10W	
S27	S26
S34	S35
1994	

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel
post.

Raise a mound of stone, 5 ft. base, 2 ft. high, W. of the corner.

The corner falls on a moderate easterly rocky slope in scattered juniper.

S. 0° 03.3' E., between sections 34 and 35

Over easterly slope and through residential area.

35.25

Record distance for the witness 1/4 section corner of sections 34 and 35, falls on the
southerly side of a graded dirt road, on a curve in a area of disturbance. There is
no remaining evidence of the original witness corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

35.45

Barbed wire fence along the westerly bank of Short Creek, bears N. 50° E. and S. 50° W.

36.179

Point selected for the witness 1/4 section corner to the corner of sections 34 and 35.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground over the top of a steel fence post, 5 1/2 ft long driven 5 ft. into sandy ground, with aluminum cap marked:

T43S R10W
WC
1/4
S34 | S35
1994

The corner falls on a narrow finger of sand, 12 lks. wide, projecting S. 40° W., into Short Creek.

39.999

Point for the 1/4 section corner of sections 34 and 35, at proportionate distance, falls within Short Creek.

58.898

Point for the closing corner of sections 34 and 35, at intersection with the Utah and Arizona State line. There is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T43S R10W
CC
S34 | S35
T42N R6W
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

Raise a mound of stone, 2 ft. base, 1 ft. high, N. of the corner.

The corner falls on flat ground, 3 1/2 lks. S. of a 4 strand barbed wire fence, bears E - W., and 4 1/2 lks., N. of the north edge of dirt road, 14 lks. wide, bears E - W.

From this corner point, the 60.19 mile post on the Utah - Arizona State line, bears N. 89° 52.6' E., 11.473 chs. dist., hereinbefore described.

From the corner of sections 26, 27, 34, and 35.

N. 0° 04.2' E., between sections 26 and 27.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Over northeasterly slope of ridge into bottom land.

20.018 Point for the S 1/16 section corner of sections 26 and 27; not monumented.

40.036 The 1/4 section corner of sections 26 and 27, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, 4 ft. base, 4 ft. high, with brass cap marked as described in the official record of the survey executed in 1909 by Collier and Gentry.

from which

A juniper, 10 ins. diam., bears S. 69° E., 43 lks. dist.,
marked 1/4 S26 BT. (record S. $74^{\circ}20'$ E., 42 lks. dist.)

A juniper, 15 ins. diam., bears S. 61° W., 43 1/2 lks. dist.,
marked 1/4 S27 BT. (record S. $66^{\circ}15'$ W., 41 lks. dist.)

The corner falls on a gradual SW slope on rocky ground.

N. $0^{\circ}04.6'$ E., beginning new measurement.

19.939 Point for the N 1/16 section corner of sections 26 and 27; not monumented.

39.878 The corner of sections 22, 23, 26, and 27, monumented with a Washington County galvanized post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above a mound of stone, with brass cap marked T43S R10W SLB-M 22 23 26 27 1979.

This corner is accepted as a careful and faithful perpetuation of the position of the original corner.

from which

A pinon, 12 ins. diam., bears S. 58° E., 72 lks. dist., marked
T43S R10W S26 BT (record S. $57^{\circ}30'$ E., 75 lks. dist.)

A pinon, 12 ins. diam., bears S. 88° W., 60 lks. dist.,
marked T43S R10W (record S. $84^{\circ}30'$ W.)

A juniper, 22 ins. diam., bears N. 20° W., 38 lks. dist.,
marked T43S R10W S22 BT (record N. $25^{\circ}30'$ W.)

The NE bearing tree was found down and dead.

The corner falls on a steep SE slope, near base of vertical ledges.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the corner of sections 23, 24, 25, and 26.

N. $89^{\circ}56.5'$ W., between sections 23 and 26.

Over bottom lands of Short Creek.

19.969 Point for the E 1/16 section corner of sections 23 and 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T43S R10W
E 1/16	<u>S23</u>
	S26
	1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

Raise a mound of stone, 4 ft. base, 2 ft. high, N. of the corner.

The corner falls on flat ground, 7 lks. N. of a 4 strand barbed wire fence, bears E - W., and 3 lks., S. of the south edge of an A.T.V. trail, 6 lks. wide, bears E - W.

39.938 The 1/4 section corner of sections 23 and 26, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground set in a collar of stone, with brass cap marked as described in the official record of the survey executed in 1909 by Collier and Gentry.

The corner falls on flat sandy ground, in sagebrush undergrowth, 1 1/2 lks. S. of fence corner of E - W - N projecting fences.

S. $89^{\circ}54.2'$ W., beginning new measurement.

19.976 Point for the W 1/16 section corner of sections 23 and 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T43S R10W
W 1/16	<u>S23</u>
	S26
	1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

Raise a mound of stone, 4 ft. base, 3 ft. high, N. of the corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

The corner falls on a gradual SW slope.

21.50 Drainage, 30 lks. wide, bears N. 70 W., and S. 15° E.

39.952 The corner of sections 22, 23, 26, and 27.

From the corner of sections 27, 28, 33, and 34, monumented with a sandstone, 28x12x8 ins., firmly set, plainly marked with 1 notch on the S. and 3 notches on the E. edges, with a mound of stone W. of the corner.

from which

A juniper, 10 ins. diam., bears S. 27° 55' E., 1.81 chs. dist.,
marked T43S R10W S34 BT.

A juniper, 15 ins. diam., bears S. 41° W., 19 lks. dist.,
with faint scribe marks visible (record 17 lks. dist.)

A juniper, 10 ins. diam., bears N. 83° 20' W., 1.79 chs.
dist., marked T43S R10W S28 BT.

The NE bearing tree was found down and dead, at record bearing and dist.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with
aluminum cap marked:

T43S R10W	
S28	S27
S33	S34
1994	

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel
post.

Raise a mound of stone, 4 ft. base, 2 ft. high, W. of the corner.

The corner falls on a steep SW slope.

S. 0° 07.6' E., between sections 33 and 34.

Descending on steep southerly slope.

20.108 Point for the N 1/16 section corner of sections 33 and 34; not monumented.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS
40.216

Point for the 1/4 section corner of sections 33 and 34, at proportionate distance; there is no remaining evidence of the position of the original corner.

Set a rebar 3/4 in. diam., 24 ins. long, 4 ins. below the surface of Utah Avenue, with 3 1/4 ins. diam., aluminum cap marked:

T43S R10W
1/4
S33 | S34
1994

from which

An aluminum post, 30 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 42°57'E., 52.6 ft. dist., with cap marked T43S R10W RM S34 52.6 FT. 1994 and an arrow pointing to the corner.

An aluminum post, 30 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 48°28.5'W., 55.4 ft. dist., with cap marked T43S R10W RM S33 55.4 FT. 1994 and an arrow pointing to the corner.

Deposit a magnet, 1 x 1 x 1 7/8 ins. long beneath each of the aluminum posts.

The corner falls in the center of Utah Ave., a paved road, 36 lks. wide, bears E - W.

From this corner point, a bolt, 1 in. diam., set flush with the road surface, bears N. 5° W., 0.84 ft. dist., as set by Ballard and Campbell Engineering for the 1/4 section corner position, using improper methods, not utilized in the course of this survey.

58.926

Point for the closing corner of sections 33 and 34, at intersection with the Utah and Arizona State line. No remaining evidence of the original sandstone, 20x8x6 ins., was found.

This point was reestablished by Ballard and Campbell Engineering during the course of a survey, by proportionate distance. The original bearing tree was not searched for during this survey. This point is utilized as the closing corner position, with a new tie made to the original bearing tree. No remaining evidence of the monument set by Ballard and Campbell was found.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 1 ft. below the surface of Lauritzen street, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T43S R10W
CC
S33 | S34
T42N R6W
1994

from which the original bearing tree, with a new tie.

A juniper, 30 ins. diam., bears N. $73^{\circ}02'$ W., 2.50 chs. dist., (record,
N. $76^{\circ}15'$ W., 2.49 chs.) marked CC T43S R10W S33 BT, visible on
partially healed blaze.

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel
post.

The corner falls 20 lks. W., of the E. edge of Laurtizen Street, a dirt road, 44 lks.
wide, bears N - S, and 44 lks. W. of a 4 strand barbed wire fence, bears N - S.

From this corner point, the 59 mile post on the Utah - Arizona State line, bears
S. $89^{\circ}52.6'$ W., 3.961 chs. dist., hereinbefore described.

From the corner of sections 26, 27, 34, and 35.

S. $89^{\circ}53.4'$ W., between sections 27 and 34.

20.011 Point for the E 1/16 section corner of sections 27 and 34.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with
aluminum cap marked:

T43S R10W
E 1/16 $\frac{S27}{S34}$
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel
post.

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the corner.

The corner falls on a gradual N. slope, 65 lks. S., of the center of a trail road, 12
lks. wide, bears N. 82° E.

40.022 The corner for the 1/4 section corner of sections 27 and 34, is determined at record
bearing and distance from the remains of the original bearing trees.

A juniper 7 ins. diam., bears N. 67° E., 36 lks. dist., marked
1/4 S 27 BT.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

A pinon 10 ins. diam., laying dead on top of the ground, with no stump or stump hole to determine its original position. A tie to the trees approximate original location bears S. 69° W., 1.42 chs. dist.

There was no remaining evidence of the original iron post, set by Collier and Gentry in 1909, or the galvanized post set by Washington County in 1979. A steel fence post was found, 1 lk. W. of this corner position.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

T43S R10W
1/4 $\frac{S27}{S34}$
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

Raise a mound of stone, 4 ft. base, 3 ft. high N. of the corner.

The corner falls on a steep rocky SW slope.

S. 89° 54.5' W., beginning new measurement.

19.942 Point for the W 1/16 section corner of sections 27 and 34.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, set in a mound of stone, 4 ft. base, to top of aluminum cap marked:

T43S R10W
W 1/16 $\frac{S27}{S34}$
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

The corner falls on flat rocky ground, 3 lks. S., of the south edge of a drainage 10 feet deep, drains SE.

39.884 The corner of sections 27, 28, 33, and 34.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. $0^{\circ}03.0'$ E., between sections 27 and 28.

Over mountainous terrain.

39.904

The 1/4 section corner of sections 27 and 28, monumented with a Washington County galvanized post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with steel fence post 1 lk. S. of the corner, with brass cap marked T43S R10W 1/4 S28 S27 1979. This corner is accepted as a careful and faithful reestablishment of the original corner. There was no remaining evidence of the original corner.

The corner falls on a steep NW slope.

N. $0^{\circ}06.4'$ E., beginning new measurement.

39.911

The corner of sections 21, 22, 27, and 28, monumented with a sandstone, 20x10x8 ins., firmly set, plainly marked with 3 notches on the E., and 2 notches on the S. edges.

from which

A juniper, 21 ins. diam., bears N. $66^{\circ}45'$ W., 20 lks. dist.,
marked T43S R10W S21 BT, visible on partially healed blaze.

The remaining original bearing trees, were found at approximate record bearing and dist., all down and dead.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T43S R10W	
S21	S22
S28	S27
1994	

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

Raise a mound of stone, 5 ft. base, 2 ft. high W. of the corner.

The corner falls on the northerly side of a drainage, drains SW., on a moderate SW slope.

From the corner of sections 22, 23, 26, and 27.

S. $89^{\circ}48.9'$ W., between sections 22 and 27.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Over mountainous terrain.

19.973 Point for the E 1/16 section corner of sections 22 and 27; not monumented.

39.946 The 1/4 section corner of sections 22 and 27, monumented with a Washington County galvanized post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground in a small mound of stone, with a steel fence post set 2 lks. NW of the corner. This corner is accepted as a careful and faithful perpetuation of the position of the original corner.

The original corner, an iron post, 3 ft. long, 1 in. diam., was found near the Washington County post, laying loose, 3 ins. below ground. I was unable to determine the true position of this corner, with no remaining evidence of the original bearing trees. I placed the iron post inside the Washington County galvanized post.

The corner falls on flat sandy ground at edge of large cactus patch, 1 ch. E., of the east bank of a drainage, 35 ft. deep, drains SE.

S. 89° 50.3' W., beginning new measurement.

39.940 The corner of sections 21, 22, 27, and 28.

From the corner of sections 28, 29, 32, and 33, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap marked as described in the official record of the survey executed by Collier and Gentry in 1909.

The corner falls on the N edge of a dirt road, 24 lks. wide, bears E - W, in an old railed area. The original NE and SW bearing trees, were found railed out, down and dead. There was no remaining evidence of the SE and NW trees.

Raise a mound of stone around the iron post.

S. 0° 05.3' E., between sections 32 and 33.

Over flat sandy ground.

20.016 Point for the N 1/16 section corner of sections 32 and 33; not monumented.

40.032 Point for the 1/4 section corner of sections 32 and 33, as determined from record data taken from the plat of survey by Ballard and Campbell Engineering, in a resurvey of the line between sections 32 and 33, during which time the original 1/4 section corner was tied. There is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a rebar 3/4 in. diam., 24 ins. long, 4 ins. below the surface of Utah Avenue, with 3 1/4 ins. diam., aluminum cap marked:

T43S R10W
1/4
S32 | S33
1994

from which

A 3/8 in. bolt, 4 ins. long, with 1 in. diam., washer, set in a power pole facing the corner, bears S. $31^{\circ}51.7' W.$, 55.60 ft. dist., with washer marked RM 1994

A 3/8 in. bolt, 4 ins. long, with 1 in. diam., washer, set in a power pole facing the corner, bears N. $33^{\circ}15.7' W.$, 53.30 ft. dist., with washer marked RM 1994.

The corner falls 3.5 lks. S. of the center of Utah Avenue, a paved road, 36 lks. wide, bears E - W.

58.935 True point for the closing corner of sections 32 and 33, at intersection with Utah and Arizona State line, monumented with a rebar, 5/8 in. diam., firmly set with yellow plastic cap marked B & C Engineering LS 4490.

From this corner point, the original closing corner, monumented with an iron post, 2 ins. diam., firmly set, 1 ft. below ground and a steel fence post alongside, with brass cap marked as described in the official record of the survey executed in 1909 by Collier and Gentry, bears S. $0^{\circ}05.3' E.$, 0.006 chs. dist.

Add the marks AM 1994 to the brass cap.

The corner point falls on flat ground on the S. side of Uzona Ave., a graded dirt road, 60 lks. wide, bears E - W.

From this corner point, the 58 mile post on the Utah - Arizona State line, bears S. $89^{\circ}52.6' W.$, 4.524 chs. dist., hereinbefore described.

From the corner of sections 27, 28, 33, and 34.

S. $89^{\circ}52.2' W.$, between sections 28 and 33.

Over broken mountainous slope.

40.007 The 1/4 section corner of sections 28 and 33, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, with brass cap marked as described in the official record of the survey executed in 1909 by Collier and Gentry.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

from which the original bearing trees

A pinon, 16 ins. diam., bears S. 42° E., 7 lks. dist., marked
1/4 S33 BT.

A pinon, 8 ins. diam., bears N. $85^{\circ}45'$ W., 58 lks. dist., marked
1/4 S28 BT.

The corner falls on steep SW slope.

S. $89^{\circ}53.8'$ W., beginning new measurement.

19.971 Point for the W 1/16 section corner of sections 28 and 33.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with
aluminum cap marked:

	T43S R10W
W 1/16	<u>S28</u>
	S33
	1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel
post.

Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, N. of the corner.

The corner falls on flat sandy ground, 17 lks. north of the center of a trail road, 18
lks. wide, bears E - W.

39.942 The corner of sections 28, 29, 32, and 33.

N. $0^{\circ}07.2'$ W., between sections 28 and 29.

Over gradual slope.

19.28 Center of dirt trail road, 15, lks. wide, bears E - W.

19.993 Point for the S 1/16 section corner of sections 28 and 29.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, set in a
mound of stone, 5 ft. base, to top of aluminum cap marked:

	T43S R10W
	S 1/16
	S29 S28
	1994

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

The corner falls in the bottom of a drainage, 4 lks. wide, course S. 30° W.

39.986 The 1/4 section corner of sections 28 and 29, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, with brass cap marked as described in the official record of the survey by Collier and Gentry in 1909.

from which the original bearing trees

A juniper, 16 ins. diam., bears S. 35° E., 35 lks. dist., marked
1/4 S28 BT.

A pinon, 16 ins. diam., bears N. 74° W., 28 lks. dist.,
(record N. 70°30' W., 27 lks. dist.) marked 1/4 S29 BT.

N. 0° 17.2' W., beginning new measurement.

32.669 The witness corner to the corner of sections 20, 21, 28, and 29, monumented with a sandstone boulder, 12x10x8 ft. above ground, with another sandstone boulder, 6x6x6 ft. on top, with illegible marks on the point of the boulder and a small mound of stone at the base of the boulder.

from which the original bearing tree

A juniper, 14 ins. diam., bears S. 25° 44' E., 3.665 chs. dist.,
(record S. 29° E., 3.78 chs. dist.) marked WC T43S R10W S28 BT.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, set in a mound of stone 5 ft. base to top of aluminum cap marked:

T43S R10W
WC

S29 | S28
1994

from which

A sandstone boulder 7x7x7 ft. above ground, marked X BO, bears
N. 65° E., 13.5 lks. dist.

The corner falls at the base of the boulder on a steep south slope.

33.02 Base of vertical sandstone face.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

39.869

Point for the corner of sections 20, 21, 28, and 29, at record dist., extending the line through the witness corner, falls in sandstone ledges. not monumented.

From the corner of sections 21, 22, 27, and 28.

S. $89^{\circ}54.7'$ W., between sections 21 and 28.

Over broken mountainous terrain.

24.25

Record distance for the original witness corner to the 1/4 section corner of sections 21 and 28. There is no remaining evidence of the witness corner.

40.163

Point for the 1/4 section corner of sections 21 and 28, at proportionate distance.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, set in a mound of stone, 4 ft. base, to top of aluminum cap marked:

T43S R10W
1/4 S21
 S28
 1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

from which

A juniper, 32 ins. diam., bears S. 53° E., 59 lks. dist., marked
1/4 S28 BT.

A pinon, 10 ins. diam., bears N. 8° W., 22 lks. dist., marked
1/4 S21 BT.

The corner falls on a steep easterly slope.

80.326

True point for the corner of sections 20, 21, 28, and 29.

From the corner of sections 29, 30, 31, and 32, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground in a collar of stone, with brass cap marked as described in the official record of the survey by Collier and Gentry in 1909.

N. $0^{\circ}06.3'$ W., between sections 29 and 30.

Over flat ground.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

- 0.115** State Road No. 59, right of way fence.
- 0.99** Center line of State Road No. 59, bears N 58° 17' W.
- 20.017** Point for the S 1/16 section corner of sections 29 and 30.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:
- T43S R10W
S 1/16
S30 | S29
1994
- Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.
- Raise a mound of stone, 1 1/2 ft. by 1 ft. high, W. of the corner.
- Set a 6 ft. steel fence post, alongside.
- The corner falls in a N - S, 4 strand barbed wire fence on flat ground, in sagebrush undergrowth and scattered juniper.
- 40.034** The 1/4 section corner of sections 29 and 30, monumented with an iron post, 1 in. diam., firmly set, 1 ft. below ground and a steel fence post E. of the corner, with brass cap marked as described in the official record of the survey executed in 1909 by Collier and Gentry.
- from which
- A juniper, 12 ins. diam., bears S. 69° 50' W., 34 lks. dist., marked
1/4 S30 BT. (record 32 lks.)
- There is no remaining evidence of the original NE bearing tree.
- Reset the post, to project 2 ins. above ground and raise a mound of stone, 3 ft. base, 2 ft. high W. of the corner.
- The corner falls in a N - S, 4 strand barbed wire fence.
- _____
- N. 0° 05.6' W., beginning new measurement.
- 40.013** The corner of sections 19, 20, 29, and 30, monumented with a rusted off 2 in. diam., iron post, 2 ft. long, with top part of post and brass cap not found.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

from which the original bearing trees

A pinon, 16 ins. diam., bears N. $31^{\circ}45'$ E., 47 lks. dist., marked
T43S R10W S19 BT.

A pinon, 16 ins. diam., bears S. $38^{\circ}50'$ E., 104 lks. dist., marked
T43S R10W S29 BT.

A pinon, 16 ins. diam., bears S. $19^{\circ}45'$ W., 26 lks. dist., marked
T43S R10W S30 BT.

A juniper, 16 ins. diam., bears N. $32^{\circ}40'$ W., 47 lks. dist., marked
T43S R10W S19 BT.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with
aluminum cap marked:

T43S R10W	
S19	S20
S30	S29
1994	

Deposit the remainder of the original iron post inside the aluminum post.

Raise a mound of stone, 5 ft. by 3 ft. high, W. of the corner.

The corner falls on a gradual easterly slope.

N. $89^{\circ}50.2'$ E., between sections 20 and 29.

Over mountainous terrain.

16.860 Found a 1 in. diam., iron post, firmly set, projecting 18 ins. above ground, with
brass cap marked WC 1/4 S20 S29 1909.

There is no official record in the 1909 survey by Collier and Gentry of this corner
being set.

Raise a mound around the iron post, 5 ft. base to top of brass cap.

16.890 The point to the 1/4 section corner of sections 20 and 29, at the foot of vertical
sandstone ledge, with the face of the sandstone ledge marked X S20 WC S29
(record X WP 1/4 S20 S29).

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

from which the original bearing tree.

A juniper, 18 ins. diam., bears S. $67^{\circ}40'$ W., 2.05 chs. dist.,
marked WC 1/4 S29 BT. (record S. 70° W., 2.02 chs. dist.).

S $89^{\circ}58.0'$ E., beginning new measurement.

23.084 Point for the 1/4 section corner of sections 20 and 29, at proportionate distance.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with
aluminum cap marked:

T43S R10W
1/4 $\frac{S20}{S29}$
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel
post.

The corner falls on a steep SE slope in scattered pinon and juniper.

This corner was not set in the original survey. Proportionate measurement is based
upon an 80 chain mile, between sections 20 and 29.

62.970 True point for the corner of sections 20, 21, 28, and 29.

The Subdivision of Section 26,
T. 43 S., R. 10 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 26 and 35.

N. $0^{\circ}04.2'$ E., on the N - S center line of section 26.

19.988 Point for the center S 1/16 section corner of section 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins in the ground to
bedrock, set in a mound of stone, 5 ft. base, to top of aluminum cap marked:

T43S R10W
C
S 1/16 | S26
C
1994

THE SUBDIVISION OF SECTION 26,
T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

The corner falls on a gradual easterly slope in sandy soil and rocky outcrops in scattered pinon and juniper.

38.07 Westerly edge of canal, 36 lks. wide, drains S. 47° W.

38.55 Top of sandy bank, 20 ft. high, bears S 47° W..

39.976 Point for the center 1/4 section corner, at intersection with the E - W center line of section 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

T43S R10W
C 1/4
S26
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

Raise a mound of stone, 3 1/2 ft. by 2 ft. high, W. of the corner.

The corner falls on flat sandy ground, on the W. edge of an A.T.V. trail, 10 lks. wide, bears N 20° E.

59.990 Point for the center N 1/16 section corner of section 26; not monumented.

80.004 The 1/4 section corner of sections 23 and 26.

From the 1/4 section corner of sections 25 and 26.

N. 89° 52.8' W., on the E - W center line of section 26.

20.049 Point for the center E 1/16 section corner of section 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T43S R10W
C $\frac{E\ 1/16}{S26}$ C
1994

THE SUBDIVISION OF SECTION 26,
T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

Raise a mound of stone, 4 ft. base, 3 ft. high N., of the corner.

The corner falls on a steep E. slope.

38.00 Westerly edge of canal, 36 lks. wide, drains S. 47° W.

38.70 Top of sandy bank, 20 ft. high, bears S 47° W.

40.098 The center 1/4 section corner of section 26.

59.41 Base of vertical ledges, 25 ft. high, bears NE and SW.

60.078 Point for the center W 1/16 section corner of section 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

$$\begin{array}{c} \text{T43S R10W} \\ \text{C} \frac{\text{W 1/16}}{\text{S26}} \text{C} \\ 1994 \end{array}$$

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high N., of the corner.

The corner falls on a steep SW slope near the base of a ring of ledges, 25 ft. high, bears NE and SW.

72.40 Top of ridge, bears NW and SE.

80.058 The 1/4 section corner of sections 26 and 27.

From the center E 1/16 section corner of section 26.

N. 0°02.5' W., on the N - S center line of the NE 1/4 of section 26.

20.025 Point for the NE 1/16 section corner at intersection with the E - W center line of the NE 1/4 of section 26.

THE SUBDIVISION OF SECTION 26,
T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over the top of a steel fence post, 5 1/2 ft. long driven 5 ft. into sandy ground, with aluminum cap marked:

T43S R10W
NE 1/16
S26
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high W., of the corner.

The corner falls on level sandy ground, 70 lks. N. and 93 lks. W. of the bottom of a drainage, 16 lks. wide at the bottom, drains SW.

40.050 The E 1/16 section corner of sections 23 and 26.

From the true point for the N 1/16 section corner of sections 25 and 26.

N. 89° 54.7' W., on the E - W center line of the NE 1/4 of section 26.

20.009 The NE 1/16 section corner of section 26.

40.018 Point for the center N 1/16 section corner of section 26.

From the E 1/16 section corner of sections 26 and 35.

N. 0° 02.5' E., on the N - S center line of the SE 1/4 of section 26.

19.978 Point for the SE 1/16 section corner at intersection with the E - W center line of the SE 1/4 of section 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T43S R10W
SE 1/16
S26
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

Raise a mound of stone, 2 ft. base, 1 ft. high W., of the corner.

THE SUBDIVISION OF SECTION 26,
T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

The corner falls on a gradual westerly slope on sandy ground, in scattered pinon and juniper.

39.956 The center E 1/16 section corner of section 26.

From the point for the S 1/16 section corner of sections 25 and 26.

N. $89^{\circ}54.7'$ W., on the E - W center line of the SE 1/4 of section 26.

20.060 The SE 1/16 section corner of section 26.

40.120 The center S 1/16 section corner of section 26.

From the center W 1/16 section corner of section 26.

N. $0^{\circ}04.4'$ E., on the N - S center line of the NW 1/4 of section 26.

39.953 The W 1/16 section corner of sections 23 and 26.

The Subdivision of Section 27,
T. 43 S., R. 10 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 27 and 34.

N. $0^{\circ}07.4'$ E., on the N - S center line of section 27.

19.988 Point for the center S 1/16 section corner of section 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, set in a mound of stone, 4 ft. base, to top of aluminum cap marked:

T43S R10W
C
S 1/16 | S27
C
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

The corner falls on a steep NE slope at the base of a boulder.

38.00 Top of finger ridge.

THE SUBDIVISION OF SECTION 27,
T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS**39.976**

Point for the center 1/4 section corner, at intersection with the E - W center line of section 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T43S R10W
C 1/4
S27
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

Raise a mound of stone, 4 ft. by 2 ft. high, W. of the corner.

The corner falls on flat top of a finger ridge.

From the corner, a Washington County galvanized post, 2 1/2 ins. diam., firmly set, projecting 14 ins. above ground, with steel fence post set 2 lks. S., bears N. 89° 16' E., 8 lks. dist., with brass cap marked WASHINGTON COUNTY SURVEY T43S R10W SLB - M C1/4 S27 1979 and a cross. This corner is not accepted or utilized during the course of this survey. (see note page 2 of these notes.)

40.60

Top edge of finger ridge, bears E - W, begin decent.

49.948

Point for the C-S-N 1/64 section corner of section 27; not monumented.

59.920

Point for the center N 1/16 section corner of section 27; not monumented.

79.864

The 1/4 section corner of sections 22 and 27.

From the 1/4 section corner of sections 26 and 27.

S. 89° 48.2' W., on the E - W center line of section 27.

19.951

Found a rebar, 5/8 in. diam., firmly set, with 1 in. diam. plastic cap marked B & C Eng. LS 4099.

19.992

Point for the center E 1/16 section corner of section 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 27,
T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T43S R10W
C $\frac{E\ 1/16}{S27}$ C
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high N., of the corner.

The corner falls, 35 lks. north of the N. edge of a graded dirt road, 35 lks. wide, bears N 65° W and S 65° E.

21.50 North edge of same dirt road, bears E - W.

22.491 Point for the center E-E-W-E 1/1024 section corner, on the E - W center line of section 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 1 lk. below the surface of a graded dirt road, 35 lks wide, bears E - W, with aluminum cap marked:

T43S R10W
C-E-E-W-E
1/1024
S27
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

Set a steel fence post, on the W. edge of the aluminum post.

The corner falls on the N. edge of the dirt road, 10 lks. S. of an E - W 4 strand barbed wire fence.

27.489 Point for the center W-E-W-E 1/1024 section corner on the E - W center line of section 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., flush with the surface of the ground.

T43S R10W
C-W-E-W-E
1/1024
S27
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

THE SUBDIVISION OF SECTION 27,
T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

- The corner falls 5 lks. north of the N. edge of a dirt road, 30 lks. wide, bears E - W.
- 29.988** Point for the center W-E 1/64 section corner on the E - W center line of section 27; not monumented.
- 38.35** Top of finger ridge, bears S. 30° W., and N. 34° W.
- 39.984** The center 1/4 section corner of section 27.
- 79.915** The 1/4 section corner of sections 27 and 28.
-
- From the center E 1/16 section corner of section 27.
N. 0°06.0' E., on the N - S center line of the NE 1/4 of section 27.
- 9.971** Point for the center S-NE 1/64 section corner of section 27; not monumented.
- 19.942** Point for the NE 1/16 section corner at intersection with the E - W center line of the NE 1/4 of section 27; not monumented.
- 39.884** Point for the E 1/16 section corner of sections 22 and 27.
-
- From the point for the N 1/16 section corner of sections 26 and 27.
S. 89°48.6' W., on the E - W center line of the NE 1/4 of section 27.
- 19.982** Point for the NE 1/16 section corner of section 27.
- 29.973** Point for the center W-NE 1/64 section corner; not monumented.
- 39.964** Point for the center N 1/16 section corner of section 27.
-
- From the point for the center W-E 1/64 section corner on the E - W center line of section 27.
N. 0°06.7' E., on the N - S center line of the SW 1/4, NE 1/4 of section 27.
- 9.971** Point for the SW-NE 1/64 section corner of section 27; not monumented.
- 19.942** Point for the center W-NE 1/64 section corner of section 27.
-

THE SUBDIVISION OF SECTION 27,
T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the point for the center S-NE 1/64 section corner of section 27.

S. $89^{\circ}48.4'$ W., on the E - W center line of the SW 1/4, NE 1/4, of section 27.

2.498 Point for the center E-E-SW-NE 1/1024 section corner of section 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T43S R10W
C-E-E-SW-NE
1/1024
S27
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

Raise a mound of stone, 4 ft. base, 3 ft. high W., of the corner.

The corner falls on a moderate SW slope.

From the corner, a rebar 5/8 in. diam., bears E., 3 lks. dist.

7.494 Point for the center W-E-SW-NE 1/1024 section corner of section 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T43S R10W
C-W-E-SW-NE
1/1024
S27
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

Raise a mound of stone, 4 ft. base, 3 ft. high W., of the corner.

The corner falls on a moderate SW slope.

From the corner, a rebar 5/8 in. diam., bears N. 88° E., 4 lks. dist.

9.992 Point for the SW-NE 1/64 section corner of section 27.

19.986 Point for the center S-N 1/64 section corner of section 27.

THE SUBDIVISION OF SECTION 27,
T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the center E-E-W-E 1/1024 section corner of section 27.

N. $0^{\circ}06.2'$ E., on the N-S center line of the E 1/2 of the SE 1/4 of the SW 1/4 of the NE 1/4 of section 27.

9.971 The center E-E-SW-NE 1/1024 section corner of section 27.

From the center W-E-SW-NE 1/1024 section corner of section 27.

N. $0^{\circ}06.5'$ E., on the N-S center line of the W 1/2 of the SE 1/4 of the SW 1/4 of the NE 1/4 of section 27.

9.971 The center W-E-SW-NE 1/1024 section corner of section 27.

From the E 1/16 section corner of sections 27 and 34.

N. $0^{\circ}05.8'$ E., on the N-S center line of the SE 1/4 of section 27.

19.35 Drainage, 17 lks. wide, bears N. 39° E.

20.003 Point for the SE 1/16 section corner, at intersection with the E-W center line of the SE 1/4 of section 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T43S R10W
SE 1/16 S27
1994

Deposit a magnet, 1x1x1 7/8 ins. in clear plastic case beneath the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

The corner falls on flat sandy ground, in scattered cedar and pinon.

From this corner, the W edge of a drainage, 20 ft. deep, with rim bearing N and S, bears E., 13 lks.

40.006 The center E 1/16 section corner of section 27.

From the point for the S 1/16 section corner of sections 26 and 27.

S. $89^{\circ}50.8'$ W., on the E-W center line of the SE 1/4 of section 27.

THE SUBDIVISION OF SECTION 27,
T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

20.001 The SE 1/16 section corner of section 27.

40.002 The center S 1/16 section corner of section 27.

The Subdivision of Section 28,
T. 43 S., R. 10 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 28 and 33.

N. 0°02.4' W., on the N - S center line of section 28.

19.977 Point for the center S 1/16 section corner of section 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins in the ground, with aluminum cap marked:

T43S R10W
C
S 1/16 | S28
C
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

Raise a mound of stone, 3 ft. base, 3 ft. high, W. of the corner.

The corner falls on flat ground, 40 lks. E. of a drainage, 25 lks. wide, drains S. 42° E.

36.70 Drainage, 20 lks. wide, drains S. 28° E.

39.954 Point for the center 1/4 section corner at intersection with the E - W center line of section 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T43S R10W
C 1/4
S28
1994

The corner falls on a moderate W. slope, 70 lks. E. of a drainage, 15 lks. wide, drains S. 45° W.

THE SUBDIVISION OF SECTION 28,
T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

79.844

The 1/4 section corner of sections 21 and 28.

From the 1/4 section corner of sections 27 and 28.

S. 89°56.5' W., on the E - W center line of section 28.

40.066

The C 1/4 section corner of section 28.

60.063

Point for the center W 1/16 section corner of section 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to bedrock, set in a mound of stone, 4 ft. base, to top of aluminum cap marked:

$$\begin{array}{c} \text{T43S R10W} \\ \text{C} \frac{\text{W 1/16}}{\text{S28}} \text{C} \\ 1994 \end{array}$$

from which

A pinon, 12 ins. diam., bears S. 41° E., 44 1/2 lks. dist.,
marked X BT.

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

The corner falls on the point of a ridge, 68 lks. N., and 20 lks. E., of top edge of rim of vertical ledge.

80.060

The 1/4 section corner of sections 28 and 29.

From the W 1/16 section corner of sections 28 and 33.

N. 0°04.8' W., on the N - S center line of the SW 1/4 of section 28.

18.30

Dirt road, 12 lks. wide, bears N 70° W.

19.985

Point for the SW 1/16 section corner, at intersection with the E - W center line of the SW 1/4 of section 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, set in a mound of stone, 3 ft. base to top of aluminum cap marked:

THE SUBDIVISION OF SECTION 28,
T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T43S R10W
SW 1/16
S28
1994

Raise a mound of stone, 4 ft. base, 3 ft. high, W of the corner.

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

The corner falls on flat ground, in a hollow.

39.970 The center W 1/16 section corner of section 28.

From the center S 1/16 section corner of section 28.

S. 89°55.2' W., on the E - W center line of the SW 1/4 of section 28.

19.984 The SW 1/16 section corner of section 28.

39.968 The S 1/16 section corner of sections 28 and 29.

The Subdivision of Section 29,
T. 43 S., R. 10 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 29 and 32, monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above ground, with brass cap marked as described in the official record of the survey in 1909 by Collier and Gentry.

N. 0°07.2' W., on the N - S center line of section 29.

20.005 Point for the center S 1/16 section corner of section 29.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T43S R10W
C
S 1/16 | S29
C
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

The corner falls on flat sandy ground, scattered cedar.

THE SUBDIVISION OF SECTION 29,
T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS**40.010**

Point for the center 1/4 section corner at intersection with the E - W center line of section 29.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T43S R10W
C 1/4
S29
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the corner.

The corner falls on level sandy ground, scattered cedar.

79.980

The 1/4 section corner of sections 20 and 29.

From the 1/4 section corner of sections 28 and 29.

S. 89°53.2' W., on the E - W center line of section 29.

40.005

The center 1/4 section corner of section 29.

80.002

The 1/4 section corner of sections 29 and 30.

From the S 1/16 section corner of sections 28 and 29.

S. 89°52.2' W., on the E - W center line of the SE 1/4 of section 29.

40.007

The center S 1/16 section corner of section 29.

From the center S 1/16 section corner of section 29.

S. 89°52.2' W., on the E - W center line of the SW 1/4 of section 29.

40.005

The S 1/16 section corner of sections 29 and 30.

The Subdivision of Section 33,
T. 43 S., R. 10 W., Salt Lake Meridian, Utah

THE SUBDIVISION OF SECTION 33,
T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the point for the 1/4 section corner of section 33 only, at midpoint between the closing corners on the south boundary of section 33; not monumented.

N. $0^{\circ}08.3'$ W., on the N - S center line of section 33.

18.807 Point for the center 1/4 section corner, at intersection with the E - W center line of section 33.

Set a rebar 3/4 in. diam., 28 ins. long, 3 ins. below the surface of Utah Avenue, with 3 1/4 ins. diam., aluminum cap marked:

T43S R10W
C 1/4
S33
1994

from which

An aluminum post, 30 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. $42^{\circ}08'$ E., 58.2 ft. dist., with cap marked T43S R10W RM 58.2 FT. 1994 and an arrow pointing to the corner. Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the aluminum post. The corner falls 1 lk. S. of an E - W, 4 strand barbed wire fence line.

An aluminum post, 30 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears N. $46^{\circ}32.3'$ W., 62.2 ft. dist., with cap marked T43S R10W RM 62.2 FT. 1994 and an arrow pointing to the corner. Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the aluminum post. The corner falls 2 lks. S. of a E - W, 4 strand barbed wire fence line.

The corner falls 2 ft. N. of the center of Utah Ave., a paved road, 36 lks. wide.

37.95 Drainage, 9 lks. wide, drains S. 40° E.

38.864 Point for the center N 1/16 section corner of section 33.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T43S R10W
C
N 1/16 | S33
C
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

THE SUBDIVISION OF SECTION 33,
T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Raise a mound of stone, 4 ft. base, 2 ft. high, W. of the corner.

The corner falls on a gradual easterly slope, 45 lks. W., of a drainage, 5 lks. wide, drains S. 21° W.

58.921 The 1/4 section corner of sections 28 and 33.

From the 1/4 section corner of sections 33 and 34.

N. $89^{\circ}59.0'$ W., on the E - W center line of section 33.

40.002 The C 1/4 section corner of section 33.

59.993 Point for the center W 1/16 section corner of section 33; not monumented.

79.984 The 1/4 section corner of sections 32 and 33.

From the point for the center W 1/16 section corner of section 33.

N. $0^{\circ}06.8'$ W., on the N - S center line of the NW 1/4 of section 33.

20.036 Point for the NW 1/16 section corner, at intersection with the E - W center line of the NW 1/4 of section 33.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T43S R10W
NW 1/16
S33
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

Raise a mound of stone, 2 ft. base, 1 ft. high, W of the corner.

Set a steel fence post, N. of the aluminum post.

The corner falls on flat sandy ground.

40.072 The W 1/16 section corner of sections 28 and 33.

THE SUBDIVISION OF SECTION 33,
T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the center N 1/16 section corner of section 33.

S. $89^{\circ}57.4'$ W., on the E - W center line of the NW 1/4 of section 33.

19.981 The NW 1/16 section corner of section 33.

39.962 Point for the N 1/16 section corner of sections 32 and 33.

The Subdivision of Section 34,
T. 43 S., R. 10 W., Salt Lake Meridian, Utah

From the point for the 1/4 section corner of section 34 only, at midpoint between the closing corners on the south boundary of section 34; not monumented.

N. $0^{\circ}09.5'$ W., on the N - S center line of section 34.

18.805 Point for the center 1/4 section corner, at intersection with the E - W center line of section 34.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. below the surface of the ground, with aluminum cap marked:

T43S R10W
C 1/4
S34
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

The corner falls 10 lks. north of the N. edge of a paved road, 36 lks. wide, bears E - W, and 3 lks. south of the S. edge of a asphalt sidewalk, 16 lks. wide, bears E - W.

38.856 Point for the center N 1/16 section corner of section 34.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, set in a mound of stone 5 ft. base to top of aluminum cap marked:

T43S R10W
C
N 1/16 | S34
C
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

THE SUBDIVISION OF SECTION 34,
T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

- The corner falls on flat ground in cove, at head of a canyon, bears E - W.
- 40.10** Bottom of drainage, drains E.
- 41.00** Base of ledges.
- 58.907** The 1/4 section corner of sections 27 and 34.
-
- From the true point for the 1/4 section corner of sections 34 and 35.
S. 89°44.5' W., on the E - W center line of section 34.
- 39.954** The center 1/4 section corner of section 34.
- 59.909** Point for the center W 1/16 section corner of section 34.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 30 ins. deep, flush with the ground, with aluminum cap marked:
- $$C \frac{T43S R10W}{\frac{W 1/16}{S34}} C$$
- 1994
- Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.
- Set a steel fence post, alongside the aluminum post.
- 79.864** The 1/4 section corner of sections 33 and 34.
-
- From the center W 1/16 section corner of section 34.
N. 0°08.5' W., on the N - S center line of the NW 1/4 of section 34.
- 2.50** Chain link fence, 6 ft. high, bears N. 85° E. and S. 85° W.
- 6.73** Chain link fence, 6 ft. high, bears E - W.
- 8.55** Top of earthen dike, 18 lks. wide, approximately 30 ft. high, bears N. 70° E. and S. 70° W.
- 20.079** Point for the NW 1/16 section corner, at intersection with the E - W center line of the NW 1/4 of section 34.

THE SUBDIVISION OF SECTION 34,
T. 43 S., R. 10 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, set in a mound of stone, 5 ft. base, to top of aluminum cap marked:

T43S R10W
NW 1/16
S34
1994

Deposit a magnet, 1 x 1 x 1 7/8 ins. in clear plastic case beneath the stainless steel post.

The corner falls on a steep S. rocky slope, 16 lks. N. of the top edge of a vertical sandstone ledge, 15 ft. high, bears E - W.

40.158 The W 1/16 section corner of sections 27 and 34.

From the center N 1/16 section corner of section 34.

S. 89°49.5' W., on the E - W center line of the NW 1/4 of section 34.

19.948 The NW 1/16 section corner of section 34.

39.896 Point for the N 1/16 section corner of sections 33 and 34.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Shane Button	Survey Aid


CERTIFICATE OF SURVEY

I, *Larry V. Judd, Cadastral Surveyor*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *7th day of March, 1994*, I have *retraced the Utah and Arizona State Boundary (south boundary) from Mile Post 58 to Mile Post 60.19, a dependent resurvey of a portion of the subdivisional lines and the subdivision of sections 26, 27, 28, 29, 33, and 34, in Township 43 South, Range 10 West,*

of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

3/26/96

Date


 Larry V. Judd
 (Cadastral Surveyor)

Date

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
 Salt Lake City, Utah

The foregoing field notes of the *retracement of the Utah and Arizona State Boundary (south boundary) from Mile Post 58 to Mile Post 60.19, and the dependent resurvey of a portion of the subdivisional lines and the subdivision of sections 26, 27, 28, 29, 33, and 34, in Township 43 South, Range 10 West, Salt Lake Meridian, Utah,*

executed by *Larry V. Judd, Cadastral Surveyor*

having been critically examined and found correct, are hereby approved.

April 18, 1996

Date


 (Chief Cadastral Surveyor for Utah)