

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF
A PORTION OF THE SOUTH BOUNDARY
(FOURTH STANDARD PARALLEL SOUTH),
A PORTION OF THE EAST BOUNDARY,
A PORTION OF THE SUBDIVISIONAL LINES,

AND

A PORTION OF THE SAN PETE INDIAN RESERVATION (SOUTH BOUNDARY),

AND

THE SUBDIVISION OF SECTIONS
1, 10, 11, 12, 14, 24, 25, 26, 27, 33, AND 35,

IN

TOWNSHIP 20 SOUTH, RANGE 1 EAST

of the Salt Lake Meridian
In the State of Utah

EXECUTED BY

Ferrel D. Reynolds
Cadastral Surveyor

Under special instructions dated *February 23, 1996*, approved February 23, 1996, which provided for the surveys included under Group Number 835, and assignment instructions dated *April 5, 1996*.

Survey commenced *April 5, 1996*

Survey completed *July 22, 1996*

INDEX DIAGRAM

Township 20 South, Range 1 East

6	5	4	3	2 18 27	1 8 17
7	8	9	10 26 31	11 16 25	12 7 15
18	17	16	15 24	14 15 23	13 6 14
19	20	21	22 22 30	23 13 22	24 5 12
30	29	28 29 32	27 20 29	26 11 20	25 4 11
31	32 31	33 27 3	34 18	35 9 2	36

The Subdivision of Section 1.....	Page 33
The Subdivision of Section 10.....	Page 35
The Subdivision of Section 11.....	Page 36
The Subdivision of Section 12.....	Page 38
The Subdivision of Section 14.....	Page 39
The Subdivision of Section 24.....	Page 41
The Subdivision of Section 25.....	Page 42
The Subdivision of Section 26.....	Page 44
The Subdivision of Section 27.....	Page 46
The Subdivision of Section 33.....	Page 47
The Subdivision of Section 35.....	Page 50
Dependent Resurvey of the South Boundary of the.....	Page 50
San Pete Indian Reservation in Section 33	
Dependent Resurvey of the South Boundary of the.....	Page 51
San Pete Indian Reservation in Section 35	

TOWNSHIP 20 SOUTH, RANGE 1 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

The following field notes describe the dependent resurvey of a portion of the south boundary, (Fourth Standard Parallel South), a portion of the east boundary, a portion of the subdivisional lines, a portion of the south boundary of the San Pete Indian Reservation Boundary, and the subdivision of sections 1, 10, 11, 12, 14, 24, 25, 26, 27, 33, and 35, in Township 20 South, Range 1 East, Salt Lake Meridian, Utah.

History of Surveys

	Surveyed by		Retr. or Resurveyed by	
NORTH BOUNDARY				
Portion	C. Mogo	1856		
All	A. Jessen	1879	A. Jessen	1879
Portion			J.L. Thomas	1990
SOUTH BOUNDARY (Fourth Standard Parallel South)				
Portion	C. Mogo	1856		
All	A.D. Ferron	1878	A.D. Ferron	1878
All			J.C. Clark and R.C. Yundt	1945
EAST BOUNDARY				
Portion	A.D. Ferron	1878		
Portion	A. Jessen	1879		
WEST BOUNDARY (Salt Lake Meridian)				
All	C. Mogo	1856		
Portion			A.D. Ferron	1871
Portion			A. Jessen	1878
SUBDIVISION				
Portion	C. Mogo	1856		
Portion			A.D. Ferron	1871
Portion	A.D. Ferron	1878		
Portion	A. Jessen	1879	A. Jessen	1879
SAN PETE INDIAN RESERVATION (South Boundary)				
Portion	J. Clark	1866		

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group 835, Utah, dated February 23, 1996.

TOWNSHIP 20 SOUTH, RANGE 1 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

The directions of lines were determined by references to true meridians established on line by hour angle observations of the sun and Polaris. The lines were carried forward by sustained angulations, being supplemented by other observations taken throughout the progress of the survey. Distances were determined by electronic measurement.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. The retracement data were thoroughly verified and only the true line notes are given herein.

The geographic position of the standard section corner of sections 32 and 33, on the south boundary, as determined by a tie made to U.S. Coast and Geodetic Survey Triangulation Station "REDMOND" is as follows:

Latitude 39° 01' 07.55" N. Longitude 111° 48' 53.18" W.
N.A.D. 1927

The mean magnetic declination as projected from the U.S. Geological Survey "Magnetic Declination Map of 1990" is: 13 1/2° East.

Dependent Resurvey of a Portion of the South Boundary,
(Fourth Standard Parallel South),
T. 20 S., R. 1 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
C. Mogo in 1856, the Resurvey by J.C. Clark and R.C. Yundt in 1945

Beginning at the standard corner of sections 35 and 36, on the south boundary of the township (Fourth Standard Parallel South) monumented with an iron post, 2 ins. diam., 6 ins. above ground, and in a collar of stone, with brass cap marked as described in the official record of the 1945 resurvey.

N. 89° 47.9' W., on the south boundary of section 35.

39.595 The standard 1/4 section corner of section 35, monumented with an iron post, 1 in. in diam., 8 ins. above ground, with brass cap marked as described in the official record of the 1945 resurvey.

N. 89° 34.9' W., beginning new measurement.

26.633 The closing corner of sections 2 and 3, T. 21 S., R. 1 E., monumented with an iron post, 2 ins. diam., 8 ins. above ground, with brass cap marked as described in the official record of the 1945 resurvey.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
(FOURTH STANDARD PARALLEL SOUTH),
T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS**39.636**

The standard section corner of sections 34 and 35, on the south boundary of the township, monumented with an iron post, 2 ins. diam., 8 ins. above ground, with brass cap marked as described in the official record of the 1945 resurvey.

From the standard section corner of sections 33 and 34, on the south boundary of the township, monumented with an iron post, 2 ins. diam., 16 ins. above ground, in a mound of stone, with brass cap marked as described in the official record of the 1945 resurvey.

From this corner, the closing corner of sections 3 and 4, T. 21 S., R. 1 E., monumented with an iron post, 2 ins. diam., 6 ins. above ground, with brass cap marked as described in the official record of the 1945 resurvey, bears S. 89° 25.8' E., 6.098 chains distance.

N. 89° 32.3' W., on the south boundary of section 33.

14.026

Point for the E 1/16 section corner of section 4 only, T. 21 S., R. 1 E., at midpoint in departure, and on the south boundary of T. 20 S., R. 1 E.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T20S R1E

E 1/16 S4
T21S R1E
1996

Set a 6 ft. steel fence post alongside the aluminum post.

The corner is located on gentle rolling land.

19.966

Point for the standard E 1/16 section corner of section 33 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T20S R1E
E 1/16 S33
1996

Set a 6 ft. steel fence post alongside the aluminum post.

The corner is located 90 lks. E of road from Willow Creek to Axtell.

34.150

The north 1/4 section corner of section 4, T. 21 S., R. 1 E., monumented with an iron post, 1 in. diam., 6 ins. above ground, with brass cap marked as described in the official record of the 1945 resurvey.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
 (FOURTH STANDARD PARALLEL SOUTH),
 T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

39.932

The standard 1/4 section corner of section 33, monumented with an iron post, 1 in. in diam., 6 ins. above ground, with brass cap marked as described in the official record of the 1945 resurvey.

N. 89° 11.9' W., beginning new measurement.

34.466

The closing corner of sections 4 and 5, T. 21 S., R. 1 E., monumented with an iron post, 2 ins. in diam., 10 ins. above ground, in a mound of stone, with brass cap marked as described in the official record of the 1945 resurvey, bears N. 1° 16' W., 0.109 chains distance.

38.507

The standard section corner of sections 32 and 33, monumented with an iron post, 2 ins. diam., 8 ins. above ground, in a mound of stone, with brass cap marked as described in the official record of the 1945 resurvey.

From which

U.S.C. & G.S. triangulation station "REDMOND" bears S. 39° 05.0' E.,
 15.786 chs. distance.

Dependent Resurvey of a Portion of the East Boundary,
 T. 20 S., R. 1 E., Salt Lake Meridian, Utah

Reestablishment of the Surveys Executed by
 A.D. Ferron in 1878 and A. Jessen in 1879

From the section corner of sections 25, 30, 31, and 36, on the east boundary of the township, monumented with a limestone, 15x10x8 ins., 5 ins. above the ground, with 5 notches on the N and 1 notch on the S edges. (Record, 15x12x10 ins., 10 ins. deep.)

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a collar of stone, with aluminum cap marked:

T20S	
R1E R2E	
S25	S30
S36	S31
1996	

Set a 6 ft. steel fence post alongside the aluminum post.

Deposit the marked stone alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

The corner is located on gentle rolling mountain land and in sagebrush.

N. 0° 01.6' E., between sections 25 and 30, on the east boundary of the township.

20.258 Point for the S 1/16 section corner of sections 25 and 30; not monumented.

40.516 The 1/4 section corner of sections 25 and 30, monumented with a limestone, 16x14x10 ins., projecting 5 ins. above ground, with 1/4 on W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S
R1E R2E
1/4
S25 | S30
1996

Deposit the marked stone alongside the aluminum post.

Set a cedar post alongside the aluminum post.

From the 1/4 section corner of sections 19 and 24, on the east boundary of the township, monumented with a clearly marked limestone, 12x8x5 ins., 4 ins. above ground, with 1/4 on W side. (Record, 12x6x4 ins., 8 ins. deep.)

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S
R1E R2E
1/4
S24 | S19
1996

Deposit the marked stone alongside the aluminum post.

Set a cedar post alongside the aluminum post.

N. 1° 00.7' E., between sections 19 and 24, on the east boundary of the township.

40.908 Point for the section corner of sections 13, 18, 19, and 24, at proportionate distance; there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S
R1E R2E
S13 | S18
S24 | S19
1996

Set a 6 ft. steel fence post alongside the aluminum post.

The corner is located on a broken east slope in scattered cedar.

N. 1° 00.7' E., between sections 13 and 18, on the east boundary of the township.

40.908 Point for the 1/4 section corner of sections 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S
R1E R2E
1/4
S13 | S18
1996

Set a 6 ft. steel fence post alongside the aluminum post, in sagebrush and scattered cedar.

The corner is located in bottom of a draw that drains E.

Corner is in sagebrush and scattered cedar.

61.362 Point for the N 1/16 section corner of sections 13 and 18.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S
R1E R2E
N 1/16
S13 | S18
1996

Set a 6 ft. steel fence post alongside the aluminum post.

The corner is located on gentle east slope in scattered cedars.

81.816 Point for the section corner of sections 7, 12, 13, and 18, at proportionate distance; there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T20S
R1E R2E
S12 | S7
S13 | S18
1996

Set a 6 ft. steel fence post alongside the aluminum post.

The corner is located on gentle N slope in scattered sagebrush and cedar.

N. 1° 00.7' E., between sections 7 and 12, on the east boundary of the township.

20.454 The S 1/16 section corner of sections 7 and 12, on the east boundary of the township.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S
R1E R2E
S 1/16
S12 | S7
1996

Set a 6 ft. steel fence post alongside the aluminum post.

The corner is located on steep slope in scattered cedars.

40.908 Point for the 1/4 section corner of sections 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to solid rock, with aluminum cap marked:

T20S
R1E R2E
1/4
S12 | S7
1996

Set a 6 ft. steel fence post alongside the aluminum post.

Corner is on top of small spur projecting west, in scattered sagebrush and juniper.

61.362 Point for the N 1/16 section corner of sections 7 and 12.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, in a mound of stone to top, of aluminum cap marked:

T20S
R1E R2E
N 1/16
S12 | S7
1996

The corner is located on SW slope in lightly scattered juniper.

81.816 The corner of sections 1, 6, 7, and 12, monumented with a limestone, 14x12x7 ins., 6 ins. above ground, clearly marked with 1 notch on the N and 5 notches on the S edges. (Record, 12x8x6 ins., 8 ins. deep.)

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T20S
R1E R2E
S1 | S6
S12 | S7
1996

Deposit the marked stone alongside the aluminum post.

Set a 6 ft. steel fence post alongside the aluminum post.

N. 1° 39.4' W., between sections 1 and 6, on the east boundary of the township.

20.430 Point for the S 1/16 section corner of sections 1 and 6.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S
R1E R2E
S 1/16
S1 | S6
1996

Set a 6 ft. steel fence post alongside the aluminum post.

The corner is located in gentle rolling land in scattered cedars and greasewood.

40.860 The 1/4 section corner of sections 1 and 6, monumented with a limestone, 16x8x6 ins., projecting 6 ins. above the ground, clearly marked 1/4 on W face.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

T20S
R1E R2E
1/4
S1 | S6
1996

Deposit the marked stone alongside the aluminum post.

Set a 6 ft. steel fence post alongside the aluminum post.

N. 0° 11.8' W., beginning new measurement.

40.260

The corner of Tps. 19 and 20 S., Rs. 1 and 2 E., monumented with an aluminum post, 2 1/2 ins. diam., 6 ins. above ground, with aluminum cap marked as described in the official record of the 1990 resurvey.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 20 S., R. 1 E., Salt Lake Meridian, Utah

Reestablishment of a Portion of the Survey by C. Mogo in 1856,
Survey and Resurvey by A.D. Ferron in 1871 and 1878,
and the Survey and Resurvey by A. Jessen in 1879

From the standard section corner of sections 35 and 36, hereinbefore described.

N. 0° 19.4' E., between sections 35 and 36.

40.359

The 1/4 section corner of sections 35 and 36, monumented with a cedar post, 4x4x36 ins., dimly marked.

From which the original bearing tree

A cedar, 8 ins. diameter, bears N. 10° E., 30 lks. distance, marked 1/4 S BT.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T20S R1E
1/4
S35 | S36
1996

Bury the cedar post alongside the aluminum post.

Set a 6 ft. steel fence post alongside the aluminum post.

N. 0° 36.2' E., beginning new measurement.

36.382 Point for the closing corner on the south boundary of the San Pete Indian Reservation, falls on original gypsum mound. There is no remaining evidence of the original corner.

From which the original bearing trees

A cedar, 12 ins. diam., bears S. 40° E., 37 lks. distance., marked
S36 T20S R1E CC BT.

A cedar, 9 ins. diam., bears N. 35° W., 55 lks. distance, marked
CC BT.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with aluminum cap marked:

T20S R1E
SPIR
C | C
S35 | S36
1996

Rebuild original gypsum mound to 3 1/2 ft. diam.

Set a 6 ft. steel fence post alongside the aluminum post.

39.942 Point for the section corner of sections 25, 26, 35, and 36, determined at the A.Jessen 1879 record distance from the SPIR closing corner of sections 35 and 36; there is no remaining evidence of the original corner.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S R1E
S26 | S25
S35 | S36
1996

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a 6 ft. steel fence post alongside the aluminum post.

The corner is located on west side of large wash, drains NNW.

From the section corner of sections 25, 30, 31, and 36, on the east boundary of the township, hereinbefore described.

N. 89° 04.6' W., between sections 25 and 36.

20.021 Point for the E 1/16 section corner of sections 25 and 36.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T20S R1E
E 1/16 $\frac{S25}{S36}$
1996

Set a 6 ft. steel fence post alongside the aluminum post.

The corner is located on west bank of Willow Creek, drains N.

40.042 Point for the 1/4 section corner of sections 25 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S R1E
1/4 $\frac{S25}{S36}$
1996

Set a 6 ft. steel fence post alongside the aluminum post.

The corner is located on gentle E slope in scattered sagebrush.

80.084 The corner of sections 25, 26, 35, and 36.

N. 0° 49.4' E., between sections 25 and 26.

40.520 Point for the 1/4 section corner of sections 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S R1E
1/4
S26 | S25
1996

Set a 6 ft. steel fence post alongside the aluminum post.

The corner is located in grass on a scattered sagebrush flat.

60.780

Point for the N 1/16 section corner of sections 25 and 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S R1E
N 1/16
S26 | S25
1996

Set a 6 ft. steel fence post alongside the aluminum post.

The corner is located in grass on a sagebrush flat.

81.040

Point for the section corner of sections 23, 24, 25, and 26, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S R1E
S23 | S24
S26 | S25
1996

Set a 6 ft. steel fence post alongside the aluminum post.

The corner is located 2.50 chains N of E and W dirt road on a greasewood flat.

From the section corner of sections 19, 24, 25, and 30, on the east boundary of the township, monumented with a limestone, 24x18x12 ins., 8 ins. above ground, with 4 notches on N and 2 notches on S edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T20S
R1E R2E
S24 | S19
S25 | S30
1996

Deposit the marked stone alongside the aluminum post.

Set a 6 ft. steel fence post alongside the aluminum post.

N. 88° 47.5' W., between sections 24 and 25.

19.713 Point for the E 1/16 section corner of sections 24 and 25.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S R1E
E 1/16 S24
S25
1996

Set a 6 ft. steel fence post alongside the aluminum post.

The corner is located on a greasewood flat.

39.426 Point for the 1/4 section corner of sections 24 and 25, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with aluminum cap marked:

T20S R1E
1/4 S24
S25
1996

Set a 6 ft. steel fence post alongside the aluminum post.

The corner is located on a steep south slope in scattered cedars.

78.852 The corner of sections 23, 24, 25, and 26.

N. 0° 23.0' E., between sections 23 and 24.

40.517 Point for the 1/4 section corner of sections 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S R1E
1/4
S23 | S24
1996

Set a 6 ft. steel fence post alongside the aluminum post.

The corner is located on a grassy flat.

81.034

Point for the section corner of sections 13, 14, 23, and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S R1E
S14 | S13
S23 | S24
1996

Set a 6 ft. steel fence post alongside the aluminum post.

The corner is located on west side of old road on a gently rolling, grassy flat.

From the section corner of sections 13, 18, 19, and 24, on the east boundary of the township, hereinbefore described.

N. 89° 21.8' W., between sections 13 and 24.

39.360

Point for the 1/4 section corner of sections 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with aluminum cap marked:

T20S R1E
1/4 S13
 S24
 1996

The corner is located on an extremely steep SE slope on a gypsum outcrop.

78.720

The corner of sections 13, 14, 23, and 24.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0° 45.4' E., between sections 13 and 14.

40.520

Point for the 1/4 section corner of sections 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, to top of aluminum cap marked:

T20S R1E
1/4
S14 | S13
1996

Set a 6 ft. steel fence post alongside the aluminum post.

The corner is located on an E slope in scattered cedars and brush.

81.040

The corner of sections 11, 12, 13, and 14, monumented with a limestone, 13x8x5 ins., 4 ins. above ground, with 4 notches on the S and 1 notch on E edges. (Record, 12x6x4 ins.)

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T20S R1E
S11 | S12
S14 | S13
1996

Deposit the marked stone alongside the aluminum post.

Set a 6 ft. steel fence post alongside the aluminum post.

From the section corner of sections 7, 12, 13, and 18, on the east boundary of the township, hereinbefore described.

N. 89° 55.6' W., between sections 12 and 13.

39.536

Point for the 1/4 section corner of sections 12 and 13, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS		
		T20S R1E 1/4 <u>S12</u> S13 1996
	Set a 6 ft. steel fence post alongside the aluminum post.	
	The corner is located on a steep east slope in scattered cedars and mahogany brush.	
79.072	The corner of sections 11, 12, 13, and 14.	
	<hr/>	
	N. 0° 11.4' W., between sections 11 and 12.	
40.808	The 1/4 section corner of sections 11 and 12, monumented with a red sandstone, 15x12x6 ins. projecting 4 ins. above ground, clearly marked 1/4 on W side.	
	At the corner point	
	Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:	
		T20S R1E 1/4 S11 S12 1996
	Deposit the marked stone alongside the aluminum post.	
	Set a 6 ft. steel fence post alongside the aluminum post.	
	<hr/>	
	N. 0° 06.1' E., beginning new measurement.	
20.395	Point for the N 1/16 section corner of sections 11 and 12.	
	Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:	
		T20S R1E N 1/16 S11 S12 1996
	Set a 6 ft. steel fence post alongside the aluminum post.	
	The corner is located on gentle, almost flat slope in grass and scattered sagebrush.	
40.790	The corner of sections 1, 2, 11, and 12, monumented with a sandstone, 16x8x5 ins., 5 ins. above ground, with 5 notches on the S and 1 notch on E edges.	

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S R1E	
S2	S1
S11	S12
1996	

Deposit the marked stone alongside the aluminum post.

Set a 6 ft. steel fence post alongside the aluminum post.

From the section corner of sections 1, 6, 7, and 12, on the east boundary of the township, hereinbefore described.

N. 89° 41.8' W., between sections 1 and 12.

40.173

The 1/4 section corner of sections 1 and 12, monumented with a broken red sandstone, 15x8x6 ins. projecting 4 ins. above ground, clearly marked 1/4 on N face. (Record, 14x8x6 ins.)

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S R1E	
1/4	S1
	S12
1996	

Deposit the marked stone alongside the aluminum post.

Set a 6 ft. steel fence post alongside the aluminum post.

S. 89° 33.1' W., beginning new measurement.

20.196

Point for the W 1/16 section corner of sections 1 and 12.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S R1E	
W 1/16	S1
	S12
1996	

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS	
	<p>Set a 6 ft. steel fence post alongside the aluminum post.</p> <p>The corner is located on west edge of wash, drains NW, and on gently rolling land, in scattered cedars and greasewood.</p>
40.392	<p>The corner of sections 1, 2, 11, and 12.</p> <hr/> <p>N. 0° 14.4' W., between sections 1 and 2.</p>
20.450	<p>Point for the S 1/16 section corner of sections 1 and 2; not monumented.</p>
40.900	<p>Point for the 1/4 section corner of sections 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to solid rock, with a mound of stone to top, with aluminum cap marked:</p> <p style="text-align: center;">T20S R1E 1/4 S2 S1 1996</p>
	<p>Set a 6 ft. steel fence post alongside the aluminum post.</p> <p>The corner is located on gently rolling land in scattered cedars and sagebrush.</p>
81.595	<p>The corner of sections 1, 2, 35, and 36, on the north boundary of the township, monumented with a properly marked Jones and DeMille Eng. aluminum cap, 1987. No other improvements were made at this location.</p> <hr/> <p>From the standard corner of sections 34 and 35, hereinbefore described.</p> <p>N. 0° 20.2' W., between sections 34 and 35.</p>
39.868	<p>The 1/4 section corner of sections 34 and 35, monumented with a limestone, 15x12x5 ins., projecting 5 ins. above ground, clearly marked 1/4 on W face.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:</p> <p style="text-align: center;">T20S R1E 1/4 S34 S35 1996</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposit the marked stone alongside the aluminum post.

Set a 6 ft. steel fence post alongside the aluminum post.

N. 0° 26.7' E., beginning new measurement.

36.890

The closing corner on the south boundary of the San Pete Indian Reservation, monumented with a limestone, 18x12x6 ins., 6 ins. above ground, clearly marked with a cross and CC on N face, with 1 notch on S and 2 notches on E edges. (Record, 17x11x5 ins.)

From which the original bearing tree

A cedar 8 ins., bears S. 15° E., 12 lks. distance, marked S35 T20S R1E CC BT.

SW bearing tree not found.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with aluminum cap marked:

T20S R1E	
SPIR	
C	C
S34	S35
1996	

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone, to the south of the aluminum post.

Set a 6 ft. steel fence post alongside the aluminum post.

40.740

Point for the section corner of sections 26, 27, 34, and 35, determined at the A. Jessen 1879 record distance from the SPIR closing corner of sections 34 and 35; there is no remaining evidence of the original corner.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S R1E	
S27	S26
S34	S35
1996	

Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, west of the corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a 6 ft. steel fence post alongside the aluminum post.

The corner is located on west side of wash, drains NNE, in scattered cedars.

From the section corner of sections 25, 26, 35, and 36.

N. 89° 28.3' W., between sections 26 and 35.

39.892 Point for the 1/4 section corner of sections 26 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S R1E
1/4 $\frac{S26}{S35}$
1996

Set a 6 ft. steel fence post alongside the aluminum post.

The corner is located on a grass and sagebrush flat.

59.838 Point for the W 1/16 section corner of sections 26 and 35.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S R1E
W 1/16 $\frac{S26}{S35}$
1996

Set a 6 ft. steel fence post alongside the aluminum post.

The corner is located on gentle SE slope in scattered sagebrush and shadscale.

79.784 The corner of sections 26, 27, 34, and 35.

N. 1° 02.7' E., between sections 26 and 27.

20.391 Point for the S 1/16 section corner of sections 26 and 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T20S R1E
S 1/16
S27 | S26
1996

The corner is located on a steep NE slope in scattered cedars.

40.782 Point for the 1/4 section corner of sections 26 and 27, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T20S R1E
1/4
S27 | S26
1996

Set a 6 ft. steel fence post alongside the aluminum post.

The corner is located near eastern edge of Willow Creek Wash, drains SW, and in tamarack and sagebrush.

61.173 Point for the N 1/16 section corner of sections 26 and 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T20S R1E
N 1/16
S27 | S26
1996

Set a 6 ft. steel fence post alongside the aluminum post.

The corner is located on gently rolling land in grass and sagebrush.

81.564 Point for the section corner of sections 22, 23, 26, and 27, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap marked:

T20S R1E
S22 | S23
S27 | S26
1996

Set a 6 ft. steel fence post alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

The corner is located 71 lks. distance N of E and W fence line, on a moderately steep E slope in grass and weeds.

From the section corner of sections 23, 24, 25, and 26.

S. 89° 32.6' W., between sections 23 and 26.

39.467

The 1/4 section corner of sections 23 and 26, monumented with a limestone, 12x8x2 ins., projecting 4 ins. above ground, clearly marked 1/4 on N face. (Record, 12x8x6 ins.)

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T20S R1E
1/4	<u>S23</u>
	S26
	1996

Deposit the marked stone alongside the aluminum post.

Set a 6 ft. steel fence post alongside the aluminum post.

N. 87° 45.0' W., beginning new measurement.

20.002

Point for the W 1/6 section corner of sections 23 and 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T20S R1E
W 1/16	<u>S23</u>
	S26
	1996

Set a 6 ft. steel fence post alongside the aluminum post.

The corner is located 98 lks. distance W of a N and S fence line on a greasewood flat.

40.004

The corner of sections 22, 23, 26, and 27.

N. 1° 08.6' E., between sections 22 and 23.

40.784

Point for the 1/4 section corner of sections 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, in a supporting mound of stone, 4 ft., base, to top of aluminum cap marked:

T20S R1E
1/4
S22 | S23
1996

The corner is located on gentle SE slope in grass and shadscale.

81.568 Point for the section corner of sections 14, 15, 22, and 23, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap marked:

T20S R1E
S15 | S14
S22 | S23
1996

Set a 6 ft. steel fence post alongside the aluminum post.

The corner is located on a moderately steep south slope.

From this corner, the 1/4 section corner of sections 15 and 22, monumented with a limestone, 16x14x2 ins., 5 ins. above ground, clearly marked with 1/4 marked on N face, bears N. 89° 24.3' W., 39.261 chains distance.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S R1E
1/4 S15
 S22
 1996

Set a 6 ft. steel fence post alongside the aluminum post.

The corner is located on a moderately steep S slope.

From the section corner of sections 13, 14, 23, and 24.

N. 88° 42.2' W., between sections 14 and 23.

39.179 Point for the 1/4 section corner of sections 14 and 23, at proportionate distance; there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to solid rock, in a supporting mound of stone, 3 ft. base, to top of aluminum cap marked:

T20S R1E
1/4 $\frac{S14}{S23}$
1996

The corner is located on gently rolling land in sagebrush and scattered cedar.

78.358

The section corner of sections 14, 15, 22, and 23.

N. 1° 38.8' E., between sections 14 and 15.

40.792

The 1/4 section corner of sections 14 and 15, monumented with a sandstone, 24x14x10 ins. projecting 8 ins. above ground, clearly marked 1/4 on W face. (Record, 24x12x10 ins.)

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S R1E
1/4
S15 | S14
1996

Deposit the marked stone alongside the aluminum post.

Set a 6 ft. steel fence post alongside the aluminum post.

N. 2° 45.3' W., beginning new measurement.

19.903

Point for the N 1/16 section corner of sections 14 and 15.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with of aluminum cap marked:

T20S R1E
N 1/16
S15 | S14
1996

Set a 6 ft. steel fence post alongside the aluminum post.

The corner is located on flat land in grass and sagebrush.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS
39.806

Point for the section corner of sections 10, 11, 14, and 15, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap marked:

T20S R1E	
S10	S11
S15	S14
1996	

Set a 6 ft. steel fence post alongside the aluminum post.

The corner is located on a gently rolling land in grass and scattered sagebrush.

From the section corner of sections 11, 12, 13, and 14.

N. 89° 05.3' W., between sections 11 and 14.

40.072

Point for the 1/4 section corner of sections 11 and 14, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to solid rock, in a mound of stone, 3 1/2 ft. base, to top of aluminum cap marked:

	T20S R1E
1/4	S11
	S14
	1996

The corner is located on steep NE slope in scattered sagebrush and shadscale.

60.108

Point for the W 1/16 section corner of sections 11 and 14.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T20S R1E
W 1/16	S11
	S14
	1996

Set a 6 ft. steel fence post alongside the aluminum post.

The corner is located in the bottom of draw, drains NW.

80.144

The corner of sections 10, 11, 14, and 15.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0° 53.1' W., between sections 10 and 11.

19.882 Point for the S 1/16 section corner of sections 10 and 11.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T20S R1E
S 1/16
S10 | S11
1996

Set a 6 ft. steel fence post alongside the aluminum post.

The corner is located on flat land in grass and scattered sagebrush.

39.764 The 1/4 section corner of sections 10 and 11, monumented with a sandstone, 16x8x6 ins., projecting 5 ins. above ground, clearly marked 1/4 on W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S R1E
1/4
S10 | S11
1996

Deposit the marked stone alongside the aluminum post.

Set a 6 ft. steel fence post alongside the aluminum post.

N. 0° 14.2' W., beginning new measurement.

20.146 Point for the N 1/16 section corner of sections 10 and 11.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with aluminum cap marked:

T20S R1E
N 1/16
S10 | S11
1996

Set a 6 ft. steel fence post alongside the aluminum post.

The corner is located on gentle rolling land in scattered sagebrush.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS
40.292

The corner of sections 2, 3, 10, and 11, monumented with a limestone, 14x12x6 ins., 4 ins. above ground, with 5 notches on the S and 2 notches on the E edges.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap marked:

T20S R1E	
S3	S2
S10	S11
1996	

Deposit the marked stone alongside the aluminum post.

Set a 6 ft. steel fence post alongside the aluminum post.

From the section corner of sections 1, 2, 11, and 12.

S. 89° 48.5' W., between sections 2 and 11.

40.415

Point for the 1/4 section corner of sections 2 and 11, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

	T20S R1E
1/4	S2
	S11
	1996

Set a 6 ft. steel fence post alongside the aluminum post.

The corner is located on gently rolling land in scattered sagebrush and grass.

80.830

The corner of sections 2, 3, 10, and 11.

From the standard corner of sections 33 and 34, hereinbefore described.

N. 0° 37.3' E., between sections 33 and 34.

39.904

Point for the 1/4 section corner of sections 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T20S R1E
1/4
S33 | S34
1996

Set a 6 ft. steel fence post alongside the aluminum post.

The corner is located on N slope in grass and shadscale.

59.856 Point for the N 1/16 section corner of sections 33 and 34.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with aluminum cap marked:

T20S R1E
N 1/16
S33 | S34
1996

Raise a mound of stone, to the west of the corner.

Set a 6 ft. steel fence post alongside the aluminum post.

The corner is located 18 lks. south of E and W fence line on a grass flat.

75.768 The closing corner on the south boundary of the San Pete Indian Reservation, monumented with a limestone, 16x10x4 ins., 5 ins. above ground, marked with a cross and a CC on N side, with 1 notch on the S and 3 notches on E edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S R1E
SPIR
C | C
S33 | S34
1996

Deposit the marked stone alongside the aluminum post.

Set a 6 ft. steel fence post alongside the aluminum post.

80.492 The corner of sections 27, 28, 33, and 34, monumented with a gray sandstone, 15x12x8 ins., 5 ins. above ground, marked 3 notches on E and 1 notch on S edges.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap marked:

T20S R1E	
S28	S27
S33	S34
1996	

Deposit the marked stone alongside the aluminum post.

Set a 6 ft. steel fence post alongside the aluminum post.

The corner is located in a N and S fence line on gentle W slope.

From the corner of sections 26, 27, 34, and 35.

N. 89° 35.3' W., between sections 27 and 34.

39.340 Point for the 1/4 section corner of sections 27 and 34, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T20S R1E	
1/4	S27
	S34
1996	

Set a 6 ft. steel fence post alongside the aluminum post.

The corner is located on steep NE slope in scattered cedars.

78.680 The corner of sections 27, 28, 33, and 34.

N. 0° 09.8' E., between sections 27 and 28.

20.243 Point for the S 1/16 section corner of sections 27 and 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, in a mound of stone, 3 1/2 ft. base, to top of aluminum cap marked:

T20S R1E	
S 1/16	
S28	S27
1996	

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

- Set a 6 ft. steel fence post alongside the aluminum post.
- The corner is located 30 lks. W of a N and S fence line.
- 40.486** Point for the 1/4 section corner of sections 27 and 28, at proportionate distance; there is no remaining evidence of the original corner.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with aluminum cap marked:
- | | |
|----------|-----|
| T20S R1E | |
| 1/4 | |
| S28 | S27 |
| 1996 | |
- Set a 6 ft. steel fence post alongside the aluminum post.
- The corner is located 3 lks. distance W of a N and S fence line, in cultivated farm land.
- 80.972** Point for the section corner of sections 21, 22, 27, and 28, determined by using the midpoint between east and west right-of-way fences, bearing N and S; and in alignment with fences bearing E and W. There is no remaining evidence of the original corner. An ancient fence on the north boundary of section 27 was determined to be the best available evidence of the original survey. A thorough retracement was conducted to the north and west to the nearest original found corners. Because of the great discrepancy with the record, the determination was made that proportionate measurement should not be used because it would not agree with the best available evidence of the original survey (the ancient fence.)
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. below the surface of a gravel road, with aluminum cap marked:
- | | |
|----------|-----|
| T20S R1E | |
| S21 | S22 |
| S28 | S27 |
| 1996 | |
-
- From the corner of sections 22, 23, 26, and 27.
- S. 89° 59.4' W., between sections 22 and 27.
- 39.960** Point for the 1/4 section corner of sections 22 and 27, at proportionate distance; there is no remaining evidence of the original corner.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

1/4 T20S R1E
S22
S27
1996

Set a 6 ft. steel fence post alongside the aluminum post.

Corner is located 20 lks. distance S of E and W fence line on W slope in grass and weeds.

79.920 The corner of sections 21, 22, 27, and 28.

From the corner of sections 10, 11, 14, and 15.

N. 89° 33.1' W., between sections 10 and 15.

40.138 The 1/4 section corner of sections 10 and 15, monumented with a limestone, 12x8x6 ins., projecting 4 ins. above ground, with clearly marked 1/4 on N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

1/4 T20S R1E
S10
S15
1996

Deposit the marked stone alongside the aluminum post.

Set a 6 ft. steel fence post alongside the aluminum post.

From the standard corner of sections 32 and 33.

N. 0° 30.6' W., between sections 32 and 33.

39.950 Point for the 1/4 section corner of sections 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in a collar of stone, with aluminum cap marked:

T20S R1E
1/4
S32 | S33
1996

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a 6 ft. steel fence post alongside the aluminum post.

Corner is located 1 chain distance E of cultivated field on a grass and weed covered flat land.

59.950 Point for the N 1/16 section corner of sections 32 and 33.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, in a collar of stone, in the middle of a small dirt road, with aluminum cap marked:

T20S R1E
N 1/16
S32 | S33
1996

Set a 6 ft. steel fence post alongside the aluminum post.

73.480 Point for the closing corner of sections 32 and 33, on the south boundary of the San Pete Indian Reservation at record distance. There is no remaining evidence of the original corner; not monumented.

79.730 Point for the section corner of sections 28, 29, 32, and 33, by using record distances of the section lines between sections 32 and 33, and sections 28 and 33. There is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap marked:

T20S R1E
S29 | S28
S32 | S33
1996

Set a 6 ft. steel fence post alongside the aluminum post.

The corner is located NE of road intersection.

From the corner of sections 27, 28, 33, and 34.

N. 89° 55.7' W., between sections 28 and 33.

20.000 Point for the E 1/16 section corner of sections 28 and 33; not monumented.

40.000 Point for the 1/4 section corner of sections 28 and 33, at record distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

1/4

T20S R1E
 $\frac{S28}{S33}$
 1996

Set a 6 ft. steel fence post alongside the aluminum post.

Corner is located on flat land at edge of cultivated field.

80.000

The corner of sections 28, 29, 32, and 33.

The Subdivision of Section 1,
T. 20 S., R. 1 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 1 and 12.

N. 0° 38.8' W., on the N-S center line of section 1.

20.306

Point for the center S 1/16 section corner of section 1.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T20S R1E
 C
 S 1/16 | S1
 C
 1996

The corner is located in low rolling hills in scattered sagebrush and cedars.

40.612

Point for the center 1/4 section corner of section 1, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T20S R1E
 C 1/4 S1
 1996

Set a 6 ft. steel fence post alongside the aluminum post.

The corner is located in a draw that drains SE.

The area is gently rolling land, with scattered sagebrush and grass.

THE SUBDIVISION OF SECTION 1,
T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

- 81.086** The 1/4 section corner of sections 1 and 36, on the north boundary of the township, monumented with an aluminum post, 2 1/2 ins. diam., projecting 6 ins. above ground, with aluminum cap marked as described in the official record of the 1990 resurvey.
-
- From the 1/4 section corner of sections 1 and 6, on the east boundary of the township, hereinbefore described.
- S. 89° 57.9' W., on the E-W center line of section 1.
- 39.446** The center 1/4 section corner.
- 59.496** Point for the center W 1/16 section corner of section 1; not monumented.
- 79.546** The 1/4 section corner of sections 1 and 2.
-
- From the W 1/16 section corner of sections 1 and 12.
- N. 0° 26.6' W., on the N-S center line of the SW 1/4 of section 1.
- 20.378** Point for the SW 1/16 section corner of section 1, at intersection with the E-W center line of the SW 1/4.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:
- T20S R1E
SW 1/16 S1
1996
- Set a 6 ft. steel fence post alongside the aluminum post.
- Corner is located in open flat land.
- 40.756** The point for the center W 1/16 section corner.
-
- From the center S 1/16 section corner of section 1.
- S. 89° 45.4' W., on the E-W center line of the SW 1/4 of section 1.
- 20.123** The SW 1/16 section corner.
- 40.246** The point for the S 1/16 section corner of sections 1 and 2.
-

THE SUBDIVISION OF SECTION 10,
T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

The Subdivision of Section 10,
T. 20 S., R. 1 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 10 and 15.

N. 0° 45.7' W., on the N-S center line of section 10.

39.496 Point for the center 1/4 section corner of section 10, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T20S R1E
C 1/4 S10
1996

Set a 6 ft. steel fence post alongside the aluminum post.

Corner is located approximately 3 chains distance W of Highland Canal, drains S.

The land is flat with very little ground cover.

59.562 Point for the center N 1/16 section corner of section 10.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T20S R1E
C
N 1/16 | S10
C
1996

Set a 6 ft. steel fence post alongside the aluminum post.

Corner is located 61 lks. S of E and W fence line on a scattered sagebrush flat.

79.628 Point for the 1/4 section corner of sections 3 and 10, as determined from intersection of fences projecting E, W, and N. There is no remaining evidence of the original corner.

This intersection of ancient fences has been long recognized by local land owners as the 1/4 section corner of sections 3 and 10, and is accepted as the best available evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

THE SUBDIVISION OF SECTION 10,
T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

	<p>1/4</p>	<p>T20S R1E $\frac{S3}{S10}$ 1966</p> <p>Set a 6 ft. steel fence post alongside the aluminum post. Corner is located on flat cultivated land.</p>
<p>40.044</p>	<p>The center 1/4 section corner of section 10.</p>	<p>From the 1/4 section corner of sections 10 and 11. N. 89° 56.1' W., on the E- W center line of section 10.</p>
<p>80.414</p>	<p>Point for the 1/4 section corner of sections 9 and 10; as determined at midpoint between E and W right-of-way fences of a gravel road, and in alignment with an ancient fence projecting N. There is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:</p>	<p>T20S R1E 1/4 S9 S10 1996</p> <p>Set a 6 ft. steel fence post alongside the aluminum post. Corner is located 12 lks. N of gravel road, bears E and W.</p>
<p>40.225</p>	<p>The center N 1/16 section corner of section 10.</p>	<p>From the N 1/16 section corner of sections 10 and 11. S. 89° 57.2' W., on the E-W center line of the NE 1/4 of section 10.</p>
<p>20.142</p>	<p>The Subdivision of Section 11, T. 20 S., R. 1 E., Salt Lake Meridian, Utah</p> <p>From the 1/4 section corner of sections 11 and 14. N. 0° 17.6' W., on the N-S center line of section 11.</p> <p>Point for the center S 1/16 section corner of section 11; not monumented.</p>	

THE SUBDIVISION OF SECTION 11,
T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

40.284

Point for the center 1/4 section corner of section 11, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S R1E
C 1/4 S11
1996

Set a 6 ft. steel fence post alongside the aluminum post.

60.554

Point for the center N 1/16 section corner of section 11.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to solid rock, in a supporting mound of stone, with 3 ft. base, to top of aluminum cap marked:

T20S R1E
C
N 1/16 | S11
C
1996

Corner is located on gently rolling land in sagebrush and scattered cedars.

80.824

The 1/4 section corner of sections 2 and 11.

From the 1/4 section corner of sections 11 and 12.

N. 89° 50.3' W., on the E-W center line of section 11.

40.142

The center 1/4 section corner of section 11.

60.372

Point for the center W 1/16 section corner of section 11; not monumented.

80.602

The 1/4 section corner of sections 10 and 11.

From the N 1/16 section corner of sections 11 and 12.

S. 89° 59.3' W., on the E-W center line of the NE 1/4 of section 11.

40.278

The center N 1/16 section corner of section 11.

From the W 1/16 section corner of sections 11 and 14.

N. 0° 35.6' W., on the N-S center line of the SW 1/4 of section 11.

THE SUBDIVISION OF SECTION 11,
T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS**20.012**

Point for the SW 1/16 section corner of section 11, at intersection with the E-W center line of the SW 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S R1E
SW 1/16 S11
1996

Set a 6 ft. steel fence post alongside the aluminum post.

Corner is located on flat land in grass and scattered sagebrush.

40.024

Point for the center W 1/16 section corner of section 11.

From the point for the center S 1/16 section corner of section 11.

N. 89°28.1' W., on the E-W center line of the SW 1/4 of section 11.

20.130

The SW 1/16 section corner of section 11.

40.260

The S 1/16 section corner of sections 10 and 11.

The Subdivision of Section 12,
T. 20 S., R. 1 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 12 and 13.

N. 0° 33.9' E., on the N-S center line of section 12.

40.857

Point for the center 1/4 section corner of section 12, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S R1E
C 1/4 S12
1996

Set a 6 ft. steel fence post alongside the aluminum post.

Corner is located on gently rolling land in scattered cedar and sagebrush.

61.412

Point for the center N 1/16 section corner of section 12.

THE SUBDIVISION OF SECTION 12,
T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S R1E
C
N 1/16 | S12
C
1996

Set a 6 ft. steel fence post alongside the aluminum post.

Corner is located on flat land in grass and sagebrush.

81.967 The 1/4 section corner of sections 1 and 12.

From the 1/4 section corner of sections 7 and 12, on the east boundary of the township, hereinbefore described.

N. 89° 59.7' W., on the E-W center line of section 12.

39.861 The center 1/4 section corner of section 12.

79.921 The 1/4 section corner of sections 11 and 12.

From the center N 1/16 section corner of section 12.

S. 89° 46.6' W., on the E-W center line of the NW 1/4 of section 12.

40.226 The N 1/16 section corner of sections 11 and 12.

The Subdivision of Section 14,
T. 20 S., R. 1 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 14 and 23.

N. 0° 06.6' E., on the N-S center line of section 14.

40.665 Point for the center 1/4 section corner of section 14, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 14,
T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T20S R1E
C 1/4 S14
1996

Set a 6 ft. steel fence post alongside the aluminum post.

Corner is located on gentle NE slope in shadscale.

60.725 Point for the center N 1/16 section corner of section 14; not monumented.

80.785 The 1/4 section corner of sections 11 and 14.

From the 1/4 section corner of sections 13 and 14.

N. 88° 30.1' W., on the E-W center line of section 14.

39.623 The center 1/4 section corner of section 14.

58.665 Point for the center W 1/16 section corner of section 14; not monumented.

77.707 The 1/4 section corner of sections 14 and 15.

From the point for the center W 1/16 section corner of sections 14.

N. 1° 19.1' W., on the N-S center line of the NW 1/4 of section 14.

19.975 Point for the NW 1/16 section corner of section 14, at intersection with the E-W center line of the NW 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to solid rock, in a supporting mound of stone, to top of aluminum cap marked:

T20S R1E
NW 1/16 S14
1996

Corner is located on moderate W slope in sagebrush.

39.950 The W 1/16 section corner of sections 11 and 14.

From the point for the center N 1/16 section corner of section 14.

N. 88° 48.2' W., on the E-W center line of the NW 1/4 of section 14.

19.536 The NW 1/16 section corner of section 14.

THE SUBDIVISION OF SECTION 14,
T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS
39.072

The N 1/16 section corner of sections 14 and 15.

The Subdivision of Section 24,
T. 20 S., R. 1 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 24 and 25.

N. 0° 20.7' E., on the N-S center line of section 24.

40.715 Point for the center 1/4 section corner of section 24, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to solid rock, in a collar of stone, with aluminum cap marked:

T20S R1E
C 1/4 S24
1996

Corner is located on a steep SE slope.

81.428 The 1/4 section corner of sections 13 and 24.

From the 1/4 section corner of sections 19 and 24, on the east boundary of the township, hereinbefore described.

N. 89° 04.7' W., on the E-W center line of section 24.

19.445 Point for the center E 1/16 section corner of section 24.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with aluminum cap marked:

T20S R1E
C E 1/16 C
S24
1996

Corner is located in bottom of drainage, drains SE through scattered cedar.

38.890 The center 1/4 section corner of section 24.

78.282 The 1/4 section corner of sections 23 and 24.

THE SUBDIVISION OF SECTION 24,
T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

- From the E 1/16 section corner of sections 24 and 25.
N. 0° 01.6' W., on the N-S center line of the SE 1/4 of section 24.
- 40.817** The center E 1/16 section corner of section 24.
-
- The Subdivision of Section 25,
T. 20 S., R. 1 E., Salt Lake Meridian, Utah
-
- From the 1/4 section corner of sections 25 and 36.
N. 0° 23.5' E., on the N-S center line of section 25.
- 20.258** Point for the center S 1/16 section corner of section 25.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:
- T20S R1E
C
S 1/16 | S25
C
1996
- Set a 6 ft. steel fence post alongside the aluminum post.
- Corner is located on gentle E slope in scattered sagebrush.
- 40.516** Point for the center 1/4 section corner of section 25, at intersection with the E-W center line.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:
- T20S R1W
C 1/4 S25
1996
- Set a 6 ft. steel fence post alongside the aluminum post.
- Corner is located on flat land covered with thick greasewood.
- 60.681** Point for the center N 1/16 section corner of section 25.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 25,
T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS	
	<p style="text-align: center;">T20S R1E C N 1/16 S25 C 1996</p> <p>Set a 6 ft. steel fence post alongside the aluminum post.</p> <p>Corner is located on flat land in thick sagebrush.</p> <p>80.846 The 1/4 section corner of sections 24 and 25.</p> <hr/> <p>From the 1/4 section corner of sections 25 and 30, on the east boundary of the township, hereinbefore described.</p> <p>N. 89° 04.2' W., on the E-W center line of section 25.</p>
	<p>19.890 Point for the center E 1/16 section corner of section 25; not monumented.</p>
	<p>39.780 The center 1/4 section corner of section 25.</p>
	<p>79.512 The 1/4 section corner of sections 25 and 26.</p> <hr/> <p>From the E 1/16 section corner of sections 25 and 36.</p> <p>N. 0° 12.6' E., on the N-S center line of the SE 1/4 of section 25.</p>
	<p>20.258 Point for the SE 1/16 section corner of section 25, at intersection with the E-W center line of the SE 1/4.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:</p>
	<p style="text-align: center;">T20S R1E SE 1/16 S25 1996</p> <p>Set a 6 ft. steel fence post alongside the aluminum post.</p> <p>Corner is located on E edge of trail road, bears N and S, and on E side of Willow Creek, drains S.</p>
	<p>40.516 The point for the center E 1/16 section corner of section 25.</p> <hr/>

THE SUBDIVISION OF SECTION 25,
T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the point for the S 1/16 section corner on the east boundary of the township, hereinbefore described.

N. 89° 04.2' W., on the E-W center line of the SE 1/4 of section 25.

19.955 The SE 1/16 section corner of section 25.

39.910 The center S 1/16 section corner of section 25.

From the center N 1/16 section corner of section 25.

N. 88° 55.7' W., on the E-W center line of the NW 1/4 of section 25.

39.579 The N 1/16 section corner of sections 25 and 26.

The Subdivision of Section 26,
T. 20 S., R. 1 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 26 and 35.

N. 1° 07.5' E., on the N-S center line of section 26.

40.668 Point for the center 1/4 section corner of section 26, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S R1E
C 1/4 S26
1996

Set a 6 ft. steel fence post alongside the aluminum post.

Corner is located in a draw, drains NNW.

60.523 Point for the center N 1/16 section corner of section 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S R1E
C
N 1/16 | S26
C
1996

THE SUBDIVISION OF SECTION 26,
T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

- Set a 6 ft. steel fence post alongside the aluminum post.
- Corner is located in bottom of Willow Creek, drains W, near S edge of tamarack and willows.
- 80.378** The 1/4 section corner of sections 23 and 26.
-
- From the 1/4 section corner of sections 25 and 26.
- N. 89° 17.0' W., on the E-W center line of section 26.
- 39.672** The center 1/4 section corner of section 26.
- 59.644** Point for the center W 1/16 section corner of section 26; not monumented.
- 79.616** The 1/4 section corner of sections 26 and 27.
-
- From the N 1/16 section corner of sections 25 and 26.
- N. 89° 52.0' W., on the E-W center line of the NE 1/4 of section 26.
- 39.566** The center N 1/16 section corner of section 26.
-
- From the point for the center W 1/16 section corner of section 26.
- N. 1° 05.1' E., on the N - S center line of the NW 1/4 of section 26.
- 20.098** Point for the NW 1/16 section corner of section 26, at intersection with the E - W center line of the NW 1/4.
- Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:
- T20S R1E
NW 1/16 S26
1996
- Set a 6 ft. steel fence post alongside the aluminum post.
- Corner is located in bottom of Willow Creek in tamarack and willows.
- 40.196** The W 1/16 section corner of sections 23 and 26.
-

THE SUBDIVISION OF SECTION 26,
T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the center N 1/16 section corner of section 26.

N. 88° 31.2' W., on the E - W center line of the NW 1/4 of section 26.

19.986 The NW 1/16 section corner of section 26.

39.972 The N 1/16 section corner of sections 26 and 27.

The Subdivision of Section 27,
T. 20 S., R. 1 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 27 and 34.

N. 0° 36.3' E., on the N-S center line of section 27.

20.316 Point for the center S 1/16 section corner of section 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S R1E
C
S 1/16 | S27
C
1996

Set a 6 ft. steel fence post alongside the aluminum post.

Corner is located approximately 2 chs. distance S of Willow Creek, drains W, and on flat land in grass and scattered greasewood.

40.632 Point for the center 1/4 section corner of section 27, at intersection with the E - W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 4 ins. in the ground to solid rock, with a mound of stone, 4 1/2 ft. base, to top of the aluminum cap marked:

T20S R1E
C 1/4 S27
1996

60.949 Point for the center N 1/16 section corner of section 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to solid rock, with a mound of stone, 4 1/2 ft. base, to top of the aluminum cap marked:

THE SUBDIVISION OF SECTION 27,
T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T20S R1E

C
N 1/16 | S27
C
1996

Corner is located on a steep W slope.

81.266 The 1/4 section corner of sections 22 and 27.

From the 1/4 section corner of sections 26 and 27.

N. 89° 48.0' W., on the E-W center line of section 27.

39.650 The center 1/4 section corner of section 27.

79.300 The 1/4 section corner of sections 27 and 28.

From the N 1/16 section corner of sections 26 and 27.

N. 89° 54.1' W., on the E-W center line of the NE 1/4 of section 27.

39.804 The center N 1/16 section corner of section 27.

From the S 1/16 section corner of sections 26 and 27.

N. 89° 41.4' W., on the E-W center line of the SE 1/4 of section 27.

39.495 The center S 1/16 section corner of section 27.

From the center S 1/16 section corner of section 27.

N. 89° 41.9' W., on the E-W center line of the SW 1/4 of section 27.

39.495 The S 1/16 section corner of sections 27 and 28.

The Subdivision of Section 33,
T. 20 S., R. 1 E., Salt Lake Meridian, Utah

From the standard 1/4 section corner of section 33, hereinbefore described.

N. 0° 34.1' E., on the N-S center line of section 33.

THE SUBDIVISION OF SECTION 33,
T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS**40.041**

Point for the center 1/4 section corner of section 33, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T20S R1E
C 1/4 S33
1996

Set a 6 ft. steel fence post alongside the aluminum post.

Corner is located on gently rolling land in scattered shadscale and sagebrush.

59.788

Point for the center N 1/16 section corner of section 33.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T20S R1E
C
N 1/16 | S33
C
1996

Set a 6 ft. steel fence post alongside the aluminum post.

Corner is located 38 lks. distance N of an E and W fence line, and on gentle E slope in grass and scattered brush.

74.733

The point of intersection with the south boundary of the San Pete Indian Reservation on the straight line between its closing corners; not monumented.,

80.221

The 1/4 section corner of sections 28 and 33.

From the 1/4 section corner of sections 33 and 34.

N. 89° 20.6' W., on the E-W center line of section 33.

19.983

The point for the center E 1/16 section corner of section 33.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T20S R1E
C E 1/16 C
S33
1996

THE SUBDIVISION OF SECTION 33,
T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a 6 ft. steel fence post alongside the aluminum post.

Corner is located on gentle W slope in grass and scattered shadscale.

39.966 The center 1/4 section corner of section 33.

79.220 The 1/4 section corner of sections 32 and 33.

From the center E 1/16 section corner of section 33.

N. 0° 35.7' E., on the N-S center line of the NE 1/4 of section 33.

19.850 Point for the NE 1/16 section corner of section 33, at intersection with the E-W center line of the NE 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T20S R1E
NE 1/16 S33
1996

Set a 6 ft. steel fence post alongside the aluminum post.

Corner is located 10 lks. distance N of E and W fence line, on a grass flat land.

35.278 The point of intersection with the south boundary of the San Pete Indian Reservation, on a straight line between its closing corners; not monumented.

40.385 Point for the E 1/16 section corner of sections 28 and 33.

From the N 1/16 section corner of sections 33 and 34.

N. 89° 38.1' W., on the E-W center line of the NE 1/4 of section 33.

19.991 The NE 1/16 section corner of section 33.

39.982 The center N 1/16 section corner of section 33.

From the standard E 1/16 section corner of section 33, hereinbefore described.

N. 0° 35.7' E., on the N-S center line of the SE 1/4 of section 33.

39.972 The center E 1/16 section corner of section 33.

THE SUBDIVISION OF SECTION 33,
T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

	From the center N 1/16 section corner of section 33. N. 88° 59.2' W., on the E-W center line of the NW 1/4 of section 33.
39.630	The N 1/16 section corner of sections 32 and 33.
Dependent Resurvey of the South Boundary of the San Pete Indian Reservation in Section 33	
(Reestablishment of the Survey Executed by J. Clark in 1866)	
	From the closing corner for sections 33 and 34, on the south boundary of the San Pete Indian Reservation. S. 88° 58.7' W., on the south boundary of the San Pete Indian Reservation.
20.005	The point of intersection with the N-S center line of the NE 1/4 of section 33.
40.010	The point of Intersection with the N-S center line of section 33.
79.907	The closing corner for sections 32 and 33, on the south boundary of the San Pete Indian Reservation.
The Subdivision of Section 35, T. 20 S., R. 1 E., Salt Lake Meridian, Utah	
	From the standard 1/4 section corner of section 35, hereinbefore described. N.0° 14.8' E., on the N-S center line of section 35.
40.190	Point for the center 1/4 section corner of section 35, at intersection with the E-W center line. Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked: T20S R1E C 1/4 S35 1996 Set a 6 ft. steel fence post alongside the aluminum post. Corner is located on a gently rolling W slope in grass and scattered sagebrush.

THE SUBDIVISION OF SECTION 35,
T. 20 S., R. 1 E., SALT LAKE MERIDIAN, UTAH

CHAINS

76.825 The point of intersection with the south boundary of the San Pete Indian Reservation on a straight line between its closing corners; not monumented.

80.514 The 1/4 section corner of sections 26 and 35.

From the 1/4 section corner of sections 35 and 36.

S. 89° 57.4' W. on the E-W center line of section 35.

39.646 The center 1/4 section corner of section 35.

59.665 Point for the center W 1/16 section corner of section 35.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T20S R1E
C W 1/16 C
S35
1996

Set a 6 ft. steel fence post alongside the aluminum post.

Corner is located on gently rolling W slope in old burned area, covered mostly with weeds and grass.

79.684 The 1/4 section corner of sections 34 and 35.

From the center W 1/16 section corner of section 35.

N. 0° 20.8' E., on the N-S center line of the NW 1/4 of section 35.

36.762 The point of intersection with the south boundary of the San Pete Indian Reservation on a straight line between the closing corners; not monumented.

40.532 The W 1/16 section corner of sections 26 and 35.

Dependent Resurvey of the South Boundary of the
San Pete Indian Reservation in Section 35

(Reestablishment of the Survey Executed by
J. Clark in 1866)

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY OF THE
SAN PETE INDIAN RESERVATION IN SECTION 35

CHAINS

From the closing corner for sections 35 and 36, on the south boundary of the San Pete Indian Reservation.

N. 89° 40.8' W., on the south boundary of the San Pete Indian Reservation.

39.868 The point of intersection with the N-S center line of section 35.

59.821 The point of intersection with the N-S center line of the NW 1/4 of section 35.

79.774 The closing corner on the south boundary of the San Pete Indian Reservation for sections 34 and 35.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Philip Tobler	Surveying Technician

CERTIFICATE OF SURVEY

I, *Ferrel D. Reynolds, Cadastral Surveyor*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *23rd day of February, 1996*, I have *dependently resurveyed portions of the south and east boundaries, and south boundary of the San Pete Indian Reservation, and subdivisional lines, and subdivided sections 1, 10, 11, 12, 14, 24, 25, 26, 27, 33, and 35, in Township 20 South, Range 1 East,*

of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

2-28-2000

Date

Ferrel D. Reynolds

(Cadastral Surveyor)

Date

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of portions of the south and east boundaries, subdivisional lines, and south boundary of the San Pete Indian Reservation, and subdivided sections 1, 10, 11, 12, 14, 24, 25, 26, 27, 33, and 35, in Township 20 South, Range 1 East, Salt Lake Meridian, Utah,*

executed by *Ferrel D. Reynolds, Cadastral Surveyor*

having been critically examined and found correct, are hereby approved.

July 21, 2000

Date

Daniel W. Webb

(Chief Cadastral Surveyor for Utah)