

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

## FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

THE NORTH BOUNDARY,

A PORTION OF THE SOUTH AND WEST BOUNDARIES,

A PORTION OF THE SUBDIVISIONAL LINES,

THE SUBDIVISION OF SECTIONS 5, 8, 17, 29, AND 30,

AND

MINERAL SURVEY NO. 7270

IN

TOWNSHIP 12 SOUTH, RANGE 3 WEST

OF THE SALT LAKE MERIDIAN  
IN THE STATE OF UTAH

EXECUTED BY

*Jerry L. Thomas*  
*Cadastral Surveyor*

Under special instructions dated *August 1, 1996*, approved *August 1, 1996*, which provided for the surveys included under Group Number *849*, and assignment instructions dated *August 1, 1996*

Survey commenced *August 1, 1996*  
Survey completed *July 24, 1997*

**INDEX DIAGRAM**

Township 12 South, Range 3 West

10	9	8	8	7	6
6 44	5 32	4 25	3 19	2 13	1
43	42	31	25	19	18
7 41	8 31	9 24	10 18	11 11	12
41	39	30	24	17	
18 39	17 30	16 23	15 17	14	13
38	37	29	22	16	
19 37	20 28	21 22	22 16	23	24
36	35	28	21	15	
10 30 34	29 27	28 28	27 14	26	25
34	33	26	20	14	
31 32	32 26	33 19	34 13	35	36
5	4	3	2		

The Subdivision of Section 5 ..... Page 44  
 The Subdivision of Section 8 ..... Page 46  
 The Subdivision of Section 17..... Page 48  
 The Subdivision of Section 29..... Page 49  
 The Subdivision of Section 30..... Page 52  
 Mineral Survey No. 7270..... Page 53

## TOWNSHIP 12 SOUTH, RANGE 3 WEST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

The following field notes describe the dependent resurvey of the north boundary, a portion of the south and west boundaries, a portion of the subdivisional lines, the subdivision of sections 5, 8, 17, 29, and 30, and Mineral Survey No. 7270, T. 12 S., R. 3 W., Salt Lake Meridian, Utah.

**History of Surveys**

<b>Surveyed by</b>		<b>Retr. or Resurveyed by</b>	
<b>SOUTH BOUNDARY</b>			
All	J. Gorlinski	1872	
Portion			E. Bird and A. Nelson 1944
Portion			G.E. Reynolds 1986
<b>EAST BOUNDARY</b>			
Portion	J. Gorlinski	1872	
All	E. Bird and A. Nelson	1944	E. Bird and A. Nelson 1944
<b>WEST BOUNDARY</b>			
All	J. Gorlinski	1872	
Portion			J.W. Dougall 1911
<b>NORTH BOUNDARY</b>			
All	J. Gorlinski	1872	
<b>SUBDIVISION</b>			
Portion	J. Gorlinski	1872	
Portion	E. Bird and A. Nelson	1944	
Portion			E. Bird and A. Nelson 1944

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 849, Utah, dated August 1, 1996.

The direction of the lines of this survey refer to the true meridian, determined by hour angle observations of the sun and Polaris and carried forward by means of sustained angulation. The measurements of these lines were made with an electronic distance measuring device. Horizontal distances only are entered in the field notes.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line notes are given herein.

## TOWNSHIP 12 SOUTH, RANGE 3 WEST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

The geographic position of Triangulation Station "DYER", as published by the National Geodetic Surveys, is as follows:

Latitude 39° 40' 21.24325" N.  
N.A.D. 1983 (1986)

Longitude 112° 15' 40.11759" W.

The geographic position of the corner of Townships 12 and 13 South, Ranges 3 and 4 West, determined by ties to U.S.G.S. triangulation station "DYER", by the Global Positioning System, using relative positioning techniques, and now also functioning as a B.L.M. control station, is as follows:

Latitude 39° 43' 42.214"N.  
N.A.D. 1983.

Longitude 112° 13' 59.228"W.

The mean magnetic declination as determined from numerous readings throughout the survey is: 12 3/4° East.

---

Dependent Resurvey of a Portion of the South Boundary,  
T. 12 S., R. 3 W., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by  
J. Gorlinski in 1872

---

Beginning at the corner of sections 2, 3, 34, and 35, on the south boundary of the township, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with aluminum cap marked as described in the official record of the 1986 resurvey of a portion of the north boundary of T. 13 S., R. 3 W.,

N. 89° 10.6' W., between sections 3 and 34, on the south boundary of the township.

Over gentle rolling land.

**37.765**

The 1/4 section corner of sections 3 and 34, monumented with a limestone, 10x10x7 inches, firmly set, projecting 6 inches above ground, plainly marked 1/4 on the N face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W  
1/4      S34    
          S3  
          T13S  
          1996

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

---

S. 89° 27.7' W., beginning new measurement.

**42.985** The corner of sections 3, 4, 33, and 34, monumented with a limestone, 14x10x6 inches, firmly set, projecting 8 inches above ground, plainly marked 3 notches on the E and W edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W	
S33	S34
S4	S3
T13S	
1996	

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

---

N. 89° 51.7' W., between sections 4 and 33, south boundary.

Over gentle rolling land.

**40.570** The 1/4 section corner of sections 4 and 33, monumented with a limestone, 16x12x8 inches, firmly set, projecting 8 inches above ground, dimly marked 1/4 on the N face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W	
1/4	S33
	S4
T13S	
1996	

Deposit the dimly marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

---

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

N. 89° 49.8' W., beginning new measurement.

**40.545** The corner of sections 4, 5, 32, and 33, monumented with a limestone, 12x10x8 inches, firmly set, projecting 8 inches above ground, and dimly marked.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W	
S32	S33
S5	S4
T13S	
1996	

Deposit the dimly marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

Corner is located 1 chain west of U.S. Highway No. 6.

---

N. 89° 49.7' W., between sections 5 and 32, south boundary.

Over rolling land.

**40.505** The 1/4 section corner of sections 5 and 32, monumented with a limestone, 14x10x6 inches, firmly set, projecting 8 inches above ground, plainly marked 1/4 on the N face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

	T12S R3W
	S32
1/4	S5
	T13S
	1996

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

---

N. 89° 52.2' W., beginning new measurement.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

**40.340**

The corner of sections 5, 6, 31, and 32, monumented with a limestone 14x10x6 inches, plainly marked 5 notches on the E and 1 notch on the W edges, from which the original bearing tree

A cedar, 14 inches diameter, bears North, 30 links distance, marked  
T12S R3W S32 BT.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W	
S31	S32
S6	S5
T13S	
1996	

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

---

N. 89° 51.4' W., between sections 6 and 31, south boundary.

Over rolling land.

**40.390**

The 1/4 section corner of sections 6 and 31, monumented with a quartzite stone, 14x12x8 inches, firmly set, projecting 8 inches above ground, plainly marked 1/4 on the N face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

	T12S R3W
1/4	S31
	S6
	T13S
	1996

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

---

N. 89° 53.1' W., beginning new measurement.

**20.202**

Point for the W 1/16 section corner of sections 6 and 31.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

W 1/16      $\frac{S31}{S6}$   
1996

Set a steel fence post alongside the corner.

- 40.404** The corner of Townships 12 and 13 South, Ranges 3 and 4 W., monumented with an iron post, 3 inches diameter, firmly set, projecting 8 inches above ground, with brass cap marked as described in the official record of the 1911 resurvey of the south boundary of T. 12 S., R. 4 W.

---

Dependent Resurvey of the North Boundary,  
T. 12 S., R. 3 W., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by  
J. Gorkinski in 1872

---

From the corner of Township 11 South, Ranges 2 and 3 West, Township 11 1/2 South, Range 2 1/2 West, and Township 12 South, Range 3 West, monumented with an iron post, 3 inches diameter, firmly set, projecting 10 inches above ground, with brass cap marked as described in the official record of the 1944 resurvey of a portion of the east boundary.

N. 89° 56.5' W., between sections 1 and 36, north boundary.

Over broken and rolling land.

- 40.405** Point for the 1/4 section corner of sections 1 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T11S R3W  
1/4      $\frac{S36}{S1}$   
T12S  
1996

Set a steel fence post alongside the corner.

Corner is located 12 1/2 links N of E and W fence line.

- 80.810** Point for the corner of sections 1, 2, 35, and 36, at proportionate distance; there is remaining evidence of the original corner.

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,  
T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T11S	R3W
<u>S35</u>	<u>S36</u>
S2	S1
T12S	
1996	

Set a steel fence post alongside the corner.

Corner is located 6 1/2 links N of E and W fence line.

---

N. 89° 56.5' W., between sections 2 and 35, north boundary.

Over rolling land.

**40.405** The 1/4 section corner of sections 2 and 35, monumented with a limestone, 16x12x6 inches, firmly set, dimly marked 1/4 on the N face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

	T11S	R3W
1/4	<u>S35</u>	
	S2	
	1996	

Deposit the dimly marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

---

N. 89° 57.7' W., beginning new measurement.

**40.025** Point for the corner of sections 2, 3, 34, and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

	T11S	R3W
	<u>S34</u>	<u>S35</u>
	S3	S2
	T12S	
	1996	

Set a steel fence post alongside the corner.

---

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,  
T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

N. 89° 57.7' W., between sections 3 and 34, north boundary.

Over gentle rolling land.

**40.025** Point for the 1/4 section corner of sections 3 and 34, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with aluminum cap marked:

	T11S	R3W
1/4	<u>S34</u>	
	S3	
	T12S	
	1996	

Set a steel fence post alongside the corner.

Corner is located 6 1/2 links S of E and W fence line.

**80.050** The corner of sections 3, 4, 33, and 34, monumented with a black sandstone, 22x14x12 inches, firmly set, projecting 12 inches above ground, plainly marked 3 notches on the E and W edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

	T11S	R3W
	<u>S33</u>	<u>S34</u>
	S4	S3
	T12S	
	1996	

Deposit the marked stone alongside the aluminum post.

Corner is located in E and W fence line.

---

N. 89° 47.3' W., between sections 4 and 33, on the north boundary.

Over rolling land.

**40.345** Point for the 1/4 section corner of sections 4 and 33, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,  
T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

1/4      T11S R3W  
          S33  
          S4  
          T12S  
          1996

Set a steel fence post alongside the corner.

**80.690** The corner of sections 4, 5, 32, and 33, monumented with a sandstone, 10x8x4 inches, firmly set, projecting 6 inches above ground, plainly marked 4 notches on the E and 2 notches on the W edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

          T11S R3W  
          S32 | S33  
          S5    | S4  
          T12S  
          1996

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

---

S. 89° 59.4' W., between sections 5 and 32, north boundary.

Over rolling land.

**40.385** Point for the 1/4 section corner of sections 5 and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

          T11S R3W  
1/4      S32  
          S5  
          T12S  
          1996

Set a steel fence post alongside the corner.

**80.770** The corner of sections 5, 6, 31, and 32, monumented with a sandstone, 16x8x6 inches, firmly set, projecting 8 inches above ground, plainly marked 5 notches on the E and 1 notch on the W edges.

At the corner point

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,  
T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T11S R3W	
S31	S32
S6	S5
T12S	
1996	

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

---

N. 89° 51.2' W., between sections 6 and 31, on the north boundary.

Over rolling land.

**40.290** Point for the 1/4 section corner of sections 6 and 31, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T11S R3W	
1/4	S31
	S6
	T12S
	1996

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of corner.

Set a steel fence post alongside the corner.

**80.580** The corner of Townships 11 and 12 South, Ranges 3 and 4 West, monumented with an iron post, 3 inches diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1911 resurvey of the east boundary of T. 12 S., R. 4 W.

---

Dependent Resurvey of a Portion of the West Boundary,  
T. 12 S., R. 3 W., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by  
J. Gorlinski in 1872, and the Resurvey  
by J. W. Dougall in 1911

---

From the 1/4 section corner of section 30 only, determined from the original bearing trees

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

A cedar, 10 inches diameter, bears N. 76° 40' E., 98 links distance,  
marked 1/4 S30 BT.

A cedar, 13 inches diameter, bears S. 8° 40' W., 144 links distance,  
marked 1/4 S25 BT.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with  
aluminum cap marked:

T12S  
R4W R3W  
| 1/4  
| S30  
1996

Set a steel fence post alongside the corner.

N. 0° 12.5' W., on the west boundary of section 30.

Over rolling land.

**20.190** Point for the N 1/16 section corner of section 30, only.

Point not monumented.

**39.140** The corner of sections 24 and 25, T. 12 S., R. 4 W., monumented with an iron post, 2  
inches diameter, firmly set, projecting 8 inches above ground, with brass cap marked as  
described in the official record of the 1911 survey of the east boundary of T. 12 S., R. 4 W.

**40.380** The corner of sections 19 and 30, monumented with an iron post, 2 inches diameter, firmly  
set, projecting 8 inches above ground, with brass cap marked as described in the official  
record of the 1911 survey of the east boundary of T. 12 S., R. 4 W.

---

Dependent Resurvey of a Portion of the Subdivisional,  
Lines, T. 12 S., R. 3 W., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed  
by J. Gorlinski in 1872

---

From the corner of sections 11, 12, 13, and 14, monumented with an iron post, 2 inches  
diameter, firmly set, projecting 8 inches above ground, with brass cap marked as described  
in the official record of the 1944 survey of a portion of the subdivisional lines of T. 12 S.,  
R. 3 W.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

N. 0° 03.8' E., between sections 11 and 12.

Over rolling land.

**40.380** Point for the 1/4 section corner of sections 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W	
1/4	
S11	S12
1996	

Set a steel fence post alongside the corner.

**80.760** Point for the corner of sections 1, 2, 11, and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W	
S2	S1
S11	S12
1996	

Set a steel fence post alongside the corner.

---

From the corner of sections 1 and 12, east boundary, which also functions as the corner of Townships 11 1/2 and 12 S., Range 2 1/2 West, monumented with an iron post, 3 inches diameter, firmly set, projecting 8 inches above ground, with brass cap marked as described in the official record of the 1944 survey of the east boundary of T. 12 S., R. 3 W.

S. 89° 56.7' W., between sections 1 and 12.

Over broken land.

**40.165** Point for the 1/4 section corner of sections 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W	
1/4	S1
	S12
1996	

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

- Set a steel fence post alongside the corner.
- 80.330** The corner of sections 1, 2, 11, and 12.
- 
- N. 0° 14.1' W., between sections 1 and 2.
- Over rolling land.
- 40.380** Point for the 1/4 section corner of sections 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.
- Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:
- T12S R3W  
1/4  
S2 | S1  
1996
- Set a steel fence post alongside the corner.
- 80.960** The corner of sections 1, 2, 35, and 36, north boundary, hereinbefore described.
- 
- From the corner of sections 2, 3, 34, and 35, south boundary, hereinbefore described.
- N. 0° 12.6' E., between sections 34 and 35.
- Over rolling land.
- 40.510** Point for the 1/4 section corner of sections 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.
- Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:
- T12S R3W  
1/4  
S34 | S35  
1996
- Set a steel fence post alongside the corner.
- 81.020** The corner of sections 26, 27, 34, and 35, monumented with a quartzite stone, 18x12x10 inches, firmly set, projecting 6 inches above ground, plainly marked 1 notch on the S and 2 notches on the E edges.
- At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W	
S27	S26
S34	S35
1996	

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

---

From the corner of sections 25, 26, 35, and 36, monumented with an iron post, 2 inches diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1944 survey of a portion of the subdivisional lines of T. 12 S., R.3 W.

N. 89° 48.6' W., between sections 26 and 35.

Over rolling land.

**40.475** Point for the 1/4 section corner of sections 26 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W	
1/4	S26
	S35
1996	

Set a steel fence post alongside the corner.

**80.950** The corner of sections 26, 27, 34, and 35.

---

N. 0° 09.7' E., between sections 26 and 27.

Over rolling land.

**40.660** The 1/4 section corner of sections 26 and 27, monumented with a limestone, 14x10x6 inches, firmly set, projecting 8 inches above ground, plainly marked 1/4 on the W face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T12S R3W  
1/4  
S27 | S26  
1996

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

---

N. 1° 25.5' W., beginning new measurement.

**40.415** Point for the corner of sections 22, 23, 26, and 27, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W  
S22 | S23  
S27 | S26  
1996

Set a steel fence post alongside the corner.

---

From the corner of sections 23, 24, 25, and 26, monumented with an iron post, 2 inches diameter, firmly set, projecting 8 inches above ground, with brass cap marked as described in the official record of the 1944 survey of a portion of the subdivisional lines of T. 12 S., R. 3 W.

N. 89° 48.7' W., between sections 23 and 26.

Over rolling land.

**40.700** Point for the 1/4 section corner of sections 23 and 26, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W  
1/4     S23  
         S26  
         1996

Set a steel fence post alongside the corner.

**81.400** The corner of sections 22, 23, 26, and 27.

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

N. 0° 12.2' E., between sections 22 and 23.

Over rolling land.

**40.405** Point for the 1/4 section corner of sections 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W	
1/4	
S22	S23
1996	

Set a steel fence post alongside the corner.

**80.810** Point for the corner of sections 14, 15, 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W	
S15	S14
S22	S23
1996	

Set a steel fence post alongside the corner.

---

From the corner of sections 13, 14, 23, and 24, monumented with an iron post, 2 inches diameter, firmly set, projecting 8 inches above ground, with brass cap marked as described in the official record of the 1944 survey of a portion of the subdivisional lines of T. 12 S., R. 3 W.

S. 89° 58.6' W., between sections 14 and 23.

Over rolling land.

**40.390** Point for the 1/4 section corner of sections 14 and 23, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W	
1/4	S14
	S23
1996	

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

<i>CHAINS</i>	
	Set a steel fence post alongside the corner.
<b>80.780</b>	The corner of sections 14, 15, 22, and 23.
	<hr/> <p>N. 0° 00.2' E., between sections 14 and 15.</p> <p>Over rolling land.</p>
<b>40.405</b>	Point for the 1/4 section corner of sections 14 and 15, at proportionate distance; there is no remaining evidence of the original corner.
	Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:
	<p>T12S R3W 1/4 S15   S14 1996</p>
	Set a steel fence post alongside the corner.
<b>80.810</b>	The corner of sections 10, 11, 14, and 15, monumented with a limestone 15x8x7 inches, firmly set, projecting 10 inches above ground, plainly marked 4 notches on the S and 2 notches on the E edges.
	At the corner point
	Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:
	<p>T12S R3W S10   S11 S15   S14 1996</p>
	Deposit the marked stone alongside the aluminum post.
	Set a steel fence post alongside the corner.
	<hr/> <p>From the corner of sections 11, 12, 13, and 14.</p> <p>S. 89° 54.8' W., between sections 11 and 14.</p> <p>Over rolling land.</p>
<b>40.210</b>	Point for the 1/4 section corner of sections 11 and 14, at proportionate distance; there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W  
1/4     S11  
          S14  
          1996

Set a steel fence post alongside the corner.

**80.420** The corner of sections 10, 11, 14, and 15.

---

N. 0° 13.2' E., between sections 10 and 11.

Over rolling land.

**40.580** Point for the 1/4 section corner of sections 10 and 11, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W  
1/4  
S10 | S11  
1996

Set a steel fence post alongside the corner.

**81.160** The corner of sections 2, 3, 10, and 11, monumented with a porphyry stone, 18x12x5 inches, firmly set, projecting 10 inches above ground, plainly marked 5 notches on the S and 2 notches on the E edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W  
S3 | S2  
S10 | S11  
1996

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the corner of sections 1, 2, 11, and 12.

N. 89° 47.7' W., between sections 2 and 11.

Over rolling land.

**40.095** Point for the 1/4 section corner of sections 2 and 11, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

	T12S R3W
1/4	<u>S2</u>
	S11
	1996

Set a steel fence post alongside the corner.

**80.190** The corner of sections 2, 3, 10, and 11.

---

N. 0° 25.0' W., between sections 2 and 3.

Over rolling land.

**40.240** Point for the 1/4 section corner of sections 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

	T12S R3W
	1/4
S3	S2
	1996

Set a steel fence post alongside the corner.

**80.760** The corner of sections 2, 3, 34, and 35, north boundary, hereinbefore described.

---

From the corner of sections 3, 4, 33, and 34, south boundary, hereinbefore described.

N. 0° 17.3' E., between sections 33 and 34.

Over gentle rolling land.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

40.620

Point for the 1/4 section corner of sections 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W  
1/4  
S33 | S34  
1996

Set a steel fence post alongside the corner.

81.240

The corner of sections 27, 28, 33, and 34, monumented with a limestone, 15x10x7 inches, firmly set, projecting 8 inches above ground, plainly marked 3 notches on the E edge.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W  
S28 | S27  
S33 | S34  
1996

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the corner.

Set a steel fence post alongside the corner.

---

From the corner of sections 26, 27, 34, and 35.

N. 89° 44.8' W., between sections 27 and 34.

Over rolling land.

40.315

Point for the 1/4 section corner of sections 27 and 34, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 14 inches in the ground, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

T12S R3W  
1/4     S27  
         S34  
         1996

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

- Set a steel fence post alongside the corner.
- 80.630** The corner of sections 27, 28, 33, and 34.
- 
- N. 0° 28.3' W., between sections 27 and 28.
- Over rolling land.
- 40.545** Point for the 1/4 section corner of sections 27 and 28, at proportionate distance; there is no remaining evidence of the original corner.
- Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:
- T12S R3W  
1/4  
S28 | S27  
1996
- Set a steel fence post alongside the corner.
- 81.090** Point for the corner of sections 21, 22, 27, and 28, at proportionate distance; there is no remaining evidence of the original corner.
- Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:
- T12S R3W  
S21 | S22  
S28 | S27  
1996
- Set a steel fence post alongside the corner.
- 
- From the corner of sections 22, 23, 26, and 27.
- N. 89° 43.5' W., between sections 22 and 27.
- Over rolling land.
- 40.195** Point for the 1/4 section corner of sections 22 and 27, at proportionate distance; there is no remaining evidence of the original corner.
- Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T12S R3W  
1/4  $\frac{S22}{S27}$   
1996

Set a steel fence post alongside the corner.

**80.390** The corner of sections 21, 22, 27, and 28.

---

N. 0° 01.9' W., between sections 21 and 22.

Over rolling land.

**40.545** Point for the 1/4 section corner of sections 21 and 22, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W  
1/4  
S21 | S22  
1996

Set a steel fence post alongside the corner.

**81.090** The corner of sections 15, 16, 21, and 22, monumented with a limestone, 11x11x10 inches, firmly set, projecting 6 inches above ground, dimly marked.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W  
S16 | S15  
S21 | S22  
1996

Deposit the dimly marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

---

From the corner of sections 14, 15, 22, and 23.

N. 89° 31.8' W., between sections 15 and 22.

Over rolling land.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

40.340

Point for the 1/4 section corner of sections 15 and 22, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

	T12S	R3W
1/4	<u>S15</u>	
	S22	
	1996	

Set a steel fence post alongside the corner.

80.680

The corner of sections 15, 16, 21, and 22.

---

N. 0° 08.8' E., between sections 15 and 16.

Over rolling land.

40.240

The 1/4 section corner of sections 15 and 16, monumented with a limestone, 11x8x6 inches, firmly set, projecting 6 inches above ground, plainly marked 1/4 on the W face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

	T12S	R3W
	1/4	
S16		S15
	1996	

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

---

N. 0° 18.5' E., beginning new measurement.

40.245

The corner of sections 9, 10, 15, and 16, monumented with a limestone, 10x8x6 inches, firmly set and dimly marked, with a scattered mound of stone to the W.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

	T12S	R3W
S9		S10
S16		S15
	1996	

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposit the dimly marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

---

From the corner of sections 10, 11, 14, and 15.

N. 89° 45.5' W., between sections 10 and 15.

Over rolling land.

**40.175** Point for the 1/4 section corner of sections 10 and 15, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W  
1/4        S10  
          S15  
          1996

Set a steel fence post alongside the corner.

Corner is located in old E and W fence line, and 15 ft. W of a wash, which drains SW.

**80.350** The corner of sections 9, 10, 15, and 16.

---

N. 0° 07.8' E., between sections 9 and 10.

Over rolling land.

**40.230** Point for the 1/4 section corner of sections 9 and 10, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W  
1/4  
S9 | S10  
1996

Set a steel fence post alongside the corner.

**80.460** The corner of sections 3, 4, 9, and 10, monumented with a limestone, 15x15x6 inches, firmly set, projecting 10 inches above ground and dimly marked.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W	
S4	S3
S9	S10
1996	

Deposit the dimly marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

---

From the corner of sections 2, 3, 10, and 11.

S. 89° 44.8' W., between sections 3 and 10.

Over rolling land.

**40.240** Point for the 1/4 section corner of sections 3 and 10, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

	T12S R3W	
1/4	S3	S10
	1996	

Set a steel fence post alongside the corner.

**80.480** The corner of sections 3, 4, 9, and 10.

---

N. 0° 07.5' W., between sections 3 and 4.

Over rolling land.

**40.640** Point for the 1/4 section corner of sections 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

	T12S R3W	
	1/4	
S4	S3	
1996		

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set a steel fence post alongside the corner.

**81.160** The corner of sections 3, 4, 33, and 34, north boundary, hereinbefore described.

---

From the corner of sections 4, 5, 32, and 33, south boundary, hereinbefore described..

N. 0° 16.7' E., between sections 32 and 33.

Over rolling land.

**40.550** Point for the 1/4 section corner of sections 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W  
1/4  
S32 | S33  
1996

Set a steel fence post alongside the corner.

**81.100** The corner of sections 28, 29, 32, and 33, monumented with a limestone, 18x15x12 inches, firmly set, projecting 12 inches above ground, plainly marked 1 notch on the S and 4 notches on the E edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground, and in a collar of stone to top, with aluminum cap marked:

T12S R3W  
S29 | S28  
S32 | S33  
1996

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

---

From the corner of sections 27, 28, 33, and 34.

N. 89° 56.7' W., between sections 28 and 33.

Over rolling land.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

**40.545**

Point for the 1/4 section corner of sections 28 and 33, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

	T12S R3W
1/4	<u>S28</u>
	S33
	1996

Set a steel fence post alongside the corner.

**81.090**

The corner of sections 28, 29, 32, and 33.

---

N. 0° 04.0' E., between sections 28 and 29.

Over rolling land.

**40.440**

The 1/4 section corner of sections 28 and 29, monumented with a cedar stake, 4 ft. long, with a sharp pointed end, and dim scribe markings.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

	T12S R3W
	1/4
S29	S28
	1996

Deposit the dimly marked cedar stake alongside the aluminum post.

Set a steel fence post alongside the corner.

---

N. 1° 28.8' W., beginning new measurement.

**39.980**

The corner of sections 20, 21, 28, and 29, monumented with a limestone, 24x12x6 inches, firmly set, projecting 16 inches above ground, plainly marked 2 notches on the S and 4 notches on the E edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T12S R3W  
S20 | S21  
S29 | S28  
1996

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

---

From the corner of sections 21, 22, 27, and 28.

S. 89° 34.4' W., between sections 21 and 28.

Over rolling land.

**40.700** Point for the 1/4 section corner of sections 21 and 28, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

1/4 T12S R3W  
S21  
S28  
1996

Set a steel fence post alongside the corner.

**81.400** The corner of sections 20, 21, 28, and 29.

---

N. 0° 09.0' E., between sections 20 and 21.

Over rolling land.

**40.490** The 1/4 section corner of sections 20 and 21, monumented with a limestone, 15x12x6 inches, firmly set, projecting 10 inches above ground, plainly marked 1/4 on the W face.  
At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W  
1/4  
S20 | S21  
1996

Deposit the marked stone alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set a steel fence post alongside the corner.

---

N. 0° 20.6' E., beginning new measurement.

**40.490** The corner of sections 16, 17, 20, and 21, monumented with a trachyte stone, 18x12x8 inches, firmly set, projecting 10 inches above ground, plainly marked 3 notches on the S and 4 notches on the E edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W	
S17	S16
S20	S21
1996	

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

---

From the corner of sections 15, 16, 21, and 22.

S. 89° 29.7' W., between sections 16 and 21.

Over rolling land.

**40.510** The 1/4 section corner of sections 16 and 21, monumented with a porphyry stone, 13x10x6 inches, firmly set, projecting 10 inches above ground, dimly marked 1/4 on the N face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W	
1/4	S16
	S21
	1996

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

S. 89° 28.7' W., beginning new measurement.

**40.495** The corner of sections 16, 17, 20, and 21.

---

N. 0° 29.0' E., between sections 16 and 17.

Over rolling land.

**40.620** Point for the 1/4 section corner of sections 16 and 17, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W  
1/4  
S17 | S16  
1996

Set a steel fence post alongside the corner.

**81.240** Point for the corner of sections 8, 9, 16, and 17, at proportionate distance, falls on railroad track and cannot be monumented; there is no remaining evidence of the original corner.

---

From the corner of sections 9, 10, 15, and 16.

N. 89° 58.7' W., between sections 9 and 16.

Over rolling land.

**40.305** Point for the 1/4 section corner of sections 9 and 16, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W  
1/4     S9  
          S16  
          1996

Set a steel fence post alongside the corner.

**80.610** The true point for the corner of sections 8, 9, 16, and 17.

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0° 08.7' W., between sections 8 and 9.

Over rolling land.

**40.620** Point for the 1/4 section corner of sections 8 and 9, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W  
1/4  
S8 | S9  
1996

Set a steel fence post alongside the corner.

**81.240** The corner of sections 4, 5, 8, and 9, monumented with a limestone, 16x13x10 inches, firmly set, projecting 10 inches above ground, and dimly marked.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W  
S5 | S4  
S8 | S9  
1996

Deposit the dimly marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

---

From the corner of sections 3, 4, 9, and 10.

N. 89° 25.0' W., between sections 4 and 9.

Over rolling land.

**40.480** Point for the 1/4 section corner of sections 4 and 9, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T12S R3W  
1/4      $\frac{S4}{S9}$   
1996

Set a steel fence post alongside the corner.

**80.960** The corner of sections 4, 5, 8, and 9.

---

N. 0° 07.0' W., between sections 4 and 5.

Over rolling land.

**40.365** The 1/4 section corner of sections 4 and 5, monumented with a sandstone, 12x8x6 inches, firmly set, projecting 6 inches above ground, plainly marked 1/4 on the W face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W  
1/4  
S5 | S4  
1996

Deposit the marked stone alongside aluminum post.

Set a steel fence post alongside the corner.

---

N. 0° 15.3' E., beginning new measurement.

**40.255** The corner of sections 4, 5, 32, and 33, north boundary, hereinbefore described.

---

From the corner of sections 5, 6, 31, and 32, south boundary, hereinbefore described.

N. 0° 04.9' E., between sections 31 and 32.

Over rolling land.

**40.365** The 1/4 section corner of sections 31 and 32, monumented with a quartzite stone 14x10x6 inches, firmly set and dimly marked 1/4 on W face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T12S R3W  
1/4  
S31 | S32  
1996

Deposit the dimly marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

---

N. 0° 01.9' E., beginning new measurement.

**40.465** The corner of sections 29, 30, 31, and 32, monumented with a quartzite stone 14x10x6 inches, set and dimly marked 1 notch on the S edge.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W  
S30 | S29  
S31 | S32  
1996

Deposit the dimly marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

---

From the corner of sections 28, 29, 32, and 33.

N. 89° 59.7' W., between sections 29 and 32.

Over rolling land.

**40.625** The 1/4 section corner of sections 29 and 32, determined from the original bearing tree

A cedar, 20 inches diameter, bears west, 27 links distance,  
dimly marked S on a nearly healed over blaze.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W  
1/4     S29  
         S32  
         1996

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a steel fence post alongside the corner.

---

S. 89° 54.9' W., beginning new measurement.

**20.260** Point for the W 1/16 section corner of sections 29 and 32.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

W 1/16      $\frac{S29}{S32}$   
                  1996

Set a steel fence post alongside the corner.

**40.520** The corner of sections 29, 30, 31, and 32.

---

N. 89° 51.4' W., between sections 30 and 31.

Over rolling land.

**40.300** Point for the 1/4 section corner of sections 30 and 31, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

                  T12S R3W  
1/4      $\frac{S30}{S31}$   
                  1997

Set a steel fence post alongside the corner.

**80.880** The corner of sections 30 and 31 only, west boundary, monumented with an iron post, 2 inches diameter, firmly set, projecting 8 inches above ground, with brass cap marked as described in the official record of the 1911 resurvey of the east boundary of T. 12 S., R. 4 W.

---

From the corner of sections 29, 30, 31, and 32.

N. 0° 32.1' W., between sections 29 and 30.

Over rolling land.

**20.155** Point for the S 1/16 section corner of sections 29 and 30.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Corner point not monumented.

- 40.310** Point for the 1/4 section corner of sections 29 and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W  
1/4  
S30 | S29  
1996

Set a steel fence post alongside the corner.

- 60.465** Point for the N 1/16 section corner of sections 29 and 30.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

N 1/16  
S30 | S29  
1996

Set a steel fence post alongside the corner.

- 80.620** The corner of sections 19, 20, 29, and 30, monumented with a limestone, 14x10x8 inches, firmly set, projecting 6 inches above ground, plainly marked 2 notches on the S and 5 notches on the E edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, and in a collar of stone, with aluminum cap marked:

T12S R3W  
S19 | S20  
S30 | S29  
1996

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

Corner is located 10 links E of dirt road, which bears N and S.

---

From the corner of sections 20, 21, 28, and 29.

N. 89° 53.6' W., between sections 20 and 29.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Over rolling land.

**40.360** The 1/4 section corner of sections 20 and 29, monumented with a sandstone 12x10x8 inches, firmly set, projecting 8 inches above ground, dimly marked 1/4 on the N face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, and in a collar of stone, with aluminum cap marked:

	T12S R3W
1/4	<u>S20</u>
	S29
	1996

Deposit the dimly marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

---

N. 89° 53.1' W., beginning new measurement.

**40.535** The corner of sections 19, 20, 29, and 30.

---

N. 89° 51.9' W., between sections 19 and 30.

Over rolling land.

**39.960** Point for the 1/4 section corner of sections 19 and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

	T12S R3W
1/4	<u>S19</u>
	S30
	1996

Set a steel fence post alongside the corner.

**59.940** Point for the W 1/16 section corner of sections 19 and 30.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

W 1/16	<u>S19</u>
	S30
	1996

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set a steel fence post alongside the corner.

**80.280** The corner of sections 19 and 30 only, west boundary, hereinbefore described.

---

From the corner of sections 19, 20, 29, and 30.

N. 0° 06.4' E., between sections 19 and 20.

Over rolling land.

**40.350** Point for the 1/4 section corner of sections 19 and 20, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground,, with aluminum cap marked:

T12S R3W  
1/4  
S19 | S20  
1996

Set a steel fence post alongside the corner.

**80.700** The corner of sections 17, 18, 19, and 20, monumented with a quartzite stone 14x10x6 inches, firmly set, projecting 10 inches above ground, dimly marked 3 notches on the S edge.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W  
S18 | S17  
S19 | S20  
1996

Deposit the dimly marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

---

From the corner of sections 16, 17, 20, and 21.

N. 89° 57.2' W., between sections 17 and 20.

Over rolling land.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

40.475

The 1/4 section corner of sections 17 and 20, monumented with a sandstone, 12x12x6 inches, firmly set, projecting 6 inches above ground, dimly marked 1/4 on the N face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

	T12S R3W
1/4	<u>S17</u>
	S20
	1996

Deposit the dimly marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

---

S. 89° 48.2' W., beginning new measurement.

20.300

Point for the W 1/16 section corner of sections 17 and 20.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

	W 1/16	<u>S17</u>
		S20
		1996

Set a steel fence post alongside the corner.

40.600

The corner of sections 17, 18, 19, and 20.

---

N. 89° 37.5' W., between sections 18 and 19.

Over rolling land.

39.880

Point for the 1/4 section corner of sections 18 and 19, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

	T12S R3W
1/4	<u>S18</u>
	S19
	1996

Set a steel fence post alongside the corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS****80.160**

The corner of sections 18 and 19 only, west boundary, monumented with an iron post, 2 inches diameter, firmly set, projecting 8 inches above ground, with brass cap marked as described in the official record of the 1911 resurvey of the east boundary of T. 12 S., R. 4 W.

---

From the corner of sections 17, 18, 19, and 20.

N. 1° 03.3' E., between sections 17 and 18.

Over rolling land.

**40.605**

The 1/4 section corner of sections 17 and 18, monumented with a sandstone 12x8x6 inches, firmly set, projecting 6 inches above ground, plainly marked 1/4 on the W face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W  
1/4  
S18 | S17  
1996

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

---

N. 0° 44.7' E., beginning new measurement.

**40.670**

Point for the corner of sections 7, 8, 17, and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W  
S7 | S8  
S18 | S17  
1996

Set a steel fence post alongside the corner.

---

From the true corner for the corner of sections 8, 9, 16, and 17.

S. 89° 56.5' W., between sections 8 and 17.


DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Over rolling land.

**1.000** Point selected for the witness corner of sections 8, 9, 16, and 17.


Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:



Set a steel fence post alongside the corner.

**20.120** Point for the E 1/16 section corner of sections 8 and 17.


Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:



Set a steel fence post alongside the corner.

**40.240** Point for the 1/4 section corner of sections 8 and 17, at proportionate distance; there is no remaining evidence of the original corner.


Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:



Set a steel fence post alongside the corner.

**60.360** Point for the W 1/16 section corner of sections 8 and 17.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:



Set a steel fence post alongside the corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

**80.480**

The corner of sections 7, 8, 17, and 18.

---

N. 89° 22.5' W., between sections 7 and 18.

Over rolling land.

**40.490**

The 1/4 section corner of sections 7 and 18, monumented with a limestone, 16x14x10 inches, firmly set, projecting 10 inches above ground, plainly marked 1/4 on the N face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

	T12S R3W
1/4	<u>S7</u>
	S18
	1996

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

---

S. 89° 58.0' W., beginning new measurement.

**40.765**

The corner of sections 7 and 18 only, west boundary, monumented with an iron post, 2 inches diameter, firmly set, projecting 8 inches above ground, with brass cap marked as described in the 1911 resurvey of the east boundary of T. 12 S., R. 4 W.

---

From the corner of sections 7, 8, 17, and 18.

N. 0° 28.3' W., between sections 7 and 8.

Over rolling land.

**40.670**

The 1/4 section corner of sections 7 and 8, monumented with a quartzite stone 12x12x6 inches, firmly set, projecting 6 inches above ground, marked 1/4 on the W face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T12S R3W  
1/4  
S7 | S8  
1996

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

---

North, beginning new measurement.

**40.480** Point for the corner of sections 5, 6, 7, and 8, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W  
S6 | S5  
S7 | S8  
1996

Set a steel fence post alongside the corner.

---

From the corner of sections 4, 5, 8, and 9.

S. 89° 53.0' W., between sections 5 and 8.

Over rolling land.

**20.145** Point for the E 1/16 section corner of sections 5 and 8.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

E 1/16 S5  
S8  
1996

Set a steel fence post alongside the corner.

**40.290** Point for the 1/4 section corner of sections 5 and 8, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T12S R3W  
1/4      $\frac{S5}{S8}$   
1996

Set a steel fence post alongside the corner.

**60.435** Point for the W 1/16 section corner of sections 5 and 8.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

W 1/16      $\frac{S5}{S8}$   
1996

Set a steel fence post alongside the corner.

**80.580** The corner of sections 5, 6, 7, and 8.

---

N. 89° 36.3' W., between sections 6 and 7.

Over rolling land.

**40.420** The 1/4 section corner of sections 6 and 7, monumented with a quartzite stone, 8x8x6 inches, firmly set, projecting 4 inches above ground, plainly marked 1/4 on the N face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W  
1/4      $\frac{S6}{S7}$   
1996

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

---

S. 89° 57.5' W., beginning new measurement.

**40.380** The corner of sections 6 and 7 only, west boundary, monumented with an iron post, 2 inches diameter, firmly set, projecting 8 inches above ground, with brass cap marked as described in the official record of the 1911 resurvey of the east boundary of T. 12 S., R. 4 W.

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the corner of sections 5, 6, 7, and 8

N. 0° 04.6' W., between sections 5 and 6.

Over rolling land.

**20.240** Point for the S 1/16 section corner of sections 5 and 6.

Corner point not monumented.

**40.480** Point for the 1/4 section corner of sections 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W  
1/4  
S6 | S5  
1996

Set a steel fence post alongside the corner.

**80.800** The corner of sections 5, 6, 31, and 32, north boundary, hereinbefore described.

---

The Subdivision of Section 5,  
T. 12 S., R. 3 W., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 5 and 8.

N. 0° 00.6' W., on the N - S center line of section 5.

Over rolling land.

**20.210** Point for the center S 1/16 section corner of section 5.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

C  
S 1/16 | S5  
C  
1996

Set a steel fence post alongside the corner.

Corner is located 3 ft. E of old N and S fence line.

THE SUBDIVISION OF SECTION 5,  
T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

**40.420**

Point for the center 1/4 section corner of section 5, at intersection with the E - W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W  
C 1/4 S5  
1996

Set a steel fence post alongside the corner.

**80.710**

The 1/4 section corner of sections 5 and 32, north boundary, hereinbefore described.

---

From the 1/4 section corner of sections 4 and 5.

S. 89° 56.7' W., on the E - W center line of section 5.

Over rolling land.

**20.105**

Point for the center E 1/16 section corner of section 5.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

C  $\frac{E\ 1/16}{S5}$  C  
1996

Set a steel fence post alongside the corner.

**40.210**

The center 1/4 section corner of section 5.

**60.375**

Point for the center W 1/16 section corner of section 5.

Corner point not monumented.

**80.540**

The 1/4 section corner of sections 5 and 6.

---

From the E 1/16 section corner of sections 5 and 8.

N. 0° 03.8' W., on the N - S center line of the SE 1/4 of section 5.

Over rolling land.

**40.390**

The center E 1/16 section corner of section 5.

---

THE SUBDIVISION OF SECTION 5,  
T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the W 1/16 section corner of sections 5 and 8.

N. 0° 02.6' W., on the N - S center line of the SW 1/4 of section 5.

Over rolling land.

**20.225** Point for the SW 1/16 section corner of section 5, at intersection with the E - W center line, of the SW 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

SW 1/16 S5  
1996

Set a steel fence post alongside the corner.

**40.450** Point for the center W 1/16 section corner of section 5.

---

From the center S 1/16 section corner of section 5.

S. 89° 54.8' W., on the E - W center line of the SW 1/4 of section 5.

Over rolling land.

**20.155** The SW 1/16 section corner of section 5.

**40.310** Point for the S 1/16 section corner of sections 5 and 6.

---

The Subdivision of Section 8,  
T. 12 S., R. 3 W., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 8 and 17.

N. 0° 11.0' W., on the N - S center line of section 8.

Over rolling land.

**40.645** Point for the center 1/4 section corner of section 8, at intersection with the E - W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 8,  
T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

T12S R3W  
C 1/4 S8  
1996

Set a steel fence post alongside the corner.

**81.190** The 1/4 section corner of sections 5 and 8.

---

From the 1/4 section corner of sections 8 and 9.

S. 89° 58.7' W., on the E - W center line of section 8.

Over rolling land.

**20.130** Point for the center E 1/16 section corner of section 8.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

C  $\frac{E\ 1/16}{S8}$  C  
1996

Set a steel fence post alongside the corner.

**40.260** The center 1/4 section corner of section 8.

**60.480** Point for the center W 1/16 section corner of section 8.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

C  $\frac{W\ 1/16}{S8}$  C  
1996

Set a steel fence post alongside the corner.

**80.700** The 1/4 section corner of sections 7 and 8.

---

From the center E 1/16 section corner of section 8.

N. 0° 09.9' W., on the N - S center line of the NE 1/4 of section 8.

THE SUBDIVISION OF SECTION 8,  
T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Over rolling land.

**40.585** The E 1/16 section corner of sections 5 and 8.

---

From the E 1/16 section corner of sections 8 and 17.

N. 0° 09.9' W., on the N - S center line of the SE 1/4 of section 8.

Over rolling land.

**40.630** The center E 1/16 section corner of section 8.

---

From the W 1/16 section corner of sections 8 and 17.

N. 0° 19.6' W., on the N - S center line of the SW 1/4 of section 8.

Over rolling land.

**40.655** The center W 1/16 section corner of section 8.

---

N. 0° 05.5' W., on the N - S center line of the NW 1/4 of section 8.

Over rolling land.

**40.510** The W 1/16 section corner of sections 5 and 8.

---

The Subdivision of Section 17,  
T. 12 S., R. 3 W., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 17 and 20.

N. 0° 38.8' E., on the N - S center line of section 17.

Over rolling land.

**40.535** Point for the center 1/4 section corner of section 17, at intersection with the E - W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W  
C 1/4 S17  
1996

THE SUBDIVISION OF SECTION 17,  
T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set a steel fence post alongside the corner.

**81.180** The 1/4 section corner of sections 8 and 17.

---

From the 1/4 section corner of sections 16 and 17.

S. 89° 54.5' W., on the E - W center line of section 17.

Over rolling land.

**40.355** The center 1/4 section corner of section 17.

**60.510** Point for the center W 1/16 section corner of section 17.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

$$C \frac{W \ 1/16}{S17} C$$

1996

Set a steel fence post alongside the corner.

**80.665** The 1/4 section corner of sections 17 and 18.

---

From the W 1/16 section corner of sections 17 and 20.

N. 0° 51.1' E., on the N - S center line of the SW 1/4 of section 17.

Over rolling land.

**40.570** The center W 1/16 section corner of section 17.

---

The Subdivision of Section 29,  
T. 12 S., R. 3 W., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 29 and 32.

N. 0° 31.5' W., on the N - S center line of section 29.

Over rolling land.

**12.170** Intersect line 1 - 2, King Mill Site No. 1, Mineral Survey No. 7270.

THE SUBDIVISION OF SECTION 29,  
T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

- 20.180** Point for the center S 1/16 section corner of section 29.  
Corner point not monumented.
- 26.305** Intersect line 3 - 4, King Mill Site No. 2, Mineral Survey No. 7270.
- 40.360** Point for the center 1/4 section corner of section 29, at intersection with the E - W center line.  
Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:  

$$\begin{array}{c} \text{T12S R3W} \\ \text{C } 1/4 \quad \text{S29} \\ 1996 \end{array}$$
Set a steel fence post alongside the corner.
- 60.420** Point for the center N 1/16 section corner of section 29.  
Set an a aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:  

$$\begin{array}{c} \text{C} \\ \text{N } 1/16 \quad | \quad \text{S29} \\ \text{C} \\ 1996 \end{array}$$
Set a steel fence post alongside the corner.
- 80.480** The 1/4 section corner of sections 20 and 29.  


---

From the 1/4 section corner of sections 28 and 29.  
S. 89° 52.0' W., on the E - W center line of section 29.  
Over rolling land.
- 41.030** The center 1/4 section corner of section 29.
- 61.295** Point for the center W 1/16 section corner of section 29.  
Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:  

$$\text{C } \frac{\text{W } 1/16}{\text{S29}} \text{ C} \\ 1996$$

THE SUBDIVISION OF SECTION 29,  
T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

- Set a steel fence post alongside the corner.
- 81.560** The 1/4 section corner of sections 29 and 30.
- 
- From the W 1/16 section corner of sections 29 and 32.
- N. 0° 31.8' W., on the N - S center line of the SW 1/4 of section 29.
- Over rolling land.
- 20.170** Point for the SW 1/16 section corner of section 29, at intersection with the E - W center line.
- Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:
- SW 1/16 S29  
1996
- Set a steel fence post alongside the corner.
- 40.340** The center W 1/16 section corner of section 29.
- 
- From a point for the center S 1/16 section corner of section 29.
- S. 89° 53.5' W., on the E - W center line of the SW 1/4 of section 29.
- Over rolling land.
- 7.665** Intersect line 2 - 3, King Mill Site No. 2, Mineral Survey No. 7270.
- 20.265** The SW 1/16 section corner of section of section 29.
- 40.530** Point for the S 1/16 section corner of sections 29 and 30; not monumented.
- 
- From the center N 1/16 section corner of section 29.
- S. 89° 59.5' W., along the E - W center line of the NW 1/4 of section 29.
- Over rolling land.
- 40.530** The N 1/16 section corner of sections 29 and 30.
-

THE SUBDIVISION OF SECTION 30,  
T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

The Subdivisional Lines of Section 30,  
T. 12 S., R. 3 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 30 and 31.

N. 0° 18.5' W., on the N - S center line of section 30. Over rolling land.

**40.270** Point for the center 1/4 section corner of section 30, at intersection with the E - W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T12S R3W  
C 1/4 S30  
1996

Set a steel fence post alongside the corner.

**60.440** Point for the center N 1/16 section corner of section 30.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

C  
N 1/16 | S30  
C  
1996

Set a steel fence post alongside the corner.

**80.610** The 1/4 section corner of sections 19 and 30.

From the 1/4 section corner of sections 29 and 30.

N. 89° 55.0' W., on the E - W center line of section 30.

Over rolling land.

**40.130** The center 1/4 section corner of section 30.

**60.170** Point for the center W 1/16 section corner of section 30.

Corner point not monumented.

**80.530** The 1/4 section corner of section 30 only, west boundary, hereinbefore described.

THE SUBDIVISION OF SECTION 30,  
T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the N 1/16 section corner of sections 29 and 30.

N. 89° 53.5' W., on the E - W center line of the NE 1/4 of section 30.

Over rolling land.

**40.045** The center N 1/16 section corner of section 30.

---

From a point for the center W 1/16 section corner of section 30.

N. 0° 13.8' W., on the N - S center line of the NW 1/4 of section 30.

Over rolling land.

**20.180** Point for the NW 1/16 section corner of section 30, at intersection with the E - W center line, of the NW 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

NW 1/16 S30  
1996

Set a steel fence post alongside the corner.

**40.360** The W 1/16 section corner of sections 19 and 30.

---

From the center N 1/16 section corner of section 30.

N. 89° 53.5' W., on the E - W center line of the NW 1/4 of section 30.

Over rolling land.

**20.010** The NW 1/16 section corner of section 30.

**40.360** Point for the N 1/16 section corner of section 30 only, west boundary, hereinbefore described.

---

Dependent Resurvey of Mineral Survey No. 7270,  
T.12 S., R. 3 W., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by  
Andrew R. Shelton in 1956

---

DEPENDENT RESURVEY OF MINERAL SURVEY No. 7270,  
T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

King Mill Site (7270)

From corner No. 1 of King Mill Site, identical with corner No. 2, of the King Mill Site No. 1, of this survey, monumented with a galvanized post, 3/4 inches diameter, firmly set, projecting 10 inches above ground, with galvanized cap marked as described in the official record of the 1956 survey of Mineral Survey No. 7270.

S. 88° 33.0' W., along line 1 - 2.

- 7.130** Corner No. 2, of this survey, monumented with a galvanized post, 3/4 inches diameter, firmly set, projecting 10 inches above ground, with galvanized cap marked as described in the official record of the 1956 survey of Mineral Survey No. 7270.

Thence, N. 20° 01.5' E., along line 2 - 3.

- 7.700** Corner No. 3, of this survey, monumented with a galvanized post, 3/4 inches diameter, firmly set, projecting 10 inches above ground, with galvanized cap marked as described in the official record of the 1956 survey of Mineral Survey No. 7270.

Thence, N. 89° 55.7' E., along line 3 - 4.

- 1.610** Corner No. 2, King Mill Site No. 2, of this survey, monumented with a galvanized post, 3/4 inches diameter, firmly set, projecting 10 inches above ground, with galvanized cap marked as described in the official record of the 1956 survey of Mineral Survey No. 7270.

King Mill Site No. 2 (7270)

Thence, N. 20° 03.0' E., along line 2 - 3.

- 1.010** Intersect the E - W center line of the SW 1/4 of section 29.
- 7.530** Point for Corner No. 3, at proportionate distance based on the Grant Boundary Method; there is no remaining evidence of the original corner.

Set a steel fence post for the corner point.

Thence, N. 89° 53.0' E., along line 3 - 4.

- 5.370** Intersect the N - S center line of section 29.
- 7.065** Point for Corner No. 4, identical with Corner No. 2, King Mill Site No. 3, at proportionate distance; there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 7270,  
T. 12 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set a steel fence post for the corner point.

---

King Mill Site No. 3 (7270)

Thence, N. 89° 53.0' E., along line 2 - 3.

- 7.065** Corner No. 3, King Mill Site No. 3, of this same survey, monumented with a galvanized post, 3/4 inches diameter, firmly set, projecting 10 inches above ground, with galvanized cap marked as described in the official record of the 1956 survey of Mineral Survey No. 7270.
- 

Thence, S. 20° 00.7' W., along line 3 - 4.

- 7.530** Corner No. 4, King Mill Site No. 3, of this same survey, monumented with a galvanized post, 3/4 inches diameter, firmly set, projecting 8 inches above ground, with galvanized cap marked as described in the official record of the 1956 survey of Mineral Survey No. 7270.
- 

Thence, N. 89° 58.3' W., along line 4 - 1.

- 1.615** Corner No. 4, King Mill Site No. 1, of this same survey, monumented with a galvanized post, 3/4 inches diameter, firmly set, projecting 8 inches above ground, with galvanized cap marked as described in the official record of the 1956 survey of Mineral Survey No. 7270.
- 

King Mill Site No. 1 (7270)

Thence, S. 20° 01.8' W., along line 4 - 1.

- 7.400** Point selected for the witness corner of Corner No.1, King Mill Site No. 1.

Set a steel fence post for the corner point

- 7.530** Point for Corner No. 1, King Mill Site No. 1, at proportionate distance, falls in bottom of drainage and is unsafe to monument.
- 

Thence, S. 89° 54.8' W., along line 1 - 2.

- 1.865** Intersect the N - S center line of Section 29.

- 7.070** Corner No. 2, King Mill Site No. 1, identical with Corner No. 1, King Mill Site.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD ASSISTANTS**

---

Name	Capacity
Steve Oatman	Survey Technician
Nathan James	Surveying Aid
Judd Beagley	Surveying Aid
Garrett Snow	Surveying Aid
Dave Harris (BOR)	Survey Technician
Tracey Thompson (BOR)	Survey Technician

## CERTIFICATE OF SURVEY

I, *Jerry L. Thomas, Cadastral Surveyor*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *1st day of August, 1996*, I have *dependently resurveyed the north boundary, a portion of the south and west boundaries, a portion of the subdivisional lines, and the subdivision of sections 5, 8, 17, 29, and 30, and Mineral Survey No. 7270, in Township 12 South, Range 3 West,*

of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

January 20 1999

Date

Jerry L. Thomas

(Cadastral Surveyor)

\_\_\_\_\_

Date

\_\_\_\_\_

(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of the dependent resurvey of the north boundary, a portion of the south and west boundaries, a portion of the subdivisional lines, the subdivision of sections 5, 8, 17, 29, and 30, and Mineral Survey No. 7270,, in Township 12 South, Range 3 West, Salt Lake Meridian, Utah,*

executed by *Jerry L. Thomas, Cadastral Surveyor*

Ohaving been critically examined and found correct, are hereby approved.

May 21, 1999

Date

Daniel W. Webb

(Chief Cadastral Surveyor for Utah)