

218

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

# FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

PORTIONS OF

THE NORTH BOUNDARY

( FIFTH STANDARD PARALLEL SOUTH )

THE WEST BOUNDARY

AND

SUBDIVISIONAL LINES

IN

TOWNSHIP 26 SOUTH, RANGE 7 WEST

OF THE SALT LAKE MERIDIAN  
IN THE STATE OF UTAH

EXECUTED BY

*Larry V. Judd*  
*Cadastral Surveyor*

Under special instructions dated *August 15, 1996*, approved August 23, 1996, which provided for the surveys included under Group Number 854, and assignment instructions dated *August 23, 1996*

Survey commenced *September 3, 1996*  
Survey completed *September 26, 1996*

INDEX DIAGRAM

Township 26 South, Range 7 West

	4		3		2					
9	6	29	5	20	4	13	3		2	1
	28		28		19					
8	7	26	8	18	9	12	10		11	12
	26		25		17					
7	18	24	17	16	16	11	15		14	13
	24		23		16					
6	19	22	20	15	21	10	22		23	24
	21		20		14					
	30		29		28		27		26	25
	31		32		33		34		35	36

## TOWNSHIP 26 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

The following field notes describe the dependent resurvey of portions of the north boundary (Fifth Standard Parallel South), the west boundary, and subdivisional lines in Township 26 South, Range 7 West, Salt Lake Meridian, Utah.

**History of Surveys**

Surveyed by		Retr. or Resurveyed by		
<b>NORTH BOUNDARY ( Fifth Standard Parallel South )</b>				
All	J. Bausman	1869		
All			Page & Erwin	1901
Portion			Miller & Byergo	1919
<b>SOUTH BOUNDARY</b>				
Portion	J. Bausman	1869		
Portion	Page & Erwin	1901		
All			C.P. Sylvester	1969
<b>EAST BOUNDARY ( Guide Meridian )</b>				
Portion	J. Bausman	1869		
All	Page & Erwin	1900	Page & Erwin	1900
<b>WEST BOUNDARY</b>				
All	Page & Erwin	1901		
<b>SUBDIVISION</b>				
Portion	F. Dickert	1870		
Portion	J. Bausman	1870		
Portion	Page & Erwin	1901	Page & Erwin	1901

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 854, Utah, dated August 15, 1996.

The directions of lines were determined by references to true meridians established on line by hour angle observations of the sun and Polaris. The lines were carried forward by sustained angulations, being supplemented by other observations taken throughout the progress of the survey. Distances were determined by electronic measurement.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. The retracement data were thoroughly verified and only the true line notes are given herein.

## TOWNSHIP 26 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

The geographic position of the corner of sections 20, 21, 28, and 29, as determined by a tie made to the U.S. Coast and Geodetic Survey triangulation station "PINEY" is as follows:

Latitude 38° 31' 37.21" N.      Longitude 112° 39' 19.29" W.  
N.A.D. 1927.

The mean magnetic declination as projected from the U.S. Geological Survey Magnetic Declination Map of 1990 is: 13 1/2° East.

---

Dependent Resurvey of a Portion of the North Boundary  
(Fifth Standard Parallel South),  
T. 26 S., R. 7 W., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by  
J. Bausman in 1869 and the Resurvey Executed by Page & Erwin  
in 1901 and the Resurvey Executed by Miller & Byergo in 1919

---

Beginning at the standard corner of sections 33 and 34, Township 25 South, Range 7 West, monumented with an iron post, 2 inches diameter, firmly set, projecting 12 inches above ground, with brass cap marked as described in the official record of the resurvey by H.W. Miller and W. Byergo in 1919, and with a mound of stone, 4 ft. base by 2 ft. high, N of the corner.

N. 89°59.3' W., on the south boundary of section 33, T. 25 S., R. 7 W.

**4.342** The closing corner of sections 3 and 4, T. 26 S., R. 7 W., monumented with a lava stone, 18x12x6 inches, firmly set, plainly marked with 3 grooves on the E and 3 grooves on the W edges, and CC on the S face, with a large mound of stone to the S.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T25S  
CC  
-----  
S4 | S3  
T26S R7W  
1996

Buried the marked rock alongside the aluminum post.

Raise a mound of stone, 5 ft. base by 3 ft. high, S of the corner.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
 (FIFTH STANDARD PARALLEL SOUTH),  
 T. 26 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

The corner falls on a gradual, easterly slope in dense juniper.

**40.011** The standard 1/4 section corner of section 33, T. 25 S., R. 7 W., monumented with an iron post, 1 inch diameter, firmly set, projecting 8 inches, above ground, with brass cap marked as described in the official record of the resurvey by H.W. Miller and W. Byergo in 1919.

The corner falls on flat, rocky ground in burn area.

---

N. 89°58.0' W., beginning new measurement.

**4.317** Point for the 1/4 section corner of section 4 only, T. 26 S., R. 7 W., at midpoint between closing corners; not monumented.

**40.004** The standard corner of sections 32 and 33, T. 25 S., R. 7 W., monumented with an iron post, 2 inches, diameter, firmly set in a mound of stone, 4 ft. base, to top of brass cap marked as described in the official record of the resurvey by H.W. Miller and W. Byergo in 1919.

The corner falls on a ridge, bears NW and SE, in burn area.

---

N. 89°57.7' W., on the south boundary of section 32, T. 25 S., R. 7 W.

**4.300** The closing corner of sections 4 and 5, T. 26 S., R. 7 W., monumented with a lava stone, 17x10x6 inches, firmly set in a scattered mound of stone, plainly marked with 4 grooves on the E and 2 grooves on the W edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 10 inches in the ground to bedrock, set in a mound of stone, 4 ft. base to the top of aluminum cap marked:

T25S	
CC	
S5	S4
T26S R7W	
1996	

Buried the marked stone alongside the aluminum post.

The corner falls on a gradual SW, slope in burn area.

**40.103** The standard 1/4 section corner of section 32, T. 25 S., R. 7 W., monumented with an iron post, 1 inch diameter, firmly set in a mound of stone, with brass cap marked as described in the official record of the resurvey by H.W. Miller and W. Byergo in 1919.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
(FIFTH STANDARD PARALLEL SOUTH),  
T. 26 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

The corner falls on a small flat bench.

---

N. 89°51.2' W., beginning new measurement.

**4.287** Point for the 1/4 section corner of section 5 only, T. 26 S., R. 7 W., at midpoint between closing corners; not monumented.

**40.074** The standard corner of sections 31 and 32, T. 25 S., R. 7 W., monumented with an iron post, 2 inches, diameter, firmly set, projecting 12 inches, above ground, with brass cap marked as described in the official record of the resurvey by H.W Miller and W. Byergo in 1919.

The corner falls on flat ground in burn area.

---

S. 89°54.3' W., on the south boundary of section 31, T. 25 S., R. 7 W.

**4.303** The closing corner of sections 5 and 6, T. 26 S., R. 7 W., monumented with a lava stone, 16x10x6 inches, firmly set, plainly marked CC on the S face, 5 grooves on the E and 1 on the W faces, with a mound of stone to the S.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T25S	
CC	
S6	S5
T26S R7W	
1996	

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 4 ft. base by 2 ft. high, S of the corner.

The corner falls on open, flat ground in burn area.

**40.127** The standard 1/4 section corner of section 31, T. 25 S., R. 7 W., monumented with an iron post, 1 inch diameter, firmly set in a mound of stone, 5 ft. base, to top of brass cap marked as described in the official record of the resurvey by H.W. Miller and W. Byergo in 1919.

Set a steel fence post alongside.

The corner falls on a rocky, westerly slope in burn area.

---

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
(FIFTH STANDARD PARALLEL SOUTH),  
T. 26 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

N. 89°45.9' W., beginning new measurement.

**4.259** Point for the 1/4 section corner of section 6 only, T. 26 S., R. 7 W., at proportionate distance between the closing corner of sections 5 and 6, T. 26 S., R. 7 W., and the NW corner of T. 26 S., R. 7 W.; not monumented.

**40.051** The SW corner of section 31, T. 25 S., R. 7 W., monumented with an iron post, 3 inches diameter, firmly set, projecting 8 inches, above ground with a scattered mound to the W, and with brass cap marked as described in the official record of resurvey by H.W. Miller and W. Byergo in 1919.

N. 89° 14.9' W., on the north boundary of section 6.

**1.376** The closing corner of sections 1 and 6, T. 26 S., Rs. 7 and 8 W., monumented with a lava stone, 24x12x8 inches, firmly set, plainly marked CC on the S face and 6x6x6 notches on different edges, and with a scattered mound to the S.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

	S6
R8W	R7W
	T26S
	1996

Buried the marked stone, alongside the aluminum post.

Raise a mound of stone, 3 ft. base, by 2 ft. high, S of the corner.

This corner will now function as the NW corner of T. 26 S., R. 7 W.

The corner falls on flat, open ground in burn area.

---

Dependent Resurvey of a Portion of the West Boundary,  
T. 26 S., R. 7 W., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by  
H.D. Page and H. Erwin, Deputy Surveyors in 1901

---

From the corner of sections 19, 24, 25, and 30, on the west boundary of the township, monumented with a lava stone, 20x10x6 inches, firmly set and plainly marked with 2 notches on the S edge and 4 notches on the N edge, with a scattered mound of stone to the W.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
T. 26 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T26S	
R8W	R7W
<u>S24</u>	<u>S19</u>
S25	S30
1996	

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 5 ft. base by 2 ft. high, W of the corner.

The corner falls on a gradual, NE slope in dense juniper and pinon.

N. 0°03.9' W., between sections 19 and 24.

**40.023** The 1/4 section corner of sections 19 and 24, monumented with a lava stone, 20x8x6 inches, firmly set, dimly marked 1/4 on the W face, with a mound of stone to the W (record, marked 1/4 S24 on W, 19 on E faces.).

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T26S	
R8W	R7W
1/4	
<u>S24</u>	<u>S19</u>
1996	

Buried the marked stone alongside the aluminum post.

Raise a mound of stone 3 ft. base, by 2 ft. high, west of the corner.

The corner falls on open, flat ground in burn area.

N. 0°04.0' W., beginning new measurement.

**40.066** The corner of sections 13, 18, 19, and 24, monumented with a lava stone, 12x8x6 inches, firmly set, plainly marked with 3 notches on the S and 3 notches on the N edges (record, 15x10x10 inches, mound of stone, 2 ft. base, 1 1/2 ft. high, west of corner).

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
T. 26 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T26S	
R8W	R7W
S13	S18
S24	S19
1996	

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base by 2 ft. high, west of the corner.

The corner falls on a rocky ridge on a gradual, NW slope.

N. 0°02.9' E., between sections 13 and 18.

**40.109** The 1/4 section corner of sections 13 and 18, monumented with a lava stone, 14x14x6 inches, firmly set, plainly marked 1/4 on the W face, with a scattered mound of stone to the W (record, 14x8x6 inches, marked 1/4 S13 on W, 18 on E faces.).

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 14 inches in the ground, set in a mound of stone, 3 ft. base, to top of aluminum cap marked:

T26S	
R8W	R7W
1/4	
S13	S18
1996	

Buried the marked stone alongside the aluminum post.

The corner falls on a gradual, southerly slope.

N. 0°05.1' W., beginning new measurement.

**39.977** The corner of sections 7, 12, 13, and 18, monumented with a lava stone, 24x16x4 inches, firmly set, plainly marked with 4 notches on the S and 2 notches on the N edges, with a mound of stone to the W.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
T. 26 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked:

T26S	
R8W R7W	
S12	S7
S13	S18
1996	

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 4 ft. base by 4 ft. high, west of the corner

The corner falls 30 ft. N of a dirt trail road, 7 ft. wide, bears N. 75° W., and S. 75° E.

---

N. 0°06.7' W., between sections 7 and 12.

**40.080** The 1/4 section corner of sections 7 and 12, monumented with a lava stone, 20x16x6 inches, firmly set, plainly marked 1/4 on the W face, with a mound of stone to the W (record, 16x10x4 inches, marked 1/4 S12 on W, 7 on E faces.).

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T26S	
R8W R7W	
1/4	
S12	S7
1996	

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 4 ft. base by 3 ft. high, W of the corner.

The corner falls on a gradual, open, NW slope in burn area.

---

N. 0°12.2' W., beginning new measurement.

**40.206** The corner of sections 1, 6, 7, and 12, monumented with a lava stone, 18x10x8 inches, firmly set, plainly marked with 2 notches on the N and 4 notches on the S edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 4 inches in the ground, set in a mound of stone, 5 ft. base, to top of aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
T. 26 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T26S  
R8W R7W  
S1 | S6  
S12 | S7  
1996

Deposit the marked stone within the mound at the base of the aluminum post.

The corner falls on top of a open, rocky ridge in a burn area.

---

N. 0°06.7' E., between sections 1 and 6.

**39.978** The 1/4 section corner of sections 1 and 6, monumented with a lava stone, 18x10x8 inches, laying over, dimly marked 1/4 on the W face (record, 14x8x6 inches, marked 1/4 S1 on W, 6 on E faces.).

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T26S  
R8W R7W  
1/4  
S1 | S6  
1996

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base by 2 ft. high, W of the corner.

The corner falls on flat ground in burn area.

---

N. 0°09.5' E., beginning new measurement.

**39.990** The NW corner of T. 26 S., R. 7 W., hereinbefore described.

---

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 26 S., R. 7 W., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by  
H.D. Page and H. Erwin in 1901

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 26 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the corner of sections 21, 22, 27, and 28, monumented with a trachyte stone, 18x10x8 inches, dimly marked with 4 notches on the S and none on the E edges, firmly set alongside a cedar post (record, quartzite, 14x10x7 inches, marked with 2 notches on the S and 4 notches on the N edges.)

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T26S R7W	
S21	S22
S28	S27
1996	

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base by 2 ft. high, W of the corner.

The corner falls on a gradual, NE slope in sagebrush.

N. 0°01.6' W., between sections 21 and 22.

**39.842**

The 1/4 section corner of sections 21 and 22, monumented with a lava stone, 18x8x5 inches, firmly set, plainly marked 1/4 on the W face, with a small mound of stone to the W (record, 20x20x10 inches, marked 1/4 S21 on W, 22 on E).

No remaining evidence of the original bearing trees was found.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 10 inches in the ground to bedrock, set in a mound of stone, 5 ft. base, to top of aluminum cap marked:

T26S R7W	
1/4	
S21	S22
1996	

Buried the marked stone alongside the aluminum post.

---

N. 0°08.1' E., beginning new measurement.

**40.373**

The corner of sections 15, 16, 21, and 22, monumented with a lava stone, 18x10x8 inches, plainly marked with 3 notches on the N and 3 notches on the S edges (record, 12x12x5 inches, marked T26S on NE and R7W on SE faces, mound of stone, 2 ft. base, 1 1/2 ft. high, west of corner).

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 26 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

from which the original bearing trees

A cedar, 8 inches diameter, bears N. 25° E., 79 1/2 links distance,  
no scribe marks visible (record, N. 15° E., 92 links marked T26SR7WS15BT).

A cedar, 9 inches diameter, bears N. 2° E., 69 1/2 links distance, with  
legible scribe marks visible (record, N. 5° W., 1.00 chain, marked  
T26SR7WS15BT).

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with  
aluminum cap marked:

T26S R7W	
S16	S15
S21	S22
1996	

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base by 3 ft. high, W of the corner.

The corner falls on a gradual, easterly slope in dense juniper.

---

N. 0°04.4' W., between sections 15 and 16.

**40.024** The 1/4 section corner of sections 15 and 16, monumented with a lava stone, 18x8x5 inches,  
firmly set, dimly marked 1/4 on the W face, with a scattered mound of stone to the W (record,  
14x8x6 inches, marked 1/4 S16 on W and 15 on E faces).

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with  
aluminum cap marked:

T26S R7W	
1/4	
S16	S15
1996	

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base by 2 ft. high, W of the corner.

The corner falls on a gradual, southerly slope.

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 26 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

N. 0°04.4' W., beginning new measurement.

**40.053** The corner of sections 9, 10, 15, and 16, monumented with a lava stone, 18x14x7 inches, loosely set, plainly marked with 2 notches on the E and 4 notches on the S edges, with a small mound of stone to the W (record, 2 notches on N edge).

from which the original bearing trees

A juniper, 10 inches diameter, with scribe marks visible,  
bears S. 60° E., 111 links distance.

A juniper, 8 inches diameter, with scribe marks visible,  
bears N. 55° W., 53 1/2 links distance.

There is no record of these bearing trees within the written record.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 14 inches in the ground, set in a mound of stone, 5 ft. base, to top of aluminum cap marked:

T26S R7W	
S9	S10
S16	S15
1996	

Buried the marked stone alongside the aluminum post.

The corner falls on a gradual, southerly slope in dense juniper.

N. 0°10.6' E., between sections 9 and 10.

**39.900** The 1/4 section corner of sections 9 and 10, monumented with a lava stone, 18x8x6 inches, laying over, plainly marked 1/4 on the W face, with a small mound of stone to the W (record, 16x10x6 inches, marked 1/4 S9 on W and 10 on E faces).

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T26S R7W	
1/4	
S9	S10
1996	

Buried the marked stone alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 26 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Raise a mound of stone, 4 ft. base by 2 ft. high, W of the aluminum post.

The corner falls on a SE slope between ridges in burn area.

---

N. 0°17.4' W., beginning new measurement.

**40.354** The corner of sections 3, 4, 9, and 10, monumented with a lava stone, 16x10x6 inches, firmly set, plainly marked with 5 notches on the S and 3 notches on the E edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T26S R7W	
S4	S3
S9	S10
1996	

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 4 ft. base by 3 ft. high, W of the corner.

The corner falls on a steep, westerly slope in juniper and sage.

---

N. 0°01.8' W., between sections 3 and 4.

**39.996** The 1/4 section corner of sections 3 and 4, monumented with a lava stone, 15x8x5 inches, firmly set, plainly marked 1/4 on the W face, with a scattered mound of stone to the N (record, marked 1/4 S4 on W and 3 on E faces.).

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T26S R7W	
1/4	
S4	S3
1996	

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 2 ft. base by 2 ft. high, W of the aluminum post.

The corner falls on a gradual, NE slope in dense juniper.

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 26 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0°02.2' W., beginning new measurement.

**8.10** Centerline of paved road, 16 ft. wide, bears, N. 39° E., and S. 39° W.

**39.604** The closing corner of sections 3 and 4, on the north boundary of the township; hereinbefore described.

---

From the corner of sections 21, 22, 27, and 28.

S. 89°56.8' W., between sections 21 and 28.

**39.790** The 1/4 section corner of sections 21 and 28, monumented with a sandstone, 12x10x5 inches, firmly set, plainly marked 1/4 on the N face (record, trachyte stone, marked 1/4 S21 on N and 28 on S faces).

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

	T26S R7W
1/4	<u>S21</u>
	S28
	1996

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base by 2 ft. high, N of the aluminum post.

The corner falls on flat ground in burn area.

---

N. 89°59.1' W., beginning new measurement.

**40.098** The corner of sections 20, 21, 28, and 29, monumented with a trachyte stone, 20x16x4 inches, firmly set, plainly marked with 4 notches on the E and 2 notches on the S edges, with a large scattered mound to the W.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

	T26S R7W
<u>S20</u>	<u>S21</u>
S29	S28
	1996

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 26 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base by 2 ft. high, W of the corner.

The corner falls on a gradual, NW slope in sagebrush and scattered juniper.

From this corner, U.S. Coast and Geodetic Survey triangulation station "PINEY 1938", bears S.  $1^{\circ}40.7'$  E., 129.660 chains distance, monumented with a standard brass disk, 3 1/2 inches diameter, firmly cemented in drill hole, with disk marked PINEY 1938.

---

N  $0^{\circ}09.4'$  W., between sections 20 and 21.

- 40.170** The 1/4 section corner of sections 20 and 21 monumented with a lava stone, 14x8x6 inches, firmly set, dimly marked 1/4 on the W face, with a scattered mound of stone to the W (record, 12x8x8 inches, marked 1/4 S20 on W and 21 on E faces).

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T26S R7W  
1/4  
S20 | S21  
1996

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 4 ft. base by 2 ft. high, W of the aluminum post.

The corner falls on an open, southerly slope in burn area.

---

N.  $0^{\circ}06.3'$  W., beginning new measurement.

- 40.034** The corner of sections 16, 17, 20, and 21, monumented with a lava stone, 20x12x8 inches, firmly set, plainly marked with 4 notches on the S and 2 notches on the E edges, with a mound of stone to the W.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 16 inches in the ground, set in a mound of stone, 4 ft. base, to top of aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 26 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T26S R7W	
S17	S16
S20	S21
1996	

Buried the marked stone alongside the aluminum post.

The corner falls on a gradual, westerly slope in dense juniper.

---

From the corner of sections 15, 16, 21, and 22.

S. 89°57.7' W., between sections 16 and 21.

- 40.135** The 1/4 section corner of sections 16 and 21, monumented with a lava stone, 12x10x8 inches, firmly set, dimly marked 1/4 on the N face, with a scattered mound of stone to the N (record, 12x8x7 inches, marked 1/4 S16 on N and 21 on S faces.).

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground to bedrock, set in a mound of stone, 3 ft. base, to top of aluminum cap marked:

T26S R7W	
1/4	S16
	S21
1996	

Buried the marked stone alongside the aluminum post.

The corner falls on top of a flat ridge, bears NE and SW, in sagebrush.

---

S. 89°59.0' W., beginning new measurement.

- 39.996** The corner of sections 16, 17, 20, and 21.
- 

N. 0°02.4' W., between sections 16 and 17.

- 40.106** The 1/4 section corner of sections 16 and 17, monumented with a lava stone, 12x10x6 inches, firmly set, dimly marked 1/4 on the W face, with a scattered mound of stone to the W (record, 12x10x8 inches, marked 1/4 S17 on W and 16 on E faces).

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 26 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T26S R7W  
1/4  
S17 | 16  
1996

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base by 2 ft. high, W of the aluminum post.

The corner falls 40 ft. S of a trail road, bears W and NE, in burn area.

---

N. 0°00.6' E., beginning new measurement.

**40.099** The corner of sections 8, 9, 16, and 17, monumented with a lava stone, 15x12x6 inches, firmly set, plainly marked with 4 notches on the S and 3 notches on the E edges, with a scattered mound of stone to the W.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T26S R7W  
S8 | S9  
S17 | S16  
1996

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base by 2 ft. high, W of the aluminum post.

The corner falls on a gradual, SW slope in burn area.

---

From the corner of sections 9, 10, 15, and 16.

N. 89°51.8' W., between sections 9 and 16.

**39.920** The 1/4 section corner of sections 9 and 16, monumented with a lava stone, 15x8x6 inches, firmly set, plainly marked 1/4 on the N face, with a scattered mound of stone to the N (record, marked 1/4 S9 on N and 16 on S faces).

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 26 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

	T26S R7W
1/4	<u>S9</u>
	S16
	1996

Buried the marked stone alongside the aluminum post.

The corner falls in burn area.

---

S. 89°59.5' W., beginning new measurement.

**40.114** The corner of sections 8, 9, 16, and 17.

---

N. 0°03.8' W., between sections 8 and 9.

**40.082** The 1/4 section corner of sections 8 and 9, monumented with a lava stone, 14x10x8 inches, loosely set, plainly marked 1/4 on the W face, with a scattered mound of stone to the W (record, 13x8x6 inches, marked 1/4 S8 on W and 9 on E faces).

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

	T26S R7W
	1/4
S8	S9
	1996

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 4 ft. base by 3 ft. high, W of the aluminum post.

Set a steel fence post alongside the aluminum post.

The corner falls on a gradual, westerly slope in burn area.

---

N. 0°00.5' E., beginning new measurement.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 26 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

**40.081**

The corner of sections 4, 5, 8, and 9, monumented with a lava stone, 18x8x8 inches, firmly set, plainly marked with 5 notches on the S and 4 notches on the E edges, with a scattered mound of stone to the W.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 10 inches in the ground, set in a mound of stone, 4 ft. base, to the top of aluminum cap marked:

T26S R7W	
S5	S4
S8	S9
1996	

Buried the marked stone alongside the aluminum post.

The corner falls on a gradual, northerly slope in dense juniper.

---

From the corner of sections 3, 4, 9, and 10.

N. 89°56.7' W., between sections 4 and 9.

**40.078**

The 1/4 section corner of sections 4 and 9, monumented with an X chiseled on a rock outcrop (record, boulder 6x6x2 ft., marked 1/4 on N and 9 on S faces, mound of stone, 3 ft. base, 2 ft. high, north of corner).

At the corner point

Set a rebar, 10 inches long, 3/4 inches diameter, drilled 8 inches in the rock outcrop, with aluminum cap marked:

T26S R7W	
1/4	S4
	S9
1996	

Raise a mound of stone, 4 ft. base, by 2 ft. high, N of the corner.

The corner falls on rocky ground in pinon and juniper.

---

S. 89°56.6' W., beginning new measurement.

**39.897**

The corner of sections 4, 5, 8, and 9.

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 26 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0°03.1' W., between sections 4 and 5.

- 40.086** The 1/4 section corner of sections 4 and 5, monumented with a lava stone, 14x8x6 inches, firmly set, plainly marked 1/4 on the W face, with a scattered mound of stone to the W (record, 15x10x8 inches, marked 1/4 S5 on W and 4 on E faces).

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T26S R7W  
1/4  
S5 | S4  
1996

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base by 3 ft. high, W of the aluminum post.

The corner falls on a gradual, westerly slope in burn area in scattered juniper and sage.

N. 0°02.1' W., beginning new measurement.

- 39.569** The closing corner of sections 4 and 5, on the north boundary of the township; hereinbefore described.

From the corner of sections 20, 21, 28, and 29.

S. 89°59.6' W., between sections 20 and 29.

- 40.050** The 1/4 section corner of sections 20 and 29, monumented with a lava stone, 15x12x5 inches, firmly set, dimly marked 1/4 on the N face (record, 15x10x5 inches, marked 1/4 S20 on N and 29 on S faces.).

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T26S R7W  
1/4     S20  
         S29  
         1996

Buried the marked stone alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 26 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Raise a mound of stone, 2 ft. base by 1 ft. high, north of the aluminum post.

Set a steel fence post alongside the aluminum post.

The corner falls in sagebrush flat.

S. 89°59.7' W., beginning new measurement.

**39.966** The corner of sections 19, 20, 29, and 30, monumented with a lava stone, 14x12x6 inches, firmly set, plainly marked with 5 notches on the E and 2 notches on the S edges.

From which the original bearing trees:

A juniper, 10 inches diameter, with a blaze only, no scribe marks visible, bears N. 18°W., 28 links distance (record, N. 21° W., 27 links).

A juniper, 12 inches diameter, with a blaze only, no scribe marks visible, bears S. 38°W., 24 links distance.

No remaining evidence of NE and SE bearing trees was found.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T26S R7W	
<u>S19</u>	<u>S20</u>
S30	S29
1996	

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base by 2 ft. high, W of the aluminum post.

The corner falls on a moderate, northerly slope in scattered juniper and sage.

N. 89°58.5' W., between sections 19 and 30.

**40.048** The 1/4 section corner of sections 19 and 30, monumented with scattered remains of the original cedar post.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 26 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T26S R7W  
1/4     S19  
          S30  
          1996

Raise a mound of stone, 3 ft. base by 2 ft. high, N of the aluminum post.

Set a steel fence post alongside the aluminum post.

The corner falls on flat ground in sagebrush.

\_\_\_\_\_

N. 89°58.8' W., beginning new measurement.

**37.645** The corner of sections 19, 24, 25, and 30, on the west boundary of the township; hereinbefore described.

\_\_\_\_\_

From the corner of sections 19, 20, 29, and 30.

N. 0°12.7' W., between sections 19 and 20.

**40.156** The 1/4 section corner of sections 19 and 20, monumented with a lava stone, 14x10x8 inches, firmly set, plainly marked, with 1/4 on the W face, with a scattered mound of stone to the N (record, 12x8x8 inches, marked 1/4 S19 on W and 20 on E edges, mound to the W).

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T26S R7W  
1/4  
S19 | S20  
1996

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base by 3 ft. high, W of the aluminum post.

The corner falls on a gradual, SE slope in burn area.

\_\_\_\_\_

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 26 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0°01.4' E., beginning new measurement.

40.062

The corner of sections 17, 18, 19, and 20, monumented with a lava stone, 18x12x6 inches, firmly set, plainly marked, with 5 notches on the E and 3 notches on the S edges, with a scattered mound of stone to the W.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 14 inches in the ground to bedrock, set in a mound of stone, 4 ft. base, to the top of aluminum cap marked:

T26S R7W	
S18	S17
S19	S20
1996	

Buried the marked stone alongside the aluminum post.

The corner falls on a gradual, westerly slope in burn area.

From the corner of sections 16, 17, 20, and 21.

N. 89°59.0' W., between sections 17 and 20.

39.944

The 1/4 section corner of sections 17 and 20, monumented with a lava stone, 18x10x6 inches, firmly set, plainly marked 1/4 on the N face, with a scattered mound of stone to the N (record, 14x10x6 inches, marked 1/4 S17 on N and 20 on S faces).

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T26S R7W	
1/4	S17
	S20
1996	

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base by 2 ft. high, W of the aluminum post.

The corner falls on a gradual, northerly, rocky slope, 50 links N from the top of a ridge.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 26 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

S. 89°59.4' W., beginning new measurement.

**40.005** The corner of sections 17, 18, 19, and 20.

---

S. 89°49.3' W., between sections 18 and 19.

**40.035** The 1/4 section corner of sections 18 and 19, monumented with a lava stone, 16x12x8 inches, firmly set, dimly marked 1/4 on the N face, with a small mound of stone to the N (record, 12x10x7 inches, marked 1/4 S18 on N and 19 on S faces).

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

	T26S R7W
1/4	<u>S18</u>
	S19
	1996

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base by 2 ft. high, N of the aluminum post.

The corner falls on a gradual, westerly slope in burn area.

---

N. 89°57.6' W., beginning new measurement.

**37.603** The corner of sections of 13, 18, 19, and 24, on the west boundary of the township, hereinbefore described.

---

From the corner of sections 17, 18, 19, and 20.

N. 0°00.4' W., between sections 17 and 18.

**40.088** The 1/4 section corner of sections 17 and 18, monumented with a lava stone, 14x10x6 inches, firmly set, plainly marked 1/4 on the W face, with a scattered mound of stone to the W (record, 14x10x8 inches, marked 1/4 S18 on W and 17 on E faces).

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 26 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T26S R7W  
1/4  
S18 | S17  
1996

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 4 ft. base by 2 ft. high, W of the aluminum post.

Set a steel fence post alongside the aluminum post.

The corner falls on open, flat ground in burn area.

---

N. 0°00.2' E., beginning new measurement.

**40.077** The corner of sections 7, 8, 17, and 18, monumented with a lava stone, 14x10x6 inches, firmly set, plainly marked with 5 notches on the E and 4 notches on the S edges, with a mound of stone to the W.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T26S R7W  
S7 | S8  
S18 | S17  
1996

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base by 2 ft. high, W of the aluminum post.

The corner falls on a gradual, SW slope in burn area.

---

From the corner of sections 8, 9, 16, and 17.

S. 89°59.3' W., between sections 8 and 17.

**39.854** The 1/4 section corner of sections 8 and 17, monumented with a lava stone, 14x14x8 inches, firmly set, plainly marked 1/4 on the N face, with a scattered mound of stone to the N (record, 15x15x8 inches, marked 1/4 S8 on N and 17 on S faces).

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 16 inches in the ground, set in a mound of stone, 3 ft. base, to the top of aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 26 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T26S R7W  
1/4     S8  
          S17  
          1996

Buried the marked stone alongside the aluminum post.

The corner falls on open ground in burn area.

---

S. 89°57.8' W., beginning new measurement.

**40.060** The corner of sections 7, 8, 17, and 18.

---

S. 89°51.3' W., between sections 7 and 18.

**40.039** The 1/4 section corner of sections 7 and 18, monumented with a lava stone, 18x12x8 inches, firmly set, plainly marked 1/4 on the N face, with a small mound of stone to the N (record, 20x14x10 inches, marked 1/4 S7 on N and 18 on S faces).

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T26S R7W  
1/4     S7  
          S18  
          1996

Raise a mound of stone, 4 ft. base by 2 ft. high, N of the aluminum post.

The corner falls on an open, westerly slope in burn area.

---

S. 89°52.9' W., beginning new measurement.

**37.606** The corner of sections 7, 12, 13, and 18, on the west boundary of the township; hereinbefore described.

---

From the corner of sections 7, 8, 17, and 18.

N. 0°27.7' W., between sections 7 and 8.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 26 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

**41.169**

The 1/4 section corner of sections 7 and 8, monumented with a lava stone, 12x10x8 inches, firmly set, plainly marked 1/4 on the W face, with a scattered mound of stone to the W (record, 12x12x10 inches, marked 1/4 S7 on W and 8 on E faces).

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T26S R7W  
1/4  
S7 | S8  
1996

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base by 2 ft. high, W of the aluminum post.

The corner falls on a gradual, NW slope in burn area.

---

N. 0°06.7' W., beginning new measurement.

**39.041**

The corner of sections 5, 6, 7, and 8, monumented with a lava stone, 16x12x4 inches, laying loose, plainly marked with 5 notches on the E and 5 notches on the S edges, with a small mound of stone to the W.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T26S R7W  
S6 | S5  
S7 | S8  
1996

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base by 2 ft. high, W of the aluminum post.

Set a steel fence post alongside the aluminum post.

The corner falls on an open, gradual, northerly slope in burn area.

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 26 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the corner of sections 4, 5, 8, and 9.

N. 89°57.3' W., between sections 5 and 8.

- 40.251** The 1/4 section corner of sections 5 and 8, monumented with a lava stone, 16x8x8 inches, firmly set, dimly marked 1/4 on the N face (record, 12x8x8 inches, marked 1/4 S5 on N and 8 on S faces).

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

	T26S R7W
1/4	<u>S5</u>
	S8
	1996

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base by 2 ft. high, W of the aluminum post.

Set a steel fence post alongside the aluminum post.

The corner falls on open ground in burn area.

---

S. 89°58.2' W., beginning new measurement.

- 40.017** The corner of sections 5, 6, 7, and 8.

---

N. 89°59.6' W., between sections 6 and 7.

- 40.009** The 1/4 section corner of sections 6 and 7, monumented with a lava stone, 18x10x8 inches, firmly set, plainly marked 1/4 on the N face, with a mound of stone to the N (record, 14x8x8 inches, marked 1/4 S6 on N and 7 on S faces).

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 8 inches in the ground, set in a mound of stone, 5 ft. base, to the top of aluminum cap marked:

	T26S R7W
1/4	<u>S6</u>
	S7
	1996

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 26 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

The corner falls on an open, rocky, finger ridge in burn area.

---

S. 89°50.3' W., beginning new measurement.

**37.433** The corner of sections 1, 6, 7, and 12, on the west boundary of the township; hereinbefore described.

---

From the corner of sections 5, 6, 7, and 8.

N. 0°01.9' W., between sections 5 and 6.

**40.083** The 1/4 section corner of sections 5 and 6, monumented with a lava stone, 15x10x8 inches, firmly set, plainly marked 1/4 on the W face, with a mound of stone to the W (record, marked 1/4 S6 on W and 5 on E faces).

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T26S R7W  
1/4  
S6 | S5  
1996

Buried the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base by 3 ft. high, W of the aluminum post.

Set a steel fence post alongside the aluminum post.

The corner falls in the bottom of a hollow, 128 ft. W of a fence, bears NW and SE, in burn area.

---

N. 0°03.0' E., beginning new measurement.

**39.662** The closing corner of sections 5 and 6, on the north boundary of the township; hereinbefore described.

---

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD ASSISTANTS**

---

Name	Capacity
Brandon S. Sanchez	Survey Technician
Darin H. Robinson	Range Technician
Shane L. Berry	Survey Aid

### CERTIFICATE OF SURVEY

I, *Larry V. Judd, Cadastral Surveyor*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *15th day of August, 1996*, I have *dependently resurveyed portions of the north boundary (Fifth Standard Parallel South), the west boundary, and subdivisional lines in Township 26 South, Range 7 West,*

of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

3 / 23 / 98  
Date

*Larry V. Judd*  
(Cadastral Surveyor)

\_\_\_\_\_  
Date

\_\_\_\_\_  
(Cadastral Surveyor)

### CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of portions of the north boundary (Fifth Standard Parallel South), the west boundary, and subdivisional lines in Township 26 South, Range 7 West, Salt Lake Meridian, Utah,*

executed by *Larry V. Judd, Cadastral Surveyor*

having been critically examined and found correct, are hereby approved.

April 23, 1998  
Date

*Daniel W. Webb*  
(Chief Cadastral Surveyor for Utah)