

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF
A PORTION OF THE SUBDIVISIONAL LINES,
AND THE
SUBDIVISION OF SECTIONS 5, 6, 8, 18, AND 19

OF

TOWNSHIP 13 SOUTH, RANGE 3 WEST

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Jerry L. Thomas
Cadastral Surveyor

Under special instructions dated *August 22, 1996*, approved *August 23, 1996*, which provided for the surveys included under Group Number 856, and assignment instructions dated *September 3 1996*.

Survey commenced *September 12, 1996*
Survey completed *September 28, 1996*

INDEX DIAGRAM

Township 13 South , Range 3 West

6 11 11	5 6 10	4 4 5 4	3 3 3	2	1
7 9 8	8 4 8	9 2 2	10	11	12
18 7	17	16	15	14	13
19 6	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

The Subdivision of Section 5.....Page 12
 The Subdivision of Section 6.....Page 13
 The Subdivision of Section 8.....Page 15
 The Subdivision of Section 18.....Page 17
 The Subdivision of Section 19.....Page 19

TOWNSHIP 13 SOUTH, RANGE 3 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

The following field notes describe the dependent resurvey of a portion of the subdivisional lines, and the subdivision of sections 5, 6, 8, 18, and 19, Township 13 South, Range 3 West, Salt Lake Meridian, Utah.

History of Surveys

		Surveyed by	Retr. or Resurveyed by	
SOUTH BOUNDARY				
Portion	J. Gorlinski	1872		
All	S.M. Richardson	1884	S.M. Richardson	1884
Portion			Stewart and Stewart	1898
Portion			B.S. Owens	1960
EAST BOUNDARY				
All	J. Gorlinski	1872		
All			Stewart and Stewart	1898
Portion			E. Bird and A. Nelson	1944
Portion			G.E. Reynolds	1986
WEST BOUNDARY				
Portion	J. Gorlinski	1872		
Portion	S.M. Richardson	1884	S.M. Richardson	1884
Portion			B.S. Owens	1960
Portion			M.R. Workman	1996
NORTH BOUNDARY				
All	J. Gorlinski	1872		
Portion			E. Bird and A. Nelson	1944
Portion			G.E. Reynolds	1986
Portion			J.L. Thomas	1996
SUBDIVISION				
Portion	J. Gorlinski	1872		
Portion			S.M. Richardson	1884
Portion	B.S. Owens	1960		
Portion			G.E. Reynolds	1986

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 856, dated August 22, 1996.

TOWNSHIP 13 SOUTH, RANGE 3 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

The directions of lines were determined by hour angle observations of the Sun and Polaris, carried forward by sustained angulation. Distances were determined by electronic measurement.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line notes are given herein.

The geographic positions of the following corners were determined by ties to U.S.G.S. triangulation station "DYER", (Latitude $39^{\circ} 40' 21.24325''$ N., Longitude $112^{\circ} 15' 40.11759''$ W., Elev. 5108 ft., N.A.D. 1983), by the Global Positioning System (GPS), using relative positioning techniques. They will also function as B.L.M. control stations.

The geographic position of the corner of Townships 12 and 13 South, Ranges 3 and 4 West, is as follows:

Latitude $39^{\circ} 43' 42.214''$ N. Longitude $112^{\circ} 13' 59.228''$ W.
N.A.D. 1983

The geographic position of the corner of sections 13, 18, 19, and 24, west boundary, is as follows:

Latitude $39^{\circ} 41' 04.318''$ N. Longitude $112^{\circ} 13' 59.117''$ W.
N.A.D. 1983

The mean magnetic declination as determined from numerous readings throughout the survey is: $13 \frac{1}{4}^{\circ}$ East.

NOTE: Portions of the west and north boundaries were surveyed concurrently with this survey in 1996 and 1997, under Group Nos. 849 and 853.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 13 S., R. 3 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
J. Gorlinski in 1872

Beginning at the corner of sections 9, 10, 15, and 16, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with aluminum cap marked as described in the official record of the 1986 resurvey of a portion of the subdivisional lines of T. 13 S., R. 3 W.

N. $0^{\circ} 15.3'$ W., between sections 9 and 10.

Over gentle rolling land.

THE DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 13 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS**40.270**

Point for the 1/4 section corner of sections 9 and 10, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T13S	R3W
	1/4
S9	S10
	1996

Set a steel fence post alongside the corner.

80.540

The corner of sections 3, 4, 9, and 10, monumented with a limestone, 13x8x5 inches, firmly set, projecting 8 inches above ground, plainly marked 5 notches on the S. and 2 notches on the E. edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T13S	R3W
S4	S3
S9	S10
	1996

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

From the corner of sections 2, 3, 10, and 11, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with aluminum cap marked as described in the official record of the 1986 resurvey of a portion of the subdivisional lines of T. 13 S., R. 3 W.

N. 89° 52.6' W., between sections 3 and 10.

Over gentle rolling land.

40.510

The 1/4 section corner of sections 3 and 10, monumented with a limestone, 14x7x5 inches, firmly set, projecting 6 inches above ground, plainly marked 1/4 on the N. face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

THE DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 13 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T13S R3W
1/4 $\frac{S3}{S10}$
1996

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

N. 89° 44.3' W., beginning new measurement.

40.520 The corner of sections 3, 4, 9, and 10.

N. 0° 00.6' E., between sections 3 and 4.

Over gentle rolling land.

40.660 Point for the 1/4 section corner of sections 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T13S R3W
1/4
S4 | S3
1996

Set a steel fence post alongside the corner.

80.990 The corner of sections 3, 4, 33, and 34, on the north boundary, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with aluminum cap marked as described in the official record of the 1996 concurrent resurvey, under Group No. 849, of a portion of the south boundary of T. 12 S., R. 3 W.

From the corner of sections 8, 9, 16, and 17, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with aluminum cap marked as described in the official record of the 1986 resurvey of a portion of the subdivisional lines of T. 13 S., R. 3 W.

N. 0° 27.2' W., between sections 8 and 9.

Over gentle rolling land.

40.425 Point for the 1/4 section corner of sections 8 and 9, at proportionate distance; there is no remaining evidence of the original corner.

THE DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 13 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T13S R3W
1/4
S8 | S9
1996

Set a steel fence post alongside the corner.

80.850 The corner of sections 4, 5, 8, and 9, monumented with a limestone, 12x7x5 inches, firmly set, projecting 4 inches above ground, plainly marked 5 notches on the S. and 4 notches on the E. edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T13S R3W
S5 | S4
S8 | S9
1996

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

From the corner of sections 3, 4, 9, and 10.

N. 89° 53.9' W., between sections 4 and 9.

Over gentle rolling land.

40.615 The 1/4 section corner of sections 4 and 9, monumented with a limestone, 13x8x6 inches, firmly set, projecting 9 inches above ground, plainly marked 1/4 on the N. face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T13S R3W
1/4 S4
S9
1996

Deposit the marked alongside the aluminum post.

THE DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 13 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a steel fence post alongside the corner.

N. 89° 41.1' W., beginning new measurement.

40.640 The corner of sections 4, 5, 8, and 9.

N. 0° 06.2' E., between sections 4 and 5.

Over gentle rolling land.

40.380 Point for the 1/4 section corner of sections 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T13S R3W
1/4
S5 | S4
1996

Set a steel fence post alongside the corner.

80.920 The corner of sections 4, 5, 32, and 33, on the north boundary, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with aluminum cap marked as described in the official record of the 1996 concurrent resurvey, under Group No. 849, of a portion of the south boundary of T. 12 S., R. 3 W.

From the corner of sections 19, 20, 29, and 30, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with aluminum cap marked as described in the official record of the 1986 resurvey of a portion of the subdivisional lines of T. 13 S., R. 3 W.

N. 89° 54.4' W., between sections 19 and 30.

Over rolling land.

40.630 True point for the 1/4 section corner of sections 19 and 30, at proportionate distance, falls in deep wash and is unsafe to monument; there is no remaining evidence of the original corner.

Due to inconsistencies between the surveyors field notes and the draftsman's plat of the 1884 resurvey, there is confusion about the 1/4 section corner position between sections 19 and 30. Therefore, I decided to use the original 1872 survey by J. Gorlinski for proportioning purposes, as this survey better protects the acreages.

40.880 Point selected for the witness 1/4 section corner of sections 19 and 30.

THE DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 13 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

$$\begin{array}{c} \text{WC} \\ \text{T13S R3W} \\ 1/4 \frac{\text{S19}}{\text{S30}} \blacktriangleright \\ 1996 \end{array}$$

Set a steel fence post alongside the corner.

- 80.960** The corner of sections 19, 24, 25, and 30, on the west boundary, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with aluminum cap marked as described in the official record of the 1996 concurrent resurvey, under Group no. 853, of a portion of the east boundary of T. 13 S., R. 4 W.

From the corner of sections 17, 18, 19, and 20, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with aluminum cap marked as described in the official record of the 1986 resurvey of a portion of the subdivisional lines of T. 13 S., R. 3 W.

N. 89° 38.5' W., between sections 18 and 19.

Over rolling land.

- 40.370** Point for the 1/4 section corner of sections 18 and 19, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

$$\begin{array}{c} \text{T13S R3W} \\ 1/4 \frac{\text{S18}}{\text{S19}} \\ 1996 \end{array}$$

Set a steel fence post alongside the corner.

- 60.555** Point for the W. 1/16 section corner of sections 18 and 19.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

$$\begin{array}{c} \text{W } 1/16 \frac{\text{S18}}{\text{S19}} \\ 1996 \end{array}$$

Set a steel fence post alongside the corner.

THE DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 13 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

80.845

The corner of sections 13, 18, 19, and 24, on the west boundary, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground with aluminum cap marked as described in the official record of the 1996 concurrent resurvey, under Group No. 853, of a portion of the east boundary of T. 13 S., R. 4 W.

From the corner of sections 8, 9, 16, and 17.

N. 89° 46.8' W., between sections 8 and 17.

Over rolling land.

40.546

The 1/4 section corner of sections 8 and 17, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with aluminum cap marked as described in the official record of the 1986 resurvey of a portion of the subdivisional line of T. 13 S., R. 3 W.

N. 89° 47.6' W., beginning new measurement.

Over rolling land.

40.514

The corner of sections 7, 8, 17, and 18, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with aluminum cap marked as described in the official record of the 1986 resurvey of a portion of the subdivisional line of T. 13 S., R. 3 W.

N. 89° 58.6' W., between sections 7 and 18.

Over rolling land.

40.690

The 1/4 section corner of sections 7 and 18, monumented with a quartzite stone, 14x10x8 inches, firmly set, projecting 6 inches above ground, plainly marked 1/4 on the N. face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T13S R3W
1/4 $\frac{S7}{S18}$
1996

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

THE DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 13 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 89° 52.9' W., beginning new measurement.

- 40.465** The corner of sections 7, 12, 13, and 18, on the west boundary monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with aluminum cap marked as described in the official record of the 1996 concurrent resurvey, under Group No. 853, of a portion of the east boundary of T. 13 S., R. 4 W.

From the corner of sections 7, 8, 17, and 18.

N. 0° 06.0' E., between sections 7 and 8.

Over rolling land.

- 40.235** The 1/4 section corner of sections 7 and 8, monumented with a limestone, 12x10x6 inches, firmly set, dimly marked 1/4 on the W. face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T13S R3W
1/4
S7 | S8
1996

Deposit the dimly marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

North, beginning new measurement.

- 20.100** Point for the N. 1/16 section corner of sections 7 and 8.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

N 1/16
S7 | S8
1996

Set a steel fence post alongside the corner.

- 40.200** The corner of sections 5, 6, 7, and 8, monumented with a limestone, 14x8x6 inches, firmly set, projecting 8 inches above ground, dimly marked 5 notches on the S. and E. edges.

At the corner point

THE DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 13 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T13S R3W	
S6	S5
S7	S8
1996	

Deposit the dimly marked stone alongside the aluminum post.

Set a steel fence post alongside the corner.

From the corner of sections 4, 5, 8, and 9.

S. 89° 55.5' W., between sections 5 and 8.

Over rolling land.

20.085 Point for the E. 1/16 section corner of sections 5 and 8.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

E 1/16	S5
	S8
	1996

Set a steel fence post alongside the corner.

40.170 Point for the 1/4 section corner of sections 5 and 8, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T13S R3W	
1/4	S5
	S8
	1996

Set a steel fence post alongside the corner.

60.255 Point for the W. 1/16 section corner of sections 5 and 8.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

W 1/16	S5
	S8
	1996

THE DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 13 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

- Set a steel fence post alongside the corner.
- 80.340** The corner of sections 5, 6, 7, and 8.
-
- N. 89° 30.5' W., between sections 6 and 7.
- Over rolling land.
- 40.700** Point for the 1/4 section corner of sections 6 and 7, at proportionate distance; there is no remaining evidence of the original corner.
- Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:
- T13S R3W
1/4 $\frac{S6}{S7}$
1996
- Set a steel fence post alongside the corner.
- 81.200** The corner of sections 1, 6, 7, and 12, on the west boundary, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with aluminum cap marked as described in the official record of the 1996 concurrent resurvey, under Group No. 853, of a portion of the east boundary of T. 13 S., R. 4 W.
-
- From the corner of sections 5, 6, 7, and 8.
- N. 0° 16.0' W., between sections 5 and 6.
- Over rolling land.
- 20.515** Point for the S. 1/16 section corner of sections 5 and 6; not monumented.
- 41.030** Point for the 1/4 section corner of sections 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.
- Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:
- T13S R3W
1/4
S6 | S5
1996
- Set a steel fence post alongside the corner.

THE DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 13 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS**81.235**

The corner of sections 5, 6, 31, and 32, on the north boundary, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with aluminum cap marked as described in the official record of the 1996 concurrent resurvey, under Group No. 849, of a portion of the south boundary of T. 12 S., R. 3 W.

The Subdivision of Section 5,
T. 13 S., R. 3 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 5 and 8.

N. 0° 08.4' W., on the N - S center line of section 5.

Over rolling land.

20.355

Point for the center S. 1/16 section corner of section 5.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

$$\begin{array}{c} \text{C} \\ \text{S } 1/16 \text{ | S5} \\ \text{C} \\ 1996 \end{array}$$

Set a steel fence post alongside the corner.

40.710

Point for the center 1/4 section corner of section 5, at intersection with the E - W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

$$\begin{array}{c} \text{T13S R3W} \\ \text{C } 1/4 \text{ S5} \\ 1996 \end{array}$$

Set a steel fence post 5 ft. east of corner.

Corner is located 23 links east of railroad tracks.

81.090

The 1/4 section corner of sections 5 and 32, on the north boundary, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with aluminum cap marked as described in the official record of the 1996 concurrent resurvey, under Group No. 849, of a portion of the south boundary of T. 12 S., R. 3 W.

From the 1/4 section corner of sections 4 and 5.

N. 89° 36.7' W., on the E - W center line of section 5.

THE SUBDIVISION OF SECTION 5,
T. 13 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

- Over rolling land.
- 40.340** The center 1/4 section corner of section 5.
- 60.465** Point for the center W. 1/16 section corner of section 5; not monumented.
- 80.590** The 1/4 section corner of sections 5 and 6.
-
- From the W. 1/16 section corner of sections 5 and 8.
- N. 0° 12.2' W., on the N - S center line of the SW 1/4 of section 5.
- Over rolling land.
- 20.435** Point for the SW 1/16 section corner of section 5, at intersection with the E - W center line of the SW 1/4.
- Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:
- SW 1/16
S 5
1996
- Set a steel fence post alongside the corner.
- 40.870** Point for the center W. 1/16 section corner of section 5.
-
- From the center S. 1/16 section corner of section 5.
- N. 89° 50.6' W., on the E - W center line of the SW 1/4 of section 5.
- Over rolling land.
- 20.105** The SW 1/16 section corner of section 5.
- 40.210** Point for the S. 1/16 section corner of sections 5 and 6.
-
- The Subdivision of Section 6,
T. 13 S., R. 3 W., Salt Lake Meridian, Utah
-
- From the 1/4 section corner of sections 6 and 7.
- N. 0° 03.0' W., on the N - S center line of section 6.

THE SUBDIVISION OF SECTION 6,
T. 13 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Over rolling land.

40.380 Point for the center 1/4 section corner of section 6, at intersection with the E - W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum marked:

T13S R3W
C 1/4 S6
1996

Corner is located 1.10 chains E. of the center line of the "Little Sahara" road.

60.890 Point for the center N. 1/16 section corner of section 6; not monumented.

80.990 The 1/4 section corner of sections 6 and 31, on the north boundary, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with aluminum cap marked as described in the official record of the 1996 concurrent resurvey, under Group No. 849, of a portion of the south boundary of T. 12 S., R. 3 W.

From the 1/4 section corner of sections 5 and 6.

S. 89° 34.6' W., on the E - W center line of section 6.

Over rolling land.

40.545 The center 1/4 section corner of section 6.

60.865 Point for the center W. 1/16 section corner of section 6.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

C $\frac{W \ 1/16}{S6}$ C
1996

Set a steel fence post alongside the corner.

81.085 The 1/4 section corner of sections 1 and 6, on the west boundary, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with aluminum cap marked as described in the official record of the 1996 concurrent resurvey, under Group no. 853, of a portion of the east boundary of T. 13 S., R. 4 W.

From the center W. 1/16 section corner of section 6.

N. 0° 05.5' E., on the N - S center line of the NW 1/4 of section 6.

THE SUBDIVISION OF SECTION 6
T. 13 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Over rolling land.

7.710 Little Sahara road, bears E. and W.

20.500 Point for the NW 1/16 section corner of section 6, at intersection with the E - W center line of the NW 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

NW 1/16 S6
1996

Set a steel fence post alongside the corner.

40.795 Point for the W. 1/16 section corner of sections 6 and 31, on the north boundary, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with aluminum cap marked as described in the official record of the 1996 concurrent resurvey, under Group No. 849, of a portion of the south boundary of T. 12 S., R. 3 W.

From the point for the center N. 1/16 section corner of section 6.

S. 89° 33.3' W., on the E - W center line of the NW 1/4 of section 6.

Over rolling land.

20.265 The NW 1/16 section corner of section 6.

40.475 The N. 1/16 section corner of sections 1 and 6, on the west boundary, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with aluminum cap marked as described in the official record of the 1996 concurrent resurvey, under Group No. 853, of a portion of east boundary, T. 13 S., R. 4 W.

The Subdivision of Section 8,
T. 13 S., R. 3 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 8 and 17.

N. 0° 11.4' W., on the N - S center line of section 8.

Over rolling land.

40.325 Point for the center 1/4 section corner of section 8, at intersection with the E - W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 8
T. 13 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T13S R3W
C 1/4 S8
1996

Set a steel fence post alongside the corner.

60.480 Point for the center N. 1/16 section corner of section 8; not monumented.

80.635 The 1/4 section corner of sections 5 and 8.

From the 1/4 section corner of sections 8 and 9.

N. 89° 55.2' W., on the E - W center line of section 8.

Over rolling land.

20.180 Point for the center E. 1/16 section corner of section 8.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

C $\frac{E \ 1/16}{S8}$ C
1996

Set a steel fence post alongside the corner.

40.360 The center 1/4 section corner of section 8.

60.515 Point for the center W. 1/16 section corner of section 8.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

C $\frac{W \ 1/16}{S8}$ C
1996

Set a steel fence post alongside the corner.

80.670 The 1/4 section corner of sections 7 and 8.

From the center E. 1/16 section corner of section 8.

N. 0° 19.3' W., on the N - S center line of the NE 1/4 of section 8.

THE SUBDIVISION OF SECTION 8,
T. 13 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Over rolling land.

40.370 The E. 1/16 section corner of sections 5 and 8.

From the center W. 1/16 section corner of section 8.

N. 0° 05.7' W., on the N - S center line of the NW 1/4 of section 8.

Over rolling land.

20.125 Point for the NW 1/16 section corner of section 8, at intersection with the E - W center line of the NW 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

NW 1/16 S8
1996

Set a steel fence post alongside the corner.

40.250 The W. 1/16 section corner of sections 5 and 8.

From a point for the center N. 1/16 section corner of section 8.

West, on the E - W center line of the NW 1/4 of section 8.

Over rolling land.

20.120 The NW 1/16 section corner of section 8.

40.240 The N. 1/16 section corner of sections 7 and 8.

The Subdivision of Section 18,
T. 13 S., R. 3 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 18 and 19.

N. 0° 06.8' W., on the N - S center line of section 18.

Over rolling land.

40.320 Point for the center 1/4 section corner of section 18, at intersection with the E - W center line.

THE SUBDIVISION OF SECTION 18,
T. 13 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T13S R3W
C 1/4 S18
1996

Set a steel fence post alongside the corner.

80.555 The 1/4 section corner of sections 7 and 18.

From the 1/4 section corner of sections 17 and 18, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with aluminum cap marked as described in the official record of the 1986 resurvey of a portion of the subdivisional lines of T. 13 S., R. 3 W.

S. 89° 59.4' W., on the E - W center line of section 18.

Over rolling land.

40.495 The center 1/4 section corner of section 18.

60.840 Point for the center W. 1/16 section corner of section 18.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

C $\frac{W \ 1/16}{S18}$ C
1996

Set a steel fence post alongside the corner.

81.115 The 1/4 section corner of sections 13 and 18, on the west boundary, monumented with an aluminum post, firmly set, projecting 6 inches above ground, with aluminum cap marked as described in the official record of the 1996 concurrent resurvey, under Group No. 853, of a portion of the east boundary of T. 13 S., R. 4 W.

From the W. 1/16 section corner of sections 18 and 19.

N. 0° 20.6' W., on the N - S center line of the SW 1/4 of section 18.

Over rolling land.

40.190 The center W. 1/16 section corner of section 18.

THE SUBDIVISION OF SECTION 19,
T. 13 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

The Subdivision of Section 19,
T. 13 S., R. 3 W., Salt Lake Meridian, Utah

From the true point for the 1/4 section corner of sections 19 and 30.

N. 0° 16.1' E., on the N - S center line of section 19.

Over rolling land.

40.495 Point for the center 1/4 section corner of section 19, at intersection with the E - W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T13S R3W
C 1/4 S19
1996

Set a steel fence post alongside the corner.

81.030 The 1/4 section corner of sections 18 and 19.

From the 1/4 section corner of sections 19 and 20, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with aluminum cap marked as described in the official record of the 1986 resurvey of a portion of the subdivisional lines of T. 13 S., R. 3 W.

N. 89° 44.6' W., on the E - W center line of section 19.

Over rolling land.

40.505 The center 1/4 section corner of section 19.

60.755 Point for the center W. 1/16 section corner of section 19.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

C $\frac{W \ 1/16}{S19}$ C
1996

Set a steel fence post alongside the corner.

THE SUBDIVISION OF SECTION 19,
T. 13 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS**80.905**

The 1/4 section corner of sections 19 and 24, on the west boundary, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with aluminum cap marked as described in the official record of the 1996 concurrent resurvey, under Group No. 853, of the east boundary of T. 13 S., R. 4 W.

From the center W. 1/16 section corner of section 19.

N. 0° 21.5' E., on the N - S center line of the NW 1/4 of section 19.

Over rolling land.

40.570

The W. 1/16 section corner of sections 18 and 19.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Judd Beagley	Surveying Aid
Garrett Snow	Surveying Aid
Dave Harris (BOR)	Survey Technician
Tracy Thompson (BOR)	Survey Technician

CERTIFICATE OF SURVEY

I, *Jerry L. Thomas, Cadastral Surveyor*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *22nd day of August, 1996*, I have *dependently resurveyed a portion of the subdivisional lines, and the subdivision of sections 5, 6, 8, 18, and 19, and, in Township 13 South, Range 3 West,*

of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

August 21, 2001

Date

Jerry L. Thomas

(Cadastral Surveyor)

Date

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of a portion of the subdivisional lines, and the subdivision of sections 5, 6, 8, 18, and 19, in Township 13 South, Range 3 West, Salt Lake Meridian, Utah,*

executed by *Jerry L. Thomas, Cadastral Surveyor*

having been critically examined and found correct, are hereby approved.

Aug. 24, 2001

Date

Daniel W. Webb

(Chief Cadastral Surveyor for Utah)