

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

# FIELD NOTES

OF  
THE DEPENDENT RESURVEY OF

A PORTION OF THE SOUTH BOUNDARY,

THE EAST BOUNDARY,

A PORTION OF THE NORTH BOUNDARY,

AND

A PORTION OF THE SUBDIVISIONAL LINES,

AND THE

SUBDIVISION OF SECTIONS 22, 25, 28, AND 35,

IN

TOWNSHIP 14 SOUTH, RANGE 3 WEST

OF THE SALT LAKE MERIDIAN

IN THE STATE OF UTAH

EXECUTED BY

*Ronald K. Baugh and M. Ross Workman*  
*Supervisory Cadastral Surveyors*

Under special instructions dated *September 3, 1996*, approved *September 3, 1996*, which provided for the surveys included under Group Number *862*, and assignment instructions dated *September 16, 1996*.

Survey commenced *October 22, 1996*

Survey completed *October 12, 2000*

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

# FIELD NOTES

OF  
THE DEPENDENT RESURVEY OF

A PORTION OF THE SOUTH BOUNDARY,

THE EAST BOUNDARY,

A PORTION OF THE NORTH BOUNDARY,

AND

A PORTION OF THE SUBDIVISIONAL LINES,

AND THE

SUBDIVISION OF SECTIONS 22, 25, 28, AND 35,

IN

TOWNSHIP 14 SOUTH, RANGE 3 WEST

OF THE SALT LAKE MERIDIAN

IN THE STATE OF UTAH

EXECUTED BY

*Ronald K. Baugh and M. Ross Workman*  
*Supervisory Cadastral Surveyors*

Under special instructions dated *September 3, 1996*, approved *September 3, 1996*, which provided for the surveys included under Group Number *862*, and assignment instructions dated *September 16, 1996*.

Survey commenced *October 22, 1996*

Survey completed *October 12, 2000*

# INDEX DIAGRAM

Township 14 South, Range 3 West

					17	16
6	5	4	3	2	25	1 15 25
7	8	9	10	11 24 29	12 13 24	
18	17	16	15 29 32	14 23 28	13 11 23	
19	20	21 31 34	22 28 31	23 22 27	24 10 21	
			30			
30	29 33	28	27	26 20 27	25 8 19	
31	32	33	34 26 6	35 18 4	36 7 2	

The Subdivision of Section 22.....Page 34

The Subdivision of Section 25.....Page 36

The Subdivision of Section 28.....Page 37

The Subdivision of Section 35.....Page 39

## TOWNSHIP 14 SOUTH, RANGE 3 WEST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

The following field notes describe the dependent resurvey of a portion of the south boundary, the east boundary, a portion of the north boundary, and a portion of the subdivisional lines, and the subdivision of sections 22, 25, 28, and 35, in Township 14 South, Range 3 West, Salt Lake Meridian, Utah.

**History of Surveys**

		<b>Surveyed by</b>	<b>Retr. or Resurveyed by</b>	
<b>SOUTH BOUNDARY</b>				
All	S.M. Richardson	1884		
Portion			Stewart and Heist	1912
Portion			J.C. Thoma, C.J. Terry and H.W. Miller	1920
Portion			D.H. Meyers (Mineral Surveyor)	1988 Portion
Portion			R.L. Houston	1997
<b>EAST BOUNDARY</b>				
All	S.M. Richardson	1884		
All			Stewart and Heist	1912
<b>WEST BOUNDARY</b>				
All	S.M. Richardson	1884		
All			Stewart and Clark	1913
<b>NORTH BOUNDARY</b>				
Portion	J. Gorlinski	1972		
All	S.M. Richardson	1884	S.M. Richardson	1884
Portion			B.S. Owens	1960
<b>SUBDIVISION</b>				
All	S.M. Richardson	1884		
Portion			D.H. Meyers (Mineral Surveyor)	1988

Portions of T. 13 S., R. 2 W., Salt Lake Meridian, were resurveyed concurrently, 1996-1997, by J.L. Thomas, under Group No. 859.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 862, dated September 3, 1996.

The directions and distances were determined by the use of Global Positioning System (G.P.S.) using relative positioning techniques.

## TOWNSHIP 14 SOUTH, RANGE 3 WEST, SALT LAKE MERIDIAN, UTAH

*CHAINS*

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line notes are given herein.

The geographic position of the southeast corner of section 36, was determined by ties to National Geodetic Survey triangulation stations "CAPPS" and "DYER", by G.P.S. using relative positioning techniques, is as follows:

Latitude: 39° 33' 13.303" N.      Longitude: 112° 07' 22.259" W.  
N.A.D. 1983    Elev. 5300 ft.

The geographic position of National Geodetic Survey triangulation station "CAPPS", is as follows:

Latitude: 39° 39' 43.87548" N.      Longitude: 112° 02' 47.39982" W.  
N.A.D. 1983 (1994) Elev. 5656 ft.

The geographic position of National Geodetic Survey triangulation station "DYER", is as follows:

Latitude: 39° 40' 21.25464" N.      Longitude: 112° 15' 40.12772" W.  
N.A.D. 1983 (1994) Elev. 5112 ft.

The mean magnetic declination as projected from U.S. Geological Survey "Magnetic Declination Map of 1990", is 13 1/2° E.

---

Dependent Resurvey of a Portion of the South Boundary,  
T. 14 S., R. 3 W., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by  
S.M. Richardson in 1884

---

Beginning at the southeast corner of section 36, T. 14 S., R. 3 W. only, monumented with a granite stone, 16x12x10 inches, firmly set in a mound of stone, plainly marked with 6 notches on N, S, E, and W edges, with a 2 inch aluminum cap on a 5/8 inch rebar alongside, with aluminum cap marked: T14S., R3W., T14S R3W, S36 and PLS 6464 - Commowealth Assoc. Inc.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 inches diameter, 18 inches in the ground to bedrock, and in a mound of stone, 4 ft. base, to top of aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T14S	
R3W	R2W
<hr style="width: 50%; margin: 0 auto;"/>	
S36	
1996	

Deposit the marked stone and rebar alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 89° 51.6' W., along the south boundary of section 36.

**21.506** Point for the closing corner of section 1, T. 15 S., R. 3 W., and section 31, T. 14 S., R. 2 W.

From this point, the closing corner of section 1, T. 15 S., R. 3 W., and section 31, T. 14 S., R. 2 W., monumented with an aluminum post, 2 1/2 inches diameter, 8 inches above ground, with aluminum cap marked as described in the official record of 1997 resurvey under Group No. 861, bears N. 0° 13.5' E., 0.164 chains distance.

This corner has the original quartzite stone buried alongside and a mound of stone, 4 ft. base by 3 ft. high, to the south.

Remove the aluminum post closing corner, add marks AM and rebury the quartzite stone in place, which will now function as an amended monument and dismantle mound of stone.

Reset the aluminum post closing corner at the true intersect point for the closing corner, 22 inches in the ground to bedrock, in a collar of stone, with 2000 added to the aluminum cap.

Raise a mound of stone, 4 ft. base by 3 ft. high, south of corner.

Corner is located on a gradual west slope about 96 links west of a dirt road, 15 ft. wide, bears NW and SE.

From this new closing corner position, the closing corner for section 6, T. 15 S., R. 2 W., and section 31, T. 14 S., R. 2 W., monumented with an iron post, 2 1/2 inches diameter, 14 inches above ground, firmly set in a collar of stone, with brass cap marked as described in the official record of the 1912 survey, bears S. 0° 13.5' W., 33.043 chains distance.

**40.744** Point for the 1/4 section corner of section 36 only, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T14S R3W	
1/4	S36
<hr style="width: 50%; margin: 0 auto;"/>	
T15S	
2000	

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

*CHAINS*

Deposit a Deep 1 magnet at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Raise a mound of stone, 4 ft. base by 2 ft. high, north of the corner.

Corner is located in sagebrush.

**62.854** Point for the 1/4 section corner of section 1 only, T. 15 S., R. 3 W., midpoint between closing corners.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T14S
-----
1/4 S1
T15S R3W
2000

Deposit a Deep 1 magnet at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner is located on an east slope, 50 links north of a draw, drains NE.

**81.488** Point for the corner of sections 35 and 36 only, on the south boundary of the township, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T14S R3W
S35   S36
-----
T15S
2000

Deposit a Deep 1 magnet at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner is located in sagebrush and greasewood.

---

N. 89° 51.6' W., along the south boundary of section 35.

**20.372** Point for the E 1/16 section corner of section 35 only.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

*CHAINS*

T14S R3W  
E 1/16 S35  
T15S  
2000

Deposit a Deep 1 magnet at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Raise a mound of stone, 4 ft. base by 2 ft. high, north of the corner.

Corner is located in a reseeded area.

**22.714** Point for the closing corner of sections 1 and 2, T. 15 S., R. 3 W., at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 16 inches in the ground to solid rock, in a mound of stone, 4 ft. base to top of aluminum cap marked:

T14S  
S35  
S2 | S1  
C | C  
T15S R3W  
2000

Deposit a Deep 1 magnet at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner is located in a reseeded area.

**40.744** Point for the south 1/4 section corner of section 35 only, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T14S R3W  
1/4 S35  
2000

Deposit a Deep 1 magnet at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner is located in a reseeded area.

**81.488** The corner of sections 34 and 35 only, on the south boundary of the township, monumented with a granite stone, 14x10x4 inches, in a small mound of stone, marked with 2 notches on the E and 4 notches on the W edges.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

*CHAINS*

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T14S R3W
<u>S34   S35</u>
S2
2000

Deposit the marked stone alongside the aluminum post.

Corner is located 50 links north of a small draw draining ENE, and in scattered juniper and sagebrush.

---

N. 89° 35.2' W., along the south boundary of section 34.

**22.556** Point for the closing corner of sections 2 and 3, T. 15 S., R. 3 W., at proportionate distance; there is no remaining evidence of the original corner.

Set a rebar, 12 inches long, 3/4 inches diameter, in a 6 inch drill hole, with aluminum cap marked:

T14S R3W
<u>S3   S2</u>
C   C
T15S R3W
2000

Raise a mound of stone, 4 ft. base by 3 ft. high, south of the corner.

Corner is located 30 links west of rock outcrop.

**40.642** The south 1/4 section corner of section 34 only, monumented with an iron stone, 34x10x8 inches, marked 1/4 on W face.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 10 inches in the ground to bedrock, with a mound of stone, 4 ft. Base to top of brass cap marked:

T14S R3W
<u>1/4   S34</u>
1999

Deposit the marked stone alongside the stainless steel post.

Corner is located on top of small spur sloping east in juniper and sagebrush.

---

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

*CHAINS*

N. 88° 59.3' W., beginning new measurement.

- 39.009** The corner of sections 33 and 34 only, on the south boundary of the township, monumented with an iron post, 2 inches diameter, 18 inches above ground, in a mound of stone, 3 ft. base, 16 inches high around corner, with brass cap marked as described in the official record of the 1919-1920 resurvey.

Rebuild mound of stone 6 ft. base to top of brass cap.

---

Dependent Resurvey of the East Boundary,  
T. 14 S., R. 3 W., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by S.M. Richardson in 1884,  
and the Retracement Executed by Stewart and Heist in 1912

---

From the southeast corner of section 36 only, T. 14 S., R. 3 W., hereinbefore described.

N. 0° 18.5' E., along the east boundary of section 36.

- 7.066** Point for the west 1/4 section corner of section 31 only, T. 14 S., R. 2 W., at midpoint between closing corners. Not monumented.

- 40.890** The East 1/4 section corner of section 36 only, monumented with a granite stone, 16x14x10 inches, firmly set and marked 1/4 on west face, and with a 1/2 in. rebar in a small mound of stone, with a 2 inch aluminum cap marked: Commonwealth Assoc Inc. Land Cor, 1/4 S36 R3W R2W RLS 6464 T14S.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T14S  
R3W R2W  
1/4 |  
S36 |  
2000

Deposit the rebar and marked stone alongside the aluminum post.

Rebuild the mound of stone, 4 ft. base by 3 ft. high, west of the corner.

Corner is located in juniper, sagebrush and bunchgrass.

---

DEPENDENT RESURVEY OF EAST BOUNDARY,  
T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 2° 47.5' W., beginning new measurement.

- 6.237** From this point, the closing corner of sections 30 and 31, T. 14 S., R. 2 W., monumented with a 2 inch iron post, firmly set, 12 inches above ground, with brass cap marked as described in the official record of the 1912 survey and retracement, bears East, 0.079 chains distance.

From which

A cedar, 12 inches diameter, with healed blaze, bears N. 20° E.,  
26.5 links distance.

A cedar, 8 inches diameter, with open blaze, bears S. 25° E.,  
79 links distance.

This corner now functions as an amended monument. Add AM and 2000  
to brass cap.

Raise a collar of stone, 3 ft. base by 1 ft. high around 2 inch iron post.

Set a steel fence post alongside the iron post.

- 41.935** The corner of sections 25 and 36 only, monumented with a sandstone, 11x10x8 inches, firmly set, marked with 1 notch on S edge and no other marks visible.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground to bedrock, with a mound of stone, 4 ft. base to top of aluminum cap, marked:

	T14S	
	R3W	R2W
S25		S30
S36		
	1996	

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner is located on S slope in juniper and sagebrush.

---

N. 0° 20.4' W., along the east boundary of section 25.

- 4.296** Point for the west 1/4 section corner of section 30 only, T. 14 S., R. 2 W., not monumented.

DEPENDENT RESURVEY OF EAST BOUNDARY,  
T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

*CHAINS*

**39.711** The east 1/4 section corner of section 25 only, monumented with a mound of stone is harmoniously related to identified original corners, and is accepted as the best available evidence of the original corner position.

At the corner point (center of mound)

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground to bedrock, in a mound of stone, 4 ft. base to top of aluminum cap marked:

T14S  
R3W R2W  
1/4 |  
S25 |  
1996

Deposit a Deep 1 magnet at the base of the aluminum post.

Corner is located on a NNE slope in juniper, sagebrush and bunchgrass.

N. 0° 03.8' W., beginning new measurement.

**4.538** The closing corner of sections 19 and 30, T. 14 S., R. 2 W., monumented with an iron post, 2 inches diameter, firmly set, 4 inches above ground, in a mound of stone, 4 ft. base by 1 ft. high, with brass cap marked as described in the official record of the 1912 survey and retracement:

From which

A cedar stump, 4 inches diameter, bears N. 60° E., 1.54 chains distance.

A cedar, 14 inches diameter, bears S. 20° E., 0.35 chs. distance.

Set a steel fence post alongside mound of stone.

**40.998** The corner of sections 24 and 25 only, monumented with a granite stone, 18x13x12 inches, loosely set, marked with 2 notches on S and 4 notches on N edges.

From which

A cedar, 20 inches diameter, marked T14S R3W S25 BT in an open blaze, bears N. 81° W., 21 links distance.

DEPENDENT RESURVEY OF EAST BOUNDARY,  
T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

*CHAINS*

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground to bedrock, and in a mound of stone, 4 ft. base to top of aluminum cap marked:

T14S	
R3W	R2W
S24	S19
S25	
1996	

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 0° 32.3' E., along the east boundary of section 24.

**3.597** Point for the west 1/4 section corner of section 19 only, T. 14 S., R. 2 W., at midpoint between closing corners.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of aluminum cap, marked:

T14S	
R3W	R2W
	1/4
	S19
2000	

Deposit a Deep 1 magnet at base of the aluminum post.

Corner is located 1 link west of an old barb wire fence that bears north and south.

Corner is located on a steep SE slope in juniper, sagebrush and bunchgrass.

**41.274** The east 1/4 section corner of section 24 only, monumented with a scattered mound of stone, is harmoniously related to identified original corners, and is accepted as the best available evidence of the original corner position.

At the corner point (center of mound)

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T14S	
R3W	R2W
1/4	
S24	
2000	

DEPENDENT RESURVEY OF EAST BOUNDARY,  
T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposit a Deep 1 magnet at base of the aluminum post.

Corner is located 10 links north of a draw, draining W, in juniper, sagebrush and bunchgrass area.

---

N. 0° 21.4' E., beginning new measurement.

- 2.380** The closing corner of sections 18 and 19, T. 14 S., R. 2 W., monumented with an iron post, 2 inches diameter, 14 inches above ground, firmly set in a mound of stone, with brass cap marked as described in the official record of the 1912 survey and retracement.

From which

A cedar, 10 inches diameter, bears N. 57° E., 28 links distance.

A cedar, 12 inches diameter, bears S. 35° E., 44 links distance.

Set a steel fence post alongside the mound of stone.

- 40.393** The corner of sections 13 and 24 only, monumented with a granite stone, 20x13x6 inches, firmly set and plainly marked with 3 notches on N and S edges, with a small mound of stone to the west of the granite stone.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T14S	
R3W	R2W
S13	S18
S24	
2000	

Deposit a Deep 1 magnet at the base of the aluminum post.

Deposit the marked stone alongside the aluminum post.

Rebuild the mound of stone, 4 ft. base by 2 ft. high, west of aluminum post.

Corner is located on a SSW slope in juniper, sagebrush and bunchgrass.

---

N. 0° 32.9' W., along the east boundary of section 13.

- 2.032** Point for the west 1/4 section corner of section 18 only, T. 14 S., R. 2 W., at midpoint between closing corners.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground to bedrock, in a mound of stone, 3 ft. base to top of aluminum cap, marked:

DEPENDENT RESURVEY OF EAST BOUNDARY,  
T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T14S  
R3W R2W  
| 1/4  
S18  
2000

Deposit a Deep 1 magnet at base of the aluminum post.

Corner is located 30 links north of a spur that bears WNW on a north slope in juniper and grass.

**41.099**

The east 1/4 section corner of section 13 only, monumented with a sandstone, 16x12x6 inches firmly set with a small mound of stone to the west, marked with 1/4 on west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T14S  
R3W R2W  
1/4 |  
S13 |  
2000

Deposit a Deep 1 magnet at base of the aluminum post.

Deposit the marked stone alongside the aluminum post.

Rebuild the mound of stone to 4 ft. base by 2 ft. high, west of the aluminum post.

Corner is located on S slope in juniper, sagebrush and bunchgrass.

N. 0°22.0' E., beginning new measurement.

**0.977**

The closing corner of sections 7 and 18, T. 14 S., R. 2 W., monumented with an iron post, 2 inches diameter, firmly set, 18 inches above ground, with brass cap marked as described in the official record of the 1912 survey and retracement.

From which

A cedar, 6 inches diameter, bears N. 22° E., 40 links distance.

A cedar, 8 inches diameter, bears S. 30° E., 32 links distance.

**40.510**

The corner of sections 12 and 13 only, monumented with a granite stone, 16x10x6 inches, in a small mound of stone, dimly marked with 4 notches on the S and 2 notches on the N edges.

DEPENDENT RESURVEY OF EAST BOUNDARY,  
T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground to bedrock, in a mound of stone, 3 ft base, to top of aluminum cap marked:

	T14S	
	R3W	R2W
S12		S7
S13		
	2000	

Deposit a Deep 1 magnet at base of the aluminum post.

Deposit the marked stone alongside the aluminum post.

Corner is located on a steep south slope in juniper and bunchgrass.

N. 1° 23.8' E., along east boundary of section 12.

**0.472** Point for the west 1/4 section corner of section 7 only, T. 14 S., R. 2 W., at midpoint between closing corners.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 16 inches in the ground to bedrock, in a mound of stone, 5 ft. base to top of aluminum cap marked:

	T14S	
	R3W	R2W
		1/4
		S7
	2000	

Corner is located on a steep S slope in juniper and bunchgrass.

**40.473** The closing corner of sections 6 and 7, T. 14 S., R. 2 W., monumented with an iron post, 2 inches diameter, firmly set in a mound of stone, 3 ft. base to top of brass cap marked as described in the official record of the 1912 survey and retracement.

No other improvements were made at this location.

**40.726** The east 1/4 section corner of section 12 only, monumented with a sandstone, 12x8x7 inches firmly set, marked 1/4 on W face, with a small mound of stone to the W.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF EAST BOUNDARY,  
T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T14S  
R3W R2W  
1/4 |  
S12 |  
1996

Deposit a Deep 1 Magnet at base of the aluminum post.

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

---

N. 0° 26.3' E., beginning new measurement.

**39.756** Point for the west 1/4 section corner of section 6 only, T. 14 S., R. 2 W., at proportionate distance between closing corners.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T14S  
R3W R2W  
| 1/4  
| S6  
2000

Raise a mound of stone, 3 ft. base by 2 ft. high, east of the aluminum post.

**41.035** The corner of sections 1 and 12 only, monumented with a mound of stone, is harmoniously related to identified original corners and is accepted as the best available evidence of the original corner position.

At the corner point (mound of stone)

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T14S  
R3W R2W  
— S1 | S6  
S12 |  
1996

Set a steel fence post alongside the aluminum post.

Raise a mound of stone to the west of the aluminum post.

---

DEPENDENT RESURVEY OF EAST BOUNDARY,  
T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 4° 50.4' E., along the east boundary of section 1.

**12.025**

The closing corner of section 6, T. 14 S., R. 2 W., and section 31, T. 13 S., R. 2 W., monumented with a granite stone, 14x8x8 inches firmly set and plainly mkd. 6 notches on the N, S, and E edges and a CC on the E face.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with brass cap marked:

T14S	T13S	
R3W	R2W	
	C	S31
	C	S6
S1	T14S	
	R2W	
		1996

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.



N. 0° 09.5' E., beginning new measurement.

**29.230**

Point for the east 1/4 section corner of section 1 only, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T14S	T13S	
R3W	R2W	
1/4		
S1		
		1996

Set a steel fence post alongside the aluminum post.

**39.904**

Point for west 1/4 section corner of section 31 only, T. 13 S., R. 2 W., at midpoint between closing corners.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF EAST BOUNDARY,  
T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T13S  
R2W  
| 1/4  
S31  
1996

Set a steel fence post alongside the aluminum post.

**57.872**

The closing corner of section 1, T. 14 S., R. 3 W., and section 31, T. 13 S., R. 2 W., monumented with a trachyte stone, 18x10x8 inches, firmly set, 8 inches above ground, plainly marked with 6 notches on the W, 1 notch on S, and 5 notches on N edges, also a CC marked on S face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap, marked:

T13S R3W  
-----  
S36  
S1 | S31  
C | C  
R3W R2W  
T14S T13S  
1996

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

Dependent Resurvey of a Portion of the North Boundary,  
T. 14 S., R. 3 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by R. Gorlinski in 1872,  
and the Resurvey Executed by S.M. Richardson in 1884

From the southeast corner of section 36 only, T. 13 S., R. 3 W., monumented with an aluminum post, 2 1/2 inches diameter, 6 inches above ground, and a steel fence post alongside, with aluminum cap marked as described in the official record of the 1996 resurvey under Group No. 859.

From this corner, the closing corner of sections 30 and 31, T. 13 S., R. 2 W., monumented with an aluminum post, 2 1/2 inches diameter, 6 inches above ground, with aluminum cap marked as described under the concurrent resurvey of Group No. 859, bears N. 0° 03.8' E., 22.000 chains distance.

N. 89° 49.2' W., along the south boundary of section 36, T. 13 S., R. 3 W.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

- 13.484** The closing corner of section 1, T. 14 S., R. 3 W., and section 31, T. 13 S., R. 2 W., hereinbefore described.
- 40.232** Point for the south 1/4 section corner of section 36 only, T. 13 S., R. 3 W., at proportionate distance; there is no remaining evidence of the original corner.
- Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground to bedrock, in a collar of stone, with aluminum cap marked:
- $$\begin{array}{r} \text{T13S R3W} \\ \hline \text{1/4 S36} \\ \hline \text{T14S R3W} \\ 1996 \end{array}$$
- Set a steel fence post alongside the aluminum post.
- 54.138** Point for the north 1/4 section corner of section 1 only, at midpoint between closing corners.
- Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap, marked:
- $$\begin{array}{r} \hline \text{T13S R3W} \\ \hline \text{1/4 S1} \\ \hline \text{T14S R3W} \\ 1996 \end{array}$$
- Set a steel fence post alongside the aluminum post.
- 80.464** Point for the corner of sections 35 and 36 only, on the south boundary T. 13 S., R. 3 W., at proportionate distance; there is no remaining evidence of the original corner.
- Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:
- $$\begin{array}{r} \text{T13S R3W} \\ \hline \text{S35 | S36} \\ \hline \text{S1} \\ \hline \text{T14S R3W} \\ 1996 \end{array}$$
- Set a steel fence post alongside the aluminum post.
- 
- N. 89° 49.2' W., along the south boundary of section 35, T. 13 S., R. 3 W.
- 14.328** Point for the closing corner of sections 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.
- Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, in a collar of stone, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T13S R3W
S35
C   C
S2   S1
T14S R3W
1996

Set a steel fence post alongside the aluminum post.

- 40.232** The 1/4 section corner of section 35 only, T. 13 S., R. 3 W., monumented with an iron post, 2 1/2 inches diameter, firmly set, 10 inches above ground, with brass cap marked as described in the official record of the 1960 resurvey.

---

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 14 S., R. 3 W., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by  
S.M. Richardson, in 1884

---

From the corner of sections 35 and 36 only, on the south boundary of the township, hereinbefore described.

N. 1° 42.3' W., between sections 35 and 36.

- 20.191** Point for the S 1/16 section corner of sections 35 and 36.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T14S R3W
S 1/16
S35   S36
2000

Deposit a Deep 1 magnet at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner is located 1 chain north of base of hill that bears NW and SE, and in thin tamarisk and sagebrush.

- 40.382** Point for the 1/4 section corner of sections 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T14S R3W  
1/4  
S35 | S36  
2000

Deposit a Deep 1 magnet at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner is located in the Sevier Canyon River bottom.

**80.764**

The corner of sections 25, 26, 35, and 36, monumented with a 1/2 inch rebar, firmly set, 3 inches above ground, with a 2 inch aluminum cap marked: COMMONWEALTH ASSOC LAND COR S25 S26 S35 S36 RLS 6484 T14S R3W. This corner is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T14S R3W  
S26 | S25  
S35 | S36  
2000

Put rebar and aluminum cap inside the aluminum post.

Deposit a Deep 1 magnet at base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner is located 2.00 chains N of Sevier River, drains E.

From the corner of sections 25 and 36 only, on the east boundary of the township, hereinbefore described.

S. 88° 42.8' W., between sections 25 and 36.

**41.034**

Point for the 1/4 section corner of sections 25 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T145S R3W  
1/4     S25  
         S36  
         2000

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

*CHAINS*

Deposit a Deep 1 magnet at base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner is located at base of a knoll which bears E and W, on S slope.

**61.551** Point for the W 1/16 section corner of sections 25 and 36.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

	T14S R3W
W 1/16	<u>S25</u>
	S36
	2000

Deposit a Deep 1 magnet at base of the aluminum post.

Set a steel fence post alongside the aluminum post.

**82.068** The corner of sections 25, 26, 35, and 36.

---

N. 0° 54.1' W., between sections 25 and 26.

**20.451** Point for the S 1/16 section corner of sections 25 and 26.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

	T14S R3W
	S 1/16
S26	S25
	2000

Deposit a Deep 1 magnet at base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner is located 1.50 chains E of Sevier river, drains NW.

**40.902** Point for the 1/4 section corner of sections 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T14S R3W  
1/4  
S26 | S25  
2000

Deposit a Deep 1 magnet at base of the aluminum post.

Corner is located 22.7 links west of railroad tracks.

**81.804**

The corner of sections 23, 24, 25, and 26, monumented with a flintstone, 12x10x8 inches, plainly marked with 2 notches on the S and 1 notch on the E edges.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with brass cap marked:

T14S R3W  
S23 | S24  
S26 | S25  
1999

Deposit the marked stone alongside the stainless steel post

Set a steel fence post alongside the stainless steel post.

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the corner.

Corner is located on a W slope in sagebrush and scattered juniper.

From the corner of sections 24 and 25 only, on the east boundary of the township, hereinbefore described.

S. 89° 28.6' W., between sections 24 and 25.

**41.521**

Point for the 1/4 section corner of sections 24 and 25, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground to bedrock, and in a mound of stone, 3 ft. base, to top of aluminum cap marked:

T14S R3W  
1/4     S24  
         S25  
         2000

Deposit a Deep 1 magnet at base of the aluminum post.

Corner is located on steep W slope in juniper, sagebrush, and bunchgrass.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

*CHAINS*

**83.042** The corner of sections 23, 24, 25, and 26.

---

N. 1° 55.4' W., between sections 23 and 24.

**40.434** The 1/4 section corner of sections 23 and 24, monumented with a flintstone, 12x6x5 inches, marked 1/4 on the W face with a small mound of stone to the west.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T14S	R3W
	1/4
S23	S24
	1999

Deposit the marked stone alongside the stainless steel post.

Rebuild the mound of stone, 3 ft. base by 2 ft. high, west of the corner.

Corner is located on a SE slope.

---

N. 0° 56.1' W., beginning new measurement.

**40.825** The corner of sections 13, 14, 23, and 24, monumented with a limestone, 9x7x4 inches, with 4 notches on the S and 1 notch on the E edges.

At the corner point

Set a stainless steel post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with brass cap marked:

T14	R3W
S14	S13
S23	S24
	1999

Deposit the marked stone alongside the stainless steel post.

Raise a mound of stone, 2 ft. base by 1 ft. high, west of corner.

Corner is located on top of a spur that bears SSE, in greasewood and June grass.

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the corner of sections 13 and 24 only, on the east boundary of the township, hereinbefore described.

S. 89° 12.3' W., between sections 13 and 24.

**42.846** Point for the 1/4 section corner of sections 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground to bedrock, in a mound of stone, 4 ft. base, to top of aluminum cap marked:

	T14S R3W.
1/4	$\frac{S13}{S24}$
	2000

Deposit a Deep 1 magnet at base of the aluminum post.

Corner is located on top of a small spur sloping NW.

**85.692** The corner of sections 13, 14, 23, and 24.

---

N. 0° 18.7' W., between sections 13 and 14.

**41.437** The 1/4 section corner of sections 13 and 14, monumented with a flintstone, 19x9x8 inches, marked 1/4 on the W face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

	T14S R3W
	1/4
S14	S13
	1999

Deposit a Deep 1 magnet at base of the aluminum post.

Deposit the marked stone alongside the aluminum post.

Corner is located in bottom of small draw, drains NE.

---

N. 0° 52.6' E., beginning new measurement.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

**41.299**

The corner of sections 11, 12, 13, and 14, monumented with an aluminum post, 2 1/2 inches diameter, firmly set in a mound of stone to top of aluminum cap marked JUAB COUNTY T14S R3W S11 S12 S13 S14 1986. This corner is accepted as the best available evidence of the original corner position.

No other improvements were made at this location.

---

From the corner of sections 12 and 13 only, on the east boundary of the township, hereinbefore described.

S. 89° 57.5' W., between sections 12 and 13.

**42.562**

Point for the 1/4 section corner of sections 12 and 13, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

	T14S R3W
1/4	<u>S12</u>
	S13
	2000

Raise a mound of stone, 3 ft. base by 2 ft. high, north of the aluminum post.

Corner is located 75 links west of the west right-of-way fence of Utah State Highway No. 132, bears NE and SW.

**85.124**

The corner of sections 11, 12, 13, and 14.

---

N. 0° 15.7' E., between sections 11 and 12.

**41.217**

Point for the 1/4 section corner of sections 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

	T14S R3W
	1/4
S11	S12
	2000

Raise a mound of stone, 3 ft. base by 2 ft. high, west of the corner.

Corner is located on a spur that bears ESE and about 3.00 chains east of a power line.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

**82.434**

The corner of sections 1, 2, 11, and 12, monumented with a 3/4 inch rebar, firmly set and 9 inches above ground, with aluminum cap marked LOYAL D OLSON T14S S2 S1 S11 S12 R3W RLS 4954. This corner is accepted as the best available evidence of the original corner position.

Raise a mound of stone, west of the rebar.

Set a steel fence post in the mound of stone.

---

From the corner of sections 1 and 12, on the east boundary of the township, hereinbefore described.

N. 88° 33.7' W., between sections 1 and 12.

**42.545**

The 1/4 section corner of sections 1 and 12, monumented with a limestone, 16x11x6 inches, firmly set and dimly marked 1/4 on west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

	T14S R3W			
1/4	<table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S1</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S12</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">1996</td> </tr> </table>	S1	S12	1996
S1				
S12				
1996				

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

---

S.89° 24.7' W., beginning new measurement.

**43.505**

The corner of sections 1, 2, 11, and 12.

---

N. 3° 27.0' E., between sections 1 and 2.

**39.271**

The 1/4 section corner of sections 1 and 2, monumented with a sandstone, 22x8x5 inches, firmly set and dimly marked 1/4 on W face, with a small mound of stone to the west.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground to bedrock, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T14S R3W  
1/4  
S2 | S1  
1996

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 6° 38.2' E., beginning new measurement.

**30.492** The closing corner of sections 1 and 2, on the north boundary of the township, hereinbefore described.

From the corner of sections 34 and 35 only, on the south boundary of the township, hereinbefore described.

N. 0° 24.6' E., between sections 34 and 35.

**40.557** Point for the 1/4 section corner of sections 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with aluminum cap marked:

T14S R3W  
1/4  
S34 | S35  
2000

Deposit Deep 1 magnet alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

Raise a mound of stone, 3 ft. base by 1 1/2 ft. high, west of the corner.

Corner is located on west slope, 3.00 chains south from the bottom of a draw, drains E.

**81.114** The corner of sections 26, 27, 34, and 35, monumented with a flintstone, 12x7x7 inches, dimly marked with 1 notch on S and 2 notches on E edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 6 inches in the ground to solid rock, in a mound of stone, 5 ft. base to top of aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T14S R3W	
<u>S27</u>	<u>S26</u>
S34	S35
2000	

Deposit a Deep 1 magnet at base of the aluminum post.

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

---

From the corner of sections 23, 24, 25, and 26.

N. 89° 54.8' W., between sections 23 and 26.

**42.209** Point for the 1/4 section corner of sections 23 and 26, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T14S R3W	
1/4	<u>S23</u>
	S26
	2000

Set a steel fence post alongside the aluminum post.

**84.418** The corner of sections 22, 23, 26, and 27, monumented with a granite stone, 30x18x6 inches, firmly set and marked with 2 grooves on S face and 2 notches on E edge, with a mound of stone, NE of the corner.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground to bedrock, in a mound of stone, 4 ft. base to top of aluminum cap marked:

T14S R3W	
<u>S22</u>	<u>S23</u>
S27	S26
1996	

Deposit the marked stone alongside the aluminum post.

Corner is located on a NW slope covered with sagebrush and juniper.

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

N. 0° 15.9' W., between sections 22 and 23.

**20.192** Point for the S 1/16 section corner of sections 22 and 23.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T14S R3W  
S 1/16  
S22 | S23  
1996

**40.384** The 1/4 section corner of sections 22 and 23, monumented with a limestone, 15x12x8 inches, marked 1/4 on west face, and a mound of stone to the west.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground to bedrock, in a mound of stone, 4 ft. base, to top of aluminum cap marked:

T14S R3W  
1/4  
S22 | S23  
1996

N. 0° 45.7' E., beginning new measurement.

**41.716** The corner of sections 14, 15, 22, and 23, monumented with a sandstone, 18x14x7 inches, with no markings found, located by a mound of stone.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 6 inches in the ground to solid rock, in a mound of stone, 6 ft. base, to top of aluminum cap marked:

T14S R3W  
S15 | S14  
S22 | S23  
2000

From the corner of sections 13, 14, 23, and 24.

N. 89° 18.3' W., between sections 14 and 23.

**41.007** Point for the 1/4 section corner of sections 14 and 23, at proportionate distance; there is no remaining evidence of the original corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

$$\begin{array}{r} \text{T14S R3W} \\ 1/4 \quad \frac{\text{S14}}{\text{S23}} \\ \hline 2000 \end{array}$$

Raise a mound of stone, 3 ft. base by 2 ft. high north of the aluminum post.

Corner is located 3 links east of a power line which bears NE and SW, on an E slope in juniper and sagebrush.

**82.014** The corner of sections 14, 15, 22, and 23.

---

N. 0° 19.5' E., between sections 14 and 15.

**41.834** Point for the 1/4 section corner of sections 14 and 15, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

$$\begin{array}{r} \text{T14S R3W} \\ 1/4 \\ \text{S15} \quad | \quad \text{S14} \\ \hline 2000 \end{array}$$

Raise a mound of stone, 3 ft. base by 2 ft. high west of corner.

**83.668** The corner of sections 10, 11, 14, and 15, monumented with a 3/4 inch Rebar, firmly set, with a mound of stone, 3 ft. base by 2 ft. high, west of rebar corner, with a 3 1/4 inches diameter, aluminum cap marked T14S LOYAL D OLSON S10 S11 S14 S15 R3W 1992 RLS 4954. This corner is accepted as the best available evidence of the original corner position. No other improvements were made at this location.

---

From the corner of sections 11, 12, 13, and 14.

N. 89° 06.1' W., between sections 11 and 14.

**40.672** The 1/4 section corner of sections 11 and 14, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, 12 inches above ground with aluminum cap marked JUAB COUNTY T14S R3W 1/4 S11 S14 1987. This corner is accepted as the best available evidence of the original corner position.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

*CHAINS*

From which:

A cedar, marked 1/4 BT on an open blaze, bears S. 17° E.,  
32 links distance. (Record, S. 5° E., 40 links distance.)

Build a mound of stone around aluminum post, 3 ft. base to top of aluminum cap.

Set a steel fence post alongside the aluminum post.

Raise a mound of stone, 3 ft. base by 2 ft. high, north of the corner.

---

N. 88° 12.3' W., beginning new measurement.

**41.276** The corner of sections 10, 11, 14, and 15.

---

From the 1/4 section corner of sections 27 and 28, monumented with a sandstone, 14x10x6 inches, firmly set in a small mound of stone, marked 1/4 on W face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T14S R3W  
1/4  
S28 | S27  
1996

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 1° 00.3' E., between sections 27 and 28.

**20.330** Point for the N 1/16 section corner of sections 27 and 28, falls in the Sevier River; not monumented.

**40.660** The corner of sections 21, 22, 27, and 28, monumented with a granite stone, 15x10x7 inches, plainly marked with 2 notches on the S and 3 notches on the E edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

T14S R3W	
<u>S21</u>	<u>S22</u>
S28	S27
1996	

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

---

From the corner of sections 22, 23, 26, and 27.

N. 89° 57.2' W., between sections 22 and 27.

**20.360** Point for the E 1/16 section corner of sections 22 and 27.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground to bedrock, in a collar of stone, with aluminum cap marked:

T14S R3W	
E 1/16	<u>S22</u>
	S27
1996	

Set a steel fence post alongside the aluminum post.

**40.720** Point for the 1/4 section corner of sections 22 and 27, at proportionate distance; there is no remaining evidence of the original corner

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T14S R3W	
1/4	<u>S22</u>
	S27
1996	

Set a steel fence post alongside the aluminum post.

**81.440** The corner of sections 21, 22, 27, and 28.

---

N. 0° 35.5' W., between sections 21 and 22.

**40.792** The 1/4 section corner of sections 21 and 22, monumented with a limestone, 14x10x4 inches, dimly marked 1/4, with the stone being in the center of the mound.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground to bedrock, in a mound of stone, 3 ft. base to top of aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

*CHAINS*

T14S R3W  
1/4  
S21 | S22  
1996

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

---

N. 0° 14.4' W., beginning new measurement.

**37.792** The corner of sections 15, 16, 21, and 22, monumented with a sandstone, 15x10x7 inches with no visible marks found, in a mound of stone.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T14S R3W  
S16 | S15  
S21 | S22  
1996

Deposit the unmarked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

---

From the corner of sections 14, 15, 22, and 23.

S. 89° 39.8' W., between sections 15 and 22.

**40.150** The 1/4 section corner of sections 15 and 22, monumented with a limestone, 14x10x10 inches, firmly set in a mound of stone, dimly marked 1/4 on N face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground to bedrock, in a mound of stone, 4 ft. base, to top of aluminum cap marked:

T14S R3W  
1/4    S15  
         S22  
         1996

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

S. 85° 38.8' W., beginning new measurement.

**42.340** The corner of sections 15, 16, 21, and 22.

---

From the corner of sections 28, 29, 32, and 33, monumented with a private 2 1/2 inches brass cap, firmly set in concrete, in an old E and W fence line with brass cap marked T14S 28 29 32 33 R3W 1980. This corner is accepted as the best available evidence of the original corner position. No other improvements were made at this location.

N. 1° 17.0' W., between sections 28 and 29.

**40.358** Point for the 1/4 section corner of sections 28 and 29, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 10 inches in the ground to solid rock, in a mound of stone, 5 ft. base to top of aluminum cap marked:

T14S	R3W
1/4	
29	28
2000	

Set a steel fence post alongside the aluminum post.

Corner is located on S slope in juniper.

**60.537** Point for the N 1/16 section corner of sections 28 and 29.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T14S	R3W
N 1/16	
29	28
2000	

**80.716** The corner of sections 20, 21, 28, and 29, monumented with a limestone, 20x12x6 inches with no visible marking, deeply embedded in a mound of stone.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground to bedrock, in a mound of stone, 4 ft. base to top of aluminum cap marked:

T14S	R3W
S20	S21
S29	S28
1996	

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the corner of sections 21, 22, 27, and 28.

S. 89° 44.1' W., between sections 21 and 28.

**37.730** Point for the 1/4 section corner of sections 21 and 28, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

	T14S R3W
1/4	$\frac{S21}{S28}$
	2000

Deposit a Deep 1 magnet at base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Raise a small mound of stone, to the north of the corner.

**56.595** Point for the W 1/16 section corner of sections 21 and 28.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

	T14S R3W
W 1/16	$\frac{S21}{S28}$
	2000

Deposit a Deep 1 magnet at base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Raise a mound of stone, 3 ft. base by 2 ft. high, north of the corner.

**75.460** The corner of sections 20, 21, 28, and 29.

---

The Subdivision of Section 22,  
T. 14 S., R. 3 W., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 22 and 27.

N. 0° 39.0' E., on the N-S center line of section 22.

**20.299** Point for the center S 1/16 section corner of section 22; not monumented.

THE SUBDIVISION OF SECTION 22,  
T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

**40.598** Point for the center 1/4 section corner of section 22, at intersection with the E-W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T14S R3W  
C 1/4  
S22  
1996

Set a steel fence post alongside the aluminum post.

**81.833** The 1/4 section corner of sections 15 and 22.

---

From the 1/4 section corner of sections 22 and 23.

N. 89° 39.4' W., on the E-W center line of section 22.

**20.037** Point for the center E 1/16 section corner of section 22; not monumented.

**40.074** The center 1/4 section corner of section 22.

**81.678** The 1/4 section corner of section 21 and 22.

---

From the E 1/16 section corner of sections 22 and 27.

N. 0° 11.6' E., on the N-S center line of the SE 1/4 of section 22.

**20.246** Point for the SE 1/16 section corner of section 22, at intersection with the E-W center line of the SE 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T14S R3W  
SE 1/16  
S22  
1996

Set a steel fence post alongside the aluminum post.

**40.491** The point for the center E 1/16 section corner of section 22.

---

From the S 1/16 section corner of sections 22 and 23.

N. 89° 48.2' W., on the E-W center line of the SE 1/4 of section 22.

THE SUBDIVISION OF SECTION 22,  
T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

**20.197** The SE 1/16 section corner of section 22.

**40.394** The point for the center S 1/16 section corner of section 22.

---

The Subdivision of Section 25,  
T. 14 S., R. 3 W., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 25 and 36.

N. 0° 33.2' W., on the N-S center line of section 25.

**20.155** Point for the center S 1/16 section corner of section 25; not monumented.

**40.310** Point for the center 1/4 section corner of section 25; at intersection with the E-W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T14S R3W  
C 1/4  
S25  
2000

Raise a mound of stone, 4 ft. base by 3 ft. high, west of the corner.

**81.255** The 1/4 section corner of sections 24 and 25.

---

From the 1/4 section corner of section 25 only, on the east boundary of the township, hereinbefore described.

S. 89° 32.2' W., on the E-W center line of section 25.

**41.174** The center 1/4 section corner of section 25.

**61.812** Point for the center W 1/16 section corner of section 25; not monumented.

**82.450** The 1/4 section corner of sections 25 and 26.

---

From the W 1/16 section corner of sections 25 and 36.

N. 0° 43.8' W., on the N-S center line of the SW 1/4 of section 25.

**20.303** Point for the SW 1/16 section corner of section 25; at intersection with the E-W center line of the SW 1/4.

THE SUBDIVISION OF SECTION 25,  
T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground to bedrock, in a mound of stone, 3 ft. base to top of aluminum cap marked:

T14S R3W  
SW 1/16  
S25  
2000

Deposit a Deep 1 magnet at base of the aluminum post.

Corner is located in the bottom of small wash, drains W.

**40.606** The point for the center W 1/16 section corner of section 25.

---

From the point for the center S 1/16 section corner of section 25.

S. 89° 07.5' W., on the E-W center line of the SW 1/4 of section 25.

**20.577** The SW 1/16 section corner of section 25.

**41.154** The S 1/16 section corner of sections 25 and 26.

---

The Subdivision of Section 28,  
T. 14 S., R. 3 W., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 28 and 33, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, 8 inches above ground, with aluminum cap marked JUAB COUNTY T14S R3W 1/4 S28 S33 1985. This corner is accepted as the best available evidence of the original corner position. No other improvements were made at this corner.

N. 0° 09.0' W., on the N-S center line of section 28.

**40.288** Point for the center 1/4 section corner of section 28, at intersection with the E-W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T14S R3W  
C 1/4  
S28  
2000

Set a steel fence post alongside the aluminum post.

Raise a mound of stone, 3 ft. base by 2 ft. high, west of the corner.

Corner is located 23 links north of the railroad right-of-way fence.

THE SUBDIVISION OF SECTION 28,  
T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS****60.539**

Point for the center N 1/16 section corner of section 28.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

$$\begin{array}{c} \text{T14S R3W} \\ \text{C} \\ \text{N } 1/16 \quad | \quad \text{S28} \\ \text{C} \\ 2000 \end{array}$$

Deposit a Deep 1 magnet at base of the aluminum post.

Set a steel fence post alongside the aluminum post.

**80.790**

The 1/4 section corner of sections 21 and 28.

---

From the 1/4 section corner of sections 27 and 28.

S. 89° 58.1' W., on the E-W center line of section 28.

**36.914**

The center 1/4 section corner of section 28.

**55.382**

Point for the center W 1/16 section corner of section 28.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

$$\begin{array}{c} \text{T14S R3W} \\ \text{C } \frac{\text{W } 1/16}{\text{S28}} \text{ C} \\ 2000 \end{array}$$

Set a steel fence post alongside the aluminum post.

Corner is located in bottom of a wash draining SW.

**73.850**

The 1/4 section corner of sections 28 and 29.

---

From the point for the N 1/16 section corner of sections 27 and 28.

S. 89° 51.0' W., on the E-W center line of the NE 1/4 of section 28.

**37.322**

The center N 1/16 section corner of section 28.

---

THE SUBDIVISION OF SECTION 28,  
T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the center W 1/16 section corner of section 28.

N. 0° 42.9' W., on the N-S center line of the NW 1/4 of section 28.

**20.214** Point for the NW 1/16 section corner of section 28, at intersection with the E-W center line of the NW 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T14S R3W  
NW 1/16  
S28  
2000

Deposit a Deep 1 magnet at base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner is located on a steep W slope.

**40.428** The W 1/16 section corner of sections 21 and 28.

---

From the center N 1/16 section corner of section 28.

S. 89° 51.0' W., on the E-W center line of the NW 1/4 of section 28.

**18.667** The NW 1/16 section corner of section 28.

**37.334** The N 1/16 section corner of section 28 and 29.

---

The Subdivision of Section 35,  
T. 14 S., R. 3 W., Salt Lake Meridian, Utah

---

From the 1/4 section corner of section 35 only, on the south boundary of the township, hereinbefore described.

N. 0° 03.9' W., on the N-S center line of section 35.

**20.229** Point for the center S 1/16 section corner of section 35; not monumented.

**40.458** Point for the center 1/4 section corner of section 35, at intersection with the E-W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 35,  
T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T14S R3W  
C 1/4  
S35  
2000

Deposit a Deep 1 magnet at base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Raise a mound of stone, 3 ft. base by 2 ft. high, west of the corner.

Corner is located 20 links north of a bottom of a wash, drains NE.

**81.185** The 1/4 section corner of sections 26 and 35, monumented with a broken flintstone, 8x8x5 inches, marked with 1/4 on the N face.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, in a mound of stone, 3 ft. base to top of aluminum cap marked:

T14S R3W  
1/4      $\frac{S26}{S35}$   
2000

Deposit a Deep 1 magnet at base of the aluminum post.

Deposit the broken flintstone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner is located on a N slope in sagebrush and greasewood.

From the 1/4 section corner of sections 35 and 36.

N. 89° 43.2' W., on the E-W center line of section 35.

**19.792** Point for the center E 1/16 section corner of section 35; not monumented.

**39.584** The center 1/4 section corner of section 35.

**79.988** The 1/4 section corner of sections 34 and 35.

From the E 1/16 section corner of section 35 only, on the south boundary of the township, hereinbefore described.

N. 0° 53.1' W., on the N-S center line of the SE 1/4 of section 35.

THE SUBDIVISION OF SECTION 35,  
T. 14 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

*CHAINS***20.208**

Point for the SE 1/16 section corner of section 35, at intersection with the E-W center line of the SE 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T14S R3W  
SE 1/16  
S35  
2000

Deposit a Deep 1 magnet at base of the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner is located on a steep E slope about 2.00 chains E of the top of a hill.

**40.416**

The point for the center E 1/16 section corner of section 35.

---

From the S 1/16 section corner of sections 35 and 36.

N. 89° 47.5' W., on the E-W center line of the SE 1/4 of section 35.

**20.081**

The SE 1/16 section corner of section 35.

**40.162**

The point for the center S 1/16 section corner of section 35.

---

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD ASSISTANTS**

---

<b>Name</b>	<b>Capacity</b>
Daniel W. Webb	Chief Cadastral Surveyor for Utah
Jerry L. Thomas	Cadastral Surveyor
Steven Oatman	Survey Tech
Nathan James	Survey Aid
Billy Shepard	Engineering Technician

## CERTIFICATE OF SURVEY

We, *Ronald K. Baugh and M. Ross Workman, Supervisory Cadastral Surveyors*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *3rd day of September, 1996*, we have *dependently resurveyed a portion of the south boundary, the east boundary, a portion of the north boundary, and a portion of the subdivisional lines, and subdivided sections 22, 25, 28, and 35, in Township 14 South, Range 3 West,*

of the *Salt Lake* Meridian, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

June 15, 2001

Date

Ronald K. Baugh

(Supervisory Cadastral Surveyor)

June 15, 2001

Date

M. Ross Workman

(Supervisory Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of a portion of the south boundary, the east boundary, a portion of the north boundary, and a portion of the subdivisional lines and the subdivision of sections 22, 25, 28, and 35, in Township 14 South, Range 3 West, Salt Lake Meridian, Utah,*

executed by *Ronald K. Baugh and M. Ross Workman, Supervisory Cadastral Surveyors*

having been critically examined and found correct, are hereby approved.

June 22, 2001

Date

Daniel W. Webb

(Chief Cadastral Surveyor for Utah)