

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

# FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE SOUTH BOUNDARY,

A PORTION OF THE EAST BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES,

THE SUBDIVISION OF SECTIONS 11, 12, 14, 23, 25, AND 35,

AND

MINERAL SURVEYS BETWEEN PRIVATE AND PUBLIC LANDS

IN SECTIONS 22, 23, AND 26

IN

TOWNSHIP 11 SOUTH, RANGE 5 WEST

OF THE SALT LAKE MERIDIAN  
IN THE STATE OF UTAH

EXECUTED BY

*Jerry L. Thomas*  
*Cadastral Surveyor*

Under special instructions dated *October 11, 1996*, approved *October 11, 1996*, which provided for the surveys included under Group Number *865*, and assignment instructions dated *July 28, 1997*.

Survey commenced *July 30, 1997*  
Survey completed *October 8, 1997*

**INDEX DIAGRAM**

Township 11 South, Range 5 West

6	5	4	3	2 16	1 10
7	8	9	10 15	11 14	12 9 4
18	17	16	15 14	14 13	13 8
19	20	21	22 13	23 12	24 8 7
30	29	28	27	26 12	25 5 3
31	32	33	34 11	35 5 2	36

The Subdivision of Section 11 ..... Page 16  
 The Subdivision of Section 12 ..... Page 18  
 The Subdivision of Section 14 ..... Page 19  
 The Subdivision of Section 23 ..... Page 20  
 The Subdivision of Section 25 ..... Page 23  
 The Subdivision of Section 35 ..... Page 26  
 Dependent Resurvey of a Portion of Mineral Survey No. 6317 ... Page 29

## TOWNSHIP 11 SOUTH, RANGE 5 WEST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

The following field notes describe the dependent resurvey of a portion of the south boundary, a portion of the east boundary, a portion of the subdivisional lines, the subdivision of sections 11, 12, 14, 23, 25, and 35, and the mineral surveys between private and public lands in sections 22, 23, and 26, in Township 11 South, Range 5 West, Salt Lake Meridian, Utah.

**History of Surveys**

Surveyed by		Retr. or Resurveyed by	
<b>SOUTH BOUNDARY</b>			
All	J. Gurlinski	1872	
Portion			Stewart and Clark 1913
Portion			G.B. Hatch 1966-68
Portion			J.L. Thomas 1990
<b>EAST BOUNDARY</b>			
All	J. Gurlinski	1872	
Portion			B.S. Owens 1960
Portion			G.B. Hatch 1968
<b>WEST BOUNDARY (First Guide Meridian West)</b>			
All	J. Bausman	1869	
All			G.W. Hochstrasser 1966
<b>NORTH BOUNDARY (Second Standard Parallel South)</b>			
All	J. Gurlinski	1872	
All			A.J. Stookey 1907
Portion			Stewart and Clark 1913
Portion			H.W. Miller and 1915
			I. Hays
Portion			G.B. Hatch 1966-68
<b>SUBDIVISION</b>			
Portion	J. Gurlinski	1872-74	
Portion	Stewart and Clark	1913	Stewart and Clark 1913
Portion			G.B. Hatch 1966-68

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 865, dated October 11, 1996.

## TOWNSHIP 11 SOUTH, RANGE 5 WEST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

The directions of lines were determined by hour angle observations of the Sun and Polaris, carried forward by sustained angulation and Global Positioning System (G.P.S.), using relative positioning techniques. Distances were determined by electronic measurement.

Preliminary to the resurvey the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line notes are given herein.

The geographic positions of the following section corners were determined by ties to U.S.G.S. triangulation station "MAPLE 2", by the Global Positioning System, using relative positioning techniques. They will also function as B.L.M. Control Stations.

The geographic position of the corner of sections 1, 6, 7, and 12, East Boundary, is as follows:

Latitude  $39^{\circ} 53' 23.972''$  N.      Longitude  $112^{\circ} 20' 51.757''$  W.  
N.A.D. 1983

The geographic position of the corner of sections 1, 2, 35, and 36, South Boundary, is as follows:

Latitude  $39^{\circ} 49' 01.538''$  N.      Longitude  $112^{\circ} 21' 57.727''$  W.  
N.A.D. 1983

The mean magnetic declination as determined from numerous readings throughout the survey is:  $14^{\circ} 00'$  East.

---

Dependent Resurvey of a Portion of the South Boundary,  
T. 11 S., R. 5 W., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by  
J. Gorkinski in 1872 and the Resurvey by  
G. Hatch in 1968

---

Beginning at the 1/4 section corner of sections 2 and 35, on the south boundary of the township, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1968 resurvey of a portion of the south boundary of T. 11 S., R. 5 W.

S.  $89^{\circ} 27.5'$  W., between sections 2 and 35, on the south boundary of the township.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 11 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Over rolling land.

**20.075** Point for the W 1/16 section corner of sections 2 and 35.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, and in a collar of stone, with aluminum cap marked:

T11S R5W  
W 1/16  $\frac{S35}{S2}$   
T12S  
1997

Set a steel fence post alongside the aluminum post.

Corner is located 6 links E of fence corner, with fences projecting N and W.

**40.150** The corner of sections 2, 3, 34, and 35, monumented with an iron post, 2 inches diameter, firmly set, projecting 8 inches above ground, with brass cap marked as described in the official record of the 1913 resurvey of a portion of the south boundary of T. 11 S., R. 5 W.

---

Dependent Resurvey of a Portion of the East Boundary,  
T. 11 S., R. 5 W., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by  
J. Gorlinski in 1872 and the Resurvey by  
G.B. Hatch in 1968

---

From the corner of sections 25 and 36 only, on the east boundary of the township, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 8 inches above the ground, with brass cap marked as described in the official record of the 1968 resurvey of a portion of the east boundary of T. 11 S., R. 5 W.

Corner is located in an E-W fence line.

N. 0° 31.0' W., along the east boundary of section 25.

**40.150** The 1/4 section corner of section 25 only, on the east boundary of the township, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1968 resurvey of a portion of the east boundary of T. 11 S., R. 5 W.

---

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,  
T. 11 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

N. 0° 30.0' W., beginning new measurement.

Over rolling land through thick juniper timber.

**20.105** Point for the N 1/16 section corner of section 25 only.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

	T11S	
	R5W   R4W	
N 1/16		
	S25	
	1997	

Set a steel fence post alongside the aluminum post.

Corner is located in dense juniper timber.

**40.210** The corner of sections 24 and 25 only, on the east boundary of the township, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1968 resurvey of a portion of the east boundary of T. 11 S., R. 5 W.

---

From the corner of sections 7, 12, 13, and 18, on the east boundary of the township, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1968 resurvey of a portion of the east boundary of T. 11 S., R. 5 W.

N. 0° 05.0' W., between secs. 7 and 12, on the east boundary of the township.

**40.265** The 1/4 section corner of sections 7 and 12, on the east boundary of the township, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1968 resurvey of a portion of the east boundary of T. 11 S., R. 5 W.

---

N. 0° 05.0' W., beginning new measurement.

Over rolling land.

**20.130** Point for the N 1/16 section corner of sections 7 and 12.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,  
T. 11 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N 1/16  
S12 | S7  
1997

Set a steel fence post alongside the aluminum post.

- 40.260** The corner of sections 1, 6, 7, and 12, on the east boundary of the township, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1968 resurvey of a portion of the east boundary of T. 11 S., R. 5 W.

---

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 11 S., R. 5 W., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by J. Gorlinski in 1872  
and the Resurvey by G.B. Hatch in 1968

---

From the 1/4 section corner of sections 35 and 36, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1968 resurvey of a portion of the subdivisional lines of T. 11 S., R. 5 W.

From this corner, the section corner of sections 1, 2, 35, and 36, on the south boundary of the township, monumented with an iron post, 2 1/2 inches diameter, projecting 10 inches above ground, in a collar of stone, marked as described in the official record of the 1968 resurvey of a portion of the south boundary of T. 11 S., R. 5 W., bears S. 0° 25.0' E., 40.095 chains distance.

Set a 6 ft. steel fence post alongside the iron post.

N. 0° 08.5' W., between sections 35 and 36.

Over rolling land.

- 20.070** Point for the N 1/16 section corner of sections 35 and 36; not monumented.

- 40.140** The corner of sections 25, 26, 35, and 36, monumented with an iron post, 2 inches diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1913 resurvey of a portion of the subdivisional lines of T. 11 S., R. 5 W.

---

From the 1/4 section corner of sections 25 and 36, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1968 resurvey of a portion of the subdivisional lines of T. 11 S., R. 5 W.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 11 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Corner is located in a fence corner, from which fences bear north and east.

S.89° 32.5' W., between sections 25 and 36.

Over rolling land.

19.965 Point for the W 1/16 section corner of sections 25 and 36.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

	T11S R5W
W 1/16	<u>S25</u>
	S36
	1997

Set a steel fence post alongside the aluminum post.

Corner is located in dense juniper timber and about 3 chains West of a dirt road.

39.930 The corner of sections 25, 26, 35, and 36.

---

Reestablishment of the Survey Executed by  
J. Gorlinski in 1872, and the Retracement by  
Stewart and Clark in 1913

---

From the 1/4 section corner of sections 25 and 26, monumented with an iron post, 2 inches diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1913 resurvey of a portion of the subdivisional lines of T. 11 S., R. 5 W.

N. 0° 16.5' W., between sections 25 and 26.

Over rolling land.

20.150 Point for the N 1/16 section corner of sections 25 and 26.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

	T11S R5W
	N 1/16
S26	S25
	1997

Set a steel fence post alongside the aluminum post.

Corner is located in reseeded area.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

**40.300**

The corner of sections 23, 24, 25, and 26, monumented with an iron post, 2 inches diameter, firmly set, projecting 6 inches above ground, with brass cap as described in the official record of the 1913 resurvey of a portion of the subdivisional lines of T. 11 S., R. 5 W.

---

Reestablishment of the Survey Executed by  
J. Gorlinski in 1872, and the  
Resurvey by G. Hatch in 1968

---

From the corner of sections 24 and 25 only, on the east boundary of the township, hereinbefore described.

S. 89° 48.5' W., between sections 24 and 25.

Over rolling land, through thick juniper timber.

**19.915**

Point for the E 1/16 section corner of sections 24 and 25.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T11S R5W  
E 1/16  $\frac{S24}{S25}$   
1997

Set a steel fence post alongside the aluminum post.

Corner is located in dense juniper forest.

**39.830**

The 1/4 section corner of sections 24 and 25, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1968 resurvey of a portion of the subdivisional lines of T. 11 S., R. 5 W.

---

S. 89° 42.5' W., beginning new measurement.

**19.925**

Point for the W 1/16 section corner of sections 24 and 25.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T11S R5W  
W 1/16  $\frac{S24}{S25}$   
1997

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set a steel fence post alongside the aluminum post.

Corner is located on a SE slope in dense juniper forest.

**39.850** The corner of sections 23, 24, 25, and 26.

---

Reestablishment of the Survey Executed by  
J. Gorkinski in 1872, and the Retracement by  
Stewart and Clark in 1913

---

N. 0° 11.0' W., between sections 23 and 24.

Over rolling land.

**40.240** The 1/4 section corner of sections 23 and 24, monumented with an iron post, 1 in. diam., firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1913 resurvey of a portion of the subdivisional lines of T. 11 S., R. 5 W.

---

N. 0° 15.0' W., beginning new measurement.

**20.105** Point for the N 1/16 section corner of sections 23 and 24.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

N 1/16  
S23 | S24  
1997

Set a steel fence post alongside the aluminum post.

Corner is located on a south slope.

**40.210** The corner of sections 13, 14, 23, and 24, monumented with an iron post, 2 inches diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1913 resurvey of a portion of the subdivisional lines of T. 11 S., R. 5 W.

---

N. 1° 00.0' W., between sections 13 and 14.

Over rolling land.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

**CHAINS****40.275**

The 1/4 section corner of sections 13 and 14, monumented with an iron post, 1 in. diam., firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1913 resurvey of a portion of the subdivisional lines of T. 11 S., R. 5 W.

---

N. 1° 02.0' W., beginning new measurement.

**39.790**

The corner of sections 11, 12, 13, and 14, monumented with an iron post, 2 inches diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1913 resurvey of a portion of the subdivisional lines of T. 11 S., R. 5 W.

---

Reestablishment of the Survey by  
J. Gorlinski in 1872, and the  
Resurvey by G. Hatch in 1968

---

From the corner of sections 7, 12, 13, and 18, on the east boundary of the township, hereinbefore described.

S. 89° 33.0' W., between sections 12 and 13.

Over rough and broken mountainous land.

**40.360**

The 1/4 section corner of sections 12 and 13, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 6 inches above mound of stone, with brass cap marked as described in the official record of the 1968 resurvey of a portion of the subdivisional lines of T. 11 S., R. 5 W.

---

S. 89° 38.5' W., beginning new measurement.

**40.155**

The corner of sections 11, 12, 13, and 14.

---

Reestablishment of the Survey Executed by J. Gorlinski,  
in 1872, and the Retracement by  
Stewart and Clark in 1913

---

N. 0° 26.0' W., between sections 11 and 12.

Over rough and broken mountainous land.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

**CHAINS****40.035**

The 1/4 section corner of sections 11 and 12, monumented with an iron post, 1 inch diameter, firmly set, projecting 6 inches above ground, with brass cap marked as described in the official record of the 1913 retracement of a portion of the subdivisional lines of T. 11 S., R. 5 W.

---

N. 0° 29.0' E., beginning new measurement.

**40.150**

The corner of sections 1, 2, 11, and 12, monumented with an iron post, 2 inches diameter, firmly set, projecting 12 inches above mound of stone, with brass cap marked as described in the official record of the 1913 retracement of a portion of the subdivisional lines of T. 11 S., R. 5 W.

---

Reestablishment of the Survey Executed by  
J. Gorkinski in 1872, and Resurvey by  
G. Hatch in 1968

---

From the corner of sections 1, 6, 7, and 12, on the east boundary of the township, hereinbefore described.

S. 89° 21.0' W., between sections 1 and 12.

Over rolling land.

**20.090**

Point for the E 1/16 section corner of sections 1 and 12.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

E 1/16     $\frac{S1}{S12}$   
                  1997

Set a steel fence post alongside the aluminum post.

**40.180**

Point for the 1/4 section corner of sections 1 and 12 at proportionate distance. The iron post set in the 1968 survey was found lying nearby and used to reestablish the corner point.

Reset the iron post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with brass cap marked:

                  T11S R5W  
1/4             $\frac{S1}{S12}$   
                  1968  
                  1997

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

- Add the markings 1997 on the brass cap.
- Corner is located 5 1/2 links W. of N and S fence line.
- 80.360** The corner of sections 1, 2, 11, and 12.
- 
- Reestablishment of the Survey Executed by  
J. Gorlinski in 1872 and the Retracement by  
Stewart and Clark in 1913
- 
- From the corner of sections 2, 3, 34, and 35, on the south boundary of the township, hereinbefore described.
- N. 1° 19.5' W., between sections 34 and 35.
- Over rolling land.
- 20.475** Point for the S 1/16 section corner of sections 34 and 35.
- Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, and in a collar of stone, with aluminum cap marked:
- T11S R5W  
S 1/16  
S34 | S35  
1997
- Set a steel fence post alongside the aluminum post.
- Corner is located 15 links W of dirt road, which bears N. 10° E. and S. 10° W.
- 40.950** The 1/4 section corner of sections 34 and 35, monumented with an iron post, 1 inch diameter, firmly set, projecting 8 inches above ground, with brass cap marked as described in the official record of the 1913 resurvey of a portion of the subdivisional lines of T. 11 S., R. 5 W.
- 
- N. 0° 24.5' E., beginning new measurement.
- 40.275** The corner of sections 26, 27, 34, and 35, monumented with an iron post, 2 inches diameter, firmly set, projecting 8 inches above ground, with brass cap marked as described in the official record of the 1913 resurvey of a portion of the subdivisional lines of T. 11 S., R. 5 W.
-

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the corner of sections 25, 26, 35, and 36.

N. 89° 49.0' W., between sections 26 and 35.

Over rolling land.

**20.175** Point for the E 1/16 section corner of sections 26 and 35.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T11S R5W  
E 1/16  $\frac{S26}{S35}$   
1997

Set a steel fence post alongside the aluminum post.

Corner is located 8 links E of small wash, which drains S.

**40.350** The 1/4 section corner of sections 26 and 35, monumented with an iron post, 1 inch diameter, firmly set, projecting 8 inches above ground, with brass cap marked as described in the official record of the 1913 resurvey of a portion of the subdivisional lines of T. 11 S., R. 5 W.

---

N. 89° 47.5' W., beginning new measurement.

**40.330** The corner of sections 26, 27, 34, and 35.

---

From the corner of sections 23, 24, 25, and 26.

S. 89° 48.5' W., between sections 23 and 26.

Over mountainous land.

**40.185** The 1/4 section corner of sections 23 and 26, monumented with an iron post, 1 inch diameter, firmly set, projecting 8 inches above ground, with brass cap marked as described in the official record of the 1913 resurvey of a portion of the subdivisional lines of T. 11 S., R. 5 W.

---

Reestablishment of the Survey Executed  
by Stewart and Clark in 1913

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

S. 89° 55.5' W., beginning new measurement.

**37.610** Intersect line 1-2, Central lode, Mineral Survey No. 6317.

**40.035** The corner of sections 22, 23, 26, and 27, monumented with an iron post, 2 inches diameter, firmly set, projecting 8 inches above ground, with brass cap marked as described in the official record of the 1913 survey of a portion of the subdivisional lines of T. 11 S., R. 5 W.

---

N. 0° 01' E., between sections 22 and 23.

Over mountainous land.

**12.130** Intersect line 3-4, Summit lode, Mineral Survey No. 6317.

**40.150** The 1/4 section corner of sections 22 and 23, monumented with an iron post, 1 inch diameter, firmly set, projecting 8 inches above ground, with brass cap marked as described in the official record of the 1913 survey of a portion of the subdivisional lines of T. 11 S., R. 5 W.

---

N. 0° 00.5' W., beginning new measurement.

**20.085** Point for the N 1/16 section corner of sections 22 and 23.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground to bedrock, and in a mound of stone to top, with aluminum cap marked:

N 1/16  
S22 | S23  
1997

**40.170** The corner of sections 14, 15, 22, and 23, monumented with an iron post, 2 inches diameter, firmly set, projecting 8 inches above ground, with brass cap marked as described in the official record of the 1913 resurvey of a portion of the subdivisional lines of T. 11 S., R. 5 W.

---

Reestablishment of the Survey Executed by  
J. Gorkinski in 1872 and Resurvey by  
Stewart and Clark in 1913

---

From the corner of sections 13, 14, 23, and 24.

S. 89° 29' W., between sections 14 and 23.

Over mountainous land.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

- 19.885** Point for the E 1/16 section corner of sections 14 and 23; not monumented.
- 39.770** The 1/4 section corner of sections 14 and 23, monumented with an iron post, 1 inch diameter, firmly set, projecting 8 inches above ground, with brass cap marked as described in the official record of the 1913 resurvey of a portion of the subdivisional lines of T. 11 S., R. 5 W.
- 
- N. 89° 56.5' W., beginning new measurement.
- 20.060** Point for the W 1/16 section corner of sections 14 and 23; not monumented.
- 40.120** The corner of sections 14, 15, 22, and 23.
- 
- N. 0° 15.5' W., between sections 14 and 15.
- Over mountainous land.
- 39.950** The 1/4 section corner of sections 14 and 15, monumented with an iron post, 1 inch diameter, firmly set, projecting 8 inches above ground, with brass cap marked as described in the official record of the 1913 resurvey of a portion of the subdivisional lines of T. 11 S., R. 5 W.
- 
- Reestablishment of the Survey Executed by  
Stewart and Clark in 1913
- 
- N. 0° 02.0' E., beginning new measurement.
- 40.365** The corner of sections 10, 11, 14, and 15, monumented with an iron post, 2 inches diameter, firmly set, projecting 8 inches above ground, with brass cap marked as described in the official record of the 1913 survey of a portion of the subdivisional lines of T. 11 S., R. 5 W.
- 
- From the corner of sections 11, 12, 13, and 14.
- S. 89° 58.0' W., between sections 11 and 14.
- Over mountainous land.
- 39.305** The 1/4 section corner of sections 11 and 14, monumented with an iron post, 1 inch diameter, firmly set, projecting 8 inches above ground, with brass cap marked as described in the official record of the 1913 survey of a portion of the subdivisional lines of T. 11 S., R. 5 W.
-

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

S. 89° 57.0' W., beginning new measurement.

**19.655** Point for the W 1/16 section corner of sections 11 and 14.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 14 inches in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

$$\begin{array}{r} \text{W } 1/16 \quad \frac{\text{S11}}{\text{S14}} \\ \quad \quad \quad 1997 \end{array}$$

Set a steel fence post alongside the aluminum post.

**39.310** The corner of sections 10, 11, 14, and 15.

---

N. 0° 03.0' W., between sections 10 and 11.

Over mountainous land.

**40.035** The 1/4 section corner of sections 10 and 11, monumented with a broken iron post, 1 inch diameter. The bottom portion of the iron post was firmly set in it's original position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

$$\begin{array}{r} \text{T11S R5W} \\ \quad \quad \quad 1/4 \\ \text{S10} \quad | \quad \text{S11} \\ \quad \quad \quad 1997 \end{array}$$

Deposit the broken iron post alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, west of the corner.

---

North, beginning new measurement.

**40.035** The corner of sections 2, 3, 10, and 11, monumented with an iron post, 2 inches diameter, firmly set, projecting 8 inches above ground, with brass cap marked as described in the official record of the 1913 survey of a portion of the subdivisional lines of T. 11 S., R. 5 W.

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the corner of sections 1, 2, 11, and 12.

S. 89° 50.0' W., between sections 2 and 11.

Over mountainous land.

- 38.630** The 1/4 section corner of section 11 only, monumented with an iron post, 1 inch diameter, firmly set, projecting 8 inches above ground, with brass cap marked as described in the official record of the 1913 survey of a portion of the subdivisional lines of T. 11 S., R. 5 W.

---

S. 89° 55.5' W., beginning new measurement.

- 1.460** Point for the 1/4 section corner of section 2 only, at proportionate distance; not monumented.

- 20.020** Point for the W 1/16 section corner of section 11 only.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

---

W 1/16 S11  
1997

Set a steel fence post alongside the aluminum post.

Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, south of the corner.

- 40.040** The corner of sections 2, 3, 10, and 11.

---

The Subdivision of Section 11,  
T. 11 S., R. 5 W., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 11 and 14.

N. 0° 30.0' E., on the N - S center line of section 11.

Over mountainous land.

- 40.035** Point for the center 1/4 section corner of section 11, at intersection with the E - W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 14 inches in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

THE SUBDIVISION OF SECTION 11,  
T. 11 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

T11S R5W  
C 1/4 S11  
1997

Set a steel fence post alongside the aluminum post.

**80.095** The 1/4 section corner of section 11 only.

---

From the 1/4 section corner of sections 11 and 12.

S. 89° 58.0' W., on the E - W center line of section 11.

Over mountainous land.

**38.650** The center 1/4 section corner of section 11.

**58.495** Point for the center W 1/16 section corner of section 11.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 14 inches in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

C  $\frac{W \ 1/16}{S11}$  C  
1997

Set a steel fence post alongside the aluminum post.

**78.340** The 1/4 section corner of sections 10 and 11.

---

From the W 1/16 section corner of sections 11 and 14.

N. 0° 13.5' E., on the N - S center line of the SW 1/4 of section 11.

Over mountainous land.

**40.035** The center W 1/16 section corner of section 11.

---

From the center W 1/16 section corner of section 11.

N. 0° 15.0' E., on the N - S center line of the NW 1/4 of section 11.

Over mountainous land.

**40.050** The W 1/16 section corner of section 11 only.

---

THE SUBDIVISION OF SECTION 12,  
T. 11 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

The Subdivision of Section 12,  
T. 11 S., R. 5 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 12 and 13.

N. 0° 02.5' E., on the N - S center line of section 12.

Over mountainous land.

**40.180** Point for the center 1/4 section corner of section 12, at intersection with the E - W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T11S R5W  
C 1/4 S12  
1997

Set a steel fence post alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, west of the corner.

**60.280** Point for the center N 1/16 section corner of section 12; not monumented.

**80.380** The 1/4 section corner of sections 1 and 12.

From the 1/4 section corner of sections 7 and 12, on the east boundary of the township, hereinbefore described.

S. 89° 26.5' W., on the E - W center line of section 12.

Over mountainous land.

**20.135** Point for the center E 1/16 section corner of section 12; not monumented.

**40.270** The center 1/4 section corner of section 12.

**80.750** The 1/4 section corner of sections 11 and 12.

From a point for the center E 1/16 section corner of section 12.

N. 0° 01.5' W., on the N - S center line of the NE 1/4 of section 12.

Over mountainous land.

THE SUBDIVISION OF SECTION 12,  
T. 11 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

**20.115** Point for the NE 1/16 section corner of section 12, at intersection with the E - W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

NE 1/16  
S12  
1997

Set a steel fence post alongside the aluminum post.

**40.230** The E 1/16 section corner of sections 1 and 12.

---

From the N 1/16 section corner of sections 7 and 12, on the east boundary of the township, hereinbefore described.

S. 89° 23.5' W., on the E - W center line of the NE 1/4 of section 12.

Over mountainous land.

**20.115** The NE 1/16 section corner of section 12.

**40.230** Point for the center N 1/16 section corner of section 12.

---

The Subdivision of Section 14,  
T. 11 S., R. 5 W., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 14 and 23.

N. 0° 41.0' W., on the N - S center line of section 14.

Over mountainous land.

**40.315** Point for the center 1/4 section corner of section 14, at intersection with the E - W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, and in a collar of stone, with aluminum cap marked:

T11S R5W  
C 1/4 S14  
1997

Set a steel fence post alongside the aluminum post.

THE SUBDIVISION OF SECTION 14,  
T. 11 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

**CHAINS****80.395**

The 1/4 section corner of sections 11 and 14.

---

From the 1/4 section corner of sections 13 and 14.

S. 89° 32.5' W., on the E - W center line of section 14.

Over mountainous land.

**39.550**

The center 1/4 section corner of section 14.

**59.460**

Point for the center W 1/16 section corner of section 14.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground, in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

$$C \frac{W \ 1/16}{S14} C$$

1997

Set a steel fence post alongside the aluminum post.

**79.370**

The 1/4 section corner of sections 14 and 15.

---

From the center W 1/16 section corner of section 14.

N. 0° 19.5' W., on the N - S center line of the NW 1/4 of section 14.

Over mountainous land.

**40.220**

The W 1/16 section corner of sections 11 and 14.

---

The Subdivision of Section 23,  
T. 11 S., R. 5 W., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 23 and 26.

N. 0° 05.5' E., on the N - S center line of section 23.

Over mountainous land.

**40.235**

Point for the center 1/4 section corner of section 23, at intersection with the E - W center line.

THE SUBDIVISION OF SECTION 23,  
T. 11 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

T11S R5W  
C 1/4 S23  
1997

Set a steel fence post alongside the aluminum post.

**60.230** Point for center N 1/16 section corner of section 23; not monumented.

**80.225** The 1/4 section corner of sections 14 and 23.

---

From the 1/4 section corner of sections 23 and 24.

S. 89° 49.0' W., on the E - W center line of section 23.

Over mountainous land.

**20.000** Point for the center E 1/16 section corner of section 23.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground to bedrock, and in a collar of stone, with aluminum cap marked:

C  $\frac{E \ 1/16}{S23}$  C  
1997

Set a steel fence post alongside the aluminum post.

**40.000** The center 1/4 section corner of section 23.

**60.040** Point for the center W 1/16 section corner of section 23.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground to bedrock, in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

C  $\frac{W \ 1/16}{S23}$  C  
1997

Set a steel fence post alongside the aluminum post.

**80.080** The 1/4 section corner of sections 22 and 23.

---

THE SUBDIVISION OF SECTION 23,  
T. 11 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the center E 1/16 section corner of section 23.

N. 0° 05.0' W., on the N - S center line of the NE 1/4 of section 23.

Over mountainous land.

**20.050** Point for the NE 1/16 section corner of section 23, at intersection with the E - W center line of the NE 1/4.

Set a rebar, 12 inches long, 5/8 inches diameter, in a drill hole, 8 inches deep, with aluminum cap marked:

NE 1/16 S23  
1997

Set a steel fence post in a mound of stone west of the corner.

**40.100** Point for the E 1/16 section corner of sections 14 and 23.

---

From the N 1/16 section corner of sections 23 and 24.

S. 89° 40.0' W., on the E - W center line of the NE 1/4 of section 23.

Over mountainous land.

**19.940** The NE 1/16 section corner of section 23.

**39.880** Point for the center N 1/16 section corner of section 23.

---

From the center W 1/16 section corner of section 23.

N. 0° 03.0' E., on the N - S center line of the NW 1/4 of section 23.

Over mountainous land.

**20.040** Point for the NW 1/16 section corner of section 23, at intersection with the E and W center line of the NW 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 16 inches in the ground, in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

NW 1/16 S23  
1997

THE SUBDIVISION OF SECTION 23,  
T. 11 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

- Set a steel fence post alongside the aluminum post.
- 40.080** Point for the W 1/16 section corner of sections 14 and 23.
- 
- From the point for the center N 1/16 section corner of section 23.
- S. 89° 57.0' W., on the E - W center line of the NW 1/4 of section 23.
- Over mountainous land.
- 20.050** The NW 1/16 section corner of section 23.
- 40.100** The N 1/16 section corner of sections 22 and 23.
- 
- The Subdivision of Section 25,  
T. 11 S., R. 5 W., Salt Lake Meridian, Utah
- 
- From the 1/4 section corner of sections 25 and 36.
- N. 0° 19.5' W., on the N - S center line of section 25.
- Over rolling land through thick juniper forest.
- 40.245** Point for the center 1/4 section corner of section 25, at intersection with the E - W center line.
- Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:
- T11S R5W  
C 1/4 S25  
1997
- Set a steel fence post alongside the aluminum post.
- Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, west of the corner.
- Corner is located about 1 chain west of dirt road.
- 60.395** Point for the center N 1/16 section corner of section 25.
- Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 25,  
T. 11 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

CHAINS

$$\begin{array}{c} \text{C} \\ \text{N } 1/16 \quad | \quad \text{S25} \\ \text{C} \\ 1997 \end{array}$$

Set a steel fence post alongside the aluminum post.

Raise a mound of stone 2 1/2 ft. base, 1 1/2 ft. high west of the corner.

Cover is located on a south slope in dense juniper.

**80.545** The 1/4 section corner of sections 24 and 25.

---

From the 1/4 section corner of section 25 only, on the east boundary, hereinbefore described.

S. 89° 41.5' W., on the E - W center line of section 25.

Over mountainous land.

**19.980** Point for the center E 1/16 section corner of section 25.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

$$\begin{array}{c} \text{T11S R5W} \\ \text{C } \frac{\text{E } 1/16}{\text{S25}} \text{ C} \\ 1997 \end{array}$$

Set a steel fence post alongside the aluminum post.

Corner is located in dense juniper.

**39.960** The center 1/4 section corner of section 25.

**59.905** Point for the center W 1/16 section corner of section 25.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

$$\begin{array}{c} \text{T11S R5W} \\ \text{C } \frac{\text{W } 1/16}{\text{S25}} \text{ C} \\ 1997 \end{array}$$

Set a steel fence post alongside the aluminum post.

THE SUBDIVISION OF SECTION 25,  
T. 11 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

- Corner is located in dense juniper.
- 79.850** The 1/4 section corner of sections 25 and 26.
- 
- From the center E 1/16 section corner of section 25.
- N. 0° 25.0' W., on the N - S center line of the NE 1/4 of section 25.
- Over rolling land through thick juniper forest.
- 20.125** Point for the NE 1/16 section corner of section 25, at intersection with the E - W center line of the NE 1/4.
- Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, and in a collar of stone to top, with aluminum cap marked:
- T11S R5W  
NE 1/16  
S25  
1997
- Set a steel fence post alongside the aluminum post.
- Corner is located in a barbed wire fence, bears N and S.
- 40.250** The E 1/16 section corner of sections 24 and 25.
- 
- From the N 1/16 section corner of section 25 only, on the east boundary, hereinbefore described.
- S. 89° 45.0' W., on the E - W center line of the NE 1/4 of section 25.
- Over rolling land through thick juniper forest.
- 19.950** The NE 1/16 section corner of section 25.
- 39.900** The center N 1/16 section corner of section 25.
- 
- From the W 1/16 section corner of sections 25 and 36.
- N. 0° 17.5' W., on the N - S center line of the SW 1/4 of section 25.
- Over rolling land.
- 40.300** The center W 1/16 section corner of section 25.
-

THE SUBDIVISION OF SECTION 25,  
T. 11 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the center W 1/16 section corner of section 25.

N. 0° 18.0' W., on the N - S center line of the NW 1/4 of section 25.

Over rolling land.

**20.150** Point for the NW 1/16 section corner of section 25, at intersection with the E - W center line of the NW 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T11S R5W  
NW 1/16  
S25  
1997

Set a steel fence post alongside the aluminum post.

Corner is located on a gentle south slope in a chained and reseeded area.

**40.300** The W 1/16 section corner of sections 24 and 25.

---

From the center N 1/16 section corner of section 25.

S. 89° 42.0' W., on the E - W center line of the NW 1/4 of section 25.

Over rolling land.

**19.935** The NW 1/16 section corner of section 25.

**39.870** The N 1/16 section corner of sections 25 and 26.

---

The Subdivision of Section 35,  
T. 11 S., R. 5 W., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 2 and 35, on the south boundary, hereinbefore described.

N. 0° 20.0' W., on the N - S center line of section 35.

Over rolling land.

**20.245** Point for the center S 1/16 section corner of section 35.

THE SUBDIVISION OF SECTION 35,  
T. 11 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

C  
S 1/16 | S35  
C  
1997

Set a steel fence post alongside the aluminum post.

Corner is located on a flat bench, about 80 links south of the northerly edge of the bench and in juniper.

**40.490** Point for the center 1/4 section corner of section 35, at intersection with the E - W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T11S R5W  
C 1/4 S35  
1997

Set a steel fence post alongside the aluminum post.

Corner is located 90 links east of N and S fence line.

**60.590** Point for the center N 1/16 section corner of section 35.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T11S R5W  
C  
N 1/16 | S35  
C  
1997

Set a steel fence post alongside the aluminum post.

Corner is located on a gentle south slope in dense juniper.

**80.690** The 1/4 section corner of sections 26 and 35.

---

From the 1/4 section corner of sections 35 and 36.

N. 89° 54.0' W., on the E - W center line of section 35.

Over rolling land.

THE SUBDIVISION OF SECTION 35,  
T. 11 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

**20.110** Point for the center E 1/16 section corner of section 35; not monumented.

**40.220** The center 1/4 section corner of section 35.

**60.650** Point for the center W 1/16 section corner of section 35.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

$$C \frac{W \ 1/16}{S35} C$$

1997

Set a steel fence post alongside the aluminum post.

Corner is located on a gradual NW slope among juniper and 140 links north of spur, bears N. 50° E. and S. 50° W.

**81.080** The 1/4 section corner of sections 34 and 35.

---

From the point for the center E 1/16 section corner of section 35.

N. 0° 14.0' W., on the N - S center line of the NE 1/4 of section 35.

Over rolling land.

**20.085** Point for the NE 1/16 section corner of section 35, at intersection with the E - W center line of the NE 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground to bedrock, and in a collar of stone, with aluminum cap marked:

$$T11S \ R5W$$

$$NE \ 1/16$$

$$S35$$

$$1997$$

Set a steel fence post alongside the aluminum post.

Corner is located in dense juniper.

**40.170** The E 1/16 section corner of sections 26 and 35.

---

From the point for the N 1/16 section corner of sections 35 and 36.

N. 89° 51.5' W., on the E - W center line of the NE 1/4 of section 35.

THE SUBDIVISION OF SECTION 35,  
T. 11 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Over rolling land.

**20.145** The NE 1/16 section corner of section 35.

**40.290** The center N 1/16 section corner of section 35.

---

From the W 1/16 section corner of sections 2 and 35, on the south boundary, hereinbefore described.

N. 0° 50.0' W., on the N - S center line of the SW 1/4 of section 35.

Over rolling land.

**20.360** Point for the SW 1/16 section corner of section 35, at intersection with the E - W center line of the SW 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground to bedrock, and in a collar of stone, with aluminum cap marked:

T11S R5W  
SW 1/16 S35  
1997

Set a steel fence post alongside the aluminum post.

Corner is located at intersection of fences, projecting east and south.

**40.720** The center W 1/16 section corner of section 35.

---

From the center S 1/16 section corner of section 35.

S. 89° 47.0' W., on the E - W center line of the SW 1/4 of section 35.

Over rolling land.

**20.250** The SW 1/16 section corner of section 35.

**40.500** The S 1/16 section corner of sections 34 and 35.

---

Dependent Resurvey of a Portion of Mineral Survey  
No. 6317, T. 11 S., R. 5 W., Salt Lake Meridian, Utah

---

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY  
No. 6317, T. 11 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Reestablishment of the Survey by  
Chas. P. Brooks in 1914


Central Lode (6317)

From Cor. No. 3, Central lode, identical with Cor. No. 5, Ella lode, Mineral Survey No. 6956, monumented with an iron post, 2 inches diameter, firmly set, projecting 12 inches above ground, with brass cap marked as described in Mineral Survey No. 6956, in 1928.

N. 44° 43.0' E., along line 3 - 2.

- 21.685** Cor. No. 2, at proportionate distance, based on the Grant Boundary method; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 14 inches in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:



Set a steel fence post alongside the aluminum post.


N. 47° 56.0' W., along line 2 - 1.

- 5.875** Intersect the section line of sections 23 and 26.

- 9.080** Cor. No. 1, at intersect line 1 - 6, Eastern Iron lode, monumented with the remains of a burned pine post, set in a mound of stone.

At the claim corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 16 inches in the ground to bedrock, in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:



Deposit the burned pine post alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY  
No. 6317, T. 11 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

Eastern Iron Lode (6317)


---

N. 46° 12.0' E., along line 6 - 1.

- 1.024** Cor. No. 1, identical with Cor. No. 1, Summit lode, monumented with the remains of a burned pine post, set in a mound of stone.

At the claim corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 14 inches in the ground to bedrock, in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:



Deposit burned pine post alongside the aluminum post.

---

Summit (6317)


---

N. 59° 51.8' E., along line 1 - 4.

- 9.275** Corner No. 4, Summit Lode, monumented with the remains of burned pine post, set in a mound of stone.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground to bedrock, and in a collar of stone to top, with aluminum cap marked:



Deposit the burned pine post alongside the aluminum post.

---

N. 62° 20.2' W., along line 4 - 3.

- 9.940** Intersect the section line between sections 22 and 23.


DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY  
No. 6317, T. 11 S., R. 5 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**  
**20.195**

Corner No. 3, identical with Corner No. 4, Bates Iron Lode, monumented with a pine post, 4 ft. long, plainly marked 6317, and set in a mound of stone.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground to bedrock, and in a mound of stone to top, with aluminum cap marked:



Deposit the pine post alongside the aluminum post.

---

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD ASSISTANTS**

---

Name	Capacity
Ryan Snow	Survey Aid
Shane Chamberlin	Survey Aid
Ryan Christensen	Survey Aid


## CERTIFICATE OF SURVEY

I, **Jerry L. Thomas, Cadastral Surveyor**, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *11th day of October, 1996*, I have *dependently Resurveyed portion of the south and east boundaries, a portion of the subdivisional lines, the subdivision of sections 11, 12, 14, 23, 25, and 35, and Mineral Surveys between private and public lands in sections 22, 23, and 26, in Township 11 South, Range 5 West,*

of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

May 20, 1999

Date



(Cadastral Surveyor)

Date

(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah


The foregoing field notes of the *dependent resurvey of portions of the south and east boundaries, a portion of the subdivisional lines, the subdivision of sections 11, 12, 14, 23, 25, and 35, and the mineral surveys between private and public lands in sections 22, 23, and 26, in Township 11 South, Range 5 West, Salt Lake Meridian, Utah,*

executed by **Jerry L. Thomas, Cadastral Surveyor**

having been critically examined and found correct, are hereby approved.

May 28, 1999

Date



(Chief Cadastral Surveyor for Utah)