

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL
FIELD NOTES

OF
THE DEPENDENT RESURVEY

OF

A PORTION OF THE THIRD STANDARD PARALLEL SOUTH

ALONG THE SOUTH BOUNDARY OF

TOWNSHIP 15 SOUTH, RANGE 3 WEST,

A PORTION OF THE SOUTH AND EAST BOUNDARIES,

A PORTION OF THE SUBDIVISIONAL LINES,

THE SUBDIVISION OF PORTIONS OF SECTIONS 1, 12, 26, AND 35,

AND

THE SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES

IN

TOWNSHIP 16 SOUTH, RANGE 3 WEST

of the SALT LAKE Meridian
In the State of UTAH

EXECUTED BY

John F. Carroll
Cadastral Surveyor

Under special instructions dated *September 15, 1997*, approved September 15, 1997, which provided for the surveys included under Group Number 874 and assignment instructions dated *September 15, 1997*

Survey commenced *October 1, 1997*
Survey completed *October 11, 1997*

INDEX DIAGRAM

Township 16 South, Range 3 West

						2	2
6	5	4	3	2	1	5	5
					12	4	4
7	8	9	10	11	12	4	4
					11	4	4
18	17	16	15	14	10	13	3
					9	9	3
19	20	21	22	23	9	24	3
					12	8	3
30	29	28	27	26	7	7	25
					11	6	6
31	32	33	34	35	5	36	
					3	2	

The Subdivision of Portions of Section 1.....Page 13

The Subdivision of Portions of Section 12.....Page 14

The Subdivision of Portions of Section 26.....Page 16

The Subdivision of Portions of Section 35.....Page 17

TOWNSHIP 16 SOUTH, RANGE 3 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

The following field notes describe the dependent resurvey of a portion of the Third Standard Parallel South, along the south boundary of Township 15 South, Range 3 West, a portion of the south and east boundaries, a portion of the subdivisional lines, the subdivision of portions of sections 1, 12, 26 and 35, and the survey of a portion of the subdivisional lines in T. 16 S., R. 3 W., Salt Lake Meridian, Utah.

History of Surveys

Surveyed by		Retr. or Resurveyed by		
SOUTH BOUNDARY				
Portion	F. Dickert 1871			
All	R. Gentry, etal	1932-34	R. Gentry, etal	1932-34
EAST BOUNDARY				
All	F. Dickert 1871			
All			C.P. Sylvester	1974
NORTH BOUNDARY				
Portion	F. Dickert	1871		
Portion	A.J. Stewart	1884	A.J. Stewart	1884
Portion	J.C. Thoma	1919		
Portion			R.K. Baugh and M.R. Workman	1997
SUBDIVISION				
Portion	F. Dickert 1871			
REMONUMENTATION				
Portion	F.D. Reynolds	1969		

This survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 874, Utah, dated September 15, 1997.

The directions of the lines of this survey refer to the true meridian and measurements of these lines were determined by utilizing Global Positioning System.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line notes are given herein.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 16 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

The geographic position of the cor. of Tps. 15 and 16 S., Rs. 2 and 3 W., a B.L.M. Control Station, was determined by utilizing satellite based Global Position System (GPS) in conjunction with a tie made to U.S.G.S. triangulation station "FAN", during the execution of the survey by R.K. Baugh and M.R. Workman 1997, under Group No. 862, is:

Latitude: 39°27'38.279" N. Longitude: 112°07'40.847" W.
N.A.D. 1983

The mean magnetic declination is 13 1/2° E.

Dependent Resurvey of a Portion of the Third Standard Parallel South,
Along the South Boundary of T. 15 S., R. 3 W.,
Salt Lake Meridian, Utah

Reestablishment of the Survey Executed
by F. Dickert, Deputy Surveyor in 1871,
and the Resurveys Executed by A.J. Stewart, Deputy Surveyor, in 1884
and R.K. Baugh and M.R. Workman, Cadastral Surveyors, in 1997

Beginning at the cor. of Tps. 15 and 16 S., Rs. 2 and 3 W., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap marked as described in the field notes of the 1974 resurvey record.

N. 89° 38.5' W., between secs. 1 and 36, on the Third Standard Parallel South.

Over gentle rolling land.

40.291 The standard 1/4 sec. cor. of secs. 1 and 36, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, flush with the ground, with aluminum cap mkd. as described in the field notes of 1997 resurvey record.

Dependent Resurvey of a Portion of the South Boundary,
T. 16 S., R. 3 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by F. Dickert, Deputy Surveyor,
in 1871, and the Resurvey Executed by
R. Gentry, U.S. Cadastral Engineer, in 1932-34

From the cor. of secs. 1, 2, 35 and 36, Tps. 16 and 17 S., R. 3 W., monumented with an iron post, 2 ins. diam., firmly set, in a mound of stone, 3 ft. base, with brass cap mkd. as described in the field notes of the 1932-34 resurvey record.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 16 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Cor. is located in a barbed wire fence, bears E and W, in rolling hills, grass and rocks.

N. 89°59.5' W., bet. sections 2 and 35.

39.952

The 1/4 sec. cor. of secs. 2 and 35, monumented with an iron post, 1 in. diam., firmly set, in a mound of stone, 3 ft. diam., with brass cap mkd. as described in the field notes of the 1932-34 resurvey record.

There is no remaining evidence of the 1932 bearing trees or accessory.

Cor. is located in a barbed wire fence, bears E and W, in rolling hills, grass and rocks.

Dependent Resurvey of a Portion of the East Boundary,
T. 16 S., R. 3 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by F. Dickert, Deputy Surveyor,
in 1871, the Resurvey Executed by
C.P. Sylvester, Supervisory Cadastral Surveyor, in 1974

From the cor. of secs. 19, 24, 25 and 30, T. 16 S., Rs. 2 and 3 W., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. as described in the field notes of the 1974 resurvey record.

N. 0°58.4' W., bet. secs. 19 and 24.

41.229

The 1/4 sec. cor. of secs. 19 and 24, T. 16 S., Rs. 2 and 3 W., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. as described in the field notes of the 1974 resurvey record.

N. 0°51.9' W., beginning new measurement.

39.608

The cor. of secs. 13, 18, 19 and 24, T. 16 S., Rs. 2 and 3 W., monumented with an iron post, 2 1/2 ins. diam., firmly set, in a collar of stone, projecting 6 ins. above ground, with brass cap mkd. as described in the field notes of the 1974 resurvey record.

N. 0°00.3' W., bet. secs. 13 and 18.

39.894

The 1/4 sec. cor. of secs. 13 and 18, T. 16 S., Rs. 2 and 3 W., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. as described in the field notes of the 1974 resurvey record.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 16 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 1°47.5' E., beginning new measurement.

- 40.611** The cor. of secs. 7, 12, 13 and 18, T. 16 S., Rs. 2 and 3 W., monumented with an iron post, 2 1/2 ins. diam., firmly set, in a collar of stone, projecting 6 ins. above ground, with brass cap mkd. as described in the field notes of the 1974 resurvey record.

N. 0°03.4' W., bet. secs. 7 and 12.

- 40.275** The 1/4 sec. cor. of secs. 7 and 12, T. 16 S., Rs. 2 and 3 W., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. as described in the field notes of the 1974 resurvey record.

N. 0°02.6' W., beginning new measurement.

- 20.077** Point for the N 1/16 sec. cor. of secs. 7 and 12, T. 16 S., Rs. 2 and 3 W.

Set an aluminum post, 2 1/2 ins. diam., 30 ins. long, 18 ins. in the ground, to bedrock, in a supporting mound of stone, 3 ft. diam., to top, with aluminum cap mkd.

T16S
R3W R2W
N1/16
S12 | S7
1997

Drive a 6 ft. steel fence post alongside aluminum post.

Cor. is located on a gradual southeast slope in rolling hills, grass and rocks.

- 40.154** The cor. of secs. 1, 6, 7 and 12, T. 16 S., Rs. 2 and 3 W., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. as described in the field notes of the 1974 resurvey record.

N. 0°04.4' E., bet. secs. 1 and 6.

- 19.956** Point for the S 1/16 sec. cor. of secs. 1 and 6, T. 16 S., Rs. 2 and 3 W.

Set an aluminum post, 2 1/2 ins. diam., 30 ins. long, 24 ins. in the ground, with aluminum cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 16 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T16S
R3WR2W
S1/16
S1 | S6
1997

Build a reference mound, 2 ft. diam., W of aluminum post.

Drive a 6 ft. steel fence post alongside aluminum post.

Cor. is located on a gradual southeast slope, in grass, and 20 lks. N of a draw, drains S. 70° E.

- 39.912** The 1/4 sec. cor. of secs. 1 and 6, T. 16 S., Rs. 2 and 3 W., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. and referenced as described in the field notes of the 1974 resurvey record.

N. 0°02.6' E., beginning new measurement.

- 39.910** The cor. of Tps. 15 and 16 S., Rs. 2 and 3 W., hereinbefore described.

Dependent Resurvey of a portion of the Subdivisional Lines
T. 16 S., R. 3 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed
by F. Dickert in 1871

From the cor. of secs. 1, 2, 35 and 36, on the S bdy. of the tp., hereinbefore described.

N. 0°07.2' W., bet. secs. 35 and 36.

- 39.976** Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 2 1/2 ins. diam., 30 ins. long, 15 ins. in the ground to bedrock, in a supporting mound of stone, 3 ft. diam., with aluminum cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 16 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T16SR3W
1/4
S35 | S36
1997

Drive a 6 ft. steel fence post alongside aluminum post.

Cor. is located on a gradual SE slope among rocks, grass and cactus.

79.952

Point for the cor. of secs. 25, 26, 35 and 36, at proportionate dist. utilizing 3 point method of adjustment; there is no remaining evidence of the original cor.

Set an aluminum post, 2 1/2 ins. diam., 30 ins. long, 15 ins. in the ground to bedrock, in a supporting mound of stone, 4 ft. diam., with aluminum cap mkd.

T16SR3W
S26 | S25
S35 | S36
1997

Drive a 6 ft. steel fence post alongside aluminum post.

Cor. is located on a gradual SE slope among grass and boulders, 100 lks. N of a shallow draw, bears E.

From the cor. of secs. 25, 30, 31 and 36, on the E bdy. of the tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. as described in the field notes of the 1974 resurvey record.

A 6 ft. steel fence post is alongside iron post.

Cor. is located on a gradual easterly slope among grass and rocks.

S. 89°44.6' W., bet. secs. 25 and 36.

40.151

Point for the 1/4 sec. cor. of secs. 25 and 36, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 2 1/2 ins. diam., 30 ins. long, 20 ins. in the ground to bedrock, in a supporting mound of stone, 3 ft. diam., with aluminum cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 16 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T16SR3W

1/4 $\frac{S25}{S36}$
1997

Build a reference mound, 3 ft. diam., S of aluminum post.

Drive a 6 ft. steel fence post alongside aluminum post.

Cor. is located on a gradual SE slope among grass and rocks.

80.302 The cor. of secs. 25, 26, 35 and 36.

N. 0°26.8' E., bet. secs. 25 and 26.

39.978 Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 2 1/2 ins. diam., 30 ins. long, 24 ins. in the ground, with aluminum cap mkd.

T16SR3W
1/4
S26 | S25
1997

Build a reference mound, 5 ft. diam., W of aluminum post.

Drive a 6 ft. steel fence post alongside aluminum post.

Cor. is located on a gradual SE slope among rocks, grass and cactus.

59.967 Point for the N 1/16 sec. cor. of secs. 25 and 26.

Set an aluminum post, 2 1/2 ins. diam., 30 ins. long, 14 ins. in the ground to bedrock, in a supporting mound of stone, 4 ft. diam., with aluminum cap mkd.

T16SR3W
N1/16
S26 | S25
1997

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 16 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Build a reference mound, 2 1/2 ft. diam., W of aluminum post.

Drive a 6 ft. steel fence post alongside aluminum post.

79.956 Point for the cor. of secs. 23, 24, 25 and 26, at proportionate dist. utilizing 3 point method of adjustment; there is no remaining evidence of the original cor.

Set an aluminum post, 2 1/2 ins. diam., 30 ins. long, 16 ins. in the ground to bedrock, in a supporting mound of stone, 4 ft. diam., with aluminum cap mkd.

T16SR3W
S23 | S24

S26 | S25
1997

Drive a 6 ft. steel fence post alongside aluminum post.

Cor. is located on a gradual northeast slope in grass and scattered rocks, 90 lks. N of a draw, drains N. 80° E.

From the cor. of secs. 19, 24, 25 and 30, on the E bdy. of the tp., hereinbefore described.

S. 88°40.7' W., bet. secs. 24 and 25.

39.937 Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 2 1/2 ins. diam., 30 ins. long, 24 ins. in the ground, with aluminum cap mkd.

T16SR3W
1/4 S24
S25
1997

Build a reference mound, 3 ft. diam., W of aluminum post.

Drive a 6 ft. steel fence post alongside aluminum post.

Cor. is located on a very gradual northeast slope among grass.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 16 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

79.874

The cor. of secs. 23, 24, 25 and 26.

N. 1°11.5' W., bet. secs. 23 and 24.

39.985

Point for the 1/4 sec. cor. of secs. 23 and 24, at proportionate dist.; there is no remaining evidence of the original cor., falls on a rock outcrop where it is impractical to set a standard aluminum post.

Set a rebar, 3/4 in. diam., 8 ins. long, 4 ins. in solid rock, with a 3 1/4 ins. diam. aluminum cap mkd.

T16SR3W
1/4
S23 | S24
1997

Cor. is located on a rock outcrop, about 100 lks. E of a barbed wire fence, bears N and S.

79.970

Point for the cor. of secs. 13, 14, 23 and 24, at proportionate dist. utilizing 3 point method of adjustment; there is no remaining evidence of the original cor.

Set an aluminum post, 2 1/2 ins. diam., 30 ins. long, 20 ins. in the ground, in a mound of stone, 4 ft. diam., with aluminum cap mkd.

T16SR3W
S14 | S13
S23 | S24
1997

Drive a 6 ft. steel fence post alongside aluminum post.

Cor. is located on a gradual E slope in grass and rocks, 30 lks. E of a barbed wire fence, bears N and S.

From the cor. of secs. 13, 18, 19 and 24, on the E bdy. of the tp., hereinbefore described.

S. 88°03.6' W., bet. secs. 13 and 24.

40.124

Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate dist.; there is no remaining evidence of the original cor.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 16 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 2 1/2 ins. diam., 30 ins. long, 24 ins. in the ground, with aluminum cap mkd.

T16SR3W

1/4 $\frac{S13}{S24}$
1997

Build a reference mound, 2 1/2 ft. diam., W of aluminum post.

Drive a 6 ft. steel fence post alongside aluminum post.

Cor. is located on a gradual E slope and on a small spur ridge, bears E.

80.248 The cor. of secs. 13, 14, 23 and 24.

N. 0°48.7' E., bet. secs. 13 and 14.

39.980 Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 2 1/2 ins. diam., 30 ins. long, 20 ins. in the ground, in a mound of stone, 3 ft. diam., with aluminum cap mkd.

T16SR3W
1/4

S14 | S13

1997

Drive a 6 ft. steel fence post alongside aluminum post.

Cor. is located on a gradual NE slope among grass and rocks, 110 lks. E of a barbed wire fence, bears N and S.

79.960 Point for the cor. of secs. 11, 12, 13 and 14, at proportionate dist. utilizing 2 point method of adjustment; there is no remaining evidence of the original cor.

Set an aluminum post, 2 1/2 ins. diam., 30 ins. long, 24 ins. in the ground, with aluminum cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 16 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T16SR3W

S11	S12
S14	S13
1997	

Build a reference mound, 3 ft. diam., W of aluminum post.

Drive a 6 ft. steel fence post alongside aluminum post.

Cor. is located on a small spur ridge, bears N. 70° E. and S. 70° W., 190 lks. E of a barbed wire fence, bears N and S.

From the cor. of secs. 7, 12, 13 and 18, on the E bdy. of the tp., hereinbefore described.

S. 88° 38.7' W., bet. secs. 12 and 13.

40.145 The 1/4 sec. cor. of secs. 12 and 13, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. as described in the field notes of the 1969 remonumentation record.

A steel fence post is 2 lks. W of iron post.

Cor. is located on a nearly level land in scattered juniper, 350 lks. N of trail road, bears E and W, and 200 lks. W of small draw, drains S. 20° E.

S. 86°43.3 W., beginning new measurement.

40.252 The cor. of secs. 11, 12, 13 and 14.

From the cor. of secs. 25, 26, 35 and 36.

West, bet. secs. 26 and 35.

40.000 Point for the 1/4 sec. cor. of secs. 26 and 35, determined utilizing 1 point control; there is no remaining evidence of the original cor.

Set an aluminum post, 2 1/2 ins. diam., 30 ins. long, 24 ins. in the ground, with aluminum cap mkd.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 16 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T16SR3W

1/4 $\frac{S26}{S35}$
1997

Build a reference mound, 3 ft. diam., W of aluminum post.

Drive a 6 ft. steel fence post alongside aluminum post.

Cor. is located on a gradual SE slope in grass, juniper and boulders, 120 lks. E of a barbed wire fence, bears N and S.

Survey of a Portion of the Subdivisional Lines
T. 16 S., R. 3 W., Salt Lake Meridian, Utah

From the cor. of secs. 1, 6, 7 and 12, on the E bdy. of the tp., hereinbefore described.

West, bet. secs. 1 and 12.

40.000 Point for the 1/4 sec. cor. of secs. 1 and 12.

Set an aluminum post, 2 1/2 ins. diam., 30 ins. long, 24 ins. in the ground, in a mound of stone, 4 1/2 ft. diam., with aluminum cap mkd.

T16SR3W

1/4 $\frac{S1}{S12}$
1997

Cor. is located on a SW slope and rocky ledge, among grass and scattered juniper, 20 lks. E of a barbed wire fence, bears N and S.

From the cor. of secs. 23, 24, 25 and 26.

West, bet. secs. 23 and 26.

40.000 Point for the 1/4 sec. cor. of secs. 23 and 26.

Set an aluminum post, 2 1/2 ins. diam., 30 ins. long, 24 ins. in the ground, in a mound of stone, 3 ft. diam., with aluminum cap mkd.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 16 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T16SR3W

1/4 S23
S26
1997

Cor. is located on a southeasterly slope, 60 lks. N of a draw, bears S. 10° E., and about 250 lks. E of a barbed wire fence, bears N and S.

Survey of a Portion of the Subdivision of Section 1,
T. 16 S., R. 3 W., Salt Lake Meridian

From the S 1/16 sec. cor. of sec. of secs. 1 and 6, on the E bdy. of the tp., hereinbefore described.

N. 89°38.5' W., parallel with the N boundary of sec. 1, on the E-W center line of the SE 1/4 of sec. 1.

40.297 Point for the center S 1/16 sec. cor. of sec. 1.

Set an aluminum post, 2 1/2 ins. diam., 30 ins. long, 24 ins. in the ground, in a mound of stone, with aluminum cap mkd.

T16SR3W
C
S1/16 | S1
C
1997

Build a reference mound, 2 ft. diam., S of aluminum post.

Cor. is located on a steep SE slope among rock and grass, 3 lks. W of a barbed wire fence, bears N and S.

N. 0°04.4' E., parallel with the E bdy. of sec. 1, on the N-S center line of sec. 1.

19.956 Point for the C 1/4 sec. cor. of sec. 1, at intersection with the E-W center line of sec. 1.

Set an aluminum post, 2 1/2 ins. diam., 30 ins. long, 18 ins. in the ground, with aluminum cap mkd.

T16SR3W

C1/4 S1

1997

SURVEY OF A PORTION OF THE SUBDIVISION OF SECTION 12,
T. 16 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Cor. is located on a steep northwesterly slope, 4 lks. W of a barbed wire fence, bears N and S.

N. 0°02.6' E., parallel with the E bdy. of sec. 1, on the N-S center line of sec. 1, beginning new measurement.

39.910 The 1/4 sec. cor. of secs. 1 and 36, on the N bdy. of the tp., hereinbefore described.

From the 1/4 sec. cor. of secs. 1 and 6, on the E bdy. of the tp., hereinbefore described.

N. 89°38.5' W., parallel with the N bdy. of sec. 1, on the E-W center line of sec. 1.

40.295 The C 1/4 sec. cor. of sec. 1.

From the 1/4 sec. cor. of secs. 1 and 12.

N. 0° 46.4' W., on the N-S center line of section 1.

20.212 The center S 1/16 sec. cor. of sec. 1.

Survey of a Portion of the Subdivision of Section 12,
T. 16 S., R. 3 W., Salt Lake Meridian

From the 1/4 sec. cor. of secs. 12 and 13.

N. 0°03.4' W., parallel with the E bdy. of sec. 12, on the N-S center line of sec. 12.

40.275 Point for the C 1/4 sec. cor. of sec. 12, at intersection with the E-W center line of sec. 12.

Set an aluminum post, 2 1/2 ins. diam., 30 ins. long, 24 ins. in the ground, with aluminum cap mkd.

T16SR3W

C1/4 S12

1997

Build a reference mound of stone, 2 ft. diam., W of aluminum post.

Drive a 6 ft. steel fence post alongside aluminum post.

SURVEY OF A PORTION OF THE SUBDIVISION OF SECTION 12,
T. 16 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Cor. is located in a swale, drains N. 80° E., 110 lks. W of a barbed wire fence, bears N and S.

N. 0°02.6' W., parallel with the E bdy. of sec. 12, on the N-S center line of sec. 12, beginning new measurement.

20.077 Point for the center N 1/16 sec. cor. of sec. 12, falls on a rock outcrop, where it is impractical to set a standard monument.

Set a rebar, 3/4 in. diam., 15 ins. long, 8 ins. in rock, with 3 1/4 ins. diam. aluminum cap mkd.

T16SR3W
C
N1/16 | S12
C
1997

Cor. is located on a steep and rocky E slope, 10 lks. E of a barbed wire fence, bears N and S.

N. 0° 18.0' E., beginning new measurement.

21.026 The 1/4 sec. cor. of secs. 1 and 12.

From the 1/4 sec. cor. of secs. 7 and 12, on the E bdy. of the tp., hereinbefore described.

S. 88°38.7' W., parallel with the S bdy. of sec. 12, on the E-W center line of sec. 12.

40.141 The C 1/4 sec. cor. of sec. 12.

From the N 1/16 sec. cor. of secs. 7 and 12, on the E bdy. of the tp., hereinbefore described.

S. 88°38.7' W., parallel with the S bdy. of sec. 12, on the E-W center line of the NE 1/4 of sec. 12.

40.139 The center N 1/16 sec. cor. of sec. 12.

SURVEY OF A PORTION OF THE SUBDIVISION OF SECTION 26,
T. 16 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Survey of a Portion of the Subdivision of Section 26,
T. 16 S., R. 3 W., Salt Lake Meridian

From the 1/4 sec. cor. of secs. 26 and 35.

N. 0°26.8' E., parallel with the E bdy. of sec. 26, on the N-S center line of sec. 26.

39.978 Point for the C 1/4 sec. cor. of sec. 26, at intersection with the E-W center line of sec. 26.

Set an aluminum post, 2 1/2 ins. diam., 30 ins. long, 14 ins. in the ground to bedrock, in a supporting mound of stone, 5 ft. diam. to top, with aluminum cap mkd.

T16SR3W

C1/4 S26

1997

Cor. is located on a gradual NE slope in grass and rocks, 150 lks. E of a barbed wire fence, bears N and S.

59.967 Point for the center N 1/16 sec. cor. of sec. 26.

Set an aluminum post, 2 1/2 ins. diam., 30 ins. long, 24 ins. in the ground, in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.

T16SR3W

C
N1/16 | S26
C
1997

Build a reference mound, 2 ft. diam., W of aluminum post.

Drive a 6 ft. steel fence post alongside aluminum post.

Cor. is located on a gradual NE slope in grass and rocks, 160 lks. E of a barbed wire fence, bears N and S.

N. 0° 25.4' E., beginning new measurement.

19.989 The 1/4 sec. cor. of secs. 23 and 26.

SURVEY OF A PORTION OF THE SUBDIVISION OF SECTION 26,
T. 16 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

39.996 From the 1/4 sec. cor. of secs. 25 and 26.
West, parallel with the S boundary of sec. 26, on the E-W center line of sec. 26.
The C 1/4 sec. cor. of sec. 26.

39.994 From the N 1/16 sec. cor. of secs. 25 and 26.
West, parallel with the S boundary of sec. 26, on the E-W center line of the NE 1/4 of sec. 26.
The center N 1/16 sec. cor. of sec. 26.

Survey of a Portion of the Subdivision of Section 35,
T. 16 S., R. 3 W., Salt Lake Meridian

39.973 From the 1/4 sec. cor. of secs. 2 and 35, on the S bdy. of the tp., hereinbefore described.
N. 0°09.6' W, on the N-S center line of sec. 35.
Point for the C 1/4 sec. cor. of sec. 35, at intersection with the E-W center line of sec. 35.
Set and aluminum post, 2 1/2 ins. diam., 30 ins. long, 20 ins. in the ground, in a mound of stone, 3 ft. diam., with aluminum cap mkd.

T16SR3W

C1/4 S35

1997

79.946 Drive a 6 ft. steel fence post alongside aluminum post.
Cor. is located on a gradual SE slope in rocks and boulders, 190 lks. E of a barbed wire fence, bears N and S.

The 1/4 sec. cor. of secs. 26 and 35.

From the 1/4 sec. cor. of secs. 35 and 36.
N. 89°59.8' W. on a mean bearing of the N and S boundaries of sec. 35.

SURVEY OF A PORTION OF THE SUBDIVISION OF SECTION 35,
T. 16 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

39.976 The C 1/4 sec. cor. of sec. 35.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Milton R. Workman	Land Surveyor
Stephen Oatman	Survey Technician
Shane L. Chamberlin	Survey Aid

CERTIFICATE OF SURVEY

I, *John F. Carroll, Cadastral Surveyor*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *15th day of September, 1997*, I have *dependently resurveyed a portion of the Third Standard Parallel South, along the south boundary of Township 15 South, Range 3 West, a portion of the south and east boundaries, a portion of the subdivisional lines, the subdivision of portions of sections 1, 12, 26, and 35, and the survey of a portion of the subdivisional lines, in Township 16 South, Range 3 West,*

of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

2-12-2001

Date

John F. Carroll

(Cadastral Surveyor)

Date

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of a portion of the Third Standard Parallel South, along the south boundary of Township 15 South, Range 3 West, a portion of the south and east boundaries, a portion of the subdivisional lines, the subdivision of portions of sections 1, 12, 26, and 35, and the survey of a portion of the subdivisional lines, in Township 16 South, Range 3 West,*

executed by *John L. Carroll, Cadastral Surveyor*

having been critically examined and found correct, are hereby approved.

February 16, 2001

Date

Daniel W. Webb

(Chief Cadastral Surveyor, Utah State Office)