

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF
THE DEPENDENT RESURVEY OF
A PORTION OF THE WEST BOUNDARY,
A PORTION OF THE SUBDIVISIONAL LINES,
AND THE
SUBDIVISION OF SECTIONS 18, 19, AND 20,
IN
TOWNSHIP 2 SOUTH, RANGE 6 WEST

OF THE UINTAH SPECIAL MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Richard L. Houston
Cadastral Surveyor

Under special instructions dated and approved *June 29, 1998*, approved *June 29, 1998*, which provided for the surveys included under Group Number 887, and assignment instructions dated *June 29, 1998*.

Survey commenced *July 21, 1998*
Survey completed *September 24, 1998*

INDEX DIAGRAM

Township 2 South , Range 6 West

6	5	4	3	2	1
7	8	9	10	11	12
14					
4 18 11	12 17 10	7 16	15	14	13
2 19	9 20 8	6 21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

The Subdivision of Section 18.....Page 15
 The Subdivision of Section 19.....Page 16
 The Subdivision of Section 20.....Page 18

TOWNSHIP 2 SOUTH, RANGE 6 WEST, UINTAH SPECIAL MER., UTAH

CHAINS

The following field notes describe the dependent resurvey of a portion of the west boundary, a portion of the subdivisional lines, and the subdivision of sections 18, 19 and 20, in T. 2 S., R. 6 W., Uintah Special Meridian, Utah.

HISTORY OF EARLIER SURVEYS

	Surveyed by	Rear. or Resurveyed by
SOUTH BOUNDARY		
All	A.J. Stewart, Jr. and A.L. Booth	1903
EAST BOUNDARY		
All	A.J. Stewart, Jr. and A.L. Booth	1903
WEST BOUNDARY		
All	A.J. Stewart, Jr. and A.L. Booth	1903
NORTH BOUNDARY		
All	A.J. Stewart, Jr. and A.L. Booth	1903
SUBDIVISION		
All	A.J. Stewart, Jr. and A.L. Booth	1903

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973 edition, and the Special Instructions dated June 29, 1998, for Group No. 887, Utah.

The direction of a portion of the lines were determined by hour angle observations of the sun, and carried forth by sustained angulation. Distances were determined by electronic measurement. Also the directions and distances of a portion of the lines were determined by the use of Global Positioning System (G.P.S.) using relative positioning techniques.

Preliminary to the resurvey, the lines of the original surveys were retraced and a diligent search was made for any evidence of the monuments and calls of the original field note record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

TOWNSHIP 2 SOUTH, RANGE 6 WEST, UINTAH SPECIAL MER., UTAH

CHAINS

The geographic position of the southeast corner of section 20, which will also function as a B.L.M. control station, was determined by a tie to national Geodetic Survey triangulation station "TABONIA", by G.P.S. using relative positioning techniques, is as follows:

Latitude: 40°17'04.450" N. Longitude: 110°34'39.125" W.
N.A.D 1983

The geographic position of "TABONIA", is:

Latitude: 40°19'32.55750" N. Longitude: 110°40'56.40480" W.
N.A.D. 1983 (1994)

The mean magnetic declination as projected from U.S. Geological Survey "MAGNETIC", Declination Map of 1990, is 13° E.

Dependent Resurvey of a Portion of the West Boundary,
T. 2 S., R. 6 W., Uintah Special Meridian, Utah

Reestablishment of the Survey Executed
by A.J. Stewart, Jr., and A.L. Booth in 1903

Beginning at the 1/4 section corner of sections 19 and 24, on the west boundary of the township, monumented with an unmarked sandstone, 24x11x4 inches (record, 24x12x6 inches) loosely set, projecting 10 inches above ground, with 1/2 inch rebar alongside.

From which the original bearing trees:

A pinon, 30 inches diameter, (record, 24 inches) bears E, 60 links distance, marked as described in the 1903 survey.

A pinon, 28 inches diameter, (record, 24 inches) bears S. 86° W., 36 links distance, with tree dead and laying down, marked as described in the 1903 survey.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a collar of stone, with aluminum cap marked:

T2S
1/4
R7W R6W
S24 | S19
1998

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 2 S., R. 6 W., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

Deposit a magnet at base of aluminum post.

Deposit sandstone and rebar alongside the aluminum post.

Corner is located on a pinon covered bench with a N slope.

From this corner, the section corner of sections 19, 24, 25, and 30, on the west boundary, monumented with a sandstone, 18x8x6 inches, firmly set, projecting 8 inches above the ground, marked 4 notches on the N edge and 2 notches on the S edge, bears S. 0° 00.2' E., 39.988 chains distance.

From which the original bearing trees:

A pinon, 8 inches diameter, (record, 6 inches) bears N. 44° E.,
110 links distance, blaze healed over.

A pinon, 7 inches diameter, (record, 4 inches) bears S. 63° E.,
95 links distance, marked as described in the 1903 survey.

A pinon, 8 inches diameter, (record, 5 inches) bears S. 26° W.,
120 links distance, blaze healed over.

A pinon, 7 inches diameter, (record, 5 inches) bears N. 73° W.,
81 links distance, marked as described in the 1903 survey.

Alongside the sandstone is a 1/2 inch rebar with plastic cap marked PEATROSS #4779, and a steel T-post next to rebar. A small mound is west of sandstone.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 14 inches in the ground, in a mound of stone, with aluminum cap marked:

T2S	
R7W	R6W
S24	S19
S25	S30
1998	

Deposit a magnet at base of aluminum post.

Deposit marked sandstone and rebar alongside the aluminum post.

Reset T-post alongside aluminum post.

Corner is located on W slope of N and s ridge, covered with pinons.

N. 0° 11.9' E., between sections 19 and 24, on the west boundary of the township.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 2 S., R. 6 W., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

19.703 Point for the N 1/16 section corner of sections 19 and 24, on the west boundary of the township. Not monumented.

39.406 Point for the corner of sections 13, 18, 19 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a collar of stone, 30 inch diameter at base, with aluminum cap marked:

T2S	
R7W	R6W
S13	S18
S24	S19
1998	

Deposit a magnet at base of aluminum post.

Corner is located 73 links N of the waters edge of the Duchesne River and 30 links S of a ditch in Russian Olive and cottonwood trees.

N. 0° 11.9' E., between sections 13 and 18, on the west boundary of the township.

39.406 Point for the 1/4 section corner of sections 13 and 18, determined from original bearing trees.

A pinon, 15 inches diameter, (record, 8 inches) bears S. 40° E.,
29 links distance, plainly marked as described in the 1903 survey.

A fallen pinon, 13 inches diameter, (record, 12 inches) bears S. 89° W.,
37 links distance. The root location fits record location. The blaze has
rotted and is illegible.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 15 inches in the ground to bedrock, in a mound of stone, 3 1/2 ft. base, to top of aluminum cap marked:

T2S	
R7W	R6W
1/4	
S13	S18
1998	

Deposit a magnet at base of aluminum post.

Corner is located on S slope covered with pinon and ledges.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 2 S., R. 6 W., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

N. 0°01.5" E., beginning new measurement.

39.700 The corner of sections 7, 12, 13, and 18, monumented with a soft sandstone, 24x10x10 inches, with marks obliterated.

from which the original bearing trees

A pinon, 14 inches diameter, (record, 10 inches) bears N. 49° E.,
41 links distance, marked as described in the 1903 survey.

A pinon, 22 inches diameter, (record, 20 inches) bears S. 35° E.,
36 links distance, marked as described in the 1903 survey.

A pinon, 22 inches diameter, (record, 20 inches) bears S. 56° W.,
49 links distance, marked as described in the 1903 survey.

A pinon, 14 inches diameter, (record, 10 inches) bears N. 62° W.,
90 links distance, plainly marked with blazed partially grown over,
marked as described in the 1903 survey.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 15 inches in the
ground to bedrock, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

T2S	
R7W R6W	
S12	S7
S13	S18
1998	

Deposit a magnet at base of aluminum post.

Corner is located in a small flat area on south slope in pinon and juniper.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 2 S., R. 6 W., Uintah Special Meridian, Utah

Reestablishment of the Survey Executed by
A.J. Stewart, Jr., and A.L. Booth in 1903

From the point for the corner of sections 20, 21, 28, and 29, determined from
original bearing trees.

A dead and standing pinon, 8 inches diameter, (record, 10 inches)
bears N. 19° E., (record, N. 16° E.) 124 links distance, burned
and plainly marked as described in the 1903 survey.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 2 S., R. 6 W., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

A dead and fallen pinon, 20 inches diameter, (record, 14 inches) bears S. 27° E., (record, S. 35° E.) 246 links distance, plainly marked as described in the 1903 survey.

No trace of pinon in SW quarter.

A dead and fallen pinon, 18 inches diameter, (record, 16 inches) bears N. 49° W., (record, N. 50° W) , 110 links distance, with blaze and burned scribes, marked as described in the 1903 survey.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T2S	R6W
S20	S21
S29	S28
1998	

From this corner, a N and S fence line bears W, 26.5 links distance.

From this same corner, a 3/8 inch rebar, with yellow plastic cap marked LS 4779, bears N. 81° 11.1' W., 26.9 links distance; not used in the reestablishment of this corner position.

N. 0°13.9' W., between sections 20 and 21.

39.589 The 1/4 section corner of sections 20 and 21, monumented with a sandstone, 16x10x7 inches, faintly marked and in a pile of stone.

From which the original bearing trees

A pinon, 15 inches diameter, (record, 12 inches) bears S. 80° E., 32 links distance, (record, 41 links) marked as described in the 1903 survey.

A red pine, 17 inches diameter, (record, 15 inches) bears N. 50° W., 31.5 links distance, (record, N. 45° W., 28 links) marked as described in the 1903 survey.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 16 inches in the ground to bedrock, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 2 S., R. 6 W., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

T2S R6W
1/4
S20 | S21
1998

Deposit the marked stone alongside the aluminum post.

N. 0°18.6' E., beginning new measurement.

19.895 Point for the N 1/16 section corner of sections 20 and 21.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground to bedrock, in a mound of stone, 3 1/2 ft. base, to top of aluminum cap marked:

N 1/16
S20 | S21
1998

Deposit a magnet at base of the aluminum post.

Corner is located on NW slope 150 lks. east of drainage to S.

39.790 Point for the corner of sections 16, 17, 20, and 21, determined longitudinally by a N - S fence and latitudinally by proportionate measurement; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a N and S fence line, with aluminum cap marked:

T2S R6W
S17 | S16
S20 | S21
1998

Deposit a magnet at base of aluminum post.

Corner is located 3 links S of intersection with new fence extending W.

N. 0° 05.6' W., between sections 16 and 17.

39.790 The 1/4 section corner of sections 16 and 17, monumented with a weathered illegible sandstone, 16x10x7 inches, 5 inches above the ground.

From which the original bearing trees

A dead and fallen pinon, 24 inches diameter, bears S. 24° 39' E.,
46 links distance, plainly marked and overgrown blaze..

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 2 S., R. 6 W., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

An uprooted pinon with a stump hole, 20 inches diameter,
bears S. 77° 30' W., 51 links distance, plainly marked as
described in the 1903 survey.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 15 inches in the
ground into a ledge, in a mound of stone to top of aluminum cap marked:

T2S R6W
1/4
S17 | S16
1998

Deposit the marked stone alongside the aluminum post.

From the corner of sections 20, 21, 28, and 29.

N. 89°24.4' W., between sections 20 and 29.

40.205 Point for the 1/4 section corner of sections 20 and 29, at proportionate distance;
there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 10 inches in the
ground to a ledge rock, in a mound of stone, 3 1/2 ft. base, to top of aluminum cap
marked:

T2S R6W
1/4 $\frac{S20}{S29}$
1998

Deposit a magnet at base of the aluminum post.

From which

A juniper, 11 inches diameter, bears S. 40° E., 16.4 links distance,
marked BT 1/4.

80.410 The corner of sections 19, 20, 29, and 30, monumented with a sandstone, 15x8x7
inches, projecting 3 inches above ground, firmly set, plainly marked with 2 notches
on S edge and 5 notches on E edge.

From which the original bearing trees

A pinon, 28 inches diameter, (record, 17 inches) bears N. 86° E.,
110 links distance, plainly marked with blaze partially healed,
marked as described in the 1903 survey.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 2 S., R. 6 W., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

A red pine, 30 inches diameter, (record, 11 inches) bears S. 50° E.,
14 links distance, (record, 12 links) with no scribe marks
and blaze overgrown.

A red pine, 28 inches diameter, (record, 6 inches) bears S. 66° W.,
89 links distance, with no scribe marks or blaze.

A red pine stump, 8 inches diameter, (record, 6 inches) bears N. 45° W.,
125 links distance, with no scribe marks or blaze.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the
ground, in a collar of stone, with aluminum cap marked:

T2S R6W	
S19	S20
S30	S29
1998	

Deposit a magnet at base of the aluminum post.

Deposit the marked sandstone alongside the aluminum post.

Corner is located on steep N slope covered with red pine and pinon.

From the 1/4 section corner of section 19 and 20, monumented with a sandstone,
20x12x8 inches, (record, 20x12x5 inches) with no marks visible, and 1/2 inch rebar
alongside.

From which the original bearing trees

A pinon, 8 inches diameter, (record, 10 inches) bears S. 44° E.,
29 links distance, (record, S. 45° E., 30 links distance) The
blaze is overgrown with no legible marks.

A pinon, 14 inches diameter, bears N. 49° W., 19.4 links distance,
(record, N. 45° W., 20 links distance) with an open blaze
and marked as described in the 1903 survey.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the
ground, with aluminum cap marked:

T2S R6W	
1/4	
S19	S20
1998	

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 2 S., R. 6 W., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

Deposit the sandstone alongside the aluminum post.

Deposit 1/2 inch rebar inside the aluminum post.

N. 0°03.1' E., between sections 19 and 20.

20.018 Point for the N 1/16 section corner of sections 19 and 20.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 14 inches in the ground to bedrock, and in a supporting mound of stone, 3 1/2 ft. base, to top of aluminum cap marked:

N 1/16	
S19	S20
1998	

40.036 Point for the corner of sections 17, 18, 19 and 20, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T2S R6W	
S18	S17
S19	S20
1998	

Set a 4 inch diameter cedar post, 1 ft. E of aluminum post.

Corner is located S, 30 links from an E and W fence line.

A rebar with a plastic cap, marked LS 4779, bears N. 5° 59.1' W., 30.8 links, not used in the reestablishment of this corner position.

From the corner of sections 16, 17, 20, and 21.

S. 89° 59.6' W., between sections 17 and 20.

39.850 The 1/4 section corner of sections 17 and 20, monumented with a 1/2 inch rebar with cap marked "PEATROSS" 155666. There is no remaining evidence of the original corner. This rebar is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, in a collar of stone, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 2 S., R. 6 W., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

T2S R6W
1/4 $\frac{S17}{S20}$
1998

Deposit a magnet at base of the aluminum post.

Deposit 1/2 inch rebar alongside the aluminum post.

Corner is located next to fence corner, bearing N, S, E, and W.

Corner is located in river bottom area along E side of a 3 ft. diameter cottonwood tree.

N. 89° 59.8' W., beginning new measurement.

40.146 The corner of sections 17, 18, 19, and 20.

N. 88° 54.3' W., between sections 18 and 19.

20.097 Point for the E 1/16 section corner of sections 18 and 19.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a collar of stone, with aluminum cap marked:

T2S R6W
E 1/16 $\frac{S18}{S19}$
1998

Deposit a magnet at base of the aluminum post.

Corner is located in an E and W fence line.

39.086 Point selected for the witness 1/4 section corner of sections 18 and 19.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, in a collar of stone, with aluminum cap marked:

WC
T2S R6W
1/4 $\leftarrow \frac{S18}{S19}$
1998

Deposit a magnet at base of the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 2 S., R. 6 W., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

Corner is located N, 41.5 links from a 4 strand barbed wire fence and on the right bank of the Duchesne River.

40.194 True point for the 1/4 section corner of sections 18 and 19, falls in Duchesne River.

60.161 Point selected for the witness W 1/16 section corner of sections 18 and 19.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with aluminum cap marked:

WC
 ← S18
 S19
 1998

Deposit a magnet at base of the aluminum post.

Corner is located S, 5 links from an E and W fence line, and on the left bank of the Duchesne River.

60.291 True point for the W 1/16 section corner of sections 18 and 19, falls in Duchesne River.

78.047 The corner of sections 13, 18, 19, and 24, on the west boundary of the township, hereinbefore described.

From the corner of sections 17, 18, 19, and 20.

N. 0° 13.7' E., between sections 17 and 18.

20.018 Point for the S 1/16 section corner of sections 17 and 18.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground to a ledge, in a support mound of stone, with base, 42 inches diameter, to top of aluminum cap marked:

S 1/16
 S18 | S17
 1998

Deposit a magnet at base of the aluminum post.

Corner is located on a bench of S slope, which is a continuous series of ledge shelves forming the N canyon wall of the Duchesne River.

40.036 The 1/4 section corner of sections 17 and 18, monumneted with a 3/8 inch rebar; there is no remaining evidence of the original stone.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 2 S., R. 6 W., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

From which the original bearing trees:

A pinon, 10 inches diameter, (record, 8 inches) bears S. 45° E.,
40 links distance, scribed and plainly marked as described in the
1903 survey.

A pinon, 8 inches diameter, (record, 7 inches), bears S. 75° W., 25 links
distance, tree has fallen down, scribed and plainly marked as described
in the 1903 survey.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 18 inches in the
ground to bedrock, in a mound of stone, to top of aluminum cap marked:

T2S R6W
1/4
S18 | S17
1998

Deposit a magnet at base of the aluminum post.

Deposit the rebar alongside the aluminum post.

N. 0° 04.3' E., beginning new measurement.

39.779 The corner of sections 7, 8, 17, and 18, monumented with a rebar. There is no
remaining evidence of the original stone. This rebar was set from bearing trees.

From which the original bearing trees:

A pinon, 11 inches diameter, bears N. 78° E., 50 links distance,
marked as described in the 1903 survey.

A pinon, 15 inches diameter, (record, 11 inches), bears S. 24° E.,
35 links distance, marked as described in the 1903 survey. Also,
a metal "BT" plate attached.

A pinon, 12 inches diameter, bears S. 19° W., 42 links distance,
marked as described in the 1903 survey.

A pinon, 8 inches diameter, bears N. 52° W., 60 links distance,
marked as described in the 1903 survey.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the
ground, in a collar of stone, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 2 S., R. 6 W., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

T2S R6W	
S 7	S8
S18	S17
1998	

Deposit a magnet at base of the aluminum post.

Deposit the rebar alongside the aluminum post.

Corner is located S, 180 links from road that runs E and W on top of a ridge.

N. 89° 31.0' W., between sections 7 and 18.

38.588 The 1/4 section corner of sections 7 and 18, monumented with a sandstone, 15x10x7 inches, projecting 6 inches above ground, firmly set, and plainly marked as described in the 1903 survey.

From which the original bearing trees:

A pinon, 16 inches diameter, bears N. 45° E., 60 links distance, scribing faintly visible, tree not vertical.

A pinon, 14 inches diameter, bears S, 42 links distance, marked as described in the 1903 survey.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

1/4	T2S R6W
	S7
	S18
	1998

Deposit a magnet at base of the aluminum post.

Deposit the marked stone alongside the aluminum post.

N. 89° 20.3' W., beginning new measurement.

39.485 The corner of sections 7, 12, 13, and 18, on the west boundary of the township, hereinbefore described.

THE SUBDIVISION OF SECTION 18,
T. 2 S., R. 6 W., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

The Subdivision of Section 18,
T. 2 S., R. 6 W., Uintah Special Meridian, Utah

From the true point for the 1/4 section corner of sections 18 and 19.

N. 1° 17.9' E., on the N-S center line of section 18.

19.857 Point for the center S 1/16 section corner of section 18, not monumented.

39.714 Point for the center 1/4 section corner of section 18, at intersection with the E-W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 6 inches in the ground on ledge, in a mound of stone, 3 1/2 ft. base, to top aluminum cap marked:

T2S R6W
C 1/4 S18
1998

Deposit a magnet at base of the aluminum post.

Corner is located on the ledge of a bench on S slope in pinon and juniper.

79.393 The 1/4 section corner of sections 7 and 18.

From the 1/4 section corner of sections 17 and 18.

N. 89° 22.1' W., on the E-W center line of section 18.

19.721 Point for the center E 1/16 section corner of section 18, not monumented.

39.442 The center 1/4 section corner of section 18.

78.049 The 1/4 section corner of sections 13 and 18, on the west boundary of the township, hereinbefore described.

From the E 1/16 section corner of sections 18 and 19.

N. 0° 45.7' E., on the N-S center line of the SE 1/4 of section 18.

19.938 Point for the SE 1/16 section corner of section 18.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a cross (X) carved in solid sandstone, in a mound of stone, 5 ft. base, to top of aluminum cap marked:

THE SUBDIVISION OF SECTION 18,
T. 2 S., R. 6 W., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

SE 1/16 S18
1998

Corner is located on a ledgey S slope into Duchesne River.

39.876 Point for the center E 1/16 section corner of section 18.

From the S 1/16 section corner of sections 17 and 18.

N. 89° 08.1' W., on the E-W center line of the SE 1/4 of section 18.

19.909 The SE 1/16 section corner of section 18.

39.818 Point for the center S 1/16 section corner of section 18.

The Subdivision of Section 19,
T. 2 S., R. 6 W., Uintah Special Meridian, Utah

From the 1/4 section corner of sections 19 and 30, monumented with a sandstone, 21x8x7 inches (record, 18x10x8 inches) loosely set, marked as described in the 1903 survey.

From which the original bearing trees:

A red pine, 14 inches diameter, bears N, 23.1 links distance,
(record, 25 links distance) with overgrown blaze.

A red pine, 14 inches diameter, bears S, 13.6 links distance,
with blaze overgrown.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a collar of stone, with aluminum cap marked:

T2S R6W
1/4 $\frac{S19}{S30}$
1998

Deposit a magnet at base of the aluminum post.

Deposit the sandstone alongside the aluminum post.

Corner is located on steep NW slope at 230 links distance, from center line of drainage to NE.

N. 0° 08.0' W., on the N-S center line of section 19.

THE SUBDIVISION OF SECTION 19,
T. 2 S., R. 6 W., UTAH SPECIAL MERIDIAN, UTAH

CHAINS**39.340**

Point for the center 1/4 section corner of section 19, at intersection with the E-W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a collar of stone, with aluminum cap marked:

T2S R6W
C 1/4 S19
1998

Deposit a magnet at base of the aluminum post.

Corner is located on a steep N slope covered with pine and pinon.

59.197

True point for the center N 1/16 section corner of section 19, falls on a rock ledge with a cross (x) chiseled at true point.

59.263

Point selected for the witness center N 1/16 section corner of section 19.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 16 inches in the ground, in a mound of stone, to top of aluminum cap marked:

WC
C
N 1/16 ↓ S19
C
1998

Deposit a magnet at base of the aluminum post.

Witness corner is located 3.5 links N of a base of a ledge on steep N slope.

79.054

True point for the 1/4 section corner of sections 18 and 19.

From the 1/4 section corner of sections 19 and 20.

N. 88° 26.6' W., on the E-W center line of section 19.

40.076

The center 1/4 section corner of section 19.

60.336

The point for the center W 1/16 section corner of section 19, not monumented.

78.169

The 1/4 section corner of sections 19 and 24, on the west boundary of the township, hereinbefore described.

THE SUBDIVISION OF SECTION 19,
T. 2 S., R. 6 W., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

- From the N 1/16 section corner of sections 19 and 20.
N. 88° 40.5' W., on the E-W center line of the NE 1/4 of section 19.
- 40.135** The true point for the center N 1/16 section corner of section 19.
-
- From the point for the center W 1/16 section corner of section 19.
N. 0° 06.3' E., on the N-S center line of the NW 1/4 of section 19.
- 19.775** Point for the NW 1/16 section corner of section 19, at intersection with the E-W center line.
Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground, in a mound of stone, 3 1/2 ft. base, to top of aluminum cap marked:
- NW 1/16 S19
1998
- Deposit a magnet at base of the aluminum post.
Corner is located on a steep N slope, 6 links N of a rock outcrop.
- 39.550** True point for the W 1/16 section corner of sections 18 and 19.
-
- From the true point for the center N 1/16 section corner of section 19.
N. 88° 40.6' W., on the E-W center line of the NW 1/4 of section 19.
- 20.178** The NW 1/16 section corner of section 19.
- 37.972** The point for the N 1/16 section corner of sections 19 and 24 on the west boundary of the township, not monumented.
-
- The Subdivision of Section 20,
T. 2 S., R. 6 W., Uintah Special Meridian, Utah
-
- From the 1/4 section corner of sections 20 and 29.
N. 0° 17.4' E., on the N-S center line of section 20.
- 39.050** Point for the center 1/4 section corner of section 20, at intersection with the E-W center line.

THE SUBDIVISION OF SECTION 20,
T. 2 S., R. 6 W., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked:

T2S R6W
C 1/4 S20
1998

From which a bearing tree:

A pine, 28 inches diameter, bears S. 38° W., 48.5 links distance, marked BT C 1/4.

Deposit a magnet at base of the aluminum post.

Corner is located on steep N slope at 230 links distance N of a 30 ft. high rock outcrop.

59.005 Point for the center N 1/16 section corner of section 20.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground to bedrock, in a mound of stone, 4 ft. base, to top of aluminum cap marked:

C
N 1/16 | S20
C
1998

Deposit a magnet at base of the aluminum post.

From this corner, a 5/8 inch rebar bears N. 23° 42' E., 21.9 links distance.

Corner is located on a bench with steep N slope and 15 ft. S of rock outcrop.

78.960 The 1/4 section corner of sections 17 and 20.

From the 1/4 section corner of sections 20 and 21.

S. 89° 49.2' W., on the E-W center line of section 20.

39.840 The center 1/4 section corner of section 20.

79.824 The 1/4 section corner of sections 19 and 20.

From the N 1/16 section corner of sections 20 and 21.

S. 89° 54.4' W., on the E-W center line of the NE 1/4 of section 20.

THE SUBDIVISION OF SECTION 20,
T. 2 S., R. 6 W., UTAH SPECIAL MERIDIAN, UTAH

CHAINS
39.845

The center N 1/16 section corner of section 20.

From the center N 1/16 section corner of section 20.

S. 89° 54.7' W., on the E-W center line of the NW 1/4 of section 20.

40.066

The N 1/16 section corner of sections 19 and 20.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Ronald Baugh	Supervisory Cadastral Surveyor
M.R. Workman	Supervisory Cadastral Surveyor
Harvey Pinegar	Survey Aid
Keith Batty	Survey Aid.

CERTIFICATE OF SURVEY

I, *Richard L. Houston, Cadastral Surveyor*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *29th day of June, 1998*, I have *dependently resurveyed a portion of the west boundary, a portion of the subdivisional lines and subdivision of section 18, 19, and 20, Township 2 South, Range 6 West*,

of the Uintah Special Meridian, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for The Public Lands of the United States, and in specific manner described in the foregoing field notes.

6/22/2000

Date

Richard L. Houston

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of a portion of the west boundary, a portion of the subdivisional lines and the subdivision of sections 18, 19 and 20, in Township 2 South, Range 6 West, Uintah Special Meridian, Utah*,

executed by *Richard L. Houston, Cadastral Surveyor*

having been critically examined and found correct, are hereby approved.

August 3, 2000

Date

Daniel W. Webb

(Chief Cadastral Surveyor for Utah)