

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF

A PORTION OF THE WEST BOUNDARY (UINTAH SPECIAL MERIDIAN),

A PORTION OF THE NORTH BOUNDARY (UINTAH SPECIAL BASE LINE),

A PORTION OF THE SUBDIVISIONAL LINES,

AND

A PORTION OF THE SUBDIVISION OF SECTION 6 BY THE 3 MILE METHOD

AND

THE SURVEY OF A PORTION OF THE SUBDIVISION OF SECTION 6

IN

TOWNSHIP 1 SOUTH, RANGE 1 EAST

OF THE UINTAH SPECIAL MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Richard L. Houston
Cadastral Surveyor

Under special instructions dated *July 1, 1998*, approved *July 27, 1998*, which provided for the surveys included under Group Number *888*, and authorization/assignment instructions dated *July 1, 1998*.

Survey commenced *July 13, 1998*
Survey completed *August 20, 1998*

INDEX DIAGRAM

5 4 Township 1 South, Range 1 East

2	6	6	5	4	3	2	1
	7	8	9	10	11	12	
	18	17	16	15	14	13	
	19	20	21	22	23	24	
	30	29	28	27	26	25	
	31	32	33	34	35	36	

Resurvey of a Portion of the Subdivision of Section 6.....Page 8
 by the Three Mile Method
 Survey of a Portion of the Subdivision of.....Page 11
 Section 6

TOWNSHIP 1 SOUTH, RANGE 1 EAST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

The following field notes are those of the dependent resurvey of a portion of the west boundary (Uintah Special Meridian), a portion of the north boundary (Uintah Special Base Line), a portion of the subdivisional lines, and a portion of the subdivision of section 6, by the three mile method, and the survey of a portion of the subdivision of section 6, in Township 1 South, Range 1 East, of the Uintah Special Meridian, Utah.

History of Surveys

	Surveyed by	Rear. or Resurveyed by	
SOUTH BOUNDARY			
All	C.L. DuBois	1875	
EAST BOUNDARY			
All	C.L. DuBois	1875	
WEST BOUNDARY (Uintah Special Meridian)			
All Portion	C.L. DuBois	1875	A. Nelson 1953
NORTH BOUNDARY (Uintah Special Base Line)			
All Portion	C.L. DuBois	1875	A. Nelson 1953
SUBDIVISION			
All	C.L. DuBois	1875	

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 888, Utah, dated July 1, 1998.

Preliminary to the resurvey, the lines of the original survey were retraced and a search was made for all corners and other calls of record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The direction of the lines of this survey refer to the true meridian, and were determined by hour angle observations of the sun, with a combination of GPS observations. The lines were carried forward by sustained angulation being supplemented by other solar observations taken throughout the progress of the survey. The measurements of these lines were made with an electronic total station.

TOWNSHIP 1 SOUTH, RANGE 1 EAST, UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

A magnetic marker, was deposited at the base of each monument, so indicated. This marker consist of a magnet, 1 inch long, 7/8 inch diameter, housed in a cellulose acetate tube, 2 5/8 inches long, 1 inch diameter, with 1 inch square Polyethylene end caps.

The geographic position of the SE corner of section 6, which will also function as a B.L.M. Control Station, determined by G.P.S., using relative positioning techniques, from U.S. Geological Survey triangulation stations "OLA" and "POINT", is as follows:

Latitude: 40°25'06.203" N. Longitude: 109°54'57.992" W.
N.A.D. 1983

The geographic position of U.S. Geological Survey triangulation station "OLA", is as follows:

Latitude: 40°26'51.40573" N. Longitude: 110°02'54.83549" W.
N.A.D. 1983 (1994)

The geographic position of triangulation station "POINT" is as follows:

Latitude: 40°24'38.33325" N. Longitude: 109°47'17.09606" W.
N.A.D. 1983 (1994)

The mean magnetic declination as projected from the U.S. Geological Survey "Magnetic Declination Map of 1990" is 13° East.

Dependent Resurvey of a Portion of the West Boundary,
(Uintah Special Meridian, Utah)
T. 1 S., R. 1 E., Uintah Special Meridian, Utah

Reestablishment of the Surveys Executed by C.L. DuBois 1875,
and the Reestablishment of the Survey Executed by A. Nelson 1953

Beginning at the corner of sections 1, 6, 7 and 12 monumented with an iron post, 2 1/2 inches diameter, flush with the ground, with brass cap marked as described in the official record of the 1953 reestablishment survey, from which the 1953 reference monuments

An iron post, 2 1/2 inches diameter, projecting 10 inches above ground, 15 inches SW of corner of fences extending S and W, with brass cap marked as described in the official record of the 1953 reestablishment survey, bears S. 47°00' W., 67.3 links.

An iron post, 2 1/2 inches diameter, projecting 8 inches above ground, 17 inches NW of corner of fences extending W and N, with brass cap marked as described in the official record of the 1953 reestablishment survey, bears N. 48°00' W., 72.3 links.

Corner is located at the intersection of lanes extending N, S and W.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
(UINTAH SPECIAL MERIDIAN, UTAH)
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

N. 0°04.9' W., between sections 1 and 6, on the west boundary of the township..

20.000 Point for the S 1/16 section corner of sections 1 and 6, on the west boundary of the township, at proportionate distance; there is no remaining evidence of the original corner; not monumented.

40.000 Point for the 1/4 section corner of sections 1 and 6, on the west boundary of the township, at proportionate distance; there is no remaining evidence of the original corner; not monumented.

60.000 Point for the N 1/16 section corner of sections 1 and 6, on the west boundary of the township, at proportionate distance; there is no remaining evidence of the original corner; not monumented.

80.000 The initial point for the Uintah Special Meridian and Base Line, falls 3 feet below the surface, and near the center line of a paved road, extending E and W, as determined from the three 1953 Andrew Nelson reference monuments. Using his three record distances to determine the true point, without disrupting the surface of the road, the geographic position was calculated as follows:

Latitude: 40°25'58.379" N. Longitude: 109°56'07.418" W.
N.A.D. 1983

From this true point,

An iron post, 2 1/2 inches diameter, 15 inches below ground, with brass cap marked as described in the official record of the 1953 Nelson reestablishment, bears S. 46°15' E., 51.6 ft. (78.2 links).

The geographic position by G.P.S. of this reference monument is as follows:

Latitude: 40°25'58.023" N. Longitude: 109°56'06.936" W.
N.A.D. 1983

An iron post, 2 1/2 inches diameter, in a collar of stone, at the corner of fences extending south and west; with a brass cap marked as described in the official record of the 1953 Nelson reestablishment, bears S. 51°45' W., 61.0 ft. (92.4 links).

The geographic position by G.P.S. of this reference monument is as follows:

Latitude: 40°25'58.006" N. Longitude: 109°56'08.038" W.
N.A.D. 1983

An iron post, 2 1/2 inches diameter, projecting 5 inches above ground, in a fence extending N and S, with brass cap marked as described in the official record of the 1953 Nelson reestablishment, bears N. 47°15' W., 62.0 ft. (93.9 links).

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
 (UINTAH SPECIAL MERIDIAN, UTAH)
 T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

The geographic position by G.P.S. of this reference monument is as follows:

Latitude: 40°25'58.797" N. Longitude: 109°56'08.004" W.
 N.A.D. 1983

Dependent Resurvey of a Portion of the Uintah Special Base Line,
 On the South Boundary,
 T. 1 N., R. 1 E., Uintah Special Meridian, Utah

Reestablishment of the Surveys Executed by C.L. DuBois 1875,
 and the Reestablishment of Corners Executed by A. Nelson 1953

From the Standard corner of sections 32 and 33, on the south boundary of T. 1 N., R. 1 E., determined at the intersection of center lines of county roads that extend North and East, and is accepted as the best available evidence of the original corner position.

Set a large nail, 6 inches long, 2 inches below dirt surface of road.

from which

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a collar of stone, for a reference monument, bears S. 6°25.7' W., 38.1 links with aluminum cap marked T1N R1E RM 25.15 FT 1998 and an arrow pointing to the corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a collar of stone, for a reference monument, bears N. 89°02.2' W., 41.4 links with aluminum cap marked T1N R1E S32 RM 27.03 FT 1998 and an arrow pointing to the corner.

N. 89°55.2 W., along the south boundary of section 32.

Over river bottom land.

- 0.180** Point for the closing corner of sections 4 and 5, T. 1 S., R. 1 E., at proportionate distance; there is no remaining evidence of the original corner; not monumented.
- 20.042** Point for the Standard E 1/16 section corner of section 32, T. 1 N., R. 1 E., at proportionate distance; there is no remaining evidence of the original corner; not monumented.
- 40.084** Point for the Standard 1/4 section corner of section 32, T. 1 N., R. 1 E., at proportionate distance; there is no remaining evidence of the original corner; not monumented.

DEPENDENT RESURVEY OF A PORTION OF THE UINTAH SPECIAL
BASE LINE, ON THE SOUTH BOUNDARY,
T. 1 N., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

- 60.126** Point for the Standard W 1/16 section corner of section 32, T. 1 N., R. 1 E., at proportionate distance; there is no remaining evidence of the original corner; not monumented.
- 79.010** True intersection point for the closing corner of sections 5 and 6, T.1 S., R.1 E., the corner falls in a creek bottom.
- 80.168** The Standard corner of sections 31 and 32, T. 1 N., R. 1 E., monumented with an iron post, 30 inches long, 2 1/2 inches diameter, projecting 4 inches above ground, with brass cap marked as described in the official record of the reestablishment by Andrew Nelson in 1953.
-
- S. 89°58.8' W., on the south boundary of section 31, T. 1 N., R. 1 E.
- 18.940** Point for the E 1/16 section corner of section 6 only, T. 1 S., R. 1 E., on the north boundary of section 6.
- Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a collar of stone, with aluminum cap marked.
- $$\frac{E \ 1/16 \ S \ 6}{1998}$$
- Deposit magnet at base of aluminum post.
- 19.986** The Standard E 1/16 section corner of section 31, T. 1 N., R. 1 E., monumented with a galvanized pipe, 2 1/2 inches diameter, projecting 12 inches above ground, with brass cap marked 1959 1/16, firmly set, with a marked sandstone alongside, 8x5x7 inches above ground, record (16x12x7), marked 1/16 east face, SC west face.
- Add marks to cap, BLM 1998.
- Corner is located at the corner of fences extending W and S.
-
- N. 89°46.9' W., beginning new measurement.
- 9.003** Point for the W - E 1/64 section corner of section 6 only, on the north boundary, T. 1 S., R. 1 E; not monumented.
- 18.972** Point selected for the witness 1/4 section corner of section 6 only, on the north boundary, T. 1 S., R.1 E.
- Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a collar of stone, with aluminum cap marked.

DEPENDENT RESURVEY OF A PORTION OF THE UTAH SPECIAL
BASE LINE, ON THE SOUTH BOUNDARY,
T. 1 N., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

WC
T 1 N R 1 E
←—————
1/4 S 6
T 1 S R 1 E
1998

Deposit the magnet at base of aluminum post.

Corner is located in a barbed wire fence extending E and W.

19.052 True point for the 1/4 section corner of section 6 only, falls in inaccessible area and cannot be monumented.

19.790 The Standard 1/4 section corner of section 31, T. 1 N., R. 1 E., monumented with a galvanized pipe, 2 1/2 inches diameter, projecting 11 inches above ground, with a brass cap marked: 1959 S31 1/4 SC T1N / T1S, with a 14x7x7 inches sandstone alongside, marked 1/4 N face and SC S face.

Rehabilitate with stone collar and add marks to cap: BLM 1998

Corner is located 7 ft. S of a ditch and 35 ft. S of an unimproved road, in thick brush and at the intersection of fences extending E, W and S.

S. 89°38.0' W., beginning new measurement.

19.361 Point for the W 1/16 section corner of section 6 only, T. 1 S., R. 1 E.; not monumented.

20.212 Point for the Standard W 1/16 section corner of section 31, at proportionate distance; there is no remaining evidence of the original corner; not monumented.

40.424 True point for the Initial Point for the Uintah Special Meridian and Base Line, hereinbefore described.

Dependent Resurvey of the Subdivisional Lines,
T. 1 S., R. 1 E., Uintah Special Meridian, Utah.

Reestablishment of the Surveys Executed by
C. J. Du Bois in 1875.

From the corner of sections 5, 6, 7, and 8, monumented with a sandstone, firmly set, 14x6x8 inches, projecting 3 inches above ground, plainly marked, 5 grooves on S face and 5 grooves on E face.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a collar of stone, with aluminum cap marked:

T	1	S	R	1	E
	S	6		S	5
	S	7		S	8
				1998	

Corner is located 25 ft. W of a canal center line, flowing S.

From this corner, the corner of sections 1, 6, 7, and 12, on the west boundary of the township, hereinbefore described, bears N. 89°59.1' W., 81.289 chains distance.

N. 0°04.5' E., between sections 5 and 6.

19.920 Point for the S 1/16 section corner of sections 5 and 6, at proportionate distance; there is no remaining evidence of the original corner; not monumented.

39.840 Point for the 1/4 section corner of sections 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a collar of stone, with aluminum cap marked.

T	1	S	R	1	E
				1/4	
	S	6		S	5
				1998	

Deposit the magnet at base of aluminum post.

Corner is located on level ground, with a sparse covering of brush, and 21 ft. N of 4 strand barbed wire fence, extending E and W.

59.760 The N 1/16 section corner of sections 5 and 6, monumented with a sandstone, 16x6x4 inches, loosely set and plainly marked 1/16 on face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a collar of stone, with aluminum cap marked.

	N	1/16	
S	6		S 5
			1998

Deposit the marked stone alongside aluminum post.

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

Deposit the magnet at base of aluminum post.

Corner is located in thick sage, 110 ft. E of an unimproved road.

N. 0°14.7' W., beginning new measurement.

20.199 The witness corner to the closing corner of sections 5 and 6, monumented with a galvanized pipe, 2 1/2 inches diameter, projecting 16 inches above ground, with a brass cap marked: WC CC S5 S6 WC T1S R1E, with a sandstone 11x7 projecting 6 inches above ground, marked WC north, and CC south faces.

Raised a collar of stone around pipe, and add marks to cap, BLM 1998.

20.451 True point for the closing corner of sections 5 and 6 at intersection with the south boundary of section 32, T. 1 N., R. 1 E., hereinbefore described.

Dependent Resurvey of a Portion of the Subdivision of
Section 6, by the Three Mile Method,
T. 1 S., R. 1 E., Uintah Special Meridian, Utah

Reestablishment of the Survey Executed by C. L. Du Bois in 1875

From the 1/4 section corner of sections 5 and 6.

N. 89°52.3' W., on the E-W center line of section 6.

Over level land, covered with brush and trees.

20.052 Point for the center E 1/16 section corner of section 6, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a collar of stone, with aluminum cap marked.

C $\frac{E \ 1/16}{S6}$ C
1998

Deposit the magnet at base of aluminum post.

Corner is located north, 8.70 ft. from a fence extending E and W, and west, 30 ft. from a fence extending N and S.

30.078 Point for the C-W-E 1/64 section corner of section 6.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISION OF
SECTION 6, BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a collar of stone, with aluminum cap marked.

S 6
C-W-E
1/64
1998

Deposit the magnet at base of aluminum post.

Corner is located east, 17.2 ft. from a fence, extending N and S, and north, 38.6 ft., off a corral fence.

40.104 Point for the center 1/4 section corner of section 6, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a collar of stone, with aluminum cap marked:

T 1 S R 1 E
C 1/4 S 6
1998

Deposit the magnet at base of aluminum post.

Corner is located west, 28.1 ft., from a fence extending N and S, and south, 4.1 ft., from a fence extending E and W, and west, 25 ft., from the west bank of the west channel of the Uinta River.

60.156 Point for center W 1/16 section corner of section 6, at proportionate distance; there is no remaining evidence of the original corner, not monumented.

81.370 Point for the 1/4 section corner of sections 1 and 6, on the west boundary of the township, hereinbefore described. Not monumented.

From the N 1/16 section corner of sections 5 and 6.

N. 89°48.9' W., on the E-W center line of the N 1/2 of section 6.

Over river bottom land, covered with brush and trees.

20.040 Point for the NE 1/16 section corner of section 6, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a collar of stone, with aluminum cap marked.

NE 1/16 S 6
1998

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISION OF
SECTION 6, BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

Deposit the magnet at base of aluminum post.

Corner is located 22 ft. south of a 4 strand barbed wire fence extending E and W, and S. 70°48' E., 72.48 ft. from a fence corner with fences extending E and W and N.

30.060 Point for the C-W-NE 1/64 section corner of section 6.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, in a mound of stone, 3 ft. base to top of aluminum cap marked.

S6
C-W-NE
1/64
1998

Deposit the magnet at base of aluminum post.

Corner is located south, 31 ft. off a fence extending E and W, in thick river bottom willows.

40.080 Point for the center N 1/16 section corner of section 6, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked.

C
N 1/16 | S6
C
1998

Deposit the magnet at base of aluminum post.

Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, east of corner.

Corner is located east, 65 ft. off a fence extending N and S, and south, 43 ft. of a fence extending E and W.

60.120 Point for the NW 1/16 section corner of section 6, at proportionate distance; there is no remaining evidence of the original corner, not monumented.

81.422 Point for the N 1/16 section corner of sections 1 and 6, on the west boundary of the township, hereinbefore described. Not monumented.

Survey of a Portion of the Subdivision of Section 6,
T. 1 S., R. 1 E., Uintah Special Meridian, Utah

SURVEY OF A PORTION OF THE SUBDIVISION OF SECTION 6,
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

From the center 1/4 section corner of section 6.

N. 0°08.4' E., on the N-S center line of section 6.

9.980 Point for the C-S-N 1/64 section corner of section 6.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a collar of stone, with aluminum cap marked.

S6
C-S-N
1/64
1998

Deposit the magnet at base of aluminum post.

Corner is located in thick river bottom willows and west, 7.3 ft. from a fence extending N and S, and north, 18 ft. from a fence extending E and W.

19.960 The center N 1/16 section corner of section 6.

N. 0°34.9' W., beginning new measurement.

10.095 Point for the C-N-N 1/64 section corner of section 6.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked.

S6
C-N-N
1/64
1998

Deposit the magnet at base of aluminum post.

Set a steel T-Post 1 ft. north of aluminum post.

Corner is located in a pasture, 60 ft. north of a house, and 66 ft. east of a fence extending N and S.

20.390 The 1/4 section corner of section 6 only, on the north boundary of the township, hereinbefore described.

From the center E 1/16 section corner of section 6.

N. 0°06.4' E., on the N-S center line of the NE 1/4.

SURVEY OF A PORTION OF THE SUBDIVISION OF SECTION 6,
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

- 9.970** Point for the C-S-NE 1/64 section corner of section 6.
- Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 15 inches in the ground, in a mound of stone, 3 ft. base, to top of aluminum cap marked.
- S6
C-S-NE
1/64
1998
- Deposit the magnet at base of aluminum post.
- 19.940** The NE 1/16 section corner of section 6.
-
- N. 0°24.9' W., beginning new measurement.
- 10.040** Point for the C-N-NE 1/64 section corner of section 6; not monumented.
- 20.382** The E 1/16 section corner of section 6 only, on the north boundary of the township, hereinbefore described.
-
- From the C-W-NE 1/64 section corner of section 6.
- N. 0°29.9' W., on the N-S center line of the NW 1/4 of the NE 1/4 of section 6.
- 10.067** Point for the NW-NE 1/64 section corner of section 6, at intersection with the E-W center line of the NW 1/4 of the NE 1/4.
- Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked.
- S6
NW NE
1/64
1998
- Deposit the magnet at base of aluminum post.
- Set a steel T-Post 1 ft. north of aluminum post.
- Corner located in a sea of 8 ft. high willows.
- 20.384** Point for the W-E 1/64 section corner of section 6 only, on the north boundary of the township, hereinbefore described; not monumented.
-

SURVEY OF A PORTION OF THE SUBDIVISION OF SECTION 6,
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

- From the point for the C-N-NE 1/64 section corner of section 6; not monumented.
N. 89°45.2' W., on the E-W center line of the NW1/4 of the NE 1/4, of section 6.
- 10.034** The NW-NE 1/64 section corner of section 6.
- 20.069** The C-N-N 1/64 section corner of section 6.
-
- From the C-W-E 1/64 section corner of section 6.
N. 0°07.4' E., on the N-S center line of the SW 1/4 of the NE 1/4 of section 6.
- 9.975** Point for the SW-NE 1/64 section corner of section 6, at intersection with the E-W center line of the SW 1/4 of the NE 1/4.
- Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 16 inches in the ground, in a mound of stone, 4 ft. base, to top of aluminum cap, marked:
- S6
SW NE
1/64
1998
- Deposit the magnet at base of aluminum post.
- Corner is located on a ditch bank, 32.2 ft. NW of a corner of a house and 26.9 ft. from center of head gate valve.
- 19.950** The C-W-NE 1/64 section corner of section 6.
-
- From the C-S-NE 1/64 section corner of section 6.
N. 89°50.6' W., on the E-W center line of the SW 1/4 of the NE 1/4 of section 6.
- 10.023** The SW-NE 1/64 section corner of section 6.
- 20.046** The C-S-N 1/64 section corner of section 6.
-

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Ron Baugh	Cadastral Surveyor
Ross Workman	Cadastral Surveyor
Harvey Pinegar	Survey Aid
Keith Batty	Survey Aid

CERTIFICATE OF SURVEY

I, *Richard L. Houston, Cadastral Surveyor*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *1st day of July, 1998*, I have *dependently resurveyed a portion of the west boundary (Uintah Special Meridian), a portion of the north boundary (Uintah Special Base Line), a portion of the subdivisional lines, and a portion of the subdivision of section 6 by the three mile method, and the survey of a portion of the subdivision of section 6, in T. 1 S., R. 1 E.,*

of the *Uintah Special Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

6/22/2000

Date

Richard L. Houston

(Cadastral Surveyor)

Date

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of a portion of the west boundary (Uintah Special Meridian), a portion of the north boundary (Uintah Special Base Line), a portion of the subdivisional lines, and a portion of the subdivision of section 6 by the three mile method, and the survey of a portion of the subdivision of section 6, in T. 1 S., R. 1 E., Uintah Special Meridian, Utah,*

executed by *Richard L. Houston, Cadastral Surveyor*

having been critically examined and found correct, are hereby approved.

August 3, 2000

Date

Daniel W. Welch

(Chief Cadastral Surveyor for Utah)