

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

A PORTION OF THE EAST BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES,

THE SUBDIVISION OF SECTIONS 25 AND 26,

A PORTION OF LOT NUMBER 48B (HOLDERMAN, ANGEL AND APEX MILLSITES),

AND

MILLSITE NUMBERS 53B AND 54B,

OF

TOWNSHIP 27 SOUTH, RANGE 4 WEST

OF THE SALT LAKE MERIDIAN  
IN THE STATE OF UTAH

EXECUTED BY

*John F. Carroll*  
*Cadastral Surveyor*

Under special instructions dated *February 1, 1999*, approved *February 25, 1999*, which provided for the surveys included under Group Number 896, and assignment instructions dated *February 25, 1999*.

Survey commenced *March 30, 1999*  
Survey completed *June 3, 1999*

# INDEX DIAGRAM

Township 27 South, Range 4 West

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23 11	24 7
30	29	28	27 10	26 5 8	25 3 4
31	32	33	34	35	36

The Subdivision of Section 25.....Page 11  
 The Subdivision of Section 26.....Page 12  
 Lot Number 48B.....Page 13  
 Millsite Number 53B.....Page 21  
 Millsite Number 54B.....Page 24

## TOWNSHIP 27 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

The following field notes describe the dependent resurvey of a portion of the east boundary, a portion of the subdivisional lines, the subdivision of sections 25 and 26, a portion of Lot Number 48B (Holderman, Apex and Angel Millsites), and all of Millsite Nos. 53B and 54B, in Township 27 South, Range 4 West, Salt Lake Meridian, Utah.

NOTE: Millsite Nos. 53B and 54B have been cancelled.

**HISTORY OF EARLIER SURVEYS**

	Surveyed by		Retr. or Resurveyed by	
<b>SOUTH BOUNDARY</b>				
All	J.T. Breckon	1896		
All			Page and Erwin	1900
<b>EAST BOUNDARY</b>				
Portion	J. Gorkinski	1871		
All	J.T. Breckon	1896	J.T. Breckon	1896
Portion			G.E. Reynolds	1989
<b>WEST BOUNDARY</b>				
All	J.T. Breckon	1896		
All			Page and Erwin	1900
<b>NORTH BOUNDARY</b>				
All	J.T. Breckon	1896		
Portion			Page and Erwin	1900
Portion			C.P. Sylvester	1975
<b>SUBDIVISION</b>				
All	J.T. Breckon	1896		
Portion			J.T. Breckon	1905
Portion			C.J. Truscott	1922

**HISTORY OF LOCAL SURVEYS**

In 1979, Allen's Engineering resurveyed the exterior of section 25 and subdivided section 25. This survey is not recorded.

## TOWNSHIP 27 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

## CHAINS

In 1996, Jones & DeMille Engineering resurveyed a portion of the east bdy. of the tp. (sec. 36). This survey is not recorded. This local resurvey recovered several monuments from the 1989 resurvey under Group No. 734.

In 1998, Jones & DeMille Engineering resurveyed a portion of the east bdy. of the tp. (sec. 25), resurveyed portions of the exteriors of secs. 25 and 26, and resurveyed Millsite Number 48B. This local resurvey recovered several monuments from the 1989 resurvey under Group No. 734. This survey was recorded, on May 20, 1998, Piute County Recorders Office, Entry No. 99396.

History of sec. 26:

The first cadastral survey was conducted by J.T. Breckon in 1896 for all the subdivisional lines in T. 27 S., R. 4 W., except he did not tie in previously established Millsites Nos. 48B, 53B, and 54B. Next came the patent by S.C. James in 1899 for the N 1/2 of the SE 1/4 and Lots 1 and 2 in sec. 26, in which the patent used the acreage shown on the 1896 plat at 154.21. This covers all of the SE 1/4 of sec. 26 except for Millsites Nos. 48B and 53B.

When it was discovered that Breckon did not tie in the Millsites, he was sent out in 1905 to resurvey the east 1/2 mile of secs. 26 and 35, and make ties to 5 cors. of the Millsites. When the 1905 plat was drawn, showing the newly tied positions of the Millsites, new lottings were made, incorrectly using the same original lot numbers (1 and 2), but in different quadrants or locations. This is the reason new 1905 Lot 2, which is in the SE 1/4, SW 1/4 was used on the Master Title Plat (MTP), and the old, 1896 Lot 1 was turned back into an aliquot part, and not used as the original location of this H.E. Patent.

The remaining land Bureau of Land Management has in the SE 1/4 of section 26, is Millsite Number 53B (Wedge Millsite), which was never taken to patent along with Millsite 54B. (Chambers Millsite in section 35, Millsites 48B (Holderman, Angel, and Apex) were all patented.

---

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 896, Utah, dated February 1, 1999.

The directions of lines were determined by references to true meridians established by hour angle observations of the sun and Global Positioning System (GPS), utilizing relative positioning techniques. The lines were carried forward by sustained angulations, being supplemented by other observations taken throughout the progress of the survey. Horizontal distances were determined in chains or feet by electronic measurement.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. The retracement data were thoroughly verified and only the true line notes are given herein.

## TOWNSHIP 27 SOUTH, RANGE 4 WEST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

The geographic position of the cor. of secs. 19, 24, 25 and 30, on the east bdy. of the tp., as determined by direct tie to U.S. Coast and Geodetic Survey triangulation station "LAKE", by GPS, utilizing relative positioning techniques, is as follows:

Latitude: 38°20'26.738" N.      Longitude: 112°12'37.916" W.  
N.A.D. 1983

This cor. now functions as a B.L.M. Control Station.

The mean magnetic declination as projected from the U.S. Geological Survey Magnetic Declination Map of 1990 is: 13 1/2° E.

---

Dependent Resurvey of a Portion of the East Boundary  
T. 27 S., R. 4 W., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by J. Gorlinski in 1871,  
and the Resurveys executed by J.T. Breckon in 1896 and  
G.E. Reynolds in 1989

---

\*\*\*\*\*

Note: The position for the cors. on the west boundary of sec. 30, on the west boundary of T. 27 S., R. 3 W., as established during the 1989 resurvey (Gp. No. 734, Utah) do not agree with this resurvey (the overall distance). These monuments have been utilized and recognized by local landowners and local surveyors. Therefore new bearings and distances will be returned on this resurvey for the east bdy. of sec. 25, on the east boundary of T. 27 S., R. 4 W.

\*\*\*\*\*

Beginning at the cor. of secs. 25, 30, 31 and 36, on the east bdy. of the tp., monumented with an aluminum post, 2 1/2 ins. diam., firmly set, 2 ins. below ground, with an aluminum cap mkd. as described in the field notes of the 1989 resurvey record.

From this cor., a rebar, 3/8 in. diam., firmly set, 2 ins. below ground, with plastic cap mkd. LS164561 (Kerrie B. Monroe), bears S. 83°43.6' W., 0.028 chs. dist. This monument was established utilizing incorrect procedures and is not utilized during the course of this resurvey.

Cor. is located in an alfalfa field, South, 110 lks. of a sprinkler irrigation line.

N. 0°58.0' W., between secs. 25 and 30, on the east bdy. of the tp.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY  
T. 27 S., R. 4 W., SALT LAKE MERIDIAN, UTAH

CHAINS	
1.101	<p>East, 0.015 chs. dist., of a rebar, 3/8 in. diam., firmly set, flush with ground, with plastic cap mkd. LS183343 (Ryan W. Savage). This is not a Public Land Survey System cor. and is not utilized during the course of this resurvey.</p>
40.510	<p>The 1/4 sec. cor. of secs. 25 and 30, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground., with aluminum cap mkd. as described in the field notes of the 1989 resurvey record.</p> <p>Cor. is located in bottom land of Pine Creek (commonly known as Bullion Canyon) in cottonwood and pine.</p> <hr/> <p>N. 0°56.3' W., beginning new measurement.</p>
40.048	<p>The cor. of secs. 19, 24, 25 and 30, on the east boundary of the tp., monumented with an aluminum post, 2 1/2 ins. diam. firmly set, projecting 6 ins. above ground, in a collar of stone, with aluminum cap mkd. as described in the field notes of the 1989 resurvey record.</p> <p>Cor. is located on a SE slope in sagebrush, and at the cor. of fences bearing N, E and W.</p> <hr/> <p>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 27 S., R. 4 W., Salt Lake Meridian, Utah</p> <hr/> <p>Reestablishment of the Survey Executed by J.T. Breckon in 1896</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the east boundary of the tp., hereinbefore described.</p> <p>S. 88°35.2' W., bet. secs. 25 and 36.</p>
40.444	<p>The 1/4 sec. cor. of secs. 25 and 36, monumented with a quartzite stone, 18X12X3 ins., firmly set, clearly mkd. 1/4 on north face, with a scattered reference mound of stone to the north.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 23 ins. in the ground with a magnet at base, and in a mound of stone, 2 ft. diam., to top, with aluminum cap mkd.:</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 27 S., R. 4 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T 27 S R 4 W  
S 25  
1/4 —————  
S 36  
1999

Bury mkd. stone north of aluminum post.

Rebuild scattered reference mound to mound of stone around aluminum post.

Cor. is located at the intersection of fences bearing E, S and W, in scattered sagebrush.

---


S. 89°16.9' W., beginning new measurement.

40.546

The cor. of secs. 25, 26, 35 and 36, monumented with a quartzite, 18X8X6 ins., loosely set, clearly mkd. with one notch on the east edge.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 21 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:



Bury mkd. stone along west side of aluminum post.

No undisturbed remains of the original mound of stone was recovered.

Cor. is located in juniper and pinyon pine, and at the intersection of fences bearing north and east.

---

N. 0°37.4' W., bet. secs. 25 and 26.

40.455

The 1/4 sec. cor. of secs. 25 and 26, mon. with a rebar, 1/2 in. diam., firmly set, projecting 3 ins. above ground, with an aluminum cap, 1 1/2 ins. diam., mkd. ALLEN ENG 32 RICHFIELD UT, and is accepted as the best available evidence of the original cor.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 27 S., R. 4 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Note: The original mkd. stone, a sandstone, 10X8X6 ins., clearly mkd. 1/4 on a face, has been displaced and was found lying near the rebar and aluminum cap. The rebar and aluminum cap are accepted as the best available evidence of the original cor.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with a magnet at base, and in a collar of stone, 1 ft. diam., with aluminum cap mkd.:

T 27 S R 4 W  
1/4  
S 26 | S 25  
1999

Deposit rebar and aluminum cap inside aluminum post.

Bury mkd. stone along east side of aluminum post.

Cor. is located in a fence, bears N, S, E, and W, and East, 9 lks. of the center of a dirt road, 9 ft. wide, bears NE and SW.

N. 0°44.5' W., beginning new measurement.

20.219

Point for the N 1/16 sec. cor. of secs. 25 and 26.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, with a magnet at base, and in a collar of stone, 2 ft. diam., to top, with aluminum cap mkd.:

N 1/16  
S 26 | S 25  
1999

Drive a steel fence post alongside aluminum post.

Cor. is located on a gradual North slope in pinyon pine and juniper, and N. 15° W., 22 ft. of a fence, bears E and S.

40.438


The cor. of secs. 23, 24, 25 and 26, monumented with a sandstone, 16X12X6 ins., firmly set, mkd. with 2 notches on the south and 1 notch on the east edges, in a mound of stone, 2 ft. base. (Record; mound of stone west of the mkd. stone)

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 27 S., R. 4 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 23 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 2 ft. diam., to top, with aluminum cap mkd.:



Bury mkd. stone along south side of aluminum post.

Rebuild original mound of stone to 2 ft. base.

Drive a steel fence post alongside aluminum post.

Cor. is located on a north slope in sagebrush and scattered juniper.

---


From the cor. of secs. 19, 24, 25 and 30, on the east bdy. of the tp., hereinbefore described.

S. 89°10.3' W., bet. secs. 24 and 25.

40.294

Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate dist., there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 21 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:



Drive a steel fence post alongside aluminum post.

From this point, an unrecorded rebar, 5/8 in. diam., firmly set, with aluminum cap mkd. ALLEN ENGINEERING 24 RICHFIELD UT, bears S. 0°34.2' W., 0.453 chs. dist. This monument was set using incorrect procedures and was not utilized during the course of this resurvey.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 27 S., R. 4 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Cor. is located on a gradual south slope in grass and scattered sagebrush.

80.588

The cor. of secs. 23, 24, 25 and 26.

---

Reestablishment of the Survey executed by J.T. Breckon in 1896  
and the Resurvey in 1905

---

From the cor. of secs. 25, 26, 35 and 36.

S. 89°33.2' W., bet. secs. 26 and 35.

40.359

The 1/4 sec. cor. of secs. 26 and 35, is determined at record distances from the remains of Post Number 8, Lot Number 48B, Angel Millsite, and Post Number 3, Lot Number 48B, Holderman Millsite, falls in a slide area where it is impractical to set a standard BLM monument, from this point

Post Number 3, Lot 48B, Holderman Millsite, monumented with a rebar, 5/8 in. diam., firmly set, projecting 4 ins. above ground, with plastic cap mkd. LS183343 (Ryan W. Savage), in an embedded mound of stone, 3 ft. base, bears S. 68°34.3' W., 1.44 chs. dist., and is accepted as a careful and faithful perpetuation of the original cor. (Record; S. 67°51' W.) Note: Laying nearby is a pine post, 4 ins. square, x 4 ft long, with the mark P3 visible and illegible scribe marks visible. Note: The rebar and plastic cap were recorded on May 20, 1998, Entry Number 99396, Piute County Recorders office.

From this same point, Post Number 8, Lot Number 48B, Angel Millsite, monumented with a rebar, 5/8 in. diam., firmly set, projecting 4 ins. above ground, with plastic cap mkd. LS183343 (Ryan W. Savage), in an embedded mound of stone, 3 ft. base, bears S. 59°22.1' W., 8.02 chs. dist. and is accepted as a careful and faithful perpetuation of the original cor. (Record; S. 67°51' W.) Note: Laying nearby is a pine post, 4 ins. square, X 2 ft. long, with no marks visible. Note: The rebar and plastic cap were recorded on May 20, 1998, Entry Number 99396, Piute County Recorders office.

From this same point, a reference monument, set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 21 ins. in the ground with a magnet at base, and in a mound of stone, 2 1/2 ft. diam., to top, with aluminum cap mkd.: RM T27SR4W1/4S35 1999, and an arrow pointing to the cor., bears S. 67°11.5' W., 0.615 chs. dist. Reference monument is located on a gradual northerly slope in scrub oak, juniper and pine.

Cor. is located on a steep northerly slope, in a slide area, and in scrub oak, juniper and pine.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 27 S., R. 4 W., SALT LAKE MERIDIAN, UTAH

CHAINS

---

Reestablishment of the Survey executed by J.T. Breckon in 1896

---

S. 89°39.9' W., beginning new measurement.

0.520

Intersect line 3-4, Lot Number 48B, Holderman Millsite.

1.671

Intersect line 3-12, Lot Number 48B, Holderman Millsite.

3.358

Intersect line 11-12, Lot Number 48B, Apex Millsite.

14.705

Intersect line 5-6, Lot Number 48B, Angel Millsite.

40.727

The cor. of secs. 26, 27, 34 and 35, monumented with a conglomerate stone, 14X10X10 ins., clearly mkd. with one notch on the north and 2 notches on the east edges, loosely set, in a mound of stone, (Record; no mound of stone)

from which the original bearing trees

A pine, dead and standing, 11 ins. diam., bears N. 13° E., 20 lks. dist., with illegible scribe marks visible on a partially healed blaze. (Record; 19 lks. dist.)

A cedar branch, 6 ins. diam., bears S. 21 1/2° E., 21 lks. dist., with the marks T27SR4WS35BT visible on a partially healed blaze. (Record; 16 lks. dist.)

A pine, 6 ins. diam., bears S. 77° W., 11 lks. dist., with the marks T27SR4WS34BT visible on a partially healed blaze.


A pine, 9 ins. diam., bears N. 29° W., 27 lks. dist., with illegible scribe marks visible on a partially healed blaze.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 4 ft. diam., to top, with aluminum cap mkd.:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 27 S., R. 4 W., SALT LAKE MERIDIAN, UTAH

CHAINS



Bury mkd. stone along westside of aluminum post.

Rebuild original mound of stone to 4 ft. diam.,

Drive a steel fence post alongside aluminum post.

Cor. is located in cedar and pinyon pine.

---

Reestablishment of the Survey Executed by J.T. Breckon in 1896  
and the Resurvey by C.J. Truscott in 1922

---

N. 0°14.6' W., bet. secs. 26 and 27.


38.213

The 1/4 sec. cor. of secs. 26 and 27, monumented with a sandstone, 24X8X6 ins., firmly set, clearly mkd. 1/4 on west face, in a mound of stone, 3 ft. diam. (1922 Record; mound of stone to the west)

No remaining evidence of the 1922 bearing trees was recovered.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:



Bury mkd. stone on north side of aluminum post.

Rebuild 1922 mound of stone to 3 ft. diam.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 27 S., R. 4 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Cor. is located on a north slope in juniper and pinyon pine, and West, 3 lks. dist. of a fence, bears N and SE.

---

Reestablishment of the Survey executed by J.T. Breckon in 1896

---

From the cor. of secs. 23, 24, 25 and 26.

S. 89°28.7' W., bet. secs. 23 and 26.

40.201

The 1/4 sec. cor. of secs. 23 and 26, monumented with a trachyte, 13X12X4 ins., loosely set, with no mks. visible, in a scattered mound of stone, 2 ft. diam. (Record; mound of stone to the north)

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with a magnet at base, and in a collar of stone, 2 ft. diam., to top, with aluminum cap mkd.:

T 27 S R 4 W  
S 23  
1/4 —————  
S 26  
1999

Bury the unmarked stone along westside of aluminum post.

Rebuild scattered original mound to a collar of stone.

Drive a steel fence post alongside aluminum post.

Cor. is located on a gradual north slope in juniper.

---

The Subdivision of Section 25,  
T. 27 S., R. 4 W., Salt Lake Meridian, Utah

---

From the 1/4 sec. cor. of secs. 25 and 36.

N. 0°51.3' W., on the N-S centerline of sec. 25.

THE SUBDIVISION OF SECTION 25,  
T. 27 S., R. 4 W., SALT LAKE MERIDIAN, UTAH

CHAINS

40.728 Point for the center 1/4 sec. cor. at intersection with the E-W center line of sec. 25, falls in a private driveway. Not monumented.

60.849 Point for the center N 1/16 sec. cor. of sec. 25.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, with a magnet at base, with aluminum cap mkd.:

C  
N 1/16 | S 25  
C  
1999

From this point, a steel fence post, bears South, 0.090 chs. dist.

Cor. is located in a dry pond, and NE, 15 ft., from the intersection of fences, bears N, S, and W.

80.970 The 1/4 sec. cor. of secs. 24 and 25.

---

From the 1/4 sec. cor. of secs. 25 and 30, on the east bdy. of the tp., hereinbefore described.

S. 88°53.7' W., on the E-W center line of sec. 25.

40.357 True point for the center 1/4 sec. cor. of sec. 25.

80.735 The 1/4 sec. cor. of secs. 25 and 26.

---

From the center N 1/16 sec. cor. of sec. 25.

S. 89°02.0' W., on the E-W center line of the NW 1/4 of sec. 25.

40.336 The N 1/16 sec. cor. of secs. 25 and 26.

---

The Subdivision of Section 26,  
T. 27 S., R. 4 W., Salt Lake Meridian, Utah

---

From the true point for the 1/4 sec. cor. of secs. 26 and 35.


THE SUBDIVISION OF SECTION 26,  
T. 27 S., R. 4 W., SALT LAKE MERIDIAN, UTAH

CHAINS	
	N. 0°34.6' W., on the N-S center line of sec. 26.
<b>0.327</b>	Intersect line 3-4, Lot Number 48B, Holderman Millsite.
<b>9.270</b>	Intersect line 1-2, Lot Number 48B, Holderman Millsite.
<b>39.375</b>	Point for the center 1/4 sec. cor. at intersection with the E-W center line of sec. 26.  Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, with a magnet at base, and in a supporting mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:
	T 27 S R 4 W C 1/4 S 26 1999
	Cor. is located on a gradual south slope in juniper and pinyon pine, South, 1 ch. dist. of a fence, bearing E and W.
<b>80.838</b>	The 1/4 sec. cor. of secs. 23 and 26. <hr/>
	From the 1/4 sec. cor. of secs. 25 and 26.  S. 88°01.3' W., on the E-W center line of sec. 26.
<b>40.334</b>	The center 1/4 sec. cor. of sec. 26.
<b>80.847</b>	The 1/4 sec. cor. of secs. 26 and 27. <hr/>
	Dependent Resurvey of a Portion of Lot Number 48B (Holderman, Angel and Apex Millsites) <hr/>
	Reestablishment of a Portion of the Survey Executed by A. Jessen in 1892 <hr/>
	From Post Number 1, Lot Number 48B, Holderman Millsite, monumented with an axe hewn pine post, 4X4X15 ins. long, firmly set, projecting 2 ins. above ground, with no marks visible.  At the corner point

THE SUBDIVISION OF SECTION 26,  
T. 27 S., R. 4 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:



Bury pine post on south side of aluminum post.

No remains of the bearing trees were recovered.

Drive a steel fence post alongside aluminum post.

From this point, a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above ground, with plastic cap mkd. LS183343, bears N. 71°24.0' E., 1.44 ft. dist., recorded on May 20, 1998, Piute County Recorders office, Entry Number 99396. This monument was set using incorrect procedures and is not utilized during the course of this resurvey.

Cor. is located on a steep southerly slope in juniper and scattered pine.

S. 57°22.8' W., on line 1-2, Lot 48B, Holderman Millsite.

**0.255** Intersect the N-S center line of sec. 26.

**6.582** Post Number 2, Lot Number 48B, Holderman Millsite, identical with a portion of the north easterly boundary of Lot 48B, Apex Millsite, monumented with a rebar, 5/8 in. diam., firmly set, projecting 3 ins. above ground, with plastic cap mkd. LS183343, recorded on May 20, 1998, Piute County Recorders office, Entry Number 99396, and is accepted as a careful and faithful reestablishment of the original cor. Not remonumented.

---

N. 32°41.3' W., on line 2-9, Lot Number 48B, Apex Millsite, beginning new measurement.

**1.455** Post Number 9, Lot Number 48B, Apex Millsite, monumented with a pine post, 4X4X15 ins. high, firmly set, with no marks visible, in an embedded mound of stone, 3 ft. base, with a rebar, 5/8 in. diam., firmly set, projecting 4 ins. above ground, with plastic cap mkd. LS183343, recorded on May 20, 1998, Piute County Recorders office, on the north side of the pine post. Not remonumented.

DEPENDENT RESURVEY OF A PORTION OF LOT NUMBER 48B,  
 (HOLDERMAN, ANGEL AND APEX MILLSITES)  
 T. 27 S., R. 4 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

No remaining evidence of the original bearing trees was recovered.

Cor. is located on a south slope in juniper and pine.

---


S.  $57^{\circ}27.8'$  W., on line 9-10, Lot Number 48B, Apex Millsite, beginning new measurement.

6.589

Post Number 10, Lot Number 48B, Apex Millsite, monumented with a pine post, 4X4X8 ins. high, firmly set, with no marks visible, in a mound of stone, 4 ft. diam., with a rebar, 5/8 in. diam., projecting 3 ins. above ground, with plastic cap mkd. LS183343, recorded on May 20, 1998, Piute County Recorders office, on the north side of the pine post.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:



1999

Bury original pine post on south side of aluminum post.

Bury rebar and plastic cap inside aluminum post.

Rebuild original mound of stone to 3 ft. diam.

Drive a steel fence post alongside aluminum post.

Cor. is located on a south slope in juniper and pine.

---

S.  $32^{\circ}11.5'$  E., on line 10-5, Lot Number 48B, Apex Millsite, beginning new measurement.

DEPENDENT RESURVEY OF A PORTION OF LOT NUMBER 48B,  
 (HOLDERMAN, ANGEL AND APEX MILLSITES)  
 T. 27 S., R. 4 W., SALT LAKE MERIDIAN, UTAH


## CHAINS

1.467

Post Number 5, Lot Number 48B, Angel Millsite, identical with a portion of the southwest boundary of Lot Number 48B, Apex Millsite, monumented with a rebar, 5/8 in. diam., firmly set, projecting 3 ins. above ground, with plastic cap mkd. LS183343, recorded on May 20, 1998, Piute County Recorders office, Entry Number 99396, and is accepted as a careful and faithful reestablishment of the original cor., falls on the north edge of a dirt road, 15 ft. wide, and at the base of a cut bank.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground with a magnet at base, with aluminum cap mkd.:



Bury rebar and plastic cap inside aluminum post.

Cor. is located on the north edge of a dirt road, 15 ft. wide, and at the base of a cut bank.

S. 57°24.5' W., on line 5-6, Lot Number 48B, Angel Millsite, beginning new measurement.

4.421

Intersect the boundary bet. secs. 26 and 35.

6.601

Post Number 6, Lot Number 48B, Angel Millsite, identical with Post 1, Millsite 54B, monumented with a nail, firmly set, flush with road surface, recorded on May 20, 1998, Piute County Recorders office, Entry Number 99396, and is accepted as a faithful and careful reestablishment of the original cor.

from which

A rebar, 5/8 in. diam., firmly set, projecting 3 ins. above ground, with plastic cap mkd. LS183343, recorded on May 20, 1998, Piute County Recorders office, Entry Number 99396, bears S. 32°38.7' E., 20.02 ft. dist. This rebar and plastic cap will now function as a reference monument. Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with a magnet at base, and in a mound of stone, 3 ft. diam. to top, with aluminum cap mkd. T27SR4W RM AMS 48B 6 TO COR 1999 and an arrow pointing to the cor. Bury rebar and plastic cap on south side of aluminum post. Cor. is located on a road fill, South, 10 ft., from the center of a dirt road, 17 ft. wide, bears NE and SW.

THE SUBDIVISION OF SECTION 26,  
T. 27 S., R. 4 W., SALT LAKE MERIDIAN, UTAH

CHAINS


S. 32°54.4' E., on line 6-7, Lot 48B, Angel Millsite, identical with line 1-4, Millsite 54B, beginning new measurement.

7.595

Post Number 7, Lot 48B, Angel Millsite, identical with Post Number 4, Millsite 54B, monumented with a rebar, 5/8 in. diam., firmly set, projecting 3 ins. above ground, with plastic cap mkd. LS183343, recorded on May 20, 1998, Piute County Recorders office, Entry Number 99396, in an embedded mound of stone, 3 ft. diam., and is accepted as a careful and faithful perpetuation of the original cor.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 19 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 4 ft. diam., to top, with aluminum cap mkd.:



Bury rebar and plastic cap along west side of aluminum post.

Note: The remains of the original pine post, 4X4X15 ins. long, clearly mkd. P on one side, was found laying near the embedded mound of stone. Bury the remains of the original pine post on the north side of the aluminum post.

No remaining evidence of the original bearing trees was recovered.

Drive a steel fence post alongside aluminum post.

Cor. is located on a steep northerly slope in scrub oak and scattered pine.

N. 57°13.4' E., on line 7-8, Lot 48B, Angel Millsite, beginning new measurement.

5.563

Local point-on-line, monumented with a rebar, 5/8 in. diam., firmly set, projecting 5 ins. above ground, with plastic cap mkd. LS183343, recorded on May 20, 1998, Piute County Recorders office, Entry Number 99396. Not remonumented.

Cor. is located on a steep northerly slope in scrub oak and pine.

THE SUBDIVISION OF SECTION 26,  
T. 27 S., R. 4 W., SALT LAKE MERIDIAN, UTAH


CHAINS

6.560

Post Number 8, Lot Number 48B, Angel Millsite, monumented with a rebar, 5/8 in. diam., firmly set, projecting 4 ins. above ground, with plastic cap mkd. LS183343, recorded on May 20, 1998, Piute County Recorders office, in an embedded mound of stone, and is accepted as a careful and faithful perpetuation of the original cor.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 19 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:



Bury rebar and plastic cap inside of aluminum post.

Note: The remains of the original pine post, 4X4X24 ins. long, with no marks visible, was found laying near the embedded mound of stone. Bury the remains of the original pine post on the north side of the aluminum post.

No remaining evidence of the original bearing trees was recovered.

Drive a steel fence post alongside aluminum post.

Cor. is located on a steep northerly slope in scrub oak and pine.

---

N. 32°37.6' W., on line 8-5, Lot Number 48B, Angel Millsite, beginning new measurement.

1.514


Post Number 11, Lot Number 48B, Apex Millsite, on the northeast side of Lot Number 48B, Angel Millsite, monumented with a rebar, 5/8 in. diam., firmly set, projecting 4 ins. above ground, with plastic cap mkd. LS183343, recorded on May 20, 1998, Piute County Recorders office, Entry Number 99396, and is accepted as a faithful and careful reestablishment of the original cor.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground with a magnet at base, with aluminum cap mkd.:

THE SUBDIVISION OF SECTION 26,  
T. 27 S., R. 4 W., SALT LAKE MERIDIAN, UTAH

CHAINS



Bury rebar and plastic cap inside aluminum post.

Drive a steel fence post alongside aluminum post.

Cor. is located on a flat in pine, cottonwood and birch.

---


N. 57°22.4' E., on line 11-12, Lot Number 48B, Apex Millsite, beginning new measurement.

**5.177** Intersect the sec. line bet. secs. 26 and 35.

**5.591** Local point-on-line, monumented with a rebar, 5/8 in. diam., firmly set, projecting 5 ins. above ground, with plastic cap mkd. LS183343, recorded on May 20, 1998, Piute County Records office, Entry Number 99396. Not remonumented.

**6.602** Post Number 12, Lot Number 48B, Apex Millsite, on the southwest side of Lot No. 48B, Holderman Millsite, monumented with a rebar, 5/8 in. diam., firmly set, projecting 4 ins. above ground, with plastic cap mkd. LS183343, recorded on May 20, 1998, Piute County Records office, Entry Number 99396, and is accepted as a faithful and careful reestablishment of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 21 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:



Bury rebar and plastic cap inside aluminum post.

Drive a steel fence post alongside aluminum post.

THE SUBDIVISION OF SECTION 26,  
T. 27 S., R. 4 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Cor. is located on a flat in willow, birch and pine.

---

S. 32°38.9' E., on line 2-3, Lot Number 48B, Holderman Millsite, beginning new measurement.

**0.901**

Intersect the sec. line bet. secs. 26 and 35.

**1.515**

Post Number 3, Lot Number 48B, Holderman Millsite, monumented with a rebar, 5/8 in. diam., firmly set, projecting 4 ins. above ground, with plastic cap mkd. LS183343, recorded on May 20, 1998, Piute County Recorders office, in an embedded mound of stone, and is accepted as a careful and faithful perpetuation of the original cor.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 19 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 2 ft. diam., to top, with aluminum cap mkd.:



1999

Bury rebar and plastic cap on south side of aluminum post.

Note: The remains of the original pine post, 4 ins. X 4 ins. X 4 ft. long, with scribe marks P3 visible on one side and illegible scribe marks visible on another side, was found laying near the embedded mound of stone. Bury the remains of the original pine post on the south side of the aluminum post.

No remaining evidence of the original bearing trees was recovered.

Drive a steel fence post alongside aluminum post.

Cor. is located on a north slope in scrub oak, fir and pine.

---

N. 57°26.0' E., on line 3-4, Lot Number 48B, Holderman Millsite, beginning new measurement.

**0.973**

Intersect the sec. line bet. secs. 26 and 35.

DEPENDENT RESURVEY OF A PORTION OF LOT NUMBER 48B,  
 (HOLDERMAN, ANGEL AND APEX MILLSITES)  
 T. 27 S., R. 4 W., SALT LAKE MERIDIAN, UTAH

CHAINS

1.587

Intersect the N-S center line of sec. 26.

6.635

Post Number 4, Lot Number 48B, Holderman Millsite, monumented with a pine post, 4X4X42 ins. high, firmly set, with scribe marks BP4 visible on the northwest face, in a mound of stone, 3 ft. diam., with a rebar, 5/8 in. diam., firmly set, with plastic cap mkd. LS183343, recorded on May 20, 1998, Piute County Recorders office, Entry Number 99396, on the south side of the pine post, from which the remains of the original bearing trees

A pine stump, 15 ins. diam., 36 ins. high, bears N. 68°52.5' E., 39.8 ft. dist. to the face of the pine stump, no marks visible. (Record; 24 ins. diam., N. 87°30'E., 48 ft. dist.)

A burned pine stump, 27 ins. diam., 15 ft. high, bears S. 0°32.2' E., 16.9 ft. dist. to face of pine stump. (Record; 30 ins. diam., S. 19°15' E., 35 ft.)

Not remonumented.

Cor. is located on a flat bench, South, 53 ft. dist. of Pine Creek, 6 ft. wide, flows SE.

---

N. 32°59.3' W., on line 4-1, Lot Number 48B, Holderman Millsite, beginning new measurement.

6.447

Point for Post Number 1, Lot Number 53B, (Wedge Millsite, canceled) at proportionate distance; hereinafter described.

From this point, the southwest cor. of a cabin, bears S. 55°28.6' E., 3.458 chs. dist., long side bears N. 35° W., 41 feet distance and N. 55° E., 23 feet distance.

7.585

Post Number 1, Lot Number 48B, Holderman Millsite, point of beginning.

---

Dependent Resurvey of Lot Number 53B  
 (Wedge Millsite, Canceled)

---

Reestablishment of the Survey Executed by  
 A. Jessen in 1892

---

From Post Number 4, Lot Number 48B, Holderman Millsite.

S. 28°13.4' E., on a portion of line 1-4, Lot Number 53B.

DEPENDENT RESURVEY OF LOT NUMBER 53B,  
(WEDGE MILLSITE, CANCELED)  
T. 27 S., R. 4 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

0.876

The point for Post Number 4, Lot Number 53B, determined at record bearing and dist. from the remains of the original northeast bearing tree

A pine stump, 15 ins. diam., 36 ins. high, bears N. 8°30' E., 65 ft. dist. to the record diam. face position of the pine stump, no marks visible. (Record; 24 ins. diam.)

A burned pine stump, 27 ins. diam., 15 ft. high, bears N. 38°18.5' W., 42.09 ft. dist. to face of pine stump, with the bark scribe marks USL5IIIIPP4BT clearly visible. This bearing tree is leaning heavily to the southeast, and is in a slide area, and is not utilized to establish Post Number 4, Lot Number 53B. (Record; 30 ins. diam., N. 48°30' W., 40 ft.)

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 2 ft. diam., to top, with aluminum cap mkd.:



1999

Drive a steel fence post alongside aluminum post.

Cor. is located on a steep northerly slope in scrub oak, aspen and scattered pine.


---

N. 59°40.1' E., on line 4-3, Lot Number 53B, beginning new measurement.

6.450

Point for Post Number 3, Lot Number 53B, at proportionate dist., utilizing the grant boundary method of cor. restoration, there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 19 ins. in the ground to bedrock with a magnet at base, and in a supporting mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:



1999

DEPENDENT RESURVEY OF LOT NUMBER 53B,  
(WEDGE MILLSITE, CANCELED)  
T. 27 S., R. 4 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

Drive a steel fence post alongside aluminum post.

Cor. is located on an abandoned dirt road, 10 ft. wide, bears N. 70° E. and S. 70° W., and South, 30 ft. dist. of Pine Creek (commonly known as Bullion Canyon), 10 ft. wide, flows NE.

---

N. 30°19.9' W., on line 3-2, Lot Number 53B.

7.404


Point for Post 2, Lot Number 53B, determined at record bearing and distance from the northeast bearing tree

A pine, 12 ins. diam., bears N. 45° E., 57 ft. dist., to the face of a partially healed face blaze, with ancient chop marks visible, no scribe marks visible.

Note: No remaining evidence of the other original bearing tree was recovered.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 23 ins. in the ground with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:



1999

Cor. is located on a gradual southerly slope in pine and juniper, North, 30 ft. off a dirt road, 20 ft. wide, bears NE and SW.

---

S. 58°54.8' W., on line 2-1, Lot Number 53B.


6.717

Point for Post 1, Lot Number 53B, at proportionate point on line 1-4, Lot Number 48B, Holderman Millsite.

Set a rebar, 18 ins. long, 5/8 in. diam., 20 ins. in the ground, with aluminum cap mkd.:

DEPENDENT RESURVEY OF A PORTION OF LOT NUMBER 54B,  
 (CHAMBERS MILLSITE, CANCELED)  
 T. 27 S., R. 4 W., SALT LAKE MERIDIAN, UTAH

CHAINS



Drive a steel fence post alongside aluminum post.

Cor. is located on a flat area in pine and juniper, and North, 15 ft. of a dirt road, 18 ft. wide, bears NE and SW.

---

Dependent Resurvey of a Portion of Lot Number 54B  
 (Chambers Millsite, Cancelled)

---

Reestablishment of the Survey Executed by  
 A. Jessen in 1892

---

From Post Number 6, Lot Number 48B, Angel Millsite, identical with Post 1, Lot Number 54B. (Chambers Millsite, cancelled).

S.  $63^{\circ}09.3'$  W., on line 1-2, Lot Number 54B.

6.457

Post Number 2, Lot Number 54B, monumented with 4 ins. X 4 ins. X 2 ft. high hewn pine branch, clearly mkd. P2 on the east and USL54B on the south faces. This is a twin forked pine. The west fork is 12 ins. diam. The east fork (Post Number 2, Lot Number 54B), begins 18 ins. above ground on the east face of the west fork, and protrudes at a northeast angle from the west fork. The east fork is beginning to rot at the base. For that reason an aluminum post was set at the base of the west fork (on the east face) and directly underneath the east fork. (Record; pine post, 4 ins. X 4 ins. X 4 ft. high)

No remaining evidence of the original bearing trees were recovered.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

DEPENDENT RESURVEY OF A PORTION OF LOT NUMBER 54B,  
 (CHAMBERS MILLSITE, CANCELED)  
 T. 27 S., R. 4 W., SALT LAKE MERIDIAN, UTAH

CHAINS



1999

Cor. is located on a steep southerly slope in pinyon pine and juniper.

---

S. 29°38.7' E., on line 2-3, Lot Number 54B, beginning new measurement.

7.898

Point for Post Number 3, Lot Number 54B, at proportionate dist., utilizing the grant boundary method of cor. restoration, there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, with a magnet at base, and in a supporting mound of stone, 5 ft. diam., to top, with aluminum cap mkd.:



1999

Cor. is located on a very steep north slope in scrub oak, aspen and scattered pine.

---

N. 60°21.3' E., on line 3-4, Lot Number 54B, beginning new measurement.

6.881

Post Number 7, Lot Number 48B, Angel Millsite, identical with Post Number 4, Lot Number 54B, hereinbefore described.

---

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD ASSISTANTS**

---

Name	Capacity
Max L Sevy	Volunteer (Retired Supervisory Cadastral Surveyor)

---

## CERTIFICATE OF SURVEY

I, *John F. Carroll, Cadastral Surveyor*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *1st day of February, 1999*, I have *dependently resurveyed a portion of the east boundary, a portion of the subdivisional lines, the subdivision of sections 25 and 26, a portion of Lot Number 48B (Holderman, Angel and Apex Millsites), Lot Number 53B, and Lot Number 54B of Township 27 South, Range 4 West,*

of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

6/5/2000

Date

John F. Carroll

(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of a portion of the east boundary, a portion of the subdivisional lines, the subdivision of sections 25 and 26, a portion of Lot Number 48B (Holderman, Angel and Apex Millsites), Lot Number 53B, and Lot Number 54B of Township 27 South, Range 4 West,*

executed by *John F. Carroll, Cadastral Surveyor*

having been critically examined and found correct, are hereby approved.

June 13, 2000

Date

Daniel W. Webb

(Chief Cadastral Surveyor for Utah)